

NAME

t1unmac – translate a Mac PostScript Type 1 font into PFA or PFB format

SYNOPSIS

t1unmac [-a|-b] [-r] [*input* [*output*]]

DESCRIPTION

t1unmac extracts POST resources from a Macintosh PostScript font file and creates a PFA (hexadecimal) or PFB (binary) font file. The file *input* should be in MacBinary I or II, AppleSingle, AppleDouble, or BinHex format, or it can be a raw resource fork. If the file is a raw resource fork, you need to give the ‘--raw’ option; otherwise **t1unmac** should automatically figure out what kind of file you have. If the file *output* is not specified output goes to the standard output.

OPTIONS

--pfa, -a

Output in PFA (ASCII) format.

--pfb, -b

Output in PFB (binary) format. This is the default.

--raw, -r

Indicates that the input is a raw resource fork.

--macbinary

Indicates that the input is in MacBinary I or II format.

--applesingle

Indicates that the input is in AppleSingle format.

--appledouble

Indicates that the input is in AppleDouble format.

--binhex

Indicates that the input is in BinHex 4.0 format.

--block-length=num, -l num

PFB only: Set the maximum output block length to *num*. The default length is as large as memory allows.

--line-length=num, -l num

PFA only: Set the maximum length of encrypted lines in the output to *num*. (These are the lines consisting wholly of hexadecimal digits.) The default is 64.

EXAMPLES

On Mac OS X, you can use **t1unmac** to translate a font into PFA or PFB format as follows:

% **t1unmac** --raw FONTFILENAME/..namedfork/rsrc > OUTPUT

SEE ALSO

t1mac(1), **t1ascii(1)**, **t1binary(1)**, **t1asm(1)**, **t1disasm(1)**

AUTHORS

Lee Hetherington (ilh@lcs.mit.edu)

Eddie Kohler (ekohler@gmail.com)

Ported to Microsoft C/C++ Compiler and MS-DOS operating system by Kai-Uwe Herbing (herbing@netmbx.netmbx.de).