Lwarp

LaTeX HTML5

The lwarp package

LaTeX to HTML

v0.76 — 2019/10/08

© 2016–2019 Brian Dunn
bd@BDTechConcepts.com

Abstract

The lwarp package converts LaTeX to HTML by using LaTeX to process the user's document and directly generate HTML tags. External utility programs are only used for the final conversion of text and images. Math may be represented by SVG images or MathJax. Hundreds of LaTeX packages are supported.

Documents may be produced by DVI or PDF LaTeX, LuaLaTeX, XeLaTeX; by several CJK engines, classes, and packages; or by customized systems such as perltex and pythontex. A *texlua* script automates compilation, index, glossary, and batch image processing, and also supports *latexmk*. Configuration is semi-automatic at the first manual compile. Support files are self-generated. Print and HTML versions of each document may coexist.

Assistance is provided for HTML import into EPUB conversion software and word processors.

Requirements include the commonly-available Poppler utilities (included with MiKTeX) and Perl. Detailed installation instructions are included for each of the major operating systems and TeX distributions.

A quick-start tutorial is provided, as well as extensive documentation for special cases, a general index, and a troubleshooting index. Automatic error testing is provided for configuration files, package load order, and image generation.

SVG math and many other generated images include LaTeX expressions in the `alt` tags. MathJax may be used with advanced equation numbering under the direct control of lwarp.

Complicated tables are supported, which copy/paste well into LibreOffice Writer.

Supported classes and packages include memoir and koma-script, cleveref, caption, mdframed, siunitx, and many popular packages for tabulars, floats, graphics, theorems, the title page, bibliography, indexing, footnotes, and editorial work.

TeX is a self-modifying tokenized macro-expansion language. Since lwarp is written directly in LaTeX, it is able to interpret the document's meaning at a deeper level than external conversions which merely approximate TeX. HTML5 and CSS3 are leveraged to provide advanced features such as booktabs trim, multicolumns, side-by-side minipages, and JavaScript-free navigation.

For a list of supported features, see table 2: Supported packages and features.

To update existing projects, see section 1: Updates.

Lwarp is still in development. Changes are likely.

License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in http://www.latex-project.org/lppl.txt and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

Support TEX development

TEX and related projects:

- are mostly open-sourced and a volunteer effort;
- benefit students, academics, scientists, engineers, and businesses;
- help drive education, public and private research, and commercial activity;
- are used in the fields of mathematics, science, engineering, and humanities;
- are international in reach;
- span decades of development;
- are enduring — many older packages are still actively used and maintained;
- are largely backwards compatible;
- are portable across all the major computing platforms;
- are usable even on older computers and away from internet access;
- are continuing to maintain relevance with modern improvements;
- require no yearly subscription fees;
- and are supported by an active community of knowledgeable volunteers.

Please consider helping by joining and/or contributing to the TEX Users Group, a United States 501(c)(3) tax-exempt charitable organization. Contributions are accepted by credit card, check, or Pay Pal, via the United Way, or by USA or European bank transfer. Membership in TUG supports the development of TEXLive, the major TEX distribution.

Donations may be directed towards individual projects:

TUG Bursary Fund: Assistance for attending annual TUG meetings.
CTAN: The Comprehensive TEX Archive Network — Central storage for TEX.
TeX Development Fund: Support for specific projects.
EduTeX: Teaching and using TEX in schools and universities.
GUST e-foundry fonts: Enhanced for math and additional language groups.
LaTeX Project: Modernizing the LATEX core.
Libre Font Fund: Fonts, tools (FontForge), and distribution (the Open Font Library).
LuaTeX: Combining the pdfTEX engine and the Lua language.
MetaPost: Postscript graphics.
MacTeX: TEX for Mac.
PDF Accessibility: Modern PDF standards.
Other: Additional projects may be specified.

To make a contribution: https://www.tug.org/donate.html

For country-specific TEX users groups: http://tug.org/usergroups.html

For users of MiKTEX: https://miktex.org/donations.html

Contents

Support TEX development **2**

List of Figures **38**

List of Tables **38**

1 Updates **39**

2 Introduction **61**

2.1 Typesetting conventions 63

2.2 Supported packages and features 64

3 Alternatives **70**

3.1 internet class 70

3.2 TEX4HT 70

3.3 Translators 70

3.4 AsciiDoc and Asciidoctor 71

3.4.1 Asciidoctor-LATEX 71

3.5 Pandoc 71

3.6 Word processors 71

3.7 Commercial systems 71

3.8 Comparisons 71

4 Installation **73**

4.1 Installing the lwarp package 75

4.2 Installing the *lwarpmk* utility 76

4.2.1 Using a local copy of *lwarpmk* 78

4.3 Installing additional utilities 78

5 Tutorial **80**

5.1 Starting a new project 80

5.2 Compiling the print version with *lwarpmk* 84

5.3 Compiling the HTML version with *lwarpmk* 85

5.4 Generating the SVG images 86

5.5 Using MathJax for math 87

5.6 Changing the CSS style . . . 88
5.7 Customizing the HTML output . . . 88
5.8 Using *latexmk* . . . 89
5.9 Using XeLaTeX or LuaLaTeX . . . 90
5.10 Using DVI LaTeX . . . 90
5.11 Using a glossary . . . 91
5.11.1 gloss package . . . 91
5.11.2 glossaries package . . . 91
5.12 Cleaning auxiliary files . . . 92
5.13 Cleaning auxiliary and output files . . . 92
5.14 Cleaning the images from the `<project>-images` directory . . . 92
5.15 Converting PDF or EPS images to SVG . . . 92
5.16 Creating HTML from an incomplete compile . . . 92
5.17 Processing multiple projects in the same directory . . . 92
5.18 Using the *make* utility . . . 93
5.19 What next? . . . 94
6 Converting an existing document . . . 95
7 Additional details . . . 96
7.1 Localization . . . 96
7.2 Accessibility . . . 96
7.3 Shell escape . . . 97
7.4 Font and UTF-8 support . . . 97
7.4.1 Indexes, glossaries, and encoding . . . 99
7.5 lwarp package loading and options . . . 100
7.6 Customizing the HTML output . . . 105
7.6.1 Example HTML file naming . . . 111
7.7 Customizing the CSS . . . 112
7.8 Selecting the operating system . . . 113
7.9 Selecting actions for print or HTML output . . . 113
7.10 Commands to be placed into the `warpprint` environment . . . 114

7.11 Title page . . . 115
7.12 HTML page meta descriptions . . . 115
7.13 HTML homepage meta title . . . 116
7.14 HTML page meta author . . . 116
8 Special cases and limitations . . . 116
8.1 Things to avoid . . . 117
8.1.1 Invalid HTML . . . 117
8.2 Formatting . . . 117
8.2.1 Text formatting . . . 117
8.2.2 Horizontal space . . . 118
8.2.3 Text alignment . . . 118
8.2.4 Accents . . . 118
8.2.5 textcomp package . . . 118
8.2.6 Superscripts and other non-math uses of math mode . . . 118
8.2.7 Empty \item followed by a new line of text or a nested list: . . . 118
8.2.8 Filenames and URLs in lists or footnotes . . . 119
8.2.9 relsize package . . . 119
8.3 Boxes and minipages . . . 119
8.3.1 Marginpars . . . 119
8.3.2 Save Boxes . . . 119
8.3.3 Minipages . . . 119
8.3.4 Side-by-side minipages . . . 120
8.3.5 Framed minipages and other environments . . . 120
8.3.6 fancybox package . . . 122
8.3.7 mdframed package . . . 123
8.4 Section names . . . 123
8.5 Cross-references . . . 124
8.5.1 Page references . . . 124
8.5.2 cleveref and varioref packages . . . 125
8.5.3 Hyperlinks, hyperref, and url . . . 125

8.5.4 Footnotes and page notes . . . 125
8.5.5 xr, xr-hyper, and xcite packages . . . 127
8.6 Front and back matter . . . 127
8.6.1 Custom classes with multiple authors and affiliations . . . 127
8.6.2 Starred chapters and sections . . . 127
8.6.3 abstract package . . . 128
8.6.4 titling and authblk . . . 128
8.6.5 tocloft package . . . 128
8.6.6 appendix package . . . 128
8.6.7 pagenote package . . . 128
8.6.8 endnotes package . . . 128
8.6.9 *BibTeX* . . . 129
8.6.10 xcite package . . . 129
8.6.11 gloss package . . . 129
8.6.12 glossaries package . . . 129
8.6.13 nomencl package . . . 130
8.6.14 Indexing overview . . . 130
8.6.15 Indexing with basic LaTeX and makeidx . . . 131
8.6.16 Indexing with index . . . 132
8.6.17 Indexing with splitidx . . . 132
8.6.18 Indexing with imakeidx . . . 134
8.6.19 Indexes with memoir . . . 137
8.6.20 Using a custom *makeindex* style file . . . 140
8.6.21 Using a custom *xindy* style file . . . 141
8.6.22 Additional indexing limitations . . . 141
8.6.23 Index positions, TOC, tocbibind . . . 142
8.7 Math . . . 143
8.7.1 Math in section names . . . 143
8.7.2 Rendering tradeoffs . . . 143
8.7.3 SVG option . . . 144

8.7.4 MathJax option . . . 144
8.7.5 Customizing MathJax . . . 145
8.7.6 MathJax limitations . . . 145
8.7.7 Catcode changes . . . 146
8.7.8 Complicated inline math objects . . . 146
8.7.9 Complicated display math objects . . . 146
8.7.10 ntheorem package . . . 146
8.7.11 siunitx package . . . 147
8.7.12 units and nicefrac packages . . . 147
8.7.13 newtxmath package . . . 147
8.8 Graphics . . . 147
8.8.1 tikz package . . . 149
8.8.2 grffile package . . . 149
8.8.3 color package . . . 149
8.8.4 xcolor package . . . 149
8.8.5 epstopdf package . . . 150
8.8.6 pstricks package . . . 150
8.8.7 pdftricks package . . . 150
8.8.8 psfrag package . . . 150
8.8.9 pstool package . . . 151
8.8.10 asymptote package . . . 151
8.8.11 overpic package . . . 151
8.8.12 Multimedia packages . . . 151
8.9 Tabbing . . . 152
8.10 Tabular . . . 152
8.10.1 `tabular` environment . . . 152
8.10.2 multirow package . . . 154
8.10.3 longtable package . . . 155
8.10.4 threeparttablex package . . . 156
8.10.5 supertabular and xtab packages . . . 156

8.10.6 colortbl package . . . 156
8.10.7 ctable package . . . 156
8.10.8 bigdelim package . . . 157
8.11 Floats . . . 157
8.11.1 Float contents alignment . . . 157
8.11.2 float, trivfloat, and/or algorithmicx together . . . 157
8.11.3 caption and subcaption packages . . . 157
8.11.4 subfig package . . . 158
8.11.5 floatrow package . . . 158
8.11.6 keyfloat package . . . 159
8.12 KOMA-SCRIPT classes . . . 159
8.13 MEMOIR class . . . 159
8.14 International languages . . . 160
8.15 Miscellaneous packages . . . 160
8.15.1 verse and memoir . . . 160
8.15.2 newclude package . . . 160
8.15.3 babel package . . . 161
8.15.4 polyglossia package . . . 161
8.15.5 todonotes and luatodonotes packages . . . 161
8.15.6 fixme . . . 162
8.15.7 chemfig package . . . 162
8.15.8 chemformula package . . . 162
8.15.9 mhchem package . . . 162
8.15.10 xparse package . . . 162
8.15.11 kotex package . . . 162
9 Compiling using custom shell commands . . . 163
9.1 Command options . . . 163
9.2 Literal character macros . . . 163
9.3 *latexmk* . . . 164
9.4 perltex package . . . 165

9.5 pythontex package . . . 165
9.6 Other packages . . . 165
9.7 *make* program . . . 166
9.8 UTF-8 locale . . . 166
10 EPUB conversion . . . 167
11 Word-processor conversion . . . 169
11.1 Activating word-processor conversion . . . 169
11.2 Additional modifications . . . 170
11.3 Recommendations . . . 172
11.4 Limitations . . . 173
12 Modifying lwarp . . . 174
12.1 Creating a development system . . . 174
12.2 Modifying a package for lwarp . . . 175
12.2.1 Adding a package to the lwarp.dtx file . . . 176
12.3 Modifying a class for lwarp . . . 176
12.4 Testing lwarp . . . 177
12.5 Modifying *lwarpmk* . . . 177
13 Troubleshooting . . . 179
13.1 lwarp package error conditions and warnings . . . 179
13.1.1 Configuration file `lwarpmk.conf` . . . 179
13.1.2 Image generation with **`lwarpmk limages`** . . . 179
13.1.3 Default bitmapped font . . . 180
13.1.4 Packages . . . 180
13.1.5 Compiling . . . 180
13.2 Using the lwarp package . . . 181
13.2.1 Debug tracing output . . . 184
13.3 Compiling the `lwarp.dtx` file . . . 185
14 Trademarks . . . 186
1 lwarp.sty . . . 187
15 Implementation . . . 187

16 Section depths and HTML headings . . . 188
17 Source code . . . 189
18 Detecting the TEX engine — *pdflatex*, *lualatex*, *xelatex* . . . 190
19 Early package requirements . . . 190
20 Package load order . . . 190
20.1 Tests of package load order . . . 191
20.2 Error for disallowed packages and classes loaded before lwarp . . . 193
20.3 Enforcing package loading after lwarp . . . 194
21 MD5 hashing . . . 203
22 pdfLATEX T1 and UTF-8 encoding . . . 203
23 Unicode input characters . . . 204
24 Avoid a bitmapped font . . . 204
25 Upright quotes . . . 205
26 Miscellaneous tools . . . 205
26.1 Lengths and units . . . 205
26.2 Patching . . . 206
26.3 Chinese text isolation . . . 206
26.4 Inserting vertical space . . . 206
26.5 Argument selection . . . 207
26.6 Global boxes . . . 207
27 Operating-System portability . . . 208
27.1 Literal characters . . . 208
27.2 Common portability code . . . 209
27.3 UNIX, LINUX, and MAC OS . . . 209
27.4 MS-WINDOWS . . . 209
28 Package options . . . 210
28.1 Additional options support . . . 214
28.2 Conditional compilation . . . 216
29 Required packages . . . 217
30 Loading packages . . . 222

31 Additional required packages . . . 228
32 File handles . . . 228
33 Include a file . . . 228
34 Copying a file . . . 229
35 Debugging messages . . . 230
36 Defining print and HTML versions of macros and environments . . . 231
37 HTML-conversion output modifications . . . 235
37.1 User-level controls . . . 236
37.2 Heading adjustments . . . 237
38 Remembering original formatting macros . . . 239
39 Accents . . . 240
40 Configuration files . . . 242
40.1 Decide whether to generate configuration files . . . 242
40.2 <project>_html.tex . . . 242
40.3 *lwarpmk* configuration files . . . 243
40.3.1 Helper macros . . . 243
40.3.2 lwarpmk.conf . . . 249
40.3.3 <project>.lwarpmkconf . . . 249
40.4 lwarp.css . . . 249
40.5 lwarp_sagebrush.css . . . 278
40.6 lwarp_formal.css . . . 283
40.7 sample_project.css . . . 287
40.8 lwarp.ist . . . 287
40.9 lwarp.xdy . . . 288
40.10 lwarp_one_limage.cmd . . . 289
40.11 lwarp_mathjax.txt . . . 289
40.12 lwarpmk.lua — lwarpmk option . . . 292
41 Stacks . . . 309
41.1 Assigning depths . . . 310
41.2 Closing actions . . . 310

41.3 Closing depths . . . 311
41.4 Pushing and popping the stack . . . 311
42 Data arrays . . . 312
43 Localizing catcodes . . . 313
44 Localizing dynamic math . . . 314
45 HTML entities . . . 315
46 HTML filename generation . . . 316
47 Homepage link . . . 318
48 \LWRPrintStack diagnostic tool . . . 319
49 Closing stack levels . . . 320
50 PDF pages and styles . . . 321
51 HTML tags, spans, divs, elements . . . 322
51.1 Mapping LaTeX sections to HTML sections . . . 322
51.2 Babel-French tag modifications . . . 323
51.3 HTML output formatting . . . 324
51.4 HTML tags . . . 324
51.5 Block tags and comments . . . 326
51.6 Div class and element class . . . 327
51.7 Single-line elements . . . 328
51.8 HTML5 semantic elements . . . 329
51.9 High-level block and inline classes . . . 329
51.10 Closing HTML tags . . . 331
52 Paragraph handling . . . 332
53 Paragraph start/stop handling . . . 335
54 Indentfirst . . . 338
55 Page headers and footers . . . 338
56 CSS . . . 339
57 MathJax script . . . 339
58 Title, HTML meta author, HTML meta description . . . 340

59 Footnotes 341
59.1 Regular page footnotes 342
59.2 Minipage footnotes 342
59.3 Titlepage thanks 342
59.4 Regular page footnote implementation 342
59.5 Minipage footnote implementation 345
59.6 Printing pending footnotes 346
60 Marginpars 347
61 Splitting HTML files 348
61.1 Customizing MathJax 353
62 Sectioning 358
62.1 User-level starred section commands 358
62.2 Book class commands 359
62.3 Sectioning support macros 359
62.4 Pre- and post- sectioning names 367
62.5 `\section` and friends 367
63 Starting a new file 369
64 Starting HTML output 372
65 Ending HTML output 375
66 Title page 377
66.1 Setting the title, etc. 378
66.2 `\if@titlepage` 379
66.3 Changes for `\affiliation` 379
66.4 Printing the thanks 380
66.5 Printing the title, etc. in HTML 380
66.6 Printing the title, etc. in print form 381
66.7 `\maketitle` for HTML output 382
66.8 `\published` and `\subtitle` 385
67 Abstract 386

68 Quote and verse . . . 387
68.1 Attributions . . . 387
68.2 Quotes, quotations . . . 387
68.3 Verse . . . 388
68.3.1 LaTeX core verse environment . . . 388
68.3.2 verse and memoir . . . 389
69 Verbatim and tabbing . . . 389
70 Theorems . . . 392
71 Lists . . . 392
71.1 List environment . . . 393
71.2 Itemize . . . 396
71.3 Enumerate . . . 397
71.4 Description . . . 397
71.5 Patching the lists . . . 398
72 Tabular . . . 399
72.1 Limitations . . . 399
72.2 Temporary package-related macros . . . 401
72.2.1 arydshln . . . 401
72.3 Token lookahead . . . 402
72.4 Tabular variables . . . 402
72.5 Handling &, @, !, and bar . . . 405
72.5.1 Handling & . . . 407
72.5.2 Filling an unfinished row . . . 408
72.6 Handling \\ . . . 409
72.7 Looking ahead in the column specifications . . . 410
72.8 Parsing @, >, <, !, bar columns . . . 411
72.9 Parsing 'l', 'c', or 'r' columns . . . 415
72.10 Parsing 'p', 'm', or 'b' columns . . . 415
72.11 Parsing 'w' columns . . . 415
72.12 Parsing '*' columns . . . 416

72.13 Parsing 'D' columns . . . 416
72.14 Expanding the star column specifiations . . . 416
72.15 Parsing the column specifications . . . 418
72.16 colortbl and xparse tabular color support . . . 423
72.17 Starting a new row . . . 424
72.18 Printing vertical bar tags . . . 425
72.19 Printing at or bang tags . . . 425
72.20 Data opening tag . . . 426
72.21 Midrules . . . 428
72.22 Cell colors . . . 434
72.23 Multicolumns . . . 437
72.23.1 Parsing multicolumns . . . 437
72.23.2 Multicolumn factored code . . . 441
72.23.3 Multicolumn . . . 444
72.23.4 Longtable captions . . . 444
72.23.5 Counting HTML tabular columns . . . 446
72.24 Multirow if not loaded . . . 448
72.25 Multicolumnrow . . . 448
72.26 Utility macros inside a table . . . 449
72.27 Special-case tabular markers . . . 450
72.28 Checking for a new table cell . . . 451
72.29 \mrowcell . . . 454
72.30 \mcolrowcell . . . 454
72.31 HTML tabular environment . . . 454
73 Cross-references . . . 461
73.1 Setup . . . 463
73.2 New lwarp labels. . . . 463
73.3 Labels . . . 464
73.4 References . . . 466
73.5 Hyper-references . . . 468

74 Floats . . . 472
74.1 Float environment . . . 472
74.2 Float tracking . . . 474
74.3 Caption inside a float environment . . . 476
74.4 Caption and LOF linking and tracking . . . 476
75 Table of Contents, LOF, LOT . . . 479
75.1 Reading and printing the TOC . . . 479
75.2 High-level TOC commands . . . 482
75.3 Side TOC . . . 483
75.4 Low-level TOC line formatting . . . 484
76 Index and glossary . . . 488
77 Bibliography presentation . . . 491
78 Restoring original formatting . . . 492
79 Math . . . 493
79.1 Limitations . . . 493
79.1.1 Math in section names . . . 493
79.1.2 Rendering tradeoffs . . . 494
79.1.3 SVG option . . . 494
79.1.4 MathJax option . . . 495
79.1.5 Customizing MathJax . . . 495
79.1.6 MathJax limitations . . . 495
79.1.7 Catcode changes . . . 496
79.1.8 Complicated inline math objects . . . 496
79.1.9 Complicated display math objects . . . 496
79.2 HTML `alt` tag names . . . 497
79.3 Inline and display math . . . 498
79.4 MathJax support . . . 509
79.5 Equation environment . . . 511
79.6 `\displaymathnormal` and `\displaymathother` . . . 514

79.7 AMS Math environments . . . 516
79.7.1 Support macros . . . 516
79.7.2 Environment patches . . . 517
80 Lateximages . . . 520
80.1 Description . . . 520
80.2 Support counters and macros . . . 521
80.3 Font size . . . 521
80.4 Sanitizing math expressions for HTML . . . 522
80.5 Equation numbers . . . 523
80.6 HTML alt tags . . . 524
80.7 lateximage environment . . . 525
81 center, flushleft, flushright . . . 531
82 Preloaded packages . . . 533
83 siunitx . . . 534
84 Graphics print-mode modifications . . . 535
84.1 General limitations . . . 535
84.2 Print-mode modifications . . . 537
85 xcolor boxes . . . 537
86 chemmacros environments . . . 540
87 cleveref . . . 541
88 picture environment . . . 544
89 Minipages and Boxes . . . 544
89.1 Counters and lengths . . . 545
89.2 Footnote handling . . . 545
89.3 Minipage handling . . . 545
89.4 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox . . . 550
90 Direct formatting . . . 555
91 Skips, spaces, font sizes . . . 567
92 \phantomsection . . . 575
93 \LaTeX and other logos . . . 576

94 \AtBeginDocument, \AtEndDocument . . . 579
95 Loading KOMA-SCRIPT class patches . . . 579
96 Loading MEMOIR class patches . . . 580
97 ut* class patches . . . 580
98 CTEX patches . . . 581
99 kotexutf patches . . . 582
2 lwarp-2in1.sty . . . 583
3 lwarp-2up.sty . . . 583
4 lwarp-a4.sty . . . 583
5 lwarp-a4wide.sty . . . 584
6 lwarp-a5comb.sty . . . 584
7 lwarp-abstract.sty . . . 584
8 lwarp-academicons.sty . . . 586
9 lwarp-accsupp.sty . . . 587
10 lwarp-acro.sty . . . 587
11 lwarp-acronym.sty . . . 590
12 lwarp-adjmulticol.sty . . . 591
13 lwarp-addlines.sty . . . 592
14 lwarp-afterpage.sty . . . 592
15 lwarp-algorithm2e.sty . . . 592
16 lwarp-algorithmicx.sty . . . 596
17 lwarp-alltt.sty . . . 597
18 lwarp-amsmath.sty . . . 597
19 lwarp-amsthm.sty . . . 600
20 lwarp-anonchap.sty . . . 604
21 lwarp-anysize.sty . . . 605
22 lwarp-appendix.sty . . . 605
23 lwarp-ar.sty . . . 605

24 lwarp-arabicfront.sty 607
25 lwarp-array.sty 607
26 lwarp-arydshln.sty 608
27 lwarp-asymptote.sty 610
28 lwarp-atbegshi.sty 611
29 lwarp-attachfile.sty 611
30 lwarp-attachfile2.sty 612
31 lwarp-authblk.sty 614
32 lwarp-autonum.sty 615
33 lwarp-axessibility.sty 616
34 lwarp-axodraw2.sty 616
35 lwarp-backnaur.sty 617
36 lwarp-backref.sty 617
37 lwarp-balance.sty 617
38 lwarp-bbding.sty 618
39 lwarp-biblatex.sty 622
40 lwarp-bibunits.sty 623
41 lwarp-bigdelim.sty 623
42 lwarp-bigfoot.sty 624
43 lwarp-bigstrut.sty 625
44 lwarp-bitpattern.sty 625
45 lwarp-blowup.sty 626
46 lwarp-booklet.sty 626
47 lwarp-bookmark.sty 626
48 lwarp-booktabs.sty 627
49 lwarp-bophook.sty 628
50 lwarp-bounddvi.sty 629

51 lwarp-boxedminipage2e.sty 629
52 lwarp-breakurl.sty 629
53 lwarp-breqn.sty 630
54 lwarp-bsheaders.sty 632
55 lwarp-bxpapersize.sty 632
56 lwarp-bytefield.sty 632
57 lwarp-cancel.sty 632
58 lwarp-canoniclayout.sty 633
59 lwarp-caption.sty 634
60 lwarp-cases.sty 637
61 lwarp-changebar.sty 637
62 lwarp-changelayout.sty 638
63 lwarp-changepage.sty 639
64 lwarp-changes.sty 639
65 lwarp-chappg.sty 642
66 lwarp-chapterbib.sty 642
67 lwarp-chemfig.sty 642
68 lwarp-chemformula.sty 644
69 lwarp-chemgreek.sty 649
70 lwarp-chemmacros.sty 649
168 chemmacros 649
168.1 Changes to the user's document 650
168.2 Code 650
168.3 Loading modules 650
168.4 New environments 650
168.5 Acid-base 651
168.6 Charges 653
168.7 Nomenclature 653

168.8 Particles . . . 655
168.9 Phases . . . 656
168.10 Mechanisms . . . 656
168.11 Newman . . . 658
168.12 Orbital . . . 659
168.13 Reactions . . . 659
168.14 Redox . . . 660
168.15 Scheme . . . 661
168.16 Spectroscopy . . . 661
168.17 Thermodynamics . . . 665

71 lwarp-chemnum.sty . . . 667
72 lwarp-chkfloat.sty . . . 668
73 lwarp-chngpage.sty . . . 668
74 lwarp-cite.sty . . . 668
75 lwarp-CJK.sty . . . 669
76 lwarp-CJKutf8.sty . . . 669
77 lwarp-clrdblpg.sty . . . 669
78 lwarp-cmdtrack.sty . . . 670
79 lwarp-color.sty . . . 670
80 lwarp-colortbl.sty . . . 670
81 lwarp-continue.sty . . . 672
82 lwarp-copyrightbox.sty . . . 672
83 lwarp-crop.sty . . . 673
84 lwarp-ctable.sty . . . 673
85 lwarp-cuted.sty . . . 676
86 lwarp-cutwin.sty . . . 676
87 lwarp-dblfloatfix.sty . . . 677
88 lwarp-dblfnote.sty . . . 677

89 lwarp-dcolumn.sty 677
90 lwarp-diagbox.sty 678
91 lwarp-dingbat.sty 679
92 lwarp-dprogress.sty 680
93 lwarp-draftcopy.sty 680
94 lwarp-draftfigure.sty 681
95 lwarp-draftwatermark.sty 681
96 lwarp-easy-todo.sty 682
97 lwarp-ebook.sty 682
98 lwarp-ed.sty 683
99 lwarp-ellipsis.sty 684
100 lwarp-embrac.sty 684
101 lwarp-emptypage.sty 685
102 lwarp-endfloat.sty 685
103 lwarp-endheads.sty 686
104 lwarp-endnotes.sty 686
105 lwarp-enumerate.sty 687
106 lwarp-enumitem.sty 687
107 lwarp-epigraph.sty 688
108 lwarp-epsfig.sty 689
109 lwarp-epstopdf.sty 690
110 lwarp-epstopdf-base.sty 690
111 lwarp-eqlist.sty 691
112 lwarp-eqparbox.sty 691
113 lwarp-errata.sty 692
114 lwarp-eso-pic.sty 694
115 lwarp-eurosym.sty 694

116 lwarp-everypage.sty 695
117 lwarp-everyshi.sty 695
118 lwarp-extramarks.sty 695
119 lwarp-fancybox.sty 696
120 lwarp-fancyhdr.sty 701
121 lwarp-fancyref.sty 702
122 lwarp-fancytabs.sty 703
123 lwarp-fancyvrb.sty 703
124 lwarp-figcaps.sty 709
125 lwarp-figsize.sty 710
126 lwarp-fitbox.sty 710
127 lwarp-fix2col.sty 711
128 lwarp-fixme.sty 711
129 lwarp-fixmetodonotes.sty 712
130 lwarp-flafter.sty 713
131 lwarp-flippdf.sty 713
132 lwarp-float.sty 713
133 lwarp-floatflt.sty 715
134 lwarp-floatpag.sty 716
135 lwarp-floatrow.sty 716
136 lwarp-fltrace.sty 721
137 lwarp-flushend.sty 721
138 lwarp-fnbreak.sty 722
139 lwarp-fncychap.sty 722
140 lwarp-fnlineno.sty 723
141 lwarp-fnpara.sty 723
142 lwarp-fnpos.sty 723

143 lwarp-fontawesome.sty 723
144 lwarp-fontawesome5.sty 725
145 lwarp-fontaxes.sty 725
146 lwarp-fontenc.sty 726
147 lwarp-footmisc.sty 726
148 lwarp-footnote.sty 727
149 lwarp-footnotebackref.sty 728
150 lwarp-footnotehyper.sty 729
151 lwarp-footnoterange.sty 729
152 lwarp-footnpag.sty 729
153 lwarp-foreign.sty 729
154 lwarp-forest.sty 730
155 lwarp-framed.sty 730
156 lwarp-ftcap.sty 733
157 lwarp-ftnright.sty 733
158 lwarp-fullminipage.sty 733
159 lwarp-fullpage.sty 733
160 lwarp-fullwidth.sty 733
161 lwarp-fwlw.sty 734
162 lwarp-gentombow.sty 734
163 lwarp-geometry.sty 734
164 lwarp-gloss.sty 735
165 lwarp-glossaries.sty 736
166 lwarp-gmeometric.sty 738
167 lwarp-graphics.sty 738
265 graphics 738
265.1 Graphics extensions 739

265.2 Length conversions and graphics options . . . 739
265.3 Printing HTML styles . . . 742
265.4 \includegraphics . . . 742
265.5 Boxes . . . 748

168 lwarp-graphicx.sty . . . 751
169 lwarp-grffile.sty . . . 751
170 lwarp-grid.sty . . . 751
171 lwarp-grid-system.sty . . . 752
172 lwarp-gridset.sty . . . 752
173 lwarp-hang.sty . . . 752
174 lwarp-hanging.sty . . . 754
175 lwarp-hypbmsec.sty . . . 755
176 lwarp-hypcap.sty . . . 755
177 lwarp-hypdestopt.sty . . . 755
178 lwarp-hypernat.sty . . . 755
179 lwarp-hyperref.sty . . . 756
180 lwarp-hyperxmp.sty . . . 761
181 lwarp-hyphenat.sty . . . 761
182 lwarp-idxlayout.sty . . . 762
183 lwarp-ifoddpage.sty . . . 763
184 lwarp-imakeidx.sty . . . 763
185 lwarp-index.sty . . . 767
186 lwarp-inputtrc.sty . . . 769
187 lwarp-intopdf.sty . . . 769
188 lwarp-karnaugh-map.sty . . . 770
189 lwarp-keyfloat.sty . . . 773
190 lwarp-layaureo.sty . . . 779

191 lwarp-layout.sty 779
192 lwarp-layouts.sty 779
193 lwarp-leading.sty 782
194 lwarp-letterspace.sty 782
195 lwarp-lettrine.sty 782
196 lwarp-lineno.sty 783
197 lwarp-lips.sty 786
198 lwarp-listings.sty 786
199 lwarp-listliketab.sty 790
200 lwarp-lltjext.sty 790
201 lwarp-longtable.sty 791
202 lwarp-lscape.sty 794
203 lwarp-ltablex.sty 794
204 lwarp-ltcaption.sty 795
205 lwarp-ltxgrid.sty 795
206 lwarp-ltxtable.sty 796
207 lwarp-lua-check-hyphen.sty 796
208 lwarp-lua-visual-debug.sty 796
209 lwarp-luacolor.sty 796
210 lwarp-luatodonotes.sty 797
211 lwarp-lyluatex.sty 799
212 lwarp-magaz.sty 801
213 lwarp-makeidx.sty 801
214 lwarp-manyfoot.sty 802
215 lwarp-marginal.sty 804
216 lwarp-marginfit.sty 804
217 lwarp-marginfix.sty 804

218 lwarp-marginnote.sty 805

219 lwarp-marvosym.sty 805

220 lwarp-mathtools.sty 806

221 lwarp-mcaption.sty 806

222 lwarp-mdframed.sty 807

320 mdframed 807

320.1 Limitations 807

320.2 Package loading 808

320.3 Patches 808

320.4 Initial setup 808

320.5 Color and length HTML conversion 809

320.6 Environment encapsulation 809

320.7 Mdframed environment 810

320.8 Titles and subtitles 811

320.9 New environments 813

223 lwarp-media9.sty 816

224 lwarp-memhfixc.sty 818

225 lwarp-metalogo.sty 818

226 lwarp-metalogox.sty 819

227 lwarp-mhchem.sty 819

228 lwarp-microtype.sty 822

229 lwarp-midfloat.sty 823

230 lwarp-midpage.sty 823

231 lwarp-minibox.sty 823

232 lwarp-minitoc.sty 824

233 lwarp-morefloats.sty 824

234 lwarp-moreverb.sty 825

235 lwarp-movie15.sty 826

236 lwarp-mparhack.sty 827
237 lwarp-multicap.sty 828
238 lwarp-multicol.sty 828
239 lwarp-multicolrule.sty 829
240 lwarp-multimedia.sty 830
241 lwarp-multirow.sty 831
242 lwarp-multitoc.sty 834
243 lwarp-musicography.sty 834
244 lwarp-nameauth.sty 837
245 lwarp-nameref.sty 839
246 lwarp-natbib.sty 839
247 lwarp-nccfancyhdr.sty 840
248 lwarp-needspace.sty 841
249 lwarp-nextpage.sty 841
250 lwarp-nfssext-cfr.sty 841
251 lwarp-nicefrac.sty 850
252 lwarp-niceframe.sty 851
253 lwarp-nomencl.sty 851
254 lwarp-nonfloat.sty 852
255 lwarp-nonumonpart.sty 852
256 lwarp-nopageno.sty 852
257 lwarp-notes.sty 852
258 lwarp-notespages.sty 853
259 lwarp-nowidow.sty 853
260 lwarp-ntheorem.sty 854
358 ntheorem 854
358.1 Limitations 854

358.2 Options . . . 854
358.3 Remembering the theorem style . . . 855
358.4 HTML cross-referencing . . . 858
358.5 \newtheoremstyle . . . 858
358.6 Standard styles . . . 859
358.7 Additional objects . . . 860
358.8 Renewed standard configuration . . . 860
358.9 amsthm option . . . 861
358.10 Ending a theorem . . . 864
358.11 \NoEndMark . . . 864
358.12 List-of . . . 864
358.13 Symbols . . . 865
358.14 Cross-referencing . . . 865

261 lwarp-octave.sty . . . 865
262 lwarp-overpic.sty . . . 866
263 lwarp-pagegrid.sty . . . 867
264 lwarp-pagenote.sty . . . 867
265 lwarp-pagesel.sty . . . 868
266 lwarp-paralist.sty . . . 868
267 lwarp-parnotes.sty . . . 868
268 lwarp-parskip.sty . . . 869
269 lwarp-pbox.sty . . . 870
270 lwarp-pdfcomment.sty . . . 870
271 lwarp-pdfcrypt.sty . . . 871
272 lwarp-pdflscape.sty . . . 871
273 lwarp-pdfmarginpar.sty . . . 871
274 lwarp-pdfpages.sty . . . 871
275 lwarp-pdfprivacy.sty . . . 874

276 lwarp-pdfrender.sty 874
277 lwarp-pdfsync.sty 874
278 lwarp-pdftricks.sty 875
279 lwarp-pdfx.sty 875
280 lwarp-perpage.sty 875
281 lwarp-pfnote.sty 877
282 lwarp-phfqit.sty 877
283 lwarp-pifont.sty 877
284 lwarp-placeins.sty 878
285 lwarp-plarydshln.sty 878
286 lwarp-plext.sty 879
287 lwarp-plextarydshln.sty 880
288 lwarp-plextcolortbl.sty 880
289 lwarp-prelim2e.sty 880
290 lwarp-prettyref.sty 880
291 lwarp-preview.sty 881
292 lwarp-psfrag.sty 881
293 lwarp-psfragx.sty 882
294 lwarp-pst-eps.sty 882
295 lwarp-pstool.sty 882
296 lwarp-pstricks.sty 883
297 lwarp-pxatbegshi.sty 884
298 lwarp-pxeveryshi.sty 884
299 lwarp-pxftnright.sty 884
300 lwarp-pxjahyper.sty 884
301 lwarp-quotchap.sty 885
302 lwarp-quoting.sty 886

303 lwarp-ragged2e.sty 886
304 lwarp-realscripts.sty 887
305 lwarp-refcheck.sty 888
306 lwarp-register.sty 888
307 lwarp-relsize.sty 889
308 lwarp-repeatindex.sty 890
309 lwarp-resizegather.sty 891
310 lwarp-rmpage.sty 891
311 lwarp-romanbar.sty 892
312 lwarp-romanbarpagenumber.sty 892
313 lwarp-rotating.sty 892
314 lwarp-rotfloat.sty 893
315 lwarp-rviewport.sty 894
316 lwarp-savetrees.sty 894
317 lwarp-scalefnt.sty 894
318 lwarp-schemata.sty 894
319 lwarp-scrextend.sty 895
320 lwarp-scrhack.sty 898
321 lwarp-scrlayer.sty 898
322 lwarp-scrlayer-notecolumn.sty 899
323 lwarp-scrlayer-scrpage.sty 900
324 lwarp-scrpage2.sty 901
325 lwarp-section.sty 902
326 lwarp-sectionbreak.sty 903
327 lwarp-sectsty.sty 903
328 lwarp-semantic-markup.sty 904
329 lwarp-setspace.sty 905

330 lwarp-shadow.sty 906
331 lwarp-shapepar.sty 906
332 lwarp-showidx.sty 906
333 lwarp-showkeys.sty 907
334 lwarp-showtags.sty 907
335 lwarp-sidecap.sty 907
336 lwarp-sidenotes.sty 908
337 lwarp-SIunits.sty 909
338 lwarp-siunitx.sty 910
339 lwarp-slantsc.sty 915
340 lwarp-soul.sty 915
341 lwarp-soulpos.sty 917
342 lwarp-soulutf8.sty 918
343 lwarp-splitidx.sty 918
344 lwarp-srcltx.sty 919
345 lwarp-srctex.sty 920
346 lwarp-stabular.sty 920
347 lwarp-stackengine.sty 921
348 lwarp-stfloats.sty 922
349 lwarp-struktex.sty 923
350 lwarp-subcaption.sty 923
351 lwarp-subfig.sty 924
352 lwarp-subfigure.sty 929
353 lwarp-supertabular.sty 929
354 lwarp-syntonly.sty 931
355 lwarp-tabfigures.sty 931
356 lwarp-tablefootnote.sty 931

357 lwarp-tabls.sty 932
358 lwarp-tabularx.sty 932
359 lwarp-tabulary.sty 932
360 lwarp-tascmac.sty 933
361 lwarp-textarea.sty 935
362 lwarp-textcomp.sty 935
363 lwarp-textfit.sty 938
364 lwarp-textpos.sty 939
365 lwarp-theorem.sty 940
366 lwarp-thinsp.sty 943
367 lwarp-threadcol.sty 944
368 lwarp-threeparttable.sty 944
369 lwarp-threeparttablex.sty 945
370 lwarp-thumb.sty 946
371 lwarp-thumbs.sty 946
372 lwarp-tikz.sty 946
373 lwarp-titleps.sty 948
374 lwarp-titleref.sty 951
375 lwarp-titlesec.sty 951
376 lwarp-titletoc.sty 953
377 lwarp-titling.sty 954
378 lwarp-tocbasic.sty 959
379 lwarp-tocbibind.sty 959
380 lwarp-tocdata.sty 961
381 lwarp-tocenter.sty 963
382 lwarp-tocloft.sty 963
383 lwarp-tocstyle.sty 969

384 lwarp-todo.sty 969
385 lwarp-todonotes.sty 970
386 lwarp-topcapt.sty 972
387 lwarp-tram.sty 972
388 lwarp-transparent.sty 973
389 lwarp-trimclip.sty 973
390 lwarp-trivfloat.sty 974
391 lwarp-truncate.sty 975
392 lwarp-turnthepage.sty 975
393 lwarp-twoup.sty 975
394 lwarp-typearea.sty 975
395 lwarp-typicons.sty 976
396 lwarp-ulem.sty 977
397 lwarp-umoline.sty 978
398 lwarp-underscore.sty 979
399 lwarp-units.sty 979
400 lwarp-unitsdef.sty 980
401 lwarp-upref.sty 981
402 lwarp-url.sty 981
403 lwarp-uspace.sty 981
404 lwarp-verse.sty 982
405 lwarp-versonotes.sty 983
406 lwarp-vertbars.sty 984
407 lwarp-vmargin.sty 984
408 lwarp-vowel.sty 985
409 lwarp-vpe.sty 985
410 lwarp-vwcol.sty 985

411 lwarp-wallpaper.sty 987
412 lwarp-watermark.sty 988
413 lwarp-widows-and-orphans.sty 988
414 lwarp-wrapfig.sty 989
415 lwarp-xbmks.sty 990
416 lwarp-xcolor.sty 990
514 xcolor 990
514.1 Limitations 990
514.2 xcolor definitions: location and timing 991
514.3 Package loading 993
514.4 Remembering and restoring original definitions 993
514.5 \normalcolor 993
514.6 HTML color style 993
514.7 HTML border 994
514.8 High-level macros 995
514.9 Row colors 999
417 lwarp-xechangebar.sty 1001
418 lwarp-xellipsis.sty 1001
419 lwarp-xetexko-vertical.sty 1002
420 lwarp-xfakebold.sty 1002
421 lwarp-xfrac.sty 1002
422 lwarp-xltabular.sty 1005
423 lwarp-xltxtra.sty 1005
424 lwarp-xmpincl.sty 1006
425 lwarp-xpiano.sty 1006
426 lwarp-xpinyin.sty 1007
427 lwarp-xr.sty 1007
428 lwarp-xr-hyper.sty 1008

429 lwarp-xtab.sty 1008

430 lwarp-xunicode.sty 1010

431 lwarp-xurl.sty 1011

432 lwarp-xy.sty 1011

433 lwarp-zhlineskip.sty 1012

434 lwarp-zwpagelayout.sty 1012

435 lwarp-patch-komascript.sty 1014

436 lwarp-patch-memoir.sty 1016

534 patch-memoir 1016

534.1 Packages 1017

534.2 Preliminary setup 1018

534.3 Page layout 1018

534.4 Text and fonts 1020

534.5 Titles 1021

534.6 Abstracts 1021

534.7 Docment divisions 1021

534.8 Pagination and headers 1024

534.9 Paragraphs and lists 1025

534.10 Contents lists 1026

534.11 Floats and captions 1030

534.12 Page notes 1033

534.13 Decorative text 1034

534.14 Poetry 1035

534.15 Boxes, verbatims and files 1035

534.16 Cross referencing 1036

534.17 Back matter 1037

534.18 Miscellaneous 1038

534.19 ccaption emulation 1038

534.20 Final patchwork 1040

437 lwarp-common-multimedia.sty 1041

Change History 1046

536 Chg Hist 1046

Index of Objects 1075

General Index 1096

Troubleshooting Index 1100

Index of Indexes 1105

List of Figures

1 tutorial.tex listing 81

List of Tables

1 Typesetting conventions 63
2 LaTeX lwarp package — Supported features 64
3 Required software programs 74
4 Configuration files created by print version 83
5 lwarp package options 101
6 HTML settings 106
7 Literal character macros 164
8 Section HTML headings for word-processor conversion 172
9 Section depths and HTML headings 188
10 Tabular baseline 418
11 Tabular HTML column conversions 419
12 Cross-referencing data structures 462
13 Float data structures 472
14 amsthm package — CSS styling of theorems and proofs 601
15 Ntheorem package — CSS styling of theorems and proofs 854
16 Theorem package — CSS styling of theorems and proofs 940

1 Updates

The following is a summary of updates to lwarp, highlighting new features and any special changes which must be made due to improvements or modifications in lwarp itself.

For a detailed list of the most recent changes, see the end of the Change History on page 1074.

v0.76: MathJax, updates for LaTeX 2019/10 release.

docs
- Docs: Expanded documentation regarding the use of multiple projects in the same directory. See section 5.17.

MathJax
- MathJax: Updated to v2.7.6.

packages
- xr: Updated to v5.05.
- xr-hyper: Updated to v6.1.
- Verified works as-is with xcite.
- acro: Updated to v2.10.

⚠ broken
- Currently broken by the 2019/10 LaTeX update: breqn, grffile, multimedia, movie15.

v0.75: keyfloat, wrapfig

- `\minipage`: Fix for `\linewidth`.

packages
- keyfloat: Improved color control.
- wrapfig: Fix for `\linewidth`.

v0.74: Docs, SVG math, *lwarpmk*, HTML `alt` and `title` text, lyluatex

docs
- Added to the tutorial the section What next?. See section 5.19.
- Added documentation about localization options. See section 7.1.
- Added documentation about accessibility options. See section 7.2.

HTML `alt` text
- Renamed and updated HTML `alt` text macros:

⚠ changed names

Old	New
(hard coded as "image")	`\ImageAltText`
`\mathimagename`	`\MathImageAltText`
`\pacakgediagramname`	`\PackageDiagramAltText`

- Added `\ImageAltText` for the default HTML `alt` text for an image. See section 7.6.
- Added `\ThisAltText`, which may be used to assign a one-time HTML `alt` tag to the very next image generated by lwarp, such as a `lateximage`, `picture`, `tikzpicture`, an image generated by various chemistry or engineering packages, or an SVG math image. This macro also adds a `title` tag to a reference or hyperlink. See section 7.6.

SVG math
- Adjusted `\LateximageFontScale` default from .75 to 1.

- Fix: Font control for SVG math.

misc
- Fix: Ignores negative \hspace.
- Warning if SideTOCDepth < FileDepth.

lwarpmk
- *lwarpmk*: **lwarpmk clean** removes additional files.
- *lwarpmk*: **lwarpmk epstopdf** and **lwarpmk pdftosvg** now honor directories.

packages
- lyluatex: Split images by system or per fullpage, improved margins and scaling.
- Tested to work as-is with mathspec, unicode-math.

v0.73: \include, memoir, koma-script, caption, xy, datatool, music scores.

- Fix for \include.
- Warning for a tabular inside a .
- \color: Added HTML support for rules and frames, but not inline text. Use \textcolor if possible.
- Improved many HTML tags, reducing *tidy* warnings. See Change History.

packages
- memoir: Fixes for \frontmatter* and \mainmatter*. Added \book.
- koma-script: Fix for starred captions in the TOC.
- caption: Fix for starred captions.
- datatool: Added pie, bar, and plot charts.
- threeparttable: Added measuredfigure.
- intopdf: Updated to v0.2.1.
- tocdata: Updated to v2.03.
- quotchap: Updated to v1.2.
- versonotes: Updated to v0.4.
- backnaur: Now uses SVG images. Updated to v3.1.
- xy: Fix for \xybox, improved xy, also now compatible with qcircuit.
- fancyvrb: Fix for label HTML tags.
- Added stackengine.

music
- Added lyluatex. (Music scores.)
- musicography: Updated to 2019/05/28. Added support for lateximages.

v0.72: Font control, \multicolumn, xr and xr-hyper.

⚠ images
- Due to internal changes, images for inline SVG math and lateximages will have new hash values, and will have to be regenerated using

  Enter ⇒ **lwarpmk cleanlimages**

  and

  Enter ⇒ **lwarpmk limages**
- Docs: Color-codes package names in the table of supported packages and features, table 2, according to each package's level of support by lwarp.
- \multicolumn: Fix for paragraph columns.

packages
- xr, xr-hyper: Fixes for references, `\externaldocument`.
- soulutf8: Fix: Loads soul for emulation.
- boxedminipage2e: Added support for `lateximages`.
- zhlineskip: Updated to v1.0e.
- Added fontaxes, slantsc, tabfigures.
- Added nfssext-cfr, thus supporting cfr-lm and several other font packages.
- Added backnaur, hypbmsec, minibox, pdfcrypt, shapepar.

v0.71: Error handling, multimedia, `tabular`.

- `tabular`: Added support for '`*`' columns. Fix for paragraph tags.
- `quotation`: Fix for HTML tag.
- Docs: Added a section about error conditions tested by lwarp. See section 13.1.
- *lwarpmk*: If file `lwarpmk.conf` is an older version, or the incorrect operating system, displays the print command to use to recompile.

packages
- chemfig: Updated for v1.4.
- endfloat: Updated for v2.7.
- textpos: Updated for v1.9.1.

multimedia
- Added media9, movie15, multimedia.

v0.70: Error handling, MathJax, mathtools.

- Error handling for "Label(s) changed." Refuses to **`lwarpmk limages`** until recompile first.
- Fix: If Computer Modern font is used, ensures cm-super or lmodern is used.
- Fixes for `\makebox`.
- Fixes for `\parbox` inside a `<span>`.
- MathJax: Updated to v2.7.5. Loads the `autoload-all.js` extension. Added `\MathJaxFilename` to select custom scripts.

packages
- textcomp, xunicode: Fix for `\textinterrobang`.
- mhchem: Works with MathJax. See section 325.
- changes: Updated to v3.1.2.
- Added autonum, changelayout, inputtrc, mathtools, metalogox.

v0.69: Error handling, many fixes, improved keyfloat / tocdata.

- Fix for HTML corruption of `lateximage` displays.
- `\makebox`, `\framebox`: Fix for (⟨*width,height*⟩) arguments.
- `fminipage`: Honors `\minipagefullwidth`.

packages
- array, longtable: Fix for `\tabularnewline`.
- tabularx, tabulary: Fix to require the array package.
- supertabular, xtab: Fix to clear caption after use.

- graphics: Added a warning if used the `\includegraphics scale` option.
- multirow: Added an error if didn't use `\mrowcell` or `\mcolrowcell` when using `\multirow` or `\multicolumnrow`.
- keyfloat: Updated for v2.00, additional improvements.
- Added ctable, eqlist, eqparbox, ftcap, listliketab, minitoc, tocdata, topcapt.

v0.68: Error handling, tabulars, footnotes.

lwarpmk
- *lwarpmk*: Improved error handling for image generation if compile was incomplete.
- `tabular`: Fix for `\warpprintonly`.

packages
- longtable: Improved flexibility for `\endhead`, etc. Improved error reporting if `\endhead`, etc. incorrect for lwarp.
- threeparttable: Fix for caption type.
- hyperref: Fix for options with braces.
- morefloats: Fix to be loaded early for print output.
- listings: Updated for v1.7.
- Added bigfoot, fnpara, footnotebackref, manyfoot, tablefootnote, threeparttablex.
- Added layouts, niceframe, perpage, showtags.
- Prevented alg, algorithmic, pdfcprot, fncylab.

v0.67: Filename generation, symbol fonts.

docs
- Documentation fix for `<project>-images`, `<project>-images.txt`.
- Added discussion regarding section names. See section 8.4.

filenames
- Added `\FilenameNullify` and `\FilenameSimplify` for filename generation. See section 8.4.
- Core, textcomp, xunicode: Nullified additional symbols during filename generation.

packages
- color: Fix for version number warnings.
- Added academicons, bbding, dingbat, eurosym, fontawesome, fontawesome5, marvosym, pifont, typicons.
- Added changes, easyReview, fitbox, foreign, gloss, karnaugh-map, multicap, nomencl, notes, struktex, umoline, xfakebold.
- Tested to work as-is with askmaps, curves, euro, karnaughmap, tikz-karnaugh.

v0.66: xr, multiple projects, image names/directory, HTML formatting

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

`lateximage`
- Adds options `ImagesDirectory` and `ImagesName` to assign directory and name prefixes for `lateximage` images. The new defaults include the jobname, allowing the image directories for multiple projects to coexist.

⚠ existing projects
- To reuse existing `lateximage` directories, add lwarp options

```
\usepackage[
  ImagesDirectory={lateximages},
  ImagesName={lateximage-}
]{lwarp}
```

If not reused, the existing `lateximages` directory and `lateximages.txt` file may be removed.

filenames
- Added `\FilenameLimit` to control the maximum length of the filenames generated by lwarp.

⚠ Possible filename changes
- Improved filename generation when special characters or macros are used in section names.

Windows
- Fix for **`lwarpmk cleanlimages`** with Windows.

floats
- Fixes for floats in the home page.

lists, table notes
- Improved css for definition lists, table notes.

`tabular`
- `tabular`: Fixes for `\par` in column specifier, minipage inside `tabular`.

indexing
- Indexing: Fix for a long line of multiple entries.

`minipage`
- `\minipagefullwidth`: Fix for global changes.
- Added `\UseMinipageWidths` and `\IgnoreMinipageWidths`. See section 8.3.3.

colors
- Improved `\fbox`, `\fboxBlock`, `\fminipage` to use current text color.

HTML
- Improved HTML output formatting.

docs
- Added discussion regarding invalid HTML. See section 8.1.1.
- Added discussion regarding math in section names, `\imagegraphics` `scale` option. See section 6.
- Added discussion regarding international languages in section names. See section 8.14.

packages
- caption: Fix for options clash.
- xr, xr-hyper: Now compatible.
- subcaption: Improved horizontal spacing.
- multicol: Fix for minipage inside `multicols`.
- multicolrule: Updated for v1.2.
- tocbasic: Minor update.
- acronym: Fix for acronym in float caption.
- kotexutf: Patch with *pdflatex* and new lwarp labels.
- extramarks, fancyhdr: Updated for v3.10.
- memoir: Added docs regarding version numbers. See section 8.13.
- zref: No longer required.
- Added ar, ed, indentfirst, nameauth, truncate.
- Verified to work as-is with changelog.
- Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs.

v0.65: CSS layout, `alt` tags, Japanese.

page layout
- Moved the sideTOC to the left side, allowing improved CSS for margin notes.
- Improved page layout CSS.

image `alt` tags
- graphicx `\includegraphics`: Added the `alt` key to assign an `alt` tag to an image. Default is "`image`", assigned to pass validation.

duplicate HTML files
- Detects and causes an error if duplicate HTML file names are generated, caused by identical or similar sectioning names.

fixes
- Fix for `tabular*`.
- Fix for tabular border colors.
- Fixes `\quad`, `\enskip`, and figure captions to pass validation.

Japanese
- Added ltj* classes, bounddvi, gentombow, lltjext, plarydshln, plext, plextarydshln, plextcolortbl, pxatbegshi, pxeveryshi, pxftnright, pxjahyper, tascmac.
- Verified to work with plarray, plautopatch, plextarray, plextdelarray, pxgentombow, plsiunitx, pxpdfpages, pxpgfrcs, pxpgfmark.

packages
- Added support for fontspec `\textsi` and `\sishape`.
- Added multicol's `\docolaction`.
- Added embrac, footnoterange, multicolrule, versonotes.

v0.64: Koma-Script, Japanese, Chinese.

Japanese
- Added utarticle and related classes.
- Improved ujarticle and related classes.

Chinese
- Fix for biblatex with CTEX and other classes.

Koma-Script
- Fixes for scrlayer, scrlayer-scrpage.

packages
- addlines: Updated to v0.3.
- Added bsheaders, gmeometric, marginal, rmpage, scrpage2.

v0.63: mdframed, Chinese, Japanese, Korean

localization
- Added `\linkhomename`: A user-definable name for the **Home** link.
- Documented `\sidetocname`: A user-definable name for the sideTOC.

fixes
- Fix: `\LinkHome` for print output.

optimizations
- Moved package load checks to the lwarp core to reduce the number of `lwarp-*` files.

packages
- mdframed: Fix with amsthm, improved titles and font control. Improved rule widths.

Chinese
- Fixes for xeCJK.
- Added xpinyin, zhlineskip.
- Verified to work with cjkpunct, upzhkinsoku, zhspacing.

Japanese
- Verified to work with zxjatype, luatexja, luatexja-fontspec.
- Added bxjsarticle and related classes.
- Added ltjsarticle and related classes.
- Added pLaTeX, upLaTeX, ujarticle and related classes.

- Prevented utarticle and related classes.
- Prevented bxcjkatype.

Korean
- Verified to work with kotex, xetexko, luatexko.

v0.62: MiKTEX docs, HTML title, CTEX, xeCJK, bitpattern.

docs
- Docs: Setting a UTF-8 locale. See section 9.8.

MiKTEX
- MiKTEX: Docs for *MiKTeX Console* and miktex-poppler-bin.

HTML <title>
- HTML subpage titles: Added \HTMLTitleBeforeSection and \HTMLTitleAfterSection to select whether the HTML <title> displays the website name before or after the section name. See section 7.6.

fixes
- Fix for package options handling.
- Fixes for horizontal white space between fminipage, fcolorminipage, colorboxBlock, fcolorboxBlock.
- Logos: Fix for XƎTEX logo, improved CSS, made robust, improved search-engine optimization.
- \\[$1]: Additional HTML <br> if $1 > 0 pt.
- Fixes for \includgraphics filename, and with FormatWP.
- Fix: CSS for \textup.
- Fix: Added \slshape.

Chinese
- Added ctex package and related classes, xeCJK.
- Prevented CJK, CJKutf8 unless xeCJK, ctex are used.

packages
- chemfig: Docs for new macro \polymerdelim.
- asymptote: Docs for compilation.
- chngpage: Fix to load lwarp-changepage.
- algorithm2e: Fix with non-book classes.
- register: Updated to v1.8.
- nicefrac: Improved font control and CSS, honors nice and ugly.
- units: Improved font control and CSS, honors tight and loose.
- xfrac: Improved CSS.
- textcomp and xunicode: Fix conflicts with \textcircled.
- ulem: Improved compatibility with CJKulem, lateximage.
- MathJax and siunitx: Removed inoperable extension.
- Added bitpattern, pdfcomment, pdfmarginpar, tram, unitsdef, xechangebar.
- Added musicography, octave, semantic-markup.
- Added 2in1, flippdf, notespages, rviewport, twoup.

v0.61: Custom compilation, EPS-related packages, documentation, indexes.

docs
- Split index into multiple indexes.
- Improved documentation regarding font selection. See section 7.4.
- Added documentation regarding debugging options. See section 35.

- Added documentation regarding HTML entities inside program listings. See section 8.2.1.

custom compiling

- Added options to specify the shell commands to execute for **`lwarpmk print`** and **`lwarpmk html`**, allowing the use of lwarp with perltex, pythontex, etc. If not specified, these are set automatically depending on the LaTeX engine, `--shell-escape`, and lwarp options. See section 9.

⚠ changed names

- Changed macro names to match `\displaymathother`, `\displaymathnormal`:

Old	New
`\StartDynamicMath`	`\inlinemathother`
`\StopDynamicMath`	`\inlinemathnormal`

fixes

- Fix: Paragraph tags in a `tabular`.
- Fix: supertabular and xtab captions.
- Fix: DVI LaTeX `\includegraphics` EPS images.
- Fix: newfloat lists.
- Fix: CSS footnotes text align, minipage tabular and footnote margins.

packages

- Added epsfig, psfrag, psfragx, pstool.
- Added copyrightbox, pdfprivacy, thinsp, threadcol, uspace.
- Added chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.

v0.60: Fixes for longtable, listings.

fixes

- longtable, etc.: Fixes for slowdown and memory management for very long tables.
- listings: Fix for HTML entities, and also when used inside a list.
- diagbox: Fix for incorrect HTML par tags.

packages

- Added 2up, booklet.
- Added bophook, draftfigure, fullminipage, grid-system, layaureo.
- Added leading, widows-and-orphans.
- Added fancytabs, thumb, thumbs.

v0.59: DVI *latex*, MathJax, asymptote, pdftricks and pstricks, epstopdf, brqen.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- Added an error if `lwarpmk.conf`'s format has changed and the document must be recompiled.
- Added a warning if the `lwarpmk.conf` configuration file appears to be for the wrong operating system, in case files are transferred between systems.
- Added

  ```
  lwarpmk epstopdf <list-of-EPS-files>
  ```

  to quickly convert a document's EPS images to PDF or SVG. See section 8.8.

DVI *latex*

- Added support for DVI *latex*. See section 7.5.

latexmk
- Fix for `--shell-escape` with *latexmk*.

math
- Updated MathJax script to v2.7.4.
- Fix: Mathjax chapter number removed from non-numeric tagged equations.
- Added MathJax support for nicefrac, units.
- Fix for `\[` and `\]` with `\displaymathnormal`.

images
- Fix for `\includegraphics` filename expansion.
- `\includegraphics` now works with `.pdf` and `.eps` filename extensions.

packages
- Moved amsmath out of the lwarp core.
- Fix for chemformula `\NMR`.
- Added asymptote, pdftricks, pstricks, pst-eps.
- Added breqn, SIunits.
- Added bxpapersize, canoniclayout, draftcopy, fnbreak, nccfancyhdr.
- Added accsupp, axessibility.
- Added xunicode.
- Improved and now supports epstopdf.
- Tested to work as-is: eepic, sepfootnotes.

docs
- Added information about setting up a development version of lwarp.

v0.58: Extensive improvements in indexing, glossaries. Adds PDF-inclusion packages.

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk
- *lwarpmk*: Added the `-p` option to specify the project name.

glossaries
- *lwarpmk*: Now uses *makeglossaries* for glossary generation, allowing the processing of multiple glossaries at once.
- Added lwarp option `GlossaryCmd` to specify the shell command used by **`lwarpmk printglossary`** and **`lwarpmk htmlglossary`**. Defaults to **`makeglossaries`**.

index and glossary
- Docs: Extra indexing options. See section 8.6.14.
- Added support for *makeindex*. (Previously supported only *xindy*.) Also added indexing packages listed below.
- Added lwarp options `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to specify shell commands used by **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, and *latexmk*. May be preset with the `makeindex` or `xindy` lwarp options. See section 7.5.
- Added lwarp options `makeindex` and `xindy` to set `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to sensible values for a typical single index. See section 7.5.
- Added lwarp option `makeindexStyle` to tell *lwarpmk* to use a custom style instead of `lwarp.ist`. See section 8.6.20.
- Fix for index entries with `\see`, `\seealso`, `\emph`, `\textbf`, etc.

misc. fixes
- Replaced each `\csuse` with `\@nameuse` for improved error detection.
- Additional internal print/HTML macro selection improvements.

- Fix: `\printindex` finishes pending `\index` writes first.

packages
- Fixes for memoir: makeidx, ccaption, multiple indexes, `\specialindex`.
- Fixes for komascript: Indexing improvements.
- Added imakeidx, index, repeatindex, splitidx.
- Added attachfile, attachfile2, intopdf, pdfpages, pdfx.
- Added cases.
- Tested to work as-is: notes2bib, hvindex.

v0.57: algorithm2e, float styles, tabular packages, internal improvements.

MathJax
- Added support for MathJax equations with `\footnote`, `\footnotemark`.

math macros
- Added `\StartDefiningMath` and `\StopDefiningMath` for use when defining macros in the preamble which contain $. See section 8.7.7.

dynamic math
- Added `\inlinemathother` and `\inlinemathnormal` to delimit math expressions which depend on a variable condition such as a counter. Such expressions will not be hashed for reuse, and will be converted to SVG math images even when MathJax is enabled. See section 8.7.8.

⚠ new name
- Renamed `\EndDefiningTabulars` to `\StopDefiningTabulars`.

`lateximage alt` tags
- Improved localization for `lateximage` HTML `alt` tags. For SVG math images, the `alt` tag under some conditions will be set to `\MathImageAltText`, which defaults to `math image`. For packages, the `alt` tag is set using the package name followed by `\PackageDiagramAltText`, which defaults to `diagram`. Ex:

  ```
  (-xy- diagram)
  ```

  See section 7.6.
- Fix: Improved print/HTML macro selection.

misc. fixes
- Fix: `\href` text catcodes.
- Fix: `\subref` text.
- Fixes: Colored `\rule` and `\boxframe`.

packages
- float, rotfloat: Adds support for float styles `ruled` and `boxed`.
- float: Fix: Do not create `\l@<type>` until `\listof` is used.
- marginnote: Fix: Long optional argument.
- ellipsis: Adds `\midwordellipsis`.
- breakurl: Fix for text catcodes.
- Added algorithm2e, register, ltablex, xltabular, xellipsis, trimclip, errata, vowel, xpiano.
- Prevents glossary.
- Tested to work as-is with gauss, phonrule, piano, SIunits, tikzcodeblocks.

v0.56: Shell escape, tabular packages.

lwarpmk
- Added

  ```
  lwarpmk pdftosvg <list-of-PDF-files>
  ```

  to quickly convert a document's PDF images to SVG, for use with HTML. See section 8.8.

- Added support for `--shell-escape`. See section 7.3.

tabular
- Added support for array `w` and `W` columns.
- Fix: `\multicolumn` parameter handling.
- Added support for double `\hlines`, `\midrules`, and vertical rules.
- Added support for arydshln dashed lines with HTML `tabular`, but reverts to plain rules for `lateximage` and SVG math `array`.

misc. fixes
- Fix: `\thinspace`.
- Fix: paralist compact environments.

packages
- Added parnotes, quoting, lua-check-hyphen, tocenter, underscore.
- Added bibunits.
- Tested to work as-is with babelbib, bodegraph, fast-diagram, nicematrix, structmech.

v0.55: Various fixes.

misc fixes
- Fix: Extraneous space in file links, which also prevented *Calibre* EPUB conversions.
- Fix: Float optional argument regression.
- Fix: `\ForceHTMLTOC` with `\phantomsection`.
- Fix: Overfull boxes in `lateximages`.
- Fix: QED symbols in `lateximage`.

packages
- koma-script: Fix: Figure with `\centering`, etc.
- Added clrdblpg.

v0.54: Float `\centering`, improved image checks.

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk
- `lwarpmk limages` checks for the presence of the HTML version of the document and valid image references before attempting to create the `lateximages`.
- *lwarpmk*: Improved error message if configuration file does not exist.

BibTeX
- Added documentation for avoiding error with BibTeX and `\etalchar`. See section 8.6.9.

polyglossia
- Added documentation regarding polyglossia. See section 8.15.4.

macros in section names
- Added documentation regarding the use of macros in section names. See section 8.1.

document encoding

⚠ New and revised encoding options
- Renamed and added package options:

Old Package Option	New Package Option
`xdyFilename`	`xindyStyle`
`IndexLanguage`	`xindyLanguage`
–	`xindyCodepage`
–	`pdftotextEnc`

Use these options along with inputenc or inputenx to process documents in an encoding other than UTF-8. See section 7.4.

floats with \centering, etc.

- Floats now honor \centering, \raggedright, \raggedleft, and their ragged2e equivalents, when placed directly after:

```
\begin{floattype}
\centering
```

misc. fixes

- tikz: \pgfpicture, fit, align, font.
- ragged2e: \centering etc.
- hyperref: \hypertarget was creating duplicate of \label.
- hyperref: Active chars inside \hyperref, \hyperlink.
- hyperref: \ref inside \hyperlink caused a nested HTML link.
- glossaries: Fix when not using babel or polyglossia.
- textcomp: \textperthousand.
- LaTeX core verse environment: line spacing.

⚠

- Removed \citetitle, adjusted \attribution.

packages

- memoir: Minor update for v3.7g.
- Added inputenx, bibunits, chngpage, forest, magaz, gridset.
- Prevents loading ae, aecc, t1enc, and wasysym.

v0.53: Improved image checks.

lwarpmk

- *lwarpmk*: Added a warning about corrupted images due to the need to recompile the document one more time.
- *lwarpmk*: Added the **lwarpmk cleanlimages** command.
- Added documentation for **lwarpmk cleanlimages** and **lwarpmk pdftohtml**.

v0.52: Improved footnotes, SVG math.

documentation

- Improved install instructions regarding lwarp_baseline_marker.png.
- Added documentation regarding footnotes in section headings, and footnotes with \VerbatimFootnotes from fancybox, fancyvrb. See section 8.5.4.
- Added documentation regarding font selection when using XeLaTeX or LuaLaTeX with fontspec and traditional font packages. See section 7.4.

SVG math

- Fix: Limit the number of background tasks when generating lateximages.
- Added user-adjustable SVG math font scaling. See section 80.3.
- Added warnings if lwarp_baseline_marker.png is not present, or if graphicx or graphics is not loaded.
- Improved \ensuremath hashing expansion.
- Fix: equation* with split.
- tabbing now works inside a lateximage. Use for math in tabbing.

MathJax

- Fix: MathJax script was not executing in some conditions.
- Added \CustomizeMathJax to add custom functions. See section 8.7.

footnotes

- Fix: Footnote numbering when using HTMLDebugComments.

- Fix: Footnote paragraph tags.
- Fix: `FootnoteDepth` defaults to `\subsubsection`.

misc. fixes
- Fix: `\kill` in a `lateximage`.
- Fix: `\FileDepth`, misc. others, when input encoding is not `utf8`.
- Fix: `\texorpdfstring` in a section name.

packages
- hyperref emulation: Fix for #, %, &, ~, _ characters in URLs.
- fancybox, fancyvrb: Initial support for `\VerbatimFootnotes`.
- nicefrac: Added with fix for `\ensuremath`.
- graphicx: Fix for option defaults. Added v1.1a/b options.
- endfloat: Updated for v2.6.
- url: Fixes for active characters.

v0.51: Improved SVG math, added numerous chemistry packages.

documentation
- Docs: Added Things to avoid.
- Docs: Added to Converting an existing document.
- Docs: Multiple authors and affiliations with custom classes. See section 8.6.1.
- Docs: tikz with matrices. See section 8.8.1.

SVG math
- Improved SVG math baseline.
- Improved SVG math font and color.
- Faster SVG math rendering.
- Improved support for display math containing complicated math objects, such as tikz-cd. See section 8.7.9.
- Fix: `\addcontentsline` inside SVG math.
- Fix: SVG math containing an embedded `lateximage`.

MathJax
- MathJax now handles `\ensuremath` in expressions.

misc. fixes
- Fix: Added `alignat` environment.
- Fix: afterpackage no longer required, which conflicted with scrlfile.
- Fix: titling `\thanks` mark.
- Fix: fancybox improvements.
- Fix: tikz `\tikz` macro. (Previously only the `tikzpicture` environment worked.)
- Fix: tikz with optional argument.

packages
- Added mhchem, chemfig, chemformula, chemmacros, chemnum, chemgreek, epstopdf-base, grid, ltxgrid.

v0.50: Improved SVG math.

SVG math
- SVG math and other `lateximages` now are converted to SVG using parallel background tasks, utilizing all available CPU cores.

- Inline SVG math image file names now are MD5 hashes made from their source LaTeX code. Identical inline math expressions, such as multiple instance of x, now share a single image file. This reduces the number of images to store, transmit, process, and display. Each image file is only converted to SVG a single time, and reused if it already exists. Display math and other forms of SVG image such as `picture` and Ti*k*z still use individual image files which are recreated each time **`lwarpmk limages`** is run.
- Fixes: SVG math and/or `\underline` in a sectioning file name.
- Improved SVG display math and tags.
- Improved SVG math and siunitx `alt` tags.
- Improved siunitx units.
- Fix: `\ensuremath` with MathJax now creates a `lateximage`.
- Fix: `\centering`, etc. in SVG math, `lateximage`, Ti*k*z.

misc. fixes
- Fix: Made various macros robust, additionally fixing authblk.
- Fix: ntheorem if neither `standard` nor `amsthm` selected.
- Fix: listings: Improved column alignment.
- Fix: Load fontspec if necessary.

packages
- Added xy, epstopdf, diagbox, pbox, bytefield, axodraw2, phfqit, schemata, dblfloatfix, nonfloat, morefloats.

v0.49:

tabular
- Added xcolor `\rowcolors`.
- Fix: `\noalign` inside a `tabular`.

math
- Fix: `\eqref` in a caption.

misc fixes
- Fix: Incorrect PDF font size changes caused occasional HTML corruption.
- Fix: printlen changes are now grouped for HTML output.

packages
- Added vwcol, vertbars, hyphenat, lineno, fnlineno, figsize, hypdestopt, pagegrid, pdfrender, luacolor, resizegather.

v0.48:

documentation
- Added some documentation regarding converting an existing document. See section 6.

cleveref
- Updated compatibility for new cleveref v0.21.

tabular
- Fix: Ignores optional tabular column arguments.

minor updates
- Added `\leftline`, `\centerline`, `\rightline`.
- Lists have improved font control via `\makelabel`.
- Print-mode `lateximage` now boxed to the natural width of its multiline contents.
- `abstract` now allows an optional name, as required by some classes.

math
- Fix: Improved spacing, `\mbox`, and font sizes with SVG math, Ti*k*z.
- siunitx: Improved SVG math, fraction compatibility, color output.

misc. fixes
- Fix: LOF/LOT links.

- Fix: Virtual page size grouping caused excessive PDF page breaks.
- Fix: Parsing similar package names in a single `\usepackage`.
- Fix: Adapts to classes without `\part`.
- Fix: `\newline` in `\title` was causing `<br>` in window title.
- Fix: `\maketitle` with `\cr`, `\crcr`, `\noalign`, for IEEEtran class.
- Fix: xfrac neutralized `BlockClass` and others.
- Fix: todonotes and luatodonotes: Improved `\todototoc`.

packages
- Added colortbl, chapterbib, acro, acronym, hypernat, hypcap, stfloats, vmargin, fancyheadings.
- fancyref: Now directly supported.

v0.47:

math
- Improved SVG math baseline and sizing.
- Fixes: SVGmath in captions, subcaptions, `\nameref`.
- Fixes: Line wrap at hyphen in HTML output.

packages
- Added endheads, multitoc, sectionbreak, blowup, xurl.

v0.46:

⚠ name change
- `\PrintStack` changed to `\LWRPrintStack`.

misc. fixes
- Fix: Empty lines between `tabular` rows.
- Fix: Stack unnesting.
- Fix: SVG math and `lateximages` in numerous situations.
- Fix: Spaces in `\usepackage`.
- Fix: Now allows MathJax inside `verse`.

v0.45:

documentation
- Improved *MiKTeX* install instructions.
- Improved graphics and epstopdf instructions.
- Updates to the Introduction.

memoir
- Added memoir, memhfixc. See section 8.13.

cross-references
- Fix: Now allows underscores in labels.
- Fix: `\_` and `\<blank>` in section/file names.

math
- Fix: Now allows MathJax inside `tabbing`.

bibliography
- Fix: Bibliography `\em` names.
- Added cite, natbib, backref. (Also works as-is with biblatex.)

misc. fixes
- Fix: Empty lines between `tabular` rows.
- Fix: "Improper `\prevdepth`" with minipages, lists.
- Fix: Incorrect SVG math and `lateximages` with subfig.
- Fix: Lateximages from incorrect pages with Mathjax.
- Fix: Missing sidetoc if using listings.
- Fix: Added an array emulation package.

packages
- Added subfigure, prettyref, hanging, midpage, flafter, fltrace, changebar, endfloat, continue, fwlw, turnthepage, footnpag, pagesel, textfit, titleref.

v0.44:

koma-script
- Added koma-script classes (except scrlttr2, scrjura).
- Added scrextend, scrlayer, scrlayer-notecolumn, scrlayer-scrpage, scrhack, tocstyle, tocbasic.

HTML title and author
- Added `\HTMLTitle`. Fixed web page title if `\HTMLTitle` empty and no `\title` given and not using titling package.
- Fixed web page author if `\HTMLauthor` is empty and `\author` is not given.

encodings
- If using *pdflatex*, automatically loads T1 and UTF-8 encodings. (Additional fontenc encodings may be loaded after lwarp.)

lists
- Added `list` and `trivlist` environments, hang.

tabular
- Fix: `\multicolumn` alignment if formatting for a word processor.
- Added ltxtable.

math
- Fix: MathJax combined with `lateximages`.
- algorithmicx: Improved comment symbol and floating.

packages
- Completed todonotes and luatodonotes.
- Added todo, easy-todo, fixmetodonotes, fixme.
- Added soulutf8, soulpos, cancel.
- Added section, fancyref, ifoddpage.
- Added preview, atbegshi, watermark.
- Improved tocloft `\newlistof` and `\newlistentry`.

v0.43:

- Docs: Reorganized HTML customization, added an HTML settings table. See section 7.6.

footnotes
- Added `FootnoteDepth` to control the placement of pending footnotes before section breaks. By default, pending footnotes are printed before each `\subparagraph` or higher.

sectioning
- Fix: Expansion in section name.

tabular
- Fix: Ignore spaces in tabular column specification.
- Fix: Tabular rules at bottom or when finishing incomplete rows.
- Fix: `\multicolumn` at/bang/before/after specifications, trim, and vertical rules.
- Fix: supertabular and xtab column misalignment.

math
- Fix: `equation*`.
- Fix: SVG math in a section name.
- Fix: `\ref` and `\eqref` in SVG math.

packages
- Added todonotes and luatodonotes (but only `disabled`).
- Added breakurl.
- hyperref: Fix: Several macros were made robust, `\Gauge` added.

v0.42:

Support TEX!
- Added TEX development support page. (See page 2.)

word-processor conversion
- Improved assitance for word-processor conversions when boolean `FormatWP` is set `true`. See section 11.

⚠ name change
- The boolean `FormatWordProcessor` has been renamed `FormatWP`.

⚠ name change
- The boolean `HTMLMarkFloats` has been renamed `WPMarkFloats`.
- New booleans control whether to place additional marks around minipages, at the table of contents, at the LOF and LOT, and whether to print math as LATEX source for copy/paste into the *LibreOffice Writer TeXMaths* extension.
- Improved formatting for numerous objects. See section 11.

`tabbing`
- Add: `tabbing` environment.

overpic
- Add: overpic package. See section 360.

math
- Fix: Text copy/paste of $\mathcal{AMS}$ math environment numbers and names.
- Improved `\ensuremath`.
- MATHJAX with siunitx: Updated script and documentation.

symbols
- textcomp: Improved `\textinterrobangdown`.
- realscripts: Fix for subscripts in a `lateximage`.

load order
- morewrites: Enforces loading before lwarp.

v0.41:

`tabular`
- Added tabular vertical rules, subject to some limitations. See the rules section of section 8.10.1.
- Improved booktabs: Width and trim are honored.

⚠ new syntax
- Added `\mcolrowcell` for empty cells inside a `\multicolumnrow`. Use `\mcolrowcell` instead of `\mrowcell` for two-dimensional cells created by `\multicolumnrow`. Continue to use `\mrowcell` for empty cells in a `\multirow`. See section 339.2 on page 833.
- Fix: Unfinished tabular rows are automatically filled.
- Fix for tabular column specifiers while using babel-french. (`\NoAutoSpacing` is activated then nullified inside the tabular, due to a conflict with the tabular column parsing code.)

v0.40:

graphics, graphicx
- graphics and graphicx have been moved from the lwarp core, and are only loaded if requested with `\usepackage`.

`\includegraphics` path
⚠ image file extensions
- Improved graphics `\graphicspath` support. Multiple image directories may now be used. Refer to `.pdf` files without a file extension to allow the HTML version to use a `.svg`, `.png`, `.jpg`, or `.gif` version instead. See section 8.8.
- grffile is now directly supported instead of emulated.

bigdelim
- Fix for bigdelim, and improved documentation. See section 139.

symbols
- Improved LATEX and textcomp symbols.

fixes
- Fix for LATEX logos and `\InlineClass`, etc. inside a `lateximage`.

- Fix for xltxtra with XeLaTeX.
- Fixes for tocbibind with `\simplechapter`, etc.
- Fixes for `\multicolumnrow` and `\nullfonts` with older versions of multirow and xparse.
- Added `\underline`.

margins
- Added adjmulticol.

columns
- Added cuted, midfloat.

footnotes
- Added pfnote, fnpos, dblfnote.

tabular
- Added stabular, tabls.

sectioning
- Added sectsty, anonchap, quotchap.

v0.39:

title pages
- Improved the titlepage HTML code, `\thanks` notes, and `\maketitle`. titling is no longer required, but is still supported. The `\published` and `\subtitle` fields are no longer provided, but `\AddSubtitlePublished` replicates them using titling. See section 66.8. authblk is added, and should be loaded before titling. See section 66.

⚠ `\published` and `\subtitle` ⚠ load order

tabular
- `\multirow` now supports the new optional vpos argument.

multi column/row cell
- Added `\multicolumnrow` for combined `\multicolumn` and `\multirow`. See section 339.2.
- Tabular special cases:
  - Added `\TabularMacro` to mark custom macros inside tabular data cells, avoiding row corruption. See section 8.10.1.
  - Added `\ResumeTabular` for use when a `tabular` environment is defined inside another environment. See section 8.10.1.

⚠ macros inside tabular

⚠ tabular defined inside another environment

tabular
- Added supertabular, xtab, bigstrut, bigdelim.

margins
- Added fullwidth.

page layout
- Added addlines, anysize, a4, a4wide, a5comb, textarea, zwpagelayout, typearea, ebook.

v0.38:

forced single-pass compile
- Added **`lwarpmk print1`** and **`lwarpmk html1`** actions to force a compile of the project a single time. Useful when multiple passes are not needed, or changes were not detected.

starred sections
- Added `\ForceHTMLPage` and `\ForceHTMLTOC` to force a starred sectional unit onto its own HTML page and with its own TOC entry. See section 8.6.2.

updated tutorial
- Modified the tutorial to use the new `\ForceHTMLPage` and `\ForceHTMLTOC` macros.

packages
- Added appendix, tocbibind, fncychap, fix2col.

font size
- Added relsize, scalefnt.
- Added realscripts, metalogo, xltxtra.
- Added grffile, romanbar.

page numbering
- Added arabicfront, chappg, nonumonpart, nopageno, romanbarpagenumber.

front & back matter
- Docs: Improved description of the use of front/back matter. See section 8.6.
- Fix: color requests xcolor.
- Fix: `\part` for article class.

v0.37:

`\include` for HTML
- `\include` now maintains independent `.aux` files for HTML versions.

latexmk
- comment, used by lwarp, now maintains independent cut files for print and HTML versions, helping *latexmk* to better know whether to recompile.

accents and symbols
- Improved support for LaTeX accents, textcomp, siunitx symbols.

babel-french
- Improved babel-french handling for load order and ~ tilde.

v0.36:
- Recorganized the documentation section regarding special cases and limitations. (Section 8)
- Improved source formatting.

boxes and frames
- `\fbox` and related now use `\fboxsep` and `\fboxrule`.
- `\makebox` and `\framebox` now use width and position.
- `\fcolorbox` and related now work inside a `lateximage`.

babel-french
- babel-french: Improvements for French variants, load order, footnotes, ellipses.

footnotes
- Improved footnote numbering. `lateximage` footnotes now appear as regular footnotes to match the numbering of the print version. Also fixed a regression with MathJax.

siunitx
- Improved siunitx units.
- Fix for filenames while using MathJax.
- Fix for `\rule` when xcolor is not loaded.
- Added transparent, upref.

v0.35: Fix: `\textbf` and related.

v0.34:

⚠ Optional arguments
- `BlockClass`'s optional argument has been moved in front of the mandatory argument:

  `BlockClass[style]{class}` (NEW)

  instead of:

  `BlockClass{class}[style]` (OLD)

  This change makes it more consistent with LaTeX standards, and avoids problems with space between arguments.

⚠ Optional arguments
- Likewise, `\InlineClass`'s optional argument now comes before the mandatory arguments:

  `\InlineClass[style]{class}{text}`

spans with minipages
- Improved compatibility between spans, minipages, lists, frames, and math. Handles minipages and lists inside an HTML span, such as an `\fbox` containing a minipage, although with minimal HTML fomatting. See section 8.3.3.

framing minipages
- `\fboxBlock` is added to frame minipages, tables, and lists with full HTML formatting but no longer inline, and behaves as `\fbox` for print output. The `fminipage` environment is added for framed minipages, as an environment with full HTML formatting, and draws a framed minipage in print output. See section 8.3.5. `\fbox` and minipages now often work in SVG math and `lateximages`. MATHJAX supports `\fbox`, but not `\fboxBlock` nor `fminipage`.

`lateximage`, SVG math, `tabular`
- Improved compatibility between `lateximage` and `minipage`, `\parbox`, `\makebox`, `\fbox`, `\framebox`, `\raisebox`, `\scalebox`, `\reflectbox`, `tabular`, booktabs.
- Improved font control for `lateximagees` and SVG math.

`eqnarray`
- Added the `eqnarray` environments.

verbatim packages
- fancyvrb is no longer required (preloaded), but is still supported.
- Added verbatim and moreverb.

framing packages
- Added fancybox, boxedminipage2e and shadow.

list packages
- enumitem is no longer required, but is still supported.
- Added enumerate and paralist.
- titleps is no longer required, but is still supported.
- Added crop.
- Added rotfloat, marginfit, and several minor packages; see the change log.

babel-french
- Adds fixed-width HTML spaces around punctuation when using babel-french. LuaTEX does not yet use the extra punctuation spacing.

v0.33:

- Tabular `@` and `!` columns now havetheir own HTML columns.
- `&` catcode changes are localized, perhaps causing errors about the tab alignment character `&`, so any definitions of macros or environments which themselves contain `tabular` and `&` must be enclosed within `\StartDefiningTabulars` and `\StopDefiningTabulars` (previously called `\EndDefiningTabulars`. See section 43. This change is not required for the routine use of tables, but only when a table is defined inside another macro or environment, and while also using the `&` character inside the definition. This may include the use inside conditional expressions.
- Several math environments were incorrectly placed inline. Also, for amsmath with SVG math, the `fleqn` option has been removed, resulting in improved spacing for aligned equations.
- Bug fixes; see the changelog.

v0.32: Bug fixes; no source changes needed:

- *lwarpmk* has been adjusted to work with the latest *luatex*.
- Spaces in the `\usepackage` and `\RequirePackage` package lists are now accepted and ignored.
- Fix for the glossaries package and `\glo@name`.

v0.31: Bug fix; no source changes needed:

- Improved compatibility with keyfloat, including the new `keywrap` environment.

v0.30:

⚠ lwarp-newproject

- lwarp-newproject has been removed, and its functions have been combined with lwarp.

  To modify existing documents, remove from the document source:

  ```
  \usepackage{lwarp-newproject}
  ```

  The lwarp package now produces the configuration files during print output, and also accepts the option `lwarpmk` if desired.

⚠ HTML setup changes.

- A number of macros related to HTML settings have been converted to options, and other macros and options have been renamed to create a consistent syntax:

Old Macro	New Package Option
`\HomeHTMLFileName`	`HomeHTMLFilename`
`\HTMLFileName`	`HTMLFilename`
`\useLatexmk`	`latexmk`
`\warpOSwindows`	`OSWindows`

Old Package Option	New Package Option
`lwarpmklang`	`xindyLanguage`
(new)	`xindyStyle`

Old Macro	New Macro
`\MetaLanguage`	`\HTMLLanguage`
`\HTMLauthor`	`\HTMLAuthor`
`\NewHTMLdescription`	`\HTMLDescription`
`\SetFirstPageTop`	`\HTMLFirstPageTop`
`\SetPageTop`	`\HTMLPageTop`
`\SetPageBottom`	`\HTMLPageBottom`
`\NewCSS`	`\CSSFilename`

- Per the above changes, in existing documents, modify the package load of lwarp, such as:

  ```
  \usepackage[
      HomeHTMLFilename=index,
      HTMLFilename={},
      xindyLanguage=english
  ]{lwarp}
  ```

- The file `lwarp_html.xdy` has been renamed `lwarp.xdy`. To update each document's project:

  1. Make the changes shown above.
  2. Recompile the document in print mode. This updates the project's configuration files, and also generates the new file `lwarp.xdy`.

3. The old file `lwarp_html.xdy` may be deleted.

- The new lwarp package option `xindyStyle` may be used to tell *lwarpmk* to use a custom `.xdy` file instead of `lwarp.xdy`. See section 8.6.21.
- Improvements in index processing:
  - *xindy*'s language is now used for index processing as well as glossary.
  - Print mode without *latexmk* now uses *xindy* instead of *makeindex*.
  - *texindy*/*xindy* usage depends on *pdflatex* vs *xelatex*, *lualatex*.
  - For *pdflatex* and *texindy*, the `-C utf8` option is used. This is supported in modern distributions, but a customized `lwarpmk.lua` may need to be created for use with older distributions.

v0.29:

- Add: `lwarpmklang` option for lwarp-newproject and lwarp. Sets the language to use while processing the glossary. (As of v0.30, this has been changed to the `IndexLanguage` option.) (As of v0.54, this has been changed to the `xindyLanguage` option.)
- Fix: `\includegraphics` when no optional arguments.

v0.28:

- `\HTMLAuthor {`⟨*name*⟩`}` assigns HTML meta author if non-empty. Defaults to `\theauthor`.
- Booean `HTMLDebugComments` controls whether HTML comments are added for closing `<div>`s, opening and closing sections, etc.
- Boolean `FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.
- Boolean `FormatWordProcessor` changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Name changed to `FormatWP` as of v0.42.
- Boolean `HTMLMarkFloats` adds text marks around floats only if the boolean `FormatWordProcessor` is `true`. These make it easier to identify float boundaries, which are to be manually converted to word-processor frames. Name changed to `WPMarkFloats` as of v0.42.
- Updated for the new MathJax CDN repository.
- Adds tabulary.
- Supports the options syntax for graphics.
- Improved index references, now pointing exactly to their target.
- Adds glossaries. *lwarpmk* is modified to add `printglosssary` and `htmlglossary` actions.

2 Introduction

The lwarp project aims to allow a rich LaTeX document to be converted to a reasonable HTML5 interpretation, with only minor intervention on the user's part. No attempt has been made to force LaTeX to provide for every HTML-related possibility, and HTML cannot exactly render every possible LaTeX concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the HTML conversion.

Several "modern" features of HTML5, CSS3, and SVG are employed to allow a fairly feature-rich document without relying on the use of JavaScript. Limited testing on older browsers shows that these new features degrade gracefully.

---

lwarp is a native LaTeX package, and operates by either patching or emulating various functions. Source-level compatibility is a major goal, but occasional user intervention is required in certain cases.

As a package running directly in LaTeX, lwarp has some advantages over other methods of HTML conversion. TeX itself is still used, allowing a wider range of TeX trickery to be understood. Lua expressions are still available with LuaTeX. Entire categories of LaTeX packages work as-is when used with lwarp: definitions, file handling, utilities, internal data structures and calculations, specialized math-mode typesetting for various fields of science and engineering, and anything generating plain-text output. Blocks of PDF output may be automatically converted to SVG images while using the same font and spacing as the original print document, directly supporting Ti*k*z and `picture`. Numerous packages are easily adapted for HTML versions, either by loading and patching the originals, or by creating nullified or emulated replacements, and all without resorting to external programming. As a result, several hundred packages have already been adapted (table 2), and an uncounted number more work as-is.

Packages have been selected according to several criteria: perceived importance, popularity lists, recent CTAN updates, CTAN topics, mention in other packages, support by other HTML conversion methods, and from sample documents taken from public archives. These include some "obsolete" packages as well.[1]

Assistance is also provided for modifying the HTML output to suit the creation of EPUB documents, and for modifying the HTML output to ease import into a word processor.

---

pdflatex, *xelatex*, or *lualatex* may be used, allowing lwarp to process the usual image formats. While generating HTML output, SVG files are used in place of PDF. Other formats such as PNG and JPG are used as-is.

[1] An amazing number of decades-old packages are still in use today.

SVG images may be used for math, and are also used for `picture`, Ti*k*z, and similar environments. The SVG format has better browser and e-book support than MathML (as of this writing), while still allowing for high-quality display and printing of images (again, subject to potentially bug-ridden[2] browser support).

Furthermore, SVG images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by `<alt>` tags holding the LaTeX source for the expression, allowing it to be copy/pasted into other documents.[3] Custom LaTeX macros may be used as-is in math expressions, since the math is evaluated entirely inside LaTeX. An MD5 hash is used to combine multiple instances of the same inline math expression into a single image file, which then needs to be converted to SVG only a single time.

The MathJax JavaScript display engine may be selected for math display instead of using SVG images. Subject to browser support and Internet access, MathJax allows an HTML page to display math without relying on a large number of external image files.[4] lwarp maintains LaTeX control for cross-referencing and equation numbering, and attempts to force MathJax to tag equations accordingly.

A *texlua* program called *lwarpmk* is used to process either the print or HTML version of the document. A few external utility programs are used to finish the conversion from a LaTeX-generated PDF file which happens to have HTML5 tags, to a number of HTML5 plain-text files and accompanying images.

lwarp automatically generates the extra files necessary for the HTML conversion, such as CSS and `.xdy` files, and configuration files for the utility *lwarpmk*. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects HTML output and then inputs the user's own source. This process allows both the printed and HTML versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during HTML conversion, lwarp first looks to see if it has its own modified version to use instead of the standard LaTeX version. These `lwarp-packagename.sty` files contain code used to emulate or replace functions for HTML output.

[2] Firefox has had an on-again/off-again bug for quite some time regareding printing SVGs at high resolution.

[3] There seems to be some debate as to whether MathML is actually an improvement over LaTeX for sharing math. The author has no particular opinion on the matter, except to say that in this case LaTeX is much easier to implement!

[4] One SVG image file per math expression, except that duplicate inline math expressions are combined into a single file according to the MD5 hash function of its contents. A common scientific paper can easily include several thousand files, and in one case the MD5 hash cut the number of files in half and the rendering time by 30%.

2.1 Typesetting conventions

Font weight, family, and style are used to indicate various objects:

Table 1: Typesetting conventions

package	LaTeX package.
program	Program's executable name.
`option`	Program or package option.
`filename`	File name in the operating system.
Brand Name	Proper name for a program, operating system, etc.
commands	Commands to be entered by the user.
`code`	Program code.
`\macroname`	LaTeX macro.
`environment`	LaTeX environment.
`counter`	LaTeX counter.
`boolean`	LaTeX boolean.
`<element>`	HTML element.
`attribute`	HTML attribute.
User Interface	A user-interface item.
ACRO	Acronym.

2.2 Supported packages and features

Table 2 lists some of the various LaTeX features and packages which may be used.

Package names are colored according to their support level:

name: Supported as-is.

name: Modifed to work with HTML output, and also as print output in SVG math or `latexmage` environments.

name: Emulated for HTML output.

name: Ignored for HTML output, but provides source-level compatibility.

Table 2: LaTeX lwarp package — Supported features

Category	Status and supported features.
Engines:	DVI LaTeX, pdfLaTeX, XeLaTeX, LuaLaTeX, upLaTeX
Compiling:	*latexmk*, *perltex*, *pythontex*, *make*, etc.
Classes:	article, book, report, scrartcl, scrbook, scrreprt, memoir, CJK-related as listed below.
Koma-script:	scrextend, scrhack, scrlayer. Others as listed below.
Memoir:	memhfixc
Languages:	babel, polyglossia. cjkpunct, xeCJK.
Chinese:	CTeX, ctex, upzhkinsoku, xpinyin, zhlineskip, zhspacing.
Japanese:	upLaTeX, LuaTeX-ja, gentombow, lltjext, plarray, plarydshln, plautopatch, plext, plextarray, plextarydshln, plextcolortbl, plextdelarray, pxatbegshi, pxeveryshi, pxftnright, pxgentombow, pxjahyper, pxpdfpages, pxpgfrcs, pxpgfmark, tascmac, zxjatype. bxjsarticle and related, ltjsarticle and related, luatexja, luatexja-fontspec, ujarticle and related, utarticle and related.
Korean:	kotex, luatexko, xetexko.

lwarp Supported Functions — continued

Category	Status
Page layout:	2in1, 2up, a4, a4wide, a5comb, addlines, anysize, atbegshi, blowup, booklet, bophook, bounddvi, bxpapersize, canoniclayout, changelayout, changepage, chngpage, clrdblpg, continue, draftcopy, draftfigure, draftwatermark, ebook, everyshi, fancyhdr, fancytabs, flippdf, fullminipage, fullpage, fwlw, geometry, gmeometric, grid, grid-system, gridset, layaureo, layout, layouts, leading, ltxgrid, nccfancyhdr, notespages, nowidow, pagegrid, pagesel, pdfcrypt, pdfprivacy, preview, ragged2e, rmpage, scrlayer-scrpage, scrpage2, setspace, textarea, threadcol, thumb, thumbs, titleps, tocenter, turnthepage, twoup, typearea, underlin, vmargin, watermark, widows-and-orphans, zwpagelayout.
Sectioning:	Adds `FileDepth` for splitting the HTML output. Files may be numbered sequentially or named according to section name. Common short words and punctuation are removed from the file-names. anonchap, bsheaders, fncychap, hypbmsec, indentfirst, quotchap, section, sectionbreak, secdot, sectsty, titlesec.
Table of contents, figures, tables:	Supported, with hyperlinks. minitoc, multitoc, shorttoc, titletoc, tocbasic, tocbibind, tocdata, tocloft, tocstyle.
Title page:	`\maketitle`, `titlepage`, authblk, titling.
Front & back matter:	abstract, appendix.
Indexing:	*makeindex* and *xindy* are supported, with hyperlinks. hvindex, idxlayout, imakeidx, index, makeidx, repeatindex, splitidx.
Glossary:	gloss, glossaries and *xindy*, nomencl.
Bibliography:	babelbib, backref, biblatex, bibunits, chapterbib, cite, hypernat, natbib, notes2bib, showtags.
Cross-references:	bookmark, breakurl, cleveref, fancyref, hypdestopt, hyperref, perpage, prettyref, titleref, url, varioref, xcite, xr, xr-hyper, xurl.
Margin notes:	marginal, marginfit, marginfix, scrlayer-notecolumn, versonotes.

lwarp Supported Functions — continued

Category	Status
Footnotes:	Adds `FootnoteDepth` to print footnotes at section breaks. bigfoot, dblfnote, endheads, endnotes, fixfoot, fnbreak, fnpara, fnpos, footmisc, footnote, footnotebackref, footnoterange, footnpag, manyfoot, marginnote, nccfoots, pagenote, parnotes, pfnote, sepfootnotes, sidenotes, tablefootnote.
Math:	Converted to SVG images with HTML `<alt>` tags containing the LaTeX source for the math expression. MathJax supported as an alternative. amsmath: $\mathcal{AMS}$ environments are supported. User-defined macros are available during converson, due to native LaTeX processing.
Theorems:	Native LaTeX theorems, amsthm, ntheorem, theorem.
Additional math:	Math fonts via SVG images, amscd, autonum, backnaur, bm, braket, breqn, cases, delarray, guass, jkmath, mathspec, mathtools, nicematrix, pb-diagram, resizegather, unicode-math, xfakebold, xy. Many others work as-is.
Display math with `\displaymathother`:	Complicated math objects in display math, such as tikz-cd, etc.
Units and fractions:	nicefrac, SIunits, siunitx, units, unitsdef, xfrac.
Floats:	Appear where declared. capt-of, caption, cutwin, dblfloatfix, endfloat, fix2col, flafter, float, floatflt, floatrow, fltrace, ftcap, hypcap, keyfloat, morefloats, multicap, newfloat, nonfloat, placeins, rotfloat, stfloats, subcaption, subfig, subfigure, subfloat, topcapt, trivfloat, wrapfig.
Tabular:	`tabular` environment, array, arydshln, bigdelim, booktabs, colortbl, ctable, diagbox, longtable, ltablex, ltxtable, multirow, supertabular, tabularx, tabulary, threeparttable, threeparttablex, xltabular, xtab.

lwarp Supported Functions — continued

Category	Status
Graphics:	graphics and graphicx. `\includegraphics` supports `width`, `height`, `origin`, `angle`, and `scale` tags, and adds `class`. References to PDF files are changed to SVG, other image types are accepted as well. `\rotatebox` and `\scalebox` are supported as well as HTML can handle. rotating is emulated but all objects are unrotated. `picture`, tikz, and xy are converted to an SVG image. asymptote, curves, datatool, eepic, epsfig, epstopdf, figsize, fitbox, grffile, media9, movie15, multimedia, overpic, psfrag, psfragx, pst-eps, pstool, pstricks, rviewport, tikz-3dplot.
xcolor:	Full package color names, any color models, and mixing. `\textcolor`, `\colorbox`, `\fcolorbox`. Enhanced for HTML compatibility.
Lists:	Standard LaTeX environments, enumerate, enumitem, eqlist, hang, listliketab, paralist.
Environments:	Standard LaTeX environments.
`minipage`, `\parbox`:	Some HTML5-imposed limitations. Nested minipages are supported. eqparbox, minibox, pbox, shapepar.
Quotations:	copyrightbox, csquotes, epigraph, quoting, verse.
Verbatim:	fancyvrb, moreverb, shortvrb, verbatim.
Frames:	boxedminipage2e, fancybox, framed, mdframed, niceframe, shadow, vertbars.
Multi-columns:	adjmulticol, multicol, multicolrule, vwcol.
Margins:	fullwidth, hanging, midpage.
Line numbering:	fnlineno, lineno.
Direct formatting:	`\emph`, `\textsuperscript`, `\textbf`, etc are supported. `\bfseries`, etc. are only supported in some cases. cancel, ellipsis, embrac, enparen, hyphenat, lettrine, lips, lua-check-hyphen, luacolor, magaz, pdfrender, realscripts, relsize, scalefnt, soul, soulpos, soulutf8, stackengine, textfit, thinsp, trimclip, truncate, ulem, umoline, underscore, uspace, xellipsis.
Acronyms:	acro, acronym.
Ordinals:	engord, fmtcount, nth.

lwarp Supported Functions — continued

Category	Status
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for thin-unbreakable, unbreakable, `\enskip`, `\quad`, `\qquad`, `\hspace`.
Rules:	`\rule` with width, height, raise, text color.
HTML reserved characters:	`\&`, `\textless`, and `\textgreater` are converted to HTML entities.
Fonts:	Used as-is. Appear in SVG math expressions or embedded image environments. fontaxes, nfssext-cfr, slantsc, tabfigures. Tested to work as-is: Special font macros in cfr-lm and others which use nfssext-cfr.
Symbols:	Native LaTeX diacriticals, academicons, bbding, chemgreek, dingbat, euro, eurosym, fontawesome, fontawesome5, gensymb, marvosym, metalogo, metalogox, pifont, textalpha, textcomp, textgreek, typicons, xunicode.
Files:	attachfile, attachfile2, hyperxmp, inputtrc, intopdf, pdfpages, pdfx, xmpincl.
Science and engineering:	algorithm2e, algorithmicx, ar, askmaps, axodraw2, bitpattern, blochsphere, bodegraph, bohr, bytefield, chemfig, chemformula, chemgreek, chemmacros, chemnum, circuitikz, elements, engtlc, fast-diagram, hepnicenames, heppennames, karnaughmap, karnaugh-map, listings, linop, mhchem, pgfgantt, phfqit, physics, qcircuit, register, simpler-wick, slashed, structmech, struktex. tikz-karnaugh, tikzcodeblocks
Arts and humanities:	foreign, forest, lyluatex, musicography, nameauth, octave, phonrule, piano, schemata, semantic-markup, tikz-dependency, vowel, xpiano
Admonitions:	notes.
Editorial:	changebar, changelog, changes, easy-todo, easyReview, ed, errata, fixme, fixmetodonotes, pdfcomment, pdfmarginpar, todo, todonotes, tram, xechangebar.

lwarp Supported Functions — continued

Category	Status
Accessibility:	accsupp, axessibility.
Debug:	chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.
Working as-is:	Various utility, calculation, file, and text-only packages, such as calc, fileerr, somedefs, trace, xspace. Also, most math-only packages, including specialized typesetting for various fields of science and engineering.

3 Alternatives

Summarized below are several other ways to convert a LaTeX or other document to HTML. Where an existing LaTeX document is to be converted to HTML, lwarp may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

3.1 internet class

Cls internet The closest to lwarp in design principle is the `internet` class by Andrew Stacey — an interesting project which directly produces several versions of markdown, and also HTML and EPUB. https://github.com/loopspace/latex-to-internet

3.2 TeX4ht

Prog TeX4ht http://tug.org/tex4ht/

Prog htlatex

This system uses native LaTeX processing to produce a DVI file containing special commands, and then uses additional post-processing for the HTML conversion by way of numerous configuration files. In some cases lwarp provides a better HTML conversion, and it supports a different set of packages. TeX4ht produces several other forms of output beyond HTML, including ODT and a direct path to EPUB, and is still being developed.

3.3 Translators

These systems use external programs to translate a subset of LaTeX syntax into HTML. Search for each on CTAN (http:\ctan.org).

Prog Hevea **HEVEA:** http://hevea.inria.fr/ (not on CTAN)

Prog TtH **TTH:** http://hutchinson.belmont.ma.us/tth/

Prog GELLMU **GELLMU:** http://www.albany.edu/~hammond/gellmu/

Prog LaTeXML **LaTeXML:** http://dlmf.nist.gov/LaTeXML/

Prog Plastex **PlasTeX:** https://github.com/tiarno/plastex

Prog LaTeX2HTML **LaTeX2HTML:** http://www.latex2html.org/
and http://ctan.org/pkg/latex2html.

Prog TeX2page **TeX2page:** http://ds26gte.github.io/tex2page/index.html

Finally, GladTeX may used to directly insert LaTeX math into HTML:

Prog GladTeX **GladTeX:** http://humenda.github.io/GladTeX/

3.4 AsciiDoc and Asciidoctor

AsciiDoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes LaTeX and HTML.

Prog AsciiDoc **Asciidoctor:** http://asciidoctor.org/ (More active.)

Prog AsciiDoctor **AsciiDoc:** http://asciidoc.org/ (The original project.)

3.4.1 Asciidoctor-LaTeX

The Asciidoctor-LaTeX project is developing additional LaTeX-related features.

Asciidoctor-LateX:
http://www.noteshare.io/book/asciidoctor-latex-manual
Prog Asciidoctor-LaTeX https://github.com/asciidoctor/asciidoctor-latex

3.5 Pandoc

Prog Pandoc A markup system which also reads and writes LaTeX and HTML.

Pandoc: http://pandoc.org/

(Watch for improvements in cross-references to figures and tables.)

3.6 Word processors

Prog Word
Prog LibreOffice
Prog OpenOffice

It should be noted that the popular word processors have advanced through the years in their abilities to represent math with a LaTeX-ish input syntax, unicode math fonts, and high-quality output, and also generate HTML with varying success. See recent developments in Microsoft ® *Word* ® and LibreOffice ™ *Writer*.

3.7 Commercial systems

Prog Adobe
Prog FrameMaker
Prog InDesign
Prog Flare
Prog Madcap

Likewise, several professional systems exist whose abilities have been advancing in the areas of typesetting, cross-referencing, and HTML generation. See Adobe ® *FrameMaker* ®, Adobe *InDesign* ®, and Madcap *Flare* ™.

3.8 Comparisons

AsciiDoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to require many combinations of special characters, resulting in a complicated mess of

syntax. By contrast, LaTeX spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that LaTeX is comparably easy to learn, while LaTeX provides many more advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of LaTeX vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a LaTeX back end, yielding high-quality results especially when the LaTeX template is adjusted, but they lose the ability to use LaTeX macros and other LaTeX source-document features.

The effort required to customize the output of each markup system varies. For print output, LaTeX configuration files are usually used. For HTML output, a CSS file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of lwarp, CSS is used, and much HTML output is adjusted through the usual LaTeX optional macro parameters, but further customization may require patching LaTeX code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

4 Installation

Table 3 shows the tools which are used for the LaTeX to HTML conversion. In most cases, these will be available via the standard package-installation tools.

Detailed installation instructions follow.

Table 3: Required software programs

Provided by your LaTeX distribution:

From TeXLive: http://tug.org/texlive/.

LaTeX: *pdflatex*, *xelatex*, or *lualatex*.

The lwarp package: This package.

The *lwarpmk* utility: Provided along with this package. This should be an operating-system executable in the same way that *pdflatex* or *latexmk* is. It is possible to have the lwarp package generate a local copy of *lwarpmk* called `lwarpmk.lua`. See table 4.

***luatex*:** Used by the *lwarpmk* program to simplify and automate document generation.

***xindy*:** The *xindy* program is used by lwarp to create indexes. On a MiKTeX system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

***latexmk*:** Optionally used by *lwarpmk* to compile LaTeX code. On a MiKTeX system, *Perl* may need to be installed first.

***pdfcrop*:** Used to pull images out of the LaTeX PDF.

Poppler PDF utilities:

***pdftotext*:** Used to convert PDF to text.

***pdfseparate*:** Used to pull images out of the LaTeX PDF.

***pdftocairo*:** Used to convert images to SVG.

These might be provided by your operating-system package manager, and MiKTeX provides miktex-poppler-bin-* packages.

From Poppler: poppler.freedesktop.org.

For MacOS®, see https://brew.sh/, install *Homebrew*, then

Enter ⇒ **`brew install poppler`**

For Windows, see MikTeX miktex-poppler-bin-*, or:
https://sourceforge.net/projects/poppler-win32/ and:
http://blog.alivate.com.au/poppler-windows/

***Perl*:**

This may be provided by your operating-system package manager, and may be required for some of the Poppler PDF utilities.

strawberryperl.com (recommended), perl.org

Automatically downloaded from the internet as required:

MathJax: Optionally used to display math. From: mathjax.org

4.1 Installing the lwarp package

There are several ways to install lwarp. These are listed here with the preferred methods listed first:

Pre-installed: Try entering into a command line:

Enter ⇒ **`kpsewhich lwarp.sty`**

If a path to `lwarp.sty` is shown, then lwarp is already installed and you may skip to the next section.

TEX Live: If using a TEX Live distribution, try installing via *tlmgr*:

Enter ⇒ **`tlmgr install lwarp`**

MiKTEX:

1. For newer versions of MiKTEX, install or update lwarp using the *MiKTeX Console* program.
2. For older versions of MiKTEX, to install lwarp the first time, use the *MiKTeX Package Manager (Admin)*. To update lwarp, use *MiKTeX Update (Admin)*.
3. Either way, also update the package miktex-misc, which will install and update the *lwarpmk* executable.

Operating-system package: The operating-system package manager may already have lwarp, perhaps as part of a set of TEX-related packages.

CTAN TDS archive: lwarp may be downloaded from the Comprehensive TEX Archive:

1. See `http://ctan.org/pkg/lwarp` for the lwarp package.
2. Download the TDS archive: `lwarp.tds.zip`
3. Find the TEX `local` directory:

   TEX Live:

   Enter ⇒ **`kpsewhich -var-value TEXMFLOCAL`**

   MiKTEX:

   In the **Settings** window, **Roots** tab, look for a local TDS root.

   This should be something like:

   `/usr/local/texlive/texmf-local/`
4. Unpack the archive in the TDS local directory.
5. Renew the cache:

   Enter ⇒ **`mktexlsr`**

   — or —

   Enter ⇒ **`texhash`**

   Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.

CTAN `.dtx` and `.ins` files: Another form of TEX package is `.dtx` and `.ins` source files. These files are used to create the documentation and `.sty` files.

1. See http://ctan.org/pkg/lwarp for the lwarp package.
2. Download the zip archive `lwarp.zip` into your own `lwarp` directory.
3. Unpack `lwarp.zip`.
4. Locate the contents `lwarp.dtx` and `lwarp.ins`
5. Create the `.sty` files:

   Enter ⇒ **`pdflatex lwarp.ins`**
6. Create the documentation:

```
pdflatex lwarp.dtx  (several times)
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
makeindex -s gind.ist lwarp.idx
pdflatex lwarp.dtx  (several times)
```

7. Copy the `.sty` files somewhere such as the TEX Live local tree found in the previous CTAN TDS section, under the subdirectory:

   `<texlocal>/tex/latex/local/lwarp`
8. Copy `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` to the same place as the `.sty` files.
9. Copy the documentation `lwarp.pdf` to a `source` directory in the local tree, such as:

   `<texlocal>/doc/local/lwarp`
10. Renew the cache:

    Enter ⇒ **`mktexlsr`**

    — or —

    Enter ⇒ **`texhash`**

    Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.
11. See section 4.2.1 to generate your local copy of *lwarpmk*.
12. Once the local version of `lwarpmk.lua` is installed, it may be made available system-wide as per section 4.2.

Project-local CTAN `.dtx` and `.ins` files: The `.dtx` and `.ins` files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant `*.sty` and `lwarpmk.lua` files may be used as-is, so long as they are in the same directory as the document source. The files `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` must also be copied as well. This approach is especially useful if you would like to temporarily test lwarp before deciding whether to permanently install it.

Just testing!

4.2 Installing the *lwarpmk* utility

(Note: If *lwarpmk* is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 4.2.1.)

After the lwarp package is installed, you may need to setup the *lwarpmk* utility:

1. At a command line, try executing **lwarpmk**. If the *lwarpmk* help message appears, then *lwarpmk* is already set up. If not, it is easiest to generate and use a local copy. See section 4.2.1.

2. For MiKTEX, try updating the miktex-misc package. This may install the *lwarpmk* executable for you.

   Otherwise, continue with the following:

3. Locate the file `lwarpmk.lua`, which should be in the `scripts` directory of the TDS tree. On a TEX Live or MiKTEX system you may use

   Enter ⇒ **kpsewhich lwarpmk.lua**

   (If the file is not found, you may also generate a local copy and use it instead. See section 4.2.1.)

4. Create *lwarpmk*:

   Unix: Create a symbolic link and make it executable:

   (a) Locate the TEX Live binaries:

   Enter ⇒ **kpsewhich -var-value TEXMFROOT**

   This will be something like:

   `/usr/local/texlive/<year>`

   The binaries are then located in the `bin/<arch>` directory under the root:

   `/usr/local/texlive/<year>/bin/<architecture>/`

   In this directory you will find programs such as *pdflatex* and *makeindex*.

   (b) In the binaries directory, create a new symbolic link from the binaries directory to `lwarpmk.lua`:

   Enter ⇒ **ln -s <pathtolwarpmk.lua> lwarpmk**

   (c) Make the link executable:

   Enter ⇒ **chmod 0755 lwarpmk**

   WINDOWS TEX Live: Create a new `lwarpmk.exe` file:

   (a) Locate the TEX Live binaries as shown above for UNIX.

   (b) In the binaries directory, make a *copy* of `runscript.exe` and call it `lwarpmk.exe` This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

   WINDOWS MiKTEX: Create a new `lwarpmk.bat` file:

   (a) Locate the MiKTEX binaries. These will be in a directory such as:

   `C:\Program Files\MiKTeX 2.9\miktex\bin\x64`

   In this directory you will find programs such as `pdflatex.exe` and `makeindex.exe`.

   (b) Create a new file named `lwarpmk.bat` containing:

   ```
   texlua "C:\Program Files\MiKTeX 2.9\scripts\lwarp\lwarp.texlua" %*
   ```

   This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

4.2.1 Using a local copy of *lwarpmk*

It is also possible to use a local version of *lwarpmk*:

1. When compiling the tutorial in section 5, use the `lwarpmk` option for the lwarp package:

   ```
   \usepackage[lwarpmk]{lwarp}
   ```

2. When the tutorial is compiled with *pdflatex*, the file `lwarpmk.lua` will be generated along with the other configuration files.

3. `lwarpmk.lua` may be used for this project:

   Unix:

   (a) Make `lwarpmk.lua` executable:
   Enter ⇒ **`chmod 0755 lwarpmk.lua`**

   (b) Compile documents with
   Enter ⇒ **`./lwarpmk.lua html`**
   Enter ⇒ **`./lwarpmk.lua print`**
   etc.

   (c) It may be useful to rename or link to a version without the `.lua` suffix.

   WINDOWS:

   Compile documents with either of the following, depending on which command shell is being used:
   Enter ⇒ **`texlua lwarpmk.lua html`**
   Enter ⇒ **`texlua lwarpmk.lua print`**
   etc.

   Or:
   Enter ⇒ **`lwarpmk html`**
   Enter ⇒ **`lwarpmk print`**
   etc.

4.3 Installing additional utilities

To test for the existence of the additional utilities:

Enter the following in a command line. If each programs' version is displayed, then that utility is already installed. See table 3 on page 74.

Enter ⇒ **`luatex --version`**
Enter ⇒ **`xindy --version`**
Enter ⇒ **`latexmk --version`**
Enter ⇒ **`perl --version`**
Enter ⇒ **`pdfcrop --version`**
Enter ⇒ **`pdftotext -v`**
Enter ⇒ **`pdfseparate --version`**
Enter ⇒ **`pdftocairo -v`**

To install *xindy*, *latexmk*, and *pdfcrop*:

The TEX utilities *xindy*, *latexmk*, and *pdfcrop* may be installed in *TexLive* with *tlmgr*, installed by *MiKTeX*, provided by your operating system's package manager, or downloaded from the *CTAN* archive:

http://ctan.org/pkg/xindy
http://ctan.org/pkg/latexmk
http://ctan.org/pkg/pdfcrop

Prog [requirement] pdftotext
Prog [requirement] pdfseparate
Prog [requirement] pdftocairo

To install the POPPLER utilities to a UNIX/LINUX system:

The tools from the POPPLER project should be provided by your operating system's package manager.

To install the POPPLER utilities to a MACOS machine:

1. Install *Homebrew* from https://brew.sh/:

```
/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"
```
Enter ⇒

2. Install the POPPLER utilities:

```
brew install poppler
```
Enter ⇒

To install the POPPLER utilities to a WINDOWS machine:

If using MikTEX, install a miktex-poppler-bin-* package. Otherwise:

1. See table 3 on page 74.
2. Download and extract the POPPLER utilities *pdftotext*, *pdfseparate*, and *pdfseparate* to a directory, such as `Poppler`.
3. In the **Start** window, type "Path" to search for results related to Path. Or, open the control panel and search for "Path".
4. Choose **Edit the system environment variables** in the control panel.
5. Choose the **Environment Variables** button.
6. Choose the **Path** variable, then the **Edit** button.
7. Choose the **New** button to make an additional entry.
8. Enter the `bin` directory of the POPPLER utilities, such as:

   `C:\Users\<myname>\Desktop\Poppler\poppler-0.5_x86\poppler-0.5\bin`

   Be sure to include `\bin`.
9. Click **Ok** when done.

Prog [requirement] perl

To install PERL to a WINDOWS machine:

1. Download and install a version of PERL, such as STRAWBERRY PERL, to a directory without a space in its name, such as `C:\Strawberry`.
2. Edit the **Path** as seen above for the POPPLER utilities.
3. Enter the `bin` directory of the *perl* utility, such as:

   `C:\Strawberry\perl\bin`

   Be sure to include `\bin`.
4. Click **Ok** when done.

Any utilities installed by hand must be added to the PATH.

5 Tutorial

This section shows an example of how to create an lwarp document.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

5.1 Starting a new project

1. Create a new project directory called `tutorial`.

File `tutorial.tex`

2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

   Copy from the documentation PDF:

   A listing is in fig. 1, which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

   Copy from the lwarp documentation directory:

File `lwarp_tutorial.txt`

⚠ Note: `.txt` suffix!

   Another copy may be found by entering into a command line:

   Enter ⇒ **`texdoc -l lwarp_tutorial.txt`**

   This should be in the `doc/latex/lwarp/` directory along with this PDF documentation. Copy `lwarp_tutorial.txt` directly into your `tutorial` directory, renamed as `tutorial.tex`.

⚠ Bad formatting!

   When using WINDOWS, use an editor other than NOTEPAD, since NOTEPAD does not accept the end-of-line from a UNIX text file.

3. Compile the project:

   Enter ⇒ **`pdflatex tutorial.tex`**

   (several times)

   (*xelatex* or *lualatex* may be used as well. lwarp also supports DVI *latex* for use with `.eps` images.)

4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in table 4. These files are created by the `lwarp` package.

(Two of the new files are configuration files for the helper program *lwarpmk*. Whenever a print version of the document is created, the configuration files for *lwarpmk* are updated to record the operating system, LaTeX engine (*latex*, *pdflatex*, *xelatex*, or *lualatex*), the filenames of the source code and HTML output, and whether the additional helper program *latexmk* will be used to compile the document.)

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarp package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern}            % pdflatex or dvi latex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec}           % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
%   HomeHTMLFilename=index,     % Filename of the homepage.
%   HTMLFilename={node-},       % Filename prefix of other pages.
%   IndexLanguage=english,      % Language for xindy index, glossary.
%   latexmk,                    % Use latexmk to compile.
%   OSWindows,                  % Force Windows. (Usually automatic.)
%   mathjax,                    % Use MathJax to display math.
]{lwarp}
% \boolfalse{FileSectionNames}  % If false, numbers the files.

% --- LOAD PDFLATEX MATH FONTS HERE ---

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor}             % (Demonstration purposes only.)
\usepackage{hyperref,cleveref}  % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarp Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2}        % Include subsections in the \TOC.
\setcounter{secnumdepth}{2}     % Number down to subsections.
\setcounter{FileDepth}{1}       % Split \HTML\ files at sections
\booltrue{CombineHigherDepths}  % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1}    % Include subsections in the side\TOC
\HTMLTitle{Webpage Title}       % Overrides \title for the web page.
\HTMLAuthor{Some Author}        % Sets the HTML meta author tag.
\HTMLLanguage{en-US}            % Sets the HTML meta language.
\HTMLDescription{A description.}% Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSFilename{lwarp_sagebrush.css}
```

```
\begin{document}

\maketitle                      % Or titlepage/titlingpage environment.

% An article abstract would go here.

\tableofcontents                % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math: $r = r_0 + vt - \frac{1}{2}at^2$
followed by display math:
\begin{equation}
a^2 + b^2 = c^2
\end{equation}


\begin{warpprint}   % For print output ...
\cleardoublepage    % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage      % HTML index will be on its own page.
\ForceHTMLTOC       % HTML index will have its own toc entry.
\printindex

\end{document}
```

Table 4: Configuration files created by print version

tutorial.pdf: The PDF output from LaTeX. The print version of the document.

tutorial_html.tex: A small `.tex` file used to create a parallel HTML version of the document, which co-exists with usual the PDF version, and which will have its own auxiliary files. In this way, both PDF and HTML documents may co-exist side-by-side.

Auxiliary files: The usual LaTeX files `.aux`, `.log`, `.out`, `.toc`, `.lof`, `.idx`. When an HTML version of the document is created, `_html` versions of the auxiliary files will also be generated.

lwarpmk.conf: A configuration file for *lwarpmk*, which is used to automate the compilation of PDF or HTML versions of the document.

tutorial.lwarpmkconf: Another configuration file used by *lwarpmk*, which is only useful if you wish to have several projects residing in the same directory.

.css files: `lwarp.css`, `lwarp_formal.css`, `lwarp_sagebrush.css` These files are standard for lwarp, and are not meant to be modified by the user.

sample_project.css: An example of a user-customized CSS file, which may be used for project-specific changes to the lwarp defaults.

lwarp.ist: Used by lwarp while creating an index using *makeindex*. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarp.xdy: Used by lwarp while creating an index using *xindy*. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarp_one_limage.txt: For WINDOWS only. Used to process SVG images in the background. Copied to `lwarp_one_limage.cmd` when images are generated.

lwarp_mathjax.txt: Inserted into the HTML files when MATHJAX is used to display math. This file should not be modified by the user.

comment.cut: A temporary file used by lwarp to conditionally process blocks of text. This file may be ignored.

When the `lwarpmk` option is given to the lwarp package:

lwarpmk.lua: A local copy of the *lwarpmk* utility.

On UNIX-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

5.2 Compiling the print version with *lwarpmk*

The *lwarpmk* utility program is used to compile either the printed or the HTML version of the document.

`lwarpmk print` is used to recompile a printed version of the document.

1. Re-compile the print version:

   Enter ⇒ **`lwarpmk print`**

   lwarpmk prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then *lwarpmk* informs you of that fact and then exits.

2. Make a small change in the original document, such as adding a space character.

3. Recompile again.

   Enter ⇒ **`lwarpmk print`**

   The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

4. Force a recompile to occur.

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk print`**

   `lwarpmk again` updates the date code for the file, triggering a recompile the next time the document is made.[5]

5. Process the index.[6] [7]

   Enter ⇒ **`lwarpmk printindex`**

6. Recompile again to include the index.

   Enter ⇒ **`lwarpmk print`**

7. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk print1`**

Note that the HTML customization commands are ignored while making the print version.

[5] Although, when using the utility *latexmk* (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

[6] The command **`lwarpmk printglossary`** is also available to process a glossary produced with the glossaries package. See section 8.6.12.

[7] Also see section 8.6.15 for index options.

5.3 Compiling the HTML version with *lwarpmk*

`lwarpmk html` is used to recompile an HTML version of the document.

1. Compile the HTML version:

   Enter ⇒ **`lwarpmk html`**

   (a) *lwarpmk* uses LaTeX to process `tutorial_html.tex` to create `tutorial_html.pdf`.

   (b) *pdftotext* is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.

   (c) *lwarpmk* manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`[8], `Some-math.html`, and the document's index in `_Index.html`.[9]

2. View the HTML page in a web browser.

   Open the file `tutorial.html` in a web browser.

   math Note that math is still displayed as its `alt` tag, which is the plain-text LaTeX source, until the images of the math expressions have been generated. Math may be displayed as SVG images or by a MathJax script, as seen in sections 5.4 and 5.5.

3. Force a recompile:

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk print`**

4. Process the HTML index and recompile:[10][11]

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   `_Index.html` is updated for the new LaTeX index.

5. Reload the web page to see the added index.

6. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk html1`**

[8] `First-chapter.html` also contains the first section, even though the second section is its own HTML page. This behavior is controlled by the boolean `CombineHigherDepths`.

[9] `index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

[10] The command **`lwarpmk htmlglossary`** is also available to process a glossary produced with the glossaries package. See section 8.6.12.

[11] Also see section 8.6.15 for index options.

5.4 Generating the SVG images

math as SVG images

By default lwarp represents math as SVG images, with the LaTeX source included in `alt` attributes. In this way, the math is displayed as it was drawn by LaTeX, and the LaTeX source may be copied and pasted into other documents.

`picture` and Ti*k*z

lwarp uses the same mechanism for `picture` and Ti*k*z environments.

1. Create the SVG images:

   Enter ⇒ **`lwarpmk limages`**

   Enter ⇒ **`lwarpmk html`**

2. Move to the tutorial's HTML math page and reload the document in the browser.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the LaTeX source.

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk limages`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[12] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ HTML instead of images

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect SVG images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

⚠ Lots of files!

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 5.5 to use MathJax instead.

[12] This becomes important when dealing with a document containing thousands of images.

5.5 Using MathJax for math

math with MathJax

Math may also be represented using the MathJax JavaScript project.

1. In the tutorial's source code, uncomment the `mathjax` package option for lwarp:

   ```
   mathjax, % Use MathJax to display math.
   ```

2. Recompile

   Enter ⇒ **`lwarpmk html`**

3. Reload the math page.

⚠ MathJax requirements

MathJax requires web access unless a local copy of MathJax is available, and it also requires that JavaScript is enabled for the web page. The math is rendered by MathJax. Right-click on math to see several options for rendering, and for copying the LaTeX source.

While using MathJax has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as LaTeX, and it may not support some math-related packages.

5.6 Changing the css style

For a formal css style, add to the preamble:

```
\usepackage{lwarp}
. . .
\CSSFilename{lwarp_formal.css}
. . .
\begin{document}
```

For a modern css style, `lwarp_sagebrush.css` is also provided:

```
\CSSFilename{lwarp_sagebrush.css}
```

See section 7.7 for more information about modifying the css styling of the document.

5.7 Customizing the HTML output

A number of settings may be made to control the HTML output, including filename generation, automatic compilation, math output, document splitting, meta data, and page headers and footers.

See section 7.6 for more information.

5.8 Using *latexmk*

latexmk is a LaTeX utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the `latexmk` option for the lwarp package:

   ```
   latexmk, % Use latexmk to compile.
   ```

2. Recompile the printed version of the document.

   Enter ⇒ **`lwarpmk print`**

   lwarp updates its own configuration files (`lwarpmk.conf` and `tutorial.lwarpmkconf`) whenever the printed version of the document is compiled. These configuration files remember that *lwarpmk* should use *latexmk* to compile the document.

3. Recompile the document.

   Enter ⇒ **`lwarpmk print`**

   and/or

   Enter ⇒ **`lwarpmk html`**

Changes are detected by comparing checksums rather than modification times, so `lwarpmk again` will not trigger a recompile, but *latexmk* has a much better awareness of changes than the *lwarpmk* utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source, and a single recompile may be forced with:

forced single-pass recompile

Enter ⇒ **`lwarpmk print1`**

and/or

Enter ⇒ **`lwarpmk html1`**

5.9 Using XeLaTeX or LuaLaTeX

XeLaTeX or LuaLaTeX may be used instead of LaTeX.

1. Remove the auxiliary files for the project:

   Enter ⇒ **`lwarpmk cleanall`**

2. Use *xelatex* or *lualatex* to compile the printed version a single time.

   Enter ⇒ **`xelatex tutorial.tex`**

   -or-

   Enter ⇒ **`lualatex tutorial.tex`**

   When the compile occurs, the configuration files for *lwarpmk* are modified to remember which TeX engine was used. XeLaTeX or LuaLaTeX will be used for future runs of *lwarpmk*.

3. To recompile the document:

   Enter ⇒ **`lwarpmk print`**

   -and-

   Enter ⇒ **`lwarpmk html`**

4. Also remember to update the indexes and recompile again:

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk printindex`**

   Enter ⇒ **`lwarpmk print`**

5.10 Using DVI LaTeX

Traditional DVI LaTeX may also be used along with `.eps` image files. An SVG version of each image must also be provided. *lwarpmk* may be used to convert image formats.

To convert EPS files to PDF:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

To convert PDF files to SVG:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

⚠ bitmapped fonts See section 7.4 regarding font selection to avoid the use of bitmapped fonts.

5.11 Using a glossary

lwarp supports the gloss and glossaries packages, although this tutorial does not supply an example.

5.11.1 gloss package

See section 8.6.11.

5.11.2 glossaries package

To process the glossary for the print version:

Enter ⇒ **`lwarpmk printglossary`**

⚠ (If **`makeglossaries`** is not found, see section 8.6.12.)

To process the glossary for the HTML version:

Enter ⇒ **`lwarpmk htmlglossary`**

In each case, the document will have to be recompiled afterwards:

Enter ⇒ **`lwarpmk html1`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk print1`**

Enter ⇒ **`lwarpmk print`**

See section 8.6.12 to set options for processing glossaries.

5.12 Cleaning auxiliary files

To remove the auxiliary files `.aux`, `.toc`, `.lof`, `.lot`, `.idx`, `.ind`, `.log`, and `.gl*`, and a few others:

Enter ⇒ **`lwarpmk clean`**

5.13 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the `.pdf` and `.html` files:

Enter ⇒ **`lwarpmk cleanall`**

5.14 Cleaning the images from the `<project>-images` directory

The `<project>-images` directory contains SVG images automatically generated for inline and display math, tikz, etc. To remove all the images from the `lateximages` directory:

Enter ⇒ **`lwarpmk cleanlimages`**

5.15 Converting PDF or EPS images to SVG

HTML cannot display PDF or EPS images, so any external PDF graphics images must be converted to SVG format. *pdftocairo* and *epstopdf* may be used one image at a time, but *lwarpmk* also provides a way to convert PDF or EPS images in bulk:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

Be sure to always provide SVG files for HTML output.

5.16 Creating HTML from an incomplete compile

During testing it may be useful to finish the HTML conversion even when the document had errors and did not compile successfully. To attempt an HTML conversion of an incomplete document:

Enter ⇒ **`lwarpmk pdftohtml [-p project]`**

5.17 Processing multiple projects in the same directory

⚠ xr, xr-hyper, xcite

It is possible to have several projects in the same directory. *lwarpmk* has an optional parameter which is the document to compile.

To create each project:

Enter ⇒ **pdflatex project_a**

Enter ⇒ **pdflatex project_b**

Each project is given its own configuration file:

`project_a.lwarpmkconf, project_b.lwarpmkconf`

To compile each project with `lwarkmk`:

Enter ⇒ **lwarpmk print -p project_a**

Enter ⇒ **lwarpmk print -p project_b**

Enter ⇒ **lwarpmk html -p project_a**

Enter ⇒ **lwarpmk html -p project_b**

To generate each project's images:

Enter ⇒ **lwarpmk limages -p project_a**

Enter ⇒ **lwarpmk limages -p project_b**

To clean each project's images:

Enter ⇒ **lwarpmk cleanlimages -p project_a**

Enter ⇒ **lwarpmk cleanlimages -p project_b**

To clean each project's auxiliary files:

Enter ⇒ **lwarpmk cleanall -p project_a**

Enter ⇒ **lwarpmk cleanall -p project_b**

If using *bibtex*, for example, the HTML version must also be processed:

Enter ⇒ **bibtex project_a_html**

5.18 Using the *make* utility

lwarpmk has an action which may be useful for integration with the common *make* utility:

```
lwarpmk pdftohtml [-p project]
```

make may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then *lwarpmk* may be used to convert each target to HTML files.

5.19 What next?

How do I do something? See the General Index.

Something do not work! See the Troubleshooting Index or section 13: Troubleshooting.

Package options: See section 28, Package options.

HTML and filename settings: See section 7.6, Customizing the HTML output.

Footnote placement: See section 7.6, Customizing the HTML output.

Title page, indexing, glossaries: See section 8.6, Front and back matter.

Shell escape: See section 7.3, Shell escape.

CSS customization: See section 7.7, Customizing the CSS.

Localization: (languages) — See section 7.1, Localization.

Accessibility: (`alt` and `title` tags) — See section 7.2, Accessibility.

Converting an existing document: See section 6, Converting an existing document.

EPUB conversion: See section 10, EPUB conversion.

Word processor conversion: See section 11, Word-processor conversion.

6 Converting an existing document

To convert an existing document for use with lwarp:

1. Arrange the document in the following order:
   (a) Declare the `\documentclass`.
   (b) Load text fonts.
   (c) Load inputenc or inputenx, fontenc, and/or fontspec.
   (d) Load lwarp.
   (e) Load remaining packages.
2. Modify the document:

⚠ math in section names

   (a) If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

⚠ `scale`

   (b) Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

   to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

   (c) Possible changes to `tabular` environments include: `*` columns, multirow, longtable, supertabular, xtab, bigdelim. See section 8.10.1.
   (d) Possible option clashes with memoir. See section 8.13.
   (e) If using indexes, see section 8.6.15.
   (f) If using many indexes, glossaries, `.aux` files, etc., see section 8.6.15 regarding morewrites. If morewrites is already used, be sure to add the setup with `allocate=10`.
   (g) Other changes as per Special cases and limitations, section 8.
3. Convert any PDF images to SVG. See section 8.8.
4. Manually compile the print version with *latex*, *pdflatex*, *lualatex*, or *xelatex*.
5. `lwarpmk print` to finish the print version.
6. `lwarpmk html` to create the HTML version.
7. `lwarpmk limages` to create the SVG images of any SVG math, `lateximage`, Ti*k*Z, etc.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

7 Additional details

7.1 Localization

Regional localization is supported by lwarp via the following package options and macros:

Object names: LaTeX provides redefinable names for various objects, and lwarp adds a few more. Use `\renewcommand` to change these.

`\abstractname`: This macro is honored by lwarp.

`\linkhomename`: Displayed by the link to the homepage.

`\sidetocname`: Displayed at the head of the sideTOC.

HTML settings: See table 6 and section 7.6 for details.

`\HTMLLanguage`: The language to declare for each web page.

`\ImageAltText`, `\MathImageAltText`, `\PackageDiagramAltText`, `\AltTextOpen`, `\AltTextClose`: The defaults used for HTML `alt` text for images. See section 7.2.

`\CSSFilename`: The name of the CSS file to use.

`\MathJaxFilename`: The name of the MathJax script to use.

Package options:

`ImagesName` and `ImagesDirectory`: These options control the filenames used by lwarp when it automatically generates images. See table 5 and section 7.5.

`xindyStyle`, `xindyLanguage`, `xindyCodepage`: When using *xindy*, these options may be set according to local use. See section 8.6.21.

`pdftotextEnc`: To adjust the encoding of *pdftotext*.

7.2 Accessibility

lwarp provides several methods for improving access to the document using tools such as text-only browsers, copy/paste, text-to-speech readers, or Braille readers. HTML provides the `alt` text attribute for images, which is used by lwarp as describe below. HTML also provides the `title` attribute, which usually generates a pop-up text. lwarp can add this to a reference or hyperlink. MathJax also has provisions for improved accessibility as well.

`\ImageAltText`: The default HTML `alt` text for `\includegraphics` and `lateximages`. Set with `\renewcommand`.

`\includegraphics` `alt` key: For `\includegraphics`, lwarp adds the `alt` key/value. For example:

```
\includegraphics[alt={Some text.}]{filename}
```

SVG math: For simple SVG math, lwarp places the LaTeX math expression in the `alt` text, so that the LaTeX expression may be copied and pasted to another document as plain text.

`\MathImageAltText`: For complicated SVG math, such as enclosed in `\InlineMathOther` / `\InlineMathNormal`, or `\DisplayMathOther` / `\DisplayMathNormal`, the HTML `alt` text will be set to `\MathImageAltText`. Set with `\renewcommand`.

MathJax: For MathJax, the accessibility tools provided by MathJax are enabled by default by lwarp's MathJax scripts.

`\PackageDiagramAltText`: Various packages create diagrams which lwarp converts into SVG images. These are given `alt` text set to `\PackageDiagramAltText`. Set with `\renewcommand`.

custom `alt` text

`\ThisAltText`: The HTML `alt` text of the next image may be set with:

```
\ThisAltText{Custom text about the image.}
<SVG math, Tikz, picture, etc.>
```

The next single image will be generated with the given text, and the following images will revert to back to their defaults.

references and links

`\ThisAltText` may also be used to assign an HTML `title` to the next reference or hyperlink.

```
\ThisAltText{Custom text about the link.}
Text ... \ref{label_name} ... text.
```

See section 7.6.

`\AltTextOpen` and `\AltTextClose`: By default, HTML `alt` text is enclosed by parentheses. This may be changed by redefining `\AltTextOpen` and `\AltTextClose`. Set with `\renewcommand`.

7.3 Shell escape

Opt `--shell-escape`

Some documents require the use of an external program, which is allowed when using the `--shell-escape` command-line option. When the document is first compiled manually, and also whenever the print version is recompiled, lwarp detects and remembers whether shell escape is enabled. If so, it will also be enabled when the document is recompiled with *lwarpmk*.

7.4 Font and UTF-8 support

⚠ type 3 bitmapped fonts

lwarp uses *pdftotext* to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which may prevent the use of older "type 3" bit-mapped fonts, and of older packages such as ae. The lwarp option `pdftotextEnc` may be useful in some situations. See section 7.5.

vector fonts
Computer Modern
⚠ *pdflatex*
⚠ DVI *latex*

While using DVI *latex* or PDF *pdflatex*, if no font-related package is specified then the default Computer Modern font is used, which may be a "type 3" bit-mapped font which may not convert well to plain text. A "type 1" vector font is required.

Pkg cm-super

To use the updated cm-super's type 1 fonts instead of Computer Modern, install the cm-super font package.

Pkg lmodern

To use Latin Modern instead, add

```
usepackage{lmodern}
```

to the preamble.

Pkg dejavu

Another useful option is the Deja Vu series of fonts, which have an increased coverage of language and glyphs:

```
\usepackage{dejavu}
```

latex, *pdflatex*, T1, UTF8

While using DVI *latex* or PDF *pdflatex*, lwarp automatically loads fontenc with T1 encoding. fontenc may be loaded with an additional encoding after lwarp. inputenc is automatically loaded with UTF8 encoding if if has not yet been loaded, but may also be specified with another encoding such as `latin1`. See the next section regarding index encoding.

⚠ *xelatex* and *lualatex*

XeLaTeX and LuaLaTeX users must use the fontspec package. Do NOT use fontenc!

Place fontspec or fontenc, xunicode, and other font and UTF-8 related commands after the `\documentclass` command and before `\usepackage{lwarp}`.

⚠ package conflicts

In some cases, a package conflict may require that a font package be loaded after lwarp, which should work as well:

1. `documentclass{article/book/report}` comes first, followed by any of:
2. Font and UTF-8 related commands:
   - For XeLaTeX or LuaLaTeX:
     - fontspec and font choices

       Pkg fontspec

       ligatures

       lwarp sets the following to turn off TeX ligatures during the generation of HTML tags, and turn off common ligatures in regular text, since older browsers may not display them correctly and newer browsers can automatically re-create them.

       ```
       \defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
       \defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
       \defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
       ```
   - For *pdflatex*:

     Pkg lmodern
     Pkg fontenc
     Pkg inputenc
     Pkg inputenx
     Pkg newunicodechar
     File glyphtounicode.tex

     (a) `\usepackage{lmodern}`, or other font-related packages
     (b) `\usepackage[T1]{fontenc}`
     (c) `\usepackage[utf8]{inputenc}`, or `latin1`, etc. Or use inputenx.
     (d) `\usepackage{newunicodechar}` along with related definitions.
     (e) To assist with the PDF-HTML conversion:
        i. `\input glyphtounicode.tex`
        ii. `\input glyphtounicode-cmr.tex% from the pdfx package`
        iii. `\pdfgentounicode=1`

(f) Another option to assist with the PDF-HTML conversion:
   - `\usepackage{cmap}`

Pkg cmap

(g) `\usepackage{textcomp}`

Pkg textcomp

3. `\usepackage{lwarp}` (section 7.5) goes after any of the above, followed by:
4. `\usepackage{newtxmath}` or other math-related font packages. Many of these load amsmath, which must be loaded after lwarp, so they must also be loaded after lwarp.

⚠ fontspec with traditional font packages

5. `\setmonofont{TeX Gyre Cursor}` or similar may be required if using XeLaTeX or LuaLaTeX and fontspec along with traditional font packages such as txfonts, newtxtext, etc. This is required to turn off the monospaced font's ligatures with fontspec after loading the traditional font packages. Monospaced output ligatures must be turned off to produce the correct HTML characters.
6. ... the rest of the preamble and the main document.

⚠ UTF-8 locale

In some cases, an external program may require a UTF-8 "locale". See section 9.8.

7.4.1 Indexes, glossaries, and encoding

lwarp uses the *xindy* program to processes indexes. *xelatex* and *lualatex* use *xindy* and *pdflatex* uses *texindy*.

The lwarp option `xindyLanguage` may be used to set the language option for xindy, and the `xindyCodepage` option may be used to set the codepage option for xindy. These are used for index generation.

7.5 lwarp package loading and options

lwarp supports book, report, and article classes, as well as the equivalent Koma-script classes and memoir, and various CJK-related classes and packages.

Load the lwarp package immediately after the font and UTF-8 setup commands.

Package options may be set while loading lwarp, or later with

```
\lwarpsetup{⟨key=value, . . . ⟩}
```

Pkg lwarp

lwarp package options are as follows:

Opt mathsvg
Opt mathjax

mathsvg, mathjax: For math display, select `mathsvg` (default) or `mathjax`. For more information about the math options, see section 8.7.

Opt latexmk
Default: false

latexmk: Tells *lwarpmk* to use *latexmk* to recompile the document several times if necessary. Otherwise, *lwarpmk* attempts to determing for itself whether to recompile. See section 7.6.

Opt dvips
Default: false

dvips: Tells *lwarpmk* to use *dvips* and *ps2pdf* to convert DVI output to PDF.

Opt dvipdfm
Default: false

dvipdfm: Tells *lwarpmk* to use *dvipdfm* to convert DVI output to PDF.

Opt dvipdfmx
Default: false

dvipdfmx: Tells *lwarpmk* to use *dvipdfmx* to convert DVI output to PDF.

Opt HomeHTMLFilename
Default: {}

HomeHTMLFilename: See section 7.6.

Opt HTMLFilename
Default: {}

HTMLFilename: See section 7.6.

Opt ImagesName
Default: image-

ImagesName: The prefix for the images automatically generated by lwarp for objects such as SVG math and `latexmages`.

Opt ImagesDirectory
Default: \jobname-images

ImagesDirectory: The directory for the images automatically generated by lwarp for objects such as SVG math and `latexmages`. By default, these images will appear in a directory named `<jobname>-images`, and the images will be named and numbered `image-<nn>`.

Opt PrintLatexCmd
Default: <automatic>

PrintLatexCmd: Sets the shell commands executed by **`lwarpmk print`**. If not specified, will automatically be set according to the detected LaTeX engine and the use of `--shell-escape`.

Opt HTMLLatexCmd
Default: <automatic>

HTMLLatexCmd: Sets the shell commands executed by **`lwarpmk html`**. If not specified, will automatically be set according to the detected LaTeX engine and the use of `--shell-escape`.

Opt makeindex
Default: makeindex

makeindex: Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use *makeindex*

Table 5: lwarp package options

Option	Description
mathsvg	Show math using SVG images.
mathjax	Show math using MATHJAX.
latexmk	Use *latexmk* for compiling documents.
dvips	Use *dvips* and *ps2pdf* to convert DVI documents.
dvipdfm	Use *dvipdfm* to convert DVI documents.
dvipdfmx	Use *dvipdfmx* to convert DVI documents.
HomeHTMLFilename	The filename of the home page.
HTMLFilename	A prefix for the filenames of the remaining web pages.
ImagesName	A prefix for the filenames of generated images.
ImagesDirectory	The directory used to hold generated images.
PrintLatexCmd	The shell commands for **lwarpmk print**.
HTMLLatexCmd	The shell commands for **lwarpmk html**.
For indexing (section 8.6.15) and glossaries (section 8.6.12):	
makeindex	Use *makeindex* to generate indices.
xindy	Use *xindy* to generate indices.
makeindexStyle	Set a custom style for *makeindex*.
xindyStyle	Set a custom style for *xindy*.
xindyLanguage	The *xindy* language option used for index generation.
xindyCodepage	The *xindy* codepage option used for index generation.
PrintIndexCmd	Shell commands executed by **lwarpmk printindex**.
HTMLIndexCmd	Shell commands executed by **lwarpmk htmlindex**.
LatexmkIndexCmd	Shell commands executed by *latexmk*.
GlossaryCmd	Shell command executed by **lwarpmk printglossary** and **lwarpmk htmlglossary**.
Seldom necessary:	
OSWindows	Force compatibility with MS-WINDOWS.
pdftotextEnc	Set the encoding for *pdftotext*.
lwarpmk	Generate a local copy of lwarpmk.lua.
Used internally by lwarp:	
warpprint	Generate print output, and also generate configuration files.
warpHTML	Generate HTML output.
BaseJobname	The \jobname to use. Set to the \jobname of the printed version even while generating HTML.

when generating indexes with **lwarpmk printindex**, **lwarpmk htmlindex**, or *latexmk*. If neither makeindex nor xindy is used, makeindex is assumed.

Opt xindy
Default: makeindex

xindy: Sets PrintIndexCmd, HTMLIndexCmd, and LatexmkImageCmd to use *xindy* when generating indexes with **lwarpmk printindex**, **lwarpmk htmlindex**, or *latexmk*.

Opt makeindexStyle
Default: lwarp.ist

makeindexStyle: If you wish to use a custom .ist file for index generation, see section 28.

Opt xindyStyle
Default: lwarp.xdy

xindyStyle: If you wish to use a custom .xdy file for index generation, see section 28.

Opt xindyLanguage
Default: english

xindyLanguage: If using an index or glossary, see section 28.

Opt xindyCodepage
Default: utf8

xindyCodepage: If using an index, see section 28.

Opt PrintIndexCmd
Default: <automatic>

PrintIndexCmd: Sets the shell commands executed by **lwarpmk printindex**. If not specified, will be set by the selection of makeindex or xindy. May be used to specify the creation of multiple indexes. See section 8.6.15.

Examples:

```
makeindex -s lwarp.ist projectname.idx                (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname.idx      (xindy)
```

automatic setting

The use of the makeindex or xindy options sets PrintIndexCmd to sensible values for each of those programs while compiling a single index. lwarp's makeindexStyle, xindyStyle, xindyLanuage, and xindyCodepage options will be used if specified.

⚠ xindy

If specifying PrintIndexCmd manually, be sure to assign an *xindy* language and codepage with the -L and -C *xindy* options, as the lwarp xindyLanguage and xindyCodepage options are not used for the PrintIndexCmd option when it is set manually.

This option is stored in the configuration files lwarpmk.conf and *.lwarpmkconf, and is then passed by the **lwarpmk printindex** command to the operating system to compile the print indexes. Since the command string is parsed by TEX, written to a file, read from the file by LuaTEX, and finally passed to the operating system, any attempt at quoting will be problematic. For complicated commands, it would be best to create a shell script, and simply refer to the script with the lwarp PrintIndexCmd option.

Opt HTMLIndexCmd
Default: <automatic>

HTMLIndexCmd: Sets the shell commands executed by **lwarpmk htmlindex**. If not specified, will be set by the selection of makeindex or xindy. May be used to specify the creation of multiple indexes. See section 8.6.15.

⚠ filenames

Example settings are similar to PrintIndexCmd, but append _html to the filenames:

```
makeindex -s lwarp.ist projectname_html.idx                (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname_html.idx  (xindy)
```

automatic setting

The use of the makeindex or xindy options sets HTMLIndexCmd to sensible values for each of those programs while compiling a single index. lwarp's makeindexStyle, xindyStyle, xindyLanuage, and xindyCodepage options will be used if specified.

⚠ xindy

If specifying HTMLIndexCmd manually, be sure to assign an *xindy* language and codepage with the -L and -C *xindy* options, as the lwarp xindyLanguage and xindyCodepage options are not used for the HTMLIndexCmd option when it is set manually.

As with PrintIndexCmd, to generate complicated indexes it may be worthwhile to use a shell script, then refer to that script with HTMLIndexCmd.

Opt LatexmkIndexCmd
Default: <automatic>

LatexmkIndexCmd: Sets the shell commands executed by *latexmk*. Unlike PrintIndexCmd and HTMLIndexCmd, LatexmkIndexCmd does not include any filenames, which will be provided instead by *latexmk*. See section 8.6.15.

Example settings are similar to PrintIndexCmd, but without a filename:

```
makeindex -s lwarp.ist                          (makeindex)
xindy -M lwarp.xdy -L english -C utf8              (xindy)
```

automatic setting

The use of the makeindex or xindy options sets LatexmkIndexCmd to either of the two settings show above. lwarp's makeindexStyle, xindyStyle, xindyLanuage, and xindyCodepage options will be used if specified. Unlike PrintIndexCmd and HTMLIndexCmd, *latexmk* uses either of the single-line settings of LatexmkIndexCmd shown above to compile each of multiple indexes if necessary.

⚠ xindy

If specifying LatexmkIndexCmd manually, be sure to assign an *xindy* language and codepage with the -L and -C *xindy* options, as the lwarp xindyLanguage and xindyCodepage options are not used for the LatexmkIndexCmd option when it is set manually.

Opt GlossaryCmd
Default: **makeglossaries**

GlossaryCmd: Sets the shell command executed by **lwarpmk printglossary** and **lwarpmk htmlglossary**. The print or HTML glossary filename is appended to this command. See section 8.6.12.

Opt OSWindows

OSWindows: lwarp attempts to automatically sense WINDOWS, but it may be forced with this option. See section 7.8.

Opt pdftotextEnc
Default: UTF-8

pdftotextEnc: Used to specify the encoding used by *pdftotext* during the PDF-HTML conversion. In most situations, the default is the correct choice.

Opt lwarpmk

lwarpmk: If you wish to have lwarp generate a local copy of lwarpmk.lua for archival or local-installation purposes, compile the print version with the lwarpmk option set. See section 28.

The following options are used internally by lwarp, and usually are not used in the user's document:

Opt warpprint
Opt warpHTML

warpprint and warpHTML: Usually controlled by *lwarpmk*, and not set in the document. Select the warpprint option to generate print output (default), or the warpHTML option to generate HTML5 output. The default is print output, so the print version may be compiled with the usual *pdflatex*, etc. When lwarp is loaded in print mode, it creates <project>_html.tex, which sets the warpHTML option before calling the user's source code <project>.tex. In this way, <project>.tex can \usepackage{lwarp} without any options to create a printed version, while <project>_html.tex will create an HTML version.

Opt BaseJobname
Default: \jobname

BaseJobname: Not intended for the user. Used internally by lwarp when creating the *_html.tex file used to compile the HTML version. See section 28.

7.6 Customizing the HTML output

Table 6 shows several settings may be used to customize the HTML output. Watch for the correct placement of each!

⚠ Placement!

⚠ Changes! Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:
   Enter ⇒ **`lwarpmk clearall`**
2. Recompile the print version in order to recreate the configuration files for *lwarpmk*:
   Enter ⇒ **`lwarpmk print`**
3. Finally, recompile the HTML version with the new settings:
   Enter ⇒ **`lwarpmk html`**

Options for the lwarp package:

Use the following as options for `\usepackage[<options>]{lwarp}`:

Opt HomeHTMLFilename
Default: \BaseJobname

HomeHTMLFilename: Filename of the homepage, without the "`.html`" suffix. Defaults to the `\BaseJobname`. A common setting is:

```
HomeHTMLFilename=index
```

causing the homepage to be the file `index.html`. Underscores are allowed in `HomeHTMLFilename` and `HTMLFilename` options, but may need to be escaped elsewhere, such as when appearing in a list:

filename underscores

```
\item [\href{file\_name.pdf}{text}] \
```

See section 7.6.1 for examples of naming and numbering HTML files.

Opt HTMLFilename
Default: <empty>

HTMLFilename: A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty. See section 7.6.1 for examples of naming and numbering HTML files.

Opt latexmk
Default: false

latexmk: Controls whether lwarp uses *latexmk* to compile the document. This setting is written to *lwarpmk*'s configuration files.

Opt mathsvg
Default: true

mathsvg: Selects SVG display for math output. (The default.)

Opt mathjax
Default: false

mathjax: Selects MathJax for math output.

Opt makeindex
Default: makeindex

makeindex: Selects *makeindex* for index generation by *lwarpmk*.

Opt xindy
Default: makeindex

xindy: Selects *xindy* for index generation by *lwarpmk*.

Placed in the preamble before `\begin{document}`:

`\linkhomename`
Default: Home

`\linkhomename`: Name of the link to the home page. Paragraphs are allowed. Redefine with `\renewcommand`.

Table 6: HTML settings

Macro/Cntr/Bool	Description
\linkhomename	Name of the link to the homepage.
SideTOCDepth	Sectioning depth of the sideTOC.
\sidetocname	Name of the sideTOC.
FileDepth	Sectioning depth of the file splits.
CombineHigherDepths	Combine higher section levels.
FileSectionNames	Use section names for file names, else use numbers.
\FilenameLimit	Maximum length of the generated filenames.
FootnoteDepth	Sectioning depth of footnotes.
\abstractname	The name of the abstract.
\ImageAltText	\includegraphics and other images' alt tag.
\ThisAltText {⟨text⟩}	Assigns an alt/title tag for the next image or link.
\MathImageAltText	The SVG math image lateximage alt tag.
\PackageDiagramAltText	The suffix for a package's lateximage alt tags.
\AltTextOpen	Start an HTML alt tag.
\AltTextClose	End an HTML alt tag.
\CSSFilename	The CSS for the following files.
\MathJaxFilename	The MathJax script for the following files.
\HTMLLanguage	The HTML lang tag.
\HTMLTitle	The homepage's <title>, overriding \title.
\HTMLTitleBeforeSection	Set subpage <title>s to \HTMLTitle - sectionname
\HTMLTitleAfterSection	Set subpage <title>s to sectioname - \HTMLTitle
\HTMLAuthor	The HTML author meta tag, overriding \author.
\HTMLDescription	The HTML description meta tag.
\HTMLFirstPageTop	Heading for the home page.
\HTMLPageTop	Heading for the other pages.
\HTMLPageBottom	Footing for all pages.
HTMLDebugComments	Boolean to generate HTML comments.

Ctr tocdepth

tocdepth: Sectioning depth of the table of contents. See section 16 for a list of LaTeX stack depths.

Ctr SideTOCDepth
Default: 1

SideTOCDepth: Sectioning depth of the sideTOC. Defaults to 1, causing the sideTOC to show sections but not subsections.

sideTOC

Each subpage of the website has its own small table of contents on the side (the "sideTOC"). Its depth is set by SideTOCDepth. This sideTOC is only shown if the browser display is wide enough. When using a narrow web browser window, "responsive web design" is used to show the sideTOC at the top of the page, as well as a link back to **Home** at the top and bottom.

It is recommended to set:

```
SideTOCDepth = FileDepth
```

or

```
SideTOCDepth = FileDepth+1
```

⚠ inaccessible pages

If SideTOCDepth < FileDepth, web pages will be inaccessible via the sideTOC.

\sidetocname
Default: Contents

\sidetocname: Name of the sideTOC. Paragraphs are allowed. Redefine with \renewcommand.

Ctr FileDepth
Default: -5

FileDepth: Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.

- To place the entire file into one HTML page, use:
  `\setcounter{FileDepth}{-5}`
- To split the HTML file at \section depth, use:
  `\setcounter{FileDepth}{1}`
- ⚠ To ensure that the HTML pages/files are accessible:
  Place a \tableofcontents somewhere before the first section break (therefore in the "home page"), and set
  `tocdepth >= FileDepth`

Bool CombineHigherDepths
Default: true

CombineHigherDepths: Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

⚠ Inaccesible pages!

⚠ Lost in an old page!

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (`lwarpmk cleanall`), change FileDepth

and/or CombineHigherDepths, then finally recompile and renavigate to the desired page using the new file structure.

Bool FileSectionNames
Default: true

FileSectionNames: If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the HTMLFilename option is used as a prefix. See section 7.6.1 for examples of naming and numbering HTML files. The user must ensure that filenames are unique after begin sanitized. For example, math in the section name is removed before creating the filename, so the rest of the filename must be sufficiently unique to avoid name collisions.

⚠ Unique filename!

\FilenameLimit
Default: 80

\FilenameLimit: The maximum length of the filenames generated by lwarp. ".html" is added to this length. Redefine with \renewcommand.

Ctr FootnoteDepth
Default: 3

FootnoteDepth: Determines where to place pending footnotes. 3 places footnotes before each break down to the \subsubsection level. 1 places footnotes before each \section break. Any pending footnotes are also placed at the bottom of each page before each file break.

Bool HTMLDebugComments
Default: false

HTMLDebugComments: Set true to generate HTML comments, such as which section or is being opened or closed.

\abstractname
Default: Abstract

\abstractname: The name of the abstract. This may also be over-written by the babel package. Defaults to "Abstract". Redefine with \renewcommand.

Placed before \begin{document}, or before any sectioning command which causes a file break:

\CSSFilename
Default: lwarp.css

\CSSFilename: {⟨*filename.css*⟩} Sets the css file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The css styles of the web pages are set by the \CSSFilename command. If \CSSFilename is not used, a default plain style is used to mimic printed LaTeX output. lwarp_sagebrush.css is a semi-fancy colored style as shown in this tutorial. Change it to lwarp_formal.css for a more formal look, or comment out the \CSSFilename command to see the default. \CSSFilename may be used before each file break to set the css for individual pagess of the website.

\MathJaxFilename
Default: lwarp_mathjax.txt

\MathJaxFilename: {⟨*filename*⟩} Sets the MathJax script file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The MathJax script file is copied into the head of each HTML file. This may be used to point to a local repository, add extensions, or change the script somewhere in the middle of the document. \MathJaxFilename may be used before each file break to set the script file for individual pages of the website.

\HTMLLanguage
Default: en-US

\HTMLLanguage: {⟨*langauge*⟩} The HTML file's HTML lang meta tag. Defaults to en-US.

\HTMLTitle
Default: \thetitle

\HTMLTitle: {⟨*title*⟩} Overrides \title for the HTML header's meta title. De-

faults to \thetitle, which is set by \title, or empty otherwise. Unlike the author, \thetitle is set by \title even if not using the titling package.

\HTMLTitleBeforeSection
Default: \HTMLTitleBeforeSection

\HTMLTitleBeforeSection: Sets subpage <title> tags to show the website title followed by the section name.

\HTMLTitleAfterSection

\HTMLTitleAfterSection: Sets subpage <title> tags to show the section name followed by the website title.

custom <title>

To customize subpage <title>s, redefine \theHTMLTitleSection, which defaults to:

```
\def\theHTMLTitleSection{%
  \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
}
```

\HTMLAuthor
Default: \theauthor

\HTMLAuthor: {⟨*author*⟩} The HTML header's meta author. Defaults to \theauthor, which is set by \author if using the titling package, but is empty otherwise. There are several ways to represent the author and affiliations, especially if using the authblk package, most of which do not result in a sensible \theauthor, so \HTMLAuthor is useful to create a list of authors without their affiliations.

\HTMLDescription
Default: <empty>

\HTMLDescription: {⟨*description*⟩} Sets the HTML description tag for the following files. May be changed before each each sectioning command which would cause a file split.

\HTMLFirstPageTop
Default: <empty>

\HTMLFirstPageTop: {⟨*contents*⟩} A user-definable custom action applied to the top of the home page. Useful for logos, etc. Defaults empty. Ignored in print output.

\HTMLPageTop
Default: <empty>

\HTMLPageTop: {⟨*contents*⟩} A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.

\HTMLPageBottom
Default: <empty>

\HTMLPageBottom: {⟨*contents*⟩} A user-definable custom action applied to the bottom of each web page. Useful for authors, copyright notices, contact information, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.

Placed in the home page before the first sectioning command which causes a file break:

\tableofcontents
⚠ TOC on the homepage!

\tableofcontents: Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage.

Links to each chapter/section are provided, as selected by tocdepth.

Placed in the document wherever necessary:

\ImageAltText
Default: image

\ImageAltText: Redefine with \renewcommand. \includegraphics and other images are assigned an HTML alt tag according to \ImageAltText along

with \AltTextOpen and \AltTextClose. This text is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "image", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following \includegraphics and other images.

\ThisAltText

\ThisAltText: {⟨*text*⟩} \ThisAltText can be used to assign an HTML alt text attribute to the next image generated by a lateximage, picture, tikzpicture, or any other similar environment which generates an image, or the next SVG math expression. This tag is cleared after use. The tag is also cleared after each MATHJAX expression, in case the user changes between SVG math and MATHJAX.

\ThisAltText also may be used to add an HTML title to a reference or hyperlink, such as a \ref, \cref, \href, \url, \hyperref, or \hyperlink. In each case, the alternative text is cleared after use.

\MathImageAltText
Default: math image

\MathImageAltText: Redefine with \renewcommand. When creating an SVG math image, its HTML alt tag may be set to the math expression, which may be hashed for image reuse. In the case of \ensuremath or after \inlinemathother, where the contents require a unique image for each instance of the same expression, the alt tag is set to \MathImageAltText, along with \AltTextOpen and \AltTextClose, and the image is not reused.

This alt expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "math image", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

\PackageDiagramAltText
Default: diagram

\PackageDiagramAltText: Redefine with \renewcommand. For many packages, the output is placed inside a lateximage with an HTML alt tag set to the package name followed by \PackageDiagramAltText. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

\AltTextOpen
Default: (

\AltTextOpen: Redefine with \renewcommand.

\AltTextClose
Default:)

\AltTextClose: Redefine with \renewcommand. HTML alt text is enclosed by the macros \AltTextOpen and \AltTextClose, which default to an opening and closing parenthesis.

Env warpprint

warpprint: An environment which is only used while generating print output. Place inside anything which does not apply to HTML and which may cause problems with lwarp. If lwarp knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won't have to be placed inside a warpprint environment, but unknown packages may cause problems which may be isolated from lwarp using this environment.

⚠ *Do not place anything else on the same line as* `\end{warpprint}`.

Env warpHTML **warpHTML:** An environment which is only used while generating HTML output. This is useful for website logos and other items which have no purpose in printed output.

⚠ *Do not place anything else on the same line as* `\end{warpHTML}`.

`\warpprintonly` **`\warpprintonly`:** {⟨*contents*⟩} A macro version of the `warpprint` environment.

`\warpHTMLonly` **`\warpHTMLonly`:** {⟨*contents*⟩} A macro version of the `warpHTML` environment.

7.6.1 Example HTML file naming

Examples of ways to name or number HTML files:

Numbered HTML nodes:

Example: Homepage `index.html`, and `node-1`, `node-2`. [13]

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={node-}
]{lwarp}
\boolfalse{FileSectionNames}
```

Named HTML sections, no prefix:

Example: `index.html`, and `About.html`, `Products.html`

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={}
]{lwarp}
\booltrue{FileSectionNames}
```

Named HTML sections, with prefix:

Example: Homepage `mywebsite.html`, and additional pages such as `mywebsite-About.html`, `mywebsite-Products`, etc.

```
\usepackage[
    HomeHTMLFilename=mywebsite,
    HTMLFilename={mywebsite-}
]{lwarp}
\booltrue{FileSectionNames}
```

7.7 Customizing the css

\CSSFilename {⟨*filename*⟩}
Default: lwarp.css

\CSSFilename may be used to choose which .css file is used to display each page of the web site. Use \CSSFilename before \begin{document} to assign the style of the home page. If different parts of the website should have different styles, call \CSSFilename again before each section heading which creates a new file. This may be changed numerous times throughout the file, resulting in different HTML pages having different css files assigned:

```
...
\CSSFilename{myCSS.css}
\chapter{Another Chapter}
...
```

The styles provided by lwarp include:

lwarp.css: A default style if \CSSFilename is not used. This style is comparable to a plain LaTeX document. To set this style, you may use \CSSFilename{lwarp.css}, or no \CSSFilename call at all.

lwarp_formal.css: A formal style with a serif fonts and a traditional look.

lwarp_sagebrush.css: A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the \CSSFilename entry in the tutorial, lwarpmk html again, and then reload the tutorial webpage.

Custom css

A customized style may also be created. For each new project a file called sample_project.css is generated. This may be renamed to <project>.css then used by assigning \CSSFilename{<project>.css}.

⚠ Rename it!

Note that sample_project.css is overwritten whenever lwarp is loaded in print mode. It is therefore important to rename the file to something like <project>.css before using it, so that your own changes are not overwritten.

<project>.css has an entry which loads lwarp.css, and this entry may be changed to load lwarp_formal.css or lwarp_sagebrush.css if desired. Additional changes to the css may be made by making entries later in the <project>.css file.

File lwarp.css
File project.css
File sample_project.css

It is best to make a local project-specific css file such as project.css, containing only things which are different from lwarp.css. The file project.css should refer to lwarp.css as follows:

```
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */
```

[13] See \SetHTMLFileNumber to number in groups by chapter, for example.

```
/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
```

Finally use `\CSSFilename{<project>.css}` in the document to activate the custom CSS.

7.8 Selecting the operating system

Prog Unix
Prog Mac OS
Prog Linux

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.

Prog MS-Windows
Prog Windows
Opt OSWindows

If MS-WINDOWS is not correctly detected, use the lwarp option `OSWindows`.

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean `usingOSWindows` is set `true`. This boolean may be tested by the user for later use.

7.9 Selecting actions for print or HTML output

The following environments and macros are used to select actions which only apply to either traditional LaTeX print-formatted PDF generation, or to HTML generation.

For most of built-in LaTeX and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which lwarp does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

Env warpHTML

Anything which is to be done only for HTML5 output is surrounded by a `warpHTML` environment:

```
\begin{warpHTML}
 ... something to be done only during \HTML\ generation
\end{warpHTML}
```

⚠ `\end{warpHTML}`

Do *not* place anything else on the same line as `\end{warpHTML}`. The exact phrase is used to mark the end of the environment.

Env warpprint Anything which is to be done only for print output is surrounded by a warpprint environment:

```
\begin{warpprint}
 ... something to be done only during traditional \PDF\ generation
\end{warpprint}
```

⚠ \end{warpprint} As above, do not place anything else on the line with \end{warpprint}.

Env warpall Anything which is to be done for any output may be surrounded by a warpall environment. Doing so is optional.

```
\begin{warpall}
 ... something to be done during print \PDF\ or \HTML\ output
\end{warpall}
```

As above, do not place anything else on the line with \end{warpall}.

Macros are also provided for print-only or HTML-only code:

\warpprintonly {⟨*actions*⟩}

Performs the given actions only when print output is being generated.

\warpHTMLonly {⟨*actions*⟩}

Performs the given actions only when HTML output is being generated.

7.10 Commands to be placed into the warpprint environment

Certain print-related commands should always be placed inside a warpprint environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: \parindent \parskip
- Manual page positions such as the textpos package, which is emulated but only in a limited way.
- Anything changing the page counter. lwarp requires that the page counter not be adjusted during HTML output.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 13: Troubleshooting.

7.11 Title page

In the preamble, place an additional block of code to set the following:

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
    Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

The title is used in the meta tags in the HTML files, unless overridden by `\HTMLTitle`, and the rest are used in `\maketitle`. To use a `\subtitle` or `\published` field, see section 66.8.

`\maketitle` Use `\maketitle` just after the `\begin{document}`, as this will establish the title of the homepage. Optionally, use a `titlepage` environment instead.

Env `titlepage` The `titlepage` environment may be used to hold a custom title page. The titlepage will be set in a `<div>` class `titlepage`, and `\printtitle`, etc. may be used inside this environment.

Env `titlingpage` Another form of custom title page, where `\maketitle` is allowed, and additional information may be included as well.

`\title` {⟨*title*⟩}

⚠ HTML corrupted ⚠ newlines Avoid newlines in the `\title`; these will interfere with the file break and CSS detection. Use a `\subtitle` command instead (section 66.8). The title will appear in the document `\maketitle` as a heading `<h1>`. The HTML meta `title` tag will also have this title, unless `\HTMLTitle` is used to set the meta title to something else instead.

`\author` {⟨*author*⟩}

In `\author`, `\protect` may be needed before some formatting commands. In HTML, the author will appear in a `<div>` of class `author` in the `\maketitle`. If the titling package is used, the author will also appear in a HTML meta tag, but `\HTMLAuthor` may be necessary to create a plain list of names if `\author` had affiliations added. `\affiliation` is a new addition to lwarp.

`\date` {⟨*date*⟩}

`\date` works as expected. In HTML, this will appear in a `<div>` class `titledate`.

`\thanks` {⟨*text*⟩}

`\thanks` are allowed in the titlepage fields, and will be rendered as HTML notes at the bottom of the title page.

7.12 HTML page meta descriptions

`\HTMLDescription` {⟨*A description of the web page.*⟩}
Default: (none)

limitations

Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character (").

placement

Use `\HTMLDescription` just before `\begin{document}` to set the description of the home page, and also just before each sectioning command such as `\chapter` or `\section` where a new file will be generated, depending on `FileDepth`. For example, if `FileDepth` is 1, use `\HTMLDescription` just before each `\section` command, and that description will be placed inside the HTML page for that `\section`. The same descrition will be used for all following HTML files as well, until reset by a new `\HTMLDescription`. It is best to use a unique description for each HTML file.

disabling

To disable the generation of HTML description meta tags, use:

```
\HTMLDescription{}
```

7.13 HTML homepage meta title

`\HTMLTitle` {⟨*title*⟩}
Default: `\HTMLtitle{\thetitle}`

Sets the contents of the web page `<meta name="title">` element. May be set empty to cancel the meta title tag.

See section 7.6 for `\HTMLTitleBeforeSection` and `\HTMLTitleAfterSection`, used to set the title for HTML subpages.

7.14 HTML page meta author

`\HTMLAuthor` {⟨*author*⟩}
Default: `\HTMLAuthor{\theauthor}`

Sets the contents of the web page `<meta name="author">` element. May be set empty to cancel the meta author tag.

`\author` may be used to create a list of authors and their affiliations, in several formats if using authblk, and these may not successfully parse properly into a sensible list for `\theauthor`. `\HTMLAuthor` may be used to set the meta tag to a simple list of names.

8 Special cases and limitations

Some commonly-used LaTeX expressions should be modified as follows to allow for a smooth conversion to both HTML and print-formatted outputs.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

8.1 Things to avoid

In the document, avoid the following:

page counter: Do not adjust the page counter. If doing so is required for the print version, place the adjustment inside a `warpprint` environment.

Custom math environment macros: Do not use expressions such as `\beq` as a replacement for `\begin{equation}`.

Custom macros in section, figure, table names: Custom macros which appear in sectioning commands or float captions then appear in the `.toc`, `.lof`, and `.lot` lists, and should be made robust using `\newrobustcmd` or `\robustify` from etoolbox, xparse, etc.

When setting `FileSectionNames` to `true` to name the HTML files from the section names, the file names are created from sanitized versions of the chapter or section names, but the section names must be plain text or something which expands into plain text. Robust macros will not work at the sectioning level which is used for file names, but a robust macro or other complicated name may be used for the manditory argument of `\chapter`, `\section`, etc., if a plain-text version is also included in the optional argument:

```
\chapter[Plain Name]{\ARobustMacro{Fancy Name}}
```

8.1.1 Invalid HTML

Additionally, some objects are valid LaTeX, but invalid HTML. An example is a tabular inside `\textbf`, since HTML does not allow a table inside a span. lwarp will create the table, and the browser may support it, but the result is technically invalid.

8.2 Formatting

8.2.1 Text formatting

⚠ `\bfseries`, etc. `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ HTML special chars &, <, and > have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the listings package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.

verbatim The various `verbatim`-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

8.2.2 Horizontal space

\hspace

\hspace is converted to an inline HTML span of the given width, except that `0` width is ignored, a width of `.16667em` is converted to an HTML thin breakable space (`U+2009`), and a `\fill` is converted to a `\qquad`.

\,

~ and `\,` are converted to HTML entities.

\kern
\hskip

`\kern` and `\hskip` are entered into the HTML PDF output as-is, then interpreted by *pdftotext*, and thus usually appear as a single space.

8.2.3 Text alignment

Use the environments `center`, `flushright`, `flushleft` instead of the macros `\centering`, `\raggedright`, `\raggedleft`.

⚠ figure & table alignment

`\centering`, etc. are honored in a `figure` or `table` if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

8.2.4 Accents

Native LaTeX accents such as `\"` will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX.

8.2.5 textcomp package

Pkg textcomp

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols

Many textcomp symbols are not supported by many system / browser fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

8.2.6 Superscripts and other non-math uses of math mode

Use `\textsuperscript{x}` instead of `$^{x}$`

8.2.7 Empty `\item` followed by a new line of text or a nested list:

lists

Use a trailing backslash: `\item[label] \`

8.2.8 Filenames and URLs in lists or footnotes

filename underscore

Escape underscores in the filenames:

```
\item[\href{file\_name.pdf}{text}]
```

8.2.9 relsize package

Pkg relsize

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small

The HTML browser's setting for minumum font size may limit how small the output will be displayed.

8.3 Boxes and minipages

8.3.1 Marginpars

`\marginpar` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}` `\marginpar` may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `<br />` tags.

`\marginparBlock` `[`⟨*left*⟩`]` `{`⟨*right*⟩`}` To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a `<span>`. A line break will occur in the text where the `\marginBlock` occurs.

8.3.2 Save Boxes

⚠ HTML corrupted

⚠ boxes

TEX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. lwarp uses methods which help avoid this problem.

⚠ `minipage`, `\parbox`

`\savebox` and related do not (yet) support `minipage` or `\parbox`.

8.3.3 Minipages

⚠ inline

A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

placement

`minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side

Side-by-side `minipages` may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span

There is limited support for `minipages` inside an HTML `<span>`. An HTML `<div>` cannot appear inside a `<span>`. While in a `<span>`, `minipages`, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an "inline" format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

⚠ minipage size

When using `\linewidth`, `\textwidth`, and `\textheight`, widths and heights in HTML are scaled proportionally to a 6×9 inch text area, and inside a `multicols` `\linewidth` is divided by the specified number of columns.

if width is `\linewidth`

If a `minipage` or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML

A new macro `\minipagefullwidth` requests that, during HTML output, the next single `minipage` or `\parbox` be generated without an HTML `width` attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ `tabular`, `multicols`

`\UseMinipageWidths`
`\IgnoreMinipageWidths`

Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every `minipage` or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell lwarp to honor the specified widths of all following `minipages` and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell lwarp to ignore the specified widths.

⚠ text alignment

Nested `minipages` adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a `flushleft` or similar environment in the child `minipage` to force a text alignment.

8.3.4 Side-by-side minipages

Place side-by-side minipages inside a `center` environment, with horizontal space between them, such as `\quad`, `\qquad`, `\hspace`, or `\hfill`. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

8.3.5 Framed minipages and other environments

`\fbox` can only be used around inline `<span>` items during HTML output, but HTML cannot place a block element such as a `<div>` for a minipage or a list inside of a `<span>`. Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

`\fbox`
`\fboxBlock`
Env `fminipage`

For a framed object, options include:

To remove the frame in HTML output: Place the `\fbox` command and its closing brace inside `warpprint` environments. This will nullify the frame for HTML output.

For inline text:

To frame the contents inline with some formatting losses in HTML: This is the default action of `\fbox` when enclosing a minipage. During HTML output, `\fbox` nullifies the HTML tags for `minipage`, `\parbox`, and lists. The contents are included as inline text inside the `\fbox`'s `<span>` of class `framebox`. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.

For inline `minipage` and lists:

To frame the contents on their own line with improved formatting in HTML: A new command `\fboxBlock` is included, intended to be a direct replacement for `\fbox` for cases where the `\fbox` surrounds a minipage, table, or list. For print output, this behaves as `\fbox`. For HTML output, the contents are placed inside an HTML `<div>` with the class `framed`, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and minipages look nicer, and valid HTML is created for a `tabular`. While an `\fbox` containing a `tabular` is valid LaTeX code, the result in HTML is problematic since a table is a `<div>` not a `<span>`, so use `\fboxBlock` around a `tabular`, or else place the `tabular` inside a `minipage`, or use `fminipage`, described next. Also see below regarding the "Misplaced alignment tab character &." error.

For display `tabular`, minipages, and lists:

To create a framed minipage in both print and HTML: A new environment `fminipage` is included. For print output, this is identical to `minipage`, except that it is also framed. For HTML output, this forms a `<div>` of class `framed`, the contents preserve their HTML formatting, and valid HTML is created for a `tabular`. Also see section 85 for a new environment `fcolorminipage`. Also see below regarding the "Misplaced alignment tab character &." error.

colored boxes and frames:

To create colored frames and boxes: See section 514 for xcolor's `\colorbox` and `\fcolorbox`, and lwarp's additional `\colorboxBlock` and `\fcolorboxBlock`.

⚠ Misplaced alignment tab character &

To frame tables or verbatim environments: Place the contents inside a `fminipage`, or perhaps a `\fboxBlock` for a `tabular`. Also, if using `\fboxblock` with `tabular`, you will have to use `\StartDefiningTabulars` before the start of the macro which uses `\fboxBlock` and the `tabular`, and `\StopDefiningTabulars` afterwards. Also see the lwarp documentation for the fancybox package.

To frame equations: See section 217 for the fancybox package.

For fancy framed minipages: See packages boxedminipage2e, shadow, fancybox, framed, mdframed.

Custom environments: Use a custom environment to create a sidebar, containing a `BlockClass` environment with custom css formatting, and `\warpprintonly{\hrule}` command:

```
\begin{BlockClass}{frameminipage}% ignored in print output
  % use \CSS\ to format div class ``framedminipage''
\warpprintonly{\hrule} % only appears in print output
```

```
Contents
\warpprintonly{\hrule} % only appears in print output
\end{BlockClass}
```

8.3.6 fancybox package

Pkg fancybox

framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives

\fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example

The fancybox documentation's example framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method loses HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim

lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \beginVerbatim
}{
  \endVerbatim
  \endfminipage
}
```

framed \VerbBox fancybox's \VerbBox may be used inside \fbox.

indented alignment LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

8.3.7 mdframed package

Pkg mdframed support Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading When used, lwarp loads mdframed in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where \textbf must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support \bfseries and friends, only one font selection may be made at a time.

theoremtitlefont theoremtitlefont is not supported, since the following text is not in braces in the mdframed source.

ignored options userdefinedwidth and align are currently ignored.

css classes Environments created or encapsulated by mdframed are enclosed in a of class mdframed, and also class md<environmentname> for new environments.

Frame titles are placed in a of class |mdframedtitle|. Subtitles are in a of class |mdframedsubtitle|, and likewise for subsubtitles.

8.4 Section names

If using named HTML files, by selecting \booltrue{FileSectionNames}, the generated filenames may be simplified by using \FilenameSimplify and \FilenameNullify:

\FilenameSimplify {⟨*text*⟩}

To remove common short words from the automatically-generated filenames, replacing each with a single hyphen "-", use \FilenameSimplify:

```
\FilenameSimplify*{-in-}
\FilenameSimplify*{A-}
```

The first example removes the word ”in” in the middle of a filename, and the second example removes “A” at the start of the filename. The star forces the arguments to be detokenized, which is required for a plain-text comparison. (The unstarred form is used for a token-sensitive comparison, which is seldom required by the user.) After simplfication, repeated hyphen characters will be further simplified to a single hyphen “-”. Finally, single hyphens at the start or end of the filename are removed.

`\FilenameNullify` `{`⟨*macros*⟩`}`

⚠ macros in section names

Macro names may appear in the automatically-generated file names. To remove these, create *non-robust* nullified versions of the macros, ensuring that each line ends with a percent character `%` as shown below. These are placed inside `\FilenameNullify`, which adds them to the list of macros which are nullfiied during filename generation. Low-level macros such as `\begingroup` will cause problems when nullfied. Many macros such as `\textbf` are already nullfied. lwarp also already nullifies built-in symbol and textcomp macros, including if defined by xunicode, but not all xunicode macros. See the definition of `\LWR@nullfonts` for a complete list.

```
\FilenameNullify{%
  \renewcommand*{\macroname}[1]{#1}%
  \renewcommand*{\anothermacro}{}%
}
```

⚠ duplicate filename

Avoid duplicate file names. Section names at levels which result in HTML file splits must be unique. lwarp will generate an error if a duplicate HTML filename is generated. Use the optional TOC caption entry parameter for formatting. Remember to `\protect` LaTeX commands which appear in section names and TOC captions.

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

8.5 Cross-references

labels
⚠ label characters

Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).

`\nameref`
⚠ empty link

`\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

8.5.1 Page references

⚠ LaTeX page numbers

The printed page does not translate to the HTML page, so `\pageref` references are converted to parentheses containing `\pagerefPageFor`, which defaults to “see ”, followed by a hyperlink to the appropriate object.

Ex:

```
\ref{sec:name} on page \pageref{sec:name}
```
in HTML becomes:
"Sec. 1.23 on page (**see** sec. 1.23)".

\pagerefPageFor may be redefined to "page for ", empty, etc. See page 468.

8.5.2 cleveref and varioref packages

Pkg cleveref
Pkg varioref

cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for \cpageref and \cpagerefrange. This phrase includes \cpagerefFor, which defaults to "for".

⚠ cleveref page numbers

Ex:

```
\cpageref{tab:first,tab:second}
```
in html becomes:
"pages **for** table 4.1 and **for** table 4.2"

See \cpagerefFor at page 542 to redefine the message which is printed for page number references.

8.5.3 Hyperlinks, hyperref, and url

Pkg hyperref
Pkg url

lwarp emulates hyperref, including the creation of active hyperlinks, but does not require that hyperref be loaded by the document.

⚠ comments between arguments

Do not place a comment with a % character between arguments for \hyperref, etc., as it is neutralized for inclusion in HTML URLs.

lwarp can also load url, but url should not be used at the same time as hyperref, since they both define the \url command. lwarp does not (yet) attempt to convert url links into hyperlinks during HTML output, nor does the print version of url create hyperlinks.

⚠ backref

When generating HTML, lwarp's emulation of hyperref does not automatically load backref, so backref must be loaded explicitly.

8.5.4 Footnotes and page notes

lwarp uses native LaTeX footnote code, although with its own \box to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering

To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for \alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

footmisc

The footmisc stable option is emulated by lwarp.

⚠ sectioning commands

When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the stable option, provide a short TOC entry, and \protect the \footnote:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc

⚠ memoir

If using memoir class, with which lwarp preloads footmisc, the stable option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust \secnumdepth instead.

fancybox, fancyvrb

⚠ \VerbatimFootnotes

⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

pfnote

⚠ pfnote numbers

While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

bigfoot, manyfoot

⚠ verbatim

Verbatim footnotes are not yet supported.

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XeLaTeX or LuaLaTeX instead of pdfLaTeX.

8.5.5 xr, xr-hyper, and xcite packages

See section 5.17.

8.6 Front and back matter

8.6.1 Custom classes with multiple authors and affiliations

Some classes allow multiple authors and affiliations. Often it is possible to emulate these using a standard class along with authblk:

```
%\documentclass{customclass} % for print document
\documentclass{article} % for html document

\usepackage{lwarp}
\begin{warpHTML}
\usepackage{authblk}
\let\affiliation\affil % maybe required
\end{warpHTML}
```

8.6.2 Starred chapters and sections

The following describes \ForceHTMLPage and \ForceHTMLTOC, which may be used for endnotes, glossaries, tocbibind, bibliographies, and the index. See the following sections where applicable. Continue here if interested in the reason for adding these commands to lwarp.

Some packages use \chapter* or \section* to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own HTML pages, and they are not given TOC entries.

lwarp provides a method to cause a starred section to be on its own HTML page, subject to FileDepth, and also a method to cause the starred section to have its own TOC entry during HTML output.

\ForceHTMLPage To place a starred section on its own HTML page, use \ForceHTMLPage just before the \chapter* or \section*. lwarp will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using \phantomsection and \addcontentsline works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created, or when creating an EPUB where the TOC entry will point to the page before the starred section. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is created.

⚠ inaccessible HTML page

\ForceHTMLTOC To automatically force the HTML version of the document to have a TOC entry for a

starred section, use \ForceHTMLTOC just before the \chapter* or \section*, and place \phantomsection and \addcontentsline inside a warpprint environment.

For print output, \ForceHTMLTOC and \ForceHTMLPage have no effect.

8.6.3 abstract package

Pkg abstract
⚠ missing TOC

If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

8.6.4 titling and authblk

Pkg titling
Pkg authblk
package support
⚠ load order
\published and \subtitle

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

8.6.5 tocloft package

Opt [tocloft] titles
Pkg tocloft
Pkg tocloft
⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its titles option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

8.6.6 appendix package

Pkg appendix
⚠ incorrect TOC link

During HTML conversion, the option toc without the option page results in a TOC link to whichever section was before the appendices environment. It is recommended to use both toc and also page at the same time.

8.6.7 pagenote package

Pkg pagenote

pagenote works as-is, but the page option is disabled.

8.6.8 endnotes package

Pkg endnotes
table of contents

To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

HTML page

To additionally have the endnotes on their own HTML page, if FileDepth allows:

```
\ForceHTMLPage
\theendnotes
```

8.6.9 *BibTeX*

\etalchar Displays a superscript "+" to indicate "and others".

⚠ Modify *.bib When enough authors are cited for a source, BibTeX may use the \etalchar command to display a math superscript with a + character to indicate "and others". Without modification, this will result in an "Improper \prevdepth" error. At present, lwarp requires that \etalchar be replaced by a text superscript. To do so, add to the start of the .bib file the following:

```
@PREAMBLE{"\let\etalchar\relax \newcommand{\etalchar}[1]{\textsuperscript{#1}}"}
```

8.6.10 xcite package

See section 5.17.

8.6.11 gloss package

Pkg gloss To process the HTML glossary:

⚠ compiling

```
bibtex <projectname>_html.gls
```

8.6.12 glossaries package

Pkg glossaries *lwarpmk* has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

processing glossaries

Opt GlossaryCmd

Default: makeglossaries

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

The shell command to execute is set by the lwarp option GlossaryCmd, which defaults to **makeglossaries**. The print or HTML glossary filename is appended to this command.

⚠ *makeglossaries* not found In some situations it may be required to modify the default command, such as to add the **perl** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and TOC options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style

The default `style=item` option for glossaries conflicts with lwarp, so the style is forced to `index` instead.

⚠ number list

The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions

The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

8.6.13 nomencl package

Pkg nomencl

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

8.6.14 Indexing overview

There are many ways to process indexes for a LaTeX document, including native LaTeX capabilities, a number of packages and classes, the possible availability of shell escape and *latexmk*, and the need to process print and HTML versions. lwarp attempts to provide easy recompilation of indexes along with the rest of the document, but the various indexing options must be set correctly. Numerous examples are given below. Some differ in minor details, so the important parts are highlighted in red, and options are in green.

Once set up properly, the entire document may be recompiled with **`lwarpmk print`** and **`lwarpmk html`**. In some cases, it will also be necessary to compile the indexes with **`lwarpmk printindex`** and **`lwarpmk htmlindex`**. A recompile may then be forced with **`lwarpmk print1`** and **`lwarpmk html1`**.

manual processing

The user may continue to process indexes manually or by shell script without the use of *lwarpmk*, but adjustments will be required to process HTML indexes as well. In general, `*.idx` and `*.ind` files will be accompanied by `*_html.idx` and `*_html.ind` files.

custom index style

If using a custom indexing style file, see sections 8.6.20 and 8.6.21.

source code

See section 76 for lwarp's core index and glossary code, section 283 for index, section 441 for splitidx, section 282 for imakeidx, section 477 for tocbibind, and section 534.17 for memoir's indexing patches.

8.6.15 Indexing with basic LaTeX and makeidx

lwarpmk processing

The following allow the user to process indexes automatically, or using *lwarpmk*'s commands:

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

For a single index using *makeindex*:

```
\usepackage[makeindex,latexmk] {lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.ist` style file. When creating the HTML index, "`_html`" is automatically appended to each of the names.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For a single index using *xindy*:

```
\usepackage[
    xindy,
    xindyLanguage=english,                  <optional>
    xindyCodepage=utf8,                     <optional>
    latexmk                                 <optional>
]{lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

8.6.16 Indexing with index

lwarp is told how to use *makeindex* using the PrintIndexCmd and HTMLIndexCmd options. The file lwarp.ist is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

For multiple indexes using *makeindex* and index:

(Assuming that the second index has file extensions .sist and .sind)

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist
      -o <projectname>.sind <projectname>.sidx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist
      -o <projectname>_html.sind <projectname>_html.sidx
  }
]{lwarp}
\usepackage{index}
. . .
\makeindex
\newindex{secondname}{sidx}{sind}{Second Index}
```

⚠ WINDOWS *For WINDOWS, replace the two ";" characters with "&".*

When creating the HTML index, "_html" is automatically appended to the index filenames.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

If the latexmk option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

8.6.17 Indexing with splitidx

lwarp is told how to use *splitindex* using the PrintIndexCmd and HTMLIndexCmd options. The file lwarp.ist is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

If the latexmk option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

⚠ \thepage When using \AtWriteToIndex or \AtNextWriteToIndex, the user must not refer to

\thepage during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 534.17 in the lwarp-patch-memoir package for the \@@wrspindexhyp macro as an example.

For multiple indexes using *makeindex* and splitidx:

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    splitindex <projectname> -- -s lwarp.ist
  },
  HTMLIndexCmd={
    splitindex <projectname>_html -- -s lwarp.ist
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "_html" is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

For multiple indexes using *xindy* and splitidx:

```
\usepackage[
  xindy, latexmk,
  PrintIndexCmd={
    splitindex -m xindy <projectname> -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  },
  HTMLIndexCmd={
    splitindex -m xindy <projectname>_html -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "_html" is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

8.6.18 Indexing with imakeidx

Due to the number of methods which may be used to process multiple indexes, the options for style file and *xindy* language and codepage must be specified in one of several different ways. These are described in detail later in this section, but are summarized here.

If shell escape is used, imakeidx will automatically compile the indexes by itself. Options specifying a custom style file and *xindy* language and codepage must be specified for each `\makeindex` command using its `options=` option, which must include lwarp's special `lwarp.ist` or `lwarp.xdy` file, or a file based on them. If using a custom indexing style file, see sections 8.6.20 and 8.6.21. The `splitindex` option is also available of shell escape is used, in which case the splitidx package and *splitindex* program will also be used.

If shell escape is not possible, *latexmk* may be used to automatically compile the indexes. The style, language, and codepage options are specified with lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options. These are passed to *latexmk* by *lwarpmk*'s **lwarpmk printindex** and **lwarpmk htmlindex** commands.

Where shell escape and *latexmk* are not possible, *lwarpmk* may be used to manually compile the indexes. lwarp's `PrintIndexCmd` and `HTMLIndexCmd` options are used.

For a single or multiple indexes using *makeindex* and imakeidx:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

imakeidx will automatically compile the indexes. Shell escape is not required while using *makeindex*. `latexmk` may be specified, and if so it will be used for **`lwarpmk print`** and **`lwarpmk html`**, but *imakeidx* will actually create the indexes.

For a single or multiple indexes using *makeindex* and *splitindex* with imakeidx:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

⚠ enable shell escape

Shell escape is required while using *splitindex*. For the first compile, use

Enter ⇒ **`pdflatex --shell-escape projectname.tex`**

Enter ⇒ **`pdflatex --enable-write18 projectname.tex`** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex*, and will also use *makeindex* to compile the indexes.

`latexmk` may be specified, and if so it will be used for **`lwarpmk print`** and **`lwarpmk html`**, but *imakeidx* will actually create the indexes.

For multiple indexes using *xindy* and imakeidx, using shell escape:

Options may be given to imakeidx's `\makeindex` command. The style file `lwarp.xdy` is automatically used for HTML output, and is not necessary for print output since the output will be similar. If language or codepage must be set, they should be specified as options for `\makeindex`, since imakeidx will process the indexes.

```
\usepackage[xindy,latexmk] {lwarp}
\usepackage[xindy,splitindex]{imakeidx}
. . .
\makeindex[
  options={ -M lwarp.xdy -L english -c utf8 }
]
\makeindex[
  name=secondname,
  options={ -M lwarp.xdy -L english -c utf8 }
]
```

⚠ enable shell escape

For the first compile, use

Enter ⇒ **pdflatex --shell-escape projectname.tex**

Enter ⇒ **pdflatex --enable-write18 projectname.tex** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex* if selected, and will also use *xindy* to compile the indexes.

If selected, *latexmk* will automatically recompile the entire document as necessary.

For indexes using *xindy* and *imakeidx*, without shell escape, but *with latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\usepackage[
  xindy,
  xindyLanguage=english,                    <optional>
  xindyCodepage=utf8,                       <optional>
  latexmk,
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

latexmk will create the indexes automatically when **lwarpmk print** and **lwarpmk html** are executed.

For indexes using *xindy* and *imakeidx*, without shell escape, and *without latexmk*:

lwarpmk must be told how to create the indexes:

```
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

⚠ WINDOWS *For WINDOWS, replace the two ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

8.6.19 Indexes with memoir

For a single index with memoir and makeindex:

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.ist` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes with memoir and makeindex, using *latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically when the user executes **`lwarpmk print`** and **`lwarpmk html`**.

For multiple indexes with memoir and makeindex, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  makeindex,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist secondname.idx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist secondname_html.idx
  }
]{lwarp}
. . .
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS *For WINDOWS, replace the two ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For a single index with memoir and xindy:

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk                                   <optional>
]{lwarp}
. . .
\xindyindex
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes with memoir and xindy, using latexmk:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk
]{lwarp}
. . .
\xindyindex
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically.

For multiple indexes with memoir and xindy, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
. . .
\xindyindex
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS *For WINDOWS, replace the four ";" characters with "&".*

<projectname> is the \jobname: if compiling "name.tex", use the filenames name.idx and name_html.idx.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

8.6.20 Using a custom *makeindex* style file

Prog makeindex
File lwarp.ist

When using *makeindex*, *lwarpmk* uses the file lwarp.ist to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *makeindex* style file:

1. Copy lwarp.ist to a new filename such as projectname.ist
2. Make changes to projectname.ist. Keep the lines which refer to \hyperindexref. These lines creates the hyperlinks for the HTML index. During print output \hyperindexref becomes a null function.

Opt makeindexStyle

3. In the document source use the makeindexStyle option for lwarp:

```
\usepackage[
    ... other options ...
    \textred{makeindexStyle=projectname.ist},
]{lwarp}
```

Likewise, refer to the custom style file if using \PrintIndexCmd, \HTMLIndexCmd, or \LatexmkIndexCmd.

4. Recompile the print version, which causes lwarp to rewrite the lwarpmk.conf configuration file. This tells *lwarpmk* to use the custom projectname.ist file instead of lwarp.ist.

8.6.21 Using a custom *xindy* style file

Prog xindy
File lwarp.xdy

When using *xindy*, *lwarpmk* uses the file lwarp.xdy to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *xindy* style file:

1. Copy lwarp.xdy to a new filename such as projectname.xdy
2. Make changes to projectname.xdy.

   Keep the lines which refer to \hyperindexref:

   ```
   (define-attributes (("hyperindexref")))
   (markup-locref :open "\hyperindexref{" :close "}")
   ...
   (markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
   ```

   These lines create the hyperlinks for the HTML index. During print output \hyperindexref becomes a null function.

   To create custom styles, refer to the lines for \textbf and \textit.

Opt xindyStyle

3. In the document source use the xindyStyle option for lwarp:

   ```
   \usepackage[
       ... other options ...
       \textred{xindyStyle=projectname.xdy},
   ]{lwarp}
   ```

   Likewise, refer to the custom style file if using \PrintIndexCmd, \HTMLIndexCmd, or \LatexmkIndexCmd.

4. Recompile the print version, which causes lwarp to rewrite the lwarpmk.conf configuration file. This tells *lwarpmk* to use the custom projectname.xdy file instead of lwarp.xdy.

8.6.22 Additional indexing limitations

⚠ xindy with hyperref

xindy and hyperref may not work well together for print output with “see”, “see also”, reference ranges, or stylized index references. It may be necessary to turn off hyper-referencing for indexes:

```
\usepackage[hyperindex=false]{hyperref}
```

⚠ empty index

If an HTML index is empty, it may be necessary to add the following before lwarp is

loaded:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
. . .
\usepackage{lwarp}
```

makeindex custom display styles

When using *makeindex*, custom display styles are possible:

```
\begin{warpprint}
\newcommand{\notesstyle}[1]{#1nn}
\end{warpprint}

\begin{warpHTML}
\makeatletter
\newcommand{\notesstyle}[1]{\LWR@doindexentry{#1} notes }
\makeatother
\end{warpHTML}
. . .
A sentence.\index{key|notesstyle}
```

xindy custom display styles

For custom styles with *xindy*, see `lwarp.xdy` for `\textbf` and `\textit` as examples.

8.6.23 Index positions, TOC, tocbibind

placement and TOC options

An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind

On its own HTML page, with an automatic TOC entry:

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex

numbered index section

Use the tocbibind `numindex` option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

8.7 Math

8.7.1 Math in section names

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

8.7.2 Rendering tradeoffs

Math rendering

Math may be rendered as SVG graphics or using the MathJax JavaScript display engine.

SVG files

Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline

The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files

Others LaTeX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML

Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 10 regarding EPUB output with MathJax.

8.7.3 SVG option

SVG math option

For SVG math, math is rendered as usual by LaTeX into the initial PDF file using the current font[14], then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LaTeX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the LaTeX code which generated the math, allowing copy/paste of the LaTeX math expression into other documents.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

SVG math copy/paste

For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the LaTeX code for the math expression. For $\mathcal{AMS}$ environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred $\mathcal{AMS}$ environment, although the `\tag` macro will still appear inside the LaTeX math expression.

⚠ SVG math in TeX boxes

SVG math does not work inside TeX boxes, since a `\newpage` is required before and after each image.

8.7.4 MathJax option

MathJax math option

Prog MathJax

The popular MathJax alternative (`mathjax.org`) may be used to display math.

When MathJax is enabled, math is rendered twice:

1. As regular LaTeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LaTeX, and
2. As detokenized printed LaTeX commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current LaTeX

[14] See section 519 regarding fonts and fractions.

values, and the MathJax cross-referencing system is ignored in favor of the LaTeX internal system, seamlessly integrating with the rest of the LaTeX code.

8.7.5 Customizing MathJax

MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

8.7.6 MathJax limitations

MathJax limitations

Prog MathJax

Limitations when using MathJax include:

subequations

- MathJax itself does not support subequations. This may be improved by parsing the LaTeX math expression to manually insert tags, but this has not yet been done.

footnotes in math

- Footnotes inside equations are not yet supported while using MathJax.

lateximage

- Math appearing inside a lateximage, and therefore also inside a Ti*k*z or `picture` environment, is rendered as SVG math even if MathJax is used in the rest of the document.

siunitx

⚠ siunitx inside an equation

- Usage of siunitx inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

  https://github.com/burnpanck/MathJax-siunitx

  Also see section 8.7.11.

tabbing

- A `tabbing` environment is emulated using an HTML <pre>.While MathJax is enabled inside `tabbing`, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

⚠ other macros and packages

- Other math-related macros and packages are not supported by MathJax, including `\ensuremath` and bigdelim, along with occasionally-used macros such as `\relax`. lwarp emulates footnotes, units, and nicefrac for MathJax.

8.7.7 Catcode changes

preamble macros with math

The math shift character $ is not set for HTML output until after the preamble. Macros defined in the preamble which contain $ must be enclosed between \StartDefiningMath and \StopDefiningMath to temporarily change to the HTML meaning of $:

```
\StartDefiningMath
\newcommand{. . . }
\StopDefiningMath
```

As an alternative, use \(and \) instead of $, in which case \StartDefiningMath and \StopDefiningMath are not necessary.

If a package defines macros using $, it may be nessary to use \StartDefiningMath and \StopDefiningMath before and after loading the package.

8.7.8 Complicated inline math objects

\inlinemathnormal
\inlinemathother

changing contents

complicated alt tag

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as $x+1$, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an alt tag. The macro \inlinemathother may be used before a dynamic math expression, and \inlinemathnormal after. Doing so tells lwarp to use an unhashed SVG math image, even if MathJax is in use. See section 44.

8.7.9 Complicated display math objects

\displaymathnormal

By default, or when selecting \displaymathnormal, MATHJAX math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother
MathJax unsupported
complicated alt tag

When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MATHJAX and will not make sense as an HTML alt tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

8.7.10 ntheorem package

Pkg ntheorem
⚠ Font control

This conversion is not total. Font control is via CSS, and the custom LaTeX font settings are ignored.

⚠ Equation numbering

ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environmentswhen the option `thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's `thref` option.

8.7.11 siunitx package

Pkg siunitx

fractions

Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required

Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJax script.

⚠ tabular

Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

8.7.12 units and nicefrac packages

Pkg units

Pkg nicefrac

units and nicefrac work with lwarp, but MathJax does not have an extension for units or nicefrac. These packages do work with lwarp's option `svgmath`.

8.7.13 newtxmath package

Pkg newtxmath

⚠ loading sequence

The proper load order is:

```
...
\usepackage{lwarp}
...
\usepackage{amsthm}
\usepackage{newtxmath}
...
```

8.8 Graphics

Pkg graphics

Pkg graphicx

⚠ scale

Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

`\includegraphics` file formats

For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps`

image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a `.pdf` or `.eps` image is referred to with its file extension, the extension will be changed to `.svg` for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo
PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **`pdftocairo -svg filename.pdf`**

Prog lwarpmk pdftosvg

For a large number of images, use *lwarpmk*:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of filenames)**

Prog lwarpmk epstopdf
Prog epstopdf
epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **`lwarpmk pdftosvg *.PDF`**

to convert to SVG images.

DVI latex

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of filenames)**

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of filenames)**

PNG and JPG

For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF

GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities

If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx

If using the older graphics syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

⚠ viewport

⚠ viewport units

For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options — `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys.

HTML class — With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML `alt` tags — Likewise, the `\includegraphics` `alt` key adds an HTML `alt` tag to an image, and is ignored for print output. If not assigned, each image is given an `alt` tag according to `\ImageAltText`.

`\rotatebox` — `\rotatebox` accepts the optional `origin` key.

⚠ browser support — `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

8.8.1 tikz package

Pkg `tikz`

⚠ displaymath and matrices — If using display math with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the tikz expression must be replaced with `\&`.

8.8.2 grffile package

Pkg `grffile`

⚠ matching PDF and SVG — grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

8.8.3 color package

Pkg `color`

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

8.8.4 xcolor package

Pkg `xcolor`

`\colorboxBlock` and `\fcolorboxBlock` — `\colorboxBlock` and `\fcolorboxBlock` are provided for increased HTML compatibility, and they are identical to `\colorbox` and `\fcolorbox` in print mode. In HTML mode they place their contents into a `<div>` instead of a `<span>`. These `<div>`s are set to `display: inline-block` so adjacent `\colorboxBlocks` appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for `\colorboxBlock` and `\fcolorboxBlock` are created by lwarp's core if xcolor is loaded.

background: none

`\fcolorbox` and `\fcolorboxBlock` allow a background color of `none`, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes required.

colored tables

`\rowcolors` is supported, except that the optional argument is ignored so far.

colored text and boxes

`\textcolor`, `\colorbox`, and `\fcolorbox` are supported.

`\color` and `\pagecolor`

`\color` and `\pagecolor` are ignored. Use CSS or `\textcolor` where possible.

8.8.5 epstopdf package

Pkg epstopdf

⚠ convert to `.svg`

Images with an `.eps` extension will be converted to `.pdf`. The HTML output uses the `.svg` version, so use

Enter ⇒ **`lwarpmk pdftosvg <listofPDFfiles>`**

to generate `.svg` versions.

8.8.6 pstricks package

Pkg pstricks

⚠ use `pspicture`

All pstricks content should be contained inside a `pspicture` environment.

8.8.7 pdftricks package

Pkg pdftricks

⚠ convert image files

The pdftricks image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **`lwarpmk pdftosvg <jobname>-fig*.pdf`**

8.8.8 psfrag package

Pkg psfrag

⚠ use `psfrags`

The `psfrags` environment is modified to use `lateximage` to encapsulate the image. Always use a `psfrags` environment to contain any local `\psfrag` macros and the associated `\includegraphics` or `\epsfig` calls. Outside of a `psfrags` environment, psfrags adjustments will not be seen by lwarp.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

8.8.9 pstool package

Pkg pstool

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename

The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

8.8.10 asymptote package

Pkg asymptote

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

8.8.11 overpic package

Pkg overpic

⚠ scaling

The macros \overpicfontsize and \overpicfontskip are used during HTML generation. These are sent to \fontsize to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the overpic and Overpic environments.

8.8.12 Multimedia packages

Pkg multimedia

Pkg movie15

Pkg media9

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

8.9 Tabbing

The tabbing environment works, except that SVG math and lateximages do not yet work inside the environment.

⚠ math in tabbing

If math is used inside tabbing, place tabbing inside a lateximage environment, which will render the entire environment as a single SVG image.

8.10 Tabular

8.10.1 tabular environment

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include tabular and in-

stances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

⚠ floatrow

This includes before and after defining any macro which used \ttabbox from floatrow.

⚠ tabular inside another environment

- When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

⚠ \newcolumntype

- \newcolumntype is ignored; unknown column types are set to l.

Rules:

- Doubled \hlines, \midrules, and vertical rules are supported.

vertical rules

- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

full-width rules

- `\toprule`, `\midrule`, `\bottomrule`, and `\hline` ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

⚠ `\warpprintonly`
⚠ Misplaced `\noalign`

- For `\toprule` and `\bottomrule`, when combined with a `warpprint` or `warpHTML` environment, if a "Misplaced `\noalign`" error occurs, change

```
This & That \endhead
```

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevent to HTML output.

Other:

- tabularx ignores the width, but `X` columns do produce paragraph columns or multicolumns.

`longtable` headings

- For longtable, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

⚠ `tabular` inside a `<span>`

- In LaTeX, a `tabular` may be placed inside a `minipage`, but in HTML a `<table>` may not be inside a `<span>`. If this situation is detected, a warning is printed instructing the user to isolate the `<span>` using `\warpprintonly` or the `warpprint` environment.

8.10.2 multirow package

vposn

- Note that recent versions of multirow include a new optional `vposn` argument.

multirow cells

- For multirow, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
. . . &   \multirow{2}{.5in}{text}   & . . .
. . . &   \mrowcell                  & . . .
```

colored cells

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so `\warpprintonly` and `\warpHTMLonly` must be used to make versions for print and HTML.

with `\multicolumn`

- See section 339.2 for `\multicolumnrow`.

⚠ `\multicolumn` & `\multirow`

lwarp does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

⚠ skipped cells

As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines,

⚠ empty cells

`\mcolrowcell` must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```
. . . &  \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}  & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
```

8.10.3 longtable package

Pkg longtable

Use one of either `\endhead` or `\endfirsthead` for both print and HTML, and use a `\warpprintonly` macro to disable the other head phrase, and also the `\endfoot` and `\endfirstfoot` phrases. (See section 8.10.4 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced `\noalign`

Use the `\warpprintonly` macro instead of the `warpprint` environment. Doing so helps avoid "Misplaced `\noalign`." when using `\begin{warpprint}`.

⚠ `\kill`

`\kill` is ignored, place a `\kill` line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside `\warpprintonly`.

⚠ lateximage

longtable is not supported inside a `lateximage`.

8.10.4 threeparttablex package

Pkg threeparttablex

threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width

The table notes are created using a `\multicolumn`. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use `\UseMinipageWidths` before `\insertTableNotes`. The width is then specified, and in many cases the result is an improvement in overall table layout.

8.10.5 supertabular and xtab packages

Pkg supertabular

Pkg xtab

⚠ Misplaced alignment tab character &

For `\tablefirsthead`, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage

supertabular and xtab are not supported inside a `lateximage`.

8.10.6 colortbl package

Pkg colortbl

⚠ row/cell color

Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.

colortbl ignores the overhang arguments.

8.10.7 ctable package

⚠ Misplaced alignment tab character &

Use `\StartDefiningTabulars` before one or more `\ctables`, and `\StopDefiningTabulars`

after. These change the meaning of the ampersand & character.

8.10.8 bigdelim package

Pkg bigdelim
⚠ use \mrowcell

\ldelim and \rdelim use \multirow, so \mrowcell must be used in the proper number of empty cells in the same column below \ldelim or \rdelim, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

<-> a b
left { c d
e f
g h
<-> i j

8.11 Floats

8.11.1 Float contents alignment

⚠ figure & table alignment

\centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

8.11.2 float, trivfloat, and/or algorithmicx together

Pkg float
Pkg trivfloat
Pkg algorithmicx
⚠ package conflicts

If using \newfloat, trivfloat, and/or algorithmicx together, see section 488.1.

8.11.3 caption and subcaption packages

Pkg caption
Pkg subcaption
⚠ options

To pass options to caption, select the options before loading lwarp:

```
\documentclass{article}
. . .
\PassOptionsToPackage{options_list}{caption}
. . .
\usepackage{lwarp}
. . .
\usepackage{caption}
```

⚠ numbering To ensure proper float numbering, set caption positions such as:

```
\captionsetup[figure]{position=bottom}
\captionsetup[subfigure]{position=bottom}
\captionsetup[table]{position=top}
\captionsetup[subtable]{position=top}
```

Similarly for longtable. These positions depend on where the user places the `\caption` command inside each float.

8.11.4 subfig package

Pkg subfig

⚠ lof/lotdepth At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

In the document source, use `\hfill` and `\hspace*` subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

8.11.5 floatrow package

Pkg floatrow

⚠ Misplaced alignment tab character &

⚠ subfig package

Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 8.10.1.

When combined with the subfig package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ `\FBwidth`, `\FBheight` The emulation of floatrow does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

8.11.6 keyfloat package

Pkg keyfloat
⚠ keywrap

If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the `lw` option.)

8.12 KOMA-SCRIPT classes

Cls komascript

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

`\titlehead`, `\subject`, `\captionformat`, `\figureformat`, and `\tableformat` are not yet emulated.

⚠ Not fully tested! Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

8.13 MEMOIR class

Cls memoir
⚠ options clash

While emulating memoir, lwarp pre-loads a number of packages (section 534.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

`\verbfootnote` is not supported.

`\newfootnoteseries`, etc. are not supported.

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in `\pagenotesubhead` and related macros.

Poem numbering is not supported.

The `verbatim` environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

8.14 International languages

⚠ section and file names

If using *pdflatex* with the setting `\booltrue{FileSectionNames}`, non-ASCII text in section names can result in corrupted HTML file names. *pdflatex* may be used if setting `\boolfalse{FileSectionNames}`, in which case HTML file numbers will be generated.

For correct HTML file names, use *xelatex*, *lualatex*, or dedicated document classes / engines.

(As of this writing, this warning is only relevent to the kotex package.)

8.15 Miscellaneous packages

8.15.1 verse and memoir

Pkg verse

Cls memoir

\attrib

When using verse or memoir, always place a `\\` after each line.

The documentation for the verse and memoir packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. lwarp provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip

Len \vleftmargini

Len \HTMLvleftskip

Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word "Chorus", in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (`-layout` option) of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

8.15.2 newclude package

Pkg newclude

newclude modifies `\label` in a non-adaptive way, so newclude must be loaded before

⚠ loading

lwarp is loaded:

```
\documentclass{article}
. . . <font setup>
\usepackage{newclude}
\usepackage[warpHTML]{lwarp}
. . .
```

8.15.3 babel package

Pkg babel

⚠ \CaptionSeparator

When French is used, the caption separator is changed to a dash. The following may be used to restore it to a colon:

```
\renewcommand*{\CaptionSeparator}{:~}
```

punctuation spaces

⚠ customized spacing

Also when French is used, lwarp creates fixed-width space around punctuation by patching \FBcolonspace, \FBthinspace, \FBguillspace, \FBmedkern, \FBthickkern, \FBtextellipsis, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a warpprint environment so that the user's changes do not affect the HTML output.

8.15.4 polyglossia package

Pkg polyglossia

lwarp uses cleveref, which has some limitations when using polyglossia, possibly resulting in the error

```
! Undefined control sequence. . . . \@begindocumenthook
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by cleveref, then select other languages using \setotherlanguages.

Once the print version works with cleveref and polyglossia, the HTML version should work as well using lwarp.

8.15.5 todonotes and luatodonotes packages

Pkg todonotes

Pkg luatodonotes

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

8.15.6 fixme

Pkg fixme

External layouts (\fxloadlayouts) are not supported.

⚠ external layouts

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

8.15.7 chemfig package

If using \polymerdelim to add delimiters to a \chemfig, wrap both inside a single lateximage:

```
\begin{lateximage}[-chemfig-~\PackageDiagramAltText]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

8.15.8 chemformula package

⚠ chemformula with MathJax

chemformula works best without MathJax. If MathJax is used, \displaymathother must be used before array, and then \displaymathnormal may be used after. (The chemformula package adapts to array, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, \displaymathother may also be used for other forms of display and inline math which contain chemformula expressions.

8.15.9 mhchem package

See section 325.

8.15.10 xparse package

Pkg xparse

To remove from the log any warnings about redeclaring objects, place the following before lwarp is loaded:

```
\usepackage[log-declarations=false]{xparse}
```

8.15.11 kotex package

Pkg kotex

See section 8.14 regarding *pdflatex* and Korean section names.

⚠ Korean section names

9 Compiling using custom shell commands

lwarp and *lwarpmk* try to make it easy to process print and HTML compilation tasks in most situations. Depending on the operating system, command-line options, TEX engine, and lwarp options, the commands **`lwarpmk print`** and **`lwarpmk html`** are automatically set up to correctly recompile the project. These actions may be overridden using lwarp options, thus allowing the use of packages such as perltex and pythontex.

9.1 Command options

Opt PrintLatexCmd
Opt HTMLLatexCmd

The lwarp options `PrintLatexCmd` and `HTMLLatexCmd` are used to set customized commands to be executed by **`lwarpmk print`** and **`lwarpmk html`**.

`PrintLatexCmd` should be set to shell commands which take `project.tex` and generate `project.pdf`.

`HTMLLatexCmd` should be set to take `project_html.tex` and generate `project_html.pdf`. *lwarpmk* will then take `project_html.pdf` and automatically convert it and generate `project.html`.

9.2 Literal character macros

The lwarp package options are parsed by TEX, and so some characters require the use of a special macro to represent them. See table 7. `\LWRopquote` and `\LWRopseq` may be used to increase operating-system portability. `\jobname` must have `_html` appended for processing HTML. `\space` may be necessary between other macros.

⚠ macro not found

To use these macros, either kvoptions-patch must be loaded before lwarp:

```
\usepackage{kvoptions-patch}
\usepackage[
    PrintLatexCmd={ ... } ,
    HTMLLatexCmd={ ... }
]{lwarp}
```

Table 7: Literal character macros

Character	Macro	Comment
%	\LWRpercent	
$	\LWRdollar	
&	\LWRamp	
%	\LWRhash	
\	\LWRbackslash	
' or "	\LWRopquote	Depends on the operating system.
& or &&	\LWRopseq	Depends on the operating system.
(space)	\space	Forces an extra space.
(jobname)	\jobname	Without file extension.

or \lwarpsetup must be used to set PrintLatexCmd and HTMLLatexCmd:

```
\usepackage[...]{lwarp}
\lwarpsetup{
  PrintLatexCmd=
      {
          latex tm \LWRopseq
          dvips -o tm-pics.ps tm.dvi \LWRopseq
          ps2pdf tm-pics.ps \LWRopseq
          pdflatex tm.tex
      } ,
  HTMLLatexCmd=
      {
          latex tm_html \LWRopseq
          dvips -o tm_html-pics.ps tm_html.dvi \LWRopseq
          ps2pdf tm_html-pics.ps \LWRopseq
          pdflatex tm_html.tex
      }
}
```

9.3 *latexmk*

Prog latexmk If *latexmk* is used for a project, it may be easiest to continue using it.

latexmk project.tex would create project.pdf as normal.

latexmk project_html.tex would create project_html.pdf, then

lwarpmk pdftohtml project_html.pdf would take project_html.pdf and convert it to project.html.

Pkg sagetex *latexmk* may simplify the use of packages such as sagetex.

9.4 perltex package

Pkg perltex The lwarp package option settings to use perltex would be similar to:

```
\usepackage[
  . . .
  PrintLatexCmd={perltex -latex=pdflatex project.tex} ,
  HTMLLatexCmd={perltex -latex=pdflatex project_html.tex} ,
  . . .
]{lwarp}
```

⚠ "impure" math Place perltex math expressions between `\displaymathother` and `\displaymathnormal`, or `\inlinemathother` and `\inlinemathnormal`. See section 8.7.9.

9.5 pythontex package

Pkg pythontex An example using pythontex:

```
\usepackage[
  . . .
  PrintLatexCmd={
    pdflatex project.tex \LWRopseq
    pythontex project \LWRopseq
    pdflatex project.tex
  } ,
  HTMLLatexCmd={
    pdflatex project_html.tex \LWRopseq
    pythontex project_html \LWRopseq
    pdflatex project_html.tex
  } ,
  . . .
]{lwarp}
```

Another possibility is to use *latexmk*, placing the **`latexmk . . .`** commands in the `PrintLatexCmd` and `HTMLLatexCmd` options. While using these options, the lwarp option `latexmk` would not be used.

⚠ "impure" math
⚠ HTML look-alike

No attempt has yet been made to make pythontex robust with HTML output. Some math objects must be surrounded by `\displaymathother` ... `\displaymathnormal`, or `\inlinemathother` ... `\inlinemathnormal`. Displays of code may have to be enclosed inside a `latexmage` environment to prevent <, > and similar from being interpreted by the browser as HTML entities.

9.6 Other packages

Pkg sympytex
Pkg rterface

Other packages such as sympytex and rterface would be set up similar to pythontex, and the same warnings would apply.

9.7 *make* program

Prog make

To use lwarp with the *make* program, have the `makefile` take `project.tex` and generate the print version `project.pdf`, as normal. `\usepackage{lwarp}` must be used, and it generates `lwarpmk.conf` when the print version is created.

To generate HTML, first have `project_html.tex` be compiled to generate `project_html.pdf`. This must be in PDF format. Finally, have `project_html.pdf` be converted to HTML using **`lwarpmk pdftohtml project_html.pdf`**, and convert SVG math with **`lwarpmk limages`**.

9.8 UTF-8 locale

⚠ UTF-8 locale

lwarpmk uses the *texlua* program, which sets the "locale" to "C", including for external operating-system calls such as when executing **`lwarpmk html`**. In some cases, an external program called from the user's document may require the use of a UTF-8 "locale". For UNIX-related operating systems, it may be required to use lwarp's custom compilation options to add a locale change:

```
\usepackage{lwarp}[
  PrintLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex -shell-escape project.tex
  }
  HTMLLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex -shell-escape project_html.tex
  }
]
```

Pkg ditaa

The only example seen so far where this is required is the ditaa package, where the locale change allows the use of UTF-8 with XeLaTeX and ditaa. To use LuaLaTeX instead, the locale change would have to be made inside the ditaa package where its calls the *ditaa* program.

10 EPUB conversion

lwarp does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

<meta> author

To assign the author's name for regular lwarp HTML files, and also for the EPUB, use `\HTMLAuthor {⟨name⟩}`. This assigns the name to the `<meta>` author element. It may be set empty, and it defaults to `\theauthor`.

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

`FormatEPUB`

Bool `FormatEPUB`
Default: `false`

`FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

To help convert lwarp HTML output to EPUB, add

```
\booltrue{FormatEPUB}
```

to the project's source preamble after `\usepackage{lwarp}`. The EPUB version of the document cannot co-exist with the regular HTML version, so

Enter ⇒ **`lwarpmk cleanall`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk limages`**

to recompile with the `FormatEPUB` boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.

Calibre

The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program *Calibre* (`https://calibre-ebook.com/`).

⚠ search order

The EPUB conversion program must know what order the files are included. For lwarp projects, set the EPUB conversion software to do a breadth-first search of the files. For *Calibre*, this option is found in

Preferences → Plugins → File type plugins → HTML to Zip

⚠ encoding

Check the box Add linked files in breadth first order. Set the document encoding as `utf-8`, which is what lwarp generates for HTML, even if the original printed document uses some other encoding.

⚠ section breaks

The EPUB-conversion program must also know where the section breaks are located. For a list of lwarp's section headings, see table 9. For example, an `article` class document would break at `\section`, which is mapped to HTML heading level `<h4>`, whereas a `book` class document would break at `\chapter`, which is HTML heading level `<h3>`. For *Calibre*, this option is found in

> **Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)**

Select the "magic wand" to the right of this entry box, and set the first entry

> **Match HTML tags with tag name:**

to "h4". (Or "h3" for document classes with `\chapters`.) The Detect chapters at field should then show

> **//h:h4** — or — **//h:h3**

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the lwarp-generated HTML files may be loaded by *Calibre*, and then converted to an EPUB.

MathJax support

MathJax may be used in EPUB documents. Some e-readers include MathJax, but any given reader may or may not have a recent version, and may or may not include extensions such as support for siunitx.

lwarp adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader's version of MathJax, so lwarp requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn't work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MathJax, especially for equations numbered by chapter, or where siunitx support is important.

11 Word-processor conversion

lwarp may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LibreOffice works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. lwarp provides some assistance in locating these frame boundaries, as shown below.

11.1 Activating word-processor conversion

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

FormatWP

Bool FormatWP
Default: false

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Additionally, honors the booleans WPMarkFloats, WPMarkMinipages, WPMarkTOC, and WPMarkLOFT.

To help modify lwarp HTML output for easier import to a word processor, add

```
\booltrue{FormatWP}
```

to the project's source preamble after lwarp is loaded. The following changes are then made to the HTML output:

formatting adjustments

- If using a class without chapters, \section and lower are shifted up in level for the HTML heading tags. The CSS has not been changed, so the section heading formats will not match the normal HTML output, but when imported to *LibreOffice Writer* the higher section headings will import as **Heading 1** for the title, **Heading 2** for \section, etc.
- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and s, but they are no longer useful when the document has been imported into a word processor.
- An additional with an id encapsulates each float and minipage, which on import into *LibreOffice Writer* causes a thin frame to appear around the text block for each.
- Float captions are given an explicit italic formatting.

- Tabular rule borders are made explicit for *LibreOffice Writer*. LibreOffice displays a light border around each cell while editing, even those which have no border when printed, and lwarp also uses a light border for thin rules, so it will be best to judge the results using the print preview instead of while editing in LibreOffice.
- `\includegraphics` and svg math width and height are made explicit for LibreOffice.
- `\hspace` is approximated by a number of `\quad`s, and rules are approximated by a number of underscores.
- Explicit HTML styles are given to:
  - `\textsc`, etc.
  - `\underline`, soul and ulem markup.
  - `center`, `flushleft`, `flushright`.
  - `\marginpar`, keyfloat, sidenotes, floatflt, and wrapfig.
  - fancybox `\shadowbox`, etc.
  - The LaTeX and TeX logos.
- Honors several booleans:

  WPMarkFloats: Marks the begin and end of floats.

  WPMarkMinipages: Marks the begin and end of minipages.

  WPMarkTOC: Marks the location of the Table of Contents.

  WPMarkLOFT: Marks the locations of the List of Figures/Tables.

  WPMarkMath: Prints LaTeX math instead of using images.

  WPTitleHeading: Adjusts title and section headings.

  Several of these may be used to add markers to the HTML text which help determine where to adjust the word processor document after import.

11.2 Additional modifications

`WPMarkFloats`

Bool `WPMarkFloats`
Default: `false`

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.

WPMarkMinipages

Bool WPMarkMinipages
Default: false

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

WPMarkTOC

Bool WPMarkTOC
Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set `false`*, the actual* TOC *is printed instead.*

WPMarkLOFT

Bool WPMarkLOFT
Default: false

While formatting for word processors, adds

```
=== list of figures ===    and/or
=== list of tables ===
```

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

WPMarkMath

siunitx
Bool WPMarkMath
Default: false
Prog TeXMaths

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

When using the siunitx package, enter

```
\usepackage{siunitx}
```

in the *TeXMaths* preamble. Equation numbering is problematic for $\mathcal{AMS}$ math environments.

Table 8: Section HTML headings for word-processor conversion

	HTML headings*			
	With \chapter		Without \chapter	
	WPTitleHeading		WPTitleHeading	
Section	true	false	true	false
Title	<h1>	plain	<h1>	plain
\book				
\part	<h2>	<h1>	<h2>	<h1>
\chapter	<h3>	<h2>	—	—
\section	<h4>	<h3>	<h3>	<h2>
\subsection	<h5>	<h4>	<h4>	<h3>
\paragraph	<h6>	<h5>	<h5>	<h4>
\subparagraph		<h6>	<h6>	<h5>

* For default depths when not FormatWP, see table 9 on page 188.

WPTitleHeading

Bool WPTitleHeading
Default: false
section headings

While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 172.

11.3 Recommendations

TOC, LOF, LOT

For use with *LibreOffice Writer*, it is recommended to:

1. Set \booltrue{FormatWP}
2. Set \booltrue{WPMarkTOC} and \boolfalse{WPMarkLOFT}
3. Use lwarp to generate the HTML document.
4. Copy/paste from the HTML document into an empty *LibreOffice Writer* document.
5. Manually insert a LibreOffice TOC in the LibreOffice document.
6. Manually add frames around each float, adding a caption which is cut/pasted from each float's simulated caption.
7. Manually create cross references.

This process yields a document with an actual LibreOffice Table of Contents, but a simulated List of Figures and List of Tables.

siunitx For siunitx, remember to adjust the preamble as mentioned above.

LO view border options LibreOffice has options in the **View** menu to turn on/off the display of thin borders around table cells and text objects.

11.4 Limitations

Floats and captions are not explicitly converted to LibreOffice floats with their own captions. Floats are surrounded by a thin frame in the LibreOffice editor, and may be marked with `WPMarkFloats`, but are not given a proper LibreOffice object frame. Captions are given an explicit italic formatting, but not a proper LibreOffice paragraph style.

Cross references are not actual LibreOffice linked cross references.

The List of Figures and List of Tables are not linked. The pasted pseudo LOF and LOT match the numbering of the LaTeX and HTML versions.

Equation numbering is not automatic, but the equation numbers in SVG math will match the LaTeX and HTML output. SVG math is recommended when using the $\mathcal{AMS}$ environments, which may have multiple numbered equations per object.

As of when last checked, LibreOffice ignores the following:

- Minipage alignment.
- Tabular cell vertical alignment.
- Image rotation and scaling.
- Rounded border corners, which are also used by:
  - `\textcircled`
  - booktabs trim
- `\hspace` and rules, also used by algorithmic.
- Coloring of text decorations, used by soul and ulem.
- Overline text decoration, used by romanbar.

LibreOffice also has limitations with frames and backgrounds:

- Multiple lines in an object are framed individually instead of as a whole.
- Nested frames are not handled correctly.
- Images inside boxes are not framed correctly.
- Spans with background colors and frames are not displayed correctly.

12 Modifying lwarp

locating something

To quickly find the source for a package in `lwarp.dtx`, search for `*packagename`, such as `*siunitx`.

Likewise, to quickly find the source for a file in `lwarp.dtx`, search for `*filename`, such as `*lwarp.css`.

Purely text-based packages probably will work as-is when generating HTML.

Look to existing code for ideas on how to expand into new code.

image of TEX output

An environment may be converted to a `lateximage` then displayed with an image of the resulting LATEX output. See section 88 for an example of the `picture` environment.

css classes

To create a custom HTML block or inline CSS class, see section 51.9.

print/HTML macros

To create print and HTML versions of the same macro or environment, see section 36.

⚠ TEX boxes

Any TEX boxes must be undone, as SVG math or `lateximages` require `\newpage`, which will not work in a TEX box.

index recreation

To recreate the index for the lwarp documentation:

```
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
splitindex lwarp.idx -- -s gind.ist
```

12.1 Creating a development system

The following creates a local development system for lwarp on a TeXLive system in a UNIX-like environment. Doing so allows anything requesting lwarp to use the development version instead of whichever version is installed in TeXLive.

Create a development directory:

Place into this directory `lwarp.dtx` and `lwarp.ins`.

To create `lwarp.sty`, execute

Enter ⇒ **`pdflatex lwarp.ins`**

which creates `lwarp.sty` and several hundred additional `lwarp-*.sty` files for the various packages which are supported.

To create the documentation `lwarp.pdf`, execute

Enter ⇒ **`pdflatex lwarp.dtx`**

To make the development files visible to other projects:

Create the directory

`/usr/local/texlive/texmf-local/tex/latex/local/lwarp`

Inside this directory, create the file `update`, containing:

```
ln -s /path_to_dev_directory/lwarp*.sty .
ln -s /path_to_dev_directory/lwarp_baseline_marker.png .
ln -s /path_to_dev_directory/lwarp_baseline_marker.eps .
mktexlsr
```

Run ./update now, and whenever a new lwarp-* package is added.

To make the development version of *lwarpmk* visible to other projects:

```
cd /opt
ln -s /usr/local/texlive/texmf-local/bin/x86_64-linux texbin_local
cd texbin_local
ln -s ../../scripts/lwarp/lwarpmk.lua lwarpmk
cd /usr/local/texlive/texmf-local/scripts/
mkdir lwarp
cd lwarp
ln -s /path_to_dev_directory/lwarpmk.lua lwarpmk
```

Verify that the correct version is found with

Enter ⇒ **`which lwarpmk`**

To make the local versions visible to the shell:

Paths must be set by the shell startup, such as in `.bashrc` and `.cshrc`:

In `.bashrc`:

```
PATH=/opt/texbin_local:/opt/texbin:$PATH
```

In `.cshrc`:

```
setenv PATH ${HOME}/bin:/opt/texbin_local:/opt/texbin:${PATH}
```

12.2 Modifying a package for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

When creating HTML, lwarp redefines the `\usepackage` and `\RequirePackage` macros such that it first looks to see if a `lwarp-<packagename>.sty` version exists. If so, the lwarp version is used instead. This modular system allows users to create their own versions of packages for lwarp to use for HTML, simply by creating a new package with a `lwarp-` prefix. If placed in the local directory along with the source code, it will be seen by that project alone. If placed alongside the other `lwarp-` packages where TeX

can see it, then the user's new package will be seen by any documents using lwarp. (Remember `mktexlsr` or `texhash`.)

An `lwarp-<packagename>.sty` package is only used during HTML generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful HTML conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing `lwarp-` packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new `lwarp-` package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a "local" prefix according to the package name, and `@` characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for HTML output. Only the "user-facing" macros need to be nullified or emulated.

Each `lwarp-*` package should first call either of:

```
\LWR@ProvidesPackageDrop
  -or-
\LWR@ProvidesPackagePass
```

If "`Drop`"ped, the original print-version package is ignored, and only the `lwarp-` version is used. Use this where the original print version is useless for HTML. If "`Pass`"ed, the original package is loaded first, with the user-supplied options, then the `lwarp-` version continues loading as well. See section 358 (ntheorem) for an example of selectively disabling user options for a package. Use this when HTML output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a `lwarp-` version.

12.2.1 Adding a package to the lwarp.dtx file

When adding a package to `lwarp.dtx` for permanent inclusing in lwarp, provide the `lwarp-<packagename>` code in `lwarp.dtx`, add its entry into `lwarp.ins`, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to `lwarp.dtx` in section 20.1. This causes lwarp to stop with an error if packagename is loaded before lwarp. Finally, add an entry in table 2, Supported packages and features, and also the Updates section.

12.3 Modifying a class for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

12.4 Testing lwarp

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

Remember that the configuration files are only rewritten when compiling the printed version of the document.

When changing the source to *lwarpmk* or a CSS file in `lwarp.dtx`:

1. Change the source in `lwarp.dtx`.
2. `pdflatex lwarp.ins`
3. `pdflatex lwarp.dtx`
4. If modifying *lwarpmk* the new version should now be active.
5. If modifying CSS files:
   (a) For the document, `lwarpmk print` to update the CSS files in the project.
   (b) Reload the HTML document to see the effect of the new CSS files.

Sometimes it is worth checking the `<project>_html.pdf` file, which is the PDF containing HTML tags. Also, `<project>_html.html` has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and CSS code.

12.5 Modifying *lwarpmk*

Prog `lwarpmk`
File `lwarpmk.lua`

In most installations, `lwarpmk.lua` is an executable file located somewhere the operating system knows about, and it is called by typing **`lwarpmk`** into a terminal.

A project-local copy of `lwarpmk.lua` may be generated, modified, and then used to compile documents:

1. Add the `lwarpmk` option to the lwarp package.
2. Recompile the printed version of the document. The `lwarpmk` option causes lwarp to create a local copy of `lwarpmk.lua`
3. The `lwarpmk` option may now be removed from the lwarp package.
4. Copy and rename `lwarpmk.lua` to a new file such as `mymake.lua`.

5. Modify `mymake.lua` as desired.
6. If necessary, make `mymake.lua` executable.
7. Use `mymake.lua` instead of `lwarpmk.lua`.

13 Troubleshooting

13.1 lwarp package error conditions and warnings

lwarp tests for a number of error conditions and prints appropriate warnings. The following is a summary of these conditions.

13.1.1 Configuration file `lwarpmk.conf`

File does not exist: The configuration file must exist for lwarpmk.

Incorrect `Unix` /`Windows` selection: The operating system which was detected by lwarp. So far only `Unix` and `Windows` are supported.

Incorrect delimiter characters. Older versions of *lwarpmk* used a different delimiter.

Source name is set to `lwarp`: lwarp has recently been recompiled in this directory, which overwrote the project's configuration files. This also occurs if *lwarpmk* is executed in lwarp's source directory.

Incorrect operating system: The configuratio file was set for a different operating system, perhaps due to sharing in a collaborative project.

Outdated configuration files: lwarp has been updated since this projects was last compiled. If there appears to be a valid print command in the file, lwarpmk displays this to instruct the user how to recompile the print version, which then updates the configuration files.

The designated source file does not exist: For whatever reason…

Unknown engine: lwarp cannot determing which engine is being used. Supported are DVI LaTeX, PDF LaTeX, XeLaTeX, LuaLaTeX, and upLaTeX.

13.1.2 Image generation with `lwarpmk limages`

"Wait a moment for the images to complete before reloading page.":

Images are generated by background tasks. If the document is reloaded before these tasks are complete, some images may not yet be generated. *lwarpmk* tries to wait for background tasks to complete before exiting.

HTML version does not exist: Images are extracted from the HTML version, which must be compiled before images are generated.

`*-images.txt` does not exist: This file tells which images to extract from the HTML file. If the file does not exist, it may be that no SVG math or `lateximages` were used. If so, **`lwarpmk limages`** is not necessary.

Cross references are not correct: The document must have up-to-date cross references to locate the images to extract. A number of conditions may cause incorrect cross references.

"WARNING: Images will be incorrect.": An image reference was not found. Recompile.

`lwarpmk epstopdf *` or `lwarpmk pdftosvg *`: Errors if filenames are not found.

13.1.3 Default bitmapped font

lwarp requires the use of a vector font. If lwarp detects that the document uses the default Computer Modern font, and the cm-super package is not installed, it is assumed that the font is bitmapped. An error is generated, along with the recommendation to install cm-super or use lmodern.

13.1.4 Packages

Loaded before lwarp: Some packages and classes must be loaded before lwarp. These include input and font encoding, morewrites and newclude, and a number of CJK-related packages and classes.

Loaded after lwarp: Most packages which are modified by lwarp must be loaded after lwarp.

Loaded never: Some packages do not work with lwarp. An error is generated, along with a list of alternatives to consider.

Specific packages: Some packages enforce a specific load order vs. certain other packages.

Patching error: lwarp tries to patch some packages using xpatch. If the original package has been updated more recently than lwarp, a patch may not work. It may be necessary to use an older version of the package until lwarp is updated.

longtable: lwarp's longtable package issues detailed error messages regarding the use of the table headers and footers.

13.1.5 Compiling

`SideTOCDepth` < `FileDepth`: A warning is displayed if these counters are set such that the sidetoc will not be able to access all pages of the website.

Duplicate filenames: lwarp may generate file names from section names. While doing so, the filenames are simplified and special characters are removed. If this process generates a duplicate filename, and error is generated, describing the filename and which section name generated it.

⚠ HTML corrupted **Multirow:** When `\multirow` or `\multicolrow` are used, `\mrowcell` or `\mcolrowcell` must be placed in the appropriate cells to avoid corrupted HTML output.

(width,height) missing a comma: `\makebox` and `\framebox` can accept a parenthesis-delimited width and height, which must be separated by a comma.

"Load graphicx or graphics for improved SVG math baselines.": SVG math baselines are improved if either of these packages are used.

"Load graphicx or graphics for improved XeTeX logo.": If these packages are loaded, the XeLaTeX logo can use the reversed "E".

"It is recommended to use `[width=xx\linewidth]` instead of `[scale=yy]` ": Browser support of `scale` does not have the same effect as in LaTeX.

13.2 Using the lwarp package

The following address problems which may occur, and possible solutions to each.

Also see:
Section 7.10: Commands to be placed into the `warpprint` environment
Section 8: Special cases and limitations

⚠ HTML corrupted **Text is not converting correctly / corrupted HTML tags:**

- Font-related UTF-8 information must be embedded in the PDF file. See section 7.4 regarding bitmapped vs. vector fonts.
- See section 8.2.1 regarding HTML entities and the characters &, <, and >.

Undefined HTML settings:

- See the warning regarding the placement of the HTML settings at section 7.6.

Tabular problems: See section 8.10.1.

Obscure error messages:

Print first: Be sure that a print version of the document compiles and that your document's LaTeX code is correct, before attempting to generate an HTML version.

`\end{warpHTML}, \end{warpprint}, \end{warpall}`: Each of these must be without any other characters on the same line.

Options clash: If using memoir, see section 8.13.

"No room for a new `\write`.": Before `\usepackage{lwarp}`, add:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
```

"Missing $ inserted.": If using a filename or URL in a footnote or `\item`, escape underscores with `\_`.

"Label(s) may have changed. Rerun to get cross-references right.":

This warning may repeat endlessly if a math expression is used in a caption. Simple math expressions such as $X=1$ may be replaced with

```
\textit{X}\,=\,1
```

"Leaders not followed by proper glue": This can be caused by a missing `l@<floattype>` or `l@<sectiontype>` definition. See lwarp's definitions for examples.

"Improper \prevdepth": `lateximages` and SVG math require `\newpage`, which cannot work inside TEX boxes or `\ensuremath`. Anything using `\newsavebox`, `\newbox`, `lrbox`, `\savebox`, `\hbox`, `\vbox`, `\usebox`, `\sbox`, etc., must be modified to work without box commands.

If you find something using `\ensuremath`, have it temporarily set:

```
\LetLtxMacro\@ensuredmath\LWR@origensuredmath
```

inside a group first.

⚠ macros in section,table,figure names

Also, custom macros which appear inside a section, figure, or table name should be made robust since they appear inside the `.toc`, `.lof`, or `.lot` files. Use `\newrobustcmd` or `\robustify` from etoolbox, xparse, etc.

⚠ BibTeX

If using BibTeX, see section 8.6.9.

⚠ polyglossia

"! Undefined control sequence. . . . \@begindocumenthook": See section 8.15.4 if using polyglossia.

⚠ custom macros for environments

"\begin{equation} ended by \end{document}": Do not use custom macros such as `\beq` and `\eeq` to replace

```
\begin{equation}
. . .
\end{equation}
```

⚠ `\LWR@formatted`

"Misplaced \omit": If using `\LWR@formatted` to define new macros for print and HTML modes, see section 36 regarding `\LWR@expandableformatted`.

⚠ "impure" math objects

Complicated objects inside math: Some objects, such as Ti*k*z, may not compile in lwarp's normal math emulation. Insert

```
\displaymathother -or- \inlinemathother
```

before the math, and then

```
\displaymathnormal -or- \inlinemathnormal
```

when displaying "normal" math. See section 8.7.9.

Slow compliation of math objects: Complicated math objects can also cause problems with `alt` tags, resulting in very slow compilation, large `alt` tags, and possible crashes. Use `\inlinemathother` ... `\inlinemathnormal` or `\displaymathother` ... `\displaymathnormal` around the math expression.

⚠ MathJax

Incorrect MathJax: Some objects do not convert to MathJax. Use `\displaymathother` before these objects, then `\displaymathnormal` to return to "normal" display math. See section 8.7.9.

Missing sections: See section 7.6 regarding the `FileDepth` and `SideTOCDepth` counters, and the use of `\tableofcontents` in the home page.

Misnumbered footnotes from section headings: See section 8.5.4.

Missing HTML files:

- See the warning regarding changes to the HTML settings at section 7.6.
- Ensure that the filenames are unique after math and short words are removed. See `FileSectionNames` at section 7.6.

Missing / incorrect cross-references:

- Use `lwarpmk again` followed by `lwarpmk html` or `lwarpmk print` to compile the document one more time.

labels
⚠ label characters
\nameref
⚠ empty link

- Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French). `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

⚠ cleveref page numbers

- cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to "for".

  Ex:
  ```
  \cpageref{tab:first,tab:second}
  ```
  in html becomes:
  "pages **for** table 4.1 and **for** table 4.2"

  See `\cpagerefFor` at page 542 to redefine the message which is printed for page number references.

BibTeX errors with `\etalchar`: See section 8.6.9.

Malformed URLs: Do not use the `%` character between arguments of `\hyperref`, etc., as this character is among those which is neutralized for inclusion in HTML URLs.

Em-dashes or En-dashes in listing captions and titles:

Use XeLaTeX or LuaLaTeX.

Floats out of sequence:

Mixed "Here" and floating: Floats [H]ere and regular floats may become out of order. `\clearpage` if necessary.

Caption setup: With `\captionsetup` set the positions for the captions `above` or `below` to match their use in the source code.

Images are appearing in strange places:

- Enter **`lwarpmk limages`** to refresh the `lateximage` images.

SVG images:

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk limages`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[15] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ HTML instead of images

If HTML appears where an SVG image should be, recompile the document one

[15] This becomes important when dealing with a document containing thousands of images.

more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect SVG images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

⚠ Lots of files!

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 5.5 to use MathJax instead.

Plain-looking document:

- The document's CSS stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFilename` statements point to a valid CSS file.

⚠ HTML corrupted

Broken fragments of HTML:

- Check the PDF file used to create HTML to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

Changes do not seem to be taking effect:

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the HTML settings at section 7.6.
- Verify that the proper CSS is actually being used.
- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

Un-matched conditional compiles:

- Verify the proper `begin`/`end` of `warpprint`, `warpHTML`, and `warpall` environments.

13.2.1 Debug tracing output

`\tracinglwarp`

When `\tracinglwarp` is used, lwarp will add extra tracing messages to the `.log` file. The last several messages may help track down errors.

Place `\tracinglwarp` just after `\usepackage{lwarp}` to activate tracing.

13.3 Compiling the `lwarp.dtx` file

`lwarp_tutorial.tex`: Copy or link `lwarp_tutorial.txt` from the TDS doc directory to the `source` directory, or wherever you wish to compile the documentation. This file is included verbatim in the documentation, but is in the `doc` directory so that it may be found by *texdoc* and copied by the user.

Illogical error messages caused by an out-of-sync `lwarp.sty` file:

1. Delete the `lwarp.sty` file.
2. Enter **`pdflatex lwarp.ins`** to generate a new `lwarp.sty` file.
3. Enter **`pdflatex lwarp.dtx`** to recompile the `lwarp.pdf` documentation.

Un-nested environments:

Be sure to properly nest:

- `\begin{macrocode}` and `\end{macrocode}`
- `\begin{macro}` and `\end{macro}`
- `\begin{environment}` and `\end{environment}`

14 Trademarks

- TEX is a trademark of American Mathematical Society.
- ADOBE® and ADOBE *Framemaker*® are either registered trademarks or trademarks of ADOBE SYSTEMS INCORPORATED in the United States and/or other countries.
- LINUX® is the registered trademark of Linus Torvalds in the U.S. and other countries.
- MAC OS® is a trademark of APPLE INC.
- MADCAP FLARE™ is the property of MADCAP SOFTWARE, INC.
- MATHJAX is copyright 2009 and later. The MATHJAX CONSORTIUM is a joint venture of the AMERICAN MATHEMATICAL SOCIETY (AMS) and the SOCIETY FOR INDUSTRIAL AND APPLIED MATHEMATICS (SIAM) to advance mathematical and scientific content on the web.
- MICROSOFT®, ENCARTA, MSN, and WINDOWS® are either registered trademarks or trademarks of MICROSOFT CORPORATION in the United States and/or other countries.
- UNIX® is a registered trademark of THE OPEN GROUP.
- YOUTUBE™ is trademark of GOOGLE LLC.

File 1 **lwarp.sty**

15 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of ~~crude hacks~~ clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include xcolor with its color models and conversion to HTML color output, and siunitx which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by *pdftotext*.

Packages were emulated where their primary purpose was visual formatting which is not relevent to HTML output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in HTML output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a `latexmage` environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

Table 9: Section depths and HTML headings

Section	LaTeX depth	HTML headings *
Title of the entire website		`<h1>`
(none)	-5	new for this package
book	-2	`<div class = "book">`
part	-1	`<h2>`
chapter	0	`<h3>`
section	1	`<h4>`
subsection	2	`<h5>`
subsubsection	3	`<h6>`
paragraph	4	`<span class = "paragraph">`
subparagraph	5	`<span class = "subparagraph">`
listitem	7	new for this package, used for list items

* If `FormatWP` is true, section headings may be adjusted, depending on `WPTitleHeading`. See table 8 on page 172.

16 Section depths and HTML headings

Stacks are created to track depth inside the LaTeX document structure. This depth is translated to HTML headings as shown in table 9. "Depth" here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the LaTeX document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Support for the memoir package will require the addition of a book level, which may push the HTML headings down a step, and also cause `subsubsection` to become a `<div>` due to a limit of six HTML headings.

It is possible to use HTML5 `<section>` and `<h1>` for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the CSS to remain fixed as well.

17 Source code

This is where the documented source code for lwarp begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the lwarp package.

line numbers — The small numbers at the left end of a line refer to line numbers in the `lwarp.sty` file.

subjects — Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph.

objects — Black-colored tags in the left marign are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are command macros. Each of these also appears in the index as individual entries, and are also listed together under “files”, “packages”, “environments”, “booleans”, and “counters”.

index entries

⚠ warnings — Special warnings are marked with a warning icon.

for HTML output:
for PRINT output:
for HTML & PRINT: — Green-colored tags in the left margin show which sections of source code apply to the generation of HTML, print, or both forms of output.

— lwarp source code begins on the following page —

18 Detecting the TEX engine — *pdflatex*, *lualatex*, *xelatex*

See: http://tex.stackexchange.com/a/47579.

Detects XƎTEX and LuaLATEX:

```
\RequirePackage{iftex}
\newif\ifxetexorluatex
\ifXeTeX
    \xetexorluatextrue
\else
    \ifLuaTeX
        \xetexorluatextrue
    \else
        \xetexorluatexfalse
    \fi
\fi

\ifLuaTeX
\RequirePackage{luatex85}% until the geometry package is updated
\fi

\RequirePackage{ifpdf}


\RequirePackage{ifptex}
```

19 Early package requirements

Pkg etoolbox Provides \ifbool and other functions.

Pkg xpatch Patches macros with optional arguments.

```
\RequirePackage{etoolbox}[2011/01/03]% v2.6 for \BeforeBeginEnvironment, etc.
\RequirePackage{xpatch}
```

Pkg ifplatform Provides \ifwindows to try to automatically detect WINDOWS OS.

```
\RequirePackage{ifplatform}% sense op-system platform
```

Pkg letltxmacro

```
\RequirePackage{letltxmacro}
```

20 Package load order

Several packages must never be used with lwarp, others should only be loaded before lwarp, and others should only be loaded after. The lwarp core checks most of these

cases. In some lwarp-* packages, \LWR@loadbefore is used to trigger an error if they are loaded after lwarp, while additional code provides necessary patches for when they are loaded before.

Packages which must be loaded after lwarp are enfoced by a large number of \LWR@loadafter statements, below. Some packages are emulated by memoir, and so these are tested by \LWR@notmemoirloadafter, which does not cause an error if memoir is used.

\LWR@checkloadfilename is used to check each filename to see if it must never be loaded, or must always be loaded before lwarp.

20.1 Tests of package load order

\LWR@loadafter {⟨*packagename*⟩} Error if this package was loaded before lwarp.

```
\newcommand*{\LWR@loadafter}[1]{%
\@ifpackageloaded{#1}
{
    \PackageError{lwarp}
        {%
            Package #1,\MessageBreak
            or one which uses #1,\MessageBreak
            must be loaded after lwarp
        }
        {Move \detokenize{\usepackage}{#1} after
        \detokenize{\usepackage}{lwarp}.\MessageBreak
        Package #1 may also be loaded by something else,\MessageBreak
        which must also be moved after lwarp.}
}
{}
}
```

\LWR@notmemoirloadafter {⟨*packagename*⟩} Error if not memoir class and this package was loaded before lwarp.

memoir emulates many packages, and pretends that they have already been loaded.

```
\@ifclassloaded{memoir}
{\newcommand*{\LWR@notmemoirloadafter}[1]{}}
{\LetLtxMacro\LWR@notmemoirloadafter\LWR@loadafter}
```

\LWR@notltjloadafter {⟨*packagename*⟩} Error if not a ltjs* class and this package was loaded before lwarp.

```
\LetLtxMacro\LWR@notltjloadafter\LWR@loadafter

\@ifclassloaded{ltjarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

```
\@ifclassloaded{ltjsreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjspf}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjskiyou}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

`\LWR@loadbefore` {⟨*packagename*⟩} Error if this package is loaded after lwarp.

```
\newcommand*{\LWR@loadbefore}[1]{%
\@ifpackageloaded{#1}
{}
{
\PackageError{lwarp}
{Package #1 must be loaded before lwarp}
{Move \detokenize{\usepackage}{#1} before \detokenize{\usepackage}{lwarp}.}
}
}
```

`\LWR@checkloadbefore` {⟨*thispackagename*⟩} {⟨*packagename*⟩}

If package names match, error if it is loaded after lwarp.

```
\newcommand*{\LWR@checkloadbefore}[2]{%
    \edef\LWR@tempone{#1}%
    \ifdefstring{\LWR@tempone}{#2}{%
        \LWR@loadbefore{#1}%
    }{}%
}
```

`\LWR@loadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

The first packages is not supported, so tell the user to use the second instead.

```
\newcommand*{\LWR@loadnever}[2]{%
\PackageError{lwarp}
{%
    Package #1 is not supported\MessageBreak
    by lwarp's HTML conversion.\MessageBreak
    Package(s) #2 may be useful instead
}
{%
    Package #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another package.\MessageBreak
    For a possible alternative, see package(s) #2.
}
}
```

`\LWR@checkloadnever` {⟨*thispackagename*⟩} {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

If this package name is the bad packagename, suggest the replacements instead.

```
\newcommand*{\LWR@checkloadnever}[3]{%
    \edef\LWR@tempone{#1}%
    \ifdefstring{\LWR@tempone}{#2}{%
        \LWR@loadnever{#2}{#3}%
    }{}%
}
```

`\LWR@earlyloadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgname*⟩}

The first package is not supported, so tell the user to use the second instead. This version checks immediately for packages which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyloadnever}[2]{%
\@ifpackageloaded{#1}{%
\PackageError{lwarp}
{%
    Package #1 is not supported\MessageBreak
    by lwarp's HTML conversion.\MessageBreak
    Package(s) #2 may be useful instead
}
{%
    Package #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another package.\MessageBreak
    For a possible alternative, see package(s) #2.
}
}{}%
}
```

`\LWR@earlyclassloadnever` {⟨*badclassname*⟩} {⟨*replacementclassname*⟩}

The first class is not supported, so tell the user to use the second instead. This version checks immediately for classes which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyclassloadnever}[2]{%
\@ifclassloaded{#1}{%
\PackageError{lwarp}
{%
    Class #1 is not supported\MessageBreak
    by lwarp's HTML conversion.\MessageBreak
    Class(es) #2 may be useful instead
}
{%
    Class #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another class.\MessageBreak
    For a possible alternative, see class(es) #2.
}
}{}%
}
```

20.2 Error for disallowed packages and classes loaded before lwarp

```
\LWR@earlyclassloadnever{jarticle}{ujarticle}
```

```
\LWR@earlyclassloadnever{jbook}{ujbook}
\LWR@earlyclassloadnever{jreport}{ujreport}
\LWR@earlyclassloadnever{tarticle}{utarticle}
\LWR@earlyclassloadnever{tbook}{utbook}
\LWR@earlyclassloadnever{treport}{utreport}
\LWR@earlyloadnever{ae}{cm-super, lmodern}
\LWR@earlyloadnever{aecompl}{cm-super, lmodern}
\LWR@earlyloadnever{aecc}{cm-super, lmodern}
\LWR@earlyloadnever{alg}{algorithm2e, algorithmicx}
\LWR@earlyloadnever{algorithmic}{algorithm2e, algorithmicx}
\LWR@earlyloadnever{boxedminipage}{boxedminipage2e}
\LWR@earlyloadnever{caption2}{caption}
% \LWR@earlyloadnever{ccaption}{caption}% might be preloaded by memoir
```

The older CJK and CJKutf8 only work with xeCJK:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@earlyloadnever{CJK}{ctex, xeCJK}
    \LWR@earlyloadnever{CJKutf8}{ctex, xeCJK}
}
```

bxcjkatype is based on CJK:

```
\LWR@earlyloadnever{bxcjkjatype}{upLaTeX, bxjsarticle, ujarticle, utarticle}
```

hangul is not in TeXLive, and is not tested:

```
\LWR@earlyloadnever{hangul}{kotex, xetexko, luatexko}
```

Others:

```
\LWR@earlyloadnever{colortab}{colortbl}
\LWR@earlyloadnever{epsf}{graphicx}
\LWR@earlyloadnever{fancyheadings}{fancyhdr}
\LWR@earlyloadnever{fncylab}{cleveref}
\LWR@earlyloadnever{glossary}{glossaries}
\LWR@earlyloadnever{hyper}{hyperref}
\LWR@earlyloadnever{pdfcprot}{microtype}
\LWR@earlyloadnever{picinpar}{floatflt, wrapfig}
\LWR@earlyloadnever{picins}{floatflt, wrapfig}
\LWR@earlyloadnever{sistyle}{siunitx}
\LWR@earlyloadnever{t1enc}{fontenc, inputenc, inputenx}
\LWR@earlyloadnever{ucs}{inputenc, inputencx}
\LWR@earlyloadnever{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

20.3 Enforcing package loading after lwarp

Packages which should only be loaded after lwarp are tested here to trip an error of they have already been loaded.

The following packages must be loaded after lwarp:

```
\LWR@loadafter{2in1}
\LWR@loadafter{2up}
\LWR@loadafter{a4}
```

```
\LWR@loadafter{a4wide}
\LWR@loadafter{a5comb}
\LWR@notmemoirloadafter{abstract}
\LWR@loadafter{academicons}
\LWR@loadafter{accsupp}
\LWR@loadafter{acro}
\LWR@loadafter{acronym}
\LWR@loadafter{adjmulticol}
\LWR@loadafter{addlines}
\LWR@loadafter{ae}
\LWR@loadafter{aecc}
\LWR@loadafter{afterpage}
\LWR@loadafter{algorithm2e}
\LWR@loadafter{algorithmicx}
\LWR@loadafter{alltt}
\LWR@loadafter{amsmath}
\LWR@loadafter{amsthm}
\LWR@loadafter{anonchap}
\LWR@loadafter{anysize}
\LWR@notmemoirloadafter{appendix}
\LWR@loadafter{ar}
\LWR@loadafter{arabicfront}
\LWR@notmemoirloadafter{array}
\LWR@loadafter{arydshln}
\LWR@loadafter{asymptote}
% \LWR@loadafter{atbegshi}% used by morewrites
\LWR@loadafter{attachfile}
\LWR@loadafter{attachfile2}
\LWR@loadafter{authblk}
\LWR@loadafter{autonum}
\LWR@loadafter{axessibility}
\LWR@loadafter{axodraw2}
\LWR@loadafter{backnaur}
\LWR@loadafter{backref}
\LWR@loadafter{balance}
\LWR@loadafter{bbding}
\LWR@loadafter{bigdelim}
\LWR@loadafter{bigfoot}
\LWR@loadafter{bigstrut}
\LWR@loadafter{bitpattern}
\LWR@loadafter{blowup}
\LWR@loadafter{booklet}
\LWR@loadafter{bookmark}
\LWR@notmemoirloadafter{booktabs}
\LWR@loadafter{bophook}
\LWR@loadafter{bounddvi}
\LWR@loadafter{boxedminipage}
\LWR@loadafter{boxedminipage2e}
\LWR@loadafter{breakurl}
\LWR@loadafter{breqn}
\LWR@loadafter{bsheaders}
\LWR@loadafter{bxpapersize}
\LWR@loadafter{bytefield}
\LWR@loadafter{cancel}
\LWR@loadafter{canoniclayout}
```

```
\LWR@loadafter{caption}
\LWR@loadafter{caption2}
\LWR@loadafter{cases}
% \LWR@loadafter{ccaption}% may be preloaded by memoir
\LWR@loadafter{changebar}
\LWR@loadafter{changelayout}
\LWR@notmemoirloadafter{changepage}
\LWR@loadafter{changes}
\LWR@loadafter{chappg}
\LWR@loadafter{chapterbib}
\LWR@loadafter{chemfig}
\LWR@loadafter{chemformula}
\LWR@loadafter{chemgreek}
\LWR@loadafter{chemmacros}
\LWR@loadafter{chemnum}
\LWR@loadafter{chkfloat}
\LWR@notmemoirloadafter{chngpage}
\LWR@loadafter{cite}
\LWR@loadafter{cmdtrack}
\LWR@loadafter{color}
\LWR@loadafter{colortbl}
\LWR@loadafter{continue}
\LWR@loadafter{copyrightbox}
\LWR@notmemoirloadafter{crop}
% ctex must be loaded before lwarp
\LWR@loadafter{ctable}
\LWR@loadafter{cuted}
\LWR@loadafter{cutwin}
\LWR@loadafter{dblfloatfix}
\LWR@loadafter{dblfnote}
\LWR@notmemoirloadafter{dcolumn}
\LWR@loadafter{diagbox}
\LWR@loadafter{dingbat}
\LWR@loadafter{dprogress}
\LWR@loadafter{draftcopy}
\LWR@loadafter{draftfigure}
\LWR@loadafter{draftwatermark}
\LWR@loadafter{easy-todo}
\LWR@loadafter{ebook}
\LWR@loadafter{ed}
\LWR@loadafter{ellipsis}
\LWR@loadafter{embrac}
\LWR@loadafter{emptypage}
\LWR@loadafter{endfloat}
\LWR@loadafter{endheads}
\LWR@loadafter{endnotes}
\LWR@notmemoirloadafter{enumerate}
\LWR@loadafter{enumitem}
\LWR@notmemoirloadafter{epigraph}
\LWR@loadafter{epsfig}
\LWR@loadafter{epstopdf}
\LWR@loadafter{epstopdf-base}
\LWR@loadafter{eqlist}
\LWR@loadafter{eqparbox}
\LWR@loadafter{errata}
```

```
\LWR@loadafter{eso-pic}
\LWR@loadafter{eurosym}
\LWR@loadafter{everypage}
\LWR@loadafter{everyshi}
\LWR@loadafter{extramarks}
\LWR@loadafter{fancybox}
\LWR@loadafter{fancyhdr}
\LWR@loadafter{fancyheadings}
\LWR@loadafter{fancyref}
\LWR@loadafter{fancytabs}
\LWR@loadafter{fancyvrb}
\LWR@loadafter{figcaps}
\LWR@loadafter{figsize}
\LWR@loadafter{fitbox}
\LWR@loadafter{fix2col}
\LWR@loadafter{fixme}
\LWR@loadafter{fixmetodonotes}
\LWR@loadafter{flafter}
\LWR@loadafter{flippdf}
\LWR@loadafter{float}
\LWR@loadafter{floatflt}
\LWR@loadafter{floatpag}
\LWR@loadafter{floatrow}
\LWR@loadafter{fltrace}
\LWR@loadafter{flushend}
\LWR@loadafter{fnbreak}
\LWR@loadafter{fncychap}
\LWR@loadafter{fnlineno}
\LWR@loadafter{fnpara}
\LWR@loadafter{fnpos}
\LWR@loadafter{fontawesome}
\LWR@loadafter{fontawesome5}
% fontenc must be loaded before lwarp
% fontspec must be loaded before lwarp
\LWR@loadafter{footmisc}
\LWR@loadafter{footnote}
\LWR@loadafter{footnotebackref}
\LWR@loadafter{footnotehyper}
\LWR@loadafter{footnoterange}
\LWR@loadafter{footnpag}
\LWR@loadafter{foreign}
\LWR@loadafter{forest}
\LWR@loadafter{framed}
\LWR@loadafter{ftcap}
\LWR@loadafter{ftnright}
\LWR@loadafter{fullminipage}
\LWR@loadafter{fullpage}
\LWR@loadafter{fullwidth}
\LWR@loadafter{fwlw}
\LWR@loadafter{gentombow}
% geometry is always loaded by lwarp, and lwarp-geometry is AtBeginDocument
\LWR@loadafter{gmeometric}
\LWR@loadafter{glossaries}
% \LWR@loadafter{graphics}% pre-loaded by xunicode
% \LWR@loadafter{graphicx}% pre-loaded by xunicode
```

```
\LWR@loadafter{gloss}
\LWR@loadafter{glossary}
\LWR@loadafter{grffile}
\LWR@loadafter{grid}
\LWR@loadafter{grid-system}
\LWR@loadafter{gridset}
\LWR@loadafter{hang}
\LWR@loadafter{hanging}
\LWR@loadafter{hypbmsec}
\LWR@loadafter{hypcap}
\LWR@loadafter{hypdestopt}
\LWR@loadafter{hypernat}
\LWR@loadafter{hyperref}
\LWR@loadafter{hyperxmp}
\LWR@loadafter{hyphenat}
\LWR@loadafter{idxlayout}
\LWR@loadafter{ifoddpage}
\LWR@loadafter{imakeidx}
\LWR@notmemoirloadafter{index}
% inputenc must be loaded before lwarp
% inputenx must be loaded before lwarp
% inputtrc may be loaded before lwarp
\LWR@loadafter{intopdf}
\LWR@loadafter{karnaugh-map}
\LWR@loadafter{keyfloat}
\LWR@loadafter{layaureo}
\LWR@loadafter{layout}
\LWR@loadafter{layouts}
\LWR@loadafter{leading}
\LWR@loadafter{letterspace}
\LWR@loadafter{lettrine}
\LWR@loadafter{lineno}
\LWR@loadafter{lips}
\LWR@loadafter{listings}
\LWR@loadafter{listliketab}
\LWR@loadafter{longtable}
\LWR@loadafter{lscape}
\LWR@loadafter{ltablex}
\LWR@loadafter{ltcaption}
\LWR@loadafter{ltxgrid}
\LWR@loadafter{ltxtable}
\LWR@loadafter{lua-check-hyphen}
\LWR@loadafter{lua-visual-debug}
\LWR@loadafter{luacolor}
\LWR@loadafter{luatodonotes}
\LWR@loadafter{lyluatex}
\LWR@loadafter{magaz}
\LWR@notmemoirloadafter{makeidx}
\LWR@loadafter{manyfoot}
\LWR@loadafter{marginfit}
\LWR@loadafter{marginfix}
\LWR@loadafter{marginnote}
\LWR@loadafter{marvosym}
\LWR@loadafter{mathtools}
\LWR@loadafter{mcaption}
```

```
\LWR@loadafter{mdframed}
\LWR@loadafter{media9}
\LWR@loadafter{memhfixc}
\LWR@loadafter{metalogo}
\LWR@loadafter{metalogox}
\LWR@loadafter{mhchem}
\LWR@loadafter{microtype}
\LWR@loadafter{midfloat}
\LWR@loadafter{midpage}
\LWR@loadafter{minibox}
\LWR@loadafter{minitoc}
% morefloats must be allowed early for print mode
\LWR@notmemoirloadafter{moreverb}
% morewrites must be loaded before lwarp
\LWR@notmemoirloadafter{movie15}
\LWR@notmemoirloadafter{mparhack}
\LWR@loadafter{multicap}
%\LWR@loadafter{multicol}% loaded by ltxdoc
\LWR@loadafter{multicolrule}
\LWR@loadafter{multimedia}
\LWR@loadafter{multirow}
\LWR@loadafter{multitoc}
\LWR@loadafter{musicography}
\LWR@loadafter{nameauth}
\LWR@loadafter{nameref}
\LWR@loadafter{natbib}
\LWR@notmemoirloadafter{nccfancyhdr}
\LWR@notmemoirloadafter{needspace}
% newclude must be loaded before lwarp
\LWR@loadafter{newtxmath}
% newunicodechar must be loaded before lwarp
\LWR@notmemoirloadafter{nextpage}
\LWR@loadafter{nicefrac}
\LWR@loadafter{niceframe}
\LWR@loadafter{nomencl}
\LWR@loadafter{nonfloat}
\LWR@loadafter{nonumonpart}
\LWR@loadafter{nopageno}
\LWR@loadafter{notes}
\LWR@loadafter{notespages}
\LWR@loadafter{nowidow}
\LWR@loadafter{ntheorem}
\LWR@loadafter{octave}
\LWR@loadafter{overpic}
\LWR@loadafter{pagegrid}
\LWR@notmemoirloadafter{pagenote}
\LWR@loadafter{pagesel}
\LWR@loadafter{paralist}
\LWR@loadafter{parnotes}
\LWR@notmemoirloadafter{parskip}
\LWR@loadafter{pbox}
\LWR@loadafter{pdfcomment}
\LWR@loadafter{pdfcrypt}
\LWR@loadafter{pdflscape}
\LWR@loadafter{pdfmarginpar}
```

```
\LWR@loadafter{pdfpages}
\LWR@loadafter{pdfprivacy}
\LWR@loadafter{pdfrender}
\LWR@loadafter{pdfsync}
\LWR@loadafter{pdftricks}
\LWR@loadafter{pdfx}
\LWR@loadafter{perpage}
\LWR@loadafter{pfnote}
\LWR@loadafter{phfqit}
\LWR@loadafter{pifont}
\LWR@loadafter{placeins}
\LWR@loadafter{plarray}
\LWR@loadafter{plarydshln}
\LWR@loadafter{plextarray}
\LWR@loadafter{plextarydshln}
\LWR@loadafter{plcolortbl}
\LWR@loadafter{plextdelarray}
\LWR@loadafter{prelim2e}
\LWR@loadafter{prettyref}
\LWR@loadafter{preview}
\LWR@loadafter{psfrag}
\LWR@loadafter{psfragx}
\LWR@loadafter{pst-eps}
\LWR@loadafter{pstool}
\LWR@loadafter{pstricks}
% \LWR@loadafter{pxatbegshi}% may be used by morewrites
\LWR@loadafter{pxeveryshi}
\LWR@loadafter{pxftnright}
\LWR@loadafter{pxjahyper}
\LWR@loadafter{quotchap}
\LWR@loadafter{quoting}
\LWR@loadafter{ragged2e}
\LWR@loadafter{realscripts}
\LWR@loadafter{refcheck}
\LWR@loadafter{register}
\LWR@loadafter{relsize}
\LWR@loadafter{repeatindex}
\LWR@loadafter{resizegather}
\LWR@loadafter{rmpage}
\LWR@loadafter{romanbar}
\LWR@loadafter{romanbarpagenumber}
\LWR@loadafter{rotating}
\LWR@loadafter{rotfloat}
\LWR@loadafter{rviewport}
\LWR@loadafter{savetrees}
% scalefnt is loaded by babel-french
\LWR@loadafter{schemata}
\LWR@loadafter{scrextend}
\LWR@loadafter{scrhack}
\LWR@loadafter{scrlayer}
\LWR@loadafter{scrlayer-notecolumn}
\LWR@loadafter{scrlayer-scrpage}
\LWR@loadafter{scrpage2}
\LWR@loadafter{section}
\LWR@loadafter{sectionbreak}
```

```
\LWR@loadafter{sectsty}
\LWR@loadafter{semantic-markup}
\LWR@notmemoirloadafter{setspace}
\LWR@loadafter{shadow}
\LWR@loadafter{shapepar}
\LWR@notmemoirloadafter{showidx}
\LWR@loadafter{showkeys}
\LWR@loadafter{showtags}
\LWR@loadafter{sidecap}
\LWR@loadafter{sidenotes}
\LWR@loadafter{SIunits}
\LWR@loadafter{siunitx}
\LWR@loadafter{slantsc}
\LWR@loadafter{soul}
\LWR@loadafter{soulpos}
\LWR@loadafter{soulutf8}
\LWR@loadafter{splitidx}
\LWR@loadafter{srcltx}
\LWR@loadafter{srctex}
\LWR@loadafter{stabular}
\LWR@loadafter{stackengine}
\LWR@notltjloadafter{stfloats}
\LWR@loadafter{struktex}
\LWR@loadafter{subcaption}
\LWR@loadafter{subfig}
\LWR@loadafter{subfigure}
\LWR@loadafter{supertabular}
\LWR@loadafter{t1inc}
\LWR@loadafter{tabfigures}
\LWR@loadafter{tabls}
\LWR@loadafter{tablefootnote}
\LWR@notmemoirloadafter{tabularx}
\LWR@loadafter{tabulary}
\LWR@loadafter{tascmac}
\LWR@loadafter{textarea}
% \LWR@loadafter{textcomp}% maybe before lwarp with font packages
\LWR@loadafter{textfit}
\LWR@loadafter{textpos}
\LWR@loadafter{theorem}
\LWR@loadafter{thinsp}
\LWR@loadafter{threadcol}
\LWR@loadafter{threeparttable}
\LWR@loadafter{threeparttablex}
\LWR@loadafter{thumb}
\LWR@loadafter{thumbs}
\LWR@loadafter{tikz}
\LWR@loadafter{titleps}
\LWR@loadafter{titlesec}
\LWR@loadafter{titletoc}
\LWR@notmemoirloadafter{titling}
% \LWR@loadafter{tocbasic}% preloaded by koma-script classes
\LWR@notmemoirloadafter{tocbibind}
\LWR@loadafter{tocdata}
\LWR@loadafter{tocenter}
\LWR@notmemoirloadafter{tocloft}
```

```
\LWR@loadafter{tocstyle}
\LWR@loadafter{todo}
\LWR@loadafter{todonotes}
\LWR@loadafter{topcapt}
\LWR@loadafter{tram}
\LWR@loadafter{transparent}
\LWR@loadafter{trimclip}
\LWR@loadafter{trivfloat}
\LWR@loadafter{truncate}
\LWR@loadafter{turnthepage}
\LWR@loadafter{twoup}

% \LWR@loadafter{typearea}% preloaded by koma-script classes
\LWR@loadafter{typicons}
% \LWR@loadafter{ulem}% preloaded by ctexart and related classes
\LWR@loadafter{umoline}
\LWR@loadafter{underscore}
\LWR@loadafter{units}
\LWR@loadafter{unitsdef}
\LWR@loadafter{upref}
\LWR@loadafter{url}
\LWR@loadafter{uspace}
\LWR@loadafter{varioref}% no lwarp package provided
\LWR@notmemoirloadafter{verse}
\LWR@loadafter{versonotes}
\LWR@loadafter{vertbars}
\LWR@loadafter{vmargin}
\LWR@loadafter{vowel}
\LWR@loadafter{vpe}
\LWR@loadafter{vwcol}
\LWR@loadafter{wallpaper}
\LWR@loadafter{watermark}
\LWR@loadafter{widows-and-orphans}
\LWR@loadafter{wrapfig}
\LWR@loadafter{xbmks}
\LWR@loadafter{xcolor}
\LWR@loadafter{xechangebar}
\LWR@loadafter{xellipsis}
% xetexko-vertical must be loaded before lwarp
\LWR@loadafter{xfakebold}
\LWR@loadafter{xfrac}
\LWR@loadafter{xltabular}
\LWR@loadafter{xltxtra}
\LWR@loadafter{xmpincl}
\LWR@loadafter{xpiano}
\LWR@loadafter{xpinyin}
\LWR@loadafter{xr}
\LWR@loadafter{xr-hyper}
\LWR@loadafter{xtab}
% xunicode must be loaded before lwarp
\LWR@loadafter{xurl}
\LWR@loadafter{xy}
\LWR@loadafter{zwpagelayout}
```

21 MD5 hashing

The MD5 hash is used for `lateximage` filenames for SVG math.

```
\newcommand{\LWR@mdfive}[1]{%
\PackageError{lwarp}
{No MD5 macro was found}
{Lwarp must find the macros pdfmdfivesum or mdfivesum.}
}
```

The default for pdfLaTeX, DVILaTeX, upLaTeX, etc:

```
\let\LWR@mdfive\pdfmdfivesum
```

For LuaLaTeX:

```
\ifLuaTeX
\RequirePackage{pdftexcmds}
\let\LWR@mdfive\pdf@mdfivesum
\fi
```

For XeLaTeX:

```
\ifXeTeX
\@ifundefined{pdffivesum}{}
    {\let\LWR@mdfive\pdfmdfivesum}
\@ifundefined{mdfivesum}{}
    {\let\LWR@mdfive\mdfivesum}
\fi
```

22 pdfLaTeX T1 and UTF-8 encoding

When using pdfLaTeX, lwarp requires T1 encoding, and recommends UTF-8 encoding.

If some other input encoding is already defined, lwarp will try to use it instead, and hope for the best.

XeLaTeX and LuaLaTeX are both UTF-8 by nature.

`\LWR@pdfencoding` Sets `T1`, and also `utf8` if not already set.

```
\newcommand*{\LWR@pdfencoding}{%
    \RequirePackage[T1]{fontenc}

    \@ifpackageloaded{inputenc}{}{
        \@ifpackageloaded{inputenx}{}{
            \RequirePackage[utf8]{inputenc}
        }
    }
}
```

```
\ifPDFTeX% pdflatex or dvi latex
    \LWR@pdfencoding
\fi

\ifpTeX
    \LWR@pdfencoding
\fi
```

23 Unicode input characters

for HTML & PRINT:

If using *pdflatex*, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be `\texttimes`.

The first arguments of `\newunicodechar` below are text ligatures in the source code, even though they are not printed in the following listing.

```
\ifpTeX
\else
\RequirePackage{newunicodechar}

\newunicodechar{×}{\texttimes}

\ifPDFTeX% pdflatex or dvi latex
\newunicodechar{ff}{ff}% the first arguments are ligatures
\newunicodechar{fi}{fi}
\newunicodechar{fl}{fl}
\newunicodechar{ffi}{ffi}
\newunicodechar{ffl}{ffl}
\newunicodechar{–}{---}
\newunicodechar{-}{--}
\fi

\fi
```

24 Avoid a bitmapped font

If DVI or PDF LaTeX, and if the default Computer Modern is the selected font family, ensure that cm-super or lmodern is used to provide a vector font.

```
\ifxetexorluatex
\else
    \ifdefstring{\f@family}{cmr}{
        \IfFileExists{type1ec.sty}% found in cm-super
        {}
        {% cm-super not installed
            \IfFileExists{lmodern.sty}{
                \PackageInfo{lwarp}{cm-super not installed, loading lmodern}
                \RequirePackage{lmodern}
```

```
            }{
                \PackageError{lwarp}
                {%
                    Lwarp requires a vector font.\MessageBreak
                   Install and load cm-super, lmodern, or another\MessageBreak
                    Type-1 vector font before loading lwarp%
                }
                {%
                    Install cm-super or lmodern.\MessageBreak
                    If lmodern, load it before lwarp:\MessageBreak
                        \space\space\protect\usepackage{lmodern}\MessageBreak
                        \space\space\protect\usepackage{lwarp}%
                }
            }
        }% cm-super not installed
    }{}% f@family
\fi
```

25 Upright quotes

In PDFTEX, preserve upright quotes in verbatim text. upquote also loads textcomp.

```
\ifPDFTeX
\RequirePackage{upquote}
\fi

\ifpTeX
    \RequirePackage{upquote}
\fi
```

26 Miscellaneous tools

26.1 Lengths and units

\LWR@providelength {⟨\lengthname⟩} Provides the length if it isn't defined yet.

Used to provide source compatibility for lengths which will be ignored, but might or might not be already provided by other packages.

```
\newcommand*\LWR@providelength[1]{%
    \ifdeflength{#1}{}{\newlength{#1}}%
}
```

\LWR@convertto {⟨*dest unit*⟩} {⟨*length*⟩}

Prints a length in the given units, without printing the unit itself.

```
\newcommand*{\LWR@convertto}[2]{\strip@pt\dimexpr #2*65536/\number\dimexpr 1#1}
```

\LWR@printpercentlength {⟨*smaller*⟩} {⟨*larger*⟩}

Prints a percent ratio of the two lengths.

```
\newcommand*{\LWR@printpercentlength}[2]{%
    \setcounter{LWR@tempcountone}{100*\ratio{#1}{#2}}%
    \arabic{LWR@tempcountone}%
}
```

26.2 Patching

\LWR@patcherror {⟨*packagename*⟩} {⟨*macroname*⟩}

Prints an error if could not patch a macro.

```
\newcommand*{\LWR@patcherror}[2]{%
\PackageError{lwarp}
{Unable to patch package #1, macro #2}
{Please contact the author of the lwarp package.}
}
```

26.3 Chinese text isolation

\LWR@isolate {⟨*text*⟩} Isolates Chinese characters from the surrounding text. This is required to avoid extra spaces on either side of the Chinese characters, especially when written to a file.

```
\newcommand{\LWR@isolate}[1]{#1}%

\@ifpackageloaded{ctexpatch}{
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
}{}

\@ifpackageloaded{xeCJK}{
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
}{}
```

26.4 Inserting vertical space

\LWR@forceemptyline Extra vertical space in the HTML output. Use after \LWR@stoppars.

```
\newcommand*{\LWR@forceemptyline}{%
    \LWR@origrule{0pt}{1\baselineskip}%
    \LWR@orignewline%
}
```

26.5 Argument selection

\LWR@firstoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@secondoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@thirdoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@fourthoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

Expands to the nth of the four arguments. Used for extra cross referencing.

```
\long\def\LWR@firstoffour#1#2#3#4{#1}
\long\def\LWR@secondoffour#1#2#3#4{#2}
\long\def\LWR@thirdoffour#1#2#3#4{#3}
\long\def\LWR@fourthoffour#1#2#3#4{#4}
```

26.6 Global boxes

\LWR@gsavebox {⟨*macroname*⟩} {⟨*contents*⟩}

From https://tex.stackexchange.com/questions/288702/savebox-forgets-its-content-across-columns-inside-align

```
\DeclareRobustCommand\LWR@gsavebox[1]{%
  \@ifnextchar(%)
    {\LWR@@gsavepicbox#1}{\@ifnextchar[{\LWR@@gsavebox#1}{\LWR@gsbox#1}}}%
\long\def\LWR@gsbox#1#2{\global\setbox#1\hbox{%
  \color@setgroup#2\color@endgroup}}
\def\LWR@@gsavebox#1[#2]{%
  \@ifnextchar [{\LWR@@igsavebox#1[#2]}{\LWR@@igsavebox#1[#2][c]}}
\long\def\LWR@@igsavebox#1[#2][#3]#4{%
  \LWR@gsbox#1{\@imakebox[#2][#3]{#4}}}
\def\LWR@@gsavepicbox#1(#2,#3){%
  \@ifnextchar[%]
    {\LWR@@igsavepicbox#1(#2,#3)}{\LWR@@igsavepicbox#1(#2,#3)[]}}
\long\def\LWR@@igsavepicbox#1(#2,#3)[#4]#5{%
  \LWR@gsbox#1{\@imakepicbox(#2,#3)[#4]{#5}}}
```

Env LWR@glrbox {⟨*macroname*⟩}

```
\def\LWR@glrbox#1{%
  \edef\reserved@a{%
    \endgroup
    \global\setbox#1\hbox{%
      \begingroup\aftergroup}%
        \def\noexpand\@currenvir{\@currenvir}%
        \def\noexpand\@currenvline{\on@line}}%
  \reserved@a
    \@endpefalse
```

```
727     \color@setgroup
728       \ignorespaces}
729 \let\LWR@endglrbox\LWR@endlrbox
```

27 Operating-System portability

Prog Unix
Prog Mac OS
Prog Linux
Prog MS-Windows
Prog Windows
Opt OSWindows

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.

If MS-WINDOWS is not correctly detected, use the lwarp option `OSWindows`.

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean `usingOSWindows` is set `true`. This boolean may be tested by the user for later use.

27.1 Literal characters

Literal characters to be used in `PrintLatexCmd` and `HTMLLatexCmd`. These are defined without `@` to easily allow their inclusion in the user's document.

The literal `%` character:

```
730 \let\LWRpercent\@percentchar
```

The literal `$` character:

```
731 \catcode`\$=12
732 \def\LWRdollar{$}
733 \catcode`\$=3
```

The literal `&` character:

```
734 \catcode`\&=12
735 \def\LWRamp{&}
736 \catcode`\&=4
```

The literal `\` character. The ampersand is temporarily set to the escape character during the definition of the backslash macro.

```
737 \catcode`\&=0
738 &catcode`&\=12
739 &def&LWRbackslash{\}
740 &catcode`&\=0
741 \catcode`\&=4
```

The literal `{` character. The ampersand is temporarily set to the begin group character during the definition of the leftbrace macro.

```
\catcode`\&=1
\catcode`\{=12
\def\LWRleftbrace&{}
\catcode`\{=1
\catcode`\&=4
```

The literal } character. The ampersand is temporarily set to the end group character during the definition of the leftbrace macro.

```
\catcode`\&=2
\catcode`\}=12
\def\LWRrightbrace{}&
\catcode`\}=2
\catcode`\&=4
```

The literal # character:

```
\catcode`\#=12
\def\LWRhash{#}
\catcode`\#=6
```

`\LWRopquote` The operating system's quote mark, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
\def\LWRopquote{'}
```

`\LWRopseq` The operating system's sequential execution command, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
\def\LWRopseq{\space\LWRamp\LWRamp\space\space}
```

27.2 Common portability code

Bool `usingOSWindows` Set if the `OSWindows` option is used, or if WINDOWS is automatically detected.

```
\newbool{usingOSWindows}
\boolfalse{usingOSWindows}
```

27.3 UNIX, LINUX, and MAC OS

`\OSPathSymbol` Symbol used to separate directories in a path.

```
\newcommand*{\OSPathSymbol}{/}
```

27.4 MS-WINDOWS

For MS-WINDOWS:

\LWR@setOSWindows Set defaults for the MS-WINDOWS operating system. lwarp attempts to auto-detect the operatings system, and the OSWindows option may also be used to force MS-WINDOWS compatibility.

```
\newcommand*{\LWR@setOSWindows}
{
\booltrue{usingOSWindows}
\renewcommand*{\OSPathSymbol}{\@backslashchar}
\def\LWRopquote{"}
\def\LWRopseq{\space\LWRamp\space\space}
}
```

Test for windows during compile. The user may also specify OSWindows package option in case this test fails.

```
\ifwindows
\LWR@setOSWindows
\fi
```

28 Package options

Pkg kvoptions Allows key/value package options.

```
\RequirePackage{kvoptions}
\SetupKeyvalOptions{family=LWR,prefix=LWR@}
```

\lwarpsetup A user interface to set the keys:

```
\newcommand{\lwarpsetup}[1]{\setkeys{LWR}{#1}}
```

Bool warpingprint
Bool warpingHTML
Bool mathjax
Bool LWR@origmathjax

Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax.

LWR@origmathjax remembers the original setting to be restored by \displaymathnormal.

```
\newbool{warpingprint}
\newbool{warpingHTML}
\newbool{mathjax}
\newbool{LWR@origmathjax}
```

defaults The default is print output, and SVG math if the user chose HTML output.

```
\booltrue{warpingprint}%
\boolfalse{warpingHTML}%
\boolfalse{mathjax}%
```

Opt warpprint If the warpprint option is given, boolean warpingprint is true and boolean warpingHTML

is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{warpprint}{%
\PackageInfo{lwarp}{Using option 'warpprint'}
\booltrue{warpingprint}%
\boolfalse{warpingHTML}%
}
```

Opt warpHTML Anything in the warpHTML environment will be generated for HTML output only.

Opt warpHTML If the warpHTML option is given, boolean warpingHTML is true and boolean warpingprint is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{warpHTML}{%
\PackageInfo{lwarp}{Using option 'warpHTML'}%
\booltrue{warpingHTML}%
\boolfalse{warpingprint}%
}
```

Opt mathsvg Option mathsvg selects SVG math display: If the mathsvg option is given, boolean mathjax is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{mathsvg}{%
\PackageInfo{lwarp}{Using option 'mathsvg'}
\boolfalse{mathjax}%
\boolfalse{LWR@origmathjax}%

}
```

Opt mathjax Option mathjax selects MATHJAX math display: If the mathjax option is given, boolean mathjax is true, may be used for \ifbool tests.

```
\DeclareVoidOption{mathjax}{%
\PackageInfo{lwarp}{Using option 'mathjax'}
\booltrue{mathjax}%
\booltrue{LWR@origmathjax}%

}
```

Opt BaseJobname Default: \jobname

Option BaseJobname sets the \BaseJobname for this document.

This is the \jobname of the printed version, even if currently compiling the HTML version. I.e. this is the \jobname without _html appended. This is used to set \HomeHTMLFilename if the user did not provide one.

```
\DeclareStringOption[\jobname]{BaseJobname}
```

Opt ImagesDirectory Default: \jobname-images

Option ImagesDirectory sets the name of the directory to use for the lateximage images.

```
\DeclareStringOption[\BaseJobname-images]{ImagesDirectory}
```

Opt ImagesName
Default: image-

Option ImagesName sets the prefix to use for the lateximage images.

```
\DeclareStringOption[image-]{ImagesName}
```

Opt makeindexStyle
Default: lwarp.ist

Selects a custom .ist file. A customized file should be based on lwarp.ist, and must retain the lines related to \hyperindexref.

```
\DeclareStringOption[lwarp.ist]{makeindexStyle}
```

Opt xindyStyle
Default: lwarp.xdy

Selects a custom .xdy file. A customized file should be based on lwarp.xdy, and must retain the line

```
(markup-locref :open "\hyperindexref{" :close "}")
```

```
\DeclareStringOption[lwarp.xdy]{xindyStyle}
```

Opt xindyLanguage
Default: english

Sets the xindy language to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index and glossary.

```
\DeclareStringOption[english]{xindyLanguage}
```

Opt xindyCodepage
Default: utf8

Sets the xindy codepage to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index.

```
\DeclareStringOption[utf8]{xindyCodepage}
```

Opt pdftotextEnc
Default: UTF-8

The option pdftotextEnc sets the encoding used by *pdftotext*. This is passed to *pdftotext* using its -enc option, and is used when converting LaTeX PDF output with HTML tags into a plain-text file with HTML tags.

```
\DeclareStringOption[UTF-8]{pdftotextEnc}
```

Opt lwarpmk

Tells lwarp to generate a local copy of *lwarpmk* called lwarpmk.lua. Useful for archiving for future use. This file may be made executable and acts just like *lwarpmk*.

If lwarpmk option, creates a local copy of lwarpmk.lua:

```
\newbool{LWR@creatinglwarpmk}
\boolfalse{LWR@creatinglwarpmk}

\DeclareVoidOption{lwarpmk}{
\PackageInfo{lwarp}{Using option 'lwarpmk'}
\booltrue{LWR@creatinglwarpmk}
}
```

Opt OSWindows

Tells lwarp to use MS-Windows compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated lwarpmk.conf file to find out whether the operating system was detected correctly.

```
\DeclareVoidOption{OSWindows}{
\PackageInfo{lwarp}{Using option 'OSWindows'}
\LWR@setOSWindows
}
```

Opt HomeHTMLFilename
Default: \BaseJobname

The filename of the homepage. The default is the jobname. This option is stored into \LWR@HomeHTMLFilename, and later transferred into \HomeHTMLFilename for internal use.

```
\DeclareStringOption[]{HomeHTMLFilename}
```

Opt HTMLFilename
Default: <empty>

The filename prefix of web pages after the homepage. The default is empty, no prefix. This option is stored into \LWR@HTMLFilename, and later transferred into \HTMLFilename for internal use.

```
\DeclareStringOption[]{HTMLFilename}
```

Opt PrintLatexCmd
Default: <automatic>

The shell commands to use to compile the print document.

```
\DeclareStringOption[]{PrintLatexCmd}
```

Opt HTMLLatexCmd
Default: <automatic>

The shell commands to use to compile the HTML document.

```
\DeclareStringOption[]{HTMLLatexCmd}
```

Opt PrintIndexCmd
Default: <empty>

The shell commands to use to compile the print indexes.

```
\DeclareStringOption[]{PrintIndexCmd}
```

Opt HTMLIndexCmd
Default: <empty>

The shell commands to use to compile the HTML indexes.

```
\DeclareStringOption[]{HTMLIndexCmd}
```

Opt LatexmkIndexCmd
Default: <empty>

The shell commands to by used by *latexmk* to compile the print indexes. Unlike PrintIndexCmd and HTMLIndexCmd, LatexmkIndexCmd does not include the filename, which will be provided by *latexmk*.

```
\DeclareStringOption[]{LatexmkIndexCmd}
```

Opt makeindex

Tells lwarp to use makeindex for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *makeindex* with a single index file.

```
\DeclareBoolOption[false]{makeindex}
```

Opt xindy

Tells lwarp to use xindy for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *xindy* with a single index file.

```
\DeclareBoolOption[false]{xindy}
```

Opt GlossaryCmd
Default: makeglossaries

The shell command to use to compile the glossary. The print or HTML version of the glossary filename will be appended to this command.

```
\DeclareStringOption[makeglossaries]{GlossaryCmd}
```

Opt latexmk

Option latexmk tells *lwarpmk* to use *latexmk* when compiling documents.

```
\DeclareBoolOption[false]{latexmk}
```

Opt dvips

Option dvips tells *lwarpmk* to use *dvips* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvips}
```

Opt dvipdfm

Option dvipdfm tells *lwarpmk* to use *dvipdfm* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvipdfm}
```

Opt dvipdfmx

Option dvipdfmx tells *lwarpmk* to use *dvipdfmx* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvipdfmx}
```

Execute options

Execute the package options, with the defaults which have been set just above:

```
\ProcessKeyvalOptions*\relax
```

28.1 Additional options support

Assign the \BaseJobname if the user hasn't provided one:

```
\providecommand*{\BaseJobname}{\LWR@BaseJobname}
```

Defaults unless already over-ridden by the user:

```
\ifcsempty{LWR@HomeHTMLFilename}{
    \newcommand*{\HomeHTMLFilename}{\BaseJobname}
}{
    \csedef{HomeHTMLFilename}{\LWR@HomeHTMLFilename}
}

\csedef{HTMLFilename}{\LWR@HTMLFilename}
```

Special handling for underscores in labels and filenames.

\LWR@sanitized

The sanitized version of what was given to \LWR@sanitize. Characters are set to their detokenized versions. Required for underscores in labels and filenames.

```
\newcommand*{\LWR@sanitized}{}
```

`\LWR@sanitize` {⟨*text*⟩}

Sanitizes the text and returns the result in `\LWR@sanitized`.

```
\newcommand*{\LWR@sanitize}[1]{%
\edef\LWR@sanitized{#1}%
\edef\LWR@sanitized{\detokenize\expandafter{\LWR@sanitized}}%
}
```

Sanitize some string options to neutralize underscores.

```
\LWR@sanitize{\LWR@BaseJobname}
\edef\LWR@BaseJobname{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesDirectory}
\edef\LWR@ImagesDirectory{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesName}
\edef\LWR@ImagesName{\LWR@sanitized}
```

`\LWR@PrintIndexCmd` and `\LWR@HTMLIndexCmd` are tested to see if they are empty. If so, they are set to a reasonable defaults for a single index using *makeindex*, then possibly set to defaults for *xindy* if the lwarp `xindy` option was selected.

```
\ifdefempty{\LWR@PrintIndexCmd}{
    \renewcommand{\LWR@PrintIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname.idx%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@PrintIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
            \jobname.idx%
        }
    }{}
}{}

\ifdefempty{\LWR@HTMLIndexCmd}{
    \renewcommand{\LWR@HTMLIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname_html.idx%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@HTMLIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
            \jobname_html.idx%
        }
    }{}
}{}

```

```
\ifdefempty{\LWR@LatexmkIndexCmd}{
    \renewcommand{\LWR@LatexmkIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@LatexmkIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage%
        }
    }{}
}{}
```

28.2 Conditional compilation

\warpprintonly {⟨*contents*⟩}

Only process the contents if producing printed output.

```
\newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{}}
```

\warpHTMLonly {⟨*contents*⟩}

Only process the contents if producing HTML output.

```
\newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{}}
```

Pkg comment Provides conditional code blocks.

Attempts to use versions or verbatim fail in some cases, and do not provide much of a speed benefit even when they do work.

```
\RequirePackage{comment}
```

Use `comment_print.cut` for print mode, and `comment_html.cut` for HTML mode. This helps *latexmk* to more reliably know whether to recompile.

```
\ifbool{warpingHTML}{
\def\DefaultCutFileName{\def\CommentCutFile{comment_html.cut}}
}{}

\ifbool{warpingprint}{
\def\DefaultCutFileName{\def\CommentCutFile{comment_print.cut}}
}{}
```

Env warpall Anything in the `warpall` environment will be generated for print or HTML outputs.

```
\includecomment{warpall}
```

Env warpprint
Env warpHTML

Anything in the warpprint environment will be generated for print output only.

For HTML output:

```
\ifbool{warpingHTML}
{\includecomment{warpHTML}}
{\excludecomment{warpHTML}}%

\ifbool{warpingprint}
{\includecomment{warpprint}}
{\excludecomment{warpprint}}
```

Optionally generate a local copy of *lwarpmk*. Default to no.

```
\ifbool{LWR@creatinglwarpmk}
{\includecomment{LWR@createlwarpmk}}
{\excludecomment{LWR@createlwarpmk}}
```

29 Required packages

These packages are automatically loaded by lwarp when generating HTML output. Some of them are also automatically loaded when generating print output, but some are not.

for HTML output:

```
\begin{warpHTML}
```

Load fontspec if necessary:

```
\ifxetexorluatex
\@ifpackageloaded{fontspec}{}{
    \usepackage[no-math]{fontspec}
}
```

The monospaced font is used for HTML tags, so turn off its TeX ligatures and common ligatures:

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
\else
```

pdflatex only: Only pre-loaded if *pdflatex* is being used.

Pkg microtype

ligatures

Older browsers don't display ligatures. Turn off letter ligatures, keeping LaTeX dash and quote ligatures, which may fail on older browers but at least won't corrupt written words.

```
\RequirePackage {microtype}
```

```
\microtypesetup{
    protrusion=false,
    expansion=false,
    tracking=false,
    kerning=false,
    spacing=false}

\DisableLigatures[f,q,t,T,Q]{encoding = *,family = *}

\fi

\end{warpHTML}
```

Pkg geometry Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

for HTML output:

```
\begin{warpHTML}
```

If geometry has not yet been loaded, use the preexising page and text sizes to be preserved for later reuse. These will be replaced by lwarp `\AtBeginDocument` with a very large page size to reduce HTML tag overflow off the page.

```
\@ifpackageloaded{geometry}
{}{
    \RequirePackage[
        reset,
        paperwidth=\paperwidth,
        paperheight=\paperheight,
        textwidth=\textwidth,
        textheight=\textheight,
        left=\oddsidemargin,
        top=\topmargin,
        marginparsep=\marginparsep,
        marginparwidth=\marginparwidth,
    ]{geometry}
}
```

Remember the original definitions for later reuse. If the geometry package is loaded by the user, lwarp-geometry will nullify the user-level originals.

```
\LetLtxMacro\LWR@origgeometry\geometry
\LetLtxMacro\LWR@orignewgeometry\newgeometry
\LetLtxMacro\LWR@origrestoregeometry\restoregeometry
\LetLtxMacro\LWR@origsavegeometry\savegeometry
\LetLtxMacro\LWR@origloadgeometry\loadgeometry
```

Bool
LWR@allowanothergeometry

geometry may be loaded by the user before lwarp, after lwarp, or not at all. If before lwarp, it will have already been loaded by now and its page layout has already been saved. If geometry is loaded after lwarp, its layout will be set at that time and the user macros nullified. \AtEndPreamble this layout will be saved. If the user never loads geometry, lwarp-geometry will be loaded \AtBeginDocument, but it should not change the page layout set here. This is controlled by the boolean LWR@allowanothergeometry. Geometry may be adjusted throughout the preamble until \AtEndPreamble, when this boolean is set false.

```
\newbool{LWR@allowanothergeometry}
\booltrue{LWR@allowanothergeometry}
```

Use \AtEndPreamble to avoid class and option conflict by changing settings after other packages load, instead of using geometry package options:

```
\AtEndPreamble{
```

Whatever geometry choices the user has made in the preamble, either before or after lwarp was loaded, are now saved for possible temporary reuse, such as by lyluatex.

See the lwarp-geometry section for what happens if geometry is loaded after lwarp.

```
\LWR@origsavegeometry{LWR@usergeometry}
```

The user's paper size is saved for later reuse, such as by the pdfpages package.

```
\newlength{\LWR@userspaperwidth}
\setlength{\LWR@userspaperwidth}{\paperwidth}

\newlength{\LWR@userspaperheight}
\setlength{\LWR@userspaperheight}{\paperheight}

\newlength{\LWR@usersmarginparwidth}
\setlength{\LWR@usersmarginparwidth}{\marginparwidth}
```

For lwarp, use a very large page and margins to help avoid letting HTML tags run off the edge:

```
\LWR@origgeometry{
    reset,
    paperheight=190in,
    paperwidth=20in,
    left=2in,
    right=6in,
    top=1in,
    bottom=1in,
    heightrounded,%
}
```

The lwarp page geometry is saved for future restore:

```
\LWR@origsavegeometry{LWR@lwarpgeometry}
```

No longer adjust the page layout when lwarp-geometry is loaded `\AtBeginDocument`:

```
\boolfalse{LWR@allowanothergeometry}%
```

ltjsbook and other classes can print vertically, and require these to be reset by lwarp:

```
\setlength{\textheight}{0.8\paperheight}
\setlength{\textwidth}{0.7\paperwidth}

\@twosidefalse
\@mparswitchfalse
}% \AtEndPreamble

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xparse

LaTeX3 command argument parsing

```
\RequirePackage{xparse}
```

Pkg calc

```
\RequirePackage{calc}

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg expl3

LaTeX3 programming

```
\RequirePackage{expl3}
```

Pkg gettitlestring

Used to emulate `\nameref`.

```
\RequirePackage{gettitlestring}
```

Pkg everyhook

everyhook is used to patch paragraph handling.

```
\@ifundefined{bxjs@everypar}{}{\let\everypar\bxjs@everypar}

\RequirePackage{everyhook}
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg filecontents

Used to write helper files, done in print mode.

Patched to work with morewrites, per https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910

(Recent versions of LaTeX (as of Fall 2019) now include the functionality of the filecontents package, but the package will still be used for those who still have older installations.)

```
\RequirePackage{filecontents}

\@ifpackagelater{filecontents}{2011/10/09}%
{}
{
\newwrite\fcwrite
\let\LWR@origfilec@ntents\filec@ntents
\def\filec@ntents{\def\chardef##1\write{\let\reserved@c\fcwrite}\LWR@origfilec@ntents}
}

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg xifthen

```
\RequirePackage{xifthen}
```

Pkg verbatim

```
\RequirePackage{verbatim}
```

Pkg refcount

Provides \setcounterref, \setcounterpageref, etc.

```
\RequirePackage{refcount}
```

Pkg newfloat

```
\RequirePackage{newfloat}

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xstring

⚠ index

There was a short-term bug in xstring regarding \IfInteger which affected lwarp's index generation. The updated version is requested here.

```
\RequirePackage{xstring}[2019/02/01]
```

Pkg environ Used to encapsulate math environments for re-use in HTML <alt> text.

```
\RequirePackage{environ}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg printlen Used to convert lengths for image width/height options.

```
\RequirePackage{printlen}
```

\LWR@printlength {⟨*length*⟩}

Prints a length using a locally-controlled unit and space. Rounding is used unless the length is small.

```
\newrobustcmd*{\LWR@printlength}[1]{%
\begingroup%
\uselengthunit{PT}%
\renewcommand*{\unitspace}{}%
\ifdimless{#1}{10pt}{%
    \printlength{#1}%
}{%
    \rndprintlength{#1}%
}%
\endgroup%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Pkg varwidth Used for print-mode lateximage.

```
\RequirePackage{varwidth}
```

```
\end{warpprint}
```

30 Loading packages

for HTML & PRINT:

```
\begin{warpall}
```

Remember the original \RequirePackage:

```
\LetLtxMacro\LWR@origRequirePackage\RequirePackage
```

\LWR@requirepackagenames Stores the list of required package names.

```
\newcommand*{\LWR@requirepackagenames}{}
```

\LWR@parsedrequirepackagenames Stores the parsed list of required package names after spaces are removed and `lwarp-` is prepended.

```
\newcommand*{\LWR@parsedrequirepackagenames}{}
```

\LWR@nullifycomment Remove the preexisting `comment` environment. Certain packages define it for their own use.

```
\newcommand*{\LWR@nullifycomment}{%
    \PackageInfo{lwarp}%
       {Nullifying the comment environment before loading \LWR@strresulttwo,}%
    \let\comment\relax%
    \let\endcomment\relax%
}
```

\LWR@findword [⟨*1: separator*⟩] {⟨*2: list*⟩} {⟨*3: index*⟩} [⟨*4: destination*⟩]

Note that argument 4 is passed directly to `\StrBetween`.

```
\newcommand*\LWR@findword[3][,]{%
    \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}{#1}%
}
```

\LWR@checkloadfilename {⟨*filename*⟩} Checks if this filename should be loaded after lwarp, or never at all.

The following should never be loaded:

```
\newcommand*{\LWR@checkloadfilename}[1]{%
\LWR@checkloadnever{#1}{ae}{latinmodern}
\LWR@checkloadnever{#1}{aecc}{latinmodern}
\LWR@checkloadnever{#1}{alg}{algorithm2e, algorithmicx}
\LWR@checkloadnever{#1}{algorithmic}{algorithm2e, algorithmicx}
\LWR@checkloadnever{#1}{bitfield}{bytefield}
\LWR@checkloadnever{#1}{boxedminipage}{boxedminipage2e}
\LWR@checkloadnever{#1}{caption2}{caption}
\LWR@checkloadnever{#1}{ccaption}{caption}
\LWR@checkloadnever{#1}{colortab}{colortbl}
\LWR@checkloadnever{#1}{doublespace}{setspace}
\LWR@checkloadnever{#1}{epsf}{graphicx}
\LWR@checkloadnever{#1}{fancyheadings}{fancyhdr}
\LWR@checkloadnever{#1}{fncylab}{cleveref}
\LWR@checkloadnever{#1}{glossary}{glossaries}
\LWR@checkloadnever{#1}{hyper}{hyperref}
\LWR@checkloadnever{#1}{newthm}{ntheorem}
\LWR@checkloadnever{#1}{pdfcprot}{microtype}
\LWR@checkloadnever{#1}{picinpar}{floatflt, wrapfig}
\LWR@checkloadnever{#1}{picins}{floatflt, wrapfig}
\LWR@checkloadnever{#1}{rplain}{fancyhdr}
\LWR@checkloadnever{#1}{si}{siunitx}
\LWR@checkloadnever{#1}{sistyle}{siunitx}
\LWR@checkloadnever{#1}{t1enc}{fontenc, inputenc, inputenx}
\LWR@checkloadnever{#1}{ucs}{inputenc, inputencx}
\LWR@checkloadnever{#1}{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

The following should only be loaded before lwarp:

```
\LWR@checkloadbefore{#1}{ctex}
\LWR@checkloadbefore{#1}{fontspec}
\LWR@checkloadbefore{#1}{inputenc}
\LWR@checkloadbefore{#1}{inputenx}
\LWR@checkloadbefore{#1}{nfssext-cfr}
\LWR@checkloadbefore{#1}{fontaxes}
\LWR@checkloadbefore{#1}{kotex}
\LWR@checkloadbefore{#1}{luatexja}
\LWR@checkloadbefore{#1}{luatexja-fontspec}
\LWR@checkloadbefore{#1}{luatexko}
\LWR@checkloadbefore{#1}{morewrites}
\LWR@checkloadbefore{#1}{newclude}
\LWR@checkloadbefore{#1}{newunicodechar}
\LWR@checkloadbefore{#1}{plext}
\LWR@checkloadbefore{#1}{xeCJK}
\LWR@checkloadbefore{#1}{xetexko}
\LWR@checkloadbefore{#1}{zxjatype}
}
```

`\LWR@lookforpackagename` {⟨*index*⟩}

If HTML, and if this is an lwarp-supported package name, re-direct it to the lwarp version by renaming it `lwarp-` followed by the original name.

Looks `index` deep into the list of package names, `\LWR@requirepackagenames`, and builds `\LWR@parsedrequirepackagenames` which is the modified list of names.

```
\newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the `index`'th package name from the list:

```
\LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in `LWR@strresult` and the final name with no blanks goes into `LWR@strresulttwo`.

```
\StrSubstitute[100]{\LWR@strresult}{ }{}[\LWR@strresulttwo]%
```

See if the package name was found:

```
\IfStrEq{\LWR@strresulttwo}{}%
{}% no filename
{% yes filename was found
```

Possible adjustments before loading the package. Maybe nullify the `comment` environment if the new package will be redefining it for a new purpose.

```
    \ifdefstring{\LWR@strresulttwo}{easyReview}{\LWR@nullifycomment}{}%
    \ifdefstring{\LWR@strresulttwo}{changes}{\LWR@nullifycomment}{}%
```

If HTML, check if the package should be loaded before lwarp, or never at all:

```
    \ifbool{warpingHTML}{\LWR@checkloadfilename{\LWR@strresulttwo}}{}%
```

If HTML, and if found, and if an lwarp-equivalent name exists, use `lwarp-*` instead.

```
    \ifboolexpr{
        bool{warpingHTML} and
        test{\IfFileExists{lwarp-\LWR@strresulttwo.sty}}
    }%
    {% lwarp-* file found
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
            \edef\LWR@parsedrequirepackagenames{lwarp-\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,lwarp-\LWR@strresulttwo%
            }%
        }%
    }%
    {%
```

Otherwise, use the current package name.

```
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
            \edef\LWR@parsedrequirepackagenames{\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,\LWR@strresulttwo%
            }%
        }%
    }% no lwarp-* file
}% yes filename
}
```

\RequirePackage `[`⟨*1: options*⟩`]` `{`⟨*2: package names*⟩`}` `[`⟨*3: version*⟩`]`

For each of many package names in a comma-separated list, if an lwarp version of a package exists, select it instead of the LaTeX version.

```
\RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to twenty names:[16]

```
\renewcommand*{\LWR@requirepackagenames}{#2}%
\renewcommand*{\LWR@parsedrequirepackagenames}{}%
\LWR@lookforpackagename{1}%
\LWR@lookforpackagename{2}%
\LWR@lookforpackagename{3}%
\LWR@lookforpackagename{4}%
\LWR@lookforpackagename{5}%
\LWR@lookforpackagename{6}%
\LWR@lookforpackagename{7}%
\LWR@lookforpackagename{8}%
\LWR@lookforpackagename{9}%
```

[16] This was originally nine names, but then I came across a package which used twelve...

```
\LWR@lookforpackagename{10}%
\LWR@lookforpackagename{11}%
\LWR@lookforpackagename{12}%
\LWR@lookforpackagename{13}%
\LWR@lookforpackagename{14}%
\LWR@lookforpackagename{15}%
\LWR@lookforpackagename{16}%
\LWR@lookforpackagename{17}%
\LWR@lookforpackagename{18}%
\LWR@lookforpackagename{19}%
\LWR@lookforpackagename{20}%
```

\RequirePackage depending on the options and version:

```
\IfValueTF{#1}%
{% options given
    \IfValueTF{#3}% version given?
    {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}[#3]}%
    {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}}%
}%
{% no options given
    \IfValueTF{#3}% version given?
    {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}[#3]}%
    {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}}%
}%
}
\LetLtxMacro\usepackage\RequirePackage
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@ProvidesPackagePass {⟨*pkgname*⟩} [⟨*version*⟩]

Uses the original package, including options.

```
\NewDocumentCommand{\LWR@ProvidesPackagePass}{m o}{
\PackageInfo{lwarp}{%
    Using package ‘#1’ and adding lwarp modifications,\MessageBreak
    including options,}%
\IfValueTF{#2}
{\ProvidesPackage{lwarp-#1}[#2]}
{\ProvidesPackage{lwarp-#1}}
\DeclareOption*{\PassOptionsToPackage{\CurrentOption}{#1}}
\ProcessOptions\relax
\IfValueTF{#2}
{\LWR@origRequirePackage{#1}[#2]}
{\LWR@origRequirePackage{#1}}
```

In some cases, the following seems to be required to avoid an “unknown option” error, such as when loading xcolor with options.

```
\DeclareOption*{}%
\ProcessOptions\relax
```

```
}
```

`\LWR@ProvidesPackageDropA` {⟨*name*⟩} {⟨*date or -NoValue-*⟩}

Declares the package. Factored for reuse.

```
\newcommand*{\LWR@ProvidesPackageDropA}[2]{%
    \PackageInfo{lwarp}{%
        Replacing package ‘#1’ with the lwarp version,\MessageBreak
        and discarding options,%
    }%
    \IfValueTF{#2}
    {\ProvidesPackage{lwarp-#1}[#2]}
    {\ProvidesPackage{lwarp-#1}}
}
```

`\LWR@ProvidesPackageDropB` Nullifies then processes the options.

Seems to be required when options contain curly braces, which were causing “`Missing \begin{document}`”.

```
\newcommand*{\LWR@ProvidesPackageDropB}{%
% \ProcessOptions\relax% original LaTeX code
\let\ds@\@empty%         from the original \ProcessOptions
\edef\@curroptions{}%    lwarp modification to \ProcessOptions
\@process@ptions\relax%  from the original \ProcessOptions
}
```

`\LWR@ProvidesPackageDrop` {⟨*pkgname*⟩} [⟨*version*⟩]

Ignores the original package and uses lwarp’s version instead. Drops/discards all options.

```
\NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o}{
```

Declare the package:

```
\LWR@ProvidesPackageDropA{#1}{#2}
```

Ignore all options:

```
\DeclareOption*{}
```

Process the options:

```
\LWR@ProvidesPackageDropB
}
```

```
\end{warpHTML}
```

31 Additional required packages

for HTML output:
```
\begin{warpHTML}
```

Pkg caption

```
\LWR@origRequirePackage{caption}
\AtBeginDocument{\RequirePackage{lwarp-caption}}%
```

```
\end{warpHTML}
```

32 File handles

Defines file handles for writes.

for HTML & PRINT:
```
\begin{warpall}
```

\LWR@quickfile For quick temporary use only. This is reused in several places.

```
\newwrite\LWR@quickfile%
```

```
\end{warpall}
```

for HTML output:
```
\begin{warpHTML}
```

\LWR@lateximagesfile For <project>-images.txt:

```
\newwrite\LWR@lateximagesfile
```

```
\end{warpHTML}
```

33 Include a file

During HTML output, \include{<filename>} causes the following to occur:

1. lwarp creates <filename>_html_inc.tex whose contents are:
   ```
   \input <filename>.tex
   ```
2. <filename>_html_inc.tex is then \included instead of <filename>.tex.
3. <filename>_html_inc.aux is automatically generated and used by LaTeX.

for HTML output:
```
\begin{warpHTML}
```

`\@include` {⟨*filename*⟩} Modified to load `_html_inc` files.

(Below, `\clearpage` caused missing text, and was changed to `\newpage`.)

```
\def\@include#1 {%
\immediate\openout\LWR@quickfile #1_html_inc.tex% lwarp
\immediate\write\LWR@quickfile{\string\input{#1.tex}}% lwarp
\immediate\closeout\LWR@quickfile% lwarp
\LWR@orignewpage% changed from clearpage
\if@filesw
    \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
\fi
\@tempswatrue
\if@partsw
    \@tempswafalse
    \edef\reserved@b{#1}%
    \@for\reserved@a:=\@partlist\do
    {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
\fi
\if@tempswa
    \let\@auxout\@partaux
    \if@filesw
        \immediate\openout\@partaux #1_html_inc.aux % changed
        \immediate\write\@partaux{\relax}%
    \fi
    \@input@{#1_html_inc.tex}% changed
    \LWR@orignewpage% changed from clearpage
    \@writeckpt{#1}%
    \if@filesw
        \immediate\closeout\@partaux
    \fi
\else
    \deadcycles\z@
    \@nameuse{cp@#1}%
\fi
\let\@auxout\@mainaux%
}

\end{warpHTML}
```

34 Copying a file

for HTML output:

```
\begin{warpHTML}
```

`\LWR@copyfile` {⟨*source filename*⟩} {⟨*destination filename*⟩}

Used to copy the `.toc` file to `.sidetoc` to re-print the TOC in the sideTOC navigation pane.

```
\newwrite\LWR@copyoutfile  % open the file to write to
\newread\LWR@copyinfile      % open the file to read from

```

```
\newcommand*{\LWR@copyfile}[2]{%
\LWR@traceinfo{LWR@copyfile: copying #1 to #2}

\immediate\openout\LWR@copyoutfile=#2
\openin\LWR@copyinfile=#1
\begingroup\endlinechar=-1
\makeatletter

\LWR@traceinfo{LWR@copyfile: about to loop}

\loop\unless\ifeof\LWR@copyinfile
  \LWR@traceinfo{LWR@copyfile: one line}
 \read\LWR@copyinfile to\LWR@fileline  % Read one line and store it into \LWR@fileline
%   \LWR@fileline\par                   % print the content into the pdf
% print the content:
  \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
\repeat
\immediate\closeout\LWR@copyoutfile
\LWR@traceinfo{LWR@copyfile: done}
\endgroup
}

\end{warpHTML}
```

35 Debugging messages

HTML comments

To have the HTML output include additional HTML comments, such as which is closing, use

```
\booltrue{HTMLDebugComments}
```

debugging information

To have debug information written to the log, use

```
\tracinglwarp
```

for HTML & PRINT:

```
\begin{warpall}
```

Bool `LWR@tracinglwarp`

True if tracing is turned on.

```
\newbool{LWR@tracinglwarp}
```

`\tracinglwarp`

Turns on the debug tracing messages.

```
\newcommand{\tracinglwarp}{\booltrue{LWR@tracinglwarp}}
```

`\LWR@traceinfo` {⟨*text*⟩}

If tracing is turned on, writes the text to the `.log` file.

```
\newcommand{\LWR@traceinfo}[1]{%
\ifbool{LWR@tracinglwarp}%
{%
    \typeout{*** lwarp: #1}%
```

```
}%
{}%
}
```

Bool HTMLDebugComments Add comments in HTML about closing s, sections, etc.
Default: false

```
\newbool{HTMLDebugComments}
\boolfalse{HTMLDebugComments}
```

If \tracinglwarp, show where preamble hooks occur:

```
\AfterEndPreamble{
\LWR@traceinfo{AfterEndPreamble}
}

\AtBeginDocument{
\LWR@traceinfo{AtBeginDocument}
}

\end{warpall}
```

36 Defining print and HTML versions of macros and environments

The following refers to defining objects inside lwarp, and is not for the user's document.

Many macros and environments must be provided as both print and HTML versions.

While generating the print version of a document, the original macros as defined by LaTeX and its packages are used as-is.

While generating the HTML version of a document, the original macro or environment is redefined to call a new HTML version or a copy of the original print version. The new HTML versions of macros and environments are used most of the time. Copies of the print versions are used inside a latexmage environment, which draws and remembers an image of the printed output, and also several other places. The copies of the print versions may also be used by the HTML versions, such as when the HTML version merely encloses the print version inside HTML tags.

The general structure for providing print and HTML versions of a macro or environment is as follows:

For a preexisting macro, not defined with xparse: An HTML version is provided with a special name, inside a warpHTML environment, then \LWR@formatted is used to redefine and patch various macros:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may also use xparse
```

```
\LWR@formatted{name}
\end{warpHTML}
```

`\LWR@formatted{name}` copies the original print version, then redefines `\name` to use either the print or HTML version depending on which mode lwarp is using. xparse may be used to define the new HTML version, even if the original did not use xparse.

For a preexisiting environment, not defined with xparse: The process is similar. Note the use of `\LWR@formattedenv` instead of `\LWR@formatted`.

```
\begin{warpHTML}
\newenvironment{LWR@HTML@name}{...}% may also use xparse

\LWR@formattedenv{name}
\end{warpHTML}
```

If the original used xparse: A copy must be made using a new name:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@name}{..}{..}% copy the original

\NewDocumentCommand{\LWR@HTML@name}{..}{..}% or use \newcommand

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment, using `\LWR@formattedenv`. (`\LWR@formatted` and `\LWR@formattedenv` use `\LetLtxMacro` to copy the original print definiton, which may not work with macros and environments created by xparse, so the print version must be manually recreated in the lwarp source.)

For a new macro or environment, not using xparse for the print version:

```
\begin{warpall}
\newcommand{\name}{...}% NOT xparse!
\end{warpall}

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may use xparse for HTML

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment. The plain `\name` or environment `name` is used for the printed version, and is placed inside `warpall`. xparse may be used for the `\LWR@HTML@<name>` version.

For a new macro or environment, using xparse: It is possible to use xparse for an entirely new macro or environment by defining the \LWR@print@<name> version with xparse, along with \name defined without xparse to refer directly to the \LWR@print version:

```
\begin{warpall}
\NewDocumentCommand{\LWR@print@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@print@name}{...} {...} {...}

% Simply a call to \LWR@print@name:
\newcommand{\name}{\LWR@print@name}%        -or-
\newenvironment{name}{\LWR@print@name}{\endLWR@print@name}
\end{warpall}

\begin{warpHTML}
\NewDocumentCommand{\LWR@HTML@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@HTML@name}{...} {...} {...}

\LWR@formatted{name}%    -or-
\LWR@formattedenv{name}
\end{warpHTML}
```

In general, \LWR@formatted or \LWR@formattedenv are placed inside a warpHTML environment, and while producing an HTML document they do the following:

- Macros are modified:
  1. The pre-existing print version \name is saved as \LWR@print@<name>, unless \LWR@print@<name> is already defined.
  2. The original \name is redefined to call either the print or HTML version depending on which format is in use at the moment, as set by \LWR@formatting, which is defined as either "print" or "HTML".
- When lwarp is producing a print document, the original definitions are used, as well as any new definitions defined in warpall above.
- When lwarp is generating HTML output, \LWR@formatting is set to "HTML", and \name is directed to \LWR@HTML@<name>.
- When lwarp is generating HTML output but enters a lateximage environment, or for some other reason needs to draw images using the original print defintions, \LWR@formatting is changed to "print" and \name is then redirected to \LWR@print@<name>, which was the original \name.

Since arguments are not handled by the new \name, any star and other arguments are processed by the print or HTML version.

Expandable versions are also provided as well. These usually are necessary for anything which could appear inside a tabular, without which a "Misplaced \omit" error may occur.

⚠ Misplaced \omit error

\LWR@expandableformatted
\LWR@expandableformattedenv

(Older versions of lwarp used \LetLtxMacro for everything, but this could fail when using macros defined by xparse. This older system is still in use for many definitions.)

for HTML output:

```
\begin{warpHTML}
```

\LWR@formatting Remembers if selected print/HTML formatting.

Used while \LWR@restoreorigformatting, such as in an lateximage. May be set to either "print" or "HTML".

```
\newcommand*{\LWR@formatting}{HTML}
```

\LWR@formatted {⟨*macroname*⟩} No backslash in the macro name.

If not yet defined, defines \LWR@print@<name> as the original print-mode \<name>. Also redefines \<name> to use \LWR@<format>@<name>, where <format> is set by \LWR@formatting, and is print or HTML.

```
\newcommand*{\LWR@formatted}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
        \expandafter\newrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }%
}
```

\LWR@expandableformatted {⟨*macroname*⟩} No backslash in the macro name.

An expandable version of \LWR@formatted.

```
\newcommand*{\LWR@expandableformatted}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
        \expandafter\newcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
```

```
        }%
    }%
}
```

`\LWR@formattedenv` {⟨*environmentname*⟩}

If not yet defined, defines the environment `LWR@print@<name>` as the original print-mode `<name>`. Also redefines the environment `<name>` to use environment `LWR@<format>@<name>`, where `<format>` is set by `\LWR@formatting`, and is `print` or `HTML`.

```
\newcommand*{\LWR@formattedenv}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareDocumentEnvironment{#1}{}%
    {%
        \@nameuse{LWR@\LWR@formatting @#1}%
    }%
    {%
        \@nameuse{endLWR@\LWR@formatting @#1}%
    }%
}
```

`\LWR@expandableformattedenv` {⟨*environmentname*⟩}

An expandable version of `LWR@formattedenv`.

```
\newcommand*{\LWR@expandableformattedenv}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareExpandableDocumentEnvironment{#1}{}%
    {%
        \@nameuse{LWR@\LWR@formatting @#1}%
    }%
    {%
        \@nameuse{endLWR@\LWR@formatting @#1}%
    }%
}
```

```
\end{warpHTML}
```

37 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

for HTML & PRINT:

```
\begin{warpall}
```

37.1 User-level controls

Bool FormatEPUB
Default: false

Changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

```
\newbool{FormatEPUB}
\boolfalse{FormatEPUB}
```

Bool FormatWP
Default: false

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.

```
\newbool{FormatWP}
\boolfalse{FormatWP}
```

Bool WPMarkFloats
Default: false

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions. [17]

```
\newbool{WPMarkFloats}
\boolfalse{WPMarkFloats}
```

Bool WPMarkMinipages
Default: false

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

```
\newbool{WPMarkMinipages}
\boolfalse{WPMarkMinipages}
```

Bool WPMarkTOC
Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

[17] Perhaps some day word processors will have HTML import options for identifying <figure> and caption tags for figures and tables.

If set `false`*, the actual* TOC *is printed instead.*

```
\newbool{WPMarkTOC}
\booltrue{WPMarkTOC}
```

Bool `WPMarkLOFT` Default: `false`

While formatting for word processors, adds

```
=== list of figures ===    and/or
=== list of tables ===
```

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

```
\newbool{WPMarkLOFT}
\boolfalse{WPMarkLOFT}
```

Bool `WPMarkMath` Default: `false`

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

```
\newbool{WPMarkMath}
\boolfalse{WPMarkMath}
```

Bool `WPTitleHeading` Default: `false`

While formatting for word processors, `true` sets the document title to `<h1>`, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to `false` to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 172.

```
\newbool{WPTitleHeading}
\boolfalse{WPTitleHeading}
```

```
\end{warpall}
```

37.2 Heading adjustments

If formatting the HTML for a word processor, adjust heading levels.

If `WPTitleHeading` is true, adjust so that `part` is **Heading 1**.

If `WPTitleHeading` is false, use `<h1>` for the title, and set `part` to **Heading 2**.

for HTML output:

```
\begin{warpHTML}
```

```
\AtBeginDocument{
\ifbool{FormatWP}{
\@ifundefined{chapter}{
\ifbool{WPTitleHeading}{% part and section starting at h2
\renewcommand*{\LWR@tagtitle}{h1}
```

```
\renewcommand*{\LWR@tagtitleend}{/h1}
\renewcommand*{\LWR@tagpart}{h2}
\renewcommand*{\LWR@tagpartend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
\renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% WPTitleHeading
{% not WPTitleHeading, part and section starting at h1
\renewcommand*{\LWR@tagtitle}{div class="title"}
\renewcommand*{\LWR@tagtitleend}{/div}
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagsection}{h2}
\renewcommand*{\LWR@tagsectionend}{/h2}
\renewcommand*{\LWR@tagsubsection}{h3}
\renewcommand*{\LWR@tagsubsectionend}{/h3}
\renewcommand*{\LWR@tagsubsubsection}{h4}
\renewcommand*{\LWR@tagsubsubsectionend}{/h4}
\renewcommand*{\LWR@tagparagraph}{h5}
\renewcommand*{\LWR@tagparagraphend}{/h5}
\renewcommand*{\LWR@tagsubparagraph}{h6}
\renewcommand*{\LWR@tagsubparagraphend}{/h6}
}% not WPTitleHeading
}% chapter undefined
{% chapter defined
\ifbool{WPTitleHeading}{}
{% not WPTitleHeading, part and chapter starting at h1
\renewcommand*{\LWR@tagtitle}{div class="title"}
\renewcommand*{\LWR@tagtitleend}{/div}
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagchapter}{h2}
\renewcommand*{\LWR@tagchapterend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
\renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% not WPTitleHeading
}% chapter defined
}{}% FormatWP
}% AtBeginDocument
```

```
\end{warpHTML}
```

38 Remembering original formatting macros

for HTML output:

```
\begin{warpHTML}
```

Remember original definitions of formatting commands. Will be changed to HTML commands for most uses. Will be temporarily restored to original meaning inside any lateximage environment. Also nullify unused commands.

Some packages redefine \#, which is used to generate HTML, so the original must be remembered here.

```
\chardef\LWR@origpound=‘\#

\let\LWR@origcomma\,
\let\LWR@origthinspace\thinspace
\let\LWR@orignegthinspace\negthinspace
\let\LWR@origtilde~
\let\LWR@origenskip\enskip
\let\LWR@origquad\quad
\let\LWR@origqquad\qquad
\let\LWR@orighfil\hfil
\let\LWR@orighss\hss
\let\LWR@origllap\llap
\let\LWR@origrlap\rlap
\let\LWR@orighfilneg\hfilneg
\let\LWR@orighspace\hspace

\let\LWR@origrule\rule

\let\LWR@origmedskip\medskip
\let\LWR@origbigskip\bigskip

\let\LWR@origtextellipsis\textellipsis
\let\LWR@orig@textquotedbl\textquotedbl

\LetLtxMacro\LWR@origttfamily\ttfamily

\LetLtxMacro\LWR@origem\em

\LetLtxMacro\LWR@orignormalfont\normalfont

\let\LWR@origonecolumn\onecolumn

\let\LWR@origsp\sp
\let\LWR@origsb\sb
\LetLtxMacro\LWR@origtextsuperscript\textsuperscript
\LetLtxMacro\LWR@orig@textsuperscript\@textsuperscript

\AtBeginDocument{
\LetLtxMacro\LWR@origtextsubscript\textsubscript
```

```
\LetLtxMacro\LWR@orig@textsubscript\@textsubscript
}

\LetLtxMacro\LWR@origunderline\underline


\let\LWR@orignewpage\newpage

\let\LWR@origpagestyle\pagestyle
\let\LWR@origthispagestyle\thispagestyle
\LetLtxMacro\LWR@origpagenumbering\pagenumbering

\let\LWR@orignewline\newline


\AtBeginDocument{% in case packages change definition
\let\LWR@orig@trivlist\@trivlist
\let\LWR@origtrivlist\trivlist
\let\LWR@origendtrivlist\endtrivlist
\LetLtxMacro\LWR@origitem\item
\LetLtxMacro\LWR@origitemize\itemize
\LetLtxMacro\LWR@endorigitemize\enditemize
\LetLtxMacro\LWR@origenumerate\enumerate
\LetLtxMacro\LWR@endorigenumerate\endenumerate
\LetLtxMacro\LWR@origdescription\description
\LetLtxMacro\LWR@endorigdescription\enddescription
\let\LWR@orig@mklab\@mklab
\let\LWR@origmakelabel\makelabel
\let\LWR@orig@donoparitem\@donoparitem
\LetLtxMacro\LWR@orig@item\@item
\let\LWR@orig@nbitem\@nbitem
}

\let\LWR@origpar\par

\LetLtxMacro\LWR@origfootnote\footnote
\let\LWR@orig@mpfootnotetext\@mpfootnotetext


\AtBeginDocument{% in case packages change definition
\LetLtxMacro\LWR@orighline\hline%
\LetLtxMacro\LWR@origcline\cline%
}

\end{warpHTML}
```

39 Accents

Native LaTeX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX.

for HTML output:

```
\begin{warpHTML}
```

Without `\AtBeginDocument`, `\t` was being re-defined somewhere.

```
\AtBeginDocument{
```

The following are restored for print when inside a `lateximage`.

For Unicode engines, only `\t` needs to be redefined:

```
\LetLtxMacro\LWR@origt\t
```

For pdfLaTeX, additional work is required:

```
\ifPDFTeX% pdflatex or dvi latex
\LetLtxMacro\LWR@origequalaccent\=
\LetLtxMacro\LWR@origdotaccent\.
\LetLtxMacro\LWR@origu\u
\LetLtxMacro\LWR@origv\v
\LetLtxMacro\LWR@origc\c
\LetLtxMacro\LWR@origd\d
\LetLtxMacro\LWR@origb\b
```

The HTML redefinitions follow.

For pdfLaTeX, Unicode diacritical marks are used:

```
\renewcommand*{\=}[1]{#1\HTMLunicode{0305}}
\renewcommand*{\.}[1]{#1\HTMLunicode{0307}}
\renewcommand*{\u}[1]{#1\HTMLunicode{0306}}
\renewcommand*{\v}[1]{#1\HTMLunicode{030C}}
\renewcommand*{\c}[1]{#1\HTMLunicode{0327}}
\renewcommand*{\d}[1]{#1\HTMLunicode{0323}}
\renewcommand*{\b}[1]{#1\HTMLunicode{0331}}
\fi
```

For all engines, a Unicode diacritical tie is used:

```
\def\LWR@t#1#2{#1\HTMLunicode{0361}#2}
\renewcommand*{\t}[1]{\LWR@t#1}
```

`\LWR@restoreorigaccents` Called from `\restoreoriginalformatting` when a `lateximage` is begun.

```
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@restoreorigaccents}{%
\LetLtxMacro\=\LWR@origequalaccent%
\LetLtxMacro\.\LWR@origdotaccent%
\LetLtxMacro\u\LWR@origu%
\LetLtxMacro\v\LWR@origu%
\LetLtxMacro\t\LWR@origt%
\LetLtxMacro\c\LWR@origc%
\LetLtxMacro\d\LWR@origd%
\LetLtxMacro\b\LWR@origb%
}%
\else% XeLaTeX, LuaLaTeX:
\newcommand*{\LWR@restoreorigaccents}{%
```

```
\LetLtxMacro\t\LWR@origt%
}%
\fi%
}% AtBeginDocument

\end{warpHTML}
```

40 Configuration files

40.1 Decide whether to generate configuration files

Configuration files are only written if processing the print version of the document, and not processing a pstool image. pstool uses an additional compile for each image using the original document's preamble, which includes lwarp, so the lwarp configuration files are turned off if `-pstool` is part of the `\jobname`.

Default to no configuration files:

```
\excludecomment{LWRwriteconf}
```

Generate configuration files if print mode and not `-pstool`:

for PRINT output:

```
\begin{warpprint}
\fullexpandarg%
\IfSubStr*{\jobname}{-pstool}
    {
        \PackageInfo{lwarp}{%
            Jobname with -pstool is found.\MessageBreak
            Not generating lwarp configuration files,%
        }
    }
    {
        \PackageInfo{lwarp}{Generating lwarp configuration files,}%
        \includecomment{LWRwriteconf}
    }
\end{warpprint}
```

40.2 <project>_html.tex

File `*_html.tex` Used to allow an HTML version of the document to exist alongside the print version.

Config file:

```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=\jobname_html.tex
\immediate\write\LWR@quickfile{%
\detokenize{\PassOptionsToPackage}%
{warpHTML,BaseJobname=\jobname}{lwarp}%
}
\immediate\write\LWR@quickfile{%
\detokenize{\input}\string{\jobname.tex\string }%
}
```

```
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.3 *lwarpmk* configuration files

Config file:

```
\begin{LWRwriteconf}
```

`\LWR@lwarpconfversion` The version number of the configuration file, allowing *lwarpmk* to detect an obsolete configuration file format. Incremented by one each time the configuration file format changes. (This is NOT the same as the lwarp version number.)

```
\newcommand*{\LWR@lwarpconfversion}{2}% also in lwarpmk.lua
```

40.3.1 Helper macros

`\LWR@shellescapecmd` The LaTeX compile option for shell escape, if used.

```
\ifshellescape
    \def\LWR@shellescapecmd{--shell-escape }
\else
    \def\LWR@shellescapecmd{}
\fi
```

`\LWR@compilecmd` {⟨*engine*⟩} {⟨*suffix*⟩}

Used to form the basic compilation command for a document, adding the optional shell escape.

Engine is *pdflatex*, etc. Suffix is empty or `_html`

```
\newcommand*{\LWR@compilecmd}[2]{%
    #1 \LWR@shellescapecmd \jobname#2%
}
```

`\LWR@addcompilecmd` {⟨*cmd*⟩} {⟨*suffix*⟩}

Adds to the compilation command.

Cmd is *dvipdfmx*, etc. Suffix is empty or `_html`

```
\newcommand*{\LWR@addcompilecmd}[2]{%
    \LWRopseq
    #1 \jobname#2%
}
```

`\LWR@unknownengine` Error message if not sure which LaTeX engine is being used.

```
\newcommand*{\LWR@unknownengine}{%
    \PackageError{lwarp}
```

```
    {Unknown LaTeX engine.}
   {Lwarp only knows about pdflatex, dvi latex, xelatex, lualatex, and upLateX.}
}
```

`\LWR@latexmkvar` {⟨*varname*⟩} {⟨*value*⟩}

Adds a *latexmk* variable assignment.

```
\newcommand*{\LWR@latexmkvar}[2]{%
    -e
    \LWRopquote%
    \LWRdollar #1=q/#2/%
    \LWRopquote
}
```

`\LWR@latexmkcmd` {⟨*latexmk options*⟩}

Sets a call to *latexmk* with the given options, possibly adding `--shell-escape`, and also adding the indexing program.

```
\newcommand*{\LWR@latexmkcmd}[1]{%
    latexmk  \space \LWR@shellescapecmd \space  #1 \space
    -recorder \space
    \LWR@latexmkvar{makeindex}{\LWR@LatexmkIndexCmd}
}
```

`\LWR@latexmkdvipdfm` {⟨*dvipdfm or dvipdfmx*⟩}

Adds the options settings for *dvipdfm* or *dvipdfmx*.

```
\newcommand*{\LWR@latexmkdvipdfm}[1]{%
    -pdfdvi \space
    \LWR@latexmkvar{dvipdf}{%
        #1
        \@percentchar O
        -o \@percentchar D
        \@percentchar S%
    }
}
```

`\LWR@compileuplatex` Sets compile options for upLaTeX with ujarticle or related classes.

```
\newcommand*{\LWR@compileuplatex}{
    \def\LWR@tempprintlatexcmd{%
        \LWR@compilecmd{uplatex}{}
        \LWR@addcompilecmd{dvipdfmx}{}
    }
    \def\LWR@tempHTMLlatexcmd{%
        \LWR@compilecmd{uplatex}{_html}
        \LWR@addcompilecmd{dvipdfmx}{_html}
    }
}
```

\LWR@PrintLatexCmd
\LWR@HTMLLatexCmd

If not set by the user, the following sets the command to use to compile the source to PDF form.

If using *latexmk*, a complicated string is created, eventually resulting in something such as:

For *xelatex* with `--shell-escape`:

```
[[latexmk   -xelatex   --shell-escape  -recorder
    -e '$makeindex = q/makeindex -s lwarp.ist/'  <jobname>_html]]
```

For *dvipdfmx*:

```
[[latexmk   -pdfdvi  -e '$dvipdf=q/dvipdfmx %O -o %D %S/'
    -recorder
    -e '$makeindex=q/makeindex -s lwarp.ist/'   <jobname>_html]]
```

For the following, temporary values are computed, but the permanent values are only set if the originals were not assigned by the user.

```
\ifbool{LWR@latexmk}{
```

For *latexmk* with *pdflatex* or *lualatex*:

```
    \ifpdf
```

For *latexmk* with *pdflatex*:

```
        \ifPDFTeX
            \def\LWR@latexcmd{\LWR@latexmkcmd{-pdf -dvi- -ps-}}
        \else
```

For *latexmk* with *lualatex*:

```
            \ifLuaTeX
                \def\LWR@latexcmd{\LWR@latexmkcmd{-lualatex}}
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For *latexmk* with *xelatex* or DVI *latex*:

```
        \ifXeTeX
```

For *latexmk* with *xelatex*:

```
            \def\LWR@latexcmd{\LWR@latexmkcmd{-xelatex}}
        \else% \ifXeTeX
```

For *latexmk* with DVI *latex*:

```
            \ifbool{LWR@dvipdfm}{
                \def\LWR@latexcmd{%
                    \LWR@latexmkcmd{%
                        \LWR@latexmkdvipdfm{dvipdfm}%
                    }
                }
            }{
                \ifbool{LWR@dvipdfmx}{
                    \def\LWR@latexcmd{%
                        \LWR@latexmkcmd{%
                            \LWR@latexmkdvipdfm{dvipdfmx}%
                        }
                    }
                }{
                    \def\LWR@latexcmd{\LWR@latexmkcmd{-pdfps}}
                }
            }
        \fi
    \fi% \ifpdf
```

The final assignment if *latexmk*:

```
    \def\LWR@tempprintlatexcmd{\LWR@latexcmd \space \jobname}
    \def\LWR@tempHTMLlatexcmd{\LWR@latexcmd \space \jobname_html}
}% latexmk
```

Without *latexmk*, the compiling command is simply the compiler name and the optional shell escape:

```
{% not latexmk
    \ifpdf
```

For *pdflatex* or *lualatex*:

```
        \ifPDFTeX
```

For *pdflatex*:

```
            \def\LWR@tempprintlatexcmd{\LWR@compilecmd{pdflatex}{}}
            \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{pdflatex}{_html}}
        \else
            \ifLuaTeX
```

For *lualatex*:

```
                \def\LWR@tempprintlatexcmd{\LWR@compilecmd{lualatex}{}}
                \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{lualatex}{_html}}
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For DVI *latex* or *xelatex*:

```
\ifXeTeX
```

For *xelatex*:

```
    \def\LWR@tempprintlatexcmd{\LWR@compilecmd{xelatex}{}}
    \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{xelatex}{_html}}
\else
```

For DVI *latex*. Default to *dvips*, unless told to use *dvipdfm* or *dvipdfmx*:

```
    \ifbool{LWR@dvipdfm}{
```

For DVI *latex* with *dvipdfm*:

```
        \def\LWR@tempprintlatexcmd{%
            \LWR@compilecmd{latex}{}
            \LWR@addcompilecmd{dvipdfm}{}
        }
        \def\LWR@tempHTMLlatexcmd{%
            \LWR@compilecmd{latex}{_html}
            \LWR@addcompilecmd{dvipdfm}{_html}
        }
    }{
        \ifbool{LWR@dvipdfmx}{
```

For DVI *latex* with *dvipdfmx*:

```
            \def\LWR@tempprintlatexcmd{%
                \LWR@compilecmd{latex}{}
                \LWR@addcompilecmd{dvipdfmx}{}
            }
            \def\LWR@tempHTMLlatexcmd{%
                \LWR@compilecmd{latex}{_html}
                \LWR@addcompilecmd{dvipdfmx}{_html}
            }
        }{% dvips
```

For DVI *latex* with *dvips* and *ps2pdf*:

```
            \def\LWR@tempprintlatexcmd{%
                \LWR@compilecmd{latex}{}
                \LWR@addcompilecmd{dvips}{}
                \LWR@addcompilecmd{ps2pdf}{}.ps
            }
            \def\LWR@tempHTMLlatexcmd{%
                \LWR@compilecmd{latex}{_html}
                \LWR@addcompilecmd{dvips}{_html}
                \LWR@addcompilecmd{ps2pdf}{_html}.ps
            }
        }
    }
\fi% \ifXeTeX
```

```
    \fi% \ifpdf
}% latexmk
```

For ujarticle, utarticle, and related, using upLaTeX and *dvipdfmx*:

```
\@ifclassloaded{ujarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{ujbook}{\LWR@compileuplatex}{}
\@ifclassloaded{ujreport}{\LWR@compileuplatex}{}
\@ifclassloaded{utarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{utbook}{\LWR@compileuplatex}{}
\@ifclassloaded{utreport}{\LWR@compileuplatex}{}
```

Only make the setting permanent if the original was empty:

```
\ifdefempty{\LWR@PrintLatexCmd}{
    \def\LWR@PrintLatexCmd{\LWR@tempprintlatexcmd}
}{}
\ifdefempty{\LWR@HTMLLatexCmd}{
    \def\LWR@HTMLLatexCmd{\LWR@tempHTMLlatexcmd}
}{}
```

`\LWR@writeconf` {⟨*filename*⟩}

Common code for each of `lwarpmk.conf` and `<project>.lwarpmkconf`. Each entry is a variable name, the equal sign, and a quoted string inside `[[` and `]]`, which are *lua*'s long quote characters, allowing the use of single and double quotes inside.

```
\newcommand{\LWR@writeconf}[1]{
\ifcsdef{LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
\immediate\openout\LWR@quickfile=#1
\immediate\write\LWR@quickfile{confversion = [[\LWR@lwarpconfversion]]}
\ifbool{usingOSWindows}{
    \immediate\write\LWR@quickfile{opsystem = [[Windows]]}
}{
    \immediate\write\LWR@quickfile{opsystem = [[Unix]]}
}
\immediate\write\LWR@quickfile{sourcename = [[\jobname]]}
\immediate\write\LWR@quickfile{homehtmlfilename = [[\HomeHTMLFilename]]}
\immediate\write\LWR@quickfile{htmlfilename = [[\HTMLFilename]]}
\immediate\write\LWR@quickfile{imagesdirectory = [[\LWR@ImagesDirectory]]}
\immediate\write\LWR@quickfile{imagesname = [[\LWR@ImagesName]]}
\immediate\write\LWR@quickfile{latexmk = [[\ifbool{LWR@latexmk}{true}{false}]]}
\immediate\write\LWR@quickfile{printlatexcmd = [[\LWR@PrintLatexCmd]]}
\immediate\write\LWR@quickfile{HTMLlatexcmd = [[\LWR@HTMLLatexCmd]]}
\immediate\write\LWR@quickfile{printindexcmd = [[\LWR@PrintIndexCmd]]}
\immediate\write\LWR@quickfile{HTMLindexcmd = [[\LWR@HTMLIndexCmd]]}
\immediate\write\LWR@quickfile{latexmkindexcmd = [[\LWR@LatexmkIndexCmd]]}
\immediate\write\LWR@quickfile{glossarycmd = [[\LWR@GlossaryCmd]]}
\immediate\write\LWR@quickfile{pdftotextenc = [[\LWR@pdftotextEnc]]}
\immediate\closeout\LWR@quickfile
}

\end{LWRwriteconf}
```

40.3.2 lwarpmk.conf

File lwarpmk.conf

lwarpmk.conf is automatically (re-)created by the lwarp package when executing
pdflatex <project.tex>,
or similar for *xelatex* or *lualatex*, in print-document generation mode, which is the default unless the warpHTML option is given. lwarpmk.conf is then used by the utility *lwarpmk*.

Config file:

```
\begin{LWRwriteconf}

\AtBeginDocument{\LWR@writeconf{lwarpmk.conf}}

\end{LWRwriteconf}
```

40.3.3 <project>.lwarpmkconf

File project.lwarpmkconf

A project-specific configuration file for *lwarpmk*.

The makeindex and xindy options have already been handled for lwarp.conf.

Config file:

```
\begin{LWRwriteconf}

\AtBeginDocument{\LWR@writeconf{\jobname.lwarpmkconf}}

\end{LWRwriteconf}
```

40.4 lwarp.css

File lwarp.css

This is the base CSS layer used by lwarp.

This must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.css}
/*
  CSS stylesheet for the LaTeX lwarp package
  Copyright 2016-2019 Brian Dunn — BD Tech Concepts LLC
*/


/* a fix for older browsers: */
header, section, footer, aside, nav, main,
    article, figure { display: block; }


A:link {color:#000080 ; text-decoration: none ; }
A:visited {color:#800000 ; }
A:hover {color:#000080 ; text-decoration: underline ;}
A:active {color:#800000 ; }

a.tocbook {display: inline-block ; margin-left: 0em ;
```

```
    font-weight: bold ; margin-top: 1ex ; margin-bottom: 1ex ; }
a.tocpart {display: inline-block ; margin-left: 0em ;
    font-weight: bold ;}
a.tocchapter {display: inline-block ; margin-left: 0em ;
    font-weight: bold ;}
a.tocsection {display: inline-block ; margin-left: 1em ;
    text-indent: -.5em ; font-weight: bold ; }
a.tocsubsection {display: inline-block ; margin-left: 2em ;
    text-indent: -.5em ; }
a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
    text-indent: -.5em ; }
a.tocparagraph {display: inline-block ; margin-left: 4em ;
    text-indent: -.5em ; }
a.tocsubparagraph {display: inline-block ; margin-left: 5em ;
    text-indent: -.5em ; }
a.tocfigure {margin-left: 0em}
a.tocsubfigure {margin-left: 2em}
a.toctable {margin-left: 0em}
a.tocsubtable {margin-left: 2em}
a.toctheorem {margin-left: 0em}
a.toclstlisting {margin-left: 0em}

body {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
        "Lucida Bright", Georgia, serif;
    background: #FAF7F4 ;
    color: black ;
    margin:0em ;
    padding:0em ;
    font-size: 100% ;
    line-height: 1.2 ;
}

p {margin: 1.5ex 0em 1.5ex 0em ;}
table p {margin: .5ex 0em .5ex 0em ;}

/* Holds a section number */
span.sectionnumber { margin-right: 0em }

/* Inserted in front of index lines */
span.indexitem {margin-left: 0em}
span.indexsubitem {margin-left: 2em}
span.indexsubsubitem {margin-left: 4em}

div.hidden, span.hidden { display: none ; }

kbd, span.texttt {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
    font-size: 100% ;
}

pre { padding: 3pt ; }

```

```
span.strong, span.textbf, div.strong, div.textbf { font-weight: bold; }

span.textit, div.textit { font-style: italic; }

span.textmd, div.textmd { font-weight: normal; }

span.texteb { font-weight: bolder; }

span.textlg { font-weight: lighter; }

span.textup, div.textup {
    font-style: normal;
    font-variant: normal;
    font-variant-numeric: normal ;
}

span.textsc, div.textsc {
    font-variant: small-caps;
    font-variant-numeric: oldstyle-nums ;
}

span.textulc, div.textulc {
    font-variant: normal ;
    font-variant-numeric: normal ;
}

span.textsl, div.textsl { font-style: oblique; }

span.textrm, div.textrm {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
    "Lucida Bright", Georgia, serif;
}

span.textsf, div.textsf {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
}

span.textcircled { border: 1px solid black ; border-radius: 1ex ; }

span.underline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
}

span.overline {
    text-decoration: overline ;
    text-decoration-skip: auto ;
}


/* for vertical text: */
div.verticalrl { writing-mode: vertical-rl }
div.horizontaltb { writing-mode: horizontal-tb }

```

```
1897
1898 /* for diagbox */
1899 div.diagboxtitleN { border-bottom: 1px solid gray }
1900 div.diagboxtitleS { border-top: 1px solid gray }
1901
1902 div.diagboxE {
1903     padding-left: 2em ;
1904     text-align: right ;
1905 }
1906
1907 div.diagboxW {
1908     padding-right: 2em ;
1909     text-align: left ;
1910 }
1911
1912
1913
1914 /* For realscripts */
1915 .supsubscript {
1916     display: inline-block;
1917     text-align:left ;
1918 }
1919
1920 .supsubscript sup,
1921 .supsubscript sub {
1922     position: relative;
1923     display: block;
1924     font-size: .5em;
1925     line-height: 1;
1926 }
1927
1928 .supsubscript sup {
1929     top: .5em;
1930 }
1931
1932 .supsubscript sub {
1933     top: .5em;
1934 }
1935
1936 div.attribution p {
1937     text-align: right ;
1938     font-size: 80%
1939 }
1940
1941 span.poemtitle {
1942   font-size: 120% ; font-weight: bold;
1943 }
1944
1945 pre.tabbing {
1946     font-family: "Linux Libertine Mono O", "Lucida Console",
1947         "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
1948         "Liberation Mono", "FreeMono", "Andale Mono",
1949         "Nimbus Mono L", "Courier New", monospace;
1950 }
1951
```

```
blockquote {
    display: block ;
    margin-left: 2em ;
    margin-right: 2em ;
}

/* quotchap is for the quotchap package */
div.quotchap {
    display: block ;
    font-style: oblique ;
    overflow-x: auto ;
    margin-left: 2em ;
    margin-right: 2em ;
}

blockquote p, div.quotchap p {
    line-height: 1.5;
    text-align: left ;
    font-size: .85em ;
}

/* qauthor is for the quotchap package */
div.qauthor {
  display: block ;
  text-align: right ;
  margin-left: auto ;
  margin-right: 2em ;
  font-size: 80% ;
  font-variant: small-caps;
}

div.qauthor p {
  text-align: right ;
}

div.epigraph, div.dictum {
  line-height: 1.2;
    text-align: left ;
    padding: 3ex 1em 0ex 1em ;
/*     margin: 3ex auto 3ex auto ; */ /* Epigraph centered */
    margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
/*    margin: 3ex 1em 3ex 1em ; */ /* Epigraph to the left */
    font-size: .85em ;
    max-width: 27em ;
}

div.epigraphsource, div.dictumauthor {
    text-align:right ;
    margin-left:auto ;
/*     max-width: 50% ; */
    border-top: 1px solid #A0A0A0 ;
    padding-bottom: 3ex ;
    line-height: 1.2;
}

```

```
div.epigraph p, div.dictum p { padding: .5ex ; margin: 0ex ;}
div.epigraphsource p, div.dictumauthor p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
div.dictumauthor { font-style:italic }


/* copyrightbox package */
div.copyrightbox { margin: .5ex .5em }
div.copyrightbox p {margin: 0px .5em ; padding: 0px}
div.copyrightboxnote {text-align: left ; font-size: 60%}


/* lettrine package: */
span.lettrine { font-size: 4ex ; float: left ; }
span.lettrinetext { font-variant: small-caps ; }

/* ulem, soul, umoline packages: */
span.uline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
}

span.uuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: double ;
}

span.uwave {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: wavy ;
}

span.sout {
    text-decoration: line-through ;
}

span.oline {
    text-decoration: overline ;
    text-decoration-skip: auto ;
}

span.xout {
    text-decoration: line-through ;
}

span.dashuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: dashed ;
}

span.dotuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
```

```
    text-decoration-style: dotted ;
}

span.letterspacing { letter-spacing: .2ex ; }

span.capsspacing {
    font-variant: small-caps ;
    letter-spacing: .1ex ;
}

span.highlight { background: #F8E800 ; }



html body {
  margin: 0 ;
  line-height: 1.2;
}


body div {
  margin: 0ex;
}


div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}

h1 {    /* title of the entire website, used on each page */
    text-align: center ;
    font-size: 2.5em ;
    padding: .4ex 0em 0ex 0em ;
}

div.book {
    text-align: center ;
    font-size: 2.325em ;
    padding: .4ex 0em 0ex 0em ;
}

h2 { font-size: 2.25em }
h3 { font-size: 2em }
h4 { font-size: 1.75em }
h5 { font-size: 1.5em }
h6 { font-size: 1.25em }
span.paragraph {font-size: 1em ; font-variant: normal ;
```

```
    margin-right: 1em ; }
span.subparagraph {font-size: 1em ; font-variant: normal ;
    margin-right: 1em ;  }

div.minisec {
    font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}

h1 {
  margin: 0ex 0em 0ex 0em ;
  line-height: 1.3;
  text-align: center ;
}

h2 {
  margin: 1ex 0em 1ex 0em ;
  line-height: 1.3;
  text-align: center ;
}

h3 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h4 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h5 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h6 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}


div.titlepage {
  text-align: center ;
}

.footnotes {
    text-align: left ;
    font-size: .85em ;
    margin: 3ex 2em 0ex 2em ;
    border-top: 1px solid silver ;
}
```

```
2172
2173 .marginpar, .marginparblock {
2174     max-width: 50%;
2175     float: right ;
2176     clear: both ;
2177     text-align: left ;
2178     margin: 1ex 0.5em 1ex 1em ;
2179     padding: 1ex 0.5em 1ex 0.5em ;
2180     font-size: 85% ;
2181     border-top: 1px solid silver ;
2182     border-bottom: 1px solid silver ;
2183     overflow-x: auto ;
2184 }
2185
2186 .marginpar br { margin-bottom: 2ex ; }
2187
2188 div.marginblock, div.marginparblock {
2189     max-width:50%;
2190     min-width: 10em; /* room for caption */
2191     float:right;
2192     text-align:left;
2193     margin: 1ex 0.5em 1ex 1em ;
2194     padding: 1ex 0.5em 1ex 0.5em ;
2195     overflow-x: auto;
2196 }
2197
2198 div.marginblock div.minipage,
2199 div.marginparblock div.minipage {
2200     display: inline-block ;
2201     margin: 0pt auto 0pt auto ;
2202 }
2203
2204 div.marginblock div.minipage p ,
2205 div.marginparblock div.minipage p
2206     { font-size: 85%}
2207
2208 div.marginblock br ,
2209 div.marginparblock br
2210     { margin-bottom: 2ex ; }
2211
2212 div.bodycontainer {
2213     float: left ;
2214     width: 80% ;
2215 }
2216
2217 div.bodywithoutsidetoc div.bodycontainer {
2218     float: none ;
2219     width: 100% ;
2220 }
2221
2222 section.textbody div.footnotes{
2223     margin: 3ex 2em 0ex 2em ;
2224     border-bottom: 2px solid silver ;
2225 }
2226
```

```
.footnoteheader {
    border-top: 2px solid silver ;
    margin-top: 3ex ;
    padding-top: 1ex ;
    font-weight: bold ;
}

.mpfootnotes {
    text-align: left ;
    font-size: .85em ;
    margin-left: 1em ;
    border-top: 1px solid silver ;
}

/* Remove footnote top border in the title page. */
div.titlepage div.mpfootnotes {
    border-top: none ;
}



ul, ol {
  margin: 1ex 1em 1ex 0em;
  line-height: 1.2;
}

body dir, body menu {
  margin: 3ex 1em 3ex 0em;
  line-height: 1.2;
}

li { margin: 0ex 0em 1ex 0em; }

html {
  margin: 0;
  padding: 0;
}

.programlisting {
  font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
  margin: 1ex 0ex 1ex 0ex ;
  padding: .5ex 0pt .5ex 0pt ;
  overflow-x: auto;
}

section.textbody>pre.programlisting {
border-top: 1px solid silver ;
border-bottom: 1px solid silver ;
}


div.displaymath {
    text-align: center ;
```

```
}

div.displaymathnumbered {
    text-align: right ;
    margin-left: 5% ;
    margin-right: 5% ;
    min-width: 2.5in ;
}

@media all and (min-width: 400px) {
    div.displaymathnumbered {
        margin-left: 10% ;
        margin-right: 10% ;
    }
}

@media all and (min-width: 800px) {
    div.displaymathnumbered {
        margin-right: 20% ;
    }
}

@media all and (min-width: 1200px) {
    div.displaymathnumbered {
        margin-right: 30% ;
    }
}


.inlineprogramlisting {
  font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
  overflow-x: auto;
}

span.listinglabel {
    display: inline-block ;
    font-size: 70% ;
    width: 4em ;
    text-align: right ;
    margin-right: 2em ;
}

div.abstract {
  margin: 2em 5% 2em 5% ;
  padding: 1ex 1em 1ex 1em ;
/*  font-weight: bold ; */
  font-size: 90% ;
    text-align: left ;
}

div.abstract dl {line-height:1.5;}
div.abstract dt {color:#304070;}

```

```
2337 div.abstracttitle{
2338     font-family: "URW Classico", Optima, "Linux Biolinum O",
2339         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2340         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2341     font-weight:bold;
2342     font-size:1.25em;
2343     text-align: center ;
2344 }
2345
2346 span.abstractrunintitle{
2347     font-family: "URW Classico", Optima, "Linux Biolinum O",
2348         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2349         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2350     font-weight:bold;
2351 }
2352
2353
2354 .verbatim {
2355     overflow-x: auto ;
2356 }
2357
2358 .alltt {
2359     overflow-x: auto ;
2360 }
2361
2362
2363 .bverbatim {
2364     margin: 1ex 0pt 1ex 0pt ;
2365     padding: .5ex 0pt .5ex 0pt ;
2366     overflow-x: auto ;
2367 }
2368
2369 .lverbatim {
2370     margin: 1ex 0pt 1ex 0pt ;
2371     padding: .5ex 0pt .5ex 0pt ;
2372     overflow-x: auto ;
2373 }
2374
2375 .fancyvrb {
2376     font-size:.85em ;
2377     margin: 3ex 0pt 3ex 0pt
2378 }
2379
2380 .fancyvrblabel {
2381     font-size: .85em ;
2382     text-align: center ;
2383     font-weight: bold ;
2384     margin-top: 1ex ;
2385     margin-bottom: 1ex ;
2386 }
2387
2388
2389 .verse {
2390     font-family: "Linux Libertine Mono O", "Lucida Console",
2391         "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
```

```
        "Liberation Mono", "FreeMono", "Andale Mono",
        "Nimbus Mono L", "Courier New", monospace;
    margin-left: 1em ;
}


div.singlespace { line-height: 1.2 ; }
div.onehalfspace { line-height: 1.5 ; }
div.doublespace { line-height: 2 ; }


/* Word processor format output: */
div.wpfigure { border: 1px solid red ; margin: .5ex ; padding: .5ex ; }
div.wptable { border: 1px solid blue ; margin: .5ex ; padding: .5ex ; }
div.wpminipage { border: 1px solid green ; margin: .5ex ; padding: .5ex ;}




/* Minipage environments, vertically aligned to top, center, bottom: */
.minipage, .fminipage, .fcolorminipage {
    /* display: inline-block ; */
        /* Mini pages which follow each other will be tiled. */
    margin: .25em .25em .25em .25em;
    padding: .25em .25em .25em .25em;
    display: inline-flex;
    flex-direction: column ;
    overflow: auto;
}

.inlineminipage {
    display: inline-block ;
    text-align: left
}

/* Paragraphs in the flexbox did not collapse their margins. */
/* Have not yet researched this. */
.minipage p {margin: .75ex 0em .75ex 0em ;}

.fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
.fcolorbox .minipage, .fcolorboxBlock .minipage
    {border: none ; background: none;}

.fbox, .fboxBlock { border: 1px solid black ; }

.fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
.fminipage, .fcolorminipage
    {display: inline-block}

.shadowbox, .shabox {
   border: 1px solid black;
    box-shadow: 3px 3px 3px #808080 ;
     border-radius: 0px ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
```

```
  display: inline-block ;
}

.doublebox {
   border: 3px double black;
     border-radius: 0px ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.ovalbox, .Ovalbox {
   border: 1px solid black;
     border-radius: 1ex ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.Ovalbox { border-width: 2px ; }

.framebox {
   border: 1px solid black;
     border-radius: 0px ;
    padding: .3ex .2em 0ex .2em ;
    margin: 0pt .1ex 0pt .1ex ;
  display: inline-block ;
}


.mdframed {
    padding: 0ex ;
    margin: 2ex 0em 2ex 0em ;
}

.mdframed p { padding: 0ex .5em 0ex .5em ; }

.mdframed dl { padding: 1ex .5em 0ex .5em ; }

.mdframedtitle {
    padding: .5ex 0pt 0pt 0pt ;
    border-radius: 10pt 10pt 0pt 0pt ;
    display: block ;
    margin-bottom: 1ex ;
}

.mdframedsubtitle {
    display: block ;
}

.mdframedsubsubtitle {
    display: block ;
}

.mdtheorem {
```

```
    padding: 0ex .5em 0ex .5em ;
    margin: 3ex 5% 3ex 5% ;
}


/* framed package */
.framed, pre.boxedverbatim, fcolorbox {
    margin: 3ex 0em 3ex 0em ;
   border: 1px solid black;
     border-radius: 0px ;
    padding: .3ex 1em 0ex 1em ;
  display: block ;
}

.shaded {
    margin: 3ex 0em 3ex 0em ;
    padding: .3ex 1em .3ex 1em ;
    display: block ;
}

.snugframed {
    margin: 3ex 0em 3ex 0em ;
   border: 1px solid black;
     border-radius: 0px ;
  display: block ;
}

.framedleftbar {
    margin: 3ex 0em 3ex 0em ;
   border-left: 3pt solid black;
     border-radius: 0px ;
    padding: .3ex .2em .3ex 1em ;
  display: block ;
}

.framedtitle {
    margin: 0em ;
    padding: 0em ;
    font-size: 130%
}

.framedtitle p { padding: .3em }


/* For the niceframe package: */

div.niceframe, div.curlyframe, div.artdecoframe, div.generalframe {
    padding: 1ex ;
    margin: 2ex auto ;
    border-radius: 2ex ;
}

div.niceframe {
    border: 6px groove black ;
}
```

```
2557
2558 div.curlyframe {
2559     border-left: 3px dotted black ;
2560     border-right: 3px dotted black ;
2561     border-radius: 6ex ;
2562 }
2563
2564 div.artdecoframe {
2565     border-left: 10px double black ;
2566     border-right: 10px double black ;
2567     border-radius: 6ex ;
2568 }
2569
2570 div.generalframe {
2571     border: 6px groove black ;
2572 }
2573
2574
2575
2576 dl {
2577   margin: 1ex 2em 1ex 0em;
2578   line-height: 1.3;
2579 }
2580
2581 dl dt {
2582     display: block ;
2583     float:left ;
2584     font-weight: bold;
2585     padding-right: 1em ;
2586 }
2587
2588 dl dd { display: block ; }
2589
2590 dl dd:after { content: "" ; display: block ; clear: both }
2591
2592 dl dd p { margin-top: 0em; }
2593
2594 dd ul, dd ol, dd dl { clear: both ; padding-top: 1ex }
2595
2596
2597 nav {
2598     font-family: "URW Classico", Optima, "Linux Biolinum O",
2599         "DejaVu Sans", "Bitstream Vera Sans",
2600         Geneva, Verdana, sans-serif ;
2601     margin-bottom: 4ex ;
2602 }
2603
2604 nav p {
2605     line-height: 1.2 ;
2606     margin-top:.5ex ;
2607     margin-bottom:.5ex;
2608     font-size: .9em ;
2609 }
2610
2611
```

```
2612
2613 img, img.hyperimage, img.borderimage {
2614     max-width: 600px;
2615     border: 1px solid silver;
2616     box-shadow: 3px 3px 3px #808080 ;
2617     padding: .5% ;
2618     margin: .5% ;
2619     background: none ;
2620 }
2621
2622 img.inlineimage{
2623     padding: 0px ;
2624     box-shadow: none ;
2625     border: none ;
2626     background: none ;
2627     margin: 0px ;
2628     display: inline-block ;
2629     border-radius: 0px ;
2630 }
2631
2632 img.logoimage{
2633     max-width: 300px ;
2634     box-shadow: 3px 3px 3px #808080 ;
2635     border: 1px solid black ;
2636     background:none ;
2637     padding:0 ;
2638     margin:.5ex ;
2639     border-radius: 10px ;
2640 }
2641
2642
2643 .section {
2644 /*
2645     To have each section float relative to each other:
2646 */
2647 /*
2648     display: block ;
2649     float: left ;
2650     position: relative ;
2651     background: white ;
2652     border: 1px solid silver ;
2653     padding: .5em ;
2654 */
2655     margin: 0ex .5em 0ex .5em ;
2656     padding: 0 ;
2657 }
2658
2659
2660 figure {
2661     margin: 5ex auto 5ex auto ;
2662     padding: 1ex 1em 1ex 1em ;
2663     overflow-x: auto ;
2664 }
2665
2666
```

```
/* To automatically center images in figures: */
/*
figure img.inlineimage {
    margin: 0ex auto 0ex auto ;
    display: block ;
}
*/

/* To automatically center minipages in figures: */
/*
figure div.minipage, figure div.minipage div.minipage {
    margin: 1ex auto 1ex auto ;
    display: block ;
}
*/

figure figure { margin: 0pt }

figure div.minipage p { font-size: 85% ; }

figure.subfigure, figure.subtable  {
    display: inline-block ; margin: 3ex 1em 3ex 1em ;
}

div.figurecaption .minipage { margin:0 ; padding: 0 }

div.minipage figure { border: none ; box-shadow: none ; }
div.minipage figure.table { margin: 0ex }
div.minipage div.footnotes { margin: 1ex 2em 0ex 2em }

div.floatrow { text-align: center; }

div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }

div.floatfoot { font-size: .85em ;
    border-top: 1px solid silver ; line-height: 1.2 ; }

div.figurecaption , .lstlistingtitle {
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
    margin-top: 1ex ;
    margin-bottom: 1ex ;
}

figure.subfigure div.figurecaption, figure.subtable div.figurecaption  {
    border-bottom: none ; background: none ;
}

div.nonfloatcaption {
    margin: 1ex auto 1ex auto ;
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
}
```

```
2722
2723 /* For a \RawCaption inside a minipage inside a figure's floatrow: */
2724 figure div.floatrow div.minipage div.figurecaption {
2725     border: none ;
2726     background: none ;
2727 }
2728
2729
2730 /* For packages such as float, rotfloat, and algorithm2e: */
2731
2732 figure.boxed, figure.boxruled {
2733     border: 1px solid black ;
2734 }
2735
2736 figure.ruled {
2737     border-top: 1px solid black ;
2738     border-bottom: 1px solid black ;
2739     border-left: 0px ;
2740     border-right: 0px ;
2741     border-radius: 0px ;
2742     background: none ;
2743     box-shadow: none ;
2744 }
2745
2746 figure.ruled div.figurecaption, figure.boxruled div.figurecaption {
2747     border-top: 1px solid silver ;
2748     border-bottom: 1px solid silver ;
2749 }
2750
2751
2752 table {
2753     margin: 1ex auto 1ex auto ;
2754     border-collapse: separate ;
2755     border-spacing: 0px ;
2756     line-height: 1.3 ;
2757     }
2758
2759 tr.hline td {border-top: 1px solid #808080 ; margin-top: 0ex ;
2760     margin-bottom: 0ex ; } /* for \hline */
2761
2762 tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;
2763     margin-bottom: 0ex ; } /* for \toprule, \bottomrule */
2764
2765 td {padding: .5ex .5em .5ex .5em ;}
2766
2767 table td.tdl { text-align: left ; vertical-align: middle ; }
2768 table td.tdc { text-align: center ; vertical-align: middle ; }
2769 table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }
2770 table td.tdbang { text-align: center ; vertical-align: middle ; }
2771 table td.tdr { text-align: right ; vertical-align: middle ; }
2772 table td.tdp { text-align: left ; vertical-align: bottom ; }
2773 table td.tdm { text-align: left ; vertical-align: middle ; }
2774 table td.tdb { text-align: left ; vertical-align: top ; }
2775 table td.tdP { text-align: center ; vertical-align: bottom ; }
2776 table td.tdM { text-align: center ; vertical-align: middle ; }
```

```
table td.tdB { text-align: center ; vertical-align: top ; }

table td.tvertbarl { border-left: 1px solid black }
table td.tvertbarldouble { border-left: 4px double black }
table td.tvertbarr { border-right: 1px solid black }
table td.tvertbarrdouble { border-right: 4px double black }

table td.tvertbarldash { border-left: 1px dashed black }
table td.tvertbarldoubledash { border-left: 2px dashed black }
table td.tvertbarrdash { border-right: 1px dashed black }
table td.tvertbarrdoubledash { border-right: 2px dashed black }


/* for cmidrules: */
table td.tdrule {
    border-top: 1px solid #A0A0A0 ;
}

table td.tdrulel {
    border-top-left-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}

table td.tdruler {
    border-top-right-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}

table td.tdrulelr {
    border-top-left-radius:.5em ;
    border-top-right-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}


/* Margins of paragraphs inside table cells: */
td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }
td.tdm p , td.tmbrule p , td.tdM p , td.tdMrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }
td.tdb p , td.tdbrule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }

td.tdp , td.tdprule , td.tdP , td.tdPrule
    { padding: 0ex .5em 0ex .5em ; }
td.tdm , td.tdmrule , td.tdM , td.tdMrule
    { padding: 0ex .5em 0ex .5em ; }
td.tdb , td.tdbrule , td.tdB , td.tdBrule
    { padding: 0ex .5em 0ex .5em ; }


/* table notes: */
.tnotes {
    margin: 0ex 5% 1ex 5% ;
    padding: 0.5ex 1em 0.5ex 1em;
```

```
    font-size:.80em;
    text-align: left ;
}

.minipage .tnotes {
    margin: 0pt ;
    padding: 0pt ;
}

.tnotes dl dt p {margin-bottom:0px;}

.tnoteitemheader {margin-right: 1em;}


/* for colortbl and cell color */
div.cellcolor {
    width: 100% ;
    padding: .5ex .5em .5ex .5em ;
    margin: -.5ex -.5em -.5ex -.5em ;
}


/* for lyluatex */
span.lyluatex {
    display: inline-block ;
}

div.lyluatex p span.lateximagesource img {
    display: block ;
    margin-top: 3ex ;
    margin-bottom: 3ex ;
}


/* for bigdelim */
.ldelim, .rdelim { font-size: 200% }


/* center, flushleft, flushright environments */
div.center{text-align:center;}
div.center table {margin-left:auto;margin-right:auto;}
div.flushleft{text-align:left;}
div.flushleft table {margin-left:0em ; margin-right:auto;}
div.flushright{text-align:right;}
div.flushright table {margin-left:auto ; margin-right: 0em ;}


/* Fancybox */
div.Btrivlist table tr td {
    padding: .2ex 0em ;
}


/* program listing callouts: */
span.callout {
```

```
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    border-radius: .5em;
    background-color:black;
    color:white;
    padding:0px .25em 0px .25em;
    margin: 0 ;
    font-weight: bold;
    font-size:.72em ;
}

div.programlisting pre.verbatim span.callout{
    font-size: .85em ;
}

span.verbatim {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
}



div.published
{
    text-align: center ;
    font-variant: normal ;
    font-style: italic ;
    font-size: 1em ;
    margin: 1ex 0em 1ex 0em ;
}

div.subtitle
{
    text-align: center ;
    font-variant: normal ;
    font-style: italic ;
    font-size: 1.25em ;
    margin: 1ex 0em 1ex 0em ;
}

div.subtitle p { margin: 1ex ; }

div.author
{
    font-variant: normal ;
    font-style: normal ;
    font-size: 1em ;
    margin: 1ex 0em 1ex 0em ;
}

div.oneauthor {
    display: inline-block ;
    margin: 0ex 1em 0ex 1em ;
}
```

```
2942
2943 /*
2944 div.author table {
2945     margin: 1ex auto 0ex auto ;
2946     background: none ;
2947 }
2948
2949 div.author table tbody tr td { padding: .25ex ; }
2950 */
2951
2952 span.affiliation {font-size: .85em ; font-variant: small-caps; }
2953
2954 div.titledate {
2955     text-align: center ;
2956     font-size: .85em ;
2957     font-style: italic;
2958     margin: 1ex 0em 1ex 0em ;
2959 }
2960
2961
2962 nav.topnavigation{
2963     text-align: left ;
2964     padding: 0.5ex 1em 0.5ex 1em ;
2965 /*     margin: 2ex 0em 3ex 0em ; */
2966     margin: 0 ;
2967     border-bottom: 1px solid silver ;
2968     border-top: 1px solid silver ;
2969     clear:both ;
2970 }
2971
2972 nav.botnavigation{
2973     text-align: left ;
2974     padding: 0.5ex 1em 0.5ex 1em ;
2975 /*     margin: 3ex 0em 2ex 0em ; */
2976     margin: 0 ;
2977     border-top: 1px solid silver ;
2978     border-bottom: 1px solid silver ;
2979     clear:both ;
2980 }
2981
2982
2983 header {
2984     line-height: 1.2 ;
2985     font-size: 1em ;
2986     border-bottom: 1px solid silver ;
2987     margin: 0px ;
2988     padding: 2ex 1em 2ex 1em ;
2989     text-align:left ;
2990 }
2991
2992
2993 footer {
2994     font-size: .85em ;
2995     line-height: 1.2 ;
2996     margin-top: 1ex ;
```

```
    border-top: 1px solid silver ;
    padding: 2ex 1em 2ex 1em ;
    clear:both ;
    text-align:left ;
}


a.linkhome { font-weight:bold ; font-size: 1em ;}


div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }

img.lateximage{
    padding: 0pt ;
    margin: 0pt ;
    box-shadow: none ;
    border: none ;
    background: none ;
    max-width: 100% ;
    border-radius: 0ex ;
    border: none ;
}


/* The -1px right margin compensates for the 1px right border. */
/* Without this -1px margin, the body container appears below instead */
/* of floating to the side. */
div.sidetoccontainer {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
        "Lucida Bright", Georgia, serif;
    float: left ;
    width: 20%;
    margin: 0pt -1px 3ex 0pt ;
    border-right: 1px solid silver;
    border-bottom: 1px solid silver;
    background: #FAF7F4 ;
    font-size:.9em ;
    border-radius: 0px 0px 20px 0px ;
}

div.sidetoccontents {
    overflow-y: auto ;
    width: 100% ;
    text-align: left ;
}


nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;
    text-indent: 0 ; }

nav.sidetoc p a {color:black ; font-size: .7em ;}

div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;
    border-bottom: 1px solid silver ;    }

```

```
nav.sidetoc a:hover {text-decoration: underline ; }


section.textbody { margin: 0ex 1em 0ex 1em ;}


div.multicolsheading { -webkit-column-span: all;
    -moz-column-span: all; column-span: all; }
div.multicols { -webkit-columns: 3 380px ;
    -moz-columns: 3 380px ; columns: 3 380px ; }
div.multicols p {margin-top: 0ex}


/* Used for xfrac and nicefrac: */
span.numerator {
    font-size: 60% ;
    vertical-align: .4em ;
}

span.denominator {
    font-size: 60%
}


/* Used for algorithm2e: */
div.alg2evline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
    border-radius: 0px 0px 0px 1ex ;
}

div.alg2evsline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
}

div.alg2enoline{
    margin-left: 1em ;
    padding-left: 1em ;
}

span.alg2elinenumber{
    margin-right: .5em ;
    font-size: 50% ;
    color: red ;
}


/* Used for algorithmicx: */
span.floatright { float: right ; }

```

```
/* keyfloat and tocdata: */
.floatnotes {
    margin: 0ex 5% 0ex 5% ;
    padding: 0ex 1em 0ex 1em ;
    font-size:.80em ;
    text-align: left ;
}

.authorartist{
    display:block ;
    font-size:.70em ;
    font-style: italic;
}

nav .authorartist{ display:inline; }



/* Native LaTeX theorems: */

.theoremcontents { font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ; }
.theoremlabel { font-style: normal; font-weight: bold ; margin-right: .5em ; }


/* theorem, amsthm, and ntheorem packages */

span.theoremheader,
span.theoremheaderplain,
span.theoremheaderdefinition,
span.theoremheaderbreak,
span.theoremheadermarginbreak,
span.theoremheaderchangebreak,
span.theoremheaderchange,
span.theoremheadermargin
{
    font-style:normal ; font-weight: bold ; margin-right: 1em ;
}

span.amsthmnameplain,
span.amsthmnamedefinition,
span.amsthmnumberplain,
span.amsthmnumberdefinition
{
    font-style:normal ; font-weight: bold ;
}


span.amsthmnameremark,
span.amsthmnumberremark
{font-style:italic ; font-weight: normal ; }


span.amsthmnoteplain,
span.amsthmnotedefinition
{font-style:normal ;}
```

```
3162
3163
3164 span.theoremheaderremark,
3165 span.theoremheaderproof,
3166 span.amsthmproofname
3167 {font-style:italic ; font-weight: normal ; margin-right: 1em ; }
3168
3169 span.theoremheadersc
3170 {
3171     font-style:normal ;
3172     font-variant: small-caps ;
3173     font-weight: normal ;
3174     margin-right: 1em ;
3175 }
3176
3177 .theoremendmark {float:right}
3178
3179 div.amsthmbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
3180 div.theorembodybreak, div.theorembodynonumberbreak,
3181 div.theorembodymarginbreak,
3182 div.theorembodychangebreak,
3183 div.theorembodychange,
3184 div.theorembodymargin
3185 {
3186     font-style:italic;
3187     margin-top: 3ex ; margin-bottom: 3ex ;
3188 }
3189
3190 div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
3191 div.theorembodyplainupright, nonumberplainuprightsc,
3192 div.amsthmbodydefinition, div.amsthmbodyremark,
3193 div.amsthmproof
3194 {
3195     font-style: normal ;
3196     margin-top: 3ex ; margin-bottom: 3ex ;
3197 }
3198
3199 span.amsthmnoteremark {}
3200
3201
3202 /* For the backnaur package: */
3203 div.backnaur {
3204     display: block ;
3205     margin: 2ex 2em 2ex 2em ;
3206 }
3207
3208 div.backnaur p {
3209     margin: .25ex 0ex .25ex 0ex ;
3210 }
3211
3212 div.backnaurprod {
3213     display: inline-block ;
3214     min-width: 8em ;
3215     text-align:right ;
3216 }
```

```
3217
3218 div.backnaurdesc {
3219     display: inline-block ;
3220 }
3221
3222
3223 /* For the notes package: */
3224 div.notesimportantnote, div.noteswarningnote, div.notesinformationnote {
3225     clear: both ;
3226     margin: 2ex 2em 2ex 2em ;
3227     border: 1px solid silver ;
3228 }
3229
3230 div.notesicon {
3231     float:left ;
3232     display: inline-block ;
3233     background: gold ;
3234     padding: 0ex 1em 0ex 1em ;
3235     margin-right: 1em ;
3236     font-weight: bold ;
3237 }
3238
3239 div.notescontents { font-style: italic }
3240
3241
3242 /*
3243 For CSS LaTeX and related logos:
3244 Based on spacing demonstrated by the metafont package.
3245 */
3246
3247 .latexlogofont {
3248     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3249         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3250     font-variant: normal ;
3251 }
3252
3253 .latexlogo {
3254     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3255         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3256     font-size: 1.1em;
3257 }
3258
3259 .latexlogosup {
3260   text-transform: uppercase;
3261   letter-spacing: .03em ;
3262   font-size: 0.7em;
3263   vertical-align: 0.25em;
3264   margin-left: -0.4em;
3265   margin-right: -0.15em;
3266 }
3267
3268 .latexlogosub {
3269   text-transform: uppercase;
3270   vertical-align: -0.27ex;
3271   margin-left: -0.08em;
```

```
  margin-right: -0.07em;
  font-size: 1em;
}

.latexlogotwoe {
  text-transform: none ;
  font-variant-numeric: oldstyle-nums ;
}

.latexlogotwoesub {
  font-style:italic ;
  vertical-align: -0.27ex;
  margin-left: -0.11em;
  margin-right: -0.1em;
  font-size: 1em;
}

.xelatexlogo {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    letter-spacing: .03em ;
    font-size: 1.1em;
}

.xelatexlogosub {
  vertical-align: -0.27ex;
  margin-left: -0.0667em;
  margin-right: -.05em;
  font-size: 1em;
  letter-spacing: .03em ;
}

.amslogo {
    font-family: "TeXGyreChorus","URW Chancery L",
        "Apple Chancery","ITC Zapf Chancery","Monotype Corsiva",
        "Linux Libertine O", "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif ;
    font-style: italic ;
}

.lyxlogo {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "DejaVu Sans", "Bitstream Vera Sans", Geneva,
        Verdana, sans-serif ;
}


/* Only display top and bottom navigation if a small screen: */
/* Hide the sidetoc if a small screen: */
nav.topnavigation { display:none; }
nav.botnavigation { display:none; }

/* Only display the sidetoc's webpage title if a small screen */
span.sidetocthetitle { display: none }

```

```
@media screen and (max-width: 50em) {
    div.sidetoccontainer {
        float: none ;
        width: 100% ;
        padding: 0 ;
        border-radius: 0 ;
        border-bottom: 1px solid black ;
        border-top: 1px solid black ;
        box-shadow: none ;
    }
    span.sidetocthetitle { display: inline }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
    .marginpar {
        max-width: 100%;
        float: none;
        display:block ;
        margin: 1ex 1em 1ex 1em ;
    }
}

@media print {
    body {
        font-family: "Linux Libertine O",
        "DejaVu Serif", "Bitstream Vera Serif",
        "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    }
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display: none; }
    nav.botnavigation { display: none; }
    div.bodycontainer { width: 100% }
}

@media handheld {
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display:block }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
}

@media projection {
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display:block }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
}
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.5 lwarp_sagebrush.css

File `lwarp_sagebrush.css` An optional css which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_sagebrush.css}
@import url("lwarp.css") ;


A:link {color:#105030 ; text-decoration: none ; }
A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}
A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}
A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}



div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif",
        "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif;
    font-variant: small-caps ;
    font-weight: normal ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
}

h1 {    /* title of the entire website, used on each page */
    font-variant: small-caps ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);
}

h1 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
}

h2 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #DAD0C0);
}



div.abstract {
    background: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

  border: 1px solid silver;
    border-radius: 1em ;
}
```

```
3430
3431 div.abstract dl {line-height:1.5;}
3432 div.abstract dt {color:#304070;}
3433
3434 div.abstracttitle{
3435     font-family: "URW Classico", Optima, "Linux Biolinum O",
3436         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3437         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3438     font-weight:bold;
3439     font-variant: small-caps ;
3440     font-size:1.5em;
3441     border-bottom: 1px solid silver ;
3442     color: #304070 ;
3443     text-align: center ;
3444     text-shadow: 1px 1px 2px #808080;
3445 }
3446
3447 span.abstractrunintitle{
3448     font-family: "URW Classico", Optima, "Linux Biolinum O",
3449         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3450         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3451     font-weight:bold;
3452 }
3453
3454
3455 div.epigraph, div.dictum {
3456     background: #f5f5eb ;
3457     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3458
3459     border: 1px solid silver ;
3460     border-radius: 1ex ;
3461     box-shadow: 3px 3px 3px #808080 ;
3462 }
3463
3464
3465 .example {
3466     background-color: #f5f5eb ;
3467     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3468
3469 }
3470
3471 div.exampletitle{
3472     font-family: "URW Classico", Optima, "Linux Biolinum O",
3473         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3474         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3475     font-weight:bold;
3476     font-variant: small-caps ;
3477     border-bottom: 1px solid silver ;
3478     color: #304070 ;
3479     text-align: center ;
3480     text-shadow: 1px 1px 2px #808080;
3481 }
3482
3483
3484 .sidebar {
```

```
3485     background-color: #f5f5eb ;
3486     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3487
3488 }
3489
3490 div.sidebartitle{
3491     font-family: "URW Classico", Optima, "Linux Biolinum O",
3492         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3493         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3494     font-weight:bold;
3495     font-variant: small-caps ;
3496     border-bottom: 1px solid silver ;
3497     color: #304070 ;
3498     text-align: center ;
3499     text-shadow: 1px 1px 2px #808080;
3500 }
3501
3502
3503 .fancyvrblabel {
3504     font-family: "URW Classico", Optima, "Linux Biolinum O",
3505         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3506         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3507     font-weight:bold;
3508     font-variant: small-caps ;
3509     font-size: 1.5em ;
3510     color: #304070 ;
3511     text-align: center ;
3512     text-shadow: 1px 1px 2px #808080;
3513 }
3514
3515 div.minipage {
3516     background-color: #eeeee7 ;
3517     border: 1px solid silver ;
3518     border-radius: 1ex ;
3519 }
3520
3521 table div.minipage { background: none ; border: none ; }
3522
3523 div.framebox div.minipage {border:none ; background:none}
3524
3525 section.textbody > div.minipage {
3526     box-shadow: 3px 3px 3px #808080 ;
3527 }
3528
3529 div.fboxBlock div.minipage { box-shadow: none ; }
3530
3531 .framed .minipage , .framedleftbar .minipage {
3532     border: none ;
3533     background: none ;
3534     padding: 0ex ;
3535     margin: 0ex ;
3536 }
3537
3538 figure.figure .minipage, div.figurecaption .minipage { border: none; }
3539
```

```
3540 div.marginblock div.minipage ,
3541 div.marginparblock div.minipage
3542     { border: none; }
3543
3544 figure , div.marginblock {
3545     background-color: #eeeee7 ;
3546     border: 1px solid silver ;
3547     border-radius: 1ex ;
3548     box-shadow: 3px 3px 3px #808080 ;
3549 }
3550
3551 figure figure {
3552     border: 1px solid silver ;
3553     margin: 0em ;
3554     box-shadow: none ;
3555 }
3556
3557 /*
3558 div.figurecaption {
3559     border-top: 1px solid silver ;
3560     border-bottom: 1px solid silver ;
3561     background-color: #e8e8e8 ;
3562 }
3563 */
3564
3565
3566 div.table {
3567     box-shadow: 3px 3px 3px #808080 ;
3568 }
3569
3570 /*
3571 .tnotes {
3572     background: #e8e8e8;
3573     border: 1px solid silver;
3574 }
3575 */
3576
3577
3578 nav.topnavigation{
3579     background-color: #b0b8b0 ;
3580     background-image: linear-gradient(to bottom,#e0e0e0,#b0b8b0) ;
3581 }
3582
3583 nav.botnavigation{
3584     background-color: #b0b8b0 ;
3585     background-image: linear-gradient(to top,#e0e0e0,#b0b8b0) ;
3586 }
3587
3588
3589
3590 header{
3591     background-color: #F7F7F0 ;
3592     background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
3593 }
3594
```

```
footer{
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
}



div.sidetoccontainer {
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
    box-shadow: 3px 3px 3px #808080 ;
    }

div.sidetoctitle {color: #304070 ; }

nav.sidetoc a:hover {
    color:#006000 ;
    text-decoration: none ;
    text-shadow:0px 0px 2px #a0a0a0;
}


@media screen and (max-width: 45em) {
    div.sidetoccontainer { border-radius: 0 ; }
}


\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.6 lwarp_formal.css

File lwarp_formal.css An optional CSS which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_formal.css}
@import url("lwarp.css") ;



A:link {color:#802020 ; text-decoration:none; }
A:visited {color:#802020 ; text-shadow:none ;}
A:hover {color:#400000 ; text-shadow:none ;}
A:active {color:#C00000 ; text-shadow:none ;}


body {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
```

```
3641         "Times New Roman", serif;
3642     background: #fffcf5;
3643 }
3644
3645 span.textrm {
3646     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3647         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3648         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3649         "Times New Roman", serif;
3650 }
3651
3652 span.textsf {
3653      font-family: "DejaVu Sans", "Bitstream Vera Sans",
3654         Geneva, Verdana, sans-serif ;
3655 }
3656
3657
3658
3659 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
3660 {
3661     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3662         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3663         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3664         "Times New Roman", serif;
3665     color: #800000 ;
3666     text-shadow: none ;
3667 }
3668
3669 h1, h2 {
3670     background-color: #fffcf5 ;
3671     background-image: none ;
3672     border-bottom: 1px solid #808080;
3673 /*    border-top: 2px solid #808080; */
3674 }
3675
3676 div.abstracttitle {
3677     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3678         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3679         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3680         "Times New Roman", serif;
3681     color: black ;
3682     text-shadow: none ;
3683 }
3684
3685 span.abstractrunintitle {
3686     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3687         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3688         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3689         "Times New Roman", serif;
3690     color: black ;
3691     text-shadow: none ;
3692 }
3693
3694 div.abstract { font-size: 100% }
3695
```

```
.sidebar {
    background: #fffcf5;
    background-image: none ;
  margin: 2em 5% 2em 5%;
  padding: 0.5em 1em;
  border: none ;
  border-top : 1px solid silver;
  border-bottom : 1px solid silver;
  font-size: 90% ;
}

div.sidebartitle{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}

.example {
    background: #fffcf5;
    background-image: none ;
  margin: 2em 5% 2em 5%;
  padding: 0.5em 1em;
  border: none ;
  border-top : 1px solid silver;
  border-bottom : 1px solid silver;
}

div.exampletitle{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}

div.fancyvrblabel{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}



figure {
    margin: 5ex 5% 5ex 5% ;
```

```
3751     padding: 1ex 1em 1ex 1em ;
3752     background-color: #fffcf5 ;
3753     overflow-x: auto ;
3754     border: none ;
3755 /*     border-top: 1px solid silver; */
3756 /*     border-bottom: 1px solid silver; */
3757 }
3758
3759
3760 div.figurecaption , .lstlisting {
3761     border: none ;
3762 /*     border-top: 1px solid silver ; */
3763 /*     border-bottom: 1px solid silver ; */
3764     background-color: #fffcf5 ;
3765 }
3766
3767 .tnotes {
3768     background: #fffcf5 ;
3769     border-top: 1px solid silver ;
3770     border-bottom: 1px solid silver ;
3771 }
3772
3773 .theorem {
3774         background: none ;
3775 }
3776
3777 .minipage {
3778     background-color: #fffcf5 ;
3779     border: none ;
3780 }
3781
3782 div.floatrow figure { border: none ; }
3783
3784 figure figure { border: none ; }
3785
3786
3787 nav.toc, nav.lof, nav.lot, nav.lol {
3788     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3789         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3790         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3791         "Times New Roman", serif;
3792 }
3793
3794 div.sidetoccontainer {
3795     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3796         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3797         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3798         "Times New Roman", serif;
3799     background-image: linear-gradient(to bottom, #fffcf5, #C0C0C0);
3800 }
3801
3802 div.sidetoctitle{
3803     color: #800000 ;
3804 }
3805
```

```
header{
    background-color: #e0e0e0 ;
    background-image: linear-gradient(to top, #fffcf5, #b0b0b0);
    text-align:center ;
}

footer{
    background-color: #e0e0e0 ;
    background-image: linear-gradient(to bottom, #fffcf5, #b0b0b0);
    padding: 2ex 1em 2ex 1em ;
    text-align:left ;
}

nav.botnavigation {
    background: #dedcd5 ;
    border-top: 1px solid black ;
}
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.7 sample_project.css

File sample_project.css The project-specific css file. Use with \CSSFilename.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{sample_project.css}
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.8 lwarp.ist

File lwarp.ist Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The page compositor line is for memoir's \specialindex.

Config file:
```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.ist}
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
      \\par\\textbf{#1}\\par
      \\nopagebreak
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 ", \\hyperindexref{"
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"
page_compositor "."
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.9 lwarp.xdy

File lwarp.xdy Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

See:
https://tex.stackexchange.com/questions/80300/how-can-i-convince-hyperref-and-xindy-to-play-together-nicely

Config file:
```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.xdy}
(require "tex/inputenc/latin.xdy")
(merge-rule "\\PS *" "Postscript")
(require "texindy.xdy")
(require "page-ranges.xdy")
(require "book-order.xdy")
(define-location-class "arabic-page-numbers"
    ("arabic-numbers") :min-range-length 1)
(require "makeindex.xdy")
(define-attributes (("hyperindexref")))
(markup-locref :open "\hyperindexref{" :close "}")
(markup-locref :open "\hyperindexref{" :close "}" :attr "hyperpage")
(markup-locref :open "\textbf{\hyperindexref{" :close "}}" :attr "textbf")
(markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
(define-location-class-order ("roman-page-numbers"
```

```
                    "arabic-page-numbers"
                    "alpha-page-numbers"
                    "Roman-page-numbers"
                    "Alpha-page-numbers"
                    "see"
                    "seealso"))
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.10 lwarp_one_limage.cmd

File lwarp_one_limage.cmd

Used by lwarp to help make lateximages when using WINDOWS.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The arguments are each of the three fields from <project>-images.txt, and also the base name of the source file.

MiKTeX does not allow file lwarp_one_limage.cmd to be created directly by *lwarpmk*, so lwarp_one_limage.txt is created instead, then copied to lwarp_one_limage.cmd by *lwarpmk*. This occurs each time *lwarpmk* used to create lateximages.

Config file:

```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=lwarp_one_limage.txt
\immediate\write\LWR@quickfile{%
    pdfseparate -f \LWRpercent 1 -l \LWRpercent 1 \LWRpercent 4_html.pdf %
   \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent\LWRpercent d.pdf%
}
\immediate\write\LWR@quickfile{%
   pdfcrop --hires  \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
   pdftocairo  -svg -noshrink  \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.svg%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf%
}
\immediate\write\LWR@quickfile{exit}
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.11 lwarp_mathjax.txt

File lwarp_mathjax.txt

The default MathJax script used by lwarp when using MATHJAX. A recent version of

MathJax is used, as served by the recommended repository. Adjustments are made to allow LaTeX to control the equation tags.

\MathJaxFilename determines which script file is copied into the HTML pages, and defaults to lwarp_mathjax.txt. The script files must be present when compiling the project, but do not need to be present when distributing the resulting HTML files.

custom script To generate a custom script, such as to use a local repository, copy lwarp_mathjax.txt to a new file, make changes while keeping lwarp's adjustments for equation numbering, and use \MathJaxFilename to select new filename.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_mathjax.txt}
<!-- https://groups.google.com/forum/#!topic/
                                mathjax-users/jUtewUcE2bY -->
<script type="text/x-mathjax-config">
MathJax.Hub.Register.StartupHook("TeX AMSmath Ready",function () {
    var seteqsectionDefault = {name: "", num: 0};
    var seteqsections = {}, seteqsection = seteqsectionDefault;
    var TEX = MathJax.InputJax.TeX, PARSE = TEX.Parse;
    var AMS = MathJax.Extension["TeX/AMSmath"];
    TEX.Definitions.Add({
    macros: {
        seteqsection: "mySection",
        seteqnumber: "mySetEqNumber"
    }
    });

    PARSE.Augment({
    mySection: function (name) {
        seteqsection.num = AMS.number;
        var n = this.GetArgument(name);
        if (n === "") {
            seteqsection = seteqsectionDefault;
        } else {
            if (!seteqsections["_"+n])
                seteqsections["_"+n] = {name:n, num:0};
            seteqsection = seteqsections["_"+n];
        }
        AMS.number = seteqsection.num;
    },
    mySetEqNumber: function (name) {
        var n = this.GetArgument(name);
        if (!n || !n.match(/^ *[0-9]+ *$/))
            n = "";
        else
            n = parseInt(n)-1;
        <!-- $ syntax highlighting -->
        if (n === "" || n < 1)
            TEX.Error
            ("Argument to "+name+" should be a positive integer");
        AMS.number = n;
    }
    });
    MathJax.Hub.Config({
```

```
    TeX: {
        equationNumbers: {
            formatTag: function (n) {
                <!-- if not numeric, don't include the chapter -->
                if (!n.match(/^ *[0-9]+ *$/ ))
                <!-- $ syntax highlighting -->
                    return "("+(n).replace(/^\./,"")+")" ;
                else
                  return "("+(seteqsection.name+"."+n).replace(/^\./,"")+")" ;
            },
            formatID: function (n) {
                n = (seteqsection.name+'.'+n).replace
                    (/[:"'<>&]/g,"").replace(/^\./,"");
                return 'mjx-eqn-' + n;
            }
        }
    }
    });
});
</script>

<!-- http://docs.mathjax.org/en/latest/options/ThirdParty.html -->
<script type="text/x-mathjax-config">
  MathJax.Ajax.config.path["Contrib"] =
    "https://cdn.mathjax.org/mathjax/contrib";
</script>

<script type="text/x-mathjax-config">
MathJax.Hub.Config({
    TeX: {
        extensions: ["autoload-all.js"] ,
        equationNumbers: {
            autoNumber: "AMS"
        }
    }
});
</script>

<!-- Alternative CDN provider: -->
<script type="text/javascript" async
src="https://cdnjs.cloudflare.com/ajax/libs/mathjax/2.7.6/MathJax.js?config=TeX-AMS_HTML-full">
</script>

<!-- No longer supported after April 30, 2017: -->
<!--
<script
 src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-AMS_HTML-full">
</script>
-->

\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.12 `lwarpmk.lua` — `lwarpmk` option

Opt `lwarpmk` Creates a local copy of *lwarpmk*.

Prog `lwarpmk` Command-line utility to process lwarp files and images.

parallel processing `lateximages` and SVG math images are generated using multiple processes in parallel. For UNIX and LINUX, every 32 images the `wait` command is issued to wait for the previous batch of images to finish processing before starting a new batch. For WINDOWS, every 32 images one task is dispatched with

```
START /B /WAIT /BELOWNORMAL
```

which causes the operating system to wait until this lesser-priority tasks finishes, hopefully also waiting for the normal priority tasks which were already in progress to also complete. Afterwards, the next batch of images is started.

The following is only generated if the `lwarpmk` option was given to lwarp.

```
\begin{LWR@createlwarpmk}

\begin{filecontents*}{lwarpmk.lua}
#!/usr/bin/env texlua

-- Copyright 2016-2019 Brian Dunn


printversion = "v0.76"
requiredconfversion = "2" -- also at *lwarpmk.conf

function printhelp ()
print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help.") ;
end


function printusage ()
--
-- Print the usage of the lwarpmk command:
--
print ( [[

lwarpmk print [-p project]: Compile the print version if necessary.
lwarpmk print1 [-p project]: Forced single compile of the print version.
lwarpmk printindex [-p project]: Process print indexes.
lwarpmk printglossary [-p project]: Process the glossary for the print version.
lwarpmk html [-p project]: Compile the HTML version if necessary.
lwarpmk html1 [-p project]: Forced single compile of the HTML version.
lwarpmk htmlindex [-p project]: Process HTML indexes.
lwarpmk htmlglossary [-p project]: Process the glossary for the html version.
lwarpmk again [-p project]: Touch the source code to trigger recompiles.
lwarpmk limages [-p project]: Process the "lateximages" created by lwarp.sty.
lwarpmk pdftohtml [-p project]:
    For use with latexmk or a Makefile:
    Converts project_html.pdf to project_html.html and individual HTML files.
    Finishes the HTML conversion even if there was a compile error.
```

```
lwarpmk pdftosvg <list of file names>: Converts each PDF file to SVG.
lwarpmk epstopdf <list of file names>: Converts each EPS file to PDF.
lwarpmk clean [-p project]: Remove *.aux, *.toc, *.lof/t,
    *.idx, *.ind, *.log, *_html_inc.*, .gl*,
    *_html.pdf, *_html.html, *_html.sidetoc
lwarpmk cleanall [-p project]: Remove auxiliary files, project.pdf, *.html
lwarpmk cleanlimages: Removes all images from the "lateximages" directory.
lwarpmk -h: Print this help message.
lwarpmk --help: Print this help message.

]] )
-- printconf ()
end


function splitfilename ( pathandfilename )
--
-- Separates out the path and extension from a filename.
-- Returns path, filename with extension, and extension.
-- Ex: thispath, thisfilename, thisextension = splitfilename ("path/to/filename.ext")
--
-- https://www.fhug.org.uk/wiki/wiki/doku.php?id=plugins:code_snippets:
--      split_filename_in_to_path_filename_and_extension
--
    if lfs.attributes(pathandfilename,"mode") == "directory" then
      local strPath = pathandfilename:gsub("[\\/]$","") -- $ (syntax highlighting)
        return strPath.."\\","",""
    end
    pathandfilename = pathandfilename.."."
    return pathandfilename:match("^(.-)([^\\/]-)%.([^\\/%.]-)%.?$")
end


function splitfile (destfile,sourcefile)
--
-- Split one large sourcefile into a number of files,
-- starting with destfile.
-- The file is split at each occurance of <!--|Start file|newfilename|*
--
print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
local sfile = io.open(sourcefile)
io.output(destfile)
for line in sfile:lines() do
i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*)|") ;
if ( (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then
    -- split the file
    io.output(newfilename) ;
else
    -- not a splitpoint
    io.write (line .. "\n") ;
end
end -- do
io.close(sfile)
end -- function

```

```
4102
4103 function cvalueerror ( line, linenum , cvalue )
4104 --
4105 -- Incorrect value, so print an error and exit.
4106 --
4107     print ("lwarpmk: ===")
4108     print ("lwarpmk: " .. linenum .. " : " .. line ) ;
4109     print (
4110         "lwarpmk: incorrect variable value \"" .. cvalue ..
4111         "\" in lwarpmk.conf.\n"
4112     ) ;
4113     print ("lwarpmk: ===")
4114 --    printconf () ;
4115     os.exit(1) ;
4116 end
4117
4118
4119 function printhowtorecompile ()
4120 -- Tells the user how to recompile to regenerate the configuration files.
4121   print ("lwarpmk: The configuration files lwarpmk.conf and "..sourcename..".lwarpmkconf" )
4122     print ("lwarpmk:   must be updated.  To do so, recompile" )
4123     print ("lwarpmk:   " , sourcename..".tex" )
4124     if ( printlatexcmd == "" ) then
4125         print ("lwarpmk:   using xe/lua/pdflatex," )
4126     else
4127         print ("lwarpmk:   using the command:")
4128         print ("lwarpmk:   " , printlatexcmd )
4129     end
4130     print ("lwarpmk:   then use lwarpmk again.")
4131 end -- printhowtorecompile
4132
4133
4134 function ignoreconf ()
4135 -- Global argument index
4136 argindex = 2
4137 end
4138
4139 function loadconf ()
4140 --
4141 -- Load settings from the project's "lwarpmk.conf" file:
4142 --
4143 -- Default configuration filename:
4144 local conffile = "lwarpmk.conf"
4145 local confroot = "lwarpmk"
4146 -- Global argument index
4147 argindex = 2
4148 -- Optional configuration filename:
4149 if ( arg[argindex] == "-p" ) then
4150     argindex = argindex + 1
4151     confroot = arg[argindex]
4152     conffile = confroot..".lwarpmkconf"
4153     argindex = argindex + 1
4154 end
4155 -- Additional defaults:
4156 confversion = "0"
```

```
opsystem = "Unix"
imagesdirectory = "lateximages"
imagesname = "image-"
latexmk = "false"
printlatexcmd = ""
HTMLlatexcmd = ""
printindexcmd = ""
HTMLindexcmd = ""
latexmkindexcmd = ""
-- to be removed:
-- indexprog = "makeindex"
-- makeindexstyle = "lwarp.ist"
-- xindylanguage = "english"
-- xindycodepage = "utf8"
-- xindystyle = "lwarp.xdy"
-- pdftotextenc = "UTF-8"
glossarycmd = "makeglossaries"
-- Verify the file exists:
if (lfs.attributes(conffile,"mode")==nil) then
    -- file not exists
    print ("lwarpmk: ===")
    print ("lwarpmk: File \"" .. conffile .."\" does not exist.")
    print ("lwarpmk: Move to the project's source directory,")
    print ("lwarpmk: recompile using pdflatex, xelatex, or lualatex,")
    print ("lwarpmk: then try using lwarpmk again.")
    if ( arg[argindex] ~= nil ) then
        print (
            "lwarpmk: (\"" .. confroot ..
            "\" does not appear to be a project name.)"
        )
    end
    print ("lwarpmk: ===")
    printhelp () ;
    os.exit(1) -- exit the entire lwarpmk script
else -- file exists
-- Read the file:
print ("lwarpmk: Reading " .. conffile ..".")
local cfile = io.open(conffile)
-- Scan each line, parsing each line as: name = [[string]]
local linenum = 0
for line in cfile:lines() do -- scan lines
linenum = linenum + 1
i,j,cvarname,cvalue = string.find (line,"([%w-_]*)%s*=%s*%[%[([^%]]*)%]%]") ;
-- Error if incorrect enclosing characters:
if ( i == nil ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: " ..  linenum .. " : " .. line ) ;
    print ("lwarpmk: Incorrect entry in " .. conffile ..".\n" ) ;
    print ("lwarpmk: ===")
--    printconf () ;
    os.exit(1) ;
end -- nil
if ( cvarname == "confversion" ) then
    confversion = cvalue
elseif ( cvarname == "opsystem" ) then
```

```
4212     -- Verify choice of opsystem:
4213     if ( (cvalue == "Unix") or (cvalue == "Windows") ) then
4214         opsystem = cvalue
4215     else
4216         cvalueerror ( line, linenum , cvalue )
4217     end
4218 elseif ( cvarname == "sourcename" ) then sourcename = cvalue
4219 elseif ( cvarname == "homehtmlfilename" ) then homehtmlfilename = cvalue
4220 elseif ( cvarname == "htmlfilename" ) then htmlfilename = cvalue
4221 elseif ( cvarname == "imagesdirectory" ) then imagesdirectory = cvalue
4222 elseif ( cvarname == "imagesname" ) then imagesname = cvalue
4223 elseif ( cvarname == "latexmk" ) then latexmk = cvalue
4224 elseif ( cvarname == "printlatexcmd" ) then printlatexcmd = cvalue
4225 elseif ( cvarname == "HTMLlatexcmd" ) then HTMLlatexcmd = cvalue
4226 elseif ( cvarname == "printindexcmd" ) then printindexcmd = cvalue
4227 elseif ( cvarname == "HTMLindexcmd" ) then HTMLindexcmd = cvalue
4228 elseif ( cvarname == "latexmkindexcmd" ) then latexmkindexcmd = cvalue
4229 elseif ( cvarname == "glossarycmd" ) then glossarycmd = cvalue
4230 elseif ( cvarname == "pdftotextenc" ) then pdftotextenc = cvalue
4231 else
4232     print ("lwarpmk: ===")
4233     print ("lwarpmk: " .. linenum .. " : " .. line ) ;
4234     print (
4235         "lwarpmk: Incorrect variable name \"" .. cvarname .. "\" in " ..
4236         conffile ..".\n"
4237     ) ;
4238     print ("lwarpmk: ===")
4239 --    printconf () ;
4240 os.exit(1) ;
4241 end -- cvarname
4242 end -- do scan lines
4243 io.close(cfile)
4244 end -- file exists
4245 -- Error if sourcename is "lwarp".
4246 -- This could happen if a local copy of lwarp has recently been recompiled.
4247 if sourcename=="lwarp" then
4248     print ("lwarpmk: ===")
4249    print ("lwarpmk: lwarp.sty has recently been recompiled in this directory,")
4250    print ("lwarpmk: and \"lwarpmk.conf\" is no longer set for your own project.")
4251   print ("lwarpmk: Recompile your own project using pdf/lua/xelatex <projectname>.")
4252   print ("lwarpmk: After a recompile, \"lwarpmk.conf\" will be set for your project,")
4253     print ("lwarpmk: and you may again use lwarpmk.")
4254     print ("lwarpmk: ===")
4255     os.exit(1)
4256 end -- sourcename of "lwarp"
4257 -- Select some operating-system commands:
4258 if opsystem=="Unix" then  -- For Unix / Linux / Mac OS:
4259     rmname = "rm"
4260     mvname = "mv"
4261     cpname = "cp"
4262     touchnamepre = "touch"
4263     touchnamepost = ""
4264     newtouchname = "touch"
4265     dirslash = "/"
4266     opquote= "\'"
```

```
4267     cmdgroupopenname = " ( "
4268     cmdgroupclosename = " ) "
4269     seqname = " && "
4270     bgname = " &"
4271 elseif opsystem=="Windows" then -- For Windows
4272     rmname = "DEL"
4273     mvname = "MOVE"
4274     cpname = "COPY"
4275     touchnamepre = "COPY /b"
4276     touchnamepost = "+,,"
4277     newtouchname = "echo empty >"
4278     dirslash = "\\"
4279     opquote= "\""
4280     cmdgroupopenname = ""
4281     cmdgroupclosename = ""
4282     seqname = " & "
4283     bgname = ""
4284 else
4285     print ("lwarpmk: ===")
4286     print ("lwarpmk: Select Unix or Windows for opsystem." )
4287     print ("lwarpmk: ===")
4288     os.exit(1)
4289 end --- for Windows
4290 -- Warning if the operating system does not appear to be correct,
4291 -- in case files were transferred to another system.
4292 if ( (package.config:sub(1,1)) ~= dirslash ) then
4293     print ("lwarpmk: ===")
4294    print ("lwarpmk: It appears that lwarpmk.conf is for a different operating system." )
4295     printhowtorecompile ()
4296     print ("lwarpmk: ===")
4297     os.exit(1)
4298 end
4299 -- Error if the configuration file's version is not current:
4300 if ( confversion ~= requiredconfversion ) then
4301     print ("lwarpmk: ===")
4302     printhowtorecompile ()
4303     print ("lwarpmk: ===")
4304     os.exit(1)
4305 end
4306 end -- loadconf
4307
4308
4309 function executecheckerror ( executecommands , errormessage )
4310 --
4311 -- Execute an operating system call,
4312 -- and maybe exit with an error message.
4313 --
4314 local err
4315 err = os.execute ( executecommands )
4316 if ( err ~= 0 ) then
4317     print ("lwarpmk: ===")
4318     print ("lwarpmk: " .. errormessage )
4319     print ("lwarpmk: ===")
4320     os.exit(1)
4321 end
```

```
4322 end -- executecheckerror
4323
4324
4325 function refreshdate ()
4326 os.execute(touchnamepre .. " " .. sourcename .. ".tex " .. touchnamepost)
4327 end
4328
4329
4330
4331 function reruntoget (filesource)
4332 --
4333 -- Scan the LaTeX log file for the phrase "Rerun to get",
4334 -- indicating that the file should be compiled again.
4335 -- Return true if found.
4336 --
4337 local fsource = io.open(filesource)
4338 for line in fsource:lines() do
4339 if ( string.find(line,"Rerun to get") ~= nil ) then
4340     io.close(fsource)
4341     return true
4342 end -- if
4343 end -- do
4344 io.close(fsource)
4345 return false
4346 end
4347
4348
4349
4350 function onetime (latexcmd, fsuffix)
4351 --
4352 -- Compile one time, return true if should compile again.
4353 -- fsuffix is "" for print, "_html" for HTML output.
4354 --
4355 print("lwarpmk: Compiling with: " .. latexcmd)
4356 executecheckerror (
4357     latexcmd ,
4358     "Compile error."
4359 )
4360 return (reruntoget(sourcename .. fsuffix .. ".log") ) ;
4361 end
4362
4363
4364 function manytimes (latexcmd, fsuffix)
4365 --
4366 -- Compile up to five times.
4367 -- fsuffix is "" for print, "_html" for HTML output
4368 --
4369 if onetime(latexcmd, fsuffix) == true then
4370 if onetime(latexcmd, fsuffix) == true then
4371 if onetime(latexcmd, fsuffix) == true then
4372 if onetime(latexcmd, fsuffix) == true then
4373 if onetime(latexcmd, fsuffix) == true then
4374 end end end end end
4375 end
4376
```

```
4377
4378 function verifyfileexists (filename)
4379 --
4380 -- Exit if the given file does not exist.
4381 --
4382 if (lfs.attributes ( filename , "modification" ) == nil ) then
4383     print ("lwarpmk: ===")
4384     print ("lwarpmk: " .. filename .. " not found." ) ;
4385     print ("lwarpmk: ===")
4386     os.exit (1) ;
4387 end
4388 end
4389
4390
4391
4392 function pdftohtml ()
4393 --
4394 -- Convert <project>_html.pdf into HTML files:
4395 --
4396 -- Convert to text:
4397 print ("lwarpmk: Converting " .. sourcename
4398     .."_html.pdf to " .. sourcename .. "_html.html")
4399 os.execute("pdftotext  -enc " .. pdftotextenc .. "  -nopgbrk  -layout "
4400     .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
4401 -- Split the result into individual HTML files:
4402 splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
4403 end
4404
4405
4406 function removeaux ()
4407 --
4408 -- Remove auxiliary files:
4409 -- All .aux files are removed since there may be many bbl*.aux files.
4410 -- Also removes sourcename_html.pdf, sourcename_html.html,
4411 -- and sourcename_html.sidetoc.
4412 --
4413 os.execute ( rmname .. " *.aux " ..
4414     sourcename ..".toc " .. sourcename .. "_html.toc " ..
4415     sourcename ..".lof " .. sourcename .. "_html.lof " ..
4416     sourcename ..".lot " .. sourcename .. "_html.lot " ..
4417     " *.idx " ..
4418     " *.ind " ..
4419     sourcename ..".ps " .. sourcename .."_html.ps " ..
4420     sourcename ..".log " .. sourcename .. "_html.log " ..
4421     sourcename ..".gl* " .. sourcename .. "_html.gl* " ..
4422     sourcename .. "_html.pdf " ..
4423     sourcename .. "_html.html " ..
4424     sourcename .. "_html.sidetoc " ..
4425     " *_html_inc.* "
4426     )
4427 end
4428
4429 function checkhtmlpdfexists ()
4430 --
4431 -- Error if the HTML document does not exist.
```

```
-- The lateximages are drawn from the HTML PDF version of the document,
-- so "lwarpmk html" must be done before "lwarpmk limages".
--
local htmlpdffile = io.open(sourcename .. "_html.pdf", "r")
if ( htmlpdffile == nil ) then
    print ("")
    print ("lwarpmk: ===")
    print ("lwarpmk: The HTML version of the document does not exist.")
    print ("lwarpmk: Enter \"lwarpmk html\" to compile the HTML version.")
    print ("lwarpmk: ===")
    os.exit(1)
end
io.close (htmlpdffile)
end -- checkhtmlpdfexists


function warnlimages ()
--
-- Warning of a missing <sourcename>-images.txt file:
    print ("lwarpmk: ===")
    print ("lwarpmk: \"" .. sourcename .. "-images.txt\" does not exist.")
    print ("lwarpmk: Your project does not use SVG math or other lateximages,")
    print ("lwarpmk: or the file has been deleted somehow.")
    print ("lwarpmk: Use \"lwarpmk html1\" to recompile your project")
    print ("lwarpmk: and recreate \"" .. sourcename .. "-images.txt\".")
   print ("lwarpmk: If your project does not use SVG math or other lateximages,")
   print ("lwarpmk: then \"" .. sourcename .. "-images.txt\" will never exist, and")
    print ("lwarpmk: \"lwarpmk limages\" will not be necessary.")
    print ("lwarpmk: ===")
end -- warnlimages


function warnlimagesrecompile ()
-- Warning if must recompile before creating limages:
    print ("")
    print ("lwarpmk: ===")
    print ("lwarpmk: Cross-references are not yet correct.")
   print ("lwarpmk: The document must be recompiled before creating the lateximages.")
   print ("lwarpmk: Enter \"lwarpmk html1\" again, then try \"lwarpmk limages\" again.")
    print ("lwarpmk: ===")
end --warnlimagesrecompile


function checklimages ()
--
-- Check <sourcename>.txt to see if need to recompile first.
-- If any entry has a page number of zero, then there were incorrect images.
--
print ("lwarpmk: Checking for a valid " .. sourcename .. "-images.txt file.")
local limagesfile = io.open(sourcename .. "-images.txt", "r")
if ( limagesfile == nil ) then
    warnlimages ()
    os.exit(1)
end
-- Track warning to recompile if find a page 0
```

```
local pagezerowarning = false
-- Scan <sourcename>.txt
for line in limagesfile:lines() do
    -- lwimgpage is the page number in the PDF which has the image
    -- lwimghash is true if this filename is a hash
    -- lwimgname is the lateximage filename root to assign for the image
    i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
    -- For each entry:
    if ( (i~=nil) ) then
        -- If the page number is 0, image references are incorrect
        --  and must recompile the soure document:
        if ( lwimgpage == "0" ) then
            pagezerowarning = true
        end
    end -- if i~=nil
end -- do
-- The last line should be |end|end|end|.
-- If not, the compile must have aborted, and the images are incomplete.
if ( lwimgpage ~= "end" ) then
    warnlimagesrecompile()
    os.exit(1) ;
end
if ( pagezerowarning ) then
    warnlimagesrecompile()
    os.exit(1) ;
end -- pagezerowarning
end -- checklimages


function createuniximage ( lwimgfullname )
--
-- Create one lateximage for Unix / Linux / Mac OS.
--
executecheckerror (
    cmdgroupopenname ..
    "pdfseparate -f " .. lwimgpage .. " -l " .. lwimgpage .. " " ..
        sourcename .."_html.pdf " ..
        imagesdirectory .. dirslash .."lateximagetemp-%d" .. ".pdf" ..
        seqname ..
    -- Crop the image:
    "pdfcrop  --hires  " .. imagesdirectory .. dirslash .. "lateximagetemp-" ..
        lwimgpage .. ".pdf " ..
        imagesdirectory .. dirslash .. lwimgname .. ".pdf" ..
        seqname ..
    -- Convert the image to svg:
   "pdftocairo -svg -noshrink " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf " ..
        imagesdirectory .. dirslash .. lwimgname ..".svg" ..
        seqname ..
    -- Remove the temporary files:
   rmname .. " " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf" .. seqname ..
   rmname .. " " .. imagesdirectory .. dirslash .. "lateximagetemp-" .. lwimgpage .. ".pdf" ..
    cmdgroupclosename .. " >/dev/null " .. bgname
    ,
    "File error trying to convert " .. lwimgfullname
)
```

```
-- Every 32 images, wait for completion at below normal priority,
--  allowing other image tasks to catch up.
numimageprocesses = numimageprocesses + 1
if ( numimageprocesses > 32 ) then
    numimageprocesses = 0
    print ( "lwarpmk: waiting" )
    executecheckerror ( "wait" , "File error trying to wait.")
end
end -- createuniximage


function createwindowsimage ( lwimgfullname )
--
-- Create one lateximage for Windows.
--
-- Every 32 images, wait for completion at below normal priority,
--  allowing other image tasks to catch up.
numimageprocesses = numimageprocesses + 1
if ( numimageprocesses > 32 ) then
    numimageprocesses = 0
    thiswaitcommand = "/WAIT /BELOWNORMAL"
    print ( "lwarpmk: waiting" )
else
    thiswaitcommand = ""
end
-- Execute the image generation command
executecheckerror (
    "start /B " .. thiswaitcommand .. " \"\" lwarp_one_limage " ..
    lwimgpage .. " " ..
    lwimghash .. " " ..
    lwimgname .. " " ..
    sourcename .. " <nul >nul"
    ,
    "File error trying to create image."
)
end -- createwindowsimage


function createonelateximage ( line )
--
-- Given the next line of <sourcename>.txt, convert a single image.
--
-- lwimgpage is the page number in the PDF which has the image
-- lwimghash is true if this filename is a hash
-- lwimgname is the lateximage filename root to assign for the image
i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
-- For each entry:
if ( (i~=nil) ) then
    -- Skip if the page number is 0:
    if ( lwimgpage == "0" ) then
        pagezerowarning = true
    -- Skip if the page number is "end":
    else if ( lwimgpage == "end" ) then
    else
        -- Skip is this image is hashed and already exists:
```

```
4597        local lwimgfullname = imagesdirectory .. dirslash .. lwimgname .. ".svg"
4598         if (
4599             (lwimghash ~= "true") or
4600             (lfs.attributes(lwimgfullname,"mode")==nil) -- file not exists
4601         )
4602         then -- not hashed or not exists:
4603             -- Print the name of the file being generated:
4604             print ( "lwarpmk: " .. lwimgname )
4605           -- Touch/create the dest so that only once instance tries to build it:
4606             executecheckerror (
4607                 newtouchname .. " " .. lwimgfullname ,
4608                 "File error trying to touch " .. lwimgfullname
4609             )
4610             -- Separate out the image into its own single-page pdf:
4611             if opsystem=="Unix" then
4612                 createuniximage (lwimgfullname)
4613             elseif opsystem=="Windows" then
4614                 createwindowsimage (lwimgfullname)
4615             end
4616         end -- not hashed or not exists
4617     end -- not page "end"
4618     end -- not page 0
4619 end -- not nil
4620 end -- createonelateximage
4621
4622
4623 function createlateximages ()
4624 --
4625 -- Create lateximages based on <sourcename>-images.txt:
4626 --
4627 -- See if the document must be recompiled first:
4628 checklimages ()
4629 -- See if the HTML version exists:
4630 checkhtmlpdfexists ()
4631 -- Attempt to create the lateximages:
4632 print ("lwarpmk: Creating lateximages.")
4633 local limagesfile = io.open(sourcename .. "-images.txt", "r")
4634 if ( limagesfile == nil ) then
4635     warnlimages ()
4636     os.exit(1)
4637 end
4638 -- Create the lateximages directory, ignore error if already exists
4639 err = os.execute("mkdir " .. imagesdirectory)
4640 -- For Windows, create lwarp_one_limage.cmd from lwarp_one_limage.txt:
4641 if opsystem=="Windows" then
4642     executecheckerror (
4643         cpname .. " lwarp_one_limage.txt lwarp_one_limage.cmd" ,
4644        "File error trying to copy lwarp_one_limage.txt to lwarp_one_limage.cmd"
4645     )
4646 end -- create lwarp_one_limage.cmd
4647 -- Track the number of parallel processes
4648 numimageprocesses = 0
4649 -- Track warning to recompile if find a page 0
4650 pagezerowarning = false
4651 -- Scan <sourcename>.txt
```

```
for line in limagesfile:lines() do
    createonelateximage ( line )
end -- do
io.close(limagesfile)
print ( "lwarpmk limages: ===")
print ( "lwarpmk limages: Wait a moment for the images to complete" )
print ( "lwarpmk limages:   before reloading the page." )
print ( "lwarpmk limages: ===")
print ( "lwarpmk limages: Done." )
if ( pagezerowarning == true ) then
    print ( "lwarpmk limages: WARNING: Images will be incorrect." )
    print ( "lwarpmk limages:   Enter \"lwarpmk cleanlimages\", then" )
    print ( "lwarpmk limages:   recompile the document one more time, then" )
    print ( "lwarpmk limages:   repeat \"lwarpmk images\" again." )
end -- pagezerowarning
end -- function


function convertepstopdf ()
--
-- Converts EPS files to PDF files.
-- The filenames are arg[argindex] and up.
-- arg[1] is the command "epstopdf".
--
ignoreconf ()
for i = argindex , #arg do
    if (lfs.attributes(arg[i],"mode")==nil) then
        print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
    else
        print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
        thispath, thisfilename, thisextension = splitfilename(arg[i])
        if ( thispath == nil ) then
            os.execute ( "epstopdf " .. arg[i] )
        else
            os.execute (
                "epstopdf " ..
                thispath .. thisfilename .. "." .. thisextension .. " " ..
                thispath .. thisfilename .. ".pdf"
            )
        end
    end -- if
end -- do
end --function


function convertpdftosvg ()
--
-- Converts PDF files to SVG files.
-- The filenames are arg[argindex] and up.
-- arg[1] is the command "pdftosvg".
--
ignoreconf ()
for i = argindex , #arg do
    if (lfs.attributes(arg[i],"mode")==nil) then
        print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
```

```
    else
        print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
        thispath, thisfilename, thisextension = splitfilename(arg[i])
        if ( thispath == nil ) then
            os.execute ( "pdftocairo -svg " .. arg[i] )
        else
            os.execute (
                "pdftocairo -svg " ..
                thispath .. thisfilename .. "." .. thisextension .. " " ..
                thispath .. thisfilename .. ".svg"
            )
        end
    end -- if
end -- do
end --function


-- Force an update and conclude processing:
function updateanddone ()
print ("lwarpmk: Forcing an update of " .. sourcename ..".tex.")
refreshdate ()
print ("lwarpmk: " .. sourcename ..".tex is ready to be recompiled.")
print ("lwarpmk: Done.")
end -- function


-- Start of the main code: --


-- lwarpmk --version :

if (arg[1] == "--version") then
print ( "lwarpmk: " .. printversion )

else -- not --version


-- print intro:

print ("lwarpmk: " .. printversion .. "  Automated make for the LaTeX lwarp package.")


-- lwarpmk print:

if arg[1] == "print" then
loadconf ()
if ( latexmk == "true" ) then
    print ("lwarpmk: Compiling with: " .. printlatexcmd)
    executecheckerror (
        printlatexcmd ,
        "Compile error."
    )
    print ("lwarpmk: Done.")
else -- not latexmk
    verifyfileexists (sourcename .. ".tex") ;
```

```
4762     -- See if up to date:
4763     if (
4764         ( lfs.attributes ( sourcename .. ".pdf" , "modification" ) == nil ) or
4765         (
4766             lfs.attributes ( sourcename .. ".tex" , "modification" ) >
4767             lfs.attributes ( sourcename .. ".pdf" , "modification" )
4768         )
4769     ) then
4770         -- Recompile if not yet up to date:
4771         manytimes(printlatexcmd, "")
4772         print ("lwarpmk: Done.") ;
4773     else
4774         print ("lwarpmk: " .. sourcename .. ".pdf is up to date.") ;
4775     end
4776 end -- not latexmk
4777
4778
4779 -- lwarpmk print1:
4780
4781 elseif arg[1] == "print1" then
4782     loadconf ()
4783     verifyfileexists (sourcename .. ".tex") ;
4784     onetime(printlatexcmd, "")
4785     print ("lwarpmk: Done.") ;
4786
4787
4788 -- lwarpmk printindex:
4789 -- Compile the index then touch the source
4790 -- to trigger a recompile of the document:
4791
4792 elseif arg[1] == "printindex" then
4793 loadconf ()
4794 os.execute ( printindexcmd )
4795 print ("lwarpmk: -------")
4796 updateanddone ()
4797
4798
4799 -- lwarpmk printglossary:
4800 -- Compile the glossary then touch the source
4801 -- to trigger a recompile of the document:
4802
4803 elseif arg[1] == "printglossary" then
4804 loadconf ()
4805 print ("lwarpmk: Processing the glossary.")
4806
4807 os.execute(glossarycmd .. " " .. sourcename)
4808 updateanddone ()
4809
4810
4811 -- lwarpmk html:
4812
4813 elseif arg[1] == "html" then
4814 loadconf ()
4815 if ( latexmk == "true" ) then
4816     print ("lwarpmk: Compiling with: " .. HTMLlatexcmd)
```

```
4817     executecheckerror (
4818         HTMLlatexcmd ,
4819         "Compile error."
4820     )
4821     pdftohtml ()
4822     print ("lwarpmk: Done.")
4823 else -- not latexmk
4824     verifyfileexists ( sourcename .. ".tex" ) ;
4825     -- See if exists and is up to date:
4826     if (
4827       ( lfs.attributes ( homehtmlfilename .. ".html" , "modification" ) == nil ) or
4828         (
4829             lfs.attributes ( sourcename .. ".tex" , "modification" ) >
4830             lfs.attributes ( homehtmlfilename .. ".html" , "modification" )
4831         )
4832     ) then
4833         -- Recompile if not yet up to date:
4834         manytimes(HTMLlatexcmd, "_html")
4835         pdftohtml ()
4836         print ("lwarpmk: Done.")
4837     else
4838         print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
4839     end
4840 end -- not latexmk
4841
4842
4843 -- lwarpmk html1:
4844
4845 elseif arg[1] == "html1" then
4846     loadconf ()
4847     verifyfileexists ( sourcename .. ".tex" ) ;
4848     onetime(HTMLlatexcmd, "_html")
4849     pdftohtml ()
4850     print ("lwarpmk: Done.")
4851
4852
4853 -- lwarpmk pdftohtml:
4854 elseif arg[1] == "pdftohtml" then
4855     loadconf ()
4856     pdftohtml ()
4857
4858
4859 -- lwarpmk htmlindex:
4860 -- Compile the index then touch the source
4861 -- to trigger a recompile of the document:
4862
4863 elseif arg[1] == "htmlindex" then
4864 loadconf ()
4865 os.execute ( HTMLindexcmd )
4866 print ("lwarpmk: -------")
4867 updateanddone ()
4868
4869
4870 -- lwarpmk htmlglossary:
4871 -- Compile the glossary then touch the source
```

```
-- to trigger a recompile of the document.
-- The <sourcename>.xdy file is created by the glossaries package.

elseif arg[1] == "htmlglossary" then
loadconf ()
print ("lwarpmk: Processing the glossary.")
os.execute(glossarycmd .. " " .. sourcename .. "_html")
updateanddone ()


-- lwarpmk limages:
-- Scan the <sourcename>.txt file to create lateximages.

elseif arg[1] == "limages" then
loadconf ()
print ("lwarpmk: Processing images.")
createlateximages ()
print ("lwarpmk: Done.")


-- lwarpmk again:
-- Touch the source to trigger a recompile.

elseif arg[1] == "again" then
loadconf ()
updateanddone ()


-- lwarpmk clean:
-- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*

elseif arg[1] == "clean" then
loadconf ()
removeaux ()
print ("lwarpmk: Done.")


-- lwarpmk cleanall
-- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
--    and also project.pdf, project.dvi, *.html

elseif arg[1] == "cleanall" then
loadconf ()
removeaux ()
os.execute ( rmname .. " " ..
    sourcename .. ".pdf " .. sourcename .. "_html.pdf " ..
    sourcename .. ".dvi " .. sourcename .. "_html.dvi " ..
    "*.html"
    )
print ("lwarpmk: Done.")


-- lwarpmk cleanlimages
-- Remove images from the imagesdirectory.

```

```
elseif arg[1] == "cleanlimages" then
loadconf ()
os.execute ( rmname .. " " .. imagesdirectory .. dirslash .. "*" )
print ("lwarpmk: Done.")

-- lwarpmk epstopdf <list of file names>
-- Convert EPS files to PDF using epstopdf
elseif arg[1] == "epstopdf" then
convertepstopdf ()
print ("lwarpmk: Done.")


-- lwarpmk pdftosvg <list of file names>
-- Convert PDF files to SVG using pdftocairo
elseif arg[1] == "pdftosvg" then
convertpdftosvg ()
print ("lwarpmk: Done.")


-- lwarpmk with no argument :

elseif (arg[1] == nil) then
printhelp ()


-- lwarpmk -h or lwarpmk --help :

elseif (arg[1] == "-h" ) or (arg[1] == "--help") then
printusage ()


-- Unknown command:

else
printhelp ()
print ("\nlwarpmk: ****** Unknown command \""..arg[1].."\". ******\n")
end

end -- not --version
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting


\end{LWR@createlwarpmk}
```

41 Stacks

for HTML output:

```
\begin{warpHTML}
```

Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (un-nested) in proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new `\section` would close any

currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an enumerate, for example. Depths to be recorded in `\LWR@closedepthone`, etc.

41.1 Assigning depths

initial depths for empty stack entries:

```
\newcommand*{\LWR@depthnone}{-5}
```

All sectioning depths are deeper than `LWR@depthfinished`:

```
\newcommand*{\LWR@depthfinished}{-4}
\newcommand*{\LWR@depthbook}{-2}
\newcommand*{\LWR@depthpart}{-1}
\newcommand*{\LWR@depthchapter}{0}
\newcommand*{\LWR@depthsection}{1}
\newcommand*{\LWR@depthsubsection}{2}
\newcommand*{\LWR@depthsubsubsection}{3}
\newcommand*{\LWR@depthparagraph}{4}
\newcommand*{\LWR@depthsubparagraph}{5}
```

Used by `\itemize`, `\enumerate`, `\description`:

```
\newcommand*{\LWR@depthlist}{6}
```

Used by `\item`:

```
\newcommand*{\LWR@depthlistitem}{7}
\let\LWR@depthdescitem\LWR@depthlistitem
```

41.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to `\pushclose` and `\popclose` as well.

```
\newcommand*{\LWR@closeone}{}% top of the stack
\newcommand*{\LWR@closetwo}{}
\newcommand*{\LWR@closethree}{}
\newcommand*{\LWR@closefour}{}
\newcommand*{\LWR@closefive}{}
\newcommand*{\LWR@closesix}{}
\newcommand*{\LWR@closeseven}{}
\newcommand*{\LWR@closeeight}{}
\newcommand*{\LWR@closenine}{}
```

```
\newcommand*{\LWR@closeten}{}
\newcommand*{\LWR@closeeleven}{}
\newcommand*{\LWR@closetwelve}{}
```

41.3 Closing depths

A stack to record the depth of each level:

⚠ Note that nested LaTeX structures may push depths which are non-sequential.

Ex:

```
\begin{itemize}
   \item{A}
   \begin{description}
      \item{B}
   \end{description}
\end{itemize}
```

```
\newcommand*{\LWR@closedepthone}{\LWR@depthnone}% top of the stack
\newcommand*{\LWR@closedepthtwo}{\LWR@depthnone}
\newcommand*{\LWR@closedepththree}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfour}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfive}{\LWR@depthnone}
\newcommand*{\LWR@closedepthsix}{\LWR@depthnone}
\newcommand*{\LWR@closedepthseven}{\LWR@depthnone}
\newcommand*{\LWR@closedeptheight}{\LWR@depthnone}
\newcommand*{\LWR@closedepthnine}{\LWR@depthnone}
\newcommand*{\LWR@closedepthten}{\LWR@depthnone}
\newcommand*{\LWR@closedeptheleven}{\LWR@depthnone}
\newcommand*{\LWR@closedepthtwelve}{\LWR@depthnone}
```

41.4 Pushing and popping the stack

`\LWR@pushclose` {⟨*sectiontype*⟩}

Pushes one return action and its LaTeX depth onto the stacks.

```
\NewDocumentCommand{\LWR@pushclose}{m}
{%
\global\let\LWR@closetwelve\LWR@closeeleven%
\global\let\LWR@closeeleven\LWR@closeten%
\global\let\LWR@closeten\LWR@closenine%
\global\let\LWR@closenine\LWR@closeeight%
\global\let\LWR@closeeight\LWR@closeseven%
\global\let\LWR@closeseven\LWR@closesix%
\global\let\LWR@closesix\LWR@closefive%
\global\let\LWR@closefive\LWR@closefour%
\global\let\LWR@closefour\LWR@closethree%
```

```
\global\let\LWR@closethree\LWR@closetwo%
\global\let\LWR@closetwo\LWR@closeone%
\global\csletcs{LWR@closeone}{LWR@printclose#1}%
\global\let\LWR@closedepthtwelve\LWR@closedepththeleven%
\global\let\LWR@closedepththeleven\LWR@closedepththen%
\global\let\LWR@closedepththen\LWR@closedepthnine%
\global\let\LWR@closedepthnine\LWR@closedepthheight%
\global\let\LWR@closedepthheight\LWR@closedepthseven%
\global\let\LWR@closedepthseven\LWR@closedepthsix%
\global\let\LWR@closedepthsix\LWR@closedepthfive%
\global\let\LWR@closedepthfive\LWR@closedepthfour%
\global\let\LWR@closedepthfour\LWR@closedepththree%
\global\let\LWR@closedepththree\LWR@closedepthtwo%
\global\let\LWR@closedepthtwo\LWR@closedepthone%
\global\csletcs{LWR@closedepthone}{LWR@depth#1}%
}
```

`\LWR@popclose` Pops one action and its depth off the stacks.

```
\newcommand*{\LWR@popclose}
{%
\global\let\LWR@closeone\LWR@closetwo%
\global\let\LWR@closetwo\LWR@closethree%
\global\let\LWR@closethree\LWR@closefour%
\global\let\LWR@closefour\LWR@closefive%
\global\let\LWR@closefive\LWR@closesix%
\global\let\LWR@closesix\LWR@closeseven%
\global\let\LWR@closeseven\LWR@closeeight%
\global\let\LWR@closeeight\LWR@closenine%
\global\let\LWR@closenine\LWR@closeten%
\global\let\LWR@closeten\LWR@closeeleven%
\global\let\LWR@closeeleven\LWR@closetwelve%
\global\let\LWR@closedepthone\LWR@closedepthtwo%
\global\let\LWR@closedepthtwo\LWR@closedepththree%
\global\let\LWR@closedepththree\LWR@closedepthfour%
\global\let\LWR@closedepthfour\LWR@closedepthfive%
\global\let\LWR@closedepthfive\LWR@closedepthsix%
\global\let\LWR@closedepthsix\LWR@closedepthseven%
\global\let\LWR@closedepthseven\LWR@closedepthheight%
\global\let\LWR@closedepthheight\LWR@closedepthnine%
\global\let\LWR@closedepthnine\LWR@closedepththen%
\global\let\LWR@closedepththen\LWR@closedepththeleven%
\global\let\LWR@closedepththeleven\LWR@closedepthtwelve%
}
```

```
\end{warpHTML}
```

42 Data arrays

These macros are similar to the arrayjobx package, except that `\LWR@setexparray`'s argument is expanded only once when assigned.

name has no backslash, index can be a number or a text name, and an empty value must be \relax instead of empty.

To assign an empty value:

```
\LWR@setexparray{name}{index}{}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@setexparray {⟨*name*⟩} {⟨*index*⟩} {⟨*contents*⟩}

```
\NewDocumentCommand{\LWR@setexparray}{m m m}{%
    \begingroup%
    \let\par\relax%
    \xdef\LWR@thisexparrayname{#1#2}%
    \ifstrempty{#3}%
    {\csgdef{\LWR@thisexparrayname}{}}%
    {\csxdef{\LWR@thisexparrayname}{#3}}%
    \endgroup%
}
```

\LWR@getexparray {⟨*name*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@getexparray}[2]{%
    \@nameuse{#1#2}%
}
```

```
\end{warpHTML}
```

43 Localizing catcodes

for HTML & PRINT:

```
\begin{warpall}
```

⚠ Misplaced alignment tab character &

Place \StartDefiningTabulars and \StopDefiningTabulars before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error

```
Misplaced alignment tab character &.
```

\StartDefiningTabulars Place before defining something with & in it.

```
\newcommand{\StartDefiningTabulars}{%
\LWR@traceinfo{StartDefiningTabulars}%
\warpHTMLonly{\catcode`\&=\active}%
}
```

\StopDefiningTabulars Place after defining something with & in it.

```
\newcommand{\StopDefiningTabulars}{%
\LWR@traceinfo{StopDefiningTabulars}%
\warpHTMLonly{\catcode`\&=4}%
}
```

Bool LWR@mathmacro True if currently defining math macros. Used to disable SVG math hashing and MathJax math contents while defining a macro using inline math. Begin a macro, it is not guaranteed that the contents are static, and so the image must be unique. The contents also almost certainly will not be parsed correctly by MathJax.

```
\newbool{LWR@mathmacro}
\boolfalse{LWR@mathmacro}
```

\StartDefiningMath Place before defining something with $ in it.

```
\newcommand{\StartDefiningMath}{%
\LWR@traceinfo{StartDefiningMath}%
\warpHTMLonly{\catcode`\$=\active}%
}
```

\StopDefiningMath Place after defining something with $ in it.

```
\newcommand{\StopDefiningMath}{%
\LWR@traceinfo{StopDefiningMath}%
\warpHTMLonly{\catcode`\$=3}% math shift
}
```

```
\end{warpall}
```

44 Localizing dynamic math

Inline SVG math usually uses a hash of its contents to generate `lateximage`s which are reusable for multiple instances with the same contents. If the contents may change for each use, such as depending on the current value of a counter, then `\inlinemathother` must be used before the inline math expression, and `\inlinemathnormal` must be used after.

For MathJax, the inline math expression is usually printed for MathJax to interpret. When marked as dynamic math, the following inline math expression will be displayed as an unhashed inline SVG image instead.

For existing code and packages, it may be possible to patch macros after they have been defined, using the xpatch package, which is pre-loaded by lwarp:

```
\xpatchcmd{\macroname}
    {$math expression$}
    {\inlinemathother$math expression$\inlinemathnormal}
```

```
    {}
    {\typeout{Error patching macroname.}}
```

for HTML & PRINT:

```
5094 \begin{warpall}
```

Bool `LWR@dynamicmath` Default: `false`

True to mark inline math which is dynamic in nature, thus should not be hashed for reuse.

```
5095 \newbool{LWR@dynamicmath}
5096 \boolfalse{LWR@dynamicmath}
```

`\inlinemathother` Place before using `$ ... $` or `\( ... \)` if the contents of the math are not static, depending on counters or dynamic macros.

```
5097 \newcommand{\inlinemathother}{%
5098 \LWR@traceinfo{inlinemathother}%
5099 \booltrue{LWR@dynamicmath}%
5100 }
```

`\inlinemathnormal` Place after using `$ ... $` or `\( ... \)` with dynamic contents.

```
5101 \newcommand{\inlinemathnormal}{%
5102 \LWR@traceinfo{inlinemathnormal}%
5103 \boolfalse{LWR@dynamicmath}%
5104 }
```

```
5105 \end{warpall}
```

45 HTML entities

for HTML output:

```
5106 \begin{warpHTML}
```

HTML Unicode entities:

```
5107 \let\LWR@origampersand\&
```

`\HTMLentity` {⟨*entitytag*⟩}

```
5108 \newcommand*{\HTMLentity}[1]{%
5109 % \LWR@traceinfo{HTMLentity \detokenize{#1}}%
5110 \begingroup%
5111 \LWR@FBcancel%
5112 \LWR@origampersand#1;%
5113 \endgroup%
5114 % \LWR@traceinfo{HTMLentity done}%
5115 }
```

`\HTMLunicode` {⟨*hex_unicode*⟩}

```
5116 \newcommand*{\HTMLunicode}[1]{\HTMLentity{\LWR@origpound{}x#1}}
```

\&

```
\renewrobustcmd*{\&}{\HTMLentity{amp}}
```

\textless

```
\let\LWR@origtextless\textless
\renewrobustcmd*{\textless}{\HTMLentity{lt}}
```

\textgreater

```
\let\LWR@origtextgreater\textgreater
\renewrobustcmd*{\textgreater}{\HTMLentity{gt}}
```

```
\end{warpHTML}
```

46 HTML filename generation

The filename of the homepage is set to `\HomeHTMLFilename.html`. The filenames of additional sections start with `\HTMLFilename`, to which is appended a section number or a simplified section name, depending on `FileSectionNames`.

for HTML & PRINT:

```
\begin{warpall}
```

\BaseJobname

The `\jobname` of the printed version, even if currently compiling the HTML version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLFilename` if the user did not provide one.

```
\providecommand*{\BaseJobname}{\jobname}
```

\HTMLFilename

The prefix for all generated HTML files other than the home page, defaulting to empty. See section 7.6.1.

```
\providecommand*{\HTMLFilename}{}
```

\HomeHTMLFilename

The filename of the home page, defaulting to the `\BaseJobname`. See section 7.6.1.

```
\providecommand*{\HomeHTMLFilename}{\BaseJobname}
```

\SetHTMLFileNumber {⟨*number*⟩}

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
\newcommand*{\SetHTMLFileNumber}[1]{%
\setcounter{LWR@htmlfilenumber}{#1}%
}
```

Bool FileSectionNames — Selects how to create HTML file names.

Defaults to use section names in the filenames.

```
\newbool{FileSectionNames}
\booltrue{FileSectionNames}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@htmlfilenumber — Records the number of each HTML file as it is being created. Number 0 is the home page.

```
\newcounter{LWR@htmlfilenumber}
\setcounter{LWR@htmlfilenumber}{0}
```

\LWR@htmlsectionfilename {⟨*htmlfilenumber or name*⟩}

Prints the filename for a given section: `\HTMLFilename{}filenumber/name.html`

```
\newcommand*{\LWR@htmlsectionfilename}[1]{%
\LWR@traceinfo{LWR@htmlsectionfilename A !\detokenize{#1}!}%
```

Section 0 or empty is given the home filename. The filename must be detokenized for underscores.

```
% \LWR@traceinfo{about to assign temp}%
\LWR@sanitize{#1}%
\LWR@traceinfo{about to compare with ??}%
\ifthenelse{\equal{\LWR@sanitized}{??}}%
    {\LWR@traceinfo{found ??}}%
    {\LWR@traceinfo{not found ??}}%
\LWR@traceinfo{about to compare with zero or empty}%
\ifthenelse{%
    \equal{\LWR@sanitized}{0}%
    \OR \equal{\LWR@sanitized}{}%
    \OR \equal{\LWR@sanitized}{??}%
}%
{%
    \LWR@traceinfo{LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
    \HomeHTMLFilename.html%
}%
```

For a LaTeX section named “Index” or “index” without a prefix, create a filename with a leading underscore to avoid colliding with the HTML filename `index.html`:

```
{%
    \LWR@traceinfo{LWR@htmlsectionfilename C \LWR@sanitized}%
    \ifthenelse{%
        \equal{\HTMLFilename}{} \AND
        \equal{\LWR@sanitized}{Index} \OR
        \equal{\LWR@sanitized}{index}%
```

```
    }%
    {%
        \LWR@traceinfo{Prefixing the index name with an underscore.}%
        \_\LWR@sanitized.html%
    }%
```

Otherwise, create a filename with the chosen prefix:

```
    {%
        \HTMLFilename\LWR@isolate{\LWR@sanitized}.html%
    }%
}%
\LWR@traceinfo{LWR@htmlsectionfilename Z}%
}
```

`\LWR@htmlrefsectionfilename` {⟨*label*⟩}

Prints the filename for the given label

```
\newcommand*{\LWR@htmlrefsectionfilename}[1]{%
\LWR@traceinfo{LWR@htmlrefsectionfilename: !\detokenize{#1}!}%
```

`\LWR@nullfonts` to allow math in a section name.

```
\begingroup%
\LWR@nullfonts%
\LWR@htmlsectionfilename{\LWR@htmlfileref{#1}}%
\endgroup%
\LWR@traceinfo{LWR@htmlrefsectionfilename: done}%
}
```

```
\end{warpHTML}
```

47 Homepage link

for HTML & PRINT:

```
\begin{warpall}
```

`\linkhomename` Holds the default name for the home link.

```
\newcommand{\linkhomename}{Home}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LinkHome` May be used wherever you wish to place a link back to the homepage. The filename must be detokenized for underscores.

```
\newcommand*{\LinkHome}{%
\LWR@subhyperrefclass{\HomeHTMLFilename.html}{\linkhomename}{linkhome}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

`\LinkHome` May be used wherever you wish to place a link back to the homepage. For print output, if hyperref is available a hyperlink to the first page is used, named by `\linkhomename`. If hyperref is not available, a pageref is used instead.

`\BaseJobname` is included in the link label in case multiple documents are cross-referenced.

```
\AtBeginDocument{
\@ifundefined{hyperref}{
    \newcommand*{\LinkHome}{%
        \linkhomename\ --- page \pageref{\BaseJobname-page-LWRfirstpage}%
    }
}{
    \newcommand*{\LinkHome}{%
        \hyperref[\BaseJobname-page-LWRfirstpage]{\linkhomename}%
    }
}
}

\AfterEndPreamble{\label{\BaseJobname-page-LWRfirstpage}}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@topnavigation` Creates a link to the homepage at the top of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@topnavigation}{
\LWR@htmlelementclassline{nav}{topnavigation}{\LinkHome}
}
```

`\LWR@botnavigation` Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@botnavigation}{
\LWR@htmlelementclassline{nav}{botnavigation}{\LinkHome}
}
```

```
\end{warpHTML}
```

48 `\LWRPrintStack` diagnostic tool

⚠ Diagnostics tool: Prints the LaTeX nesting depth values for the stack levels. `\LWR@startpars` is used before printing the stack, so that `\LWRPrintStack` may be called from anywhere

in the normal text flow.

for HTML output:

```
\begin{warpHTML}
```

`\LWRPrintStack` Prints the closedepth stack.

```
\newcommand*{\LWR@subprintstack}{
\LWR@closedepthone\ \LWR@closedepththwo\ \LWR@closedepththree\
\LWR@closedepthfour\ \LWR@closedepthfive\ \LWR@closedepthsix\
\LWR@closedepthseven\ \LWR@closedeptheight\ \LWR@closedepthnine\
\LWR@closedepthten\ \LWR@closedeptheleven\ \LWR@closedepthtwelve\
}

\newcommand*{\LWRPrintStack}{
\LWR@startpars
\LWR@subprintstack
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}

\newcommand*{\LWRPrintStack}{}

\end{warpprint}
```

49 Closing stack levels

for HTML output:

```
\begin{warpHTML}
```

Close one nested level:

```
\newcommand*{\LWR@closeoneprevious}{%

\LWR@closeone

\LWR@popclose
}
```

`\LWR@closeprevious` {⟨*sectintype*⟩} Close everything up to the given depth:

```
\newcommand*{\LWR@closeprevious}[1]{
\LWR@traceinfo{%
    LWR@closeprevious to depth \csuse{LWR@depth#1}, %
    depths are \LWR@subprintstack%
}%
```

Close any pending paragraph:

```
\LWR@stoppars%
```

Close anything nested deeper than the desired depth. First close anything deeper, then at most one of the same level.

```
\whileboolexpr{test{\ifnumcomp{\LWR@closedepthone}{>}{\csuse{LWR@depth#1}}}}%
{%
    \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
    \LWR@closeoneprevious%
}%
\ifboolexpr{test{\ifnumcomp{\LWR@closedepthone}{=}{\csuse{LWR@depth#1}}}}%
{%
    \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
    \LWR@closeoneprevious%
}{}%
\LWR@traceinfo{LWR@closeprevious: done, depths are \LWR@subprintstack}%
}
```

```
\end{warpHTML}
```

50 PDF pages and styles

for HTML output:

```
\begin{warpHTML}
```

\LWR@forcenewpage New PDF page a before major environment.

This is used just before major environments, such as `verse`. Reduces the chance of an environment overflowing the HTML PDF output page.

```
\newcommand{\LWR@forcenewpage}{%
\LWR@traceinfo{LWR@forcenewpage}%
\ifinner\else%
\LWR@stoppars\LWR@orignewpage\LWR@startpars%
\fi%
}
```

`\pagestyle`, etc. are nullified for HTML output.

\pagestyle {⟨*style*⟩}

```
\renewcommand*{\pagestyle}[1]{}
```

\thispagestyle {⟨*style*⟩}

```
\renewcommand*{\thispagestyle}[1]{}
```

\markboth {⟨*left*⟩} {⟨*right*⟩}

```
\renewcommand*{\markboth}[2]{}
```

\markright {⟨*right*⟩}

```
5263 \renewcommand*{\markright}[1]{}
```

\raggedbottom

```
5264 \renewcommand*{\raggedbottom}{}
```

\flushbottom

```
5265 \renewcommand*{\flushbottom}{}
```

\sloppy

```
5266 \renewcommand*{\sloppy}{}
```

\fussy

```
5267 \renewcommand*{\fussy}{}
```

\pagenumbering * {⟨*commands*⟩}

```
5268 \RenewDocumentCommand{\pagenumbering}{s m}{}
```

```
5269 \end{warpHTML}
```

51 HTML tags, spans, divs, elements

for HTML output:

```
5270 \begin{warpHTML}
```

51.1 Mapping LaTeX sections to HTML sections

```
5271 \newcommand*{\LWR@tagtitle}{h1}
5272 \newcommand*{\LWR@tagtitleend}{/h1}
5273 \newcommand*{\LWR@tagbook}{div class="book"}
5274 \newcommand*{\LWR@tagbookend}{/div}
5275 \newcommand*{\LWR@tagpart}{h2}
5276 \newcommand*{\LWR@tagpartend}{/h2}
5277 \newcommand*{\LWR@tagchapter}{h3}
5278 \newcommand*{\LWR@tagchapterend}{/h3}
5279 \newcommand*{\LWR@tagsection}{h4}
5280 \newcommand*{\LWR@tagsectionend}{/h4}
5281 \newcommand*{\LWR@tagsubsection}{h5}
5282 \newcommand*{\LWR@tagsubsectionend}{/h5}
5283 \newcommand*{\LWR@tagsubsubsection}{h6}
5284 \newcommand*{\LWR@tagsubsubsectionend}{/h6}
5285 \newcommand*{\LWR@tagparagraph}{span class="paragraph"}
```

```
\newcommand*{\LWR@tagparagraphend}{/span}
\newcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\newcommand*{\LWR@tagsubparagraphend}{/span}

\newcommand*{\LWR@tagregularparagraph}{p}
```

51.2 Babel-French tag modifications

Adjust babel-french for HTML spaces. So far, this only works for *pdflatex* and *xelatex*.

(*Emulates or patches code by* Daniel Flipo.)

```
\providecommand*{\LWR@FBcancel}{}

\AtBeginDocument{%
\@ifundefined{frenchbsetup}%
{}%
{%
    \frenchbsetup{FrenchFootnotes=false}%

%
    \LetLtxMacro\LWR@FBcancel\NoAutoSpacing%
    \renewrobustcmd*{\FBcolonspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;%
        \endgroup%
    }%
    \renewrobustcmd*{\FBthinspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \renewrobustcmd*{\FBguillspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;% ~,  for \og xyz \fg{}
        \endgroup%
    }%
    \DeclareDocumentCommand{\FBmedkern}{}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \DeclareDocumentCommand{\FBthickkern}{}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;% ~
        \endgroup%
    }%
    \renewrobustcmd*{~}{\HTMLentity{nbsp}}% was overwritten by babel-french
    \ifFBunicode%
```

```
    \else%
        \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
        \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
    \fi%
}%
}
```

51.3 HTML output formatting

Helps format the output HTML code for human readability.

`\LWR@indentHTML` Newline and indent the output HTML code.

```
\newcommand*{\LWR@indentHTML}{%
    \LWR@orignewline\LWR@origrule{2em}{0pt}%
}
```

`\LWR@indentHTMLtwo` Newline and indent the output HTML code.

```
\newcommand*{\LWR@indentHTMLtwo}{%
    \LWR@orignewline\LWR@origrule{4em}{0pt}%
}
```

51.4 HTML tags

`\LWR@htmltagc` {⟨*tag*⟩} Break ligatures and use upright apostrophes in HTML tags.

`\protect` is in case the tag appears in TOC, LOF, LOT.

```
\newcommand*{\LWR@htmltagc}[1]{%
\LWR@traceinfo{LWR@htmltagc !\detokenize{#1}!}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\protect\LWR@origtextless%
\LWR@isolate{#1}%
\protect\LWR@origtextgreater%
\endgroup%
}
```

Env `LWR@nestspan` Disable `minipage`, `\parbox`, and HTML `<div>`s inside a `<span>`.

⚠ `\begin{LWR@nestspan}` must follow the opening `<span>` tag to allow a paragraph to start if the span is at the beginning of a new paragraph.

⚠ `\end{LWR@nestspan}` must follow the `</span>` or a `<p>` may appear inside the span.

```
\newcommand*{\LWR@nestspanitem}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
```

```
\LWR@origitem%
}

\newenvironment*{LWR@nestspan}
{%
\LWR@traceinfo{LWR@nestspan starting}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{%
    \LWR@traceinfo{LWR@nestspan: inside a lateximage}%
}%
{% not in a lateximage
    \LWR@traceinfo{LWR@nestspan: NOT inside a lateximage}%
    \addtocounter{LWR@spandepth}{1}%
    \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}%
        {\LWR@subhtmlelementclass{span}{inlineminipage}}%
        {\LWR@htmltagc{/span}}%
    \RenewDocumentEnvironment{BlockClass}{o m}{}{}%
    \renewcommand{\BlockClassSingle}[2]{##2}%
    \renewcommand{\LWR@forcenewpage}{}%
    \renewcommand{\LWR@liststart}{%
        \let\item\LWR@nestspanitem%
    }%
    \renewcommand{\LWR@listend}{\LWR@htmltagc{br /}\LWR@htmltagc{br /}}%
    \renewenvironment{quote}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
    \renewenvironment{quotation}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
}% not in a lateximage
\LWR@traceinfo{LWR@nestspan starting: done}%
}% starting env
{% ending env
\LWR@traceinfo{LWR@nestspan ending}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{\addtocounter{LWR@spandepth}{-1}}%
\LWR@traceinfo{LWR@nestspan ending: done}%
}

\AfterEndEnvironment{LWR@nestspan}{\global\let\par\LWR@closeparagraph}
```

`\LWR@htmlspan` {⟨*tag*⟩} {⟨*text*⟩}

⚠ `\LWR@spandepth` is used to ensure that paragraph tags are not generated inside a span. The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```
\NewDocumentCommand{\LWR@htmlspan}{m +m}{%
\LWR@ensuredoingapar%
\LWR@htmltagc{#1}%
\begin{LWR@nestspan}%
#2%
\LWR@htmltagc{/#1}%
\end{LWR@nestspan}%
}
```

\LWR@htmlspanclass [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlspanclass}{o m +m}{%
\LWR@traceinfo{LWR@htmlspanclass |#1|#2|}%
\LWR@ensuredoingapar%
\LWR@subhtmlelementclass{span}[#1]{#2}%
\begin{LWR@nestspan}%
#3%
\LWR@htmltagc{/span}%
\LWR@traceinfo{LWR@htmlspanclass done}%
\end{LWR@nestspan}%
}
```

\LWR@htmltag {⟨*tag*⟩}

Print an HTML tag: <tag>

```
\newcommand*{\LWR@htmltag}[1]{%
% \LWR@traceinfo{LWR@htmltagb !\detokenize{#1}!}%
\LWR@htmltagc{#1}%
% \LWR@traceinfo{LWR@htmltagb: done}%
}
```

51.5 Block tags and comments

In the following, \origttfamily breaks ligatures, which may not be used for HTML codes:

\LWR@htmlopencomment
\LWR@htmlclosecomment

```
\newcommand*{\LWR@htmlopencomment}{%
{%
% \LWR@traceinfo{LWR@htmlopencomment}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\LWR@print@mbox{\LWR@origtextless{}!-\/-}%
\endgroup%
}%
}

\newcommand*{\LWR@htmlclosecomment}{%
{%
% \LWR@traceinfo{LWR@htmlclosecomment}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\LWR@print@mbox{-\/-\LWR@origtextgreater}%
\endgroup%
}%
}
```

`\LWR@htmlcomment` {⟨*comment*⟩}

```
\newcommand{\LWR@htmlcomment}[1]{%
\LWR@htmlopencomment{}%
{%
\LWR@origttfamily% break ligatures
#1%
}%
\LWR@htmlclosecomment{}}
```

`\LWR@htmlblockcomment` {⟨*comment*⟩}

```
\newcommand{\LWR@htmlblockcomment}[1]
{\LWR@stoppars\LWR@htmlcomment{#1}\LWR@startpars}
```

`\LWR@htmlblocktag` {⟨*tag*⟩} print a stand-alone HTML tag

```
\newcommand*{\LWR@htmlblocktag}[1]{%
\LWR@stoppars%
\LWR@htmltag{#1}%
\LWR@startpars%
}
```

51.6 Div class and element class

`\LWR@subhtmlelementclass` {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩}

Factored and reused in several places.

The trailing spaces allow more places for a line break.

The use of `\textquotedbl` instead of " provides improved compatibility with xeCJK.

```
\NewDocumentCommand{\LWR@subhtmlelementclass}{m O{} m}{%
\LWR@traceinfo{LWR@subhtmlelementclass !#1!#2!#3!}%
\ifblank{#2}%
{% empty option
    \LWR@htmltag{%
        #1 % space
        class=\textquotedbl#3\textquotedbl\ % space
    }%
}%
{% non-empty option
    \LWR@htmltag{%
        #1\LWR@indentHTML%
        class=\textquotedbl#3\textquotedbl\LWR@indentHTML%
        style=\textquotedbl#2\textquotedbl\LWR@orignewline%
    }%
}%
\LWR@traceinfo{LWR@subhtmlelementclass done}%
}
```

\LWR@htmlelementclass {⟨*element*⟩} {⟨*class*⟩} [⟨*style*⟩]

```
\NewDocumentCommand{\LWR@htmlelementclass}{m o m}{%
\LWR@stoppars%
\LWR@forceemptyline%
\LWR@subhtmlelementclass{#1}[#2]{#3}%
\LWR@startpars%
}
```

\LWR@htmlelementclassend {⟨*element*⟩} {⟨*class*⟩}

```
\newcommand*{\LWR@htmlelementclassend}[2]{%
\LWR@stoppars%
\LWR@htmltag{/#1}%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{End of #1 ‘‘#2’’}%
}{}%
\LWR@startpars%
}
```

\LWR@htmldivclass [⟨*style*⟩] {⟨*class*⟩}

```
\NewDocumentCommand{\LWR@htmldivclass}{o m}{%
\LWR@htmlelementclass{div}[#1]{#2}%
}
```

\LWR@htmldivclassend {⟨*class*⟩}

```
\newcommand*{\LWR@htmldivclassend}[1]{%
\LWR@htmlelementclassend{div}{#1}%
}
```

51.7 Single-line elements

A single-line element, without a paragraph tag for the line of text:

\LWR@htmlelementclassline {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlelementclassline}{m o m +m}{%
\LWR@stoppars
\LWR@forceemptyline%
\LWR@subhtmlelementclass{#1}[#2]{#3}%
#4%
\LWR@htmltag{/#1}
\LWR@startpars
}
```

51.8 HTML5 semantic elements

`\LWR@htmlelement` {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelement}[1]{%
\LWR@htmlblocktag{#1}
}
```

`\LWR@htmlelementend` {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelementend}[1]{%
\LWR@stoppars
\LWR@htmltag{/#1}
\LWR@startpars
}

\end{warpHTML}
```

51.9 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with css.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section 90.

Env `BlockClass` [⟨*style*⟩] {⟨*class*⟩} High-level interface for classes.

Ex: `\begin{BlockClass}{class}` text `\end{BlockClass}`

for PRINT output:

```
\begin{warpprint}
\NewDocumentEnvironment{BlockClass}{o m}{}{}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentEnvironment{LWR@print@BlockClass}{o m}{}{}%
\NewDocumentEnvironment{LWR@HTML@BlockClass}{o m}%
{%
    \LWR@htmldivclass[#1]{#2}%
}
{\LWR@htmldivclassend{#2}}

\LWR@formattedenv{BlockClass}
\end{warpHTML}
```

`\BlockClassSingle` {⟨*class*⟩} {⟨*text*⟩} A single-line , without a paragraph tag for the line of text.

for HTML & PRINT:

```
\begin{warpall}
\newcommand{\BlockClassSingle}[2]{#2}
\end{warpall}
```

for HTML output:
```
\begin{warpHTML}
\newcommand{\LWR@HTML@BlockClassSingle}[2]{%
\LWR@htmlelementclassline{div}{#1}{#2}%
}

\LWR@formatted{BlockClassSingle}
\end{warpHTML}
```

`\InlineClass` (⟨*WP style*⟩) [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

High-level interface for inline span classes.

(⟨*WP style*⟩) is css styling to add when formatting for a word processor import.

[⟨*style*⟩] is the css styling to add when not formatting for a word processor.

for PRINT output:
```
\begin{warpprint}
\NewDocumentCommand{\InlineClass}{D{(}{)}{} o m +m}{#4}%
\end{warpprint}
```

for HTML output:
```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@InlineClass}{D{(}{)}{} o m +m}{#4}%

\NewDocumentCommand{\LWR@HTML@InlineClass}{D{(}{)}{} o m +m}{%
\ifbool{FormatWP}{%
    \LWR@htmlspanclass[#1]{#3}{#4}%
}{%
    \LWR@htmlspanclass[#2]{#3}{#4}%
}%
}

\LWR@formatted{InlineClass}
\end{warpHTML}
```

Env `LWR@BlockClassWP` {⟨*WPstyle*⟩} {⟨*HTMLstyle*⟩} {⟨*class*⟩} Low-level interface for classes with an automatic float ID. These are often used when `\ifbool{FormatWP}`.

The use of `\textquotedbl` instead of " provides improved compatibility with xeCJK.

for PRINT output:
```
\begin{warpprint}
\NewDocumentEnvironment{LWR@BlockClassWP}{m m m}{}{}%
\end{warpprint}
```

for HTML output:
```
\begin{warpHTML}
\NewDocumentEnvironment{LWR@print@LWR@BlockClassWP}{m m m}{}{}%
\NewDocumentEnvironment{LWR@HTML@LWR@BlockClassWP}{m m m}%
{%
\LWR@stoppars%
\ifbool{FormatWP}%
{%
    \addtocounter{LWR@thisautoidWP}{1}%


    \LWR@htmltag{%
```

```
        div class=\textquotedbl#3\textquotedbl\ % space
        id=\textquotedbl%
            \LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}%
        \textquotedbl%
        \ifblank{#1}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
}% FormatWP
{% not FormatWP
    \LWR@htmltag{%
        div class=\textquotedbl#3\textquotedbl%
        \ifblank{#2}{}{ style=\textquotedbl#2\textquotedbl}%
    }%
}% not FormatWP
\LWR@startpars%
}
{\LWR@htmldivclassend{#3}}

\LWR@formattedenv{LWR@BlockClassWP}
\end{warpHTML}
```

51.10 Closing HTML tags

for HTML output:

```
\begin{warpHTML}
```

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```
\newcommand*{\LWR@printclosebook}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing book}}{}}
\newcommand*{\LWR@printclosepart}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
\newcommand*{\LWR@printclosechapter}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
\newcommand*{\LWR@printclosesection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
\newcommand*{\LWR@printclosesubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
\newcommand*{\LWR@printclosesubsubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsubsection}}{}}
\newcommand*{\LWR@printcloseparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
\newcommand*{\LWR@printclosesubparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}
```

Lists require closing HTML tags:

```
\newcommand*{\LWR@printcloselistitem}
    {\LWR@htmltag{/li}}
\newcommand*{\LWR@printclosedescitem}
    {\LWR@htmltag{/dd}}
\newcommand*{\LWR@printcloseitemize}
    {\LWR@htmltag{/ul}}
\newcommand*{\LWR@printcloseenumerate}
```

```
    {\LWR@htmltag{/ol}}
\newcommand*{\LWR@printclosedescription}
    {\LWR@htmltag{/dl}}

\end{warpHTML}
```

52 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 53 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (`\LWR@doingstartpars`), tags are not generated until a LaTeX paragraph is being used (`\LWR@doingapar`). `LWR@lateximagedepth` is used to prevent nesting tags inside a `lateximage`. `LWR@spandepth` is used to prevent nesting paragraph tags inside a paragraph, which became important inside `\fbox` commands and other spans.

for HTML output:

```
\begin{warpHTML}
```

Ctr `LWR@spandepth` Do not create paragraph tags inside of an HTML span.

```
\newcounter{LWR@spandepth}
\setcounter{LWR@spandepth}{0}
```

Bool `LWR@doingstartpars` Tells whether paragraphs may be generated.

```
\newbool{LWR@doingstartpars}
\boolfalse{LWR@doingstartpars}
```

Bool `LWR@doingapar` Tells whether have actually generated and are currently processing paragraph text.

```
\newbool{LWR@doingapar}
\global\boolfalse{LWR@doingapar}
```

`\LWR@ensuredoingapar` If are about to print something visible, and if allowed to start a new paragraph, ensure that are `LWR@doingapar`, so that paragraph tags are placed:

```
\newcommand*{\LWR@ensuredoingapar}{%
\ifbool{LWR@doingstartpars}%
{\global\booltrue{LWR@doingapar}}%
{}%
}
```

`\PN@parnotes@auto` Redefined by parnotes to print paragraph notes at the end of each paragraph.

```
\def\PN@parnotes@auto{}%
```

`\LWR@openparagraph`

```
\newcommand*{\LWR@openparagraph}
{%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingstartpars}%
{% handling pars
```

See if have already started a lateximage or a . If so, do not generate nested paragraph tags.

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }% nested par tags?
```

If so: Do nothing if already started a lateximage page. Cannot nest a lateximage. Also do nothing if already inside a . Do not nest paragraph tags inside a .

```
    {}% no nested par tags
```

Else: No lateximage or has been started yet, so it's OK to generate paragraph tags.

```
    {% yes nest par tags
```

If parnotes is used, paragraph notes are inserted before starting the next paragraph:

```
        \PN@parnotes@auto%
```

The opening paragraph tag:

```
        \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%
```

Now have started a paragraph.

```
        \global\booltrue{LWR@doingapar}%
```

At the endof each paragraph, generate closing tag and do regular /par stuff. (Attempting to use the everyhook cr hook for \LWR@closeparagraph does not work well.)

```
        \let\par\LWR@closeparagraph%
    }% end of yes nest par tags
}% end of handling pars
{}% not handling pars
}
```

\LWR@closeparagraph@br Add an HTML break if in a span, and not in a lateximage, and not in tabular metadata. Factored from \LWR@closeparagraph.

```
\newcommand*{\LWR@closeparagraph@br}
{%
```

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}} and
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}} and
        not bool {LWR@intabularmetadata}
    }%
        {\unskip\LWR@htmltagc{br /}}%
        {}%
}
```

\LWR@closeparagraph

```
\newcommand*{\LWR@closeparagraph}
{%
% \LWR@traceinfo{LWR@closeparagraph}%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingapar}%
```

If currently in paragraph mode:

```
{% handling pars
```

See if already started a `lateximage` or a :

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }%
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
    {% no nested par tags
        \LWR@closeparagraph@br%
    }% no nested par tags
```

If have not already started a `lateximage` or a :

```
    {% yes nest par tags
```

Print a closing tag and some extra vertical space.

(The fill seems to be required to force the caption package to create flush left caption text in the HTML.)

```
        \@hspacer{\fill}% \hspace*{\fill}
        \leavevmode\LWR@orignewline%
        \LWR@htmltagc{/\LWR@tagregularparagraph}%
```

No longer doing a paragraph:

```
        \global\boolfalse{LWR@doingapar}%
```

Disable the special minipage & \hspace interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}%
```

If parnotes is used, paragraph notes are inserted after ending the previous paragraph:

```
        \PN@parnotes@auto%
    }% end of yes nest par tags
}% end of handling pars
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
{% not handling pars
    \LWR@closeparagraph@br%
}% not handling pars
```

In most cases, finish with a LaTeX \par, but in the case of paragraphs between lines in a tabular fetch the next token instead:

```
\ifboolexpr{%
    not bool {LWR@doingapar} and
    test {\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}} and
    test {
        \ifnumcomp{\value{LWR@tabulardepth}}{=}{\value{LWR@tabularpardepth}}
    } and
    bool {LWR@intabularmetadata} and
    not bool {LWR@tableparcell} and
    test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
}%
{%
    \LWR@getmynexttoken%
}{%
    \LWR@origpar%
}%
}

\end{warpHTML}
```

53 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 52 has the commands which actually generate the tags.

The everyhook package is used to generate the opening paragraph tags. The closing tags are generated by \par.

for HTML output:

```
\begin{warpHTML}
```

\LWR@startpars Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```
\newcommand*{\LWR@startpars}%
{%
% \LWR@traceinfo{LWR@startpars}%
```

Ignore if inside a span:

```
\ifnumcomp{\value{LWR@spandepth}}{>}{0}%
{}%
{%
```

See if currently handling HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If already in paragraph mode, do nothing.

```
    {}%
```

If not currently in paragraph mode:

```
    {%
```

At the start of each paragraph, generate an opening tag:

```
        \PushPreHook{par}{\LWR@openparagraph}%
```

At the end of each paragraph, generate closing tag then do regular /par actions:

```
        \let\par\LWR@closeparagraph

    }% an intentionally blank line
```

Are now handling paragraphs, but have not yet actually started one:

```
    \global\setbool{LWR@doingstartpars}{true}%
```

No <par> tag yet to undo:

```
    \global\boolfalse{LWR@doingapar}%
}% nestspan
% \LWR@traceinfo{LWR@startpars: done}%
}
```

`\LWR@stoppars` Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```
\newcommand*{\LWR@stoppars}%
{%
```

Ignore if inside a span:

```
\ifnumcomp{\value{LWR@spandepth}}{>}{0}%
```

```
{}%
{%
```

See if currently handling HTML paragraphs:

```
    \ifbool{LWR@doingapar}%
```

if currently in an HTML paragraph:

```
    {%
```

Print a closing tag:

```
        \leavevmode\LWR@orignewline%
        \LWR@htmltagc{/\LWR@tagregularparagraph}%
        \LWR@orignewline%
```

No longer have an open HTML paragraph:

```
        \global\boolfalse{LWR@doingapar}%
```

Disable the special `minipage` & `\hspace` interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}
    }%
```

If was not in an HTML paragraph:

```
    {}%
```

See if currently allowing HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If so: clear the `par` hook to no longer catch paragraphs:

```
        {\ClearPreHook{par}}%
```

Else: Do nothing:

```
        {}%
```

No longer in paragraph mode:

```
    \global\setbool{LWR@doingstartpars}{false}%
```

No <p> tag to undo:

```
    \global\boolfalse{LWR@doingapar}%
}% nestspan
}

\end{warpHTML}
```

54 Indentfirst

Pkg indentfirst indentfirst redefines `\@afterindentfalse` to be `\@afterindenttrue`. This is reversed `\AtBeginDocument` here.

for HTML output:

```
\begin{warpHTML}

\AtBeginDocument{
\def\@afterindentfalse{\let\if@afterindent\iffalse}
\@afterindentfalse
}
\let\LWR@afterindent@syntaxhighlight\fi% syntax highlighting

\end{warpHTML}
```

55 Page headers and footers

for HTML & PRINT:

```
\begin{warpall}
```

In the following, catcode is manually changed back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
\newcommand{\LWR@firstpagetop}{} % for the home page alone
\newcommand{\LWR@pagetop}{} % for all other pages
\newcommand{\LWR@pagebottom}{}
```

`\HTMLFirstPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLFirstPageTop}[1]{%
    \renewcommand{\LWR@firstpagetop}{#1}%
}
```

`\HTMLPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageTop}[1]{%
    \renewcommand{\LWR@pagetop}{#1}%
}
```

`\HTMLPageBottom` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageBottom}[1]{%
    \renewcommand{\LWR@pagebottom}{#1}%
}

\end{warpall}
```

56 css

for HTML output:

```
\begin{warpHTML}
```

`\LWR@currentcss` The css filename to use. This may be changed mid-document using `\CSSFilename`, allowing different css files to be used for different sections of the document.

```
\newcommand*{\LWR@currentcss}{lwarp.css}
```

`\CSSFilename` {⟨*new-css-filename.css*⟩} Assigns the css file to be used by the following HTML pages.

```
\newcommand*{\CSSFilename}[1]{%
\renewcommand*{\LWR@currentcss}{#1}%
\@onelevel@sanitize\LWR@currentcss%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\CSSFilename}[1]{}
\end{warpprint}
```

57 MathJax script

for HTML output:

```
\begin{warpHTML}
```

Default: `lwarp_mathjax.txt`

`\LWR@mathjaxfilename` The MathJax script filename to use. This file is copied into the head of each HTML page. This may be changed mid-document using `\MathJaxFilename`, allowing the use of a custom MathJax script, such as for a local repository, or different MathJax script files to be used for different sections of the document.

```
\newcommand*{\LWR@mathjaxfilename}{lwarp_mathjax.txt}
```

`\MathJaxFilename` {⟨*filename*⟩} Assigns the MathJax script file to be used by the following HTML pages.

```
\newcommand*{\MathJaxFilename}[1]{%
    \renewcommand*{\LWR@mathjaxfilename}{#1}%
    \@onelevel@sanitize\LWR@mathjaxfilename%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\MathJaxFilename}[1]{}
\end{warpprint}
```

58 Title, HTML meta author, HTML meta description

for HTML output:

```
\begin{warpHTML}
```

`\title` {⟨*title*⟩} Modified to remember `\thetitle`, which is used to set the HTML page titles.

```
\let\LWR@origtitle\title

\renewcommand*{\title}[1]{%
    \LWR@origtitle{#1}%
    \begingroup%
        \renewcommand{\thanks}[1]{}%
        \protected@xdef\thetitle{#1}%
    \endgroup%
}
```

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

`\HTMLTitle` {⟨*Titlename*⟩} The Title to place into an HTML meta tag. The default is to use the document `\title`'s setting.

```
\providecommand{\thetitle}{\BaseJobname}

\newcommand{\theHTMLTitle}{\thetitle}

\newcommand{\HTMLTitle}[1]{\renewcommand{\theHTMLTitle}{#1}}
```

`\HTMLAuthor` {⟨*authorname*⟩} The author to place into an HTML meta tag. If none given, the default is `\theauthor`, which is empty unless the titling package is used.

```
\providecommand{\theauthor}{}

\newcommand{\theHTMLAuthor}{\theauthor}

\newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}
```

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using `\HTMLDescription`, allowing different HTML descriptions to be used for different sections of the document.

⚠ HTML author Do not use double quotes, and do not exceed 150 characters.

`\HTMLDescription` {⟨*New HTML meta description.*⟩} Assigns the HTML file's description meta tag.

```
\newcommand{\LWR@currentHTMLDescription}{}

\newcommand{\HTMLDescription}[1]{%
```

```
\renewcommand{\LWR@currentHTMLDescription}{#1}
}

\end{warpall}
```

59 Footnotes

lwarp uses native LaTeX footnote code, although with its own \box to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering

To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for \alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

footmisc

The footmisc stable option is emulated by lwarp.

⚠ sectioning commands

When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the stable option, provide a short TOC entry, and \protect the \footnote:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc

⚠ memoir

If using memoir class, with which lwarp preloads footmisc, the stable option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust \secnumdepth instead.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handle differently.

59.1 Regular page footnotes

In HTML documents, footnotes are placed at the bottom of the web page or the section, depending on `FootnoteDepth`, using the LaTeX box `\LWR@footnotebox`. Using this instead of the original `\footins` box avoids having footnotes be printed by the output routine, since footnotes should be printed per HTML page instead of per PDF page.

See section 59.4 for the implementation.

59.2 Minipage footnotes

See section 59.5 for how minipage footnotes are gathered. See section 89.3 for how minipage footnotes are placed into the document.

59.3 Titlepage thanks

See section 66.7 for titlepage footnotes.

59.4 Regular page footnote implementation

for HTML & PRINT:

```
\begin{warpall}
```

Ctr `FootnoteDepth` Default: 3

Determines how deeply to place footnotes in the HTML files, similar to `tocdepth`. The default of 3 places footnotes before each `\subsubsection` or higher. See table 9 for a table of LaTeX section headings.

```
\newcounter{FootnoteDepth}
\setcounter{FootnoteDepth}{3}
```

Ctr `footnoteReset` Default: `0`

If non-zero, the `footnote` counter is reset to this value each time the footnotes are printed, as controlled by `FootnoteDepth`. For the manyfoot and bigfoot packages, additional counters such as `footnote<suffix>Reset` will be defined as well. These counters may be set non-zero by the user, and are also set if the perpage's `\MakePerPage` or `\MakeSortedPerPage` macros are used for the `footnote` or `footnote<suffix>` counters.

(The name is not capitalized because it is made from the counter's name with "Reset" appended.)

```
\newcounter{footnoteReset}
\setcounter{footnoteReset}{0}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@footnotebox Patch LaTeX footnotes to use a new \box instead of an insert for lwarp footnotes. This avoids having the original \footins appear at the bottom of a lateximage, which is on its own new page.

```
\newbox\LWR@footnotebox
```

Much of the following has unneeded print-mode formatting removed.

\@makefntext {⟨*text*⟩}

```
\long\def\@makefntext#1{\textsuperscript{\@thefnmark}~#1}
```

\@makefnmark

```
\def\@makefnmark{%
    \textsuperscript{\@thefnmark}%
}
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or lateximage, in which case paragraph tags must be added manually.

In a lateximage during HTML output, the lateximage is placed inside a print-mode minipage, but the footnotes are broken out by:

```
\def\@mpfn{footnote}
\def\thempfn{\thefootnote}
\let\@footnotetext\LWR@footnotetext
```

\LWR@@footnotetext {⟨*text*⟩} {⟨*footnote box name*⟩}

Factored to allow multiple footnote boxes for manyfoot.

```
\long\def\LWR@@footnotetext#1#2{%
\LWR@traceinfo{LWR@footnotetext}%
\global\setbox\csname #2\endcsname=\vbox{%
```

Add to any current footnotes:

```
    \unvbox\csname #2\endcsname%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Open a group:

```
    \color@begingroup%
```

Use HTML superscripts in the footnote even inside a lateximage:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{#1}%
```

Closing paragraph tag:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {\par}%
        {%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@orignewline%
        }%
```

Close the group:

```
    \color@endgroup%
}% vbox
```

Paragraph handling:

```
\LWR@ensuredoingapar%
}%
```

`\LWR@footnotetext` {⟨*text*⟩}

```
\long\def\LWR@footnotetext#1{\LWR@@footnotetext{#1}{LWR@footnotebox}}
```

`\@footnotetext` {⟨*text*⟩}

```
\LetLtxMacro\@footnotetext\LWR@footnotetext
```

59.5 Minipage footnote implementation

Patch LaTeX minipage footnotes to use a new \box instead of an insert for lwarp minipage footnotes. This avoids having the original \@mpfootins appear at the bottom of a lateximage, which is on its own new page.

```
\newbox\LWR@mpfootnotes
```

\@mpfootnotetext {⟨*text*⟩}

```
\long\def\@mpfootnotetext#1{%
\LWR@traceinfo{@mpfootnotetext}%
\global\setbox\LWR@mpfootnotes\vbox{%
    \unvbox\LWR@mpfootnotes%
    \reset@font\footnotesize%
    \hsize\columnwidth%
    \@parboxrestore%
    \protected@edef\@currentlabel%
        {\csname p@mpfootnote\endcsname\@thefnmark}%
    \color@begingroup%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%

    \@makefntext{%
        \ignorespaces#1%
    }%
```

Don't add the closing paragraph tag if are inside a lateximage:

```
    \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}{>}{0}}%
        {}%
        {%
            \leavevmode\LWR@orignewline%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@origpar%
        }%
    \color@endgroup%
}% vbox
```

Paragraph handling:

```
\LWR@ensuredoingapar%
\LWR@traceinfo{@mpfootnotetext: done}%
}
```

\thempfootnote Redefined to remove the \itshape, which caused an obscure compiling error in some situations.

```
\AtBeginDocument{
\def\thempfootnote{\@alph\c@mpfootnote}
}
```

59.6 Printing pending footnotes

\LWR@@printpendingfootnotes {⟨*footnote counter name*⟩}

```
\newcommand*{\LWR@@printpendingfootnotes}[1]{%
\expandafter\ifvoid\csname LWR@#1box\endcsname\else
    \LWR@forcenewpage
    \begin{BlockClass}{footnotes}
    \LWR@origmedskip
    \unvbox\csuse{LWR@#1box}
    \setbox\csuse{LWR@#1box}=\vbox{}
    \end{BlockClass}
    \ifltxcounter{#1Reset}{%
        \ifnumgreater{\value{#1Reset}}{0}{%
            \setcounter{#1}{\value{#1Reset}}%
            \addtocounter{#1}{-1}%
        }{}%
    }{}%
\fi
}
```

\LWR@printpendingfootnotes Enclose the footnotes in a class, print, then clear. For manynotes, new footnotes may be added via \appto.

```
\newcommand*{\LWR@printpendingfootnotes}{%
    \LWR@@printpendingfootnotes{footnote}%
}
```

\LWR@maybeprintpendingfootnotes {⟨*depth*⟩} Used to print footnotes before sections only if formatting for an EPUB or word processor:

```
\newcommand*{\LWR@maybeprintpendingfootnotes}[1]{%
\ifboolexpr{
    not test{\ifnumcomp{#1}{>}{\value{FootnoteDepth}}} or
    bool{FormatEPUB} or
    bool{FormatWP}
}%
{\LWR@printpendingfootnotes}%
{}%
}
```

\LWR@printpendingmpfootnotes Enclose the minipage footnotes in a class, print, then clear.

```
\newcommand*{\LWR@printpendingmpfootnotes}{%
\ifvoid\LWR@mpfootnotes\else
    \LWR@forcenewpage
    \begin{BlockClass}{footnotes}
    \LWR@print@vspace*{\baselineskip}
    \unvbox\LWR@mpfootnotes
    \setbox\LWR@mpfootnotes=\vbox{}
    \end{BlockClass}
\fi
}
```

```
\end{warpHTML}
```

60 Marginpars

\marginpar [⟨*left*⟩] {⟨*right*⟩} \marginpar may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the \marginpar. Paragraph breaks are converted to <br /> tags.

\marginparBlock [⟨*left*⟩] {⟨*right*⟩} To include block-related macros, use \marginparBlock, which takes the same arguments but creates a instead of a . A line break will occur in the text where the \marginBlock occurs.

for HTML output:

```
\begin{warpHTML}
```

\marginpar [⟨*left*⟩] {⟨*right*⟩}

```
\renewcommand{\marginpar}[2][]{%
\ifbool{FormatWP}%
{%
\begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{marginblock}
#2
\end{LWR@BlockClassWP}
}%
{%
    \LWR@htmlspanclass{marginpar}{#2}%
}%
}
```

\marginparBlock [⟨*left*⟩] {⟨*right*⟩}

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

HTML version.

```
\newcommand{\marginparBlock}[2][]{%
\LWR@stoppars%
\ifbool{FormatWP}%
{%
   \begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{marginblock}
```

```
    #2
    \end{LWR@BlockClassWP}
}{%
    \begin{BlockClass}[width:2in; float:right; margin:10pt]{marginparblock}
    #2
    \end{BlockClass}
}%
\LWR@startpars%
}
```

\reversemarginpar

```
\renewcommand*{\reversemarginpar}{}
```

\normalmarginpar

```
\renewcommand*{\normalmarginpar}{}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\marginparBlock [⟨*left*⟩] {⟨*right*⟩}

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

Print version.

```
\LetLtxMacro\marginparBlock\marginpar
```

```
\end{warpprint}
```

61 Splitting HTML files

- Files are split according to FileDepth and CombineHigherDepths.
- Filenames are sanitized by \LWR@filenamenoblanks.
- \LWR@newhtmlfile finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

for HTML & PRINT:

```
\begin{warpall}
```

Ctr FileDepth {⟨*section depth*⟩} determines how deeply to break into new HTML files, similar to tocdepth. The default of -5 produces one large HTML file.

```
\newcounter{FileDepth}
\setcounter{FileDepth}{-5}
```

Bool `CombineHigherDepths` Combile higher-level sections together into one file?

```
\newbool{CombineHigherDepths}
\booltrue{CombineHigherDepths}
```

`\FilenameLimit` Maximum length of the generated filenames.

```
\newcommand*{\FilenameLimit}{80}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@thisfilename` The currently-active filename or number. At first, this is the homepage.

```
\AtBeginDocument{
\ifbool{FileSectionNames}%
    {\newcommand*{\LWR@thisfilename}{\HomeHTMLFilename}}
    {\newcommand*{\LWR@thisfilename}{0}}
}
```

`\LWR@thisnewfilename` The filename being sanitized.

```
\newcommand*{\LWR@thisnewfilename}{}
```

`\LWR@simplifyname` * {⟨*expression*⟩} Simplify `\LWR@thisnewfilename`.

If starred, detokenizes the input expression. If found, changes the expression to a single detokenized dash.

```
\NewDocumentCommand{\LWR@simplifyname}{s m}{%
\IfBooleanTF{#1}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {\detokenize{#2}}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {#2}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}
}
```

`\LWR@simplifycustom` User-defined filename simplifications. Redefine with `\newcommand`.

```
\newcommand*{\LWR@simplifycustom}{}
```

`\FilenameSimplify` * {⟨*phrase*⟩} Assign a user-defined filename simplification. Appends to `\LWR@simplifycustom`.

```
\NewDocumentCommand{\FilenameSimplify}{s m}{%
```

```
\IfBooleanTF{#1}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname*{#2}%
    }%
}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname{#2}%
    }%
}%
}
```

`\LWR@filenamenoblanks` {⟨*filename*⟩}

Convert blanks into dashes, removes short words, store result in `\LWR@thisfilename`.

Also see `\LWR@nullfonts` for nullified macros.

```
\newcommand*{\LWR@filenamenoblanks}[1]{%
\begingroup
```

Locally temporarily disable direct-formatting commands, not used in filenames:

```
\LWR@nullfonts%
\renewcommand*{\LWR@htmltagc}[1]{}%

\edef\LWR@thisnewfilename{#1}%
```

Replaces common macros with hyphens. (`\&` is done by `\LWR@nullfonts`.)

```
\RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
\LWR@simplifyname{\_}
\LWR@simplifyname{\#}
\LWR@simplifyname{\textbackslash}
\LWR@simplifyname{\protect}
\LWR@simplifyname{\ }
\LWR@simplifyname{\textless}
\LWR@simplifyname{\textgreater}

\edef\LWR@thisnewfilename{\detokenize\expandafter{\LWR@thisnewfilename}}%

\LWR@traceinfo{LWR@filenamenoblanks edef: !\LWR@thisnewfilename!}%
\fullexpandarg%
```

Convert spaces into hyphens:

```
\LWR@simplifyname*{ }
```

Convert punctutation into hyphens:

```
\LWR@simplifyname*{!}
\LWR@simplifyname*{,}
```

```
\LWR@simplifyname*{'}
\LWR@simplifyname*{+}
\LWR@simplifyname*{,}
\LWR@simplifyname*{/}
\LWR@simplifyname*{:}
\LWR@simplifyname*{;}
\LWR@simplifyname*{=}
\LWR@simplifyname*{?}
\LWR@simplifyname*{@}
\LWR@simplifyname*{^}
\LWR@simplifyname*{&}
\LWR@simplifyname*{"}
\LWR@simplifyname*{<}
\LWR@simplifyname*{>}

\LWR@simplifyname{\LWRbackslash}
```

Braces are removed entirely to avoid extra dashes in the result.

```
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRleftbrace}{}[\LWR@thisnewfilename]%
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRrightbrace}{}[\LWR@thisnewfilename]%

\LWR@simplifyname{\LWRpercent}
\LWR@simplifyname{\LWRdollar}

\LWR@simplifyname*{|}
\LWR@simplifyname*{^}
\LWR@simplifyname*{~}
\LWR@simplifyname*{[}
\LWR@simplifyname*{]}
\LWR@simplifyname*{`}
```

Convert short words:

```
\LWR@simplifyname*{-s-}
\LWR@simplifyname*{-S-}
\LWR@simplifyname*{-a-}
\LWR@simplifyname*{-A-}
\LWR@simplifyname*{-an-}
\LWR@simplifyname*{-AN-}
\LWR@simplifyname*{-to-}
\LWR@simplifyname*{-TO-}
\LWR@simplifyname*{-by-}
\LWR@simplifyname*{-BY-}
\LWR@simplifyname*{-of-}
\LWR@simplifyname*{-OF-}
\LWR@simplifyname*{-and-}
\LWR@simplifyname*{-AND-}
\LWR@simplifyname*{-for-}
\LWR@simplifyname*{-FOR-}
\LWR@simplifyname*{-the-}
\LWR@simplifyname*{-THE-}
```

Convert custom words:

```
\LWR@simplifycustom%
```

Convert multiple hyphens:

```
\LWR@simplifyname*{-----}
\LWR@simplifyname*{----}
\LWR@simplifyname*{---}
\LWR@simplifyname*{--}
```

If pdfLaTeX and not `utf8` encoding, don't try to convert emdash, endash:

```
\ifPDFTeX% pdflatex or dvi latex
\ifdefstring{\inputencodingname}{utf8}{%
\LWR@simplifyname*{—}
%     emdash
\LWR@simplifyname*{–}
%     endash
}{}%
\else% not PDFTeX
\LWR@simplifyname*{—}
\LWR@simplifyname*{–}
\fi%
```

If starts with a dash, remove the leading dash:

```
\IfBeginWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleLeft{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

If ends with a dash, remove the trailing dash:

```
\IfEndWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleRight{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

Limits the length of the filename:

```
\StrLeft{\LWR@thisnewfilename}{\FilenameLimit}[\LWR@thisnewfilename]%
```

Return the global result:

```
\global\let\LWR@thisfilename\LWR@thisnewfilename%
\endgroup%
\LWR@traceinfo{LWR@filenamenoblanks: result is \LWR@thisfilename}%
}
```

Ctr `LWR@previousautopagelabel`

Remembers which autopage label was most recently generated. Used to avoid duplicates.

```
\newcounter{LWR@previousautopagelabel}
\setcounter{LWR@previousautopagelabel}{-1}
```

File *_html.aux A new entry in the *_html.aux file is used to help cross-references:

```
\newlabel{autopage-<nnn>}{{<x>}{<y>}}
```

\LWR@newautopagelabel {⟨*pagenumber counter*⟩}

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\newcommand*{\LWR@newautopagelabel}[1]{%
\ifnumequal{\value{LWR@previousautopagelabel}}{\value{page}}%
{}% no action if this autopage label has already been defined
{%
    \label{\BaseJobname-autopage-\arabic{#1}}%
    \setcounter{LWR@previousautopagelabel}{\value{page}}
}%
}
```

61.1 Customizing MathJax

\LWR@customizedMathJax Additional MathJax definitions to be added to the start of each html page.

```
\newcommand*{\LWR@customizedMathJax}{}
```

\CustomizeMathJax MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each html page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

```
\newcommand*{\CustomizeMathJax}[1]{%
    \appto{\LWR@customizedMathJax}{%
        \(#1\)\par
    }%
}
```

\LWR@customizeMathJax Prints MathJax commands to the html output.

```
\newcommand{\LWR@customizeMathJax}{%
\ifbool{mathjax}{

\LWR@stoppars
\LWR@htmlcomment{Nullify \textbackslash{}ensuremath, footnotes for MathJax:}
```

```
\(\newcommand\ensuremath[1]{##1}\)

\(\newcommand\footnote[2][]{\text{( Footnote ##1 )}}\)

\(\newcommand\footnotemark[1][]{\text{( Footnote ##1 )}}\)

\LWR@htmlcomment{Additional customizations for MathJax:}

\LWR@customizedMathJax

\LWR@startpars
}{}
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

`\CustomizeMathJax` The print-mode version:

```
\newcommand*{\CustomizeMathJax}[1]{}
```

`\FilenameSimplify` `*` {⟨*expression*⟩}

```
\NewDocumentCommand{\FilenameSimplify}{s m}{}

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@newhtmlfile` {⟨*section name*⟩}

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and CSS are, then adds navigation, side TOC, header, and starts the text body.

```
\newcommand*{\LWR@newhtmlfile}[1]{
\LWR@traceinfo{LWR@newhtmlfile}
```

At the bottom of the ending file:

```
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{div}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}

\LWR@printpendingfootnotes

```

No footer between files if EPUB:

```
\ifbool{FormatEPUB}
{}
{

    \ifdefempty{\LWR@pagebottom}{}{%
        \LWR@htmlelement{footer}

        \LWR@pagebottom

        \LWR@htmlelementend{footer}
    }
}
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}}
```

End of this HTML file:

```
\LWR@stoppars
\LWR@htmltag{/body}\LWR@orignewline
\LWR@htmltag{/html}\LWR@orignewline
\LWR@traceinfo{LWR@newhtmlfile: about to LWR@orignewpage}
\LWR@orignewpage

\addtocounter{LWR@htmlfilenumber}{1}%
```

If using a filename based on section name, create a version without blanks. The filename without blanks will be placed into `\LWR@thisfilename`. Duplicates will be detected using MD5 hashes.

If not using a filename, the file number will be used instead.

```
\ifbool{FileSectionNames}%
{%
```

Convert the section name to a filename with blanks and common words removed. The resulting filename is in `\LWR@thisfilename`.

```
    \LWR@filenamenoblanks{#1}%
```

Create a macro name from the MD5 hash of the file name, to detect duplicates:

```
    \edef\LWR@hashedname{\LWR@mdfive{\LWR@thisfilename}}%
```

If the macro name is not yet defined, this filename is unique.

```
    \ifcsundef{LWR@filename\LWR@hashedname}{%
```

If the filename is unique, create a macro using the hashed name, to be used to test for additional duplicates in the future.

```
        \csdef{LWR@filename\LWR@hashedname}{}%
    }{%
```

If the filename is not unique, create an error.

```
        \PackageError{lwarp}
            {%
                Section name\MessageBreak
                ``#1'',\MessageBreak
                at the line number listed below,\MessageBreak
                generates the filename\MessageBreak
                ``\LWR@thisfilename'',\MessageBreak
                which appears to be a duplicate.\MessageBreak
                There is a previous section with an\MessageBreak
                identical or similar name%
            }
            {%
                Lwarp sanitizes most symbols and a few common short words
                when generating file names, and this may cause a conflict.
            }
    }
}
```

If using file numbers instead of names, the name is set to the next file number.

```
{\renewcommand*{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}
```

Include an HTML comment to instruct lwarpmk where to split the files apart. Uses pipe-separated fields for `split_html.gawk`. Uses monospaced font with ligatures disabled for everything except the title.

```
\LWR@traceinfo{LWR@newhtmlfile: about to print start file}%
```

`\LWR@nullfonts` to allow math in a section name.

```
\begingroup%
\LWR@nullfonts%
\LWR@htmlblockcomment{%
|Start file|%
\LWR@htmlsectionfilename{\LWR@thisfilename}|%
}
\endgroup%
```

At the top of the starting file:

```
\LWR@stoppars

```

Start a new file with the given section name:

```
\LWR@filestart[#1]
```

Track the page numbers:

```
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@latestautopage}%
```

No navigation between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\LWR@topnavigation}
```

No header if between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {


        \ifdefempty{\LWR@pagetop}{}{
            \LWR@htmlelement{header}

            \LWR@pagetop

            \LWR@htmlelementend{header}
        }
    }
```

The container for the sidetoc and text body:

```
\LWR@htmlelementclass{div}{bodyandsidetoc}
```

No sideTOC if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\LWR@sidetoc}
```

Start of the <textbody>:

```
\LWR@htmlelementclass{div}{bodycontainer}
\LWR@htmlelementclass{section}{textbody}
```

Print title only if there is one. Skip if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}%
    {}%
    {%
```

```
        \ifcsvoid{thetitle}{}{%
            \LWR@printthetitle%
        }%
    }%
```

Keep paragraph tags disabled for now:

```
\LWR@stoppars
```

If using MathJax, disable `\ensuremath` by printing a nullified definition at the start of each file, and add further customizations:

```
\LWR@customizeMathJax

\LWR@traceinfo{LWR@newhtmlfile: done}
}

\end{warpHTML}
```

62 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing LaTeX code and packages. Formatting is handled by CSS, so the emulated code has much less work to do than the print versions.

Unicode

⚠ accents in filenames

Section names and the resulting filenames with accented characters are partially supported, depending on the ability of *pdflatex* to generate characters and *pdftotext* to read them. If extra symbols appear in the text, it may be that *pdflatex* is actually producing a symbol over or under a character, resulting in *pdftotext* picking up the accent symbol separately.

XeLaTeX and LuaLaTeX directly support accented section and file names.

for HTML output:

```
\begin{warpHTML}
```

62.1 User-level starred section commands

`\ForceHTMLPage`

For HTML output, forces the next section to be on its own HTML page, if `FileDepth` allows, even if starred. For use with `\printindex` and others which generate a starred section which should be on its own HTML page. Also see `\ForceHTMLTOC`.

For print output, no effect.

```
\newbool{LWR@forcinghtmlpage}
\boolfalse{LWR@forcinghtmlpage}

\newcommand*{\ForceHTMLPage}{%
\global\booltrue{LWR@forcinghtmlpage}%
}
```

\ForceHTMLTOC For HTML output, forces the next section to have a TOC entry, even if starred. For use with \printindex and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with tocbibind. Also see \ForceHTMLPage.

For print output, no effect.

```
\newbool{LWR@forcinghtmltoc}
\boolfalse{LWR@forcinghtmltoc}

\newcommand*{\ForceHTMLTOC}{%
\global\booltrue{LWR@forcinghtmltoc}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\ForceHTMLPage}{}
\newcommand*{\ForceHTMLTOC}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

62.2 Book class commands

\mainmatter ⚠ Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```
\newbool{LWR@mainmatter}
\DeclareDocumentCommand{\mainmatter}{}{%
\booltrue{LWR@mainmatter}%
}
```

\frontmatter Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```
\DeclareDocumentCommand{\frontmatter}{}{%
\boolfalse{LWR@mainmatter}%
}
```

\backmatter Declare the back matter section of the document. Does not reset the page number.

```
\DeclareDocumentCommand{\backmatter}{}{%
\boolfalse{LWR@mainmatter}
}
```

62.3 Sectioning support macros

\LWR@sectionnumber {⟨*section type*⟩}

Typeset a section number and its trailing space with CSS formatting:

```
\newcommand*{\LWR@sectionnumber}[1]{%
\InlineClass{sectionnumber}{#1}%
}
```

autosec A tag used by the TOC and index.

\LWR@createautosec {⟨*section type*⟩}

Create an autosection tag.

```
\newcommand*{\LWR@createautosec}[1]{%
\LWR@htmltag{%
    #1 % space
    id=\textquotedbl\LWR@print@mbox{autosec-\arabic{page}}\textquotedbl%
}%
}
```

\LWR@pushoneclose {⟨*sectiontype*⟩} Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

⚠ \LWR@stoppars must be executed first.

```
\NewDocumentCommand{\LWR@pushoneclose}{m}{%
\LWR@traceinfo{LWR@pushoneclose #1}%
    \LWR@pushclose{#1}%
}
```

\LWR@startnewdepth {⟨*sectiontype*⟩}

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

⚠ \LWR@stoppars must be executed first.

```
\NewDocumentCommand{\LWR@startnewdepth}{m}{%
```

Close any stacked sections up to this new one.

```
\LWR@closeprevious{#1}%
```

Push a new section depth:

```
\LWR@pushoneclose{#1}%
}
```

Ctr LWR@prevFileDepth Remembers the previous LWR@FileDepth.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
\newcounter{LWR@prevFileDepth}
\setcounter{LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

`\@seccntformat` {⟨*sectiontype*⟩}

```
\def\@seccntformat#1{\csname the#1\endcsname\quad}
```

`\simplechapterdelim` Used by tocbibind and anonchap.

```
\newcommand*{\simplechapterdelim}{}
```

`\@chapcntformat` {⟨*sectiontype*⟩}

`\let` to `\@seccntformat` by default, but may be redefined by `\simplechapter` and `\restorechapter` from tocbibind or anonchap.

```
\let\@chapcntformat\@seccntformat
```

`\@partcntformat` {⟨*sectiontype*⟩}

`\let` to `\@seccntformat` by default, but may be redefined by ctex.

```
\let\@partcntformat\@seccntformat
```

`\@partnameformat` Prints “Part” for part sections.

Nullified by ctex.

```
\newcommand*{\@partnameformat}{\LWR@isolate{\partname}~}%
```

Ctr `LWR@currentautosec` Records the page number when the section was created. If a math expression is included in the section name, and SVG math is used, the corresponding `lateximage` will cause the page number to change by the time the following autosec label is created.

```
\newcounter{LWR@currentautosec}
\setcounter{LWR@currentautosec}{1}
```

`\LWR@section` * [⟨*TOC name*⟩] {⟨*name*⟩} {⟨*sectiontype*⟩}

The common actions for the high-level sectioning commands.

```
\DeclareDocumentCommand{\LWR@section}{m m m m}{%
\IfValueTF{#2}%
    {\LWR@traceinfo{LWR@section: starting #4 #2}}%
    {\LWR@traceinfo{LWR@section: starting #4 #3}}%
\LWR@maybeprintpendingfootnotes{\csuse{LWR@depth#4}}%
\LWR@stoppars%
\LWR@startnewdepth{#4}%
```

Cancel special minipage horizontal space interaction:

```
\global\boolfalse{LWR@minipagethispar}%
```

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for \part*, for appendix.

Generate a new LaTeX page so that TOC and index page number points to the section:

```
\LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%
\IfBooleanT{#1}{\LWR@traceinfo{LWR@section: starred}}%
\ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}}{}%
\ifthenelse{%
    \(%
        \(\NOT\equal{#1}{\BooleanTrue}\)\OR%
        \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)\OR%
        \(\boolean{LWR@forcinghtmlpage}\)%
    \)%
    \AND%
    \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{FileDepth}}%
    \AND%
    \(%
        \NOT\boolean{CombineHigherDepths}\OR%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}%
    \)%
    \AND%


    \(% phantomsection
        \NOT\isempty{#3}%
        \OR%
        \(\NOT\equal{#1}{\BooleanTrue}\)%
    \)%
}%
```

If so: start a new HTML file:

```
{% new file
    \LWR@traceinfo{LWR@section: new HTML file}%
```

See if there was an optional TOC name entry:

```
    \IfNoValueTF{#2}%
```

If no optional entry

```
        {\LWR@newhtmlfile{#3}}%
```

If yes an optional entry

```
        {\LWR@newhtmlfile{#2}}%
}% new file
```

Else: No new HTML file:

```
{% not new file
```

Generate a new LaTeX page so that TOC and index page number points to the section:

```
    \LWR@traceinfo{LWR@section: not a new HTML file, about to LWR@orignewpage}%
    \LWR@orignewpage%
}% not new file

```

Remember this section's name for `\nameref`:

```
\IfValueT{#3}{%
    \LWR@traceinfo{LWR@section: about to LWR@setlatestname}%
    \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
}%
```

Print an opening comment with the level and the name; ex: "section" "Introduction" Footnotes may be used in section names, which would also appear in the HTML section opening comments, so the short TOC entry is used if possible, and a limited opening comment is made if the sectional unit is starred.

```
\ifbool{HTMLDebugComments}{%
    \begingroup%
    \LWR@nullfonts%
    \IfBooleanTF{#1}% starred
    {\LWR@htmlcomment{Opening #4*}}%
    {%
        \IfNoValueTF{#2}% short TOC
            {\LWR@htmlcomment{Opening #4 ``#3''}}%
            {\LWR@htmlcomment{Opening #4 ``#2''}}%
    }\LWR@orignewline%
    \endgroup%
}{}
```

For inline sections paragraph and subparagraph, start a new paragraph now:

```
\ifthenelse{%
    \cnttest{\@nameuse{LWR@depth#4}}{>=}{\LWR@depthparagraph}%
}%
    {\LWR@startpars}%
    {}%
```

Create the opening tag with an autosec:

```
\LWR@traceinfo{LWR@section: about to LWR@createautosec}%
\LWR@createautosec{\@nameuse{LWR@tag#4}}%

\setcounter{LWR@currentautosec}{\value{page}}%
```

Check if starred:

```
\IfBooleanTF{#1}%
{%
    \LWR@traceinfo{LWR@section: starred}%
```

Starred, but also forcing a TOC entry, so add unnumbered TOC name or regular name:

```
    \ifbool{LWR@forcinghtmltoc}%
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
    }%
    {}%
}% starred
```

Not starred, so step counter and add to TOC:

```
{% not starred
```

Only add a numbered TOC entry if section number is not too deep:

```
    \ifthenelse{%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
    }%
    {% if secnumdepth
```

If in the main matter, step the counter and add the TOC entry. For `article` class, lwarp assumes that all is mainmatter.

```
        \LWR@traceinfo{LWR@section: about to test main matter}%
        \ifbool{LWR@mainmatter}%
        {%
            \LWR@traceinfo{LWR@section: yes mainmatter}%
            \refstepcounter{#4}%
```

Add main matter numbered TOC entry with the TOC name or the regular name:

```
            \LWR@traceinfo{LWR@section: about to addcontentsline}%
            \addcontentsline{toc}{#4}%
            {%
                \protect\numberline{%
                    \@nameuse{pre#4name}%
                    \@nameuse{the#4}%
                    \@nameuse{post#4name}%
                }%
                {%
                    \ignorespaces%
              \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
                }%
            }%
            \LWR@traceinfo{LWR@section: finished addcontentsline}%
        }% end of if main matter
```

If not main matter, add unnumbered TOC name or regular name:

```
        {% not main matter
            \LWR@traceinfo{LWR@section: no main matter}%
            \addcontentsline{toc}{#4}{%
                \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
            }%
        }% end of not main matter
    }% end of secnumdepth
```

Deeper than secnumdepth, so add an unnumbered TOC entry:

```
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
    }%
```

For part, print “Part”:

```
    \ifbool{LWR@mainmatter}%
    {%
        \ifthenelse{%
            \(\cnttest{\@nameuse{LWR@depth#4}}{<=}%
                {\value{secnumdepth}}\) \AND%
            \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)%
        }%
            {\@partnameformat}%
            {}%
```

Print the section number:

```
        \LWR@traceinfo{LWR@section: about to print section number}%
        \ifthenelse{%
            \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
        }%
            {%
                \ifstrequal{#4}{part}%
                {\protect\LWR@sectionnumber{\@partcntformat{#4}}}%
                {%
                    \ifstrequal{#4}{chapter}%
                        {\protect\LWR@sectionnumber{\@chapcntformat{#4}}}%
                        {\protect\LWR@sectionnumber{\@seccntformat{#4}}}%
                }%
            }%
            {}%
        \LWR@traceinfo{LWR@section: finished print section number}%
    }{}%
}% end of not starred
```

Print the section name:

```
\LWR@traceinfo{LWR@section: about to print the section name}%
\LWR@isolate{#3}%
```

Close the heading tag, such as /H2:

```
\LWR@traceinfo{LWR@section: about to close the heading tag}%
\LWR@htmltag{\@nameuse{LWR@tag#4end}}%
\LWR@orignewline%
```

Generate a LaTeX label:

```
\LWR@traceinfo{LWR@section: about to create the LaTeX label}%
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosec}\LWR@orignewline%
```

Start paragraph handing unless is an inline paragraph or subparagraph:

```
\ifthenelse{%
    \cnttest{\@nameuse{LWR@depth#4}}{<}{\LWR@depthparagraph}%
}%
    {\LWR@startpars}%
    {}%
```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a `\part*` to start a new HTML page. This is used by appendix.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a `\listoftables` was tested in the middle of the document. The `\chapter*` for the list was not allowing a new HTML page for the section following it while `CombineHigherDepths` was true.

```
\ifthenelse{%
    \NOT\equal{#1}{\BooleanTrue}\OR%
    \cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}%
}%
    {% not starred
        \setcounter{LWR@prevFileDepth}{\@nameuse{LWR@depth#4}}%
    }% not starred
    {}%
```

Reset to defaults if not a phantomsection:

```
\ifstrempty{#3}%
    {}%
    {%
        \global\boolfalse{LWR@forcinghtmlpage}%
        \global\boolfalse{LWR@forcinghtmltoc}%
    }%
%
\LWR@traceinfo{LWR@section: done}%
}
```

62.4 Pre- and post- sectioning names

\prebookname
\postbookname

Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prebookname}{}
\providecommand*{\postbookname}{}
```

\prepartname
\postpartname

Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prepartname}{}
\providecommand*{\postpartname}{}
```

\prechaptername
\postchaptername

Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prechaptername}{}
\providecommand*{\postchaptername}{}
```

\presectionname
\postsectionname

Always null, but provided here for algorithmic simplicity in \LWR@section.

```
\providecommand*{\presectionname}{}
\let\postsectionname\presectionname

\let\presubsectionname\presectionname
\let\postsubsectionname\postsectionname

\let\presubsubsectionname\presectionname
\let\postsubsubsectionname\postsectionname

\let\preparagraphname\presectionname
\let\postparagraphname\postsectionname

\let\presubparagraphname\presectionname
\let\postsubparagraphname\postsectionname
```

62.5 \section and friends

For memoir, a second optional argument is allowed.

For hypbmsec, a second optional argument or either parenthesis argument is allowed.

Each of these additional arguments are for headers or PDF bookmarks, and are ignored for HTML output.

\part * (⟨*2:PDF name*⟩) [⟨*3:TOC name*⟩] [⟨*4:PDF name*⟩] (⟨*5:PDF name*⟩) {⟨*6:name*⟩}

```
\newcommand{\part@preamble}{}% for koma-script

\DeclareDocumentCommand{\part}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{part}%

```

```
    \part@preamble% for koma-script
    \renewcommand{\part@preamble}{}%
}
```

\chapter * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\let\@printcites\relax% for quotchap package

\newcommand{\chapter@preamble}{}% for koma-script

\@ifundefined{chapter}
{}
{%
    \DeclareDocumentCommand{\chapter}{s d() o o d() m}{%
        \LWR@section{#1}{#3}{#6}{chapter}%

        \@printcites% for quotchap package

        \chapter@preamble% for koma-script
        \renewcommand{\chapter@preamble}{}%
    }
}
```

\section * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\section}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{section}%
}
```

\subsection * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\subsection}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{subsection}%
}
```

\subsubsection * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\subsubsection}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{subsubsection}%
}
```

\paragraph * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\paragraph}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{paragraph}%
}
```

\subparagraph * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\subparagraph}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{subparagraph}%
}
```

```
\end{warpHTML}
```

63 Starting a new file

for HTML & PRINT:

```
\begin{warpall}
```

`\HTMLLanguage` Default language for the HTML `lang` tag.

```
\newcommand*{\LWR@currentHTMLLanguage}{en-US}

\newcommand*{\HTMLLanguage}[1]{%
\renewcommand*{\LWR@currentHTMLLanguage}{#1}%
}
```

`\theHTMLTitleSeparator` May be used inside `\theHTMLTitleSection` to separate the website's overall HTML title and the particular page's section name.

```
\ifPDFTeX% pdflatex or dvi latex
    \ifdefstring{\inputencodingname}{utf8}{%
        \newcommand*{\theHTMLTitleSeparator}{ — }% EMdash
    }{%
        \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
    }%
\else%
    \ifpTeX
        \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
    \else
        \newcommand*{\theHTMLTitleSeparator}{ — }% EMdash
    \fi%
\fi%
```

`\HTMLTitleBeforeSection` Sets the HTML page's meta `title` tag to show the website title before the section name.

```
\newcommand*{\HTMLTitleBeforeSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
    }%
}
```

`\HTMLTitleAfterSection` Sets the HTML page's meta `title` tag to show the section name before the website title.

```
\newcommand*{\HTMLTitleAfterSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLSection\theHTMLTitleSeparator\theHTMLTitle%
    }%
}
```

`\theHTMLTitleSection` Forms the HTML page's meta `title` tag. The default is to show the website title before the section name.

```
\HTMLTitleBeforeSection
```

`\theHTMLSection` The section name is passed to `\LWR@filestart`, which then sets `\theHTMLSection` for use inside `\theHTMLTitleSection` to create an HTML meta `title` tag.

```
\newcommand*{\theHTMLSection}{}

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@filestart` `[⟨sectionname⟩]` Creates the opening HTML tags.

```
\newcommand*{\LWR@filestart}[1][]{%
\LWR@traceinfo{LWR@filestart !#1!}%
```

Locally temporarily disable direct-formatting commands:

```
\begingroup%
\LWR@nullfonts%
```

Save the section name for use while creating the HTML meta `title` tag:

```
\edef\theHTMLSection{#1}%
```

Create the page's HTML header:

```
\LWR@htmltag{!DOCTYPE html}\LWR@orignewline
```

The language is user-adjustable:

```
\LWR@htmltag{%
   html lang=\LWR@orig@textquotedbl\LWR@currentHTMLLanguage\LWR@orig@textquotedbl%
}\LWR@orignewline
```

Start of the meta data:

```
\LWR@htmltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
\LWR@htmltag{%
    meta charset=\LWR@orig@textquotedbl{}UTF-8\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

Author:

```
\ifthenelse{\equal{\theHTMLAuthor}{}}%
    {}%
    {%
        \LWR@htmltag{%
```

```
        meta name=\LWR@orig@textquotedbl{}author\LWR@orig@textquotedbl\ % space
         content=\LWR@orig@textquotedbl\theHTMLAuthor\LWR@orig@textquotedbl\ /%
        }\LWR@orignewline%
    }%
```

lwarp is the generator:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}generator\LWR@orig@textquotedbl\ % space
   content=\LWR@orig@textquotedbl{}LaTeX lwarp package\LWR@orig@textquotedbl\ /%
}\LWR@orignewline%
```

If there is a description, add it now:

```
\ifdefempty{\LWR@currentHTMLDescription}{}{%
    \LWR@htmltag{%
      meta name=\LWR@orig@textquotedbl{}description\LWR@orig@textquotedbl\ % space
      content=\LWR@orig@textquotedbl\LWR@currentHTMLDescription\LWR@orig@textquotedbl\ /%
    }\LWR@orignewline
}%
```

Mobile-friendly viewport:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}viewport\LWR@orig@textquotedbl\ % space
   content=\LWR@orig@textquotedbl{}width=device-width, initial-scale=1.0\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

IE patch:

```
\LWR@htmltag{!-\/-[if lt IE 9]}\LWR@orignewline
\LWR@htmltag{%
    script % space
    src=\LWR@orig@textquotedbl{}%
        http://html5shiv.googlecode.com/svn/trunk/html5.js%
    \LWR@orig@textquotedbl%
}%
\LWR@htmltag{/script}\LWR@orignewline
\LWR@htmltag{![endif]-\/-}\LWR@orignewline
```

The page's title, if there is one. A section name is also added if given.

```
\ifthenelse{\equal{\theHTMLTitle}{}}%
    {}%
    {%
        \LWR@htmltag{title}%
        \ifdefempty{\theHTMLSection}%
            {\theHTMLTitle}%
            {\theHTMLTitleSection}%
        \LWR@htmltag{/title}\LWR@orignewline%
    }%
```

The page's stylesheet:

```
\LWR@htmltag{%
    link % space
    rel=\LWR@orig@textquotedbl{}stylesheet\LWR@orig@textquotedbl\ % space
    type=\LWR@orig@textquotedbl{}text/css\LWR@orig@textquotedbl\ % space
    href=\LWR@orig@textquotedbl\LWR@currentcss\LWR@orig@textquotedbl\ /%
}%
\LWR@orignewline
```

Optional MathJax support. The HTML tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```
\ifbool{mathjax}%
{%
    \begingroup%
    \LWR@restoreoriglists%
    \boolfalse{LWR@verbtags}%

        \verbatiminput{\LWR@mathjaxfilename}%

    \booltrue{LWR@verbtags}%
    \endgroup%
    \LWR@stoppars%
}% end of mathjax
{}%
```

End of the header:

```
\LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```
\LWR@htmltag{body}\LWR@orignewline
\endgroup
\LWR@traceinfo{LWR@filestart: done}
}

\end{warpHTML}
```

64 Starting HTML output

for HTML output:

```
\begin{warpHTML}
```

`\LWR@LwarpStart` Executed at the beginning of the entire document.

The use of `\textquotedbl` instead of " improves compatibility with xeCJK.

```
\catcode`\$=\active
```

```
\newcommand*{\LWR@LwarpStart}
{%
\LWR@traceinfo{LWR@lwarpStart}
```

If formatting for a word processor, force filedepth to single-file only, force HTML debug comments off.

```
\ifbool{FormatWP}{%
    \setcounter{FileDepth}{-5}%
    \boolfalse{HTMLDebugComments}%
}{}
```

Expand and detokenize `\HomeHTMLFilename` and `\HTMLFilename`:

```
\edef\LWR@strresult{\HomeHTMLFilename}
\edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
\edef\LWR@strresult{\HTMLFilename}
\edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}
```

Force onecolumn and empty page style:

```
\LWR@origonecolumn%
\LWR@origpagestyle{empty}%
```

No black box for overfull lines:

```
\overfullrule=0pt
```

Reduce chance of line overflow when HTML tags are added:

```
\LWR@print@footnotesize%
```

In PDF output, don't allow line breaks to interfere with HTML tags:

```
\LWR@print@raggedright%
\LetLtxMacro{\\}{\LWR@endofline}%
```

Spread the lines for *pdftotext* to read them well:

```
\linespread{1.3}%
```

For *pdftotext* to reliably identify paragraph splits:

```
\setlength{\parindent}{0pt}
\setlength{\parskip}{2ex}
```

For the `lateximage` record file:

```
\immediate\openout\LWR@lateximagesfile=\BaseJobname-images.txt
```

Removes space around the caption in the HTML:

```
\setlength{\belowcaptionskip}{0ex}
\setlength{\abovecaptionskip}{0ex}
```

Redefine the plain page style to be empty when used by index pages:

```
\renewcommand{\ps@plain}{}
```

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Float captions:

```
\let\LWR@origcaption\caption
```

Labels: `\ltx@label` is used in amsmath environments and is also patched by cleveref.
Label in HTML

```
\let\LWR@origltx@label\ltx@label
\let\ltx@label\LWR@htmlmathlabel
```

Not yet started any paragraph handling:

```
\global\boolfalse{LWR@doingapar}
\global\boolfalse{LWR@doingstartpars}
```

Document and page settings:

```
\mainmatter
\LWR@origpagenumbering{arabic}
```

Start a new HTML file and a header:

```
\LWR@traceinfo{LWR@lwarpStart: Starting new file.}
\LWR@filestart
\LWR@traceinfo{LWR@lwarpStart: Generating first header.}

\ifdefempty{\LWR@firstpagetop}{}{%
    \LWR@htmltag{header}\LWR@orignewline
    \LWR@startpars
    \LWR@firstpagetop
    \LWR@stoppars
    \LWR@htmltag{/header}\LWR@orignewline
}%

\LWR@htmlelementclass{div}{bodywithoutsidetoc}
\LWR@htmlelementclass{div}{bodycontainer}
\LWR@traceinfo{LWR@lwarpStart: Generating textbody.}
\LWR@htmlelementclass{section}{textbody}
```

Patch the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\LWR@patchlists
```

Ensure that math mode is active to call lwarp's patches:

```
\catcode`\$=\active
```

Required for \nameref to work with SVG math:

```
\immediate\write\@mainaux{\catcode`\string$\active}%
\LetLtxMacro\LWR@syntaxhighlightone$% balance for editor syntax highlighting
```

Allow HTML paragraphs to begin:

```
\LWR@startpars
```

If using MATHJAX, disable \ensuremath by printing a nullified definition at the start of each file, and add further customizations:

```
\LWR@customizeMathJax
```

First autopage label in case a figure occurs early.

```
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosec}%

\LWR@traceinfo{LWR@lwarpStart: done}
}
\catcode`\$=3% math shift until lwarp starts

\end{warpHTML}
```

65 Ending HTML output

for HTML output:

```
\begin{warpHTML}
```

\LWR@requesttoc {⟨*boolean*⟩} {⟨*suffix*⟩} Requests that a TOC, LOF, or LOTbe generated.

```
\newcommand*{\LWR@requesttoc}[2]{%
\ifbool{#1}
{
    \expandafter\newwrite\@nameuse{tf@#2}
    \immediate\openout \@nameuse{tf@#2} \jobname.#2\relax
}{}
}
```

\LWR@LwarpEnd Final stop of all HTML output:

```
\newcommand*{\LWR@LwarpEnd}
{
\LWR@stoppars
\LWR@closeprevious{finished}
```

At the bottom of the ending file:

Close the textbody:

```
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{div}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}
```

Print any pending footnotes:

```
\LWR@printpendingfootnotes
```

Create the footer:

```
\ifdefempty{\LWR@pagebottom}{}{%
    \LWR@htmlelement{footer}

    \LWR@pagebottom

    \LWR@htmlelementend{footer}
}
```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {
        \ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}
    }
```

```
\LWR@stoppars% final stop of all paragraphs
```

Finish the HTML file:

```
\LWR@htmltag{/body}\LWR@orignewline
\LWR@htmltag{/html}\LWR@orignewline
```

Seems to be required sometimes:

```
\LWR@orignewpage
}
```

\enddocument If labels have not changed, mark successful completion of the `lateximages` file. Executed as everything is being shut down.

```
\xpatchcmd{\enddocument}
    {%
        \if@tempswa
        \@latex@warning@no@line{Label(s) may have changed.
        Rerun to get cross-references right}%
```

```
        \fi
    }
    {%
        \if@tempswa
            \@latex@warning@no@line{Label(s) may have changed.
            Rerun to get cross-references right}%
        \else
            \immediate\write\LWR@lateximagesfile{%
                |end|end|end|%
            }%
        \fi
    }
    {}
    {
        \PackageWarningNoLine{lwarp}
        {%
            Could not patch \protect\enddocument.\MessageBreak
            If labels have changed, be sure to recompile before\MessageBreak
            creating lateximages with\MessageBreak
            \space\space lwarpmk limages,\MessageBreak
            or the images may be corrupt%
        }
    }
\end{warpHTML}
```

66 Title page

package support
load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

affiliation

lwarp provides for the \author macro an additional \affiliation macro to provide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using titlingpage's \theauthor in the main text.

reusing titlepage information

The titling package maintains the definitions of \thetitle, \theauthor, etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the \thanks and \affiliation removed, and for \author the \and is replaced to generate a simple inline list of authors separated by commas. Note: \theauthor does not work well with authblk unless the traditional LaTeX syntax is used.

load order
\theauthor, authblk

custom titlepages

\printtitle, \printauthor, etc., are provided for use inside a custom titlepage or titlingpage environment, and these retain the \thanks and \affiliation.

\printthanks

\printthanks has been added to force the printing of thanks inside a titlingpage environment when \maketitle is not used.

⚠ \thanks Inside a \titlepage or \titlingpage environment, use \thanks instead of \footnote for acknowledgements, etc.

66.1 Setting the title, etc.

The following provide setting commands for both HTML and print outputs.

\author \and {⟨*author*⟩} While using \maketitle and print mode, the author is treated as a single-column tabular and the \and feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as

```
\author{Name \\ Affiliation \and Second Name \\ Second Affiliation}
```

For HTML, the entire author block is placed inside a of class author, and each individual author is inside a of class oneauthor.

\@title \@author \@date \@title, \@author, and \@date store the values as originally assigned, including any \thanks, \and, or \affiliation. These are low-level macros intended to be used by other macros only inside a titlepage or titlingpage, and are used by \maketitle. The author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For HTML, these tabulars become side-by-side s of class oneauthor, all of which are combined into one of class author.

\printtitle \printauthor \printdate \printtitle, etc. are user-level macros intended to be used in custom titlepage or titlingpage environments in cases where \maketitle is not desired. These commands preserve the \thanks, etc., and should not be used in the main text.

\thetitle \theauthor \thedate \HTMLPageBottom \thetitle, \theauthor, and \thedate are available if titling has been loaded, and are sanitized user-level versions from which have been removed the \thanks and \affiliation, and \and is changed for inline text usage. The author is printed inline without \affiliation or \thanks, with \and placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each HTML page, such as:

```
\HTMLPageBottom{
  \begin{center}\textcopyright~20xx \theauthor\end{center}
}
```

⚠ \theauthor, authblk \theauthor does not work well if authblk is used. If \theauthor is important, it is recommended to use the standard LaTeX syntax for \author, optionally with lwarp's \affiliation macro as well.

⚠ affiliations After \maketitle has completed, \theauthor retains the definition of the author, but \and is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

\affiliation A solution, provide here, is to define a macro \affiliation which, during \maketitle, starts a new row and adds the affiliation, but after \maketitle is finished \affiliation

is re-defined to discard its argument, thus printing only the author names when \author is later used inline.

66.2 \if@titlepage

for HTML & PRINT:

```
\begin{warpall}
```

\if@titlepage Some classes do not provide \if@titlepage. In this case, provide it and force it false.

```
\ifcsvoid{@titlepagefalse}{
    \newif\if@titlepage
    \@titlepagefalse
}{}

\end{warpall}
```

66.3 Changes for \affiliation

\affiliation {⟨*text*⟩}

Adds the affiliation to the author for use in \maketitle.

Inside titlepage, this macro prints its argument. Outside, it is null.

for HTML & PRINT:

```
\begin{warpall}
\providerobustcmd{\affiliation}[1]{}
\end{warpall}
```

for PRINT output:

```
\begin{warpprint}

\AtBeginEnvironment{titlepage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}

\AtBeginDocument{
\@ifpackageloaded{titling}{
\AtBeginEnvironment{titlingpage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}
}{}% titling loaded
}% AtBeginDocument

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

Env titlepage Sets up a of class titlepage. Provided even for memoir class, since it is used by \maketitle.

```
\DeclareDocumentEnvironment{titlepage}{}
{
\renewrobustcmd{\affiliation}[1]{\\ \InlineClass{affiliation}{##1}}
\LWR@printpendingfootnotes
\LWR@forcenewpage
\BlockClass{titlepage}
}
{
\endBlockClass
\LWR@printpendingfootnotes
}

\end{warpHTML}
```

66.4 Printing the thanks

for HTML & PRINT:

```
\begin{warpall}
```

`\printthanks` Forces the `\thanks` to be printed.

This is necessary in a `titlingpage` environment when `\maketitle` was not used.

```
\newcommand*{\printthanks}{\LWR@stoppars\@thanks\LWR@startpars}

\end{warpall}
```

66.5 Printing the title, etc. in HTML

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in HTML:

for HTML output:

```
\begin{warpHTML}
```

`\printtitle`

```
\newcommand*{\printtitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

`\LWR@printthetitle` A private version which prints the title without footnotes, used to title each HTML page.

```
\newcommand*{\LWR@printthetitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \thetitle%
```

```
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

\printauthor HTML version.

```
\newcommand*{\printauthor}{
```

The entire author block is contained in a named author:

```
\begin{BlockClass}{author}
```

\and finishes one author and starts the next:

```
\renewcommand{\and}{%
\end{BlockClass}
\begin{BlockClass}{oneauthor}
}
```

Individual authors are contained in a named oneauthor:

```
\begin{BlockClass}{oneauthor}
\@author
\end{BlockClass}
\end{BlockClass}
}
```

\printdate

```
\newcommand*{\printdate}{%
\begin{BlockClass}{titledate}
\@date
\end{BlockClass}
}
```

```
\end{warpHTML}
```

66.6 Printing the title, etc. in print form

The following are for printing the title, etc. in a titlepage or a titlingpage in print form:

for PRINT output:

```
\begin{warpprint}
```

\printtitle

```
\newcommand*{\printtitle}{{\Huge\@title}}
```

\printauthor Print mode.

```
\newcommand*{\printauthor}
    {{\large\begin{tabular}[t]{c}\@author\end{tabular}}}
```

\printdate

```
\newcommand*{\printdate}{{\small\textit{\@date}}}
```

```
\end{warpprint}
```

66.7 \maketitle for HTML output

An HTML of class titlepage is used.

\thanks are a form of footnotes used in the title page. See section 59 for other kinds of footnotes.

See \thanksmarkseries{series}, below, to set the style of the footnote marks.

for HTML output:

```
\begin{warpHTML}
```

```
\@ifclassloaded{memoir}
{
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
}{% not memoir
\if@titlepage
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
\else
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
}
\fi
}% not memoir
```

\LWR@maketitlesetup Patches \thanks macros.

```
\newcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
\LWR@setfootnoteseries%
\def\@makefnmark{\textsuperscript{\thefootnote}}
```

\thefootnote ⇒ \nameuse{arabic}{footnote}, or
\thefootnote ⇒ \nameuse{fnsymbol}{footnote}

Redefine the footnote text:

```
\long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
\textsuperscript{\@thefnmark}~%
```

\makethanksmark ⇒ \thanksfootmark ⇒ \tamark ⇒ \@thefnmark ⇒ \itshape a (or similar)

Print the text:

```
##1%
}%
}
```

\@fnsymbol {⟨*counter*⟩}

Re-defined to use an HTML entity for the double vertical bar symbol. The original definition used `\|` which was not being seen by ***pdftotext***.

```
\def\@fnsymbol#1{\ifcase#1\or *\or \HTMLentity{dagger}\or \HTMLentity{Dagger}\or
   \HTMLentity{sect}\or \HTMLentity{para}\or \text{\HTMLunicode{2016}}\or
   **\or \HTMLentity{dagger}\HTMLentity{dagger} \or
   \HTMLentity{Dagger}\HTMLentity{Dagger} \else\@ctrerr\fi}
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage is used for all classes.

```
\begin{titlepage}
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any `\thanks` footnotes:

```
\LWR@stoppars\@thanks\LWR@startpars
```

Close the HTML titlepage div and cleanup:

```
\end{titlepage}
\setcounter{footnote}{0}%
\global\let\thanks\relax
\global\let\maketitle\relax
\global\let\@maketitle\relax
\global\let\@thanks\@empty
\global\let\@author\@empty
\global\let\@date\@empty
\global\let\@title\@empty
\global\let\title\relax
\global\let\author\relax
\global\let\date\relax
\global\let\and\relax
}
```

`\@maketitle` HTML mode. Typesets the title, etc.:

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
    \begin{BlockClass}{author}%
```

For IEEEtran class:

```
    \renewcommand*{\cr}{}%
    \renewcommand*{\crcr}{}%
    \renewcommand*{\noalign}{}%

        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }%
        \begin{BlockClass}{oneauthor}%
            \@author%
        \end{BlockClass}%
    \end{BlockClass}%
    \begin{BlockClass}{titledate}%
    \@date%
    \end{BlockClass}%
}
```

`\LWR@titlingmaketitle` `\maketitle` for use inside an HTML `titlingpage` environment.

```
\newcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\LWR@stoppars\@thanks\LWR@startpars
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\LWR@stoppars\@thanks\LWR@startpars
}
```

```
\end{warpHTML}
```

66.8 \published and \subtitle

\subtitle and \published

To add \subtitle and \published to the titlepage, load the titling package and use \AddSubtitlePublished in the preamble.

The default lwarp.css has definitions for the published and subtitle classes.

If titling is loaded, \AddSubtitlePublished creates a number of additional macros, and also assigns some of the titling hooks. If titling is not loaded, \AddSubtitlePublished creates null macros.

⚠ titling hooks

Do not use \AddSubtitlePublished if the user has patched the titling hooks for some other reason. Portions are marked \warpprintonly to reduce extra tags in HTML. Similarly, BlockClass has no effect in print mode. Thus, the following may be marked warpall.

for HTML & PRINT:

```
\begin{warpall}
```

\AddSubtitlePublished

Adds \published and \subtitle, and related.

```
\newcommand*{\AddSubtitlePublished}{%
\@ifpackageloaded{titling}{% yes titling package
    \newcommand{\@published}{}%
    \newcommand{\published}[1]{\gdef\@published{##1}}%
    \renewcommand*{\maketitlehooka}{\printpublished}%
    \newcommand*{\printpublished}{%
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{published}%
        \warpprintonly{\large\itshape}%
        \@published%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
    \newcommand{\@subtitle}{}%
    \newcommand{\subtitle}[1]{\gdef\@subtitle{##1}}%
    \renewcommand*{\maketitlehookb}{\printsubtitle}%
    \newcommand*{\printsubtitle}{%
```

```
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{subtitle}%
        \warpprintonly{\Large\itshape}%
        \@subtitle%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
}% yes titling package
{% no titling package
    \newcommand{\published}[1]{}%
    \newcommand*{\printpublished}{}%
    \newcommand{\subtitle}{}%
    \newcommand*{\printsubtitle}%
}% no titling package
}% \AddSubtitlePublished

\end{warpall}
```

67 Abstract

The following code replaces the LaTeX default, and will itself be replaced later if the abstract package is loaded.

for HTML output:

```
\begin{warpHTML}
```

`\abstractname` User-redefinable title for the abstract.

Also over-written by the babel package.

```
\providecommand*{\abstractname}{Abstract}
```

Some classes allow an optional name, so it is allowed here.

Env `abstract`

```
\DeclareDocumentEnvironment{abstract}{O{\abstractname}}
{
\LWR@forcenewpage
\BlockClass{abstract}
\BlockClassSingle{abstracttitle}{#1}
}
{
\endBlockClass
}

\end{warpHTML}
```

68 Quote and verse

68.1 Attributions

`\attribution` `{`⟨*name*⟩`}`

For use with quote, quotation, verse:

Ex: `"A quotation." \attribution{\textsc{Author Name}\\\textsl{Book Title}}`

for HTML output:

```
\begin{warpHTML}
\newcommand{\attribution}[1]{%
    \LWR@stoppars%
    \begin{BlockClass}{attribution}
    #1
    \end{BlockClass}
    \LWR@startpars%
}
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand{\attribution}[1]{
    \begin{flushright}
    \unskip
    #1
    \end{flushright}%
}
\end{warpprint}
```

68.2 Quotes, quotations

for HTML output:

```
\begin{warpHTML}
```

Env `quote`

```
\renewenvironment*{quote}
{
    \LWR@forcenewpage
    \LWR@htmlblocktag{blockquote}
}
{\LWR@htmlblocktag{/blockquote}}
```

Env `quotation`

```
\renewenvironment*{quotation}
{
    \LWR@forcenewpage
    \LWR@htmlblocktag{blockquote}
}
{\LWR@htmlblocktag{/blockquote}}
```

```
\end{warpHTML}
```

68.3 Verse

When using verse or memoir, always place a \\ after each line.

\attrib The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

68.3.1 LaTeX core verse environment

for HTML output:

```
\begin{warpHTML}
```

Env verse

```
\renewenvironment{verse}
               {\let\\\newline% lwarp
                \list{}{\itemsep      \z@
                        \itemindent   -1.5em%
                        \listparindent\itemindent
                        \rightmargin  \leftmargin
                        \advance\leftmargin 1.5em}%
                \item\relax}
               {\endlist}
```

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

68.3.2 verse and memoir

The following lengths are used by verse and memoir. They may be set in either print or HTML output, but are only used in HTML. This allows the user to set \vleftskip and \leftmargini for print output, and optionally select different values for HTML.

Len \HTMLvleftskip Sets \vleftskip inside a verse environment in HTML.

```
\newlength{\HTMLvleftskip}
\setlength{\HTMLvleftskip}{1em}
```

Len \HTMLleftmargini Sets \leftmargini inside a verse environment in HTML.

```
\newlength{\HTMLleftmargini}
\setlength{\HTMLleftmargini}{4.5em}
```

```
\end{warpall}
```

69 Verbatim and tabbing

for HTML & PRINT:

```
\begin{warpall}
```

Len \VerbatimHTMLWidth Width to use in HTML Verbatim environment.

This width is used when placing line numbers to the right. Ignored during print output.

```
\newlength{\VerbatimHTMLWidth}
\setlength{\VerbatimHTMLWidth}{4in}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Bool LWR@verbtags Used to temporarily turn off verbatim tags while doing \verbatiminput in the HTML head.

```
\newbool{LWR@verbtags}
\booltrue{LWR@verbtags}
```

\LWR@atbeginverbatim [⟨*1: style*⟩] {⟨*2: negative* \baselineskip \vspace⟩} {⟨*3: class*⟩}

Encloses a verbatim environment with the given CSS class.

The use of \textquotedbl instead of " improves compatibility with XeCJK.

```
\newcommand*{\LWR@atbeginverbatim}[3][]
{%
```

Avoid excessive space between lines:

```
\setlength{\parskip}{0ex}%
```

Stop generating HTML paragraph tags:

```
\LWR@stoppars%
```

Create a new pre of the given class. The tags may temporarily be turned off for internal use, such as loading the MathJax script.

```
\ifbool{LWR@verbtags}{%
    \LWR@htmltag{pre class=\textquotedbl#3\textquotedbl%
        \ifthenelse{\equal{#1}{}}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
    \LWR@orignewline% pre
    \leavevmode\unskip\LWR@print@vspace*{-#2\baselineskip}%
}{}%
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the css for the verse class.

```
\begingroup%
```

```
% \LWR@print@normalsize%
\LWR@origttfamily%
\LWR@print@small%
```

Since inside a <pre>, restore the original list processing:

```
\LWR@restoreoriglists%
```

Turn off babel-french extra space before punctuation:

```
\LWR@FBcancel%
```

Do not produce HTML tags for \hspace inside a verse par. Restore plain LaTeX \hspace functionality:

```
\LWR@select@print@hspace%
}
```

\LWR@afterendverbatim {⟨*negative* \baselineskip \vspace⟩}

Finishes enclosing a verbatim environment.

```
\newcommand*{\LWR@afterendverbatim}[1]{%
\endgroup%
\par%
```

At the end of the environment, close the pre:

```
\ifbool{LWR@verbtags}{%
    \LWR@print@vspace*{-#1\baselineskip}%
    \noindent\LWR@htmltag{/pre}\LWR@orignewline% pre
}{}%
```

Resume regular paragraph handling:

```
\LWR@startpars%
}
```

`\verbatiminput` {⟨*filename*⟩}

Patch `\verbatiminput` to add HTML tags:

```
\let\LWRV@origverbatim@input\verbatim@input

\renewcommand{\verbatim@input}[2]{%
\ifbool{LWR@verbtags}{\LWR@forcenewpage}{}%
\LWR@atbeginverbatim{2.5}{Verbatim}%
\LWRV@origverbatim@input{#1}{#2}%
\LWR@afterendverbatim{1.5}%
}
```

Env `verbatim`

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verbatim.}
\AtBeginEnvironment{verbatim}{%
\LWR@forcenewpage%
\LWR@atbeginverbatim{2.5}{verbatim}%
}
\AfterEndEnvironment{verbatim}{%
    \LWR@afterendverbatim{1}%
}
}
```

Env `tabbing` The `tabbing` environment works, except that SVG math and `latexmages` do not yet work inside the environment.

⚠ math in `tabbing` If math is used inside `tabbing`, place `tabbing` inside a `latexmage` environment, which will render the entire environment as a single SVG image.

```
\newcommand*{\LWR@HTML@tabbing}{%
\LWR@forcenewpage%
\LWR@atbeginverbatim{3}{tabbing}%
\LWR@print@tabbing%
}

\newcommand*{\LWR@HTML@endtabbing}{%
    \LWR@print@endtabbing%
    \LWR@afterendverbatim{1}%
}

\LWR@formatted{tabbing}
\LWR@formatted{endtabbing}


\end{warpHTML}
```

70 Theorems

\newtheorem {⟨*text*⟩} [⟨*counter*⟩] -or- [⟨*oldname*⟩] {⟨*text*⟩}

A few minor changes are made to supply HTML tags.

- The entire theorem is placed into a of class theoremcontents.
- The label for each theorem is placed inside a of class theoremlabel.
- The contents are placed inside a of class theoremcontents.

for HTML output:

```
\begin{warpHTML}
```

\@begintheorem {⟨*name*⟩} {⟨*number*⟩}

```
\renewcommand{\@begintheorem}[2]{%
\LWR@forcenewpage
\BlockClass{theoremcontents}
\trivlist
\item[\InlineClass{theoremlabel}{#1\ #2\ }]\itshape
}
```

\@opargbegintheorem {⟨*name*⟩} {⟨*number*⟩} {⟨*oparg*⟩}

```
\renewcommand{\@opargbegintheorem}[3]{%
\LWR@forcenewpage
\BlockClass{theoremcontents}
\trivlist
\item[\InlineClass{theoremlabel}{#1\ #2\ (#3)\ }]\itshape
}
```

\@endtheorem

```
\renewcommand*{\@endtheorem}{%
\endtrivlist
\endBlockClass% theoremcontents
}
```

```
\end{warpHTML}
```

71 Lists

The environments itemize, enumerate, and description are patched when lwarp is started. These patches support the standard LaTeX environments, as well as those of enumerate, enumitem, and paralist, and at least the French version of babel. Additional patches are done on a package-specific basis.

The LaTeX source for itemize and enumerate are found in source2e, but the source for description is found in article.cls, etc.

empty item To have an empty item,use \mbox{} or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

```
begin{itemize}
item \mbox{}
    \begin{itemize}
...
    \end{itemize}
item \
    \begin{itemize}
  ...
    \end{itemize}
```

\makelabel While inside a list environment, lwarp nullifies a number of TeX horizontal skip and fill commands, allowing the user to define \makelabel for print mode while HTML mode ignores those commands.

⚠ label font When defining \makelabel in a list environment, use \textbf etc. instead of \bfseries.

71.1 List environment

for HTML output:

```
\begin{warpHTML}
```

\LWR@printcloselist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
```

\LWR@printopenlist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
```

\@mklab Removes PDF spacing.

```
\AtBeginDocument{
\def\@mklab#1{%
%      \hfil %
    #1}
\let\makelabel\@mklab
}
```

\@donoparitem Modified for HTML output by replacing TeX boxes with plain text. Also removes PDF spacing.

```
\def\@donoparitem{%
  \@noparitemfalse
%   \global\setbox\@labels\hbox{\hskip -\leftmargin
%                                \unhbox\@labels
%                                 \hskip \leftmargin}%
%   \if@minipage\else
%     \@tempskipa\lastskip
%     \vskip -\lastskip
%     \advance\@tempskipa\@outerparskip
%     \advance\@tempskipa -\parskip
%     \vskip\@tempskipa
%   \fi
}
```

\@item Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
\def\LWR@HTML@item[#1]{%
\LWR@traceinfo{@item}
  \if@noparitem
    \@donoparitem
  \else
%     \if@inlabel
%       \indent
        \par
%     \fi
    \ifhmode
%       \unskip\unskip
        \par
    \fi
    \if@newlist
      \if@nobreak
        \@nbitem
      \else
%         \addpenalty\@beginparpenalty
%         \addvspace\@topsep
%         \addvspace{-\parskip}%
      \fi
    \else
%       \addpenalty\@itempenalty
%       \addvspace\itemsep
    \fi
    \global\@inlabeltrue
  \fi
%   \everypar{%
    \@minipagefalse
    \global\@newlistfalse

%     \if@inlabel
%       \global\@inlabelfalse

%       {\setbox\z@\lastbox
%        \ifvoid\z@
%          \kern-\itemindent
%        \fi}%
```

```
%       \box\@labels
%       \penalty\z@
%     \fi

%     \if@nobreak
%       \@nobreakfalse
%       \clubpenalty \@M
%     \else
%       \clubpenalty \@clubpenalty
%       \everypar{}%
%     \fi}%

  \if@noitemarg
    \@noitemargfalse
    \if@nmbrlist

      \refstepcounter\@listctr
    \fi
  \fi


    \makelabel{#1} % extra space
%   \sbox\@tempboxa{\makelabel{#1}%
%   \global\setbox\@labels\hbox{%
%     \unhbox\@labels
%     \hskip \itemindent
%     \hskip -\labelwidth
%     \hskip -\labelsep
%     \ifdim \wd\@tempboxa >\labelwidth
%       \box\@tempboxa

%     \else
%       \hbox to\labelwidth {\unhbox\@tempboxa}%
%     \fi
%     \hskip \labelsep}%
  \ignorespaces%
}
```

\@nbitem

```
\def\@nbitem{%
%   \@tempskipa\@outerparskip
%   \advance\@tempskipa -\parskip
%   \addvspace\@tempskipa
}
```

\LWR@listitem [⟨*label*⟩]

Handles \item inside a list, itemize, or enumerate.

See \LWR@openparagraph where extra \hspace is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@listitem}{%
\LWR@stoppars%
\LWR@startnewdepth{listitem}%
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

`\LWR@nulllistfills` Nullifies various TEX fill commands, in case they are used inside `\makelabel`. Problems are caused when these are nullified all the time.

```
\newcommand*{\LWR@nulllistfills}{%
\renewcommand*{\hss}{}%
\renewcommand*{\llap}[1]{##1}%
\renewcommand*{\rlap}[1]{##1}%
\renewcommand*{\hfil}{}%
\renewcommand*{\hfilneg}{}%
\renewcommand*{\hfill}{}%
}
```

Env `list` {⟨*label*⟩} {⟨*commands*⟩}

```
\newcommand*{\LWR@liststart}{%
\LWR@traceinfo{LWR@liststart}%
\LWR@stoppars%
\LWR@pushoneclose{list}%
\LWR@htmltag{\LWR@printopenlist}\LWR@orignewline%
\LWR@startpars%
\setlength{\topsep}{0pt}%
\setlength{\partopsep}{0pt}%
\setlength{\itemsep}{0pt}%
\setlength{\parsep}{0pt}%
\setlength{\leftmargin}{0pt}%
\setlength{\rightmargin}{0pt}%
\setlength{\listparindent}{0pt}%
\setlength{\itemindent}{0pt}%
\setlength{\labelsep}{1em}%
\LWR@nulllistfills%
}
```

```
\newcommand*{\LWR@listend}{%
\LWR@traceinfo{LWR@listend}%
\LWR@stoppars%
\LWR@closeprevious{list}%
\LWR@startpars%
}
```

71.2 Itemize

`\LWR@itemizeitem` [⟨*label*⟩]

Handles `\item` inside an itemize or enumerate.

See \LWR@openparagraph where extra \hspace is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@itemizeitem}{%
\LWR@stoppars%
\LWR@startnewdepth{listitem}%
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

Env itemize [⟨*options*⟩]

```
\newcommand*{\LWR@itemizestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

71.3 Enumerate

An HTML unordered list is used with customized LaTeX-generated labels.

Env enumerate [⟨*options*⟩]

```
\newcommand*{\LWR@enumeratestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

71.4 Description

\LWR@descitem [⟨*label*⟩] Handles an \item inside a description.

```
\newcommand*{\LWR@descitem}[1][]%
{%
\LWR@stoppars%
\LWR@setlatestname{#1}%
\LWR@startnewdepth{descitem}%
```

While creating the label, encase it inside tags and disable \hspace, which is used by the standard classes to add space to the labels.

```
\begingroup%
\let\LWR@orig@desc@makelabel\makelabel
\renewcommand*{\makelabel}[1]{%
    \LWR@htmltag{dt}%
```

```
    \LWR@orig@desc@makelabel{#1}%
    \LWR@htmltag{/dt}%
}
\LWR@select@html@nohspace%
\LWR@origitem[#1]%
\endgroup%
\LWR@orignewline%
\LWR@htmltag{dd}%
\LWR@startpars%
}
```

Env `description` [⟨*options*⟩]

```
\newcommand*{\LWR@descriptionstart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printclosedescription}
\renewcommand*{\LWR@printopenlist}{dl}
\let\item\LWR@descitem%
\LWR@nulllistfills%
}
```

71.5 Patching the lists

`\LWR@patchlists` Patches list environments.

`\LWR@patchlists` remembers `\item` as defined by whatever packages have been loaded, then patches the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\newcommand*{\LWR@patchlists}{%
    \LetLtxMacro\item\LWR@listitem%
    \LetLtxMacro\@item\LWR@HTML@item%
    \renewcommand*{\@trivlist}{%
        \LWR@traceinfo{@trivlist start}%
        \LWR@liststart%
        \LWR@orig@trivlist%
        \LWR@traceinfo{@trivlist done}%
    }%
    \renewcommand*{\trivlist}{%
        \LWR@traceinfo{trivlist}%
        \LWR@origtrivlist%
    }%
    \renewcommand*{\endtrivlist}{%
        \LWR@traceinfo{endtrivlist start}%
        \LWR@origendtrivlist\LWR@listend%
        \LWR@traceinfo{endtrivlist done}%
    }%
    \renewcommand*{\itemize}{%
        \LWR@itemizestart\LWR@origitemize%
    }%
    \renewcommand*{\enumerate}{%
        \LWR@enumeratestart\LWR@origenumerate%
```

```
    }%
    \renewcommand*{\description}{%
        \LWR@descriptionstart\LWR@origdescription%
    }%
}
```

`\LWR@restoreoriglists` Restores the original `trivlist` environment.

```
\newcommand*{\LWR@restoreoriglists}{%
\LWR@traceinfo{LWR@restoreoriglists}%
\LetLtxMacro\item\LWR@origitem%
\LetLtxMacro\@item\LWR@orig@item%
\let\@trivlist\LWR@orig@trivlist%
\let\trivlist\LWR@origtrivlist%
\let\endtrivlist\LWR@origendtrivlist%
\LetLtxMacro\itemize\LWR@origitemize%
\LetLtxMacro\enditemize\LWR@endorigitemize%
\LetLtxMacro\enumerate\LWR@origenumerate%
\LetLtxMacro\endenumerate\LWR@endorigenumerate%
\LetLtxMacro\description\LWR@origdescription%
\LetLtxMacro\enddescription\LWR@endorigdescription%
\let\@mklab\LWR@orig@mklab%
\let\makelabel\LWR@origmakelabel%
\let\@donoparitem\LWR@orig@donoparitem%
\let\@nbitem\LWR@orig@nbitem%
}

\end{warpHTML}
```

72 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax of the LaTeX core and the various tabular-related packages.

72.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, siunitx `S` columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include `tabular` and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

⚠ floatrow

This includes before and after defining any macro which used \ttabbox from floatrow.

⚠ tabular inside another environment

- When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

⚠ \newcolumntype

- \newcolumntype is ignored; unknown column types are set to l.

Rules:

- Doubled \hlines, \midrules, and vertical rules are supported.

vertical rules

- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

full-width rules

- \toprule, \midrule, \bottomrule, and \hline ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional -2ex is ignored in HTML, but improves the visual formatting in the print output.

⚠ \warpprintonly
⚠ Misplaced \noalign

- For \toprule and \bottomrule, when combined with a warpprint or warpHTML environment, if a "Misplaced \noalign" error occurs, change

  ```
  This & That \endhead
  ```

  to

  ```
  \warpprintonly{This & That \endhead}
  ```

  and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevent to HTML output.

Other:

- tabularx ignores the width, but X columns do produce paragraph columns or multicolumns.

longtable headings

- For longtable, place headings and footings which do not apply to HTML inside \warpprintonly{}.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as \multirow. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

  ```
  \warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
  \warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
  ```

⚠ tabular inside a

- In LaTeX, a tabular may be placed inside a minipage, but in HTML a <table> may not be inside a . If this situation is detected, a warning is printed instructing the user to isolate the using \warpprintonly or the warpprint environment.

for HTML output:

```
\begin{warpHTML}
```

72.2 Temporary package-related macros

These macros are temporary placeholders for macros defined by various packages. If the relevent package is not loaded, these placeholders are used instead.

72.2.1 arydshln

Emualated by the original LaTeX non-dashed versions.

```
\LetLtxMacro\hdashline\hline
\LetLtxMacro\cdashline\cline
\LetLtxMacro\firsthdashline\hline
\LetLtxMacro\lasthdashline\hline
```

72.3 Token lookahead

Used by \LWR@futurenonspacelet to look at the next token.

\LWR@mynexttoken

```
\newcommand\LWR@mynexttoken\relax
```

\futurelet copies the next token then executes a function to analyze

\LWR@futurenonspacelet does the same, but ignores intervening white space

Based on the booktabs style:

\LWR@futurenonspacelet

```
\def\LWR@futurenonspacelet#1{\def\LWR@cs{#1}%
\afterassignment\LWR@fnslone\let\nexttoken= }
\def\LWR@fnslone{\expandafter\futurelet\LWR@cs\LWR@fnsltwo}
\def\LWR@fnsltwo{%
\expandafter\ifx\LWR@cs\@sptoken\let\next=\LWR@fnslthree%
\else\let\next=\nexttoken\fi\next}
\def\LWR@fnslthree{\afterassignment\LWR@fnslone\let\next= }
```

\LWR@getmynexttoken Looks ahead and copies the next token into \LWR@mynexttoken.

```
\newcommand*{\LWR@getmynexttoken}{%
\LWR@traceinfo{LWR@getmynexttoken}%
% nothing must follow this next line
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@tabledatacolumntag
}
```

72.4 Tabular variables

Bool LWR@startedrow True if should print a row tag before this column.

```
\newbool{LWR@startedrow}
\boolfalse{LWR@startedrow}
```

Bool LWR@tabularcelladded True if have added a data cell for this position.

```
\newbool{LWR@tabularcelladded}
\boolfalse{LWR@tabularcelladded}
```

Ctr LWR@hlines Number of \hlines or \midrules above the next row.

```
\newcounter{LWR@hlines}
```

Ctr LWR@hdashedlines Number of arydshln dashed lines above the next row.

```
\newcounter{LWR@hdashedlines}
```

Bool LWR@doingtbrule — True if the next row will have a top/bottom rule above it.

```
\newbool{LWR@doingtbrule}
\boolfalse{LWR@doingtbrule}
```

Bool LWR@doingcmidrule — True if the next row will have a cmidrule above it.

This is used by `\LWR@tabularfinishrow` to force a final empty row to create the border for the `\cmidrule`.

```
\newbool{LWR@doingcmidrule}
\boolfalse{LWR@doingcmidrule}
```

Bool LWR@tableparcell — True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

```
\newbool{LWR@tableparcell}
```

Bool LWR@skippingmrowcell — True if are doing an empty `\multirow` cell, and thus there is no data tag to close.

```
\newbool{LWR@skippingmrowcell}
```

Bool LWR@skippingmcolrowcell — True if are doing an empty `\multicolumnrow` cell, and thus there is no data tag to close, and do not print `@` and `!` columns.

```
\newbool{LWR@skippingmcolrowcell}
```

Bool LWR@usedmultirow — Used to error if used `\multirow` or `\multicolumnrow` without using `\mrowcell` or `\mcolrowcell`.

```
\newbool{LWR@usedmultirow}
```

Bool LWR@foundmrowcell — Used to error if used `\multirow` or `\multicolumnrow` without using `\mrowcell` or `\mcolrowcell`.

```
\newbool{LWR@foundmrowcell}
```

Bool LWR@skipatbang — True if just finished a `\multicolumn` so should not create the trailing `@` or `!` columns table data cells.

```
\newbool{LWR@skipatbang}
```

Bool LWR@emptyatbang — True if finishing a row and should print empty `@` or `!` column table data cells.

```
\newbool{LWR@emptyatbang}
```

Bool LWR@intabularmetadata — True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.

```
\newbool{LWR@intabularmetadata}
\boolfalse{LWR@intabularmetadata}
```

Ctr `LWR@tabularDepth` Tracks whether & is being used inside a `tabular`.

```
\newcounter{LWR@tabulardepth}
\setcounter{LWR@tabulardepth}{0}
```

Ctr `LWR@tabularpardepth` Tracks whether should look ahead at the next token when encountering a `\par` while processing tabular contents.

When `LWR@tabularpardepth` is deeper than `LWR@tabulardepth` then lwarp has started looking at the contents of the `tabular`, and thus any `\par`s encountered must be followed by another token lookahead.

```
\newcounter{LWR@tabularpardepth}
\setcounter{LWR@tabularpardepth}{0}
```

```
\newcommand*{\LWR@colsresult}{}%temp storage for column format results
\newcommand*{\LWR@pposition}{}
\newcommand*{\LWR@pleft}{}
\newcommand*{\LWR@pright}{}
```

`LWR@tablecolspec` Holds the parsed column specification, of total width `LWR@tabletotalLaTeXcols`, not counting `@` and `!` columns.

Will contain a string such as `llrrccpc`, exactly one letter per LaTeX table column, without `@`, `!`, `>`, `<`, or the vertical bar.

`\LWR@strresult` Holds the result of `Str` functions.

```
\providecommand*{\LWR@strresult}{}
\providecommand*{\LWR@strresulttwo}{}
```

`\LWR@origcolspec` Holds the original column specs given to `tabular`.

```
\newcommand*{\LWR@origcolspec}{}
```

Ctr `LWR@tablecolspecwidth` Holds the number of tokens in the table columns specification.

This is includes one for each `@`, `!`, `<`, `>` column, and also one for each of the parameters of `p`, `@`, `!`, `<`, `>` columns, and three for each `D` column.

(This is not the total # of LaTeX columns in the table.)

```
\newcounter{LWR@tablecolspecwidth}
```

Ctr `LWR@tablecolspecindex` While parsing the LaTeX table column specification, starts at 1 and is incremented per token of the specification.

```
\newcounter{LWR@tablecolspecindex}
```

Ctr `LWR@tableLaTeXcolindex` While producing the table, resets to 1 at the start of the table and also at each end of line, and is incremented by 1 by each ampersand.

```
\newcounter{LWR@tableLaTeXcolindex}
```

Ctr LWR@tabletotalLaTeXcols — While parsing a table column specification, begins at 0 and increments by 1 per LaTeX table column. Eventually holds the final number of LaTeX table columns in each row, not counting @ and ! columns. (In HTML, @ and ! cells become their own columns, but are not included in LWR@tabletotalLaTeXcols.)

```
\newcounter{LWR@tabletotalLaTeXcols}
```

Ctr LWR@tabletotalLaTeXcolsnext — Holds the next LaTeX table column index while parsing, equal to one more than LWR@tabletotalLaTeXcols.

```
\newcounter{LWR@tabletotalLaTeXcolsnext}
```

LWR@colatspec — A data array of specifications for @ columns. The leftmost's index is leftedge, the others are counter values. See section 42.

LWR@colbangspec — A data array of specifications for ! columns. The leftmost's index is leftedge, the others are counter values. See section 42.

LWR@colbeforespec — A data array of specifications for > columns.

LWR@colafterspec — A data array of specifications for < columns.

LWR@colbarspec — A data array of specifications for vertical rules.

72.5 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:
http://tex.stackexchange.com/questions/11638/where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860

\LWR@instertatbangcols

```
\newcommand*{\LWR@insertatbangcols}{%
\ifbool{LWR@skipatbang}%
{}%
{%
    \LWR@printatbang{at}{\arabic{LWR@tableLaTeXcolindex}}%
    \LWR@printatbang{bang}{\arabic{LWR@tableLaTeXcolindex}}%
}%
}
```

\LWR@closetabledatacell — If LWR@skippingmrowcell or LWR@skippingmcolrowcell then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
\newcommand*{\LWR@closetabledatacell}{%
\global\booltrue{LWR@intabularmetadata}%
\ifbool{LWR@exitingtabular}%
{%
```

```
    \LWR@stoppars%
}%
{% not exiting tabular
    \ifboolexpr{bool{LWR@skippingmrowcell} or bool{LWR@skippingmcolrowcell}}%
    {%

        \LWR@stoppars%
```

If not skipping a \multicolumnrow cell, insert the @ and ! columns after this non-existant column.

```
        \ifbool{LWR@skippingmcolrowcell}%
            {}%
            {\LWR@insertatbangcols}%
    }%
    {% not skippingmrowcell
```

Insert any < then any @ and ! column contents, unless muted for the \bottomrule or a \multicolumn:

```
        \unskip%
        \ifboolexpr{%
            bool{LWR@tabularmutemods} or
            bool{LWR@skipatbang} or
            bool{LWR@emptyatbang}
        }%
        {}%
        {\LWR@getexparray{LWR@colafterspec}{\arabic{LWR@tableLaTeXcolindex}}}%
```

Close paragraphs:

```
        \LWR@stoppars%
        \global\boolfalse{LWR@tableparcell}%
```

Close the table data cell.

Close any color s.

```
        \whileboolexpr{test {\ifnumcomp{\value{LWR@cellcolordepth}}{>}{0}}}{%
            \LWR@htmltag{/div}\LWR@orignewline%
            \addtocounter{LWR@cellcolordepth}{-1}%
        }%
```

Skip the @ and ! cells if are closing a multicolumn cell.

```
        \leavevmode\unskip\LWR@htmltag{/td}\LWR@orignewline%
        \global\booltrue{LWR@tabularcelladded}%
        \LWR@insertatbangcols%
    }% not skipping mrowcell
}% not exiting tabular
\global\boolfalse{LWR@skippingmrowcell}%
\global\boolfalse{LWR@skippingmcolrowcell}%
\global\boolfalse{LWR@skipatbang}%
```

Color control. Column is set by >{} for each cell, so it must be cleared here.

```
\gdef\LWR@cellHTMLcolor{}
\gdef\LWR@columnHTMLcolor{}
\setcounter{LWR@cellcolordepth}{0}
}
```

When not used inside a tabular, & performs its original function as recorded here (with catcode 4).

```
\let\LWR@origampmacro&
```

```
\end{warpHTML}
```

72.5.1 Handling &

for HTML output:

```
\begin{warpHTML}
```

& Will behave depending on whether it is being used inside tabular.

& is redefined to test whether it is inside a tabular environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```
\newcommand*{\LWR@tabularampersand}{%
\LWR@traceinfo{LWR@tabularampersand}%
\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}%
{%
```

If not skipping a multirow cell, close the current data cell.

```
    \unskip%
    \LWR@closetabledatacell%
```

Move to the next column.

```
    \addtocounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
    \global\boolfalse{LWR@tabularcelladded}%
```

Look at the next token to decide multi or single column data tag.

```
    \LWR@getmynexttoken%
}%
```

If not inside a tabular, performs the original action:

```
{\LWR@origampmacro}%
}
```

& is left with its original catcode for now.

tikz package seems to require & be left alone until after tikz has been loaded. Also, cleveref uses the ampersand in one of its options.

& is made active inside a tabular.

& is left alone when in math alignments.

72.5.2 Filling an unfinished row

\LWR@tabularfinishrow Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
\newcommand*{\LWR@tabularfinishrow}{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
\ifboolexpr{%
    not bool {LWR@exitingtabular} or%
    bool{LWR@doingtbrule} or%
    bool{LWR@doingcmidrule} or%
    test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
    test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
    bool{LWR@startedrow}%
}{%
```

To temporarily turn off LWR@exitingtabular so that table data tags will still be generated:

If generating a final row for the \bottomrule borders, turn off the @, !, <, and > column output:

```
\ifbool{LWR@exitingtabular}{%
    \global\booltrue{LWR@tabularmutemods}%
}{%
    \global\boolfalse{LWR@tabularmutemods}%
}%
```

Locally reenable the table data tags until finished with the final row:

```
\global\boolfalse{LWR@exitingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
\whileboolexpr{%
    test {
      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}
    } or %
    (%
```

```
        bool{LWR@intabularmetadata} and%
        not bool{LWR@tabularcelladded} and%
        test {
        \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}
        }%
    )%
}%
{%
    \LWR@tabledatasinglecolumntag%
```

The following is essentially `\LWR@tabularampersand` with `LWR@emptyatbang` added to empty the following cells:

```
    \LWR@closetabledatacell%
    \addtocounter{LWR@tableLaTeXcolindex}{1}%
    \global\boolfalse{LWR@tabularcelladded}%
    \global\booltrue{LWR@emptyatbang}%
```

Starts the next cell:

```
  \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}%
        {\LWR@getmynexttoken}%
        {}%
}%
```

Reenable the original `LWR@exitingtabular` to close the entire table:

```
\ifbool{LWR@tabularmutemods}{%
    \global\booltrue{LWR@exitingtabular}%
}{%
    \global\boolfalse{LWR@exitingtabular}%
}%
\global\boolfalse{LWR@tabularmutemods}%

\global\boolfalse{LWR@emptyatbang}%
}{}% ifboolexpr
}
```

72.6 Handling \\

Inside tabular, `\\` is redefined to `\LWR@tabularendofline`

Throws away options `\\[dim]` or `\\*`

`\LWR@tabularendofline`

```
\NewDocumentCommand{\LWR@tabularendofline}{s o}{%
```

Finish the row:

```
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}%
    {\LWR@tabularfinishrow}%
```

```
    {\LWR@closetabledatacell}%
\LWR@htmltag{/tr}\LWR@orignewline%
```

xcolor row color support:

```
\@rowc@lors%
```

No longer inside a data cell:

```
\global\booltrue{LWR@intabularmetadata}%
```

Not yet started a table row:

```
\global\boolfalse{LWR@startedrow}%
```

Additional setup:

```
\setcounter{LWR@hlines}{0}%
\setcounter{LWR@hdashedlines}{0}%
\global\boolfalse{LWR@doingtbrule}%
\global\boolfalse{LWR@doingcmidrule}%
\LWR@clearmidrules%
\gdef\LWR@rowHTMLcolor{}%
```

Start at first column:

```
\setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
\global\boolfalse{LWR@tabularcelladded}%
```

Allow TEX to flush the pending paragraph. Not doing so causes a slowdown for very large tables.

```
\LWR@stoppars
\LWR@origpar
```

Look at the next token to decide between single column data tag or a special case:

```
\LWR@getmynexttoken%
}
```

72.7 Looking ahead in the column specifications

`\LWR@columnspeclookahead` {⟨*offset*⟩}

Looks `offset` tokens ahead in the column specification, setting `\LWR@strresulttwo`.

The `w` column alignment will be seen as a single unit such as `{c}`.

```
\newcommand*{\LWR@columnspeclookahead}[1]{%
\setcounter{LWR@tempcountone}{\value{LWR@tablecolspecindex}}%
\addtocounter{LWR@tempcountone}{#1}%
\fullexpandarg%
\StrChar{\LWR@origcolspec}{\arabic{LWR@tempcountone}}[\LWR@strresulttwo]%
```

Get the contents of the first group in `\LWR@strresulttwo`:

```
\exploregroups%
\StrChar{\LWR@strresulttwo}{1}[\LWR@strresulttwo]%
\noexploregroups%
}
```

72.8 Parsing @, >, <, !, bar columns

Holds the parsed argument for `@`, `>`, `<`, or `!` columns:

```
\newcommand*{\LWR@colparameter}{}
```

`\LWR@parseatcolumn` Handles `@{text}` columns.

```
\newcommand*{\LWR@parseatcolumn}{%
```

Move to the next token after the '@':

```
\LWR@traceinfo{at column}%
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into `\LWR@colparameter`, expanding once:

```
\LWR@traceinfo{about to read the next token:}%
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]
\fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
\LWR@traceinfo{have now read the next token}%
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \LWR@traceinfo{at the left edge}%
    \LWR@setexparray{LWR@colatspec}{leftedge}{\LWR@colparameter}%
    \LWR@traceinfo{at the left edge: %
    \LWR@getexparray{LWR@colatspec}{leftedge}}%
}%
{% not at the left edge:
    \LWR@traceinfo{not at the left edge}%
    \LWR@setexparray{LWR@colatspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
    \LWR@traceinfo{at \arabic{LWR@tabletotalLaTeXcols}: %
```

```
    \LWR@getexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcols}}}%
}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsebangcolumn Handles !{text} columns.

```
\newcommand*{\LWR@parsebangcolumn}{%
```

Move to the next token after the '!':

```
\LWR@traceinfo{bang column}%
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
\LWR@traceinfo{about to read the next token:}%
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@traceinfo{have now read the next token}%
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \LWR@traceinfo{at the left edge}%
    \LWR@setexparray{LWR@colbangspec}{leftedge}{\LWR@colparameter}%
}%
{% not at the left edge:
    \LWR@traceinfo{not at the left edge}%
    \LWR@setexparray{LWR@colbangspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
    \LWR@traceinfo{bang \arabic{LWR@tabletotalLaTeXcols}: \LWR@colparameter!}%
}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsebeforecolumn Handles >{text} columns.

```
\newcommand*{\LWR@parsebeforecolumn}{%
```

Move to the next token after the '>':

```
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```
\expandarg%
```

```
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
\fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
\LWR@setexparray{LWR@colbeforespec}%
    {\arabic{LWR@tabletotalLaTeXcolsnext}}{\LWR@colparameter}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@parseaftercolumn` Handles `<{text}` columns.

```
\newcommand*{\LWR@parseaftercolumn}{%
```

Move to the next token after the '<':

```
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into `\LWR@colparameter`:

```
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
\fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
\LWR@setexparray{LWR@colafterspec}%
    {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@parsebarcolumn` Handles vertical rules.

```
\newcommand*{\LWR@parsebarcolumn}{%
\LWR@traceinfo{LWR@parsebarcolumn}%
```

Remember the bar at this position:

```
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
    \ifdefstring{\LWR@tempone}{tvertbarl}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldouble}}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarl}}%
}%
{% not at the left edge:
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
```

```
    }%
    \ifdefstring{\LWR@tempone}{tvertbarr}%
    {%
        \LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdouble}%
    }%
    {%
        \LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarr}%
    }%
}%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsecoloncolumn Handles vertical rules.

```
\newcommand*{\LWR@parsecoloncolumn}{%
\LWR@traceinfo{LWR@parsecoloncolumn}%
```

Remember the bar at this position:

```
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
    \ifdefstring{\LWR@tempone}{tvertbarldash}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldoubledash}}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldash}}%
}%
{% not at the left edge:
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarrdash}%
    {\LWR@setexparray{LWR@colbarspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdoubledash}}%
    {\LWR@setexparray{LWR@colbarspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdash}}%
}%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsesemicoloncolumn Handles vertical rules.

```
\newcommand*{\LWR@parsesemicoloncolumn}{%
```

Treat ; as a : column:

```
\LWR@parsecoloncolumn%
```

Skip the following width token:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}
```

72.9 Parsing ‘l’, ‘c’, or ‘r’ columns

\LWR@parsenormalcolumn {⟨*thiscolumn*⟩}

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

```
\newcommand*{\LWR@parsenormalcolumn}[1]{%
\addtocounter{LWR@tabletotalLaTeXcols}{1}%
\addtocounter{LWR@tabletotalLaTeXcolsnext}{1}%

\LWR@setexparray{LWR@tablecolspec}{\arabic{LWR@tabletotalLaTeXcols}}{#1}%

\LWR@traceinfo{normal column \arabic{LWR@tabletotalLaTeXcols}: #1}%
\LWR@setexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbangspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbeforespec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colafterspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\global\booltrue{LWR@validtablecol}%
}
```

72.10 Parsing ‘p’, ‘m’, or ‘b’ columns

\LWR@parsepcolumn {⟨*thiscolumn*⟩} The width will be ignored.

```
\newcommand*{\LWR@parsepcolumn}[1]{%
```

Converts to the given column type:

```
\LWR@parsenormalcolumn{#1}%
```

Skips the following width token:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}
```

72.11 Parsing ‘w’ columns

\LWR@parsewcolumn The width will be ignored.

```
\newcommand*{\LWR@parsewcolumn}{%

\LWR@columnspeclookahead{1}%
\expandafter\LWR@parsenormalcolumn\expandafter{\LWR@strresulttwo}%
```

Skips the following width and alignment tokens:

```
\addtocounter{LWR@tablecolspecindex}{2}%
}
```

72.12 Parsing '*' columns

\LWR@parsestarcolumn Star columns should already have been expanded, so this should never be used.

```
\newcommand*{\LWR@parsestarcolumn}{%
    \addtocounter{LWR@tablecolspecindex}{2}%
}
```

72.13 Parsing 'D' columns

From the dcolumn package.

\LWR@parseDcolumn {⟨*thiscolumn*⟩} The three parameters will be ignored.

```
\newcommand*{\LWR@parseDcolumn}[1]{%
```

Converts to the given column type.

```
\LWR@parsenormalcolumn{#1}%
```

Skips the following three parameters.

```
\addtocounter{LWR@tablecolspecindex}{3}%
}
```

72.14 Expanding the star column specifiations

Ctr LWR@starcount Internal count for duplicating star columns.

```
\newcount\LWR@starcount
```

\LWR@expcolspec Temporary storage used to build the expanded column specifier.

```
\newcommand*{\LWR@expcolspec}{}
```

Ctr LWR@splitstarindex Indexes into the column specifiers.

```
\newcounter{LWR@splitstarindex}
```

Ctr LWR@splitstarcopies Number of copies.

```
\newcounter{LWR@splitstarcopies}
```

\LWR@splitstarcontents Contents to duplicate.

```
\newcommand*{\LWR@splitstarcontents}{}
```

\expandcolspec Expands \LWR@origcolspec for star columns.

```
\newcommand*{\expandcolspec}{%
```

Find the position of any star token.

```
    \StrPosition{\LWR@origcolspec}{*}[\LWR@tempone]%
```

Expand until no stars are found:

```
    \whileboolexpr{ test {\ifnumgreater{\LWR@tempone}{0}}}%
    {%
```

Begin with any characters to the left of the star.

```
        \setcounter{LWR@splitstarindex}{\LWR@tempone}%
        \addtocounter{LWR@splitstarindex}{-1}%
      \StrLeft{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\LWR@expcolspec]%
```

Move past the star to remember its number of copies.

```
        \addtocounter{LWR@splitstarindex}{2}%
        \StrChar{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\LWR@tempone]%
       \setcounter{LWR@splitstarcopies}{\expandafter\@firstofone\LWR@tempone}%
```

Move past the number of copies and remember the contents.

```
        \addtocounter{LWR@splitstarindex}{1}%
     \StrChar{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\LWR@splitstarcontents]%
```

For each copy, append the contents.

```
        \ifnumgreater{\value{LWR@splitstarcopies}}{0}%
        {%
            \LWR@starcount=\value{LWR@splitstarcopies}%
            \loop
                \appto\LWR@expcolspec{%
```

(Remove the enclosing braces.)

```
                    \expandafter\@firstofone\LWR@splitstarcontents%
                }%
                \advance \LWR@starcount -1
            \ifnum \LWR@starcount>0 \repeat
        }{}%
```

Remove any token to the left, and append the rightmost remainding tokens.

```
     \StrGobbleLeft{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\colspecremainder]%
        \appto{\LWR@expcolspec}{\colspecremainder}%
```

Remember the final result.

```
        \edef\LWR@origcolspec{\LWR@expcolspec}%
```

Table 10: Tabular baseline

l	p	m	b	r
			bot	
		mid	bot	
l	par	mid	bot	r
	par	mid		
	par			

See if more stars exist.

```
7669          \StrPosition{\LWR@origcolspec}{*}[\LWR@tempone]%
7670      }%
7671  }
```

72.15 Parsing the column specifications

⚠ tabular baselines HTML CSS cannot exactly match the LaTeX concept of a baseline for a table row. Table 10 shows the LaTeX results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the p column specification in table 11 for details.

Table 11 describes how each kind of column is converted to HTML.

Bool LWR@validtablecol True if found a valid table column type.

```
7672 \newbool{LWR@validtablecol}
```

Bool LWR@opttablecol True if found a table column optional argument.

```
7673 \newbool{LWR@opttablecol}
```

\LWR@parsetablecols {⟨*colspecs*⟩}

Scans the column specification left to right.

Builds \LWR@tablecolspec with the final specification, one LaTeX column per entry. The final number of LaTeX columns in each row is stored in LWR@tabletotalLaTeXcols, which is the number of & and \\ in each line, but which does not include @, !, <, > specifications in the count.

```
7674 \newcommand*{\LWR@parsetablecols}[1]{%
7675 \LWR@traceinfo{LWR@parsetablecols}%
```

Remember the original supplied column spec:

```
7676 \renewcommand*{\LWR@origcolspec}{#1}%
```

Table 11: Tabular HTML column conversions

l, r, c: Converted to table cells without paragraph tags.
Uses CSS `vertical-align:middle` so that top or bottom-aligned cells may go above or below this cell.

p: Converted to table cells with paragraph tags. Ref: Table 10, LaTeX places the top line of a parbox aligned with the rest of the text line, so CSS `vertical-align:bottom` is used to have the HTML result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the HTML conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the CSS may be desired, changing `td.tdp`, `td.tdP`, `td.tdprule`, and `td.tdPrule` to `vertical-align: middle`. Another possibility is to change L,R,C, and P to `vertical-align: top` and not worry about the alignment of B and M cells or trying to approximate LaTeX baselines.

m: With paragraph tags, CSS `vertical-align:middle`.

b: With paragraph tags, CSS `vertical-align:top` so that the bottom of the text is closest to the middle of the text line.

P, M, B: Horizontally-centered versions.

S: Converted to 'r'. Ignores optional argument. From the siunitx package.

D: Converted to 'c'. From the dcolumn package.

@, !, >, <: One each, in that order.

|: Vertical rule.

Unknown: Converted to 'l'.

`\newcolumn`: Currently treated as unknown.

Remove spaces:

```
\expandarg%
\StrSubstitute{\LWR@origcolspec}{ }{}[\LWR@origcolspec]%
```

Expand any star columns:

```
\expandcolspec%
```

The parsed column spec data array, LWR@tablecolspec, will be overwritten with new values.

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```
\setcounter{LWR@tabletotalLaTeXcols}{0}%
\setcounter{LWR@tabletotalLaTeXcolsnext}{1}%
\LWR@setexparray{LWR@colatspec}{leftedge}{}%
\LWR@setexparray{LWR@colatspec}{1}{}%
\LWR@setexparray{LWR@colatspec}{2}{}%
\LWR@setexparray{LWR@colatspec}{3}{}%
\LWR@setexparray{LWR@colbangspec}{leftedge}{}%
\LWR@setexparray{LWR@colbangspec}{1}{}%
\LWR@setexparray{LWR@colbangspec}{2}{}%
\LWR@setexparray{LWR@colbangspec}{3}{}%
\LWR@setexparray{LWR@colbeforespec}{1}{}%
\LWR@setexparray{LWR@colbeforespec}{2}{}%
\LWR@setexparray{LWR@colbeforespec}{3}{}%
\LWR@setexparray{LWR@colafterspec}{1}{}%
\LWR@setexparray{LWR@colafterspec}{2}{}%
\LWR@setexparray{LWR@colafterspec}{3}{}%
\LWR@setexparray{LWR@colbarspec}{leftedge}{}%
\LWR@setexparray{LWR@colbarspec}{1}{}%
\LWR@setexparray{LWR@colbarspec}{2}{}%
\LWR@setexparray{LWR@colbarspec}{3}{}%
```

Starting at the first column specification:

```
\setcounter{LWR@tablecolspecindex}{1}%
```

Place the colspecs string length into \LWR@strresult, and remember the number of characters in the column specification:

```
\expandarg%
\StrLen{\LWR@origcolspec}[\LWR@strresult]%
\fullexpandarg%
\LWR@traceinfo{original column spec length: \LWR@strresult}%
\setcounter{LWR@tablecolspecwidth}{\LWR@strresult}%
```

Haven't seen any optional arguments so far

```
\global\boolfalse{LWR@opttablecol}%
```

Scan through the column specifications:

```
\whileboolexpr{%
    not test{%
        \ifnumcomp{\value{LWR@tablecolspecindex}}{>}%
            {\value{LWR@tablecolspecwidth}}%
    }%
}%
{%
```

Place the next single-character column type into `\LWR@strresult`:

```
\expandarg%
\StrChar{\LWR@origcolspec}{\arabic{LWR@tablecolspecindex}}[\LWR@strresult]%
\LWR@traceinfo{position \arabic{LWR@tablecolspecindex}: \LWR@strresult}%
\fullexpandarg%
```

Not yet found a valid column type:

```
\global\boolfalse{LWR@validtablecol}%
```

Skip over any optional arguments, such as siunitx `S` column:

```
\IfStrEq{\LWR@strresult}{[}{\global\booltrue{LWR@opttablecol}}{}%
```

Throw away anything found inside the optional argument:

```
\ifbool{LWR@opttablecol}%
{}% inside an optional argument
{% not an optional tabular argument
```

Not inside an optional argument, so consider the column type:

```
\IfStrEq{\LWR@strresult}{l}{\LWR@parsenormalcolumn{l}}{}%
\IfStrEq{\LWR@strresult}{c}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{r}{\LWR@parsenormalcolumn{r}}{}%
\IfStrEq{\LWR@strresult}{L}{\LWR@parsenormalcolumn{l}}{}%
\IfStrEq{\LWR@strresult}{C}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{R}{\LWR@parsenormalcolumn{r}}{}%
\IfStrEq{\LWR@strresult}{J}{\LWR@parsenormalcolumn{l}}{}%

\IfStrEq{\LWR@strresult}{S}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{s}{\LWR@parsenormalcolumn{c}}{}%

\IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@parseatcolumn}{}%
\IfStrEq{\LWR@strresult}{!}{\LWR@parsebangcolumn}{}%
\IfStrEq{\LWR@strresult}{>}{\LWR@parsebeforecolumn}{}%
\IfStrEq{\LWR@strresult}{<}{\LWR@parseaftercolumn}{}%
\IfStrEq{\LWR@strresult}{|}{\LWR@parsebarcolumn}{}%
\IfStrEq{\LWR@strresult}{:}{\LWR@parsecoloncolumn}{}%
\IfStrEq{\LWR@strresult}{;}{\LWR@parsesemicoloncolumn}{}%

\IfStrEq{\LWR@strresult}{p}{\LWR@parsepcolumn{p}}{}%
```

```
\IfStrEq{\LWR@strresult}{m}{\LWR@parsepcolumn{m}}{}%
\IfStrEq{\LWR@strresult}{b}{\LWR@parsepcolumn{b}}{}%

\IfStrEq{\LWR@strresult}{w}{\LWR@parsewcolumn}{}%
\IfStrEq{\LWR@strresult}{W}{\LWR@parsewcolumn}{}%
```

A star column:

```
\IfStrEq{\LWR@strresult}{*}{\LWR@parsestarcolumn}{}%
```

From the dcolumn package:

```
\IfStrEq{\LWR@strresult}{D}{\LWR@parseDcolumn{c}}{}%
```

From the tabularx package. X column has no parameter, but will be given paragraph tags.

```
\IfStrEq{\LWR@strresult}{X}{\LWR@parsenormalcolumn{X}}{}%
```

Many people define centered versions "P", "M", and "B":

```
\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}
```

```
\IfStrEq{\LWR@strresult}{P}{\LWR@parsepcolumn{P}}{}%
\IfStrEq{\LWR@strresult}{M}{\LWR@parsepcolumn{M}}{}%
\IfStrEq{\LWR@strresult}{B}{\LWR@parsepcolumn{B}}{}%
```

If this column was an invalid column type, convert it to an l column:

```
\ifbool{LWR@validtablecol}{}{%
    \LWR@traceinfo{invalid column type: \LWR@strresult}%
    \LWR@parsenormalcolumn{l}%
}%
}% not an optional column argument
```

If read the closing bracket, no longer inside the optional argument:

```
\IfStrEq{\LWR@strresult}{]}{\global\boolfalse{LWR@opttablecol}}{}%
```

Move to the next character:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}% whiledo
}%
```

72.16 colortbl and xparse tabular color support

These macros provide a minimal emulation of some colortbl macros which might appear between table cells. If colortbl is loaded, these macros will be replaced with functional versions.

For each of the HTML colors below, the text for the HTML color is set if requested, but the macro is empty if none has been set.

`\rownum` Reserve a counter register.

```
\@ifundefined{rownum}{\newcount\rownum}{}
```

`\@rowcolors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowcolors}{}
```

`\@rowc@lors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowc@lors}{}
```

`\LWR@xcolorrowHTMLcolor` Emulated xcolor row color.

```
\newcommand*{\LWR@xcolorrowHTMLcolor}{}
```

`\LWR@columnHTMLcolor` HTMLstyle code for the column color.

```
\def\LWR@columnHTMLcolor{}
```

`\LWR@rowHTMLcolor` HTMLstyle code for the row color.

```
\def\LWR@rowHTMLcolor{}
```

`\LWR@cellHTMLcolor` HTMLstyle code for the cell color.

```
\def\LWR@cellHTMLcolor{}
```

`\LWR@ruleHTMLcolor` HTMLstyle code for the cell color.

```
\newcommand*{\LWR@ruleHTMLcolor}{}
```

`\rowcolor` `[`⟨*model*⟩`]` `{`⟨*color*⟩`}` `[`⟨*left overhang*⟩`]` `[`⟨*right overhang*⟩`]` Print version. The HTML version is in lwarp-colortbl. Used before starting a tabular data cell, thus `\LWR@getmynexttoken`.

```
\newcommand*{\rowcolor}{\LWR@getmynexttoken}%
```

`\arrayrulecolor` `[`⟨*model*⟩`]` `{`⟨*color*⟩`}`

\arrayrulecolornexttoken [⟨*model*⟩] {⟨*color*⟩}

Print versions for use outside and inside a tabular:

```
\newcommand{\arrayrulecolor}[2][named]{}
\newcommand{\arrayrulecolornexttoken}[2][named]{\LWR@getmynexttoken}
```

\doublerulesepcolor [⟨*model*⟩] {⟨*color*⟩}

\doublerulesepcolornexttoken [⟨*model*⟩] {⟨*color*⟩}

Print versions for use inside and outside a tabular:

```
\newcommand{\doublerulesepcolor}[2][named]{}
\newcommand{\doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}
```

72.17 Starting a new row

\LWR@maybenewtablerow If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for hline or tbrule if necessary.

```
\newcommand*{\LWR@maybenewtablerow}
{%
\ifbool{LWR@startedrow}%
{}% started the row
{% not started the row
```

Remember that now have started the row:

```
    \global\booltrue{LWR@startedrow}%
```

Create the row tag, with a class if necessary.

```
    \global\booltrue{LWR@intabularmetadata}%
    \ifboolexpr{%
        test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
        test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}}%
    }%
    {%
        \LWR@htmltag{tr class="hline" }%
        \LWR@orignewline%
    }%
    {% not doing hline
        \ifbool{LWR@doingtbrule}%
        {%
            \ifdefvoid{\LWR@ruleHTMLcolor}{%
                \LWR@htmltag{tr class="tbrule"}%
            }{%
                \LWR@htmltag{%
                    tr class="tbrule" % space
                    style="border-top: 1px solid % space
                        \LWR@origpound\LWR@ruleHTMLcolor "%
```

```
                }%
            }%
            \LWR@orignewline%
        }%
        {\LWR@htmltag{tr}\LWR@orignewline}%
    }% end of not doing hline
}% end of not started the row
}
```

72.18 Printing vertical bar tags

`\LWR@printbartag` {⟨*index*⟩}

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```
\newcommand*{\LWR@printbartag}[1]{%
\LWR@traceinfo{LWR@printbartag !#1!}%
\ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
{}% muting or empty
{% not muting
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{#1}}%
    \ifdefempty{\LWR@tempone}{}{ \LWR@tempone}%
}% not muting
\LWR@traceinfo{LWR@printbartag done}%
}
```

72.19 Printing at or bang tags

`\LWR@printatbang` {⟨*at -or- bang*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@printatbang}[2]{%
```

Fetch the column at or bang spec:

```
\xdef\LWR@atbangspec{\LWR@getexparray{LWR@col#1spec}{#2}}%
\LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}%
```

Only generate if is not empty;

```
\ifdefempty{\LWR@atbangspec}%
{}%
{% not empty
    \LWR@htmltag{%
        td class="td#1%
        \LWR@subaddcmidruletrim{}{}%
        \LWR@printbartag{#2}%
        "%
        \LWR@tdstartstyles%
        \LWR@addcmidrulewidth%
        \LWR@addcdashline%
        \LWR@addtabularrulecolors%
```

```
        \LWR@tdendstyles%
    }%
```

Create an empty cell if muting for the \bottomrule:

```
    \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
    {}%
    {\LWR@atbangspec}%
%
    \LWR@htmltag{/td}\LWR@orignewline%
    \global\booltrue{LWR@tabularcelladded}%
}% not empty
}%
```

\LWR@addleftmostbartag

```
\newcommand*{\LWR@addleftmostbartag}{%
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}{%
    \LWR@printbartag{leftedge}%
}{}%
}
```

\LWR@tabularleftedge

```
\newcommand*{\LWR@tabularleftedge}{%
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}%
{%
    \LWR@printatbang{at}{leftedge}%
    \LWR@printatbang{bang}{leftedge}%
}% left edge
{}% not left edge
}
```

72.20 Data opening tag

\LWR@thiscolspec Temporary storage.

```
\newcommand*{\LWR@thiscolspec}{}
```

\LWR@tabledatasinglecolumntag Print a table data opening tag with style for alignment and color.

```
\newcommand*{\LWR@tabledatasinglecolumntag}%
{%
\LWR@traceinfo{LWR@tabledatasinglecolumntag}%
\LWR@maybenewtablerow%
```

Don't start a new paragraph tag if have already started one:

```
\ifbool{LWR@intabularmetadata}%
{%
```

If have found the end of tabular command, do not create the next data cell:

```
    \ifbool{LWR@exitingtabular}{}%
    {% not exiting tabular
```

Print the `@` and `!` contents before first column:

```
        \LWR@tabularleftedge%
```

Fetch the current column's alignment character into `\LWR@strresult`:

```
        \xdef\LWR@strresult{%
          \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
```

print the start of a new table data cell:

```
\LWR@traceinfo{LWR@tabledatasinglecolumntag: about to print td tag}%
        \LWR@htmltag{td class="td%
```

append this column's spec:

```
        \LWR@strresult%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add vertical bar tags.

```
        \LWR@addcmidruletrim%
        \LWR@addleftmostbartag%
        \LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
        "%
```

Add styles for rules, alignment:

```
        \LWR@tdstartstyles%
        \LWR@addcmidrulewidth%
        \LWR@addcdashline%


        \xdef\LWR@thiscolspec{%
          \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
        \LWR@addformatwpalignment{\LWR@thiscolspec}%
```

Add styles for cell and rule colors:

```
        \LWR@addtabularrowcolor%
        \LWR@addtabularrulecolors%

        \LWR@tdendstyles%
        }% HTML td
        \LWR@traceinfo{LWR@tabledatasinglecolumntag: done printing td tag}%
```

If this is a p, m, b, or X column, allow paragraphs:

```
        \ifboolexpr{%
            test{ \ifdefstring{\LWR@strresult}{p} } or
            test{ \ifdefstring{\LWR@strresult}{m} } or
            test{ \ifdefstring{\LWR@strresult}{b} } or
            test{ \ifdefstring{\LWR@strresult}{P} } or
            test{ \ifdefstring{\LWR@strresult}{M} } or
            test{ \ifdefstring{\LWR@strresult}{B} } or
            test{ \ifdefstring{\LWR@strresult}{X} }
        }%
        {% allow pars
          \LWR@traceinfo{LWR@tabledatasinglecolumntag: about to LWR@startpars}%
            \global\booltrue{LWR@tableparcell}%
            \LWR@startpars%
         \LWR@traceinfo{LWR@tabledatasinglecolumntag: done with LWR@startpars}%
        }% allow pars
        {}% no pars
```

Print the > contents unless muted for the \bottomrule:

```
        \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
        {}%
        {%
         \LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
        \global\boolfalse{LWR@intabularmetadata}%
    }% not exiting tabular
}{}% in tabular metadata
\LWR@traceinfo{LWR@tabledatasinglecolumntag: done}%
}%
```

72.21 Midrules

LWR@midrules — LWR@midrules is a data array (section 42) of columns each containing a non-zero width if a midrule should be created for this column.

LWR@trimlrules — LWR@trimlrules is a data array (section 42) of columns containing l if a midrule should be left trimmed for each column.

LWR@trimrrules — LWR@trimrrules is a data array (section 42) of columns containing r if a midrule should be right trimmed for each column.

LWR@cdashlines — LWR@cdashlines is a data array (section 42) of columns each containing a Y if an arydshln package "cdashed line" should be created for this column.

Ctr LWR@midrulecounter — Indexes across the LWR@midrules and LWR@trim<l/r>rules data arrays.

```
\newcounter{LWR@midrulecounter}
```

Len \LWR@heavyrulewidth — The default width of the rule.

```
\newlength{\LWR@heavyrulewidth}
\setlength{\LWR@heavyrulewidth}{.08em}
```

Len \LWR@lightrulewidth The default width of the rule.

```
\newlength{\LWR@lightrulewidth}
\setlength{\LWR@lightrulewidth}{.05em}
```

Len \LWR@cmidrulewidth The default width of the rule.

```
\newlength{\LWR@cmidrulewidth}
\setlength{\LWR@cmidrulewidth}{.03em}
```

Len \LWR@thiscmidrulewidth The width of the next rule, defaulting to \LWR@cmidrulewidth.

If not \LWR@cmidrulewidth, a style will be used to generate the custom width.

Assigned from the LWR@midrules array.

```
\newlength{\LWR@thiscmidrulewidth}
\setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}
```

\LWR@clearmidrules Start new midrules. Called at beginning of tabular and also at \\.

Clears all LWR@midrules and LWR@trimrules markers for this line.

```
\newcommand*{\LWR@clearmidrules}
{%
\setcounter{LWR@midrulecounter}{1}%
\whileboolexpr{%
    not test{%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}%
            {\value{LWR@tabletotalLaTeXcols}}%
    }%
}%
{%
    \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{0pt}%
    \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
    \LWR@setexparray{LWR@trimlrules}{\arabic{LWR@midrulecounter}}{}%
    \LWR@setexparray{LWR@trimrrules}{\arabic{LWR@midrulecounter}}{}%
    \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{N}%
    \addtocounter{LWR@midrulecounter}{1}%
}%
}
```

\LWR@subcmidrule {⟨*width*⟩} {⟨*trim*⟩} {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks LWR@midrules data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcmidrule}[4]{%
\setcounter{LWR@midrulecounter}{#3}%
\whileboolexpr{%
```

```
    not test {%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}{#4}%
    }%
}%
{%
    \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{#1}%
    \addtocounter{LWR@midrulecounter}{1}%
}% whiledo
\IfSubStr{#2}{l}{\LWR@setexparray{LWR@trimlrules}{#3}{l}}{}%
\IfSubStr{#2}{r}{\LWR@setexparray{LWR@trimrrules}{#4}{r}}{}%
\global\booltrue{LWR@doingcmidrule}%
}
```

\LWR@docmidrule [⟨*width*⟩] (⟨*trim*⟩) {⟨*leftcolumn-rightcolumn*⟩}

Marks LWR@midrules array elements to be a non-zero width from left to right columns. Also marks trimming for the L and/or R columns.

```
\NewDocumentCommand{\LWR@docmidrule}
    {O{\LWR@cmidrulewidth} D(){} >{\SplitArgument{1}{-}}m}
    {\LWR@subcmidrule{#1}{#2}#3}
```

\LWR@subcdashline {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks LWR@cdashlines data array elements to be Y from left to right columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcdashline}[2]{%
\setcounter{LWR@midrulecounter}{#1}%
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}{#2}%
    }%
}%
{%
    \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{Y}%
    \addtocounter{LWR@midrulecounter}{1}%
}% whiledo
\global\booltrue{LWR@doingcmidrule}%
}
```

\LWR@docdashline {⟨*leftcolumn-rightcolumn*⟩}

Marks LWR@cdashlines data array elements to be Y from left to right columns.

```
\NewDocumentCommand{\LWR@docdashline}
    {>{\SplitArgument{1}{-}}m}%
    {%
        \LWR@subcdashline#1%
    }
```

Used to compute margins, tabular trims, column offsets:

```
\newlength{\LWR@templengthone}
\newlength{\LWR@templengthtwo}
\newlength{\LWR@templengththree}
\newcounter{LWR@tempcountone}
```

Used to add a style to a table data cell:

```
\newbool{LWR@tdhavecellstyle}
```

`\LWR@tdstartstyles` Begins possibly adding a table data cell style.

```
\newcommand*{\LWR@tdstartstyles}{\global\boolfalse{LWR@tdhavecellstyle}}
```

`\LWR@tdaddstyle` Starts adding a table data cell style.

```
\newcommand*{\LWR@tdaddstyle}{%
\ifbool{LWR@tdhavecellstyle}%
{; }%
{ style="}%
\booltrue{LWR@tdhavecellstyle}%
}
```

`\LWR@tdendstyles` Finishes possibly adding a table data cell style. Prints the closing quote.

```
\newcommand*{\LWR@tdendstyles}{%
\ifbool{LWR@tdhavecellstyle}{%
    "%
    \global\boolfalse{LWR@tdhavecellstyle}%
}{}%
}
```

`\LWR@subaddcmidruletrim` {⟨*lefttrim*⟩} {⟨*righttrim*⟩} Adds a `\cmidrule` with optional trim.

```
\newcommand*{\LWR@subaddcmidruletrim}[2]{%
\setlength{\LWR@templengthone}{%
        \LWR@getexparray{LWR@midrules}{\arabic{LWR@tableLaTeXcolindex}}%
}%
\ifdimcomp{\LWR@templengthone}{>}{0pt}%
{%
```

Print the class with left and right trim letters appended:

```
    \LWR@origtilde tdrule#1#2%
```

Remember the width of the rule:

```
    \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
}%
{%
```

```
    \setlength{\LWR@thiscmidrulewidth}{0pt}%
}%
}
```

`\LWR@addcmidruletrim` Adds left or right trim to a `\cmidrule`.

```
\newcommand*{\LWR@addcmidruletrim}{%
\LWR@subaddcmidruletrim%
{\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
{\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@tableLaTeXcolindex}}}%
}
```

`\LWR@addrulewidth` {⟨*thiswidth*⟩} {⟨*defaultwidth*⟩}

If not default width, add a custom style with width and color depending on `thiswidth`.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addrulewidth}[2]{%
```

Only add a custom width if `thiswidth` is different than the `defaultwidth`, or if a color is being used:

```
\ifboolexpr{%
    test{\ifdimcomp{#1}{=}{0pt}} or
    (
        ( test{\ifdimcomp{#1}{=}{#2}} and not bool{FormatWP} )
        and ( test {\ifdefvoid{\LWR@ruleHTMLcolor}} )
    )
}%
{}% default width and color
{% custom width and/or color
```

Ensure that the width is wide enough to display in the browser:

```
    \LWR@forceminwidth{#1}%
```

Begin adding another style:

```
    \LWR@tdaddstyle%
```

The style itself:

```
    border-top:\LWR@printlength{\LWR@atleastonept} solid %
```

If default gray, the darkness of the color depends on the thickness of the rule:

```
    \ifdefvoid{\LWR@ruleHTMLcolor}{%
        \ifdimcomp{#1}{<}{\LWR@lightrulewidth}%
        {\LWR@origpound{}A0A0A0}%
        {% lightrule or heaver
            \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}%
```

```
            {\LWR@origpound{}808080}%
            {black}%
        }% lightrule or heavier
    }{%
        \LWR@origpound\LWR@ruleHTMLcolor%
    }
}% custom width and/or color
}
```

\LWR@addcmidrulewidth Adds a `style` for the rule width.

Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
\newcommand{\LWR@addcmidrulewidth}{%
\LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
}
```

\LWR@addcdashline Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
\newcommand{\LWR@addcdashline}{%
\edef\LWR@tempone{%
    \LWR@getexparray{LWR@cdashlines}{\arabic{LWR@tableLaTeXcolindex}}%
}%
\ifdefstring{\LWR@tempone}{Y}{%
    \LWR@tdaddstyle%
    border-top: 1pt dashed %
    \ifdefvoid{\LWR@ruleHTMLcolor}%
        {black}%
        {\LWR@origpound\LWR@ruleHTMLcolor}%
}{}%
}
```

\LWR@WPcell {⟨*text-align*⟩} {⟨*vertical-align*⟩}

```
\newcommand*{\LWR@WPcell}[2]{%
\LWR@tdaddstyle%
\LWR@print@mbox{text-align:#1}; \LWR@print@mbox{vertical-align:#2}%
}
```

\LWR@addformatwpalignment If `FormatWP`, adds a `style` for the alignment.

Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
\newcommand*{\LWR@addformatwpalignment}[1]{%
\ifbool{FormatWP}{%
\IfSubStr{#1}{l}{\LWR@WPcell{left}{middle}}{}%
\IfSubStr{#1}{c}{\LWR@WPcell{center}{middle}}{}%
\IfSubStr{#1}{r}{\LWR@WPcell{right}{middle}}{}%
\IfSubStr{#1}{p}{\LWR@WPcell{left}{bottom}}{}%
\IfSubStr{#1}{m}{\LWR@WPcell{left}{middle}}{}%
\IfSubStr{#1}{b}{\LWR@WPcell{left}{top}}{}%
\IfSubStr{#1}{P}{\LWR@WPcell{center}{bottom}}{}%
```

```
\IfSubStr{#1}{M}{\LWR@WPcell{center}{middle}}{}%
\IfSubStr{#1}{B}{\LWR@WPcell{center}{top}}{}%
}{}%
}
```

72.22 Cell colors

\LWR@addtabularrowcolor Adds a cell's row color style, if needed.

No color is added for the final row of empty cells which finishes each `tabular`.

```
\newcommand*{\LWR@addtabularrowcolor}{%
\ifbool{LWR@tabularmutemods}{}{%
    \ifdefvoid{\LWR@rowHTMLcolor}{%
        \ifdefvoid{\LWR@xcolorrowHTMLcolor}{}%
        {% xcolor row color
            \LWR@tdaddstyle%
            background:\LWR@origpound\LWR@xcolorrowHTMLcolor%
        }%
    }%
    {% explicit row color
        \LWR@tdaddstyle%
        background:\LWR@origpound\LWR@rowHTMLcolor%
    }%
}%
}
```

\LWR@addtabularhrulecolor Adds a cell's horizontal rule color style, if needed.

```
\newcommand*{\LWR@addtabularhrulecolor}{%
```

If either form of horizontal rule is requested:

```
\ifboolexpr{%
    test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
    test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
    bool{LWR@doingtbrule}%
}{%
```

If there is a no custom color:

```
    \ifdefvoid{\LWR@ruleHTMLcolor}%
    {%
        \ifnumcomp{\value{LWR@hlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 4px double%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 2px dashed%
```

```
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 1px dashed%
        }{}}}%
```

If no color and not doubled or dashed, then add nothing, since a simpler rule is the default.

```
    }%
```

If there is a custom color:

```
    {%
        \ifnumcomp{\value{LWR@hlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 4px double \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 2px dashed \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 1px dashed \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
            \LWR@tdaddstyle%
            border-top: 1px solid \LWR@origpound\LWR@ruleHTMLcolor%
        }}}%
    }%
}{}%
}
```

`\LWR@addtabularrulecolors` Adds a cell's rule color styles, if needed.

No color is added for the final row of empty cells which finishes each `tabular`.

```
\newcommand*{\LWR@addtabularrulecolors}{%
```

Custom horizonal rule color:

```
\LWR@addtabularhrulecolor%
```

No vertical rules if finishing the `tabular` with a row of empty cells:

```
\ifbool{LWR@tabularmutemods}{}{%
```

If at the leftmost cell, possibly add a leftmost vertical rule:

```
    \ifnumequal{\value{LWR@tableLaTeXcolindex}}{1}{%
```

Fetch the left edge's vertical bar specification:

```
        \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
```

Add a custom style if a vertical bar was requested:

```
        \ifdefstring{\LWR@tempone}{tvertbarl}{%
                \LWR@tdaddstyle%
                border-left: 1px solid % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldouble}{%
                \LWR@tdaddstyle%
                border-left: 4px double % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldash}{%
                \LWR@tdaddstyle%
                border-left: 1px dashed % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldoubledash}{%
                \LWR@tdaddstyle%
                border-left: 2px dashed % space
                    \LWR@vertruleHTMLcolor%
        }{}%
    }{}%
```

Possibly add a right vertical rule for this cell:

```
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tableLaTeXcolindex}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarr}{%
```

Add a custom style if a vertical bar was requested:

```
            \LWR@tdaddstyle%
            border-right: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
    \ifdefstring{\LWR@tempone}{tvertbarrdouble}{%
            \LWR@tdaddstyle%
            border-right: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifdefstring{\LWR@tempone}{tvertbarrdash}{%
            \LWR@tdaddstyle%
            border-right: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifdefstring{\LWR@tempone}{tvertbarrdoubledash}{%
            \LWR@tdaddstyle%
            border-right: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
}%
}
```

Ctr LWR@cellcolordepth Counts how many cell color s were added to the current tabular data cell.

```
\newcounter{LWR@cellcolordepth}
```

\LWR@subaddtabularcellcolor {⟨*HTML color*⟩}

```
\newcommand*{\LWR@subaddtabularcellcolor}[1]{%
\LWR@htmltag{div class="cellcolor" style="%
    background:\LWR@origpound{}{}#1 %
" }%
\addtocounter{LWR@cellcolordepth}{1}%
}
```

\LWR@addtabularcellcolor Adds a cell color style, if needed.

```
\newcommand*{\LWR@addtabularcellcolor}{%
\ifdefvoid{\LWR@cellHTMLcolor}%
{%
    \ifdefvoid{\LWR@rowHTMLcolor}%
    {%
        \ifdefvoid{\LWR@xcolorrowHTMLcolor}%
        {%
            \ifdefvoid{\LWR@columnHTMLcolor}%
            {}%
            {\LWR@subaddtabularcellcolor{\LWR@columnHTMLcolor}}%
        }%
        {\LWR@subaddtabularcellcolor{\LWR@xcolorrowHTMLcolor}}%
    }%
    {\LWR@subaddtabularcellcolor{\LWR@rowHTMLcolor}}%
}%
{\LWR@subaddtabularcellcolor{\LWR@cellHTMLcolor}}%
}
```

72.23 Multicolumns

72.23.1 Parsing multicolumns

```
\newcounter{LWR@tablemulticolswidth}
```

Indexes into the multicolumn specification:

```
\newcounter{LWR@tablemulticolspos}
```

Remembers multicolumn vertical rules if found in the column spec.

```
\newcounter{LWR@mcolvertbarsl}
\newcounter{LWR@mcolvertbarsr}
\newcounter{LWR@mcolvertbarsldash}
\newcounter{LWR@mcolvertbarsrdash}
\newbool{LWR@mcolvertbaronleft}%
```

\LWR@printmccoltype {⟨*colspec*⟩} Print any valid column type found. Does not print `@`, `!`, `>`, or `<` columns or their associated tokens.

This is printed as part of the table data tag's `class`.

```
\newcommand*{\LWR@printmccoltype}[1]{%
\LWR@traceinfo{lwr@printmccoltype -#1-}%
```

Get one token of the column spec:

```
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Add to the HTML tag depending on which column type is found:

```
\IfStrEq{\LWR@strresult}{l}{l}{}%
\IfStrEq{\LWR@strresult}{c}{c}{}%
\IfStrEq{\LWR@strresult}{r}{r}{}%
\IfStrEq{\LWR@strresult}{p}{p}{}%
\IfStrEq{\LWR@strresult}{m}{m}{}%
\IfStrEq{\LWR@strresult}{b}{b}{}%
\IfStrEq{\LWR@strresult}{P}{P}{}%
\IfStrEq{\LWR@strresult}{M}{M}{}%
\IfStrEq{\LWR@strresult}{B}{B}{}%

\IfStrEq{\LWR@strresult}{w}{w}{}%
\IfStrEq{\LWR@strresult}{W}{W}{}%

\IfStrEq{\LWR@strresult}{S}{c}{}%
\IfStrEq{\LWR@strresult}{s}{c}{}%

\IfStrEq{\LWR@strresult}{X}{p}{}%

\IfStrEq{\LWR@strresult}{|}%
{%
    \ifbool{LWR@mcolvertbaronleft}%
        {\addtocounter{LWR@mcolvertbarsl}{1}}% left edge
        {\addtocounter{LWR@mcolvertbarsr}{1}}% not left edge
}%
{%
    \IfStrEq{\LWR@strresult}{:}%
    {%
        \ifbool{LWR@mcolvertbaronleft}%
            {\addtocounter{LWR@mcolvertbarsldash}{1}}% left edge
            {\addtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
    }%
    {%
        \IfStrEq{\LWR@strresult}{;}%
        {%
            \ifbool{LWR@mcolvertbaronleft}%
                {\addtocounter{LWR@mcolvertbarsldash}{1}}% left edge
                {\addtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
        }%
        {\boolfalse{LWR@mcolvertbaronleft}}%
```

```
    }%
}%
\LWR@traceinfo{lwr@printmccoltype done}%
}
```

`\LWR@multicolpartext` {⟨*num parameters*⟩} Print the data with paragraph tags, advance to bypass the given number of parameters.

```
\newcommand*{\LWR@multicolpartext}[1]{%
\LWR@startpars%
\LWR@multicoltext%
\addtocounter{LWR@tablemulticolspos}{#1}%
\LWR@stoppars%
}
```

`\LWR@multicolother` {⟨*colspec*⟩} For `@`, `!`, `>`, `<`, print the next token without paragraph tags:

```
\newcommand*{\LWR@multicolother}[1]{%
\addtocounter{LWR@tablemulticolspos}{1}%
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
\LWR@strresult%
```

A valid column data type was found:

```
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@multicolskip` Nothing to print for this column type.

```
\newcommand*{\LWR@multicolskip}{%
```

A valid column data type was found:

```
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@printmccoldata` {⟨*colspec*⟩} Print the data for any valid column type found.

```
\newcommand*{\LWR@printmccoldata}[1]{%
\LWR@traceinfo{lwr@printmccoldata -#1}%
```

Not yet found a valid column type:

```
\global\boolfalse{LWR@validtablecol}%
```

Get one token of the column spec:

```
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Print the text depending on which column type is found. Also handles `@`, `>`, `<` as it comes to them.

```
\IfStrEq{\LWR@strresult}{l}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{c}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{r}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{D}{%
\addtocounter{LWR@tablemulticolspos}{3}% skip parameters
\LWR@multicoltext%
}{}%

\IfStrEq{\LWR@strresult}{p}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{m}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{b}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{P}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{M}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{B}{\LWR@multicolpartext{2}}{}%

\IfStrEq{\LWR@strresult}{w}{\LWR@multicolpartext{3}}{}%
\IfStrEq{\LWR@strresult}{W}{\LWR@multicolpartext{3}}{}%

\IfStrEq{\LWR@strresult}{S}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{s}{\LWR@multicoltext}{}%

\IfStrEq{\LWR@strresult}{X}{\LWR@multicolpartext{1}}{}%
\IfStrEq{\LWR@strresult}{|}{\LWR@multicolskip}{}%
\IfStrEq{\LWR@strresult}{:}{\LWR@multicolskip}{}%
\IfStrEq{\LWR@strresult}{;}{%
    \LWR@multicolskip%
    \addtocounter{LWR@tablemulticolspos}{1}% skip parameter
}{}%
\IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{!}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{>}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{<}}{\LWR@multicolother{#1}}{}%
```

If an invalid column type:

```
\ifbool{LWR@validtablecol}{}{\LWR@multicoltext}%
```

Tracing:

```
\LWR@traceinfo{lwr@printmccoldata done}%
}
```

`\parsemulticolumnalignment` {⟨*1: colspec*⟩} {⟨*2: printresults*⟩}

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a `p{spec}` column, or `@`, `>`, `<`, is a token list which will NOT match `l`, `c`, `r`, or `p`.

```
\newcommand*{\LWR@parsemulticolumnalignment}[2]{%
\setcounter{LWR@tablemulticolspos}{1}%
\StrLen{#1}[\LWR@strresult]%
\setcounter{LWR@tablemulticolswidth}{\LWR@strresult}%
```

Scan across the tokens in the column spec:

```
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@tablemulticolspos}}{>}%
            {\value{LWR@tablemulticolswidth}}%
    }%
}%
{%
```

Execute the assigned print function for each token in the column spec:

```
#2{#1}%
```

Move to the next token in the column spec:

```
\addtocounter{LWR@tablemulticolspos}{1}%
}%
}
```

72.23.2 Multicolumn factored code

\LWR@addmulticolvertrulecolor

```
\newcommand*{\LWR@addmulticolvertrulecolor}{%
```

No vertical rules if finishing the `tabular` with a row of empty cells:

```
\ifbool{LWR@tabularmutemods}{}{%
```

Left side:

```
    \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{%
        \LWR@tdaddstyle%
        border-left: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{%
        \LWR@tdaddstyle%
        border-left: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{%
        \LWR@tdaddstyle%
        border-left: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
        \LWR@tdaddstyle%
        border-left: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
```

Right side:

```
    \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{%
```

```
        \LWR@tdaddstyle%
        border-right: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{%
        \LWR@tdaddstyle%
        border-right: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{%
        \LWR@tdaddstyle%
        border-right: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
        \LWR@tdaddstyle%
        border-right: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
}%
}
```

```
\newcommand{\LWR@multicoltext}{}
```

To find multicolumn right trim:

```
\newcounter{LWR@lastmulticolumn}
```

`\LWR@domulticolumn` `[`⟨*1: vpos*⟩`]` `[`⟨*2: #rows*⟩`]` {⟨*3: numLaTeXcols*⟩} {⟨*4: numHTMLcols*⟩} {⟨*5: colspec*⟩} {⟨*6: text*⟩}

```
\NewDocumentCommand{\LWR@domulticolumn}{o o m m m +m}{%
\LWR@traceinfo{LWR@domulticolumn -#1- -#2- -#4- -#5-}%
```

Remember the text to be inserted, and remember that a valid column type was found:

```
\renewcommand{\LWR@multicoltext}{%
#6%
\global\booltrue{LWR@validtablecol}%
}%
```

Compute the rightmost column to be included. This is used to create the right trim.

```
\setcounter{LWR@lastmulticolumn}{\value{LWR@tableLaTeXcolindex}}%
\addtocounter{LWR@lastmulticolumn}{#3}%
\addtocounter{LWR@lastmulticolumn}{-1}%
```

Row processing:

```
\LWR@maybenewtablerow%
```

Begin the opening table data tag:

```
\LWR@htmltag{td colspan="#4" %

\IfValueT{#2}{ % rows?
rowspan="#2" %
```

```
\IfValueT{#1}{% vpos?
\ifstrequal{#1}{b}{style="\LWR@print@mbox{vertical-align:bottom}" }{}%
\ifstrequal{#1}{t}{style="\LWR@print@mbox{vertical-align:top}" }{}%
}% vpos?
}% rows?

 class="td%
```

Print the column type and vertical bars:

```
\setcounter{LWR@mcolvertbarsl}{0}%
\setcounter{LWR@mcolvertbarsr}{0}%
\setcounter{LWR@mcolvertbarsldash}{0}%
\setcounter{LWR@mcolvertbarsrdash}{0}%
\booltrue{LWR@mcolvertbaronleft}%
\LWR@parsemulticolumnalignment{#5}{\LWR@printmccoltype}%
```

If this column has a cmidrule, add “rule” to the end of the HTML class tag.

If this position had a “Y” then add “rule” for a horizontal rule:

```
\LWR@subaddcmidruletrim%
{\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
{\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@lastmulticolumn}}}%
```

Also add vertical bar class.

```
\ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{ tvertbarl}{}%
\ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{ tvertbarldouble}{}%
\ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{ tvertbarr}{}%
\ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{ tvertbarrdouble}{}%
\ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{ tvertbarldash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{ tvertbarldoubledash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{ tvertbarrdash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{ tvertbarrdoubledash}{}%
```

Close the class tag’s opening quote: " NOT A TYPO

```
%

\LWR@tdstartstyles%

\LWR@addtabularrowcolor%

\LWR@addcmidrulewidth%
\LWR@addcdashline%
\LWR@addtabularhrulecolor%
\LWR@addmulticolvertrulecolor%
\LWR@addformatwpalignment{#5}%
\LWR@tdendstyles%
}% end of the opening table data tag
\global\boolfalse{LWR@intabularmetadata}%
\LWR@parsemulticolumnalignment{#5}{\LWR@printmccoldata}%
}
```

72.23.3 Multicolumn

\LWR@htmlmulticolumn {⟨*numcols*⟩} {⟨*alignment*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlmulticolumn}{m m +m}%
{%
```

Figure out how many extra HTML columns to add for `@` and `!` columns:

```
\LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn tag:

```
\LWR@domulticolumn{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#3}%
```

Move to the next LaTeX column:

```
\addtocounter{LWR@tableLaTeXcolindex}{#1}%
\addtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing `@` or `!` columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}
```

72.23.4 Longtable captions

longtable captions use `\multicolumn`.

Bool LWR@starredlongtable Per the caption pacakge, step the counter if `longtable*`.

```
\newbool{LWR@starredlongtable}
\boolfalse{LWR@starredlongtable}
```

Per the caption package. User-redefinable float type.

```
\providecommand*{\LTcaptype}{table}
```

\LWR@longtabledatacaptiontag * [⟨*toc entry*⟩] {⟨*caption*⟩}

```
\NewDocumentCommand{\LWR@longtabledatacaptiontag}{s o +m}
{%
```

Remember the latest name for `\nameref`:

```
\IfValueTF{#2}{% optional given?
    \ifblank{#2}% optional empty?
    {\LWR@setlatestname{#3}}% empty
    {\LWR@setlatestname{#2}}% given and non-empty
}% optional given
{\LWR@setlatestname{#3}}% no optional
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for `@` and `!` columns found between the first and the last column:

```
\LWR@tabularhtmlcolumns{1}{\arabic{LWR@tabletotalLaTeXcols}}
```

Create the multicolumn tag:

```
\LWR@domulticolumn{\arabic{LWR@tabletotalLaTeXcols}}%
    {\arabic{LWR@tabhtmlcoltotal}}%
    {P}%
{% \LWR@domulticolumn
\IfBooleanTF{#1}% star?
```

Star version, show a caption but do not make a LOT entry:

```
{% yes star
    \LWR@figcaption%
    \LWR@isolate{#3}%
    \endLWR@figcaption%
}%
{% No star:
```

Not the star version:

Don't step the counter if `\caption[]{A caption.}`

```
    \ifbool{LWR@starredlongtable}%
    {%
        \ifblank{#2}% TOC entry
        {}%
        {%
            \refstepcounter{\LTcaptype}%
            \protected@edef\@currentlabel{%
                \@nameuse{p@\LTcaptype}\@nameuse{the\LTcaptype}%
            }%
        }%
    }{}%
```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```
    \LWR@figcaption%
    \LWR@isolate{\@nameuse{fnum@\LTcaptype}}%
    \CaptionSeparator%
    \LWR@isolate{#3}%
    \endLWR@figcaption%
```

See if an optional caption was given:

```
    \ifblank{#2}% TOC entry empty
```

if the optional caption was given, but empty, do not form a TOC entry

```
    {}%
```

If the optional caption was given, but might only be `[]`:

```
    {% TOC entry not empty
        \IfNoValueTF{#2}% No TOC entry?
```

The optional caption is `[]`:

```
        {% No TOC entry
            \addcontentsline%
            {\@nameuse{ext@\LTcaptype}}%
            {\LTcaptype}%
            {%
                \protect\numberline%
              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
                {\ignorespaces \LWR@isolate{#3}\protect\relax}%
            }%
        }% end of No TOC entry
```

The optional caption has text enclosed:

```
        {% yes TOC entry
            \addcontentsline%
            {\@nameuse{ext@\LTcaptype}}%
            {\LTcaptype}%
            {%
                \protect\numberline%
              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
                {\ignorespaces \LWR@isolate{#2}\protect\relax}%
            }%
        }% end of yes TOC entry
    }% end of TOC entry not empty
}% end of no star
```

Skip any trailing `@` or `!` columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}% end of \LWR@domulticolumn

\addtocounter{LWR@tableLaTeXcolindex}{\arabic{LWR@tabletotalLaTeXcols}}
\addtocounter{LWR@tableLaTeXcolindex}{-1}

}
```

72.23.5 Counting HTML tabular columns

The LaTeX specification for a table includes a number of columns separated by the `&` character. These columns differ in content from line to line. Additional virtual columns may be specified by the special `@` and `!` columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, @ and ! columns are placed into their own tabular columns. Thus, a LaTeX \multicolumn command may span several additional @ and ! columns in HTML output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```
\newcounter{LWR@tabhtmlcolindex}
\newcounter{LWR@tabhtmlcolend}
\newcounter{LWR@tabhtmlcoltotal}
```

\LWR@subtabularhtmlcolumns {⟨*index*⟩}

Factored from \LWr@tabularhtmlcolumns, which follows.

```
\newcommand*{\LWR@subtabularhtmlcolumns}[1]{%
```

Temporarily define a macro equal to the @ specification for this column:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colatspec}{#1}}%
```

If the @ specification is not empty, add to the count:

```
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\addtocounter{LWR@tabhtmlcoltotal}{1}}%
```

Likewise for the ! columns:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colbangspec}{#1}}%
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\addtocounter{LWR@tabhtmlcoltotal}{1}}%
}
```

\LWR@tabularhtmlcolumns {⟨*starting LaTeX column*⟩} {⟨*number LaTeX columns*⟩}

Compute the total number of HTML columns being spanned, considering the starting LaTeX table column and the number of LaTeX tabular columns being spanned. Any @ and ! columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter LWR@tabhtmlcoltotal.

```
\newcommand*{\LWR@tabularhtmlcolumns}[2]{%
```

Count the starting index, compute ending index, and begin with the count being the LaTeX span, to which additional @ and ! columns may be added:

```
\setcounter{LWR@tabhtmlcolindex}{#1}%
\setcounter{LWR@tabhtmlcoltotal}{#2}%
\setcounter{LWR@tabhtmlcolend}{#1}%
\addtocounter{LWR@tabhtmlcolend}{#2}%
```

If at the left edge, add the at/bang columns for the left edge:

```
\ifnumcomp{\value{LWR@tabhtmlcolindex}}{=}{1}{%
    \LWR@subtabularhtmlcolumns{leftedge}%
}{}%
```

Walk across the LaTeX columns looking for `@` and `!` columns:

```
\whileboolexpr{%
    test {%
        \ifnumcomp{\value{LWR@tabhtmlcolindex}}{<}{\value{LWR@tabhtmlcolend}}%
    }%
}%
{%
    \LWR@subtabularhtmlcolumns{\arabic{LWR@tabhtmlcolindex}}%
    \addtocounter{LWR@tabhtmlcolindex}{1}%
}% whiledo
}
```

```
\end{warpHTML}
```

72.24 Multirow if not loaded

A default defintion in case multirow is not loaded. This is used during table parsing.

```
\begin{warpHTML}
\newcommand{\multirow}[2][c]{}
\end{warpHTML}
```

72.25 Multicolumnrow

A print-mode version is defined here, and is also used during HTML output while inside a `lateximage`.

See section 339 for the HTML versions.

for HTML & PRINT:

```
\begin{warpall}
```

`\multicolumnrow` {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

For discussion of the use of `\DeclareExpandableDocumentCommand`, see:
https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex

`\AtBeginDocument` to adjust after the user may have loaded multirow, which requires several tests to determine which version is loaded and thus which options are available.

```
\AtBeginDocument{
```

`\@ifundefined{@xmultirow}` determines if multirow was never loaded.

Null action if not loaded:

```
\@ifundefined{@xmultirow}
{
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {}%
}% no version of multirow was loaded
{% \@xmultirow defined, so some version of multirow was loaded
```

\@ifpackageloaded{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The print version:

```
\@ifpackageloaded{multirow}{% v2.0 or newer
\@ifpackagelater{multirow}{2016/09/01}% 2016/09/27 for v2.0
{% v2.0+:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow[#3]{#4}[#5]{#6}[#7]{#8}}}%
}
{% loaded but older, probably not executed:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
}
}% packageloaded{multirow}
```

If not \@ifpackageloaded{multirow} but \@xmultirow is defined, then this must be v1.6 or earlier, which did not \ProvidesPackage{multirow}, and did not have the vposn option.

```
{% v1.6 or older did not \ProvidePackage
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
}

}% \@ifundefined{@xmultirow}

\providecommand*{\multicolumnrow}{\LWR@print@multicolumnrow}

}% AtBeginDocument


\end{warpall}
```

72.26 Utility macros inside a table

for HTML output:

```
\begin{warpHTML}
```

Used to prevent opening a tabular data cell if the following token is one which does not create tabular data:

```
\newcommand*{\LWR@donothing}{}
```

In case array is not loaded:

```
\let\firsthline\relax
\let\lasthline\relax
\newcommand*{\firsthline}{}
\newcommand*{\lasthline}{}
```

In case bigdelim is not loaded:

```
\newcommand*{\ldelim}{}
\newcommand*{\rdelim}{}
```

```
\end{warpHTML}
```

72.27 Special-case tabular markers

for HTML & PRINT:

```
\begin{warpall}
```

`\TabularMacro` Place this just before inserting a custom macro in a table data cell. Doing so tells lwarp not to automatcally start a new HTML table data cell yet. See section 8.10.1.

```
\newcommand*{\TabularMacro}{}
```

```
\end{warpall}
```

`\ResumeTabular` Used to resume tabular entries after resuming an environment.

⚠ `tabular` inside another environment

When creating a new environment which contains a `tabular` environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

for HTML output:

```
\begin{warpHTML}

\newcommand*{\ResumeTabular}{%
\global\boolfalse{LWR@exitingtabular}%
\global\boolfalse{LWR@tabularmutemods}%
\LWR@getmynexttoken%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}

\newcommand*{\ResumeTabular}{}

\end{warpprint}
```

72.28 Checking for a new table cell

for HTML output:

```
\begin{warpHTML}
```

Bool `LWR@exitingtabular` When `\end` is found, turns off the next opening data tag.

```
\newbool{LWR@exitingtabular}
```

Bool `LWR@tabularmutemods` Mutes HTML output for `@`, `!`, < and >.

This is used while printing the final row to generate `\bottomrules`.

```
\newbool{LWR@tabularmutemods}
```

`\LWR@tabledatacolumntag` Open a new HTML table cell unless the next token is for a macro which does not create data, such as `\hline`, `\toprule`, etc:

```
\newcommand*{\LWR@tabledatacolumntag}%
{%
\LWR@traceinfo{LWR@tabledatacolumntag}%
```

`\show\LWR@mynexttoken` to see what tokens to look for

If not any of the below, start a new table cell:

```
\global\let\LWR@mynextaction\LWR@tabledatasinglecolumntag%
```

If exiting the tabular:

```
\ifdefequal{\LWR@mynexttoken}{\end}%
    {\global\booltrue{LWR@exitingtabular}}{}%
```

`longtable` can have a caption in a cell

```
\ifdefequal{\LWR@mynexttoken}{\caption}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Look for other things which would not start a table cell:

```
\ifdefequal{\LWR@mynexttoken}{\multicolumn}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\multirow}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\multicolumnrow}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\noalign}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an `\mrowcell`, this is a cell to be skipped over:

```
\ifdefequal{\LWR@mynexttoken}{\mrowcell}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an `\mcolrowcell`, this is a cell to be skipped over:

```
\ifdefequal{\LWR@mynexttoken}{\mcolrowcell}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\TabularMacro}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\hline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\firsthline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\lasthline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\toprule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\midrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cmidrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%


\ifdefequal{\LWR@mynexttoken}{\morecmidrules}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\specialrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

```
\ifdefequal{\LWR@mynexttoken}{\cline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\bottomrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\rowcolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\arrayrulecolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\doublerulesepcolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\warpprintonly}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\warpHTMLonly}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\ldelim}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\rdelim}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

For arydshln:

```
\ifdefequal{\LWR@mynexttoken}{\hdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\firsthdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\lasthdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Ignore an empty line between rows:

```
\ifdefequal{\LWR@mynexttoken}{\par}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

No action for an \end token.

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```
\LWR@traceinfo{LWR@tabledatacolumntag: about to do mynext}%
\LWR@mynextaction%
\LWR@traceinfo{LWR@tabledatacolumntag: done}%
}
```

```
\end{warpHTML}
```

72.29 \mrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mrowcell
⚠ multirow cells

The user must insert \mrowcell into any \multirow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mrowcell}{}
```

```
\end{warpall}
```

72.30 \mcolrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mcolrowcell
⚠ multirow cells

The user must insert \mcolrowcell into any \multicolumnrow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mcolrowcell}{}
```

```
\end{warpall}
```

72.31 HTML tabular environment

for HTML output:

```
\begin{warpHTML}
```

These are default defininitions in case booktabs is not loaded, and are not expected to used, but must exist as placeholders. They are pre-deleted in case memoir has already loaded booktabs.

```
\LetLtxMacro\toprule\relax
\LetLtxMacro\midrule\relax
\LetLtxMacro\cmidrule\cline
\LetLtxMacro\bottomrule\relax
\LetLtxMacro\addlinespace\relax
\LetLtxMacro\morecmidrules\relax
\LetLtxMacro\specialrule\relax

```

```
\newcommand*{\toprule}[1][]{\hline}
\newcommand*{\midrule}[1][]{\hline}
\LetLtxMacro\cmidrule\cline
\newcommand*{\bottomrule}[1][]{\hline}
\newcommand*{\addlinespace}[1][]{}
\newcommand*{\morecmidrules}{}
\newcommand*{\specialrule}[3]{\hline}
```

`\noalign` {⟨*text*⟩} Redefined for use inside `tabular`.

```
\LetLtxMacro\LWR@orignoalign\noalign

\newcommand{\LWR@tabularnoalign}[1]{%
\begingroup%
\global\advance\rownum\m@ne%
\renewcommand*{\LWR@xcolorrowHTMLcolor}{}%
\multicolumn{\value{LWR@tabletotalLaTeXcols}}{l}{#1} \\
\endgroup%
% \@rowc@lors%
\LWR@getmynexttoken%
}
```

`\LWR@HTMLhline` The definition of `\hline` depends on whether tabls has been loaded. If so, optional space below the line may be specified, but will be ignored.

```
\AtBeginDocument{
\@ifpackageloaded{lwarp-tabls}
{
\newcommand*{\LWR@HTMLhline}[1][]{%
    \ifbool{FormatWP}%
    {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
    {\addtocounter{LWR@hlines}{1}}%
    \LWR@getmynexttoken}%
}
{
\newcommand*{\LWR@HTMLhline}{%
    \ifbool{FormatWP}%
    {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
    {\addtocounter{LWR@hlines}{1}}%
    \LWR@getmynexttoken}%
}
}% AtBeginDocument
```

`\LWR@HTMLcline` {⟨*columns*⟩}

```
\NewDocumentCommand{\LWR@HTMLcline}{m}%
{\LWR@docmidrule{#1}\LWR@getmynexttoken}%
```

`\LWR@tabular@warpprintonly` {⟨*contents*⟩}

Only process the contents if producing printed output. Modified inside a `tabular` to grab the next token.

```
\newcommand{\LWR@tabular@warpprintonly}[1]{%
    \ifbool{warpingprint}{#1}{}%
    \LWR@getmynexttoken%
}
```

\LWR@nullifyNoAutoSpacing For babel-french, turn off auto spacing at the start of the tabular, then nullify the autospacing commands inside the tabular, since they were not compatible with the tabular column parsing code, which uses xstring.

```
\AtBeginDocument{
\@ifundefined{frenchbsetup}%
{% no babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{}
}% no babel-french
{% yes babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{%
        \NoAutoSpacing%
        \renewcommand*{\NoAutoSpacing}{}%
        \renewcommand*{\LWR@FBcancel}{}%
    }
}% yes babel-french
}% AtBeginDocument
```

Env tabular <direction> [⟨*vertposition*⟩] {⟨*colspecs*⟩}

The <direction> is from plext for Japanese documents, and is ignored.

```
\StartDefiningTabulars

\NewDocumentCommand{\LWR@HTML@@tabular}{d<> o m}
{%
\LWR@traceinfo{LWR@HTML@@tabular started}%
```

⚠ <table> inside In LaTeX, a tabular may be placed inside a minipage, but in HTML a <table> may not be inside a . Since there may be several nested s, with an unknown number of other objects between, it is hard to undo all these s before the <table> then redo them after. The broswer probably compensates for this situation, but formatting may be lost inside the <table> because several things are neutralized inside a . Furthermore, in the HTML output, the entire <table> is placed on a single line of HTML code, since the line breaking commands are neutralized inside a . Since this is such a sloppy situation, a warning is issued here instructing the user to please isolate the to print-only.

```
\ifnumcomp{\value{LWR@spandepth}}{>}{0}{%
    \PackageWarning{lwarp}{%
        A tabular is being used inside a span such as\MessageBreak
        a minipage. Some formatting may not be correct\MessageBreak
        in the tabular.\MessageBreak
      It is recommended to use \protect\warpprintonly\space or the\MessageBreak
        warpprint environment to isolate the span to\MessageBreak
        print-only,%
    }
}{}%
```

```
\addtocounter{LWR@tabulardepth}{1}%
```

Not yet started a table row:

```
\global\boolfalse{LWR@startedrow}%
```

Not yet doing any rules:

```
\setcounter{LWR@hlines}{0}%
\setcounter{LWR@hdashedlines}{0}%
\global\boolfalse{LWR@doingtbrule}%
\global\boolfalse{LWR@doingcmidrule}%
```

For babel-french, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the tabular parsing code.

```
\LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of tabular command. Unmute the `@` and `!` columns.

```
\global\boolfalse{LWR@exitingtabular}%
\global\boolfalse{LWR@tabularmutemods}%
```

Error if failed to use `\mrowcell` or `\mcolrowcell` when needed.

```
\boolfalse{LWR@usedmultirow}
\boolfalse{LWR@foundmrowcell}
```

Create the `table` tag:

```
\global\booltrue{LWR@intabularmetadata}%
\LWR@traceinfo{LWR@@tabular: About to LWR@forecenewpage.}%
\LWR@forcenewpage
\LWR@htmlblocktag{table}%
```

Parse the table columns:

```
\LWR@parsetablecols{#3}%
```

Table col spec is: `\LWR@tablecolspec` which is a string of `llccrr`, etc.

Do not place the table inside a paragraph:

```
\LWR@stoppars%
```

Track column #:

```
\setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
\global\boolfalse{LWR@tabularcelladded}%
```

Start looking for midrules:

```
\LWR@clearmidrules%
```

\\ becomes a macro to end the table row:

```
\LetLtxMacro{\\}{\LWR@tabularendofline}%
```

\warpprintonly inside a tabular must grab the next token.

```
\LetLtxMacro\warpprintonly\LWR@tabular@warpprintonly%
```

The following adjust for colortbl.

```
\LetLtxMacro\arrayrulecolor\arrayrulecolornexttoken%
\LetLtxMacro\doublerulesepcolor\doublerulesepcolornexttoken%
\gdef\LWR@columnHTMLcolor{}%
\gdef\LWR@rowHTMLcolor{}%
\gdef\LWR@cellHTMLcolor{}%
\@rowcolors%
```

The vertical rules are set to the color active at the start of the tabular. \arrayrulecolor will then affect horizontal rules inside the tabular, but not the vertical rules.

```
\ifdefvoid{\LWR@ruleHTMLcolor}%
    {\edef\LWR@vertruleHTMLcolor{black}}%
    {\edef\LWR@vertruleHTMLcolor{\LWR@origpound\LWR@ruleHTMLcolor}}%
```

Tracking the depth of cell color s:

```
\setcounter{LWR@cellcolordepth}{0}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with \LWR@getmynextoken to see if the next token might create a new data cell:

The optional parameter for \hline supports the tabls package.

```
\LWR@traceinfo{LWR@@HTML@tabular: redefining macros}%
\LetLtxMacro\noalign\LWR@tabularnoalign%
\LetLtxMacro\hline\LWR@HTMLhline%
\LetLtxMacro\cline\LWR@HTMLcline%

\DeclareDocumentCommand{\hdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\cdashline}{m}{%
    \LWR@docdashline{##1}\LWR@getmynexttoken%
}%
```

```
\DeclareDocumentCommand{\firsthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\lasthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%
```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use `\LWR@getmynexttoken`.

```
\renewcommand{\multicolumn}{\LWR@htmlmulticolumn}%
\renewcommand*{\mrowcell}{%
    \LWR@maybenewtablerow%
    \LWR@tabularleftedge%
    \global\booltrue{LWR@skippingmrowcell}%
    \booltrue{LWR@foundmrowcell}%
}%
\renewcommand*{\mcolrowcell}{%
    \LWR@maybenewtablerow%
    \global\booltrue{LWR@skippingmcolrowcell}%
    \booltrue{LWR@foundmrowcell}%
}%
\LetLtxMacro\caption\LWR@longtabledatacaptiontag%
```

Reset for new processing:

```
\global\boolfalse{LWR@tableparcell}%
\global\boolfalse{LWR@skippingmrowcell}%
\global\boolfalse{LWR@skippingmcolrowcell}%
\global\boolfalse{LWR@skipatbang}%
\global\boolfalse{LWR@emptyatbang}%
```

Set `&` for its special meaning inside the tabular:

```
\StartDefiningTabulars%
\protected\gdef&{\LWR@tabularampersand}%
```

Locally force any minipages to be fullwidth, until the end of the `tabular`:

```
\booltrue{LWR@forceminipagefullwidth}
```

Nest one level deeper of tabular paragraph handling:

```
\addtocounter{LWR@tabularpardepth}{1}%
```

Look ahead for a possible table data cell:

```
\LWR@traceinfo{LWR@@HTML@tabular: about to LWR@getmynexttoken}%
\LWR@getmynexttoken%
}%
```

Ending the environment:

```
\newcommand*{\LWR@HTML@endtabular}
{%
\LWR@traceinfo{LWR@HTML@endtabular}%
```

Unnest one level of tabular paragraph handling:

```
\addtocounter{LWR@tabularpardepth}{-1}%
\ifboolexpr{%
    test {%
      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}
    } or %
    (%
        bool{LWR@intabularmetadata} and%
        not bool{LWR@tabularcelladded} and%
        test {%
        \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}%
        }%
    )%
}%
{%
    \LWR@tabularfinishrow%
}%
{%
    \LWR@closetabledatacell%
}%
\LWR@htmlblocktag{/tr}%
```

xcolor row color support:

```
\@rowc@lors%
```

```
\LWR@htmlblocktag{/table}%
\global\boolfalse{LWR@intabularmetadata}%
```

Unnest one level of tabular:

```
\addtocounter{LWR@tabulardepth}{-1}%
```

Restore & to its usual meaning:

```
\protected\gdef&{\LWR@origampmacro}%
\StopDefiningTabulars%
```

Error if used `\multirow` or `\multicolumnrow` without using `\mrowcell` or `\mcolrowcell`.

```
\ifbool{LWR@usedmultirow}{%
```

```
    \ifbool{LWR@foundmrowcell}%
        {}%
        {%
            \PackageError{lwarp}%
            {%
            When using \protect\multirow, \protect\multicolumnrow,\MessageBreak
                or the bigdelim package,\MessageBreak
             place \protect\mrowcell\space or \protect\mcolrowcell\MessageBreak
                in empty cells which are to be skipped.\MessageBreak
                See the lwarp package documentation:\MessageBreak
                "Special cases and limitations" -> "Tabular"
            }%
            {%
                See the lwarp package documentation:\MessageBreak
                "Special cases and limitations" -> "Tabular".
            }%
        }%
}{}%

\LWR@traceinfo{LWR@HTML@endtabular finished}%
}

\csletcs{LWR@HTML@endtabular*}{LWR@HTML@endtabular}

\StopDefiningTabulars
```

siunitx may redefine `tabular`, so set the following later:

```
\AtBeginDocument{
    \LetLtxMacro\LWR@origendtabular\endtabular
    \csletcs{LWR@origendtabular*}{endtabular*}
    \LWR@formatted{@tabular}
    \LWR@formatted{endtabular}
    \LWR@formatted{endtabular*}
}

\end{warpHTML}
```

73 Cross-references

Sectioning commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

Table 12 shows the data structures related to cross-referencing.

Table 12: Cross-referencing data structures

Original LaTeX: (print and HTML)

\refstepcounter: Steps the couunter and sets \@currentlabel.

\@currentlabel: \p@<ctr>\the<ctr> Updated by \refstepcounter.

\label: Writes to the .aux file:
\newlabel{<label>}{{\@currentlabel}{\thepage}}

\newlabel: When the .aux file is read, sets \r@<label>.

\r@<label>: Set to: {{\@currentlabel}{\thepage}}

\ref: Returns the first part of \r@<label>.

\pageref: Returns the second part of \r@<label>.

Added by lwarp: (HTML only)

\label: Adds HTML tags (section 73.3), and another .aux entry (section 73.2).

\newlabel: Unchanged. When the .aux file is read, sets \r@<label>@lwarp.

\r@<label>@lwarp: Set to {{section_name}{file_name}{depth}{number}}:

\LWR@nameref: The section name for this label.

\LWR@htmlfileref: The filenumber or name for this label.

\LWR@lateximagedepthref: The lateximagedepth for this label.

\LWR@lateximagenumberref: The lateximagenumber for this label.

\nameref: Emualted from hyperref for lwarp. See section 73.4.

\ref and \nameref: Adds HTML tags. See section 73.4.

Added by amsmath: (print and HTML)

\label: Execution is delayed until the math environment is completed.

\ltx@label: LaTeX \label, (HTML: patched by lwarp,) later patched by cleveref.

Added by cleveref: (print and HTML)

\refstepcounter: Added: sets \cref@currentlabel.

\cref@currentlabel: (<type>=<ctr> unless an alias is used):
[<type>][\arabic{<ctr>}][<parent ctrs>]{\p@<ctr>\the<ctr>} Also see section 59.4 for use with footnotes.

\label: Writes to the .aux file:
\newlabel{<label>@cref}{{\cref@currentlabel}{\thepage}}

\newlabel: Unchanged. When the .aux file is read, sets \r@<label>@cref.

\r@<label>@cref: Set to: {{\cref@currentlabel}{\thepage}}

Utility functions: See \cref@getlabel, \cref@gettype, \cref@getcounter, \cref@getprefix.

Cross-referencing names: \crefname and \Crefname assign human-readable names for references to this counter type.

Additionally patched by lwarp: (HTML only)

\cref, etc.: Modified for lwarp. See section 87.

\label inside math: See section 79.7.1.

Footnotes: See \noteentry in section 59.4.

for HTML output:
```
\begin{warpHTML}
```

73.1 Setup

`\@currentlabelname` To remember the most recently defined section name, description, or caption, for `\nameref`.

```
\providecommand*{\@currentlabelname}{}
```

`\LWR@stripperiod` {⟨*text*⟩} [⟨.⟩]

Removes a trailing period.

```
\def\LWR@stripperiod#1.\ltx@empty#2\@nil{#1}%
```

`\LWR@setlatestname` {⟨*object name*⟩}

Removes `\label`, strips any final period, and remembers the result.

```
\newcommand*{\LWR@setlatestname}[1]{%
```

Remove `\label` and other commands from the name, the strip any final period. See gettitlestring.

```
\GetTitleStringExpand{#1}%
\edef\@currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
\edef\@currentlabelname{%
    \expandafter\LWR@stripperiod\@currentlabelname%
    \ltx@empty.\ltx@empty\@nil%
}%
}
```

73.2 New lwarp labels.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

See:
http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference

`\LWR@setref` {⟨*args list*⟩} {⟨*selector*⟩} {⟨*label*⟩}

`\@setref` without the `\null` (`\hbox`), and without the warning messages. Each caused problems with lwarp references. The regular reference will cause the warning.

```
\def\LWR@setref#1#2#3{%
  \ifx#1\relax%
    ??%
  \else%
   \expandafter#2#1%
  \fi}
```

`\LWR@nameref` {⟨*label*⟩} Returns the section name for this label:

```
\newcommand*{\LWR@nameref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@firstoffour{#1}%
}
```

`\LWR@htmlfileref` {⟨*label*⟩} Returns the file number or name for this label:

```
\newcommand*{\LWR@htmlfileref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@secondoffour{#1}%
}
```

`\LWR@lateximagedepthref` {⟨*label*⟩} Returns the `lateximagedepth` for this label:

```
\newcommand*{\LWR@lateximagedepthref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@thirdoffour{#1}%
}
```

`\LWR@lateximagenumberref` {⟨*label*⟩} Returns the `lateximagenumber` for this label:

```
\newcommand*{\LWR@lateximagenumberref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@fourthoffour{#1}%
}
```

`\LWR@lwarplabel` {⟨*label*⟩} Sanitize the name and then creates the label:

```
\newcommand*{\LWR@lwarplabel}[1]{%
\LWR@traceinfo{LWR@lwarplabel !#1!}%
\LWR@setlatestname{\@currentlabelname}%
    \@bsphack%
    \protected@write\@auxout{}%
        {\string\newlabel{#1@lwarp}{%
            {\@currentlabelname}%
        {\ifbool{FileSectionNames}{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}%
            {\arabic{LWR@lateximagedepth}}%
            {\arabic{LWR@lateximagenumber}}%
        }}%
    \@esphack%
}
```

73.3 Labels

`\LWR@sublabel` {⟨*label*⟩} Creates an HTML id tag.

\detokenize is used to allow underscores in the labels.

```
\newcommand*{\LWR@sublabel}[1]{%
\LWR@traceinfo{LWR@sublabel !#1!}%
```

Create an HTML id tag unless are inside a lateximage, since it would appear in the image:

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{% not lateximage
```

If not doing a lateximage, create an HTML ID tag: (To be factored...)

```
    \LWR@sanitize{#1}%
    \ifbool{LWR@doingstartpars}%
    {% pars allowed
        \ifbool{LWR@doingapar}%
        {% par started
         \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
        }% par started
        {% par not started
            \LWR@stoppars%
         \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
            \LWR@startpars%
        }% par not started
    }% pars allowed
    {% pars not allowed
        \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
    }% pars not allowed
}% not lateximage
}
```

\LWR@new@label (⟨*bookmark*⟩) {⟨*label*⟩} [⟨*type*⟩]

\label during HTML output when not in SVG math mode, removing extra spaces around the label, as done by a regular LaTeX \label.

The is also used during a lateximage, including SVG math, since the special label handling is required, but \LWR@sublabel does not generate HTML tags inside a lateximage.

clevereref later encases this to add its own cross-referencing.

The optional ⟨*bookmark*⟩ is per the memoir class, and is ignored.

The optional ⟨*type*⟩ is per the ntheorem package, and is ignored.

```
\NewDocumentCommand{\LWR@new@label}{d() m o}{%
\LWR@traceinfo{LWR@new@label: starting}%
\LWR@traceinfo{LWR@new@label: !#2!}%
% \@bsphack%
```

Create a traditional LaTeX label, as modified by cleveref:

```
\LWR@orig@label{#2}%
```

Create a special label which holds the section number, LWR@htmlfilenumber, LWR@lateximagedepth, and LWR@lateximagenumber:

```
\LWR@traceinfo{LWR@new@label: filesectionnames is \ifbool{FileSectionNames}{true}{false}}%
\LWR@traceinfo{LWR@new@label: LWR@thisfilename is !\LWR@thisfilename!}%
\LWR@traceinfo{LWR@new@label: LWR@htmlfilenumber is \arabic{LWR@htmlfilenumber}}%
\LWR@lwarplabel{#2}%
\LWR@sublabel{#2}%
% \@esphack%
\LWR@traceinfo{LWR@new@label: done}%
}
```

73.4 References

\LWR@addlinktitle

```
\newcommand*{\LWR@addlinktitle}{%
    \ifdefvoid{\LWR@ThisAltText}{}{ % space
        title="\LWR@ThisAltText" % space
        \gdef\LWR@ThisAltText{}%
    }%
}
```

\LWR@startref {⟨*label*⟩} (Common code for \ref and \nameref.)

Open an HTML tag reference to a filename, # character, and a label.

```
\newcommand*{\LWR@startref}[1]
{%
\LWR@sanitize{#1}%
\LWR@traceinfo{LWR@startref A: !#1!}%
```

Create the filename part of the link:

```
\LWR@htmltag{a href="%
\LWR@traceinfo{LWR@startref B}%
\LWR@print@mbox{\LWR@htmlrefsectionfilename{#1}}%
\LWR@traceinfo{LWR@startref C}%
\LWR@origpound%
```

Create the destination id:

See if LWR@lateximagedepth is unknown:

```
\LWR@traceinfo{LWR@startref D: !#1!}%
\ifcsundef{r@#1@lwarp}%
```

"??" if LWR@lateximagedepth is unknown, so create a link with an unknown destination:

```
{%
    \LWR@traceinfo{LWR@startref D0: ??}%
    ??%
}%
```

If `LWR@lateximagedepth` is known. Use a lateximage if the depth is greater than zero, or a regular link otherwise:

```
{%
    \ifthenelse{\cnttest{\LWR@lateximagedepthref{#1}}{>}{0}}%
        {%
            \LWR@ImagesName\LWR@lateximagenumberref{#1}%
        }%
        {%
            \LWR@traceinfo{LWR@startref D3}%
```

`\detokenize` is used to allow underscores in the labels:

```
            \LWR@print@mbox{\LWR@sanitized}%
        }%
}%
\LWR@traceinfo{LWR@startref E}%
```

Closing quote:

```
"%
```

Maybe add a title:

```
\LWR@addlinktitle%
}%
\LWR@traceinfo{LWR@startref F}%
}
```

`\LWR@subnewref` {⟨*label*⟩} {⟨*label or sub@label*⟩}

Factored for the subfig package. Uses the original label for the hyper-reference, but prints its own text, such as "`1(b)`".

```
\NewDocumentCommand{\LWR@subnewref}{m m}{%
\LWR@traceinfo{LWR@subnewref #1 #2}%
\LWR@startref{#1}%
\LWR@print@ref{#2}%
\LWR@htmltag{/a}%
}
```

`\ref` * {⟨*label*⟩} `\ref` is redefined to `\LWR@HTML@ref`, except inside the text part of a `\hyperref`, where it is redefined to `\LWR@ref@ignorestar`.

`\LWR@HTML@ref` * {⟨*label*⟩} Create an internal document reference link, or without a link if starred per hyperref.

```
\NewDocumentCommand{\LWR@HTML@ref}{s m}{%
\LWR@traceinfo{LWR@HTML@ref !#2!}%
\IfBooleanTF{#1}%
{\LWR@print@ref{#2}}%
{\LWR@subnewref{#2}{#2}}%
}

\LWR@formatted{ref}
```

`\LWR@ref@ignorestar` * {⟨*label*⟩} For use inside `\hyperref`. Ignores the star, then uses the original `\ref`.

```
\NewDocumentCommand{\LWR@ref@ignorestar}{s m}{%
    \LWR@print@ref{#2}%
}
```

`\pagerefPageFor` Text for page references.

```
\newcommand*{\pagerefPageFor}{see }
```

`\pageref` * {⟨*label*⟩} Create an internal document reference, or just the unlinked number if starred, per hyperref.

```
\NewDocumentCommand{\LWR@new@pageref}{s m}{%
\IfBooleanTF{#1}%
{(\pagerefPageFor\LWR@print@ref{#2})}%
{(\cpageref{#2})}%
}
```

`\nameref` {⟨*label*⟩}

```
\newrobustcmd*{\nameref}[1]{%
\LWR@traceinfo{nameref}%
\LWR@startref{#1}%
\LWR@traceinfo{nameref B}%
\LWR@nameref{#1}%
\LWR@traceinfo{nameref C}%
\LWR@htmltag{/a}%
\LWR@traceinfo{nameref: done}%
}
```

`\Nameref` {⟨*label*⟩} In print, adds the page number. In HTML, does not.

```
\LetLtxMacro\Nameref\nameref
```

73.5 Hyper-references

⚠ Note that the code currently only sanitizes the underscore character. Additional

characters should be rendered inert as well. See the hyperref.sty definition of \gdef\hyper@normalise for an example.

Pkg hyperref

⚠ Do not tell other packages that hyperref is emulated. Some packages patch various commands if hyperref is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

```
% DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:
% \EmulatesPackage{hyperref}[2015/08/01]% Disabled.  Do not do this.
```

Emulates hyperref:

\@currentHref Added to support backref.

```
\AtBeginDocument{
\def\@currentHref{%
autopage-\theLWR@currentautosec%
}
}
```

\LWR@subhyperref {⟨*URL*⟩}

Starts a link for \LWR@hrefb. A group must have been opened first, with nullified catcodes. The text name is printed afterwards, after the group is closed and catcodes restored.

```
\NewDocumentCommand{\LWR@subhyperref}{m}{%
\LWR@traceinfo{LWR@subhyperref !#1!}%
\LWR@sanitize{#1}%
\LWR@htmltag{%
    a href="\LWR@sanitized" % space
    \LWR@addlinktitle % space
    target="\_{}blank" % space
}%
}
```

\LWR@subhyperreftext {⟨*text*⟩}

Finishes the hyperref for \LWR@hrefb. Catcodes must have been restored already. To be used after \LWR@subhyperref, and after its group has been closed.

```
\newcommand{\LWR@subhyperreftext}[1]{%
#1%
\LWR@htmltag{/a}%
\LWR@ensuredoingapar%
}
```

\LWR@subhyperrefclass {⟨*URL*⟩} {⟨*text*⟩} {⟨*htmlclass*⟩}

```
\NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
\LWR@htmltag{%
    a % space
    href="\begingroup\@sanitize#1\endgroup" % space
    class="#3" % space
    \LWR@addlinktitle % space
}\LWR@orignewline%
#2\LWR@orignewline%
\LWR@htmltag{/a}%
\LWR@ensuredoingapar%
}
```

`\href` `[`⟨*options*⟩`]` `{`⟨*URL*⟩`}`

Create a link with accompanying text:

```
\DeclareDocumentCommand{\LWR@hrefb}{O{} m}{%
\LWR@ensuredoingapar%
\LWR@subhyperref{#2}%
\endgroup% restore catcodes
\LWR@subhyperreftext%
}

\newrobustcmd*{\href}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hrefb%
}
```

`\nolinkurl` `{`⟨*URL*⟩`}`

Print the name of the link without creating the link:

```
\newcommand*{\LWR@nolinkurlb}[1]{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\LWR@templink%
\endgroup%
}

\newrobustcmd*{\nolinkurl}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@nolinkurlb%
}
```

`\url` {⟨*URL*⟩}

Create a link whose text name is the address of the link.

The url package may redefine `\url`, so it is `\let` to `\LWR@urlahere` and also redefined by lwarp-url.

```
\DeclareDocumentCommand{\LWR@urlb}{m}{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\href{\LWR@templink}{\LWR@templink}%
\endgroup%
}

\newrobustcmd*{\url}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@urlb%
}
```

`\LWR@subinlineimage` {⟨<alt> *tag*⟩} {⟨*class*⟩} {⟨*filename*⟩} {⟨*extension*⟩} {⟨*CSS style*⟩}

Factored from `lateximage`.

```
\newcommand*{\LWR@subinlineimage}[5]{%
    \ifblank{#1}%
    {%
        \LWR@htmltag{img \LWR@indentHTML
            src="#3.#4" \LWR@indentHTML
            alt="#3" \LWR@indentHTML
            style="#5" \LWR@indentHTML
            class="#2" \LWR@orignewline
        }%
    }%
    {%
        \LWR@htmltag{img \LWR@indentHTML
            src="#3.#4" \LWR@indentHTML
            alt="#1" \LWR@indentHTML
            style="#5" \LWR@indentHTML
            class="#2" \LWR@orignewline
        }%
    }%
}
```

```
\end{warpHTML}
```

Table 13: Float data structures

For each <type> of float (figure, table, etc.) there exists the following:

counter <type>: A counter called <type>, such as figure, table.

\<type>name: Name. \figurename prints "Figure", etc.

\ext@<type>: File extension. \ext@figure prints "lof", etc.

\fps@<type>: Placement.

\the<type>: Number. \thetable prints the number of the table, etc.

\p@<type>: Parent's number. Prints the number of the [within] figure, etc.

\fnum@<type>: Prints the figure number for the caption.
\<type>name \the<type>, "Figure 123".

\<type>: Starts the float environment. \figure or \begin{figure}

\end<type>: Ends the float environment. \endfigure or \end{figure}

\tf@<ext>: The LaTeX file identifier for the output file.

LWR@have<type>: A boolean remembering whether a \listof was requested for a float of this type.

File with extension lo<f,t,a-z>: An output file containing the commands to build the \listof<type> "table-of-contents" structure.

Cross-referencing names: For cleveref's \cref and related, \crefname and \Crefname assign human-readable names for references to this float type.

74 Floats

Floats are supported, although partially through emulation.

Table 13 shows the data structure associated with each <type> of float.

\@makecaption is redefined to print the float number and caption text, separated by \CaptionSeparator, which works with the babel package to adjust the caption separator according to the language. French, for example, uses an en-dash instead of a colon: "Figure 123 – Caption text".

74.1 Float environment

for HTML output: 9124 \begin{warpHTML}

\LWR@floatbegin {⟨*type*⟩} [⟨*placement*⟩] Begins a \newfloat environment.

```
\NewDocumentCommand{\LWR@floatbegin}{m o}{%
\ifbool{FormatWP}{\newline}{}%
\LWR@stoppars
```

There is a new float, so increment the unique float counter:

```
\addtocounter{LWR@thisautoid}{1}%
\booltrue{LWR@freezethisautoid}%

\begingroup%
```

Settings while inside the environment:

```
\LWR@print@raggedright%
```

Open an HTML `figure` tag. The figure is assigned a `class` equal to its type, and another class according to the float package style, if used. Note that `\csuse` returns an empty string if `\LWR@floatstyle@<type>` is not defined.

```
\LWR@htmltag{%
    figure id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}" % space
    class="#1 \@nameuse{LWR@floatstyle@#1}"%
}%
\ifbool{FormatWP}{%
    \LWR@orignewline%
    \LWR@BlockClassWP{}{}{wp#1}%
}{}%
```

Update the caption type:

```
\renewcommand*{\@captype}{#1}%
\caption@settype{#1}%
```

Mark the float for a word processor conversion:

```
\LWR@startpars%
\ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

=== begin #1 ===

}{}%
```

Look for `\centering`, etc:

```
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
```

For koma-script. The following does not work for tables.

```
\AtBeginDocument{
\@ifpackageloaded{tocbasic}{
\appto\figure@atbegin{%
```

```
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
}{}
}
```

\@float
\@dlbfloat

Support packages which create floats directly.

```
\let\@float\LWR@floatbegin
\let\@dblfloat\LWR@floatbegin
```

\LWR@floatend

Ends a \newfloat environment.

```
\newcommand*{\LWR@floatend}{%
```

If saw a \centering, finish the center environment:

```
\LWR@endfloatalignment%
```

Mark the float end for a word processor conversion:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

=== end ===

}{}%
\LWR@stoppars%
```

Close an HTML figure tag:

```
\ifbool{FormatWP}{\endLWR@BlockClassWP}{}%
\LWR@htmlelementend{figure}%
\endgroup%
\boolfalse{LWR@freezethisautoid}%
\LWR@startpars%
\ifbool{FormatWP}{\newline}{}%
}
```

\end@float
\end@dlbfloat

Support packages which create floats directly.

```
\let\end@float\LWR@floatend
\let\end@dblfloat\LWR@floatend
```

74.2 Float tracking

Ctr LWR@thisautoid

A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
\newcounter{LWR@thisautoid}
```

Ctr `LWR@thisautoidWP` A sequential counter for all word processor conversion s. This is used to convince LibreOffice to form a frame around this element.

```
\newcounter{LWR@thisautoidWP}
```

Bool `LWR@freezethisautoid` Prevents multiple increments of `\LWR@thisautoid` inside a float.

```
\newbool{LWR@freezethisautoid}
\boolfalse{LWR@freezethisautoid}
```

`\LWR@newautoidanchor` Adds a new <autoid> anchor.

```
\newcommand*{\LWR@newautoidanchor}{%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{%
    \ifbool{LWR@freezethisautoid}{}{%
        \addtocounter{LWR@thisautoid}{1}%
        \LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}%
            \LWR@htmltag{/a}%
    }%
}%
}
```

`\@captype` Remembers which float type is in use.

```
\newcommand*{\@captype}{}
```

`\LWR@floatalignmentname` Set to `center`, `flushleft`, or `flushright` if saw `\centering`, `\raggedright`, or `\raggedleft`.

```
\newcommand*{\LWR@floatalignmentname}{}
```

`\LWR@floatalignment` If sees a `\centering`, `\raggedleft`, or `\raggedright`, creates a `center`, `flushright`, or `flushleft` environment.

```
\newcommand*{\LWR@floatalignment}{%
\ifdefstrequal{\LWR@mynexttoken}{\centering}{%
    \center%
    \renewcommand*{\LWR@floatalignmentname}{center}%
}{}%
\ifdefstrequal{\LWR@mynexttoken}{\raggedright}{%
    \flushleft%
    \renewcommand*{\LWR@floatalignmentname}{flushleft}%
}{}%
\ifdefstrequal{\LWR@mynexttoken}{\raggedleft}{%
    \flushright%
    \renewcommand*{\LWR@floatalignmentname}{flushright}%
}{}%
}
```

`\LWR@endfloatalignment` Closes an environment from `\LWR@floatalignment`.

```
\newcommand*{\LWR@endfloatalignment}{%
\ifdefvoid{\LWR@floatalignmentname}{}{\@nameuse{end\LWR@floatalignmentname}}%
\renewcommand*{\LWR@floatalignmentname}{}%
}
```

74.3 Caption inside a float environment

\CaptionSeparator How to separate the float number and the caption text.

```
\AtBeginDocument{\providecommand*{\CaptionSeparator}{:~}}
```

\@makecaption {⟨*name and num*⟩} {⟨*text*⟩}

Prints the float type and number, the caption separator, and the caption text.

```
\AtBeginDocument{\renewcommand{\@makecaption}[2]{%
    \LWR@traceinfo{@makecaption}%
    \LWR@isolate{#1}\CaptionSeparator\LWR@isolate{#2}%
    \LWR@traceinfo{@makecaption: done}%
}%
}
```

74.4 Caption and LOF linking and tracking

When a new HTML file is marked in the LaTeX PDF file, the LaTeX page number at that point is stored in LWR@latestautopage, (and the associated filename is remembered by the special LaTeX labels). This page number is used to generate an autopage HTML <id> in the HTML output at the start of the new HTML file. Meanwhile, there is a float counter used to generate an HTML autoid <id> at the start of the float itself in the HTML file. The autopage and autoid values to use for each float are written to the .lof, etc. files just before each float's entry. These values are used by \l@figure, etc. to create the HTML links in the List of Figures, etc.

Ctr LWR@nextautoid Tracks autoid for floats. Tracks autopage for floats.

Ctr LWR@nextautopage These are updated per float as the .lof, .lot file is read.

```
\newcounter{LWR@nextautoid}
\newcounter{LWR@nextautopage}
```

\LWRsetnextfloat {⟨*autopage*⟩} {⟨*float autoid*⟩}

File *_html.lof This is written to the *_html.lof or *_html.lot file just before each float's usual entry. The autopage and the float's autoid are remembered for \l@figure to use when creating the HTML links.

File *_html.lot

```
\newcommand*{\LWRsetnextfloat}[2]{%
    \setcounter{LWR@nextautopage}{#1}%
    \setcounter{LWR@nextautoid}{#2}%
}
```

Ctr LWR@latestautopage

Updated each time a new HTML file is begun. \LWRsetnextfloat is written with this and the autoid by the modified \addcontentsline just before each float's entry.

```
\newcounter{LWR@latestautopage}
\setcounter{LWR@latestautopage}{1}
```

Env LWR@figcaption

An HTML <figcaption> is not allowed in places where LaTeX does allow a figure caption, such as inside a longtable where the tabular has already started, or inside a center environment. Therefore, a of class figurecaption is used instead.

```
\newenvironment*{LWR@figcaption}
    {
        \ifbool{FormatWP}{%
            \BlockClass[font-style:italic]{figurecaption}
%             \LWR@print@vspace*{\baselineskip}
        }{
            \BlockClass{figurecaption}
        }%
    }
    {\endBlockClass}
```

\LWR@HTML@caption@begin {⟨*type*⟩}

Low-level code to create HTML tags for captions.

The print versions are from the caption package.

```
\newcommand*{\LWR@HTML@caption@begin}[1]
{%
\LWR@traceinfo{LWR@HTML@caption@begin}%
```

Keep par and minipage changes local:

```
\begingroup%
```

No need for a minipage or \parbox inside the caption:

```
\RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{}%
\RenewDocumentCommand{\parbox}{O{t} O{} O{t} m +m}{##5}%
```

Enclose the original caption code inside an HTML tag:

```
\LWR@figcaption%
\LWR@traceinfo{LWR@HTML@caption@begin: about to LWR@origcaption@begin}%
\LWR@print@caption@begin{#1}%
\LWR@traceinfo{LWR@HTML@caption@begin: done}%
}
```

\LWR@HTML@caption@end

Low-level patches to create HTML tags for captions.

```
\newcommand*{\LWR@HTML@caption@end}
{%
```

```
\LWR@traceinfo{LWR@HTML@caption@end}%
\LWR@print@caption@end%
```

Closing tag:

```
\endLWR@figcaption%
\endgroup%
% \leavevmode% avoid bad space factor (0) error
\LWR@traceinfo{LWR@HTML@caption@end: done}%
}
```

\caption@begin
\caption@end

Low-level patches to create HTML tags for captions. These are assigned \AtBeginDocument so that other packages which modify captions will have already been loaded before saving the print-mode version.

```
\AtBeginDocument{
\LWR@formatted{caption@begin}
\LWR@formatted{caption@end}
}
```

\captionlistentry

Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```
\let\LWR@origcaptionlistentry\captionlistentry

\renewcommand*{\captionlistentry}{%
\LWR@ensuredoingapar%
\LWR@origcaptionlistentry%
}

\def\LWR@LTcaptionlistentry{%
\LWR@ensuredoingapar%
\LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
  \bgroup
  \@ifstar{\egroup\LWR@LT@captionlistentry}% gobble *
          {\egroup\LWR@LT@captionlistentry}}%
\def\LWR@LT@captionlistentry#1{%
  \caption@listentry\@firstoftwo[\LTcaptype]{#1}}%
```

\addcontentsline

Patched to write the autopage and autoid before each float's entry. No changes if writing .toc For a theorem, automatically defines \ext@<type> as needed, to mimic and reuse the float mechanism.

f

```
\let\LWR@origaddcontentsline\addcontentsline

\renewcommand*{\addcontentsline}[3]{%
\ifstrequal{#1}{toc}{}{% not TOC

\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {}%
    {\LWR@newautoidanchor}%
```

```
    \ifcsvoid{ext@#2}{\csdef{ext@#2}{#1}}{}%

    \addtocontents{\@nameuse{ext@#2}}{%
        \protect\LWRsetnextfloat%
        {\arabic{LWR@latestautopage}}%
        {\arabic{LWR@thisautoid}}%
    }%
}% not TOC
\LWR@origaddcontentsline{#1}{#2}{#3}%
}
```

Pkg capt-of
Pkg caption

Either package provides `\captionof`, which is later patched at the beginning of the document.

\captionof

Patched to handle paragraph tags.

```
\AtBeginDocument{
\let\LWR@origcaptionof\captionof

\renewcommand*{\captionof}{%
\LWR@stoppars%
\LWR@origcaptionof%
}
}

\end{warpHTML}
```

75 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The `.toc`, `.lof`, and `.lot` files are named by the source code `\jobname`.

In HTML, the printed tables are placed inside a `<div>` of class `toc`, `lof`, or `lot`.

A "sidetoc" is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular LaTeX infrastructure is used for TOC, along with some patches to generate HTML output.

for HTML output:

```
\begin{warpHTML}
```

75.1 Reading and printing the TOC

\LWR@myshorttoc {⟨*toc/lof/lot/sidetoc*⟩}

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the `@` character into a normal letter to allow formatting commands in the section names.

Unlike in regular LaTeX, the file is not reset after being read, since the sideTOC may be referred to again in each HTML page.

```
\newcommand*{\LWR@myshorttoc}[1]{%
\LWR@traceinfo{LWR@myshorttoc: #1}%
\LWR@ensuredoingapar%
```

Only if the file exists:

```
\IfFileExists{\jobname.#1}{%
\LWR@traceinfo{LWR@myshorttoc: loading}%
```

⚠ Many of the commands in the file will have @ characters in them, so @ must be made a regular letter.

```
\begingroup%
\makeatletter%
```

Read in the TOC file:

```
\@input{\jobname.#1}%
\endgroup%
}%
{}%
\LWR@traceinfo{LWR@myshorttoc: done}%
}
```

`\LWR@subtableofcontents` {⟨*toc/lof/lot*⟩} {⟨*sectionstarname*⟩}

Places a TOC/LOF/LOT at the current position.

```
\NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
\@ifundefined{chapter}
{\LWR@closeprevious{section}}
{\LWR@closeprevious{chapter}}
```

Prints any pending footnotes so that they appear above the potentially large TOC:

```
\LWR@printpendingfootnotes
```

Place the list into its own chapter (if defined) or section:

```
\@ifundefined{chapter}{\section*{#2}}{\chapter*{#2}}
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
\LWR@htmlelementclass{nav}{#1}
```

Create the actual list:

```
\LWR@myshorttoc{#1}
```

Close the nav:

```
\LWR@htmlelementclassend{nav}{#1}
}
```

\@starttoc {⟨*ext*⟩}

Patch \@starttoc to encapsulate the TOC inside HTML tags:

```
\let\LWR@orig@starttoc\@starttoc

\renewcommand{\@starttoc}[1]{
\LWR@htmlelementclass{nav}{#1}
\LWR@orig@starttoc{#1}
\LWR@htmlelementclassend{nav}{#1}
}
```

Bool LWR@copiedsidetoc Used to only copy the TOC file to the sidetoc a single time.

(listings and perhaps other packages would re-use \tableofcontents for their own purposes, causing the sidetoc to be copied more than once, and thus end up empty.)

```
\newbool{LWR@copiedsidetoc}
\boolfalse{LWR@copiedsidetoc}
```

\tableofcontents Patch \tableofcontents, etc. to print footnotes first. newfloat uses \listoffigures for all future float types.

```
\AtBeginDocument{
\let\LWR@origtableofcontents\tableofcontents

\renewcommand*{\tableofcontents}{%
```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkTOC}}{

=== table of contents ===

}
{
```

Copy the .toc file to .sidetoc for printing the sideTOC. The original .toc file is renewed when \tableofcontents is finished.

```
    \ifbool{LWR@copiedsidetoc}{}{%
        \LWR@copyfile{\jobname.toc}{\jobname.sidetoc}%
        \booltrue{LWR@copiedsidetoc}%
    }%
```

```
    \LWR@printpendingfootnotes
    \LWR@origtableofcontents
}
}% \tableofcontents
}% AtBeginDocument
```

\listoffigures

```
\let\LWR@origlistoffigures\listoffigures

\renewcommand*{\listoffigures}{
\ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{

=== list of figures ===

}
{
    \LWR@printpendingfootnotes
    \LWR@origlistoffigures
}
}
```

\listoftables

```
\let\LWR@origlistoftables\listoftables

\renewcommand*{\listoftables}{
\ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{

=== list of tables ===

}
{
    \LWR@printpendingfootnotes
    \LWR@origlistoftables
}
}
```

75.2 High-level TOC commands

\listof {⟨*type*⟩} {⟨*title*⟩}

Emulate the \listof command from the float package (section 230). Used to create lists of custom float types. Also used to redefine the standard LaTeX \listoffigures and \listoftables commands.

```
\NewDocumentCommand{\listof}{m +m}{%
\@ifundefined{l@#1}{%
    \csdef{l@#1}##1##2{\hypertocfloat{1}{#1}{\@nameuse{ext@#1}}{##1}{##2}}%
}{}%
\LWR@subtableofcontents{\@nameuse{ext@#1}}{#2}
\expandafter\newwrite\csname tf@\csname ext@#1\endcsname\endcsname
```

```
\immediate\openout \csname tf@\csname ext@#1\endcsname\endcsname
    \jobname.\@nameuse{ext@#1}\relax
}
```

75.3 Side TOC

The "side TOC" is a table-of-contents positioned to the side.

It may be renamed by redefining `\sidetocname`, and may contain paragraphs.

CSS may be used to format the sideTOC:

CSS related to sideTOC:

`div.sidetoccontainer`: The entire sideTOC.
`div.sidetoctitle`: The title.
`div.sidetoccontents`: The table of contents.

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Ctr `SideTOCDepth` Controls how deep the side-TOC gets. Use a standard LaTeX section level similar to `tocdepth`. Warn if parts of the website may be inaccessible.

```
\newcounter{SideTOCDepth}
\setcounter{SideTOCDepth}{1}

\AtBeginDocument{%
    \ifnumcomp{\value{SideTOCDepth}}{<}{\value{FileDepth}}{
        \PackageWarningNoLine{lwarp}
        {%
            SideTOCDepth is less than FileDepth,\MessageBreak
            so some website pages may be inaccessible%
        }
    }{}
}
```

`\sidetocname` Holds the default name for the sideTOC.

```
\newcommand{\sidetocname}{Contents}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@sidetoc` Creates the actual side-TOC.

```
\newcommand*{\LWR@sidetoc}{
\LWR@forcenewpage
\LWR@stoppars
```

The entire sideTOC is placed into a nav of class sidetoc.

```
\LWR@htmlelementclass{div}{sidetoccontainer}
\LWR@htmlelementclass{nav}{sidetoc}

\setcounter{tocdepth}{\value{SideTOCDepth}}

```

The title is placed into a of class sidetoctitle, and may contain paragraphs.

```
\begin{BlockClass}{sidetoctitle}
\ifcsvoid{thetitle}{}{\InlineClass{sidetocthetitle}{\thetitle}\par}
\sidetocname
\end{BlockClass}
```

The table of contents is placed into a of class sidetoccontents.

```
\begin{BlockClass}{sidetoccontents}
\LinkHome

\LWR@myshorttoc{sidetoc}
\end{BlockClass}
\LWR@htmlelementclassend{nav}{sidetoc}
\LWR@htmlelementclassend{div}{sidetoccontainer}
}
```

75.4 Low-level TOC line formatting

`\numberline` {⟨*number*⟩}

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```
\newcommand*{\LWR@numberline}[1]{%
\LWR@sectionnumber{#1}\quad%
}

\LetLtxMacro\numberline\LWR@numberline
```

`\LWR@maybetocdata` Replaced by tocdata. Adds author name.

```
\newcommand*{\LWR@maybetocdata}{}
```

`\hypertoc` {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: name*⟩} {⟨*4: page*⟩}

Called by \l@section, etc. to create a hyperlink to a section.

The autopage label is always created just after the section opens.

#1 is depth

#2 is section, subsection, etc.

#3 the text of the caption

#4 page number

```
\NewDocumentCommand{\hypertoc}{m m +m m}{%
\LWR@traceinfo{hypertoc !#1!#2!#3!#4!}%
```

Respond to tocdepth:

```
\ifthenelse{\cnttest{#1}{<=}{\value{tocdepth}}}%
    {%
        \LWR@startpars%
```

Create an HTML link to <filename>#autosec-(page), with the name, of the given HTML class.

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
        \LWR@subhyperrefclass{%
            \LWR@htmlrefsectionfilename{\BaseJobname-autopage-#4}%
                \LWR@origpound\LWR@print@mbox{autosec-#4}%
        }{#3}{toc#2}%

        \LWR@maybetocdata%

        \LWR@stoppars%
    }%
    {}%
\LWR@traceinfo{hypertoc done}%
}
```

Ctr lofdepth TOC depth for figures.

```
\@ifclassloaded{memoir}{}{
\newcounter{lofdepth}
\setcounter{lofdepth}{1}
}
```

Ctr lotdepth TOC depth for tables.

```
\@ifclassloaded{memoir}{}{
\newcounter{lotdepth}
\setcounter{lotdepth}{1}
}
```

\hypertocfloat {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: ext of parent*⟩} {⟨*4: caption*⟩} {⟨*5: page*⟩}

#1 is depth

#2 is `figure`, `table`, etc.

#3 is `lof`, `lot`, of the parent.

#4 the text of the caption

#5 page number

```
\newcommand{\hypertocfloat}[5]{%
\LWR@startpars
```

If some float-creation package has not yet defined the float type's `lofdepth` counter, etc, define it here:

```
\@ifundefined{c@#3depth}{%
\newcounter{#3depth}%
\setcounter{#3depth}{1}%
}{}%
```

Respond to `lofdepth`, etc.:

```
\LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%
\ifthenelse{\cnttest{#1}{<=}{\arabic{#3depth}}}%
    {%
        \LWR@startpars%
```

Create an HTML link to filename#autoid-(float number), with text of the caption, of the given HTML class.

`\BaseJobname` is added to the label in case xr or xr-hyper are used.

```
        \LWR@subhyperrefclass{%
        \LWR@htmlrefsectionfilename{%
            \BaseJobname-autopage-\arabic{LWR@nextautopage}%
        }%
        \LWR@origpound\LWR@print@mbox{autoid-\arabic{LWR@nextautoid}}}%
        {#4}{toc#2}%

        \LWR@maybetocdata%

        \LWR@stoppars%
    }%
    {}%
}
```

Automatically called by `\contentsline`:

`\l@book` {⟨*name*⟩} {⟨*page*⟩}

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\book`.

```
\DeclareDocumentCommand{\l@book}{m m}{\hypertoc{-2}{book}{#1}{#2}}
```

`\l@part` {⟨*name*⟩} {⟨*page*⟩}

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\part`.

```
\DeclareDocumentCommand{\l@part}{m m}{\hypertoc{-1}{part}{#1}{#2}}
```

`\l@chapter` {⟨*name*⟩} {⟨*page*⟩}

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\chapter`.

```
\@ifundefined{chapter}
{}
{
\DeclareDocumentCommand{\l@chapter}{m m}
    {\hypertoc{0}{chapter}{#1}{#2}}
}
```

`\l@section` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
```

`\l@subsection` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
```

`\l@subsubsection` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsubsection}[2]{\hypertoc{3}{subsubsection}{#1}{#2}}
```

`\l@paragraph` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}
```

`\l@subparagraph` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}
```

`\l@figure` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}
```

`\l@table` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}
```

```
\end{warpHTML}
```

76 Index and glossary

See:
http://tex.stackexchange.com/questions/187038/how-to-mention-section-number-in-index-created-by-imakeidx

Index links are tracked by the counter LWR@autoindex. This counter is used to create a label for each index entry, and a reference to this label for each entry in the index listing. This method allows each index entry to link directly to its exact position in the document.

for HTML output:

```
\begin{warpHTML}

\newcounter{LWR@autoindex}
\setcounter{LWR@autoindex}{0}

\newcounter{LWR@autoglossary}
\setcounter{LWR@autoglossary}{0}
```

Env theindex

```
\@ifundefined{chapter}
{\newcommand*{\LWR@indexsection}[1]{\section*{#1}}}
{\newcommand*{\LWR@indexsection}[1]{\chapter*{#1}}}

\AtBeginDocument{
\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

\LWR@indexitem [⟨*index key*⟩] The optional argument is added to support repeatindex.

```
\newcommand{\LWR@indexitem}[1][\@empty]{

\InlineClass{indexitem}{\LWR@htmlcomment{}}#1%
}
```

\LWR@indexsubitem

```
\newcommand{\LWR@indexsubitem}{

\InlineClass{indexsubitem}{\LWR@htmlcomment{}}
}
```

\LWR@indexsubsubitem

```
\newcommand{\LWR@indexsubsubitem}{
\InlineClass{indexsubsubitem}{\LWR@htmlcomment{}}
}
```

`\@wrindex` {⟨*term*⟩} Redefined to write the `LWR@autoindex` counter instead of page.

```
\def\LWR@wrindex#1{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
\protected@write\@indexfile{}%
{\string\indexentry{#1}{\arabic{LWR@autoindex}}}%
\endgroup
\@esphack}

\AtBeginDocument{
\let\@wrindex\LWR@wrindex
}
```

`\@wrglossary` {⟨*term*⟩} Redefined to write the `LWR@latestautopage` counter instead of page.

```
\def\@wrglossary#1{%
\addtocounter{LWR@autoglossary}{1}%
\LWR@new@label{LWRglossary-\theLWR@autoglossary}%
\protected@write\@glossaryfile{}%
{\string\glossaryentry{#1}{\theLWR@autoglossary}}%
\endgroup
\@esphack}
```

`\LWR@indexnameref` {⟨*LWR@autoindex*⟩}

Creates a hyperlink based on the given entry's autoindex.

```
\newcommand*{\LWR@indexnameref}[1]{\nameref{LWRindex-#1}}
```

`\LWR@doindexentry` {⟨*LWR@autoindex, or macros.*⟩}

Creates a hyperlink, or handles `\see`, `\textbf`, etc.

```
\newrobustcmd{\LWR@doindexentry}[1]{%
\IfInteger{#1}%
    {\LWR@indexnameref{#1}}%
    {#1}%
}
```

`\LWR@hyperindexrefnullified` Handles macros commonly seen inside an `\index` entry. Each macro is redefined to create and format a link to its entry.

⚠ index formatting To handle additional macros:

```
\appto\LWR@hyperindexrefnullified{. . . }
```

```
\newcommand{\LWR@hyperindexrefnullified}{%
\renewrobustcmd{\emph}[1]{\LWR@HTML@emph{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textbf}[1]{\LWR@HTML@textbf{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\texteb}[1]{\LWR@HTML@texteb{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textlg}[1]{\LWR@HTML@textlg{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textrm}[1]{\LWR@HTML@textrm{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsf}[1]{\LWR@HTML@textsf{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\texttt}[1]{\LWR@HTML@texttt{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textup}[1]{\LWR@HTML@textup{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsc}[1]{\LWR@HTML@textsc{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textulc}[1]{\LWR@HTML@textulc{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsi}[1]{\LWR@HTML@textsi{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textit}[1]{\LWR@HTML@textit{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsl}[1]{\LWR@HTML@textsl{\LWR@doindexentry{##1}}}%
}
```

\hyperindexref {⟨*LWR@autoindex*⟩}

\hyperindexref{LWR@autoindex} is inserted into `*.ind` by the makeindex style file `lwarp.ist` or the xindy style file `lwarp.xdy`.

```
\newcommand{\hyperindexref}[1]{%
```

In long index lines with numerous entries, *makeindex* can insert a newline before the page number, resulting in an extra space before the first digit. If the first character is a space, remove it first.

```
\def\LWR@tempone{#1}%
\IfBeginWith{\LWR@tempone}{ }{%
    \StrGobbleLeft{\LWR@tempone}{1}[\LWR@tempone]%
}{}%
```

If a numeric entry, create a link. If not numeric, such as \see, use the entry as-is. \emph, \textit, etc. have been redefined above to create and format the entry.

```
\IfInteger{\LWR@tempone}%
    {\LWR@indexnameref{\LWR@tempone}}%
    {%
        \begingroup%
        \LWR@hyperindexrefnullified
        #1%
        \endgroup%
    }%
}
```

```
\end{warpHTML}
```

for PRINT output: A null command for print mode, in case hyperref was not used:

```
\begin{warpprint}
\newcommand{\hyperindexref}[1]{#1}
\end{warpprint}
```

for HTML & PRINT: For the glossaries package, try to prevent an error where \glo@name was not found:

```
\begin{warpall}
\providecommand{\glo@name}{}
\end{warpall}
```

77 Bibliography presentation

for HTML output:
```
\begin{warpHTML}
```

\bibliography {⟨*filenames*⟩}

Modified to use the base jobname instead of the _html jobname.

```
\def\bibliography#1{%
    \if@filesw
    \immediate\write\@auxout{\string\bibdata{#1}}%
    \fi
%     \@input@{\jobname.bbl}% original
    \begingroup%
    \@input@{\BaseJobname.bbl}% lwarp
    \endgroup%
}
```

\@biblabel {⟨*text-refnumber*⟩}

```
\renewcommand{\@biblabel}[1]{[#1]\quad}
```

Env thebibliography To emphasize document titles in the bibliography, the following redefines \em inside thebibliography to gather everything until the next closing brace, then display these tokens with \textit.

Adapted from embracedef.sty, *which is by* Takayuki YATO*:*
https://gist.github.com/zr-tex8r/b72555e3e7ad2f0a37f1

```
\AtBeginDocument{
\AtBeginEnvironment{thebibliography}{
\providecommand*{\LWR@newem}[1]{\textit{#1}}

\renewrobustcmd{\em}{%
  \begingroup
    \gdef\LWR@em@after{\LWR@em@finish\LWR@newem}%
    \afterassignment\LWR@em@after
    \toks@\bgroup
}

\def\LWR@em@finish#1{%
    \xdef\LWR@em@after{\noexpand#1{\the\toks@}}%
  \endgroup
  \LWR@em@after\egroup
```

```
}
}% \AtBeginEnvironment{thebibliography}
}% \AtBeginDocument

\end{warpHTML}
```

78 Restoring original formatting

\LWR@restoreorigformatting

Used to temporarily restore the print-mode meaning of a number of formatting, graphics, and symbols-related macros while generating SVG math or a `latexmage`.

Must be used inside a group.

Sets `\LWR@formatting` to `print` until the end of the group.

A number of packages will `\appto` additional actions to this macro.

Various packages add to this macro using `\appto`.

for HTML output:

```
\begin{warpHTML}

\newcommand*{\LWR@restoreorigformatting}{%
\LWR@traceinfo{LWR@restoreorigformatting}%
```

Numerous macros change their print/HTML meaning depending on `\LWR@formatting`:

```
\renewcommand*{\LWR@formatting}{print}%
\linespread{1}%

\let\par\LWR@origpar%

\LWR@select@print@hspace%


\LetLtxMacro\hfil\LWR@orighfil%
\let\hss\LWR@orighss%
\let\llap\LWR@origllap%
\let\rlap\LWR@origrlap%
\let\hfilneg\LWR@orighfilneg%

\let\,\LWR@origcomma% disable HTML short unbreakable space
\let\thinspace\LWR@origthinspace% disable HTML short unbreakable space
\let\negthinspace\LWR@orignegthinspace% disable HTML negative short unbreakable space
\let\textellipsis\LWR@origtextellipsis%
\let\textless\LWR@origtextless%
\let\textgreater\LWR@origtextgreater%


\let\&\LWR@origampersand%


\LetLtxMacro\em\LWR@origem%
```

```
\LetLtxMacro\normalfont\LWR@orignormalfont%
\let\sp\LWR@origsp%
\let\sb\LWR@origsb%
\LetLtxMacro\textsuperscript\LWR@origtextsuperscript%
\LetLtxMacro\@textsuperscript\LWR@orig@textsuperscript%
\LetLtxMacro\textsubscript\LWR@origtextsubscript%
\LetLtxMacro\@textsubscript\LWR@orig@textsubscript%
\LetLtxMacro\underline\LWR@origunderline%
\let~\LWR@origtilde%
\let\enskip\LWR@origenskip%
\let\quad\LWR@origquad%
\let\qquad\LWR@origqquad%
```

`\endtabular` must be restored to its original, instead of relying on lwarp's `\LWR@formatted` mechanism:

```
\LetLtxMacro\endtabular\LWR@origendtabular%
\csletcs{endtabular*}{LWR@origendtabular*}%

\LetLtxMacro\noalign\LWR@orignoalign%
\LetLtxMacro\hline\LWR@orighline%

\let\newline\LWR@orignewline%
\LetLtxMacro\includegraphics\LWR@origincludegraphics%


\LetLtxMacro\@ensuredmath\LWR@origensuredmath%
%
\LWR@restoreorigaccents%
\LWR@restoreoriglists%
%
\LWR@FBcancel%
}

\end{warpHTML}
```

79 Math

79.1 Limitations

79.1.1 Math in section names

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

79.1.2 Rendering tradeoffs

Math rendering

Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.

SVG files

Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline

The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files

Others LaTeX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML

Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 10 regarding EPUB output with MATHJAX.

79.1.3 SVG option

SVG math option

For SVG math, math is rendered as usual by LaTeX into the initial PDF file using the current font[18], then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LaTeX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the LaTeX code which generated the math, allowing copy/paste of the LaTeX math expression into other documents.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

SVG math copy/paste

For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the LaTeX code for the math expression. For $\mathcal{AMS}$ environments with multiple numbers in the same environment, only the first and

[18] See section 519 regarding fonts and fractions.

last is copy/pasted, as a range. No tags are listed inside a starred $\mathcal{AMS}$ environment, although the \tag macro will still appear inside the LaTeX math expression.

⚠ SVG math in TeX boxes

SVG math does not work inside TeX boxes, since a \newpage is required before and after each image.

79.1.4 MathJax option

MathJax math option

Prog MathJax

The popular MathJax alternative (mathjax.org) may be used to display math.

When MathJax is enabled, math is rendered twice:

1. As regular LaTeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LaTeX, and
2. As detokenized printed LaTeX commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current LaTeX values, and the MathJax cross-referencing system is ignored in favor of the LaTeX internal system, seamlessly integrating with the rest of the LaTeX code.

79.1.5 Customizing MathJax

MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

79.1.6 MathJax limitations

MathJax limitations

Prog MathJax

Limitations when using MathJax include:

subequations

- MathJax itself does not support subequations. This may be improved by parsing the LaTeX math expression to manually insert tags, but this has not yet been done.

footnotes in math

- Footnotes inside equations are not yet supported while using MathJax.

lateximage

- Math appearing inside a lateximage, and therefore also inside a Ti*k*z or `picture` environment, is rendered as SVG math even if MathJax is used in the rest of the document.

siunitx

⚠ siunitx inside an equation

- Usage of siunitx inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

  https://github.com/burnpanck/MathJax-siunitx

  Also see section 8.7.11.

tabbing

- A `tabbing` environment is emulated using an HTML <pre>.While MathJax is enabled inside `tabbing`, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

⚠ other macros and packages

- Other math-related macros and packages are not supported by MathJax, including `\ensuremath` and bigdelim, along with occasionally-used macros such as `\relax`. lwarp emulates footnotes, units, and nicefrac for MathJax.

79.1.7 Catcode changes

preamble macros with math

The math shift character $ is not set for HTML output until after the preamble. Macros defined in the preamble which contain $ must be enclosed between `\StartDefiningMath` and `\StopDefiningMath` to temporarily change to the HTML meaning of $:

```
\StartDefiningMath
\newcommand{. . . }
\StopDefiningMath
```

As an alternative, use `\(` and `\)` instead of $, in which case `\StartDefiningMath` and `\StopDefiningMath` are not necessary.

If a package defines macros using $, it may be nessary to use `\StartDefiningMath` and `\StopDefiningMath` before and after loading the package.

79.1.8 Complicated inline math objects

`\inlinemathnormal` `\inlinemathother`

changing contents

complicated `alt` tag

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as `$x+1$`, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an `alt` tag. The macro `\inlinemathother` may be used before a dynamic math expression, and `\inlinemathnormal` after. Doing so tells lwarp to use an unhashed SVG math image, even if MathJax is in use. See section 44.

79.1.9 Complicated display math objects

`\displaymathnormal`

By default, or when selecting `\displaymathnormal`, MathJax math display environ-

ments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the `alt` tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

`\displaymathother`
MathJax unsupported complicated `alt` tag

When selecting `\displaymathother`, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an HTML `alt` tag. In this mode, MathJax is turned off, math display environments become SVG images, even if MathJax is selected, and the HTML `alt` tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

79.2 HTML `alt` tag names

Redefinable names for the HTML `alt` tags, for translation according to the reader's native language.

for HTML & PRINT:

```
9657 \begin{warpall}
```

`\AltTextOpen`
Default: `(`

The opening part of HTML `alt` tag for an image. The default is a left parenthesis.

```
9658 \newcommand*{\AltTextOpen}{(}
```

`\AltTextClose`
Default: `)`

The closing part of HTML `alt` tag for an image. The default is a right parenthesis.

```
9659 \newcommand*{\AltTextClose}{)}
```

`\ImageAltText`
Default: `image`

The HTML `alt` tag for an image.

```
9660 \newcommand*{\ImageAltText}{image}
```

`\MathImageAltText`
Default: `"math image"`

The HTML `alt` tag for an SVG math image.

```
9661 \newcommand*{\MathImageAltText}{math image}
```

`\LWR@ThisAltText`

The HTML `alt` tag for the next image. Cleared after use, and also after each `lateximage`, `\LWR@subsingledollar`, and each use of MathJax.

```
9662 \newcommand*{\LWR@ThisAltText}{}
```

`\ThisAltText` {⟨*text*⟩}

Assigns the HTML `alt` tag for the next image generated by lwarp, such as a `lateximage`, `picture`, or SVG math.

```
\newcommand*{\ThisAltText}[1]{%
    \renewcommand{\LWR@ThisAltText}{#1}%
}
```

\PackageDiagramAltText — Appended to the lateximage HTML alt tag for the images generated by many packages.
Default: "diagram"

```
\newcommand*{\PackageDiagramAltText}{diagram}
```

```
\end{warpall}
```

79.3 Inline and display math

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@externalfilecnt — Counter for the external files which are generated and then referenced from the HTML:

```
\newcounter{LWR@externalfilecnt}
```

Bool LWR@indisplaymathimage — True if processing display math for SVG output. Inside a lateximage, display math is only set to print-mode output if LWR@indisplaymathimage is false. Used to avoid nullifying display math before it has been completed.

```
\newbool{LWR@indisplaymathimage}
```

Bool LWR@xfakebold — True if xfakebold \setBold is in use.

```
\newbool{LWR@xfakebold}
\boolfalse{LWR@xfakebold}
```

\LWR@orig@setBold — Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@orig@setBold}{}
```

\LWR@orig@unsetBold — Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@orig@unsetBold}{}
```

\LWR@applyxfakebold — Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@applyxfakebold}{}
```

\LWR@setcurrentfont — Sets the actual LaTeX font to that which was selected for HTML output. Ex: In HTML mode, \bfseries sets \LWR@f@series to "bf". This sets the PDF output here for use inside a lateximage.

```
\newcommand*{\LWR@setcurrentfont}{%
    \LWR@traceinfo{Using font family \LWR@f@family}%
```

```
    \@nameuse{LWR@print@\LWR@f@family family}%
    \LWR@traceinfo{Using font series \LWR@f@series}%
    \@nameuse{LWR@print@\LWR@f@series series}%
    \LWR@traceinfo{Using font shape \LWR@f@shape}%
    \@nameuse{LWR@print@\LWR@f@shape shape}%
    \LWR@traceinfo{Using font caps shape \LWR@f@shapecaps}%
    \@nameuse{LWR@print@\LWR@f@shapecaps shape}%
}
```

\$ Plain dollar signs appearing in the HTML output may be interpreted by MathJax to be math shifts. For a plain text dollar \$, use an HTML entity to avoid it being interpreted by MathJax, unless are inside a lateximage, in which case it will not be seen by MathJax.

```
\let\LWR@origtextdollar\$

\renewcommand*{\$}{%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{\LWR@origtextdollar}%
{\HTMLunicode{00024}}%
}
```

File lwarp_baseline_marker.png
File lwarp_baseline_marker.eps

A marker to be used to help *pdfcrop* identify the inline math baseline and width. If either graphicx or graphics is loaded, this marker is placed at the lower left and lower right corners of the inline math. *pdfcrop* is then able to identify the width of the image, and also the height of an image such as a horizontal dash which does not otherwise touch the baseline.

A marker with alpha or opacity of 0% is not registered by *pdfcrop*, so the marker is a small square block of 1% alpha, which seems to work while still being effectively invisible in the final SVG image.

If graphicx is loaded, this marker is sized as a tiny 1 sp square. If graphics is loaded, this marker is used at its default size of around .25 pt. If neither graphics package is loaded, the marker is replaced by a 10 sp horizontal space, and there is no assistance for determining baseline or width of the inline math image. The best results are obtained when using graphicx.

\LWR@addbaselinemarker Places a small marker in an SVG inline image. If graphics or graphicx are loaded, the marker is a mostly transparent image. If neither is loaded, no marker is used.

```
\AtBeginDocument{

\ifpdf
    \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
\else
    \ifXeTeX
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
    \else
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.eps}
    \fi
\fi

```

```
\IfFileExists{\LWR@baselinename}%
{
    \@ifpackageloaded{graphicx}{
        \newcommand*{\LWR@addbaselinemarker}{%
            \LWR@origincludegraphics{\LWR@baselinename}%
        }
    }{
        \@ifpackageloaded{graphics}{
            \newcommand*{\LWR@addbaselinemarker}{%
                \LWR@origincludegraphics{\LWR@baselinename}%
            }
        }{
            \PackageWarningNoLine{lwarp}{Load graphicx or graphics
                for improved\MessageBreak
                SVG math baselines%
            }
            \newcommand*{\LWR@addbaselinemarker}{}
        }
    }
}{% lwarp_baseline_marker.png or .eps is not present
    \PackageWarningNoLine{lwarp}{%
        File \LWR@baselinename\space is not installed\MessageBreak
        alongside the lwarp-*.sty files,\MessageBreak
        so SVG math baselines may not be accurate}
    \newcommand*{\LWR@addbaselinemarker}{}
}

}% AtBeginDocument
```

\LWR@subsingledollar * {⟨*2: alt text*⟩} {⟨*3: add'l hashing*⟩} {⟨*4: math expression*⟩}

For inline math. Uses MathJax, or for SVG math the image is measured and ajusted to the baseline of the HTML output, and placed inside a `latexmage`.

image filename hashing

If starred, a hashed filename is used.If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

```
\newlength{\LWR@singledollarwidth}
\newlength{\LWR@singledollarheight}
\newlength{\LWR@singledollardepth}

\newsavebox{\LWR@singledollarbox}
```

```
\NewDocumentCommand{\LWR@subsingledollar}{s m m m}{%
\LWR@traceinfo{LWR@subsingledollar}%

\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{%
\LWR@traceinfo{LWR@subsingledollar: already in a lateximage}%
    #4% contents
}%
{% not in a lateximage
\begingroup%
```

Support for xfakebold:

```
\LWR@applyxfakebold%
```

MathJax cannot parse the often complicated TEX expressions which appear in the various uses of `\ensuredmath`. `\ensuremath` forces the `alt` tag to "`(math image)`", as translated according to `\MathImageAltText`. If this is the case, force the use of a `lateximage` even if MathJax. Likewise for siunitx if `parse-numbers=false`.

If MathJax, or if formatting math for a word processor, and not `\ensuredmath`, and not a dynamic math expression, print the math expression:

```
\ifboolexpr{%
    (
        bool{mathjax} or
        ( bool{FormatWP} and bool{WPMarkMath} )
    ) and
    ( not test {
            \ifstrequal {#2}
              {\AltTextOpen\MathImageAltText\AltTextClose} % from \ensuredmath
        }
    ) and
    ( not bool{LWR@dynamicmath} )
}%
```

For MATHJAX, print the math between `\(` and `\)`:

```
{%
    \LWR@traceinfo{LWR@subsingledollar: Mathjax}%
    {\textbackslash(\LWR@HTMLsanitize{#4}\textbackslash)}%
}% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the LATEX code, and a CSS style to control the baseline adjustment.

```
{% not mathjax
\LWR@traceinfo{LWR@subsingledollar: NOT mathjax, or is ensuremath, or is dynamic}%
```

Measure the depth, width, and height of the math image:

```
    \begingroup%
```

Temporarily disable formatting while measuring the image parameters:

```
    \LWR@restoreorigformatting%
    \RenewDocumentEnvironment{lateximage}{s o s o o}{}{}% inside group
    \LWR@print@normalsize%
```

Temporarily set font for the HTML PDF output:

```
    \LWR@setcurrentfont%
```

`lateximagedepth` must be nested to avoid generating paragraph tags. $\mathcal{AMS}$ math modifies the `\text` macro such that `\addtocounter` does not always occur as expected. Lower-level code is used instead.

```
    \global\advance\c@LWR@lateximagedepth 1\relax%
```

Typeset and save the contents, depending on how they were generated:

SVG math: `\LWR@origensuredmath` is part of argument #4.

SVG math `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

SVG dynamic math: `\LWR@origensuredmath` is part of argument #4.

Mathjax: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`. This case is handled above.

Mathjax `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

Mathjax dynamic math: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`, so `\LWR@origensuredmath` is added below.

`\ifmmode`: Included "just in case".

```
    \ifmmode%
        \global\sbox{\LWR@singledollarbox}{#4}%
    \else%
        \ifbool{LWR@dynamicmath}{%
            \ifbool{mathjax}{%
                \global\sbox{\LWR@singledollarbox}{\LWR@origensuredmath{#4}}%
            }{%
                \global\sbox{\LWR@singledollarbox}{#4}%
            }%
        }{%
            \global\sbox{\LWR@singledollarbox}{#4}%
        }%
    \fi%
```

Add a small and almost transparent marker at the depth of the image.

A math minus sign has the same depth as a plus, even though it does not draw anything below the baseline. This means that *pdfcrop* would crop the image without depth. The marker below the baseline is seen by *pdfcrop* and preserves the depth.

```
    \global\sbox{\LWR@singledollarbox}{%
        \usebox{\LWR@singledollarbox}%
        \raisebox{-\dp\LWR@singledollarbox}{%
            \LWR@addbaselinemarker%
        }%
    }%
```

More low-level code to undo the counter change.

```
    \global\advance\c@LWR@lateximagedepth -1\relax% Due to AmS \text macro.
```

Measure the depth:

```
    \setlength{\LWR@singledollardepth}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
```

Make the length a global change:

```
    \global\LWR@singledollardepth=\LWR@singledollardepth%
```

Likewise for width:

```
    \setlength{\LWR@singledollarwidth}{%
        \LateximageFontScale\wd\LWR@singledollarbox%
    }%
    \global\LWR@singledollarwidth=\LWR@singledollarwidth%
```

Likewise for total height:

```
    \setlength{\LWR@singledollarheight}{%
        \LateximageFontScale\ht\LWR@singledollarbox%
    }%
    \addtolength{\LWR@singledollarheight}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
    \global\LWR@singledollarheight=\LWR@singledollarheight%

    \endgroup%
```

Set a style for the the height or width. The `em` unit is used so that the math scales according to the user's selected font size.

Start with the greater of the width or the height, biased towards the width:

```
    \ifdimgreater{\LWR@singledollarwidth}{.7\LWR@singledollarheight}{%
        \def\LWR@singledollarstyle{%
            width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
        }%
    }{%
        \def\LWR@singledollarstyle{%
            height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
        }%
    }%
```

If a very narrow width, use the height.

```
    \ifdimless{\LWR@singledollarwidth}{.2em}%
    {%
        \def\LWR@singledollarstyle{%
            height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
        }%
    }%
    {}%
```

If very wide and short, use the width:

```
    \ifdimless{\LWR@singledollarheight}{.2em}%
    {%
        \def\LWR@singledollarstyle{%
            width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
        }%
    }%
    {}%
```

If there is significant text depth, add the depth to the style.

```
    \ifdimgreater{\LWR@singledollardepth}{0.05ex}{%
        \def\LWR@singledollardepthstyle{%
            \ ; % extra space
            \LWR@print@mbox{%
            vertical-align:-\LWR@convertto{em}{\the\LWR@singledollardepth} em%
            } % extra space
        }%
    }{%
        \def\LWR@singledollardepthstyle{}%
    }%
```

Create the `latexmage` using the alternate tag and the computed size and depth. The star causes `latexmage` to use an MD5 hash as the filename. When hashing, also include the current font and color in the hash.

```
    \ifbool{LWR@dynamicmath}{%
        \LWR@traceinfo{subsingledollar: dynamic}%
        \begin{lateximage}% no hashing
            [\MathImageAltText]% alt tag
            []% no add'l hashing
            [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
    }{%
        \LWR@traceinfo{subsingledollar: static}%
        \IfValueTF{#1}{%
            \LWR@findcurrenttextcolor% sets \LWR@tempcolor
```

Support for xfakebold:

```
            \ifbool{LWR@xfakebold}%
                {\def\LWR@tempone{Y}}%
                {\def\LWR@tempone{N}}%
```

```
            \begin{lateximage}*% use hashing
                [#2]% alt
                *% do not add open/closing braces
                [% addl' hashing
                    #3%
                    FM\LWR@f@family%
                    SR\LWR@f@series%
                    SH\LWR@f@shape%
                    SHC\LWR@f@shapecaps%
                    CL\LWR@tempcolor%
                    FB\LWR@tempone% xfakebold
                ]%
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
        }{%
            \begin{lateximage}% no hashing
                [#2]% alt
                []% no add'l hashing
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
        }%
    }%
```

Place small and almost transparent markers on the baseline at the left and right edges of the image. These markers are seen by *pdfcrop*, and force vertically-centered objects such as a dash to be raised off the baseline in the cropped image, and also force the total width and left / right margins to be correct. (Except that in some fonts a character may exceed the bounding box, and thus may appear wider than expected when converted to an image.)

```
    \LWR@addbaselinemarker%
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

Typeset the contents:

```
    \usebox{\LWR@singledollarbox}%
```

The closing baseline marker:

```
    \LWR@addbaselinemarker%

    \end{lateximage}%
%
}% not mathjax
\endgroup%
}% not in a lateximage
```

Clear the single-use `alt` text:

```
\gdef\LWR@ThisAltText{}%
\LWR@traceinfo{LWR@subsingledollar: done}%
}
```

```
\LetLtxMacro\LWR@origdollar$
\LetLtxMacro\LWR@secondorigdollar$% balance for editor syntax highlighting

\LetLtxMacro\LWR@origopenparen\(
\LetLtxMacro\LWR@origcloseparen\)
\LetLtxMacro\LWR@origopenbracket\[
\LetLtxMacro\LWR@origclosebracket\]
```

$ $$ Redefine the dollar sign to place math inside a `lateximage`, or use MathJax:

```
\begingroup
\catcode`\$=\active%
\protected\gdef${\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

Used by chemformula to escape single-dollar math:

```
\protected\gdef\LWR@newsingledollar{\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

\LWR@doubledollar Redefine the double dollar sign to place math inside a `lateximage`, or use MathJax:

```
\protected\gdef\LWR@doubledollar$#1$${%
```

If MathJax or formatting for a word processor, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

For MathJax, print the math between `\[` and `\]`:

```
{

    \textbackslash[%
    \LWR@HTMLsanitize{#1}%
    \textbackslash]

}% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the LaTeX code:

```
{% not mathjax
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [%
        \textbackslash{[} % extra space
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash{]}%
    ]%
    *% do not add open/closing braces
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

```
    \LWR@origdollar\LWR@origdollar#1\LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}% not mathjax
```

Clear the single-use `alt` text:

```
\gdef\LWR@ThisAltText{}%
}%
```

`\LWR@singledollar` {⟨*alt text*⟩} {⟨*math expression*⟩}

```
\protected\gdef\LWR@singledollar#1${%
\ifbool{mathjax}{%
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {#1}% contents
}{% not mathjax
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {\LWR@origensuredmath{#1}}% contents
}% not mathjax
```

Clear the single-use `alt` text:

```
\gdef\LWR@ThisAltText{}%
}
```

`\(` `\[` Redefine to the above dollar macros.

```
\AtBeginDocument{
\protected\gdef\(#1\){$#1$}
\protected\gdef\[#1\]{$$#1$$}
}

\endgroup


\AtBeginDocument{
\LetLtxMacro\LWR@openbracketnormal\[
\LetLtxMacro\LWR@closebracketnormal\]
}
```

`\@ensuredmath` {⟨*expression*⟩}

If MathJax, a `lateximage` is used, since `\ensuremath` is often used for complex TEX expressions which MathJax may not render. If SVG math, a hashed file is used with a simple `alt` tag, but additional hashing provided by the contents.

```
\LetLtxMacro\LWR@origensuredmath\@ensuredmath

\renewcommand{\@ensuredmath}[1]{%
\ifbool{mathjax}{%
    \LWR@subsingledollar*{\AltTextOpen\MathImageAltText\AltTextClose}{%
           \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{\relax%
        \LWR@origensuredmath{#1}%
    }%
}{% SVG math
```

If already inside a `lateximage` in math mode, continue as-is.

```
\ifmmode%
    \LWR@origensuredmath{#1}%
\else%
```

Create an inline math `lateximage` with a simple `alt` tag and additional hashing according to the contents.

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {\LWR@origensuredmath{#1}}%
    {%
        \LWR@subsingledollar*{\AltTextOpen\MathImageAltText\AltTextClose}{%
           \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
        }{%
            \LWR@origensuredmath{#1}%
        }%
    }%
\fi%
}%
```

Clear the single-use `alt` text:

```
\gdef\LWR@ThisAltText{}%
}
```

Remove the old `math` and `displaymath` environments:

```
\let\math\relax
\let\endmath\relax
\let\displaymath\relax
\let\enddisplaymath\relax
```

Env `math` Set math mode then typeset the body of what was between the begin/end. See the environ package for `\BODY`.

```
\NewEnviron{math}{\expandafter\(\BODY\)}
```

Env LWR@displaymathnormal Set math mode then typeset the body of what was between the begin/end. See the environ package for \BODY.

```
\NewEnviron{LWR@displaymathnormal}{\expandafter\[\BODY\]\@ignoretrue}
```

Set the default displaymath to the normal version:

```
\LetLtxMacro\[\LWR@openbracketnormal%
\LetLtxMacro\]\LWR@closebracketnormal%
\LetLtxMacro\displaymath\LWR@displaymathnormal%
\LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
```

Env LWR@displaymathother A version of displaymath which can handle complicated objects, but does not supply MathJax or HTML alt tags.

```
\newenvironment{LWR@displaymathother}
{%
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [\MathImageAltText]%
    \LWR@origdollar\LWR@origdollar%
}
{%
    \LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}
```

Env LWR@equationother A version of displaymath which can handle complicated objects, but does not supply MathJax or HTML alt tags.

```
\newenvironment{LWR@equationother}
{%
    \begin{BlockClass}{displaymathnumbered}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\MathImageAltText]%
    \LWR@origequation%
}
{%
    \LWR@origendequation%
    \end{lateximage}%
    \end{BlockClass}%
}
```

79.4 MathJax support

Ctr LWR@nextequation Used to add one to compute the next equation number.

```
\newcounter{LWR@nextequation}
```

\LWR@syncmathjax Sets the MathJax equation format and number for the following equations.

These MathJax commands are printed inside "\(" and "\)" characters. They are printed to HTML output, not interpreted by LaTeX.

```
\newcommand*{\LWR@syncmathjax}{%
```

If using chapters, place the chapter number in front of the equation. Otherwise, use the simple equation number.

```
\ifcsdef{thechapter}{
    \InlineClass{hidden}{
        \textbackslash(
        \textbackslash{}seteqsection \{\thechapter\}
        \textbackslash)
    }
}
{}% not using chapters
```

MathJax doesn't allow setting the equation number to 1:

```
\ifthenelse{\cnttest{\value{equation}}>0}
{
```

Tell MathJax that the next set of equations begins with the current LaTeX equation number, plus one.

```
    \setcounter{LWR@nextequation}{\value{equation}}
    \addtocounter{LWR@nextequation}{1}
```

Place the MathJax command inside "\(" and "\)" characters, to be printed to HTML, not interpreted by LaTeX.

```
    \InlineClass{hidden}{
        \textbackslash(
        \textbackslash{}seteqnumber \{\arabic{LWR@nextequation}\}
        \textbackslash)
    }
}{}% not eq > 0
}
```

\LWR@hidelatexequation {⟨*environment*⟩} {⟨*contents*⟩}

Creates the LaTeX version of the equation inside an HTML comment.

```
\NewDocumentCommand{\LWR@hidelatexequation}{m +m}{%
```

Stop HTML paragraph handling and open an HTML comment:

```
\LWR@stoppars
\LWR@htmlopencomment
```

Start the LaTeX math environment inside the HTML comment:

```
\begingroup
\@nameuse{LWR@orig#1}
```

While in the math environment, restore various commands to their LaTeX meanings.

```
\LWR@restoreorigformatting
```

See `\LWR@htmlmathlabel` in section 79.7.1.

Print the contents of the equation:

```
#2
```

End the LaTeX math environment inside the HTML comment:

```
\@nameuse{LWR@origend#1}
\endgroup

```

Close the HTML comment and resume HTML paragraph handling:

```
\LWR@htmlclosecomment
\LWR@startpars
}
```

`\LWR@addmathjax` {⟨*environment*⟩} {⟨*contents*⟩}

Given the name of a math environment and its contents, create a MathJax instance. The contents are printed to HTML output, not interpreted by LaTeX.

```
\NewDocumentCommand{\LWR@addmathjax}{m +m}{%
```

Enclose the MathJax environment inside printed "`\(`" and "`\)`" characters.

```
\LWR@origtilde\LWR@orignewline
\textbackslash{}begin\{#1\}
```

Print the contents, sanitizing for HTML special characters.

```
\LWR@HTMLsanitizeexpand{\detokenize\expandafter{#2}}
```

Close the MathJax environment:

```
\textbackslash{}end\{#1\}
\LWR@orignewline
}
```

79.5 Equation environment

Remember existing `equation` environment, after redefined by amsmath, if loaded.

```
\AtBeginDocument{
\let\LWR@origequation\equation
\let\LWR@origendequation\endequation
\csletcs{LWR@origequation*}{equation*}
\csletcs{LWR@origendequation*}{endequation*}
}
```

`\LWR@doequation` {⟨*env contents*⟩} {⟨*env name*⟩}

For SVG math output, the contents are typeset using the original `equation` inside a `lateximage`, along with an `<alt>` tag containing a detokenized copy of the LaTeX source for the math.

For MathJax output, the contents are typeset in an original `equation` environment placed inside a HTML comment, with special processing for `\label`s. The contents are also printed to the HTML output for processing by the MathJax script.

```
\newcommand*{\LWR@doequation}[2]{%

```

If `mathjax` or `FormatWP`, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

MathJax output:

```
{
```

Print commands to syncronize MathJax's equation number and format to the current LaTeX chapter/section and equation number:

```
    \LWR@syncmathjax
```

Print the LaTeX math inside an HTML comment:

```
    \LWR@hidelatexequation{#2}{#1}
}
```

SVG output: Create the `lateximage` along with an HTML `<alt>` tag having an equation number, the LaTeX equation environment commmands, and the contents of the environment's `\BODY`.

```
{% not mathjax
```

Begin the `lateximage` with an `<alt>` tag containing the math source:

```
    \ifstrequal{#2}{equation*}{%
        \begin{BlockClass}{displaymath}%
    }{%
        \begin{BlockClass}{displaymathnumbered}%
    }%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
```

```
    \begin{lateximage}[%
        \ifstrequal{#2}{equation*}{%
            \ifdefequal{\LWR@equationtag}{\theequation}{%
% no tag was given
            }{%
                (\LWR@equationtag) % tag was given
            }%
        }{%
            (\LWR@equationtag) % automatic numbering
        }%
        \textbackslash{begin\{#2\}} % extra space
        \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#1}} % extra space
        \textbackslash{end\{#2\}}%
    ]*% alt tag
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

Create the actual LaTeX-formatted equation inside the lateximage using the contents of the environment.

```
    \@nameuse{LWR@orig#2}%
    #1% contents collected by \collect@body
    \@nameuse{LWR@origend#2}%
    \end{lateximage}%
    \end{BlockClass}%
}% not mathjax
```

Clear the single-use alt text:

```
\gdef\LWR@ThisAltText{}%
}
```

After the environment, if MathJax, print the math to the HTML output for MathJax processing:

```
\newcommand*{\LWR@doendequation}[1]{%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {%
        \LWR@addmathjax{#1}{\BODY}%
    }{}%

```

Clear the single-use alt text:

```
\gdef\LWR@ThisAltText{}%
}
```

Remove existing equation environment:

```
\AtBeginDocument{
\let\equation\relax
```

```
\let\endequation\relax
\csletcs{equation*}{relax}
\csletcs{endequation*}{relax}
}
```

Env equation

The new equation environment is created with \NewEnviron (from the environ package), which stores the contents of its environment in a macro called \BODY.

```
\AtBeginDocument{
\NewEnviron{equation}%
{\LWR@doequation{\BODY}{equation}}%
[\LWR@doendequation{equation}]

\LetLtxMacro\LWR@equationnormal\equation
\LetLtxMacro\endLWR@equationnormal\endequation
}
```

Env equation*

```
\AtBeginDocument{
\NewEnviron{equation*}%
{\LWR@doequation{\BODY}{equation*}}%
[\LWR@doendequation{equation*}]

\csletcs{LWR@equationnormalstar}{equation*}
\csletcs{LWR@endequationnormalstar}{endequation*}
}
```

Remember the "less" version of equation, which uses MathJax and alt tags, but does not support complicated contents such as some Ti*k*z expressions.

```
\AtBeginDocument{
\LetLtxMacro\LWR@equationless\equation
\LetLtxMacro\endLWR@equationless\endequation
\csletcs{LWR@equationlessstar}{equation*}
\csletcs{LWR@endequationlessstar}{endequation*}
}
```

79.6 \displaymathnormal and \displaymathother

\displaymathnormal

By default, or when selecting \displaymathnormal, MathJax math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother

MathJax unsupported complicated alt tag

When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an HTML alt tag. In this mode, MathJax is turned off, math display environments become SVG images, even if MathJax is selected, and the HTML alt tags become simple messages. The contents are internally

processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

`\displaymathnormal` simple math objects

Use when display math environments have simple math which is to sent to MathJax or included in HTML `alt` tags.

```
\newcommand*{\displaymathnormal}{%
\ifbool{LWR@origmathjax}{\booltrue{mathjax}}{\boolfalse{mathjax}}%
\LetLtxMacro\[\LWR@openbracketnormal%
\LetLtxMacro\]\LWR@closebracketnormal%
\LetLtxMacro\displaymath\LWR@displaymathnormal%
\LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
\LetLtxMacro\equation\LWR@equationnormal%
\LetLtxMacro\endequation\endLWR@equationnormal%
\csletcs{equation*}{LWR@equationnormalstar}%
\csletcs{endequation*}{LWR@endequationnormalstar}%
}
```

`\displaymathother` complicated math objects

Use when display math environments have complicated objects which will not work with MathJax or should not be included in HTML `alt` tags. Complicated contents are more likely to compile correctly.

```
\newcommand*{\displaymathother}{%
\boolfalse{mathjax}%
\LetLtxMacro\displaymath\LWR@displaymathother%
\LetLtxMacro\enddisplaymath\endLWR@displaymathother%
\LetLtxMacro\[\LWR@displaymathother%
\LetLtxMacro\]\endLWR@displaymathother%
\LetLtxMacro\equation\LWR@equationother%
\LetLtxMacro\endequation\endLWR@equationother%
\csletcs{equation*}{displaymath}%
\csletcs{endequation*}{enddisplaymath}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Print-mode versions:

```
\newcommand*{\displaymathnormal}{}
\newcommand*{\displaymathother}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

79.7 AMS Math environments

79.7.1 Support macros

Bool `LWR@amsmultline` True if processing a multline environment.

To compensate for `multline`-spefific code, `LWR@amsmultline` is used to add extra horizontal space in `\LWR@htmlmathlabel` if is used in an amsmath environment which is not a `multline` environment and not an `equation`.

```
\newbool{LWR@amsmultline}
\boolfalse{LWR@amsmultline}
```

`\LWR@htmlmathlabel` {⟨*label*⟩}

lwarp points `\ltx@label` here. This is used by `\label` when inside a LaTeX AMS math environment's math display environment.

`\LWR@origltx@label` points to the LaTeX original, modified by lwarp, then by amsmath, then by cleveref.

```
\newcommand*{\LWR@htmlmathlabel}[1]{%
\LWR@traceinfo{LWR@htmlmathlabelb #1}%
```

If `mathjax` or `FormatWP`, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{%
```

The combined LaTeX & HTML label is printed in a `\text` field:

```
    \text{%
```

Shift the label over to the right side of the environment to avoid over-printing the math:

```
    \ifbool{LWR@amsmultline}{}{\hspace*{\totwidth@}}%
```

Temporarily end the HTML comment, insert the LaTeX & HTML label, then resume the HTML comment. `\@firstofone` is required to remove extra braces introduced by the amsmath package.)

```
    \LWR@htmlclosecomment%
    \LWR@origltx@label{#1}%
    \LWR@htmlopencomment%
    }% text
}% mathjax
{%
    \LWR@origltx@label{#1}%
}%
}
```

\LWR@beginhideamsmath Starts hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@beginhideamsmath}{
\LWR@stoppars
\LWR@origtilde\LWR@orignewline
\LWR@htmlopencomment

\begingroup
\LWR@restoreorigformatting
}
```

\LWR@endhideamsmath Ends hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@endhideamsmath}{
\endgroup

\LWR@htmlclosecomment
\LWR@orignewline
\LWR@startpars
}
```

79.7.2 Environment patches

The amsmath environments already collect their contents in \@envbody for further processing. eqnarray is not an $\mathcal{AMS}$ package, and thus requires special handling.

For SVG math: Each envrionment is encapsulated inside a lateximage environment, along with a special optional argument of \LWR@amsmathbody or \LWR@amsmathbodynumbered telling lateximage to use as the HTML <alt> tag the environment's contents which were automatically captured by the $\mathcal{AMS}$ environment.

For MathJax: Each environment is syched with LaTeX's equation numbers, typeset with LaTeX inside an HTML comment, then printed to HTML output for MathJax to process.

Env eqnarray This environmnet is not an $\mathcal{AMS}$ environment and thus its body is not automatically captured, so the environ package is used to capture the environment into \BODY.

```
\let\LWR@origeqnarray\eqnarray
\let\LWR@origendeqnarray\endeqnarray
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
\newbool{LWR@numbereqnarray}
\booltrue{LWR@numbereqnarray}
```

Common code used by eqnarray and Beqnarray (from fancybox):

```
\newcommand{\LWR@eqnarrayfactor}{%
```

If mathjax or FormatWP, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{%
```

If MathJax, the environment contents (the \BODY) are executed in a HTML comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for MathJax to interpret:

```
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \ifbool{LWR@numbereqnarray}
    {
```

If numbering the equations, execute a copy inside an HTML comment block:

```
        \LWR@beginhideamsmath
        \LWR@origeqnarray
        \BODY
        \LWR@origendeqnarray
        \LWR@endhideamsmath
```

Then print the (sanitized) contents to the output for MathJax to interpret:

```
        \LWR@addmathjax{eqnarray}{\BODY}
    }%
    {% not LWR@numbereqnarray
```

If not numbering equations, just create the contents for MathJax:

```
    \LWR@addmathjax{eqnarray*}{\BODY}
    }% LWR@numbereqnarray
}% mathjax
{% not mathjax
    \ifbool{LWR@numbereqnarray}
    {
```

For numbered SVG equations, first create a lateximage with an alt attribute containing sanitized copy of the source code:

```
        \begin{BlockClass}{displaymathnumbered}%
        \LWR@newautoidanchor%
        \booltrue{LWR@indisplaymathimage}%
        \begin{lateximage}[(\LWR@startingequationtag--\LWR@equationtag)
            \LWR@addmathjax{eqnarray}{\BODY}]*
```

Support for xfakebold:

```
        \LWR@applyxfakebold%
```

Create the image contents using an actual eqnarray:

```
        \LWR@origeqnarray
```

```
        \BODY
        \LWR@origendeqnarray
        \end{lateximage}
        \end{BlockClass}
    }%
    {% not LWR@numbereqnarray
```

If not numbered, do the same, but an extra `\nonumber` seems to be required:

```
        \begin{BlockClass}{displaymath}
        \LWR@newautoidanchor%
        \booltrue{LWR@indisplaymathimage}%
        \begin{lateximage}[\LWR@addmathjax{eqnarray*}{\BODY}]*
```

Support for xfakebold:

```
        \LWR@applyxfakebold%

        \LWR@origeqnarray
        \BODY
        \nonumber
        \LWR@origendeqnarray
        \end{lateximage}
        \end{BlockClass}
    }% LWR@numbereqnarray
}% not mathjax
```

Default to number equations in the future:

```
\booltrue{LWR@numbereqnarray}
```

Clear the single-use `alt` text:

```
\gdef\LWR@ThisAltText{}%
}
```

`eqnarray` itself is made with a blank line before and after to force it to be on its own line:

```
\RenewEnviron{eqnarray}
{%

\LWR@eqnarrayfactor

}
```

The starred version is patched to turn off the numbering:

```
\csgpreto{eqnarray*}{\boolfalse{LWR@numbereqnarray}}

\end{warpHTML}
```

80 Lateximages

80.1 Description

Env `lateximage` A `lateximage` is a piece of the document which is typeset in LaTeX then included in the HTML output as an image. This is used for math if SVG math is chosen, and also for the `picture`, `tikzpicture`, and other environments.

Before typesetting the `lateximage` a large number of formatting, graphics, and symbols-related macros are temporarily restored to their print-mode meaning by `\LWR@restoreorigformatting`. (See section 78.)

A `lateximage` is typeset on its own PDF page inside an HTML comment which starts on the preceeding page and ends on following page, and instructions are written to `lateximage.txt` for *lwarpmk* to extract the `lateximage` from the page of the PDF file then generate an accompanying `.svg` file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML `<span>` is created to hold both the HTML comment, which will have the *pdftotext* conversion, and also the link to the final `.svg` image.

A LaTeX label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

HTML `alt` tag The HTML `alt` tag is set to the LaTeX source for SVG math, some chemistry expressions, and perhaps some other expressions which make sense for text copy/paste. In some other cases, the `alt` tag is set according to the package name.

When creating an SVG math image, its HTML `alt` tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the `alt` tag is set to `\MathImageAltText`, along with `\AltTextOpen` and `\AltTextClose`, and the image is not reused.

This `alt` expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "`math image`", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

For many packages, the output is placed inside a `lateximage` with an HTML `alt` tag set to the package name followed by `\PackageDiagramAltText`. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

SVG image font size For the `lateximage` environment, the size of the math and text used in the SVG image

may be adjusted by setting \LateximageFontSizeName to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by \LateximageFontScale, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

80.2 Support counters and macros

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@lateximagenumber

Sequence the images.

```
\newcounter{LWR@lateximagenumber}
\setcounter{LWR@lateximagenumber}{0}
```

Ctr LWR@lateximagedepth

Do not create \lateximage inside of \lateximage.

```
\newcounter{LWR@lateximagedepth}
\setcounter{LWR@lateximagedepth}{0}
```

A few utility macros to write special characters:

```
\edef\LWR@hashmark{\string#} % for use in \write
\edef\LWR@percent{\@percentchar} % for use in \write
```

Ctr LWR@LIpage

Used to reference the PDF page number of a lateximage to be written into <project>-images.txt.

```
\newcounter{LWR@LIpage}
```

```
\end{warpHTML}
```

80.3 Font size

for HTML & PRINT:

```
\begin{warpall}
```

\LateximageFontSizeName

Declares how large to write text in \lateximages. The .svg file text size should blend well with the surrounding HTML text size.

⚠ no backslash

Do not include the leading backslash in the name.

```
\newcommand*{\LateximageFontSizeName}{normalsize}
```

\LateximageFontScale

Declares how large to scale inline SVG math images. The .svg file text size should blend well with the surrounding HTML text size. The default is 1, but it may be redefined as needed depending on the HTML font.

```
\newcommand*{\LateximageFontScale}{1}
\end{warpall}
```

80.4 Sanitizing math expressions for HTML

for HTML output:

```
\begin{warpHTML}
```

`\LWR@HTMLsanitize` {⟨*text*⟩}

Math expressions are converted to `latexmage`s, and some math environments may contain &, <, or >, which should not be allowed inside an HTML <alt> tag, so must convert them to HTML entities.

Two versions follow, depending on expansion needs. There may be a better way…

```
\newrobustcmd{\LWR@HTMLsanitize}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
\begingroup%
\LWR@FBcancel%
\fullexpandarg%
```

The &, <, and > may be interpreted by the browser:

```
\protect\StrSubstitute{\detokenize{#1}}%
{\detokenize{&}}{\detokenize{&amp;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{<}}{\detokenize{&lt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{>}}{\detokenize{&gt;}}[\LWR@strresult]%
```

The double quote occasionally causes problems.

```
\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{"}}{\detokenize{&quot;}}[\LWR@strresult]%
```

MathJax allows expressions to be defined with `\newcommand`. These expressions would appear with ## for each argument, and each must be changed to a single #. This must be done after all the above changes. Attempting another conversion after this causes an error upon further expansion.

```
\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{##}}{\LWR@origpound}[\LWR@strresult]%

\LWR@strresult%
\endgroup%
}
```

\LWR@HTMLsanitizeexpand {⟨*text*⟩}

This version expands the argument before sanitizing it.

```
\newrobustcmd{\LWR@HTMLsanitizeexpand}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
\begingroup%
\LWR@FBcancel%
\fullexpandarg%
```

The difference between this and \LWR@HTMLsanitize (without "expand") is the following \expandafter:

```
\protect\StrSubstitute{\detokenize\expandafter{#1}}%
{\detokenize{&}}{\detokenize{&amp;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{<}}{\detokenize{&lt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{>}}{\detokenize{&gt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{"}}{\detokenize{&quot;}}[\LWR@strresult]%
```

\LWR@HTMLsanitizeexpand is not used for defining new MathJax macros, so the ## conversion is not needed here.

```
\LWR@strresult%
\endgroup%
}
```

80.5 Equation numbers

Ctr LWR@startingequation For use with lateximage and multi-line numbered equations. Remembers the next equation number so that it may be printed in the alt tag.

```
\newcounter{LWR@startingequation}

\@ifundefined{chapter}
{
\renewcommand{\theLWR@startingequation}{%
\arabic{LWR@startingequation}%
}
}
{% chapter defined
\renewcommand{\theLWR@startingequation}{%
\ifnumcomp{\value{chapter}}{>}{0}{\arabic{chapter}.}{}%
\arabic{LWR@startingequation}%
```

```
}
}
```

Bool `LWR@isstartingequation` True for the first equation tag, false for later tags in the same environment.

```
\newbool{LWR@isstartingequation}
```

`\LWR@startingequationtag` Prints the starting equation number or tag.

```
\let\LWR@startingequationtag\theLWR@startingequation
```

`\LWR@equationtag` Prints the ending equation number or tag.

This is reset by `lateximage`, may be temporarily overwritten by `\tag` calling `\LWR@remembertag`.

```
\newcommand*{\LWR@equationtag}{}
```

Only if SVG math, patch `\tag` after packages have loaded, in case someone else modified `\tag`.

```
\AtBeginDocument{

\ifbool{mathjax}{}{% not mathjax
```

`\LWR@remembertag` {⟨*tag*⟩}

For use inside the math environments while using SVG math. Sets `\theLWR@startingequation` and `\theequation` to the given tag.

```
\NewDocumentCommand{\LWR@remembertag}{m}{%
\ifbool{LWR@isstartingequation}%
{%
    \global\boolfalse{LWR@isstartingequation}%
    \xdef\LWR@startingequationtag{#1}%
}{}%
\xdef\LWR@equationtag{#1}%
}%

}% not mathjax
}% AtBeginDocument
```

80.6 HTML `alt` tags

`\LWR@amsmathbody` {⟨*envname*⟩} For use inside the optional argument to a `lateximage` to add the contents of a AMS math environment to the <alt> tag.

```
\newcommand*{\LWR@amsmathbody}[1]
{%
\textbackslash\{begin\}\{#1\} % extra space
```

```
\LWR@HTMLsanitizeexpand{\detokenize\expandafter{\the\@envbody}}%
\textbackslash\{end\}\{#1\}%
}
```

`\LWR@amsmathbodynumbered` {⟨*envname*⟩} For use inside the optional argument to a `lateximage` to add the contents of a AMS math environment to the `alt` tag, prefixed by the equation numbers.

```
\newcommand*{\LWR@amsmathbodynumbered}[1]
{%
\ifnumcomp{\value{LWR@startingequation}}{=}{\value{equation}}%
{(\LWR@equationtag)}%
{(\LWR@startingequationtag--\LWR@equationtag)} % extra space
\LWR@amsmathbody{#1} % extra space
}
```

80.7 `lateximage` environment

`\LWR@lateximage@oneimageb` {⟨*1: alt text*⟩} {⟨*2: filename*⟩} {⟨*3: CSS style*⟩} Creates the image for the `lateximage`.

```
\newcommand{\LWR@lateximage@oneimageb}[3]{%
    \LWR@subinlineimage{#1}{lateximage}%
    {%
        \LWR@print@mbox{%
            \LWR@ImagesDirectory\OSPathSymbol%
            #2%
        }%
    }{svg}{#3}%
}
```

`\LWR@lateximage@oneimage` {⟨*1: alt text*⟩} {⟨*2: filename*⟩} {⟨*3: css style*⟩} {⟨*4: delimit?*⟩}

Creates an image for the `lateximage`, whose `alt` text depends on the circumstances.

```
\newcommand{\LWR@lateximage@oneimage}[4]{%
    \ifdefvoid{\LWR@ThisAltText}{%
        \IfBooleanTF{#4}{%
            \LWR@lateximage@oneimageb{#1}{#2}{#3}%
        }{%
            \LWR@lateximage@oneimageb%
                {\AltTextOpen#1\AltTextClose}%
                {#2}{#3}%
        }%
    }{%
        \LWR@lateximage@oneimageb%
            {\AltTextOpen\LWR@ThisAltText\AltTextClose}%
            {#2}{#3}%
    }%
}
```

Env `lateximage` * [⟨*2:* <alt> *tag*⟩] * [⟨*4: add'l hashing*⟩] [⟨*5: css style*⟩]

Typesets the contents and then renders the result as an SVG file. Star #1 causes the image to be hashed for reuse. Star #3 causes the `alt` tag to not include `\AltTextOpen` and `\AltTextClose`, for use with math expressions.

The optional `<alt>` tag is included in the HTML code for use with copy/paste.

image filename hashing

If starred, a hashed filename is used.If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

File `*_html.aux`

A new label is placed into the file `*_html.aux`:

```
\newlabel{LWRlateximage-<BaseJobname>-<number>}{{<x>}{<y>}}
```

This is used to find the image in the PDF file, according to its name.

File `*-images.txt`

A list of images to generate is created in `<jobname>-images.txt`. Each line has three pipe-delimited fields, containing the PDF page number from `<jobname>_html.pdf`, where the image is located, a boolean indicating whether the image is hashed, and the filename of the image. The last line has “end” in each field, and is used to detect an incomplete compile.

```
\catcode`\$=\active%

\NewDocumentEnvironment{lateximage}{s O{\ImageAltText} s O{} O{}}
{%
\LWR@traceinfo{lateximage: starting on \jobname.pdf page \arabic{page}}%
\LWR@traceinfo{lateximage: entering depth is \arabic{LWR@lateximagedepth}}%
```

Nested `lateximages` remain one large `lateximage`:

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
```

If nesting inside an already-existing lateximage, simply record one more level. $\mathcal{AMS}$ packages redefine `\addtocounter` to do nothing if inside a `\text`, so lower-level TEX macros are used for tracking nested `lateximages`.

```
{%
%     \addtocounter{LWR@lateximagedepth}{1}%
    \global\advance\c@LWR@lateximagedepth 1\relax% Due to AmS \text macro.
}%
```

Otherwise, this is the outer-most lateximage:

```
{% start of outer-most lateximage
```

Remember the next equation number to be allocated, in case it must be printed in a multi-equation environment:

```
\LWR@traceinfo{lateximage: starting outer-most lateximage}%
    \setcounter{LWR@startingequation}{\value{equation}}%
    \addtocounter{LWR@startingequation}{1}%
    \booltrue{LWR@isstartingequation}%
    \let\LWR@startingequationtag\theLWR@startingequation%
```

The default equation tag, unless overwritten by `\tag`:

```
    \let\LWR@equationtag\theequation%
```

Starting a new lateximage:

```
    \addtocounter{LWR@lateximagenumber}{1}%
  \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{LWR@lateximagenumber}}%
```

While inside a lateximage, locally do not use mathjax:

```
    \boolfalse{mathjax}%
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Next file:

```
    \addtocounter{LWR@externalfilecnt}{1}%
  \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{LWR@externalfilecnt}}%
```

Figure out what the next page number will be. `\setcounterpageref` assigns `LWR@LIpage` to the page number for the reference `LWRlateximage-BaseJobname-XXX`:

```
    \setcounterpageref{LWR@LIpage}{%
        LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}%
    }%
    \LWR@traceinfo{lateximage: LWR@LIpage is \arabic{LWR@LIpage}}%
```

Create an HTML span which will hold the comment which contains the *pdftotext* translation of the image's page, and also will hold the link to the `.svg` file:

```
    \LWR@htmltag{span\LWR@indentHTML%
     id="lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}"\LWR@indentHTML
        class="lateximagesource"\LWR@orignewline
    }%
```

Write instructions to the `<ImagesDirectory>.txt` file:

```
    \LWR@traceinfo{lateximage: about to write to \BaseJobname-images.txt}%
    \IfBooleanTF{#1}% starred
    {% hash
```

Compute and save the hashed file name for later use:

```
        \ifdefvoid{\LWR@ThisAltText}{%
            \IfBooleanTF{#3}{%
                \edef\LWR@hashedname{%
                    \LWR@mdfive{\detokenize\expandafter{#2}-!-#4}%
                }%
            }{%
                \edef\LWR@hashedname{%
              \LWR@mdfive{\detokenize\expandafter{\AltTextOpen#2\AltTextClose}-!-#4}%
                }%
            }%
        }{%
            \edef\LWR@hashedname{%
           \LWR@mdfive{\detokenize\expandafter{\AltTextOpen\LWR@ThisAltText\AltTextClose}-!-#4}%
            }%
        }%
        \LWR@traceinfo{lateximage: hash is \LWR@hashedname}%
```

Write the page, hashing, and hashed name:

```
        \immediate\write\LWR@lateximagesfile{%
            |\arabic{LWR@LIpage}|true|\LWR@hashedname|%
        }%
    }% hash
    {% no hash
```

No hash, so write the page, no hashing, and the image number:

```
        \LWR@traceinfo{lateximage: hash false}%
        \immediate\write\LWR@lateximagesfile{%
        |\arabic{LWR@LIpage}|false|\LWR@ImagesName\arabic{LWR@externalfilecnt}|%
        }%
    }% no hash
```

Place an open comment tag. This will hide any traces of the lateximage PDF page which were picked up by *pdftotext*.

```
    \LWR@traceinfo{lateximage: about to create open comment}%
    \LWR@htmlopencomment%
```

One level deeper. At this outer-most `lateximage`, it is known that this is not being used inside an $\mathcal{AMS}$ `\text`, since the outer-most level will never be in math mode.

```
     \addtocounter{LWR@lateximagedepth}{1}%
```

Start the new PDF page:

```
    \LWR@traceinfo{lateximage: about to create a new page}%
    \LWR@orignewpage%
```

Typeset the image in a “standard” width page and font size:

```
    \LWR@traceinfo{lateximage: about to create minipage}%
    \LWR@print@minipage{6in}%
    \@nameuse{LWR@print@\LateximageFontSizeName}%
```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for \hspace, etc. inside a lateximage.

```
    \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
    \LWR@restoreorigformatting%
```

Use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```
    \def\@mpfn{footnote}%
    \def\thempfn{\thefootnote}%
    \LetLtxMacro\@footnotetext\LWR@footnotetext%
```

Create the LWRlateximage<number> label:

```
    \LWR@traceinfo{lateximage: about to create label}%
    \LWR@orig@label{LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}}%
    \LWR@traceinfo{lateximage: finished creating the label}%
```

Enable print-mode math functions:

```
    \LetLtxMacro$\LWR@origdollar%
    \catcode`\$=3% math shift
    \LetLtxMacro\(\LWR@origopenparen%
    \LetLtxMacro\)\LWR@origcloseparen%
```

Only enable print-mode display math if are not already inside display math:

```
    \ifbool{LWR@indisplaymathimage}{}{% not in display math
        \LetLtxMacro\[\LWR@origopenbracket%
        \LetLtxMacro\]\LWR@origclosebracket%
        \let\equation\LWR@origequation%
        \let\endequation\LWR@origendequation%
        \csletcs{equation*}{LWR@origequation*}%
        \csletcs{endequation*}{LWR@origendequation*}%
    }% not in display math
```

For chemformula:

```
    \LetLtxMacro\LWR@newsingledollar$%
    \LetLtxMacro\LWR@newsingledollar$% syntax highlighting

}% end of outer-most lateximage
\LWR@traceinfo{lateximage: finished start of environment}%
}% end of \begin{lateximage}
```

\endlateximage When the environment closes:

```
{% start of \end{lateximage}
\LWR@traceinfo{lateximage: starting end of lateximage}%
```

Nested more than one deep?

```
\LWR@traceinfo{lateximage: internal depth was \arabic{LWR@lateximagedepth}}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
```

If nesting inside an already existing lateximage, simply record one less level. Uses a lower-level TEX macro due to $\mathcal{AMS}$ `\text` change of `\addtocounter`.

```
{%
    \LWR@traceinfo{lateximage: unnesting}%
    \global\advance\c@LWR@lateximagedepth -1\relax%
}%
```

If this is the outer-most lateximage:

```
{% end of outer-most lateximage
```

Finish the lateximage minipage and start a new PDF page:

```
\LWR@traceinfo{lateximage: ending outer-most lateximage}%
    \endLWR@print@minipage%
    \LWR@orignewpage%
```

Close the HTML comment which encapsulated any traces of the lateximage picked up by *pdftotext*:

```
    \LWR@print@vspace*{.5\baselineskip}%
    \LWR@htmlclosecomment%
    \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%
```

Create a link to the lateximage, allowing its natural height:

```
    \IfBooleanTF{#1}% starred
    {% hash
        \LWR@lateximage@oneimage{#2}{\LWR@hashedname}{#5}{#3}%
    }% hash
    {% no hash
     \LWR@lateximage@oneimage{#2}{\LWR@ImagesName\theLWR@externalfilecnt}{#5}{#3}%
    }% no hash
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Close the HTML span which has the *pdftotext* comment and also the link to the `.svg` image:

```
    \LWR@htmltag{/span}%
    \ifbool{HTMLDebugComments}{%
        \LWR@htmlcomment{End of lateximage}%
    }{}%
```

Undo one lateximage level. This is not inside an $\mathcal{AMS}$ `\text`, so regular `\addtocounter` may be used here.

```
    \addtocounter{LWR@lateximagedepth}{-1}%
```

Clear the single-use `alt` text:

```
    \gdef\LWR@ThisAltText{}%
}% end of outer-most lateximage
\LWR@traceinfo{lateximage: exiting depth is \arabic{LWR@lateximagedepth}}%
\LWR@traceinfo{lateximage: done}%
}%
\catcode`\$=3% math shift
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Env `lateximage` * [⟨<alt> *tag*⟩] * [⟨*add'l hashing*⟩] [⟨*css style*⟩]

`varwidth` is used to create a box of the natural width of its contents.

```
\NewDocumentEnvironment{lateximage}{s o s o o}
    {\begin{varwidth}[b]{\linewidth}}
    {\end{varwidth}}
```

```
\end{warpprint}
```

81 `center`, `flushleft`, `flushright`

for HTML output:

```
\begin{warpHTML}
```

Env `center` Replace `center` functionality with CSS tags:

```
\renewenvironment*{center}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:center}]{center}}
{\BlockClass{center}}
}
{\endBlockClass}
```

Env `flushright`

```
\renewenvironment*{flushright}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:right}]{flushright}}
```

```
10524 {\BlockClass{flushright}}
10525 }
10526 {\endBlockClass}
```

Env `flushleft`

```
10527 \renewenvironment*{flushleft}
10528 {
10529 \LWR@forcenewpage
10530 \ifbool{FormatWP}
10531 {\BlockClass[\LWR@print@mbox{text-align:left}]{flushleft}}
10532 {\BlockClass{flushleft}}
10533 }
10534 {\endBlockClass}
```

`\centering`, `\raggedleft`, and `\raggedright` usually have no effect on the HTML output, but they may be used to compare with the next token to identify their use at the start of a float. See `\LWR@floatalignment`.

`\centering`

```
10535 \newcommand*{\LWR@HTML@centering}{%
10536 \ifbool{HTMLDebugComments}{%
10537     \LWR@htmlcomment{centering}%
10538 }{}%
10539 }
10540 \LWR@formatted{centering}
```

`\raggedleft`

```
10541 \newcommand*{\LWR@HTML@raggedleft}{%
10542 \ifbool{HTMLDebugComments}{%
10543     \LWR@htmlcomment{raggedleft}%
10544 }{}%
10545 }
10546 \LWR@formatted{raggedleft}
```

`\raggedright`

```
10547 \newcommand*{\LWR@HTML@raggedright}{%
10548 \ifbool{HTMLDebugComments}{%
10549     \LWR@htmlcomment{raggedright}%
10550 }{}%
10551 }
10552 \LWR@formatted{raggedright}
```

`\leftline` {⟨*text*⟩}

```
10553 \renewcommand{\leftline}[1]{\begin{flushleft}#1\end{flushleft}}
```

\centerline {⟨*text*⟩}

```
\renewcommand{\centerline}[1]{\begin{center}#1\end{center}}
```

\rightline {⟨*text*⟩}

```
\renewcommand{\rightline}[1]{\begin{flushright}#1\end{flushright}}
```

```
\end{warpHTML}
```

82 Preloaded packages

for HTML output:
```
\begin{warpHTML}
```

If the given package was loaded before or by lwarp, load the lwarp version as well.

\LWR@PreloadedPackage {⟨*packagename*⟩}

```
\newcommand*{\LWR@PreloadedPackage}[1]{%
    \@ifpackageloaded{#1}%
        {%
            \AtBeginDocument{
                \LWR@origRequirePackage{lwarp-#1}%
            }
        }%
        {}%
}
```

If inputtrc was loaded before lwarp, as is usually done, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{inputtrc}
```

If textcomp was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{textcomp}
```

If xunicode was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{xunicode}
```

If graphics or graphicx were loaded before lwarp, perhaps by xunicode, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{graphics}
\LWR@PreloadedPackage{graphicx}
```

fontaxes must be preloaded so that lwarp may patch it for HTML.

```
\LWR@PreloadedPackage{fontaxes}
```

nfssext-cfr may be preloaded by cfm-lm or related font packages.

```
\LWR@PreloadedPackage{nfssext-cfr}
```

ulem may be preloaded by ctex, ctexart, and related classes.

```
\LWR@PreloadedPackage{ulem}
```

xetexko-vertical may be preloaded by xetexko.

```
\LWR@PreloadedPackage{xetexko-vertical}
```

geometry is preloaded by lwarp, and perhaps by various classes.

```
\LWR@PreloadedPackage{geometry}
```

plext is preloaded by some CJK classes.

```
\LWR@PreloadedPackage{plext}
```

stfloats is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{stfloats}
```

lltjext is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{lltjext}
```

```
\end{warpHTML}
```

83 siunitx

Pkg siunitx — The lwarp core passes a few options to siunitx.

fractions — Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required — Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJax script.

⚠ tabular — Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

for HTML output:

```
\begin{warpHTML}
```

Options for siunitx:

```
\newrobustcmd{\LWR@siunitx@textcelsius}{\HTMLentity{deg}C}
\newrobustcmd{\LWR@siunitx@textdegree}{\HTMLentity{deg}}
\newrobustcmd{\LWR@siunitx@textprime}{\HTMLunicode{2032}}
\newrobustcmd{\LWR@siunitx@textdblprime}{\HTMLunicode{2033}}
\newrobustcmd{\LWR@siunitx@textplanckbar}{\text{\textit{\HTMLunicode{0127}}}}

\appto\LWR@restoreorigformatting{%
\renewrobustcmd{\LWR@siunitx@textcelsius}{\text{\ensuremath{^\circ}C}}%
\renewrobustcmd{\LWR@siunitx@textdegree}{\text{\ensuremath{^\circ}}}%
\renewrobustcmd{\LWR@siunitx@textprime}{\text{\ensuremath{^\prime}}}%
\renewrobustcmd{\LWR@siunitx@textdblprime}{\text{\ensuremath{^{\prime\prime}}}}%
\renewrobustcmd{\LWR@siunitx@textplanckbar}{\text{\ensuremath{\hbar}}}%
}

\PassOptionsToPackage{
    detect-mode=true,
    per-mode=symbol,% fraction is not seen by pdftotext
    text-celsius = {\LWR@siunitx@textcelsius},
    text-degree = {\LWR@siunitx@textdegree},
    text-arcminute = {\LWR@siunitx@textprime} ,
    text-arcsecond = {\LWR@siunitx@textdblprime} ,
}{siunitx}

\end{warpHTML}
```

84 Graphics print-mode modifications

84.1 General limitations

⚠ scale Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

\includegraphics file formats For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps` image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a `.pdf` or `.eps` image is referred to with its file extension, the extension will be changed to `.svg` for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo

PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **pdftocairo -svg filename.pdf**

Prog lwarpmk pdftosvg

For a large number of images, use *lwarpmk*:

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

Prog lwarpmk epstopdf

Prog epstopdf

epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **lwarpmk pdftosvg *.PDF**

to convert to SVG images.

DVI latex

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **lwarpmk epstopdf *.eps** **(or a list of filenames)**

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

PNG and JPG

For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF

GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities

If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx

⚠ viewport

⚠ viewport units

If using the older graphics syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options

`\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys.

HTML class

With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML `alt` tags

Likewise, the `\includegraphics` `alt` key adds an HTML `alt` tag to an image, and is ignored for print output. If not assigned, each image is given an `alt` tag according to `\ImageAltText`.

\rotatebox \rotatebox accepts the optional origin key.

⚠ browser support \rotatebox, \scalebox, and \reflectbox depend on modern browser support. The css3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

84.2 Print-mode modifications

for PRINT output: For print output, accept and then discard the new class key:

```
\begin{warpprint}
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
```

Print-mode additions for the overpic package. See section 360 for the HTML version.

```
\AtBeginDocument{
\@ifpackageloaded{overpic}{
\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}
}{}
}
\end{warpprint}
```

85 xcolor boxes

Pkg xcolor A few new definitions are provided for enhanced HTML colored boxes, and \fcolorbox is slightly modified. Print-mode version are also provided.

Print-mode versions of new xcolor defintions. These are defined inside warpall because they are also used for HTML while inside a lateximage. They are defined \AtBeginDocument so that the xcolor originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of none, in which case only the frame is drawn, allowing the background page color to show.

for HTML & PRINT:
```
\begin{warpall}
```

After xparse may have been loaded …

```
\AtBeginDocument{
```

… and *only* if xcolor was loaded:

```
\@ifpackageloaded{xcolor}{
\LWR@traceinfo{patching xcolor}
```

The print version:

\colorboxBlock \colorboxBlock is the same as \colorbox:

```
\LetLtxMacro\colorboxBlock\colorbox
```

The original definition is reused by the new versions:

```
\LetLtxMacro\LWR@orig@print@fcolorbox\fcolorbox
```

\fcolorbox [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

In print mode, \fcolorbox is modified to accept a background color of none.

(\fcolorbox is particular about its optional arguments, thus the elaborate combinations of \ifthenelse.)

```
\newsavebox{\LWR@colorminipagebox}

\NewDocumentCommand{\LWR@print@fcolorbox}{o m o m +m}{%
\LWR@traceinfo{LWR@print@fcolorbox #2 #4}%
```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
\begin{lrbox}{\LWR@colorminipagebox}%
#5%
\end{lrbox}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
\ifstrequal{#4}{none}%
{% #4 none
    \LWR@traceinfo{background is none}%
    {% scope the \colorlet
        \colorlet{LWR@currentcolor}{.}%
        \color{#2}%
        \fbox{%
            \color{LWR@currentcolor}%
            \usebox{\LWR@colorminipagebox}%
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
\LWR@traceinfo{background not none}%
\IfValueTF{#1}%
{%
    \IfValueTF{#3}%
  {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}%
{% no value #1
    \IfValueTF{#3}%
```

```
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}% no value #1
}% #4 not none
\LWR@traceinfo{LWR@print@fcolorbox done}%
}

\renewcommand*{\fcolorbox}{\LWR@print@fcolorbox}
```

\fcolorboxBlock `[`⟨*framemodel*⟩`]` `{`⟨*framecolor*⟩`}` `[`⟨*boxmodel*⟩`]` `{`⟨*boxcolor*⟩`}` `{`⟨*text*⟩`}`

In print mode, \fcolorboxBlock is the same as \fcolorbox.

```
\newcommand*{\LWR@print@fcolorboxBlock}{\LWR@print@fcolorbox}
\newcommand*{\fcolorboxBlock}{\LWR@print@fcolorboxBlock}
```

Env fcolorminipage `[`⟨*1:framemodel*⟩`]` `{`⟨*2:framecolor*⟩`}` `[`⟨*3:boxmodel*⟩`]` `{`⟨*4:boxcolor*⟩`}` `[`⟨*5:align*⟩`]` `[`⟨*6:height*⟩`]` `[`⟨*7:inner-align*⟩`]` `{`⟨*8:width*⟩`}`

In print mode, becomes a \fcolorbox containing a minipage:

```
\NewDocumentEnvironment{LWR@print@fcolorminipage}{o m o m O{c} O{} o m}
{%
\LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%
```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
\begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```
\IfValueTF{#7}%
{\begin{minipage}[#5][#6][#7]{#8}}%
{\begin{minipage}[#5][#6][#5]{#8}}%
}%
{%
\end{minipage}%
\end{lrbox}%
\LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
\ifstrequal{#4}{none}%
{% #4 none
    {% scope the \colorlet
        \colorlet{LWR@currentcolor}{.}%
        \color{#2}%
        \fbox{%
            \color{LWR@currentcolor}%
```

```
            \usebox{\LWR@colorminipagebox}%
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
    \IfValueTF{#1}%
    {%
    \IfValueTF{#3}%
   {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
    }%
    {% no value #1
    \IfValueTF{#3}%
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
    }% no value #1
}% #4 not none
\LWR@traceinfo{*** finished end fcolorminipage}%
}

\newenvironment*{fcolorminipage}
    {\LWR@print@fcolorminipage}
    {\endLWR@print@fcolorminipage}

\LWR@traceinfo{xcolor patches done}
}{}% xcolor loaded
}% AtBeginDocument

\end{warpall}
```

86 chemmacros environments

\makepolymerdelims and redox reactions must be enclosed in a lateximage during HTML output. These environments are provided here in print mode, and in the chemmacros code in HTML mode, as a high-level semantic syntax which automatically embeds the contents in a lateximage with an appropriate alt tag.

for PRINT output:

```
\begin{warpprint}

\AtBeginDocument{
\@ifpackageloaded{chemmacros}{
```

Env polymerdelims

```
\DeclareDocumentEnvironment{polymerdelims}{}
    {}{}
```

Env redoxreaction {⟨*space above*⟩} {⟨*space below*⟩}

For print output, extra space is include above and below the image, and a lateximage is not necessary. This extra space must be enforced, even inside a float, so zero-width rules are used.

For the HTML version, see section 168.4.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
    {\rule{0pt}{#1}}{\rule[-#2]{0pt}{#2}}

}{}% chemmacros
}% AtBeginDocument

\end{warpprint}
```

87 cleveref

Pkg cleveref

cleveref package is used as-is with minor patches.

⚠ cleveref page numbers

cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for \cpageref and \cpagerefrange. This phrase includes \cpagerefFor, which defaults to "for".

Ex:

```
    \cpageref{tab:first,tab:second}
 in html becomes:
```

"pages **for** table 4.1 and **for** table 4.2"

See \cpagerefFor at page 542 to redefine the message which is printed for page number references.

loading order

cleveref and the following associated macro patches are automatically preloaded at the end of the preamble via \AtEndPreamble and \AfterEndPreamble. This is done because the HTML conversion requires cleveref. The user's document may not require cleveref, thus the user may never explicitly load it, so during HTML output lwarp loads it last. If the user's document preamble uses cleveref options, or functions such as \crefname, then cleveref may be loaded in the user's preamble near the end, and lwarp's additional loading of cleveref will have no effect.

Table 12 on page 462 shows the data structure of the label/reference system as revised by lwarp and cleveref.

A few patches allow cleveref to work as-is:

for HTML output:

```
\begin{warpHTML}
```

\AtEndPreable forces cleveref to be loaded last:

```
\AtEndPreamble{
    \RequirePackage{cleveref}
}
```

The following patches are applied after cleveref has loaded, and after \AtBeginDocument. Print-mode versions are not required since they all come down to \ref eventually, and \ref has a print-mode version.

```
\AfterEndPreamble{
\LWR@traceinfo{Patching cleveref.}
```

`\@@@setcref` {⟨*kindofref*⟩} {⟨*label*⟩}

`\@templabel` becomes the section number.

```
\def\LWR@orig@@@setcref#1#2{\cref@getlabel{#2}{\@templabel}#1{\@templabel}{}{}}%

\ifdefequal{\@@setcref}{\LWR@orig@@@setcref}{% before v0.21
    \renewcommand*{\@@setcref}[2]{#1{\ref{#2}}{}{}}
}{
    \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% as of v0.21
        \renewcommand*{\@@@setcref}[2]{#1{\ref{#2}}{}{}}
    }{
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cref\space will fail.
        }%
    }
}
```

`\@@@setcrefrange` {⟨*text*⟩} {⟨*label*⟩} {⟨*label*⟩}

```
\def\LWR@orig@@@setcrefrange#1#2#3{%
  \cref@getlabel{#2}{\@labela}%
  \cref@getlabel{#3}{\@labelb}%
  #1{\@labela}{\@labelb}{}{}{}{}}%

\ifdefequal{\@@setcrefrange}{\LWR@orig@@@setcrefrange}{
    \renewcommand{\@@setcrefrange}[3]{%
        #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
    }
}{
    \ifdefequal{\@@@setcrefrange}{\LWR@orig@@@setcrefrange}{
        \renewcommand{\@@@setcrefrange}[3]{%
            #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
        }
    }{
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\crefrange\space will fail.
        }
    }
}

```

`\cpagerefFor` Redefinable word between “page(s)” and the page numbers.

```
\newcommand*{\cpagerefFor}{for}
```

`\@@@setcpageref` {⟨*typeofref*⟩} {⟨*label*⟩}, where typeofref is “page” or “pages”

```
\def\LWR@orig@@setcpageref#1#2{% before v0.21
  \cref@getpageref{#2}{\@temppage}#1{\@temppage}{}{}}%

\def\LWR@orig@@@setcpageref#1#2{% as of v0.21
  \cpageref@getlabel{#2}{\@temppage}#1{\@temppage}{}{}}%

\ifdefequal{\@@setcpageref}{\LWR@orig@@setcpageref}{
    \renewcommand*{\@@setcpageref}[2]{%
        #1{\cpagerefFor\ \cref{#2}}{}{}%
    }
}{
    \ifdefequal{\@@@setcpageref}{\LWR@orig@@@setcpageref}{
        \renewcommand*{\@@@setcpageref}[2]{%
            #1{\cpagerefFor\ \cref{#2}}{}{}%
        }
    }
    {
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cpageref\space will fail.
        }
    }
}

\def\LWR@orig@@setcpagerefrange#1#2#3{% before v0.21
  \cref@getpageref{#2}{\@pagea}%
  \cref@getpageref{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}}%

\def\LWR@orig@@@setcpagerefrange#1#2#3{% as of v0.21
  \cpageref@getlabel{#2}{\@pagea}%
  \cpageref@getlabel{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}}%

\ifdefequal{\@@setcpagerefrange}{\LWR@orig@@setcpagerefrange}{
    \renewcommand*{\@@setcpagerefrange}[3]{%
        #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
    }
}{
    \ifdefequal{\@@@setcpagerefrange}{\LWR@orig@@@setcpagerefrange}{
        \renewcommand*{\@@@setcpagerefrange}[3]{%
            #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
        }
    }
    {
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cpagerefrange\space will fail.
        }
    }
}

}% AfterEndPreamble
```

Remember and patch some label-related defintions. These will be further encased and patched by other packages later.

`\label` and `\pageref` do NOT change their behavior according to print or HTML output, and thus do not use the `\LWR@formatted` system.

```
\LetLtxMacro\LWR@orig@label\label
\RenewDocumentCommand{\label}{}{\LWR@new@label}

\LetLtxMacro\LWR@orig@pageref\pageref
\RenewDocumentCommand{\pageref}{}{\LWR@new@pageref}
\end{warpHTML}
```

88 `picture` environment

Env `picture` The `picture` environment is enclosed inside a `\lateximage`.

for HTML output:

```
\begin{warpHTML}
```

Env `picture`

```
\BeforeBeginEnvironment{picture}{\begin{lateximage}[picture]}

\AfterEndEnvironment{picture}{\end{lateximage}}
```

```
\end{warpHTML}
```

89 Minipages and Boxes

A css flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

⚠ inline A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

placement `minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side Side-by-side `minipages` may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span There is limited support for `minipages` inside an HTML . An HTML cannot appear inside a . While in a , `minipages`, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an “inline” format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

⚠ minipage size — When using \linewidth, \textwidth, and \textheight, widths and heights in HTML are scaled proportionally to a 6×9 inch text area, and inside a multicols \linewidth is divided by the specified number of columns.

if width is \linewidth — If a minipage or \parbox is assigned a width of exactly \linewidth, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML — A new macro \minipagefullwidth requests that, during HTML output, the next single minipage or \parbox be generated without an HTML width attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ tabular, multicols — Inside a tabular or multicols environment, where the width depends on the browser window, \minipagefullwidth is effectively used by default for every minipage or \parbox inside the environment. \UseMinipageWidths may be used to tell lwarp to honor the specified widths of all following minipages and \parboxes until the end of the local scope, and \IgnoreMinipageWidths may be used to tell lwarp to ignore the specified widths.

\UseMinipageWidths
\IgnoreMinipageWidths

⚠ text alignment — Nested minipages adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a flushleft or similar environment in the child minipage to force a text alignment.

for HTML output:
```
\begin{warpHTML}
```

89.1 Counters and lengths

Ctr LWR@minipagedepth — Used to only reset the line width at the outermost minipage.

```
\newcounter{LWR@minipagedepth}
\setcounter{LWR@minipagedepth}{0}
```

Len \LWR@minipagewidth — Used to convert the width into printable units.

```
\newlength{\LWR@minipagewidth}
```

Len \LWR@minipageheight — Used to convert the height into printable units.

```
\newlength{\LWR@minipageheight}
```

89.2 Footnote handling

Also see section 59 for other forms of footnotes. Minipage footnotes are gathered in section 59.5, and then placed into the document in section 89.3.

89.3 Minipage handling

Bool LWR@minipagefullwidth — Should the next minipage have no HTML width?

```
\newbool{LWR@minipagefullwidth}
\boolfalse{LWR@minipagefullwidth}
```

Bool `LWR@forceminipagefullwidth` Should the next minipage have no HTML `width`? Used to force full width for all minipages in an environment such as `tabular` or `multicols`, where the actual width depends on the browser width. Controlled by `\useminipagewidths` and `\ignoreminipagewidths`.

```
\newbool{LWR@forceminipagefullwidth}
\boolfalse{LWR@forceminipagefullwidth}
```

`\minipagefullwidth` Requests that the next minipage have no `width` tag in HTML:

for HTML output:

```
\newcommand*{\minipagefullwidth}{\global\booltrue{LWR@minipagefullwidth}}
```

`\UseMinipageWidths` Locally requests that minipage widths be honored.

```
\newcommand*{\UseMinipageWidths}{\boolfalse{LWR@forceminipagefullwidth}}
```

`\IgnoreMinipageWidths` Locally requests that minipage widths be ignored.

```
\newcommand*{\IgnoreMinipageWidths}{\booltrue{LWR@forceminipagefullwidth}}
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\minipagefullwidth}{}
\newcommand*{\UseMinipageWidths}{}
\newcommand*{\IgnoreMinipageWidths}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

Bool `LWR@minipagethispar` Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.

```
\newbool{LWR@minipagethispar}
\boolfalse{LWR@minipagethispar}
```

Env `minipage` `[`⟨*vert position*⟩`]` `[`⟨*height*⟩`]` `[`⟨*inner vert position*⟩`]` `{`⟨*width*⟩`}`

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using `\linewidth`, `\textwidth`, or `\textheight`, these are scaled proportionally to a 6×9 inch text area.

```
\NewDocumentEnvironment{LWR@HTML@sub@minipage}{m m m m}
{%
\LWR@traceinfo{minipage}%
```

Temporarily open a group, in which width and height is computed based on a virtual page size instead of the extra-large PDF page used during HTML tag generation.

The following used to be an actual LaTeX minipage.

```
\begingroup%
```

Compute width, adjusted for frames:

```
\setlength{\LWR@minipagewidth}{#4}%
\ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}{%
```

Only create a new page if not yet nested:

```
    \LWR@orignewpage%
```

Adjust virtual page size:

```
    \addtolength{\LWR@minipagewidth}{3em}% room for frames
    \setlength{\linewidth}{6in}%
    \setlength{\textwidth}{6in}%
    \setlength{\textheight}{9in}%
}{}%
\LWR@traceinfo{computed width is \LWR@printlength{\LWR@minipagewidth}}%
```

Compute height:

```
\setlength{\LWR@minipageheight}{\textheight}% default unless specified
\ifblank{#2}{}{\setlength{\LWR@minipageheight}{#2}}%
```

Track nesting depth:

```
\addtocounter{LWR@minipagedepth}{1}%
```

LaTeX wants to start a paragraph for the virtual minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

```
\ifbool{FormatWP}{\newline}{}%
\LWR@stoppars%
```

If `FormatWP`, add a text frame:

```
\ifbool{FormatWP}{%

\addtocounter{LWR@thisautoidWP}{1}%
\LWR@htmltag{%
    div id="\LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}" %
    class="wpminipage"%
}%

}{}%
```

Create the tag with optional alignment style:

```
\LWR@traceinfo{minipage: creating div class}%
\LWR@htmltag{div class="minipage" style="%
\ifthenelse{\equal{#1}{t}}{\LWR@print@mbox{vertical-align:bottom} ; }{}%
\ifthenelse{\equal{#1}{c}}{\LWR@print@mbox{vertical-align:middle} ; }{}%
\ifthenelse{\equal{#1}{b}}{\LWR@print@mbox{vertical-align:top} ; }{}%
\ifthenelse{\equal{#3}{t}}{\LWR@print@mbox{justify-content:flex-start} ; }{}%
\ifthenelse{\equal{#3}{c}}{\LWR@print@mbox{justify-content:center} ; }{}%
\ifthenelse{\equal{#3}{b}}{\LWR@print@mbox{justify-content:flex-end} ; }{}%
\ifthenelse{\equal{#3}{s}}{\LWR@print@mbox{justify-content:space-between} ; }{}%
```

Print the width and optional height styles:

```
\LWR@traceinfo{minipage: about to print the width of \LWR@printlength{\LWR@minipagewidth}}%
\ifbool{LWR@minipagefullwidth}%
{\global\boolfalse{LWR@minipagefullwidth}}%
{%
    \ifbool{LWR@forceminipagefullwidth}%
        {}%
        {%
            \ifdimequal{#4}{\linewidth}%
                {}%
                {width:\LWR@printlength{\LWR@minipagewidth} ; }%
        }%
}%
\LWR@traceinfo{minipage: about to print the height}%
\ifblank{#2}{}{height:\LWR@printlength{\LWR@minipageheight} ; }%
"}%
```

Finish with an empty line to start the contents on a new line.

```

% The preceding empty line is required.
```

Set the user-accessible line and text width and height values inside the virtual minipage. These do not affect the actual size of the PDF output, but are used by any reference to \linewidth, etc. inside the virtual minipage being created here. \LWR@minipagewidth was the original then padded by 3em, which is restored here. This is done instead of settings back to #4, in case #4 was \linewidth, which was changed to 6in above.

```
\setlength{\linewidth}{\LWR@minipagewidth}% the padded width
\addtolength{\linewidth}{-3em}% the original width
\setlength{\textwidth}{6in}%
\setlength{\textheight}{9in}%
```

\raggedright cancels hyphenation, which will be done by HTML instead.

```
\LWR@print@raggedright%
```

Set minipage footnotes:

```
\def\@mpfn{mpfootnote}%
\def\thempfn{\thempfootnote}\c@mpfootnote\z@%
```

```
\let\@footnotetext\@mpfootnotetext%
```

Resume paragraph tag handling for the contents of the minipage:

```
\LWR@startpars%
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

=== begin minipage ===

}{}%
\LWR@traceinfo{minipage: finished starting the minipage}%
}% finished \minipage
{% \endminipage
```

Print pending minipage footnotes:

```
\LWR@printpendingmpfootnotes%
```

End the environment with closing tag:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

=== end minipage ===

}{}%
\LWR@stoppars%
```

The following used to be an actual LaTeX minipage.

```
\endgroup%

\ifbool{FormatWP}{%

\LWR@htmlelementend{div}%

}{}%
\LWR@htmldivclassend{minipage}%

\addtocounter{LWR@minipagedepth}{-1}%
\LWR@startpars%
\ifbool{FormatWP}{\newline}{}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{LWR@minipage: done}%
}

\NewDocumentEnvironment{LWR@HTML@minipage}{O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#1}{#2}{#3}{#4}}
    {\endLWR@HTML@sub@minipage}

\LWR@formattedenv{minipage}
```

89.4 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox

for HTML output:

\parbox [⟨*pos*⟩] [⟨*height*⟩] [⟨*inner-pos*⟩] {⟨*width*⟩} {⟨*text*⟩}

A parbox uses the minipage code:

```
\NewDocumentCommand{\LWR@HTML@parbox}{O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#1][#2][#3]{#4}%
#5
\end{minipage}%
}

\LWR@formatted{parbox}
```

\mbox {⟨*text*⟩} Nullified for HTML.

```
\newcommand*{\LWR@HTML@mbox}[1]{#1}

\LWR@formatted{mbox}
```

\LWR@@makebox@paren {⟨*width*⟩} , {⟨*height*⟩}

Adds to the style in \LWR@temptwo.

```
\NewDocumentCommand{\LWR@@makebox@paren}{m m}{%
\IfValueTF{#2}{%
    \setlength{\LWR@tempwidth}{#1\unitlength}%
    \setlength{\LWR@tempheight}{#2\unitlength}%
    \appto{\LWR@temptwo}{%
        \LWR@print@mbox{width:\LWR@printlength{\LWR@tempwidth}} ; % space
        \LWR@print@mbox{height:\LWR@printlength{\LWR@tempheight}} ; % space
    }%
}{%
    \PackageError{lwarp}%
        {(width,height) is missing a comma ',' character}%
        {\protect\makebox\space and \protect\framebox\space accept
            a size in the format (width,height).}%
}%
}
```

\LWR@@makebox@align {⟨*alignment character*⟩}

Adds to the style in \LWR@temptwo.

```
\newcommand*{\LWR@@makebox@align}[1]{%
    \def\LWR@align{center}%
    \ifstrequal{#1}{l}{\def\LWR@align{left}}{}%
    \ifstrequal{#1}{r}{\def\LWR@align{right}}{}%
    \ifstrequal{#1}{s}{\def\LWR@align{justify}}{}%
```

```
    \appto{\LWR@temptwo}{%
        \LWR@print@mbox{text-align:\LWR@align} ; %
    }%
}
```

\makebox (⟨*width,height*⟩) [⟨*width*⟩] [⟨*pos*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@makebox}{>{\SplitArgument{1}{,}}d() o o +m}{%
```

Build the style depending on arguments:

```
{% scope
    \def\LWR@temptwo{}%
    \IfValueTF{#1}%
    {% (width,height) ..
        \LWR@@makebox@paren #1%
        \IfValueT{#2}%
        {% (width,height) [posn]
            \LWR@@makebox@align{#2}%
        }%
    }%
    {% [width]
        \IfValueT{#2}% [width]
        {%
            \setlength{\LWR@tempwidth}{#2}%
            \ifdimgreater{\LWR@tempwidth}{0pt}{%
                \appto{\LWR@temptwo}{%
                    width:\LWR@printlength{\LWR@tempwidth} ; % space
                }%
            }{}%
        }%
    }%
    \IfValueT{#3}%
    {% [width] [posn]
        \LWR@@makebox@align{#3}%
    }%
    \InlineClass[%
        \LWR@print@mbox{display:inline-block} ; %
        \LWR@temptwo%
    ]%
    {makebox}%
    {#4}%
}% scope
}
\LWR@formatted{makebox}
```

\framebox (⟨*width,height*⟩) [⟨*width*⟩] [⟨*pos*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@framebox}{d() o o +m}{%
    \fbox{\makebox(#1)[#2][#3]{#4}}%
}

\LWR@formatted{framebox}
```

\LWR@forceminwidth {⟨*legth*⟩}

Sets \LWR@atleastonept to be at least 1pt.

```
\newlength{\LWR@atleastonept}

\newcommand*{\LWR@forceminwidth}[1]{%
\setlength{\LWR@atleastonept}{#1}%
\ifthenelse{%
    \lengthtest{\LWR@atleastonept>0pt}\AND%
    \lengthtest{\LWR@atleastonept<1pt}%
}%
    {\setlength{\LWR@atleastonept}{1pt}}%
    {}%
}
```

\LWR@fboxstyle Prints the HTML attributes for a black border and padding.

\LWR@forceminwidth must be used first in order to set the border width.

```
\newcommand*{\LWR@fboxstyle}{%
\LWR@findcurrenttextcolor%
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@origpound\LWR@tempcolor ; %
padding:\LWR@printlength{\fboxsep} ; %
color:\LWR@origpound\LWR@tempcolor%
}
```

\fbox {⟨*text*⟩}

Creates a framed inline span enclosing the text.

Create a new HTML version, but don't use it until after xcolor may have loaded:

```
\newcommand{\LWR@HTML@fbox}[1]{%
\LWR@traceinfo{HTML fbox}%
\LWR@forceminwidth{\fboxrule}%
\InlineClass[%
    \LWR@print@mbox{display:inline-block} ; %
    \LWR@fboxstyle%
]{fbox}{#1}%
}
```

xcolor \lets things to \fbox when it is loaded, and this must remain even for HTML output while in a lateximage, so \fbox is not modified until \AtBeginDocument:

```
\AtBeginDocument{\LWR@formatted{fbox}}
```

\fboxBlock {⟨*text*⟩} Creates a framed HTML of the text.

First, a print-mode version. This is newly defined for print mode, so it is defined inside warpall.

for HTML & PRINT:

```
\end{warpHTML}
```

```
\begin{warpall}
\let\fboxBlock\fbox
\end{warpall}

\begin{warpHTML}
```

for HTML output: Next, an HTML version:

```
\newcommand{\LWR@HTML@fboxBlock}[1]{%
\LWR@forceminwidth{\fboxrule}%
\LWR@stoppars%
\begin{BlockClass}[%
\LWR@fboxstyle%
]{fboxBlock}
#1
\end{BlockClass}
\LWR@startpars%
}

\LWR@formatted{fboxBlock}

\end{warpHTML}
```

Env `fminipage` `[`⟨*align*⟩`]` `[`⟨*height*⟩`]` `[`⟨*align*⟩`]` `{`⟨*width*⟩`}`

Creates a framed HTML around its contents.

for HTML & PRINT: Print version:

```
\begin{warpall}

\newsavebox{\LWR@fminipagebox}

\NewDocumentEnvironment{LWR@print@fminipage}{O{t} o O{t} m}
{%
```

An outer minipage will be used for vertical alignment. An inner minipage will be framed with \fbox.

If the optional inner alignment is not given, use the outer instead:

```
\IfValueTF{#3}%
{\def\LWR@thisalign{#3}}
{\def\LWR@thisalign{#1}}%
```

Form the outer minipage depending on whether a height was given. Make the outer minipage larger to compensate for the frame.

```
\IfValueTF{#2}%
{\minipage[#1][#2+2\fboxsep+2\fboxrule][\LWR@thisalign]{#4+2\fboxsep+2\fboxrule}}%
{\minipage[#1]{#4+2\fboxsep+2\fboxrule}}%
```

Capture the contents of the environment:

```
\begin{lrbox}{\LWR@fminipagebox}%
```

Nest the contents inside an inner minipage of the desired size:

```
\IfValueTF{#2}%
{\minipage[#1][#2][\LWR@thisalign]{#4}}%
{\minipage[#1]{#4}}%
}
{%
```

Close the inner minipage and the LR box with the contents:

```
\endminipage%
\end{lrbox}%
```

Create a frame around the contents of the environment:

```
\fbox{\usebox{\LWR@fminipagebox}}%
```

The entire thing is placed inside the outer minipage:

```
\endminipage%
}

\LetLtxMacro\fminipage\LWR@print@fminipage
\LetLtxMacro\endfminipage\endLWR@print@fminipage
% \newenvironment{fminipage}{\LWR@print@fminipage}{\endLWR@print@fminipage}

\end{warpall}
```

HTML version:

for HTML output:

```
\begin{warpHTML}

\NewDocumentEnvironment{LWR@HTML@fminipage}{O{t} o O{t} m}
{%
\LWR@traceinfo{fminipage #1 #2 #3 #4}%
\LWR@forceminwidth{\fboxrule}%
\setlength{\LWR@tempwidth}{#4}%
\IfValueT{#2}{\setlength{\LWR@tempheight}{#2}}%


\LWR@stoppars%

\begin{BlockClass}[%
\LWR@fboxstyle ; %
\IfValueT{#2}{height:\LWR@printlength{\LWR@tempheight} ; }%
\ifbool{LWR@minipagefullwidth}%
{\global\boolfalse{LWR@minipagefullwidth}}%
{%
    \ifbool{LWR@forceminipagefullwidth}%
        {}%
        {%
            \ifdimequal{\LWR@tempwidth}{\linewidth}%
                {}%
                {width:\LWR@printlength{\LWR@tempwidth} ; }%
        }%
```

```
}%
]{fminipage}%
}
{%
\end{BlockClass}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{fminipage done}%
}

\LWR@formattedenv{fminipage}
```

`\raisebox` {⟨*raiselen*⟩} [⟨*height*⟩] [⟨*depth*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@raisebox}{m o o m}{%
#4%
}

\LWR@formatted{raisebox}
```

```
\end{warpHTML}
```

90 Direct formatting

⚠ `\bfseries`, etc. — `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ HTML special chars — &, <, and > have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings — For program listings, the listings package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.

verbatim — The various `verbatim`-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

For high-level block and inline custom CSS classes, see section 51.9.

for HTML output:

```
\begin{warpHTML}
```

`\emph` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@emph}[1]{%
    {%
        \itshape%
        \LWR@htmlspan{em}{#1}%
```

```
    }%
}

\LWR@formatted{emph}

\newcommand{\LWR@null@emph}[1]{#1}
```

`\textmd` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textmd}[1]{%
    {%
        \mdseries%
        \InlineClass(font-weight:normal){textmd}{#1}%
    }%
}

\LWR@formatted{textmd}

\newcommand{\LWR@null@textmd}[1]{#1}
```

`\textbf` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textbf}[1]{%
    {%
        \bfseries%
        \LWR@htmlspan{b}{#1}%
    }%
}

\LWR@formatted{textbf}

\newcommand{\LWR@null@textbf}[1]{#1}
```

`\texteb` {⟨*text*⟩} From nfssext-cfr.

```
\DeclareRobustCommand{\LWR@HTML@texteb}[1]{%
    {%
        \ebweight%
        \InlineClass{texteb}{#1}%
    }%
}

\LWR@formatted{texteb}

\newcommand{\LWR@null@texteb}[1]{#1}
```

`\textlg` {⟨*text*⟩} From nfssext-cfr.

```
\DeclareRobustCommand{\LWR@HTML@textlg}[1]{%
    {%
        \lgweight%
        \InlineClass{textlg}{#1}%
```

```
    }%
}

\LWR@formatted{textlg}

\newcommand{\LWR@null@textlg}[1]{#1}
```

\textrm {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textrm}[1]{%
    {%
        \rmfamily%
        \InlineClass(font-family:serif){textrm}{#1}%
    }%
}

\LWR@formatted{textrm}

\newcommand{\LWR@null@textrm}[1]{#1}
```

\textsf {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsf}[1]{%
    {%
        \sffamily%
        \InlineClass(font-family:sans){textsf}{#1}%
    }%
}

\LWR@formatted{textsf}

\newcommand{\LWR@null@textsf}[1]{#1}
```

\texttt {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@texttt}[1]{%
    {%
        \ttfamily%
        \LWR@htmlspan{kbd}{#1}%
    }%
}

\LWR@formatted{texttt}

\newcommand{\LWR@null@texttt}[1]{#1}
```

\textup {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textup}[1]{%
    {%
        \upshape%
        \InlineClass(font-style:normal){textup}{#1}%
```

```
    }%
}

\LWR@formatted{textup}

\newcommand{\LWR@null@textup}[1]{#1}
```

`\textit` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textit}[1]{%
    {%
        \itshape%
        \LWR@htmlspan{i}{#1}%
    }%
}

\LWR@formatted{textit}

\newcommand{\LWR@null@textit}[1]{#1}
```

`\textsc` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsc}[1]{%
    {%
        \scshape%
        \InlineClass{textsc}{#1}%
    }%
}

\LWR@formatted{textsc}

\newcommand{\LWR@null@textsc}[1]{#1}
```

`\textulc` {⟨*text*⟩} From fontaxes.

```
\DeclareRobustCommand{\LWR@HTML@textulc}[1]{%
    {%
        \ulcshape%
        \InlineClass{textulc}{#1}%
    }%
}

\LWR@formatted{textulc}

\newcommand{\LWR@null@textulc}[1]{#1}
```

`\textsi` {⟨*text*⟩}

```
\@ifundefined{textsi}{
    \LetLtxMacro\LWR@print@textsi\LWR@print@textsc
}{}

```

```
\DeclareRobustCommand{\LWR@HTML@textsi}[1]{%
    {%
        \sishape%
        \textsc{\textit{#1}}%
      % \InlineClass(
      %     font-style: italic;
      %     font-variant: small-caps ;
      %     font-variant-numeric: oldstyle-nums ;
      % ){textsi}{#1}%
    }%
}

\LWR@formatted{textsi}

\newcommand{\LWR@null@textsi}[1]{#1}
```

`\textsl` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsl}[1]{%
    {%
        \slshape%
        \InlineClass(font-style:oblique){textsl}{#1}%
    }%
}

\LWR@formatted{textsl}

\newcommand{\LWR@null@textsl}[1]{#1}
```

`\textnormal` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textnormal}[1]{\textmd{\textrm{\textup{#1}}}}

\LWR@formatted{textnormal}

\newcommand{\LWR@null@textnormal}[1]{#1}

\newcommand{\LWR@null@rmfamily}{}
\newcommand{\LWR@null@sffamily}{}
\newcommand{\LWR@null@ttfamily}{}
\newcommand{\LWR@null@bfseries}{}
\newcommand{\LWR@null@ebweight}{}
\newcommand{\LWR@null@lgweight}{}
\newcommand{\LWR@null@mdseries}{}
\newcommand{\LWR@null@upshape}{}
\newcommand{\LWR@null@slshape}{}
\newcommand{\LWR@null@scshape}{}
\newcommand{\LWR@null@itshape}{}
\newcommand{\LWR@null@normalfont}{}


\newcommand{\LWR@null@em}{}
```

`\LWR@nullfonts` Removes formatting during filename operations, file references, and HTML comments.

⚠ Use only inside a group.

The following are *not* made robust, since they must be expanded to their nullified versions.

```
\catcode`\$=\active% redefining $ below
\catcode`\_=12% redefining \_ below
\newcommand*{\LWR@nullfonts}{%
\LetLtxMacro\emph\LWR@null@emph%
\LetLtxMacro\textmd\LWR@null@textmd%
\LetLtxMacro\textbf\LWR@null@textbf%
\LetLtxMacro\textrm\LWR@null@textrm%
\LetLtxMacro\textsf\LWR@null@textsf%
\LetLtxMacro\texttt\LWR@null@texttt%
\LetLtxMacro\textup\LWR@null@textup%
\LetLtxMacro\textit\LWR@null@textit%
\LetLtxMacro\textsc\LWR@null@textsc%
\LetLtxMacro\textulc\LWR@null@textulc%
\LetLtxMacro\textsi\LWR@null@textsi%
\LetLtxMacro\textsl\LWR@null@textsl%
\LetLtxMacro\textnormal\LWR@null@textnormal%
\LetLtxMacro\rmfamily\LWR@null@rmfamily%
\LetLtxMacro\sffamily\LWR@null@sffamily%
\LetLtxMacro\ttfamily\LWR@null@ttfamily%
\LetLtxMacro\bfseries\LWR@null@bfseries%
\LetLtxMacro\mdseries\LWR@null@mdseries%
\LetLtxMacro\upshape\LWR@null@upshape%
\LetLtxMacro\slshape\LWR@null@slshape%
\LetLtxMacro\scshape\LWR@null@scshape%
\LetLtxMacro\ulcshape\LWR@null@ulcshape%
\LetLtxMacro\sishape\LWR@null@sishape%
\LetLtxMacro\itshape\LWR@null@itshape%
\LetLtxMacro\normalfont\LWR@null@normalfont%
\LetLtxMacro\em\LWR@null@em%
```

Various built-in symbols.

```
\renewcommand*{\$}{-}%
\renewcommand*{\%}{-}%
\renewcommand*{\_}{-}%
\renewcommand*{\}}{-}%
\renewcommand*{\{}{-}%
\renewcommand*{\&}{and}%
\renewcommand*{\#}{-}%
\renewcommand*{\,}{-}%
\renewcommand*{~}{-}%
\renewcommand*{\^}[1]{-}%
\renewcommand*{\~}[1]{-}%
\renewcommand*{\newline}{-}%
\renewcommand*{\textasciicircum}{-}%
\renewcommand*{\textasciitilde}{-}%
\renewcommand*{\textasteriskcentered}{-}%
```

```
\renewcommand*{\textbackslash}{-}%
\renewcommand*{\textbar}{-}%
\renewcommand*{\textbardbl}{-}%
\renewcommand*{\textbigcircle}{-}%
\renewcommand*{\textbraceleft}{-}%
\renewcommand*{\textbraceright}{-}%
\renewcommand*{\textbullet}{-}%
\renewcommand*{\textcopyright}{-}%
\renewcommand*{\textdagger}{-}%
\renewcommand*{\textdaggerdbl}{-}%
\renewcommand*{\textdollar}{-}%
\renewcommand*{\textellipsis}{-}%
\renewcommand*{\textemdash}{-}%
\renewcommand*{\textendash}{-}%
\renewcommand*{\textexclamdown}{-}%
\renewcommand*{\textgreater}{-}%
\renewcommand*{\textless}{-}%
\renewcommand*{\textordfeminine}{-}%
\renewcommand*{\textordmasculine}{-}%
\renewcommand*{\textparagraph}{-}%
\renewcommand*{\textperiodcentered}{-}%
\renewcommand*{\textpertenthousand}{-}%
\renewcommand*{\textperthousand}{-}%
\renewcommand*{\textquestiondown}{-}%
\renewcommand*{\textquotedblleft}{-}%
\renewcommand*{\textquotedblright}{-}%
\renewcommand*{\textquoteleft}{-}%
\renewcommand*{\textquoteright}{-}%
\renewcommand*{\textregistered}{-}%
\renewcommand*{\textsection}{-}%
\renewcommand*{\textsterling}{-}%
\renewcommand*{\texttrademark}{-}%
\renewcommand*{\textunderscore}{-}%
\renewcommand*{\textvisiblespace}{-}%
\renewcommand*{\copyright}{-}%
\renewcommand*{\dag}{-}%
\renewcommand*{\ddag}{-}%
\renewcommand*{\dots}{-}%
\renewcommand*{\P}{-}%
\renewcommand*{\pounds}{-}%
\renewcommand*{\S}{-}%
\renewcommand*{\aa}{a}%
\renewcommand*{\AA}{A}%
\renewcommand*{\AE}{AE}%
\renewcommand*{\ae}{ae}%
\renewcommand*{\dh}{d}%
\renewcommand*{\DH}{D}%
\renewcommand*{\DJ}{D}%
\renewcommand*{\dj}{d}%
\renewcommand*{\IJ}{IJ}%
\renewcommand*{\ij}{ij}%
\renewcommand*{\L}{L}%
\renewcommand*{\l}{l}%
\renewcommand*{\NG}{NG}%
\renewcommand*{\ng}{ng}%
```

```
\renewcommand*{\O}{O}%
\renewcommand*{\o}{o}%
\renewcommand*{\oe}{oe}%
\renewcommand*{\OE}{OE}%
\renewcommand*{\ss}{ss}%
\renewcommand*{\SS}{SS}%
\renewcommand*{\th}{th}%
\renewcommand*{\TH}{TH}%
\renewcommand*{\guillemotleft}{}%
\renewcommand*{\guilsinglleft}{}%
\renewcommand*{\quotedblbase}{}%
\renewcommand*{\textquotedbl}{}%
\renewcommand*{\guillemotright}{}%
\renewcommand*{\guilsinglright}{}%
\renewcommand*{\quotesinglbase}{}%

\renewcommand*{\HTMLunicode}[1]{}%
\renewcommand*{\HTMLentity}[1]{}%

\renewcommand{\textsuperscript}[1]{##1}%
\renewcommand{\textsubscript}[1]{##1}%


\renewcommand{\underline}[1]{##1}%


\RenewDocumentCommand{\hspace}{s m}{}%

\RenewDocumentCommand{\LWR@htmlspanclass}{o m +m}{##3}%
\DeclareExpandableDocumentCommand{\InlineClass}{D{(}{)}{} o m +m}{##4}%
```

Nullify math macros.

```
\def\(##1\){}%
\def\[##1\]{}%
\RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
\protected\def$##1${}%
```

Nullify logos:

```
\renewcommand*{\TeX}{TeX}%
\renewcommand*{\LaTeX}{LaTeX}%
\renewcommand*{\LaTeXe}{LaTeX2e}%
\renewcommand*{\LuaTeX}{LuaTeX}%
\renewcommand*{\LuaLaTeX}{LuaLaTeX}%
\renewcommand*{\XeTeX}{XeTeX}%
\renewcommand*{\XeLaTeX}{XeLaTeX}%
\renewcommand*{\ConTeXt}{ConTeXt}%
\renewcommand*{\BibTeX}{BibTeX}%
\renewcommand*{\MakeIndex}{MakeIndex}%
\renewcommand*{\AmS}{AmS}%
\renewcommand*{\MiKTeX}{MiKTeX}%
\renewcommand*{\LyX}{LyX}%
```

Use the simpler form with \texorpdfstring:

```
\let\texorpdfstring\relax%
\newcommand{\texorpdfstring}[2]{##2}%
}
\catcode`\$=3%
\catcode`\_=8%
```

\FilenameNullify {⟨*redefinitions*⟩}

Adds more nullifying definitions for filename generation.

```
\newcommand*{\FilenameNullify}[1]{%
    \appto{\LWR@nullfonts}{#1}%
}
```

Remembers the current font family, series, and shape. fontaxes support is integrated here.

```
\newcommand*{\LWR@f@family}{rm}
\newcommand*{\LWR@f@series}{md}
\newcommand*{\LWR@f@shape}{up}
\newcommand*{\LWR@f@shapecaps}{ulc}
```

\LWR@textcurrentfont {⟨*text*⟩}

Prints the text with the current font choices. Avoids nesting repeated font selections.

```
\newcounter{LWR@textcurrentfontdepth}
\setcounter{LWR@textcurrentfontdepth}{0}

\newcommand*{\LWR@textcurrentfont}[1]{%
    \ifnumcomp{\value{LWR@textcurrentfontdepth}}{>}{0}%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            #1%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
        }%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            \InlineClass{%
                    text\LWR@f@family\LWR@origtilde{}%
                    text\LWR@f@series\LWR@origtilde{}%
                    text\LWR@f@shape\LWR@origtilde{}%
                    text\LWR@f@shapecaps%
                }%
                {#1}%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
        }%
}
```

Env LWR@blocktextcurrentfont Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{%
\LWR@stoppars%
\BlockClass{%
        text\LWR@f@family\LWR@origtilde{}%
        text\LWR@f@series\LWR@origtilde{}%
        text\LWR@f@shape\LWR@origtilde{}%
        text\LWR@f@shapecaps%
    }%
}{\endBlockClass\LWR@startpars}
```

\mdseries

```
\newrobustcmd*{\LWR@HTML@mdseries}{\renewcommand*{\LWR@f@series}{md}}
\LWR@formatted{mdseries}
```

\bfseries

```
\newrobustcmd*{\LWR@HTML@bfseries}{\renewcommand*{\LWR@f@series}{bf}}
\LWR@formatted{bfseries}
```

\ebweight From nfssext-cfr.

```
\newrobustcmd*{\LWR@HTML@ebweight}{\renewcommand*{\LWR@f@series}{eb}}
\LWR@formatted{ebweight}
```

\lgweight From nfssext-cfr.

```
\newrobustcmd*{\LWR@HTML@lgweight}{\renewcommand*{\LWR@f@series}{lg}}
\LWR@formatted{lgweight}
```

\rmfamily

```
\newrobustcmd*{\LWR@HTML@rmfamily}{\renewcommand*{\LWR@f@family}{rm}}
\LWR@formatted{rmfamily}
```

\sffamily

```
\newrobustcmd*{\LWR@HTML@sffamily}{\renewcommand*{\LWR@f@family}{sf}}
\LWR@formatted{sffamily}
```

\ttfamily

```
\newrobustcmd*{\LWR@HTML@ttfamily}{\renewcommand*{\LWR@f@family}{tt}}
\LWR@formatted{ttfamily}
```

\upshape

```
\newrobustcmd*{\LWR@HTML@upshape}{\renewcommand*{\LWR@f@shape}{up}}
\LWR@formatted{upshape}
```

\itshape

```
\newrobustcmd*{\LWR@HTML@itshape}{\renewcommand*{\LWR@f@shape}{it}}
\LWR@formatted{itshape}
```

\scshape

```
\newrobustcmd*{\LWR@HTML@scshape}{\renewcommand*{\LWR@f@shapecaps}{sc}}
\LWR@formatted{scshape}
```

\ulcshape From fontaxes.

```
\@ifundefined{ulcshape}{
    \LetLtxMacro\ulcshape\upshape
}{}
\newrobustcmd*{\LWR@HTML@ulcshape}{\renewcommand*{\LWR@f@shapecaps}{ulc}}
\LWR@formatted{ulcshape}
```

\sishape

```
\@ifundefined{sishape}{
    \LetLtxMacro\sishape\scshape
}{}
\newrobustcmd*{\LWR@HTML@sishape}{%
    \renewcommand*{\LWR@f@shape}{it}
    \renewcommand*{\LWR@f@shapecaps}{sc}%
}
\LWR@formatted{sishape}
```

\slshape

```
\newrobustcmd*{\LWR@HTML@slshape}{\renewcommand*{\LWR@f@shape}{sl}}
\LWR@formatted{slshape}
```

\normalfont

```
\renewrobustcmd*{\normalfont}{\rmfamily\mdseries\upshape\ulcshape}
```

\sp {⟨*text*⟩}

For siunitx. Must work in math mode.

```
\renewcommand{\sp}[1]{\text{<sup>#1</sup>}{}}
```

\sb {⟨*text*⟩}

For siunitx. Must work in math mode.

```
\renewcommand{\sb}[1]{\text{<sub>#1</sub>}{}}
```

\textsuperscript {⟨*text*⟩}

```
\renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

\@textsuperscript {⟨*text*⟩}

```
\renewcommand{\@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

\textsubscript {⟨*text*⟩}

```
\AtBeginDocument{
\renewrobustcmd{\textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
}
```

\@textsubscript {⟨*text*⟩}

```
\AtBeginDocument{
\renewcommand{\@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
}
```

\up {⟨*text*⟩} Prints superscript.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
\AtBeginDocument{\let\up\textsuperscript}
```

\fup {⟨*text*⟩} Prints superscript.

Supports fmtcount package.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
\AtBeginDocument{\let\fup\textsuperscript}
```

\underline {⟨*text*⟩}

```
\renewcommand{\underline}[1]{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {underline}{#1}%
}
```

\LWR@overline {⟨*text*⟩}

```
\newcommand{\LWR@overline}[1]{%
    \InlineClass%
        (text-decoration:overline; text-decoration-skip: auto)%
        {overline}{#1}%
}
```

`\LWR@currenttextcolor` The color to use for text and `\rule`, defaulting to black:

```
\newcommand*{\LWR@currenttextcolor}{black}
```

`\LWR@tempcolor` `\LWR@tempcolortwo` The color converted to HTML colorspace.

```
\newcommand*{\LWR@tempcolor}{}
\newcommand*{\LWR@tempcolortwo}{}
```

`\LWR@findcurrenttextcolor` Sets `\LWR@tempcolor` to the current color.

```
\newcommand*{\LWR@findcurrenttextcolor}{%
\renewcommand{\LWR@tempcolor}{000000}%
}
```

`\LWR@textcurrentcolor` {⟨*text*⟩} Like `\textcolor` but uses the current `\color` instead.

```
\NewDocumentCommand{\LWR@textcurrentcolor}{m}{%
    \renewcommand*{\LWR@currenttextcolor}{black}%
    #1%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

`\LWR@textcurrentfont` {⟨*text*⟩}

Prints the text with the current font choices.

```
\newcommand*{\LWR@textcurrentfont}[1]{#1}
```

Env `LWR@blocktextcurrentfont` Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{}{}
```

`\FilenameNullify` {⟨*macros to nullify*⟩}

```
\newcommand*{\FilenameNullify}[1]{}
```

```
\end{warpprint}
```

91 Skips, spaces, font sizes

for HTML output:

```
\begin{warpHTML}
```

\, and \thinspace may be redefined by other packages, so are redefined \AtBeginDocument here.

Direct-formatting space commands become HTML entities:

```
\AtBeginDocument{
\renewrobustcmd*{\,}{\HTMLunicode{202f}} % HTML thin non-breakable space
\renewrobustcmd*{\thinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{\negthinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{~}{\HTMLentity{nbsp}}
\renewrobustcmd*{\textellipsis}{\HTMLunicode{2026}}
}
```

Direct-formatting font sizes are ignored:

```
\newrobustcmd*{\LWR@HTML@normalsize}{}
\LWR@formatted{normalsize}

\newrobustcmd*{\LWR@HTML@small}{}
\LWR@formatted{small}

\newrobustcmd*{\LWR@HTML@footnotesize}{}
\LWR@formatted{footnotesize}

\newrobustcmd*{\LWR@HTML@scriptsize}{}
\LWR@formatted{scriptsize}

\newrobustcmd*{\LWR@HTML@tiny}{}
\LWR@formatted{tiny}

\newrobustcmd*{\LWR@HTML@large}{}
\LWR@formatted{large}

\newrobustcmd*{\LWR@HTML@Large}{}
\LWR@formatted{Large}

\newrobustcmd*{\LWR@HTML@LARGE}{}
\LWR@formatted{LARGE}

\newrobustcmd*{\LWR@HTML@huge}{}
\LWR@formatted{huge}

\newrobustcmd*{\LWR@HTML@Huge}{}
\LWR@formatted{Huge}


\DeclareDocumentCommand{\onecolumn}{}{}

\DeclareDocumentCommand{\twocolumn}{O{}}{
#1

}
```

\hfill

```
\newcommand*{\LWR@HTML@hfill}{\qquad}
\LWR@formatted{hfill}
```

\hrulefill

```
\newcommand*{\LWR@HTML@hrulefill}{\rule{1in}{1pt}}
\LWR@formatted{hrulefill}
```

\dotfill

```
\newcommand*{\LWR@HTML@dotfill}{\dots}
\LWR@formatted{dotfill}
```

\newpage

```
\renewcommand*{\newpage}{
}
```

\newline Uses the HTML <br /> element.

```
\newrobustcmd*{\LWR@newlinebr}{\unskip\LWR@htmltag{br /}\LWR@orignewline}%
\LetLtxMacro\newline\LWR@newlinebr
```

\\ Redefined to \LWR@endofline or \LWR@tabularendofline.

\LWR@endofline * [⟨*len*⟩]

\\ is assigned to \LWR@endofline at \LWR@LwarpStart.

Inside tabular, \\ is temporarily changed to \LWR@tabularendofline.

```
\LetLtxMacro\LWR@origendofline\\
\NewDocumentCommand{\LWR@endofline}{s O{0pt}}
{%
\newline%
```

```
\setlength{\LWR@templengthone}{#2}%
\ifdimgreater{\LWR@templengthone}{0pt}{\newline}{}%
}
```

\LWR@minipagestartpars Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a to be inside a p, paragraphs must be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, lwarp correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to

\hspace \enskip \quad \qquad

be on its own line. Since people often place small horizontal space between minipages, it is desirable to maintain this space if possible. lwarp tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around \hspace, \enskip, \quad, and \qquad until the end of the paragraph, when the closing p tag is created.

When a minipage is seen, the boolean LWR@minipagethispar is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. LWR@minipagethispar is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestartpars}{%
\ifbool{LWR@minipagethispar}{\LWR@startpars}{}%
}
```

\LWR@minipagestoppars

Placed just after \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestoppars}{%
\ifbool{LWR@minipagethispar}{\LWR@stoppars}{}%
}
```

\quad

Handles special minipage & horizontal space interactions. Uses 2003 EM SPACE to pass validation.

```
\renewrobustcmd*{\quad}{%
\LWR@minipagestoppars%
\HTMLunicode{2003}%
\LWR@minipagestartpars%
}
```

\qquad

Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\qquad}{\quad\quad}
```

\enskip

Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\enskip}{%
\LWR@minipagestoppars%
\HTMLunicode{2002}%
\LWR@minipagestartpars%
}
```

Len \LWR@tempwidth
Len \LWR@tempheight
Len \LWR@tempraise

Used to compute span width, height, raise for \hspace and \rule:

```
\newlength{\LWR@tempwidth}
\newlength{\LWR@tempheight}
\newlength{\LWR@tempraise}
```

\LWR@select@html@hspace
\hspace

* {⟨*length*⟩} * {⟨*length*⟩}

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

\hspace{\fill} is converted to \hspace{2em}, equal to \qquad.

```
\newcommand{\LWR@select@html@hspace}{%
\RenewDocumentCommand{\hspace}{s m}{%
\setlength{\LWR@tempwidth}{##2}%
```

If \fill, change to \qquad:

```
\ifnum\gluestretchorder\LWR@tempwidth>0%
\setlength{\LWR@tempwidth}{2em}%
\fi%
```

Only if the width is greater than zero:

```
\ifdimcomp{\LWR@tempwidth}{>}{0pt}{%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Support the HTML thin wrappable space:

```
    \ifdimcomp{\LWR@tempwidth}{=}{.16667em}%
    {%
        \HTMLunicode{2009}% thin breakable space
    }%
```

Print the span with the converted width. Not rounded.

```
    {%
        \LWR@htmltagc{%
            span style="width:\LWR@printlength{\LWR@tempwidth};  % extra space
                display:inline-block"%
        }%
```

If formatting for a word processor, approximate with a number of \quads, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \quad%
                \addtolength{\LWR@templengthone}{-1em}%
            }%
        }%
```

If NOT formatting for a word processor, include an empty comment to avoid an empty span:

```
11660         {\LWR@htmlcomment{}}%
```

Close the span:

```
11661         \LWR@htmltagc{/span}%
11662     }%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
11663     \LWR@minipagestartpars%
11664 }{}% width greater than 0
11665 }%
11666 }
```

`\LWR@select@html@nohspace` * {⟨*length*⟩}
`\hspace`

Used to disable `\hspace` while creating `description` `\item`s.

```
11667 \newcommand{\LWR@select@html@nohspace}{%
11668     \RenewDocumentCommand{\hspace}{s m}{}%
11669 }
```

`\LWR@select@print@hspace`

```
11670 \newcommand*{\LWR@select@print@hspace}{%
11671     \renewrobustcmd\hspace{\@ifstar\@hspacer\@hspace}%
11672 }
```

`\hspace` * {⟨*length*⟩}

Handles special minipage & horizontal space interactions.

```
11673 \LWR@select@html@hspace
```

`\LWR@vspace` * {⟨*length*⟩} Nullified vspace.

```
11674 \NewDocumentCommand{\LWR@HTML@vspace}{s m}{}
11675
11676 \LWR@formatted{vspace}
```

`\linebreak` [⟨*num*⟩] Inserts an HTML `br` tag.

```
11677 \renewcommand*{\linebreak}[1][]{\newline}
```

`\nolinebreak` [⟨*num*⟩]

```
11678 \renewcommand*{\nolinebreak}[1][]{}
```

`\pagebreak` `[`⟨*num*⟩`]` Starts a new paragraph.

```
\renewcommand*{\pagebreak}[1][]{
}
```

`\nopagebreak` `[`⟨*num*⟩`]`

```
\renewcommand*{\nopagebreak}[1][]{}
```

`\enlargethispage` `*` `{`⟨*len*⟩`}`

```
\RenewDocumentCommand{\enlargethispage}{s m}{}
```

`\clearpage`
`\cleardoublepage`

```
\renewcommand*{\clearpage}{}
\renewcommand*{\cleardoublepage}{}
```

`\rule` `[`⟨*raise*⟩`]` `{`⟨*width*⟩`}` `{`⟨*height*⟩`}`

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

`\fill` is zero-width, so `\hspace{\fill}` is ignored.

```
\newcommand*{\LWR@HTML@rule}[3][]{%
```

The width is copied into a temporary LaTeX length, from which comparisons and conversions may be made:

```
\setlength{\LWR@tempwidth}{#2}%
```

If it's zero-width then skip the entire rule:

```
\ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}%
{}% zero- width
{% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
    \ifthenelse{%
        \lengthtest{\LWR@tempwidth>0pt}\AND%
        \lengthtest{\LWR@tempwidth<1pt}%
    }%
        {\setlength{\LWR@tempwidth}{1pt}}%
        {}%
```

Likewise with height:

```
    \setlength{\LWR@tempheight}{#3}%
    \ifthenelse{%
        \lengthtest{\LWR@tempheight>0pt}\AND%
        \lengthtest{\LWR@tempheight<1pt}%
    }%
        {\setlength{\LWR@tempheight}{1pt}}%
        {}%
```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in LaTeX code.

```
    \LWR@findcurrenttextcolor%
    \LWR@htmltagc{%
    span\LWR@indentHTML%
    style="%
```

The HTML background color is used to draw the filled rule according to the LaTeX foreground color set by `\textcolor`.

```
    \ifbool{FormatWP}{}{background:\LWR@currenttextcolor ; }%
```

The width and height are printed, converted to PT:

```
    width:\LWR@printlength{\LWR@tempwidth} ; %
    height:\LWR@printlength{\LWR@tempheight} ; %
```

The raise height is converted to a CSS transform. The `*2` raise multiplier is to approximately match HTML output's X height. Conversion to a LaTeX length allows a typical LaTeX expression to be used as an argument for the raise, whereas printing the raise argument directly to HTML output without conversion to a LaTeX length limits the allowable syntax. To do: A superior method would compute a ratio of LaTeX ex height, then print that to HTML with an ex unit.

```
    \ifblank{#1}%
    {}%
    {%
        \setlength{\LWR@tempraise}{0pt-#1}%
        \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
        \LWR@indentHTML%
        -ms-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
        -webkit-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
        transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
    }%
```

Display inline-block to place the span inline with the text:

```
    display:inline-block;"\LWR@orignewline%
    }%
```

If formatting for a word processor, approximate with a number of underscores, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \_{}%
                \addtolength{\LWR@templengthone}{-1em}%
            }%
        }%
```

If NOT formatting for a word processor, add a comment to avoid an empty :

```
        {\LWR@htmlcomment{}}%
```

Close the span:

```
    \LWR@htmltagc{/span}%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestartpars%
}% non-zero width
}

\LWR@formatted{rule}

\end{warpHTML}
```

92 \phantomsection

for HTML output:

```
\begin{warpHTML}
```

\phantomsection Emulate the hyperref \phantomsection command, often used to insert the bibliography into the table of contents. Ignores \ForceHTMLTOC.

```
\DeclareDocumentCommand{\phantomsection}{}{%
\begingroup%
\boolfalse{LWR@forcinghtmltoc}%
\section*{}%
\endgroup%
}

\end{warpHTML}
```

93 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally set by \LWR@formatted.

For CSS conversions, see:
http://edward.oconnor.cx/2007/08/tex-poshlet
http://nitens.org/taraborelli/texlogo
and the spacing described in the metafont package documentation.

for HTML & PRINT:

```
\begin{warpall}
\newrobustcmd*{\Xe}
    {X\hspace{-.1667em}\raisebox{-.5ex}{E}}

\AtBeginDocument{
\@ifpackageloaded{graphics}{
    \@ifpackageloaded{metalogo}{}{
        \renewrobustcmd*{\Xe}
            {X\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}}
    }
}{
    \PackageWarningNoLine{lwarp}{Load graphicx or graphics
        for improved XeTeX logo}
}
}

\providerobustcmd*{\XeTeX}{\mbox{\Xe\hspace{-.125em}\TeX}}
\providerobustcmd*{\XeLaTeX}{\mbox{\Xe\hspace{-.125em}\LaTeX}}
\providerobustcmd*{\AmS}{%
    \leavevmode\hbox{$\mathcal A\kern-.2em\lower.376ex%
    \hbox{$\mathcal M$}\kern-.2em\mathcal S$}%
}
\newrobustcmd*{\LyX}{\textsf{LyX}}
\providerobustcmd*{\LuaTeX}{\mbox{Lua\TeX}}
\providerobustcmd*{\LuaLaTeX}{\mbox{Lua\LaTeX}}
\providerobustcmd*{\BibTeX}{\mbox{B\textsc{ib}\TeX}}
\providerobustcmd*{\MakeIndex}{\mbox{\textit{MakeIndex}}}
\providerobustcmd*{\ConTeXt}{\mbox{Con\TeX{}t}}
\providerobustcmd*{\MiKTeX}{\mbox{MiK\TeX}}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

The print-mode versions of the following may be changed by metalogo, so their print formatting is recorded \AtBeginDocument.

\TeX TEX

latexlogo is a CSS class used to properly typeset the E and A in LATEX and friends.

`latexlogofont` is a css class used to select the font for the rest of the logo in LaTeX, LuaTeX, ConTeXt, etc.

```
\newrobustcmd*{\LWR@HTML@TeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
}
\AtBeginDocument{\LWR@formatted{TeX}}% may have been patched by metalogo
```

`\LaTeX` `\LaTeXe` LaTeX, LaTeX 2$_\varepsilon$

```
\newrobustcmd*{\LWR@HTML@LaTeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            L%
            \InlineClass{latexlogosup}{a}%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
}

\AtBeginDocument{\LWR@formatted{LaTeX}}% may have been patched by metalogo


\newrobustcmd*{\LWR@HTML@LaTeXe}
{%
    \LaTeX%
    \InlineClass{latexlogofont}{%
        \InlineClass{latexlogotwoe}{%
            2%
            \InlineClass{latexlogotwoesub}{\HTMLunicode{03B5}}%
        }%
    }%
}
\AtBeginDocument{\LWR@formatted{LaTeXe}}% may have been patched by metalogo
```

`\LuaTeX` `\LuaLaTeX` LuaTeX, LuaLaTeX

```
\newrobustcmd*{\LWR@HTML@LuaTeX}{\InlineClass{latexlogofont}{Lua}\TeX}
\AtBeginDocument{\LWR@formatted{LuaTeX}}% may have been patched by metalogo

```

```
\newrobustcmd*{\LWR@HTML@LuaLaTeX}{\InlineClass{latexlogofont}{Lua}\LaTeX}
\AtBeginDocument{\LWR@formatted{LuaLaTeX}}% may have been patched by metalogo
```

\XeTeX
\XeLaTeX

XeTeX, XeLaTeX

xetexlogo is a css class which aligns the backwards E in XeTeX and spaces TeX appropriately.

xelatexlogo is a css class which aligns the backwards E in XeLaTeX and spaces LaTeX appropriately.

```
\newrobustcmd*{\LWR@HTML@Xe}
    {%
        X%
        \InlineClass{xelatexlogosub}{\HTMLunicode{18e}}%
    }
\AtBeginDocument{\LWR@formatted{Xe}}% may have been patched by metalogo

\newrobustcmd*{\LWR@HTML@XeTeX}{\InlineClass{xelatexlogo}{\Xe}\TeX}
\AtBeginDocument{\LWR@formatted{XeTeX}}% may have been patched by metalogo

\newrobustcmd*{\LWR@HTML@XeLaTeX}{\InlineClass{xelatexlogo}{\Xe}\LaTeX}
\AtBeginDocument{\LWR@formatted{XeLaTeX}}% may have been patched by metalogo
```

\ConTeXt

ConTeXt

```
\newrobustcmd*{\LWR@HTML@ConTeXt}{%
    \InlineClass{latexlogofont}{Con}\TeX{}%
    \InlineClass{latexlogofont}{t}%
}
\LWR@formatted{ConTeXt}
```

\BibTeX
\MakeIndex

BibTeX, *MakeIndex*

```
\newrobustcmd*{\LWR@HTML@BibTeX}
    {\InlineClass{latexlogofont}{B\textsc{ib}}\TeX}
\LWR@formatted{BibTeX}

\newrobustcmd*{\LWR@HTML@MakeIndex}
    {\InlineClass{latexlogofont}{\textit{MakeIndex}}}
\LWR@formatted{MakeIndex}
```

\AmS

$\mathcal{AMS}$

amslogo is a css class used for the $\mathcal{AMS}$ logo.

```
\AtBeginDocument{%
\newrobustcmd*{\LWR@HTML@AmS}
{%
    \InlineClass{amslogo}{%
        \textit{%
            A%
            \InlineClass{latexlogosub}{M}%
```

```
            S%
        }%
    }%
}%
\LWR@formatted{AmS}
}
```

\MiKTeX MiKTEX

```
\newrobustcmd*{\LWR@HTML@MiKTeX}{\InlineClass{latexlogofont}{MiK}\TeX}
\LWR@formatted{MiKTeX}
```

\LyX LyX

lyxlogo is a css class used for the LyX logo.

```
\newrobustcmd*{\LWR@HTML@LyX}{\InlineClass{lyxlogo}{LyX}}
\LWR@formatted{LyX}
```

```
\end{warpHTML}
```

94 \AtBeginDocument, \AtEndDocument

for HTML output:

```
\begin{warpHTML}
```

\LWR@LwarpStart
\LWR@LwarpEnd

Automatically sets up the HTML-related actions for the start and end of the document.

```
\AfterEndPreamble{\LWR@LwarpStart}
\AtEndDocument{\LWR@LwarpEnd}
```

```
\end{warpHTML}
```

95 Loading KOMA-SCRIPT class patches

Load patches to koma-script.

for HTML output:

```
\begin{warpHTML}
```

```
\@ifclassloaded{scrbook}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrartcl}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrreprt}{\RequirePackage{lwarp-patch-komascript}}{}
```

```
\end{warpHTML}
```

96 Loading MEMOIR class patches

Load patches to memoir.

for HTML output:
```
\begin{warpHTML}
\@ifclassloaded{memoir}{\RequirePackage{lwarp-patch-memoir}}{}
\end{warpHTML}
```

97 ut* class patches

Load patches to uj* and ut* classes, as well as ltj* classes.

for HTML output:
```
\begin{warpHTML}
\newcommand*{\LWR@patchujtclasses}{
```

uj/t does not use \partname

```
    \def\@partnameformat{}

    \def\@partcntformat##1{%
        \prepartname%
        \csname the##1\endcsname%
        \postpartname%
        \quad%
    }
    \@ifundefined{chapter}{}{
        \def\@chapcntformat##1{%
            \prechaptername%
            \csname the##1\endcsname%
            \postchaptername%
            \quad%
        }
    }
```

Use decimal points instead of centered dots:

```
    \renewcommand{\thepart}{\@Roman\c@part}
    \@ifundefined{chapter}{
        \renewcommand{\thesection}{\@arabic\c@section}
    }{
        \renewcommand{\thechapter}{\@arabic\c@chapter}
        \renewcommand{\thesection}{\thechapter.\@arabic\c@section}
    }
    \renewcommand{\thesubsection}{\thesection.\@arabic\c@subsection}
    \renewcommand{\thesubsubsection}{%
    \thesubsection.\@arabic\c@subsubsection}
    \renewcommand{\theparagraph}{%
```

```
    \thesubsubsection.\@arabic\c@paragraph}
    \renewcommand{\thesubparagraph}{%
    \theparagraph.\@arabic\c@subparagraph}
    \@ifundefined{chapter}{
        \renewcommand{\thefigure}{\@arabic\c@figure}
        \renewcommand{\thetable}{\@arabic\c@table}
    }{
        \renewcommand{\thefigure}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@figure}
        \renewcommand{\thetable}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@table}
    }
}

\@ifclassloaded{ujarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{utarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{utbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{utreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjskiyou}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjspf}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtreport}{\LWR@patchujtclasses}{}

\end{warpHTML}
```

98 CTEX patches

Patches for ctex and related classes, which are loaded before lwarp.

All CTEX classes and the ctex package seem to load ctexpatch, so its presence is used to decide whether to have lwarp patch CTEX.

for HTML output:

```
\begin{warpHTML}
```

`\AtBeginDocument` in case the user set `FileSectionNames` in the preamble.

```
\AtBeginDocument{
    \@ifpackageloaded{ctexpatch}{%
        \def\@partcntformat#1{%
            \LWR@isolate{\CTEX@partname}~%
            \CTEX@part@aftername%
        }%

```

```
        \def\@partnameformat{}

        \def\@chapcntformat#1{%
            \LWR@isolate{\CTEX@chaptername}~%
            \CTEX@chapter@aftername%
        }%
    }{}
}
\end{warpHTML}
```

99 kotexutf patches

Patch for kotexutf, which is loaded before lwarp.

kotexutf's `\@setref` was conflicting with lwarp's cross references.

for HTML output:

```
\begin{warpHTML}
```

If kotexutf's version of `\@setref` is detected, it is reverted to the original.

```
\AtBeginDocument{
\@ifpackageloaded{kotexutf}{%
    \def\LWR@kotexutf@setref#1#2#3{%
        \@setref@dhucs@orig{#1}{#2}{#3}%
      \ifx#1\relax\else
        \bgroup
        \dhucs@make@cjkchar@null
        \edef\@temp{\expandafter#2#1}\global\josatoks\expandafter{\@temp}%
        \egroup
      \fi%
    }%

    \ifdefequal{\@setref}{\LWR@kotexutf@setref}{
        \let\@setref\@setref@dhucs@orig
    }{}
}{}
}
```

```
\end{warpHTML}
```

File 2 **lwarp-2in1.sty**

§ 100 Package 2in1

Pkg 2in1 2in1 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2in1}
```

File 3 **lwarp-2up.sty**

§ 101 Package 2up

Pkg 2up 2up is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2up}[2010/05/15]

\def\source#1#2#3{}
\def\target#1#2#3{}
\def\targetlayout#1{}
\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\def\twoupemptypage{}
\def\twoupclearpage{}
\def\twoupeject{}
\def\twouparticle{}
\def\twoupplain{}
\def\twouplegaltarget{}
\def\twouplandscape{}
\def\TwoupWrites{}
```

File 4 **lwarp-a4.sty**

§ 102 Package a4

Pkg a4 a4 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a4}[2004/04/15]

\newcommand*{\WideMargins}{}
```

File 5 **lwarp-a4wide.sty**

§ 103 Package a4wide

Pkg a4wide a4wide is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a4wide}[1994/08/30]
```

File 6 **lwarp-a5comb.sty**

§ 104 Package a5comb

Pkg a5comb a5comb is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a5comb}
```

File 7 **lwarp-abstract.sty**

§ 105 Package abstract

(*Emulates or patches code by* Peter Wilson.)

Pkg abstract abstract is supported and patched by lwarp.

⚠ missing toc If using the `number` option with file splits, be sure to place the table of contents before the abstract. The `number` option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

for HTML output: memoir provides an `abstract` environment even though it is not an article or report class. Meanwhile, lwarp loads book to emulate memoir, but book does not have an `abstract` environment, so when the abstract package is loaded for emulation there is no pre-existing `abstract` to redefine, which would cause an error. Thus, a null `abstract` is provide here:

```
\ProvideDocumentEnvironment{abstract}{}{}{}
```

Accept all options for lwarp-abstract:

```
\LWR@ProvidesPackagePass{abstract}[2009/06/08]

\AtBeginDocument{
\BeforeBeginEnvironment{abstract}{
\LWR@forcenewpage
\BlockClass{abstract}
}
```

```
\AfterEndEnvironment{abstract}{\endBlockClass}
}

\renewcommand{\@bsrunintitle}{%
\hspace*{\abstitleskip}%
{\abstractnamefont%
\InlineClass{abstractrunintitle}{\abstractname}%
\@bslabeldelim}%
}

\@ifclassloaded{memoir}
{
  \renewenvironment{abstract}{%
%     \titlepage
    \null\vfil
    \@beginparpenalty\@lowpenalty
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
            \@endparpenalty\@M
          \end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
    }
}{% not memoir
\if@titlepage
  \renewenvironment{abstract}{%
%     \titlepage
    \null\vfil
    \@beginparpenalty\@lowpenalty
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
            \@endparpenalty\@M
          \end\absnamepos%
```

```
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
    }
\else
  \renewenvironment{abstract}{%
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
\begin{\absnamepos}%
\abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
\end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}}
\fi
}% not memoir
```

File 8 **lwarp-academicons.sty**

§ 106 Package

academicons

(*Emulates or patches code by* Diogo A. B. Fernandes.)

Pkg academicons academicons is patched for use by lwarp.

If \aiicon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{academicons}[2018/06/27]

\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@academicons@orig@AI\AI

\newcommand*{\LWR@academicons@symbol}[1]{%
    \begin{lateximage}*[academicon][academicons#1]%
    \begingroup%
```

```
    \LWR@academicons@orig@AI%
    \LWR@orig@symbol{#1}%
    \endgroup%
    \end{lateximage}%
}

\renewcommand*{\AI}{%
    \LetLtxMacro\symbol\LWR@academicons@symbol%
}

\renewcommand*{\aiicon}[1]
{%
    \begin{lateximage}*[#1 icon][academicons#1]%
    \AI\csname aiicon@#1\endcsname%
    \end{lateximage}%
}
```

File 9 **lwarp-accsupp.sty**

§ 107 Package accsupp

Pkg accsupp accsupp is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{accsupp}[2018/03/28]

\newcommand*{\BeginAccSupp}[1]{}
\newcommand*{\EndAccSupp}[1]{}
```

File 10 **lwarp-acro.sty**

§ 108 Package acro

(*Emulates or patches code by* Clemens Niederberger.)

Pkg acro acro is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{acro}[2017/01/30]
```

\DeclareAcronym is used in the preamble, where lwarp has not yet made the dollar active, so temporarily enable lwarp math catcode just for this definition:

```
\ExplSyntaxOn
\NewDocumentCommand \LWR@DeclareAcronym {mm}
{
    \acro_declare_acronym:nn {#1} {#2}
    \catcode`\$=3% lwarp
}
\ExplSyntaxOff

```

```
\RenewDocumentCommand{\DeclareAcronym}{}{
    \catcode`\$=\active% lwarp
    \LWR@DeclareAcronym
}
```

Modified to activate the current font:

```
\ExplSyntaxOn
\@ifpackagelater{acro}{2019/09/23}%
{% v2.10 or later
\cs_gset_protected:Npn \__acro_typeset:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \use:x
        {
          \bool_if:cTF {l__acro_custom_#1_format_bool}
            { \exp_not:v {l__acro_custom_#1_format_tl} }
            { \exp_not:v {l__acro_#1_format_tl} }
            {\exp_not:N\LWR@textcurrentfont{#2}}%   lwarp
        }
    \group_end:
  }

\cs_gset_protected:Npn \__acro_ending_format:nn #1#2
  {
    \bool_if:NTF \l__acro_include_endings_format_bool
      {
        \str_case:nn {#1}
          {
            {long}
            {
              \bool_if:NTF \l__acro_custom_long_format_bool
                { \l__acro_custom_long_format_tl }
                {
                  \bool_if:NTF \l__acro_first_instance_bool
                    { \l__acro_first_long_format_tl }
                    { \l__acro_long_format_tl }
                }
            }
            {short}
            {
              \bool_if:NTF \l__acro_custom_short_format_bool
                { \l__acro_custom_short_format_tl }
                { \l__acro_short_format_tl }
            }
            {alt}
            {
              \bool_if:NTF \l__acro_custom_alt_format_bool
                { \l__acro_custom_alt_format_tl }
                { \l__acro_alt_format_tl }
            }
          }
      }
      { \use:n }
```

```
      {\exp_not:N\LWR@textcurrentfont{#2}}% lwarp
  }
}% v2.10 or later
{% before v2.10
\cs_gset_protected:Npn \acro_write_short:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_short_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_alt:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_alt_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_long:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_long_format_bool
        { \l__acro_custom_long_format_tl }
        { \use:n }
      {
        \use:x
          {
            \exp_not:n {#1}
            {
              \bool_if:NTF \l__acro_first_upper_bool
                { \exp_not:N \__acro_first_upper_case:n { \exp_not:n {
                    \LWR@textcurrentfont{#2}% lwarp
                } } }
                { \exp_not:n {\LWR@textcurrentfont{#2}} }% lwarp
            }
          }
      }
    \group_end:
  }
}% before v2.10
\ExplSyntaxOff
```

File 11 **lwarp-acronym.sty**

§ 109 Package

acronym

(*Emulates or patches code by* Tobias Oetiker.)

Pkg acronym acronym is patched for use by lwarp.

⚠ multiply-defined labels `\acresetall` does not work with cleveref, causing multiply-defined labels. lwarp patches acronym for HTML, but not for print mode.

for HTML output:

```
\LWR@ProvidesPackagePass{acronym}[2015/03/21]
```

Uses `\textit` instead of `\itshape`:

```
\renewcommand{\acfia}[1]{%
  {\textit{\AC@acl{#1}}} (\ifAC@starred\acs*{#1}\else\acs{#1}\fi)}
```

Removes the mbox to allow math inside:

```
\renewcommand*\AC@acs[1]{%
%     \mbox{
 \expandafter\AC@get\csname fn@#1\endcsname\@firstoftwo{#1}}
% }
```

Fix for acronym labels in the captions of floats.

```
\renewcommand{\@starttoc}[1]{
\LWR@htmlelementclass{nav}{#1}
\LetLtxMacro\@verridelabel\@gobble
\LWR@orig@starttoc{#1}
\LWR@htmlelementclassend{nav}{#1}
}
```

Modified for cleveref and lwarp:

```
\renewcommand*\AC@und@newl@bel[3]{%
    \@ifundefined{#1@#3}%
    {%
        \global\expandafter\let\csname#2@#3\endcsname\@nnil
        \global\expandafter\let\csname#2@#3@lwarp\endcsname\@nnil% lwarp
        \global\expandafter\let\csname#2@#3@cref\endcsname\@nnil% lwarp
    }%
    {%
        \global\expandafter\let\csname#1@#3\endcsname\relax
        \global\expandafter\let\csname#1@#3@lwarp\endcsname\relax% lwarp
        \global\expandafter\let\csname#1@#3@cref\endcsname\relax% lwarp
    }%
}%
```

File 12 **lwarp-adjmulticol.sty**

§ 110 Package

adjmulticol

(*Emulates or patches code by* Boris Veytsman.)

Pkg adjmulticol adjmulticol is emulated.

Emulation similar to multicols is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, lwarp allows a variable number of columns up to three.

for HTML output:

```
\LWR@ProvidesPackageDrop{adjmulticol}[2012/01/20]
\RequirePackage{multicol}
```

adjmulticols * {⟨*numcols*⟩} {⟨*left margi*⟩} {⟨*right margin*⟩}

```
\NewDocumentEnvironment{adjmulticols}{s m m m}
{%
```

Compute the margins, and limit to positive only:

```
\setlength{\LWR@templengthone}{#3}%
\ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{}%
\setlength{\LWR@templengthtwo}{#4}
\ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{}%
```

If one column is specified, use a of class singlecolumn, else use multicols:

```
\newcommand*{\LWR@mcolstype}{multicols}%
\ifnumcomp{#2}{=}{1}{\renewcommand*{\LWR@mcolstype}{singlecolumn}}{}%
```

Help avoid page overflow:

```
\LWR@forcenewpage%
```

Create the with the given margin and class:

```
\BlockClass[%
\LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
\LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%
]{\LWR@mcolstype}%
}
{\endBlockClass}
```

File 13 **lwarp-addlines.sty**

§ 111 Package addlines

(*Emulates or patches code by* Will Robertson.)

Pkg addlines addlines is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{addlines}[2018/12/05]

\newcommand\addlines{\@ifstar\addlines@a\addlines@a}
\newcommand\addlines@a[1][1]{}
\let\addline\addlines
\newcommand\removelines{\@ifstar\removelines@a\removelines@a}
\newcommand\removelines@a[1][1]{}
\let\removeline\removelines
\newcommand\squeezepage[1][0]{}
```

File 14 **lwarp-afterpage.sty**

§ 112 Package afterpage

(*Emulates or patches code by* David Carlisle.)

Pkg afterpage afterpage is emulated.

for HTML output: Discard all options for lwarp-afterpage:

```
\LWR@ProvidesPackageDrop{afterpage}[2014/10/28]

\newcommand{\afterpage}[1]{#1}
```

File 15 **lwarp-algorithm2e.sty**

§ 113 Package algorithm2e

(*Emulates or patches code by* Christophe Fiorio.)

Pkg algorithm2e algorithm2e is patched for use by lwarp.

For print output, captions are placed according to package options, but for HTML output captions are placed where used. Therefore, to have captions appear at the top of the algorithms for both print and HTML, place each captions at the top of each algorithm.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithm2e}[2017/07/18]
```

For the list-of entries:

```
\renewcommand{\l@algocf}[2]{\hypertocfloat{1}{algocf}{loa}{#1}{#2}}
```

Select the lwarp float style according to the algorithm2e style:

```
\newcommand*{\LWR@floatstyle@algocf}{ruled}

\ifdefstring{\algocf@style}{boxed}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxed}
}{}

\ifdefstring{\algocf@style}{boxruled}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxruled}
}{}

\ifdefstring{\algocf@style}{plain}{%
\renewcommand*{\LWR@floatstyle@algocf}{plain}
}{}
```

Paragraph handling to allow line numbers under certain conditions:

```
\newbool{LWR@algocf@dopars}
\booltrue{LWR@algocf@dopars}

\renewcommand{\algocf@everypar}{%
\ifbool{LWR@algocf@dopars}{%
    \ifbool{LWR@doingstartpars}{%
        \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
            {}%
            {%
                \algocf@everyparnl\algocf@everyparhanging%
            }%
    }{}%
}{}%
}
```

lwarp caption handling:

```
\renewcommand{\algocf@makecaption}[2]{%
\LWR@HTML@caption@begin{algocf}%
\LWR@isolate{\algocf@captiontext{#1}{#2}}%
\LWR@HTML@caption@end%
}
```

Print any caption where it is declared:

```
\renewcommand{\algocf@makecaption@plain}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@boxed}[2]{%
    \LWR@HTML@caption@begin{algocf}%
```

```
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@ruled}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}
```

Turn off line numbering while making the caption:

```
\long\def\algocf@latexcaption#1[#2]#3{% original definition of caption
\boolfalse{LWR@algocf@dopars}%  lwarp
  \par%
  \addcontentsline{\csname ext@#1\endcsname}{#1}%
 {\protect\numberline{\csname the#1\endcsname}{\ignorespaces \LWR@isolate{#2}}}%
  \begingroup%
  \@parboxrestore%
  \if@minipage%
    \@setminipage%
  \fi%
  \normalsize%
  \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par%
  \endgroup%
\booltrue{LWR@algocf@dopars}%   lwarp
}
```

Line numbers are printed in a of class `alg2elinenumber`:

```
\renewcommand{\algocf@printnl}[1]{%
    \InlineClass{alg2elinenumber}{\NlSty{#1}}~%
}%
```

While initializing an algorithm environment, locally declare the style of a regular figure to be the same as the algorithm style, in case the `figure` option was used.

```
\preto\@algocf@init{%
  \edef\LWR@floatstyle@figure{\LWR@floatstyle@algocf}%
}
```

For lwarp, the algorithm is not assembled inside a box, since `latexi`mages would not work, so the captions are printed where declared.

```
\renewcommand{\@algocf@start}{%
    \let\@mathsemicolon=\;\def\;{\ifmmode\@mathsemicolon\else\@endalgoln\fi}%
%     \raggedright%
    \AlFnt{}%
    \booltrue{LWR@algocf@dopars}% lwarp
}

\renewcommand{\@algocf@finish}{%
    \boolfalse{LWR@algocf@dopars}% lwarp
    \lineskip\normallineskip\setlength{\skiptotal}{\@defaultskiptotal}%
```

```
    \let\;=\@mathsemicolon%
    \let\]=\@emathdisplay%
}
```

Use an HTML break:

```
\renewcommand{\BlankLine}{%
\LWR@stoppars%
\LWR@htmltagc{br /}%
\LWR@startpars%
}
```

Simplified for HTML. The paragraph handling must be preserved.

```
\renewcommand{\SetKwInOut}[2]{%
  \algocf@newcommand{#1}[1]{%
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@seteveryparhanging{\relax}}%
    \ifthenelse{\boolean{algocf@inoutnumbered}}%
        {\relax}%
        {\algocf@seteveryparnl{\relax}}%
    {%
            \KwSty{#2\algocf@typo:}%
        ~##1\par%
    }%
    \algocf@linesnumbered% reset the numbering of the lines
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@reseteveryparhanging}%
  }%
}%

\renewcommand{\ResetInOut}[1]{}%
```

Each of the following creates a of a given class, and turns off line numbering while creating the tags:

```
\renewcommand{\algocf@Vline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2evline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
\booltrue{LWR@algocf@dopars}%
}

\renewcommand{\algocf@Vsline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2evsline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
```

```
\booltrue{LWR@algocf@dopars}%
}

\renewcommand{\algocf@Noline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2enoline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
\booltrue{LWR@algocf@dopars}%
}
```

The [H] environment is converted to a regular float, which in HTML is placed where declared. Reusing the regular float allows the [H] version to reuse the ruled and boxed options.

```
\LetLtxMacro\algocf@Here\algocf
\LetLtxMacro\endalgocf@Here\endalgocf
```

File 16 **lwarp-algorithmicx.sty**

§ 114 Package

algorithmicx

(*Emulates or patches code by* Szász János.)

Pkg algorithmicx algorithmicx is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithmicx}[2005/04/27]
```

Inside the algorithmic environment, level indenting is converted to a of the required length, and comments are placed inside a which is floated right.

⚠ package conflicts If using \newfloat, trivfloat, and/or algorithmicx together, see section 488.1.

for HTML output:

```
\begin{warpHTML}

\AtBeginEnvironment{algorithmic}{%
%
\let\origALG@doentity\ALG@doentity%
%
\renewcommand*{\ALG@doentity}{%
\origALG@doentity%
\LWR@htmltagc{%
span style="width:\LWR@printlength{\ALG@thistlm}; display:inline-block;"%
}%
\ifbool{FormatWP}{%
\setlength{\LWR@templengthone}{\the\ALG@thistlm}%
\whiledo{\lengthtest{\LWR@templengthone>1em}}{%
\quad%
\addtolength{\LWR@templengthone}{-1em}%
}%
```

```
}{}%
\LWR@htmltagc{/span}%
}%

\let\LWR@origComment\Comment%

\renewcommand{\Comment}[1]{%
    \InlineClass{floatright}{\LWR@origComment{#1}}%
}%
}

\renewcommand\algorithmiccomment[1]{%
\hfill\HTMLunicode{25B7} #1% white right triangle
}%

\end{warpHTML}
```

File 17 **lwarp-alltt.sty**

§ 115 Package alltt

(*Emulates or patches code by* Johannes Braams.)

Pkg alltt alltt is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{alltt}[1997/06/16]

\AfterEndPreamble{
\LWR@traceinfo{Patching alltt.}
\AtBeginEnvironment{alltt}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{alltt}%
}
\AfterEndEnvironment{alltt}{%
    \LWR@afterendverbatim{2}%
}
}
```

File 18 **lwarp-amsmath.sty**

§ 116 Package amsmath

(*Emulates or patches code by* American Mathematical Society, LaTeX3 Project.)

Pkg amsmath amsmath is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{amsmath}[2017/09/02]
```

Patches to allow `\eqref` inside a caption:

```
\def\maketag@@@#1{\text{#1}}
\def\tagform@#1{\maketag@@@{(\ignorespaces#1\unskip)}}
```

Patches for $\mathcal{AMS}$ math `\tag` macro to remember the first tag:

```
\ifbool{mathjax}{}{% not mathjax

\LetLtxMacro\LWR@origmake@df@tag@@\make@df@tag@@
\LetLtxMacro\LWR@origmake@df@tag@@@\make@df@tag@@@

\renewcommand*{\make@df@tag@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@{#1}%
}

\renewcommand*{\make@df@tag@@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@@{#1}%
}

}% not mathjax
```

The following $\mathcal{AMS}$ environments are patched in-place:

`\LWR@amsmathenv@@before` {⟨*environment name*⟩}

Embeds the environment inside a `lateximage`.

```
\newcommand*{\LWR@amsmathenv@@before}[1]{%
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{#1}]*
    \LWR@applyxfakebold%
}
```

`\LWR@amsmathenv@before` {⟨*environment name*⟩}

Embeds the environment with MathJax or a `lateximage`.

```
\newcommand*{\LWR@amsmathenv@before}[1]{%
    \LWR@stoppars%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {
        \LWR@syncmathjax
        \boolfalse{LWR@amsmultline}
        \ifstrequal{#1}{multline}{\booltrue{LWR@amsmultline}}{}
        \ifstrequal{#1}{multline*}{\booltrue{LWR@amsmultline}}{}
```

⚠ autonum's "+" environments are not supported by MathJax.

```
        \LWR@beginhideamsmath
    }
    {
        \LWR@amsmathenv@@before{#1}
    }
}
```

\LWR@amsmathenv@@after

Embeds the environment inside a lateximage.

```
\newcommand*{\LWR@amsmathenv@@after}{%
    \end{lateximage}\end{BlockClass}\LWR@startpars%
}
```

\LWR@amsmathenv@after {⟨*environment name*⟩}

Embeds the environment with MathJax or a lateximage.

```
\newcommand*{\LWR@amsmathenv@after}[1]{%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {
        \LWR@endhideamsmath
        \boolfalse{LWR@amsmultline}
        \LWR@addmathjax{#1}{\the\@envbody}
    }
    {\LWR@amsmathenv@@after}
```

Clear the single-use alt text:

```
\gdef\LWR@ThisAltText{}%
}
```

Env multline

```
\BeforeBeginEnvironment{multline}{\LWR@amsmathenv@before{multline}}

\AfterEndEnvironment{multline}{\LWR@amsmathenv@after{multline}}
```

Env multline*

```
\BeforeBeginEnvironment{multline*}{\LWR@amsmathenv@before{multline*}}

\AfterEndEnvironment{multline*}{\LWR@amsmathenv@after{multline*}}

```

Env gather

```
\BeforeBeginEnvironment{gather}{\LWR@amsmathenv@before{gather}}

\AfterEndEnvironment{gather}{\LWR@amsmathenv@after{gather}}
```

Env gather*

```
\BeforeBeginEnvironment{gather*}{\LWR@amsmathenv@before{gather*}}

\AfterEndEnvironment{gather*}{\LWR@amsmathenv@after{gather*}}
```

Env align

```
\BeforeBeginEnvironment{align}{\LWR@amsmathenv@before{align}}

\AfterEndEnvironment{align}{\LWR@amsmathenv@after{align}}
```

Env `align*`

```
\BeforeBeginEnvironment{align*}{\LWR@amsmathenv@before{align*}}

\AfterEndEnvironment{align*}{\LWR@amsmathenv@after{align*}}
```

Env `flalign`

```
\BeforeBeginEnvironment{flalign}{\LWR@amsmathenv@before{flalign}}

\AfterEndEnvironment{flalign}{\LWR@amsmathenv@after{flalign}}
```

Env `flalign*`

```
\BeforeBeginEnvironment{flalign*}{\LWR@amsmathenv@before{flalign*}}

\AfterEndEnvironment{flalign*}{\LWR@amsmathenv@after{flalign*}}
```

Env `alignat`

```
\BeforeBeginEnvironment{alignat}{\LWR@amsmathenv@before{alignat}}

\AfterEndEnvironment{alignat}{\LWR@amsmathenv@after{alignat}}
```

Env `alignat*`

```
\BeforeBeginEnvironment{alignat*}{\LWR@amsmathenv@before{alignat*}}

\AfterEndEnvironment{alignat*}{\LWR@amsmathenv@after{alignat*}}
```

File 19 **`lwarp-amsthm.sty`**

§ 117 Package

amsthm

(*Emulates or patches code by* Publications Technical Group — American Mathematical Society.)

The original source code is located in `amsclass.dtx`, and printed in `amsclass.pdf`.

Pkg `amsthm` amsthm is patched for use by lwarp.

for HTML output: amsthm must be loaded before mdframed:

```
\@ifpackageloaded{mdframed}{
    \PackageError{lwarp}
    {Package mdframed must be loaded after package amsthm}
```

Table 14: amsthm package — css styling of theorems and proofs

Theorem: of class amsthmbody<theoremstyle>

Theorem Name: of class amsthmname<theoremtyle>

Theorem Number: of class amsthmnumber<theoremstyle>

Theorem Note: of class amsthmnote<theoremstyle>

Proof: of class amsthmproof

Proof Name: of class amsthmproofname

where <theoremstyle> is plain, definition, etc.

```
    {%
        Move \detokenize{\usepackage}{amsthm} before
        \detokenize{\usepackage}{mdframed}.\MessageBreak
        Package amsthm may be loaded by something else,\MessageBreak
        which must also be moved before mdframed.%
    }
}
{}

\LWR@ProvidesPackagePass{amsthm}[2017/10/31]
```

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\renewcommand{\theoremstyle}[1]{%
  \@ifundefined{th@#1}{%
    \PackageWarning{amsthm}{Unknown theoremstyle `#1'}%
    \thm@style{plain}%
    \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
  }{%
    \thm@style{#1}%
    \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
  }%
}
```

Patched to remember the style for this theorem type:

```
\def\@xnthm#1#2{%
  \csedef{LWR@thmstyle#2}{\LWR@newtheoremstyle}% lwarp
  \let\@tempa\relax
  \@xp\@ifdefinable\csname #2\endcsname{%
    \global\@xp\let\csname end#2\endcsname\@endtheorem
    \ifx *#1% unnumbered, need to get one more mandatory arg
      \edef\@tempa##1{%
```

```
        \gdef\@xp\@nx\csname#2\endcsname{%
          \@nx\@thm{\@xp\@nx\csname th@\the\thm@style\endcsname}%
            {}{##1}}}%
    \else % numbered theorem, need to check for optional arg
      \def\@tempa{\@oparg{\@ynthm{#2}}[]}%
    \fi
   \AtBeginEnvironment{#2}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#2}}}% lwarp
  }%
  \@tempa
}
```

Patched to enclose with css:

```
\newcommand{\LWR@haveamsthmname}{
\renewcommand{\thmname}[1]{\InlineClass{amsthmname\LWR@thisthmstyle}{##1}}
}

\newcommand{\LWR@haveamsthmnumber}{
\renewcommand{\thmnumber}[1]{\InlineClass{amsthmnumber\LWR@thisthmstyle}{##1}}
}

\newcommand{\LWR@haveamsthmnote}{
\renewcommand{\thmnote}[1]{\InlineClass{amsthmnote\LWR@thisthmstyle}{##1}}
}

\LWR@haveamsthmname
\LWR@haveamsthmnumber
\LWR@haveamsthmnote
```

Patches for css:

```
\def\@begintheorem#1#2[#3]{%
    \item[
%   \deferred@thm@head{
%     \the\thm@headfont \thm@indent
    \@ifempty{#1}{\let\thmname\@gobble}{\LWR@haveamsthmname}% lwarp
    \@ifempty{#2}{\let\thmnumber\@gobble}{\LWR@haveamsthmnumber}% lwarp
    \@ifempty{#3}{\let\thmnote\@gobble}{\LWR@haveamsthmnote}% lwarp
    \thm@swap\swappedhead\thmhead{#1}{#2}{#3}%
    \the\thm@headpunct~
    \thmheadnl % possibly a newline.
    \hskip\thm@headsep
%   }%
    ]
  \ignorespaces}
```

Patched for css:

```
\def\@thm#1#2#3{%
  \ifhmode\unskip\unskip\par\fi
  \normalfont
  \LWR@forcenewpage% lwarp
  \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
  \trivlist
  \let\thmheadnl\relax
```

```
  \let\thm@swap\@gobble
  \thm@notefont{\fontseries\mddefault\upshape}%
  \thm@headpunct{.}% add period after heading
  \thm@headsep 5\p@ plus\p@ minus\p@\relax
  \thm@space@setup
  #1% style overrides
  \@topsep \thm@preskip               % used by thm head
  \@topsepadd \thm@postskip           % used by \@endparenv
  \def\@tempa{#2}\ifx\@empty\@tempa
    \def\@tempa{\@oparg{\@begintheorem{#3}{}}[]}%
  \else
    \refstepcounter{#2}%
    \def\@tempa{\@oparg{\@begintheorem{#3}{\csname the#2\endcsname}}[]}%
  \fi
  \@tempa
}
```

cleveref patches `\@thm` to do `\cref@thmoptarg` if an optional argument is given. lwarp then patches `\cref@thmoptarg` `\AtBeginDocument`.

```
\AtBeginDocument{%
\def\cref@thmoptarg[#1]#2#3#4{%
    \ifhmode\unskip\unskip\par\fi%
    \normalfont%
    \LWR@forcenewpage% lwarp
    \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
    \trivlist%
    \let\thmheadnl\relax%
    \let\thm@swap\@gobble%
    \thm@notefont{\fontseries\mddefault\upshape}%
    \thm@headpunct{.}% add period after heading
    \thm@headsep 5\p@ plus\p@ minus\p@\relax%
    \thm@space@setup%
    #2% style overrides
    \@topsep \thm@preskip               % used by thm head
    \@topsepadd \thm@postskip           % used by \@endparenv
    \def\@tempa{#3}\ifx\@empty\@tempa%
        \def\@tempa{\@oparg{\@begintheorem{#4}{}}[]}%
    \else%
        \refstepcounter[#1]{#3}%  <<< cleveref modification
        \def\@tempa{\@oparg{\@begintheorem{#4}{\csname the#3\endcsname}}[]}%
    \fi%
    \@tempa
}%
}% AtBeginDocument

\def\@endtheorem{\endtrivlist\endBlockClass\@endpefalse }
```

Proof QED symbol:

```
\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box
```

```
\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\openbox\LWR@orig@openbox%
\LetLtxMacro\blacksquare\LWR@orig@blacksquare%
\LetLtxMacro\Box\LWR@orig@Box%
}% appto
}{}% @ifundefined
}% AtBeginDocument
```

Patched for css:

```
\renewenvironment{proof}[1][\proofname]{\par
\LWR@forcenewpage% lwarp
    \BlockClass{amsthmproof}% lwarp
  \pushQED{\qed}%
  \normalfont \topsep6\p@\@plus6\p@\relax
  \trivlist
  \item[
        \InlineClass{amsthmproofname}{#1\@addpunct{.}}]\ignorespaces% changes
}{%
  \InlineClass{theoremendmark}{\popQED}\endtrivlist%
  \endBlockClass% lwarp
  \@endpefalse
}
```

File 20 **lwarp-anonchap.sty**

§ 118 Package

anonchap

(*Emulates or patches code by* Peter Wilson.)

Pkg anonchap anonchap is emulated.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

The code is shared by tocbibind.

for HTML output:

```
\LWR@ProvidesPackageDrop{anonchap}[2009/08/03]

\newcommand{\simplechapter}[1][\@empty]{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\newcommand{\restorechapter}{%
\let\@chapcntformat\@seccntformat%
```

```
10 }
```

File 21 **lwarp-anysize.sty**

§ 119 Package anysize

(*Emulates or patches code by* Michael Salzenberg, Thomas Esser.)

Pkg anysize anysize is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{anysize}[1994/08/13]

2 \def\papersize#1#2{}
3 \def\marginsize#1#2#3#4{}
```

File 22 **lwarp-appendix.sty**

§ 120 Package appendix

(*Emulates or patches code by* Peter Wilson.)

Pkg appendix appendix is patched for use by lwarp.

⚠ incorrect TOC link During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

for HTML output:

```
1 \LWR@ProvidesPackagePass{appendix}[2009/09/02]

2 \renewcommand*{\@chap@pppage}{%
3 \part*{\appendixpagename}
4  \if@dotoc@pp
5  \addappheadtotoc
6  \fi
7 }
8
9 \renewcommand*{\@sec@pppage}{%
10 \part*{\appendixpagename}
11  \if@dotoc@pp
12  \addappheadtotoc
13  \fi
14 }
```

File 23 **lwarp-ar.sty**

§ 121 Package ar

(*Emulates or patches code by* Agostino De Marco.)

Pkg ar ar is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ar}[2012/01/23]
```

Measure and print the width of the supplied glyph.

```
\newlength{\LWR@ar@width}

\newcommand*{\LWR@ar@printwidth}[1]{%
    \setlength{\LWR@ar@width}{\widthof{#1}}%
    width:%
    \LWR@convertto{em}{\the\LWR@ar@width}em%
}
```

The HTML version of \AR:

```
\newrobustcmd*{\LWR@HTML@AR}{%
```

Start a hashed lateximage, additionally hashed by the font series, with a width depending on the given glyph:

```
    \begin{lateximage}*[AR][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@AR}]%
```

For text mode, set the font series according to the HTML font series:

```
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
```

Print the original glyph using the newly set font series:

```
    \LWR@print@AR%
```

Done.

```
    \end{lateximage}%
}
```

Combine the print and HTML versions:

```
\LWR@formatted{AR}

\newrobustcmd*{\LWR@HTML@ARb}{%
    \begin{lateximage}*[AR][b][\LWR@ar@printwidth{\LWR@print@ARb}]%
    \LWR@print@ARb%
    \end{lateximage}%
}
\LWR@formatted{ARb}

\newrobustcmd*{\LWR@HTML@ARss}{%
   \begin{lateximage}*[ARss][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@ARss}]%
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
    \LWR@print@ARss%
    \end{lateximage}%
}
\LWR@formatted{ARss}
```

```
\newrobustcmd*{\LWR@HTML@ARssb}{%
    \begin{lateximage}*[AR][ssb][\LWR@ar@printwidth{\LWR@print@ARssb}]%
    \LWR@print@ARssb%
    \end{lateximage}%
}
\LWR@formatted{ARssb}

\newrobustcmd*{\LWR@HTML@ARtt}{%
    \begin{lateximage}*[AR][tt][\LWR@ar@printwidth{\LWR@print@ARtt}]%
    \LWR@print@ARtt%
    \end{lateximage}%
}
\LWR@formatted{ARtt}
```

File 24 **lwarp-arabicfront.sty**

§ 122 Package arabicfront

Pkg arabicfront arabicfront is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{arabicfront}[2006/09/03]
```

File 25 **lwarp-array.sty**

§ 123 Package array

Pkg array array is used as-is for print output, and emulated for HTML.

plarray and plextarray do not affect `\firsthline` or `\lasthline`, and so are not affected by the following.

for HTML output: Remove the default nullfied macros:

```
\let\firsthline\relax
\let\lasthline\relax

\LWR@ProvidesPackagePass{array}[2018/12/30]

\newcommand*{\LWR@HTML@firsthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{firsthline}

\newcommand*{\LWR@HTML@lasthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{lasthline}

\providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
\LWR@formatted{tabularnewline}
```

File 26 **lwarp-arydshln.sty**

§ 124 Package

arydshln

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg arydshln

arydshln heavily patches tabular code, so the actual package is not used. arydshln is emulated for HTML `tabular`, and reverts to solid rules for SVG math `array` and `tabular` in a `lateximage`.

CSS is not able to display a double-dashed border, so a single-dashed rule is displayed as a single-dashed border, and a double-dashed rule is displayed as a thicker single-dashed border.

for HTML output:

array is required to allow `\newcolumn` below.

```
\RequirePackage{array}
```

```
\LWR@ProvidesPackageDrop{arydshln}[2018/09/26]
```

Ignored, but included for source compatibility:

```
\newdimen\dashlinedash \dashlinedash4pt %
\newdimen\dashlinegap \dashlinegap4pt %
\let\hdashlinewidth\dashlinedash
\let\hdashlinegap\dashlinegap

\def\ADLnullwide{}
\def\ADLsomewide{}
\def\ADLnullwidehline{}
\def\ADLsomewidehline{}

\def\ADLactivate{}
\def\ADLinactivate{}
\newcommand*{\ADLdrawingmode}[1]{}
\newcommand*{\ADLnoshorthanded}{}
\newcommand*{\dashgapcolor}[2][]{}
\newcommand*{\nodashgapcolor}{}
```

In a `lateximage`, revert to solid vertical rules:

```
\appto\LWR@restoreorigformatting{%
\newcolumntype{:}{|}%
\newcolumntype{;}[1]{|}%
\LetLtxMacro\hdashline\hline%
}
```

Some of these macros are already defined as temporary placeholders in the lwarp core, so they must be redefined here.

The emulated defaults also work for an emulated print mode inside a `lateximage`:

```
\def\hdashline{
%     \adl@hdashline\adl@ihdashline
    \adl@hdashline\adl@inactivehdl
}
\def\adl@hdashline#1{\noalign{\ifnum0=`}\fi
%         \ifadl@zwhrule \vskip-\arrayrulewidth
%         \else
%             \adl@hline\adl@connect\arrayrulewidth
                \hrule \@height \arrayrulewidth% lwarp
%         \fi
        \@ifnextchar[%]
                     {#1}%
                     {#1[%
%                          \dashlinedash/\dashlinegap
                        1pt/1pt
                     ]}}
% \def\adl@ihdashline[#1/#2]{\ifnum0=`{\fi}%
%         \multispan{\adl@columns}\unskip \adl@hcline\z@[#1/#2]%
%         \noalign{\ifnum0=`}\fi
%         \futurelet\@tempa\adl@xhline}
\def\adl@inactivehdl[#1/#2]{
%         \ifadl@zwhrule \vskip-\arrayrulewidth \fi
        \hrule\@height\arrayrulewidth
        \futurelet\@tempa\adl@xhline}
\def\adl@xhline{\ifx\@tempa\hline \adl@ixhline\fi
        \ifx\@tempa\hdashline \adl@ixhline\fi
        \ifnum0=`{\fi}}
\def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
\def\adl@hline#1#2{%
% \@tempcnta#2
%         \global\advance\adl@totalheight\@tempcnta
%         \xdef\adl@rowsL{\adl@rowsL
%                 (#1/\number\@tempcnta);}%
%         \xdef\adl@rowsR{\adl@rowsR
%                 (#1/\number\@tempcnta);}
}

\def\cdashline#1{\noalign{\ifnum0=`}\fi
        \@ifnextchar[%]
%                       {\adl@cdline[#1]}%
%                       {\adl@cdline[#1][\dashlinedash/\dashlinegap]}
                     {\adl@inactivecdl[#1]}%
                     {\adl@inactivecdl[#1][\dashlinedash/\dashlinegap]}
}

\def\adl@inactivecdl[#1-#2][#3]{\ifnum0=`{\fi}\cline{#1-#2}}
```

File 27 **lwarp-asymptote.sty**

§ 125 Package

asymptote

(*Emulates or patches code by* Andy Hammerlindl, John Bowman, Tom Prince.)

Pkg asymptote asymptote is patched for use by lwarp.

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

for HTML output:

```
\LWR@ProvidesPackagePass{asymptote}[2016/11/26]

\BeforeBeginEnvironment{asy}{%
    \begin{lateximage}[-asymptote-~\PackageDiagramAltText]%
}
\AfterEndEnvironment{asy}{\end{lateximage}}

\xpatchcmd{\asyinclude}
    {\begingroup}
    {\begin{lateximage}[-asymptote-~\PackageDiagramAltText]}
    {}
    {\LWR@patcherror{asymptote}{asyinclude-begingroup}}

\xpatchcmd{\asyinclude}
    {\endgroup}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{asymptote}{asyinclude-endgroup}}
```

File 28 **lwarp-atbegshi.sty**

§ 126 Package

atbegshi

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg atbegshi atbegshi is ignored.

for HTML output: Discard all options for lwarp-atbegshi:

```
\LWR@ProvidesPackageDrop{atbegshi}[2011/10/05]

\newcommand*{\AtBeginShipout}[1]{}
\newbox\AtBeginShipoutBox
\newcommand*{\AtBeginShipoutNext}[1]{}
\newcommand*{\AtBeginShipoutFirst}[1]{}
\newcommand*{\AtBeginShipoutDiscard}{}
\newcommand*{\AtBeginShipoutInit}{}
\newcommand*{\AtBeginShipoutAddToBox}[1]{}
\newcommand*{\AtBeginShipoutAddToBoxForeground}[1]{}
\newcommand*{\AtBeginShipoutUpperLeft}[1]{}
\newcommand*{\AtBeginShipoutUpperLeftForeground}[1]{}
\newcommand*{\AtBeginShipoutOriginalShipout}[1]{}
\def\AtBeginShipoutBoxWidth{0pt}
\def\AtBeginShipoutBoxHeight{0pt}
\def\AtBeginShipoutBoxDepth{0pt}

```

File 29 **lwarp-attachfile.sty**

§ 127 Package

attachfile

(*Emulates or patches code by* Scott Pakin.)

Pkg attachfile attachfile is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile}[2016/09/18]
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
            \detokenize\expandafter{\atfi@color@rgb}%
```

```
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an `\attachfile` reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \href{#1}{\LWR@attachfile@appearance}%
}
```

File 30 **lwarp-attachfile2.sty**

§ 128 Package

attachfile2

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg attachfile2 attachfile2 is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile2}[2016/05/16]
```

Adds memory of the selected color:

```
\def\LWR@attachfiletwo@color{}%

\define@key{AtFi}{color}{%
    \def\LWR@attachfiletwo@color{#1}%   lwarp
  \HyColor@AttachfileColor{#1}%
          \atfi@color@tex\atfi@color@inline\atfi@color@annot
          {attachfile2}{color}%
}
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
            \detokenize\expandafter{\LWR@attachfiletwo@color}%
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an `\attachfile` reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\def\atfi@set@appearance@icon{%
    \atfi@set@appearance{\csname atfi@acro\atfi@icon@icon\endcsname}%
}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \href{#1}{\LWR@attachfile@appearance}%
}
```

Modified for text color:

```
\DeclareRobustCommand{\notextattachfile}[2][]{%
  \begingroup
    \atfi@setup{#1}%
    \ifatfi@print
      \leavevmode
      \begingroup
        \HyColor@UseColor\atfi@color@tex
        \LWR@textcurrentcolor{#2}%      lwarp
% \strut
      \endgroup
%     \else
%       \sbox\ltx@zero{#2\strut}%
%       \makebox[\wd0]{}%
    \fi
  \endgroup
}
```

Modified to draw the icon:

```
\DeclareRobustCommand{\noattachfile}[1][]{%
  \begingroup
    \atfi@setup{#1}%
    \atfi@set@appearance@icon
    \ifatfi@print
        \LWR@attachfile@appearance%     lwarp
%       \expandafter
%       \atfi@refxform\csname atfi@appobj@\atfi@icon@icon\endcsname
%     \else
%       \makebox[\atfi@appearancewidth]{}%
    \fi
  \endgroup
}
```

File 31 **lwarp-authblk.sty**

§ 129 Package

authblk

(*Emulates or patches code by* Patrick W. Daly.)

Pkg authblk

authblk is patched for HTML.

package support

⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle

may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

(*Emulates or patches code by* Patrick W. Daly.)

for HTML output: Require that authblk be loaded before titling:

```
\@ifpackageloaded{titling}{
\PackageError{lwarp-authblk}
{Package authblk must be loaded before titling}
{Titling appends authblk's author macro, so authblk must be loaded first.}
}
{}
```

Load authblk:

```
\LWR@ProvidesPackagePass{authblk}[2001/02/27]
```

Patch to add a class for the affiliation:

```
\LetLtxMacro\LWRAB@affil\affil

\renewcommand{\affil}[2][]{%
\LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}
}
```

Create an HTML break for an \authorcr:

```
\renewcommand*{\authorcr}{\protect\LWR@newlinebr}
```

File 32 **lwarp-autonum.sty**

§ 130 Package

autonum

Pkg autonum autonum is ignored.

⚠ numbering All equations are numbered in HTML output.

MathJax does not support the "+" environments.

for HTML output:

```
\LWR@ProvidesPackageDrop{autonum}[2015/01/18]

\RequirePackage{amsmath}


\newenvironment{equation+}{\equation}{\endequation}


\newenvironment{gather+}{\gather}{\endgather}

\BeforeBeginEnvironment{gather+}{\LWR@amsmathenv@@before{gather+}}

\AfterEndEnvironment{gather+}{\LWR@amsmathenv@@after}
```

```
13
14
15 \newenvironment{multline+}{\multline}{\endmultline}
16
17 \BeforeBeginEnvironment{multline+}{\LWR@amsmathenv@@before{multline+}}
18
19 \AfterEndEnvironment{multline+}{\LWR@amsmathenv@@after}
20
21
22 \newenvironment{flalign+}{\flalign}{\endflalign}
23
24 \BeforeBeginEnvironment{flalign+}{\LWR@amsmathenv@@before{flaline+}}
25
26 \AfterEndEnvironment{flalign+}{\LWR@amsmathenv@@after}
27
28
29 \newenvironment{align+}{\align}{\endalign}
30
31 \BeforeBeginEnvironment{align+}{\LWR@amsmathenv@@before{aline+}}
32
33 \AfterEndEnvironment{align+}{\LWR@amsmathenv@@after}
34
35
36 \newenvironment{alignat+}{\alignat}{\endalignat}
37
38 \BeforeBeginEnvironment{alignat+}{\LWR@amsmathenv@@before{alineat+}}
39
40 \AfterEndEnvironment{alignat+}{\LWR@amsmathenv@@after}
41
42
43 \newenvironment{split+}{\split}{\endsplit}
```

File 33 **lwarp-axessibility.sty**

§ 131 Package axessibility

Pkg axessibility axessibility is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{axessibility}

2 \newcommand{\wrap}[1]{}
```

File 34 **lwarp-axodraw2.sty**

§ 132 Package axodraw2

(*Emulates or patches code by* John C. Collins, J.A.M. Vermaseren.)

Pkg axodraw2 axodraw2 is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{axodraw2}[2018/02/15]
```

```
\BeforeBeginEnvironment{axopicture}{%
    \begin{lateximage}[-axopicture-~\PackageDiagramAltText]%
}

\AfterEndEnvironment{axopicture}{\end{lateximage}}
```

File 35 **lwarp-backnaur.sty**

§ 133 Package backnaur

(*Emulates or patches code by* Adrian P. Robson.)

Pkg backnaur backnaur is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{backnaur}[2019/06/18]

\renewenvironment{bnf}{\eqnarray}{\endeqnarray}
\renewenvironment{bnf*}{\csuse{eqnarray*}}{\csuse{endeqnarray*}}
```

File 36 **lwarp-backref.sty**

§ 134 Package backref

(*Emulates or patches code by* David Carlisle and Sebastian Rahtz.)

Pkg backref backref is patched for use by lwarp.

⚠ loading Note that backref must be explicitly loaded, and is not automatically loaded by hyperref when generating HTML output.

for HTML output:

```
\LWR@ProvidesPackagePass{backref}[2016/05/21]
```

Force the `hyperref` option:

```
\def\backref{}\let\backrefxxx\hyper@section@backref
```

File 37 **lwarp-balance.sty**

§ 135 Package balance

(*Emulates or patches code by* Patrick W. Daly.)

Pkg balance balance is ignored.

for HTML output: Discard all options for lwarp-balance:

```
\LWR@ProvidesPackageDrop{balance}[1999/02/23]
```

```
\newcommand*{\balance}{}
\newcommand*{\nobalance}{}
```

File 38 **lwarp-bbding.sty**

§ 136 Package

bbding

(*Emulates or patches code by* Karel Horak, Peter Møller Neergaard.)

Pkg bbding bbding is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bbding}[1999/04/15]

\newcommand*{\LWR@bbdingsymbol}[2]{\HTMLunicode{#2}}

\newcommand{\LWR@HTML@ScissorRightBrokenBottom}{\LWR@bbdingsymbol{000}   {2701}}
\newcommand{\LWR@HTML@ScissorRight}{\LWR@bbdingsymbol{001}               {2702}}
\newcommand{\LWR@HTML@ScissorRightBrokenTop}{\LWR@bbdingsymbol{002}     {2703}}
\newcommand{\LWR@HTML@ScissorLeftBrokenBottom}{\LWR@bbdingsymbol{003}   {2701}}
\newcommand{\LWR@HTML@ScissorLeft}{\LWR@bbdingsymbol{004}                {2702}}
\newcommand{\LWR@HTML@ScissorLeftBrokenTop}{\LWR@bbdingsymbol{005}      {2703}}
\newcommand{\LWR@HTML@ScissorHollowRight}{\LWR@bbdingsymbol{006}        {2704}}
\newcommand{\LWR@HTML@ScissorHollowLeft}{\LWR@bbdingsymbol{007}         {2704}}
\newcommand{\LWR@HTML@Phone}{\LWR@bbdingsymbol{010}                     {260E}}
\newcommand{\LWR@HTML@PhoneHandset}{\LWR@bbdingsymbol{011}              {2706}}
\newcommand{\LWR@HTML@Tape}{\LWR@bbdingsymbol{012}                      {2707}}
\newcommand{\LWR@HTML@Plane}{\LWR@bbdingsymbol{013}                     {2708}}
\newcommand{\LWR@HTML@Envelope}{\LWR@bbdingsymbol{014}                  {2709}}
\newcommand{\LWR@HTML@HandCuffRight}{\LWR@bbdingsymbol{015}             {261B}}
\newcommand{\LWR@HTML@HandCuffLeft}{\LWR@bbdingsymbol{016}              {261A}}
\newcommand{\LWR@HTML@HandCuffRightUp}{\LWR@bbdingsymbol{017}           {261D}}
\newcommand{\LWR@HTML@HandCuffLeftUp}{\LWR@bbdingsymbol{020}            {261F}}
\newcommand{\LWR@HTML@HandRight}{\LWR@bbdingsymbol{021}                 {261E}}
\newcommand{\LWR@HTML@HandLeft}{\LWR@bbdingsymbol{022}                  {261C}}
\newcommand{\LWR@HTML@HandRightUp}{\LWR@bbdingsymbol{023}               {261D}}
\newcommand{\LWR@HTML@HandLeftUp}{\LWR@bbdingsymbol{024}                {261F}}
\newcommand{\LWR@HTML@Peace}{\LWR@bbdingsymbol{025}                     {270C}}
\newcommand{\LWR@HTML@HandPencilLeft}{\LWR@bbdingsymbol{026}            {270D}}
\newcommand{\LWR@HTML@PencilRight}{\LWR@bbdingsymbol{027}               {270F}}
\newcommand{\LWR@HTML@PencilLeft}{\LWR@bbdingsymbol{030}                {270F}}
\newcommand{\LWR@HTML@PencilRightUp}{\LWR@bbdingsymbol{031}             {2710}}
\newcommand{\LWR@HTML@PencilLeftUp}{\LWR@bbdingsymbol{032}              {2710}}
\newcommand{\LWR@HTML@PencilRightDown}{\LWR@bbdingsymbol{033}           {270E}}
\newcommand{\LWR@HTML@PencilLeftDown}{\LWR@bbdingsymbol{034}            {270E}}
\newcommand{\LWR@HTML@NibRight}{\LWR@bbdingsymbol{035}                  {2711}}
\newcommand{\LWR@HTML@NibLeft}{\LWR@bbdingsymbol{036}                   {2711}}
\newcommand{\LWR@HTML@NibSolidRight}{\LWR@bbdingsymbol{037}             {2712}}
\newcommand{\LWR@HTML@NibSolidLeft}{\LWR@bbdingsymbol{040}              {2712}}
\newcommand{\LWR@HTML@Checkmark}{\LWR@bbdingsymbol{041}                 {2713}}
\newcommand{\LWR@HTML@CheckmarkBold}{\LWR@bbdingsymbol{042}             {2714}}
\newcommand{\LWR@HTML@XSolid}{\LWR@bbdingsymbol{043}                    {2715}}
\newcommand{\LWR@HTML@XSolidBold}{\LWR@bbdingsymbol{044}                {2716}}
\newcommand{\LWR@HTML@XSolidBrush}{\LWR@bbdingsymbol{045}               {2717}}
```

```
\newcommand{\LWR@HTML@PlusOutline}{\LWR@bbdingsymbol{046}                {2719}}
\newcommand{\LWR@HTML@Plus}{\LWR@bbdingsymbol{047}                       {271A}}
\newcommand{\LWR@HTML@PlusCenterOpen}{\LWR@bbdingsymbol{050}             {271C}}
\newcommand{\LWR@HTML@PlusThinCenterOpen}{\LWR@bbdingsymbol{051}         {271B}}
\newcommand{\LWR@HTML@Cross}{\LWR@bbdingsymbol{052}                      {271D}}
\newcommand{\LWR@HTML@CrossOpenShadow}{\LWR@bbdingsymbol{053}            {271E}}
\newcommand{\LWR@HTML@CrossOutline}{\LWR@bbdingsymbol{054}               {271F}}
\newcommand{\LWR@HTML@CrossBoldOutline}{\LWR@bbdingsymbol{055}           {271F}}
\newcommand{\LWR@HTML@CrossMaltese}{\LWR@bbdingsymbol{056}               {2720}}
\newcommand{\LWR@HTML@DavidStarSolid}{\LWR@bbdingsymbol{057}             {2721}}
\newcommand{\LWR@HTML@DavidStar}{\LWR@bbdingsymbol{060}                  {2721}}
\newcommand{\LWR@HTML@FourAsterisk}{\LWR@bbdingsymbol{061}               {2722}}
\newcommand{\LWR@HTML@JackStar}{\LWR@bbdingsymbol{062}                   {2723}}
\newcommand{\LWR@HTML@JackStarBold}{\LWR@bbdingsymbol{063}               {2724}}
\newcommand{\LWR@HTML@CrossClowerTips}{\LWR@bbdingsymbol{064}            {2725}}
\newcommand{\LWR@HTML@FourStar}{\LWR@bbdingsymbol{065}                   {2726}}
\newcommand{\LWR@HTML@FourStarOpen}{\LWR@bbdingsymbol{066}               {2727}}
\newcommand{\LWR@HTML@FiveStarLines}{\LWR@bbdingsymbol{067}              {2729}}
\newcommand{\LWR@HTML@FiveStar}{\LWR@bbdingsymbol{070}                   {2605}}
\newcommand{\LWR@HTML@FiveStarOpen}{\LWR@bbdingsymbol{071}               {2729}}
\newcommand{\LWR@HTML@FiveStarOpenCircled}{\LWR@bbdingsymbol{072}        {272A}}
\newcommand{\LWR@HTML@FiveStarCenterOpen}{\LWR@bbdingsymbol{073}         {272B}}
\newcommand{\LWR@HTML@FiveStarOpenDotted}{\LWR@bbdingsymbol{074}         {272C}}
\newcommand{\LWR@HTML@FiveStarOutline}{\LWR@bbdingsymbol{075}            {272D}}
\newcommand{\LWR@HTML@FiveStarOutlineHeavy}{\LWR@bbdingsymbol{076}       {272E}}
\newcommand{\LWR@HTML@FiveStarConvex}{\LWR@bbdingsymbol{077}             {272F}}
\newcommand{\LWR@HTML@FiveStarShadow}{\LWR@bbdingsymbol{100}             {2730}}
\newcommand{\LWR@HTML@AsteriskBold}{\LWR@bbdingsymbol{101}               {2731}}
\newcommand{\LWR@HTML@AsteriskCenterOpen}{\LWR@bbdingsymbol{102}         {2732}}
\newcommand{\LWR@HTML@AsteriskThin}{\LWR@bbdingsymbol{103}               {273B}}
\newcommand{\LWR@HTML@AsteriskThinCenterOpen}{\LWR@bbdingsymbol{104}     {273C}}
\newcommand{\LWR@HTML@EightStarTaper}{\LWR@bbdingsymbol{105}             {2733}}
\newcommand{\LWR@HTML@EightStarConvex}{\LWR@bbdingsymbol{106}            {2735}}
\newcommand{\LWR@HTML@SixStar}{\LWR@bbdingsymbol{107}                    {2736}}
\newcommand{\LWR@HTML@EightStar}{\LWR@bbdingsymbol{110}                  {2737}}
\newcommand{\LWR@HTML@EightStarBold}{\LWR@bbdingsymbol{111}              {2738}}
\newcommand{\LWR@HTML@TwelweStar}{\LWR@bbdingsymbol{112}                 {2739}}
\newcommand{\LWR@HTML@SixteenStarLight}{\LWR@bbdingsymbol{113}           {273A}}
\newcommand{\LWR@HTML@SixFlowerPetalRemoved}{\LWR@bbdingsymbol{114}      {273B}}
\newcommand{\LWR@HTML@SixFlowerOpenCenter}{\LWR@bbdingsymbol{115}        {273C}}
\newcommand{\LWR@HTML@Asterisk}{\LWR@bbdingsymbol{116}                   {273D}}
\newcommand{\LWR@HTML@SixFlowerAlternate}{\LWR@bbdingsymbol{117}         {273E}}
\newcommand{\LWR@HTML@FiveFlowerPetal}{\LWR@bbdingsymbol{120}            {273F}}
\newcommand{\LWR@HTML@SixFlowerPetalDotted}{\LWR@bbdingsymbol{121}       {2740}}
\newcommand{\LWR@HTML@FiveFlowerOpen}{\LWR@bbdingsymbol{122}             {2740}}
\newcommand{\LWR@HTML@EightFlowerPetal}{\LWR@bbdingsymbol{123}           {2741}}
\newcommand{\LWR@HTML@SunshineOpenCircled}{\LWR@bbdingsymbol{124}        {2742}}
\newcommand{\LWR@HTML@SixFlowerAltPetal}{\LWR@bbdingsymbol{125}          {2743}}
\newcommand{\LWR@HTML@FourClowerOpen}{\LWR@bbdingsymbol{126}             {273F}}
\newcommand{\LWR@HTML@FourClowerSolid}{\LWR@bbdingsymbol{127}            {273F}}
\newcommand{\LWR@HTML@AsteriskRoundedEnds}{\LWR@bbdingsymbol{130}        {2749}}
\newcommand{\LWR@HTML@EightFlowerPetalRemoved}{\LWR@bbdingsymbol{131}    {274A}}
\newcommand{\LWR@HTML@EightAsterisk}{\LWR@bbdingsymbol{132}              {274B}}
\newcommand{\LWR@HTML@SixFlowerRemovedOpenPetal}{\LWR@bbdingsymbol{133}  {2740}}
\newcommand{\LWR@HTML@SparkleBold}{\LWR@bbdingsymbol{134}                 {2748}}
```

```
\newcommand{\LWR@HTML@Sparkle}{\LWR@bbdingsymbol{135}                    {2747}}
\newcommand{\LWR@HTML@SnowflakeChevron}{\LWR@bbdingsymbol{136}           {2744}}
\newcommand{\LWR@HTML@SnowflakeChevronBold}{\LWR@bbdingsymbol{137}       {2746}}
\newcommand{\LWR@HTML@Snowflake}{\LWR@bbdingsymbol{140}                  {2744}}
\newcommand{\LWR@HTML@CircleSolid}{\LWR@bbdingsymbol{141}                {25CF}}
\newcommand{\LWR@HTML@Ellipse}{\LWR@bbdingsymbol{142}                    {274D}}
\newcommand{\LWR@HTML@EllipseSolid}{\LWR@bbdingsymbol{143}               {25CF}}
\newcommand{\LWR@HTML@CircleShadow}{\LWR@bbdingsymbol{144}               {274D}}
\newcommand{\LWR@HTML@EllipseShadow}{\LWR@bbdingsymbol{145}              {274D}}
\newcommand{\LWR@HTML@Square}{\LWR@bbdingsymbol{146}                     {25A1}}
\newcommand{\LWR@HTML@SquareSolid}{\LWR@bbdingsymbol{147}                {25A0}}
\newcommand{\LWR@HTML@SquareShadowBottomRight}{\LWR@bbdingsymbol{150}    {2751}}
\newcommand{\LWR@HTML@SquareShadowTopRight}{\LWR@bbdingsymbol{151}       {2752}}
\newcommand{\LWR@HTML@SquareShadowTopLeft}{\LWR@bbdingsymbol{152}        {2752}}
\newcommand{\LWR@HTML@SquareCastShadowBottomRight}{\LWR@bbdingsymbol{153} {2751}}
\newcommand{\LWR@HTML@SquareCastShadowTopRight}{\LWR@bbdingsymbol{154}    {2752}}
\newcommand{\LWR@HTML@SquareCastShadowTopLeft}{\LWR@bbdingsymbol{155}     {2752}}
\newcommand{\LWR@HTML@TriangleUp}{\LWR@bbdingsymbol{156}                 {25B2}}
\newcommand{\LWR@HTML@TriangleDown}{\LWR@bbdingsymbol{157}               {25BC}}
\newcommand{\LWR@HTML@DiamondSolid}{\LWR@bbdingsymbol{160}               {25C6}}
\newcommand{\LWR@HTML@OrnamentDiamondSolid}{\LWR@bbdingsymbol{161}       {2756}}
\newcommand{\LWR@HTML@HalfCircleRight}{\LWR@bbdingsymbol{162}            {25D7}}
\newcommand{\LWR@HTML@HalfCircleLeft}{\LWR@bbdingsymbol{163}             {25D6}}
\newcommand{\LWR@HTML@RectangleThin}{\LWR@bbdingsymbol{164}              {2758}}
\newcommand{\LWR@HTML@Rectangle}{\LWR@bbdingsymbol{165}                  {2759}}
\newcommand{\LWR@HTML@RectangleBold}{\LWR@bbdingsymbol{166}              {275A}}
\newcommand{\LWR@HTML@ArrowBoldRightStrobe}{\LWR@bbdingsymbol{167}       {27A0}}
\newcommand{\LWR@HTML@ArrowBoldUpRight}{\LWR@bbdingsymbol{170}           {27A6}}
\newcommand{\LWR@HTML@ArrowBoldDownRight}{\LWR@bbdingsymbol{171}         {27A5}}
\newcommand{\LWR@HTML@ArrowBoldRightShort}{\LWR@bbdingsymbol{172}        {27A7}}
\newcommand{\LWR@HTML@ArrowBoldRightCircled}{\LWR@bbdingsymbol{173}      {27B2}}


\LWR@formatted{ScissorRightBrokenBottom}
\LWR@formatted{ScissorRight}
\LWR@formatted{ScissorRightBrokenTop}
\LWR@formatted{ScissorLeftBrokenBottom}
\LWR@formatted{ScissorLeft}
\LWR@formatted{ScissorLeftBrokenTop}
\LWR@formatted{ScissorHollowRight}
\LWR@formatted{ScissorHollowLeft}
\LWR@formatted{Phone}
\LWR@formatted{PhoneHandset}
\LWR@formatted{Tape}
\LWR@formatted{Plane}
\LWR@formatted{Envelope}
\LWR@formatted{HandCuffRight}
\LWR@formatted{HandCuffLeft}
\LWR@formatted{HandCuffRightUp}
\LWR@formatted{HandCuffLeftUp}
\LWR@formatted{HandRight}
\LWR@formatted{HandLeft}
\LWR@formatted{HandRightUp}
\LWR@formatted{HandLeftUp}
\LWR@formatted{Peace}
```

```
\LWR@formatted{HandPencilLeft}
\LWR@formatted{PencilRight}
\LWR@formatted{PencilLeft}
\LWR@formatted{PencilRightUp}
\LWR@formatted{PencilLeftUp}
\LWR@formatted{PencilRightDown}
\LWR@formatted{PencilLeftDown}
\LWR@formatted{NibRight}
\LWR@formatted{NibLeft}
\LWR@formatted{NibSolidRight}
\LWR@formatted{NibSolidLeft}
\LWR@formatted{Checkmark}
\LWR@formatted{CheckmarkBold}
\LWR@formatted{XSolid}
\LWR@formatted{XSolidBold}
\LWR@formatted{XSolidBrush}
\LWR@formatted{PlusOutline}
\LWR@formatted{Plus}
\LWR@formatted{PlusCenterOpen}
\LWR@formatted{PlusThinCenterOpen}
\LWR@formatted{Cross}
\LWR@formatted{CrossOpenShadow}
\LWR@formatted{CrossOutline}
\LWR@formatted{CrossBoldOutline}
\LWR@formatted{CrossMaltese}
\LWR@formatted{DavidStarSolid}
\LWR@formatted{DavidStar}
\LWR@formatted{FourAsterisk}
\LWR@formatted{JackStar}
\LWR@formatted{JackStarBold}
\LWR@formatted{CrossClowerTips}
\LWR@formatted{FourStar}
\LWR@formatted{FourStarOpen}
\LWR@formatted{FiveStarLines}
\LWR@formatted{FiveStar}
\LWR@formatted{FiveStarOpen}
\LWR@formatted{FiveStarOpenCircled}
\LWR@formatted{FiveStarCenterOpen}
\LWR@formatted{FiveStarOpenDotted}
\LWR@formatted{FiveStarOutline}
\LWR@formatted{FiveStarOutlineHeavy}
\LWR@formatted{FiveStarConvex}
\LWR@formatted{FiveStarShadow}
\LWR@formatted{AsteriskBold}
\LWR@formatted{AsteriskCenterOpen}
\LWR@formatted{AsteriskThin}
\LWR@formatted{AsteriskThinCenterOpen}
\LWR@formatted{EightStarTaper}
\LWR@formatted{EightStarConvex}
\LWR@formatted{SixStar}
\LWR@formatted{EightStar}
\LWR@formatted{EightStarBold}
\LWR@formatted{TwelweStar}
\LWR@formatted{SixteenStarLight}
\LWR@formatted{SixFlowerPetalRemoved}
```

```
\LWR@formatted{SixFlowerOpenCenter}
\LWR@formatted{Asterisk}
\LWR@formatted{SixFlowerAlternate}
\LWR@formatted{FiveFlowerPetal}
\LWR@formatted{SixFlowerPetalDotted}
\LWR@formatted{FiveFlowerOpen}
\LWR@formatted{EightFlowerPetal}
\LWR@formatted{SunshineOpenCircled}
\LWR@formatted{SixFlowerAltPetal}
\LWR@formatted{FourClowerOpen}
\LWR@formatted{FourClowerSolid}
\LWR@formatted{AsteriskRoundedEnds}
\LWR@formatted{EightFlowerPetalRemoved}
\LWR@formatted{EightAsterisk}
\LWR@formatted{SixFlowerRemovedOpenPetal}
\LWR@formatted{SparkleBold}
\LWR@formatted{Sparkle}
\LWR@formatted{SnowflakeChevron}
\LWR@formatted{SnowflakeChevronBold}
\LWR@formatted{Snowflake}
\LWR@formatted{CircleSolid}
\LWR@formatted{Ellipse}
\LWR@formatted{EllipseSolid}
\LWR@formatted{CircleShadow}
\LWR@formatted{EllipseShadow}
\LWR@formatted{Square}
\LWR@formatted{SquareSolid}
\LWR@formatted{SquareShadowBottomRight}
\LWR@formatted{SquareShadowTopRight}
\LWR@formatted{SquareShadowTopLeft}
\LWR@formatted{SquareCastShadowBottomRight}
\LWR@formatted{SquareCastShadowTopRight}
\LWR@formatted{SquareCastShadowTopLeft}
\LWR@formatted{TriangleUp}
\LWR@formatted{TriangleDown}
\LWR@formatted{DiamondSolid}
\LWR@formatted{OrnamentDiamondSolid}
\LWR@formatted{HalfCircleRight}
\LWR@formatted{HalfCircleLeft}
\LWR@formatted{RectangleThin}
\LWR@formatted{Rectangle}
\LWR@formatted{RectangleBold}
\LWR@formatted{ArrowBoldRightStrobe}
\LWR@formatted{ArrowBoldUpRight}
\LWR@formatted{ArrowBoldDownRight}
\LWR@formatted{ArrowBoldRightShort}
\LWR@formatted{ArrowBoldRightCircled}
```

File 39 **lwarp-biblatex.sty**

§ 137 Package biblatex

(*Emulates or patches code by* Philipp Lehman.)

Pkg biblatex When biblatex is used, modifications from newfloat may have to be undone.

for HTML output:

1. lwarp uses newfloat.
2. For classes with chapters which newfloat does not know about, such as CTEX-related classes, newfloat may modify `\addtocontents`.
3. biblatex, though, wants to patch `\addtocontents`, which causes an error if `\addtocontents` has been changed.
4. Therefore, `\addtocontents` is restored to its original here, since biblatex is about to be loaded.
5. This means that the newfloat's `chapterlistsgaps` option may no longer work.

```
\ifdef{\newfloat@addtocontents@ORI}{
    \let\addtocontents\newfloat@addtocontents@ORI
}{}

\LWR@ProvidesPackagePass{biblatex}[2018/03/04]
```

File 40 **lwarp-bibunits.sty**

§ 138 Package bibunits

(*Emulates or patches code by* Thorsten Hansen.)

Pkg bibunits bibunits is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bibunits}[2004/05/12]

\def\bu@bibdata{\BaseJobname}
```

File 41 **lwarp-bigdelim.sty**

§ 139 Package bigdelim

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigdelim bigdelim is used as-is for print or `lateximage`, and patched for HTML.

The delimiters are displayed in HTML by printing the delimiter, the text, and a thick border across the side of the `\multirow` which indicates the actual height of the delimiter. The delimiter character is given a `<span>` class of `ldelim` or `rdelim`, and the default CSS sets this to `font-size:200%`

⚠ use `\mrowcell` `\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

<-> a b

left { c d
e f
g h

<-> i j

for HTML output: First, remove the temporary definitions of `\ldelim` and `\rdelim`, which were previously defined for tabular scanning in case bigdelim was not loaded:

```
\let\ldelim\relax
\let\rdelim\relax
```

Next, load the package's new definitions:

```
\LWR@ProvidesPackagePass{bigdelim}[2018/08/03]
```

`\ldelim` {⟨*1:delimiter*⟩} {⟨*2:#rows*⟩} {⟨*3:width*⟩} [⟨*4:text*⟩]
`\rdelim`

```
\NewDocumentCommand{\LWR@HTML@ldelim}{m m m O{}}{%
\renewcommand{\LWR@multirowborder}{right}%
\multirow{#2}{#3}{#4 \InlineClass{ldelim}{#1}}%
}

\LWR@formatted{ldelim}

\NewDocumentCommand{\LWR@HTML@rdelim}{m m m O{}}{%
\renewcommand{\LWR@multirowborder}{left}%
\multirow{#2}{#3}{\InlineClass{rdelim}{#1} #4}%
}

\LWR@formatted{rdelim}
```

File 42 **lwarp-bigfoot.sty**

§ 140 Package

bigfoot

Pkg bigfoot bigfoot is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{bigfoot}[2015/08/30]

\RequirePackage{manyfoot}
```

```
\RequirePackage{perpage}

\def\RestyleFootnote#1#2{}
\def\FootnoteSpecific#1{}
\def\DefineFootnoteStack#1{}
\def\PushFootnoteMark#1{}
\def\PopFootnoteMark#1{}
\def\hfootfraction{0.9}
\def\vtypefraction{0.7}
\def\FootnoteMinimum{1sp}
\def\FootnoteMainMinimum{0pt}
\newcount\bigfoottolerance
\bigfoottolerance=100
\providecommand\footnotecarryratio{2}
```

File 43 **lwarp-bigstrut.sty**

§ 141 Package bigstrut

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigstrut bigstrut is used as-is for print or lateximage, and patched for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{bigstrut}[2018/08/03]

\LetLtxMacro\LWR@origbigstrut\bigstrut

\renewcommand\bigstrut[1][x]{}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bigstrut\LWR@origbigstrut%
}
```

File 44 **lwarp-bitpattern.sty**

§ 142 Package bitpattern

(*Emulates or patches code by* Jean-Marc Bourguet.)

Pkg bitpattern bitpattern is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bitpattern}[2015/12/11]

\xpatchcmd{\bitpattern}
    {\begingroup}
    {\begin{lateximage}[-bitpattern-~\PackageDiagramAltText]}
    {}
    {\LWR@patcherror{bitpattern}{bitpattern}}

\xpatchcmd{\bp@Done}
```

```
    {\endgroup}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{bitpattern}{bp@Done}}
```

File 45 **lwarp-blowup.sty**

§ 143 Package blowup

Pkg blowup blowup is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{blowup}[2018/01/02]
\newcommand*\blowUp[1]{}
```

File 46 **lwarp-booklet.sty**

§ 144 Package booklet

(*Emulates or patches code by* Peter Wilson.)

Pkg booklet booklet is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{booklet}[2009/09/02]
\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\newif\ifsidebyside     \sidebysidetrue
\newif\ifuselandscape   \uselandscapefalse
\newif\ifprintoption    \printoptionfalse
\newcommand*{\pagespersignature}[1]{}
\def\magstepminus#1{}
\newcommand*{\target}[3]{}
\newcommand*{\source}[3]{}
\newcommand*{\setpdftargetpages}{}
\newcommand*{\setdvipstargetpages}{}
\newcommand*{\targettopbottom}{}
\newcommand*{\twoupemptypage}{}
\newcommand*{\twoupclearpage}{}
\newcommand*{\checkforlandscape}{}
```

File 47 **lwarp-bookmark.sty**

§ 145 Package bookmark

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg bookmark bookmark is ignored.

for HTML output: Discard all options for lwarp-bookmark:

```
\LWR@ProvidesPackageDrop{bookmark}[2016/05/17]

\newcommand*{\bookmarksetup}[1]{}
\newcommand*{\bookmarksetupnext}[1]{}
\newcommand*{\bookmark}[2][]{}
\newcommand*{\bookmarkdefinestyle}[2]{}
\newcommand*{\bookmarkget}[1]{}
\newcommand{\BookmarkAtEnd}[1]{}
```

File 48 **lwarp-booktabs.sty**

§ 146 Package

booktabs

(*Emulates or patches code by* Simon Fear.)

Pkg booktabs booktabs is emulated during HTML output, and used as-is during print output and inside an HTML `lateximage`.

for HTML output: First, forget the placeholder macros:

```
\LetLtxMacro\toprule\relax
\LetLtxMacro\midrule\relax
\LetLtxMacro\cmidrule\cline
\LetLtxMacro\bottomrule\relax
\LetLtxMacro\addlinespace\relax
\LetLtxMacro\morecmidrules\relax
\LetLtxMacro\specialrule\relax

\LWR@ProvidesPackagePass{booktabs}[2016/04/27]

\DeclareDocumentCommand{\LWR@HTML@toprule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
                {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\global\booltrue{LWR@doingtbrule}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{toprule}

\DeclareDocumentCommand{\LWR@HTML@midrule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
```

```
                {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\addtocounter{LWR@hlines}{1}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{midrule}

\DeclareDocumentCommand{\LWR@HTML@cmidrule}{O{\LWR@cmidrulewidth} d() m}{%
    \LWR@docmidrule[#1](#2){#3}%
    \LWR@getmynexttoken%
}%

\LWR@expandableformatted{cmidrule}

\DeclareDocumentCommand{\LWR@HTML@bottomrule}{o d()}{%
    \IfValueTF{#1}%
        {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {%
            \ifbool{FormatWP}%
            {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {\global\booltrue{LWR@doingtbrule}}%
        }%
    \LWR@getmynexttoken%
}%

\LWR@expandableformatted{bottomrule}

\DeclareDocumentCommand{\LWR@HTML@addlinespace}{o}{}%

\LWR@expandableformatted{addlinespace}

\DeclareDocumentCommand{\LWR@HTML@morecmidrules}{}{}%

\LWR@expandableformatted{morecmidrules}

\DeclareDocumentCommand{\LWR@HTML@specialrule}{m m m d()}%
  {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}\LWR@getmynexttoken}%

\LWR@expandableformatted{specialrule}
```

File 49 **lwarp-bophook.sty**

§ 147 Package

bophook

Pkg bophook bophook is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bophook}[2001/03/29]

\newcommand*{\AtBeginPage}[1]{}
\newcommand*{\PageLayout}[1]{}
```

File 50 **lwarp-bounddvi.sty**

§ 148 Package bounddvi

Pkg bounddvi bounddvi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bounddvi}[2016/12/28]
```

File 51 **lwarp-boxedminipage2e.sty**

§ 149 Package boxedminipage2e

(*Emulates or patches code by* Scott Pakin.)

Pkg boxedminipage2e boxedminipage2e is emulated for HTML, and used as-is for `latexmk`ages.

for HTML output: Discard all options for lwarp-boxedminipage2e:

```
\LWR@ProvidesPackagePass{boxedminipage2e}[2015/03/09]

\newenvironment{LWR@HTML@boxedminipage}{%
    \LWR@stoppars%
    \begin{BlockClass}{framebox}%
    \minipage%
}
{%
    \endminipage%
    \end{BlockClass}%
    \LWR@startpars%
}
\LWR@formattedenv{boxedminipage}
```

File 52 **lwarp-breakurl.sty**

§ 150 Package breakurl

(*Emulates or patches code by* Vilar Camara Neto.)

Pkg breakurl breakurl is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{breakurl}[2013/04/10]

\LetLtxMacro\burl\url

\NewDocumentCommand{\LWR@burlaltb}{O{} +m m}{%
\LWR@ensuredoingapar%
```

```
\LWR@subhyperref{#2}%
\LWR@subhyperreftext{#3}%
\endgroup% restore catcodes
}

\newrobustcmd*{\burlalt}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@burlaltb%
}

\LetLtxMacro\urlalt\burlalt
```

File 53 **lwarp-breqn.sty**

§ 151 Package

breqn

(*Emulates or patches code by* Michael J. Downes, Morten Høgholm.)

Pkg breqn breqn is patched for use by lwarp.

⚠ darray darray is not supported.

⚠ MathJax MathJax does not support breqn.

for HTML output:

```
\LWR@ProvidesPackagePass{breqn}[2017/01/27]

\setkeys{breqn}{spread={5pt}}

\def\eqnumside{R}
% \def\eqnumplace{T}

\BeforeBeginEnvironment{dmath}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath- \MathImageAltText]
}

\AfterEndEnvironment{dmath}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dmath*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath*- \MathImageAltText]
}
```

```
24
25 \AfterEndEnvironment{dmath*}{
26     \end{lateximage}\end{BlockClass}
27 }
28
29 \BeforeBeginEnvironment{dseries}{
30     \begin{BlockClass}{displaymathnumbered}
31     \LWR@newautoidanchor%
32     \booltrue{LWR@indisplaymathimage}%
33     \begin{lateximage}[-breqn dseries- \MathImageAltText]
34 }
35
36 \AfterEndEnvironment{dseries}{
37     \end{lateximage}\end{BlockClass}
38 }
39
40 \BeforeBeginEnvironment{dseries*}{
41     \begin{BlockClass}{displaymath}
42     \LWR@newautoidanchor%
43     \booltrue{LWR@indisplaymathimage}%
44     \begin{lateximage}[-breqn dseries*- \MathImageAltText]
45 }
46
47 \AfterEndEnvironment{dseries*}{
48     \end{lateximage}\end{BlockClass}
49 }
50
51 \BeforeBeginEnvironment{dgroup}{
52     \begin{BlockClass}{displaymath}
53     \LWR@newautoidanchor%
54     \booltrue{LWR@indisplaymathimage}%
55     \begin{lateximage}[-breqn dgroup- \MathImageAltText]
56 }
57
58 \AfterEndEnvironment{dgroup}{
59     \end{lateximage}\end{BlockClass}
60 }
61
62 \BeforeBeginEnvironment{dgroup*}{
63     \begin{BlockClass}{displaymath}
64     \LWR@newautoidanchor%
65     \booltrue{LWR@indisplaymathimage}%
66     \begin{lateximage}[-breqn dgroup*- \MathImageAltText]
67 }
68
69 \AfterEndEnvironment{dgroup*}{
70     \end{lateximage}\end{BlockClass}
71 }
```

File 54 **lwarp-bsheaders.sty**

§ 152 Package bsheaders

Pkg bsheaders bsheaders is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bsheaders}[1997/10/06]
```

File 55 **lwarp-bxpapersize.sty**

§ 153 Package bxpapersize

Pkg bxpapersize bxpapersize is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bxpapersize}[2017/10/08]

\providecommand*\papersizesetup{\bxpapersizesetup}
\newcommand*\bxpapersizesetup[1]{}
```

File 56 **lwarp-bytefield.sty**

§ 154 Package bytefield

(*Emulates or patches code by* Scott Pakin.)

Pkg bytefield bytefield is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bytefield}[2017/09/15]

\BeforeBeginEnvironment{bytefield}{%
    \begin{lateximage}[-bytefield-~\PackageDiagramAltText]%
}

\AfterEndEnvironment{bytefield}{\end{lateximage}}
```

File 57 **lwarp-cancel.sty**

§ 155 Package cancel

Pkg cancel cancel is used as-is for SVG math, and emulated for HTML text output.

for HTML output:

```
\LWR@origRequirePackage{lwarp-xcolor}% for \convertcolorspec
\LWR@ProvidesPackagePass{cancel}[2013/04/12]
```

\cancelto is math-only, so is used as-is.

```
\LetLtxMacro\LWR@origcancel\cancel
\LetLtxMacro\LWR@origbcancel\bcancel
\LetLtxMacro\LWR@origxcancel\xcancel

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\cancel\LWR@origcancel%
\LetLtxMacro\bcancel\LWR@origbcancel%
\LetLtxMacro\xcancel\LWR@origxcancel%
}
```

\LWR@cancelcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@cancelcolor}[5]{%
\ifcsempty{#2}%
{\InlineClass(#5){#3}{#1}}%
{\LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}%
}
```

\cancel {⟨*text*⟩}

```
\DeclareRobustCommand{\cancel}[1]{%
\begingroup%
\CancelColor%
\LWR@findcurrenttextcolor%
\color{black}%
\LWR@cancelcolor{#1}{LWR@tempcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
\endgroup%
}

\LetLtxMacro\bcancel\cancel
\LetLtxMacro\xcancel\cancel
```

File 58 **lwarp-canoniclayout.sty**

§ 156 Package

canoniclayout

Pkg canoniclayout canoniclayout is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{canoniclayout}[2011/11/05]

\newcommand*{\currentfontletters}{}
\newcommand*{\charactersperpage}{}
```

File 59 **lwarp-caption.sty**

§ 157 Package caption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg caption caption is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{caption}[2019/09/01]

\renewcommand\caption@ibox[3]{%
  \@testopt{\caption@iibox{#1}{#2}{#3}}{%
%         \wd\@tempboxa%
        \linewidth% lwarp
  }%
% \LWR@traceinfo{caption@ibox: done}%
}

\long\def\caption@iibox#1#2#3[#4]{%
  \@testopt{\caption@iiibox{#1}{#2}{#3}{#4}}\captionbox@hj@default
}

\long\def\caption@iiibox#1#2#3#4[#5]#6{%
%   \setbox\@tempboxa\hbox{#6}%
  \begingroup
  #1*% set \caption@position
  \caption@iftop{%
    \LWR@traceinfo{caption@iiibox top}%
    \endgroup
    \parbox[t]{#4}{%
      #1\relax
      \caption@setposition t%
%       \vbox{\caption#2{#3}}%
      {\caption#2{#3}}% lwarp
%       \captionbox@hrule
%       \csname caption@hj@#5\endcsname
%       \unhbox\@tempboxa
       #6% lwarp
    }%
  }{%
    \LWR@traceinfo{caption@iiibox bottom}%
    \endgroup
    \parbox[b]{#4}{%
      #1\relax
      \caption@setposition b%
%       \csname caption@hj@#5\endcsname
%       \unhbox\@tempboxa
        #6% lwarp
%       \captionbox@hrule
%       \vtop{\caption#2{#3}}}%
      {\caption#2{#3}}% lwarp
```

```
    }%
  }%
\LWR@traceinfo{caption@iiibox: done}%
}

% \def\caption@caption{%
%   \caption@iftype
%     {%
%      \caption@checkgrouplevel\@empty\caption
%      \caption@star
%        {\caption@refstepcounter\@captype}%
%        {\caption@dblarg{\@caption\@captype}}}%
%     {\caption@Error{\noexpand\caption outside float}%
%      \caption@gobble}%
% }

\long\def\caption@@caption#1[#2]#3{%

  \ifcaption@star
    \else
    \caption@prepareanchor{#1}{#2}%
    \memcaptioninfo{#1}{\csname the#1\endcsname}{#2}{#3}%
    \@nameuse{nag@hascaptiontrue}%
  \fi

  \par
  \caption@beginex{#1}{#2}{#3}%
    \caption@setfloatcapt{%
      \caption@boxrestore
      \if@minipage
        \@setminipage
      \fi
      \caption@normalsize

      \ifcaption@star
        \let\caption@makeanchor\@firstofone
        #3%                 lwarp
        \else%              lwarp
      \@makecaption{\csname fnum@#1\endcsname}%
                   {\ignorespaces\caption@makeanchor{#3}}%
        \fi%                lwarp

% \par
      \caption@if@minipage\@minipagetrue\@minipagefalse}%
  \caption@end%
}
```

\caption@@@make {⟨*caption label*⟩} {⟨*caption text*⟩}

```
\renewcommand\caption@@@make[2]{%
\LWR@traceinfo{caption@@@make}%
%   \sbox\@tempboxa{#1}%
%   \ifdim\wd\@tempboxa=\z@
```

```
%     \let\caption@lsep\relax
%   \fi
  \caption@ifempty{#2}{%
    \let\caption@lsep\@empty
    \let\caption@tfmt\@firstofone
  }%
  \caption@applyfont
```

`\caption@fmt` with `plain` format is defined as `{#1#2#3\par}`:

```
%     \caption@fmt
    {\ifcaption@star\else
       \begingroup
        \captionlabelfont
         #1%
       \endgroup
     \fi}%
    {\ifcaption@star\else
       \begingroup
         \caption@iflf\captionlabelfont
         \relax
        \caption@lsep
       \endgroup
     \fi}%
    {{%
        \captiontextfont
%       \caption@ifstrut
%         {\vrule\@height\ht\strutbox\@width\z@}%
%         {}%
%       \nobreak\hskip\z@skip % enable hyphenation
        \caption@tfmt{#2}%
%       \caption@ifstrut
%         {\ifhmode\@finalstrut\strutbox\fi}%
%         {}%
      }}%
\LWR@traceinfo{caption@@@make done}%
}
```

`\caption@@make@` {⟨⟩} {⟨⟩}

```
\renewcommand{\caption@@make@}[2]{%
  \caption@stepthecounter
  \caption@beginhook
     \caption@@@make{#1}{#2}%
  \caption@endhook
}
```

`\caption@makecaption`

```
\long\def\caption@makecaption#1#2{%
%   \caption@iftop
%     {\vskip\belowcaptionskip}%
%     {\caption@rule\vskip\abovecaptionskip}%
  \caption@@make{#1}{#2}%
%   \caption@iftop
%     {\vskip\abovecaptionskip\caption@rule}%
```

```
%     {\vskip\belowcaptionskip}%
}

% \DeclareCaptionBox{none}{#2}
\DeclareCaptionBox{parbox}{%
#2%
}
\DeclareCaptionBox{colorbox}{%
#2%
}
```

File 60 **lwarp-cases.sty**

§ 158 Package cases

(*Emulates or patches code by* Donald Arseneau.)

Pkg cases cases is patched for use by lwarp.

⚠ MathJax MathJax does not support cases.

for HTML output:

```
\LWR@ProvidesPackagePass{cases}[2002/05/02]

\BeforeBeginEnvironment{numcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \MathImageAltText]
}

\AfterEndEnvironment{numcases}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{subnumcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \MathImageAltText]
}

\AfterEndEnvironment{subnumcases}{
    \end{lateximage}\end{BlockClass}
}
```

File 61 **lwarp-changebar.sty**

§ 159 Package changebar

Pkg changebar changebar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{changebar}[2018/03/09]

\newcommand*{\cbstart}{}
\newcommand*{\cbend}{}
\newenvironment*{\changebar}{}{}
\newcommand*{\cbdelete}{}
\newcommand*{\nochnagebars}{}
\newcommand*{\cbcolor}[1]{}
\newlength{\changebarwidth}
\newlength{\deletebarwidth}
\newlength{\changebarsep}
\newcounter{changebargrey}
```

File 62 **lwarp-changelayout.sty**

§ 160 Package

changelayout

(*Emulates or patches code by* Ahmed Musa.)

Pkg changelayout changelayout is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{changelayout}[2009/10/07]

\renewrobustcmd\cpl@backtodefaults{}

\renewrobustcmd\cpl@checkifoddpage{%
  \cpl@oddpagefalse%
}

\renewrobustcmd\changepagelayout[1]{%
  \setkeys[KV]{changelay}{#1}%
}

\renewrobustcmd{\changetextlayout}[1]{\changepagelayout{#1}}

\renewrobustcmd\adjustpagelayout[1]{%
  \setkeys[KV@X]{changelay}{#1}%
}

\renewrobustcmd{\adjusttextlayout}[1]{\adjustpagelayout{#1}}

\renewrobustcmd\adjusttextwidth[1]{%
  \setkeys[KV]{changelay}{#1}%
   \begin{BlockClass}[color:\LWR@colorstyle{named}{\cpl@textcolor}]{changelayout}
        \color{\cpl@textcolor}%
        \cpl@content
    \end{BlockClass}
}
```

File 63 **lwarp-changepage.sty**

§ 161 Package changepage

(*Emulates or patches code by* Peter Wilson.)

Pkg changepage changepage is ignored.

for HTML output: Discard all options for lwarp-changepage:

```
\LWR@ProvidesPackageDrop{changepage}[2009/10/20]

\newif\ifoddpage
\DeclareRobustCommand{\checkoddpage}{\oddpagetrue}
\DeclareRobustCommand{\changetext}[5]{}
\DeclareRobustCommand{\changepage}[9]{}

\@ifundefined{adjustwidth}{
\newenvironment{adjustwidth}[2]{}{}
\newenvironment{adjustwidth*}[2]{}{}
}{
\renewenvironment{adjustwidth}[2]{}{}
\renewenvironment{adjustwidth*}[2]{}{}
}

\DeclareDocumentCommand{\strictpagecheck}{}{}
\DeclareDocumentCommand{\easypagecheck}{}{}
```

File 64 **lwarp-changes.sty**

§ 162 Package changes

(*Emulates or patches code by* Ekkart Kleinod.)

Pkg changes changes is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{changes}[2019/01/26]
```

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\renewcommand{\ChangesListline}[4]{%
    \IfSubStr{\Changes@loc@show}{#1}{%
        \LWR@startpars%
        #2: #3 \qquad
        \nameref{\BaseJobname-autopage-#4}%
        \LWR@stoppars%
    }{}%
}
```

```
10
11 \renewcommand{\Changes@summaryline}[4]{%
12     \IfSubStr{\Changes@loc@show}{#1}{%
13         \ifthenelse{\not\equal{\Changes@loc@style}{compactsummary} \or #2 > 0}%
14             {%
15                 #3:~#2#4%
16             }{}%
17     }{}%
18 }
19
20 \xpatchcmd{\listofchanges}
21     {{\changesauthorname: \changesanonymousname}}
22     {{\LWR@textcurrentcolor{\changesauthorname: \changesanonymousname}}}
23     {}
24     {\LWR@patcherror{changes}{listofchanges A}}
25
26 \xpatchcmd{\listofchanges}
27     {\changesauthorname: \Changes@InID}
28     {\LWR@textcurrentcolor{\changesauthorname: \Changes@InID}}
29     {}
30     {\LWR@patcherror{changes}{listofchanges B}}
31
32 \xpatchcmd{\listofchanges}
33     {(\Changes@InName)}
34     {\LWR@textcurrentcolor{(\Changes@InName)}}
35     {}
36     {\LWR@patcherror{changes}{listofchanges C}}
37
38 \xpatchcmd{\listofchanges}
39     {\parbox{\Changes@summary@width}}
40     {}
41     {}
42     {\LWR@patcherror{changes}{listofchanges D}}
43
44 \xpatchcmd{\Changes@Markup@comment}
45     {%
46         \ifthenelse{\isAnonymous{#2}}%
47             {\textbf{[\arabic{Changes@commentCount#2}]:} }%
48             {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
49         #1%
50     }
51     {%
52         \LWR@textcurrentcolor{%         lwarp
53         \ifthenelse{\isAnonymous{#2}}%
54             {\textbf{[\arabic{Changes@commentCount#2}]:} }%
55             {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
56         #1%
57         }%                              lwarp
58     }
59     {}
60     {\LWR@patcherror{changes}{\Changes@Markup@comment A}}
61
62 \xpatchcmd{\Changes@Markup@comment}
63     {%
64         \uwave{%
```

```
            \ifthenelse{\isAnonymous{#2}}%
                {\textbf{[\arabic{Changes@commentCount#2}]:} }%
                {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
            #1%
        }%
    }
    {%
        \LWR@textcurrentcolor{%         lwarp
        \uwave{%
            \ifthenelse{\isAnonymous{#2}}%
                {\textbf{[\arabic{Changes@commentCount#2}]:} }%
                {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
            #1%
        }%
        }%                              lwarp
    }
    {}
    {\LWR@patcherror{changes}{\Changes@Markup@comment B}}

\xpatchcmd{\Changes@output}
    {\Changes@Markup@author{\Changes@output@author{#2}{left}}}
   {\LWR@textcurrentcolor{\Changes@Markup@author{\Changes@output@author{#2}{left}}}}
    {}
    {\LWR@patcherror{changes}{Changes@output A}}

\xpatchcmd{\Changes@output}
    {%
        \ifthenelse{\equal{#1}{added}}{\Changes@Markup@added{#3}}{}%
        \ifthenelse{\equal{#1}{deleted}}{\Changes@Markup@deleted{#4}}{}%
        \ifthenelse{\equal{#1}{replaced}}{%
            {\Changes@Markup@added{#3}}\allowbreak\Changes@Markup@deleted{#4}%
        }{}%
        \ifthenelse{\equal{#1}{highlight}}{\Changes@Markup@highlight{#3}}{}%
    }
    {%
        \LWR@textcurrentcolor{%
        \ifthenelse{\equal{#1}{added}}{\Changes@Markup@added{#3}}{}%
        \ifthenelse{\equal{#1}{deleted}}{\Changes@Markup@deleted{#4}}{}%
        \ifthenelse{\equal{#1}{replaced}}{%
            {\Changes@Markup@added{#3}}\allowbreak\Changes@Markup@deleted{#4}%
        }{}%
        \ifthenelse{\equal{#1}{highlight}}{\Changes@Markup@highlight{#3}}{}%
        }%
    }
    {}
    {\LWR@patcherror{changes}{Changes@output B}}

\xpatchcmd{\Changes@output}
    {\Changes@Markup@author{\Changes@output@author{#2}{right}}}
   {\LWR@textcurrentcolor{\Changes@Markup@author{\Changes@output@author{#2}{right}}}}
    {}
    {\LWR@patcherror{changes}{Changes@output C}}
```

File 65 **lwarp-chappg.sty**

§ 163 Package chappg

(*Emulates or patches code by* Robin Fairbairns.)

Pkg chappg chappg is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{chappg}[2006/05/09]

\renewcommand{\pagenumbering}[2][]{}
\providecommand{\chappgsep}{--}
```

File 66 **lwarp-chapterbib.sty**

§ 164 Package chapterbib

(*Emulates or patches code by* Donald Arseneau.)

Pkg chapterbib chapterbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chapterbib}[2010/09/18]

\xdef\@savedjobname{\BaseJobname}
\let\@currentipfile\@savedjobname
```

File 67 **lwarp-chemfig.sty**

§ 165 Package chemfig

(*Emulates or patches code by* Christian Tellechea.)

Pkg chemfig chemfig is patched for use by lwarp.

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```
\begin{lateximage}[-chemfig-~\PackageDiagramAltText]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

The images are not hashed because they depend on external settings which may be changed at any time, and are unlikely to be reused inline anyhow.

for HTML output:

```
\LWR@ProvidesPackagePass{chemfig}
```

```
2
3 \catcode`\_=11
4
5 \@ifpackagelater{chemfig}{2019/04/18}%
6 {% 2019/04/18 or newer
7
8     \LetLtxMacro\LWR@chemfig@origchemfig\chemfig
9
10    \renewcommand*{\chemfig}[2][]{%
11        \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
12        \LWR@chemfig@origchemfig[#1]{#2}%
13        \end{lateximage}%
14    }
15
16    \GlobalLetLtxMacro\LWR@chemfig@origCF_lewisc\CF_lewisc
17    \gdef\CF_lewisc#1,#2\_nil{%
18    \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
19    \LWR@chemfig@origCF_lewisc#1,#2\_nil
20    \end{lateximage}
21    }
22
23    \gpreto{\schemestart}{%
24        \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
25    }
26    \gappto{\CF_schemestop}{\end{lateximage}}
27
28 }% 2019/04/18 or newer
29 {% older than 2019/04/18
30
31    \LetLtxMacro\LWR@chemfig@origchemfig\chemfig
32
33    \DeclareDocumentCommand\chemfig{s O{} O{} m}{%
34        \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
35        \IfBooleanTF{#1}{%
36            \LWR@chemfig@origchemfig*[#2][#3]{#4}%
37        }{%
38            \LWR@chemfig@origchemfig[#2][#3]{#4}%
39        }
40        \end{lateximage}%
41    }
42
43    \LetLtxMacro\LWR@chemfig@origCF@lewis@b\CF@lewis@b
44
45    \def\CF@lewis@b#1#2{%
46    \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
47    \LWR@chemfig@origCF@lewis@b{#1}{#2}%
48    \end{lateximage}%
49    }
50
51    \preto{\schemestart}{%
52        \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
53    }
54    \appto{\CF@schemestop}{\end{lateximage}}
55
56 }% older than 2019/04/18
```

```
57
58 \catcode`\_=8%
59
60
61
62 \LetLtxMacro\LWR@chemfig@origchemleft\chemleft
63
64 \def\chemleft#1#2\chemright#3{%
65 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
66 \LWR@chemfig@origchemleft#1#2\chemright#3%
67 \end{lateximage}%
68 }
69
70 \LetLtxMacro\LWR@chemfig@origchemup\chemup
71
72 \def\chemup#1#2\chemdown#3{%
73 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
74 \LWR@chemfig@origchemup#1#2\chemdown#3%
75 \end{lateximage}%
76 }
```

File 68 **lwarp-chemformula.sty**

§ 166 Package

chemformula

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemformula

chemformula is patched for use by lwarp.

The SVG images are hashed according to contents and local options. Global options are assumed to be constant document-wide.

⚠ chemformula with MathJax

chemformula works best without MathJax. If MathJax is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The chemformula package adapts to `array`, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, `\displaymathother` may also be used for other forms of display and inline math which contain chemformula expressions.

for HTML output:

```
1 \LWR@ProvidesPackagePass{chemformula}[2017/03/23]

2 \ExplSyntaxOn
```

`\ch` Enclose in an inline SVG image or MathJax. The `alt` tag is is the contents of the `\ch` expression. The filename is hashed, and also has additional hashing information based on the local options.

```
3 \RenewDocumentCommand \ch { O{}m }
4  {%
```

To work inside `align` with `\displaymathother`, a simple version must be used to work with chemformula's adaptation to `align`.

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%  lwarp
    {
        \chemformula_ch:nn {#1} {#2}%   original
    }
```

If used as the outer level, must temporarily ensure MathJax is disabled:

```
    {
        \begingroup%
        \boolfalse{mathjax}%
```

An inline image is used, adjusted for the baseline:

```
        \LWR@subsingledollar*{% lwarp
            \textbackslash{}ch\{\LWR@HTMLsanitize{#2}\}% alt text
        }{%
         \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}% add'l hashing
        }%
        {%
            \chemformula_ch:nn {#1} {#2}%   original
        }%
        \endgroup%
    }
}
```

`\chcpd` Similar to `\ch`.

```
\cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
{
  \begingroup%
  \boolfalse{mathjax}%
  \LWR@subsingledollar*{% lwarp
      \textbackslash{}chcpd\{\LWR@HTMLsanitize{#2}\}%
  }{%
      \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
  }{% original
  \group_begin:
    \tl_if_blank:nF {#2}
      {
        \keys_set:nn {chemformula} {#1}
        \__chemformula_save_catcodes:
        \__chemformula_sanitize:Nn
          \l__chemformula_chemformula_tmpa_tl
          {#2}
        \__chemformula_input_compound_no_check:NV
          \l__chemformula_compound_tl
          \l__chemformula_chemformula_tmpa_tl
        \__chemformula_prepare_output:N \l__chemformula_compound_tl
        \chemformula_write:V \l__chemformula_compound_tl
      }
  \group_end:
  }
  \endgroup
}
```

\charrow If standalone, appears in a regular lateximage.

```
\RenewDocumentCommand \charrow { mO{}O{} }
{
    \begin{lateximage}[-chemformula- charrow]
    \group_begin:
      \__chemformula_draw_arrow:nnn {#1} {#2} {#3}
    \group_end:
    \end{lateximage}
}
```

\chname If standalone, appears in a regular lateximage, hashed according to contents.

```
\RenewDocumentCommand \chname { R(){}R(){} }
  {
    \begin{lateximage}*[%
        \textbackslash{}chname(\LWR@HTMLsanitize{#1})(\LWR@HTMLsanitize{#2})
    ]*%
        \chemformula_chwritebelow:nn {#1} {#2}
    \end{lateximage}
  }
```

\chlewis Placed inline, hashed according to contents and options.

```
\RenewDocumentCommand \chlewis { O{}mm }
  {
    \begingroup%
    \boolfalse{mathjax}%
    \LWR@subsingledollar*{\textbackslash{}chlewis\{#2\}\{#3\}}%
    {
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{
        \chemformula_lewis:nnn {#1} {#2} {#3}
    }
    \endgroup%
  }
```

lwarp redefines the $ character, so special handling is required to escape math expressions inside \ch.

This boolean tracks a new kind of escaped math:

```
\bool_new:N      \l__chemformula_first_last_LWRdollar_bool
```

\chemformula_input_escape_math

Adds additional escaping for the new dollar definition:

```
\cs_gset_protected:Npn \__chemformula_input_escape_math:n #1
  {
    \__chemformula_first_last_math:n {#1}
    \bool_if:NT \l__chemformula_first_last_dollar_bool
      {
```

```
      \bool_set_true:N \l__chemformula_first_last_math_bool
      \__chemformula_read_escape_dollar:w #1 \q_nil
    }
  \bool_if:NT \l__chemformula_first_last_mathbraces_bool
    {
      \bool_set_true:N \l__chemformula_first_last_math_bool
      \__chemformula_read_escape_mathbraces:w #1 \q_nil
    }
```

Added by lwarp:

```
  \bool_if:NT \l__chemformula_first_last_LWRdollar_bool%      lwarp
    {
      \bool_set_true:N \l__chemformula_first_last_math_bool%  lwarp
      \__chemformula_read_escape_LWRdollar:w #1 \q_nil%       lwarp
    }
}
```

\chemformula_read_escape_LWRdollar

The following parses the contents inside the new dollars.

lwarp keeps the dollar as its original math shift until the document starts. While chemmacros is being patched, the dollar must temporarily be set to its new meaning during the following definition.

```
\begingroup
\catcode`\$=\active

\cs_new_protected:Npn \__chemformula_read_escape_LWRdollar:w $#1$ \q_nil
{
  \__chemformula_read_escape_math:n {#1}
}

\endgroup
```

\chemformula_bool_set_if_first_last

The following looks at the first and last tokens for delimiters to escape math inside \ch. The original definition is modified to look for the control sequences which are used by the new meaning of $.

```
\cs_new_protected:Npn \__chemformula_bool_cs_set_if_first_last:NnNN #1#2#3#4
 {
   \int_zero:N \l__chemformula_tmpa_int
   \int_zero:N \l__chemformula_tmpb_int
   \int_set:Nn \l__chemformula_tmpa_int { \tl_count:n {#2} }
   \tl_map_inline:nn {#2}
     {
       \int_incr:N \l__chemformula_tmpb_int
       \int_compare:nT { \l__chemformula_tmpb_int = 1 }
         {
```

At the start, the cs_ version compares control sequences:

```
           \ifdefstrequal{##1}{#3}% lwarp
```

```
                {
                    \bool_set_true:N #1
                }% lwarp
                {}
          }
```

At the end, compare more control sequences:

```
        \int_compare:nT { \l__chemformula_tmpb_int = \l__chemformula_tmpa_int }
          {
            \ifdefstrequal{##1}{#4}
                {}
                {
                    \bool_set_false:N #1
                }
          }
      }
  }
```

\chemformula_first_last_math

Modified to check for the new meaning of $ at first/last:

```
\cs_gset_protected:Npn \__chemformula_first_last_math:n #1
  {
    \bool_set_false:N \l__chemformula_first_last_math_bool
    \bool_set_false:N \l__chemformula_first_last_dollar_bool
    \bool_set_false:N \l__chemformula_first_last_LWRdollar_bool%    lwarp
    \bool_set_false:N \l__chemformula_first_last_mathbraces_bool
    \__chemformula_bool_set_if_first_last:Nnnn
      \l__chemformula_first_last_dollar_bool
      {#1}
      { $ } { $ }
    \bool_if:NF \l__chemformula_first_last_dollar_bool
      {
        \__chemformula_bool_set_if_first_last:Nnnn
          \l__chemformula_first_last_mathbraces_bool
          {#1}
          { \( } { \) }
```

Added by lwarp:

```
          \bool_if:NF \l__chemformula_first_last_mathbraces_bool%   lwarp
            {
                \__chemformula_bool_cs_set_if_first_last:NnNN
                \l__chemformula_first_last_LWRdollar_bool
                {#1}
                { \LWR@newsingledollar } { \LWR@newsingledollar }
            }%  lwarp
      }
  }

\ExplSyntaxOff
```

File 69 **lwarp-chemgreek.sty**

§ 167 Package

chemgreek

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemgreek chemgreek is patched for use by lwarp.

Greek symbols
⚠ package selection To use text-mode symbols, use packages textalpha or textgreek. Using the other packages supported by chemgreek will result in math-mode greek characters, which will result in svg images being used. These images will be hashed.

⚠ XeLaTeX, LuaLaTeX If using XeLaTeX or LuaLaTeX, select the `fontspec` mapping:

```
\selectchemgreekmapping{fontspec}
```

for HTML output:

```
\LWR@ProvidesPackagePass{chemgreek}[2016/02/10]

\ExplSyntaxOn

\cs_gset_protected:Npn \chemgreek_text:n #1
  { { \text {#1} } }

\appto\LWR@restoreorigformatting{%
\cs_set_protected:Npn \chemgreek_text:n #1%
  { \ensuremath { \text {#1} } }%
}

\ExplSyntaxOff
```

File 70 **lwarp-chemmacros.sty**

§ 168 Package

chemmacros

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemmacros chemmacros is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chemmacros}[2017/08/28]
```

SVG file hashing assumes that the relevent options are constant for the entire document.

§ 168.1 Changes to the user's document

⚠ \makepolymerdelims When using \makepolymerdelims, enclose the entire expression inside a polymerdelims environment, such as (from the chemmacros manual):

```
\begin{polymerdelims}
\chemfig{-[@{op,.75}]CH_2-CH(-[6]Cl)-[@{cl,0.25}]}
\makepolymerdelims{5pt}[27pt]{op}{cl}
\end{polymerdelims}
```

⚠ redox reactions Redox reactions must be enclosed inside a redoxreaction environment. For print output, extra space must be included above and/or below the result, so they are declared as arguments to the environment, instead of being manually entered as per the chemmacros manual. For HTML output, the extra space is ignored and a lateximage is used instead.

```
\begin{redoxreaction}{7mm}{7mm}
\OX{a,Na} $\rightarrow$ \OX{b,Na}\pch\redox(a,b){oxidation}
\end{redoxreaction}
```

§ 168.2 Code

§ 168.3 Loading modules

Patching chemmacros modules must be done \AtBeginDocument, since modules are invoked by the user in the preamble, and each patch is only done if the module is loaded.

```
\ExplSyntaxOn

\newcommand{\@ifchemmacrosmoduleloaded}[1]{%
\@ifl@aded{\c__chemmacros_module_extension_tl}{\c__chemmacros_module_prefix_tl.#1}%
}

\ExplSyntaxOff
```

§ 168.4 New environments

\makepolymerdelims and redox reactions must be enclosed in a lateximage during HTML output. These environments are provided here in HTML mode, and in the lwarp core in print mode, as a high-level semantic syntax which automatically embeds the contents in a lateximage with an appropriate alt tag.

Env polymerdelims

```
\DeclareDocumentEnvironment{polymerdelims}{}
{\begin{lateximage}[-chemmacros- polymer]}
{\end{lateximage}}
```

Env redoxreaction {⟨*space above*⟩} {⟨*space below*⟩}

For HTML output, the above and below space is ignored, and a `lateximage` is used instead. For the print output version, see section 86.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
{\begin{lateximage}[-chemmacros- redoxreaction]}
{\end{lateximage}}

\ExplSyntaxOn
```

§ 168.5 Acid-base

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{acid-base}{
\PackageInfo{lwarp}{Patching~chemmacros~module~acid-base}

\cs_gset_protected:Npn \chemmacros_p:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{
        \textbackslash{}p\{\LWR@HTMLsanitize{#1}\}
    }{
        chemmacrosp\protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{
    \group_begin:
      \mbox
        {
          \chemmacros_p_style:n {p}
          \ensuremath {#1}
        }
    \group_end:
    }
    \endgroup
  }

\RenewDocumentCommand \pH  {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {H} }
    }
    \endgroup
}

\RenewDocumentCommand \pOH {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pOH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {OH} }
    }
    \endgroup
}

\RenewDocumentCommand \pKa {O{}}
  {
    \begingroup
```

```
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKa{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Ka \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
    \endgroup
  }

\RenewDocumentCommand \pKb {O{}}
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKb{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Kb \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
    \endgroup
  }

\LetLtxMacro\LWR@chemmacros@origKa\Ka
\renewcommand*{\Ka}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Ka}{chemmacros}{%
        \LWR@chemmacros@origKa%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKb\Kb
\renewcommand*{\Kb}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Kb}{chemmacros}{%
        \LWR@chemmacros@origKb%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKw\Kw
\renewcommand*{\Kw}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Kw}{chemmacros}{
        \LWR@chemmacros@origKw
    }
    \endgroup
}

```

```
}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.6 Charges

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{charges}{
\PackageInfo{lwarp}{Patching~chemmacros~module~charges}

\cs_gset_protected:Npn \fplus  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fplus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fplus:}  }
    \endgroup
}
\cs_gset_protected:Npn \fminus {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fminus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fminus:} }
    \endgroup
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.7 Nomenclature

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{nomenclature}{
\PackageInfo{lwarp}{Patching~chemmacros~module~nomenclature}

\cs_gset_protected:Npn \chemmacros_charge:n #1
  {
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}
    {\chemmacros_chemformula:n { {}^{#1} }}
    {
        \ifmmode
            {\chemmacros_chemformula:n { {}^{#1} }}
        \else
            { \textsuperscript{\ensuremath{#1}} }
        \fi
    }
  }


\LetLtxMacro\LWR@chemmacros@origchemprime\chemprime

\protected\def\chemprime { \HTMLunicode{2032} }

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\chemprime\LWR@chemmacros@origchemprime%
}
```

```
\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_cip:n #1
  {
    \tl_set:Nn \l__chemmacros_tmpa_tl {#1}
    \int_step_inline:nnnn {0} {1} {9}
      {
        \tl_replace_all:Nnn \l__chemmacros_tmpa_tl
          {##1}
          { { \l__chemmacros_cip_number_tl ##1} }
      }
    {
        \l__chemmacros_cip_inner_tl
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \l__chemmacros_tmpa_tl
        }}% lwarp
    }
  }
\EndChemCompatibility

\RenewDocumentCommand \Sconf { O{S} } {
\begin{lateximage}[\textbackslash{}Sconf{[}#1{]}]*
    \chemmacros_sconf:n {#1}
\end{lateximage}
}

\RenewDocumentCommand \Rconf { O{R} } {
\begin{lateximage}[\textbackslash{}Rconf{[}#1{]}]*
    \chemmacros_rconf:n {#1}
\end{lateximage}
}

\cs_gset_protected:Npn \chemmacros_hapto:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}hapto\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemeta }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_dento:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}dento\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
```

```
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemkappa }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_bridge:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}bridge\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        { \l__chemmacros_bridge_super_bool }
        { \chemmu }
        {#1}
    }
    \endgroup
  }
}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.8 Particles

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{particles}{
\PackageInfo{lwarp}{Patching~chemmacros~module~particles}

\cs_gset_protected:Npn \chemmacros_declare_nucleophile:Nn #1#2
  {
    \cs_set_protected:cpn {__chemmacros_ \chemmacros_remove_backslash:N #1:}
      {
        \bool_if:NTF \l__chemmacros_nucleophile_elpair_bool
          {
            \chemmacros_elpair:n { #2 }
            \chemmacros_if_compatibility:nnT {>=} {5.3}
              { \skip_horizontal:N \l__chemmacros_nucleophile_dim }
            \chemmacros_chemformula:n { {}^{-} }
          }
          { \chemmacros_chemformula:n { #2^{-} } }
      }
    \DeclareDocumentCommand #1 {o}
      {%
        \begin{lateximage}%
        \group_begin:%
          \IfNoValueF {##1}%
            { \chemmacros_set_keys:nn {particles} {##1} }%
          \use:c {__chemmacros_ \chemmacros_remove_backslash:N #1:}%
        \group_end:%
        \end{lateximage}%
      }
```

```
  }

\RenewChemNucleophile \Nuc {Nu}
\RenewChemNucleophile \ba  {ba}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.9 Phases

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{phases}{
\PackageInfo{lwarp}{Patching~chemmacros~module~phases}

\cs_undefine:N \chemmacros_phase:n
\cs_new_protected:Npn \chemmacros_phase:n #1
  {
    \chemmacros_leave_vmode:
    \bool_if:NTF \l__chemmacros_phases_sub_bool
      {
        \ifnumequal{\value{LWR@lateximagedepth}}{0}
        {
            \textsubscript{ (#1) }
        }
        {
            \chemformula_subscript:n { (#1) }
        }
      }
      {
        \skip_horizontal:N \l__chemmacros_phases_space_dim
        \chemmacros_text:n { (#1) }
      }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.10 Mechanisms

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{mechanisms}{
\PackageInfo{lwarp}{Patching~chemmacros~module~mechanisms}

\chemmacros_define_keys:nn {textmechanisms}
  {
    type      .choice: ,
    type /    .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{N}
          }
          { }
      } ,
    type / 1  .code:n    =
```

```
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{N}
          1
        }
        { }
    } ,
  type / 2  .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{N}
          2
        }
        { }
    } ,
  type / se .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{E}
        }
        { }
    } ,
  type / 1e .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{E}
          1
        }
        { }
    } ,
  type / 2e .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{E}
          2
        }
        { }
    } ,
  type / ar .code:n    =
    {
      \__chemmacros_set_mechanisms:nnn { S }
        {
            \textsubscript{E}
        }
        { Ar - }
    } ,
  type / e  .code:n    =
    { \__chemmacros_set_mechanisms:nnn { E } { } { } } ,
  type / e1 .code:n    =
    { \__chemmacros_set_mechanisms:nnn { E } { 1 } { } } ,
```

```
    type / e2 .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { 2 } { } } ,
    type / cb .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { E }
          {
            1
              \textsubscript{cb}
          }
          { }
      } ,
    type      .default:n =
  }

\cs_gset_protected:Npn \chemmacros_mechanisms:n #1
  {
    \tl_if_blank:nTF {#1}
      { \chemmacros_set_keys:nn {textmechanisms} { type } }
      { \chemmacros_set_keys:nn {textmechanisms} { type = #1 } }
    \mbox
      {
        \tl_use:N \l__chemmacros_mechanisms_ar_tl
        \tl_use:N \l__chemmacros_mechanisms_type_tl
        \tl_use:N \l__chemmacros_mechanisms_mol_tl
      }
  }

\appto\LWR@restoreorigformatting{%
\cs_set_protected:Npn \chemmacros_mechanisms:n #1%
  {%
    \tl_if_blank:nTF {#1}%
      { \chemmacros_set_keys:nn {mechanisms} { type } }%
      { \chemmacros_set_keys:nn {mechanisms} { type = #1 } }%
    \mbox%
      {%
        \tl_use:N \l__chemmacros_mechanisms_ar_tl%
        \tl_use:N \l__chemmacros_mechanisms_type_tl%
        \tl_use:N \l__chemmacros_mechanisms_mol_tl%
      }%
  }%
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.11 Newman

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{newman}{
\PackageInfo{lwarp}{Patching~chemmacros~module~newman}

\RenewDocumentCommand \newman {od()m}%
  {
    \IfValueTF{#2}
    {\begin{lateximage}[\textbackslash{}newman(#2)\{#3\}]*}
    {\begin{lateximage}[\textbackslash{}newman\{#3\}]*}
```

```
    \group_begin:
      \IfNoValueF  {#1} { \chemmacros_set_keys:nn {newman} {#1} }
      \IfNoValueTF {#2}
        { \chemmacros_newman:nn {  } {#3} }
        { \chemmacros_newman:nn {#2} {#3} }
    \group_end:
    \end{lateximage}
  }%

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.12 Orbital

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{orbital}{
\PackageInfo{lwarp}{Patching~chemmacros~module~orbital}

\RenewDocumentCommand \orbital {om}
  {
    \IfValueTF{#1}
    {
        \begin{lateximage}[%
            \textbackslash{}orbital{[}\LWR@HTMLsanitize{#1}{]}\{#2\}%
        ]*[][margin-left: 1em ; margin-right: 1em]
    }
    {
        \begin{lateximage}[%
            \textbackslash{}orbital\{#2\}%
        ]*[][margin-left: 1em ; margin-right: 1em]
    }
    \group_begin:
      \chemmacros_set_keys:nn {orbital/type} {#2}
      \IfNoValueTF {#1}
        { \chemmacros_orbital:n {  } }
        { \chemmacros_orbital:n {#1} }
    \group_end:
    \end{lateximage}
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.13 Reactions

`\chemmacros_declare_reaction_env` {⟨*chem*⟩} {⟨*math*⟩} {⟨*args number*⟩} {⟨*argument list (#2}{#3}...)*⟩}

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{reactions}{
\PackageInfo{lwarp}{Patching~chemmacros~module~reactions}

\cs_gset_protected:Npn \chemmacros_declare_reaction_env:nnnn #1#2#3#4
  {
   \exp_args:Nnx \DeclareDocumentEnvironment {#1} { O{} \prg_replicate:nn {#3+0} {m} }
      {
```

```
        \boolfalse{mathjax}%                        lwarp
        \ifdefvoid{\LWR@ThisAltText}{%              lwarp
            \ThisAltText{-chemmacros-~reaction}%    lwarp
        }{}%                                        lwarp
        \chemmacros_add_reaction_description:n {##1}
        \__chemmacros_begin_reaction:
        \chemmacros_reaction_read:nnw {#2} {#4}
      }
      {
        \__chemmacros_end_reaction:
        \gdef\LWR@ThisAltText{}%                    lwarp
      }
  }
\cs_generate_variant:Nn \chemmacros_declare_reaction_env:nnnn {nnnV}

\RenewChemReaction {reaction}   {equation}
\RenewChemReaction {reaction*}  {equation*}
\RenewChemReaction {reactions}  {align}
\RenewChemReaction {reactions*} {align*}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.14 Redox

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{redox}{
\PackageInfo{lwarp}{Patching~chemmacros~module~redox}

\NewDocumentCommand \LWR@chemmacros@ox { s m >{\SplitArgument{1}{,}}m }
  {
    \IfBooleanTF {#1}
      { \chemmacros_ox:nnnn {#1} {#2} #3 }
      { \chemmacros_ox:nnnn {  } {#2} #3 }
  }

\RenewDocumentCommand \ox { s O{} m }
  {
    \begingroup
    \boolfalse{mathjax}
    \IfBooleanTF {#1}
      {
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            star \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
        }{%
            \LWR@chemmacros@ox* {#2} {#3}% contents
        }%
      }
      {
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
```

```
        }{%
            \LWR@chemmacros@ox {#2} {#3}% contents
        }%
      }
    \endgroup
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.15 Scheme

Fix for chemmacros as of v5.8b, when using newfloat and babel:

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{scheme}{
\PackageInfo{lwarp}{Patching~chemmacros~module~scheme}

\ifdefstring{\schemename}{los}{
\SetupFloatingEnvironment{scheme}{
name = \chemmacros_translate:n {scheme-name}
}
}{}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.16 Spectroscopy

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{spectroscopy}{
\PackageInfo{lwarp}{Patching~chemmacros~module~spectroscopy}

\ChemCompatibilityTo{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
      {
        \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
        \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
      }
    \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%     \chemmacros_chemformula:n { ^{#1} }
    \textsuperscript{#1}
    \bool_if:NTF \l__chemmacros_nmr_parse_bool
      { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
      { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
    \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
    \tl_use:N \l__chemmacros_nmr_method_tl
  }
\EndChemCompatibility
\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \group_begin:
```

```
      \tl_use:N \l__chemmacros_nmr_base_format_tl
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
          \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
        }
      \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%       \chemmacros_chemformula:n { ^{#1} }
      \textsuperscript{#1}
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \bool_if:NTF \l__chemmacros_nmr_parse_bool
            { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
           { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
        }
      \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
      \tl_use:N \l__chemmacros_nmr_method_tl
    \group_end:
  }
\EndChemCompatibility


\cs_gset_protected:Npn \chemmacros_nmr_position:n #1
  {
    \chemmacros_chemformula:x
      {
        \exp_not:V \g__chemmacros_nmr_element_tl
        \bool_if:NF \l__chemmacros_nmr_position_side_bool
          {
            \tl_if_eq:NnTF \l__chemmacros_nmr_position_tl {^}% lwarp
            { \textsuperscript{\exp_not:n { {#1} }} }% lwarp
            { \textsubscript{\exp_not:n { {#1} }} }% lwarp
%             \exp_not:V \l__chemmacros_nmr_position_tl
%             \exp_not:n { {#1} }
          }
      }
    \bool_if:NT \l__chemmacros_nmr_position_side_bool
      {
        \tl_use:N \l__chemmacros_nmr_position_tl
        \__chemmacros_nmr_position:n {#1}
      }
  }

\cs_gset_protected:Npn \__chemmacros_nmr_coupling:w (#1;#2)
  {
    \tl_set:Nn \l__chemmacros_nmr_coupling_bonds_tl
      {
        \l__chemmacros_nmr_coupling_bonds_pre_tl
        #1
        \l__chemmacros_nmr_coupling_bonds_post_tl
      }
    \bool_if:NTF \l__chemmacros_nmr_coupling_nuclei_sub_bool
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
```

```
%             \c_math_subscript_token
            \textsubscript% lwarp
              {
                \l__chemmacros_nmr_coupling_nuclei_pre_tl
                \chemmacros_chemformula:n {#2}
                \l__chemmacros_nmr_coupling_nuclei_post_tl
              }
          }
      }
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
            \l__chemmacros_nmr_coupling_nuclei_pre_tl
            \chemmacros_chemformula:n {#2}
            \l__chemmacros_nmr_coupling_nuclei_post_tl
          }
      }
    \__chemmacros_nmr_coupling_aux_i:w
  }

\AfterEndPreamble{% After \AtBeginDocument
% \NMR{<num>,<elem>}(<num>,<unit>)[<solvent>] ALL arguments are optional
% \NMR* same but without ": $\delta$" at end
\cs_gset_protected:Npn \chemmacros_nmr:nnnn #1#2#3#4
    {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item \scan_stop: }
    \group_begin:
        \chemmacros_leave_vmode:
        \bool_set_false:N \l__chemmacros_nmr_frequency_bool
        \bool_set_false:N \l__chemmacros_nmr_solvent_bool
        \tl_if_empty:nF {#3}
        { \bool_set_true:N \l__chemmacros_nmr_frequency_bool }
        \tl_if_empty:nF {#4}
        { \bool_set_true:N \l__chemmacros_nmr_solvent_bool }
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            ||
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_delimiters_bool }
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            &&
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_comma_bool }
        \tl_if_empty:nTF {#2}
        {
            \__chemmacros_nmr_nucleus:VV
            \l__chemmacros_nmr_isotope_default_tl
            \l__chemmacros_nmr_element_default_tl
        }
        { \__chemmacros_nmr_nucleus:w #2 \q_stop }
```

```
        \mode_if_math:TF
        {
            \text
            {
                \group_begin:
                \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
                \__chemmacros_nmr_base:VV
                    \g__chemmacros_nmr_isotope_tl
                    \g__chemmacros_nmr_element_tl
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ~ ( }
                \bool_if:NT \l__chemmacros_nmr_frequency_bool
                    { \__chemmacros_nmr_frequency:n {#3} }
                \bool_if:NT \l__chemmacros_nmr_comma_bool
                    { , ~ }
                \bool_if:NT \l__chemmacros_nmr_solvent_bool
                    { \chemmacros_chemformula:n {#4} }
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ) }
                \tl_if_blank:nT {#1} {:~}
}}% lwarp
                \group_end:
            }
            \tl_if_blank:nT {#1}
            {
                \delta
                \text { \l__chemmacros_nmr_delta_tl }
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {=}
            }
        }
        {
            \group_begin:
            \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \__chemmacros_nmr_base:VV
                \g__chemmacros_nmr_isotope_tl
                \g__chemmacros_nmr_element_tl
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {~(}
            \bool_if:NT \l__chemmacros_nmr_frequency_bool
                { \__chemmacros_nmr_frequency:n {#3} }
            \bool_if:NT \l__chemmacros_nmr_comma_bool
                {,~}
            \bool_if:NT \l__chemmacros_nmr_solvent_bool
                {
                \bool_if:NTF \l__chemmacros_nmr_parse_bool

% 
                    { \chemformula_ch:nn { } {#4} }%  original
                {\ch{#4}}%  lwarp
                {#4}
                }
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {)}
}}% lwarp
```

```
            \tl_if_blank:nT {#1} {:}
            \group_end:
            \tl_if_blank:nT {#1}
            {
                \tl_use:N \c_space_tl
                \c_math_toggle_token
                \delta
                \c_math_toggle_token
                \l__chemmacros_nmr_delta_tl
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {~=}
            }
        }
    \group_end:
    }
}% AfterEndPremble


\RenewDocumentCommand \chemmacros_data:w { smo }
  {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item }
      {
%         \tl_use:N \l__chemmacros_nmr_format_tl #2
        \tl_use:N \l__chemmacros_nmr_format_tl
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            #2
            \IfNoValueF {#3} { ~ ( #3 ) }
         \IfBooleanT {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { : } }
        }}% lwarp
      }
    \IfBooleanF {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { ~ = } }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.17 Thermodynamics

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{thermodynamics}{
\PackageInfo{lwarp}{Patching~chemmacros~module~thermodynamics}

\cs_gset_protected:Npn \chemmacros_state:nn #1#2
  {
    \group_begin:
      \boolfalse{mathjax}
      \chemmacros_set_keys:nn {thermodynamics} {#1}
        \LWR@subsingledollar*{% yes hashing
            \textbackslash{}state\{\LWR@HTMLsanitize{#2}\}% alt
        }{%
            chemmacros_state% add'l hashing
            #1% options
            LSP \tl_use:N \l__chemmacros_state_sp_left_tl% super/subscripts
            LSB \tl_use:N \l__chemmacros_state_sb_left_tl
            RSP \tl_use:N \l__chemmacros_state_sp_right_tl
            RSB \tl_use:N \l__chemmacros_state_sb_right_tl
        }
```

```
        {
         \LWR@origensuredmath{
          \chemmacros_text:V \l__chemmacros_state_pre_tl
          \c_math_superscript_token
            { \chemmacros_text:V \l__chemmacros_state_sp_left_tl }
```

Only add the subscripts if they are being used. This avoids causing an incorrect depth, as the empty subscript will be measured by TEX but cropped out by *pdfcrop*.

```
          \tl_if_empty:NTF \l__chemmacros_state_sb_left_tl
          {}
          {
            \c_math_subscript_token
            { \chemmacros_text:V \l__chemmacros_state_sb_left_tl }
          }
          #2
          \c_math_superscript_token
            { \chemmacros_text:V \l__chemmacros_state_sp_right_tl }
          \tl_if_empty:NTF \l__chemmacros_state_sb_right_tl
          {}
          {
            \c_math_subscript_token
            { \chemmacros_text:V \l__chemmacros_state_sb_right_tl }
          }
          \chemmacros_text:V \l__chemmacros_state_post_tl
         }
        }
    \group_end:
  }
\cs_generate_variant:Nn \chemmacros_state:nn { nV }

\cs_gset_protected:Npn \chemmacros_declare_state:Nn #1#2
  {
    \chemmacros_define_keys:xn
      {thermodynamics/\chemmacros_remove_backslash:N #1}
      {
        pre               .meta:nn = {chemmacros/thermodynamics} { pre = ##1 } ,
        post              .meta:nn = {chemmacros/thermodynamics} { post = ##1 } ,
      superscript-left  .meta:nn = {chemmacros/thermodynamics} { superscript-left = ##1 } ,
      superscript-right .meta:nn = {chemmacros/thermodynamics} { superscript-right = ##1 } ,
        superscript       .meta:n  = { superscript-right = ##1 } ,
      subscript-left   .meta:nn = {chemmacros/thermodynamics} { subscript-left = ##1 } ,
      subscript-right  .meta:nn = {chemmacros/thermodynamics} { subscript-right = ##1 } ,
        subscript         .meta:n     = { subscript-left = ##1 } ,
        subscript-pos     .choices:nn =
          { left , right }
          { \tl_set_eq:NN \l__chemmacros_state_sb_pos_tl \l_keys_choice_tl } ,
        symbol            .tl_set:N = \l__chemmacros_state_symbol_tl ,
        unit              .tl_set:N = \l__chemmacros_state_unit_tl
      }
    \DeclareDocumentCommand #1 { sO{}D(){}m }
      {
        \group_begin:
          \chemmacros_set_keys:xn
            {thermodynamics/\chemmacros_remove_backslash:N #1}
```

```
            {#2}
          \tl_if_blank:nF {##3}
            {
              \chemmacros_set_keys:nx {thermodynamics}
               { subscript-\l__chemmacros_state_sb_pos_tl = \exp_not:n {##3} }
            }
              \chemmacros_state:nV {##2} \l__chemmacros_state_symbol_tl
             \chemmacros_set_keys_groups:nnn {thermodynamics} {variables} {##2}
           \IfBooleanF {##1} {  = ~ \SI {##4} { \l__chemmacros_state_unit_tl } }
        \group_end:
      }
  }
```

The pre-existing macros are redefined with the new definition:

```
\RenewChemState \enthalpy { symbol = H , unit = \kilo\joule\per\mole }
\RenewChemState \entropy  { symbol = S , unit = \joule\per\kelvin\per\mole , pre = }
\RenewChemState \gibbs    { symbol = G , unit = \kilo\joule\per\mole }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument

\ExplSyntaxOff
```

File 71 **lwarp-chemnum.sty**

§ 169 Package chemnum

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemnum chemnum is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chemnum}[2016/04/14]

\ExplSyntaxOn

\cs_gset_protected:Npn \chemnum_compound_write:n #1
  {
    \chemnum_get_compound_property:nn {#1} {pre-main-label-code}
    \group_begin:
      \bool_if:NTF \l__chemnum_compound_local_bool
        { \l__chemnum_local_label_format_tl }
        { \chemnum_get_compound_property:nn {#1} {label-format} }
      {
        \LWR@textcurrentfont{
            \chemnum_get_compound_property:nn {#1} {counter-representation}
        }
      }
    \group_end:
    \chemnum_get_compound_property:nn {#1} {post-main-label-code}
  }

\cs_gset_protected:Npn \chemnum_subcompound_write:nn #1#2
```

```
{
  \group_begin:
    \bool_if:NTF \l__chemnum_compound_local_bool
      { \l__chemnum_local_label_format_tl }
      { \chemnum_get_compound_property:nn {#1} {label-format} }
    {
      \LWR@textcurrentfont{
          \chemnum_get_subcompound_property:nnn {#1} {#2}
          {counter-representation}
      }
    }
  \group_end:
}

\ExplSyntaxOff
```

File 72 **lwarp-chkfloat.sty**

§ 170 Package chkfloat

Pkg chkfloat chkfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{chkfloat}[2012/08/19]
```

File 73 **lwarp-chngpage.sty**

§ 171 Package chngpage

(*Emulates or patches code by* Peter Wilson.)

Pkg chngpage chngpage is ignored.

for HTML output: Discard all options for lwarp-chngpage:

```
\LWR@ProvidesPackageDrop{chngpage}[2009/10/20]
\LWR@origRequirePackage{lwarp-changepage}
```

File 74 **lwarp-cite.sty**

§ 172 Package cite

(*Emulates or patches code by* Donald Arseneau.)

Pkg cite cite is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{cite}[2015/02/27]
```

For the [super] option, the \kern must be removed:

```
\def\LWRCT@biblabel#1{\@citess{#1}\kern-\labelsep\,}

\ifdefstrequal{\@biblabel}{\LWRCT@biblabel}
{
    \def\@biblabel#1{\@citess{#1}}
}{}
```

For the [super] option, \textsuperscript is used instead of math superscript:

```
\def\@citess#1{\textsuperscript{#1}}

\DeclareDocumentCommand\citepunct{}{,\,\relax}
```

File 75 **lwarp-CJK.sty**

§ 173 Package CJK

Pkg CJK CJK does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJK}{ctex, xeCJK}
}

\LWR@ProvidesPackagePass{CJK}[2015/04/18]
```

File 76 **lwarp-CJKutf8.sty**

§ 174 Package CJKutf8

Pkg CJKutf8 CJKutf8 does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJKutf8}{ctex, xeCJK}
}

\LWR@ProvidesPackagePass{CJKutf8}[2015/04/18]
```

File 77 **lwarp-clrdblpg.sty**

§ 175 Package clrdblpg

Pkg clrdblpg clrdblpg is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{clrdblpg}[2018/04/21]
```

File 78 **lwarp-cmdtrack.sty**

§ 176 Package
# cmdtrack

Pkg cmdtrack cmdtrack is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{cmdtrack}[2012/12/18]
\newcommand{\untrack}[1]{}
```

File 79 **lwarp-color.sty**

§ 177 Package
# color

Pkg color Allowed but ignored. xcolor is then required as well.

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

for HTML output:

```
\LWR@ProvidesPackageDrop{color}[2016/07/10]
\RequirePackage{xcolor}
```

File 80 **lwarp-colortbl.sty**

§ 178 Package
# colortbl

Pkg colortbl colortbl is used as-is for print output, and emulated for HTML.

⚠ row/cell color Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.

colortbl ignores the overhang arguments.

for HTML output: A placeholder definition is forgotten first:

```
\let\rowcolor\relax

\LWR@ProvidesPackagePass{colortbl}[2018/12/12]
```

The following `\LWR@HTML` versions are used inside an HTML `tabular`.

`\columncolor` `[`⟨*model*⟩`]` `{`⟨*color*⟩`}` `[`⟨*left overhang*⟩`]` `[`⟨*right overhang*⟩`]`

`\LWR@getmynexttoken` is not used here because `\columncolor` is not used inside the data area of the tabular.

```
\NewDocumentCommand{\LWR@HTML@columncolor}{O{named} m o o}{%
```

```
\convertcolorspec{#1}{#2}{HTML}\LWR@columnHTMLcolor%
\LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{columncolor}}
```

\LWR@getmynexttoken is used for \rowcolor because it is used inside the data area of the tabular.

\rowcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

```
\NewDocumentCommand{\LWR@HTML@rowcolor}{O{named} m o o}{%
\convertcolorspec{#1}{#2}{HTML}\LWR@rowHTMLcolor%
\LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{rowcolor}}
```

\cellcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

```
\NewDocumentCommand{\LWR@HTML@cellcolor}{O{named} m o o}{%
\convertcolorspec{#1}{#2}{HTML}\LWR@cellHTMLcolor%
\LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{cellcolor}}
```

\arrayrulecolor [⟨*model*⟩] {⟨*color*⟩}

The HTML version for use outside a tabular. Inside a tabular, \LWR@HTML@arrayrulecolornexttoken is used instead.

```
\newcommand{\LWR@HTML@arrayrulecolor}[2][named]{%
\convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolor}}
```

\LWR@arrayrulecolornexttoken [⟨*model*⟩] {⟨*color*⟩}

The HTML version for use inside a tabular.

```
\newcommand{\LWR@HTML@arrayrulecolornexttoken}[2][named]{%
\convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
\LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolornexttoken}}
```

\doublerulesepcolor [⟨*model*⟩] {⟨*color*⟩}

The version for use outside a tabular.

```
\newcommand{\LWR@HTML@doublerulesepcolor}[2][named]{}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolor}}
```

[⟨*model*⟩] {⟨*color*⟩}

\LWR@doublerulesepcolornexttoken The version for use inside a `tabular`.

```
\newcommand{\LWR@HTML@doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolornexttoken}}
```

File 81 **lwarp-continue.sty**

§ 179 Package continue

Pkg continue continue is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{continue}}[2018/12/09]

\newcommand*{\flagcont}{}
\newcommand*{\flagend}{}
\newcommand*{\flagword}{}
\newcommand*{\preflagword}{}
\newcommand*{\postflagword}{}
\newlength\contsep
\newlength\contdrop
```

File 82 **lwarp-copyrightbox.sty**

§ 180 Package copyrightbox

(*Emulates or patches code by* Thomas Fischer, Ives van der Flaas.)

Pkg copyrightbox copyrightbox is emulated for use by lwarp.

The entire copyright box is placed inside a of class copyrightbox.

The contents are placed inside a of class copyrightboxcontents.

The copyright notice is placed inside a of class copyrightboxnote.

for HTML output:

```
\LWR@ProvidesPackageDrop{copyrightbox}[2011/11/27]

\newcommand{\copyrightbox}[3][r]{%
\begin{BlockClass}[
    display: inline-flex;
    flex-direction: column ;
]{copyrightbox}
\begin{BlockClass}{copyrightboxcontents}
#2
\end{BlockClass}
\begin{BlockClass}{copyrightboxnote}
#3
```

```
\end{BlockClass}
\end{BlockClass}
}

\newcommand{\CRB@setcopyrightfont}{}
\newcommand{\CRB@setcopyrightparagraphstyle}{}
```

File 83 **lwarp-crop.sty**

§ 181 Package crop

(*Emulates or patches code by* Melchior FRANZ.)

Pkg crop crop is ignored.

for HTML output: Discard all options for lwarp-crop:

```
\LWR@ProvidesPackageDrop{crop}[2003/05/20]

\newcommand*{\crop}[1][]{}
\newcommand*{\cropdef}[6][]{}
```

File 84 **lwarp-ctable.sty**

§ 182 Package ctable

(*Emulates or patches code by* Wybo Dekker.)

Pkg ctable ctable is patched for use by lwarp.

⚠ Misplaced alignment tab character & Use `\StartDefiningTabulars` before one or more `\ctables`, and `\StopDefiningTabulars` after. These change the meaning of the ampersand & character.

for HTML output:

```
\LWR@ProvidesPackagePass{ctable}[2015/10/17]
```

The following is in the original:

```
\newcommand{\LWR@HTML@ctable}[4][]{%
   \let\@CTtaborfig  \@dfltCTtaborfig
   \let\@CTalign     \@dfltCTalign
   \let\@CTsideways  \@dfltCTsideways
   \let\@CTcontinued \empty
   \let\@CTpos       \@dfltCTpos
   \let\@CTcaption   \empty
   \let\@CTcap       \undefined
   \let\@CTlabel     \empty
   \let\@CTbotcap    \@dfltCTbotcap
   \let\@CTstarred   \@dfltCTstarred
   \let\@CTsuper     \@dfltCTsuper
   \let\@CTnotespar  \@dfltCTnotespar
```

```
\let\@CTdoinside  \@dfltCTdoinside
\let\@CTbgopacity \@dfltCTbgopacity
\@CTframerule     \@dfltCTframerule
\@CTcaptionskip   \@dfltCTcaptionskip
\@CTframesep      \@dfltCTframesep
\@CTwidth         \@dfltCTwidth
\@CTmaxwidth      \@dfltCTmaxwidth
\@CTmincapwidth   \@dfltCTmincapwidth
\@CTfooterwidth   \@dfltCTfooterwidth
\def\@CTfgactual {@dfltCTframefg}%
\def\@CTbgactual {@dfltCTframebg}%
\def\@CTbeg      {\begin{\@CTsideways\@CTtaborfig\@CTstarred}}%
\def\@CTbegin    {\@CTbeg}%
\def\@CTend      {\end{\@CTsideways\@CTtaborfig\@CTstarred}}%
\setkeys{CT}{#1}%
\ifx\@CTcap\undefined\let\@CTcap\@CTcaption\fi
\ifx\@CTcap\empty
  \if@CTcaptionloaded\else
    \PackageWarningNoLine{lwarp-ctable}{\MessageBreak
       An empty cap= option prevents lot/loc entry only\MessageBreak
       if the caption package is loaded!}
  \fi
\fi
\if@CTinmemoir\else
   \ifx\@CTbotcap\undefined
      \PackageError{lwarp-ctable}{\MessageBreak
         You can, currently, use the sidecap option only with\MessageBreak
         memoir documents. Use topcap or botcap only}
   \fi
\fi
\ifdim\@CTwidth=0pt\else
   \ifdim\@CTmaxwidth=0pt\else
      \PackageError{lwarp-ctable}{\MessageBreak
        You may not use the width and maxwidth options together\MessageBreak
         Use either width or maxwidth}
   \fi
\fi
\ifx\@CTpos\empty
   \ifx\@CTsideways\empty\else
   \PackageError{lwarp-ctable}{\MessageBreak
      You may not use the pos and sideways options together\MessageBreak
      Rotated tables and figures are always typeset on a separate page}
   \fi
\fi
\ifx\@CTcaption\empty
   \ifx\@CTlabel\empty\else
      \PackageError{lwarp-ctable}{\MessageBreak
         You may not label a captionless table\MessageBreak
         Such a label can't be referenced}
   \fi
\fi
```

Some of the original, regarding computing the width of `\CT@t`, is removed here.

```
\@CTbegin
```

```
    \ifx\@CTcontinued\empty\else\addtocounter{\@CTtaborfig}{-1}\fi
    \@CTalign
```

lwarp's patches begin here:

```
  \begin{center}
      \setlength{\fboxrule}{\@CTframerule}
      \setlength{\fboxsep}{\@CTframesep}
      \LWR@forceminwidth{\fboxrule}%  lwarp
      \convertcolorspec{named}{\@CTbgactual}{HTML}\LWR@tempcolor% lwarp
      \begin{BlockClass}[%                              lwarp
          border:
              \LWR@printlength{\LWR@atleastonept}
              solid
              \LWR@colorstyle{named}{\@CTfgactual} ; %
          padding:\LWR@printlength{\fboxsep} ; %
          \ifdefstring{\LWR@tempcolor}{FFFFFF}{}{%
              background: \LWR@colorstyle{named}{\@CTbgactual} ; %
          }%
      ]{fminipage}%       lwarp
       \ifx\@CTbotcap\@CTfalse\@CTcaption\vskip\@CTcaptionskip\fi
       \ifx\@CTbotcap\undefined%
           \begin{sidecaption}[\@CTcap]{\@CTcaption}[\@CTlabel]
       \fi
       \@CTdoinside
       \begin{tabularx}{\linewidth}{#2}%      lwarp
          #4%
       \end{tabularx}%                    lwarp
       \def\@CTfootnotes{#3}%
       \ifx#3\empty\else{% append footnotes, if any
          \begin{BlockClass}{tnotes}%     lwarp
          #3
          \end{BlockClass}%               lwarp
       }
       \fi
       \ifx\@CTbotcap\undefined\end{sidecaption}\fi
       \ifx\@CTbotcap\@CTtrue\vskip\@CTcaptionskip\@CTcaption\fi
      \end{BlockClass}
   \end{center}
  \@CTend
}
\LWR@formatted{ctable}
```

Required to properly detect the toprule:

```
\LetLtxMacro\FL\toprule
```

Table notes are redefined for HTML:

```
\newcommand{\LWR@HTML@tmark}[1][a]{%
  \textsuperscript{\textrm{\textit{#1}}}
}
\LWR@formatted{tmark}

\newcommand{\LWR@HTML@tnote}[2][a]{%
```

```
    \tmark[#1]\,#2\par
}
\LWR@formatted{tnote}
```

File 85 **lwarp-cuted.sty**

§ 183 Package cuted

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg cuted cuted is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{cuted}[2012/10/04]

\newenvironment{strip}{}{}
\newskip\stripsep
\def\oldcolsbreak#1{}
```

File 86 **lwarp-cutwin.sty**

§ 184 Package cutwin

(*Emulates or patches code by* Peter Wilson and Alan Hoenig.)

Pkg cutwin cutwin is emulated.

for HTML output: Discard all options for lwarp-cutwin:

```
\LWR@ProvidesPackageDrop{cutwin}[2010/09/29]

\newcommand*{\opencutleft}{}
\newcommand*{\opencutright}{}
\newcommand*{\opencutcenter}{}
\newcommand*{\cutfuzz}{}

\newenvironment{cutout}[4]
{\marginpar{\windowpagestuff}}
{}

\newcommand*{\windowpagestuff}{}

\newcommand*{\pageinwindow}{%
% \begin{minipage}{.3\linewidth}
\windowpagestuff
% \end{minipage}
}

\newenvironment{shapedcutout}[3]
{\marginpar{\picinwindow}}
{}
```

```
22
23 \newcommand*{\putstuffinpic}{}
24
25 \newcommand*{\picinwindow}{%
26 \begin{picture}(0,0)
27 \putstuffinpic
28 \end{picture}}
```

File 87 **lwarp-dblfloatfix.sty**

§ 185 Package dblfloatfix

Pkg dblfloatfix dblfloatfix is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{dblfloatfix}[2012/12/31]
```

File 88 **lwarp-dblfnote.sty**

§ 186 Package dblfnote

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg dblfnote dblfnote is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{dblfnote}[1999/07/14]

2 \newcounter{DFNsloppiness}
3 \newdimen\DFNcolumnsep
4 \newdimen\DFNcolumnwidth
5 \def\DFNallowcbreak{}
6 \def\DFNinhibitcbreak{}
7 \def\DFNtrysingle{}
8 \def\DFNalwaysdouble{}
9 \def\DFNruleboth{}
10 \def\DFNruleleft{}
```

File 89 **lwarp-dcolumn.sty**

§ 187 Package dcolumn

Pkg dcolumn dcolumn is emulated by the lwarp core.

```
1 \LWR@ProvidesPackageDrop{dcolumn}[2014/10/28]
```

File 90 **lwarp-diagbox.sty**

§ 188 Package

diagbox

(*Emulates or patches code by* Leo Liu.)

Pkg diagbox diagbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{diagbox}[2016/12/28]
```

To restore print-mode inside a `lateximage`:

```
\LetLtxMacro\LWR@origdiagbox@double\diagbox@double
\LetLtxMacro\LWR@origdiagbox@triple\diagbox@triple

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\diagbox@double\LWR@origdiagbox@double%
\LetLtxMacro\diagbox@triple\LWR@origdiagbox@triple%
}
```

`\LWR@diagbox@AB` {⟨*E/W*⟩} {⟨*A*⟩} {⟨*E/W*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagbox@AB}[4]{
\begingroup%
\LetLtxMacro\\\newline%
\BlockClassSingle{diagbox#1}{#2}%
\BlockClassSingle{diagbox#3}{#4}%
\endgroup%
\LWR@stoppars%
}
```

`\LWR@diagboxNW` {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxNW}[2]{%
\LWR@diagbox@AB{E}{#2}{W}{#1}%
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxNE}[2]{%
\LWR@diagbox@AB{W}{#1}{E}{#2}%
}

\let\LWR@diagboxSW\LWR@diagboxNE
\let\LWR@diagboxSE\LWR@diagboxNW
```

`\diagbox@double` {⟨*keys*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\def\diagbox@double#1#2#3{%
\setkeys{diagbox}{dir=NW,#1}%
```

```
\@nameuse{LWR@diagbox\diagbox@dir}{#2}{#3}%
}
```

`\LWR@diagboxTNW` {⟨*title*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxTNW}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNW{#2}{#3}
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxTNE}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNE{#2}{#3}
}

\newcommand{\LWR@diagboxTSW}[3]{%
\LWR@diagboxSW{#2}{#3}
\BlockClassSingle{diagboxtitleS}{#1}
\LWR@stoppars%
}

\newcommand{\LWR@diagboxTSE}[3]{%
\LWR@diagboxSE{#2}{#3}
\BlockClassSingle{diagboxtitleS}{#1}
\LWR@stoppars%
}
```

`\diagbox@triple` {⟨*keys*⟩} {⟨*A*⟩} {⟨*T*⟩} {⟨*B*⟩}

```
\def\diagbox@triple#1#2#3#4{%
\setkeys{diagbox}{dir=NW,#1}%
\@nameuse{LWR@diagboxT\diagbox@dir}{#3}{#2}{#4}%
}
```

File 91 **lwarp-dingbat.sty**

§ 189 Package

dingbat

(*Emulates or patches code by* Scott Pakin.)

Pkg dingbat dingbat is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{dingbat}[2001/04/27]

\newcommand*{\LWR@dingbatsymbol}[1]{\HTMLunicode{#1}}

\newcommand{\LWR@HTML@rightpointright}{\LWR@dingbatsymbol{261E}}
\newcommand{\LWR@HTML@leftpointright}{\LWR@dingbatsymbol{261E}}
\newcommand{\LWR@HTML@leftthumbsdown}{\LWR@dingbatsymbol{1F44E}}
\newcommand{\LWR@HTML@leftthumbsup}{\LWR@dingbatsymbol{1F44D}}
```

```
\newcommand{\LWR@HTML@rightpointleft}{\LWR@dingbatsymbol{261C}}
\newcommand{\LWR@HTML@rightthumbsdown}{\LWR@dingbatsymbol{1F44E}}
\newcommand{\LWR@HTML@rightthumbsup}{\LWR@dingbatsymbol{1F44D}}
\newcommand{\LWR@HTML@squarewithdots}{\LWR@dingbatsymbol{25C7}}
\newcommand{\LWR@HTML@filledsquarewithdots}{\LWR@dingbatsymbol{25C6}}
\newcommand{\LWR@HTML@Sborder}{\LWR@dingbatsymbol{271A}}
\newcommand{\LWR@HTML@Zborder}{\LWR@dingbatsymbol{274B}}
\newcommand{\LWR@HTML@largepencil}{\LWR@dingbatsymbol{270E}}
\newcommand{\LWR@HTML@anchor}{\LWR@dingbatsymbol{2693}}
\newcommand{\LWR@HTML@carriagereturn}{\LWR@dingbatsymbol{23CE}}
\newcommand{\LWR@HTML@checkmark}{\LWR@dingbatsymbol{2713}}
\newcommand{\LWR@HTML@eye}{\LWR@dingbatsymbol{1F441}}
\newcommand{\LWR@HTML@satellitedish}{\LWR@dingbatsymbol{1F4E1}}
\newcommand{\LWR@HTML@smallpencil}{\LWR@dingbatsymbol{270E}}

\LWR@formatted{rightpointright}
\LWR@formatted{leftpointright}
\LWR@formatted{leftthumbsdown}
\LWR@formatted{leftthumbsup}
\LWR@formatted{rightpointleft}
\LWR@formatted{rightthumbsdown}
\LWR@formatted{rightthumbsup}
\LWR@formatted{squarewithdots}
\LWR@formatted{filledsquarewithdots}
\LWR@formatted{Sborder}
\LWR@formatted{Zborder}
\LWR@formatted{largepencil}
\LWR@formatted{anchor}
\LWR@formatted{carriagereturn}
\LWR@formatted{checkmark}
\LWR@formatted{eye}
\LWR@formatted{satellitedish}
\LWR@formatted{smallpencil}
```

File 92 **lwarp-dprogress.sty**

§ 190 Package dprogress

Pkg dprogress dprogress is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{dprogress}[2008/02/21]
```

File 93 **lwarp-draftcopy.sty**

§ 191 Package draftcopy

Pkg draftcopy draftcopy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftcopy}[2002/02/25]
```

```
\newcommand{\draftcopyVersion}[1]{}
\newcommand{\draftcopySetGrey}[1]{}
\newcommand{\draftcopySetScale}[1]{}
\newcommand{\draftcopySetScaleFactor}[1]{}
\newcommand{\draftcopyFirstPage}[1]{}
\newcommand{\draftcopyLastPage}[1]{}
\newcommand{\draftcopyName}[2]{}
\newcommand{\draftcopyPageTransform}[1]{}
\newcommand{\draftcopyBottomTransform}[1]{}
\newcommand{\draftcopyPageX}[1]{}
\newcommand{\draftcopyPageY}[1]{}
\newcommand{\draftcopyBottomX}[1]{}
\newcommand{\draftcopyBottomY}[1]{}
```

File 94 **lwarp-draftfigure.sty**

§ 192 Package draftfigure

Pkg draftfigure draftfigure is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftfigure}[2017/07/19]
\RequirePackage{xkeyval}

\define@key{draftfigure}{code}{}
\define@key{draftfigure}{noframe}[true]{}
\define@key{draftfigure}{filename}[true]{}
\define@key{draftfigure}{content}[]{}
\define@key{draftfigure}{style}[normal]{}
\define@key{draftfigure}{position}[left]{}
\define@key{draftfigure}{size}[normal]{}
\newcommand\setdf[1]{\setkeys{draftfigure}{#1}}
```

File 95 **lwarp-draftwatermark.sty**

§ 193 Package draftwatermark

(*Emulates or patches code by* Sergio Callegari.)

Pkg draftwatermark draftwatermark is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftwatermark}[2015/02/19]

\newcommand{\SetWatermarkAngle}[1]{}
\newcommand{\SetWatermarkColor}[1]{}
\newcommand{\SetWatermarkLightness}[1]{}
\newcommand{\SetWatermarkFontSize}[1]{}
\newcommand{\SetWatermarkScale}[1]{}
\newcommand{\SetWatermarkHorCenter}[1]{}
\newcommand{\SetWatermarkVertCenter}[1]{}
\newcommand{\SetWatermarkText}[1]{}
```

File 96 **lwarp-easy-todo.sty**

§ 194 Package

easy-todo

(*Emulates or patches code by* Juan Rada-Vilela.)

Pkg easy-todo easy-todo is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{easy-todo}[2014/01/01]
```

\listoftodos Modified to correct buggy use of \flushright.

```
\let\LWR@origlistoftodos\listoftodos

\renewcommand{\listoftodos}{%
\begingroup
\renewcommand{\flushright}{}
\LWR@origlistoftodos
\endgroup
}
```

\todoii Modified to use \textcolor instead of \color.

```
\renewcommand{\todoii}[2]{%
\ifthenelse{\equal{\@todoobeyfinal}{true}}%
    {%
        \ifoptionfinal{\todoenable{false}}{\todoenable{true}}%
    }%
    {}%
\ifthenelse{\equal{\@todoenable}{true}}%
    {%
        \refstepcounter{todos}%
        \noindent{%
            \todocolor%
            \LWR@textcurrentcolor{%
                \normalfont\scriptsize{\bfseries{\thetodos.#1}}%
            }%
        }%
        \addcontentsline{lod}{todos}{\protect{\thetodos. }\LWR@isolate{#2}}%
    }%
    {}%
}
```

File 97 **lwarp-ebook.sty**

§ 195 Package

ebook

(*Emulates or patches code by* Jørgen Steensgaard.)

Pkg ebook ebook is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ebook}

\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}

\providecommand{\pagefill}[1][0.001mm]{\noindent}

\providecommand{\ebook}{
\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}
}
```

File 98 **lwarp-ed.sty**

§ 196 Package

ed

(*Emulates or patches code by* Michael Kohlhase.)

Pkg ed ed is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ed}[2012/01/29]
```

Bugs:

1. `todolist` fails with the `hide` option, as does `\edexplanation`.
2. `\edstubURI` is actually `\edstuURI`.

```
\RequirePackage{xcolor}

\renewenvironment{edstub}[2][The following blue text]
{%
    \def\@test{#1}%
    \begin{center}%
        \huge%
        \textcolor{red}{%
            #1 is only a provisional stub\\\Large
            the Office document
            \ifx\ed@stubURI\@empty{#2}\else\href{\ed@stubURI}{#2}\fi\
            contains more text\\which will be merged for the final document%
        }%
    \end{center}%
    \BlockClass[color:blue]{edstub}%
}
{\endBlockClass}
```

File 99 **lwarp-ellipsis.sty**

§ 197 Package ellipsis

(*Emulates or patches code by* Peter J. Heslin.)

Pkg ellipsis ellipsis is emulated.

```
\LWR@ProvidesPackageDrop{ellipsis}[2004/09/28]

\newcommand{\ellipsisgap}{0.1em}

\newcommand*{\midwordellipsis}{\,\textellipsis\,}
```

File 100 **lwarp-embrac.sty**

§ 198 Package embrac

(*Emulates or patches code by* Clemens Niederberger.)

Pkg embrac embrac is nullfied for HTML and used as-is for print.

for HTML output:

```
\LWR@ProvidesPackagePass{embrac}[2017/07/04]

\LetLtxMacro\LWR@orig@HTML@emph\LWR@HTML@emph
\RenewDocumentCommand{\LWR@HTML@emph}{s m}{\LWR@orig@HTML@emph{#2}}

\LetLtxMacro\LWR@orig@HTML@textit\LWR@HTML@textit
\RenewDocumentCommand{\LWR@HTML@textit}{s m}{\LWR@orig@HTML@textit{#2}}

\LetLtxMacro\LWR@orig@HTML@textsl\LWR@HTML@textsl
\RenewDocumentCommand{\LWR@HTML@textsl}{s m}{\LWR@orig@HTML@textsl{#2}}

\ifxetexorluatex
    \LetLtxMacro\LWR@orig@HTML@textsi\LWR@HTML@textsi
    \RenewDocumentCommand{\LWR@HTML@textsi}{s m}{%
    \LWR@orig@HTML@textsi{#2}}
\fi

\AtBeginDocument{
    \LWR@formatted{emph}
    \LWR@formatted{textit}
    \LWR@formatted{textsl}
    \ifxetexorluatex
        \LWR@formatted{textsi}
    \fi
}

```

```
\newcommand{\LWR@HTML@EmbracOff}{}
\LWR@formatted{EmbracOff}

\newcommand{\LWR@HTML@EmbracOn}{}
\LWR@formatted{EmbracOn}
```

File 101 **lwarp-emptypage.sty**

§ 199 Package emptypage

Pkg emptypage emptypage is ignored.

for HTML output: Discard all options for lwarp-emptypage:

```
\LWR@ProvidesPackageDrop{emptypage}[2010/05/30]
```

File 102 **lwarp-endfloat.sty**

§ 200 Package endfloat

Pkg endfloat endfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endfloat}[2019/04/15]

\newcommand\figureplace{}
\newcommand\tableplace{}
\newcommand\floatplace[1]{}
\newcounter{posttable}
\newcounter{postfigure}
\newcommand*{\theposttbl}{}
\newcommand*{\thepostfig}{}
\newcommand{\AtBeginFigures}[1]{}
\newcommand{\AtBeginTables}[1]{}
\newcommand{\AtBeginDelayedFloats}[1]{}
\newcommand*{\processdelayedfloats}{}
\newcommand*{\efloatseparator}{}
\def\efloattype{}
\providecommand\efloatheading[1]{}
\providecommand\efloatpreamble{}
\providecommand\efloatpostamble{}
\NewDocumentCommand{\addtodelayedfloat}{s m m}{}
\providecommand{\efloatbegin}{}
\providecommand{\efloatend}{}
\providecommand{\efloatbeginlist}{}
\providecommand{\efloatendlist}{}
```

File 103 **lwarp-endheads.sty**

§ 201 Package endheads

Pkg endheads endheads is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endheads}[2017/04/06]

\newcommand{\changesinglepageabbrev}[1]{}
\newcommand{\changemultiplepageabbrev}[1]{}
\newcommand{\changenotesname}[1]{}
\newcommand{\changenotesheader}[1]{}
\newcommand{\changenotescontentsname}[1]{}
\newcommand{\changechapternotesline}[1]{}
\newcommand{\checknoteheaders}{}
\newif\ifnotesincontentson \notesincontentsonfalse
\newcommand{\notesincontents}{\notesincontentsontrue}
\newif\ifendnoteheaderson \endnoteheadersonfalse
\newcommand{\setupendnoteheaders}{%
    \endnoteheadersontrue%
}
\newif\iftitleinnotes \titleinnotestrue
\newcommand{\styleforchapternotebegin}{}
\newcommand{\styleforchapternoteend}{}
\newcommand{\setstyleforchapternotebegin}[1]{%
    \renewcommand{\styleforchapternotebegin}{#1}%
}
\newcommand{\setstyleforchapternoteend}[1]{%
    \renewcommand{\styleforchapternoteend}{#1}%
}
\newcommand{\resetendnotes}{}
\newif\ifnotesbychapteron \notesbychapteronfalse
\newcommand{\notesbychapter}{\notesbychapterontrue}
```

File 104 **lwarp-endnotes.sty**

§ 202 Package endnotes

(*Emulates or patches code by* John Lavagnino.)

Pkg endnotes Used as-is.

table of contents To place the endnotes in the toc, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

HTML page To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

for HTML output:

```
\LWR@ProvidesPackagePass{endnotes}

\def\enoteformat{%
% \rightskip\z@ \leftskip\z@ \parindent=1.8em
\leavevmode
% \llap{
\makeenmark
% }
}

\def\@makeenmark{\hbox{\LWR@htmlspan{sup}{\normalfont\theenmark}}}
\def\makeenmark{\@makeenmark}
```

File 105 **lwarp-enumerate.sty**

§ 203 Package enumerate

Pkg enumerate enumerate is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by lwarp and thus must no longer be dropped.

for HTML output:

```
\LWR@ProvidesPackagePass{enumerate}[2015/07/23]
```

File 106 **lwarp-enumitem.sty**

§ 204 Package enumitem

(*Emulates or patches code by* Javier Bezos.)

Pkg enumitem enumitem is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{enumitem}[2018/11/30]
```

for HTML output:

```
\begin{warpHTML}
```

`\newlist` {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}
`\renewlist` {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}

For enumitem lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

```
\let\LWR@enumitem@orignewlist\newlist

\renewcommand*{\newlist}[3]{%
\LWR@enumitem@orignewlist{#1}{#2}{#3}%
\AtBeginEnvironment{#1}{\@nameuse{LWR@#2start}}%
\AtEndEnvironment{#1}{\@nameuse{LWR@#2end}}%
}

\def\DrawEnumitemLabel{}

\end{warpHTML}
```

File 107 **lwarp-epigraph.sty**

§ 205 Package

epigraph

(*Emulates or patches code by* Peter Wilson.)

Pkg epigraph epigraph is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{epigraph}[2009/09/02]

\DeclareDocumentCommand{\qitem}{m m}
{
\begin{BlockClass}{qitem}
#1
\LWR@stoppars%
\ifbool{FormatWP}
{\begin{BlockClass}[border-top:1px solid gray]{epigraphsource}}
{\begin{BlockClass}{epigraphsource}}
#2
\end{BlockClass}
\end{BlockClass}
}

\DeclareDocumentCommand{\epigraph}{m m}
{
\begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{epigraph}
\qitem{#1}{#2}
\end{LWR@BlockClassWP}
}

\DeclareDocumentEnvironment{epigraphs}{}
{\LWR@BlockClassWP{\LWR@print@mbox{text-align:right}}{}{epigraph}}
{\endLWR@BlockClassWP}
```

Use css to format epigraphs.

The following are null commands for source compatibility:

```
\newenvironment*{flushepinormal}{}{}
```

```
\@ifclassloaded{memoir}{
\setlength{\epigraphwidth}{.5\linewidth}
\renewcommand{\textflush}{flushepinormal}
\renewcommand{\epigraphhead}[2][0]{#2}
\renewcommand{\dropchapter}[1]{}
\renewcommand*{\undodrop}{}
}{% not memoir
\newlength{\epigraphwidth}
\setlength{\epigraphwidth}{.5\linewidth}
\newcommand{\textflush}{flushepinormal}
\newcommand{\epigraphflush}{flushright}
\newcommand{\sourceflush}{flushright}
\newcommand*{\epigraphsize}{\small}
\newlength{\epigraphrule}
\newlength{\beforeepigraphskip}
\newlength{\afterepigraphskip}
\newcommand{\epigraphhead}[2][0]{#2}
\newcommand{\dropchapter}[1]{}
\newcommand*{\undodrop}{}
}% not memoir

\let\cleartoevenpage\relax% also in nextpage
\newcommand{\cleartoevenpage}[1][]{}
```

File 108 **lwarp-epsfig.sty**

§ 206 Package

epsfig

Pkg epsfig epsfig is emulated for use by lwarp.

⚠ Only the LaTeX2e syntax is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{epsfig}[2017/06/25]
```

A few additional keys to capture the filename:

```
\RequirePackage{graphics}

\define@key{igraph}{file}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{figure}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{prolog}{}

\define@key{igraph}{silent}[]{}
```

The captured filename is used as the argument to `\includegraphics`:

```
\newcommand{\epsfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}

\newcommand{\psfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
```

File 109 **lwarp-epstopdf.sty**

§ 207 Package

epstopdf

Pkg epstopdf

Previous versions of lwarp had a nullfied version, but now epstopdf-base is supported. lwarp-epstopdf becomes a placeholder to overwrite previous versions.

See package epstopdf-base for details.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf}[2016/05/15]
```

File 110 **lwarp-epstopdf-base.sty**

§ 208 Package

epstopdf-base

Pkg epstopdf-base

⚠ convert to .svg

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf-base}[2016/05/15]
```

Redefine to remember the image filename, replacing .pdf with .svg. Use the epstopdf print version inside a latexmage.

```
\newcommand*{\LWR@HTML@ETE@OrgGin@setfile}[3]{%
    \edef\LWR@tempone{#3}%
    \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
    \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
    \xdef\LWR@parsedfilename{\LWR@tempone}%
}

\LWR@formatted{ETE@OrgGin@setfile}
```

\includegraphics in HTML mode redefines \Gin@setfile to be \LWR@HTML@Gin@setfile, which is now redirected to epstopdf's version:

```
\renewcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \ETE@Gin@setfile{#1}{#2}{#3}%
}
```

Allow .eps images to be found if a suffix is not provided:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{%
    .eps,.EPS,.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Likewise when inside a `lateximage`:

```
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{%
    .eps,.EPS,.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}%
}
```

File 111 **lwarp-eqlist.sty**

§ 209 Package eqlist

Pkg eqlist eqlist is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{eqlist}[2002/08/15]
```

```
\newenvironment{eqlist}[1][]{\description}{\enddescription}
\newenvironment{eqlist*}[1][]{\description}{\enddescription}
\newenvironment{Eqlist}[2][]{\description}{\enddescription}
\newenvironment{Eqlist*}[2][]{\description}{\enddescription}
\newcommand*{\longitem}[1][]{\item[#1]}
\newcommand*{\eqlistinit}{}
\newcommand*{\eqliststarinit}{}
\newcommand*{\eqlistinitpar}{}
\def\eqlistlabel#1{#1}
\newcommand{\eqlistauto}[1]{}
\newcommand{\eqlistnoauto}{}
```

File 112 **lwarp-eqparbox.sty**

§ 210 Package eqparbox

(*Emulates or patches code by* Scott Pakin.)

Pkg eqparbox eqparbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{eqparbox}[2017/09/03]
```

```
\NewDocumentCommand{\LWR@HTML@eqparbox}{O{t} O{} O{t} m +m}{%
```

```
    {%
        \minipagefullwidth%
        \parbox[#1][#2][#3]{\linewidth}{#5}%
    }%
}
\LWR@formatted{eqparbox}

\NewDocumentCommand{\LWR@HTML@eqmakebox}{o o m}{%
    \makebox[#2]{#3}%
}
\LWR@formatted{eqmakebox}

\NewDocumentCommand{\LWR@HTML@eqframebox}{o o m}{%
    \framebox[#2]{#3}%
}
\LWR@formatted{eqframebox}

\NewDocumentEnvironment{LWR@HTML@eqminipage}{O{t} O{} O{t} m}
{%
    \begingroup%
    \minipagefullwidth%
    \minipage[#1][#2][#3]{\linewidth}%
}%
{%
    \endminipage%
    \endgroup%
}

\newcommand*{\LWR@HTML@eqboxwidth}[1]{.25\linewidth}
\LWR@formatted{eqboxwidth}

\newcommand*{\LWR@HTML@eqsetminwidth}[2]{}
\newcommand*{\LWR@HTML@eqsetmaxwidth}[2]{}

\newcommand*{\LWR@HTML@eqsetminwidthto}[2]{}
\newcommand*{\LWR@HTML@eqsetmaxwidthto}[2]{}
```

File 113 **lwarp-errata.sty**

§ 211 Package errata

(*Emulates or patches code by* Michael Kohlhase.)

Pkg errata errata is patched for use by lwarp.

This is for v0.3 of errata. A newer version of errata with more features is under development, at which time the lwarp version will have to be updated.

for HTML output: Macros are being defined with the math dollar, so enable the HTML version during package loading:

```
\StartDefiningMath
```

Now load the package:

```
\LWR@ProvidesPackagePass{errata}[2006/11/12]
```

Patches for dynamic inline math:

```
\xpatchcmd{\erratumAdd}
    {$_a^{\arabic{erratum}}$}
%     {\inlinemathother$_a^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{a}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumAdd}}

\xpatchcmd{\erratumDelete}
    {$_d^{\arabic{erratum}}$}
%     {\inlinemathother$_d^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratumReplace}
    {$_r^{\arabic{erratum}}$}
%     {\inlinemathother$_r^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumReplace}}

\xpatchcmd{\erratum}
    {$_a$}
%     {\inlinemathother$_a$\inlinemathnormal}
    {\textsubscript{a}}
    {}
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratum}
    {$_d^{\@thefnmark}$}
%     {\inlinemathother$_d^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eDelete}}

\xpatchcmd{\erratum}
    {$_r^{\@thefnmark}$}
%     {\inlinemathother$_r^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eReplace}}
```

Finish the current page's errata before closing and reloading the list:

```
\preto\PrintErrata{\LWR@orignewpage}
```

No longer defining math macros with the HTML $:

```
\StopDefiningMath
```

File 114 **lwarp-eso-pic.sty**

§ 212 Package eso-pic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg eso-pic eso-pic is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{eso-pic}[2018/04/12]

\newcommand*{\LenToUnit}{}
\newcommand{\AtPageUpperLeft}[1]{}
\newcommand{\AtPageLowerLeft}[1]{}
\newcommand{\AtPageCenter}[1]{}
\newcommand{\AtStockLowerLeft}[1]{}
\newcommand{\AtStockUpperLeft}[1]{}
\newcommand{\AtStockCenter}[1]{}
\newcommand{\AtTextUpperLeft}[1]{}
\newcommand{\AtTextLowerLeft}[1]{}
\newcommand{\AtTextCenter}[1]{}
\NewDocumentCommand{\AddToShipoutPictureBG}{s +m}{}

\newcommand{\AddToShipoutPicture}{\AddToShipoutPictureBG}
\NewDocumentCommand{\AddToShipoutPictureFG}{s +m}{}
\newcommand*{\ClearShipoutPictureBG}{}
\newcommand*{\ClearShipoutPicture}{}
\newcommand*{\ClearShipoutPictureFG}{}
\newcommand{\gridSetup}[6][]{}
```

File 115 **lwarp-eurosym.sty**

§ 213 Package eurosym

(*Emulates or patches code by* Henrik Theiling.)

Pkg eurosym eurosym is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{eurosym}[1998/08/06]

\renewrobustcmd\officialeuro{\HTMLentity{euro}}
\let\geneuro\officialeuro
\let\geneuronarrow\officialeuro
\let\geneurowide\officialeuro
\let\euro\officialeuro
\renewrobustcmd\eurobars{}
\renewrobustcmd\eurobarsnarrow{}
\renewrobustcmd\eurobarswide{}
```

File 116 **lwarp-everypage.sty**

§ 214 Package everypage

(*Emulates or patches code by* Sergio Callegari.)

Pkg everypage everypage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{everypage}[2007/06/20]

\newcommand*{\AddEverypageHook}[1]{}
\newcommand*{\AddThispageHook}[1]{}
```

File 117 **lwarp-everyshi.sty**

§ 215 Package everyshi

(*Emulates or patches code by* Martin Schröder.)

Pkg everyshi ignored.

for HTML output: Discard all options for lwarp-everyshi:

```
\LWR@ProvidesPackageDrop{everyshi}[2001/05/15]

\newcommand*{\EveryShipout}[1]{}
\newcommand*{\AtNextShipout}[1]{}
```

File 118 **lwarp-extramarks.sty**

§ 216 Package extramarks

(*Emulates or patches code by* Piet van Oostrum.)

Pkg extramarks extramarks is ignored.

for HTML output: Discard all options for lwarp-extramarks:

```
\LWR@ProvidesPackageDrop{extramarks}[2019/01/31]

\newcommand*{\extramarks}[2]{}
\newcommand*{\firstleftxmark}{}
\newcommand*{\lastleftxmark}{}
\newcommand*{\firstrightxmark}{}
\newcommand*{\lastrightxmark}{}
\newcommand*{\firstxmark}{}
```

```
\newcommand*{\lastxmark}{}
\newcommand*{\topxmark}{}
\newcommand*{\topleftxmark}{}
\newcommand*{\toprightxmark}{}
\newcommand*{\firstleftmark}{}
\newcommand*{\lastrightmark}{}
\newcommand*{\firstrightmark}{}
\newcommand*{\lastleftmark}{}
```

File 119 **lwarp-fancybox.sty**

§ 217 Package

fancybox

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancybox fancybox is supported with some patches.

framed equation example fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives \fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example The fancybox documentation's example framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method loses HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim lwarp does not support the verbatim environment inside a span, box, or fancybox's

\Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \beginVerbatim
}{
  \endVerbatim
  \endfminipage
}
```

framed \VerbBox

fancybox's \VerbBox may be used inside \fbox.

indented alignment

LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

fancybox, fancyvrb

⚠ \VerbatimFootnotes

⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\LWR@ProvidesPackagePass{fancybox}[2010/05/15]
```

After the preamble is loaded, after any patches to Verbatim:

```
\AfterEndPreamble{
\LWR@traceinfo{Patching fancybox.}
```

\VerbatimFootnotes

Patched to use the new version.

```
\def\VerbatimFootnotes{%
\let\@footnotetext\V@footnotetext%
\let\LWR@footnotetext\V@footnotetext% lwarp
}
```

\V@@footnotetext

Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@@footnotetext.

```
\def\V@@footnotetext{%
\LWR@traceinfo{V@footnotetext}%
\global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
    \unvbox\LWR@footnotebox%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Use HTML superscripts in the footnote even inside a lateximage:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{}%
```

The footnote text will follow after \V@@@footnotetext has completed.

```
  \bgroup%
  \aftergroup{\V@@@footnotetext}%
  \ignorespaces%
}%

}% AfterEndPreamble

\renewcommand*{\@shadowbox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black]{shadowbox}{#1}}%
{\InlineClass{shadowbox}{#1}}%
}

\renewcommand*{\@doublebox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px double black]{doublebox}{#1}}%
{\InlineClass{doublebox}{#1}}%
}

\renewcommand*{\@ovalbox}[2]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black; border-radius:1ex]{ovalbox}{#2}}%
{%
    \ifthenelse{\isequivalentto{#1}{\thinlines}}%
        {\InlineClass{ovalbox}{#2}}%
        {\InlineClass{Ovalbox}{#2}}%
}%
}
```

Convert minipages, parboxes, and lists into linear text using the LWR@nestspan environment:

```
\let\LWR@origSbox\Sbox
```

```
\def\Sbox{\LWR@origSbox\LWR@nestspan}


\let\LWR@origendSbox\endSbox

\def\endSbox{\endLWR@nestspan\LWR@origendSbox}
```

`Beqnarray` is adapted for MathJax or enclosed inside a `latexmage`:

```
\RenewEnviron{Beqnarray}
{\LWR@eqnarrayfactor}

\csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}
```

`\GenericCaption` is enclosed in an HTML block:

```
\renewcommand{\GenericCaption}[1]{%
\LWR@figcaption%
\LWR@isolate{#1}%
\endLWR@figcaption%
}
```

`Btrivlist` is enclosed in an HTML block. This is a tabular, and does not use `\item`.

`\trivlist` `{`⟨*l/c/r*⟩`}` `[`⟨*t/c/b*⟩`]`

```
\RenewDocumentEnvironment{Btrivlist}{m o}
{%
    \LWR@stoppars%
    \begin{BlockClass}{Btrivlist}%
    \tabular{#1}%
}
{%
    \endtabular%
    \end{BlockClass}%
    \LWR@startpars%
}
```

`Btrivlist` is also neutralized when used inside a span:

```
\AtBeginEnvironment{LWR@nestspan}{%
\RenewDocumentEnvironment{Btrivlist}{m o}{}{}%
}
```

lwarp's handling of `\item` is patched to accept fancybox's optional arguments:

```
\let\LWRFB@origitemizeitem\LWR@itemizeitem
\let\LWRFB@origdescitem\LWR@descitem

\RenewDocumentCommand{\LWR@itemizeitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origitemizeitem[#2]%
```

```
    }{%
        \LWRFB@origitemizeitem%
    }%
}

\RenewDocumentCommand{\LWR@descitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origdescitem[#2]~%
    }{%
        \LWRFB@origdescitem%
    }%
}


\RenewDocumentCommand{\LWR@nestspanitem}{d()}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
\LWR@origitem%
}
```

The various boxed lists become regular lists:

```
\renewenvironment{Bitemize}[1][]{\begin{itemize}}{\end{itemize}}
\renewenvironment{Benumerate}[1][]{\begin{enumerate}}{\end{enumerate}}
\renewenvironment{Bdescription}[1][]{\begin{description}}{\end{description}}
```

`\boxput` simply prints one then the other argument, side-by-side instead of above and behind:

```
\RenewDocumentCommand{\boxput}{s d() m m}{%
\IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
}
```

Neutralized commands:

```
\RenewDocumentCommand{\fancyput}{s d() m}{}
\RenewDocumentCommand{\thisfancyput}{s d() m}{}

\RenewDocumentCommand{\fancypage}{m m}{}
\RenewDocumentCommand{\thisfancypage}{m m}{}

\def\LandScape#1{}
\def\endLandScape{}
\def\@Landscape#1#2#3{}
\def\endLandscape{}
```

Low-level patches for `UseVerbatim` and friends:

```
\let\LWRFB@UseVerbatim\UseVerbatim
\renewcommand*{\UseVerbatim}[1]{%
\LWR@atbeginverbatim{3}{Verbatim}%
\LWRFB@UseVerbatim{#1}%
\LWR@afterendverbatim{.5}%
}
```

```
124
125 \let\LWRFB@LUseVerbatim\LUseVerbatim
126
127 \renewcommand*{\LUseVerbatim}[1]{%
128 \LWR@atbeginverbatim{3}{LVerbatim}%
129 \noindent%
130 \LWRFB@LUseVerbatim{#1}%
131 \LWR@afterendverbatim{.5}%
132 }
133
134 \def\@BUseVerbatim[#1]#2{%
135 \LWR@atbeginverbatim{3}{BVerbatim}%
136 \LWRFB@UseVerbatim{#2}%
137 \LWR@afterendverbatim{.5}%
138 }
```

File 120 **lwarp-fancyhdr.sty**

§ 218 Package

fancyhdr

(*Emulates or patches code by* Piet van Oostrum.)

Pkg fancyhdr fancyhdr is ignored.

for HTML output: Discard all options for lwarp-fancyhdr:

```
1 \LWR@ProvidesPackageDrop{fancyhdr}[2019/01/31]

2 \newcommand*{\fancyhead}[2][]{}
3 \newcommand*{\fancyfoot}[2][]{}
4 \newcommand*{\fancyhf}[2][]{}
5 \newcommand*{\fancypagestyle}[2]{}
6 \newcommand*{\lhead}[2][]{}
7 \newcommand*{\chead}[2][]{}
8 \newcommand*{\rhead}[2][]{}
9 \newcommand*{\lfoot}[2][]{}
10 \newcommand*{\cfoot}[2][]{}
11 \newcommand*{\rfoot}[2][]{}
12 \newcommand*{\headrulewidth}{}
13 \newcommand*{\footrulewidth}{}
14 \newcommand*{\headrule}{}
15 \newcommand*{\footrule}{}
16 \newlength{\headwidth}
17 \newcommand*{\fancyheadoffset}[2][]{}
18 \newcommand*{\fancyfootoffset}[2][]{}
19 \newcommand*{\fancyhfoffset}[2][]{}
20 \newcommand*{\iffloatpage}[2]{#2}
21 \newcommand*{\ifftopfloat}[2]{#2}
22 \newcommand*{\iffbotfloat}[2]{#2}
23 \newcommand*{\iffootnote}[2]{#2}
```

File 121 **lwarp-fancyref.sty**

§ 219 Package

fancyref

Pkg fancyref fancyref is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{fancyref}[1999/02/03]
```

To remove the margin option, if \fancyrefhook is anything other than the paren option, then force it to the default instead. (Comparing to the margin option was not possible since lwarp has revised the meaning of \mbox so the comparison failed.)

```
\newcommand*{\LWRfref@parenfancyrefhook}[1]{(#1)}

\ifdefstrequal{\fancyrefhook}{\LWRfref@parenfancyrefhook}
{}{
    \renewcommand*{\fancyrefhook}[1]{#1}%
}
```

Modified to ignore the page number and varioref.

```
\renewcommand*{\@f@ref}[4]{%
  \@ifundefined{#1r@#2@#3}{%
    \PackageError{lwarp-fancyref}{%
      \backslashchar#1ref\space format ``#2''
      undefined\MessageBreak
      for label type ``#3''%
    }{%
      The format ``#2'' was not defined for the label type
      ``#3''\MessageBreak
      and the \backslashchar#1ref\space command.  Perhaps
      you have only misspelled its name.\MessageBreak
      Otherwise you will have to define it with
      \protect\new#1refformat\MessageBreak
      prior to using it.%
    }%
  }{%
    \fancyrefhook{%
      \@nameuse{#1r@#2@#3}%
        {\ref{#3\fancyrefargdelim#4}}%
%         {\pageref{#3\fancyrefargdelim#4}}% original
%         {\@fancyref@page@ref{#3\fancyrefargdelim#4}}% original
        {}% lwarp
        {}% lwarp
    }%
  }%
}%
```

File 122 **lwarp-fancytabs.sty**

§ 220 Package

fancytabs

Pkg fancytabs fancytabs is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fancytabs}[2016/03/29]

\newcommand{\fancytab}[3][RIGHT]{}
\newcommand{\fancytabsStyle}[1]{}
\newcommand{\fancytabsHeight}[1]{}
\newcommand{\fancytabsWidth}[1]{}
\newcommand{\fancytabsCount}[1]{}
\newcommand{\fancytabsLeftColor}[1]{}
\newcommand{\fancytabsRightColor}[1]{}
\newcommand{\fancytabsTop}[1]{}
\newcommand{\fancytabsTextVPos}[1]{}
\newcommand{\fancytabsTextHPos}[1]{}
\newcommand{\fancytabsGap}[1]{}
\newcommand{\fancytabsFloor}[1]{}
\newcommand{\fancytabsRotate}[1]{}
```

File 123 **lwarp-fancyvrb.sty**

§ 221 Package

fancyvrb

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancyvrb fancyvrb is supported with some patches.

HTML classes

The fancy verbatim environment is placed inside a of class fancyvrb. The label is placed inside a of class fancyvrblabel. The verbatim text itself is placed inside a of class verbatim.

fancybox, fancyvrb

⚠ \VerbatimFootnotes

⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\RequirePackage{xcolor}% for \convertcolorspec
```

```
2
3 \LWR@ProvidesPackagePass{fancyvrb}[2008/02/07]
```

Initial default patch for fancyvrb:

```
4 \fvset{frame=none}%
```

After the preamble is loaded, after any patches to `Verbatim`:

```
5 \AfterEndPreamble{
6 \LWR@traceinfo{Patching fancyvrb.}
```

`\VerbatimFootnotes` Patched to use the new version.

```
7 \def\VerbatimFootnotes{%
8 \let\@footnotetext\V@footnotetext%
9 \let\footnote\V@footnote%
10 \let\LWR@footnotetext\V@footnotetext% lwarp
11 }
```

`\V@@footnotetext` Patches in a subset of lwarp's `\LWR@footnotetext` to the fancyvrb version of `\V@@footnotetext`.

```
12 \def\V@@footnotetext{%
13 \LWR@traceinfo{V@footnotetext}%
14 \global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
15     \unvbox\LWR@footnotebox%
```

Remember the footnote number for `\ref`:

```
16     \protected@edef\@currentlabel{%
17         \csname p@footnote\endcsname\@thefnmark%
18     }% @currentlabel
```

Use HTML superscripts in the footnote even inside a `lateximage`:

```
19     \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
20     \ifthenelse{%
21         \boolean{LWR@doingstartpars} \AND%
22         \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
23     }%
24         {}%
25         {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote mark to the list:

```
26     \@makefntext{}%
```

The footnote text will follow after `\V@@@footnotetext` has completed.

```
27   \bgroup%
28   \aftergroup{\V@@@footnotetext}%
29   \ignorespaces%
30 }%
```

```
\preto\FVB@Verbatim{\LWR@forcenewpage}
\preto\FVB@LVerbatim{\LWR@forcenewpage}
% \preto\FVB@BVerbatim{\LWR@forcenewpage}% Fails, so done below.
```

Simplified to remove PDF formatting:

```
\def\FV@BeginListFrame@Single{%
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Single{%
  \FV@SingleFrameLine{\@ne}%
}

\def\FV@BeginListFrame@Lines{%
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Lines{%
    \FV@SingleFrameLine{\@ne}%
}

\renewcommand*{\FV@SingleFrameSep}{}
```

Adds HTML formatting:

```
\def\FV@BUseVerbatim#1{%
    \LWR@atbeginverbatim{0}{verbatim}%
    \FV@BVerbatimBegin#1\FV@BVerbatimEnd%
    \LWR@afterendverbatim{0}%
}
```

`\LWR@FVstyle` Holds the style of the verbatim.

```
\newcommand*{\LWR@FVstyle}{}
```

The following patches to `Verbatim` are executed at the start and end of the environment, depending on the choice of `frame`. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@fvstartnone}{%
\LWR@traceinfo{fvstartnone}%
% \hbox to\z@{
\BlockClass[\LWR@FVstyle]{fancyvrb}
\LWR@stoppars
\ifx\FV@LabelPositionTopLine\relax\else
    \ifx\FV@LabelBegin\relax\else
        \FancyVerbRuleColor{\LWR@FVfindbordercolor}
        \LWR@htmltagc{%
            div class="fancyvrblabel" % extra space
                style="color: \LWR@origpound\LWR@tempcolor"%
        }
        \LWR@print@textrm{\FV@LabelBegin}% \textrm preserves emdash
```

```
        \LWR@htmltagc{/div}\LWR@orignewline%
    \fi
\fi
\LWR@atbeginverbatim{0}{verbatim}%
% }%
}

\newcommand*{\LWR@fvendnone}{%
\LWR@traceinfo{fvendnone}%
% \hbox to\z@{
\LWR@afterendverbatim{0}%
\LWR@stoppars%
\ifx\FV@LabelPositionBottomLine\relax\else
    \ifx\FV@LabelEnd\relax\else
        \FancyVerbRuleColor{\LWR@FVfindbordercolor}
        \LWR@htmltagc{%
            div class="fancyvrblabel" % extra space
                style="color: \LWR@origpound\LWR@tempcolor"%
        }
        \LWR@print@textrm{\FV@LabelEnd}
        \LWR@htmltagc{/div}\LWR@orignewline%
    \fi
\fi
\endBlockClass
}

\newcommand*{\LWR@fvstartsingle}{%
\LWR@traceinfo{fvstartsingle}%
\LWR@fvstartnone%
\FV@BeginListFrame@Single%
}

\newcommand*{\LWR@fvendsingle}{%
\LWR@traceinfo{fvendsingle}%
\FV@EndListFrame@Single%
\LWR@fvendnone%
}

\newcommand*{\LWR@fvstartline}{%
\LWR@traceinfo{fvstartline}%
\LWR@fvstartnone%
% \setlength{\LWR@templengthone}{\baselineskip}%
\FV@BeginListFrame@Lines%
% \setlength{\baselineskip}{\LWR@templengthone}%
% \setlength{\baselineskip}{5pt}%
}

\newcommand*{\LWR@fvendline}{%
\LWR@traceinfo{fvendline}%
\FV@EndListFrame@Lines%
\LWR@fvendnone%
}
```

The following patches select the start/left/right/end behaviors depending on `frame`. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@FVfindbordercolor}{%
\FancyVerbRuleColor%
\LWR@findcurrenttextcolor%
\color{black}%
}

% border width of \FV@FrameRule
\newcommand*{\LWR@FVborderstyle}[1]{%
padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ; % space
\LWR@FVfindbordercolor\LWR@indentHTMLtwo%
border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt % space
solid {\FancyVerbRuleColor{\LWR@origpound\LWR@tempcolor}} ; % space
}

\def\FV@Frame@none{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle}%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}

\FV@Frame@none% default values

\def\FV@Frame@single{%
\renewcommand*{\LWR@FVstyle}{%
    \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
    \LWR@FVborderstyle{}%
}%
\let\FV@BeginListFrame\LWR@fvstartsingle%
\let\FV@LeftListFrame\FV@LeftListFrame@Single%
\let\FV@RightListFrame\FV@RightListFrame@Single%
\let\FV@EndListFrame\LWR@fvendsingle}

\def\FV@Frame@lines{%
\renewcommand*{\LWR@FVstyle}{%
    \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
    \LWR@FVborderstyle{-top}%
    \LWR@indentHTMLtwo%
    \LWR@FVborderstyle{-bottom}%
}%
\let\FV@BeginListFrame\LWR@fvstartline%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendline}

\def\FV@Frame@topline{%
\renewcommand*{\LWR@FVstyle}{%
    \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
    \LWR@FVborderstyle{-top}%
}%
\let\FV@BeginListFrame\LWR@fvstartline%
\let\FV@LeftListFrame\relax%
```

```
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}

\def\FV@Frame@bottomline{%
\renewcommand*{\LWR@FVstyle}{%
    \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
    \LWR@FVborderstyle{-bottom}%
}%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendline}

\def\FV@Frame@leftline{%
\renewcommand*{\LWR@FVstyle}{%
    \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
    \LWR@FVborderstyle{-left}%
}%
% To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)
\ifx\FancyVerbFillColor\relax%
\let\FV@FrameFillLine\relax%
\else%
\@tempdima\FV@FrameRule\relax%
\multiply\@tempdima-\tw@%
\edef\FV@FrameFillLine{%
{\noexpand\FancyVerbFillColor{\vrule\@width\number\@tempdima sp}%
\kern-\number\@tempdima sp}}%
\fi%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\FV@LeftListFrame@Single%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}
```

Adds the optional label to the top and bottom edges. Original code is from the fancyvrb package.

```
\def\FV@SingleFrameLine#1{%
%   \hbox to\z@{%
%     \kern\leftmargin
    \ifnum#1=\z@\relax
      \let\FV@Label\FV@LabelBegin
    \else
      \let\FV@Label\FV@LabelEnd
    \fi
    \ifx\FV@Label\relax
%       \FancyVerbRuleColor{\vrule \@width\linewidth \@height\FV@FrameRule}%
    \else
      \ifnum#1=\z@
%         \setbox\z@\hbox{\strut\enspace\FV@LabelBegin\enspace\strut}%
        \ifx\FV@LabelPositionTopLine\relax
        \else
        \fi
      \else
%         \setbox\z@\hbox{\strut\enspace\FV@LabelEnd\enspace\strut}%
        \ifx\FV@LabelPositionBottomLine\relax
```

```
        \else
        \fi
      \fi
    \fi
% \hss
% }
}
```

Processes each line, adding optional line numbers. Original code is from the fancyvrb package.

```
\def\FV@ListProcessLine#1{%
  \hbox to \hsize{%
% \kern\leftmargin
    \hbox to \VerbatimHTMLWidth {%
     \ifcsvoid{FV@LeftListNumber}{}{\kern 2.5em}%
      \FV@LeftListNumber%
% \FV@LeftListFrame
    \FancyVerbFormatLine{#1}%
    \hss%
% \FV@RightListFrame
    \FV@RightListNumber%
   }%
    \hss% required to avoid underfull hboxes
}
}
```

Env BVerbatim

```
\AtBeginEnvironment{BVerbatim}
{%
\LWR@forcenewpage% instead of \preto
\LWR@atbeginverbatim{0}{bverbatim}%
}

\AfterEndEnvironment{BVerbatim}
{%
\LWR@afterendverbatim{0}%
}
```

End of the modifications to make at the end of the preamble:

```
} % \AfterEndPreamble
```

File 124 **lwarp-figcaps.sty**

§ 222 Package figcaps

(*Emulates or patches code by* Patrick W. Daly.)

Pkg figcaps figcaps is ignored.

for HTML output: Discard all options for lwarp-figcaps:

```
\LWR@ProvidesPackageDrop{figcaps}[1999/02/23]

\newcommand*{\figcapson}{}
\newcommand*{\figcapsoff}{}
\newcommand*{\printfigures}{}
\newcommand*{\figmarkon}{}
\newcommand*{\figmarkoff}{}
\def\figurecapname{Figure Captions}
\def\tablepagename{Tables}
\def\figurepagename{Figures}
```

File 125 **lwarp-figsize.sty**

§ 223 Package figsize

(*Emulates or patches code by* Anthony A. Tanbakuchi.)

Pkg figsize figsize is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{figsize}[2002/03/18]
```

Emulates a virtual 6×9 inch textsize.

```
\newlength{\figwidth}
\newlength{\figheight}

\newcommand{\SetFigLayout}[3][0]{%
\setlength{\figheight}{8in}%
\setlength{\figheight}{\figheight / #2}%
%
\setlength{\figwidth}{5.5in}%
\setlength{\figwidth}{\figwidth / #3}%
}
```

File 126 **lwarp-fitbox.sty**

§ 224 Package fitbox

Pkg fitbox fitbox is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fitbox}[2019/02/20]

\NewDocumentCommand{\fitbox}{s o m}{%
    \begin{BlockClass}{fitbox}
    #3
    \end{BlockClass}
}
```

```
7
8 \newcommand*{\fitboxset}[1]{}
9
10 \newdimen\fitboxnatheight
11 \newdimen\fitboxnatwidth
12
13 \newcommand\SetFitboxLayout[3][]{}
```

File 127 **lwarp-fix2col.sty**

§ 225 Package

fix2col

Pkg fix2col fix2col is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{fix2col}[2015/11/13]
```

File 128 **lwarp-fixme.sty**

§ 226 Package

fixme

(*Emulates or patches code by* Didier Verna.)

Pkg fixme fixme is patched for use by lwarp.

⚠ external layouts External layouts (`\fxloadlayouts`) are not supported.

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

for HTML output:

```
1 \LWR@ProvidesPackagePass{fixme}[2017/03/05]
```

Restore lwarp's version of `\@wrindex`, ignoring the fixme package's `target` option:

```
2 \let\@wrindex\LWR@wrindex
```

Float-related macros required by lwarp:

```
3 \newcommand{\ext@fixme}{lox}
4
5 \renewcommand{\l@fixme}[2]{\hypertocfloat{1}{fixme}{lox}{#1}{#2}}
```

Other modifications:

```
6 \def\FXFaceInlineHTMLStyle{font-weight:bold}
```

```
7
8 \renewcommand*\FXLayoutInline[3]{ %
9 \InlineClass[\FXFaceInlineHTMLStyle]{fixmeinline}%
10     {\@fxtextstd{#1}{#2}{#3}}%
11 }
12
13 \def\FXFaceEnvHTMLStyle{font-weight:bold}
14
15 \renewcommand*\FXEnvLayoutPlainBegin[2]{%
16 \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
17 \ignorespaces#2 \fxnotename{#1}: \ignorespaces}
18
19 \renewcommand*\FXEnvLayoutPlainEnd[2]{\endBlockClass}
20
21 \renewcommand*\FXEnvLayoutSignatureBegin[2]{%
22 \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
23 \fxnotename{#1}: \ignorespaces}
24
25 \renewcommand*\FXEnvLayoutSignatureEnd[2]{\@fxsignature{#2}\endBlockClass}
26
27 \def\FXFaceSignatureHTMLStyle{font-style:italic}
28
29 \DeclareRobustCommand*\@fxsignature[1]{%
30 \ifthenelse{\equal{#1}{}}%
31     {}%
32     { -- {\InlineClass[\FXFaceSignatureHTMLStyle]{fixmesignature}{#1}}}%
33 }
34
35
36 \def\FXFaceTargetHTMLStyle{font-style:italic}
37
38 \renewcommand\FXTargetLayoutPlain[2]{%
39     \InlineClass[\FXFaceTargetHTMLStyle]{fixmetarget}{#2}%
40 }
```

File 129 **lwarp-fixmetodonotes.sty**

§ 227 Package

fixmetodonotes

(*Emulates or patches code by* Gioele Barabucci.)

Pkg fixmetodonotes fixmetodonotes is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{fixmetodonotes}[2013/04/28]

2 \renewcommand{\NOTES@addtolist}[2]{%
3     \refstepcounter{NOTES@note}%
4 %   \phantomsection% REMOVED
5     \addcontentsline{notes}{NOTES@note}{%
6         \protect\numberline{\theNOTES@note}{{#1}: {#2}}%
7     }%
8 }
9
```

```
\renewcommand{\NOTES@marker}[2]{\fbox{%
    \textcolor{#2}{% WAS \color
        \textbf{#1}}%
    }}

\renewcommand{\NOTES@colorline}[2]{%
  \bgroup%
    \ULon{\LWR@backgroundcolor{#1}{#2}}%
}
```

File 130 **lwarp-flafter.sty**

§ 228 Package flafter

Pkg flafter flafter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flafter}[2018/01/08]
\providecommand\fl@trace[1]{}
```

File 131 **lwarp-flippdf.sty**

§ 229 Package flippdf

Pkg flippdf flippdf is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flippdf}[2006/06/30]

\newcommand\FlipPDF{}
\newcommand\UnFlipPDF{}
```

File 132 **lwarp-float.sty**

§ 230 Package float

(*Emulates or patches code by* Anselm Lingnau.)

Pkg float float is emulated.

Float styles `boxed` and `ruled` are emulated by CSS and a float class according to style.

The HTML `<figure>` `class` is set to the float type, so CSS may also be used to format the float and its caption, according to float type. Furthermore, an additional class is set to the float style: `plain`, `plaintop`, `boxed`, or `ruled`, so CSS may be used to format by float style as well. Default formatting by CSS is provided for `ruled` and `boxed` styles.

for HTML output:

```
\LWR@ProvidesPackageDrop{float}[2001/11/08]
```

`\listof` See section 75.2 for the `\listof` command.

`\LWR@floatstyle` The default float style:

```
\newcommand*{\LWR@floatstyle}{plain}
```

`\newfloat` {⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the `\newfloat` command from the float package.

"placement" is ignored.

```
\NewDocumentCommand{\newfloat}{m m m o}{%
\IfValueTF{#4}%
{\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}%
{\DeclareFloatingEnvironment[fileext=#3]{#1}}%
```

Remember the float style:

```
\csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the `\listof` command for new floats, but float does not, so remove `\listof` here in case it is manually created later.

```
\cslet{listof#1s}\relax%
\cslet{listof#1es}\relax%
```

Likesize, newfloat also creates `\l@<type>`, but float does not, so remove it here:

```
\cslet{l@#1}\relax%
}
```

`\floatname` {⟨*type*⟩} {⟨*name*⟩}

Sets the text name of the float, such as "Figure".

```
\NewDocumentCommand{\floatname}{m +m}{%
    \SetupFloatingEnvironment{#1}{name=#2}%
}
```

`\floatplacement` {⟨*type*⟩} {⟨*placement*⟩}

Float placement is ignored.

```
\newcommand*{\floatplacement}[2]{%
    \SetupFloatingEnvironment{#1}{placement=#2}%
}
```

`\floatstyle` {⟨*style*⟩}

Remember the style for future floats:

```
\newcommand{\floatstyle}[1]{%
    \def\LWR@floatstyle{#1}%
}
```

`\restylefloat` * {⟨*type*⟩}

Remember the style for this float:

```
\NewDocumentCommand{\restylefloat}{s m}{%
    \csedef{LWR@floatstyle@#2}{\LWR@floatstyle}%
}
```

File 133 **lwarp-floatflt.sty**

§ 231 Package

floatflt

(*Emulates or patches code by* Mats Dahlgren.)

Pkg `floatflt` floatflt is emulated.

for HTML output: Discard all options for lwarp-floatflt:

```
\LWR@ProvidesPackageDrop{floatflt}[1997/07/16]
```

Env `[⟨⟩]` offset {⟨*type*⟩} {⟨*width*⟩} Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTfloatflt@marginfloat}{O{-1.2ex} m m}
{%
\setlength{\LWR@templengthone}{#3}%
\LWR@BlockClassWP{%
    float:right; %
    width:\LWR@printlength{\LWR@templengthone};  % extra space
    margin:10pt%
}{%
    width:\LWR@printlength{\LWR@templengthone}%
}%
{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}
```

Env `floatingfigure` [⟨*placement*⟩] {⟨*width*⟩}

```
\DeclareDocumentEnvironment{floatingfigure}{o m}
  {\begin{KFLTfloatflt@marginfloat}{figure}{#2}}
  {\end{KFLTfloatflt@marginfloat}}
```

Env `floatingtable` [⟨*placement*⟩]

```
\DeclareDocumentEnvironment{floatingtable}{o}
  {\begin{KFLTfloatflt@marginfloat}{table}{1.5in}}
  {\end{KFLTfloatflt@marginfloat}}
```

File 134 **lwarp-floatpag.sty**

§ 232 Package

floatpag

(*Emulates or patches code by* Vytas Statulevičius and Sigitas Tolušis.)

Pkg floatpag floatpag is ignored.

for HTML output: Discard all options for lwarp-floatpag:

```
\LWR@ProvidesPackageDrop{floatpag}[2012/05/29]

\newcommand*{\floatpagestyle}[1]{}
\newcommand*{\rotfloatpagestyle}[1]{}
\newcommand*{\thisfloatpagestyle}[1]{}
```

File 135 **lwarp-floatrow.sty**

§ 233 Package

floatrow

(*Emulates or patches code by* Olga Lapko.)

Pkg floatrow floatrow is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{floatrow}[2008/08/02]
```

⚠ Misplaced alignment tab character &

Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 8.10.1.

⚠ subfig package

When combined with the subfig package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ `\FBwidth, \FBheight`

The emulation of floatrow does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether subcaption was loaded. If not, it is assumed that subfig is used instead:

```
\newbool{LWR@subcaptionloaded}

\AtBeginDocument{
\@ifpackageloaded{subcaption}
{\booltrue{LWR@subcaptionloaded}}
{\boolfalse{LWR@subcaptionloaded}}
}
```

\floatbox [⟨*1 preamble*⟩] {⟨*2 captype*⟩} [⟨*3 width*⟩] [⟨*4 height*⟩] [⟨*5 vert pos*⟩] {⟨*6 caption*⟩} {⟨*7 object*⟩}

Only parameters for captype, width, caption, and object are used.

`LWR@insubfloatrow` is true if inside a `subfloatrow` environment.

There are two actions, depending on the use of subcaption or subfig.

```
\NewDocumentCommand{\floatbox}{o m o o o +m +m}{%
\ifbool{LWR@subcaptionloaded}%
{% subcaption
```

For subcaption:

```
    \ifbool{LWR@insubfloatrow}%
    {% subcaption in a subfloatrow
```

`subfigure` and `subtable` environments take width as an argument.

```
        \IfValueTF{#3}%
        {\@nameuse{sub#2}{#3}}%
        {\@nameuse{sub#2}{\linewidth}}%
    }% subcaption in a subfloatrow
    {% subcaption not in subfloatrow
```

`figure` and `table` environments do not take a width argument.

```
        \@nameuse{#2}%
    }% subcaption not in subfloatrow
    #6

    #7
```

End the environments:

```
    \ifbool{LWR@insubfloatrow}%
    {\@nameuse{endsub#2}}%
    {\@nameuse{end#2}}%
}% subcaption
{% assume subfig
```

For subfig:

```
\ifbool{LWR@insubfloatrow}%
{% subfig in a subfloatrow
```

`\subfloat` is a macro, not an environment.

Package subfig's `\subfloat` command takes an optional argument which is the caption, but `\floatbox` argument #6 contains commands to create the caption and label, not the caption itself. Thus, `\caption` is temporarily disabled to return its own argument without braces.

```
    \begingroup
    \let\caption\@firstofone
    \subfloat[#6]{#7}
    \endgroup
}% subfig in a subfloatrow
{% subfig package, but not a subfig
```

figure and table are environments:

```
\@nameuse{#2}
#6

#7
\@nameuse{end#2}
}% subfig package, but not a subfig
}% assume subfig
}
```

Not used:

```
\newcommand*{\nocapbeside}{}
\newcommand*{\capbeside}{}
\newcommand*{\captop}{}
\newlength{\FBwidth}
\setlength{\FBwidth}{.3\linewidth}
\newlength{\FBheight}
\setlength{\FBheight}{2in}
\newcommand*{\useFCwidth}{}
\newcommand{\floatsetup}[2][]{}
\newcommand{\thisfloatsetup}[1]{}
\newcommand{\clearfloatsetup}[1]{}
\newcommand*{\killfloatstyle}{}
```

\newfloatcommand {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\newfloatcommand}{m m o o}{%
\@namedef{#1}{
\floatbox{#2}
}
}
```

\renewfloatcommand {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\renewfloatcommand}{m m o o}{%
\@namedef{#1}{%
\floatbox{#2}
}
}
```

\ffigbox [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ffigbox}{figure}[\nocapbeside][]
```

\ttabbox [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ttabbox}{table}[\captop][\FBwidth]
```

\fcapside [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{fcapside}{figure}[\capbeside][]
```

Env floatrow [⟨*numfloats*⟩]

The row of floats is placed into a of class floatrow.

```
\newenvironment*{floatrow}[1][2]
{
\LWR@forcenewpage
\BlockClass{floatrow}
```

While inside the floatrow, divide the \linewidth by the number of floats.

```
\booltrue{LWR@infloatrow}
\setlength{\linewidth}{6in/#1}
}
{
\boolfalse{LWR@infloatrow}
\endBlockClass
}
```

Keys for \DeclareNewFloatType:

```
\newcommand*{\LWR@frowkeyplacement}{}
\newcommand*{\LWR@frowkeyname}{}
\newcommand*{\LWR@frowkeyfileext}{}
\newcommand*{\LWR@frowkeywithin}{}
\newcommand*{\LWR@frowkeycapstyle}{}

\define@key{frowkeys}{placement}{}%
\define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}%
\define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}%
\define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}%
\define@key{frowkeys}{relatedcapstyle}{}%
```

\DeclareNewFloatType {⟨*type*⟩} {⟨*options*⟩}

Use \listof{type}{Title} to print a list of the floats.

```
\newcommand*{\DeclareNewFloatType}[2]{%
```

Reset key values:

```
\renewcommand*{\LWR@frowkeyplacement}{}%
\renewcommand*{\LWR@frowkeyname}{}%
\renewcommand*{\LWR@frowkeyfileext}{}%
\renewcommand*{\LWR@frowkeywithin}{}%
\renewcommand*{\LWR@frowkeycapstyle}{}%
```

Read new key values:

```
\LWR@traceinfo{about to setkeys frowkeys}%
\setkeys{frowkeys}{#2}%
```

```
\LWR@traceinfo{finished setkeys frowkeys}%
```

Create a new float with optional [within]:

```
\ifthenelse{\equal{\LWR@frowkeywithin}{}}%
{%
    \LWR@traceinfo{about to newfloat #1 \LWR@frowkeyplacement\ %
        \LWR@frowkeyfileext}%
    \newfloat{#1}{\LWR@frowkeyplacement}{\LWR@frowkeyfileext}%
}%
{%
    \LWR@traceinfo{about to newfloat #1\ \LWR@frowkeyplacement\ %
        \LWR@frowkeyfileext\ \LWR@frowkeywithin}%
    \newfloat{#1}{\LWR@frowkeyplacement}%
    {\LWR@frowkeyfileext}[\LWR@frowkeywithin]%
    \LWR@traceinfo{finished newfloat #1}%
}%
```

Rename the float if a name was given:

```
\ifthenelse{\equal{\LWR@frowkeyname}{}}%
    {}%
    {\floatname{#1}{\LWR@frowkeyname}}%
}
```

Not used:

```
\newcommand{\buildFBBOX}[2]{}
\newcommand*{\CenterFloatBoxes}{}
\newcommand*{\TopFloatBoxes}{}
\newcommand*{\BottomFloatBoxes}{}
\newcommand*{\PlainFloatBoxes}{}

\newcommand{\capsubrowsettings}{}

\NewDocumentCommand{\RawFloats}{o o}{}
```

`\RawCaption` {⟨*text*⟩}

To be used inside a minipage or parbox.

```
\newcommand{\RawCaption}[1]{#1}
```

`\floatfoot` {⟨*text*⟩}

Places additional text inside a float, inside a css `<div>` of class `floatfoot`.

```
\NewDocumentCommand{\floatfoot}{s +m}{%
\begin{BlockClass}{floatfoot}
#2
\end{BlockClass}
}
```

Used to compute `\linewidth`.

```
\newbool{LWR@insubfloatrow}
\boolfalse{LWR@insubfloatrow}
```

Env subfloatrow [⟨*num_floats*⟩]

```
\newenvironment*{subfloatrow}[1][2]
{
```

The row of floats is placed into a of class floatrow:

```
\LWR@forcenewpage
\BlockClass{floatrow}
```

While inside the floatrow, LWR@insubfloatrow is set true, which tells \floatbox to use \subfigure or \subtable.

```
\begingroup
\booltrue{LWR@insubfloatrow}
}
{
\endgroup
\endBlockClass
\boolfalse{LWR@insubfloatrow}
}
```

File 136 **lwarp-fltrace.sty**

§ 234 Package fltrace

Pkg fltrace fltrace is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fltrace}[2018/01/08]
```

```
\def\tracefloats{}
\def\tracefloatsoff{}
\def\tracefloatvals{}
```

File 137 **lwarp-flushend.sty**

§ 235 Package flushend

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg flushend flushend is ignored.

for HTML output: Discard all options for lwarp-flushend:

```
\LWR@ProvidesPackageDrop{flushend}[2017/03/27]
```

```
\newcommand*{\flushend}{}
\newcommand*{\raggedend}{}
\newcommand*{\flushcolsend}{}
\newcommand*{\raggedcolsend}{}
\newcommand*{\atColsBreak}[1]{}
```

```
\newcommand*{\atColsEnd}[1]{}
\newcommand*{\showcolsendrule}{}
```

File 138 **lwarp-fnbreak.sty**

§ 236 Package fnbreak

Pkg fnbreak fnbreak is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnbreak}[2012/01/01]
```

```
\newcommand*{\fnbreakverbose}{}
\newcommand*{\fnbreaknonverbose}{}
\newcommand*{\fnbreaklabel}{}
\newcommand*{\fnbreaknolabel}{}
```

File 139 **lwarp-fncychap.sty**

§ 237 Package fncychap

(*Emulates or patches code by* Ulf A. Lindgren.)

Pkg fncychap fncychap is ignored.

for HTML output: Discard all options for lwarp-fncychap:

```
\LWR@ProvidesPackageDrop{fncychap}[2007/07/30]
```

```
\def\mghrulefill#1{}
\def\ChNameLowerCase{}
\def\ChNameUpperCase{}
\def\ChNameAsIs{}
\def\ChTitleLowerCase{}
\def\ChTitleUpperCase{}
\def\ChTitleAsIs{}
\newcommand{\ChRuleWidth}[1]{}
\newcommand{\ChNameVar}[1]{}
\newcommand{\ChNumVar}[1]{}
\newcommand{\ChTitleVar}[1]{}
\newcommand{\TheAlphaChapter}{}
\newcommand{\DOCH}{}
\newcommand{\DOTI}[1]{}
\newcommand{\DOTIS}[1]{}
\newlength{\mylen}
\newlength{\myhi}
\newlength{\px}
\newlength{\py}
\newlength{\pyy}
\newlength{\pxx}
\newlength{\RW}
```

```
\newcommand{\FmN}[1]{#1}
\newcommand{\FmTi}[1]{#1}
```

File 140 **lwarp-fnlineno.sty**

§ 238 Package

fnlineno

Pkg fnlineno fnlineno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnlineno}[2011/01/07]
```

File 141 **lwarp-fnpara.sty**

§ 239 Package

fnpara

Pkg fnpara fnpara is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpara}
```

File 142 **lwarp-fnpos.sty**

§ 240 Package

fnpos

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg fnpos fnpos is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpos}[1999/07/14]

\newcommand*{\makeFNbottom}{}
\newcommand*{\makeFNmid}{}
\newcommand*{\makeFNbelow}{}
\newcommand*{\makeFNabove}{}
```

File 143 **lwarp-fontawesome.sty**

§ 241 Package

fontawesome

(*Emulates or patches code by* Xavier Danaux.)

Pkg fontawesome fontawesome is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

⚠ *poppler* syntax warning If using pdfLaTeX, *poppler* may issue a syntax warning regarding parsing a ligature

component. XeLaTeX or LuaLaTeX may be used to avoid this warning.

In the following, the general strategy is to intercept `\symbol` and embed it inside a `lateximage`. These changes are done inside a local group.

For pdfLaTeX, the `alt` tag includes the icon (symbol) number. For XeLaTeX and LuaLaTeX, the `alt` tag is generic.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome}[2016/05/15]

\LetLtxMacro\LWR@orig@symbol\symbol

\ifxetexorluatex

\newfontfamily{\LWR@orig@FA}{FontAwesome}

\newcommand*{\LWR@fontawesome@xelatex@symbol}[1]{%
\begin{lateximage}*[icon][fontawesomexetex#1]%
\begingroup%
\LWR@orig@FA%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\RenewDocumentCommand{\FA}{}{%
    \LetLtxMacro\symbol\LWR@fontawesome@xelatex@symbol%
}

\else

\newcommand*{\LWR@fontawesome@symbolone}[1]{%
\begin{lateximage}*[icon #1][fontawesomeone#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesomeone}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\newcommand*{\LWR@fontawesome@symboltwo}[1]{%
\begin{lateximage}*[icon #1][fontawesometwo#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesometwo}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\newcommand*{\LWR@fontawesome@symbolthree}[1]{%
\begin{lateximage}*[icon #1][fontawesomethree#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesomeonethree}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
```

```
\end{lateximage}%
}

\renewrobustcmd\FAone{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolone%
}

\renewrobustcmd\FAtwo{%
    \LetLtxMacro\symbol\LWR@fontawesome@symboltwo%
}

\renewrobustcmd\FAthree{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolthree%
}
\fi
```

File 144 **lwarp-fontawesome5.sty**

§ 242 Package fontawesome5

(*Emulates or patches code by* Marcel Krüger.)

Pkg fontawesome5 fontawesome5 is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

The `alt` tag has the name of the icon.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome5}[2018/07/27]

\ExplSyntaxOn
\cs_set:Nn\fontawesome_use_icon:nn{
  \cs_if_exist:cTF{c__fontawesome_slot_#2_tl}{
    \begin{lateximage}*[#2][#1]
    \exp_last_unbraced:Nv
      \__fontawesome_icon_at:nnnn
      {c__fontawesome_slot_#2_tl}
        {#1}{#2}
    \end{lateximage}
  }{
    \msg_error:nnxx{fontawesome5}{icon-not-found}{#2}{#1}
  }
}
\ExplSyntaxOff
```

File 145 **lwarp-fontaxes.sty**

§ 243 Package fontaxes

(*Emulates or patches code by* Andreas Bühmann, Michael Ummels.)

Pkg fontaxes

fontaxes is emulated for HTML, and used as-is for print output.

Functionality for small caps is in the lwarp core. Swashes and figure styles are ignored for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{fontaxes}[2014/03/23]

\newrobustcmd{\LWR@HTML@sscshape}{\LWR@HTML@scshape}
\LWR@formatted{sscshape}
\newcommand*{\LWR@null@sscshape}{}

\newrobustcmd{\LWR@HTML@textssc}[1]{\textsc{#1}}
\LWR@formatted{textssc}
\newcommand*{\LWR@null@textssc}[1]{#1}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by nfssext-cfr
    \newcommand{\LWR@HTML@swshape}{}
    \LWR@formatted{swshape}
    \newcommand*{\LWR@null@swshape}{}

    \newcommand{\LWR@HTML@textsw}[1]{#1}
    \LWR@formatted{textsw}
    \newcommand*{\LWR@null@textsw}[1]{#1}
}

\appto{\LWR@nullfonts}{%
\LetLtxMacro\sscshape\LWR@null@sscshape%
\LetLtxMacro\textssc\LWR@null@textssc%
\LetLtxMacro\swshape\LWR@null@swshape%
\LetLtxMacro\textsw\LWR@null@textsw%
}
```

File 146 **lwarp-fontenc.sty**

§ 244 Package fontenc

Pkg fontenc

If using pdfLaTeX, lwarp used to require fontenc be loaded before lwarp, but now lwarp itself loads `\fontenc` with T1 encoding, which lwarp requires. fontenc is now allowed to be loaded with another encoding after lwarp.

lwarp-fontenc is no longer necessary, but is still provided to overwrite older versions.

for HTML output:

```
\LWR@ProvidesPackagePass{fontenc}[2017/04/05]
```

File 147 **lwarp-footmisc.sty**

§ 245 Package footmisc

(*Emulates or patches code by* Robin Fairbairns.)

Pkg footmisc footmisc is emulated.

lwarp incidentally happens to emulate the `stable` option.

```
\LWR@ProvidesPackageDrop{footmisc}[2011/06/06]
```

Some nullified commands:

```
\newcommand{\footnotelayout}{}
\newcommand{\setfnsymbol}[1]{}
\NewDocumentCommand{\DefineFNsymbols}{s m o m}{}

\newdimen\footnotemargin
\footnotemargin1.8em\relax

\newcommand*\hangfootparskip{0.5\baselineskip}
\newcommand*\hangfootparindent{0em}%

\let\pagefootnoterule\footnoterule
\let\mpfootnoterule\footnoterule
\def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}

\providecommand*{\multiplefootnotemarker}{3sp}
\providecommand*{\multfootsep}{,}
```

Using cleveref:

```
\providecommand*{\footref}[1]{\labelcref{#1}}
```

The following work as-is:

```
\newcommand\mpfootnotemark{%
  \@ifnextchar[%
    \@xmpfootnotemark%
    {%
      \stepcounter\@mpfn%
      \protected@xdef\@thefnmark{\thempfn}%
      \@footnotemark%
    }%
}
\def\@xmpfootnotemark[#1]{%
  \begingroup%
    \csname c@\@mpfn\endcsname #1\relax%
    \unrestored@protected@xdef\@thefnmark{\thempfn}%
  \endgroup%
  \@footnotemark%
}
```

File 148 **lwarp-footnote.sty**

§ 246 Package footnote

(*Emulates or patches code by* Mark Wooding.)

Pkg footnote footnote is used with minor patches.

for HTML output:

```
\LWR@ProvidesPackagePass{footnote}[1997/01/28]
```

Removed print-version formatting:

```
\def\fn@startnote{%
%   \@parboxrestore%
  \protected@edef\@currentlabel{\csname p@\@mpfn\endcsname\@thefnmark}%
%   \color@begingroup% *** conflicts with lwarp
}

% \let\fn@endnote\color@endgroup% *** conflicts with lwarp
\def\fn@endnote{%
\LWR@htmltagc{/\LWR@tagregularparagraph}%
\LWR@orignewline%
}
```

Removed print-version formatting:

```
\def\fn@startfntext{%
  \setbox\z@\vbox\bgroup%
    \fn@startnote%
    \ignorespaces%
}
```

Removed print-version formatting, added closing paragraph tag:

```
\def\fn@endfntext{%
    \LWR@htmltagc{/\LWR@tagregularparagraph}%
    \LWR@orignewline%
  \egroup%
  \begingroup%
    \let\@makefntext\@empty%
    \let\@finalstrut\@gobble%
    \LetLtxMacro\rule\@gobbletwo% *8* also the optional argument?
    \@footnotetext{\unvbox\z@}%
  \endgroup%
}
```

These have been redefined, so re-`\let` them again:

```
\let\endfootnote\fn@endfntext
\let\endfootnotetext\endfootnote
```

File 149 **lwarp-footnotebackref.sty**

§ 247 Package

footnotebackref

Pkg footnotebackref footnotebackref is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnotebackref}[2012/07/01]
```

File 150 **lwarp-footnotehyper.sty**

§ 248 Package footnotehyper

Pkg footnotehyper footnotehyper is a hyperref-safe version of footnote. For lwarp, footnotehyper is emulated.

for HTML output: Discard all options for lwarp-footnotehyper:

```
\RequirePackage{footnote}
\LWR@ProvidesPackageDrop{footnotehyper}[2018/01/23]
```

File 151 **lwarp-footnoterange.sty**

§ 249 Package footnoterange

(*Emulates or patches code by* H.-Martin Münch.)

Pkg footnoterange footnoterange is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{footnoterange}[2012/02/17]

\csletcs{footnoterange}{footnoterange*}
\csletcs{endfootnoterange}{endfootnoterange*}
```

File 152 **lwarp-footnpag.sty**

§ 250 Package footnpag

Pkg footnpag footnpag is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnpag}
```

File 153 **lwarp-foreign.sty**

§ 251 Package foreign

(*Emulates or patches code by* Philip G. Ratcliffe.)

Pkg foreign foreign is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{foreign}[2012/09/25]
```

```
\renewcommand\foreignabbrfont{\emph}
```

File 154 **lwarp-forest.sty**

§ 252 Package

forest

(*Emulates or patches code by* Sašo Živanović.)

Pkg forest forest is patched for use by lwarp.

⚠ \Forest* The starred version of the macro \Forest* is not supported. lwarp encases each lateximage in an environment, so the global results of the starred \Forest* are lost.

for HTML output:

```
\LWR@ProvidesPackagePass{forest}[2017/07/14]

\BeforeBeginEnvironment{forest}{\begin{lateximage}[forest]}

\AfterEndEnvironment{forest}{\end{lateximage}}

\RenewDocumentCommand{\Forest}{s D(){} m}{%
  \forest@config{#2}%
  \IfBooleanTF{#1}{%
        \PackageError{lwarp-forest}%
        {Starred \Forest is not supported}%
     {Lwarp uses an environment for images, but \Forest* cannot work in an environment.}%
        \let\forest@next\forest@env%
    }{\let\forest@next\forest@group@env}%
    \begin{lateximage}[-forest-~\PackageDiagramAltText]%     lwarp
  \forest@next{#3}%
    \end{lateximage}%               lwarp
}
```

File 155 **lwarp-framed.sty**

§ 253 Package

framed

(*Emulates or patches code by* Donald Arseneau.)

Pkg framed framed is supported and patched by lwarp.

for HTML output: Accept all options for lwarp-framed:

```
\LWR@ProvidesPackagePass{framed}[2011/10/22]
\RequirePackage{xcolor}% for \convertcolorspec

\renewenvironment{framed}{%
\LWR@forcenewpage
\BlockClass{framed}%
}
```

```
{\endBlockClass}

\renewenvironment{oframed}{%
\LWR@forcenewpage
\BlockClass{framed}%
}
{\endBlockClass}


\renewenvironment{shaded}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
}
{\endBlockClass}

\renewenvironment{shaded*}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
}
{\endBlockClass}


\renewenvironment{leftbar}{%
\LWR@forcenewpage
    \BlockClass{framedleftbar}
  \def\FrameCommand{}%
  \MakeFramed {}
}%
 {\endMakeFramed\endBlockClass}


\renewenvironment{snugshade}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\renewenvironment{snugshade*}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\let\oframed\framed
\let\endoframed\endframed


\RenewEnviron{titled-frame}[1]{%
\CustomFBox{#1}{}{0pt}{0pt}{0pt}{0pt}{\BODY}
}
```

\CustomFBox {⟨*toptitle*⟩} {⟨*bottitle*⟩} {⟨*thicknesstop*⟩} {⟨*bottom*⟩} {⟨*left*⟩} {⟨*right*⟩} {⟨*text contents*⟩}

```
\renewcommand{\CustomFBox}[7]{%
\convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\begin{BlockClass}[border: 3px solid \LWR@origpound\LWR@tempcolor]{framed}%
\ifthenelse{\isempty{#1}}{}{% not empty
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#1}}%
    \end{BlockClass}
}% not empty

#7

\ifthenelse{\isempty{#2}}{}{% not empty
    \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#2}}%
    \end{BlockClass}
}% not empty
\end{BlockClass}
}
```

\TitleBarFrame [⟨*marker*⟩] {⟨*title*⟩} {⟨*contents*⟩}

```
\renewcommand\TitleBarFrame[3][]{
\CustomFBox
    {#2}{}%
    \fboxrule\fboxrule\fboxrule\fboxrule
    {#3}%
}

\renewcommand{\TF@Title}[1]{#1}
```

MakeFramed {⟨*settings*⟩}

```
\let\MakeFramed\relax
\let\endMakeFramed\relax

\NewEnviron{MakeFramed}[1]{%
\FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
}
```

\fb@put@frame {⟨*frame cmd no split*⟩} {⟨*frame cmd split*⟩}

```
\renewcommand*{\fb@put@frame}[2]{%
\relax%
\@tempboxa%
}
```

File 156 **lwarp-ftcap.sty**

§ 254 Package ftcap

Pkg ftcap ftcap is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ftcap}
```

File 157 **lwarp-ftnright.sty**

§ 255 Package ftnright

Pkg ftnright ftnright is ignored.

for HTML output: Discard all options for lwarp-ftnright:

```
\LWR@ProvidesPackageDrop{ftnright}[2014/10/28]
```

File 158 **lwarp-fullminipage.sty**

§ 256 Package fullminipage

Pkg fullminipage fullminipage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fullminipage}[2014/07/06]
\newenvironment{fullminipage}[1][]{}{}
```

File 159 **lwarp-fullpage.sty**

§ 257 Package fullpage

Pkg fullpage fullpage is ignored.

for HTML output: Discard all options for lwarp-fullpage:

```
\LWR@ProvidesPackageDrop{fullpage}[1994/06/01]
```

File 160 **lwarp-fullwidth.sty**

§ 258 Package fullwidth

(*Emulates or patches code by* Marco Daniel.)

Pkg fullwidth fullwidth is emulated.

A minipage is used, of no HTML width.

for HTML output:

```
\LWR@ProvidesPackageDrop{fullwidth}[2011/11/18]

\newenvironment*{fullwidth}[1][]{%
\minipagefullwidth%
\minipage{\linewidth}%
}
{%
\endminipage%
}
```

File 161 **lwarp-fwlw.sty**

§ 259 Package fwlw

Pkg fwlw fwlw is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fwlw}

\newbox\FirstWordBox      \global\setbox\FirstWordBox\hbox{}
\newbox\NextWordBox       \global\setbox\NextWordBox\hbox{}
\newbox\LastWordBox       \global\setbox\LastWordBox\hbox{}
\def\ps@fwlwhead{}
\def\ps@NextWordFoot{}
```

File 162 **lwarp-gentombow.sty**

§ 260 Package gentombow

Pkg gentombow gentombow is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gentombow}[2018/05/17]

\newcommand{\settombowbanner}[1]{}
\newcommand{\settombowbannerfont}[1]{}
\newcommand{\settombowwidth}[1]{}
\newcommand{\settombowbleed}[1]{}
\newcommand{\settombowcolor}[1]{}
```

File 163 **lwarp-geometry.sty**

§ 261 Package geometry

(*Emulates or patches code by* Hideo Umeki.)

Pkg geometry geometry is preloaded by lwarp, but must be nullified as seen by the user's source code.

for HTML output: Discard all options for lwarp-geometry:

```
\LWR@ProvidesPackageDropA{geometry}{2018/04/16}
```

If geometry is never loaded by the user, it will be loaded by lwarp `\AtBeginDocument`. If this is the case, the page layout should not be changed but the user macros should still be nullified.

```
\ifbool{LWR@allowanothergeometry}{%
```

Gather all options:

```
\newcommand*{\LWR@newgeometryoptions}{reset,}

\DeclareOption*{%
    \edef\LWR@newgeometryoptions{\LWR@newgeometryoptions\CurrentOption,}%
}
```

Process the options:

```
\ProcessOptions\relax
```

Assign and set the selected geometry. `\AtEndPreamble` lwarp will save this, then set its own geometry.

```
\ifdefvoid{\LWR@newgeometryoptions}{}{
    \expandafter\LWR@origgeometry\expandafter{\LWR@newgeometryoptions}
}

}{}% LWR@allowanothergeometry
```

The user-level commands are nullified:

```
\renewcommand*{\geometry}[1]{}
\renewcommand*{\newgeometry}[1]{}
\renewcommand*{\restoregeometry}{}
\renewcommand*{\savegeometry}[1]{}
\renewcommand*{\loadgeometry}[1]{}
```

File 164 **lwarp-gloss.sty**

§ 262 Package

gloss

(*Emulates or patches code by* Jose Luis Díiaz, Javier Bezos.)

Pkg gloss gloss is patched for use by lwarp.

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

for HTML output:

```
\LWR@ProvidesPackagePass{gloss}[2002/07/26]
```

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\xpatchcmd{\gls@gloss@iii}
   {\thepage}
   {\theLWR@previousautopagelabel}
   {}
   {\LWR@patcherror{gloss}{gls@gloss@iii}}

\def\gls@page@i#1#2{%
  \endgroup%
  \global\@namedef{glsp@#1}{\nameref{\BaseJobname-autopage-#2}}}%
```

File 165 **lwarp-glossaries.sty**

§ 263 Package

glossaries

(*Emulates or patches code by* Nicola L.C. Talbot.)

Pkg glossaries

processing glossaries

Opt GlossaryCmd

Default: makeglossaries

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

lwarpmk has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

The shell command to execute is set by the lwarp option `GlossaryCmd`, which defaults to **`makeglossaries`**. The print or HTML glossary filename is appended to this command.

⚠ *makeglossaries* not found

In some situations it may be required to modify the default command, such as to add the **`perl`** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and TOC options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style

The default `style=item` option for glossaries conflicts with lwarp, so the style is forced to `index` instead.

⚠ number list

The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions

The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

for HTML output:

```
\PassOptionsToPackage{xindy}{glossaries}

\LWR@ProvidesPackagePass{glossaries}[2018/07/23]

\setupglossaries{nonumberlist}
\setglossarystyle{index}
```

Patched to fix TOC pointing to the previous page:

```
\renewcommand*{\@p@glossarysection}[2]{%
  \glsclearpage
  \phantomsection
  \ifdefempty\@@glossarysecstar
  {%
    \csname\@@glossarysec\endcsname{#2}%
  }%
  {%
```

In the original, the TOC entry was made before the section, thus linking to the phantomsection in the printed version, but for HTML, this caused the link to point to the page before the glossaries, which could be a different HTML file. Here, the TOC entry is made after the section is created:

```
      \csname\@@glossarysec\endcsname*{#2}%
    \@gls@toc{#1}{\@@glossarysec}% Moved after the previous line.
  }%
  \@@glossaryseclabel
}
```

lwarp's sectioning commands cannot handle robust macros when splitting HTML into named filenames. glossaries uses `\translate` in sectioning names, and `\translate` is

robust and cannot be expanded. The following pre-expands the translations at this moment, making use of \translatelet.

```
\newcommand*{\LWR@comp@glossaryname}{\translate{Glossary}}

\ifdefstrequal{\glossaryname}{\LWR@comp@glossaryname}{
    \translatelet\LWR@translatetemp{Glossary}
    \edef\glossaryname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@acronymname}{\translate{Acronym}}

\ifdefstrequal{\acronymname}{\LWR@comp@acronymname}{
    \translatelet\LWR@translatetemp{Acronym}
    \edef\acronymname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glssymbolsgroupname}{\translate{Symbols (glossaries)}}

\ifdefstrequal{\glssymbolsgroupname}{\LWR@comp@glssymbolsgroupname}{
    \translatelet\LWR@translatetemp{Symbols (glossaries)}
    \edef\glssymbolsgroupname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glsnumbersgroupname}{\translate{Numbers (glossaries)}}

\ifdefstrequal{\glsnumbersgroupname}{\LWR@comp@glsnumbersgroupname}{
    \translatelet\LWR@translatetemp{Numbers (glossaries)}
    \edef\glsnumbersgroupname{\LWR@translatetemp}
}{}
```

File 166 **lwarp-gmeometric.sty**

§ 264 Package gmeometric

Pkg gmeometric gmeometric is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gmeometric}[2008/11/22]
```

File 167 **lwarp-graphics.sty**

§ 265 Package graphics

(*Emulates or patches code by* D. P. Carlisle.)

Pkg graphics graphics is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{graphics}[2017/06/25]
```

§ 265.1 Graphics extensions

\DeclareGraphicsExtensions {⟨*list*⟩}

\AtBeginDocument allow SVG files instead of PDF:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Inside a lateximage, allow PDF instead of SVG:

```
\ifpdf
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
\else% \ifpdf
        \ifXeTeX
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \else
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \fi
\fi
```

§ 265.2 Length conversions and graphics options

⚠ whitespace

A scaled image in LaTeX by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

Used to store the user's selected dimensions and HTML class.

The class defaults to "inlineimage" unless changed by a class=xyx option.

```
\newlength{\LWR@igwidth}
\newlength{\LWR@igheight}
\newcommand*{\LWR@igwidthstyle}{}
\newcommand*{\LWR@igheightstyle}{}
\newcommand*{\LWR@igorigin}{}
\newcommand*{\LWR@igangle}{}
\newcommand*{\LWR@igxscale}{1}
\newcommand*{\LWR@igyscale}{1}
\newcommand*{\LWR@igclass}{inlineimage}
```

```
\newcommand*{\LWR@igalt}{\ImageAltText}
```

Set the actions of each of the key/value combinations for \includegraphics. Many are ignored.

If an optional width was given, set an HTML style:

```
\define@key{igraph}{width}{%
\setlength{\LWR@igwidth}{#1}%
\ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes px
    {}% not px
}{}% end of length > 0pt
}
```

If an optional height was given, set an HTML style:

```
\define@key{igraph}{height}{%
\setlength{\LWR@igheight}{#1}%
\ifthenelse{\lengthtest{\LWR@igheight > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igheightstyle}{%
    height:\LWR@printlength{\LWR@igheight} % extra space
    }%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes px
```

```
    {}% not px
}{}% end of length > 0pt
}
```

Handle `origin` key:

```
\define@key{igraph}{origin}[c]{%
    \renewcommand*{\LWR@igorigin}{#1}%
}
```

Handle `angle` key:

```
\define@key{igraph}{angle}{\renewcommand*{\LWR@igangle}{#1}}
```

Handle `class` key:

```
\define@key{igraph}{class}{\renewcommand*{\LWR@igclass}{#1}}
```

Handle `alt` key:

```
\define@key{igraph}{alt}{\renewcommand*{\LWR@igalt}{#1}}
```

It appears that graphicx does not have separate keys for `xscale` and `yscale`. `scale` adjusts both at the same time.

```
\define@key{igraph}{scale}{%
    \ifthenelse{\equal{#1}{1}}{}{%  must expand #1
        \PackageWarning{lwarp}{%
            It is recommended to use\MessageBreak
            [width=xx\protect\linewidth]\MessageBreak
            instead of [scale=yy],%
        }%
    }%
    \renewcommand*{\LWR@igxscale}{#1}%
    \renewcommand*{\LWR@igyscale}{#1}%
}
```

Numerous ignored keys:

```
\define@key{igraph}{bb}{}
\define@key{igraph}{bbllx}{}
\define@key{igraph}{bblly}{}
\define@key{igraph}{bburx}{}
\define@key{igraph}{bbury}{}
\define@key{igraph}{natwidth}{}
\define@key{igraph}{natheight}{}
\define@key{igraph}{hiresbb}[true]{}
\define@key{igraph}{viewport}{}
\define@key{igraph}{trim}{}
\define@key{igraph}{totalheight}{}
\define@key{igraph}{keepaspectratio}[true]{}
\define@key{igraph}{clip}[true]{}
\define@key{igraph}{draft}[true]{}
\define@key{igraph}{type}{}
```

```
\define@key{igraph}{ext}{}
\define@key{igraph}{read}{}
\define@key{igraph}{command}{}
```

New in v1.1a:

```
\define@key{igraph}{quite}{}
\define@key{igraph}{page}{}
\define@key{igraph}{pagebox}{}
\define@key{igraph}{interpolate}[true]{}
```

New in v1.1b:

```
\define@key{igraph}{decodearray}{}
```

§ 265.3 Printing HTML styles

`\LWR@rotstyle` {⟨*prefix*⟩} {⟨*degrees*⟩}

Prints the rotate style with the given prefix.

`prefix` is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:rotate` style.

```
\newcommand*{\LWR@rotstyle}[2]{%
 #1transform:rotate(-#2deg);
}
```

`\LWR@scalestyle` {⟨*prefix*⟩} {⟨*xscale*⟩} {⟨*yscale*⟩}

Prints the scale style with the given prefix.

`prefix` is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:scale` style.

```
\newcommand*{\LWR@scalestyle}[3]{%
 #1transform:scale(#2,#3);
}
```

§ 265.4 `\includegraphics`

Bool `LWR@infloatrow` Used to compute `\linewidth`.

```
\newbool{LWR@infloatrow}
\boolfalse{LWR@infloatrow}
```

`\LWR@opacity` For HTML, used only for `\includegraphics`.

`\LWR@opacity` may be set by the transparent package.

```
\def\LWR@opacity{1}
```

\LWR@imagesizebox Used to determine the actual image size if needed.

```
\newsavebox{\LWR@imagesizebox}
```

\LWR@HTML@Gin@setfile {⟨*w*⟩} {⟨*h*⟩} {⟨*filename*⟩} Sets the parsed filename for HTML output.

```
\newcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \xdef\LWR@parsedfilename{#3}%
}
```

Key [Gin] class CSS class for the image.

Define the new class key for the print-mode version of `\includegraphics`, which is enabled inside a `lateximage`.

```
\AtBeginDocument{
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
}
```

\LWR@replaceEPSSVG Usually, references to EPS files become SVG files, but if the epstopdf package is being used, it automatically converts EPS to PDF, and the following must NOT be done.

```
\AtBeginDocument{
\@ifpackageloaded{epstopdf}
{
    \newcommand*{\LWR@replaceEPSSVG}{}
}{%
    \newcommand*{\LWR@replaceEPSSVG}{%
        \StrSubstitute{\LWR@tempone}{.eps}{.svg}[\LWR@tempone]%
        \StrSubstitute{\LWR@tempone}{.EPS}{.SVG}[\LWR@tempone]%
    }
}%
}
```

\LWR@includegraphicsb * [⟨*2: options*⟩] [⟨*3: options*⟩] {⟨*4: filename*⟩}

graphics syntax is `\includegraphics` * [⟨*llx,lly*⟩] [⟨*urx,ury*⟩] {⟨*file*⟩}

graphicx syntax is `\includegraphics` [⟨*key values*⟩] {⟨*file*⟩}

If `#3` is empty, only one optional argument was given, thus graphicx syntax.

If using `\epsfig` or `\psfig` from the epsfig package, `#4` will be `\LWR@epsfig@filename`, which will have been set by the `file` or `figure` keys. Therefore, `#4` must not be used until after the keys have been processed.

```
\NewDocumentCommand{\LWR@includegraphicsb}{s o o m}
{%
```

Start the image tag on a new line, allow PDF output word wrap:

```
\LWR@origtilde \LWR@orignewline%
```

Temporarily compute \linewidth, \textwidth, \textheight arguments with a 6x9 inch size until the next \endgroup.

```
\begingroup%
\ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}%
{%
    \ifbool{LWR@infloatrow}%
    {}
    {% not in a minipage or a floatrow:
        \setlength{\linewidth}{6in}%
        \setlength{\textwidth}{6in}%
        \setlength{\textheight}{9in}%
    }%
}{}%
```

For correct em sizing during the width and height conversions:

```
\large%
```

Reset some defaults, possibly will be changed below if options were given:

```
\setlength{\LWR@igwidth}{0pt}%
\setlength{\LWR@igheight}{0pt}%
\renewcommand*{\LWR@igwidthstyle}{}%
\renewcommand*{\LWR@igheightstyle}{}%
\renewcommand*{\LWR@igorigin}{}%
\renewcommand*{\LWR@igangle}{}%
\renewcommand*{\LWR@igxscale}{1}%
\renewcommand*{\LWR@igyscale}{1}%
\renewcommand*{\LWR@igclass}{inlineimage}%


\ifdefvoid{\LWR@ThisAltText}{%
    \renewcommand*{\LWR@igalt}{\ImageAltText}%
}{%
    \renewcommand*{\LWR@igalt}{\LWR@ThisAltText}%
}%
```

If #3 is empty, only one optional argument was given, thus graphicx syntax:

```
\IfValueF{#3}{%
    \IfValueTF{#2}%
        {\setkeys{igraph}{#2}}%
        {\setkeys{igraph}{}}%
}%
```

Fully expand and detokenize the filename, changing the file extension to .svg if necessary.

```
\begingroup%
\LetLtxMacro\Gin@setfile\LWR@HTML@Gin@setfile%
\edef\LWR@tempone{#4}%
\StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
\StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
\LWR@replaceEPSSVG%
```

```
\xdef\LWR@parsedfilename{\LWR@tempone}%
\Ginclude@graphics{\detokenize\expandafter{\LWR@tempone}}%
\endgroup%
\filename@parse{\LWR@parsedfilename}%
\LWR@traceinfo{LWR@parsedfilename is \LWR@parsedfilename}%
% \LWR@sanitize{\LWR@parsedfilename}%
```

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```
\ifbool{FormatWP}{%
    \begingroup%
    \LWR@restoreorigformatting%
    \ifpdf%
    \appto\LWR@restoreorigformatting{%
  \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
    }%
    \else% \ifpdf
            \ifXeTeX%
    \appto\LWR@restoreorigformatting{%
  \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
    }%
            \else%
    \appto\LWR@restoreorigformatting{%
  \DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
    }%
            \fi%
    \fi% \ifpdf
    \define@key{Gin}{angle}{}%
    \IfBooleanTF{#1}%
    {% starred
        \IfValueTF{#3}%
        {%
        \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics*[#2][#3]{#4}}%
        }%
        {%
            \IfValueTF{#2}%
            {%
           \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics*[#2]{#4}}%
            }{%
               \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics*{#4}}%
            }%
        }%
    }% starred
    {% not starred
        \IfValueTF{#3}%
        {%
        \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics[#2][#3]{#4}}%
        }%
        {%
            \IfValueTF{#2}%
            {%
            \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics[#2]{#4}}%
            }{%
                \global\sbox{\LWR@imagesizebox}{\LWR@originincludegraphics{#4}}%
```

```
            }%
        }%
    }% not starred
    \endgroup%
    \settowidth{\LWR@igwidth}{\usebox{\LWR@imagesizebox}}%
   \global\renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
    \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
   \global\renewcommand*{\LWR@igheightstyle}{height:\LWR@printlength{\LWR@igheight}}%
}{}% FormatWP
```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class.

The \LWR@origtilde adds space between tags in case this is being done inside a \savebox where \newline has no effect.

```
\LWR@traceinfo{LWR@includegraphicsb: about to create href}%
\href{\LWR@parsedfilename}%
{% start of href
\LWR@traceinfo{LWR@includegraphicsb: about to LWR@htmltag}%
\LWR@htmltag{% start of image tags
img\LWR@indentHTML%
src="%

\detokenize\expandafter{\LWR@parsedfilename}%

"\LWR@indentHTML%
```

Only include a style tag if a width, height, angle, or scale was given:

```
\ifthenelse{
    \NOT\equal{\LWR@igwidthstyle}{} \OR
    \NOT\equal{\LWR@igheightstyle}{} \OR
    \NOT\equal{\LWR@igorigin}{} \OR
    \NOT\equal{\LWR@igangle}{} \OR
    \NOT\equal{\LWR@igxscale}{1} \OR
    \NOT\equal{\LWR@igyscale}{1}
}%
{%
    style="\LWR@indentHTML
    \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{}}%
        {\LWR@igwidthstyle;\LWR@indentHTML}{}%
    \ifthenelse{\NOT\equal{\LWR@igheightstyle}{}}%
        {\LWR@igheightstyle;\LWR@indentHTML}{}%
    \ifthenelse{\NOT\equal{\LWR@igorigin}{}}%
        {%
            transform-origin: \LWR@originnames{\LWR@igorigin};\LWR@indentHTML%
        }{}%
    \ifthenelse{\NOT\equal{\LWR@igangle}{}}%
    {%
        \LWR@rotstyle{-ms-}{\LWR@igangle}\LWR@indentHTML
        \LWR@rotstyle{-webkit-}{\LWR@igangle}\LWR@indentHTML
        \LWR@rotstyle{}{\LWR@igangle }\LWR@indentHTML
    }{}%
```

```
    \ifthenelse{%
        \NOT\equal{\LWR@igxscale}{1}\OR%
        \NOT\equal{\LWR@igyscale}{1}%
    }%
    {%
        \LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
        \LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
        \LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
    }{}%
    %
    \ifthenelse{\NOT\equal{\LWR@opacity}{1}}%
        {opacity:\LWR@opacity;\LWR@indentHTML}{}%
    %
    "\LWR@indentHTML%
}{}%
```

Set the class and alt tag:

```
class="\LWR@igclass"\LWR@indentHTML%
alt="\AltTextOpen\LWR@igalt\AltTextClose" \LWR@orignewline%
}% end of image tags
}% end of href
```

Return to original page size and font size:

```
\endgroup
```

Clear the single-use `alt` text:

```
\gdef\LWR@ThisAltText{}%
\LWR@traceinfo{LWR@includegraphicsb done}%
}
```

`\includegraphics` `[`⟨*key=val*⟩`]` `{`⟨*filename*⟩`}`

Handles width and height, converted to fixed width and heights.

The user should always use no file suffix in the document source.

```
\AtBeginDocument{

\LWR@traceinfo{Patching includegraphics.}

\LetLtxMacro\LWR@origincludegraphics\includegraphics

\renewcommand*{\includegraphics}
{%
```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```
\LWR@traceinfo{includegraphics}%
\LWR@ensuredoingapar%
```

```
\LWR@includegraphicsb%
}% includegraphics
}% AtBeginDocument
```

§ 265.5 Boxes

\LWR@rotboxorigin Holds the origin key letters.

```
\newcommand*{\LWR@rotboxorigin}{}
```

\LWR@originname {⟨*letter*⟩}

Given one LaTeX origin key value, translate into an HTML origin word:

```
\newcommand*{\LWR@originname}[1]{%
    \ifthenelse{\equal{#1}{t}}{top}{}%
    \ifthenelse{\equal{#1}{b}}{bottom}{}%
    \ifthenelse{\equal{#1}{c}}{center}{}%
    \ifthenelse{\equal{#1}{l}}{left}{}%
    \ifthenelse{\equal{#1}{r}}{right}{}%
}
```

\LWR@originnames {⟨*letters*⟩}

Given one- or two-letter LaTeX origin key values, translate into HTML origin words:

```
\newcommand*{\LWR@originnames}[1]{%
\StrChar{#1}{1}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
\StrChar{#1}{2}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
}
```

Handle the `origin` key for `\rotatebox`:

```
\define@key{krotbox}{origin}{%
\renewcommand*{\LWR@rotboxorigin}{#1}%
}
```

These keys are ignored:

```
\define@key{krotbox}{x}{}
\define@key{krotbox}{y}{}
\define@key{krotbox}{units}{}
```

\rotatebox [⟨*keyval list*⟩] {⟨*angle*⟩} {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@rotatebox}{O{} m +m}{%
```

Reset the origin to “none-given”:

```
\renewcommand*{\LWR@rotboxorigin}{}
```

Process the optional keys, which may set `\LWR@rotateboxorigin`:

```
\setkeys{krotbox}{#1}%
```

Select `inline-block` so that HTML will transform this span:

```
\LWR@htmltagc{%
    span\LWR@indentHTML
    style="\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

If an origin was given, translate and print the origin information:

```
    \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{}}%
      {transform-origin: \LWR@originnames{\LWR@rotboxorigin};\LWR@indentHTML}%
        {}%
```

Print the rotation information:

```
    \LWR@rotstyle{-ms-}{#2}\LWR@indentHTML
    \LWR@rotstyle{-webkit-}{#2}\LWR@indentHTML
    \LWR@rotstyle{}{#2}"\LWR@orignewline%
}\LWR@orignewline%
```

Print the text to be rotated:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{rotatebox}

}% AtBeginDocument
```

`\scalebox` {⟨*h-scale*⟩} [⟨*v-scale*⟩] {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@scalebox}{m o m}{%
```

Select `inline-block` so that HTML will transform this span:

```
\LWR@htmltagc{%
    span\LWR@indentHTML
    style="\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

Print the scaling information:

```
    \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{}{#1}{\IfNoValueTF{#2}{#1}{#2}}
    "\LWR@orignewline
}\LWR@orignewline%
```

Print the text to be scaled:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{scalebox}

}% AtBeginDocument
```

`\reflectbox` {⟨*text*⟩}

```
\AtBeginDocument{

\newcommand{\LWR@HTML@reflectbox}[1]{%
\scalebox{-1}[1]{#1}%
}% \reflectbox

\LWR@formatted{reflectbox}

}% AtBeginDocument
```

`\resizebox` {⟨*h-length*⟩} {⟨*v-length*⟩} {⟨*text*⟩}

Simply prints its text argument.

```
\AtBeginDocument{

\NewDocumentCommand{\LWR@HTML@resizebox}{s m m m}{%
#4%
}
```

```
385
386 \LWR@formatted{resizebox}
387
388 }% AtBeginDocument
```

File 168 **lwarp-graphicx.sty**

§ 266 Package graphicx

Pkg graphicx graphicx is emulated.

graphicx loads graphics, which also loads lwarp-graphics, which remembers the original graphics definitions for use inside a lateximage, and then patches them \AtBeginDocument for HTML output.

lwarp-graphics handles the syntax of either graphics or graphicx.

for HTML output:

```
1 \LWR@ProvidesPackagePass{graphicx}[2017/06/01]
```

File 169 **lwarp-grffile.sty**

§ 267 Package grffile

Pkg grffile

⚠ matching PDF and SVG

grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

lwarp-grffile now exists as a placeholder since grffile used to be emulated by lwarp, and thus older versions of lwarp-grffile may exist and should be overwritten by this newer version.

for HTML output:

```
1 \LWR@ProvidesPackagePass{grffile}[2017/06/30]
```

File 170 **lwarp-grid.sty**

§ 268 Package grid

Pkg grid grid is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{grid}[2009/06/16]

2 \newenvironment*{gridenv}{}{}
```

File 171 **lwarp-grid-system.sty**

§ 269 Package grid-system

(*Emulates or patches code by* Marcus Bitzl.)

Pkg grid-system grid-system is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{grid-system}[2014/02/16]
```

(\ifdef is in case the older syntax is removed.)

```
\AtBeginEnvironment{Row}{\setlength{\linewidth}{6in}}

\ifdef{\endrow}{
    \AtBeginEnvironment{row}{\setlength{\linewidth}{6in}}
}{}

\renewcommand{\gridsystem@finishcell}{\hspace{\gridsystem@cellsep}}
```

File 172 **lwarp-gridset.sty**

§ 270 Package gridset

Pkg gridset gridset is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gridset}

\newcommand*{\gridbase}{}
\newcommand*{\gridinterval}{}
\newcommand*{\savepos}[1]{}
\newcounter{gridcnt}
\newcommand*{\vskipnextgrid}{}
\newcommand*{\thegridinfo}[1]{}
\newcommand*{\theposinfo}[1]{}
\newcommand*{\theypos}[1]{}
```

File 173 **lwarp-hang.sty**

§ 271 Package hang

(*Emulates or patches code by* Andreas Nolda.)

Pkg hang hang is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hang}[2017/02/18]
```

```
\newlength{\hangingindent}
\setlength{\hangingindent}{1em}
\newlength{\hangingleftmargin}
\setlength{\hangingleftmargin}{0em}

\newcommand*{\LWR@findhangingleftmargin}{%
\setlength{\LWR@templengthone}{\hangingleftmargin}%
\addtolength{\LWR@templengthone}{\hangingindent}%
}

\newenvironment{hangingpar}
{
    \LWR@findhangingleftmargin%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}

\newenvironment{hanginglist}
{%
    \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}%
    \renewcommand*{\LWR@printopenlist}{%
        \LWR@findhangingleftmargin%
        ul style="%
            \LWR@print@mbox{list-style-type:none;} % extra space
            \LWR@print@mbox{%
                margin-left:\LWR@printlength{\LWR@templengthone}%
            } ; % extra space
            \LWR@print@mbox{%
                text-indent:-\LWR@printlength{\hangingindent}%
            }%
        "%
    }%
    \let\item\LWR@itemizeitem%
    \list{}{}%
}
{\endlist}

\newenvironment{compacthang}
{\hanginglist}
{\endhanginglist}

\newlength{\labeledleftmargin}
\setlength{\labeledleftmargin}{0em}

\newenvironment{labeledpar}[2]
{%
    \BlockClass[%
        \LWR@findhangingleftmargin%
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]{labeledpar}#2%
```

```
}
{\endBlockClass}

\newenvironment{labeledlist}[1]
{\hanginglist}
{\endhanginglist}

\newenvironment{compactlabel}[1]
{\hanginglist}
{\endhanginglist}
```

File 174 **lwarp-hanging.sty**

§ 272 Package

hanging

Pkg hanging hanging is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hanging}[2009/09/02]

\@ifclassloaded{memoir}{
\let\hangpara\relax
\let\hangparas\relax
\let\endhangparas\relax
\let\hangpunct\relax
\let\endhangpunct\relax
}{}
```

\hangpara {⟨*indent*⟩} {⟨*afternum*⟩}

Use hangparas instead.

```
\newcommand*{\hangpara}[2]{}
```

Env hangparas {⟨*indent*⟩} {⟨*afternum*⟩}

```
\newenvironment*{hangparas}[2]
{%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{#1}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{#1}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}
```

Env hangpunct

```
\newenvironment*{hangpunct}
{\BlockClass{hangpunct}}
{\endBlockClass}

\newcommand{\nhpt}{.}
```

```
\newcommand{\nhlq}{‘}
\newcommand{\nhrq}{’}
```

File 175 **lwarp-hypbmsec.sty**

§ 273 Package hypbmsec

Pkg hypbmsec hypbmsec is emulated by the lwarp core.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypbmsec}[2016/05/16]
```

File 176 **lwarp-hypcap.sty**

§ 274 Package hypcap

Pkg hypcap hypcap is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypcap}[2016/05/16]

\newcommand*{\capstart}{}
\newcommand*{\hypcapspace}{}
\newcommand*{\hypcapredef}[1]{}
\newcommand*{\capstartfalse}{}
\newcommand*{\capstarttrue}{}
```

File 177 **lwarp-hypdestopt.sty**

§ 275 Package hypdestopt

Pkg hypdestopt hypdestopt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypdestopt}[2016/05/21]
```

File 178 **lwarp-hypernat.sty**

§ 276 Package hypernat

Pkg hypernat hypernat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypernat}[2001/07/09]
```

File 179 **lwarp-hyperref.sty**

§ 277 Package hyperref

(*Emulates or patches code by* Sebastian Rahtz, Heiko Oberdiek.)

Pkg hyperref hyperref is emulated.

for HTML output:

```
% \LWR@ProvidesPackageDrop{hyperref}% not allowed
% \ProvidesPackage{lwarp-#1-#2}% not allowed
\PackageInfo{lwarp}{%
Using the lwarp HTML version of package ‘hyperref’,\MessageBreak
and discarding options.\MessageBreak
(Not using \protect\ProvidesPackage, so that other packages\MessageBreak
do not attempt to patch lwarp’s version of ‘hyperref’.)\MessageBreak}

\DeclareOption*{}


% \ProcessOptions\relax
\let\ds@\@empty%         from the original \ProcessOptions
\edef\@curroptions{}%    lwarp modification to \ProcessOptions
\@process@ptions\relax%  from the original \ProcessOptions

\newcommand*{\hypersetup}[1]{}
\newcommand*{\hyperbaseurl}[1]{}
```

\hyperimage {⟨*URL*⟩} {⟨*alt text*⟩}

Insert an image with alt text:

```
\NewDocumentCommand{\LWR@hyperimageb}{m +m}{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\LWR@htmltag{img src="\LWR@templink" alt="#2" class="hyperimage"}%
\LWR@ensuredoingapar%
\endgroup%
}

\newrobustcmd*{\hyperimage}{%
\begingroup%
\catcode‘\#=12%
\catcode‘\%=12%
\catcode‘\&=12%
\catcode‘\~=12%
\catcode‘\_=12%
\LWR@hyperimageb%
}

```

`\hyperdef` {⟨*1: category*⟩} {⟨*2: name*⟩} {⟨*3: text*⟩}

Creates an HTML anchor to `category.name` with the given text.

```
\NewDocumentCommand{\LWR@hyperdefb}{m m +m}{%
\LWR@ensuredoingapar%
\LWR@sublabel{#1.#2}%
#3%
\endgroup%
}

\newcommand*{\hyperdef}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperdefb%
}

```

`\LWR@hyperrefb` {⟨*1: URL*⟩} {⟨*2: category*⟩} {⟨*3: name*⟩} {⟨*4: text*⟩}

Creates an HTML link to `URL#category.name` with the given text.

```
\newcommand{\LWR@hyperreffinish}[1]{%
\begingroup%
\RenewDocumentCommand{\ref}{}{\LWR@ref@ignorestar}%
#1%
\endgroup%
\LWR@htmltag{/a}%
}

\newcommand*{\LWR@hyperrefbb}[3]{%
\LWR@htmltag{%
    a href="%
        \detokenize\expandafter{#1}\LWR@hashmark%
        \detokenize\expandafter{#2}.\detokenize\expandafter{#3}%
    "%
    \LWR@addlinktitle%
}%
\endgroup%
\LWR@hyperreffinish%
}

\newrobustcmd*{\LWR@hyperrefb}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperrefbb%
}
```

\LWR@hyperrefc [⟨*label*⟩] {⟨*text*⟩}

Creates text as an HTML link to the LaTeX label.

```
\NewDocumentCommand{\LWR@hyperrefcb}{O{label}}{%
\LWR@startref{#1}%
\endgroup%
\LWR@hyperreffinish%
}

\newcommand*{\LWR@hyperrefc}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperrefcb%
}
```

\hyperref {⟨*1: URL*⟩} {⟨*2: category*⟩} {⟨*3: name*⟩} {⟨*4: text*⟩} —or— [⟨*1: label*⟩] {⟨*2: text*⟩}

```
\DeclareRobustCommand*{\hyperref}{%
\LWR@ensuredoingapar%
\@ifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
}
```

\hypertarget {⟨*name*⟩} {⟨*text*⟩}

Creates an anchor to name with the given text.

```
\NewDocumentCommand{\LWR@hypertargetb}{m +m}{%
\label{LWR-ht-#1}%
#2%
\endgroup%
}

\newcommand*{\hypertarget}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hypertargetb%
}
```

\hyperlink {⟨*name*⟩} {⟨*text*⟩}

Creates a link to the anchor created by hypertarget, with the given link text.

Declared because also defined by memoir.

```
\DeclareDocumentCommand{\LWR@hyperlinkb}{m}{%
\LWR@hyperrefcb[LWR-ht-#1]%
```

```
}

\DeclareDocumentCommand{\hyperlink}{}{%
\LWR@ensuredoingapar%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperlinkb%
}
```

\autoref * {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autoref}{s m}{%
    \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
}
```

\autopageref {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autopageref}{s m}{%
    \IfBooleanTF{#1}{\cpageref{#2}}{\cref{#2}}%
}
```

\pdfstringdef {⟨*macroname*⟩} {⟨*TEXstring*⟩}

```
\newcommand{\pdfstringdef}[2]{}
```

\pdfbookmark [⟨*level*⟩] {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\pdfbookmark}[3][]{}
```

\currentpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\currentpdfbookmark}[2]{}
```

\subpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\subpdfbookmark}[2]{}
```

\belowpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\belowpdfbookmark}[2]{}
```

\texorpdfstring {⟨*TEXstring*⟩} {⟨*PDFstring*⟩}

```
\newcommand{\texorpdfstring}[2]{#1}
```

`\hypercalcbp` {⟨*dimen*⟩} From hyperref.

```
\def\hypercalcbp#1{%
\strip@pt\dimexpr 0.99626401\dimexpr(#1)\relax\relax
}%
```

`\Acrobatmenu` {⟨*menuoption*⟩} {⟨*text*⟩}

```
\newcommand{\Acrobatmenu}[2]{}
```

`\TextField` [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\TextField}[2][]{}
```

`\CheckBox` [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\CheckBox}[2][]{}
```

`\ChoiceMenu` [⟨*parameters*⟩] {⟨*label*⟩} {⟨*choices*⟩}

```
\DeclareRobustCommand{\ChoiceMenu}[3][]{}
```

`\PushButton` [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\PushButton}[2][]{}
```

`\Submit` [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\Submit}[2][]{}
```

`\Reset` [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\Reset}[2][]{}
```

`\Gauge` [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\Gauge}[2][]{}
```

`\LayoutTextField` {⟨*label*⟩} {⟨*field*⟩}

```
\newcommand*{\LayoutTextField}[2]{}
```

`\LayoutChoiceField` {⟨*label*⟩} {⟨*field*⟩}

```
\newcommand*{\LayoutChoiceField}[2]{}
```

`\LayoutCheckField` {⟨*label*⟩} {⟨*field*⟩}

```
\newcommand*{\LayoutCheckField}[2]{}
```

`\MakeRadioField` {⟨*width*⟩} {⟨*height*⟩}

```
\newcommand*{\MakeRadioField}[2]{}
```

\MakeCheckField {⟨*width*⟩} {⟨*height*⟩}

```
\newcommand*{\MakeCheckField}[2]{}
```

\MakeTextField {⟨*width*⟩} {⟨*height*⟩}

```
\newcommand*{\MakeTextField}[2]{}
```

\MakeChoiceField {⟨*width*⟩} {⟨*height*⟩}

```
\newcommand*{\MakeChoiceField}[2]{}
```

\MakeFieldButton {⟨*text*⟩}

```
\newcommand{\MakeFieldButton}[1]{}
```

File 180 **lwarp-hyperxmp.sty**

§ 278 Package hyperxmp

Pkg hyperxmp hyperxmp is ignored.

for HTML output: Discard all options for lwarp-hyperxmp:

```
\LWR@ProvidesPackageDrop{hyperxmp}[2018/11/27]
```

File 181 **lwarp-hyphenat.sty**

§ 279 Package hyphenat

Pkg hyphenat hyphenat is emulated during HTML output, while the print-mode version is used inside a lateximage.

for HTML output:

```
\LWR@ProvidesPackagePass{hyphenat}[2009/09/02]

\LetLtxMacro\LWRHYNAT@origtextnhtt\textnhtt
\LetLtxMacro\LWRHYNAT@orignhttfamily\nhttfamily
\LetLtxMacro\LWRHYNAT@orignohyphens\nohyphens
\LetLtxMacro\LWRHYNAT@origbshyp\bshyp
\LetLtxMacro\LWRHYNAT@origfshyp\fshyp
\LetLtxMacro\LWRHYNAT@origdothyp\dothyp
\LetLtxMacro\LWRHYNAT@origcolonhyp\colonhyp
\LetLtxMacro\LWRHYNAT@orighyp\hyp

\LetLtxMacro\textnhtt\texttt
\LetLtxMacro\nhttfamily\ttfamily

```

```
\renewcommand{\nohyphens}[1]{#1}
\renewrobustcmd{\bshyp}{%
    \ifmmode\backslash\else\textbackslash\fi%
}
\renewrobustcmd{\fshyp}{/}
\renewrobustcmd{\dothyp}{.}
\renewrobustcmd{\colonhyp}{:}
\renewrobustcmd{\hyp}{-}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\textnhtt\LWRHYNAT@origtextnhtt%
\LetLtxMacro\nhttfamily\LWRHYNAT@orignhttfamily%
\LetLtxMacro\nohyphens\LWRHYNAT@orignohyphens%
\LetLtxMacro\bshyp\LWRHYNAT@origbshyp%
\LetLtxMacro\fshyp\LWRHYNAT@origfshyp%
\LetLtxMacro\dothyp\LWRHYNAT@origdothyp%
\LetLtxMacro\colonhyp\LWRHYNAT@origcolonhyp%
\LetLtxMacro\hyp\LWRHYNAT@orighyp%
}
```

File 182 **lwarp-idxlayout.sty**

§ 280 Package

idxlayout

(*Emulates or patches code by* Thomas Titz.)

Pkg idxlayout idxlayout is emulated.

for HTML output: Discard all options for lwarp-idxlayout:

```
\LWR@ProvidesPackageDrop{idxlayout}[2012/03/30]

\newcommand{\LWR@indexprenote}{}

\preto\printindex{

\LWR@orignewpage
\LWR@startpars

\LWR@indexprenote

}

\newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
\newcommand*{\noindexprenote}{\renewcommand{\LWR@indexprenote}{}}

\newcommand{\idxlayout}[1]{}
\newcommand*{\indexfont}{}
\newcommand*{\indexjustific}{}
\newcommand*{\indexsubsdelim}{}
\newcommand*{\indexstheadcase}{}
```

File 183 **lwarp-ifoddpage.sty**

§ 281 Package ifoddpage

(*Emulates or patches code by* Martin Scharrer.)

Pkg ifoddpage ifoddpage is emulated.

for HTML output: Discard all options for lwarp-ifoddpage:

```
\LWR@ProvidesPackageDrop{ifoddpage}[2016/04/23]

\newif\ifoddpage

\newif\ifoddpageoroneside

\DeclareRobustCommand{\checkoddpage}{\oddpagetrue\oddpageoronesidetrue}

\def\oddpage@page{1}

\def\@ifoddpage{%
        \expandafter\@firstoftwo
}

\def\@ifoddpageoroneside{%
        \expandafter\@firstoftwo
}
```

File 184 **lwarp-imakeidx.sty**

§ 282 Package imakeidx

(*Emulates or patches code by* Enrico Gregorio.)

Pkg imakeidx imakeidx is patched for use by lwarp.

letter headings When using *makeindex*, to match the print and HTML output's display of index letter headings, specify the `lwarp.ist` style:

```
\makeindex[options={-s lwarp.ist}]
```

(For HTML the `lwarp.ist` style is used automatically, which displays letter headings. When using *xindy* the default style also displays letter headings.)

index setup See section 8.6.18 for how to setup *lwarpmk* to process the indexes with imakeidx, both with and without shell escape.

for HTML output:

```
\LWR@ProvidesPackagePass{imakeidx}[2016/10/15]
```

Use the new HTML suffix:

```
\catcode`\_=12%
\define@key{imki}{name}{\def\imki@name{#1_html}}
\catcode`\_=8%
```

\printindex The HTML version of \printindex:

```
\catcode`\_=12%

\renewcommand*{\printindex}[1][\imki@jobname]{%
\LWR@orignewpage%
\LWR@startpars%
\ifstrequal{#1}{\imki@jobname}{%
  \@ifundefined{#1@idxfile}{%
        \imki@error{#1}%
    }{%
        \imki@putindex{#1}%
    }%
}{%
 \@ifundefined{#1_html@idxfile}{\imki@error{#1_html}}{\imki@putindex{#1_html}}%
}%
}

\catcode`\_=8%
```

\@index The HTML version of \index:

```
\catcode`\_=12%

\def\@index[#1]{%
    \ifstrequal{#1}{\imki@jobname}%
    {%
        \@ifundefined{#1@idxfile}%
        {%
            \PackageWarning{lwarp-imakeidx}{Undefined index file `#1'}%
            \begingroup
            \@sanitize
            \imki@nowrindex%
        }%
        {%
            \edef\@idxfile{#1}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
    {%
        \@ifundefined{#1_html@idxfile}%
        {%
            \PackageWarning{lwarp-imakeidx}{Undefined index file `#1_html'}%
            \begingroup
            \@sanitize
            \imki@nowrindex%
        }%
```

```
        {%
            \edef\@idxfile{#1_html}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
}

\catcode`\_=8%
```

\item
\subitem
\subsubitem HTML versions of \item, etc.:

```
\appto\theindex{%
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}
```

\imki@wrindexentrysplit {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}
\imki@wrindexentryunique {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}

While writing index entries, adds an HTML label, and writes the label's index instead of the page number:

```
\renewcommand\imki@wrindexentrysplit[3]{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
  \expandafter\protected@write\csname#1@idxfile\endcsname{}%
    {\string\indexentry{#2}{\arabic{LWR@autoindex}}}%
}

\renewcommand\imki@wrindexentryunique[3]{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
  \protected@write\@indexfile{}%
    {\string\indexentry[#1]{#2}{\arabic{LWR@autoindex}}}%
}

\def\imki@wrindexsplit#1#2{%
\imki@wrindexentrysplit{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
}

\def\imki@wrindexunique#1#2{%
\imki@wrindexentryunique{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
  }

```

\LWR@imki@setxdydefopts

Sets the xindy HTML options, ignoring the user's settings.

```
\newcommand*{\LWR@imki@setxdydefopts}{%
    \edef\imki@options{ \space %
        -M \space \LWR@xindyStyle\space %
        -L \space \LWR@xindyLanguage\space %
        -C \space \LWR@xindyCodepage\space %
    }%
}
```

\LWR@imki@setdefopts {⟨*user options*⟩}

Sets the HTML options, added to the user's settings, depending on whether makeindex or xindy are used.

For *makeindex*, the user's choice is ignored, and only the lwarp version is used. (Only one style at a time is possible.)

For *xindy*, multiple modules may be specified, and the lwarp version is appended.

```
\newcommand*{\LWR@imki@setdefopts}[1]{%
\ifblank{#1}{%
    \edef\imki@options{\space -s \space \LWR@makeindexStyle \space}%
    \ifdefstring{\imki@progdefault}{xindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{texindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{truexindy}{\LWR@imki@setxdydefopts}{}%
}{%
    \edef\imki@options{\space #1 \space}%
}%
}
```

\imki@makeindex Use the new HTML options:

```
\xpatchcmd{\imki@makeindex}
    {\let\imki@options\space}
    {\LWR@imki@setdefopts{}}%
    {}
    {\LWR@patcherror{imakeidx}{makeindex}}
```

Use the new HTML options.

```
\define@key{imki}{options}{\LWR@imki@setdefopts{#1}}
```

\imki@resetdefaults Use the new HTML options:

```
\xpatchcmd{\imki@resetdefaults}
    {\def\imki@options{ }}
    {\LWR@imki@setdefopts{}}
    {}
    {\LWR@patcherror{imakeidx}{resetdefaults}}
```

theindex was already defined \AtBeginDocument by the lwarp core, so it must be redefined here similarly, but patched for imakeidx:

Env theindex

```
\AtBeginDocument{
```

```
\renewenvironment*{theindex}{%
    \imki@maybeaddtotoc
     \imki@indexlevel{\indexname}
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

Update to the new defaults:

```
\imki@resetdefaults
```

Update to the new patches:

`\AtBeginDocument` is because `\@wrindex` is previously defined as `\AtBeginDocument` in the lwarp core.

```
\ifimki@splitindex
  \let\imki@startidx\imki@startidxunique
  \AtBeginDocument{\let\@wrindex\imki@wrindexunique}
  \let\imki@putindex\imki@putindexunique
  \let\imki@wrindexentry\imki@wrindexentryunique
  \let\imki@startidxsplit\@undefined
  \let\imki@wrindexsplit\@undefined
  \let\imki@putindexsplit\@undefined
\else
  \let\imki@startidx\imki@startidxsplit
  \AtBeginDocument{\let\@wrindex\imki@wrindexsplit}
  \let\imki@putindex\imki@putindexsplit
  \let\imki@wrindexentry\imki@wrindexentrysplit
  \let\imki@startidxunique\@undefined
  \let\imki@wrindexunique\@undefined
  \let\imki@putindexunique\@undefined
\fi
```

File 185 **lwarp-index.sty**

§ 283 Package

index

(*Emulates or patches code by* David M. Jones.)

Pkg index index is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{index}[2004/01/20]
```

Use `\theLWR@autoindex` instead of `\thepage`. `\@tempswatrue` is used to force an immediate write to the index file instead of waiting until the end of the page.

```
\xpatchcmd{\newindex}
    {\x@newindex[thepage]}
    {%
```

```
        \@tempswatrue%
        \x@newindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{newindex}}

\xpatchcmd{\renewindex}
    {\x@renewindex[thepage]}
    {%
        \@tempswatrue%
        \x@renewindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{renewindex}}
```

Patched to set a new autoindex:

```
\xpatchcmd{\@wrindex}
    {\begingroup}
    {%
        \addtocounter{LWR@autoindex}{1}%                    lwarp
        \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
        \begingroup%
    }
    {}
    {\LWR@patcherror{index}{@wrindex}}
```

`\AtBeginDocument` lwarp core `\lets` `\@wrindex` to `\LWR@wrindex`. Since the index package has been loaded, `\let` to its version instead:

```
\let\LWR@index@wrindex\@wrindex

\AtBeginDocument{
\let\@wrindex\LWR@index@wrindex
}
```

Modified to add `\index@prologue`:

```
\AtBeginDocument{
\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \ifx\index@prologue\@empty\else
        \index@prologue
        \bigskip
    \fi
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

Disabled:

```
\def\@showidx#1{}
\let\@texttop\relax
```

```
\renewcommand*{\raggedbottom}{}
\renewcommand*{\flushbottom}{}
\renewcommand*{\markboth}[2]{}
\renewcommand*{\markright}[1]{}
```

File 186 **lwarp-inputtrc.sty**

§ 284 Package inputtrc

(*Emulates or patches code by* Uwe Lück.)

Pkg inputtrc inputtrc is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{inputtrc}[2012/10/10]
```

Patched to remove extraneous spaces, which sometimes showed up in logos inside a `lateximage`.

```
\renewcommand*{\IT@prim@input}[1]{%
  \typeout{\IT@indent\IT@currfile INPUTTING #1}%
%% ... TODO: option to write to ‘.log’ only.
  \xdef\IT@filestack{{\IT@currfile}\IT@filestack}%
  \xdef\IT@currfile{#1}%
  \expandafter \gdef\expandafter \IT@indent\expandafter{%
    \IT@indent \IT@indent@unit}%               lwarp
  \@@input#1%                                  lwarp
  \expandafter\IT@pop@indent\IT@indent   \@nil% lwarp
  \expandafter\IT@pop@file  \IT@filestack\@nil% lwarp
  \IT@maybe@returnmessage%% v0.2               lwarp
}
```

File 187 **lwarp-intopdf.sty**

§ 285 Package intopdf

Pkg intopdf intopdf is emulated.

The filespec, MIME type, and description are ignored for now.

for HTML output:

```
\LWR@ProvidesPackageDrop{intopdf}[2019/05/28]
```

```
\NewDocumentCommand{\attachandlink}{o m o m m}{%
    \href{#2}{#5}%
}
```

File 188 **lwarp-karnaugh-map.sty**

§ 286 Package karnaugh-map

(*Emulates or patches code by* Mattias Jacobsson.)

Pkg karnaugh-map karnaugh-map is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{karnaugh-map}[2017/02/20]
```

(It is hard to patch this macro, so the entire thing is redefined here, with the lwarp modificaitions identified in comments.)

```
\RenewDocumentEnvironment{karnaugh-map}{s O{4} O{4} O{1} O{$X_1X_0$} O{$X_3X_2$} O{$X_5X_4$}} {%
  \begingroup
    % store map size {[START]
      \renewcommand{\@karnaughmap@var@mapsizex@}{#2}%
      \renewcommand{\@karnaughmap@var@mapsizey@}{#3}%
      \renewcommand{\@karnaughmap@var@mapsizez@}{#4}%
    % [END]}
    % determinate if markings should be color or black and white
    \IfBooleanTF{#1}{%
      % should be black and white
      \renewcommand{\@karnaughmap@var@bw@}{1}%
    }{%
      % should be color
      \renewcommand{\@karnaughmap@var@bw@}{0}%
    }%
    %
    % find matching matrix template and alignment parameters {[START]
    \newcommand{\@karnaughmap@local@matrixtemplate@}{0}% '0' is considered as missing matrix template
      \newcommand{\@karnaughmap@local@maprealignmentx@}{0}%
      \newcommand{\@karnaughmap@local@maprealignmenty@}{0}%
    \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=221
        \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
                  \&                  0 \&                  1 \& \phantom{0} \\
             0 \& |(000000)|  \phantom{0} \& |(000001)|  \phantom{0} \&         \\
             1 \& |(000010)|  \phantom{0} \& |(000011)|  \phantom{0} \&         \\
        \phantom{0}  \&                    \&                    \&           \\
        }%
      \fi
    \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=241
        \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
                  \&                  0 \&                  1 \& \phantom{00} \\
            00 \& |(000000)|  \phantom{0} \& |(000001)|  \phantom{0} \&         \\
            01 \& |(000010)|  \phantom{0} \& |(000011)|  \phantom{0} \&         \\
            11 \& |(000110)|  \phantom{0} \& |(000111)|  \phantom{0} \&         \\
            10 \& |(000100)|  \phantom{0} \& |(000101)|  \phantom{0} \&         \\
        \phantom{00} \&                    \&                    \&           \\
        }%
      \fi
```

```
    \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=421
        \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
                \&              00 \&              01 \&              11 \&              10 \& \phanto
             0  \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
             1  \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
       \phantom{00} \&                \&                \&                \&                \&
        }%
      \fi
    \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=441
        \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
                \&              00 \&              01 \&              11 \&              10 \& \phanto
             00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
             01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
             11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(00111
             10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(00101
       \phantom{00} \&                \&                \&                \&                \&
        }%
      \fi
    \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=442
        \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
                \&              00 \&              01 \&              11 \&              10 \& \phanto
             00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
             01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
             11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(00111
             10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(00101
       \phantom{00} \&                \&                \&                \&                \&
        }%
        \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
      \fi
    \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=444
        \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
                \&              00 \&              01 \&              11 \&              10 \& \phanto
             00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
             01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
             11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(00111
             10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(00101
       \phantom{00} \&                \&                \&                \&                \&
             00 \& |(100000)| \phantom{0} \& |(100001)| \phantom{0} \& |(100011)| \phantom{0} \& |(10001
             01 \& |(100100)| \phantom{0} \& |(100101)| \phantom{0} \& |(100111)| \phantom{0} \& |(10011
             11 \& |(101100)| \phantom{0} \& |(101101)| \phantom{0} \& |(101111)| \phantom{0} \& |(10111
             10 \& |(101000)| \phantom{0} \& |(101001)| \phantom{0} \& |(101011)| \phantom{0} \& |(10101
       \phantom{00} \&                \&                \&                \&                \&
        }%
        \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
        \renewcommand{\@karnaughmap@local@maprealignmenty@}{-2.5}%
      \fi
    % [END]}
   % test if a matrix template is found or not(aka "\@karnaughmap@local@matrixtemplate@" equals to '0')
    \ifdefstring{\@karnaughmap@local@matrixtemplate@}{0}{%  lwarp
%     \ifnum0=\@karnaughmap@local@matrixtemplate@%  original
      % print error if no template could be found
      \PackageError{lwarp-karnaugh-map}{%
     Can not find a template fitting your specification (\@karnaughmap@var@mapsizex@\space x \@karnaughma
      }{%
     Existing templates have the following dimensions: 2x2x1, 2x4x1, 4x2x1, 4x4x1, 4x4x2, and 4x4x4.
```

```
      }%
%     \fi   original
    }{}%    lwarp
    \begin{tikzpicture}
      % grid
      % for all dimensions
    \draw[color=black, ultra thin] (0,0) grid (\@karnaughmap@var@mapsizex@,\@karnaughmap@var@mapsizey@);
      % when there are 2 sub maps
      \ifnum\@karnaughmap@var@mapsizez@=2
        \draw[color=black, ultra thin] (5,0) grid (9,4);
      \fi
      % when there are 4 sub maps
      \ifnum\@karnaughmap@var@mapsizez@=4
        \draw[color=black, ultra thin] (5,0) grid (9,4);
        \draw[color=black, ultra thin] (0,-5) grid (4,-1);
        \draw[color=black, ultra thin] (5,-5) grid (9,-1);
      \fi
      % labels
      % for all dimensions
    \node[above] at (\@karnaughmap@var@mapsizex@*0.5,\@karnaughmap@var@mapsizey@+0.9) {\small{#5}};
      \node[left] at (-0.9,\@karnaughmap@var@mapsizey@*0.5) {\small{#6}};
      % when there are 2 sub maps
      \ifnum\@karnaughmap@var@mapsizez@=2
        \node[above] at (7,4.9) {\small{#5}};
        % extra sub maps labels
        \node[below] at (2,-0.1) {\small{#7$=0$}};
        \node[below] at (7,-0.1) {\small{#7$=1$}};
      \fi
      % when there are 4 sub maps
      \ifnum\@karnaughmap@var@mapsizez@=4
        \node[above] at (7,4.9) {\small{#5}};
        \node[left] at (-0.9,-3) {\small{#6}};
        % extra sub maps labels
        \node[below] at (2,-0.1) {\small{#7$=00$}};
        \node[below] at (7,-0.1) {\small{#7$=01$}};
        \node[below] at (2,-5.1) {\small{#7$=10$}};
        \node[below] at (7,-5.1) {\small{#7$=11$}};
      \fi
      % data
      \matrix[
        matrix of nodes,
        ampersand replacement=\&,
        column sep={1cm,between origins},
        row sep={1cm,between origins},
    ] at (\@karnaughmap@var@mapsizex@*0.5+\@karnaughmap@local@maprealignmentx@,\@karnaughmap@var@mapsiz
        \@karnaughmap@local@matrixtemplate@%
      };
}{
    \end{tikzpicture}
  \endgroup
}
```

File 189 **lwarp-keyfloat.sty**

§ 287 Package

keyfloat

(*Emulates or patches code by* Brian Dunn.)

Pkg keyfloat keyfloat is supported with a considerable amount of hacking. (It's a mashup of lwarp, keyfloat, and tocdata.)

⚠ keywrap If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the `lw` option.)

for HTML output:

```
\LWR@ProvidesPackagePass{keyfloat}[2019/09/23]

\@ifpackagelater{keyfloat}{2019/09/23}{}{
    \PackageError{lwarp-keyfloat}
    {%
        The keyfloat package is out of date.\MessageBreak
        Update to keyfloat v2.01 2019/09/23 or later%
    }
    {%
        Please update the keyfloat package.  It's worth it!%
    }
}
```

After keyfloat has loaded:

```
\AtBeginDocument{


\providecommand*{\KFLT@LWR@hook@boxouter}{}
\renewcommand*{\KFLT@LWR@hook@boxouter}{%
    \ifbool{KFLT@keywrap}{%
    }{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
            \setlength{\textheight}{9in}%
        }{}%
    }%
    \normalcolor%
}


\providecommand*{\KFLT@LWR@hook@keysubfloats}{}
\renewcommand*{\KFLT@LWR@hook@keysubfloats}{%
    \ifbool{KFLT@keywrap}{%
    }{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
```

```
            \setlength{\textheight}{9in}%
        }{}%
    }%
    \normalcolor%
}

\let\KFLT@LWR@hook@keyfloatsminipage\relax
\let\endKFLT@LWR@hook@keyfloatsminipage\relax
\newenvironment*{KFLT@LWR@hook@keyfloatsminipage}[1]{}{}


\providecommand*{\KFLT@LWR@hook@keyfloats}{}
\renewcommand*{\KFLT@LWR@hook@keyfloats}{%
    \ifbool{KFLT@keywrap}{%
    }{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
            \setlength{\textheight}{9in}%
        }{}%
    }%
    \normalcolor%
}

\renewcommand*{\KFLT@maybeendfloatrow}{%
    \ifnumless{\value{KFLT@thiscol}}{\value{KFLT@numcols}}%
    {}% thiscol < numcols
    {% >=
        \defcounter{KFLT@thiscol}{0}%
    }%
}%

\renewcommand{\KFLT@trackrows}%
{%
```

If are nested inside a keyfloats or a subfloat:

```
    \ifboolexpr{%
        test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or%
        bool{KFLT@inkeysubfloats}%
    }%
    {% nested
```

Tracks row start and end:

```
        \KFLT@maybestartfloatrow%
```

Possibly fill space between columns:

```
        \ifnumgreater{\value{KFLT@thiscol}}{1}%
            {%
% \hfill%
            }%
            {}%
    }% nested
```

```
    {}% not nested
}

\RenewDocumentCommand{\KFLT@onefigureimage}{m}
{%
\LWR@traceinfo{KFLT@onefigureimage}%
% \begin{lrbox}{\KFLT@envbox}%
\ifthenelse{\NOT\equal{\KFLT@lw}{}}%
    {%
        \KFLT@frame{\includegraphics%
        [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
    }%
    {% not linewidth
        \ifthenelse{\dimtest{\KFLT@w}{>}{0pt}}%
        {% width is given
            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
            {% w and h
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,%
                width=\KFLT@imagewidth,height=\KFLT@h]{#1}}%
            }% w and h
            {% only w
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
            }% only w
        }% width is given
        {% width is not given
            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
            {%
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,height=\KFLT@h]{#1}}%
            }%
            {%
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s]{#1}}%
            }%
        }% width is not given
    }% not linewidth
% \end{lrbox}%
% \unskip%
% \KFLT@findenvboxwidth%
% \begin{turn}{\KFLT@r}%
% \KFLT@frame{\usebox{\KFLT@envbox}}%
% \unskip%
% \end{turn}%
\LWR@traceinfo{KFLT@onefigureimage: done}%
}

\RenewDocumentEnvironment{KFLT@boxinner}{}
{%
    \LWR@traceinfo{KFLT@boxinner}%
    \LWR@stoppars%
    \minipagefullwidth%
    \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{%
        \fminipage{\KFLT@imagewidth}%
```

```
    }{%
        \minipage{\KFLT@imagewidth}%
    }%
}
{%
    \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{%
        \endfminipage%
    }{%
        \endminipage%
    }%
    \LWR@startpars%
    \LWR@traceinfo{KFLT@boxinner: done}%
}

\newcommand*{\LWR@KFLT@settextalign}[1]{%
    \def\LWR@KFLT@textalign{justify}%
    \ifcsstring{KFLT@#1textalign}{\centering}%
        {\def\LWR@KFLT@textalign{center}}%
        {}%
    \ifcsstring{KFLT@#1textalign}{\raggedleft}%
        {\def\LWR@KFLT@textalign{right}}%
        {}%
    \ifcsstring{KFLT@#1textalign}{\raggedright}%
        {\def\LWR@KFLT@textalign{left}}%
        {}%
}

\renewcommand{\KFLT@addtext}[1]
{%
```

Is there text to add?

```
    \ifcsempty{KFLT@#1t}%
    {}% no text
    {% text to add
        {% local
```

Add some space, then create a to contain the text:

```
        \addvspace{\smallskipamount}%
        \LWR@KFLT@settextalign{#1}%
        \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%
```

Set the alignment and some text parameters:

```
%         \csuse{KFLT@#1textalign}%
%         \footnotesize%
        \setlength{\parskip}{1.5ex}%
        \setlength{\parindent}{0em}%
```

Typeset the actual text:

```
        \csuse{KFLT@#1t}%
```

Close it all out with a little more space:

```
        \end{BlockClass}%
%         \par\addvspace{2ex}%
        }% local
    }% text to add
}

\@ifpackageloaded{tocdata}
{}
{% tocdata not loaded

    \newcommand*{\LWR@KFLT@setnamealign}[1]{%
        \def\LWR@KFLT@textalign{justify}%
        \ifstrequal{#1}{\centering}%
            {\def\LWR@KFLT@textalign{center}}%
            {}%
        \ifstrequal{#1}{\raggedleft}%
            {\def\LWR@KFLT@textalign{right}}%
            {}%
        \ifstrequal{#1}{\raggedright}%
            {\def\LWR@KFLT@textalign{left}}%
            {}%
    }

    \renewcommand*{\KFLT@@addartisttext}[3]{%

```

Add space and create the name inside a :

```
%         \addvspace{\medskipamount}%
    %     \begin{minipage}{\linewidth}%
        \LWR@KFLT@setnamealign{#3}%
        \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%

```

Text alignment is #3, and depends on artist or author:

```
    %     #3%

```

#1 is empty or 'subgrp'
#2 is empty for artist, 'u' for author:

```
        \footnotesize\textsc{%
            \KFLT@optionalname{\csuse{KFLT@#1a#2p}}%
            \KFLT@optionalname{\csuse{KFLT@#1a#2f}}%
            \csuse{KFLT@#1a#2l}%
            \csuse{KFLT@#1a#2s}%
        }%
    %     \end{minipage}%
        \end{BlockClass}
%         \par\addvspace{2ex}%
    }

```

```
}% tocdata not loaded
```

Env KFLT@marginfloat [⟨*offset*⟩] {⟨*type*⟩}

```
\DeclareDocumentEnvironment{KFLT@marginfloat}{O{-1.2ex} m}
{%
    \uselengthunit{PT}%
    \LWR@BlockClassWP%
        {float:right; width:2in; margin:10pt}%
        {}%
        {marginblock}%
    \captionsetup{type=#2}%
    \minipage{\LWR@usersmarginparwidth}%
    \setlength{\marginparwidth}{.95\LWR@usersmarginparwidth}%
}
{%
    \endminipage%
    \endLWR@BlockClassWP%
}

\DeclareDocumentEnvironment{marginfigure}{o}
    {\begin{KFLT@marginfloat}{figure}}
    {\end{KFLT@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
    {\begin{KFLT@marginfloat}{table}}
    {\end{KFLT@marginfloat}}
```

Env keywrap {⟨*width*⟩} {⟨*keyfloat*⟩}

```
\DeclareDocumentEnvironment{keywrap}{m +m}
{%
    \LWR@ensuredoingapar%
    \setlength{\linewidth}{6in}% in case #1 has \linewidth
    \setlength{\LWR@templengthone}{#1}%
    \begin{LWR@BlockClassWP}%
        {%
         float:right; width:\LWR@printlength{\LWR@templengthone};  % extra space
            margin:10pt%
        }%
        {}%
        {marginblock}%
    \setlength{\linewidth}{.95\LWR@templengthone}%
    \booltrue{KFLT@keywrap}%
    #2%
    \end{LWR@BlockClassWP}%
}
{}

}% AtBeginDocument
```

File 190 **lwarp-layaureo.sty**

§ 288 Package layaureo

Pkg layaureo layaureo is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{layaureo}[2004/09/16]
```

File 191 **lwarp-layout.sty**

§ 289 Package layout

Pkg layout layout is ignored.

for HTML output: Discard all options for lwarp-layout:

```
\LWR@ProvidesPackageDrop{layout}[2014/10/28]
\NewDocumentCommand{\layout}{s}{}
```

File 192 **lwarp-layouts.sty**

§ 290 Package layouts

Pkg layouts layouts is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{layouts}[2009/09/02]
\newif\ifoddpagelayout
  \oddpagelayouttrue
\newif\iftwocolumnlayout
  \twocolumnlayoutfalse
\newif\ifdrawmarginpars
  \drawmarginparstrue
\newif\ifdrawparameters
  \drawparameterstrue
\newif\iflistaspara
  \listasparatrue
\newif\ifruninhead
  \runinheadfalse
\newif\ifprintparameters
  \printparameterstrue
\newif\ifdrawdimensions
  \drawdimensionsfalse
\newif\ifprintheadings
```

```
  \printheadingstrue
\newcommand{\testdrawdimensions}{}
\newcommand{\testprintparameters}{}
\newcommand{\setlabelfont}[1]{}
\newcommand{\setparametertextfont}[1]{}
\newcommand{\setvaluestextsize}[1]{}
\newcommand{\setlayoutscale}[1]{}
\newcommand{\setuplayouts}{}
\newcommand{\printinunitsof}[1]{}
\newcommand{\prntlen}[1]{}
\newcommand{\trypaperwidth}[1]{}
\newcommand{\trypaperheight}[1]{}
\newcommand{\tryhoffset}[1]{}
\newcommand{\tryvoffset}[1]{}
\newcommand{\trytopmargin}[1]{}
\newcommand{\tryheadheight}[1]{}
\newcommand{\tryheadsep}[1]{}
\newcommand{\trytextheight}[1]{}
\newcommand{\tryfootskip}[1]{}
\newcommand{\tryoddsidemargin}[1]{}
\newcommand{\tryevensidemargin}[1]{}
\newcommand{\trytextwidth}[1]{}
\newcommand{\trymarginparsep}[1]{}
\newcommand{\trymarginparwidth}[1]{}
\newcommand{\trymarginparpush}[1]{}
\newcommand{\trycolumnsep}[1]{}
\newcommand{\trycolumnseprule}[1]{}
\newcommand{\setfootbox}[2]{}
\newcommand{\currentpage}{}
\newcommand{\drawpage}{(draw page)}
\newcommand{\pagediagram}{(page diagram)}
\newcommand{\pagedesign}{(page design)}
\newcommand{\pagevalues}{(page values)}
\newcommand{\trystockwidth}[1]{}
\newcommand{\trystockheight}[1]{}
\newcommand{\trytrimedge}[1]{}
\newcommand{\trytrimtop}[1]{}
\newcommand{\tryuppermargin}[1]{}
\newcommand{\tryspinemargin}[1]{}
\newcommand{\currentstock}{}
\newcommand{\drawstock}{(draw stock)}
\newcommand{\stockdiagram}{(stock diagram)}
\newcommand{\stockdesign}{(stock design)}
\newcommand{\stockvalues}{(stock values)}
\newcommand{\tryitemindent}[1]{}
\newcommand{\trylabelwidth}[1]{}
\newcommand{\trylabelsep}[1]{}
\newcommand{\tryleftmargin}[1]{}
\newcommand{\tryrightmargin}[1]{}
\newcommand{\trylistparindent}[1]{}
\newcommand{\trytopsep}[1]{}
\newcommand{\tryparskip}[1]{}
\newcommand{\trypartopsep}[1]{}
\newcommand{\tryparsep}[1]{}
\newcommand{\tryitemsep}[1]{}
```

```
\newcommand{\currentlist}{}
\newcommand{\drawlist}{(draw list)}
\newcommand{\listdiagram}{(list diagram)}
\newcommand{\listdesign}{(list design)}
\newcommand{\listvalues}{(list values)}
\newcommand{\tryfootins}[1]{}
\newcommand{\tryfootnotesep}[1]{}
\newcommand{\tryfootnotebaseline}[1]{}
\newcommand{\tryfootruleheight}[1]{}
\newcommand{\tryfootrulefrac}[1]{}
\newcommand{\currentfootnote}{}
\newcommand{\drawfootnote}{(draw footnote)}
\newcommand{\footnotediagram}{(footnote diagram)}
\newcommand{\footnotedesign}{(footnote design)}
\newcommand{\footnotevalues}{(footnote values)}
\newcommand{\tryparindent}[1]{}
\newcommand{\tryparlinewidth}[1]{}
\newcommand{\tryparbaselineskip}[1]{}
\newcommand{\currentparagraph}{}
\newcommand{\drawparagraph}{(draw paragraph)}
\newcommand{\paragraphdiagram}{(paragraph diagram)}
\newcommand{\paragraphdesign}{(paragraph design)}
\newcommand{\paragraphvalues}{(paragraph values)}
\newcommand{\trybeforeskip}[1]{}
\newcommand{\tryafterskip}[1]{}
\newcommand{\tryindent}[1]{}
\newcommand{\currentheading}{}
\newcommand{\drawheading}[1]{(draw heading)}
\newcommand{\headingdiagram}[1]{(heading diagram)}
\newcommand{\headingdesign}[1]{(heading design)}
\newcommand{\headingvalues}{(heading values)}
\newcommand{\trytextfloatsep}[1]{}
\newcommand{\tryfloatsep}[1]{}
\newcommand{\tryintextsep}[1]{}
\newcommand{\trytopfigrule}[1]{}
\newcommand{\trybotfigrule}[1]{}
\newcommand{\currentfloat}{}
\newcommand{\drawfloat}{(draw float)}
\newcommand{\floatdiagram}{(float diagram)}
\newcommand{\floatdesign}{(float design)}
\newcommand{\floatvalues}{(float values)}
\newcommand{\trytotalnumber}[1]{}
\newcommand{\trytopnumber}[1]{}
\newcommand{\trybottomnumber}[1]{}
\newcommand{\trytopfraction}[1]{}
\newcommand{\trytextfraction}[1]{}
\newcommand{\trybottomfraction}[1]{}
\newcommand{\currentfloatpage}{}
\newcommand{\drawfloatpage}{(draw floatpage)}
\newcommand{\floatpagediagram}{(floatpage diagram)}
\newcommand{\floatpagedesign}{(floatpage design)}
\newcommand{\floatpagevalues}{(floatpage values)}
\newcommand{\trytocindent}[1]{}
\newcommand{\trytocnumwidth}[1]{}
\newcommand{\trytoclinewidth}[1]{}
```

```
\newcommand{\trytocrmarg}[1]{}
\newcommand{\trytocpnumwidth}[1]{}
\newcommand{\trytocdotsep}[1]{}
\newcommand{\currenttoc}{}
\newcommand{\drawtoc}{(draw toc)}
\newcommand{\tocdiagram}{(toc diagram)}
\newcommand{\tocdesign}{(toc design)}
\newcommand{\tocvalues}{(toc values)}
\newcommand{\drawaspread}[8][0]{(a spread)}
\newcommand{\drawfontframe}[1]{(font frame)}
\newcommand{\drawfontframelabel}[1]{}
```

File 193 **lwarp-leading.sty**

§ 291 Package leading

Pkg leading leading is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{leading}[2008/12/11]
\newcommand\leading[1]{}
```

File 194 **lwarp-letterspace.sty**

§ 292 Package letterspace

(*Emulates or patches code by* R Schlicht.)

Pkg letterspace letterspace is a subset of microtype, which is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output: Discard all options for lwarp-letterspace:

```
\LWR@ProvidesPackageDrop{letterspace}[2018/01/14]
\newcommand*\lsstyle{}
\newcommand\textls[2][]{}
\def\textls#1#{}
\newcommand*\lslig[1]{#1}
```

File 195 **lwarp-lettrine.sty**

§ 293 Package lettrine

(*Emulates or patches code by* Daniel Flipo.)

Pkg lettrine lettrine is emulated.

for HTML output: Discard all options for lwarp-lettrine:

```
\LWR@ProvidesPackageDrop{lettrine}[2018-08-28]
```

The initial letter is in a of class `lettrine`, and the following text is in a of class `lettrinetext`. `\lettrine` [⟨*keys*⟩] {⟨*letter*⟩} {⟨*additional text*⟩}

```
\DeclareDocumentCommand{\lettrine}{o m m}{%
\InlineClass{lettrine}{#2}\InlineClass{lettrinetext}{#3} % extra space
}

\newcounter{DefaultLines}
\setcounter{DefaultLines}{2}
\newcounter{DefaultDepth}
\newcommand*{\DefaultOptionsFile}{\relax}
\newcommand*{\DefaultLoversize}{0}
\newcommand*{\DefaultLraise}{0}
\newcommand*{\DefaultLhang}{0}
\newdimen\DefaultFindent
\setlength{\DefaultFindent}{\z@}
\newdimen\DefaultNindent
\setlength{\DefaultNindent}{0.5em}
\newdimen\DefaultSlope
\setlength{\DefaultSlope}{\z@}
\newdimen\DiscardVskip
\setlength{\DiscardVskip}{0.2\p@}
\newif\ifLettrineImage
\newif\ifLettrineOnGrid
\newif\ifLettrineRealHeight

\newcommand*{\LettrineTextFont}{\scshape}
\newcommand*{\LettrineFontHook}{}
\newcommand*{\LettrineFont}[1]{\InlineClass{lettrine}{#1}}
\newcommand*{\LettrineFontEPS}[1]{\includegraphics[height=1.5ex]{#1}}
```

File 196 **lwarp-lineno.sty**

§ 294 Package lineno

(*Emulates or patches code by* Stephan I. Böttcher.)

Pkg lineno lineno is partly emulated, but mostly ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lineno}[2005/11/02]

\newcommand*\resetlinenumber[1][\@ne]{}

\def\linenumbers{%
     \@ifnextchar[{\resetlinenumber}%]
                  {\@ifstar{\resetlinenumber}{}}%
     }

\newcommand*{\nolinenumbers}{}
```

```
10
11 \@namedef{linenumbers*}{\par\linenumbers*}
12 \@namedef{runninglinenumbers*}{\par\runninglinenumbers*}
13
14 \def\endlinenumbers{\par}
15 \let\endrunninglinenumbers\endlinenumbers
16 \let\endpagewiselinenumbers\endlinenumbers
17 \expandafter\let\csname endlinenumbers*\endcsname\endlinenumbers
18 \expandafter\let\csname endrunninglinenumbers*\endcsname\endlinenumbers
19 \let\endnolinenumbers\endlinenumbers
20
21 \def\pagewiselinenumbers{\linenumbers\setpagewiselinenumbers}
22
23 \def\runninglinenumbers{\setrunninglinenumbers\linenumbers}
24
25 \def\setpagewiselinenumbers{}
26
27 \def\setrunninglinenumbers{}
28
29 \def\linenomath{}%
30 \@namedef{linenomath*}{}%
31 \def\endlinenomath{}
32 \expandafter\let\csname endlinenomath*\endcsname\endlinenomath
33
34 \let\linelabel\label
35
36 \def\switchlinenumbers{\@ifstar{}{}}
37 \def\setmakelinenumbers#1{\@ifstar{}{}}
38
39 \def\leftlinenumbers{\@ifstar{}{}}
40 \def\rightlinenumbers{\@ifstar{}{}}
41
42 \newcounter{linenumber}
43 \newcount\c@pagewiselinenumber
44 \let\c@runninglinenumber\c@linenumber
45
46 \def\runningpagewiselinenumbers{}
47 \def\realpagewiselinenumbers{}
48
49
50 \NewDocumentCommand\modulolinenumbers{s o}{}
51
52 \chardef\c@linenumbermodulo=5
53 \modulolinenumbers[1]
54
55 \newcommand*\firstlinenumber[1]{}
56
57 \newcommand\internallinenumbers{}
58 \let\endinternallinenumbers\endlinenumbers
59 \@namedef{internallinenumbers*}{\internallinenumbers*}
60 \expandafter\let\csname endinternallinenumbers*\endcsname\endlinenumbers
61
62 \newcommand*{\linenoplaceholder}[1]{% redefine per language
63     (line number reference for \detokenize\expandafter{#1})
64 }
```

```
65
66 \newcommand*{\lineref}[2][]{\linenoplaceholder{#2}}
67 \newcommand*{\linerefp}[2][]{\linenoplaceholder{#2}}
68 \newcommand*{\linerefr}[2][]{\linenoplaceholder{#2}}
69
70 \newcommand\quotelinenumbers
71    {\@ifstar\linenumbers{\@ifnextchar[\linenumbers{\linenumbers*}}}
72
73 \newdimen\linenumbersep
74 \newdimen\linenumberwidth
75 \newdimen\quotelinenumbersep
76
77 \quotelinenumbersep=\linenumbersep
78 \let\quotelinenumberfont\linenumberfont
79
80 \def\linenumberfont{\normalfont\tiny\sffamily}
81
82
83 \linenumberwidth=10pt
84 \linenumbersep=10pt
85
86 \def\thelinenumber{}
87
88 \def\LineNumber{}
89 \def\makeLineNumber{}
90 \def\makeLineNumberLeft{}
91 \def\makeLineNumberRight{}
92 \def\makeLineNumberOdd{}
93 \def\makeLineNumberEven{}
94 \def\makeLineNumberRunning{}
95
96
97 \newenvironment{numquote}     {\quote}{\endquote}
98 \newenvironment{numquotation} {\quotation}{\endquotation}
99 \newenvironment{numquote*}    {\quote}{\endquote}
100 \newenvironment{numquotation*}{\quotation}{\endquotation}
101
102 \newdimen\bframerule
103 \bframerule=\fboxrule
104
105 \newdimen\bframesep
106 \bframesep=\fboxsep
107
108 \newenvironment{bframe}
109 {%
110     \LWR@forceminwidth{\bframerule}%
111     \BlockClass[
112         border:\LWR@printlength{\LWR@atleastonept} solid black ; %
113         padding:\LWR@printlength{\bframesep}%
114     ]{bframe}
115 }
116 {\endBlockClass}
```

File 197 **lwarp-lips.sty**

§ 295 Package

lips

(*Emulates or patches code by* Matt Swift.)

Pkg lips lips is emulated.

```
% \LWR@ProvidesPackageDrop{lips}
\PackageInfo{lwarp}{Using the lwarp version of package ‘lips’.}%
\ProvidesPackage{lwarp-lips}[2001/08/31]

\NewDocumentCommand{\Lips}{}{\textellipsis}

\NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}

\let\lips\Lips
\let\olips\lips

\DeclareOption*{}
\DeclareOption{mla}{
\let\lips\BracketedLips
}
\ProcessOptions\relax

\newcommand \LPNobreakList {}
```

File 198 **lwarp-listings.sty**

§ 296 Package

listings

(*Emulates or patches code by* Carsten Heinz, Brooks Moses, Jobst Hoffmann.)

Pkg listings listings is supported with some limitations. Text formatting is not yet supported.

for HTML output:

```
\begin{warpHTML}

\LWR@ProvidesPackagePass{listings}[2018/09/02]
```

Force flexible columns. Fixed columns inserts spaces in the PDF output.

```
\lst@column@flexible
```

Patches to embed listings inside pre tags:

```
\let\LWR@origlst@Init\lst@Init
\let\LWR@origlst@DeInit\lst@DeInit

```

```
\let\LWR@origlsthkEveryPar\lsthk@EveryPar

\renewcommand{\l@lstlisting}[2]{\hypertocfloat{1}{lstlisting}{lol}{#1}{#2}}
```

`\lstset` {⟨*options*⟩}

Use the listings `literate` option to replace HTML entities:

```
\def\lstset@#1{\endgroup%
%  \ifx\@empty#1%
%         \@empty%
%     \else%
        \setkeys{lst}{%
            #1%
            ,literate=%
            {<}{\HTMLentity{lt}}{4}%
            {>}{\HTMLentity{gt}}{4}%
            {\&}{\HTMLentity{amp}}{5}%
        }%
%     \fi%
}
```

`\lst@Init` {⟨*backslash-processing*⟩} Done at the start of a listing.

```
\renewcommand{\lst@Init}[1]{%
```

Perform the listings initialization:

```
\LWR@traceinfo{lst@Init}%
\renewcommand*{\@captype}{lstlisting}%
\let\lst@aboveskip\z@\let\lst@belowskip\z@%
\gdef\lst@boxpos{t}%
\let\lst@frame\@empty
    \let\lst@frametshape\@empty
    \let\lst@framershape\@empty
    \let\lst@framebshape\@empty
    \let\lst@framelshape\@empty
\lstframe@\lst@frameround ffff\relax%
\lst@multicols\@empty%
\LWR@origlst@Init{#1}\relax%
```

Avoids extra horizontal space:

```
\def\lst@framelr{}%
```

```
\LWR@traceinfo{finished origlst@Init}%
\lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the <pre>, then reenable line numbers.

```
\LWR@traceinfo{About to create verbatim.}%
\let\lsthk@EveryPar\relax%
\LWR@forcenewpage
\LWR@atbeginverbatim{2}{programlisting}%

\let\lsthk@EveryPar\LWR@origlsthkEveryPar%
\else%
```

Inline, so open a :

```
\ifbool{LWR@verbtags}{\LWR@htmltag{span class="inlineprogramlisting"}}{}%
\fi%
}
```

`\lst@DeInit` Done at the end of a listing.

```
\renewcommand*{\lst@DeInit}{%
\lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```
\let\lsthk@EveryPar\relax%
\LWR@afterendverbatim{0}%
\let\lsthk@EveryPar\LWR@origlsthkEveryPar%
\else%
```

Inline, so create the closing :

```
\ifbool{LWR@verbtags}{\noindent\LWR@htmltag{/span}}{}%
\fi%
```

Final listings deinit:

```
\LWR@origlst@DeInit%
}
```

`\lst@MakeCaption` {⟨*t*/*b*⟩}

This is called BOTH at the top and at the bottom of each listing.

Patched for lwarp.

```
\def\lst@MakeCaption#1{%
\LWR@traceinfo{MAKING CAPTION at #1}%
  \lst@ifdisplaystyle
\LWR@traceinfo{making a listings display caption}%
    \ifx #1t%
         \ifx\lst@@caption\@empty\expandafter\lst@HRefStepCounter \else
                                  \expandafter\refstepcounter
         \fi {lstlisting}%
\LWR@traceinfo{About to assign label: !\lst@label!}%
%         \ifx\lst@label\@empty\else
% \label{\lst@label}\fi
\LWR@traceinfo{Finished assigning the label.}%
        \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
        \global\let\lst@name\lst@arg \global\let\lstname\lst@name
        \lst@ifnolol\else
            \ifx\lst@@caption\@empty
                \ifx\lst@caption\@empty
                    \ifx\lst@intname\@empty \else \def\lst@temp{ }%
                    \ifx\lst@intname\lst@temp \else
```

This code places a contents entry for a non-float. This would have to be modified for lwarp:

```
\LWR@traceinfo{addcontents lst@name: -\lst@name-}%
```

```
%                               \addcontentsline{lol}{lstlisting}{\lst@name}
                      \fi\fi
                  \fi
              \else
```

This would have to be modified for lwarp:

```
\LWR@traceinfo{addcontents lst@@caption: -\lst@@caption-}%
                   \addcontentsline{lol}{lstlisting}%
{\protect\numberline{\thelstlisting}%
{\protect\ignorespaces \LWR@isolate{\lst@@caption} \protect\relax}}%
             \fi
          \fi
      \fi
    \ifx\lst@caption\@empty\else
\LWR@traceinfo{lst@caption not empty-}%
        \lst@IfSubstring #1\lst@captionpos
            {\begingroup
\LWR@traceinfo{at the selected position}%
```

These space and box commands are not needed for HTML output:

```
%               \let\@@vskip\vskip
%               \def\vskip{\afterassignment\lst@vskip \@tempskipa}%
%               \def\lst@vskip{\nobreak\@@vskip\@tempskipa\nobreak}%
%               \par\@parboxrestore\normalsize\normalfont % \noindent (AS)
%               \ifx #1t\allowbreak \fi
              \ifx\lst@title\@empty
```

New lwarp code to create a caption:

```
                     \LWR@stoppars%
                    \lst@makecaption\fnum@lstlisting{\ignorespaces \lst@caption}
              \else
```

New lwarp code to create a title:

```
%                   \lst@maketitle\lst@title % (AS)
\LWR@traceinfo{Making title: \lst@title}%
\begin{BlockClass}{lstlistingtitle}% lwarp
\lst@maketitle\lst@title% lwarp
\end{BlockClass}% lwarp
              \fi
\LWR@traceinfo{About to assign label: !\lst@label!}%
        \ifx\lst@label\@empty\else
\leavevmode% gets rid of bad space factor error
\GetTitleStringExpand{\lst@caption}%
\edef\LWR@lntemp{\GetTitleStringResult}%
\edef\@currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
\label{\lst@label}\fi
\LWR@traceinfo{Finished assigning the label.}%
```

Not needed for lwarp:

```
%               \ifx #1b\allowbreak \fi
              \endgroup}{}%
    \fi
\LWR@traceinfo{end of making a listings display caption}%
  \else
\LWR@traceinfo{INLINE}%
```

```
  \fi
\LWR@traceinfo{DONE WITH CAPTION at #1}%
}
```

line numbers Patched to keep left line numbers outside of the left margin, and place right line numbers in a field `\VerbatimHTMLWidth` wide.

```
\lst@Key{numbers}{none}{%
    \let\lst@PlaceNumber\@empty
    \lstKV@SwitchCases{#1}%
    {none:\\%
     left:\def\lst@PlaceNumber{%
```

For now, lwarp places left line numbers inline. Ideally the entire line would be moved to the right, but conflicts with list indenting occurs.

```
%         \LWR@origllap{
            \LWR@orignormalfont%
            \lst@numberstyle{\thelstnumber}\kern\lst@numbersep%
%         }
    }\\%
     right:\def\lst@PlaceNumber{\LWR@origrlap{\LWR@orignormalfont
                \kern 6in \kern\lst@numbersep
                \lst@numberstyle{\thelstnumber}}}%
    }{\PackageError{lwarp-listings}{Numbers #1 unknown}\@ehc}}

\end{warpHTML}
```

File 199 **lwarp-listliketab.sty**

§ 297 Package listliketab

Pkg listliketab listliketab is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{listliketab}[2005/01/09]

\newcommand*{\storestyleof}[1]{}
\newcommand*{\storeliststyle}{}
\newenvironment{listliketab}{}{}
```

File 200 **lwarp-lltjext.sty**

§ 298 Package lltjext

(*Emulates or patches code by* The LuaTeX-ja project team.)

Pkg lltjext lltjext is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{lltjext}[2018/10/07]
```

```
\protected\def\yoko{%
  \directlua{luatexja.direction.set_list_direction(4, 'yoko')}%
}
\protected\def\tate{\yoko}
\protected\def\dtou{\yoko}
\protected\def\utod{\yoko}

\define@key[ltj]{japaram}{direction}{}

\yoko

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

File 201 **lwarp-longtable.sty**

§ 299 Package

longtable

(*Emulates or patches code by* David Carlisle.)

Pkg longtable longtable is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{longtable}[2014/10/28]
```

Use one of either \endhead or \endfirsthead for both print and HTML, and use a \warpprintonly macro to disable the other head phrase, and also the \endfoot and \endfirstfoot phrases. (See section 8.10.4 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced \noalign Use the \warpprintonly macro instead of the warpprint environment. Doing so helps avoid "Misplaced \noalign." when using \begin{warpprint}.

⚠ \kill \kill is ignored, place a \kill line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside \warpprintonly.

⚠ lateximage longtable is not supported inside a lateximage.

See:
http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable

Used to detect more than one of \endhead and \endfirsthead in use for HTML at the same time.

```
\newbool{LWR@longtable@havehead}
\boolfalse{LWR@longtable@havehead}
```

Env longtable * [⟨*horizalignment*⟩] {⟨*colspec*⟩} Emulates the longtable environment.

Per the caption package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options [c], [l], and [r] are ignored.

```
\newenvironment{longtable*}[2][]{%
\LWR@floatbegin{table}%
\setcaptiontype{\LTcaptype}%
\caption@setoptions{longtable}%
\caption@setoptions{@longtable}%
\caption@LT@setup%
\booltrue{LWR@starredlongtable}%
\boolfalse{LWR@longtable@havehead}%
\let\captionlistentry\LWR@LTcaptionlistentry%
\tabular{#2}
}
{\endtabular\LWR@floatend}

```

```
\newenvironment{longtable}[2][]{%
\LWR@floatbegin{table}%
\setcaptiontype{\LTcaptype}%
\caption@setoptions{longtable}%
\caption@setoptions{@longtable}%
\caption@LT@setup%
\refstepcounter{\LTcaptype}%
\boolfalse{LWR@longtable@havehead}%
\let\captionlistentry\LWR@LTcaptionlistentry%
\tabular{#2}
}
{\endtabular\LWR@floatend}
```

Provided for compatibility, but ignored:

```
\newcounter{LTchunksize}
```

Error for heads which should have been in `\warpprintonly`:

```
\newcommand*{\LWR@longtable@headerror}{%
    \PackageError{lwarp}
    {For longtable:\MessageBreak
    1: Keep either one of an \protect\endhead\space or
        \protect\endfirsthead\space\MessageBreak
        \space phrase as-is, to be used by both print and HTML.\MessageBreak
    2: Place any other \protect\end... phrases inside a\MessageBreak
        \space\protect\warpprintonly\space macro,
            to be ignored by HTML.\MessageBreak
    3: Add a final footer for HTML at the end of the table\MessageBreak
        \space inside a \protect\warpHTMLonly\space macro.
            This can be\MessageBreak
        \space a copy of an \protect\endfoot\space or
            \protect\endfirstfoot\space phrase,\MessageBreak
        \space but without the actual \protect\endfoot\space
            or \protect\endfirstfoot\MessageBreak
        \space macros.  If using threeparttablex, add\MessageBreak
        \space \protect\insertTableNotes\space here,
            optionally with\MessageBreak
        \space \protect\UseMinipageWidths\space in front.\MessageBreak
    See the lwarp documentation regarding longtables\MessageBreak
    and threeparttablex}
    {See the lwarp documentation regading longtables and threeparttablex.}
}
```

Error if more than one of `\endhead` or `\endfirsthead` is outside of `warpprintonly`.

```
\newcommand*{\LWR@longtable@maybeheaderror}{%
\ifbool{LWR@longtable@havehead}%
    {\LWR@longtable@headerror}%
    {%
        \booltrue{LWR@longtable@havehead}
        \LWR@tabularendofline% throws away options //[dim] and //*
    }%
}
```

Error if more than one of these is outside of `warppprint`.

```
\def\endhead{\LWR@longtable@maybeheaderror}
\def\endfirsthead{\LWR@longtable@maybeheaderror}
```

Error if ANY of these is outside of `warppprint`.

```
\def\endfoot{\LWR@longtable@headerror}
\def\endlastfoot{\LWR@longtable@headerror}
```

```
\providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
\LWR@formatted{tabularnewline}
```

```
\newcommand{\setlongtables}{}% Obsolete command, does nothing.
\newlength{\LTleft}
\newlength{\LTright}
\newlength{\LTpre}
\newlength{\LTpost}
\newlength{\LTcapwidth}
```

```
\LetLtxMacro\LWR@origkill\kill
\renewcommand*{\kill}{\LWR@tabularendofline}
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\kill\LWR@origkill%
}
```

File 202 **lwarp-lscape.sty**

§ 300 Package lscape

(*Emulates or patches code by* D. P. Carlisle.)

Pkg lscape lscape is ignored.

for HTML output: Discard all options for lwarp-lscape.

```
\LWR@ProvidesPackageDrop{lscape}[2000/10/22]
```

```
\newenvironment*{landscape}{}{}
```

File 203 **lwarp-ltablex.sty**

§ 301 Package ltablex

(*Emulates or patches code by* Anil K. Goel.)

Pkg ltablex ltablex is emulated by lwarp.

for HTML output:

Relies on tabularx.

```
\RequirePackage{tabularx}

\LWR@ProvidesPackageDrop{ltablex}[2014/08/13]

\DeclareDocumentEnvironment{tabularx}{m o m}
{\longtable{#3}}
{\endlongtable}

\DeclareDocumentEnvironment{tabularx*}{m o m}
{\longtable{#3}}
{\endlongtable}

\newcommand*{\keepXColumns}{}
\newcommand*{\convertXColumns}{}
```

File 204 **lwarp-ltcaption.sty**

§ 302 Package ltcaption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg ltcaption ltcaption is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltcaption}[2018/08/26]
```

\LTcaptype is already defined by lwarp.

longtable* is already defined by lwarp-longtable.

```
\newlength{\LTcapskip}
\newlength{\LTcapleft}
\newlength{\LTcapright}
\newcommand*{\LTcapmarginsfalse}{}
```

File 205 **lwarp-ltxgrid.sty**

§ 303 Package ltxgrid

Pkg ltxgrid ltxgrid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltxgrid}[2010/07/25]

\newcommand*{\onecolumngrid}{}
\newcommand*{\twocolumngrid}{}
\newcommand*{\removestuff}{}
\newcommand*{\addstuff}[2]{}
\newcommand*{\replacestuff}[2]{}
```

File 206 **lwarp-ltxtable.sty**

§ 304 Package
# ltxtable

Pkg ltxtable ltxtable is emulated.

⚠ table numbering The print version does not seem to honor `longtable*` from the caption package, while lwarp does.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltxtable}[1995/12/11]
```

`\LTXtable` {⟨*width*⟩} {⟨*file*⟩}

```
\newcommand*{\LTXtable}[2]{%
\input{#2}%
}
```

File 207 **lwarp-lua-check-hyphen.sty**

§ 305 Package
# lua-check-hyphen

Pkg lua-check-hyphen lua-check-hyphen is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-check-hyphen}[2018/04/19]
```

```
\newcommand*{\LuaCheckHyphen}[1]{}
```

File 208 **lwarp-lua-visual-debug.sty**

§ 306 Package
# lua-visual-debug

Pkg lua-visual-debug lua-visual-debug is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-visual-debug}[2016/05/30]
```

File 209 **lwarp-luacolor.sty**

§ 307 Package
# luacolor

Pkg luacolor luacolor is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{luacolor}[2016/05/16]
```

```
\newcommand{\luacolorProcessBox}[1]{}
```

File 210 **lwarp-luatodonotes.sty**

§ 308 Package

luatodonotes

(*Emulates or patches code by* Fabian Lipp.)

Pkg luatodonotes luatodonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{luatodonotes}[2017/09/30]
```

Nullify options:

```
\@todonotes@additionalMarginEnabledfalse

\if@todonotes@disabled
\else

\newcommand{\ext@todo}{tdo}

\renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}

\let\LWRTODONOTES@orig@todototoc\todototoc

\renewcommand*{\todototoc}{%
\phantomsection%
\LWRTODONOTES@orig@todototoc%
}


\renewcommand{\@todonotes@drawMarginNoteWithLine}{%
\fcolorbox
    {\@todonotes@currentbordercolor}
    {\@todonotes@currentbackgroundcolor}
    {\arabic{@todonotes@numberoftodonotes}}
\marginpar{\@todonotes@drawMarginNote}
}

\renewcommand{\@todonotes@drawInlineNote}{%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \if@todonotes@authorgiven%
        {\@todonotes@author:\,}%
        \fi%
        \@todonotes@text%
```

```
    }%
}

\newcommand{\@todonotes@drawMarginNote}{%
    \if@todonotes@authorgiven%
        \@todonotes@author\par%
    \fi%
    \arabic{@todonotes@numberoftodonotes}: %
    \fcolorbox%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \@todonotes@sizecommand%
        \@todonotes@text %
    }%
}%

\renewcommand{\missingfigure}[2][]{%
\setkeys{todonotes}{#1}%
\addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todocommon\@todocommon

\RenewDocumentCommand{\@todocommon}{m m}{%
\begingroup%
\renewcommand*{\phantomsection}{}%
\LWRTODONOTES@orig@todocommon{#1}{#2}%
\endgroup%
}

\renewcommand{\@todoarea}[3][]{%
    \@todonotes@areaselectedtrue%
    \@todocommon{#1}{#2}%
    \todonotes@textmark@highlight{#3}%
    \zref@label{@todonotes@\arabic{@todonotes@numberoftodonotes}@end}%
}%


\DeclareDocumentCommand{\todonotes@textmark@highlight}{m}{%
\InlineClass[background:\LWR@origpound{}B3FFB3]{highlight}{#1}%
}

\fi% \if@todonotes@disabled
```

File 211 **lwarp-lyluatex.sty**

§ 309 Package

lyluatex

(*Emulates or patches code by* Fr. Jacques Peron, Urs Liska, Br. Samuel Springuel.)

Pkg lyluatex lyluatex is patched for use by lwarp.

For the first compile, to set *lwarpmk*'s configuration, use:

```
lualatex --shell-escape <filename>
```

⚠ images After compiling the document with **lwarpmk html**, use **lwarpmk limages** to convert the Lilypond images for HTML.

The option `insert=systems` results in an image per system. Each music image "system" CSS is placed inside a `<span>` of class `lyluatex`, which defaults to `display: inline-block`.

⚠ insert=fullpage The option `insert=fullpage` results in a single image per page of printed output. CSS Each music "fullpage" image is placed inside a `<div>` of class `lyluatex`. To match the number of measures per line with the printed version, use the geometry package to select the page geometry, or use the lyluatex options for page and staff sizes.

⚠ options To use `\linewidth` or `\textwidth` inside the package options for lyluatex, use the kvoptions-patch package first:

```
\usepackage{kvoptions-patch}
\usepackage[...,line-width-0.8\linewidth,...]{lyluatex}
```

⚠ raw-pdf If using `raw-pdf`, the resulting PDF images must be converted to SVG:

Enter ⇒ **lwarpmk pdftosvg tmp-ly/*.pdf**

for HTML output:

```
\LWR@origRequirePackage{luacode}

\LWR@ProvidesPackagePass{lyluatex}[2019/05/27]
```

User-redefinable `ALT` tag:

```
\newcommand*{\LyluatexImageAltText}{-lilypond-~\PackageDiagramAltText}
```

`\ly@compilescore` {⟨*Lilypond object*⟩}

```
\LetLtxMacro\LWR@orig@ly@compilescore\ly@compilescore

\renewcommand*{\ly@compilescore}[1]{%
```

A local group holds a number of changes:

```
    \begingroup%
```

The user's original geometry and font size are restored to match the print version. This allows for correct spacing in the musical score.

```
    \LWR@orignewpage%
    \LWR@origloadgeometry{LWR@usergeometry}%
    \LWR@print@normalsize%
```

A local group holds a redefined `\includegraphics` which is used by *lyluatex.lua* to insert the *Lilypond* score if `insert=systems` is used. This is now placed inside a `lateximage`, which itself is placed inside a of class `lyluatex`.

`\LWR@addbaselinemarker` preserves the left margins.

```
    \renewcommand{\includegraphics}[2][]{%
        \InlineClass{lyluatex}{%
            \begin{lateximage}[\LyluatexImageAltText]%
            \LWR@addbaselinemarker%
            \LWR@origincludegraphics{##2}%
            \end{lateximage}%
        }%
    }%
```

From the original:

```
    \ly@setunits%
    \directlua{
        ly_opts:set_option('currfiledir', [[\currfiledir]])
        ly_opts:set_option('twoside', '\ly@istwosided')
        #1
    }%
    \ly@resetunits%
    \ly@currentfonts%
```

The fullpage version is set inside an HTML :

```
    \directlua{
        if (ly.score.insert == 'fullpage') then
            tex.print{[[\string\begin{BlockClass}{lyluatex}]]}
        end
    }%
```

Generate the score:

```
    \directlua{ly.score:process()}%
```

Close the :

```
    \directlua{
        if (ly.score.insert == 'fullpage') then
            tex.print{[[\string\end{BlockClass}]]}
        end
    }%
```

Move to a new page and renew the regular page geometry:

```
    \LWR@orignewpage%
    \LWR@origrestoregeometry%
```

End of the local group.

```
    \endgroup%
}
```

In HTML the following generates an error, so is removed:

```
\xpatchcmd{\endly@bufferenv}
    {\hspace{0pt}\\}
    {}
    {}
    {\LWR@patcherror{lyluatex}{endly@bufferenv}}
```

File 212 **lwarp-magaz.sty**

§ 310 Package magaz

Pkg magaz magaz is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{magaz}[2011/11/24]

\newcommand\FirstLine[1]{%
    \begingroup%
    \FirstLineFont{%
        \LWR@textcurrentcolor{%
            \LWR@textcurrentfont{%
                #1%
            }%
        }%
    }%
    \endgroup%
}

\providecommand\FirstLineFont{\scshape}
```

File 213 **lwarp-makeidx.sty**

§ 311 Package makeidx

(*Emulates or patches code by* LaTeX Project Team.)

Pkg makeidx makeidx is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{makeidx}[2014/09/29]
```

\@wrindex is redefined \AtBeginDocument by the lwarp core.

\printindex

```
\preto\printindex{%
    \LWR@orignewpage%
    \LWR@startpars%
}
```

File 214 **lwarp-manyfoot.sty**

§ 312 Package

manyfoot

Pkg manyfoot

manyfoot is emulated.

bigfoot, manyfoot

⚠ verbatim

Verbatim footnotes are not yet supported.

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XeLaTeX or LuaLaTeX instead of pdfLaTeX.

lwarp's emulation of bigfoot uses manyfoot, so some of the bigfoot enhancements are included here.

The bigfoot "default" footnote is ignored, using the lwarp version instead.

for HTML output:

```
\LWR@ProvidesPackageDrop{manyfoot}[2005/09/11]

\RequirePackage{nccfoots}

\newcommand{\extrafootnoterule}{}

\let\defaultfootnoterule\footnoterule

\newcommand*{\SelectFootnoteRule}[2][0]{}

\newcommand{\footnoterulepriority}{1}

\newcommand{\SetFootnoteHook}[1]{}
\@onlypreamble\SetFootnoteHook

\newcommand{\SplitNote}{}

\newcommand*\ExtraParaSkip[1]{}

\newcommand*{\newfootnote}[2][plain]{%
    \ifstrequal{#2}{default}{}{% not "default"
        \expandafter\newbox\csname LWR@footnote#2box\endcsname%
        \appto{\LWR@printpendingfootnotes}{%
            \LWR@@printpendingfootnotes{footnote#2}%
        }
        \long\csdef{Footnotetext#2}##1##2{%
            \NCC@makefnmark{##1}%
```

```
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
        \long\csdef{Footnotetext#2+}##1##2{%
            \NCC@makefnmark{##1}%
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
    }% not "default"
}
\@onlypreamble\newfootnote

\newcommand*{\DeclareNewFootnote}[2][plain]{%
  \@ifnextchar[%
        {\LWR@manyfoot@declare{#1}{#2}}%
        {\LWR@manyfoot@declare{#1}{#2}[arabic]}%
}

\def\LWR@manyfoot@declare#1#2[#3]{%
\ifstrequal{#2}{default}{}{% not "default"
  \newfootnote[#1]{#2}%
  \newcounter{footnote#2}%
    \newcounter{footnote#2Reset}%
    \setcounter{footnote#2Reset}{0}%
    \csdef{thefootnote#2}{%
      \expandafter\noexpand\csname @#3\endcsname%
      \expandafter\noexpand\csname c@footnote#2\endcsname%
    }%
```

For bigfoot, the footnote commands may be appended with one or two plusses or one or two minuses, which are ignored in HTML.

```
  \expandafter\NewDocumentCommand\csname footnote#2\endcsname{t{+}t{+}t{-}t{-}}{%
        \stepcounter{footnote#2}%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \@footnotemark%
        \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
    }%
    \csdef{footnotemark#2}{%
        \stepcounter{footnote#2}%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \@footnotemark%
    }%
  \expandafter\NewDocumentCommand\csname footnotetext#2\endcsname{t{+}t{+}t{-}t{-}}{%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
    }%
    \csdef{Footnotemark#2}{%
      \Footnotemark%
    }%
    \csdef{Footnote#2}##1{%
      \Footnotemark{##1}%
      \csuse{Footnotetext#2}{##1}%
    }%
}% not "default"
}
\@onlypreamble\DeclareNewFootnote
```

File 215 **lwarp-marginal.sty**

§ 313 Package marginal

Pkg marginal marginal is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{marginal}

\newcommand*{\showlostmarginals}{}
\newcommand*{\enlargefreelist}{}
\newcommand*{\onesidemarginals}{}
```

File 216 **lwarp-marginfit.sty**

§ 314 Package marginfit

Pkg marginfit marginfit is ignored.

for HTML output: Discard all options for lwarp-marginfit:

```
\LWR@ProvidesPackageDrop{marginfit}[2018/06/08]
```

File 217 **lwarp-marginfix.sty**

§ 315 Package marginfix

(*Emulates or patches code by* Stephen Hicks.)

Pkg marginfix marginfix is ignored.

for HTML output: Discard all options for lwarp-marginfix:

```
\LWR@ProvidesPackageDrop{marginfix}[2013/09/08]

\newcommand*{\marginskip}[1]{}
\newcommand*{\clearmargin}{}
\newcommand*{\softclearmargin}{}
\newcommand*{\extendmargin}[1]{}
\newcommand*{\mparshift}[1]{}
\newdimen\marginheightadjustment
\newdimen\marginposadjustment
\newcommand*{\blockmargin}[1][]{}
\newcommand*{\unblockmargin}[1][]{}
\newcommand*{\marginphantom}[2][]{}
```

File 218 **lwarp-marginnote.sty**

§ 316 Package marginnote

(*Emulates or patches code by* Markus Kohm.)

Pkg marginnote marginnote is emulated.

for HTML output: Discard all options for lwarp-marginnote:

```
\LWR@ProvidesPackageDrop{marginnote}[2018/08/09]

\NewDocumentCommand{\marginnote}{+o +m o}{\marginpar{#2}}

\newcommand*{\marginnoteleftadjust}{}
\newcommand*{\marginnoterightadjust}{}
\newcommand*{\marginnotetextwidth}{}
\let\marginnotetextwidth\textwidth
\newcommand*{\marginnotevadjust}{}
\newcommand*{\marginfont}{}
\newcommand*{\raggedleftmarginnote}{}
\newcommand*{\raggedrightmarginnote}{}
```

File 219 **lwarp-marvosym.sty**

§ 317 Package marvosym

(*Emulates or patches code by* Thomas Henlich, Mojca Miklavec.)

Pkg marvosym marvosym is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```
\LWR@ProvidesPackagePass{marvosym}[2011/07/20]

\renewcommand{\mvchr}[1]{%
    \begin{lateximage}*[symbol #1][marvosym #1]%
    \mvs\char#1%
    \end{lateximage}%
}

\renewcommand{\textmvs}[1]{%
    \begin{lateximage}%
    \mvs #1%
    \end{lateximage}%
}
```

File 220 **lwarp-mathtools.sty**

§ 318 Package mathtools

(*Emulates or patches code by* Morten Høgholm, Lars Madsen.)

Pkg mathtools mathtools is patched for use by lwarp.

⚠ numbering, italics showonlyrefs and mathic are disabled.

for HTML output:

```
\LWR@ProvidesPackagePass{mathtools}[2018/01/08]
\RequirePackage{graphicx}
\MHInternalSyntaxOn
```

Forces showonlyrefs off because lwarp uses cleveref, which is not compatible with showonlyrefs.

```
\renewcommand*\MT_showonlyrefs_true:{\MT_showonlyrefs_false:}
\mathtoolsset{showonlyrefs=false}
```

Forces math italic correction off. Not patched for lwarp.

```
\renewcommand*{\MT_mathic_true:}{\MT_mathic_false:}
\mathtoolsset{mathic=false}
\MHInternalSyntaxOff
```

File 221 **lwarp-mcaption.sty**

§ 319 Package mcaption

(*Emulates or patches code by* Stephan Hennig.)

Pkg mcaption mcaption is ignored.

for HTML output: Discard all options for lwarp-mcaption:

```
\LWR@ProvidesPackageDrop{mcaption}[2009/03/13]
\newenvironment{margincap}{}{}
\newcommand*{\margincapalign}{}
\newlength{\margincapsep}
```

File 222 **lwarp-mdframed.sty**

§ 320 Package mdframed

(*Emulates or patches code by* Marco Daniel, Elke Schubert.)

Pkg mdframed mdframed is loaded with options forced to `framemethod=none`.

§ 320.1 Limitations

support Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading When used, lwarp loads mdframed in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont `theoremtitlefont` is not supported, since the following text is not in braces in the mdframed source.

ignored options `userdefinedwidth` and `align` are currently ignored.

css classes Environments created or encapsulated by mdframed are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class |mdframedtitle|. Subtitles are in a `<div>` of class |mdframedsubtitle|, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

§ 320.2 Package loading

for HTML output:

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackageDrop{mdframed}[2013/07/01]
```

Do not require Ti*k*z or pstricks:

```
\LWR@origRequirePackage[framemethod=none]{mdframed}
```

§ 320.3 Patches

Patch to remove PDF formatting and add HTML tags:

```
\AtBeginDocument{
\def\mdf@trivlist#1{%
  \edef\mdf@temp{%
%     \topsep=\the\topsep\relax%
%     \partopsep=\the\partopsep\relax%
%     \parsep=\the\parsep\relax%
  }%
%   \setlength{\topsep}{#1}%
%   \topskip\z@%
%   \partopsep\z@%
%   \parsep\z@%
%   \@nmbrlistfalse%
%   \@trivlist%
%   \labelwidth\z@%
%   \leftmargin\z@%
%   \itemindent\z@%
  \let\@itemlabel\@empty%
  \def\makelabel##1{##1}%
%   \item\relax\mdf@temp\relax%
}

\renewcommand*{\endmdf@trivlist}{%
\LWR@traceinfo{endmdf@trivlist}%
% \endtrivlist%
\LWR@listend%
}
}% AtBeginDocument
```

§ 320.4 Initial setup

To handle CSS and paragraphs, patch code at start and end of environment and contents. `\LWR@print@raggedright` helps avoid hyphenation.

```
\mdfsetup{
startcode={\LWR@mdframedstart\LWR@print@raggedright},
endcode={\LWR@mdframedend},
startinnercode={\LWR@startpars\LWR@print@raggedright},
endinnercode={\LWR@stoppars},
}
```

§ 320.5 Color and length HTML conversion

\LWR@mdfprintcolor {⟨*mdfcolorkey*⟩}

Given the mdframed key, print the color.

```
\newcommand*{\LWR@mdfprintcolor}[1]{%
\convertcolorspec{named}{\@nameuse{mdf@#1}}{HTML}\LWR@tempcolor%
\LWR@origpound\LWR@tempcolor
}
```

\LWR@mdfprintlength {⟨*mdflengthkey*⟩}

Given the mdframed key, print the length.

```
\newcommand*{\LWR@mdfprintlength}[1]{%
\LWR@forceminwidth{\@nameuse{mdf@#1@length}}%
\LWR@printlength{\LWR@atleastonept}%
}
```

§ 320.6 Environment encapsulation

\LWR@mdframedstart Actions before an mdframe starts.

Encapsulate a frame inside a of the desired class.

```
\newcommand*{\LWR@mdframedstart}{%
\LWR@traceinfo{LWR@mdframedstart start}%
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
\LWR@stoppars%
```

Open a and with custom class and custom style. A BlockClass environment is not used because this is created by the mdframed startcode and endcode settings, which do not properly nest the inside the mdframed environment.

```
\LWR@htmltagc{div class="%
mdframed%
\ifdefstring{\LWR@mdthisenv}{mdframed}{}{ \LWR@mdthisenv}%
" \LWR@orignewline
style=" \LWR@orignewline
```

Convert and print the background color:

```
background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
border: \LWR@mdfprintlength{linewidth} solid
\LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
\ifbool{mdf@shadow}{%
    box-shadow:
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintcolor{shadowcolor} ;
```

```
}
{box-shadow: none ;}
\LWR@orignewline

"}
% \LWR@htmldivclass{\LWR@mdthisenv}
```

mdframed environment may not work with the HTML versions of the following, so restore them to their originals while inside mdframed:

```
\LWR@select@print@hspace%
\renewcommand*{\rule}{\LWR@print@rule}
\LetLtxMacro\makebox\LWR@print@makebox%

\LWR@startpars%
\LWR@traceinfo{LWR@mdframedstart done}%
}
```

\LWR@mdframedend Actions after an mdframe ends.

After closing the , globally restore to the default environment type:

```
\newcommand*{\LWR@mdframedend}{
\LWR@traceinfo{LWR@mdframedend start}%
```

Close the custom :

```
\LWR@htmldivclassend{\LWR@mdthisenv}
```

Reset future custom class to the default:

```
\gdef\LWR@mdthisenv{mdframed}
```

Resume paragraph handling:

```
\LWR@startpars%
\LWR@traceinfo{LWR@mdframedend done}%
}
```

§ 320.7 Mdframed environment

```
\renewenvironment{mdframed}[1][]{%
 \color@begingroup%
   \mdfsetup{userdefinedwidth=\linewidth,#1}%
   \mdf@startcode%
   \mdf@preenvsetting%
   \ifdefempty{\mdf@firstframetitle}{}%
            {\let\mdf@frametitlesave\mdf@frametitle%
             \let\mdf@frametitle\mdf@firstframetitle%
            }%
   \ifvmode\nointerlineskip\fi%
        \ifdefempty{\mdf@frametitle}{}%
            {\mdfframedtitleenv{\mdf@frametitle}%
% \mdf@@frametitle@use%
            }%
   \mdf@trivlist{\mdf@skipabove@length}%%
   \mdf@settings%
%    \mdf@lrbox{\mdf@splitbox@one}%
%    \mdf@startinnercode%
  }%
```

```
 {%
%    \mdf@@ignorelastdescenders%
   \par%
%     \unskip\ifvmode\nointerlineskip\hrule \@height\z@ \@width\hsize\fi%%
   \ifmdf@footnoteinside%
      \def\mdf@reserveda{%
        \mdf@footnoteoutput%
%         \mdf@endinnercode%
%         \endmdf@lrbox%
%         \ifdefempty{\mdf@frametitle}{}%
%             {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%         \detected@mdf@put@frame
      }%
   \else%
      \def\mdf@reserveda{%
%         \mdf@endinnercode%
%         \endmdf@lrbox%
%         \ifdefempty{\mdf@frametitle}{}%
%             {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%         \detected@mdf@put@frame%
        \mdf@footnoteoutput%
        }%
   \fi%
   \mdf@reserveda%
  \aftergroup\endmdf@trivlist%
 \color@endgroup%
 \mdf@endcode%
}
```

\mdf@footnoteoutput

```
\renewrobustcmd*\mdf@footnoteoutput{%
    \LWR@printpendingmpfootnotes%
}
```

§ 320.8 Titles and subtitles

\mdfframedtitleenv {⟨*title*⟩}

Place the title inside a of class mdframedtitle:

```
\newlength{\LWR@titleroundcorner}

\renewrobustcmd\mdfframedtitleenv[1]{%
\LWR@traceinfo{LWR@mdframedtitleenv start}%
```

Open a with a custom class and custom style:

```
\begin{BlockClass}[%
```

Convert and print the title background color:

```
background:
\LWR@mdfprintcolor{frametitlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the title rule:

```
\ifbool{mdf@frametitlerule}{%
```

```
    border-bottom:
    \LWR@mdfprintlength{frametitlerulewidth}
    solid
    \LWR@mdfprintcolor{frametitlerulecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening tag:

```
]{mdframedtitle}%
```

Print the title inside the :

```
\mdf@frametitlefont{\LWR@textcurrentfont{#1}}%
```

Close the :

```
\end{BlockClass}%
\LWR@traceinfo{LWR@mdframedtitleenv end}%
}
```

\LWR@mdfsubtitlecommon {⟨*sub -or- subsub*⟩} [⟨*options*⟩] {⟨*title*⟩}

Common code for \LWR@mdfsubtitle and \LWR@mdfsubsubtitle.

Encapsulate the subtitle inside a of class mdframedsubtitle:

```
\NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}
{% the following empty line is required

\LWR@traceinfo{LWR@mdframedsubtitlecommon start}%
```

Open a with a custom class and custom style:

```
\begin{BlockClass}[%
```

Convert and print the background color:

```
background:
\LWR@mdfprintcolor{#1titlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the above line:

```
\ifbool{mdf@#1titleaboveline}{%
    border-top:
    \LWR@mdfprintlength{#1titleabovelinewidth}
    solid
    \LWR@mdfprintcolor{#1titleabovelinecolor}
    ; \LWR@orignewline
}{}%
```

Convert and print the below line:

```
\ifbool{mdf@#1titlebelowline}{%
    border-bottom:
    \LWR@mdfprintlength{#1titlebelowlinewidth}
    solid
    \LWR@mdfprintcolor{#1titlebelowlinecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening tag:

```
174 ]{mdframed#1title}%
```

Perform the original subtitle action:

```
175 \IfNoValueTF{#2}
176 {\@nameuse{LWR@origmdf#1title}{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
177 {\@nameuse{LWR@origmdf#1title}[#2]{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
```

Close the :

```
178 \end{BlockClass}%
179 \LWR@traceinfo{LWR@mdframedsubtitlecommon end}%
180 }
```

\LWR@mdfsubtitle [⟨*options*⟩] {⟨*title*⟩}

```
181 \newcommand*{\LWR@mdfsubtitle}{%
182 \LWR@mdfsubtitlecommon{sub}%
183 }
184 \let\mdfsubtitle\LWR@mdfsubtitle
```

\LWR@mdfsubsubtitle [⟨*options*⟩] {⟨*title*⟩}

```
185 \newcommand*{\LWR@mdfsubsubtitle}{%
186 \LWR@mdfsubtitlecommon{subsub}%
187 }
188 \let\mdfsubsubtitle\LWR@mdfsubsubtitle
```

§ 320.9 New environments

\LWR@mdthisenv Stores the environment of the frame about to be created:

```
189 \newcommand*{\LWR@mdthisenv}{mdframed}
```

\newmdenv [⟨*options*⟩] {⟨*env-name*⟩}

Modified from the original to remember the environment.

```
190 \renewrobustcmd*\newmdenv[2][]{%
191 \newenvironment{#2}%
192 {%
193 \mdfsetup{#1}%
194 \renewcommand*{\LWR@mdthisenv}{md#2}%
195 \begin{mdframed}%
196 }
197 {\end{mdframed}}%
198 }
```

\surroundwithmdframed [⟨*options*⟩] {⟨*environment*⟩}

Modified from the original to remember the environment.

```
199 \renewrobustcmd*{\surroundwithmdframed}[2][]{%
200 \BeforeBeginEnvironment{#2}{%
201 \renewcommand*{\LWR@mdthisenv}{md#2}%
202 \begin{mdframed}[#1]}%
203 \AfterEndEnvironment{#2}{\end{mdframed}}%
204 }
```

\mdtheorem [⟨*mdframed-options*⟩] {⟨*envname*⟩} [⟨*numberedlike*⟩] {⟨*caption*⟩} [⟨*within*⟩]

Modified from the original to remember the environment.

```
\DeclareDocumentCommand{\mdtheorem}{ O{} m o m o }%
{\ifcsdef{#2}%
  {\mdf@PackageWarning{Environment #2 already exits\MessageBreak}}%
  {%
   \IfNoValueTF {#3}%
    {%#3 not given -- number relationship
     \IfNoValueTF {#5}%
       {%#3+#5 not given
       \@definecounter{#2}%
       \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
       \newenvironment{#2}[1][]{%
         \refstepcounter{#2}%
         \ifstrempty{##1}%
           {\let\@temptitle\relax}%
           {%
            \def\@temptitle{\mdf@theoremseparator%
                            \mdf@theoremspace%
                            \mdf@theoremtitlefont%
                            \LWR@textcurrentfont{##1}}% lwarp
            \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
            }%
         \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                         \@temptitle}]}%
         {\end{mdframed}}%
       \newenvironment{#2*}[1][]{%
         \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
         \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
         {\end{mdframed}}%
       }%
       {%#5 given -- reset counter
       \@definecounter{#2}\@newctr{#2}[#5]%
       \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
       \expandafter\xdef\csname the#2\endcsname{%
             \expandafter\noexpand\csname the#5\endcsname \@thmcountersep%
                \@thmcounter{#2}}%
       \newenvironment{#2}[1][]{%
         \refstepcounter{#2}%
         \ifstrempty{##1}%
           {\let\@temptitle\relax}%
           {%
            \def\@temptitle{\mdf@theoremseparator%
                            \mdf@theoremspace%
                            \mdf@theoremtitlefont%
                            \LWR@textcurrentfont{##1}}% lwarp
            \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
            }
         \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                         \@temptitle}]}%
         {\end{mdframed}}%
       \newenvironment{#2*}[1][]{%
         \ifstrempty{##1}%
```

```
            {\let\@temptitle\relax}%
            {%
             \def\@temptitle{\mdf@theoremseparator%
                             \mdf@theoremspace%
                             \mdf@theoremtitlefont%
                             \LWR@textcurrentfont{##1}}% lwarp
             \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
             }%
          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
          {\end{mdframed}}%
        }%
     }%
     {%#3 given -- number relationship
        \global\@namedef{the#2}{\@nameuse{the#3}}%
        \newenvironment{#2}[1][]{%
          \refstepcounter{#3}%
          \ifstrempty{##1}%
            {\let\@temptitle\relax}%
            {%
             \def\@temptitle{\mdf@theoremseparator%
                             \mdf@theoremspace%
                             \mdf@theoremtitlefont%
                             \LWR@textcurrentfont{##1}}% lwarp
             \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
             }
          \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                          \@temptitle}]}%
          {\end{mdframed}}%
        \newenvironment{#2*}[1][]{%
          \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
          {\end{mdframed}}%
     }%
    \BeforeBeginEnvironment{#2}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
    \BeforeBeginEnvironment{#2*}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
   }%
}
```

\newmdtheoremenv [⟨*1: mdframed-options*⟩] {⟨*2: envname*⟩} [⟨*3: numberedlike*⟩] {⟨*4: caption*⟩} [⟨*5: within*⟩]

Modified from the original to remember the environment.

```
\DeclareDocumentCommand\newmdtheoremenv{O{} m o m o }{%
 \ifboolexpr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }%
    {\newtheorem{#2}{#4}}%
    {%
     \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}%
     \IfValueT{#5}{\newtheorem{#2}{#4}[#5]}%
    }%
\BeforeBeginEnvironment{#2}{%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}[#1]}%
\AfterEndEnvironment{#2}{%
\end{mdframed}}%
}
```

File 223 **lwarp-media9.sty**

§ 321 Package

media9

Pkg media9 media9 is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

⚠ & in a URL Many special characters are converted to regular catcode 12 characters for use inside a URL. & is used in the flash variables fields, which are split with xparse \SplitList, which does not seem to work with a catcode 12 divider token, so & is not converted to catcode 12, and will not work in a URL with media9. Using & in a URL in a flashvars field may also cause parsing problems with print output, as well.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{media9}[2019/02/21]
```

```
\LWR@origRequirePackage{lwarp-common-multimedia}

\RequirePackage{xkeyval}
```

`\addmediapath` {⟨*path*⟩}

Supported.

```
\newcommand*{\LWR@medianine@path}{}

\newcommand*{\addmediapath}[1]{\appto\LWR@medianine@path{{#1}}}
```

The options and poster text are reused in several places.

```
\newcommand*{\LWR@medianine@postertext}{}
\newcommand*{\LWR@medianine@options}{}
```

Each `addresource` can generate a multimedia object.

```
\define@key{LWR@medianine}{addresource}{%
    \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]
        {\LWR@medianine@postertext}
        {#1}
}
```

Each `flashvars` source can generate a multimedia object.

```
\newcommand*{\LWR@medianine@flashvarsb}[1]{%
    \IfBeginWith{#1}{source=}{%
        \StrGobbleLeft{#1}{7}[\LWR@tempone]%
        \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
            {\LWR@medianine@postertext}%
            {\LWR@tempone}%
    }{}%
    \IfBeginWith{#1}{src=}{%
        \StrGobbleLeft{#1}{4}[\LWR@tempone]%
        \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
            {\LWR@medianine@postertext}%
            {\LWR@tempone}%
    }{}%
}

\NewDocumentCommand{\LWR@medianine@flashvars}{ >{\SplitList{&}} m }{%
    \ProcessList {#1}{\LWR@medianine@flashvarsb}%
}

\define@key{LWR@medianine}{flashvars}{%
    \LWR@medianine@flashvars{#1}%
}
```

`\includemedia` [⟨*options*⟩] {⟨*poster text*⟩} {⟨*file or URL*⟩}

```
\newcommand*{\LWR@includemediab}[3][]{%
    \let\input@path\LWR@medianine@path%
    \renewcommand*{\LWR@medianine@options}{#1}%
```

```
    \renewcommand*{\LWR@medianine@postertext}{#2}%
    \setkeys*{LWR@medianine}{#1}%
    \IfBeginWith{#3}{http}{\LWR@multimedia[#1]{#2}{#3}}{%
    \IfBeginWith{#3}{HTTP}{\LWR@multimedia[#1]{#2}{#3}}{%
    \IfBeginWith{#3}{ftp}{\LWR@multimedia[#1]{#2}{#3}}{%
    \IfBeginWith{#3}{FTP}{\LWR@multimedia[#1]{#2}{#3}}{%
    }}}}%
    \endgroup%
}

\newrobustcmd*{\includemedia}{%
    \begingroup%
    \catcode`\#=12%
    \catcode`\%=12%
%     \catcode`\&=12% left alone for splitting flash variables
    \catcode`\~=12%
    \catcode`\_=12%
    \LWR@includemediab%
}
```

\mediabutton `[`⟨*options*⟩`]` `{`⟨*text*⟩`}`

Ignored.

```
\newcommand*{\mediabutton}[2][]{}
```

File 224 **lwarp-memhfixc.sty**

§ 322 Package memhfixc

Pkg memhfixc memhfixc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{memhfixc}[2013/05/30]
```

File 225 **lwarp-metalogo.sty**

§ 323 Package metalogo

(*Emulates or patches code by* Andrew Gilbert Moschou.)

Pkg metalogo metalogo is used in print mode, and emulated in HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{metalogo}[2010/05/29]

\newcommand*{\LWR@HTML@setlogokern}[2]{}
\newcommand*{\LWR@HTML@setlogodrop}[2][XeTeX]{}
\newcommand*{\LWR@HTML@setLaTeXa}[1]{}
\newcommand*{\LWR@HTML@setLaTeXee}[1]{}
\newcommand*{\LWR@HTML@seteverylogo}[1]{}
\newcommand*{\LWR@HTML@everylogo}[1]{}

```

```
\LWR@formatted{setlogokern}
\LWR@formatted{setlogodrop}
\LWR@formatted{setLaTeXa}
\LWR@formatted{setLaTeXee}
\LWR@formatted{seteverylogo}
\LWR@formatted{everylogo}
```

File 226 **lwarp-metalogox.sty**

§ 324 Package metalogox

(*Emulates or patches code by* Brian Dunn.)

Pkg metalogox metalogox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{metalogox}[2019/01/20]
```

\AtBeginDocument, adjust the logo setting according to the font which is active at that moment.

```
\AtBeginDocument{
    \let\LWR@metalogox@currentformatting\LWR@formatting
    \renewcommand*{\LWR@formatting}{print}%
    \autoadjustlogos*
    \let\LWR@formatting\LWR@metalogox@currentformatting
}
```

File 227 **lwarp-mhchem.sty**

§ 325 Package mhchem

(*Emulates or patches code by* Martin Hensel.)

Pkg mhchem mhchem is patched for use by lwarp.

without MathJax Without MathJax, mhchem expressions are converted to svg math. Inline expressions use hashed filenames to allow reuse, and assume that any mhchem options are global.

MathJax with mhchem extension For MathJax, the mhchem extension is used if the mhchem expression is used inside a math expression:

```
$\ce{C6H5-CHO}$
```

not inside math If *not* used inside a math expression, lwarp converts standalone mhchem expressions into svg math images.

MathJax without mhchem extension If the MathJax mhchem extension is not used, expressions inside math must be placed between \displaymathother and \displaymathnormal:

```
\displaymathother
\[ \ce{ . . . } \]     . . .     $ \ce { . . . } $
\displaymathnormal
```

⚠ nested math

When producing HTML output without the MathJax mhchem extension, lwarp does not support the use of nested dollar signs in mhchem expressions.

For some examples from the mhchem manual, change as follows:

```
$\ce{NaOH(aq,$\infty$)}$            % old
$\ce{NaOH(aq,\infty)}$              % new

$\ce{Fe(CN)_{$\frac{6}{2}$}$}$      % old
$\ce{Fe(CN)_{\frac{6}{2}}}$         % new

$\ce{NO_$x$}$                       % old
$\ce{NO_x}$                         % new

$\ce{NO_${x}$}$                     % old
$\ce{NO_{x}}$                       % new

$\ce{$cis${-}[PtCl2(NH3)2]}$        % old
$\ce{\mathit{cis}{-}[PtCl2(NH3)2]}$ % new
```

for HTML output:

```
\LWR@ProvidesPackagePass{mhchem}[2018/06/22]
```

The original definition of \ce:

```
\LetLtxMacro\LWR@mhchem@origce\ce
```

The new definition, called from the new \ce after math shift is set. The starred lateximage uses a hashed filename for the SVG image. The alt tag is set to the mhchem expression.

```
\newcommand{\LWR@mhchem@HTML@ce}[1]{%
\LWR@findcurrenttextcolor% sets \LWR@tempcolor
\ifbool{LWR@xfakebold}%
    {\def\LWR@tempone{Y}}%
    {\def\LWR@tempone{N}}%
\begin{lateximage}*[\textbackslash{}ce\{\LWR@HTMLsanitize{#1}\}]*%
    [%
        FM\LWR@f@family%
        SR\LWR@f@series%
        SH\LWR@f@shape%
        SHC\LWR@f@shapecaps%
        CL\LWR@tempcolor%
        FB\LWR@tempone% xfakebold
    ]%
\LWR@setcurrentfont%
\LWR@mhchem@origce{#1}%
\end{lateximage}%
\endgroup%
\addtocounter{LWR@mhchem@cedepth}{-1}%
```

```
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cedepth}
\setcounter{LWR@mhchem@cedepth}{0}
```

The new `\ce`. Sets math shift then continues.

```
\renewcommand{\ce}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cedepth}}{0}{%
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cedepth}{1}%
\LWR@mhchem@HTML@ce%
}
```

The original definition of `\cesplit`:

```
\LetLtxMacro\LWR@mhchem@origcesplit\cesplit
```

The new definition, called from the new `\cesplit` after math shift is set. The starred `lateximage` uses a hashed filename for the SVG image. The `alt` tag is set to the mhchem expression.

```
\newcommand*{\LWR@mhchem@HTML@cesplit}[2]
{%
\LWR@findcurrenttextcolor% sets \LWR@tempcolor
\ifbool{LWR@xfakebold}%
    {\def\LWR@tempone{Y}}%
    {\def\LWR@tempone{N}}%
\begin{lateximage}*[\textbackslash{}cesplit\{\LWR@HTMLsanitize{#2}\}]*%
    [%
        FM\LWR@f@family%
        SR\LWR@f@series%
        SH\LWR@f@shape%
        SHC\LWR@f@shapecaps%
        CL\LWR@tempcolor%
        FB\LWR@tempone% xfakebold
    ]%
\LWR@setcurrentfont%
\LWR@mhchem@origcesplit{#1}{#2}%
\end{lateximage}%
\endgroup%
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cesplitdepth}
\setcounter{LWR@mhchem@cesplitdepth}{0}
```

The new `\cesplit`. Sets math shift then continues.

```
\renewcommand{\cesplit}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cesplitdepth}}{0}{%
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cesplitdepth}{1}%
\LWR@mhchem@HTML@cesplit%
}
```

Resore originals inside a `lateximage`:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\ce\LWR@mhchem@origce%
\LetLtxMacro\cesplit\LWR@mhchem@origcesplit%
}
```

File 228 **lwarp-microtype.sty**

§ 326 Package

microtype

(*Emulates or patches code by* R Schlicht.)

Pkg microtype

microtype is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output:

Discard all options for lwarp-microtype:

```
\LWR@ProvidesPackageDrop{microtype}[2018/01/14]

\DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m}{}
\DeclareDocumentCommand{\UseMicrotypeSet}{o m}{}
\DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m}{}
\DeclareDocumentCommand{\SetProtrusion}{o m m}{}
\DeclareDocumentCommand{\SetExpansion}{o m m}{}
\DeclareDocumentCommand{\SetTracking}{o m m}{}
\DeclareDocumentCommand{\SetExtraKerning}{o m m}{}
\DeclareDocumentCommand{\SetExtraSpacing}{o m m}{}
\DeclareDocumentCommand{\DisableLigatures}{o m}{}
\DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m}{}
\DeclareDocumentCommand{\DeclareMicrotypeVariants}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m}{}
\DeclareDocumentCommand{\LoadMicrotypeFile}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m}{}
\DeclareDocumentCommand{\microtypesetup}{m}{}
\DeclareDocumentCommand{\microtypecontext}{m}{}
\DeclareDocumentCommand{\textmicrotypecontext}{m m}{#2}
\@ifpackageloaded{letterspace}{\let\MT@textls\relax}{%
\DeclareDocumentCommand{\lsstyle}{}{}
\DeclareDocumentCommand{\textls}{o +m}{}
\DeclareDocumentCommand{\lslig}{m}{#1}
}
\def\DeclareMicrotypeSet#1#{\@gobbletwo}
\def\DeclareMicrotypeVariants#1#{\@gobble}
```

```
\@onlypreamble\DeclareMicrotypeSet
\@onlypreamble\UseMicrotypeSet
\@onlypreamble\DeclareMicrotypeSetDefault
\@onlypreamble\DisableLigatures
\@onlypreamble\DeclareMicrotypeVariants
\@onlypreamble\DeclareMicrotypeBabelHook
```

File 229 **lwarp-midfloat.sty**

§ 327 Package midfloat

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg midfloat midfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{midfloat}[2012/05/29]
```

```
\newenvironment{strip}[1][]{}{}
\newskip\stripsep
```

File 230 **lwarp-midpage.sty**

§ 328 Package midpage

Pkg midpage midpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{midpage}[2009/09/03]
```

```
\newenvironment{midpage}
{\begin{BlockClass}[%
    \LWR@print@mbox{margin-top:6ex} ; \LWR@print@mbox{margin-bottom:6ex}%
]{midpage}}
{\end{BlockClass}}
```

File 231 **lwarp-minibox.sty**

§ 329 Package minibox

(*Emulates or patches code by* Will Robertson.)

Pkg minibox minibox is patched for use by lwarp.

Due to HTML limitations regarding paragraphs and s, miniboxes inline with other text will appear on their own line.

for HTML output:

```
\LWR@ProvidesPackagePass{minibox}[2013/06/21]
```

```
\ExplSyntaxOn
\newcommand\LWR@HTML@minibox[2][]{%
    \LWR@stoppars%
    \group_begin:
    \keys_set:nn {minibox} {#1}
    \bool_if:NTF \l_minibox_frame_bool
    {
        \setlength\fboxrule{\l_minibox_rule_dim}
        \setlength\fboxsep{\l_minibox_pad_dim}
        \fboxBlock{%
            \begin{tabular}[\l_minibox_tabular_valign_tl]%
              {\l_minibox_tabular_preamble_tl}
                {#2}
            \end{tabular}
        }%
    }
    {
        \begin{BlockClass}[display:inline-block]{minibox}
        \begin{tabular}[\l_minibox_tabular_valign_tl]%
          {\l_minibox_tabular_preamble_tl}
            {#2}
        \end{tabular}
        \end{BlockClass}
    }
    \group_end:
    \LWR@startpars%
}
\ExplSyntaxOff

\LWR@formatted{minibox}
```

File 232 **lwarp-minitoc.sty**

§ 330 Package minitoc

Pkg minitoc minitoc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{minitoc}[2018/07/12]
```

mtcoff disables minitoc.

```
\usepackage{mtcoff}
```

File 233 **lwarp-morefloats.sty**

§ 331 Package morefloats

Pkg morefloats morefloats is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{morefloats}[2015/07/22]
```

File 234 **lwarp-moreverb.sty**

§ 332 Package moreverb

(*Emulates or patches code by* Robin Fairbairns.)

Pkg moreverb moreverb is supported with some patches.

for HTML output:

```
\begin{warpHTML}

\LWR@ProvidesPackagePass{moreverb}[2008/06/03]

\BeforeBeginEnvironment{verbatimtab}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{Verbatim}%
}
\AfterEndEnvironment{verbatimtab}{%
\LWR@afterendverbatim{1}%
}


\LetLtxMacro\LWRMV@orig@verbatimtabinput\@verbatimtabinput

\renewcommand{\@verbatimtabinput}[2][]{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{Verbatim}%
\LWRMV@orig@verbatimtabinput[#1]{#2}%
\LWR@afterendverbatim{1}%
}

\BeforeBeginEnvironment{listing}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
}

\AfterEndEnvironment{listing}{%
\LWR@afterendverbatim{1}%
}

\BeforeBeginEnvironment{listingcont}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
}

\AfterEndEnvironment{listingcont}{%
\LWR@afterendverbatim{1}%
}

\LetLtxMacro\LWRMV@@listinginput\@listinginput

\renewcommand{\@listinginput}[3][]{
```

```
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
\LWRMV@@listinginput[#1]{#2}{#3}%
\LWR@afterendverbatim{1}%
}


\renewenvironment*{boxedverbatim}
{
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{boxedverbatim}%
\verbatim%
}
{
\endverbatim%
\LWR@afterendverbatim{1}%
}

\end{warpHTML}
```

File 235 **lwarp-movie15.sty**

§ 333 Package movie15

Pkg movie15 movie15 is emualted.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

for HTML output:

```
\LWR@ProvidesPackageDrop{movie15}[2012/05/16]

\LWR@origRequirePackage{lwarp-common-multimedia}

\RequirePackage{xkeyval}

\newcommand*{\LWR@moviefifteen@text}{}

\define@key{LWR@moviefifteen}{text}{\renewcommand{\LWR@moviefifteen@text}{#1}}

\newcommand*{\LWR@includemovieb}[4][]{%
    \renewcommand{\LWR@moviefifteen@text}{(multimedia)}
    \setkeys*{LWR@moviefifteen}{#1}%
    \LWR@multimediab[#1,width=#2,height=#3]{\LWR@moviefifteen@text}{#4}%
}

\newrobustcmd*{\includemovie}{%
    \begingroup%
    \catcode`\#=12%
    \catcode`\%=12%
    \catcode`\&=12%
    \catcode`\~=12%
    \catcode`\_=12%
    \LWR@includemovieb%
}


\newcommand*{\movieref}[3][]{}

\LetLtxMacro\movie\LWR@multimedia
% \LetLtxMacro\sound\LWR@multimedia% not in media15

\newcommand{\hyperlinkmovie}[3][]{}
```

File 236 **lwarp-mparhack.sty**

§ 334 Package

mparhack

Pkg mparhack

mparhack is ignored.

for HTML output:

Discard all options for lwarp-mparhack:

```
\LWR@ProvidesPackageDrop{mparhack}[2005/04/17]
```

File 237 **lwarp-multicap.sty**

§ 335 Package multicap

Pkg multicap multicap is emualted.

for HTML output:

```
\LWR@ProvidesPackageDrop{multicap}[2002/05/04]

\newcommand*{\mfcaption}{\captionof{figure}}
\newcommand*{\mtcaption}{\captionof{table}}
\newcounter{mcapsize}
\newcounter{mcapskip}
\newlength{\abvmcapskip}
\newlength{\blwmcapskip}
```

File 238 **lwarp-multicol.sty**

§ 336 Package multicol

(*Emulates or patches code by* Frank Mittelbach.)

Pkg multicol multicol is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{multicol}[2018/12/27]
```

Multicols are converted into a 1–3 column display, browser-supported.

The optional multicols heading is placed inside a of class multicolsheading.

The content is placed inside a of class multicols.

```
\begin{warpHTML}
```

Env multicols * {⟨*numcols*⟩} [⟨*heading*⟩]

```
\NewDocumentEnvironment{multicols}{s m o}
```

HTML class to contain everything:

```
{
    \LWR@forcenewpage
    \BlockClass{multicols}
```

Optional HTML class for the heading:

```
    \IfValueT{#3}{\begin{BlockClass}{multicolsheading}#3\end{BlockClass}}%
```

Change \linewidth to compensate for expected size:

```
    \setlength{\linewidth}{\linewidth/#2}
```

Locally force any minipages to be fullwidth:

```
    \booltrue{LWR@forceminipagefullwidth}
}
```

When done with the environment, close the :

```
{\endBlockClass}
```

Emulated null functions which are not used in HTML:

```
\newcommand*{\columnbreak}{}
\newcommand*{\RLmulticolcolumns}{}
\newcommand*{\LRmulticolcolumns}{}

\newlength{\premulticols}
\newlength{\postmulticols}
\newlength{\multicolsep}
\newlength{\multicolbaselineskip}
\newlength{\multicoltolerance}
\newlength{\multicolpretolerance}
\newcommand*{\columnseprulecolor}{\normalcolor}
\newcounter{columnbadness}
\newcounter{finalcolumnbadness}
\newcounter{collectmore}
\newcounter{unbalance}
\newlength{\multicolovershoot}
\newlength{\multicolundershoot}


\NewDocumentCommand{\docolaction}{s o m m m}{%
    \IfValueTF{#2}{#2}{#3}%
}


\end{warpHTML}
```

File 239 **lwarp-multicolrule.sty**

§ 337 Package

multicolrule

Pkg multicolrule

multicolrule is ignored.

for HTML output:

```
\RequirePackage{multicol}

\LWR@ProvidesPackageDrop{multicolrule}[2019/01/01]


\newcommand*{\SetMCRule}[1]{}
\NewDocumentCommand{\DeclareMCRulePattern}{m m}{}
```

File 240 **lwarp-multimedia.sty**

§ 338 Package

multimedia

Pkg multimedia multimedia is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

for HTML output:

```
\LWR@ProvidesPackageDrop{multimedia}[2012/05/02]

\LWR@origRequirePackage{lwarp-common-multimedia}

\LetLtxMacro\movie\LWR@multimedia
\LetLtxMacro\sound\LWR@multimedia

\newcommand{\hyperlinkmovie}[3][]{}
```

File 241 **lwarp-multirow.sty**

§ 339 Package

multirow

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg multirow multirow is emulated during HTML output, and used as-is while inside a latexmage.

vposn

- Note that recent versions of multirow include a new optional vposn argument.

multirow cells

- For multirow, insert \mrowcell into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
. . . &  \multirow{2}{.5in}{text}  & . . .
. . . &  \mrowcell                 & . . .
```

colored cells

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.

with \multicolumn

- See section 339.2 for \multicolumrow.

⚠ \multicolumn & \multirow

lwarp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

⚠ skipped cells

⚠ empty cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines, \mcolrowcell must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```
. . . &  \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}  & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
```

In a latexmage, \LWR@restoreorigformatting restores the original print-mode versions.

See section 72.25 for the print-mode versions.

for HTML output: Remove the placeholder macro which was used if multirow was not loaded:

```
\LetLtxMacro\multirow\relax
\LWR@ProvidesPackagePass{multirow}[2018/08/03]
```

\LWR@multirowborder Set to `left` or `right` to create a thick border for the cell, for use by bigdelim:

```
\newcommand{\LWR@multirowborder}{}
```

§ 339.1 Multirow

\multirow [⟨*vpos*⟩] {⟨*numrows*⟩} [⟨*bigstruts*⟩] {⟨*width*⟩} [⟨*fixup*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@multirow}{O{c} m o m o +m}%
{%
\LWR@traceinfo{*** LWR@HTML@multirow #1 #2 #4}%

\booltrue{LWR@usedmultirow}%

\LWR@maybenewtablerow%
\LWR@tabularleftedge%
```

Print the start of a new table data cell:

```
\LWR@htmltag{td rowspan="#2" %
```

The vertical alignment, if given:

```
\IfValueT{#1}{%
\ifstrequal{#1}{b}{style="\LWR@print@mbox{vertical-align:bottom}" }{}%
\ifstrequal{#1}{t}{style="\LWR@print@mbox{vertical-align:top}" }{}%
}%
```

The left/right border, if given:

```
\ifdefvoid{\LWR@multirowborder}{}{%
style="\LWR@print@mbox{border-\LWR@multirowborder:} 2px dotted black ; %
\LWR@print@mbox{padding-\LWR@multirowborder:} 2px" %
}%
```

A class adds the column spec and the rule:

```
class="td%
```

Append this column's spec:

```
\LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add the vertical bar class.

```
\LWR@addcmidruletrim%
\LWR@addleftmostbartag%
\LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
"%
```

```
\LWR@tdstartstyles%
\LWR@addcmidrulewidth%
\LWR@addcdashline%
\LWR@addtabularrulecolors%
\LWR@tdendstyles%
}%
```

The column's < spec:

```
\LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
```

While printing the text, redefine \\ to generate a new line

```
\begingroup\LetLtxMacro{\\}{\LWR@endofline}#6\endgroup%
\LWR@stoppars%
\global\boolfalse{LWR@intabularmetadata}%
\renewcommand{\LWR@multirowborder}{}%
\LWR@traceinfo{*** LWR@HTML@multirow done}%
}%

\LWR@formatted{multirow}
```

§ 339.2 Combined multicolumn and multirow

\multicolumnrow {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

\@ifpackageloaded{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The HTML version follows.

\AtBeginDocument because the print version had to see if multirow was loaded before determining how to define \LWR@print@multicolumnrow.

```
\AtBeginDocument{

\NewExpandableDocumentCommand{\LWR@HTML@multicolumnrow}{m m O{} m O{} m O{} +m}{%

\booltrue{LWR@usedmultirow}%
```

Figure out how many extra HTML columns to add for @ and ! columns:

```
\LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn/multirow tag:

```
\begingroup%
\LetLtxMacro{\\}{\LWR@endofline}%
\LWR@domulticolumn[#3][#4]{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#8}%
\endgroup%
```

Move to the next LaTeX column:

```
\addtocounter{LWR@tableLaTeXcolindex}{#1}%
\addtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing `@` or `!` columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}

\LWR@expandableformatted{multicolumnrow}

}% \AtBeginDocument
```

File 242 **lwarp-multitoc.sty**

§ 340 Package multitoc

Pkg multitoc multitoc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{multitoc}[1999/06/08]

\newcommand{\multicolumntoc}{2}
\newcommand{\multicolumnlot}{2}
\newcommand{\multicolumnlof}{2}
\newcommand*{\immediateaddtocontents}[2]{}
```

File 243 **lwarp-musicography.sty**

§ 341 Package musicography

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg musicography musicography is patched for use by lwarp.

Images are used for the meter symbols and fingered bass, since the HTML fonts tend not to be the correct size and HTML cannot stack items. The HTML `alt` tag copies `C` and `3/2`, etc. Hashes are used for the meter images, which are then reused as necessary.

⚠ Note that browser support for musical symbols may be buggy. ALT text and copy/paste into a text editor work well.

for HTML output:

```
\LWR@ProvidesPackagePass{musicography}[2019/05/28]

\NewDocumentCommand{\LWR@HTML@musSymbol}{ O{\musFont} m m m m }{%
\begin{lateximage}%
{#1\kern#2\raisebox{#3}{#5}\kern#4}%
\end{lateximage}%
}

\LWR@formatted{musSymbol}
```

```
9
10 \NewDocumentCommand{\LWR@HTML@musStemmedNote}{ m }{%
11 \begin{lateximage}%
12 \musSymbol{0.05em}{0.5ex}{0.2em}{#1\musStem}%
13 \end{lateximage}%
14 }
15
16 \LWR@formatted{musStemmedNote}
17
18 \NewDocumentCommand{\LWR@HTML@musFlaggedNote}{ m m }{%
19 \begin{lateximage}%
20 \musSymbol{0.05em}{0.5ex}{0pt}{#1\musStem}%
21 \musSymbol{0pt}{0pt}{0.9em}{#2}%
22 \end{lateximage}%
23 }
24
25 \LWR@formatted{musFlaggedNote}
26
27 \NewDocumentCommand{\LWR@HTML@musDottedNote}{ m }{%
28 \begin{lateximage}%
29 #1\musDot%
30 \end{lateximage}%
31 }
32
33 \LWR@formatted{musDottedNote}
34
35 \NewDocumentCommand{\LWR@HTML@musMeter}{ m m }{%
36 \begin{lateximage}*[#1/#2][#1#2]*%
37 \musStack{#1 #2}\kern0.05em%
38 \end{lateximage}%
39 }
40
41 \LWR@formatted{musMeter}
42
43 \NewDocumentCommand{\LWR@HTML@meterCplus}{ m }{%
44 \begin{lateximage}*[C#1]*%
45     \meterC{}\kern-0.7pt#1%
46 \end{lateximage}%
47 }
48
49 \LWR@formatted{meterCplus}
50
51 \NewDocumentCommand{\LWR@HTML@meterC}{}{%
52 \begin{lateximage}*[C]*%
53 \musSymbolMeter{\symbol{83}}%
54 \end{lateximage}%
55 }
56
57 \LWR@formatted{meterC}
58
59 \NewDocumentCommand{\LWR@HTML@meterCutC}{}{%
60 \begin{lateximage}*[C|]*%
61 \musSymbolMeter{\symbol{82}}%
62 \end{lateximage}%
63 }
```

```
64
65 \LWR@formatted{meterCutC}
66
67 \NewDocumentCommand{\LWR@HTML@meterCThreeTwo}{}{%
68 \begin{lateximage}*[C3/2]*%
69 \meterCplus{\musStack{3 2}}%
70 \end{lateximage}%
71 }
72
73 \LWR@formatted{meterCThreeTwo}
74
75 \NewDocumentCommand{\LWR@HTML@meterO}{}{\HTMLunicode{25EF}}
76
77 \LWR@formatted{meterO}
78
79 \newcommand{\LWR@null@noFig}[1][]{}%
80
81 \NewDocumentCommand{\LWR@HTML@musFig}{ m }{%
82 \begin{lateximage}*[%
83     {% ALT text for copy/paste
84         \LetLtxMacro\noFig\LWR@null@noFig%
85         \LetLtxMacro\musSharp\LWR@HTML@musSharp%
86         \LetLtxMacro\musDoubleSharp\LWR@HTML@musDoubleSharp%
87         \LetLtxMacro\musFlat\LWR@HTML@musFlat%
88         \LetLtxMacro\musDoubleFlat\LWR@HTML@musDoubleFlat%
89         \LetLtxMacro\musNatural\LWR@HTML@musNatural%
90         {#1}% braces here because \noFig uses []
91     }%
92 ]*%
93     \musStack[\musFigFont]{#1}%
94 \end{lateximage}%
95 }
96
97 \LWR@formatted{musFig}
98
99 \NewDocumentCommand{\LWR@HTML@musFlat}       {}{\HTMLunicode{266D}}
100 \NewDocumentCommand{\LWR@HTML@musDoubleFlat} {}{\HTMLunicode{1D12B}}
101 \NewDocumentCommand{\LWR@HTML@musSharp}      {}{\HTMLunicode{266F}}
102 \NewDocumentCommand{\LWR@HTML@musDoubleSharp}{}{\HTMLunicode{1D12A}}
103 \NewDocumentCommand{\LWR@HTML@musNatural}    {}{\HTMLunicode{266E}}
104
105 \LWR@formatted{musFlat}
106 \LWR@formatted{musDoubleFlat}
107 \LWR@formatted{musSharp}
108 \LWR@formatted{musDoubleSharp}
109 \LWR@formatted{musNatural}
110
111 \NewDocumentCommand{\LWR@HTML@musWhole}         {}{\HTMLunicode{1D15D}}
112 \NewDocumentCommand{\LWR@HTML@musHalf}          {}{\HTMLunicode{1D15E}}
113 \NewDocumentCommand{\LWR@HTML@musQuarter}       {}{\HTMLunicode{1D15F}}
114 \NewDocumentCommand{\LWR@HTML@musEighth}        {}{\HTMLunicode{1D160}}
115 \NewDocumentCommand{\LWR@HTML@musSixteenth}     {}{\HTMLunicode{1D161}}
116 \NewDocumentCommand{\LWR@HTML@musThirtySecond}  {}{\HTMLunicode{1D162}}
117 \NewDocumentCommand{\LWR@HTML@musSixtyFourth}   {}{\HTMLunicode{1D163}}
118
```

```
\LWR@formatted{musWhole}
\LWR@formatted{musHalf}
\LWR@formatted{musQuarter}
\LWR@formatted{musEighth}
\LWR@formatted{musSixteenth}
\LWR@formatted{musThirtySecond}
\LWR@formatted{musSixtyFourth}

\NewDocumentCommand{\LWR@HTML@musWholeDotted}{}
    {\HTMLunicode{1D15D}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musHalfDotted}{}
    {\HTMLunicode{1D15E}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musQuarterDotted}{}
    {\HTMLunicode{1D15F}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musEighthDotted}{}
    {\HTMLunicode{1D160}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musSixteenthDotted}{}
    {\HTMLunicode{1D161}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musThirtySecondDotted}{}
    {\HTMLunicode{1D162}\HTMLunicode{1D16D}}
\NewDocumentCommand{\LWR@HTML@musSixtyFourthDotted}{}
    {\HTMLunicode{1D163}\HTMLunicode{1D16D}}

\LWR@formatted{musWholeDotted}
\LWR@formatted{musHalfDotted}
\LWR@formatted{musQuarterDotted}
\LWR@formatted{musEighthDotted}
\LWR@formatted{musSixteenthDotted}
\LWR@formatted{musThirtySecondDotted}
\LWR@formatted{musSixtyFourthDotted}
```

File 244 **lwarp-nameauth.sty**

§ 342 Package nameauth

(*Emulates or patches code by* Charles P. Schaum.)

Pkg nameauth nameauth is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nameauth}[2017/03/22]
```

lwarp formatting is inserted in the following.

```
\renewcommand*\@nameauth@Hook[1]
{%
  \if@nameauth@Lock
    \@nameauth@InHooktrue%
    \protected@edef\test{#1}%
    \expandafter\@nameauth@TestDot\expandafter{\test}%
    \if@nameauth@InAKA
      \if@nameauth@AlwaysFormat
        \@nameauth@FirstFormattrue%
      \else
```

```
      \unless\if@nameauth@AKAFormat
      \@nameauth@FirstFormatfalse\fi
    \fi
    \if@nameauth@MainFormat
      \if@nameauth@FirstFormat
        \bgroup\NamesFormat{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \else
        \bgroup\MainNameHook{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \fi
    \else
      \if@nameauth@FirstFormat
        \bgroup\FrontNamesFormat{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \else
        \bgroup\FrontNameHook{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \fi
    \fi
  \else
    \if@nameauth@AlwaysFormat
      \@nameauth@FirstFormattrue%
    \fi
    \if@nameauth@MainFormat
      \if@nameauth@FirstFormat
        \bgroup\NamesFormat{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \else
        \bgroup\MainNameHook{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \fi
    \else
      \if@nameauth@FirstFormat
        \bgroup\FrontNamesFormat{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \else
        \bgroup\FrontNameHook{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \fi
    \fi
  \fi
  \@nameauth@FirstFormatfalse%
  \@nameauth@InHookfalse%
\fi
}
```

File 245 **lwarp-nameref.sty**

§ 343 Package
# nameref

Pkg nameref nameref is emulated by lwarp.

for HTML output: Discard all options for lwarp-nameref:

```
\PackageInfo{lwarp}{%
Using the lwarp HTML version of package ‘nameref’,\MessageBreak
and discarding options.\MessageBreak
(Not using \protect\ProvidesPackage, so that other packages\MessageBreak
do not attempt to patch lwarp’s version of ‘nameref’.)\MessageBreak
}
\DeclareOption*{}
\ProcessOptions\relax
```

File 246 **lwarp-natbib.sty**

§ 344 Package
# natbib

(*Emulates or patches code by* Patrick W. Daly.)

Pkg natbib natbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{natbib}[2010/09/13]
```

Replace math < and > with \textless and \textgreater:

A macro to compare:

```
\newcommand{\LWRNB@NAT@open}{$<$}
```

To patch \NAT@open and \NAT@close

```
\newcommand{\LWRNB@patchnatbibopenclose}{
\ifdefstrequal{\NAT@open}{\LWRNB@NAT@open}
{
    \renewcommand{\NAT@open}{\textless}
    \renewcommand{\NAT@close}{\textgreater}
}{}
}
```

Do it now in case angle was selected as an option:

```
\LWRNB@patchnatbibopenclose
```

Also patch \setcitestyle to patch after settings are made:

```
\let\LWRNB@origsetcitestyle\setcitestyle

\renewcommand{\setcitestyle}[1]{%
\LWRNB@origsetcitestyle{#1}%
\LWRNB@patchnatbibopenclose%
}
```

File 247 **lwarp-nccfancyhdr.sty**

§ 345 Package nccfancyhdr

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg nccfancyhdr nccfancyhdr is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nccfancyhdr}[2004/12/07]

\newcommand*{\headrulewidth}{}
\newcommand*{\footrulewidth}{}
\newcommand{\headstrutheight}{}
\newcommand{\footstrutheight}{}
\newcommand*{\headrule}{}
\newcommand*{\footrule}{}

\newdimen\headwidth
\newcommand*{\extendedheaders}{}
\newcommand*{\normalheaders}{}

\newcommand*{\fancyhead}[2][]{}
\newcommand*{\fancyfoot}[2][]{}
\newcommand*{\fancyhf}[2][]{}
\newcommand*{\fancypagestyle}[2]{}
\newcommand*{\lhead}[2][]{}
\newcommand*{\chead}[2][]{}
\newcommand*{\rhead}[2][]{}
\newcommand*{\lfoot}[2][]{}
\newcommand*{\cfoot}[2][]{}
\newcommand*{\rfoot}[2][]{}

\newcommand{\nouppercase}[1]{#1}

\NewDocumentCommand{\fancycenter}{o o m m m}{}

\NewDocumentCommand{\newpagestyle}{m o m}{}

\newcommand*{\iffloatpage}[2]{#2}
\newcommand*{\ifftopfloat}[2]{#2}
\newcommand*{\iffbotfloat}[2]{#2}
```

File 248 **lwarp-needspace.sty**

§ 346 Package needspace

(*Emulates or patches code by* Peter Wilson.)

Pkg needspace needspace is ignored.

for HTML output: Discard all options for lwarp-needspace:

```
\LWR@ProvidesPackageDrop{needspace}[2010/09/12]

\DeclareDocumentCommand{\needspace}{m}{}
\DeclareDocumentCommand{\Needspace}{s m}{}
```

File 249 **lwarp-nextpage.sty**

§ 347 Package nextpage

(*Emulates or patches code by* Peter Wilson.)

Pkg nextpage nextpage is ignored.

for HTML output: Discard all options for lwarp-nextpage.

```
\LWR@ProvidesPackageDrop{nextpage}[2009/09/03]

\DeclareDocumentCommand{\cleartoevenpage}{o}{}
\DeclareDocumentCommand{\movetoevenpage}{o}{}
\DeclareDocumentCommand{\cleartooddpage}{o}{}
\DeclareDocumentCommand{\movetooddpage}{o}{}
```

File 250 **lwarp-nfssext-cfr.sty**

§ 348 Package nfssext-cfr

(*Emulates or patches code by* Clea F. Rees.)

Pkg nfssext-cfr nfssext-cfr is emulated in HTML, and used as-is in print output.

Results depend on the browser's font.

for HTML output:

```
\LWR@ProvidesPackagePass{nfssext-cfr}[2017/03/28]
```

Macros which are present in the lwarp core are commented out here.

```
\newrobustcmd{\LWR@HTML@lnstyle}{}
\newrobustcmd{\LWR@HTML@osstyle}{}
\newrobustcmd{\LWR@HTML@instyle}{}
\newrobustcmd{\LWR@HTML@sustyle}{}
\newrobustcmd{\LWR@HTML@swstyle}{}
\newrobustcmd{\LWR@HTML@pstyle}{}
\newrobustcmd{\LWR@HTML@tistyle}{}
\newrobustcmd{\LWR@HTML@ostyle}{\LWR@HTML@scshape}
\newrobustcmd{\LWR@HTML@postyle}{\LWR@HTML@scshape}
\newrobustcmd{\LWR@HTML@ltstyle}{}
\newrobustcmd{\LWR@HTML@ofstyle}{}
\newrobustcmd{\LWR@HTML@altstyle}{}
\newrobustcmd{\LWR@HTML@regstyle}{}
\newrobustcmd{\LWR@HTML@embossstyle}{}
\newrobustcmd{\LWR@HTML@ornamentalstyle}{}
\newrobustcmd{\LWR@HTML@qtstyle}{}
\newrobustcmd{\LWR@HTML@shstyle}{}
\newrobustcmd{\LWR@HTML@swashstyle}{}
\newrobustcmd{\LWR@HTML@tmstyle}{}
\newrobustcmd{\LWR@HTML@tvstyle}{\renewcommand*{\LWR@f@family}{tt}}
\newrobustcmd{\LWR@HTML@tstyle}{}
\newrobustcmd{\LWR@HTML@lstyle}{}
\newrobustcmd{\LWR@HTML@tlstyle}{}
\newrobustcmd{\LWR@HTML@plstyle}{}
\newrobustcmd{\LWR@HTML@tostyle}{\LWR@HTML@scshape}
% \newrobustcmd{\LWR@HTML@sishape}{}
\newrobustcmd{\LWR@HTML@olshape}{}
\newrobustcmd{\LWR@HTML@scolshape}{}
\newrobustcmd{\LWR@HTML@ushape}{}
\newrobustcmd{\LWR@HTML@scushape}{}
\newrobustcmd{\LWR@HTML@uishape}{\LWR@HTML@itshape}
\newrobustcmd{\LWR@HTML@rishape}{}
\newrobustcmd{\LWR@HTML@regwidth}{}
\newrobustcmd{\LWR@HTML@nwwidth}{}
\newrobustcmd{\LWR@HTML@cdwidth}{}
\newrobustcmd{\LWR@HTML@ecwidth}{}
\newrobustcmd{\LWR@HTML@ucwidth}{}
\newrobustcmd{\LWR@HTML@etwidth}{}
\newrobustcmd{\LWR@HTML@epwidth}{}
\newrobustcmd{\LWR@HTML@exwidth}{}
\newrobustcmd{\LWR@HTML@uxwidth}{}
\newrobustcmd{\LWR@HTML@mbweight}{\renewcommand*{\LWR@f@series}{md}}
\newrobustcmd{\LWR@HTML@dbweight}{\renewcommand*{\LWR@f@series}{bf}}
\newrobustcmd{\LWR@HTML@sbweight}{\renewcommand*{\LWR@f@series}{bf}}
% \newrobustcmd{\LWR@HTML@ebweight}{\renewcommand*{\LWR@f@series}{eb}}
\newrobustcmd{\LWR@HTML@ubweight}{\renewcommand*{\LWR@f@series}{eb}}
% \newrobustcmd{\LWR@HTML@lgweight}{\renewcommand*{\LWR@f@series}{lg}}
\newrobustcmd{\LWR@HTML@elweight}{\renewcommand*{\LWR@f@series}{lg}}
\newrobustcmd{\LWR@HTML@ulweight}{\renewcommand*{\LWR@f@series}{lg}}
% \newrobustcmd{\LWR@HTML@itshape}{}
% \newrobustcmd{\LWR@HTML@scshape}{}
% \newrobustcmd{\LWR@HTML@upshape}{}
\newrobustcmd{\LWR@HTML@dfshape}{}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
```

```
    \newrobustcmd{\LWR@HTML@swshape}{}
}

\newrobustcmd{\LWR@HTML@ornament}[1]{}

\LWR@formatted{lnstyle}
\LWR@formatted{osstyle}
\LWR@formatted{instyle}
\LWR@formatted{sustyle}
\LWR@formatted{swstyle}
\LWR@formatted{pstyle}
\LWR@formatted{tistyle}
\LWR@formatted{ostyle}
\LWR@formatted{postyle}
\LWR@formatted{ltstyle}
\LWR@formatted{ofstyle}
\LWR@formatted{altstyle}
\LWR@formatted{regstyle}
\LWR@formatted{embossstyle}
\LWR@formatted{ornamentalstyle}
\LWR@formatted{qtstyle}
\LWR@formatted{shstyle}
\LWR@formatted{swashstyle}
\LWR@formatted{tmstyle}
\LWR@formatted{tvstyle}
\LWR@formatted{tstyle}
\LWR@formatted{lstyle}
\LWR@formatted{tlstyle}
\LWR@formatted{plstyle}
\LWR@formatted{tostyle}
% \LWR@formatted{sishape}
\LWR@formatted{olshape}
\LWR@formatted{scolshape}
\LWR@formatted{ushape}
\LWR@formatted{scushape}
\LWR@formatted{uishape}
\LWR@formatted{rishape}
\LWR@formatted{regwidth}
\LWR@formatted{nwwidth}
\LWR@formatted{cdwidth}
\LWR@formatted{ecwidth}
\LWR@formatted{ucwidth}
\LWR@formatted{etwidth}
\LWR@formatted{epwidth}
\LWR@formatted{exwidth}
\LWR@formatted{uxwidth}
\LWR@formatted{mbweight}
\LWR@formatted{dbweight}
\LWR@formatted{sbweight}
% \LWR@formatted{ebweight}
\LWR@formatted{ubweight}
% \LWR@formatted{lgweight}
\LWR@formatted{elweight}
\LWR@formatted{ulweight}
% \LWR@formatted{itshape}
```

```
% \LWR@formatted{scshape}
% \LWR@formatted{upshape}
\LWR@formatted{dfshape}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \LWR@formatted{swshape}
}

\LWR@formatted{ornament}


\newcommand{\LWR@null@lnstyle}{}
\newcommand{\LWR@null@osstyle}{}
\newcommand{\LWR@null@instyle}{}
\newcommand{\LWR@null@sustyle}{}
\newcommand{\LWR@null@swstyle}{}
\newcommand{\LWR@null@pstyle}{}
\newcommand{\LWR@null@tistyle}{}
\newcommand{\LWR@null@ostyle}{}
\newcommand{\LWR@null@postyle}{}
\newcommand{\LWR@null@ltstyle}{}
\newcommand{\LWR@null@ofstyle}{}
\newcommand{\LWR@null@altstyle}{}
\newcommand{\LWR@null@regstyle}{}
\newcommand{\LWR@null@embossstyle}{}
\newcommand{\LWR@null@ornamentalstyle}{}
\newcommand{\LWR@null@qtstyle}{}
\newcommand{\LWR@null@shstyle}{}
\newcommand{\LWR@null@swashstyle}{}
\newcommand{\LWR@null@tmstyle}{}
\newcommand{\LWR@null@tvstyle}{}
\newcommand{\LWR@null@tstyle}{}
\newcommand{\LWR@null@lstyle}{}
\newcommand{\LWR@null@tlstyle}{}
\newcommand{\LWR@null@plstyle}{}
\newcommand{\LWR@null@tostyle}{}
% \newcommand{\LWR@null@sishape}{}
\newcommand{\LWR@null@olshape}{}
\newcommand{\LWR@null@scolshape}{}
\newcommand{\LWR@null@ushape}{}
\newcommand{\LWR@null@scushape}{}
\newcommand{\LWR@null@uishape}{}
\newcommand{\LWR@null@rishape}{}
\newcommand{\LWR@null@regwidth}{}
\newcommand{\LWR@null@nwwidth}{}
\newcommand{\LWR@null@cdwidth}{}
\newcommand{\LWR@null@ecwidth}{}
\newcommand{\LWR@null@ucwidth}{}
\newcommand{\LWR@null@etwidth}{}
\newcommand{\LWR@null@epwidth}{}
\newcommand{\LWR@null@exwidth}{}
\newcommand{\LWR@null@uxwidth}{}
\newcommand{\LWR@null@mbweight}{}
\newcommand{\LWR@null@dbweight}{}
\newcommand{\LWR@null@sbweight}{}
```

```
% \newcommand{\LWR@null@ebweight}{}
\newcommand{\LWR@null@ubweight}{}
% \newcommand{\LWR@null@lgweight}{}
\newcommand{\LWR@null@elweight}{}
\newcommand{\LWR@null@ulweight}{}
% \newcommand{\LWR@null@itshape}{}
% \newcommand{\LWR@null@scshape}{}
% \newcommand{\LWR@null@upshape}{}
\newcommand{\LWR@null@dfshape}{}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \newcommand{\LWR@null@swshape}{}
}

\newcommand{\LWR@null@ornament}[1]{}

\appto{\LWR@nullfonts}{%
\LetLtxMacro\lnstyle\LWR@null@lnstyle%
\LetLtxMacro\osstyle\LWR@null@osstyle%
\LetLtxMacro\instyle\LWR@null@instyle%
\LetLtxMacro\sustyle\LWR@null@sustyle%
\LetLtxMacro\swstyle\LWR@null@swstyle%
\LetLtxMacro\pstyle\LWR@null@pstyle%
\LetLtxMacro\tistyle\LWR@null@tistyle%
\LetLtxMacro\ostyle\LWR@null@ostyle%
\LetLtxMacro\postyle\LWR@null@postyle%
\LetLtxMacro\ltstyle\LWR@null@ltstyle%
\LetLtxMacro\ofstyle\LWR@null@ofstyle%
\LetLtxMacro\altstyle\LWR@null@altstyle%
\LetLtxMacro\regstyle\LWR@null@regstyle%
\LetLtxMacro\embossstyle\LWR@null@embossstyle%
\LetLtxMacro\ornamentalstyle\LWR@null@ornamentalstyle%
\LetLtxMacro\qtstyle\LWR@null@qtstyle%
\LetLtxMacro\shstyle\LWR@null@shstyle%
\LetLtxMacro\swashstyle\LWR@null@swashstyle%
\LetLtxMacro\tmstyle\LWR@null@tmstyle%
\LetLtxMacro\tvstyle\LWR@null@tvstyle%
\LetLtxMacro\tstyle\LWR@null@tstyle%
\LetLtxMacro\lstyle\LWR@null@lstyle%
\LetLtxMacro\tlstyle\LWR@null@tlstyle%
\LetLtxMacro\plstyle\LWR@null@plstyle%
\LetLtxMacro\tostyle\LWR@null@tostyle%
% \LetLtxMacro\sishape\LWR@null@sishape
\LetLtxMacro\olshape\LWR@null@olshape%
\LetLtxMacro\scolshape\LWR@null@scolshape%
\LetLtxMacro\ushape\LWR@null@ushape%
\LetLtxMacro\scushape\LWR@null@scushape%
\LetLtxMacro\uishape\LWR@null@uishape%
\LetLtxMacro\rishape\LWR@null@rishape%
\LetLtxMacro\regwidth\LWR@null@regwidth%
\LetLtxMacro\nwwidth\LWR@null@nwwidth%
\LetLtxMacro\cdwidth\LWR@null@cdwidth%
\LetLtxMacro\ecwidth\LWR@null@ecwidth%
\LetLtxMacro\ucwidth\LWR@null@ucwidth%
\LetLtxMacro\etwidth\LWR@null@etwidth%
```

```
\LetLtxMacro\epwidth\LWR@null@epwidth%
\LetLtxMacro\exwidth\LWR@null@exwidth%
\LetLtxMacro\uxwidth\LWR@null@uxwidth%
\LetLtxMacro\mbweight\LWR@null@mbweight%
\LetLtxMacro\dbweight\LWR@null@dbweight%
\LetLtxMacro\sbweight\LWR@null@sbweight%
% \LetLtxMacro\ebweight\LWR@null@ebweight%
\LetLtxMacro\ubweight\LWR@null@ubweight%
% \LetLtxMacro\lgweight\LWR@null@lgweight%
\LetLtxMacro\elweight\LWR@null@elweight%
\LetLtxMacro\ulweight\LWR@null@ulweight%
% \LetLtxMacro\itshape\LWR@null@itshape%
% \LetLtxMacro\scshape\LWR@null@scshape%
% \LetLtxMacro\upshape\LWR@null@upshape%
\LetLtxMacro\dfshape\LWR@null@dfshape%
\LetLtxMacro\swshape\LWR@null@swshape%
\LetLtxMacro\ornament\LWR@null@ornament%
}

\newrobustcmd{\LWR@HTML@textln}[1]{#1}
\newrobustcmd{\LWR@HTML@textos}[1]{\textsc{#1}}
\newrobustcmd{\LWR@HTML@textin}[1]{#1}
\newrobustcmd{\LWR@HTML@textsu}[1]{#1}
% \newrobustcmd{\LWR@HTML@textsi}[1]{#1}
\newrobustcmd{\LWR@HTML@textdf}[1]{#1}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \newrobustcmd{\LWR@HTML@textsw}[1]{#1}
}

\newrobustcmd{\LWR@HTML@textti}[1]{#1}
\newrobustcmd{\LWR@HTML@textlt}[1]{#1}
\newrobustcmd{\LWR@HTML@textof}[1]{#1}
\newrobustcmd{\LWR@HTML@textalt}[1]{#1}
\newrobustcmd{\LWR@HTML@textreg}[1]{#1}
\newrobustcmd{\LWR@HTML@emboss}[1]{#1}
\newrobustcmd{\LWR@HTML@textorn}[1]{#1}
\newrobustcmd{\LWR@HTML@textqt}[1]{#1}
\newrobustcmd{\LWR@HTML@textsh}[1]{#1}
\newrobustcmd{\LWR@HTML@texttm}[1]{#1}
\newrobustcmd{\LWR@HTML@texttv}[1]{\texttt{#1}}
\newrobustcmd{\LWR@HTML@textl}[1]{#1}
\newrobustcmd{\LWR@HTML@texto}[1]{#1}
\newrobustcmd{\LWR@HTML@textp}[1]{#1}
\newrobustcmd{\LWR@HTML@textt}[1]{#1}
\newrobustcmd{\LWR@HTML@textpl}[1]{#1}
\newrobustcmd{\LWR@HTML@textpo}[1]{\textsc{#1}}
\newrobustcmd{\LWR@HTML@texttl}[1]{#1}
\newrobustcmd{\LWR@HTML@textto}[1]{\textsc{#1}}
\newrobustcmd{\LWR@HTML@textol}[1]{#1}
\newrobustcmd{\LWR@HTML@textswash}[1]{#1}
\newrobustcmd{\LWR@HTML@textu}[1]{#1}
\newrobustcmd{\LWR@HTML@textscu}[1]{#1}
\newrobustcmd{\LWR@HTML@textui}[1]{\LWR@HTML@textit{#1}}
\newrobustcmd{\LWR@HTML@textri}[1]{#1}
```

```
\newrobustcmd{\LWR@HTML@textnw}[1]{#1}
\newrobustcmd{\LWR@HTML@textcd}[1]{#1}
\newrobustcmd{\LWR@HTML@textec}[1]{#1}
\newrobustcmd{\LWR@HTML@textuc}[1]{#1}
\newrobustcmd{\LWR@HTML@textet}[1]{#1}
\newrobustcmd{\LWR@HTML@textep}[1]{#1}
\newrobustcmd{\LWR@HTML@textex}[1]{#1}
\newrobustcmd{\LWR@HTML@textux}[1]{#1}
\newrobustcmd{\LWR@HTML@textrw}[1]{#1}
\newrobustcmd{\LWR@HTML@textmb}[1]{\textmd{#1}}
\newrobustcmd{\LWR@HTML@textdb}[1]{\textbf{#1}}
\newrobustcmd{\LWR@HTML@textsb}[1]{\textbf{#1}}
% \newrobustcmd{\LWR@HTML@texteb}[1]{#1}
\newrobustcmd{\LWR@HTML@textub}[1]{\texteb{#1}}
% \newrobustcmd{\LWR@HTML@textlg}[1]{#1}
\newrobustcmd{\LWR@HTML@textel}[1]{\textlg{#1}}
\newrobustcmd{\LWR@HTML@textul}[1]{\textlg{#1}}

\LWR@formatted{textln}
\LWR@formatted{textos}
\LWR@formatted{textin}
\LWR@formatted{textsu}
% \LWR@formatted{textsi}
\LWR@formatted{textdf}
\LWR@formatted{textsw}
\LWR@formatted{textti}
\LWR@formatted{textlt}
\LWR@formatted{textof}
\LWR@formatted{textalt}
\LWR@formatted{textreg}
\LWR@formatted{emboss}
\LWR@formatted{textorn}
\LWR@formatted{textqt}
\LWR@formatted{textsh}
\LWR@formatted{texttm}
\LWR@formatted{texttv}
\LWR@formatted{textl}
\LWR@formatted{texto}
\LWR@formatted{textp}
\LWR@formatted{textt}
\LWR@formatted{textpl}
\LWR@formatted{textpo}
\LWR@formatted{texttl}
\LWR@formatted{textto}
\LWR@formatted{textol}
\LWR@formatted{textswash}
\LWR@formatted{textu}
\LWR@formatted{textscu}
\LWR@formatted{textui}
\LWR@formatted{textri}
\LWR@formatted{textnw}
\LWR@formatted{textcd}
\LWR@formatted{textec}
\LWR@formatted{textuc}
\LWR@formatted{textet}
```

```
\LWR@formatted{textep}
\LWR@formatted{textex}
\LWR@formatted{textux}
\LWR@formatted{textrw}
\LWR@formatted{textmb}
\LWR@formatted{textdb}
\LWR@formatted{textsb}
% \LWR@formatted{texteb}
\LWR@formatted{textub}
% \LWR@formatted{textlg}
\LWR@formatted{textel}
\LWR@formatted{textul}

\newrobustcmd{\LWR@null@textln}[1]{#1}
\newrobustcmd{\LWR@null@textos}[1]{#1}
\newrobustcmd{\LWR@null@textin}[1]{#1}
\newrobustcmd{\LWR@null@textsu}[1]{#1}
% \newrobustcmd{\LWR@null@textsi}[1]{#1}
\newrobustcmd{\LWR@null@textdf}[1]{#1}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \newrobustcmd{\LWR@null@textsw}[1]{#1}
}

\newrobustcmd{\LWR@null@textti}[1]{#1}
\newrobustcmd{\LWR@null@textlt}[1]{#1}
\newrobustcmd{\LWR@null@textof}[1]{#1}
\newrobustcmd{\LWR@null@textalt}[1]{#1}
\newrobustcmd{\LWR@null@textreg}[1]{#1}
\newrobustcmd{\LWR@null@emboss}[1]{#1}
\newrobustcmd{\LWR@null@textorn}[1]{#1}
\newrobustcmd{\LWR@null@textqt}[1]{#1}
\newrobustcmd{\LWR@null@textsh}[1]{#1}
\newrobustcmd{\LWR@null@texttm}[1]{#1}
\newrobustcmd{\LWR@null@texttv}[1]{#1}
\newrobustcmd{\LWR@null@textl}[1]{#1}
\newrobustcmd{\LWR@null@texto}[1]{#1}
\newrobustcmd{\LWR@null@textp}[1]{#1}
\newrobustcmd{\LWR@null@textt}[1]{#1}
\newrobustcmd{\LWR@null@textpl}[1]{#1}
\newrobustcmd{\LWR@null@textpo}[1]{#1}
\newrobustcmd{\LWR@null@texttl}[1]{#1}
\newrobustcmd{\LWR@null@textto}[1]{#1}
\newrobustcmd{\LWR@null@textol}[1]{#1}
\newrobustcmd{\LWR@null@textswash}[1]{#1}
\newrobustcmd{\LWR@null@textu}[1]{#1}
\newrobustcmd{\LWR@null@textscu}[1]{#1}
\newrobustcmd{\LWR@null@textui}[1]{#1}
\newrobustcmd{\LWR@null@textri}[1]{#1}
\newrobustcmd{\LWR@null@textnw}[1]{#1}
\newrobustcmd{\LWR@null@textcd}[1]{#1}
\newrobustcmd{\LWR@null@textec}[1]{#1}
\newrobustcmd{\LWR@null@textuc}[1]{#1}
\newrobustcmd{\LWR@null@textet}[1]{#1}
\newrobustcmd{\LWR@null@textep}[1]{#1}
```

```
\newrobustcmd{\LWR@null@textex}[1]{#1}
\newrobustcmd{\LWR@null@textux}[1]{#1}
\newrobustcmd{\LWR@null@textrw}[1]{#1}
\newrobustcmd{\LWR@null@textmb}[1]{#1}
\newrobustcmd{\LWR@null@textdb}[1]{#1}
\newrobustcmd{\LWR@null@textsb}[1]{#1}
% \newrobustcmd{\LWR@null@texteb}[1]{#1}
\newrobustcmd{\LWR@null@textub}[1]{#1}
% \newrobustcmd{\LWR@null@textlg}[1]{#1}
\newrobustcmd{\LWR@null@textel}[1]{#1}
\newrobustcmd{\LWR@null@textul}[1]{#1}

\appto{\LWR@nullfonts}{%
\LetLtxMacro\textln\LWR@null@textln%
\LetLtxMacro\textos\LWR@null@textos%
\LetLtxMacro\textin\LWR@null@textin%
\LetLtxMacro\textsu\LWR@null@textsu%
% \LetLtxMacro\textsi\LWR@null@textsi%
\LetLtxMacro\textdf\LWR@null@textdf%
\LetLtxMacro\textsw\LWR@null@textsw%
\LetLtxMacro\textti\LWR@null@textti%
\LetLtxMacro\textlt\LWR@null@textlt%
\LetLtxMacro\textof\LWR@null@textof%
\LetLtxMacro\textalt\LWR@null@textalt%
\LetLtxMacro\textreg\LWR@null@textreg%
\LetLtxMacro\emboss\LWR@null@emboss%
\LetLtxMacro\textorn\LWR@null@textorn%
\LetLtxMacro\textqt\LWR@null@textqt%
\LetLtxMacro\textsh\LWR@null@textsh%
\LetLtxMacro\texttm\LWR@null@texttm%
\LetLtxMacro\texttv\LWR@null@texttv%
\LetLtxMacro\textl\LWR@null@textl%
\LetLtxMacro\texto\LWR@null@texto%
\LetLtxMacro\textp\LWR@null@textp%
\LetLtxMacro\textt\LWR@null@textt%
\LetLtxMacro\textpl\LWR@null@textpl%
\LetLtxMacro\textpo\LWR@null@textpo%
\LetLtxMacro\texttl\LWR@null@texttl%
\LetLtxMacro\textto\LWR@null@textto%
\LetLtxMacro\textol\LWR@null@textol%
\LetLtxMacro\textswash\LWR@null@textswash%
\LetLtxMacro\textu\LWR@null@textu%
\LetLtxMacro\textscu\LWR@null@textscu%
\LetLtxMacro\textui\LWR@null@textui%
\LetLtxMacro\textri\LWR@null@textri%
\LetLtxMacro\textnw\LWR@null@textnw%
\LetLtxMacro\textcd\LWR@null@textcd%
\LetLtxMacro\textec\LWR@null@textec%
\LetLtxMacro\textuc\LWR@null@textuc%
\LetLtxMacro\textet\LWR@null@textet%
\LetLtxMacro\textep\LWR@null@textep%
\LetLtxMacro\textex\LWR@null@textex%
\LetLtxMacro\textux\LWR@null@textux%
\LetLtxMacro\textrw\LWR@null@textrw%
\LetLtxMacro\textmb\LWR@null@textmb%
```

```
\LetLtxMacro\textdb\LWR@null@textdb%
\LetLtxMacro\textsb\LWR@null@textsb%
% \LetLtxMacro\texteb\LWR@null@texteb%
\LetLtxMacro\textub\LWR@null@textub%
% \LetLtxMacro\textlg\LWR@null@textlg%
\LetLtxMacro\textel\LWR@null@textel%
\LetLtxMacro\textul\LWR@null@textul%
}

\providecommand*{\zeroslash}{0}
\newrobustcmd*{\LWR@HTML@zeroslash}{0}
\LWR@formatted{zeroslash}
```

File 251 **lwarp-nicefrac.sty**

§ 349 Package nicefrac

(*Emulates or patches code by* Axel Reichert.)

Pkg nicefrac nicefrac is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nicefrac}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@@UnitsNiceFrac}[3][]{%
    {% localize font selection
        #1{%
            \LWR@textcurrentfont{%
                \InlineClass{numerator}{#2}%
                /%
                \InlineClass{denominator}{#3}%
            }%
        }%
    }%
}

\LWR@formatted{@UnitsNiceFrac}

\DeclareRobustCommand*{\LWR@HTML@@UnitsUglyFrac}[3][]{%
    {% localize font selection
        #1{\LWR@textcurrentfont{#2/#3}}%
    }%
}

\LWR@formatted{@UnitsUglyFrac}
```

For Mathjax:

```
\CustomizeMathJax{\newcommand{\nicefrac}[3][]{#2/#3}}
```

File 252 **lwarp-niceframe.sty**

§ 350 Package niceframe

Pkg niceframe niceframe is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{niceframe}% the original date is in yyyy/dd/mm format

\newcommand{\LWR@niceframe}[3]{
    \setlength{\LWR@templengthone}{#1}
    \begin{BlockClass}[max-width:\LWR@printlength{\LWR@templengthone}]{#3}
    #2
    \end{BlockClass}
}

\newcommand{\niceframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{niceframe}}
\newcommand{\curlyframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{curlyframe}}
\newcommand{\artdecoframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{artdecoframe}}

\newcommand{\generalframe}[9]{\LWR@niceframe{\textwidth}{#9}{generalframe}}
```

File 253 **lwarp-nomencl.sty**

§ 351 Package nomencl

(*Emulates or patches code by* Boris Veytsman, Bernd Schandl, Lee Netherton, CV Radhakrishnan.)

Pkg nomencl nomencl is patched for use by lwarp.

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

for HTML output:

```
\LWR@ProvidesPackagePass{nomencl}[2005/09/22]
```

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\def\@@@nomenclature[#1]#2#3{%
 \def\@tempa{#2}\def\@tempb{#3}%
 \protected@write\@nomenclaturefile{}%
  {\string\nomenclatureentry{#1\nom@verb\@tempa @[{\nom@verb\@tempa}]%
      \begingroup\nom@verb\@tempb\protect\nomeqref{\theequation}%
        |nompageref}{\theLWR@previousautopagelabel}}%   lwarp
 \endgroup
 \@esphack}

\renewcommand*{\pagedeclaration}[1]{, \nameref{\BaseJobname-autopage-#1}}%
```

File 254 **lwarp-nonfloat.sty**

§ 352 Package nonfloat

(*Emulates or patches code by* Kai Rascher.)

Pkg nonfloat nonfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonfloat}[1999/07/05]

\LetLtxMacro\topcaption\caption
\newcommand{\figcaption}{\def\@captype{figure}\caption}
\newcommand{\tabcaption}{\def\@captype{table}\topcaption}
\newenvironment{narrow}[2]{}{}
```

File 255 **lwarp-nonumonpart.sty**

§ 353 Package nonumonpart

Pkg nonumonpart nonumonpart is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonumonpart}[2011/04/15]
```

File 256 **lwarp-nopageno.sty**

§ 354 Package nopageno

Pkg nopageno nopageno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nopageno}[1989/01/01]
```

File 257 **lwarp-notes.sty**

§ 355 Package notes

Pkg notes notes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{notes}[2002/10/29]

\newcommand*{\LWR@notes@onenote}[2]{%
\newenvironment{#1}
    {
```

```
        \BlockClass{notes#1}
        \begin{BlockClass}{notesicon}\textcircled{~#2~}\end{BlockClass}
        \BlockClass{notescontents}
    }
    {\endBlockClass\endBlockClass}
}

\LWR@notes@onenote{importantnote}{!}

\LWR@notes@onenote{warningnote}{--}

\LWR@notes@onenote{informationnote}{i}
```

File 258 **lwarp-notespages.sty**

§ 356 Package notespages

Pkg notespages notespages is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{notespages}[2016/08/21]

\newcommand*{\npnotesname}{}
\newcommand*{\npnotestext}{}
\newcommand*{\remainingtextheight}{}
\newdimen\remainingtextheight
\newcommand*{\notestitletext}{}
\newcommand*{\notesareatext}{}
\newcommand*{\npnpinfo}[1]{}
\newcommand*{\tracingnpmarks}{}
\newcommand*{\notespage}[1][]{}
\newcommand*{\notespages}[1][]{}
\newcommand*{\notesfill}[1][]{}
\newcommand*{\setnotespages}[1]{}
\newcommand*{\definenotesoption}[2]{}
\newcommand{\definenotesstyle}[2]{}
\newcommand{\definetitlestyle}[2]{}
\newcommand{\nppatchchapter}[1]{}
\newcommand{\npunpatchchapter}{}
```

File 259 **lwarp-nowidow.sty**

§ 357 Package nowidow

(*Emulates or patches code by* Raphaël Pinson.)

Pkg nowidow nowidow is ignored.

Discard all options for lwarp-nowidow:

for HTML output:

```
\LWR@ProvidesPackageDrop{nowidow}[2011/09/20]
```

\nowidow [⟨*lines*⟩]
\setnowidow [⟨*lines*⟩]

```
\newcommand*{\nowidow}[1][]{}
\newcommand*{\setnowidow}[1][]{}
```

\noclub [⟨*lines*⟩]
\setnoclub [⟨*lines*⟩]

```
\newcommand*{\noclub}[1][]{}
\newcommand*{\setnoclub}[1][]{}
```

File 260 **lwarp-ntheorem.sty**

§ 358 Package ntheorem

(*Emulates or patches code by* Wolfgang May, Andreas Schedler.)

Pkg ntheorem ntheorem is patched for use by lwarp.

Table 15: Ntheorem package — css styling of theorems and proofs

Theorem: of class theorembody<theoremstyle>

Theorem Header: of class theoremheader<style>

where <theoremstyle> is plain, break, etc.

§ 358.1 Limitations

⚠ Font control This conversion is not total. Font control is via css, and the custom LaTeX font settings are ignored.

⚠ Equation numbering ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environmentswhen the option thref is used. lwarp does not share this bug, so equations with \split, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's thref option.

§ 358.2 Options

Options amsthm or standard choose which set of theorems and proofs to initialize.

⚠ Disabled options The options thmmarks and amsmath are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option thref is disabled because cleveref functions are used instead. \thref is emulated.

Option hyperref is disabled because lwarp emulated hyperref.

for HTML output: Some disabled options:

```
\DeclareOption{thref}{}


\newbool{LWR@ntheoremmarks}
\boolfalse{LWR@ntheoremmarks}

\DeclareOption{thmmarks}{
\booltrue{LWR@ntheoremmarks}
\newif\ifsetendmark\setendmarktrue
}


\newbool{LWR@ntheoremamsthm}
\boolfalse{LWR@ntheoremamsthm}

\DeclareOption{amsthm}{\booltrue{LWR@ntheoremamsthm}}


\DeclareOption{amsmath}{}
\DeclareOption{hyperref}{}

\LWR@ProvidesPackagePass{ntheorem}[2011/08/15]
```

§ 358.3 Remembering the theorem style

Storage for the style being used for new theorems.

```
\newcommand{\LWR@newtheoremstyle}{plain}


\AtBeginDocument{
\@ifpackageloaded{cleveref}{
\gdef\@thm#1#2#3{%
   \if@thmmarks
     \stepcounter{end\InTheoType ctr}%
   \fi
   \renewcommand{\InTheoType}{#1}%
   \if@thmmarks
     \stepcounter{curr#1ctr}%
     \setcounter{end#1ctr}{0}%
   \fi
   \refstepcounter[#1]{#2}%  <<< cleveref modification
   \theorem@prework
    \LWR@forcenewpage% lwarp
    \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
   \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
     \ifthm@inframe
       \thm@topsep\theoreminframepreskipamount
       \thm@topsepadd\theoreminframepostskipamount
      \else
       \thm@topsep\theorempreskipamount
       \thm@topsepadd\theorempostskipamount
      \fi
```

```
    \else% oldframeskips
      \thm@topsep\theorempreskipamount
      \thm@topsepadd \theorempostskipamount
      \ifvmode\advance\thm@topsepadd\partopsep\fi
  \fi
  \@topsep\thm@topsep
  \@topsepadd\thm@topsepadd
  \advance\linewidth -\theorem@indent
  \advance\linewidth -\theorem@rightindent
  \advance\@totalleftmargin \theorem@indent
  \parshape \@ne \@totalleftmargin \linewidth
  \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
}
}{% not @ifpackageloaded{cleveref}
\gdef\@thm#1#2#3{%
  \if@thmmarks
    \stepcounter{end\InTheoType ctr}%
  \fi
  \renewcommand{\InTheoType}{#1}%
  \if@thmmarks
    \stepcounter{curr#1ctr}%
    \setcounter{end#1ctr}{0}%
  \fi
  \refstepcounter{#2}%
  \theorem@prework
   \LWR@forcenewpage% lwarp
   \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
  \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
  \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
    \ifthm@inframe
      \thm@topsep\theoreminframepreskipamount
      \thm@topsepadd\theoreminframepostskipamount
     \else
      \thm@topsep\theorempreskipamount
      \thm@topsepadd\theorempostskipamount
     \fi
   \else% oldframeskips
     \thm@topsep\theorempreskipamount
     \thm@topsepadd \theorempostskipamount
     \ifvmode\advance\thm@topsepadd\partopsep\fi
  \fi
  \@topsep\thm@topsep
  \@topsepadd\thm@topsepadd
  \advance\linewidth -\theorem@indent
  \advance\linewidth -\theorem@rightindent
  \advance\@totalleftmargin \theorem@indent
  \parshape \@ne \@totalleftmargin \linewidth
  \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
}
}
}% AtBeginDocument
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
```

```
   \@ifundefined{th@#1}{\@warning
          {Unknown theoremstyle '#1'. Using 'plain'}%
          \theorem@style{plain}
            \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
            }%
      {
        \theorem@style{#1}
        \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
        }
}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

\gdef\@xnthm#1#2[#3]{%
  \ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \expandafter\@ifundefined{c@#1}%
        {\@definecounter{#1}}{}%
     \@newctr{#1}[#3]%
     \expandafter\xdef\csname the#1\endcsname{%
       \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
          {\noexpand\csname\the\theoremnumbering\endcsname{#1}}}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@ynthm#1#2{%
  \ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \expandafter\@ifundefined{c@#1}%
        {\@definecounter{#1}}{}%
     \expandafter\xdef\csname the#1\endcsname
        {\noexpand\csname\the\theoremnumbering\endcsname{#1}}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@othm#1[#2]#3{%
  \@ifundefined{c@#2}{\@nocounterr{#2}}%
   {\ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \global\@namedef{the#1}{\@nameuse{the#2}}%
     \expandafter\protected@xdef\csname num@addtheoremline#1\endcsname{%
```

```
              \noexpand\@num@addtheoremline{#1}{#3}}%
     \expandafter\protected@xdef\csname nonum@addtheoremline#1\endcsname{%
              \noexpand\@nonum@addtheoremline{#1}{#3}}%
    \theoremkeyword{#3}%
    \expandafter\protected@xdef\csname #1Keyword\endcsname
             {\the\theoremkeyword}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
                \@thm{#1}{#2}{#3}
        }%
     \global\@namedef{end#1}{\@endtheorem}
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi}
}
```

§ 358.4 HTML cross-referencing

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```
\newcommand{\LWR@inctheorem}{%
\addtocounter{LWR@thisautoid}{1}%
\LWR@stoppars%
\LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
\LWR@startpars%
}
```

§ 358.5 `\newtheoremstyle`

The following are patched for CSS.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader<style>`.

```
\gdef\newtheoremstyle#1#2#3{%
  \expandafter\@ifundefined{th@#1}%
   {\expandafter\gdef\csname th@#1\endcsname{%
    \def\@begintheorem####1####2{%
    \LWR@inctheorem% lwarp
    #2}%
    \def\@opargbegintheorem####1####2####3{%
    \LWR@inctheorem% lwarp
    #3}%
}%
}%
{\PackageError{\basename}{Theorem style #1 already defined}\@eha}
}
```

§ 358.6 Standard styles

```
\renewtheoremstyle{plain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}

\renewtheoremstyle{break}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheaderbreak}%
        {##1\ ##2\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{change}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]}

\renewtheoremstyle{changebreak}%
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\theorem@separator}\newline
    ]}%
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{margin}%
  {\item[
        \InlineClass{theoremheadermargin}{##2 \qquad ##1\theorem@separator}
    ]}%
  {\item[
     \InlineClass{theoremheadermargin}{##2 \qquad ##1\ (##3)\theorem@separator}
    ]}

\renewtheoremstyle{marginbreak}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{nonumberplain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ (##3)\theorem@separator}]}
```

```
238
239 \renewtheoremstyle{nonumberbreak}%
240   {\item[
241     \InlineClass{theoremheaderbreak}{##1\theorem@separator}\newline
242     ]}%
243   {\item[
244     \InlineClass{theoremheaderbreak}{##1\ (##3)\theorem@separator}\newline
245     ]}
246
247 \renewtheoremstyle{empty}%
248   {\item[]}%
249   {\item[
250     \InlineClass{theoremheaderplain}{##3}]}
251
252 \renewtheoremstyle{emptybreak}%
253   {\item[]}%
254   {\item[
255     \InlineClass{theoremheaderplain}{##3}] \ \newline}
```

§ 358.7 Additional objects

The following manually adjust the css for the standard configuration objects which are not a purely plain style:

```
256 \ifbool{LWR@ntheoremamsthm}{}{%
```

Upright text via CSS:

```
257     \newtheoremstyle{plainupright}%
258     {\item[
259         \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
260     {\item[
261         \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}
```

Upright text and small caps header via CSS:

```
262     \newtheoremstyle{nonumberplainuprightsc}%
263     {\item[
264         \InlineClass{theoremheadersc}{##1\theorem@separator}]}%
265     {\item[
266         \InlineClass{theoremheadersc}{##1\ (##3)\theorem@separator}]}
267 }% not amsthm
```

§ 358.8 Renewed standard configuration

The following standard configuration is renewed using the new css:

```
268 \ifbool{LWR@ntheoremamsthm}{}{%
```

```
269 \ifx\thm@usestd\@undefined
270 \else
271     \theoremnumbering{arabic}
272     \theoremstyle{plain}
273     \RequirePackage{latexsym}
```

```
    \theoremsymbol{\Box}
    \theorembodyfont{\itshape}
    \theoremheaderfont{\normalfont\bfseries}
    \theoremseparator{}
    \renewtheorem{Theorem}{Theorem}
    \renewtheorem{theorem}{Theorem}
    \renewtheorem{Satz}{Satz}
    \renewtheorem{satz}{Satz}
    \renewtheorem{Proposition}{Proposition}
    \renewtheorem{proposition}{Proposition}
    \renewtheorem{Lemma}{Lemma}
    \renewtheorem{lemma}{Lemma}
    \renewtheorem{Korollar}{Korollar}
    \renewtheorem{korollar}{Korollar}
    \renewtheorem{Corollary}{Corollary}
    \renewtheorem{corollary}{Corollary}

    \theoremstyle{plainupright}
    \theorembodyfont{\upshape}
    \theoremsymbol{\HTMLunicode{25A1}}% UTF-8 white box
    \renewtheorem{Example}{Example}
    \renewtheorem{example}{Example}
    \renewtheorem{Beispiel}{Beispiel}
    \renewtheorem{beispiel}{Beispiel}
    \renewtheorem{Bemerkung}{Bemerkung}
    \renewtheorem{bemerkung}{Bemerkung}
    \renewtheorem{Anmerkung}{Anmerkung}
    \renewtheorem{anmerkung}{Anmerkung}
    \renewtheorem{Remark}{Remark}
    \renewtheorem{remark}{Remark}
    \renewtheorem{Definition}{Definition}
    \renewtheorem{definition}{Definition}

    \theoremstyle{nonumberplainuprightsc}
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \renewtheorem{Proof}{Proof}
    \renewtheorem{proof}{Proof}
    \renewtheorem{Beweis}{Beweis}
    \renewtheorem{beweis}{Beweis}
    \qedsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof

    \theoremsymbol{}
\fi
}% not amsthm
```

§ 358.9 amsthm option

Only if the amsthm option was given:

```
\ifbool{LWR@ntheoremamsthm}{

\gdef\th@plain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
```

```
      \item[
  \InlineClass{theoremheaderplain}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberplain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderplain}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ (##3).}
        ]}}

\gdef\th@definition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberdefinition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderdefinition}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ (##3).}
        ]}}

\gdef\th@remark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1\ ##2.}
        ]}%
```

```
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderremark}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberremark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderremark}{##1\ (##3).}
        ]}}

\gdef\th@proof{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderproof}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderproof}{##1\ (##3).}
        ]}}



\newcounter{proof}%
\if@thmmarks
    \newcounter{currproofctr}%
    \newcounter{endproofctr}%
\fi

\gdef\proofSymbol{\openbox}

\newcommand{\proofname}{Proof}

\newenvironment{proof}[1][\proofname]{
    \th@proof
    \def\theorem@headerfont{\itshape}%
    \normalfont
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \@thm{proof}{proof}{#1}
}%
{\@endtheorem}

}{}% amsthm option
```

§ 358.10 Ending a theorem

Patched for css:

```
\let\LWR@origendtheorem\@endtheorem
\renewcommand{\@endtheorem}{%
\ifbool{LWR@ntheoremmarks}{%
    \ifsetendmark%
    \InlineClass{theoremendmark}{\csname\InTheoType Symbol\endcsname}%
    \setendmarkfalse%
    \fi%
}{}%
\LWR@origendtheorem% also does \@endtrivlist
\ifbool{LWR@ntheoremmarks}{\global\setendmarktrue}{}%
\endBlockClass%
}
```

§ 358.11 `\NoEndMark`

```
\gdef\NoEndMark{\global\setendmarkfalse}
```

§ 358.12 List-of

Redefined to reuse the float mechanism to add list-of-theorem links:

`\thm@thmline` {⟨*1: printed type*⟩} {⟨*2: #*⟩} {⟨*3: optional*⟩} {⟨*4: page*⟩}

```
\renewcommand{\thm@@thmline@noname}[4]{%
\hypertocfloat{1}{theorem}{thm}{#2 #3}{}%
}

\renewcommand{\thm@@thmline@name}[4]{%
\hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}%
}
```

This was redefined by ntheorem when loaded, so it is now redefined for lwarp:

```
\def\thm@@thmline{\thm@@thmline@name}
```

Patch for css:

```
\def\listtheorems#1{
\LWR@htmlelementclass{nav}{lothm}%
\begingroup
\c@tocdepth=-2%
\def\thm@list{#1}\thm@processlist
\endgroup
\LWR@htmlelementclassend{nav}{lothm}%
}
```

§ 358.13 Symbols

Proof QED symbol:

```
\newcommand{\qed}{\qquad\the\qedsymbol}

\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box

\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\openbox\LWR@orig@openbox%
\LetLtxMacro\blacksquare\LWR@orig@blacksquare%
\LetLtxMacro\Box\LWR@orig@Box%
}% appto
}{}% @ifundefined
}% AtBeginDocument
```

§ 358.14 Cross-referencing

\thref {⟨*label*⟩}

```
\newcommand*{\thref}[1]{\cref{#1}}%
```

File 261 **lwarp-octave.sty**

§ 359 Package octave

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg octave octave is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{octave}[2017/10/31]
```

Remove the leading 1pt kern:

```
\RenewDocumentCommand{\@PrintTicks}{ m }{%
\kern-1pt%  lwarp
\@TickNum = #1%
\loop
\@Tick{}%
\advance\@TickNum by -1
\ifnum\@TickNum > 0
\repeat
}
```

Use unicode for the prime character:

```
\RenewDocumentCommand{\@Tick}{}{\HTMLunicode{2032}}
```

Catch the inline font:

```
\RenewDocumentCommand{\pitch}{ m o m }{%
\if@OctaveNumber%
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \MakeUppercase{#1}%
            \IfValueTF{#2}{#2}{}\textsubscript{#3}%
        }%
    }%
}%
\else%
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \@GetOctaveTick{#1}[#2]{#3}%
        }%
    }%
}%
\fi%
}
```

The original was hard to adapt to lwarp's handling of &.

```
\StartDefiningTabulars
\renewcommand{\octavetable}{%
\begin{tabular}{ll}
\octaveprimes \pitch{C}{0} & \octavenumbers \pitch{C}{0} \\
\octaveprimes \pitch{C}{1} & \octavenumbers \pitch{C}{1} \\
\octaveprimes \pitch{C}{2} & \octavenumbers \pitch{C}{2} \\
\octaveprimes \pitch{C}{3} & \octavenumbers \pitch{C}{3} \\
\octaveprimes \pitch{C}{4} & \octavenumbers \pitch{C}{4} \\
\octaveprimes \pitch{C}{5} & \octavenumbers \pitch{C}{5} \\
\octaveprimes \pitch{C}{6} & \octavenumbers \pitch{C}{6} \\
\octaveprimes \pitch{C}{7} & \octavenumbers \pitch{C}{7} \\
\end{tabular}
}
\StopDefiningTabulars
```

File 262 **lwarp-overpic.sty**

§ 360 Package overpic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg overpic overpic is patched for use by lwarp.

⚠ scaling The macros \overpicfontsize and \overpicfontskip are used during HTML genera-

tion. These are sent to \fontsize to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the overpic and Overpic environments.

See section 84.2 for the print-mode version of \overpicfontsize and \overpicfontskip.

for HTML output:

```
\LWR@ProvidesPackagePass{overpic}[2017/10/06]

\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}

\BeforeBeginEnvironment{overpic}{%
    \begin{lateximage}%
    \fontsize{\overpicfontsize}{\overpicfontskip}%
    \selectfont%
}

\AfterEndEnvironment{overpic}{\end{lateximage}}

\BeforeBeginEnvironment{Overpic}{%
    \begin{lateximage}%
    \fontsize{\overpicfontsize}{\overpicfontskip}%
    \selectfont%
}

\AfterEndEnvironment{Overpic}{\end{lateximage}}
```

File 263 **lwarp-pagegrid.sty**

§ 361 Package pagegrid

Pkg pagegrid pagegrid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pagegrid}[2016/05/16]

\newcommand*{\pagegridsetup}[1]{}
```

File 264 **lwarp-pagenote.sty**

§ 362 Package pagenote

Pkg pagenote pagenote works as-is, but the page option is disabled.

for HTML output:

```
\DeclareOption{page}{}
\LWR@ProvidesPackagePass{pagenote}[2009/09/03]
```

File 265 **lwarp-pagesel.sty**

§ 363 Package

pagesel

Pkg pagesel pagesel is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pagesel}[2016/05/16]
```

File 266 **lwarp-paralist.sty**

§ 364 Package

paralist

(*Emulates or patches code by* Bernd Schandl.)

Pkg paralist paralist is supported with minor changes.

for HTML output:

```
\LWR@ProvidesPackagePass{paralist}[2017/01/22]
```

The compact environments are identical to the regular ones:

```
\LetLtxMacro\compactitem\itemize
\LetLtxMacro\compactenum\enumerate
\LetLtxMacro\compactdesc\description
\LetLtxMacro\endcompactitem\enditemize
\LetLtxMacro\endcompactenum\endenumerate
\LetLtxMacro\endcompactdesc\enddescription
```

For the inline environments, revert `\item` to its original print-mode version:

```
\AtBeginEnvironment{inparaitem}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparaenum}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparadesc}{\LetLtxMacro\item\LWR@origitem}
```

Manual formatting of the description labels:

```
\def\paradescriptionlabel#1{{\normalfont\textbf{#1}}}
```

File 267 **lwarp-parnotes.sty**

§ 365 Package

parnotes

(*Emulates or patches code by* Chelsea Hughes.)

Pkg parnotes parnotes is supported with some patches.

for HTML output:

```
\LWR@ProvidesPackagePass{parnotes}[2016/08/15]
```

```
\long\def\PN@parnote@real#1#2{%
    \parnotemark{#1}%
    % Unless this is the first parnote in \PN@text, add a separator first
    \unless\ifx\PN@text\@empty\g@addto@macro\PN@text{\parnoteintercmd}\fi
    % Redefine \@currentlabel to the parnote label, so \label works
    \g@addto@macro\PN@text{%
%         \phantomsection%
        \def\@currentlabel{#1}%
        \def\cref@currentlabel{%        lwarp
            [parnotemark][\arabic{parnotemark}][]\theparnotemark%
        }%
    }%
    \g@addto@macro\PN@text{%
        \LWR@textcurrentfont{%          lwarp
            \parnotemark{#1}\nolinebreak\thinspace#2%
        }%
    }%
}

\def\PN@parnotes@real{%
    % We call \par later, so this avoids recursion with \PN@parnotes@auto
    \PN@inparnotestrue
    \unless\ifvmode\par\fi
    % Avoid page breaks between a paragraph and its parnotes
    \nopagebreak\addvspace{\parnotevskip}%
    \LWR@forcenewpage%                  lwarp
    \begin{BlockClass}{footnotes}%      lwarp
    {\parnotefmt{\PN@text}\par}%
    \end{BlockClass}%                   lwarp
    \global\def\PN@text{}%
    \addvspace{\parnotevskip}%
    %
    % These can be enabled or disabled by package options
    %
    \PN@disable@indent
    \PN@reset@optional
    \PN@inparnotesfalse
}

\AtBeginDocument{
\crefname{parnotemark}{paragraph note}{paragraph notes}%
\Crefname{parnotemark}{Paragraph note}{Paragraph notes}
}
```

File 268 **lwarp-parskip.sty**

§ 366 Package

parskip

Pkg parskip parskip is ignored.

for HTML output: Discard all options for lwarp-parskip.

```
\LWR@ProvidesPackageDrop{parskip}[2001/04/09]
```

File 269 **lwarp-pbox.sty**

§ 367 Package pbox

(*Emulates or patches code by* Simon Law.)

Pkg pbox pbox is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{pbox}[2011/12/07]

\NewDocumentCommand{\pbox}{O{t} O{} O{t} m +m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox[#1][#2][#3]{#4}{#5}%
}

\newcommand{\settominwidth}[3][\columnwidth]{%
\settowidth{#2}{#3}%
}

\newcommand{\widthofpbox}[1]{%
\widthof{#1}%
}
```

File 270 **lwarp-pdfcomment.sty**

§ 368 Package pdfcomment

Pkg pdfcomment pdfcomment is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcomment}[2016/06/13]

\newenvironment{pdfsidelinecomment}[2][]{}{}
\newcommand{\pdfcomment}[2][]{}
\newcommand{\pdfmargincomment}[2][]{}
\newcommand{\pdfmarkupcomment}[3][]{#2}
\newcommand{\pdffreetextcomment}[2][]{}
\newcommand{\pdfsquarecomment}[2][]{}
\newcommand{\pdfcirclecomment}[2][]{}
\newcommand{\pdflinecomment}[2][]{}
\newcommand{\pdftooltip}[3][]{#2}
\newcommand{\pdfcommentsetup}[2][]{}
\newcommand{\listofpdfcomments}[1][]{}
\newcommand{\setliststyle}[1]{}
\newcommand{\defineliststyle}[2]{}
\newcommand{\defineavatar}[2]{}
\newcommand{\definestyle}[2]{}
```

File 271 **lwarp-pdfcrypt.sty**

§ 369 Package pdfcrypt

Pkg pdfcrypt pdfcrypt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcrypt}[2016/05/16]
\newcommand*{\pdfcryptsetup}[1]{}
```

File 272 **lwarp-pdflscape.sty**

§ 370 Package pdflscape

Pkg pdflscape pdflscape is ignored.

for HTML output: Discard all options for lwarp-pdflscape:

```
\LWR@ProvidesPackageDrop{pdflscape}[2016/05/14]
```

File 273 **lwarp-pdfmarginpar.sty**

§ 371 Package pdfmarginpar

Pkg pdfmarginpar pdfmarginpar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfmarginpar}[2011/08/05]
\newcommand{\pdfmarginpar}[2][]{}
\newcommand{\pdfmarginparset}[1]{}
```

File 274 **lwarp-pdfpages.sty**

§ 372 Package pdfpages

(*Emulates or patches code by* Andreas Matthias.)

Pkg pdfpages pdfpages is patched for use by lwarp.

Option `link` and `linkname` work:

```
\hyperlink{<filename>.pdf.<pagenubmer}}{some text}
\hyperlink{<linkname>.<pagenubmer}}{some text}
```

Options which make no sense in HTML are disabled.

for HTML output:

```
\LWR@ProvidesPackagePass{pdfpages}[2017-10-31]
```

Disable option which have no meaning for HTML output:

```
\define@key{pdfpages}{fitpaper}[false]{}
\define@key{pdfpages}{landscape}[false]{}
\define@key{pdfpages}{openright}[false]{}
\define@key{pdfpages}{signature}{}
\define@key{pdfpages}{signature*}{}
\define@key{pdfpages}{booklet}[false]{}
\define@key{pdfpages}{rotateoversize}[false]{}
\define@key{pdfpages}{doublepages}[false]{}
\define@key{pdfpages}{doublepagestwist}[false]{}
\define@key{pdfpages}{doublepagestwistodd}[false]{}
\define@key{pdfpages}{doublepagestwist*}[false]{}
\define@key{pdfpages}{doublepagestwistodd*}[false]{}
\define@key{pdfpages}{duplicatepages}[2]{}
\define@key{pdfpages}{thread}[false]{}
\define@key{pdfpages}{threadname}{}
\define@key{pdfpages}{linkfit}{}
\define@key{pdfpages}{linktodoc}[false]{}
\define@key{pdfpages}{linktodocfit}{}
\define@key{pdfpages}{linkfilename}{}
\define@key{pdfpages}{survey}[false]{}
\define@key{pdfpages}{survey-nolink}[false]{}
\define@key{pdfpages}{newwindow}[false]{}
```

Use print mode while measuring the page numbers:

```
\xpretocmd{\AM@getpagecount}{\LWR@restoreorigformatting}{}{}
```

Emulate a bit of eso-pic:

```
\newif\ifESO@texcoord

\newcommand{\ESO@HookIIBG}{}

\renewcommand{\AM@AddToShipoutPicture}{\g@addto@macro\ESO@HookIIBG}

\renewcommand{\ClearShipoutPicture}{}
```

`\LWR@esopic@newpage` At each \newpage.

```
\newcommand*{\LWR@esopic@newpage}{%
```

Is there something to draw?

```
\ifdefvoid{\ESO@HookIIBG}%
```

```
{}%
{%
```

If the `link` option was specified, add a hyper target:

```
    \ifAM@link%
        \hypertarget{\AM@linkname.\AM@page}{}%
    \fi%
```

Draw inside a picture environment of the size of a virtual page:

```
    \begingroup%
    \setlength{\unitlength}{1in}%
    \begin{picture}(8,10.5)%
    \ESO@HookIIBG%
    \end{picture}%
    \endgroup%
    \global\let\ESO@HookIIBG\@empty%
}
}
```

`\AM@output` Patched to use `\LWR@esopic@newpage`.

```
\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-1}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-2}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-3}}
```

`\includepdf` Patched to set the user's paper size.

```
\xpretocmd{\includepdf}{%
    \begingroup%
    \setlength{\paperwidth}{\LWR@userspaperwidth}%
    \setlength{\paperheight}{\LWR@userspaperheight}%
}{}{}

\xapptocmd{\includepdf}{%
    \endgroup%
}{}{}
```

`\includepdfmerge` Patched to set the user's paper size.

```
\xpretocmd{\includepdfmerge}{%
    \begingroup%
```

```
    \setlength{\paperwidth}{\LWR@userspaperwidth}%
    \setlength{\paperheight}{\LWR@userspaperheight}%
}{}{}

\xapptocmd{\includepdfmerge}{%
    \endgroup%
}{}{}
```

\AM@hyper@begin@i Hyper links are created by \LWR@esopic@newpage, so don't create them here:

```
\renewcommand{\AM@hyper@begin@i}{}
```

File 275 **lwarp-pdfprivacy.sty**

§ 373 Package pdfprivacy

Pkg pdfprivacy pdfprivacy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfprivacy}[2017/12/03]
```

File 276 **lwarp-pdfrender.sty**

§ 374 Package pdfrender

Pkg pdfrender pdfrender is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfrender}[2016/05/17]

\newcommand*{\pdfrender}[1]{}
\newcommand{\textpdfrender}[2]{#2}
```

File 277 **lwarp-pdfsync.sty**

§ 375 Package pdfsync

(*Emulates or patches code by* J. Laurens.)

Pkg pdfsync pdfsync is ignored.

for HTML output: Discard all options for lwarp-pdfsync:

```
\LWR@ProvidesPackageDrop{pdfsync}[2008/01/26]

\newcommand*{\pdfsync}{}
\newcommand*{\pdfsyncstart}{}
\newcommand*{\pdfsyncstop}{}
```

File 278 **lwarp-pdftricks.sty**

§ 376 Package pdftricks

(*Emulates or patches code by* C. V. Radhakrishnan, C. V. Rajagopal, Antoine Chambert-Loir.)

Pkg pdftricks pdftricks is patched for use by lwarp.

⚠ convert image files The pdftricks image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **lwarpmk pdftosvg <jobname>-fig*.pdf**

for HTML output:

```
\LWR@ProvidesPackagePass{pdftricks}[2003/08/10]
```

Reuse the print-mode images:

```
\def\PDFTfigname{\BaseJobname-fig\thepsfig}
```

If the `.pdf` images have not yet been converted to `.svg` then an error about a missing file will occur. Warn the user to convert the images.

```
\PackageWarning{lwarp-pdftricks}{
When the pdftricks images change,
remember to convert PDF images to SVG using 'lwarpmk pdftosvg *-fig.pdf',
}

\AfterEndDocument{\typeout{***}}
\AfterEndDocument{\typeout{*** Note: If pdftricks images are not found, new, or updated,}}
\AfterEndDocument{\typeout{*** \space use 'lwarpmk pdftosvg \BaseJobname-fig*.pdf'}}
\AfterEndDocument{\typeout{***}}
```

File 279 **lwarp-pdfx.sty**

§ 377 Package pdfx

Pkg pdfx pdfx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfx}[2017/05/18]
```

File 280 **lwarp-perpage.sty**

§ 378 Package perpage

(*Emulates or patches code by* David Kastrup.)

Pkg perpage

perpage is mostly ignored, but support is added for footnote counters.

There is no page number in HTML, so most counters are not reset. If the document redefines \the<countername> to include \theperpage, it is necessary to place that redefininition inside a warpprint environment to avoid modifying the HTML defintions.

\AddAbsoluteCounter must not be inside warpprint, as the counter must be added for HTML also, although it is not incremented.

footnote numbering

To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for \alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

for HTML output:

```
\LWR@ProvidesPackageDrop{perpage}[2014/10/25]

\newcommand\AddAbsoluteCounter[1]
{
    \@ifundefined{c@abs#1}{%
        \expandafter\newcount\csname c@abs#1\endcsname
        \global\value{abs#1}\@ne
%         \global\expandafter\let\csname cl@abs#1\endcsname\@empty
        \expandafter\xdef\csname theabs#1\endcsname{%
%             \noexpand\number \csname c@abs#1\endcsname
        }%
%         \global\@namedef{c@pabs@#1}{\pp@cl@begin
%         \stepcounter{abs#1}%
%         \pp@cl@end}%
%         \@addtoreset{pabs@#1}{#1}
    }
    {}
}

\AddAbsoluteCounter{page}
\def\theabspage{1}

\newcommand*\MakePerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
    }{

}%
}

\newcommand*\MakeSorted[1]{}

```

```
\newcommand*\MakeSortedPerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
    }{
}%
}

\newcommand*{\theperpage}{1}
```

File 281 **lwarp-pfnote.sty**

§ 379 Package

pfnote

Pkg pfnote pfnote is ignored.

pfnote

⚠ pfnote numbers While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

for HTML output:

```
\LWR@ProvidesPackageDrop{pfnote}[1999/07/14]
```

File 282 **lwarp-phfqit.sty**

§ 380 Package

phfqit

(*Emulates or patches code by* Philippe Faist.)

Pkg phfqit phfqit is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{phfqit}[2017/08/16]

\LetLtxMacro\LWR@origbitstring\bitstring

\renewcommand\bitstring[1]{%
\InlineClass[%
    text-decoration: overline underline ;
]{bitstring}{#1}%
% \phfqit@bitstring{#1}%
}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bitstring\LWR@origbitstring%
}
```

File 283 **lwarp-pifont.sty**

§ 381 Package

pifont

(*Emulates or patches code by* Walter Schmidt.)

Pkg pifont pifont is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```
\LWR@ProvidesPackagePass{pifont}[2005/04/12]

\renewcommand{\Pisymbol}[2]{%
    \begin{lateximage}*[Pisymbol][pisymbol#1#2]%
    {\Pifont{#1}\char#2}%
    \end{lateximage}%
}

\newcommand{\LWR@HTML@Pifill}[2]{
    \Pisymbol{#1}{#2} \Pisymbol{#1}{#2} \Pisymbol{#1}{#2}
}
\LWR@formatted{Pifill}

\newcommand{\LWR@HTML@Piline}[2]{%
    \par\noindent\hspace*{0.5in}
    \Pifill{#1}{#2} \Pifill{#1}{#2} \Pifill{#1}{#2}
}
\LWR@formatted{Piline}
```

File 284 **lwarp-placeins.sty**

§ 382 Package placeins

(*Emulates or patches code by* Donald Arseneau.)

Pkg placeins placeins is ignored.

Discard all options for lwarp-placeins:

for HTML output:

```
\LWR@ProvidesPackageDrop{placeins}[2005/04/18]

\newcommand*{\FloatBarrier}{}
```

File 285 **lwarp-plarydshln.sty**

§ 383 Package plarydshln

Pkg plarydshln plarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plarydshln}[2018/10/20]

\LWR@origRequirePackage{lwarp-arydshln}
```

File 286 **lwarp-plext.sty**

§ 384 Package

plext

Pkg plext plext is preloaded by jtarticle and related classes.

for HTML output:

```
\LWR@loadbefore{plext}

\LWR@ProvidesPackagePass{plext}[2017/07/21]


\let\tate\relax

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

% \layoutfloat(width,height)[pos]#4
\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

% \DeclareLayoutCaption{type} <dir>(width)[pos1pos2]
\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

% \layoutcaption<dir>(width)[pos]
\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
```

Add the optional <t/y> direction:

```
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

% \pbox <t/y> [width] [l/r] {contents}
\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

picture, as modified by pext, is encapsulated by the lwarp core.

File 287 **lwarp-plextarydshln.sty**

§ 385 Package plextarydshln

Pkg plextarydshln plextarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextarydshln}[2018/10/20]
\LWR@origRequirePackage{lwarp-arydshln}
```

File 288 **lwarp-plextcolortbl.sty**

§ 386 Package plextcolortbl

Pkg plextcolortbl plextcolortbl is emulated by lwarp-colortbl.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextcolortbl}[2018/09/19]
\LWR@origRequirePackage{lwarp-colortbl}
```

File 289 **lwarp-prelim2e.sty**

§ 387 Package prelim2e

(*Emulates or patches code by* Martin Schröder.)

Pkg prelim2e prelim2e is ignored.

for HTML output: Discard all options for lwarp-prelim2e:

```
\LWR@ProvidesPackageDrop{prelim2e}[2009/05/29]
\newcommand{\PrelimText}{}
\newcommand{\PrelimTextStyle}{}
\newcommand{\PrelimWords}{}
```

File 290 **lwarp-prettyref.sty**

§ 388 Package prettyref

(*Emulates or patches code by* Kevin S. Ruland.)

Pkg prettyref prettyref is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{prettyref}[1998/07/09]

\newrefformat{fig}{Figure \ref{#1}}
\newrefformat{tab}{Table \ref{#1}}
```

File 291 **lwarp-preview.sty**

§ 389 Package preview

Pkg preview preview is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{preview}[2017/04/24]

\newenvironment{preview}{}{}
\newenvironment{nopreview}{}{}
\NewDocumentCommand{\PreviewMacro}{s o o +m}{}
\NewDocumentCommand{\PreviewEnvironment}{s o o +m}{}
\newcommand{\PreviewSnarfEnvironment}[2][]{}
\NewDocumentCommand{\PreviewOpen}{s o}{}
\NewDocumentCommand{\PreviewClose}{s o}{}
\let\ifPreview\iffalse% \fi for syntax highlighting
```

File 292 **lwarp-psfrag.sty**

§ 390 Package psfrag

(*Emulates or patches code by* Michael C. Grant, David Carlisle.)

Pkg psfrag psfrag is patched for use by lwarp.

⚠ use psfrags The psfrags environment is modified to use lateximage to encapsulate the image. Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.

⚠ Tip: Use a mono-spaced font for the tags in the eps file.

for HTML output:

```
\LWR@ProvidesPackagePass{psfrag}[1998/04/11]
```

A lateximage captures the modified image from the document.

```
\BeforeBeginEnvironment{psfrags}{%
    \begin{lateximage}[-psfrags-~\PackageDiagramAltText]%
}

\AfterEndEnvironment{psfrags}{\end{lateximage}}
```

File 293 **lwarp-psfragx.sty**

§ 391 Package psfragx

(*Emulates or patches code by* Pascal Kockaert.)

Pkg psfragx psfragx is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{psfragx}[2012/05/02]
```

A lateximage captures the modified image from the document.

```
\def\pfx@includegraphicx#1#2{%
    \begin{lateximage}[-psfragx-~\PackageDiagramAltText]%
    \mbox{\pfx@overpix{#1}{#2}\endpfx@overpix}%
    \end{lateximage}%
}

\def\@@@overpix[#1]<#2>[#3]#4{%
    \begin{lateximage}[-psfragx-~\PackageDiagramAltText]%
    \pfx@overpix{#1,ovpfgd={#2},ovpbgd={#3}}{#4}%
}

\def\endoverpix{%
    \endpfx@overpix%
    \end{lateximage}%
}
```

File 294 **lwarp-pst-eps.sty**

§ 392 Package pst-eps

(*Emulates or patches code by* Herbert Voss.)

Pkg pst-eps pst-eps is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{pst-eps}[2005/05/20]
```

```
\renewenvironment{TeXtoEPS}{}{}
\renewcommand{\PSTtoEPS}[3][]{}
```

File 295 **lwarp-pstool.sty**

§ 393 Package pstool

(*Emulates or patches code by* Zebb Prime, Will Robertson.)

Pkg pstool pstool is patched for use by lwarp.

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

for HTML output:

```
\LWR@ProvidesPackagePass{pstool}[2018/01/20]
```

Each image is placed inside a lateximage to capture the results of psfrag.

```
\renewcommand\pstool@alwaysprocess[3][]{%
    \begin{lateximage}[-pstool-~\PackageDiagramAltText]%
    \includegraphics{#2.pdf}%
    \end{lateximage}%
}
\LetLtxMacro\pstool@neverprocess\pstool@alwaysprocess
\LetLtxMacro\pstool@maybeprocess\pstool@alwaysprocess

\renewcommand\pstool@@psfragfig[4]{%
    \begin{lateximage}[-pstool-~\PackageDiagramAltText]%
    \includegraphics{#2.pdf}%
    \end{lateximage}%
}
```

File 296 **lwarp-pstricks.sty**

§ 394 Package

pstricks

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg pstricks pstricks is patched for use by lwarp.

⚠ use pspicture All pstricks content should be contained inside a pspicture environment.

for HTML output:

```
\LWR@ProvidesPackagePass{pstricks}[2018/01/06]

\BeforeBeginEnvironment{pspicture}{%
    \begin{lateximage}[pspicture]%
}
\AfterEndEnvironment{pspicture}{\end{lateximage}}
```

File 297 **lwarp-pxatbegshi.sty**

§ 395 Package pxatbegshi

Pkg pxatbegshi pxatbegshi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxatbegshi}[2017/11/04]
\LWR@origRequirePackage{lwarp-atbegshi}
```

File 298 **lwarp-pxeveryshi.sty**

§ 396 Package pxeveryshi

Pkg pxeveryshi pxeveryshi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxeveryshi}[2012/05/19]
\LWR@origRequirePackage{lwarp-everyshi}
```

File 299 **lwarp-pxftnright.sty**

§ 397 Package pxftnright

Pkg pxftnright pxftnright is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxftnright}[2017/02/28]
\LWR@origRequirePackage{lwarp-ftnright}
```

File 300 **lwarp-pxjahyper.sty**

§ 398 Package pxjahyper

Pkg pxjahyper pxjahyper is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxjahyper}[2018/07/15]
```

File 301 **lwarp-quotchap.sty**

§ 399 Package

quotchap

(*Emulates or patches code by* Karsten Tinnefeld, Jan Klever.)

Pkg quotchap quotchap is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{quotchap}[2019/07/09]

\newcommand{\@quotchap}{}
\newlength{\LWR@quotchapwidth}

\let\@printcites\relax

\newcommand*{\@iprintcites}{%
```

Place the quotes inside a of class quotchap, of the maximum selected width:

```
\begin{BlockClass}[max-width: \LWR@printlength{\LWR@quotchapwidth}]{quotchap}
%\begin{minipage}{\LWR@quotchapwidth}
\@quotchap
%\end{minipage}
\end{BlockClass}
```

Deactivate the quote printing:

```
\global\let\@printcites\relax
}

\NewEnviron{savequote}[1][\linewidth]{%
```

Remember the width, adjusted for HTML, and make the length assignment global, per: https://tex.stackexchange.com/questions/300823/why-is-setlength-ineffective-inside-a-tabular-environment

```
\setlength{\LWR@quotchapwidth}{#1*2}%
\global\LWR@quotchapwidth=\LWR@quotchapwidth%
```

Remember the body, and activate the quote printing:

```
\global\let\@quotchap\BODY
\global\let\@printcites\@iprintcites%
}
```

The quotation author is placed inside a of class qauthor:

```
\newcommand{\qauthor}[1]{%
    \LWR@stoppars%
```

```
    \begin{BlockClass}{qauthor}%
    {#1}%
    \end{BlockClass}%
    \LWR@startpars%
}
```

Fonts are ignored. Use css.

```
\newcommand{\qsetcnfont}[1]{}
\providecommand*{\quotefont}{}
\providecommand*{\qauthorfont}{}
```

File 302 **lwarp-quoting.sty**

§ 400 Package quoting

(*Emulates or patches code by* Thomas Titz.)

Pkg quoting quoting is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{quoting}[2014/01/28]
```

```
\xpatchcmd{\quoting}{\quo@begintext}
    {\begin{LWR@blocktextcurrentfont}\quo@begintext}
    {}
    {\LWR@patcherror{quoting}{quoting}}

\xpatchcmd{\endquoting}{\quo@endtext}
    {\quo@endtext\end{LWR@blocktextcurrentfont}\LWR@stoppars}
    {}
    {\LWR@patcherror{imakeidx}{endquoting}}
```

File 303 **lwarp-ragged2e.sty**

§ 401 Package ragged2e

(*Emulates or patches code by* Martin Schröder.)

Pkg ragged2e ragged2e is emulated.

Discard all options for lwarp-ragged2e:

for HTML output:

```
\LWR@ProvidesPackageDrop{ragged2e}[2009/05/21]
```

```
\LetLtxMacro\Centering\centering
\LetLtxMacro\RaggedLeft\raggedleft
\LetLtxMacro\RaggedRight\raggedright
\newcommand*{\justifying}{}
\newlength{\CenteringLeftskip}
\newlength{\RaggedLeftLeftskip}
```

```
\newlength{\RaggedRightLeftskip}
\newlength{\CenteringRightskip}
\newlength{\RaggedLeftRightskip}
\newlength{\RaggedRightRightskip}
\newlength{\CenteringParfillskip}
\newlength{\RaggedLeftParfillskip}
\newlength{\RaggedRightParfillskip}
\newlength{\JustifyingParfillskip}
\newlength{\CenteringParindent}
\newlength{\RaggedLeftParindent}
\newlength{\RaggedRightParindent}
\newlength{\JustifyingParindent}
\newenvironment*{Center}{\center}{\endcenter}
\newenvironment*{FlushLeft}{\flushleft}{\endflushleft}
\newenvironment*{FlushRight}{\flushright}{\endflushright}
\newenvironment*{justify}{\justifying}{\endjustifying}
```

File 304 **lwarp-realscripts.sty**

§ 402 Package

realscripts

(*Emulates or patches code by* Will Robertson.)

Pkg realscripts realscripts is emulated. See `lwarp.css` for the of class supsubscript.

for HTML output:

```
\LWR@ProvidesPackageDrop{realscripts}[2016/02/13]

\let\realsuperscript\textsuperscript
\let\realsubscript\textsubscript

\let\fakesuperscript\textsuperscript
\let\fakesubscript\textsubscript

\newlength{\subsupersep}

\newcommand*{\LWR@realscriptsalign}{}

\newcommand*{\LWR@setrealscriptsalign}[1]{%
    \renewcommand*{\LWR@realscriptsalign}{}%
    \ifthenelse{\equal{#1}{c}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:center} ; %
        }%
    }{}%
    \ifthenelse{\equal{#1}{r}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:right} ; %
        }%
    }{}%
}

\DeclareDocumentCommand \textsubsuperscript {s O{l} mm} {%
    \LWR@setrealscriptsalign{#2}%
```

```
    \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
        \textsuperscript{#4}\textsubscript{#3}%
    }%
}

\DeclareDocumentCommand \textsupersubscript {s O{l} mm} {%
    \LWR@setrealscriptsalign{#2}%
    \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
        \textsubscript{#4}\textsuperscript{#3}%
    }%
}
```

File 305 **lwarp-refcheck.sty**

§ 403 Package refcheck

Pkg refcheck refcheck is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{refcheck}[2013/02/14]

\def\showrefnames{}
\def\norefnames{}
\def\showcitenames{}
\def\nocitenames{}
\def\setonmsgs{}
\def\setoffmsgs{}
\def\checkunlbld{}
\def\ignoreunlbld{}
\newcommand*{\refcheckxrdoc}[2][]{}
```

File 306 **lwarp-register.sty**

§ 404 Package register

(*Emulates or patches code by* Matthew Lovell.)

Pkg register register is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{register}[2019/01/01]

\xpatchcmd{\register}
    {\centering}
    {%
        \begin{center}%
        \begin{lateximage}[-register-~\PackageDiagramAltText]%
    }
    {}
    {\LWR@patcherror{register}{register}}

\xpatchcmd{\endregister}
```

```
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister}}

\expandafter\xapptocmd\csname register*\endcsname
    {%
        \begin{center}%
        \begin{lateximage}[-register-~\PackageDiagramAltText]%
    }
    {}
    {\LWR@patcherror{register}{register*}}

\expandafter\xpatchcmd\csname endregister*\endcsname
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister*}}

\setlength{\regWidth}{5in}
```

File 307 **lwarp-relsize.sty**

§ 405 Package

relsize

(*Emulates or patches code by* Donald Arseneau, Bernie Cosell, Matt Swift.)

Pkg relsize relsize is patched for use by lwarp.

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small The HTML browser's setting for minumum font size may limit how small the output will be displayed.

for HTML output:

```
\LWR@ProvidesPackagePass{relsize}[2013/03/29]

\let\LWR@origrelsize\relsize
\LetLtxMacro\LWR@origlarger\larger
\LetLtxMacro\LWR@origsmaller\smaller
\let\LWR@relscale\relscale
\LetLtxMacro\LWR@origtextlarger\textlarger
```

```
\LetLtxMacro\LWR@origtextsmaller\textsmaller
\let\LWR@textscale\textscale

\appto\LWR@restoreorigformatting{%
\let\relsize\LWR@origrelsize%
\LetLtxMacro\larger\LWR@origlarger%
\LetLtxMacro\smaller\LWR@origsmaller%
\let\relscale\LWR@relscale%
\LetLtxMacro\textlarger\LWR@origtextlarger%
\LetLtxMacro\textsmaller\LWR@origtextsmaller%
\let\textscale\LWR@textscale%
}

\newcounter{LWR@relsizetemp}

\renewcommand*{\relsize}[1]{}
\renewcommand*{\larger}[1][]{}
\renewcommand*{\smaller}[1][]{}
\renewcommand*{\relscale}[1]{}

\renewcommand*{\textlarger}[2][1]{%
\setcounter{LWR@relsizetemp}{100+(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textlarger}{#2}%
}

\renewcommand*{\textsmaller}[2][1]{%
\setcounter{LWR@relsizetemp}{100-(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textsmaller}{#2}%
}

\renewcommand*{\textscale}[2]{%
\setcounter{LWR@relsizetemp}{100*\real{#1}}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textscale}{#2}%
}
```

File 308 **lwarp-repeatindex.sty**

§ 406 Package

repeatindex

Pkg repeatindex repeatindex is emulated for lwarp.

⚠ style file lwarp must be used with a special style file:

```
\usepackage[makeindex,makeindexStyle={lwarp_repeatindex}]{lwarp}
```

where `lwarp_repeatindex.ist` may be copied from the following modified version of `lwarp.ist`:

```
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
```

```
      \\par\\textbf{#1}\\par
      \\nopagebreak
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 "], \\hyperindexref{"
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"

item_0 "\n  \\item ["
```

(The modifications are the `delim_0` and `item_0` entries.)

for HTML output:

```
\LWR@ProvidesPackageDrop{repeatindex}[2001/10/13]
```

In the lwarp core, `\LWR@indexitem` is modified to accept the optional `\item` argument.

```
\RequirePackage{makeidx}
\def\entryprefix{\itshape}
\def\entrypostfix{\dots}
```

File 309 **lwarp-resizegather.sty**

§ 407 Package resizegather

Pkg resizegather resizegather is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{resizegather}[2016/05/16]
```

```
\newcommand*{\resizegathersetup}[1]{}
```

File 310 **lwarp-rmpage.sty**

§ 408 Package rmpage

Pkg rmpage rmpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{rmpage}[1997/09/29]
```

File 311 **lwarp-romanbar.sty**

§ 409 Package romanbar

(*Emulates or patches code by* H.-Martin Münch.)

Pkg romanbar romanbar is patched for use by lwarp.

An inline class with an overline and underline is used.

for HTML output:

```
\LWR@ProvidesPackagePass{romanbar}[2012/01/01]

\DeclareRobustCommand{\Roman@bar}[1]{% #1 is in Roman, i.e. MMXII
\InlineClass[%
    text-decoration: overline underline ;
]{romanbar}{#1}%
}
```

File 312 **lwarp-romanbarpagenumber.sty**

§ 410 Package romanbarpagenumber

Pkg romanbarpagenumber romanbarpagenumber is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{romanbarpagenumber}[2015/02/06]
```

File 313 **lwarp-rotating.sty**

§ 411 Package rotating

(*Emulates or patches code by* Robin Fairbairns, Sebastian Rahtz, Leonor Barroca.)

Pkg rotating rotating is emulated.

All rotations are ignored in HTML output.

for HTML output:

```
\LWR@ProvidesPackageDrop{rotating}[2016/08/11]
\RequirePackage{graphicx}

\LetLtxMacro\sidewaystable\table
\let\endsidewaystable\endtable

\LetLtxMacro\sidewaysfigure\figure
\let\endsidewaysfigure\endfigure

\newenvironment*{sideways}{}{}
```

```
\newenvironment*{turn}[1]{}{}
\newenvironment*{rotate}[1]{}{}
\NewDocumentCommand{\turnbox}{m +m}{#2}
\let\rotcaption\caption
\let\@makerotcaption\@makecaption
```

File 314 **lwarp-rotfloat.sty**

§ 412 Package

rotfloat

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg rotfloat rotfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{rotfloat}[2004/01/04]

\RequirePackage{float}
```

\newfloat {⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the \newfloat command from the float package. Sideways floats are \let to the same as regular floats.

"placement" is ignored.

```
\RenewDocumentCommand{\newfloat}{m m m o}{%
\IfValueTF{#4}%
{%
    \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}%
}%
{%
    \DeclareFloatingEnvironment[fileext=#3]{#1}%
}%
\csletcs{sideways#1}{#1}%
\csletcs{endsideways#1}{end#1}%
```

Remember the float style:

```
\csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
\csedef{LWR@floatstyle@sideways#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later:

```
\cslet{listof#1s}\relax%
\cslet{listof#1es}\relax%
\cslet{listofsideways#1s}\relax%
\cslet{listofsideways#1es}\relax%
}
```

File 315 **lwarp-rviewport.sty**

§ 413 Package rviewport

Pkg rviewport rviewport is honored inside a lateximage, and otherwise ignored for HTML output.

If rviewport is important for an image, enclose the image inside a lateximage environment.

for HTML output:

```
\LWR@ProvidesPackagePass{rviewport}[2011/08/27]
\define@key{igraph}{rviewport}{}
```

File 316 **lwarp-savetrees.sty**

§ 414 Package savetrees

Pkg savetrees savetrees is ignored.

for HTML output: Discard all options for lwarp-savetrees:

```
\LWR@ProvidesPackageDrop{savetrees}[2016/04/13]
```

File 317 **lwarp-scalefnt.sty**

§ 415 Package scalefnt

(*Emulates or patches code by* D. Carlisle.)

Pkg scalefnt scalefnt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{scalefnt}
\DeclareRobustCommand\scalefont[1]{}
```

File 318 **lwarp-schemata.sty**

§ 416 Package schemata

(*Emulates or patches code by* Charles P. Schaum.)

Pkg schemata schemata is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{schemata}[2016/01/25]
```

```
\LetLtxMacro\LWR@schemata@origschema\schema
\LetLtxMacro\LWR@schemata@origSchema\Schema

\renewcommand{\schema}[3][open]{%
\begin{lateximage}%
\LWR@print@normalsize
\LWR@schemata@origschema[#1]{#2}{#3}%
\end{lateximage}%
}

\renewcommand{\Schema}[5][open]{%
\begin{lateximage}%
\LWR@print@normalsize
\LWR@schemata@origSchema[#1]{#2}{#3}{#4}{#5}%
\end{lateximage}%
}
```

File 319 **lwarp-scrextend.sty**

§ 417 Package

scrextend

Pkg scrextend

scrextend is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{scrextend}[2018/03/30]

\DeclareDocumentCommand{\setkomafont}{m m}{}
\DeclareDocumentCommand{\addkomafont}{m m}{}
\DeclareDocumentCommand{\usekomafont}{m}{}

\DeclareDocumentCommand{\usefontofkomafont}{m}{}
\DeclareDocumentCommand{\useencodingofkomafont}{m}{}
\DeclareDocumentCommand{\usesizeofkomafont}{m}{}
\DeclareDocumentCommand{\usefamilyofkomafont}{m}{}
\DeclareDocumentCommand{\useseriesofkomafont}{m}{}
\DeclareDocumentCommand{\useshapeofkomafont}{m}{}

\AtBeginDocument{
    \let\LWR@koma@orig@maketitle\maketitle
    \DeclareDocumentCommand{\maketitle}{o}{\LWR@koma@orig@maketitle}
}

\DeclareDocumentCommand{\extratitle}{m}{}
\DeclareDocumentCommand{\titlehead}{m}{}
\DeclareDocumentCommand{\subject}{m}{}
\DeclareDocumentCommand{\publishers}{m}{\published{#1}}
\DeclareDocumentCommand{\uppertitleback}{m}{}
\DeclareDocumentCommand{\lowertitleback}{m}{}
\DeclareDocumentCommand{\dedication}{m}{}
```

```
25
26 \DeclareDocumentCommand{\ifthispageodd}{m m}{#1}
27
28 \DeclareDocumentCommand{\titlepagestyle}{}{}
29
30 \DeclareDocumentCommand{\cleardoublepageusingstyle}{m}{}
31 \DeclareDocumentCommand{\cleardoubleemptypage}{}{}
32 \DeclareDocumentCommand{\cleardoubleplainpage}{}{}
33 \DeclareDocumentCommand{\cleardoublestandardpage}{}{}
34 \DeclareDocumentCommand{\cleardoubleoddpage}{}{}
35 \DeclareDocumentCommand{\cleardoubleoddpageusingstyle}{m}{}
36 \DeclareDocumentCommand{\cleardoubleoddemptypage}{}{}
37 \DeclareDocumentCommand{\cleardoubleoddplainpage}{}{}
38 \DeclareDocumentCommand{\cleardoubleoddstandardpage}{}{}
39 \DeclareDocumentCommand{\cleardoubleevenpage}{}{}
40 \DeclareDocumentCommand{\cleardoubleevenpageusingstyle}{m}{}
41 \DeclareDocumentCommand{\cleardoubleevenemptypage}{}{}
42 \DeclareDocumentCommand{\cleardoubleevenplainpage}{}{}
43 \DeclareDocumentCommand{\cleardoubleevenstandardpage}{}{}
44
45 \DeclareDocumentCommand{\multiplefootnoteseparator}{}{%
46   \begingroup\let\thefootnotemark\multfootsep\@makefnmark\endgroup
47 }
48
49 \DeclareDocumentCommand{\multfootsep}{}{,}
50
51 \DeclareDocumentCommand{\footref}{m}{%
52   \begingroup
53     \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
54   \endgroup
55   \@footnotemark
56 }
57
58 \DeclareDocumentCommand{\deffootnote}{o m m m}{}
59 \DeclareDocumentCommand{\deffootnotemark}{m}{}
60 \DeclareDocumentCommand{\setfootnoterule}{o m}{}
61 \DeclareDocumentCommand{\raggedfootnote}{}{}


62 \DeclareDocumentCommand{\dictum}{o m}{
63 \begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{dictum}
64     #2
65     \IfValueT{#1}
66     {
67         \LWR@stoppars%
68         \ifbool{FormatWP}
69       {\begin{BlockClass}[\LWR@print@mbox{border-top:} 1px solid gray]{dictumauthor}}
70         {\begin{BlockClass}{dictumauthor}}
71         \dictumauthorformat{#1}
72         \end{BlockClass}
73     }
74 \end{LWR@BlockClassWP}
75 }
76
77 \DeclareDocumentCommand{\dictumwidth}{}{}
78 \DeclareDocumentCommand{\dictumauthorformat}{m}{(#1)}
```

```
\DeclareDocumentCommand{\dictumrule}{}{}
\DeclareDocumentCommand{\raggeddictum}{}{}
\DeclareDocumentCommand{\raggeddictumtext}{}{}
\DeclareDocumentCommand{\raggeddictumauthor}{}{}

\DeclareDocumentEnvironment{labeling}{o m}
{%
\def\sc@septext{#1}%
\list{}{}%
\let\makelabel\labelinglabel%
}
{
\endlist
}

\DeclareDocumentCommand{\labelinglabel}{m}{%
#1 \qquad \sc@septext%
}

\let\addmargin\relax
\let\endaddmargin\relax
\cslet{addmargin*}{\relax}
\cslet{endaddmargin*}{\relax}


\NewDocumentEnvironment{addmargin}{s O{} m}
{
\LWR@stoppars%
\setlength{\LWR@templengthtwo}{#3}
\ifblank{#2}
{
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthtwo}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
{
    \setlength{\LWR@templengthone}{#2}
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
}
{\end{BlockClass}\LWR@startpars}
```

Ref to create a starred environment:
https://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment

```

\ExplSyntaxOn
\cs_new:cpn {addmargin*} {\addmargin*}
\cs_new_eq:cN {endaddmargin*} \endaddmargin
\ExplSyntaxOff
```

```
127
128 \DeclareDocumentCommand{\marginline}{m}{\marginpar{#1}}
```

File 320 **lwarp-scrhack.sty**

§ 418 Package **scrhack**

Pkg scrhack scrhack is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{scrhack}[2018/03/30]
```

File 321 **lwarp-scrlayer.sty**

§ 419 Package **scrlayer**

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer scrlayer is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
1 \LWR@ProvidesPackageDrop{scrlayer}[2018/03/30]

2 \newcommand*{\DeclareSectionNumberDepth}[2]{}
3 \newcommand*{\DeclareLayer}[2][]{}
4 \newcommand*{\DeclareNewLayer}[2][]{}
5 \newcommand*{\ProvideLayer}[2][]{}
6 \newcommand*{\RedeclareLayer}[2][]{}
7 \newcommand*{\ModifyLayer}[2][]{}
8 \newcommand*{\layerhalign}{}
9 \newcommand*{\layervalign}{}
10 \newcommand*{\layerxoffset}{}
11 \newcommand*{\layeryoffset}{}
12 \newcommand*{\layerwidth}{}
13 \newcommand*{\layerheight}{}
14 \providecommand*{\LenToUnit}[1]{\strip@pt\dimexpr#1*\p@/\unitlength}
15 \newcommand*{\putUL}[1]{}
16 \newcommand*{\putUR}[1]{}
17 \newcommand*{\putLL}[1]{}
18 \newcommand*{\putLR}[1]{}
19 \newcommand*{\putC}[1]{}
20 \newcommand*{\GetLayerContents}[1]{}
21 \newcommand{\IfLayerExists}[3]{#3}
22 \newcommand*{\DestroyLayer}[1]{}
23 \newcommand*{\layercontentsmeasure}{}
24 \newcommand*{\currentpagestyle}{}
25 \newcommand*{\BeforeSelectAnyPageStyle}[1]{}
26 \newcommand*{\AfterSelectAnyPageStyle}[1]{}
27 \newcommand*{\DeclarePageStyleAlias}[2]{}
28 \newcommand*{\DeclareNewPageStyleAlias}[2]{}
```

```
\newcommand*{\ProvidePageStyleAlias}[2]{}
\newcommand*{\RedeclarePageStyleAlias}[2]{}
\newcommand*{\DestroyPageStyleAlias}[1]{}
\newcommand*{\GetRealPageStyle}[1]{}
\newcommand*{\DeclarePageStyleByLayers}[3][]{}
\newcommand*{\DeclareNewPageStyleByLayers}[3][]{}
\newcommand*{\ProvidePageStyleByLayers}[3][]{}
\newcommand*{\RedeclarePageStyleByLayers}[3][]{}
\NewDocumentCommand{\ForEachLayerOfPageStyle}{s m m}{}
\newcommand*{\AddLayersToPageStyle}[2]{}
\newcommand*{\AddLayersAtBeginOfPageStyle}[2]{}
\newcommand*{\AddLayersAtEndOfPageStyle}[2]{}
\newcommand*{\RemoveLayersFromPageStyle}[2]{}
\newcommand*{\AddLayersToPageStyleBeforeLayer}[3]{}
\newcommand*{\AddLayersToPageStyleAfterLayer}[3]{}
\newcommand*{\UnifyLayersAtPageStyle}[1]{}
\newcommand*{\ModifyLayerPageStyleOptions}[2]{}
\newcommand*{\AddToLayerPageStyleOptions}[2]{}
\newcommand{\IfLayerPageStyleExists}[3]{#3}
\newcommand{\IfRealLayerPageStyleExists}[3]{#3}
\newcommand{\IfLayerAtPageStyle}[4]{#4}
\newcommand{\IfSomeLayerAtPageStyle}[4]{#4}
\newcommand{\IfLayersAtPageStyle}[4]{#4}
\newcommand*{\DestroyRealLayerPageStyle}[1]{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\automark}{s o m}{}
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}


\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\DeclareDocumentCommand{\GenericMarkFormat}{m}{}

\newcommand*{\@mkleft}[1]{}
\newcommand*{\@mkright}[1]{}
\newcommand*{\@mkdouble}[1]{}
\newcommand*{\@mkboth}[2]{}
\newcommand*{\scrlayerInitInterface}[1][]{}
\newcommand{\scrlayerAddToInterface}[3][]{}
\newcommand{\scrlayerAddCsToInterface}[3][]{}
\newcommand{\scrlayerOnAutoRemoveInterface}[2][]{}
```

File 322 **lwarp-scrlayer-notecolumn.sty**

§ 420 Package scrlayer-notecolumn

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-notecolumn scrlayer-notecolumn is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-notecolumn}[2018/02/02]

\newcommand*{\DeclareNoteColumn}[2][]{}
\newcommand*{\DeclareNewNoteColumn}[2][]{}
\newcommand*{\ProvideNoteColumn}[2][]{}
\newcommand*{\RedeclareNoteColumn}[2][]{}
\NewDocumentCommand{\makenote}{s o m}{\marginpar{#3}}
\newcommand*{\syncwithnotecolumn}[1][]{}
\newcommand*{\syncwithnotecolumns}[1][]{}
\newcommand*{\clearnotecolumn}[1][]{}
\newcommand*{\clearnotecolumns}[1][]{}
```

File 323 **lwarp-scrlayer-scrpage.sty**

§ 421 Package

scrlayer-scrpage

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-scrpage scrlayer-scrpage is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-scrpage}[2018/03/30]

\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{s o m}{}
\NewDocumentCommand{\cehead}{s o m}{}
\NewDocumentCommand{\rehead}{s o m}{}
\NewDocumentCommand{\lohead}{s o m}{}
\NewDocumentCommand{\cohead}{s o m}{}
\NewDocumentCommand{\rohead}{s o m}{}
\NewDocumentCommand{\lefoot}{s o m}{}
\NewDocumentCommand{\cefoot}{s o m}{}
\NewDocumentCommand{\refoot}{s o m}{}
\NewDocumentCommand{\lofoot}{s o m}{}
\NewDocumentCommand{\cofoot}{s o m}{}
\NewDocumentCommand{\rofoot}{s o m}{}
\NewDocumentCommand{\ohead}{s o m}{}
\NewDocumentCommand{\chead}{s o m}{}
\NewDocumentCommand{\ihead}{s o m}{}
\NewDocumentCommand{\ofoot}{s o m}{}
\NewDocumentCommand{\cfoot}{s o m}{}
\NewDocumentCommand{\ifoot}{s o m}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
\newcommand*{\defpairofpagestyles}[3][]{}
\newcommand*{\newpairofpagestyles}[3][]{}
\newcommand*{\renewpairofpagestyles}[3][]{}
\newcommand*{\providepairofpagestyles}[3][]{}

\newcommand*{\clearmainofpairofpagestyles}{}
```

```
\newcommand*{\clearplainofpairofpagestyles}{}
\newcommand*{\clearpairofpagestyles}{}
\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}

\NewDocumentCommand{\deftriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\newtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\renewtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\providetriplepagestyle}{m o o m m m m m m}{}
\newcommand*{\defpagestyle}[3]{}
\newcommand*{\newpagestyle}[3]{}
\newcommand*{\providepagestyle}[3]{}
\newcommand*{\renewpagestyle}[3]{}
```

File 324 **lwarp-scrpage2.sty**

§ 422 Package scrpage2

(*Emulates or patches code by* Markus Kohm.)

Pkg scrpage2 scrpage2 is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrpage2}[2018/03/30]

\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{o m}{}
\NewDocumentCommand{\cehead}{o m}{}
\NewDocumentCommand{\rehead}{o m}{}
\NewDocumentCommand{\lohead}{o m}{}
\NewDocumentCommand{\cohead}{o m}{}
\NewDocumentCommand{\rohead}{o m}{}
\NewDocumentCommand{\lefoot}{o m}{}
\NewDocumentCommand{\cefoot}{o m}{}
\NewDocumentCommand{\refoot}{o m}{}
\NewDocumentCommand{\lofoot}{o m}{}
\NewDocumentCommand{\cofoot}{o m}{}
\NewDocumentCommand{\rofoot}{o m}{}
\NewDocumentCommand{\ohead}{o m}{}
\NewDocumentCommand{\chead}{o m}{}
\NewDocumentCommand{\ihead}{o m}{}
\NewDocumentCommand{\ofoot}{o m}{}
\NewDocumentCommand{\cfoot}{o m}{}
\NewDocumentCommand{\ifoot}{o m}{}
\DeclareDocumentCommand{\automark}{o m}{}
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
\NewDocumentCommand{\deftripstyle}{m o o m m m m m}{}
\NewDocumentCommand{\defpagestyle}{s m m m}{}
\NewDocumentCommand{\newpagestyle}{s m m m}{}
\NewDocumentCommand{\renewpagestyle}{s m m m}{}
```

```
\NewDocumentCommand{\providepagestyle}{s m m m}{}
\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\newcommand{\subsectionmarkformat}{}
\newcommand{\subsubsectionmarkformat}{}
\newcommand{\paragraphmarkformat}{}
\newcommand{\subparagraphmarkformat}{}

\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}
```

File 325 **lwarp-section.sty**

§ 423 Package

section

Pkg section

section is ignored.

(*Emulates or patches code by* Oliver Pretzel.)

for HTML output:

```
\LWR@ProvidesPackageDrop{section}

\ifx\chapter\undefined
 \def\chsize{\Large}\def\hdsize{\huge}\else
 \def\chsize{\huge}\def\hdsize{\Huge}
\fi
\let\ttsize\LARGE
\let\ausize\large
\let\dasize\large
\let\secsize\Large
\let\subsize\large
\let\hdpos\raggedright
\newcounter{hddepth}
\let\fpind\relax
\def\ttfnt{}
\def\hdfnt{}
\def\fefnt{}
\def\thfnt{}
\def\pgfnt{}
\def\hmkfnt{}
\let\mkcse\uppercase
\def\hddot{}
\def\cpdot{:}
\def\nmdot{}
\ifx\secindent\undefined
 \newdimen\secindent
 \newskip\secpreskp
 \newskip\secpstskp
 \newdimen\subindent
 \newskip\subpreskp
```

```
\newskip\subpstskp
\newskip\parpstskp
\newcount\c@hddepth
\fi
```

File 326 **lwarp-sectionbreak.sty**

§ 424 Package sectionbreak

(*Emulates or patches code by* Michal Hoftich.)

Pkg sectionbreak sectionbreak is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{sectionbreak}[2018-01-03]

\renewcommand\asterism{\HTMLunicode{2042}}

\renewcommand\pre@sectionbreak{}
\renewcommand\post@sectionbreak{}

\renewcommand\print@sectionbreak[1]{%
\begin{center}
#1
\end{center}
}

```

File 327 **lwarp-sectsty.sty**

§ 425 Package sectsty

(*Emulates or patches code by* Rowland McDonnell.)

Pkg sectsty sectsty is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{sectsty}[2002/02/25]

\newcommand*{\partfont}          [1] {}
\newcommand*{\partnumberfont}    [1] {}
\newcommand*{\parttitlefont}     [1] {}
\newcommand*{\chapterfont}       [1] {}
\newcommand*{\chapternumberfont} [1] {}
\newcommand*{\chaptertitlefont}  [1] {}
\newcommand*{\sectionfont}       [1] {}
\newcommand*{\subsectionfont}    [1] {}
\newcommand*{\subsubsectionfont} [1] {}
\newcommand*{\paragraphfont}     [1] {}
\newcommand*{\subparagraphfont}  [1] {}
\newcommand*{\minisecfont}  [1] {}
\newcommand*{\allsectionsfont}[1] {}
\newcommand{\nohang}{}
```

`\sectionrule` is only to be used in `*font` commands, thus it is ignored.

```
\newcommand*{\sectionrule}[5]{}

\def\ulemheading#1#2{}
```

File 328 **lwarp-semantic-markup.sty**

§ 426 Package

semantic-markup

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg semantic-markup semantic-markup is patched for use by lwarp.

⚠ If using the endnotes option, add `\theendnotes` where desired.

for HTML output:

```
\LWR@ProvidesPackagePass{semantic-markup}[2018/05/21]
```

The endnotes must be printed by the user before the end of the document, since the end is after the HTML footer, etc.

```
\ifendnotes
\RenewDocumentCommand{\SetupEndnotes}{}{%
    \let\footnote=\endnote
%     \AtEndDocument{\DoBeforeEndnotes{\EndnoteFont\theendnotes}}%
}
\fi
```

HTML unicode characters from musicography are used.

```
\RequirePackage{musicography}

\let\fl\musFlat
\let\sh\musSharp
\let\na\musNatural
```

The `\musfig` is placed inside a hashed image, with a simple `alt` tag.

```
\RequirePackage{amsmath}

\RenewDocumentCommand{\musfig}{ m m }{%
    \LWR@subsingledollar*%
        {#1/#2}% alt tag
        {musfig}% addl' hashing
        {% contents
            \LWR@origensuredmath{%
                \genfrac{}{}{0pt}{1}{\text{#1}}{\text{#2}}%
            }%
        }%
}
```

The `\meter` is taken from musicography, and becomes a hashed image with a simple `alt` tag.

```
\RenewDocumentCommand{\meter}{ m m }{%
    \musMeter{#1}{#2}%
}
```

File 329 **lwarp-setspace.sty**

§ 427 Package setspace

(*Emulates or patches code by* Robin Fairbairns.)

Pkg setspace setspace is emulated.

Discard all options for lwarp-setspace:

for HTML output:

```
\LWR@ProvidesPackageDrop{setspace}[2011/12/19]

\newcommand*{\setstretch}[1]{}
\newcommand*{\SetSinglespace}[1]{}
\newcommand*{\singlespacing}{}
\newcommand*{\onehalfspacing}{}
\newcommand*{\doublespacing}{}

\newenvironment*{singlespace}
{
\LWR@forcenewpage
\BlockClass{singlespace}
}
{\endBlockClass}

\newenvironment*{singlespace*}
{
\LWR@forcenewpage
\BlockClass{singlespace}
}
{\endBlockClass}

\newenvironment*{spacing}[1]{

}{

}

\newenvironment*{onehalfspace}
{
\LWR@forcenewpage
\BlockClass{onehalfspace}
}
{\endBlockClass}

\newenvironment*{doublespace}
```

```
{
\LWR@forcenewpage
\BlockClass{doublespace}
}
{\endBlockClass}
```

File 330 **lwarp-shadow.sty**

§ 428 Package shadow

(*Emulates or patches code by* Mauro Orlandini.)

Pkg shadow shadow is emulated.

for HTML output: Discard all options for lwarp-shadow:

```
\LWR@ProvidesPackageDrop{shadow}[2003/02/19]

\newdimen\sboxsep
\newdimen\sboxrule
\newdimen\sdim

\newcommand{\shabox}[1]{%
\InlineClass{shabox}{#1}%
}
```

File 331 **lwarp-shapepar.sty**

§ 429 Package shapepar

(*Emulates or patches code by* Donald Arseneau.)

Pkg shapepar shapepar is patched for use by lwarp. Shapes appear in print mode, as well as inside a `latexi`mage, but are ignored for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{shapepar}[2013/03/26]

\newcommand*{\LWR@HTML@shapepar}[2][]{}
\LWR@formatted{shapepar}

\NewDocumentCommand{\LWR@HTML@cutout}{m d()}{}
\LWR@formatted{cutout}
```

File 332 **lwarp-showidx.sty**

§ 430 Package showidx

Pkg showidx showidx is ignored.

for HTML output: Discard all options for lwarp-showidx:

```
\LWR@ProvidesPackageDrop{showidx}[2014/09/29]
```

`\@wrindex` is redefined `\AtBeginDocument` by the lwarp core.

File 333 **lwarp-showkeys.sty**

§ 431 Package showkeys

(*Emulates or patches code by* David Carlisle, Morten Høgholm.)

Pkg showkeys showkeys is ignored.

for HTML output: Discard all options for lwarp-showkeys:

```
\LWR@ProvidesPackageDrop{showkeys}[2014/10/28]
\NewDocumentCommand{\showkeys}{s}{}
```

File 334 **lwarp-showtags.sty**

§ 432 Package showtags

Pkg showtags showtags is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{showtags}% no version is given
\newcommand{\thecitetag}[1]{}
```

File 335 **lwarp-sidecap.sty**

§ 433 Package sidecap

(*Emulates or patches code by* Rolf Niepraschk, Hubert Gässlein.)

Pkg sidecap sidecap is emulated.

for HTML output: Discard all options for lwarp-sidecap.

```
\LWR@ProvidesPackageDrop{sidecap}[2003/06/06]
```

See:
http://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment
regarding the creation of starred environments with xparse.

```
\NewDocumentEnvironment{SCtable}{soo}
{\IfValueTF{#3}{\table[#3]}{\table}}
{\endtable}

\ExplSyntaxOn
\cs_new:cpn {SCtable*} {\SCtable*}
\cs_new_eq:cN {endSCtable*} \endSCtable
\ExplSyntaxOff


\NewDocumentEnvironment{SCfigure}{soo}
{\IfValueTF{#3}{\figure[#3]}{\figure}}
{\endfigure}

\ExplSyntaxOn
\cs_new:cpn {SCfigure*} {\SCfigure*}
\cs_new_eq:cN {endSCfigure*} \endSCfigure
\ExplSyntaxOff


\newenvironment*{wide}{}{}
```

File 336 **lwarp-sidenotes.sty**

§ 434 Package

sidenotes

(*Emulates or patches code by* Andy Thomas, Oliver Schebaum.)

Pkg sidenotes Patched for lwarp.

for HTML output: Load the original package:

```
\LWR@ProvidesPackagePass{sidenotes}
```

The following patch sidenotes for use with lwarp:

\sidecaption * [⟨*entry*⟩] [⟨*offset*⟩] {⟨*text*⟩}

```
\RenewDocumentCommand \sidecaption {s o o +m}
{
   \LWR@stoppars
   \begingroup
  \captionsetup{style=sidecaption}
  \IfBooleanTF{#1}
  { % starred
    \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
    \caption*{#4}
    \end{BlockClass}
  }
  { % unstarred
  \IfNoValueOrEmptyTF{#2}
    {\def\@sidenotes@sidecaption@tof{#4}}
    {\def\@sidenotes@sidecaption@tof{#2}}
```

```
    \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
    \caption[\@sidenotes@sidecaption@tof]{#4}
    \end{BlockClass}
  }
    \endgroup
    \LWR@startpars
}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTsidenotes@marginfloat}{O{-1.2ex} m}
{% start
\LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}

\RenewDocumentEnvironment{marginfigure}{o}
  {\begin{KFLTsidenotes@marginfloat}{figure}}
  {\end{KFLTsidenotes@marginfloat}}

\RenewDocumentEnvironment{margintable}{o}
  {\begin{KFLTsidenotes@marginfloat}{table}}
  {\end{KFLTsidenotes@marginfloat}}
```

The following were changed by sidenotes, and now are reset back to their lwarp-supported originals:

Restoring the definition from the LaTeX 2$_\varepsilon$ `article.cls` source:

```
\renewenvironment{figure*}
               {\@dblfloat{figure}}
               {\end@dblfloat}

\renewenvironment{table*}
               {\@dblfloat{table}}
               {\end@dblfloat}
```

File 337 **lwarp-SIunits.sty**

§ 435 Package

SIunits

(*Emulates or patches code by* Marcel Heldoorn.)

Pkg SIunits SIunits is patched for use by lwarp.

It is recommended to use `\unit` where possible, which combines the entire expression into a single `lateximage`, and adds the `alt` tag containing the LaTeX code, allowing for copy/paste. When units are used outside of the `\unit` macro, each unit macro will have its own `lateximage`, and each will have the `alt` tag set according to `\MathImageAltText`, which defaults to `(math image)`.

for HTML output:

```
\LWR@ProvidesPackagePass{SIunits}[2007/12/02]
```

Patched for copy/paste with the HTML `alt` tag:

```
\DeclareRobustCommand{\unit}[2]{%
\@inunitcommandtrue%    original
\LWR@subsingledollar*%  lwarp
{% alt tag
    \textbackslash{}unit\{\LWR@HTMLsanitize{#1}\}%
        \{ \LWR@HTMLsanitize{#2}\}% extra space
}%
{SIunits}% add'l hashing
{%
    \LWR@origensuredmath{%  lwarp modification
        \SI@fstyle{#1\@qsk\period@active{#2}}%  original
    }%
}% contents
\@inunitcommandfalse%   original
}
```

File 338 **lwarp-siunitx.sty**

§ 436 Package siunitx

(*Emulates or patches code by* Joseph Wright.)

Pkg siunitx siunitx is patched for use by lwarp.

fractions Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJax script.

⚠ `tabular` Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

for HTML output:

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackagePass{siunitx}[2018/05/17]


\AtBeginDocument{% in case textcomp was not loaded
\DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
\DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
\DeclareSIUnit\elementarycharge{\textit{e}}
\DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
\DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
\DeclareSIUnit\planckbar{\LWR@siunitx@textplanckbar}
```

```
}% AtBeginDocument
```

\@ensuredmath is not supported inside an \hbox, so it must temporarily be restored to its original. Similar for \mbox. SVG math is created explicitly when necessary, using \LWR@subsingledollar.

```

\ExplSyntaxOn
%
```

Modified to set set HTML \textcolor if not black:

```
\cs_undefine:N \__siunitx_print_aux:
\cs_new_protected:Npn \__siunitx_print_aux:
  {
    \text
      {
        \__siunitx_ensure_ltr:n
          {
            \color@begingroup
            \__siunitx_print_color:
            \__siunitx_font_shape:
            \__siunitx_font_weight:
            \use:c
              {
                @@_ \l__siunitx_print_type_tl _
                text \l__siunitx_font_family_tl :
              }
            \bool_if:NTF \l__siunitx_font_math_mode_bool
              { \__siunitx_print_math: }
              {
                \LWR@findcurrenttextcolor% lwarp
                \ifdefstring{\LWR@tempcolor}{000000}% lwarp
                {\__siunitx_print_text:}% lwarp
                {% lwarp
                    \LWR@textcurrentcolor{% lwarp
                        \__siunitx_print_text:
                    }% lwarp
                }% lwarp
              }
            \color@endgroup
          }
      }
  }


\cs_undefine:N \__siunitx_set_math_fam:n
\cs_new_protected:Npn \__siunitx_set_math_fam:n #1 {
  \int_new:c { c__siunitx_math #1 _int }
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \hbox_set:Nn \l__siunitx_tmp_box
      {
        \ensuremath
```

```
          {
            \use:c { math #1 }
              {
                \int_gset:cn { c__siunitx_math #1 _int } { \fam }
              }
          }
      }
  \group_end:% lwarp
}

\cs_undefine:N \__siunitx_combined_output:n
\cs_new_protected:Npn \__siunitx_combined_output:n #1 {
    \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
  \bool_if:NTF \l__siunitx_number_parse_bool
    {
      \tl_clear:N \l__siunitx_number_out_tl
      \bool_set_false:N \l__siunitx_number_compound_bool
      \__siunitx_number_output_parse:n {#1}
    }
    {
      \__siunitx_unit_output_pre_print:
```

For `parse-numbers=false`:

```
%       \__siunitx_print:nn { number } { \ensuremath {#1} }
        \LWR@subsingledollar{% lwarp
            \textbackslash( \LWR@HTMLsanitize{#1} \textbackslash)% lwarp
        }{siunitx}{%
            \__siunitx_print:nn { number } {%
                \LWR@origensuredmath{#1}%
            }%
        }% lwarp


      \__siunitx_unit_output_print:
    }
    \group_end:% lwarp
}
%
```

For quotients, the fraction code is replaced by the symbol code:

```
\cs_undefine:N \__siunitx_number_output_quotient_fraction:
\cs_new_protected:Npn \__siunitx_number_output_quotient_fraction: {
  \bool_set_true:N \l__siunitx_number_compound_bool
  \__siunitx_number_output_quotient_aux_i:
  \tl_set_eq:NN \l__siunitx_number_out_tl
    \l__siunitx_number_numerator_tl
  \tl_put_right:NV \l__siunitx_number_out_tl \l__siunitx_output_quotient_tl
  \tl_put_right:NV \l__siunitx_number_out_tl
    \l__siunitx_number_denominator_tl
  \__siunitx_number_output_single_aux:
}
```

For units, the fraction code is replaced by the symbol code:

```
\cs_undefine:N \__siunitx_unit_format_fraction_fraction:
\cs_new_protected:Npn \__siunitx_unit_format_fraction_fraction: {
  \__siunitx_unit_format_fraction_symbol_aux:
  \int_compare:nNnT { \l__siunitx_unit_denominator_int } > { 1 }
    {
      \bool_if:NT \l__siunitx_unit_denominator_bracket_bool
        {
       \tl_put_left:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_open_tl
       \tl_put_right:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_close_tl
        }
    }
  \tl_set_eq:NN \l__siunitx_unit_tl \l__siunitx_unit_numerator_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_per_symbol_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_unit_denominator_tl
}


\cs_undefine:N \__siunitx_angle_print_astronomy_aux:
\cs_new_protected:Npn \__siunitx_angle_print_astronomy_aux: {
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-integer }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
 {% lateximage
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
    }
  \hbox_set:Nn \l__siunitx_angle_unit_box
    {
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \skip_horizontal:n { -\scriptspace }
    }
  \__siunitx_angle_print_astronomy_aux:n { marker }
  \__siunitx_angle_print_astronomy_aux:n { unit }
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \box_use:N \l__siunitx_angle_marker_box
      \box_use:N \l__siunitx_angle_unit_box
    }
  \dim_compare:nNnTF
    { \l__siunitx_angle_marker_dim } > { \l__siunitx_angle_unit_dim }
    { \__siunitx_angle_print_astronomy_marker: }
    { \__siunitx_angle_print_astronomy_unit: }
 }% lateximage
 {% not a lateximage
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
 }% not a lateximage
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-decimal }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
}
```

```
\RenewDocumentCommand \num { o m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_number_output:n {#2}
  \group_end:% lwarp
}

\RenewDocumentCommand \numrange { o m m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_range_numbers:nn {#2} {#3}
  \group_end:% lwarp
}

\RenewDocumentCommand \ang { o > { \SplitArgument { 2 } { ; } } m } {
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_angle_output:nnn #2
  \group_end:% lwarp
}

\RenewDocumentCommand \si { o m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_unit_output:nn {#2} { } }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_unit_output:nn {#2} {#1}
      }
  \group_end:% lwarp
}


\RenewDocumentCommand{\SIrange}{o m m m}
{%
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
```

```
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_range_unit:nnnn {#4} { } {#2} {#3} }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_range_unit:nnnn {#4} {#1} {#2} {#3}
      }
  \group_end:% lwarp
}

\ExplSyntaxOff
```

File 339 **lwarp-slantsc.sty**

§ 437 Package slantsc

(*Emulates or patches code by* Harald Harders.)

Pkg slantsc slantsc is emulated for HTML, and used as-is for print output.

for HTML output:

```
\LWR@ProvidesPackagePass{slantsc}[2012/01/01]

\newcommand*{\LWR@HTML@noscshape}{}
\LWR@formatted{noscshape}

\newcommand*{\LWR@null@noscshape}{}

\appto{\LWR@nullfonts}{%
\LetLtxMacro\noscshape\LWR@null@noscshape%
}
```

File 340 **lwarp-soul.sty**

§ 438 Package soul

(*Emulates or patches code by* Melchior FRANZ.)

Pkg soul soul is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{soul}[2003/11/17]
\RequirePackage{xcolor}% for \convertcolorspec
```

Storage for the colors to use:

```
\newcommand*{\LWR@soululcolor}{}

\newcommand*{\LWR@soulstcolor}{}

% \definecolor{LWR@soulhlcolordefault}{HTML}{F8E800}
```

```
% \newcommand*{\LWR@soulhlcolor}{LWR@soulhlcolordefault}
\newcommand*{\LWR@soulhlcolor}{}
```

\so {⟨*text*⟩}

Basic markup with CSS:

```
\newcommand{\so}[1]{%
\InlineClass(letter-spacing:.2ex){letterspacing}{#1}%
}
```

\caps {⟨*text*⟩}

```
\newcommand{\caps}[1]{%
    \InlineClass%
        (font-variant:small-caps;letter-spacing:.1ex)%
        {capsspacing}{#1}%
}
```

\LWR@soulcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@soulcolor}[5]{%
\ifcsempty{#2}%
{%
    \InlineClass(#5){#3}{#1}%
}%
{%
    \convertcolorspec{named}{\@nameuse{#2}}{HTML}\LWR@tempcolor%
    \LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}%
}%
}
```

```
\newcommand{\ul}[1]{%
\LWR@soulcolor{#1}{LWR@soululcolor}{uline}{text-decoration-color}%
    {text-decoration:underline; text-decoration-skip: auto;}%
}

\newcommand{\st}[1]{
\LWR@soulcolor{#1}{LWR@soulstcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
}

\newcommand{\hl}[1]{
\LWR@soulcolor{#1}{LWR@soulhlcolor}{highlight}{background-color}%
    {background:\LWR@origpound{}F8E800}
}
```

Nullified:

```
\newcommand*{\soulaccent}[1]{}
\newcommand*{\soulregister}[2]{}
\newcommand{\sloppyword}[1]{#1}
\newcommand*{\sodef}[5]{\DeclareRobustCommand*#1[1]{\so{##1}}}
```

```
\newcommand*{\resetso}{}
\newcommand*{\capsdef}[5]{}
\newcommand*{\capsreset}{}
\newcommand*{\capssave}[1]{}
\newcommand*{\capsselect}[1]{}
\newcommand*{\setul}[2]{}
\newcommand*{\resetul}{}
\newcommand*{\setuldepth}[1]{}
\newcommand*{\setuloverlap}[1]{}
```

Set colors:

```
\newcommand*{\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}
\newcommand*{\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}
\newcommand*{\sethlcolor}[1]{\renewcommand{\LWR@soulhlcolor}{#1}}
```

Long versions of the user-level macros:

```
\let\textso\so
\let\textul\ul
\let\texthl\hl
\let\textcaps\caps
```

File 341 **lwarp-soulpos.sty**

§ 439 Package

soulpos

(*Emulates or patches code by* Javier Bezos.)

Pkg soulpos soulpos is emulated.

for HTML output:

```
\RequirePackage{soul}
\RequirePackage{soulutf8}
\LWR@ProvidesPackageDrop{soulpos}[2012/02/25]

\NewDocumentCommand{\ulposdef}{m o m}{}

\newdimen\ulwidth

\newcommand\ifulstarttype[1]{%
\expandafter\@secondoftwo%
}

\newcommand\ifulendtype[1]{%
\expandafter\@secondoftwo%
}

\newcommand{\ulstarttype}{0}
\newcommand{\ulendtype}{0}
\newcommand\ulpostolerance{0}%
```

File 342 **lwarp-soulutf8.sty**

§ 440 Package soulutf8

Pkg soulutf8 soulutf8 is emulated.

lwarp's HTML output naturally supports UTF-8 encoding.

for HTML output:

```
\LWR@ProvidesPackageDrop{soulutf8}[2016/05/16]
\RequirePackage{soul}
```

File 343 **lwarp-splitidx.sty**

§ 441 Package splitidx

(*Emulates or patches code by* Markus Kohm.)

Pkg splitidx splitidx is patched for use by lwarp.

If the `latexmk` option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **`lwarpmk printindex`** and **`lwarpmk htmlindex`** will still be required.

⚠ `\thepage` When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to `\thepage` during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the `\index`-like action occurs, and then refer to `\arabic{LWR@autoindex}` instead of `\thepage` where the reference should occur.

See section 534.17 in the lwarp-patch-memoir package for the `\@@wrspindexhyp` macro as an example.

for HTML output:

```
\LWR@ProvidesPackagePass{splitidx}[2016/02/18]

\catcode`\_=12%
\xpatchcmd{\newindex}
    {\jobname-#2.idx}
    {\jobname-#2_html.idx}
    {}
    {\LWR@patcherror{splitidx}{@newindex}}
\catcode`\_=8%
```

Patched to use lwarp's automatic indexing counter instead of `\thepage`:

```
\renewcommand*{\@wrsindex}[2][]{%
  \ifx\relax#1\relax
    \if@splitidx
      \@wrsindex[idx]{#2}%
    \else
      \def\@tempa{#2}%
      \if@verbindex\@onelevel@sanitize\@tempa\fi
      \@wrindex{\@tempa}%
    \fi
  \else
    \def\@tempa{#2}%
    \csname index@#1@hook\endcsname
%     \expandafter\ifx\csname @@wrsindex\endcsname\relax
    \addtocounter{LWR@autoindex}{1}%                    lwarp
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
%       \@@@wrsindex{#1}{{\@tempa}{\thepage}}%
      \@@@wrsindex{#1}{{\@tempa}{\arabic{LWR@autoindex}}}%
%     \else
%       \def\@tempb{\@@wrsindex{#1}}%
%       \expandafter\@tempb\@tempa||\\%
%     \fi
    \endgroup
    \@esphack
  \fi
}
```

lwarp defines sectioning commands with xparse, so the below patches are done as temporary redefinitions instead of being `\let`.

```
\xpatchcmd{\printsubindex}
    {\let\section\subsection}
    {\renewcommand*{\section}{\subsection}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-section}}

\xpatchcmd{\printsubindex}
    {\let\chapter\section}
    {\renewcommand*{\chapter}{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}

\xpatchcmd{\printsubindex}
    {\let\@makechapterhead\section}
    {\def\@makechapterhead{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}
```

File 344 **lwarp-srcltx.sty**

§ 442 Package srcltx

Pkg srcltx srcltx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{srcltx}[2006/11/12]

\newif\ifSRCOK \SRCOKfalse
\newcommand*\srcIncludeHook[1]{}
\newcommand*\srcInputHook[1]{}
\newcommand*\MainFile{}
\def\MainFile{\jobname.tex}
\newcommand*\CurrentInput{}
\gdef\CurrentInput{\MainFile}
\newcommand\Input{}
\let\Input\input
```

File 345 **lwarp-srctex.sty**

§ 443 Package srctex

Pkg srctex srctex is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{srctex}[2006/11/12]
\LWR@origRequirePackage{lwarp-srcltx}
```

File 346 **lwarp-stabular.sty**

§ 444 Package stabular

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg stabular stabular is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{stabular}[2014/03/20]
```

Env stabular [⟨*vpos*⟩] {⟨*colspec*⟩}

```
\newenvironment{stabular}[2][c]
{
\begin{tabular}[#1]{#2}
\renewcommand{\noalign}[1]{}
}
{\end{tabular}}
```

Env stabular {⟨*width*⟩} [⟨*vpos*⟩] {⟨*colspec*⟩}

```
\NewDocumentEnvironment{stabular*}{m o m}
{
\begin{tabular}[#2]{#3}
\renewcommand{\noalign}[1]{}
}
{\end{tabular}}
```

File 347 **lwarp-stackengine.sty**

§ 445 Package

stackengine

(*Emulates or patches code by* Steven B. Segletes.)

Pkg stackengine stackengine is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{stackengine}[2017/02/13]
```

The original version is neccessary for the patched \@stack and \stackanchor, where nesting lateximages does not work:

```
\LetLtxMacro\LWR@orig@stackengine\stackengine

\renewcommand*{\stackengine}[8]{%
    \ifstrequal{#4}{O}%
        {\begin{lateximage}[\ImageAltText]}%
        {\begin{lateximage}[\ImageAltText][][vertical-align:top]}%
    \LWR@orig@stackengine{#1}{#2}{#3}{#4}{#5}{#6}{#7}{#8}%
    \end{lateximage}%
}
```

\@stack uses a lateximage with a vertical alignment:

```
\LetLtxMacro\LWR@orig@@stack\@stack

\xpatchcmd{\LWR@orig@@stack}{\stackengine}{\LWR@orig@stackengine}
    {}
    {\LWR@patcherror{stackengine}{LWR@orig@@stack}}

\renewcommand*{\@stack}[4]{%
    \ifstrequal{#3}{O}%
        {\begin{lateximage}[\ImageAltText]}%
        {\begin{lateximage}[\ImageAltText][][vertical-align:top]}%
    \LWR@orig@@stack{#1}{#2}{#3}{#4}%
    \end{lateximage}%
}
```

The lapping macros are disabled for HTML:

```
\newcommand*\LWR@HTML@@stacklap[4]{#3}
\LWR@formatted{@stacklap}
```

\stackanchor is patched for two instances of \stackengine. A lateximage with vertical alignment is used.

```
\xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
    {}
    {\LWR@patcherror{stackengine}{stackanchor patch 1}}
```

```
\xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
    {}
    {\LWR@patcherror{stackengine}{stackanchor patch 2}}

\xpretocmd{\stackanchor}
    {\begin{lateximage}[\ImageAltText][][vertical-align:middle]}
    {}
    {\LWR@patcherror{stackengine}{stackanchor pre}}

\xapptocmd{\stackanchor}{\end{lateximage}}
    {}
    {\LWR@patcherror{stackengine}{stackanchor app}}
```

\Centerstack is simply placed inside a lateximage with a vertical alignment:

```
\xpretocmd{\Centerstack}
    {\begin{lateximage}[\ImageAltText][][vertical-align:middle]}
    {}
    {\LWR@patcherror{stackengine}{Centerstack pre}}

\xapptocmd{\Centerstack}{\end{lateximage}}
    {}
    {\LWR@patcherror{stackengine}{Centerstack app}}
```

\savestack reverts to print mode while saving the box, then places it inside a lateximage when used:

```
\renewcommand*\savestack[2]{%
  \xdef\sv@name{\stack@macro@name{#1}}%
  \@ifundefined{\sv@name content}{%
    \expandafter\newsavebox\expandafter{\csname\sv@name content\endcsname}%
   }{}%
    \begingroup%    lwarp
    \LWR@restoreorigformatting%     lwarp
    \RenewDocumentEnvironment{lateximage}{s o s o o}{}{}% lwarp: inside group
  \expandafter\LWR@gsavebox\csname\sv@name content\endcsname{#2}%
  \expandafter\gdef\expandafter#1\expandafter{%
        \expandafter\begin\expandafter{lateximage\expandafter}%     lwarp
        \expandafter\usebox\expandafter%
        {\csname\sv@name content\endcsname}%
        \expandafter\end\expandafter{lateximage\expandafter}%       lwarp
    }%
    \endgroup%      lwarp
}
```

File 348 **lwarp-stfloats.sty**

§ 446 Package

stfloats

Pkg stfloats

stfloats is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{stfloats}[2017/03/27]
```

stfloats may have been preloaded by a ltj* class.

The following are provided in case they have not yet been defined:

```
\providecommand*{\fnbelowfloat}{}
\providecommand*{\fnunderfloat}{}
\providecommand*{\setbaselinefloat}{}
\providecommand*{\setbaselinefixed}{}
```

Nullified for HTML:

```
\renewcommand*{\fnbelowfloat}{}
\renewcommand*{\fnunderfloat}{}
\renewcommand*{\setbaselinefloat}{}
\renewcommand*{\setbaselinefixed}{}
```

File 349 **lwarp-struktex.sty**

§ 447 Package struktex

(*Emulates or patches code by* JOBST HOFFMANN.)

Pkg struktex struktex is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{struktex}[2018/06/04]

\BeforeBeginEnvironment{struktogramm}{%
    \begin{lateximage}[-struktex-~\PackageDiagramAltText]%
}
\AfterEndEnvironment{struktogramm}{\end{lateximage}}

\newenvironment{LWR@HTML@centernss}{\begin{center}}{\end{center}}
\LWR@formattedenv{centernss}

\newcommand{\LWR@HTML@CenterNssFile}[1]{%
    \begin{center}
    \input{#1.nss}
    \end{center}
}
\LWR@formatted{CenterNssFile}

\newcommand{\LWR@HTML@centernssfile}{\LWR@HTML@CenterNssFile}
\LWR@formatted{centernssfile}
```

File 350 **lwarp-subcaption.sty**

§ 448 Package subcaption

(*Emulates or patches code by* AXEL SOMMERFELDT.)

Pkg subcaption subcaption is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{subcaption}[2018/05/01]
```

Tells lwarp to ignore minipage widths inside a subfigure or subtable. In print mode the minipages are used to place the items next to each other. In HTML they are placed side-by-side automatically.

```
\ifdef{\subcaption@minipage}{
    \xpatchcmd{\subcaption@minipage}
        {\minipage}
        {\minipagefullwidth\minipage}
        {}
        {\LWR@patcherror{subcaption}{subcaption@minipage}}
}{}
```

Likewise for a \subcaptionbox:

```
\ifdef{\subcaptionbox}{
    \xpretocmd{\subcaptionbox}
        {\minipagefullwidth}
        {}
        {\LWR@patcherror{subcaption}{subcaptionbox}}
}{}
```

File 351 **lwarp-subfig.sty**

§ 449 Package

subfig

(*Emulates or patches code by* Steven Douglas Cochran.)

Pkg subfig subfig is supported and patched by lwarp.

⚠ lof/lotdepth At present, the package options for lofdepth and lotdepth are not working. These counters must be set separately after the package has been loaded.

In the document source, use \hfill and \hspace* subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

for HTML output: Accept all options for lwarp-subfig:

```
\LWR@ProvidesPackagePass{subfig}[2005/06/28]
```

\sf@@@subfloat {⟨*1 type*⟩} [⟨*2 LOF entry*⟩] [⟨*3 caption*⟩] {⟨*4 contents*⟩}

The outer minipage allows side-by-side subfloats with \hfill between.

```
\long\def\sf@@@subfloat#1[#2][#3]#4{%
\begin{minipage}{\linewidth}% lwarp
```

```
\IfValueTF{#2}{%
    \LWR@setlatestname{#2}%
}{%
    \IfValueTF{#3}{%
        \LWR@setlatestname{#3}%
    }{}%
}%
\LWR@stoppars% lwarp
    \@ifundefined{FBsc@max}{}%
        {\FB@readaux{\let\FBsuboheight\relax}}%
    \@tempcnta=\@ne
    \if@minipage
      \@tempcnta=\z@
    \else\ifdim \lastskip=\z@ \else
      \@tempcnta=\tw@
    \fi\fi
    \ifmaincaptiontop
      \sf@top=\sf@nearskip
      \sf@bottom=\sf@farskip
    \else
      \sf@top=\sf@farskip
      \sf@bottom=\sf@nearskip
    \fi
    \leavevmode

%     \setbox\@tempboxa \hbox{#4}%
%     \@tempdima=\wd\@tempboxa
%     \@ifundefined{FBsc@max}{}%
%         {\global\advance\Xhsize-\wd\@tempboxa
%          \dimen@=\ht\@tempboxa
%          \advance\dimen@\dp\@tempboxa
%          \ifdim\dimen@>\FBso@max
%            \global\FBso@max\dimen@
%          \fi}%
```

Do not use boxes, which interfere with `lateximages`:

```
%     \vtop%
    \bgroup
%       \vbox%
      \bgroup
        \ifcase\@tempcnta
          \@minipagefalse
        \or
%           \vskip\sf@top
        \or
          \ifdim \lastskip=\z@ \else
%             \@tempskipb\sf@top\relax\@xaddvskip
          \fi
        \fi
        \sf@ifpositiontop{%
          \ifx \@empty#3\relax \else
            \sf@subcaption{#1}{#2}{#3}%
%             \vskip\sf@capskip
%             \vskip\sf@captopadj
          \fi\egroup
```

```
%           \hrule width0pt height0pt depth0pt
            \LWR@startpars% lwarp
%  \box\@tempboxa
            #4
            \LWR@stoppars% lwarp
        }{%
        \LWR@startpars% lwarp
        \@ifundefined{FBsc@max}%
            {
%  \box\@tempboxa
                #4
            }%
            {\ifx\FBsuboheight\relax
%                \box\@tempboxa
                #4
             \else
%                \vbox to \FBsuboheight{\FBafil\box\@tempboxa\FBbfil}%
                #4
             \fi}%
        \LWR@stoppars% lwarp
          \egroup
          \ifx \@empty#3\relax \else
%             \vskip\sf@capskip
%             \hrule width0pt height0pt depth0pt
            \sf@subcaption{#1}{#2}{#3}%
         \fi
        }%
%       \vskip\sf@bottom
    \egroup
    \@ifundefined{FBsc@max}{}%
        {\addtocounter{FRobj}{-1}%
         \ifnum\c@FRobj=0\else
           \subfloatrowsep
         \fi}%
    \ifmaincaptiontop\else
      \global\advance\@nameuse{c@\@captype}\m@ne
    \fi
\end{minipage}% lwarp
\LWR@startpars% lwarp
  \endgroup\ignorespaces%
}%
```

\sf@subcaption {⟨*1 type*⟩} {⟨*2* LOF *entry*⟩} {⟨*3 caption*⟩}

```
\long\def\sf@subcaption#1#2#3{%
\LWR@stoppars% lwarp
  \ifx \relax#2\relax \else
    \bgroup
      \let\label=\@gobble
      \let\protect=\string
      \def\@subcaplabel{%
        \caption@lstfmt{\@nameuse{p@#1}}{\@nameuse{the#1}}}%
      \sf@updatecaptionlist{#1}{#2}{\the\value{\@captype}}{\the\value{#1}}%
    \egroup
  \fi
```

```
\bgroup
  \ifx \relax#3\relax
    \let\captionlabelsep=\relax
  \fi
%     \setbox0\vbox{%
%        \hb@xt@\the\@tempdima{%
%
% %          \hss
% %         \parbox[t]{\the\@tempdima}{%
%           \caption@make
%               {\@nameuse{sub\@captype name}}%
%               {\@nameuse{thesub\@captype}}%
%               {#3}
% %  }%
% %            \hss
%   }
%  }%
   \@ifundefined{FBsc@max}%
%         {\box0}%
       {
%  \parbox[t]{\the\@tempdima}{%
\LWR@traceinfo{sfsubcap B1}% lwarp
            \LWR@figcaption% lwarp
            \caption@make
                {\@nameuse{sub\@captype name}}%
                {\@nameuse{thesub\@captype}}%
                {\LWR@isolate{#3}}%

            \endLWR@figcaption% lwarp
\LWR@traceinfo{sfsubcap B2}% lwarp
%  }%
        }%
        {\dimen@\ht0%
         \advance\dimen@\dp0%
         \ifdim\dimen@>\FBsc@max
           \global\FBsc@max\dimen@
         \fi
         \FB@readaux{\let\FBsubcheight\relax}%
         \ifx\FBsubcheight\relax
           \def\next{
%  \parbox[t]{\the\@tempdima}
            }%
         \else
           \def\next{
%  \parbox[t][\FBsubcheight][t]{\the\@tempdima}
            }%
         \fi
%          \vbox{%
%            \hb@xt@\the\@tempdima{%

%              \hss
%              \next{%
\LWR@traceinfo{sfsubcap C1}% lwarp
               \caption@make
                   {\@nameuse{sub\@captype name}}%
                   {\@nameuse{thesub\@captype}}%
```

```
                    {#3}
\LWR@traceinfo{sfsubcap C1}% lwarp
%  }%
%               \hss
%  }
%            }
         }%
  \egroup
\LWR@startpars% lwarp
}
```

\subfloat@label Patches for \sf@sub@label:

```
\def\subfloat@label{%
\LWR@ensuredoingapar% lwarp
  \@ifnextchar(%   %) match left parenthesis
    {\sf@sub@label}
    {\sf@sub@label(Sub\@captype\space
                    \@ifundefined{thechapter}{}{\@nameuse{thechapter}\space}%
                    \@nameuse{p@sub\@captype}%
                    \@nameuse{thesub\@captype}.)}}
```

Patches for \subref.

\sf@subref {⟨*label*⟩}

The unstarred version uses a \ref link whose printed text comes from the sub@<label>:

```
\renewcommand{\sf@subref}[1]{%
\LWR@subnewref{#1}{sub@#1}%
}
```

\sf@@subref {⟨*label*⟩}

The starred version uses the printed sub@<label> which is stored as if it were a page number:

```
\renewcommand{\sf@@subref}[1]{\LWR@orig@pageref{sub@#1}}
```

Defining new subfloats. The l@sub<type> for each is redefined.

\@newsubfloat [⟨*keys/values*⟩] {⟨*float name*⟩}

```
\LetLtxMacro\LWR@orig@newsubfloat\@newsubfloat

\def\@newsubfloat[#1]#2{%
\LWR@orig@newsubfloat[#1]{#2}%
\renewcommand{\l@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
}
```

Pre-defined for figures and tables:

\l@subfigure {⟨*text*⟩} {⟨*pagenum*⟩}

```
\renewcommand{\l@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}
```

\l@subtable {⟨*text*⟩} {⟨*pagenum*⟩}

```
193 \renewcommand{\l@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
```

File 352 **lwarp-subfigure.sty**

§ 450 Package

subfigure

Pkg subfigure subfigure is emulated by subfig.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{subfigure}[2002/03/15]
2 \RequirePackage{subfig}

3 \LetLtxMacro\subfigure\subfloat
4 \LetLtxMacro\subtable\subfloat
5 \LetLtxMacro\Subref\subref
6 \@ifundefined{figuretopcaptrue}{\newif\iffiguretopcap}{}
7 \newif\ifsubfiguretopcap
8 \newif\ifsubcaphang
9 \newif\ifsubcapcenter
10 \newif\ifsubcapcenterlast
11 \newif\ifsubcapnooneline
12 \newif\ifsubcapraggedright
13 \newskip\subfigtopskip
14 \newskip\subfigcapskip
15 \newdimen\subfigcaptopadj
16 \newskip\subfigbottomskip
17 \newdimen\subfigcapmargin
18 \newskip\subfiglabelskip
19 \newcommand*{\subcapsize}{}
20 \newcommand*{\subcaplabelfont}{}
21 \newcommand*{\subcapfont}{}
```

File 353 **lwarp-supertabular.sty**

§ 451 Package

supertabular

(*Emulates or patches code by* Johannes Braams, Theo Jurriens.)

Pkg supertabular supertabular is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{supertabular}[2004/02/20]
```

⚠ Misplaced alignment tab character &

For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a `lateximage`.

```
\newcommand{\LWRST@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRST@firsthead{#1}%
}

\newcommand{\tablehead}[1]{}
\newcommand{\tabletail}[1]{}

\newcommand{\LWRST@lasttail}{}

\newcommand{\tablelasttail}[1]{%
    \long\gdef\LWRST@lasttail{#1}%
}


\newcommand{\tablecaption}[2][]{%
    \long\gdef\LWRST@caption{%
        \ifblank{#1}%
            {\caption{#2}}%
            {\caption[#1]{#2}}%
    }%
}

\let\topcaption\tablecaption
\let\bottomcaption\tablecaption


\newcommand*{\LWRST@caption}{}

\newcommand*{\shrinkheight}[1]{}

\NewDocumentEnvironment{supertabular}{s o m}
{%
\LWR@traceinfo{supertabular}%
\begin{table}%
\LWRST@caption%
\begin{tabular}{#3}%
\TabularMacro\ifdefvoid{\LWRST@firsthead}%
{\LWR@getmynexttoken}%
{\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
}%
{%
\ifdefvoid{\LWRST@lasttail}%
{}%
{%
\TabularMacro\ResumeTabular%
\LWRST@lasttail%
}%
\end{tabular}%
\end{table}%
```

```
\gdef\LWRST@caption{}%

\LWR@traceinfo{supertabular done}%
}

\NewDocumentEnvironment{mpsupertabular}{s o m}
{\minipage{\linewidth}\supertabular{#3}}
{\endsupertabular\endminipage}
```

File 354 **lwarp-syntonly.sty**

§ 452 Package syntonly

(*Emulates or patches code by* Frank Mittelbach, Rainer Schöpf.)

Pkg syntonly syntonly is ignored.

for HTML output: Discard all options for lwarp-syntonly:

```
\LWR@ProvidesPackageDrop{syntonly}[2017/06/30]

\newif\ifsyntax@
\syntax@false

\newcommand*{\syntaxonly}{}

\@onlypreamble\syntaxonly
```

File 355 **lwarp-tabfigures.sty**

§ 453 Package tabfigures

Pkg tabfigures tabfigures is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tabfigures}[2012/01/24]
```

File 356 **lwarp-tablefootnote.sty**

§ 454 Package tablefootnote

Pkg tablefootnote tablefootnote is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tablefootnote}[2014/01/26]
```

This works because in HTML tables are no longer floats.

```
\LetLtxMacro\tablefootnote\footnote
```

File 357 **lwarp-tabls.sty**

§ 455 Package tabls

(*Emulates or patches code by* DONALD ARSENEAU.)

Pkg tabls tabls is emulated. `\LWR@hline` is used to handle the optional argument when tabls is loaded.

for HTML output:

```
\LWR@ProvidesPackageDrop{tabls}

\newdimen\tablinesep
\newdimen\arraylinesep
\newdimen\extrarulesep
```

File 358 **lwarp-tabularx.sty**

§ 456 Package tabularx

(*Emulates or patches code by* DAVID CARLISLE.)

Pkg tabularx tabularx is emulated by lwarp.

for HTML output: Discard all options for lwarp-tabularx:

```
\LWR@ProvidesPackageDrop{tabularx}[2016/02/03]
\RequirePackage{array}

\DeclareDocumentEnvironment{tabularx}{m o m}
{\tabular{#3}}
{\endtabular}

\DeclareDocumentEnvironment{tabularx*}{m o m}
{\tabular{#3}}
{\endtabular}
```

File 359 **lwarp-tabulary.sty**

§ 457 Package tabulary

(*Emulates or patches code by* DAVID CARLISLE.)

Pkg tabulary tabulary is emulated by lwarp.

for HTML output: Discard all options for lwarp-tabulary.

Column types L, C, R, and J are emulated by lwarp core code.

```
\LWR@ProvidesPackageDrop{tabulary}[2014/06/11]
\RequirePackage{array}

\NewDocumentEnvironment{tabulary}{m o m}
{\tabular{#3}}
{\endtabular}

\NewDocumentEnvironment{tabulary*}{m o m}
{\tabular{#3}}
{\endtabular}

\newdimen\tymin
\newdimen\tymax
\def\tyformat{}
```

File 360 **lwarp-tascmac.sty**

§ 458 Package

tascmac

Pkg tascmac tascmac is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{tascmac}[2018/03/09]

\newenvironment*{boxnote}
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid black ;
            border-top: 1px dashed black ;
        ]{boxnote}
    }
    {\endBlockClass}

\newenvironment*{screen}[1][]
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
            border-radius: 8pt
        ]{boxnote}
    }
    {\endBlockClass}

\newenvironment*{itembox}[2][]
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
            border-radius: 8pt
```

```
        ]{boxnote}
        \InlineClass{itemboxtitle}{#2}\par
    }
    {\endBlockClass}

\newenvironment*{shadebox}
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid black ;
            box-shadow: 3px 3px 3px \#808080 ;
        ]{boxnote}
    }
    {\endBlockClass}

\newcommand*{\mask}[2]{%
    \InlineClass[background: lightgray]{mask}{#1}%
}

\newcommand*{\maskbox}[5]{%
    \InlineClass[background: lightgray]{mask}{#5}%
}

\newcommand*{\Maskbox}[6]{%
    \InlineClass[
        background: lightgray ;
        border: #5 solid black
    ]{mask}{#6}%
}

\newcommand*{\keytop}[2][]{%
    \InlineClass[%
        padding: .2ex ;
        border: 1px solid black ;
        border-radius: .7ex ;
    ]{keytop}{#2}%
}

\def\yen{\HTMLunicode{00A5}}

\def\return{\HTMLunicode{23CE}}

\def\Return{\HTMLunicode{23CE}}

\def\ascii{ASCII Corporation}

\def\Ascii{ASCII Corporation}

\def\ASCII{ASCII Corporation}
```

File 361 **lwarp-textarea.sty**

§ 459 Package textarea

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg textarea textarea is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{textarea}[2005/12/26]

\newcommand\StartFromTextArea{}
\newcommand\StartFromHeaderArea{}
\newcommand*\RestoreTextArea{}
\newcommand*\ExpandTextArea[1][*]{}
\let\NCC@restoretextarea\@empty
```

File 362 **lwarp-textcomp.sty**

§ 460 Package textcomp

(*Emulates or patches code by* Frank Mittelbach, Robin Fairbairns, Werner Lemberg.)

Pkg textcomp textcomp is patched for use by lwarp.

§ 460.1 Limitations

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols Many textcomp symbols are not supported by many system / browser fonts. In the css try referencing fonts which are more complete, but expect to see gaps in coverage.

§ 460.2 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{textcomp}[2017/04/05]
```

§ 460.3 HTML symbols

For HTML, use HTML entities or direct Unicode, depending on the engine.

`\AtBeginDocument` improves support for LuaLaTeX and XeLaTeX.

§ 460.3.1 pdfLaTeX symbols

```
\AtBeginDocument{
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@HTML@textdegree}{\HTMLentity{deg}}
\newcommand*{\LWR@HTML@textcelsius}{\HTMLunicode{2103}}
\newcommand*{\LWR@HTML@textohm}{\HTMLunicode{2126}}
\newcommand*{\LWR@HTML@textmu}{\HTMLunicode{00B5}}
\newcommand*{\LWR@HTML@textlquill}{\HTMLunicode{2045}}
\newcommand*{\LWR@HTML@textrquill}{\HTMLunicode{2046}}
\newcommand*{\LWR@HTML@textcircledP}{\HTMLunicode{2117}}
\newcommand*{\LWR@HTML@texttwelveudash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textmho}{\HTMLunicode{2127}}
\newcommand*{\LWR@HTML@textnaira}{\HTMLunicode{20A6}}
\newcommand*{\LWR@HTML@textpeso}{\HTMLunicode{20B1}}
\newcommand*{\LWR@HTML@textrecipe}{\HTMLunicode{211E}}
\newcommand*{\LWR@HTML@textinterrobang}{\HTMLunicode{203D}}
\newcommand*{\LWR@HTML@textinterrobangdown}{\HTMLunicode{2E18}}
\newcommand*{\LWR@HTML@textperthousand}{\HTMLunicode{2030}}
\newcommand*{\LWR@HTML@textpertenthousand}{\HTMLunicode{2031}}
\newcommand*{\LWR@HTML@textbaht}{\HTMLunicode{0E3F}}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{\HTMLunicode{2120}}
\else
```

§ 460.3.2 XeLaTeX and LuaLaTeX symbols

NOTE: Some of the following do not print well in the listing. Consult the .dtx or .sty file for the actual characters.

```
\newcommand*{\LWR@HTML@textdegree}{°}
\newcommand*{\LWR@HTML@textcelsius}{}
\newcommand*{\LWR@HTML@textohm}{}
\newcommand*{\LWR@HTML@textmu}{µ}
\newcommand*{\LWR@HTML@textlquill}{}
\newcommand*{\LWR@HTML@textrquill}{}
\newcommand*{\LWR@HTML@textcircledP}{}
\newcommand*{\LWR@HTML@texttwelveudash}{–}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{–}% emdash
\newcommand*{\LWR@HTML@textmho}{}
\newcommand*{\LWR@HTML@textnaira}{}
\newcommand*{\LWR@HTML@textpeso}{}
\newcommand*{\LWR@HTML@textrecipe}{}
\newcommand*{\LWR@HTML@textinterrobang}{}
\newcommand*{\LWR@HTML@textinterrobangdown}{}
\newcommand*{\LWR@HTML@textperthousand}{%}
\newcommand*{\LWR@HTML@textpertenthousand}{%}
\newcommand*{\LWR@HTML@textbaht}{}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{}
\fi

\LWR@formatted{textdegree}
```

```
\LWR@formatted{textcelsius}
\LWR@formatted{textohm}
\LWR@formatted{textmu}
\LWR@formatted{textlquill}
\LWR@formatted{textrquill}
\LWR@formatted{textcircledP}
\LWR@formatted{texttwelveudash}
\LWR@formatted{textthreequartersemdash}
\LWR@formatted{textmho}
\LWR@formatted{textnaira}
\LWR@formatted{textpeso}
\LWR@formatted{textrecipe}
\LWR@formatted{textinterrobang}
\LWR@formatted{textinterrobangdown}
\LWR@formatted{textperthousand}
\LWR@formatted{textpertenthousand}
\LWR@formatted{textbaht}
\LWR@formatted{textdiscount}
\LWR@formatted{textservicemark}
```

§ 460.4 HTML diacritics

For HTML, Unicode diacritical marks are used:

```
\newcommand*{\LWR@HTML@capitalcedilla}[1]{#1\HTMLunicode{0327}}
\newcommand*{\LWR@HTML@capitalogonek}[1]{#1\HTMLunicode{0328}}
\newcommand*{\LWR@HTML@capitalgrave}[1]{#1\HTMLunicode{0300}}
\newcommand*{\LWR@HTML@capitalacute}[1]{#1\HTMLunicode{0301}}
\newcommand*{\LWR@HTML@capitalcircumflex}[1]{#1\HTMLunicode{0302}}
\newcommand*{\LWR@HTML@capitaltilde}[1]{#1\HTMLunicode{0303}}
\newcommand*{\LWR@HTML@capitaldieresis}[1]{#1\HTMLunicode{0308}}
\newcommand*{\LWR@HTML@capitalhungarumlaut}[1]{#1\HTMLunicode{30B}}
\newcommand*{\LWR@HTML@capitalring}[1]{#1\HTMLunicode{30A}}
\newcommand*{\LWR@HTML@capitalcaron}[1]{#1\HTMLunicode{30C}}
\newcommand*{\LWR@HTML@capitalbreve}[1]{#1\HTMLunicode{306}}
\newcommand*{\LWR@HTML@capitalmacron}[1]{#1\HTMLunicode{304}}
\newcommand*{\LWR@HTML@capitaldotaccent}[1]{#1\HTMLunicode{307}}
```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with xunicode.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
\InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{capitalcedilla}
\LWR@formatted{capitalogonek}
\LWR@formatted{capitalgrave}
\LWR@formatted{capitalacute}
\LWR@formatted{capitalcircumflex}
\LWR@formatted{capitaltilde}
\LWR@formatted{capitaldieresis}
\LWR@formatted{capitalhungarumlaut}
\LWR@formatted{capitalring}
\LWR@formatted{capitalcaron}
```

```
\LWR@formatted{capitalbreve}
\LWR@formatted{capitalmacron}
\LWR@formatted{capitaldotaccent}
\LWR@formatted{textcircled}
```

Nullify textcomp macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobang}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify

}% AtBeginDocument
```

File 363 **lwarp-textfit.sty**

§ 461 Package textfit

Pkg `textfit` textfit is emulated.

Text is placed into a of class `textfit`. Sizes are approximated, and also limited by browser min/max font-size settings.

for HTML output:

```
\LWR@ProvidesPackageDrop{textfit}[1994/04/15]

\newsavebox{\LWR@textfitbox}

\newcommand*{\LWR@textfitscale}[2]{%
\setlength{\LWR@templengthone}{#1}%
\setlength{\LWR@templengthone}{%
    1em*\ratio{\LWR@templengthone}{\LWR@templengthtwo}%
}%
\InlineClass[font-size:\LWR@printlength{\LWR@templengthone}]{textfit}{#2}%
}

\newcommand*{\scaletowidth}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settowidth{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}

\newcommand*{\scaletoheight}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}
```

File 364 **lwarp-textpos.sty**

§ 462 Package textpos

(*Emulates or patches code by* Norman Gray.)

Pkg `textpos` textpos is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{textpos}[2019/04/15]

\NewDocumentEnvironment{textblock}{m o r()}{}{}
\NewDocumentEnvironment{textblock*}{m o r()}{}{}
\newcommand*{\TPGrid}[3][]{}
\NewDocumentCommand{\TPMargin}{s o}{}
\newcommand*{\textblockcolour}[1]{}
\newcommand*{\textblockrulecolour}[1]{}
\newcommand*{\textblockcolor}[1]{}
\newcommand*{\textblockrulecolor}[1]{}
\newcommand*{\tekstblokkulur}[1]{}
\newcommand*{\tekstblokrulekulur}[1]{}
\newlength{\TPHorizModule}
\newlength{\TPVertModule}
\newlength{\TPboxrulesize}
\newcommand{\textblocklabel}[1]{}
\newcommand*{\showtextsize}{}
\newcommand{\textblockorigin}[2]{}
```

```
\newcommand*{\TPoptions}[1]{}
\newcommand*{\TPReferencePosition}[1]{}
```

File 365 **lwarp-theorem.sty**

§ 463 Package

theorem

(*Emulates or patches code by* Frank Mittelbach.)

Pkg theorem theorem is patched for use by lwarp.

Table 16: Theorem package — css styling of theorems and proofs

Theorem: of class theorembody<theoremstyle>

Theorem Header: of class theoremheader

where <theoremstyle> is plain, break, etc.

for HTML output:

```
\LWR@ProvidesPackagePass{theorem}[2014/10/28]
```

§ 463.1 Remembering the theorem style

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
   \@ifundefined{th@#1}{\@warning
          {Unknown theoremstyle `#1'. Using `plain'}%
          \theorem@style{plain}%
           \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
          }%
      {%
          \theorem@style{#1}%
          \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
      }%
      \begingroup
        \csname th@\the\theorem@style \endcsname
      \endgroup}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
\gdef\@xnthm#1#2[#3]{%
   \expandafter\@ifdefinable\csname #1\endcsname
   {%
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
```

```
    \@definecounter{#1}\@newctr{#1}[#3]%
    \expandafter\xdef\csname the#1\endcsname
      {\expandafter \noexpand \csname the#3\endcsname
       \@thmcountersep \@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}%
    \expandafter \@tempa \expandafter{%
      \csname th@\the \theorem@style
            \expandafter \endcsname \the \theorem@bodyfont
     \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@ynthm#1#2{%
    \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \@definecounter{#1}%
    \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@othm#1[#2]#3{%
  \expandafter\ifx\csname c@#2\endcsname\relax
   \@nocounterr{#2}%
  \else
   \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \expandafter \xdef \csname the#1\endcsname
     {\expandafter \noexpand \csname the#2\endcsname}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#2}{#3}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
    }%
  \fi}
```

§ 463.2 css patches

The following are patched for css.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader`.

```
\gdef\th@plain{%
```

```
  \def\@begintheorem##1##2{%
        \item[
            \InlineClass{theoremheader}{##1\ ##2}
        ]
    }%
\def\@opargbegintheorem##1##2##3{%
   \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}
    ]
    }
}

\gdef\th@break{%
  \def\@begintheorem##1##2{%
    \item[
        \InlineClass{theoremheader}{##1\ ##2}\newline%
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
  \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}\newline
    ]
    }
}

\gdef\th@marginbreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}\newline
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1\ %
        (##3)}\newline
    ]
    }
}

\gdef\th@changebreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2\ ##1}\newline
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{ ##2\ ##1\ %
        (##3)}\newline
    ]
    }
}

\gdef\th@change{%
  \def\@begintheorem##1##2{
```

```
    \item[
        \InlineClass{theoremheader}{##2\ ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2\ ##1\ (##3)}
    ]
    }
}

\gdef\th@margin{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
            \InlineClass{theoremheader}{##2 \qquad ##1\ (##3)}
    ]
    }
}
```

Patched for css:

```
\gdef\@thm#1#2{\refstepcounter{#1}%
\LWR@forcenewpage% lwarp
    \BlockClass{theorembody\LWR@thisthmstyle}% lwarp
   \trivlist
   \@topsep \theorempreskipamount               % used by first \item
   \@topsepadd \theorempostskipamount           % used by \@endparenv
   \@ifnextchar [%
   {\@ythm{#1}{#2}}%
   {\@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}}

\gdef\@endtheorem{%
\endtrivlist
\endBlockClass
}
```

File 366 **lwarp-thinsp.sty**

§ 464 Package

thinsp

Pkg thinsp thinsp is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{thinsp}[2016/10/02]

\AtBeginDocument{
\let\thinthinspace\relax% defined by some packages
\newcommand*{\thinthinspace}{\thinspace}
```

```
}

\newcommand*{\stretchthinspace}{\thinspace}
\newcommand*{\stretchthinthinspace}{\thinthinspace}
\newcommand*{\stretchnegthinspace}{\negthinspace}
```

File 367 **lwarp-threadcol.sty**

§ 465 Package threadcol

Pkg threadcol threadcol is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{threadcol}[2013/01/06]

\newcommand{\setthreadname}[1]{}
```

File 368 **lwarp-threeparttable.sty**

§ 466 Package threeparttable

(*Emulates or patches code by* Donald Arseneau.)

Pkg threeparttable threeparttable is emulated.

Table note are contained inside a css of class tnotes. If enumitem is used, the note item labels are also individually highlighted with an additional css of class tnoteitemheader, otherwise they are plain text.

for HTML output:

```
\LWR@ProvidesPackageDrop{threeparttable}[2003/06/13]
```

Env threeparttable [⟨*alignment*⟩]

```
\newenvironment*{threeparttable}[1][b]
    {\def\@captype{table}}
    {}
```

Env tablenotes [⟨*options*⟩]

```
\newenvironment*{tablenotes}[1][]
{%
\LWR@forcenewpage
\BlockClass{tnotes}%

\description%
}
{%
\enddescription%
\endBlockClass%
}
```

\tnote {⟨*text*⟩}

```
\newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}
```

Env measuredfigure [⟨*alignment*⟩]

```
\newenvironment*{measuredfigure}[1][t]
   {\def\@captype{figure}}
   {}
```

File 369 **lwarp-threeparttablex.sty**

§ 467 Package

threeparttablex

Pkg threeparttablex threeparttablex is patched for use by lwarp.

threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width The table notes are created using a \multicolumn. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use \UseMinipageWidths before \insertTableNotes. The width is then specified, and in many cases the result is an improvement in overall table layout.

for HTML output:

```
\LWR@ProvidesPackagePass{threeparttablex}[2013/07/23]
```

The width is guessed depending on the number of columns, then limited to a min/max.

```
\renewcommand\insertTableNotes{%
   \setlength{\LWR@templengthone}{.375in*\value{LWR@tabletotalLaTeXcols}}%
   \setlength{\LWR@templengthone}{\minof{\textwidth}{\LWR@templengthone}}%
   \setlength{\LWR@templengthone}{\maxof{2.5in}{\LWR@templengthone}}%
  \multicolumn{\value{LWR@tabletotalLaTeXcols}}{c}{%
```

```
      \parbox{\LWR@templengthone}{%
        \begin{tablenotes}[\TPTL@optarg]%
          \TPTL@font%
          \TPTL@body%
        \end{tablenotes}%
      }%
  }%
}

\renewcommand\TPTL@tnotex[2]{\tnote{\nameref{#2}}}
```

File 370 **lwarp-thumb.sty**

§ 468 Package thumb

Pkg thumb thumb is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{thumb}[1997/12/24]

\newcommand*{\Overviewpage}{}
\newlength{\thumbheight}
\newlength{\thumbwidth}
```

File 371 **lwarp-thumbs.sty**

§ 469 Package thumbs

Pkg thumbs thumbs is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{thumbs}[2014/03/09]

\newcommand{\addthumb}[4]{}
\newcommand{\addtitlethumb}[5]{}
\newcommand{\stopthumb}{}
\newcommand{\continuethumb}{}
\newcommand{\thumbsoverview}[1]{}
\newcommand{\thumbsoverviewback}[1]{}
\newcommand{\thumbsoverviewverso}[1]{}
\newcommand{\thumbsoverviewdouble}[1]{}
\newcommand{\thumbnewcolumn}{}
\newcommand{\addthumbsoverviewtocontents}[2]{}
\newcommand{\thumbsnophantom}{}
```

File 372 **lwarp-tikz.sty**

§ 470 Package tikz

(*Emulates or patches code by* Till Tantau.)

Pkg tikz — tikz is supported.

⚠ displaymath and matrices — If using display math with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the tikz expression must be replaced with `\&`.

Accept all options for lwarp-tikz:

```
\LWR@ProvidesPackagePass{tikz}[2015/08/07]
```

catcodes — lwarp changes the catcode of `$` for its own use. The Ti*k*z `babel` library temporarily changes catcodes back to normal for Ti*k*z's use. tikz v3.0.0 introduced the `babel` library which handles catcode changes. For older versions, lwarp must change `$`'s catcode itself.

Also see:
https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded

```
\newbool{LWR@tikzbabel}

\@ifpackagelater{tikz}{2013/12/20}% Test for Tikz version v3.0.0
{\usetikzlibrary{babel}\booltrue{LWR@tikzbabel}}
{\boolfalse{LWR@tikzbabel}}
```

Env pgfpicture — The `\pgfpicture` environment is enclosed inside a `\lateximage`. Enclose the low-level `\pgfpicture` in a `lateximage`. This is also used by the higher-level `\tikz` and `tikzpicture`.

```
\preto\pgfpicture{%
    \begin{lateximage}[-tikz-~\PackageDiagramAltText]%
    \ifbool{LWR@tikzbabel}% Test for Tikz version v3.0.0
    {}%
    {\catcode`\$=3}% dollar sign is math shift
}

\appto\endpgfpicture{\end{lateximage}}
```

Ti*k*z is placed inside an SVG image, so use the original meanings of the following:

```
\LetLtxMacro\pgfutil@minipage\LWR@print@minipage
\let\pgfutil@endminipage\endLWR@print@minipage

\let\pgfutil@raggedleft\LWR@print@raggedleft
\let\pgfutil@raggedright\LWR@print@raggedright

\def\pgfutil@font@tiny{\LWR@printtiny}
\def\pgfutil@font@scriptsize{\LWR@printscriptsize}
\def\pgfutil@font@footnotesize{\LWR@printfootnotesize}
```

```
\def\pgfutil@font@small{\LWR@print@small}
\def\pgfutil@font@normalsize{\LWR@print@normalsize}
\def\pgfutil@font@large{\LWR@printlarge}
\def\pgfutil@font@Large{\LWR@printLarge}
\def\pgfutil@font@huge{\LWR@printhuge}
\def\pgfutil@font@Huge{\LWR@printHuge}

\def\pgfutil@font@itshape{\LWR@origitshape}
\def\pgfutil@font@bfseries{\LWR@origbfseries}

\def\pgfutil@font@normalfont{\LWR@orignormalfont}
```

File 373 **lwarp-titleps.sty**

§ 471 Package

titleps

(*Emulates or patches code by* Javier Bezos.)

Pkg titleps

titleps is loaded and used by lwarp during HTML output. All user options and macros are ignored and disabled.

Discard all options for lwarp-titleps:

for HTML output:

```
\LWR@ProvidesPackageDrop{titleps}[2016/03/15]
```

\pagestyle and \thispagestyle are already disabled in the lwarp code.

\newpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\newpagestyle}{m o m}{}
```

\renewpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\renewpagestyle}{m o m}{}
```

\sethead [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\sethead}{o o o m m m}{}
```

\setfoot [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\setfoot}{o o o m m m}{}
```

\settitlemarks * {⟨*names*⟩}

```
\NewDocumentCommand{\settitlemarks}{s m}{}
```

\headrule

```
\newcommand*{\headrule}{}
```

\footrule

```
\newcommand*{\footrule}{}
```

\setheadrule {⟨*length*⟩}

```
\newcommand*{\setheadrule}[1]{}
```

\setfootrule {⟨*length*⟩}

```
\newcommand*{\setfootrule}[1]{}
```

\makeheadrule

```
\newcommand*{\makeheadrule}{}
```

\makefootrule

```
\newcommand*{\makefootrule}{}
```

\setmarkboth {⟨*code*⟩}

```
\newcommand{\setmarkboth}[1]{}
```

\widenhead

```
\NewDocumentCommand{\widenhead}{s o o m m}{}
```

\bottitlemarks

```
\newcommand*{\bottitlemarks}{}
```

\toptitlemarks

```
\newcommand*{\toptitlemarks}{}
```

\firsttitlemarks

```
\newcommand*{\firsttitlemarks}{}
```

\nexttitlemarks

```
\newcommand*{\nexttoptitlemarks}{}
```

\outertitlemarks

```
\newcommand*{\outertitlemarks}{}
```

\innertitlemarks

```
\newcommand*{\innertitlemarks}{}
```

\newtitlemark * {⟨*name*⟩}

```
\NewDocumentCommand{\newtitlemark}{s m}{}
```

\pretitlemark * {⟨*section*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\pretitlemark}{s m m}{}
```

\ifsamemark {⟨*group*⟩} {⟨*command*⟩} {⟨*true*⟩} {⟨*false*⟩}

```
\newcommand{\ifsamemark}[4]{}
```

\setfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\setfloathead}{s o o o m m m m m}{}
```

\setfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\setfloatfoot}{s o o o m m m m m}{}
```

\nextfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\nextfloathead}{s o o o m m m m m}{}
```

\nextfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\nextfloatfoot}{s o o o m m m m m}{}
```

\newmarkset {⟨*markset*⟩}

```
\newcommand{\newmarkset}[1]{}
```

\newextramark * {⟨*markset*⟩} {⟨*macro-name*⟩}

```
\NewDocumentCommand{\newextramarkset}{s m m}{}
```

\botextramarks {⟨*markset*⟩}

```
\newcommand{\botextramarks}[1]{}
```

\topextramarks {⟨*markset*⟩}

```
\newcommand{\topextramarks}[1]{}
```

\firstextramarks {⟨*markset*⟩}

```
\newcommand{\firstextramarks}[1]{}
```

\nextextramarks {⟨*markset*⟩}

```
\newcommand{\nexttopextramarks}[1]{}
```

\outerextramarks {⟨*markset*⟩}

```
\newcommand{\outerextramarks}[1]{}
```

\innerextramarks {⟨*markset*⟩}

```
\newcommand{\innerextramarks}[1]{}
```

File 374 **lwarp-titleref.sty**

§ 472 Package titleref

Pkg titleref titleref is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{titleref}[2001/04/05]

\LetLtxMacro\titleref\nameref

\providecounter{LWR@currenttitle}

\newcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}

\newcommand*{\theTitleReference}[2]{}
```

File 375 **lwarp-titlesec.sty**

§ 473 Package titlesec

(*Emulates or patches code by* Javier Bezos.)

Pkg titlesec titlesec is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titlesec:

for HTML output:

```
\LWR@ProvidesPackageDrop{titlesec}[2016/03/21]
```

\titlelabel {⟨*label-format*⟩}

```
\newcommand*{\titlelabel}[1]{}
```

\titleformat* {⟨*command*⟩} {⟨*format*⟩}

\titleformat {⟨*command*⟩} [⟨*shape*⟩] {⟨*format*⟩} {⟨*label*⟩} {⟨*sep*⟩} {⟨*begfore*⟩} [⟨*after*⟩]

```
\newcommand\titleformat{%
  \@ifstar{\ttl@format@s}%
```

```
          {\ttl@format@i}}
\newcommand{\ttl@format@s}[1]{}
\NewDocumentCommand{\ttl@format@i}{m o m m m m o}{}
```

\chaptertitlename

```
\@ifundefined{@chapapp}{\let\@chapapp\chaptername}{}
\newcommand\chaptertitlename{\@chapapp}
```

\titlespacing * {⟨*command*⟩} {⟨*left*⟩} {⟨*before*⟩} {⟨*after*⟩} [⟨*right*⟩]

```
\NewDocumentCommand{\titlespacing}{s m m m m o}{}
```

\filright

```
\newcommand*{\filright}{}
```

\filcenter

```
\newcommand*{\filcenter}{}
```

\filleft

```
\newcommand*{\filleft}{}
```

\fillast

```
\newcommand*{\fillast}{}
```

\filinner

```
\newcommand*{\filinner}{}
```

\filouter

```
\newcommand*{\filouter}{}
```

\wordsep

```
\newcommand\wordsep{\fontdimen\tw@\font \@plus
  \fontdimen\thr@@\font \@minus \fontdimen4\font}
```

\titleline * [⟨*align*⟩] {⟨*material*⟩}

```
\NewDocumentCommand{\titleline}{s o m}{}
```

\titlerule [⟨*height*⟩]

```
\providecommand*\titlerule{\@ifstar{\ttl@row}{\ttl@rule}}
\newcommand*{\ttl@rule}[1][]{}
\newcommand*{\ttl@row}[2][]{}
```

\iftitlemeasuring {⟨*true*⟩} {⟨*false*⟩}

```
23 \newcommand{\iftitlemeasuring}[2]{#2}
```

\assignpagestyle {⟨*command*⟩} {⟨*pagestyle*⟩}

```
24 \newcommand{\assignpagestyle}[2]{#2}
```

\titleclass {⟨*name*⟩} [⟨*startlevel*⟩] {⟨*class*⟩} [⟨*cmd*⟩]

```
25 \NewDocumentCommand{\titleclass}{m o m o}
```

File 376 **lwarp-titletoc.sty**

§ 474 Package

titletoc

(*Emulates or patches code by* Javier Bezos.)

Pkg titletoc titletoc is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titletoc:

for HTML output:

```
1 \LWR@ProvidesPackageDrop{titletoc}[2011/12/15]
```

\dottedcontents {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*label*⟩} {⟨*leader*⟩}

```
2 \NewDocumentCommand{\dottedcontents}{m o m m m}{}
```

\titlecontents * {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*numbered*⟩} {⟨*numberless*⟩} {⟨*filler*⟩} [⟨*below or begin*⟩] [⟨*separator*⟩] [⟨*end*⟩]

```
3 \newcommand{\titlecontents}{\@ifstar{\ttl@tcstar}{\ttl@tcnostar}}
4 \NewDocumentCommand{\ttl@tcstar}{m o m m m m o o o}{}
5 \NewDocumentCommand{\ttl@tcnostar}{m o m m m m o}{}
```

\contentsmargin [⟨*correction*⟩] {⟨*right*⟩}

```
6 \newcommand{\contentsmargin}[2][]{}
```

\thecontentslabel

```
7 \newcommand*{\thecontentslabel}{thecontentslabel}
```

\thecontentspage

```
8 \newcommand*{\thecontentspage}{thecontentspage}
```

\contentslabel [⟨*format*⟩] {⟨*space*⟩}

```
9 \newcommand{\contentslabel}[2][]{\thecontentslabel}
```

\contentspage [⟨*format*⟩]

```
10 \newcommand{\contentspage}[1][]{\thecontentspage}
```

\contentspush {⟨*text*⟩}

```
11 \newcommand{\contentspush}[1]{}
```

\contentsuse {⟨*name*⟩} {⟨*text*⟩}

```
12 \newcommand{\contentsuse}[2]{}
```

\startcontents [⟨*name*⟩]

```
13 \newcommand*{\startcontents}[1][]{}
```

\stopcontents [⟨*name*⟩]

```
14 \newcommand*{\stopcontents}[1][]{}
```

\resumecontents [⟨*name*⟩]

```
15 \newcommand*{\resumecontents}[1][]{}
```

\printcontents [⟨*name*⟩] {⟨*prefix*⟩} {⟨*start*⟩} {⟨*code*⟩}

```
16 \newcommand{\printcontents}[4][]{}
```

\startlist [⟨*name*⟩] {⟨*list*⟩}

```
17 \newcommand{\startlist}[2][]{}
```

\stoplist [⟨*name*⟩] {⟨*list*⟩}

```
18 \newcommand{\stoplist}[2][]{}
```

\resumelist [⟨*name*⟩] {⟨*list*⟩}

```
19 \newcommand{\resumelist}[2][]{}
```

\printlist [⟨*name*⟩] {⟨*list*⟩} {⟨*prefix*⟩} {⟨*code*⟩}

```
20 \newcommand{\printlist}[4][]{}
```

File 377 **lwarp-titling.sty**

§ 475 Package

titling

(*Emulates or patches code by* Peter Wilson.)

Pkg titling

package support
⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

The various titling footnote restyling commands have no effect.

Pass all options to lwarp-titling:

for HTML output:

```
\LWR@ProvidesPackagePass{titling}[2009/09/04]
```

\@bsmtitlempty

Patch \@bsmtitlempty:

```
\let\LWR@orig@bsmtitlempty\@bsmtitlempty
\renewcommand*{\@bsmtitlempty}{%
\LWR@orig@bsmtitlempty%
}
```

\keepthetitle

Patch \keepthetitle:

```
\let\LWR@origkeepthetitle\keepthetitle
\renewcommand*{\keepthetitle}{%
\LWR@orig@keepthetitle%
}
```

\killtitle

Patch \killtitle:

```
\let\LWR@origkilltitle\killtitle
\renewcommand*{\killtitle}{%
\LWR@orig@killtitle%
}
```

Env titlingpage

```
\renewenvironment*{titlingpage}
{%
```

Start an HTML titlepage div:

```
\LWR@printpendingfootnotes
\begin{titlepage}
```

Prepare for a custom version of \maketitle inside the titlingpage:

```
\LWR@maketitlesetup
\let\maketitle\LWR@titlingmaketitle
}
{
```

At the end of the environment, end the HTML titlepage div:

```
\end{titlepage}
}
```

Patch the pre/post title/author/date to add HTML tags, then initilize:

```
\pretitle{}
\posttitle{}

\preauthor{}
\postauthor{}

\predate{}
\postdate{}
```

`\LWR@maketitlesetup` Patches `\thanks` macros.

```
\renewcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
\def\@makefnmark{\textsuperscript{\@thefnmark}}
```

`\thefootnote` ⇒ `\nameuse{arabic}{footnote}`, or
`\thefootnote` ⇒ `\nameuse{fnsymbol}{footnote}`

Redefine the footnote text:

```
\long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
\makethanksmark~%
```

`\makethanksmark` ⇒ `\thanksfootmark` ⇒ `\tamark` ⇒
`\@thefnmark` ⇒ `\itshape` a (or similar)

Print the text:

```
##1%
}% \@makefntext
}
```

`\thanksfootmark`

```
\renewcommand{\thanksfootmark}{%
%   \hb@xt@\thanksmarkwidth{\hfil\normalfont%
        \thanksscript{%
            \thanksfootpre \tamark \thanksfootpost%
        }%
%   }%
}
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage is used for all classes.

```
\begin{titlepage}
```

Select which kind of footnote marks to use:

```
\@bsmarkseries
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\LWR@stoppars\@thanks\LWR@startpars
```

Close the HTML titlepage div:

```
\end{titlepage}
```

Reset the footnote counter:

```
\@bscontmark
}
```

\@maketitle Typesets the title, etc. Patched for HTML.

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \maketitlehooka
    {
        \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
        \@bspretitle \@title \@bsposttitle%
        \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
    }
    \maketitlehookb
    {
        \begin{BlockClass}{author}
        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }
        \begin{BlockClass}{oneauthor}%
```

```
        \@bspreauthor \@author  \@bspostauthor%
        \end{BlockClass}%
        \end{BlockClass}%
    }
    \maketitlehookc
    {
        \begin{BlockClass}{titledate}%
        \@bspredate \@date \@bspostdate%
        \end{BlockClass}%
    }
    \maketitlehookd
}
```

`\LWR@titlingmaketitle` `\maketitle` for use inside an HTML `titlingpage` environment.

```
\renewcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\LWR@stoppars\@thanks\LWR@startpars
```

Select which kind of footnote marks to use:

```
\@bsmarkseries
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any `\thanks` footnotes:

```
\LWR@stoppars\@thanks\LWR@startpars
```

Reset the footnote counter:

```
\@bscontmark
}
```

`\thanksmarkseries` {⟨*series*⟩}

Sets the type of footnote marks used by `\thanks`, where type is 'arabic', 'roman', 'fnsymbol', etc.

```
\renewcommand{\thanksmarkseries}[1]{%
\def\@bsmarkseries{\renewcommand{\thefootnote}{\@nameuse{#1}{footnote}}}%
}
```

Set default titlepage thanks footnote marks. See section 66.7.

```
\@ifclassloaded{memoir}{
   \thanksmarkseries{arabic}
}{% not memoir
\if@titlepage
   \thanksmarkseries{arabic}
\else
   \thanksmarkseries{fnsymbol}
\fi
}% not memoir
```

File 378 **lwarp-tocbasic.sty**

§ 476 Package

tocbasic

(*Emulates or patches code by* Markus Kohm.)

Pkg tocbasic tocbasic is nullified for lwarp.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackagePass{tocbasic}[2018/12/30]

\DeclareDocumentCommand{\usetocbasicnumberline}{o}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntry}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntries}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCEntryStyle}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryOption}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryBooleanOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryCommandOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryIfOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryLengthOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryNumberOption}{m o m m m}{}
\DeclareDocumentCommand{\CloneTOCEntryStyle}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleInitCode}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleStartInitCode}{m m}{}
```

File 379 **lwarp-tocbibind.sty**

§ 477 Package

tocbibind

(*Emulates or patches code by* Peter Wilson.)

Pkg tocbibind tocbibind is patched for use by lwarp.

placement and TOC options An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex

numbered index section

Use the tocbibind numindex option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

for HTML output:

```
\let\simplechapterdelim\relax

\LWR@ProvidesPackagePass{tocbibind}[2010/10/13]


\renewenvironment{theindex}%
{%
    \if@bibchapter
       \if@donumindex
           \chapter{\indexname}
       \else
         \if@dotocind
           \chapter*{\indexname}
           \addcontentsline{toc}{chapter}{\LWR@isolate{\indexname}}
         \else
           \chapter*{\indexname}
```

```
          \fi
        \fi
     \else
        \if@donumindex
            \section{\indexname}
        \else
          \if@dotocind
            \section*{\indexname}
            \addcontentsline{toc}{\@tocextra}{\LWR@isolate{\indexname}}
          \else
            \section*{\indexname}
          \fi
        \fi
     \fi
\let\item\LWR@indexitem%
\let\subitem\LWR@indexsubitem%
\let\subsubitem\LWR@indexsubsubitem%
}{}
```

The following code is shared by anonchap.

```
\DeclareDocumentCommand{\simplechapter}{O{\@empty}}{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\DeclareDocumentCommand{\restorechapter}{}{%
\let\@chapcntformat\@seccntformat%
}
```

File 380 **lwarp-tocdata.sty**

§ 478 Package

tocdata

(*Emulates or patches code by* Brian Dunn.)

Pkg tocdata tocdata is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{tocdata}[2019/07/06]

\renewcommand*{\LWR@maybetocdata}{%
    \ifdefempty{\TD@thistocdata}{}{%
        \qquad \InlineClass{authorartist}{\tocdataformat{\TD@thistocdata}}%
        \def\TD@thistocdata{}
    }
}

\renewrobustcmd{\tocdatapartprint}[4]
{%
    \InlineClass{authorartist}{%
```

```
        \qquad --- %
        \TDoptionalnameprint{#1}\TDoptionalnameprint{#2}#3#4%
    }%
}

\@ifundefined{chapter}{}{
    \let\tocdatachapterprint\tocdatapartprint
}
\let\tocdatasectionprint\tocdatapartprint
\let\tocdatasubsectionprint\tocdatapartprint

\newcommand*{\LWR@TD@settextalign}[1]{%
    \def\LWR@TD@textalign{justify}%
    \ifcsstring{TD@#1align}{\centering}%
        {\def\LWR@TD@textalign{center}}%
        {}%
    \ifcsstring{TD@#1align}{\raggedleft}%
        {\def\LWR@TD@textalign{right}}%
        {}%
    \ifcsstring{TD@#1align}{\raggedright}%
        {\def\LWR@TD@textalign{left}}%
        {}%
}

\renewcommand{\TDartistauthorprint}[5]{%
    \LWR@TD@settextalign{#1}%
    \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
   \InlineClass{authorartist}{\TDoptionalnameprint{#2}\TDoptionalnameprint{#3}#4#5}%
    \end{BlockClass}%
}

\newcommand*{\LWR@TD@setnamealign}[1]{%
    \def\LWR@TD@textalign{justify}%
    \ifcsstring{TD@#1textalign}{\centering}%
        {\def\LWR@TD@textalign{center}}%
        {}%
    \ifcsstring{TD@#1textalign}{\raggedleft}%
        {\def\LWR@TD@textalign{right}}%
        {}%
    \ifcsstring{TD@#1textalign}{\raggedright}%
        {\def\LWR@TD@textalign{left}}%
        {}%
}

\renewcommand{\TDartistauthortextprint}[2]{%
    \LWR@TD@setnamealign{#1}%
    \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
    #2%
    \end{BlockClass}%
}
```

File 381 **lwarp-tocenter.sty**

§ 479 Package tocenter

Pkg tocenter tocenter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tocenter}[2004/12/09]

\NewDocumentCommand{\ToCenter}{s o m m}{}
\NewDocumentCommand{\FromMargins}{s o m m m m}{}
```

File 382 **lwarp-tocloft.sty**

§ 480 Package tocloft

(*Emulates or patches code by* Peter Wilson.)

Pkg tocloft tocloft is emulated. Most user options and macros are ignored and disabled. `\newlistof` and `\cftchapterprecis` are supported.

Pkg tocloft ⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

Discard all options for lwarp-tocloft:

for HTML output:

```
\LWR@ProvidesPackageDrop{tocloft}[2017/08/31]
```

`\tocloftpagestyle` {⟨*style*⟩}

```
\newcommand{\tocloftpagestyle}[1]{}
```

`\cftmarktoc`

```
\newcommand*{\cftmarktoc}{}
```

`\cfttoctitlefont`

```
\newcommand*{\cfttoctitlefont}{}
```

`\cftaftertoctitle`

```
\newcommand*{\cftaftertoctitle}{}

\newlength{\cftbeforetoctitleskip}
\newlength{\cftaftertoctitleskip}
```

\cftmarklof

```
\newcommand*{\cftmarklof}{}
```

\cftloftitlefont

```
\newcommand*{\cftloftitlefont}{}
```

\cftafterloftitle

```
\newcommand*{\cftafterloftitle}{}

\newlength{\cftbeforeloftitleskip}
\newlength{\cftafterloftitleskip}
```

\cftmarklot

```
\newcommand*{\cftmarklot}{}
```

\cftlottitlefont

```
\newcommand*{\cftlottitlefont}{}
```

\cftafterlottitle

```
\newcommand*{\cftafterlottitle}{}

\newlength{\cftbeforelottitleskip}
\newlength{\cftafterlottitleskip}
```

\cftdot

```
\providecommand*{\cftdot}{.}
```

\cftdotsep

```
\providecommand*{\cftdotsep}{1}
```

\cftnodots

```
\providecommand*{\cftnodots}{5000}
```

\cftdotfill {⟨*sep*⟩}

```
\providecommand{\cftdotfill}[1]{}
```

\cftsetpnumwidth {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetpnumwidth}{m}{}
```

\cftsetrmarg {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetrmarg}{m}{}
```

\cftpnumalign {⟨*alignment*⟩}

```
\DeclareDocumentCommand{\cftpnumalign}{m}{}

\LWR@providelength{\cftparskip}
```

The part-related items are also provided by memoir:

```
\LWR@providelength{\cftbeforepartskip}
\LWR@providelength{\cftpartindent}
\LWR@providelength{\cftpartnumwidth}
\providecommand*{\cftpartfont}{}
\providecommand*{\cftpartpresnum}{}
\providecommand*{\cftpartaftersnum}{}
\providecommand*{\cftpartaftersnumb}{}
\providecommand*{\cftpartleader}{}
\providecommand*{\cftpartdotsep}{1}
\providecommand*{\cftpartpagefont}{}
\providecommand*{\cftpartafterpnum}{}
```

memoir uses the full name “chapter” instead of “chap”:

```
\LWR@providelength{\cftbeforechapskip}
\LWR@providelength{\cftchapindent}
\LWR@providelength{\cftchapnumwidth}
\newcommand*{\cftchapfont}{}
\newcommand*{\cftchappresnum}{}
\newcommand*{\cftchapaftersnum}{}
\newcommand*{\cftchapaftersnumb}{}
\newcommand*{\cftchapleader}{}
\newcommand*{\cftchapdotsep}{1}
\newcommand*{\cftchappagefont}{}
\newcommand*{\cftchapafterpnum}{}
```

The following do not appear in memoir:

```
\LWR@providelength{\cftbeforesecskip}
\LWR@providelength{\cftsecindent}
\LWR@providelength{\cftsecnumwidth}
\newcommand*{\cftsecfont}{}
\newcommand*{\cftsecpresnum}{}
\newcommand*{\cftsecaftersnum}{}
\newcommand*{\cftsecaftersnumb}{}
\newcommand*{\cftsecleader}{}
\newcommand*{\cftsecdotsep}{1}
\newcommand*{\cftsecpagefont}{}
\newcommand*{\cftsecafterpnum}{}

\LWR@providelength{\cftbeforesubsecskip}
\LWR@providelength{\cftsubsecindent}
```

```
\LWR@providelength{\cftsubsecnumwidth}
\newcommand*{\cftsubsecfont}{}
\newcommand*{\cftsubsecpresnum}{}
\newcommand*{\cftsubsecaftersnum}{}
\newcommand*{\cftsubsecaftersnumb}{}
\newcommand*{\cftsubsecleader}{}
\newcommand*{\cftsubsecdotsep}{1}
\newcommand*{\cftsubsecpagefont}{}
\newcommand*{\cftsubsecafterpnum}{}

\LWR@providelength{\cftbeforesubsubsecskip}
\LWR@providelength{\cftsubsubsecindent}
\LWR@providelength{\cftsubsubsecnumwidth}
\newcommand*{\cftsubsubsecfont}{}
\newcommand*{\cftsubsubsecpresnum}{}
\newcommand*{\cftsubsubsecaftersnum}{}
\newcommand*{\cftsubsubsecaftersnumb}{}
\newcommand*{\cftsubsubsecleader}{}
\newcommand*{\cftsubsubsecdotsep}{1}
\newcommand*{\cftsubsubsecpagefont}{}
\newcommand*{\cftsubsubsecafterpnum}{}

\LWR@providelength{\cftbeforeparaskip}
\LWR@providelength{\cftparaindent}
\LWR@providelength{\cftparanumwidth}
\newcommand*{\cftparafont}{}
\newcommand*{\cftparapresnum}{}
\newcommand*{\cftparaaftersnum}{}
\newcommand*{\cftparaaftersnumb}{}
\newcommand*{\cftparaleader}{}
\newcommand*{\cftparadotsep}{1}
\newcommand*{\cftparapagefont}{}
\newcommand*{\cftparaafterpnum}{}

\LWR@providelength{\cftbeforesubparaskip}
\LWR@providelength{\cftsubparaindent}
\LWR@providelength{\cftsubparanumwidth}
\newcommand*{\cftsubparafont}{}
\newcommand*{\cftsubparapresnum}{}
\newcommand*{\cftsubparaaftersnum}{}
\newcommand*{\cftsubparaaftersnumb}{}
\newcommand*{\cftsubparaleader}{}
\newcommand*{\cftsubparadotsep}{1}
\newcommand*{\cftsubparapagefont}{}
\newcommand*{\cftsubparaafterpnum}{}

\LWR@providelength{\cftbeforefigskip}
\LWR@providelength{\cftfigindent}
\LWR@providelength{\cftfignumwidth}
\newcommand*{\cftfigfont}{}
\newcommand*{\cftfigpresnum}{}
\newcommand*{\cftfigaftersnum}{}
\newcommand*{\cftfigaftersnumb}{}
\newcommand*{\cftfigleader}{}
\newcommand*{\cftfigdotsep}{1}
```

```
\newcommand*{\cftfigpagefont}{}
\newcommand*{\cftfigafterpnum}{}

\LWR@providelength{\cftbeforesubfigskip}
\LWR@providelength{\cftsubfigindent}
\LWR@providelength{\cftsubfignumwidth}
\newcommand*{\cftsubfigfont}{}
\newcommand*{\cftsubfigpresnum}{}
\newcommand*{\cftsubfigaftersnum}{}
\newcommand*{\cftsubfigaftersnumb}{}
\newcommand*{\cftsubfigleader}{}
\newcommand*{\cftsubfigdotsep}{1}
\newcommand*{\cftsubfigpagefont}{}
\newcommand*{\cftsubfigafterpnum}{}

\LWR@providelength{\cftbeforetabskip}
\LWR@providelength{\cfttabindent}
\LWR@providelength{\cfttabnumwidth}
\newcommand*{\cfttabfont}{}
\newcommand*{\cfttabpresnum}{}
\newcommand*{\cfttabaftersnum}{}
\newcommand*{\cfttabaftersnumb}{}
\newcommand*{\cfttableader}{}
\newcommand*{\cfttabdotsep}{1}
\newcommand*{\cfttabpagefont}{}
\newcommand*{\cfttabafterpnum}{}

\LWR@providelength{\cftbeforesubtabskip}
\LWR@providelength{\cftsubtabindent}
\LWR@providelength{\cftsubtabnumwidth}
\newcommand*{\cftsubtabfont}{}
\newcommand*{\cftsubtabpresnum}{}
\newcommand*{\cftsubtabaftersnum}{}
\newcommand*{\cftsubtabaftersnumb}{}
\newcommand*{\cftsubtableader}{}
\newcommand*{\cftsubtabdotsep}{1}
\newcommand*{\cftsubtabpagefont}{}
\newcommand*{\cftsubtabafterpnum}{}

\DeclareDocumentCommand{\cftsetindents}{m m m}{}

\newcommand{\pagenumbersoff}[1]{}
\newcommand{\pagenumberson}[1]{}
```

\newlistentry [⟨*within*⟩] {⟨*counter*⟩} {⟨*ext*⟩} {⟨*level-1*⟩}

```
\DeclareDocumentCommand{\newlistentry}{o m m m}
{%
\LWR@traceinfo{newlistentry #2 #3 #4}%
\IfValueTF{#1}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}[#1]%
        \expandafter\edef\csname the#2\endcsname{%
```

```
            \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}%
        }%
    }{}%
}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}%
    }{}%
}%
\@namedef{l@#2}##1##2{%
    \hypertocfloat{1}{#2}{#3}{##1}{##2}%
    \def\cftwhatismyname{#2}% from memoir
}%
\expandafter\newlength\csname cftbefore#2skip\endcsname%
\expandafter\newlength\csname cft#2indent\endcsname%
\expandafter\newlength\csname cft#2numwidth\endcsname%
\@namedef{cft#2font}{}%
\@namedef{cft#2presnum}{}%
\@namedef{cft#2aftersnum}{}%
\@namedef{cft#2aftersnumb}{}%
\@namedef{cft#2leader}{}%
\@namedef{cft#2dotsep}{1}%
\@namedef{cft#2pagefont}{}%
\@namedef{cft#2afterpnum}{}%
\@namedef{toclevel@#2}{#4}%
\@namedef{cft#2fillnum}##1{}%
\LWR@traceinfo{newlistentry done}%
}
```

`\newlistof` `[`⟨*within*⟩`]` {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the `\newfloat` mechanism.

```
\DeclareDocumentCommand{\newlistof}{o m m m}
{%
\IfValueTF{#1}
{\newlistentry[#1]{#2}{#3}{0}}
{\newlistentry{#2}{#3}{0}}
\@namedef{ext@#2}{#3}
\@ifundefined{c@#3depth}{\newcounter{#3depth}}{}
\setcounter{#3depth}{1}
\@namedef{cftmark#3}{}
\@namedef{listof#2}{\listof{#2}{#4}}
\@namedef{@cftmake#3title}{}
\expandafter\newlength\csname cftbefore#3titleskip\endcsname
\expandafter\newlength\csname cftafter#3titleskip\endcsname
\@namedef{cft#3titlefont}{}
\@namedef{cftafter#3title}{}
\@namedef{cft#3prehook}{}
\@namedef{cft#3posthook}{}
}
```

`\cftchapterprecis` {⟨*text*⟩}

```
\newcommand{\cftchapterprecis}[1]{%
  \cftchapterprecishere{#1}
```

```
  \cftchapterprecistoc{#1}}
\newcommand{\cftchapterprecishere}[1]{%
  \begin{quote}\textit{#1}\end{quote}}
\newcommand{\cftchapterprecistoc}[1]{
  \addtocontents{toc}{%
  {
     \protect\begin{quote}#1\protect\end{quote}}
  }
}
```

File 383 **lwarp-tocstyle.sty**

§ 481 Package tocstyle

Pkg tocstyle tocstyle is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{tocstyle}[2017/02/23]

\newcommand*{\usetocstyle}[2][]{}
\newcommand*{\deactivatetocstyle}[1][]{}
\newcommand*{\reactivatetocstyle}[1][]{}
\NewDocumentCommand{\settocfeature}{o o m m}{}
\NewDocumentCommand{\settocstylefeature}{o m m}{}
\NewDocumentCommand{\newtocstyle}{o o m m}{}
\newcommand*{\aliastoc}[2]{}
\newcommand*{\showtoc}[2][]{}
\newcommand{\iftochasdepth}[4]{}
```

File 384 **lwarp-todo.sty**

§ 482 Package todo

(*Emulates or patches code by* Federico Garcia.)

Pkg todo todo is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{todo}[2010/03/31]

\renewcommand\todoitem[2]{%
    \refstepcounter{todo}%
    \item[%
        \HTMLunicode{2610} \quad
        \ref{todopage:\thetodo}
     ] : {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
    \label{todolbl:\thetodo}%
}%

\renewcommand\doneitem[2]{%
```

```
    \stepcounter{todo}%
    \item[%
        \HTMLunicode{2611} \quad
        \ref{todopage:\thetodo}
    ] \@nameuse{@done\the\c@todo}:
        {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
}

\xpatchcmd{\@displaytodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displaytodo.}}

\xpatchcmd{\@displayfulltodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displayfulltodo.}}

\patchcmd{\todoenv}{\itshape see text.}{\textit{see text.}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch todoenv.}}

\patchcmd{\astodos}{\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch astodos.}}

\AtBeginDocument{
    \crefname{todo}{todo}{todos}
    \Crefname{todo}{Todo}{Todos}
}
```

File 385 **lwarp-todonotes.sty**

§ 483 Package todonotes

(*Emulates or patches code by* Henrik Skov Midtiby.)

Pkg todonotes todonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{todonotes}[2012/07/25]

\if@todonotes@disabled
\else

\newcommand{\ext@todo}{tdo}

\renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}

\let\LWRTODONOTES@orig@todototoc\todototoc

\renewcommand*{\todototoc}{%
\phantomsection%
```

```
\LWRTODONOTES@orig@todototoc%
}

\renewcommand{\@todonotes@drawMarginNoteWithLine}{
\fcolorbox
    {\@todonotes@currentbordercolor}
    {\@todonotes@currentbackgroundcolor}
    {\arabic{@todonotes@numberoftodonotes}}
\marginpar{\@todonotes@drawMarginNote}
}

\renewcommand{\@todonotes@drawInlineNote}{%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \if@todonotes@authorgiven%
        {\@todonotes@author:\,}%
        \fi%
        \@todonotes@text%
    }%
}

\renewcommand{\@todonotes@drawMarginNote}{%
    \if@todonotes@authorgiven%
        \@todonotes@author\par%
    \fi%
    \arabic{@todonotes@numberoftodonotes}: %
    \fcolorbox%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \@todonotes@sizecommand%
        \@todonotes@text %
    }%
}%

\renewcommand{\@todonotes@drawLineToRightMargin}{}

\renewcommand{\@todonotes@drawLineToLeftMargin}{}

\renewcommand{\missingfigure}[2][]{%
\setkeys{todonotes}{#1}%
\addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todo\@todo

```

```
\RenewDocumentCommand{\@todo}{o m}{%
\begingroup%
\renewcommand*{\phantomsection}{}%
\IfValueTF{#1}{%
    \LWRTODONOTES@orig@todo[#1]{#2}%
}{%
    \LWRTODONOTES@orig@todo{#2}%
}
\endgroup%
}

\fi% \if@todonotes@disabled
```

File 386 **lwarp-topcapt.sty**

§ 484 Package topcapt

Pkg topcapt topcapt is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{topcapt}[2004/12/11]

\LetLtxMacro\topcaption\caption
```

File 387 **lwarp-tram.sty**

§ 485 Package tram

Pkg tram tram is emulated.

⚠ block only The HTML emulation uses a , which must not appear inside an HTML or an HTML paragraph. For this reason, the tram environment should only be used to contain paragraphs inside a \parbox or minipage. tram should not be used to mark up inline text.

To disable tram, allowing source compatibility with inline uses:

```
\begin{warpHTML}
\renewenvironment{tram}[1][]{}{}
\end{warpHTML}
```

for HTML output:

```
\LWR@ProvidesPackageDrop{tram}[2013/04/04]

\newenvironment{tram}[1][]%
    {\BlockClass[background:lightgray]{tram}}
    {\endBlockClass}
```

File 388 **lwarp-transparent.sty**

§ 486 Package transparent

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg transparent transparent is emulated. \texttransparent works for inline objects. \transparent only works for \includegraphics.

⚠ Not XeLaTeX! Note that transparent does not work with XeLaTeX.

for HTML output: Discard all options for lwarp-transparent:

```
\LWR@ProvidesPackageDrop{transparent}[2016/05/16]

\newcommand*{\transparent}[1]{\edef\LWR@opacity{#1}}

\newcommand*{\texttransparent}[2]{%
\begingroup%
\transparent{#1}%
\InlineClass[opacity: #1]{transparent}{#2}%
\endgroup%
}
```

File 389 **lwarp-trimclip.sty**

§ 487 Package trimclip

Pkg trimclip trimclip is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{trimclip}[2018/04/08]
```

The third argument, the text, is not touched. This allows \bgroup / \egroup, and verbatim content.

```
\csdef{trimbox}{\@ifstar\@gobble\@gobble}
\csletcs{trimbox*}{trimbox}
\def\endtrimbox{}
\csletcs{endtrimbox*}{endtrimbox}

\csletcs{clipbox}{trimbox}
\csletcs{clipbox*}{trimbox}
\csletcs{endclipbox}{endtrimbox}
\csletcs{endclipbox*}{endtrimbox}

\csletcs{marginbox}{trimbox}
\csletcs{marginbox*}{trimbox}
\csletcs{endmarginbox}{endtrimbox}
\csletcs{endmarginbox*}{endtrimbox}
```

File 390 **lwarp-trivfloat.sty**

§ 488 Package

trivfloat

(*Emulates or patches code by* Joseph Wright.)

Pkg trivfloat

trivfloat is forced to use the built-in lwarp emulation for floats.

To create a new float type and change its name:

```
\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}
```

Discard all options for lwarp-trivfloat. This tells trivfloat not to use floatrow or memoir.

```
\LWR@ProvidesPackageDrop{trivfloat}[2009/04/23]
\LWR@origRequirePackage{trivfloat}
```

\tfl@chapter@fix Nullified at the beginning of the document. Is used by trivfloat to correct float chapter numbers, but is not needed for lwarp.

for HTML output:

```
\begin{warpHTML}
\AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{}}
\end{warpHTML}
```

§ 488.1 Combining \newfloat, \trivfloat, and algorithmicx

for HTML & PRINT:

```
\begin{warpall}
```

For both print and HTML output:

⚠ When using float, trivfloat, or algorithmicx at the same time, be aware of conflicting file usage. algorithmicx uses .loa. trivfloat by default starts with .loa and goes up for additional floats, skipping .lof and .lot.

⚠ When using \newfloat, be sure to manually assign higher letters to the \newfloat files to avoid .loa used by algorithmicx, and any files used by trivfloat. Also avoid using .lof and .lot.

⚠ When using \trivfloat, you may force it to avoid conflicting with algorithmicx by starting trivfloat's file extensions with .lob:

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
```

```
\end{warpall}
```

File 391 **lwarp-truncate.sty**

§ 489 Package truncate

Pkg truncate truncate is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{truncate}[2001/08/20]
```

```
\providecommand{\TruncateMarker}{}
\newcommand{\truncate}[3][\TruncateMarker]{#3}
```

File 392 **lwarp-turnthepage.sty**

§ 490 Package turnthepage

Pkg turnthepage turnthepage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{turnthepage}[2011/03/24]
```

```
\newcommand{\turnthepage}{}
```

File 393 **lwarp-twoup.sty**

§ 491 Package twoup

Pkg twoup twoup is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{twoup}[2007/02/26]
```

```
\newcommand{\cleartolastpage}{}
```

File 394 **lwarp-typearea.sty**

§ 492 Package typearea

(*Emulates or patches code by* Markus Kohm.)

Pkg typearea typearea is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{typearea}[2018/03/30]

\DeclareDocumentCommand{\typearea}{o m}{}
\DeclareDocumentCommand{\recalctypearea}{}{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\areaset}{o m m}{}
\DeclareDocumentCommand{\activateareas}{}{}
\DeclareDocumentCommand{\storeareas}{m}{}
\DeclareDocumentCommand{\BeforeRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterCalculatingTypearea}{s m}{}
\DeclareDocumentCommand{\AfterSettingArea}{s m}{}
```

File 395 **lwarp-typicons.sty**

§ 493 Package

typicons

(*Emulates or patches code by* Arthur Vigil, Xavier Danaux.)

Pkg typicons typicons is patched for use by lwarp.

If \ticon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{typicons}[2015/05/20]

\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@orig@typicon@TI\TI

\newcommand*{\LWR@typicon@symbol}[1]{%
    \begin{lateximage}*[typicon][typicon#1]%
    \begingroup%
    \LWR@orig@typicon@TI%
    \LWR@orig@symbol{#1}%
    \endgroup%
    \end{lateximage}%
}

\renewcommand*{\TI}{%
    \LetLtxMacro\symbol\LWR@typicon@symbol%
}

\renewcommand*{\ticon}[1]
{%
    \begin{lateximage}*[#1 icon][typicon#1]%
```

```
    \TI\csname ticon@#1\endcsname%
    \end{lateximage}%
}
```

File 396 **lwarp-ulem.sty**

§ 494 Package

ulem

(*Emulates or patches code by* Donald Arseneau.)

Pkg ulem Patched for use by lwarp.

for HTML output: Use the original package:

```
\LWR@ProvidesPackagePass{ulem}[2012/05/18]
```

Basic markup commands, using css:

```
\NewDocumentCommand{\LWR@HTML@uline}{+m}{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {uline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uline}

\NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:double%
        )%
        {uuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uuline}

\NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:wavy%
        )%
        {uwave}{\LWR@isolate{#1}}%
}
\LWR@formatted{uwave}

\NewDocumentCommand{\LWR@HTML@sout}{+m}{%
    \InlineClass%
        (text-decoration:line-through)%
        {sout}{\LWR@isolate{#1}}%
}
\LWR@formatted{sout}

\NewDocumentCommand{\LWR@HTML@xout}{+m}{%
```

```
    \InlineClass%
        (text-decoration:line-through)%
        {xout}{\LWR@isolate{#1}}%
}

\NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style:dashed%
        )%
        {dashuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{xout}

\NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style: dotted%
        )%
        {dotuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{dotuline}
```

Nullified/emulated macros:

```
\NewDocumentCommand{\LWR@HTML@markoverwith}{m}{}
\LWR@formatted{markoverwith}

\NewDocumentCommand{\LWR@HTML@ULon}{+m}{\uline{#1}\egroup}
\LWR@formatted{ULon}
```

File 397 **lwarp-umoline.sty**

§ 495 Package

umoline

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg umoline umoline is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{umoline}[2000/07/11]

\newcommand*{\LWR@HTML@Underline}[1]{%
    \InlineClass{uline}{#1}%
}
\LWR@formatted{Underline}

\newcommand*{\LWR@HTML@Midline}[1]{%
    \InlineClass{sout}{#1}%
}
```

```
\LWR@formatted{Midline}

\newcommand*{\LWR@HTML@Overline}[1]{%
    \InlineClass{oline}{#1}%
}
\LWR@formatted{Overline}

\newcommand*{\LWR@HTML@UMOline}[2]{%
    \InlineClass{uline}{#2}%
}
\LWR@formatted{UMOline}

\NewDocumentCommand{\LWR@HTML@UMOspace}{s m o}{\hspace*{#2}}
\LWR@formatted{UMOspace}

\NewDocumentCommand{\LWR@HTML@UMOnewline}{s}{\newline}
\LWR@formatted{UMOnewline}
```

File 398 **lwarp-underscore.sty**

§ 496 Package underscore

Pkg underscore underscore is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{underscore}[2006/09/13]
```

File 399 **lwarp-units.sty**

§ 497 Package units

(*Emulates or patches code by* Axel Reichert.)

Pkg units units is patched for use by lwarp.

Values are not styled by CSS, and take the style of the surrounding HTML text.

Units are styled according to the print version, so they will be forced to upright roman in HTML if the print version does so. It may be necessary to adjust the document's body CSS to match the print version.

for HTML output:

```
\LWR@ProvidesPackagePass{units}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@unit}[2][]{%
\ifblank{#1}%
    {\LWR@textcurrentfont{#2}}%
    {%
        #1%
        \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
        \LWR@textcurrentfont{#2}%
    }%
```

```
}
\LWR@formatted{unit}

\DeclareRobustCommand*{\LWR@HTML@unitfrac}[3][]{%
\ifblank{#1}%
    {%
            \nicefrac{#2}{#3}%
    }%
    {%
            #1%
            \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
            \nicefrac{#2}{#3}%
    }%
}

\LWR@formatted{unitfrac}
```

For Mathjax:

```
\CustomizeMathJax{\newcommand{\unit}[2][]{#1 #2}}
\CustomizeMathJax{\newcommand{\unitfrac}[3][]{#1 #2/#3}}
```

File 400 **lwarp-unitsdef.sty**

§ 498 Package

unitsdef

(*Emulates or patches code by* Patrick Happel.)

Pkg unitsdef unitsdef is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{unitsdef}[2005/01/04]

\renewcommand{\unitvaluesep}{\,}

\renewcommand{\unittimes}{\@@setunitsepfalse\HTMLunicode{22c5}}% \cdot

\renewunit{\arcmin}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^\prime}}%
        {\HTMLunicode{2032}}% prime
}

\renewunit{\arcsec}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^{\prime\prime}}}%
        {\HTMLunicode{2033}}% dbl prime
}

\renewrobustcmd{\SI}[2]{%
  \begingroup%
    \let\unit@@xspace\relax%
    \unitSIdef\selectfont%
```

```
      \LWR@textcurrentfont{#1#2}% lwarp
  \endgroup%
}
```

File 401 **lwarp-upref.sty**

§ 499 Package upref

Pkg upref upref is ignored.

for HTML output: Discard all options for lwarp-upref:

```
\LWR@ProvidesPackageDrop{upref}[2007/03/14]
```

File 402 **lwarp-url.sty**

§ 500 Package url

(*Emulates or patches code by* Donald Arseneau.)

Pkg url url is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{url}[2013/09/16]
```

url uses math mode to print its string inside a group, so the original meaning of math is restored first.

```
\LetLtxMacro\LWR@url@origUrl@FormatString\Url@FormatString

\renewcommand*{\Url@FormatString}{%
    \InlineClass{verbatim}{%
        \LWR@restoreorigformatting%
        \LWR@url@origUrl@FormatString%
    }%
}
```

File 403 **lwarp-uspace.sty**

§ 501 Package uspace

Pkg uspace uspace is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{uspace}[2016/11/06]
```

File 404 **lwarp-verse.sty**

§ 502 Package

verse

(*Emulates or patches code by* Peter Wilson.)

Pkg verse verse is supported and patched by lwarp.

for HTML output: Pass all options for lwarp-verse:

```
\LWR@ProvidesPackagePass{verse}[2009/09/04]
```

When using verse or memoir, always place a \\ after each line.

\attrib The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

Env verse The verse environment will be placed inside a HTML <pre>.

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verse.}
```

At the beginning of the verse environment:

```
\AtBeginEnvironment{verse}
{%
```

Use the original `list` environment inside a <pre> to attempt to preserve formatting.

```
\LWR@restoreoriglists%
```

Pkg verse
Cls memoir
\flagverse
Len \vleftskip

The verse or memoir packages can place stanza numbers to the left with their `\flagverse` command. Do not allow them to go into the left margin, which would cause *pdfcrop* to crop the entire page further to the left:

```
\ifdef{\vleftskip}{%
\setlength{\vleftskip}{\HTMLvleftskip}
\setlength{\leftmargini}{\HTMLleftmargini}
}{}
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{verse}%
}
```

After the end of the `verse` environment, which places the <pre> tag at the regular left margin:

```
\AtEndEnvironment{verse}{%
\leavevmode%
\LWR@afterendverbatim{1}%
}
```

Patch to place poemtitle inside an HTML of class `poemtitle`:

```
\ifdef{\poemtitle}{
\DeclareDocumentCommand{\@vstypeptitle}{m}{%
   \vspace{\beforepoemtitleskip}%
   {\InlineClass{poemtitle}{\poemtitlefont #1}\par}%
   \vspace{\afterpoemtitleskip}%
 }
}{}

\LWR@traceinfo{Finished patching verse.}
}% AfterEndPreamble
```

File 405 **lwarp-versonotes.sty**

§ 503 Package

versonotes

(*Emulates or patches code by* Norman Gray.)

Pkg versonotes

versonotes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{versonotes}[2019/07/06]

\newcommand{\versonote}[1]{\marginpar{#1}}
\newdimen\versotextwidth
\newdimen\versoleftmargin
\newcommand*{\versolayout}{}
```

In case the user changed the page number before loading versonotes:

```
\setcounter{page}{1}
```

File 406 **lwarp-vertbars.sty**

§ 504 Package vertbars

(*Emulates or patches code by* Peter Wilson.)

Pkg vertbars vertbars is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{vertbars}[2010/11/27]

\newlength{\barwidth}
\setlength{\barwidth}{0.4pt}
\newlength{\barspace}
\setlength{\barspace}{1em}

\newenvironment{vertbar}{
    \LWR@forcenewpage
    \LWR@forceminwidth{\barwidth}
    \begin{BlockClass}[%
        border-left: \LWR@printlength{\LWR@atleastonept} solid black ; %
        padding-left: \LWR@printlength{\barspace}%
    ]{vertbar}
}{
    \end{BlockClass}
}
```

File 407 **lwarp-vmargin.sty**

§ 505 Package vmargin

Pkg vmargin vmargin is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vmargin}[2004/07/15]

\newcommand*{\LWRVM@customsize}[2]{}
\newcommand*{\setpapersize}[2][]{\ifstrequal{#2}{custom}{\LWRVM@customsize}{}}
\newcommand*{\setmargins}[8]{}
\newcommand*{\setmarginsrb}[8]{}
\newcommand*{\setmargnohf}[4]{}
\newcommand*{\setmargnohfrb}[4]{}
\newcommand*{\setmarg}[4]{}
\newcommand*{\setmargrb}[4]{}
\newlength{\PaperWidth}
\setlength{\PaperWidth}{8.5in}
\newlength{\PaperHeight}
\setlength{\PaperHeight}{11in}
\newif\ifLandscape
```

File 408 **lwarp-vowel.sty**

§ 506 Package vowel

(*Emulates or patches code by* FUKUI REI.)

Pkg vowel vowel is patched for use by lwarp.

This package has been tested with *pdflatex* and the Type 1 TIPA fonts using the following package load sequence:

```
\usepackage[T3,T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[noenc]{tipa}
\usepackage{vowel}
```

for HTML output:

```
\LWR@ProvidesPackagePass{vowel}[2002/08/08]

\renewenvironment{vowel}[1][]
    {%
        \begin{lateximage}[-vowel-~\PackageDiagramAltText]%
        \@vowel[#1]%
    }
    {%
        \@@vowel%
        \end{lateximage}%
    }
```

File 409 **lwarp-vpe.sty**

§ 507 Package vpe

Pkg vpe vpe is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vpe}[2012/04/18]
```

File 410 **lwarp-vwcol.sty**

§ 508 Package vwcol

(*Emulates or patches code by* WILL ROBERTSON.)

Pkg vwcol vwcol is patched for use with lwarp.

The `width` option is ignored. All `vwcol` environments adjust to 1–3 equal-width columns, depening on the width of the browser window.

The remaining options are supported, except for `lines` and `maxrecursion`.

for HTML output:

```
\LWR@ProvidesPackagePass{vwcol}[2015/02/10]
```

Factored from `\vwcol`. Each is given a style tag to append to the final style.

`\LWR@vwcol@addrule` {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addrule}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
     \LWR@printlength{\vwcol@rule} solid \LWR@origpound\LWR@vwcol@rulecolor ; %
    }%
}
```

`\LWR@vwcol@addrule` {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addgap}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
        \LWR@printlength{\vwcol@sep} ; %
    }%
}
```

Env `vwcol` {⟨*key/values*⟩}

Redefine the environment to add a HTML style. The style is built depending on the required options.

```
\renewenvironment*{vwcol}[1][]{%
```

New paragraph, and process the options:

```
\LWR@stoppars%
\vwcolsetup{#1}%
```

Begin with no style:

```
\newcommand*{\LWR@vwcolstyle}{}
```

`presep` and `postsep` are created with HTML `margin`s:

```
\if@vwcol@presep
    \appto{\LWR@vwcolstyle}{margin-left: 1em ; padding-left: .5em ; }
\fi
\if@vwcol@postsep
    \appto{\LWR@vwcolstyle}{margin-right: 1em ; padding-right: .5em ; }
\fi
```

`sep` becomes `column-gap`:

```
\ifdimgreater{\vwcol@sep}{1sp}{
    \LWR@vwcol@addgap{column-gap}
    \LWR@vwcol@addgap{-moz-column-gap}
    \LWR@vwcol@addgap{-webkit-column-gap}
}{}
```

`rule` become `column-rule`, while `prerule` and `postrule` become HTML borders:

```
\convertcolorspec{named}{\vwcol@rulecol}{HTML}\LWR@vwcol@rulecolor%
```

```
\ifdimgreater{\vwcol@rule}{0pt}{
    \ifdimless{\vwcol@rule}{1pt}{
        \setlength{\vwcol@rule}{1pt}
    }{}
    \LWR@vwcol@addrule{column-rule}
    \LWR@vwcol@addrule{-moz-column-rule}
    \LWR@vwcol@addrule{-webkit-column-rule}
    \if@vwcol@prerule\LWR@vwcol@addrule{border-left}\fi
    \if@vwcol@postrule\LWR@vwcol@addrule{border-right}\fi
}{}
```

Each of the justify options becomes a `text-align`. Indentation is added where appropriate.

```
\ifdefequal{\vwcol@justify}{\RaggedRight}{
    \appto{\LWR@vwcolstyle}{text-align: left ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
}{}
\ifdefequal{\vwcol@justify}{\RaggedLeft}{
    \appto{\LWR@vwcolstyle}{text-align: right ; }
}{}
\ifdefequal{\vwcol@justify}{\Centering}{
    \appto{\LWR@vwcolstyle}{text-align: center ; }
}{}
\ifdefequal{\vwcol@justify}{\justifying}{
    \appto{\LWR@vwcolstyle}{text-align: justify ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
}{}
```

Create the with the assembled style:

```
\BlockClass[\LWR@vwcolstyle]{multicols}
}
```

When the environment ends:

```
{
\endBlockClass
\LWR@startpars
}
```

File 411 **lwarp-wallpaper.sty**

§ 509 Package wallpaper

(*Emulates or patches code by* Michael H.F. Wilkinson.)

Pkg wallpaper wallpaper is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{wallpaper}[2005/01/18]

\newcommand*{\CenterWallPaper}[2]{}
\newcommand*{\ThisCenterWallPaper}[2]{}
\newcommand*{\TileWallPaper}[3]{}
\newcommand*{\ThisTileWallPaper}[3]{}
\newcommand*{\TileSquareWallPaper}[2]{}
\newcommand*{\ThisTileSquareWallPaper}[2]{}
\newcommand*{\ULCornerWallPaper}[2]{}
\newcommand*{\ThisULCornerWallPaper}[2]{}
\newcommand*{\LLCornerWallPaper}[2]{}
\newcommand*{\ThisLLCornerWallPaper}[2]{}
\newcommand*{\URCornerWallPaper}[2]{}
\newcommand*{\ThisURCornerWallPaper}[2]{}
\newcommand*{\LRCornerWallPaper}[2]{}
\newcommand*{\ThisLRCornerWallPaper}[2]{}
\newcommand*{\ClearWallPaper}{}
\newlength{\wpXoffset}
\newlength{\wpYoffset}
```

File 412 **lwarp-watermark.sty**

§ 510 Package watermark

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg watermark watermark is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{watermark}[2004/12/09]

\newcommand{\watermark}[1]{}
\newcommand{\leftwatermark}[1]{}
\newcommand{\rightwatermark}[1]{}
\newcommand{\thiswatermark}[1]{}
\newcommand{\thispageheading}[1]{}
```

File 413 **lwarp-widows-and-orphans.sty**

§ 511 Package widows-and-orphans

Pkg widows-and-orphans widows-and-orphans is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{widows-and-orphans}[2018/09/01]

\NewDocumentCommand\WaOsetup{m}{}
\NewDocumentCommand\WaOparameters{}{}
\NewDocumentCommand\WaOignorenext{}{}
```

File 414 **lwarp-wrapfig.sty**

§ 512 Package

wrapfig

(*Emulates or patches code by* Donald Arseneau.)

Pkg wrapfig wrapfig is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{wrapfig}[2003/01/31]

\newcommand*{\LWR@wrapposition}{}

\newcommand*{\LWR@subwrapfigure}[2]{%
\renewcommand*{\LWR@wrapposition}{}%
\ifthenelse{%
    \equal{#1}{r}\OR\equal{#1}{R}\OR%
    \equal{#1}{o}\OR\equal{#1}{O}%
}%
    {\renewcommand*{\LWR@wrapposition}{float:right}}%
    {\renewcommand*{\LWR@wrapposition}{float:left}}%
\setlength{\LWR@templengthone}{#2}%
\LWR@BlockClassWP{%
    width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
    margin:10pt%
}%
{%
    \LWR@wrapposition%
}%
{marginblock}%

\setlength{\linewidth}{\LWR@templengthone}%
}


\NewDocumentEnvironment{wrapfigure}{o m o m}
{%
\LWR@subwrapfigure{#2}{#4}%
\captionsetup{type=figure}%
}
{%
\endLWR@BlockClassWP%
}


\NewDocumentEnvironment{wraptable}{o m o m}
{%
\LWR@subwrapfigure{#2}{#4}%
\captionsetup{type=table}%
}
{%
\endLWR@BlockClassWP%
```

```
}


\NewDocumentEnvironment{wrapfloat}{m o m o m}
{%
\LWR@subwrapfigure{#3}{#5}%
\captionsetup{type=#1}%
}
{%
\endLWR@BlockClassWP%
}

\newlength{\wrapoverhang}
```

File 415 **lwarp-xbmks.sty**

§ 513 Package xbmks

Pkg xbmks xbmks is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xbmks}[2018/07/04]

\newcommand{\xbmksetup}[1]{}
\NewDocumentCommand{\pdfbookmarkx}{o m o m}{}
\NewDocumentCommand{\currentpdfbookmarkx}{m o m}{}
\NewDocumentCommand{\subpdfbookmarkx}{m o m}{}
\NewDocumentCommand{\belowpdfbookmarkx}{m o m}{}
```

File 416 **lwarp-xcolor.sty**

§ 514 Package xcolor

(*Emulates or patches code by* Dr. Uwe Kern.)

Pkg xcolor xcolor is supported by lwarp.

§ 514.1 Limitations

\colorboxBlock and \fcolorboxBlock

\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a instead of a . These s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none

\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support — Color definitions, models, and mixing are fully supported without any changes required.

colored tables — `\rowcolors` is supported, except that the optional argument is ignored so far.

colored text and boxes — `\textcolor`, `\colorbox`, and `\fcolorbox` are supported.

`\color` and `\pagecolor` — `\color` and `\pagecolor` are ignored. Use css or `\textcolor` where possible.

§ 514.2 xcolor definitions: location and timing

The lwarp core and its lwarp-xcolor package are tightly integrated to allow comparable results for print, HTML, and print inside an HTML `lateximage`. This requires a number of definitions and redefintions depending on whether each of xcolor and `lateximage` is being used, and whether print or HTML is being generated. Some of these actions are one-time when xcolor is loaded, and others are temporary as `lateximage` is used.

When xcolor is loaded in print mode: No special actions are taken at the time that xcolor is loaded in print mode, but see `\AtBeginDocument` below.

When lwarp-xcolor is loaded in HTML mode: xcolor's original definitions are saved for later restoration. `\LWR@restoreorigformatting` is appended to restore these definitions for use inside a `lateximage`. New HTML-mode definitions are created for `\textcolor`, `\pagecolor`, `\nopagecolor`, `\colorbox`, `\colorboxBlock`, `\fcolorbox`, `\fcolorboxBlock`, and `fcolorminipage`.

`\AtBeginDocument` in print or HTML mode: See Section 85. If xcolor has been loaded, the print-mode `\fcolorbox` is modified to accept a background color of `none`, and additional definitions are created for lwarp's new macros print-mode macros `\colorboxBlock`, `\fcolorboxBlock`, and `fcolorminipage`. The HTML versions of these macros will already have been created by lwarp-xcolor if it has been loaded.

For use inside an HTML `lateximage`, `\LWR@restoreorigformatting` is appended to temporarily set these functions to their print-mode versions.

In a `lateximage` in HTML mode: `\LWR@restoreorigformatting` temporarily restores the print-mode definitions of xcolor's functions. See `\LWR@restoreorigformatting` on page 492.

`\color`:

Print: Used as-is.

HTML: Ignored by *pdftotext*, and will not appear.

HTML `lateximage`: Colors will appear in a `lateximage`.

`\textcolor`:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 995.

HTML `lateximage`: Remembers and reuses the print version.

`\pagecolor`:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a `lateximage`.

\nopagecolor:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a `lateximage`.

\colorbox:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 995.

HTML lateximage: Remembers and reuses the print version.

\colorboxBlock:

Print: Becomes `\colorbox`.

HTML: Newly defined by lwarp-xcolor to use a `<div>`, page 996.

HTML lateximage: Remembers and reuses the print version `\colorbox`.

\fcolorbox:

Print: Modified to allow a background of `none`.
`\LWR@print@fcolorbox` at section 85

HTML: Redefined by lwarp-xcolor, page 996.

HTML lateximage: Remembers and reuses the print version.

\fcolorboxBlock:

Print: Becomes `\fcolorbox`. Section 85

HTML: Newly defined by lwarp-xcolor to use a `<div>`, page 997.

HTML lateximage: Remembers and reuses the print version `\fcolorbox`.

fcolorminipage:

Print: Newly defined in the lwarp core.
`LWR@print@fcolorminipage` at section 85

HTML: Newly defined by lwarp-xcolor, page 998.

HTML lateximage: Uses the print version.

\boxframe:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 999.

HTML lateximage: Remembers and reuses the print version.

§ 514.3 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{xcolor}[2016/05/11]
\begin{warpHTML}
```

§ 514.4 Remembering and restoring original definitions

Remember the following print-mode actions to be restored when inside a `lateximage` environment:

```
\LetLtxMacro\LWR@print@pagecolor\pagecolor
\LetLtxMacro\LWR@print@nopagecolor\nopagecolor
```

`\LWR@restoreorigformatting` Inside a `lateximage` the following gets restored to their print-mode actions:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\pagecolor\LWR@print@pagecolor%
\LetLtxMacro\nopagecolor\LWR@print@nopagecolor%
}
```

§ 514.5 `\normalcolor`

`\normalcolor`

```
\DeclareRobustCommand{\LWR@HTML@normalcolor}{\color{black}}%

\LWR@formatted{normalcolor}
```

§ 514.6 HTML color style

`\LWR@findcurrenttextcolor` Sets `\LWR@tempcolor` to the current color.

```
\renewcommand*{\LWR@findcurrenttextcolor}{%
\protect\colorlet{LWR@current@color}{.}%
\protect\convertcolorspec{named}{LWR@current@color}{HTML}\LWR@tempcolor%
}
```

`\LWR@currenttextcolorstyle` Prints a color style for the current color.

```
\newcommand*{\LWR@currenttextcolorstyle}{%
\LWR@findcurrenttextcolor%
\ifdefstring{\LWR@tempcolor}{000000}%
{}%
{color: \LWR@origpound\LWR@tempcolor ; }%
}
```

`\LWR@textcurrentcolor` {⟨*text*⟩} Like `\textcolor` but uses the current `\color` instead.

```
\DeclareDocumentCommand{\LWR@textcurrentcolor}{m}{%
\begingroup%
\LWR@FBcancel%
\LWR@findcurrenttextcolor%
```

```
\InlineClass[color:\LWR@origpound\LWR@tempcolor]{textcolor}{%
    \renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
    #1%
}%
\endgroup%
}
```

`\LWR@colorstyle` {⟨*2: model*⟩} {⟨*3: color*⟩}

For a color style, prints the color converted to HTML colors.

```
\NewDocumentCommand{\LWR@colorstyle}{m m}{%
\begingroup%
\LWR@FBcancel%
```

Use the xcolor package to convert to an HTML color space:

```
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```
\LWR@origpound\LWR@tempcolor%
\endgroup%
}
```

`\LWR@backgroundcolor` [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Similar to `\textcolor`, but prints black text against a color background.

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@backgroundcolor}{O{named} m m}{%
\begingroup%
\LWR@FBcancel%
\InlineClass[background:\LWR@colorstyle{#1}{#2}]{backgroundcolor}{%
#3%
}%
\endgroup%
}
```

§ 514.7 HTML border

`\LWR@borderpadding` {⟨*colorstyle*⟩} {⟨*color*⟩} Prints the HTML attributes for a black border and padding. `\LWR@forceminwidth` must be used first in order to set the border width.

```
\newcommand*{\LWR@borderpadding}[2]{%
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
}
```

§ 514.8 High-level macros

\color [⟨*model*⟩] {⟨*color*⟩}

⚠ The current \color is used by HTML rules and frames, but does not affect the current HTML text output, due to the lack of HTML states and scoping limitations. Use \textcolor if possible.

```
\NewDocumentCommand{\LWR@HTML@color}{o m}{%
\IfValueTF{#1}{%
    \LWR@print@color[#1]{#2}%
    \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
}{%
    \LWR@print@color{#2}%
    \convertcolorspec{named}{#2}{HTML}\LWR@tempcolor%
}%
\edef\LWR@currenttextcolor{\LWR@origpound\LWR@tempcolor}%
}

\LWR@formatted{color}
```

\textcolor [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@HTML@textcolor}{o m m}{%
\begingroup%
\IfValueTF{#1}{%
    \color[#1]{#2}%
}{%
    \color{#2}%
}
\InlineClass[color:\LWR@currenttextcolor]{textcolor}{#3}%
\endgroup%
}%

\LWR@formatted{textcolor}
```

\pagecolor [⟨*model*⟩] {⟨*color*⟩}

Ignored. Use css instead.

```
\renewcommand*{\pagecolor}[2][named]{}
```

\nopagecolor Ignored.

```
\renewcommand*{\nopagecolor}{}
```

\colorbox [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex background color .

```
\NewDocumentCommand{\LWR@HTML@colorbox}{O{named} m +m}{%
\begingroup%
\LWR@FBcancel%
\InlineClass[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorbox}{#3}%
\endgroup%
}

\AtBeginDocument{
\LWR@formatted{colorbox}
}
```

\colorboxBlock [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex background color .

```
\NewDocumentCommand{\LWR@HTML@colorboxBlock}{O{named} m +m}{%
\begingroup%
\LWR@FBcancel%


\LWR@stoppars%

\begin{BlockClass}[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorboxBlock}
#3
\end{BlockClass}%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
\LWR@formatted{colorboxBlock}
}
```

\fcolorbox [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorbox}{O{named} m O{named} m +m}{%
\LWR@traceinfo{HTML fcolorbox #2 #4}%
\begingroup%
\LWR@FBcancel%
\LWR@forceminwidth{\fboxrule}%
\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2}%
        ]{fcolorbox}{#5}%
    }%
    {% yes background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2} ; %
        background:\LWR@colorstyle{#3}{#4}%
        ]{fcolorbox}{#5}%
    }%
\endgroup%
}

\AtBeginDocument{
\LWR@formatted{fcolorbox}
}
```

\fcolorboxBlock `[`⟨*frame model*⟩`]` `{`⟨*frame color*⟩`}` `[`⟨*box model*⟩`]` `{`⟨*box color*⟩`}` `{`⟨*text*⟩`}`

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorboxBlock}{O{named} m O{named} m +m}{%
\LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
\begingroup%
\LWR@FBcancel%
\LWR@forceminwidth{\fboxrule}%

\LWR@stoppars%

\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \begin{BlockClass}[%
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
        \end{BlockClass}%
    }%
    {% yes background color
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \begin{BlockClass}[%
            background:\LWR@origpound\LWR@tempcolortwo\ ; %
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
```

```
        \end{BlockClass}%
    }%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{HTML fcolorboxBlock done}%
}

\AtBeginDocument{
\LWR@formatted{fcolorboxBlock}
}
```

Creates a framed HTML around its contents.

A print-output version is defined in the lwarp core: section 85

`\LWR@subfcolorminipage` {⟨*framemodel*⟩} {⟨*framecolor*⟩} {⟨*background tag*⟩} {⟨*height*⟩}

```
\NewDocumentCommand{\LWR@subfcolorminipage}{m m m m}{%

\LWR@stoppars%

\begin{BlockClass}[%
#3%
\LWR@borderpadding{#1}{#2} ; %
\IfValueT{#4}{height:\LWR@printlength{\LWR@tempheight} ; }%
width:\LWR@printlength{\LWR@tempwidth}%
]{fcolorminipage}%
}
```

Env `fcolorminipage` [⟨*1:framemodel*⟩] {⟨*2:framecolor*⟩} [⟨*3:boxmodel*⟩] {⟨*4:boxcolor*⟩} [⟨*5:align*⟩] [⟨*6:height*⟩] [⟨*7:inner-align*⟩] {⟨*8:width*⟩}

```
\NewDocumentEnvironment{LWR@HTML@fcolorminipage}{O{named} m O{named} m O{c} o o m}
{%
\LWR@FBcancel%
\setlength{\LWR@tempwidth}{#8}%
\IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
\LWR@forceminwidth{\fboxrule}%
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
\ifthenelse{\equal{#4}{none}}%
    {\LWR@subfcolorminipage{#1}{#2}{}{#6}}%
    {%
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \LWR@subfcolorminipage{#1}{#2}%
            {background:\LWR@origpound\LWR@tempcolortwo\ ; }%
            {#6}%
    }%
}%
{%
    \end{BlockClass}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
    \global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
\LWR@formattedenv{fcolorminipage}
}
```

\boxframe {⟨*width*⟩} {⟨*height*⟩} {⟨*depth*⟩}

The depth is added to the height, but the box is not decended below by the depth. `\textcolor` is honored.

```
\newcommand*{\LWR@HTML@boxframe}[3]{%
{%
\setlength{\LWR@tempwidth}{#1}%
\setlength{\LWR@tempheight}{#2}%
\addtolength{\LWR@tempheight}{#3}%
\LWR@forceminwidth{\fboxrule}%
\LWR@findcurrenttextcolor%
\InlineClass[%
display:inline-block ; %
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@currenttextcolor{} ; %
width:\LWR@printlength{\LWR@tempwidth} ; %
height:\LWR@printlength{\LWR@tempheight}%
]{boxframe}{}%
}%
}

\LWR@formatted{boxframe}
```

§ 514.9 Row colors

\rowc@l@rs [⟨*cmds*⟩] {⟨*startrow*⟩} {⟨*odd color*⟩} {⟨*even color*⟩}

```
\newcommand*{\LWR@xcolortempcolor}{}

\def\rowc@l@rs[#1]#2#3#4%
{
\global\rownum=1
   \global\@rowcolorstrue
   \@ifxempty{#3}%
     {\def\@oddrowcolor{\@norowcolor}}%
     {%
        \convertcolorspec{named}{#3}{HTML}\LWR@xcolortempcolor%
        \edef\@oddrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
        }%
     }%
   \@ifxempty{#4}%
     {\def\@evenrowcolor{\@norowcolor}}%
     {%
```

```
        \convertcolorspec{named}{#4}{HTML}\LWR@xcolortempcolor%
        \edef\@evenrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
        }%
    }%
  \if@rowcmd
    \def\@rowcolors
    {%
% #1%
      \if@rowcolors
% \noalign{%
          \relax\ifnum\rownum<#2\@norowcolor\else
          \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi\fi%
% }%
      \fi%
    }%
  \else
    \def\@rowcolors
    {%
      \if@rowcolors
          \ifnum\rownum<#2%
% \noalign{%
             \@norowcolor
% }
          \else
% #1%
% \noalign{%
             \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi%
% }%
          \fi
      \fi%
    }%
  \fi
  \ignorespaces%
}
```

\@norowcolor Turns off color for this row.

```
\def\@norowcolor{%
\renewcommand{\LWR@xcolorrowHTMLcolor}{}%
}
```

\@rowc@lors Executed at the end of each row.

```
\def\@rowc@lors{%
%   \noalign{%
        \global\advance\rownum\@ne%
%   }%
    \@rowcolors%
}

\end{warpHTML}
```

File 417 **lwarp-xechangebar.sty**

§ 515 Package xechangebar

Pkg xechangebar xechangebar is ignored

for HTML output:

```
\LWR@ProvidesPackageDrop{xechangebar}[2017/08/03]
\LWR@origRequirePackage{lwarp-changebar}
```

File 418 **lwarp-xellipsis.sty**

§ 516 Package xellipsis

(*Emulates or patches code by* Donald P. Goodman III.)

Pkg xellipsis xellipsis is patched for use by lwarp.

When non-zero, each of the spaces is converted to an HTML thin unbreakable space.

for HTML output:

```
\LWR@ProvidesPackagePass{xellipsis}[2015/11/01]

\newcommand*{\LWR@xellipsespace}[1]{%
\ifdim#1=0pt\else%
    \ifdim#1<\fontdimen2\font%
        \,%
    \else%
        ~%
    \fi%
\fi%
}

\def\xelip{%
\mbox{%
    \LWR@xellipsespace{\xelipprebef}%
    \xelipprechar%
    \LWR@xellipsespace{\xelippreaft}%
    \LWR@xellipsespace{\xelipbef}%
    \xelipchar%
    \xel@loopi = 1%
    \loop\ifnum\xelipnum>\xel@loopi%
        \advance\xel@loopi by1%
        \LWR@xellipsespace{\xelipgap}%
        \xelipchar%
    \repeat%
    \LWR@xellipsespace{\xelipaft}%
    \LWR@xellipsespace{\xelippostbef}%
    \xelippostchar%
    \LWR@xellipsespace{\xelippostaft}%
```

```
}%
}%
```

File 419 **lwarp-xetexko-vertical.sty**

§ 517 Package xetexko-vertical

(*Emulates or patches code by* Dohyun Kim.)

Pkg xetexko-vertical xetexko-vertical is patched for use by lwarp.

for HTML output:

```
\LWR@loadbefore{xetexko-vertical}

\LWR@ProvidesPackagePass{xetexko-vertical}[2018/04/06]

\renewcommand{\verticaltypesetting}{}
\renewenvironment{vertical}[1]{\BlockClass{verticalrl}}{\endBlockClass}
\renewenvironment{horizontal}[1]{\BlockClass{horizontaltb}}{\endBlockClass}
\renewcommand{\vertlatin}[1]{#1}
```

File 420 **lwarp-xfakebold.sty**

§ 518 Package xfakebold

(*Emulates or patches code by* Herbert Voss.)

Pkg xfakebold xfakebold is patched for use by lwarp, and additional underlying support is found in the lwarp core.

⚠ page breaks Note that the print version resets to unbold at each page break, whereas the HTML version maintains the bold state until it is undone.

for HTML output:

```
\LWR@ProvidesPackagePass{xfakebold}[2018/07/25]

\let\LWR@orig@setBold\setBold
\let\LWR@orig@unsetBold\unsetBold
\renewcommand*{\setBold}{\booltrue{LWR@xfakebold}}
\renewcommand*{\unsetBold}{\boolfalse{LWR@xfakebold}}

\renewcommand*{\LWR@applyxfakebold}{%
    \ifbool{LWR@xfakebold}{\LWR@orig@setBold}{\LWR@orig@unsetBold}%
}
```

File 421 **lwarp-xfrac.sty**

§ 519 Package xfrac

(*Emulates or patches code by* The LaTeX3 Project.)

Pkg xfrac Supported by adding xfrac instances.

for HTML output:
```
\LWR@ProvidesPackagePass{xfrac}[2018-08-23]
```

⚠ font size In the user's document preamble, lwarp should be loaded after font-related setup. During HTML conversion, this font is used by lwarp to generate its initial PDF output containing HTML tags, later to be converted by *pdftotext* to a plain text file. While the text may be in any font which *pdftotext* can read, the math is directly converted into SVG images using this same user-selected font. xfrac below is set for the Latin Modern (lmr) font. If another font is used, it may be desirable to redefine \xfracHTMLfontsize with a different em size.

\sfrac [⟨*instance*⟩] {⟨*num*⟩} [⟨*sep*⟩] {⟨*denom*⟩}

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in HTML tags. \scalebox is made null inside the numerator and denominator, since the HTML tags should not be scaled, and we do not want to introduce additional HTML tags for scaling.

In math mode, which will appear inside a lateximage, no adjustments are necessary.

for HTML & PRINT:
```
\begin{warpall}
```

\xfracHTMLfontsize User-redefinable macro which controls the font size of the fraction.

```
\newcommand*{\xfracHTMLfontsize}{.6em}
```

```
\end{warpall}
```

for HTML output:
```
\begin{warpHTML}
```

instances Instances of xfrac for various font choices:

Produce CSS for a small raised numerator and a small denominator.

Scaling is turned off so that *pdftotext* correctly reads the result.

```
\DeclareInstance{xfrac}{default}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmr}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmss}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmtt}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}
```

```
\end{warpHTML}
```

File 422 **lwarp-xltabular.sty**

§ 520 Package xltabular

(*Emulates or patches code by* Rolf Niepraschk, Herbert Voss.)

Pkg xltabular xltabular is emulated by lwarp.

for HTML output: Relies on tabularx.

⚠ table numbering At present, an `xltabular` without a caption or with only a `\caption*` may be misnumbered in HTML, so it may be necessary to place at the end of the table:

```
\warpHTMLonly{\addtocounter{table}{-1}}
```

```
\RequirePackage{tabularx}

\LWR@ProvidesPackageDrop{xltabular}[2018/05/23]

\DeclareDocumentEnvironment{xltabular}{o m m}
{\longtable{#3}}
{\endlongtable}
```

File 423 **lwarp-xltxtra.sty**

§ 521 Package xltxtra

(*Emulates or patches code by* Will Robertson, Jonathan Kew.)

Pkg xltxtra xltxtra is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xltxtra}[2016/01/21]

\RequirePackage{realscripts}
\RequirePackage{metalogo}
\newcommand*\TeX@logo@spacing[6]{}

\newcommand*{\vfrac}[2]{%
\textsuperscript{#1}/\textsubscript{#2}%
}

\newcommand\namedglyph[1]{%
```

```
  \@tempcnta=\XeTeXglyphindex "#1"\relax
  \ifnum\@tempcnta>0
    \XeTeXglyph\@tempcnta
  \else
    \xxt@namedglyph@fallback{#1}%
  \fi}

\newcommand\xxt@namedglyph@fallback[1]{[#1]}

\DeclareDocumentCommand{\showhyphens}{m}{}
```

File 424 **lwarp-xmpincl.sty**

§ 522 Package xmpincl

(*Emulates or patches code by* Maarten Sneep.)

Pkg xmpincl xmpincl is ignored.

for HTML output: Discard all options for lwarp-xmpincl:

```
\LWR@ProvidesPackageDrop{xmpincl}[2008/05/10]

\newcommand*{\includexmp}[1]{}
```

File 425 **lwarp-xpiano.sty**

§ 523 Package xpiano

(*Emulates or patches code by* Enrico Gregorio.)

Pkg xpiano xpiano is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{xpiano}

\ExplSyntaxOn
\NewDocumentCommand{\LWR@print@keyboard}{ O{}m }
{
\xpiano_keyboard:nn { #1 } { #2 }
}

\NewDocumentCommand{\LWR@HTML@keyboard}{ O{}m }
{
\begin{lateximage}*
    [%
        -xpiano-~\PackageDiagramAltText{}: \detokenize\expandafter{#2}%
    ]
    [\detokenize\expandafter{#1}]
\xpiano_keyboard:nn { #1 } { #2 }
\end{lateximage}
```

```
}
\ExplSyntaxOff

\LWR@formatted{keyboard}
```

File 426 **lwarp-xpinyin.sty**

§ 524 Package xpinyin

(*Emulates or patches code by* Soben Lee.)

Pkg xpinyin xpinyin is partly supported. `\xpinyin` and `pinyinscope` are nullified, but `\pinyin` works.

for HTML output:

```
\LWR@ProvidesPackagePass{xpinyin}[2018/01/28]

\RenewDocumentEnvironment{pinyinscope}{O{}}{}{}

\RenewDocumentCommand{\xpinyin}{s O{} m}{%
    \IfBooleanTF{#1}{#3}{\@firstoftwo#3}%
}

\RenewDocumentCommand{\enablepinyin}{}{}
```

File 427 **lwarp-xr.sty**

§ 525 Package xr

(*Emulates or patches code by* Jean-Pierre Drucbert, David Carlisle.)

Pkg xr xr is patched for use by lwarp. The `*_html.aux` file is used. `\externaldocument` is modified to also accept the optional arguments for xr-hyper, which currently uses xr for HTML output.

See section 5.17.

for HTML output:

```
\LWR@ProvidesPackagePass{xr}[2019/07/22]%

\LetLtxMacro\LWR@orig@externaldocument\externaldocument

\RenewDocumentCommand{\externaldocument}{O{} O{} m O{}}{%
    \ifblank{#1}{%
        \LWR@orig@externaldocument{#3_html}%
    }{%
        \LWR@orig@externaldocument[#1]{#3_html}%
    }%
}
```

File 428 **lwarp-xr-hyper.sty**

§ 526 Package xr-hyper

(*Emulates or patches code by* David Carlisle.)

Pkg xr-hyper xr-hyper is replaced by xr, which is modified to accept the optional arguments for \externaldocument. So far, no hyperlinks are provided for citations.

See section 5.17.

for HTML output:

```
\LWR@ProvidesPackageDrop{xr-hyper}[2019/10/03]%

\LWR@origRequirePackage{lwarp-xr}
```

File 429 **lwarp-xtab.sty**

§ 527 Package xtab

(*Emulates or patches code by* Peter Wilson.)

Pkg xtab xtab is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xtab}[2011/07/31]
```

⚠ Misplaced alignment tab character &

For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a lateximage.

```
\newcommand{\LWRXT@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRXT@firsthead{#1}%
}

\newcommand{\tablehead}[1]{}

\newcommand{\tablelasthead}[1]{}

\newcommand{\notablelasthead}{}

\newcommand{\tabletail}[1]{}
```

```
15
16 \newcommand{\LWRXT@lasttail}{}
17
18 \newcommand{\tablelasttail}[1]{%
19     \long\gdef\LWRXT@lasttail{#1}%
20 }


21 \newcommand{\tablecaption}[2][]{%
22     \long\gdef\LWRXT@caption{%
23         \ifblank{#1}%
24             {\caption{#2}}%
25             {\caption[#1]{#2}}%
26     }%
27 }
28
29 \let\topcaption\tablecaption
30 \let\bottomcaption\tablecaption


31 \newcommand*{\LWRXT@caption}{}
32
33 \newcommand*{\shrinkheight}[1]{}
34
35 \newcommand*{\xentrystretch}[1]{}
36
37 \NewDocumentEnvironment{xtabular}{s o m}
38 {%
39 \LWR@traceinfo{xtabular}%
40 \table%
41 \LWRXT@caption%
42 \begin{tabular}{#3}%
43 \TabularMacro\ifdefvoid{\LWRXT@firsthead}%
44 {\LWR@getmynexttoken}%
45 {\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
46 }%
47 {%
48 \ifdefvoid{\LWRXT@lasttail}%
49 {}%
50 {%
51 \TabularMacro\ResumeTabular%
52 \LWRXT@lasttail%
53 }%
54 \end{tabular}%
55 \endtable%


56 \gdef\LWRXT@caption{}%


57 \LWR@traceinfo{xtabular done}%
58 }
59
60 \NewDocumentEnvironment{mpxtabular}{s o m}
61 {\minipage{\linewidth}\xtabular{#3}}
62 {\endxtabular\endminipage}
```

File 430 **lwarp-xunicode.sty**

§ 528 Package

xunicode

Pkg xunicode

Error if xunicode is loaded after lwarp.

Patch lwarp-xunicode, but also verify that is was loaded before lwarp:

for HTML output:

```
\LWR@loadbefore{xunicode}%

\LWR@ProvidesPackagePass{xunicode}[2011/09/09]
```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with textcomp.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
    \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{textcircled}
```

Nullify xunicode macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobang}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
```

```
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify
```

File 431 **lwarp-xurl.sty**

§ 529 Package xurl

Pkg xurl xurl is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xurl}[2018/06/02]
```

File 432 **lwarp-xy.sty**

§ 530 Package xy

(*Emulates or patches code by* Kristoffer H. Rose, Ross Moore.)

Pkg xy xy is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{xy}[2013/10/06]
```

After xy modules have been loaded:

```
\AtBeginDocument{
```

The original definitions without a `lateximage`:

```
\LetLtxMacro\LWR@orig@xy\xy
\LetLtxMacro\LWR@orig@endxy\endxy
```

The outer-most `xy` environment is placed in a `lateximage`, but not more than one level deep, which would conflict with xy:

```
\renewcommand*{\xy}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\addtocounter{LWR@lateximagedepth}{1}}%
        {\begin{lateximage}[-xy-~\PackageDiagramAltText]}%
    \LWR@orig@xy%
}

\renewcommand*{\endxy}{%
    \LWR@orig@endxy%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
```

```
        {\addtocounter{LWR@lateximagedepth}{-1}}%
        {\end{lateximage}}%
}
```

The \xybox must use the original definitions of \xy, \endxy:

```
\def\xybox#1{%
    \LWR@orig@xy#1\LWR@orig@endxy%
    \Edge@c={\rectangleEdge}\computeLeftUpness@%
}
```

If \xygraph is used, it is placed inside a lateximage:

```
\@ifundefined{xygraph}{}{
\LetLtxMacro\LWR@origxygraph\xygraph
\renewcommand{\xygraph}[1]{%
    \begin{lateximage}[-xy- xygraph \PackageDiagramAltText]
    \LWR@origxygraph{#1}
    \end{lateximage}
}
}% xygraph defined
}% AtBeginDocument
```

File 433 **lwarp-zhlineskip.sty**

§ 531 Package zhlineskip

Pkg zhlineskip zhlineskip is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{zhlineskip}[2019/05/15]

\newcommand*\SetTextEnvironmentSinglespace[1]{}
\newcommand*\RestoreTextEnvironmentLeading[1]{}
\newcommand*\SetMathEnvironmentSinglespace[1]{}
\newcommand*\RestoreMathEnvironmentLeading[1]{}
```

File 434 **lwarp-zwpagelayout.sty**

§ 532 Package zwpagelayout

(*Emulates or patches code by* Zdeněk Wagner.)

Pkg zwpagelayout zwpagelayout is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{zwpagelayout}[2013/01/13]
```

```
\def\noBboxes{}
\@onlypreamble\noBboxes

\expandafter\ifx\csname definecolor\endcsname\relax \else
  \definecolor{cmykblack}{cmyk}{0,0,0,1}
  \definecolor{grblack}{gray}{0}
%   \ifzwpl@redefineblack
%     \definecolor{black}{cmyk}{0,0,0,1}\color{black}
%   \fi
  \definecolor{cmykred}{cmyk}{0,1,1,0}
  \definecolor{cmykgreen}{cmyk}{1,0,1,0}
  \definecolor{cmykblue}{cmyk}{1,1,0,0}
  \definecolor{rgbred}{rgb}{1,0,0}
  \definecolor{rgbgreen}{rgb}{0,1,0}
  \definecolor{rgbblue}{rgb}{0,0,1}
%   \ifzwpl@redefinetocmyk
%     \definecolor{red}{cmyk}{0,1,1,0}
%     \definecolor{green}{cmyk}{1,0,1,0}
%     \definecolor{blue}{cmyk}{1,1,0,0}
%   \fi
\fi

\let\OverprintXeTeXExtGState\relax

\DeclareRobustCommand\SetOverprint{\ignorespaces}
\DeclareRobustCommand\SetKnockout{\ignorespaces}
\DeclareRobustCommand\textoverprint[1]{{\SetOverprint#1}}
\DeclareRobustCommand\textknockout[1]{{\SetKnockout#1}}

\def\SetPDFminorversion#1{}
\@onlypreamble\SetPDFminorversion

\newcommand*\Vcorr{}

\DeclareRobustCommand\vb[1][]{}
\NewDocumentCommand{\NewOddPage}{* o}{}
\NewDocumentCommand{\NewEvenPage}{* o}{}
\def\SetOddPageMessage#{\gdef\ZW@oddwarning}
\def\SetEvenPageMessage#{\gdef\Z@@evenwarning}
\def\ZW@oddwarning{Empty page inserted}\let\ZW@evenwarning\ZW@oddwarning

\def\clap#1{#1}

\def\CropFlap{2in}
\def\CropSpine{1in}
\def\CropXSpine{1in}
\def\CropXtrim{.25in}
\def\CropYtrim{.25in}
\def\UserWidth{5in}
\def\UserLeftMargin{1in}
\def\UserRightMargin{1in}
\def\UserTopMargin{1in}
\def\UserBotMargin{1in}
\def\thePageNumber{\LWR@origpound\,\arabic{page}}
\ifXeTeX
```

```
\def\ifcaseZWdriver{\ifcase2}
\else
\def\ifcaseZWdriver{\ifcase1}
\fi
\DeclareRobustCommand\ZWifdriver[2]{}
```

File 435 **lwarp-patch-komascript.sty**

§ 533 Package

patch-komascript

Pkg lwarp-patch-komascript

Patches for komascript classes.

lwarp loads this package when scrbook, scrartcl, or scrreprt classes are detected.

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

`\titlehead`, `\subject`, `\captionformat`, `\figureformat`, and `\tableformat` are not yet emulated.

⚠ Not fully tested! Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

for HTML output:

```
\ProvidesPackage{lwarp-patch-komascript}
```

typearea is emulated.

```
\RequirePackage{lwarp-typearea}
```

tocbasic is emulated.

```
\RequirePackage{lwarp-tocbasic}
```

scrextend patches most of the new macros.

```
\RequirePackage{lwarp-scrextend}
```

Indexing macros, simplified for lwarp:

```
\AtBeginDocument{

\renewcommand*{\idx@heading}{%
  \idx@@heading{\indexname}%
}

\renewenvironment{theindex}{%
  \idx@heading%
  \index@preamble\par\nobreak
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
```

```
}
{}

\renewcommand*\indexspace{}

}% AtBeginDocument
```

The \minisec is placed inside a of class minisec.

```
\renewcommand*{\minisec}[1]{
\begin{BlockClass}{minisec}
#1
\end{BlockClass}
}
```

The part and chapter preambles are placed as plain text just after each heading.

```
\@ifundefined{setpartpreamble}{}{
\RenewDocumentCommand{\setpartpreamble}{o o +m}{%
\renewcommand{\part@preamble}{#3}%
}
}

\@ifundefined{setchapterpreamble}{}{
\RenewDocumentCommand{\setchapterpreamble}{o o +m}{%
\renewcommand{\chapter@preamble}{#3}%
}
}
```

Simple captions are used in all cases.

```
\AtBeginDocument{
    \LetLtxMacro\captionbelow\caption
    \LetLtxMacro\captionabove\caption

    \LetLtxMacro\captionofbelow\captionof
    \LetLtxMacro\captionofabove\captionof
}

\RenewDocumentEnvironment{captionbeside}{o m o o o s}
{}
{%
\IfValueTF{#1}%
{\caption[#1]{#2}}%
{\caption{#2}}%
}

\RenewDocumentEnvironment{captionofbeside}{m o m o o o s}
{}
{%
\IfValueTF{#2}%
{\captionof{#1}[#2]{#3}}%
{\captionof{#1}{#3}}%
}

```

```
\RenewDocumentCommand{\setcapindent}{s m}{}
\renewcommand*{\setcaphanging}{}
\renewcommand*{\setcapwidth}[2][]{}
\renewcommand*{\setcapdynwidth}[2][]{}
\RenewDocumentCommand{\setcapmargin}{s o m}{}
```

File 436 **lwarp-patch-memoir.sty**

§ 534 Package

patch-memoir

(*Emulates or patches code by* Peter Wilson.)

Pkg lwarp-patch-memoir

Patches for memoir class.

⚠ Not fully tested!

Please send bug reports!

lwarp loads this package when the memoir class is detected.

⚠ options clash

While emulating memoir, lwarp pre-loads a number of packages (section 534.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

`\verbfootnote` is not supported.

`\newfootnoteseries`, etc. are not supported.

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in `\pagenotesubhead` and related macros.

Poem numbering is not supported.

The `verbatim` environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

for HTML output:

```
\ProvidesPackage{lwarp-patch-memoir}
```

§ 534.1 Packages

These are pre-loaded to provide emulation for many of memoir's functions. memoir pretends that abstract, etc. are already loaded, via its "emulated" package mechanism, but lwarp is directly loading the "`lwarp-`" version of each, which happens to avoid memoir's emulation system.

```
\RequirePackage{lwarp-abstract}% req'd
\RequirePackage{lwarp-array}% req'd
\RequirePackage{lwarp-booktabs}% req'd
% \RequirePackage{lwarp-ccaption}% emualated below
\RequirePackage{lwarp-changepage}% req'd
\RequirePackage{lwarp-crop}
\RequirePackage{lwarp-dcolumn}% req'd
\RequirePackage{lwarp-enumerate}% req'd
\RequirePackage{lwarp-epigraph}% req'd
\RequirePackage{lwarp-fancyvrb}% req'd
\RequirePackage{lwarp-footmisc}% req'd
\RequirePackage{lwarp-framed}% req'd
\RequirePackage{lwarp-hanging}% req'd
\RequirePackage{lwarp-makeidx}% req'd
\DisemulatePackage{moreverb}
\RequirePackage{lwarp-moreverb}
\RequirePackage{lwarp-mparhack}
\RequirePackage{lwarp-needspace}% req'd
\RequirePackage{lwarp-nextpage}% req'd
\RequirePackage{lwarp-pagenote}% req'd
\RequirePackage{lwarp-parskip}
\RequirePackage{lwarp-setspace}% req'd
\RequirePackage{lwarp-showidx}
\RequirePackage{lwarp-subfigure}% red'q
\makeindex
```

subfigure is emulated via subfig, which pre-defines `subfigure` and `subtable`, but memoir does not, so they must be tested for here:

```
\LetLtxMacro\LWR@memorignewsubfloat\newsubfloat
\RenewDocumentCommand{\newsubfloat}{O{} m}{%
    \@ifundefined{c@sub#2}{%
        \LWR@memorignewsubfloat[#1]{#2}%
    }{}%
}

\RequirePackage{lwarp-tabularx}% req'd
\RequirePackage{lwarp-titling}% req'd
% \RequirePackage{lwarp-tocbibind}% not emulated by memoir
\RequirePackage{lwarp-tocloft}% req'd
\RequirePackage{lwarp-verse}% req'd
```

§ 534.2 Preliminary setup

Bypass the memoir package mechanism:

```
\LetLtxMacro\LWR@orig@label\@mem@old@label
```

memoir already set the page size to a default, so it must be forced large for lwarp's use, to avoid tag overflows off the page.

```
\setstocksize{190in}{20in}
\setlrmarginsandblock{2in}{2in}{*}
\setulmarginsandblock{1in}{1in}{*}
```

§ 534.3 Page layout

```
\renewcommand*{\stockavi}{}
\renewcommand*{\stockav}{}
\renewcommand*{\stockaiv}{}
\renewcommand*{\stockaiii}{}
\renewcommand*{\stockbvi}{}
\renewcommand*{\stockbv}{}
\renewcommand*{\stockbiv}{}
\renewcommand*{\stockbiii}{}
% \renewcommand*{\stockmetriccrownvo}{}% in docs but not in the package
\renewcommand*{\stockmlargecrownvo}{}
\renewcommand*{\stockmdemyvo}{}
\renewcommand*{\stockmsmallroyalvo}{}
\renewcommand*{\pageavi}{}
\renewcommand*{\pageav}{}
\renewcommand*{\pageaiv}{}
\renewcommand*{\pageaiii}{}
\renewcommand*{\pagebvi}{}
\renewcommand*{\pagebv}{}
\renewcommand*{\pagebiv}{}
\renewcommand*{\pagebiii}{}
% \renewcommand*{\pagemetriccrownvo}{}% in docs but not in the package
\renewcommand*{\pagemlargecrownvo}{}
\renewcommand*{\pagemdemyvo}{}
\renewcommand*{\pagemsmallroyalvo}{}

\renewcommand*{\stockdbill}{}
\renewcommand*{\stockstatement}{}
\renewcommand*{\stockexecutive}{}
\renewcommand*{\stockletter}{}
\renewcommand*{\stockold}{}
\renewcommand*{\stocklegal}{}
\renewcommand*{\stockledger}{}
\renewcommand*{\stockbroadsheet}{}
\renewcommand*{\pagedbill}{}
\renewcommand*{\pagestatement}{}
\renewcommand*{\pageexecutive}{}
\renewcommand*{\pageletter}{}
\renewcommand*{\pageold}{}
\renewcommand*{\pagelegal}{}
\renewcommand*{\pageledger}{}
```

```
\renewcommand*{\pagebroadsheet}{}

\renewcommand*{\stockpottvo}{}
\renewcommand*{\stockfoolscapvo}{}
\renewcommand*{\stockcrownvo}{}
\renewcommand*{\stockpostvo}{}
\renewcommand*{\stocklargecrownvo}{}
\renewcommand*{\stocklargepostvo}{}
\renewcommand*{\stocksmalldemyvo}{}
\renewcommand*{\stockdemyvo}{}
\renewcommand*{\stockmediumvo}{}
\renewcommand*{\stocksmallroyalvo}{}
\renewcommand*{\stockroyalvo}{}
\renewcommand*{\stocksuperroyalvo}{}
\renewcommand*{\stockimperialvo}{}
\renewcommand*{\pagepottvo}{}
\renewcommand*{\pagefoolscapvo}{}
\renewcommand*{\pagecrownvo}{}
\renewcommand*{\pagepostvo}{}
\renewcommand*{\pagelargecrownvo}{}
\renewcommand*{\pagelargepostvo}{}
\renewcommand*{\pagesmalldemyvo}{}
\renewcommand*{\pagedemyvo}{}
\renewcommand*{\pagemediumvo}{}
\renewcommand*{\pagesmallroyalvo}{}
\renewcommand*{\pageroyalvo}{}
\renewcommand*{\pagesuperroyalvo}{}
\renewcommand*{\pageimperialvo}{}

\renewcommand*{\memfontfamily}{}
\renewcommand*{\memfontenc}{}
\renewcommand*{\memfontpack}{}

\renewcommand*{\anyptfilebase}{}
\renewcommand*{\anyptsize}{10}

\renewcommand*{\setstocksize}[2]{}
\renewcommand*{\settrimmedsize}[3]{}
\renewcommand*{\settrims}[2]{}

% \newlength{\lxvchars}
% \setlength{\lxvchars}{305pt}
% \newlength{\xlvchars}
% \setlength{\xlvchars}{190pt}
\renewcommand*{\setxlvchars}[1]{}
\renewcommand*{\setlxvchars}[1]{}

\renewcommand*{\settypeblocksize}[3]{}
\renewcommand*{\setlrmargins}[3]{}
\renewcommand*{\setlrmarginsandblock}[3]{}
\renewcommand*{\setbinding}[1]{}
\renewcommand*{\setulmargins}[3]{}
\renewcommand*{\setulmarginsandblock}[3]{}
\renewcommand*{\setcolsepandrule}[2]{}

```

```
\renewcommand*{\setheadfoot}[2]{}
\renewcommand*{\setheaderspaces}[3]{}
\renewcommand*{\setmarginnotes}[3]{}
\renewcommand*{\setfootins}[2]{}
\renewcommand*{\checkandfixthelayout}[1][]{}
\renewcommand*{\checkthelayout}[1]{}
\renewcommand*{\fixthelayout}{}
%
% \newlength{\stockheight}
% \newlength{\trimtop}
% \newlength{\trimedge}
% \newlength{\stockwidth}
% \newlength{\spinemargin}
% \newlength{\foremargin}
% \newlength{\uppermargin}
% \newlength{\headmargin}
%
\renewcommand*{\typeoutlayout}{}
\renewcommand*{\typeoutstandardlayout}{}
\renewcommand*{\settypeoutlayoutunit}[1]{}
\renewcommand*{\fixpdflayout}{}
\renewcommand*{\fixdvipslayout}{}

\renewcommand*{\medievalpage}[1][]{}
\renewcommand*{\isopage}[1][]{}
\renewcommand*{\semiisopage}[1][]{}

\renewcommand{\setpagebl}[3]{}
\renewcommand{\setpageml}[3]{}
\renewcommand{\setpagetl}[3]{}
\renewcommand{\setpagetm}[3]{}
\renewcommand{\setpagetr}[3]{}
\renewcommand{\setpagemr}[3]{}
\renewcommand{\setpagebr}[3]{}
\renewcommand{\setpagebm}[3]{}
\renewcommand{\setpagecc}[3]{}
```

§ 534.4 Text and fonts

```
\let\miniscule\tiny
\let\HUGE\Huge

\renewcommand*{\abnormalparskip}[1]{}
\renewcommand*{\nonzeroparskip}{}
\renewcommand*{\traditionalparskip}{}

\let\onelineskip\baselineskip

\let\OnehalfSpacing\onehalfspacing
\let\DoubleSpacing\doublespacing
\renewcommand*{\setPagenoteSpacing}[1]{}
\renewcommand*{\setFloatSpacing}[1]{}
\let\SingleSpacing\singlespacing
\let\setSingleSpace\SetSinglespace
\let\SingleSpace\singlespace
\let\endSingleSpace\endsinglespace
```

```
\let\Spacing\spacing
\let\endSpacing\endspacing
\let\OnehalfSpace\onehalfspace
\let\endOnehalfSpace\endonehalfspace
\csletcs{OnehalfSpace*}{onehalfspace}
\csletcs{endOnehalfSpace*}{endonehalfspace}
\let\DoubleSpace\doublespace
\let\endDoubleSpace\enddoublespace
\csletcs{DoubleSpace*}{doublespace}
\csletcs{endDoubleSpace*}{enddoublespace}
\renewcommand*{\setDisplayskipStretch}[1]{}
\renewcommand*{\memdskipstretch}{}
\renewcommand*{\noDisplayskipStretch}{}
\renewcommand*{\memdskips}{}

\renewcommand*{\midsloppy}{}
\renewenvironment*{midsloppypar}{}{}

\renewcommand*{\sloppybottom}{}
```

§ 534.5 Titles

```
\csletcs{titlingpage*}{titlingpage}
\csletcs{endtitlingpage*}{endtitlingpage}
\let\titlingpageend\relax
\newcommand{\titlingpageend}[2]{}
\let\andnext\and
\renewcommand*{\thanksmarkstyle}[1]{}
\renewcommand{\thanksfootmark}{%
\thanksscript{\tamark}%
}

% \newlength{\thanksmarksep}
```

§ 534.6 Abstracts

```
\renewcommand*{\abstractcol}{}
\renewcommand*{\abstractintoc}{}
\renewcommand*{\abstractnum}{}
\renewcommand*{\abstractrunin}{}
```

§ 534.7 Docment divisions

\book * (⟨*2:PDF name*⟩) [⟨*3:TOC name*⟩] [⟨*4:PDF name*⟩] (⟨*5:PDF name*⟩) {⟨*6:name*⟩}

```
\DeclareDocumentCommand{\book}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{book}%
}

\def\@apppage{%
    \part*{\appendixpagename}
}
\renewcommand\mempreaddapppagetotochook{}
\renewcommand\mempostaddapppagetotochook{}

```

```
\def\@sapppage{%
    \part*{\appendixpagename}
}

\DeclareDocumentCommand{\mainmatter}{s}{%
    \booltrue{LWR@mainmatter}%
}

\DeclareDocumentCommand{\frontmatter}{s}{%
\boolfalse{LWR@mainmatter}%
}

\renewcommand*{\raggedbottomsection}{}
\renewcommand*{\normalbottomsection}{}
\renewcommand*{\bottomsectionskip}{}
\renewcommand*{\bottomsectionpenalty}{}
\csletcs{appendixpage*}{appendixpage}
\renewcommand*{\namedsubappendices}{}
\renewcommand*{\unnamedsubappendices}{}
\renewcommand*{\setsecnumdepth}[1]{}% todo tocvsec2
\renewcommand*{\maxsecnumdepth}[1]{}% todo tocvsec2
\renewcommand*{\beforebookskip}{}
\renewcommand*{\afterbookskip}{}
\renewcommand*{\beforepartskip}{}
\renewcommand*{\afterpartskip}{}
\renewcommand*{\midbookskip}{}
\renewcommand*{\midpartskip}{}
\renewcommand*{\printbookname}{}
\renewcommand*{\booknamefont}{}
\renewcommand*{\booknamenum}{}
\renewcommand*{\printbooknum}{}
\renewcommand*{\booknumfont}{}
\renewcommand*{\printpartname}{}
\renewcommand*{\partnamefont}{}
\renewcommand*{\partnamenum}{}
\renewcommand*{\printpartnum}{}
\renewcommand*{\partnumfont}{}
\renewcommand*{\printbooktitle}[1]{}
\renewcommand*{\booktitlefont}{}
\renewcommand{\printparttitle}[1]{}
\renewcommand*{\parttitlefont}{}
\renewcommand*{\bookpageend}{}
\renewcommand*{\bookblankpage}{}
\renewcommand*{\nobookblankpage}{}
\renewcommand*{\partpageend}{}
\renewcommand*{\partblankpage}{}
\renewcommand*{\nopartblankpage}{}
\RenewDocumentCommand{\newleadpage}{s o m m}{}% todo
\RenewDocumentCommand{\renewleadpage}{s o m m}{}% todo
\renewcommand*{\leadpagetoclevel}{chapter}

\renewcommand*{\openright}{}
\renewcommand*{\openleft}{}
\renewcommand*{\openany}{}
\renewcommand*{\clearforchapter}{}
```

```
\renewcommand*{\memendofchapterhook}{}
\renewcommand*{\chapterheadstart}{}
% \newlength{\beforechapskip}
\renewcommand*{\afterchapternum}{}
% \newlength{\midchapskip}
\renewcommand*{\afterchaptertitle}{}
% \newlength{\afterchapskip}
\renewcommand*{\printchaptername}{}
\renewcommand*{\chapnamefont}{}
\renewcommand*{\chapternamenum}{}
\renewcommand*{\printchapternum}{}
\renewcommand*{\chapnumfont}{}
\renewcommand{\printchaptertitle}[1]{}
\renewcommand*{\chaptitlefont}{}
\renewcommand*{\printchapternonum}{}
\renewcommand*{\indentafterchapter}{}
\renewcommand*{\noindentafterchapter}{}
\renewcommand*{\insertchapterspace}{}

\renewcommand*{\chapterstyle}[1]{}
\renewcommand{\makechapterstyle}[2]{}
\renewcommand*{\chapindent}{}
\let\chapterprecis\cftchapterprecis
\let\chapterprecishere\cftchapterprecishere
\let\chapterprecistoc\cftchapterprecistoc
\renewcommand*{\precisfont}{}
\renewcommand*{\prechapterprecis}{}
\renewcommand*{\postchapterprecis}{}
\renewcommand{\precistoctext}[1]{}
\renewcommand*{\precistocfont}{}
\renewcommand*{\precistocformat}{}
% \newlength{\prechapterprecisshift}

\renewcommand*{\setbeforesecskip}[1]{}
\renewcommand*{\setaftersecskip}[1]{}
\renewcommand*{\setsecindent}[1]{}
\renewcommand*{\setsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsecskip}[1]{}
\renewcommand*{\setaftersubsecskip}[1]{}
\renewcommand*{\setsubsecindent}[1]{}
\renewcommand*{\setsubsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsubsecskip}[1]{}
\renewcommand*{\setaftersubsubsecskip}[1]{}
\renewcommand*{\setsubsubsecindent}[1]{}
\renewcommand*{\setsubsubsecheadstyle}[1]{}
\renewcommand*{\setbeforeparaskip}[1]{}
\renewcommand*{\setafterparaskip}[1]{}
\renewcommand*{\setparaindent}[1]{}
\renewcommand*{\setparaheadstyle}[1]{}
\renewcommand*{\setbeforesubparaskip}[1]{}
\renewcommand*{\setaftersubparaskip}[1]{}
\renewcommand*{\setsubparaindent}[1]{}
\renewcommand*{\setsubparaheadstyle}[1]{}
\renewcommand{\@hangfrom}[1]{#1}
\renewcommand{\sethangfrom}[1]{}
```

```
\renewcommand{\setsecnumformat}[1]{}

\renewcommand*{\hangsecnum}{}
\renewcommand*{\defaultsecnum}{}

\renewcommand*{\sechook}{}
\renewcommand{\setsechook}[1]{}
\renewcommand*{\subsechook}{}
\renewcommand{\setsubsechook}[1]{}
\renewcommand*{\subsubsechook}{}
\renewcommand{\setsubsubsechook}[1]{}
\renewcommand*{\parahook}{}
\renewcommand{\setparahook}[1]{}
\renewcommand*{\subparahook}{}
\renewcommand{\setsubparahook}[1]{}

\RenewDocumentCommand{\plainbreak}{s m}{\begin{center}~\end{center}}

\RenewDocumentCommand{\fancybreak}{s +m}{%
\begin{center}#2\end{center}%
}

\RenewDocumentCommand{\plainfancybreak}{s m m +m}{%
\begin{center}#4\end{center}%
}

\RenewDocumentCommand{\pfbreak}{s}{%
\begin{center}
\pfbreakdisplay
\end{center}
}

% \newlength{\pfbreakskip}
\renewcommand{\pfbreakdisplay}{*\quad*\quad*}

\renewcommand{\makeheadstyles}[2]{}
\renewcommand*{\headstyles}[1]{}
```

§ 534.8 Pagination and headers

```
\renewcommand*{\savepagenumber}{}
\renewcommand*{\restorepagenumber}{}
\renewcommand*{\uppercaseheads}{}
\renewcommand*{\nouppercaseheads}{}

\renewcommand*{\bookpagemark}[1]{}
\renewcommand*{\partmark}[1]{}
\renewcommand*{\bibmark}{}
\renewcommand*{\indexmark}{}
\renewcommand*{\glossarymark}{}

\LWR@origpagestyle{empty}
\renewcommand*{\ps@empty}{}
\renewcommand*{\makepagestyle}[1]{}
\renewcommand*{\emptypshook}{}%
% \renewcommand*{\empty@oddhead}{}
```

```
% \renewcommand*{\empty@oddfoot}{}
% \renewcommand*{\empty@evenhead}{}
% \renewcommand*{\empty@evenfoot}{}
\renewcommand*{\@oddhead}{}
\renewcommand*{\@oddfoot}{}
\renewcommand*{\@evenhead}{}
\renewcommand*{\@evenfoot}{}
\renewcommand*{\aliaspagestyle}[2]{}
\renewcommand*{\copypagestyle}[2]{}

\renewcommand*{\makeevenhead}[4]{}
\renewcommand*{\makeoddhead}[4]{}
\renewcommand*{\makeevenfoot}[4]{}
\renewcommand*{\makeoddfoot}[4]{}
\renewcommand*{\makerunningwidth}[3]{}
% \newlength{\headwidth}
\renewcommand*{\makeheadrule}[3]{}
\renewcommand*{\makefootrule}[3]{}
\renewcommand*{\makeheadfootruleprefix}[3]{}
% \newlength{\normalrulethickness}
% \setlength{\normalrulethickness}{.4pt}
% \newlength{\footruleheight}
% \newlength{\footruleskip}
\renewcommand*{\makeheadposition}[5]{}
\renewcommand{\makepsmarks}[2]{}
\renewcommand*{\makeheadfootstrut}[3]{}

\renewcommand{\createplainmark}[3]{}
\renewcommand{\memUChead}[1]{}
\renewcommand{\createmark}[5]{}
\renewcommand*{\clearplainmark}[1]{}
\renewcommand*{\clearmark}[1]{}
\renewcommand{\addtopsmarks}[3]{}
\renewcommand{\ifonlyfloats}[2]{#2}
\renewcommand*{\mergepagefloatstyle}[3]{}

\renewcommand*{\framepichead}{}
\renewcommand*{\framepictextfoot}{}
\renewcommand*{\framepichook}{}
\renewcommand*{\showheadfootlocoff}{}
\renewcommand*{\showtextblocklocoff}{}
```

§ 534.9 Paragraphs and lists

```
\renewcommand{\hangfrom}[1]{#1}
\let\centerfloat\centering
\renewcommand*{\raggedyright}[1][]{}
% \newlength{\ragrparindent}
\renewcommand{\sourceatright}[2][]{\attribution{#2}}
\let\memorigdbs\LWR@endofline
\let\memorigpar\par
\let\atcentercr\LWR@endofline

\renewcommand*{\linenottooshort}[1][]{}
\renewcommand*{\russianpar}{}
\renewcommand*{\lastlinerulefill}{}
```

```
\renewcommand*{\lastlineparrule}{}
\renewcommand*{\justlastraggedleft}{}
\renewcommand*{\raggedrightthenleft}{}
\renewcommand*{\leftcenterright}{}

\renewcommand{\leftspringright}[4]{%
\begin{minipage}{#1\linewidth}#3\end{minipage}\qquad%
\begin{minipage}{#2\linewidth}\begin{flushright}#4\end{flushright}\end{minipage}%
}

\renewenvironment*{blockdescription}
{\LWR@descriptionstart\LWR@origdescription}
{\enddescription}
\renewcommand*{\blockdescriptionlabel}[1]{\textbf{#1}}
\renewenvironment*{labelled}[1]{\begin{description}}{\end{description}}
\renewenvironment*{flexlabelled}[6]{\begin{description}}{\end{description}}
\renewcommand*{\tightlists}{}
\renewcommand*{\defaultlists}{}
\RenewDocumentCommand{\firmlists}{s}{}
\renewcommand*{\firmlist}{}
\renewcommand*{\tightlist}{}
\renewcommand*{\zerotrivseps}{}
\renewcommand*{\savetrivseps}{}
\renewcommand*{\restoretrivseps}{}
```

§ 534.10 Contents lists

```
\csletcs{tableofcontents*}{tableofcontents}
\csletcs{listoffigures*}{listoffigures}
\csletcs{listoftables*}{listoftables}
\renewenvironment{KeepFromToc}{}{}
\renewcommand*{\onecoltocetc}{}
\renewcommand*{\twocoltocetc}{}
\renewcommand*{\ensureonecol}{}
\renewcommand*{\restorefromonecol}{}
\renewcommand*{\doccoltocetc}{}
\renewcommand*{\maxtocdepth}[1]{}% tocvsec2
\renewcommand*{\settocdepth}[1]{}% tocvsec2

\renewcommand{\tocheadstart}{}
\renewcommand{\printtoctitle}[1]{}
\renewcommand{\tocmark}{}
\renewcommand{\aftertoctitle}{}
\renewcommand{\lofheadstart}{}
\renewcommand{\printloftitle}[1]{}
\renewcommand{\lofmark}{}
\renewcommand{\afterloftitle}{}
\renewcommand{\lotheadstart}{}
\renewcommand{\printlottitle}[1]{}
\renewcommand{\lotmark}{}
\renewcommand{\afterlottitle}{}

\renewcommand*{\setpnumwidth}[1]{}
\renewcommand*{\setrmarg}[1]{}
\renewcommand*{\cftbookbreak}{}
\renewcommand*{\cftpartbreak}{}
```

```
\renewcommand*{\cftchapterbreak}{}

% \newlength{\cftbeforebookskip}
% \newlength{\cftbookindent}
% \newlength{\cftbooknumwidth}
\renewcommand*{\cftbookfont}{}
\renewcommand*{\cftbookname}{}
\renewcommand*{\cftbookpresnum}{}
\renewcommand*{\cftbookaftersnum}{}
\renewcommand*{\cftbookaftersnumb}{}
\renewcommand*{\cftbookleader}{}
\renewcommand*{\cftbookdotsep}{1}
\renewcommand*{\cftbookpagefont}{}
\renewcommand*{\cftbookafterpnum}{}
\renewcommand*{\cftbookformatpnum}[1]{}
\renewcommand*{\cftbookformatpnumhook}[1]{}
```

Part is already defined by tocloft.

```
% \newlength{\cftbeforechapterskip}
% \newlength{\cftchapterindent}
% \newlength{\cftchapternumwidth}
\renewcommand*{\cftchapterfont}{}
\renewcommand*{\cftchaptername}{}
\renewcommand*{\cftchapterpresnum}{}
\renewcommand*{\cftchapteraftersnum}{}
\renewcommand*{\cftchapteraftersnumb}{}
\renewcommand*{\cftchapterleader}{}
\renewcommand*{\cftchapterdotsep}{1}
\renewcommand*{\cftchapterpagefont}{}
\renewcommand*{\cftchapterafterpnum}{}
\renewcommand*{\cftchapterformatpnum}[1]{}
\renewcommand*{\cftchapterformatpnumhook}[1]{}

% \newlength{\cftbeforesectionskip}
% \newlength{\cftsectionindent}
% \newlength{\cftsectionnumwidth}
\renewcommand*{\cftsectionfont}{}
\renewcommand*{\cftsectionname}{}
\renewcommand*{\cftsectionpresnum}{}
\renewcommand*{\cftsectionaftersnum}{}
\renewcommand*{\cftsectionaftersnumb}{}
\renewcommand*{\cftsectionleader}{}
\renewcommand*{\cftsectiondotsep}{1}
\renewcommand*{\cftsectionpagefont}{}
\renewcommand*{\cftsectionafterpnum}{}
\renewcommand*{\cftsectionformatpnum}[1]{}
\renewcommand*{\cftsectionformatpnumhook}[1]{}

% \newlength{\cftbeforesubsectionskip}
% \newlength{\cftsubsectionindent}
% \newlength{\cftsubsectionnumwidth}
\renewcommand*{\cftsubsectionfont}{}
\renewcommand*{\cftsubsectionname}{}
\renewcommand*{\cftsubsectionpresnum}{}
\renewcommand*{\cftsubsectionaftersnum}{}
```

```
\renewcommand*{\cftsubsectionaftersnumb}{}
\renewcommand*{\cftsubsectionleader}{}
\renewcommand*{\cftsubsectiondotsep}{1}
\renewcommand*{\cftsubsectionpagefont}{}
\renewcommand*{\cftsubsectionafterpnum}{}
\renewcommand*{\cftsubsectionformatpnum}[1]{}
\renewcommand*{\cftsubsectionformatpnumhook}[1]{}

% \newlength{\cftbeforesubsubsectionskip}
% \newlength{\cftsubsubsectionindent}
% \newlength{\cftsubsubsectionnumwidth}
\renewcommand*{\cftsubsubsectionfont}{}
\renewcommand*{\cftsubsubsectionname}{}
\renewcommand*{\cftsubsubsectionpresnum}{}
\renewcommand*{\cftsubsubsectionaftersnum}{}
\renewcommand*{\cftsubsubsectionaftersnumb}{}
\renewcommand*{\cftsubsubsectionleader}{}
\renewcommand*{\cftsubsubsectiondotsep}{1}
\renewcommand*{\cftsubsubsectionpagefont}{}
\renewcommand*{\cftsubsubsectionafterpnum}{}
\renewcommand*{\cftsubsubsectionformatpnum}[1]{}
\renewcommand*{\cftsubsubsectionformatpnumhook}[1]{}

% \newlength{\cftbeforeparagraphskip}
% \newlength{\cftparagraphindent}
% \newlength{\cftparagraphnumwidth}
\renewcommand*{\cftparagraphfont}{}
\renewcommand*{\cftparagraphname}{}
\renewcommand*{\cftparagraphpresnum}{}
\renewcommand*{\cftparagraphaftersnum}{}
\renewcommand*{\cftparagraphaftersnumb}{}
\renewcommand*{\cftparagraphleader}{}
\renewcommand*{\cftparagraphdotsep}{1}
\renewcommand*{\cftparagraphpagefont}{}
\renewcommand*{\cftparagraphafterpnum}{}
\renewcommand*{\cftparagraphformatpnum}[1]{}
\renewcommand*{\cftparagraphformatpnumhook}[1]{}

% \newlength{\cftbeforesubparagraphskip}
% \newlength{\cftsubparagraphindent}
% \newlength{\cftsubparagraphnumwidth}
\renewcommand*{\cftsubparagraphfont}{}
\renewcommand*{\cftsubparagraphname}{}
\renewcommand*{\cftsubparagraphpresnum}{}
\renewcommand*{\cftsubparagraphaftersnum}{}
\renewcommand*{\cftsubparagraphaftersnumb}{}
\renewcommand*{\cftsubparagraphleader}{}
\renewcommand*{\cftsubparagraphdotsep}{1}
\renewcommand*{\cftsubparagraphpagefont}{}
\renewcommand*{\cftsubparagraphafterpnum}{}
\renewcommand*{\cftsubparagraphformatpnum}[1]{}
\renewcommand*{\cftsubparagraphformatpnumhook}[1]{}

% \newlength{\cftbeforefigureskip}
% \newlength{\cftfigureindent}
% \newlength{\cftfigurenumwidth}
```

```
\renewcommand*{\cftfigurefont}{}
\renewcommand*{\cftfigurename}{}
\renewcommand*{\cftfigurepresnum}{}
\renewcommand*{\cftfigureaftersnum}{}
\renewcommand*{\cftfigureaftersnumb}{}
\renewcommand*{\cftfigureleader}{}
\renewcommand*{\cftfiguredotsep}{1}
\renewcommand*{\cftfigurepagefont}{}
\renewcommand*{\cftfigureafterpnum}{}
\renewcommand*{\cftfigureformatpnum}[1]{}
\renewcommand*{\cftfigureformatpnumhook}[1]{}

% \newlength{\cftbeforesubfigureskip}
% \newlength{\cftsubfigureindent}
% \newlength{\cftsubfigurenumwidth}
\newcommand*{\cftsubfigurefont}{}
\newcommand*{\cftsubfigurename}{}
\newcommand*{\cftsubfigurepresnum}{}
\newcommand*{\cftsubfigureaftersnum}{}
\newcommand*{\cftsubfigureaftersnumb}{}
\newcommand*{\cftsubfigureleader}{}
\newcommand*{\cftsubfiguredotsep}{1}
\newcommand*{\cftsubfigurepagefont}{}
\newcommand*{\cftsubfigureafterpnum}{}
\newcommand*{\cftsubfigureformatpnum}[1]{}
\newcommand*{\cftsubfigureformatpnumhook}[1]{}

% \newlength{\cftbeforetableskip}
% \newlength{\cfttableindent}
% \newlength{\cfttablenumwidth}
\renewcommand*{\cfttablefont}{}
\renewcommand*{\cfttablename}{}
\renewcommand*{\cfttablepresnum}{}
\renewcommand*{\cfttableaftersnum}{}
\renewcommand*{\cfttableaftersnumb}{}
\renewcommand*{\cfttableleader}{}
\renewcommand*{\cfttabledotsep}{1}
\renewcommand*{\cfttablepagefont}{}
\renewcommand*{\cfttableafterpnum}{}
\renewcommand*{\cfttableformatpnum}[1]{}
\renewcommand*{\cfttableformatpnumhook}[1]{}

% \newlength{\cftbeforesubtableskip}
% \newlength{\cftsubtableindent}
% \newlength{\cftsubtablenumwidth}
\newcommand*{\cftsubtablefont}{}
\newcommand*{\cftsubtablename}{}
\newcommand*{\cftsubtablepresnum}{}
\newcommand*{\cftsubtableaftersnum}{}
\newcommand*{\cftsubtableaftersnumb}{}
\newcommand*{\cftsubtableleader}{}
\newcommand*{\cftsubtabledotsep}{1}
\newcommand*{\cftsubtablepagefont}{}
\newcommand*{\cftsubtableafterpnum}{}
\newcommand*{\cftsubtableformatpnum}[1]{}
\newcommand*{\cftsubtableformatpnumhook}[1]{}
```

```
\renewcommand*{\booknumberline}[1]{}
\renewcommand*{\partnumberline}[1]{}
\renewcommand*{\chapternumberline}[1]{}
\renewcommand*{\numberlinehook}[1]{}
% \renewcommand*{\cftwhatismyname}{}%
\renewcommand*{\booknumberlinehook}[1]{}
\renewcommand*{\partnumberlinehook}[1]{}
\renewcommand*{\chapternumberlinehook}[1]{}
\renewcommand{\numberlinebox}[2]{}
\renewcommand{\booknumberlinebox}[2]{}
\renewcommand{\partnumberlinebox}[2]{}
\renewcommand{\chapternumberlinebox}[2]{}
%
% \newlength{\cftparfillskip}
\renewcommand*{\cftpagenumbersoff}[1]{}
\renewcommand*{\cftpagenumberson}[1]{}
\renewcommand*{\cftlocalchange}[3]{}
\renewcommand*{\cftaddtitleline}[4]{}
\renewcommand*{\cftaddnumtitleline}[4]{}
\renewcommand{\cftinsertcode}[2]{}
\renewcommand{\cftinserthook}[2]{}
\renewcommand{\settocpreprocessor}[2]{}
\DeclareRobustCommand{\cftpagenumbersoff}[1]{}
\DeclareRobustCommand{\cftpagenumberson}[1]{}
```

§ 534.11 Floats and captions

`\newfloat` `[`⟨*1: within*⟩`]` {⟨*2: type*⟩} {⟨*3: ext*⟩} {⟨*4: capname*⟩}

```
\RenewDocumentCommand{\newfloat}{o m m m}{%
\IfValueTF{#1}%
{\DeclareFloatingEnvironment[fileext=#3,within=#1,name={#4}]{#2}}%
{\DeclareFloatingEnvironment[fileext=#3,name={#4}]{#2}}%
```

newfloat package automatically creates the `\listof` command for new floats, but float does not, so remove `\listof` here in case it is manually created later.

```
\cslet{listof#2s}\relax%
\cslet{listof#2es}\relax%
}
```

`\newlistof` `[`⟨*within*⟩`]` {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the `\newfloat` mechanism. Note that memoir uses a different syntax than tocloft for the name.

```
\RenewDocumentCommand{\newlistof}{o m m m}
{%
\IfValueTF{#1}
{\newlistentry[#1]{#2}{#3}{0}}
{\newlistentry{#2}{#3}{0}}
\@namedef{ext@#2}{#3}%
\@ifundefined{c@#3depth}{\newcounter{#3depth}}{}%
\setcounter{#3depth}{1}%
\@namedef{#3mark}{}%
\@namedef{#2}{\listof{#2}{#4}}
\@namedef{@cftmake#3title}{}
```

```
\@ifundefined{cftbefore#3titleskip}{
    \expandafter\newlength\csname cftbefore#3titleskip\endcsname
    \expandafter\newlength\csname cftafter#3titleskip\endcsname
}{}
\@namedef{cft#3titlefont}{}
\@namedef{cftafter#3title}{}
\@namedef{cft#3prehook}{}
\@namedef{cft#3posthook}{}
}

\renewcommand{\setfloatadjustment}[2]{}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTmemoir@marginfloat}{O{-1.2ex} m}
{% start
\LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}

\DeclareDocumentEnvironment{marginfigure}{o}
  {\begin{KFLTmemoir@marginfloat}{figure}}
  {\end{KFLTmemoir@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
  {\begin{KFLTmemoir@marginfloat}{table}}
  {\end{KFLTmemoir@marginfloat}}

\renewcommand{\setmarginfloatcaptionadjustment}[2]{}
\renewcommand{\setmpjustification}[2]{}
\renewcommand*{\mpjustification}{}
\renewcommand*{\setfloatlocations}[2]{}
\DeclareDocumentCommand{\suppressfloats}{o}{}
\renewcommand*{\FloatBlock}{}
\renewcommand*{\FloatBlockAllowAbove}{}
\renewcommand*{\FloatBlockAllowBelow}{}
\renewcommand*{\setFloatBlockFor}{}

\renewcommand{\captiontitlefinal}[1]{}

\renewcommand{\flegtable}{\tablename}
\renewcommand{\flegfigure}{\figurename}
\renewcommand{\flegtoctable}{}
\renewcommand{\flegtocfigure}{}


\renewcommand{\subcaption}[2][]{%
\ifblank{#1}{\subfloat[#2]{}}{\subfloat[#1][#2]{}}%
}

\renewcommand{\contsubcaption}{\ContinuedFloat\subcaption}

```

```
\LetLtxMacro\subcaptionref\subref

\renewcommand*{\tightsubcaptions}{}
\renewcommand*{\loosesubcaptions}{}

\renewcommand*{\subcaptionsize}[1]{}
\renewcommand*{\subcaptionlabelfont}[1]{}
\renewcommand*{\subcaptionfont}[1]{}
\renewcommand*{\subcaptionstyle}[1]{}

\renewcommand*{\hangsubcaption}{}
\renewcommand*{\shortsubcaption}{}
\renewcommand*{\normalsubcaption}{}

\RenewDocumentEnvironment{sidecaption}{o m o}
{}
{
\IfValueTF{#1}{\caption[#1]{#2}}{\caption{#2}}%
\IfValueT{#3}{\label{#3}}%
}

% \newlength{\sidecapwidth}
% \newlength{\sidecapsep}
\renewcommand*{\setsidecaps}[2]{}
\renewcommand*{\sidecapmargin}[1]{}
% \newif\ifscapmargleft
\scapmargleftfalse
\renewcommand*{\setsidecappos}[1]{}

\RenewDocumentEnvironment{sidecontcaption}{m o}
{}
{%
\ContinuedFloat%
\caption{#1}%
```

Without `\@captype`, the section is referred to instead.

```
\IfValueT{#2}{\label[\@captype]{#2}}%
}
```

`\sidenamedlegend` does not appear to use the TOC argument.

```
\renewenvironment{sidenamedlegend}[2][]{
\begin{center}
\@nameuse{\@captype name}\CaptionSeparator#2
\end{center}
}
{}

\renewenvironment{sidelegend}[1]
{\begin{center}
#1

}
{\end{center}}
```

```
797
798 \renewcommand*{\sidecapstyle}{}
799 \renewcommand*{\overridescapmargin}[1]{}
800 % \newlength{\sidecapraise}
801 \renewcommand*{\sidecapfloatwidth}{\linewidth}
802
803 \LetLtxMacro\ctabular\tabular
804 \LetLtxMacro\endctabular\endtabular
805
806 \renewcommand{\autorows}[5][]{%
807 #5
808 }
809
810 \renewcommand{\autocols}[5][]{%
811 #5
812 }
```

§ 534.12 Page notes

```
813 \renewcommand*{\feetabovefloat}{}
814 \renewcommand*{\feetbelowfloat}{}
815 \renewcommand*{\feetatbottom}{}
816
817 \renewcommand*{\verbfootnote}[2][]{
818 \PackageError{lwarp,memoir}
819 {Verbatim footnotes are not yet supported by lwarp.}
820 {This may be improved some day.}
821 }
822
823 \renewcommand*{\plainfootnotes}{}
824 \renewcommand*{\twocolumnfootnotes}{}
825 \renewcommand*{\threecolumnfootnotes}{}
826 \renewcommand*{\paragraphfootnotes}{}
827 \renewcommand*{\footfudgefiddle}{}
828
829 \renewcommand*{\newfootnoteseries}[1]{
830 \PackageError{lwarp,memoir}
831 {Memoir footnote series are not yet supported by lwarp.}
832 {This may be improved some day.}
833 }
834
835 \renewcommand*{\plainfootstyle}[1]{}
836 \renewcommand*{\twocolumnfootstyle}[1]{}
837 \renewcommand*{\threecolumnfootstyle}[1]{}
838 \renewcommand*{\paragraphfootstyle}[1]{}
839
840 \renewcommand*{\footfootmark}{}
841 \renewcommand*{\footmarkstyle}[1]{}
842
843 % \newlength{\footmarkwidth}
844 % \newlength{\footmarksep}
845 % \newlength{\footparindent}
846
847 \renewcommand*{\foottextfont}{}
848
```

```
\renewcommand*{\marginparmargin}[1]{}
\renewcommand*{\sideparmargin}[1]{}

\LetLtxMacro\sidepar\marginpar
\renewcommand*{\sideparfont}{}
\renewcommand*{\sideparform}{}
\LWR@providelength{\sideparvshift}

\renewcommand*{\parnopar}{}

\renewcommand{\sidebar}[1]{\begin{quote}#1\end{quote}}
\renewcommand*{\sidebarmargin}[1]{}
\renewcommand*{\sidebarfont}{}
\renewcommand*{\sidebarform}{}
% \newlength{\sidebarhsep}
% \newlength{\sidebarvsep}
% \newlength{\sidebarwidth}
% \newlength{\sidebartopsep}
\renewcommand{\setsidebarheight}[1]{}
\renewcommand*{\setsidebars}[6]{}
\renewcommand*{\footnotesatfoot}{}
\renewcommand*{\footnotesinmargin}{}

\LetLtxMacro\sidefootnote\footnote
\LetLtxMacro\sidefootnotemark\footnotemark
\LetLtxMacro\sidefootnotetext\footnotetext

\renewcommand*{\sidefootmargin}[1]{}
% \newlength{\sidefoothsep}
% \newlength{\sidefootvsep}
% \newlength{\sidefootwidth}
% \newlength{\sidefootadjust}
% \newlength{\sidefootheight}
\renewcommand*{\setsidefootheight}[1]{}
% \renewcommand*{\sidefootfont}{}% in docs but not in the package
\renewcommand*{\setsidefeet}[6]{}
\renewcommand*{\sidefootmarkstyle}[1]{}
\renewcommand*{\sidefoottextfont}{}
\renewcommand*{\sidefootform}{}

\renewcommand*{\continuousnotenums}{\pncontopttrue}% from pagenote
\renewcommand*{\notepageref}{}
\renewcommand*{\prenotetext}{}
\renewcommand*{\postnotetext}{}
\renewcommand*{\idtextinnotes}[1]{}
\renewcommand*{\printpageinnotes}[1]{}
\renewcommand*{\printpageinnoteshyperref}[1]{}
\renewcommand*{\foottopagenote}{}
\renewcommand*{\pagetofootnote}{}
```

§ 534.13 Decorative text

```
\renewcommand*{\epigraphposition}[1]{}
\renewcommand*{\epigraphtextposition}[1]{}
\renewcommand*{\epigraphsourceposition}[1]{}
\renewcommand*{\epigraphfontsize}[1]{}
```

```
\renewcommand*{\epigraphforheader}[2][]{}
\renewcommand*{\epigraphpicture}{}
```

§ 534.14 Poetry

```
\renewcommand*{\vinphantom}{}
\renewcommand*{\vleftofline}[1]{#1}
% \let\linenumberfrequency\poemlines
% \renewcommand*{\linenumberfont}[1]{}

\DeclareDocumentCommand{\PoemTitle}{s o o m}{%
\IfValueTF{#2}%
{\poemtitle[#2]{#4}}%
{\poemtitle{#4}}%
}

\renewcommand*{\NumberPoemTitle}{}
\renewcommand*{\PlainPoemTitle}{}
\renewcommand*{\poemtitlepstyle}{}
\renewcommand*{\poemtitlestarmark}[1]{}
\renewcommand*{\poemtitlestarpstyle}{}
\renewcommand*{\PoemTitleheadstart}{}
\renewcommand*{\printPoemTitlenonum}{}
\renewcommand*{\printPoemTitlenum}{}
\renewcommand*{\afterPoemTitlenum}{}
\renewcommand*{\printPoemTitletitle}[1]{}
\renewcommand*{\afterPoemTitle}{}
\newlength{\midpoemtitleskip}
\renewcommand*{\PoemTitlenumfont}{}
\renewcommand*{\PoemTitlefont}{}
```

§ 534.15 Boxes, verbatims and files

```
\renewenvironment{qframe}{\framed}{\endframed}
\renewenvironment{qshade}{\shaded}{\endshaded}
```

Use the comment package:

```
\renewcommand*{\commentsoff}[1]{\includecomment{#1}}
\renewcommand*{\commentson}[1]{\excludecomment{#1}}
\LetLtxMacro\renewcomment\commentson

\renewcommand*{\setverbatimfont}[1]{}
\renewcommand*{\tabson}[1]{}
\renewcommand*{\tabsoff}{}
\renewcommand*{\wrappingon}{}
\renewcommand*{\wrappingoff}{}
\renewcommand*{\verbatimindent}{}
\renewcommand*{\verbatimbreakchar}[1]{}

\DefineVerbatimEnvironment{fboxverbatim}{Verbatim}{frame=single}
```

`boxedverbatim` is already defined by moreverb. `boxedverbatim*` does not appear to work at all, even in a minimal print memoir document.

```
\renewcommand*{\bvbox}{}
\renewcommand*{\bvtopandtail}{}
\renewcommand*{\bvsides}{}
\renewcommand*{\nobvbox}{}
% \newlength\bvboxsep
\renewcommand*{\bvtoprulehook}{}
\renewcommand*{\bvtopmidhook}{}
\renewcommand*{\bvendrulehook}{}
\renewcommand*{\bvleftsidehook}{}
\renewcommand*{\bvrightsidehook}{}
\renewcommand*{\bvperpagetrue}{}
\renewcommand*{\bvperpagefalse}{}
\renewcommand{\bvtopofpage}[1]{}
\renewcommand{\bvendofpage}[1]{}
\renewcommand*{\linenumberfrequency}[1]{}
\renewcommand*{\resetbvlinenumber}{}
\renewcommand*{\setbvlinenums}[2]{}
\renewcommand*{\linenumberfont}[1]{}
\renewcommand*{\bvnumbersinside}{}
\renewcommand*{\bvnumbersoutside}{}
```

§ 534.16 Cross referencing

```
\renewcommand*{\fref}[1]{\cref{#1}}
\renewcommand*{\tref}[1]{\cref{#1}}
\renewcommand*{\pref}[1]{\cpageref{#1}}
\renewcommand*{\Aref}[1]{\cref{#1}}
\renewcommand*{\Bref}[1]{\cref{#1}}
\renewcommand*{\Pref}[1]{\cref{#1}}
\renewcommand*{\Sref}[1]{\cref{#1}}
\renewcommand*{\figurerefname}{Figure}
\renewcommand*{\tablerefname}{Table}
\renewcommand*{\pagerefname}{page}
\renewcommand*{\bookrefname}{Book~}
\renewcommand*{\partrefname}{Part~}
\renewcommand*{\chapterrefname}{Chapter~}
\renewcommand*{\sectionrefname}{\S}
\renewcommand*{\appendixrefname}{Appendix~}
\LetLtxMacro\titleref\nameref
\renewcommand*{\headnameref}{}
\renewcommand*{\tocnameref}{}

\providecounter{LWR@currenttitle}

\renewcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}

\renewcommand*{\theTitleReference}[2]{}
\renewcommand*{\namerefon}{}
\renewcommand*{\namerefoff}{}
```

§ 534.17 Back matter

Redefined to write the LWR@autoindex counter instead of page. Note that memoir has two versions, depending on the use of hyperref.

```
\AtBeginDocument{

\def\@@wrindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
    {\string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}}%
    \endgroup
    \@esphack}%
```

\specialindex behaves like a regular \index, pointing to where \specialindex is used. If \specialindex is used inside a figure or table after the \caption, then the hyperlink will be given the name of that particular figure or table.

```
\def\@@wrspindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
    {%
%         \string\@@wrindexm@m{\@idxfile}{#1}{\@nameuse{the\@sptheidx}}%
        \string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}%
    }%
    \endgroup
    \@esphack}%

}% \AtBeginDocument
```

Patched to use _html filename and \BaseJobname:

```
\catcode`\_=12%
\renewcommand*{\makeindex}[1][\BaseJobname]{%
  \if@filesw
    \def\gindex{\@bsphack%
      \@ifnextchar [{\@index}{\@index[\BaseJobname]}}
    \def\specialindex{\@bsphack\@spindex}%
    \makememindexhook
    \expandafter\newwrite\csname #1@idxfile\endcsname
   \expandafter\immediate\openout \csname #1@idxfile\endcsname #1_html.idx\relax
    \typeout{Writing index file #1_html.idx }%
  \fi}
\catcode`\_=8%
```

Patched to use _html filename and \BaseJobname. This will later be patched by the lwarp core.

```
\catcode`\_=12%
\renewcommand{\printindex}[1][\BaseJobname]{\@input@{#1_html.ind}}
\catcode`\_=8%
```

```
\DeclareDocumentCommand{\newblock}{}{}
%
\renewcommand*{\showindexmarks}{}
\renewcommand*{\hideindexmarks}{}

\renewcommand*{\xindyindex}{}
```

§ 534.18 Miscellaneous

```
\renewcommand*{\changemarks}{}
\renewcommand*{\nochangemarks}{}
\renewcommand*{\added}[1]{}
\renewcommand*{\deleted}[1]{}
\renewcommand*{\changed}[1]{}

\renewcommand*{\showtrimsoff}{}
\renewcommand*{\showtrimson}{}
\renewcommand*{\trimXmarks}{}
\renewcommand*{\trimLmarks}{}
\renewcommand*{\trimFrame}{}
\renewcommand*{\trimNone}{}
\renewcommand*\trimmarkscolor{}
\renewcommand*{\trimmarks}{}
\renewcommand*{\tmarktl}{}
\renewcommand*{\tmarktr}{}
\renewcommand*{\tmarkbr}{}
\renewcommand*{\tmarkbl}{}
\renewcommand*{\tmarktm}{}
\renewcommand*{\tmarkmr}{}
\renewcommand*{\tmarkbm}{}
\renewcommand*{\tmarkml}{}
\renewcommand*{\trimmark}{}
\renewcommand*{\quarkmarks}{}
\renewcommand*{\registrationColour}[1]{}

\renewcommand*{\leavespergathering}[1]{}

\renewcommand*{\noprelistbreak}{}

\renewcommand*{\cleartorecto}{}
\renewcommand*{\cleartoverso}{}

\renewenvironment{vplace}[1][]{}{}
```

§ 534.19 ccaption emulation

```
\renewcommand*{\captiondelim}[1]{\renewcommand*{\CaptionSeparator}{#1}}
\renewcommand*{\captionnamefont}[1]{}
\renewcommand*{\captiontitlefont}[1]{}
\renewcommand*{\flushleftright}{}
\renewcommand*{\centerlastline}{}
\renewcommand*{\captionstyle}[2][]{}
\DeclareDocumentCommand{\captionwidth}{m}{}
\renewcommand*{\changecaptionwidth}{}
\renewcommand*{\normalcaptionwidth}{}
```

```
\renewcommand*{\hangcaption}{}
\renewcommand*{\indentcaption}[1]{}
\renewcommand*{\normalcaption}{}
\renewcommand{\precaption}[1]{}
\renewcommand{\postcaption}[1]{}
\renewcommand{\midbicaption}[1]{}
\renewcommand{\contcaption}[1]{%
% \ContinuedFloat%
% \caption{#1}%
\begin{LWR@figcaption}% later becomes \caption*
\LWR@isolate{\@nameuse{\@captype name}}~%
\thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#1}%
\end{LWR@figcaption}
}

\newlength{\abovelegendskip}
\setlength{\abovelegendskip}{0.5\baselineskip}
\newlength{\belowlegendskip}
\setlength{\belowlegendskip}{\abovelegendskip}
```

The extra \\ here forces a <br> in HTML when \legend is used in a \marginpar.

```
\renewcommand{\legend}[1]{\begin{center}#1\\\end{center}}

\renewcommand{\namedlegend}[2][]{
\begin{center}
\@nameuse{fleg\@captype}\CaptionSeparator#2\\
\end{center}
\@nameuse{flegtoc\@captype}{#1}
}

\renewcommand{\newfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
\renewcommand{\renewfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
\renewcommand{\providefixedcaption}[3][\caption]{%
  \providecommand{#2}{\def\@captype{#3}#1}}

\renewcommand{\bitwonumcaption}[6][]{%
\ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
\addtocounter{\@captype}{-1}%
\begingroup%
\csdef{\@captype name}{#4}%
\ifblank{#5}{\caption{#6}}{\caption[#5]{#6}}%
\endgroup%
\ifblank{#1}{}{\label{#1}}%
}

\LetLtxMacro\bionenumcaption\bitwonumcaption% todo

\renewcommand{\bicaption}[5][]{%
\ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
\begin{LWR@figcaption}% later becomes \caption*
\LWR@isolate{#4} \thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#5}%
\end{LWR@figcaption}
\ifblank{#1}{}{\label{#1}}%
```

```
}

\renewcommand{\bicontcaption}[3]{%
\contcaption{#1}%
\begingroup%
\csdef{\@captype name}{#2}%
\contcaption{#3}%
\endgroup%
}

% only in ccaption, not in memoir:
% \LetLtxMacro\longbitwonumcaption\bitwonumcaption%
% \LetLtxMacro\longbionenumcaption\bitwonumcaption%
% \LetLtxMacro\longbicaption\bicaption%

\RenewDocumentCommand{\subtop}{O{} O{} m}{%
\subfloat[#1][#2]{#3}%
}

\RenewDocumentCommand{\subbottom}{O{} O{} m}{%
\subfloat[#1][#2]{#3}%
}

\renewcommand{\contsubtop}{%
\ContinuedFloat\addtocounter{\@captype}{1}%
\subtop}

\renewcommand{\contsubbottom}{%
\ContinuedFloat\addtocounter{\@captype}{1}%
\subbottom}

\renewcommand{\subconcluded}{}

\let\subfigure\subbottom
\let\subtable\subtop

\let\contsubtable\contsubtop
\let\contsubfigure\contsubbottom

\newcommand{\newfloatentry}[4][\@empty]{TODO: newfloatentry}
\newcommand{\newfloatlist}[5][\@empty]{TODO: newfloatlist}
\newcommand{\newfloatenv}[4][\@empty]{TODO: newfloatenv}
\DeclareRobustCommand{\newfloatpagesoff}[1]{}
\DeclareRobustCommand{\newfloatpageson}[1]{}
\newcommand{\setnewfloatindents}[3]{}
```

§ 534.20 Final patchwork

```
\newlistof{tableofcontents}{toc}{\contentsname}
\newlistof{listoffigures}{lof}{\listfigurename}
\newlistof{listoftables}{lot}{\listtablename}
```

File 437 **lwarp-common-multimedia.sty**

§ 535 Package

common-multimedia

Pkg lwarp-common-multimedia

Common code for multimedia, movie15, and media9.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

for HTML output:

```
\ProvidesPackage{lwarp-common-multimedia}[2019/04/22]

\RequirePackage{xkeyval}

\define@key{LWR@multimedia}{width}{\setlength{\LWR@multimedia@width}{#1}}
\define@key{LWR@multimedia}{height}{\setlength{\LWR@multimedia@height}{#1}}
\define@key{LWR@multimedia}{totalheight}{\setlength{\LWR@multimedia@height}{#1}}
```

```
\newlength{\LWR@multimedia@width}
\newlength{\LWR@multimedia@height}
\newlength{\LWR@multimedia@maxdimension}
```

\LWR@multimedia@printsize

Proportional to \linewidth and the viewport's smaller dimension. This scales each object such that it will always fit on the screen, even if a tall or wide object inside a tall or wide viewport.

```
\newcommand*{\LWR@multimedia@printsize}{%
    \setlength{\LWR@multimedia@maxdimension}{%
        \maxof%
            {\linewidth}%
            {\maxof{\LWR@multimedia@width}{\LWR@multimedia@height}}%
    }%
    \setlength{\LWR@multimedia@maxdimension}{1.1\LWR@multimedia@maxdimension}%
    \ifdimgreater{\LWR@multimedia@width}{0pt}{%
        width:%
            \LWR@printpercentlength%
                {\LWR@multimedia@width}%
                {\LWR@multimedia@maxdimension}vmin ; % space
    }{}%
    \ifdimgreater{\LWR@multimedia@height}{0pt}{%
        height:%
            \LWR@printpercentlength%
                {\LWR@multimedia@height}%
                {\LWR@multimedia@maxdimension}vmin ; % space
    }{}%
}
```

\LWR@multimedia@fileAV {⟨*poster text*⟩} {⟨*filename*⟩} {⟨*audio/video*⟩} {⟨*mimetype*⟩}

Creates a video or audio from a file.

```
\newcommand*{\LWR@multimedia@fileAV}[4]{%
\filename@parse{#2}%
\IfFileExists{#2}{%
```

The container is sized as desired.

```
    \ifstrequal{#3}{audio}{%
        \begin{BlockClass}{AVviewport}
    }{%
        \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{AVviewport}
    }
```

Paragraph tags are unnecessary for the A / V tags.

```
    \LWR@stoppars
```

The A / V element is 100% of the container.

```
    \LWR@htmltag{%
        #3\ % space
        \ifstrequal{#3}{audio}{}{%
            width=\textquotedbl{}100\%\textquotedbl\ % space
            height=\textquotedbl{}100\%\textquotedbl\ % space
        }%
        controls%
```

```
    }\LWR@orignewline
```

The file source and type:

```
    \LWR@htmltag{%
        source % space
        src=\textquotedbl%
        \@filef@und\unskip\textquotedbl\ % space
        type=\textquotedbl{}#4\textquotedbl}
```

The poster text inside paragraph tags, along with a reference to the file.

```
    \LWR@startpars
    \href{\@filef@und}{#1}
    \LWR@stoppars
```

Finish.

```
    \LWR@htmltag{/#3}\LWR@orignewline
    \end{BlockClass}
}{%
    \PackageError{lwarp-common-multimedia}
    {File '#2' not found}
    {Perhaps an incorrect path?}
}%
}
```

`\LWR@multimedia@httpAV` {⟨*poster text*⟩} {⟨*filename*⟩} {⟨*audio/video*⟩} {⟨*mimetype*⟩}

Creates a video or audio from a URL link.

```
\newcommand*{\LWR@multimedia@httpAV}[4]{%
```

The container is sized as desired.

```
    \ifstrequal{#3}{audio}{%
        \begin{BlockClass}{AVviewport}
    }{%
        \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{AVviewport}
    }
```

Paragraph tags are unnecessary for the A / V tags.

```
    \LWR@stoppars
```

The A / V element is 100% of the container.

```
    \LWR@htmltag{%
        #3\ % space
        \ifstrequal{#3}{audio}{}{%
            width=\textquotedbl{}100\%\textquotedbl\ % space
            height=\textquotedbl{}100\%\textquotedbl\ controls%
        }%
    }\LWR@orignewline
```

The file source and type:

```
    \LWR@htmltag{%
        source % space
        src=\textquotedbl#2\textquotedbl\ % space
        type=\textquotedbl#4\textquotedbl}
```

The poster text inside paragraph tags, along with a reference to the URL.

```
    \LWR@startpars
    \href{#2}{#1}
    \LWR@stoppars
```

Finish.

```
    \LWR@htmltag{/#3}\LWR@orignewline
    \end{BlockClass}
}
```

\LWR@multimedia@AV {⟨*poster text*⟩} {⟨*filename*⟩} {⟨*audio/video*⟩} {⟨*mimetype*⟩}

Creates an audio or video from a file or a URL.

```
\newcommand*{\LWR@multimedia@AV}[4]{%
    \IfBeginWith{#2}{http}%
        {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
        {%
            \IfBeginWith{#2}{HTTP}%
                {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
                {\LWR@multimedia@fileAV{#1}{#2}{#3}{#4}}%
        }%
}
```

\LWR@multimedia@embed {⟨*poster text*⟩} {⟨*URL or filename*⟩} {⟨*mime type*⟩}

Embeds multimedia of an arbitrary type. The poster text is not used, as it would appear along with the video if the <embed> element is supported.

```
\newcommand*{\LWR@multimedia@embed}[3]{%
    \begin{BlockClass}[width:100\%]{AVviewport}%
    \LWR@stoppars
        \LWR@htmltag{%
            embed % space
            \ifblank{#3}{}{type=\textquotedbl#3\textquotedbl\ }%
        style=\textquotedbl\LWR@multimedia@printsize\ margin:auto\textquotedbl\ % space
            src=\textquotedbl#2\textquotedbl\ % space
        }%
    \LWR@startpars
    \end{BlockClass}
}
```

\LWR@multimedia@percenterror

Error message if the comment character is used among the arguments of \LWR@multimediab.

```
\newcommand*{\LWR@multimedia@percenterror}{%
    \PackageError{lwarp-media9}
    {%
        Do not use a percent comment
        between\MessageBreak
        \protect\includemedia\space arguments%
    }
    {Percent is changed to a regular character to allow its use inside a URL.}
}
```

\LWR@multimediab [⟨*options*⟩] {⟨*poster text*⟩} {⟨*filename*⟩}

Creates multimedia. Examines the file extension to determine the type. If not a supported type, creates an embedded object if it has a URL. If neither, create a link to the unsupported object.

```
\newcommand*{\LWR@multimediab}[3][]{%
```

Error if the percent character appears among the arguments. This could happen since the comment character has been temporarily disabled, for use in a URL.

```
    \if#1\@percentchar\LWR@multimedia@percenterror\fi%
    \if#2\@percentchar\LWR@multimedia@percenterror\fi%
    \if#3\@percentchar\LWR@multimedia@percenterror\fi%
```

Paragraph handling:

```
    \LWR@stoppars%
```

Record the desired size.

```
    \setlength{\LWR@multimedia@width}{0pt}%
    \setlength{\LWR@multimedia@height}{0pt}%
    \setkeys*{LWR@multimedia}{#1}%
```

If a known A / V type, create an HTML5 <video> or <audio>.

```
    \IfEndWith{#3}{.mp4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
    \IfEndWith{#3}{.MP4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
    \IfEndWith{#3}{.mp3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
    \IfEndWith{#3}{.MP3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
```

If an arbitrary URL, embed it.

```
    \IfBeginWith{#3}{http}{\LWR@multimedia@embed{#2}{#3}{}}{%
    \IfBeginWith{#3}{HTTP}{\LWR@multimedia@embed{#2}{#3}{}}{%
    \IfBeginWith{#3}{ftp}{\LWR@multimedia@embed{#2}{#3}{}}{%
    \IfBeginWith{#3}{FTP}{\LWR@multimedia@embed{#2}{#3}{}}{%
```

If unknown, create a link to it.

```
        \href{#3}{#2}% unknown format
    }}}}}}}}%
```

Paragraph handling:

```
    \LWR@startpars%
    \endgroup%
}
```

Catcodes which may apper in a URL.

```
\newrobustcmd*{\LWR@multimedia}{%
    \begingroup%
    \catcode`\#=12%
    \catcode`\%=12%
    \catcode`\&=12%
    \catcode`\~=12%
    \catcode`\_=12%
    \LWR@multimediab%
}
```

Change History

§ 536 ## Chg Hist

For the most recent changes, see page 1074.

v0.10
General: 2016/03/08 Initial version . . 1
v0.11
General: 2016/03/11 1
Added section: Operating-System portability. 208
Added section: Selecting the operating system. 113
Test Suite: MS-WINDOWS in README.txt 1
Test Suite: limages and index in README.txt 1
v0.12
\LWR@newhtmlfile: Bugfix: TOC with numbered files. 355
General: 2016/03/14 1
Global: Uses \p@(type) in float captions. 1
Test Suite: Sub-figures 1
v0.13
\CaptionSeparator: Fix for newer babel package. 476
\LWR@LwarpStart: \up and \fup . . . 374
General: 2016/03/24 1
Fix dollar-redefined bug for newer package. 947
Removed package: subfig 1
Test Suite: Ordinals, Subcaption . . . 1
v0.14
\LWR@htmlsectionfilename: Fix: Links to home page. 317
General: 2016/03/31 1
floatrow: Added. 716
Docs: Commands for a successful HTML conversion. 116
Docs: Commands into a warpprint environment. 114
Docs: Newclude limitations. . . . 160
Docs: Table: Cross-referencing data structures. 461
Docs: Table: Float data structures. 472
Docs: Trademarks section. 186
Docs: Troubleshooting cross-references. 181
Test Suite: Assigned cleveref name for Test Float. 1
Test Suite: Floatrow 1
v0.15
General: 2016/04/06 1
Added. 721
Ampersand (&): Fixed handling when passed as an argument. . . 407
Docs: Added warning icons for items needing special attention. 189
Docs: Clarify print/HTML output. 113
Docs: Moved the supported features table to the introduction. 64
Files: lwarp_formal.css added. 1
Fix: steps counter 720
Fixed & handling. 719
Test Suite: test_suite_formal.css file added. 1
v0.16
General: 2016/04/11 1
\titlingpage: Improved print-output spacing. 381
xfrac: Adjusted for the use of any font: 1003
Added XeLaTeX, LuaLaTeX support. 190
Docs: Font and UTF-8 support. . . 97
Docs: Moved location of \usepackage{lwarp}. 100
Docs: Text not converting. 181
Lwarp no longer selects fonts. 97, 217
Removed package: suffix 1
Test Suite: Improved titlingpage. 381
Test Suite: Lwarp no longer selects fonts. 1
Test Suite: Supports XeLaTeX, LuaLaTeX. 1
v0.17
\LWR@htmlsectionfilename: Fix: Links when entire doc is one HTML page. 317
General: 2016/04/14 1
mdframed: Added. 807

Test Suite: Fix: Print-version front-matter page numbers. 1
Test Suite: Mdframed 1
v0.18
\LWR@includegraphicsb: Add: svgz file extension. 743
em, ex, %, px dimensions preserved. 743
Fix: \linewidth, \textwidth, \textheight inside a minipage. 743
Improved HTML output linebreaks. 743
\LWR@myshorttoc: Reorganize \HomeHTMLFilename logic. 479
\LWR@newhtmlfile: sideTOC after title, improving responsive design. . . 354
\LWR@requesttoc: Reorganize \HomeHTMLFilename logic. 375
\LWR@subhyperref: Improved HTML output linebreaks. 469
\LWR@subhyperrefclass: Improved HTML output linebreaks. 469
\LWR@subinlineimage: Suppress extra space. 471
\hspace: \hspace supported. 571
General: 2016/05/19 1
File: lwarp.css: Improved TOC outline display. 1
Files: lwarp.css and lwarp_formal.css: Improved responsive design. 1
Microtype disabled during HTML generation 217
PDF Unicode input characters. . 204
Test Suite: Verse package 1
lateximage: pdfcrop: --hires added. 526
Reorganize \HomeHTMLFilename logic. 526
Suppress extra space. 526
verse: Supports verse, memoir packages. 982
minipage: Fix: \linewidth, \textwidth, \textheight inside a minipage. 546
v0.19
\HTMLFilename: Docs: Escape filename underscores. 316
\HomeHTMLFilename: Docs: Escape filename underscores. 316
\LWR@LwarpStart: Enabled \\ equal to \newline. 372
\LWR@doequation: MathJax support. 512
\LWR@doubledollar: MathJax support. 506
\LWR@filestart: lwarp_mathjax.txt loaded. 370
\LWR@minipagestartpars: Suppresses paragraph tags between minipages. 569
\LWR@subsingledollar: MathJax support. 500
\LateximageFontSizeName: Add: User-adjustable math/lateximage font size. 521
\hspace: Fix: \hspace length computations. 571
\minipagefullwidth: Added: No width tag for the next minipage in HTML. 546
\warpHTMLonly: Added. 216
\warpprintonly: Replaces \rowprintedonly. 216
\xfracHTMLfontsize: Added. . . . 1003
General: 2016/06/08 1
CSS for table note item. 944
MathJax support added. 509, 516, 517
multirow: Added optional args. . . 832
Adapts to tikz version. 947
Avoids MathJax. 499
cleveref: Loaded \AtEndPreamble. 541
Docs: Math options. 100
Docs: Table: Cross-referencing data structures, updated. 461
File: lwarp.css: tnoteitemheader added. 1
File: lwarp_mathjax.txt added. . . 1
Introduction: MathJax support mentioned. 61
Options: mathsvg and mathjax . 211
Supports colored \rule. 994
titleps: null \pagestyle and \thispagestyle for HTML. . . . 948
v0.20
\BlockClassSingle: Renamed from "LWR@htmldivclassline". 329
\HTMLDescription: Added \NewHTMLdescription. (Renamed in v0.30.) 340
\HTMLFilename: No longer escape underscores. 316
\HomeHTMLFilename: No longer escape underscores. 316
\InlineClass: Renamed from "inlineclass". 330
\LWR@LwarpStart: Fix: math cross references. 374
\LWR@closeparagraph: \unskip extra spaces. 334
No break tags in the start/end of a tabular. 334
\LWR@endofline: Fix: \\ 569

\LWR@filestart: Adds meta description. 370
\LWR@htmldivclass: Added optional style. 328
\LWR@htmlelementclass: Added optional style. 328
\LWR@htmlsectionfilename: HTMLFilename: removed additional trailing '-', and may be empty. 317
Sections called "Index" or "index" have an underscore prepended to their filenames if no prefix. 317
\LWR@includegraphicsb: Fix: \linewidth in a floatrow. 743
Fix: Expands filename. 743
\LWR@longtabledatacaptiontag: Fix: Pars in captions. 444
\LWR@section: Combined higher-level sections together into files. 361
\LWR@setOSWindows: Auto-detects operating system. 210
\LWR@subhtmlelementclass: Factored code. 327
\SetHTMLFileNumber: Add: Control file numbers. 316
\cpagerefFor: User-redefinable word for page references. 542
\dotfill: Inserts an ellipsis. 569
\hfill: Inserts a \qquad. 568
\hrulefill: Inserts a short rule. . . 569
\hspace: Add: Supports HTML thin breakable space. 571
\hyperindexref: Print mode provided in case hyperref not used. 490
\pageref: Added. 468
\tracinglwarp: Added. 230
General: 2017/02/09 1
afterpage: Added. 592
alltt: Added. 597
bookmark: Added. 627
caption and subcaption supported. . 1
cleveref and referencing patches: Applied \AfterEndPreamble. . . . 541
draftwatermark: Added. 681
eso-pic: Added. 694
everypage: Added. 695
extramarks: Added. 695
fancyhdr: Added. 701
float: Improved float caption type handling. 713
hyperref: Additional user macros. 756
keyfloat: Added. 773
letterspace: User-interface emulated. 782
listings: Added. 786
ltcaption: Added. 795
lwarp-newproject: Added. 242
microtype: User-interface emulated. 822
needspace: Added. 841
nowidow: Added. 853
placeins: Added. 878
ragged2e: Added. 886
setspace: Improved support. . . . 905
textpos: Added. 939
titleps: Added. 948
titlesec: Added. 951
titletoc: Added. 953
titling: Improved compatibility. . 955
tocloft: Added. 963
wallpaper: Added. 987
wrapfig: Added. 989
xetexko-vertical: Added. 1002
Added @, <, > columns. 401
Added single-expansion data arrays. 313
Code factored into independent lwarp_html files. 582
Docs: Examples for generating HTML file names. 111
Docs: Improved index. 1
Enhanced titling support. 380
File: lwarp.css: Minor fixes for validation. 1
File: lwarpmk used to compile print, HTML, indexes, and latexmages. 1
Fix: \linewidth in a floatrow. . . 719
Moved sidebar and example code to test suite. 1
Page geometry set to 6in wide with large margins. 218
Parallel versions of aux files for print/HTML. 1
Removed reliance on make, grep, gawk. 1
Tabular: \unskip extra spaces. . . 401
Test Suite: HTML meta descriptions. 1
verbatim: Added. 391
BlockClass: Added optional style. . 329
Renamed from "blockclass". . . . 329
LWR@nestspan: Fix: Minipages inside a span. 324
v0.21
\LWR@LwarpStart: Changed latexmages to a .txt file. . . . 372
\LWR@filestart: Skip title if not given. 370

\LWR@newhtmlfile: Skip title if not given. 354
\marginpar: Fixed source listing. . . 347
\marginparBlock: Fixed source listing. 347
General: 2017/02/23 1
fontenc: Added. 726
lwarpmk: Fix: **lwarpmk again** for WINDOWS. 292
lwarpmk: Fix: **lwarpmk limages** for WINDOWS. 292
lwarpmk: Fix: *lwarpmk* uses lateximages text file instead of shell script. 292
Add: Errors for misplaced packages. 190
Docs: Added internet class. 70
Docs: Added TeX2page, GladTeX. . 70
Docs: Installing on WINDOWS. . . . 76
File: lwarp_tutorial.txt added. . 80
v0.22
\LWR@parseDcolumn: Added tabular D column. 416
\LWR@parsebangcolumn: Added tabular ! column. 412
\LWR@parsetablecols: Unknown table column types become l. Added tabular D, !, X columns. . 418
\LWR@printmccoldata: Added tabular D, !, and X columns. 439
General: 2017/03/02 1
abstract: Added. 584
changepage: Added. 639
dcolumn: Added. 677
ftnright: Added. 733
geometry: Nullified commands. . 735
layout: Added. 779
lscape: Added. 794
mcaption: Added. 806
nameref: Added. 839
nextpage: Added. 841
parskip: Added. 869
showkeys: Added. 907
sidecap: Added. 907
tabularx: Added. 932
varioref: Supported. 125
verse: Added. 982
v0.23
\LWR@parsetablecols: Fix for vert bar column type. 418
\LWR@printmccoldata: Fix for vert bar column type. 439
General: 2017/03/02 1
v0.24
\LWR@htmlfileref: Fix: Index links while \tracinglwarp. 464
\hspace: Add: \hspace \fill converts to 2em 571
\hypertocfloat: List of floats responds to lofdepth, lotdepth. 486
General: 2017/03/15 1
floatrow: Support for subfig. . . . 716
subfig: Added. 924
tikz: For tikz v3.0.0 or later, auto-loads tikz babel library if necessary. 947
Docs: Filename underscore. 105, 119
Fix for inline images. 947
No longer preloads subcaption; conflicted with subfig. 221
picture: Fix for inline images. . . . 544
v0.25
\LWR@loadnever: Added the ability to prevent conflicting packages. . . 192
\addcontentsline: Handles theorems. 478
General: 2016/03/22 1
amsthm: Added. 600
ellipsis: Added. 684
emptypage: Added. 685
framed: Added. 730
lips: Added. 786
mdframed: Help avoid hyphenation. 808
ntheorem: Added. 854
showidx: Added. 906
theorem: Added. 940
Basic LaTeX theorems: improved css. 392
Docs: Adds credits for patched code. 1
Docs: Testing lwarp. 177
Fix: Allows XeLaTeX and LuaLaTeX to preload graphics and graphicx. 194
v0.26
General: 2017/03/31 1
lwarp.css: Improved responsive marginpar and marginblock. . . 249
cutwin: Added. 676
endnotes: Added. 687
floatflt: Added. 715
footmisc: Added. 726
footnotehyper: Added. 729
footnote: Added. 728
marginfix: Added. 804
marginnote: Added. 805
mparhack: Added. 827
pagenote: Supported as-is. 867

sidenotes: Added. 908
Docs: Improved MiKTEX install instructions. 75, 77
Dollar span avoided in a lateximage. 499
Footnotes now are LATEX boxes instead of pagenotes. 341
lateximage: Labels track page numbers of lateximages. 526
Print mode now uses a minipage of \linewidth. 526
picture: Fix for \makebox in picture. 544
v0.27
\LWR@@footnotetext: Fix for table footnote par tags. 343
General: 2017/04/04 1
lettrine: Added. 782
microtype: Fix with XeLATEX, LuaLATEX. 822
soul: Added. 915
ulem: Added. 977
Docs: Installing utilities for MACOS. 78
Docs: Limitations of saveboxes. . 119
Page geometry modified to reduce line overflow. 218
v0.28
\@wrindex: Improved indexing. . . . 489
\HTMLAuthor: Added \HTMLauthor. (Renamed in v0.30.) 340
\LWR@LwarpEnd: If FormatEPUB or FormatWP, no bottom nav. 375
\LWR@LwarpStart: FormatWordProcessor forces single-file output. 372
\LWR@filestart: Adds HTML meta author. 370
\LWR@forcenewpage: Forces new PDF page before major environments. 321
\LWR@htmlcomment: Breaks ligatures in HTML comments. 327
\LWR@includegraphicsb: Adapts to graphics syntax. 743
\LWR@newhtmlfile: If FormatEPUB or FormatWP: skips headers, footers, nav. 354
\LWR@parsetablecols: Added L, C, R, J column types. 418
\LWR@startref: Removed space. . . 466
\chapter: If EPUB, prints footnotes before each section. 368
\hyperindexref: Improved indexing. 490
\textup: Fixed span class. 557
General: 2017/04/14 1
glossaries: Added. 737
graphics: Added. 738
tabularx: Fix for optional pos. . . . 932
tabulary: Added. 932
lwarpmk: Add: **printglossary** and **htmlglossary** commands. . . . 292
Added boolean FormatEPUB. . . . 236
Added boolean FormatWP. 236
Added boolean HTMLDebugComments. 231
Added boolean HTMLMarkFloats, changed to WPMarkFloats as of v0.42. 236
Docs: Modfying lwarpmk and index processing. 177
File: lwarp_mathjax.txt: Updated CDN repository. 290
Forced oneside to maintain large right margin. 218
v0.29
\LWR@includegraphicsb: Fix: Error when no optional arguments. . . 743
General: 2017/04/15 1
*.lwarpmkconf: Add: language option for config files. 249
lwarpmk.conf: Add: language option for config files. 249
lwarpmk: Add: language option for config files. 292
Add: lwarpmklang option for lwarp. 212
Docs: Using a glossary 91
v0.30
\CSSFilename: Renamed from \NewCSS. 339
\HTMLAuthor: Renamed from \HTMLauthor. 340
\HTMLDescription: Renamed from \NewHTMLdescription. 340
\HTMLFirstPageTop: Renamed from \SetFirstPageTop. 338
\HTMLLanguage: Renamed from \MetaLanguage. 369
\HTMLPageBottom: Renamed from \SetPageBottom. 338
\HTMLPageTop: Renamed from \SetPageTop. 338
General: 2017/04/29 1
lwarp-newproject removed, and combined with lwarp. 242
lwarpmk: Add: xdyfile configuration option. 292
lwarpmk: Fix: *xindy* and *texindy* adjusted for *pdflatex*, *xelatex* and *lualatex*. 292

lwarpmk: Fix: *xindy* now used for print index generation with *latexmk*. 292
lwarpmk: `language` now used for both index and glossary generation. 292
File: `lwarp_html.xdy` renamed to `lwarp.xdy`. 288
Fix: `*.css` files only written in print mode. 249
Fix: `lwarp.xdy` only written in print mode. 288
Fix: `lwarp_mathjax.txt`: Only written in print mode. 290
Option `lwarpmklang` changed to `IndexLanguage`. 212
Option `OSWindows` replaces macro `\warpOSwindows`. 212
Option `xdyFilename` added. 212
Option *latexmk* replaces macro `\UseLatexmk`. 214
Options `HomeHTMLFilename` and `HTMLFilename` replace macros `\HomeHTMLFilename` and `\HTMLFilename`. 213
v0.31
General: 2017/05/15 1
keyfloat: Improved compatibility. 773
v0.32
`\RequirePackage`: Fix: Ignores blanks in package list. 225
General: 2016/06/09 1
glossaries: Prevent error with `\glo@name` not defined. 491
lwarpmk: Fix: **`io.lines()`** changed to **`file:lines()`** due to *luatex* changes. 292
v0.33
`\HTMLAuthor`: Fix: Provides empty default author if none given. . . . 340
`\LWR@loadbefore`: Fix: No `\PackageError` if already loaded. 192
`\LWR@parseatcolumn`: Fix: Column alignment with leftmost `@`. 411
`\LWR@tabledatasinglecolumntag`: Fix: Macros in tabular could cause extra data cell. 426
`\LWR@vspace`: Add: `\vspace` nullified. 572
`\StartDefiningTabulars`: Add: Avoids error: `Misplaced alignment tab character &`. . . 313
General: 2017/07/10 1
amsmath: Removed `fleqn` option. 597
fancyhdr: Fix: Optional args for `\lhead`, etc. 701
Add: Tabular at and bang columns now have their own HTML columns. 401
cleveref: Fix: Loaded `\AtEndPreamble`. 541
Fix: Incorrectly-inline math environments. 517
New handling of `&` to localize catcode changes. 401
v0.34
`\@fnsymbol`: Text symbols instead of math. 383
`\InlineClass`: Moved optional argument in front of mandatory. 330
`\LWR@htmldivclass`: Moved optional argument in front of mandatory. 328
`\LWR@htmlelementclass`: Moved optional argument in front of mandatory. 328
`\LWR@htmlelementclassline`: Moved optional argument in front of mandatory. 328
`\LWR@htmlspanclass`: Moved optional argument in front of mandatory. 326
`\LWR@nullfonts`: Improved font control. 560
`\LWR@restoreorigformatting`: booktabs: Works inside `lateximage`. 492
Improved font control. 492
`\LWR@subhtmlelementclass`: Moved optional argument in front of mandatory. 327
`\LWR@tabledatacolumntag`: booktabs: Works inside `lateximage`. 451
`\fboxBlock`: Added. 553
`\makebox`: Fix: Handles paren arg. . 551
General: 2017/08/08 1
babel-french: Adds fixed-width HTML spaces to punctuation. . . 323
balance: Added. 617
booktabs: Works inside `lateximage`. 454, 627
boxedminipage2e: Added. 629
crop: Added. 673
enumerate: Added. 687
enumitem: Added, no longer required. 687
everyshi: Added. 695
fancybox: Added. 697
fancyvrb: Added, no longer required. 703
figcaps: Added. 709
filecontents: Required. Patched for morewrites. 221

floatpag: Added. 716
flushend: Added. 721
fullpage: Added. 733
hyperxmp: Added. 761
idxlayout: Added. 762
marginfit: Added. 804
mdframed: Improved mdtheorem patch. 814
moreverb: Added. 825
paralist: Added. 868
pdflscape: Added. 871
pdfsync: Added. 874
prelim2e: Added. 880
rotfloat: Added. 893
savetrees: Added. 894
shadow: Added. 906
syntonly: Added. 931
titleps: No longer required. 948
titleref: Prevented. 951
xmpincl: Added. 1006
Added. 998
Docs: Horizontal space limitations. 1
Docs: Misplaced alignment character. 181
File: lwarp_mathjax.txt: Version change. 290
File: README.txt: updated. 1
Fix: Added the eqnarray environments. 517
Improved font control. 555
Lists refactored to remove enumitem requirement. 393
Verbatim refactored to remove fancyvrb requirement. 389
tabular: booktabs: Works inside lateximage. 456
lateximage: Fix: lateximage with minipage, \parbox, \makebox, \fbox, \framebox, \raisebox, \scalebox, \reflectbox. 526
BlockClass: Moved optional argument in front of mandatory. 329
fminipage: Added. 553
LWR@nestspan: Fix: Minipages, BlocksClass, and lists inside a span. 324
v0.35
General: 2017/08/08 1
Fix: \textbf and related. 555
v0.36
\LWR@@footnotetext: Extra HTML source space after paragraphs. . 343
Force HTML superscripts. 343
\LWR@HTMLsanitize: Fix for babel-french. 522
\LWR@HTMLsanitizeexpand: Fix for babel-french. 523
\LWR@closeparagraph: Extra HTML source space after paragraphs. . 334
\LWR@currenttextcolor: Fix for \rule when xcolor not loaded. . 567
\LWR@nullfonts: Fix: Filenames while using MathJax. 560
\LWR@restoreorigformatting: siunitx: Improved super/subscripts in a lateximage. 492
\LWR@section: Improved spacing. . 361
\LWR@stoppars: Extra HTML source space after paragraphs. 336
\fbox: Fix: Uses \fboxrule and \fboxsep. 552
\framebox: Fix: Handles width and horiz position. 551
\makebox: Fix: Handles width and horiz position. 551
General: 2017/08/17 1
babel-french: Adjustements for French variants, load order, footnotes, ellipses. 323
footnote: Extra HTML source space after paragraphs. 728
siunitx: Fix for babel-french. . . . 534
siunitx: Improved symbol support. 910
transparent: Added. 973
upref: Added. 981
xcolor: Added \fcolorboxBlock, \colorboxBlock. 990
xcolor: Fix: Background none in print mode. 990
xcolor: Refactored \LWR@colorstyle. 994
xcolor: Uses \fboxrule and \fboxsep. 990
xcolor: \fcolorbox etc. now work inside lateximage. 990
Docs: Reorganized: Special cases and limitations. 116
Source: Improved formatting. . . . 1
tabular: Fix for babel-french. . . . 456
lateximage: Footnotes appear in regular text instead of the lateximage minipage. 526
v0.37
\@include: Maintains independent aux files for HTML. 229
General: 2017/08/19 1
LaTeX accents: Added. 240
babel-french: Adjustment for load order. 323

color: Prevented. 670
comment: Maintains independent cutfiles for print, HTML. 216
siunitx: Improved symbol support. 910
textcomp: Improved support. . . 935
lwarpmk: Removes additional HTML aux files. 292
File handles reorganized. 228
v0.38
\@seccntformat: Added for appendix. 361
\ForceHTMLPage: Added. 358
\ForceHTMLTOC: Added. 359
\LWR@section: \part* starts a new HTML page, for appendix. 361
Modified spacing, uses \numberline. 361
\numberline: Added trailing \quad. 484
\part: Fix with article class. 367
General: 2017/08/27 1
appendix: Added. 605
arabicfront: Added. 607
chappg: Added. 642
color: Forces xcolor as well. . . . 670
fix2col: Added. 711
fncychap: Added. 722
grffile: Added. 751
metalogo: Added. 818
nonumonpart: Added. 852
nopageno: Added. 852
pagenote: Option page disabled. 867
realscripts: Added. 887
relsize: Added. 889
romanbarpagenumber: Added. . . 892
romanbar: Added. 892
scalefnt: Added. 894
siunitx: Removed from lwarp core. 910
textcomp: Removed from lwarp core. 935
tocbibind: Added. 960
xltxtra: Added. 1005
lwarpmk: Added **print1** and **html1** actions. 292
Added \markboth, \sloppy, etc. . 321
Docs: Enhanced *Supported Features* table. 64
Docs: Index, tocbibind. 131
Docs: Starred sections. 127
v0.39
\@maketitle: titling version. 957
Native LaTeX version. 384
Removed minipages. 384, 957
Supports authblk with s of class oneauthor instead of tabular. 384, 957
\AddSubtitlePublished: Added. . . 385
\LWR@domulticolumn: Add: Optional vpos and # rows. 442
\LWR@restoreorigformatting: Appended with \appto instead of calling various macros. 492
\LWR@tabledatacolumntag: Don't start a data cell if see \TabularMacro. 451
\ResumeTabular: Added. 450
\TabularMacro: Added. 450
\multicolumnrow: Added. 448, 833
\printauthor: Removed minipages. 381
Supports authblk with s of class oneauthor instead of tabular. 381
\thanksmarkseries: Removed minipage footnotes. 958
General: 2017/09/05 1
a4wide: Added. 584
a4: Added. 583
a5comb: Added. 584
addlines: Added. 592
anysize: Added. 605
authblk: Added. 614
bigdelim: Added. 624
bigstrut: Added. 625
ebook: Added. 683
fullwidth: Added. 734
midpage: Added. 823
multirow: Add: New optional vpos argument. 832
multirow: Add: Supports left/right border for bigdelim. 832
multirow: Fix: Long text argument. 832
supertabular: Added. 929
textarea: Added. 935
titling: Improved compatibility. . 955
titling: Removed extraneous center environments. 956
typearea: Added. 976
xtabular: Added. 1008
zwpagelayout: Added. 1012
Docs: Reorganized tabular discussion. 152
Titlepage \published and \subtitle removed. \AddSubtitlePublished restores. 385
titlepage: Clear pending footnotes. 379
Removed minipages. 379
titlingpage: Clear pending footnotes. 955
v0.40
\@chapcntformat: Added for tocbibind, anonchap. 361

\LWR@HTMLhline: Added. 455
\LWR@includegraphicsb: Add: Full \graphicspath support. 743
\LWR@nullfonts: Fix: Long arguments for expandable command. 560
\LWR@restoreorigformatting: Improved LaTeX logos inside a lateximage. 492
Improved symbols inside a lateximage. 492
Nullified \InlineClass, etc. inside a lateximage. 492
\LWR@tabledatacolumntag: Fix for bigdelim: \ldelim, \rdelim. . . . 451
\chapter: Added support for quotchap. 368
\multicolumnrow: Fix: Adapts to older multirow and xparse. 448
\simplechapterdelim: Added for tocbibind, anonchap. 361
\underline: Added. 566
General: 2017/09/25 1
adjmulticol: Added. 591
anonchap: Added. 604
bigdelim: Improved documentation. 624
cuted: Added. 676
dblfnote: Added. 677
fnpos: Added. 723
graphics: Moved out of the lwarp core. 738
graphics: Restores \includegraphics and \DeclareGraphicsExtensions in a lateximage. 738
graphicx: Moved out of the lwarp core. 751
grffile: Directly supported. 751
midfloat: Added. 823
multirow: Improved bigdelim borders. 832
pfnote: Added. 877
quotchap: Added. 885
sectsty: Added. 903
stabular: Added. 920
tabls: Added. 932
textcomp: Additional symbols, improved XeLaTeX and LuaLaTeX support. 935
tocbibind: Improved for \simplechapter. 960
xfrac: No longer preloaded. 222
xltxtra: Fix for \showhyphens with XeLaTeX. 1005
v0.41
\LWR@addcmidruletrim: Add: \cmidrule trims. 432
\LWR@clearmidrules: Add: \cmidrule trims. 429
\LWR@closetabledatacell: Add: Mute > for \bottomrule. 405
Fix: At/bang column with \multirow. 406
Fix: Cancel < for \multicolumn. . 406
\LWR@domulticolumn: Add: \cmidrule trims. 442
Added vertical rules. 443
\LWR@nullifyNoAutoSpacing: Fix: \NoAutoSpacing in a tabular with babel-french. 456
\LWR@parsebarcolumn: Added vertical rules. 413
\LWR@printatbang: Add: \cmidrule trims. 425
Add: Mute at and bang columns for \bottomrule. 425
\LWR@printbartag: Added vertical rules. 425
\LWR@subaddcmidruletrim: Added. 431
\LWR@subcmidrule: Add: \cmidrule trims. 429
\LWR@tabledatasinglecolumntag: Add: \cmidrule trims. 426
Add: Mute < for \bottomrule. . . 426
\LWR@tabularfinishrow: Unfinished tabular rows automatically filled. 408
\mcolrowcell: Added for \multicolumrow cells. 454
General: 2017/10/07 1
multirow: Add: \cmidrule trims. 832
Added vertical rules. 832
Fix: < spec. 833
Improved rules. 627
tabular: Fix: \NoAutoSpacing in a tabular with babel-french. . . . 457
v0.42
\@ensuredmath: Improved \ensuremath. 508
\@textsubscript: Added. 566
\@textsuperscript: Added. 566
\LWR@HTMLhline: If FormatWP force explicit border. 455
\LWR@addformatwpalignment: If FormatWP add explicit style for cell alignment. 433
\LWR@addrulewidth: If FormatWP force explicit border. 432

\LWR@amsmathbody: Fix: Numbering and naming AMS math environments. 524
\LWR@amsmathbodynumbered: Fix: Numbering and naming AMS math environments. 525
\LWR@doequation: If FormatWP print LaTeX expression. 512
\LWR@domulticolumn: If FormatWP add cell alignment. 443
\LWR@doubledollar: If FormatWP print LaTeX expression. 506
Improved \ensuremath. 506
Improved line spacing with mathjax. 506
\LWR@floatbegin: If FormatWP add a text frame. 473
\LWR@floatend: If FormatWP add a text frame. 474
\LWR@htmlmathlabel: If FormatWP print LaTeX expression. 516
\LWR@includegraphicsb: Fix: Filename expansion. 743
If FormatWP, use explicit size. . . . 745
\LWR@rememberтag: Fix: Numbering and naming AMS math environments. 524
\LWR@restoreorigformatting: Improved \ensuremath. 493
\LWR@subaddcmidruletrim: 0pt if no rule given. 431
\LWR@subsingledollar: If FormatWP print LaTeX expression. 500
\LWR@tabledatasinglecolumntag: If FormatWP add cell alignment. . . 427
\LaTeX: If FormatWP use explicit style. 577
\TeX: If FormatWP use explicit style. 577
\hspace: If FormatWP add \quads. . . 571
\listoffigures: Added boolean WPMarkLOFT. 482
\listoftables: Added boolean WPMarkLOFT. 482
\marginpar: If FormatWP emulate a wrapfig. 347
\marginparBlock: If FormatWP emulate a wrapfig. 347
\rule: If FormatWP add \quads. . . . 575
\tableofcontents: Added boolean WPMarkTOC. 481
\underline: If FormatWP, use explicit styles for \underline, etc. 566
General: 2017/10/30 1
\textbf and related: If FormatWP, use explicit styles for \textsc, etc. 555
algorithmicx: If FormatWP add \quads. 596
epigraph: If FormatWP add HTML styles. 688
fancybox: If FormatWP add HTML styles. 697
floatflt: Added width. 715
includegraphics: Fix: Class key. . . 743
keyfloat: If FormatWP add explicit HTML style. 778
moreverb: Simplified formatting of listings. 825
multirow: If FormatWP add cell alignment. 833
overpic: Added. 866
realscripts: Fix for subscripts in a lateximage. 887
sidenotes: If FormatWP add explicit HTML style. 909
siunitx: Improved \ensuremath. . 911
soul: If FormatWP, add explicit styles. 915
textcomp: Improved \interrobangdown. 935
wrapfig: If FormatWP add explicit HTML style. 989
Added boolean WPMarkLOFT. . . . 237
Added boolean WPMarkMath. . . . 237
Added boolean WPMarkMinipages. 236
Added boolean WPMarkTOC. 236
Added boolean WPTitleHeading. 237
Docs: Added support page. 2
Docs: Improper \prevdepth. . . . 181
Docs: Reorganized math limitations 143
File: lwarp_mathjax.txt: Updated siunitx script. 290
Fix: Numbering and naming AMS math environments. 523
If FormatWP force explicit border. 627
If FormatWP, shift section headings. 237
tabbing: Added. 391
lateximage: Fix: Numbering and naming AMS math environments. 527
center: If FormatWP use explicit text-align. 531
minipage: Added boolean WPMarkMinipages. 549
If FormatWP add a text frame. . . . 547
eqnarray: Fix: Numbering and naming AMS math environments. 518
If FormatWP print LaTeX expression. 518
LWR@BlockClassWP: Added to factor code. 330

LWR@figcaption: If FormatWP forces italic captions. 477
v0.43
\LWR@domulticolumn: Fix for vertical rules. 443
Fix: Multicolumn trim. 442, 443
\LWR@maybeprintpendingfootnotes: Added FootnoteDepth. 346
\LWR@nullfonts: Fix: Nullify dollar inside filesnames. 560
\LWR@parsetablecols: Ignore spaces in col spec. 420
\LWR@printmccoltype: Added vertical rules. 438
\LWR@section: Fix: Expansion in comparison. 362
Fix: Math in section name. . 363, 366
Fix: Nullify fonts inside HTML comment. 363
\TabularMacro: \newcommand instead of \relax to fix supertabular and xtab. 450
\href: Made robust. 470
\nameref: Made robust. 468
\nolinkurl: Made robust. 470
\url: Made robust. 471
General: 2017/11/08 1
LWR@currentautosec: Added. . . . 361
breakurl: Added. 629
hyperref: Made robust. 756, 758, 760
hyperref: \Gauge added. 760
luatodonotes: Added. 797
todonotes: Added. 970
Added FootnoteDepth. 342
Docs: HTML settings table. 105
Docs: Reorganized HTML customization. 105
v0.44
\@currentlabelname: Adjustment for koma-script. 463
\HTMLTitle: Added. 340
\LWR@addformatwpalignment: Fix for multicolumn alignment if FormatWP. 433
\LWR@backgroundcolor: Added. . . . 994
\LWR@filestart: Add \HTMLTitle. . 371
Fix \HTMLAuthor. 370
\LWR@listitem: Added list and trivlist. 395
\LWR@patchlists: Added list and trivlist. 398
\LWR@strresult: Fix: \providecommand. 404
\LWR@textcurrentcolor: xcolor: Added \LWR@textcurrentcolor. 993
\addcontentsline: Automatic \LWR@newfloatanchor. 478
\chapter: Add preamble for koma-script. 368
\marginparBlock: Added. 347
\nopagecolor: xcolor: Fix for \nopagecolor. 995
\part: Add preamble for koma-script. 367
\title: Added \thetitle. 340
General: 2017/11/22 1
algorithmicx: Improved comment symbol. 596
atbegshi: Added. 611
cancel: Added. 632
changepage: Additional options. 639
easy-todo: Added. 682
fancyref: Added. 702
fixmetodonotes: Added. 712
fixme: Added. 711
fontenc: Allowed after lwarp. . . . 726
hang: Added. 752
ifoddpage: Added. 763
ltxtable: Added. 796
luatodonotes: Improved. 797
lwarp-patch-komascript: Added. 1014
overpic: Fix: Groups for lateximages. 866
pdfsync: Fixes. 874
preview: Added. 881
scrextend: Added. 895
scrhack: Added. 898
scrlayer-notecolumn: Added. . . . 900
scrlayer-scrpage: Added. 900
scrlayer: Added. 898
section: Added. 902
soulpos: Added. 917
soulutf8: Added. 918
supertabular: Fix for caption. . . . 930
tikz: Fix: Groups for lateximages. 947
tocbasic: Added. 959
tocloft: Added \newlistentry. . . 967
tocloft: Improved \newlistof. . . 968
tocstyle: Added. 969
todonotes: Improved. 970
todo: Added. 969
typearea: Added expert commands. 976
watermark: Added. 988
xcolor: Added \LWR@currenttextcolorstyle. . 993
xcolor: Added \LWR@findcurrenttextcolor. . . 993
xtab: Fix for caption. 1009
Adjustment for koma-script. . . . 202

AMS environments: Fix: Groups for lateximages. 598
If pdfLaTeX, require T1 and UTF-8 encoding. 203
picture: overpic: Fix: Groups for lateximages. 544
list: Added list and trivlist. . . 396
LWR@nestspan: Added list and trivlist. 324
v0.45
\@currentHref: Added. 469
\@donoparitem: Modified for HTML. 393
\@item: Modified for HTML. 394
\@mklab: Modified for HTML. 393
\CSSFilename: Improved filenames with underscores. 339
\LWR@LwarpStart: Fix: Lateximages on incorrect pages with Mathjax. 374
\LWR@includegraphicsb: Improved URLs with underscores. 743
\LWR@newautoidanchor: Fix: No anchor if frozen autoid. 475
\LWR@notmemoirloadafter: Added. 191
\LWR@printpendingmpfootnotes: Added. 346
\LWR@startref: Fix: Labels with underscores. 467
\LWR@subhyperref: Improved URLs with underscores. 469
\LWR@subhyperrefclass: Improved URLs with underscores. 469
\LWR@sublabel: Fix: Labels with underscores. 465
\LWR@tabledatacolumntag: Fix: Empty line between rows. 453
\chapter: Add optional heading title for memoir. 368
\newpage: Added. 569
\nolinkurl: Fix: Underscore in URL. 470
\normalmarginpar: Added. 348
\reversemarginpar: Added. 348
\section: Add optional heading title for memoir. 368
\tableofcontents: Fix: Empty sidetoc. 481
Fix: Patch \AtBeginDocument. . . 481
\url: Improved URLs with underscores. 471
General: 2018/01/14 1
array: Added. 607
babel-french: Robust commands. 323
backref: Added. 617
breakurl: Fix: Underscore in URL. 629
changebar: Added. 637
cite: Added. 668
continue: Added. 672
endfloat: Added. 685
epigraph: Support for memoir. . . 689
fancyvrb: Improvements. . . . 703, 705
flafter: Added. 713
fltrace: Added. 721
footnpag: Added. 729
fwlw: Added. 734
hanging: Added. 754
hyperref: Fix: Underscore in URL. 756, 757
lwarp-patch-memoir: Added. . . 1016
memhfixc: Added. 818
memoir: Added. 580
natbib: Added. 839
pagesel: Added. 868
prettyref: Added. 881
subfigure: Added. 929
subfig: Fix for subcaption end tag. 927
subfig: Fix: Math in subcaptions. 925
textfit: Added. 939
titleref: Added. 951
turnthepage: Added. 975
Allows memoir's preloaded packages. 194
Docs: xparse warnings. 162
Docs: Fix for double hyphens. . . . 78
Docs: Improved install instructions. 79
Docs: Improved MiKTEX install instructions. 75
Docs: Moved table so doesn't interfere with install docs. 74
File: lwarp_mathjax.txt: Allow MATHJAX inside tabbing. 290
File: lwarp_mathjax.txt: Allow MATHJAX inside verse. 290
Fix: Empty sidetoc. 481
Improved: Robust \, \ , and \textellipsis commands. 568
Separate LWR@thisautoidWP for word processor s. 475
thebibliography: Patched to emphasize titles. 491
minipage: Fix: Improper \prevdepth. 547, 549
v0.46
\LWR@closeparagraph: Fix: Tabular empty lines. 335
\LWR@closeprevious: Fix: Stack unnesting. 321
\LWR@forcenewpage: Fix: Improper \prevdepth. 321
\LWR@lookforpackagename: Fix: Spaces in \usepackage. 225
\LWR@popclose: Fix: Stack unnesting. 312

\LWR@providelength: Added. 205
\LWR@pushclose: Fix: Stack unnesting. 311
\LWRPrintStack: Name changed from \PrintStack. 320
General: 2018/01/23 1
LWR@tabularpardepth added. . . 404
amsthm: Adapted to trivlist changes. 602
mdframed: Fixes for svg math or lateximage in title. 810
mdframed: Fixes for footnotes. . 811
ntheorem: Adapted to trivlist changes. 854
theorem: Adapt to trivlist changes. 941, 943
tabular: Fix: Tabular empty lines. 459, 460
list: Fix: Stack unnesting. 396
v0.47
\LWR@HTML@caption@begin: Fix: Argument passed to \LWR@origcaption@begin. 477
\LWR@LwarpStart: Fix for svg math in \nameref. 375
\LWR@WPcell: Fix: Line wrap at html hyphen. 433
\LWR@createautosec: Fix: Line wrap at html hyphen. 360
\LWR@domulticolumn: Fix: Line wrap at html hyphen. 443
\LWR@floatbegin: Fix: Line wrap at html hyphen. 473
\LWR@htmlclosecomment: Add \mbox to prevent line breaks. 326
\LWR@newautoidanchor: Fix: Line wrap at html hyphen. 475
\LWR@printopenlist: Fix: Line wrap at html hyphen. 393
\LWR@startref: Fix: Line wrap at html hyphen. 466
\LWR@sublabel: Fix: Line wrap at html hyphen. 465
\LWR@subsingledollar: Added svg math image baseline adjust and em sizing. 500
Fix: Line wrap at html hyphen. . 504
\captionlistentry: Fix: Line wrap at html hyphen. 478
\hypertoc: Fix: Line wrap at html hyphen. 485
\hypertocfloat: Fix: Line wrap at html hyphen. 486
General: 2018/01/30 1
adjmulticol: Fix: Line wrap at html hyphen. 591
blowup: Added. 626
caption: Added. 634
caption: Also loads lwarp-caption. 228
changepage: Fix for pagecheck macros. 639
endheads: Added. 686
epigraph: Fix: Line wrap at html hyphen. 688
hanging: Fix: Line wrap at html hyphen. 754
hang: Fix: Line wrap at html hyphen. 752
keyfloat: Fix for svg math in captions. 775
midpage: Fix: Line wrap at html hyphen. 823
multirow: Fix: Line wrap at html hyphen. 832
multitoc: Added. 834
ntheorem: Fix: Line wrap at html hyphen. 858
realscripts: Fix: Line wrap at html hyphen. 887
scrextend: Fix: Line wrap at html hyphen. 895
sectionbreak: Added. 903
sidenotes: Fix for svg math in captions. 908
subfig: Fix for svg math in captions. 925
subfig: Fix: Support \nameref. . . 924
xurl: Added. 1011
lwarpmk: *pdfcrop*: Removed hires option for improved crop accuracy. 292
lateximage: Added css style option. 526
Fix: Line wrap at html hyphen. . 530
center: Fix: Line wrap at html hyphen. 531
minipage: Fix: Line wrap at html hyphen. 547, 548
flushleft: Fix: Line wrap at html hyphen. 532
flushright: Fix: Line wrap at html hyphen. 531
enumerate: Fix: Line wrap at html hyphen. 397
itemize: Fix: Line wrap at html hyphen. 397
LWR@BlockClassWP: Fix: Line wrap at html hyphen. 330

v0.48
\@@@setcpageref: Fix for new v0.21 of cleveref. 543
\@@@setcref: Fix for new v0.21 of cleveref. 542
\@@@setcrefrange: Fix for new v0.21 of cleveref. 542
\@biblabel: Improved bibliography label. 491
\@item: Honors \makelabel. 394
\@maketitle: Fix: Errors with IEEEtran class. 384
\LWR@LwarpStart: Adjusted space around captions. 373
\LWR@ProvidesPackageDropB: Fix: Options with braces. 227
\LWR@addtabularhrulecolor: colortbl: Added. 434
\LWR@addtabularrulecolors: colortbl: Added. 435
\LWR@closetabledatacell: colortbl: Added. 406, 407
\LWR@includegraphicsb: Fix: Virtual page size limited to a group. 744, 747
\LWR@lookforpackagename: Fix: Parsing similar package names. . 224
\LWR@newautopagelabel: Fix: TOC, LOF, LOT links. 353
\LWR@newhtmlfile: Fix: TOC, LOF, LOT links. 357
\LWR@nullfonts: Fix: \newline in title. 560
\LWR@parsedrequirepackagenames: Fix: Parsing similar package names. 223
\LWR@parsetablecols: Fix: Ignore optional tabular column arguments. 421
\LWR@restoreorigformatting: Fix: Spacing in SVG math, lateximage, Ti*k*z. 492
\LWR@section: Fix: TOC, LOF, LOT links. 366
\LWR@tabledatasinglecolumntag: colortbl: Added. 427
\LWR@textcurrentfont: Added. Improves font control. 563
\bibliography: Fix: \BaseJobname for bibliography. 491
\centerline: Added. 533
\l@part: Adapts to classes without \part. 487
\leftline: Added. 532
\mbox: Nullified for HTML. 550
\rightline: Added. 533
\thempfootnote: Removed \itshape. 346
General: 2018/02/14 1
acronym: Added. 590
acro: Added. 587
chapterbib: Added. 642
colortbl: Added. 423, 434, 670
fancyref: Now directly supported. 702
hypcap: Added. 755
hypernat: Added. 755
hyperref: \texorpdfstring now uses the TEX string. 759
luatodonotes: Improved \todototoc. 797
siunitx: Changes fraction to symbol. 912, 913
siunitx: Improved SVG math. 911, 912
siunitx: Improved color output. . 911
stfloats: Added. 922
todonotes: Improved \todototoc. 970
vmargin: Added. 984
xfrac: Fix: Added groups around super/subscripts to localize LWR@nestspan changes. 1003
Docs: Converting an existing document. 95
Improved font control. . . . 563, 564
tabular: colortbl: Added. 458
lateximage: Print mode boxed to natural width. 531
abstract: Allow optional name. . . . 386
v0.49
\LWR@addtabularcellcolor: xcolor: Added tabular row colors. 437
\LWR@domulticolumn: xcolor: Added tabular row colors. 443
\LWR@printlength: Fix: Group printlen changes. 222
\affiliation: Fix: Adapts to classes which already provide. 379
\href: Fix: Adapt to classes. 470
\noalign: Fix: \noalign inside tabular. 455
\url: Fix: Adapt to classes. 471
General: 2018/02/19 1
amsmath: Fix: Patches for \eqref. 597
eso-pic: Fix for \AddToShipoutPicture. 694
figsize: Added. 710
fnlineno: Added. 723
hypdestopt: Added. 755
hyphenat: Added. 761
lineno: Added. 783
luacolor: Added. 796
pagegrid: Added. 867
pdfrender: Added. 874

resizegather: Added. 891
vertbars: Added. 984
vwcol: Added. 985
xcolor: Added tabular row colors. 423, 999
Fix: Adapt to classes. 568
v0.50
\@ensuredmath: Fix: Use lateximage even if MathJax. 508
Improved SVG math alt tags. . . . 508
\LWR@@footnotetext: Robustify macros. 344
\LWR@atbeginverbatim: Improved column alignment. 390
\LWR@doequation: Improved SVG math display. 512
\LWR@doubledollar: Improved SVG math alt tags. 506
Improved SVG math display. 506
\LWR@htmlrefsectionfilename: Fix: SVG math in a section name. . . 318
\LWR@newhtmlfile: Fix: SVG math in a section name. 356
\LWR@nullfonts: Fix: \underline in sectioning file name. 562
\LWR@overline: Added. 566
\LWR@subsingledollar: Fix: Use lateximage even if MathJax. . . . 500
Improved SVG math alt tags. . . . 500
MD5 hash avoids duplicate SVG math. 504
\LWR@vspace: Robustify macros. . . . 572
\newline: Robustify macros. 569
\textsubscript: Robustify macros. 566
\textsuperscript: Robustify macros. 566
General: 2018/03/03 1
lwarp.css: Improved SVG display math centering. 249
lwarp_one_limage.txt: Added. . 289
amsmath: Fix: Upright tags for SVGmath. 597
axodraw2: Added. 616
bytefield: Added. 632
dblfloatfix: Added. 677
diagbox: Added. 678
epstopdf: Added. 690
listings: Force flexible columns. . 786
morefloats: Added. 824
nonfloat: Added. 852
ntheorem: Fix: Not standard nor amsthm selected. 860
pbox: Added. 870
phfqit: Added. 877
schemata: Added. 894
siunitx: Fix: Loads xcolor. 910
siunitx: Improved SVG math alt tags. 912
siunitx: Improved units. 535, 910, 913
xy: Added. 1011
lwarpmk: Error if lateximages.txt does not exist. 292
lwarpmk: Error if lwarpmk.conf points to lwarp. 292
lwarpmk: Improved error messages. 292
lwarpmk: MD5 hash avoids duplicate SVG math. 292
lwarpmk: Multiprocess support making lateximages. 292
AMS environments: Improved SVG math display. 598
Fix: Load fontspec if necessary. . 217
Robustify macros. 564
lateximage: Fix: SVG math in a section name. 529
MD5 hash avoids duplicate SVG math. 527, 530
eqnarray: Improved SVG math display. 518, 519
v0.51
\@ensuredmath: Hashes \ensuremath. 508
\@item: Restored list label space. . . 395
\LWR@HTMLsanitize: Fix: Escapes double quotes. 522
\LWR@HTMLsanitizeexpand: Fix: Escapes double quotes. 523
\LWR@LwarpStart: MathJax: Nullifies \ensuremath. 375
\LWR@addbaselinemarker: Improved SVG math baseline. 499
\LWR@atbeginverbatim: Adds vertical offset. 389
\LWR@customizeMathJax: MathJax: Nullifies \ensuremath. 353
\LWR@doequation: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 512
\LWR@doubledollar: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 506
\LWR@findcurrenttextcolor: Added \LWR@findcurrenttextcolor when no xcolor. 567
\LWR@newautoidanchor: Fix: No autoid is inside a lateximage. . . 475
\LWR@newhtmlfile: MathJax: Nullifies \ensuremath. 358

\LWR@subsingledollar: Fix: \ensuredmath inside SVG image. 501
Fix: lateximage inside $\mathcal{AMS}$ \text. 502
Fix: Honors text font around SVG math. 502
Fix: SVG math with enclosed lateximage. 501
Improved SVG math baseline. . . . 502
SVG math baseline improved with invisible rule at corner. 505
Typeset SVG math only once during measurement. 502
\LWR@textcurrentcolor: xcolor: \LWR@textcurrentcolor if xcolor not loaded. 567
\addcontentsline: Add missing support for float mechanism if necessary. 479
No anchor ID if inside SVG image. 478
\displaymathnormal: Processing for complicated display math. . . . 515
\displaymathother: Processing for complicated display math. . . . 515
General: 2018/03/24 1
lwarp_one_limage.txt: *pdftocairo* -noshrink added. 289
afterpackage: No longer required. 220
chemfig: Added. 642
chemformula: Added. 644
chemgreek: Added. 649
chemmacros: Added. 649
chemnum: Added. 667
epstopdf-base: Added. 690
fancybox: Fix: Optional tag for \item in a span. 700
grid: Added. 751
listings: Forces cleared options. . 787
ltxgrid: Added. 795
mhchem: Added. 820
tikz: Fix for \tikz macro. 947
tikz: Fix for tikz with optional argument. 947
titling: Fix for \thanks mark. . . . 956
lwarpmk: *pdfcrop*: Restored hires option. 292
lwarpmk: *pdftocairo* -noshrink added. 292
AMS environments: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 598
Docs: tikz limitations. 149
Docs: Multiple authors and affiliations. 127
Docs: Things to avoid. 117
Docs: Updated Converting an existing document. 95
Fix: Remember original \# in case is redefined. 239
Named HTML entity used for text dollar. 499
lateximage: Added additional hashing option. 526
Fix: lateximage inside $\mathcal{AMS}$ \text. 526
Processing for complicated display math. 529
alignat: Fix: Added. 600
eqnarray: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 518, 519
LWR@displaymathother: Processing for complicated display math. . . 509
LWR@equationother: Processing for complicated display math. . . . 509
v0.52
\@ensuredmath: Improved hashing expansion. 508
\@mpfootnotetext: Fix: Paragraph handling. 345
\CustomizeMathJax: Added. 353
\LWR@@footnotetext: Fix: Paragraph handling. 344
\LWR@addbaselinemarker: Warnings if lwarp_baseline_marker.png is not present or if graphicx/s not loaded. 499
\LWR@customizedMathJax: Added. . 353
\LWR@doequation: Fix: equation* now based on equation instead of displaymath. 512
Fix: equation* with split. . . . 512
\LWR@filenamenoblanks: Fix: \FileDepth with non-utf8 encoding. 352
\LWR@nullfonts: Fix: \texorpdfstring in section names. 563
\LWR@section: Fix: Footnote numbering: Limited HTML comment if starred. 363
Fix: Footnote numbering: Use short TOC entry for HTMLDebug comments. 363
\LWR@subsingledollar: Added user-adjustable SVG math font scaling. 503
\LateximageFontScale: Added user-adjustable SVG math font scaling. 521

\href: Fix: #, %, &, ~, _ in URL. 470
\nolinkurl: Fix: #, %, &, ~, _ in URL. 470
\theHTMLTitleSeparator: Fix: \FileDepth with non-utf8 encoding. 369
\url: Fix: #, %, &, ~, _ in URL. 471
General: 2018/04/01 1
breakurl: Fix: #, %, &, ~, _ in URL. . 629
endfloat: Updated for v2.6. 685
fancyvrb: Initial support for \VerbatimFootnotes. 697, 703
hyperref: Fix: #, %, &, ~, _ in URL. 756–758
nicefrac: Added. 850
url: Added. 981
lwarpmk: Fix: Memory overflow when spawning tasks. 292
lwarpmk: Fix: Skip image generation if from page 0. 292
Changed FootnoteDepth default to \subsubsection. 342
Docs: Improved install instructions. 76
Fix: MathJax script line wraps. Reduced right margin. 218
If pdfLaTeX, allow other input encoding. 203
pkggraphics: Added defaults. . . . 741
pkggraphicx: Updated for v1.1a. . 742
pkggraphicx: Updated for v1.1b. . 742
Restore \kill in a lateximage. . 794
tabbing: Fix to allow inside lateximage. 391
lateximage: Fix for hash expansion. 528
v0.53
General: 2018/04/01 1
lwarpmk: Added **lwarpmk cleanlimages**. 292
lwarpmk: Added warning for corrupted images. 292
Docs: **lwarpmk cleanlimages**. . . . 92
Docs: **lwarpmk pdftohtml**. 92
v0.54
\LWR@afterendverbatim: Added vspace argument. 390
\LWR@atbeginverbatim: Improved column alignment. 390
\LWR@earlyloadnever: Added. 193
\LWR@endfloatalignment: Honor \centering, etc. in floats. 475
\LWR@floatalignment: Honor \centering, etc. in floats. 475
\LWR@floatbegin: Honor \centering, etc. in floats. 473
\LWR@floatend: Honor \centering, etc. in floats. 474
\LateximageFontSizeName: Defaults to normalsize. 521
\centering: Added debug comment. 532
\raggedleft: Added debug comment. 532
\raggedright: Added debug comment. 532
General: 2018/04/22 1
*.lwarpmkconf: Option IndexLanguage changed to xindyLanguage. 249
*.lwarpmkconf: Option pdftotextEnc added. 249
*.lwarpmkconf: Option xdyFilename changed to xindyStyle. 249
*.lwarpmkconf: Option xindyCodepage added. 249
lwarp.css: Fix: Text-decoration-skip: auto. . . . 249
lwarpmk.conf: Option IndexLanguage changed to xindyLanguage. 249
lwarpmk.conf: Option pdftotextEnc added. 249
lwarpmk.conf: Option xdyFilename changed to xindyStyle. 249
lwarpmk.conf: Option xindyCodepage added. 249
bibunits: Added. 623
chngpage: Added. 668
forest: Added. 730
glossaries: Fix when not using babel or polyglossia. 738
gridset: Added. 752
hyperref: Fix: \hyperref and \hyperlink with special chars in text. 758
hyperref: Fix: \ref in \hyperref and \hyperlink caused nested link. 758
lwarp-patch-memoir: Update for v3.7g. 1021
magaz: Added. 801
ragged2e: Fix: \centering, etc. . 886
textcomp: Fix for \textperthousand. 935
tikz: Fixes for \pgfpicture, minipages, fit, align, font. 947
lwarpmk: Added pdftotextenc. . 292
lwarpmk: Added xindycodepage. 292
lwarpmk: Changed language to xindylanguage. 292

lwarpmk: Changed `xdyfile` to `xindystyle`. 292
lwarpmk: Improved error if configuration file does not exist. 292
lwarpmk: Increased prominence for error for an unknown command. 292
lwarpmk: Verifies HTML version exists before `lwarpmk limages`. . 292
lwarpmk: Verifies image references before `lwarpmk limages`. 292
Add: `pdftotextEnc`. 212
Add: `xindyCodepage`. 212
Added early check for disallowed packages. 193
Docs: BibTeX. 129
Docs: Macros in sectioning names. 117
Never load aecompl. 193
Option `IndexLanguage` changed to `xindyLanguage`. 212
Option `xdyFilename` changed to `xindyStyle`. 212
`verse`: Fix: Line spacing. 388
v0.55
`\LWR@LwarpStart`: Fix: Overfull boxes in `lateximages`. 373
`\LWR@floatbegin`: Fix: Float optional args. 473
`\LWR@nullfonts`: Removed extraneous space which appeared in file links. 562
`\phantomsection`: Fix: `\ForceHTMLTOC` with `\phantomsection`. 575
General: 2018/04/26 1
clrdblpg: Added. 669
Fix: `\centering`, etc. for koma-script. 473
Fix: QED symbols in `lateximage`. 603, 865
v0.56
`\LWR@addcdashline`: arydshln: Added. 433
`\LWR@addmulticolvertrulecolor`: Adds support for dashed vertical rules. 441
Adds support for double vertical rules. 441
`\LWR@addtabularhrulecolor`: Adds support for arydshln dashed rules. 434
Adds support for double `\hlines` and `\midrules`. 434
`\LWR@addtabularrulecolors`: Adds support for dashed vertical rules. 435
Adds support for double vertical rules. 435
`\LWR@closeparagraph`: Added support for parnotes. 335
`\LWR@domulticolumn`: Adds support for dashed vertical rules. 443
Adds support for double vertical rules. 443
`\LWR@floatbegin`: Adds a `<class>` per float package style. 473
`\LWR@multicolpartext`: Fix: `\multicolumn` parameters. . . . 439
`\LWR@openparagraph`: Added support for parnotes. 333
`\LWR@parsebarcolumn`: Adds support for double vertical rules. 413
`\LWR@parsecoloncolumn`: arydshln: Added. 414
`\LWR@parsesemicoloncolumn`: arydshln: Added. 414
`\LWR@parsetablecols`: Added array `W` column. 422
`\LWR@printmccoldata`: Added array `W` column. 440
Fix: `\multicolumn` parameters. . . 440
`\LWR@printmccoltype`: Added array `W` column. 438
Adds support for dashed vertical rules. 438
Adds support for double vertical rules. 438
`\LWR@tabledatacolumntag`: Fix: `\morecmidrules` 452
`\LWR@textcurrentfont`: Added `span.textbf`, etc. 563
General: 2018/05/12 1
`*.lwarpmkconf`: Records `--shell-escape`. 249
`lwarp.css`: Added `div.textbf`, etc. 249
`lwarp.css`: Added `span.textbf`, etc. 249
`lwarpmk.conf`: Records `--shell-escape`. 249
arydshln: Added. 401, 608
lua-check-hyphen: Added. 796
paralist: Fixes for `compactenum`, `compactitem`, `compactdesc`. . . 868
parnotes: Added. 868
quoting: Added. 886
tocenter: Added. 963
underscore: Added. 979
lwarpmk: Added `lwarpmk pdftosvg`. 292

lwarpmk: Supports `--shell-escape`. 292
Added `\thinspace`. 568
Docs: **`lwarpmk pdftosvg`**. 92
`LWR@blocktextcurrentfont`: Added `div.textbf`, etc. 563
v0.57
`\BlockClassSingle`: Improved print/HTML output selection. . . 329
`\InlineClass`: Improved print/HTML output selection. 330
`\LWR@customizeMathJax`: MathJax: Supports `\footnote`, `\footnotemark`. 353
`\LWR@ref@ignorestar`: subcaption: Fix: `\subref`. 468
`\LWR@subhyperref`: Fix: Text catcodes. 469
`\LWR@subhyperreftext`: Fix: Text catcodes. 469
`\LWR@subsingledollar`: Fix: Dynamic inline math expressions. 501, 502, 504
`\LWR@vspace`: Improved print/HTML output selection. 572
`\MathImageAltText`: Added. 497
`\PackageDiagramAltText`: Added. . 498
`\StartDefiningMath`: Added. 314
`\boxframe`: xcolor: Fix: Colored `\boxframe`. 999
`\colorbox`: xcolor: New system for switching print and HTML outputs. 996
`\colorboxBlock`: xcolor: New system for switching print and HTML outputs. 996
`\fboxBlock`: Improved print/HTML output selection. 553
`\fcolorbox`: xcolor: New system for switching print and HTML outputs. 996
`\framebox`: Improved print/HTML output selection. 551
`\href`: Fix: Text catcodes. 470
`\inlinemathother`: Added. 315
`\listof`: Fix: Provide `\l@name` if not defined. 482
`\makebox`: Improved print/HTML output selection. 551
`\mbox`: Improved print/HTML output selection. 550
`\multicolumnrow`: multirow: Improved print/HTML output selection. 833
Improved print/HTML output selection. 448
`\newfloat`: rotfloat: Added float styles. 893
rotfloat: Fix for listof sideways floats. 893
`\parbox`: Improved print/HTML output selection. 550
`\raisebox`: Improved print/HTML output selection. 555
`\reflectbox`: Improved print/HTML output selection. 750
`\resizebox`: Improved print/HTML output selection. 750
`\rotatebox`: Improved print/HTML output selection. 748
`\rule`: Fix: Colored rules. 574
`\scalebox`: Improved print/HTML output selection. 749
`\textcolor`: xcolor: New system for switching print and HTML outputs. 995
General: 2018/06/06 1
`lwarp.css`: Added ruled, boxed, boxruled floats. 249
`lwarp.css`: Increased float vertical margins. 249
algorithm2e: Added. 592
bigdelim: Improved print/HTML output selection. 624
breakurl: Fix: Text catcodes. . . . 629
colortbl: New system for switching print and HTML outputs. . . 670, 671
ellipsis: Added `\midwordellipsis`. 684
errata: Added. 692
float: Added float styles. 714
float: Fix: Do not pre-define `\l@name`. 714
ltablex: Added. 794
marginnote: Fix: Long optional argument. 805
multirow: Improved print/HTML output selection. 832
register: Added. 888
subcaption: Fix: `\subref`. 757
trimclip: Added. 973
vowel: Added. 985
xellipsis: Added. 1001
xfrac: Improved print/HTML `\scalebox` control. 1003
xltabular: Added. 1005
xpiano: Added. 1006
lwarpmk: Improved code factoring. 292
lwarpmk: Improved error handling. 292
Docs: Recompiling *lwarpmk* or CSS files. 177

Docs: Recreating the index for lwarp source. 174
New system for switching print and HTML outputs. 234
minipage: Improved print/HTML output selection. 546
BlockClass: Improved print/HTML output selection. 329
fminipage: Improved print/HTML output selection. 553
LWR@BlockClassWP: Improved print/HTML output selection. . . 330
v0.58
\LWR@HTML@caption@begin: Improved print/HTML output selection. . . 477
\LWR@HTML@caption@end: Improved print/HTML output selection. . . 477
\LWR@HTML@ref: Improved print/HTML output selection. 467
\LWR@doindexentry: Adds support for \see, \seealso, \emph, \textbf, etc. 489
\LWR@hyperindexrefnullified: Adds support for \see, \seealso, \emph, \textbf, etc. 489
\LWR@indexitem: Accepts optional arg for repeatindex. 488
\dotfill: Improved print/HTML output selection. 569
\hfill: Improved print/HTML output selection. 568
\hrulefill: Improved print/HTML output selection. 569
\hyperindexref: Adds support for \see, \seealso, \emph, \textbf, etc. 490
\printindex: Fix: Extra \newpage to flush pending \index writes. . . . 801
General: 2018/07/07 1
*.lwarpmkconf: Added option makeindexstyle. 249
*.lwarpmkconf: Added options makeindex and xindy. 249
*.lwarpmkconf: Generated \AtBeginDocument. 249
lwarp.xdy: Requires makeindex.xdy. 288
lwarp.xdy: Supports bold, italic. 288
lwarp_html.ist: Added. 288
lwarpmk.conf: Added option makeindexstyle. 249
lwarpmk.conf: Added options makeindex and xindy. 249
lwarpmk.conf: Generated \AtBeginDocument. 249
array: Improved print/HTML output selection. 607
attachfile2: Added. 612
attachfile: Added. 611
cases: Added. 637
imakeidx: Added. 763
index: Added. 767
intopdf: Added. 769
lwarp-patch-komascript: Modified indexing. 1014
lwarp-patch-memoir: Fix for \specialindex. 1037
lwarp-patch-memoir: Fix for multiple indexes. 1037
makeidx: Added. Moved from lwarp core. 801
memoir: Fix for \firsthlline, \lasthline. 450
memoir: Fix for booktabs. 454
pdfpages: Added. 872
pdfx: Added. 875
repeatindex: Added. 891
splitidx: Added. 918
textcomp: Improved print/HTML output selection. 935
lwarpmk: Added makeindex and xindy options. 292
lwarpmk: Added -p option for project name. 292
lwarpmk: Added optional list of names for **lwarpmk printindex** and /cmdslwarpmk htmlindex. . 292
lwarpmk: Glossary generation now uses *makeglossaries*. 292
lwarpmk: **lwarpmk clean** removes all *.ind and *.idx files. 292
Added makeindex option. 213
Added xindy option. 213
Added option makeindexStyle. . 212
Docs: Index, *makeindex*, imakeidx. 131
Docs: Misplaced \omit. 181
Fix: memoir and ccaption. 194
Improved print/HTML output selection. 568
Replaced each \csuse with \@nameuse to force error if undefined. 1
tabbing: Improved print/HTML output selection. 391
v0.59
\LWR@addbaselinemarker: Uses .eps if DVI *latex*. 499
\LWR@includegraphicsb: Fix: Expand filename. 744

Now works with .pdf and .eps filename extensions. 743
\LWR@latexmkcmd: Fix: --shell-escape with *latexmk*. . . 244
\LWR@writeconf: Compilation commands now preassigned by lwarp instead of being computed by *lwarpmk*. 248
\[: Fix with \displaymathnormal. . 507
General: 2018/09/07 1
Slunits: Added. 909
accsupp: Added. 587
amsmath: Moved from the lwarp core. 597
asymptote: Added. 610
axessibility: Added. 616
breqn: Added. 630
bxpapersize: Added. 632
canoniclayout: Added. 633
chemformula: Fix for \NMR. 664
draftcopy: Added. 680
epstopdf-base: Improved. 690
epstopdf: Improved. 690
fnbreak: Added. 722
nccfancyhdr: Added. 840
pdftricks: Added. 875
pst-eps: Added. 882
pstricks: Added. 883
units: Added support for MathJax. 979
xunicode: Added. 1010
lwarpmk: Added **lwarpmk epstopdf**. 292
lwarpmk: Consolidated compiling options into printlatexcmd and HTMLlatexcmd. 292
lwarpmk: Double insead of single-dashed --shell-escape option. 292
lwarpmk: Error if lwarpmk.conf format changed. 292
lwarpmk: Warning if operating system changed. 292
Added option dvipdfmx. 214
Added option dvipdfm. 214
Added option dvips. 214
Docs: **lwarpmk epstopdf**. 92
File: lwarp_mathjax.txt: Fix: Removed chapter number from tagged non-numeric MathJax equations. 290
File: lwarp_mathjax.txt: Updated to MathJax v2.7.4. 290
picture: Added an alt tag. 544
v0.60
\LWR@clearmidrules: tabular: Fix for midrules. 429
\LWR@parsenormalcolumn: tabular: Improved memory management: Not using xstring. 415
\LWR@tabledatasinglecolumntag: tabular: Improved memory management: Not using xstring. 427
\LWR@tabularendofline: Fix: Slowdown for long tables. 410
General: 2018/09/19 1
tabular: Improved memory management: Global boolean. 402, 403
tabular: Improved memory management: Not using xstring. 404, 832
2up: Added. 583
booklet: Added. 626
bophook: Added. 628
diagbox: Fix for par tags. 679
draftfigure: Added. 681
fancytabs: Added. 703
fullminipage: Added. 733
grid-system: Added. 752
layaureo: Added. 779
leading: Added. 782
listings: Fix for HTML entities. . . . 787
listings: Fix if inside a list. . . 787, 790
thumbs: Added. 946
thumb: Added. 946
widows-and-orphans: Added. . . 988
v0.61
\DeclareGraphicsExtensions: Fix: EPS for DVI LaTeX. 739
\LWR@HTMLLatexCmd: Added HTMLLatexCmd option. 248
Added PrintLatexCmd option. . . 248
\LWR@addcompilecmd: Removed spaces. 243
\LWR@closetabledatacell: Fix: Par tags in tabular. 405
\LWR@hyperindexrefnullified: Made robust, ... 489
\LWR@includegraphicsb: Fix: EPS for DVI LaTeX. 745
Set keys before using filename, for epsfig. 744
\LWRopseq: Added spaces. 209
\RequirePackage: Support up to 20 packages. 225
\inlinemathnormal: Changed name from \StopDynamicMath to \inlinemathnormal. 315

\inlinemathother: Changed name from \StartDynamicMath to \inlinemathother. 315
\listof: Fix: newfloat lists. 482
\lwarpsetup: Added. 210
General: 2018/10/13 1
lwarp.css: Footnotes text align left. 249
lwarp.css: Minipage table and footnotes: tighter margin. 249
chkfloat: Added. 668
cmdtrack: Added. 670
copyrightbox: Added. 672
dprogress: Added. 680
epsfig: Added. 689
lua-visual-debug: Added. 796
pdfprivacy: Added. 874
psfragx: Added. 882
psfrag: Added. 881
pstool: Added. 883
refcheck: Added. 888
srcltx: Added. 919
srctex: Added. 920
supertabular: Fix for caption w/o opt arg. 930
thinsp: Added. 943
threadcol: Added. 944
uspace: Added. 981
vpe: Added. 985
xbmks: Added. 990
xtab: Fix for caption w/o opt arg. 1009
Added HTMLLatexCmd option. . . . 213
Added PrintLatexCmd option. . . 213
Docs: \tracinglwarp 230
Docs: HTML entities. 117
Docs: Compiling using custom shell commands. 163
Docs: Fonts. 97
Docs: HTMLDebugComments 105, 230
Docs: Multiple indexes. 186
Don't write configuration files if processing pstool image. 242
Spaces redefined \AtBeginDocument. 568
v0.62
\@partcntformat: Added for ctex. . 361
\@partnameformat: Added for ctex. 361
\InlineClass: Added optional word-processing style. Replaces \LWR@HTMLtextstyle. 330
\LWR@PreloadedPackage: Added. . . 533
\LWR@ProvidesPackagePass: Fix: Unknown option error. 226
\LWR@endofline: Extra space if optional arg. 569
\LWR@filestart: Refactored. 371
\LWR@includegraphicsb: Fix: FormatWP. 745
Fix: Filename expansion. 746
\LWR@isolate: Added. 206
\LWR@textcurrentfont: Added print version. 567
Tracks depth to avoid nesting repeated font changes. 563
\colorboxBlock: Fix: Horiz white space. 996
\fcolorbox: Fix: No longer requires xifthen. 538
\fcolorboxBlock: Fix: Horiz white space. 997, 998
\l@chapter: Don't define if no \chapter. Fix for algorithm2e. . . 487
\slshape: Added. 565
\textup: Fixed WP span class. . . . 557
\theHTMLSection: Added. 370
\theHTMLTitleSection: Added. . . . 369
\theHTMLTitleSeparator: Refactored. 369
General: 2018/11/19 1
\textbf and related: Improved font detection. 555
lwarp.css: Added css for xfrac, nicefrac. 249
lwarp.css: Fixed css for \textup. 249
lwarp.css: Reduced margins in titlepage. 249
lwarp_formal.css: Fix: Font for verse. 283
2in1: Added. 583
CJKutf8: Prevented unless xeCJK. 669
CJK: Prevented unless xeCJK. . . . 669
asymptote: Improved alt tags. . 610
bitpattern: Added. 625
calc: Fix: Required for print version. 220
chngpage: Fix: Loads lwarp-chngpage. 668
ctexpatch: Added patch. 581
flippdf: Added. 713
musicography: Added. 834
nicefrac: Improved font control and css, honors nice, ugly. 850
notespages: Added. 853
octave: Added. 865
pdfcomment: Added. 870
pdfmarginpar: Added. 871
register: Updated to v1.8. 888
rviewport: Added. 894
semantic-markup: Added. 904

textcomp: Fix conflict with xunicode. 937
tram: Added. 972
twoup: Added. 975
ulem: Improved compatibility with CJKulem. 977
ulem: Now works in a lateximage. 977
unitsdef: Added. 980
units: Improved font control and css, honors loose, tight. 979
xechangebar: Added. 1001
xfrac: Improved css. 1003
xunicode: Fix conflict with textcomp. 1010
Added early checks for CJK, CJKutf8. 193
Docs: asymptote. 151
Docs: miktex-poppler-bin-* 79
Docs: *MiKTeX Console* 75
Docs: Improved MiKTEX install instructions. 75
Docs: UTF-8 locale. 166
File: lwarp_mathjax.txt: Removed inoperable siunitx extension. . . . 290
Fix for \em. 559
Fix: Horiz white space. 998
Logos: CSS instead of <sup>, <sub>. 576
Logos: Fix for XƎTEX logo if graphics is not loaded. 576
Logos: Improved CSS. 576
Logos: Made robust. 576
fcolorminipage: Fix: Horiz white space. 999
Fix: No longer requires xifthen. . 539
fminipage: Fix: Horiz white space. 554, 555
LWR@blocktextcurrentfont: Added print version. 567
v0.63
\LWR@HTMLLatexCmd: ujarticle and related: Compile options. 248
\LWR@LwarpStart: Fixes for xeCJK. . 372
\LWR@atbeginverbatim: Fix for xeCJK. 389
\LWR@checkloadbefore: Added. . . . 192
\LWR@checkloadfilename: Added to reduce number of lwarp-* files. 223
\LWR@checkloadnever: Added. 192
\LWR@compileuplatex: Added. 244
\LWR@createautosec: Fix for xeCJK. 360
\LWR@earlyclassloadnever: Added. 193
\LWR@filestart: Fix: Break ligature for luatexko. 371
\LWR@firstoffour: Added. 207
\LWR@htmlclosecomment: Fix: Break ligature for luatexko. 326
\LWR@isolate: Fix for xeCJK. 206
\LWR@notltjloadafter: Added more classes. 191
Added. 191
\LWR@subhtmlelementclass: Fix for xeCJK. 327
\LinkHome: Fix: Print version. . . . 319
\linkhomename: Added. 318
General: 2018/12/03 1
lwarp.css: Added css for vertical writing. 249
lwarp.css: Improved css for mdframed. 249
amsthm, mdframed: Fix for enforced load order. 600
emumitem: v3.6: Nullifiy \DrawEnumitemLabel. 687
everyhook: Fix for bxjs* classes. . 220
geometry: Fix for bxjs* classes. . . 219
mdframed: Avoid thin rules. . . . 809
mdframed: Improved font control. 812–814
stfloats: Adapted to ltj* classes. . 922
xpinyin: Added. 1007
zhlineskip: Added. 1012
Added pTEXsupport. 190
Docs: \linkhomename. 105
Docs: \sidetocname. 107
Fix: Default \LWR@mdfive. 203
Improved titles. 811, 812
pTEX: Encoding. 203
pTEX: Load upquote. 205
pTEX: No newunicodechar. 204
LWR@BlockClassWP: Fix for xeCJK. . . 330
v0.64
\LWR@HTMLLatexCmd: utarticle and related: Added. 248
\LWR@checkloadfilename: Prevented bitfield, doublespace, newthm, rplain, si. 223
\LWR@section: Support for ujarticle and related. 364
\enskip: Made robust. 570
\qquad: Made robust. 570
\quad: Made robust. 570
\theHTMLTitleSeparator: Added utarticle and related. 369
General: 2018/12/08 1
addlines: Updated to v0.3. 592
biblatex: Added patch for CTEX. . 623
bsheaders: Added. 632
gmeometric: Added. 738
marginal: Added. 804

rmpage: Added. 891
scrlayer-scrpage: Fixes. 900
scrlayer: Fixes. 899
scrpage2: Added. 901
ujarticle and related: Improved \today. 580
Added utarticle and related. 580
v0.65
\LWR@LwarpEnd: Improved CSS for page layout. 376
\LWR@LwarpStart: Improved CSS for page layout. 374
\LWR@PreloadedPackage: \AtBeginDocument to avoid option clashes. 533
\LWR@hyperindexrefnullified: Added \textsi. 489
\LWR@includegraphicsb: graphics: Added \includegraphics alt key. 744, 747
\LWR@newhtmlfile: Error if duplicate file name. 355
Improved CSS for page layout. 354, 357
\LWR@nullfonts: Added \sishape. . 560
Added \textsi. 560
\LWR@restoreorigformatting: Fix: tabular*. 493
\enskip: Changed to Unicode EN SPACE. 570
\quad: Changed to Unicode EM SPACE. 570
\sishape: Added \sishape. 565
\textsi: Added. 558
General: 2018/12/22 1
lwarp.css: Added \sishape, \textsi. 249
lwarp.css: Improved CSS for page layout. 249
lwarp.css: Improved CSS for quotations. 249
lwarp.css: SideTOCto left for improved \marginpars. 249
lwarp_formal.css: SideTOCto left for improved \marginpars. . . . 283
lwarp_sagebrush.css: SideTOCto left for improved \marginpars. . 279
bounddvi: Added. 629
embrac: Added. 684
footnoterange: Added. 729
gentombow: Added. 734
geometry: Fix for bxjs* classes. . . 219
graphics: Added \includegraphics alt key. 537, 739, 741, 743
lltjext: Added. 790
multicolrule: Added. 829
multicol: Added \docolaction. . 829
plarydshln: Added. 878
plextarydshln: Added. 880
plextcolortbl: Added. 880
plext: Added. 879
pxatbegshi: Added. 884
pxeveryshi: Added. 884
pxftnright: Added. 884
pxjahyper: Added. 884
tascmac: Added. 933
versonotes: Added. 983
Added early checks for jarticle, tarticle, and related. 193
Fix for \rensuji. 580
Fix space between class and id. . 330
tabular: Added support for plext. . 456
Fix: tabular*. 456
Fix: Rule color. 458
minipage: Refactored to later allow Japanese <t/y> argument. 546
LWR@figcaption: Uses <figurecaption> instead of <figcaption>. 477
v0.66
\@mpfootnotetext: Improved HTML formatting. 345
\IgnoreMinipageWidths: Added, . . 546
\LWR@@footnotetext: Improved HTML formatting. 344
\LWR@LwarpStart: Fix: TOC, LOF, LOT links. 375
\LWR@checkloadfilename: Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 223
\LWR@closeparagraph: Fix: Combined span, tabular, and lateximage. 335
Improved HTML formatting. 334
\LWR@closeparagraph@br: Factored. 333
\LWR@fboxstyle: Use current text color. 552
\LWR@filenamenoblanks: Fix: Section names detokenized. 350
Fix: Section names with macros. 351
Fix: Section names with percent. 351
Improved file name generation. . 350
Limits filename length. 352
\LWR@findcurrenttextcolor: Fix: Color if xcolor not loaded. 567
\LWR@htmlfileref: No longer use zref. 464
\LWR@htmlsectionfilename: Sanitize underscores. 317
\LWR@includegraphicsb: Improved HTML formatting. 743
\LWR@indentHTML: Added. 324

\LWR@lateximagedepthref: No longer use zref. 464
\LWR@lateximagenumberref: No longer use zref. 464
\LWR@lwarplabel: No longer use zref. 464
\LWR@nameref: No longer use zref. . 464
\LWR@nullfonts: Logos. 562
\LWR@openparagraph: Improved HTML formatting. 333
\LWR@section: Fix: TOC, LOF, LOT links. 366
Improved HTML formatting. 366
\LWR@setexparray: Fix with \par. . 313
\LWR@setref: No longer use zref. . . 463
\LWR@simplifyname: Added. 349
\LWR@startref: No longer use zref. 466
\LWR@stoppars: Improved HTML formatting. 337
\LWR@subhtmlelementclass: Improved HTML formatting. . . . 327
\LWR@subhyperrefclass: Improved HTML formatting. 469
\LWR@subinlineimage: Improved HTML formatting. 471
\LWR@writeconf: Added ImagesDirectory and ImagesName. 248
\LinkHome: Fix: Document cross-references. 319
\UseMinipageWidths: Added, ... 546
\fbox: Fix: Removed extra space. . . 552
\hyperindexref: Fix: Long index entries. 490
\minipagefullwidth: Made \global. 546
\rotatebox: Improved HTML formatting. 749
\rule: Improved HTML formatting. . 574
\scalebox: Improved HTML formatting. 750
\textgreater: Made robust. 316
\textless: Made robust. 316
General: 2019/02/08 1
LWR@currentautosec: Fix for LOF, LOTfloat in home page. 361
lwarp.css: Added niceframe. . . . 249
lwarp.css: Improved CSS for definition lists. 249
lwarp_formal.css: Improved CSS for table notes. 283
lwarp_one_limage.txt: Image directory and prefix. 289
acronym: Fix for acronym in caption. 590
acronym: No longer uses zref. . . 590
ar: Added. 606
caption: Fix for options clash. . . 228
ed: Added. 683
extramarks: Updated to v3.10. . . 695
fancyhdr: Updated to v3.10. 701
fancyvrb: Improved HTML formatting. 698
kotexutf: Patch for references. . . 582
memoir: Docs re: version numbers. 159
multicolrule: Updated for v1.2. . . 829
nameauth: Added. 837
register: Verified for v1.9. 888
subcaption: Added. 924
tocbasic: Updated to v3.26a. . . . 959
truncate: Added. 975
zref: No longer used. 222
lwarpmk: Added ImagesDirectory and ImagesName. 292
lwarpmk: Fix for **cleanlimages**. . 292
Added early checks for colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 193
Added option ImagesDirectory. 211
Added option ImagesName. 212
Added support for indentfirst. . . 338
Docs: Updated Converting an existing document. 95
Fix: Minipages inside multicols. 829
Improved HTML formatting. 704
Package dates added where possible. 583
Sanitize filenames. 215
tabular: Fix: Minipages inside tabular. 459
lateximage: Added \BaseJobname for multiple projects. 526
Improved HTML formatting. 527
minipage: Honor \LWR@forceminipagefullwidth. 548
v0.67
\FilenameNullify: Added. . . . 563, 567
\FilenameSimplify: Added. . . 349, 354
\LWR@doequation: xfakebold: Added support. 513
\LWR@doubledollar: xfakebold: Added support. 506
\LWR@filenamenoblanks: Improved file name generation. 350
\LWR@lookforpackagename: easyReview: Supported. 224
\LWR@nullfonts: Add'l symbols. . . 560
\LWR@simplifycustom: Added. 349
\LWR@subsingledollar: xfakebold: Added support. 501, 504, 505
General: 2019/02/23 1

academicons: Added. 586
bbding: Added. 618
changes: Added. 639
color: Fix for version number. . . 670
dingbat: Added. 679
eurosym: Added. 694
fitbox: Added. 710
fontawesome5: Added. 725
fontawesome: Added. 724
foreign: Added. 729
gloss: Added. 736
karnaugh-map: Added. 770
marvosym: Added. 805
multicap: Added. 828
nomencl: Added. 851
notes: Added. 852
pifont: Added. 878
struktex: Added. 923
textcomp: Nullify in filenames. . 938
typicons: Added. 976
umoline: Added. 978
xfakebold: Added support. 498
xfakebold: Added. 1002
xunicode: Nullify in filenames. . 1010
AMS environments: Added xfakebold support. 598
eqnarray: xfakebold: Added support. 518, 519
v0.68
\LWR@@footnotetext: Factored for multiple foot boxes. 343
\LWR@checkloadfilename: Prevented alg, algorithmic, fncylab, pdfcprot. 223
\LWR@printpendingfootnotes: Factored for multiple footnote boxes. 346
\LWR@tabular@warpprintonly: Added. 455
General: 2019/03/05 1
bigfoot: Added. 624
fnpara: Added. 723
footnotebackref: Added. 728
hyperref: Fix for options with braces. 756
layouts: Added. 779
listings: Fix for listings v1.7. . . . 790
longtable: Improved error handling. 793
manyfoot: Added. 802
niceframe: Added. 851
perpage: Added. 876
showtags: Added. 907
tablefootnote: Added. 931
threeparttablex: Added. 945
threeparttable: Fix for caption type. 944
lwarpmk: Improved error handling if incomplete compile. 292
Prevented alg, algorithmic, fncylab, pdfcprot. 193
tabular: Fix: \warpprintonly inside tabular. 458
v0.69
\LWR@maybetocdata: Added support for tocdata. 484
\framebox: Fix: Handle paren arg. . 551
\hypertoc: Added support for tocdata. 485
\hypertocfloat: Added support for tocdata. 486
\makebox: Fix: Handle paren arg. . . 551
\multicolumnrow: multirow: Error if \multirow without \mrowcell. . 833
General: 2019/03/21 1
array: Fix for \tabularnewline. 607, 794
ctable: Added. 673
eqlist: Added. 691
eqparbox: Added. 691
ftcap: Added. 733
graphics: Warning if using scale option. 741
keyfloat: Updated for v2.00. . . . 773
listliketab: Added. 790
minitoc: Added. 824
multirow: Error if \multirow without \mrowcell. 832
rotfloat: Requires graphicx. . . . 892
supertabular: Fix: Clear caption after use. 930
tabularx: Require array. 932
tabulary: Require array. 932
tocdata: Added. 961
topcapt: Added. 972
xtab: Fix: Clear caption after use. 1009
tabular: Error if \multirow without \mrowcell. 457, 459, 460
lateximage: Fix for *pdftotext* errors from font size change. 530
fminipage: Honors \minipagefullwidth. 554
v0.70
\LWR@closeparagraph: Reduced underfull \hbox warnings. 334
\LWR@lookforpackagename: changes: Updated to v3.1.2. 224
\LWR@mathjaxfilename: Added. . . . 339
\LWR@restoreorigformatting: Fix: \& in a lateximage. 492

\MathJaxFilename: Added. 339
\enddocument: If labels changed, require recompile before making limages. 376
\framebox: Fix: Accept long arg. . . 551
\makebox: Fix: Accept long arg. . . . 551
Fix: Ignore width of 0pt. 551
Fix: No width given. 551
General: 2019/04/03 1
autonum: Added. 615
caption: Fix: Extra par tags. . . . 635
changelayout: Added. 638
changes: Updated to v3.1.2. . . . 639
inputtrc: Added. 769
mathtools: Added. 806
metalogox: Added. 819
metalogo: Used in print mode. . 818
textcomp: Fix for \textinterrobang. 935
textpos: Added optional arg to textblock. 939
xunicode: Fix for \textinterrobang. 1010
AMS environments: Refactored. . 598
Ensure vector font. 204
File: lwarp_mathjax.txt: Loads autoload-all.js extension. . . . 290
File: lwarp_mathjax.txt: Updated to MathJax v2.7.5. 290
Logos: Improved for metalogox, lateximages. 576
LWR@nestspan: Improved minipage, \parbox inside a span. 324
v0.71
\@mpfootnotetext: Improved HTML formatting. 345
Reduced underfull \hbox warnings. 345
\LWR@closeparagraph: Flush left captions. 334
\LWR@closetabledatacell: Fix: Tabular par tags. 406
\LWR@stoppars: Reduced underfull \hbox warnings. 337
\expandcolspec: Added support for tabular '*' column. 417
General: 2019/04/29 1
chemfig: Updated for v1.4. 642
endfloat: Updated for v2.7. . . . 685
lwarp-common-multimedia: Added. 1041
media9: Added. 816
movie15: Added. 827
multimedia: Added. 830
textpos: Updated for v1.9.1. . . . 939
lwarpmk: If wrong lwarpmk.conf version, or wrong OS, displays the print command to recompile. . . 292
Docs: Error testing. 179
Fix: blockquotation tag. 387
Reduced underfull \hbox warnings. 636
v0.72
\LWR@newautopagelabel: Fix: References for xr, xr-hyper. . . . 353
\LWR@printmccoldata: Fix: \multicolumn parameters. . . . 440
\LWR@restoreorigformatting: Use \LWR@formatted for \bfseries, etc. 492
\chapter: Added support for hypbmsec. 368
\ebweight: nfssext-cfr: Added. . . 564
\hypertoc: Fix: References for xr, xr-hyper. 485
\hypertocfloat: Fix: References for xr, xr-hyper. 486
\lgweight: nfssext-cfr: Added. . . 564
\paragraph: Added support for hypbmsec. 368
\part: Added support for hypbmsec. 367
\section: Added support for hypbmsec. 368
\subparagraph: Added support for hypbmsec. 368
\subsection: Added support for hypbmsec. 368
\subsubsection: Added support for hypbmsec. 368
\texteb: nfssext-cfr: Added. 556
\textlg: nfssext-cfr: Added. 556
\textulc: fontaxes: Added. 558
\ulcshape: fontaxes: Added. 565
General: 2019/06/08 1
lwarp.css: Added backnaur. . . . 249
lwarp.css: Removed unneeded support for \sishape, \textsi. . 249
backnaur: Added. 617
boxedminipage2e: Added support for lateximages. 629
changes: Fix references for xr, xr-hyper. 639
fontaxes: Added. 563, 726
gloss: Fix references for xr, xr-hyper. 736
hypbmsec: Added. 755
minibox: Added. 823
nfssext-cfr: Added. 841
nomencl: Fix references for xr, xr-hyper. 851
pdfcrypt: Added. 871

shapepar: Added. 906
slantsc: Added. 915
soulutf8: Fix: Loads soul. 918
tabfigures: Added. 931
xr-hyper: Added. 1008
xr: Added. 1007
zhlineskip: Updated to v1.0e. . . 1012
Use \LWR@formatted for \bfseries, etc. 239, 564
v0.73
\@include: Fix: \newpage instead of \clearpage. 229
\HTMLTitle: Added default title if none specified. 340
\LWR@LwarpEnd: Fix: Empty header/footer. 376
\LWR@LwarpStart: Fix: Empty header/footer. 374
\LWR@addbaselinemarker: Improved warning messages. 499
\LWR@descitem: Fix: HTML tags. . . . 397
\LWR@forceemptyline: Added. 206
\LWR@gsavebox: Added global save boxes. 207
\LWR@htmlelementclass: Vertical space. 328
\LWR@htmlelementclassline: Vertical space. 328
\LWR@indentHTMLtwo: Added. 324
\LWR@indexitem: Fix: Avoid empty 488
\LWR@indexsubitem: Fix: Avoid empty 488
\LWR@indexsubsubitem: Fix: Avoid empty 488
\LWR@newhtmlfile: Fix: Empty header/footer. 355, 357
\LWR@nullfonts: Fix: \hspace in sectioning file name. 562
\LWR@titlingmaketitle: titling: Fix: Paragraph tags. 384, 958
Fix: Paragraph tags. 385
\attribution: Fix: Paragraph tags. . 387
\color: Added HTML support. 995
\fboxBlock: Fix: Paragraph tags. . . 553
\hspace: Fix: Avoid empty . . 571
\l@book: Added \book for memoir. . 486
\maketitle: titling: Fix: Paragraph tags. 957
Fix: Paragraph tags. 383
\marginparBlock: Fix: Paragraph tags. 347
\postbookname: Added \book for memoir. 367
\rule: Fix: Avoid empty . . . 575
General: 2019/07/11 1
lwarp.css: Added \book for memoir. 249
lwarp.css: Improved pkgtocdata formatting. 249
lwarp_formal.css: Added \book for memoir. 279, 283
boxedminipage2e: Fix: Paragraph tags. 629
caption: Fix for starred captions. 635
epigraph: Fix: Paragraph tags. . . 688
fancyvrb: Fix: Nested /<pre>. 705, 708
fancyvrb: Btrivlist: Fixed paragraph tags. 699
intopdf: Updated to v0.2.1. 769
listings: Fix: Paragraph tags. 789
lwarp-common-multimedia: Fix: No size for audio file. . . . 1042, 1043
lwarp-common-multimedia: Fix: Paragraph tags. 1045
lwarp-patch-komascript: Fix for captions. 1015
lwarp-patch-memoir: Added \book. 1021
lwarp-patch-memoir: Fix for \frontmatter* and \mainmatter*. 1022
lyluatex: Added. 799
musicography: Updated to 2019/05/28. Now supports lateximages. 834
quotchap: Fix: Paragraph tags. . . 885
quotchap: Updated to v1.2. 885
quoting: Fix: Paragraph tags. . . . 886
scrextend: Fix: Paragraph tags. 896, 897
stackengine: Added. 921
threeparttable: Added measuredfigure. 945
tocdata: Honors \tocdataformat. 961
tocdata: Improved formatting. . . 961
tocdata: Updated to v2.03. 961
versonotes: Updated to v0.4. . . . 983
vwcol: Fix: Paragraph tags. 986
xy: Fix for \xybox. 1011
xy: Improved xy, reverted \xymatrix, for qcicuit. 1011
Added \book for memoir. . . 310, 322
AMS environments: Fix: alt tags. 598
AMS environments: Fix: Paragraph tags. 598, 599
Fix: Paragraph tags. 380
Numbered HTML entity used for text dollar. 499

tabular: Fix and warning for tabular inside a 456
LWR@blocktextcurrentfont: Fix: Paragraph tags. 563
LWR@nestspan: Fix: quote, quotation inside a span. 324
v0.74
\@ensuredmath: Add \ThisAltText. 508
\AltTextClose: Added. 497
\AltTextOpen: Added. 497
\ImageAltText: Added. 497
\LWR@ThisAltText: Add \ThisAltText. 497
\LWR@addlinktitle: Added. 466
\LWR@doequation: Add \ThisAltText. 513
\LWR@doubledollar: Add \ThisAltText. 507
\LWR@includegraphicsb: Add \ThisAltText. 744, 747
\LWR@lateximage@oneimage: Factored from lateximage. 525
\LWR@lateximage@oneimageb: Factored from lateximage. . . . 525
\LWR@setcurrentfont: Factored. . . 498
\LWR@singledollar: Add \ThisAltText. 507
\LWR@subinlineimage: Add \ThisAltText. 471
\LWR@subsingledollar: Add \ThisAltText. 505
Adds star argument for lateximage. 504
Fix: Font control. 502
\LateximageFontScale: Adjusted SVG math font scaling default to 1. . . 521
\MathImageAltText: Renamed from \mathimage. 497
\PackageDiagramAltText: Renamed from \packagediagramname. . . . 498
\ThisAltText: Add \ThisAltText. . 497
\hspace: Ignore negative space. . . . 571
General: 2019/09/02 1
lwarp.css: Added lyluatex. . . . 249
forest: alt text. 730
geometry: Remembers user's geometry. 735
lyluatex: Adapts to user's geometry. 800
lyluatex: Preserves left margin. . . 800
lyluatex: Renamef \lyluateximagename. 799
lyluatex: Split system images, assign class. 799
mhchem: Modified for new lateximage. 820
pdfpages: Adjust to user's paper size. 873
stackengine: alt tags. 921
struktex: alt text. 923
tikz: Added alt text. 947
lwarpmk: **lwarpmk clean** removes add'l files. 292
lwarpmk: **lwarpmk epstopdf** and **pdftosvg** honor directories. . . . 292
Add \ThisAltText. 599, 741
Remembers user's geometry. . . . 218
lateximage: Add \ThisAltText. . . 531
Added second starred argument. 526, 531
Improved alt text. 528
New syntax for \LWR@subinlineimage. 530
eqnarray: Add \ThisAltText. 519
LWR@displaymathother: Uses \MathImageAltText. 509
LWR@equationother: Uses \MathImageAltText. 509
v0.75
\normalcolor: Added for HTML. . . . 993
General: 2019/09/23 1
lwarp.css: Improved marginblock. 249
keyfloat: Fix: \normalcolor. . 773, 774
wrapfig: Fix for \linewidth. 989
wrapfig: Fix for width. 989
minipage: Fix: \linewidth. 548
v0.76
General: 2019/10/08 1
lwarp.css: Fix for small caps. . . 249
acro: Updated for v2.10. 588
xr-hyper: Updated for v6.1. . . . 1008
xr: Updated for v5.05 and xr-hyper v6.1. 1007
Docs expanded: Multiple projects. 92
File: lwarp_mathjax.txt: Updated to MathJax v2.7.6. 290

Index of Objects

This is an index of macros, environments, booleans, counters, lengths, packages, classes, options, keys, files, and various other programming objects. Each is listed by itself, and also by category. In some cases, they are further subdivided by [class].

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

Symbols

\$ *499*
\& *316*, 7402
\(. 9946
*-images.txt (file) *526*
*_html.aux (file) *353*, *461*, *463*, *526*
*_html.lof (file) *476*
*_html.lot (file) *476*
*_html.tex (file) *242*
\, ... *118*
--shell-escape (option) *97*
\@@@setcpageref 10759
\@@@setcref 10722
\@@@setcrefrange 10736
\@author *378*
\@begintheorem 7057
\@biblabel 9591
\@captype 9191
\@chapcntformat 6272
\@currentHref 9024
\@currentlabelname 8875
\@date *378*
\@dlbfloat 9157
\@donoparitem 7083
\@endtheorem 7069
\@ensuredmath 9956
\@float 9157
\@fnsymbol 6843
\@footnotetext 5842
\@include 1215
\@item 7096
\@makecaption 9212
\@makefnmark 5809
\@makefntext 5808
\@maketitle 56, 6866
\@mklab 7077
\@mpfootnotetext 5844
\@nbitem 7163
\@opargbegintheorem 7063
\@partcntformat 6273
\@partnameformat 6274
\@rowc@lors 7761
\@rowcolors 7760
\@seccntformat 6270
\@starttoc 9324
\@textsubscript 11523
\@textsuperscript 11519
\@title *378*
\@wrglossary 9532
\@wrindex 9521
\[. 9946
\\ *569*
$ *506*
$$ *506*
2in1 (package) *583*
2up (package) *583*

A

a4 (package) *583*
a4wide (package) *584*
a5comb (package) *584*
abstract (environment) 6931
abstract (package) *128*, *584*
\abstractname *108*, 6930
academicons (package) *586*
accsupp (package) *587*
acro (package) *587*
acronym (package) *590*
\addcontentsline 9275
addlines (package) *592*
\AddSubtitlePublished 6896
adjmulticol (package) *591*
Adobe (program) *71*
\affiliation 6746
afterpage (package) *592*
algorithm2e (package) *592*
algorithmicx (package) *157*, *596*
align (environment) 67
align* (environment) 70
alignat (environment) 79
alignat* (environment) 82
alltt (package) *597*
\AltTextClose *110*, 9659

\AltTextOpen 110, 9658
\AmS 11852
amsmath (package) 597
amsthm (package) 600
\and 378
anonchap (package) 604
anysize (package) 605
appendix (package) 128, 605
ar (package) 606
arabicfront (package) 607
array (package) 607
\arrayrulecolor 7768
\arrayrulecolornexttoken 7768
arydshln (package) 608
AsciiDoc (program) 71
AsciiDoctor (program) 71
Asciidoctor-LaTeX (program) 71
asymptote (package) 151, 610
atbegshi (package) 611
attachfile (package) 611
attachfile2 (package) 612
\attrib 160, 388, 982
\attribution 6941
authblk (package) 128, 614
\author 115, 378
autonum (package) 615
autosec 360
axessibility (package) 616
axodraw2 (package) 616

B

babel (package) 161
\backmatter 6248
backnaur (package) 617
backref (package) 617
balance (package) 617
\BaseJobname 5124
BaseJobname (option) 104, 211
bbding (package) 618
\bfseries 11482
biblatex (package) 623
\bibliography 9582
\BibTeX 11845
bibunits (package) 623
bigdelim (package) 157, 623
bigfoot (package) 624
bigstrut (package) 625
bitpattern (package) 625
BlockClass (environment) 5507
\BlockClassSingle 5520
blowup (package) 626
booklet (package) 626
bookmark (package) 627
booktabs (package) 627
boolean:
CombineHigherDepths 107, 349
FileSectionNames 108, 317
FormatEPUB 167, 236
FormatWP 169, 236
HTMLDebugComments 108, 231
LWR@allowanothergeometry 219
LWR@amsmultline 516
LWR@copiedsidetoc 481
LWR@doingapar 332
LWR@doingcmidrule 403
LWR@doingstartpars 332
LWR@doingtbrule 403
LWR@dynamicmath 315
LWR@emptyatbang 403
LWR@exitingtabular 451
LWR@forceminipagefullwidth 546
LWR@foundmrowcell 403
LWR@freezethisautoid 475
LWR@indisplaymathimage 498
LWR@infloatrow 742
LWR@intabularmetadata 403
LWR@isstartingequation 524
LWR@mathmacro 314
LWR@minipagefullwidth 545
LWR@minipagethispar 546
LWR@opttablecol 418
LWR@origmathjax 210
LWR@skipatbang 403
LWR@skippingmcolrowcell 403
LWR@skippingmrowcell 403
LWR@starredlongtable 444
LWR@startedrow 402
LWR@tableparcell 403
LWR@tabularcelladded 402
LWR@tabularmutemods 451
LWR@tracinglwarp 230
LWR@usedmultirow 403
LWR@validtablecol 418
LWR@verbtags 389
LWR@xfakebold 498
mathjax 210
usingOSWindows 209
warpingHTML 210
warpingprint 210
WPMarkFloats 170, 236
WPMarkLOFT 171, 237
WPMarkMath 171, 237
WPMarkMinipages 171, 236
WPMarkTOC 171, 236
WPTitleHeading 172, 237
bophook (package) 628
bounddvi (package) 629
boxedminipage2e (package) 629
\boxframe 194
breakurl (package) 629
breqn (package) 630

bsheaders (package) 632
BVerbatim (environment) 247
bxpapersize (package) 632
bytefield (package) 632

C

calc (package) 220
cancel (package) 632
canoniclayout (package) 633
capt-of (package) 479
caption (package) 157, 228, 479, 634
\caption@begin 9256
\caption@end 9256
\captionlistentry 9260
\captionof 9291
\CaptionSeparator 9211
cases (package) 637
center (environment) 10511
\centering 10535
\centerline 10554
changebar (package) 637
changelayout (package) 638
changepage (package) 639
changes (package) 639
chappg (package) 642
\chapter 6475
chapterbib (package) 642
chemfig (package) 642
chemformula (package) 644
chemgreek (package) 649
chemmacros (package) 649
chemnum (package) 667
chkfloat (package) 668
chngpage (package) 668
cite (package) 668
CJK (package) 669
CJKutf8 (package) 669
class (key) [Gin] 743
class:
  internet 70
  komascript 159
  memoir 159, 160, 983
\cleardoublepage 11684
\clearpage 11684
cleveref (package) 125, 541
clrdblpg (package) 669
cm-super (package) 98
cmap (package) 99
cmdtrack (package) 670
\color 51
color (package) 149, 670
\colorbox 77
\colorboxBlock 90, 10619
colortbl (package) 156, 670
CombineHigherDepths (boolean) . . 107, 349
comment (package) 216
\ConTeXt 11840
continue (package) 672
copyrightbox (package) 672
counter:
  FileDepth 107, 348
  FootnoteDepth 108, 342
  footnoteReset 342
  lofdepth 485
  lotdepth 485
  LWR@cellcolordepth 437
  LWR@currentautosec 361
  LWR@externalfilecnt 498
  LWR@hdashedlines 402
  LWR@hlines 402
  LWR@htmlfilenumber 317
  LWR@latestautopage 477
  LWR@lateximagedepth 521
  LWR@lateximagenumber 521
  LWR@LIpage 521
  LWR@midrulecounter 428
  LWR@minipagedepth 545
  LWR@nextautoid 476
  LWR@nextautopage 476
  LWR@nextequation 509
  LWR@prevFileDepth 360
  LWR@previousautopagelabel 352
  LWR@spandepth 332
  LWR@splitstarcopies 416
  LWR@splitstarindex 416
  LWR@starcount 416
  LWR@startingequation 523
  LWR@tablecolspecindex 404
  LWR@tablecolspecwidth 404
  LWR@tableLaTeXcolindex 404
  LWR@tabletotalLaTeXcols 405
  LWR@tabletotalLaTeXcolsnext . . . 405
  LWR@tabularDepth 404
  LWR@tabularpardepth 404
  LWR@thisautoid 474
  LWR@thisautoidWP 475
  SideTOCDepth 107, 483
  tocdepth 107
\cpagerefFor 10758
crop (package) 673
\CSSFilename 108, 112, 5751
ctable (package) 673
\CustomizeMathJax 6088, 6113
cuted (package) 676
cutwin (package) 676

D

\date 115
dblfloatfix (package) 677
dblfnote (package) 677
dcolumn (package) 677
\DeclareGraphicsExtensions 2

dejavu (package) *98*
description (environment) 7244
diagbox (package) *678*
dingbat (package) *679*
\displaymathnormal . *146*, *496*, *514*, 10141
\displaymathother . . *146*, *497*, *514*, 10152
ditaa (package) *166*
\dotfill 11602
\doublerulesepcolor 7770
\doublerulesepcolornexttoken 7770
dprogress (package) *680*
draftcopy (package) *680*
draftfigure (package) *681*
draftwatermark (package) *681*
dvipdfm (option) *100*, *214*
dvipdfmx (option) *100*, *214*
dvips (option) *100*, *214*

E

easy-todo (package) *682*
ebook (package) *683*
\ebweight 11484
ed (package) *683*
ellipsis (package) *684*
embrac (package) *684*
\emph 11131
emptypage (package) *685*
\end@dlbfloat 9174
\end@float 9174
\enddocument 6711
endfloat (package) *685*
endheads (package) *686*
endnotes (package) *128*, *686*
\enlargethispage 11683
\enskip *570*, 11628
enumerate (environment) 7219
enumerate (package) *687*
enumitem (package) *687*
environ (package) *222*
environment:
  fminipage *120*
  lateximage *520*
  picture *544*
  titlepage *115*
  titlingpage *115*
  warpall *114*
  warpHTML *111*, *113*
  warpprint *110*, *114*
environments:
  abstract 6931
  align 67
  align* 70
  alignat 79
  alignat* 82
  BlockClass 5507
  BVerbatim 247
  center 10511
  description 7244
  enumerate 7219
  eqnarray 10201
  equation 10119
  equation* 10127
  fcolorminipage 170, 10660
  flalign 73
  flalign* 76
  flushleft 10527
  flushright 10519
  fminipage 11063
  gather 61
  gather* 64
  itemize 7213
  lateximage 10376, 10506
  list 7183
  longtable 4
  LWR@BlockClassWP 5546
  LWR@blocktextcurrentfont 11471, 11551
  LWR@displaymathnormal 9987
  LWR@displaymathother 9992
  LWR@equationother 10006
  LWR@figcaption 9226
  LWR@glrbox 718
  LWR@nestspan 5354
  math 9986
  minipage 10843
  multline 54
  multline* 57
  picture 10818
  quotation 6965
  quote 6959
  tabbing 7042
  tabular 8715
  thebibliography 9592
  theindex 9497
  titlepage 6763
  titlingpage 14
  verbatim 7032
  verse 2, 6973
  warpall 908
  warpHTML 909
  warpprint 909
epigraph (package) *688*
epsfig (package) *689*
epstopdf (package) *150*, *690*
epstopdf (program) *148*, *536*
epstopdf-base (package) *690*
eqlist (package) *691*
eqnarray (environment) 10201
eqparbox (package) *691*
equation (environment) 10119
equation* (environment) 10127
errata (package) *692*

eso-pic (package) 694
\etalchar 129
etoolbox (package) 190
eurosym (package) 694
everyhook (package) 220
everypage (package) 695
everyshi (package) 695
\expandcolspec 7644
expl3 (package) 220
extramarks (package) 695

F

fancybox (package) 122, 696
fancyhdr (package) 701
fancyref (package) 702
fancytabs (package) 703
fancyvrb (package) 703
\fbox 120, 11034
\fboxBlock 120, 11043
\fcolorbox 107, 10621
\fcolorboxBlock 130, 10658
fcolorminipage (environment) . 170, 10660
figcaps (package) 709
figsize (package) 710
file:
*-images.txt 526
*_html.aux 353, 461, 463, 526
*_html.lof 476
*_html.lot 476
*_html.tex 242
glyphtounicode.tex 98
lwarp.css 112, 249
lwarp.ist 140, 287
lwarp.xdy 141, 288
lwarp_baseline_marker.eps 499
lwarp_baseline_marker.png 499
lwarp_formal.css 283
lwarp_mathjax.txt 289
lwarp_one_limage.cmd 289
lwarp_sagebrush.css 278
lwarp_tutorial.txt 80
lwarpmk.conf 249
lwarpmk.lua 177
project.css 112
project.lwarpmkconf 249
sample_project.css 112, 287
tutorial.tex 80
filecontents (package) 221
FileDepth (counter) 107, 348
\FilenameLimit 108, 5954
\FilenameNullify 124, 11442, 11552
\FilenameSimplify 123, 5975, 6114
FileSectionNames (boolean) 108, 317
fitbox (package) 710
fix2col (package) 711
fixme (package) 162, 711
fixmetodonotes (package) 712
flafter (package) 713
\flagverse 983
flalign (environment) 73
flalign* (environment) 76
Flare (program) 71
flippdf (package) 713
float (package) 157, 713
floatflt (package) 715
floatpag (package) 716
floatrow (package) 158, 716
fltrace (package) 721
\flushbottom 5265
flushend (package) 721
flushleft (environment) 10527
flushright (environment) 10519
fminipage (environment) 120, 11063
fnbreak (package) 722
fncychap (package) 722
fnlineno (package) 723
fnpara (package) 723
fnpos (package) 723
fontawesome (package) 723
fontawesome5 (package) 725
fontaxes (package) 726
fontenc (package) 98, 726
fontspec (package) 98
footmisc (package) 727
footnote (package) 728
footnotebackref (package) 728
FootnoteDepth (counter) 108, 342
footnotehyper (package) 729
footnoterange (package) 729
footnoteReset (counter) 342
footnpag (package) 729
\ForceHTMLPage 127, 6223
\ForceHTMLTOC 127, 6229
foreign (package) 729
forest (package) 730
FormatEPUB (boolean) 167, 236
FormatWP (boolean) 169, 236
\framebox 11012
framed (package) 730
FrameMaker (program) 71
\frontmatter 6245
ftcap (package) 733
ftnright (package) 733
fullminipage (package) 733
fullpage (package) 733
fullwidth (package) 734
\fup 11527
\fussy 5267
fwlw (package) 734

G

gather (environment) 61

gather* (environment) 64
GELLMU (program) 70
gentombow (package) 734
geometry (package) 218, 735
gettitlestring (package) 220
[Gin]:
class (key) 743
GladTeX (program) 70
gloss (package) 129, 735
glossaries (package) 129, 736
GlossaryCmd (option) . . . 103, 129, 214, 736
glyphtounicode.tex (file) 98
gmeometric (package) 738
graphics (package) 147, 738
graphicx (package) 147, 751
grffile (package) 149, 751
grid (package) 751
grid-system (package) 752
gridset (package) 752

H

hang (package) 752
hanging (package) 754
Hevea (program) 70
\hfill 11598
\HomeHTMLFilename 5126
HomeHTMLFilename (option) . 100, 105, 213
\href 9054
\hrulefill 11600
\hskip 118
\hspace 118, 570, 11636, 11667, 11673
htlatex (program) 70
\HTMLAuthor 109, 116, 5788
HTMLDebugComments (boolean) 108, 231
\HTMLDescription 109, 115, 5793
\HTMLentity 5108
\HTMLFilename 5125
HTMLFilename (option) 100, 105, 213
\HTMLFirstPageTop 109, 5739
htmlglossary (option) [lwarpmk] . 129, 736
HTMLIndexCmd (option) 102, 213
\HTMLLanguage 108, 6508
HTMLLatexCmd (option) 100, 163, 213
\HTMLleftmargini (length) 160, 388, 389, 982
\HTMLPageBottom 109, 378, 5745
\HTMLPageTop 109, 5742
\HTMLTitle 108, 116, 5783
\HTMLTitleAfterSection 109, 6531
\HTMLTitleBeforeSection 109, 6526
\HTMLunicode 5116
\HTMLvleftskip (length) 160, 388, 389, 982
hypbmsec (package) 755
hypcap (package) 755
hypdestopt (package) 755
\hyperindexref 9560
hypernat (package) 755
hyperref (package) 125, 469, 756
\hypertoc 9431
\hypertocfloat 9454
hyperxmp (package) 761
hyphenat (package) 761

I

idxlayout (package) 762
\if@titlepage 6741
ifoddpage (package) 763
ifplatform (package) 190
\IgnoreMinipageWidths . . . 120, 545, 10833
\ImageAltText 109, 9660
ImagesDirectory (option) 100, 211
ImagesName (option) 100, 212
imakeidx (package) 763
\includegraphics 296
indentfirst (package) 338
InDesign (program) 71
index (package) 767
\InlineClass 5530
\inlinemathnormal 146, 496, 5101
\inlinemathother 146, 496, 5097
inputenc (package) 98
inputenx (package) 98
inputtrc (package) 769
internet (class) 70
intopdf (package) 769
itemize (environment) 7213
\itshape 11496

K

karnaugh-map (package) 770
\kern 118
key:
[Gin]:
class 743
keyfloat (package) 159, 773
komascript (class) 159
kotex (package) 162
kvoptions (package) 210

L

\l@book 9475
\l@chapter 9477
\l@figure 9488
\l@paragraph 9486
\l@part 9476
\l@section 9483
\l@subparagraph 9487
\l@subsection 9484
\l@subsubsection 9485
\l@table 9489
\LaTeX 11794
LaTeX2HTML (program) 70
\LaTeXe 11794

lateximage (environment) *520*, 10376, 10506
\LateximageFontScale 10274
\LateximageFontSizeName 10273
latexmk (option) *100*, *105*, *214*
latexmk (program) *164*
LatexmkIndexCmd (option) *103*, *213*
LaTeXML (program) *70*
layaureo (package) *779*
layout (package) *779*
layouts (package) *779*
leading (package) *782*
\leftline 10553
length:
\HTMLleftmargini . . *160*, *388*, *389*, *982*
\HTMLvleftskip *160*, *388*, *389*, *982*
\LWR@cmidrulewidth *429*
\LWR@heavyrulewidth *428*
\LWR@lightrulewidth *429*
\LWR@minipageheight *545*
\LWR@minipagewidth *545*
\LWR@tempheight *570*
\LWR@tempraise *570*
\LWR@tempwidth *570*
\LWR@thiscmidrulewidth *429*
\VerbatimHTMLWidth *389*
\vleftmargini *160*, *388*, *982*
\vleftskip *160*, *388*, *982*, *983*
letltxmacro (package) *190*
letterspace (package) *782*
lettrine (package) *782*
\lgweight 11486
LibreOffice (program) *71*
\linebreak 11677
lineno (package) *783*
\LinkHome 5184, 5189
\linkhomename *105*, 5181
Linux (program) *113*, *208*
lips (package) *786*
list (environment) 7183
listings (package) *786*
listliketab (package) *790*
\listof 9378
\listoffigures 9352
\listoftables 9365
lltjext (package) *790*
lmodern (package) *98*
lofdepth (counter) *485*
longtable (environment) 4
longtable (package) *155*, *791*
lotdepth (counter) *485*
lscape (package) *794*
ltablex (package) *794*
ltcaption (package) *795*
ltxgrid (package) *795*
ltxtable (package) *796*
lua-check-hyphen (package) *796*
lua-visual-debug (package) *796*
luacolor (package) *796*
\LuaLaTeX 11823
LuaLaTeX (program) [requirement] *74*
\LuaTeX 11823
luatodonotes (package) *161*, *797*
lwarp (package) *100*
lwarp-common-multimedia (package) . *1041*
lwarp-patch-komascript (package) . *1014*
lwarp-patch-memoir (package) *1016*
lwarp.css (file) *112*, *249*
lwarp.ist (file) *140*, *287*
lwarp.xdy (file) *141*, *288*
lwarp_baseline_marker.eps (file) *499*
lwarp_baseline_marker.png (file) *499*
lwarp_formal.css (file) *283*
lwarp_mathjax.txt (file) *289*
lwarp_one_limage.cmd (file) *289*
lwarp_sagebrush.css (file) *278*
lwarp_tutorial.txt (file) *80*
[lwarpmk]:
htmlglossary (option) *129*, *736*
printglossary (option) *129*, *736*
lwarpmk (option) *103*, *212*, *292*
lwarpmk (program) *177*, *292*
lwarpmk epstopdf (program) *148*, *536*
lwarpmk pdftosvg (program) *148*, *536*
lwarpmk.conf (file) *249*
lwarpmk.lua (file) *177*
\lwarpsetup 772
\LWR@@footnotetext 5812
\LWR@@makebox@align 10968
\LWR@@makebox@paren 10953
\LWR@@printpendingfootnotes 5878
\LWR@addbaselinemarker 9693
\LWR@addcdashline 8039
\LWR@addcmidruletrim 8005
\LWR@addcmidrulewidth 8036
\LWR@addcompilecmd 1591
\LWR@addformatwpalignment 8055
\LWR@addleftmostbartag 7840
\LWR@addlinktitle 8952
\LWR@addmathjax 10054
\LWR@addmulticolvertrulecolor . . . 8314
\LWR@addrulewidth 8010
\LWR@addtabularcellcolor 8183
\LWR@addtabularhrulecolor 8083
\LWR@addtabularrowcolor 8068
\LWR@addtabularrulecolors 8129
\LWR@afterendverbatim 7015
LWR@allowanothergeometry (boolean) . *219*
\LWR@amsmathbody 10339
\LWR@amsmathbodynumbered 10345
LWR@amsmultline (boolean) *516*

\LWR@applyxfakebold 9675
\LWR@atbeginverbatim 6996
\LWR@backgroundcolor 39
\LWR@beginhideamsmath 10186
LWR@BlockClassWP (environment) . . . 5546
LWR@blocktextcurrentfont (environment) 11471, 11551
\LWR@botnavigation 5207
LWR@cdashlines *428*
LWR@cellcolordepth (counter) *437*
\LWR@cellHTMLcolor 7765
\LWR@checkloadbefore 64
\LWR@checkloadfilename 1053
\LWR@checkloadnever 83
\LWR@clearmidrules 7920
\LWR@closeparagraph 5646
\LWR@closeparagraph@br 5636
\LWR@closeprevious 5234
\LWR@closetabledatacell 7358
\LWR@cmidrulewidth (length) *429*
LWR@colafterspec *405*
LWR@colatspec *405*
LWR@colbangspec *405*
LWR@colbarspec *405*
LWR@colbeforespec *405*
\LWR@columnHTMLcolor 7763
\LWR@columnspeclookahead 7480
\LWR@compilecmd 1588
\LWR@compileuplatex 1620
\LWR@convertto 677
LWR@copiedsidetoc (boolean) *481*
\LWR@copyfile 1250
\LWR@createautosec 6254
LWR@currentautosec (counter) *361*
\LWR@currentcss 5750
\LWR@currenttextcolor 11538
\LWR@customizedMathJax 6087
\LWR@customizeMathJax 6093
\LWR@descitem 7225
LWR@displaymathnormal (environment) 9987
LWR@displaymathother (environment) 9992
\LWR@docdashline 7969
\LWR@docmidrule 7953
\LWR@doequation 10067
\LWR@doindexentry 9540
LWR@doingapar (boolean) *332*
LWR@doingcmidrule (boolean) *403*
LWR@doingstartpars (boolean) *332*
LWR@doingtbrule (boolean) *403*
\LWR@domulticolumn 8352
\LWR@doubledollar 9897
LWR@dynamicmath (boolean) *315*
\LWR@earlyclassloadnever 104
\LWR@earlyloadnever 89
LWR@emptyatbang (boolean) *403*
\LWR@endfloatalignment 9207
\LWR@endhideamsmath 10194
\LWR@endofline 11609
\LWR@ensuredoingapar 5612
LWR@equationother (environment) . 10006
\LWR@equationtag 10325
LWR@exitingtabular (boolean) *451*
\LWR@expandableformatted 1312
\LWR@expandableformattedenv 1341
\LWR@expcolspec 7640
LWR@externalfilecnt (counter) *498*
\LWR@fboxstyle 11028
LWR@figcaption (environment) 9226
\LWR@filenamenoblanks 5986
\LWR@filestart 6540
\LWR@findcurrenttextcolor 11541
\LWR@findword 1050
\LWR@firstoffour 700
\LWR@floatalignment 9193
\LWR@floatalignmentname 9192
\LWR@floatbegin 9125
\LWR@floatend 9159
\LWR@floatstyle 2
\LWR@footnotebox 5807
\LWR@footnotetext 5841
\LWR@forceemptyline 696
LWR@forceminipagefullwidth (boolean) *546*
\LWR@forceminwidth 11017
\LWR@forcenewpage 5254
\LWR@formatted 1297
\LWR@formattedenv 1327
\LWR@formatting 1296
LWR@foundmrowcell (boolean) *403*
\LWR@fourthoffour 700
LWR@freezethisautoid (boolean) *475*
\LWR@futurenonspacelet 7303
\LWR@FVstyle 56
\LWR@getexparray 5070
\LWR@getmynexttoken 7310
LWR@glrbox (environment) 718
\LWR@gsavebox 704
LWR@hdashedlines (counter) *402*
\LWR@heavyrulewidth (length) *428*
\LWR@hidelatexequation 10040
LWR@hlines (counter) *402*
\LWR@HTML@caption@begin 9236
\LWR@HTML@caption@end 9247
\LWR@HTML@Gin@setfile 122
\LWR@HTML@ref 8995
\LWR@htmlblockcomment 5444
\LWR@htmlblocktag 5446
\LWR@HTMLcline 8696
\LWR@htmlclosecomment 5416
\LWR@htmlcomment 5437
\LWR@htmldivclass 5483

\LWR@htmldivclassend 5486
\LWR@htmlelement 5497
\LWR@htmlelementclass 5469
\LWR@htmlelementclassend 5475
\LWR@htmlelementclassline 5489
\LWR@htmlelementend 5500
LWR@htmlfilenumber (counter) *317*
\LWR@htmlfileref 8894
\LWR@HTMLhline 8679
\LWR@HTMLLatexCmd 1630
\LWR@htmlmathlabel 10171
\LWR@htmlmulticolumn 8401
\LWR@htmlopencomment 5416
\LWR@htmlrefsectionfilename 5171
\LWR@HTMLsanitize 10277
\LWR@HTMLsanitizeexpand 10294
\LWR@htmlsectionfilename 5136
\LWR@htmlspan 5393
\LWR@htmlspanclass 5401
\LWR@htmltag 5411
\LWR@htmltagc 5344
\LWR@hyperindexrefnullified 9545
\LWR@imagesizebox 121
\LWR@includegraphicsb 140
\LWR@indentHTML 5338
\LWR@indentHTMLtwo 5341
\LWR@indexitem 9509
\LWR@indexnameref 9539
\LWR@indexsubitem 9513
\LWR@indexsubsubitem 9517
LWR@indisplaymathimage (boolean) . . *498*
LWR@infloatrow (boolean) *742*
\LWR@instertatbangcols 7350
LWR@intabularmetadata (boolean) . . . *403*
\LWR@isolate 687
LWR@isstartingequation (boolean) . . *524*
\LWR@itemizeitem 7206
LWR@latestautopage (counter) *477*
\LWR@lateximage@oneimage 10361
\LWR@lateximage@oneimageb 10352
LWR@lateximagedepth (counter) *521*
\LWR@lateximagedepthref 8897
LWR@lateximagenumber (counter) *521*
\LWR@lateximagenumberref 8900
\LWR@lateximagesfile 1212
\LWR@latexmkcmd 1606
\LWR@latexmkdvipdfm 1611
\LWR@latexmkvar 1600
\LWR@lightrulewidth (length) *429*
LWR@LIpage (counter) *521*
\LWR@listitem 7168
\LWR@loadafter 23
\LWR@loadbefore 55
\LWR@loadnever 70
\LWR@longtabledatacaptiontag 8412
\LWR@lookforpackagename 1097
\LWR@lwarpconfversion 1582
\LWR@LwarpEnd 6686, 11871
\LWR@lwarplabel 8903
\LWR@LwarpStart 6620, 11871
\LWR@maketitlesetup 33, 6835
\LWR@mathjaxfilename 5761
LWR@mathmacro (boolean) *314*
\LWR@maybenewtablerow 7772
\LWR@maybeprintpendingfootnotes . 5897
\LWR@maybetocdata 9430
LWR@midrulecounter (counter) *428*
LWR@midrules *428*
LWR@minipagedepth (counter) *545*
LWR@minipagefullwidth (boolean) . . . *545*
\LWR@minipageheight (length) *545*
\LWR@minipagestartpars 11616
\LWR@minipagestoppars 11619
LWR@minipagethispar (boolean) *546*
\LWR@minipagewidth (length) *545*
\LWR@multicolother 8255
\LWR@multicolpartext 8249
\LWR@multicolskip 8261
\LWR@multirowborder 3
\LWR@mynexttoken 7302
\LWR@myshorttoc 9301
\LWR@nameref 8891
LWR@nestspan (environment) 5354
\LWR@new@label 8939
\LWR@newautoidanchor 9180
\LWR@newautopagelabel 6079
\LWR@newhtmlfile 6117
LWR@nextautoid (counter) *476*
LWR@nextautopage (counter) *476*
LWR@nextequation (counter) *509*
\LWR@notltjloadafter 42
\LWR@notmemoirloadafter 39
\LWR@nullfonts 11298
\LWR@nullifycomment 1044
\LWR@nullifyNoAutoSpacing 8702
\LWR@nulllistfills 7175
\LWR@opacity 120
\LWR@openparagraph 5618
LWR@opttablecol (boolean) *418*
\LWR@orig@setBold 9673
\LWR@orig@unsetBold 9674
\LWR@origcolspec 7344
\LWR@originname 310
\LWR@originnames 317
LWR@origmathjax (boolean) *210*
\LWR@overline 11533
\LWR@parseaftercolumn 7550
\LWR@parseatcolumn 7490
\LWR@parsebangcolumn 7516
\LWR@parsebarcolumn 7561

\LWR@parsebeforecolumn 7539
\LWR@parsecoloncolumn 7586
\LWR@parseDcolumn 7635
\LWR@parsedrequirepackagenames .. 1043
\LWR@parsenormalcolumn 7611
\LWR@parsepcolumn 7623
\LWR@parsesemicoloncolumn 7607
\LWR@parsestarcolumn 7632
\LWR@parsetablecols 7674
\LWR@parsewcolumn 7627
\LWR@patcherror 682
\LWR@patchlists 7250
\LWR@pdfencoding 608
\LWR@popclose 5034
\LWR@PreloadedPackage 10558
LWR@prevFileDepth (counter) *360*
LWR@previousautopagelabel (counter) *352*
\LWR@printatbang 7815
\LWR@printbartag 7805
\LWR@printcloselist 7075
\LWR@PrintLatexCmd 1630
\LWR@printlength 1025
\LWR@printmccoldata 8264
\LWR@printmccoltype 8207
\LWR@printopenlist 7076
\LWR@printpendingfootnotes 5894
\LWR@printpendingmpfootnotes 5906
\LWR@printpercentlength 678
\LWR@printthetitle 6787
\LWR@providelength 674
\LWR@ProvidesPackageDrop 1198
\LWR@ProvidesPackageDropA 1183
\LWR@ProvidesPackageDropB 1192
\LWR@ProvidesPackagePass 1168
\LWR@pushclose 5007
\LWR@pushoneclose 6260
\LWR@quickfile 1209
\LWR@ref@ignorestar 9003
\LWR@remembertag 10329
\LWR@replaceEPSSVG 129
\LWR@requesttoc 6679
\LWR@requirepackagenames 1042
\LWR@restoreorigaccents 1537
\LWR@restoreorigformatting 9611
\LWR@restoreoriglists 7278
\LWR@rotboxorigin 309
\LWR@rotstyle 112
\LWR@rowHTMLcolor 7764
\LWR@ruleHTMLcolor 7766
\LWR@sanitize 843
\LWR@sanitized 842
\LWR@scalestyle 115
\LWR@secondoffour 700
\LWR@section 6277
\LWR@sectionnumber 6251
\LWR@select@html@hspace 11636
\LWR@select@html@nohspace 11667
\LWR@select@print@hspace 11670
\LWR@setcurrentfont 9676
\LWR@setexparray 5061
\LWR@setlatestname 8877
\LWR@setOSWindows 760
\LWR@setref 8885
\LWR@shellescapecmd 1583
\LWR@sidetoc 9404
\LWR@simplifycustom 5974
\LWR@simplifyname 5963
\LWR@singledollar 9924
LWR@skipatbang (boolean) *403*
LWR@skippingmcolrowcell (boolean) .. *403*
LWR@skippingmrowcell (boolean) *403*
LWR@spandepth (counter) *332*
\LWR@splitstarcontents 7643
LWR@splitstarcopies (counter) *416*
LWR@splitstarindex (counter) *416*
LWR@starcount (counter) *416*
LWR@starredlongtable (boolean) *444*
LWR@startedrow (boolean) *402*
LWR@startingequation (counter) *523*
\LWR@startingequationtag 10324
\LWR@startnewdepth 6264
\LWR@startpars 5688
\LWR@startref 8958
\LWR@stoppars 5706
\LWR@stripperiod 8876
\LWR@strresult 7342
\LWR@subaddcmidruletrim 7992
\LWR@subaddtabularcellcolor 8177
\LWR@subcdashline 7956
\LWR@subcmidrule 7938
\LWR@subhtmlelementclass 5451
\LWR@subhyperref 9029
\LWR@subhyperrefclass 9043
\LWR@subhyperreftext 9038
\LWR@subinlineimage 9104
\LWR@sublabel 8916
\LWR@subnewref 8989
\LWR@subsingledollar 9733
\LWR@subtableofcontents 9314
\LWR@subtabularhtmlcolumns 8484
\LWR@syncmathjax 10020
LWR@tablecolspec *404*
LWR@tablecolspecindex (counter) ... *404*
LWR@tablecolspecwidth (counter) ... *404*
\LWR@tabledatacolumntag 8575
\LWR@tabledatasinglecolumntag ... 7854
LWR@tableLaTeXcolindex (counter) ... *404*
LWR@tableparcell (boolean) *403*
LWR@tabletotalLaTeXcols (counter) .. *405*
LWR@tabletotalLaTeXcolsnext (counter) *405*

\LWR@tabular@warpprintonly 8698
LWR@tabularcelladded (boolean) *402*
LWR@tabularDepth (counter) *404*
\LWR@tabularendofline 7460
\LWR@tabularfinishrow 7414
\LWR@tabularhtmlcolumns 8494
\LWR@tabularleftedge 7845
LWR@tabularmutemods (boolean) *451*
LWR@tabularpardepth (counter) *404*
\LWR@tdaddstyle 7980
\LWR@tdendstyles 7986
\LWR@tdstartstyles 7979
\LWR@tempcolor 11539
\LWR@tempcolortwo 11539
\LWR@tempheight (length) *570*
\LWR@tempraise (length) *570*
\LWR@tempwidth (length) *570*
\LWR@textcurrentcolor 22, 11544
\LWR@textcurrentfont 11449, 11550
\LWR@thirdoffour 700
\LWR@ThisAltText 9662
LWR@thisautoid (counter) *474*
LWR@thisautoidWP (counter) *475*
\LWR@thiscmidrulewidth (length) *429*
\LWR@thiscolspec 7853
\LWR@thisfilename 5957
\LWR@thisnewfilename 5962
\LWR@titlingmaketitle 83, 6888
\LWR@topnavigation 5204
\LWR@traceinfo 1278
LWR@tracinglwarp (boolean) *230*
LWR@trimlrules *428*
LWR@trimrrules *428*
\LWR@unknownengine 1595
LWR@usedmultirow (boolean) *403*
LWR@validtablecol (boolean) *418*
LWR@verbtags (boolean) *389*
\LWR@vspace 11674
\LWR@WPcell 8051
\LWR@writeconf 1732
\LWR@xcolorrowHTMLcolor 7762
LWR@xfakebold (boolean) *498*
\LWRopquote 755
\LWRopseq 756
\LWRPrintStack 5212
\LWRsetnextfloat 9220
lyluatex (package) *799*
\LyX 11867

M

Mac OS (program) *113*, *208*
Madcap (program) *71*
magaz (package) *801*
\mainmatter 6241
make (program) *166*
\makebox 10977
makeidx (package) *142*, *801*, *959*, *960*
\MakeIndex 11845
makeindex (option) *100*, *105*, *213*
makeindex (program) *140*
makeindexStyle (option) ... *102*, *140*, *212*
\makelabel *393*
\maketitle 47, *115*, 6847
manyfoot (package) *802*
marginal (package) *804*
marginfit (package) *804*
marginfix (package) *804*
marginnote (package) *805*
\marginpar *119*, *347*, 5918
\marginparBlock *119*, *347*, 5929, 5947
\markboth 5262
\markright 5263
marvosym (package) *805*
math (environment) 9986
\MathImageAltText *110*, 9661
MathJax (program) *144*, *145*, *495*
MathJax (program) [requirement] *74*
mathjax (boolean) *210*
mathjax (option) *100*, *105*, *211*
\MathJaxFilename *108*, 5762
mathsvg (option) *100*, *105*, *211*
mathtools (package) *806*
\mbox 10950
mcaption (package) *806*
\mcolrowcell 8650
mdframed (package) *123*, *807*
\mdseries 11480
media9 (package) *151*, *816*
memhfixc (package) *818*
memoir (class) *159*, *160*, *983*
metalogo (package) *818*
metalogox (package) *819*
mhchem (package) *819*
microtype (package) *217*, *822*
midfloat (package) *823*
midpage (package) *823*
\MiKTeX 11865
minibox (package) *823*
minipage (environment) 10843
\minipagefullwidth 10831
minitoc (package) *824*
morefloats (package) *824*
moreverb (package) *825*
movie15 (package) *151*, *826*
mparhack (package) *827*
\mrowcell 8647
MS-Windows (program) *113*, *208*
multicap (package) *828*
multicol (package) *828*
multicolrule (package) *829*
\multicolumnrow 40, 8517

multimedia (package) 151, 830
\multirow 832
multirow (package) 831
multitoc (package) 834
multline (environment) 54
multline* (environment) 57
musicography (package) 834

N

nameauth (package) 837
\Nameref 9021
\nameref 9012
nameref (package) 839
natbib (package) 839
nccfancyhdr (package) 840
needspace (package) 841
newclude (package) 160
\newfloat 4
newfloat (package) 221
\newline 11607
\newpage 11604
\newtheorem 392
newtxmath (package) 147
newunicodechar (package) 98
nextpage (package) 841
nfssext-cfr (package) 841
nicefrac (package) 147, 850
niceframe (package) 851
\noalign 8668
\nolinebreak 11678
\nolinkurl 9070
nomencl (package) 130, 851
nonfloat (package) 852
nonumonpart (package) 852
\nopagebreak 11682
\nopagecolor 76
nopageno (package) 852
\normalcolor 9
\normalfont 11515
\normalmarginpar 5944
notes (package) 852
notespages (package) 853
nowidow (package) 853
ntheorem (package) 146, 854
\numberline 9425
numindex (option) [tocbibind] 143, 960

O

octave (package) 865
OpenOffice (program) 71
option:
  --shell-escape 97
  [lwarpmk]:
    htmlglossary 129, 736
    printglossary 129, 736
  [tocbibind]:
    numindex 143, 960
  [tocloft]:
    titles 128
  BaseJobname 104, 211
  dvipdfm 100, 214
  dvipdfmx 100, 214
  dvips 100, 214
  GlossaryCmd 103, 129, 214, 736
  HomeHTMLFilename 100, 105, 213
  HTMLFilename 100, 105, 213
  HTMLIndexCmd 102, 213
  HTMLLatexCmd 100, 163, 213
  ImagesDirectory 100, 211
  ImagesName 100, 212
  latexmk 100, 105, 214
  LatexmkIndexCmd 103, 213
  lwarpmk 103, 212, 292
  makeindex 100, 105, 213
  makeindexStyle 102, 140, 212
  mathjax 100, 105, 211
  mathsvg 100, 105, 211
  OSWindows 103, 113, 208, 212
  pdftotextEnc 103, 212
  PrintIndexCmd 102, 213
  PrintLatexCmd 100, 163, 213
  warpHTML 103, 211
  warpprint 103, 210
  xindy 102, 105, 213
  xindyCodepage 102, 212
  xindyLanguage 102, 212
  xindyStyle 102, 141, 212
\OSPathSymbol 759
OSWindows (option) 103, 113, 208, 212
overpic (package) 151, 866

P

package:
  2in1 583
  2up 583
  a4 583
  a4wide 584
  a5comb 584
  abstract 128, 584
  academicons 586
  accsupp 587
  acro 587
  acronym 590
  addlines 592
  adjmulticol 591
  afterpage 592
  algorithm2e 592
  algorithmicx 157, 596
  alltt 597
  amsmath 597
  amsthm 600

anonchap 604
anysize 605
appendix 128, 605
ar 606
arabicfront 607
array 607
arydshln 608
asymptote 151, 610
atbegshi 611
attachfile 611
attachfile2 612
authblk 128, 614
autonum 615
axessibility 616
axodraw2 616
babel 161
backnaur 617
backref 617
balance 617
bbding 618
biblatex 623
bibunits 623
bigdelim 157, 623
bigfoot 624
bigstrut 625
bitpattern 625
blowup 626
booklet 626
bookmark 627
booktabs 627
bophook 628
bounddvi 629
boxedminipage2e 629
breakurl 629
breqn 630
bsheaders 632
bxpapersize 632
bytefield 632
calc 220
cancel 632
canoniclayout 633
capt-of 479
caption 157, 228, 479, 634
cases 637
changebar 637
changelayout 638
changepage 639
changes 639
chappg 642
chapterbib 642
chemfig 642
chemformula 644
chemgreek 649
chemmacros 649
chemnum 667
chkfloat 668
chngpage 668
cite 668
CJK 669
CJKutf8 669
cleveref 125, 541
clrdblpg 669
cm-super 98
cmap 99
cmdtrack 670
color 149, 670
colortbl 156, 670
comment 216
continue 672
copyrightbox 672
crop 673
ctable 673
cuted 676
cutwin 676
dblfloatfix 677
dblfnote 677
dcolumn 677
dejavu 98
diagbox 678
dingbat 679
ditaa 166
dprogress 680
draftcopy 680
draftfigure 681
draftwatermark 681
easy-todo 682
ebook 683
ed 683
ellipsis 684
embrac 684
emptypage 685
endfloat 685
endheads 686
endnotes 128, 686
enumerate 687
enumitem 687
environ 222
epigraph 688
epsfig 689
epstopdf 150, 690
epstopdf-base 690
eqlist 691
eqparbox 691
errata 692
eso-pic 694
etoolbox 190
eurosym 694
everyhook 220
everypage 695
everyshi 695

expl3 220
extramarks 695
fancybox 122, 696
fancyhdr 701
fancyref 702
fancytabs 703
fancyvrb 703
figcaps 709
figsize 710
filecontents 221
fitbox 710
fix2col 711
fixme 162, 711
fixmetodonotes 712
flafter 713
flippdf 713
float 157, 713
floatflt 715
floatpag 716
floatrow 158, 716
fltrace 721
flushend 721
fnbreak 722
fncychap 722
fnlineno 723
fnpara 723
fnpos 723
fontawesome 723
fontawesome5 725
fontaxes 726
fontenc 98, 726
fontspec 98
footmisc 727
footnote 728
footnotebackref 728
footnotehyper 729
footnoterange 729
footnpag 729
foreign 729
forest 730
framed 730
ftcap 733
ftnright 733
fullminipage 733
fullpage 733
fullwidth 734
fwlw 734
gentombow 734
geometry 218, 735
gettitlestring 220
gloss 129, 735
glossaries 129, 736
gmeometric 738
graphics 147, 738
graphicx 147, 751
grffile 149, 751
grid 751
grid-system 752
gridset 752
hang 752
hanging 754
hypbmsec 755
hypcap 755
hypdestopt 755
hypernat 755
hyperref 125, 469, 756
hyperxmp 761
hyphenat 761
idxlayout 762
ifoddpage 763
ifplatform 190
imakeidx 763
indentfirst 338
index 767
inputenc 98
inputenx 98
inputtrc 769
intopdf 769
karnaugh-map 770
keyfloat 159, 773
kotex 162
kvoptions 210
layaureo 779
layout 779
layouts 779
leading 782
letltxmacro 190
letterspace 782
lettrine 782
lineno 783
lips 786
listings 786
listliketab 790
lltjext 790
lmodern 98
longtable 155, 791
lscape 794
ltablex 794
ltcaption 795
ltxgrid 795
ltxtable 796
lua-check-hyphen 796
lua-visual-debug 796
luacolor 796
luatodonotes 161, 797
lwarp 100
lwarp-common-multimedia 1041
lwarp-patch-komascript 1014
lwarp-patch-memoir 1016
lyluatex 799

magaz 801
makeidx 142, 801, 959, 960
manyfoot 802
marginal 804
marginfit 804
marginfix 804
marginnote 805
marvosym 805
mathtools 806
mcaption 806
mdframed 123, 807
media9 . . . . . 151, 816
memhfixc 818
metalogo 818
metalogox 819
mhchem 819
microtype 217, 822
midfloat 823
midpage 823
minibox 823
minitoc 824
morefloats 824
moreverb 825
movie15 . . . . . 151, 826
mparhack 827
multicap 828
multicol 828
multicolrule 829
multimedia 151, 830
multirow 831
multitoc 834
musicography 834
nameauth 837
nameref 839
natbib 839
nccfancyhdr 840
needspace 841
newclude 160
newfloat 221
newtxmath 147
newunicodechar 98
nextpage 841
nfssext-cfr 841
nicefrac 147, 850
niceframe 851
nomencl 130, 851
nonfloat 852
nonumonpart 852
nopageno 852
notes 852
notespages 853
nowidow 853
ntheorem 146, 854
octave 865
overpic 151, 866
pagegrid 867
pagenote 128, 867
pagesel 868
paralist 868
parnotes 868
parskip 869
pbox 870
pdfcomment 870
pdfcrypt 871
pdflscape 871
pdfmarginpar 871
pdfpages 871
pdfprivacy 874
pdfrender 874
pdfsync 874
pdftricks 150, 875
pdfx 875
perltex 165
perpage 876
pfnote 877
phfqit 877
pifont 878
placeins 878
plarydshln 878
plext 879
plextarydshln 880
plextcolortbl 880
polyglossia 161
prelim2e 880
prettyref 881
preview 881
printlen 222
psfrag 150, 881
psfragx 882
pst-eps 882
pstool 151, 883
pstricks 150, 883
pxatbegshi 884
pxeveryshi 884
pxftnright 884
pxjahyper 884
pythontex 165
quotchap 885
quoting 886
ragged2e 886
realscripts 887
refcheck 888
refcount 221
register 888
relsize 119, 889
repeatindex 890
resizegather 891
rmpage 891
romanbar 892
romanbarpagenumber 892

rotating 892
rotfloat 893
rterface 165
rviewport 894
sagetex 165
savetrees 894
scalefnt 894
schemata 894
scrextend 895
scrhack 898
scrlayer 898
scrlayer-notecolumn 899
scrlayer-scrpage 900
scrpage2 901
section 902
sectionbreak 903
sectsty 903
semantic-markup 904
setspace 905
shadow 906
shapepar 906
showidx 906
showkeys 907
showtags 907
sidecap 907
sidenotes 908
SIunits 909
siunitx 147, 534, 910
slantsc 915
soul 915
soulpos 917
soulutf8 918
splitidx 918
srcltx 919
srctex 920
stabular 920
stackengine 921
stfloats 922
struktex 923
subcaption 157, 924
subfig 158, 924
subfigure 929
supertabular 156, 929
sympytex 165
syntonly 931
tabfigures 931
tablefootnote 931
tabls 932
tabularx 932
tabulary 932
tascmac 933
textarea 935
textcomp 99, 118, 935
textfit 938
textpos 939
theorem 940
thinsp 943
threadcol 944
threeparttable 944
threeparttablex 156, 945
thumb 946
thumbs 946
tikz 149, 947
titleps 948
titleref 951
titlesec 951
titletoc 953
titling 128, 954
tocbasic 959
tocbibind 142, 143, 959, 960
tocdata 961
tocenter 963
tocloft 128, 143, 604, 963
tocstyle 969
todo 969
todonotes 161, 970
topcapt 972
tram 972
transparent 973
trimclip 973
trivfloat 157, 974
truncate 975
turnthepage 975
twoup 975
typearea 976
typicons 976
ulem 977
umoline 978
underscore 979
units 147, 979
unitsdef 980
upref 981
url 125, 981
uspace 981
varioref 125
varwidth 222
verbatim 221
verse 160, 982, 983
versonotes 983
vertbars 984
vmargin 984
vowel 985
vpe 985
vwcol 985
wallpaper 988
watermark 988
widows-and-orphans 988
wrapfig 989
xbmks 990
xcolor 149, 537, 990

xechangebar 1001
xellipsis 1001
xetexko-vertical 1002
xfakebold 1002
xfrac 1003
xifthen 221
xltabular 1005
xltxtra 1005
xmpincl 1006
xparse 162, 220
xpatch 190
xpiano 1006
xpinyin 1007
xr 1007
xr-hyper 1008
xstring 221
xtab 156, 1008
xunicode 1010
xurl 1011
xy 1011
zhlineskip 1012
zwpagelayout 1012
\PackageDiagramAltText 110, 9666
\pagebreak 11679
\pagecolor 75
pagegrid (package) 867
pagenote (package) 128, 867
\pagenumbering 5268
\pageref 9007
\pagerefPageFor 9006
pagesel (package) 868
\pagestyle 5260
Pandoc (program) 71
\paragraph 6500
paralist (package) 868
\parbox 10941
parnotes (package) 868
\parsemulticolumnalignment 8299
parskip (package) 869
\part 6467
pbox (package) 870
pdfcomment (package) 870
pdfcrop (program) [requirement] 74
pdfcrypt (package) 871
pdfLaTeX (program) [requirement] 74
pdflscape (package) 871
pdfmarginpar (package) 871
pdfpages (package) 871
pdfprivacy (package) 874
pdfrender (package) 874
pdfseparate (program) [requirement] 74, 79
pdfsync (package) 874
pdftocairo (program) 148, 536
pdftocairo (program) [requirement] 74, 79
pdftotext (program) [requirement] . 74, 79
pdftotextEnc (option) 103, 212
pdftricks (package) 150, 875
pdfx (package) 875
perl (program) [requirement] 79
perltex (package) 165
perpage (package) 876
pfnote (package) 877
\phantomsection 11743
phfqit (package) 877
picture (environment) 544, 10818
pifont (package) 878
placeins (package) 878
plarydshln (package) 878
Plastex (program) 70
plext (package) 879
plextarydshln (package) 880
plextcolortbl (package) 880
\PN@parnotes@auto 5617
polyglossia (package) 161
\postbookname 6447
\postchaptername 6451
\postpartname 6449
\postsectionname 6453
\prebookname 6447
\prechaptername 6451
prelim2e (package) 880
\prepartname 6449
\presectionname 6453
prettyref (package) 881
preview (package) 881
\printauthor 378, 6795, 6814
\printdate 378, 6806, 6816
printglossary (option) [lwarpmk] 129, 736
\printindex 2
PrintIndexCmd (option) 102, 213
PrintLatexCmd (option) 100, 163, 213
printlen (package) 222
\printthanks 377, 380
\printtitle 378, 6779, 6813
program:
  [requirement]:
    LuaLaTeX 74
    MathJax 74
    pdfcrop 74
    pdfLaTeX 74
    pdfseparate 74, 79
    pdftocairo 74, 79
    pdftotext 74, 79
    perl 79
    XeLaTeX 74
  Adobe 71
  AsciiDoc 71
  AsciiDoctor 71
  Asciidoctor-LaTeX 71
  epstopdf 148, 536

Flare 71
FrameMaker 71
GELLMU 70
GladTeX 70
Hevea 70
htlatex 70
InDesign 71
LaTeX2HTML 70
latexmk 164
LaTeXML 70
LibreOffice 71
Linux 113, 208
lwarpmk 177, 292
lwarpmk epstopdf 148, 536
lwarpmk pdftosvg 148, 536
Mac OS 113, 208
Madcap 71
make 166
makeindex 140
MathJax 144, 145, 495
MS-Windows 113, 208
OpenOffice 71
Pandoc 71
pdftocairo 148, 536
Plastex 70
TeX2page 70
TeX4ht 70
TeXMaths 171
TtH 70
Unix 113, 208
Windows 113, 208
Word 71
xindy 141
project.css (file) 112
project.lwarpmkconf (file) 249
psfrag (package) 150, 881
psfragx (package) 882
pst-eps (package) 882
pstool (package) 151, 883
pstricks (package) 150, 883
pxatbegshi (package) 884
pxeveryshi (package) 884
pxftnright (package) 884
pxjahyper (package) 884
pythontex (package) 165

Q

\qquad 570, 11627
\quad 570, 11622
quotation (environment) 6965
quotchap (package) 885
quote (environment) 6959
quoting (package) 886

R

ragged2e (package) 886
\raggedbottom 5264
\raggedleft 10541
\raggedright 10547
\raisebox 11124
realscripts (package) 887
\ref 8995
refcheck (package) 888
refcount (package) 221
\reflectbox 371
register (package) 888
relsize (package) 119, 889
repeatindex (package) 890
[requirement]:
LuaLaTeX (program) 74
MathJax (program) 74
pdfcrop (program) 74
pdfLaTeX (program) 74
pdfseparate (program) 74, 79
pdftocairo (program) 74, 79
pdftotext (program) 74, 79
perl (program) 79
XeLaTeX (program) 74
\RequirePackage 1130
\resizebox 380
resizegather (package) 891
\ResumeTabular 8562
\reversemarginpar 5943
\rightline 10555
\rmfamily 11488
rmpage (package) 891
romanbar (package) 892
romanbarpagenumber (package) 892
\rotatebox 329
rotating (package) 892
rotfloat (package) 893
\rowcolor 7767
\rownum 7759
rterface (package) 165
\rule 11686
rviewport (package) 894

S

sagetex (package) 165
sample_project.css (file) 112, 287
savetrees (package) 894
\sb 11517
\scalebox 352
scalefnt (package) 894
schemata (package) 894
scrextend (package) 895
scrhack (package) 898
scrlayer (package) 898
scrlayer-notecolumn (package) 899
scrlayer-scrpage (package) 900
scrpage2 (package) 901
\scshape 11498

\section 6491
section (package) 902
sectionbreak (package) 903
sectsty (package) 903
semantic-markup (package) 904
\SetHTMLFileNumber 5127
setspace (package) 905
\sffamily 11490
\sfrac 1003
shadow (package) 906
shapepar (package) 906
showidx (package) 906
showkeys (package) 907
showtags (package) 907
sidecap (package) 907
sidenotes (package) 908
SideTOCDepth (counter) 107, 483
\sidetocname 107, 9401
\simplechapterdelim 6271
\sishape 11505
SIunits (package) 909
siunitx (package) 147, 534, 910
slantsc (package) 915
\sloppy 5266
\slshape 11513
soul (package) 915
soulpos (package) 917
soulutf8 (package) 918
\sp 11516
splitidx (package) 918
srcltx (package) 919
srctex (package) 920
stabular (package) 920
stackengine (package) 921
\StartDefiningMath 5085
\StartDefiningTabulars 5075
stfloats (package) 922
\StopDefiningMath 5089
\StopDefiningTabulars 5079
struktex (package) 923
subcaption (package) 157, 924
subfig (package) 158, 924
subfigure (package) 929
\subparagraph 6503
\subsection 6494
\subsubsection 6497
supertabular (package) 156, 929
sympytex (package) 165
syntonly (package) 931

T

tabbing (environment) 7042
tabfigures (package) 931
tablefootnote (package) 931
\tableofcontents 109, 9333
tabls (package) 932
tabular (environment) 8715
\TabularMacro 8560
tabularx (package) 932
tabulary (package) 932
tascmac (package) 933
\TeX 11781
TeX2page (program) 70
TeX4ht (program) 70
TeXMaths (program) 171
textarea (package) 935
\textbf 11151
\textcolor 63
textcomp (package) 99, 118, 935
\texteb 11161
textfit (package) 938
\textgreater 5120
\textit 11221
\textless 5118
\textlg 11171
\textmd 11141
\textnormal 11280
textpos (package) 939
\textrm 11181
\textsc 11231
\textsf 11191
\textsi 11251
\textsl 11270
\textsubscript 11520
\textsuperscript 11518
\texttt 11201
\textulc 11241
\textup 11211
\tfl@chapter@fix 974
\thanks 115
\thanksmarkseries 91
\theauthor 378
thebibliography (environment) 9592
\thedate 378
\theHTMLSection 6537
\theHTMLTitleSection 6536
\theHTMLTitleSeparator 6513
theindex (environment) 9497
\thempfootnote 5875
theorem (package) 940
\thetitle 378
thinsp (package) 943
\ThisAltText 110, 9663
\thispagestyle 5261
threadcol (package) 944
threeparttable (package) 944
threeparttablex (package) 156, 945
thumb (package) 946
thumbs (package) 946
tikz (package) 149, 947
\title 115, 5772

titlepage (environment) 115, 6763
titleps (package) 948
titleref (package) 951
titles (option) [tocloft] 128
titlesec (package) 951
titletoc (package) 953
titling (package) 128, 954
titlingpage (environment) 14, 115
tocbasic (package) 959
[tocbibind]:
numindex (option) 143, 960
tocbibind (package) . . . 142, 143, 959, 960
tocdata (package) 961
tocdepth (counter) 107
tocenter (package) 963
[tocloft]:
titles (option) 128
tocloft (package) 128, 143, 604, 963
tocstyle (package) 969
todo (package) 969
todonotes (package) 161, 970
topcapt (package) 972
\tracinglwarp 184, 1277
tram (package) 972
transparent (package) 973
trimclip (package) 973
trivfloat (package) 157, 974
truncate (package) 975
\ttfamily 11492
TtH (program) 70
turnthepage (package) 975
tutorial.tex (file) 80
twoup (package) 975
typearea (package) 976
typicons (package) 976

U

\ulcshape 11500
ulem (package) 977
umoline (package) 978
\underline 11528
underscore (package) 979
units (package) 147, 979
unitsdef (package) 980
Unix (program) 113, 208
\up 11526
upref (package) 981
\upshape 11494
\url 9087
url (package) 125, 981
\UseMinipageWidths 120, 545, 10832
usingOSWindows (boolean) 209
uspace (package) 981

V

varioref (package) 125
varwidth (package) 222
verbatim (environment) 7032
verbatim (package) 221
\VerbatimHTMLWidth (length) 389
\verbatiminput 7024
verse (environment) 2, 6973
verse (package) 160, 982, 983
versonotes (package) 983
vertbars (package) 984
\vleftmargini (length) 160, 388, 982
\vleftskip (length) 160, 388, 982, 983
vmargin (package) 984
vowel (package) 985
vpe (package) 985
vwcol (package) 985

W

wallpaper (package) 988
warpall (environment) 114, 908
warpHTML (environment) 111, 113, 909
warpHTML (option) 103, 211
\warpHTMLonly 111, 114, 899
warpingHTML (boolean) 210
warpingprint (boolean) 210
warpprint (environment) . . . 110, 114, 909
warpprint (option) 103, 210
\warpprintonly 111, 114, 898
watermark (package) 988
widows-and-orphans (package) 988
Windows (program) 113, 208
Word (program) 71
WPMarkFloats (boolean) 170, 236
WPMarkLOFT (boolean) 171, 237
WPMarkMath (boolean) 171, 237
WPMarkMinipages (boolean) 171, 236
WPMarkTOC (boolean) 171, 236
WPTitleHeading (boolean) 172, 237
wrapfig (package) 989

X

xbmks (package) 990
xcolor (package) 149, 537, 990
xechangebar (package) 1001
\XeLaTeX 11828
XeLaTeX (program) [requirement] 74
xellipsis (package) 1001
\XeTeX 11828
xetexko-vertical (package) 1002
xfakebold (package) 1002
xfrac (package) 1003
\xfracHTMLfontsize 3
xifthen (package) 221
xindy (option) 102, 105, 213
xindy (program) 141
xindyCodepage (option) 102, 212
xindyLanguage (option) 102, 212

xindyStyle (option) 102, 141, 212
xltabular (package) 1005
xltxtra (package) 1005
xmpincl (package) 1006
xparse (package) 162, 220
xpatch (package) 190
xpiano (package) 1006
xpinyin (package) 1007
xr (package) 1007
xr-hyper (package) 1008
xstring (package) 221
xtab (package) 156, 1008
xunicode (package) 1010
xurl (package) 1011
xy (package) 1011

Z

zhlineskip (package) 1012
zwpagelayout (package) 1012

General Index

This is an index of instructions and concepts. Look here when wondering how to do something, and check the Troubleshooting Index when something goes wrong.

Symbols

\, . . . 118
~ . . . 118

A

accents
  in section & file names . . . 358
accessibility . . . 96
adapting
  class . . . 176
  document . . . 95
  package . . . 175
affiliation
  multiple authors . . . 127
algorithmicx
  with newfloat, trivfloat . . . 974
alt text . . . 96
array
  mhchem . . . 820
audio . . . 151
author
  HTML meta tag . . . 116, 340
  multiple . . . 127

B

baseline
  tabular . . . 418
bibliography
  HTML page and TOC . . . 127
bitmapped fonts . . . 97
bugs . . . 179

C

Calibre . . . 167
chemistry
  Greek symbols . . . 649
class
  modifying for lwarp . . . 176
code listings . . . 117
compiling
  custom . . . 163
Computer Modern . . . 97
converting
  class . . . 176
  document . . . 95
  package . . . 175
CSS
  file selection . . . 112
  lwarp.css . . . 112
  per HTML page . . . 112
  project-specific changes . . . 112
ctable . . . 156

D

danger icon . . . 189
debugging . . . 179
  HTML debug comments . . . 230
  tracing log . . . 230
Deja Vu . . . 98
description
  HTML meta tag . . . 115, 340
display math
  complicated objects . . . 146
document
  convert existing . . . 95
DVI LaTeX . . . 90, 97
dynamic math . . . 146
dynamic math expressions . . . 314

E

endnotes
  HTML page and TOC . . . 127
EPS image
  converting . . . 92
  using . . . 147, 535
EPUB
  conversion software . . . 167
  HTML conversion settings . . . 167, 236
error messages . . . 179
export
  to word processor . . . 169

F

FAQ . . . 179
filename
  accent in . . . 358
  hashed . . . 500, 526
  international languages . . . 160
  length . . . 108
  simplify . . . 123
  underscore in . . . 105, 119
  unique . . . 108

font
Computer Modern 97
Deja Vu 98
ligatures 98
packages 98
selection 97
size
lateximage 144, 494, 521
math, SVG 144, 494, 521
xfrac 1003
type 1 vector 97
type 3 bitmapped 97
footnotes 341
numbering 125
foreign
section names 160
framed objects 120
Frequently Asked Questions 179

G

generator
HTML meta tag 371
GIF images 148, 536
gloss 129
glossaries
HTML page and TOC 127
language 129
options 129
processing 91
graphics
file formats 147, 535
Greek
chemistry symbols 649

H

hash
SVG image filename 500, 526
heading, word processor 172
horizontal space 118
between minipages 569
HTML
alt text 96
conversion settings 105
debug comments 230
EPUB 167, 236
word processor 169, 236
conversion suggestions 116
entities, conversion 117
filename generation 111
headings 188
meta tag
author 116, 340
description 115, 340
generator 371
title 108, 109, 116, 340
viewport 371
selecting print/HTML definitions . . 231
tabular column conversion 419
verbatim, in 117
hyperref
and xindy 131
title text 96

I

icon
warning 189
image
alt text 96
file formats 147, 535
GIF 148, 536
graphicx package 535
hashed filename 500, 526
PDF or EPS
converting 92, 148, 536
using 147, 535
PNG and JPG 148, 536
processing 292
\includegraphics
using 147, 535
index
custom makeindex style file 140
custom xindy style file 141
custom display styles 142
formatting 489
HTML page and TOC 127
letter headings 763
placement and TOC options . . . 142, 959
processing 84, 85, 131
see, seealso, ranges 131
source code 131
table of contents 142, 959
UTF-8 99
xindy and hyperref 131
inline math
complicated objects 146
international
section names 160
item
empty 393

J

JAVASCRIPT
MATHJAX 143, 494
JPG images 148, 536

L

label
in HTML 374
math environment 516
language
glossaries 129
localization 96
language HTML metadata 369

latexmk
  font size 144, 494, 521
  processing 292
Latin Modern font 97
LibreOffice
  conversion recommendations 172
  import into 169
  section headings 172
ligatures 98, 217
line numbers 189
link
  title text 96
list
  empty item 393
  filename 119
listings, program code 117
locale 166
localization 96
LuaLaTeX
  detection 190
  file & section names 358
lwarp
  loading 100
  options 100
lwarp.ist
  customizing 140
lwarp.xdy
  customizing 141
lwarpmk
  customizing 177

M

make utility 166
makeindex
  customizing 140
margin
  numbers 189
  tags 189
markup languages 71
math
  alt text 96
  display with complicated objects . . 146
  dynamic 146, 314
  font size — SVG 144, 494, 521
  inline with complicated objects . . . 146
  MathJax custom functions . . . 145, 495
  MathJax summary 144, 495
  mathjax option 211
  mathsvg option 211
  mhchem 820
  SVG summary 144, 494
  word processor conversion 171
MathJax
  accessibility 96
  custom functions 145, 495
  custom script 290
  mathjax option 211
  summary 144, 495
\mcolrowcell 154
MD5 hash
  SVG image filename 500, 526
memoir
  verse 983
meta tag, HTML
  author 116, 340
  description 115, 340
  generator 371
  title 116, 340
  viewport 371
minipage
  framed 120
  horizontal space between 569
modifying
  class 176
  document 95
  package 175
\mrowcell 154
\multicolumn
  with \multirow 154
multimedia 151
multiple projects in a directory 92
\multirow
  with \multicolumn 154
multirow
  \mrowcell and \mcolrowcell 154

N

newfloat
  with trivfloat, algorithmicx 974
nomencl 130
numbers
  left margin 189

P

package
  modifying for lwarp 175
  required 217
\par
  hooks 336
PDF image
  converting 92
  using 147, 535
Perl 79
PNG images 148, 536
Poppler 74, 79
print
  selecting print/HTML definitions . . 231
problems 179
program listings 117
programs
  utility 73
projects 92

\published 385

S

section
depths 188
file names 123
heading, word processor 172
international languages 160
settings
accessibility 96
CSS project-specific 112
CSS selection 112
filenames 105
HTML conversion 105
language 96
lwarp package options 100
selecting output 113
title page 115
shell escape 97
sidetoc
name 96
sidetoc
depth 105
siunitx
with *TeXMaths* 171
space
horizontal 118
between minipages 569
stack depths 188
\subtitle 385
SVG
converting from PDF or EPS 92
dynamic math 314
image processing 292
math summary 144, 494
mathsvg option 211

T

tabular
baseline 418
HTML columnn conversion 419
macros inside 153, 400
\multicolumn with \multirow 154
multirow \mrowcell and \mcolrowcell 154
tikz
catcodes 947
dollar redefined 947
title
HTML meta tag 116, 340
titlepage
\subtitle and \published 385
tracing log 230
trivfloat
with newfloat, algorithmicx 974
troubleshooting 179
HTML debug comments 230
tracing log 230
type 1 vector fonts 97
type 3 bitmapped fonts 97

U

underscore
filename 105, 119
Unicode
enhanced coverage 98
file & section names 358
input characters 204
selection 97
UTF-8
enhanced coverage 98
file & section names 358
index 99
locale 166
selection 97
utility
programs 73

V

vector fonts 97
verbatim
code and HTML tags 117
video 151
viewport
HTML meta tag 371

W

warning icon 189
word processor
conversion recommendations 172
HTML conversion settings 169, 236
section headings 172

X

xcite 92
XeLaTeX
detection 190
file & section names 358
xindy
and hyperref 131
customizing 141
xparse
warnings 162
xr 92
xr-hyper 92

Troubleshooting Index

This index is a sorted reference of problems and solutions. In order to make it easier to locate a solution, the same issue may be addressed by more than one entry.

Entries with higher page numbers are often duplicates of entries with lower page numbers, as the same warning may occur within the user manual and again within the source code for a given package.

A

abstract
  missing TOC 128, 584
acronym
  multiply-defined labels 590
\AddSubtitlePublished 385
affiliation 378
alt tags 146, 182
AMSmath
  ntheorem
    numbering 147, 854
appendix
  incorrect TOC link 128, 605
array
  chemformula 162
audio 151
authblk
  \theauthor 377, 378
  titling 128, 377, 614, 955
author
  affiliation 378
  formatting 115
autonum 615

B

babel
  French 161
backref 617
backref 125
bibliography
  HTML page and TOC 127
bibtex
  \etalchar 129
  Improper \prevdepth 129
bigdelim 157, 623
bigfoot 126, 802
boxes 119
breqn
  darray 630
  MathJax 630

C

Calibre
  EPUB conversion 167
caption
  numbering 158
  options 157
cases
  MathJax 637
chemfig 162
chemformula
  MathJax 162, 644
chemgreek
  fontspec mapping 649
  text-mode symbols 649
chemmacros
  \makepolymerdelims 650
  redox reactions 650
colortbl 156, 670
cross reference
  incorrect link 183
  missing 182
CSS 184
ctable 156

D

ditaa 166
duplcate filename 124

E

\endhead, etc. 155
endnotes
  HTML page and TOC 127
\ensuremath 182
epstopdf 150, 690
EPUB
  encoding 167
  page order 167
  search order 167
  section breaks 168
error messages 179
\etalchar 129

F

fancybox
  \VerbatimFootnotes . . . 126, 697, 703
fancyvrb
  \VerbatimFootnotes . . . 126, 697, 703
figure
  macro in name . . . 182
file
  inaccessible . . . 107
  multiple projects in directory . . . 92
filename
  accents . . . 358
  corrupted . . . 124, 160
  duplicate . . . 124
  international, UTF-8 . . . 160
  Korean . . . 162
  macro in name . . . 124
  math in . . . 95, 124, 143, 493
  Missing $ inserted . . . 181
fixme . . . 162, 711
float
  alignment . . . 118, 157
  out of sequence . . . 183
floatrow
  \FBwidth and \FBheight . . . 158, 716
  with subfig . . . 158, 716
floatrow
  \ttabbox . . . 153, 400
font
  ligatures . . . 98, 99
  missing symbols . . . 118, 935
  monospace . . . 99
  package conflicts . . . 98
  selection . . . 97
  UTF-8 . . . 97
fontspec . . . 98
footmisc . . . 126, 341
footnote
  displaymath . . . 126, 697, 703
  in math . . . 126
  in sectioning command . . . 125
  memoir . . . 126, 341
  numbering . . . 125
  paragraph tags . . . 126, 697, 703
  sectioning, footmisc . . . 126, 341
  sectioning, verbatim . . . 126, 697, 703
  title . . . 378
  verbatim . . . 126
  \VerbatimFootnotes . . . 126, 697, 703
forest . . . 730
formatting
  \bfseries etc. . . . 117, 555
frames . . . 120

G

gloss . . . 129
glossaries
  HTML page and TOC . . . 127
  makeglossaries not found . . . 129, 736
  page numbers . . . 130, 737
  style . . . 130, 737
graphics
  \rotatebox, \scalebox, \reflectbox . . . 149, 537
  image format priorities . . . 148, 536
  images out of order . . . 86, 183
  multimedia . . . 151
  optional arguments . . . 148, 536
  scale option . . . 95, 147, 535
  scaled . . . 739
  viewport . . . 148, 536
Greek packages . . . 649
grffile . . . 149, 751

H

horizontal spacing . . . 158, 924
HTML
  &, <, > . . . 117, 555
  alt tags . . . 146
  author . . . 340
  corrupted . . . 115, 119, 180, 181, 184
  entities . . . 117, 555
  image appear as HTML code . . . 86, 183
  inaccessible pages . . . 107, 109
    starred section . . . 127
  invalid . . . 117
  missing pages
    filename not unique . . . 108
    recompile . . . 184
    SideTOCDepth and FileDepth . . . 107
    SideTOCDepth and tocdepth . . . 107
  page did not update . . . 107, 184
  settings
    changed . . . 105
    undefined . . . 181
  validation . . . 117
\HTMLAuthor . . . 340
HTMLIndexCmd
  filenames . . . 102
hyperref
  backref . . . 125
  comments between arguments . . . 125
  incorrect link . . . 183

I

image
  appears as HTML code . . . 86, 183
  format priorities . . . 148, 536
  incorrect . . . 86, 183, 184
  viewport . . . 148, 536
Improper \prevdepth
  bibtex . . . 129

boxes 182
\includegraphics
optional arguments 148, 536
scale 95, 147, 535
index
empty 141
empty link 124, 183
formatting 489
HTML page and TOC 127
missing entries 131
numbers, not links 221
reference ranges 141
see and seealso 141
styling references 141
xindy and hyperref 141
xstring bug 221

K

keyfloat 159, 773

L

label
\nameref empty 124, 183
characters 124, 183
Label(s) may have changed 181
\LateximageFontSizeName 521
Leaders not followed by proper glue . . 181
LibreOffice
import 169
ligatures 99
LINUX 113, 208
list
empty item 118, 393
listings 183
lists
label formatting 393
locale 166
longtable
\endhead, etc. 155
lrbox 119
ltxtable
numbering 796
lualaTeX 98
\LWRbackslash 163
\LWRdollar 163
\LWRhash 163
\LWRopquote 163
\LWRopseq 163
\LWRpercent 163

M

MAC OS 113, 208
makeglossaries
not found 129, 736
\makelabel 393
manyfoot 126, 802
\marginpar 119, 347
math
alt tags 182
appears as HTML code 86, 183
chemformula 162
custom macros 182
dynamic 314
equation numbering
ntheorem 147, 854
file name 95, 124, 143, 493
footnote 126
in TeX boxes 144, 495
incorrect 86, 184, 314
non-math contents 182
section name 95, 124, 143, 493
slow or failed compile 182
subequations 145, 495
tabbing 152, 391
Ti*k*z 146
MATHJAX
breqn 630
cases 637
chemformula 162, 644
custom script 290
errors 146, 182, 314
mhchem 819
siunitx 145, 147, 496, 534, 910
subequations 145, 495
unsupported packages . . 145, 182, 496
mathtools 806
\mcolrowcell 154
media9 151
memoir
footmisc 126, 341
options clash 159, 1016
version clash 159, 1016
mhchem
MATHJAX 819
nested dollar signs 820
minipage
alignment 120, 545
horizontal space between 569
in a span 120, 544
inline 119, 544
multicols, width in 120, 545
size 120, 545
tabular, width in 120, 545
Misplaced \noalign 155, 792
tabular
rules 154, 401
Misplaced \omit
tabular 233
Misplaced alignment tab character &
ctable 156, 673
floatrow 158, 716

frames 121
supertabular 156, 929, 1008
tabular
macros 152, 313, 399
Missing $ inserted
filename or URL 181
morewrites 181
morewrites 141
movie15 151
\mrowcell 154
MS-WINDOWS 113, 208
multimedia 151
multiple projects in a directory 92
multiply-defined labels
acronym 590
\multirow and \multicolumn 155, 831
multirow
\mrowcell and \mcolrowcell 154

N

newclude 161
newtxmath 147
nicefrac 147
No room for a new \write 181
nomencl 130
ntheorem 854
font 146, 854
numbering 147, 854

O

operating system 113, 208
options clash
memoir 159, 1016
overpic 151, 866

P

package
version numbers with memoir 159, 1016
page
inacessible 107
page counter
references 124
SVG images 86, 184
page numbers 125, 183, 541
pdftricks 150, 875
perltex 165
pfnote
numbering 126, 877
polyglossia
Undefined control sequence 161
poppler
Syntax Warning (ligature) 723
PrintIndexCmd 102
projects
multiple 92
psfrag 150
pstool 151, 883
pstricks 150, 883
pythontex 165

R

reference
% character between arguments . . 183
empty link 124, 183
incorrect link 183
label characters 124, 183
missing or incorrect 182
page number 125, 183, 541
repeatindex 890
rterface 165

S

sample_projects.css
overwritten 112
\savebox 119
\sbox 119
scale (\includegraphics option) 95, 147, 535
sectioning
accents 358
duplicate name 124
international language 160
macro in name 124, 182
math in name 95, 124, 143, 493
missing 107
starred section 127
word processor import 172
siunitx
MATHJAX 147, 534, 910
with TeXMaths 171
siunitx 147, 534, 910
MATHJAX 145, 496
S column 154, 401
tabular S and s columns . 147, 534, 910
splitidx
\thepage and \AtWriteToIndex 132, 918
subcaption
numbering 158
subfig
options 158, 924
with floatrow 158, 716
SVG image
appears as HTML code 86, 183
incorrect 86, 183, 184
math incorrect 314
out of order 86, 183
sympytex 165
Syntax Warning (ligature) 723

T

tabbing
math 152, 391

table
macro in name . . . 182
numbering . . . 796
Table of Contents
missing . . . 109
tabular
baselines . . . 418
corrupt rows . . . 153, 400, 450
\endhead, \endfoot, \endlastfoot . . . 155, 791
inside an environment . . . 153, 400, 450
\kill . . . 155, 792
macro inside . . . 153, 400
Misplaced \noalign . . . 154, 401
Misplaced alignment tab character & . . . 152, 399
macros . . . 313
rules . . . 154
\multicolumn with \multirow . . . 154
multirow \mrowcell and \mcolrowcell . . . 154
\newcolumntype . . . 153, 400
numbering . . . 1005
row corruption . . . 153, 400
rules . . . 154, 401
S column . . . 154, 401
TeXMaths . . . 171
text
&, <, > . . . 117, 555
\bfseries etc. . . . 117, 555
corrupted . . . 97
textcomp
missing symbols . . . 118, 935
\theauthor and authblk . . . 377, 378
threeparttablex . . . 156
tikz
in math . . . 146
matrices, & . . . 149, 947
title
affiliation . . . 378
newlines . . . 115
\thanks . . . 378
titling
authblk . . . 128, 377, 614, 955
hooks . . . 385
tocloft
chapter titles . . . 128, 143, 604, 963
todonotes . . . 161, 797, 970
tracing lwarp . . . 184
tram . . . 972
transparent . . . 973

U

Undefined control sequence
polyglossia . . . 161
Unicode
fonts . . . 97
UTF-8 locale . . . 166
units . . . 147
Unix . . . 113, 208
URL
Missing $ inserted . . . 181
\usebox . . . 119
UTF-8
locale . . . 166

V

verbatim
footnote . . . 126
framed . . . 122, 696
VerbatimFootnotes . . . 126, 697, 703
verse
spacing . . . 160, 388, 982
version numbers
with memoir . . . 159, 1016
video . . . 151
viewport . . . 148, 536

W

warning messages . . . 179
warpall . . . 181
warpHTML . . . 113, 181
warpprint . . . 114, 181
Windows . . . 113, 208
word processor
import . . . 169
sectioning headings . . . 172

X

xcite . . . 92
xeLaTeX . . . 98
xfakebold . . . 1002
xfrac . . . 1003
xindy
hyperref . . . 141
options
HTMLIndexCmd . . . 103
LatexmkIndexCmd . . . 103
PrintIndexCmd . . . 102
xltabular
numbering . . . 1005
xparse . . . 162
xr . . . 92
xr-hyper . . . 92
xstring . . . 221

Index of Indexes

C

Change History 1046

G

General Index 1096

I

Index of Objects 1075

T

Troubleshooting Index 1100