

The kvdefinekeys package

Heiko Oberdiek*

2016/05/16 v1.4

Abstract

Package kvdefinekeys provides `\kv@define@key` to define keys the same way as keyval's `\define@key`. However, it works also using ini-TeX.

Contents

1	Documentation	1
1.1	Motivation	1
2	Implementation	2
2.1	Identification	2
2.2	Package loading	4
2.3	Provide key defining macro	4
3	Test	5
3.1	Catcode checks for loading	5
4	Installation	7
4.1	Download	7
4.2	Bundle installation	7
4.3	Package installation	7
4.4	Refresh file name databases	7
4.5	Some details for the interested	8
5	References	8
6	History	8
	[2010/03/01 v1.0]	8
	[2010/08/19 v1.1]	8
	[2011/01/30 v1.2]	8
	[2011/04/07 v1.3]	8
	[2016/05/16 v1.4]	8

1 Documentation

1.1 Motivation

`\kvsetkeys` serves as replacement for keyval's `\setkeys`. This package adds macros to define keys, closing the gap `\kvsetkeys` leaves.

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

<code>\kv@define@key {<family>} {<key>} [<default>] {<definition>}</code>

Macro `\kv@define@key` reimplements `keyval`'s `\define@key`. Differences to the original:

- The defined keys also allow `\par` inside values.
- Shorthands of package `babel` are supported in family and key names.
- Macro `\kv@define@key` is made robust if ε -TeX's `\protected` or L^AT_EX's `\DeclareRobustCommand` are found.

2 Implementation

2.1 Identification

```
1 <*package>
```

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3   \catcode13=5 % ^~M
4   \endlinechar=13 %
5   \catcode35=6 % #
6   \catcode39=12 % '
7   \catcode44=12 % ,
8   \catcode45=12 % -
9   \catcode46=12 % .
10  \catcode58=12 % :
11  \catcode64=11 % @
12  \catcode123=1 % {
13  \catcode125=2 % }
14  \expandafter\let\expandafter\x\csname ver@kvdefinekeys.sty\endcsname
15  \ifx\x\relax % plain-TeX, first loading
16  \else
17    \def\empty{}%
18    \ifx\x\empty % LaTeX, first loading,
19      % variable is initialized, but \ProvidesPackage not yet seen
20    \else
21      \expandafter\ifx\csname PackageInfo\endcsname\relax
22        \def\x#1#2{%
23          \immediate\write-1{Package #1 Info: #2.}%
24        }%
25      \else
26        \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27      \fi
28      \x{kvdefinekeys}{The package is already loaded}%
29      \aftergroup\endinput
30    \fi
31  \fi
32 \endgroup%
```

Package identification:

```
33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34   \catcode13=5 % ^~M
35   \endlinechar=13 %
36   \catcode35=6 % #
37   \catcode39=12 % '
38   \catcode40=12 % (
39   \catcode41=12 % )
```

```

40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51 \def\x#1#2#3[#4]{\endgroup
52 \immediate\write-1{Package: #3 #4}%
53 \xdef#1{#4}%
54 }%
55 \else
56 \def\x#1#2[#3]{\endgroup
57 #2[#{#3}]%
58 \ifx#1\@undefined
59 \xdef#1{#3}%
60 \fi
61 \ifx#1\relax
62 \xdef#1{#3}%
63 \fi
64 }%
65 \fi
66 \expandafter\x\csname ver@kvdefinekeys.sty\endcsname
67 \ProvidesPackage{kvdefinekeys}%
68 [2016/05/16 v1.4 Define keys (H0)]%
69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^~M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76 \expandafter\edef\csname KVD@AtEnd\endcsname{%
77 \endlinechar=\the\endlinechar\relax
78 \catcode13=\the\catcode13\relax
79 \catcode32=\the\catcode32\relax
80 \catcode35=\the\catcode35\relax
81 \catcode61=\the\catcode61\relax
82 \catcode64=\the\catcode64\relax
83 \catcode123=\the\catcode123\relax
84 \catcode125=\the\catcode125\relax
85 }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^~M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95 \edef\KVD@AtEnd{%
96 \KVD@AtEnd
97 \catcode#1=\the\catcode#1\relax

```

```

98 }%
99 \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{42}{12}% *
102 \TMP@EnsureCode{46}{12}% .
103 \TMP@EnsureCode{47}{12}% /
104 \TMP@EnsureCode{91}{12}% [
105 \TMP@EnsureCode{93}{12}% ]
106 \edef\KVD@AtEnd{\KVD@AtEnd\noexpand\endinput}

```

2.2 Package loading

```

107 \begingroup\expandafter\expandafter\expandafter\endgroup
108 \expandafter\ifx\csname RequirePackage\endcsname\relax
109 \def\TMP@RequirePackage#1[#2]{%
110 \begingroup\expandafter\expandafter\expandafter\endgroup
111 \expandafter\ifx\csname ver@#1.sty\endcsname\relax
112 \input #1.sty\relax
113 \fi
114 }%
115 \TMP@RequirePackage{ltxcms}[2010/03/01]%
116 \else
117 \RequirePackage{ltxcms}[2010/03/01]%
118 \fi

```

2.3 Provide key defining macro

\kv@define@key

```

119 \ltx@ifundefined{protected}{%
120 \ltx@ifundefined{DeclareRobustCommand}{%
121 \def\kv@define@key#1#2{%
122 }{%
123 \DeclareRobustCommand*{\kv@define@key}[2]%
124 }%
125 }{%
126 \protected\def\kv@define@key#1#2{%
127 }%
128 }%
129 \begingroup
130 \csname @safe@activetrue\endcsname
131 \let\ifin\csname\iftrue
132 \edef\KVD@temp{\endgroup
133 \noexpand\KVD@DefineKey{#1}{#2}%
134 }%
135 \KVD@temp
136 }

```

\KVD@DefineKey

```

137 \def\KVD@DefineKey#1#2{%
138 \ltx@ifnextchar[{%
139 \KVD@DefineKeyWithDefault{#1}{#2}%
140 }{%
141 \long\expandafter\def\csname KV@#1@#2\endcsname##1%
142 }%
143 }

```

\KVD@DefineKeyWithDefault

```

144 \long\def\KVD@DefineKeyWithDefault#1#2[#3]{%
145 \expandafter\def\csname KV@#1@#2@default\endcsname

```

```

146 \expandafter{%
147   \csname KV@#1@#2\endcsname{#3}%
148 }%
149 \long\expandafter\def\csname KV@#1@#2\endcsname##1%
150 }

151 \KVD@AtEnd%
152 \</package>

```

3 Test

3.1 Catcode checks for loading

```

153 \<{*test1}

154 \catcode`\{=1 %
155 \catcode`\}=2 %
156 \catcode`\#=6 %
157 \catcode`\@=11 %
158 \expandafter\ifx\csname count@\endcsname\relax
159   \countdef\count@=255 %
160 \fi
161 \expandafter\ifx\csname @gobble\endcsname\relax
162   \long\def\@gobble#1{%
163 \fi
164 \expandafter\ifx\csname @firstofone\endcsname\relax
165   \long\def\@firstofone#1{#1}%
166 \fi
167 \expandafter\ifx\csname loop\endcsname\relax
168   \expandafter\@firstofone
169 \else
170   \expandafter\@gobble
171 \fi
172 {%
173   \def\loop#1\repeat{%
174     \def\body{#1}%
175     \iterate
176   }%
177   \def\iterate{%
178     \body
179     \let\next\iterate
180   \else
181     \let\next\relax
182   \fi
183   \next
184 }%
185 \let\repeat=\fi
186 }%
187 \def\RestoreCatcodes{}
188 \count@=0 %
189 \loop
190   \edef\RestoreCatcodes{%
191     \RestoreCatcodes
192     \catcode\the\count@=\the\catcode\count@\relax
193   }%
194 \ifnum\count@<255 %
195   \advance\count@ 1 %
196 \repeat

```

```

197
198 \def\RangeCatcodeInvalid#1#2{%
199   \count@=#1\relax
200   \loop
201     \catcode\count@=15 %
202     \ifnum\count@<#2\relax
203       \advance\count@ 1 %
204     \repeat
205 }
206 \def\RangeCatcodeCheck#1#2#3{%
207   \count@=#1\relax
208   \loop
209     \ifnum#3=\catcode\count@
210     \else
211       \errmessage{%
212         Character \the\count@\space
213         with wrong catcode \the\catcode\count@\space
214         instead of \number#3%
215       }%
216     \fi
217     \ifnum\count@<#2\relax
218       \advance\count@ 1 %
219     \repeat
220 }
221 \def\space{ }
222 \expandafter\ifx\csname LoadCommand\endcsname\relax
223   \def\LoadCommand{\input kvdefinekeys.sty\relax}%
224 \fi
225 \def\Test{%
226   \RangeCatcodeInvalid{0}{47}%
227   \RangeCatcodeInvalid{58}{64}%
228   \RangeCatcodeInvalid{91}{96}%
229   \RangeCatcodeInvalid{123}{255}%
230   \catcode`\@=12 %
231   \catcode`\|=0 %
232   \catcode`\%=14 %
233   \LoadCommand
234   \RangeCatcodeCheck{0}{36}{15}%
235   \RangeCatcodeCheck{37}{37}{14}%
236   \RangeCatcodeCheck{38}{47}{15}%
237   \RangeCatcodeCheck{48}{57}{12}%
238   \RangeCatcodeCheck{58}{63}{15}%
239   \RangeCatcodeCheck{64}{64}{12}%
240   \RangeCatcodeCheck{65}{90}{11}%
241   \RangeCatcodeCheck{91}{91}{15}%
242   \RangeCatcodeCheck{92}{92}{0}%
243   \RangeCatcodeCheck{93}{96}{15}%
244   \RangeCatcodeCheck{97}{122}{11}%
245   \RangeCatcodeCheck{123}{255}{15}%
246   \RestoreCatcodes
247 }
248 \Test
249 \csname @@end\endcsname
250 \end
251 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/kvdefinekeys.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/kvdefinekeys.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex kvdefinekeys.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>kvdefinekeys.sty</code>	→ <code>tex/generic/oberdiek/kvdefinekeys.sty</code>
<code>kvdefinekeys.pdf</code>	→ <code>doc/latex/oberdiek/kvdefinekeys.pdf</code>
<code>test/kvdefinekeys-test1.tex</code>	→ <code>doc/latex/oberdiek/test/kvdefinekeys-test1.tex</code>
<code>kvdefinekeys.dtx</code>	→ <code>source/latex/oberdiek/kvdefinekeys.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your T_EX distribution (teT_EX, mikT_EX, ...) relies on file name databases, you must refresh these. For example, teT_EX users run `texhash` or `mktextlsr`.

¹[CTAN:pkg/kvdefinekeys](#)

4.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{kvdefinekeys.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex kvdefinekeys.dtx
makeindex -s gind.ist kvdefinekeys.idx
pdflatex kvdefinekeys.dtx
makeindex -s gind.ist kvdefinekeys.idx
pdflatex kvdefinekeys.dtx
```

5 References

- [1] David Carlisle: *The keyval package*; 1999/03/16 v1.13; [CTAN:macros/latex/required/graphics/keyval.dtx](#).

6 History

[2010/03/01 v1.0]

- First version.

[2010/08/19 v1.1]

- Documentation fix, no code change.

[2011/01/30 v1.2]

- Already loaded package files are not input in plain T_EX.

[2011/04/07 v1.3]

- Support for package `babel`'s shorthands added.
- `\kv@define@key` is made robust if available.

[2016/05/16 v1.4]

- Documentation updates.

7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols			
\#	156	\immediate	23, 52
\%	232	\input	112, 223
\@	157, 230	\iterate	175, 177, 179
\@firstofone	165, 168	K	
\@gobble	162, 170	\kv@define@key	2, 119
\@undefined	58	\KVD@AtEnd	95, 96, 106, 151
\\	231	\KVD@DefineKey	133, 137
\{	154	\KVD@DefineKeyWithDefault	139, 144
\}	155	\KVD@temp	132, 135
A		L	
\advance	195, 203, 218	\LoadCommand	223, 233
\aftergroup	29	\loop	173, 189, 200, 208
B		\ltx@ifnextchar	138
\body	174, 178	\ltx@ifUndefined	119, 120
C		N	
\catcode	2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 69, 70, 72, 73, 74, 78, 79, 80, 81, 82, 83, 84, 87, 88, 90, 91, 92, 93, 97, 99, 154, 155, 156, 157, 192, 201, 209, 213, 230, 231, 232	\next	179, 181, 183
\count@	159, 188, 192, 194, 195, 199, 201, 202, 203, 207, 209, 212, 213, 217, 218	\number	214
\countdef	159	P	
\csname	14, 21, 50, 66, 76, 108, 111, 130, 141, 145, 147, 149, 158, 161, 164, 167, 222, 249	\PackageInfo	26
D		\protected	126
\DeclareRobustCommand	123	\ProvidesPackage	19, 67
E		R	
\empty	17, 18	\RangeCatcodeCheck	206, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245
\end	250	\RangeCatcodeInvalid	198, 226, 227, 228, 229
\endcsname	14, 21, 50, 66, 76, 108, 111, 130, 141, 145, 147, 149, 158, 161, 164, 167, 222, 249	\repeat	173, 185, 196, 204, 219
\endinput	29, 106	\RequirePackage	117
\endlinechar	4, 35, 71, 77, 89	\RestoreCatcodes	187, 190, 191, 246
\errmessage	211	S	
I		\space	212, 213, 221
\ifincsname	131	T	
\ifnum	194, 202, 209, 217	\Test	225, 248
\iftrue	131	\the	77, 78, 79, 80, 81, 82, 83, 84, 97, 192, 212, 213
\ifx	15, 18, 21, 50, 58, 61, 108, 111, 158, 161, 164, 167, 222	\TMP@EnsureCode	94, 101, 102, 103, 104, 105
		\TMP@RequirePackage	109, 115
		W	
		\write	23, 52
		X	
		\x	14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87