

The `catchfile` package

Heiko Oberdiek*

2016/05/16 v1.7

Abstract

This package catches the contents of a file and puts it in a macro. It requires ε -TeX. Both L^AT_EX and plain T_EX are supported.

Contents

1	Documentation	2
2	Implementation	2
2.1	Reload check and package identification	2
2.2	Catcodes	3
2.3	Preparations	4
2.4	Looking for primitive <code>\input</code>	4
2.5	Input file check	5
2.6	Catch file contents	6
3	Test	7
3.1	Catcode checks for loading	7
3.2	L ^A T _E X	9
3.3	plain T _E X	11
4	Installation	12
4.1	Download	12
4.2	Bundle installation	13
4.3	Package installation	13
4.4	Refresh file name databases	13
4.5	Some details for the interested	13
5	History	14
	[2007/05/30 v1.0]	14
	[2007/09/09 v1.1]	14
	[2007/11/11 v1.2]	14
	[2010/03/01 v1.3]	14
	[2010/04/08 v1.4]	14
	[2010/04/28 v1.5]	14
	[2011/03/01 v1.6]	14
	[2016/05/16 v1.7]	14

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 Documentation

The package relies on ϵ -TeX's `\everyeof`. Otherwise it aborts with an error message.

```
\CatchFileDef {\cmd} {\file name} {\setup}
\CatchFileEdef {\cmd} {\file name} {\setup}
```

Macro `\cmd` is defined with the contents of file `\file name`. `\CatchFileDef` uses `\def`, `\CatchFileEdef` `\edef` for the definition. Additional setup code for setting catcodes or treatment of line ends can be given in code `\setup`. See the test files for an example.

2 Implementation

```
1 \*package)
```

2.1 Reload check and package identification

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@catchfile.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17 \def\empty{}%
18 \ifx\x\empty % LaTeX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
25 \else
26 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27 \fi
28 \x{catchfile}{The package is already loaded}%
29 \aftergroup\endinput
30 \fi
31 \fi
32 \endgroup%
```

Package identification:

```
33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^M
35 \endlinechar=13 %
36 \catcode35=6 % #
```

```

37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51   \def\x#1#2#3[#4]{\endgroup
52     \immediate\write-1{Package: #3 #4}%
53     \xdef#1{#4}%
54   }%
55 \else
56   \def\x#1#2[#3]{\endgroup
57     #2[#{#3}]%
58     \ifx#1\@undefined
59       \xdef#1{#3}%
60     \fi
61     \ifx#1\relax
62       \xdef#1{#3}%
63     \fi
64   }%
65 \fi
66 \expandafter\x\csname ver@catchfile.sty\endcsname
67 \ProvidesPackage{catchfile}%
68 [2016/05/16 v1.7 Catch the contents of a file (H0)]%

```

2.2 Catcodes

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^~M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76   \expandafter\edef\csname CatchFile@AtEnd\endcsname{%
77     \endlinechar=\the\endlinechar\relax
78     \catcode13=\the\catcode13\relax
79     \catcode32=\the\catcode32\relax
80     \catcode35=\the\catcode35\relax
81     \catcode61=\the\catcode61\relax
82     \catcode64=\the\catcode64\relax
83     \catcode123=\the\catcode123\relax
84     \catcode125=\the\catcode125\relax
85   }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^~M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @

```

```

92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95   \edef\CatchFile@AtEnd{%
96     \CatchFile@AtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{39}{12}% '
102 \TMP@EnsureCode{44}{12}% ,
103 \TMP@EnsureCode{45}{12}% -
104 \TMP@EnsureCode{46}{12}% .
105 \TMP@EnsureCode{47}{12}% /
106 \TMP@EnsureCode{91}{12}% [
107 \TMP@EnsureCode{93}{12}% ]
108 \TMP@EnsureCode{96}{12}% `
109 \edef\CatchFile@AtEnd{\CatchFile@AtEnd\noexpand\endinput}

```

2.3 Preparations

```

110 \begingroup\expandafter\expandafter\expandafter\endgroup
111 \expandafter\ifx\csname RequirePackage\endcsname\relax
112   \input infwarerr.sty\relax
113   \input ltxcmds.sty\relax
114 \else
115   \RequirePackage{infwarerr}[2007/09/09]%
116   \RequirePackage{ltxcmds}[2010/03/09]%
117 \fi

```

Check for ε -TeX's `\everyeof`.

```

118 \begingroup
119   \escapechar=92\relax
120   \edef\TestString{\string\everyeof}%
121   \edef\TestMeaning{\meaning\everyeof}%
122   \ifx\TestString\TestMeaning
123   \else
124     \@PackageError{catchfile}{%
125       Cannot find e-TeX's \string\everyeof, \MessageBreak
126       package loading is aborted%
127     }\@ehd
128   \endgroup
129   \expandafter\CatchFile@AtEnd
130 \fi%
131 \endgroup

```

2.4 Looking for primitive `\input`

`\CatchFile@Input` The package needs the expandable primitive `\input`. However there are formats that redefine it. For example, L^AT_EX's `\input` is not expandable, but it stores the primitive in `\@input`. The third possibility is `\pdfprimitive`, introduced in pdf_TE_X 1.40.0.

Thus we try to find the primitive and store it in `\CatchFile@Input`. If it is used, it must be expanded twice (because of the solution with `\pdfprimitive`).

```

132 \begingroup
133   \def\Check#1#2#3#4\endgroup{%
134     \edef\TestString{\string#1}%
135     \edef\TestMeaning{\meaning#2}%
136     \ifx\TestString\TestMeaning
137       \endgroup

```

```

138     \let\CatchFile@Primitive#2%
139     \def\CatchFile@Input{\CatchFile@Primitive#3}%
140     \else
141         #4\endgroup
142     \fi
143 }%
144 \Check\input\input{%
145 \Check\input\@@input{%
146 \Check\pdfprimitive\pdfprimitive\input
147 \@PackageError{%
148     Cannot find primitive \string\input,\MessageBreak
149     package loading is aborted%
150 }\@ehd
151 \csname endgroup\endcsname
152 \CatchFile@AtEnd%
153 \endgroup

```

2.5 Input file check

\CatchFile@CheckFileExists

```

154 \begingroup\expandafter\expandafter\expandafter\endgroup
155 \expandafter\ifx\csname IfFileExists\endcsname\relax
156     \input pdftexcmds.sty\relax
157 \begingroup\expandafter\expandafter\expandafter\endgroup
158 \expandafter\ifx\csname pdf@filesize\endcsname\relax
159     \def\CatchFile@CheckFileExists#1{%
160         \expandafter\ifx\csname @inputcheck\endcsname\relax
161             \csname newread\endcsname\@inputcheck
162         \fi
163         \openin\@inputcheck#1\relax
164         \expandafter\closein\expandafter\@inputcheck
165         \ifeof\@inputcheck
166             \let\CatchFile@File\relax
167         \else
168             \def\CatchFile@File{#1}%
169         \fi
170     }%
171 \else
172     \def\CatchFile@CheckFileExists#1{%
173         \expandafter\expandafter\expandafter\ifx
174         \expandafter\expandafter\expandafter\relax\pdf@filesize{#1}\relax
175         \let\CatchFile@File\relax
176     \else
177         \def\CatchFile@File{#1}%
178     \fi
179 }%
180 \fi
181 \else
182     \def\CatchFile@CheckFileExists#1{%
183         \IfFileExists{#1}{%
184             \expandafter\CatchFile@DefFile\@filef@und\@nil
185             \begingroup\expandafter\expandafter\expandafter\endgroup
186             \expandafter\ifx\csname @addtofilelist\endcsname\relax
187                 \else
188                     \@addtofilelist\CatchFile@File
189                 \fi
190             }{%
191                 \let\CatchFile@File\relax

```

```

192 }%
193 }%
194 \def\CatchFile@DefFile#1 \@nil{%
195 \def\CatchFile@File{#1}%
196 }%
197 \fi

```

\CatchFile@NotFound

```

198 \def\CatchFile@NotFound#1#2{%
199 \def#1{%
200 \@PackageError{catchfile}{%
201 File `#2' not found%
202 }\@ehc
203 }

```

2.6 Catch file contents

```

204 \ltx@ifundefined{RequirePackage}{%
205 \input etexcmds.sty\relax
206 }{%
207 \RequirePackage{etexcmds}[2010/01/28]%
208 }

```

\CatchFileEdef

```

209 \long\def\CatchFileEdef#1#2#3{%
210 \CatchFile@CheckFileExists{#2}%
211 \ifx\CatchFile@File\relax
212 \CatchFile@NotFound{#1}{#2}%
213 \else
214 \begingroup
215 \everyeof{\noexpand}%
216 #3%
217 \xdef\CatchFile@Contents{\CatchFile@Input\CatchFile@File\space}%
218 \endgroup
219 \let#1\CatchFile@Contents
220 \fi
221 }

```

\CatchFileDef

```

222 \long\def\CatchFileDef#1#2#3{%
223 \CatchFile@CheckFileExists{#2}%
224 \ifx\CatchFile@File\relax
225 \CatchFile@NotFound{#1}{#2}%
226 \else
227 \begingroup
228 \everyeof\expandafter{%
229 \CatchFile@EOF
230 \expandafter\CatchFile@Finish
231 \noexpand
232 }%
233 \ltx@ifundefined{etex@unexpanded}{%
234 \expandafter\long\expandafter\def\expandafter\CatchFile@Do
235 \expandafter##\expandafter1\CatchFile@EOF{%
236 \toks\ltx@zero{##1}%
237 \xdef\CatchFile@gtemp{\the\toks\ltx@zero}%
238 \def\CatchFile@Finish{%
239 \endgroup
240 \let#1\CatchFile@gtemp

```

```

241         \global\let\CatchFile@gtemp\ltx@undefined
242     }%
243 }%
244 }{%
245     \expandafter\long\expandafter\def\expandafter\CatchFile@Do
246         \expandafter##\expandafter1\CatchFile@EOF{%
247         \edef\CatchFile@Finish{%
248         \endgroup
249         \etex@unexpanded{%
250             \edef#1{\etex@unexpanded{##1}}%
251         }%
252     }%
253 }%
254 }%
255     #3\relax
256 \expandafter\expandafter\expandafter\CatchFile@Do
257 \CatchFile@Input\CatchFile@File\relax
258 \fi
259 }

```

\relax after #3 was added to make it more robust in case the user uses something like

```
\CatchFileDef{\content}{\jobname.tt}{\endlinechar=-1}
```

that expands the following \expandafter after #3 prematurely (contribution of Martin Scharrer).

`\CatchFile@EOF` If the file is read the catcode mappings are fixed. This means that the same character cannot occur inside the file with different catcodes. Thus we use as end of file marker the at sign twice with different catcodes.

```

260 \begingroup
261     \lccode65=64 % lowercase('A') = '@'
262     \lccode66=64 % lowercase('B') = '@'
263     \catcode65=8 % catcode('A') = subscript
264     \catcode66=3 % catcode('B') = math shift
265 \lowercase{\endgroup
266     \def\CatchFile@EOF{AB}%
267 }

268 \CatchFile@AtEnd%
269 \</package>

```

3 Test

3.1 Catcode checks for loading

```

270 \<*test1>
271 \catcode`\{=1 %
272 \catcode`\}=2 %
273 \catcode`\#=6 %
274 \catcode`\@=11 %
275 \expandafter\ifx\csname count@endcsname\relax
276     \countdef\count@=255 %
277 \fi
278 \expandafter\ifx\csname @gobble@endcsname\relax
279     \long\def\@gobble#1{%
280 \fi

```

```

281 \expandafter\ifx\csname @firstofone\endcsname\relax
282 \long\def\@firstofone#1{#1}%
283 \fi
284 \expandafter\ifx\csname loop\endcsname\relax
285 \expandafter\@firstofone
286 \else
287 \expandafter\@gobble
288 \fi
289 {%
290 \def\loop#1\repeat{%
291 \def\body{#1}%
292 \iterate
293 }%
294 \def\iterate{%
295 \body
296 \let\next\iterate
297 \else
298 \let\next\relax
299 \fi
300 \next
301 }%
302 \let\repeat=\fi
303 }%
304 \def\RestoreCatcodes{}
305 \count@=0 %
306 \loop
307 \edef\RestoreCatcodes{%
308 \RestoreCatcodes
309 \catcode\the\count@=\the\catcode\count@\relax
310 }%
311 \ifnum\count@<255 %
312 \advance\count@ 1 %
313 \repeat
314
315 \def\RangeCatcodeInvalid#1#2{%
316 \count@=#1\relax
317 \loop
318 \catcode\count@=15 %
319 \ifnum\count@<#2\relax
320 \advance\count@ 1 %
321 \repeat
322 }
323 \def\RangeCatcodeCheck#1#2#3{%
324 \count@=#1\relax
325 \loop
326 \ifnum#3=\catcode\count@
327 \else
328 \errmessage{%
329 Character \the\count@\space
330 with wrong catcode \the\catcode\count@\space
331 instead of \number#3%
332 }%
333 \fi
334 \ifnum\count@<#2\relax
335 \advance\count@ 1 %
336 \repeat
337 }
338 \def\space{ }

```



```

339 \expandafter\ifx\csname LoadCommand\endcsname\relax
340 \def\LoadCommand{\input catchfile.sty\relax}%
341 \fi
342 \def\Test{%
343 \RangeCatcodeInvalid{0}{47}%
344 \RangeCatcodeInvalid{58}{64}%
345 \RangeCatcodeInvalid{91}{96}%
346 \RangeCatcodeInvalid{123}{255}%
347 \catcode`\@=12 %
348 \catcode`\=0 %
349 \catcode`\%=14 %
350 \LoadCommand
351 \RangeCatcodeCheck{0}{36}{15}%
352 \RangeCatcodeCheck{37}{37}{14}%
353 \RangeCatcodeCheck{38}{47}{15}%
354 \RangeCatcodeCheck{48}{57}{12}%
355 \RangeCatcodeCheck{58}{63}{15}%
356 \RangeCatcodeCheck{64}{64}{12}%
357 \RangeCatcodeCheck{65}{90}{11}%
358 \RangeCatcodeCheck{91}{91}{15}%
359 \RangeCatcodeCheck{92}{92}{0}%
360 \RangeCatcodeCheck{93}{96}{15}%
361 \RangeCatcodeCheck{97}{122}{11}%
362 \RangeCatcodeCheck{123}{255}{15}%
363 \RestoreCatcodes
364 }
365 \Test
366 \csname @@end\endcsname
367 \end
368 </test1>

```

3.2 L^AT_EX

```

369 <*test2>
370 \NeedsTeXFormat{LaTeX2e}
371 \nofiles
372 \listfiles
373 \tracingnesting=2 %
374 \documentclass{minimal}
375 \usepackage{catchfile}[2016/05/16]
376 \makeatletter
377 \def\mysetup{%
378 \let\do\@makeother
379 \dospecials
380 }
381 \def\CheckContents{%
382 \begingroup
383 \expandafter\ifx\csname contents\endcsname\relax
384 \PackageError{TEST}{\string\contents\space is not defined}\@ehc
385 \fi
386 \endgroup
387 }
388 \def\StartDisableUnexpanded{%
389 \begingroup
390 \let\etex@unexpanded\@undefined
391 }
392 \def\StopDisableUnexpanded{%
393 \endgroup
394 }

```

```

395 \def\CheckCleanup{%
396   \begingroup
397   \edef\x{\the\toks0}%
398   \def\y{ABC}%
399   \ifx\x\y
400   \else
401     \PackageError{TEST}{\string\toks0 has changed}\@ehc
402   \fi
403   \ifx\CatchFile@gtemp\@undefined
404   \else
405     \PackageError{TEST}{Left over \string\CatchFile@gtemp}\@ehc
406   \fi
407   \endgroup
408 }
409 \def\Check{%
410   \CheckContents
411   \CheckCleanup
412 }
413 \makeatother
414 \begin{document}
415 \toks0{ABC}
416
417 \CatchFileDef\contents{catchfile.sty}\mysetup
418 \typeout{\meaning\contents}
419 \Check
420 \typeout{*****}%
421 \CatchFileDef\contents{catchfile.sty}{}
422 \typeout{\meaning\contents}
423 \Check
424 \typeout{*****}%
425
426 \StartDisableUnexpanded
427 \CatchFileDef\contents{catchfile.sty}\mysetup
428 \typeout{\meaning\contents}
429 \Check
430 \typeout{*****}%
431 \CatchFileDef\contents{catchfile.sty}{}
432 \typeout{\meaning\contents}
433 \Check
434 \typeout{*****}%
435 \StopDisableUnexpanded
436
437 \CatchFileEdef\contents{catchfile.sty}{%
438   \mysetup
439   \def\par{^^J}%
440   \obeylines
441 }
442 \typeout{\contents}
443 \Check
444 \typeout{*****}%
445 \CatchFileEdef\contents{catchfile.sty}{%
446   \catcode`\=12 %
447   \catcode`\#=12 %
448   \def\par{^^J}%
449   \obeylines
450 }
451 \typeout{\contents}
452 \Check

```

```

453 \typeout{*****}%
454 \end{document}
455 \end{test2}

```

3.3 plain T_EX

```

456 \begin{test3}
457 \def\msg#{\immediate\write16}
458 \newlinechar=10 %
459 \tracingnesting=2 %
460 \input catchfile.sty\relax
461
462 \def\mysetup{%
463   \def\do##1{%
464     \catcode`##1=12\relax
465   }%
466   \dospecials
467 }
468 \def\CheckContents{%
469   \begingroup
470     \expandafter\ifx\csname contents\endcsname\relax
471     \def\space{ }%
472     \errmessage{\string\contents\space is not defined.}%
473   \fi
474   \endgroup
475 }
476 \catcode`\@=11 %
477 \def\CheckCleanup{%
478   \begingroup
479     \edef\x{\the\toks0}%
480     \def\y{ABC}%
481     \ifx\x\y
482     \else
483       \errmessage{\string\toks0 has changed}%
484     \fi
485     \ifx\CatchFile@gtemp\@undefined
486     \else
487       \errmessage{Left over \string\CatchFile@gtemp}%
488     \fi
489   \endgroup
490 }
491 \def\Check{%
492   \CheckContents
493   \CheckCleanup
494 }
495 \def\StartDisableUnexpanded{%
496   \begingroup
497     \let\etex@unexpanded\@undefined
498 }
499 \def\StopDisableUnexpanded{%
500   \endgroup
501 }
502 \catcode`\@=12 %
503
504 \toks0{ABC}
505
506 \CatchFileDef\contents{catchfile.sty}\mysetup
507 \msg{\meaning\contents}
508 \Check

```

```

509 \msg{*****}%
510 \CatchFileDef\contents{catchfile.sty}{}
511 \msg{\meaning\contents}
512 \Check
513 \msg{*****}%
514
515 \StartDisableUnexpanded
516 \CatchFileDef\contents{catchfile.sty}\mysetup
517 \msg{\meaning\contents}
518 \Check
519 \msg{*****}%
520 \CatchFileDef\contents{catchfile.sty}{}
521 \msg{\meaning\contents}
522 \Check
523 \msg{*****}%
524 \StopDisableUnexpanded
525
526 \CatchFileEdef\contents{catchfile.sty}{%
527   \mysetup
528   \def\par{^^J}%
529   \obeylines
530 }
531 \msg{\contents}
532 \Check
533 \msg{*****}%
534 \CatchFileEdef\contents{catchfile.sty}{%
535   \catcode`\=12 %
536   \catcode`\#=12 %
537   \def\par{^^J}%
538   \obeylines
539 }
540 \msg{\contents}
541 \Check
542 \msg{*****}%
543
544 \csname @@end\endcsname
545 \end
546 </test3>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/catchfile.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/catchfile.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

¹[CTAN:pkg/catchfile](#)

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TEX`:

```
tex catchfile.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
catchfile.sty      → tex/generic/oberdiek/catchfile.sty
catchfile.pdf      → doc/latex/oberdiek/catchfile.pdf
test/catchfile-test1.tex → doc/latex/oberdiek/test/catchfile-test1.tex
test/catchfile-test2.tex → doc/latex/oberdiek/test/catchfile-test2.tex
test/catchfile-test3.tex → doc/latex/oberdiek/test/catchfile-test3.tex
catchfile.dtx      → source/latex/oberdiek/catchfile.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TEX` distribution (`teTEX`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `teTEX` users run `texhash` or `mktextlsr`.

4.5 Some details for the interested

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain `TEX`: Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{catchfile.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex_catchfile.dtx
makeindex_s_gind.ist_catchfile.idx
pdflatex_catchfile.dtx
makeindex_s_gind.ist_catchfile.idx
pdflatex_catchfile.dtx
```

5 History

[2007/05/30 v1.0]

- First version.

[2007/09/09 v1.1]

- Catcode section rewritten.

[2007/11/11 v1.2]

- Use of package `pdfTeXcmds` for Lua_TE_X support.

[2010/03/01 v1.3]

- Fix for unknown `\@PackageErrorNoLine`.

[2010/04/08 v1.4]

- `\closein` also added if `\ifeof` is true.

[2010/04/28 v1.5]

- `\CatchFileDef`: Getting rid of warning ‘end of semi simple group entered at line ... of a different file (Florent Chervet).
- `\CatchFileDef`: Fix for error ‘Illegal parameter number in definition of ...’ (HO) including improvement that uses `\unexpanded` if available (Florent Chervet).

[2011/03/01 v1.6]

- `\relax` added after the setup argument of `\CatchFileDef` to prevent premature file reading (Martin Scharrer).

[2016/05/16 v1.7]

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
\#	273, 447, 536
\%	349
\@	274, 347, 476, 502
\@input	145
\@PackageError	124, 147, 200
\@addtofilelist	188
\@ehc	202, 384, 401, 405
\@ehd	127, 150
\@filef@und	184
\@firstofone	282, 285
\@gobble	279, 287
\@inputcheck	161, 163, 164, 165
\@makeother	378
\@nil	184, 194
\@undefined	58, 390, 403, 485, 497
\\	348, 446, 535
\{	271
\}	272
A	
\advance	312, 320, 335
\aftergroup	29
B	
\begin	414
\body	291, 295
C	
\CatchFile@AtEnd	95, 96, 109, 129, 152, 268
\CatchFile@CheckFileExists	154, 210, 223
\CatchFile@Contents	217, 219
\CatchFile@DefFile	184, 194
\CatchFile@Do	234, 245, 256
\CatchFile@EOF	229, 235, 246, <u>260</u>
\CatchFile@File	166, 168, 175, 177, 188, 191, 195, 211, 217, 224, 257
\CatchFile@Finish	230, 238, 247
\CatchFile@gttemp	237, 240, 241, 403, 405, 485, 487
\CatchFile@Input	<u>132</u> , 217, 257
\CatchFile@NotFound	<u>198</u> , 212, 225
\CatchFile@Primitive	138, 139
\CatchFileDef	2, <u>222</u> , 417, 421, 427, 431, 506, 510, 516, 520
\CatchFileEdef	<u>209</u> , 437, 445, 526, 534
\catcode	2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 69, 70, 72, 73, 74, 78, 79, 80, 81, 82, 83, 84, 87, 88, 90, 91, 92, 93, 97, 99, 263, 264, 271, 272, 273, 274, 309, 318, 326, 330, 347, 348, 349, 446, 447, 464, 476, 502, 535, 536
\Check	133, 144, 145, 146, 409, 419, 423, 429, 433, 443, 452, 491, 508, 512, 518, 522, 532, 541
\CheckCleanup	395, 411, 477, 493
\CheckContents	381, 410, 468, 492
\closein	164
\contents	384, 417, 418, 421, 422, 427, 428, 431, 432, 437, 442, 445, 451, 472, 506, 507, 510, 511, 516, 517, 520, 521, 526, 531, 534, 540
\count@	276, 305, 309, 311, 312, 316, 318, 319, 320, 324, 326, 329, 330, 334, 335
\countdef	276
\csname	14, 21, 50, 66, 76, 111, 151, 155, 158, 160, 161, 186, 275, 278, 281, 284, 339, 366, 383, 470, 544
D	
\do	378, 463
\documentclass	374
\dospecials	379, 466
E	
\empty	17, 18
\end	367, 454, 545
\endcsname	14, 21, 50, 66, 76, 111, 151, 155, 158, 160, 161, 186, 275, 278, 281, 284, 339, 366, 383, 470, 544
\endinput	29, 109
\endlinechar	4, 35, 71, 77, 89
\errmessage	328, 472, 483, 487
\escapechar	119
\etex@unexpanded	249, 250, 390, 497
\everyeof	120, 121, 125, 215, 228
I	
\ifeof	165
\IfFileExists	183
\ifnum	311, 319, 326, 334
\ifx	15, 18, 21, 50, 58, 61, 111, 122, 136, 155, 158, 160, 173, 186, 211, 224, 275, 278, 281, 284, 339, 383, 399, 403, 470, 481, 485

\immediate	23, 52, 457		
\input	112, 113, 144, 145, 146, 148, 156, 205, 340, 460		
\iterate	292, 294, 296		
L			
\lccode	261, 262		
\listfiles	372		
\LoadCommand	340, 350		
\loop	290, 306, 317, 325		
\lowercase	265		
\ltx@ifundefined	204		
\ltx@ifundefined	233		
\ltx@undefined	241		
\ltx@zero	236, 237		
M			
\makeatletter	376		
\makeatother	413		
\meaning	121, 135, 418, 422, 428, 432, 507, 511, 517, 521		
\MessageBreak	125, 148		
\msg	457, 507, 509, 511, 513, 517, 519, 521, 523, 531, 533, 540, 542		
\mysetup	377, 417, 427, 438, 462, 506, 516, 527		
N			
\NeedsTeXFormat	370		
\newlinechar	458		
\next	296, 298, 300		
\nofiles	371		
\number	331		
O			
\obeylines	440, 449, 529, 538		
\openin	163		
P			
\PackageError	384, 401, 405		
\PackageInfo	26		
\par	439, 448, 528, 537		
\pdf@filesize	174		
\pdfprimitive	146		
\ProvidesPackage	19, 67		
R			
\RangeCatcodeCheck	323, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362		
\RangeCatcodeInvalid	315, 343, 344, 345, 346		
\repeat	290, 302, 313, 321, 336		
\RequirePackage	115, 116, 207		
\RestoreCatcodes	304, 307, 308, 363		
S			
\space	217, 329, 330, 338, 384, 471, 472		
\StartDisableUnexpanded	388, 426, 495, 515		
\StopDisableUnexpanded	392, 435, 499, 524		
T			
\Test	342, 365		
\TestMeaning	121, 122, 135, 136		
\TestString	120, 122, 134, 136		
\the	77, 78, 79, 80, 81, 82, 83, 84, 97, 237, 309, 329, 330, 397, 479		
\TMP@EnsureCode	94, 101, 102, 103, 104, 105, 106, 107, 108		
\toks	236, 237, 397, 401, 415, 479, 483, 504		
\tracingnesting	373, 459		
\typeout	418, 420, 422, 424, 428, 430, 432, 434, 442, 444, 451, 453		
U			
\usepackage	375		
W			
\write	23, 52, 457		
X			
\x	14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87, 397, 399, 479, 481		
Y			
\y	398, 399, 480, 481		