

The `hologo` package

Heiko Oberdiek*

2017/05/01 v1.13

Abstract

This package starts a collection of logos with support for bookmarks strings.

Contents

1	Documentation	3
1.1	Logo macros	3
1.2	Setup macros	4
1.3	Options	5
1.4	Driver options	5
1.5	Font setup	6
1.5.1	Font order	6
1.6	Additional user macros	7
1.7	Supported contexts	7
1.8	Example	7
2	Implementation	10
2.1	Logo list	12
2.2	Load resources	13
2.3	Setup macros	14
2.4	Options	14
2.5	Break/no-break support	16
2.6	Font support	17
2.6.1	Font defaults	18
2.6.2	Font setup	20
2.7	Generic logo commands	21
2.7.1	<code>\hologo</code> and friends	21
2.7.2	<code>\hologoRobust</code> and friends	23
2.8	Helpers	25
2.8.1	Text subscript	26
2.9	$\mathrm{T}_\mathrm{E}\mathrm{X}$ and friends	27
2.9.1	$\mathrm{T}_\mathrm{E}\mathrm{X}$	27
2.9.2	plain $\mathrm{T}_\mathrm{E}\mathrm{X}$	28
2.9.3	$\mathrm{L}^{\mathrm{A}}\mathrm{T}_\mathrm{E}\mathrm{X}$	29
2.9.4	$(\mathrm{L}^{\mathrm{A}})\mathrm{T}_\mathrm{E}\mathrm{X}$	30
2.9.5	$\mathrm{L}^{\mathrm{A}}\mathrm{T}_\mathrm{E}\mathrm{X} 2_{\epsilon}$	32
2.9.6	$\mathrm{L}^{\mathrm{A}}\mathrm{T}_\mathrm{E}\mathrm{X} 3$	33
2.9.7	$\mathrm{L}^{\mathrm{A}}\mathrm{T}_\mathrm{E}\mathrm{X} \mathrm{ML}$	34

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

2.9.8	ε -TeX	34
2.9.9	iniTeX	35
2.9.10	virTeX	35
2.9.11	SLiTeX	36
2.9.12	LuaTeX	39
2.9.13	Lua ^{LA} TeX	39
2.9.14	X _q TeX, X _q ^{LA} TeX	39
2.9.15	pdfTeX, pdf ^{LA} TeX	44
2.9.16	VTeX	44
2.9.17	$\mathcal{A}\mathcal{M}\mathcal{S}$, ...	45
2.9.18	B _W TeX	46
2.9.19	B _W TeX8	48
2.9.20	ConTeXt	48
2.9.21	emTeX	49
2.9.22	ε_X TeX	50
2.9.23	MiKTeX	51
2.9.24	OzTeX and friends	51
2.9.25	PCTeX	52
2.9.26	PiCTeX	52
2.9.27	teTeX	54
2.9.28	TeX4ht	54
2.9.29	SageTeX	54
2.10	METAFONT and friends	54
2.11	Others	55
2.11.1	biber	55
2.11.2	KOMA-Script	55
2.11.3	LyX	57
2.11.4	$\mathcal{N}\mathcal{T}\mathcal{S}$	57
2.11.5	T _T H (TeX to HTML translator)	58
2.11.6	Hàn Thế Thành	58
2.12	Driver detection	59
2.12.1	Reflect box macros	62
3	Test	64
3.1	Catcode checks for loading	64
3.2	Spacefactor	66
3.3	Complete list	67
4	Installation	68
4.1	Download	68
4.2	Bundle installation	69
4.3	Package installation	69
4.4	Refresh file name databases	69
4.5	Some details for the interested	69
5	References	70
6	History	70
	[2010/04/08 v1.0]	70
	[2010/04/16 v1.1]	70
	[2010/04/24 v1.2]	71
	[2010/11/21 v1.3]	71
	[2011/03/25 v1.4]	71
	[2011/04/21 v1.5]	71

[2011/10/01 v1.6]	71
[2011/11/22 v1.7]	71
[2011/11/29 v1.8]	71
[2011/12/21 v1.9]	71
[2012/04/26 v1.10]	72
[2016/05/12 v1.11]	72
[2016/05/16 v1.12]	72
[2017/05/01 v1.13]	72

1 Documentation

1.1 Logo macros

`\hologo {⟨name⟩}`

Macro `\hologo` sets the logo with name `⟨name⟩`. The following table shows the supported names.

name	variant	logo	since
(La)TeX		(L)TeX	2011/10/01
AmSLaTeX		$\mathcal{A}\mathcal{M}\mathcal{S}$ -L _{ATEX}	2010/04/16
AmSTeX		$\mathcal{A}\mathcal{M}\mathcal{S}$ -T _{EX}	2010/04/16
biber		biber	2011/10/01
BibTeX		B _{IB} T _{EX}	2011/10/01
BibTeX	sf	B _{IB} T _{EX}	2011/10/01
BibTeX	sc	B _{IB} T _{EX}	2011/10/01
BibTeX8		B _{IB} T _{EX} 8	2011/11/22
ConTeXt		ConT _{EX} t	2011/03/25
ConTeXt	narrow	ConT _{EX} t	2011/03/25
ConTeXt	simple	ConT _{EX} t	2011/03/25
emTeX		emT _{EX}	2010/04/26
eTeX		ε -T _{EX}	2010/04/08
ExTeX		ε_X -T _{EX}	2011/10/01
HànThếThành		Hàn Thế Thành	2011/11/29
iniTeX		iniT _{EX}	2011/10/01
KOMAScript		KOMA-Script	2011/10/01
La		L ^A	2010/05/08
LaTeX		L ^A T _{EX}	2010/04/08
LaTeX2e		L ^A T _{EX} 2 _{ε}	2010/04/08
LaTeX3		L ^A T _{EX} 3	2010/04/24
LaTeXe		L ^A T _{EX} 2 _{ε}	2010/04/08
LaTeXML		L ^A T _{EX} ML	2011/11/22
LaTeXTeX		(L)TeX	2011/10/01
LuaLaTeX		LuaL ^A T _{EX}	2010/04/08
LuaTeX		LuaT _{EX}	2010/04/08
LyX		L _Y X	2011/10/01
METAFONT		METAFONT	2011/10/01
MetaFun		MetaFun	2011/10/01
METAPOST		METAPOST	2011/10/01
MetaPost		MetaPost	2011/10/01
MiKTeX		MiK _T EX	2011/10/01
NTS		$\mathcal{N}\mathcal{T}\mathcal{S}$	2011/10/01

name	variant	logo	since
OzMF		OzMF	2011/10/01
OzMP		OzMP	2011/10/01
OzTeX		OzTeX	2011/10/01
OzTtH		OzTtH	2011/10/01
PCTeX		PCTeX	2011/10/01
pdfTeX		pdfTeX	2011/10/01
pdfLaTeX		pdfLaTeX	2011/10/01
PiC		PiC	2011/10/01
PiCTeX		PiCTeX	2011/10/01
plainTeX		plain TeX	2010/04/08
plainTeX	space	plain TeX	2010/04/16
plainTeX	hyphen	plain-TeX	2010/04/16
plainTeX	runtogether	plainTeX	2010/04/16
SageTeX		SageTeX	2011/11/22
SLiTeX		SLiTeX	2011/10/01
SLiTeX	lift	SLiTeX	2011/10/01
SLiTeX	narrow	SLiTeX	2011/10/01
SLiTeX	simple	SLiTeX	2011/10/01
SliTeX		SliTeX	2011/10/01
SliTeX	narrow	SliTeX	2011/10/01
SliTeX	simple	SliTeX	2011/10/01
SliTeX	lift	SliTeX	2011/10/01
teTeX		teTeX	2011/10/01
TeX		TeX	2010/04/08
TeX4ht		TeX4ht	2011/11/22
TTH		T _T H	2011/11/22
virTeX		virTeX	2011/10/01
VTeX		VTeX	2010/04/24
Xe		X _E	2010/04/08
XeLaTeX		X _E LaTeX	2010/04/08
XeTeX		X _E TeX	2010/04/08

`\Hologo {⟨name⟩}`

Macro `\Hologo` starts the logo $\langle name \rangle$ with an uppercase letter. As an exception small greek letters are not converted to uppercase. Examples, see ε -TeX and ε_X TeX.

1.2 Setup macros

The package does not support package options, but the following setup macros can be used to set options.

`\hologoSetup {⟨key value list⟩}`

Macro `\hologoSetup` sets global options.

`\hologoLogoSetup {⟨logo⟩} {⟨key value list⟩}`

Some options can also be used to configure a logo. These settings take precedence over global option settings.

1.3 Options

There are boolean and string options:

Boolean option: It takes `true` or `false` as value. If the value is omitted, then `true` is used.

String option: A value must be given as string. (But the string might be empty.)

The following options can be used both in `\hologoSetup` and `\hologoLogoSetup`:

break: enables or disables line breaks inside the logo. This setting is refined by options `hyphenbreak`, `spacebreak` or `discretionarybreak`. Default is `false`.

hyphenbreak: enables or disables the line break right after the hyphen character.

spacebreak: enables or disables line breaks at space characters.

discretionarybreak: enables or disables line breaks at hyphenation points (inserted by `\-`).

Macro `\hologoLogoSetup` also knows:

variant: This is a string option. It specifies a variant of a logo that must exist. An empty string selects the package default variant.

Example:

```
\hologoSetup{break=false}  
\hologoLogoSetup{plainTeX}{variant=hyphen,hyphenbreak}  
Then “plain-TeX” contains one break point after the hyphen.
```

1.4 Driver options

Sometimes graphical operations are needed to construct some glyphs (e.g. $\text{\X}\text{\TeX}$). If package `graphics` or package `pgf` are found, then the macros are taken from there. Otherwise the package defines its own operations and therefore needs the driver information. Many drivers are detected automatically (`pdfTeX`/`LuaTeX` in PDF mode, `XYTeX`, `VTeX`). These have precedence over a driver option. The driver can be given as package option or using `\hologoDriverSetup`. The following list contains the recognized driver options:

- `pdftex`, `luatex`
- `dvipdfm`, `dvipdfmx`
- `dvips`, `dvipsone`, `xdvi`
- `xetex`
- `vtex`

The left driver of a line is the driver name that is used internally. The following names are aliases for drivers that use the same method. Therefore the entry in the `.log` file for the used driver prints the internally used driver name.

driverfallback: This option expects a driver that is used, if the driver could not be detected automatically.

`\hologoDriverSetup {(<driver option>)}`

The driver can also be configured after package loading using `\hologoDriverSetup`, also the way for plain `TeX` to setup the driver.

1.5 Font setup

Some logos require a special font, but should also be usable by plain \TeX . Therefore the package provides some ways to influence the font settings. The options below take font settings as values. Both font commands such as \sf sf and macros that take one argument like $\text{\textsf{textsf}}$ can be used.

$\text{\hologoFontSetup}\{\langle key\ value\ list\rangle\}$

Macro \hologoFontSetup sets the fonts for all logos. Supported keys:

general: This font is used for all logos. The default is empty. That means no special font is used.

bibsf: This font is used for BibTeX with variant sf .

rm: This font is a serif font. It is used for \varepsilon_XTeX .

sc: This font specifies a small caps font. It is used for BibTeX with variant sc .

sf: This font specifies a sans serif font. The default is \sf sf , then \sf is tried. Otherwise a warning is given. It is used by KOMA-Script.

sy: This is the font for math symbols (e.g. cmsy). It is used by \mathcal{AMS} , \mathcal{NTS} , \varepsilon_XTeX .

logo: METAFONT and METAPOST are using that font. In \LaTeX \logofamily is used and the definitions of package mflogo are used if the package is not loaded. Otherwise the \tenlogo is used and defined if it does not already exists.

$\text{\hologoLogoFontSetup}\{\langle logo\rangle\}\{\langle key\ value\ list\rangle\}$

Fonts can also be set for a logo or logo component separately, see the following list. The keys are the same as for \hologoFontSetup .

$\langle logo\rangle$	keys	result
BibTeX	bibsf	BibTeX
BibTeX	sc	BibTeX
ExTeX	rm	\varepsilon_XTeX
SlitTeX	rm	SlitTeX
AmS	sy	\mathcal{AMS}
ExTeX	sy	\varepsilon_XTeX
NTS	sy	\mathcal{NTS}
KOMAScript	sf	KOMA-Script
METAFONT	logo	METAFONT
METAPOST	logo	METAPOST
SlitTeX	sc SlitTeX	

1.5.1 Font order

For all logos the font **general** is applied first. Example:

$\text{\hologoFontSetup}\{\text{general}=\text{\color{red}}\}$

will print red logos. Then if the font uses a special font `sf`, for example, the font is applied that is setup by `\hologoLogoFontSetup`. If this font is not setup, then the common font setup by `\hologoFontSetup` is used. Otherwise a warning is given, that there is no font configured.

1.6 Additional user macros

Usually a variant of a logo is configured by using `\hologoLogoSetup`, because it is bad style to mix different variants of the same logo in the same text. There the following macros are a convenience for testing.

```
\hologoVariant {\langle name \rangle} {\langle variant \rangle}
\HologoVariant {\langle name \rangle} {\langle variant \rangle}
```

Logo `\langle name \rangle` is set using `\langle variant \rangle` that specifies explicitly which variant of the macro is used. If the argument is empty, then the default form of the logo is used (configurable by `\hologoLogoSetup`).

`\HologoVariant` is used if the logo is set in a context that needs an uppercase first letter (beginning of a sentence, ...).

```
\hologoList
\hologoEntry {\langle logo \rangle} {\langle variant \rangle} {\langle since \rangle}
```

Macro `\hologoList` contains all logos that are provided by the package including variants. The list consists of calls of `\hologoEntry` with three arguments starting with the logo name `\langle logo \rangle` and its variant `\langle variant \rangle`. An empty variant means the current default. Argument `\langle since \rangle` specifies with version of the package `hologo` is needed to get the logo. If the logo is fixed, then the date gets updated. Therefore the date `\langle since \rangle` is not exactly the date of the first introduction, but rather the date of the latest fix.

Before `\hologoList` can be used, macro `\hologoEntry` needs a definition. The example file in section 1.8 shows applications of `\hologoList`.

1.7 Supported contexts

Macros `\hologo` and friends support special contexts:

- L^AT_EX's protection mechanism.
- Bookmarks of package `hyperref`.
- Package `tex4ht`.
- The macros can be used inside `\csname` constructs, if `\ifincsn` is available (pdfT_EX, X_YT_EX, LuaT_EX).

1.8 Example

The following example prints the logos in different fonts.

```
1 \documentclass{article}
2 %<<verbatim
3 \NeedsTeXFormat{LaTeX2e}
4 \documentclass[a4paper]{article}
5 \usepackage[
6   hmargin=20mm,
```

```

7   vmargin=20mm,
8 ]{geometry}
9 \pagestyle{empty}
10 \usepackage{hologo}[2017/05/01]
11 \usepackage{longtable}
12 \usepackage{array}
13 \setlength{\extrarowheight}{2pt}
14 \usepackage[T1]{fontenc}
15 \usepackage{lmodern}
16 \usepackage{pdflscape}
17 \usepackage[
18   pdfencoding=auto,
19 ]{hyperref}
20 \hypersetup{
21   pdfauthor={Heiko Oberdiek},
22   pdftitle={Example for package `hologo'},
23   pdfsubject={Logos with fonts lmr, lmss, qtm, qpl, qhv},
24 }
25 \usepackage{bookmark}
26
27 % Print the logo list on the console
28
29 \begin{group}
30   \typeout{}%
31   \typeout{*** Begin of logo list ***}%
32   \newcommand*{\hologoEntry}[3]{%
33     \typeout{#1 \ifx\#2\\\else(#2) \fi[#3]}%
34   }%
35   \hologoList
36   \typeout{*** End of logo list ***}%
37   \typeout{}%
38 \end{group}
39
40 \begin{document}
41 \begin{landscape}
42
43   \section{Example file for package `hologo'}
44
45   % Table for font names
46
47   \begin{longtable}{>{\bfseries}ll}
48     \textbf{font} & \textbf{Font name}\\
49     \hline
50     lmr & Latin Modern Roman\\
51     lmss & Latin Modern Sans\\
52     qtm & \TeX\ Gyre Termes\\
53     qhv & \TeX\ Gyre Heros\\
54     qpl & \TeX\ Gyre Pagella\\
55   \end{longtable}
56
57   % Logo list with logos in different fonts
58
59   \begin{group}
60     \newcommand*{\SetVariant}[2]{%
61       \ifx\#2\\%
62       \else
63         \hologoLogoSetup{#1}{variant=#2}%
64       \fi

```



```

65 }%
66 \newcommand*{\hologoEntry}[3]{%
67   \SetVariant{#1}{#2}%
68   \raisebox{1em}[0pt][0pt]{\hypertarget{#1@#2}{}}%
69   \bookmark[%
70     dest={#1@#2},%
71   ]{%
72     #1\ifx\\#2\\else\space(#2)\fi: \Hologo{#1}, \hologo{#1} %
73     [Unicode]%
74   }%
75   \hypersetup{unicode=false}%
76   \bookmark[%
77     dest={#1@#2},%
78   ]{%
79     #1\ifx\\#2\\else\space(#2)\fi: \Hologo{#1}, \hologo{#1} %
80     [PDFDocEncoding]%
81   }%
82   \texttt{#1}%
83   &%
84   \texttt{#2}%
85   &%
86   \Hologo{#1}%
87   &%
88   \SetVariant{#1}{#2}%
89   \hologo{#1}%
90   &%
91   \SetVariant{#1}{#2}%
92   \fontfamily{qtm}\selectfont
93   \hologo{#1}%
94   &%
95   \SetVariant{#1}{#2}%
96   \fontfamily{qpl}\selectfont
97   \hologo{#1}%
98   &%
99   \SetVariant{#1}{#2}%
100  \textsf{\hologo{#1}}%
101  &%
102  \SetVariant{#1}{#2}%
103  \fontfamily{qhv}\selectfont
104  \hologo{#1}%
105  \tabularnewline
106 }%
107 \begin{longtable}{llllllll}%
108   \textbf{\textit{logo}} & \textbf{\textit{variant}} & & & & & & & \\
109   \texttt{\string\Hologo} & & & & & & & & \\
110   \textbf{lmr} & \textbf{qtm} & \textbf{qpl} & & & & & & \\
111   \textbf{lmss} & \textbf{qhv} & & & & & & & \\
112   \tabularnewline
113   \hline
114   \endhead
115   \hologoList
116 \end{longtable}%
117 \endgroup
118
119 \end{landscape}
120 \end{document}
121 %verbatim
122 /example>

```

2 Implementation

123 `\package`

Reload check, especially if the package is not used with L^AT_EX.

```

124 \begingroup\catcode61\catcode48\catcode32=10\relax%
125   \catcode13=5 % ^^M
126   \endlinechar=13 %
127   \catcode35=6 % #
128   \catcode39=12 % '
129   \catcode44=12 % ,
130   \catcode45=12 % -
131   \catcode46=12 % .
132   \catcode58=12 % :
133   \catcode64=11 % @
134   \catcode123=1 % {
135   \catcode125=2 % }
136   \expandafter\let\expandafter\x\csname ver@hologo.sty\endcsname
137   \ifx\x\relax % plain-TeX, first loading
138   \else
139     \def\empty{}%
140     \ifx\x\empty % LaTeX, first loading,
141       % variable is initialized, but \ProvidesPackage not yet seen
142     \else
143       \expandafter\ifx\csname PackageInfo\endcsname\relax
144         \def\x#1#2{%
145           \immediate\write-1{Package #1 Info: #2.}%
146         }%
147       \else
148         \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
149       \fi
150       \x{hologo}{The package is already loaded}%
151       \aftergroup\endinput
152     \fi
153   \fi
154 \endgroup%
```

Package identification:

```

155 \begingroup\catcode61\catcode48\catcode32=10\relax%
156   \catcode13=5 % ^^M
157   \endlinechar=13 %
158   \catcode35=6 % #
159   \catcode39=12 % '
160   \catcode40=12 % (
161   \catcode41=12 % )
162   \catcode44=12 % ,
163   \catcode45=12 % -
164   \catcode46=12 % .
165   \catcode47=12 % /
166   \catcode58=12 % :
167   \catcode64=11 % @
168   \catcode91=12 % [
169   \catcode93=12 % ]
170   \catcode123=1 % {
171   \catcode125=2 % }
172   \expandafter\ifx\csname ProvidesPackage\endcsname\relax
173     \def\x#1#2#3[#4]{\endgroup
174       \immediate\write-1{Package: #3 #4}%
175       \xdef#1{#4}%
176     }%
```

```

177 \else
178   \def\x#1#2[#3]{\endgroup
179     #2[#3]}%
180   \ifx#1\@undefined
181     \xdef#1[#3]%
182   \fi
183   \ifx#1\relax
184     \xdef#1[#3]%
185   \fi
186 }%
187 \fi
188 \expandafter\x\csname ver@hologo.sty\endcsname
189 \ProvidesPackage{hologo}%
190 [2017/05/01 v1.13 A logo collection with bookmark support (H0)]%
191 \begingroup\catcode61\catcode48\catcode32=10\relax%
192 \catcode13=5 % ^~M
193 \endlinechar=13 %
194 \catcode123=1 % {
195 \catcode125=2 % }
196 \catcode64=11 % @
197 \def\x{\endgroup
198   \expandafter\edef\csname HOLOGO@AtEnd\endcsname{%
199     \endlinechar=\the\endlinechar\relax
200     \catcode13=\the\catcode13\relax
201     \catcode32=\the\catcode32\relax
202     \catcode35=\the\catcode35\relax
203     \catcode61=\the\catcode61\relax
204     \catcode64=\the\catcode64\relax
205     \catcode123=\the\catcode123\relax
206     \catcode125=\the\catcode125\relax
207   }%
208 }%
209 \x\catcode61\catcode48\catcode32=10\relax%
210 \catcode13=5 % ^~M
211 \endlinechar=13 %
212 \catcode35=6 % #
213 \catcode64=11 % @
214 \catcode123=1 % {
215 \catcode125=2 % }
216 \def\TMP@EnsureCode#1#2{%
217   \edef\HOLOGO@AtEnd{%
218     \HOLOGO@AtEnd
219     \catcode#1=\the\catcode#1\relax
220   }%
221   \catcode#1=#2\relax
222 }
223 \TMP@EnsureCode{10}{12}% ^~J
224 \TMP@EnsureCode{33}{12}% !
225 \TMP@EnsureCode{34}{12}% "
226 \TMP@EnsureCode{36}{3}% $
227 \TMP@EnsureCode{38}{4}% &
228 \TMP@EnsureCode{39}{12}% '
229 \TMP@EnsureCode{40}{12}% (
230 \TMP@EnsureCode{41}{12}% )
231 \TMP@EnsureCode{42}{12}% *
232 \TMP@EnsureCode{43}{12}% +
233 \TMP@EnsureCode{44}{12}% ,
234 \TMP@EnsureCode{45}{12}% -

```

```

235 \TMP@EnsureCode{46}{12}% .
236 \TMP@EnsureCode{47}{12}% /
237 \TMP@EnsureCode{58}{12}% :
238 \TMP@EnsureCode{59}{12}% ;
239 \TMP@EnsureCode{60}{12}% <
240 \TMP@EnsureCode{62}{12}% >
241 \TMP@EnsureCode{63}{12}% ?
242 \TMP@EnsureCode{91}{12}% [
243 \TMP@EnsureCode{93}{12}% ]
244 \TMP@EnsureCode{94}{7}% ^ (superscript)
245 \TMP@EnsureCode{95}{8}% _ (subscript)
246 \TMP@EnsureCode{96}{12}% `
247 \TMP@EnsureCode{124}{12}% |
248 \edef\Hologo@AtEnd{%
249   \Hologo@AtEnd
250   \escapechar\the\escapechar\relax
251   \noexpand\endinput
252 }
253 \escapechar=92 %

```

2.1 Logo list

\hologoList

```

254 \def\hologoList{%
255   \hologoEntry{(La)TeX}{-}{2011/10/01}%
256   \hologoEntry{AmSLaTeX}{-}{2010/04/16}%
257   \hologoEntry{AmSTeX}{-}{2010/04/16}%
258   \hologoEntry{biber}{-}{2011/10/01}%
259   \hologoEntry{BibTeX}{-}{2011/10/01}%
260   \hologoEntry{BibTeX}{sf}{2011/10/01}%
261   \hologoEntry{BibTeX}{sc}{2011/10/01}%
262   \hologoEntry{BibTeX8}{-}{2011/11/22}%
263   \hologoEntry{ConTeXt}{-}{2011/03/25}%
264   \hologoEntry{ConTeXt}{narrow}{2011/03/25}%
265   \hologoEntry{ConTeXt}{simple}{2011/03/25}%
266   \hologoEntry{emTeX}{-}{2010/04/26}%
267   \hologoEntry{eTeX}{-}{2010/04/08}%
268   \hologoEntry{ExTeX}{-}{2011/10/01}%
269   \hologoEntry{HanTheThanh}{-}{2011/11/29}%
270   \hologoEntry{iniTeX}{-}{2011/10/01}%
271   \hologoEntry{KOMAScript}{-}{2011/10/01}%
272   \hologoEntry{La}{-}{2010/05/08}%
273   \hologoEntry{LaTeX}{-}{2010/04/08}%
274   \hologoEntry{LaTeX2e}{-}{2010/04/08}%
275   \hologoEntry{LaTeX3}{-}{2010/04/24}%
276   \hologoEntry{LaTeXe}{-}{2010/04/08}%
277   \hologoEntry{LaTeXML}{-}{2011/11/22}%
278   \hologoEntry{LaTeXTeX}{-}{2011/10/01}%
279   \hologoEntry{LuaLaTeX}{-}{2010/04/08}%
280   \hologoEntry{LuaTeX}{-}{2010/04/08}%
281   \hologoEntry{LyX}{-}{2011/10/01}%
282   \hologoEntry{METAfont}{-}{2011/10/01}%
283   \hologoEntry{MetaFun}{-}{2011/10/01}%
284   \hologoEntry{METAPOST}{-}{2011/10/01}%
285   \hologoEntry{MetaPost}{-}{2011/10/01}%
286   \hologoEntry{MiKTeX}{-}{2011/10/01}%
287   \hologoEntry{NTS}{-}{2011/10/01}%
288   \hologoEntry{OzMF}{-}{2011/10/01}%
289   \hologoEntry{OzMP}{-}{2011/10/01}%

```

```

290 \hologoEntry{OzTeX}{-}{2011/10/01}%
291 \hologoEntry{OzTtH}{-}{2011/10/01}%
292 \hologoEntry{PCTeX}{-}{2011/10/01}%
293 \hologoEntry{pdfTeX}{-}{2011/10/01}%
294 \hologoEntry{pdfLaTeX}{-}{2011/10/01}%
295 \hologoEntry{PiC}{-}{2011/10/01}%
296 \hologoEntry{PiCTeX}{-}{2011/10/01}%
297 \hologoEntry{plainTeX}{-}{2010/04/08}%
298 \hologoEntry{plainTeX}{space}{2010/04/16}%
299 \hologoEntry{plainTeX}{hyphen}{2010/04/16}%
300 \hologoEntry{plainTeX}{runtogether}{2010/04/16}%
301 \hologoEntry{SageTeX}{-}{2011/11/22}%
302 \hologoEntry{SLiTeX}{-}{2011/10/01}%
303 \hologoEntry{SLiTeX}{lift}{2011/10/01}%
304 \hologoEntry{SLiTeX}{narrow}{2011/10/01}%
305 \hologoEntry{SLiTeX}{simple}{2011/10/01}%
306 \hologoEntry{SliTeX}{-}{2011/10/01}%
307 \hologoEntry{SliTeX}{narrow}{2011/10/01}%
308 \hologoEntry{SliTeX}{simple}{2011/10/01}%
309 \hologoEntry{SliTeX}{lift}{2011/10/01}%
310 \hologoEntry{teTeX}{-}{2011/10/01}%
311 \hologoEntry{TeX}{-}{2010/04/08}%
312 \hologoEntry{TeX4ht}{-}{2011/11/22}%
313 \hologoEntry{TTH}{-}{2011/11/22}%
314 \hologoEntry{virTeX}{-}{2011/10/01}%
315 \hologoEntry{VTeX}{-}{2010/04/24}%
316 \hologoEntry{Xe}{-}{2010/04/08}%
317 \hologoEntry{XeLaTeX}{-}{2010/04/08}%
318 \hologoEntry{XeTeX}{-}{2010/04/08}%
319 }

```

2.2 Load resources

```

320 \begingroup\expandafter\expandafter\expandafter\endgroup
321 \expandafter\ifx\csname RequirePackage\endcsname\relax
322   \def\TMP@RequirePackage#1[#2]{%
323     \begingroup\expandafter\expandafter\expandafter\endgroup
324     \expandafter\ifx\csname ver@#1.sty\endcsname\relax
325       \input #1.sty\relax
326     \fi
327   }%
328   \TMP@RequirePackage{ltxcmds}[2011/02/04]%
329   \TMP@RequirePackage{infwarerr}[2010/04/08]%
330   \TMP@RequirePackage{kvsetkeys}[2010/03/01]%
331   \TMP@RequirePackage{kvdefinekeys}[2010/03/01]%
332   \TMP@RequirePackage{pdftexcmds}[2010/04/01]%
333   \TMP@RequirePackage{ifpdf}[2010/01/28]%
334   \TMP@RequirePackage{ifluatex}[2010/03/01]%
335   \ltx@ifundefined{newif}{%
336     \expandafter\let\csname newif\endcsname\ltx@newif
337   }{}%
338   \TMP@RequirePackage{ifxetex}[2009/01/23]%
339   \TMP@RequirePackage{ifvtex}[2010/03/01]%
340 \else
341   \RequirePackage{ltxcmds}[2011/02/04]%
342   \RequirePackage{infwarerr}[2010/04/08]%
343   \RequirePackage{kvsetkeys}[2010/03/01]%
344   \RequirePackage{kvdefinekeys}[2010/03/01]%

```

```

345 \RequirePackage{pdftexcmds}[2010/04/01]%
346 \RequirePackage{ifpdf}[2010/01/28]%
347 \RequirePackage{ifluatex}[2010/03/01]%
348 \RequirePackage{ifxetex}[2009/01/23]%
349 \RequirePackage{ifvtex}[2010/03/01]%
350 \fi

\HOLOGO@IfDefined

351 \def\HOLOGO@IfExists#1{%
352   \ifx\@undefined#1%
353     \expandafter\ltx@secondoftwo
354   \else
355     \ifx\relax#1%
356       \expandafter\ltx@secondoftwo
357     \else
358       \expandafter\expandafter\expandafter\ltx@firstoftwo
359     \fi
360   \fi
361 }

```

2.3 Setup macros

```

\hologoSetup

362 \def\hologoSetup{%
363   \let\HOLOGO@name\relax
364   \HOLOGO@Setup
365 }

\hologoLogoSetup

366 \def\hologoLogoSetup#1{%
367   \edef\HOLOGO@name{#1}%
368   \ltx@ifundefined{HoLogo@\HOLOGO@name}{%
369     \@PackageError{hologo}{%
370       Unknown logo ``\HOLOGO@name'%
371     }{\ehc
372     \ltx@gobble
373   }{%
374     \HOLOGO@Setup
375   }%
376 }

\HOLOGO@Setup

377 \def\HOLOGO@Setup{%
378   \kvsetkeys{HoLogo}%
379 }

```

2.4 Options

```

\HOLOGO@DeclareBoolOption

380 \def\HOLOGO@DeclareBoolOption#1{%
381   \expandafter\chardef\csname HOLOGOOPT@#1\endcsname\ltx@zero
382   \kv@define@key{HoLogo}{#1}[true]{%
383     \def\HOLOGO@temp{##1}%
384     \ifx\HOLOGO@temp\HOLOGO@true
385       \ifx\HOLOGO@name\relax
386         \expandafter\chardef\csname HOLOGOOPT@#1\endcsname=\ltx@one
387       \else

```

```

388     \expandafter\chardef\csname
389     HoLogoOpt@#1@\Hologo@name\endcsname\ltx@one
390   \fi
391   \Hologo@SetBreakAll{#1}%
392 \else
393   \ifx\Hologo@temp\Hologo@false
394     \ifx\Hologo@name\relax
395       \expandafter\chardef\csname HologoOpt@#1\endcsname=\ltx@zero
396     \else
397       \expandafter\chardef\csname
398       HoLogoOpt@#1@\Hologo@name\endcsname=\ltx@zero
399     \fi
400     \Hologo@SetBreakAll{#1}%
401   \else
402     \@PackageError{hologo}{%
403       Unknown value `##1' for boolean option `#1'.\MessageBreak
404       Known values are `true' and `false'%
405     }\@ehc
406   \fi
407 \fi
408 }%
409 }

```

\Hologo@SetBreakAll

```

410 \def\Hologo@SetBreakAll#1{%
411   \def\Hologo@temp{#1}%
412   \ifx\Hologo@temp\Hologo@break
413     \ifx\Hologo@name\relax
414       \chardef\HologoOpt@hyphenbreak=\HologoOpt@break
415       \chardef\HologoOpt@spacebreak=\HologoOpt@break
416       \chardef\HologoOpt@discretionarybreak=\HologoOpt@break
417     \else
418       \expandafter\chardef
419       \csname HoLogoOpt@hyphenbreak@\Hologo@name\endcsname=%
420       \csname HoLogoOpt@break@\Hologo@name\endcsname
421     \expandafter\chardef
422     \csname HoLogoOpt@spacebreak@\Hologo@name\endcsname=%
423     \csname HoLogoOpt@break@\Hologo@name\endcsname
424     \expandafter\chardef
425     \csname HoLogoOpt@discretionarybreak@\Hologo@name
426     \endcsname=%
427     \csname HoLogoOpt@break@\Hologo@name\endcsname
428   \fi
429 \fi
430 }

```

\Hologo@true

```
431 \def\Hologo@true{true}
```

\Hologo@false

```
432 \def\Hologo@false{false}
```

\Hologo@break

```

433 \def\Hologo@break{break}

434 \Hologo@DeclareBoolOption{break}
435 \Hologo@DeclareBoolOption{hyphenbreak}
436 \Hologo@DeclareBoolOption{spacebreak}
437 \Hologo@DeclareBoolOption{discretionarybreak}

```

```

438 \kv@define@key{HoLogo}{variant}{%
439   \ifx\HOLOGO@name\relax
440     \@PackageError{hologo}{%
441       Option `variant' is not available in \string\hologoSetup,%
442       \MessageBreak
443       Use \string\hologoLogoSetup\space instead%
444     }\@ehc
445   \else
446     \edef\HOLOGO@temp{#1}%
447     \ifx\HOLOGO@temp\ltx@empty
448       \expandafter
449       \let\csname HoLogoOpt@variant@\HOLOGO@name\endcsname\@undefined
450     \else
451       \ltx@ifundefined{HoLogo@\HOLOGO@name @\HOLOGO@temp}{%
452         \@PackageError{hologo}{%
453           Unknown variant ``\HOLOGO@temp' of logo ``\HOLOGO@name'%
454         }\@ehc
455       }{%
456         \expandafter
457         \let\csname HoLogoOpt@variant@\HOLOGO@name\endcsname
458           \HOLOGO@temp
459       }%
460     \fi
461   \fi
462 }

```

\HOLOGO@Variant

```

463 \def\HOLOGO@Variant#1{%
464   #1%
465   \ltx@ifundefined{HoLogoOpt@variant@#1}{%
466     }{%
467       @\csname HoLogoOpt@variant@#1\endcsname
468     }%
469 }

```

2.5 Break/no-break support

\HOLOGO@space

```

470 \def\HOLOGO@space{%
471   \ltx@ifundefined{HoLogoOpt@spacebreak@\HOLOGO@name}{%
472     \ltx@ifundefined{HoLogoOpt@break@\HOLOGO@name}{%
473       \chardef\HOLOGO@temp=\HOLOGO@OPT@spacebreak
474     }{%
475       \chardef\HOLOGO@temp=%
476       \csname HoLogoOpt@break@\HOLOGO@name\endcsname
477     }%
478   }{%
479     \chardef\HOLOGO@temp=%
480     \csname HoLogoOpt@spacebreak@\HOLOGO@name\endcsname
481   }%
482   \ifcase\HOLOGO@temp
483     \penalty10000 %
484   \fi
485   \ltx@space
486 }

```

\HOLOGO@hyphen


```

487 \def\HOLOGO@hyphen{%
488   \ltx@ifundefined{HoLogoOpt@hyphenbreak@\HOLOGO@name}{%
489     \ltx@ifundefined{HoLogoOpt@break@\HOLOGO@name}{%
490       \chardef\HOLOGO@temp=\HOLOGO@OPT@hyphenbreak
491     }{%
492       \chardef\HOLOGO@temp=%
493       \csname HoLogoOpt@break@\HOLOGO@name\endcsname
494     }%
495   }{%
496     \chardef\HOLOGO@temp=%
497     \csname HoLogoOpt@hyphenbreak@\HOLOGO@name\endcsname
498   }%
499   \ifcase\HOLOGO@temp
500     \ltx@mbox{-}%
501   \else
502     -%
503   \fi
504 }

```

\HOLOGO@discretionary

```

505 \def\HOLOGO@discretionary{%
506   \ltx@ifundefined{HoLogoOpt@discretionarybreak@\HOLOGO@name}{%
507     \ltx@ifundefined{HoLogoOpt@break@\HOLOGO@name}{%
508       \chardef\HOLOGO@temp=\HOLOGO@OPT@discretionarybreak
509     }{%
510       \chardef\HOLOGO@temp=%
511       \csname HoLogoOpt@break@\HOLOGO@name\endcsname
512     }%
513   }{%
514     \chardef\HOLOGO@temp=%
515     \csname HoLogoOpt@discretionarybreak@\HOLOGO@name\endcsname
516   }%
517   \ifcase\HOLOGO@temp
518   \else
519     \-%
520   \fi
521 }

```

\HOLOGO@mbox

```

522 \def\HOLOGO@mbox#1{%
523   \ltx@ifundefined{HoLogoOpt@break@\HOLOGO@name}{%
524     \chardef\HOLOGO@temp=\HOLOGO@OPT@hyphenbreak
525   }{%
526     \chardef\HOLOGO@temp=%
527     \csname HoLogoOpt@break@\HOLOGO@name\endcsname
528   }%
529   \ifcase\HOLOGO@temp
530     \ltx@mbox{#1}%
531   \else
532     #1%
533   \fi
534 }

```

2.6 Font support

#1:	logo name
\HoLogoFont@font #2:	font short name
#3:	text

```

535 \def\HoLogoFont@font#1#2#3{%
536   \begingroup
537     \ltx@ifundefined{HoLogoFont@logo@#1.#2}{%
538       \ltx@ifundefined{HoLogoFont@font@#2}{%
539         \@PackageWarning{hologo}{%
540           Missing font `#2' for logo `#1'%
541         }%
542         #3%
543       }{%
544         \csname HoLogoFont@font@#2\endcsname{#3}%
545       }%
546     }{%
547       \csname HoLogoFont@logo@#1.#2\endcsname{#3}%
548     }%
549   \endgroup
550 }

```

\HoLogoFont@Def

```

551 \def\HoLogoFont@Def#1{%
552   \expandafter\def\csname HoLogoFont@font@#1\endcsname
553 }

```

\HoLogoFont@LogoDef

```

554 \def\HoLogoFont@LogoDef#1#2{%
555   \expandafter\def\csname HoLogoFont@logo@#1.#2\endcsname
556 }

```

2.6.1 Font defaults

\HoLogoFont@font@general

```

557 \HoLogoFont@Def{general}{}%

```

\HoLogoFont@font@rm

```

558 \ltx@ifundefined{rmfamily}{%
559   \ltx@ifundefined{rm}{%
560     }{%
561       \HoLogoFont@Def{rm}{\rm}%
562     }%
563 }{%
564   \HoLogoFont@Def{rm}{\rmfamily}%
565 }

```

\HoLogoFont@font@sf

```

566 \ltx@ifundefined{sffamily}{%
567   \ltx@ifundefined{sf}{%
568     }{%
569       \HoLogoFont@Def{sf}{\sf}%
570     }%
571 }{%
572   \HoLogoFont@Def{sf}{\sffamily}%
573 }

```

\HoLogoFont@font@bibs

In case of plain T_EX the original small caps variant is used as default. In L^AT_EX the definition of package dtklogos [2] is used.

```

\DeclareRobustCommand{\BibTeX}{%
  \B%
  \kern-.05em%
}

```

```

    \hbox{%
      $\m@th$%%\force\math\size\calculations
      \csname S@\f@size\endcsname
      \fontsize\sfontsize\z@
      \math@fontsfalse
      \selectfont
      I%
      \kern-.025em%
      B
    }%
    \kern-.08em%
    \-%
    \TeX
  }

574 \ltx@ifundefined{selectfont}{%
575   \ltx@ifundefined{tensc}{%
576     \font\tensc=cmcsc10\relax
577   }{}%
578   \HoLogoFont@Def{bibsfont}{\tensc}%
579 }{%
580   \HoLogoFont@Def{bibsfont}{%
581     $\mathsurround=0pt$%
582     \csname S@\f@size\endcsname
583     \fontsize\sfontsize{0pt}%
584     \math@fontsfalse
585     \selectfont
586   }%
587 }

```

\HoLogoFont@font@sc

```

588 \ltx@ifundefined{scshape}{%
589   \ltx@ifundefined{tensc}{%
590     \font\tensc=cmcsc10\relax
591   }{}%
592   \HoLogoFont@Def{scfont}{\tensc}%
593 }{%
594   \HoLogoFont@Def{scfont}{\scshape}%
595 }

```

\HoLogoFont@font@sy

```

596 \ltx@ifundefined{usefont}{%
597   \ltx@ifundefined{tensy}{%
598   }{}%
599   \HoLogoFont@Def{syfont}{\tensy}%
600 }%
601 }{%
602   \HoLogoFont@Def{syfont}{%
603     \usefont{OMS}{cmsy}{m}{n}%
604   }%
605 }

```

\HoLogoFont@font@logo

```

606 \begingroup
607   \def\x{LaTeX2e}%
608 \expandafter\endgroup
609 \ifx\fontname\x
610   \ltx@ifundefined{logofamily}{%

```

```

611 \DeclareRobustCommand\logofamily{%
612 \not@math@alphabet\logofamily\relax
613 \fontencoding{U}%
614 \fontfamily{logo}%
615 \selectfont
616 }%
617 }{}%
618 \ltx@ifundefined{logofamily}{%
619 }{%
620 \HoLogoFont@Def{logo}{\logofamily}%
621 }%
622 \else
623 \ltx@ifundefined{tenlogo}{%
624 \font\tenlogo=logo10\relax
625 }{}%
626 \HoLogoFont@Def{logo}{\tenlogo}%
627 \fi

```

2.6.2 Font setup

\holoFontSetup

```

628 \def\holoFontSetup{%
629 \let\HOLOGO@name\relax
630 \HOLOGO@FontSetup
631 }

```

\holoLogoFontSetup

```

632 \def\holoLogoFontSetup#1{%
633 \edef\HOLOGO@name{#1}%
634 \ltx@ifundefined{HoLogo@\HOLOGO@name}{%
635 \@PackageError{holo}{%
636 Unknown logo '\HOLOGO@name'%
637 }{\@ehc
638 \ltx@gobble
639 }{}%
640 \HOLOGO@FontSetup
641 }%
642 }

```

\HOLOGO@FontSetup

```

643 \def\HOLOGO@FontSetup{%
644 \kvsetkeys{HoLogoFont}%
645 }

646 \def\HOLOGO@temp#1{%
647 \kv@define@key{HoLogoFont}{#1}{%
648 \ifx\HOLOGO@name\relax
649 \HoLogoFont@Def{#1}{##1}%
650 \else
651 \HoLogoFont@LogoDef\HOLOGO@name{#1}{##1}%
652 \fi
653 }%
654 }
655 \HOLOGO@temp{general}
656 \HOLOGO@temp{sf}

```

2.7 Generic logo commands

```
657 \HOLOGO@IfExists\hologo{%
658   \@PackageError{hologo}{%
659     \string\hologo\ltx@space is already defined.\MessageBreak
660     Package loading is aborted%
661   }\@ehc
662   \HOLOGO@AtEnd
663 }%
664 \HOLOGO@IfExists\hologoRobust{%
665   \@PackageError{hologo}{%
666     \string\hologoRobust\ltx@space is already defined.\MessageBreak
667     Package loading is aborted%
668   }\@ehc
669   \HOLOGO@AtEnd
670 }%
```

2.7.1 \hologo and friends

```
671 \ifluatex
672   \expandafter\ltx@firstofone
673 \else
674   \expandafter\ltx@gobble
675 \fi
676 {%
677   \ltx@ifundefined{ifincsnam}{%
678     \ifnum\luatexversion<36 %
679       \expandafter\ltx@gobble
680     \else
681       \expandafter\ltx@firstofone
682     \fi
683   {%
684     \begingroup
685     \ifcase0%
686       \directlua{%
687         if tex.enableprimitives then %
688           tex.enableprimitives('HOLOGO@', {'ifincsnam'})%
689         else %
690           tex.print('1')%
691         end%
692       }%
693     \ifx\HOLOGO@ifincsnam\@undefined 1\fi%
694     \relax
695     \expandafter\ltx@firstofone
696   \else
697     \endgroup
698     \expandafter\ltx@gobble
699   \fi
700   {%
701     \global\let\ifincsnam\HOLOGO@ifincsnam
702   }%
703   \HOLOGO@temp
704 }%
705 }{}%
706 }

707 \ltx@ifundefined{ifincsnam}{%
708   \catcode`\$=14 %
709 }{%
710   \catcode`\$=9 %
```

```

711 }

\hologo
712 \def\hologo#1{%
713 $ \ifincsname
714 $ \ltx@ifundefined{HoLogoCs@\HOLOGO@Variant{#1}}{%
715 $ #1%
716 $ }{%
717 $ \csname HoLogoCs@\HOLOGO@Variant{#1}\endcsname\ltx@firstoftwo
718 $ }%
719 $ \else
720 \HOLOGO@IfExists\texorpdfstring\texorpdfstring\ltx@firstoftwo
721 {%
722 \hologoRobust{#1}%
723 }{%
724 \ltx@ifundefined{HoLogoBkm@\HOLOGO@Variant{#1}}{%
725 \ltx@ifundefined{HoLogo@#1}{?#1?}{#1}%
726 }{%
727 \csname HoLogoBkm@\HOLOGO@Variant{#1}\endcsname
728 \ltx@firstoftwo
729 }%
730 }%
731 $ \fi
732 }

\Hologo
733 \def\Hologo#1{%
734 $ \ifincsname
735 $ \ltx@ifundefined{HoLogoCs@\HOLOGO@Variant{#1}}{%
736 $ #1%
737 $ }{%
738 $ \csname HoLogoCs@\HOLOGO@Variant{#1}\endcsname\ltx@secondoftwo
739 $ }%
740 $ \else
741 \HOLOGO@IfExists\texorpdfstring\texorpdfstring\ltx@firstoftwo
742 {%
743 \HologoRobust{#1}%
744 }{%
745 \ltx@ifundefined{HoLogoBkm@\HOLOGO@Variant{#1}}{%
746 \ltx@ifundefined{HoLogo@#1}{?#1?}{#1}%
747 }{%
748 \csname HoLogoBkm@\HOLOGO@Variant{#1}\endcsname
749 \ltx@secondoftwo
750 }%
751 }%
752 $ \fi
753 }

\hologoVariant
754 \def\hologoVariant#1#2{%
755 \ifx\relax#2\relax
756 \hologo{#1}%
757 \else
758 $ \ifincsname
759 $ \ltx@ifundefined{HoLogoCs@#1@#2}{%
760 $ #1%
761 $ }{%
762 $ \csname HoLogoCs@#1@#2\endcsname\ltx@firstoftwo

```

```

763 $    }%
764 $    \else
765        \Hologo@IfExists\texorpdfstring\texorpdfstring\ltx@firstoftwo
766        {%
767            \hologoVariantRobust{#1}{#2}%
768        }{%
769            \ltx@ifundefined{HoLogoBkm@#1@#2}{%
770                \ltx@ifundefined{HoLogo@#1}{?#1?}{#1}%
771            }{%
772                \csname HoLogoBkm@#1@#2\endcsname
773                \ltx@firstoftwo
774            }%
775        }%
776 $    \fi
777 \fi
778 }

```

\HologoVariant

```

779 \def\HologoVariant#1#2{%
780     \ifx\relax#2\relax
781         \Hologo{#1}%
782     \else
783 $     \ifincsname
784 $         \ltx@ifundefined{HoLogoCs@#1@#2}{%
785 $             #1%
786 $         }{%
787 $             \csname HoLogoCs@#1@#2\endcsname\ltx@secondoftwo
788 $         }%
789 $     \else
790         \Hologo@IfExists\texorpdfstring\texorpdfstring\ltx@firstoftwo
791         {%
792             \HologoVariantRobust{#1}{#2}%
793         }{%
794             \ltx@ifundefined{HoLogoBkm@#1@#2}{%
795                 \ltx@ifundefined{HoLogo@#1}{?#1?}{#1}%
796             }{%
797                 \csname HoLogoBkm@#1@#2\endcsname
798                 \ltx@secondoftwo
799             }%
800         }%
801 $     \fi
802 \fi
803 }

804 \catcode`\$=3 %

```

2.7.2 \hologoRobust and friends

\hologoRobust

```

805 \ltx@ifundefined{protected}{%
806     \ltx@ifundefined{DeclareRobustCommand}{%
807         \def\hologoRobust#1%
808         }{%
809             \DeclareRobustCommand*\hologoRobust[1]%
810         }%
811     }{%
812         \protected\def\hologoRobust#1%
813     }%

```

```

814 {%
815   \edef\HOLOGO@name{#1}%
816   \ltx@ifundefined{HoLogo@\HOLOGO@Variant\HOLOGO@name}{%
817     \@PackageError{hologo}{%
818       Unknown logo `\'HOLOGO@name'%
819     }\@ehc
820     ?\'HOLOGO@name?%
821   }{%
822     \ltx@ifundefined{ver@tex4ht.sty}{%
823       \HoLogoFont@font\HOLOGO@name{general}{%
824         \csname HoLogo@\HOLOGO@Variant\HOLOGO@name\endcsname
825         \ltx@firstoftwo
826       }%
827     }{%
828       \ltx@ifundefined{HoLogoHtml@\HOLOGO@Variant\HOLOGO@name}{%
829         \HOLOGO@name
830       }{%
831         \csname HoLogoHtml@\HOLOGO@Variant\HOLOGO@name\endcsname
832         \ltx@firstoftwo
833       }%
834     }%
835   }%
836 }

```

\HologoRobust

```

837 \ltx@ifundefined{protected}{%
838   \ltx@ifundefined{DeclareRobustCommand}{%
839     \def\HologoRobust#1%
840   }{%
841     \DeclareRobustCommand*\HologoRobust[1]%
842   }%
843 }{%
844   \protected\def\HologoRobust#1%
845 }%
846 {%
847   \edef\HOLOGO@name{#1}%
848   \ltx@ifundefined{HoLogo@\HOLOGO@Variant\HOLOGO@name}{%
849     \@PackageError{hologo}{%
850       Unknown logo `\'HOLOGO@name'%
851     }\@ehc
852     ?\'HOLOGO@name?%
853   }{%
854     \ltx@ifundefined{ver@tex4ht.sty}{%
855       \HoLogoFont@font\HOLOGO@name{general}{%
856         \csname HoLogo@\HOLOGO@Variant\HOLOGO@name\endcsname
857         \ltx@secondoftwo
858       }%
859     }{%
860       \ltx@ifundefined{HoLogoHtml@\HOLOGO@Variant\HOLOGO@name}{%
861         \expandafter\HOLOGO@Uppercase\HOLOGO@name
862       }{%
863         \csname HoLogoHtml@\HOLOGO@Variant\HOLOGO@name\endcsname
864         \ltx@secondoftwo
865       }%
866     }%
867   }%
868 }

```


`\hologoVariantRobust`

```

869 \ltx@ifundefined{protected}{%
870   \ltx@ifundefined{DeclareRobustCommand}{%
871     \def\hologoVariantRobust#1#2%
872   }{%
873     \DeclareRobustCommand*\hologoVariantRobust[2]%
874   }%
875 }{%
876   \protected\def\hologoVariantRobust#1#2%
877 }%
878 {%
879   \begingroup
880     \hologoLogoSetup{#1}{variant={#2}}%
881     \hologoRobust{#1}%
882   \endgroup
883 }
```

`\HologoVariantRobust`

```

884 \ltx@ifundefined{protected}{%
885   \ltx@ifundefined{DeclareRobustCommand}{%
886     \def\HologoVariantRobust#1#2%
887   }{%
888     \DeclareRobustCommand*\HologoVariantRobust[2]%
889   }%
890 }{%
891   \protected\def\HologoVariantRobust#1#2%
892 }%
893 {%
894   \begingroup
895     \hologoLogoSetup{#1}{variant={#2}}%
896     \HologoRobust{#1}%
897   \endgroup
898 }
```

`\hologorobust` Macro `\hologorobust` is only defined for compatibility. Its use is deprecated.

```

899 \def\hologorobust{\hologoRobust}
```

2.8 Helpers

`\HOLOGO@Uppercase` Macro `\HOLOGO@Uppercase` is restricted to `\uppercase`, because plain \TeX or \iniTeX do not provide `\MakeUppercase`.

```

900 \def\HOLOGO@Uppercase#1{\uppercase{#1}}
```

`\HOLOGO@PdfdocUnicode`

```

901 \def\HOLOGO@PdfdocUnicode{%
902   \ifx\ifHy@unicode\iftrue
903     \expandafter\ltx@secondoftwo
904   \else
905     \expandafter\ltx@firstoftwo
906   \fi
907 }
```

`\HOLOGO@Math`

```

908 \def\HOLOGO@MathSetup{%
909   \mathsurroundOpt\relax
910   \HOLOGO@IfExists\series{%
911     \if b\expandafter\ltx@car\series x\@nil
```

```

912     \csname boldmath\endcsname
913     \fi
914   }{}%
915 }

```

\HOLOGO@TempDimen

```

916 \dimendef\HOLOGO@TempDimen=\ltx@zero

```

\HOLOGO@NegativeKerning

```

917 \def\HOLOGO@NegativeKerning#1{%
918   \begingroup
919     \HOLOGO@TempDimen=0pt\relax
920     \comma@parse@normalized{#1}{%
921       \ifdim\HOLOGO@TempDimen=0pt %
922         \expandafter\HOLOGO@@NegativeKerning\comma@entry
923       \fi
924       \ltx@gobble
925     }%
926     \ifdim\HOLOGO@TempDimen<0pt %
927       \kern\HOLOGO@TempDimen
928     \fi
929   \endgroup
930 }

```

\HOLOGO@@NegativeKerning

```

931 \def\HOLOGO@@NegativeKerning#1#2{%
932   \setbox\ltx@zero\hbox{#1#2}%
933   \HOLOGO@TempDimen=\wd\ltx@zero
934   \setbox\ltx@zero\hbox{#1\kern0pt#2}%
935   \advance\HOLOGO@TempDimen by -\wd\ltx@zero
936 }

```

\HOLOGO@SpaceFactor

```

937 \def\HOLOGO@SpaceFactor{%
938   \spacefactor1000 %
939 }

```

\HOLOGO@Span

```

940 \def\HOLOGO@Span#1#2{%
941   \HCode{<span class="HoLogo-#1">}%
942   #2%
943   \HCode{</span>}%
944 }

```

2.8.1 Text subscript

\HOLOGO@SubScript

```

945 \def\HOLOGO@SubScript#1{%
946   \ltx@ifundefined{textsubscript}{%
947     \ltx@ifundefined{text}{%
948       \ltx@mbox{%
949         \mathsurround=0pt\relax
950         $%
951         _{%
952           \ltx@ifundefined{sf@size}{%
953             \mathrm{#1}%
954           }{%

```

```

955         \mbox{%
956             \fontsize\sf@size{0pt}\selectfont
957             #1%
958         }%
959     }%
960 }%
961 $%
962 }%
963 }{%
964     \ltx@mbox{%
965         \mathsurround=0pt\relax
966         $_{\text{#1}}$%
967     }%
968 }%
969 }{%
970     \textsubscript{#1}%
971 }%
972 }

```

2.9 T_EX and friends

2.9.1 T_EX

\HoLogo@TeX Source: L^AT_EX kernel.

```

973 \def\HoLogo@TeX#1{%
974     T\kern-.1667em\lower.5ex\hbox{E}\kern-.125emX\HOLOGO@SpaceFactor
975 }

```

\HoLogoHtml@TeX

```

976 \def\HoLogoHtml@TeX#1{%
977     \HoLogoCss@TeX
978     \HOLOGO@Span{TeX}{%
979         T%
980         \HOLOGO@Span{e}{%
981             E%
982         }%
983         X%
984     }%
985 }

```

\HoLogoCss@TeX

```

986 \def\HoLogoCss@TeX{%
987     \Css{%
988         span.HoLogo-TeX span.HoLogo-e{%
989             position:relative;%
990             top:.5ex;%
991             margin-left:-.1667em;%
992             margin-right:-.125em;%
993         }%
994     }%
995     \Css{%
996         a span.HoLogo-TeX span.HoLogo-e{%
997             text-decoration:none;%
998         }%
999     }%
1000 \global\let\HoLogoCss@TeX\relax
1001 }

```

2.9.2 plain T_EX

```
\HoLogo@plainTeX@space Source: “The TEXbook”
1002 \def\HoLogo@plainTeX@space#1{%
1003   \HOLOGO@mbbox{#1{p}{P}lain}\HOLOGO@space\hologo{TeX}%
1004 }

\HoLogoCs@plainTeX@space
1005 \def\HoLogoCs@plainTeX@space#1{#1{p}{P}lain TeX}%

\HoLogoBkm@plainTeX@space
1006 \def\HoLogoBkm@plainTeX@space#1{%
1007   #1{p}{P}lain \hologo{TeX}%
1008 }

\HoLogoHtml@plainTeX@space
1009 \def\HoLogoHtml@plainTeX@space#1{%
1010   #1{p}{P}lain \hologo{TeX}%
1011 }

\HoLogo@plainTeX@hyphen
1012 \def\HoLogo@plainTeX@hyphen#1{%
1013   \HOLOGO@mbbox{#1{p}{P}lain}\HOLOGO@hyphen\hologo{TeX}%
1014 }

\HoLogoCs@plainTeX@hyphen
1015 \def\HoLogoCs@plainTeX@hyphen#1{#1{p}{P}lain-TeX}

\HoLogoBkm@plainTeX@hyphen
1016 \def\HoLogoBkm@plainTeX@hyphen#1{%
1017   #1{p}{P}lain-\hologo{TeX}%
1018 }

\HoLogoHtml@plainTeX@hyphen
1019 \def\HoLogoHtml@plainTeX@hyphen#1{%
1020   #1{p}{P}lain-\hologo{TeX}%
1021 }

\HoLogo@plainTeX@runtogether
1022 \def\HoLogo@plainTeX@runtogether#1{%
1023   \HOLOGO@mbbox{#1{p}{P}lain\hologo{TeX}}%
1024 }

\HoLogoCs@plainTeX@runtogether
1025 \def\HoLogoCs@plainTeX@runtogether#1{#1{p}{P}lainTeX}

\HoLogoBkm@plainTeX@runtogether
1026 \def\HoLogoBkm@plainTeX@runtogether#1{%
1027   #1{p}{P}lain\hologo{TeX}%
1028 }

\HoLogoHtml@plainTeX@runtogether
1029 \def\HoLogoHtml@plainTeX@runtogether#1{%
1030   #1{p}{P}lain\hologo{TeX}%
1031 }
```

```

\HoLogo@plainTeX
1032 \def\HoLogo@plainTeX{\HoLogo@plainTeX@space}

\HoLogoCs@plainTeX
1033 \def\HoLogoCs@plainTeX{\HoLogoCs@plainTeX@space}

\HoLogoBkm@plainTeX
1034 \def\HoLogoBkm@plainTeX{\HoLogoBkm@plainTeX@space}

\HoLogoHtml@plainTeX
1035 \def\HoLogoHtml@plainTeX{\HoLogoHtml@plainTeX@space}

```

2.9.3 L^AT_EX

Source: L^AT_EX kernel.

```

\DeclareRobustCommand{\LaTeX}{%
  \L%
  \kern-.36em%
  {\%
    \sbox\z@{\T%
      \vbox\to\ht\z@{%
        \hbox{%
          \check@mathfonts
          \fontsize\sf@size\z@
          \math@fontsfalse
          \selectfont
          A%
        }%
        \vss
      }%
    }%
    \kern-.15em%
    \TeX
  }

\HoLogo@La
1036 \def\HoLogo@La#1{%
1037   L%
1038   \kern-.36em%
1039   \begingroup
1040     \setbox\ltx@zero\hbox{T}%
1041     \vbox\to\ht\ltx@zero{%
1042       \hbox{%
1043         \ltx@ifundefined{check@mathfonts}{%
1044           \csname sevenrm\endcsname
1045         }{%
1046           \check@mathfonts
1047           \fontsize\sf@size{0pt}%
1048           \math@fontsfalse\selectfont
1049         }%
1050         A%
1051       }%
1052       \vss
1053     }%
1054   \endgroup
1055 }

```

\HoLogo@LaTeX Source: L^AT_EX kernel.

```

1056 \def\HoLogo@LaTeX#1{%
1057   \hologo{La}%
1058   \kern-.15em%
1059   \hologo{TeX}%
1060 }

```

\HoLogoHtml@LaTeX

```

1061 \def\HoLogoHtml@LaTeX#1{%
1062   \HoLogoCss@LaTeX
1063   \HOLOGO@Span{LaTeX}{%
1064     L%
1065     \HOLOGO@Span{a}{%
1066       A%
1067     }%
1068     \hologo{TeX}%
1069   }%
1070 }

```

\HoLogoCss@LaTeX

```

1071 \def\HoLogoCss@LaTeX{%
1072   \Css{%
1073     span.HoLogo-LaTeX span.HoLogo-a{%
1074       position:relative;%
1075       top:-.5ex;%
1076       margin-left:-.36em;%
1077       margin-right:-.15em;%
1078       font-size:85\%;%
1079     }%
1080   }%
1081   \global\let\HoLogoCss@LaTeX\relax
1082 }

```

2.9.4 (L^A)T_EX

`\HoLogo@LaTeXTeX` The kerning around the parentheses is taken from package `dtklogos` [2].

```

\DeclareRobustCommand{\LaTeXTeX}{%
  \(\%
  \kern-.15em%
  \L%
  \kern-.36em%
  {\%
    \sbox\z@T%
    \vbox\to\ht0{%
      \hbox{%
        $m@th$%
        \csize\sf@size\endcsize
        \fontsize\sf@size\z@
        \math@fontfalse
        \selectfont
        A%
      }%
    }%
    \vss
  }%
  \kern-.2em%
  )%

```

```

        \kern-.15em%
        \TeX
    }

1083 \def\HoLogo@LaTeXTeX#1{%
1084     (%
1085     \kern-.15em%
1086     \hologo{La}%
1087     \kern-.2em%
1088     )%
1089     \kern-.15em%
1090     \hologo{TeX}%
1091 }

\HoLogoBkm@LaTeXTeX

1092 \def\HoLogoBkm@LaTeXTeX#1{(La)TeX}

\HoLogo@(La)TeX

1093 \expandafter
1094 \let\csname HoLogo@(La)TeX\endcsname\HoLogo@LaTeXTeX

\HoLogoBkm@(La)TeX

1095 \expandafter
1096 \let\csname HoLogoBkm@(La)TeX\endcsname\HoLogoBkm@LaTeXTeX

\HoLogoHtml@LaTeXTeX

1097 \def\HoLogoHtml@LaTeXTeX#1{%
1098     \HoLogoCss@LaTeXTeX
1099     \HOLOGO@Span{LaTeXTeX}{%
1100         (%
1101         \HOLOGO@Span{L}{L}%
1102         \HOLOGO@Span{a}{A}%
1103         \HOLOGO@Span{ParenRight}{})}%
1104     \hologo{TeX}%
1105     }%
1106 }

\HoLogoHtml@(La)TeX Kerning after opening parentheses and before closing parentheses is  $-0.1$  em. The
original values  $-0.15$  em looked too ugly for a serif font.

1107 \expandafter
1108 \let\csname HoLogoHtml@(La)TeX\endcsname\HoLogoHtml@LaTeXTeX

\HoLogoCss@LaTeXTeX

1109 \def\HoLogoCss@LaTeXTeX{%
1110     \Css{%
1111         span.HoLogo-LaTeXTeX span.HoLogo-L{%
1112             margin-left:-.1em;%
1113         }%
1114     }%
1115     \Css{%
1116         span.HoLogo-LaTeXTeX span.HoLogo-a{%
1117             position:relative;%
1118             top:-.5ex;%
1119             margin-left:-.36em;%
1120             margin-right:-.1em;%
1121             font-size:85\%;%
1122         }%
1123     }%

```

```

1124 \Css{%
1125     span.HoLogo-LaTeXTeX span.HoLogo-ParenRight{%
1126         margin-right:-.15em;%
1127     }%
1128 }%
1129 \global\let\HoLogoCss@LaTeXTeX\relax
1130 }

```

2.9.5 L^AT_EX 2_ε

\HoLogo@LaTeXe Source: L^AT_EX kernel

```

1131 \def\HoLogo@LaTeXe#1{%
1132     \hologo{LaTeX}%
1133     \kern.15em%
1134     \hbox{%
1135         \HOLOGO@MathSetup
1136         2%
1137         $_{\textstyle\varepsilon}$%
1138     }%
1139 }

```

\HoLogoCs@LaTeXe

```

1140 \ifnum64=\^^^0040\relax % test for big chars of LuaTeX/XeTeX
1141     \catcode`\$=9 %
1142     \catcode`\&=14 %
1143 \else
1144     \catcode`\$=14 %
1145     \catcode`\&=9 %
1146 \fi
1147 \def\HoLogoCs@LaTeXe#1{%
1148     LaTeX2%
1149     $ \string \^^^0395%
1150     & e%
1151 }%
1152 \catcode`\$=3 %
1153 \catcode`\&=4 %

```

\HoLogoBkm@LaTeXe

```

1154 \def\HoLogoBkm@LaTeXe#1{%
1155     \hologo{LaTeX}%
1156     2%
1157     \HOLOGO@PdfdocUnicode{e}{\textepsilon}%
1158 }

```

\HoLogoHtml@LaTeXe

```

1159 \def\HoLogoHtml@LaTeXe#1{%
1160     \HoLogoCss@LaTeXe
1161     \HOLOGO@Span{LaTeX2e}{%
1162         \hologo{LaTeX}%
1163         \HOLOGO@Span{2}{2}%
1164         \HOLOGO@Span{e}{%
1165             \HOLOGO@MathSetup
1166             \ensuremath{\textstyle\varepsilon}%
1167         }%
1168     }%
1169 }

```



```

\HoLogoCss@LaTeXe
1170 \def\HoLogoCss@LaTeXe{%
1171   \Css{%
1172     span.HoLogo-LaTeX2e span.HoLogo-2{%
1173       padding-left:.15em;%
1174     }%
1175   }%
1176   \Css{%
1177     span.HoLogo-LaTeX2e span.HoLogo-e{%
1178       position:relative;%
1179       top:.35ex;%
1180       text-decoration:none;%
1181     }%
1182   }%
1183   \global\let\HoLogoCss@LaTeXe\relax
1184 }

\HoLogo@LaTeX2e
1185 \expandafter
1186 \let\csname HoLogo@LaTeX2e\endcsname\HoLogo@LaTeXe

\HoLogoCs@LaTeX2e
1187 \expandafter
1188 \let\csname HoLogoCs@LaTeX2e\endcsname\HoLogoCs@LaTeXe

\HoLogoBkm@LaTeX2e
1189 \expandafter
1190 \let\csname HoLogoBkm@LaTeX2e\endcsname\HoLogoBkm@LaTeXe

\HoLogoHtml@LaTeX2e
1191 \expandafter
1192 \let\csname HoLogoHtml@LaTeX2e\endcsname\HoLogoHtml@LaTeXe

2.9.6 LATEX3

\HoLogo@LaTeX3 Source: LATEX kernel
1193 \expandafter\def\csname HoLogo@LaTeX3\endcsname#1{%
1194   \hologo{LaTeX}%
1195   3%
1196 }

\HoLogoBkm@LaTeX3
1197 \expandafter\def\csname HoLogoBkm@LaTeX3\endcsname#1{%
1198   \hologo{LaTeX}%
1199   3%
1200 }

\HoLogoHtml@LaTeX3
1201 \expandafter
1202 \let\csname HoLogoHtml@LaTeX3\expandafter\endcsname
1203 \csname HoLogo@LaTeX3\endcsname

```

2.9.7 L^AT_EX_{xml}

\HoLogo@LaTeXML

```

1204 \def\HoLogo@LaTeXML#1{%
1205   \HOLG0@mbbox{%
1206     \hologo{La}%
1207     \kern-.15em%
1208     T%
1209     \kern-.1667em%
1210     \lower.5ex\hbox{E}%
1211     \kern-.125em%
1212     \HoLogoFont@font{LaTeXML}{sc}{xml}%
1213   }%
1214 }
```

\HoLogoHtml@pdfLaTeX

```

1215 \def\HoLogoHtml@LaTeXML#1{%
1216   \HOLG0@Span{LaTeXML}{%
1217     \HoLogoCss@LaTeX
1218     \HoLogoCss@TeX
1219     \HOLG0@Span{LaTeX}{%
1220       L%
1221       \HOLG0@Span{a}{%
1222         A%
1223       }%
1224     }%
1225     \HOLG0@Span{TeX}{%
1226       T%
1227       \HOLG0@Span{e}{%
1228         E%
1229       }%
1230     }%
1231     \HCode{<span style="font-variant: small-caps;">}%
1232     xml%
1233     \HCode{</span>}%
1234   }%
1235 }
```

2.9.8 ϵ -T_EX

\HoLogo@eTeX Source: package etex

```

1236 \def\HoLogo@eTeX#1{%
1237   \ltx@mbbox{%
1238     \HOLG0@MathSetup
1239     $\varepsilon$%
1240     -%
1241     \HOLG0@NegativeKerning{-T,T-,To}%
1242     \hologo{TeX}%
1243   }%
1244 }
```

\HoLogoCs@eTeX

```

1245 \ifnum64=\^^^0040\relax % test for big chars of LuaTeX/XeTeX
1246   \catcode`\$=9 %
1247   \catcode`\&=14 %
1248 \else
1249   \catcode`\$=14 %
1250   \catcode`\&=9 %
```

```

1251 \fi
1252 \def\HoLogoCs@eTeX#1{%
1253 $ #1{\string ~~~~0395}{\string ~~~~03b5}%
1254 & #1{e}{E}%
1255 TeX%
1256 }%
1257 \catcode`\$=3 %
1258 \catcode`\&=4 %

```

\HoLogoBkm@eTeX

```

1259 \def\HoLogoBkm@eTeX#1{%
1260 \HOLOGO@PdfdocUnicode{#1{e}{E}}{\textepsilon}%
1261 -%
1262 \hologo{TeX}%
1263 }

```

\HoLogoHtml@eTeX

```

1264 \def\HoLogoHtml@eTeX#1{%
1265 \ltx@mbox{%
1266 \HOLOGO@MathSetup
1267 $\varepsilon$%
1268 -%
1269 \hologo{TeX}%
1270 }%
1271 }

```

2.9.9 iniTeX

\HoLogo@iniTeX

```

1272 \def\HoLogo@iniTeX#1{%
1273 \HOLOGO@mbox{%
1274 #1{i}{I}ni\hologo{TeX}%
1275 }%
1276 }

```

\HoLogoCs@iniTeX

```

1277 \def\HoLogoCs@iniTeX#1{#1{i}{I}niTeX}

```

\HoLogoBkm@iniTeX

```

1278 \def\HoLogoBkm@iniTeX#1{%
1279 #1{i}{I}ni\hologo{TeX}%
1280 }

```

\HoLogoHtml@iniTeX

```

1281 \let\HoLogoHtml@iniTeX\HoLogo@iniTeX

```

2.9.10 virTeX

\HoLogo@virTeX

```

1282 \def\HoLogo@virTeX#1{%
1283 \HOLOGO@mbox{%
1284 #1{v}{V}ir\hologo{TeX}%
1285 }%
1286 }

```

\HoLogoCs@virTeX

```

1287 \def\HoLogoCs@virTeX#1{#1{v}{V}irTeX}

```

\HoLogoBkm@virTeX

```
1288 \def\HoLogoBkm@virTeX#1{%
1289   #1{v}{V}ir\hologo{TeX}%
1290 }
```

\HoLogoHtml@virTeX

```
1291 \let\HoLogoHtml@virTeX\HoLogo@virTeX
```

2.9.11 SliTeX

Definitions of the three variants.

\HoLogo@SLiTeX@lift

```
1292 \def\HoLogo@SLiTeX@lift#1{%
1293   \HoLogoFont@font{SLiTeX}{rm}{%
1294     S%
1295     \kern-.06em%
1296     L%
1297     \kern-.18em%
1298     \raise.32ex\hbox{\HoLogoFont@font{SLiTeX}{sc}{i}}}%
1299   \HOLOGO@discretionary
1300   \kern-.06em%
1301   \hologo{TeX}%
1302   }%
1303 }
```

\HoLogoBkm@SLiTeX@lift

```
1304 \def\HoLogoBkm@SLiTeX@lift#1{SLiTeX}
```

\HoLogoHtml@SLiTeX@lift

```
1305 \def\HoLogoHtml@SLiTeX@lift#1{%
1306   \HoLogoCss@SLiTeX@lift
1307   \HOLOGO@Span{SLiTeX-lift}{%
1308     \HoLogoFont@font{SLiTeX}{rm}{%
1309       S%
1310       \HOLOGO@Span{L}{L}%
1311       \HOLOGO@Span{i}{i}%
1312       \hologo{TeX}%
1313     }%
1314   }%
1315 }
```

\HoLogoCss@SLiTeX@lift

```
1316 \def\HoLogoCss@SLiTeX@lift{%
1317   \Css{%
1318     span.HoLogo-SLiTeX-lift span.HoLogo-L{%
1319       margin-left:-.06em;%
1320       margin-right:-.18em;%
1321     }%
1322   }%
1323   \Css{%
1324     span.HoLogo-SLiTeX-lift span.HoLogo-i{%
1325       position:relative;%
1326       top:-.32ex;%
1327       margin-right:-.06em;%
1328       font-variant:small-caps;%
1329     }%
1330   }
```

```

1330 }%
1331 \global\let\HoLogoCss@SliTeX@lift\relax
1332 }

\HoLogo@SliTeX@simple
1333 \def\HoLogo@SliTeX@simple#1{%
1334   \HoLogoFont@font{SliTeX}{rm}{%
1335     \ltx@mbox{%
1336       \HoLogoFont@font{SliTeX}{sc}{Sli}%
1337     }%
1338     \HOLOGO@discretionary
1339     \hologo{TeX}%
1340   }%
1341 }

\HoLogoBkm@SliTeX@simple
1342 \def\HoLogoBkm@SliTeX@simple#1{SliTeX}

\HoLogoHtml@SliTeX@simple
1343 \let\HoLogoHtml@SliTeX@simple\HoLogo@SliTeX@simple

\HoLogo@SliTeX@narrow
1344 \def\HoLogo@SliTeX@narrow#1{%
1345   \HoLogoFont@font{SliTeX}{rm}{%
1346     \ltx@mbox{%
1347       S%
1348       \kern-.06em%
1349       \HoLogoFont@font{SliTeX}{sc}{%
1350         l%
1351         \kern-.035em%
1352         i%
1353       }%
1354     }%
1355     \HOLOGO@discretionary
1356     \kern-.06em%
1357     \hologo{TeX}%
1358   }%
1359 }

\HoLogoBkm@SliTeX@narrow
1360 \def\HoLogoBkm@SliTeX@narrow#1{SliTeX}

\HoLogoHtml@SliTeX@narrow
1361 \def\HoLogoHtml@SliTeX@narrow#1{%
1362   \HoLogoCss@SliTeX@narrow
1363   \HOLOGO@Span{SliTeX-narrow}{%
1364     \HoLogoFont@font{SliTeX}{rm}{%
1365       S%
1366       \HOLOGO@Span{l}{l}%
1367       \HOLOGO@Span{i}{i}%
1368     \hologo{TeX}%
1369     }%
1370   }%
1371 }

\HoLogoCss@SliTeX@narrow
1372 \def\HoLogoCss@SliTeX@narrow{%

```

```

1373 \Css{%
1374     span.HoLogo-SLiTeX-narrow span.HoLogo-l{%
1375         margin-left:-.06em;%
1376         margin-right:-.035em;%
1377         font-variant:small-caps;%
1378     }%
1379 }%
1380 \Css{%
1381     span.HoLogo-SLiTeX-narrow span.HoLogo-i{%
1382         margin-right:-.06em;%
1383         font-variant:small-caps;%
1384     }%
1385 }%
1386 \global\let\HoLogoCss@SLiTeX@narrow\relax
1387 }

```

Macro set completion.

```

\HoLogo@SLiTeX@simple
1388 \def\HoLogo@SLiTeX@simple{\HoLogo@SLiTeX@simple}

\HoLogoBkm@SLiTeX@simple
1389 \def\HoLogoBkm@SLiTeX@simple{\HoLogoBkm@SLiTeX@simple}

\HoLogoHtml@SLiTeX@simple
1390 \def\HoLogoHtml@SLiTeX@simple{\HoLogoHtml@SLiTeX@simple}

\HoLogo@SLiTeX@narrow
1391 \def\HoLogo@SLiTeX@narrow{\HoLogo@SLiTeX@narrow}

\HoLogoBkm@SLiTeX@narrow
1392 \def\HoLogoBkm@SLiTeX@narrow{\HoLogoBkm@SLiTeX@narrow}

\HoLogoHtml@SLiTeX@narrow
1393 \def\HoLogoHtml@SLiTeX@narrow{\HoLogoHtml@SLiTeX@narrow}

\HoLogo@SLiTeX@lift
1394 \def\HoLogo@SLiTeX@lift{\HoLogo@SLiTeX@lift}

\HoLogoBkm@SLiTeX@lift
1395 \def\HoLogoBkm@SLiTeX@lift{\HoLogoBkm@SLiTeX@lift}

\HoLogoHtml@SLiTeX@lift
1396 \def\HoLogoHtml@SLiTeX@lift{\HoLogoHtml@SLiTeX@lift}

```

Defaults.

```

\HoLogo@SLiTeX
1397 \def\HoLogo@SLiTeX{\HoLogo@SLiTeX@lift}

\HoLogoBkm@SLiTeX
1398 \def\HoLogoBkm@SLiTeX{\HoLogoBkm@SLiTeX@lift}

\HoLogoHtml@SLiTeX
1399 \def\HoLogoHtml@SLiTeX{\HoLogoHtml@SLiTeX@lift}

```

\HoLogo@SliTeX

```
1400 \def\HoLogo@SliTeX{\HoLogo@SliTeX@narrow}
```

\HoLogoBkm@SliTeX

```
1401 \def\HoLogoBkm@SliTeX{\HoLogoBkm@SliTeX@narrow}
```

\HoLogoHtml@SliTeX

```
1402 \def\HoLogoHtml@SliTeX{\HoLogoHtml@SliTeX@narrow}
```

2.9.12 LuaTeX

\HoLogo@LuaTeX The kerning is an idea of Hans Hagen, see mailing list ‘luatex at tug dot org’ in March 2010.

```
1403 \def\HoLogo@LuaTeX#1{%
1404   \HOLOGO@mbbox{%
1405     Lua%
1406     \HOLOGO@NegativeKerning{aT,oT,To}%
1407     \holologo{TeX}%
1408   }%
1409 }
```

\HoLogoHtml@LuaTeX

```
1410 \let\HoLogoHtml@LuaTeX\HoLogo@LuaTeX
```

2.9.13 LuaLaTeX

\HoLogo@LuaLaTeX

```
1411 \def\HoLogo@LuaLaTeX#1{%
1412   \HOLOGO@mbbox{%
1413     Lua%
1414     \holologo{LaTeX}%
1415   }%
1416 }
```

\HoLogoHtml@LuaLaTeX

```
1417 \let\HoLogoHtml@LuaLaTeX\HoLogo@LuaLaTeX
```

2.9.14 X_TTeX, X_TLaTeX

\HOLOGO@IfCharExists

```
1418 \ifluatex
1419   \ifnum\luatexversion<36 %
1420   \else
1421     \def\HOLOGO@IfCharExists#1{%
1422       \ifnum
1423         \directlua{%
1424           if luaotfload and luaotfload.aux then
1425             if luaotfload.aux.font_has_glyph(%
1426               font.current(), \number#1) then %
1427               tex.print("1") %
1428             end %
1429           elseif font and font.fonts and font.current then %
1430             local f = font.fonts[font.current()]%
1431             if f.characters and f.characters[\number#1] then %
1432               tex.print("1")%
1433             end %
1434           }
1435     }
1436   \fi
1437 }
```

```

1434         end%
1435         }0=\ltx@zero
1436         \expandafter\ltx@secondoftwo
1437     \else
1438         \expandafter\ltx@firstoftwo
1439     \fi
1440 }%
1441 \fi
1442 \fi
1443 \ltx@ifundefined{HOLOGO@ifCharExists}{%
1444 \def\HOLOGO@ifCharExists#1{%
1445     \begingroup
1446     \tracinglostchars=\ltx@zero
1447     \setbox\ltx@zero=\hbox{%
1448         \kern7sp\char#1\relax
1449         \ifnum\lastkern>\ltx@zero
1450             \expandafter\aftergroup\csname iffalse\endcsname
1451         \else
1452             \expandafter\aftergroup\csname iftrue\endcsname
1453         \fi
1454     }%
1455     % \if{true|false} from \aftergroup
1456     \endgroup
1457     \expandafter\ltx@firstoftwo
1458 \else
1459     \endgroup
1460     \expandafter\ltx@secondoftwo
1461 \fi
1462 }%
1463 \ifxetex
1464     \ltx@ifundefined{XeTeXfonttype}{}{%
1465         \ltx@ifundefined{XeTeXcharglyph}{}{%
1466             \def\HOLOGO@ifCharExists#1{%
1467                 \ifnum\XeTeXfonttype\font>\ltx@zero
1468                     \expandafter\ltx@firstofthree
1469                 \else
1470                     \expandafter\ltx@gobble
1471                 \fi
1472             }%
1473             \ifnum\XeTeXcharglyph#1>\ltx@zero
1474                 \expandafter\ltx@firstoftwo
1475             \else
1476                 \expandafter\ltx@secondoftwo
1477             \fi
1478         }%
1479         \HOLOGO@ifCharExists{#1}%
1480     }%
1481 }%
1482 }%
1483 \fi
1484 }{}
1485 \ltx@ifundefined{HOLOGO@ifCharExists}{%
1486     \ifnum64=``^^^0040\relax % test for big chars of LuaTeX/XeTeX
1487     \let\HOLOGO@ifCharExists\HOLOGO@ifCharExists
1488 \else
1489     \def\HOLOGO@ifCharExists#1{%
1490         \ifnum#1>255 %
1491             \expandafter\ltx@fourthoffour

```



```

1492     \fi
1493     \HOLOGO@IfCharExists{#1}%
1494 }%
1495 \fi
1496 }{}

```

\HoLogo@Xe Source: package dtklogos

```

1497 \def\HoLogo@Xe#1{%
1498   X%
1499   \kern-.1em\relax
1500   \HOLOGO@IfCharExists{"018E}{%
1501     \lower.5ex\hbox{\char"018E}%
1502 }{%
1503   \chardef\HOLOGO@choice=\ltx@zero
1504   \ifdim\fontdimen\ltx@one\font>0pt %
1505     \ltx@ifundefined{rotatebox}{%
1506       \ltx@ifundefined{pgftext}{%
1507         \ltx@ifundefined{psscalebox}{%
1508           \ltx@ifundefined{HOLOGO@ScaleBox@}\hologoDriver}{%
1509             }{%
1510               \chardef\HOLOGO@choice=4 %
1511             }%
1512           }{%
1513             \chardef\HOLOGO@choice=3 %
1514           }%
1515         }{%
1516           \chardef\HOLOGO@choice=2 %
1517         }%
1518       }{%
1519         \chardef\HOLOGO@choice=1 %
1520       }%
1521     \ifcase\HOLOGO@choice
1522       \HOLOGO@WarningUnsupportedDriver{Xe}%
1523       e%
1524     \or % 1: \rotatebox
1525       \begingroup
1526         \setbox\ltx@zero\hbox{\rotatebox{180}{E}}%
1527         \ltx@LocDimenA=\dp\ltx@zero
1528         \advance\ltx@LocDimenA by -.5ex\relax
1529         \raise\ltx@LocDimenA\box\ltx@zero
1530       \endgroup
1531     \or % 2: \pgftext
1532       \lower.5ex\hbox{%
1533         \pgfpicture
1534           \pgftext[rotate=180]{E}%
1535         \endpgfpicture
1536       }%
1537     \or % 3: \psscalebox
1538       \begingroup
1539         \setbox\ltx@zero\hbox{\psscalebox{-1 -1}{E}}%
1540         \ltx@LocDimenA=\dp\ltx@zero
1541         \advance\ltx@LocDimenA by -.5ex\relax
1542         \raise\ltx@LocDimenA\box\ltx@zero
1543       \endgroup
1544     \or % 4: \HOLOGO@PointReflectBox
1545       \lower.5ex\hbox{\HOLOGO@PointReflectBox{E}}%
1546     \else
1547       \@PackageError{hologo}{Internal error (choice/it)}\@ehc

```

```

1548 \fi
1549 \else
1550 \ltx@ifundefined{reflectbox}{%
1551 \ltx@ifundefined{pgftext}{%
1552 \ltx@ifundefined{psscalebox}{%
1553 \ltx@ifundefined{HOLOGO@ScaleBox@hologoDriver}{%
1554 }{%
1555 \chardef\HOLOGO@choice=4 %
1556 }%
1557 }{%
1558 \chardef\HOLOGO@choice=3 %
1559 }%
1560 }{%
1561 \chardef\HOLOGO@choice=2 %
1562 }%
1563 }{%
1564 \chardef\HOLOGO@choice=1 %
1565 }%
1566 \ifcase\HOLOGO@choice
1567 \HOLOGO@WarningUnsupportedDriver{Xe}%
1568 e%
1569 \or % 1: reflectbox
1570 \lower.5ex\hbox{%
1571 \reflectbox{E}%
1572 }%
1573 \or % 2: \pgftext
1574 \lower.5ex\hbox{%
1575 \pgfpicture
1576 \pgftransformxscale{-1}%
1577 \pgftext{E}%
1578 \endpgfpicture
1579 }%
1580 \or % 3: \psscalebox
1581 \lower.5ex\hbox{%
1582 \psscalebox{-1 1}{E}%
1583 }%
1584 \or % 4: \HOLOGO@Reflectbox
1585 \lower.5ex\hbox{%
1586 \HOLOGO@ReflectBox{E}%
1587 }%
1588 \else
1589 \@PackageError{hologo}{Internal error (choice/up)}{\@ehc
1590 \fi
1591 \fi
1592 }%
1593 }

```

\HoLogoHtml@Xe

```

1594 \def\HoLogoHtml@Xe#1{%
1595 \HoLogoCss@Xe
1596 \HOLOGO@Span{Xe}{%
1597 X%
1598 \HOLOGO@Span{e}{%
1599 \HCode{&\ltx@hashchar x018e;}%
1600 }%
1601 }%
1602 }

```

\HoLogoCss@Xe

```
1603 \def\HoLogoCss@Xe{%
1604   \Css{%
1605     span.HoLogo-Xe span.HoLogo-e{%
1606       position:relative;%
1607       top:.5ex;%
1608       left-margin:-.1em;%
1609     }%
1610   }%
1611   \global\let\HoLogoCss@Xe\relax
1612 }
```

\HoLogo@XeTeX

```
1613 \def\HoLogo@XeTeX#1{%
1614   \hologo{Xe}%
1615   \kern-.15em\relax
1616   \hologo{TeX}%
1617 }
```

\HoLogoHtml@XeTeX

```
1618 \def\HoLogoHtml@XeTeX#1{%
1619   \HoLogoCss@XeTeX
1620   \HOLOGO@Span{XeTeX}{%
1621     \hologo{Xe}%
1622     \hologo{TeX}%
1623   }%
1624 }
```

\HoLogoCss@XeTeX

```
1625 \def\HoLogoCss@XeTeX{%
1626   \Css{%
1627     span.HoLogo-XeTeX span.HoLogo-TeX{%
1628       margin-left:-.15em;%
1629     }%
1630   }%
1631   \global\let\HoLogoCss@XeTeX\relax
1632 }
```

\HoLogo@XeLaTeX

```
1633 \def\HoLogo@XeLaTeX#1{%
1634   \hologo{Xe}%
1635   \kern-.13em%
1636   \hologo{LaTeX}%
1637 }
```

\HoLogoHtml@XeLaTeX

```
1638 \def\HoLogoHtml@XeLaTeX#1{%
1639   \HoLogoCss@XeLaTeX
1640   \HOLOGO@Span{XeLaTeX}{%
1641     \hologo{Xe}%
1642     \hologo{LaTeX}%
1643   }%
1644 }
```

\HoLogoCss@XeLaTeX

```
1645 \def\HoLogoCss@XeLaTeX{%
1646   \Css{%
```

```

1647     span.HoLogo-XeLaTeX span.HoLogo-Xe{%
1648         margin-right:-.13em;%
1649     }%
1650 }%
1651 \global\let\HoLogoCss@XeLaTeX\relax
1652 }

```

2.9.15 pdfTeX, pdfLaTeX

\HoLogo@pdfTeX

```

1653 \def\HoLogo@pdfTeX#1{%
1654     \HOLOGO@mbbox{%
1655         #1{p}{P}df\hologo{TeX}%
1656     }%
1657 }

```

\HoLogoCs@pdfTeX

```

1658 \def\HoLogoCs@pdfTeX#1{#1{p}{P}dfTeX}

```

\HoLogoBkm@pdfTeX

```

1659 \def\HoLogoBkm@pdfTeX#1{%
1660     #1{p}{P}df\hologo{TeX}%
1661 }

```

\HoLogoHtml@pdfTeX

```

1662 \let\HoLogoHtml@pdfTeX\HoLogo@pdfTeX

```

\HoLogo@pdfLaTeX

```

1663 \def\HoLogo@pdfLaTeX#1{%
1664     \HOLOGO@mbbox{%
1665         #1{p}{P}df\hologo{LaTeX}%
1666     }%
1667 }

```

\HoLogoCs@pdfLaTeX

```

1668 \def\HoLogoCs@pdfLaTeX#1{#1{p}{P}dfLaTeX}

```

\HoLogoBkm@pdfLaTeX

```

1669 \def\HoLogoBkm@pdfLaTeX#1{%
1670     #1{p}{P}df\hologo{LaTeX}%
1671 }

```

\HoLogoHtml@pdfLaTeX

```

1672 \let\HoLogoHtml@pdfLaTeX\HoLogo@pdfLaTeX

```

2.9.16 VTeX

\HoLogo@VTeX

```

1673 \def\HoLogo@VTeX#1{%
1674     \HOLOGO@mbbox{%
1675         V\hologo{TeX}%
1676     }%
1677 }

```

\HoLogoHtml@VTeX

```

1678 \let\HoLogoHtml@VTeX\HoLogo@VTeX

```

2.9.17 $\mathcal{M}\mathcal{S}$, ...

Source: class amsdtx

`\HoLogo@AmS`

```
1679 \def\HoLogo@AmS#1{%
1680   \HoLogoFont@font{AmS}{sy}{%
1681     A%
1682     \kern-.1667em%
1683     \lower.5ex\hbox{M}%
1684     \kern-.125em%
1685     S%
1686   }%
1687 }
```

`\HoLogoBkm@AmS`

```
1688 \def\HoLogoBkm@AmS#1{AmS}
```

`\HoLogoHtml@AmS`

```
1689 \def\HoLogoHtml@AmS#1{%
1690   \HoLogoCss@AmS
1691 %   \HoLogoFont@font{AmS}{sy}{%
1692     \HOLOGO@Span{AmS}{%
1693       A%
1694       \HOLOGO@Span{M}{M}%
1695       S%
1696     }%
1697 %   }%
1698 }
```

`\HoLogoCss@AmS`

```
1699 \def\HoLogoCss@AmS{%
1700   \Css{%
1701     span.HoLogo-AmS span.HoLogo-M{%
1702       position:relative;%
1703       top:.5ex;%
1704       margin-left:-.1667em;%
1705       margin-right:-.125em;%
1706       text-decoration:none;%
1707     }%
1708   }%
1709   \global\let\HoLogoCss@AmS\relax
1710 }
```

`\HoLogo@AmSTeX`

```
1711 \def\HoLogo@AmSTeX#1{%
1712   \hologo{AmS}%
1713   \HOLOGO@hyphen
1714   \hologo{TeX}%
1715 }
```

`\HoLogoBkm@AmSTeX`

```
1716 \def\HoLogoBkm@AmSTeX#1{AmS-TeX}%
```

`\HoLogoHtml@AmSTeX`

```
1717 \let\HoLogoHtml@AmSTeX\HoLogo@AmSTeX
```

\HoLogo@AmSLaTeX

```
1718 \def\HoLogo@AmSLaTeX#1{%
1719   \hologo{AmS}%
1720   \HOLOGO@hyphen
1721   \hologo{LaTeX}%
1722 }
```

\HoLogoBkm@AmSLaTeX

```
1723 \def\HoLogoBkm@AmSLaTeX#1{AmS-LaTeX}%
```

\HoLogoHtml@AmSLaTeX

```
1724 \let\HoLogoHtml@AmSLaTeX\HoLogo@AmSLaTeX
```

2.9.18 BibTeX

\HoLogo@BibTeX@sc A definition of BibTeX is provided in the documentation source for the manual of BibTeX [1].

```
\def\BibTeX{%
  \rm
  B%
  \kern-.05em%
  {\sc
  i%
  \kern-.025em%
  b%
  }%
  \kern-.08em
  T%
  \kern-.1667em%
  \lower.7ex\hbox{E}%
  \kern-.125em%
  X%
  }%
}
```

```
1725 \def\HoLogo@BibTeX@sc#1{%
1726   B%
1727   \kern-.05em%
1728   \HoLogoFont@font{BibTeX}{sc}{%
1729     i%
1730     \kern-.025em%
1731     b%
1732   }%
1733   \HOLOGO@discretionary
1734   \kern-.08em%
1735   \hologo{TeX}%
1736 }
```

\HoLogoHtml@BibTeX@sc

```
1737 \def\HoLogoHtml@BibTeX@sc#1{%
1738   \HoLogoCss@BibTeX@sc
1739   \HOLOGO@Span{BibTeX-sc}{%
1740     B%
1741     \HOLOGO@Span{i}{i}%
1742     \HOLOGO@Span{b}{b}%
1743   }
```

```

1743 \hologo{TeX}%
1744 }%
1745 }

```

\HoLogoCss@BibTeX@sc

```

1746 \def\HoLogoCss@BibTeX@sc{%
1747 \Css{%
1748 span.HoLogo-BibTeX-sc span.HoLogo-i{%
1749 margin-left:-.05em;%
1750 margin-right:-.025em;%
1751 font-variant:small-caps;%
1752 }%
1753 }%
1754 \Css{%
1755 span.HoLogo-BibTeX-sc span.HoLogo-b{%
1756 margin-right:-.08em;%
1757 font-variant:small-caps;%
1758 }%
1759 }%
1760 \global\let\HoLogoCss@BibTeX@sc\relax
1761 }

```

\HoLogo@BibTeX@sf Variant sf avoids trouble with unavailable small caps fonts (e.g., bold versions of Computer Modern or Latin Modern). The definition is taken from package dtklogos [2].

```

\DeclareRobustCommand{\BibTeX}{%
  \B%
  \kern-.05em%
  \hbox{%
    \m@th$\mathsf{\fontfamily{sf}\fontseries{t}\fontshape{b}\fontsize{10pt}\selectfont}%
    \csname S@\f@size\endcsname
    \fontsize{10pt}\sf@size\z@
    \math@fontsfalse
    \selectfont
    I%
    \kern-.025em%
    B
  }%
  \kern-.08em%
  \TeX
}

```

```

1762 \def\HoLogo@BibTeX@sf#1{%
1763 B%
1764 \kern-.05em%
1765 \HoLogoFont@font{BibTeX}{bibsfont}%
1766 I%
1767 \kern-.025em%
1768 B%
1769 }%
1770 \HOLOGO@discretionary
1771 \kern-.08em%
1772 \hologo{TeX}%
1773 }

```

\HoLogoHtml@BibTeX@sf

```

1774 \def\HoLogoHtml@BibTeX@sf#1{%

```

```

1775 \HoLogoCss@BibTeX@sf
1776 \HOLG0@Span{BibTeX-sf}{%
1777   B%
1778   \HoLogoFont@font{BibTeX}{bibs}{%
1779     \HOLG0@Span{i}{I}%
1780     B%
1781   }%
1782   \holo{TeX}%
1783 }%
1784 }

```

\HoLogoCss@BibTeX@sf

```

1785 \def\HoLogoCss@BibTeX@sf{%
1786   \Css{%
1787     span.HoLogo-BibTeX-sf span.HoLogo-i{%
1788       margin-left:-.05em;%
1789       margin-right:-.025em;%
1790     }%
1791   }%
1792   \Css{%
1793     span.HoLogo-BibTeX-sf span.HoLogo-TeX{%
1794       margin-left:-.08em;%
1795     }%
1796   }%
1797   \global\let\HoLogoCss@BibTeX@sf\relax
1798 }

```

\HoLogo@BibTeX

```

1799 \def\HoLogo@BibTeX{\HoLogo@BibTeX@sf}

```

\HoLogoHtml@BibTeX

```

1800 \def\HoLogoHtml@BibTeX{\HoLogoHtml@BibTeX@sf}

```

2.9.19 BIB_TEX₈

\HoLogo@BibTeX₈

```

1801 \expandafter\def\csname HoLogo@BibTeX8\endcsname#1{%
1802   \holo{BibTeX}%
1803   8%
1804 }

```

\HoLogoBkm@BibTeX₈

```

1805 \expandafter\def\csname HoLogoBkm@BibTeX8\endcsname#1{%
1806   \holo{BibTeX}%
1807   8%
1808 }

```

\HoLogoHtml@BibTeX₈

```

1809 \expandafter
1810 \let\csname HoLogoHtml@BibTeX8\expandafter\endcsname
1811 \csname HoLogo@BibTeX8\endcsname

```

2.9.20 Con_TEX_t

\HoLogo@ConTeXt@simple

```

1812 \def\HoLogo@ConTeXt@simple#1{%
1813   \HOLG0@mbox{Con}%

```



```

1814 \HOLOGO@discretionary
1815 \HOLOGO@mbbox{\hologo{TeX}t}%
1816 }

```

\HoLogoHtml@ConTeXt@simple

```

1817 \let\HoLogoHtml@ConTeXt@simple\HoLogo@ConTeXt@simple

```

\HoLogo@ConTeXt@narrow This definition of logo ConTeXt with variant narrow comes from TUGboat's class ltugboat (version 2010/11/15 v2.8).

```

1818 \def\HoLogo@ConTeXt@narrow#1{%
1819   \HOLOGO@mbbox{C\kern-.0333emon}%
1820   \HOLOGO@discretionary
1821   \kern-.0667em%
1822   \HOLOGO@mbbox{\hologo{TeX}\kern-.0333emt}%
1823 }

```

\HoLogoHtml@ConTeXt@narrow

```

1824 \def\HoLogoHtml@ConTeXt@narrow#1{%
1825   \HoLogoCss@ConTeXt@narrow
1826   \HOLOGO@Span{ConTeXt-narrow}{%
1827     \HOLOGO@Span{C}{C}%
1828     on%
1829     \hologo{TeX}%
1830     t%
1831   }%
1832 }

```

\HoLogoCss@ConTeXt@narrow

```

1833 \def\HoLogoCss@ConTeXt@narrow{%
1834   \Css{%
1835     span.HoLogo-ConTeXt-narrow span.HoLogo-C{%
1836       margin-left:-.0333em;%
1837     }%
1838   }%
1839   \Css{%
1840     span.HoLogo-ConTeXt-narrow span.HoLogo-TeX{%
1841       margin-left:-.0667em;%
1842       margin-right:-.0333em;%
1843     }%
1844   }%
1845   \global\let\HoLogoCss@ConTeXt@narrow\relax
1846 }

```

\HoLogo@ConTeXt

```

1847 \def\HoLogo@ConTeXt{\HoLogo@ConTeXt@narrow}

```

\HoLogoHtml@ConTeXt

```

1848 \def\HoLogoHtml@ConTeXt{\HoLogoHtml@ConTeXt@narrow}

```

2.9.21 emTeX

\HoLogo@emTeX

```

1849 \def\HoLogo@emTeX#1{%
1850   \HOLOGO@mbbox{#1{e}{E}m}%
1851   \HOLOGO@discretionary
1852   \hologo{TeX}%
1853 }

```

```

\HoLogoCs@emTeX
1854 \def\HoLogoCs@emTeX#1{#1{e}{E}mTeX}%

\HoLogoBkm@emTeX
1855 \def\HoLogoBkm@emTeX#1{%
1856   #1{e}{E}m\hologo{TeX}%
1857 }

\HoLogoHtml@emTeX
1858 \let\HoLogoHtml@emTeX\HoLogo@emTeX

```

2.9.22 ε_X TeX

\HoLogo@ExTeX The definition is taken from the FAQ of the project ε_X TeX [4].

```

\def\ExTeX{%
  \textrm{\Logo_always_with_serifs
  \ensuremath{%
    \textstyle
    \varepsilon_{%
      \kern-0.15em%
      \mathcal{X}}%
    }%
  }%
  \kern-.15em%
  \TeX
}%

1859 \def\HoLogo@ExTeX#1{%
1860   \HoLogoFont@font{ExTeX}{rm}{%
1861     \ltx@mbbox{%
1862       \HOLOGO@MathSetup
1863       $%
1864       \textstyle
1865       \varepsilon_{%
1866         \kern-0.15em%
1867         \HoLogoFont@font{ExTeX}{sy}{X}%
1868       }%
1869       $%
1870     }%
1871     \HOLOGO@discretionary
1872     \kern-.15em%
1873     \hologo{TeX}%
1874   }%
1875 }

\HoLogoHtml@ExTeX
1876 \def\HoLogoHtml@ExTeX#1{%
1877   \HoLogoCss@ExTeX
1878   \HoLogoFont@font{ExTeX}{rm}{%
1879     \HOLOGO@Span{ExTeX}{%
1880       \ltx@mbbox{%
1881         \HOLOGO@MathSetup
1882         $\textstyle\varepsilon_{%
1883           \HOLOGO@Span{X}{$\textstyle\chi$}%
1884         \hologo{TeX}%
1885       }%

```

```

1886     }%
1887 }%
1888 }

\HoLogoBkm@ExTeX
1889 \def\HoLogoBkm@ExTeX#1{%
1890   \HOLOGO@PdfdocUnicode{#1{e}{E}x}{\textepsilon\textchi}%
1891   \hologo{TeX}%
1892 }

\HoLogoCss@ExTeX
1893 \def\HoLogoCss@ExTeX{%
1894   \Css{%
1895     span.HoLogo-ExTeX{%
1896       font-family:serif;%
1897     }%
1898   }%
1899   \Css{%
1900     span.HoLogo-ExTeX span.HoLogo-TeX{%
1901       margin-left:-.15em;%
1902     }%
1903   }%
1904   \global\let\HoLogoCss@ExTeX\relax
1905 }

```

2.9.23 MiKTeX

```

\HoLogo@MiKTeX
1906 \def\HoLogo@MiKTeX#1{%
1907   \HOLOGO@mbbox{MiK}%
1908   \HOLOGO@discretionary
1909   \hologo{TeX}%
1910 }

\HoLogoHtml@MiKTeX
1911 \let\HoLogoHtml@MiKTeX\HoLogo@MiKTeX

```

2.9.24 OzTeX and friends

Source: OzTeX FAQ [6]:

```

\def\OzTeX{0\kern-.03em z\kern-.15em\TeX}
(There is no kerning in OzMF, OzMP and OzTtH.)

```

```

\HoLogo@OzTeX
1912 \def\HoLogo@OzTeX#1{%
1913   0%
1914   \kern-.03em %
1915   z%
1916   \kern-.15em %
1917   \hologo{TeX}%
1918 }

\HoLogoHtml@OzTeX
1919 \def\HoLogoHtml@OzTeX#1{%
1920   \HoLogoCss@OzTeX
1921   \HOLOGO@Span{OzTeX}{%

```

```

1922      0%
1923      \HOLOGO@Span{z}{z}%
1924      \hologo{TeX}%
1925    }%
1926 }

\HoLogoCss@OzTeX
1927 \def\HoLogoCss@OzTeX{%
1928   \Css{%
1929     span.HoLogo-OzTeX span.HoLogo-z{%
1930       margin-left:-.03em;%
1931       margin-right:-.15em;%
1932     }%
1933   }%
1934   \global\let\HoLogoCss@OzTeX\relax
1935 }

\HoLogo@OzMF
1936 \def\HoLogo@OzMF#1{%
1937   \HOLOGO@mbox{OzMF}%
1938 }

\HoLogo@OzMP
1939 \def\HoLogo@OzMP#1{%
1940   \HOLOGO@mbox{OzMP}%
1941 }

\HoLogo@OzTtH
1942 \def\HoLogo@OzTtH#1{%
1943   \HOLOGO@mbox{OzTtH}%
1944 }

```

2.9.25 PCT_EX

```

\HoLogo@PCTeX
1945 \def\HoLogo@PCTeX#1{%
1946   \HOLOGO@mbox{PC}%
1947   \hologo{TeX}%
1948 }

\HoLogoHtml@PCTeX
1949 \let\HoLogoHtml@PCTeX\HoLogo@PCTeX

```

2.9.26 PiCT_EX

The original definitions from `pictex.tex` [7]:

```

\def\PiC{%
  \PiP%
  \kern-.12em%
  \lower.5ex\hbox{I}%
  \kern-.075em%
  C%
}
\def\PiCTeX{%
  \PiC
  \kern-.11em%
  TeX
}

```

\HoLogo@PiC

```
1950 \def\HoLogo@PiC#1{%
1951   P%
1952   \kern-.12em%
1953   \lower.5ex\hbox{I}%
1954   \kern-.075em%
1955   C%
1956   \HOLOGO@SpaceFactor
1957 }
```

\HoLogoHtml@PiC

```
1958 \def\HoLogoHtml@PiC#1{%
1959   \HoLogoCss@PiC
1960   \HOLOGO@Span{PiC}{%
1961     P%
1962     \HOLOGO@Span{i}{I}%
1963     C%
1964   }%
1965 }
```

\HoLogoCss@PiC

```
1966 \def\HoLogoCss@PiC{%
1967   \Css{%
1968     span.HoLogo-PiC span.HoLogo-i{%
1969       position:relative;%
1970       top:.5ex;%
1971       margin-left:-.12em;%
1972       margin-right:-.075em;%
1973       text-decoration:none;%
1974     }%
1975   }%
1976   \global\let\HoLogoCss@PiC\relax
1977 }
```

\HoLogo@PiTeX

```
1978 \def\HoLogo@PiTeX#1{%
1979   \hologo{PiC}%
1980   \HOLOGO@discretionary
1981   \kern-.11em%
1982   \hologo{TeX}%
1983 }
```

\HoLogoHtml@PiTeX

```
1984 \def\HoLogoHtml@PiTeX#1{%
1985   \HoLogoCss@PiTeX
1986   \HOLOGO@Span{PiTeX}{%
1987     \hologo{PiC}%
1988     \hologo{TeX}%
1989   }%
1990 }
```

\HoLogoCss@PiTeX

```
1991 \def\HoLogoCss@PiTeX{%
1992   \Css{%
1993     span.HoLogo-PiTeX span.HoLogo-PiC{%
1994       margin-right:-.11em;%
1995     }%
1996   }
```

```

1996 }%
1997 \global\let\HoLogoCss@PiCTeX\relax
1998 }

```

2.9.27 teTeX

```

\HoLogo@teTeX

1999 \def\HoLogo@teTeX#1{%
2000   \HOLOGO@mbbox{#1{t}{T}e}%
2001   \HOLOGO@discretionary
2002   \hologo{TeX}%
2003 }

\HoLogoCs@teTeX

2004 \def\HoLogoCs@teTeX#1{#1{t}{T}dfTeX}

\HoLogoBkm@teTeX

2005 \def\HoLogoBkm@teTeX#1{%
2006   #1{t}{T}e\hologo{TeX}%
2007 }

\HoLogoHtml@teTeX

2008 \let\HoLogoHtml@teTeX\HoLogo@teTeX

```

2.9.28 TeX4ht

```

\HoLogo@TeX4ht

2009 \expandafter\def\csname HoLogo@TeX4ht\endcsname#1{%
2010   \HOLOGO@mbbox{\hologo{TeX}4ht}%
2011 }

\HoLogoHtml@TeX4ht

2012 \expandafter
2013 \let\csname HoLogoHtml@TeX4ht\expandafter\endcsname
2014 \csname HoLogo@TeX4ht\endcsname

```

2.9.29 SageTeX

```

\HoLogo@SageTeX

2015 \def\HoLogo@SageTeX#1{%
2016   \HOLOGO@mbbox{Sage}%
2017   \HOLOGO@discretionary
2018   \HOLOGO@NegativeKerning{eT,oT,To}%
2019   \hologo{TeX}%
2020 }

\HoLogoHtml@SageTeX

2021 \let\HoLogoHtml@SageTeX\HoLogo@SageTeX

```

2.10 METAFONT and friends

```

\HoLogo@METAFONT

2022 \def\HoLogo@METAFONT#1{%
2023   \HoLogoFont@font{METAFONT}{logo}{%
2024     \HOLOGO@mbbox{META}%
2025     \HOLOGO@discretionary

```

```

2026 \Hologo@mbox{FONT}%
2027 }%
2028 }

```

\Hologo@METAPOST

```

2029 \def\Hologo@METAPOST#1{%
2030 \HologoFont@font{METAPOST}{logo}{%
2031 \Hologo@mbox{META}%
2032 \Hologo@discretionary
2033 \Hologo@mbox{POST}%
2034 }%
2035 }

```

\Hologo@MetaFun

```

2036 \def\Hologo@MetaFun#1{%
2037 \Hologo@mbox{Meta}%
2038 \Hologo@discretionary
2039 \Hologo@mbox{Fun}%
2040 }

```

\Hologo@MetaPost

```

2041 \def\Hologo@MetaPost#1{%
2042 \Hologo@mbox{Meta}%
2043 \Hologo@discretionary
2044 \Hologo@mbox{Post}%
2045 }

```

2.11 Others

2.11.1 biber

\Hologo@biber

```

2046 \def\Hologo@biber#1{%
2047 \Hologo@mbox{#1{b}{B}i}%
2048 \Hologo@discretionary
2049 \Hologo@mbox{ber}%
2050 }

```

\HologoCs@biber

```

2051 \def\HologoCs@biber#1{#1{b}{B}iber}

```

\HologoBkm@biber

```

2052 \def\HologoBkm@biber#1{%
2053 #1{b}{B}iber%
2054 }

```

\HologoHtml@biber

```

2055 \let\HologoHtml@biber\Hologo@biber

```

2.11.2 KOMA-Script

\Hologo@KOMAScript The definition for KOMA-Script is taken from KOMA-Script (scrlogo.dtx, reformatted) [8]:

```

\@ifundefined{KOMAScript}{%
  \DeclareRobustCommand{\KOMAScript}{%
    \textsf{

```

```

        \kern.05em\kern.05emM\kern.05emA%
        \kern.1em-\kern.1em%
        Script%
    }%
} %
} {}

2056 \def\HoLogo@KOMAScript#1{%
2057   \HoLogoFont@font{KOMAScript}{sf}{%
2058     \HOLOGO@mbox{%
2059       K\kern.05em%
2060       O\kern.05em%
2061       M\kern.05em%
2062       A%
2063     }%
2064     \kern.1em%
2065     \HOLOGO@hyphen
2066     \kern.1em%
2067     \HOLOGO@mbox{Script}%
2068   }%
2069 }

\HoLogoBkm@KOMAScript

2070 \def\HoLogoBkm@KOMAScript#1{%
2071   KOMA-Script%
2072 }

\HoLogoHtml@KOMAScript

2073 \def\HoLogoHtml@KOMAScript#1{%
2074   \HoLogoCss@KOMAScript
2075   \HoLogoFont@font{KOMAScript}{sf}{%
2076     \HOLOGO@Span{KOMAScript}{%
2077       K%
2078       \HOLOGO@Span{O}{O}%
2079       M%
2080       \HOLOGO@Span{A}{A}%
2081       \HOLOGO@Span{hyphen}{-}%
2082       Script%
2083     }%
2084   }%
2085 }

\HoLogoCss@KOMAScript

2086 \def\HoLogoCss@KOMAScript{%
2087   \Css{%
2088     span.HoLogo-KOMAScript{%
2089       font-family:sans-serif;%
2090     }%
2091   }%
2092   \Css{%
2093     span.HoLogo-KOMAScript span.HoLogo-O{%
2094       padding-left:.05em;%
2095       padding-right:.05em;%
2096     }%
2097   }%
2098   \Css{%
2099     span.HoLogo-KOMAScript span.HoLogo-A{%
2100       padding-left:.05em;%

```



```

2101 }%
2102 }%
2103 \Css{%
2104     span.HoLogo-KOMAScript span.HoLogo-hyphen{%
2105         padding-left:.1em;%
2106         padding-right:.1em;%
2107     }%
2108 }%
2109 \global\let\HoLogoCss@KOMAScript\relax
2110 }

```

2.11.3 LyX

\HoLogo@LyX The definition is taken from the documentation source files of LyX, Intro.lyx [5]:

```

\def\LyX{%
  \texorpdfstring{%
    \L\kern-.1667em\lower.25em\hbox{Y}\kern-.125emX\@%
  }{%
    \LyX%
  }%
}

2111 \def\HoLogo@LyX#1{%
2112   L%
2113   \kern-.1667em%
2114   \lower.25em\hbox{Y}%
2115   \kern-.125em%
2116   X%
2117   \HOLOGO@SpaceFactor
2118 }

```

\HoLogoHtml@LyX

```

2119 \def\HoLogoHtml@LyX#1{%
2120   \HoLogoCss@LyX
2121   \HOLOGO@Span{LyX}{%
2122     L%
2123     \HOLOGO@Span{y}{Y}%
2124     X%
2125   }%
2126 }

```

\HoLogoCss@LyX

```

2127 \def\HoLogoCss@LyX{%
2128   \Css{%
2129     span.HoLogo-LyX span.HoLogo-y{%
2130       position:relative;%
2131       top:.25em;%
2132       margin-left:-.1667em;%
2133       margin-right:-.125em;%
2134       text-decoration:none;%
2135     }%
2136   }%
2137   \global\let\HoLogoCss@LyX\relax
2138 }

```

2.11.4 $\mathcal{N}\mathcal{S}$

\HoLogo@NTS Definition for $\mathcal{N}\mathcal{S}$ can be found in package etex_man for the ε -TeX manual [3] and in package dtklogos [2]:

```

\def\NTS{%
  \leavevmode
  \hbox{%
    $%
    \cal N%
    \kern-0.35em%
    \lower0.5ex\hbox{$\cal T$}%
    \kern-0.2em%
    S%
    $%
  }%
}

2139 \def\HoLogo@NTS#1{%
2140   \HoLogoFont@font{NTS}{sy}{%
2141     N\/%
2142     \kern-.35em%
2143     \lower.5ex\hbox{T\}%
2144     \kern-.2em%
2145     S\/%
2146   }%
2147   \HOLOGO@SpaceFactor
2148 }

```

2.11.5 T_TH (T_EX to HTML translator)

Source: <http://hutchinson.belmont.ma.us/tth/> In the HTML source the second ‘T’ is printed as subscript.

```

T<sub>T</sub>H

\HoLogo@TTH

2149 \def\HoLogo@TTH#1{%
2150   \ltx@mbox{%
2151     T\HOLOGO@SubScript{T}H%
2152   }%
2153   \HOLOGO@SpaceFactor
2154 }

\HoLogoHtml@TTH

2155 \def\HoLogoHtml@TTH#1{%
2156   T\HCode{<sub>}T\HCode{</sub>}H%
2157 }

```

2.11.6 Hàn Thế Thành

Partial source: Package dtklogos. The double accent is U+1EBF (latin small letter e with circumflex and acute).

```

\HoLogo@HanTheThanh

2158 \def\HoLogo@HanTheThanh#1{%
2159   \ltx@mbox{H\`an}%
2160   \HOLOGO@space
2161   \ltx@mbox{%
2162     Th%
2163     \HOLOGO@IfCharExists{"1EBF}{%
2164       \char"1EBF\relax
2165     }{%

```

```

2166      \^e\hbox to 0pt{\hss\raise .5ex\hbox{'{}}}%
2167    }%
2168  }%
2169  \HOLOGO@space
2170  \ltx@mbox{Th\`anh}%
2171 }

```

\HoLogoBkm@HanTheThanh

```

2172 \def\HoLogoBkm@HanTheThanh#1{%
2173   H\`an %
2174   Th\HOLOGO@PdfdocUnicode{\^e}{\9036\277} %
2175   Th\`anh%
2176 }

```

\HoLogoHtml@HanTheThanh

```

2177 \def\HoLogoHtml@HanTheThanh#1{%
2178   H\`an %
2179   Th\HCode{&\ltx@hashchar x1ebf;} %
2180   Th\`anh%
2181 }

```

2.12 Driver detection

```

2182 \HOLOGO@IfExists\InputIfFileExists{%
2183   \InputIfFileExists{holologo.cfg}{}{}%
2184 }{%
2185   \ltx@ifundefined{pdf@filesize}{%
2186     \def\HOLOGO@InputIfExists{%
2187       \openin\HOLOGO@temp=holologo.cfg\relax
2188       \ifeof\HOLOGO@temp
2189         \closein\HOLOGO@temp
2190       \else
2191         \closein\HOLOGO@temp
2192       \begingroup
2193         \def\x{LaTeX2e}%
2194         \expandafter\endgroup
2195         \ifx\fmtname\x
2196           \input{holologo.cfg}%
2197         \else
2198           \input holologo.cfg\relax
2199         \fi
2200       \fi
2201     }%
2202   \ltx@ifundefined{newread}{%
2203     \chardef\HOLOGO@temp=15 %
2204     \def\HOLOGO@CheckRead{%
2205       \ifeof\HOLOGO@temp
2206         \HOLOGO@InputIfExists
2207       \else
2208         \ifcase\HOLOGO@temp
2209           \@PackageWarningNoLine{holologo}{%
2210             Configuration file ignored, because\MessageBreak
2211             a free read register could not be found%
2212           }%
2213         \else
2214           \begingroup
2215             \count\ltx@cclv=\HOLOGO@temp
2216             \advance\ltx@cclv by \ltx@minusone

```

```

2217         \edef\x{\endgroup
2218         \chardef\noexpand\HOLOGO@temp=\the\count\ltx@cclv
2219         \relax
2220         }%
2221     \x
2222     \fi
2223 \fi
2224 }%
2225 }{%
2226     \csname newread\endcsname\HOLOGO@temp
2227     \HOLOGO@InputIfExists
2228 }%
2229 }{%
2230     \edef\HOLOGO@temp{\pdf@filesize{hologo.cfg}}%
2231     \ifx\HOLOGO@temp\ltx@empty
2232     \else
2233         \ifnum\HOLOGO@temp>0 %
2234             \begingroup
2235                 \def\x{LaTeX2e}%
2236                 \expandafter\endgroup
2237                 \ifx\fmtname\x
2238                     \input{hologo.cfg}%
2239                 \else
2240                     \input hologo.cfg\relax
2241                 \fi
2242             \else
2243                 \@PackageInfoNoLine{hologo}{%
2244                     Empty configuration file `hologo.cfg' ignored%
2245                 }%
2246             \fi
2247         \fi
2248     }%
2249 }

2250 \def\HOLOGO@temp#1#2{%
2251     \kv@define@key{HoLogoDriver}{#1}[]{}%
2252     \begingroup
2253         \def\HOLOGO@temp{##1}%
2254         \ltx@onelevel@sanitize\HOLOGO@temp
2255         \ifx\HOLOGO@temp\ltx@empty
2256         \else
2257             \@PackageError{hologo}{%
2258                 Value (\HOLOGO@temp) not permitted for option `#1'%
2259             }%
2260             \@ehc
2261         \fi
2262     \endgroup
2263     \def\hologoDriver{#2}%
2264 }%
2265 }%
2266 \def\HOLOGO@@temp#1#2{%
2267     \ifx\kv@value\relax
2268         \HOLOGO@temp{#1}{#1}%
2269     \else
2270         \HOLOGO@temp{#1}{#2}%
2271     \fi
2272 }%
2273 \kv@parse@normalized{%
2274     pdftex,%

```

```

2275    luatex=pdftex,%
2276    dvipdfm,%
2277    dvipdfmx=dvipdfm,%
2278    dvips,%
2279    dvipsone=dvips,%
2280    xdvi=dvips,%
2281    xetex,%
2282    vtex,%
2283 } \HOLOGO@temp

2284 \kv@define@key{HoLogoDriver}{driverfallback}{%
2285   \def\HOLOGO@DriverFallback{#1}}%
2286 }

\HOLOGO@DriverFallback

2287 \def\HOLOGO@DriverFallback{dvips}

\holoDriverSetup

2288 \def\holoDriverSetup{%
2289   \let\holoDriver\ltx@undefined
2290   \HOLOGO@DriverSetup
2291 }

\HOLOGO@DriverSetup

2292 \def\HOLOGO@DriverSetup#1{%
2293   \kvsetkeys{HoLogoDriver}{#1}%
2294   \HOLOGO@CheckDriver
2295   \ltx@ifundefined{holoDriver}{%
2296     \begingroup
2297     \edef\x{\endgroup
2298       \noexpand\kvsetkeys{HoLogoDriver}{\HOLOGO@DriverFallback}}%
2299     }\x
2300   }{}%
2301   \@PackageInfoNoLine{holo}{Using driver `\'holoDriver'}%
2302 }

\HOLOGO@CheckDriver

2303 \def\HOLOGO@CheckDriver{%
2304   \ifpdf
2305     \def\holoDriver{pdftex}%
2306     \let\HOLOGO@pdfliteral\pdfliteral
2307   \ifluatex
2308     \ifx\pdfextension\@undefined\else
2309       \protected\def\pdfliteral{\pdfextension literal}%
2310       \let\HOLOGO@pdfliteral\pdfliteral
2311     \fi
2312     \ltx@ifundefined{HOLOGO@pdfliteral}{%
2313       \ifnum\luatexversion<36 %
2314       \else
2315         \begingroup
2316         \let\HOLOGO@temp\endgroup
2317         \ifcase0%
2318           \directlua{%
2319             if tex.enableprimitives then %
2320               tex.enableprimitives('HOLOGO@', {'pdfliteral'})%
2321             else %
2322               tex.print('1')%
2323             end%
2324           }%

```

```

2325         \ifx\HOLOGO@pdfliteral\@undefined 1\fi%
2326         \relax%
2327     \endgroup
2328     \let\HOLOGO@temp\relax
2329     \global\let\HOLOGO@pdfliteral\HOLOGO@pdfliteral
2330 \fi%
2331 \HOLOGO@temp
2332 \fi
2333 }{}%
2334 \fi
2335 \ltx@ifundefined{HOLOGO@pdfliteral}{%
2336     \@PackageWarningNoLine{hologo}{%
2337         Cannot find \string\pdfliteral
2338     }%
2339 }{}%
2340 \else
2341     \ifxetex
2342         \def\hologoDriver{xetex}%
2343     \else
2344         \ifvtex
2345             \def\hologoDriver{vtex}%
2346         \fi
2347     \fi
2348 \fi
2349 }

```

HOLOGO@WarningUnsupportedDriver

```

2350 \def\HOLOGO@WarningUnsupportedDriver#1{%
2351     \@PackageWarningNoLine{hologo}{%
2352         Logo `#1' needs driver specific macros.\MessageBreak
2353         but driver ``hologoDriver' is not supported.\MessageBreak
2354         Use a different driver or\MessageBreak
2355         load package `graphics' or `pgf'%
2356     }%
2357 }

```

2.12.1 Reflect box macros

Skip driver part if not needed.

```

2358 \ltx@ifundefined{reflectbox}{}{}%
2359 \ltx@ifundefined{rotatebox}{}{}%
2360     \HOLOGO@AtEnd
2361 }%
2362 }
2363 \ltx@ifundefined{pgftext}{}{}%
2364     \HOLOGO@AtEnd
2365 }
2366 \ltx@ifundefined{psscalebox}{}{}%
2367     \HOLOGO@AtEnd
2368 }
2369 \def\HOLOGO@temp{LaTeX2e}
2370 \ifx\fmtname\HOLOGO@temp
2371     \RequirePackage{kvoptions}[2011/06/30]%
2372     \ProcessKeyvalOptions{HoLogoDriver}%
2373 \fi
2374 \HOLOGO@DriverSetup{

```

\HOLOGO@ReflectBox

```

2375 \def\HOLOGO@ReflectBox#1{%
2376   \begingroup
2377   \setbox\ltx@zero\hbox{\begingroup#1\endgroup}%
2378   \setbox\ltx@two\hbox{%
2379     \kern\wd\ltx@zero
2380     \csname HOLOGO@ScaleBox@\hologoDriver\endcsname{-1}{1}{%
2381       \hbox to Opt{\copy\ltx@zero\hss}%
2382     }%
2383   }%
2384   \wd\ltx@two=\wd\ltx@zero
2385   \box\ltx@two
2386 \endgroup
2387 }

```

\HOLOGO@PointReflectBox

```

2388 \def\HOLOGO@PointReflectBox#1{%
2389   \begingroup
2390   \setbox\ltx@zero\hbox{\begingroup#1\endgroup}%
2391   \setbox\ltx@two\hbox{%
2392     \kern\wd\ltx@zero
2393     \raise\ht\ltx@zero\hbox{%
2394       \csname HOLOGO@ScaleBox@\hologoDriver\endcsname{-1}{-1}{%
2395         \hbox to Opt{\copy\ltx@zero\hss}%
2396       }%
2397     }%
2398   }%
2399   \wd\ltx@two=\wd\ltx@zero
2400   \box\ltx@two
2401 \endgroup
2402 }

```

We must define all variants because of dynamic driver setup.

```

2403 \def\HOLOGO@temp#1#2{#2}

```

\HOLOGO@ScaleBox@pdftex

```

2404 \HOLOGO@temp{pdftex}{%
2405   \def\HOLOGO@ScaleBox@pdftex#1#2#3{%
2406     \HOLOGO@pdfliteral{%
2407       q #1 0 0 #2 0 0 cm%
2408     }%
2409     #3%
2410     \HOLOGO@pdfliteral{%
2411       Q%
2412     }%
2413   }%
2414 }

```

\HOLOGO@ScaleBox@dvips

```

2415 \HOLOGO@temp{dvips}{%
2416   \def\HOLOGO@ScaleBox@dvips#1#2#3{%
2417     \special{ps:%
2418       gsave %
2419       currentpoint %
2420       currentpoint translate %
2421       #1 #2 scale %
2422       neg exch neg exch translate%
2423     }%

```

```

2424     #3%
2425     \special{ps:%
2426         currentpoint %
2427         grestore %
2428         moveto%
2429     }%
2430 }%
2431 }

```

\HOLOGO@ScaleBox@dviptdm

```

2432 \HOLOGO@temp{dviptdm}{%
2433     \let\HOLOGO@ScaleBox@dviptdm\HOLOGO@ScaleBox@dviptdm
2434 }

```

Since X_YTEX v0.6.

\HOLOGO@ScaleBox@xetex

```

2435 \HOLOGO@temp{xetex}{%
2436     \def\HOLOGO@ScaleBox@xetex#1#2#3{%
2437         \special{x:gsave}%
2438         \special{x:scale #1 #2}%
2439         #3%
2440         \special{x:grestore}%
2441     }%
2442 }

```

\HOLOGO@ScaleBox@vtex

```

2443 \HOLOGO@temp{vtex}{%
2444     \def\HOLOGO@ScaleBox@vtex#1#2#3{%
2445         \special{r(#1,0,0,#2,0,0}%
2446         #3%
2447         \special{r)}%
2448     }%
2449 }

```

```

2450 \HOLOGO@AtEnd%

```

```

2451 \endpackage

```

3 Test

3.1 Catcode checks for loading

```

2452 (*test1)
2453 \catcode`\{=1 %
2454 \catcode`\}=2 %
2455 \catcode`\#=6 %
2456 \catcode`\@=11 %
2457 \expandafter\ifx\csname count@\endcsname\relax
2458     \countdef\count@=255 %
2459 \fi
2460 \expandafter\ifx\csname @gobble\endcsname\relax
2461     \long\def\@gobble#1{}%
2462 \fi
2463 \expandafter\ifx\csname @firstofone\endcsname\relax
2464     \long\def\@firstofone#1{#1}%
2465 \fi
2466 \expandafter\ifx\csname loop\endcsname\relax

```



```

2467 \expandafter\@firstofone
2468 \else
2469 \expandafter\@gobble
2470 \fi
2471 {%
2472 \def\loop#1\repeat{%
2473 \def\body{#1}%
2474 \iterate
2475 }%
2476 \def\iterate{%
2477 \body
2478 \let\next\iterate
2479 \else
2480 \let\next\relax
2481 \fi
2482 \next
2483 }%
2484 \let\repeat=\fi
2485 }%
2486 \def\RestoreCatcodes{}
2487 \count@=0 %
2488 \loop
2489 \edef\RestoreCatcodes{%
2490 \RestoreCatcodes
2491 \catcode\the\count@=\the\catcode\count@\relax
2492 }%
2493 \ifnum\count@<255 %
2494 \advance\count@ 1 %
2495 \repeat
2496
2497 \def\RangeCatcodeInvalid#1#2{%
2498 \count@=#1\relax
2499 \loop
2500 \catcode\count@=15 %
2501 \ifnum\count@<#2\relax
2502 \advance\count@ 1 %
2503 \repeat
2504 }
2505 \def\RangeCatcodeCheck#1#2#3{%
2506 \count@=#1\relax
2507 \loop
2508 \ifnum#3=\catcode\count@
2509 \else
2510 \errmessage{%
2511 Character \the\count@\space
2512 with wrong catcode \the\catcode\count@\space
2513 instead of \number#3%
2514 }%
2515 \fi
2516 \ifnum\count@<#2\relax
2517 \advance\count@ 1 %
2518 \repeat
2519 }
2520 \def\space{ }
2521 \expandafter\ifx\csname LoadCommand\endcsname\relax
2522 \def\LoadCommand{\input hologo.sty\relax}%
2523 \fi
2524 \def\Test{%

```

```

2525 \RangeCatcodeInvalid{0}{47}%
2526 \RangeCatcodeInvalid{58}{64}%
2527 \RangeCatcodeInvalid{91}{96}%
2528 \RangeCatcodeInvalid{123}{255}%
2529 \catcode`\@=12 %
2530 \catcode`\=0 %
2531 \catcode`\%=14 %
2532 \LoadCommand
2533 \RangeCatcodeCheck{0}{36}{15}%
2534 \RangeCatcodeCheck{37}{37}{14}%
2535 \RangeCatcodeCheck{38}{47}{15}%
2536 \RangeCatcodeCheck{48}{57}{12}%
2537 \RangeCatcodeCheck{58}{63}{15}%
2538 \RangeCatcodeCheck{64}{64}{12}%
2539 \RangeCatcodeCheck{65}{90}{11}%
2540 \RangeCatcodeCheck{91}{91}{15}%
2541 \RangeCatcodeCheck{92}{92}{0}%
2542 \RangeCatcodeCheck{93}{96}{15}%
2543 \RangeCatcodeCheck{97}{122}{11}%
2544 \RangeCatcodeCheck{123}{255}{15}%
2545 \RestoreCatcodes
2546 }
2547 \Test
2548 \csname @@end\endcsname
2549 \end
2550 </test1>

```

3.2 Spacefactor

The space factor must be 1000 after a logo. If it is greater 1000 then the following space is a space after a sentence closing point. If the space factor is smaller 1000 then an immediate following dot is interpreted as abbreviation, not sentence closing point.

```

2551 (*test-spacefactor)
2552 \NeedsTeXFormat{LaTeX2e}
2553 \documentclass{article}
2554 \usepackage{hologo}[2017/05/01]
2555 \usepackage{kvsetkeys}
2556 \usepackage{qstest}
2557 \IncludeTests{*}
2558 \LogTests{log}{*}{*}
2559 \begin{document}
2560 \begin{qstest}{spacefactor}{spacefactor}
2561 \newcommand*{\Test}[1]{%
2562   \sbox0{%
2563     \hologo{#1}%
2564     \Expect*{1000 (#1)}*{\the\spacefactor\space(#1)}%
2565   }%
2566 }%
2567 \makeatletter
2568 \def\TestList{}
2569 \def\hologoEntry#1#2#3{%
2570   \edef\TestList{%
2571     \ifx\TestList\@empty
2572     \else
2573       \TestList,%
2574     \fi
2575     #1%

```

```

2576 \ifx\#2\%
2577 \else
2578   ={variant=#2}%
2579 \fi
2580 }%
2581 }
2582 \hologoList
2583 \expandafter\kv@parse@normalized\expandafter{%
2584   \TestList
2585 }{%
2586   \begingroup
2587     \let\@logo=\kv@key
2588     \ifx\kv@value\relax
2589     \else
2590       \expandafter\hologoLogoSetup\expandafter\@logo\expandafter{%
2591         \kv@value
2592       }%
2593     \fi
2594     \Test\@logo
2595   \endgroup
2596   \@gobbletwo
2597 }
2598 \end{qstest}
2599 \end{document}
2600 \test-spacefactor

```

3.3 Complete list

```

2601 (*test-list)
2602 \NeedsTeXFormat{LaTeX2e}
2603 \documentclass[12pt,a4paper]{article}
2604 \usepackage{hologo}[2017/05/01]
2605 \usepackage[T1]{fontenc}
2606 \usepackage{lmodern}
2607 \usepackage{parskip}
2608 \usepackage[unicode]{hyperref}[2011/09/28]
2609 \usepackage{bookmark}[2011/09/19]
2610 \bookmarksetup{%
2611   numbered,%
2612   open,%
2613   openlevel=2,%
2614 }
2615 \renewcommand*{\contentsname}{List of logos}
2616 \begin{document}
2617 \tableofcontents
2618 \def\TestFont#1#2#3#4#5#6{%
2619   \begingroup
2620     \usefont{#3}{#4}{#5}{#6}%
2621     \HologoVariant{#1}{#2}/\hologoVariant{#1}{#2}%
2622     \quad
2623     \begingroup\scriptsize\hologoVariant{#1}{#2}\endgroup
2624     \quad
2625   \endgroup
2626   (#3/#4/#5/#6)%
2627   \par
2628 }
2629 \makeatletter
2630 \def\hologoEntry#1#2#3{%

```

```

2631 \section{%
2632   \HologoVariant{#1}{#2}/\hologoVariant{#1}{#2} %
2633   {[#1\ifx\#2\else\space(#2)\fi]}% hash-ok
2634 }% braces around [] because of bug in tex4ht
2635 \begingroup
2636   \hypersetup{unicode=false}%
2637   \bookmark[%
2638     dest=\@currentHref,%
2639     rellevel=1,%
2640     keeplevel,%
2641   ]{%
2642     \HologoVariant{#1}{#2}/\hologoVariant{#1}{#2} %
2643     (PDFDocEncoding)%
2644   }%
2645 \endgroup
2646 \TestFont{#1}{#2}{OT1}{cmr}{m}{n}%
2647 \TestFont{#1}{#2}{OT1}{cmss}{m}{n}%
2648 \TestFont{#1}{#2}{OT1}{cmr}{b}{n}%
2649 \TestFont{#1}{#2}{OT1}{cmr}{m}{it}%
2650 \TestFont{#1}{#2}{OT1}{cmtt}{m}{n}%
2651 \TestFont{#1}{#2}{T1}{lmr}{m}{n}%
2652 \TestFont{#1}{#2}{T1}{lmss}{m}{n}%
2653 \TestFont{#1}{#2}{T1}{lmr}{b}{n}%
2654 \TestFont{#1}{#2}{T1}{lmr}{m}{it}%
2655 \TestFont{#1}{#2}{T1}{lmtt}{m}{n}%
2656 \TestFont{#1}{#2}{T1}{lmvtt}{m}{n}%
2657 \TestFont{#1}{#2}{T1}{qtm}{m}{n}%
2658 \TestFont{#1}{#2}{T1}{qhv}{m}{n}%
2659 \TestFont{#1}{#2}{T1}{qtm}{b}{n}%
2660 \TestFont{#1}{#2}{T1}{qtm}{m}{it}%
2661 \TestFont{#1}{#2}{T1}{qcr}{m}{n}%
2662 \newpage
2663 }
2664 \makeatother
2665 \hologoList
2666 \end{document}
2667 </test-list>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/hologo.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/hologo.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for \TeX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

¹[CTAN:pkg/hologo](#)

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TEX`:

```
tex hologo.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>hologo.sty</code>	→ <code>tex/generic/oberdiek/hologo.sty</code>
<code>hologo.pdf</code>	→ <code>doc/latex/oberdiek/hologo.pdf</code>
<code>example/hologo-example.tex</code>	→ <code>doc/latex/oberdiek/example/hologo-example.tex</code>
<code>test/hologo-test1.tex</code>	→ <code>doc/latex/oberdiek/test/hologo-test1.tex</code>
<code>test/hologo-test-spacefactor.tex</code>	→ <code>doc/latex/oberdiek/test/hologo-test-spacefactor.tex</code>
<code>test/hologo-test-list.tex</code>	→ <code>doc/latex/oberdiek/test/hologo-test-list.tex</code>
<code>hologo.dtx</code>	→ <code>source/latex/oberdiek/hologo.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TEX` distribution (te`TEX`, mik`TEX`, ...) relies on file name databases, you must refresh these. For example, te`TEX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Unpacking with `LATEX`. The `.dtx` chooses its action depending on the format:

plain `TEX`: Run `docstrip` and extract the files.

`LATEX`: Generate the documentation.

If you insist on using `LATEX` for `docstrip` (really, `docstrip` does not need `LATEX`), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{hologo.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex_hologo.dtx
makeindex_s_gind.ist_hologo.idx
pdflatex_hologo.dtx
makeindex_s_gind.ist_hologo.idx
pdflatex_hologo.dtx
```

5 References

- [1] Oren Patashnik, *BIBT_EXing*, 1988-02-08.
[CTAN:pkg/base](#)
- [2] Gerd Neugebauer, DANTE, *Package dtklogos*, 2011-04-25.
<http://mirrors.ctan.org/usergrps/dante/dtk/dtk-logos.sty>
- [3] The $\mathcal{N}\mathcal{S}$ Team, *The ε -T_EX manual*, 1998-02.
[CTAN:pkg/doc](#)
- [4] The ε_X T_EX group, *ε_X T_EX: FAQ – How is ε_X T_EX typeset?*, 2007-04-14.
<http://www.extex.org/documentation/faq.html>
- [5] The L^AX Team, *L^AX – The Document Processor*, 2011-05-08.
<http://www.lyx.org/>
- [6] Andrew Trevorrow, OzT_EX FAQ: What is the correct way to typeset “OzT_EX”?, 2011-09-15 (visited).
<http://www.trevorrow.com/oztex/ozfaq.html#oztex-logo>
- [7] Michael Wichura, *The P_TCT_EX macro package*, 1987-09-21. [CTAN:pkg/pictex](#)
- [8] Markus Kohm, *KOMA-Script Datei scrlogo.dtx*, 2009-01-30.
[CTAN:install/macros/latex/contrib/koma-script.tds.zip](#)

6 History

[2010/04/08 v1.0]

- The first version.

[2010/04/16 v1.1]

- `\Hologo` added for support of logos at start of a sentence.
- `\hologoSetup` and `\hologoLogoSetup` added.
- Options `break`, `hyphenbreak`, `spacebreak` added.
- Variant support added by option `variant`.

[2010/04/24 v1.2]

- L^AT_EX3 added.
- V_TE_X added.

[2010/11/21 v1.3]

- ini_TE_X, vir_TE_X added.

[2011/03/25 v1.4]

- Con_TE_Xt with variants added.
- Option discretionarybreak added as refinement for option break.

[2011/04/21 v1.5]

- Wrong TDS directory for test files fixed.

[2011/10/01 v1.6]

- Support for package tex4ht added.
- Support for \csname added if \ifincsname is available.
- New logos: L^AT_EX, biber, Bib_TE_X (sc, sf), em_TE_X, ε_X_TE_X, KOMA-Script, L_X_X, MiK_TE_X, M_TS, OzMF, OzMP, Oz_TE_X, OzTtH, PCT_EX, P_IC, P_ICT_EX, METAFONT, MetaFun, METAPOST, MetaPost, SL_TE_X (lift, narrow, simple), SL_TE_X (narrow, simple, lift), te_TE_X.
- Fixes: ini_TE_X, pdfL^AT_EX, pdf_TE_X, vir_TE_X.
- \hologoFontSetup and \hologoLogoFontSetup added.
- \hologoVariant and \HologoVariant added.

[2011/11/22 v1.7]

- New logos: Bib_TE_X8, L^AT_EX_{ML}, Sage_TE_X, T_EX4ht, T_TH.
- X_Y and friends: Driver stuff fixed.
- X_Y and friends: Support for italic added.
- X_Y and friends: Package support for pgf and pstricks added.

[2011/11/29 v1.8]

- New logos: Hàn Thế Thành.

[2011/12/21 v1.9]

- Patch for package ifxetex added for the case that \newif is undefined in ini_TE_X.
- Some fixes for ini_TE_X.

[2012/04/26 v1.10]

- Fix in bookmark version of logo “Hàn Thế Thành”.

[2016/05/12 v1.11]

- Update HOLOGO@ifCharExists (previously in texlive)
- define pdfliteral in current luatex.

[2016/05/16 v1.12]

- Documentation updates.

[2017/05/01 v1.13]

- Removing spurious comments in bibliography. (github PR from yudai-nkt)

7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	Numbers
<code>\#</code>	2455
<code>\\$</code> 804, 1141, 1144, 1152, 1246, 1249, 1257	
<code>\%</code>	1078, 1121, 2531
<code>\&</code>	1142, 1145, 1153, 1247, 1250, 1258
<code>\'</code>	2166
<code>\-</code>	519
<code>\/</code>	2141, 2143, 2145
<code>\@</code>	2456, 2529
<code>\@PackageError</code>	
.	369, 402, 440, 452, 635,
658, 665, 817, 849, 1547, 1589, 2257	
<code>\@PackageInfoNoLine</code>	2243, 2301
<code>\@PackageWarning</code>	539
<code>\@PackageWarningNoLine</code>	
.	2209, 2336, 2351
<code>\@currentHref</code>	2638
<code>\@ehc</code>	371, 405, 444, 454, 637,
661, 668, 819, 851, 1547, 1589, 2260	
<code>\@empty</code>	2571
<code>\@firstofone</code>	2464, 2467
<code>\@gobble</code>	2461, 2469
<code>\@gobbletwo</code>	2596
<code>\@logo</code>	2587, 2590, 2594
<code>\@nil</code>	911
<code>\@undefined</code>	
.	180, 352, 449, 693, 2308, 2325
<code>\</code>	33, 48, 50, 51, 52,
53, 54, 61, 72, 79, 2530, 2576, 2633	
<code>\{</code>	2453
<code>\}</code>	2454
<code>\^</code>	1140, 1245, 1486, 2166, 2174
<code>\`</code>	2159, 2170, 2173, 2175, 2178, 2180
<code>\2</code>	2174
<code>\9</code>	2174
<code>_</code>	52, 53, 54
A	
<code>\advance</code>	935,
1528, 1541, 2216, 2494, 2502, 2517	
<code>\aftergroup</code>	151, 1450, 1452, 1455
B	
<code>\begin</code>	40, 41, 47, 107, 2559, 2560, 2616
<code>\bfseries</code>	47
<code>\body</code>	2473, 2477
<code>\bookmark</code>	69, 76, 2637
<code>\bookmarksetup</code>	2610
<code>\box</code>	1529, 1542, 2385, 2400
C	
<code>\catcode</code>	124, 125, 127, 128,
129, 130, 131, 132, 133, 134,	
135, 155, 156, 158, 159, 160,	
161, 162, 163, 164, 165, 166,	
167, 168, 169, 170, 171, 191,	
192, 194, 195, 196, 200, 201,	
202, 203, 204, 205, 206, 209,	
210, 212, 213, 214, 215, 219,	
221, 708, 710, 804, 1141, 1142,	
1144, 1145, 1152, 1153, 1246,	
1247, 1249, 1250, 1257, 1258,	
2453, 2454, 2455, 2456, 2491,	
2500, 2508, 2512, 2529, 2530, 2531	

\Hologo@ifCharExists	1444, 1479, 1487, 1493	\Hologo@LyX	2111
\Hologo@NegativeKerning ...	922, 931	\Hologo@Math	908
\Hologo@temp	2266, 2283	\Hologo@MathSetup	908,
\Hologo@AmS	1679	1135, 1165, 1238, 1266, 1862, 1881	
\Hologo@AmSLaTeX	1718, 1724	\Hologo@mbox	522,
\Hologo@AmSTeX	1711, 1717	1003, 1013, 1023, 1205, 1273,	
\Hologo@AtEnd ..	217, 218, 248, 249,	1283, 1404, 1412, 1654, 1664,	
662, 669, 2360, 2364, 2367, 2450		1674, 1813, 1815, 1819, 1822,	
\Hologo@biber	2046, 2055	1850, 1907, 1937, 1940, 1943,	
\Hologo@BibTeX	1799	1946, 2000, 2010, 2016, 2024,	
\Hologo@BibTeX8	1801	2026, 2031, 2033, 2037, 2039,	
\Hologo@BibTeX@sc	1725	2042, 2044, 2047, 2049, 2058, 2067	
\Hologo@BibTeX@sf	1762, 1799	\Hologo@METAFONT	2022
\Hologo@break	412, 433	\Hologo@MetaFun	2036
\Hologo@CheckDriver	2294, 2303	\Hologo@METAPOST	2029
\Hologo@CheckRead	2204	\Hologo@MetaPost	2041
\Hologo@choice	1503, 1510, 1513, 1516, 1519,	\Hologo@MiKTeX	1906, 1911
1521, 1555, 1558, 1561, 1564, 1566		\Hologo@name	363, 367, 368,
\Hologo@ConTeXt	1847	370, 385, 389, 394, 398, 413,	
\Hologo@ConTeXt@narrow ...	1818, 1847	419, 420, 422, 423, 425, 427,	
\Hologo@ConTeXt@simple ...	1812, 1817	439, 449, 451, 453, 457, 471,	
\Hologo@DeclareBoolOption	380, 434, 435, 436, 437	472, 476, 480, 488, 489, 493,	
\Hologo@discretionary	505, 1299, 1338,	497, 506, 507, 511, 515, 523,	
1355, 1733, 1770, 1814, 1820,		527, 629, 633, 634, 636, 648,	
1851, 1871, 1908, 1980, 2001,		651, 815, 816, 818, 820, 823,	
2017, 2025, 2032, 2038, 2043, 2048		824, 828, 829, 831, 847, 848,	
\Hologo@DriverFallback	2285, 2287, 2298	850, 852, 855, 856, 860, 861, 863	
\Hologo@DriverSetup	2290, 2292, 2374	\Hologo@NegativeKerning	917, 1241, 1406, 2018
\Hologo@emTeX	1849, 1858	\Hologo@NTS	2139
\Hologo@eTeX	1236	\Hologo@OzMF	1936
\Hologo@ExTeX	1859	\Hologo@OzMP	1939
\Hologo@false	393, 432	\Hologo@OzTeX	1912
\Hologo@FontSetup	630, 640, 643	\Hologo@OzTtH	1942
\Hologo@HanTheThanh	2158	\Hologo@PCTeX	1945, 1949
\Hologo@hyphen	487, 1013, 1713, 1720, 2065	\Hologo@PdfdocUnicode	901, 1157, 1260, 1890, 2174
\Hologo@ifCharExists	1418, 1500, 2163	\Hologo@pdfLaTeX	1663, 1672
\Hologo@ifDefined	351	\Hologo@pdfliteral	2306, 2310, 2325, 2329, 2406, 2410
\Hologo@ifExists	351, 657,	\Hologo@pdfTeX	1653, 1662
664, 720, 741, 765, 790, 910, 2182		\Hologo@PiC	1950
\Hologo@ifincsname	693, 701	\Hologo@PiCTeX	1978
\Hologo@iniTeX	1272, 1281	\Hologo@plainTeX	1032
\Hologo@InputIfExists	2186, 2206, 2227	\Hologo@plainTeX@hyphen	1012
\Hologo@KOMAScript	2056	\Hologo@plainTeX@runtogether ..	1022
\Hologo@La	1036	\Hologo@plainTeX@space ...	1002, 1032
\Hologo@LaTeX	1056	\Hologo@PointReflectBox	1544, 1545, 2388
\Hologo@LaTeX2e	1185	\Hologo@ReflectBox	1586, 2375
\Hologo@LaTeX3	1193	\Hologo@Reflectbox	1584
\Hologo@LaTeXe	1131, 1186	\Hologo@SageTeX	2015, 2021
\Hologo@LaTeXML	1204	\Hologo@ScaleBox@dviPDFm	2432
\Hologo@LaTeXTeX	1083, 1094	\Hologo@ScaleBox@dviPS ...	2415, 2433
\Hologo@LuaLaTeX	1411, 1417	\Hologo@ScaleBox@pdftex	2404
\Hologo@LuaTeX	1403, 1410	\Hologo@ScaleBox@vtex	2443
		\Hologo@ScaleBox@xetex	2435
		\Hologo@SetBreakAll ...	391, 400, 410

<code>\Hologo@Setup</code>	364, 374, 377	<code>\HologoBkm@emTeX</code>	1855
<code>\Hologo@SLiTeX</code>	1397	<code>\HologoBkm@eTeX</code>	1259
<code>\Hologo@SliTeX</code>	1400	<code>\HologoBkm@ExTeX</code>	1889
<code>\Hologo@SLiTeX@lift</code>	1292, 1394, 1397	<code>\HologoBkm@HanTheThanh</code>	2172
<code>\Hologo@SLiTeX@lift</code>	1394	<code>\HologoBkm@iniTeX</code>	1278
<code>\Hologo@SLiTeX@narrow</code>	1391	<code>\HologoBkm@KOMAScript</code>	2070
<code>\Hologo@SLiTeX@narrow</code>	1344, 1391, 1400	<code>\HologoBkm@LaTeX2e</code>	1189
<code>\Hologo@SLiTeX@simple</code>	1388	<code>\HologoBkm@LaTeX3</code>	1197
<code>\Hologo@SLiTeX@simple</code>	1333, 1343, 1388	<code>\HologoBkm@LaTeXe</code>	1154, 1190
<code>\Hologo@space</code>	470, 1003, 2160, 2169	<code>\HologoBkm@LaTeXTeX</code>	1092, 1096
<code>\Hologo@SpaceFactor</code>		<code>\HologoBkm@pdfLaTeX</code>	1669
	937, 974, 1956, 2117, 2147, 2153	<code>\HologoBkm@pdfTeX</code>	1659
<code>\Hologo@Span</code>	940, 978, 980,	<code>\HologoBkm@plainTeX</code>	1034
	1063, 1065, 1099, 1101, 1102,	<code>\HologoBkm@plainTeX@hyphen</code>	1016
	1103, 1161, 1163, 1164, 1216,	<code>\HologoBkm@plainTeX@runtogether</code>	1026
	1219, 1221, 1225, 1227, 1307,	<code>\HologoBkm@plainTeX@space</code>	1006, 1034
	1310, 1311, 1363, 1366, 1367,	<code>\HologoBkm@SLiTeX</code>	1398
	1596, 1598, 1620, 1640, 1692,	<code>\HologoBkm@SliTeX</code>	1401
	1694, 1739, 1741, 1742, 1776,	<code>\HologoBkm@SLiTeX@lift</code>	
	1779, 1826, 1827, 1879, 1883,		1304, 1395, 1398
	1921, 1923, 1960, 1962, 1986,	<code>\HologoBkm@SLiTeX@lift</code>	1395
	2076, 2078, 2080, 2081, 2121, 2123	<code>\HologoBkm@SLiTeX@narrow</code>	1392
<code>\Hologo@SubScript</code>	945, 2151	<code>\HologoBkm@SLiTeX@narrow</code>	
<code>\Hologo@temp</code>	383, 384, 393, 411, 412,		1360, 1392, 1401
	446, 447, 451, 453, 458, 473,	<code>\HologoBkm@SLiTeX@simple</code>	1389
	475, 479, 482, 490, 492, 496,	<code>\HologoBkm@SLiTeX@simple</code>	1342, 1389
	499, 508, 510, 514, 517, 524,	<code>\HologoBkm@teTeX</code>	2005
	526, 529, 646, 655, 656, 703,	<code>\HologoBkm@virTeX</code>	1288
	2187, 2188, 2189, 2191, 2203,	<code>\HologoCs@biber</code>	2051
	2205, 2208, 2215, 2218, 2226,	<code>\HologoCs@emTeX</code>	1854
	2230, 2231, 2233, 2250, 2253,	<code>\HologoCs@eTeX</code>	1245
	2254, 2255, 2258, 2268, 2270,	<code>\HologoCs@iniTeX</code>	1277
	2316, 2328, 2331, 2369, 2370,	<code>\HologoCs@LaTeX2e</code>	1187
	2403, 2404, 2415, 2432, 2435, 2443	<code>\HologoCs@LaTeXe</code>	1140, 1188
<code>\Hologo@TempDimen</code>		<code>\HologoCs@pdfLaTeX</code>	1668
	916, 919, 921, 926, 927, 933, 935	<code>\HologoCs@pdfTeX</code>	1658
<code>\Hologo@teTeX</code>	1999, 2008	<code>\HologoCs@plainTeX</code>	1033
<code>\Hologo@TeX</code>	973	<code>\HologoCs@plainTeX@hyphen</code>	1015
<code>\Hologo@TeX4ht</code>	2009	<code>\HologoCs@plainTeX@runtogether</code>	1025
<code>\Hologo@true</code>	384, 431	<code>\HologoCs@plainTeX@space</code>	1005, 1033
<code>\Hologo@TTH</code>	2149	<code>\HologoCs@teTeX</code>	2004
<code>\Hologo@Uppercase</code>	861, 900	<code>\HologoCs@virTeX</code>	1287
<code>\Hologo@Variant</code>	463, 714, 717, 724,	<code>\HologoCss@AmS</code>	1690, 1699
	727, 735, 738, 745, 748, 816,	<code>\HologoCss@BibTeX@sc</code>	1738, 1746
	824, 828, 831, 848, 856, 860, 863	<code>\HologoCss@BibTeX@sf</code>	1775, 1785
<code>\Hologo@virTeX</code>	1282, 1291	<code>\HologoCss@ConTeXt@narrow</code>	1825, 1833
<code>\Hologo@VTeX</code>	1673, 1678	<code>\HologoCss@ExTeX</code>	1877, 1893
<code>\Hologo@WarningUnsupportedDriver</code>		<code>\HologoCss@KOMAScript</code>	2074, 2086
	1522, 1567, 2350	<code>\HologoCss@LaTeX</code>	1062, 1071, 1217
<code>\Hologo@Xe</code>	1497	<code>\HologoCss@LaTeXe</code>	1160, 1170
<code>\Hologo@XeLaTeX</code>	1633	<code>\HologoCss@LaTeXTeX</code>	1098, 1109
<code>\Hologo@XeTeX</code>	1613	<code>\HologoCss@LyX</code>	2120, 2127
<code>\HologoBkm@(La)TeX</code>	1095	<code>\HologoCss@OzTeX</code>	1920, 1927
<code>\HologoBkm@AmS</code>	1688	<code>\HologoCss@PiC</code>	1959, 1966
<code>\HologoBkm@AmSLaTeX</code>	1723	<code>\HologoCss@PiCTeX</code>	1985, 1991
<code>\HologoBkm@AmSTeX</code>	1716	<code>\HologoCss@SLiTeX@lift</code>	1306, 1316
<code>\HologoBkm@biber</code>	2052	<code>\HologoCss@SliTeX@narrow</code>	1362, 1372
<code>\HologoBkm@BibTeX8</code>	1805	<code>\HologoCss@TeX</code>	977, 986, 1218

<code>\HoLogoCss@Xe</code>	1595, 1603	<code>\HoLogoHtml@LaTeXML</code>	1215
<code>\HoLogoCss@XeLaTeX</code>	1639, 1645	<code>\HoLogoHtml@LaTeXTeX</code>	1097, 1108
<code>\HoLogoCss@XeTeX</code>	1619, 1625	<code>\HoLogoHtml@LuaLaTeX</code>	1417
<code>\hologoDriver</code>		<code>\HoLogoHtml@LuaTeX</code>	1410
. 1508, 1553, 2263, 2289, 2301,		<code>\HoLogoHtml@LyX</code>	2119
2305, 2342, 2345, 2353, 2380, 2394		<code>\HoLogoHtml@MiKTeX</code>	1911
<code>\hologoDriverSetup</code>	5, 2288	<code>\HoLogoHtml@OzTeX</code>	1919
<code>\hologoEntry</code>		<code>\HoLogoHtml@PCTeX</code>	1949
32, 66, 255, 256, 257, 258, 259,		<code>\HoLogoHtml@pdfLaTeX</code>	1215, 1672
260, 261, 262, 263, 264, 265,		<code>\HoLogoHtml@pdfTeX</code>	1662
266, 267, 268, 269, 270, 271,		<code>\HoLogoHtml@PiC</code>	1958
272, 273, 274, 275, 276, 277,		<code>\HoLogoHtml@PiCTeX</code>	1984
278, 279, 280, 281, 282, 283,		<code>\HoLogoHtml@plainTeX</code>	1035
284, 285, 286, 287, 288, 289,		<code>\HoLogoHtml@plainTeX@hyphen</code> ..	1019
290, 291, 292, 293, 294, 295,		<code>\HoLogoHtml@plainTeX@runtogether</code>	
296, 297, 298, 299, 300, 301,		1029
302, 303, 304, 305, 306, 307,		<code>\HoLogoHtml@plainTeX@space</code>	1009, 1035
308, 309, 310, 311, 312, 313,		<code>\HoLogoHtml@SageTeX</code>	2021
314, 315, 316, 317, 318, 2569, 2630		<code>\HoLogoHtml@SLiTeX</code>	1399
<code>\HoLogoFont@Def</code>	551, 557,	<code>\HoLogoHtml@SLiTeX</code>	1402
561, 564, 569, 572, 578, 580,		<code>\HoLogoHtml@SLiTeX@lift</code>	
592, 594, 599, 602, 620, 626, 649		1305, 1396, 1399
<code>\HoLogoFont@font</code> 535, 823, 855, 1212,		<code>\HoLogoHtml@SLiTeX@lift</code>	1396
1293, 1298, 1308, 1334, 1336,		<code>\HoLogoHtml@SLiTeX@narrow</code>	1393
1345, 1349, 1364, 1680, 1691,		<code>\HoLogoHtml@SLiTeX@narrow</code>	
1728, 1765, 1778, 1860, 1867,		1361, 1393, 1402
1878, 2023, 2030, 2057, 2075, 2140		<code>\HoLogoHtml@SLiTeX@simple</code>	1390
<code>\HoLogoFont@font@bibs</code>	574	<code>\HoLogoHtml@SLiTeX@simple</code> 1343, 1390	
<code>\HoLogoFont@font@general</code>	557	<code>\HoLogoHtml@tTeX</code>	2008
<code>\HoLogoFont@font@logo</code>	606	<code>\HoLogoHtml@TeX</code>	976
<code>\HoLogoFont@font@rm</code>	558	<code>\HoLogoHtml@TeX4ht</code>	2012
<code>\HoLogoFont@font@sc</code>	588	<code>\HoLogoHtml@TTH</code>	2155
<code>\HoLogoFont@font@sf</code>	566	<code>\HoLogoHtml@virTeX</code>	1291
<code>\HoLogoFont@font@sy</code>	596	<code>\HoLogoHtml@VTeX</code>	1678
<code>\HoLogoFont@LogoDef</code>	554, 651	<code>\HoLogoHtml@Xe</code>	1594
<code>\hologoFontSetup</code>	6, 628	<code>\HoLogoHtml@XeLaTeX</code>	1638
<code>\HoLogoHtml@LaTeX</code>	1107	<code>\HoLogoHtml@XeTeX</code>	1618
<code>\HoLogoHtml@AmS</code>	1689	<code>\hologoList</code> 7, 35, 115, 254, 2582, 2665	
<code>\HoLogoHtml@AmSLaTeX</code>	1724	<code>\hologoLogoFontSetup</code>	6, 632
<code>\HoLogoHtml@AmSTeX</code>	1717	<code>\hologoLogoSetup</code>	
<code>\HoLogoHtml@biber</code>	2055	... 4, 63, 366, 443, 880, 895, 2590	
<code>\HoLogoHtml@BibTeX</code>	1800	<code>\HOLGOOPT@break</code>	414, 415, 416
<code>\HoLogoHtml@BibTeX8</code>	1809	<code>\HOLGOOPT@discretionarybreak</code> ...	
<code>\HoLogoHtml@BibTeX@sc</code>	1737	416, 508
<code>\HoLogoHtml@BibTeX@sf</code>	1774, 1800	<code>\HOLGOOPT@hyphenbreak</code> .	414, 490, 524
<code>\HoLogoHtml@ConTeXt</code>	1848	<code>\HOLGOOPT@spacebreak</code>	415, 473
<code>\HoLogoHtml@ConTeXt@narrow</code> 1824, 1848		<code>\HologoRobust</code>	743, 837, 896
<code>\HoLogoHtml@ConTeXt@simple</code> ...	1817	<code>\hologoRobust</code>	
<code>\HoLogoHtml@emTeX</code>	1858 664, 666, 722, 805, 881, 899	
<code>\HoLogoHtml@eTeX</code>	1264	<code>\hologorobust</code>	899
<code>\HoLogoHtml@ExTeX</code>	1876	<code>\hologoSetup</code>	4, 362, 441
<code>\HoLogoHtml@HanTheThanh</code>	2177	<code>\HologoVariant</code> ..	779, 2621, 2632, 2642
<code>\HoLogoHtml@iniTeX</code>	1281	<code>\hologoVariant</code>	
<code>\HoLogoHtml@KOMAScript</code>	2073	... 7, 754, 2621, 2623, 2632, 2642	
<code>\HoLogoHtml@LaTeX</code>	1061	<code>\HologoVariantRobust</code>	792, 884
<code>\HoLogoHtml@LaTeX2e</code>	1191	<code>\hologoVariantRobust</code>	767, 869
<code>\HoLogoHtml@LaTeX3</code>	1201	<code>\hss</code>	2166, 2381, 2395
<code>\HoLogoHtml@LaTeXe</code>	1159, 1192	<code>\ht</code>	1041, 2393

<code>\hypersetup</code>	20, 75, 2636	<code>\ltx@car</code>	911
<code>\hypertarget</code>	68	<code>\ltx@ccclv</code>	2215, 2216, 2218
I			
<code>\if</code>	911, 1455	<code>\ltx@empty</code>	447, 2231, 2255
<code>\ifcase</code>	482, 499, 517, 529, 685, 1521, 1566, 2208, 2317	<code>\ltx@firstofone</code>	672, 681, 695
<code>\ifdim</code>	921, 926, 1504	<code>\ltx@firstofthree</code>	1468
<code>\ifeof</code>	2188, 2205	<code>\ltx@firstoftwo</code>	358, 717, 720, 728, 741, 762, 765, 773, 790, 825, 832, 905, 1438, 1457, 1474
<code>\ifHy@unicode</code>	902	<code>\ltx@fourthoffour</code>	1491
<code>\ifincsname</code> ...	701, 713, 734, 758, 783	<code>\ltx@gobble</code>	
<code>\ifluatex</code>	671, 1418, 2307		372, 638, 674, 679, 698, 924, 1470
<code>\ifnum</code> .	678, 1140, 1245, 1419, 1422, 1449, 1467, 1473, 1486, 1490, 2233, 2313, 2493, 2501, 2508, 2516	<code>\ltx@hashchar</code>	1599, 2179
<code>\ifpdf</code>	2304	<code>\ltx@ifUndefined</code>	
<code>\iftrue</code>	902		335, 368, 451, 537, 538, 558, 559, 566, 567, 574, 575, 588, 589, 596, 597, 610, 618, 623, 634, 677, 707, 805, 806, 816, 822, 828, 837, 838, 848, 854, 860, 869, 870, 884, 885, 946, 947, 952, 1443, 1464, 1465, 1505, 1506, 1507, 1508, 1550, 1551, 1552, 1553, 2185, 2202, 2312, 2335, 2358, 2359, 2363, 2366
<code>\ifvtx</code>	2344	<code>\ltx@ifundefined</code>	465, 471, 472, 488, 489, 506, 507, 523, 714, 724, 725, 735, 745, 746, 759, 769, 770, 784, 794, 795, 1043, 1485, 2295
<code>\ifx</code>	33, 61, 72, 79, 137, 140, 143, 172, 180, 183, 321, 324, 352, 355, 384, 385, 393, 394, 412, 413, 439, 447, 609, 648, 693, 755, 780, 902, 2195, 2231, 2237, 2255, 2267, 2308, 2325, 2370, 2457, 2460, 2463, 2466, 2521, 2571, 2576, 2588, 2633	<code>\ltx@LocDimenA</code>	
<code>\ifxetex</code>	1463, 2341		1527, 1528, 1529, 1540, 1541, 1542
<code>\immediate</code>	145, 174	<code>\ltx@mbox</code>	500, 530, 948, 964, 1237, 1265, 1335, 1346, 1861, 1880, 2150, 2159, 2161, 2170
<code>\IncludeTests</code>	2557	<code>\ltx@minusone</code>	2216
<code>\input</code>	325, 2196, 2198, 2238, 2240, 2522	<code>\ltx@newif</code>	336
<code>\InputIfFileExists</code>	2182, 2183	<code>\ltx@one</code>	386, 389, 1504
<code>\iterate</code>	2474, 2476, 2478	<code>\ltx@onelevel@sanitize</code>	2254
K			
<code>\kern</code>	927, 934, 974, 1038, 1058, 1085, 1087, 1089, 1133, 1207, 1209, 1211, 1295, 1297, 1300, 1348, 1351, 1356, 1448, 1499, 1615, 1635, 1682, 1684, 1727, 1730, 1734, 1764, 1767, 1771, 1819, 1821, 1822, 1866, 1872, 1914, 1916, 1952, 1954, 1981, 2059, 2060, 2061, 2064, 2066, 2113, 2115, 2142, 2144, 2379, 2392	<code>\ltx@secondoftwo</code>	
<code>\kv@define@key</code>	382, 438, 647, 2251, 2284		353, 356, 738, 749, 787, 798, 857, 864, 903, 1436, 1460, 1476
<code>\kv@key</code>	2587	<code>\ltx@space</code>	485, 659, 666
<code>\kv@parse@normalized</code>	2273, 2583	<code>\ltx@two</code>	
<code>\kv@value</code>	2267, 2588, 2591		2378, 2384, 2385, 2391, 2399, 2400
<code>\kvsetkeys</code>	378, 644, 2293, 2298	<code>\ltx@undefined</code>	2289
L			
<code>\lastkern</code>	1449	<code>\ltx@zero</code> ..	381, 395, 398, 916, 932, 933, 934, 935, 1040, 1041, 1435, 1446, 1447, 1449, 1467, 1473, 1503, 1526, 1527, 1529, 1539, 1540, 1542, 2377, 2379, 2381, 2384, 2390, 2392, 2393, 2395, 2399
<code>\LoadCommand</code>	2522, 2532	<code>\luatexversion</code>	678, 1419, 2313
<code>\logofamily</code>	611, 612, 620	M	
<code>\LogTests</code>	2558	<code>\makeatletter</code>	2567, 2629
<code>\loop</code>	2472, 2488, 2499, 2507	<code>\makeatother</code>	2664
<code>\lower</code>	974, 1210, 1501, 1532, 1545, 1570, 1574, 1581, 1585, 1683, 1953, 2114, 2143	<code>\math@fontsfalse</code>	584, 1048
		<code>\mathrm</code>	953
		<code>\mathsurround</code>	581, 909, 949, 965
		<code>\mbox</code>	955

`\MessageBreak` 403, 442,
659, 666, 2210, 2352, 2353, 2354

N

`\NeedsTeXFormat` 3, 2552, 2602
`\newcommand` 32, 60, 66, 2561
`\newpage` 2662
`\next` 2478, 2480, 2482
`\not@math@alphabet` 612
`\number` 1426, 1431, 2513

O

`\openin` 2187

P

`\PackageInfo` 148
`\pagestyle` 9
`\par` 2627
`\pdf@filesize` 2230
`\pdfextension` 2308, 2309
`\pdfliteral` ... 2306, 2309, 2310, 2337
`\penalty` 483
`\pgfpicture` 1533, 1575
`\pgftext` 1531, 1534, 1573, 1577
`\pgftransformxscale` 1576
`\ProcessKeyvalOptions` 2372
`\protected` ... 812, 844, 876, 891, 2309
`\ProvidesPackage` 141, 189
`\psscalebox` ... 1537, 1539, 1580, 1582

Q

`\quad` 2622, 2624

R

`\raise` 1298, 1529, 1542, 2166, 2393
`\raisebox` 68
`\RangeCatcodeCheck` ... 2505, 2533,
2534, 2535, 2536, 2537, 2538,
2539, 2540, 2541, 2542, 2543, 2544
`\RangeCatcodeInvalid`
.... 2497, 2525, 2526, 2527, 2528
`\reflectbox` 1571
`\renewcommand` 2615
`\repeat` ... 2472, 2484, 2495, 2503, 2518
`\RequirePackage` 341, 342, 343,
344, 345, 346, 347, 348, 349, 2371
`\RestoreCatcodes` 2486, 2489, 2490, 2545
`\rm` 561
`\rmfamily` 564
`\rotatebox` 1524, 1526

S

`\sbox` 2562
`\scriptsize` 2623
`\scshape` 594
`\section` 43, 2631
`\selectfont`
.. 92, 96, 103, 585, 615, 956, 1048

`\setbox` 932, 934, 1040, 1447,
1526, 1539, 2377, 2378, 2390, 2391
`\setlength` 13
`\SetVariant` . 60, 67, 88, 91, 95, 99, 102
`\sf` 569
`\sf@size` 583, 956, 1047
`\sffamily` 572
`\space` 72, 79,
443, 2511, 2512, 2520, 2564, 2633
`\spacefactor` 938, 2564
`\special` 2417,
2425, 2437, 2438, 2440, 2445, 2447

T

`\tableofcontents` 2617
`\tabularnewline` 105, 112
`\tenlogo` 624, 626
`\tensc` 576, 578, 590, 592
`\tensy` 599
`\Test` 2524, 2547, 2561, 2594
`\TestFont` 2618,
2646, 2647, 2648, 2649, 2650,
2651, 2652, 2653, 2654, 2655,
2656, 2657, 2658, 2659, 2660, 2661
`\TestList` . 2568, 2570, 2571, 2573, 2584
`\TeX` 52, 53, 54
`\texorpdfstring` ... 720, 741, 765, 790
`\text` 966
`\textbf` 48, 108, 110, 111
`\textchi` 1890
`\textepsilon` 1157, 1260, 1890
`\textit` 108
`\textsf` 100
`\textstyle` 1137, 1166, 1864, 1882, 1883
`\textsubscript` 970
`\texttt` 82, 84, 109
`\the` 199, 200, 201,
202, 203, 204, 205, 206, 219,
250, 2218, 2491, 2511, 2512, 2564
`\TMP@EnsureCode` 216,
223, 224, 225, 226, 227, 228,
229, 230, 231, 232, 233, 234,
235, 236, 237, 238, 239, 240,
241, 242, 243, 244, 245, 246, 247
`\TMP@RequirePackage` 322, 328, 329,
330, 331, 332, 333, 334, 338, 339
`\tracinglostchars` 1446
`\typeout` 30, 31, 33, 36, 37

U

`\uppercase` 900
`\usefont` 603, 2620
`\usepackage` 5, 10, 11, 12, 14,
15, 16, 17, 25, 2554, 2555, 2556,
2604, 2605, 2606, 2607, 2608, 2609

V

`\varepsilon`
1137, 1166, 1239, 1267, 1865, 1882

<code>\vbox</code>	1041		X
<code>\vss</code>	1052	<code>\x</code>	136, 137, 140, 144, 148, 150, 173, 178, 188, 197, 209, 607, 609, 2193, 2195, 2217, 2221, 2235, 2237, 2297, 2299
			W
<code>\wd</code> ...	933, 935, 2379, 2384, 2392, 2399	<code>\XeTeXcharglyph</code>	1473
<code>\write</code>	145, 174	<code>\XeTeXfonttype</code>	1467