

# The L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> Sources

Johannes Braams  
David Carlisle  
Alan Jeffrey  
Leslie Lamport  
Frank Mittelbach  
Chris Rowley  
Rainer Schöpf

2020-02-01 Patch level -2

This file is maintained by the L<sup>A</sup>T<sub>E</sub>X Project team.  
Bug reports can be opened (category `latex`) at  
<https://latex-project.org/bugs.html>.

## Contents

<b>a</b>	<b>ltdirchk.dtx</b>	<b>1</b>
<b>1</b>	<b>L<sup>A</sup>T<sub>E</sub>X System Dependent Initialisations</b>	<b>1</b>
<b>2</b>	<b>Initialisation</b>	<b>2</b>
2.1	INITEX . . . . .	2
2.2	Some bits of 2e . . . . .	4
<b>3</b>	<b>texsys.cfg</b>	<b>5</b>
3.1	texsys.cfg . . . . .	5
3.2	UNIX (web2c) . . . . .	7
3.3	UNIX (other) . . . . .	7
3.4	MSDOS (emtex) . . . . .	7
3.5	MSDOS (other) . . . . .	7
3.6	VMS (DECUS T <sub>E</sub> X, PD VMS 3.6) . . . . .	7
3.7	VMS (???) . . . . .	8
3.8	MACINTOSH (OzT <sub>E</sub> X 1.6) . . . . .	8
3.9	MACINTOSH (other) . . . . .	8
3.10	FAKE EXAMPLE . . . . .	8
<b>4</b>	<b>Setting \@currdir</b>	<b>9</b>
<b>5</b>	<b>Setting \input@path</b>	<b>10</b>

<b>6</b>	<b>Filename Parsing</b>	<b>11</b>
<b>7</b>	<b>T<sub>E</sub>X Versions</b>	<b>13</b>
<b>8</b>	<b>ltxcheck.tex</b>	<b>13</b>
<b>b</b>	<b>ltpain.dtx</b>	<b>15</b>
<b>9</b>	<b>Plain T<sub>E</sub>X</b>	<b>15</b>
<b>c</b>	<b>ltvers.dtx</b>	<b>33</b>
<b>10</b>	<b>Version Identification</b>	<b>33</b>
<b>d</b>	<b>ltdefns.dtx</b>	<b>36</b>
<b>11</b>	<b>Definitions</b>	<b>36</b>
11.1	Initex initialisations . . . . .	36
11.2	Saved versions of T <sub>E</sub> X primitives . . . . .	36
11.3	Command definitions . . . . .	37
11.4	Robust commands and protect . . . . .	44
11.5	Internal defining commands . . . . .	48
<b>12</b>	<b>Discretionary Hyphenation</b>	<b>51</b>
<b>e</b>	<b>ltdllc.dtx</b>	<b>54</b>
<b>13</b>	<b>Counters</b>	<b>54</b>
<b>f</b>	<b>ltdntrl.dtx</b>	<b>56</b>
<b>14</b>	<b>Program control structure</b>	<b>56</b>
<b>g</b>	<b>ltderror.dtx</b>	<b>60</b>
<b>15</b>	<b>Error handling and tracing</b>	<b>60</b>
15.1	General commands . . . . .	60
15.2	Specific errors . . . . .	65
15.3	Tracing . . . . .	68
<b>h</b>	<b>ltdpar.dtx</b>	<b>69</b>
<b>16</b>	<b>Paragraphs</b>	<b>69</b>
16.1	Implementation . . . . .	69

<b>i</b>	<b>ltspace.dtx</b>	<b>71</b>
<b>17</b>	<b>Spacing</b>	<b>71</b>
17.1	User Commands . . . . .	71
17.2	Chris' comments . . . . .	71
17.3	Some immediate actions . . . . .	73
17.4	The code . . . . .	74
17.5	Vertical spacing . . . . .	80
17.6	Horizontal space (and breaks) . . . . .	84
<b>j</b>	<b>ltlogos.dtx</b>	<b>87</b>
<b>18</b>	<b>Logos</b>	<b>87</b>
<b>k</b>	<b>ltfiles.dtx</b>	<b>88</b>
<b>19</b>	<b>File Handling</b>	<b>88</b>
19.1	Safe Input Macros . . . . .	96
19.2	Listing files . . . . .	100
<b>l</b>	<b>ltoutenc.dtx</b>	<b>102</b>
<b>20</b>	<b>Font encodings</b>	<b>102</b>
20.1	Removing encoding-specific commands . . . . .	104
20.2	The order of declarations . . . . .	105
20.3	Docstrip modules . . . . .	105
20.4	Definitions for the kernel . . . . .	106
20.4.1	Declaration commands . . . . .	106
20.4.2	Hyphenation . . . . .	113
20.4.3	Miscellania . . . . .	113
20.4.4	Default encodings . . . . .	114
20.4.5	Math material . . . . .	116
20.5	Definitions for the OT1 encoding . . . . .	117
20.6	Definitions for the T1 encoding . . . . .	120
20.7	Definitions for the OMS encoding . . . . .	125
20.8	Definitions for the OML encoding . . . . .	126
20.9	Definitions for the OT4 encoding . . . . .	126
20.10	Definitions for the TS1 encoding . . . . .	128
20.11	Definitions for the TU encoding . . . . .	132
<b>21</b>	<b>Package files</b>	<b>142</b>
21.1	The fontenc package . . . . .	142
21.2	The textcomp package . . . . .	144
21.2.1	Supporting oldstyle digits . . . . .	152
21.2.2	Subset encoding defaults . . . . .	153
<b>m</b>	<b>ltcounts.dtx</b>	<b>155</b>

<b>22 Counters and Lengths</b>	<b>155</b>
22.1 Environment Counter Macros . . . . .	155
<b>n ltlength.dtx</b>	<b>162</b>
<b>23 Lengths</b>	<b>162</b>
<b>o ltfssbas.dtx</b>	<b>163</b>
<b>24 Preliminary macros</b>	<b>163</b>
<b>25 Macros for setting up the tables</b>	<b>164</b>
<b>26 Selecting a new font</b>	<b>169</b>
26.1 Macros for the user . . . . .	169
26.2 Macros for loading fonts . . . . .	173
<b>27 Assigning math fonts to <i>versions</i></b>	<b>179</b>
<b>p ltfssstrc.dtx</b>	<b>185</b>
<b>28 Introduction</b>	<b>185</b>
<b>29 A driver for this document</b>	<b>185</b>
<b>30 The Implementation</b>	<b>186</b>
<b>31 Handling Options</b>	<b>186</b>
<b>32 Macros common to fam.tex and tracefnt.sty</b>	<b>188</b>
32.1 General font loading . . . . .	188
32.2 Math fonts setup . . . . .	192
32.2.1 Outline of algorithm for math font sizes . . . . .	192
32.2.2 Code for math font size setting . . . . .	194
32.2.3 Other code for math . . . . .	195
<b>33 Scaled font extraction</b>	<b>197</b>
33.1 Sizefunctions . . . . .	204
<b>q ltfsscnp.dtx</b>	<b>207</b>
<b>r ltfssdcl.dtx</b>	<b>211</b>
<b>34 Interface Commands</b>	<b>211</b>
<b>s ltfssini.dtx</b>	<b>237</b>

<b>35 NFSS Initialisation</b>	<b>237</b>
35.1 Providing math <i>versions</i>	237
35.2 Miscellaneous	239
 <b>t fontdef.dtx</b>	 <b>243</b>
<b>36 Introduction</b>	<b>243</b>
<b>37 Customization</b>	<b>243</b>
<b>38 The docstrip modules</b>	<b>244</b>
<b>39 A driver for this document</b>	<b>244</b>
<b>40 The fonttext.ltx file</b>	<b>245</b>
40.1 Encodings	245
40.2 Defaults	247
<b>41 The fontmath.ltx file</b>	<b>248</b>
41.1 The font encodings used	248
41.1.1 Symbolfont and Alphabet declarations	249
41.2 Math font sizes	249
41.3 The math symbol assignments	250
41.3.1 The letters	250
41.3.2 The digits	251
41.3.3 Punctuation, brace, etc. keys	251
41.3.4 Delimitercodes for characters	252
41.4 Symbols accessed via control sequences	252
41.4.1 Greek letters	252
41.4.2 Ordinary symbols	253
41.4.3 Large Operators	254
41.4.4 Binary symbols	254
41.4.5 Relations	255
41.4.6 Arrows	256
41.4.7 Punctuation symbols	257
41.4.8 Math accents	257
41.4.9 Radicals	258
41.4.10 Over and under something, etc	258
41.4.11 Delimiters	259
41.5 Math versions of text commands	260
41.6 Other special functions and parameters	260
41.6.1 Biggggg	260
41.6.2 The log-like functions	261
41.6.3 Parameters	261
 <b>42 Default cfg files</b>	 <b>261</b>
 <b>u preload.dtx</b>	 <b>262</b>

<b>43 Overview</b>	<b>262</b>
<b>44 Customization</b>	<b>262</b>
<b>45 Module switches for the DOCSTRIP program</b>	<b>263</b>
<b>46 A driver for this document</b>	<b>263</b>
<b>47 The code</b>	<b>263</b>
 <b>v ltfntcmd.dtx</b>	 <b>266</b>
<b>48 Introduction</b>	<b>266</b>
<b>49 The implementation</b>	<b>268</b>
<b>50 Initialization</b>	<b>273</b>
 <b>w ltpageno.dtx</b>	 <b>274</b>
<b>51 Page Numbering</b>	<b>274</b>
 <b>x ltxref.dtx</b>	 <b>275</b>
<b>52 Cross Referencing</b>	<b>275</b>
52.1 Cross Referencing . . . . .	275
 <b>y ltmiscen.dtx</b>	 <b>279</b>
<b>53 Miscellaneous Environments</b>	<b>279</b>
53.1 Environments . . . . .	279
53.2 Center, Flushright, Flushleft . . . . .	287
53.3 Verbatim . . . . .	289
 <b>z ltmath.dtx</b>	 <b>294</b>
<b>54 Math setup</b>	<b>294</b>
54.1 Math commands based on plain T <sub>E</sub> X . . . . .	294
54.1.1 The log-like functions . . . . .	294
54.1.2 Biggggg . . . . .	295
54.1.3 The UNSORTED Rest . . . . .	295
54.2 Math Environments . . . . .	300
54.3 External options to the standard document classes . . . . .	303
54.3.1 Left equation numbering . . . . .	303
54.3.2 Flush left equations . . . . .	304

<b>A</b>	<b>ltlists.dtx</b>	<b>307</b>
<b>55</b>	<b>List, and related environments</b>	<b>307</b>
55.1	List and Trivlist . . . . .	308
55.2	Vertical Spacing (skips) . . . . .	309
55.3	Penalties . . . . .	309
55.4	Horizontal Spacing (dimens) . . . . .	309
55.5	Default Values . . . . .	310
55.6	Itemize and Enumerate . . . . .	320
<b>B</b>	<b>ltboxes.dtx</b>	<b>322</b>
<b>56</b>	<b>L<sup>A</sup>T<sub>E</sub>X Box commands</b>	<b>322</b>
56.1	Some low-level constructs . . . . .	334
<b>C</b>	<b>lftab.dtx</b>	<b>335</b>
<b>57</b>	<b>Tabbing, Tabular and Array Environments</b>	<b>335</b>
57.1	tabbing . . . . .	335
57.2	array and tabular environments . . . . .	343
<b>D</b>	<b>ltpictur.dtx</b>	<b>357</b>
<b>58</b>	<b>Picture Mode</b>	<b>357</b>
58.1	Curves . . . . .	377
<b>E</b>	<b>ltthm.dtx</b>	<b>380</b>
<b>59</b>	<b>Theorem Environments</b>	<b>380</b>
<b>F</b>	<b>ltsect.dtx</b>	<b>384</b>
<b>60</b>	<b>Sectioning Commands</b>	<b>384</b>
60.1	The Title . . . . .	384
60.2	Sectioning . . . . .	385
60.2.1	Initializations . . . . .	391
60.3	Table of Contents etc. . . . .	392
60.3.1	Convention . . . . .	392
60.3.2	Commands . . . . .	392
<b>G</b>	<b>ltfloat.dtx</b>	<b>396</b>
<b>61</b>	<b>Floats</b>	<b>396</b>
61.1	Floating Environments . . . . .	396
61.2	Footnotes . . . . .	409

<b>H</b>	<b>ltxglo.dtx</b>	<b>415</b>
<b>62</b>	<b>Index and Glossary Generation</b>	<b>415</b>
<b>I</b>	<b>ltbibl.dtx</b>	<b>417</b>
<b>63</b>	<b>Bibliography Generation</b>	<b>417</b>
63.1	Default definitions . . . . .	420
<b>J</b>	<b>ltpage.dtx</b>	<b>421</b>
<b>64</b>	<b>Page styles and related commands</b>	<b>421</b>
64.1	Page Style Commands . . . . .	421
64.2	How a page style makes running heads and feet . . . . .	421
64.3	marking conventions . . . . .	421
<b>K</b>	<b>ltoutput.dtx</b>	<b>424</b>
<b>65</b>	<b>Output Routine</b>	<b>424</b>
65.1	Floats . . . . .	424
65.1.1	Kludgeins . . . . .	479
65.1.2	Float control . . . . .	480
65.1.3	Float placement parameters . . . . .	492
<b>L</b>	<b>ltxclass.dtx</b>	<b>496</b>
<b>66</b>	<b>Introduction</b>	<b>496</b>
<b>67</b>	<b>User interface</b>	<b>496</b>
67.1	Option processing . . . . .	497
<b>68</b>	<b>Class and Package interface</b>	<b>498</b>
68.1	Class name and version . . . . .	498
68.2	Package name and version . . . . .	498
68.3	Requiring other packages . . . . .	498
68.4	Declaring new options . . . . .	499
68.5	Safe Input Macros . . . . .	500
<b>69</b>	<b>Implementation</b>	<b>500</b>
69.1	Hooks . . . . .	512
69.2	Providing shipment . . . . .	514
<b>70</b>	<b>Package/class rollback mechanism</b>	<b>519</b>
<b>71</b>	<b>After Preamble</b>	<b>527</b>
<b>M</b>	<b>ltxhyphen.dtx</b>	<b>528</b>



<b>N</b>	<b>l<sup>u</sup>atex.dtx</b>	<b>530</b>
<b>72</b>	<b>Overview</b>	<b>530</b>
<b>73</b>	<b>Core T<sub>E</sub>X functionality</b>	<b>530</b>
<b>74</b>	<b>Plain T<sub>E</sub>X interface</b>	<b>531</b>
<b>75</b>	<b>Lua functionality</b>	<b>531</b>
75.1	Allocators in Lua . . . . .	531
75.2	Lua access to T <sub>E</sub> X register numbers . . . . .	532
75.3	Module utilities . . . . .	533
75.4	Callback management . . . . .	533
<b>76</b>	<b>Implementation</b>	<b>534</b>
76.1	Minimum LuaT <sub>E</sub> X version . . . . .	534
76.2	Older L <sup>A</sup> T <sub>E</sub> X/Plain T <sub>E</sub> X setup . . . . .	534
76.2.1	Fixes to <code>etex.src/etex.sty</code> . . . . .	535
76.2.2	luatex specific settings . . . . .	535
76.3	Attributes . . . . .	536
76.4	Category code tables . . . . .	536
76.5	Named Lua functions . . . . .	538
76.6	Custom whatsits . . . . .	539
76.7	Lua bytecode registers . . . . .	539
76.8	Lua chunk registers . . . . .	539
76.9	Lua loader . . . . .	539
76.10	Lua module preliminaries . . . . .	541
76.11	Lua module utilities . . . . .	541
76.11.1	Module tracking . . . . .	541
76.11.2	Module messages . . . . .	542
76.12	Accessing register numbers from Lua . . . . .	543
76.13	Attribute allocation . . . . .	544
76.14	Custom whatsit allocation . . . . .	544
76.15	Bytecode register allocation . . . . .	545
76.16	Lua chunk name allocation . . . . .	545
76.17	Lua function allocation . . . . .	546
76.18	Lua callback management . . . . .	546
76.18.1	Housekeeping . . . . .	546
76.18.2	Handlers . . . . .	548
76.18.3	Public functions for callback management . . . . .	550
<b>O</b>	<b>l<sup>u</sup>tfinal.dtx</b>	<b>555</b>
<b>77</b>	<b>Final settings</b>	<b>555</b>
77.1	Debugging . . . . .	555
77.2	Typesetting parameters . . . . .	555
77.3	Lccodes for hyphenation . . . . .	557
77.4	Hyphenation . . . . .	560
77.5	Font loading . . . . .	561
77.6	Input encoding . . . . .	561

77.7	Lccodes and uccodes . . . . .	565
77.8	Applying Patch files . . . . .	567
77.9	Loading further extensions . . . . .	568
77.10	Freeing Memory . . . . .	568
77.11	Initialise file list . . . . .	569
77.12	Dumping the format . . . . .	569
 <b>Change History</b>		 <b>570</b>
 <b>Index</b>		 <b>632</b>

# File a

## ltdirchk.dtx

### 1 L<sup>A</sup>T<sub>E</sub>X System Dependent Initialisations

This file implements the semi-automatic determination of various system dependent parts of the initialisation. The actual definitions may be placed in a file `texsys.cfg`. Thus for operating systems for which the tests here do not result in acceptable settings, a ‘hand written’ `texsys.cfg` may be produced.

The macros that must be defined are:

`\@currdir` `\@currdir{filename}<space>` should expand to a form of the filename that uniquely refers to the ‘current directory’ if this is possible. (The expansion should also end with a space.) on UNIX, this is `\def\@currdir{./}`. For more exotic operating systems you may want to make `\@currdir` a macro with arguments delimited by `.` and/or `<space>`. If the operating system has no concept of directory structure, this macro should be defined to be empty.

`\input@path` If the primitive `\openin` searches the same directories as the primitive `\input`, then it is possible to tell (using `\ifeof`) whether a file exists before trying to input it. For systems like this, `\input@path` should be left undefined.

If `\openin` does not ‘follow’ `\input` then `\input@path` must be defined to be a list of directories to search for input files. The format for each directory is as for `\@currdir`, normally just a prefix is required, but it may be a macro with space-delimited argument. That is, if `<dir>` is an entry in the input path, T<sub>E</sub>X will try to load the expansion of `<dir><filename><space>`

So either `<dir>` should be defined as a macro with argument delimited by space, or it should just expand to a directory name, including the final directory separator, so that it may be concatenated with the `<filename>`. This means that for UNIX-like syntax, each `<dir>` should end with a slash, `/`.

`\input@path` should expand to a list of such directories, each in a `{}` group.

`\filename@parse` After a call of the form: `\filename@parse{<filename>}`, the three macros `\filename@area`, `\filename@base`, `\filename@ext` should be defined to be the ‘area’ (or directory), basename and extension respectively. If there was no extension specified in `<filename>`, `\filename@ext` should be `\let` to `\relax` (so this case may be tested with `\ifundefined{filename@ext}` and, perhaps a default extension substituted).

Normally one would not need to define this macro in `texsys.cfg` as the automatic tests can supply parsers that work with UNIX and VMS and Macintosh syntax, as well as a basic parser that will cover many other cases. However some operating systems may need a ‘hand produced’ parser in which case it should be defined in this file.

The UNIX parser also works for most MSDOS T<sub>E</sub>X versions. Currently if the UNIX, VMS or Macintosh parser is not used, `\filename@parse` is defined to always return an empty area, and to split the argument into basename and extension at the first ‘.’ that occurs in the name. Parsers for other formats may be defined in `texsys.cfg`, in which case they will be used in preference to the default definitions.

`\@TeXversion` `\@TeXversion` is now set automatically by the initialisation tests in this file. You should not need to set it in `texsys.cfg`, however the following documentation

is left for information. L<sup>A</sup>T<sub>E</sub>X does not set this variable exactly, the automatic tests set it to:

2 for any version,  $v$ ,  $v < 3.0$

3 for any version,  $v$ ,  $3.0 \leq v \leq 3.14$

*undefined* otherwise.

However these values are accurate enough for L<sup>A</sup>T<sub>E</sub>X to take appropriate action for these old T<sub>E</sub>Xs.

If your T<sub>E</sub>X is older than version 3.141, then you should define `\@TeXversion` (using `\def`) to be the version number. If you do not do this<sup>1</sup>, L<sup>A</sup>T<sub>E</sub>X will not work around a bug in old T<sub>E</sub>X versions, and so error messages will appear in a very strange format, with `^^J` appearing instead of line breaks:

```
! LaTeX Error: \rubbish undefined.^^J^^JSee the LaTeX manual or LaTeX Companion
for explanation.^^JType H <return> for immediate help.
...
```

```
1.3 \renewcommand{\rubbish}
      {}
?
```

However if you put `\def\@TeXversion{3.14}` in `texsys.cfg` the following format will be used:

```
! LaTeX Error: \rubbish undefined.
```

```
See the LaTeX manual or LaTeX Companion for explanation.
```

```
Type H <return> for immediate help.
```

```
! .
...
```

```
1.3 \renewcommand{\rubbish}
      {}
?
```

Note that this has an extra line `! .` which does not appear in error messages that use the default settings with a current version of T<sub>E</sub>X, but this should not cause any confusion we hope.

## 2 Initialisation

As this file is read at a very early stage, some definitions that are normally considered to be part of the format must be made here.

### 2.1 INITEX

```
1 \<dircheck>
2 \<initex>
3 \<initex>\ifnum\catcode'\{=1
4 \<initex> \errmessage
5 \<initex> {LaTeX must be made using an initex with no format preloaded}
```

---

<sup>1</sup>Actually if your T<sub>E</sub>X is really old, version 2, L<sup>A</sup>T<sub>E</sub>X can detect this, and sets `\@TeXversion` to 2 if it is not set in the `cfg` file.

```

6 <initex>\fi
7 \catcode'\{=1
8 \catcode'\}=2

```

If Lua<sub>TEX</sub> is in use the extensions and other new primitives have to be activated: this is done as early as possible. Older versions of Lua<sub>TEX</sub> do not hide the primitives: a version check is not needed as the version itself will be missing in the case where action is needed!

```

9 \ifx\directlua\undefined
10 \else
11 \ifx\luatexversion\undefined

```

Enable e-TeX/pdfTeX/Umath primitives with their natural names

```

12 \directlua{tex.enableprimitives("",%
13 tex.extraprimitives('etex', 'pdftex', 'umath'))}

```

In current formats enable primitives with unprefix names. the latexrelease guards allow the primitives to be defined with a \luatex prefix if older formats are specified.

```

14 </initex>
15 </dircheck>
16 <*initex, latexrelease>
17 <latexrelease>\ifx\directlua\undefined\else
18 <latexrelease>\IncludeInRelease{2015/10/01}{\luatexluafunction}
19 <latexrelease>{LuaTeX (prefixed names)}%
20 \directlua{tex.enableprimitives("",%
21 tex.extraprimitives("omega", "aleph", "luatex"))}
22 <latexrelease>\EndIncludeInRelease
23 <latexrelease>\IncludeInRelease{0000/00/00}{\luatexluafunction}
24 <latexrelease>{LuaTeX (prefixed names)}%
25 <latexrelease>\directlua{
26 <latexrelease> tex.enableprimitives(
27 <latexrelease> "luatex",
28 <latexrelease> tex.extraprimitives("core","omega", "aleph", "luatex")
29 <latexrelease> )
30 <latexrelease> local i
31 <latexrelease> local t = { }
32 <latexrelease> for _,i in pairs(tex.extraprimitives("luatex")) do
33 <latexrelease> if not string.match(i,"^U") then
34 <latexrelease> if not string.match(i, "^luatex") then
35 <latexrelease> table.insert(t,i)
36 <latexrelease> end
37 <latexrelease> else
38 <latexrelease> if string.match(i,"^Uchar$") then
39 <latexrelease> table.insert(t,i)
40 <latexrelease> end
41 <latexrelease> end
42 <latexrelease> end
43 <latexrelease> for _,i in pairs(t) do
44 <latexrelease> tex.print(
45 <latexrelease> "\noexpand\\let\noexpand\\" .. i
46 <latexrelease> .. "\noexpand\\undefined"
47 <latexrelease> )
48 <latexrelease> end
49 <latexrelease>}
50 <latexrelease>\EndIncludeInRelease

```

```

51 \latexrelease\fi
52 \ifinitex, latexrelease\fi
53 \ifdircheck\fi
54 \ifinitex\fi
55 \fi
56 \fi

```

A test can now be made for eTeX.

```

57 \ifinitex\ifx\etexversion\undefined
58 \ifinitex\errmessage
59 \ifinitex{LaTeX requires e-TeX}
60 \ifinitex\expandafter\endinput
61 \ifinitex\fi

```

That distraction over, back to the basics of a format.

```

62 \catcode'\#=6
63 \catcode'\^=7
64 \chardef\active=13
65 \catcode'\@=11
66 \countdef\count@=255
67 \let\bgroup={ \let\egroup=}
68 \ifx@@input\@undefined\let@@input\input\fi
69 \ifx@@end\@undefined\let@@end\end\fi
70 \chardef\@inputcheck0
71 \chardef\sixt@@n=16
72 \newlinechar'\^^J
73 \def\typeout{\immediate\write17}
74 \def\dospecials{\do\ \do\\\do\{\do\}\do\$\do\&%
75 \do\#\do\^{\do\_ \do\% \do\~}
76 \def\@makeother#1{\catcode'#1=12\relax}
77 \def\space{ }
78 \def\@tempwafalse{\let\if@tempwa\iffalse}
79 \def\@tempwatrue{\let\if@tempwa\iftrue}
80 \let\if@tempwa\iffalse
81 \def\loop#1\repeat{\def\iterate{#1\relax\expandafter\iterate\fi}%
82 \iterate \let\iterate\relax}
83 \let\repeat\fi
84 \ifinitex\fi

```

## 2.2 Some bits of 2e

```

85 \if2kernel
86 \def\two@digits#1{\ifnum#1<10 0\fi\number#1}
87 \long\def\@firstoftwo#1#2{#1}
88 \long\def\@secondoftwo#1#2{#2}

```

This is a special version of \ProvidesFile for initex use.

```

89 \def\ProvidesFile#1{%
90 \begingroup
91 \catcode'\ 10 %
92 \ifnum \endlinechar<256 %
93 \ifnum \endlinechar>\m@ne
94 \catcode\endlinechar 10 %
95 \fi
96 \fi
97 \@makeother\/%

```

```

98     \ifnextchar[{\@providesfile{#1}}{\@providesfile{#1}[]}]
99 \def\@providesfile#1[#2]{%
100     \wlog{File: #1 #2}%
101     \@addtofilelist{ #2}%
102     \endgroup}
103 \long\def\@addtofilelist#1{}
104 \def\@empty{}
105 \catcode'\%=12
106 \def\@percentchar{%}
107 \catcode'\%=14
108 \let\@currdir\@undefined
109 \let\input@path\@undefined
110 \let\filename@parse\@undefined

\strip@prefix

111 \def\strip@prefix#1>{}
112 </2ekernel>

```

### 3 texsys.cfg

As mentioned above, any site specific definitions required to describe the filename handling must be entered into a file `texsys.cfg`. If `texsys.cfg` can not be located by `\openin`, we write a default version out. The default version only contains comments, so we do not actually input the file in that case. The automatic tests later will, hopefully, correctly define the required macros.

The tricky code below checks to see if `texsys.cfg` exists. If it does not, all the text in this file between `START` and `END` is copied verbatim to a new file `texsys.cfg`. If `texsys.cfg` is found, then it is simply input. This is only done when this file is being used unstripped.

```

113 <docstrip>
114 \openin15=texsys.cfg
115 \ifeof15
116 \typeout{** Writing a default texsys.cfg}
117 \immediate\openout15=texsys.cfg
118 \begingroup
119 \catcode'\^M\active%
120 \let^M\par%
121 \def\reserved@a#1^M{%
122     \def\reserved@b{#1}%
123     \ifx\reserved@b\reserved@c\endgroup\else%
124         \immediate\write15{#1}%
125         \expandafter\reserved@a\fi}%
126 \def\reserved@d#1START^M{\let\do\@makeother\dospecials\reserved@a}%
127 \catcode'\%=12
128 \def\reserved@c{END}
129 \reserved@d

START

```

#### 3.1 texsys.cfg

This file contains the site specific definitions of the four macros `\@currdir`, `\input@path`, `\filename@parse` and `\TeXversion`.

As distributed it only contains comments, however this ‘empty’ file will work on many systems because of the automatic tests built into `ltdirchk.dtx`. You *are* allowed to edit this file to add definitions of these macros appropriate to your system.

The macros that must be defined are:

`\@currdir`      `\@currdir{filename}<space>` should expand to a form of the filename that uniquely refers to the ‘current directory’ if this is possible. (The expansion should also end with a space.) on UNIX, this is `\def\@currdir{./}`. For more exotic operating systems you may want to make `\@currdir` a macro with arguments delimited by `.` and/or `<space>`. If the operating system has no concept of directory structure, this macro should be defined to be empty.

`\input@path`    If the primitive `\openin` searches the same directories as the primitive `\input`, then it is possible to tell (using `\ifeof`) whether a file exists before trying to input it. For systems like this, `\input@path` should be left undefined.

If `\openin` does not ‘follow’ `\input` then `\input@path` must be defined to be a list of directories to search for input files. The format for each directory is as for `\@currdir`, normally just a prefix is required, but it may be a macro with space-delimited argument. That is, if `<dir>` is an entry in the input path, `TEX` will try to load the expansion of

`<dir><filename><space>`

So either `<dir>` should be defined as a macro with argument delimited by space, or it should just expand to a directory name, including the final directory separator, so that it may be concatenated with the `<filename>`. This means that for UNIX-like syntax, each `<dir>` should end with a slash, `/`. One exception to this rule is that the input path should *always* contain the empty directory `{}` as this will allow ‘full pathnames’ to be used, and the ‘current directory’ to be searched.

`\input@path` should expand to a list of such directories, each in a `{}` group.

`\filename@parse`    After a call of the form: `\filename@parse{<filename>}`, the three macros `\filename@area`, `\filename@base`, `\filename@ext` should be defined to be the ‘area’ (or directory), basename and extension respectively. If there was no extension specified in `<filename>`, `\filename@ext` should be `\let` to `\relax` (so this case may be tested with `\@ifundefined{filename@ext}` and, perhaps a default extension substituted).

Normally one would not need to define this macro in `texsys.cfg` as the automatic tests can supply parsers that work with UNIX and VMS syntax, as well as a basic parser that will cover many other cases. However some operating systems may need a ‘hand produced’ parser in which case it should be defined in this file.

The UNIX parser also works for most MSDOS `TEX` versions. Currently if the UNIX or VMS parser is not used, `\filename@parse` is defined to always return an empty area, and to split the argument into basename and extension at the first ‘.’ that occurs in the name. Parsers for other formats may be defined in `texsys.cfg`, in which case they will be used in preference to the default definitions.

`\@TeXversion`    You should not need to set this macro in `texsys.cfg`. `LATEX` tests to set this automatically. See the comments in the opening section of `ltdirchk.dtx`.

The following sections give examples of definitions which might work on various systems. These are currently mainly untested as I only have access to a few systems, all of which do not need this file as the automatic tests work. All the code is commented out.



### 3.2 UNIX (web2c)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
130 %\def\@currdir{./}
131 %\let\input@path\@undefined
```

### 3.3 UNIX (other)

Apparently some commercial UNIX implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following (with whatever directories are used at your site): note that the directory names should end with `/`.

```
132 % \def\@currdir{./}
133 % \def\input@path{%
134 %   {/usr/local/lib/tex/inputs/distrib/}%
135 %   {/usr/local/lib/tex/inputs/contrib/}%
136 %   {/usr/local/lib/tex/inputs/local/}%
137 % }
```

### 3.4 MSDOS (emtex)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
138 % \def\@currdir{./}
139 % \let\input@path\@undefined
```

### 3.5 MSDOS (other)

Some PC implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following (with whatever directories are used at your site): note that the directory names should end with `/`. This assumes the implementation uses UNIX style `/` as the directory separator.

```
140 % \def\@currdir{./}
141 % \def\input@path{%
142 %   {c:/tex/inputs/distrib/}%
143 %   {c:/tex/inputs/contrib/}%
144 %   {c:/tex/inputs/local/}%
145 % }
```

### 3.6 VMS (DECUS T<sub>E</sub>X, PD VMS 3.6)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
146 % \def\@currdir{[] }
147 % \let\input@path\@undefined
```

### 3.7 VMS (???)

Some VMS implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following:

```
148 % \def\@currdir{[]}  
149 % \def\input@path{%  
150 %   {tex_inputs:}%  
151 %   {SOMEDISK:[SOME.TEX.DIRECTORY]}%  
152 % }
```

### 3.8 MACINTOSH (OzTeX 1.6)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
153 % \def\@currdir{:}  
154 % \let\input@path\@undefined
```

### 3.9 MACINTOSH (other)

Some Macintosh implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following (with whatever folders are used on your machine): note that the directory names should end with `:`, and they should contain *no* spaces.

```
155 % \def\@currdir{:}  
156 % \def\input@path{%  
157 %   {Hard-Disk:Applications:TeX:TeX-inputs:}%  
158 %   {Hard-Disk:Applications:TeX:My-inputs:}%  
159 % }
```

### 3.10 FAKE EXAMPLE

This example is for an operating system that has filenames of the form `<area>name`. For maximum compatibility with macro sets, you want `name.ext` to be mapped to `<ext>name`. and `<area>name.ext` to be mapped to `<area.ext>name`. `\input` does this mapping automatically, but `\openin` does not, and does not look in the same places as `\input`. `<>name` is the desired ‘current directory’ syntax.

the following code would possibly work:

```
160 % \def\@dir#1#2 {%  
161 %   \@d@r{#1}#2..\@nil}  
162 % \def\@d@r#1#2.#3.#4\@nil{%  
163 %   <\ifx\@dir#1\@dir\else#1\ifx\@dir#3\@dir\else.\fi\fi#3>#2 }  
164 %  
165 % \def\@currdir{\@dir{}}  
166 % \def\input@path{%  
167 %   {\@dir{area.one}}%  
168 %   {\@dir{area.two}}%  
169 % }  
  
END  
  
170 \immediate\closeout15
```

If `texsys.cfg` did exist, then input it.

```
171 \else
172 \typeout{** Using the existing texsys.cfg}
173 \closein15
174 \input texsys.cfg
175 \fi
176 \docstrip
```

If the stripped version of this file is being used (in `latex2e.ltx`) then `texsys.cfg` should be there, so just input it.

```
177 \dircheck\input texsys.cfg
```

## 4 Setting `\currdir`

`\currdir` This is a local definition of `\IfFileExists`. It tries to relocate `texsys.aux`. If `\IfFileExists` it succeeds, then the `\currdir` syntax has been determined. If all the tests fail then `\currdir` will be set to `\empty`, and `ltxcheck` will warn of this when it checks the format.

```
178 \begingroup
179 \count@ \time
180 \divide \count@ 60
181 \count2 = - \count@
182 \multiply \count2 60
183 \advance \count2 \time
```

`\today` The current date and time stamp.

```
184 \edef \today {%
185   \the year / \two@digits {\the month} / \two@digits {\the day} : %
186   \two@digits {\the count@} : \two@digits {\the count2}}
```

Create a file `texsys.aux` (hopefully in the current directory), then try to locate it again.

```
187 \immediate \openout15 = texsys.aux
188 \immediate \write15 {\today ^^J}
189 \immediate \closeout15 %
```

`#1` is the file to try, `#2` is what to do on success, `#3` on failure. Note that this definition is overwritten later on again!

```
190 \def \IfFileExists #1#2#3 {%
191   \openin \@inputcheck #1 %
192   \ifeof \@inputcheck
193     #3 \relax
194   \else
195     \read \@inputcheck to \reserved@a
196     \ifx \reserved@a \today
197       \typeout {#1 found} #2 \relax
198     \else
199       \typeout {BAD: old file \reserved@a (should be \today)} %
200       #3 \relax
201     \fi
202   \fi
203   \closein \@inputcheck}
```

```
204 \endlinechar=-1
```

If `\@currdir` has not been pre-defined in `texsys.cfg` then test for UNIX, VMS and Oz-TeX-Mac. syntax.

```
205 \ifx\@currdir\undefined
206   \IfFileExists{./texsys.aux}{\gdef\@currdir{.}}%
207   {\IfFileExists{[]texsys.aux}{\gdef\@currdir{[]}}%
208    {\IfFileExists{:texsys.aux}{\gdef\@currdir{:}}{}}}
```

If it is still undefined at this point, all the above tests failed. Earlier versions interactively prompted for a definition at this point, but it seems impossible to reliably obtain information from users at this point in the installation. This version of the file produces a format with no user-interaction. Later if the format is not suitable for the system, `texsys.cfg` may be edited and the format re-made.

```
209 \ifx\@currdir\undefined
210   \global\let\@currdir\empty
211   \typeout{^^J^^J%
212     !! No syntax for the current directory could be found^^J%
213   }%
214 \fi
```

Otherwise `\@currdir` was defined in `texsys.cfg`. In this case check that the syntax specified works on this system. (In case a complete L<sup>A</sup>T<sub>E</sub>X system has been copied from one system to another.) If the test fails, give up. The installer should remove or correct the offending `texsys.cfg` and try again.

```
215 \else
216   \IfFileExists{\@currdir texsys.aux}{}{%
217     \edef\reserved@a{\errhelp{%
218       texsys.cfg specifies the current directory syntax to be^^J%
219       \meaning\@currdir^^J%
220       but this does not work on this system.^^J%
221       Remove texsys.cfg and restart.}}\reserved@a
222     \errmessage{Bad texsys.cfg file: \noexpand\@currdir}\@@end}
```

The version of `\@currdir` in `texsys.cfg` looks OK.

```
223 \fi

224 \immediate\closeout15 %
225 \endgroup

226 \typeout{^^J^^J%
227   \noexpand\@currdir set to:
228   \expandafter\strip@prefix\meaning\@currdir.^^J%
229 }
```

Stop here if the file is being used unstripped.

```
230 \docstrip
231 \relax\endinput
232 \docstrip
```

## 5 Setting `\input@path`

Earlier versions of this file attempted to automatically test whether `\input@path` was required, and interactively prompt for a path if necessary. This was not found

to be very reliable The first-time installer of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> can not be expected to have enough information to supply the correct information to the prompts. Now the interaction is omitted. After the format is made the installer can attempt to run the test document `ltxcheck.tex` through L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. This will check, amongst other things, whether `texsys.cfg` will need to be edited and the format remade.

```
\input@path Now set up the \input@path.
      \input@path should either be undefined, or a list of directories as described
      in the introduction.
233   \typeout{^^J%
234     Assuming \noexpand\openin and \noexpand\input^^J%
235     \ifx\input@path\undefined
\input@path has not been pre-defined.
236       have the same search path.^^J%
237     \else
\input@path has been defined in texsys.cfg.
238       have different search paths.^^J%
239       LaTeX will use the path specified by \noexpand\input@path:^^J%
240     \fi
241   }
```

## 6 Filename Parsing

```
\filename@parse Split a filename into its components.
242 \ifx\filename@parse\undefined
243   \def\reserved@a{.}\ifx\currdir\reserved@a
\filename@parse was not specified in texsys.cfg, but \@currdir looks like
UNIX...
244   \typeout{^^JDefining UNIX/DOS style filename parser.^^J}
245   \def\filename@parse#1{%
246     \let\filename@area\empty
247     \expandafter\filename@path#1/\}
      Search for the last /.
248   \def\filename@path#1/#2\{%
249     \ifx\#2\%
250       \def\reserved@a{\filename@simple#1.\}%
251     \else
252       \edef\filename@area{\filename@area#1/}%
253       \def\reserved@a{\filename@path#2\}%
254     \fi
255     \reserved@a}
256 \else\def\reserved@a{[]}\ifx\currdir\reserved@a
\filename@parse was not specified in texsys.cfg, but \@currdir looks like
VMS...
257   \typeout{^^JDefining VMS style filename parser.^^J}
258   \def\filename@parse#1{%
259     \let\filename@area\empty
260     \expandafter\filename@path#1/\}
```

Search for the last ].

```

261 \def\filename@path#1:#2\\{%
262 \ifx\\#2\\%
263 \def\reserved@a{\filename@simple#1.\\}%
264 \else
265 \edef\filename@area{\filename@area#1}%
266 \def\reserved@a{\filename@path#2\\}%
267 \fi
268 \reserved@a}
269 \else\def\reserved@a{:}\ifx\@currdir\reserved@a

```

\filename@parse was not specified in texsys.cfg, but \@currdir looks like Macintosh...

```

270 \typeout{^^JDefining Mac style filename parser.^^J}
271 \def\filename@parse#1{%
272 \let\filename@area\@empty
273 \expandafter\filename@path#1:}

```

Search for the last :.

```

274 \def\filename@path#1:#2\\{%
275 \ifx\\#2\\%
276 \def\reserved@a{\filename@simple#1.\\}%
277 \else
278 \edef\filename@area{\filename@area#1:}%
279 \def\reserved@a{\filename@path#2\\}%
280 \fi
281 \reserved@a}
282 \else

```

\filename@parse was not specified in texsys.cfg. So just make a simple parser that always sets \filename@area to empty.

```

283 \typeout{^^JDefining generic filename parser.^^J}
284 \def\filename@parse#1{%
285 \let\filename@area\@empty
286 \expandafter\filename@simple#1.}
287 \fi\fi\fi

```

\filename@simple is used by all three versions. Finally we can split off the extension.

```

288 </dircheck>
289 <{*dircheck, latexrelease>
290 <latexrelease> \IncludeInRelease{2019/10/01}{\filename@simple}
291 <latexrelease> {Final dot for extension}%
292 \def\filename@simple#1.#2\\{%
293 \ifx\\#2\\%
294 \let\filename@ext\relax
295 \edef\filename@base{#1}%
296 \else
297 \filename@dots{#1}#2\\%
298 \fi}
299 \def\filename@dots#1#2.#3\\{%
300 \ifx\\#3\\%
301 \def\filename@ext{#2}%
302 \edef\filename@base{#1}%

```

```

303 \else
304   \filename@dots{#1.#2}#3\\%
305 \fi}
306 \latexrelease\EndIncludeInRelease
307 \latexrelease\IncludeInRelease{0000/00/00}{\filename@simple}
308 \latexrelease\{Final dot for extension}%
309 \latexrelease\def\filename@simple#1.#2\\{%
310 \latexrelease\ifx\#2\\%
311 \latexrelease\let\filename@ext\relax
312 \latexrelease\else
313 \latexrelease\edef\filename@ext{\filename@dot#2\\}%
314 \latexrelease\fi
315 \latexrelease\edef\filename@base{#1}}
316 \latexrelease\EndIncludeInRelease
317 \</dircheck, latexrelease>
318 \<(*dircheck>

    Remove a final dot, added earlier.
319 \def\filename@dot#1.\\{#1}
320 \else

Otherwise, \filename@parse was specified in texsys.cfg.
321 \typeout{^^J^^J%
322 \noexpand\filename@parse was defined in texsys.cfg:^^J%
323 \expandafter\strip@prefix\meaning\filename@parse.^^J%
324 }
325 \fi

```

## 7 T<sub>E</sub>X Versions

\TeXversion T<sub>E</sub>X versions older than than 3.141 require \TeXversion to be set. This can be determined automatically due to a trick suggested by Bernd Raichle. (Actually this will not always get the correct version number, eg T<sub>E</sub>X3.14 would be detected as T<sub>E</sub>X3, but L<sup>A</sup>T<sub>E</sub>X only needs to take account of T<sub>E</sub>X's older than 3, or between 3 and 3.14.

```

326 \ifx\TeXversion\undefined
327 \ifx\undefined\inputlineno
328 \def\TeXversion{2}
329 \else
330 {\catcode'\^^J=\active
331 \def\reserved@a#1#2\@@{\if#1\string~3\fi}
332 \edef\reserved@a{\expandafter\reserved@a\string^^J\@@}
333 \ifx\reserved@a\@empty\else\gdef\TeXversion{3}\fi}
334 \fi
335 \fi

336 \</dircheck>

```

## 8 lt<sub>x</sub>check.tex

After the format has been made, and article.cls moved with the other files to the 'standard input directory' as specified in install.txt, the format may be checked

by running the file `ltxcheck.tex`.



# File b

## ltplain.dtx

### 9 Plain T<sub>E</sub>X

L<sup>A</sup>T<sub>E</sub>X includes almost all of the functionality of Knuth's original 'Basic Macros'. That is, the plain T<sub>E</sub>X format described in Appendix B of the T<sub>E</sub>XBook. However, some of the user commands are not much use so, in order to save memory, we may remove them from the kernel into a package. Here is a list of the commands that may be removed (PROBABLY NOT COMPLETE).

```
\magstep      \magstephalf
\mathhexbox
\vglue        \vgl@
\hglue        \hgl@
```

This file is by now very small as most of it has been moved to more appropriate kernel files: it may disappear completely one day.

L<sup>A</sup>T<sub>E</sub>X font definitions are done using NFSS2 so none of PLAIN's font definitions are in L<sup>A</sup>T<sub>E</sub>X.

L<sup>A</sup>T<sub>E</sub>X has its own tabbing environment, so PLAIN's is disabled.

L<sup>A</sup>T<sub>E</sub>X uses its own output routine, so most of the plain one was removed.

```
1 (*2ekernel)
2 \catcode'\{=1 % left brace is begin-group character
3 \catcode'\}=2 % right brace is end-group character
4 \catcode'\$=3 % dollar sign is math shift
5 \catcode'\&=4 % ampersand is alignment tab
6 \catcode'\#=6 % hash mark is macro parameter character
7 \catcode'\^=7 % circumflex and uparrow are for superscripts
8 \catcode'\_ =8 % underline and downarrow are for subscripts
9 \catcode'\^I=10 % ascii tab is a blank space
10 \chardef\active=13 \catcode'\^=\active % tilde is active
11 \catcode'\^L=\active \def^L{\par}% ascii form-feed is \par
12 \message{catcodes,}
```

We had to define the \catcodes right away, before the message line, since \message uses the { and } characters. When INITEX (the T<sub>E</sub>X initializer) starts up, it has defined the following \catcode values:

```
\catcode'\^@=9 %  ascii null is ignored
\catcode'\^M=5 %  ascii return is end-line
\catcode'\ =0 %    backslash is TeX escape character
\catcode'\%=14 %   percent sign is comment character
\catcode'\ =10 %   ascii space is blank space
\catcode'\^?=15 %  ascii delete is invalid
\catcode'\A=11 ... \catcode'\Z=11 % uppercase letters
\catcode'\a=11 ... \catcode'\z=11 % lowercase letters
all others are type 12 (other)
```

Here is a list of the characters that have been specially catcoded:

```
13 \def\dospecials{\do\ \do\\\do\{\do\}\do\$ \do\&%
14 \do\# \do\^ \do\_ \do\% \do\^}
```

(not counting ascii null, tab, linefeed, formfeed, return, delete) Each symbol in the list is preceded by , which can be defined if you want to do something to every item in the list.

We make @ signs act like letters, temporarily, to avoid conflict between user names and internal control sequences of plain format.

```
15 \catcode'@=11
```

To make the plain macros more efficient in time and space, several constant values are declared here as control sequences. If they were changed, anything could happen; so they are private symbols.

```
\@ne Small constants are defined using \chardef.
\tw@ 16 \chardef\@ne=1
\thr@@ 17 \chardef\tw@=2
\sixt@@n 18 \chardef\thr@@=3
\@cclv 19 \chardef\sixt@@n=16
        20 \chardef\@cclv=255

\@cclvi Constants above 255 defined using \mathchardef.
\@m 21 \mathchardef\@cclvi=256
\@M 22 \mathchardef\@m=1000
\@MM 23 \mathchardef\@M=10000
      24 \mathchardef\@MM=20000
```

Allocation of registers

Here are macros for the automatic allocation of \count, \box, \dimen, \skip, \muskip, and \toks registers, as well as \read and \write stream numbers, \fam codes, \language codes, and \insert numbers.

```
25 \message{registers,}
```

When a register is used only temporarily, it need not be allocated; grouping can be used, making the value previously in the register return after the close of the group. The main use of these macros is for registers that are defined by one macro and used by others, possibly at different nesting levels. All such registers should be defined through these macros; otherwise conflicts may occur, especially when two or more macro packages are being used at the same time.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

The following counters are reserved:

- 0 to 9 page numbering
- 10 count allocation
- 11 dimen allocation
- 12 skip allocation
- 13 muskip allocation
- 14 box allocation
- 15 toks allocation
- 16 read file allocation
- 17 write file allocation
- 18 math family allocation
- 19 language allocation
- 20 insert allocation
- 21 the most recently allocated number
- 22 constant -1

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

New counters are allocated starting with 23, 24, etc. Other registers are allocated starting with 10. This leaves 0 through 9 for the user to play with safely, except that counts 0 to 9 are considered to be the page and subpage numbers (since they are displayed during output). In this scheme, `\count` 10 always contains the number of the highest-numbered counter that has been allocated, `\count` 14 the highest-numbered box, etc. Inserts are given numbers 254, 253, etc., since they require a `\count`, `\dimen`, `\skip`, and `\box` all with the same number; `\count` 20 contains the lowest-numbered insert that has been allocated. Of course, `\box255` is reserved for `\output`; `\count255`, `\dimen255`, and `\skip255` can be used freely.

It is recommended that macro designers always use `\global` assignments with respect to registers numbered

1, 3, 5, 7, 9,

and always non-`\global` assignments with respect to registers

0, 2, 4, 6, 8, 255.

This will prevent “save stack buildup” that might otherwise occur.

```
26 \count10=22 % allocates \count registers 23, 24, ...
27 \count11=9 % allocates \dimen registers 10, 11, ...
28 \count12=9 % allocates \skip registers 10, 11, ...
29 \count13=9 % allocates \muskip registers 10, 11, ...
30 \count14=9 % allocates \box registers 10, 11, ...
31 \count15=9 % allocates \toks registers 10, 11, ...
32 \count16=-1 % allocates input streams 0, 1, ...
33 \count17=-1 % allocates output streams 0, 1, ...
34 \count18=3 % allocates math families 4, 5, ...
35 \count19=0 % allocates \language codes 1, 2, ...
36 \count20=255 % allocates insertions 254, 253, ...
```

```
\insc@unt The insertion counter and most recent allocation.
\allocationnumber 37 \countdef\insc@unt=20
38 \countdef\allocationnumber=21
```

```
\m@ne The constant -1.
39 \countdef\m@ne=22 \m@ne=-1
```

```
\wlog Write on log file (only)
40 \def\wlog{\immediate\write\m@ne}
```

```
\count@ Here are abbreviations for the names of scratch registers that don't need to be
\dimen@ allocated.
\dimen@i 41 \countdef\count@=255
\dimen@ii 42 \dimendef\dimen@=0
\skip@ 43 \dimendef\dimen@i=1 % global only
\toks@ 44 \dimendef\dimen@ii=2
45 \skipdef\skip@=0
46 \toksdef\toks@=0
```

```
\newcount Now, we define \newcount, \newbox, etc. so that you can say \newcount\foo and
\newdimen \foo will be defined (with \countdef) to be the next counter.
\newskip To find out which counter \foo is, you can look at \allocationnumber.
\newmuskip Since there's no \boxdef command, \chardef is used to define a \newbox,
\newbox \newinsert, \newfam, and so on.
\newtoks
\newread
\newwrite
\newfam
\newlanguage
```

L<sup>A</sup>T<sub>E</sub>X change: remove `\outer` from `\newcount` and `\newdimen` (FMi) This is necessary to use `\newcount` inside `\if...` later on. Also remove from `\newskip`, `\newbox` `\newwrite` and `\newfam` (DPC) to save later redefinition.

```

47 /2ekernel>
48 /*2ekernel | latexrelease>
49 (latexrelease)\IncludeInRelease{2015/01/01}%
50 (latexrelease)          {\newcount}{Extended Allocation}%

51 \def\newcount {\e@alloc\count \countdef {\count10}\insc@unt\float@count}
52 \def\newdimen {\e@alloc\dimen \dimendef {\count11}\insc@unt\float@count}
53 \def\newskip  {\e@alloc\skip \skipdef {\count12}\insc@unt\float@count}
54 \def\newmuskip
55          {\e@alloc\muskip\muskipdef{\count13}\m@ne\e@alloc@top}

```

For compatibility use `\chardef` in the classical range.

```

56 \def\newbox    {\e@alloc\box
57                {\ifnum\allocationnumber<\@ccclvi
58                 \expandafter\chardef
59                 \else
60                 \expandafter\e@alloc@chardef
61                 \fi}
62                {\count14}\insc@unt\float@count}
63 \def\newtoks   {\e@alloc\toks \toksdef{\count15}\m@ne\e@alloc@top}
64 \def\newread   {\e@alloc\read \chardef{\count16}\m@ne\sixt@@n}

```

Skip `\write18` due to its traditional use as a shell-escape.

```

65 \ifx\directlua\@undefined
66   \def\newwrite {\e@alloc\write \chardef{\count17}\m@ne\sixt@@n}
67 \else
68   \def\newwrite {\e@alloc\write
69                 {\ifnum\allocationnumber=18
70                  \advance\count17\@ne
71                  \allocationnumber\count17 %
72                  \fi
73                  \global\chardef}%
74                 {\count17}%
75                 \m@ne
76                 {128}}
77 \fi

78 \def\new@mathgroup
79   {\e@alloc\mathgroup\chardef{\count18}\m@ne\e@mathgroup@top}
80 \let\newfam\new@mathgroup

81 \ifx\directlua\@undefined
82   \def\newlanguage {\e@alloc\language \chardef{\count19}\m@ne\@ccclvi}
83 \else
84   \def\newlanguage {\e@alloc\language \chardef{\count19}\m@ne{16384}}
85 \fi
86 /2ekernel | latexrelease>

87 (latexrelease)\EndIncludeInRelease
88 (latexrelease)\IncludeInRelease{0000/00/00}%
89 (latexrelease)          {\newcount}{Extended Allocation}%
90 (latexrelease)\def\newcount{\alloc@0\count\countdef\insc@unt}
91 (latexrelease)\def\newdimen{\alloc@1\dimen\dimendef\insc@unt}

```

```

92 <latexrelease>\def\newskip{\alloc@2\skip\skipdef\insc@unt}
93 <latexrelease>\def\newmuskip{\alloc@3\muskip\muskipdef\@ccclvi}
94 <latexrelease>\def\newbox{\alloc@4\box\chardef\insc@unt}
95 <latexrelease>\def\newtoks{\alloc@5\toks\toksdef\@ccclvi}
96 <latexrelease>\def\newread{\alloc@6\read\chardef\sixt@@n}
97 <latexrelease>\def\newwrite{\alloc@7\write\chardef\sixt@@n}
98 <latexrelease>\def\new@mathgroup{\alloc@8\fam\chardef\sixt@@n}
99 <latexrelease>\def\newlanguage{\alloc@9\language\chardef\@ccclvi}
100 <latexrelease>\let\newfam\new@mathgroup
101 <latexrelease>\EndIncludeInRelease

\@alloc@chardef The upper limit of extended registers, which leaves this number (eg \dimen32767)
\@alloc@top always unallocated by these macros. cf traditional \dimen255.

102 <*2kernel | latexrelease>
103 <latexrelease>\IncludeInRelease{2015/01/01}%
104 <latexrelease> \{\@alloc@chardef\}{Extended Allocation}%

105 \ifx\directlua\@undefined
106 \ifx\widowpenalties\@undefined

classic tex has 28 registers.

107 \mathchardef\@alloc@top=255
108 \let\@alloc@chardef\chardef
109 \else

etex and xetex have 215 registers.

110 \mathchardef\@alloc@top=32767
111 \let\@alloc@chardef\mathchardef
112 \fi
113 \else

luatex has 216 registers.

114 \chardef\@alloc@top=65535
115 \let\@alloc@chardef\chardef
116 \fi

117 </2kernel | latexrelease>
118 <latexrelease>\EndIncludeInRelease
119 <latexrelease>\IncludeInRelease{0000/00/00}%
120 <latexrelease> \{\@alloc@chardef\}{Extended Allocation}%
121 <latexrelease>\let\@alloc@top\@undefined
122 <latexrelease>\let\@alloc@chardef\@undefined
123 <latexrelease>\EndIncludeInRelease

\@mathgroup@top The upper limit of extended math groups (\fam) 16 in classic TEX and e-TEX, but
256 in Unicode TeX variants.

124 <*2kernel | latexrelease>
125 <latexrelease>\IncludeInRelease{2015/01/01}%
126 <latexrelease> \{\@mathgroup@top\}{Extended Allocation}%

127 \ifx\Umathcode\@undefined

classic and e tex have 16 fam (0–15).

128 \chardef\@mathgroup@top=16
129 \else

```

xetex and luatex have 256 fam (0–255).

```

130 \chardef\@mathgroup@top=256
131 \fi
132 </2ekernel | latexrelease>
133 <latexrelease>\EndIncludeInRelease
134 <latexrelease>\IncludeInRelease{0000/00/00}%
135 <latexrelease> \{\@mathgroup@top\}{Extended Allocation}%
136 <latexrelease>\let\@mathgroup@top\@undefined
137 <latexrelease>\EndIncludeInRelease

```

**\@alloc** A modified version of `\alloc@` that takes the count register rather than just the final digit of its number (assuming `\count1x`). It also has an extra argument to give the top of the extended range.

```

#1 #2 #3 #4 #5 #6
\@alloc type defcmd current top extended-top newname
Note that if just a single allocation range is required (not omitting a range up
to 255 for inserts) then -1 should be used for the first upper bound argument, #4.
138 <*2ekernel | latexrelease>
139 <latexrelease>\IncludeInRelease{2015/01/01}\{\@alloc\}{Extended Allocation}%
140 \def\@alloc#1#2#3#4#5#6{%
141 \global\advance#3\@ne
142 \e@ch@ck{#3}{#4}{#5}#1%
143 \allocationnumber#3\relax
144 \global#2#6\allocationnumber
145 \wlog{\string#6=\string#1\the\allocationnumber}}%
146 </2ekernel | latexrelease>
147 <latexrelease>\EndIncludeInRelease
148 <latexrelease>\IncludeInRelease{0000/00/00}\{\@alloc\}{Extended Allocation}%
149 <latexrelease>\let\@alloc\@undefined
150 <latexrelease>\EndIncludeInRelease
151 <*2ekernel>

```

**\e@ch@ck** Extended check command. If the first range is exceeded, bump to 256 (or 266 for counts) and try again, testing the extended range.

**\extrafloats** Allocate matching registers from the top of the extended range and add to `\@freelist`.

```

152 </2ekernel>
153 <*2ekernel | latexrelease>
154 <latexrelease>\IncludeInRelease{2015/10/01}
155 <latexrelease> \{\e@ch@ck\}{Extended Allocation (checking)}%
156 \gdef\e@ch@ck#1#2#3#4{%
157 \ifnum#1<#2\else
158 \ifnum#1=#2\relax
159 \global#1\@cclvi
160 \ifx\count#4\global\advance#1 10 \fi
161 \fi

```

If we've reached the classical top limit, bump to 256 or 266 for counts (count 256–265 are reserved by the allocation system).

Check we are below the extended limit.

```

162 \ifnum#1<#3\relax
163 \else
164 \errmessage{No room for a new \string#4}%
165 \fi
166 \fi}%
167 \<latexrelease>\EndIncludeInRelease
168 \<latexrelease>\IncludeInRelease{2015/01/01}%
169 \<latexrelease>{\e@ch@ck}{Extended Allocation (checking)}%
170 \<latexrelease>\gdef\e@ch@ck#1#2#3#4{%
171 \<latexrelease> \ifnum#1<#2\else
172 \<latexrelease> \ifnum#1=#2\relax
173 \<latexrelease> #1\@cclvi
174 \<latexrelease> \ifx\count#4\advance#1 10 \fi
175 \<latexrelease> \fi
176 \<latexrelease> \ifnum#1<#3\relax
177 \<latexrelease> \else
178 \<latexrelease> \errmessage{No room for a new #4}%
179 \<latexrelease> \fi
180 \<latexrelease> \fi}%
181 \<latexrelease>\EndIncludeInRelease
182 \<latexrelease>\IncludeInRelease{0000/00/00}%
183 \<latexrelease>{\e@ch@ck}{Extended Allocation (checking)}%
184 \<latexrelease>\let\e@ch@ck\@undefined
185 \<latexrelease>\EndIncludeInRelease

186 \<latexrelease>\IncludeInRelease{2015/01/01}%
187 \<latexrelease>{\extrafloats}{Extra floats}%

188 \let\float@count\e@alloc@top

```

\extrafloats

```

189 \ifx\numexpr\@undefined
In classic TeX use \newinsert to allocate float boxes.
190 \def\extrafloats#1{%
191 \count@#1\relax
192 \ifnum\count@>\z@
193 \newinsert\reserved@a
194 \global\expandafter\chardef
195 \csname bx@the\allocationnumber\endcsname\allocationnumber
196 \@cons\@freelist{\csname bx@the\allocationnumber\endcsname}%
197 \advance\count@\m@ne
198 \expandafter\extrafloats
199 \expandafter\count@
200 \fi
201 }%

202 \else
In e-tex take float boxes from the top of the extended range.
203 \def\extrafloats#1{%
204 \ifnum#1>\z@
205 \count@\numexpr\float@count-1\relax
206 \ch@ck0\count@\count
207 \ch@ck1\count@\dimen

```

```

208 \ch@ck2\count@\skip
209 \ch@ck4\count@\box
210 \global\@alloc@chardef\float@count\count@
211 \global\expandafter\@alloc@chardef
212 \csname bx@\the\float@count\endcsname\float@count
213 \@cons\@freelist{\csname bx@\the\float@count\endcsname}%
214 \expandafter
215 \extrafloats\expandafter{\numexpr#1-1\relax}%
216 \fi}%
217 \fi

218 /2ekernel | latexrelease)
219 (latexrelease)\EndIncludeInRelease
220 (latexrelease)\IncludeInRelease{0000/00/00}%
221 (latexrelease) {\extrafloats}{Extra floats}%
222 (latexrelease)\let\float@count\@undefined
223 (latexrelease)\let\extrafloats\@undefined
224 (latexrelease)\EndIncludeInRelease
225 (*2ekernel)

\alloc@

226 \def\alloc@#1#2#3#4#5{\global\advance\count1#1\@ne
227 \ch@ck#1#4#2%
228 \allocationnumber\count1#1%
229 \global#3#5\allocationnumber
230 \wlog{\string#5=\string#2\the\allocationnumber}}

\newinsert

231 /2ekernel)
232 (*2ekernel | latexrelease)
233 (latexrelease)\IncludeInRelease{2015/10/01}
234 (latexrelease) {\newinsert}{Extended \newinsert}%

235 \ifx\numexpr\@undefined
If e-TeX is not available use the original plain TeX definition of \newinsert.
236 \def\newinsert#1{\global\advance\insc@unt \m@ne
237 \ch@ck0\insc@unt\count
238 \ch@ck1\insc@unt\dimen
239 \ch@ck2\insc@unt\skip
240 \ch@ck4\insc@unt\box
241 \allocationnumber\insc@unt
242 \global\chardef#1\allocationnumber
243 \wlog{\string#1=\string\insert\the\allocationnumber}}

244 \else
The highest register allowed with \insert.
245 \ifx\directlua\@undefined
246 \chardef\@insert@top255
247 \else
248 \chardef\@insert@top\@alloc@top
249 \fi
If the classic registers are exhausted, take an insert from the free float list and use
\extrafloats to add a new float to that list.

```



```

250 \def\newinsert#1{%
251 \@tempswafalse
252 \global\advance\insc@unt\m@ne
253 \ifnum\count10<\insc@unt
254 \ifnum\count11<\insc@unt
255 \ifnum\count12<\insc@unt
256 \ifnum\count14<\insc@unt
257 \@tempswatrue
258 \fi\fi\fi\fi
259 \if@tempswa
260 \allocationnumber\insc@unt
261 \else
262 \global\advance\insc@unt\@ne
263 \extrafloats\@ne
264 \@next\@currbox\@freelist
265 {\ifnum\@currbox<\e@insert@top
266 \allocationnumber\@currbox
267 \else
268 \ch@ck0\m@ne\insert
269 \fi}%
270 {\ch@ck0\m@ne\insert}%
271 \fi
272 \global\chardef#1\allocationnumber
273 \wlog{\string#1=\string\insert\the\allocationnumber}%
274 }

275 \fi
276 </2ekernel | latexrelease>

277 <latexrelease>\EndIncludeInRelease
278 <latexrelease>\IncludeInRelease{0000/00/00}%
279 <latexrelease> {\newinsert}{Extended \newinsert}%
280 <latexrelease>\let\e@insert@top\@undefined
281 <latexrelease>\def\newinsert#1{\global\advance\insc@unt \m@ne
282 <latexrelease> \ch@ck0\insc@unt\count
283 <latexrelease> \ch@ck1\insc@unt\dimen
284 <latexrelease> \ch@ck2\insc@unt\skip
285 <latexrelease> \ch@ck4\insc@unt\box
286 <latexrelease> \allocationnumber\insc@unt
287 <latexrelease> \global\chardef#1\allocationnumber
288 <latexrelease> \wlog{\string#1=\string\insert\the\allocationnumber}}
289 <latexrelease>\EndIncludeInRelease
290 <*2ekernel>

\ch@ck

291 \gdef\ch@ck#1#2#3{%
292 \ifnum\count1#1<#2\else
293 \errmessage{No room for a new #3}%
294 \fi}

\newhelp

295 \def\newhelp#1#2{\newtoks#1#1\expandafter{\csname#2\endcsname}}

\maxdimen Here are some examples of allocation.
\hideskip

```

```

296 \newdimen\maxdimen \maxdimen=16383.99999pt % the largest legal <dimen>
297 \newskip\hideskip \hideskip=-1000pt plus 1fill % negative but can grow

\p@
\z@ 298 \newdimen\p@ \p@=1pt % this saves macro space and time
\z@skip 299 \newdimen\z@ \z@=0pt % can be used both for 0pt and 0
\voidb@x 300 \newskip\z@skip \z@skip=0pt plus0pt minus0pt
301 \newbox\voidb@x % permanently void box register

Assign initial values to TeX's parameters
302 \message{parameters,}

All of TeX's numeric parameters are listed here, but the code is commented
out if no special value needs to be set. INITEX makes all parameters zero except
where noted.
Historical ETeX 2.09 comments (not necessarily accurate any more):
303 \pretolerance=100
304 \tolerance=200 % INITEX sets this to 10000
305 \hbadness=1000
306 \vbadness=1000
307 \linepenalty=10
308 \hyphenpenalty=50
309 \exhyphenpenalty=50
310 \binoppenalty=700
311 \relpenalty=500
312 \clubpenalty=150
313 \widowpenalty=150
314 \displaywidowpenalty=50
315 \brokenpenalty=100
316 \predisplaypenalty=10000
\postdisplaypenalty=0
\interlinepenalty=0
\floatingpenalty=0, set during \insert
\outputpenalty=0, set before TeX enters \output
317 \doublehyphendemerits=10000
318 \finalhyphendemerits=5000
319 \adjdemerits=10000
\looseness=0, cleared by TeX after each paragraph
\pausing=0
\holdinginserts=0
\tracingonline=0
\tracingmacros=0
\tracingstats=0
\tracingparagraphs=0
\tracingpages=0
\tracingoutput=0
320 \tracinglostchars=1
\tracingcommands=0
\tracingrestores=0
\language=0
321 \uchyph=1

```

```

\lefthyphenmin=2 \righthyphenmin=3 set below
\globaldefs=0
\maxdeadcycles=25 % INITEX does this
\hangafter=1 % INITEX does this, also TeX after each paragraph
\fam=0
\mag=1000 % INITEX does this
\escapechar='\ % INITEX does this

322 \defaultthyphenchar='\-
323 \defaultskewchar=-1

\endlinechar='\^^M % INITEX does this
\newlinechar=-1 \LaTeX\ sets this in ltdefs.dtx.

324 \delimiterfactor=901

\time=now % TeX does this at beginning of job
\day=now % TeX does this at beginning of job
\month=now % TeX does this at beginning of job
\year=now % TeX does this at beginning of job

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

In L<sup>A</sup>T<sub>E</sub>X we don't want box information in the transcript unless we do a full tracing.

```

325 \showboxbreadth=-1
326 \showboxdepth=-1
327 \errorcontextlines=-1

328 \hfuzz=0.1pt
329 \vfuzz=0.1pt
330 \overfullrule=5pt
331 \maxdepth=4pt
332 \splitmaxdepth=\maxdimen
333 \boxmaxdepth=\maxdimen

```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```

\lineskiplimit=0pt, changed by \normalbaselines

334 \delimitershortfall=5pt
335 \nulldelimiterspace=1.2pt
336 \scriptspace=0.5pt

\mathsurround=0pt
\predisplaysize=0pt, set before TeX enters $$
\displaywidth=0pt, set before TeX enters $$
\displayindent=0pt, set before TeX enters $$

337 \parindent=20pt

\hangindent=0pt, zeroed by TeX after each paragraph
\hoffset=0pt
\voffset=0pt

\baselineskip=0pt, changed by \normalbaselines
\lineskip=0pt, changed by \normalbaselines

338 \parskip=0pt plus 1pt

```

```

339 \abovedisplayskip=12pt plus 3pt minus 9pt
340 \abovedisplayshortskip=0pt plus 3pt
341 \belowdisplayskip=12pt plus 3pt minus 9pt
342 \belowdisplayshortskip=7pt plus 3pt minus 4pt

\leftskip=0pt
\rightskip=0pt

343 \topskip=10pt
344 \splittopskip=10pt

\tabskip=0pt
\spaceskip=0pt
\xspaceskip=0pt

345 \parfillskip=0pt plus 1fil
End of historical LATEX 2.09 comments.

\normalbaselineskip We also define special registers that function like parameters:
\normallineskip 346 \newskip\normalbaselineskip \normalbaselineskip=12pt
\normallineskiplimit 347 \newskip\normallineskip \normallineskip=1pt
348 \newdimen\normallineskiplimit \normallineskiplimit=0pt

\interfootlinepenalty

349 \newcount\interfootnotelinepenalty \interfootnotelinepenalty=100

Definitions for preloaded fonts

\magstephalf
\magstep 350 \def\magstephalf{1095 }
351 \def\magstep#1{\ifcase#1 \@m\or 1200\or 1440\or 1728\or
352 2074\or 2488\fi\relax}

Macros for setting ordinary text

\frenchspacing
\nonfrenchspacing 353 \def\frenchspacing{\sfcode'\.\@m \sfcode'\?\@m \sfcode'\!\@m
354 \sfcode'\:\@m \sfcode'\;\@m \sfcode'\,\@m}
355 \def\nonfrenchspacing{\sfcode'\.3000\sfcode'\?3000\sfcode'\!3000%
356 \sfcode'\:2000\sfcode'\;1500\sfcode'\,1250 }

\normalbaselines
357 \def\normalbaselines{\lineskip\normallineskip
358 \baselineskip\normalbaselineskip \lineskiplimit\normallineskiplimit}

\M Save a bit of space by using \let here.
\I 359 \def\^^M{\ } % control <return> = control <space>
360 \let\^^I\^^M % same for <tab>

\lq
\rq 361 \def\lq{' }
362 \def\rq{' }

\lbrack
\rbrack 363 \def\lbrack{[ }
364 \def\rbrack{[ }

```

```

\aa These are not from plain.tex but they are similar to other commands found here
\AA and nowhere else, being alternate input forms for characters.
365 \def \aa {\r a}
366 \def \AA {\r A}

\endgraf
\endline 367 \let\endgraf=\par
368 \let\endline=\cr

\space
369 \def\space{ }

\empty This probably ought to go altogether, but let it to the LATEX version to save space.
370 \let\empty\@empty

\null
371 \def\null{\hbox{}}

\bgroup
\egroup 372 \let\bgroup={
373 \let\egroup=}

\obeylines In \obeylines, we say \let^^M=\par instead of \def^^M{\par} since this allows,
\obeyspaces for example, \let\par=\cr \obeylines \halign{...
374 {\catcode'\^^M=\active % these lines must end with %
375 \gdef\obeylines{\catcode'\^^M\active \let^^M\par}%
376 \global\let^^M\par} % this is in case ^^M appears in a \write
377 \def\obeyspaces{\catcode'\ \active}
378 {\obeyspaces\global\let \=\space}

\loop We use Kabelschacht's method of doing loops, see TUB 8#2 (1987). (unless that
\iterate breaks something :-). It turned out to need an extra \relax: see pr/642 (\loop
\repeat could do one iteration too much in certain cases).
379 \long\def \loop #1\repeat{%
380 \def\iterate{#1\relax % Extra \relax
381 \expandafter\iterate\fi
382 }%
383 \iterate
384 \let\iterate\relax
385 }

This setting of \repeat is needed to make \loop...\if...\repeat skippable
within another \if....
386 \let\repeat=\fi

LATEX defines \smallskip, etc. in lt-space.dtx.

\nointerlineskip
\offinterlineskip 387 \def\nointerlineskip{\prevdepth-\@m\p@}
388 \def\offinterlineskip{\baselineskip-\@m\p@
389 \lineskip\z@ \lineskiplimit\maxdimen}

```

```

\vglue
\hglue 390 \def\vglue{\afterassignment\vgl@\skip@=}
391 \def\vgl@{\par \dimen@\prevdepth \hrule \@height\z@
392 \nobreak\vskip\skip@ \prevdepth\dimen@}
393 \def\hglue{\afterassignment\hgl@\skip@=}
394 \def\hgl@{\leavevmode \count@\spacefactor \vrule \@width\z@
395 \nobreak\hskip\skip@ \spacefactor\count@}

LATEX defines ~ in ltdefns.dtx.

\slash This generates a / acting a bit like - but still allows hyphenation in the word part
preceding it (but not after).
396 \def\slash{/\penalty\exhyphenpenalty}

\break
\nobreak 397 \def\break{\penalty-\@M}
\allowbreak 398 \def\nobreak{\penalty \@M}
399 \def\allowbreak{\penalty \z@}

\filbreak
\goodbreak 400 \def\filbreak{\par\vfil\penalty-200\vfilneg}
401 \def\goodbreak{\par\penalty-500 }

\eject Define \eject as in plain TEX but define \supereject only in the compatibility
file.
402 \def\eject{\par\break}

\removelastskip
403 \def\removelastskip{\ifdim\lastskip=\z@\else\vskip-\lastskip\fi}

\smallbreak
\medbreak 404 \def\smallbreak{\par\ifdim\lastskip<\smallskipamount
\bigbreak 405 \removelastskip\penalty-50\smallskip\fi}
406 \def\medbreak{\par\ifdim\lastskip<\medskipamount
407 \removelastskip\penalty-100\medskip\fi}
408 \def\bigbreak{\par\ifdim\lastskip<\bigskipamount
409 \removelastskip\penalty-200\bigskip\fi}

\m@th
410 \def\m@th{\mathsurround\z@}

\underbar Due to LATEX's redefinition of \underline plain TEX's \underbar can be done in
a simpler fashion (but do we need it at all?).
411 \def\underbar#1{\underline{\sbox\tw@{#1}\dp\tw@\z@\box\tw@}}

\strutbox LATEX sets \strutbox in \set@fontsize.
\strut 412 \newbox\strutbox
413 \def\strut{\relax\ifmmode\copy\strutbox\else\unhcopy\strutbox\fi}

\hidewidth For alignment entries that can stick out.
414 \def\hidewidth{\hskip\hideskip}

```

`\narrower`

```
415 \def\narrower{%
416   \advance\leftskip\parindent
417   \advance\rightskip\parindent}
```

L<sup>A</sup>T<sub>E</sub>X defines `\ae` and similar commands elsewhere.

```
418 \chardef\%='\'%
419 \chardef\&='&
420 \chardef\#='#&
```

Most text commands are actually encoding specific and therefore defined later, so commented out or removed from this file.

`\leavevmode` begins a paragraph, if necessary

```
421 \def\leavevmode{\unhbox\voidb@x}
```

`\mathhexbox`

```
422 \def\mathhexbox#1#2#3{\mbox{$\m@th \mathchar"#1#2#3$}}
```

`\ialign`

```
423 \def\ialign{\everycr{}\tabskip\z@skip\halign} % initialized \halign
```

`\oalign`

`\o@lign`

`\ooalign`

```
424 \def\oalign#1{\leavevmode\top{\baselineskip\z@skip \lineskip.25ex%
425   \ialign{##\crrc#1\crrc}}}%
426 \def\o@lign{\lineskiplimit\z@ \oalign}
427 \def\ooalign{\lineskiplimit-\maxdimen \oalign}
```

`\sh@ft`

The definition of this macro in `plain.tex` was improved in about 1997; but as a result its usage was changed and its new definition is not appropriate for L<sup>A</sup>T<sub>E</sub>X.

Since the version given here has been in use by L<sup>A</sup>T<sub>E</sub>X for many years it does not seem prudent to remove it now. As far as we can tell it has only been used to define `\b` and `\d` but this cannot be certain.

```
428 \def\sh@ft#1{\dimen@.00#1ex\multiply\dimen@\fontdimen1\font
429   \kern-.0156\dimen@} % compensate for slant in lowered accents
```

`\ltx@sh@ft`

This is the L<sup>A</sup>T<sub>E</sub>X version of the second incarnation of the plain macro `\sh@ft`, which takes a dimension as its argument. It shifts a pseudo-accent horizontally by an amount proportional to the product of its argument and the slant-per-point (`fontdimen 1`).

```
430 \def\ltx@sh@ft #1{%
431   \dimen@ #1%
432   \kern \strip@pt
433   \fontdimen1\font \dimen@
434 } % kern by #1 times the current slant
```

L<sup>A</sup>T<sub>E</sub>X change: the text commands such as `\d`, `\b`, `\c`, `\copyright`, `\TeX` are now defined elsewhere.

L<sup>A</sup>T<sub>E</sub>X change: Make `\t` work in a moving argument. Now defined elsewhere.

```

\hrulefill  LATEX change: \kern\z@ added to end of \hrulefill and \dotfill to make them
\dotfill    work in ‘tabular’ and ‘array’ environments. (Change made 24 July 1987). LATEX
            change: \leavevmode added at beginning of \dotfill and \hrulefill so that
            they work as expected in vertical mode.
435 \def\hrulefill{\leavevmode\leaders\hrule\hfill\kern\z@}

The box in \dotfill originally contained (in plain.tex):
\mkern 1.5mu .\mkern 1.5mu;
the width of .44em differs from this by .04pt which is probably an acceptable
difference within leaders.
436 \def\dotfill{%
437   \leavevmode
438   \cleaders \hb@xt@ .44em{\hss.\hss}\hfill
439   \kern\z@}

INITEX sets \sfcode x=1000 for all x, except that \sfcode‘X’=999 for upper-
case letters. The following changes are needed:
440 \sfcode‘\’=0 \sfcode‘\’=0 \sfcode‘\’=0

The \nonfrenchspacing macro will make further changes to \sfcode values.
Definitions related to output
\magnification doesn’t work in LATEX.

\def\magnification{\afterassignment\m@g\count@}
\def\m@g{\mag\count@
\hspace6.5truein\vspace8.9truein\dimen\footins8truein}

\showoverfull The following commands are used in debugging:
441 \def\showoverfull{\tracingonline\@ne}

\showoutput
\loggingoutput 442 \gdef\loggingoutput{\tracingoutput\@ne
443   \showboxbreadth\maxdimen\showboxdepth\maxdimen\errorstopmode}
444 \gdef\showoutput{\loggingoutput\showoverfull}
445 /2kernel)

\tracingall
\loggingall 446 (latexrelease)\IncludeInRelease{2015/01/01}{\loggingall}{etex tracing}%
447 (*2kernel | latexrelease)
448 \ifx\tracingscantokens\@undefined
449 \gdef\loggingall{%
450   \tracingstats\tw@
451   \tracingpages\@ne
452   \tracinglostchars\@ne
453   \tracingparagraphs\@ne
454   \errorcontextlines\maxdimen
455   \loggingoutput
456   \tracingmacros\tw@
457   \tracingcommands\tw@
458   \tracingrestores\@ne
459   }%
460 \else
461 \gdef\loggingall{%
462   \tracingstats\tw@

```



```

463 \tracingpages\@ne
464 \tracinglostchars\tw@
465 \tracingparagraphs\@ne
466 \tracinggroups\@ne
467 \tracingifs\@ne
468 \tracingscantokens\@ne
469 \tracingnesting\@ne
470 \errorcontextlines\maxdimen
471 \loggingoutput
472 \tracingmacros\tw@
473 \tracingcommands\thr@@
474 \tracingrestores\@ne
475 \tracingassigns\@ne
476 }%
477 \fi
478 \gdef\tracingall{\showoverfull\loggingall}
479 </2ekernel | latexrelease>
480 (latexrelease)\EndIncludeInRelease
481 (latexrelease)\IncludeInRelease{0000/00/00}{\loggingall}{etex tracing}%
482 (latexrelease)\gdef\loggingall{\tracingcommands\tw@\tracingstats\tw@
483 (latexrelease) \tracingpages\@ne\tracinglostchars\@ne
484 (latexrelease) \tracingmacros\tw@\tracingparagraphs\@ne\tracingrestores\@ne
485 (latexrelease) \errorcontextlines\maxdimen\loggingoutput}
486 (latexrelease) \gdef\tracingall{\loggingall\showoverfull}
487 (latexrelease)\EndIncludeInRelease

\tracingnone
\hideoutput 488 (latexrelease)\IncludeInRelease{2015/01/01}{\tracingnone}%
489 (latexrelease) {turn off etex tracing}%
490 (*2ekernel | latexrelease>
491 \ifx\tracingscantokens\@undefined
492 \def\tracingnone{%
493 \tracingonline\z@
494 \tracingcommands\z@
495 \showboxdepth\m@ne
496 \showboxbreadth\m@ne
497 \tracingoutput\z@
498 \errorcontextlines\m@ne
499 \tracingrestores\z@
500 \tracingparagraphs\z@
501 \tracingmacros\z@
502 \tracinglostchars\@ne
503 \tracingpages\z@
504 \tracingstats\z@
505 }%
506 \else
507 \def\tracingnone{%
508 \tracingassigns\z@
509 \tracingrestores\z@
510 \tracingonline\z@
511 \tracingcommands\z@
512 \showboxdepth\m@ne
513 \showboxbreadth\m@ne
514 \tracingoutput\z@

```

```

515 \errorcontextlines\m@ne
516 \tracingnesting\z@
517 \tracingscantokens\z@
518 \tracingifs\z@
519 \tracinggroups\z@
520 \tracingparagraphs\z@
521 \tracingmacros\z@
522 \tracinglostchars\@ne
523 \tracingpages\z@
524 \tracingstats\z@
525 }%
526 \fi

527 \def\hideoutput{%
528   \tracingoutput\z@
529   \showboxbreadth\m@ne
530   \showboxdepth\m@ne
531   \tracingonline\m@ne
532 }%

533 </2ekernel | latexrelease>
534 <latexrelease>\EndIncludeInRelease
535 <latexrelease>\IncludeInRelease{0000/00/00}{\tracingnone}%
536 <latexrelease>                                     {turn off etex tracing}%
537 <latexrelease>\let\tracingnone\@undefined
538 <latexrelease>\let\hideoutput\@undefined
539 <latexrelease>\EndIncludeInRelease

    LATEX change: \showhyphens Defined later.
    Punctuation affects the spacing.

540 <*2ekernel>
541 \nonfrenchspacing
542 </2ekernel>

```

# File c

## ltvers.dtx

### 10 Version Identification

First we identify the date and version number of this release of L<sup>A</sup>T<sub>E</sub>X, and set `\everyjob` so that it is printed at the start of every L<sup>A</sup>T<sub>E</sub>X run.

`\fmtname` A `\patch@level` of 0 or higher denotes an official public release. A negative value indicates a candidate release that is not distributed.

`\fmtversion` If we put code updates into the kernel that are supposed to go into the next release we set the `\patch@level` to -1 and the `\fmtversion` / `\latexreleaseversion` to the date of the next release (guessed, the real value is not so important and will get corrected when we make the release official).

`\patch@level` If the `\patch@level` is already at -1 we do nothing here and use the `\fmtversion` date for any new `\IncludeInRelease` line when we add further code.

Finally, if we do make a public release we either just set the `\patch@level` to zero (if our initial guess was good) or we also change the date and then have to additionally change to that date on all the `\IncludeInRelease` statements that used the “guessed” date.

```

1 (*2ekernel)
2 \def\fmtname{LaTeX2e}
3 \edef\fmtversion
4 (/2ekernel)
5 (latexrelease)\edef\latexreleaseversion
6 (*2ekernel| latexrelease)
7 {2020-02-01}
8 (/2ekernel| latexrelease)
9 (*2ekernel)
10 \def\patch@level{-2}

```

`\development@branch@name` For more fine grain control there is the possibility to name the current development branch. This is only used when the `\patch@level` is negative (i.e., a pre-release format) and is intended to help help us internally when we locally install a format out of some development branch.

```

11 \edef\development@branch@name{development \the\year-\the\month-\the\day}

```

Check that the format being made is not too old. The error message complains about ‘more than 5 years’ but in fact the error is not triggered until 65 months.

This code is currently not activated as we don’t know if we already got to the last official 2e version (due to staff shortage or due to a successor (think positive:-)).

```

12 \iffalse
13 \def\reserved@a#1/#2/#3\@nil{%
14   \count@\year
15   \advance\count@-#1\relax
16   \multiply\count@ by 12\relax
17   \advance\count@\month
18   \advance\count@-#2\relax}
19 \expandafter\reserved@a\fmtversion\@nil

```



```

68 \latexrelease\newif\if@includeinrelease
69 \latexrelease\@includeinreleasefalse

70 \def\IncludeInRelease#1{%
71   \if@includeinrelease
72     \PackageError{latexrelease}{mis-matched IncludeInRelease}%
73       {There is an \string\EndIncludeRelease\space missing}%
74     \@includeinreleasefalse
75   \fi
76   \kernel@ifnextchar[%
77     {\@IncludeInRelease{#1}}
78     {\@IncludeInRelease{#1}[#1]}

    If a specific date has not been specified in latexrelease use ‘#1’.

79 \def\@IncludeInRelease#1[#2]{\@IncludeInRelease@se{#2}}

80 \def\@IncludeInRelease@se#1#2#3{%
81   \toks@{[#1] #3}%
82   \expandafter\ifx\csname\string#2+\@currname+IIR\endcsname\relax
83     \ifnum\expandafter\@parse@version#1//00\@nil
84       >\expandafter\@parse@version\fmtversion//00\@nil
85       \GenericInfo{}{Skipping: \the\toks@}%
86       \expandafter\expandafter\expandafter\@gobble@IncludeInRelease
87     \else
88       \GenericInfo{}{Applying: \the\toks@}%
89       \@includeinreleasetrue
90       \expandafter\let\csname\string#2+\@currname+IIR\endcsname\@empty
91     \fi
92   \else
93     \GenericInfo{}{Already applied: \the\toks@}%
94     \expandafter\@gobble@IncludeInRelease
95   \fi
96 }

97 \def\EndIncludeInRelease{%
98   \if@includeinrelease
99     \@includeinreleasefalse
100 \else
101   \PackageError{latexrelease}{mis-matched EndIncludeInRelease}{}%
102 \fi}

103 \long\def\@gobble@IncludeInRelease#1\EndIncludeInRelease{%
104   \@includeinreleasefalse
105   \@check@IncludeInRelease#1\IncludeInRelease\@check@IncludeInRelease
106   \@end@check@IncludeInRelease}

107 \long\def\@check@IncludeInRelease#1\IncludeInRelease
108                                     #2#3\@end@check@IncludeInRelease{%
109   \ifx\@check@IncludeInRelease#2\else
110     \PackageError{latexrelease}{skipped IncludeInRelease for tag \string#2}{}%
111   \fi}

112 \</2ekernel | latexrelease>

```

# File d

## ltxdefns.dtx

### 11 Definitions

This section contains commands used in defining other macros.

```
1 (*2ekernel)
```

#### 11.1 Initex initialisations

`\two@digits` Prefix a number less than 10 with ‘0’.

```
2 \def\two@digits#1{\ifnum#1<10 0\fi\number#1}
```

`\typeout` Display something on the terminal.

```
3 \def\typeout#1{\begingroup\set@display@protect
4   \immediate\write\@unused{#1}\endgroup}
```

`\newlinechar` A char to be used as new-line in output to files.

```
5 \newlinechar‘^^J
```

#### 11.2 Saved versions of TeX primitives

The TeX primitive `\foo` is saved as `\@foo`. The following primitives are handled in this way:

`\@@par`

```
6 \let\@@par=\par
7 %\let\@@input=\input      %%% moved earlier
8 %\let\@@end=\end          %%%
```

`\@@hyph` Save original primitive definition.

```
9 \let\@@hyph=\-
```

`\@@italiccorr` Save the original italic correction.

```
10 \let\@@italiccorr=\/
```

`\@height` The following definitions save token space. E.g., using `\@height` instead of `height`  
`\@depth` saves 5 tokens at the cost in time of one macro expansion.

```
11 \def\@height{height} \def\@depth{depth} \def\@width{width}
12 \def\@minus{minus}
13 \def\@plus{plus}
```

`\hb@xt@` The next one is another 100 tokens worth.

```
14 \def\hb@xt@{\hbox to}
15 \message{hacks,}
```

## 11.3 Command definitions

This section defines the following commands:

<code>\@namedef</code>	<code>{\NAME}</code>	
		Expands to <code>\def\{NAME}</code> , except name can contain any characters.
<code>\@nameuse</code>	<code>{\NAME}</code>	
		Expands to <code>\{NAME}</code> .
<code>\@ifnextchar</code>	<code>X{\YES}{\NO}</code>	
		Expands to <code>\YES</code> if next character is an ‘X’, and to <code>\NO</code> otherwise. (Uses <code>\reserved@a–\reserved@c.</code> ) NOTE: GOBBLES ANY SPACE FOLLOWING IT.
<code>\@ifstar</code>	<code>{\YES}{\NO}</code>	
		Gobbles following spaces and then tests if next the character is a ‘*’. If it is, then it gobbles the ‘*’ and expands to <code>\YES</code> , otherwise it expands to <code>\NO</code> .
<code>\@dblarg</code>	<code>{\CMD}{\ARG}</code>	
		Expands to <code>\{\CMD\}[\ARG]{\ARG}</code> . Use <code>\@dblarg\CS</code> when <code>\CS</code> takes arguments <code>[ARG1]{ARG2}</code> , where default is <code>ARG1 = ARG2</code> .
<code>\@ifundefined</code>	<code>{\NAME}{\YES}{\NO}</code>	
		: If <code>\NAME</code> is undefined then it executes <code>\YES</code> , otherwise it executes <code>\NO</code> . More precisely, true if <code>\NAME</code> either undefined or <code>= \relax</code> .
<code>\@ifdefinable</code>	<code>\NAME{\YES}</code>	Executes <code>\YES</code> if the user is allowed to define <code>\NAME</code> , otherwise it gives an error. The user can define <code>\NAME</code> if <code>\@ifundefined{NAME}</code> is true, ‘NAME’ $\neq$ ‘relax’ and the first three letters of ‘NAME’ are not ‘end’, and if <code>\endNAME</code> is not defined.
<code>\newcommand</code>	<code>*{\FOO}[i]{\TEXT}</code>	
		User command to define <code>\FOO</code> to be a macro with <i>i</i> arguments ( <i>i</i> = 0 if missing) having the definition <code>\TEXT</code> . Produces an error if <code>\FOO</code> already defined.
		Normally the command is defined to be <code>\long</code> (ie it may take multiple paragraphs in its argument). In the star-form, the command is not defined as <code>\long</code> and a blank line in any argument to the command would generate an error.
<code>\renewcommand</code>	<code>*{\FOO}[i]{\TEXT}</code>	
		Same as <code>\newcommand</code> , except it checks if <code>\FOO</code> already defined.
<code>\newenvironment</code>	<code>*{\FOO}[i]{\DEF1}{\DEF2}</code>	
		equivalent to: <code>\newcommand{\FOO}[i]{\DEF1} \def{\endFOO}{\DEF2}</code> (or the appropriate star forms).
<code>\renewenvironment</code>		Obvious companion to <code>\newenvironment</code> .
<code>\@cons</code>		: See description of <code>\output</code> routine.
<code>\@car</code>	<code>\@car T1 T2 ... Tn\@nil == T1</code>	(unexpanded)
<code>\@cdr</code>	<code>\@cdr T1 T2 ... Tn\@nil == T2 ... Tn</code>	(unexpanded)
<code>\typeout</code>	<code>{\message}</code>	
		Produces a warning message on the terminal.
<code>\typein</code>	<code>{\message}</code>	
		Types message, asks the user to type in a command, then executes it
<code>\typein</code>	<code>[\CS]{\MSG}</code>	
		Same as above, except defines <code>\CS</code> to be the input instead of executing it.
<code>\typein</code>		
	<code>16 \def\typein{%</code>	

```

17 \let\@typein\relax
18 \@testopt\@xtypein\@typein}

19 \ifx\directlua\@undefined
20 \def\@xtypein[#1]#2{%
21 \typeout{#2}%
22 \advance\endlinechar\@M
23 \read\@inputcheck to#1%
24 \advance\endlinechar-\@M
25 \@typein}%
26 \else
27 \def\@xtypein[#1]#2{%
28 \typeout{#2}%
29 \begingroup \endlinechar\m@ne
30 \read\@inputcheck to#1%
31 \expandafter\endgroup
32 \expandafter\def\expandafter#1\expandafter{#1}%
33 \@typein}%
34 \fi

\@namedef
35 \def\@namedef#1{\expandafter\def\csname #1\endcsname}

\@nameuse
36 \def\@nameuse#1{\csname #1\endcsname}

\@cons
37 \def\@cons#1#2{\begingroup\let\@elt\relax\xdef#1{#1\@elt #2}\endgroup}

\@car
\@cdr
38 \def\@car#1#2\@nil{#1}
39 \def\@cdr#1#2\@nil{#2}

\@carcube \@carcube T1 ... Tn\@nil = T1 T2 T3 , n > 3
40 \def\@carcube#1#2#3#4\@nil{#1#2#3}

\@onlypreamble This macro adds its argument to the list of commands stored in \@preamblecmds
\@preamblecmds to be disabled after \begin{document}. These commands are redefined to gener-
ate \@notprerr at this point.
41 \def\@preamblecmds{}
42 \def\@onlypreamble#1{%
43 \expandafter\gdef\expandafter\@preamblecmds\expandafter{%
44 \@preamblecmds\do#1}}
45 \@onlypreamble\@onlypreamble
46 \@onlypreamble\@preamblecmds

\@star@or@long Look ahead for a *. If present reset \l@ngrel@x so that the next definition, #1,
will be non-long.
47 \def\@star@or@long#1{%
48 \@ifstar
49 {\let\l@ngrel@x\relax#1}%
50 {\let\l@ngrel@x\long#1}}

```



`\l@ngrel@x` This is either `\relax` or `\long` depending on whether the `*`-form of a definition command is being executed.

```
51 \let\l@ngrel@x\relax
```

`\newcommand` User level `\newcommand`.

```
52 \def\newcommand{\@star@or@long\new@command}
```

`\new@command`

```
53 \def\new@command#1{%
54   \@testopt{\@newcommand#1}0}
```

`\@newcommand` Handling arguments for `\newcommand`.

```
\@argdef 55 \def\@newcommand#1[#2]{%
\@xargdef 56   \kernel@ifnextchar [{\@xargdef#1[#2]}%
57               {\@argdef#1[#2]}}
```

Define `#1` if it is definable.

Both here and in `\@xargdef` the replacement text is absorbed as an argument because if we are not allowed to make the definition we have to get rid of it completely.

```
58 \long\def\@argdef#1[#2]#3{%
59   \@ifdefinable #1{\@yargdef#1\@ne{#2}{#3}}}
```

Handle the second optional argument.

```
60 \long\def\@xargdef#1[#2] [#3]#4{%
61   \@ifdefinable#1{%
```

Define the actual command to be:

```
\def\foo{\@protected@testopt\foo\foo{default}}
```

where `\foo` is a csname generated from applying `\csname` and `\string` to `\foo`, ie the actual name contains a backslash and therefore can't clash easily with existing command names. "Default" is the contents of the second optional argument of `(re)newcommand`.

```
62   \expandafter\def\expandafter#1\expandafter{%
63     \expandafter
64     \@protected@testopt
65     \expandafter
66     #1%
67     \csname\string#1\endcsname
68     {#3}}%
```

Now we define the internal macro ie `\foo` which is supposed to pick up all arguments (optional and mandatory).

```
69   \expandafter\@yargdef
70   \csname\string#1\endcsname
71   \tw@
72   {#2}%
73   {#4}}}
```

`\@testopt` This macro encapsulates the most common call to `\@ifnextchar`, saving several tokens each time it is used in the definition of a command with an optional argument. `#1` The code to execute in the case that there is a `[` need not be a single token but can be any sequence of commands that 'expects' to be followed by `[`.

If this command were only used in `\newcommand` definitions then `#1` would be a single token and the braces could be omitted from `{#1}` in the definition below, saving a bit of memory.

```
74 \long\def\@testopt#1#2{%
75   \kernel@ifnextchar[#{#1}{#1[#{#2}]]}
```

`\@protected@testopt` Robust version of `\@testopt`. The extra argument (`#1`) must be a single token. If protection is needed the call expands to `\protect` applied to this token, and the 2nd and 3rd arguments are discarded (by `\@x@protect`). Otherwise `\@testopt` is called on the 2nd and 3rd arguments.

This method of making commands robust avoids the need for using up two csnames per command, the price is the extra expansion time for the `\ifx` test.

```
76 \def\@protected@testopt#1{%
77   \ifx\protect\@typeset@protect
78     \expandafter\@testopt
79   \else
80     \@x@protect#1%
81   \fi}
```

`\@yargdef` These generate a primitive argument specification, from a L<sup>A</sup>T<sub>E</sub>X [*<digit>*] form; `\@yargd@f` in fact *<digit>* can be anything such that `\number <digit>` is single digit.

Reorganised slightly so that `\renewcommand{\reserved@a}[1]{foo}` works. I am not sure this is worth it, as a following `\newcommand` would over-write the definition of `\reserved@a`.

Recall that L<sup>A</sup>T<sub>E</sub>X 2.09 goes into an infinite loop with `\renewcommand[1]{\@tempa}{foo}` (DPC 6 October 93).

Reorganised again (DPC 1999). Rather than make a loop to construct the argument spec by counting, just extract the required argument spec by using a delimited argument (delimited by the digit). This is faster and uses less tokens. The coding is slightly odd to preserve the old interface (using `#2 = \tw@` as the flag to surround the first argument with []). But the new method did not allow for the number of arguments `#3` not being given as an explicit digit; hence (further expansion of this argument and use of) `\number` was added later in 1999.

It is not clear why these are still `\long`.

```
82 \long \def \@yargdef #1#2#3{%
83   \ifx#2\tw@
84     \def\reserved@b##11{####1}}%
85   \else
86     \let\reserved@b\@gobble
87   \fi
88   \expandafter
89   \@yargd@f \expandafter{\number #3}#1%
90 }

91 \long \def \@yargd@f#1#2{%
92   \def \reserved@a ##1#1##2##{%
93     \expandafter\def\expandafter#2\reserved@b ##1#1%
94   }%
95   \l@ngrel@x \reserved@a 0##1##2##3##4##5##6##7##8##9####1%
96 }
```

```

\@reargdef
    97 \long\def\@reargdef#1[#2]{%
    98   \@yargdef#1\@ne{#2}}

\renewcommand Check the command name is already used. If not give an error message. Then
temporarily disable \@ifdefinable then call \newcommand. (Previous version
\let#1=\relax but this does not work too well if #1 is \@tempa-e.)
    99 \def\renewcommand{\@star@or@long\renew@command}

\renew@command
    100 \def\renew@command#1{%
    101   \begingroup \escapechar\m@ne\xdef\@gtempa{\string#1}}\endgroup
    102   \expandafter\@ifundefined\@gtempa
    103     {\@latex@error{Command \string#1 undefined}\@ehc}%
    104     \relax
    105   \let\@ifdefinable\@rc@ifdefinable
    106   \new@command#1}

\@ifdefinable Test is user is allowed to define a command.
\@@ifdefinable
\@rc@ifdefinable
    107 \long\def\@ifdefinable #1#2{%
    108   \edef\reserved@a{\expandafter\@gobble\string #1}%
    109   \ifundefined\reserved@a
    110     {\edef\reserved@b{\expandafter\@carcube \reserved@a xxx\@nil}%
    111      \ifx \reserved@b\@qend \notdefinable\else
    112        \ifx \reserved@a\@qrelax \notdefinable\else
    113          #2%
    114        \fi
    115      \fi}%
    116   \notdefinable}
Saved definition of \@ifdefinable.
    117 \let\@@ifdefinable\@ifdefinable
Version of \@ifdefinable for use with \renewcommand. Does not do the check
this time, but restores the normal definition.
    118 \long\def\@rc@ifdefinable#1#2{%
    119   \let\@ifdefinable\@@ifdefinable
    120   #2}

\newenvironment Define a new user environment. #1 is the environment name. #2# Grabs all the
tokens up to the first {. These will be any optional arguments. They are not
parsed at this point, but are just passed to \@newenv which will eventually call
\newcommand. Any optional arguments will then be parsed by \newcommand as it
defines the command that executes the ‘begin code’ of the environment.
This #2# trick removed with version 1.2i as it fails if a { occurs in the optional
argument. Now use \@ifnextchar directly.
    121 \def\newenvironment{\@star@or@long\new@environment}

\new@environment
    122 \def\new@environment#1{%
    123   \@testopt{\@newenva#1}0}

```

```

\@newenva
124 \def\@newenva#1[#2]{%
125   \kernel@ifnextchar [{\@newenvb#1[#2]}{\@newenv{#1}{[#2]}}}]

\@newenvb
126 \def\@newenvb#1[#2][#3]{\@newenv{#1}{[#2][#3]}}

\renewenvironment Redefine an environment. For \renewenvironment disable \@ifdefinable and
then call \newenvironment. It is OK to \let the argument to \relax here as
there should not be a @temp... environment.
127 \def\renewenvironment{\@star@or@long\renew@environment}

\renew@environment
128 \def\renew@environment#1{%
129   \@ifundefined{#1}%
130     {\@latex@error{Environment #1 undefined}\@ehc
131     }\relax
132   \expandafter\let\csname#1\endcsname\relax
133   \expandafter\let\csname end#1\endcsname\relax
134   \new@environment{#1}}

\@newenv The internal version of \newenvironment.
Call \newcommand to define the begin-code for the environment. \def is used
for the end-code as it does not take arguments. (but may contain \pars)
Make sure that an attempt to define a ‘graf’ or ‘group’ environment fails.
135 \long\def\@newenv#1#2#3#4{%
136   \@ifundefined{#1}%
137     {\expandafter\let\csname#1\expandafter\endcsname
138       \csname end#1\endcsname}%
139     \relax
140   \expandafter\new@command
141     \csname #1\endcsname#2{#3}%
142     \l@ngrel@x\expandafter\def\csname end#1\endcsname{#4}}

\newif And here’s a different sort of allocation: For example, \newif\iffoo creates
\footrue, \foofalse to go with \iffoo.
143 \def\newif#1{%
144   \count@\escapechar \escapechar\m@ne
145   \let#1\iffalse
146   \@if#1\iftrue
147   \@if#1\iffalse
148   \escapechar\count@}

\@if
149 \def\@if#1#2{%
150   \expandafter\def\csname\expandafter\@gobbletwo\string#1%
151     \expandafter\@gobbletwo\string#2\endcsname
152     {\let#1#2}}

\providecommand \providecommand takes the same arguments as \newcommand, but discards them
if #1 is already defined, Otherwise it just acts like \newcommand. This imple-
mentation currently leaves any discarded definition in \reserved@a (and possibly

```

`\reserved@a`) this wastes a bit of space, but it will be reclaimed as soon as these scratch macros are redefined.

```
153 \def\providecommand{\@star@or@long\providecommand}
```

`\providecommand`

```
154 \def\providecommand#1{%
155   \begingroup
156   \escapechar\m@ne\xdef\@gtempa{\string#1}%
157   \endgroup
158   \expandafter\@ifundefined\@gtempa
159   {\def\reserved@a{\newcommand#1}}%
160   {\def\reserved@a{\renewcommand\reserved@a}}%
161   \reserved@a}%
```

`\CheckCommand` `\CheckCommand` takes the same arguments as `\newcommand`. If the command already exists, with the same definition, then nothing happens, otherwise a warning is issued. Useful for checking the current state before a macro package starts redefining things. Currently two macros are considered to have the same definition if they are the same except for different default arguments. That is, if the old definition was: `\newcommand\xxx[2][a]{(#1)(#2)}` then `\CheckCommand\xxx[2][b]{(#1)(#2)}` would *not* generate a warning, but, for instance `\CheckCommand\xxx[2]{(#1)(#2)}` would.

```
162 \def\CheckCommand{\@star@or@long\checkcommand}
```

`\CheckCommand` is only available in the preamble part of the document.

```
163 \@onlypreamble\CheckCommand
```

`\checkcommand`

```
164 \def\checkcommand#1#2#{\@check@c#1{#2}}
165 \@onlypreamble\checkcommand
```

`\@check@c` `\CheckCommand` itself just grabs all the arguments we need, without actually looking for [ optional argument forms. Now define `\reserved@a`. If `\reserved@a` is then defined, compare it with the “`\#1`” otherwise compare `\reserved@a` with `\#1`.

```
166 \long\def\@check@c#1#2#3{%
167   \expandafter\let\csname\string\reserved@a\endcsname\relax
168   \renewcommand\reserved@a#2{#3}%
169   \@ifundefined{\string\reserved@a}%
170   {\@check@eq#1\reserved@a}%
171   {\expandafter\@check@eq
172     \csname\string#1\expandafter\endcsname
173     \csname\string\reserved@a\endcsname}}
174 \@onlypreamble\@check@c
```

`\@check@eq` Complain if `\#1` and `\#2` are not `\ifx` equal.

```
175 \def\@check@eq#1#2{%
176   \ifx#1#2\else
177     \latex@warning@no@line
178       {Command \noexpand#1 has
179         changed.\MessageBreak
180         Check if current package is valid}%
181   \fi}
182 \@onlypreamble\@check@eq
```

```

\@gobble The \@gobble macro is used to get rid of its argument.
\@gobbletwo 183 \long\def \@gobble #1{}
\@gobblefour 184 \long\def \@gobbletwo #1#2{}
185 \long\def \@gobblefour #1#2#3#4{}

\@firstofone Some argument-grabbers.
\@firstoftwo 186 \long\def \@firstofone#1{#1}
\@secondoftwo 187 \long\def \@firstoftwo#1#2{#1}
188 \long\def \@secondoftwo#1#2{#2}

\@iden \@iden is another name for \@firstofone for compatibility reasons.
189 \let \@iden \@firstofone

\@thirdofthree Another grabber now used in the encoding specific section.
190 \long\def \@thirdofthree#1#2#3{#3}

\@expandtwoargs A macro to totally expand two arguments to another macro
191 \def \@expandtwoargs#1#2#3{%
192 \edef \reserved@a{\noexpand#1{#2}{#3}}\reserved@a}

\@backslashchar A category code 12 backslash.
193 \edef \@backslashchar{\expandafter \@gobble \string \}

```

## 11.4 Robust commands and protect

Fragile and robust commands are one of the thornier issues in L<sup>A</sup>T<sub>E</sub>X's commands. Whilst typesetting documents, L<sup>A</sup>T<sub>E</sub>X makes use of many of T<sub>E</sub>X's features, such as arithmetic, defining macros, and setting variables. However, there are (at least) three different occasions when these commands are not safe. These are called 'moving arguments' by L<sup>A</sup>T<sub>E</sub>X, and consist of:

- writing information to a file, such as indexes or tables of contents.
- writing information to the screen.
- inside an `\edef`, `\message`, `\mark`, or other command which evaluates its argument fully.

The method L<sup>A</sup>T<sub>E</sub>X uses for making fragile commands robust is to precede them with `\protect`. This can have one of five possible values:

- `\relax`, for normal typesetting. So `\protect\foo` will execute `\foo`.
- `\string`, for writing to the screen. So `\protect\foo` will write `\foo`.
- `\noexpand`, for writing to a file. So `\protect\foo` will write `\foo` followed by a space.
- `\@unexpandable@protect`, for writing a moving argument to a file. So `\protect\foo` will write `\protect\foo` followed by a space. This value is also used inside `\edefs`, `\marks` and other commands which evaluate their arguments fully. More precisely, whenever the content of an `\edef` or `\xdef`

etc. can contain arbitrary user input not under the direct control of the programmer, one should use `\protected@edef` instead of `\edef`, etc., so that `\protect` has a suitable definition and the user input will not break if it contains fragile commands.

`\@unexpandable@protect`

```
194 \def\@unexpandable@protect{\noexpand\protect\noexpand}
```

`\DeclareRobustCommand` This is a package-writers command, which has the same syntax as `\newcommand`,  
`\declare@robustcommand` but which declares a protected command. It does this by having

`\DeclareRobustCommand\foo`  
define `\foo` to be `\protect\foo<space>`,  
and then use `\newcommand\foo<space>`.  
Since the internal command is `\foo<space>`, when it is written to an auxiliary file, it will appear as `\foo`.

We have to be a bit cleverer if we're defining a short command, such as `\_`, in order to make sure that the auxiliary file does not include a space after the command, since `\_ a` and `\_a` aren't the same. In this case we define `\_` to be:

```
\x@protect\_ \protect\_<space>
```

which expands to:

```
\ifx\protect\@typeset@protect\else
  \x@protect\_
\fi
\protect\_<space>
```

Then if `\protect` is `\@typeset@protect` (normally `\relax`) then we just perform `\_<space>`, and otherwise `\x@protect@` gobbles everything up and expands to `\protect\_`.

*Note:* setting `\protect` to any value other than `\relax` whilst in 'typesetting' mode will cause commands to go into an infinite loop! In particular, setting `\protect` to `\empty` will cause `\_` to loop forever. It will also break lots of other things, such as protected `\ifmmodes` inside `\haligns`. If you really really have to do such a thing, then please set `\@typeset@protect` to be `\empty` as well. (This is what the code for `\patterns` does, for example.)

More fun with `\expandafter` and `\csname`.

```
195 \def\DeclareRobustCommand{\@star@or@long\declare@robustcommand}
196 \def\declare@robustcommand#1{%
197   \ifx#1\@undefined\else\ifx#1\relax\else
198     \@latex@info{Redefining \string#1}%
199   \fi\fi
200   \edef\reserved@a{\string#1}%
201   \def\reserved@b{#1}%
202   \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
203   \edef#1{%
204     \ifx\reserved@a\reserved@b
205       \noexpand\x@protect
206       \noexpand#1%
207     \fi
```

```

208      \noexpand\protect
209      \expandafter\noexpand\csname
210      \expandafter\@gobble\string#1 \endcsname
211    }%
212    \let\@ifdefinable\@rc@ifdefinable
213    \expandafter\new@command\csname
214    \expandafter\@gobble\string#1 \endcsname
215  }

```

```

\@x@protect
\@x@protect 216 \def\@x@protect#1{%
217   \ifx\protect\@typeset@protect\else
218     \@x@protect#1%
219   \fi
220 }
221 \def\@x@protect#1\fi#2#3{%
222   \fi\protect#1%
223 }

```

\@typeset@protect We set \@typeset@protect to \relax rather than \@empty to make sure that the protection mechanism stops the look-ahead and expansion performed at the start of \halign cells.

```
224 \let\@typeset@protect\relax
```

\set@display@protect These macros set \protect appropriately for typesetting or displaying.

```

\set@typeset@protect 225 \def\set@display@protect{\let\protect\string}
226 \def\set@typeset@protect{\let\protect\@typeset@protect}

```

\protected@edef The commands \protected@edef and \protected@xdef perform ‘safe’ \edefs and \xdefs, saving and restoring \protect appropriately. For cases where restoring \protect doesn’t matter, there’s an ‘unsafe’ \unrestored@protected@xdef, useful if you know what you’re doing!

```

\protected@xdef
\unrestored@protected@xdef
\restore@protect
227 \def\protected@edef{%
228   \let\@@protect\protect
229   \let\protect\@unexpandable@protect
230   \afterassignment\restore@protect
231   \edef
232 }
233 \def\protected@xdef{%
234   \let\@@protect\protect
235   \let\protect\@unexpandable@protect
236   \afterassignment\restore@protect
237   \xdef
238 }
239 \def\unrestored@protected@xdef{%
240   \let\protect\@unexpandable@protect
241   \xdef
242 }
243 \def\restore@protect{\let\protect\@@protect}

```

\protect The normal meaning of \protect

```
244 \set@typeset@protect
```



`\MakeRobust` This macro makes an existing fragile macro robust, but only if it hasn't been robust in the past, i.e., it checks for the existence of the macro `\<name>` and if that exists it assumes that `\<name>` is already robust. In that case either undefine the inner macro first or use `\DeclareRobustCommand` to define it in a robust way directly. We could probably test the top-level definition to have the right kind of structure, but this is somewhat problematical as we then have to distinguish between `\long` macros and others and also take into account that sometimes the top-level is deliberately done manually (like with `\begin`).

The macro firstly checks if the control sequence in question exists at all.

```

245 </2ekernel>
246 <latexrelease>\IncludeInRelease{2019/10/01}{\MakeRobust}{\MakeRobust}%
247 <*2ekernel | latexrelease>
248 \def\MakeRobust#1{%
249   \@ifundefined{\expandafter\@gobble\string#1}{%
250     \@latex@error{The control sequence '\string#1' is undefined!%
251       \MessageBreak There is nothing here to make robust}%
252     \@eha
253   }%

Then we check if the macro is already robust. We do this by testing if the internal
name for a robust macro is defined, namely \foo. If it is already defined do
nothing, otherwise set \foo equal to \foo and redefine \foo so that it acts like
a macro defined with \DeclareRobustCommand.

254   {%
255     \@ifundefined{\expandafter\@gobble\string#1\space}%
256     {%
257       \global\expandafter\let\csname
258         \expandafter\@gobble\string#1\space\endcsname=#1%
259       \edef\reserved@a{\string#1}%
260       \def\reserved@b{#1}%
261       \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
262       \xdef#1{%
263         \ifx\reserved@a\reserved@b
264           \noexpand\x@protect\noexpand#1%
265         \fi
266         \noexpand\protect\expandafter\noexpand
267         \csname\expandafter\@gobble\string#1\space\endcsname}%
268     }%
269     {\@latex@info{The control sequence '\string#1' is already robust}}%
270   }%
271 }%
272 </2ekernel | latexrelease>
273 <latexrelease>\EndIncludeInRelease
274 <latexrelease>\IncludeInRelease{2015/01/01}{\MakeRobust}{\MakeRobust}%
275 <latexrelease>\def\MakeRobust#1{%
276 <latexrelease>  \@ifundefined{\expandafter\@gobble\string#1}{%
277 <latexrelease>    \@latex@error{The control sequence '\string#1' is undefined!%
278 <latexrelease>      \MessageBreak There is nothing here to make robust}%
279 <latexrelease>    \@eha
280 <latexrelease>  }%
281 <latexrelease>  {%
282 <latexrelease>    \@ifundefined{\expandafter\@gobble\string#1\space}%
283 <latexrelease>    {%

```

```

284 \latexrelease> \expandafter\let\csname
285 \latexrelease> \expandafter\@gobble\string#1\space\endcsname=#1%
286 \latexrelease> \edef\reserved@a{\string#1}%
287 \latexrelease> \def\reserved@b{#1}%
288 \latexrelease> \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
289 \latexrelease> \edef#1{%
290 \latexrelease> \ifx\reserved@a\reserved@b
291 \latexrelease> \noexpand\x@protect\noexpand#1%
292 \latexrelease> \fi
293 \latexrelease> \noexpand\protect\expandafter\noexpand
294 \latexrelease> \csname\expandafter\@gobble\string#1\space\endcsname}%
295 \latexrelease> }%
296 \latexrelease> {\@latex@info{The control sequence ‘\string#1’ is already robust}}%
297 \latexrelease> }%
298 \latexrelease>}%
299 \latexrelease>\EndIncludeInRelease
300 \latexrelease>\IncludeInRelease{0000/00/00}{\MakeRobust}{\MakeRobust}%
301 \latexrelease>\let\MakeRobust\@undefined
302 \latexrelease>\EndIncludeInRelease
303 \kernel)

```

`\kernel@make@fragile` The opposite of `\MakeRobust` except that it doesn't do many checks as it is internal to the kernel. Why does one want such a thing? Only for compatibility reasons if `latexrelease` requests a rollback of the kernel. For this reason we pretend that this command existed in all earlier versions of L<sup>A</sup>T<sub>E</sub>X i.e., we are not rolling it back since we need it precisely then. But we have to get it into the `latexrelease` file so that a roll forward is possible too.

```

304 \kernel)
305 \kernel | latexrelease>
306 \latexrelease> \IncludeInRelease{0000/00/00}%
307 \latexrelease> \kernel@make@fragile{Undo robustness}%
308 \def\kernel@make@fragile#1{%
309 \@ifundefined{\expandafter\@gobble\string#1\space}%

```

If not robust do nothing.

```

310 {}%

```

Otherwise copy `\foo` back to `\foo` and then undefine the payload command.

```

311 {}%
312 \global\expandafter\let\expandafter #1\csname
313 \expandafter\@gobble\string#1\space\endcsname
314 \global\expandafter\let\csname
315 \expandafter\@gobble\string#1\space\endcsname\@undefined
316 }%
317 }
318 \latexrelease>\EndIncludeInRelease
319 \kernel | latexrelease>
320 \kernel)

```

## 11.5 Internal defining commands

These commands are used internally to define other L<sup>A</sup>T<sub>E</sub>X commands.

`\@ifundefined` Check if first arg is undefined or `\relax` and execute second or third arg depending,

```

321 </2ekernel>
322 <latexrelease>\IncludeInRelease{2018-04-01}{\@ifundefined}
323 <latexrelease>\Leave commands undefined in \@ifundefined}%
324 <*2ekernel|latexrelease>

Version using \ifcsname to avoid defining undefined tokens to \relax. Defined
here to simplify using unmatched \fi.

325 \def\@ifundefined#1{%
326   \ifcsname#1\endcsname\@ifundefin@d@i\else\@ifundefin@d@ii\fi{#1}}

327 \long\def\@ifundefin@d@i#1\fi#2{\fi
328   \expandafter\ifx\csname #2\endcsname\relax
329     \@ifundefin@d@ii
330   \fi
331   \@secondoftwo}

332 \long\def\@ifundefin@d@ii\fi#1#2#3{\fi #2}

Now test of engine.

333 \ifx\numexpr\@undefined

Classic version (should not be needed as etex is assumed).

334 \def\@ifundefined#1{%
335   \expandafter\ifx\csname#1\endcsname\relax
336     \expandafter\@firstoftwo
337   \else
338     \expandafter\@secondoftwo
339   \fi}
340 \else\ifx\directlua\@undefined

Use the \ifcsname defined above.

341 \else

Optimised version for LuaTeX, using \lastnamedcs

342 \def\@ifundefined#1{%
343   \ifcsname#1\endcsname
344     \expandafter\ifx\lastnamedcs\relax\else\@ifundefin@d@i\fi
345   \fi
346   \@firstoftwo}

347 \long\def\@ifundefin@d@i#1#2#3#4#5{#1#2#5}

348 \fi
349 \fi
350 </2ekernel|latexrelease>
351 <latexrelease>\EndIncludeInRelease
352 <latexrelease>\IncludeInRelease{0000-00-00}{\@ifundefined}
353 <latexrelease>\Leave commands undefined in \@ifundefined}%
354 <latexrelease>\def\@ifundefined#1{%
355 <latexrelease>   \expandafter\ifx\csname#1\endcsname\relax
356 <latexrelease>     \expandafter\@firstoftwo
357 <latexrelease>   \else
358 <latexrelease>     \expandafter\@secondoftwo
359 <latexrelease>   \fi}
360 <latexrelease>\EndIncludeInRelease
361 <*2ekernel>

```

`\@qend` The following define `\@qend` and `\@qrelax` to be the strings ‘end’ and ‘relax’ with the characters `\catcoded 12`.

```
362 \edef\@qend{\expandafter\@cdr\string\end\@nil}
363 \edef\@qrelax{\expandafter\@cdr\string\relax\@nil}
```

`\@ifnextchar` `\@ifnextchar` peeks at the following character and compares it with its first argument. If both are the same it executes its second argument, otherwise its third.

```
364 \long\def\@ifnextchar#1#2#3{%
365   \let\reserved@d=#1%
366   \def\reserved@a{#2}%
367   \def\reserved@b{#3}%
368   \futurelet\@let@token\@ifnch}
```

`\kernel@ifnextchar` This macro is the kernel version of `\@ifnextchar` which is used in a couple of places to prevent the AMS variant from being used since in some places this produced chaos (for example if an `fd` file is loaded in a random place then the optional argument to `\ProvidesFile` could get printed there instead of being written only in the log file. This happened when there was a space or a newline between the mandatory and optional arguments! It should really be fixed in the `amsmath` package one day, but...

Note that there may be other places in the kernel where this version should be used rather than the original, but variable, version.

```
369 \let\kernel@ifnextchar\@ifnextchar
```

`\@ifnch` `\@ifnch` is a tricky macro to skip any space tokens that may appear before the character in question. If it encounters a space token, it calls `xifnch`.

```
370 \def\@ifnch{%
371   \ifx\@let@token\@sptoken
372     \let\reserved@c\@xifnch
373   \else
374     \ifx\@let@token\reserved@d
375       \let\reserved@c\reserved@a
376     \else
377       \let\reserved@c\reserved@b
378     \fi
379   \fi
380   \reserved@c}
```

`\@sptoken` The following code makes `\@sptoken` a space token. It is important here that the control sequence `\:` consists of a non-letter only, so that the following whitespace is significant. Together with the fact that the equal sign in a `\let` may be followed by only one optional space the desired effect is achieved. NOTE: the following hacking must precede the definition of `\:` as math medium space.

```
381 \def\:{\let\@sptoken= } \: % this makes \@sptoken a space token
```

`\@xifnch` In the following definition of `\@xifnch`, `\:` is again used to get a space token as delimiter into the definition.

```
382 \def\:{\@xifnch} \expandafter\def\:{\futurelet\@let@token\@ifnch}
```

`\@ifstar` The new implementation below avoids passing the *⟨true code⟩* Through one more `\def` than the *⟨false code⟩*, which previously meant that `#` had to be written as `####` in one argument, but `##` in the other. The `*` is gobbled by `\@firstoftwo`.

```
383 \def\@ifstar#1{\@ifnextchar *{\@firstoftwo{#1}}}
```

```

\@dblarg
\@xdblarg 384 \long\def\@dblarg#1{\kernel@ifnextchar[{#1}]{\@xdblarg{#1}}}
385 \long\def\@xdblarg#1#2{#1[{#2}]{#2}}

\@sanitize The command \@sanitize changes the catcode of all special characters except
for braces to ‘other’. It can be used for commands like \index that want to write
their arguments verbatim. Needless to say, this command should only be executed
within a group, or chaos will ensue.

386 \def\@sanitize{\@makeother\ \@makeother\\\@makeother$\@makeother\&%
387 \@makeother\#\@makeother^\@makeother_\@makeother%\@makeother\~}

\@onelevel@sanitize This makes the whole “meaning” of #1 (its one-level expansion) into catcode 12
tokens: it could be used in \DeclareRobustCommand.
If it is to be used on default float specifiers, this should be done when they are
defined.

388 \def \@onelevel@sanitize #1{%
389 \edef #1{\expandafter\strip@prefix
390 \meaning #1}%
391 }

\makeatletter Make internal control sequences accessible or inaccessible.
\makeatother 392 \DeclareRobustCommand\makeatletter{\catcode'\@11\relax}
393 \DeclareRobustCommand\makeatother{\catcode'\@12\relax}

```

## 12 Discretionary Hyphenation

```

\@dischph
\@dischph Moved here to be after the definition of \DeclareRobustCommand.
The primitive \@dischph command adds a discretionary hyphen using the current font’s
\hyphenchar. Monospace fonts are usually declared with \hyphenchar set to −1
to suppress hyphenation.
LATEX, from LATEX 2.09 in 1986 defined \@dischph by

\def\@dischph{-\discretionary{-}{-}{-}}

```

The following comment was added when these commands were first set up, 19 April 1986:

the \@dischph command is redefined to allow it to work in the \ttfamily type style, where automatic hyphenation is suppressed by setting \hyphenchar to −1. The original primitive T<sub>E</sub>X definition is saved as \@@hyph just in case anyone needs it.

L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>, between 1993 and 2017, had a comment at this point saying that the definition “would probably change” because the definition always uses -. The definition used below was given in comments at this point during time.

In 2017 we finally enabled this definition by default, with the older L<sup>A</sup>T<sub>E</sub>X definition accessible via `latexrelease` as usual.

```

394 \</2ekernel>
395 \ifx\latexrelease\IncludeInRelease{2017/04/15}\@dischph{-\discretionary{-}{-}{-}}\@dischph{-\discretionary{-}{-}{-}}\@dischph{-\discretionary{-}{-}{-}}

```

Temporary definition of \@latex@info, final definition is later.

```

396 (*2ekernel)
397 \def\@latex@info#1{}
398 (/2ekernel)

399 (*2ekernel | latexrelease)
400 \DeclareRobustCommand{\-}{%
401   \discretionary{%
402     \char \ifnum\hyphenchar\font<\z@
403       \defaultshyphenchar
404     \else
405       \hyphenchar\font
406     \fi
407     }{}{}%
408 }
409 \let\@dischyph=\-
410 (/2ekernel | latexrelease)
411 (latexrelease)\EndIncludeInRelease
412 (latexrelease)\IncludeInRelease{0000/00/00}{\-}{Use \hyphenchar in \-}%
413 (latexrelease)\def\-\{\discretionary{-}{}{}\}
414 (latexrelease)\let\@dischyph=\-
415 (latexrelease)\EndIncludeInRelease
416 (*2ekernel)

    Delayed from ltvers.dtx
417 \newif\if@includeinrelease
418 \@includeinreleasefalse

    Delayed from ltplain.dtx
419 (/2ekernel)
420 (*2ekernel | latexrelease)
421 (latexrelease)\IncludeInRelease{2019/10/01}%
422 (latexrelease)          {\allowbreak}{Make various commands robust}%
423 \MakeRobust\allowbreak
424 \MakeRobust\bigbreak
425 \MakeRobust\break
426 \MakeRobust\dotfill
427 \MakeRobust\frenchspacing
428 \MakeRobust\goodbreak
429 \MakeRobust\hrulefill
430 \MakeRobust\medbreak
431 \MakeRobust\nobreak
432 \MakeRobust\nonfrenchspacing
433 \MakeRobust\obeylines
434 \MakeRobust\obeyspaces
435 \MakeRobust\slash
436 \MakeRobust\smallbreak
437 \MakeRobust\strut
438 \MakeRobust\underbar
439 (/2ekernel | latexrelease)
440 (latexrelease)\EndIncludeInRelease
441 (latexrelease)\IncludeInRelease{0000/00/00}%
442 (latexrelease)          {\allowbreak}{Make various commands robust}%
443 (latexrelease)
444 (latexrelease)\kernel@make@fragile\allowbreak

```

```

445 \latexrelease\kernel@make@fragile\bigbreak
446 \latexrelease\kernel@make@fragile\break
447 \latexrelease\kernel@make@fragile\dotfill
448 \latexrelease\kernel@make@fragile\frenchspacing
449 \latexrelease\kernel@make@fragile\goodbreak
450 \latexrelease\kernel@make@fragile\hrulefill
451 \latexrelease\kernel@make@fragile\medbreak
452 \latexrelease\kernel@make@fragile\nobreak
453 \latexrelease\kernel@make@fragile\nonfrenchspacing
454 \latexrelease\kernel@make@fragile\obeylines
455 \latexrelease\kernel@make@fragile\obeyspaces
456 \latexrelease\kernel@make@fragile\slash
457 \latexrelease\kernel@make@fragile\smallbreak
458 \latexrelease\kernel@make@fragile\strut
459 \latexrelease\kernel@make@fragile\underbar
460 \latexrelease\
461 \latexrelease\EndIncludeInRelease
462 \*2ekernel\
463 \2ekernel\

```

# File e

## lalloc.dtx

### 13 Counters

This section deals with counter and other variable allocation.

1 (\*2ekernel)

The following are from plain T<sub>E</sub>X:

\z@ A zero dimen or number. It's more efficient to write \parindent\z@ than  
    \parindent 0pt.

\@ne The number 1.

\m@ne The number -1.

\tw@ The number 2.

\sixt@@n The number 16.

\@m The number 1000.

\@MM The number 20000.

\@xxxii The constant 32.

2 \chardef\@xxxii=32

\@Mi Constants 10001-10004.

\@Mii 3 \mathchardef\@Mi=10001

\@Miii 4 \mathchardef\@Mii=10002

\@Miv 5 \mathchardef\@Miii=10003

6 \mathchardef\@Miv=10004

\@tempcnta Scratch count registers used by L<sup>A</sup>T<sub>E</sub>X kernel commands.

\@tempcntb 7 \newcount\@tempcnta

8 \newcount\@tempcntb

\if@tempswa General boolean switch used by L<sup>A</sup>T<sub>E</sub>X kernel commands.

9 \newif\if@tempswa

\@tempdima Scratch dimen registers used by L<sup>A</sup>T<sub>E</sub>X kernel commands.

\@tempdimb 10 \newdimen\@tempdima

\@tempdimc 11 \newdimen\@tempdimb

12 \newdimen\@tempdimc

\@tempboxa Scratch box register used by L<sup>A</sup>T<sub>E</sub>X kernel commands.

13 \newbox\@tempboxa

\@tempskipa Scratch skip registers used by L<sup>A</sup>T<sub>E</sub>X kernel commands.

\@tempskipb 14 \newskip\@tempskipa

15 \newskip\@tempskipb



```

\@temptokena Scratch token register used by LATEX kernel commands.
16 \newtoks\@temptokena

\@flushglue Glue used for \right- & \leftskip = 0pt plus 1fil
17 \newskip\@flushglue \@flushglue = 0pt plus 1fil
18 \>/2ekernel\

```

# File f

## ltnctrl.dtx

### 14 Program control structure

This section defines a number of control structure macros, such as while-loops and for-loops.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```

1 (*2kernel)
2 \message{control,}

\@whilenum TEST \do {BODY}
\@whiledim TEST \do {BODY} : These implement the loop
    while TEST do BODY od
    where TEST is a TeX \ifnum or \ifdim test, respectively.
    They are optimized for the normal case of TEST initially false.

\@whilesw SWITCH \fi {BODY} : Implements the loop
    while SWITCH do BODY od
    Optimized for normal case of SWITCH initially false.

\@for NAME := LIST \do {BODY} : Assumes that LIST expands to
A1,A2,
    ... ,An .
    Executes BODY n times, with NAME = Ai on the i-th
iteration.
    Optimized for the normal case of n = 1. Works for n=0.

\@tfor NAME := LIST \do {BODY}
    if, before expansion, LIST = T1 ... Tn where each Ti is a
    token or {...}, then executes BODY n times, with NAME = Ti
    on the i-th iteration. Works for n=0.

NOTES: 1. These macros use no \@temp sequences.
        2. These macros do not work if the body contains anything that
        looks syntactically to TeX like an improperly balanced \if
        \else \fi.

\@whilenum TEST \do {BODY} ==
BEGIN
    if TEST
    then BODY
        \@iwhilenum{TEST \relax BODY}
    END

\@iwhilenum {TEST BODY} ==
BEGIN
    if TEST

```

```

        then BODY
          \@nextwhile = def(\@iwhilenum)
        else \@nextwhile = def(\@whilenoop)
        fi
        \@nextwhile {TEST BODY}
      END

```

```

\@whilesw SWITCH \fi {BODY} ==
BEGIN
  if SWITCH
    then BODY
      \@iwhilesw {SWITCH BODY}\fi
    fi
  END

```

```

\@iwhilesw {SWITCH BODY} \fi ==
BEGIN
  if SWITCH
    then BODY
      \@nextwhile = def(\@iwhilesw)
    else \@nextwhile = def(\@whileswnoop)
    fi
    \@nextwhile {SWITCH BODY} \fi
  END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

\@whilenoop
\@whilenum 3 \long\def\@whilenum#1\do #2{\ifnum #1\relax #2\relax\@iwhilenum{#1\relax
\@iwhilenum 4 #2\relax}\fi}
5 \long\def\@iwhilenum#1{\ifnum #1\expandafter\@iwhilenum
6 \else\expandafter\@gobble\fi{#1}}

```

```

\@whiledim
\@iwhiledim 7 \long\def\@whiledim#1\do #2{\ifdim #1\relax#2\@iwhiledim{#1\relax#2}\fi}
8 \long\def\@iwhiledim#1{\ifdim #1\expandafter\@iwhiledim
9 \else\expandafter\@gobble\fi{#1}}

```

```

\@whileswnoop
\@whilesw 10 \long\def\@whilesw#1\fi#2{#1#2\@iwhilesw{#1#2}\fi\fi}
\@iwhilesw 11 \long\def\@iwhilesw#1\fi{#1\expandafter\@iwhilesw
12 \else\@gobbletwo\fi{#1}\fi}

```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```

\@for NAME := LIST \do {BODY} ==
  BEGIN \@forloop expand(LIST),\@nil,\@nil \@@ NAME {BODY}
END

```

```

\@forloop CAR, CARCDR, CDRCDR \@@ NAME {BODY} ==
  BEGIN

```

```

NAME = CAR
if def(NAME) = def(\@nnil)
else BODY;
NAME = CARCDR
if def(NAME) = def(\@nnil)
else BODY
\@iforloop CDRCDR \@@ NAME \do {BODY}
fi
fi
END

\@iforloop CAR, CDR \@@ NAME {BODY} =
NAME = CAR
if def(NAME) = def(\@nnil)
then \@nextwhile = def(\@fornoop)
else BODY ;
\@nextwhile = def(\@iforloop)
fi
\@nextwhile name cdr {body}

\@tfor NAME := LIST \do {BODY}
= \@tforloop LIST \@nil \@@ NAME {BODY}

\@tforloop car cdr \@@ name {body} =
name = car
if def(name) = def(\@nnil)
then \@nextwhile == \@fornoop
else body ;
\@nextwhile == \@forloop
fi
\@nextwhile name cdr {body}
End of historical LATEX 2.09 comments.

\@nnil
13 \def\@nnil{\@nil}

\@empty
14 \def\@empty{}

\@fornoop
15 \long\def\@fornoop#1\@@#2#3{}

\@for
16 \long\def\@for#1:=#2\do#3{%
17 \expandafter\def\expandafter\@fortmp\expandafter{#2}%
18 \ifx\@fortmp\@empty \else
19 \expandafter\@forloop#2,\@nil,\@nil\@@#1{#3}\fi}

\@forloop
20 \long\def\@forloop#1,#2,#3\@@#4#5{\def#4{#1}\ifx #4\@nnil \else
21 #5\def#4{#2}\ifx #4\@nnil \else#5\@iforloop #3\@@#4{#5}\fi\fi}

```

```

\@iforloop
22 \long\def\@iforloop#1,#2\@@#3#4{\def#3{#1}\ifx #3\@nnil
23     \expandafter\@fornoop \else
24     #4\relax\expandafter\@iforloop\fi#2\@@#3{#4}}

\@tfor
25 \def\@tfor#1:={\@tfor#1 }
26 \long\def\@tfor#1#2\do#3{\def\@fortmp{#2}\ifx\@fortmp\space\else
27     \@tforloop#2\@nil\@nil\@@#1{#3}\fi}
28 \long\def\@tforloop#1#2\@@#3#4{\def#3{#1}\ifx #3\@nnil
29     \expandafter\@fornoop \else
30     #4\relax\expandafter\@tforloop\fi#2\@@#3{#4}}

\@break@tfor Break out of a \@tfor loop. This should be called inside the scope of an \if. See
\@iffileonpath for an example.
31 \long\def\@break@tfor#1\@@#2#3{\fi\fi}

\@removeelement Removes an element from a comma-separated list and puts it into a control se-
quence, called as \@removeelement{<element>}{<list>}{<cs>}. Due to the imple-
mentation method the <element> is not allowed to contain braces.
32 \def\@removeelement#1#2#3{%
33     \def\reserved@a##1,#1,##2\reserved@a{##1,##2\reserved@b}%
34     \def\reserved@b##1,\reserved@b##2\reserved@b{%
35         \ifx,##1\@empty\else##1\fi}%
36     \edef#3{%
37         \expandafter\reserved@b\reserved@a,#2,\reserved@b,#1,\reserved@a}}

38 </2ekernel>

```

# File g

## lterror.dtx

### 15 Error handling and tracing

This section defines L<sup>A</sup>T<sub>E</sub>X's error commands.

```
1 (*2ekernel)
```

The '2ekernel' code ensures that a `\usepackage{autoerr}` is essentially ignored if a 'full' format is being used that has the error messages already in the format.

These days we don't support autoloading approach any longer, but this part bit is kept in case it is used in old documents.

```
2 \expandafter\let\csname ver@autoerr.sty\endcsname\fmtversion
```

#### 15.1 General commands

**\MessageBreak** This command prints a new-line inside a message, followed by a continuation line begun with `\@msg@continuation`. Normally it is defined to be `\relax`, but inside messages, it is let to `\@message@break`.

```
3 \let\MessageBreak\relax
```

**\GenericInfo** This takes two arguments: a continuation and a message, and sends the result to the log file.

```
4 \DeclareRobustCommand{\GenericInfo}[2]{%
5   \begingroup
6     \def\MessageBreak{^^J#1}%
7     \set@display@protect
8     \immediate\write\m@ne{#2\on@line.}%
9   \endgroup
10 }
```

**\GenericWarning** This takes two arguments: a continuation and a message, and sends the result to the screen.

```
11 \DeclareRobustCommand{\GenericWarning}[2]{%
12   \begingroup
13     \def\MessageBreak{^^J#1}%
14     \set@display@protect
15     \immediate\write\@unused{^^J#2\on@line.^^J}%
16   \endgroup
17 }
```

**\GenericError** This macro takes four arguments: a continuation, an error message, where to go for further information, and the help information. It displays the error message, and sets the error help (the result of typing `h` to the prompt), and does a horrible hack to turn the last context line (which by default is the only context line) into just three dots. This could be made more efficient.

```
18 \bgroup
19 \lccode'\@=' \ %
```

```

20 \lccode'\~=' \ %
21 \lccode'\}= ' \ %
22 \lccode'\{=' \ %
23 \lccode'\T=' \T%
24 \lccode'\H=' \H%
25 \catcode'\ =11\relax%
26 \lowercase{%
27 \egroup%

```

Unfortunately T<sub>E</sub>X versions older than 3.141 have a bug which means that `^^J` does not force a linebreak in `\message` and `\errmessage` commands. So for these old T<sub>E</sub>X's we use `\typeout` to produce the message, and then have an empty `\errmessage` command. This causes an extra line of the form

! .

To appear on the terminal, but if you do not like it, you can always upgrade your T<sub>E</sub>X! In order for your format to use this version, you must define the macro `\@TeXversion` to be the version number, e.g., 3.14 of the underlying T<sub>E</sub>X. See the comments in `ltdircheck.dtx`.

```

28 \dimen@ \ifx\@TeXversion\undefined4\else\@TeXversion\fi\p@%
29 \ifdim\dimen@>3.14\p@%

```

First the 'standard case'.

```

30 \DeclareRobustCommand{\GenericError}[4]{%
31 \begingroup%
32 \immediate\write\@unused{}%
33 \def\MessageBreak{^^J}%
34 \set@display@protect%
35 \edef%
36 %    %<-----do not delete this space!----->%
37 \@err@
38 {{#4}}%
39 \errhelp
40 %    %<-----do not delete this space!----->%
41 \@err@
42 \let
43 %    %<-----do not delete this space!----->%
44 \@err@
45 \empty
46 \def\MessageBreak{^^J#1}%
47 \def~{\errmessage{%
48 #2.^^J^^J%
49 #3^^J%
50 Type H <return> for immediate help%
51 %    %<-----do not delete this space!----->%
52 \@err@
53 }}%
54 ~%
55 \endgroup}%
56 \else%

```

Secondly the version for old T<sub>E</sub>X's.

```

57 \DeclareRobustCommand{\GenericError}[4]{%
58 \begingroup%

```

```

59 \immediate\write\@unused{}%
60 \def\MessageBreak{^^J}%
61 \set@display@protect%
62 \edef%
63 %    %<-----do not delete this space!----->%
64 \@err@ %
65 {{#4}}%
66 \errhelp
67 %    %<-----do not delete this space!----->%
68 \@err@ %
69 \let
70 %    %<-----do not delete this space!----->%
71 \@err@ %
72 \errmessage
73 \def\MessageBreak{^^J#1}%
74 \def~{\typeout{! %
75 #2.^^J^^J%
76 #3^^J%
77 Type H <return> for immediate help.}%
78 %    %<-----do not delete this space!----->%
79 \@err@ %
80 {}}%
81 ~%
82 \endgroup}%
83 \fi}%

```

<pre> \PackageError \PackageWarning \PackageWarningNoLine \PackageInfo \ClassError \ClassWarning \ClassWarningNoLine \ClassInfo </pre>	<pre> \PackageError{&lt;package&gt;}{&lt;error&gt;}{&lt;help&gt;} \PackageWarning{&lt;package&gt;}{&lt;warning&gt;} \PackageWarningNoLine{&lt;package&gt;}{&lt;warning&gt;} \PackageInfo{&lt;package&gt;}{&lt;info&gt;} </pre>
--	--

and similarly for classes. The **Error** commands print the *<error>* message, and present the interactive prompt; if the author types **h**, then the *<help>* information is displayed. The **Warning** commands produce a warning but do not present the interactive prompt. The **WarningNoLine** commands do the same, but don't print the input line number. The **Info** commands write the message to the **log** file. Within the messages, the command **\MessageBreak** can be used to break a line, **\protect** can be used to protect command names, and **\space** is a space, for example:

```

\newcommand{\foo}{F00}
\PackageWarning{ethel}{%
  Your hovercraft is full of eels,\MessageBreak
  and \protect\foo\space is \foo}

```

produces:

```

Package ethel warning: Your hovercraft is full of eels,
(ethel)                and \foo is F00 on input line 54.

```



```

84 \gdef\PackageError#1#2#3{%
85   \GenericError{%
86     (#1)\@spaces\@spaces\@spaces\@spaces
87   }{%
88     Package #1 Error: #2%
89   }{%
90     See the #1 package documentation for explanation.%
91   }{#3}%
92 }

93 \def\PackageWarning#1#2{%
94   \GenericWarning{%
95     (#1)\@spaces\@spaces\@spaces\@spaces
96   }{%
97     Package #1 Warning: #2%
98   }%
99 }

100 \def\PackageWarningNoLine#1#2{%
101   \PackageWarning{#1}{#2\@gobble}%
102 }

103 \def\PackageInfo#1#2{%
104   \GenericInfo{%
105     (#1) \@spaces\@spaces\@spaces
106   }{%
107     Package #1 Info: #2%
108   }%
109 }

110 \gdef\ClassError#1#2#3{%
111   \GenericError{%
112     (#1) \space\@spaces\@spaces\@spaces
113   }{%
114     Class #1 Error: #2%
115   }{%
116     See the #1 class documentation for explanation.%
117   }{#3}%
118 }

119 \def\ClassWarning#1#2{%
120   \GenericWarning{%
121     (#1) \space\@spaces\@spaces\@spaces
122   }{%
123     Class #1 Warning: #2%
124   }%
125 }

126 \def\ClassWarningNoLine#1#2{%
127   \ClassWarning{#1}{#2\@gobble}%
128 }

129 \def\ClassInfo#1#2{%
130   \GenericInfo{%
131     (#1) \space\space\@spaces\@spaces
132   }{%
133     Class #1 Info: #2%
134   }%
135 }

```

```

\@latex@error Errors and other info, for use in the LATEX core.
\@latex@warning 136 \gdef\@latex@error#1#2{%
\@latex@warning@no@line 137 \GenericError{%
\@latex@info 138 \space\space\space\@spaces\@spaces\@spaces
\@latex@info@no@line 139 }{%
140 LaTeX Error: #1%
141 }{%
142 See the LaTeX manual or LaTeX Companion for explanation.%
143 }{#2}%
144 }

145 \def\@latex@warning#1{%
146 \GenericWarning{%
147 \space\space\space\@spaces\@spaces\@spaces
148 }{%
149 LaTeX Warning: #1%
150 }%
151 }

152 \def\@latex@warning@no@line#1{%
153 \@latex@warning{#1\@gobble}}

154 \def\@latex@info#1{%
155 \GenericInfo{%
156 \@spaces\@spaces\@spaces
157 }{%
158 LaTeX Info: #1%
159 }%
160 }

161 \def\@latex@info@no@line#1{%
162 \@latex@info{#1\@gobble}}

\@font@warning and \@font@info are defined later since they have to be
redefined by the tracefnt package.

\def\@font@warning#1{%
\GenericWarning{%
{(font)\@spaces\@spaces}%
{Font Warning: #1}%
}
\def\@font@info#1{%
\GenericInfo{%
(font)\space\@spaces
}%
Font Info: #1%
}%
}

\c@errorcontextlines \errorcontextlines as a LATEX counter, so that it may be manipulated with
\setcounter (once it is defined :-))
163 \let\c@errorcontextlines\errorcontextlines
164 \c@errorcontextlines=-1

\on@line The message ‘ on input line n’.
165 \def\on@line{ on input line \the\inputlineno}

```

`\@warning` Older L<sup>A</sup>T<sub>E</sub>X messages. For the moment, these `\let` to the new message commands.  
`\@@warning` They may be changed later, once only obsolete packages and classes contain them.  
`\@latexerr`

```
166 \let\@warning\@latex@warning
167 \let\@@warning\@latex@warning@no@line
168 \global\let\@latexerr\@latex@error
```

`\@spaces` Four spaces.

```
169 \def\@spaces{\space\space\space\space}
```

## 15.2 Specific errors

`\@eha` The more common error help messages.

```
\@ehb 170 \gdef\@eha{%
\@ehc 171 Your command was ignored.\MessageBreak
\@ehd 172 Type \space I <command> <return> \space to replace it %
173 with another command,\MessageBreak
174 or \space <return> \space to continue without it.}
175 \gdef\@ehb{%
176 You've lost some text. \space \@ehc}
177 \gdef\@ehc{%
178 Try typing \space <return> %
179 \space to proceed.\MessageBreak
180 If that doesn't work, type \space X <return> \space to quit.}
181 \gdef\@ehd{%
182 You're in trouble here. \space\@ehc}
```

`\@notdefinable` Error message generated in `\@ifdefinable` from calls to one of the commands `\newcommand`, `\newlength` or `\newtheorem` specifying an already-defined command name or one that begins `\end...`

```
183 \gdef\@notdefinable{%
184 \@latex@error{%
185 Command \@backslashchar\reserved@a\space
186 already defined.\MessageBreak
187 Or name \@backslashchar\@qend... illegal,
188 see p.192 of the manual}\@eha}
```

`\@nolnerr` Generated by `\newline` and `\\` when called in vertical mode.

```
189 \gdef\@nolnerr{%
190 \@latex@error{There's no line here to end}\@eha}
```

`\@nocounterr` Generated by `\setcounter`, `\addtocounter` or `\newcounter` if applied to an undefined counter *<cnt>*.

`\@nocnterr` Obsolete error message generated in L<sup>A</sup>T<sub>E</sub>X 2.09 by `\setcounter`, `\addtocounter` or `\newcounter` for undefined counter. DO NOT use for L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> it MIGHT vanish! Use `\@nocounterr{<cnt>}` instead.

```
191 \gdef\@nocounterr#1{%
192 \@latex@error{No counter '#1' defined}\@eha}
193 \gdef\@nocnterr{\@nocounterr?}
```

`\@ctrerr` Called when trying to print the value of a counter numbered by letters that's greater than 26.

```

194 \gdef\@ctrerr{%
195   \latex@error{Counter too large}\@ehb}

```

`\@nodocument` Error produced if paragraphs are typeset in the preamble.

```

196 \gdef\@nodocument{%
197   \latex@error{Missing \protect\begin{document}}\@ehd}

```

`\@badend` Called by `\end` that doesn't match its `\begin`. RmS 1992/08/24: added code to `\@badend` to display position of non-matching `\begin`. FMi 1993/01/14: missing space added.

```

198 \gdef\@badend#1{%
199   \latex@error{\protect\begin{\@currenvir}\@currenvline
200               \space ended by \protect\end{#1}}\@eha}

```

`\@badmath` Called by `\[`, `\]`, `\(` or `\)` when used in wrong mode.

```

201 \gdef\@badmath{%
202   \latex@error{Bad math environment delimiter}\@eha}

```

`\@toodeep` Called by a list environment nested more than six levels deep, or an `enumerate` or `itemize` nested more than four levels.

```

203 \gdef\@toodeep{%
204   \latex@error{Too deeply nested}\@ehd}

```

`\@badpoptabs` Called by `\endtabbing` when not enough `\poptabs` have occurred, or by `\poptabs` when too many have occurred.

```

205 \gdef\@badpoptabs{%
206   \latex@error{\protect\pushtabs\space and \protect\poptabs
207               \space don't match}\@ehd}

```

`\@badtab` Called by `\>`, `\+`, `\-` or `\<` when stepping to an undefined tab.

```

208 \gdef\@badtab{%
209   \latex@error{Undefined tab position}\@ehd}

```

`\@preamerr` This error is special: it appears in places where we normally have to `\protect` expansions. However, to prevent a protection of the error message itself (which would result in the message getting printed not issued on the terminal) we need to locally reset `\protect` to `\relax`.

```

210 \gdef\@preamerr#1{%
211   \begingroup
212     \let\protect\relax
213     \latex@error{\ifcase #1 Illegal character\or
214                 Missing @-exp\or Missing p-arg\fi\space
215                 in array arg}\@ehd
216   \endgroup}

```

`\@badlinearg` Occurs in `\line` and `\vector` command when a bad slope argument is encountered.

```

217 \gdef\@badlinearg{%
218   \latex@error{%
219       Bad \protect\line\space or \protect\vector
220       \space argument}\@ehb}

```

`\@parmoderr` Occurs in a float environment or a `\marginpar` when encountered in inner vertical mode.

```

221 \gdef\@parmoderr{%
222   \latex@error{Not in outer par mode}\@ehb}

```

`\@fltovf` Occurs in float environment or `\marginpar` when there are no more free boxes for storing floats.

```

223 \gdef\@fltovf{%
224   \latex@error{Too many unprocessed floats}\@ehb}

```

`\@latexbug` Occurs in output routine. This is bad news.

```

225 \gdef\@latexbug{%
226   \latex@error{This may be a LaTeX bug}{Call for help}}

```

`\@badcrerr` This error was removed and replaced by `\@nolnerr`.

```

227 %\def\@badcrerr {\latex@error{Bad use of \protect}\@ehc}

```

`\@noitemerr` `\addvspace` or `\addpenalty` was called when not in vmode. Probably caused by a missing `\item`.

```

228 \gdef\@noitemerr{%
229   \latex@error{Something's wrong--perhaps a missing %
230     \protect\item}\@ehc}

```

`\@notprerr` A command that can be used only in the preamble appears after the command `\begin{document}`.

```

231 \gdef\@notprerr{%
232   \latex@error{Can be used only in preamble}\@eha}

```

`\@inmatherr` Issued by commands that don't work correctly within math (like `\item`). There is no real error recovery happening, e.g., the user might get additional errors afterwards.

```

233 \gdef\@inmatherr#1{%
234   \relax
235   \ifmmode
236     \latex@error{Command \protect#1 invalid in math mode}\@ehc
237   \fi}

```

`\@invalidchar` An error for use with invalid characters. This is commented out, since we decided to use catcode 15 instead.

```

238 %\def\@invalidchar{\latex@error{Invalid character in input}\@ehc}

```

As well as the above error commands some error messages are directly coded to save space. The messages already present in  $\text{\LaTeX}2.09$  include:

**Environment --- undefined**

Issued by `\begin` for undefined environment.

**Tab overflow**

Occurs in `\=` when maximum number of tabs exceeded.

**\< in mid line**

Occurs in `\<` when it appears in middle of line.

**Float(s) lost**

In output routine, caused by a float environment or `\marginpar` occurring in inner vertical mode.

## 15.3 Tracing

The `trace` package implements the commands `\traceon` and `\traceoff` that work similar to `\tracingall` but skip certain code blocks that produce a lot of tracing output being of no interest during debugging (for example loading a font). Code blocks that should be hidden during tracing need to be surrounded by the macros `\conditionally@traceoff` and `\conditionally@traceon`.

For the kernel code the `trace` package then redefines a number of macros to include this tracing support.

However, in order to allow any macro package to react to `\traceon` we also provide dummy definitions for the two commands in the kernel so that they can be used by external packages without the need to distinguish between `trace` being loaded or not.

```
\conditionally@traceon  These are only dummy definitions. For details see the trace package.
\conditionally@traceoff 239 \let\conditionally@traceon\@empty
                        240 \let\conditionally@traceoff\@empty
                        241 </2kernel>
```

# File h

## ltpar.dtx

### 16 Paragraphs

This section of the kernel declares the commands used to set `\par` and `\everypar` when ever their function needs to be changed for a long time.

#### 16.1 Implementation

There are two situations in which `\par` may be changed:

- Long-term changes, in which the new value is to remain in effect until the current environment is left. The environments that change `\par` in this way are the following:
  - All list environments (itemize, quote, etc.)
  - Environments that turn `\par` into a noop: tabbing, array and tabular.
- Temporary changes, in which `\par` is restored to its previous value the next time it is executed. The following are all such uses.
  - `\end` when preceded by `\@endparenv`, which is called by `\endtrivlist`
  - The mechanism for avoiding page breaks and getting the spacing right after section heads.

`\@setpar` To permit the proper interaction of these two situations, long-term changes are made by the `\@setpar{<VAL>}` command. It's function is:

To set `\par`. It `\def`'s `\par` and `\@par` to `<VAL>`.

`\@restorepar` Short-term changes are made by the usual `\def\par` commands. The original values are restored after a short-term change by the `\@restorepar` commands.

`\@@par` `\@@par` always is defined to be the original `TEX` `\par`.

`\everypar` `\everypar` is changed only for the short term. Whenever `\everypar` is set non-null, it should restore itself to null when executed.

The following commands change `\everypar` in this way:

- `\item`
- `\end` when preceded by `\@endparenv`, which is called by `\endtrivlist`
- `\minipage`

When dealing with `\par` and `\everypar` remember the following two warnings:

1. Commands that make short-term changes to `\par` and `\everypar` must take account of the possibility that the new commands and the ones that do the restoration may be executed inside a group. In particular, `\everypar` is executed inside a group whenever a new paragraph begins with a left brace. The `\everypar` command that restores its definition should be local to the current group (in case the command is inside a minipage used inside someplace

where `\everypar` has been redefined). Thus, if `\everypar` is redefined to do an `\everypar{}` it could take several executions of `\everypar` before the restoration “holds”. This usually causes no problem. However, to prevent the extra executions from doing harm, use a global switch to keep anything harmful in the new `\everypar` from being done twice.

2. Commands that change `\everypar` should remember that `\everypar` might be supposed to set the following switches false:

- `@nobreak`
- `@minipage`

they should do the setting if necessary.

```
1 \*2kernel)
2 \message{par,}
```

`\@setpar` Initiate a long-term change to `\par`.

```
\@par 3 \def\@setpar#1{\def\par{#1}\def\@par{#1}}
```

The default definition of `\@par` will ensure that if `\@restorepar` defines `\par` to execute `\@par` it will redefine itself to the primitive `\@@par` after one iteration.

```
4 \def\@par{\let\par\@@par\par}
```

`\@restorepar` Restore from a short-term change to `\par`.

```
5 \def\@restorepar{\def\par{\@par}}
6 \*2kernel)
```



# File i

## ltspace.dtx

### 17 Spacing

This section deals with spacing, and line- and page-breaking.

#### 17.1 User Commands

`\nopagebreak` [ $\langle i \rangle$ ] :  $\langle i \rangle = 0, \dots, 4$ .  
 Default argument = 4. Puts a penalty into the vertical list output as follows:  
 0 : penalty = 0  
 1 : penalty = `\@lowpenalty`  
 2 : penalty = `\@medpenalty`  
 3 : penalty = `\@highpenalty`  
 4 : penalty = 10000  
`\pagebreak` [ $\langle i \rangle$ ] : same as except negatives of its penalty  
`\linebreak` [ $\langle i \rangle$ ] : analog of the above  
`\nolinebreak` [ $\langle i \rangle$ ] : analog of the above  
`\samepage` : inhibits page breaking most places by setting the following penalties to 10000:  
`\interlinepenalty`  
`\postdisplaypenalty`  
`\interdisplaylinepenalty`  
`\@beginparpenalty`  
`\@endparpenalty`  
`\@itempenalty`  
`\@secpenalty`  
`\interfootnotelinepenalty`  
`\` : initially defined to be `\newline`  
`\` [ $\langle length \rangle$ ] : initially defined to be `\vspace{\langle length \rangle}\newline`  
 Note: `\`\* adds a `\adjust{\penalty 10000}`  
 OBSOLETE COMMANDS (which never made it into the manual):  
`\obeycr` : defines `\CRi` == `\`  
`\restorecr` : restores `\CRi` to its usual meaning.

#### 17.2 Chris' comments

There are several aspects of the handling of space in horizontal mode that are inconsistent or do not work well in some cases. These are largely concerned with ignoring the effect of space tokens that would otherwise typeset an inter-word space.

Negating the effect of such space tokens is achieved by two mechanisms:

- `\unskip` is used to remove the glue just added by a space that has already had its effect; it is sometimes invoked after an `\ifdim` test on `\lastskip` (see below);
- `\ignorespaces` is used to ignore space-tokens yet to come.

The test done on `\lastskip` is sometimes for equality with zero and sometimes for being positive. Recall also that the test is only on the natural length of the glue and that no glue cannot be distinguished from glue whose natural length is zero: to summarise, a pretty awful test. It is not clear why these tests are not all the same; I think that they should all be for equality. One place where `\unskip` is often used is just before a `\par` (which itself internally does an `\unskip`) and one bit of code (in `\@item`) even has two `\unskips` before a `\par`. These uses may be fossil code but if they are necessary, maybe `\@killglue` would be even safer.

Such removal of glue by `\unskip` may sometimes have the wrong result, removing not the glue from a space-token but other explicit glue; this is sometimes not what is intended.

A common way to prevent such removal is to add an `\hskip\z@` after the glue that should not be removed. This protects that glue against one `\unskip` with no test but not against more than one. It does work for ‘tested `\unskips`’. This is used by `\hspace*` but not by `\hspace`; this is inconsistent as the star is supposed to prevent removal only at the beginning of a line, not at the end, or in a tabular, etc.

If this reason for removing glue were the only consideration then a tested-`\unskip` and protection by `\hskip\z@` would suffice but would need to be consistently implemented.

However, the class of invisibles, commands and environments tries to be even cleverer: one of these tries to leave only one inter-word space whenever there is one before it and one after it; and it does this quite well.

But problems can arise when there is not a space-token on both sides of it; in particular, when an invisible appears at the beginning or end of a piece of text the method still leaves one space token whereas usually in these cases it should leave none.

Also, the current rules do not work well when more than one such command appears consecutively, separated by space-tokens; it leaves glue between every other invisible.

There is also a question about what these commands should do when they occur next to spaces that do not come from space tokens but, for example, from `\hspace`. Should they still produce ‘just one space’? If so, which one? It is good to note that the manual is sufficiently cautious about invisibles that we are not obliged to make anything work.

Another interesting side-road to explore is whether the space-tokens either side of an `\hspace{...}` should be ignored.

One alternative to the current algorithm that is often suggested is that all glue around the invisible should be consolidated into a space after it (usually without stating how much glue should be put there). The command `\nolinebreak` is implemented this way (and `\linebreak` should also be). This does not work correctly for the following common case:

```
... some text
\index{some-word}
some-word and more text.
```

This is optimal coding since it is normal to index a word that gets split across a page-break on its starting page. This would, on the other hand, fix another common (and documented) failure of the current system: when the invisible is

the last thing in a paragraph the space before it is not removed and, worse, it is also hidden from the paragraph-ending mechanism so that an ‘empty’ line can be created at the end of the paragraph.

Another deficiency (I think) of the current system is that the following is treated as having the `\index` command between the paragraphs, which is probably not what the author intended (since there is no empty line after it).

```
\index{beginnings}
Beginnings of paragraphs ...
```

I know of no algorithm that will handle satisfactorily even all the most common cases; note that it could be that the best algorithm may be different for different invisibles since, for example, the common uses and expected behaviour of `\index`, `\marginpar`, `\linebreak`, `\pagebreak` and `\vspace` are somewhat different. [For example, is `\vspace` ever used in the middle of a paragraph?]

One method that can (and is) used to make invisible commands produce no space when used at the beginning of text is to put in some glue that is nearly enough the same as no glue or glue of zero length in all respects except for the precise test for not being exactly equal to zero; examples of such glue are `\hskip 1sp` and, possibly better but more complex, `\hskip -1sp \hskip 1sp`. However, this only works when it is known that user-supplied text is about to start.

Some similar concerns apply to the handling of space and penalties in vertical mode; there is an extra hurdle here as `\unskip` does not work on the main vertical list. The complexity of the tests done by `\addvspace` have never been explained.

The implementation of space hacks etc for vertical mode is another major area that needs further attention; my earlier experiments did not produce much improvement over the current unsatisfactory situation.

One particular problem is what happens when the following very natural coding is used (part of the problem here is that this looks like an hmode problem, but it is not):

```
... end of text.

\begin{enumerate}
  \item \label{item:xxx} Item text.
\end{enumerate}
```

### 17.3 Some immediate actions

- Fix bug in `\linebreak`.
- Fix bug in `\\*`.
- Reimplement `\\`, etc, removing extra `\vadjusts` and getting better error trapping (this seems to involve a lot more tokens).
- Investigate whether `\\`, etc need to be errors in vmode; I think that they could be noops (maybe with a warning).
- Make all(?) `\unskips` include test for zero skip (rather than other tests or no test).

- Consider replacing `\hskip 1sp` by something better (here called an ‘infinitesimal’ skip).
- Look at all `\hskip\z@` (or similar) to see if they should be changed to an ‘infinitesimal’ skip.
- Resolve the inconsistency between `\hspace` and `\hspace*`.
- Remove unnecessary `\unskips`.
- Investigate and rationalise the ‘newline’ code.
- Find better algorithms for all sorts of things or, easier(?), fix T<sub>E</sub>X itself.

## 17.4 The code

```

1 (*2ekernel)
2 \message{spacing,}

3 (/2ekernel)
4 (*2ekernel | latexrelease)
5 (latexrelease)\IncludeInRelease{2019/10/01}%
6 (latexrelease)          {\pagebreak}{Make commands robust}%

\pagebreak
\nopagebreak 7 \DeclareRobustCommand\pagebreak{\@testopt{\@no@pgbk-}4}
8 \DeclareRobustCommand\nopagebreak{\@testopt{\@no@pgbk4}

\linebreak
\nolinebreak 9 \DeclareRobustCommand\linebreak{\@testopt{\@no@lnbk-}4}
10 \DeclareRobustCommand\nolinebreak{\@testopt{\@no@lnbk4}

\samepage

11 \DeclareRobustCommand\samepage{\interlinepenalty\@M
12   \postdisplaypenalty\@M
13   \interdisplaylinepenalty\@M
14   \@beginparpenalty\@M
15   \@endparpenalty\@M
16   \@itempenalty\@M
17   \@secpenalty\@M
18   \interfootnotelinepenalty\@M}

19 (/2ekernel | latexrelease)
20 (latexrelease)\EndIncludeInRelease
21 (latexrelease)\IncludeInRelease{0000/00/00}%
22 (latexrelease)          {\pagebreak}{Make commands robust}%
23 (latexrelease)

24 (latexrelease)\kernel@make@fragile\pagebreak
25 (latexrelease)\kernel@make@fragile\nopagebreak
26 (latexrelease)\kernel@make@fragile\linebreak
27 (latexrelease)\kernel@make@fragile\nolinebreak
28 (latexrelease)\kernel@make@fragile\samepage
29 (latexrelease)
30 (latexrelease)\EndIncludeInRelease
31 (*2ekernel)

```

`\@no@pgbk`

```
32 \def\@no@pgbk #1[#2]{%
33   \ifvmode
34     \penalty #1\@getpen{#2}%
35   \else
36     \@bsphack
37     \vadjust{\penalty #1\@getpen{#2}}%
38     \@esphack
39   \fi}
```

`\@no@lnbk`

```
40 \def\@no@lnbk #1[#2]{%
41   \ifvmode
42     \@nolnerr
43   \else
44     \@tempskipa\lastskip
45     \unskip
46     \penalty #1\@getpen{#2}%
47     \ifdim\@tempskipa>\z@
48       \hskip\@tempskipa
49       \ignorespaces
50     \fi
51   \fi}
```

`\` The purpose of the new code is to fix a few bugs; however, it also attempts to optimize the following, in order of priority:

1. efficient execution of plain `\`;
2. efficient execution of `\[...]`;
3. memory use;
4. name-space use.

The changes should make no difference to the typeset output. It appears to be safe to use `\reserved@e` and `\reserved@f` here (other reserved macros are somewhat disastrous).

These changes made `\newline` even less robust than it had been, so now it is explicitly robust, like `\`.

`\@normalcr` The internal definition of the ‘normal’ definition of `\`.

```
52 </2ekernel>
53 <*2ekernel | latexrelease>
54 <latexrelease> \IncludeInRelease{2020/02/01}%
55 <latexrelease> {\@normalcr}{Make robust}%
56 \protected\def\@normalcr{%
57   \let \reserved@e \relax
58   \let \reserved@f \relax
59   \@ifstar{\let \reserved@e \vadjust \let \reserved@f \nobreak
60     \xnewline}%
61   \@xnewline}
```

```

62 \let\\\@normalcr
63 /2ekernel | latexrelease)
64 (latexrelease)\EndIncludeInRelease
65 (latexrelease)\IncludeInRelease{0000/00/00}%
66 (latexrelease)          {\@normalcr}{Make robust}%
67 (latexrelease)
68 (latexrelease)\DeclareRobustCommand\\\{%
69 (latexrelease)  \let \reserved@e \relax
70 (latexrelease)  \let \reserved@f \relax
71 (latexrelease)  \@ifstar{\let \reserved@e \vadjust \let \reserved@f \nobreak
72 (latexrelease)          \@xnewline}%
73 (latexrelease)  \@xnewline}
74 (latexrelease)\expandafter\let\expandafter\@normalcr
75 (latexrelease)  \csname\expandafter\@gobble\string\\\ \endcsname
76 (latexrelease)
77 (latexrelease)\EndIncludeInRelease
78 (*2ekernel)

```

`\newline` A simple form of the ‘normal’ definition of `\\`.

```
79 \DeclareRobustCommand\newline{\@normalcr\relax}
```

`\@xnewline`

```
80 \def\@xnewline{\@ifnextchar[% ] bracket matching
81             \@newline
82             {\@gnewline\relax}}
```

`\@newline`

```
83 \def\@newline[#1]{\let \reserved@e \vadjust
84             \@gnewline {\vskip #1}}
```

`\@gnewline` The `\nobreak` added to prevent null lines when `\\` ends an overfull line. Change made 24 May 89 as suggested by Frank Mittelbach and Rainer Schöpf

```
85 \def\@gnewline #1{%
86   \ifvmode
87     \@nolnerr
88   \else
89     \unskip \reserved@e {\reserved@f#1}\nobreak \hfil \break
90   \fi}
```

`\@getpen`

```
91 \def\@getpen#1{\ifcase #1 \z@ \or \@lowpenalty\or
92             \@medpenalty \or \@highpenalty
93             \else \@M \fi}
```

`\if@nobreak` Switch used to avoid page breaks caused by `\label` after a section heading, etc. It should be **GLOBALLY** set true after the `\nobreak` and **globally** set false by the next invocation of `\everypar`.

Commands that reset `\everypar` should globally set it false if appropriate.

```
94 \def\@nobreakfalse{\global\let\if@nobreak\iffalse}
95 \def\@nobreaktrue {\global\let\if@nobreak\iftrue}
96 \@nobreakfalse

```

`\@savsk` Registers used to save the space factor and last skip.  
`\@savsf` 97 `\newdimen\@savsk`  
98 `\newcount\@savsf`

`\@bsphack` `\@bsphack` and `\@esphack` used by macros such as `\index` and `\begin{@float}` ... `\end{@float}` that want to be invisible — i.e., not leave any extra space when used in the middle of text. Such a macro should begin with `\@bsphack` and end with `\@esphack`. The macro in question should not create any text, nor change the mode.

Before giving the current definition we give an extended definition that is currently not used (because it doesn't work as advertised:-)

These are generalised hacks which attempt to do sensible things when 'invisible commands' appear in vmode too.

They need to cope with space in both hmode (plus spacefactor) and vmode, and also cope with breaks etc. In vmode this means ensuring that any following `\addvspace`, etc sees the correct glue in `\lastskip`.

In fact, these improved versions should be used for other cases of 'whatsits, thingies etc' which should be invisible. They are only for commands, not environments (see notes on `\@Esphack`).

BTW, anyone know why the standard hacks are surrounded by `\ifmmode\else` rather than simply `\ifhmode`?

And are there any cases where saving the spacefactor is essential? I have some extensions where it is, but it does not appear to be so in the standard uses.

```
\def \@bsphack{%
  \relax \ifvmode
    \@savsk \lastskip
    \ifdim \lastskip=\z@
      \else
        \vskip -\lastskip
      \fi
    \else
      \ifhmode
        \@savsk \lastskip
        \@savsf \spacefactor
      \fi
    \fi
}
```

I think that, in vmode, it is the safest to put in a `\nobreak` immediately after such things since writes, inserts etc followed by glue give valid breakpoints and, in general, it is possible to create breaks but impossible to destroy them.

```
\def \@esphack{%
  \relax \ifvmode
    \nobreak
    \ifdim \@savsk=\z@
      \else
        \vskip\@savsk
      \fi
    \else
      \ifhmode
        \spacefactor \@savsf
      \fi
    \fi
}
```

```

        \ifdim \@savsk>\z@
        \ignorespaces
        \fi
    \fi
\fi
}

```

For the moment we are going to ignore the vertical versions until they are correct.

```

99 \def\@bsphack{%
100 \relax
101 \ifhmode
102 \savsk\lastskip
103 \savsf\spacefactor
104 \fi}

```

**\@esphack** Companion to \@bsphack. If this command is not properly paired with \@bsphack one might end up with a low-level T<sub>E</sub>X error: “BAD spacefactor”. One possible cause is calling \@bsphack in vertical mode, then doing something that gets you (sometimes) into horizontal mode and finally calling \@esphack. Even if no error is generated that is wrong, because \@esphack will then use the saved values for \@savsk and \@savsf from some earlier invocation of \@bsphack which will have nothing to do with the current situation.

```

105 </2ekernel>
106 <latexrelease>\IncludeInRelease{2018/10/10}%
107 <latexrelease>          {\@esphack}{hyphenation and nobreak after space hack}%
108 <*2ekernel | latexrelease>
109 \def\@esphack{%
110 \relax
111 \ifhmode
112 \spacefactor\@savsf
113 \ifdim\@savsk>\z@
114 \ifdim\lastskip=\z@
115 \nobreak \hskip\z@skip
116 \fi
117 \ignorespaces
118 \fi
119 \else
120 \ifvmode
121 \if@nobreak\nobreak\else\if@noskipsec\nobreak\fi\fi
122 \fi
123 \fi}%
124 </2ekernel | latexrelease>
125 <latexrelease>\EndIncludeInRelease
126 <latexrelease>\IncludeInRelease{2015/10/01}%
127 <latexrelease>          {\@esphack}{hyphenation and nobreak after space hack}%
128 <latexrelease>\def\@esphack{%
129 <latexrelease> \relax
130 <latexrelease> \ifhmode
131 <latexrelease> \spacefactor\@savsf
132 <latexrelease> \ifdim\@savsk>\z@

```



```

133 <latexrelease> \ifdim\lastskip=\z@
134 <latexrelease> \nobreak \hskip\z@skip
135 <latexrelease> \fi
136 <latexrelease> \ignorespaces
137 <latexrelease> \fi
138 <latexrelease> \fi}%
139 <latexrelease>\EndIncludeInRelease
140 <latexrelease>\IncludeInRelease{2015/01/01}%
141 <latexrelease> {\@esphack}{hyphenation and nobreak after space hack}%
142 <latexrelease>\def\@esphack{%
143 <latexrelease> \relax
144 <latexrelease> \ifhmode
145 <latexrelease> \spacefactor\@savsf
146 <latexrelease> \ifdim\@savsk>\z@
147 <latexrelease> \nobreak \hskip\z@skip
148 <latexrelease> \ignorespaces
149 <latexrelease> \fi
150 <latexrelease> \fi}%
151 <latexrelease>\EndIncludeInRelease
152 <latexrelease>\IncludeInRelease{0000/00/00}%
153 <latexrelease> {\@esphack}{hyphenation and nobreak after space hack}%
154 <latexrelease>\def\@esphack{%
155 <latexrelease> \relax
156 <latexrelease> \ifhmode
157 <latexrelease> \spacefactor\@savsf
158 <latexrelease> \ifdim\@savsk>\z@
159 <latexrelease> \ignorespaces
160 <latexrelease> \fi
161 <latexrelease> \fi}%
162 <latexrelease>\EndIncludeInRelease
163 <*2ekernel>

```

**\@Esphack** A variant of \@esphack that sets the @ignore switch to true (as \@esphack used to do previously). This is currently used only for floats and similar environments.

```

w
164 </2ekernel>
165 <latexrelease>\IncludeInRelease{2015/01/01}%
166 <latexrelease> {\@Esphack}{hyphenation after space hack}%
167 <*2ekernel | latexrelease>
168 \def\@Esphack{%
169 \relax
170 \ifhmode
171 \spacefactor\@savsf
172 \ifdim\@savsk>\z@
173 \nobreak \hskip\z@skip
174 \@ignoretrue
175 \ignorespaces
176 \fi
177 \fi}%
178 </2ekernel | latexrelease>
179 <latexrelease>\EndIncludeInRelease
180 <latexrelease>\IncludeInRelease{0000/00/00}%
181 <latexrelease> {\@Esphack}{hyphenation after space hack}%
182 <latexrelease>\def\@Esphack{%

```

```

183 <latexrelease> \relax
184 <latexrelease> \ifhmode
185 <latexrelease> \spacefactor\@savs f
186 <latexrelease> \ifdim\@savsk>\z@
187 <latexrelease> \ignoretrue
188 <latexrelease> \ignorespaces
189 <latexrelease> \fi
190 <latexrelease> \fi}%
191 <latexrelease>\EndIncludeInRelease
192 <*2kernel>

```

`\@vbsphack` Another variant which is useful for invisible things which should not live in vmode (this is how some people feel about marginals).

If it occurs in vmode then it enters hmode and ensures that `\@savsk` is nonzero so that the `\ignorespaces` is put in later. It is not used at present.

```

\def \@vbsphack{ %
  \relax \ifvmode
    \leavevmode
    \@savsk 1sp
    \@savs f \spacefactor
  \else
    \ifhmode
      \@savsk \lastskip
      \@savs f \spacefactor
    \fi
  \fi
}

```

## 17.5 Vertical spacing

L<sup>A</sup>T<sub>E</sub>X supports the plain T<sub>E</sub>X commands `\smallskip`, `\medskip` and `\bigskip`. However, it redefines them using `\vspace` instead of `\vskip`.

Extra vertical space is added by the command `\addvspace{<skip>}`, which adds a vertical skip of *<skip>* to the document. The sequence `\addvspace{<s1>} \addvspace{<s2>}` is equivalent to `\addvspace{<maximum of s1, s2>}`.

`\addvspace` should be used only in vertical mode, and gives an error if it's not. The `\addvspace` command does *not* add vertical space if `@minipage` is true. The minipage environment uses this to inhibit the addition of extra vertical space at the beginning.

Penalties are put into the vertical list with the `\addpenalty{<penalty>}` command. It works properly when `\addpenalty` and `\addvspace` commands are mixed.

The `@nobreak` switch is set true used when in vertical mode and no page break should occur. (Right now, it is used only by the section heading commands to inhibit page breaking after a heading.)

```

\addvspace{SKIP} ==
BEGIN
  if vmode
    then if @minipage
      else if \lastskip =0

```

```

        then \vskip SKIP
      else if \lastskip < SKIP
        then \vskip -\lastskip
             \vskip SKIP
        else if SKIP < 0 and \lastskip >= 0
          then \vskip -\lastskip
               \vskip \lastskip + SKIP
        fi
      fi
    fi
  else useful error message (CAR).
fi
END

```

**\@xaddvskip** Internal macro for `\vspace` handling the case that space has previously been added.

```

193 \def\@xaddvskip{%
194   \ifdim\lastskip<\@tempskipb
195     \vskip-\lastskip
196     \vskip\@tempskipb
197   \else
198     \ifdim\@tempskipb<\z@
199       \ifdim\lastskip<\z@
200         \else
201           \advance\@tempskipb\lastskip
202           \vskip-\lastskip
203           \vskip \@tempskipb
204         \fi
205       \fi
206     \fi}

```

**\addvspace** Add vertical space taking into account space already added, as described above.

```

207 \def\addvspace#1{%
208   \ifvmode
209     \if@minipage\else
210       \ifdim \lastskip =\z@
211         \vskip #1\relax
212       \else
213         \@tempskipb#1\relax
214         \@xaddvskip
215       \fi
216     \fi
217   \else
218     \@noitemerr
219   \fi}

```

**\addpenalty**

```

220 \if2ekernel
221 \iflatexrelease\IncludeInRelease{2015/01/01}%
222 \iflatexrelease
223 \if*2ekernel\iflatexrelease

```

Fix provided by Donald (though the original fix was not good enough). In 2005 Plamen Tanovski discovered that this fix wasn't good enough either as the `\vskip` kept getting bigger if several `\addpenalty` commands followed each other. Donald kindly send a new fix.

```
224 \def\addpenalty#1{%
```

```
225   \ifvmode
```

```
226     \if@minipage
```

```
227     \else
```

```
228       \if@nobreak
```

```
229       \else
```

```
230         \ifdim\lastskip=\z@
```

```
231         \penalty#1\relax
```

```
232       \else
```

```
233         \@tempskipb\lastskip
```

We have to make sure the final `\vskip` seen by  $\text{\TeX}$  is the correct one, namely `\@tempskipb`. However we may have to adjust for `\prevdepth` when placing the penalty but that should not affect the skip we pass on to  $\text{\TeX}$ .

```
234     \begingroup
```

```
235       \@tempskipa\@tempskipb
```

```
236       \advance \@tempskipb
```

```
237       \ifdim\prevdepth>\maxdepth\maxdepth\else
```

If `\prevdepth` is -1000pt due to `\nointerlineskip` we better not add it!

```
238         \ifdim \prevdepth = -\@m\p@ \z@ \else \prevdepth \fi
```

```
239       \fi
```

```
240       \vskip -\@tempskipb
```

```
241       \penalty#1%
```

```
242       \ifdim\@tempskipa=\@tempskipb
```

Do nothing if the `\prevdepth` check made no adjustment.

```
243     \else
```

Combine the `\prevdepth` adjustment into a single skip.

```
244       \advance\@tempskipb -\@tempskipa
```

```
245       \vskip \@tempskipb
```

```
246     \fi
```

The final skip is always the specified length.

```
247       \vskip \@tempskipa
```

```
248     \endgroup
```

```
249   \fi
```

```
250   \fi
```

```
251   \fi
```

```
252   \else
```

```
253     \@noitemerr
```

```
254   \fi}%
```

```
255 \</2ekernel | latexrelease>
```

```
256 \<latexrelease>\EndIncludeInRelease
```

```
257 \<latexrelease>\IncludeInRelease{0000/00/00}%
```

```
258 \<latexrelease>{\addpenalty}{\addpenalty}%
```

```
259 \<latexrelease>\def\addpenalty#1{%
```

```
260 \<latexrelease>  \ifvmode
```

```
261 \<latexrelease>    \if@minipage
```

```
262 \<latexrelease>    \else
```

```
263 \<latexrelease>      \if@nobreak
```

```
264 \<latexrelease>      \else
```

```
265 \<latexrelease>        \ifdim\lastskip=\z@
```

```
266 \<latexrelease>        \penalty#1\relax
```

```

267 \latexrelease\else
268 \latexrelease\@tempskipb\lastskip
269 \latexrelease\vskip -\lastskip
270 \latexrelease\penalty#1%
271 \latexrelease\vskip\@tempskipb
272 \latexrelease\fi
273 \latexrelease\fi
274 \latexrelease\fi
275 \latexrelease\else
276 \latexrelease\@noitemerr
277 \latexrelease\fi}%
278 \latexrelease\EndIncludeInRelease
279 \*2ekernel)

```

`\vspace` The new code for these commands depends on the following facts:

`\@vspace`  
`\@vspacer`

- The value of `prevdepth` is changed only when a box or rule is created and added to a vertical list;
- The value of `prevdepth` is used only when a box is created and added to a vertical list;
- The value of `prevdepth` is always local to the building of one vertical list.

```

280 \DeclareRobustCommand\vspace{\@ifstar\@vspacer\@vspace}
281 \def\@vspace #1{%
282   \ifvmode
283     \vskip #1
284     \vskip\z@skip
285   \else
286     \@bsphack
287     \vadjust{\@restorepar
288               \vskip #1
289               \vskip\z@skip
290             }%
291     \@esphack
292   \fi}
293 \def\@vspacer#1{%
294   \ifvmode
295     \dimen@\prevdepth
296     \hrule \@height\z@
297     \nobreak
298     \vskip #1
299     \vskip\z@skip
300     \prevdepth\dimen@
301   \else
302     \@bsphack
303     \vadjust{\@restorepar
304               \hrule \@height\z@
305               \nobreak
306               \vskip #1
307               \vskip\z@skip}%
308     \@esphack
309   \fi}

```

```

\smallskip
\medskip 310 \def\smallskip{\vspace\smallskipamount}
\bigskip 311 \def\medskip{\vspace\medskipamount}
          312 \def\bigskip{\vspace\bigskipamount}

\smallskipamount
\medskipamount 313 \newskip\smallskipamount \smallskipamount=3pt plus 1pt minus 1pt
\bigskipamount 314 \newskip\medskipamount \medskipamount =6pt plus 2pt minus 2pt
                315 \newskip\bigskipamount \bigskipamount =12pt plus 4pt minus 4pt

```

## 17.6 Horizontal space (and breaks)

`\nobreakdashes` This idea is borrowed from the `amsmath` package but here we define a robust command.

This command is a low-level command designed for use only before hyphens or dashes (such as `-`, `--`, or `---`).

It could probably be better implemented: it may need its own private token register and temporary command.

Setting the hyphen in a box and then unboxing it means that the normal penalty will not be added after it—and if the penalty is not there a break will not be taken (unless an explicit penalty or glue follows, thus the final `\nobreak`).

Note that even if it is not followed by a `'-`, it still leaves `vmode` and sets the `spacefactor`; so use it carefully!

```

316 \DeclareRobustCommand{\nobreakdashes}{%
317   \leavevmode
318   \toks@{}%
319   \def\reserved@a##1{\toks@\expandafter{\the\toks@-}%
320                     \futurelet\@let@token \reserved@b}%
321   \def\reserved@b  {\ifx\@let@token -%
322                     \expandafter\reserved@a
323                     \else
324                     \setbox\z@ \hbox{\the\toks@\nobreak}%
325                     \unhbox\z@
326                     \spacefactor\sfcode'\-
327                     \fi}%
328   \futurelet\@let@token \reserved@b
329 }

```

`\nobreakspace` This is a robust command that produces a horizontal space at which, in paragraph-mode, a line-break is not possible. We then define an active `~` to expand to it since this is the documented behaviour of `~`. One reason for introducing this is that some 8-bit input encodings have a slot for such a space and we do not want to use active characters as the  $\text{\LaTeX}$  internal commands.

The braces in the definition of `~` are needed to ensure that a following space is preserved when reading to/from internal files.

We need to keep `\@xobeysp` as it is widely used; so here it is let to the non-robust command `\nobreakspace`.

```

330 \DeclareRobustCommand{\nobreakspace}{%
331   \leavevmode\nobreak\ }
332 \catcode '\~ =13
333 \def~{\nobreakspace}
334 \expandafter\let\expandafter\@xobeysp\csname nobreakspace \endcsname

```

`\,` Used in paragraph mode produces a `\thinspace`. It has the ordinary definition in math mode. Useful for quotes inside quotes, as in ‘‘`\,`‘Foo’, he said.’’

```
335 \DeclareRobustCommand{\,}{%
336   \relax\ifmmode\mskip\thinmuskip\else\thinspace\fi
337 }
```

`\@` Placed before a ‘.’, makes it a sentence-ending period. Does the right thing for other punctuation marks as well. Does this by setting spacefactor to 1000.

```
338 \/2ekernel)
339 \latexrelease\IncludeInRelease{2015/01/01}%
340 \latexrelease          {\@}{Space after \@}%
341 \*2ekernel | latexrelease)
342 \def\@{\spacefactor\@m{}}%
343 \/2ekernel | latexrelease)
344 \latexrelease\EndIncludeInRelease
345 \latexrelease\IncludeInRelease{0000/00/00}%
346 \latexrelease          {\@}{Space after \@}%
347 \latexrelease\def\@{\spacefactor\@m}%
348 \latexrelease\EndIncludeInRelease
349 \*2ekernel)
```

`\hspace`

```
350 \DeclareRobustCommand\hspace{\@ifstar\@hspacer\@hspace}
```

`\@hspace`

```
351 \def\@hspace#1{\hskip #1\relax}
```

`\@hspacer` extra `\hskip` Opt added 1985/17/12 to guard against a following `\unskip \relax` added 13 Oct 88 for usual T<sub>E</sub>X lossage replaced both changes by `\hskip\z@skip` 27 Nov 91

```
352 \def\@hspacer#1{\vrule \@width\z@\nobreak
353   \hskip #1\hskip \z@skip}
```

`\fill`

```
354 \newskip\fill
355 \fill = Opt plus 1fill
```

`\stretch`

```
356 \def\stretch#1{\z@ \@plus #1fill\relax}
357 \/2ekernel)
358 \*2ekernel | latexrelease)
359 \latexrelease\IncludeInRelease{2018/12/01}%
360 \latexrelease          {\thinspace}{Start LR-mode}%
```

`\thinspace`

`\negthinspace`

`\enspace`

```
361 \DeclareRobustCommand\thinspace{\leavevmode@ifvmode\kern .16667em }
362 \DeclareRobustCommand\negthinspace{\leavevmode@ifvmode\kern-.16667em }
363 \DeclareRobustCommand\enspace{\leavevmode@ifvmode\kern.5em }
```

`\leavevmode@ifvmode` Leave vmode but only if we are really in vmode, otherwise the expansion is empty (which is not the case with the default definition).

```
364 \protected\def\leavevmode@ifvmode{\ifvmode\expandafter\indent\fi}
```

```

365 </2ekernel | latexrelease>
366 <latexrelease>\EndIncludeInRelease
367 <latexrelease>\IncludeInRelease{0000/00/00}%
368 <latexrelease>{\thinspace}{Start LR-mode}%
369 <latexrelease>\def\thinspace{\kern .16667em }
370 <latexrelease>\def\negthinspace{\kern-.16667em }
371 <latexrelease>\def\enspace{\kern.5em }
372 <latexrelease>\let\leavevmode@ifvmode\@undefined
373 <latexrelease>\EndIncludeInRelease
374 <*2ekernel>

\enskip
\quad 375 \def\enskip{\hskip.5em\relax}
\qqquad 376 \def\quad{\hskip1em\relax}
377 \def\qqquad{\hskip2em\relax}

\obeycr The following definitions will probably get deleted or moved to compatibility mode
\restorecr soon.

378 {\catcode'\^^M=13 \gdef\obeycr{\catcode'\^^M13 \def^^M{\\ \relax}%
379 \gobblecr}%
380 {\catcode'\^^M=13 \gdef@gobblecr{\@ifnextchar
381 \@gobble\ignorespaces}}
382 \gdef\restorecr{\catcode'\^^M5 }}

383 </2ekernel>

```



# File j

## ltlogos.dtx

### 18 Logos

Various logos are defined here.

`\TeX` The  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$  logo, adjusted so that a full stop after the logo counts as ending a sentence.

```
1 <*2ekernel>
2 \DeclareRobustCommand\TeX{T\kern-.1667em\lower.5ex\hbox{E}\kern-.125emX\@}
```

`\LaTeX` The  $\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$  logo.

```
3 \DeclareRobustCommand{\LaTeX}{L\kern-.36em%
4     {\sbox\z@ T%
5       \vbox to\ht\z@{\hbox{\check@mathfonts
6                             \fontsize\sf@size\z@
7                             \math@fontsfalse\selectfont
8                             A}%
9                             \vss}%
10    }%
11    \kern-.15em%
12    \TeX}
```

`\LaTeXe` The  $\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X} 2_{\varepsilon}$  logo as proposed by A-W designers.

```
13 \DeclareRobustCommand{\LaTeXe}{\mbox{\m@th
14   \if b\expandafter\@car\f@series\@nil\boldmath\fi
15   \LaTeX\kern.15em2$_{\textstyle\varepsilon}$}}
16 </2ekernel>
```

# File k

## ltfiles.dtx

### 19 File Handling

The following user commands are defined in this part:

<code>\document</code>	<code>(ie \begin{document})</code> Reads in the .AUX files and <code>\catcode</code> 's @ to 12.
<code>\nofiles</code>	Suppresses all file output by setting <code>\@files</code> false.
<code>\includeonly</code>	<code>{\NAME1, ... ,NAMEn}</code> Causes only parts NAME1, ... ,NAMEn to be read by their <code>\include</code> commands. Works by setting <code>partsw</code> true and setting <code>\@partlist</code> to NAME1, ... ,NAMEn.
<code>\include</code>	<code>{\NAME}</code> Does an <code>\input</code> NAME unless <code>\@partsw</code> is true and NAME is not in <code>\@partlist</code> . If <code>\@files</code> is true, then it directs .AUX output to NAME.AUX, including a checkpoint at the end.
<code>\input</code>	<code>{\NAME}</code> The same as TeX's <code>\input</code> , except it allows optional braces around the file name. In $\text{\LaTeX 2}_{\epsilon}$ , it also avoids the primitive 'missing file' error, if the file can not be found.
<code>\IfFileExists</code>	<code>{\NAME}{\&lt;then&gt;}{\&lt;else&gt;}</code> If the file exists on the system, execute <i>then</i> otherwise execute <i>else</i> .
<code>\InputIfFileExists</code>	<code>{\NAME}{\&lt;then&gt;}{\&lt;else&gt;}</code> If the file exists on the system, execute <i>then</i> and input NAME otherwise execute <i>else</i> . <i>Historical \LaTeX 2.09 comments (not necessarily accurate any more):</i>

```
1 (*2ekernel)
2 \message{files,}
```

VARIABLES, SWITCHES AND INTERNAL COMMANDS:

`\@mainaux` : Output file number for main .AUX file.  
`\@partaux` : Output file number for current part's .AUX file.  
`\@auxout` : Either `\@mainout` or `\@partout`, depending on which .AUX file output goes to.  
`\@input{foo}` : If file foo exists, then `\input`'s it, otherwise types a warning message.  
`@files` : Switch – set false if no .AUX, .TOC, .IDX etc files are to be written  
`@partsw` : Set true by a `\includeonly` command.  
`\@partlist` : Set to the argument of the `\includeonly` command.  
`\cp@FOO` : The checkpoint for `\include`'d file FOO.TEX, written by `\@writeckpt` at the end of file FOO.AUX

```
\includeonly{FILELIST} ==
```

```

BEGIN
  \@partsw := T
  \@partlist := FILELIST
END

\include{FILE} ==
BEGIN
  \clearpage
  if \@filesw = T
    then \immediate\write\@mainaux{\string\@input{FILE.AUX}}
  fi
  if \@partsw = T
    then \@tempswa := F
      \reserved@a == FILE
      for \reserved@a := \@partlist
        do if eval(\reserved@a) = eval(\reserved@b)
          then \@tempswa := T fi
        od
      fi
  fi

  if \@tempswa = T
    then \@auxout := \@partaux
      if \@filesw = T
        then \immediate\openout\@partaux{FILE.AUX}
          \immediate\write\@partaux{\relax}
        fi
        \@input{FILE.TEX}
        \clearpage
        \@writeckpt{FILE}
        if @filesw then \closeout \@partaux fi
        \@auxout := \@mainaux
      else \cp@FILE
    fi
  fi
END

\@writeckpt{FILE} ==
BEGIN
  if \@filesw = T
    \immediate\write on file \@partaux:
      \@setckpt{FILE}{
        for \reserved@a := \cl@ckpt
        do \immediate\write on file \@partaux:
          \global\string\setcounter
            {eval(\reserved@a)}{eval(\c@eval(\reserved@a))}
        od
        \immediate\write on file \@partaux: }
  fi
END

```

```

\@setckpt{FILE}{LIST} ==
BEGIN
  G \cp@FILE := LIST
END

INITIALIZATION
  \@tempswa := T

End of historical LATEX 2.09 comments.

\@inputcheck Allocate read stream for testing and output stream.
  \@unused 3 \newread\@inputcheck
            4 \newwrite\@unused

  \@mainaux
  \@partaux 5 \newwrite\@mainaux
            6 \newwrite\@partaux

  \if@filesw
  \if@partsw 7 \newif\if@filesw \@fileswtrue
            8 \newif\if@partsw \@partswfalse

\@clubpenalty This stores the current normal (non-infinite) value of \@clubpenalty; it should
               therefore be reset whenever the normal value is changed (as in the bibliography
               in the standard styles).
               9 \newcount\@clubpenalty
               10 \@clubpenalty \@clubpenalty

\document
  11 \ifx\@clubpenalty\@clubpenalty
  12 \ifx\@clubpenalty\@clubpenalty
  13 \ifx\@clubpenalty\@clubpenalty
  14 \ifx\@clubpenalty\@clubpenalty
  15 \ifx\@clubpenalty\@clubpenalty
  16 \ifx\@clubpenalty\@clubpenalty
  17 \ifx\@clubpenalty\@clubpenalty
  18 \ifx\@clubpenalty\@clubpenalty
  19 \ifx\@clubpenalty\@clubpenalty
  20 \ifx\@clubpenalty\@clubpenalty
  21 \ifx\@clubpenalty\@clubpenalty
  22 \ifx\@clubpenalty\@clubpenalty
  23 \ifx\@clubpenalty\@clubpenalty
  24 \ifx\@clubpenalty\@clubpenalty
  25 \ifx\@clubpenalty\@clubpenalty
  26 \ifx\@clubpenalty\@clubpenalty
  27 \ifx\@clubpenalty\@clubpenalty
  28 \ifx\@clubpenalty\@clubpenalty
  29 \ifx\@clubpenalty\@clubpenalty
  30 \ifx\@clubpenalty\@clubpenalty

Cancel the \begin from \begin.
  15 \def\document{\endgroup

If some options on \documentclass haven't been used by any package we will now
give a warning since this is most certainly a misspelling.
  16 \ifx\@clubpenalty\@clubpenalty
  17 \ifx\@clubpenalty\@clubpenalty
  18 \ifx\@clubpenalty\@clubpenalty
  19 \ifx\@clubpenalty\@clubpenalty
  20 \ifx\@clubpenalty\@clubpenalty
  21 \ifx\@clubpenalty\@clubpenalty
  22 \ifx\@clubpenalty\@clubpenalty
  23 \ifx\@clubpenalty\@clubpenalty
  24 \ifx\@clubpenalty\@clubpenalty
  25 \ifx\@clubpenalty\@clubpenalty
  26 \ifx\@clubpenalty\@clubpenalty
  27 \ifx\@clubpenalty\@clubpenalty
  28 \ifx\@clubpenalty\@clubpenalty
  29 \ifx\@clubpenalty\@clubpenalty
  30 \ifx\@clubpenalty\@clubpenalty

```

```

31   \global \let \@multiplelabels \relax
32   \@input{\jobname.aux}%
33 \endgroup
34 \if@filesw
35   \immediate\openout\@mainaux\jobname.aux
36   \immediate\write\@mainaux{\relax}%
37 \fi

```

Dateline 1991/03/26: FMi added `\process@table` to support NFSS; This will also work with old lfonts if no other style defines `\process@table`. The following line forces the initialization of the math fonts.

```

38   \process@table
39   \let\glb@currsizel@empty % Force math initialization.

40   \normalsize
41   \everypar{}%

```

So that punctuation in headings is not disturbed by verbatim or other local changes to the space factor codes, save the document default here. This will be locally reset by the output routine. For special cases a class may want to define `\normalsfcodes` directly, in case that definition will be used. (This is an old bug, problem existed in L<sup>A</sup>T<sub>E</sub>X2.0x and plain T<sub>E</sub>X.)

```

42   \ifx\normalsfcodes\@empty
43     \ifnum\sfcode'\.=\@m
44       \let\normalsfcodes\frenchspacing
45     \else
46       \let\normalsfcodes\nonfrenchspacing
47   \fi
48 \fi

```

For similar reasons also save the default language, this will be reset locally in the output routine. In particular it allows hyphenation in the page head even if the page break happens in verbatim. If this has already been set by a package, set to the value of `\language` at this point.

```

49   \ifx\document@default@language\m@ne
50     \chardef\document@default@language\language
51   \fi

```

Way back in 1991 (08/26) FMi & RmS set the `\@noskipsec` switch to true in the preamble and to false here. This was done to trap lists and related text in the preamble but it does not catch everything; hence Change 1.1g was introduced.

```

52   \@noskipsecfalse

53   \let \@refundefined \relax

```

Just before disabling the preamble commands we execute the begin document hook which contains any code contributed by `\AtBeginDocument`. Also disable the gathering of the file list, if no `\listfiles` has been issued. `\AtBeginDocument` is redefined at this point so that and such commands that get into the hook do not chase their tail...

```

54   \let\AtBeginDocument\@firstofone
55   \@begindocumenthook

```

Most of the following assignments will be done globally in case the user adds something like `\begin{multicols}` to the document hook, i.e. starts are group in `\begin{document}`.

Since a value of exactly 0pt for `\topskip` causes `\twocolumn[]` to misbehave, we add this check, hoping that it will not cause any problems elsewhere.

```
56 \ifdim\topskip<1sp\global\topskip 1sp\relax\fi
57 \global\@maxdepth\maxdepth
58 \global\let\@begindocumenthook\@undefined
59 \ifx\@listfiles\@undefined
60   \global\let\@filelist\relax
61   \global\let\@addtofilelist\@gobble
62 \fi
```

At the very end we disable all preamble commands. This has to happen after the begin document hooks was executed so that this hook can still use such commands.

```
63 \gdef\do##1{\global\let ##1\@notprerr}%
64 \@preamblecmds
```

The next line saves tokens and also allows `\@nodocument` to be used directly to trap preamble errors.

```
65 \global\let \@nodocument \relax
```

The next line is a pure safety measure in case a do list is ever expanded at the wrong place. In addition it will save a few tokens to get rid of the above definition.

```
66 \global\let\do\noexpand
```

Use of `\AtBeginDocument` hook might mean that we are already in horizontal mode, so ignore the space after `\begin{document}`.

```
67 \ignorespaces}
68 \</2ekernel|latexrelease>
69 \<latexrelease>\EndIncludeInRelease
70 \<latexrelease>\IncludeInRelease{0000/00/00}%
71 \<latexrelease> {\document}{Save language for hyphenation}
72 \<latexrelease>\def\document{\endgroup
73 \<latexrelease> \ifx\@unusedoptionlist\@empty\else
74 \<latexrelease>   \<latex@warning@no@line>{Unused global option(s):^^J%
75 \<latexrelease>     \<spaces>[\@unusedoptionlist]}}%
76 \<latexrelease> \fi
77 \<latexrelease> \<colht>\textheight
78 \<latexrelease> \<colroom>\textheight \<vsize>\textheight
79 \<latexrelease> \<columnwidth>\textwidth
80 \<latexrelease> \<clubpenalty>\clubpenalty
81 \<latexrelease> \if@twocolumn
82 \<latexrelease>   \<advance>\columnwidth -\<columnsep>
83 \<latexrelease>   \<divide>\columnwidth\tw@ \<hsize>\columnwidth
84 \<latexrelease>   \<@firstcolumntrue>
85 \<latexrelease> \fi
86 \<latexrelease> \<hsize>\columnwidth \<linewidth>\hsize
87 \<latexrelease> \<begingroup>\<floatplacement>\<dblfloatplacement>
88 \<latexrelease>   \<makeatletter>\let\<writefile>\<gobbletwo>
89 \<latexrelease>   \global \let \<multiplelabels> \relax
90 \<latexrelease>   \<input>\jobname.aux}%
91 \<latexrelease> \endgroup
92 \<latexrelease> \if@filesw
93 \<latexrelease>   \<immediate>\openout\<mainaux>\jobname.aux
94 \<latexrelease>   \<immediate>\write\<mainaux>\relax}%
95 \<latexrelease> \fi
```

```

96 \latexrelease \process@table
97 \latexrelease \let\glb@currsizel@empty
98 \latexrelease \normalsize
99 \latexrelease \everypar{}%
100 \latexrelease \ifx\normalsfcode@empty
101 \latexrelease \ifnum\scode'\.=\@m
102 \latexrelease \let\normalsfcode\xfrenchspacing
103 \latexrelease \else
104 \latexrelease \let\normalsfcode\nonfrenchspacing
105 \latexrelease \fi
106 \latexrelease \fi
107 \latexrelease \@noskipsecfalse
108 \latexrelease \let \@refundefined \relax
109 \latexrelease \let\AtBeginDocument\@firstofone
110 \latexrelease \@begindocumenthook
111 \latexrelease \ifdim\topskip<1sp\global\topskip 1sp\relax\fi
112 \latexrelease \global\@maxdepth\maxdepth
113 \latexrelease \global\let\@begindocumenthook\@undefined
114 \latexrelease \ifx\@listfiles\@undefined
115 \latexrelease \global\let\@filelist\relax
116 \latexrelease \global\let\@addtofilelist\@gobble
117 \latexrelease \fi
118 \latexrelease \gdef\do##1{\global\let ##1\@notprerr}%
119 \latexrelease \@preamblecmds
120 \latexrelease \global\let \@nodocument \relax
121 \latexrelease \global\let\do\noexpand
122 \latexrelease \ignorespaces}
123 \latexrelease\EndIncludeInRelease
124 (*2ekernel)

125 \@onlypreamble\document

```

**\normalsfcode** The setting of \@empty is just a flag. This command may be defined in a class or package file. If it is still \@empty at \begin{document} it will be defined to be \frenchspacing or \nonfrenchspacing, depending on which of those appears to be in effect at that point.

```
126 \let\normalsfcode@empty
```

**\nofiles** Set \@fileswfalse which suppresses the places where L<sup>A</sup>T<sub>E</sub>X makes \immediate writes. The \makeindex and \makeglossary are disabled. \protected@write is redefined not to write to the file specified, but rather to write a blank line to the log file. This ensures that a *whatsit* node is still created, and so spacing is not affected by the \nofiles command; to ensure this more generally, the \if@nobreak test is needed.

```

127 \def\nofiles{%
128   \@fileswfalse
129   \typeout{No auxiliary output files.^^J}%
130   \long\def\protected@write##1##2##3%
131     {\write\m@ne{}\if@nobreak\ifvmode\nobreak\fi\fi}%
132   \let\makeindex\relax
133   \let\makeglossary\relax}
134 \@onlypreamble\nofiles

```

**\protected@write** This takes three arguments: an output stream, some initialization code, and some

text to write. It then writes this, with appropriate handling of `\protect` and `\thepage`.

```

135 \long\def \protected@write#1#2#3{%
136     \begingroup
137     \let\thepage\relax
138     #2%
139     \let\protect\@unexpandable@protect
140     \edef\reserved@a{\write#1{#3}}%
141     \reserved@a
142     \endgroup
143     \if@nobreak\ifvmode\nobreak\fi\fi
144 }

```

```

145 \let\@auxout=\@mainaux

```

`\includeonly`

```

146 </2ekernel>
147 <*2ekernel | latexrelease>
148 <latexrelease>\IncludeInRelease{2019/10/01}%
149 <latexrelease>           {\includeonly}{Spaces in file names}%
150 \def\includeonly#1{%
151     \@partswtrue
152     \set@curr@file{\zap@space#1 \@empty}%
153     \let\@partlist\@curr@file
154 }
155 \@onlypreamble\includeonly

```

`\include` In the definition of `\include`, `\def\reserved@b` changed to `\edef\reserved@b` to be consistent with the `\edef` in `\includeonly`. (Suggested by Rainer Schöpf & Frank Mittelbach. Change made 20 Jul 88.)

Changed definition of `\include` to allow space at end of file name — otherwise, typing `\include{foo }` would cause L<sup>A</sup>T<sub>E</sub>X to overwrite `foo.tex`. Change made 24 May 89, suggested by Rainer Schöpf and Frank Mittelbach

Made `\include` check for being used inside an `\include`'d file, as this will not work and cause surprising results.

```

156 \def\include#1{\relax
157     \ifnum\@auxout=\@partaux
158         \@latex@error{\string\include\space cannot be nested}\@eha
159     \else
160         \set@curr@file{#1 }%
161         \expandafter\@include\@curr@file
162     \fi}

163 </2ekernel | latexrelease>
164 <latexrelease>\EndIncludeInRelease
165 <latexrelease>\IncludeInRelease{0000/00/00}%
166 <latexrelease>           {\includeonly}{Spaces in file names}%
167 <latexrelease>\def\includeonly#1{%
168 <latexrelease>     \@partswtrue
169 <latexrelease>     \edef\@partlist{\zap@space#1 \@empty}}
170 <latexrelease>
171 <latexrelease>\def\include#1{\relax
172 <latexrelease>     \ifnum\@auxout=\@partaux

```



```

173 \latexrelease) \latexerror{\string\include\space cannot be nested}\@eha
174 \latexrelease) \else \@include#1 \fi}
175 \latexrelease)
176 \latexrelease)\EndIncludeInRelease
177 (*2kernel)

\@include
178 \def\@include#1 {%
179   \clearpage
180   \if@filesw
181     \immediate\write\@mainaux{\string\@input{#1.aux}}%
182   \fi
183   \@tempswatrue
184   \if@partsw
185     \@tempwafalse
186     \edef\reserved@a{\@partlist\do
187       {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
188     \fi
189   \fi
190   \if@tempswa
191     \let\@auxout\@partaux
192     \if@filesw
193       \immediate\openout\@partaux #1.aux
194       \immediate\write\@partaux{\relax}%
195     \fi
196     \input@{#1.tex}%
197     \clearpage
198     \@writeckpt{#1}%
199     \if@filesw
200       \immediate\closeout\@partaux
201     \fi
202   \else
203     \if the file is not included, reset \deadcycles, so that a long list of non-included
204     files does not generate an ‘Output loop’ error.
205     \deadcycles\z@
206     \nameuse{cp@#1}%
207   \fi
208   \let\@auxout\@mainaux}

\@writeckpt
207 \def\@writeckpt#1{%
208   \if@filesw
209     \immediate\write\@partaux{\string\@setckpt{#1}\@charlb}%
210     {\let\@elt\@wckptelt \cl@ckpt}%
211     \immediate\write\@partaux{\@charrb}%
212   \fi}

\@wckptelt
213 \def\@wckptelt#1{%
214   \immediate\write\@partaux{%
215     \string\setcounter{#1}{\the\@nameuse{c@#1}}}}

\@setckpt RmS 93/08/31: introduced \@setckpt
216 \def\@setckpt#1{\global\@namedef{cp@#1}}

```

```

\@charlb The following defines \@charlb and \@charrb to be { and }, respectively with
\@charrb \catcode 11.
217 {\catcode' [=1 \catcode']=2
218 \catcode' {=11 \catcode'}=11
219 \gdef\@charlb[{
220 \gdef\@charrb[]
221 ]% }brace matching

```

## 19.1 Safe Input Macros

`\@curr@file` File name handling is done by generating a `csname` from the provided file name  
`\set@curr@file` (which means that UTF-8 octets gets turned into strings as this is what happens if they appear in a `csname` due to the code in `utf8.def`). By setting `\escapechar` to `-1` we ensure that we don't get a backslash in front. As a result we end up with all characters as catcode 12 (plus spaces). We then sometimes add quotes around the construct (removing any existing inner quotes. Sometimes we only remove the quotes if they have been supplied by the user. There is clearly some room for improvement.

A side effect of the new code is that we will see quotes around file name displays where there haven't been any before.

For compatibility with existing code using `{abc}.tex` or `{one.two}.png` an initial brace group is discarded before expansion and `\string` is applied. The content of the brace group is discarded. This means that a leading space will be lost unless protected (by `{ }` or `" "` or `\space`) but filenames with a space are hopefully rare.

```

222 </2ekernel>
223 <*2ekernel | latexrelease>
224 <latexrelease> \IncludeInRelease{2019/10/01}%
225 <latexrelease>          {\set@curr@file}{Quote file names}%
226 \def\set@curr@file#1{%
227   \begingroup
228     \escapechar\m@ne
229     \xdef\@curr@file{%
230       \expandafter\expandafter\expandafter\unquote@name
231       \expandafter\expandafter\expandafter{%
232         \expandafter\string
233         \csname\@firstofone#1\@empty\endcsname}}%
234   \endgroup
235 }

```

```

\quote@name Quoting spaces
\quote@@name
\unquote@name
a b c      -> "a b c"
"a b c"    -> "a b c"
a" "b" "c -> "a b c"
           -> ""

```

```

236 \def\quote@name#1{"\quote@@name#1@gobble"}
237 \def\quote@@name#1{"#1\quote@@name}

```

and removing quotes ...

```

238 \def\unquote@name#1{\quote@@name#1@gobble}

```

`\IfFileExists`

```
239 \DeclareRobustCommand\IfFileExists[1]{%
240   \set@curr@file{#1}%
241   \expandafter\IfFileExists@\expandafter{\@curr@file}}
```

`\IfFileExists@` Argument #1 is `\@curr@file` so catcode 12 string with no quotes.

```
242 \long\def \IfFileExists@#1#2#3{%
243   \openin\@inputcheck"#1" %
244   \ifeof\@inputcheck
245     \ifx\input@path\@undefined
246       \def\reserved@a{#3}%
247     \else
248       \def\reserved@a{\@iffileonpath{#1}{#2}{#3}}%
249     \fi
250   \else
251     \closein\@inputcheck
252     \edef\@filef@und{"#1" }%
253     \def\reserved@a{#2}%
254   \fi
255   \reserved@a}
```

`\@iffileonpath` If the file is not found by `\openin`, and `\input@path` is defined, look in all the directories specified in `\input@path`.

```
256 \long\def\@iffileonpath#1{%
257   \let\reserved@a\@secondoftwo
258   \expandafter\@tfor\expandafter\reserved@b\expandafter
259     :\expandafter=\input@path\do{%
260     \openin\@inputcheck\expandafter\quote@name\expandafter{\reserved@b#1} %
261     \ifeof\@inputcheck\else
262       \edef\@filef@und{\expandafter\quote@name\expandafter{\reserved@b#1} }%
263       \let\reserved@a\@firstoftwo%
264       \closein\@inputcheck
265       \@break@tfor
266     \fi}%
267   \reserved@a}
```

```
268 </2ekernel | latexrelease>
269 <latexrelease>\EndIncludeInRelease
270 <latexrelease>\IncludeInRelease{0000/00/00}%
271 <latexrelease>          {\set@curr@file}{Quote file names}%
272 <latexrelease>
273 <latexrelease>\let\quote@name\@undefined
274 <latexrelease>\let\quote@@name\@undefined
275 <latexrelease>\let\unquote@name\@undefined
276 <latexrelease>\let\set@curr@file\@undefined
277 <latexrelease>
278 <latexrelease>\let\IfFileExists@\@undefined
279 <latexrelease>
280 <latexrelease>\long\def \IfFileExists#1#2#3{%
281 <latexrelease>   \openin\@inputcheck#1 %
282 <latexrelease>   \ifeof\@inputcheck
283 <latexrelease>     \ifx\input@path\@undefined
284 <latexrelease>       \def\reserved@a{#3}%
285 <latexrelease>     \else
```

```

286 \latexrelease \def\reserved@a{\@iffileonpath{#1}{#2}{#3}}%
287 \latexrelease \fi
288 \latexrelease \else
289 \latexrelease \closein\@inputcheck
290 \latexrelease \edef\@filef@und{#1 }%
291 \latexrelease \def\reserved@a{#2}%
292 \latexrelease \fi
293 \latexrelease \reserved@a}
294 \latexrelease
295 \latexrelease\long\def\@iffileonpath#1{%
296 \latexrelease \let\reserved@a\@secondoftwo
297 \latexrelease \expandafter\@tfor\expandafter\reserved@b\expandafter
298 \latexrelease : \expandafter=\input@path\do{%
299 \latexrelease \openin\@inputcheck\reserved@b#1 %
300 \latexrelease \ifeof\@inputcheck\else
301 \latexrelease \edef\@filef@und{\reserved@b#1 }%
302 \latexrelease \let\reserved@a\@firstoftwo%
303 \latexrelease \closein\@inputcheck
304 \latexrelease \@break@tfor
305 \latexrelease \fi}%
306 \latexrelease \reserved@a}
307 \latexrelease
308 \latexrelease\EndIncludeInRelease
309 \*2ekernel)

```

**\InputIfFileExists** Now define `\InputIfFileExists` to input #1 if it seems to exist. Immediately prior to the input, #2 is executed. If the file #1 does not exist, execute ‘#3’.

```

310 \*2ekernel)
311 \latexrelease\IncludeInRelease{2019/10/01}%
312 \latexrelease {\InputIfFileExists}{Don't lose the file name}%
313 \*2ekernel | \latexrelease
314 % \begin{macrocode}
315 \DeclareRobustCommand \InputIfFileExists[2]{%
316 \IfFileExists{#1}%
317 {%
318 \expandafter\@swaptwoargs\expandafter
319 {\@filef@und}{#2\@addtofilelist{#1}\@input}}

```

**\@swaptwoargs** Swap two arguments and return them unbraced (like `\@firstoftwo` etc).

```

320 \long\def\@swaptwoargs#1#2{#2#1}

321 \*2ekernel | \latexrelease
322 \latexrelease\EndIncludeInRelease
323 \latexrelease\IncludeInRelease{0000/00/00}%
324 \latexrelease {\InputIfFileExists}{Don't lose the file name}%
325 \latexrelease\long\def \InputIfFileExists#1#2{%
326 \latexrelease \IfFileExists{#1}%
327 \latexrelease {\#2\@addtofilelist{#1}\@input \@filef@und}}
328 \latexrelease
329 \latexrelease\let\@swaptwoargs\@undefined
330 \latexrelease\EndIncludeInRelease
331 \*2ekernel)

```

**\input** Input a file: if the argument is given in braces use safe input macros, otherwise use  $\text{\TeX}$ ’s primitive `\input` command (which is called `\@input` in  $\text{\LaTeX}$ ).

```

332 \def\input{\@ifnextchar\bgroup\@iinput\@@input}

\@iinput Define \@iinput (i.e., \input) in terms of \InputIfFileExists.
333 \kernel
334 \*kernel | latexrelease
335 \latexrelease\IncludeInRelease{2019/10/01}%
336 \latexrelease\@iinput{Quote file names}%
337 \def\@iinput#1{%
338   \InputIfFileExists{#1}{}%
339   {\filename@parse\@curr@file
340     \edef\reserved@a{\noexpand\@missingfileerror
341       {\filename@area\filename@base}%
342       {\ifx\filename@ext\relax tex\else\filename@ext\fi}}%
343     \reserved@a}}
344 \kernel | latexrelease
345 \latexrelease\EndIncludeInRelease
346 \latexrelease\IncludeInRelease{0000/00/00}%
347 \latexrelease\@iinput{Quote file names}%
348 \latexrelease\def\@iinput#1{%
349 \latexrelease\@InputIfFileExists{#1}{}%
350 \latexrelease\{\filename@parse{#1}%
351 \latexrelease\@edef\reserved@a{\noexpand\@missingfileerror
352 \latexrelease\{\filename@area\filename@base}%
353 \latexrelease\{\ifx\filename@ext\relax tex\else\filename@ext\fi}}%
354 \latexrelease\@reserved@a}}
355 \latexrelease\EndIncludeInRelease
356 \*kernel

\@input Define \@input in terms of \IfFileExists. So this is a ‘safe input’ command,
but the files input are not listed by \listfiles.
We don’t want .aux, .toc files etc be listed by \listfiles. However, some-
thing like .bbl probably should be listed and thus should be implemented not by
\@input.
357 \def\@input#1{%
358   \IfFileExists{#1}{\@input\@filef@und}{\typeout{No file #1.}}}

\@input@ Version of \@input that does add the file to \@filelist.
359 \def\@input@#1{\InputIfFileExists{#1}{\typeout{No file #1.}}}

\@missingfileerror This ‘error’ command avoids TeX’s primitive missing file loop.
Missing file error. Prompt for a new filename, offering a default extension.
360 \gdef\@missingfileerror#1#2{%
361   \typeout{^^J! LaTeX Error: File ‘#1.#2’ not found.^^J^^J%
362   Type X to quit or <RETURN> to proceed,^^J%
363   or enter new name. (Default extension: #2)^^J}%
364   \message{Enter file name: }%
365   {\endlinechar@m@ne
366     \global\read@m@ne to\@gtempa}%
367   \ifx\@gtempa\@empty
368     \else
369     \def\reserved@a{x}\ifx\reserved@a\@gtempa\batchmode\@end\fi
370     \def\reserved@a{X}\ifx\reserved@a\@gtempa\batchmode\@end\fi
371     \filename@parse\@gtempa

```

```

372 \edef\filename@ext{%
373 \ifx\filename@ext\relax#2\else\filename@ext\fi}%
374 \edef\reserved@a{%
375 \noexpand\inputIfFileExists
376 {\filename@area\filename@base.\filename@ext}%
377 }%
378 {\noexpand\@missingfileerror
379 {\filename@area\filename@base}{\filename@ext}}}%
380 \reserved@a
381 \fi}

```

**\@obsoletefile** For compatibility with L<sup>A</sup>T<sub>E</sub>X 2.09 document styles, we distribute files called `article.sty`, `book.sty`, `report.sty`, `slides.sty` and `letter.sty`. These use the command `\@obsoletefile`, which produces a warning message.

```

382 \def\@obsoletefile#1#2{%
383 \latex@warning@no@line{inputting ‘#1’ instead of obsolete ‘#2’}}
384 \@onlypreamble\@obsoletefile

```

## 19.2 Listing files

**\@filelist** A list of files input so far. The initial value of `\@gobble` eats the comma before the first file name.

```

385 \let\@filelist\@gobble

```

**\@addtofilelist** Add to the list of files input so far. This ‘real’ definition is only used for ‘cfg’ files during `initex`. An initial definition of `\@gobble` has already been set.

```

386 %\def\@addtofilelist#1{\xdef\@filelist{\@filelist,#1}}

```

**\listfiles** A preamble command to cause `\end{document}` to list files input from the main file.

```

387 \def\listfiles{%
388 \let\listfiles\relax
389 \def\@listfiles##1##2##3##4##5##6##7##8##9\@{%
390 \def\reserved@d{\}%
391 \tfor\reserved@c:=##1##2##3##4##5##6##7##8\do{%
392 \ifx\reserved@c\reserved@d
393 \edef\filename@area{ \filename@area}%
394 \fi}}%

395 \def\@dofilelist{%
396 \typeout{^^J *File List*}%
397 \@for\@currname:=\@filelist\do{%
398 \filename@parse\@currname
399 \edef\reserved@a{%
400 \filename@base.%
401 \ifx\filename@ext\relax tex\else\filename@ext\fi}%
402 \expandafter\let\expandafter\reserved@b
403 \csname ver@\reserved@a\endcsname
404 \expandafter\expandafter\expandafter\@listfiles\expandafter
405 \filename@area\filename@base\////////////////////////////////\@
406 \typeout{%
407 \filename@area\reserved@a
408 \ifx\reserved@b\relax\else\@spaces\reserved@b\fi}}%
409 \typeout{ *****^^J}}

```

The `\@filelist` will be de-activated if `\listfiles` does not appear in the preamble. `\begin{document}` contains code equivalent to the following:

```
\AtBeginDocument{%
  \ifx\@listfiles\@undefined
    \let\@filelist\relax
    \let\@addtofilelist\@gobble
  \fi}

410 \@onlypreamble\listfiles

\@dofilelist

411 \let\@dofilelist\relax

412 \</2kernel>
```

## File 1

# ltoutenc.dtx

## 20 Font encodings

This section of the kernel contains commands for declaring encoding-specific commands, such as accents. It also contains the code for some of the encoding files, including `omlenc.def`, `omsenc.def`, `t1enc.def` and `ot1enc.def` files, which define the OLM, OMS, T1 and OT1 encodings, and the `fontenc` package for selecting encodings.

The `fontenc` package has options for encodings, of which the last option is the default encoding. For example, to use the OT2, OT3 and T1 encodings, with T1 as the default, you say:

```
\usepackage[OT2,OT3,T1]{fontenc}
```

The standard kernel set-up loads font encoding files and selects an encoding as follows.

```
\input {omlenc.def}
\input {t1enc.def}
\input {ot1enc.def}
\input {omsenc.def}
\fontencoding{OT1}
```

Note that the files in the standard `inputenc` package depend on this behaviour of the kernel.

The syntax for declaring encoding-specific commands is:

```
\DeclareTextCommand{<command>}{<encoding>}
                        [<number>] [<default>] {<commands>}
```

This command is like `\newcommand`, except that it defines a command which is specific to one encoding. The resulting command is always robust, even if its definition is fragile. For example, the definition of `\l` in the OT1 encoding is:

```
\DeclareTextCommand{\l}{OT1}{\@xxxii l}
```

`\DeclareTextCommand` takes the same optional arguments as `\newcommand`.

```
\ProvideTextCommand{<command>}{<encoding>}
                        [<number>] [<default>] {<commands>}
```

This acts like `\DeclareTextCommand`, but does nothing if the command is already defined.

```
\DeclareTextSymbol{<command>}{<encoding>}{<slot>}
```

This command defines a text symbol, with a particular slot in that encoding. The commands:

```
\DeclareTextSymbol{\ss}{OT1}{25}
\DeclareTextCommand{\ss}{OT1}{\char25 }
```



have the same effect, but the `\DeclareTextSymbol` is faster.

```
\DeclareTextAccent{<command>}{<encoding>}{<slot>}
```

This command declares a text accent. The commands:

```
\DeclareTextAccent{"}{OT1}{127}
\DeclareTextCommand{"}{OT1}{\add@accent {127}}
```

have the same effect.

```
\DeclareTextComposite{<command>}{<encoding>}{<argument>}{<slot>}
```

This command declares a composite letter, for example in the T1 encoding `\'a` is slot 225, which is declared by:

```
\DeclareTextComposite{\'}{T1}{a}{225}
```

The *command* will normally have been declared with `\DeclareTextAccent`, or as a one-argument `\DeclareTextCommand`.

`\DeclareTextComposite` is the most common example of using the more general declaration `\DeclareTextCompositeCommand`, which can define a composite to be an arbitrary piece of text.

```
\DeclareTextCompositeCommand{<command>}{<encoding>}{<argument>}{<text>}
```

For example, in the OT1 encoding Å has a hand-crafted definition this is declared as follows

```
\DeclareTextCompositeCommand{\r}{OT1}{A}
{\leavevmode\setbox\z@\hbox{!}\dimen@ \ht\z@\advance\dimen@-1ex%
\rlap{\raise.67\dimen@\hbox{\char23}}A}
```

The *command* will normally have been declared with `\DeclareTextAccent`, or as a one-argument `\DeclareTextCommand`.

The commands defined using the above declarations can be used in two ways. Normally they are used by just calling the command in the appropriate encoding, for example `\ss`. However, sometimes you may wish to use a command in an encoding where it is not defined. If the command has no arguments, then you can use it in another encoding by calling `\UseTextSymbol`:

```
\UseTextSymbol{<encoding>}{<command>}
```

For example, `\UseTextSymbol{OT1}{\ss}` has the same effect as:

```
{\fontencoding{OT1}\selectfont\ss}
```

If the command has one argument then you can use it in another encoding by calling `\UseTextAccent`:

```
\UseTextAccent{<encoding>}{<command>}{<text>}
```

For example, if the current encoding is OT2 then `\UseTextAccent{OT1}{\'a}` has the same effect as:

```
{\fontencoding{OT1}\selectfont\'{\fontencoding{OT2}\selectfont a}}
```

You can also declare a default definition for a text command, which will be used if the current encoding has no appropriate definition. Such use will also set the definition for this command in the current encoding to equal this default definition; this makes subsequent uses of the command much faster.

```
\DeclareTextCommandDefault{<command>}{<definition>}
```

For example, the default definition of the command `\textonequarter` (which produces the fraction  $\frac{1}{4}$ ) could be built using math mode:

```
\DeclareTextCommandDefault{\textonequarter}{\ensuremath {\frac{1}{4}}}
```

There is a matching `\Provide` command which will not override an existing default definition:

```
\ProvideTextCommandDefault{<command>}{<definition>}
```

The most common use for these commands is to use symbols from other encodings, so there are some optimizations provided:

```
\DeclareTextSymbolDefault{<command>}{<encoding>}
\DeclareTextAccentDefault{<command>}{<encoding>}
```

are short for:

```
\DeclareTextCommandDefault{<command>}
      {\UseTextSymbol{<encoding>}{<command>}}
\DeclareTextCommandDefault[1]{<command>}
      {\UseTextAccent{<encoding>}{<command>}{#1}}
```

For example, to make OT1 the default encoding for `\ss` and `\'` you say:

```
\DeclareTextSymbolDefault{\ss}{OT1}
\DeclareTextAccentDefault{\'}{OT1}
```

Note that you can use these commands on any zero- or one-argument commands declared with `\DeclareText*` or `\ProvideText*`, not just those defined using `\DeclareTextSymbol` or `\DeclareTextAccent`.

## 20.1 Removing encoding-specific commands

In some cases encoding definitions are given to provide some limited support since nothing better is available, for example, the definition for `\textdollar` in OT1 is a hack since \$ and £ actually share the same slot in this encoding. Thus if such a glyph becomes available in a different encoding (e.g., TS1) one would like to get rid of the flaky one and make the default definition point to the new encoding. In such a case defining

```
\DeclareTextSymbol{\textdollar}{TS1}{36}
\DeclareTextSymbolDefault{\textdollar}{TS1}
```

is not enough since if typesetting in OT1  $\LaTeX$  will still find the encoding specific-definition for OT1 and therefore ignore the new default. Therefore to ensure that in this case the TS1 version is used we have to remove the OT1 declaration:

```
\UndeclareTextCommand{\textdollar}{OT1}
```

Since the \$ sign is a proper glyph in the T1 encoding there is no point removing its definition and forcing L<sup>A</sup>T<sub>E</sub>X to pick up the TS1 version if typesetting in this encoding. However, assume you want to use the variant dollar sign, i.e., \$ for your dollars. In that case you have to get rid of the T1 declaration as well, e.g., the following would do that for you:

```
\UndeclareTextCommand{\textdollar}{OT1}
\UndeclareTextCommand{\textdollar} {T1}
\DeclareTextCommandDefault{\textdollar}
{\UseTextSymbol{TS1}\textdollaroldstyle}
```

## 20.2 The order of declarations

If an encoding-specific command is defined for more than one encoding, then it will execute fastest in the encoding in which it was defined last since its top-level definition will be set up to execute in that encoding without any overhead.

For this reason the file `fonttext.ltx` currently first loads the definitions for the T1 encoding and then those for the OT1 encoding so that typesetting in OT1 is optimized since that is (still) the default. However, when T1 is explicitly requested (via `\usepackage[T1]{fontenc}`) the top-level definitions are automatically changed to favour T1 since its declarations are reloaded in the process.

For the same reason default declarations should never come last since they are implemented as a special encoding themselves (with the name ?). Specifying them last would simply mean to make those encoding-specific commands equally inefficient in all encodings. Therefore the `textcomp` package, for example, first sets up all defaults to point to TS1 and then declares the commands in the TS1 encoding.

## 20.3 Docstrip modules

This `.dtx` file is be used to generate several related files containing font encoding definitions. The mutually exclusive docstrip options are listed here.

T1	generates <code>t1enc.def</code> for the Cork encoding.
TS1	generates <code>ts1enc.def</code> for the Text Companion encoding.
TS1sty	generates <code>textcomp.sty</code> , package that sets up use of the Text Companion encoding.
OT1	generates <code>ot1enc.def</code> for Knuth's CM encoding.
OMS	generates <code>omsenc.def</code> for Knuth's math symbol encoding.
OML	generates <code>omlenc.def</code> for Knuth's math letters encoding.
OT4	generates <code>ot4enc.def</code> for the Polish extension to the OT1 encoding, created by B. Jackowski and M. Ryćko for use with the Polish version of Computer Modern and Computer Concrete.
TU	generates <code>tuenc.def</code> for Unicode font encoding.
package	generates <code>fontenc.sty</code> for selecting encodings.
2ekernel	for the kernel commands.

## 20.4 Definitions for the kernel

### 20.4.1 Declaration commands

This section contains definitions for commands such as accents which depend on the current encoding. These commands will usually be kept in `.def` files, for example `ot1enc.def` contains the definitions for the OT1 encoding.

```
1 (*2kernel)
2 \message{font encodings,}

Far too many macros in one block here!
```

```
\DeclareTextCommand If you say:
\ProvideTextCommand
\DeclareTextSymbol
\@dec@text@cmd then \foo is defined to be \T1-cmd \foo \T1\foo, where \T1\foo is one control
\chardef@text@cmd sequence, not two! We then call \newcommand to define \T1\foo.
\@changed@cmd
\@changed@x
\TextSymbolUnavailable
\@inmathwarn

3 \def\DeclareTextCommand{%
4   \@dec@text@cmd\newcommand}

5 \def\ProvideTextCommand{%
6   \@dec@text@cmd\providecommand}

7 \def\@dec@text@cmd#1#2#3{%
8   \expandafter\def\expandafter#2%
9     \expandafter{%
10       \csname#3-cmd\expandafter\endcsname
11       \expandafter#2%
12       \csname#3\string#2\endcsname
13     }%
14   \let\@ifdefinable\@rc@ifdefinable
15   \expandafter#1\csname#3\string#2\endcsname}
```

This command was introduced to fix a major bug in `\@dec@text@cmd` without changing that command itself. This was thought to be necessary because it is defined in more than one package. (Perhaps the more serious bug is to put complex low-level commands like this in packages?)

The problem it solves is that whereas both `\newcommand` and `\providecommand` (used just above) both handle the resetting of `\@ifdefinable` (following its disabling in `\@dec@text@cmd`), the primitive `\chardef` neither needs the disabling, nor does the resetting.

```
16 \def\chardef@text@cmd{%
17   \let\@ifdefinable\@@ifdefinable
18   \chardef
19 }
20 \def\DeclareTextSymbol#1#2#3{%
21   \@dec@text@cmd\chardef@text@cmd#1{#2}#3\relax
22 }
```

The declarations are only available before `\begin{document}`.

```
23 \@onlypreamble\DeclareTextCommand
24 \@onlypreamble\DeclareTextSymbol
```

The sneaky bit in all this is what `\T1-cmd \foo \T1\foo` does. There are five possibilities, depending on the current values of `\protect`, `\cf@encoding` and `\ifmmode`:

- If `\protect` is `\@typeset@protect` and `\cf@encoding` is T1, then we execute `\T1\foo`. This should be the normal behaviour, and is optimized for speed.
- If `\protect` is `\@typeset@protect`, `\cf@encoding` is (say) OT1, and `\OT1\foo` is defined, then we execute `\OT1\foo`.
- If `\protect` is `\@typeset@protect`, `\cf@encoding` is (say) OT1, we're in text mode, and `\OT1\foo` is undefined, then we define `\OT1\foo` to be the default value of `\foo`, and execute `\OT1\foo`.
- If `\protect` is `\@typeset@protect`, `\cf@encoding` is (say) OT1, we're in math mode, and `\OT1\foo` is undefined, then we execute the default value of `\foo`. (This is necessary so that things like `$X_\copyright$` work properly.)
- If `\protect` is not `\@typeset@protect` then we execute `\noexpand\foo`. For example, if we are writing to a file, then this results in `\foo` being written. If we are in a `\mark`, then `\foo` will be put in the mark—since `\foo` is robust, it will then survive all the things which may happen to it whilst it's a `\mark`.

So after all that, we will either execute the appropriate definition of `\foo` for the current encoding, or we will execute `\noexpand\foo`.

The default value of `\foo` is `\?\foo` if it is defined, and an error message otherwise.

When the encoding is changed from T1 to OT1, `\T1-cmd` is defined to be `\@changed@cmd` and `\OT1-cmd` is defined to be `\@current@cmd`. This means that the test for what the current encoding is can be performed quickly.

```

25 \def\@current@cmd#1{%
26   \ifx\protect\@typeset@protect
27     \inmathwarn#1%
28   \else
29     \noexpand#1\expandafter\@gobble
30   \fi}

31 \def\@changed@cmd#1#2{%
32   \ifx\protect\@typeset@protect
33     \inmathwarn#1%
34     \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
35       \expandafter\ifx\csname ?\string#1\endcsname\relax
36         \expandafter\def\csname ?\string#1\endcsname{%
37           \TextSymbolUnavailable#1%
38         }%
39       \fi
40       \global\expandafter\let
41         \csname\cf@encoding\string#1\expandafter\endcsname
42         \csname ?\string#1\endcsname
43       \fi
44       \csname\cf@encoding\string#1%
45         \expandafter\endcsname
46     \else
47       \noexpand#1%
48     \fi}

49 \gdef\TextSymbolUnavailable#1{%

```

```

50 \latex@error{%
51   Command \protect#1 unavailable in encoding \cf@encoding%
52 }\@eha}

```

The command `\@inmathwarn` produces a warning message if we are currently in math mode. Note that since this command is used inside text commands, it can't call `\relax` before the `\ifmmode`. This means that it is possible for the warning to fail to be issued at the beginning of a row of an `halign` whose template enters math mode. This is probably a bad feature, but there's not much that can be done about it, since adding a `\relax` would break ligatures and kerning between text symbols.

A more efficient solution would be to make `\@inmathwarn` and `\@inmatherr` equal to `\@empty` and `\relax` by default, and to have `\everymath` reset them to their usual definitions. This is left for future investigation (for example it may break some third party code).

```

53 \def\@inmathwarn#1{%
54   \ifmmode
55     \latex@warning{Command \protect#1 invalid in math mode}%
56   \fi}

```

`\DeclareTextCommandDefault` These define commands with encoding ?.

`\ProvideTextCommandDefault` Note that `\DeclareTextCommandDefault` can only be used in the preamble, but that the `\Provide` version is allowed in inputenc .def files, so is allowed anywhere.

```

57 \def\DeclareTextCommandDefault#1{%
58   \DeclareTextCommand#1?}

59 \def\ProvideTextCommandDefault#1{%
60   \ProvideTextCommand#1?}

61 \@onlypreamble\DeclareTextCommandDefault
62 %\@onlypreamble\ProvideTextCommandDefault

```

They require `\?-cmd` to be initialized as `\@changed@cmd`.

```

63 \expandafter\let\csname?\-cmd\endcsname\@changed@cmd

```

`\DeclareTextAccent` This is just a disguise for defining a TeX `\accent` command.

```

64 \def\DeclareTextAccent#1#2#3{%
65   \DeclareTextCommand#1{#2}{\add@accent{#3}}
66 \@onlypreamble\DeclareTextAccent

```

`\add@accent` To save space this code is shared between all text accents that are set using the `\accent` primitive. The argument is pre-set in a box so that any font loading that is needed is already done within the box. This is needed because font-loading involves grouping and that would prevent the accent mechanism from working so that the accent would not be positioned over the argument. Declarations that change the font should be allowed (only low-level ones are at present) inside the argument of an accent command, but not size changes, as they involve `\setbox` operations which also inhibit the mechanism of the `\accent` primitive.

Note that the whole process is within a group. For a detailed discussion of this reimplementaion and its deficiencies, see pr/3160.

```

67 \def\add@accent#1#2{\hmode@bgroup

```

Turn off the group in `\UseTextSymbol` in case this is used inside the argument of `\add@accent`.

```
68 \let\hmode@start@before@group\@firstofone
69 \setbox\@tempboxa\hbox{#2}
```

When presetting the argument in a box we record its `\spacefactor` for later use after the accent got typeset. This way something like `\‘A` gets the spacefactor of `A` (i.e., 999) rather than the default value of 1000.

```
70 \global\mathchardef\accent@spacefactor\spacefactor}%
71 \accent#1 #2\egroup\spacefactor\accent@spacefactor}
```

Default definition for `\accent@spacefactor` prevents a horrible death of the above macro inside an unprotected `\edef`.

```
72 \let\accent@spacefactor\relax
```

`\hmode@bgroup`

```
73 \def\hmode@bgroup{\leavevmode\bgroup}
```

`\DeclareTextCompositeCommand` Another amusing game to play with `\expandafter`, `\csname`, and `\string`. When you say `\DeclareTextCompositeCommand{\foo}{T1}{a}{bar}`, we look to see if the expansion of `\T1\foo` begins with `\@text@composite`, and if it doesn't, we redefine `\T1\foo` to be:

```
\@text@composite@x
\@strip@args
#1 -> \@text@composite \T1\foo #1\@empty \@text@composite {...}
```

where `...` is the previous definition of `\T1\foo`. Finally, we define `\T1\foo-a` to expand to `bar`.

```
74 \</2ekernel>
75 \<latexrelease>\IncludeInRelease{2017/04/15}{\DeclareTextCompositeCommand}
76 \<latexrelease> \test for undeclared accent}%
77 \<*2ekernel | latexrelease>
78 \def\DeclareTextCompositeCommand#1#2#3#4{%
79 \expandafter\let\expandafter\reserved@a\csname#2\string#1\endcsname
80 \ifx\reserved@a\relax
81 \DeclareTextCommand#1{#2}{%
82 \@latex@error{\string#1 undeclared in encoding #2}\@eha}%
83 \@latex@info{Composite with undeclared \string#1 in encoding #2}%
84 \expandafter\let\expandafter\reserved@a\csname#2\string#1\endcsname
85 \fi
86 \expandafter\expandafter\expandafter\ifx
87 \expandafter\@car\reserved@a\relax\relax\@nil \@text@composite \else
88 \edef\reserved@b##1{%
89 \def\expandafter\noexpand
90 \csname#2\string#1\endcsname###1{%
91 \noexpand\@text@composite
92 \expandafter\noexpand\csname#2\string#1\endcsname
93 ###1\noexpand\@empty\noexpand\@text@composite
94 {##1}}}%
95 \expandafter\reserved@b\expandafter{\reserved@a{##1}}%
96 \fi
97 \expandafter\def\csname\expandafter\string\csname
98 #2\endcsname\string#1-\string#3\@empty\endcsname{#4}%
99 }
100 \</2ekernel | latexrelease>
```

```

101 \latexrelease\EndIncludeInRelease
102 \latexrelease\IncludeInRelease{0000/00/00}{\DeclareTextCompositeCommand}
103 \latexrelease\{test for undeclared accent}%
104 \latexrelease\def\DeclareTextCompositeCommand#1#2#3#4{%
105 \latexrelease\expandafter\let\expandafter\reserved@a
106 \latexrelease\csname#2\string#1\endcsname
107 \latexrelease\expandafter\expandafter\expandafter\ifx
108 \latexrelease\expandafter\@car\reserved@a\relax\relax\@nil
109 \latexrelease\@text@composite \else
110 \latexrelease\edef\reserved@b##1{%
111 \latexrelease\def\expandafter\noexpand
112 \latexrelease\csname#2\string#1\endcsname###1{%
113 \latexrelease\noexpand\@text@composite
114 \latexrelease\expandafter\noexpand\csname#2\string#1\endcsname
115 \latexrelease###1\noexpand\@empty\noexpand\@text@composite
116 \latexrelease{##1}}}%
117 \latexrelease\expandafter\reserved@b\expandafter{\reserved@a{##1}}%
118 \latexrelease\fi
119 \latexrelease\expandafter\def\csname\expandafter\string\csname
120 \latexrelease#2\endcsname\string#1-\string#3\@empty\endcsname{#4}}
121 \latexrelease\EndIncludeInRelease
122 (*2kernel)

123 \onlypreamble\DeclareTextCompositeCommand

```

This all works because:

```
\@text@composite \T1\foo A\@empty \@text@composite {...}
```

expands to `\T1\foo-A` if `\T1\foo-A` has been defined, and `{...}` otherwise.

Note that `\@text@composite` grabs the first token of the argument and puts just that in the csname. This is so that `\'\textit{e}` will work—it checks whether `\T1\'-\textit` is defined (which presumably it isn't) and so expands to `{\accent 1 \textit{e}}`.

This trick won't always work, for example `\'\{itshape e}` will expand to (with spaces added for clarity):

```
\csname \string \T1\' - \string {itshape e} \@empty \endcsname
```

which will die pretty horribly. Unfortunately there's not much can be done about this if we're going to use `\csname` lookups as a fast way of accessing composites.

This has an unfortunate 'misfeature' though, which is that in the T1 encoding, `\'{aa}` produces á. This is not the expected behaviour, and should perhaps be fixed if the fix doesn't affect performance too badly.

Finally, it's worth noting that the `\@empty` is used in `\@text@composite` so that accents will work even when the argument is empty. If you say `\'` then this looks up `\T1\'-\@empty`, which ought to be `\relax`, and so all is well. If we didn't include the `\@empty`, then `\'` would expand to:

```
\csname \string \T1\' - \string \endcsname
```

so the `\endcsname` would be `\string`'ed and the whole of the rest of the document would be put inside the `\csname`. This would not be good.

```

124 \def\@text@composite#1#2#3\@text@composite{%
125 \expandafter\@text@composite@x
126 \csname\string#1-\string#2\endcsname}

```



Originally the `\@text@composite@x` macro had two arguments and if #1 was not `\relax` it was executed, otherwise #2 was executed. All this happened within the `\ifx` code so that neither #1 nor #2 could have picked up any additional arguments from the input stream. This has now been changed using the typical `\@firstoftwo / \@secondoftwo` coding. This way the final expansion will happen without any `\else` or `\fi` intervening in the case that we need to get a further token from the input stream.

```
127 \def\@text@composite@x#1{%
128   \ifx#1\relax
129     \expandafter\@secondoftwo
130   \else
131     \expandafter\@firstoftwo
132   \fi
133   #1}
```

The command `\DeclareTextComposite` uses `\DeclareTextCompositeCommand` to declare a command which expands out to a single glyph.

```
134 \catcode\z@=11\relax

135 \def\DeclareTextComposite#1#2#3#4{%
136   \def\reserved@a{\DeclareTextCompositeCommand#1{#2}{#3}}%
137   \bgroup
138     \lccode\z@#4%
139     \lowercase{%
140       \egroup
141       \reserved@a ^^@}}

142 \catcode\z@=15\relax

143 \@onlypreamble\DeclareTextComposite

144 </2ekernel>
145 <*2ekernel | latexrelease>
146 <latexrelease>\IncludeInRelease{2019/10/01}%
147 <latexrelease>          {\UseTextAccent}{Make commands robust}%
```

<code>\UseTextAccent</code> <code>\UseTextSymbol</code> <code>\@use@text@encoding</code>	<p>These fragile commands access glyphs from different encodings. They use grotty low-level calls to the font selection scheme for speed, and in order to make sure that <code>\UseTextSymbol</code> doesn't do anything which you're not allowed to do between an <code>\accent</code> and its glyph.</p>
--	--

For a detailed discussion of this reimplementaion and its deficiencies, see [pr/3160](#).

```
148 \DeclareRobustCommand\UseTextAccent[3]{%
149   \hmode@start@before@group
150   {%
```

Turn off the group in `\UseTextSymbol` in case this is used inside the arguments of `\UseTextAccent`.

```
151   \let\hmode@start@before@group\@firstofone
152   \let\@curr@enc\cf@encoding
153   \@use@text@encoding{#1}%
154   #2{\@use@text@encoding\@curr@enc#3}%
155   }}
```

```
156 \DeclareRobustCommand\UseTextSymbol[2]{%
157   \hmode@start@before@group
```

```

158      {%
159        \def\@wrong@font@char{\MessageBreak
160          for \noexpand\symbol'\string#2'}%
161        \@use@text@encoding{#1}%
162        #2%
163      }%
164    }
165  /2kernel | latexrelease)
166 (latexrelease)\EndIncludeInRelease
167 (latexrelease)\IncludeInRelease{0000/00/00}%
168 (latexrelease)      {\UseTextAccent}{Make commands robust}%
169 (latexrelease)
170 (latexrelease)\kernel@make@fragile\UseTextAccent
171 (latexrelease)\kernel@make@fragile\UseTextSymbol
172 (latexrelease)
173 (latexrelease)\EndIncludeInRelease
174 (*2kernel)
175 \def\@use@text@encoding#1{%
176   \edef\f@encoding{#1}%
177   \xdef\font@name{%
178     \csname\curr@fontshape/\f@size\endcsname}%
179   \pickup@font
180   \font@name
181   \@enc@update}

```

`\hmode@start@before@group` The `\hmode@start@before@group` starts hmode and should be immediately followed by an explicit `{...}`. Its purpose is to ensure that hmode is started before this group is opened. Inside `\add@accent` and `\UseTextAccent` it is redefined to remove this group so that it doesn't conflict with the `\accent` primitive.

For a detailed discussion see pr/3160.

```
182 \let\hmode@start@before@group\leavevmode
```

`\DeclareTextSymbolDefault` Some syntactic sugar. Again, these should probably be optimized for speed.

```

\DeclareTextAccentDefault 183 \def\DeclareTextSymbolDefault#1#2{%
184   \DeclareTextCommandDefault#1{\UseTextSymbol{#2}#1}}
185 \def\DeclareTextAccentDefault#1#2{%
186   \DeclareTextCommandDefault#1{\UseTextAccent{#2}#1}}
187 \@onlypreamble\DeclareTextSymbolDefault
188 \@onlypreamble\DeclareTextAccentDefault

```

`\UndeclareTextCommand` This command safely removes an encoding specific declaration for a given encoding. It is helpful if one intends to use the default definition always and therefore wants to get rid of a declaration for some specific encoding.

```
189 \def\UndeclareTextCommand#1#2{%
```

If there is no declaration for the current encoding do nothing. (This makes a hash table entry but without eTeX we can't do anything about that).

```

190   \expandafter\ifx\csname#2\string#1\endcsname\relax
191   \else

```

Else: throw away that declaration.

```

192     \global\expandafter\let\csname#2\string#1\endcsname
193     \@undefined

```

But this is unfortunately not enough, we have to take a look at the top-level definition of the encoding specific command which for a command `\foo` would look similar to `\T1-cmd \foo \T1\foo` (three tokens).

Of course, instead of `T1` one could see a different encoding name; which one depends the encoding for which `\foo` was declared last.

Now assume we have just removed the declaration for `\foo` in `T1` and the top-level of `\foo` expands to the above. Then we better change that pretty fast otherwise we do get an “undefined csname error” when we try to typeset `\foo` within `T1` instead of getting the default definition for `\foo`. And what is the best way to change that top-level definition? Well, the only “encoding” we know for sure will still be around is the default encoding denoted by `?`.

Thus in case the last token of the top-level expansion is now undefined we change the declaration to look like `\?-cmd \foo \?\foo` which is done by the following (readable?) code:

```

194     \expandafter\expandafter\expandafter
195     \ifx\expandafter\@thirdofthree#1\@undefined
196     \expandafter\gdef\expandafter#1\expandafter
197         {\csname ?-cmd\expandafter\endcsname\expandafter
198          #1\csname?\string#1\endcsname}%
199     \fi
200 \fi
201 }
202 \@onlypreamble\UndeclareTextCommand

```

## 20.4.2 Hyphenation

<code>\patterns</code> <code>\@patterns</code> <code>\hyphenation</code> <code>\@hyphenation</code>	<p>We redefine <code>\patterns</code> and <code>\hyphenation</code> to allow the use of commands declared with <code>\DeclareText*</code> to be used inside them.</p> <pre> 203 %\let\@patterns\patterns 204 %\let\@hyphenation\hyphenation 205 %\def\patterns{% 206 %    \bgroup 207 %        \let\protect\@empty 208 %        \let\@typeset@protect\@empty 209 %        \let\@changed@x\@changed@x@mouth 210 %    \afterassignment\egroup 211 %    \@patterns 212 %} 213 %\def\hyphenation{% 214 %    \bgroup 215 %        \let\protect\@empty 216 %        \let\@typeset@protect\@empty 217 %        \let\@changed@x\@changed@x@mouth 218 %    \afterassignment\egroup 219 %    \@hyphenation 220 %} </pre>
--	--

## 20.4.3 Miscellanea

- `\a` The `\a` command is used to access the accent commands even when they have been redefined (for example by the `tabbing` environment). Its internal name is `\@tabacckludge`.

The `\string` within the `\csname` guards against something like `'` being active at the point of use.

```
221 \def\@tabacckludge#1{\expandafter\@changed@cmd
222                               \csname\string#1\endcsname\relax}
223 \let\@=\@tabacckludge
```

#### 20.4.4 Default encodings

We define the default encodings for most commands to be either OT1, OML or OMS. These defaults are in the kernel and therefore fonts with these encodings must be available unless these defaults are redefined elsewhere. Recall that the standard kernel loads the encoding files for these encodings, and also that for the T1 encoding.

The naming conventions in the kernel are not what we would use if we were starting from scratch... Those defined by DEK (like `\ae` and `\ss`) or by the T<sub>E</sub>X Users Group Technical Working Group on multi-lingual typesetting (like `\th` and `\ng`) have short names. Those which were added to the kernel in 1993 and early 1994 are named after their Adobe glyph names (like `\guillemotleft` and `\quotedblbase`). Unfortunately, this naming scheme won't work for all glyphs, since some names (like `\space`) are already used, and some (like `\endash`) are very likely to be defined by users. So we're now using the naming scheme of `\text` followed by the Adobe name, (like `\textendash` and `\textsterling`). Except that some glyphs don't have Adobe names, so we're using the names used by fontinst for those (like `\textcompwordmark`). Sigh.

Some accents from OT1:

```
224 \DeclareTextAccentDefault{"}{OT1}
225 \DeclareTextAccentDefault{'}{OT1}
226 \DeclareTextAccentDefault{.}{OT1}
227 \DeclareTextAccentDefault{=}{OT1}
228 \DeclareTextAccentDefault{H}{OT1}
229 \DeclareTextAccentDefault{^}{OT1}
230 \DeclareTextAccentDefault{'}{OT1}
231 \DeclareTextAccentDefault{b}{OT1}
232 \DeclareTextAccentDefault{c}{OT1}
233 \DeclareTextAccentDefault{d}{OT1}
234 \DeclareTextAccentDefault{r}{OT1}
235 \DeclareTextAccentDefault{u}{OT1}
236 \DeclareTextAccentDefault{v}{OT1}
237 \DeclareTextAccentDefault{~}{OT1}
```

Some symbols from OT1:

```
238 %\DeclareTextSymbolDefault{\AA}{OT1}
239 \DeclareTextSymbolDefault{\AE}{OT1}
240 \DeclareTextSymbolDefault{\L}{OT1}
241 \DeclareTextSymbolDefault{\OE}{OT1}
242 \DeclareTextSymbolDefault{\O}{OT1}
243 %\DeclareTextSymbolDefault{\aa}{OT1}
244 \DeclareTextSymbolDefault{\ae}{OT1}
245 \DeclareTextSymbolDefault{\i}{OT1}
246 \DeclareTextSymbolDefault{\j}{OT1}

247 \DeclareTextSymbolDefault{\ij}{OT1}
```

```

248 \DeclareTextSymbolDefault{\IJ}{OT1}
249 \DeclareTextSymbolDefault{\l}{OT1}
250 \DeclareTextSymbolDefault{\oe}{OT1}
251 \DeclareTextSymbolDefault{\o}{OT1}
252 \DeclareTextSymbolDefault{\ss}{OT1}
253 \DeclareTextSymbolDefault{\textdollar}{OT1}
254 \DeclareTextSymbolDefault{\textemdash}{OT1}
255 \DeclareTextSymbolDefault{\textendash}{OT1}
256 \DeclareTextSymbolDefault{\textexclamdown}{OT1}
257 %\DeclareTextSymbolDefault{\texthyphenchar}{OT1}
258 %\DeclareTextSymbolDefault{\texthyphen}{OT1}
259 \DeclareTextSymbolDefault{\textquestiondown}{OT1}
260 \DeclareTextSymbolDefault{\textquotedblleft}{OT1}
261 \DeclareTextSymbolDefault{\textquotedblright}{OT1}
262 \DeclareTextSymbolDefault{\textquoteleft}{OT1}
263 \DeclareTextSymbolDefault{\textquoteright}{OT1}
264 \DeclareTextSymbolDefault{\textsterling}{OT1}

```

Some symbols from OMS:

```

265 \DeclareTextSymbolDefault{\textasteriskcentered}{OMS}
266 \DeclareTextSymbolDefault{\textbackslash}{OMS}
267 \DeclareTextSymbolDefault{\textbar}{OMS}
268 \DeclareTextSymbolDefault{\textbardbl}{OMS}
269 \DeclareTextSymbolDefault{\textbraceleft}{OMS}
270 \DeclareTextSymbolDefault{\textbraceright}{OMS}
271 \DeclareTextSymbolDefault{\textbullet}{OMS}
272 \DeclareTextSymbolDefault{\textdaggerdbl}{OMS}
273 \DeclareTextSymbolDefault{\textdagger}{OMS}
274 \DeclareTextSymbolDefault{\textparagraph}{OMS}
275 \DeclareTextSymbolDefault{\textperiodcentered}{OMS}
276 \DeclareTextSymbolDefault{\textsection}{OMS}
277 \DeclareTextAccentDefault{\textcircled}{OMS}

```

Some symbols from OML:

```

278 \DeclareTextSymbolDefault{\textless}{OML}
279 \DeclareTextSymbolDefault{\textgreater}{OML}
280 \DeclareTextAccentDefault{\t}{OML}

```

Some defaults we can fake.

The interface for defining `\copyright` changed, it used to use `\expandafter` to add braces at the appropriate points.

```

281 \DeclareTextCommandDefault{\textcopyright}{\textcircled{c}}
282 % \expandafter\def\expandafter
283 % \copyright\expandafter{\expandafter{\copyright}}

284 \DeclareTextCommandDefault{\textasciicircum}{\~{}}
285 \DeclareTextCommandDefault{\textasciitilde}{\~{}}
286 \DeclareTextCommandDefault{\textcompwordmark}{\leavevmode\kern\z@}
287 \DeclareTextCommandDefault{\textunderscore}{%
288 \leavevmode \kern.06em\vbox{\hrule\@width.3em}}

289 \DeclareTextCommandDefault{\textvisiblespace}{%
290 \mbox{\kern.06em\vrule \@height.3ex}%
291 \vbox{\hrule \@width.3em}%
292 \hbox{\vrule \@height.3ex}}

```

Using `\fontdimen3` in the next definition is some sort of a kludge (since it is the interword stretch) but it makes the ellipsis come out right in mono-spaced fonts too (since there it is zero).

```

293 \DeclareTextCommandDefault{\textellipsis}{%
294   .\kern\fontdimen3\font
295   .\kern\fontdimen3\font
296   .\kern\fontdimen3\font}

297 %\DeclareTextCommandDefault{\textregistered}{\textcircled{\scshape r}}
298 \DeclareTextCommandDefault{\textregistered}{\textcircled{%
299   \check@mathfonts\fontsize\sf@size\z@\math@fontsfalse\selectfont R}}
300 \DeclareTextCommandDefault{\texttrademark}{\textsuperscript{TM}}
301 \DeclareTextCommandDefault{\SS}{SS}

302 \DeclareTextCommandDefault{\textordfeminine}{\textsuperscript{a}}
303 \DeclareTextCommandDefault{\textordmasculine}{\textsuperscript{o}}

```

## 20.4.5 Math material

Some commands can be used in both text and math mode:

```

304 \DeclareRobustCommand{\$}{\ifmmode\mathdollar\else\textdollar\fi}
305 \DeclareRobustCommand{\{ }{\ifmmode\lbrace\else\textbraceleft\fi}
306 \DeclareRobustCommand{\} }{\ifmmode\rbrace\else\textbraceright\fi}
307 \DeclareRobustCommand{\P }{\ifmmode\mathparagraph\else\textparagraph\fi}
308 \DeclareRobustCommand{\S }{\ifmmode\mathsection\else\textsection\fi}
309 \DeclareRobustCommand{\dag }{\ifmmode{\dagger}\else\textdagger\fi}
310 \DeclareRobustCommand{\ddag }{\ifmmode{\ddagger}\else\textdaggerdbl\fi}

```

For historical reasons `\copyright` needs `{ }` around the definition in maths.

```

311 \DeclareRobustCommand{\_ }{%
312   \ifmmode\nfss@text{\textunderscore}\else\textunderscore\fi}
313 \DeclareRobustCommand{\copyright }{%
314   \ifmmode{\nfss@text{\textcopyright}}\else\textcopyright\fi}
315 \DeclareRobustCommand{\pounds }{%
316   \ifmmode\mathsterling\else\textsterling\fi}

317 \DeclareRobustCommand{\dots }{%
318   \ifmmode\mathellipsis\else\textellipsis\fi}

319 \let\ldots\dots

```

Default definition of the `commabelow` accent.

```

320 </2ekernel>
321 <latexrelease>\IncludeInRelease{2015/10/01}{\textcommabelow}{comma accent}%
322 <*2ekernel | latexrelease>
323 \DeclareTextCommandDefault\textcommabelow[1]
324   {\hmode\bgroup\oalign{\null#1\crr\hidewidth\raise-.31ex
325     \hbox{\check@mathfonts\fontsize\ssf@size\z@
326       \math@fontsfalse\selectfont,}\hidewidth}\egroup}
327 <latexrelease>\EndIncludeInRelease
328 </2ekernel | latexrelease>
329 <latexrelease>\IncludeInRelease{0000/00/00}{\textcommabelow}{comma accent}%
330 <latexrelease>\let\textcommabelow\@undefined
331 <latexrelease>\expandafter
332 <latexrelease> \let\csname\string\T1\string\c-G\endcsname\@undefined

```

```

333 <latexrelease>\expandafter
334 <latexrelease> \let\csname\string\T1\string\c-K\endcsname\@undefined
335 <latexrelease>\expandafter
336 <latexrelease> \let\csname\string\T1\string\c-k\endcsname\@undefined
337 <latexrelease>\expandafter
338 <latexrelease> \let\csname\string\T1\string\c-L\endcsname\@undefined
339 <latexrelease>\expandafter
340 <latexrelease> \let\csname\string\T1\string\c-l\endcsname\@undefined
341 <latexrelease>\expandafter
342 <latexrelease> \let\csname\string\T1\string\c-N\endcsname\@undefined
343 <latexrelease>\expandafter
344 <latexrelease> \let\csname\string\T1\string\c-n\endcsname\@undefined
345 <latexrelease>\expandafter
346 <latexrelease> \let\csname\string\T1\string\c-R\endcsname\@undefined
347 <latexrelease>\expandafter
348 <latexrelease> \let\csname\string\T1\string\c-r\endcsname\@undefined
349 <latexrelease>\EndIncludeInRelease

    Default definition of the commaabove accent(E.G.).
350 <latexrelease>\IncludeInRelease{2016/02/01}{\textcommaabove}{comma above}%
351 <*2kernel | latexrelease>
352 \DeclareTextCommandDefault\textcommaabove[1]{%
353   \hmode\bgroup
354   \ooalign{%
355     \hidewidth
356     \raise.7ex\hbox{%
357       \check@mathfonts\fontsize\ssf@size\z@\math@fontsfalse\selectfont‘%
358     }%
359     \hidewidth\crrc
360     \null#1\crrc
361   }%
362   \egroup
363 }
364 <latexrelease>\EndIncludeInRelease
365 </2kernel | latexrelease>
366 <latexrelease>\IncludeInRelease{0000/00/00}{\textcommaabove}{comma above}%
367 <latexrelease>\let\textcommaabove\@undefined
368 <latexrelease>\expandafter
369 <latexrelease> \let\csname\string\OT1\string\c-g\endcsname\@undefined
370 <latexrelease>\expandafter
371 <latexrelease> \let\csname\string\T1\string\c-g\endcsname\@undefined
372 <latexrelease>\EndIncludeInRelease

```

## 20.5 Definitions for the OT1 encoding

The definitions for the ‘T<sub>E</sub>X text’ (OT1) encoding.

Declare the encoding.

```

373 <*OT1>
374 \DeclareFontEncoding{OT1}{-}{-}

```

Declare the accents.

```

375 \DeclareTextAccent{"}{OT1}{127}
376 \DeclareTextAccent{'}{OT1}{19}
377 \DeclareTextAccent{.}{OT1}{95}

```

```

378 \DeclareTextAccent{\=}{OT1}{22}
379 \DeclareTextAccent{\~}{OT1}{94}
380 \DeclareTextAccent{\'}{OT1}{18}
381 \DeclareTextAccent{\`}{OT1}{126}
382 \DeclareTextAccent{\H}{OT1}{125}
383 \DeclareTextAccent{\u}{OT1}{21}
384 \DeclareTextAccent{\v}{OT1}{20}
385 \DeclareTextAccent{\r}{OT1}{23}

```

Some accents have to be built by hand: Note that `\oalign` and `\oalign` must be inside a group. In these definitions we no longer use the helper function `\sh@ft` from `plain.tex` since that now has two incompatible definitions.

```

386 \DeclareTextCommand{\b}{OT1}[1]
387   {\hmode\bgroup\oalign{\relax#1\crrcr\hidewidth\ltx@sh@ft{-3ex}%
388     \vbox to.2ex{\hbox{\char22}\vss}\hidewidth}\egroup}
389 \DeclareTextCommand{\c}{OT1}[1]
390   {\leavevmode\setbox\z@\hbox{#1}\ifdim\ht\z@=1ex\accent24 #1%
391     \else{\oalign{\unhbox\z@\crrcr\hidewidth\char24\hidewidth}}\fi}
392 \DeclareTextCommand{\d}{OT1}[1]
393   {\hmode\bgroup
394     \oalign{\relax#1\crrcr\hidewidth\ltx@sh@ft{-1ex}.\hidewidth}\egroup}

```

Declare the text symbols.

```

395 \DeclareTextSymbol{\AE}{OT1}{29}
396 \DeclareTextSymbol{\OE}{OT1}{30}
397 \DeclareTextSymbol{\O}{OT1}{31}
398 \DeclareTextSymbol{\ae}{OT1}{26}
399 \DeclareTextSymbol{\i}{OT1}{16}
400 \DeclareTextSymbol{\j}{OT1}{17}
401 \DeclareTextSymbol{\oe}{OT1}{27}
402 \DeclareTextSymbol{\o}{OT1}{28}
403 \DeclareTextSymbol{\ss}{OT1}{25}
404 \DeclareTextSymbol{\textendash}{OT1}{124}
405 \DeclareTextSymbol{\textendash}{OT1}{123}

```

Using the ligatures helps with OT1 fonts that have `\textexclamdown` and `\textquestiondown` in unusual positions.

```

406 %\DeclareTextSymbol{\textexclamdown}{OT1}{60}
407 %\DeclareTextSymbol{\textquestiondown}{OT1}{62}
408 \DeclareTextCommand{\textexclamdown}{OT1}{\!'}
409 \DeclareTextCommand{\textquestiondown}{OT1}{\?' }
410 %\DeclareTextSymbol{\textthyphenchar}{OT1}{'\-}
411 %\DeclareTextSymbol{\textthyphen}{OT1}{'\-}
412 \DeclareTextSymbol{\textquotedblleft}{OT1}{92}
413 \DeclareTextSymbol{\textquotedblright}{OT1}{'\'}
414 \DeclareTextSymbol{\textquoteleft}{OT1}{'\'}
415 \DeclareTextSymbol{\textquoteright}{OT1}{'\'}

```

Some symbols which are faked from others:

```

416 % \DeclareTextCommand{\aa}{OT1}
417 %   {\{\accent23a}}
418 \DeclareTextCommand{\L}{OT1}
419   {\leavevmode\setbox\z@\hbox{L}\hb@xt@\wd\z@{\hss\@xxxii L}}
420 \DeclareTextCommand{\l}{OT1}
421   {\hmode\bgroup\@xxxii l\egroup}

```



```

422 % \DeclareTextCommand{\AA}{OT1}
423 %     {\leavevmode\setbox\z@\hbox{h}\dimen@ht\z@\advance\dimen@-1ex%
424 %       \rlap{\raise.67\dimen@\hbox{\char23}}A}

```

In the OT1 encoding Å has a hand-crafted definition, so we have here the first recorded explicit use of `\DeclareTextCompositeCommand`.

```

425 \DeclareTextCompositeCommand{\r}{OT1}{A}
426   {\leavevmode\setbox\z@\hbox{!}\dimen@ht\z@\advance\dimen@-1ex%
427     \rlap{\raise.67\dimen@\hbox{\char23}}A}

```

The dutch language uses the letter ‘ij’. It is available in T1 encoded fonts, but not in the OT1 encoded fonts. Therefor we fake it for the OT1 encoding.

```

428 \DeclareTextCommand{\ij}{OT1}{%
429   \nobreak\hskip\z@skip i\kern-0.02em j\nobreak\hskip\z@skip}
430 \DeclareTextCommand{\IJ}{OT1}{%
431   \nobreak\hskip\z@skip I\kern-0.02em J\nobreak\hskip\z@skip}

```

In the OT1 encoding, £ and \$ share a slot.

```

432 \DeclareTextCommand{\textdollar}{OT1}{\hmode@bgroup
433   \ifdim \fontdimen\@ne\font >\z@
434     \slshape
435   \else
436     \upshape
437   \fi
438   \char‘\$’\egroup}
439 \DeclareTextCommand{\textsterling}{OT1}{\hmode@bgroup
440   \ifdim \fontdimen\@ne\font >\z@
441     \itshape
442   \else
443     \fontshape{ui}\selectfont
444   \fi
445   \char‘\$’\egroup}

```

Here we are adding some more composite commands to the OT1 encoding. This makes the use of certain accents with `i` compatible with their use with the T1 encoding; this enables them to become true L<sup>A</sup>T<sub>E</sub>X internal representations. However, it will make these accents work a little less fast since a check will always be made for the existence of a composite.

```

446 \DeclareTextComposite{\.}{OT1}{i}{‘\i}
447 \DeclareTextComposite{\.}{OT1}{i}{‘\i}
448 \DeclareTextCompositeCommand{‘}{OT1}{i}{\@tabacckludge‘\i}
449 \DeclareTextCompositeCommand{’}{OT1}{i}{\@tabacckludge’\i}
450 \DeclareTextCompositeCommand{˘}{OT1}{i}{˘\i}
451 \DeclareTextCompositeCommand{¨}{OT1}{i}{¨\i}

```

T1 encoding is given more extensive set of overloads for `\c` But here we just adjust `\c{g}`.

```

452 \ifx\textcommaabove@undefined\else
453 \DeclareTextCompositeCommand{\c}{OT1}{g}{\textcommaabove{g}}
454 \fi
455 </OT1>

```

## 20.6 Definitions for the T1 encoding

The definitions for the ‘Extended T<sub>E</sub>X text’ (T1) encoding.

Declare the encoding.

```
456 \*T1
457 \DeclareFontEncoding{T1}{-}{-}
```

Declare the accents.

```
458 \DeclareTextAccent{\`}{T1}{0}
459 \DeclareTextAccent{\'}{T1}{1}
460 \DeclareTextAccent{\~}{T1}{2}
461 \DeclareTextAccent{\^}{T1}{3}
462 \DeclareTextAccent{\"}{T1}{4}
463 \DeclareTextAccent{\H}{T1}{5}
464 \DeclareTextAccent{\r}{T1}{6}
465 \DeclareTextAccent{\v}{T1}{7}
466 \DeclareTextAccent{\u}{T1}{8}
467 \DeclareTextAccent{\=}{T1}{9}
468 \DeclareTextAccent{\.}{T1}{10}
```

Some accents have to be built by hand. Note that `\oalign` and `\o@lign` must be inside a group. In these definitions we no longer use the helper function `\sh@ft` from `plain.tex` since that now has two incompatible definitions.

```
469 \DeclareTextCommand{\b}{T1}[1]
470   {\hmode\bgroup\o@lign{\relax#1\crrc\hidewidth\ltx@sh@ft{-3ex}%
471     \vbox to.2ex{\hbox{\char9}\vss}\hidewidth}\egroup}
472 \DeclareTextCommand{\c}{T1}[1]
473   {\leavevmode\setbox\z@\hbox{#1}\ifdim\ht\z@=1ex\accent11 #1%
474     \else\oalign{\unhbox\z@\crrc
475       \hidewidth\char11\hidewidth}}\fi}
476 \DeclareTextCommand{\d}{T1}[1]
477   {\hmode\bgroup
478     \o@lign{\relax#1\crrc\hidewidth\ltx@sh@ft{-1ex}.\hidewidth}\egroup}
479 \DeclareTextCommand{\k}{T1}[1]
480   {\hmode\bgroup\oalign{\null#1\crrc\hidewidth\char12}\egroup}
481 \DeclareTextCommand{\textogonekcentered}{T1}[1]
482   {\hmode\bgroup\oalign{%
483     \null#1\crrc\hidewidth\char12\hidewidth}\egroup}
```

Some symbols are constructed.

Slot 24 contains a small circle intended for construction of these two glyphs.

```
484 \DeclareTextCommand{\textperthousand}{T1}
485   {\%\char 24 } % space or ‘relax as delimiter?
486 \DeclareTextCommand{\textpertenthousand}{T1}
487   {\%\char 24\char 24 } % space or ‘relax as delimiter?
```

For Maltese, `\Hwithstroke` and `\hwithstroke` are needed.

```
488 \DeclareTextCommand{\Hwithstroke}{T1}
489   {%
490     \hmode\bgroup
491     \vphantom{H}%
492     \sbox\z@{H}%
493     \oalign{%
494       H\cr
495       \hidewidth
```

```

496     \vrule
497     height \dimexpr 0.7\ht\z@+0.1ex\relax
498     depth  -0.7\ht\z@
499     width   0.8\wd\z@
500     \hidewidth\cr
501   }%
502 \egroup
503 }
504 \DeclareTextCommand{\hwithstroke}{T1}
505 {%
506   \hmode\bgroup
507   \vphantom{h}%
508   \sbox\z@{h}%
509   \ooalign{%
510     h\cr
511     \kern0.075\wd\z@
512     \vrule
513     height \dimexpr 0.7\ht\z@+0.1ex\relax
514     depth  -0.7\ht\z@
515     width   0.4\wd\z@
516     \hidewidth\cr
517   }%
518 \egroup
519 }

```

Declare the text symbols.

```

520 %\DeclareTextSymbol{\AA}{T1}{197}
521 \DeclareTextSymbol{\AE}{T1}{198}
522 \DeclareTextSymbol{\DH}{T1}{208}
523 \DeclareTextSymbol{\DJ}{T1}{208}
524 \DeclareTextSymbol{\L}{T1}{138}
525 \DeclareTextSymbol{\NG}{T1}{141}
526 \DeclareTextSymbol{\OE}{T1}{215}
527 \DeclareTextSymbol{\O}{T1}{216}
528 \DeclareTextSymbol{\SS}{T1}{223}
529 \DeclareTextSymbol{\TH}{T1}{222}
530 %\DeclareTextSymbol{\aa}{T1}{229}
531 \DeclareTextSymbol{\ae}{T1}{230}
532 \DeclareTextSymbol{\dh}{T1}{240}
533 \DeclareTextSymbol{\dj}{T1}{158}

534 \DeclareTextSymbol{\guillemetleft}{T1}{19}
535 \DeclareTextSymbol{\guillemetright}{T1}{20}
536 % old Adobe names
537 \DeclareTextSymbol{\guillemotleft}{T1}{19}
538 \DeclareTextSymbol{\guillemotright}{T1}{20}

539 \DeclareTextSymbol{\guilsinglleft}{T1}{14}
540 \DeclareTextSymbol{\guilsinglright}{T1}{15}
541 \DeclareTextSymbol{\i}{T1}{25}
542 \DeclareTextSymbol{\j}{T1}{26}
543 \DeclareTextSymbol{\ij}{T1}{188}
544 \DeclareTextSymbol{\IJ}{T1}{156}
545 \DeclareTextSymbol{\l}{T1}{170}
546 \DeclareTextSymbol{\ng}{T1}{173}

```

```

547 \DeclareTextSymbol{\oe}{T1}{247}
548 \DeclareTextSymbol{\o}{T1}{248}
549 \DeclareTextSymbol{\quotedblbase}{T1}{18}
550 \DeclareTextSymbol{\quotesinglbase}{T1}{13}
551 \DeclareTextSymbol{\ss}{T1}{255}
552 \DeclareTextSymbol{\textasciicircum}{T1}{'\^}
553 \DeclareTextSymbol{\textasciitilde}{T1}{'\~}
554 \DeclareTextSymbol{\textbackslash}{T1}{'\}
555 \DeclareTextSymbol{\textbar}{T1}{'|}
556 \DeclareTextSymbol{\textbraceleft}{T1}{'\{ }
557 \DeclareTextSymbol{\textbraceright}{T1}{'\} }
558 \DeclareTextSymbol{\textcompwordmark}{T1}{23}
559 \DeclareTextSymbol{\textdollar}{T1}{'\$}
560 \DeclareTextSymbol{\textemdash}{T1}{22}
561 \DeclareTextSymbol{\textendash}{T1}{21}
562 \DeclareTextSymbol{\textexclamdown}{T1}{189}
563 \DeclareTextSymbol{\textgreater}{T1}{'\>}
564 %\DeclareTextSymbol{\texthyphenchar}{T1}{127}
565 %\DeclareTextSymbol{\texthyphen}{T1}{'\-}
566 \DeclareTextSymbol{\textless}{T1}{'\<}
567 \DeclareTextSymbol{\textquestiondown}{T1}{190}
568 \DeclareTextSymbol{\textquotedblleft}{T1}{16}
569 \DeclareTextSymbol{\textquotedblright}{T1}{17}
570 \DeclareTextSymbol{\textquotedbl}{T1}{'\"}
571 \DeclareTextSymbol{\textquoteleft}{T1}{'\'}
572 \DeclareTextSymbol{\textquoteright}{T1}{'\'}
573 \DeclareTextSymbol{\textsection}{T1}{159}
574 \DeclareTextSymbol{\textsterling}{T1}{191}
575 \DeclareTextSymbol{\textunderscore}{T1}{95}
576 \DeclareTextSymbol{\textvisiblespace}{T1}{32}
577 \DeclareTextSymbol{\th}{T1}{254}

```

Declare the composites.

```

578 \DeclareTextComposite{\.}{T1}{i}{'\i}
579 \DeclareTextComposite{\.}{T1}{i}{'\i}
"80 = 128
580 \DeclareTextComposite{\u}{T1}{A}{128}
581 \DeclareTextComposite{\k}{T1}{A}{129}
582 \DeclareTextComposite{\'}{T1}{C}{130}
583 \DeclareTextComposite{\v}{T1}{C}{131}
584 \DeclareTextComposite{\v}{T1}{D}{132}
585 \DeclareTextComposite{\v}{T1}{E}{133}
586 \DeclareTextComposite{\k}{T1}{E}{134}
587 \DeclareTextComposite{\u}{T1}{G}{135}
"88 = 136
588 \DeclareTextComposite{\'}{T1}{L}{136}
589 \DeclareTextComposite{\v}{T1}{L}{137}
590 \DeclareTextComposite{\'}{T1}{N}{139}
591 \DeclareTextComposite{\v}{T1}{N}{140}
592 \DeclareTextComposite{\H}{T1}{O}{142}
593 \DeclareTextComposite{\'}{T1}{R}{143}
"90 = 144
594 \DeclareTextComposite{\v}{T1}{R}{144}

```

```

595 \DeclareTextComposite{\'}{T1}{S}{145}
596 \DeclareTextComposite{\v}{T1}{S}{146}
597 \DeclareTextComposite{\c}{T1}{S}{147}
598 \DeclareTextComposite{\v}{T1}{T}{148}
599 \DeclareTextComposite{\c}{T1}{T}{149}
600 \DeclareTextComposite{\H}{T1}{U}{150}
601 \DeclareTextComposite{\r}{T1}{U}{151}
"98 = 152
602 \DeclareTextComposite{"}{T1}{Y}{152}
603 \DeclareTextComposite{\'}{T1}{Z}{153}
604 \DeclareTextComposite{\v}{T1}{Z}{154}
605 \DeclareTextComposite{\.}{T1}{Z}{155}
606 \DeclareTextComposite{\.}{T1}{I}{157}
"A0 = 160
607 \DeclareTextComposite{\u}{T1}{a}{160}
608 \DeclareTextComposite{\k}{T1}{a}{161}
609 \DeclareTextComposite{\'}{T1}{c}{162}
610 \DeclareTextComposite{\v}{T1}{c}{163}
611 \DeclareTextComposite{\v}{T1}{d}{164}
612 \DeclareTextComposite{\v}{T1}{e}{165}
613 \DeclareTextComposite{\k}{T1}{e}{166}
614 \DeclareTextComposite{\u}{T1}{g}{167}
"A8 = 168
615 \DeclareTextComposite{\'}{T1}{l}{168}
616 \DeclareTextComposite{\v}{T1}{l}{169}
617 \DeclareTextComposite{\'}{T1}{n}{171}
618 \DeclareTextComposite{\v}{T1}{n}{172}
619 \DeclareTextComposite{\H}{T1}{o}{174}
620 \DeclareTextComposite{\'}{T1}{r}{175}
"B0 = 176
621 \DeclareTextComposite{\v}{T1}{r}{176}
622 \DeclareTextComposite{\'}{T1}{s}{177}
623 \DeclareTextComposite{\v}{T1}{s}{178}
624 \DeclareTextComposite{\c}{T1}{s}{179}
625 \DeclareTextComposite{\v}{T1}{t}{180}
626 \DeclareTextComposite{\c}{T1}{t}{181}
627 \DeclareTextComposite{\H}{T1}{u}{182}
628 \DeclareTextComposite{\r}{T1}{u}{183}
"B8 = 184
629 \DeclareTextComposite{"}{T1}{y}{184}
630 \DeclareTextComposite{\'}{T1}{z}{185}
631 \DeclareTextComposite{\v}{T1}{z}{186}
632 \DeclareTextComposite{\.}{T1}{z}{187}
"C0 = 192
633 \DeclareTextComposite{\'}{T1}{A}{192}
634 \DeclareTextComposite{\'}{T1}{A}{193}
635 \DeclareTextComposite{\^}{T1}{A}{194}
636 \DeclareTextComposite{\~}{T1}{A}{195}
637 \DeclareTextComposite{"}{T1}{A}{196}
638 \DeclareTextComposite{\r}{T1}{A}{197}
639 \DeclareTextComposite{\c}{T1}{C}{199}

```

"C8 = 200

```

640 \DeclareTextComposite{\'}{T1}{E}{200}
641 \DeclareTextComposite{\'}{T1}{E}{201}
642 \DeclareTextComposite{\^}{T1}{E}{202}
643 \DeclareTextComposite{\"}{T1}{E}{203}
644 \DeclareTextComposite{\'}{T1}{I}{204}
645 \DeclareTextComposite{\'}{T1}{I}{205}
646 \DeclareTextComposite{\^}{T1}{I}{206}
647 \DeclareTextComposite{\"}{T1}{I}{207}

```

"D0 = 208

```

648 \DeclareTextComposite{\~}{T1}{N}{209}
649 \DeclareTextComposite{\'}{T1}{O}{210}
650 \DeclareTextComposite{\'}{T1}{O}{211}
651 \DeclareTextComposite{\~}{T1}{O}{212}
652 \DeclareTextComposite{\~}{T1}{O}{213}
653 \DeclareTextComposite{\"}{T1}{O}{214}

```

"D8 = 216

```

654 \DeclareTextComposite{\'}{T1}{U}{217}
655 \DeclareTextComposite{\'}{T1}{U}{218}
656 \DeclareTextComposite{\~}{T1}{U}{219}
657 \DeclareTextComposite{\"}{T1}{U}{220}
658 \DeclareTextComposite{\'}{T1}{Y}{221}

```

"E0 = 224

```

659 \DeclareTextComposite{\'}{T1}{a}{224}
660 \DeclareTextComposite{\'}{T1}{a}{225}
661 \DeclareTextComposite{\~}{T1}{a}{226}
662 \DeclareTextComposite{\~}{T1}{a}{227}
663 \DeclareTextComposite{\"}{T1}{a}{228}
664 \DeclareTextComposite{\r}{T1}{a}{229}
665 \DeclareTextComposite{\c}{T1}{c}{231}

```

"E8 = 232

```

666 \DeclareTextComposite{\'}{T1}{e}{232}
667 \DeclareTextComposite{\'}{T1}{e}{233}
668 \DeclareTextComposite{\~}{T1}{e}{234}
669 \DeclareTextComposite{\"}{T1}{e}{235}
670 \DeclareTextComposite{\'}{T1}{i}{236}
671 \DeclareTextComposite{\'}{T1}{i}{236}
672 \DeclareTextComposite{\'}{T1}{i}{237}
673 \DeclareTextComposite{\'}{T1}{i}{237}
674 \DeclareTextComposite{\~}{T1}{i}{238}
675 \DeclareTextComposite{\~}{T1}{i}{238}
676 \DeclareTextComposite{\"}{T1}{i}{239}
677 \DeclareTextComposite{\"}{T1}{i}{239}

```

"F0 = 240

```

678 \DeclareTextComposite{\~}{T1}{n}{241}
679 \DeclareTextComposite{\'}{T1}{o}{242}
680 \DeclareTextComposite{\'}{T1}{o}{243}
681 \DeclareTextComposite{\~}{T1}{o}{244}
682 \DeclareTextComposite{\~}{T1}{o}{245}
683 \DeclareTextComposite{\"}{T1}{o}{246}

```

```

" F8 = 248

684 \DeclareTextComposite{'}{T1}{u}{249}
685 \DeclareTextComposite{''}{T1}{u}{250}
686 \DeclareTextComposite{'^'}{T1}{u}{251}
687 \DeclareTextComposite{'"}{T1}{u}{252}
688 \DeclareTextComposite{''}{T1}{y}{253}

689 \DeclareTextCompositeCommand{\k}{T1}{o}{\textogonekcentered{o}}
690 \DeclareTextCompositeCommand{\k}{T1}{O}{\textogonekcentered{O}}

691 \ifx\textcommaabove@undefined\else
692 \DeclareTextCompositeCommand{\c}{T1}{g}{\textcommaabove{g}}
693 \fi
694 \ifx\textcommabelow@undefined\else
695 \DeclareTextCompositeCommand{\c}{T1}{G}{\textcommabelow{G}}
696 \DeclareTextCompositeCommand{\c}{T1}{K}{\textcommabelow{K}}
697 \DeclareTextCompositeCommand{\c}{T1}{k}{\textcommabelow{k}}
698 \DeclareTextCompositeCommand{\c}{T1}{L}{\textcommabelow{L}}
699 \DeclareTextCompositeCommand{\c}{T1}{l}{\textcommabelow{l}}
700 \DeclareTextCompositeCommand{\c}{T1}{N}{\textcommabelow{N}}
701 \DeclareTextCompositeCommand{\c}{T1}{n}{\textcommabelow{n}}
702 \DeclareTextCompositeCommand{\c}{T1}{R}{\textcommabelow{R}}
703 \DeclareTextCompositeCommand{\c}{T1}{r}{\textcommabelow{r}}
704 \fi
705 </T1>

```

## 20.7 Definitions for the OMS encoding

The definitions for the ‘TeX math symbol’ (OMS) encoding. Even though this is meant to be a math font, it includes some of the standard L<sup>A</sup>T<sub>E</sub>X text symbols.

Declare the encoding.

```

706 (*OMS)
707 \DeclareFontEncoding{OMS}{}{}

```

Declare the symbols. Note that slot 13 has in places been named \Orb: please root out and destroy this impolity wherever you find it!

```

708 \DeclareTextSymbol{\textasteriskcentered}{OMS}{3} % "03
709 \DeclareTextSymbol{\textbackslash}{OMS}{110} % "6E
710 \DeclareTextSymbol{\textbar}{OMS}{106} % "6A
711 \DeclareTextSymbol{\textbardbl}{OMS}{107} % "6B
712 \DeclareTextSymbol{\textbraceleft}{OMS}{102} % "66
713 \DeclareTextSymbol{\textbraceright}{OMS}{103} % "67
714 \DeclareTextSymbol{\textbullet}{OMS}{15} % "0F
715 \DeclareTextSymbol{\textdaggerdbl}{OMS}{122} % "7A
716 \DeclareTextSymbol{\textdagger}{OMS}{121} % "79
717 \DeclareTextSymbol{\textparagraph}{OMS}{123} % "7B
718 \DeclareTextSymbol{\textperiodcentered}{OMS}{1} % "01
719 \DeclareTextSymbol{\textsection}{OMS}{120} % "78
720 \DeclareTextSymbol{\textbigcircle}{OMS}{13} % "0D
721 \DeclareTextCommand{\textcircled}{OMS}[1]{\hmode@bgroup
722 \oalign{%
723 \hfil \raise .07ex\hbox {\upshape#1}\hfil \crcr
724 \char 13 % "0D

```

```

725 }%
726 \egroup}
727 </OMS>

```

## 20.8 Definitions for the OML encoding

The definitions for the ‘T<sub>E</sub>X math italic’ (OML) encoding. Even though this is meant to be a math font, it includes some of the standard L<sup>A</sup>T<sub>E</sub>X text symbols.

Declare the encoding.

```

728 (*OML)
729 \DeclareFontEncoding{OML}{-}{-}

Declare the symbols.

730 \DeclareTextSymbol{\textless}{OML}{'\<}
731 \DeclareTextSymbol{\textgreater}{OML}{'\>}
732 \DeclareTextAccent{\t}{OML}{127} % "7F
733 </OML>

```

## 20.9 Definitions for the OT4 encoding

These definitions are for the Polish extension to the ‘T<sub>E</sub>X text’ (OT1) encoding. This encoding was created by B. Jackowski and M. Ryćko for use with the Polish version of Computer Modern and Computer Concrete. In positions 0–127 it is identical to OT1 but it contains some additional characters in the upper half. The L<sup>A</sup>T<sub>E</sub>X support was developed by Mariusz Olko.

The PL fonts that use it are available as follows:

Metafont sources <ftp://ftp.gust.org.pl/TeX/language/polish/pl-mf.zip>;

Font files <ftp://ftp.gust.org.pl/TeX/language/polish/pl-tfm.zip>.

Declare the encoding.

```

734 (*OT4)
735 \DeclareFontEncoding{OT4}{-}{-}
736 \DeclareFontSubstitution{OT4}{cmr}{m}{n}

```

Declare the accents.

```

737 \DeclareTextAccent{"}{OT4}{127}
738 \DeclareTextAccent{\'}{OT4}{19}
739 \DeclareTextAccent{\.}{OT4}{95}
740 \DeclareTextAccent{\=}{OT4}{22}
741 \DeclareTextAccent{\^}{OT4}{94}
742 \DeclareTextAccent{\'}{OT4}{18}
743 \DeclareTextAccent{\~}{OT4}{126}
744 \DeclareTextAccent{\H}{OT4}{125}
745 \DeclareTextAccent{\u}{OT4}{21}
746 \DeclareTextAccent{\v}{OT4}{20}
747 \DeclareTextAccent{\r}{OT4}{23}

```

The ogonek accent is available only under a e A & E. But we have to provide some definition for \k. Some other accents have to be built by hand as in OT1:

```

748 \DeclareTextCommand{\k}{OT4}[1]{%
749   \TextSymbolUnavailable{\k{#1}}#1}

```

In these definitions we no longer use the helper function \sh@ft from plain.tex since that now has two incompatible definitions.

```

750 \DeclareTextCommand{\b}{OT4}[1]

```



```

751 {\hmode\bgroup\o@lign{\relax#1\crrc\hidewidth\ltx@sh@ft{-3ex}%
752 \vbox to.2ex{\hbox{\char22}\vss}\hidewidth}\egroup}
753 \DeclareTextCommand{\c}{OT4}[1]
754 {\leavevmode\setbox\z@\hbox{#1}\ifdim\ht\z@=1ex\accent24 #1%
755 \else{\oalign{\unhbox\z@\crrc\hidewidth\char24\hidewidth}}\fi}
756 \DeclareTextCommand{\d}{OT4}[1]
757 {\hmode\bgroup
758 \o@lign{\relax#1\crrc\hidewidth\ltx@sh@ft{-1ex}.\hidewidth}\egroup}

```

Declare the text symbols.

```

759 \DeclareTextSymbol{\AE}{OT4}{29}
760 \DeclareTextSymbol{\OE}{OT4}{30}
761 \DeclareTextSymbol{\O}{OT4}{31}
762 \DeclareTextSymbol{\L}{OT4}{138}
763 \DeclareTextSymbol{\ae}{OT4}{26}

764 \DeclareTextSymbol{\guillemetleft}{OT4}{174}
765 \DeclareTextSymbol{\guillemetright}{OT4}{175}
766 % old Adobe names
767 \DeclareTextSymbol{\guillemotleft}{OT4}{174}
768 \DeclareTextSymbol{\guillemotright}{OT4}{175}

769 \DeclareTextSymbol{\i}{OT4}{16}
770 \DeclareTextSymbol{\j}{OT4}{17}
771 \DeclareTextSymbol{\l}{OT4}{170}
772 \DeclareTextSymbol{\o}{OT4}{28}
773 \DeclareTextSymbol{\oe}{OT4}{27}
774 \DeclareTextSymbol{\quotedblbase}{OT4}{255}
775 \DeclareTextSymbol{\ss}{OT4}{25}
776 \DeclareTextSymbol{\textemdash}{OT4}{124}
777 \DeclareTextSymbol{\textendash}{OT4}{123}
778 \DeclareTextSymbol{\textexclamdown}{OT4}{60}
779 %\DeclareTextSymbol{\textthyphenchar}{OT4}{'\-}
780 %\DeclareTextSymbol{\textthyphen}{OT4}{'\-}
781 \DeclareTextSymbol{\textquestiondown}{OT4}{62}
782 \DeclareTextSymbol{\textquotedblleft}{OT4}{92}
783 \DeclareTextSymbol{\textquotedblright}{OT4}{'\'}
784 \DeclareTextSymbol{\textquoteleft}{OT4}{'\'}
785 \DeclareTextSymbol{\textquoteright}{OT4}{'\'}

```

Definition for Å as in OT1:

```

786 \DeclareTextCompositeCommand{\r}{OT4}{A}
787 {\leavevmode\setbox\z@\hbox{!}\dimen@ht\z@\advance\dimen@-1ex%
788 \rlap{\raise.67\dimen@\hbox{\char23}}A}

```

In the OT4 encoding, £ and \$ share a slot.

```

789 \DeclareTextCommand{\textdollar}{OT4}{\hmode\bgroup
790 \ifdim \fontdimen\@ne\font >\z@
791 \slshape
792 \else
793 \upshape
794 \fi
795 \char'\$\egroup}
796 \DeclareTextCommand{\textsterling}{OT4}{\hmode\bgroup
797 \ifdim \fontdimen\@ne\font >\z@
798 \itshape

```

```

799 \else
800 \fontshape{ui}\selectfont
801 \fi
802 \char'\$\egroup}

```

Declare the composites.

```

803 \DeclareTextComposite{\k}{OT4}{A}{129}
804 \DeclareTextComposite{\'}{OT4}{C}{130}
805 \DeclareTextComposite{\k}{OT4}{E}{134}
806 \DeclareTextComposite{\'}{OT4}{N}{139}
807 \DeclareTextComposite{\'}{OT4}{S}{145}
808 \DeclareTextComposite{\'}{OT4}{Z}{153}
809 \DeclareTextComposite{\.}{OT4}{Z}{155}
810 \DeclareTextComposite{\k}{OT4}{a}{161}
811 \DeclareTextComposite{\'}{OT4}{c}{162}
812 \DeclareTextComposite{\k}{OT4}{e}{166}
813 \DeclareTextComposite{\'}{OT4}{n}{171}
814 \DeclareTextComposite{\'}{OT4}{s}{177}
815 \DeclareTextComposite{\'}{OT4}{z}{185}
816 \DeclareTextComposite{\.}{OT4}{z}{187}
817 \DeclareTextComposite{\'}{OT4}{O}{211}
818 \DeclareTextComposite{\'}{OT4}{o}{243}
819 /OT4}

```

## 20.10 Definitions for the TS1 encoding

```

820 (*TS1)
821 \DeclareFontEncoding{TS1}{}{}
822 \DeclareFontSubstitution{TS1}{cmr}{m}{n}

```

Some accents have to be built by hand. Note that `\oalign` and `\o@lign` must be inside a group.

```

823 \DeclareTextCommand{\capitalcedilla}{TS1}[1]
824 {\hmode@bgroup
825 \oalign{\null#1\crcr\hidewidth\char11\hidewidth}\egroup}
826 \DeclareTextCommand{\capitalogonek}{TS1}[1]
827 {\hmode@bgroup
828 \oalign{\null#1\crcr\hidewidth\char12\hidewidth}\egroup}

```

Accents for capital letters.

These commands can be used by the end user either directly or through definitions of the type

```
\DeclareTextCompositeCommand{\'}{T1}{X}{\capitalacute X}
```

None of the latter definitions are provided by default, since they are probably rarely used.

"00 = 0

```

829 \DeclareTextAccent{\capitalgrave}{TS1}{0}
830 \DeclareTextAccent{\capitalacute}{TS1}{1}
831 \DeclareTextAccent{\capitalcircumflex}{TS1}{2}
832 \DeclareTextAccent{\capitaltilde}{TS1}{3}
833 \DeclareTextAccent{\capitaldieresis}{TS1}{4}
834 \DeclareTextAccent{\capitalhungarumlaut}{TS1}{5}
835 \DeclareTextAccent{\capitalring}{TS1}{6}
836 \DeclareTextAccent{\capitalcaron}{TS1}{7}

```

"08 = 8

```
837 \DeclareTextAccent{\capitalbreve}{TS1}{8}  
838 \DeclareTextAccent{\capitalmacron}{TS1}{9}  
839 \DeclareTextAccent{\capitaldotaccent}{TS1}{10}
```

Tie accents.

The tie accent was borrowed from the `cmmt` font. The `tc` fonts now provide four tie accents, the first two are done in the classical way with assymetric glyphs hanging out of their boxes; the new ties are centered in their boxes like all other accents. They need a name: please tell us if you know what to call them.

" =

```
840 \DeclareTextAccent{\t}{TS1}{26}  
841 \DeclareTextAccent{\capitaltie}{TS1}{27}  
842 \DeclareTextAccent{\newtie}{TS1}{28}  
843 \DeclareTextAccent{\capitalnewtie}{TS1}{29}
```

Compound word marks.

The text companion fonts contain two compound word marks of different heights, one has `cap_height`, the other `asc_height`.

```
844 \DeclareTextSymbol{\textcapitalcompwordmark}{TS1}{23}  
845 \DeclareTextSymbol{\textascendercompwordmark}{TS1}{31}
```

The text companion symbols.

```
846 \DeclareTextSymbol{\textquotestraightbase}{TS1}{13}  
"10 = 16  
847 \DeclareTextSymbol{\textquotestraightdblbase}{TS1}{18}  
848 \DeclareTextSymbol{\texttwelveudash}{TS1}{21}  
849 \DeclareTextSymbol{\textthreequartersemdash}{TS1}{22}
```

"18 = 24

```
850 \DeclareTextSymbol{\textleftarrow}{TS1}{24}  
851 \DeclareTextSymbol{\textrightarrow}{TS1}{25}
```

"20 = 32

```
852 \DeclareTextSymbol{\textblank}{TS1}{32}  
853 \DeclareTextSymbol{\textdollar}{TS1}{36}  
854 \DeclareTextSymbol{\textquotesingle}{TS1}{39}
```

"28 = 40

```
855 \DeclareTextSymbol{\textasteriskcentered}{TS1}{42}
```

Note that '054 is a comma and '056 is a full stop: these make numbers using oldstyle digits easier to input.

```
856 \DeclareTextSymbol{\textdblhyphen}{TS1}{45}  
857 \DeclareTextSymbol{\textfractionsolidus}{TS1}{47}
```

Oldstyle digits.

"30 = 48

```
858 \DeclareTextSymbol{\textzerooldstyle}{TS1}{48}  
859 \DeclareTextSymbol{\textoneoldstyle}{TS1}{49}  
860 \DeclareTextSymbol{\texttwooldstyle}{TS1}{50}  
861 \DeclareTextSymbol{\textthreeoldstyle}{TS1}{51}  
862 \DeclareTextSymbol{\textfouroldstyle}{TS1}{52}  
863 \DeclareTextSymbol{\textfiveoldstyle}{TS1}{53}  
864 \DeclareTextSymbol{\textsixoldstyle}{TS1}{54}  
865 \DeclareTextSymbol{\textsevenoldstyle}{TS1}{55}
```

"38 = 56

```
866 \DeclareTextSymbol{\texteightoldstyle}{TS1}{56}
```

```
867 \DeclareTextSymbol{\textnineoldstyle}{TS1}{57}
```

More text companion symbols.

```
868 \DeclareTextSymbol{\textlangle}{TS1}{60}
```

```
869 \DeclareTextSymbol{\textminus}{TS1}{61}
```

```
870 \DeclareTextSymbol{\textrangle}{TS1}{62}
```

"48 = 72

```
871 \DeclareTextSymbol{\textmho}{TS1}{77}
```

The big circle is here to define the command `\textcircled`. Formerly it was taken from the `cmsy` font.

```
872 \DeclareTextSymbol{\textbigcircle}{TS1}{79}
```

```
873 \DeclareTextCommand{\textcircled}{TS1}[1]{\hmode\bgroup
```

```
874   \oalign{%
```

```
875     \hfil \raise .07ex\hbox {\upshape#1}\hfil \crcr
```

```
876     \char 79   % '117 = "4F
```

```
877   }%
```

```
878 \egroup}
```

More text companion symbols.

"50 = 80

```
879 \DeclareTextSymbol{\textohm}{TS1}{87}
```

"58 = 88

```
880 \DeclareTextSymbol{\textlbrackdbl}{TS1}{91}
```

```
881 \DeclareTextSymbol{\textrbrackdbl}{TS1}{93}
```

```
882 \DeclareTextSymbol{\textuparrow}{TS1}{94}
```

```
883 \DeclareTextSymbol{\textdownarrow}{TS1}{95}
```

"60 = 96

```
884 \DeclareTextSymbol{\textasciigrave}{TS1}{96}
```

```
885 \DeclareTextSymbol{\textborn}{TS1}{98}
```

```
886 \DeclareTextSymbol{\textdivorced}{TS1}{99}
```

```
887 \DeclareTextSymbol{\textdied}{TS1}{100}
```

"68 = 104

```
888 \DeclareTextSymbol{\textleaf}{TS1}{108}
```

```
889 \DeclareTextSymbol{\textmarried}{TS1}{109}
```

```
890 \DeclareTextSymbol{\textmusicalnote}{TS1}{110}
```

"78 = 120

```
891 \DeclareTextSymbol{\texttildelow}{TS1}{126}
```

This glyph, `\textdblhyphenchar` is hanging, like the `hyphenchar` of the `ec` fonts.

```
892 \DeclareTextSymbol{\textdblhyphenchar}{TS1}{127}
```

"80 = 128

```
893 \DeclareTextSymbol{\textasciibreve}{TS1}{128}
```

```
894 \DeclareTextSymbol{\textasciicaron}{TS1}{129}
```

This next glyph is *not* the same as `\textquotedbl`.

```
895 \DeclareTextSymbol{\textacutedbl}{TS1}{130}
```

```
896 \DeclareTextSymbol{\textgravedbl}{TS1}{131}
```

```

897 \DeclareTextSymbol{\textdagger}{TS1}{132}
898 \DeclareTextSymbol{\textdaggerdbl}{TS1}{133}
899 \DeclareTextSymbol{\textbardbl}{TS1}{134}
900 \DeclareTextSymbol{\textperthousand}{TS1}{135}

"88 = 136

901 \DeclareTextSymbol{\textbullet}{TS1}{136}
902 \DeclareTextSymbol{\textcelsius}{TS1}{137}
903 \DeclareTextSymbol{\textdollaroldstyle}{TS1}{138}
904 \DeclareTextSymbol{\textcentoldstyle}{TS1}{139}
905 \DeclareTextSymbol{\textflorin}{TS1}{140}
906 \DeclareTextSymbol{\textcolonmonetary}{TS1}{141}
907 \DeclareTextSymbol{\textwon}{TS1}{142}
908 \DeclareTextSymbol{\textnaira}{TS1}{143}

"90 = 144

909 \DeclareTextSymbol{\textguarani}{TS1}{144}
910 \DeclareTextSymbol{\textpeso}{TS1}{145}
911 \DeclareTextSymbol{\textlira}{TS1}{146}
912 \DeclareTextSymbol{\textrecipe}{TS1}{147}
913 \DeclareTextSymbol{\textinterrobang}{TS1}{148}
914 \DeclareTextSymbol{\textinterrobangdown}{TS1}{149}
915 \DeclareTextSymbol{\textdong}{TS1}{150}
916 \DeclareTextSymbol{\texttrademark}{TS1}{151}

"98 = 152

917 \DeclareTextSymbol{\textpertenthousand}{TS1}{152}
918 \DeclareTextSymbol{\textpilcrow}{TS1}{153}
919 \DeclareTextSymbol{\textbaht}{TS1}{154}
920 \DeclareTextSymbol{\textnumero}{TS1}{155}

This next name may change. For the following sign we know only a german name,
which is abzüglich. The meaning is something like "commercial minus". An ASCII
ersatz is ./.. (dot slash dot). The temporary English name is \textdiscount.

921 \DeclareTextSymbol{\textdiscount}{TS1}{156}
922 \DeclareTextSymbol{\textestimated}{TS1}{157}
923 \DeclareTextSymbol{\textopenbullet}{TS1}{158}
924 \DeclareTextSymbol{\textservicemark}{TS1}{159}

"A0 = 160

925 \DeclareTextSymbol{\textlquill}{TS1}{160}
926 \DeclareTextSymbol{\textrquill}{TS1}{161}
927 \DeclareTextSymbol{\textcent}{TS1}{162}
928 \DeclareTextSymbol{\textsterling}{TS1}{163}
929 \DeclareTextSymbol{\textcurrency}{TS1}{164}
930 \DeclareTextSymbol{\textyen}{TS1}{165}
931 \DeclareTextSymbol{\textbrokenbar}{TS1}{166}
932 \DeclareTextSymbol{\textsection}{TS1}{167}

"A8 = 168

933 \DeclareTextSymbol{\textasciidieresis}{TS1}{168}
934 \DeclareTextSymbol{\textcopyright}{TS1}{169}
935 \DeclareTextSymbol{\textordfeminine}{TS1}{170}
936 \DeclareTextSymbol{\textcopyleft}{TS1}{171}
937 \DeclareTextSymbol{\textlnot}{TS1}{172}

```

The meaning of the circled-P is “sound recording copyright”.

```

938 \DeclareTextSymbol{\textcircledP}{TS1}{173}
939 \DeclareTextSymbol{\textregistered}{TS1}{174}
940 \DeclareTextSymbol{\textasciimacron}{TS1}{175}

”B0 = 176

941 \DeclareTextSymbol{\textdegree}{TS1}{176}
942 \DeclareTextSymbol{\textpm}{TS1}{177}
943 \DeclareTextSymbol{\texttwosuperior}{TS1}{178}
944 \DeclareTextSymbol{\textthreesuperior}{TS1}{179}
945 \DeclareTextSymbol{\textasciicute}{TS1}{180}
946 \DeclareTextSymbol{\textmu}{TS1}{181} % micro sign
947 \DeclareTextSymbol{\textparagraph}{TS1}{182}
948 \DeclareTextSymbol{\textperiodcentered}{TS1}{183}

”B8 = 184

949 \DeclareTextSymbol{\textreferencemark}{TS1}{184}
950 \DeclareTextSymbol{\textonesuperior}{TS1}{185}
951 \DeclareTextSymbol{\textordmasculine}{TS1}{186}
952 \DeclareTextSymbol{\textsurd}{TS1}{187}
953 \DeclareTextSymbol{\textonequarter}{TS1}{188}
954 \DeclareTextSymbol{\textonehalf}{TS1}{189}
955 \DeclareTextSymbol{\textthreequarters}{TS1}{190}
956 \DeclareTextSymbol{\texteuro}{TS1}{191}

”E0 = 208

957 \DeclareTextSymbol{\texttimes}{TS1}{214}

”F0 = 240

958 \DeclareTextSymbol{\textdiv}{TS1}{246}
959 \end{TS1}

```

## 20.11 Definitions for the TU encoding

The TU encoding was originally introduced in the contributed package `fontspec` as a Unicode encoding for XeTeX and LuaTeX.

Normally for these engines, the input consists of Unicode characters encoded in UTF-8. There is therefore little need to use the traditional (ASCII) encoding-specific commands

However, sometimes (e.g. for backwards compatibility) it can be useful to access these Unicode characters via such ASCII-based markup. The commands provided here cover the characters in the T1 and TS1 encodings, but specified in Unicode position. Almost all the command names have been mechanically extracted from the `inputenc` UTF-8 support, which is essentially doing a reverse mapping from UTF-8 data to L<sup>A</sup>T<sub>E</sub>X LICR commands.

A few additional names for character which were supported in the original `fontspec` version of this file have also been added, even though they are not currently in the default `inputenc` UTF-8 declarations.

```

960 \newcommand{*TU}

```

In the base interface the Unicode encoding is always known as TU But we parameterise the encoding name to allow for modelling differences in Unicode support by different fonts.

```

961 \providecommand\UnicodeEncodingName{TU}

```

As the Unicode encoding, TU, is only currently available with XeTeX or LuaTeX, we detect these engines first, and make adjustments for the differing font loading syntax. For other engines, we issue a warning then abort this file, switching back to T1 encoding.

```

962 \begingroup\expandafter\expandafter\expandafter\endgroup
963 \expandafter\ifx\csname XeTeXrevision\endcsname\relax
964   \begingroup\expandafter\expandafter\expandafter\endgroup
965   \expandafter\ifx\csname directlua\endcsname\relax

```

Not LuaTeX or XeTeX, abort with a warning.

```

966   \PackageWarningNoLine{fontenc}
967     {\UnicodeEncodingName\space
968       encoding is only available with XeTeX and LuaTeX.\MessageBreak
969       Defaulting to T1 encoding}
970   \def\encodingdefault{T1}
971   \expandafter\expandafter\expandafter\endinput
972 \else

```

LuaTeX.

```

973   \def\UnicodeFontTeXLigatures{+tlig;}
974   \def\reserved@a#1{%
975     \def\@remove@tlig##1{\@remove@tlig@##1\@nil#1\@nil\relax}
976     \def\@remove@tlig@##1#1{\@remove@tlig@##1}}
977   \edef\reserved@b{\detokenize{+tlig;}}
978   \expandafter\reserved@a\expandafter{\reserved@b}
979   \def\@remove@tlig@##1\@nil#2\relax{#1}
980   \def\remove@tlig#1{%
981     \begingroup
982     \font\remove@tlig
983     \expandafter\@remove@tlig\expandafter{\fontname\font}%
984     \remove@tlig
985     \char#1\relax
986   \endgroup
987   }
988 \fi
989 \else

```

XeTeX

```

990   \def\UnicodeFontTeXLigatures{mapping=tex-text;}
991   \def\remove@tlig#1{\XeTeXglyph\numexpr\XeTeXcharglyph#1\relax}
992 \fi
993 \def\UnicodeFontFile#1#2{"[#1]:#2"}
994 \def\UnicodeFontName#1#2{"#1:#2"}

```

Declare the encoding

```

995 \DeclareFontEncoding\UnicodeEncodingName{}{}

```

Declare accent command to use a postpended combining character rather than the TeX \accent primitive

```

996 \def\add@unicode@accent#1#2{%
997   \if\relax\detokenize{#2}\relax~^a0\else#2\fi
998   \char#1\relax}

```

```

999 \def\DeclareUnicodeAccent#1#2#3{%
1000   \DeclareTextCommand{#1}{#2}{\add@unicode@accent{#3}}%
1001 }

    Wrapper around \DeclareTextCompositeCommand that uses the declared composite if it exists in the current font or falls back to the default definition for the TU accent if not.

1002 {
1003   \catcode\z@=11\relax
1004   \gdef\DeclareUnicodeComposite#1#2#3{%
1005     \def\reserved@a##1##2{%
1006       \DeclareTextCompositeCommand#1\UnicodeEncodingName{#2}{%
1007         \iffontchar\font#3 ##2%
1008           \else ##1\fi}}%
1009     \expandafter\expandafter\expandafter\extract@default@composite
1010     \csname\UnicodeEncodingName\string#1\endcsname{#2}\@nil
1011     \bgroup
1012       \lccode\z@#3 %
1013       \lowercase{\egroup
1014         \expandafter\reserved@a\expandafter{\reserved@b}{^^@}}}%
1015   }

1016 \def\extract@default@composite#1{%
1017   \ifx\@text@composite#1%
1018     \expandafter\extract@default@composite@a
1019   \else
1020     \expandafter\extract@default@composite@b\expandafter#1%
1021   \fi}

1022 \def\extract@default@composite@a#1\@text@composite#2\@nil{%
1023   \def\reserved@b{#2}}
1024 \def\extract@default@composite@b#1#2\@nil{%
1025   \def\reserved@b{#1#2}}

1026 \DeclareTextCommand\textquotesingle \UnicodeEncodingName{%
1027   \remove@tlig{"0027}}
1028 \DeclareTextCommand\textasciigrave \UnicodeEncodingName{%
1029   \remove@tlig{"0060}}
1030 \DeclareTextCommand\textquotedbl \UnicodeEncodingName{%
1031   \remove@tlig{"0022}}

1032 \DeclareTextSymbol{\textdollar} \UnicodeEncodingName{"0024}
1033 \DeclareTextSymbol{\textless} \UnicodeEncodingName{"003C}
1034 \DeclareTextSymbol{\textgreater} \UnicodeEncodingName{"003E}
1035 \DeclareTextSymbol{\textbackslash} \UnicodeEncodingName{"005C}
1036 \DeclareTextSymbol{\textasciicircum} \UnicodeEncodingName{"005E}
1037 \DeclareTextSymbol{\textunderscore} \UnicodeEncodingName{"005F}
1038 \DeclareTextSymbol{\textbraceleft} \UnicodeEncodingName{"007B}
1039 \DeclareTextSymbol{\textbar} \UnicodeEncodingName{"007C}
1040 \DeclareTextSymbol{\textbraceright} \UnicodeEncodingName{"007D}
1041 \DeclareTextSymbol{\textasciitilde} \UnicodeEncodingName{"007E}
1042 \DeclareTextSymbol{\textexclamdown} \UnicodeEncodingName{"00A1}
1043 \DeclareTextSymbol{\textcent} \UnicodeEncodingName{"00A2}
1044 \DeclareTextSymbol{\textsterling} \UnicodeEncodingName{"00A3}
1045 \DeclareTextSymbol{\textcurrency} \UnicodeEncodingName{"00A4}
1046 \DeclareTextSymbol{\textyen} \UnicodeEncodingName{"00A5}
1047 \DeclareTextSymbol{\textbrokenbar} \UnicodeEncodingName{"00A6}

```



1048 \DeclareTextSymbol{\textsection}	\UnicodeEncodingName{"00A7}
1049 \DeclareTextSymbol{\textasciidieresis}	\UnicodeEncodingName{"00A8}
1050 \DeclareTextSymbol{\textcopyright}	\UnicodeEncodingName{"00A9}
1051 \DeclareTextSymbol{\textordfeminine}	\UnicodeEncodingName{"00AA}
1052 \DeclareTextSymbol{\guillemetleft}	\UnicodeEncodingName{"00AB}
1053 % old Adobe name	
1054 \DeclareTextSymbol{\guillemotleft}	\UnicodeEncodingName{"00AB}
1055 \DeclareTextSymbol{\textlnot}	\UnicodeEncodingName{"00AC}
1056 \DeclareTextSymbol{\textregistered}	\UnicodeEncodingName{"00AE}
1057 \DeclareTextSymbol{\textasciimacron}	\UnicodeEncodingName{"00AF}
1058 \DeclareTextSymbol{\textdegree}	\UnicodeEncodingName{"00B0}
1059 \DeclareTextSymbol{\textpm}	\UnicodeEncodingName{"00B1}
1060 \DeclareTextSymbol{\texttwosuperior}	\UnicodeEncodingName{"00B2}
1061 \DeclareTextSymbol{\textthreesuperior}	\UnicodeEncodingName{"00B3}
1062 \DeclareTextSymbol{\textasciicute}	\UnicodeEncodingName{"00B4}
1063 \DeclareTextSymbol{\textmu}	\UnicodeEncodingName{"00B5}
1064 \DeclareTextSymbol{\textparagraph}	\UnicodeEncodingName{"00B6}
1065 \DeclareTextSymbol{\textperiodcentered}	\UnicodeEncodingName{"00B7}
1066 \DeclareTextSymbol{\textonesuperior}	\UnicodeEncodingName{"00B9}
1067 \DeclareTextSymbol{\textordmasculine}	\UnicodeEncodingName{"00BA}
1068 \DeclareTextSymbol{\guillemetright}	\UnicodeEncodingName{"00BB}
1069 % old Adobe name	
1070 \DeclareTextSymbol{\guillemotright}	\UnicodeEncodingName{"00BB}
1071 \DeclareTextSymbol{\textonequarter}	\UnicodeEncodingName{"00BC}
1072 \DeclareTextSymbol{\textonehalf}	\UnicodeEncodingName{"00BD}
1073 \DeclareTextSymbol{\textthreequarters}	\UnicodeEncodingName{"00BE}
1074 \DeclareTextSymbol{\textquestiondown}	\UnicodeEncodingName{"00BF}
1075 \DeclareTextSymbol{\AE}	\UnicodeEncodingName{"00C6}
1076 \DeclareTextSymbol{\DH}	\UnicodeEncodingName{"00D0}
1077 \DeclareTextSymbol{\texttimes}	\UnicodeEncodingName{"00D7}
1078 \DeclareTextSymbol{\O}	\UnicodeEncodingName{"00D8}
1079 \DeclareTextSymbol{\TH}	\UnicodeEncodingName{"00DE}
1080 \DeclareTextSymbol{\ss}	\UnicodeEncodingName{"00DF}
1081 \DeclareTextSymbol{\ae}	\UnicodeEncodingName{"00E6}
1082 \DeclareTextSymbol{\dh}	\UnicodeEncodingName{"00F0}
1083 \DeclareTextSymbol{\textdiv}	\UnicodeEncodingName{"00F7}
1084 \DeclareTextSymbol{\o}	\UnicodeEncodingName{"00F8}
1085 \DeclareTextSymbol{\th}	\UnicodeEncodingName{"00FE}
1086 \DeclareTextSymbol{\DJ}	\UnicodeEncodingName{"0110}
1087 \DeclareTextSymbol{\dj}	\UnicodeEncodingName{"0111}
1088 \DeclareTextSymbol{\i}	\UnicodeEncodingName{"0131}
1089 \DeclareTextSymbol{\IJ}	\UnicodeEncodingName{"0132}
1090 \DeclareTextSymbol{\ij}	\UnicodeEncodingName{"0133}
1091 \DeclareTextSymbol{\L}	\UnicodeEncodingName{"0141}
1092 \DeclareTextSymbol{\l}	\UnicodeEncodingName{"0142}
1093 \DeclareTextSymbol{\NG}	\UnicodeEncodingName{"014A}
1094 \DeclareTextSymbol{\ng}	\UnicodeEncodingName{"014B}
1095 \DeclareTextSymbol{\OE}	\UnicodeEncodingName{"0152}
1096 \DeclareTextSymbol{\oe}	\UnicodeEncodingName{"0153}
1097 \DeclareTextSymbol{\textflorin}	\UnicodeEncodingName{"0192}
1098 \DeclareTextSymbol{\j}	\UnicodeEncodingName{"0237}
1099 \DeclareTextSymbol{\textasciicaron}	\UnicodeEncodingName{"02C7}

1100	\DeclareTextSymbol{\textasciibreve}	\UnicodeEncodingName{"02D8}
1101	\DeclareTextSymbol{\textacutedbl}	\UnicodeEncodingName{"02DD}
1102	\DeclareTextSymbol{\textgravedbl}	\UnicodeEncodingName{"02F5}
1103	\DeclareTextSymbol{\texttildelow}	\UnicodeEncodingName{"02F7}
1104	\DeclareTextSymbol{\textbaht}	\UnicodeEncodingName{"0E3F}
1105	\DeclareTextSymbol{\SS}	\UnicodeEncodingName{"1E9E}
1106	\DeclareTextSymbol{\textcompwordmark}	\UnicodeEncodingName{"200C}
1107	\DeclareTextSymbol{\textendash}	\UnicodeEncodingName{"2013}
1108	\DeclareTextSymbol{\textemdash}	\UnicodeEncodingName{"2014}
1109	\DeclareTextSymbol{\textbardbl}	\UnicodeEncodingName{"2016}
1110	\DeclareTextSymbol{\textquoteleft}	\UnicodeEncodingName{"2018}
1111	\DeclareTextSymbol{\textquoteright}	\UnicodeEncodingName{"2019}
1112	\DeclareTextSymbol{\quotesinglbase}	\UnicodeEncodingName{"201A}
1113	\DeclareTextSymbol{\textquotedblleft}	\UnicodeEncodingName{"201C}
1114	\DeclareTextSymbol{\textquotedblright}	\UnicodeEncodingName{"201D}
1115	\DeclareTextSymbol{\quotedblbase}	\UnicodeEncodingName{"201E}
1116	\DeclareTextSymbol{\textdagger}	\UnicodeEncodingName{"2020}
1117	\DeclareTextSymbol{\textdaggerdbl}	\UnicodeEncodingName{"2021}
1118	\DeclareTextSymbol{\textbullet}	\UnicodeEncodingName{"2022}
1119	\DeclareTextSymbol{\textellipsis}	\UnicodeEncodingName{"2026}
1120	\DeclareTextSymbol{\textperthousand}	\UnicodeEncodingName{"2030}
1121	\DeclareTextSymbol{\textpertenthousand}	\UnicodeEncodingName{"2031}
1122	\DeclareTextSymbol{\guilsinglleft}	\UnicodeEncodingName{"2039}
1123	\DeclareTextSymbol{\guilsinglright}	\UnicodeEncodingName{"203A}
1124	\DeclareTextSymbol{\textreferencemark}	\UnicodeEncodingName{"203B}
1125	\DeclareTextSymbol{\textinterrobang}	\UnicodeEncodingName{"203D}
1126	\DeclareTextSymbol{\textfractionsolidus}	\UnicodeEncodingName{"2044}
1127	\DeclareTextSymbol{\textlquill}	\UnicodeEncodingName{"2045}
1128	\DeclareTextSymbol{\textrquill}	\UnicodeEncodingName{"2046}
1129	\DeclareTextSymbol{\textdiscount}	\UnicodeEncodingName{"2052}
1130	\DeclareTextSymbol{\textcolonmonetary}	\UnicodeEncodingName{"20A1}
1131	\DeclareTextSymbol{\textlira}	\UnicodeEncodingName{"20A4}
1132	\DeclareTextSymbol{\textnaira}	\UnicodeEncodingName{"20A6}
1133	\DeclareTextSymbol{\textwon}	\UnicodeEncodingName{"20A9}
1134	\DeclareTextSymbol{\textdong}	\UnicodeEncodingName{"20AB}
1135	\DeclareTextSymbol{\texteuro}	\UnicodeEncodingName{"20AC}
1136	\DeclareTextSymbol{\textpeso}	\UnicodeEncodingName{"20B1}
1137	\DeclareTextSymbol{\textcelsius}	\UnicodeEncodingName{"2103}
1138	\DeclareTextSymbol{\textnumero}	\UnicodeEncodingName{"2116}
1139	\DeclareTextSymbol{\textcircledP}	\UnicodeEncodingName{"2117}
1140	\DeclareTextSymbol{\textrecipe}	\UnicodeEncodingName{"211E}
1141	\DeclareTextSymbol{\textservicemark}	\UnicodeEncodingName{"2120}
1142	\DeclareTextSymbol{\texttrademark}	\UnicodeEncodingName{"2122}
1143	\DeclareTextSymbol{\textohm}	\UnicodeEncodingName{"2126}
1144	\DeclareTextSymbol{\textmho}	\UnicodeEncodingName{"2127}
1145	\DeclareTextSymbol{\textestimated}	\UnicodeEncodingName{"212E}
1146	\DeclareTextSymbol{\textleftarrow}	\UnicodeEncodingName{"2190}
1147	\DeclareTextSymbol{\textuparrow}	\UnicodeEncodingName{"2191}
1148	\DeclareTextSymbol{\textrightarrow}	\UnicodeEncodingName{"2192}
1149	\DeclareTextSymbol{\textdownarrow}	\UnicodeEncodingName{"2193}
1150	\DeclareTextSymbol{\textminus}	\UnicodeEncodingName{"2212}
1151		
1152	\DeclareTextSymbol{\Hwithstroke}	\UnicodeEncodingName{"0126}

```
1153 \DeclareTextSymbol{\hwithstroke} \UnicodeEncodingName{"0127}
```

Not all fonts have U+2217 but using U+002A requires some adjustment.

```
1154 \DeclareTextCommand{\textasteriskcentered}\UnicodeEncodingName{%
1155   \iffontchar\font"2217 \char"2217 \else
1156     \begingroup
1157       \fontsize
1158       {\the\dimexpr1.2\dimexpr\f@size pt\relax}%
1159       {\f@baselineskip}%
1160       \selectfont
1161       \raisebox{-0.6ex}{\dimexpr\height-0.6ex}[0pt]{*}%
1162     \endgroup
1163   \fi
1164 }

1165 \DeclareTextSymbol{\textsurd} \UnicodeEncodingName{"221A}
1166 \DeclareTextSymbol{\textlangle} \UnicodeEncodingName{"2329}
1167 \DeclareTextSymbol{\textrangle} \UnicodeEncodingName{"232A}
1168 \DeclareTextSymbol{\textblank} \UnicodeEncodingName{"2422}
1169 \DeclareTextSymbol{\textvisiblespace} \UnicodeEncodingName{"2423}
1170 \DeclareTextSymbol{\textopenbullet} \UnicodeEncodingName{"25E6}
1171 \DeclareTextSymbol{\textbigcircle} \UnicodeEncodingName{"25EF}
1172 \DeclareTextSymbol{\textmusicalnote} \UnicodeEncodingName{"266A}
1173 \DeclareTextSymbol{\textmarried} \UnicodeEncodingName{"26AD}
1174 \DeclareTextSymbol{\textdivorced} \UnicodeEncodingName{"26AE}
1175 \DeclareTextSymbol{\textinterrobangdown} \UnicodeEncodingName{"2E18}
```

Accents must be declared before the composites that use them.

```
1176 \DeclareUnicodeAccent{\` } \UnicodeEncodingName{"0300}
1177 \DeclareUnicodeAccent{\' } \UnicodeEncodingName{"0301}
1178 \DeclareUnicodeAccent{\^ } \UnicodeEncodingName{"0302}
1179 \DeclareUnicodeAccent{\~ } \UnicodeEncodingName{"0303}
1180 \DeclareUnicodeAccent{\= } \UnicodeEncodingName{"0304}
1181 \DeclareUnicodeAccent{\u } \UnicodeEncodingName{"0306}
1182 \DeclareUnicodeAccent{\. } \UnicodeEncodingName{"0307}
1183 \DeclareUnicodeAccent{\" } \UnicodeEncodingName{"0308}
1184 \DeclareUnicodeAccent{\r } \UnicodeEncodingName{"030A}
1185 \DeclareUnicodeAccent{\H } \UnicodeEncodingName{"030B}
1186 \DeclareUnicodeAccent{\v } \UnicodeEncodingName{"030C}
1187 \DeclareUnicodeAccent{\b } \UnicodeEncodingName{"0332}
1188 \DeclareUnicodeAccent{\d } \UnicodeEncodingName{"0323}
1189 \DeclareUnicodeAccent{\c } \UnicodeEncodingName{"0327}
1190 \DeclareUnicodeAccent{\k } \UnicodeEncodingName{"0328}
1191 \DeclareTextCommand\textcommabelow \UnicodeEncodingName[1]
1192   {\hmode\bgroup\oalign{\null#1\cr\hidewidth\raise-.31ex
1193     \hbox{\check@mathfonts\fontsize\ssf@size\z@
1194       \math@fontsfalse\selectfont,}\hidewidth}\egroup}

1195 \DeclareUnicodeComposite{\^ } {}{"005E}
1196 \DeclareUnicodeComposite{\~ } {}{"007E}

1197 \DeclareUnicodeComposite{\` } {A}{"00C0}
1198 \DeclareUnicodeComposite{\' } {A}{"00C1}
1199 \DeclareUnicodeComposite{\^ } {A}{"00C2}
1200 \DeclareUnicodeComposite{\~ } {A}{"00C3}
1201 \DeclareUnicodeComposite{\" } {A}{"00C4}
```

1202 \DeclareUnicodeComposite{\r}	{A}{"00C5}
1203 \DeclareUnicodeComposite{\c}	{C}{"00C7}
1204 \DeclareUnicodeComposite{\'}	{E}{"00C8}
1205 \DeclareUnicodeComposite{\'}	{E}{"00C9}
1206 \DeclareUnicodeComposite{\^}	{E}{"00CA}
1207 \DeclareUnicodeComposite{\"}}	{E}{"00CB}
1208 \DeclareUnicodeComposite{\'}	{I}{"00CC}
1209 \DeclareUnicodeComposite{\'}	{I}{"00CD}
1210 \DeclareUnicodeComposite{\^}	{I}{"00CE}
1211 \DeclareUnicodeComposite{\"}}	{I}{"00CF}
1212 \DeclareUnicodeComposite{\~}	{N}{"00D1}
1213 \DeclareUnicodeComposite{\'}	{O}{"00D2}
1214 \DeclareUnicodeComposite{\'}	{O}{"00D3}
1215 \DeclareUnicodeComposite{\^}	{O}{"00D4}
1216 \DeclareUnicodeComposite{\~}	{O}{"00D5}
1217 \DeclareUnicodeComposite{\"}}	{O}{"00D6}
1218 \DeclareUnicodeComposite{\'}	{U}{"00D9}
1219 \DeclareUnicodeComposite{\'}	{U}{"00DA}
1220 \DeclareUnicodeComposite{\^}	{U}{"00DB}
1221 \DeclareUnicodeComposite{\"}}	{U}{"00DC}
1222 \DeclareUnicodeComposite{\'}	{Y}{"00DD}
1223 \DeclareUnicodeComposite{\'}	{a}{"00E0}
1224 \DeclareUnicodeComposite{\'}	{a}{"00E1}
1225 \DeclareUnicodeComposite{\^}	{a}{"00E2}
1226 \DeclareUnicodeComposite{\~}	{a}{"00E3}
1227 \DeclareUnicodeComposite{\"}}	{a}{"00E4}
1228 \DeclareUnicodeComposite{\r}	{a}{"00E5}
1229 \DeclareUnicodeComposite{\c}	{c}{"00E7}
1230 \DeclareUnicodeComposite{\'}	{e}{"00E8}
1231 \DeclareUnicodeComposite{\'}	{e}{"00E9}
1232 \DeclareUnicodeComposite{\^}	{e}{"00EA}
1233 \DeclareUnicodeComposite{\"}}	{e}{"00EB}
1234 \DeclareUnicodeComposite{\'}	\i {"00EC}
1235 \DeclareUnicodeComposite{\'}	{i}{"00EC}
1236 \DeclareUnicodeComposite{\'}	\i {"00ED}
1237 \DeclareUnicodeComposite{\'}	{i}{"00ED}
1238 \DeclareUnicodeComposite{\^}	\i {"00EE}
1239 \DeclareUnicodeComposite{\^}	{i}{"00EE}
1240 \DeclareUnicodeComposite{\"}}	\i {"00EF}
1241 \DeclareUnicodeComposite{\"}}	{i}{"00EF}
1242 \DeclareUnicodeComposite{\~}	{n}{"00F1}
1243 \DeclareUnicodeComposite{\'}	{o}{"00F2}
1244 \DeclareUnicodeComposite{\'}	{o}{"00F3}
1245 \DeclareUnicodeComposite{\^}	{o}{"00F4}
1246 \DeclareUnicodeComposite{\~}	{o}{"00F5}
1247 \DeclareUnicodeComposite{\"}}	{o}{"00F6}
1248 \DeclareUnicodeComposite{\'}	{u}{"00F9}
1249 \DeclareUnicodeComposite{\'}	{u}{"00FA}
1250 \DeclareUnicodeComposite{\^}	{u}{"00FB}
1251 \DeclareUnicodeComposite{\"}}	{u}{"00FC}
1252 \DeclareUnicodeComposite{\'}	{y}{"00FD}
1253 \DeclareUnicodeComposite{\"}}	{y}{"00FF}
1254 \DeclareUnicodeComposite{\=}	{A}{"0100}
1255 \DeclareUnicodeComposite{\=}	{a}{"0101}

1256 \DeclareUnicodeComposite{\u}	{A}-{ "0102}
1257 \DeclareUnicodeComposite{\u}	{a}-{ "0103}
1258 \DeclareUnicodeComposite{\k}	{A}-{ "0104}
1259 \DeclareUnicodeComposite{\k}	{a}-{ "0105}
1260 \DeclareUnicodeComposite{\'}	{C}-{ "0106}
1261 \DeclareUnicodeComposite{\'}	{c}-{ "0107}
1262 \DeclareUnicodeComposite{\^}	{C}-{ "0108}
1263 \DeclareUnicodeComposite{\^}	{c}-{ "0109}
1264 \DeclareUnicodeComposite{\.}	{C}-{ "010A}
1265 \DeclareUnicodeComposite{\.}	{c}-{ "010B}
1266 \DeclareUnicodeComposite{\v}	{C}-{ "010C}
1267 \DeclareUnicodeComposite{\v}	{c}-{ "010D}
1268 \DeclareUnicodeComposite{\v}	{D}-{ "010E}
1269 \DeclareUnicodeComposite{\v}	{d}-{ "010F}
1270 \DeclareUnicodeComposite{\=}	{E}-{ "0112}
1271 \DeclareUnicodeComposite{\=}	{e}-{ "0113}
1272 \DeclareUnicodeComposite{\u}	{E}-{ "0114}
1273 \DeclareUnicodeComposite{\u}	{e}-{ "0115}
1274 \DeclareUnicodeComposite{\.}	{E}-{ "0116}
1275 \DeclareUnicodeComposite{\.}	{e}-{ "0117}
1276 \DeclareUnicodeComposite{\k}	{E}-{ "0118}
1277 \DeclareUnicodeComposite{\k}	{e}-{ "0119}
1278 \DeclareUnicodeComposite{\v}	{E}-{ "011A}
1279 \DeclareUnicodeComposite{\v}	{e}-{ "011B}
1280 \DeclareUnicodeComposite{\^}	{G}-{ "011C}
1281 \DeclareUnicodeComposite{\^}	{g}-{ "011D}
1282 \DeclareUnicodeComposite{\u}	{G}-{ "011E}
1283 \DeclareUnicodeComposite{\u}	{g}-{ "011F}
1284 \DeclareUnicodeComposite{\.}	{G}-{ "0120}
1285 \DeclareUnicodeComposite{\.}	{g}-{ "0121}
1286 \DeclareUnicodeComposite{\c}	{G}-{ "0122}
1287 \DeclareUnicodeComposite{\c}	{g}-{ "0123}
1288 \DeclareUnicodeComposite{\^}	{H}-{ "0124}
1289 \DeclareUnicodeComposite{\^}	{h}-{ "0125}
1290 \DeclareUnicodeComposite{\~}	{I}-{ "0128}
1291 \DeclareUnicodeComposite{\~}	\i { "0129}
1292 \DeclareUnicodeComposite{\~}	{i}-{ "0129}
1293 \DeclareUnicodeComposite{\=}	{I}-{ "012A}
1294 \DeclareUnicodeComposite{\=}	\i { "012B}
1295 \DeclareUnicodeComposite{\=}	{i}-{ "012B}
1296 \DeclareUnicodeComposite{\u}	{I}-{ "012C}
1297 \DeclareUnicodeComposite{\u}	\i { "012D}
1298 \DeclareUnicodeComposite{\u}	{i}-{ "012D}
1299 \DeclareUnicodeComposite{\k}	{I}-{ "012E}
1300 \DeclareUnicodeComposite{\k}	\i { "012F}
1301 \DeclareUnicodeComposite{\k}	{i}-{ "012F}
1302 \DeclareUnicodeComposite{\.}	{I}-{ "0130}
1303 \DeclareUnicodeComposite{\^}	{J}-{ "0134}
1304 \DeclareUnicodeComposite{\^}	\j { "0135}
1305 \DeclareUnicodeComposite{\^}	{j}-{ "0135}
1306 \DeclareUnicodeComposite{\c}	{K}-{ "0136}
1307 \DeclareUnicodeComposite{\c}	{k}-{ "0137}
1308 \DeclareUnicodeComposite{\'}	{L}-{ "0139}
1309 \DeclareUnicodeComposite{\'}	{l}-{ "013A}

1310 \DeclareUnicodeComposite{c}	{L}-{013B}
1311 \DeclareUnicodeComposite{c}	{l}-{013C}
1312 \DeclareUnicodeComposite{v}	{L}-{013D}
1313 \DeclareUnicodeComposite{v}	{l}-{013E}
1314 \DeclareUnicodeComposite{'}	{N}-{0143}
1315 \DeclareUnicodeComposite{'}	{n}-{0144}
1316 \DeclareUnicodeComposite{c}	{N}-{0145}
1317 \DeclareUnicodeComposite{c}	{n}-{0146}
1318 \DeclareUnicodeComposite{v}	{N}-{0147}
1319 \DeclareUnicodeComposite{v}	{n}-{0148}
1320 \DeclareUnicodeComposite{=}	{O}-{014C}
1321 \DeclareUnicodeComposite{=}	{o}-{014D}
1322 \DeclareUnicodeComposite{u}	{O}-{014E}
1323 \DeclareUnicodeComposite{u}	{o}-{014F}
1324 \DeclareUnicodeComposite{H}	{O}-{0150}
1325 \DeclareUnicodeComposite{H}	{o}-{0151}
1326 \DeclareUnicodeComposite{'}	{R}-{0154}
1327 \DeclareUnicodeComposite{'}	{r}-{0155}
1328 \DeclareUnicodeComposite{c}	{R}-{0156}
1329 \DeclareUnicodeComposite{c}	{r}-{0157}
1330 \DeclareUnicodeComposite{v}	{R}-{0158}
1331 \DeclareUnicodeComposite{v}	{r}-{0159}
1332 \DeclareUnicodeComposite{'}	{S}-{015A}
1333 \DeclareUnicodeComposite{'}	{s}-{015B}
1334 \DeclareUnicodeComposite{^}	{S}-{015C}
1335 \DeclareUnicodeComposite{^}	{s}-{015D}
1336 \DeclareUnicodeComposite{c}	{S}-{015E}
1337 \DeclareUnicodeComposite{c}	{s}-{015F}
1338 \DeclareUnicodeComposite{v}	{S}-{0160}
1339 \DeclareUnicodeComposite{v}	{s}-{0161}
1340 \DeclareUnicodeComposite{c}	{T}-{0162}
1341 \DeclareUnicodeComposite{c}	{t}-{0163}
1342 \DeclareUnicodeComposite{v}	{T}-{0164}
1343 \DeclareUnicodeComposite{v}	{t}-{0165}
1344 \DeclareUnicodeComposite{~}	{U}-{0168}
1345 \DeclareUnicodeComposite{~}	{u}-{0169}
1346 \DeclareUnicodeComposite{=}	{U}-{016A}
1347 \DeclareUnicodeComposite{=}	{u}-{016B}
1348 \DeclareUnicodeComposite{u}	{U}-{016C}
1349 \DeclareUnicodeComposite{u}	{u}-{016D}
1350 \DeclareUnicodeComposite{r}	{U}-{016E}
1351 \DeclareUnicodeComposite{r}	{u}-{016F}
1352 \DeclareUnicodeComposite{H}	{U}-{0170}
1353 \DeclareUnicodeComposite{H}	{u}-{0171}
1354 \DeclareUnicodeComposite{k}	{U}-{0172}
1355 \DeclareUnicodeComposite{k}	{u}-{0173}
1356 \DeclareUnicodeComposite{^}	{W}-{0174}
1357 \DeclareUnicodeComposite{^}	{w}-{0175}
1358 \DeclareUnicodeComposite{^}	{Y}-{0176}
1359 \DeclareUnicodeComposite{^}	{y}-{0177}
1360 \DeclareUnicodeComposite{"}	{Y}-{0178}
1361 \DeclareUnicodeComposite{'}	{Z}-{0179}
1362 \DeclareUnicodeComposite{'}	{z}-{017A}
1363 \DeclareUnicodeComposite{.}	{Z}-{017B}

1364 \DeclareUnicodeComposite{.}	{z}{017C}
1365 \DeclareUnicodeComposite{v}	{Z}{017D}
1366 \DeclareUnicodeComposite{v}	{z}{017E}
1367 \DeclareUnicodeComposite{v}	{A}{01CD}
1368 \DeclareUnicodeComposite{v}	{a}{01CE}
1369 \DeclareUnicodeComposite{v}	{I}{01CF}
1370 \DeclareUnicodeComposite{v}	\i {01D0}
1371 \DeclareUnicodeComposite{v}	{i}{01D0}
1372 \DeclareUnicodeComposite{v}	{O}{01D1}
1373 \DeclareUnicodeComposite{v}	{o}{01D2}
1374 \DeclareUnicodeComposite{v}	{U}{01D3}
1375 \DeclareUnicodeComposite{v}	{u}{01D4}
1376 \DeclareUnicodeComposite{=}	\AE{01E2}
1377 \DeclareUnicodeComposite{=}	\ae{01E3}
1378 \DeclareUnicodeComposite{v}	{G}{01E6}
1379 \DeclareUnicodeComposite{v}	{g}{01E7}
1380 \DeclareUnicodeComposite{v}	{K}{01E8}
1381 \DeclareUnicodeComposite{v}	{k}{01E9}
1382 \DeclareUnicodeComposite{k}	{O}{01EA}
1383 \DeclareUnicodeComposite{k}	{o}{01EB}
1384 \DeclareUnicodeComposite{v}	\j {01F0}
1385 \DeclareUnicodeComposite{v}	{j}{01F0}
1386 \DeclareUnicodeComposite{'}	{G}{01F4}
1387 \DeclareUnicodeComposite{'}	{g}{01F5}
1388 \DeclareUnicodeComposite{\textcommabelow}	{S}{0218}
1389 \DeclareUnicodeComposite{\textcommabelow}	{s}{0219}
1390 \DeclareUnicodeComposite{\textcommabelow}	{T}{021A}
1391 \DeclareUnicodeComposite{\textcommabelow}	{t}{021B}
1392 \DeclareUnicodeComposite{=}	{Y}{0232}
1393 \DeclareUnicodeComposite{=}	{y}{0232}
1394 \DeclareUnicodeComposite{.}	{B}{1E02}
1395 \DeclareUnicodeComposite{.}	{b}{1E03}
1396 \DeclareUnicodeComposite{d}	{B}{1E04}
1397 \DeclareUnicodeComposite{d}	{b}{1E05}
1398 \DeclareUnicodeComposite{d}	{D}{1E0C}
1399 \DeclareUnicodeComposite{d}	{d}{1E0D}
1400 \DeclareUnicodeComposite{=}	{G}{1E20}
1401 \DeclareUnicodeComposite{=}	{g}{1E21}
1402 \DeclareUnicodeComposite{d}	{H}{1E24}
1403 \DeclareUnicodeComposite{d}	{h}{1E25}
1404 \DeclareUnicodeComposite{d}	{K}{1E32}
1405 \DeclareUnicodeComposite{d}	{k}{1E33}
1406 \DeclareUnicodeComposite{d}	{L}{1E36}
1407 \DeclareUnicodeComposite{d}	{l}{1E37}
1408 \DeclareUnicodeComposite{d}	{M}{1E42}
1409 \DeclareUnicodeComposite{d}	{m}{1E43}
1410 \DeclareUnicodeComposite{d}	{N}{1E46}
1411 \DeclareUnicodeComposite{d}	{n}{1E47}
1412 \DeclareUnicodeComposite{d}	{R}{1E5A}
1413 \DeclareUnicodeComposite{d}	{r}{1E5B}
1414 \DeclareUnicodeComposite{d}	{S}{1E62}
1415 \DeclareUnicodeComposite{d}	{s}{1E63}
1416 \DeclareUnicodeComposite{d}	{T}{1E6C}
1417 \DeclareUnicodeComposite{d}	{t}{1E6D}





```

1450 \CYRHRDSN\cyri\CYRI\cyrie\CYRIE\cyrii\CYRII\cyrishrt\CYRISHRT
1451 \cyrishrtdsc\CYRISHRTDSC\cyrizh\CYRIZH\cyrje\CYRJE\cyrk\CYRK
1452 \cyrkbeak\CYRKBEAK\cyrkdisc\CYRKDSC\cyrkchrs\CYRKHCRS\cyrkhhk
1453 \CYRKHK\cyrkvcrs\CYRKVCRS\cyr1\CYRL\cyrlldsc\CYRLDSC\cyr1hk
1454 \CYRLHK\cyr1je\CYRLJE\cyrm\CYRM\cyrmldsc\CYRMDSC\cyrmhk\CYRMHK
1455 \cyrn\CYRN\cyrndsc\CYRNDSC\cyrng\CYRNG\cyrnhk\CYRNHK\cyrnje
1456 \CYRNJE\cyrn1hk\CYRNLHK\cyro\CYRO\cyrotld\CYROTLD\cyrp\CYRP
1457 \cyrphk\CYRPHK\cyrq\CYRQ\cyrr\CYRR\cyrrdsc\CYRRDSC\cyrrhk
1458 \CYRRHK\cyrrtick\CYRRTICK\cyrs\CYRS\cyrsacrs\CYRSACRS
1459 \cyrschwa\CYRSCHWA\cyrsdsc\CYRSDSC\cyrsemisftsn\CYRSEMISFTSN
1460 \cyrsftsn\CYRSFTSN\cyrsh\CYRSH\cyrshch\CYRSHCH\cyrshha\CYRSHHA
1461 \cyrt\CYRT\cyrtldsc\CYRTDSC\cyrtetse\CYRTETSE\cyrtshe\CYRTSHE
1462 \cyru\CYRU\cyrushrt\CYRUSHRT\cyrv\CYRV\cyrw\CYRW\cyr\CYRY
1463 \cyrya\CYRYA\cyryat\CYRYAT\cyryhcrs\CYRYHCRS\cyryi\CYRYI\cyryo
1464 \CYRYO\cyryu\CYRYU\cyrz\CYRZ\cyzldsc\CYRZDSC\cyzhdsc\CYRZH
1465 \cyzhdsc\CYRZHDSC}%
1466 \let\update@uclc@with@cyrillic\relax
1467 }

```

Here we process each option:

```

1468 \DeclareOption*{%
1469   \let\encodingdefault\CurrentOption
1470   \edef\reserved@f{%
1471     \lowercase{\def\noexpand\reserved@f{\CurrentOption enc.def}}}%
1472   \reserved@f
1473   \InputIfFileExists\reserved@f
1474     {\PackageError{fontenc}%
1475       {Encoding file ‘\reserved@f’ not found.%
1476       \MessageBreak
1477       You might have misspelt the name of the encoding}%
1478     {Necessary code for this encoding was not
1479     loaded.\MessageBreak
1480     Thus calling the encoding later on will
1481     produce further error messages.}}%
1482   \let\reserved@f\relax

```

In case the current encoding is one of a list of known cyrillic ones we extend the `\@uclclist`:

```

1483   \expandafter\in@\expandafter{\CurrentOption}%
1484                                     {T2A,T2B,T2C,X2,LCY,OT2}%
1485   \ifin@

```

But only if it hasn't already been extended. This might happen if there are several calls to fontenc loading one of the above encodings. If we don't do this check the `\@uclclist` gets unnecessarily big, slowing down the processing at runtime.

```

1486     \expandafter\in@\expandafter\cyra\expandafter
1487                                     {\@uclclist}%
1488   \ifin@
1489   \else
1490     \update@uclc@with@cyrillic
1491   \fi
1492 \fi
1493 }
1494 \ProcessOptions*

```

```
1495 \fontencoding\encodingdefault\selectfont
```

To save some space we get rid of the macro extending the `\@uclclist` (might have happened already).

```
1496 \let\update@uclc@with@cyrillic\relax
```

Finally we pretend that the `fontenc` package wasn't read in. This allows for using it several times, e.g., in a class file and in the preamble (at the cost of not getting any version info). That kind of hackery shows that using a general purpose package just for loading an encoding is not the right kind of interface for setting up encodings — it will get replaced at some point in the future.

```
1497 \global\expandafter\let\csname ver@fontenc.sty\endcsname\relax
```

```
1498 \global\expandafter\let\csname opt@fontenc.sty\endcsname\relax
```

```
1499 \global\let\@ifl@ter@@\@ifl@ter
```

```
1500 \def\@ifl@ter#1#2#3#4#5{\global\let\@ifl@ter\@ifl@ter@@}
```

```
1501 \endpackage
```

## 21.2 The `textcomp` package

This one is for the `TS1` encoding which contains text symbols for use with the `T1`-encoded text fonts. It therefore first inputs the file `TS1enc.def` and then sets (or resets) the defaults for the symbols it contains. The result of this is that when one of these symbols is accessed and the current encoding does not provide it, the symbol will be supplied by a silent, local change to this encoding.

```
1502 (*TS1sty)
```

Since many PostScript fonts only implement a subset of `TS1` many commands only produce black blobs of ink. To resolve the resulting problems a number of options have been introduced and some code has been developed to distinguish sub-encodings.

The sub-encodings have a numerical id and are defined as follows for `TS1`:

**#5** those `TS1` symbols that are also in the ISO-Adobe character set; without `textcurrency`, which is often misused for the Euro. Older Type1 fonts from the non- $\TeX$  world provide only this subset.

**#4** = **#5** + `\texteuro`. Most newer fonts provide this.

**#3** = **#4** + `\textomega`. Can also be described as  $TS1 \cap (ISO-Adobe \cup MacRoman)$ . (Except for the missing "currency".)

**#2** = **#3** + `\textestimated` + `textcurrency`. Can also be described as  $TS1 \cap Adobe-Western-2$ . This may be relevant for OpenType fonts, which usually show the Adobe-Western-2 character set.

**#1** = `TS1` without `\textcircled` and `\t`. These two glyphs are often not implemented and if their kernel defaults are changed commands like `\copyright` unnecessarily fail.

**#0** = full `TS1`

And here a summary to go in the transcript file:

```
1503 \PackageInfo{textcomp}{Sub-encoding information:\MessageBreak
```

```
1504 \space\space 5 = only ISO-Adobe without
```

```

1505                                \string\textcurrency\MessageBreak
1506    \space\space 4 = 5 + \string\texteuro\MessageBreak
1507    \space\space 3 = 4 + \string\textohm\MessageBreak
1508    \space\space 2 = 3 + \noexpand\textestimated+
1509                                \string\textcurrency\MessageBreak
1510    \space\space 1 = TS1 - \noexpand\textcircled-
1511                                \string\t\MessageBreak
1512    \space\space 0 = TS1 (full)\MessageBreak
1513    Font families with sub-encoding setting implement\MessageBreak
1514    only a restricted character set as indicated.\MessageBreak
1515    Family '?' is the default used for unknown fonts.\MessageBreak
1516    See the documentation for details\@gobble}

```

**\DeclareEncodingSubset** An encoding subset to which a font family belongs is declared by the command **\DeclareEncodingSubset** that takes the major encoding as the first argument (e.g., TS1), the family name as the second argument (e.g., cmr), and the subset encoding id as a third, (e.g., 0 for cmr).

The default encoding subset to use when nothing is known about the current font family is named ?.

```

1517 \def\DeclareEncodingSubset#1#2#3{%
1518     \ifundefined{#1:#2}%
1519         {\PackageInfo{textcomp}{Setting #2 sub-encoding to #1/#3}}%
1520         {\PackageInfo{textcomp}{Changing #2 sub-encoding to #1/#3}}%
1521     \@namedef{#1:#2}{#3}}
1522 \@onlypreamble\DeclareEncodingSubset

```

The options for the package are the following:

**safe** for unknown font families enables only symbols that are also in the ISO-Adobe character set; without "currency", which is often misused for the Euro. Older Type1 fonts from the non-Tex world provide only this subset.

**euro** enables the "safe" symbols plus the **\texteuro** command. Most newer fonts provide this.

**full** enables all TS1 commands; useful only with fonts like EC or CM bright.

**almostfull** same as "full", except that **\textcircled** and **\t** are *not* redefined from their defaults to avoid that commands like **\copyright** suddenly no longer work.

**force** ignore all subset encoding definitions stored in the package itself or in the configuration file and always use the default subset as specified by one of the other options (seldom useful, only dangerous).

**\iftc@forced** Switch used to implement the **force** option

```

1523 \newif\iftc@forced    \tc@forcedfalse

```

This is implemented by defining the default subset:

```

1524 \DeclareOption{full}{\DeclareEncodingSubset{TS1}{?}{0}}
1525 \DeclareOption{almostfull}{\DeclareEncodingSubset{TS1}{?}{1}}
1526 \DeclareOption{euro}{\DeclareEncodingSubset{TS1}{?}{4}}
1527 \DeclareOption{safe}{\DeclareEncodingSubset{TS1}{?}{5}}

```

The default is “almostfull” which means that old documents will work except that `\textcircled` and `\t` will use the kernel defaults (with the advantage that this also works if the current font (as often the case) doesn’t implement these glyphs.

The “force” option simply sets the switch to true.

```
1528 \DeclareOption{force}{\tc@forcedtrue}
```

The suggestions to user is to use the “safe” option always unless that balks in which case they could switch to “almostfull” but then better check their output manually.

```
1529 \def\tc@errorwarn{\PackageError}
```

```
1530 \DeclareOption{warn}{\gdef\tc@errorwarn#1#2#3{\PackageWarning{#1}{#2}}}
```

```
1531 \ExecuteOptions{almostfull}
```

```
1532 \ProcessOptions\relax
```

`\CheckEncodingSubset` The command `\CheckEncodingSubset` will check if the current font family has the right encoding subset to typeset a certain command. It takes five arguments as follows: first argument is either `\UseTextSymbol`, `\UseTextAccent` depending on whether or not the symbol is a text symbol or a text accent.

The second argument is the encoding from which this symbol should be fetched.

The third argument is either a fake accessor command or an error message. the code in that argument (if ever executed) receives two arguments: `#2` and `#5` of `\CheckEncodingSubset`.

Argument four is the subset encoding id to test against: if this value is higher than the subset id of the current font family then we typeset the symbol, i.e., execute `#1{#2}#5` otherwise it runs `#3#5`, e.g., to produce an error message or fake the glyph somehow.

Argument five is the symbol or accent command that is being checked.

For usage examples see definitions below.

```
1533 \iftc@forced
```

If the “force” option was given we always use the default for testing against.

```
1534 \def\CheckEncodingSubset#1#2#3#4#5{%
```

```
1535   \ifnum #4>%
```

```
1536       0\csname #2:\endcsname
```

```
1537       \relax
```

```
1538   \expandafter\@firstoftwo
```

```
1539   \else
```

```
1540   \expandafter\@secondoftwo
```

```
1541   \fi
```

```
1542   {#1{#2}}{#3}%
```

```
1543   #5%
```

```
1544 }
```

In normal circumstances the test is a bit more complicated: first check if there exists a macro `\langle arg2\rangle:\langle current-family\rangle` and if so use that value to test against, otherwise use the default to test against.

```
1545 \else
```

```
1546 \def\CheckEncodingSubset#1#2#3#4#5{%
```

```
1547   \ifnum #4>%
```

```
1548       \expandafter\ifx\csname #2:f@family\endcsname\relax
```

```
1549       0\csname #2:\endcsname
```

```
1550       \else
```

```

1551      \csname #2:\f@family\endcsname
1552      \fi
1553      \relax
1554      \expandafter\@firstoftwo
1555      \else
1556      \expandafter\@secondoftwo
1557      \fi
1558      {#1{#2}}{#3}%
1559      #5%
1560 }
1561 \fi

\tc@subst
1562 \def\tc@subst#1{%
1563   \tc@errorwarn{textcomp}% % should be latex error if general
1564   {Symbol \string#1 not provided by\MessageBreak
1565    font family \f@family\space
1566    in TS1 encoding.\MessageBreak Default family used instead}\@eha
1567   \bgroup\fontfamily\textcompsubstdefault\selectfont#1\egroup
1568 }

```

\textcompsubstdefault

```

1569 \def\textcompsubstdefault{cmr}

```

\tc@error \tc@error is going to be used in arg #3 of \CheckEncodingSubset when a symbol is not available in a certain font family. It gets pass the encoding it normally lives in (arg one) and the name of the symbol or accent that has a problem.

```

1570 % error commands take argument:
1571 % #1 symbol to be used
1572 \def\tc@error#1{%
1573   \PackageError{textcomp}% % should be latex error if general
1574   {Accent \string#1 not provided by\MessageBreak
1575    font family \f@family\space
1576    in TS1 encoding}\@eha
1577 }

```

\tc@fake@euro \tc@fake@euro is an example of a “fake” definition to use in arg #3 of \CheckEncodingSubset when a symbol is not available in a certain font family. Here we produce an Euro symbol by combining a “C” with a “=”.

```

1578 \def\tc@fake@euro#1{%
1579   \leavevmode
1580   \PackageInfo{textcomp}{Faking \noexpand#1for font family
1581                        \f@family\MessageBreak in TS1 encoding}%
1582   \valign{##\cr
1583     \vfil\hbox to 0.07em{\dimen@ \f@size\p@
1584                        \math@fontsfalse
1585                        \fontsize{.7\dimen@}\z@\selectfont=\hss}%
1586     \vfil\cr%
1587     \hbox{C}\crr
1588   }%
1589 }

```

`\tc@check@symbol` These are two abbreviations that we use below to check symbols and accents in  
`\tc@check@accent` TS1. Only there to save some space, e.g., we can then write

```
\DeclareTextCommandDefault{\textcurrency}{\tc@check@symbol3\textcurrency}
```

to ensure that `\textcurrency` is only typeset if the current font has a TS1 subset id of less than 3. Otherwise `\tc@error` is called telling the user that for this font family `\textcurrency` is not available.

```
1590 \def\tc@check@symbol{\CheckEncodingSubset\UseTextSymbol{TS1}\tc@subst}
1591 \def\tc@check@accent{\CheckEncodingSubset\UseTextAccent{TS1}\tc@error}
```

We start with the commands that are “safe” and which can be unconditionally set up, first the accents...

```
1592 \DeclareTextAccentDefault{\capitalcedilla}{TS1}
1593 \DeclareTextAccentDefault{\capitalogonek}{TS1}
1594 \DeclareTextAccentDefault{\capitalgrave}{TS1}
1595 \DeclareTextAccentDefault{\capitalacute}{TS1}
1596 \DeclareTextAccentDefault{\capitalcircumflex}{TS1}
1597 \DeclareTextAccentDefault{\capitaltilde}{TS1}
1598 \DeclareTextAccentDefault{\capitaldieresis}{TS1}
1599 \DeclareTextAccentDefault{\capitalhungarumlaut}{TS1}
1600 \DeclareTextAccentDefault{\capitalring}{TS1}
1601 \DeclareTextAccentDefault{\capitalcaron}{TS1}
1602 \DeclareTextAccentDefault{\capitalbreve}{TS1}
1603 \DeclareTextAccentDefault{\capitalmacron}{TS1}
1604 \DeclareTextAccentDefault{\capitaldotaccent}{TS1}
```

...and then the other glyphs.

```
1605 \DeclareTextSymbolDefault{\textcapitalcompwordmark}{TS1}
1606 \DeclareTextSymbolDefault{\textascendercompwordmark}{TS1}
1607 \DeclareTextSymbolDefault{\textquotestraightbase}{TS1}
1608 \DeclareTextSymbolDefault{\textquotestraightdblbase}{TS1}
1609 \DeclareTextSymbolDefault{\texttwelveudash}{TS1}
1610 \DeclareTextSymbolDefault{\textthreequartersemdash}{TS1}
1611 \DeclareTextSymbolDefault{\textdollar}{TS1}
1612 \DeclareTextSymbolDefault{\textquotesingle}{TS1}
1613 \DeclareTextSymbolDefault{\textasteriskcentered}{TS1}
1614 \DeclareTextSymbolDefault{\textfractionsolidus}{TS1}
1615 \DeclareTextSymbolDefault{\textminus}{TS1}
1616 \DeclareTextSymbolDefault{\textlbrackdbl}{TS1}
1617 \DeclareTextSymbolDefault{\textrbrackdbl}{TS1}
1618 \DeclareTextSymbolDefault{\textasciigrave}{TS1}
1619 \DeclareTextSymbolDefault{\texttildelow}{TS1}
1620 \DeclareTextSymbolDefault{\textasciibreve}{TS1}
1621 \DeclareTextSymbolDefault{\textasciicaron}{TS1}
1622 \DeclareTextSymbolDefault{\textgravedbl}{TS1}
1623 \DeclareTextSymbolDefault{\textacutedbl}{TS1}
1624 \DeclareTextSymbolDefault{\textdagger}{TS1}
1625 \DeclareTextSymbolDefault{\textdaggerdbl}{TS1}
1626 \DeclareTextSymbolDefault{\textbardbl}{TS1}
1627 \DeclareTextSymbolDefault{\textperthousand}{TS1}
1628 \DeclareTextSymbolDefault{\textbullet}{TS1}
1629 \DeclareTextSymbolDefault{\textcelsius}{TS1}
1630 \DeclareTextSymbolDefault{\textflorin}{TS1}
```

```

1631 \DeclareTextSymbolDefault{\texttrademark}{TS1}
1632 \DeclareTextSymbolDefault{\textcent}{TS1}
1633 \DeclareTextSymbolDefault{\textsterling}{TS1}
1634 \DeclareTextSymbolDefault{\textyen}{TS1}
1635 \DeclareTextSymbolDefault{\textbrokenbar}{TS1}
1636 \DeclareTextSymbolDefault{\textsection}{TS1}
1637 \DeclareTextSymbolDefault{\textasciidieresis}{TS1}
1638 \DeclareTextSymbolDefault{\textcopyright}{TS1}
1639 \DeclareTextSymbolDefault{\textordfeminine}{TS1}
1640 \DeclareTextSymbolDefault{\textlnot}{TS1}
1641 \DeclareTextSymbolDefault{\textregistered}{TS1}
1642 \DeclareTextSymbolDefault{\textasciimacron}{TS1}
1643 \DeclareTextSymbolDefault{\textdegree}{TS1}
1644 \DeclareTextSymbolDefault{\textpm}{TS1}
1645 \DeclareTextSymbolDefault{\texttwosuperior}{TS1}
1646 \DeclareTextSymbolDefault{\textthreesuperior}{TS1}
1647 \DeclareTextSymbolDefault{\textasciacute}{TS1}
1648 \DeclareTextSymbolDefault{\textmu}{TS1}
1649 \DeclareTextSymbolDefault{\textparagraph}{TS1}
1650 \DeclareTextSymbolDefault{\textperiodcentered}{TS1}
1651 \DeclareTextSymbolDefault{\textonesuperior}{TS1}
1652 \DeclareTextSymbolDefault{\textordmasculine}{TS1}
1653 \DeclareTextSymbolDefault{\textonequarter}{TS1}
1654 \DeclareTextSymbolDefault{\textonehalf}{TS1}
1655 \DeclareTextSymbolDefault{\textthreequarters}{TS1}
1656 \DeclareTextSymbolDefault{\texttimes}{TS1}
1657 \DeclareTextSymbolDefault{\textdiv}{TS1}

```

The `\texteuro` is only available for subsets with id 4 or less. Otherwise we fake the glyph using `\tc@fake@euro`

```

1658 \DeclareTextCommandDefault{\texteuro}
1659 {\CheckEncodingSubset\UseTextSymbol{TS1}\tc@fake@euro5\texteuro}

```

The `\textohm` is only available for subsets with id 3 or less. Otherwise we produce an error.

```

1660 \DeclareTextCommandDefault{\textohm}{\tc@check@symbol4\textohm}

```

The `\textestimated` and `\textcurrency` are only provided for fonts with subset encoding with id 2 or less.

```

1661 \DeclareTextCommandDefault{\textestimated}%
1662 {\tc@check@symbol3\textestimated}
1663 \DeclareTextCommandDefault{\textcurrency}%
1664 {\tc@check@symbol3\textcurrency}

```

Nearly all of the remaining glyphs are provided only with fonts with id 1 or 0, i.e., are essentially complete.

```

1665 \DeclareTextCommandDefault{\capitaltie}%
1666 {\tc@check@accent2\capitaltie}
1667 \DeclareTextCommandDefault{\newtie}%
1668 {\tc@check@accent2\newtie}
1669 \DeclareTextCommandDefault{\capitalnewtie}%
1670 {\tc@check@accent2\capitalnewtie}
1671 \DeclareTextCommandDefault{\textleftarrow}%
1672 {\tc@check@symbol2\textleftarrow}
1673 \DeclareTextCommandDefault{\textrightarrow}%

```

```

1674 {\tc@check@symbol2\textrightarrow}%
1675 \DeclareTextCommandDefault{\textblank}%
1676 {\tc@check@symbol2\textblank}%
1677 \DeclareTextCommandDefault{\textdblhyphen}%
1678 {\tc@check@symbol2\textdblhyphen}%
1679 \DeclareTextCommandDefault{\textzerooldstyle}%
1680 {\tc@check@symbol2\textzerooldstyle}%
1681 \DeclareTextCommandDefault{\textoneoldstyle}%
1682 {\tc@check@symbol2\textoneoldstyle}%
1683 \DeclareTextCommandDefault{\texttwooldstyle}%
1684 {\tc@check@symbol2\texttwooldstyle}%
1685 \DeclareTextCommandDefault{\textthreeoldstyle}%
1686 {\tc@check@symbol2\textthreeoldstyle}%
1687 \DeclareTextCommandDefault{\textfouroldstyle}%
1688 {\tc@check@symbol2\textfouroldstyle}%
1689 \DeclareTextCommandDefault{\textfiveoldstyle}%
1690 {\tc@check@symbol2\textfiveoldstyle}%
1691 \DeclareTextCommandDefault{\textsixoldstyle}%
1692 {\tc@check@symbol2\textsixoldstyle}%
1693 \DeclareTextCommandDefault{\textsevenoldstyle}%
1694 {\tc@check@symbol2\textsevenoldstyle}%
1695 \DeclareTextCommandDefault{\texteightoldstyle}%
1696 {\tc@check@symbol2\texteightoldstyle}%
1697 \DeclareTextCommandDefault{\textnineoldstyle}%
1698 {\tc@check@symbol2\textnineoldstyle}%
1699 \DeclareTextCommandDefault{\textlangle}%
1700 {\tc@check@symbol2\textlangle}%
1701 \DeclareTextCommandDefault{\textrangle}%
1702 {\tc@check@symbol2\textrangle}%
1703 \DeclareTextCommandDefault{\textmho}%
1704 {\tc@check@symbol2\textmho}%
1705 \DeclareTextCommandDefault{\textbigcircle}%
1706 {\tc@check@symbol2\textbigcircle}%
1707 \DeclareTextCommandDefault{\textuparrow}%
1708 {\tc@check@symbol2\textuparrow}%
1709 \DeclareTextCommandDefault{\textdownarrow}%
1710 {\tc@check@symbol2\textdownarrow}%
1711 \DeclareTextCommandDefault{\textborn}%
1712 {\tc@check@symbol2\textborn}%
1713 \DeclareTextCommandDefault{\textdivorced}%
1714 {\tc@check@symbol2\textdivorced}%
1715 \DeclareTextCommandDefault{\textdied}%
1716 {\tc@check@symbol2\textdied}%
1717 \DeclareTextCommandDefault{\textleaf}%
1718 {\tc@check@symbol2\textleaf}%
1719 \DeclareTextCommandDefault{\textmarried}%
1720 {\tc@check@symbol2\textmarried}%
1721 \DeclareTextCommandDefault{\textmusicalnote}%
1722 {\tc@check@symbol2\textmusicalnote}%
1723 \DeclareTextCommandDefault{\textdblhyphenchar}%
1724 {\tc@check@symbol2\textdblhyphenchar}%
1725 \DeclareTextCommandDefault{\textdollaroldstyle}%
1726 {\tc@check@symbol2\textdollaroldstyle}%
1727 \DeclareTextCommandDefault{\textcentoldstyle}%

```



```

1728 {\tc@check@symbol2\textcentoldstyle}
1729 \DeclareTextCommandDefault{\textcolonmonetary}%
1730 {\tc@check@symbol2\textcolonmonetary}
1731 \DeclareTextCommandDefault{\textwon}%
1732 {\tc@check@symbol2\textwon}
1733 \DeclareTextCommandDefault{\textnaira}%
1734 {\tc@check@symbol2\textnaira}
1735 \DeclareTextCommandDefault{\textguarani}%
1736 {\tc@check@symbol2\textguarani}
1737 \DeclareTextCommandDefault{\textpeso}%
1738 {\tc@check@symbol2\textpeso}
1739 \DeclareTextCommandDefault{\textlira}%
1740 {\tc@check@symbol2\textlira}
1741 \DeclareTextCommandDefault{\textrecipe}%
1742 {\tc@check@symbol2\textrecipe}
1743 \DeclareTextCommandDefault{\textinterrobang}%
1744 {\tc@check@symbol2\textinterrobang}
1745 \DeclareTextCommandDefault{\textinterrobangdown}%
1746 {\tc@check@symbol2\textinterrobangdown}
1747 \DeclareTextCommandDefault{\textdong}%
1748 {\tc@check@symbol2\textdong}
1749 \DeclareTextCommandDefault{\textpertenthousand}%
1750 {\tc@check@symbol2\textpertenthousand}
1751 \DeclareTextCommandDefault{\textpilcrow}%
1752 {\tc@check@symbol2\textpilcrow}
1753 \DeclareTextCommandDefault{\textbaht}%
1754 {\tc@check@symbol2\textbaht}
1755 \DeclareTextCommandDefault{\textnumero}%
1756 {\tc@check@symbol2\textnumero}
1757 \DeclareTextCommandDefault{\textdiscount}%
1758 {\tc@check@symbol2\textdiscount}
1759 \DeclareTextCommandDefault{\textopenbullet}%
1760 {\tc@check@symbol2\textopenbullet}
1761 \DeclareTextCommandDefault{\textservicemark}%
1762 {\tc@check@symbol2\textservicemark}
1763 \DeclareTextCommandDefault{\textlquill}%
1764 {\tc@check@symbol2\textlquill}
1765 \DeclareTextCommandDefault{\textrquill}%
1766 {\tc@check@symbol2\textrquill}
1767 \DeclareTextCommandDefault{\textcopyleft}%
1768 {\tc@check@symbol2\textcopyleft}
1769 \DeclareTextCommandDefault{\textcircledP}%
1770 {\tc@check@symbol2\textcircledP}
1771 \DeclareTextCommandDefault{\textreferencemark}%
1772 {\tc@check@symbol2\textreferencemark}
1773 \DeclareTextCommandDefault{\textsurd}%
1774 {\tc@check@symbol2\textsurd}

```

The `\textcircled` and `\t` are handled specially, unless the current font has a subset id of 0 (i.e. full TS1) we pick the symbols up from the the math font encodings, i.e., the third argument to `\CheckEncodingSubset` uses `\UseTextAccent` to get them from there.

```

1775 \DeclareTextCommandDefault{\textcircled}
1776 {\CheckEncodingSubset\UseTextAccent{TS1}%

```

```

1777     {\UseTextAccent{OMS}}1\textcircled{
1778 \DeclareTextCommandDefault{\t}
1779 {\CheckEncodingSubset\UseTextAccent{TS1}%
1780  {\UseTextAccent{OML}}1\t}

```

Finally input the encoding-specific definitions for TS1 thus making the top-level definitions optimised for this encoding (and not for the default encoding, see section 20.2).

```

1781 \input{ts1enc.def}

```

Now having the new glyphs available we also want to make sure that they are used. For most cases this will automatically happen but for some glyphs there are inferior definitions already known to L<sup>A</sup>T<sub>E</sub>X which will prevent the usage of the TS1 versions (see section 20.1 above). So we better get rid of them:

```

1782 \UndeclareTextCommand{\textsterling}{OT1}
1783 \UndeclareTextCommand{\textdollar}  {OT1}

```

Similar declarations should probably be made for other encodings like OT4 if they are in use.

```

1784 %\UndeclareTextCommand{\textsterling}{OT4}
1785 %\UndeclareTextCommand{\textdollar}  {OT4}

```

From the T1 encoding there are two candidates for removal: %<sub>o</sub> and %<sub>oo</sub> since these are both constructed from % followed by a tiny ‘o’ rather than being a single glyph. The problem with this approach is that in PostScript fonts this small zero is usually not available resulting in %■ rather than %<sub>o</sub> while the real glyph (at least for \textperthousand) is available in the PostScript version of TS1. So for the moment we compromise by removing the T1 declaration for \textperthousand but keeping the one for \textpertenthousand. This will have the effect that with Computer Modern fonts everything will come out (although %<sub>o</sub> and %<sub>oo</sub> are not taken from the same physical font) and with PostScript fonts %<sub>o</sub> will come out correctly while %<sub>oo</sub> will most likely look like %■ — which is probably an improvement over just getting a single ‘■’ to indicate a completely missing glyph, which would happen if we also ‘undeclared’ \textpertenthousand.

```

1786 \UndeclareTextCommand{\textperthousand}{T1}
1787 %\UndeclareTextCommand{\textpertenthousand}{T1}

```

### 21.2.1 Supporting oldstyle digits

```

1788 \DeclareRobustCommand\oldstylenums[1]{%
1789 \begingroup
1790 \ifmmode
1791   \mathgroup\symletters #1%
1792 \else
1793   \CheckEncodingSubset\@use@text@encoding{TS1}%
1794   {\PackageWarning{textcomp}%
1795     {Oldstyle digits unavailable for
1796      family \f@family.\MessageBreak
1797      Lining digits used instead}}%
1798   \tw@{#1}%
1799 \fi
1800 \endgroup
1801 }

```

### 21.2.2 Subset encoding defaults

For many font families commonly used in the T<sub>E</sub>X world we provide the subset encoding data here. Users can add additional font families in the file `textcomp.cfg` if they own other fonts.

However, if the option “forced” was given then all subset encoding specifications are ignored, so there is no point in setting any of them up:

```
1802 \iftc@forced \else
```

Computer modern based fonts (e.g., CM, CM-Bright, Concrete):

```
1803 \DeclareEncodingSubset{TS1}{cmr}      {0}
1804 \DeclareEncodingSubset{TS1}{cmss}     {0}
1805 \DeclareEncodingSubset{TS1}{cmtt}     {0}
1806 \DeclareEncodingSubset{TS1}{cmvtt}    {0}
1807 \DeclareEncodingSubset{TS1}{cmbr}     {0}
1808 \DeclareEncodingSubset{TS1}{cmtl}     {0}
1809 \DeclareEncodingSubset{TS1}{ccr}      {0}
```

PSNFSS fonts:

```
1810 \DeclareEncodingSubset{TS1}{ptm}      {4}
1811 \DeclareEncodingSubset{TS1}{pcr}      {4}
1812 \DeclareEncodingSubset{TS1}{phv}      {4}
1813 \DeclareEncodingSubset{TS1}{ppl}      {3}
1814 \DeclareEncodingSubset{TS1}{pag}      {4}
1815 \DeclareEncodingSubset{TS1}{pbk}      {4}
1816 \DeclareEncodingSubset{TS1}{pnc}      {4}
1817 \DeclareEncodingSubset{TS1}{pzc}      {4}
1818 \DeclareEncodingSubset{TS1}{bch}      {4}
1819 \DeclareEncodingSubset{TS1}{put}      {5}
```

Other CTAN fonts (probably not complete):

```
1820 \DeclareEncodingSubset{TS1}{uag}      {5}
1821 \DeclareEncodingSubset{TS1}{ugq}      {5}
1822 \DeclareEncodingSubset{TS1}{ul8}      {4}
1823 \DeclareEncodingSubset{TS1}{ul9}      {4} % (LuxiSans, one day)
1824 \DeclareEncodingSubset{TS1}{augie}    {5}
1825 \DeclareEncodingSubset{TS1}{dayrom}   {3}
1826 \DeclareEncodingSubset{TS1}{dayroms} {3}
1827 \DeclareEncodingSubset{TS1}{pxr}      {0}
1828 \DeclareEncodingSubset{TS1}{pxss}     {0}
1829 \DeclareEncodingSubset{TS1}{pxtt}     {0}
1830 \DeclareEncodingSubset{TS1}{txr}      {0}
1831 \DeclareEncodingSubset{TS1}{txss}     {0}
1832 \DeclareEncodingSubset{TS1}{txtt}     {0}
```

Latin Modern and TeX Gyre:

```
1833 \DeclareEncodingSubset{TS1}{lmr}      {0}
1834 \DeclareEncodingSubset{TS1}{lmdh}     {0}
1835 \DeclareEncodingSubset{TS1}{lmss}     {0}
1836 \DeclareEncodingSubset{TS1}{lmssq}    {0}
1837 \DeclareEncodingSubset{TS1}{lmvtt}    {0}
1838 \DeclareEncodingSubset{TS1}{lmtt}     {0}

1839 \DeclareEncodingSubset{TS1}{qhv}      {0}
1840 \DeclareEncodingSubset{TS1}{qag}      {0}
1841 \DeclareEncodingSubset{TS1}{qbk}      {0}
```

```

1842 \DeclareEncodingSubset{TS1}{qcr}    {0}
1843 \DeclareEncodingSubset{TS1}{qcs}    {0}
1844 \DeclareEncodingSubset{TS1}{qpl}    {0}
1845 \DeclareEncodingSubset{TS1}{qtm}    {0}
1846 \DeclareEncodingSubset{TS1}{qzc}    {0}
1847 \DeclareEncodingSubset{TS1}{qhvc}    {0}

```

Fourier-GUTenberg:

```

1848 \DeclareEncodingSubset{TS1}{futs}    {4}
1849 \DeclareEncodingSubset{TS1}{futex}   {4}
1850 \DeclareEncodingSubset{TS1}{futj}     {4}

```

Y&Y's Lucida Bright

```

1851 \DeclareEncodingSubset{TS1}{hlh}     {3}
1852 \DeclareEncodingSubset{TS1}{hls}     {3}
1853 \DeclareEncodingSubset{TS1}{hlst}    {3}

```

The remaining settings for Lucida are conservative: the following fonts contain the `\textohm` character but not the `\texteuro`, i.e., belong to neither subset 4 nor subset 3. If you want to use the `\textohm` with these fonts copy these definition to `textcomp.cfg` and change the subset to 3. However in that case make sure that you do not use the `\texteuro`.

```

1854 \DeclareEncodingSubset{TS1}{hlct}    {5}
1855 \DeclareEncodingSubset{TS1}{hlx}     {5}
1856 \DeclareEncodingSubset{TS1}{hlce}    {5}
1857 \DeclareEncodingSubset{TS1}{hlcn}    {5}
1858 \DeclareEncodingSubset{TS1}{hlcw}    {5}
1859 \DeclareEncodingSubset{TS1}{hlcf}    {5}

```

Other commercial families...

```

1860 \DeclareEncodingSubset{TS1}{pplx}    {3}
1861 \DeclareEncodingSubset{TS1}{pplj}    {3}
1862 \DeclareEncodingSubset{TS1}{ptmx}    {4}
1863 \DeclareEncodingSubset{TS1}{ptmj}    {4}

```

If the file `textcomp.cfg` exists it will be loaded at this point. This allows to define further subset encodings for font families not covered by default.

```

1864 \InputIfFileExists{textcomp.cfg}
1865 {\PackageInfo{textcomp}{Local configuration file used}}{}

1866 \fi
1867 \</TS1sty>

```

# File m

## ltcounts.dtx

### 22 Counters and Lengths

Commands for defining and using counters. This file defines:

<code>\newcounter</code>	To define a new counter.
<code>\setcounter</code>	To set the value of counters.
<code>\addtocounter</code>	Increase the counter #1 by the number #2.
<code>\stepcounter</code>	Increase a counter by one.
<code>\refstepcounter</code>	Increase a counter by one, also setting the value used by <code>\label</code> .
<code>\value</code>	For accessing the value of the counter as a T <sub>E</sub> X number (as opposed to <code>\the&lt;counter&gt;</code> which expands to the <i>printed</i> representation of <code>&lt;counter&gt;</code> )
<code>\arabic</code>	<code>\arabic{&lt;counter&gt;}</code> : 1, 2, 3, ...
<code>\roman</code>	<code>\roman{&lt;counter&gt;}</code> : i, ii, iii, ...
<code>\Roman</code>	<code>\Roman{&lt;counter&gt;}</code> : I, II, III, ...
<code>\alph</code>	<code>\alph{&lt;counter&gt;}</code> : a, b, c, ...
<code>\Alph</code>	<code>\Alph{&lt;counter&gt;}</code> : A, B, C, ...
<code>\fnsymbol</code>	<code>\fnsymbol{&lt;counter&gt;}</code> : *, †, ‡, ...
<code>\counterwithin</code>	<code>\counterwithin{&lt;counter&gt;}{&lt;within-counter&gt;}</code> : Resets <code>&lt;counter&gt;</code> whenever <code>&lt;within-counter&gt;</code> is stepped. Also redefines <code>\the&lt;counter&gt;</code> command to produce <code>\the&lt;within-counter&gt;.\arabic{&lt;counter&gt;}</code> . Star form omits redefining the print representation.
<code>\counterwithout</code>	<code>\counterwithout{&lt;counter&gt;}{&lt;within-counter&gt;}</code> : Removes <code>&lt;counter&gt;</code> from the reset list of <code>&lt;within-counter&gt;</code> . Also redefines <code>\the&lt;counter&gt;</code> command to produce <code>\arabic{&lt;counter&gt;}</code> . Star form omits redefining the print representation.

1 (\*2ekernel)

#### 22.1 Environment Counter Macros

An environment foo has an associated counter defined by the following control sequences:

<code>\c@foo</code>	Contains the counter's numerical value. It is defined by <code>\newcount\foocounter</code> .
<code>\thefoo</code>	Macro that expands to the printed value of <code>\foocounter</code> . For example, if sections are numbered within chapters, and section headings look like Section II-3. The Nature of Counters then <code>\thesection</code> might be defined by: <code>\def\thesection</code> <code>{\@Roman{\c@chapter}-\@arabic{\c@section}}</code>
<code>\p@foo</code>	Macro that expands to a printed 'reference prefix' of counter foo. Any <code>\ref</code> to a value created by counter foo will produce the expansion of <code>\p@foo\thefoo</code> when the <code>\label</code> command is executed. See file <code>ltxref.dtx</code> for an extension of this mechanism.
<code>\cl@foo</code>	List of counters to be reset when foo stepped. Has format <code>\@elt{countera}\@elt{counterb}\@elt{counterc}</code> .

### NOTE:

`\thefoo` and `\p@foo` *must* be defined in such a way that `\edef\bar{\thefoo}` or `\edef\bar{\p@foo}` defines `\bar` so that it will evaluate to the counter value at the time of the `\edef`, even after `\foocounter` and any other counters have been changed. This will happen if you use the standard commands `\@arabic`, `\@Roman`, etc.

The following commands are used to define and modify counters.

`\refstepcounter{<foo>}`

Same as `\stepcounter`, but it also defines `\@currentreference` so that a subsequent `\label{<bar>}` command causes `\ref{<bar>}` to generate the current value of counter `<foo>`.

`\@definecounter{<foo>}`

Initializes counter `{<foo>}` (with empty reset list), defines `\p@foo` and `\thefoo` to be null. Also adds `<foo>` to `\cl@ckpt` – the reset list of a dummy counter `@ckpt` used for taking checkpoints for the `\include` system.

`\@addtoreset{<foo>}{<bar>}` : Adds counter `<foo>` to the list of counters `\cl@bar` to be reset when counter `<bar>` is stepped.

`\@removefromreset{<foo>}{<bar>}` : Removes counter `<foo>` to the list of counters `\cl@bar` to be reset when counter `<bar>` is stepped.

`\setcounter` `\setcounter{<foo>}{<val>}` : Globally sets `\foocounter` equal to `<val>`.

```
2 \def\setcounter#1#2{%
3   \@ifundefined{c@#1}%
4     {\@nocounterr{#1}}%
5     {\global\csname c@#1\endcsname#2\relax}}
```

`\addtocounter` `\addtocounter{<foo>}{<val>}` Globally increments `\foocounter` by `<val>`.

```
6 \def\addtocounter#1#2{%
7   \@ifundefined{c@#1}%
8     {\@nocounterr{#1}}%
9     {\global\advance\csname c@#1\endcsname #2\relax}}
```

`\newcounter` `\newcounter{<newctr>}[<oldctr>]` Defines `<newctr>` to be a counter, which is reset when counter `<oldctr>` is stepped. If `<newctr>` already defined produces ‘`c@newctr` already defined’ error.

```
10 \def\newcounter#1{%
11   \expandafter\@ifdefinable \csname c@#1\endcsname
12     {\@definecounter{#1}}%
13   \@ifnextchar[{\@newctr{#1}}{-}]}
```

`\value` `\value{<ctr>}` produces the value of counter `<ctr>`, for use with a `\setcounter` or `\addtocounter` command.

```
14 \def\value#1{\csname c@#1\endcsname}
```

`\@newctr`

```
15 \def\@newctr#1[#2]{%
16   \@ifundefined{c@#2}{\@nocounterr{#2}}{\@addtoreset{#1}{#2}}}
```

`\stepcounter` `\stepcounterfoo` Globally increments counter `\c@F00` and resets all subsidiary counters.

```
17 \def\stepcounter#1{%
```

```

18 \addtocounter{#1}\@ne
19 \begingroup
20 \let\@elt\@stpelt
21 \csname cl@#1\endcsname
22 \endgroup}

```

**\@stpelt** Rather than resetting the “within” counter to zero we set it to  $-1$  and then run **\stepcounter** that moves it to 0 and also initiates resetting the next level down.

```

23 \</2ekernel>
24 \<latexrelease>\IncludeInRelease{2015/01/01}{\@stpelt}
25 \<latexrelease> {Reset nested counters}%
26 \<*2ekernel | latexrelease>
27 \def\@stpelt#1{\global\csname c@#1\endcsname \m@ne\stepcounter{#1}}%
28 \<latexrelease>\EndIncludeInRelease
29 \</2ekernel | latexrelease>
30 \<latexrelease>\IncludeInRelease{0000/00/00}{\@stpelt}
31 \<latexrelease> {Reset nested counters}%%
32 \<latexrelease>\def\@stpelt#1{\global\csname c@#1\endcsname \z@}%
33 \<latexrelease>\EndIncludeInRelease
34 \<*2ekernel>

```

**\cl@ckpt**

```

35 \def\cl@ckpt{\@elt{page}}

```

**\@definecounter**

```

36 \def\@definecounter#1{\expandafter\newcount\csname c@#1\endcsname
37 \setcounter{#1}\z@
38 \global\expandafter\let\csname cl@#1\endcsname\@empty
39 \@addtoreset{#1}{@ckpt}%
40 \global\expandafter\let\csname p@#1\endcsname\@empty
41 \expandafter
42 \gdef\csname the#1\expandafter\endcsname\expandafter
43 {\expandafter\@arabic\csname c@#1\endcsname}}

```

**\@addtoreset**

```

44 \def\@addtoreset#1#2{\expandafter\@cons\csname cl@#2\endcsname {{#1}}}
45 \</2ekernel>

```

**\@removefromreset**

```

46 \<latexrelease>\IncludeInRelease{2018-04-01}
47 \<latexrelease> {\@removefromreset}{Add interfaces}%
48 \<*2ekernel | latexrelease>
49 \def\@removefromreset#1#2{%

```

Even through this is internal and the programmer should know what he/she is doing we test here if counter #2 is defined. If not, the execution would run into a tight loop.

```

50 \ifundefined{c@#2}\relax
51 {\begingroup
52 \expandafter\let\csname c@#1\endcsname\@removefromreset
53 \def\@elt##1{%
54 \expandafter\ifx\csname c@##1\endcsname\@removefromreset

```

```

55     \else
56         \noexpand\@elt{##1}%
57     \fi}%
58     \expandafter\xdef\csname cl@#2\endcsname
59     {\csname cl@#2\endcsname}%
60     \endgroup}}

```

`\@ifbothcounters` Test if arg #1 and #2 are counters and if so execute #3.

```

61 \def\@ifbothcounters#1#2#3{%
62     \@ifundefined{c@#1}{\@nocounterr{#1}}%
63     {% else counter is defined
64         \@ifundefined{c@#2}{\@nocounterr{#2}}%
65         {% else both counter and within are defined
66             #3}}}

```

`\counterwithout`

```

67 \def\counterwithout {\@ifstar\counterwithout@s\counterwithout@x}
68 \def\counterwithout@s#1#2{%
69     \@ifbothcounters{#1}{#2}{\@removefromreset{#1}{#2}}}
70 \def\counterwithout@x#1#2{%
71     \@ifbothcounters{#1}{#2}%
72     {\@removefromreset{#1}{#2}%
73         \expandafter
74         \gdef\csname the#1\expandafter\endcsname\expandafter
75             {\expandafter
76                 \@arabic\csname c@#1\endcsname}}}

```

`\counterwithin`

```

77 \def\counterwithin{\@ifstar\counterwithin@s\counterwithin@x}
78 \def\counterwithin@s#1#2{%
79     \@ifbothcounters{#1}{#2}{\@addtoreset{#1}{#2}}}
80 \def\counterwithin@x#1#2{%
81     \@ifbothcounters{#1}{#2}%
82     {\@addtoreset{#1}{#2}%
83         \expandafter
84         \gdef\csname the#1\expandafter\endcsname\expandafter
85             {\csname the#2\expandafter\endcsname\expandafter
86                 .\expandafter
87                 \@arabic\csname c@#1\endcsname}}}

```

```

88 </2ekernel | latexrelease>
89 <latexrelease>\EndIncludeInRelease
90 <latexrelease>\IncludeInRelease{0000-00-00}
91 <latexrelease>         {\@removefromreset}{Add interfaces}%
92 <latexrelease>\let \@removefromreset \undefined
93 <latexrelease>\let \@ifbothcounters \undefined
94 <latexrelease>\let \counterwithout \undefined
95 <latexrelease>\let \counterwithout@s \undefined
96 <latexrelease>\let \counterwithout@x \undefined
97 <latexrelease>\let \counterwithin \undefined
98 <latexrelease>\let \counterwithin@s \undefined
99 <latexrelease>\let \counterwithin@x \undefined

```



```

100 (latexrelease)\EndIncludeInRelease
101 (*2ekernel)

    Numbering commands for definitions of \theCOUNTER and \list arguments.
    All commands can now be used in text and math mode.

\arabic Representation of counter as arabic numerals. Changed 29 Apr 86 to make it
print the obvious thing it COUNTER not positive.
102 \def\arabic#1{\expandafter\@arabic\csname c@#1\endcsname}

\roman Representation of counter as lower-case Roman numerals.
103 \def\roman#1{\expandafter\@roman\csname c@#1\endcsname}

\Roman Representation of counter as upper-case Roman numerals.
104 \def\Roman#1{\expandafter\@Roman\csname c@#1\endcsname}

\alph Representation of counter as a lower-case letter: 1 = a, 2 = b, etc.
105 \def\alph#1{\expandafter\@alph\csname c@#1\endcsname}

\Alph Representation of counter as an upper-case letter: 1 = A, 2 = B, etc.
106 \def\Alph#1{\expandafter\@Alph\csname c@#1\endcsname}

\fnsymbol Representation of COUNTER as a footnote symbol: 1 = *, 2 = †, etc.
107 \def\fnsymbol#1{\expandafter\@fnsymbol\csname c@#1\endcsname}

\@arabic \@arabic\F00counter Representation of \F00counter as arabic numerals.
108 \def\@arabic#1{\number #1} %% changed 29 Apr 86

\@roman \@roman\F00counter Representation of \F00counter as lower-case Roman nu-
merals.
109 \def\@roman#1{\romannumeral #1}

\@Roman \@Roman\F00counter Representation of \F00counter as upper-case Roman nu-
merals.
110 \def\@Roman#1{\expandafter\@slowromancap\romannumeral #1@}

\@slowromancap Fully expandable macro to change a roman number to uppercase.
111 \def\@slowromancap#1{\ifx @#1% then terminate
112     \else
113         \if i#1I\else\if v#1V\else\if x#1X\else\if l#1L\else\if
114             c#1C\else\if d#1D\else \if m#1M\else#1\fi\fi\fi\fi\fi\fi
115             \expandafter\@slowromancap
116             \fi
117 }

\@alph \@alph\F00counter Representation of \F00counter as a lower-case letter: 1 =
a, 2 = b, etc.
118 \def\@alph#1{%
119     \ifcase#1\or a\or b\or c\or d\or e\or f\or g\or h\or i\or j\or
120     k\or l\or m\or n\or o\or p\or q\or r\or s\or t\or u\or v\or w\or x\or
121     y\or z\else\@ctrerr\fi}

```

`\@Alph` `\@Alph\F00counter` Representation of `\F00counter` as an upper-case letter: 1 = A, 2 = B, etc.

```
122 \def\@Alph#1{%
123   \ifcase#1\or A\or B\or C\or D\or E\or F\or G\or H\or I\or J\or
124   K\or L\or M\or N\or O\or P\or Q\or R\or S\or T\or U\or V\or W\or X\or
125   Y\or Z\else\@ctrerr\fi}
```

`\@fnsymbol` Typesetting old fashioned footnote symbols. This can be done both in text or math mode now.

This macro is another example of an ever recurring problem in  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ : Determining if something is text-mode or math-mode. It is imperative for the decision between text and math to be delayed until the actual typesetting is done as the code in question may go through an `\edef` or `\write` where an `\ifmode` test would be executed prematurely. Hence in the implementation below, `\@fnsymbol` is not robust in itself but the parts doing the actual typesetting are.

In the case of `\@fnsymbol` we make use of the robust command `\TextOrMath` which takes two arguments and typesets the first if in text-mode and the second if in math-mode. Note that in order for this command to make the correct decision, it must insert a `\relax` token if run under regular  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ , which ruins any kerning between the preceding characters and whatever awaits typesetting. If you use  $\mathrm{eT}_{\mathrm{E}}\mathrm{X}$  as engine for  $\mathrm{L}^{\mathrm{A}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$  (as recommended) this unfortunate side effect is not present.

```
126 \</2ekernel>
127 \<latexrelease>\IncludeInRelease{2015/01/01}{\@fnsymbol}{Use \TextOrMath}%
128 \<*2ekernel | latexrelease>
129 \def\@fnsymbol#1{%
130   \ifcase#1\or \TextOrMath\textasteriskcentered *\or
131   \TextOrMath \textdagger \dagger\or
132   \TextOrMath \textdaggerdbl \ddagger \or
133   \TextOrMath \textsection \mathsection\or
134   \TextOrMath \textparagraph \mathparagraph\or
135   \TextOrMath \textbardbl ||\or
136   \TextOrMath {\textasteriskcentered\textasteriskcentered}{**}\or
137   \TextOrMath {\textdagger\textdagger}{\dagger\dagger}\or
138   \TextOrMath {\textdaggerdbl\textdaggerdbl}{\ddagger\ddagger}\else
139   \@ctrerr \fi
140 }%
141 \</2ekernel | latexrelease>
142 \<latexrelease>\EndIncludeInRelease
143 \<latexrelease>\IncludeInRelease{0000/00/00}{\@fnsymbol}{Use \TextOrMath}%
144 \<latexrelease>\def\@fnsymbol#1{\ensuremath{%
145 \<latexrelease>   \ifcase#1\or *\or \dagger\or \ddagger\or \mathsection\or
146 \<latexrelease>   \mathparagraph\or ||\or **\or \dagger\dagger
147 \<latexrelease>   \or \ddagger\ddagger \else\@ctrerr\fi}}%
148 \<latexrelease>\EndIncludeInRelease
149 \<*2ekernel>
```

`\TextOrMath` When using regular  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ , we make this command robust so that it always selects the correct branch in an `\ifmode` switch with the usual disadvantage of ruining kerning. For the application we use it for here that shouldn't matter. The alternative would be to mimic `\IeC` from `inputenc` but then it will have the disadvantage of choosing the wrong branch if appearing at the beginning of an alignment cell.

However, users of eTeX will be pleasantly surprised to get the best of both worlds and no bad side effects.

First some code for checking if we are running eTeX but making sure not to permanently turn `\protected` into `\relax`.

```
150 </2ekernel>
151 <latexrelease>\IncludeInRelease{2015/01/01}{\TextOrMath}{\TextOrMath}%
152 <*2ekernel | latexrelease>
153 \begingroup\expandafter\expandafter\expandafter\endgroup
154 \expandafter\ifx\csname protected\endcsname\relax
```

In case of ordinary TeX we define `\TextOrMath` as a robust command but make sure it always grabs its arguments. If we didn't do this it might very well gobble spaces in the input stream.

```
155 \DeclareRobustCommand\TextOrMath{%
156   \ifmmode \expandafter\@secondoftwo
157   \else \expandafter\@firstoftwo \fi}
158 \protected@edef\TextOrMath#1#2{\TextOrMath{#1}{#2}}
159 \else
```

For eTeX the situation is similar. The robust macro is a hidden one so that we again avoid problems of gobbling spaces in the input.

```
160 \protected\expandafter\def\csname TextOrMath\space\endcsname{%
161   \ifmmode \expandafter\@secondoftwo
162   \else \expandafter\@firstoftwo \fi}
163 \edef\TextOrMath#1#2{%
164   \expandafter\noexpand\csname TextOrMath\space\endcsname
165   {#1}{#2}}
166 \fi
167 </2ekernel | latexrelease>
168 <latexrelease>\EndIncludeInRelease
169 <latexrelease>\IncludeInRelease{0000/00/00}{\TextOrMath}{\TextOrMath}%
170 <latexrelease>\let\TextOrMath\@undefined
171 <latexrelease>\EndIncludeInRelease
172 <*2ekernel>

173 </2ekernel>
```

# File n ltnlength.dtx

## 23 Lengths

```

\newlength Declare #1 to be a new length command.
\setlength Set the length command, #1, to the value #2.
\addtolength Increase the value of the length command, #1, by the value #2.
\settowidth Set the length, #1 to the width of a box containing #2.
\settoheight Set the length, #1 to the height of a box containing #2.
\settodepth Set the length, #1 to the depth of a box containing #2.

1 (*2ekernel)
2 \message{lengths,}

\newlength
3 \def\newlength#1{\@ifdefinable#1{\newskip#1}}

\setlength
4 (/2ekernel)
5 \langle latexrelease \rangle \IncludeInRelease{2015/01/01}%
6 \langle latexrelease \rangle { \setlength } { Using \setlength with \dimen0 } %
7 (*2ekernel | latexrelease)

8 \def\setlength#1#2{#1 #2\relax}
9 (/2ekernel | latexrelease)
10 \langle latexrelease \rangle \EndIncludeInRelease
11 \langle latexrelease \rangle \IncludeInRelease{0000/00/00}%
12 \langle latexrelease \rangle { \setlength } { Using \setlength with \dimen0 } %
13 \langle latexrelease \rangle \def\setlength#1#2{#1#2\relax}
14 \langle latexrelease \rangle \EndIncludeInRelease
15 (*2ekernel)

\addtolength \relax added 24 Mar 86
16 \def\addtolength#1#2{\advance#1 #2\relax}

\settoheight The obvious analogs of \settowidth.
\settodepth 17 \def\@settodim#1#2#3{\setbox\@tempboxa\hbox{#{#3}}#2#1\@tempboxa}
\settowidth Clear the memory afterwards (which might be a lot).
\@settodim 18 \setbox\@tempboxa\box\voidb@x}
19 \DeclareRobustCommand\settoheight{\@settodim\ht}
20 \DeclareRobustCommand\settodepth {\@settodim\dp}
21 \DeclareRobustCommand\settowidth {\@settodim\wd}

\@settopoint This macro takes the contents of the skip register that is supplied as its argument
and removes the fractional part to make it a whole number of points. This can be
used in class files to avoid values like 345.4666666pt when calculating a dimension.

22 \def\@settopoint#1{\divide#1\p@\multiply#1\p@}
23 (/2ekernel)

```

# File o

## lftssbas.dtx

This file contains the main implementation of the ‘low level’ font selection commands. See other parts of the L<sup>A</sup>T<sub>E</sub>X distribution, or *The L<sup>A</sup>T<sub>E</sub>X Companion* for higher level documentation of the L<sup>A</sup>T<sub>E</sub>X ‘New’ Font Selection Scheme.

**Warning:** The macro documentation is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

## 24 Preliminary macros

We define a number of macros that will be used later.

`\@nomath` `\@nomath` is used by most macros that will have no effect in math mode. It issues a warning message.

```
1 (*2kernel)
2 \def\@nomath#1{\relax\ifmmode
3   \@font@warning{Command \noexpand#1invalid in math mode}\fi}
```

`\no@alphabet@error` The macro `\no@alphabet@error` is called whenever the user requests a math *alphabet* that is not available in the current *version*. In math mode an error message is produced otherwise the command keeps silent. The argument is the name of the control sequence that identifies the math *alphabet*. The `\relax` at the beginning is necessary to prevent T<sub>E</sub>X from scanning too far in certain situations.

```
4 \gdef\no@alphabet@error#1{\relax \ifmmode
5   \@latex@error{Math\space alphabet\space identifier\space
6     \noexpand#1is\space undefined\space in\space math\space
7     version\space ‘\math@version’}%
8   {Your\space requested\space math\space alphabet\space
9     is\space undefined\space in\space the\space current\space
10    math\space version.^^JCheck\space the\space spelling\space
11    or\space use\space the\space \noexpand\SetMathAlphabet\space
12    command.}
13   \fi}
```

`\new@mathgroup` We also give a new name to `\newfam` and `\fam` to avoid verbal confusion (see the introduction).<sup>2</sup>

`\mathgroup`

```
14 %\def\new@mathgroup{\alloc@8\mathgroup\chardef\sixt@@n}
15 \let\mathgroup\fam
16 %\let\newfam\new@mathgroup
17 \@onlypreamble\new@mathgroup
```

<sup>2</sup>For the same reason it seems advisable to `\let\fam` and `\newfam` equal to `\relax`, but this is commented out to retain compatibility to existing style files.

## 25 Macros for setting up the tables

`\DeclareFontShape` The macro `\DeclareFontShape` takes 6 arguments:

```
18 \def\DeclareFontShape{\begingroup
```

First we restore the catcodes of all characters used in the syntax.

```
19 \nfss@catcodes
```

We use `\expandafter \endgroup` to restore catcode in case something goes wrong with the argument parsing (suggested by Tim Van Zandt)

`\DeclareFontShape`

```
20 \expandafter\endgroup
21 \DeclareFontShape@}
22 \def\DeclareFontShape@#1#2#3#4#5#6{%
23 \expandafter\ifx\csname #1+#2\endcsname\relax
24 \@latex@error{Font family ‘#1+#2’ unknown}\@eha
25 \else
26 \expandafter
27 \xdef\csname#1/#2/#3/#4\endcsname{\expandafter\noexpand
28 \csname #5\endcsname}%
29 \def\reserved@a{#6}%
30 \global
31 \expandafter\let\csname#5\endcsname\expandafter\endcsname
32 \ifx\reserved@a@empty
33 \@empty
34 \else
35 \reserved@a
36 \fi
37 \fi
38 }
```

`\DeclareFixedFont` Define a direct font switch that avoids all overhead.

```
39 \def\DeclareFixedFont#1#2#3#4#5#6{%
40 \begingroup
41 \math@fontsfalse
42 \every@math@size{}%
43 \fontsize{#6}\z@
44 \usefont{#2}{#3}{#4}{#5}%
45 \global\expandafter\let\expandafter#1\the\font
46 \endgroup
47 }
```

`\do@subst@correction`

```
48 \def\do@subst@correction{%
49 \xdef\subst@correction{%
50 \font@name
51 \global\expandafter\font
52 \csname \curr@fontshape/\f@size\endcsname
53 \noexpand\fontname\font
54 \relax}%
```

Calling `\subst@correction` after the current group means calling it after we have loaded the substitution font which is done inside a group.

```
55 \aftergroup\subst@correction
56 }
```

`\DeclareFontFamily`

```
57 \def\DeclareFontFamily#1#2#3{%
```

If we want fast checking for the encoding scheme we can just check for `\T@. .` being defined.

```
58 % \@tempswafalse
59 % \def\reserved@b{#1}%
60 % \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
61 %     \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
62 % \cdp@list
63 % \if@tempswa
64 % \ifundefined{T@#1}%
65 %     {%
66 %         \@latex@error{Encoding scheme ‘#1’ unknown}\@eha
67 %     }%
68 % }
```

Now we have to define the macro `\<#1>+<#2>` to contain `#3`. But since most of the time `#3` will be empty we use `\let` in a tricky way rather than a simple `\def` since this will save internal memory. We store the argument `#3` in a temporary macro `\reserved@a`.

```
69     \def\reserved@a{#3}%
```

We compare `\reserved@a` with `\@empty`. If these two are the same we `\let` the ‘extra’ macro equal to `\@empty` which is not the same as doing a `\let` to `\reserved@a` — the latter would blow one extra memory location rather than reusing the one from `\@empty`.

```
70     \global
71     \expandafter\let\csname #1+#2\expandafter\endcsname
72         \ifx \reserved@a\@empty
73             \@empty
74         \else \reserved@a
75         \fi
76     }%
77 }
```

`\cdp@list` We initialize the code page list to be empty.

```
78 \let\cdp@list\@empty
79 \@onlypreamble\cdp@list
```

`\cdp@elt`

```
80 \let\cdp@elt\relax
81 \@onlypreamble\cdp@elt
```

`\DeclareFontEncoding`

```
82 \def\DeclareFontEncoding{%
```

First we start with ignoring all blanks and newlines since every surplus space in the second or third argument will come out in a weird place in the document.

```
83     \begingroup
84     \nfss@catcodes
85     \expandafter\endgroup
86     \DeclareFontEncoding@}
87 \@onlypreamble\DeclareFontEncoding
```

```

88 \def\DeclareFontEncoding#1#2#3{%
89   \expandafter
90   \ifx\csname T@#1\endcsname\relax
91     \def\cdp@elt{\noexpand\cdp@elt}%
92     \xdef\cdp@list{\cdp@list\cdp@elt{#1}%
93                   {\default@family}{\default@series}%
94                   {\default@shape}}%

```

To support encoding dependent commands (like accents) we initialise the command `\<encoding>-cmd` to be `\@changed@cmd`. (See `ltoutenc.dtx` for details.)

```

95   \expandafter\let\csname#1-cmd\endcsname\@changed@cmd
96   \else
97     \font@info{Redeclaring font encoding #1}%
98   \fi
99   \global\@namedef{T@#1}{#2}%
100  \global\@namedef{M@#1}{\default@M#3}%

```

Keep a record of the last encoding being declared:

```

101  \xdef\LastDeclaredEncoding{#1}%
102  }
103 \@onlypreamble\DeclareFontEncoding@

```

`\LastDeclaredEncoding` The last encoding being declared by `\DeclareFontEncoding`.

```

104 \def\LastDeclaredEncoding{}

```

`\DeclareFontSubstitution`

```

105 \def\DeclareFontSubstitution#1#2#3#4{%
106   \expandafter
107   \ifx\csname T@#1\endcsname\relax
108     \@latex@error{Encoding scheme ‘#1’ unknown}\@eha
109   \else
110     \begingroup

```

We loop through the `\cdp@list` and rebuild it anew in `\toks@` thereby replacing the defaults for the encoding in question with the new defaults. It is important to store the encoding to test against expanded in `\reserved@a` since it might just be `\LastDeclaredEncoding` that is passed as `#1`.

```

111     \edef\reserved@a{#1}%
112     \toks@{}%
113     \def\cdp@elt##1##2##3##4{%
114       \def\reserved@b{##1}%
115       \ifx\reserved@a\reserved@b

```

Here we use the new defaults but we use `##1` (i.e., the encoding name already stored previously) since we know that it is expanded.

```

116       \addto@hook\toks@{\cdp@elt{##1}{##2}{##3}{##4}}%
117     \else

```

If `\reserved@a` and `\reserved@b` differ then we simply copy from the old list to the new.

```

118       \addto@hook\toks@{\cdp@elt{##1}{##2}{##3}{##4}}%
119     \fi}%
120     \cdp@list

```



```

121     \xdef\cdp@list{\the\toks@}%
122   \endgroup
123   \global
124   \@namedef{D@#1}{%
125     \def\default@family{#2}%
126     \def\default@series{#3}%
127     \def\default@shape{#4}%
128   }%
129   \fi
130 }
131 \@onlypreamble\DeclareFontSubstitution

```

`\DeclareFontEncodingDefaults`

```

132 \def\DeclareFontEncodingDefaults#1#2{%
133   \ifx\relax#1\else
134     \ifx\default@T\@empty\else
135       \@font@info{Overwriting encoding scheme text defaults}%
136     \fi
137     \gdef\default@T{#1}%
138   \fi
139   \ifx\relax#2\else
140     \ifx\default@M\@empty\else
141       \@font@info{Overwriting encoding scheme math defaults}%
142     \fi
143     \gdef\default@M{#2}%
144   \fi
145 }
146 \@onlypreamble\DeclareFontEncodingDefaults

```

`\default@T`

`\default@M`

```

147 \let\default@T\@empty
148 \let\default@M\@empty

```

`\DeclarePreloadSizes`

```

149 \def\DeclarePreloadSizes#1#2#3#4#5{%
150   \@ifundefined{T@#1}%
151   {\@latex@error{Encoding scheme ‘#1’ unknown}\@eha}%
152   {%

```

Don't know at the moment what this group here does!

```

153   \begingroup

```

We define a macro `\reserved@f`<sup>3</sup> that grabs the next *size* and loads the corresponding font. This is done by delimiting `\reserved@f`'s only argument by the token `,` (comma).

```

154   \def\reserved@f##1,{%

```

The end of the list will be detected when there are no more elements, i.e. when `\reserved@f`'s argument is empty. The trick used here is explained in Appendix D of the *T<sub>E</sub>Xbook*: if the argument is empty the `\if` will select the first clause and `\let \reserved@f equal to \relax`. (We use the `>` character here since it cannot appear in font file names.)

```

155   \if>##1>%

```

---

<sup>3</sup>We cannot use `\@tempa` since it is needed in `\pickup@font`.

```

156         \let\reserved@f\relax
157     \else

```

Otherwise, we define `\font@name` appropriately and call `\pickup@font` to do the work. Note that the requested `\curr@fontshape` combination must have been defined, or you will get an error. The definition of `\font@name` is carried out globally to be consistent with the rest of the code in this file.

```

158         \xdef\font@name{\csname#1/#2/#3/#4/##1\endcsname}%
159         \pickup@font

```

Now we forget the name of the font just loaded. More precisely, we set the corresponding control sequence to `\relax`. This means that later on, when the font is first used, the macro `\define@newfont` is called again to execute the ‘extra’ macro for this font.

```

160         \global\expandafter\let\font@name\relax
161     \fi

```

Finally we call `\reserved@f` again to process the next *size*. If `\reserved@f` was `\let` equal to `\relax` this will end the macro.

```

162     \reserved@f}%

```

We finish with reinserting the list of sizes after the `\reserved@f` macro and appending an empty element so that the end of the list is recognized properly.

```

163     \reserved@f#5,,%
164     \endgroup
165 }%
166 }
167 \@onlypreamble\DeclarePreloadSizes

```

`\ifmath@fonts` We need a switch to decide if we have to switch math fonts. For this purpose we provide `\ifmath@fonts` that can be set to true or false by the `\S@...` macros depending on if math fonts are provided for this size or not. The default is of course to switch all fonts.

```

168 \newif\ifmath@fonts \math@fontstrue

```

`\DeclareMathSizes` `\DeclareMathSizes` takes the text size, math text size, math script size, and math scriptscript size as arguments and defines the right `\S@...` macro.

```

169 \def\DeclareMathSizes{%
170     \@ifstar{\@DeclareMathSizes\math@fontsfalse}%
171     {\@DeclareMathSizes{}}%
172 \@onlypreamble\DeclareMathSizes

```

`\@DeclareMathSizes` This modification by Michael J. Downes on `comp.text.tex` on 2002/10/17 allows the user to have settings such as `\DeclareMathSizes{9.5dd}{9.5dd}{7.4dd}{6.6dd}`.

```

173 \if2kernel
174 \iflatexrelease\IncludeInRelease{2015/01/01}{\@DeclareMathSizes}%
175 \iflatexrelease\Arbitrary units in \DeclareMathSizes}%
176 \if*2kernel\iflatexrelease
177 \def\@DeclareMathSizes #1#2#3#4#5{%
178     \@defaultunits\dimen@ #2pt\relax\@nnil
179     \if $#3$%
180         \expandafter\let\csname S@#3\strip@pt\dimen@\endcsname\math@fontsfalse
181     \else

```

```

182 \@defaultunits\dimen@ii #3pt\relax\@nnil
183 \@defaultunits\@tempdima #4pt\relax\@nnil
184 \@defaultunits\@tempdimb #5pt\relax\@nnil
185 \toks@{#1}%
186 \expandafter\edef\csname S@\strip@pt\dimen@\endcsname{%
187 \gdef\noexpand\tf@size{\strip@pt\dimen@ii}%
188 \gdef\noexpand\sfont@size{\strip@pt\@tempdima}%
189 \gdef\noexpand\ssfont@size{\strip@pt\@tempdimb}%
190 \the\toks@
191 }%
192 \fi
193 }%
194 \end{kernel}
195 \end{release}
196 \includeinrelease{0000/00/00}{\@DeclareMathSizes}%
197 \includeinrelease{Arbitrary units in \DeclareMathSizes}%
198 \def\@DeclareMathSizes#1#2#3#4#5{%
199 \@defaultunits\dimen@#2pt\relax\@nnil
200 \if$#3$%
201 \expandafter \let
202 \csname S@\strip@pt\dimen@\endcsname
203 \mathfontsfalse
204 \else
205 \expandafter \gdef
206 \csname S@\strip@pt\dimen@\endcsname
207 {\gdef\tf@size{#3}\gdef\sfont@size{#4}%
208 \gdef\ssfont@size{#5}%
209 #1%
210 }%
211 \fi}%
212 \end{release}
213 \end{kernel}
214 \onlypreamble{\@DeclareMathSizes

```

## 26 Selecting a new font

### 26.1 Macros for the user

`\fontencoding` As we said in the introduction a font is described by four parameters. We first define macros to specify the wanted *family*, *series*, or *shape*. These are simply recorded in internal macros `\f@family`, `\f@series`, and `\f@shape`, resp. We use `\edef`'s so that the arguments can also be macros.

```

215 \DeclareRobustCommand\fontencoding[1]{%
216 \expandafter\ifx\csname T@#1\endcsname\relax
217 \latexerror{Encoding scheme ‘#1’ unknown}\@eha
218 \else
219 \edef\f@encoding{#1}%
220 \ifx\cf@encoding\f@encoding

```

If the new encoding is the same as the old encoding we have nothing to do. However, in case we had a sequence of several encoding changes without a `\selectfont` in-between we can save processing by making sure that `\enc@update` is `\relax`.

```

221         \let\enc@update\relax
222     \else
    If current and new encoding differ we define the macro \enc@update to contain
    all updates necessary at \selectfont time.
223         \let\enc@update\@enc@update
224     \fi
225     \fi
226 }

\@enc@update
227 \def\@enc@update{%
    When \@enc@update is executed \f@encoding holds the encoding name for the
    new encoding and \cf@encoding the name of the last active encoding.
    We start by setting the init command for encoding dependent macros to
    \@changed@cmd.
228     \expandafter
229     \let
230     \csname\cf@encoding -cmd\endcsname
231     \@changed@cmd
    Then we turn the one for the new encoding to \@current@cmd (see ltoutenc.dtx
    for further explanations).
232     \expandafter
233     \let
234     \csname\f@encoding-cmd\endcsname
235     \@current@cmd
    We execute the default settings \default@T, followed by the one for the new
    encoding.
236     \default@T
237     \csname T@\f@encoding\endcsname
    Finally we change the default substitution values, disable \enc@update and make
    \f@encoding officially the current encoding.
238     \csname D@\f@encoding\endcsname
239     \let\enc@update\relax
240     \let\cf@encoding\f@encoding
241 }

\enc@update The default action in \selectfont is to do nothing.
242 \let\enc@update\relax

\fontfamily
    \f@family 243 \DeclareRobustCommand\fontfamily[1]{\edef\f@family{#1}}
\fontseries 244 \DeclareRobustCommand\fontseries[1]{\edef\f@series{#1}}
    \f@series 245 \DeclareRobustCommand\fontshape [1]{\edef\f@shape{#1}}
\fontshape Some handy abbreviation if you want to get some particular font in the current
    \f@shape size. If also the size should change one has to issue a \fontsize command first.
246 \DeclareRobustCommand\usefont[4]{\fontencoding{#1}\fontfamily{#2}%
247     \fontseries{#3}\fontshape{#4}\selectfont
248     \ignorespaces}

```

`\linespread` The command `\linespread` changes the current `\baselinestretch` by calling `\set@fontsize`. The values for `\f@size` and `\f@baselineskip` will be left unchanged.

```

249 \DeclareRobustCommand\linespread[1]
250   {\set@fontsize{#1}\f@size\f@baselineskip}

```

`\fontsize` We also define a macro that allows to specify a size. In this case, however, we also need the value of `\baselineskip`. As the first argument to `\set@fontsize` we pass the current value of `\baselinestretch`. This will either match the internal value (in which case nothing changes, or it will be an updated value due to a user change of that macro using `\renewcommand`. If we would pass the internal `\f@linespread` such a change would be effectively overwritten by a size change.

```

251 \DeclareRobustCommand\fontsize[2]
252   {\set@fontsize\baselinestretch{#1}{#2}}

```

`\f@linespread` This macro holds the current internal value for `\baselinestretch`.

```

253 \let\f@family\@empty
254 \let\f@series\@empty
255 \let\f@shape\@empty
256 \let\f@size\@empty
257 \let\f@baselineskip\@empty
258 \let\f@linespread\@empty

```

`\cf@encoding`

```

259 \let\f@encoding\@empty
260 \let\cf@encoding\@empty

```

`\@defaultunits` The function `\@defaultunits` when wrapped around a `dimen` or `skip` assignment supplies default units. Usage:

```

\@defaultunits\dimen@=#1pt\relax\@nnil

```

Note: the `\relax` is *\*important\**. Other units can be substituted for the ‘pt’ if desired.

We use `\remove@to@nnil` as an auxiliary macros for `\@defaultunits`. It just has to gobble the supplied default unit ‘pt’ or whatever, if it wasn’t used in the assignment.

```

261 \def\@defaultunits{\afterassignment\remove@to@nnil}

```

`\strip@pt` This macro strips the characters `pt` produced by using `\the` on a `dimen` register.

```

\rem@pt
262 \begingroup
263   \catcode‘P=12
264   \catcode‘T=12
265   \lowercase{
266     \def\x{\def\rem@pt##1.##2PT{##1\ifnum##2>\z@.##2\fi}}
267   \expandafter\endgroup\x
268 \def\strip@pt{\expandafter\rem@pt\the}

```

`\mathversion` `\mathversion` takes the math *version* name as argument, defines `\math@version` appropriately and switches to the font selected forcing a call to `\glb@settings` if the *version* is known to the system.

```

269 \DeclareRobustCommand\mathversion[1]
270   {\@nomath\mathversion

```

```

271      \expandafter\ifx\csname mv@#1\endcsname\relax
272      \@latex@error{Math version ‘#1’ is not defined}\@eha\else
273      \edef\math@version{#1}%

```

We need to force a math font setup both now and at the point where we return to the previous math version. Forcing a math font setup can simply be done by setting `\glb@currsz` to an invalid value since this will trigger the setup when the formula starts.

```

274      \gdef\glb@currsz{}%

```

When the scope of the current `\mathversion` ends we need to restore the old setup. However this time we need to force it directly at least if we are inside math, otherwise we could wait. Another way to enhance this code here is to do the setting only if the version really has changed after all. This might be interesting in case of `amstext` and `boldsymbol`.

```

275      \aftergroup\glb@settings
276      \fi}

```

If  $\TeX$  would support a hook just before the end of a formula (opposite of `\everymath` so to speak) the implementation of the algorithm would be much simpler because in that case we would set up the correct math fonts at this point without having to worry about incorrect settings due to nesting. The same would be true if in  $\LaTeX$  the use of `$` (as the primitive  $\TeX$  command) would be impossible and instead only a higher-level interface would be available. Note that this does not mean that a `$` couldn't be the short-hand for starting and stopping that higher-level interface, it only means that the direct  $\TeX$  function must be hidden.

Anyway, since we don't have this and won't have it in  $\LaTeX 2_\epsilon$  we need to implement it in a somewhat slower way.

We test for the current math font setup on entry of a formula, i.e., on the hooks `\everymath` and `\everydisplay`. But since these hooks may contain user data we provide ourselves with an internal version of these hooks which stays frozen.

```

\frozen@everymath New internal names for \everymath and \everydisplay.
\frozen@everydisplay 277 \let\frozen@everymath\everymath
278 \let\frozen@everydisplay\everydisplay

```

```

\everymath Now we provide now user hooks that will be called in the frozen internals.
\everydisplay 279 \newtoks\everymath
280 \newtoks\everydisplay

```

```

\frozen@everymath Now we define the behaviour of the frozen hooks: first check the math setup then
call the user hook.

```

```

281 \frozen@everymath = {\check@mathfonts
282                      \the\everymath}

```

```

\frozen@everydisplay Ditto for the display hook.
283 \frozen@everydisplay = {\check@mathfonts
284                        \the\everydisplay}

```

```

\curr@math@size This holds locally the current math size.
285 \let\curr@math@size\@empty

```

## 26.2 Macros for loading fonts

<code>\pickup@font</code>	<p>The macro <code>\pickup@font</code> which is used in <code>\selectfont</code> is very simple: if the font name is undefined (i.e. not known yet) it calls <code>\define@newfont</code> to load it.</p> <pre> 286 \def\pickup@font{% 287     \expandafter \ifx \font@name \relax 288         \define@newfont 289     \fi} </pre>
<code>\split@name</code>	<p><code>\pickup@font</code> assumes that <code>\font@name</code> is set but it is sometimes called when <code>\f@family</code>, <code>\f@series</code>, <code>\f@shape</code>, or <code>\f@size</code> may have the wrong settings (see, e.g., the definition of <code>\getanddefine@fonts</code>). Therefore we need a macro to extract font <i>family</i>, <i>series</i>, <i>shape</i>, and <i>size</i> from the font name. To this end we define <code>\split@name</code> which takes the font name as a list of characters of <code>\catcode 12</code> (without the backslash at the beginning) delimited by the special control sequence <code>\@nil</code>. This is not very complicated: we first ensure that <code>/</code> has the right <code>\catcode</code></p> <pre> 290 {\catcode'\/=12 </pre> <p>and define <code>\split@name</code> so that it will define our private <code>\f@encoding</code>, <code>\f@family</code>, <code>\f@series</code>, <code>\f@shape</code>, and <code>\f@size</code> macros.</p> <pre> 291 \gdef\split@name#1/#2/#3/#4/#5\@nil{\def\f@encoding{#1}% 292                                     \def\f@family{#2}% 293                                     \def\f@series{#3}% 294                                     \def\f@shape{#4}% 295                                     \def\f@size{#5}}} </pre>
<code>\curr@fontshape</code>	<p>Abbreviation which may get removed again for speed.</p> <pre> 296 \def\curr@fontshape{\f@encoding/\f@family/\f@series/\f@shape} </pre>
<code>\define@newfont</code>	<p>Now we can tackle the problem of defining a new font.</p> <pre> 297 \def\define@newfont{% </pre> <p>We have already mentioned that the token list that <code>\split@name</code> will get as argument must not start with a backslash. To reach this goal we will set the <code>\escapechar</code> to <code>-1</code> so that the <code>\string</code> primitive will not generate an escape character. To keep this change local we open a group. We use <code>\begingroup</code> for this purpose since <code>\define@newfont</code> might be called in math mode, and an empty <code>\bgroup... \egroup</code> would add an empty Ord atom to the math list and thus affect the spacing.</p> <p>Also locally redefine <code>\typeout</code> so that ‘No file ...fd’ Warnings become Font Info message just sent to the log file.</p> <pre> 298     \begingroup 299     \let\typeout\@font@info 300     \escapechar\m@ne </pre> <p>Then we extract <i>encoding scheme</i>, <i>family</i>, <i>series</i>, <i>shape</i>, and <i>size</i> from the font name. Note the four <code>\expandafter</code>’s so that <code>\font@name</code> is expanded first, then <code>\string</code>, and finally <code>\split@name</code>.</p> <pre> 301     \expandafter\expandafter\expandafter 302         \split@name\expandafter\string\font@name\@nil </pre>

If the `\curr@fontshape` combination is not available, (i.e. undefined) we call the macro `\wrong@fontshape` to take care of this case. Otherwise `\extract@font` will load the external font for us.

```

303 %   \expandafter\ifx
304 %       \csname\curr@fontshape\endcsname \relax
305 %   \try@load@fontshape % try always
306 %   \fi
307 \expandafter\ifx
308     \csname\curr@fontshape\endcsname \relax
309     \wrong@fontshape\else

```

To allow substitution we call the `curr@fontshape` macro which usually will expand to `\relax` but may hold code for substitution (see `\subst@fontshape` definition).

```

310 %       \csname\curr@fontshape\endcsname
311       \extract@font\fi

```

We are nearly finished and must only restore the `\escapechar` by closing the group.

```

312 \endgroup}

313 \def\try@load@fontshape{%
314     \expandafter
315     \ifx\csname \f@encoding+\f@family\endcsname\relax
316         \@font@info{Trying to load font information for
317                     \f@encoding+\f@family}%

```

We predefine this combination to be `\@empty` which means that next time we don't try again unnecessary in case we don't find a `.fd` file. If the file contains a `\DeclareFontFamily` command than this setting will be overwritten.

```

318     \global\expandafter\let
319     \csname\f@encoding+\f@family\endcsname\@empty

```

Set the catcodes used in the syntax, but do it only once (this will be restored at the end of the font loading group).

```

320     \nfss@catcodes
321     \let\nfss@catcodes\relax

```

For increased portability make the external filename monospace, but look for the (old style) mixed case filename if the first attempt fails.

On any monospace system this means that the file is looked for twice which takes up time and string space, but at least for this release Check for both names to give people time to re-install their private fd files with lowercase names.

```

322     \edef\reserved@a{%
323         \lowercase{%
324             \noexpand\InputIfFileExists{\f@encoding\f@family.fd}}}%
325     \reserved@a\relax
326         {\@input@{\f@encoding\f@family.fd}}%
327 \fi}

```

`\nfss@catcodes` This macro should contain the standard `\catcode` assignments to all characters which are used in the commands found in an `.fd` file and which might have special `\catcodes` in the middle of a document. If necessary, this list can be extended in a package file using a suitable number of `\expandafter`, i.e.,

```

\expandafter\def\expandafter\nfss@catcodes
\expandafter{\nfss@catcodes <additional settings>}

```



Note, that this macro might get executed several times since it is also called by `\DeclareFontShape`, thus it probably should not be misused as a general purpose hook.

```
328 \def\nfss@catcodes{%
```

We start by making @ a letter and ignoring all blanks and newlines.

```
329     \makeatletter
330     \catcode'\ 9%
331     \catcode'\^^I9%
332     \catcode'\^^M9%
```

Then we set up \, {, }, # and % in case an .fd file is loaded during a verbatim environment.

```
333     \catcode'\z@
334     \catcode'\{ \@ne
335     \catcode'\}\tw@
336     \catcode'\#6%
337     \catcode'\^7%
338     \catcode'\%14%
```

The we make sure that the important syntax parts have the right `\catcode`.

```
339     \@makeother\<%
340     \@makeother\>%
341     \@makeother\*%
342     \@makeother\.%
343     \@makeother\-%
344     \@makeother\/%
345     \@makeother\[%
346     \@makeother\]%
347     \@makeother\'%
348     \@makeother\'%
349     \@makeother\"%
350 }
```

`\DeclareErrorFont` Declare the last resort shape! We assume that in this fontshape there is a 10pt font but it doesn't really matter. We only loose one macro name if the assumption is false. But at least the font should be there!

```
351 \</2ekernel>
352 \<*/2ekernel | latexrelease>
353 \<latexrelease>\IncludeInRelease{2019/10/01}%
354 \<latexrelease>{\DeclareErrorFont}{No side effects please}%
355 \def\DeclareErrorFont#1#2#3#4#5{%
356     \xdef\error@fontshape{%
357         \noexpand\expandafter\noexpand\split@name\noexpand\string
358         \expandafter\noexpand\csname#1/#2/#3/#4/#5\endcsname
359         \noexpand\nil}%
```

Initialize all those internal variables which may or may not have values in the first seconds of NFSS' bootstrapping process. Later on such values will be updated when an encoding is selected, etc.

We definitely don't want to set `\f@encoding`; we can set all the others since if they are left "blank" any selection would grap "error default values" as well. However, this probably should go also—and now it did.

```
360 %     \gdef\f@encoding{#1}%
```

```

361 \gdef\default@family{#2}%
362 \gdef\default@series{#3}%
363 \gdef\default@shape{#4}%
364 }
365 \if2kernel| latexrelease)
366 \latexrelease)\EndIncludeInRelease
367 \latexrelease)\IncludeInRelease{0000/00/00}%
368 \latexrelease) \DeclareErrorFont}{No side effects please}%
369 \latexrelease)
370 \latexrelease)\def\DeclareErrorFont#1#2#3#4#5{%
371 \latexrelease) \xdef\error@fontshape{%
372 \latexrelease) \noexpand\expandafter\noexpand\split@name\noexpand\string
373 \latexrelease) \expandafter\noexpand\csname#1/#2/#3/#4/#5\endcsname
374 \latexrelease) \noexpand\@nil}%
375 \latexrelease) \gdef\default@family{#2}%
376 \latexrelease) \gdef\default@series{#3}%
377 \latexrelease) \gdef\default@shape{#4}%
378 \latexrelease) \global\let\f@family\default@family
379 \latexrelease) \global\let\f@series\default@series
380 \latexrelease) \global\let\f@shape\default@shape
381 \latexrelease) \gdef\f@size{#5}%
382 \latexrelease) \gdef\f@baselineskip{#5pt}%
383 \latexrelease)}
384 \latexrelease)\EndIncludeInRelease
385 \if2kernel)
386 \onlypreamble\DeclareErrorFont

```

`\wrong@fontshape` Before we come to the macro `\extract@font` we have to take care of unknown `\curr@fontshape` combinations. The general strategy is to issue a warning and to try a default *shape*, then a default *series*, and finally a default *family*. If this last one also fails T<sub>E</sub>X will go into an infinite loop. But if the defaults are set incorrectly one deserves nothing else!

```

387 \if2kernel)
388 \latexrelease)\IncludeInRelease{2015/01/01}{\wrong@fontshape}%
389 \latexrelease) \Font substitution in preamble}%
390 \if2kernel| latexrelease)
391 \def\wrong@fontshape{%
392 \csname D@f@encoding\endcsname % install defaults if in math

```

We remember the wanted `\curr@fontshape` combination which we will need in a moment.

```

393 \edef\reserved@a{\csname\curr@fontshape\endcsname}%
394 \ifx\last@fontshape\reserved@a
395 \errmessage{Corrupted NFSS tables}%
396 \error@fontshape
397 \else

```

Then we warn the user about the mess and set the shape to its default.

```

398 \let\f@shape\default@shape

```

If the combination is not known, try the default *series*.

```

399 \expandafter\ifx\csname\curr@fontshape\endcsname\relax
400 \let\f@series\default@series

```

If this is still undefined, try the default *family*. Otherwise give up. We never try to change the encoding scheme!

```
401      \expandafter
402      \ifx\csname\curr@fontshape\endcsname\relax
403      \let\f@family\default@family
```

If we change the font family and we are in the preamble then the corresponding .fd file may not been loaded yet. Therefore we try this now. Otherwise equating the requested font shape with the finally selected fontshape below will fail and can result in “NFSS tables corrupted”. After begin document that will not happen as all .fd files involved in substitution are loaded at \begin{document}.

```
404      \begingroup
405      \try@load@fontshape
406      \endgroup
407      \fi \fi
408      \fi
```

At this point a valid \curr@fontshape combination must have been found. We inform the user about this fact.

The \expandafter\string here stops T<sub>E</sub>X adding the space that it usually puts after command names in messages. The similar construction with \@undefined just produces ‘undefined’, but saves a few tokens.

\@wrong@font@char is locally redefined in \UseTextSymbol from its normal (empty) definition, to report the symbol generating the font switch.

```
409      \@font@warning{Font shape ‘\expandafter\string\reserved@a’
410                      \expandafter\@gobble\string\@undefined\MessageBreak
411                      using ‘\curr@fontshape’ instead\@wrong@font@char}%
412      \global\let\last@fontshape\reserved@a
```

We change \@defaultsubs to produce a warning at the end of the document.

The macro \@defaultsubs is initially \relax but gets changed here if some default font substitution happens. It is then executed in \enddocument.

```
413      \gdef\@defaultsubs{%
414      \@font@warning{Some font shapes were not available, defaults
415                      substituted.\@gobbletwo}}%
```

If we substitute a \curr@fontshape combination by the default one we don’t want the warning to be printed out whenever this (unknown) combination is used. Therefore we globally \let the macro corresponding to the wanted combination equal to its substitution. This requires the use of four \expandafter’s since \csname... \endcsname has to be expanded before \reserved@a (i.e. the requested combination), and this must happen before the \let is executed.

```
416      \global\expandafter\expandafter\expandafter\let
417      \expandafter\reserved@a
418      \csname\curr@fontshape\endcsname
```

Now we can redefine \font@name accordingly. This *must* be done globally since it might occur in the group opened by \define@newfont. If we would this definition were local the closing \endgroup there would restore the old meaning of \font@name and then switch to the wrong font at the end of \selectfont although the correct font was loaded.

```
419      \xdef\font@name{%
420      \csname\curr@fontshape/\f@size\endcsname}%
```

The last thing this macro does is to call `\pickup@font` again to load the font if it is not defined yet. At this point this code will loop endlessly if the defaults are not well defined.

```

421 \pickup@font}
422 /2kernel | latexrelease)
423 (latexrelease)\EndIncludeInRelease
424 (latexrelease)\IncludeInRelease{0000/00/00}{\wrong@fontshape}%
425 (latexrelease) {Font substitution in preamble}%
426 (latexrelease)\def\wrong@fontshape{%
427 (latexrelease) \csname D@f@encoding\endcsname
428 (latexrelease) \edef\reserved@a{\csname\curr@fontshape\endcsname}%
429 (latexrelease) \ifx\last@fontshape\reserved@a
430 (latexrelease) \errmessage{Corrupted NFSS tables}%
431 (latexrelease) \error@fontshape
432 (latexrelease) \else
433 (latexrelease) \let\f@shape\default@shape
434 (latexrelease) \expandafter\ifx\csname\curr@fontshape\endcsname\relax
435 (latexrelease) \let\f@series\default@series
436 (latexrelease) \expandafter
437 (latexrelease) \ifx\csname\curr@fontshape\endcsname\relax
438 (latexrelease) \let\f@family\default@family
439 (latexrelease) \fi \fi
440 (latexrelease) \fi
441 (latexrelease) \@font@warning{Font shape
442 (latexrelease) '\expandafter\string\reserved@a'
443 (latexrelease) \expandafter\@gobble\string\@undefined
444 (latexrelease) \MessageBreak
445 (latexrelease) using '\curr@fontshape' instead\@wrong@font@char}%
446 (latexrelease) \global\let\last@fontshape\reserved@a
447 (latexrelease) \gdef\@defaultsubs{%
448 (latexrelease) \@font@warning{Some font shapes were not available,
449 (latexrelease) defaults substituted.\@gobbletwo}}%
450 (latexrelease) \global\expandafter\expandafter\expandafter\let
451 (latexrelease) \expandafter\reserved@a
452 (latexrelease) \csname\curr@fontshape\endcsname
453 (latexrelease) \xdef\font@name{%
454 (latexrelease) \csname\curr@fontshape/f@size\endcsname}%
455 (latexrelease) \pickup@font}
456 (latexrelease)\EndIncludeInRelease
457 (*2kernel)

```

`\@wrong@font@char` Normally empty but redefined in `\UseTextSymbol` so that the Font shape undefined message can refer to the symbol causing the problem.

```
458 \let\@wrong@font@char\@empty
```

`\@@defaultsubs` See above.

```
\@defaultsubs 459 \let\@defaultsubs\relax
```

`\strip@prefix` In `\extract@font` we will need a way to recover the replacement text of a macro. This is done by the primitive `\meaning` together with the macro `\strip@prefix` (for the details see appendix D of the `TEXbook`, p. 382).

```
460 \def\strip@prefix#1>{}
```

## 27 Assigning math fonts to *versions*

`\install@mathalphabet` This is just another name for `\gdef` but we can redefine it if necessary later on.  
 461 `\let\install@mathalphabet\gdef`

`\math@fonts`  
 462 `\let\math@fonts\@empty`

`\select@group` `\select@group` has four arguments: the new *math alphabet identifier* (a control sequence), the *math group number*, the extra macro for math mode and the `\curr@fontshape` definition macro name. We first check if we are in math mode.

463 `%\def\select@group#1#2#3{\relax\ifmmode`

We do these things locally using `\begingroup` instead of `\bgroup` to avoid the appearance of an empty Ord atom on the math list.

464 `% \begingroup`

We set the math fonts for the *family* in question by calling `\getanddefine@fonts` in the correct environment.

465 `% \escapechar\m@ne`

466 `% \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%`

We globally select the math fonts...

467 `% \globaldefs\@ne \math@fonts`

... and close the group to restore `\globaldefs` and `\escapechar`.

468 `% \endgroup`

As long as no *size* or *version* change occurs the *math alphabet identifier* should simply switch to the installed *math group* instead of calling `\select@group` unnecessarily. So we globally redefine the first argument (the new *math alphabet identifier*) to expand into a `\mathgroup` switch and then select this *alphabet*. Note that this redefinition will be overwritten by the next call to a *version* macro.

The original code for the end of `\select@group` was

`\gdef#1{#3\mathgroup #2}#1\fi}`

i.e. first redefining the *math alphabet identifier* and then calling the new definition to switch to the wanted *math group*. Now we define the *math alphabet identifier* as a call to the `\use@mathgroup` command.

469 `% \xdef#1{\noexpand\use@mathgroup\noexpand#2%`

470 `{\number\csname c@mv@\math@version\endcsname}}%`

But this is not sufficient, as we learned the hard way. The problem here is that the loading of the fonts that comprise the alphabet identifier `#1`, as well as the necessary math font assignments is deferred until it is used. This is OK so far, but if the fonts are switched within the current formula (which may happen if a sub-formula is a box that contains a math version switch) the font assignments for `#1` are not restored unless `#1` is used again. This is disastrous since TeX sees the wrong fonts at the end of the math formula, when it converts the math list into a horizontal list.

This is taken into account as follows: When a math alphabet identifier is used for the first time in a certain version it modifies the corresponding macro `\mv@<version>` so that it calls `\getanddefine@fonts` directly in future as well.

We use the macro `\extract@alph@from@version` to do this. It takes the math alphabet identifier `#1` and the math version macro as arguments.

```

471 % \expandafter\extract@alph@from@version
472 % \csname mv@\math@version\expandafter\endcsname
473 % \expandafter{\number\csname c@mv@\math@version\endcsname}%
474 % #1%
475 % \stepcounter{mv@\math@version}%

```

Finally, it is not possible to simply call the new definition since we have an argument (the third argument of `\use@mathgroup` or more exactly the argument of `\math@egroup` if the `margid` option is in force) which would swallow our closing `\fi`. So we use the `\expandafter` technique to remove the `\fi` before the `\use@mathgroup` is expanded.

```

476 %\expandafter #1\fi}

```

`\extract@alph@from@version` We proceed to the definition of the macro `\extract@alph@from@version`. As stated above, it takes a math alphabet identifier and a math version macro (e.g. `\mv@normal`) as its arguments.

```

477 \def\extract@alph@from@version#1#2#3{%

```

To extract and replace the definition of math alphabet identifier `#3` in macro `#1` we have to recall how this definition looks like: Somewhere in the replacement text of `#1` there is the sequence

```

\install@mathalphabet<math alphabet identifier> #3{%
    <Definitions for >#3}

```

Hence, the first thing we do is to extract the tokens preceding this definitions, the definition itself, and the tokens following it. To this end we define one auxiliary macro `\reserved@a`.

```

478 \def\reserved@a##1\install@mathalphabet#3##2##3\@nil{%

```

When `\reserved@a` is expanded, it will have the tokens preceding the definition in question in its first argument (`##1`), the following tokens in its third argument (`##3`), and the replacement text for the math alphabet identifier `#3` in its second argument. (`##2`). This is then recorded for later use in a temporary macro `\reserved@b`.

```

479 \def\reserved@b{##2}%

```

Additionally, we define a macro `\reserved@c` to reconstruct the definitions for the math version in question from the tokens that will remain unchanged (`##1` and `##3`) and the yet to build new definitions for the math alphabet identifier `#3`.

```

480 \def\reserved@c####1{\gdef#1{##1####1##3}}%

```

Then we execute our auxiliary macro.

```

481 \expandafter\reserved@a#1\@nil

```

OK, so now we have to build the new definition for `#3`. To do so, we first extract the interesting parts out of the old one. The old definition looks like:

```

\select@group<math alphabet identifier>
    <math group number><math extra part>
<curr@fontshape definition>

```

So we define a new temporary macro `\reserved@a` that extracts these parts.

```

482 \def\reserved@a\select@group#3##1##2\@nil{%

```

This macro can now directly rebuild the math version definition by calling `\reserved@c`:

```
483 \reserved@c{%
484 \getanddefine@fonts{#2}##2%
485 \install@mathalphabet#3{%
486 \relax\ifmmode \else \non@alpherr#3\fi
487 \use@mathgroup##1{#2}}}%

```

In addition it defines the alphabet the way it should be used from now on.

```
488 \gdef#3{\relax\ifmmode \else \non@alpherr#3\fi
489 \use@mathgroup##1{#2}}}%

```

Finally, we only have to call this macro `\reserved@a` on the old definitions recorded in `\reserved@b`:

```
490 \expandafter\reserved@a\reserved@b\@nil
491 }

```

`\math@bgroup` Here are the default definitions for `\math@bgroup` and `\math@egroup`. We use `\bgroup` instead of `\begingroup` to avoid ‘leaking out’ of style changes. This has the side effect of always producing mathord atoms.

```
492 \let\math@bgroup\bgroup
493 \def\math@egroup#1{#1\egroup}

```

`\calculate@math@sizes` Here is the default definition for `\calculate@math@sizes` a more elaborate interface is under testing in `mthscale.sty`.

```
494 \gdef\calculate@math@sizes{%
495 \font@info{Calculating\space math\space sizes\space for\space
496 size\space <\f@size>}%
497 \dimen@f@size \p@
498 \@tempdimb \defaultscriptratio \dimen@
499 \dimen@ \defaultscriptscriptratio \dimen@
500 \expandafter\xdef\csname S@\f@size\endcsname{%
501 \gdef\noexpand\tf@size{\f@size}%
502 \gdef\noexpand\s@size{\strip@pt\@tempdimb}%
503 \gdef\noexpand\ssf@size{\strip@pt\dimen@}%
504 \noexpand\math@fontstrue}}

```

`\defaultscriptratio` The default ratio for math sizes is:  
`\defaultscriptscriptratio` 1 to `\defaultscriptratio` to `\defaultscriptscriptratio`.  
By default this is 1 to .7 to .5.  
505 `\def\defaultscriptratio{.7}`  
506 `\def\defaultscriptscriptratio{.5}`

`\noaccents@` If we don’t have a definition for `\noaccents@` we provide a dummy.  
507 `\ifx\noaccents@\@undefined`  
508 `\let\noaccents@\@empty`  
509 `\fi`

`\showhyphens` The `\showhyphens` command must be redefined since the version in `plain.tex` uses `\tenrm`. We have also made some further adjustments for its use in L<sup>A</sup>T<sub>E</sub>X.  
510 `/2ekernel`  
511 `(\latexrelease)\IncludeInRelease{2017/01/01}{\showhyphens}%`  
512 `(\latexrelease) {XeTeX support for \showhyphens}%`  
513 `(*2ekernel | \latexrelease)`  
514 `\ifx\XeTeXcharclass\@undefined`

Version for engines other than XeTeX.

```

515 \DeclareRobustCommand\showhyphens[1]{%
516   \setbox0\vbox{%
517     \color@begingroup
518     \everypar{}%
519     \parfillskip\z@skip\hsize\maxdimen
520     \normalfont
521     \pretolerance\m@ne\tolerance\m@ne\hbadness\z@\showboxdepth\z@\ #1%
522     \color@endgroup}}
523 \else

```

XeTeX version. When using system fonts XeTeX reports consecutive runs of characters as a single item in box logging, which means the standard `\showhyphens` does not work. This version typesets the text into a narrow box to force hyphenation and then reconstructs a horizontal list with explicit hyphens to generate the display. Note that the `lmr` OpenType font is forced, this works even if the characters are not in the font as hyphenation is attempted due to the width of the space and hyphen character. It may generate spurious Missing Character warnings in the log, these are however suppressed from the terminal output by ensuring that `\tracingonline` is locally zero.

```

524 \DeclareRobustCommand\showhyphens[1]{%
525   \setbox0\vbox{%
526     \usefont{TU}{lmr}{m}{n}%
527     \hsize 1sp %
528     \hbadness\@M
529     \hfuzz\maxdimen
530     \tracingonline\z@
531     \everypar={}%
532     \leftskip\z@skip
533     \rightskip\z@skip
534     \parfillskip\z@skip
535     \hyphenpenalty=-\@M
536     \pretolerance\m@ne
537     \interlinepenalty\z@
538     \clubpenalty\z@
539     \widowpenalty\z@
540     \brokenpenalty1127 %
541     \setbox\z@\hbox{%
542       \noindent
543       \hskip\z@skip
544       #1%
545       \par

```

Note here we stop the loop if made no progress, non-removable items may mean that we can not process the whole list (which would be testable as `\lastnodetype=-1`).

```

546     \loop
547     \@tempwafalse
548     \ifnum\lastnodetype=11\unskip\@tempwattrue\fi
549     \ifnum\lastnodetype=12\unkern\@tempwattrue\fi
550     \ifnum\lastnodetype=13 %
551       \count@\lastpenalty
552       \unpenalty\@tempwattrue

```



```

553 \fi
554 \ifnum\lastnodetype=\@ne
555 \setbox\tw@\lastbox\@tempswatrue
556 \setbox0\hbox{\unhbox\tw@\unskip\unskip\unpenalty%
557 \ifnum\count@=1127 \else\ \fi
558 \unhbox0}%
559 \count@\z@
560 \fi
561 \if@tempswa
562 \repeat
563 \hbadness\z@
564 \hsize\maxdimen
565 \showboxdepth\z@
566 \tolerance\m@ne
567 \hyphenpenalty\z@
568 \noindent\unhbox\z@
569 }}
570 \fi
571 </2ekernel | latexrelease>
572 <latexrelease>\EndIncludeInRelease
573 <latexrelease>\IncludeInRelease{0000/00/00}{\showhyphens}%
574 <latexrelease> {XeTeX support for \showhyphens}%
575 <latexrelease>\gdef\showhyphens#1{%
576 <latexrelease> \setbox0\vbox{%
577 <latexrelease> \color@begingroup
578 <latexrelease> \everypar{%
579 <latexrelease> \parfillskip\z@skip\hsize\maxdimen
580 <latexrelease> \normalfont
581 <latexrelease> \pretolerance\m@ne\tolerance\m@ne
582 <latexrelease> \hbadness\z@\showboxdepth\z@\ #1%
583 <latexrelease> \color@endgroup}}
584 <latexrelease>\EndIncludeInRelease
585 <*2ekernel>

```

\addto@hook We need a macro to add tokens to a hook.

```

586 \long\def\addto@hook#1#2{#1\expandafter{\the#1#2}}

```

\@vpt

```

587 \def\@vpt{5}

```

\@vipt

```

588 \def\@vipt{6}

```

\@viipt

```

589 \def\@viipt{7}

```

\@viiipt

```

590 \def\@viiipt{8}

```

\@ixpt

```

591 \def\@ixpt{9}

```

```

\@xpt
592 \def\@xpt{10}

\@xipt
593 \def\@xipt{10.95}

\@xiipt
594 \def\@xiipt{12}

\@xivpt
595 \def\@xivpt{14.4}

\@xvipt
596 \def\@xvipt{17.28}

\@xxpt
597 \def\@xxpt{20.74}

\@xxvpt
598 \def\@xxvpt{24.88}
599 </2ekernel>

```

# File p

## ltfsstrc.dtx

### 28 Introduction

This package contains the code for tracing font loading and font changes. It basically overlays some of the low-level functions of NFSS with additional code used for tracing.

The package accepts the following options:

**errorshow** Write all information about font changes etc. only to the transcript file unless an error happens. This means that information about font substitution will not be shown on the terminal.

**warningshow** Show all NFSS warnings on the terminal. This setting corresponds to the default behaviour of NFSS if the `tracefmt` package is *not* loaded!

**infoshow** Show all NFSS warning and all NFSS info messages (that are normally only written to the transcript file) also on the terminal. This is the default if the `tracefmt` package is loaded.

**debugshow** In addition to `infoshow` show also changing of math fonts as far as possible (this option can produce a large amount of output).

**loading** Show the name of external fonts when they are loaded. This option shows only “newly” loaded fonts not those already preloaded in the format or the class file before the `tracefmt` package became active.

**pausing** Turn all font warnings into errors so that L<sup>A</sup>T<sub>E</sub>X will stop.

### 29 A driver for this document

The next bit of code contains the documentation driver file for T<sub>E</sub>X, i.e., the file that will produce the documentation you are currently reading. It will be extracted from this file by the DOCSTRIP program.

When this file is processed directly by L<sup>A</sup>T<sub>E</sub>X this will produce the documentation as well.

```
1 \(*driver)
2 \documentclass{ltxdoc}
3
4
5 %\OnlyDescription % comment out for implementation details
6
7 \begin{document}
8   \DocInput{ltfsstrc.dtx}
9 \end{document}
10 \(/driver)
```

## 30 The Implementation

**Warning:** Read the macro documentation with a grain of salt. It is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

If we are making a package file it is a good idea to test whether we are running under 2e. This code is actually placed at the very beginning of this file for easier maintenance, thus commented out here.

```
11 (*package)
12 %\NeedsTeXFormat{LaTeX2e}
13 %\ProvidesPackage{tracefnt}[??/??/?? v?.??]
14 %
15 %\Standard LaTeX package (font tracing)]
16 \end{package}
```

The `debug` module makes use of commands contained in a special package file named `trace.sty`.<sup>4</sup>

```
16 \input{trace.sty}
```

## 31 Handling Options

`\tracingfonts` Here is the definition of the integer register for the font trace. As a default in a package file we use 1 to give error messages if fonts are substituted. If this code is used for debugging or tracing reasons in the format file (i.e. in `fam.dtx`) we use 0 as the default. But if no font trace is used we build a definition that will produce a warning message.

```
17 (*2ekernel)
18 \def\tracingfonts{%
19   \@font@warning{Command \noexpand\tracingfonts
20     not provided.\MessageBreak
21     Use the ‘tracefnt’ package.\MessageBreak Command found:}%
22   \count@}
23 \end{2ekernel}
```

The `\count@` in the line above will remove the number after `\tracingfonts`. Note that this definition will be overwritten by the next line if one of these modules are included.

```
24 (*package, trace, debug)
25 \newcount\tracingfonts
26 \tracingfonts=0
27 \end{package, trace, debug}
```

The option `errorshow` turns off all warnings so that only real errors are shown. `warningshow` corresponds to the NFSS default (when `tracefnt` is not loaded). `infoshow` is the default for this package here; and `debugshow`, `loading`, and `pausing` extend the amount of information even further.

```
28 (*package)
29 \DeclareOption{errorshow}{%
30   \def\@font@info#1{%
31     \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
32   }
33 }
```

---

<sup>4</sup>This package is not in distribution at the moment (and probably doesn't any longer work). Think of this part of the code as being historical artefacts.

```

32             {LaTeX Font Info: \space\space\space#1}}%
33   \def\@font@warning#1{%
34     \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
35     {LaTeX Font Warning: #1}}%
36   }

37 \DeclareOption{warningshow}{%
38   \def\@font@info#1{%
39     \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
40     {LaTeX Font Info: \space\space\space#1}}%
41   \def\@font@warning#1{%
42     \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
43     {LaTeX Font Warning: #1}}%
44   }

45 \DeclareOption{infoshow}{%
46   \def\@font@info#1{%
47     \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
48     {LaTeX Font Info: \space\space\space#1}}%
49   \def\@font@warning#1{%
50     \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
51     {LaTeX Font Warning: #1}}%
52   }

53 \DeclareOption{loading}{%
54   \tracingfonts\tw@
55   }

56 \DeclareOption{debugshow}{%
57   \ExecuteOptions{infoshow}%
58   \tracingfonts\thr@@
59   }

60 \DeclareOption{pausing}{%
61   \def\@font@warning#1{%
62     \GenericError
63       {(Font)\@spaces\@spaces\@spaces\space\space}%
64       {LaTeX Font Warning: #1}%
65       {See the LaTeX Companion for details.}%
66       {I'll stop for every LaTeX Font Warning because
67        you requested\MessageBreak the 'pausing' option
68        to the tracefnt package.}}%
69   }

```

We make `infoshow` the default, which in turn defines `\font@warning` and `\font@info`.

```

70 \ExecuteOptions{infoshow}
71 \ProcessOptions
72 </package>

```

We also need a default definition inside the kernel:

```

73 <*2kernel>
74 \def\@font@info#1{%
75   \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
76   {LaTeX Font Info: \space\space\space#1}}%
77 \def\@font@warning#1{%
78   \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%

```

```

79                                     {LaTeX Font Warning: #1}}%
80 </2ekernel>

```

## 32 Macros common to fam.tex and tracefmt.sty

In the first versions of `tracefmt.dtx` some macros of `fam.dtx`<sup>5</sup> were redefined to included the extra tracing information. Now these macros are all defined in this file (i.e. removed from `fam.dtx`) and different production versions can be obtained simply by specifying a different set of modules to include when generating `lftss.dtx`.

### 32.1 General font loading

`\extract@font` This macro organizes the font loading. It first calls `\get@external@font` which will return in `\external@font` the name of the external font file (the .tfm) as it was determined by the NFSS tables.

```

81 <*2ekernel | package>
82 \def\extract@font{%
83   \get@external@font

```

Then the external font is loaded and assigned to the font identifier stored inside `\font@name` (for this reason we need `\expandafter`).

```

84   \global\expandafter\font\font@name\external@font\relax

```

When tracing we typeout the internal and external font name.

```

85 <*trace>
86   \ifnum \tracingfonts >\@ne
87     \@font@info{External font '\external@font'
88               loaded as\MessageBreak \font@name}\fi
89 </trace>

```

Finally we call the corresponding “loading action” macros to finish things. First the font is locally selected to allow the use of `\font` inside the loading action macros.

```

90   \font@name \relax

```

The next two lines execute the “loading actions” for the family and then for the individual font shape.

```

91   \csname \f@encoding+\f@family\endcsname
92   \csname\curr@fontshape\endcsname
93   \relax
94   }
95 </2ekernel | package>

```

The `\relax` at the end needs to be explained. This is inserted to prevent `TEX` from scanning too far when it is executing the replacement text of the loading code macros.

`\get@external@font` This function tries to find an external font name. It will place the name into the macro `\external@font`. If no font is found it will return the one that was defined via `\DeclareErrorFont`.

```

96 <*2ekernel>
97 \def\get@external@font{%

```

---

<sup>5</sup>This file is currently not distributed in documented form. Its code is part of `lftss.dtx`.

We don't know the external font name at the beginning.

```

98   \let\external@font\@empty
99   \edef\font@info{\expandafter\expandafter\expandafter\string
100     \csname \curr@fontshape \endcsname}%
101   \try@size@range

```

If this failed, we'll try to substitute another size of the same font. This is done by the `\try@size@substitution` macro. It “knows about” `\do@extract@font`, `\font@name`, `\f@size`, and so on.

```

102   \ifx\external@font\@empty
103     \try@size@substitution
104     \ifx\external@font\@empty
105       \@latex@error{Font \expandafter \string\font@name\space
106         not found}\@eha
107       \error@fontshape
108       \get@external@font
109   \fi\fi
110 }
111 \</2ekernel>

```

`\selectfont` The macro `\selectfont` is called whenever a font change must take place.

```

112 (*2ekernel | package)
113 \DeclareRobustCommand\selectfont
114   {%

```

When `debug` is specified we actually want something like ‘undebug’. The font selection is now stable so that using `\tracingall` on some other macros will show us a lot of unwanted information about font loading. Therefore we disable tracing during font loading as long as `\tracingfonts` is less than 4.

```

115 (+debug) \pushtracing
116 (+debug) \ifnum\tracingfonts<4 \tracingoff
117 (+debug) \else \tracingon\p@selectfont \fi

```

If `\baselinestretch` was redefined by the user it will not longer match its internal counterpart `\f@linespread`. If so we call `\set@fontsize` to prepare `\size@update`.

```

118   \ifx\f@linespread\baselinestretch \else
119     \set@fontsize\baselinestretch\f@size\f@baselineskip \fi

```

Then we generate the internal name of the font by concatenating *family*, *series*, *shape*, and current *size*, with slashes as delimiters between them. This is much more readable than standard L<sup>A</sup>T<sub>E</sub>X's `\twfbf`, etc. We define `\font@name` globally, as always. The reason for this is explained later on.

```

120   \xdef\font@name{%
121     \csname\curr@fontshape/\f@size\endcsname}%

```

We call the macro `\pickup@font` which will load the font if necessary.

```

122   \pickup@font

```

Then we select the font.

```

123   \font@name

```

If `\tracingfonts` is greater than 2 we also show the font switch. We do this before `\glb@settings` is called since this macro might redefine `\font@name`.

```

124 (*trace)

```

```

125 \ifnum \tracingfonts>\tw@
126 \font@info{Switching to \font@name}\fi
127 \trace)

```

Finally we call `\size@update`. This macro is normally empty but will contain actions (like setting the `\baselineskip`) that have to be carried out when the font size, the base `\baselineskip` or the `\baselinestretch` have changed.

```

128 \size@update

```

A similar function is called to handle anything related to encoding updates. This one is changed from `\relax` by `\fontencoding`.

```

129 \enc@update

```

Just before ending this macro we have to pop the tracing stack if it was pushed before.

```

130 \ifx\debug\poptracing
131 \fi

```

`\set@fontsize` The macro `\set@fontsize` does the actual work. First it assigns new values to `\f@size`, `\f@baselineskip` and `\f@linespread`.

```

132 \def\set@fontsize#1#2#3{%
133 \@defaultunits\@tempdimb#2pt\relax\@nnil
134 \edef\f@size{\strip@pt\@tempdimb}%
135 \@defaultunits\@tempskipa#3pt\relax\@nnil
136 \edef\f@baselineskip{\the\@tempskipa}%
137 \edef\f@linespread{#1}%

```

For backward compatibility and for later testing within `\selectfont` the internal value of `\f@linespread` is passed back to `\baselinestretch`.

```

138 \let\baselinestretch\f@linespread

```

Additional processing will happen within `\selectfont`. For this reason the macro `\size@update` (which will be called in `\selectfont`) will be defined to be:

```

139 \def\size@update{%

```

First calculate the new `\baselineskip` and also store it in `normalbaselineskip`

```

140 \baselineskip\f@baselineskip\relax
141 \baselineskip\f@linespread\baselineskip
142 \normalbaselineskip\baselineskip

```

then to set up a new `\strutbox`

```

143 \setbox\strutbox\hbox{%
144 \vrule\@height.7\baselineskip
145 \@depth.3\baselineskip
146 \@width\z@}%

```

We end with a bit of tracing information.

```

147 \ifx\tracingfont\tracingfont
148 \ifnum \tracingfonts>\tw@
149 \ifx\f@linespread\empty
150 \let\reserved@a\empty
151 \else
152 \def\reserved@a{\f@linespread x}%
153 \fi
154 \font@info{Changing size to \f@size/\reserved@a
155 \f@baselineskip}%
156 \aftergroup\type@restoreinfo \fi
157 \trace)

```



When all this is processed `\size@update` redefines itself to `\relax` so that in later calls of `\selectfont` no extra code will be executed.

```
158      \let\size@update\relax}%
159  }
```

Instead of defining this macro internally we might speed things up by placing the code into a separate macro and use `\let`!

`\size@update` Normally this macro does nothing; it will be redefined by `\set@fontsize` to initiate an update.

```
160 \let\size@update\relax
```

`\type@restoreinfo` This macro produces some info when a font size and/or baseline change will get restored.

```
161 (*trace)
162   \def\type@restoreinfo{%
163     \ifx\f@linespread\@empty
164       \let\reserved@a\@empty
165     \else
166       \def\reserved@a{\f@linespread x}%
167     \fi
168     \@font@info{Restoring size to
169                \f@size/\reserved@a\f@baselineskip}}
170 (/trace)
```

`\glb@settings` The macro `\glb@settings` globally selects all math fonts for the current size if necessary.

```
171 \def\glb@settings{%
```

When `\glb@settings` gains control a size change was requested and all previous font assignments need to be replaced. Therefore the old values of the fonts are no longer needed. For every *math group* the new assignments are appended to `\math@fonts`. But this happens only if the `math@fonts` switch is set to true. However, we always set up the correct math sizes for script and scriptscript fonts since they may be needed even if we don't set up the whole math machinery.

Here we set the math size, script size and scriptscript size. If the `S@...` macro is not defined we have to first calculate the three sizes.

```
172   \expandafter\ifx\csname S@\f@size\endcsname\relax
173     \calculate@math@sizes
174   \fi
```

The effect of this is that `\calculate@math@sizes` may or may not define the `S@...` macro. In the first case the next time the same size is requested this macro is used, otherwise `\calculate@math@sizes` is called again. This also sets the `math@fonts` switch. If it is true we must switch the math fonts.

```
175   \csname S@\f@size\endcsname
176   \ifmath@fonts
177 (*trace)
178   \ifnum \tracingfonts>\tw@
179     \@font@info{Setting up math fonts for
180                \f@size/\f@baselineskip}\fi
181 (/trace)
```

Inside a group we execute the macro for the current math *version*. This sets `\math@fonts` to a list of `\textfont...` assignments. `\getanddefine@fonts` (which may be called at this point) needs the `\escapechar` parameter to be set to `-1`.

```
182      \begingroup
183      \escapechar\m@ne
184      \csname mv@\math@version \endcsname
```

Then we set `\globaldefs` to 1 so that all following changes are done globally. The math font assignments recorded in `\math@fonts` are executed and `\glb@currsiz` is set equal to `\f@size`. This signals that the fonts for math in this size are set up.

```
185      \globaldefs\@ne
186      \math@fonts
187      \let \glb@currsiz \f@size
188      \endgroup
```

Finally we execute any code that is supposed to happen whenever the math font setup changes. This register will be executed in local mode which means that everything that is supposed to have any effect should be done globally inside. We can't execute it within `\globaldefs\@ne` as we don't know what ends up inside this register, e.g., it might contain calculations which use some local registers to calculate the final (global) value.

```
189      \the\every@math@size
```

Otherwise we announce that the math fonts are not set up for this size.

```
190 (*trace)
191      \else
192          \ifnum \tracingfonts>\tw@
193              \@font@info{No math setup for
194                          \f@size/\f@baselineskip}\fi
195      \endtrace
196      \fi
197  }
198  \endkernel | package)
```

`\baselinestretch` In `\selectfont` we used `\baselinestretch` as a factor when assigning a value to `\baselineskip`. We use 1 as a default (i.e. no stretch).

```
199 (*2ekernel)
200 \def\baselinestretch{1}
```

`\every@math@size` We must still define the hook `\every@math@size` we used in `\glb@settings`. We initialize it to nothing. It is important to remember that everything that goes into this hook should to global updates, local changes will have weird effects.

```
201 \newtoks\every@math@size
202 \every@math@size={}
203 \endkernel
```

## 32.2 Math fonts setup

### 32.2.1 Outline of algorithm for math font sizes

$\TeX$  uses the the math fonts that are current when the end of a formula is reached. If we don't want to keep font setups local to every formula (which would result in

an enormous overhead, we have to be careful not to end up with the wrong setup in case formulas are nested, e.g., we need to be able to handle

```
$ a=b+c \mbox{ \small for all $b$ and $c$ in $Z$ }$
```

Here the inner formulae `b` and `c\in Z` are typeset in `\small` but we have to return to `\normalsize` before we reach the closing `$` of the outer formula.

This is handled in the following way:

1. At any point in the document the global variable `\gbl@currsz` contains the point size for which the math fonts currently are set up.
2. Whenever we start a formula we compare its value with the local variable `\f@size` that describes the current text font size.
3. If both are the same we assume that we can use the current math font setup without adjustment.
4. If they differ we call `\gbl@settings` which changes the math font setup and updates `\gbl@currsz`.
  - (a) If we are recursively inside another formula (`\if@inmath`) we ensure that `\gbl@settings` is executed again in the outer formula, so that the old setup is automatically restored.
  - (b) Otherwise, we set the switch `@inmath` locally to `true` so that all nested formulae will be able to detect that they are nested in some outer formula.

The above algorithm has the following features:

- For sizes which are not containing any formula no math setup is done. Compared to the original algorithm of NFSS this results in the following savings:
  - No unnecessary loading of math fonts for sizes that are not used to typeset any math formulae (explicit or implicit ones).
  - No time overhead due to unnecessary changes of the math font setup on entrance and exit of the text font size.
- Math font setup changes for top-level formulae will survive (there is no restoration after the formula) thus any following formula in the same size will be directly typesettable. Compared to original implementation in NFSS2 the new algorithm has the overhead of one test per formula to see if the current math setup is valid (in the original algorithm the setup was always valid, thus no test was necessary).
- In nested formulae the math font setup is restored in the outer formula by a series of `\aftergroup` commands and checks. Compared to the original algorithm this involves additional checks ( $2 \times \langle \text{non-math levels} \rangle$  per inner formula).

### 32.2.2 Code for math font size setting

`\check@mathfonts` In the `\check@mathfonts` macros we implement the steps 2 to 4 except that instead of a switch the macro `\init@restore@glb@settings` is used.

```

204 (*2kernel|package)
205 \def\check@mathfonts{%
206   \ifx \glb@currsiz \f@size
207   (*trace)
208     \ifnum \tracingfonts>\thr@@
209       \@font@info{*** MATH: no change \f@size\space
210         curr/global (\curr@math@size/\glb@currsiz)}\fi
211   (/trace)
212   \else
213   (*trace)
214     \ifnum \tracingfonts>\thr@@
215       \@font@info{*** MATH: setting up \f@size\space
216         curr/global (\curr@math@size/\glb@currsiz)}\fi
217   (/trace)
218     \glb@settings
219     \init@restore@glb@settings
220   \fi
221   \let\curr@math@size\f@size
222   \def\init@restore@glb@settings{\aftergroup\restglb@settings}%
223 }
```

`\init@restore@glb@settings` This macros does by default nothing but get redefined inside `\check@mathfonts` to initiate fontsize restoring in nested formulas.

```

224 (-trace)\let\init@restore@glb@settings\relax
225 (*trace)
226 \def\init@restore@glb@settings{%
227   \ifnum \tracingfonts>\thr@@
228     \@font@info{*** MATH: no resetting (not in
229       nested math)}\fi
230 }
231 (/trace)
```

`\restglb@settings` This macro will be executed the first time after the current formula.

```

232 \def\restglb@settings{%
233   (*trace)
234     \ifnum \tracingfonts>\thr@@
235       \@font@info{*** MATH: restoring}\fi
236   (/trace)
237     \begingroup
238       \let\f@size\curr@math@size
239       \ifx\glb@currsiz \f@size
240   (*trace)
241     \ifnum \tracingfonts>\thr@@
242       \@font@info{*** MATH: ... already okay (\f@size)}\fi
243   (/trace)
244     \else
245   (*trace)
246     \ifnum \tracingfonts>\thr@@
247       \@font@info{*** MATH: ... to \f@size}\fi
248   (/trace)
```

```

249         \glb@settings
250     \fi
251 \endgroup
252 }

```

### 32.2.3 Other code for math

`\use@mathgroup` The `\use@mathgroup` macro should be used in user macros to select a math group. Depending on whether or not the `margid` option is in force it has two or three arguments. For this reason it should be called as the last macro.

First we test if we are inside math mode since we don't want to apply a useless definition.

```

253 \def\use@mathgroup#1#2{\relax\ifmmode

254 (*trace)
255   \ifnum \tracingfonts>\tw@
256     \count@#2\relax
257     \@font@info{Using \noexpand\mathgroup
258               (\the\count@) #2}\fi
259 }/trace)

```

If so we first call the '=' macro (i.e. argument three) to set up special things for the selected math group. Then we call `\mathgroup` to select the group given by argument two and finally we place #1 (i.e. the argument of the *math alphabet identifier*) at the end. This part of the code is surrounded by two commands which behave like `\begingroup` and `\endgroup` if we want *math alphabet identifier*s but will expand into `\@empty` if we want simply switches to a new math group. Since argument number 2 may be a digit instead of a control sequence we add a `\relax`. Otherwise something like `\mit{1}` would switch to math group 11 (and back) instead of printing an oldstyle 1.

```

260     \math@bgroup
261     \expandafter\ifx\csname M@f@encoding\endcsname#1\else
262     #1\fi
263     \mathgroup#2\relax

```

Before we reinsert the swallowed token (arg. three) into the input stream, in the case that the *math alphabet identifier* isn't called in math mode, we remove the `\fi` with the `\expandafter` trick. This is necessary if the token is actually an macro with arguments. In such a case the `\fi` will be misinterpreted as the first argument which would be disastrous.

```

264     \expandafter\math@egroup\fi}%

```

The surrounding macros equal `\begingroup` and `\endgroup`. But using internal names makes it possible to overwrite their meaning in certain cases. This is for example used in  $\mathscr$ -TeX macros for placing accents.

`\math@egroup` If the `margid` option is in force (which can be tested by looking at the definition of `\math@bgroup` we change the `\math@egroup` command a bit to display the current *math group number* after it closes the scope of *math alphabet* with `\endgroup`.

```

265 (*trace)
266   \ifx\math@bgroup\bgroup
267     \def\math@egroup#1{#1\egroup

```

```

268     \ifnum \tracingfonts>\tw@
269     \@font@info{Restoring \noexpand\mathgroup
270       (\ifnum\mathgroup=\m@ne default\else \the\mathgroup \fi)%
271       }\fi}
272   \fi
273 \trace)

```

`\getanddefine@fonts` `\getanddefine@fonts` has two arguments: the *(math group number)* and the *family/series/shape* name as a control sequence.

```

274 \def\getanddefine@fonts#1#2{%
First we turn of tracing when \tracingfonts is less than 4.
275 (+debug) \pushtracing
276 (+debug) \ifnum\tracingfonts<4 \tracingoff
277 (+debug) \else \tracingon\getanddefine@fonts \fi

278 (*trace)
279 \ifnum \tracingfonts>\tw@
280 \count@#1\relax
281 \@font@info{\noexpand\mathgroup (\the\count@) #1 :=\MessageBreak
282   \string#2 \tf@size/\sf@size/\ssf@size}\fi
283 \trace)

```

We append the current `\tf@size` to `#2` to obtain the font name.<sup>6</sup> Again, `font@name` is defined globally, for the reasons explained in the description of `\wrong@fontshape`.

```

284 \xdef\font@name{\csname \string#2/\tf@size\endcsname}%

```

Then we call `\pickup@font` to load it if necessary. We remember the internal name as `\textfont@name`.

```

285 \pickup@font \let\textfont@name\font@name

```

Same game for `\scriptfont` and `\scriptscriptfont`:

```

286 \xdef\font@name{\csname \string#2/\sf@size\endcsname}%
287 \pickup@font \let\scriptfont@name\font@name
288 \xdef\font@name{\csname \string#2/\ssf@size\endcsname}%
289 \pickup@font

```

Then we append the new `\textfont...` assignments to the `\math@fonts`.

```

290 \edef\math@fonts{\math@fonts
291   \textfont#1\textfont@name
292   \scriptfont#1\scriptfont@name
293   \scriptscriptfont#1\font@name}%

```

Just before ending this macro we have to pop the tracing stack if it was pushed before.

```

294 (+debug) \poptracing
295   }
296 \endkernel | package)

```

---

<sup>6</sup>One might ask why this expansion does not generate a macro name that starts with an additional `\` character. The solution is that `\escapechar` is set to `-1` before `\getanddefine@fonts` is called.

### 33 Scaled font extraction

`\ifnot@nil` We begin with a simple auxiliary macro. It checks whether its argument is the token `\@nil`. If so, it expands to `\@gobble` which discards the following argument, otherwise it expands to `\@firstofone` which reproduces its argument.

```
297 (*2kernel)
298 \def\ifnot@nil#1{\def\reserved@a{#1}%
299 \ifx\reserved@a\@nnil \expandafter\@gobble
300 \else \expandafter\@firstofone\fi}
```

`\remove@to@nnil` Three other auxiliary macros will be needed in the following: `\remove@to@nnil` gobbles up everything up to, and including, the next `\@nnil` token, and `\remove@angles` and `\remove@star` do the same for the character `>` and `*`, respectively, instead of `\@nnil`.

```
301 \def\remove@to@nnil#1\@nnil{}
302 \def\remove@angles#1>{\set@simple@size@args}
303 \def\remove@star#1*{#1}
```

`\extract@sizefn` This macro takes a size specification and parses it into size function and the optional and mandatory arguments.

```
304 \def\extract@sizefn#1*#2\@nnil{%
305 \if>#2>\set@size@func@args#1\@nnil
306 \let\sizefn@info\@empty
307 \else\expandafter\set@size@func@args\remove@star#2\@nnil
308 \def\sizefn@info{#1}\fi
309 }
```

`\try@simple@size` This function tries to extract the given size (specified by `\f@size`) for the requested font shape. The font information must already be present in `\font@info`. The central macro that does the real work is `\extract@fontinfo`. We will first give a simple example how this macro works, and describe it in full generality later.

Assume that the requested parameters are: *encoding scheme* ‘OT1’, *family* ‘cm’, *series* ‘sansserif’, *shape* ‘normal’, and *size* ‘12’. The corresponding font definitions have already been extracted from the macro `\OT1/cm/sansserif/normal` and stored in `font@info`. (Otherwise `\extract@fontinfo` doesn’t get called.) This information consists of a token list made of characters of category code 12 of the form

```
<10*>cmss10<12*>cmss12<17*>cmss17
```

For reasonable packages one usually needs more sizes but this is sufficient to get the flavour. We will define a macro `\extract@fontinfo` to find the external font name (‘cmss12’) for us:

```
\def\extract@fontinfo#1<12*#2>#3<#4\@nnil{%
\set@simple@size@args#3<#4\@nnil
\execute@size@function{#2}}
```

so that when it gets called via

```
\extract@fontinfo<10*>cmss10<12*>cmss12<17*>cmss17\@nnil
```

#1 will contain all characters before <12\*>, #2 will be empty, #3 will be exactly cmss12, and #3 will be 17>cmss17. The expansion is therefore

```
\set@simple@size@args cmss12<17*>cmss17\@nnil
\execute@size@function{}
```

This means: the default (empty) size function will be executed, with its optional argument argument set to empty and its mandatory argument set to cmss12 by \set@simple@size@args. As we discussed earlier, the effect of the default size function is to load the given external font (cmss12) at the specified size (12)—which is exactly what was intended.

But this is only part of the whole story. It may be that the size requested does not occur in the token list \font@info. And the simple definition of \extract@fontinfo we gave above does not allow to specify give more than one size specification in front of the external font name.

Let's address these two problems separately. The first one is solved with the following trick: We define \extract@fontinfo as follows:

```
\def\extract@fontinfo#1<12*#2>#3<#4\@nnil{%
  \ifnot@nil{#3}%
    {\set@simple@size@args#3<#4\@nnil
      \execute@size@function{#2}%
    }}%
```

How does this work? We call \extract@fontinfo via

```
\expandafter\extract@fontinfo\font@info<12*>\@nil<\@nnil
```

i.e. by appending <12\*>\@nil<\@nnil. If the size ('12' in this case) appears in \font@info everything works as explained above, the only difference being that argument #4 of \extract@fontinfo additionally gets the tokens <12\*>\@nil<\@nnil. However, if the size is not found everything up to the final <12\*> is in argument #1, #3 gets \@nil, and #2 and #4 are empty. The macro \ifnot@nil will discard the calls to \set@simple@size@args and execute@size@function, and hence \font@info will continue to be equal to \@empty. This means that no simple size specification matching the requested size could be found.

The second problem (more than one simple size specification for one external font name) will be addressed in \set@simple@size@args below.

The macros are hidden inside other control sequences so that we have to build \extract@fontinfo in several steps.

So here's the actual definition of \extract@font in \try@simple@size.

```
310 % % this could be replaced by \try@size@range making the subst slower!
```

```
311 \def\try@simple@size{%
```

\reserved@a is made an abbreviation for the head of the definition of the macro \extract@fontinfo.

```
312   \def\reserved@a{\def\extract@fontinfo###1}%
```

Now we can define \extract@fontinfo. Here we handle a small but convenient variation: in case of the default (empty) size function it is allowed to omit the \* character.

```
313   \expandafter\reserved@a\expandafter<\f@size>##2<##3\@nnil{%
```

```
314     \ifnot@nil{##2}%
```



```

315         {\set@simple@size@args##2<##3\@nnil
316         \execute@size@function\sizefn@info
317         }}%

```

Now we call `\extract@fontinfo`. Note the `<\@nil` tokens at the end.

```

318     \expandafter\expandafter
319     \expandafter\extract@fontinfo\expandafter\font@info
320     \expandafter<\f@size>\@nil<\@nnil
321 }

```

`\set@simple@size@args` As promised above, the macro `\set@simple@size@args` will handle the case of several size specifications in a row. If another size specification follows, the very first token of its argument list is the character `<`. By starting the definition as follows,

```

322 \def\set@simple@size@args#1<{%

```

parameter `#1` is empty in this case, and contains the size function's arguments otherwise. We distinguish these two cases (Note that the character `<` cannot appear in `#1`) by calling `\remove@angles` for empty `#1` and `\extract@sizefn` otherwise. In the latter case we have to take care of the remaining character tokens and discard them. This is done by `\remove@to@nnil`. Note also the use of Kabelschacht's method.

```

323         \if<#1<%
324         \expandafter\remove@angles
325         \else
326         \extract@sizefn#1*\@nil
327         \expandafter\remove@to@nnil
328         \fi}

```

Now, we are through with the case of a simple size, except for calling the size function. This will be handled later, as it is the same mechanism for all types of size specification. We will now proceed to macros for extraction of size range specification.

`\extract@rangefontinfo` `\extract@rangefontinfo` goes through a font shape definition in the input until it recognizes the tokens `<\@nil->`. It looks for font ranges with font size functions. It's operation is rather simple: it discards everything up to the next size specification and passes this on to `\is@range` for inspection. The specification (parameter `#2` is inserted again, in case it is needed later.

```

329 \def\extract@rangefontinfo#1<#2>{%
330     \is@range#2->\@nil#2>}

```

`\is@range` `\is@range` is again a sort of dispatcher macro: if the size specification it is looking at is not a range specification it discards it and calls `\extract@rangefontinfo` to continue the search. Otherwise it calls `\check@range` to check the requested size against the specified range.

From the way `\is@range` is called inside `\extract@rangefontinfo` we see that `#2` is the character `>` if the size specification found is a simple one (as it does not contain a `-` character. This is checked easily enough and `\extract@rangefontinfo` called again. Note that the extra tokens inserted after the `\@nil` in the call to `\is@range` appear at the beginning of the first argument to `\extract@rangefontinfo` and are hence ignored.

```

331 \def\is@range#1-#2\@nil{%
332   \if>#2\expandafter\check@single\else
333     \expandafter\check@range\fi}

```

`\check@range` `\check@range` takes lower bound as parameter #1, upper bound as #2, size function as #3 and the size function's arguments as #4. If #3 is the special token `\@nil` `\font@info` is exhausted and we can stop searching.

```

334 \def\check@range#1-#2>#3<#4\@nnil{%
335   \ifnot@nil{#3}{%

```

If #3 wasn't `\@nil` we have a range. We start by assuming that we have to recurse. Note that we have to reinsert an `<` as it was already removed by scanning.

```

336     \def\reserved@f{\extract@rangefontinfo<#4\@nnil}%

```

We have to make sure that both boundaries are present, if not we have to set them. Here we check the upper bound. If `\upper@bound` is zero after the assignment we set it to `\maxdimen` (upper open range). We need to use a *dimen* register for the scan since we may have a decimal number as the boundary.

```

337     \upper@bound0#2\p@
338     \ifdim\upper@bound=\z@ \upper@bound\maxdimen\fi

```

Now we check the upper boundary against `\f@size`. If it is larger or equal than `\f@size` this range is no good and we have to recurse.

```

339     \ifdim \f@size \p@<\upper@bound

```

Otherwise we have to check the lower bound. This time it is not necessary to scan the boundary value into a register because if it is empty we get zero as desired. We could even omit the 0 which would result in `1pt` as default lower boundary. If `\f@size` is smaller than the boundary we have to recurse.

```

340     \lower@bound0#1\p@
341     \ifdim \f@size \p@<\lower@bound
342     \else

```

If both tests are passed we can try executing the size function.

```

343     \set@simple@size@args#3<#4\@nnil
344     \execute@size@function\sizefn@info

```

If the function was successful it should have left an external font name in `\external@font`. We use this to see if we can stop scanning. Otherwise we recurse.

```

345     \ifx\external@font\@empty
346     \else
347       \let\reserved@f\@empty
348     \fi
349     \fi
350     \fi
351     \reserved@f}}

```

`\lower@bound` We use two *dimen* registers `\lower@bound` and `\upper@bound` to store the lower  
`\upper@bound` and upper endpoints of the range we found.

```

352 \newdimen\lower@bound
353 \newdimen\upper@bound

```

`\check@single` `\check@single` takes the size as parameter #1, size function as #2 and the size function's arguments as #3. We can assume that there is always something in the pipeline since the very last entry is a faked range (see above).

```
354 \def\check@single#1>#2<#3\@nnil{%
```

We start by assuming that we have to recurse. Note that we have to reinsert an < as it was already removed by scanning.

```
355 \def\reserved@f{\extract@rangefontinfo<#3\@nnil}%
```

Now we check the the size against `\f@size`. If it is not equal `\f@size` it is not good and we have to recurse.

```
356 \ifdim \f@size \p@=#1\p@
```

Otherwise if this test is passed we can try executing the size function.

```
357 \set@simple@size@args#2<#3\@nnil
```

```
358 \execute@size@function\sizefn@info
```

If the function was successful it should have left an external font name in `\external@font`. We use this to see if we can stop scanning. Otherwise we recurse.

```
359 \ifx\external@font\@empty
```

```
360 \else
```

```
361 \let\reserved@f\@empty
```

```
362 \fi
```

```
363 \fi
```

```
364 \reserved@f}
```

`\set@size@funct@args` This macro sets the optional and mandatory arguments for a size function. If the optional argument is not present it is set to the empty token list. The mandatory argument is delimited by the token `\@nil`.

```
365 \def\set@size@funct@args{\@ifnextchar[%
```

```
366 \set@size@funct@args@{\set@size@funct@args@[]}]}
```

```
367 \def\set@size@funct@args@[#1]#2\@nil{%
```

```
368 \def\mandatory@arg{#2}%
```

```
369 \def\optional@arg{#1}%
```

```
370 \</2kernel>
```

`\DeclareSizeFunction` This function defines a new size function hiding the internal from the designer. The body of the size function may use `\optional@arg` and `\mandatory@arg` denoting the optional and mandatory argument that may follow the size specification <...>.

```
371 \<2kernel>
```

```
372 \def\DeclareSizeFunction#1#2{\@namedef{s@fct@#1}{#2}}
```

```
373 \@onlypreamble\DeclareSizeFunction
```

```
374 \</2kernel>
```

`\execute@size@function` This macro is very simple. The only point worth noting is that calling an undefined size function will do nothing (actually execute a `\relax`).

```
375 \<2kernel | package>
```

```
376 \def\execute@size@function#1{%
```

```
377 \<trace>
```

```
378 \ifundefined{s@fct@#1}%
```

```
379 {\errmessage{Undefined font size function #1}%
```

```

380         \s@fct@}%
381         {\csname s@fct@#1\endcsname}%
382 \trace)
383 (-trace)      \csname s@fct@#1\endcsname
384 }
385 \endkernel | package)

```

**\try@size@range** This macro tries to find a suitable range for requested size (specified by `\f@size`) in `\font@info`. All the relevant action is done in `\extract@rangefontinfo`. All that needs to be done is to stuff in the token list in `\font@info` so that `\extract@rangefontinfo` can inspect it. Note the `<-*\@nil>` token at the end to stop scanning.

```

386 (*2kernel)
387 \def\try@size@range{%
388     \expandafter\extract@rangefontinfo\font@info <-*\@nil>\@nnil
389 }

```

**\try@size@substitution** This is the last thing that can be tried. If the desired `\f@size` is found neither among the simple size specifications nor in one of the ranges the whole list of size specifications is searched for a nearby simple size.

```

390 \gdef\try@size@substitution{%

```

First we do some initializations. `\@tempdimb` will hold the difference between the wanted size and the best solution found so far, so we initialise it with `\maxdimen`. The macro `\best@size` will hold the best size found, nothing found is indicated by the empty value.

```

391 \@tempdimb \maxdimen
392 \let \best@size \@empty

```

Now we loop over the specification

```

393 \expandafter \try@simples \font@info <\number\M>\@nil>\@nnil
394 }

```

**\font@submax** The macro `\font@submax` records the maximal deviation from the desired size encountered so far. Its value is used in a warning message at `\end{document}`. The macro `\fontsubfuzz` contains the amount that will not cause terminal warnings (warnings still go into the transcript file).

```

395 \def\font@submax{0pt}
396 \def\fontsubfuzz{.4pt}
397 \endkernel)
398 (+package)\def\fontsubfuzz{0pt}

```

**\try@simples** `\try@simples` goes through a font shape definition in the input until it recognizes the tokens `<-*\@nil>`. It looks for simple sizes to determine the two closest sizes. It is assumed that simple sizes are in increasing order.

```

399 (*2kernel)
400 \gdef\try@simples#1<#2>{%
401     \tryif@simple#2->\tryif@simple}

```

**\tryis@simple** `\tryis@simple` is similar to `\is@range`. If it sees a simple size, it checks it against the value of `\f@size` and sets `\lower@font@size` or `\higher@font@size`. In the latter case, it stops the iteration. By adding `<\number\M>` at the end of the line we always have an end point. This is a hack which probably should be corrected.

First it checks whether it is finished already, then whether the size specification in question is a simple one.

```
402 \gdef\tryif@simple#1-#2\tryif@simple{%
```

Most common case for \reserved@f first:

```
403 \let \reserved@f \try@simples
404 \if>#2%
```

If so, it compares it to the value of \f@size. This is done using a dimen register since there may be fractional numbers.

```
405 \dimen@ #1\p@
406 \ifdim \dimen@<\@M\p@
```

If \dimen@ is \@M\p@ we have reached the end of the fontspec (hopefully) otherwise we compare the value with \f@size and compute in \@tempdimc the absolute value of the difference between the two values.

```
407 \ifdim \f@size\p@<\dimen@
408 \tempdimc \dimen@
409 \advance\tempdimc -\f@size\p@
410 \else
411 \tempdimc \f@size\p@
412 \advance\tempdimc -\dimen@
413 \fi
```

The result is then compared with the smallest difference we have encountered, if the new value (in \@tempdimc is smaller) we have found a size which is a better approximation so we make it the \best@size and adjust \@tempdimb.

```
414 \ifdim \tempdimc<\tempdimb
415 \tempdimb \tempdimc
416 \def \best@size{#1}%
417 \fi
```

When we have reached the end of the fontspec we substitute the best size found (if any). We code this inline to save macro space; in the past this was done by a macro called \subst@size.

```
418 \else
```

\subst@size This macro substitutes the size recorded in \best@size for the unavailable size \f@size. \font@submax records the maximum difference between desired size and selected size in the whole run.

```
419 % \subst@size %% coded inline
420 % \def\subst@size{%
421 \ifx \external@font\@empty
422 \ifx \best@size\@empty
423 \else
424 \ifdim \tempdimb>\font@submax \relax
425 \xdef \font@submax {\the\tempdimb}%
426 \fi
427 \let \f@user@size \f@size
428 \let \f@size \best@size
429 \ifdim \tempdimb>\fontsubfuzz\relax
430 \@font@warning{Font\space shape\space
431 'curr@fontshape'\space in\space size\space
432 <\f@user@size>\space not\space available\MessageBreak
433 size\space <\f@size>\space substituted}%
```

```

434      \fi
435      \try@simple@size
436      \do@subst@correction
437      \fi
438      \fi
439      % %}

```

This brings us back into the main part of `\tryif@simple`. Finally we get rid of any rubbish left over on the input stack.

```

440      \let \reserved@f \remove@to@nnil
441      \fi
442      \fi

```

If it's a range iterate also.

```

443      \reserved@f}

```

### 33.1 Sizefunctions

In the following we define some useful size functions.

`\s@fct@` This is the default size function. Mandatory argument is an external font name, optional argument a scale factor. The font is scaled to `\f@size` if no optional argument is present, and to `\f@size` multiplied by the optional argument otherwise.

```

444 \DeclareSizeFunction{}\empty@sfcnt\@font@warning}
445 \DeclareSizeFunction{s}\empty@sfcnt\@font@info}
446 \def\empty@sfcnt#1{%
447     \@tempdimb \f@size\p@
448     \ifx\optional@arg\empty
449     \else
450         \@tempdimb \optional@arg\@tempdimb
451         #1{Font\space shape\space '\curr@fontshape'\space
452             will\space be\MessageBreak
453             scaled\space to\space size\space \the\@tempdimb}%
454     \fi
455     \edef\external@font{\mandatory@arg\space at\the\@tempdimb}}

```

`\s@fct@gen` This size function generates the external name from the mandatory argument and the requested user size, and thus can be used for external names where the size is encoded in the font name. The optional argument a scale factor. The font is scaled to `\f@size` if no optional argument is present, and to `\f@size` multiplied by the optional argument otherwise.

```

456 \DeclareSizeFunction{gen}\gen@sfcnt\@font@warning}
457 \DeclareSizeFunction{sgen}\gen@sfcnt\@font@info}
458 \def\gen@sfcnt{%
459     \edef\mandatory@arg{\mandatory@arg\f@size}%
460     \empty@sfcnt}

```

`\s@fct@genb` This size function is similar to `gen`, but for fonts where the size is encoded in the font name in centipoints, as in the DC fonts version 1.2. The font is scaled to `\f@size` if no optional argument is present, and to `\f@size` multiplied by the optional argument otherwise.

```

461 \DeclareSizeFunction{genb}{\genb@sfcnt\@font@warning}
462 \DeclareSizeFunction{sgenb}{\genb@sfcnt\@font@info}

463 \def\genb@sfcnt{%
464     \edef\mandatory@arg{\mandatory@arg\expandafter\genb@x\f@size..\@}%
465     \empty@sfcnt}

\genb@x The auxiliary macros \genb@x and \genb@y are used to convert the \f@size into
\genb@y centipoints.

466 \def\genb@x#1.#2.#3\@@{\two@digits{#1}\genb@y#200\@@}
467 \def\genb@y#1#2#3\@@{#1#2}

\s@fct@sub This size function handles font substitution. The mandatory argument is a fam-
ily/series/shape combination, the optional argument (if present) is ignored. The
font encoding scheme cannot be changed. Therefore, the first thing we do is to
prepend the encoding scheme.

468 \DeclareSizeFunction{sub}{\sub@sfcnt\@font@warning}
469 \DeclareSizeFunction{ssub}{\sub@sfcnt\@font@info}

470 \def\sub@sfcnt#1{%
471     \edef\mandatory@arg{\f@encoding/\mandatory@arg}%

Next action is split the arg into its individual components and allow for a late font
shape load.

472     \begingroup
473     \expandafter\split@name\mandatory@arg/\@nil
474     \try@load@fontshape
475     \endgroup

Then we record the current \f@size since it may get clobbered.

476     \let\f@user@size\f@size

Then we check whether this new combination is defined and give an error message
if not. In this case we also switch to \error@fontshape.

477     \expandafter
478     \ifx\csname\mandatory@arg\endcsname\relax
479         \errmessage{No\space declaration\space for\space
480             shape\space \mandatory@arg}%
481         \error@fontshape
482     \else

Otherwise we warn the user about the substitution taking place.

483     #1{Font\space shape\space '\curr@fontshape'\space in\space
484         size\space <\f@size>\space not\space available\MessageBreak
485         Font\space shape\space '\mandatory@arg'\space tried\space
486         instead}%
487     \expandafter\split@name\mandatory@arg/\@nil
488     \fi

Then we restart the font specification scan by calling \get@external@font.

489     \edef\f@size{\f@user@size}%
490     \get@external@font

Finally \do@subst@correction is called to get the font name right.

491     \do@subst@correction
492 }

```

`\s@fct@subf` The `subf` size function allows substitution of another font. The mandatory argument is the external name of the font to be substituted, the optional argument a size scaling factor like in the default size function. The main difference to the default size function is the warning message.

```

493 \DeclareSizeFunction{subf}{\subf@sfcnt\@font@warning}
494 \DeclareSizeFunction{ssubf}{\subf@sfcnt\@font@info}

495 \def\subf@sfcnt#1{%
496     #1{Font\space shape\space '\curr@fontshape'\space in\space
497         size\space \f@size\space not\space available\MessageBreak
498         external\space font\space '\mandatory@arg'\space used}%
499     \empty@sfcnt#1%
500 }
```

`\s@fct@fixed` The `fixed` size function is for using a font at a different size than requested. A warning message is printed, and the external font to be used is taken from the mandatory argument. If an optional argument is present it is used as the ‘at’ size for the font. Otherwise the font is loaded at its design size.

```

501 \DeclareSizeFunction{fixed}{\fixed@sfcnt\@font@warning}
502 \DeclareSizeFunction{sfixed}{\fixed@sfcnt\@font@info}

503 \def\fixed@sfcnt#1{%
504     \ifx\optional@arg\@empty
505         \let\external@font\mandatory@arg
506     \else
507         \edef\external@font{\mandatory@arg\space at\optional@arg pt}%
508     \fi
509     #1{External\space font\space '\external@font'\space loaded\space
510         for\space size\MessageBreak
511         <\f@size>}%
512 }
513 />2ekernel)
```



# File q

## ltfsscmp.dtx

This file contains the implementation of commands giving compatibility with the original ‘NFSS1’ release of the Font Selection Scheme.

**Warning:** The macro documentation is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

Version 1 of NFSS is obsolete now for about 20 years (and was “current” only for a short intermediate time) so with the 2015 release these internal interface commands are removed from the kernel and made available via `latexrelease` package so that backward compatibility remains ensured for very old documents.

```

1 (*latexrelease)
2 \IncludeInRelease{2015/01/01}{\new@fontshape}%
3                               {NFSS version1 commands}%
4 \let\new@fontshape\@undefined
5 \let\warn@rel@i\@undefined
6 \let\scan@fontshape\@undefined
7 \let\scan@@fontshape\@undefined
8 \let\subst@fontshape\@undefined
9 \let\extra@def\@undefined
10 \let\default@mextra\@undefined
11 \let\preload@sizes\@undefined
12 \let\err@rel@i\@undefined
13 \let\newmathalphabet\@undefined
14 \let\newmathalphabet@\@undefined
15 \let\newmathalphabet@@\@undefined
16 \let@if@no@font@opt\@undefined
17 \let@no@font@optfalse\@undefined
18 \let\define@mathalphabet\@undefined
19 \let\define@mathgroup\@undefined
20 \let\addtoversion\@undefined
21 \EndIncludeInRelease

```

In older releases we provide the original definitions.

```

22 \IncludeInRelease{0000/00/00}{\new@fontshape}%
23                               {NFSS version1 commands}%

```

`\new@fontshape` The interface is now `\DeclareFontShape`.

```

24 \gdef\new@fontshape#1#2#3#4{%
25     \warn@rel@i\new@fontshape\DeclareFontShape
26     \expandafter\scan@fontshape\@gobble#4<\@nil><<%
27     \DeclareFontShape U{#1}{#2}{#3}\reserved@f}%
28 \@onlypreamble\new@fontshape

```

`\warn@rel@i` The warning message used above.

```

29 \gdef\warn@rel@i#1#2{%
30     \@font@warning{*** NFSS release 1 command
31                     \noexpand#1found\MessageBreak
32     *** Update by using release 2 command

```

```

33      \string#2.\MessageBreak
34      *** Recovery is probably possible}%
35 }%
36 \@onlypreamble\warn@rel@i

```

\scan@fontshape This will scan the old font shape definition syntax.

```

37 \gdef\scan@fontshape{%
38   \let\reserved@f\@empty
39   \let\reserved@e\@empty %      holds last info
40   \scan@@fontshape
41 }%
42 \@onlypreamble\scan@fontshape

```

\scan@@fontshape

```

43 \gdef\scan@@fontshape#1>#2#3<{%
44   \ifx\@nil#1%
45     \edef\reserved@f{\reserved@f\reserved@e}%
46   \else
47     \def\reserved@b{#1}%      nick names
48     \def\reserved@c{#3}%
49     \in@{ at}{#3}%
50     \ifin@
51       \in@{pt}{#3}% not a proof but a good chance
52     \ifin@

```

We grap also everything after pt and discard it if people have forgotten to place a percent sign there.

```

53     \def\reserved@a##1 at##2pt##3\@nil{%
54       \def\reserved@b{##2}%
55       \def\reserved@c{##1}%
56     }%
57     \reserved@a#3\@nil
58   \fi
59 \fi
60 \ifnum 0<0#2
61   \edef\reserved@d{subf*\reserved@c}%
62   \ifcase #2\or
63     \or
64   \else
65     \errmessage{*** What's this? NFSS release 0? ***}%
66   \fi
67 \else
68   \edef\reserved@d{#2\reserved@c}%
69 \fi
70 \ifx\reserved@d\reserved@e
71   \edef\reserved@f{\reserved@f<\reserved@b>}%
72 \else
73   \edef\reserved@f{\reserved@f\reserved@e<\reserved@b>}%add old info
74   \let\reserved@e\reserved@d
75 \fi
76 \expandafter\scan@@fontshape
77 \fi
78 }%
79 \@onlypreamble\scan@@fontshape

```

`\subst@fontshape` This is now also handled by the extend syntax of `\DeclareFontShape`.

```

80 \gdef\subst@fontshape#1#2#3#4#5#6{%
81     \warn@rel@i\subst@fontshape\DeclareFontShape
82     \DeclareFontShape{U}{#1}{#2}{#3}{<->sub*#4/#5/#6}{}}%
83 \@onlypreamble\subst@fontshape

```

`\extra@def` This was replaced by `\DeclareFontFamily`.

```

84 \gdef\extra@def#1#2#3{%
85     \warn@rel@i\extra@def\DeclareFontFamily
86     \DeclareFontFamily{U}{#1}{}%
87 }%
88 \@onlypreamble\extra@def

```

`\default@mextra` The new name is `\DeclareFontEncodingDefaults` but in this case we don't feel comfortable with this either.

```

89 \gdef\default@mextra{%
90     \warn@rel@i\default@mextra\DeclareFontEncodingDefaults

```

We pick up the argument to `\default@mextra` implicitly as the second argument of `\DeclareFontEncodingDefaults`.

```

91 \DeclareFontEncodingDefaults\relax
92 }%
93 \@onlypreamble\default@mextra

```

`\preload@sizes` The new interface is `\DeclarePreloadSizes`.

```

94 \gdef\preload@sizes{%
95     \warn@rel@i\preload@sizes\DeclarePreloadSizes
96     \DeclarePreloadSizes U%
97 }%
98 \@onlypreamble\preload@sizes

```

`\err@rel@i` This macro is used in cases where emulation with NFSS2 features is not really possible.

```

99 \gdef\err@rel@i#1#2{%
100 \@latex@error{*** NFSS release 1 command \noexpand#1found%
101     ^^J*** Recovery not possible. Use \string#2}%
102     {The new release of NFSS doesn't support the
103     \noexpand#1command^^Jany longer.
104     Please upgrade your file to the syntax of NFSS
105     release 2^^Jusing the \noexpand#2command.}%

```

Let's die.

```

106 \batchmode\input.\relax
107 }%
108 \@onlypreamble\err@rel@i

```

`\newmathalphabet` `\newmathalphabet` is the old form.

`\newmathalphabet@`

```

109 \gdef\newmathalphabet{%

```

`\newmathalphabet@@`

```

110 \if@no@font@opt
111 \@latex@error{*** NFSS release 1 command
112     \noexpand\newmathalphabet found%
113     ^^J \space*** Automatic recovery not possible.%
114     ^^J \space*** TYPE H for Help%
115     }%

```

```

116         {Please look at the file usrguide.tex for hints on
117         how to resolve this problem.}%
118     \else
119         \warn@rel@i\newmathalphabet\DeclareMathAlphabet
120     \fi
121     \@ifstar\newmathalphabet@@@
122         \newmathalphabet@@}%
123 \gdef\newmathalphabet@@#1{\DeclareMathAlphabet#1{U}{-}{-}{-}}%
124 \gdef\newmathalphabet@@@#1#2#3#4{%
125     \DeclareMathAlphabet{#1}{U}{#2}{#3}{#4}}%
126 \@onlypreamble\newmathalphabet
127 \@onlypreamble\newmathalphabet@@
128 \@onlypreamble\newmathalphabet@@@

\if@no@font@opt
\@no@font@optfalse 129 \global\let\if@no@font@opt\iftrue
130 \gdef\@no@font@optfalse{\let\if@no@font@opt\iffalse}%

\define@mathalphabet This is a case where dying is best.
131 \gdef\define@mathalphabet{%
132     \err@rel@i\define@mathalphabet\DeclareMathAlphabet
133 }%
134 \@onlypreamble\define@mathalphabet

\define@mathgroup And here is another one
135 \gdef\define@mathgroup{%
136     \err@rel@i\define@mathgroup\DeclareSymbolFont
137 }%
138 \@onlypreamble\define@mathgroup

\addtoversion \addtoversion is the old form.
139 \def\addtoversion#1#2{%
140     \warn@rel@i\addtoversion\SetMathAlphabet
141     \SetMathAlphabet#2{#1}{U}}%
142 \@onlypreamble\addtoversion

Finishing off this huge \IncludeInRelease argument:
143 \EndIncludeInRelease
144 </latexrelease>

```

# File r

## ltxssdcl.dtx

This file contains the main implementation of the font selection scheme commands. See other parts of the L<sup>A</sup>T<sub>E</sub>X distribution, or *The L<sup>A</sup>T<sub>E</sub>X Companion* for higher level documentation of these commands.

**Warning:** The macro documentation is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

## 34 Interface Commands

`\in@` `\in` is a utility macro with two arguments. It determines whether its first argument occurs in its second and sets the switch `\ifin@` accordingly. The first argument may not contain braces nor # (more precisely, tokens of category code 1, 2, or 6).

```

1 (*2kernel)
2 \def\in@#1#2%
3 {%
4   \begingroup
5     \def\in@@##1#1{%
6       \toks@\expandafter{\in@@#2{}}#1}%
7       \edef\in@@{\the\toks@}%
8     \expandafter\endgroup
9     \ifx\in@@\@empty
10      \in@false
11    \else
12      \in@true
13    \fi
14  }
15 \newif\ifin@

```

Before the `\begin{document}` command several *math versions* and *math alphabet identifiers* may be declared. In principle, there should be exactly one family/series/shape combination be declared for each version/alphabet pair. But we want to allow for defaults as well for automagical filling of holes.

While building the tables for math alphabet identifiers and math versions we keep several lists:

- the list of all math versions, `\version@list`, each entry prefixed by the control sequence `\version@elt`, i.e. this list has the following form

```

\version@elt<version1>\version@elt<version2>...
\version@elt<versionn>

```

- the list of all math alphabet identifiers. Here every entry has the form:

```

\group@elt<math group number>
{\{<default family>\}{<default series>\}{<default shape>\}}.

```

- Each defined math alphabet identifier holds a list containing Information about the *versions* for which it is defined. This list has a more complicated structure: it looks as follows:

```

\set@alpha<the alphabet identifier itself>
\reserved@c<math version><font info>
...
\@nil

```

where  $\langle font\ info \rangle$  is either  $\backslash reserved@e$  (if the combination is not defined yet) or

```

{\langle family \rangle}{\langle series \rangle}{\langle shape \rangle}

```

$\backslash version@list$  We initialize the version list to be empty.

```

16 \let\version@list=\@empty
17 \@onlypreamble\version@list

```

$\backslash version@elt$

```

18 \let\version@elt\relax
19 \@onlypreamble\version@elt

```

$\backslash new@mathversion$  The macro  $\backslash new@mathversion$  is called with the version control sequence as its argument.

```

20 %\def\new@mathversion#1{%

```

The first thing this macro does is to check if the version identifier is already present in  $\backslash version@list$ . We enclose  $\backslash version@list$  in braces since it might be empty (if no *version* is defined yet). But this means that we need a suitable number of  $\backslash expandafter$  primitives.

```

21 % \expandafter\in@\expandafter#1\expandafter{\version@list}%
22 % \ifin@

```

If so it prints an error message. The  $\backslash next$  macro is used to get rid of the four characters  $\backslash mv@$  that would otherwise appear at the begin of the version name in the error message.

```

23 % \latexerror{Math version
24 % \expandafter\@gobblefour\string#1'
25 % already defined}\@eha

```

Otherwise we have a new version, and we can proceed with entering it into the tables. We add it to  $\backslash version@list$ . This is very easy: we define  $\backslash version@elt$  (which is the delimiter in  $\backslash version@list$ ) to protect itself and the following token from being expanded and simply redefine  $\backslash version@list$ .

```

26 % \else
27 % \global\expandafter\newcount\csname c@\expandafter
28 % \gobble\string#1\endcsname
29 % \global\csname c@\expandafter
30 % \gobble\string#1\endcsname\@ne
31 % \def\version@elt{\noexpand\version@elt\noexpand}%
32 % \edef\version@list{\version@list\version@elt#1}%

```

Then we prepare to enter the new version into all math alphabet identifier lists. Remember that these lists use `\reserved@c` as delimiter, and that there appears the control sequence `\reserved@e` that must not be expanded. Therefore we take suitable precautions.

```
33 %      \def\reserved@c{\noexpand\reserved@c\noexpand}%
34 %      \let\reserved@e\relax
```

We will now go through the `\alpha@list` to process every  $\langle\textit{math alphabet identifier}\rangle$  in turn. Since this list has `\group@elt` as a delimiter we define this control sequence. It has three arguments as every entry consists of three items (as explained above).

```
35 %      \def\group@elt##1##2##3{%
```

The first of these arguments is the  $\langle\textit{math alphabet identifier}\rangle$ . We redefine it by appending the information about the new version at the end of the list contained in it. However, there is one subtlety: the definitions for `\reserved@c` and `\reserved@e` made above prevent the main part of the list from being expanded. But we still have to take care of the header and the trailer. To do this we remove the trailer by means of the macro `\remove@nil` which also protect the header from being expanded. Its definition is given below. Now we can prepare to add the new version.

```
36 %          \edef##1{\expandafter\remove@nil##1%
37 %              \reserved@c
38 %              #1%
39 %              \reserved@e
40 %              \noexpand\@nil}}%
```

Finally we call `\alpha@list` which will now execute the macro `\group@elt` once for every defined  $\langle\textit{math alphabet identifier}\rangle$ . And that's all for now.

```
41 %      \alpha@list
42 %      \fi}
```

`\alpha@list` As we explained above every entry in `\alpha@list` has the form  
`\alpha@elt`  
 $\langle\textit{alphabet identifier}\rangle\langle\textit{internal group number}\rangle\langle\textit{default font assignments}\rangle\dots$

We initialize it to `\@empty`.

```
43 \let\alpha@list\@empty
44 \@onlypreamble\alpha@list
```

`\alpha@elt`

```
45 \let\alpha@elt\relax
46 \@onlypreamble\alpha@elt
```

`\newgroup` Start the group (fam) allocation at 0. (Doesn't belong here.)

```
47 \count18=-1
```

`\stepcounter`

`\select@group` We surround `\select@group` with braces so that functions using it can be used directly after `_` or `^`. However, if we use oldstyle syntax where the math alphabet doesn't have arguments (ie if `\math@bgroup` is not `\bgroup`) we need to get rid of the extra group.

```

48 </2ekernel>
49 <latexrelease>\IncludeInRelease{2015/01/01}
50 <latexrelease>          {\select@group}{\select@group}%
51 <*2ekernel | latexrelease>
52 \def\select@group#1#2#3#4{%
53   \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
54   {%
55     \ifmmode
56       \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
57         \begingroup
58         \escapechar\m@ne
59         \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
60         \globaldefs\@ne \math@fonts
61       \endgroup
62       \init@restore@version
63       \xdef#1{\noexpand\use@mathgroup\noexpand#2%
64         {\number\csname c@mv@\math@version\endcsname}}%
65       \global\advance\csname c@mv@\math@version\endcsname\@ne
66     \else
67       \let#1\relax
68       \@latex@error{Too many math alphabets used in
69         version \math@version}%
70       \@eha
71     \fi
72   \else \expandafter\non@alpherr\fi
73   #1{#4}%
74   }%
75 }
76 </2ekernel | latexrelease>
77 <latexrelease>\EndIncludeInRelease
78 <latexrelease>\IncludeInRelease{0000/00/00}
79 <latexrelease>          {\select@group}{\select@group}%
80 <latexrelease>\def\select@group#1#2#3#4{%
81 <latexrelease> \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
82 <latexrelease> {%
83 <latexrelease> \ifmmode
84 <latexrelease>   \ifnum\csname c@mv@\math@version\endcsname<\sixt@@n
85 <latexrelease>     \begingroup
86 <latexrelease>     \escapechar\m@ne
87 <latexrelease>     \getanddefine@fonts
88 <latexrelease>       {\csname c@mv@\math@version\endcsname}#3%
89 <latexrelease>     \globaldefs\@ne \math@fonts
90 <latexrelease>   \endgroup
91 <latexrelease>   \init@restore@version
92 <latexrelease>   \xdef#1{\noexpand\use@mathgroup\noexpand#2%
93 <latexrelease>     {\number\csname c@mv@\math@version\endcsname}}%
94 <latexrelease>   \global\advance\csname c@mv@\math@version\endcsname\@ne
95 <latexrelease>   \else
96 <latexrelease>     \let#1\relax
97 <latexrelease>     \@latex@error{Too many math alphabets used in
98 <latexrelease>       version \math@version}%
99 <latexrelease>     \@eha
100 <latexrelease>   \fi
101 <latexrelease> \else \expandafter\non@alpherr\fi

```



```

102 <latexrelease> #1{#4}%
103 <latexrelease> }%
104 <latexrelease>}
105 <latexrelease>\EndIncludeInRelease
106 <*2ekernel>

107 \@onlypreamble\restore@mathversion

\init@restore@version
108 \def\init@restore@version{%
109     \global\let\init@restore@version\relax
110     \xdef\restore@mathversion
111         {\expandafter\noexpand\csname mv@\math@version\endcsname
112         \global\csname c@mv@\math@version\endcsname
113         \number\csname c@mv@\math@version\endcsname\relax}%
114     \aftergroup\dorestore@version
115 }
116 \@onlypreamble\init@restore@version

\non@alpherr
117 \gdef\non@alpherr#1{\@latex@error{%
The command here will have a space at the end of its name, so we make sure not
to insert an extra one.
118     \string#1allowed only in math mode}\@ehd}

\dorestore@version
119 \def\dorestore@version
120 {\ifmmode
121     \aftergroup\dorestore@version
122 \else
123     \gdef\init@restore@version{%
124         \global\let\init@restore@version\relax
125         \xdef\restore@mathversion
126             {\expandafter\noexpand\csname mv@\math@version\endcsname
127             \global\csname c@mv@\math@version\endcsname
128             \number\csname c@mv@\math@version\endcsname\relax}%
129         \aftergroup\dorestore@version
130     }%
131     \begingroup
132         \let\getanddefine@fonts\@gobbletwo
133         \restore@mathversion
134     \endgroup
135     \fi}%
136 \@onlypreamble\dorestore@version

\document@select@group We surround \select@group with braces so that functions using it can be used
directly after _ or ^.
137 </2ekernel>
138 <latexrelease>\IncludeInRelease{2015/01/01}
139 <latexrelease> {\document@select@group}{\document@select@group}%
140 <*2ekernel | latexrelease>
141 \def\document@select@group#1#2#3#4{%
142     \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi

```

```

143 {%
144 \ifmmode
145 \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
146 \begingroup
147 \escapechar\m@ne
148 \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
149 \globaldefs\@ne \math@fonts
150 \endgroup
151 \expandafter\extract@alph@from@version
152 \csname mv@\math@version\expandafter\endcsname
153 \expandafter{\number\csname
154 c@mv@\math@version\endcsname}%
155 #1%
156 \global\advance\csname c@mv@\math@version\endcsname\@ne
157 \else
158 \let#1\relax
159 \@latex@error{Too many math alphabets used
160 in version \math@version}%
161 \@eha
162 \fi
163 \else \expandafter\non@alpherr\fi
164 #1{#4}%
165 }%
166 }
167 </2ekernel | latexrelease>
168 <latexrelease>\EndIncludeInRelease
169 <latexrelease>\IncludeInRelease{0000/00/00}
170 <latexrelease> {\document@select@group}{\document@select@group}%
171 <latexrelease>\def\document@select@group#1#2#3#4{%
172 <latexrelease> \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
173 <latexrelease> {%
174 <latexrelease> \ifmmode
175 <latexrelease> \ifnum\csname c@mv@\math@version\endcsname<\sist@n
176 <latexrelease> \begingroup
177 <latexrelease> \escapechar\m@ne
178 <latexrelease> \getanddefine@fonts
179 <latexrelease> {\csname c@mv@\math@version\endcsname}#3%
180 <latexrelease> \globaldefs\@ne \math@fonts
181 <latexrelease> \endgroup
182 <latexrelease> \expandafter\extract@alph@from@version
183 <latexrelease> \csname mv@\math@version\expandafter\endcsname
184 <latexrelease> \expandafter{\number\csname
185 <latexrelease> c@mv@\math@version\endcsname}%
186 <latexrelease> #1%
187 <latexrelease> \global\advance\csname c@mv@\math@version\endcsname\@ne
188 <latexrelease> \else
189 <latexrelease> \let#1\relax
190 <latexrelease> \@latex@error{Too many math alphabets used
191 <latexrelease> in version \math@version}%
192 <latexrelease> \@eha
193 <latexrelease> \fi
194 <latexrelease> \else \expandafter\non@alpherr\fi
195 <latexrelease> #1{#4}%
196 <latexrelease> }%

```

```

197 \latexrelease}
198 \latexrelease\EndIncludeInRelease
199 \*2ekernel)

```

`\process@table`

```

200 \def\process@table{%
201   \def\cdp@elt##1##2##3##4{%
202     \@font@info{Checking defaults for
203       ##1/##2/##3/##4}%
204     \expandafter
205     \ifx\csname##1/##2/##3/##4\endcsname\relax

```

Grouping is important for two reasons, first `\cdp@elt` will get redefined if `\Declare...` functions are executed within the external `.fd` file and secondly `\try@load@fontshape` changes a lot of catcodes without surrounding itself with a group.

```

206     \begingroup
207     \def\fontencoding{##1}\def\fontfamily{##2}%
208     \try@load@fontshape
209     \endgroup
210     \fi
211     \expandafter
212     \ifx\csname##1/##2/##3/##4\endcsname\relax
213       \@latex@error{This NFSS system isn't set up properly}%
214       {For encoding scheme ##1 the defaults
215         ##2/##3/##4 do not form a valid font shape}%
216     \else
217       \@font@info{... okay}%
218     \fi}%
219   \cdp@list

```

Now we make sure that `\error@fontshape` is okay.

```

220   \begingroup
221   \escapechar\m@ne
222   \error@fontshape
223   \expandafter\ifx\csname \curr@fontshape\endcsname\relax
224     \begingroup
225     \try@load@fontshape
226     \endgroup
227   \fi
228   \expandafter\ifx\csname \curr@fontshape\endcsname\relax
229     \@latex@error{This NFSS system isn't set up properly}%
230     {The system maintainer forgot to specify a suitable
231       substitution
232       font shape using the \noexpand\DeclareErrorFont
233       command}%
234   \fi
235   \endgroup

```

Set `\select@group` to its meaning used within the document body.

```

236   \let\select@group\document@select@group

```

Install the default font attributes they are currently pointing to error font shape. Don't use `\reset@font` since that would trigger `\selectfont`.

```

237   \fontencoding{\encodingdefault}%

```

```

238 \fontfamily{\familydefault}%
239 \fontseries{\seriesdefault}%
240 \fontshape{\shapedefault}%
kill all macros not longer needed. we need to add many more!!!!
241 \everyjob{}%
242 }
243 \@onlypreamble\process@table

244 %\@onlypreamble\set@mathradical

```

\DeclareMathVersion

```

245 \def\DeclareMathVersion#1{%
246 \expandafter\new@mathversion\csname mv@#1\endcsname}
247 \@onlypreamble\DeclareMathVersion

```

\new@mathversion

```

248 \def\new@mathversion#1{%
249 \expandafter\in@\expandafter#1\expandafter{\version@list}%
250 \ifin@
251 \font@info{Redefining math version
252 \expandafter\@gobblefour\string#1'}%
253 \else
254 \expandafter\newcount\csname c@\expandafter
255 \expandafter\@gobble\string#1\endcsname
256 \def\version@elt{\noexpand\version@elt\noexpand}%
257 \edef\version@list{\version@list\version@elt#1}%
258 \fi

```

\toks@ is used to gather all tokens for the math version. \count@ will be used to count the math groups we add to this version.

```

259 \toks@{}%
260 \count@\z@

```

Now we loop over \group@list to add all math groups defined so far to the version and at the same time to count them.

```

261 \def\group@elt##1##2{%
262 \advance\count@\@ne
263 \addto@hook\toks@{\getanddefine@fonts##1##2}%
264 }%
265 \group@list

```

We set the counter for this math version to the number of math groups found in \group@list.

```

266 \global\csname c@\expandafter\@gobble\string#1\endcsname\count@

```

Now we loop over \alpha@list to add all math alphabets known so far. We have to distinguish the case that an alphabet by default should produce an error in new versions.

```

267 \def\alpha@elt##1##2##3{%
268 \ifx##2\no@alphabet@error
269 \toks@\expandafter{\the\toks@\install@mathalphabet##1%
270 {\no@alphabet@error##1}}%
271 \else
272 \toks@\expandafter{\the\toks@\install@mathalphabet##1%
273 {\select@group##1##2##3}}%

```

```

274     \fi
275   }%
276   \alpha@list

```

Finally we define the math version to expand to the contents of `\toks@`.

```

277   \xdef#1{\the\toks@}%
278 }
279 \@onlypreamble\new@mathversion

```

`\DeclareSymbolFont`

```

280 \def\DeclareSymbolFont#1#2#3#4#5{%
281   \@tempswafalse
282   \edef\reserved@b{#2}%
283   \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
284     \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
285   \cdp@list
286   \if@tempswa
287     \ifundefined{sym#1}{%
288       \ifnum\count18<15 %
289         \expandafter\new@mathgroup\csname sym#1\endcsname
290         \expandafter\new@symbolfont\csname sym#1\endcsname
291           {#2}{#3}{#4}{#5}%
292       \else
293         \@latex@error{Too many symbol fonts declared}\@eha
294       \fi
295     }%
296     {%
297       \@font@info{Redeclaring symbol font ‘#1’}%

```

Update the group list.

```

298   \def\group@elt##1##2{%
299     \noexpand\group@elt\noexpand##1%
300     \expandafter\ifx\csname sym#1\endcsname##1%
301       \expandafter\noexpand\csname#2/#3/#4/#5\endcsname
302     \else
303       \noexpand##2%
304     \fi}%
305   \xdef\group@list{\group@list}%

```

Update the version list.

```

306   \def\version@elt##1{%
307     \expandafter
308     \SetSymbolFont@expandafter##1\csname#2/#3/#4/#5\endcsname
309     \endcsname \csname sym#1\endcsname
310   }%
311   \version@list
312 }%
313 \else
314   \@latex@error{Encoding scheme ‘#2’ unknown}\@eha
315 \fi
316 }
317 \@onlypreamble\DeclareSymbolFont

```

`\group@list`

```

318 \let\group@list\@empty
319 \@onlypreamble\group@list

\group@elt
320 \let\group@elt\relax
321 \@onlypreamble\group@elt

\new@symbolfont
322 \def\new@symbolfont#1#2#3#4#5{%
323   \toks@\expandafter{\group@list}%
324   \edef\group@list{\the\toks@\noexpand\group@elt\noexpand#1%
325     \expandafter\noexpand\csname#2/#3/#4/#5\endcsname}%
326   \def\version@elt##1{\toks@\expandafter{##1}%
327     \edef##1{\the\toks@\noexpand\getanddefine@fonts
328       #1\expandafter\noexpand\csname#2/#3/#4/#5\endcsname}%
329     \global\advance\csname c@\expandafter
330       \@gobble\string##1\endcsname\@ne
331   }%
332   \version@list
333 }
334 \@onlypreamble\new@symbolfont

\SetSymbolFont
335 \def\SetSymbolFont#1#2#3#4#5#6{%
336   \@tempswafalse
337   \edef\reserved@b{#3}%
338   \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
339     \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
340   \cdp@list
341   \if@tempswa
342     \expandafter\SetSymbolFont@
343     \csname mv@#2\expandafter\endcsname\csname#3/#4/#5/#6\expandafter
344     \endcsname \csname sym#1\endcsname
345   \else
346     \@latex@error{Encoding scheme ‘#3’ unknown}\@eha
347   \fi
348 }
349 \@onlypreamble\SetSymbolFont

\SetSymbolFont@
350 \def\SetSymbolFont@#1#2#3{%
351   \expandafter\in@\expandafter#1\expandafter{\version@list}%
352   \ifin@
353     \expandafter\in@\expandafter#3\expandafter{\group@list}%
354     \ifin@
355       \begingroup
356       \expandafter\get@cdp\string#2\@nil\reserved@a
357       \toks@{}%
358       \def\install@mathalphabet##1##2{%
359         \addto@hook\toks@{\install@mathalphabet##1{##2}}%
360       }%
361       \def\getanddefine@fonts##1##2{%
362         \ifnum##1=#3%
363           \addto@hook\toks@{\getanddefine@fonts#3#2}%

```

```

364         \expandafter\get@cdp\string##2\@nil\reserved@b
365         \ifx\reserved@a\reserved@b\else
366             \@font@info{Encoding '\reserved@b' has changed
367                 to '\reserved@a' for symbol font\MessageBreak
368                 '\expandafter\@gobblefour\string#3' in the
369                 math version '\expandafter
370                 \@gobblefour\string#1'}}%
371         \fi
372         \@font@info{%
373             Overwriting symbol font
374             '\expandafter\@gobblefour\string#3' in
375             version '\expandafter
376             \@gobblefour\string#1'\MessageBreak
377             \@spaces \expandafter\@gobble\string##2 -->
378                 \expandafter\@gobble\string#2}%
379         \else
380             \addto@hook\toks@{\getanddefine@fonts##1##2}%
381             \fi}%
382         #1%
383         \xdef#1{\the\toks@}%
384     \endgroup
385 \else
386     \@latex@error{Symbol font '\expandafter\@gobblefour\string#3'
387         not defined}\@eha
388 \fi
389 \else
390     \@latex@error{Math version '\expandafter\@gobblefour\string#1'
391         is not
392         defined}{You probably misspelled the name of the math
393         version.^^JOr you have to specify an additional package.}%
394 \fi
395 }
396 \@onlypreamble\SetSymbolFont@

```

\get@cdp

```

397 \def\get@cdp#1#2/#3\@nil#4{\def#4{#2}}
398 \@onlypreamble\get@cdp

```

\DeclareMathAlphabet

```

399 \def\DeclareMathAlphabet#1#2#3#4#5{%
400     \@tempswafalse
401     \edef\reserved@b{#2}%
402     \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
403         \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
404     \cdp@list
405     \if@tempswa
406         \expandafter\ifx
407             \csname\expandafter\@gobble\string#1\endcsname
408             \relax
409             \new@mathalphabet#1{#2}{#3}{#4}{#5}%
410         \else
411             Check if it is already a math alphabet.
412             \edef\reserved@a{\noexpand\in@\string\select@group}%

```

```

412         {\expandafter\meaning\csname \expandafter
413         \@gobble\string#1\space\endcsname}}}%
414     \reserved@a
415     \ifin@
416         \@font@info{Redeclaring math alphabet \string#1}%
417         \def\version@elt##1{%
418             \expandafter\SetMathAlphabet@\expandafter
419             ##1\csname#2/#3/#4/#5\expandafter\endcsname

420             \csname M@#2\expandafter\endcsname
421             \csname \expandafter\@gobble\string#1\space\endcsname#1}%
422         \version@list
423     \else

```

Check if it is a math alphabet defined via `\DeclareSymbolFontAlphabet`.

```

424     \edef\reserved@a{\noexpand\in@{\string\use@mathgroup}%
425     {\expandafter\meaning\csname \expandafter
426     \@gobble\string#1\space\endcsname}}}%
427     \reserved@a
428     \ifin@

```

In that case overwriting is simple since there is nothing inserted in the math version macros.

```

429         \@font@info{Redeclaring math alphabet \string#1}%
430         \new@mathalphabet#1{#2}{#3}{#4}{#5}%

```

Otherwise panic.

```

431     \else
432         \@latex@error{Command ‘\string#1’ already defined}\@eha
433     \fi
434     \fi
435     \fi
436     \else
437         \@latex@error{Encoding scheme ‘#2’ unknown}\@eha
438     \fi
439     }
440 \onlypreamble\DeclareMathAlphabet

```

`\new@mathalphabet`

```

441 \def\new@mathalphabet#1#2#3#4#5{%
442     \toks@{\expandafter{\alpha@list}}%
443     \edef#1{\expandafter\noexpand\csname \expandafter
444         \@gobble\string#1\space\endcsname
445         \if/#5/%
446             \noexpand\no@alphabet@error
447             \noexpand\no@alphabet@error
448         \else
449             \expandafter\noexpand\csname M@#2\endcsname
450             \expandafter\noexpand\csname#2/#3/#4/#5\endcsname
451         \fi
452     }%
453     \toks2\expandafter{#1}%
454     \edef\alpha@list{\the\toks@\noexpand\alpha@elt\the\toks2}%
455     \def\version@elt##1{\toks@\expandafter{##1}%
456         \edef##1{\the\toks@\install@mathalphabet

```



```

457 \expandafter\noexpand
458 \csname \expandafter\@gobble
459 \string#1\space\endcsname
460 {\if/#5/%
461 \noexpand\no@alphabet@error
462 \noexpand#1%
463 \else
464 \noexpand\select@group\the\toks2
465 \fi}}%
466 }%
467 \version@list
468 \expandafter\edef\csname \expandafter\@gobble
469 \string#1\space\endcsname{\if/#5/%
470 \noexpand\no@alphabet@error
471 \noexpand#1%
472 \else
473 \noexpand\select@group\the\toks2
474 \fi}%
475 \edef#1{\noexpand\protect
476 \expandafter\noexpand\csname \expandafter
477 \@gobble\string#1\space\endcsname}%
478 }
479 \@onlypreamble\new@mathalphabet

```

\SetMathAlphabet

```

480 \def\SetMathAlphabet#1#2#3#4#5#6{%
481 \tempwafalse
482 \edef\reserved@b{#3}%
483 \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
484 \ifx\reserved@b\reserved@c \tempwattrue\fi}%
485 \cdp@list
486 \if@tempswa
487 \expandafter\SetMathAlphabet@
488 \csname mv@#2\expandafter\endcsname\csname#3/#4/#5/#6\expandafter
489 \endcsname \csname M@#3\expandafter\endcsname
490 \csname \expandafter\@gobble\string#1\space\endcsname#1%
491 \else
492 \@latex@error{Encoding scheme ‘#3’ unknown}\@eha
493 \fi
494 }
495 \@onlypreamble\SetMathAlphabet

```

\SetMathAlphabet@

```

496 \def\SetMathAlphabet@#1#2#3#4#5{%
497 \expandafter\in@\expandafter#1\expandafter{\version@list}%
498 \ifin@
499 \expandafter\in@\expandafter#4\expandafter{\alpha@list}%
500 \ifin@
501 \begin@group
502 \toks@{}%
503 \def\getanddefine@fonts##1##2{%
504 \addto@hook\toks@{\getanddefine@fonts##1##2}%
505 }%
506 \def\reserved@c##1##2##3##4{% % for message below

```

```

507         \expandafter\@gobble\string##4}%
508 \def\install@mathalphabet##1##2{%
509     \ifx##1#4%
510         \addto@hook\toks@
511             {\install@mathalphabet#4{\select@group#4#3#2}}}%
512         \@font@info{Overwriting math alphabet
513             '\string#5' in version '\expandafter
514             \@gobblefour\string#1'\MessageBreak
515             \@spaces \reserved@c##2 -->
516                 \expandafter\@gobble\string#2}%
517     \else
518         \addto@hook\toks@{\install@mathalphabet##1{##2}}}%
519     \fi
520 }%
521 #1%
522 \xdef#1{\the\toks@}%
523 \endgroup
524 \else

```

If the math alphabet was defined via `\DeclareSymbolFontAlphabet` we have remove its external definition and add it as a normal math alphabet to every version before trying to change it in one version.

```

525     \edef\reserved@a{%
526         \noexpand\in@{\string\use@mathgroup}{\meaning#4}}%
527     \reserved@a
528     \ifin@
529         \def\reserved@b##1\use@mathgroup##2##3{%
530             \def\reserved@b{##3}\def\reserved@c{##2}}%
531         \expandafter\reserved@b#4%
532         \begingroup
533             \def\install@mathalphabet##1##2{%
534                 \addto@hook\toks@{\install@mathalphabet##1{##2}}}%
535             }%
536         \def\getanddefine@fonts##1##2{%
537             \addto@hook\toks@{\getanddefine@fonts##1##2}%
538             \ifnum##1=\reserved@b
539                 \expandafter
540                 \addto@hook\expandafter\toks@
541                 \expandafter{\expandafter\install@mathalphabet
542                 \expandafter#4\expandafter
543                     {\expandafter\select@group\expandafter
544                     #4\reserved@c##2}}}%
545             \fi
546         }%
547         \def\version@elt##1{%
548             \toks@{}%
549             ##1%
550             \xdef##1{\the\toks@}%
551         }%
552         \version@list
553     \endgroup

```

Put it into the `\alpha@list` with default ‘error’

```

554     \expandafter\gdef\expandafter\alpha@list\expandafter
555         {\alpha@list

```

```

556         \alpha@elt #4\no@alphabet@error \no@alphabet@error}%
557         \gdef#4{\no@alphabet@error #5}% fake things :-)
Then call the internal setting routine again:
558         \SetMathAlphabet@{#1}{#2}{#3}#4#5%
559     \else
560         \@latex@error{Command '\string#5' not defined as a
561             math alphabet}%
562         {Use \noexpand\DeclareMathAlphabet to define it.}%
563     \fi
564 \fi
565 \else
566     \@latex@error{Math version '\expandafter\@gobblefour\string#1'
567         is not
568         defined}{You probably misspelled the name of the math
569         version.^^JOr you have to specify an additional package.}%
570 \fi
571 }
572 \@onlypreamble\SetMathAlphabet@

```

```

\DeclareMathAccent Could do with more checks like allowing single number in #4 lowercase in #4 etc
573 </2ekernel>
574 <*2ekernel | latexrelease>
575 <latexrelease>\IncludeInRelease{2019/10/01}%
576 <latexrelease>           {DeclareMathAccent}{Make math accents robust}%
577 \def\DeclareMathAccent#1#2#3#4{%
578     \expandafter\in@\csname sym#3\expandafter\endcsname
579     \expandafter{\group@list}%
580     \ifin@
581         \begingroup
582         \count\z@=#4\relax
583         \count\tw@\count\z@
584         \divide\count\z@\sixt@@n
585         \count@\count\z@
586         \multiply\count@\sixt@@n
587         \advance\count\tw@-\count@
588         \if\relax\noexpand#1% is command?
589             \edef\reserved@a{\noexpand\in@
590                 {\expandafter\@gobble\string\mathaccent}
591                 {\expandafter\meaning
592                 \csname\expandafter\@gobble\string#1\space\endcsname}}%
593             \reserved@a
594         \ifin@
595             \expandafter\let
596             \csname\expandafter\@gobble\string#1\space\endcsname
597             \@undefined
598             \expandafter\set@mathaccent
599             \csname sym#3\endcsname#1#2%
600             {\hexnumber@\count\z@}\hexnumber@\count\tw@}%
601             \@font@info{Redeclaring math accent \string#1}%
602         \else
603             \expandafter\ifx
604             \csname\expandafter\@gobble\string#1\endcsname
605             \relax

```

```

606         \expandafter\set@mathaccent
607         \csname sym#3\endcsname#1#2%
608         {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
609     \else
610         \@latex@error{Command '\string#1' already defined}\@eha
611     \fi
612 \fi
613 \else
614     \@latex@error{Not a command name: '\noexpand#1'}\@eha
615 \fi
616 \endgroup
617 \else
618     \@latex@error{Symbol font '#3' is not defined}\@eha
619 \fi
620 }
621 /2kernel | latexrelease)
622 (latexrelease)\EndIncludeInRelease
623 (latexrelease)\IncludeInRelease{0000/00/00}%
624 (latexrelease)      {DeclareMathAccent}{Make math accents robust}%
625 (latexrelease)\def\DeclareMathAccent#1#2#3#4{%
626 (latexrelease)  \expandafter\in@ \csname sym#3\endcsname
627 (latexrelease)  \expandafter{\group@list}%
628 (latexrelease)  \ifin@
629 (latexrelease)  \begingroup
630 (latexrelease)  \count\z@=#4\relax
631 (latexrelease)  \count\tw@ \count\z@
632 (latexrelease)  \divide\count\z@\sist@@n
633 (latexrelease)  \count@ \count\z@
634 (latexrelease)  \multiply\count@\sist@@n
635 (latexrelease)  \advance\count\tw@-\count@
636 (latexrelease)  \if\relax\noexpand#1% is command?
637 (latexrelease)  \edef\reserved@a{\noexpand\in@
638 (latexrelease)  {\expandafter\@gobble\string\mathaccent}{\meaning#1}}%
639 (latexrelease)  \reserved@a
640 (latexrelease)  \ifin@
641 (latexrelease)  \expandafter\set@mathaccent
642 (latexrelease)  \csname sym#3\endcsname#1#2%
643 (latexrelease)  {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
644 (latexrelease)  \@font@info{Redeclaring math accent \string#1}%
645 (latexrelease)  \else
646 (latexrelease)  \expandafter\ifx
647 (latexrelease)  \csname\expandafter\@gobble\string#1\endcsname
648 (latexrelease)  \relax
649 (latexrelease)  \expandafter\set@mathaccent
650 (latexrelease)  \csname sym#3\endcsname#1#2%
651 (latexrelease)  {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
652 (latexrelease)  \else
653 (latexrelease)  \@latex@error{Command '\string#1' already defined}\@eha
654 (latexrelease)  \fi
655 (latexrelease)  \fi
656 (latexrelease)  \else
657 (latexrelease)  \@latex@error{Not a command name: '\noexpand#1'}\@eha
658 (latexrelease)  \fi
659 (latexrelease)  \endgroup

```

```

660 \latexrelease \else
661 \latexrelease \@latexerror{Symbol font '#3' is not defined}\@eha
662 \latexrelease \fi
663 \latexrelease}
664 \latexrelease\EndIncludeInRelease
665 (*2ekernel)

666 \@onlypreamble\DeclareMathAccent

\set@mathaccent
667 (/2ekernel)
668 (*2ekernel | latexrelease)
669 \latexrelease\IncludeInRelease{2019/10/01}%
670 \latexrelease {\set@mathaccent}{makemath accents robust}%
671 \def\set@mathaccent#1#2#3#4{%
672 \xdef#2{\mathaccent"\mathchar@type#3\hexnumber@#1#4\relax}%
673 \MakeRobust#2%
674 }
675 \@onlypreamble\set@mathaccent
676 (/2ekernel | latexrelease)
677 \latexrelease\EndIncludeInRelease
678 \latexrelease\IncludeInRelease{0000/00/00}%
679 \latexrelease {\set@mathaccent}{makemath accents robust}%
680 \latexrelease
681 \latexrelease\def\set@mathaccent#1#2#3#4{%
682 \latexrelease \xdef#2{\mathaccent"\mathchar@type#3\hexnumber@#1#4\relax}}
683 \latexrelease
684 \latexrelease\EndIncludeInRelease
685 (*2ekernel)

\DeclareMathSymbol
686 \def\DeclareMathSymbol#1#2#3#4{%
687 \expandafter\in@\csname sym#3\expandafter\endcsname
688 \expandafter{\group@list}%
689 \ifin@
690 \begingroup
691 \count\z@=#4\relax
692 \count\tw@\count\z@
693 \divide\count\z@\sist@@n
694 \count@\count\z@
695 \multiply\count@\sist@@n
696 \advance\count\tw@-\count@
697 \if\relax\noexpand#1% is command?

Store the command name with a space attached inside \reserved@@b in case we
look at a robust definition.
698 \edef\reserved@b{\expandafter\noexpand
699 \csname\expandafter\@gobble\string#1\space\endcsname}%

Test both #1 and #1_ for containing mathchar.
700 \edef\reserved@a
701 {\noexpand\in@\expandafter\@gobble\string\mathchar}%
702 {\meaning#1\expandafter\meaning\reserved@b}}%
703 \reserved@a

```

Drop #1<sub>␣</sub> in case it was defined before.

```

704     \global\expandafter\let\reserved@b\@undefined
705     \ifin@
706         \expandafter\set@mathsymbol
707             \csname sym#3\endcsname#1#2%
708             {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
709             \@font@info{Redeclaring math symbol \string#1}%
710     \else
711         \expandafter\ifx
712             \csname\expandafter\@gobble\string#1\endcsname
713             \relax
714             \expandafter\set@mathsymbol
715                 \csname sym#3\endcsname#1#2%
716                 {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
717         \else
718             \@latex@error{Command ‘\string#1’ already defined}\@eha
719         \fi
720     \fi
721 \else
722     \expandafter\set@mathchar
723         \csname sym#3\endcsname#1#2
724         {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
725     \fi
726 \endgroup
727 \else
728     \@latex@error{Symbol font ‘#3’ is not defined}\@eha
729 \fi
730 }
731 \@onlypreamble\DeclareMathSymbol

```

\set@mathchar

```

732 \def\set@mathchar#1#2#3#4{%
733     \global\mathcode‘#2="\mathchar@type#3\hexnumber@#1#4\relax}
734 \@onlypreamble\set@mathchar

```

\set@mathsymbol

```

735 \def\set@mathsymbol#1#2#3#4{%
736     \global\mathchardef#2"\mathchar@type#3\hexnumber@#1#4\relax}
737 \@onlypreamble\set@mathsymbol

738 %\def\mathsymbol#1#2#3{%
739 %    \@tempcnta=#3\relax
740 %    \@tempcntb\@tempcnta
741 %    \divide\@tempcnta\sixt@@n
742 %    \count@\@tempcnta
743 %    \multiply\count@\sixt@@n
744 %    \advance\@tempcntb-\count@
745 %    \mathchar"\mathchar@type#1\hexnumber@#2%
746 %        \hexnumber@\@tempcnta\hexnumber@\@tempcntb\relax}
747 %
748 %\def\DeclareMathAlphabetCharacter#1#2#3{%
749 %    \DeclareMathSymbol{#1}7{#2}{#3}

```

\DeclareMathDelimiter

```

750 \def\DeclareMathDelimiter#1{%
751   \if\relax\noexpand#1%
752     \expandafter\@DeclareMathDelimiter
753   \else
754     \expandafter\@xxDeclareMathDelimiter
755   \fi
756   #1}
757 \onlypreamble\DeclareMathDelimiter

```

`\@xxDeclareMathDelimiter` This macro checks if the second arg is a “math type” such as `\mathopen`. The undocumented original code didn’t use math types when the delimiter was a single letter. For this reason the coding is a bit strange as it tries to support the undocumented syntax for compatibility reasons.

```

758 \def\@xxDeclareMathDelimiter#1#2#3#4{%

```

7 is the default value returned in the case that `\mathchar@type` is passed something unexpected, like a math symbol font name. We locally move `\mathalpha` out of the way so if you use that the right branch is taken. This will still fail if an explicit number 7 is used!

```

759   \begingroup
760   \let\mathalpha\mathord
761   \ifnum7=\mathchar@type{#2}%
762   \endgroup

```

If this branch is taken we have old syntax (5 arguments).

```

763     \expandafter\@firstofone
764   \else

```

If this branch is taken `\mathchar@type` is different from 7 so we assume new syntax. In this case we also use the arguments to set up the letter as a math symbol for the case where it is not used as a delimiter.

```

765     \endgroup
766     \DeclareMathSymbol#1{#2}{#3}{#4}%

```

Then we arrange that `\@xDeclareMathDelimiter` only gets #1, #3, #4 ... as it does not expect a math type as argument.

```

767     \expandafter\@firstoftwo
768   \fi
769   {\@xDeclareMathDelimiter#1}{#2}{#3}{#4}}
770 \onlypreamble\@xxDeclareMathDelimiter

```

`\@DeclareMathDelimiter`

```

771 \if2kernel)
772 (*2kernel | latexrelease)
773 (latexrelease)\IncludeInRelease{2019/10/01}%
774 (latexrelease)      {\@DeclareMathDelimiter}{Make math delimiters robust}%
775 \def\@DeclareMathDelimiter#1#2#3#4#5#6{%
776   \expandafter\in@\csname sym#3\expandafter\endcsname
777   \expandafter{\group@list}%
778   \ifin@
779     \expandafter\in@\csname sym#5\expandafter\endcsname
780     \expandafter{\group@list}%
781   \ifin@
782     \begingroup
783     \count\z@=#4\relax

```

```

784      \count\tw@\count\z@
785      \divide\count\z@\sist@n
786      \count@\count\z@
787      \multiply\count@\sist@n
788      \advance\count\tw@-\count@
789      \edef\reserved@c{\hexnumber@\count\z@}\hexnumber@\count\tw@}%
790      %
791      \count\z@=#6\relax
792      \count\tw@\count\z@
793      \divide\count\z@\sist@n
794      \count@\count\z@
795      \multiply\count@\sist@n
796      \advance\count\tw@-\count@
797      \edef\reserved@d{\hexnumber@\count\z@}\hexnumber@\count\tw@}%
798      %
799      \edef\reserved@a{\noexpand\in@
800        {\expandafter\@gobble\string\delimiter}%
801        {\expandafter\meaning\csname\expandafter\@gobble\string#1\space\endcsname}}%
802      \reserved@a
803      \ifin@
804        \expandafter\let\csname\expandafter\@gobble\string#1\space\endcsname\@undefined
805        \expandafter\set@mathdelimiter
806        \csname sym#3\expandafter\endcsname
807        \csname sym#5\endcsname#1#2%
808        \reserved@c\reserved@d
809        \@font@info{Redeclaring math delimiter \string#1}%
810      \else
811        \expandafter\ifx
812        \csname\expandafter\@gobble\string#1\endcsname
813        \relax
814        \expandafter\set@mathdelimiter
815        \csname sym#3\expandafter\endcsname
816        \csname sym#5\endcsname#1#2%
817        \reserved@c\reserved@d
818      \else
819        \@latex@error{Command '\string#1' already defined}\@eha
820      \fi
821    \fi
822  \endgroup
823 \else
824   \@latex@error{Symbol font '#5' is not defined}\@eha
825 \fi
826 \else
827   \@latex@error{Symbol font '#3' is not defined}\@eha
828 \fi
829 }
830 </2ekernel | latexrelease>
831 <latexrelease>\EndIncludeInRelease
832 <latexrelease>\IncludeInRelease{0000/00/00}%
833 <latexrelease>          {\@DeclareMathDelimiter}{Make math delimiters robust}%
834 <latexrelease>\def\@DeclareMathDelimiter#1#2#3#4#5#6{%
835 <latexrelease>  \expandafter\in@\csname sym#3\expandafter\endcsname
836 <latexrelease>    \expandafter{\group@list}%
837 <latexrelease>  \ifin@

```



```

838 \latexrelease\ \expandafter\in@\csname sym#5\expandafter\endcsname
839 \latexrelease\ \expandafter{\group@list}%
840 \latexrelease\ \ifin@
841 \latexrelease\ \begin@group
842 \latexrelease\ \count\z@=#4\relax
843 \latexrelease\ \count\tw@\count\z@
844 \latexrelease\ \divide\count\z@\sist@@n
845 \latexrelease\ \count@\count\z@
846 \latexrelease\ \multiply\count@\sist@@n
847 \latexrelease\ \advance\count\tw@-\count@
848 \latexrelease\ \edef\reserved@c{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
849 \latexrelease\ %
850 \latexrelease\ \count\z@=#6\relax
851 \latexrelease\ \count\tw@\count\z@
852 \latexrelease\ \divide\count\z@\sist@@n
853 \latexrelease\ \count@\count\z@
854 \latexrelease\ \multiply\count@\sist@@n
855 \latexrelease\ \advance\count\tw@-\count@
856 \latexrelease\ \edef\reserved@d{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
857 \latexrelease\ %
858 \latexrelease\ \edef\reserved@a{\noexpand\in@
859 \latexrelease\ \{\expandafter\@gobble\string\delimiter}\meaning#1}}%
860 \latexrelease\ \reserved@a
861 \latexrelease\ \ifin@
862 \latexrelease\ \expandafter\set@mathdelimiter
863 \latexrelease\ \csname sym#3\expandafter\endcsname
864 \latexrelease\ \csname sym#5\endcsname#1#2%
865 \latexrelease\ \reserved@c\reserved@d
866 \latexrelease\ \@font@info{Redeclaring math delimiter \string#1}%
867 \latexrelease\ \else
868 \latexrelease\ \expandafter\ifx
869 \latexrelease\ \csname\expandafter\@gobble\string#1\endcsname
870 \latexrelease\ \relax
871 \latexrelease\ \expandafter\set@mathdelimiter
872 \latexrelease\ \csname sym#3\expandafter\endcsname
873 \latexrelease\ \csname sym#5\endcsname#1#2%
874 \latexrelease\ \reserved@c\reserved@d
875 \latexrelease\ \else
876 \latexrelease\ \@latex@error{Command ‘\string#1’ already defined}\@eha
877 \latexrelease\ \fi
878 \latexrelease\ \fi
879 \latexrelease\ \endgroup
880 \latexrelease\ \else
881 \latexrelease\ \@latex@error{Symbol font ‘#5’ is not defined}\@eha
882 \latexrelease\ \fi
883 \latexrelease\ \else
884 \latexrelease\ \@latex@error{Symbol font ‘#3’ is not defined}\@eha
885 \latexrelease\ \fi
886 \latexrelease\}
887 \latexrelease\ \EndIncludeInRelease
888 \*2kernel)
889 \@onlypreamble\@DeclareMathDelimiter

```

\@xDeclareMathDelimiter

```

890 \def\xDeclareMathDelimiter#1#2#3#4#5{%
891   \expandafter\in@\csname sym#2\expandafter\endcsname
892   \expandafter{\group@list}%
893   \ifin@
894     \expandafter\in@\csname sym#4\expandafter\endcsname
895     \expandafter{\group@list}%
896     \ifin@
897       \begingroup
898         \count\z@=#3\relax
899         \count\tw@\count\z@
900         \divide\count\z@\sist@n
901         \count@\count\z@
902         \multiply\count@\sist@n
903         \advance\count\tw@-\count@
904         \edef\reserved@c{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
905         %
906         \count\z@=#5\relax
907         \count\tw@\count\z@
908         \divide\count\z@\sist@n
909         \count@\count\z@
910         \multiply\count@\sist@n
911         \advance\count\tw@-\count@
912         \edef\reserved@d{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
913         \expandafter\set@mathdelimiter
914         \csname sym#2\expandafter\endcsname\csname sym#4\endcsname#1%
915         \reserved@c\reserved@d
916       \endgroup
917     \else
918       \@latex@error{Symbol font ‘#4’ is not defined}\@eha
919     \fi
920   \else
921     \@latex@error{Symbol font ‘#2’ is not defined}\@eha
922   \fi
923 }
924 \@onlypreamble\xDeclareMathDelimiter

```

`\set@mathdelimiter` We have to end the definition of a math delimiter like `\lfloor` with a space and not with `\relax` as we did before, because otherwise constructs involving `\abovewithdelims` will prematurely end (pr/1329)

```

925 </2ekernel>
926 <*2ekernel | latexrelease>
927 <latexrelease>\IncludeInRelease{2019/10/01}%
928 <latexrelease>          {\set@mathdelimiter}{make delimiters robust}%
929 \def\set@mathdelimiter#1#2#3#4#5#6{%
930   \xdef#3{\delimiter"\mathchar@type#4\hexnumber@#1#5%
931     \hexnumber@#2#6 }%
932   \MakeRobust#3%
933 }
934 \@onlypreamble\set@mathdelimiter
935 </2ekernel | latexrelease>
936 <latexrelease>\EndIncludeInRelease
937 <latexrelease>\IncludeInRelease{0000/00/00}%
938 <latexrelease>          {\set@mathdelimiter}{make delimiters robust}%
939 <latexrelease>

```

```

940 \latexrelease\def\set@mathdelimiter#1#2#3#4#5#6{%
941 \latexrelease\  \xdef#3{\delimiter" \mathchar@type#4\hexnumber@#1#5%
942 \latexrelease\  \hexnumber@#2#6 }}
943 \latexrelease\
944 \latexrelease\EndIncludeInRelease
945 \*2kernel)

```

`\set@mathdelimiter`

```

946 \def\set@mathdelimiter#1#2#3#4#5{%
947 \global\delcode'#3="\hexnumber@#1#4\hexnumber@#2#5\relax}
948 \onlypreamble\set@mathdelimiter

```

`\DeclareMathRadical`

```

949 \def\DeclareMathRadical#1#2#3#4#5{%

```

Below is a crude fix to make this macro work if #1 is undefined or `\relax`. Should be improved!

```

950 \expandafter\ifx
951 \csname\expandafter\@gobble\string#1\endcsname
952 \relax
953 \let#1\radical
954 \fi
955 \edef\reserved@a{\noexpand\in@
956 {\expandafter\@gobble\string\radical}{\meaning#1}}%
957 \reserved@a
958 \ifin@
959 \expandafter\in@\csname sym#2\expandafter\endcsname
960 \expandafter{\group@list}%
961 \ifin@
962 \expandafter\in@\csname sym#4\expandafter\endcsname
963 \expandafter{\group@list}%
964 \ifin@
965 \begingroup
966 \count\z@=#3\relax
967 \count\tw@\count\z@
968 \divide\count\z@\sixt@@n
969 \count@\count\z@
970 \multiply\count@\sixt@@n
971 \advance\count\tw@-\count@
972 \edef\reserved@c{%
973 \hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
974 \count\z@=#5\relax
975 \count\tw@\count\z@
976 \divide\count\z@\sixt@@n
977 \count@\count\z@
978 \multiply\count@\sixt@@n
979 \advance\count\tw@-\count@
980 \edef\reserved@d{%
981 \hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%

```

Coded inline instead of using `\set@mathradical`

```

982 % \expandafter\set@mathradical
983 % \csname sym#2\expandafter\endcsname
984 % \csname sym#4\endcsname#1%
985 % \reserved@c\reserved@d

```

```

986         \xdef#1{\radical"\expandafter\hexnumber@
987             \csname sym#2\endcsname\reserved@c
988             \expandafter\hexnumber@
989             \csname sym#4\endcsname\reserved@d
990         \relax}%
991     \endgroup
992 \else
993     \@latex@error{Symbol font ‘#4’ is not defined}\@eha
994 \fi
995 \else
996     \@latex@error{Symbol font ‘#2’ is not defined}\@eha
997 \fi
998 \else
999     \@latex@error{Command ‘\string#1’ already defined}\@eha
1000 \fi
1001 }
1002 \@onlypreamble\DeclareMathRadical

```

Definition below was wrong it contained \delimiter !

```

\def\set@mathradical#1#2#3#4#5{%
    \xdef#3{\radical"\hexnumber@#1#4\hexnumber@#2#5\relax}}

```

\mathalpha just a dummy currently

```

1003 \let\mathalpha\relax

```

\mathchar@type

```

1004 \def\mathchar@type#1{%
1005     \ifodd 2#1#1 #1\else % is this non-negative number?
1006         \ifx#1\mathord 0\else
1007             \ifx#1\mathop 1\else
1008                 \ifx#1\mathbin 2\else
1009                     \ifx#1\mathrel 3\else
1010                         \ifx#1\mathopen 4\else
1011                             \ifx#1\mathclose 5\else
1012                                 \ifx#1\mathpunct 6\else
1013                                     7% % anything else is variable ord
1014                                 \fi
1015                             \fi
1016                         \fi
1017                     \fi
1018                 \fi
1019             \fi
1020         \fi
1021     \fi}
1022 \@onlypreamble\mathchar@type

```

\DeclareSymbolFontAlphabet

```

1023 \def\DeclareSymbolFontAlphabet#1#2{%
1024     \expandafter\DeclareSymbolFontAlphabet@
1025     \csname \expandafter\@gobble\string#1\space\endcsname{#2}#1}
1026 \@onlypreamble\DeclareSymbolFontAlphabet

```

\DeclareSymbolFontAlphabet@

```

1027 \def\DeclareSymbolFontAlphabet@#1#2#3{%

```

We use the switch `\if@tempswa` to decide if we can declare this symbol font alphabet.

```
1028 \if@tempswa true
```

First check if #2 is known to be a symbol font

```
1029 \expandafter\in@\csname sym#2\expandafter\endcsname
1030 \expandafter{\group@list}%
1031 \ifin@
```

Check if #1 is defined as a math alphabet defined via `\DeclareMathAlphabet`:

```
1032 \expandafter\in@\expandafter#1\expandafter{\alpha@list}%
1033 \ifin@
```

If so remove it from the `\alpha@list` and from all math version macros.

```
1034 \@font@info{Redeclaring math alphabet \string#3}%
1035 \toks@{}%
1036 \def\alpha@elt##1##2##3{%
1037 \ifx##1#1\else\addto@hook\toks@{\alpha@elt##1##2##3}\fi}%
1038 \alpha@list
1039 \xdef\alpha@list{\the\toks@}%

```

Now we loop over all versions and remove the math alphabet:

```
1040 \def\version@elt##1{%
1041 \begingroup
1042 \toks@{}%
1043 \def\getanddefine@fonts####1####2{%
1044 \addto@hook\toks@{\getanddefine@fonts####1####2}}%
1045 \def\install@mathalphabet####1####2{%
1046 \ifx####1#1\else
1047 \addto@hook\toks@{\install@mathalphabet
1048 ####1{####2}}\fi}%
1049 ##1%
1050 \xdef##1{\the\toks@}%
1051 \endgroup
1052 }%
1053 \version@list
1054 \else

```

If #3 is not defined as a math alphabet check if it is defined at all:

```
1055 \expandafter\ifx
1056 \csname\expandafter\@gobble\string#1\space\endcsname
1057 \relax

```

If it is undefined, fine otherwise check if it is a math alphabet defined via `\DeclareSymbolFontAlphabet`:

```
1058 \else
1059 \edef\reserved@a{%
1060 \noexpand\in@{\string\use@mathgroup}{\meaning#1}}%
1061 \reserved@a
1062 \ifin@
1063 \@font@info{Redeclaring math alphabet \string#3}%
1064 \else

```

Since the command #3 is defined to be something which is not a math alphabet we have to skip redefining it.

```
1065 \if@tempswa false
```

```

1066         \@latex@error{Command ‘\string#3’ already defined}\@eha
1067     \fi
1068 \fi
1069 \fi
1070 \else

```

Since the symbol font is not known we better skip defining this alphabet.

```

1071     \@tempswafalse
1072     \@latex@error{Unknown symbol font ‘#2’}\@eha
1073 \fi
1074 \if@tempswa

```

When we reach this point we are allowed to define #1 to be a symbol font math alphabet. This means that we have to set it to

```
\use@mathgroup <math-settings> \sym<name>
```

The *<math-settings>* are the one for the encoding that is used in the font shape where *\sym<name>* is pointing to. This means that we have to get it from the information stored in *\group@list*. Thus we loop through that list after defining *\group@elt* in a suitable way.

```

1075     \def\group@elt##1##2{%
1076         \expandafter\ifx\csname sym#2\endcsname##1%
1077         \expandafter\reserved@a\string##2\@nil
1078         \fi}%
1079     \def\reserved@a##1##2/##3\@nil{%
1080         \def\reserved@a{##2}}%
1081     \group@list
1082     \toks@{\relax\ifmmode \else \non@alpherr#1\fi}%
1083     \edef#1{\the\toks@
1084         \noexpand\use@mathgroup
1085         \expandafter\noexpand\csname M@\reserved@a\endcsname
1086         \csname sym#2\endcsname}%
1087     \def#3{\protect#1}%
1088 \fi
1089 }
1090 \@onlypreamble\DeclareSymbolFontAlphabet@
1091 /2ekernel)

```

File s

## ltfssini.dtx

This file contains the top level L<sup>A</sup>T<sub>E</sub>X interface to the font selection scheme commands. See other parts of the L<sup>A</sup>T<sub>E</sub>X distribution, or *The L<sup>A</sup>T<sub>E</sub>X Companion* for higher level documentation of these commands.

### 35 NFSS Initialisation

Finally, there are six commands that are to be used in L<sup>A</sup>T<sub>E</sub>X and that we will therefore protect against expansion at the wrong point: `\fontfamily`, `\fontseries`, `\fontshape`, `\fontsize`, `\selectfont`, and `\mathversion`.

```
1 \<2kernel>
```

#### 35.1 Providing math *versions*

L<sup>A</sup>T<sub>E</sub>X provides two *versions*. We call them *normal* and *bold*, respectively.

```
2 \DeclareMathVersion{normal}
3 \DeclareMathVersion{bold}
```

Now we define the standard font change commands. We don't allow the use of `\rmfamily` etc. in math mode.

First the changes to another *family*:

```
4 \DeclareRobustCommand\rmfamily
5     {\not@math@alphabet\rmfamily\mathrm
6      \fontfamily\rmdefault\selectfont}
7 \DeclareRobustCommand\sffamily
8     {\not@math@alphabet\sffamily\mathsf
9      \fontfamily\sfdefault\selectfont}
10 \DeclareRobustCommand\ttfamily
11     {\not@math@alphabet\ttfamily\mathtt
12      \fontfamily\ttdefault\selectfont}
```

Then the commands changing the *series*:

```
13 \DeclareRobustCommand\bfseries
14     {\not@math@alphabet\bfseries\mathbf
15      \fontseries\bfdefault\selectfont}
16 \DeclareRobustCommand\mdseries
17     {\not@math@alphabet\mdseries\relax
18      \fontseries\mddefault\selectfont}
19 \DeclareRobustCommand\upshape
20     {\not@math@alphabet\upshape\relax
21      \fontshape\updefault\selectfont}
```

Then the commands changing the *shape*:

```
22 \DeclareRobustCommand\slshape
23     {\not@math@alphabet\slshape\relax
24      \fontshape\sldefault\selectfont}
25 \DeclareRobustCommand\scshape
26     {\not@math@alphabet\scshape\relax
27      \fontshape\scdefault\selectfont}
```

```

28 \DeclareRobustCommand\itshape
29     {\not@math@alphabet\itshape\mathit
30      \fontshape\itdefault\selectfont}

```

`\em` We also have to define the *emphasize* font change command (i.e. `\em`). This command will look is the current font is sloped (i.e. has a positive `\fontdimen1`) and will then select either `\upshape` or `\itshape`.

```

31 \ifdim\fontdimen1>0pt\relax
32 \ifdim\fontdimen1>0pt\relax
33 \ifdim\fontdimen1>0pt\relax
34 \DeclareRobustCommand\em
35     {\@nomath\em \ifdim \fontdimen1>0pt\font >\z@
36      \emminnershape \else \itshape \fi}%
37 \def\emminnershape{\upshape}%
38 \ifdim\fontdimen1>0pt\relax
39 \ifdim\fontdimen1>0pt\relax
40 \ifdim\fontdimen1>0pt\relax
41 \ifdim\fontdimen1>0pt\relax
42 \ifdim\fontdimen1>0pt\relax
43 \ifdim\fontdimen1>0pt\relax
44 \ifdim\fontdimen1>0pt\relax
45 \ifdim\fontdimen1>0pt\relax
46 \ifdim\fontdimen1>0pt\relax

```

`\not@math@alphabet` This function generates an error message when it is called in math mode. The same function should be defined in `newlfont.sty`.

```

47 \def\not@math@alphabet#1#2{%
48     \relax
49     \ifmmode
50         \latexerror{Command \noexpand#1invalid in math mode}%
51         {%
52             Please
53             \ifx#2\relax
54                 define a new math alphabet^^J%
55                 if you want to use a special font in math mode%
56             \else

```

We have to a `\noexpand` below to prevent expansion of `#2`. In case of `#1` we can omit this (due to the current definition of robust commands since they do come out right there :-).

```

57         use the math alphabet \noexpand#2instead of
58         the #1command%
59     \fi
60     .
61 }%
62 \fi}

```

Finally we provide two abbreviations to switch to the  $\text{\LaTeX}$  versions.

```

63 \DeclareRobustCommand\boldmath{\@nomath\boldmath
64     \mathversion{bold}}
65 \DeclareRobustCommand\unboldmath{\@nomath\unboldmath
66     \mathversion{normal}}

```



Here we switch to the default math version by defining the internal macro `\math@version`. We dare not to call `\mathversion` at this place because this would call `\glb@settings`.

```
67 \def\math@version{normal}
```

## 35.2 Miscellaneous

`\newfont` We start by defining a few macros that are part of standard L<sup>A</sup>T<sub>E</sub>X's user interface.  
`\symbol` The use of these functions is not encouraged, but they will allow to process older documents without changes to the source.

```
68 \def\newfont#1#2{\@ifdefinable#1{\font#1=#2\relax}}
```

```
69 \DeclareRobustCommand\symbol[1]{\char #1\relax}
```

`\@setfontsize` This abbreviation is used by L<sup>A</sup>T<sub>E</sub>X's user level size changing commands, such as  
`\@setsize` `\large`.

```
70 \def\@setfontsize#1#2#3{\@nomath#1%
```

For the benefit of people relying on keeping the name of the current font command saved in `\@currsz` we define it. To ensure that `\@setfontsize` keeps being robust we omit this assignment during times where `\protect` differs from `\@typeset@protect`.

```
71 \ifx\protect\@typeset@protect
```

```
72 \let\@currsz#1%
```

```
73 \fi
```

```
74 \fontsize{#2}{#3}\selectfont}
```

For compatibility we also define `\@setsize` the 209 command

```
75 (*compat)
```

```
76 \def\@setsize#1#2#3#4{\@setfontsize#1{#4}{#2}}
```

```
77 /compat)
```

`\oldstylenums` This macro implements old style numerals but only works if we assume that the standard math fonts are used. Thus it needs changing in case other math encodings are used.

```
78 \DeclareRobustCommand\oldstylenums[1]{%
```

```
79 \begingroup
```

Provide spacing using the interword space of the current font.

```
80 \spaceskip\fontdimen\tw\font
```

Then switch to the math italic font. We don't change the current value of `\f@series` which means that you can use bold numerals if `\bfseries` is in force. As family we use `\rmdefault` which means that this only works if there exist an OML encoded version of that font or rather a corresponding `.fd` file (which is the case for standard L<sup>A</sup>T<sub>E</sub>X fonts even though they only contain substitutions).

```
81 \usefont{OML}{\rmdefault}{\f@series}{it}%
```

```
82 \mathgroup\symletters #1%
```

```
83 \endgroup
```

```
84 }
```

`\hexnumber@` To set up L<sup>A</sup>T<sub>E</sub>X's special math character definitions we first provide a macro to generate hexadecimal numbers. It is a rather simple `\ifcase`.

```
85 \def\hexnumber@#1{\ifcase\number#1
```

```

86 0\or 1\or 2\or 3\or 4\or 5\or 6\or 7\or 8\or
87 9\or A\or B\or C\or D\or E\or F\fi}

```

`\nfss@text` In its simplest form `\nfss@text` is an `\mbox`. This will produce unbreakable text outside math and inside math you will get text with the same fonts as outside. The only drawback is that such item won't change sizes in subscripts. But this behavior can be easily changed. With the `amstex` style option one will get a sub style called `amstext` which will redefine the `\nfss@text` macro to produce correct text in all sizes.

We have to use `\def` instead of the shorter `\let` since `\mbox` is undefined when we reach this point.

```
88 \def\nfss@text#1{{\mbox{#1}}}
```

`\copyright` The definition of `\copyright` was changed so that it works in other type styles, and to make it robust. We leave the family untouched so that the copyright notice will come out differently if a different font family is in use. This command is commented out, since it is now defined in `ltoutenc.dtx`.

```

89 %\DeclareRobustCommand\copyright
90 %    {{\ooalign{\hfil
91 %        \raise.07ex\hbox{\mdseries\upshape c}\hfil\crcr
92 %        \mathhexbox20D}}}

```

`\normalfont` The macro `\reset@font` is used in  $\text{\LaTeX}$  to switch to a standard font, in order to initialize the current font in situations where typesetting is done in a new visual context (e.g. in a footnote). We define it here to allow the test for the new  $\text{\LaTeX}$  version above but nevertheless are able to run all kind of mixtures.

`\reset@font`

`\p@reset@font`

The user interface name for `\reset@font` is `\normalfont`:

```

93 \DeclareRobustCommand\normalfont
94     {\usefont\encodingdefault
95         \familydefault
96         \seriesdefault
97         \shapedefault
98         \relax}
99 \let\reset@font\normalfont

```

We left out the special  $\text{\LaTeX}$  fonts which are not automatically included in the base version of the font selection since these fonts contain only a few characters which are also included in the AMS fonts so anybody who is using these fonts doesn't need them. But for compatibility reasons we will define these symbols.

```

100 \def\not@base#1{\@latex@error
101   {Command \noexpand#1not provided in base LaTeX2e}%
102   {Load the latexsym or the amsfonts package to
103   define this symbol}}
104 \def\mho{\not@base\mho}
105 \def\Join{\not@base\Join}
106 \def\Box{\not@base\Box}
107 \def\Diamond{\not@base\Diamond}
108 \def\leadsto{\not@base\leadsto}
109 \def\squsubset{\not@base\squsubset}
110 \def\sqsupset{\not@base\sqsupset}
111 \def\lhd{\not@base\lhd}

```

```

112 \def\unlhd{\not@base\unlhd}
113 \def\rhd{\not@base\rhd}
114 \def\unrhd{\not@base\unrhd}

```

We now initialize all variables set by `\DeclareErrorFont`. These values are not really important since they will be overwritten later on by the definition in `fontdef.ltx`.

However, if `fontdef.cfg` is corrupted then at least a hopefully suitable error font is present.

```

115 \DeclareErrorFont{OT1}{cmr}{m}{n}{10}  %% don't modify this setting
116                                         %% overwrite it in fontdef.cfg
117                                         %% if necessary

```

We also set some default values for `\f@family` etc. Note that we don't yet have any encodings that comes later. In the past this was implicitly done by `\DeclareErrorFont`.

```

118 \fontfamily{cmr}
119 \fontseries{m}
120 \fontshape{n}
121 \fontsize{10}{10}

```

We now load the customizable parts of NFSS.

```

122 \InputIfFileExists{fonttext.cfg}
123     {\typeout{=====^^J%
124             ^^J%
125             Local config file fonttext.cfg used^^J%
126             ^^J%
127             =====}%
128     \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
129     }
130     {\input{fonttext.ltx}}
131 \let\@addtofilelist\@gobble

```

Ditto for math although I don't think that we will get a lot of customisation :-)

```

132 \InputIfFileExists{fontmath.cfg}
133     {\typeout{=====^^J%
134             ^^J%
135             Local config file fontmath.cfg used^^J%
136             ^^J%
137             =====}%
138     \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
139     }
140     {\input{fontmath.ltx}}
141 \let\@addtofilelist\@gobble

```

Then we preload several fonts. This file might be customized *without* changing the behavior of the format (i.e. necessary font definitions will be loaded at runtime if they are not preloaded). This is done in the file `preload.ltx`.

```

142 \InputIfFileExists{preload.cfg}
143     {\typeout{=====^^J%
144             ^^J%
145             Local config file preload.cfg used^^J%
146             ^^J%
147             =====}%

```

```

148             \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
149             }
150             {\input{preload.ltx}}
151 \let\@addtofilelist\@gobble

\@acci We also save the values of some accents in \@acci, \@accii and \@acciii so they
\@accii can be restored by a minipage inside a tabbing environment.
\@acciii 152 \let\@acci\' \let\@accii\' \let\@acciii\=

\cal Here were the two old ⟨alphabet identifiers⟩.
\mit
153 </2ekernel>

```

# File t

## fontdef.dtx

j-latexreleasej [2019/09/21 v3.0d LaTeX Kernel (j-latexreleasej font setup)]

### 36 Introduction

This file is used to generate the files `fonttext.ltx` (text font declarations) and `fontmath.ltx` (math font declarations), which are used during the format generation. It contains the declaration of the standard text encodings used at the site as well as a minimal subset of font shape groups that NFSS will look at to ensure that the specified encodings are valid.

The math part contains the setup for math encodings as well as the default math symbol declarations that belong to the encoding.

It is possible to change this setup (by using other fonts, or defaults) without losing the ability to process documents written at other sites. Portability in this sense means that a document will compile without errors. It does not mean, however, that identical output will be produced. For this it is necessary that the distributed setup is used at both installations.

### 37 Customization

You are not allowed to change this source file! If you want to change the default encodings and/or the font shape groups preloaded you should create a copy of `fonttext.ltx` under the name `fonttext.cfg` and change this copy. If  $\text{\LaTeX}$  2 $\epsilon$  finds a file of this name it will use it, otherwise it uses the standard file which is `fontdef.ltx`.

If you don't plan to use Computer Modern much or at all, it might (!) be a good idea to make your own `fonttext.cfg`. Look at the comments below (docstrip module 'text') to see what should go into such a file.

To change the math font setup use a copy of `fontmath.ltx` under the name `fontmath.cfg` and change this copy. However, dealing with this interface is even more a job for an expert than changing the text font setup — in short, we don't encourage either.

**Warning:** please note that we don't support customised  $\text{\LaTeX}$  versions. Thus, before sending in a bug report please try your test file with a  $\text{\LaTeX}$  format which is not customised and send in the log from that version (unless the problem goes away).

Please note: the following standard encodings have to be defined in all local variants of `font....cfg` to guarantee that all  $\text{\LaTeX}$  installations behave in the same way.

T1	Cork T <sub>E</sub> X text encoding
OT1	old T <sub>E</sub> X text encoding
U	unknown encoding
OML	old T <sub>E</sub> X math letters encoding
OMS	old T <sub>E</sub> X math symbols encoding
OMX	old T <sub>E</sub> X math extension symbols encoding
TU	Unicode

Notice that some of these encodings are ‘old’ in the sense that we hope that they will be superseded soon by encoding standards defined by the T<sub>E</sub>X user community. Therefore this set of default encodings may change in the future.

The first candidate is OT1 which will soon be replaced by T1, the official T<sub>E</sub>X text encoding.

**Warning:** If you add additional encodings to this file there is no guarantee any longer that files processable at your installation will also be processable at other installations. Thus, if you make use of such an encoding in your document, e.g. if you intend to typeset in Cyrillic (OT2 encoding), you need to specify this encoding in the preamble of your document prior to sending it to another installation. Once the encoding is specified in that place in your document, the document is processable at all L<sup>A</sup>T<sub>E</sub>X installations (provided they have suitable fonts installed).

For this reason we suggest that you define a short package file that sets up an additional encoding used at your site (rather than putting the encoding into this file) since this package can easily be shipped with your document.

## 38 The docstrip modules

The following modules are used to direct **docstrip** in generating external files:

driver	produce a documentation driver file
text	produce the file <b>fonttext.ltx</b>
math	produce the file <b>fontmath.ltx</b>
cfgtext	produce a dummy <b>fonttext.cfg</b> file
cfgmath	produce a dummy <b>fontmath.cfg</b> file

A typical **docstrip** command file would then have entries like:

```
\generateFile{fonttext.ltx}{t}{\from{fontdef.dtx}{text}}
```

## 39 A driver for this document

The next bit of code contains the documentation driver file for T<sub>E</sub>X, i.e. the file that will produce the documentation you are currently reading. It will be extracted from this file by the DOCSTRIP program.

```
1 (*driver)
2 \documentclass{ltxdoc}
3 \GetFileInfo{fontdef.dtx}
```

```

4 \begin{document}
5   \DocInput{fontdef.dtx}
6 \end{document}
7 \</driver>

```

## 40 The fonttext.ltx file

The identification is done earlier on with a `\ProvidesFile` declaration.

```

8 (*text)
9 \typeout{=== Don't modify this file, use a .cfg file instead ===^J}

```

### 40.1 Encodings

This file declares the standard encodings for text and math fonts. All others should be declared in packages or in the documents directly.

For every text encoding there are normally a number of encoding specific commands, e.g. accents, special characters, etc. (The definition for such a command might have to change when the encoding is changed, because the character is in a different position, or not available at all, or the accent is produced in a different way.) This is handled by a general mechanism which is described in `ltoutenc.dtx`.

By convention, text encoding specific declarations, including the declaration `\DeclareFontEncoding`, are kept in separate file of the form `<enc>enc.def`, e.g. `otlenc.def`. This allows other applications to make use of the declarations as well.

Similar to the default encoding, the loading of the encoding files for the two major text encodings shouldn't be changed. In particular, the `inputenc` package depends on this.

```

10 \input {omlenc.def}
11 \input {t1enc.def}
12 \input {otlenc.def}      % <- should come after T1 for speed
13 \input {omsenc.def}

```

```

14 \ifx\Umathchar\@undefined

```

We then set the default text font encoding. This will hopefully change some day to T1. This setting should *not* be changed to produce a portable format.

```

15 \fontencoding{OT1}

```

```

16 \else

```

Unicode.

```

17 \input {tuenc.def}
18 \fontencoding{TU}
19 \DeclareFontSubstitution{TU}{lmr}{m}{n}
20 \begingroup
21 \nfss@catcodes
22 \input {tulmr.fd}
23 \input {tulmss.fd}
24 \input {tulmtt.fd}
25 \endgroup
26 \DeclareFontSubstitution{TU}{lmr}{m}{n}

```

End of Unicode branch.

```
27 \fi
```

If different encodings for text fonts are in use one could put the common setup into `\DeclareFontEncodingDefaults`. There is now a better mechanism so using this interface is discouraged!

```
28 \DeclareFontEncodingDefaults{}{}
```

Then we define the default substitution for every encoding. This release of  $\text{\LaTeX} 2_{\epsilon}$  assumes that the ec fonts are available. It is possible to change this to point to some other font family (e.g., Times with the appropriate encoding if it is available) without making documents non-portable. However, in such a case documents will produce different page breaks at other sites. The substitution defaults can all be changed without losing portability as long as there are font shape definitions for the selected substitutions.

```
29 \DeclareFontSubstitution{T1}{cmr}{m}{n}
```

```
30 \DeclareFontSubstitution{OT1}{cmr}{m}{n}
```

For every encoding declaration,  $\text{\LaTeX} 2_{\epsilon}$  will try to verify that the given substitution information makes sense, i.e. that it is impossible to go into an endless loop if font substitution happens. This is done at the moment the `\begin{document}` is encountered.  $\text{\LaTeX} 2_{\epsilon}$  will then check that for every encoding the substitution defaults form a valid font shape group, which means that it will check if there is a `\DeclareFontShape` declaration for this combination. We will therefore load the corresponding .fd files now. If we don't do this they would be loaded at verification time (i.e. at `\begin{document}`) which would delay processing unnecessarily.

**Warning:** Please note that this means that you have to regenerate the format whenever you change any of these .fd files since  $\text{\LaTeX} 2_{\epsilon}$  will not read .fd files if it already knows about the encoding/family combination.

The `\nfss@catcodes` ensures that white space is ignored in any definitions made in the fd files.

```
31 \begingroup
```

```
32 \nfss@catcodes
```

```
33 \input {t1cmr.fd}
```

```
34 \input {ot1cmr.fd}
```

```
35 \endgroup
```

We also load some other font definition files which are normally needed in a document. This is only done for processing speed and you can comment the next two lines out to save some memory. If necessary these files are then loaded when your document is processed. (Loading .fd files is a less drastic step compared to preloading fonts because the number of fonts is limited 255 at (nearly) every  $\text{\TeX}$  installation, while the amount of main memory is not a limiting factor at most installations.)

```
36 \begingroup
```

```
37 \nfss@catcodes
```

```
38 \input {ot1cmss.fd}
```

```
39 \input {ot1cmtt.fd}
```

```
40 \endgroup
```



Even with all the precautions it is still possible that NFSS will run into problems, for example, when a .fd file contains corrupted data. To guard against such cases NFSS has a very low-level fallback font that is installed with the following line.

```
41 \DeclareErrorFont{OT1}{cmr}{m}{n}{10}
```

This means, “if everything else fails use Computer Modern Roman normal shape at 10pt in the old text encoding”. You can change the font used but the encoding should be the same as the one specified with `\fontencoding` above.

## 40.2 Defaults

To allow the use of `\rmfamily`, `\sffamily`, etc. in documents even if non-standard families are used we provide nine macros which hold the name of the corresponding families, series, and so on. This makes it easy to use other font families (like Times Roman, etc.). One simply has to redefine these defaults.

All these hooks have to be defined in this file but you can change their meaning (except for `\encodingdefault`) without making documents non-portable.

```
\encodingdefault The following three definitions set up the meaning for \rmfamily, \sffamily, and
\rmdefault      \ttfamily.
\sfddefault      42 \ifx\Umathchar\@undefined
\ttdefault      43 \newcommand\encodingdefault{OT1}
                  44 \newcommand\rmdefault{cmr}
                  45 \newcommand\sfddefault{cmss}
                  46 \newcommand\ttdefault{cmtt}
                  47 \else
                  48 \newcommand\encodingdefault{TU}
                  49 \newcommand\rmdefault{lmr}
                  50 \fontfamily{\rmdefault}
                  51 \newcommand\sfddefault{lmss}
                  52 \newcommand\ttdefault{lmtt}
                  53 \fi
                  54 \</text>
                  55 \<latexrelease>\IncludeInRelease{2017/01/01}%
                  56 \<latexrelease>          {\encodingdefault}{TU encoding default}%
                  57 \<latexrelease>\ifx\Umathchar\@undefined
                  58 \<latexrelease>\renewcommand\encodingdefault{OT1}
                  59 \<latexrelease>\fontencoding{\encodingdefault}
                  60 \<latexrelease>\renewcommand\rmdefault{cmr}
                  61 \<latexrelease>\fontfamily{\rmdefault}
                  62 \<latexrelease>\renewcommand\sfddefault{cmss}
                  63 \<latexrelease>\renewcommand\ttdefault{cmtt}
                  64 \<latexrelease>\else
                  65 \<latexrelease>\renewcommand\encodingdefault{TU}
                  66 \<latexrelease>%done in everyjob\fontencoding{\encodingdefault}
                  67 \<latexrelease>\renewcommand\rmdefault{lmr}
                  68 \<latexrelease>\fontfamily{\rmdefault}
                  69 \<latexrelease>\renewcommand\sfddefault{lmss}
                  70 \<latexrelease>\renewcommand\ttdefault{lmtt}
                  71 \<latexrelease>\fi
                  72 \<latexrelease>\EndIncludeInRelease
                  73 \<latexrelease>\IncludeInRelease{0000/00/00}%
```

```

74 \latexrelease) \encodingdefault}{TU encoding default}%
75 \latexrelease)\fontencoding{OT1}
76 \latexrelease)\renewcommand\encodingdefault{OT1}
77 \latexrelease)\fontencoding{\encodingdefault}
78 \latexrelease)\renewcommand\rmdefault{cmr}
79 \latexrelease)\fontfamily{\rmdefault}
80 \latexrelease)\renewcommand\sfddefault{cmss}
81 \latexrelease)\renewcommand\ttdefault{cmtt}
82 \latexrelease)\EndIncludeInRelease
83 (*text)

\bfdefault Series changing commands are influenced by the following hooks.
\mddefault 84 \newcommand\bfdefault{bx}
            85 \newcommand\mddefault{m}

\itdefault Shape changing commands use the following hooks.
\sldefault 86 \newcommand\itdefault{it}
\scdefault 87 \newcommand\sldefault{sl}
\updefault 88 \newcommand\scdefault{sc}
            89 \newcommand\updefault{n}

\familydefault Finally we have the hooks that describe the behaviour of the \normalfont com-
\seriesdefault mand. To stay portable, the definition of \encodingdefault should not be
\shapedefault changed and should match the setting above for \fontencoding. All other values
            can be set according to your taste.
            90 \newcommand\familydefault{\rmdefault}
            91 \newcommand\seriesdefault{\mddefault}
            92 \newcommand\shapedefault{\updefault}

            This finishes the low-level setup in fonttext.ltx.
            93 \text

```

## 41 The fontmath.ltx file

The identification is done earlier on with a \ProvidesFile declaration.

```

94 (*math)
95 \typeout{=== Don't modify this file, use a .cfg file instead ===^J}

```

### 41.1 The font encodings used

```

96 \DeclareFontEncoding{OML}{-}{-}
97 \DeclareFontEncoding{OMS}{-}{-}
98 \DeclareFontEncoding{OMX}{-}{-}

```

Finally a declaration for U encoding which serves for all fonts that do not fit standard encodings. For math this sets up \noaccents@ providing for AMS-L<sup>A</sup>T<sub>E</sub>X. This macro is used therein to handle accented characters if they are not supported by the font. In other words, if fonts with U encoding are used in math, all accents (like from \breve) are obtained from some other font that has them.

```

99 \DeclareFontEncoding{U}{-}{\noaccents@}

```

The encodings for math are next:

```

100 \DeclareFontSubstitution{OML}{cmm}{m}{it}

```

```

101 \DeclareFontSubstitution{OMS}{cmsy}{m}{n}
102 \DeclareFontSubstitution{OMX}{cmex}{m}{n}
103 \DeclareFontSubstitution{U}{cmr}{m}{n}
104 \begingroup
105 \nfss@catcodes
106 \input {omlcmm.fd}
107 \input {omscmsy.fd}
108 \input {omxcmex.fd}
109 \input {ucmr.fd}
110 \endgroup

```

#### 41.1.1 Symbolfont and Alphabet declarations

We now define the basic symbol fonts used by L<sup>A</sup>T<sub>E</sub>X. These four symbol fonts must be defined by this file.

It is possible to make the symbol fonts point to other external fonts without losing the ability to process documents written at other sites, as long as one defines the same symbol font names with the same encodings, e.g. `operators` with `OT1` etc. If other encodings are used documents become non-portable. Such a change should therefore be done in a package file.

```

111 \DeclareSymbolFont{operators} {OT1}{cmr} {m}{n}
112 \DeclareSymbolFont{letters} {OML}{cmm} {m}{it}
113 \DeclareSymbolFont{symbols} {OMS}{cmsy}{m}{n}
114 \DeclareSymbolFont{largesymbols}{OMX}{cmex}{m}{n}

115 \SetSymbolFont{operators}{bold}{OT1}{cmr} {bx}{n}
116 \SetSymbolFont{letters} {bold}{OML}{cmm} {b}{it}
117 \SetSymbolFont{symbols} {bold}{OMS}{cmsy}{b}{n}

```

Below are the seven math alphabets which are defined by NFSS. Again they must be defined by this file. However, as before you can change the fonts used without losing portability, but you should be careful when changing the encoding since that may make documents come out wrong.

```

118 \DeclareSymbolFontAlphabet{\mathrm} {operators}
119 \DeclareSymbolFontAlphabet{\mathnormal}{letters}
120 \DeclareSymbolFontAlphabet{\mathcal} {symbols}
121 \DeclareMathAlphabet {\mathbf} {OT1}{cmr}{bx}{n}
122 \DeclareMathAlphabet {\mathsf} {OT1}{cmss}{m}{n}
123 \DeclareMathAlphabet {\mathit} {OT1}{cmr}{m}{it}
124 \DeclareMathAlphabet {\mathtt} {OT1}{cmtt}{m}{n}

```

Given the currently available fonts we cannot bold-en `\mathbf` and `\mathtt` but in principle one could use ‘ultra bold’ or something. The alphabets defined via `\DeclareSymbolFontAlphabet` will change automatically in a new math version if the corresponding symbol font changes.

```

125 \SetMathAlphabet\mathsf{bold}{OT1}{cmss}{bx}{n}
126 \SetMathAlphabet\mathit{bold}{OT1}{cmr}{bx}{it}

```

## 41.2 Math font sizes

The declarations below declare the text, script and scriptscript size to be used for each text font size.

All occurrences of sizes longer than a single character are replaced with the macro name that holds them, saving a number of tokens (but losing a bit of speed, so this may not stay this way).

```

127 \DeclareMathSizes{5}{5}{5}{5}
128 \DeclareMathSizes{6}{6}{5}{5}
129 \DeclareMathSizes{7}{7}{5}{5}
130 \DeclareMathSizes{8}{8}{6}{5}
131 \DeclareMathSizes{9}{9}{6}{5}
132 \DeclareMathSizes{\@xpt}{\@xpt}{7}{5}
133 \DeclareMathSizes{\@xipt}{\@xipt}{8}{6}
134 \DeclareMathSizes{\@xipt}{\@xipt}{8}{6}
135 \DeclareMathSizes{\@xivpt}{\@xivpt}{\@xpt}{7}
136 \DeclareMathSizes{\@xvipt}{\@xvipt}{\@xipt}{\@xpt}
137 \DeclareMathSizes{\@xxpt}{\@xxpt}{\@xivpt}{\@xipt}
138 \DeclareMathSizes{\@xxvpt}{\@xxvpt}{\@xxpt}{\@xvipt}

```

### 41.3 The math symbol assignments

We start by setting up math codes for most of the characters typed in directly from the keyboard. Most of them are normally already setup up in the same way by `InitTeX`. However, we repeat them here to have a complete setup which can be exchanged with another if desired.

#### 41.3.1 The letters

```

139 \DeclareMathSymbol{a}{\mathalpha}{letters}{‘a}
140 \DeclareMathSymbol{b}{\mathalpha}{letters}{‘b}
141 \DeclareMathSymbol{c}{\mathalpha}{letters}{‘c}
142 \DeclareMathSymbol{d}{\mathalpha}{letters}{‘d}
143 \DeclareMathSymbol{e}{\mathalpha}{letters}{‘e}
144 \DeclareMathSymbol{f}{\mathalpha}{letters}{‘f}
145 \DeclareMathSymbol{g}{\mathalpha}{letters}{‘g}
146 \DeclareMathSymbol{h}{\mathalpha}{letters}{‘h}
147 \DeclareMathSymbol{i}{\mathalpha}{letters}{‘i}
148 \DeclareMathSymbol{j}{\mathalpha}{letters}{‘j}
149 \DeclareMathSymbol{k}{\mathalpha}{letters}{‘k}
150 \DeclareMathSymbol{l}{\mathalpha}{letters}{‘l}
151 \DeclareMathSymbol{m}{\mathalpha}{letters}{‘m}
152 \DeclareMathSymbol{n}{\mathalpha}{letters}{‘n}
153 \DeclareMathSymbol{o}{\mathalpha}{letters}{‘o}
154 \DeclareMathSymbol{p}{\mathalpha}{letters}{‘p}
155 \DeclareMathSymbol{q}{\mathalpha}{letters}{‘q}
156 \DeclareMathSymbol{r}{\mathalpha}{letters}{‘r}
157 \DeclareMathSymbol{s}{\mathalpha}{letters}{‘s}
158 \DeclareMathSymbol{t}{\mathalpha}{letters}{‘t}
159 \DeclareMathSymbol{u}{\mathalpha}{letters}{‘u}
160 \DeclareMathSymbol{v}{\mathalpha}{letters}{‘v}
161 \DeclareMathSymbol{w}{\mathalpha}{letters}{‘w}
162 \DeclareMathSymbol{x}{\mathalpha}{letters}{‘x}
163 \DeclareMathSymbol{y}{\mathalpha}{letters}{‘y}
164 \DeclareMathSymbol{z}{\mathalpha}{letters}{‘z}

165 \DeclareMathSymbol{A}{\mathalpha}{letters}{‘A}
166 \DeclareMathSymbol{B}{\mathalpha}{letters}{‘B}

```

```

167 \DeclareMathSymbol{C}{\mathalpha}{letters}{‘C}
168 \DeclareMathSymbol{D}{\mathalpha}{letters}{‘D}
169 \DeclareMathSymbol{E}{\mathalpha}{letters}{‘E}
170 \DeclareMathSymbol{F}{\mathalpha}{letters}{‘F}
171 \DeclareMathSymbol{G}{\mathalpha}{letters}{‘G}
172 \DeclareMathSymbol{H}{\mathalpha}{letters}{‘H}
173 \DeclareMathSymbol{I}{\mathalpha}{letters}{‘I}
174 \DeclareMathSymbol{J}{\mathalpha}{letters}{‘J}
175 \DeclareMathSymbol{K}{\mathalpha}{letters}{‘K}
176 \DeclareMathSymbol{L}{\mathalpha}{letters}{‘L}
177 \DeclareMathSymbol{M}{\mathalpha}{letters}{‘M}
178 \DeclareMathSymbol{N}{\mathalpha}{letters}{‘N}
179 \DeclareMathSymbol{O}{\mathalpha}{letters}{‘O}
180 \DeclareMathSymbol{P}{\mathalpha}{letters}{‘P}
181 \DeclareMathSymbol{Q}{\mathalpha}{letters}{‘Q}
182 \DeclareMathSymbol{R}{\mathalpha}{letters}{‘R}
183 \DeclareMathSymbol{S}{\mathalpha}{letters}{‘S}
184 \DeclareMathSymbol{T}{\mathalpha}{letters}{‘T}
185 \DeclareMathSymbol{U}{\mathalpha}{letters}{‘U}
186 \DeclareMathSymbol{V}{\mathalpha}{letters}{‘V}
187 \DeclareMathSymbol{W}{\mathalpha}{letters}{‘W}
188 \DeclareMathSymbol{X}{\mathalpha}{letters}{‘X}
189 \DeclareMathSymbol{Y}{\mathalpha}{letters}{‘Y}
190 \DeclareMathSymbol{Z}{\mathalpha}{letters}{‘Z}

```

#### 41.3.2 The digits

```

191 \DeclareMathSymbol{0}{\mathalpha}{operators}{‘0}
192 \DeclareMathSymbol{1}{\mathalpha}{operators}{‘1}
193 \DeclareMathSymbol{2}{\mathalpha}{operators}{‘2}
194 \DeclareMathSymbol{3}{\mathalpha}{operators}{‘3}
195 \DeclareMathSymbol{4}{\mathalpha}{operators}{‘4}
196 \DeclareMathSymbol{5}{\mathalpha}{operators}{‘5}
197 \DeclareMathSymbol{6}{\mathalpha}{operators}{‘6}
198 \DeclareMathSymbol{7}{\mathalpha}{operators}{‘7}
199 \DeclareMathSymbol{8}{\mathalpha}{operators}{‘8}
200 \DeclareMathSymbol{9}{\mathalpha}{operators}{‘9}

```

#### 41.3.3 Punctuation, brace, etc. keys

```

201 \DeclareMathSymbol{!}{\mathclose}{operators}{"21}
202 \DeclareMathSymbol{*}{\mathbin}{symbols}{"03} % \ast
203 \DeclareMathSymbol{+}{\mathbin}{operators}{"2B}
204 \DeclareMathSymbol{,}{\mathpunct}{letters}{"3B}
205 \DeclareMathSymbol{-}{\mathbin}{symbols}{"00}
206 \DeclareMathSymbol{.}{\mathord}{letters}{"3A}
207 \DeclareMathSymbol{:}{\mathrel}{operators}{"3A}
208 \DeclareMathSymbol{;}{\mathpunct}{operators}{"3B}
209 \DeclareMathSymbol{=}{\mathrel}{operators}{"3D}
210 \DeclareMathSymbol{?}{\mathclose}{operators}{"3F}

```

The following symbols are defined as delimiters below which automatically defines them as math symbols.

```

211 %\DeclareMathSymbol{(}{\mathopen}{operators}{"28}
212 %\DeclareMathSymbol{)}{\mathclose}{operators}{"29}
213 %\DeclareMathSymbol{/}{\mathord}{letters}{"3D}

```

```

214 %\DeclareMathSymbol{\mathopen}{operators}{5B}
215 %\DeclareMathSymbol{\mathclose}{operators}{5D}
216 %\DeclareMathSymbol{\mathord}{symbols}{6A}
217 %\DeclareMathSymbol{\mathrel}{letters}{3C}
218 %\DeclareMathSymbol{\mathrel}{letters}{3E}

```

Should all of the following being activated by default? Probably not.

```

219 %\DeclareMathSymbol{\mathopen}{symbols}{66}
220 %\DeclareMathSymbol{\mathclose}{symbols}{67}
221 %\DeclareMathSymbol{\mathord}{symbols}{6E} % \backslash
222 \mathcode'\ =8000 % \space
223 \mathcode'\prime =8000 % ^\prime
224 \mathcode'\_ =8000 % \_

```

#### 41.3.4 Delimitercodes for characters

[to be completed]

Finally, `\InitEX` sets all `\delcode` values to -1, except `\delcode' = 0`

```

225 \DeclareMathDelimiter{\mathopen}{operators}{28}{largesymbols}{00}
226 \DeclareMathDelimiter{\mathclose}{operators}{29}{largesymbols}{01}
227 \DeclareMathDelimiter{\mathopen}{operators}{5B}{largesymbols}{02}
228 \DeclareMathDelimiter{\mathclose}{operators}{5D}{largesymbols}{03}

```

The next two are considered to be relations when not used in the context of a delimiter! And worse, they do even represent different glyphs when being used as delimiter and not as delimiter. This is a user level syntax inherited from plain `TeX`. Therefore we explicitly redefine the math symbol definitions for these symbols afterwards.

```

229 \DeclareMathDelimiter{\mathopen}{symbols}{68}{largesymbols}{0A}
230 \DeclareMathDelimiter{\mathclose}{symbols}{69}{largesymbols}{0B}
231 \DeclareMathSymbol{\mathrel}{letters}{3C}
232 \DeclareMathSymbol{\mathrel}{letters}{3E}

```

And here is another case where the non-delimiter version produces a glyph different from the delimiter version.

```

233 \DeclareMathDelimiter{\mathord}{operators}{2F}{largesymbols}{0E}
234 \DeclareMathSymbol{\mathord}{letters}{3D}

235 \DeclareMathDelimiter{\mathord}{symbols}{6A}{largesymbols}{0C}
236 \expandafter\DeclareMathDelimiter\@backslashchar
237 \mathord{symbols}{6E}{largesymbols}{0F}

```

N.B. `{` and `}` should NOT get `delcodes`; otherwise parameter grouping fails!

### 41.4 Symbols accessed via control sequences

#### 41.4.1 Greek letters

```

238 \DeclareMathSymbol{\alpha}{mathord}{letters}{0B}
239 \DeclareMathSymbol{\beta}{mathord}{letters}{0C}
240 \DeclareMathSymbol{\gamma}{mathord}{letters}{0D}
241 \DeclareMathSymbol{\delta}{mathord}{letters}{0E}
242 \DeclareMathSymbol{\epsilon}{mathord}{letters}{0F}
243 \DeclareMathSymbol{\zeta}{mathord}{letters}{10}
244 \DeclareMathSymbol{\eta}{mathord}{letters}{11}
245 \DeclareMathSymbol{\theta}{mathord}{letters}{12}
246 \DeclareMathSymbol{\iota}{mathord}{letters}{13}

```

```

247 \DeclareMathSymbol{\kappa}{\mathord}{letters}{14}
248 \DeclareMathSymbol{\lambda}{\mathord}{letters}{15}
249 \DeclareMathSymbol{\mu}{\mathord}{letters}{16}
250 \DeclareMathSymbol{\nu}{\mathord}{letters}{17}
251 \DeclareMathSymbol{\xi}{\mathord}{letters}{18}
252 \DeclareMathSymbol{\pi}{\mathord}{letters}{19}
253 \DeclareMathSymbol{\rho}{\mathord}{letters}{1A}
254 \DeclareMathSymbol{\sigma}{\mathord}{letters}{1B}
255 \DeclareMathSymbol{\tau}{\mathord}{letters}{1C}
256 \DeclareMathSymbol{\upsilon}{\mathord}{letters}{1D}
257 \DeclareMathSymbol{\phi}{\mathord}{letters}{1E}
258 \DeclareMathSymbol{\chi}{\mathord}{letters}{1F}
259 \DeclareMathSymbol{\psi}{\mathord}{letters}{20}
260 \DeclareMathSymbol{\omega}{\mathord}{letters}{21}
261 \DeclareMathSymbol{\varepsilon}{\mathord}{letters}{22}
262 \DeclareMathSymbol{\vartheta}{\mathord}{letters}{23}
263 \DeclareMathSymbol{\varpi}{\mathord}{letters}{24}
264 \DeclareMathSymbol{\varrho}{\mathord}{letters}{25}
265 \DeclareMathSymbol{\varsigma}{\mathord}{letters}{26}
266 \DeclareMathSymbol{\varphi}{\mathord}{letters}{27}
267 \DeclareMathSymbol{\Gamma}{\mathalpha}{operators}{00}
268 \DeclareMathSymbol{\Delta}{\mathalpha}{operators}{01}
269 \DeclareMathSymbol{\Theta}{\mathalpha}{operators}{02}
270 \DeclareMathSymbol{\Lambda}{\mathalpha}{operators}{03}
271 \DeclareMathSymbol{\Xi}{\mathalpha}{operators}{04}
272 \DeclareMathSymbol{\Pi}{\mathalpha}{operators}{05}
273 \DeclareMathSymbol{\Sigma}{\mathalpha}{operators}{06}
274 \DeclareMathSymbol{\Upsilon}{\mathalpha}{operators}{07}
275 \DeclareMathSymbol{\Phi}{\mathalpha}{operators}{08}
276 \DeclareMathSymbol{\Psi}{\mathalpha}{operators}{09}
277 \DeclareMathSymbol{\Omega}{\mathalpha}{operators}{0A}

```

#### 41.4.2 Ordinary symbols

```

278 \DeclareMathSymbol{\aleph}{\mathord}{symbols}{40}
279 \DeclareMathSymbol{\imath}{\mathord}{letters}{7B}
280 \DeclareMathSymbol{\jmath}{\mathord}{letters}{7C}
281 \DeclareMathSymbol{\ell}{\mathord}{letters}{60}
282 \DeclareMathSymbol{\wp}{\mathord}{letters}{7D}
283 \DeclareMathSymbol{\Re}{\mathord}{symbols}{3C}
284 \DeclareMathSymbol{\Im}{\mathord}{symbols}{3D}
285 \DeclareMathSymbol{\partial}{\mathord}{letters}{40}
286 \DeclareMathSymbol{\infty}{\mathord}{symbols}{31}
287 \DeclareMathSymbol{\prime}{\mathord}{symbols}{30}
288 \DeclareMathSymbol{\emptyset}{\mathord}{symbols}{3B}
289 \DeclareMathSymbol{\nabla}{\mathord}{symbols}{72}
290 \DeclareMathSymbol{\top}{\mathord}{symbols}{3E}
291 \DeclareMathSymbol{\bot}{\mathord}{symbols}{3F}
292 \DeclareMathSymbol{\triangle}{\mathord}{symbols}{34}
293 \DeclareMathSymbol{\forall}{\mathord}{symbols}{38}
294 \DeclareMathSymbol{\exists}{\mathord}{symbols}{39}
295 \DeclareMathSymbol{\neg}{\mathord}{symbols}{3A}
296 \let\not=\neg
297 \DeclareMathSymbol{\flat}{\mathord}{letters}{5B}
298 \DeclareMathSymbol{\natural}{\mathord}{letters}{5C}

```

```

299 \DeclareMathSymbol{\sharp}{\mathord}{letters}{"5D}
300 \DeclareMathSymbol{\clubsuit}{\mathord}{symbols}{"7C}
301 \DeclareMathSymbol{\diamondsuit}{\mathord}{symbols}{"7D}
302 \DeclareMathSymbol{\heartsuit}{\mathord}{symbols}{"7E}
303 \DeclareMathSymbol{\spadesuit}{\mathord}{symbols}{"7F}

304 \DeclareRobustCommand\hbar{{\mathchar'26\mkern-9muh}}
305 \DeclareRobustCommand\surd{{\mathchar"1270}}
306 \DeclareRobustCommand\angle{{\vbox{\ialign{$\m@th\scriptstyle##$\crrc
307     \not\mathrel{\mkern14mu}\crrc
308     \noalign{\nointerlineskip}
309     \mkern2.5mu\leaders\hrule \@height.34pt\hfill\mkern2.5mu\crrc}}}}

```

#### 41.4.3 Large Operators

```

310 \DeclareMathSymbol{\coprod}{\mathop}{largesymbols}{"60}
311 \DeclareMathSymbol{\bigvee}{\mathop}{largesymbols}{"57}
312 \DeclareMathSymbol{\bigwedge}{\mathop}{largesymbols}{"56}
313 \DeclareMathSymbol{\biguplus}{\mathop}{largesymbols}{"55}
314 \DeclareMathSymbol{\bigcap}{\mathop}{largesymbols}{"54}
315 \DeclareMathSymbol{\bigcup}{\mathop}{largesymbols}{"53}
316 \DeclareMathSymbol{\intop}{\mathop}{largesymbols}{"52}
317 \DeclareRobustCommand\int{\intop\nolimits}
318 \DeclareMathSymbol{\prod}{\mathop}{largesymbols}{"51}
319 \DeclareMathSymbol{\sum}{\mathop}{largesymbols}{"50}
320 \DeclareMathSymbol{\bigotimes}{\mathop}{largesymbols}{"4E}
321 \DeclareMathSymbol{\bigoplus}{\mathop}{largesymbols}{"4C}
322 \DeclareMathSymbol{\bigodot}{\mathop}{largesymbols}{"4A}
323 \DeclareMathSymbol{\ointop}{\mathop}{largesymbols}{"48}
324 \DeclareRobustCommand\oint{\ointop\nolimits}
325 \DeclareMathSymbol{\bigsqcup}{\mathop}{largesymbols}{"46}
326 \DeclareMathSymbol{\smallint}{\mathop}{symbols}{"73}

```

#### 41.4.4 Binary symbols

```

327 \DeclareMathSymbol{\triangleleft}{\mathbin}{letters}{"2F}
328 \DeclareMathSymbol{\triangleright}{\mathbin}{letters}{"2E}
329 \DeclareMathSymbol{\bigtriangleup}{\mathbin}{symbols}{"34}
330 \DeclareMathSymbol{\bigtriangledown}{\mathbin}{symbols}{"35}
331 \let \varbigtriangledown \bigtriangledown
332 \let \varbigtriangleup \bigtriangleup

```

These last two synonyms are needed because the `stamryrd` package redefines them as Operators.

```

333 \DeclareMathSymbol{\wedge}{\mathbin}{symbols}{"5E}
334 \let\land=\wedge
335 \DeclareMathSymbol{\vee}{\mathbin}{symbols}{"5F}
336 \let\lor=\vee
337 \DeclareMathSymbol{\cap}{\mathbin}{symbols}{"5C}
338 \DeclareMathSymbol{\cup}{\mathbin}{symbols}{"5B}
339 \DeclareMathSymbol{\ddagger}{\mathbin}{symbols}{"7A}
340 \DeclareMathSymbol{\dagger}{\mathbin}{symbols}{"79}
341 \DeclareMathSymbol{\sqcap}{\mathbin}{symbols}{"75}
342 \DeclareMathSymbol{\sqcup}{\mathbin}{symbols}{"74}
343 \DeclareMathSymbol{\uplus}{\mathbin}{symbols}{"5D}
344 \DeclareMathSymbol{\amalg}{\mathbin}{symbols}{"71}
345 \DeclareMathSymbol{\diamond}{\mathbin}{symbols}{"05}

```



```

346 \DeclareMathSymbol{\bullet}{\mathbin}{symbols}{"0F}
347 \DeclareMathSymbol{\wr}{\mathbin}{symbols}{"6F}
348 \DeclareMathSymbol{\div}{\mathbin}{symbols}{"04}
349 \DeclareMathSymbol{\odot}{\mathbin}{symbols}{"0C}
350 \DeclareMathSymbol{\oslash}{\mathbin}{symbols}{"0B}
351 \DeclareMathSymbol{\otimes}{\mathbin}{symbols}{"0A}
352 \DeclareMathSymbol{\ominus}{\mathbin}{symbols}{"09}
353 \DeclareMathSymbol{\oplus}{\mathbin}{symbols}{"08}
354 \DeclareMathSymbol{\mp}{\mathbin}{symbols}{"07}
355 \DeclareMathSymbol{\pm}{\mathbin}{symbols}{"06}
356 \DeclareMathSymbol{\circ}{\mathbin}{symbols}{"0E}
357 \DeclareMathSymbol{\bigcirc}{\mathbin}{symbols}{"0D}
358 \DeclareMathSymbol{\setminus}{\mathbin}{symbols}{"6E}
359 \DeclareMathSymbol{\cdot}{\mathbin}{symbols}{"01}
360 \DeclareMathSymbol{\ast}{\mathbin}{symbols}{"03}
361 \DeclareMathSymbol{\times}{\mathbin}{symbols}{"02}
362 \DeclareMathSymbol{\star}{\mathbin}{letters}{"3F}

```

#### 41.4.5 Relations

```

363 \DeclareMathSymbol{\propto}{\mathrel}{symbols}{"2F}
364 \DeclareMathSymbol{\sqsubseteq}{\mathrel}{symbols}{"76}
365 \DeclareMathSymbol{\sqsupseteq}{\mathrel}{symbols}{"77}
366 \DeclareMathSymbol{\parallel}{\mathrel}{symbols}{"6B}
367 \DeclareMathSymbol{\mid}{\mathrel}{symbols}{"6A}
368 \DeclareMathSymbol{\dashv}{\mathrel}{symbols}{"61}
369 \DeclareMathSymbol{\vdash}{\mathrel}{symbols}{"60}
370 \DeclareMathSymbol{\nearrow}{\mathrel}{symbols}{"25}
371 \DeclareMathSymbol{\searrow}{\mathrel}{symbols}{"26}
372 \DeclareMathSymbol{\nwarrow}{\mathrel}{symbols}{"2D}
373 \DeclareMathSymbol{\swarrow}{\mathrel}{symbols}{"2E}
374 \DeclareMathSymbol{\Leftrightarrow}{\mathrel}{symbols}{"2C}
375 \DeclareMathSymbol{\Leftarrow}{\mathrel}{symbols}{"28}
376 \DeclareMathSymbol{\Rightarrow}{\mathrel}{symbols}{"29}
377 \DeclareRobustCommand\neq{\not=}

```

As `\neq` is robust we should not use `\let` to define `\ne` as then then it would change if `\neq` changes.

```

378 %\let\ne=\neq
379 \DeclareRobustCommand\ne{\not=}

```

It is ok to use `\let` for those declared by `\DeclareMathSymbol`.

```

380 \DeclareMathSymbol{\leq}{\mathrel}{symbols}{"14}
381 \let\le=\leq
382 \DeclareMathSymbol{\geq}{\mathrel}{symbols}{"15}
383 \let\ge=\geq
384 \DeclareMathSymbol{\succ}{\mathrel}{symbols}{"1F}
385 \DeclareMathSymbol{\prec}{\mathrel}{symbols}{"1E}
386 \DeclareMathSymbol{\approx}{\mathrel}{symbols}{"19}
387 \DeclareMathSymbol{\succeeds}{\mathrel}{symbols}{"17}
388 \DeclareMathSymbol{\preceq}{\mathrel}{symbols}{"16}
389 \DeclareMathSymbol{\supseteq}{\mathrel}{symbols}{"1B}
390 \DeclareMathSymbol{\subset}{\mathrel}{symbols}{"1A}
391 \DeclareMathSymbol{\supseteq}{\mathrel}{symbols}{"13}
392 \DeclareMathSymbol{\subseteq}{\mathrel}{symbols}{"12}
393 \DeclareMathSymbol{\in}{\mathrel}{symbols}{"32}

```

```

394 \DeclareMathSymbol{\ni}{\mathrel}{symbols}{"33}
395   \let\owns=\ni
396 \DeclareMathSymbol{\gg}{\mathrel}{symbols}{"1D}
397 \DeclareMathSymbol{\ll}{\mathrel}{symbols}{"1C}
398 \DeclareMathSymbol{\not}{\mathrel}{symbols}{"36}
399 \DeclareMathSymbol{\leftrightharpoonup}{\mathrel}{symbols}{"24}
400 \DeclareMathSymbol{\leftarrow}{\mathrel}{symbols}{"20}
401   \let\gets=\leftarrow
402 \DeclareMathSymbol{\rightarrow}{\mathrel}{symbols}{"21}
403   \let\to=\rightarrow
404 \DeclareMathSymbol{\mapstochar}{\mathrel}{symbols}{"37}
405   \DeclareRobustCommand\mapsto{\mapstochar\rightarrow}
406 \DeclareMathSymbol{\sim}{\mathrel}{symbols}{"18}
407 \DeclareMathSymbol{\simeq}{\mathrel}{symbols}{"27}
408 \DeclareMathSymbol{\perp}{\mathrel}{symbols}{"3F}
409 \DeclareMathSymbol{\equiv}{\mathrel}{symbols}{"11}
410 \DeclareMathSymbol{\asymp}{\mathrel}{symbols}{"10}
411 \DeclareMathSymbol{\smile}{\mathrel}{letters}{"5E}
412 \DeclareMathSymbol{\frown}{\mathrel}{letters}{"5F}
413 \DeclareMathSymbol{\leftharpoonup}{\mathrel}{letters}{"28}
414 \DeclareMathSymbol{\leftharpoondown}{\mathrel}{letters}{"29}
415 \DeclareMathSymbol{\rightharpoonup}{\mathrel}{letters}{"2A}
416 \DeclareMathSymbol{\rightharpoondown}{\mathrel}{letters}{"2B}

```

Here cometh much profligate robustification of math constructs. Warning: some of these commands may become non-robust if an AMS package is loaded.

Further potential problems: some math font packages may make unfortunate assumptions about some of these definitions that are not true of the robust versions we need.

```

417 \DeclareRobustCommand
418   \cong{\mathrel{\mathpalette\@vereq\sim}} % congruence sign
419 \def\@vereq#1#2{\lower.5p\p@\vbox{\lineskiplimit\maxdimen\lineskip-.5p@
420   \ialign{\m@th#1\hfil##\hfil$\crrc#2\crrc=\crrc}}
421 \DeclareRobustCommand
422   \notin{\mathrel{\m@th\mathpalette\c@ncel\in}}
423 \def\c@ncel#1#2{\m@th\oalign{$\hfil#1\mkern1mu/\hfil$\crrc#1#2$}}
424 \DeclareRobustCommand
425   \rightleftharpoons{\mathrel{\mathpalette\rlh@{}}}
426 \def\rlh@#1{\vcenter{\m@th\hbox{\oalign{\raise2pt
427   \hbox{$#1\rightharpoonup$}\crrc
428   $#1\leftharpoondown$}}}}
429 \DeclareRobustCommand
430   \doteq{\buildrel\textstyle.\over=}

```

#### 41.4.6 Arrows

```

431 \DeclareRobustCommand
432   \joinrel{\mathrel{\mkern-3mu}}
433 \DeclareRobustCommand
434   \relbar{\mathrel{\smash-}} % \smash, because -
435   % has the same height as +

```

In contrast to `plain.tex` `\Relbar` got braces around the equal sign to guard against it being “math active” expanding to `\futurelet...`. This might be the case when packages are implementing shorthands for math, e.g. `=>` meaning `\Rightarrow` etc. It would actually be better not to use `=` in such definitions

but instead define something like `\mathequalsign` and use this. However we can't do this now as it would break other math layouts where characters are in different places (since those wouldn't know about the need for a new command name).

```

436 \DeclareRobustCommand
437   \Relbar{\mathrel{=}}
438 \DeclareMathSymbol{\lhook}{\mathrel}{letters}{"2C}
439   \DeclareRobustCommand\hookrightarrow{\lhook\joinrel\rightarrow}
440 \DeclareMathSymbol{\rhook}{\mathrel}{letters}{"2D}
441   \DeclareRobustCommand\hookleftarrow{\leftarrow\joinrel\rhook}
442 \DeclareRobustCommand
443   \bowtie{\mathrel{\triangleright\joinrel\mathrel{\triangleleft}}}
444 \DeclareRobustCommand
445   \models{\mathrel{||}\joinrel\Relbar}
446 \DeclareRobustCommand
447   \Longrightarrow{\Relbar\joinrel\rightarrow}

```

LaTeX Change: `\longrightarrow` and `\longleftarrow` redefined to make then robust.

```

448 \DeclareRobustCommand\longrightarrow
449   {\relbar\joinrel\rightarrow}
450 \DeclareRobustCommand\longleftarrow
451   {\leftarrow\joinrel\relbar}
452 \DeclareRobustCommand
453   \Longleftarrow{\Leftarrow\joinrel\Relbar}
454 \DeclareRobustCommand
455   \longmapsto{\mapstochar\longrightarrow}
456 \DeclareRobustCommand
457   \longleftrightharrow{\leftarrow\joinrel\rightarrow}
458 \DeclareRobustCommand
459   \Longleftrightharrow{\Leftarrow\joinrel\rightarrow}
460 \DeclareRobustCommand
461   \iff{\;\Longleftrightharrow\;}

```

#### 41.4.7 Punctuation symbols

```

462 \DeclareMathSymbol{\ldotp}{\mathpunct}{letters}{"3A}
463 \DeclareMathSymbol{\cdotp}{\mathpunct}{symbols}{"01}
464 \DeclareMathSymbol{\colon}{\mathpunct}{operators}{"3A}

```

This is commented out, since `\ldots` is now defined in `ltoutenc.dtx`.

```

465 %\def\@ldots{\mathinner{\ldotp\ldotp\ldotp}}
466 %\DeclareRobustCommand\ldots
467 %   {\relax\ifmmode\@ldots\else\mbox{$\m@th\@ldots$,}$\fi}
468 \DeclareRobustCommand
469   \cdots{\mathinner{\cdotp\cdotp\cdotp}}
470 \DeclareRobustCommand
471   \vdots{\vbox{\baselineskip4\p@ \lineskiplimit\z@
472     \kern6\p@\hbox{.}\hbox{.}\hbox{.}}}
473 \DeclareRobustCommand
474   \ddots{\mathinner{\mkern1mu\raise7\p@
475     \vbox{\kern7\p@\hbox{.}}\mkern2mu
476     \raise4\p@\hbox{.}\mkern2mu\raise\p@\hbox{.}\mkern1mu}}

```

#### 41.4.8 Math accents

```

477 \DeclareMathAccent{\acute}{\mathalpha}{operators}{"13}

```

```

478 \DeclareMathAccent{\grave}{\mathalpha}{operators}{12}
479 \DeclareMathAccent{\ddot}{\mathalpha}{operators}{7F}
480 \DeclareMathAccent{\tilde}{\mathalpha}{operators}{7E}
481 \DeclareMathAccent{\bar}{\mathalpha}{operators}{16}
482 \DeclareMathAccent{\breve}{\mathalpha}{operators}{15}
483 \DeclareMathAccent{\check}{\mathalpha}{operators}{14}
484 \DeclareMathAccent{\hat}{\mathalpha}{operators}{5E}
485 \DeclareMathAccent{\vec}{\mathord}{letters}{7E}
486 \DeclareMathAccent{\dot}{\mathalpha}{operators}{5F}
487 \DeclareMathAccent{\widetilde}{\mathord}{largesymbols}{65}
488 \DeclareMathAccent{\widehat}{\mathord}{largesymbols}{62}

```

For some reason plain T<sub>E</sub>X never bothered to provide a ring accent in math (although it is available in the fonts), but since we got a request for it here we go:

```

489 \DeclareMathAccent{\mathring}{\mathalpha}{operators}{17}

```

#### 41.4.9 Radicals

```

490 \DeclareMathRadical{\sqrtsign}{symbols}{70}{largesymbols}{70}

```

#### 41.4.10 Over and under something, etc

```

491 \DeclareRobustCommand\overrightarrow[1]{\vbox{\m@th\ialign{##\crrc
492   \rightarrowfill\crrc\noalign{\kern-\p@ \nointerlineskip}
493   $\hfil\displaystyle{#1}\hfil$\crrc}}}
494 \DeclareRobustCommand\overleftarrow[1]{\vbox{\m@th\ialign{##\crrc
495   \leftarrowfill\crrc\noalign{\kern-\p@ \nointerlineskip}}%
496   $\hfil\displaystyle{#1}\hfil$\crrc}}}
497 \DeclareRobustCommand\overbrace[1]
498   {\mathop{\vbox{\m@th\ialign{##\crrc\noalign{\kern3\p@}%
499     \downbracefill\crrc\noalign{\kern3\p@ \nointerlineskip}}%
500     $\hfil\displaystyle{#1}\hfil$\crrc}}}\limits}
501 \DeclareRobustCommand\underbrace[1]{\mathop{\vtop{\m@th\ialign{##\crrc
502   $\hfil\displaystyle{#1}\hfil$\crrc
503   \noalign{\kern3\p@ \nointerlineskip}}%
504   \upbracefill\crrc\noalign{\kern3\p@}}}\limits}

```

(quite a waste of tokens, IMHO — Frank)

```

505 \DeclareRobustCommand\skew[3]
506   {\muskip\z@#1mu\divide\muskip\z@ \tw@ \mkern\muskip\z@
507   #2{\mkern-\muskip\z@#3}\mkern\muskip\z@}\mkern-\muskip\z@}{}}
508 \DeclareRobustCommand\rightarrowfill{$\m@th\smash-\mkern-7mu%
509   \cleaders\hbox{$\mkern-2mu\smash-\mkern-2mu$}\hfill
510   \mkern-7mu\mathord\rightarrow$}
511 \DeclareRobustCommand\leftarrowfill{$\m@th\mathord\leftarrow\mkern-7mu%
512   \cleaders\hbox{$\mkern-2mu\smash-\mkern-2mu$}\hfill
513   \mkern-7mu\smash-$}
514 \DeclareMathSymbol{\braceld}{\mathord}{largesymbols}{7A}
515 \DeclareMathSymbol{\bracerd}{\mathord}{largesymbols}{7B}
516 \DeclareMathSymbol{\bracelu}{\mathord}{largesymbols}{7C}
517 \DeclareMathSymbol{\braceru}{\mathord}{largesymbols}{7D}
518 \DeclareRobustCommand\downbracefill{$\m@th \setbox\z@\hbox{$\braceld$}%
519   \braceld\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\braceru
520   \bracelu\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\bracerd$}
521 \DeclareRobustCommand\upbracefill{$\m@th \setbox\z@\hbox{$\braceld$}%
522   \bracelu\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\bracerd

```

```
523 \braced\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\braceru$}
```

#### 41.4.11 Delimiters

```
524 \DeclareMathDelimiter{\lmoustache} % top from (, bottom from )
525 {\mathopen}{largesymbols}{"7A}{largesymbols}{"40}
526 \DeclareMathDelimiter{\rmoustache} % top from ), bottom from (
527 {\mathclose}{largesymbols}{"7B}{largesymbols}{"41}
528 \DeclareMathDelimiter{\arrowvert} % arrow without arrowheads
529 {\mathord}{symbols}{"6A}{largesymbols}{"3C}
530 \DeclareMathDelimiter{\Arrowvert} % double arrow without arrowheads
531 {\mathord}{symbols}{"6B}{largesymbols}{"3D}
532 \DeclareMathDelimiter{\Vert}
533 {\mathord}{symbols}{"6B}{largesymbols}{"0D}
```

`\DeclareMathDelimiter` produces a command that is robust (with an internal macro containing the payload) so we should not use `\let` for making an alias

```
534 %\let\l=\Vert
535 \DeclareMathDelimiter{\l}
536 {\mathord}{symbols}{"6B}{largesymbols}{"0D}
537 \DeclareMathDelimiter{\vert}
538 {\mathord}{symbols}{"6A}{largesymbols}{"0C}
539 \DeclareMathDelimiter{\uparrow}
540 {\mathrel}{symbols}{"22}{largesymbols}{"78}
541 \DeclareMathDelimiter{\downarrow}
542 {\mathrel}{symbols}{"23}{largesymbols}{"79}
543 \DeclareMathDelimiter{\updownarrow}
544 {\mathrel}{symbols}{"6C}{largesymbols}{"3F}
545 \DeclareMathDelimiter{\Uparrow}
546 {\mathrel}{symbols}{"2A}{largesymbols}{"7E}
547 \DeclareMathDelimiter{\Downarrow}
548 {\mathrel}{symbols}{"2B}{largesymbols}{"7F}
549 \DeclareMathDelimiter{\Updownarrow}
550 {\mathrel}{symbols}{"6D}{largesymbols}{"77}
551 \DeclareMathDelimiter{\backslash} % for double coset G\backslash H
552 {\mathord}{symbols}{"6E}{largesymbols}{"0F}
553 \DeclareMathDelimiter{\rangle}
554 {\mathclose}{symbols}{"69}{largesymbols}{"0B}
555 \DeclareMathDelimiter{\langle}
556 {\mathopen}{symbols}{"68}{largesymbols}{"0A}
557 \DeclareMathDelimiter{\rbrace}
558 {\mathclose}{symbols}{"67}{largesymbols}{"09}
559 \DeclareMathDelimiter{\lbrace}
560 {\mathopen}{symbols}{"66}{largesymbols}{"08}
561 \DeclareMathDelimiter{\rceil}
562 {\mathclose}{symbols}{"65}{largesymbols}{"07}
563 \DeclareMathDelimiter{\lceil}
564 {\mathopen}{symbols}{"64}{largesymbols}{"06}
565 \DeclareMathDelimiter{\rfloor}
566 {\mathclose}{symbols}{"63}{largesymbols}{"05}
567 \DeclareMathDelimiter{\lfloor}
568 {\mathopen}{symbols}{"62}{largesymbols}{"04}
```

`\lgroup` There are three plain T<sub>E</sub>X delimiters which are not fully supported by NFSS,  
`\rgroup` since they partly point into a bold cmr font. Allocating a full symbol font, just  
`\bracevert` to have three delimiters seems a bit too much given the limited space available.

For this reason only the extensible sizes are supported. If this is not desired one can use, without losing portability, define `\mathbf` and `\mathtt` as font symbol alphabet (setting up `cmr/bx/n` and `cmmt/m/n` as symbol fonts first) and modify the delimiter declarations to point with their small variant to those symbol fonts. (This is done in `oldlfont.dtx` so look there for examples.)

```
569 \DeclareMathDelimiter{\lgroup} % extensible ( with sharper tips
570     {\mathopen}{largesymbols}{"3A}{largesymbols}{"3A}
571 \DeclareMathDelimiter{\rgroup} % extensible ) with sharper tips
572     {\mathclose}{largesymbols}{"3B}{largesymbols}{"3B}
573 \DeclareMathDelimiter{\bracevert} % the vertical bar that extends braces
574     {\mathord}{largesymbols}{"3E}{largesymbols}{"3E}
```

## 41.5 Math versions of text commands

The `\mathunderscore` here is really a text definition, so it has been put back into `loutenc.dtx` (by Chris, 30/04/97) and should be removed from here.

These symbols are the math versions of text commands such as `\P`, `\$`, etc.

```
\mathparagraph These math symbols are not in plain TEX.
\mathsection 575 \DeclareMathSymbol{\mathparagraph}{\mathord}{symbols}{"7B}
\mathdollar 576 \DeclareMathSymbol{\mathsection}{\mathord}{symbols}{"78}
\mathsterling 577 \DeclareMathSymbol{\mathdollar}{\mathord}{operators}{"24}
\mathunderscore 578 \DeclareRobustCommand\mathsterling{\mathit{\mathchar"7024}}
579 \DeclareRobustCommand\mathunderscore{\kern.06em\vbox{\hrule\@width.3em}}

\mathellipsis This is plain TEX's \ldots.
580 \DeclareRobustCommand\mathellipsis{\mathinner{\ldotp\ldotp\ldotp}}%
```

## 41.6 Other special functions and parameters

### 41.6.1 Biggggg

```
581 \</math>
582 \<math | latexrelease>
583 \<latexrelease>\IncludeInRelease{2018/12/01}%
584 \<latexrelease>           {\Big}{Start LR-mode}%
585 \DeclareRobustCommand\big[1]{\leavevmode@ifvmode
586     {\hbox{$\left#1\vbox to8.5p@{\right.\n@space$}}}}
587 \DeclareRobustCommand\Big[1]{\leavevmode@ifvmode
588     {\hbox{$\left#1\vbox to11.5p@{\right.\n@space$}}}}
589 \DeclareRobustCommand\bigg[1]{\leavevmode@ifvmode
590     {\hbox{$\left#1\vbox to14.5p@{\right.\n@space$}}}}
591 \DeclareRobustCommand\Bigg[1]{\leavevmode@ifvmode
592     {\hbox{$\left#1\vbox to17.5p@{\right.\n@space$}}}}
593 \</math | latexrelease>
594 \<latexrelease>\EndIncludeInRelease
595 \<latexrelease>\IncludeInRelease{0000/00/00}%
596 \<latexrelease>           {\Big}{Start LR-mode}%
597 \<latexrelease>\def\big#1{{\hbox{$\left#1\vbox to8.5p@{\right.\n@space$}}}}
598 \<latexrelease>\def\Big#1{{\hbox{$\left#1\vbox to11.5p@{\right.\n@space$}}}}
599 \<latexrelease>\def\bigg#1{{\hbox{$\left#1\vbox to14.5p@{\right.\n@space$}}}}
600 \<latexrelease>\def\Bigg#1{{\hbox{$\left#1\vbox to17.5p@{\right.\n@space$}}}}
601 \<latexrelease>\EndIncludeInRelease
```

```

602 <*math>
603 \def\n@space{\nulldelimiterspace\z@ \m@th}

```

### 41.6.2 The log-like functions

`\operator@font` The `\operator@font` determines the symbol font used for log-like functions.

```

604 \def\operator@font{\mathgroup\symoperators}

```

### 41.6.3 Parameters

```

605 \thinmuskip=3mu
606 \medmuskip=4mu plus 2mu minus 4mu
607 \thickmuskip=5mu plus 5mu

This finishes the low-level setup in fontmath.ltx.
608 </math>

```

## 42 Default cfg files

We provide default `cfg` files here to ensure that on installations that search large file trees we do not pick up some strange customisation files from somewhere.

```

609 <*cfgtext | cfgmath | cfgprel>
610 %%
611 %%
612 %%
613 %% Load the standard setup:
614 %%
615 <+cfgtext>\input{fonttext.ltx}
616 <+cfgmath>\input{fontmath.ltx}
617 <+cfgprel>\input{preload.ltx}
618 %%
619 %% Small changes could go here; see documentation in cfgguide.tex for
620 %% allowed modifications.
621 %%
622 %% In particular it is not allowed to misuse this configuration file
623 %% to modify internal LaTeX commands!
624 %%
625 %% If you use this file as the basis for configuration please change
626 %% the \ProvidesFile lines to clearly identify your modification, e.g.,
627 %%
628 <+cfgtext>%% \ProvidesFile{fonttext.cfg}[2001/06/01
629 <+cfgmath>%% \ProvidesFile{fonttext.cfg}[2001/06/01
630 <+cfgprel>%% \ProvidesFile{preload.cfg}[2001/06/01
631 %% Customised local font setup]
632 %%
633 %%
634 </cfgtext | cfgmath | cfgprel>

```

# File u

## preload.dtx

### 43 Overview

This file contains an number of possible settings for preloading fonts during installation of NFSS2 (which is used by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>). It will be used to generate the following files:

preload.min	minimal subset of fonts necessary to run NFSS2
preload.ori	preload of CM fonts similar to the old <code>lfonts.tex</code>
preload.ltx	The standard selection of preloads
cmpreloa.xpt	preload of CM fonts for 10pt document size
cmpreloa.xip	preload of CM fonts for 11pt document size
cmpreloa.xii	preload of CM fonts for 12pt document size
depreloa.xpt	preload of DC fonts for 10pt size
depreloa.xip	preload of DC fonts for 11pt size
depreloa.xii	preload of DC fonts for 12pt size

These files are for installations that make use of Computer Modern fonts either old encoding (OT1) or Cork encoding (T1). The Computer Modern fonts with Cork encoding are known as DC-fonts.

Most important is `preload.ltx` which is used during format generation. You are *not* allowed to change this file.

### 44 Customization

You can customize the preloaded fonts in your L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> system by installing a file with the name `preload.cfg`. If this file exists it will be used in place of the system file `preload.ltx`. You can, for example, copy one of the files mentioned above (that can be generated from this source) to `preload.cfg`.

Or you can define completely other preloads. In that case start from `preload.min` since that contains the fonts that have to be preloaded by *\*all\** L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> systems.

Avoid using `preload.ori`, it will load so many fonts that on most installations it is nearly impossible to load other font families afterwards. This file is only generated to show what fonts have been preloaded by L<sup>A</sup>T<sub>E</sub>X 2.09.

If you normally use other fonts than Computer Modern `preload.min` might be best.

**Warning:** If you preload fonts with encodings other than the normally supported encodings you have to declare that encoding in a `fontdef.cfg` configuration file (see the documentation in the file `fontdef.dtx`). Adding an extra encoding to the format might produce non-portable documents, thus this should be avoided if possible.



## 45 Module switches for the DOCSTRIP program

The DOCSTRIP will generate the above file from this source using the following module directives:

driver	produce a documentation driver file
preload	produce a preload...file
cm	for OT1 encoded Computer Modern
dc	for T1 encoded Computer Modern
min	produce minimal subset
xpt	produce 10pt preloads
xipt	produce 11pt preloads
xipt	produce 12pt preloads
ori	produce preloads similar to old <code>lfonts.tex</code>
tex	produce preload.ltx

A typical DOCSTRIP command file would then have entries like:

```
\generateFile{preload.min}{t}{\from{preload.dtx}{preload,min}}
```

for generating preload files.

## 46 A driver for this document

The next bit of code contains the documentation driver file for T<sub>E</sub>X, i.e., the file that will produce the documentation you are currently reading. It will be extracted from this file by the DOCSTRIP program.

```
1 (*driver)
2 \documentclass{ltxdoc}
3 %\OnlyDescription % comment out for implementation details
4 \begin{document}
5   \DocInput{preload.dtx}
6 \end{document}
7 \end{driver}
```

## 47 The code

We begin by loading the math extension font (cmex10) and the L<sup>A</sup>T<sub>E</sub>X line and circle fonts. It is necessary to do this explicitly since these are used by `lplain.tex` and `latex.tex`. Since the internal font name contains / characters and digits we construct the name via `\csname`. These are the only fonts (!) that must be loaded in this file.

All `\DeclarePreloadSizes` can be removed or others can be added, they only influence the processing speed.

```
8 \expandafter\font\csname OMX/cmex/m/n/10\endcsname=cmex10\relax
9 \font\tenln =line10 \font\tenlnw =linew10\relax
10 \font\tencirc=lcircle10 \font\tencircw=lcirclew10\relax
```

The above fonts should not be touched but anything below this point here in the preload suggestions can be modified without any problems.

```
11 (-tex)%*****
```

```

12 (-tex)% Start any modification below this point **
13 (-tex)%*****
14 (-tex)
15 %%
16 %% Computer Modern Roman:
17 %%-----
18 (*ori)
19 \DeclarePreloadSizes{OT1}{cmr}{m}{n}
20     {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74,24.88}
21 \DeclarePreloadSizes{OT1}{cmr}{bx}{n}{9,10,10.95,12,14.4,17.28}
22 \DeclarePreloadSizes{OT1}{cmr}{m}{sl}{10,10.95,12}
23 \DeclarePreloadSizes{OT1}{cmr}{m}{it}{7,8,9,10,10.95,12}
24 (/ori)
25 (+xpt & cm) \DeclarePreloadSizes{OT1}{cmr}{m}{n}{5,7,10}
26 (+xpt & dc) \DeclarePreloadSizes{T1}{cmr}{m}{n}{5,7,10}
27 (+xipt & cm) \DeclarePreloadSizes{OT1}{cmr}{m}{n}{6,8,10.95}
28 (+xipt & dc) \DeclarePreloadSizes{T1}{cmr}{m}{n}{6,8,10.95}
29 (+xipt & cm) \DeclarePreloadSizes{OT1}{cmr}{m}{n}{6,8,12}
30 (+xipt & dc) \DeclarePreloadSizes{T1}{cmr}{m}{n}{6,8,12}
31 %%
32 %% Computer Modern Sans:
33 %%-----
34 (+ori) \DeclarePreloadSizes{OT1}{cmss}{m}{n}{10,10.95,12}
35 %%
36 %% Computer Modern Typewriter:
37 %%-----
38 (+ori) \DeclarePreloadSizes{OT1}{cmtt}{m}{n}{9,10,10.95,12}
39 %%
40 %% Computer Modern Math:
41 %%-----
42 (*ori)
43 \DeclarePreloadSizes{OML}{cmm}{m}{it}
44     {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74}
45 \DeclarePreloadSizes{OMS}{cmsy}{m}{n}
46     {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74}
47 (/ori)

```

The math fonts are the same for both DC and CM fonts. So far there isn't an agreed on standard.

```

48 (*xpt)
49 \DeclarePreloadSizes{OML}{cmm}{m}{it}{5,7,10}
50 \DeclarePreloadSizes{OMS}{cmsy}{m}{n}{5,7,10}
51 (/xpt)
52 (*xipt)
53 \DeclarePreloadSizes{OML}{cmm}{m}{it}{6,8,10.95}
54 \DeclarePreloadSizes{OMS}{cmsy}{m}{n}{6,8,10.95}
55 (/xipt)
56 (*xiipt)
57 \DeclarePreloadSizes{OML}{cmm}{m}{it}{6,8,12}
58 \DeclarePreloadSizes{OMS}{cmsy}{m}{n}{6,8,12}
59 (/xiipt)
60 %%
61 %% LaTeX symbol fonts:
62 %%-----

```

```
63 <*ori>
64 \DeclarePreloadSizes{U}{lasy}{m}{n}
65      {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74}
66 </ori>
67 </preload>
```

# File v

## ltfntcmd.dtx

### Abstract

The commands defined in this file `ltfntcmd` are part of the kernel code for  $\text{\LaTeX 2}_{\epsilon}$ /NFSS2.

It is also meant to serve as documentation for package writers since it demonstrates how to define high-level font changing commands using a small number of creator functions.

## 48 Introduction

Font changes such as `\bfseries`, `\sffamily`, etc. are declarations; this means that their scope is delimited by the grouping structure, either by the next `\end` of some environment or by explicitly using a group, e.g., writing something like `{\bfseries...}` in the source. If you make the mistake of writing `\bfseries{...}` (thinking of `\bfseries` as a command with one argument) then the result is rather striking.

Font declarations are an artifact of the  $\text{\TeX}$  system and for several reasons it is better to avoid them on the user level whenever possible. In  $\text{\LaTeX 3}$  they will probably all be replaced by environments and by font commands taking one argument.

This file defines a creator function for such declarative font switches. This function creates commands which can be used in both math and text.

This file also defines a number of high-level commands (all starting with `\text..`) that have one argument and typeset this argument in the requested way. Thus these commands are for typesetting short pieces of text in a specific family, series or shape. These are all produced as examples of the use of a creator function which is itself also defined in this file.

Table 1 shows all these high-level commands in action. A further advantage of using these commands is that they automatically take care of any necessary italic correction on either side of their argument.

Thus, when using such commands, one does not have to worry about forgetting the italic correction when changing fonts. Only in very few situations is this additional space wrong but, for example, most typographers recommend omitting the italic correction if a small punctuation character, like a comma, directly follows the font change. Since the amount of correction required is partly a matter of taste, you can define in what situations the italic correction should be suppressed. This is done by putting the characters that should cancel a preceding italic correction in the list `\nocorrlist`.<sup>7</sup> The default definition for this list is produced by the following.

```
\newcommand \nocorrlist {,.}
```

---

<sup>7</sup>Any package that changes the `\catcode` of a character inside `\nocorrlist` must then explicitly reset the list. Otherwise the changed character will no longer be recognized by the suppression algorithm.

<i>Command</i>	<i>Corresponds to</i>	<i>Action</i>
<code>\textnormal{..}</code>	<code>\normalfont</code>	Typeset argument in normal family
<code>\textrm{..}</code>	<code>\rmfamily</code>	Typeset argument in roman family
<code>\textsf{..}</code>	<code>\sffamily</code>	Typeset argument in <b>sans serif</b> family
<code>\texttt{..}</code>	<code>\ttfamily</code>	Typeset argument in <b>typewriter</b> family
<code>\textmd{..}</code>	<code>\mdseries</code>	Typeset argument in medium series
<code>\textbf{..}</code>	<code>\bfseries</code>	Typeset argument in <b>bold</b> series
<code>\textup{..}</code>	<code>\upshape</code>	Typeset argument in normal shape
<code>\textit{..}</code>	<code>\itshape</code>	Typeset argument in <i>italic</i> shape
<code>\textsl{..}</code>	<code>\slshape</code>	Typeset argument in <i>slanted</i> shape
<code>\textsc{..}</code>	<code>\scshape</code>	Typeset argument in SMALL CAPS shape
<code>\emph{..}</code>	<code>\em</code>	Typeset argument <i>emphasized</i>

Table 1: Font-change commands with arguments

The font change commands provided here all start with `\text..` to emphasize that they are for use in normal text and to be easily memorable. They automatically take care of any necessary italic correction on either side of the argument.

It is best to declare the most often used characters first, because this will make the processing slightly faster. For example,

```
\emph{When using the \NFSS{ } high-level commands,
the \emph{proper} use of italic corrections is
automatically taken care of}. Only
\emph{sometimes} one has to help \LaTeX{ } by
adding a \verb=\nocorr= command.
```

which results in:

*When using the NFSS high-level commands, the proper use of italic corrections is automatically taken care of. Only sometimes one has to help L<sup>A</sup>T<sub>E</sub>X by adding a \nocorr command.*

In contrast, the use of the declaration forms is often more appropriate when you define your own commands or environments.

```
\newenvironment{bfitemize}{\begin{itemize}\normalfont\bfseries}
{\end{itemize}}
\begin{bfitemize}
\item This environment produces boldface items.
\item It is defined in terms of \LaTeX's
\texttt{itemize} environment and NFSS
declarations.
\end{bfitemize}
```

This gives:

- This environment produces boldface items.
- It is defined in terms of L<sup>A</sup>T<sub>E</sub>X's `itemize` environment and NFSS declarations.

In addition to global customization of when to insert the italic correction, it is of course sometimes necessary to explicitly insert one with `\/`.

It is also possible to suppress the italic correction in individual instances. For this, the command `\nocorr` is provided.

The `\nocorr` must appear as the first or last token inside the braces of the argument of the `\text...` commands, at that end of the text where you wish to suppress the italic correction.

It is worth pointing out here that inserting a `\/` in places where it can have no function (i.e. anywhere except immediately after a slanted letter) is not an error—it will just be silently ignored. Unfortunately this is not true if the redefinition of `\/` in `amstex.sty` is used as this version can cause space to be removed immediately before the `\/`.

## 49 The implementation

`\DeclareTextFontCommand` This is the creator function for `\text..` commands. It gives a warning if `\foo` or `\fragfoo` is already defined.

In math mode it simply puts the font declaration and text into a box (possibly an automagically sized one).

Otherwise it first scans the text to see where `\nocorr` occurs within it. This sets the `\check@ic` commands to do what is necessary concerning the italic correction at both ends.

The algorithm for deciding whether to put in an italic correction is not very subtle: one is added whenever the newly current font is not itself positively sloped, unless the next token is a character in the ‘nocorr’ list. At the end of the text this is done after closing the group so as to check the ‘outer font’. Note that this will often result in adding an italic correction token after a character in an unsloped font; we believe (in early 2003) that this is perhaps inefficient but not dangerous.

It also now checks for empty contents of the text command and optimises this case. Some care is also taken to check that doing dangerous things in vertical mode is avoided.

The italic correction token is added to the horizontal list before (in the list) an immediately preceding non-zero glob of glue (skip) and any non-zero penalty preceding that since, in the typical case, this puts it immediately after the last character in the preceding word.

Note that it is necessary to put in the `\aftergroup\maybe@ic` at the end of the group so that it comes after any other aftergroup tokens and immediately before the following tokens. It is also necessary to remove the `\fi` from the token list before the group ends; this is done by adding an `\expandafter` just before the closing brace.

```

1 (*2kernel)
2 \def \DeclareTextFontCommand #1#2{%
3   \DeclareRobustCommand#1[1]{%
4     \ifmode
5       \nfss@text{#2##1}%

```

```

6      \else
7      \hmode\bgroup
8      \text@command{##1}%
9      #2\check@icl ##1\check@icr
10     \expandafter
11     \egroup
12     \fi
13         }%
14 }

\textrm Now we define the \text{family} commands in terms of the above; \texttt does
\textsf not look very nice!
\texttt 15 \DeclareTextFontCommand{\textrm}{\rmfamily}
\textnormal 16 \DeclareTextFontCommand{\textsf}{\sffamily}
17 \DeclareTextFontCommand{\texttt}{\ttfamily}
18 \DeclareTextFontCommand{\textnormal}{\normalfont}

\textbf For the series attribute:
\textmd 19 \DeclareTextFontCommand{\textbf}{\bfseries}
20 \DeclareTextFontCommand{\textmd}{\mdseries}

\textit And for the shapes:
\textsl 21 \DeclareTextFontCommand{\textit}{\itshape}
\textsc 22 \DeclareTextFontCommand{\textsl}{\slshape}
\textup 23 \DeclareTextFontCommand{\textsc}{\scshape}
24 \DeclareTextFontCommand{\textup}{\upshape}

\emph Finally we have the \em font change declaration of LATEX. The corresponding
definition with argument is
25 \DeclareTextFontCommand{\emph}{\em}

\nocorr This is just a label, so it does nothing; it should also be unexpandable.
26 \let \nocorr \relax

\check@icl We define these defaults in case some error causes them to be expanded at the
\check@icr wrong time.
27 \let \check@icl \@empty
28 \let \check@icr \@empty

\text@command This checks for a \nocorr as the first token in its argument and also for one in
\check@nocorr@ any other position not protected within braces (the latter is treated as if it were
at the end of the argument).
Is this the correct action in the ‘empty’ case? It is efficient but typographically
it is, strictly, incorrect!
29 \def \text@command #1{%
30   \def \reserved@a {#1}%
31   \ifx \reserved@a \@empty
32     \let \check@icl \@empty
33     \let \check@icr \@empty
34   \else

```

`\space` is a reserved word in L<sup>A</sup>T<sub>E</sub>X or actually already in plain T<sub>E</sub>X. If somebody really redefines it so many things will break that I don't see any reason to make this routine here slower than necessary.

```

35 %    \def \reserved@b { }%
36 %    \ifx \reserved@a \reserved@b
37     \ifx \reserved@a \space
38         \let \check@ic1 \@empty
39         \let \check@icr \@empty
40     \else
41         \check@nocorr@ #1\@nocorr\@nil
42     \fi
43 \fi
44 }
45 \def \check@nocorr@ #1#2\@nocorr#3\@nil {%

```

The two checks are initialised here to their values in the normal case.

```

46 \let \check@ic1 \maybe@ic
47 \def \check@icr {\ifvmode \else \aftergroup \maybe@ic \fi}%
48 \def \reserved@a {\@nocorr}%
49 \def \reserved@b {#1}%
50 \def \reserved@c {#3}%
51 \ifx \reserved@a \reserved@b
52     \ifx \reserved@c \@empty

```

In this case there is a `\nocorr` at the start but not at the end, so `\check@ic1` should be empty.

```

53         \let \check@ic1 \@empty
54     \else

```

Otherwise there is a `\nocorr` both at the start and elsewhere, so no italic corrections should be added.

```

55         \let \check@ic1 \@empty
56         \let \check@icr \@empty
57     \fi
58 \else
59     \ifx \reserved@c \@empty

```

In this case there is no `\nocorr` anywhere, so we need to check for an italic correction at both the beginning and the end. This has been set up as the default so no code is needed here.

```

60     \else

```

In this case there is no `\nocorr` at the start but there is one elsewhere, so no `\aftergroup` is needed.

```

61         \let \check@icr \@empty
62     \fi
63 \fi
64 }

```

`\ifmaybe@ic` Switch used solely within `\maybe@ic` not interfering with other switches.

```

65 \newif\ifmaybe@ic

```

`\maybe@ic` These macros implement the italic correction.

```

\maybe@ic@
66 \def \maybe@ic {\futurelet\@let@token\maybe@ic@}
67 \def \maybe@ic@ {%

```



We first check to see if the current font is positively sloped. (But do not forget the message Rainer sent about an upright font with non-zero slope! Or is this an urban myth?) It has been suggested that this should test against a small positive value, but what?

```
68 \ifdim \fontdimen\@ne\font>\z@
69 \else
70 \maybe@ictrue
```

It would be possible, but probably not worthwhile, to continue the forward scan beyond any closing braces.

```
71 \expandafter\@tfor\expandafter\reserved@a\expandafter:\expandafter=%
72 \nocorrlist
```

We have to hide the `\@let@token` in the macro `\t@st@ic` rather than testing it directly in the loop since it might be `\let` to a `\fi` or `\else`, which would result in chaos.

```
73 \do \t@st@ic
```

Frank thinks that the next bit it is inefficient if done after the second change. Chris thinks that most all of this is inefficient for the commonest cases: but that is the price of a cleverer algorithm. It is certainly needed to deal with the use of `\nolinebreak`.

```
74 \ifmaybe@ic \sw@slant \fi
75 \fi
76 }
```

`\t@st@ic` The next token in the input stream is stored in `\@let@token` via a `\let`, the current token from `\nocorrlist` is stored via `\def` in `\reserved@a`. To compare them we have to fiddle around a bit.

If the only things to check were characters then this could be done via an `\if` thus their catcodes would not matter; but this will not work whilst `\futurelet` is used above.

```
77 \def \t@st@ic {%
78 \expandafter\let\expandafter\reserved@b\expandafter=\reserved@a\relax
79 \ifx\reserved@b\@let@token
```

If they are the same we record the fact and jump out of the loop.

```
80 \maybe@icfalse
81 \@break@tfor
82 \fi
83 }
```

`\sw@slant` The definition of the mysterious `\sw@slant` command is as follows.  
`\fix@penalty`

```
84 \def \sw@slant {%
```

It is surely correct to put in an italic correction when there is no skip. If the last thing on the list is actually a zero skip (including things whose dimension part is zero, such as `\hfill`), or anything other than a character, then the italic correction will have no effect.

In order to work correctly with unbreakable spaces from `~` (and other common forms of line-breaking control) we also move back across a penalty before the glue.

```
85 \ifdim \lastskip=\z@
86 \fix@penalty
```

```

87 \else
88   \skip@ \lastskip
89   \unskip
90   \fix@penalty
91   \hskip \skip@
92 \fi
93 }

```

The above code means: “If there is a non-zero space just before the current position (`\ifdim...`) save the amount of that space (`\skip@\lastskip`), remove it (`\unskip`), then do a similar thing if there is a penalty just before the skip, and finally put the space back in.”

Since zero glue cannot be distinguished in this context from no glue, we dare not put in an `\hskip` in this case as this may produce an unwanted breakpoint. This is not satisfactory.

The penalty before the glue is handled similarly, with the same caveats concerning the zero case. Is this the first recorded use of `\unpenalty` in standard L<sup>A</sup>T<sub>E</sub>X code?

```

94 \def \fix@penalty {%
95   \ifnum \lastpenalty=\z@
96     \@@italiccorr
97   \else
98     \count@ \lastpenalty
99     \unpenalty
100    \@@italiccorr
101    \penalty \count@
102 \fi
103 }

```

`\nocorrlist` This holds the list of characters that should prevent italic correction. They should be ordered by decreasing frequency of use. If any such character is made active later on one needs to redefine the list so that the active character becomes part of it.

```
104 \def \nocorrlist {,.}
```

`\nfss@text` This command will by default behave like a L<sup>A</sup>T<sub>E</sub>X `\mbox` but may be redefined by packages such as `amstext.sty` to be a bit cleverer.

```

105 \ifx \nfss@text\@undefined
106   \def \nfss@text {\leavevmode\hbox}
107 \fi

```

`\DeclareOldFontCommand` This is the function used to create declarative font-changing commands that can also be used to change alphabets in math-mode.

Usage: `\DeclareOldFontCommand \fn{<font-change decls>} <math-alphabet>`

Here `\fn` is the font-declaration command being defined, `<font-change decls>` is the declaration it will expand to in text-mode, and `<math-alphabet>` is the (single) math alphabet specifier which is to be used in math-mode.

It does not care whether the command being defined already exists but it does give a warning if it redefines anything.

Here are some typical examples of its use in conjunction with more basic NFSS2 font commands.

```
\DeclareOldFontCommand{\rm}{\normalfont\rmfamily}{\mathrm}
```

```

\DeclareOldFontCommand{\sf}{\normalfont\sffamily}{\mathsf}
\DeclareOldFontCommand{\tt}{\normalfont\ttfamily}{\mathtt}

108 \def \DeclareOldFontCommand #1#2#3{%
109   \DeclareRobustCommand #1{\@fontswitch {#2}{#3}}%
110 }

\@fontswitch These two commands actually do the necessary tests and declarative font- or
\@math@egroup alphabet-changing.
\@math@egroup
111 \def \@fontswitch #1#2{%
112   \ifmmode
113     \let \math@bgroup \relax
114     \def \math@egroup {\let \math@bgroup \@math@bgroup
115                       \let \math@egroup \@math@egroup}%

We need to have a \relax in the following line in case the #2 is something like
\mathsf grabbing the next token as an argument. For this reason the code also
uses explicit arguments again (see pr/1275).

116     #2\relax
117   \else
118     #1%
119   \fi
120 }
121 \let \@math@bgroup \math@bgroup
122 \let \@math@egroup \math@egroup

These commands are available only in the preamble.
123 \onlypreamble \DeclareTextFontCommand
124 \onlypreamble \DeclareOldFontCommand

```

## 50 Initialization

```

\normalsize This is defined to produce an error.
125 \def\normalsize{%
126   \@latex@error {The font size command \protect\normalsize\space
127                 is not defined:\MessageBreak
128                 there is probably something wrong with
129                 the class file}\@eha
130 }
131 \endkernel

```

File w

## ltpageno.dtx

### 51 Page Numbering

Page numbers are produced by a page counter, used just like any other counter. The only difference is that `\c@page` contains the number of the next page to be output (the one currently being produced), rather than one minus it. Thus, it is normally initialized to 1 rather than 0. `\c@page` is defined to be `\count0`, rather than a count assigned by `\newcount`.

`\pagenumbering` The user sets the pagenumber style with the `\pagenumbering{<foo>}` command, which sets the page counter to 1 and defines `\thepage` to be `\foo`. For example, `\pagenumbering{roman}` causes pages to be numbered i, ii, etc.

```
1 <*2kernel>
2 \message{page nos.,}

3 \countdef\c@page=0 \c@page=1
4 \def\c1@page{}
5 \def\pagenumbering#1{%
6   \global\c@page \c@one \gdef\thepage{\csname @#1\endcsname
7     \c@page}}
8 </2kernel>
```

File x

# ltxref.dtx

## 52 Cross Referencing

The user writes `\label{foo}` to define the following cross-references:

`\ref{foo}`: value of most recently incremented referencable counter. in the current environment. (Chapter, section, theorem and enumeration counters counters are referencable, footnote counters are not.)

`\pageref{foo}`: page number at which `\label{foo}` command appeared. where foo can be any string of characters not containing ‘\’, ‘{’ or ‘}’.

Note: The scope of the `\label` command is delimited by environments, so `\begin{theorem} \label{foo} ... \end{theorem} \label{bar}` defines `\ref{foo}` to be the theorem number and `\ref{bar}` to be the current section number.

Note: `\label` does the right thing in terms of spacing – i.e., leaving a space on both sides of it is equivalent to leaving a space on either side.

### 52.1 Cross Referencing

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
1 (*2ekernel)
2 \message{x-ref,}
```

This is implemented as follows. A referencable counter CNT is incremented by the command `\refstepcounter{CNT}`, which sets `@currentlabel == {CNT}{eval(\p@cnt\theCNT)}`. The command `\label{FOO}` then writes the following on file `\@auxout`:

```
\newlabel{FOO}{{eval(\@currentlabel)}{eval(\thepage)}}
```

```
\ref{FOO} ==
BEGIN
  if \r@foo undefined
  then @refundundefined := G T
    ??
    Warning: 'reference foo on page ... undefined'
  else \@car \eval(\r@FOO)\@nil
  fi
END
```

```
\pageref{foo} =
BEGIN
  if \r@foo undefined
  then @refundundefined := G T
    ??
    Warning: 'reference foo on page ... undefined'
  else \@cdr \eval(\r@FOO)\@nil
  fi
END
```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\labelformat` A reference via `\ref` produces by default the data associated with the corresponding `\label` command (typically a number); any additional formatting has to be provided by the user. If, for example, references to equations are always to be typeset as “equation (*number*)”, one has to code “`equation (\ref{key})`”. With `\labelformat` there is a possibility to generate such frills automatically without resorting to low-level coding. The command takes two arguments: the first is the name of a counter and the second is its representation when referenced. This means that for a successful usage, one has to know the counter name being used for generating the label, though in practice this should not pose a problem. The current counter number is picked up as an argument. Here are two examples:

```
\labelformat{section}{section~#1}
\labelformat{equation}{equation~(#1)}
```

`\Ref` A side effect of using `\labelformat` is that, depending on the defined formatting, it becomes impossible to use `\ref` at the beginning of a sentence (if its replacement text starts with a lowercase letter). To overcome this problem we introduce the command `\Ref` that behave like `\ref` except that it uppercases the first token of the generated string.

To make `\Ref` work properly the very first token in the second argument of `\labelformat` has to be a simple ASCII or UTF-8 letter, otherwise the capitalization will fail or worse, you will end up with some error messages. If you actually need something more complicated in this place (e.g., an accented letter not written as a UTF-8 character) you have to explicitly surround it with braces, to identify the part that needs to be capitalized. For example, for figure references in the Hungarian language you might want to write `\labelformat{figure}{\a'bra~\thefigure}` or use `\labelformat{figure}{ábra~\thefigure}` which avoids the brace problem.

`\G@refundefinedtrue` This does not save on name-space (since `\G@refundefinedfalse` was never needed) but it does make the implementation of such one-way switches more consistent. The extra macro to make the change is used since this change appears several times.

`\@refundefined`

**Note** despite its name, `\G@refundefinedtrue` does *not* correspond to an `\if` command, and there is no matching `...false`. It would be more natural to call the command `\G@refundefined` (as inspection of the change log will reveal) but unfortunately such a change would break any package that had defined a `\ref`-like command that mimicked the definition of `\ref`, calling `\G@refundefinedtrue`. Inspection of the T<sub>E</sub>X archives revealed several such packages, and so this command has been named `...true` so that the definition of `\ref` need not be changed, and the packages will work without change.

```
3 % \newif\ifG@refundefined
4 % \def\G@refundefinedtrue{\global\let\ifG@refundefined\iftrue}
5 % \def\G@refundefinedfalse{\global\let\ifG@refundefined\iffalse}
6 \def\G@refundefinedtrue{%
7   \gdef\@refundefined{%
8     \@latex@warning@no@line{There were undefined references}}
9 \let\@refundefined\relax
```

`\ref` Referencing a `\label`. RmS 91/10/25: added a few extra `\reset@font`, as suggested by Bernd Raichle  
`\pageref`  
`\setref` RmS 92/08/14: made `\ref` and `\pageref` robust  
RmS 93/09/08: Added setting of redefined switch.

```

10 \def\@setref#1#2#3{%
11   \ifx#1\relax
12     \protect\G@refundefinedtrue
13     \nfss@text{\reset@font\bfseries ??}%
14     \@latex@warning{Reference ‘#3’ on page \thepage \space
15                   undefined}%
16   \else
17     \expandafter#2#1\null
18   \fi}
19 \def\ref#1{\expandafter\@setref\csname r@#1\endcsname\@firstoftwo{#1}}
20 \def\pageref#1{\expandafter\@setref\csname r@#1\endcsname
21               \@secondoftwo{#1}}

```

`\newlabel` This command will be written to the `.aux` file to pass label information from one run to another.

`\@newl@bel` The internal form of `\newlabel` and `\bibcite`. Note that this macro does its work inside a group. That way the local assignments it needs to do don't clutter the save stack. This prevents large documents with many labels to run out of save stack.

```

22 \def\@newl@bel#1#2#3{%
23   \@ifundefined{#1#2}%
24     \relax
25     {\gdef \@multiplelabels {%
26       \@latex@warning@no@line{There were multiply-defined labels}}%
27       \@latex@warning@no@line{Label ‘#2’ multiply defined}}%
28   \global\@namedef{#1#2}{#3}}
29 \def\newlabel{\@newl@bel r}
30 \@onlypreamble\@newl@bel

```

`\if@multiplelabels` This is redefined to produce a warning if at least one label is defined more than once. It is executed by the `\enddocument` command.

```

31 \let \@multiplelabels \relax

```

`\label` The commands `\label` and `\refstepcounter` have been changed to allow `\protect`'ed commands to work properly. For example,

```

\def\thechapter{\protect\foo{\arabic{chapter}.\roman{section}}}

```

will cause a `\label{bar}` command to define `\ref{bar}` to expand to something like `\foo{4.d}`. Change made 20 Jul 88.

```

32 \def\label#1{\@bsphack
33   \protected@write\@auxout{%
34     {\string\newlabel{#1}{\@currentlabel}\thepage}}%
35   \@esphack}

36 \</2ekernel>
37 \<2ekernel | latexrelease>
38 \<latexrelease>\IncludeInRelease{2019/10/01}%
39 \<latexrelease>           {\refstepcounter}{Add \labelformat and \Ref}%

```

`\refstepcounter` Step the counter and allow for labels to point to its current value.

```
40 \def\refstepcounter#1{\stepcounter{#1}%  
41   \protected@edef\@currentlabel
```

By generating the second `csname` first the `\p@...` command can grab it as an argument which can be helpful for more complicated typesetting arrangements.

The trick is to ensure that `\csname the#1\endcsname` is turned into a single token before `\p@...` is expanded further. This way, if the `\p@...` command is a macro with one argument it will receive `\the...`. With the original kernel code (i.e., without the `\expandafter`) it will instead pick up `\csname` which would be disastrous.

Using `\expandafter` instead of braces delimiting the argument is better because, assuming that the `\p@...` command is not defined as a macro with one argument, the braces will stay and prohibit kerning that might otherwise happen between the glyphs generated by `\the...` and surrounding glyphs.

```
42     {\csname p@#1\expandafter\endcsname\csname the#1\endcsname}%  
43 }
```

`\labelformat` A shortcut to set the `\p@...` macro for a counter. It will pick up the counter representation as an argument so that it can be specially formatted.

```
44 \def\labelformat#1{\expandafter\def\csname p@#1\endcsname##1}
```

`\Ref` This macro expands the result of `\ref` and then uppercases the first token. Only useful if the label was generated via `\labelformat` and contains some lower case letter at its start. If the label starts with a complicated construct (e.g., an accented letter that is provided via a command, e.g., `\"a` instead of a UTF-8 character like ä) one has to surround everything that needs uppercasing in a brace group in the definition of `\labelformat`.<sup>8</sup>

```
45 \DeclareRobustCommand\Ref[1]{\protected@edef\@tempa{\ref{#1}}%  
46   \expandafter\MakeUppercase\@tempa}  
  
47 \if2ekernel\latexrelease  
48 \if\latexrelease\EndIncludeInRelease  
49 \if\latexrelease\IncludeInRelease{0000/00/00}%  
50 \if\latexrelease      {\refstepcounter}{Add \labelformat and \Ref}%  
51 \if\latexrelease  
52 \if\latexrelease\def\refstepcounter#1{\stepcounter{#1}%  
53 \if\latexrelease    \protected@edef\@currentlabel  
54 \if\latexrelease      {\csname p@#1\endcsname\csname the#1\endcsname}%  
55 \if\latexrelease}  
56 \if\latexrelease\let\labelformat\undefined  
57 \if\latexrelease\let\Ref\undefined  
58 \if\latexrelease  
59 \if\latexrelease\EndIncludeInRelease  
60 \if*2ekernel
```

`\@currentlabel` Default for `\label` commands that come before any environment.

```
61 \def\@currentlabel{}  
  
62 \if2ekernel
```

---

<sup>8</sup>There is one problem with this approach: the braces are kept in a normal `\ref` which might spoil kerning. Perhaps one day this needs redoing.



# File y

## ltnmiscen.dtx

### 53 Miscellaneous Environments

This section implements the basic environment mechanism, and also a few specific environments including `document`, The math environments and related commands, the ‘flushing’ environments, (`center`, `flushleft`, `flushright`), and `verbatim`.

```
1 (*2kernel)
2 \message{environments,}
```

#### 53.1 Environments

`\begin{foo}` and `\end{foo}` are used to delimit environment `foo`.

`\begin{foo}` starts a group and calls `\foo` if it is defined, otherwise it does nothing.

`\end{foo}` checks to see that it matches the corresponding `\begin` and if so, it calls `\endfoo` and does an `\endgroup`. Otherwise, `\end{foo}` does nothing.

If `\end{foo}` needs to ignore blanks after it, then `\endfoo` should globally set the `@ignore` switch true with `\@ignoretrue` (this will automatically be global).

NOTE: `\@@end` is defined to be the `\end` command of T<sub>E</sub>X82.

`\enddocument` is the user’s command for ending the manuscript file.

`\stop` is a panic button — to end T<sub>E</sub>X in the middle.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\enddocument ==
BEGIN
  \@checkend{document}    %% checks for unmatched \begin
  \clearpage
  \begingroup
  if @filesw = true
  then close file @mainaux
  if G@refundefined = true
  then LaTeX Warning: 'There are undefined references.' fi
  if @multiplelabels = true
  then LaTeX Warning:
    'One or more label(s) multiply defined.'
  else
    \setckpt {ARG1}{ARG2} == null
    \newlabel{LABEL}{VAL} ==
    BEGIN
      \reserved@a == VAL
      if def(\reserved@a) = def(\r@LABEL)
      else @tempwa := true      fi
    END
    \bible{LABEL}{VAL} == null
    BEGIN
      \reserved@a == VAL
      if def(\reserved@a) = def(\g@LABEL)
```

```

else @tempswa := true          fi
END
@tempswa := false
make @ a letter
\input \jobname.AUX
if @tempswa = true
then LaTeX Warning: 'Label may have changed.
                        Rerun to get cross-references right.'
fi
fi
\endgroup
finish up
END

\@writefile{EXT}{ENTRY} ==
if tf@EXT undefined
else \write\tf@EXT{ENTRY}
fi
End of historical LATEX 2.09 comments.

\@currenvir The name of the current environment.  Initialized to document to so that
\end{document} works correctly.
3 \def\@currenvir{document}

\if@ignore
\@ignoretrue 4 \def\@ignorefalse{\global\let\if@ignore\iffalse}
\@ignorefalse 5 \def\@ignoretrue {\global\let\if@ignore\iftrue}
6 \@ignorefalse

\ignorespacesafterend

7 \let\ignorespacesafterend\@ignoretrue

\enddocument

8 \def\enddocument{%
The \end{document} hook is executed first.  If necessary it can contain a
\clearpage to output dangling floats first.  In this position it can also contain
something like \end{foo} so that the whole document effectively starts and ends
with some special environment.  However, this must be used with care, eg if two
applications would use this without knowledge of each other the order of the en-
vironments will be wrong after all.  \AtEndDocument is redefined at this point so
that and such commands that get into the hook do not chase their tail...

9 \let\AtEndDocument\@firstofone
10 \@enddocumenthook
11 \@checkend{document}%
12 \clearpage
13 \begingroup
14 \if@filesw
15 \immediate\closeout\@mainaux
16 \let\@setckpt\@gobbletwo
17 \let\@newl@bel\@testdef

```

The previous line is equiv to setting

```
\def\newlabel{\@testdef r}%
\def\bibcite{\@testdef b}%
```

We use `\@input` to load the `.aux` file, so that it doesn't show up in the list of files produced by `\listfiles`.

```
18      \@tempswafalse
19      \makeatletter \@input\jobname.aux
20      \fi

21      \@dofilelist
```

First we check for font size substitution bigger than `\fontsubfuzz`. The `\relax` is necessary because this is a macro not a register.

```
22      \ifdim \font@submax >\fontsubfuzz\relax
```

In case you wonder about the `\@gobbletwo` inside the message below, this is a horrible hack to remove the tokens `\on@line`. that are added by `\@font@warning` at the end.

```
23      \@font@warning{Size substitutions with differences\MessageBreak
24                      up to \font@submax\space have occurred.\@gobbletwo}%
25      \fi
```

The macro `\@defaultsubs` is initially `\relax` but gets redefined to produce a warning if there have been some default font substitutions.

```
26      \@defaultsubs
```

The macro `\@refundefined` is initially `\relax` but gets redefined to produce a warning if there are undefined refs.

```
27      \@refundefined
```

If a label is defined more than once, `\@tempswa` will always be true and thus produce a “Label(s) may ...” warning. But since a rerun will not solve that problem (unless one uses a package like `varioref` that generates labels on the fly), we suppress this message.

```
28      \if@filesw
29      \ifx \@multiplelabels \relax
30      \if@tempswa
31      \@latex@warning@no@line{Label(s) may have changed.
32      Rerun to get cross-references right}%
33      \fi
34      \else
35      \@multiplelabels
36      \fi
37      \fi
38      \endgroup
39      \deadcycles\z@\@end}
```

```
\@testdef
```

```
40 \def\@testdef #1#2#3{%
41   \def\reserved@a{#3}\expandafter \ifx \csname #1#2\endcsname
42   \reserved@a \else \@tempswatrue \fi}
```

Reading data from auxiliary files (like `.toc` normally happens in vertical mode and it therefore doesn't matter if line endings are converted to spaces by `TeX` during that process.

However, especially the `.toc` file might be read in L-R mode (in cases the `\tableofcontents` attempts to put, say a list of sub-sections as a paragraph. In that case the newlines after a line like

```
\contentsline {subsubsection}{\numberline {1.1.1}A C-head}{2}
```

might result in spurious spaces (e.g., when that level is not included).

That could be fixed by reading in the file using `\endlinechar=-1` but that has the danger that it drops some valid endlines that should be converted to spaces (for example when the user edited the TOC and then used `\nofiles` to preserve it.

So the approach taken instead is this:

- `\addcontentsline` adds the command `\protected@file@percent` to the end of the second argument of `\@writefile` that is written to the `.aux`. As the name indicates this is a protected macro so it doesn't change if it is written out.
- When the `.aux` is read back in at the end of the run, `\@writefile` is executed and writes its second argument unmodified to the file with the extension given by its first argument. Or rather that was how it was in the past.
- Instead we change `\@writefile` slightly: basically it looks at the second argument and if the last token in there is `\protected@file@percent` then it is replaced by a percent character and that is then written out. If not (for example, if the data came from a user issued `\addtocontents`, or from some package that uses `\@writefile` for writing its own files) then the command behaves exactly as before.

`\protected@file@percent` Dummy cs to be replaced by a percent sign inside `\@writefile`. If it survives (when used incorrectly) it will expand to nothing in a typesetting context.

```
43 \</2kernel>
44 (*2kernel | latexrelease)
45 (latexrelease)\IncludeInRelease{2018/12/01}%
46 (latexrelease)          {\protected@file@percent}{Mask line endings}%
47 \protected\def\protected@file@percent{}
```

`\add@percent@to@temptokena` Helper function which is used to inspect a sequence of tokens (the second argument of `\@writefile` and if the last token is `\protected@file@percent` it will replace it by a harmless percent. The result is saved in `\@temptokena` for later use.

```
48 \catcode'\^^A=9
49 \long\gdef\add@percent@to@temptokena
50   #1\protected@file@percent#2\add@percent@to@temptokena
```

When we call this macro in `\@writefile` we stick in `\@empty` at the beginning, so that in case the tokenlist consists of a single brace group the braces aren't stripped. The `\expandafter` then expands this extra token away again.

```
51   {\expandafter\ifx\expandafter X\detokenize{#2}X\expandafter\dontadd@percent@to@temptokena
52     \expandafter\doadd@percent@to@temptokena\fi{#1}}
```

```

53 \long\def\dont@add@percent@to@temptokena#1{%
54   \@temptokena\expandafter{#1}}

```

`latexrelease` will read this code in high-speed mode in certain situations. During that it will only look for `\if` tests but not actually execute the `\catcode` change above. As a result it will drop anything after the `%` character in the definition. Therefore the `\fi` needs to be on the next line and we need locally another comment character to avoid getting spaces into the definition—a weird problem :-)

```

55 \begingroup
56 \catcode'\%=12
57 \catcode'\^^A=14
58 \long\gdef\do@add@percent@to@temptokena#1{\@temptokena\expandafter{#1%\^^A

```

Can't be on the same line as the `%` — see above.

```

59   }}
60 \endgroup

```

`\@writefile`

```

61 \long\def\@writefile#1#2{%
62   \@ifundefined{tf@#1}\relax
63   {%

```

If we write to the file we first prepare `#2` using `\add@percent@to@temptokena` and then write the token register out.

```

64     \add@percent@to@temptokena
65     \@empty#2\protected@file@percent
66     \add@percent@to@temptokena
67     \immediate\write\csname tf@#1\endcsname{\the\@temptokena}%
68   }%
69 }

70 \if2kernel | latexrelease)
71 \if2kernel | latexrelease)\EndIncludeInRelease
72 \if2kernel | latexrelease)\IncludeInRelease{0000/00/00}%
73 \if2kernel | latexrelease)      {\protected@file@percent}{Mask line endings}%
74 \if2kernel | latexrelease)\let\protected@file@percent\@undefined
75 \if2kernel | latexrelease)\let\add@percent@to@temptokena\@undefined
76 \if2kernel | latexrelease)\let\do@add@percent@to@temptokena\@undefined
77 \if2kernel | latexrelease)\let\dont@add@percent@to@temptokena\@undefined
78 \if2kernel | latexrelease)\long\def\@writefile#1#2{%
79 \if2kernel | latexrelease)  \@ifundefined{tf@#1}\relax
80 \if2kernel | latexrelease)    {\@temptokena{#2}}%
81 \if2kernel | latexrelease)    \immediate\write\csname tf@#1\endcsname{\the\@temptokena}%
82 \if2kernel | latexrelease)    }%
83 \if2kernel | latexrelease)}
84 \if2kernel | latexrelease)\EndIncludeInRelease
85 \if2kernel |

```

`\stop`

```

86 \def\stop{\clearpage\deadcycles\z@\let\par\@par\@end}

```

*Historical  $\LaTeX$  2.09 comments (not necessarily accurate any more):*

```

87 \everypar{\@nodocument} %% To get an error if text appears before the

```

```

88 \nullfont                %% \begin{document}

\begin, \end, and \@checkend changed so \end{document} will catch
an unmatched \begin.  Changed 24 May 89 as suggested by
Frank Mittelbach and Rainer Sch\"opf.

\begin{NAME} ==
BEGIN
  IF \NAME undefined THEN \reserved@a == BEGIN report error
END
                                ELSE \reserved@a ==
                                (\@currenvir :=L NAME) \NAME
  FI
  @ignore :=G F                %% Added 30 Nov 88
  \begingroup
  \@endpe := F
  \@currenvir :=L NAME
  \NAME
END

\end{NAME} ==
BEGIN
  \endNAME
  \@checkend{NAME}
  \endgroup
  IF \@endpe = T                %% \@endpe set True by \@endparenv
    THEN \@doendpe              %% \@doendpe redefines \par and
\everypar                      %% to suppress paragraph indentation in
                                %% immediately following text
  FI
  IF @ignore = T
    THEN @ignore :=G F
    \ignorespaces
  FI
END

\@checkend{NAME} ==
BEGIN
  IF \@currenvir = NAME
    ELSE \@badend{NAME}
  FI
END

End of historical LATEX 2.09 comments.

\begin
89 </2kernel>
90 <*2kernel | latexrelease>
91 <latexrelease>\IncludeInRelease{2019/10/01}%
92 <latexrelease>                {\begin}{Making \begin/\end robust}%
93 \DeclareRobustCommand\begin[1]{%

```

```

94 \ifundefined{#1}%
95   {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
96   {\def\reserved@a{\def\@currentvir{#1}%
97     \edef\@currentvline{\on@line}%
98     \csname #1\endcsname}}%
99 \ignorefalse
100 \begingroup\@endpfalse\reserved@a}

```

A version that doesn't start out with `\relax` when in typesetting mode would be the following, but since `\begin` issues a `\begingroup` it wouldn't help much with respect to allowing things like `\noalign` or `\multicolumn` inside.

```

101 %\edef\begin
102 %  {\unexpanded{%
103 %    \ifx\protect\@typeset@protect
104 %      \expandafter\@gobble
105 %    \fi
106 %    \protect
107 %  }}%
108 %  \expandafter\noexpand\csname begin \endcsname
109 % }
110 %\@namedef{begin }#1{%
111 %  \ifundefined{#1}%
112 %    {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
113 %    {\def\reserved@a{\def\@currentvir{#1}%
114 %      \edef\@currentvline{\on@line}%
115 %      \csname #1\endcsname}}%
116 %  \ignorefalse
117 %  \begingroup\@endpfalse\reserved@a}

```

`\end` While `\begin` was made robust simply by using `\DeclareRobustCommand` we need to be a bit more subtle with `\end` as there are packages out there that try to look into the top-level contents of `\end{foo}` (that is at the expansion of `\endfoo`) to see if it contains certain macros. This is done by hitting `\end{foo}` with three `\expandafters`, the first to get

```
\csname endfoo\endcsname \checkend{foo}% etc.
```

the second to expand the `\csname`, i.e., to get to

```
\endfoo \checkend{foo}% etc.
```

and the third to finally get to the top-level content of `\endfoo`, i.e.

```
<top-level content of \endfoo> \checkend{foo}% etc.
```

Therefore a robust replacement should produce the same results after three expansions (there first is obviously different).

Basically the definition of `\end` should either produce `\protect\end␣` (when not doing typesetting) or it should produce `\end␣` (without the `\protect`) when doing typesetting. Furthermore, it should (when in typesetting mode) show exactly the same result as `\end␣` (which is the original fragile definition of `\end`) when you expand either of them twice, i.e.,

```
\endfoo \checkend{foo}% etc.
```

That is achieved with the code below (which is worth studying carefully).

There is some trickery involved here: in particular we use `\romannumeral` to change a single expansion into three successive expansions in one go. That primitive expands until it has scanned a number (0 in this case, so it doesn't produce any output) and so it allows us to place arbitrary many `\expandafters` inside that are all going to be executed when `\romannumeral` is hit by a single `\expandafter`.

```

118 \edef\end
119   {\unexpanded{%
120     \romannumeral
121     \ifx\protect\@typeset@protect
122       \expandafter      %1
123       \expandafter      %2
124       \expandafter      %1
125       \expandafter      %3 expands the \csname inside \end<space>
126       \expandafter      %1
127       \expandafter      %2 expands \end<space>
128       \expandafter      %1 expands the \else
129       \z@
130     \else
131       \expandafter\z@\expandafter\protect
132     \fi
133   }%
134   \expandafter\noexpand\csname end \endcsname
135 }

```

And here is the original definition of `\end` the way it was in L<sup>A</sup>T<sub>E</sub>X for several decades now hidden in `\end_`.

```

136 \@namedef{end }#1{%
137   \csname end#1\endcsname\@checkend{#1}%
138   \expandafter\endgroup\if@endpe\@doendpe\fi
139   \if@ignore\@ignorefalse\ignorespaces\fi}
140 </2ekernel | latexrelease>
141 <latexrelease>\EndIncludeInRelease

```

And here the rollback in case that is ever needed.

```

142 <latexrelease>\IncludeInRelease{0000/00/00}%
143 <latexrelease>          {\begin}{Making \begin/\end robust}%
144 <latexrelease>\kernel@make@fragile\begin
145 <latexrelease>\kernel@make@fragile\end
146 <latexrelease>
147 <latexrelease>\EndIncludeInRelease
148 <*2ekernel>

```

`\@checkend`

```

149 \def\@checkend#1{\def\reserved@a{#1}\ifx
150   \reserved@a\@currenvir \else\@badend{#1}\fi}

```

`\@currenvline` We do need a default value for `\@currenvline` on top-level since the document environment cancels the brace group. This means that a mismatch with `\begin{document}` will not produce a line number. Thus the outer default must be `\@empty` or we will end up with two spaces.

```

151 \let\@currenvline\@empty

```



## 53.2 Center, Flushright, Flushleft

152 \message{center,}

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\center, \flushright and \flushleft set
  \rightskip = 0pt or \@flushglue (as appropriate)
  \leftskip  = 0pt or \@flushglue (as appropriate)
  \parindent = 0pt
  \parfillskip = 0pt. (except \flushleft)
  \l = \par \vskip -\parskip
  \l[LENGTH] == \l \vskip LENGTH
  \l* == \par \penalty 10000 \vskip -\parskip
  \l*[LEN] == \l* \vskip LENGTH
```

They invoke the `trivlist` environment to handle vertical spacing before and after them.

`\centering`, `\raggedright` and `\raggedleft` are the declaration analogs of the above.

`\raggedright` has a more universal effect, however. It sets `\@rightskip := flushglue`. Every environment, like the list environments, that set `\rightskip` to its 'normal' value set it to `\@rightskip`

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\@centercr`

```
153 \</2kernel>
154 \<*2kernel | latexrelease>
155 \<latexrelease>\IncludeInRelease{2020/02/01}%
156 \<latexrelease> \<\@centercr>\Make robust}%
157 \protected\def\@centercr{\ifhmode \unskip\else \<\nolnerr\fi
158 \par\@ifstar{\nobreak\<\xcentercr>\<\xcentercr>}
159 \</2kernel | latexrelease>
160 \<latexrelease>\EndIncludeInRelease
161 \<latexrelease>\IncludeInRelease{0000/00/00}%
162 \<latexrelease> \<\@centercr>\Make robust}%
163 \<latexrelease>
164 \<latexrelease>\def\@centercr{\ifhmode \unskip\else \<\nolnerr\fi
165 \<latexrelease> \par\@ifstar{\nobreak\<\xcentercr>\<\xcentercr>}
166 \<latexrelease>
167 \<latexrelease>\EndIncludeInRelease
168 \<*2kernel>
```

`\@xcentercr`

```
169 \def\@xcentercr{\addvspace{-\parskip}\@ifnextchar
170 [\@icentercr\ignorespaces}
```

`\@icentercr`

```
171 \def\@icentercr[#1]{\vskip #1\ignorespaces}
```

```

center We use \relax to prevent \item scanning too far.
172 \def\center{\trivlist \centering\item\relax}
173 \def\endcenter{\endtrivlist}

174 \if2kernel
175 \if*2kernel | latexrelease
176 \if latexrelease \IncludeInRelease{2019/10/01}%
177 \if latexrelease {\centering}{Make commands robust}%

\centering
178 \DeclareRobustCommand\centering{%
179 \let\\@centercr
180 \rightskip\@flushglue\leftskip\@flushglue
181 \parindent\z@\parfillskip\z@skip}

\raggedright
182 \DeclareRobustCommand\raggedright{%
183 \let\\@centercr\@rightskip\@flushglue \rightskip\@rightskip
184 \leftskip\z@skip
185 \parindent\z@}

\raggedleft
186 \DeclareRobustCommand\raggedleft{%
187 \let\\@centercr
188 \rightskip\z@skip\leftskip\@flushglue
189 \parindent\z@\parfillskip\z@skip}

190 \if2kernel | latexrelease
191 \if latexrelease \EndIncludeInRelease
192 \if latexrelease \IncludeInRelease{0000/00/00}%
193 \if latexrelease {\centering}{Make commands robust}%
194 \if latexrelease
195 \if latexrelease \kernel@make@fragile\centering
196 \if latexrelease \kernel@make@fragile\raggedright
197 \if latexrelease \kernel@make@fragile\raggedleft
198 \if latexrelease
199 \if latexrelease \EndIncludeInRelease
200 \if*2kernel

\@rightskip
201 \newskip\@rightskip \@rightskip \z@skip

flushleft We use \relax to prevent \item scanning too far.
202 \def\flushleft{\trivlist \raggedright\item\relax}
203 \def\endflushleft{\endtrivlist}

flushright We use \relax to prevent \item scanning too far.
204 \def\flushright{\trivlist \raggedleft\item\relax}
205 \def\endflushright{\endtrivlist}

```

### 53.3 Verbatim

206 \message{verbatim,}

The verbatim environment uses the fixed-width `\ttfamily` font, turns blanks into spaces, starts a new line for each carriage return (or sequence of consecutive carriage returns), and interprets *every* character literally. I.e., all special characters `\`, `{`, `$`, etc. are `\catcode`'d to 'other'.

The command `\verb` produces in-line verbatim text, where the argument is delimited by any pair of characters. E.g., `\verb #...#` takes '...' as its argument, and sets it verbatim in `\ttfamily` font.

The \*-variants of these commands are the same, except that spaces print as the TeXbook's space character instead of as blank spaces.

\@vobeyspaces

207 {\catcode'\ =\active%

208 \gdef\@vobeyspaces{\catcode'\ \active\let \@xobeysp}}

\@xobeysp

\@xverbatim

\@sxverbatim

```
209 \begingroup \catcode '='0 \catcode '['= 1
210 \catcode']=2 \catcode '{=12 \catcode '\}=12
211 \catcode'\=12 \gdef\@xverbatim#1\end{verbatim}[#1\end[verbatim]]
212 \gdef\@sxverbatim#1\end{verbatim*}[#1\end[verbatim*]]
213 \endgroup
```

\@verbatim Real start of verbatim environment We use `\relax` to prevent `\item` scanning too far.

```
214 \</2kernel>
215 \*2kernel| latexrelease>
216 \<latexrelease>\IncludeInRelease{2017-04-15}{\@verbatim}%
217 \<latexrelease> {Disable hyphenation in verbatim}%
218 \def\@verbatim{\trivlist \item\relax
219 \if@minipage\else\vskip\parskip\fi
220 \leftskip\@totalleftmargin\rightskip\z@skip
221 \parindent\z@\parfillskip\@flushglue\parskip\z@skip
```

Added `\@@par` to clear possible `\parshape` definition from a surrounding list (the verbatim guru says). Switch language when in vertical mode.

222 \@@par

Set `\language` here to suppress hyphenation. Done this way rather than setting `\hyphenchar` as that is a global setting.

```
223 \language\l@nohyphenation
224 \@tempswafalse
225 \def\par{%
226 \if@tempswa
```

A `\leavevmode` added: needed if, for example, a blank verbatim line is the first thing in a list item (wow!).

```
227 \leavevmode \null \@@par\penalty\interlinepenalty
228 \else
229 \@tempswatrue
230 \ifhmode\@@par\penalty\interlinepenalty\fi
231 \fi}%
```

To allow customization we hide the font used in a separate macro.

```

232 \let\do\@makeother \dospecials
233 \obeylines \verbatim@font \@noligs

To avoid a breakpoint after the labels box, we remove the penalty put there by
the list macros: another use of \unpenalty!

234 \everypar \expandafter{\the\everypar \unpenalty}%
235 }
236 /2kernel | latexrelease>
237 (latexrelease)\EndIncludeInRelease
238 (latexrelease)\IncludeInRelease{0000-00-00}{\@verbatim}%
239 (latexrelease) {Disable hyphenation in verbatim}%
240 (latexrelease)\def\@verbatim{\trivlist \item\relax
241 (latexrelease) \if@minipage\else\vskip\parskip\fi
242 (latexrelease) \leftskip\@totalleftmargin\rightskip\z@skip
243 (latexrelease) \parindent\z@\parfillskip\@flushglue\parskip\z@skip
244 (latexrelease) @@par
245 (latexrelease) \@tempswafalse
246 (latexrelease) \def\par{%
247 (latexrelease) \if@tempswa
248 (latexrelease) \leavevmode \null @@par\penalty\interlinepenalty
249 (latexrelease) \else
250 (latexrelease) \@tempswatrue
251 (latexrelease) \ifhmode@@par\penalty\interlinepenalty\fi
252 (latexrelease) \fi}%
253 (latexrelease) \let\do\@makeother \dospecials
254 (latexrelease) \obeylines \verbatim@font \@noligs
255 (latexrelease) \hyphenchar\font\m@ne
256 (latexrelease) \everypar \expandafter{\the\everypar \unpenalty}%
257 (latexrelease)}
258 (latexrelease)\EndIncludeInRelease
259 (*2kernel)

```

`\verbatim` (RmS 93/09/19) Protected against ‘missing item’ error message triggered by empty verbatim environment.

```

260 \def\verbatim{\@verbatim \frenchspacing\@vobeyspaces \@xverbatim}
261 \def\endverbatim{\if@newlist \leavevmode\fi\endtrivlist}

```

`\verbatim@font` Macro to select the font used for verbatim typesetting. It also does other work if necessary for the font used.

```

262 \def\verbatim@font{\normalfont\ttfamily}

263 /2kernel)
264 (*2kernel | latexrelease>
265 (latexrelease)\IncludeInRelease{2018/12/01}%
266 (latexrelease) {\verbvisiblespace}{Setup visible space for verb}%

```

`\asciispace` The character in slot 32, in typewriter fonts (historically) a visible space but in other fonts a real space or something else

```

267 \DeclareRobustCommand\asciispace{\char 32 }

```

`\verbvisiblespace` This defines how to get a visible space in `\verb*` and friends. In classic T<sub>E</sub>X this is just the slot 32, but in TU encoded fonts we switch fonts and take the character from cmtt.

```

268 \ifx\Umathcode\@undefined
269   \let\verbvisiblespace\asciispace % Pdftex version
270 \else
271   \DeclareRobustCommand\verbvisiblespace
272     {\leavevmode{\usefont{OT1}{cmtt}{m}{n}\asciispace}} % xetex/luatex version
273 \fi

```

**\@setupverbvisiblespace** In pdf<sub>T</sub>E<sub>X</sub> a catcode 12 space will produce the character in slot 32 which is assumed to be a visible space character (in a typewriter font in OT1 or T1 encoding). In Xe<sub>T</sub>E<sub>X</sub> or Lua<sub>T</sub>E<sub>X</sub> a font in TU encoding is normally used and that has a real space in this slot. So what we do in this case is this: we check the definition of `\verbvisiblespace` and if it is `\asciispace` we assume that the char32 can be used (e.g., in pdf<sub>T</sub>E<sub>X</sub>). We then redefine `\@xobeysp` so that after running `\@vobeyspaces` we get characters from slot 32 for each active space.

```

274 \def\@setupverbvisiblespace{%
275   \ifx\verbvisiblespace\asciispace
276     \let\@xobeysp\asciispace
277   \else

```

Otherwise we measure the width of a character in the mon-spaced current font and place a `\verbvisiblespace` into a box of the right width which we are then using as the character for a space. By default this will be the space character from OT1 cmtt but by changing `\verbvisiblespace` one could use, for example, the `\textvisiblespace` of the current typewriter font.

```

278     \setbox\z@\hbox{x}%
279     \setbox\@verbvisiblespacebox\hbox to\wd\z@{\hss\verbvisiblespace\hss}%
280     \def\@xobeysp{\leavevmode\copy\@verbvisiblespacebox}%
281   \fi
282 }

```

**\@verbvisiblespacebox** The box to hold the visible space character if it isn't in slot 32 in the current typewriter font.

```

283 \newbox\@verbvisiblespacebox

```

**\@sverb** Definitions of `\@sverb` and `\@verb` changed so `\verb+foo+` does not lose leading blanks when it comes at the beginning of a line. Change made 24 May 89. Suggested by Frank Mittelbach and Rainer Schöpf.

```

284 \def\@sverb#1{%
285   \catcode'\#1\active
286   \lccode'\~'#1%
287   \gdef\verb@balance@group{\verb@egroup
288     \@latexerror{\noexpand\verb illegal in command argument}\@ehc}%
289   \aftergroup\verb@balance@group
290   \lowercase{\let~\verb@egroup}%

```

If `\@sverb` is called from `\@verb` then space is already active and supposed to produce a real space. In this case we do nothing. Otherwise we run `\@setupverbvisiblespace` to setup the right visible space char and afterwards `\@vobeyspaces` to make it the definition for the active space character.

```

291   \ifnum\catcode'\ =\active
292     \else \@setupverbvisiblespace \@vobeyspaces \fi
293 }

```

`verbatim*` For `verbatim*` we also set up the correct visible space character definition and then run `\@vobeyspaces`. As this code is not called as part of the normal `verbatim` environment (the method is done the other way around this time) we don't have to check if `space` is already active—it shouldn't be.

```

294 \@namedef{verbatim*}{\@verbatim
295   \@setupverbvisiblespace
296   \frenchspacing\@vobeyspaces\@sxverbatim}
297 \expandafter\let\csname endverbatim*\endcsname=\endverbatim

298 </2ekernel | latexrelease>
299 <latexrelease>\EndIncludeInRelease
300 <latexrelease>\IncludeInRelease{0000/00/00}%
301 <latexrelease>           {\verbvisiblespace}{Setup visible space for verb}%
302 <latexrelease>
303 <latexrelease>\@namedef{verbatim*}{\@verbatim\@sxverbatim}
304 <latexrelease>
305 <latexrelease>\let\asciispace           \@undefined
306 <latexrelease>\let\verbvisiblespace     \@undefined
307 <latexrelease>\let\@setupverbvisiblespace \@undefined
308 <latexrelease>\let\@verbvisiblespacebox  \@undefined
309 <latexrelease>
310 <latexrelease>\def\@sverb#1{%
311 <latexrelease>  \catcode'#1\active
312 <latexrelease>  \lccode'\~'#1%
313 <latexrelease>  \gdef\verb@balance@group{\verb@egroup
314 <latexrelease>    \@latex@error{noexpand\verb illegal in command argument}\@ehc}%
315 <latexrelease>  \aftergroup\verb@balance@group
316 <latexrelease>  \lowercase{\let~\verb@egroup}}%
317 <latexrelease>
318 <latexrelease>\EndIncludeInRelease
319 <*2ekernel>

```

`\@makeoother`

```

320 \def\@makeoother#1{\catcode'#112\relax}

```

`\verb@balance@group`

```

321 \let\verb@balance@group\@empty

```

`\verb@egroup`

```

322 \def\verb@egroup{\global\let\verb@balance@group\@empty\egroup}

```

`\verb@eol@error`

```

323 \begingroup
324   \obeylines%
325   \gdef\verb@eol@error{\obeylines%
326     \def~M{\verb@egroup\@latex@error{%
327       \noexpand\verb ended by end of line}\@ehc}}%
328 \endgroup

```

`\verb` Typesetting a small piece `verbatim`.

```

329 </2ekernel>
330 <*2ekernel | latexrelease>
331 <latexrelease>\IncludeInRelease{2017-04-15}{\verb}%

```

```

332 \latexrelease) {Disable hyphenation in verb}%
333 \def\verb{\relax\ifmmode\hbox\else\leavevmode\null\fi
334 \bgroup
335 \verb@eol@error \let\do\@makeother \dospecials
336 \verbatim@font\@noligs

```

Set \language here to suppress hyphenation. Done this way rather than setting \hyphenchar as that is a global setting.

```

337 \language\l@nohyphenation
338 \ifstar\@sverb\@verb}
339 \endkernel\latexrelease)
340 \EndIncludeInRelease
341 \IncludeInRelease{0000-00-00}{\verb}%
342 \latexrelease) {Disable hyphenation in verb}%
343 \def\verb{\relax\ifmmode\hbox\else\leavevmode\null\fi
344 \bgroup
345 \verb@eol@error \let\do\@makeother \dospecials
346 \verbatim@font\@noligs
347 \ifstar\@sverb\@verb}
348 \EndIncludeInRelease
349 \endkernel)

```

\@verb

```

350 \def\@verb{\@vobeyspaces \frenchspacing \@sverb}

```

\verbatim@nolig@list

```

351 \def\verbatim@nolig@list{\do\'\do\<\do\>\do\,\do\'\do\~}

```

\do@noligs

```

352 \def\do@noligs#1{%
353 \catcode'#1\active
354 \begingroup
355 \lccode'\~'#1\relax
356 \lowercase{\endgroup\def~{\leavevmode\kern\z@\char'#1}}

```

\@noligs To stay compatible with packages that use \@noligs we keep it.

```

357 \def\@noligs{\let\do\do@noligs \verbatim@nolig@list}

```

```

358 \endkernel)

```

File z

# ltmath.dtx

## 54 Math setup

This file contains a lot of the original plain T<sub>E</sub>X code, as well as the L<sup>A</sup>T<sub>E</sub>X environments for math. It still needs sorting out.

```
1 (*2kernel)
2 \message{math definitions,}
```

### 54.1 Math commands based on plain T<sub>E</sub>X

#### 54.1.1 The log-like functions

```
\log The standard operators:
3 \DeclareRobustCommand\log{\mathop{\operator@font log}\nolimits}
4 \DeclareRobustCommand\lg{\mathop{\operator@font lg}\nolimits}
5 \DeclareRobustCommand\ln{\mathop{\operator@font ln}\nolimits}
6 \DeclareRobustCommand\lim{\mathop{\operator@font lim}}
7 \DeclareRobustCommand\limsup{\mathop{\operator@font lim}\nolimits,\sup}
8 \DeclareRobustCommand\liminf{\mathop{\operator@font lim}\nolimits,\inf}
9 \DeclareRobustCommand\sin{\mathop{\operator@font sin}\nolimits}
10 \DeclareRobustCommand\arcsin{\mathop{\operator@font arcsin}\nolimits}
11 \DeclareRobustCommand\sinh{\mathop{\operator@font sinh}\nolimits}
12 \DeclareRobustCommand\cos{\mathop{\operator@font cos}\nolimits}
13 \DeclareRobustCommand\arccos{\mathop{\operator@font arccos}\nolimits}
14 \DeclareRobustCommand\cosh{\mathop{\operator@font cosh}\nolimits}
15 \DeclareRobustCommand\tan{\mathop{\operator@font tan}\nolimits}
16 \DeclareRobustCommand\arctan{\mathop{\operator@font arctan}\nolimits}
17 \DeclareRobustCommand\tanh{\mathop{\operator@font tanh}\nolimits}
18 \DeclareRobustCommand\cot{\mathop{\operator@font cot}\nolimits}
19 \DeclareRobustCommand\coth{\mathop{\operator@font coth}\nolimits}
20 \DeclareRobustCommand\sec{\mathop{\operator@font sec}\nolimits}
21 \DeclareRobustCommand\csc{\mathop{\operator@font csc}\nolimits}
22 \DeclareRobustCommand\max{\mathop{\operator@font max}}
23 \DeclareRobustCommand\min{\mathop{\operator@font min}}
24 \DeclareRobustCommand\sup{\mathop{\operator@font sup}}
25 \DeclareRobustCommand\inf{\mathop{\operator@font inf}}
26 \DeclareRobustCommand\arg{\mathop{\operator@font arg}\nolimits}
27 \DeclareRobustCommand\ker{\mathop{\operator@font ker}\nolimits}
28 \DeclareRobustCommand\dim{\mathop{\operator@font dim}\nolimits}
29 \DeclareRobustCommand\hom{\mathop{\operator@font hom}\nolimits}
30 \DeclareRobustCommand\det{\mathop{\operator@font det}}
31 \DeclareRobustCommand\exp{\mathop{\operator@font exp}\nolimits}
32 \DeclareRobustCommand\Pr{\mathop{\operator@font Pr}}
33 \DeclareRobustCommand\gcd{\mathop{\operator@font gcd}}
34 \DeclareRobustCommand\deg{\mathop{\operator@font deg}\nolimits}

\bmod And some operators have to be done by hand:
35 \DeclareRobustCommand\bmod{%
36 \nonscript\mskip-\medmuskip\mkern5mu%
```



```

37 \mathbin{\operatorname@font mod}\penalty900\mkern5mu%
38 \nonscript\mskip-\medmuskip}

```

`\pmod`

```

39 \DeclareRobustCommand\pmod[1]{%
40 \allowbreak\mkern18mu({\operatorname@font mod}\,\,\,#1)}

```

### 54.1.2 Biggggg

`\big` Variants on `\big` and friends for use with delimiters:

```

41 \DeclareRobustCommand\bigl{\mathopen\big}
42 \DeclareRobustCommand\bigm{\mathrel\big}
43 \DeclareRobustCommand\bigr{\mathclose\big}
44 \DeclareRobustCommand\Bigl{\mathopen\Big}
45 \DeclareRobustCommand\Bigm{\mathrel\Big}
46 \DeclareRobustCommand\Bigr{\mathclose\Big}
47 \DeclareRobustCommand\biggl{\mathopen\bigg}
48 \DeclareRobustCommand\biggm{\mathrel\bigg}
49 \DeclareRobustCommand\biggr{\mathclose\bigg}
50 \DeclareRobustCommand\Biggl{\mathopen\Bigg}
51 \DeclareRobustCommand\Biggm{\mathrel\Bigg}
52 \DeclareRobustCommand\Biggr{\mathclose\Bigg}

```

### 54.1.3 The UNSORTED Rest

The other math commands are lifted from plain T<sub>E</sub>X.

`\jot`

```

53 \newdimen\jot
54 \jot=3pt

```

`\interdisplaylinepenalty`

```

55 \newcount\interdisplaylinepenalty
56 \interdisplaylinepenalty=100

```

`\choose`

```

57 \def\choose{\atopwithdelims()}

```

`\brack`

```

58 \def\brack{\atopwithdelims[]}

```

`\brace`

```

59 \def\brace{\atopwithdelims\{\}}

```

`\mathpalette`

```

60 \def\mathpalette#1#2{%
61 \mathchoice
62 {\#1\displaystyle\#2}}%
63 {\#1\textstyle\#2}}%
64 {\#1\scriptstyle\#2}}%
65 {\#1\scriptscriptstyle\#2}}

```

```

\root
\rootbox 66 \newbox\rootbox
\root 67 \def\root#1\of{%
68 \setbox\rootbox\hbox{\$ \m@th\scriptscriptstyle{#1}$}%
69 \mathpalette\root@t}

70 \def\root#1#2{%
71 \setbox\z@ \hbox{\$ \m@th#1\sqrt{sign{#2}$}%
72 \dimen@ \ht\z@ \advance\dimen@ -\dp\z@
73 \mkern5mu\raise.6\dimen@\copy\rootbox
74 \mkern-10mu\box\z@}

\phantom
\hphantom 75 \newif\ifv@
\vphantom 76 \newif\ifh@

77 \if2kernel
78 \if*2kernel | latexrelease
79 \if latexrelease \IncludeInRelease{2019/10/01}%
80 \if latexrelease {\vphantom}{Make commands robust}%
81 \DeclareRobustCommand\vphantom{\v@true\h@false\ph@nt}
82 \DeclareRobustCommand\hphantom{\v@false\h@true\ph@nt}
83 \DeclareRobustCommand\phantom{\v@true\h@true\ph@nt}

\mathstrut

84 \DeclareRobustCommand\mathstrut{\vphantom{}}

85 \if2kernel | latexrelease
86 \if latexrelease \EndIncludeInRelease
87 \if latexrelease \IncludeInRelease{0000/00/00}%
88 \if latexrelease {\vphantom}{Make commands robust}%
89 \if latexrelease
90 \if latexrelease \kernel@make@fragile\vphantom
91 \if latexrelease \kernel@make@fragile\hphantom
92 \if latexrelease \kernel@make@fragile\phantom
93 \if latexrelease \kernel@make@fragile\mathstrut
94 \if latexrelease
95 \if latexrelease \EndIncludeInRelease
96 \if*2kernel

97 \def\ph@nt{%
98 \ifmmode
99 \expandafter\mathpalette\expandafter\mathph@nt
100 \else
101 \expandafter\makeph@nt
102 \fi}

103 \def\makeph@nt#1{%
104 \setbox\z@ \hbox{\color@begingroup#1\color@endgroup}\finph@nt}

105 \def\mathph@nt#1#2{%
106 \setbox\z@ \hbox{\$ \m@th#1{#2}$}\finph@nt}

```

```

107 </2ekernel>
108 <*2ekernel | latexrelease>
109 <latexrelease>\IncludeInRelease{2018/12/01}%
110 <latexrelease>          {\finph@nt}{Start LR-mode}%
111 \def\finph@nt{%
112   \setbox\tw@ \null
113   \ifv@ \ht\tw@\ht\z@ \dp\tw@\dp\z@\fi
114   \ifh@ \wd\tw@\wd\z@\fi

115   \leavevmode@ifvmode\box\tw@}
116 </2ekernel | latexrelease>
117 <latexrelease>\EndIncludeInRelease
118 <latexrelease>\IncludeInRelease{0000/00/00}%
119 <latexrelease>          {\finph@nt}{Start LR-mode}%
120 <latexrelease>\def\finph@nt{%
121 <latexrelease>   \setbox\tw@ \null
122 <latexrelease>   \ifv@ \ht\tw@\ht\z@ \dp\tw@\dp\z@\fi
123 <latexrelease>   \ifh@ \wd\tw@\wd\z@\fi \box\tw@}
124 <latexrelease>\EndIncludeInRelease
125 <*2ekernel>

\smash

126 \DeclareRobustCommand\smash{%
127   \relax % \relax, in case this comes first in \halign
128   \ifmmode
129     \expandafter\mathpalette\expandafter\mathsm@sh
130   \else
131     \expandafter\makesm@sh
132   \fi}

133 \def\makesm@sh#1{%
134   \setbox\z@\hbox{\color@begingroup#1\color@endgroup}\finsm@sh}
135 \def\mathsm@sh#1#2{%
136   \setbox\z@\hbox{\$m@th#1{#2}$}\finsm@sh}

137 </2ekernel>
138 <*2ekernel | latexrelease>
139 <latexrelease>\IncludeInRelease{2018/12/01}%
140 <latexrelease>          {\finsm@sh}{Start LR-mode}%
141 \def\finsm@sh{\ht\z@\z@ \dp\z@\z@ \leavevmode@ifvmode\box\z@}
142 </2ekernel | latexrelease>
143 <latexrelease>\EndIncludeInRelease
144 <latexrelease>\IncludeInRelease{0000/00/00}%
145 <latexrelease>          {\finsm@sh}{Start LR-mode}%
146 <latexrelease>\def\finsm@sh{\ht\z@\z@ \dp\z@\z@ \box\z@}
147 <latexrelease>\EndIncludeInRelease
148 <*2ekernel>

\buildrel

149 \def\buildrel#1\over#2{\mathrel{\mathop{\kern\z@#2}\limits^{#1}}}}

150 </2ekernel>
151 <*2ekernel | latexrelease>
152 <latexrelease>\IncludeInRelease{2019/10/01}%
153 <latexrelease>          {\cases}{Make commands robust}%

```

```

\cases
154 \DeclareRobustCommand\cases[1]{\left\{\,\,\vcenter{\normalbaselines\m@th
155 \ialign{\##\hfil$\&\quad{\##}\hfil\crr#1\crr}\}\right.}

\matrix
156 \DeclareRobustCommand\matrix[1]{\null\,\vcenter{\normalbaselines\m@th
157 \ialign{\hfil$\##$\hfil$\&\quad\hfil$\##$\hfil\crr
158 \mathstrut\crr\noalign{\kern-\baselineskip}
159 #1\crr\mathstrut\crr\noalign{\kern-\baselineskip}}}\,,}

\pmatrix
160 \DeclareRobustCommand\pmatrix[1]{\left(\matrix{#1}\right)}

161 (/2kernel | latexrelease)
162 (latexrelease)\EndIncludeInRelease
163 (latexrelease)\IncludeInRelease{0000/00/00}%
164 (latexrelease) \cases{Make commands robust}%
165 (latexrelease)
166 (latexrelease)\kernel@make@fragile\cases
167 (latexrelease)\kernel@make@fragile\matrix
168 (latexrelease)\kernel@make@fragile\pmatrix
169 (latexrelease)
170 (latexrelease)\EndIncludeInRelease
171 (*2kernel)

\bordermatrix
172 \def\bordermatrix#1{\begingroup \m@th
173 \@tempdima 8.75\p@
174 \setbox\z@\vbox{%
175 \def\cr{\crr\noalign{\kern2\p@\global\let\cr\endline}}%
176 \ialign{\##\hfil\kern2\p@\kern\@tempdima&\thinspace\hfil$\##$\hfil
177 &\quad\hfil$\##$\hfil\crr
178 \omit\strut\hfil\crr\noalign{\kern-\baselineskip}%
179 #1\crr\omit\strut\cr}}%
180 \setbox\tw@\vbox{\unvcopy\z@\global\setbox\@ne\lastbox}%
181 \setbox\th@\hbox{\unhbox\@ne\unskip\global\setbox\@ne\lastbox}%
182 \setbox\th@\hbox{$\kern\wd\@ne\kern-\@tempdima\left(\kern-\wd\@ne
183 \global\setbox\@ne\vbox{\box\@ne\kern2\p@}%
184 \vcenter{\kern-\ht\@ne\unvbox\z@\kern-\baselineskip}\,,\right)$}%
185 \null\;\vbox{\kern\ht\@ne\box\th@}\endgroup}

\openup
186 \def\openup{\afterassignment\openup\dimen@}
187 \def\@openup{\advance\lineskip\dimen@
188 \advance\baselineskip\dimen@
189 \advance\lineskiplimit\dimen@}

\displaylines
190 \newif\ifdt@p
191 \def\display{\global\dt@ptrue\openup\jot\m@th
192 \everycr{\noalign{\ifdt@p \global\dt@pfalse \ifdim\prevdepth>-1000\p@
193 \vskip-\lineskiplimit \vskip\normallineskiplimit \fi
194 \else \penalty\interdisplaylinepenalty \fi}}}

```

```

195 \def\@align{\tabskip\z@skip\everycr{}} % restore inside \displ@y
196 \def\displaylines#1{\displ@y \tabskip\z@skip
197   \halign{\hb@xt@\displaywidth{${\@align\hfil\displaystyle##\hfil$}\crr
198     #1\crr}}

\sp
\sb 199 \let\sp=^
    200 \let\sb=_

\>
\; 201 %\def\,{\mskip\thinmuskip} % already defined in ltspac
\! 202 \def\>{\mskip\medmuskip}
    203 \def\;{\mskip\thickmuskip}
    204 \def\!{\mskip-\thinmuskip}

\*
205 \DeclareRobustCommand\*{\discretionary{\thinspace\the\textfont2\char2}{-}{-}}

\: Nickname for the medium space since \> is not available inside tabbing.
206 \let\:=\>

\active@math@prime This is the definition of the active math prime.
207 \def\active@math@prime{^{\bgroup\prim@s}}

\prime@s
208 {\catcode'\=' \active \global\let'\active@math@prime}
209 \def\prim@s{%
210   \prime\futurelet\@let@token\pr@m@s}
211 \def\pr@m@s{%
212   \ifx'\@let@token
213     \expandafter\pr@@@s
214   \else
215     \ifx^\@let@token
216       \expandafter\expandafter\expandafter\pr@@@t
217     \else
218       \egroup
219     \fi
220   \fi}
221 \def\pr@@@s#1{\prim@s}
222 \def\pr@@@t#1#2{#2\egroup}

223 {\catcode'\_=\active \gdef\_{} % _ in math is
224   % either subscript or \_

```

## 54.2 Math Environments

`\(` Produces  $\$. \dots \$$  with checks that `\(` isn't used in math mode, and that `\)` is only used in math mode begun with `\(`.

```

225 \endkernel
226 \ifx\relax\ifmmode\@badmath\else$\fi}%
227 \endkernel | latexrelease
228 \DeclareRobustCommand\({%
229   \relax\ifmmode\@badmath\else$\fi}%
230 \DeclareRobustCommand\){%
231   \relax\ifmmode\ifinner$\else\@badmath\fi\else \@badmath\fi}%
232 \endkernel | latexrelease
233 \ifx\relax\ifmmode\@badmath\else$\fi}%
234 \endkernel | latexrelease
235 \def\({%
236   \relax\ifmmode\@badmath\else$\fi}%
237 \endkernel | latexrelease
238 \def\){%
239   \relax\ifmmode\ifinner$\else\@badmath\fi\else \@badmath\fi}%
240 \endkernel | latexrelease
241 \endkernel
242 \endkernel

```

`\[` Produces  $$$ \dots $$$  with checks that `\[` isn't used in math mode, and that `\]` is only used in display math mode (though there is no real test that this display math started with `\[` and not with  $$$$ ).

```

243 \endkernel
244 \ifx\relax\ifmmode\@badmath\else$\fi}%
245 \endkernel | latexrelease
246 \DeclareRobustCommand\[{%
247   \relax\ifmmode
248     \@badmath
249   \else
250     \ifvmode
251       \nointerlineskip
252       \makebox[.6\linewidth]{}%
253     \fi
254     $$$ BRACE MATCH HACK
255   \fi
256 }%
257 \DeclareRobustCommand\]{%
258   \relax\ifmmode
259     \ifinner
260     \@badmath
261   \else
262     $$$ BRACE MATCH HACK
263   \fi
264   \else
265     \@badmath
266   \fi
267   \ignorespaces
268 }%
269 \endkernel | latexrelease

```

```

270 \latexrelease\EndIncludeInRelease
271 \latexrelease\IncludeInRelease{0000/00/00}\{\[}{Make \[ robust}%
272 \latexrelease\def\[%
273 \latexrelease\relax\ifmmode
274 \latexrelease\@badmath
275 \latexrelease\else
276 \latexrelease\ifvmode
277 \latexrelease\nointerlineskip
278 \latexrelease\makebox[.6\linewidth]{}%
279 \latexrelease\fi
280 \latexrelease$$$ BRACE MATCH HACK
281 \latexrelease\fi
282 \latexrelease}%
283 \latexrelease\expandafter\let\csname\string\endcsname\@undefined
284 \latexrelease\def\[%
285 \latexrelease\relax\ifmmode
286 \latexrelease\ifinner
287 \latexrelease\@badmath
288 \latexrelease\else
289 \latexrelease$$$ BRACE MATCH HACK
290 \latexrelease\fi
291 \latexrelease\else
292 \latexrelease\@badmath
293 \latexrelease\fi
294 \latexrelease\ignorespaces
295 \latexrelease}%
296 \latexrelease\expandafter\let\csname\string\endcsname\@undefined
297 \latexrelease\EndIncludeInRelease
298 \*2ekernel)

math Disguises for \(\dots\) and \[...\].
displaymath 299 \let\math=\(
300 \let\endmath=\)
301 \def\displaymath{\[}
302 \def\enddisplaymath{\]\@ignoretrue}

equation \c@equation Numbered equations, using the counter \c@equation. Note: The document style
must define \theequation etc., and do the appropriate \@addtoreset. It should
also redefine \@eqnnum if another format for the equation number is desired other
than the standard (...), or to move the equation numbers to the flushleft. (See
comment on the \def of \@eqnnum.)
303 \definecounter{equation}
304 \def\equation{$$\refstepcounter{equation}}
305 \def\endequation{\eqno \hbox{\@eqnnum}$$\@ignoretrue}

\@eqnnum Produces the equation number for equation and eqnarray environments. The
following definition is for flushright numbers; for flushleft numbers, see leqno.clo.
The equation number is set in black roman type even if an eqnarray environment
appears in an italic environment.
306 \def\@eqnnum{\normalfont \normalcolor (\theequation)}

\stackrel A disguise for plain TEX's buildrel.
307 \DeclareRobustCommand\stackrel[2]{\mathrel{\mathop{#2}\limits^{#1}}}
```

`\frac` A disguise for plain T<sub>E</sub>X's `\over`.  
308 `\DeclareRobustCommand\frac[2]{\begingroup#1\endgroup\over#2}`

`\sqrt` Add an optional argument to plain's `\sqrt` to give the  $n$ th root of an expression  
`\@sqrt`  $\sqrt[n]{e}$ .  
309 `\DeclareRobustCommand\sqrt{\@ifnextchar[\@sqrt\sqrtsign}`  
310 `\def\@sqrt[#1]{\root #1\of}`

`eqnarray` Here's the `eqnarray` environment: Default is for left-hand side of equations to be  
`\@eqcnt` flushright. To make them flushleft, `\let\@eqnrel = \hfil`.  
`\@eqpen` 311 `\newcount\@eqcnt`  
`\if@eqnsw` 312 `\newcount\@eqpen`  
`\@eqnrel` 313 `\newif\if@eqnsw\@eqnswtrue`  
314 `\newskip\@centering`  
315 `\@centering = 0pt plus 1000pt`

To get a proper `\@currentlabel` we have to redefine it for the whole display. Note that we can't use `\refstepcounter` as this results in `\@currentlabel` getting restored at the wrong and thus always writing the first label to the .aux file.

```

316 \def\eqnarray{%
317   \stepcounter{equation}%
318   \def\@currentlabel{\p@equation\theequation}%
319   \global\@eqnswtrue
320   \m@th
321   \global\@eqcnt\z@
322   \tabskip\@centering
323   \let\\\@eqnrel
324   $$\everycr{}\halign to\displaywidth\bgroup
325     \hskip\@centering$\displaystyle\tabskip\z@skip{##}$\@eqnrel
326     &\global\@eqcnt\@ne\hskip \tw@\arraycolsep \hfil${##}$\hfil
327     &\global\@eqcnt\tw@ \hskip \tw@\arraycolsep
328     $\displaystyle{##}$\hfil\tabskip\@centering
329     &\global\@eqcnt\thr@@ \hbxt@\z@\bgroup\hss##\egroup
330     \tabskip\z@skip
331     \cr
332 }
333 \def\endeqnarray{%
334   \@eqnrel
335   \egroup
336   \global\advance\c@equation\m@ne
337   $$\@ignoretrue
338 }
339 \let\@eqnrel=\relax

```

`\nonumber` Switches off equation numbering.  
340 `\def\nonumber{\global\@eqnswfalse}`

`\@eqnrel`  
`\@xeqnrel` 341 `\def\@eqnrel{%`  
`\@yeqnrel` 342 `{\ifnum0='}\fi`  
343 `\@ifstar{%`  
344 `\global\@eqpen\@M\@yeqnrel`



```

345 }{%
346 \global\@eqpen\interdisplaylinepenalty \@eqnocr
347 }%
348 }

349 \def\@yeqnocr{\@testopt\@xeqnocr\z@skip}

350 \def\@xeqnocr[#1]{%
351 \ifnum0='{ \fi}%
352 \@eqnocr
353 \noalign{\penalty\@eqpen\vskip\jot\vskip #1\relax}%
354 }

\@eqnocr
355 \def\@eqnocr{\let\reserved@a\relax
356 \ifcase\@eqcnt \def\reserved@a{& &}\or \def\reserved@a{& &}%
357 \or \def\reserved@a{&}\else
358 \let\reserved@a\empty
359 \latexerror{Too many columns in eqnarray environment}\@ehc\fi
360 \reserved@a \if@eqnsw\@eqnnum\stepcounter{equation}\fi
361 \global\@eqnswtrue\global\@eqcnt\z@\cr}

eqnarray* Here's the eqnarray* environment:
\@seqnocr 362 \let\@seqnocr=\@eqnocr
363 \@namedef{eqnarray*}{\def\@eqnocr{\nonumber\@seqnocr}\eqnarray}
364 \@namedef{endeqnarray*}{\nonumber\endeqnarray}

\lefteqn \lefteqn{FORMULA} typesets FORMULA in display math style flushleft in a box of
width zero.
365 \def\lefteqn#1{\rlap{$\displaystyle #1$}}

\ensuremath In math mode, \ensuremath{text} is equivalent to text; in LR or paragraph
mode, it is equivalent to $text$. \relax is not needed in front of the \ifmmode as
\protect will be \let to \relax. This version (due to Donald Arseneau) avoids
duplicating its argument in the 'then' and 'else' part of the \ifmath which is
necessary in nested 'tabular' like environments. See amslatex/2104.
366 \DeclareRobustCommand{\ensuremath}{%
367 \ifmmode
368 \expandafter\@firstofone
369 \else
370 \expandafter\@ensuredmath
371 \fi}

\@ensuredmath The \relax stops \ensuremath{} starting display math.
372 \long\def\@ensuredmath#1{$\relax#1$}
373 \endkernel

```

## 54.3 External options to the standard document classes

### 54.3.1 Left equation numbering

`\@eqnnum` To put the equation number on the left side of an equation we have to use a little trick. The number is shifted `\displaywidth` to the left inside a box of

(approximately) zero width. This fails when the equation is too wide, the equation number than may overprint the equation itself.

```

374 (*leqno)
375 \renewcommand\@eqnnum{\hb@xt@.01\p@{}}%
376 \rlap{\normalfont\normalcolor
377 \hskip -\displaywidth(\theequation)}}
378 \leqno

```

### 54.3.2 Flush left equations

To get the displayed math environments to print the contents flush left (with an indentation) we have to redefine all of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s displayed math environments.

```

\mathindent The amount of indentation of the equations is stored in a register.
379 (*fleqn)
380 \newdimen\mathindent

The setting of \mathindent has to be deferred until the class file has been pro-
cessed, because \leftmargini is still 0pt wide at the moment fleqn.clo is read
in.
381 \AtEndOfClass{\mathindent\leftmargini}

\[ Begin display math;
382 \IncludeInRelease{2015/01/01}{\[\]{Make \[ robust}%
383 \DeclareRobustCommand\[\relax
384 \ifmmode\@badmath
385 \else
386 \begin{trivlist}%
387 \beginparpenalty\predisplaypenalty
388 \endparpenalty\postdisplaypenalty
389 \item[]\leavevmode
390 \hb@xt@\linewidth\bgroup $\m@th\displaystyle %$
391 \hskip\mathindent\bgroup
392 \fi}
393 \EndIncludeInRelease

394 \IncludeInRelease{0000/00/00}{\[\]{Make \[ robust}%
395 \renewcommand\[\relax
396 \ifmmode\@badmath
397 \else
398 \begin{trivlist}%
399 \beginparpenalty\predisplaypenalty
400 \endparpenalty\postdisplaypenalty
401 \item[]\leavevmode
402 \hb@xt@\linewidth\bgroup $\m@th\displaystyle %$
403 \hskip\mathindent\bgroup
404 \fi}
405 \EndIncludeInRelease

\] end display math;
406 \IncludeInRelease{2015/01/01}{\]\]{Make \] robust}%
407 \DeclareRobustCommand\]\relax
408 \ifmmode
409 \egroup $\hfil% $

```

```

410             \egroup
411             \end{trivlist}%
412             \else \@badmath
413             \fi}
414 \EndIncludeInRelease

415 \IncludeInRelease{0000/00/00}{\[]}{Make \] robust}%
416 \renewcommand\]{\relax
417             \ifmmode
418                 \egroup $\hfil% $
419                 \egroup
420                 \end{trivlist}%
421                 \else \@badmath
422                 \fi}
423 \EndIncludeInRelease

```

equation The equation environment

```

424 \renewenvironment{equation}%
425 {\@beginparpenalty\predisplaypenalty
426   \@endparpenalty\postdisplaypenalty
427   \refstepcounter{equation}%
428   \trivlist \item[]\leavevmode
429     \hb@xt@\linewidth\bgroup $\m@th% $
430     \displaystyle
431     \hskip\mathindent}%
432   {$\hfil % $
433     \displaywidth\linewidth\hbox{\@eqnnum}%
434   \egroup
435   \endtrivlist}

```

eqnarray The eqnarray environment

```

436 \renewenvironment{eqnarray}{%
437   \stepcounter{equation}%
438   \def\@currentlabel{\p@equation\theequation}%
439   \global\@eqnswtrue\m@th
440   \global\@eqcnt\z@
441   \tabskip\mathindent
442   \let\=\@eqnocr
443   \setlength\abovedisplayskip{\topsep}%
444   \ifvmode
445     \addtolength\abovedisplayskip{\partopsep}%
446   \fi

```

When the documentclass uses a non-zero \parskip setting the \topsep might have a negative value to compensate for that. Therefore we add \parskip to \abovedisplayskip.

```

447   \addtolength\abovedisplayskip{\parskip}%
448   \setlength\belowdisplayskip{\abovedisplayskip}%
449   \setlength\belowdisplayshortskip{\abovedisplayskip}%
450   \setlength\abovedisplayshortskip{\abovedisplayskip}%
451   $$\everycr{}\halign to\linewidth% $$
452   \bgroup
453     \hskip\@centering
454     $\displaystyle\tabskip\z@skip{##}$\@eqnsele%
455     \global\@eqcnt\@ne \hskip \tw@\arraycolsep \hfil$##$\hfil%

```

```

456     \global\@eqcnt\tw@ \hskip \tw@\arraycolsep
457     $\displaystyle{##}$\hfil \tabskip\@centering&%
458     \global\@eqcnt\thr@@
459     \hb@xt@\z@\bgroup\hss##\egroup\tabskip\z@skip\cr}%
460     {\@eqnocr
461     \egroup
462     \global\advance\c@equation\m@ne$$% $$
463     \@ignoretrue
464     }
465 \</fleqn>

```

## File A

# ltlists.dtx

## 55 List, and related environments

The generic commands for creating an indented environment – `enumerate`, `itemize`, `quote`, etc – are:

```
\list{<LABEL>}{<COMMANDS>} ... \endlist
```

which can be invoked by the user as the list environment. The LABEL argument specifies item labeling. COMMANDS contains commands for changing the horizontal and vertical spacing parameters.

Each item of the environment is begun by the command `\item[ITEMLABEL]` which produces an item labeled by ITEMLABEL. If the argument is missing, then the LABEL argument of the `\list` command is used as the item label.

The label is formed by putting `\makelabel{<ITEMLABEL>}` in an hbox whose width is either its natural width or else `\labelwidth`, whichever is larger. The `\list` command defines `\makelabel` to have the default definition:

```
\makelabel{<ARG>} == BEGIN \hfil ARG END
```

which, for a label of width less than `\labelwidth`, puts the label flushright, `\labelsep` to the left of the item's text. However, `\makelabel` can be `\let` to another command by the `\list`'s COMMANDS argument.

A `\usecounter{<foo>}` command in the second argument causes the counter `foo` to be initialized to zero, and stepped by every `\item` command without an argument. (`\label` commands within the list refer to this counter.)

When you leave a list environment, returning either to an enclosing list or normal text mode, LaTeX begins a new paragraph if and only if you leave a blank line after the `\end` command. This is accomplished by the `\@endparenv` command.

Blank lines are ignored every other reasonable place–i.e.:

- Between the `\begin{list}` and the first `\item`,
- Between the `\item` and the text of that item.
- Between the end of the last item and the `\end{list}`.

For an environment like quotation, in which items are not labeled, the entire environment is a single item. It is defined by letting `\quotation == \list{}{...}\item\relax`. (Note the `\relax`, there in case the first character in the environment is a '['.) The spacing parameters provide a great deal of flexibility in designing the format, including the ability to let the indentation of the first paragraph be different from that of the subsequent ones.

The trivlist environment is equivalent to a list environment whose second argument sets the following parameter values:

`\leftmargin = 0`: causes no indentation of left margin

`\labelwidth = 0`: see below for precise effect this has.

`\itemindent = 0`: with a null label, makes first paragraph have no indentation. Succeeding paragraphs have `\parindent` indentation. To give first paragraph same indentation, set `\itemindent = \parindent` before the `\item[]`.

Every `\item` in a trivlist environment must have an argument—in many cases, this will be the null argument (`\item[]`). The trivlist environment is mainly used for paragraphing environments, like `verbatim`, in which there is no margin change. It provides the same vertical spacing as the list environment, and works reasonably well when it occurs immediately after an `\item` command in an enclosing list.

## 55.1 List and Trivlist

The following variables are used inside a list environment:

`\totalleftmargin` The distance that the prevailing left margin is indented from the outermost left margin,

`\linewidth` The width of the current line. Must be initialized to `\hsize`.

`\listdepth` A count for holding current list nesting depth.

`\makelabel` A macro with a single argument, used to generate the label from the argument (given or implied) of the `\item` command. Initialized to `\@mklab` by the `\list` command. This command must produce some stretch—i.e., an `\hfil`.

`\@inlabel` A switch that is false except between the time an `\item` is encountered and the time that `TeX` actually enters horizontal mode. Should be tested by commands that can be messed up by the list environment's use of `\everypar`.

`\box\@labels` When `\@inlabel = true`, it holds the labels to be put out by `\everypar`.

`\@nparitem` A switch set by `\list` when `\@inlabel = true`. Handles the case of a `\list` being the first thing in an item.

`\@nparlist` A switch set true for a list that begins an item. No `\topsep` space is added before or after `\item`'s such a list.

`\@newlist` Set true by `\list`, set false by the first text (by `\everypar`).

`\@noitemarg` Set true when executing an `\item` with no explicit argument. Used to save space. To save time, make two separate `\@item` commands.

`\@nmbrlist` Set true by `\usecounter` command, causes list to be numbered.

`\@listctr` `\def`'ed by `\usecounter` to name of counter.

`\@noskipsec` A switch set true by a sectioning command when it is creating an in-text heading with `\everypar`.

Throughout a list environment, `\hsize` is the width of the current line, measured from the outermost left margin to the outermost right margin. Environments like `tabbing` should use `\linewidth` instead of `\hsize`.

Here are the parameters of a list that can be set by commands in the `\list's` COMMANDS argument. These parameters are all TeX skips or dimensions (defined by `\newskip` or `\newdimen`), so the usual TeX or L<sup>A</sup>T<sub>E</sub>X commands can be used to set them. The commands will be executed in vmode if and only if the `\list` was preceded by a `\par` (or something like an `\end{list}`), so the spacing parameters can be set according to whether the list is inside a paragraph or is its own paragraph.

## 55.2 Vertical Spacing (skips)

`\topsep`: Space between first item and preceding paragraph.

`\partopsep`: Extra space added to `\topsep` when environment starts a new paragraph (is called in vmode).

`\itemsep`: Space between successive items.

`\parsep`: Space between paragraphs within an item – the `\parskip` for this environment.

## 55.3 Penalties

`\@beginparpenalty`: put at the beginning of a list

`\@endparpenalty`: put at end of list

`\@itempenalty`: put between items.

## 55.4 Horizontal Spacing (dimens)

`\leftmargin`: space between left margin of enclosing environment (or of page if top level list) and left margin of this list. Must be nonnegative.

`\rightmargin`: analogous.

`\listparindent`: extra indentation at beginning of every paragraph of a list except the one started by the `\item` command. May be negative! Usually, labeled lists have `\listparindent` equal to zero.

`\itemindent`: extra indentation added right BEFORE an item label.

`\labelwidth`: nominal width of box that contains the label. If the natural width of the label  $\leq$  `\labelwidth`, then the label is flushed right inside a box of width `\labelwidth` (with an `\hfil`). Otherwise, a box of the natural width is employed, which causes an indentation of the text on that line.

`\labelsep`: space between end of label box and text of first item.

## 55.5 Default Values

Defaults for the list environment are set as follows. First, `\rightmargin`, `\listparindent` and `\itemindent` are set to 0pt. Then, one of the commands `\@listi`, `\@listii`, ... , `\@listvi` is called, depending upon the current level of the list. The `\@list` ... commands should be defined by the document style. A convention that the document style should follow is to set `\leftmargin` to `\leftmargini`, ..., `\leftmarginvi` for the appropriate level. Items that aren't changed may be left alone, but everything that could possibly be changed must be reset. *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\list{LABEL}{COMMANDS} ==
BEGIN
  if \@listdepth > 5
    then LaTeX error: 'Too deeply nested'
    else \@listdepth :=G \@listdepth + 1
  fi
  \rightmargin      := 0pt
  \listparindent    := 0pt
  \itemindent       := 0pt
  \eval{@list \romannumeral\the\@listdepth} %% Set default values:
  \@itemlabel       :=L LABEL
  \makelabel        == \@mklab
  @nmbrlist         :=L false
  COMMANDS

  \@trivlist          % commands common to \list and
\trivlist

  \parskip           :=L \parsep
  \parindent         :=L \listparindent
  \linewidth         :=L \linewidth - \rightmargin -\leftmargin
  \@totalleftmargin :=L \@totalleftmargin + \leftmargin
  \parshape 1 \@totalleftmargin \linewidth
  \ignorespaces      % gobble space up to \item
END

\endlist == BEGIN \@listdepth :=G \@listdepth -1
              \endtrivlist
              END

\@trivlist ==
BEGIN
  if @newlist = T then \@noitemerr fi
                      %% This command removed for some forgotten
reason.
  \@topsepadd :=L \topsep
  if @noskipsec then leave vertical mode fi %% Added 11 Jun 85
  if vertical mode
    then \@topsepadd :=L \@topsepadd + \partopsep
    else \unskip \par          % remove glue from end of last line
```



```

    fi
    if @inlabel = true
      then @noperitem :=L true
           @noperlist :=L true
      else @noperlist :=L false
           \@topsep    :=L \@topsepadd
    fi
    \@topsep      :=L \@topsep + \parskip %% Change 4 Sep 85
    \leftskip     :=L 0pt                % Restore paragraphing
parameters
    \rightskip    :=L \@rightskip
    \parfillskip  :=L 0pt + 1fil

NOTE: \@setpar called on every \list in case \par has been
temporarily munged before the \list command.
    \@setpar{if @newlist = false then {\@@par} fi}
    \@newlist    :=G T
    \@outerparskip :=L \parskip
END

\trivlist ==
BEGIN
  \parsep      := \parskip
  @nmbrlist := F
  \@trivlist
  \labelwidth := 0
  \leftmargin := 0
  \itemindent := \parindent
  \@itemlabel :=L "empty"          %% added 93/12/13
  \makelabel{LABEL} == LABEL
END

\endtrivlist ==
BEGIN
  if @inlabel = T then \indent fi
  if horizontal mode then \unskip \par fi
  if @noperlist = true
    else if \lastskip > 0
      then \@tempskipa := \lastskip
           \vskip - \lastskip
           \vskip \@tempskipa - \@outerparskip + \parskip
    fi
    \@endparenv
  fi
END

\@endparenv ==
BEGIN
  \addpenalty{@endparpenalty}
  \addvspace{\@topsepadd}

```

```

\endgroup    %% ends the \begin command's \begingroup
\par == BEGIN
            \@restorepar
            \everypar{}
            \par
            END
\everypar == BEGIN remove \lastbox \everypar{} END
\begingroup %% to match the \end commands \endgroup
END

\item == BEGIN if math mode then WARNING fi
            if next char = [
            then \item
            else @noitemarg := true
                \@item[@itemlabel]
            END

\@item[LAB] ==
BEGIN
  if @noparitem = true
  then @noparitem := false
      % NOTE: then clause hardly every taken,
      % so made a macro \@donoparitem
      \box\@labels :=G \hbox{\hskip -\leftmargin
                          \box\@labels
                          \hskip \leftmargin }
  if @minipage = false then
      \@tempskipa := \lastskip
      \vskip -\lastskip
      \vskip \@tempskipa + \@outerparskip - \parskip
  fi
  else if @inlabel = true
  then \indent \par % previous item empty.
  fi
  if hmode then 2 \unskip's
      % To remove any space at end of prev.
      % paragraph that could cause a blank line.
      \par
  fi
  if @newlist = T
  then if @nobreak = T % Kludge if list follows \section
      then \addvspace{\@outerparskip - \parskip}
      else \addpenalty{\@beginparpenalty}
          \addvspace{\@topsep}
          \addvspace{-\parskip} %% added 4 Sep 85
      fi
  else \addpenalty{\@itempenalty}
      \addvspace{\itemsep}
  fi
  @inlabel :=G true

```

```

fi

\everypar{ @minipage :=G F
            @newlist :=G F
            if @inlabel = true
            then @inlabel :=G false
                \hskip -\parindent
                \box\@labels
                \penalty 0
                %% 3 Oct 85 - allow line break here
                \box\@labels :=G null
            fi
        \everypar{} }
@nobreak :=G false
if @noitemarg = true
then @noitemarg := false
    if @nmbrlist
    then \refstepcounter{\@listctr}
fi
fi
\@tempboxa :=L \hbox{\makelabel{LAB}}
\box\@labels :=G \@labels \hskip \itemindent
                \hskip - (\labelwidth + \labelsep)
                if \wd \@tempboxa > \labelwidth
                then \box\@tempboxa
                else \hbox to \labelwidth
{\unhbox\@tempboxa}
fi
\hskip\labelsep
\ignorespaces %gobble space up to text
END

\makelabel{LABEL} == ERROR %% default to catch lonely \item

\usecounter{CTR} == BEGIN @nmbrlist :=L true
                        \@listctr == CTR
                        \setcounter{CTR}{0}
                        END

DEFINE \dimen's and \count
End of historical LATEX 2.09 comments.

\topskip
\partopsep 1 (*2ekernel)
\itemsep 2 \newskip\topsep
\parsep 3 \newskip\partopsep
\@topsep 4 \newskip\itemsep
\@topsepadd 5 \newskip\parsep
\outerparskip 6 \newskip\@topsep
7 \newskip\@topsepadd

```

```

8 \newskip\@outerparskip

\leftmargin
\rightmargin 9 \newdimen\leftmargin
\listparindent 10 \newdimen\rightmargin
\itemindent 11 \newdimen\listparindent
\labelwidth 12 \newdimen\itemindent
\labelsep 13 \newdimen\labelwidth
\@totalleftmargin 14 \newdimen\labelsep
15 \newdimen\linewidth
16 \newdimen\@totalleftmargin \@totalleftmargin=\z@

\leftmargini
\leftmarginii 17 \newdimen\leftmargini
\leftmarginiii 18 \newdimen\leftmarginii
\leftmarginiv 19 \newdimen\leftmarginiii
\leftmarginv 20 \newdimen\leftmarginiv
\leftmarginvi 21 \newdimen\leftmarginv
22 \newdimen\leftmarginvi

\@listdepth
\@itempenalty 23 \newcount\@listdepth \@listdepth=0
\@beginparpenalty 24 \newcount\@itempenalty
\@endparpenalty 25 \newcount\@beginparpenalty
26 \newcount\@endparpenalty

\@labels
27 \newbox\@labels

\if@inlabel
\@inlabelfalse 28 \newif\if@inlabel \@inlabelfalse
\@inlabeltrue
\if@newlist
\@newlistfalse 29 \newif\if@newlist \@newlistfalse
\@newlisttrue
\if@noparitem
\@noparitemfalse 30 \newif\if@noparitem \@noparitemfalse
\@noparitemtrue
\if@noparlist
\@noparlistfalse 31 \newif\if@noparlist \@noparlistfalse
\@noparlisttrue
\if@noitemarg
\@noitemargfalse 32 \newif\if@noitemarg \@noitemargfalse
\@noitemargtrue
\if@newlist
\@newlistfalse 33 \newif\if@nmbrlist \@nmbrlistfalse
\@newlisttrue
\list
34 \def\list#1#2{%
35 \ifnum \@listdepth >5\relax
36 \@toodeep
37 \else
38 \global\advance\@listdepth\@ne

```

```

39 \fi
40 \rightmargin\z@
41 \listparindent\z@
42 \itemindent\z@
43 \csname @list\romannumeral\the\@listdepth\endcsname
44 \def\@itemlabel{#1}%
45 \let\makelabel\@mklab
46 \@nmblistfalse
47 #2\relax
48 \@trivlist
49 \parskip\parsep
50 \parindent\listparindent
51 \advance\linewidth -\rightmargin
52 \advance\linewidth -\leftmargin
53 \advance\@totalleftmargin \leftmargin
54 \parshape \@ne \@totalleftmargin \linewidth
55 \ignorespaces}

```

\par@deathcycles

```

56 \newcount\par@deathcycles

```

\@trivlist Because \par is sometimes made a no-op it is possible for a missing \item to produce a loop that does not fill memory and so never gets trapped by T<sub>E</sub>X. We thus need to trap this here by setting \par to count the number of times a paragraph ii is called with no progress being made started.

```

57 \def\@trivlist{%
58   \if@noskipsec \leavevmode \fi
59   \@topsepadd \topsep
60   \ifvmode
61     \advance\@topsepadd \partopsep
62   \else
63     \unskip \par
64   \fi
65   \if@inlabel
66     \@nparitemtrue
67     \@nparlisttrue
68   \else
69     \if@newlist \@noitemerr \fi
70     \@nparlistfalse
71     \@topsep \@topsepadd
72   \fi
73   \advance\@topsep \parskip
74   \leftskip \z@skip
75   \rightskip \@rightskip
76   \parfillskip \@flushglue
77   \par@deathcycles \z@
78   \@setpar{\if@newlist
79             \advance\par@deathcycles \@ne
80             \ifnum \par@deathcycles >\@m
81               \@noitemerr
82               {\@par}%
83             \fi
84             \else
85               {\@par}%

```

```

86         \fi}%
87 \global \@newlisttrue
88 \@outerparskip \parskip}

```

`\trivlist`

```

89 \def\trivlist{%
90   \parsep\parskip
91   \@nmbrlistfalse
92   \@trivlist
93   \labelwidth\z@
94   \leftmargin\z@
95   \itemindent\z@

```

We initialise `\@itemlabel` so that a `\trivlist` with an `\item` not having an optional argument doesn't produce an error message.

```

96   \let\@itemlabel\@empty
97   \def\makelabel##1{##1}}

```

`\endlist`

```

98 \def\endlist{%
99   \global\advance\@listdepth\m@ne
100   \endtrivlist}

```

The definition of `\trivlist` used to be in `ltspace.dtx` so that other commands could be 'let to it'. They now use `\def`.

`\endtrivlist`

```

101 \def\endtrivlist{%
102   \if@inlabel
103     \leavevmode
104     \global \@inlabelfalse
105   \fi
106   \if@newlist
107     \@noitemerr
108     \global \@newlistfalse
109   \fi
110   \ifhmode\unskip \par

```

We also check if we are in math mode and issue an error message if so (hoping that `\@currenvir` resolves suitably). Otherwise the usual "perhaps a missing item" error will get triggered later which is confusing.

```

111   \else
112     \@inmatherr{\end{\@currenvir}}}%
113   \fi
114   \if@nolist \else
115     \ifdim\lastskip >\z@
116       \@tempskipa\lastskip \vskip -\lastskip
117       \advance\@tempskipa\parskip \advance\@tempskipa -\@outerparskip
118       \vskip\@tempskipa
119     \fi
120     \@endparenv
121   \fi
122 }

```

`\@endparenv` To suppress the paragraph indentation in text immediately following a paragraph-making environment, `\everypar` is changed to remove the space, and `\par` is redefined to restore `\everypar`. Instead of redefining `\par` and `\everypar`, `\@endparenv` was changed to set the `@endpe` switch, letting `\end` redefine `\par` and `\everypar`.

This allows paragraph-making environments to work right when called by other environments. (Changed 27 Oct 86)

```
123 \def\@endparenv{%
124   \addpenalty\@endparpenalty\addvspace\@topsepadd\@endpetrue}

125 (latexrelease)\IncludeInRelease{2015/01/01}{\@doendpe}{clubpenalty fix}%
126 \def\@doendpe{\@endpetrue
127   \def\par{\@restorepar
```

If a section heading changes `\clubpenalty` to keep lines after it together then this modification is restored via the `\everypar` mechanism at the start of the next paragraph. As we destroy the contents of this token here we explicitly set `\clubpenalty` back to its default.

```
128   \clubpenalty\@clubpenalty
129   \everypar{\par\@endpefalse}\everypar
```

Use `\setbox0=\lastbox` instead of `\hskip -\parindent` so that a `\noindent` becomes a no-op when used before a line immediately following a list environment(23 Oct 86).

```
130   {\setbox\z@\lastbox}%
131   \everypar{\@endpefalse}}
132 (latexrelease)\EndIncludeInRelease

133 (latexrelease)\IncludeInRelease{0000/00/00}{\@doendpe}{clubpenalty fix}%
134 (latexrelease)\def\@doendpe{\@endpetrue
135 (latexrelease)   \def\par{\@restorepar\everypar{\par\@endpefalse}\everypar
136 (latexrelease)   {\setbox\z@\lastbox}\everypar{\@endpefalse}}
137 (latexrelease)\EndIncludeInRelease
```

```
\if@endpe
\@endpefalse 138 \newif\if@endpe
\@endpeltrue 139 \@endpefalse
```

```
\@mklab
140 \def\@mklab#1{\hfil #1}
```

```
\item
141 \def\item{%
142   \@inmatherr\item
143   \@ifnextchar [\@item{\@noitemargtrue \@item[\@itemlabel]}}
```

```
\@donoparitem
144 \def\@donoparitem{%
145   \@noparitemfalse
146   \global\setbox\@labels\hbox{\hskip -\leftmargin
147     \unhbox\@labels
148     \hskip \leftmargin}%
149   \if@minipage\else
```

```

150 \@tempskipa\lastskip
151 \vskip -\lastskip
152 \advance\@tempskipa\@outerparskip
153 \advance\@tempskipa -\parskip
154 \vskip\@tempskipa
155 \fi}

```

`\@item`

```

156 \def\@item[#1]{%
157 \if@nparitem
158 \@donoparitem
159 \else
160 \if@inlabel
161 \indent \par
162 \fi
163 \ifhmode
164 \unskip\unskip \par
165 \fi
166 \if@newlist
167 \if@nobreak
168 \@nbitem
169 \else
170 \addpenalty\@beginparpenalty
171 \addvspace\@topsep
172 \addvspace{-\parskip}%
173 \fi
174 \else
175 \addpenalty\@itempenalty
176 \addvspace\itemsep
177 \fi
178 \global\@inlabeltrue
179 \fi
180 \everypar{%
181 \@minipagefalse
182 \global\@newlistfalse

```

This `\if@inlabel` check is needed in case an item starts of inside a group so that `\everypar` does not become empty outside that group. `nobreakfalse`, etc etc.

```

183 \if@inlabel
184 \global\@inlabelfalse

```

The paragraph indent is now removed by using `\setbox...` since this makes `\noindent` a no-op here, as it should be. Thus the following comment is redundant but is left here for the sake of future historians: this next command was changed from an `hskip` to a `kern` to avoid a break point after the `parindent` box: the skip could cause a line-break if a very long label occurs in `raggedright` setting.

If `\noindent` was used after `\item` want to cancel the `\itemindent` skip. This case can be detected as the indentation box will be void.

```

185 {\setbox\z@\lastbox
186 \ifvoid\z@
187 \kern-\itemindent
188 \fi}%
189 \box\@labels
190 \penalty\z@

```



```
191 \fi
```

This code is intended to prevent a page break after the first line of an item that comes immediately after a section title. It may be sensible to always forbid a page break after one line of an item? As with all such settings of `\clubpenalty` it is local so will have no effect if the item starts in a group.

Only resetting `\@nobreak` when it is true is now essential since now it is sometimes set locally.

```
192 \if@nobreak
193 \@nobreakfalse
194 \clubpenalty \@M
195 \else
196 \clubpenalty \@clubpenalty
197 \everypar{}%
198 \fi}%
```

```
199 \if@noitemarg
200 \@noitemargfalse
201 \if@nmbrrlist

202 \refstepcounter\@listctr
203 \fi
204 \fi
```

We use `\sbox` to support colour commands.

```
205 \sbox\@tempboxa{\makelabel{#1}}%
206 \global\setbox\@labels\hbox{%
207 \unhbox\@labels
208 \hskip \itemindent
209 \hskip -\labelwidth
210 \hskip -\labelsep
211 \ifdim \wd\@tempboxa >\labelwidth
212 \box\@tempboxa

213 \else
214 \hbox to\labelwidth {\unhbox\@tempboxa}%
215 \fi
216 \hskip \labelsep}%
217 \ignorespaces}
```

`\makelabel`

```
218 \def\makelabel#1{%
219 \@latex@error{Lonely \string\item--perhaps a missing
220 list environment}\@ehc}
```

`\@nbitem`

```
221 \def\@nbitem{%
222 \@tempskipa\@outerparskip
223 \advance\@tempskipa -\parskip
224 \addvspace\@tempskipa}
```

`\usecounter`

```
225 \def\usecounter#1{\@nmbrrlisttrue\def\@listctr{#1}\setcounter{#1}\z@}
```

## 55.6 Itemize and Enumerate

Enumeration is done with four counters: `enumi`, `enumii`, `enumiii` and `enumiv`, where `enumN` controls the numbering of the Nth level enumeration. The label is generated by the commands `\labelenumi` ... `\labelenumiv`, which should be defined by the document style. Note that `\p@enumN\theenumN` defines the output of a `\ref` command. A typical definition might be:

```
\def\theenumii{\alph{enumii}}
\def\p@enumii{\theenumi}
\def\labelenumii{(\theenumii)}
```

which will print the labels as ‘(a)’, ‘(b)’, ... and print a `\ref` as ‘3a’.

The item numbers are moved to the right of the label box, so they are always a distance of `\labelsep` from the item.

`\@enumdepth` holds the current enumeration nesting depth.

Itemization is controlled by four commands: `\labelitemi`, `\labelitemii`, `\labelitemiii`, and `\labelitemiv`. To cause the second-level list to be bulleted, you just define `\labelitemii` to be `•`. `\@itemspacing` and `\@itemdepth` are the analogs of `\@enumspacing` and `\@enumdepth`.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\enumerate ==
BEGIN
  if \@enumdepth > 3
    then errormessage: "Too deeply nested".
  else \@enumdepth :=L \@enumdepth + 1
    \@enumctr :=L eval(enum@\romannumeral\the\@enumdepth)
    \list{\label{\@enumctr}}
      {\usecounter{\@enumctr}
       \makelabel{LABEL} == \hss \llap{LABEL}}
    fi
END
```

```
\endenumerate == \endlist
```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```
\@enumdepth
226 \newcount\@enumdepth \@enumdepth = 0

\c@enumi
\c@enumii 227 \@definecounter{enumi}
\c@enumii 228 \@definecounter{enumii}
\c@enumiv 229 \@definecounter{enumiii}
230 \@definecounter{enumiv}

enumerate
231 \def\enumerate{%
232   \ifnum \@enumdepth >\thr@@\toodeep\else
233     \advance\@enumdepth\@ne
234     \edef\@enumctr{enum\romannumeral\the\@enumdepth}%
```

```

235     \expandafter
236     \list
237         \csname label\@enumctr\endcsname
238         {\usecounter\@enumctr\def\makelabel##1{\hss\llap{##1}}}%
239     \fi}

240 \let\endenumerate =\endlist

Historical LATEX 2.09 comments (not necessarily accurate any more):
\itemize ==
    BEGIN
        if \@itemdepth > 3
            then errormessage: 'Too deeply nested'.
            else \@itemdepth :=L \@itemdepth + 1
                \itemitem ==
eval(labelitem\romannumeral\the\@itemdepth)
                \list{\@nameuse{\@itemitem}}
                    {\makelabel{LABEL} == \hss \llap{LABEL}}
            fi
        END

\enditemize == \endlist

End of historical LATEX 2.09 comments.

\@itemdepth
241 \newcount\@itemdepth \@itemdepth = 0

itemize
242 \def\itemize{%
243     \ifnum \@itemdepth >\thr@@\toodeep\else
244         \advance\@itemdepth\@ne
245         \edef\@itemitem{labelitem\romannumeral\the\@itemdepth}%

246         \expandafter
247         \list
248             \csname\@itemitem\endcsname
249             {\def\makelabel##1{\hss\llap{##1}}}%
250     \fi}

251 \let\enditemize =\endlist
252 </2ekernel>

```

## File B

# ltboxes.dtx

## 56 L<sup>A</sup>T<sub>E</sub>X Box commands

<code>\makebox</code>	<code>\makebox[⟨wid⟩][⟨pos⟩]{⟨obj⟩}</code> Puts <code>⟨obj⟩</code> in an <code>\hbox</code> of width <code>⟨wid⟩</code> , positioned by <code>⟨pos⟩</code> . The possible <code>⟨pos⟩</code> are: s stretched, l flushleft, r flushright, c (default) centred. If <code>⟨wid⟩</code> is missing, then <code>⟨pos⟩</code> is also missing and <code>⟨obj⟩</code> is put in an <code>\hbox</code> of its natural width. <code>\makebox(⟨x⟩,⟨y⟩)[⟨pos⟩]{⟨obj⟩}</code> Puts <code>⟨obj⟩</code> in an <code>\hbox</code> of width <code>x*\unitlength</code> and height <code>y*\unitlength</code> . <code>⟨pos⟩</code> arguments are s, l, r or c (default) for stretched, flushleft, flushright or centred, and t or b for top, bottom – or combinations like tr or rb. Default for horizontal and vertical are centered. Note that in this picture mode version of <code>\makebox</code> a [b] aligns on the <i>bottom</i> of the text as documented. If you want to align on the <i>baseline</i> use <code>\makebox( , ) [b]{\raisebox{0pt}[\height][0pt]{xyz}}</code> or <code>\makebox( , ) [b]{\smash{xyz}}</code>
<code>\mbox</code>	<code>\mbox{⟨obj⟩}</code> The same as <code>\makebox{⟨obj⟩}</code> , but is more efficient as no checking for optional arguments is done.
<code>\newsavebox</code>	<code>\newsavebox{⟨cmd⟩}</code> : If <code>⟨cmd⟩</code> is undefined, then defines it to be a T <sub>E</sub> X box register.
<code>\savebox</code>	<code>\savebox{⟨cmd⟩} ...</code> : <code>⟨cmd⟩</code> is defined to be a T <sub>E</sub> X box register, and the '...' are any <code>\makebox</code> arguments. It is like <code>\makebox</code> , except it doesn't produce text but saves the value in <code>\box ⟨cmd⟩</code> .
<code>\sbox</code>	<code>\sbox{⟨cmd⟩}{⟨obj⟩}</code> is an efficient abbreviation for <code>\savebox{⟨cmd⟩}{⟨obj⟩}</code> .
<code>\lrbox</code>	<code>\begin{lrbox}{⟨cmd⟩}⟨text⟩\end{lrbox}</code> is equivalent to <code>\sbox{⟨cmd⟩}{⟨text⟩}</code> except that any white space at the beginning and end of <code>⟨text⟩</code> is ignored.
<code>\framebox</code>	<code>\framebox ...</code> : like <code>\makebox</code> , except it puts a 'frame' around the box. The frame is made of lines of thickness <code>\fboxrule</code> , separated by space <code>\fboxsep</code> from the text – except for <code>\framebox(X,Y) ...</code> , where the thickness of the lines is as for the picture environment, and there is no separation added.
<code>\fbox</code>	<code>\fbox{⟨obj⟩}</code> is an abbreviation for <code>\framebox{⟨obj⟩}</code> .
<code>\parbox</code>	<code>\parbox[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}{⟨text⟩}</code> : Makes a box with <code>\hsize ⟨width⟩</code> , positioned by <code>⟨pos⟩</code> as follows: c : <code>\vcenter</code> (placed in <code>\$...\$</code> if not in math mode) b : <code>\vbox</code> t : <code>\vtop</code> default value is c. Sets <code>\hsize := ⟨width⟩</code> and calls <code>\@parboxrestore</code> , which does the following: Restores the original definitions of:

```

\par
\\
\--
\'
\'
\=
Resets the following parameters:
\parindent      = 0pt
\parskip        = 0pt
\linewidth      = \hsize
\@totalleftmargin = 0pt
\leftskip       = 0pt
\rightskip      = 0pt
\@rightskip     = 0pt
\parfillskip    = 0pt plus 1fil
\lineskip       = \normallineskip
\baselineskip   = \normalbaselineskip
Calls \sloppy
Note: \@arrayparboxrestore same as \@parboxrestore but it doesn't re-
store \\.
minipage      minipage : Similar to \parbox, except it also makes this look like a page by
setting
\textwidth == \columnwidth == box width
changes footnotes by redefining:
\@mpfn == mpfootnote
\thempfn == \thempfootnote
\@footnotetext == \@mpfootnotetext
resets the following list environment parameters:
\@listdepth == \@mplistdepth
where \@mplistdepth is initialized to zero,
and executes \@minipagerestore to allow the document style to reset any
other parameters it desires. It sets @minipage true, and resets \everypar to set it
false. This switch keeps \addvspace from putting space at the top of a minipage.
Change added 24 May 89: \minipage sets @minipage globally; \endminipage
resets it false.
\rule      \rule[\langle raised \rangle]{\langle width \rangle}{\langle height \rangle} : Makes a \langle width \rangle * \langle height \rangle rule, raised
\langle raised \rangle.
\underline \underline{\langle text \rangle} : Makes an underlined hbox with \langle text \rangle in it.
\raisebox \raisebox{\langle distance \rangle}{\langle height \rangle}[\langle depth \rangle]{\langle box \rangle} :
Raises \langle box \rangle up by \langle distance \rangle length (down if \langle distance \rangle negative). Makes TeX
think that the new box extends \langle height \rangle above the line and \langle depth \rangle below, for a
total vertical length of \langle height \rangle + \langle depth \rangle. Default values of \langle height \rangle & \langle depth \rangle =
actual height and depth of box in new position.
1 \langle *2ekernel \rangle
2 \message{boxes,}

\makebox \makebox User level command just looks for optional [ or (.
3 \langle /2ekernel \rangle
4 \langle latexrelease \rangle \IncludeInRelease{2015/01/01}%
5 \langle latexrelease \rangle \{\makebox\}{Make \makebox robust}%

```

```

6 <*2ekernel | latexrelease>
7 \DeclareRobustCommand\makebox{%
8   \leavevmode
9   \@ifnextchar(%)
10    \makepicbox
11    {\@ifnextchar[\@makebox\mbox}}}%
12 </2ekernel | latexrelease>
13 <latexrelease>\EndIncludeInRelease
14 <latexrelease>\IncludeInRelease{0000/00/00}%
15 <latexrelease>          {\makebox}{Make \makebox robust}%
16 <latexrelease>\def\makebox{%
17 <latexrelease>  \leavevmode
18 <latexrelease>  \@ifnextchar(%)
19 <latexrelease>    \makepicbox
20 <latexrelease>    {\@ifnextchar[\@makebox\mbox}}}%
21 <latexrelease>\expandafter\let\csname makebox \endcsname\undefined
22 <latexrelease>\EndIncludeInRelease
23 <*2ekernel>

\mbox The basic horizontal box command for LATEX.
24 \DeclareRobustCommand\mbox[1]{\leavevmode\hbox{#1}}

\@makebox Look for a possible second optional argument (defaults to c).
25 \def\@makebox[#1]{%
26   \@ifnextchar [{\@imakebox[#1]}{\@imakebox[#1][c]}}

\@begin@tempboxa Helper macro for supporting \height, \width etc. Grab #1 into \@tempboxa and
measure it.
27 \long\def\@begin@tempboxa#1#2{%
28   \begingroup
29   \setbox\@tempboxa#1{\color@begingroup#2\color@endgroup}%
30   \def\width{\wd\@tempboxa}%
31   \def\height{\ht\@tempboxa}%
32   \def\depth{\dp\@tempboxa}%
33   \let\totalheight\@ovri
34   \totalheight\height
35   \advance\totalheight\depth}

\@end@tempboxa End the group started by \@begin@tempboxa, so that the scope of \height only
includes the ‘length’ argument to the user-command.
36 \let\@end@tempboxa\endgroup

\bm@c Set up spacing.
\bm@l 37 \def\bm@c{\hss\unhbox\@tempboxa\hss}
\bm@r 38 \def\bm@l{\unhbox\@tempboxa\hss}\let\bm@t\bm@l
\bm@s 39 \def\bm@r{\hss\unhbox\@tempboxa}\let\bm@b\bm@r
\bm@t 40 \def\bm@s{\unhbox\@tempboxa}
\bm@b
\@imakebox Internal form of \makebox.
41 \long\def\@imakebox[#1][#2]#3{%
42   \@begin@tempboxa\hbox{#3}%
43   \setlength\@tempdima{#1}%          support calc
44   \hb@xt@\@tempdima{\csname bm@#2\endcsname}%
45   \@end@tempboxa}

```

`\@makepicbox` Picture mode form of `\makebox`.

```
46 \def\@makepicbox(#1,#2){%
47   \ifnextchar[{\@makepicbox(#1,#2)}{\@makepicbox(#1,#2) []}}
```

`\imakepicbox` picture mode version

```
48 \long\def\imakepicbox(#1,#2)[#3]#4{%
49   \vbox to#2\unitlength
50   {\let\mb@b\vss \let\mb@l\hss\let\mb@r\hss
51     \let\mb@t\vss
52     \@tfor\reserved@a :=#3\do{%
53       \if s\reserved@a
54         \let\mb@l\relax\let\mb@r\relax
55       \else
56         \expandafter\let\csname mb@\reserved@a\endcsname\relax
57       \fi}%
58     \mb@t
59     \hb@xt@ #1\unitlength{\mb@l #4\mb@r}%
60     \mb@b
```

This kern ensures that a `b` option aligns on the bottom of the text rather than the baseline. this is the documented behaviour in the `LATEX`Book. The kern is removed in compatibility mode.

```
61   \kern\z@}}
```

`\set@color` This macro is initially a no-op, but the colour package will redefine it to insert a `\special`.

```
62 \let\set@color\relax
```

`\color@begingroup` These macros are initially a no-op, but the colour package will redefine them to be `\begingroup`, `\endgroup`, `\begingroup\set@color`, `\color@endgroup\color@begingroup`, `\color@endgroup\egroup`. and *(set to main document colour)* respectively.

`\color@hbox` 63 `\let\color@begingroup\relax`

`\color@vbox` 64 `\let\color@endgroup\relax`

`\color@endbox` 65 `\let\color@setgroup\relax`

```
66 \let\normalcolor\relax
```

```
67 \let\color@hbox\relax
```

```
68 \let\color@vbox\relax
```

```
69 \let\color@endbox\relax
```

`\newsavebox` Allocate a new ‘savebox’.

```
70 \def\newsavebox#1{\@ifdefinable{#1}{\newbox#1}}
```

`\savebox` Save #1 in a box register.

```
71 \</2ekernel>
```

```
72 \<latexrelease>\IncludeInRelease{2015/01/01}%
```

```
73 \<latexrelease>          {\savebox}{Make \savebox robust}%
```

```
74 \<*2ekernel | latexrelease>
```

```
75 \DeclareRobustCommand\savebox[1]{%
```

```
76   \@ifnextchar(%)
```

```
77     {\@savepicbox#1}{\@ifnextchar[{\@savebox#1}{\sbox#1}}}%
```

```
78 \</2ekernel | latexrelease>
```

```
79 \<latexrelease>\EndIncludeInRelease
```

```

80 \latexrelease\IncludeInRelease{0000/00/00}%
81 \latexrelease\savebox\Make \savebox robust}%
82 \latexrelease\def\savebox#1{%
83 \latexrelease\ifnextchar(
84 \latexrelease\@savepicbox#1\@ifnextchar[\@savebox#1\@sbox#1}}%
85 \latexrelease\expandafter\let\csname savebox \endcsname\undefined
86 \latexrelease\EndIncludeInRelease
87 \*2ekernel)

\savebox Save #1 in a box register.
88 \DeclareRobustCommand\savebox[2]{\setbox#1\hbox{%
89 \color@setgroup#2\color@endgroup}}

\@savebox Look for second optional argument.
90 \def\@savebox#1[#2]{%
91 \ifnextchar [\@isavebox#1[#2]]{\@isavebox#1[#2] [c]}}

\@isavebox
92 \long\def\@isavebox#1[#2] [#3] #4{%
93 \sbox#1{\@imakebox[#2] [#3] #4}}

\@savepicbox Picture mode version of \savebox.
94 \def\@savepicbox#1(#2,#3){%
95 \ifnextchar [%
96 {\@isavepicbox#1(#2,#3)}{\@isavepicbox#1(#2,#3) []}}

\@isavepicbox Picture mode version of \savebox.
97 \long\def\@isavepicbox#1(#2,#3) [#4] #5{%
98 \sbox#1{\@imakepicbox(#2,#3) [#4] #5}}

\lrbox lrbox: the new environment form of \savebox. Use \aftergroup tricks to enable a
local assignment to be made to the box, in a way that it still has an effect outside
the lrbox environment.
99 \def\lrbox#1{%
100 \edef\reserved@a{%
101 \endgroup
102 \setbox#1\hbox{%
103 \begingroup\aftergroup}%
104 \def\noexpand\@currenvir{\@currenvir}%
105 \def\noexpand\@currenvline{\on@line}}%
106 \reserved@a
107 \@endpfalse
108 \color@setgroup
109 \ignorespaces}

\endlrbox End the lrbox environment.
110 \def\endlrbox{\unskip\color@endgroup}

\usebox unchanged
111 \DeclareRobustCommand\usebox[1]{\leavevmode\copy #1\relax}

```



`\frame` The following definition of `\frame` was written by Pavel Curtis (Extra space removed 14 Jan 88) RmS 92/08/24: Replaced occurrence of `\@halfwidth` by `\@wholewidth`

```

112 \DeclareRobustCommand\frame[1]{%
113   \leavevmode
114   \hbox{%
115     \hskip-\@wholewidth
116     \vbox{%
117       \vskip-\@wholewidth
118       \hrule \@height\@wholewidth
119       \hbox{%
120         \vrule\@width\@wholewidth
121         #1%
122         \vrule\@width\@wholewidth}%
123       \hrule \@height\@wholewidth
124       \vskip-\@wholewidth}%
125     \hskip-\@wholewidth}}
```

`\fboxrule` user level parameters,

`\fboxsep` 126 `\newdimen\fboxrule`  
127 `\newdimen\fboxsep`

`\fbox` Abbreviated framed box command.

```

128 \DeclareRobustCommand\fbox[1]{%
129   \leavevmode
130   \setbox\@tempboxa\hbox{%
131     \color@begingroup
132     \kern\fboxsep{#1}\kern\fboxsep
133     \color@endgroup}%
134   \@frameb@x\relax}
```

`\framebox` Framed version of `\makebox`.

```

135 \if2ekernel
136 \iflatexrelease\IncludeInRelease{2015/01/01}%
137 \iflatexrelease{\framebox}{\Make \framebox robust}%
138 \if*2ekernel\iflatexrelease
139 \DeclareRobustCommand\framebox{%
140   \@ifnextchar(%)
141   \@framepicbox{\@ifnextchar[\@framebox\fbox}}%
142 \if2ekernel\iflatexrelease
143 \iflatexrelease\EndIncludeInRelease
144 \iflatexrelease\IncludeInRelease{0000/00/00}%
145 \iflatexrelease{\framebox}{\Make \framebox robust}%
146 \iflatexrelease\def\framebox{%
147 \iflatexrelease \ifnextchar(%)
148 \iflatexrelease \@framepicbox{\@ifnextchar[\@framebox\fbox}}%
149 \iflatexrelease\expandafter\let\csname framebox \endcsname\@undefined
150 \iflatexrelease\EndIncludeInRelease
151 \if*2ekernel
```

`\@framebox` Deal with optional arguments.

```

152 \def\@framebox[#1]{%
153   \@ifnextchar[%]
```

```

154     {\@iframebox[#1]}%
155     {\@iframebox[#1][c]}}

\@iframebox The handling the optional arguments. In order to set the whole box, including
the frame to the specified dimension, we first determine that dimension from the
natural size of the text, #3. calculated width.
156 \long\def\@iframebox[#1][#2]#3{%
157   \leavevmode
158   \@begin@tempboxa\hbox{#3}%
159   \setlength\@tempdima{#1}%
160   \setbox\@tempboxa\hbext\@tempdima
161     {\kern\fboxsep\csname bm@#2\endcsname\kern\fboxsep}%
162   \@frameb@x{\kern-\fboxrule}%
163   \@end@tempboxa}

\@frameb@x Common part of \framebox and \fbox. #1 is a negative kern in the \framebox
case so that the vertical rules do not add to the width of the box.
164 \def\@frameb@x#1{%
165   \@tempdima\fboxrule
166   \advance\@tempdima\fboxsep
167   \advance\@tempdima\dp\@tempboxa
168   \hbox{%
169     \lower\@tempdima\hbox{%
170       \vbox{%
171         \hrule\@height\fboxrule
172         \hbox{%
173           \vrule\@width\fboxrule
174           #1%
175           \vbox{%
176             \vskip\fboxsep
177             \box\@tempboxa
178             \vskip\fboxsep}%
179           #1%
180           \vrule\@width\fboxrule}%
181         \hrule\@height\fboxrule}%
182         }%
183       }%
184   }

\@framepicbox Picture mode version.
185 \def\@framepicbox(#1,#2){%
186   \@ifnextchar[{\@iframepicbox(#1,#2)}{\@iframepicbox(#1,#2) []}}

\@iframepicbox Picture mode version.
187 \long\def\@iframepicbox(#1,#2)[#3]#4{%
188   \frame{\@makepicbox(#1,#2)[#3]{#4}}

\parbox The main vertical-box command for LATEX.
189 </2ekernel>
190 <latexrelease>\IncludeInRelease{2015/01/01}%
191 <latexrelease>           {\parbox}{Make \parbox robust}%
192 <*2ekernel | latexrelease>
193 \DeclareRobustCommand\parbox{%

```

```

194 \@ifnextchar[%]
195 \@iparbox
196 {\@iiiparbox c\relax[s]}}%
197 /2ekernel | latexrelease)
198 (latexrelease)\EndIncludeInRelease
199 (latexrelease)\IncludeInRelease{0000/00/00}%
200 (latexrelease) {\parbox}{Make \parbox robust}%
201 (latexrelease)\def\parbox{%
202 (latexrelease) \@ifnextchar[%]
203 (latexrelease) \@iparbox
204 (latexrelease) {\@iiiparbox c\relax[s]}}%
205 (latexrelease)\expandafter\let\csname parbox \endcsname\@undefined
206 (latexrelease)\EndIncludeInRelease
207 (*2ekernel)

```

`\@iparbox` Optional argument handling.

```

208 \def\@iparbox[#1]{%
209 \@ifnextchar[%]
210 {\@iiiparbox{#1}}%
211 {\@iiiparbox{#1}\relax[s]}}

```

`\@iiiparbox` Optional argument handling.

```

212 \def\@iiiparbox#1[#2]{%
213 \@ifnextchar[%]
214 {\@iiiparbox{#1}{#2}}%
215 {\@iiiparbox{#1}{#2}[#1]}}

```

`\@iiiparbox` The internal version of `\parbox`.

```

\@parboxto
216 \let\@parboxto\@empty
217 \long\def\@iiiparbox#1#2[#3]#4#5{%
218 \leavevmode
219 \@pboxswfalse
220 \setlength\@tempdima{#4}%
221 \@begin@tempboxa\vbox{\hsize\@tempdima\@parboxrestore#5\@par}%
222 \ifx\relax#2\else
223 \setlength\@tempdimb{#2}%
224 \edef\@parboxto{to\the\@tempdimb}%
225 \fi
226 \if#1b\vbox
227 \else\if #1t\vtop
228 \else\ifmmode\vcenter
229 \else\@pboxswtrue $\vcenter
230 \fi\fi\fi
231 \@parboxto{\let\hss\vss\let\unhbox\unvbox
232 \csname bm@#3\endcsname}%
233 \if@pboxsw \m@th$\fi
234 \@end@tempboxa}

```

`\@arrayparboxrestore` Restore various paragraph parameters.

The rationale for allowing two normally global flags to be set locally here was stated originally by Donald Arsenau and extended by Chris Rowley. It is because these flags are only set globally to true by section commands, and these should

never appear within boxes or, indeed, in any group; and they are only ever set globally to false when they are definitely true.

If anyone is unhappy with this argument then both flags should be treated as in `\set@nbreak`; otherwise this command will be redundant.

```

235 \end{kernel}
236 \let\@arrayparboxrestore\@arrayparboxrestore
237 \let\@arrayparboxrestore\@arrayparboxrestore
238 \let\@arrayparboxrestore\@arrayparboxrestore
239 \let\@arrayparboxrestore\@arrayparboxrestore
240 \def\@arrayparboxrestore{%
241   \let\if@nbreak\iffalse
242   \let\if@noskipsec\iffalse
243   \let\par\@par
244   \let\-\@dischyph
245   \let\'\@acci\let\'\@accii\let\=\@acciii
246   \parindent\z@ \parskip\z@skip
247   \everypar{}%
248   \linewidth\hsize
249   \@totalleftmargin\z@
250   \leftskip\z@skip \rightskip\z@skip \@rightskip\z@skip
251   \parfillskip\@flushglue
252   \lineskip\normallineskip
253   \lineskiplimit\normallineskiplimit
254   \baselineskip\normalbaselineskip
255   \sloppy}
256 \end{kernel}
257 \let\@arrayparboxrestore\@arrayparboxrestore
258 \let\@arrayparboxrestore\@arrayparboxrestore
259 \let\@arrayparboxrestore\@arrayparboxrestore
260 \let\@arrayparboxrestore\@arrayparboxrestore
261 \def\@arrayparboxrestore{%
262   \let\if@nbreak\iffalse
263   \let\if@noskipsec\iffalse
264   \let\par\@par
265   \let\-\@dischyph
266   \let\'\@acci\let\'\@accii\let\=\@acciii
267   \parindent\z@ \parskip\z@skip
268   \everypar{}%
269   \linewidth\hsize
270   \@totalleftmargin\z@
271   \leftskip\z@skip \rightskip\z@skip \@rightskip\z@skip
272   \parfillskip\@flushglue \lineskip\normallineskip
273   \baselineskip\normalbaselineskip
274   \sloppy}
275 \end{kernel}
276 \let\@arrayparboxrestore\@arrayparboxrestore

```

`\parboxrestore` Restore various paragraph parameters, and also `\.`

```

277 \def\@parboxrestore{\@arrayparboxrestore\let\\\@normalcr}

```

```

\if@minipage Switch that is true at the start of a minipage.
278 \def\@minipagefalse{\global\let\if@minipage\iffalse}
279 \def\@minipagetrue {\global\let\if@minipage\iftrue}
280 \@minipagefalse

\minipage Essentially an environment form of \parbox.
281 \def\minipage{%
282   \@ifnextchar[%]
283     \@iminipage
284     {\@iiiminipage c\relax[s]}}

\@iminipage Optional argument handling.
285 \def\@iminipage[#1]{%
286   \@ifnextchar[%]
287     {\@iiiminipage{#1}}%
288     {\@iiiiminipage{#1}\relax[s]}}

\@iiiminipage Optional argument handling.
289 \def\@iiiminipage#1[#2]{%
290   \@ifnextchar[%]
291     {\@iiiiminipage{#1}{#2}}%
292     {\@iiiiminipage{#1}{#2}[#1]}}

\@iiiiminipage Internal form of minipage.
293 \def\@iiiiminipage#1#2[#3]#4{%
294   \leavevmode
295   \@pboxswfalse
296   \setlength\@tempdima{#4}%
297   \def\@mpargs{{#1}{#2}[#3]{#4}}%
298   \setbox\@tempboxa\vbox\bgroup
299     \color@begingroup
300       \hsize\@tempdima
301       \textwidth\hsize \columnwidth\hsize
302       \@parboxrestore
303       \def\@mpfn{\mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
304       \let\@footnotetext\@mpfootnotetext
305       \let\@listdepth\@mplistdepth \@mplistdepth\z@
306       \@minipagerestore
307       \@setminipage}

\@minipagerestore Hook so that other styles can reset other commands in a minipage.
308 \let\@minipagerestore=\relax

\endminipage
309 \def\endminipage{%
310   \par
311   \unskip
312   \ifvoid\@mpfootins\else
313     \vskip\skip\@mpfootins
314     \normalcolor
315     \footnoterule
316     \unvbox\@mpfootins
317   \fi

```

```

318 \minipagefalse %% added 24 May 89
319 \color@endgroup
320 \egroup
321 \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}}

\@mplistdepth Versions of \@listdepth and \footins local to minipage.
\@mpfootins 322 \newcount\@mplistdepth
323 \newinsert\@mpfootins

\@mpfootnotetext Minipage version of \@footnotetext.
Final \strut added 27 Mar 89, on suggestion by Don Hosek
324 \long\def\@mpfootnotetext#1{%
325 \global\setbox\@mpfootins\vbox{%
326 \unvbox\@mpfootins
327 \reset@font\footnotesize
328 \hsize\columnwidth
329 \@parboxrestore
330 \protected@edef\@currentlabel
331 {\csname p@mpfootnote\endcsname\@thefnmark}%
332 \color@begingroup
333 \@makefntext{%
334 \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
335 \color@endgroup}}

336 \newif\if@pboxsw

\@rule Draw a rule of the specified size.
337 (/2ekernel)
338 (latexrelease)\IncludeInRelease{2015/01/01}%
339 (latexrelease) {\rule}{Make \rule robust}%
340 (*2ekernel | latexrelease)
341 \DeclareRobustCommand\rule{\@ifnextchar[\@rule{\@rule[\z@]}}%
342 (/2ekernel | latexrelease)
343 (latexrelease)\EndIncludeInRelease
344 (latexrelease)\IncludeInRelease{0000/00/00}%
345 (latexrelease) {\rule}{Make \rule robust}%
346 (latexrelease)\def\rule{\@ifnextchar[\@rule{\@rule[\z@]}}%
347 (latexrelease)\expandafter\let\csname rule \endcsname\@undefined
348 (latexrelease)\EndIncludeInRelease
349 (*2ekernel)

\@rule Internal form of \rule.
350 \def\@rule[#1]#2#3{%
351 \leavevmode
352 \hbox{%
353 \setlength\@tempdima{#1}%
354 \setlength\@tempdimb{#2}%
355 \setlength\@tempdimc{#3}%
356 \advance\@tempdimc\@tempdima
357 \vrule\@width\@tempdimb\@height\@tempdimc\@depth-\@tempdima}}

\@@underline Saved primitive \underline.
358 \let\@@underline\underline

```

`\underline` L<sup>A</sup>T<sub>E</sub>X version works outside math.

```

359 \DeclareRobustCommand\underline[1]{%
360   \relax
361   \ifmmode\@@underline{#1}%
362   \else $\@@underline{\hbox{#1}}\m@th$\relax\fi}

```

`\raisebox` Raise a box, and change its vertical dimensions.

```

363 \ifx\@ifnextchar\@ifnextchar
364 \ifx\@ifnextchar\@ifnextchar
365 \ifx\@ifnextchar\@ifnextchar
366 \ifx\@ifnextchar\@ifnextchar
367 \ifx\@ifnextchar\@ifnextchar
368 \ifx\@ifnextchar\@ifnextchar
369 \ifx\@ifnextchar\@ifnextchar
370 \ifx\@ifnextchar\@ifnextchar
371 \ifx\@ifnextchar\@ifnextchar
372 \ifx\@ifnextchar\@ifnextchar
373 \ifx\@ifnextchar\@ifnextchar
374 \ifx\@ifnextchar\@ifnextchar
375 \ifx\@ifnextchar\@ifnextchar
376 \ifx\@ifnextchar\@ifnextchar
377 \ifx\@ifnextchar\@ifnextchar
378 \ifx\@ifnextchar\@ifnextchar
379 \ifx\@ifnextchar\@ifnextchar

```

`\@rsbox` Optional argument handling.

```

380 \def\@rsbox#1[#2]{%
381   \ifnextchar\@iirsbox{#1}[#2]{\@irsbox{#1}[#2]}

```

`\@argsbox` ...

`\@irsbox` Internal version of `\raisebox` (less than two optional args).

```

382 \long\def\@irsbox#1[#2][#3]{%
383   \begin@tempboxa\hbox{#3}%
384   \setlength\@tempdima{#1}%
385   \ifx\@rsbox\@rsbox\else\setlength\@tempdimb{#2}\fi
386   \setbox\@tempboxa\hbox{\raise\@tempdima\box\@tempboxa}%
387   \ifx\@rsbox\@rsbox\else\ht\@tempboxa\@tempdimb\fi
388   \box\@tempboxa
389   \end@tempboxa}

```

`\@iirsbox` Internal version of `\raisebox` (two optional args).

```

390 \long\def\@iirsbox#1[#2][#3][#4]{%
391   \begin@tempboxa\hbox{#4}%
392   \setlength\@tempdima{#1}%
393   \setlength\@tempdimb{#2}%
394   \setlength\dimen@{#3}%
395   \setbox\@tempboxa\hbox{\raise\@tempdima\box\@tempboxa}%
396   \ht\@tempboxa\@tempdimb
397   \dp\@tempboxa\dimen@
398   \box\@tempboxa
399   \end@tempboxa}

```

`\@finalstrut` This macro adds a special strut the *depth* of the box given as `#1`, and height and width 0pt. It is used for ensuring that the last line of a paragraph has the correct depth in ‘p’ columns of tables and in footnotes. In vertical mode nothing is done, as adding the strut (as done in 2.09) would start a new paragraph. It would be possible to inspect `\prevdepth` to check the depth of the just-completed paragraph, but we do not do that here. Actually we do even less now, skip the vmode test as it broke tabular ‘p’ columns. .

The `\nobreak` was added (1995/10/31) to allow hyphenation of the final word of the paragraph.

```
400 \def\@finalstrut#1{%
401   \unskip\ifhmode\nobreak\fi\vrule\@width\z@\@height\z@\@depth\dp#1}
```

## 56.1 Some low-level constructs

The following commands are basically inherited from plain T<sub>E</sub>X.

<code>\leftline</code>	These macros place text on a full line either centred or left or right adjusted.
<code>\rightline</code>	
<code>\centerline</code>	
<code>\@@line</code>	

```

402 \def\@@line{\hb@xt@\hsize}
403 \DeclareRobustCommand\leftline[1]{\@@line{#1\hss}}
404 \DeclareRobustCommand\rightline[1]{\@@line{\hss#1}}
405 \DeclareRobustCommand\centerline[1]{\@@line{\hss#1\hss}}

\rlap These macros place text to the left or right of the current reference point without
\llap taking up space.

406 \DeclareRobustCommand\rlap[1]{\hb@xt@\z@{#1\hss}}
407 \DeclareRobustCommand\llap[1]{\hb@xt@\z@{\hss#1}}

408 \endkernel
```



## File C

# lftab.dtx

## 57 Tabbing, Tabular and Array Environments

This section deals with ‘Lining It Up in Columns’. First the `tabbing` environment is defined, and then in second part, `tabular` together with its variants, `tabular*` and `array`.

Note that the `tabular` defined here is essentially the original L<sup>A</sup>T<sub>E</sub>X 2.09 version, not the extended version described in *The L<sup>A</sup>T<sub>E</sub>X Companion*. Use the `array` package to obtain the extended version.

### 57.1 tabbing

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

`\dimen\@firsttab + i` = distance of tab stop `i` from left margin  
0 <= `i` <= 15 (?).

`\dimen\@firsttab` is initialized to `\@totalleftmargin`, so it starts at the prevailing left margin.

`\@maxtab` = number of highest defined tab register  
probably = `\@firsttab + 12`

`\@nxttabmar` = tab stop number of next line’s left margin

`\@curtabmar` = tab stop number of current line’s left margin

`\@curtab` = number of the current tab. At start of line,  
it equals `\@curtabmar`

`\@hightab` = largest tab number currently defined.

`\@tabpush` = depth of `\pushtab`’s

`\box\@curline` = contents of current line, excluding left margin  
skip, and excluding contents of current field

`\box\@curfield` = contents of current field

`@rjfield` = switch: T iff the last field of the line should  
be right-justified at the right margin.

`\tabbingsep` = distance left by the `\’` command between the  
current position and the field that is  
“left-shifted”.

#### UTILITY MACROS

`\@stopfield` : closes the current field

`\@addfield` : adds the current field to the current line.

`\@contfield` : continues the current field

`\@startfield` : begins the next field

`\@stopline` : closes the current line and outputs it

```

\@startline : starts the next line
\@ifatmargin : an \if that is true iff the current line.
                has width zero

\@startline ==
BEGIN
  \@curtabmar :=G \@nxttabmar
  \@curtab :=G \@curtabmar
  \box\@curline :=G null
  \@startfield
  \strut
END

\@stopline ==
BEGIN
  \unskip
  \@stopfield
  if @rjfield = T
    then @rjfield :=G F
      \@tempdima := \@totalleftmargin + \linewidth
      \hb@xt@ \@tempdima{\@itemfudge
                          \hskip \dimen\@curtabmar
                          \box\@curline
                          \hfil
                          \box\@curfield}
    else \@addfield
      \hbox {\@itemfudge
            \hskip \dimen\@curtabmar
            \box\@curline}
    fi
  END

\@startfield ==
BEGIN
  \box\@curfield :=G \hbox {
  END

\@stopfield ==
BEGIN
  }
  END

\@contfield ==
BEGIN
  \box\@curfield :=G \hbox { \unhbox\@currfield %%} brace
matching
  END
\@addfield ==
BEGIN
  \box\@curline :=G \unbox\@curline * \unbox\@curfield

```

```

END

\@ifatmargin ==
BEGIN
  if dim of box\@curline = 0pt then
  END

\@tabbing ==
BEGIN
  \lineskip :=L 0pt
  \> == \@rtab
  \< == \@ltab
  \= == \@settab
  \+ == \@tabplus
  \- == \@tabminus
  \‘ == \@tabrj
  \’ == \@tablab
  \\\ == BEGIN \@stopline \@startline END
  \\[DIST] == BEGIN
    \@stopline \vskip DIST \@startline\ignorespaces
  END
  \\\* == BEGIN \@stopline \penalty 10000 \@startline END
  \\[DIST] == BEGIN \@stopline \penalty 10000 \vskip DIST
    \@startline\ignorespaces END
  \@hightab := \@nxxtabmar :=G \@firsttab
  \@tabpush :=G 0
  \dimen\@firsttab := \@totalleftmargin
  @rjfield :=G F
  \trivlist \item\relax
  if @minipage = F then \vskip \parskip fi
  \box\@tabfbox = \rlap{\indent\the\everypar}
    % note: \the\everypar sets @inlabel :=G F
  \@itemfudge == BEGIN \box\@tabfbox END
  \@startline
  \ignorespaces
  END

\@endtabbing ==
BEGIN
  \@stopline
  if \@tabpush > 0 then error message: "unmatched \poptabs" fi
  \endtrivlist
  END

\@rtab ==
BEGIN
  \@stopfield
  \@addfield
  if \@curtab < \@hightab

```

```

        then \@curtab :=G \@curtab + 1
        else error message "Undefined Tab"    fi
    \@tempdima := \dimen\@curtab - \dimen\@curtabmar
                - width of box \@curline
    \box\@curline :=G \hbox{\unhbox\@curline + \hskip\@tempdima}
    \@startfield
END

\@settab ==
BEGIN
    \@stopfield
    \@addfield
    if \@curtab < \@maxtab
        then \@curtab :=G \@curtab+1
        else error message: "Too many tabs"    fi
    if \@curtab > \@hightab
        then \@hightab :=L \@curtab    fi
    \dimen\@curtab :=L \dimen\@curtabmar + width of \box\@curline
    \@startfield
END

\@ltab ==
BEGIN
    \@ifatmargin
        then if \@curtabmar > \@firsttab
            then \@curtab :=G \@curtab - 1
                \@curtabmar :=G \@curtabmar - 1
            else error message "Too many untab"    fi
        else error message "Left tab in middle of line"
        fi
END

\@tabplus ==
BEGIN
    if \@nxxtabmar < \@hightab
        then \@nxxtabmar :=G \@nxxtabmar+1
        else error message "Undefined tab"
        fi
END

\@tabminus ==
BEGIN
    if \@nxxtabmar > \@firsttab
        then \@nxxtabmar :=G \@nxxtabmar-1
        else error message "Too many untab"
        fi
END

\@tabrj ==
BEGIN \@stopfield

```

```

        \@addfield
        @rjfield :=G T
        \@startfield
    END

\@tablab ==
BEGIN \@stopfield
    \box\@curline G:= \hbox{\box\@curline %% 'G' added 17 Jun 86
        \hskip - width of \box\@curfield
        \hskip -\tabbingsep
        \box\@curfield
        \hskip \tabbingsep }

    \@startfield
END

\pushtabs ==
BEGIN
    \@stopfield
    \@tabpush :=G \@tabpush + 1
    \begingroup
    \@contfield
END

\poptabs ==
BEGIN
    \@stopfield
    if \@tabpush > 0
    then \endgroup
        \@tabpush :=G \@tabpush - 1
    else error message: "Too many \poptabs"
    fi
    \@contfield
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

- \a The accents \‘ , \’ , and \= that have been redefined inside a tabbing environment can be called by typing \a‘ , \a’ , and \a=. The macro \a is defined in `ltoutenc.dtx`.

The ‘2ekernel’ code ensures that a `\usepackage{autotabg}` is essentially ignored if a ‘full’ format is being used that has picture mode already in the format.

```

1 \<2ekernel>\expandafter\let\csname ver@autotabg.sty\endcsname\fmtversion

\@firsttab
\@maxtab
2 \*2ekernel)
3 \newdimen\@gtempa
4 \chardef\@firsttab=\the\allocationnumber
5 \newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa
6 \newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa
7 \newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa

```

```

8 \newdimen\@gtempa
9 \chardef\@maxtab=\the\allocationnumber
10 \dimen\@firsttab=0pt

\@nxttabmar
\@curtabmar 11 \newcount\@nxttabmar
\@curtab 12 \newcount\@curtabmar
\@hightab 13 \newcount\@curtab
\@tabpush 14 \newcount\@hightab
15 \newcount\@tabpush

\@curline
\@curfield 16 \newbox\@curline
\@tabfbox 17 \newbox\@curfield
18 \newbox\@tabfbox

\if@rjfield
19 \newif\if@rjfield

\@startline It is, in some sense, an error if the current margin tab setting is higher than
the value of \@hightab (which is a local variable). That this is allowed is a
fundamental design flaw which is not going to be corrected now.
20 \def\@startline{%
21     \ifnum \@nxttabmar > \@hightab
22         \@badtab
23         \global\@nxttabmar \@hightab
24     \fi
25     \global\@curtabmar \@nxttabmar
26     \global\@curtab \@curtabmar
27     \global\setbox\@curline \hbox {%
28         \@startfield
29         \strut}

\@stopline
30 \def\@stopline{%
31     \unskip
32     \@stopfield
33     \if@rjfield
34         \global\@rjfieldfalse
35         \@tempdima\@totalleftmargin
36         \advance\@tempdima\linewidth
37         \hb@xt@\@tempdima{%
38             \@itemfudge\hskip\dimen\@curtabmar
39             \box\@curline
40             \hfil
41             \box\@curfield}%
42     \else
43         \@addfield
44         \hbox{\@itemfudge\hskip\dimen\@curtabmar\box\@curline}%
45     \fi}

\@startfield
46 \def\@startfield{%
47     \global\setbox\@curfield\hbox\bgroup\color@begingroup}

```

```

\@stopfield
48 \def\@stopfield{%
49   \color@endgroup\egroup}

\@contfield
50 \def\@contfield{%
51   \global\setbox\@curfield\hbox\bgroup\color@begingroup
52   \unhbox\@curfield}

\@addfield
53 \def\@addfield{\global\setbox\@curline\hbox{\unhbox
54   \@curline\unhbox\@curfield}}

\@ifatmargin
55 \def\@ifatmargin{\ifdim \wd\@curline =\z@}

\@tabcr
56 \def\@tabcr{\@stopline \ifstar{\penalty \@M \@xtabcr}\@xtabcr}

\@xtabcr
57 \def\@xtabcr{\@ifnextchar[\@itabcr{\@startline\ignorespaces}}

\@itabcr
58 \def\@itabcr[#1]{\vskip #1\@startline\ignorespaces}

\tabbing We use \relax to prevent \item from scanning too far.
59 \def\tabbing{\lineskip \z@skip\let>\@rtab\let<\@ltab\let\=\@settab
60   \let+\@tabplus\let-\@tabminus\let'\@tabrj\let'\@tablab
61   \let\=\@tabcr
62   \@hightab\@firsttab
63   \global\@nxttabmar\@firsttab
64   \dimen\@firsttab\@totalleftmargin
65   \global\@tabpush\z@ \global\@rjfieldfalse
66   \trivlist \item\relax
67   \if@minipage\else\vskip\parskip\fi

68   \setbox\@tabfbox\hbox{%
69     \rlap{\hskip\@totalleftmargin\indent\the\everypar}}%
70   \def\@itemfudge{\box\@tabfbox}%
71   \@startline\ignorespaces}

\endtabbing
72 \def\endtabbing{%
73   \@stopline\ifnum\@tabpush >\z@ \@badpoptabs \fi\endtrivlist}

\@rtab Omitted \global added to \@rtab 17 Jun 86
74 \def\@rtab{\@stopfield\@addfield\ifnum \@curtab<\@hightab
75   \global\advance\@curtab \@ne \else\@badtab\fi
76   \@tempdima\dimen\@curtab
77   \advance\@tempdima -\dimen\@curtabmar
78   \advance\@tempdima -\wd\@curline
79   \global\setbox\@curline\hbox{\unhbox\@curline\hskip\@tempdima}%
80   \@startfield\ignorespaces}

```

\@settab

```
81 \def\@settab{\@stopfield\@addfield
82   \ifnum \@curtab <\@maxtab
83     \ifnum\@curtab =\@hightab
84       \advance\@hightab \@ne
85     \fi
86     \global\advance\@curtab \@ne
87   \else
88     \@latex@error{Tab overflow}\@ehd
89   \fi
90   \dimen\@curtab \dimen\@curtabmar
91   \advance\dimen\@curtab \wd\@curline
92   \@startfield
93   \ignorespaces}
```

\@ltab

```
94 \def\@ltab{\@ifatmargin\ifnum\@curtabmar >\@firsttab
95   \global\advance\@curtab \m@ne \global\advance\@curtabmar\m@ne\else
96   \@badtab\fi\else
97   \@latex@error{string<\space in mid line}\@ehd\fi\ignorespaces}
```

\@tabplus

```
98 \def\@tabplus{%
99   \ifnum\@nxttabmar<\@hightab
100     \global\advance\@nxttabmar\@ne
101   \else
102     \@badtab
103   \fi
104   \ignorespaces}
```

\@tabminus

```
105 \def\@tabminus{%
106   \ifnum\@nxttabmar>\@firsttab
107     \global\advance\@nxttabmar\m@ne
108   \else
109     \@badtab
110   \fi
111   \ignorespaces}
```

\@tabrj

```
112 \def\@tabrj{%
113   \@stopfield\@addfield\global\@rjfieldtrue\@startfield\ignorespaces}
```

\@tablab \setbox\@curline made \global in \@tablab. 17 Jun 86

```
114 \def\@tablab{%
115   \@stopfield
116   \global\setbox\@curline\hbox{%
117     \box\@curline
118     \hskip-\wd\@curfield \hskip-\tabbingsep
119     \box\@curfield
120     \hskip\tabbingsep}%
121   \@startfield
122   \ignorespaces}
```



```

123 </2ekernel>
124 <*2ekernel | latexrelease>
125 <latexrelease>\IncludeInRelease{2019/10/01}%
126 <latexrelease>                {\pushtabs}{Make commands robust}%

\pushtabs
127 \DeclareRobustCommand\pushtabs{%
128   \@stopfield\@addfield\global\advance\@tabpush \@ne \begingroup
129     \@contfield}

\poptabs It is, in some sense, an error if, after the endgroup, the current tab setting is higher
          than the new value of \@hightab (which is a local variable). That this is allowed
          is a fundamental design flaw which is not going to be corrected now.
130 \DeclareRobustCommand\poptabs{\@stopfield\@addfield
131   \ifnum \@tabpush >\z@
132     \endgroup
133     \global\advance\@tabpush \m@ne
134     \ifnum \@curtab >\@hightab
135       \global \@curtab \@hightab
136       \@badtab
137     \fi
138   \else
139     \@badpoptabs
140   \fi
141   \@contfield}

142 \DeclareRobustCommand\kill{\@stopfield\@startline\ignorespaces}

143 </2ekernel | latexrelease>
144 <latexrelease>\EndIncludeInRelease
145 <latexrelease>\IncludeInRelease{0000/00/00}%
146 <latexrelease>                {\pushtabs}{Make commands robust}%
147 <latexrelease>
148 <latexrelease>\kernel@make@fragile\pushtabs
149 <latexrelease>\kernel@make@fragile\poptabs
150 <latexrelease>\kernel@make@fragile\kill
151 <latexrelease>
152 <latexrelease>\EndIncludeInRelease
153 <*2ekernel>

\tabbingsep
154 \newdimen\tabbingsep

```

## 57.2 array and tabular environments

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

ARRAY PARAMETERS:

```

\arraycolsep
    : half the width separating columns in an array environment
\tabcolsep
    : half the width separating columns in a tabular environment
\arrayrulewidth

```

`:` width of rules  
`\doublerulesep`  
`:` space between adjacent rules in array or tabular  
`\arraystretch`  
`:` line spacing in array and tabular environments is done by placing a strut in every row of height and depth `\arraystretch` times the height and depth of the strut produced by an ordinary `\strut` command.

#### PREAMBLE:

The PREAMBLE argument of an array or tabular environment can contain the following:  
`l,r,c` : indicate where entry is to be placed.  
`|` : for vertical rule  
`@{EXP}` : inserts the text EXP in every column.  
`\arraycolsep` or `\tabcolsep` spacing is suppressed.  
`*{N}{PRE}` : equivalent to writing N copies of PRE in the preamble. PRE may contain `*{N'}{EXP'}` expressions.  
`p{LEN}` : makes entry in parbox of width LEN.

#### SPECIAL ARRAY COMMANDS:

`\multicolumn{N}{FORMAT}{ITEM}` : replaces the next N column items by ITEM, formatted according to FORMAT.  
 FORMAT should contain at most one `l,r` or `c`.  
 If it contains none, then ITEM is ignored.  
  
`\vline` : draws a vertical line the height of the current row. May appear in an array element entry.  
`\hline` : draws a horizontal line between rows. Must appear either before the first entry (to appear above the first row) or right after a `\\` command. If followed by another `\hline`, then adds a `\vskip` of `\doublerulesep`.  
  
`\cline{i-j}` : draws horizontal lines between rows covering columns i through j, inclusive. Multiple commands may follow one another to provide lines covering several disjoint columns  
`\extracolsep{WIDTH}` : for use inside an `@` in the preamble. Causes a WIDTH space to be added between columns for the rest of the columns. This is in addition to the ordinary intercolumn space.

```

\array ==
  BEGIN
    \@acol    == \@arrayacol
    \@classz  == \@arrayclassz
    \@classiv == \@arrayclassiv
    \\        == \@arraycr
    \@halignto == NULL
    \@tabarray
  
```

```

END

\endarray{NAME} == BEGIN \crrc }} END

\tabular ==
  BEGIN
    \@halignto == NULL
    \@tabular
  END

\tabular*{WIDTH} ==
  BEGIN
    \@halignto == to WIDTH
    \@tabular
  END

\@tabular ==
  BEGIN
    \leavevmode
    \hbox { $
      \@acol == \@tabacol
      \@classz == \@tabclassz
      \@classiv == \@tabclassiv
      \\\ == \@tabularcrrc
      \@tabarray
    END

\endtabular == BEGIN \crrc}} $} END

\@tabarray == if next char = [ then \@array else \@array[c] fi

\@array[POS]{PREAMBLE} ==
  BEGIN
    define \@arstrutbox to make \@arstrut produce strut of height
      and depth \arraystretch times the height and
      depth of a normal strut.
    \@mkpream{PREAMBLE}
    \@preamble == \halign \@halignto {\tabskip=0pt\@arstrut
      eval{\@preamble}\tabskip = 0pt\crrc %%}
    \@startpbox == \@@startpbox
    \@endpbox == \@@endpbox
    if POS = t then \vtop
      else if POS = b then \vbox
        else \vcenter
      fi
    fi
    {
      \par ==L {} % changed 92/09/18
      \@sharp == #
      \protect == \relax
      \lineskip :=L 0pt
    }
  END

```

```

\baselineskip :=L 0pt
\@preamble
END

\@arraycr ==
BEGIN
$ %% Prevents extra space at end of row's last entry.
if next char = [
then \@argarraycr
else $ \cr %% Needed to balance $
END

\@argarraycr[LENGTH] ==
BEGIN
$ %% Needed to balance $ of \@arraycr
if LENGTH > 0
then \@tempdima := depth of \@arstrutbox + LENGTH
\vrule height 0pt width 0pt depth \@tempdima
\cr
else \cr \noalign{\vskip LENGTH}
END

\@tabularcr and \@argtabularcr same as \@arraycr and
\@argarraycr
except without the extra $'s.
End of historical LATEX 2.09 comments.

\extracolsep This command needs to expand during the tabular preamble construction so can't
be robust.
155 \def\extracolsep#1{\tabskip #1\relax}

\array
156 \def\array{\let\@acol\@arrayacol \let\@classz\@arrayclassz
157 \let\@classiv\@arrayclassiv
158 \let\\\@arraycr\let\@halignto\@empty\@tabarray}

\endarray
\endtabular 159 \def\endarray{\crrcr\egroup\egroup}
\endtabular* 160 \def\endtabular{\crrcr\egroup\egroup $\egroup}
161 \expandafter \let \csname endtabular*\endcsname = \endtabular

\tabular
162 \def\tabular{\let\@halignto\@empty\@tabular}

\tabular* Note that the change to use \setlength slightly alters the timing of the expansion
and use of the length in #1 but this is very unlikely to have any practical effect.
163 \@namedef{tabular*}#1{%
164 \setlength\dimen@{#1}%
165 \edef\@halignto{to\the\dimen@}\@tabular}

```

```

\@tabular
166 \def\@tabular{\leavevmode \hbox \bgroup $\let\@acol\@tabacol
167 \let\@classz\@tabclassz
168 \let\@classiv\@tabclassiv \let\\\@tabularcr\@tabarray}

\@tabarray RmS 91/11/04 added \m@th.
169 \def\@tabarray{\m@th\ifnextchar[\@array{\@array[c]}}

RmS 1993/11/03 changed \halign to \ialign and removed superfluous
\tabskip assignment

\@array
170 \def\@array[#1]#2{%
171 \if #1t\vtop \else \if#1b\vbox \else \vcenter \fi\fi
172 \bgroup

This next bit of code sets up the strut and then builds the halign and its preamble
according to the specification in the second argument.

This code has been moved inside the box. A side effect of this has been to
expose what was a buglet in the previous version: since the \@arstrut below is
expanded and contains an \ifmmode then it could produce an unnecessary extra
box in every row, thus wasting ‘lots of’ main memory.

173 \setbox\@arstrutbox\hbox{%
174 \vrule \@height\arraystretch\ht\strutbox
175 \@depth\arraystretch \dp\strutbox
176 \@width\z@}%
177 \mkpream{#2}%
178 \edef\@preamble{%
179 \ialign \noexpand\@halignto
180 \bgroup \@arstrut \@preamble \tabskip\z@skip \cr}%

That is the end of setting up the preamble; now we reset things before executing
the halign built-up in \@preamble. The restorations could be done by introducing
an extra group, thus saving tokens.

181 \let\@startpbox\@startpbox \let\@endpbox\@endpbox
182 \let\tabularnewline\\%
183 \let\par\@empty
184 \let\@sharp##%
185 \set@typeset@protect
186 \lineskip\z@skip\baselineskip\z@skip

If the parsing of the preamble goes wrong there may be some characters left which
TeX then tries to typeset, i.e., we would be in horizontal mode. That would
produce an endless loop because the \halign expects vertical mode thus issues a
\par but that is a no-op at this point. So we better test this case issue some error
message and make a crude recovery by ending that horizontal mode with force. A
better fix would be to ensure that we never pick up more than a single character
token (not done).

187 \ifhmode \@preamerr\z@ \@@par\fi
188 \@preamble}

\@arraycr Array version of \\.
189 \def\@arraycr{%
190 ${\ifnum0='}\fi\@ifstar\@xarraycr\@arraycr}

```

```

\@arraycr
191 \def\@xarraycr{\@ifnextchar[\@argarraycr{\ifnum0='{ \fi}$\}\cr}}

\@argarraycr
192 \def\@argarraycr[#1]{%
193   \ifnum0='{ \fi}$\}\ifdim #1>\z@ \@xargarraycr{#1}\else
194     \@yargarraycr{#1}\fi}

\tabularnewline Tabular version of \\.
195 \let\tabularnewline\relax

\@tabularcr
196 \def\@tabularcr{%
197   {\ifnum0='{ \fi}\@ifstar\@xtabularcr\@xtabularcr}

\@xtabularcr
198 \def\@xtabularcr{\@ifnextchar[\@argtabularcr{\ifnum0='{ \fi}\cr}}

\@argtabularcr
199 \def\@argtabularcr[#1]{%
200   \ifnum0='{ \fi}%
201   \ifdim #1>\z@
202     \unskip\@xargarraycr{#1}%
203   \else
204     \@yargarraycr{#1}%
205   \fi}

\@xargarraycr
206 \def\@xargarraycr#1{\@tempdima #1\advance\@tempdima \dp \@arstrutbox
207   \vrule \@height\z@ \@depth\@tempdima \@width\z@ \cr}

\@yargarraycr
208 \def\@yargarraycr#1{\cr\noalign{\vskip #1}}

\multicolumn Historical LATEX 2.09 comments (not necessarily accurate any more):
\multicolumn{NUMBER}{FORMAT}{ITEM} ==
BEGIN
\multispan{NUMBER}
\begingroup
\@addamp == null
\@mkpream{FORMAT}
\@sharp == ITEM
\protect == \relax
\@startpbox == \@@startpbox
\@endpbox == \@@endpbox
\@arstrut
\@preamble
\endgroup
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

The command `\def\@addamp{}` was removed from `\multicolumn` on 6 Dec 86 because it caused embedded array environments not to work. I think that it

was included originally to prevent an error message if the 2nd argument to the `\multicolumn` command had two column specifiers.

8 Feb 89 — `\hbox{}` added after `\@preamble` to correct bug that occurred if `\multicolumn` preceded `\\[D]` with  $D > 0$ , caused by `\\[]` command doing an `\unskip`, which removed `\tabcolsep` glue inserted by `\multicolumn`.

This has been made long so that, for example, a p-column can contain multiple paragraphs; maybe the arguments of @-expressions should also be able to contain multiple paragraphs.

```
209 \long\def\multicolumn#1#2#3{\multispan{#1}\begingroup
210   \mkpream{#2}%
211   \def\@sharp{#3}\set@typeset@protect
212   \let\@startpbox\@startpbox\let\@endpbox\@endpbox
213   \@arstrut \@preamble\hbox{}\endgroup\ignorespaces}
```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

Codes for classes and character numbers of array, tabular and multicolumn arguments.

Character	Class	Number
c	0	0
l	0	1
r	0	2
l	1	-
@	2	-
p	3	-
{@-exp}	4	-
{p-arg}	5	-

`\@testpach \foo` : expands `\foo`, which should be an array parameter token, and sets `\@chclass` and `\@chnum` to its class and number. Uses `\@lastchclass` to distinguish 4 and 5

Preamble error codes

- 0: 'illegal character'
- 1: 'Missing @-exp'
- 2: 'Missing p-arg'

```
\@addamp ==
BEGIN if \@firstamp = true then \@firstamp := false
                                     else &                               fi
END
```

```
\@mkpream TOKENLIST ==
BEGIN
  \@firstamp      := T
  \@lastchclass   := 6
  \@preamble      == null
  \@sharp         == \relax
```

```

\protect      == BEGIN \noexpand\protect\noexpand END
\@startpbox   == \relax
\@endpbox     == \relax
\@expast{TOKENLIST}
for \@nextchar := expand(\reserved@a)
do \@testpach{\@nextchar}
  case of \@chclass
    0 -> \@classz
    1 -> \@classi
    ...
    5 -> \@classv
  end case
  \@lastchclass := \@chclass
od
case of \@lastchclass
  0 -> \hskip \arraycolsep           % lrc
  1 ->                               % l
  2 -> \@preamerr1 % 'Missing @-exp' % @
  3 -> \@preamerr2 % 'Missing p-arg' % p
  4 ->                               % @-exp
  5 -> \hskip \arraycolsep           % p-exp
end case
END

\@arrayclassz ==
BEGIN
  \@preamble := \@preamble *
  case of \@lastchclass
    0 -> \hskip \arraycolsep \@addamp \hskip
\arraycolsep
    1 -> \@addamp \hskip \arraycolsep
    2 -> % impossible
    3 -> % impossible
    4 -> \@addamp
    5 -> \hskip \arraycolsep \@addamp \hskip
\arraycolsep
    6 -> \@addamp \hskip \arraycolsep
  end case
  * case of \@chnum
    0 -> \hfil$\relax\@sharp$\hfil
    1 -> $\relax\@sharp$\hfil
    2 -> \hfil$\relax\@sharp$
  end case
END

\@tabclassz == similar to \@arrayclassz

\@classi ==
BEGIN
  \@preamble := \@preamble *

```



```

                                case of \@lastchclass
                                0 -> \hskip \arraycolsep \@arrayrule
                                1 -> \hskip \doublerulesep \@arrayrule
                                2 -> % impossible
                                3 -> % impossible
                                4 -> \@arrayrule
                                5 -> \hskip \arraycolsep \@arrayrule
                                6 -> \@arrayrule
                                end case
END

\@classii ==
BEGIN
  \@preamble := \@preamble *
                                case of \@lastchclass
                                0 ->
                                1 -> \hskip .5\arrayrulewidth
                                2 -> % impossible
                                else ->
                                end case
END

\@classiii ==
BEGIN
  \@preamble := \@preamble *
                                case of \@lastchclass
                                0 -> \hskip \arraycolsep \@addamp \hskip
\arraycolsep
                                1 -> \@addamp \hskip \arraycolsep
                                2 -> % impossible
                                3 -> % impossible
                                4 -> \@addamp
                                5 -> \hskip \arraycolsep \@addamp \hskip
\arraycolsep
                                6 -> \@addamp \hskip \arraycolsep
                                end case
END

\@arrayclassiv ==
BEGIN \@preamble := \@preamble * $ \@nextchar$ END

\@tabclassiv == same as \@arrayclassiv except without the $ ... $

\@classv ==
BEGIN
  \@preamble :=
    \@preamble * \@startpbox{\@nextchar}\ignorespaces\@sharp
    \@endpbox
END

```

```

\@expast{S}:
  Sets \reserved@a := S with all instances of *{N}{STRING}
  replaced by N copies of STRING, where N > 0. An *
  appearing inside braces is ignored, but *-expressions
  inside STRING are expanded, so nested *-expressions are
  handled properly.

\@expast{S} == BEGIN \@exexpast S *0x\@@ END

\@exexpast S1 *{N}{S2} S3 \@@ ==
BEGIN
  \reserved@a := S1
  \@tempcnta := N
  if \@tempcnta > 0
    then while \@tempcnta > 0 do \reserved@a := \reserved@a S2
      \@tempcnta := \@tempcnta - 1 od
      \reserved@b == \@exexpast
    else \reserved@b == \@exnoop
    fi
  \expandafter \reserved@b \reserved@a S3 \@@
END
End of historical LATEX 2.09 comments.

\@exnoop
214 \def\@exnoop #1\@@{}

\@expast
215 \def\@expast#1{\@exexpast #1*0x\@@}

\@expast
216 \def\@expast#1*#2#3#4\@@{%
217   \edef\reserved@a{#1}%
218   \@tempcnta#2\relax
219   \ifnum\@tempcnta>\z@
220     \@whilenum\@tempcnta>\z@\do
221       {\edef\reserved@a{\reserved@a#3}\advance\@tempcnta \m@ne}%
222     \let\reserved@b\@expast
223   \else
224     \let\reserved@b\@exnoop
225   \fi
226   \expandafter\reserved@b\reserved@a #4\@@}

\if@firstamp
  \@addamp 227 \newif\if@firstamp
228 \def\@addamp{%
229   \if@firstamp
230     \@firstampfalse
231   \else
232     \edef\@preamble{\@preamble &}%
233   \fi}

```

```

\@arrayacol
\@tabacol 234 \def\@arrayacol{\edef\@preamble{\@preamble \hskip \arraycolsep}}
\@ampacol 235 \def\@tabacol{\edef\@preamble{\@preamble \hskip \tabcolsep}}
\@acolampacol 236 \def\@ampacol{\@addamp \@acol}
237 \def\@acolampacol{\@acol\@addamp\@acol}

\@mkpream
238 \def\@mkpream#1{\@firstampttrue\@lastchclass6
239 \let\@preamble\@empty
240 \let\protect\@unexpandable@protect
241 \let\@sharp\relax
242 \let\@startpbox\relax\let\@endpbox\relax
243 \@expast{#1}%
244 \expandafter\@tfor \expandafter
245 \nextchar \expandafter:\expandafter=\reserved@a\do
246 {\@testpach\@nextchar
247 \ifcase \@chclass \@classz \or \@classi \or \@classii \or \@classiii
248 \or \@classiv \or \@classv \fi\@lastchclass\@chclass}%
249 \ifcase \@lastchclass \@acol
250 \or \or \@preamerr \@one\or \@preamerr \tw@\or \or \@acol \fi}

\@arrayclassz
251 \def\@arrayclassz{\ifcase \@lastchclass \@acolampacol \or \@ampacol \or
252 \or \or \@addamp \or
253 \@acolampacol \or \@firstampfalse \@acol \fi
254 \edef\@preamble{\@preamble
255 \ifcase \@chnum
256 \hfil$\relax\@sharp$\hfil \or $\relax\@sharp$\hfil
257 \or \hfil$\relax\@sharp$\fi}}

\@tabclassz RmS 91/08/14 inserted extra braces around entry for NFSS
258 \def\@tabclassz{%
259 \ifcase\@lastchclass
260 \@acolampacol
261 \or
262 \@ampacol
263 \or
264 \or
265 \or
266 \@addamp
267 \or
268 \@acolampacol
269 \or
270 \@firstampfalse\@acol
271 \fi
272 \edef\@preamble{%
273 \@preamble{%
274 \ifcase\@chnum
275 \hfil
276 \hskip1sp%
277 \ignorespaces\@sharp\unskip\hfil
278 \or

```

```

279      \hskip1sp\ignorespaces\@sharp\unskip\hfil
280      \or
281      \hfil\hskip1sp\ignorespaces\@sharp\unskip
282      \fi}}

\@classi
283 \def\@classi{%
284   \ifcase\@lastchclass
285     \@acol\@arrayrule
286   \or
287     \@addtopreamble{\hskip \doublerulesep}\@arrayrule
288   \or
289   \or
290   \or
291     \@arrayrule
292   \or
293     \@acol\@arrayrule
294   \or
295     \@arrayrule
296   \fi}

\@classii
297 \def\@classii{%
298   \ifcase\@lastchclass
299   \or
300     \@addtopreamble{\hskip .5\arrayrulewidth}%
301   \fi}

\@classiii
302 \def\@classiii{\ifcase \@lastchclass \@acolampacol \or
303   \@addamp\@acol \or
304   \or \or \@addamp \or
305   \@acolampacol \or \@ampacol \fi}

\@tabclassiv
306 \def\@tabclassiv{\@addtopreamble\@nextchar}

\@arrayclassiv
307 \def\@arrayclassiv{\@addtopreamble{$\@nextchar$}}

\@classv
308 \def\@classv{\@addtopreamble{\@startpbox{\@nextchar}\ignorespaces
309 \@sharp\@endpbox}}

\@addtopreamble
310 \def\@addtopreamble#1{\edef\@preamble{\@preamble #1}}

\@chclass
\@lastchclass 311 \newcount\@chclass
\@chnum 312 \newcount\@lastchclass
313 \newcount\@chnum

```

```

\arraycolsep
\tabcolsep 314 \newdimen\arraycolsep
\arrayrulewidth 315 \newdimen\tabcolsep
\doublerulesep 316 \newdimen\arrayrulewidth
317 \newdimen\doublerulesep

\arraystretch
318 \def\arraystretch{1} % Default value.

\@arstrutbox
\@arstrut 319 \newbox\@arstrutbox
320 \def\@arstrut{%
321 \relax\ifmmode\copy\@arstrutbox\else\unhcopy\@arstrutbox\fi}

\@arrayrule
322 \def\@arrayrule{\@addtopreamble{\hskip -.5\arrayrulewidth
323 \vrule \@width \arrayrulewidth\hskip -.5\arrayrulewidth}}

\@testpatch
324 \def\@testpatch#1{\@chclass \ifnum \@lastchclass=\tw@ 4 \else
325 \ifnum \@lastchclass=3 5 \else
326 \z@ \if #1c\@chnum \z@ \else
327 \if #1l\@chnum \@ne \else
328 \if #1r\@chnum \tw@ \else
329 \chclass \if #1\@ne \else
330 \if #1@ \tw@ \else
331 \if #1p3 \else \z@ \@preamerr 0\fi
332 \fi \fi \fi \fi \fi \fi
333 \fi}

\hline
334 \def\hline{%
335 \noalign{\ifnum0='}\fi\hrule \@height \arrayrulewidth \futurelet
336 \reserved@a\@xhline}

\@xhline
337 \def\@xhline{\ifx\reserved@a\hline
338 \vskip\doublerulesep
Measure from the middle of the rules.
339 \vskip-\arrayrulewidth
340 \fi
341 \ifnum0='{ \fi}}

\vline
342 \def\vline{\vrule \@width \arrayrulewidth}

\cline The old LATEX 2.09 implementation of \cline used up quite a lot of memory and
\@cline two precious count registers. This new (1995/09/14) implementation does not use
any count registers. It is coded in a way that depends heavily on the definition of
\multispan so that command has been moved here from the file ltplain.dtx.
These counters are no longer declared.

\newcount\@cla
\newcount\@clb

```

```
343 \def\cline#1{\@cline#1\@nil}
```

```
344 \def\@cline#1-#2\@nil{%
345   \omit
```

Use the counter from \multispan.

```
346   \@multicnt#1%
347   \advance\@multispan\m@ne
348   \ifnum\@multicnt=\@ne\@firstofone{&\omit}\fi
349   \@multicnt#2%
350   \advance\@multicnt-#1%
351   \advance\@multispan\@ne
```

The original had \unskip at this point, but how could a skip get here ???

```
352   \leaders\hrule\@height\arrayrulewidth\hfill
353   \cr
```

This is back spacing is fairly horrible, but it is what happened in the old version. . . An alternative would be to make \cline look ahead for a following \cline as does \hline. This would alter the spacing in existing documents so keep the old version in the kernel. Perhaps a package should do this differently.

```
354   \noalign{\vskip-\arrayrulewidth}}
```

**\mscount** The \mscount counter is no longer declared, saving a csname and a register. It is declared in compatibility mode.

**\multispan** Modify \multispan slightly from its plain T<sub>E</sub>X definition to allow more efficient code sharing with \multicolumn. Also share a count register with \multiput.

```
\@multispan
\sp@n
355 \def\multispan{\omit\@multispan}
356 \def\@multispan#1{%
357   \@multicnt#1\relax
358   \loop\ifnum\@multicnt>\@ne \sp@n\repeat}
359 \def\sp@n{\span\omit\advance\@multicnt\m@ne}
```

**\@startpbox** Helper macros for ‘p’ columns.

**\@endpbox** \@startpbox{<width>} text \egroup is essentially \parbox{<width>}{<text>} \@endpbox is essentially \unskip \strut \par \egroup\hfil (Changed 14 Jan 89) (changed again 1994/05/13)

```
360 \def\@startpbox#1{\vtop\bgroup \setlength\hsize{#1}\@arrayparboxrestore}
361 \def\@endpbox{\@finalstrut\@arstrutbox\par\egroup\hfil}
```

14 Jan 89: Def of \@endpbox changed from  
\def\@endpbox{\par\vskip\dp\@arstrutbox\egroup\hfil}  
so vertical spacing works out right if the last line of a ‘p’ entry has a descender.

**\@@startpbox**

```
\@endpbox
362 \let\@@startpbox=\@startpbox
363 \let\@@endpbox=\@endpbox
```

```
364 </2kernel>
```

# File D

## ltpictur.dtx

### 58 Picture Mode

Picture mode commands. In addition to the commands available in L<sup>A</sup>T<sub>E</sub>X 2.09, This section adds the new `\qbezier` command for drawing curves.

`\qbezier` `[\N](\langle AX,AY\rangle)(\langle BX,BY\rangle)(\langle CX,CY\rangle)` plots a quadratic Bezier curve from  $(\langle AX,AY\rangle)$  to  $(\langle CX,CY\rangle)$ , with  $(\langle BX,BY\rangle)$  as the third Bezier point, using  $N + 1$  points equally spaced parametrically. If  $N = 0$  (the default value), then a sufficient number of points are used to draw a connected curve—except that at most `\qbeziermax` + 1 points are drawn. A “point” is a square of side `\@wholewidth`.

`\bezier` In addition, to be compatible with the old `bezier` package, a variant of this command, `\bezier`, is defined, in which the first argument is not optional.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

<code>\unitlength</code>	= value of dimension argument
<code>\@wholewidth</code>	= current line width
<code>\@halfwidth</code>	= half of current line width
<code>\@linefont</code>	= font for drawing lines
<code>\@circlefont</code>	= font for drawing circles

`\linethickness{DIM}` : Sets the width of horizontal and vertical lines in a picture to DIM. Does not change width of slanted lines or circles. Width of all lines reset by `\thinlines` and `\thicklines`

```

\picture(XSIZE,YSIZE)(XORG,YORG)
  BEGIN
    \@picht :=L YSIZE * \unitlength
    box \@picbox :=
      \hb@xt@ XSIZE * \unitlength
      {\hskip -XORG * \unitlength
       \lower YORG * \unitlength
       \hbox{
         \ignorespaces      %% added 13 June 89
       }
      }
  END

\endpicture ==
  BEGIN
    } \hss }
    height of \@picbox := \@picht
    depth of \@picbox := 0
    \mbox{\box\@picbox}    %% change 26 Aug 91
  END

```

```

\put(X, Y){OBJ} ==

```

```

BEGIN
  \@killglue
  \raise Y * \unitlength \hb@xt@ 0pt { \hskip X * \unitlength
                                     OBJ \hss
}
  \ignorespaces
END

\multiput(X,Y)(DELX,DELY){N}{OBJ} ==
BEGIN
  \@killglue
  \@multicnt := N
  \@xdim := X * \unitlength
  \@ydim := Y * \unitlength
  while \@multicnt > 0
    do \raise \@ydim \hb@xt@ 0pt { \hskip \@xdim
                                   OBJ \hss   }
      \@multicnt := \@multicnt - 1
      \@xdim := \@xdim + DELX * \unitlength
      \@ydim := \@ydim + DELY * \unitlength
    od
  \ignorespaces
END

```

`\shortstack[POS]{TEXT}` : Makes a `\vbox` containing TEXT stacked as a one-column array, positioned l, r or c as indicated by POS.

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

The ‘2ekernel’ code ensures that a `\usepackage{autopict}` is essentially ignored if a ‘full’ format is being used that has picture mode already in the format.

```

1 (2ekernel)\expandafter\let\csname ver@autopict.sty\endcsname\fmtversion

\@wholewidth
\@halfwidth 2 (*2ekernel)
3 \newdimen\@wholewidth
4 \newdimen\@halfwidth

\unitlength
5 \newdimen\unitlength \unitlength =1pt

\@picbox
\@picht 6 \newbox\@picbox
7 \newdimen\@picht

\picture #1 should be white space.

\pictur@ #1 should be a ( (eating any white space before the bracket),
8 \long\def\picture#1{\pictur@#1}
9 \def\pictur@(#1){%
10  \@ifnextchar({\@picture(#1)}{\@picture(#1)(0,0)}}

```



```

\@picture
11 \def\@picture(#1,#2)(#3,#4){%
12   \@picht#2\unitlength
13   \setbox\@picbox\hb@xt@#1\unitlength\bgroup
14     \hskip -#3\unitlength
15     \lower #4\unitlength\hbox\bgroup
16     \ignorespaces}

\endpicture
17 \def\endpicture{%
18   \egroup\hss\egroup
19   \ht\@picbox\@picht\dp\@picbox\z@
20   \mbox{\box\@picbox}}

In the definitions of \put and \multiput, \hskip was replaced by \kern just
in case arg #3 = "plus". (Bug detected by Don Knuth. changed 20 Jul 87).

21 \long\def\put(#1,#2)#3{%
22   \@killglue\raise#2\unitlength
23   \hb@xt@\z@{\kern#1\unitlength #3\hss}%
24   \ignorespaces}

\multiput #3 had better be a (.
25 \def\multiput(#1,#2)#3{%
26   \@xdim #1\unitlength
27   \@ydim #2\unitlength
28   \@multiput{ }

\multiput
29 \long\def\@multiput(#1,#2)#3#4{%
30   \@killglue\@multicnt #3\relax
31   \@whilenum \@multicnt >\z@\do
32     {\raise\@ydim\hb@xt@\z@{\kern\@xdim #4\hss}%
33     \advance\@multicnt\m@ne
34     \advance\@xdim#1\unitlength\advance\@ydim#2\unitlength}%
35   \ignorespaces}

\@killglue
36 \def\@killglue{\unskip\@whiledim \lastskip >\z@\do{\unskip}}

\thinlines
\thicklines
37 \DeclareRobustCommand\thinlines{\let\@linefnt\tenln \let\@circlefnt\tencirc
38   \@wholewidth\fontdimen8\tenln \@halfwidth .5\@wholewidth}
39 \DeclareRobustCommand\thicklines{\let\@linefnt\tenlnw \let\@circlefnt\tencircw
40   \@wholewidth\fontdimen8\tenlnw \@halfwidth .5\@wholewidth}

\linethickness
41 \DeclareRobustCommand\linethickness[1]
42   {\@wholewidth #1\relax \@halfwidth .5\@wholewidth}

\ishortstack
43 \def\shortstack{\@ifnextchar[\@shortstack{\@shortstack[c]}}

```

```

\@ishortstack
44 \def\@shortstack[#1]{%
45   \leavevmode
46   \vbox\bgroup
47   \baselineskip-\p@\lineskip 3\p@
48   \let\mb@l\hss\let\mb@r\hss
49   \expandafter\let\csname mb@#1\endcsname\relax
50   \let\\\@stackcr
51   \@ishortstack}

\@ishortstack
52 \def\@ishortstack#1{\ialign{\mb@l {##}\unskip\mb@r\cr #1\cr}\egroup}

\@stackcr
\@ixstackcr
53 \def\@stackcr{\@ifstar\@ixstackcr\@ixstackcr}
54 \def\@ixstackcr{\@ifnextchar[\@istackcr{\cr\ignorespaces}}

\@istackcr
55 \def\@istackcr[#1]{\cr\noalign{\vskip #1}\ignorespaces}

Historical LATEX 2.09 comments (not necessarily accurate any more):
\line(X,Y){LEN} ==
BEGIN
  \@xarg := X
  \@yarg := Y
  \@linelen := LEN * \unitlength
  if \@xarg = 0
    then \@vline
    else if \@yarg = 0
      then \@hline
      else \@sline
    if
  if
END

\@sline ==
BEGIN
  if \@xarg < 0
    then @negarg := T
      \@xarg := -\@xarg
      \@yyarg := -\@yarg
    else @negarg := F
      \@yyarg := \@yarg
  fi
  \@tempcnta := |\@yyarg|
  if \@tempcnta > 6
    then error: 'LATEX ERROR: Illegal \line or \vector argument.'
      \@tempcnta := 0
  fi

```

```

\box\@linechar := \hbox{\@linefnt \@getlinechar(\@xarg,\@yyarg)
}
  if \@yarg > 0 then \@upordown = \raise
    \@clnht := 0
  else \@upordown = \lower
    \@clnht := height of \box\@linechar
  fi
  \@clnwd := width of \box\@linechar
  if @negarg
    then \hskip - width of \box\@linechar
      \reserved@a == \hskip - 2* width of box \@linechar
    else \reserved@a == \relax
  fi
%% Put out integral number of line segments
while \@clnwd < \@linelen
  do \@upordown \@clnht \copy\@linechar
    \reserved@a
    \@clnht := \@clnht + ht of \box\@linechar
    \@clnwd := \@clnwd + width of \box\@linechar
  od

%% Put out last segment
\@clnht := \@clnht - height of \box\@linechar
\@clnwd := \@clnwd - width of \box\@linechar
\@tempdima := \@linelen - \@clnwd
\@tempdimb := \@tempdima - width of \box\@linechar
if @negarg then \hskip -\@tempdimb
  else \hskip \@tempdimb
fi
\@tempdima := 1000 * \@tempdima
\@tempcnta := \@tempdima / width of \box\@linechar
\@tempdima := (\@tempcnta * ht of \box\@linechar)/1000
\@clnht := \@clnht + \@tempdima
if \@linelen < width of box\@linechar
  then \hskip width of box\@linechar
  else \hbox{\@upordown \@clnht \copy\@linechar}
fi
END

\@hline ==
  BEGIN
    if \@xarg < 0 then \hskip -\@linelen \fi
    \vrule height \@halfwidth depth \@halfwidth width \@linelen
    if \@xarg < 0 then \hskip -\@linelen \fi
  END

\@vline == if \@yarg < 0 \@downline else \@upline fi

\@getlinechar(X,Y) ==

```

```

BEGIN
  \@tempcnta := 8*X - 9
  if Y > 0
    then \@tempcnta := \@tempcnta + Y
    else \@tempcnta := \@tempcnta - Y + 64
  fi
  \char\@tempcnta
END

\vector(X,Y){LEN} ==
BEGIN
  \@xarg := X
  \@yarg := Y
  \@linelen := LEN * \unitlength
  if \@xarg = 0
    then \@vvector
    else if \@yarg = 0
      then \@hvector
      else \@svector
    fi
  fi
END

\@hvector ==
BEGIN
  \@hline
  {\@linefnt if \@xarg < 0 then \@getlarrow(1,0)
    else \@getrarrow(1,0)
  fi}
END

\@vvector == if \@yarg < 0 \@downvector else \@upvector fi

\@svector ==
BEGIN
  \@sline
  \@tempcnta := |\@yarg|
  if \@tempcnta < 5
    then \hskip - width of \box\@linechar
      \@upordown \@clnht \hbox
        {\@linefnt
          if @negarg then \@getlarrow(\@xarg,\@yyarg)
            else \@getrarrow(\@xarg,\@yyarg)
          fi }
    else error: 'LATEX ERROR: Illegal \line or \vector argument.'
  fi
END

\@getlarrow(X,Y) ==
BEGIN

```

```

if Y = 0
  then \@tempcnta := '33
  else \@tempcnta := 16 * X - 9
    \@tempcntb := 2 * Y
    if \@tempcntb > 0
      then \@tempcnta := \@tempcnta + \@tempcntb
      else \@tempcnta := \@tempcnta - \@tempcntb + 64
    fi
  fi
\char\@tempcnta
END

```

```

\@getrarrow(X,Y) ==
BEGIN
  \@tempcntb := |Y|
  case of \@tempcntb
    0 : \@tempcnta := '55
    1 : if X < 3
      then \@tempcnta := 24*X - 6
      else if X = 3
        then \@tempcnta := 49
        else \@tempcnta := 58 fi
      fi
    2 : if X < 3
      then \@tempcnta := 24*X - 3
      else \@tempcnta := 51 % X must = 3
      fi
    3 : \@tempcnta := 16*X - 2
    4 : \@tempcnta := 16*X + 7
  endcase
  if Y < 0
    then \@tempcnta := \@tempcnta + 64
  fi
  \char\@tempcnta
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

\if@negarg

```
56 \newif\if@negarg
```

\line

```

57 \def\line(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
58  \@linelen #3\unitlength
59  \ifdim\@linelen<\z@\@badlinearg\else
60    \ifnum\@xarg =\z@ \@vline
61    \else \ifnum\@yarg =\z@ \@hline \else \@sline\fi
62    \fi
63  \fi}

```

\@sline

```

64 \def\@sline{%
65   \ifnum\@xarg<\z@ \@negargtrue \@xarg -\@xarg \@yyarg -\@yarg
66   \else \@negargfalse \@yyarg \@yarg \fi
67   \ifnum \@yyarg >\z@ \@tempcnta\@yyarg \else \@tempcnta -\@yyarg \fi
68   \ifnum\@tempcnta>6 \@badlinearg\@tempcnta\z@ \fi
69   \ifnum\@xarg>6 \@badlinearg\@xarg \@ne \fi
70   \setbox\@linechar\hbox{\@linefnt\@getlinechar(\@xarg,\@yyarg)}%

```

If we have something like `\line(5,5){30}` the `\@linechar` will not contain a char and later on we will end in an infinite loop. So we check the width of the box and put in something as an emergency fix if necessary.

```

71 \ifdim\wd\@linechar=\z@
72   \setbox\@linechar\hbox{.}%
73   \@badlinearg
74 \fi
75 \ifnum \@yarg >\z@ \let\@upordown\raise \@clnht\z@
76   \else\let\@upordown\lower \@clnht \ht\@linechar\fi
77 \@clnwd \wd\@linechar
78 \if@negarg
79   \hskip -\wd\@linechar \def\reserved@a{\hskip -2\wd\@linechar}%
80 \else
81   \let\reserved@a\relax
82 \fi
83 \@whiledim \@clnwd <\@linelen \do
84   {\@upordown\@clnht\copy\@linechar
85     \reserved@a
86     \advance\@clnht \ht\@linechar
87     \advance\@clnwd \wd\@linechar}%
88 \advance\@clnht -\ht\@linechar
89 \advance\@clnwd -\wd\@linechar
90 \@tempdima\@linelen\advance\@tempdima -\@clnwd
91 \@tempdimb\@tempdima\advance\@tempdimb -\wd\@linechar
92 \if@negarg \hskip -\@tempdimb \else \hskip \@tempdimb \fi
93 \multiply\@tempdima \@m
94 \@tempcnta \@tempdima
95 \@tempdima \wd\@linechar \divide\@tempcnta \@tempdima
96 \@tempdima \ht\@linechar \multiply\@tempdima \@tempcnta
97 \divide\@tempdima \@m
98 \advance\@clnht \@tempdima
99 \ifdim \@linelen <\wd\@linechar
100   \hskip \wd\@linechar

```

Warn if line gets so short that it can't be printed. But don't warn if it is exactly zero since that was probably deliberate (e.g., to get a vector head only).

```

101 \ifdim \@linelen = \z@
102   \else
103     \@picture@warn
104   \fi
105 \else\@upordown\@clnht\copy\@linechar\fi}

```

\@hline

```

106 \def\@hline{\ifnum \@xarg <\z@ \hskip -\@linelen \fi
107 \vrule \@height \@halfwidth \@depth \@halfwidth \@width \@linelen
108 \ifnum \@xarg <\z@ \hskip -\@linelen \fi}

```

```

\@getlinechar
109 \def\@getlinechar(#1,#2){\@tempcnta#1\relax\multiply\@tempcnta 8%
110 \advance\@tempcnta -9\ifnum #2>\z@ \advance\@tempcnta #2\relax\else
111 \advance\@tempcnta -#2\relax\advance\@tempcnta 64 \fi
112 \char\@tempcnta}

\vector
113 \def\vector(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
114 \@tempcnta \ifnum\@xarg<\z@ -\@xarg\else\@xarg\fi
115 \ifnum\@tempcnta<5\relax
116 \@linelen #3\unitlength
117 \ifdim\@linelen<\z@\@badlinearg\else
118 \ifnum\@xarg =\z@ \vvector
119 \else \ifnum\@yarg =\z@ \hvector \else \svector\fi
120 \fi
121 \fi
122 \else\@badlinearg\fi}

\hvector
123 \def\hvector{\@hline\hb@xt@\z@{\@linefnt
124 \ifnum \@xarg <\z@ \@getlarrow(1,0)\hss\else
125 \hss\@getrarrow(1,0)\fi}}

\vvector
126 \def\vvector{\ifnum \@yarg <\z@ \downvector \else \upvector \fi}

\svector
127 \def\svector{\@sline
128 \@tempcnta\@yarg \ifnum\@tempcnta <\z@ \@tempcnta -\@tempcnta\fi
129 \ifnum\@tempcnta <5%
130 \hskip -\wd\@linechar
131 \upordown\@clnht \hbox{\@linefnt \if@negarg
132 \@getlarrow(\@xarg,\@yyarg)\else \@getrarrow(\@xarg,\@yyarg)\fi}%
133 \else\@badlinearg\fi}

\@getlarrow
134 \def\@getlarrow(#1,#2){\ifnum #2=\z@ \@tempcnta 27 % '33
135 \else
136 \@tempcnta #1\relax\multiply\@tempcnta \sixt@@n
137 \advance\@tempcnta -9 \@tempcntb #2\relax\multiply\@tempcntb \tw@
138 \ifnum \@tempcntb >\z@ \advance\@tempcnta \@tempcntb
139 \else\advance\@tempcnta -\@tempcntb\advance\@tempcnta 64
140 \fi\fi\char\@tempcnta}

\@getrarrow
141 \def\@getrarrow(#1,#2){\@tempcntb #2\relax
142 \ifnum\@tempcntb <\z@ \@tempcntb -\@tempcntb\relax\fi
143 \ifcase \@tempcntb\relax \@tempcnta 45 % '55
144 \or
145 \ifnum #1<\thr@@ \@tempcnta #1\relax\multiply\@tempcnta
146 24\advance\@tempcnta -6 \else \ifnum #1=\thr@@ \@tempcnta 49
147 \else\@tempcnta 58 \fi\fi\or

```

```

148 \ifnum #1<\thr@@ \@tempcnta=#1\relax\multiply\@tempcnta
149 24\advance\@tempcnta -\thr@@ \else \@tempcnta 51 \fi\or
150 \@tempcnta #1\relax\multiply\@tempcnta
151 \sift@@n \advance\@tempcnta -\tw@ \else
152 \@tempcnta #1\relax\multiply\@tempcnta
153 \sift@@n \advance\@tempcnta 7 \fi\ifnum #2<\z@ \advance\@tempcnta 64 \fi
154 \char\@tempcnta}

```

`\@vline`

```

155 \def\@vline{\ifnum \@yarg <\z@ \@downline \else \@upline\fi}

```

`\@upline`

```

156 \def\@upline{%
157   \hb@xt@\z@{\hskip -\@halfwidth \vrule \@width \@wholewidth
158     \@height \@linelen \@depth \z@\hss}}

```

`\@downline`

```

159 \def\@downline{%
160   \hb@xt@\z@{\hskip -\@halfwidth \vrule \@width \@wholewidth
161     \@height \z@ \@depth \@linelen \hss}}

```

`\@upvector`

```

162 \def\@upvector{\@upline\setbox\@tempboxa\hbox{\@linefnt\char 54}% '66
163   \raise \@linelen \hb@xt@\z@{\lower \ht\@tempboxa\box\@tempboxa\hss}}

```

`\@downvector`

```

164 \def\@downvector{\@downline\lower \@linelen
165   \hb@xt@\z@{\@linefnt\char 63 % '77
166   \hss}}

```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```

\dashbox{D}(X,Y) ==
  BEGIN
  leave vertical mode
  \hb@xt@ 0pt {
    \baselineskip := 0pt
    \lineskip      := 0pt
  %% HORIZONTAL DASHES
    \@dashdim := X * \unitlength
    \@dashcnt := \@dashdim + 200 % to prevent roundoff error
    \@dashdim := D * \unitlength
    \@dashcnt := \@dashcnt / \@dashdim
    if \@dashcnt is odd
    then \@dashdim := 0pt
        \@dashcnt := (\@dashcnt + 1) / 2
    else \@dashdim := \@dashdim / 2
        \@dashcnt := \@dashcnt / 2 - 1
        \box\@dashbox := \hbox{\vrule height \@halfwidth
                                depth \@halfwidth width \@dashdim}
        \put(0,0){\copy\@dashbox}
        \put(0,Y){\copy\@dashbox}
  }

```



```

        \put(X,0){\hskip -\@dashdim\copy\@dashbox}
        \put(X,Y){\hskip -\@dashdim\box\@dashbox}
        \@dashdim := 3 * \@dashdim
    fi
    \box\@dashbox := \hbox{\vrule height \@halfwidth
        depth \@halfwidth width D * \unitlength
        \hskip D * \unitlength}

    \@tempcnta := 0
    \put(0,0){\hskip \@dashdim
        while \@tempcnta < \@dashcnt
        do \copy\@dashbox
            \@tempcnta := \@tempcnta + 1
        od
    }
    \@tempcnta := 0
    \put(0,Y){\hskip \@dashdim
        while \@tempcnta < \@dashcnt
        do \copy\@dashbox
            \@tempcnta := \@tempcnta + 1
        od
    }
}

%% vertical dashes
\@dashdim := Y * \unitlength
\@dashcnt := \@dashdim + 200 % to prevent roundoff error
\@dashdim := D * \unitlength
\@dashcnt := \@dashcnt / \@dashdim
if \@dashcnt is odd
then \@dashdim := 0pt
    \@dashcnt := (\@dashcnt + 1) / 2
else \@dashdim := \@dashdim / 2
    \@dashcnt := \@dashcnt / 2 - 1
    \box\@dashbox := \hbox{\hskip -\@halfwidth
        \vrule width \@wholewidth
        height \@dashdim }

    \put(0,0){\copy\@dashbox}
    \put(X,0){\copy\@dashbox}
    \put(0,Y){\lower\@dashdim\copy\@dashbox}
    \put(X,Y){\lower\@dashdim\copy\@dashbox}
    \@dashdim := 3 * \@dashdim
fi
\box\@dashbox := \hbox{\vrule width \@wholewidth
    height D * \unitlength }

\@tempcnta := 0
\put(0,0){\hskip -\halfwidth
    \vbox{while \@tempcnta < \@dashcnt
        do \vskip D*\unitlength
            \copy\@dashbox
            \@tempcnta := \@tempcnta + 1
        od
    }
}

```

```

        \vskip \@dashdim
      } }
\@tempcnta := 0
put(X,0){\hskip -\halfwidth
  \vbox{while \@tempcnta < \@dashcnt
    do \vskip D*\unitlength
      \copy\@dashbox
      \@tempcnta := \@tempcnta + 1
    od
    \vskip \@dashdim
  }
}
} % END DASHES

\@imakepicbox(X,Y)
END
End of historical LATEX 2.09 comments.

\dashbox
167 \def\dashbox#1(#2,#3){\leavevmode\hb@xt@\z@{\baselineskip \z@skip
168 \lineskip \z@skip
169 \@dashdim #2\unitlength
170 \@dashcnt \@dashdim \advance\@dashcnt 200
171 \@dashdim #1\unitlength\divide\@dashcnt \@dashdim
172 \ifodd\@dashcnt\@dashdim \z@
173 \advance\@dashcnt \@one \divide\@dashcnt \tw@
174 \else \divide\@dashdim \tw@ \divide\@dashcnt \tw@
175 \advance\@dashcnt \m@ne
176 \setbox\@dashbox \hbox{\vrule \@height \@halfwidth \@depth \@halfwidth
177 \@width \@dashdim}\put(0,0){\copy\@dashbox}%
178 \put(0,#3){\copy\@dashbox}%
179 \put(#2,0){\hskip-\@dashdim\copy\@dashbox}%
180 \put(#2,#3){\hskip-\@dashdim\box\@dashbox}%
181 \multiply\@dashdim \thr@@
182 \fi
183 \setbox\@dashbox \hbox{\vrule \@height \@halfwidth \@depth \@halfwidth
184 \@width #1\unitlength\hskip #1\unitlength}\@tempcnta\z@
185 \put(0,0){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
186 \do{\copy\@dashbox\advance\@tempcnta \@one }}\@tempcnta\z@
187 \put(0,#3){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
188 \do{\copy\@dashbox\advance\@tempcnta \@one }}%
189 \@dashdim #3\unitlength
190 \@dashcnt \@dashdim \advance\@dashcnt 200
191 \@dashdim #1\unitlength\divide\@dashcnt \@dashdim
192 \ifodd\@dashcnt \@dashdim \z@
193 \advance\@dashcnt \@one \divide\@dashcnt \tw@
194 \else
195 \divide\@dashdim \tw@ \divide\@dashcnt \tw@
196 \advance\@dashcnt \m@ne
197 \setbox\@dashbox\hbox{\hskip -\halfwidth
198 \vrule \@width \@wholewidth
199 \@height \@dashdim}\put(0,0){\copy\@dashbox}%

```

```

200 \put(#2,0){\copy\@dashbox}%
201 \put(0,#3){\lower\@dashdim\copy\@dashbox}%
202 \put(#2,#3){\lower\@dashdim\copy\@dashbox}%
203 \multiply\@dashdim \thr@@
204 \fi
205 \setbox\@dashbox\hbox{\vrule \@width \@wholewidth
206 \@height #1\unitlength}\@tempcnta\z@
207 \put(0,0){\hskip -\@halfwidth \vbox{\@whilenum \@tempcnta <\@dashcnt
208 \do{\vskip #1\unitlength\copy\@dashbox\advance\@tempcnta \@ne }%
209 \vskip\@dashdim}}\@tempcnta\z@
210 \put(#2,0){\hskip -\@halfwidth \vbox{\@whilenum \@tempcnta <\@dashcnt
211 \do{\vskip #1\unitlength\copy\@dashbox\advance\@tempcnta \@ne }%
212 \vskip\@dashdim}}}\@makepicbox(#2,#3)}

```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

#### CIRCLES AND OVALS

##### USER COMMANDS:

`\circle{D}` : Produces the circle with the diameter as close as possible to  $D * \text{\unitlength}$ . `\put(X,Y){\circle{D}}` puts the circle with its center at (X,Y).

`\oval(X,Y)` : Makes an oval as round as possible that fits in the rectangle of width  $X * \text{\unitlength}$  and height  $Y * \text{\unitlength}$ . The reference point is the center.

`\oval(X,Y)[POS]` : Same as `\oval(X,Y)` except it draws only the half or quadrant of the oval indicated by POS. E.G., `\oval(X,Y)[t]` draws just the top half and `\oval(X,Y)[br]` draws just the bottom right quadrant. In all cases, the reference point is the same as the unqualified `\oval(X,Y)` command.

`\@ovvert {DELTA1} {DELTA2}` : Makes a vbox containing either the left side or the right side of the oval being constructed. The baseline will coincide with the outside bottom edge of the oval; the left side of the box will coincide with the left edge of the vertical rule. The width of the box will be `\@tempdima`.

DELTA1 and DELTA2 are added to the character number in

`\@tempcnta`

to get the characters for the top and bottom quarter circle pieces.

`\@ovhorz` : Makes an hbox containing the straight rule for either the top or the bottom of the oval being constructed. The baseline will coincide with bottom edge of the rule; the left side of the box will coincide with the left side of the oval. The width of the box will be `\@ovvxx`.

`\@getcirc {DIAM}` : Sets `\@tempcnta` to the character number of the top-right quarter circle with the largest

diameter less than or equal to DIAM.  
 Sets \@tempboxa to an hbox containing that character.  
 Sets \@tempdima to \wd \@tempboxa, which is the distance  
 from the circle's left outside edge to its right  
 inside edge.  
 (These characters are like those described in the  
 TeXbook, pp. 389-90.)

```
\@getcirc {DIAM} ==
  BEGIN
    \@tempcnta      := integer coercion of (DIAM + 2pt)
                                + 2pt added 1 Nov 88
    \@tempcnta      := \@tempcnta / integer coercion of 4pt
    if \@tempcnta > 10
      then \@tempcnta := 10 fi
    if \@tempcnta > 0
      then \@tempcnta := \@tempcnta-1
      else LaTeX Warning: Oval too small.
      fi
    \@tempcnta      := 4 * \@tempcnta
    \@tempboxa      := \hbox{\@circlefnt \char \@tempcnta}
    \@tempdima      := \wd \@tempboxa
  END
```

```
\@put{X}{Y}{OBJ} ==
  BEGIN
    \raise Y \hb@xt@ 0pt{\hskip X OBJ \hss}
  END
```

```
\@oval(X,Y)[POS] ==
  BEGIN
    \begingroup
    \boxmaxdepth := \maxdimen
    @ovt := @ovb := @ovl := @ovr := true
    for all E in POS
      do @ovE := false od
    \@ovxx := X * \unitlength
    \@ovyy := Y * \unitlength
    \@tempdimb := min(\@ovxx,\@ovyy)
    \@getcirc{\@tempdimb-2pt} %% "-2pt" added 7 Dec 89
    \@ovro := \ht \@tempboxa
    \@ovri := \dp \@tempboxa
    \@ovdx := \@ovxx - \@tempdima
    \@ovdx := \@ovdx/2
    \@ovdy := \@ovyy - \@tempdima
    \@ovdy := \@ovdy/2
    \@circlefnt
    \@tempboxa :=
      \hbox{
        if @ovr
```

```

        then \@ovvert{3}{2} \kern -\@tempdima
      fi
      if @ovl
        then \kern \@ovxx \@ovvert{0}{1} \kern
- \@tempdima
          \kern -\@ovxx
        fi
        if @ovt
          then \@ovhorz \kern -\@ovxx
        fi
        if @ovb
          then \raise \@ovyy \@ovhorz
        fi
      }
      \@ovdx := \@ovdx + \@ovro
      \@ovdy := \@ovdy + \@ovro
      \ht\@tempboxa := \dp\@tempboxa := 0
      \put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}
    \endgroup
  END

\@ovvert {DELTA1} {DELTA2} ==
  BEGIN
    \vbox to \@ovyy {
      if @ovb
        then \@tempcntb := \@tempcnta + DELTA1
          \kern -\@ovro
          \hbox { \char \@tempcntb }
          \nointerlineskip
        else \kern \@ovri \kern \@ovdy
      fi
      \leaders \vrule width \@wholewidth \vfil
      \nointerlineskip
      if @ovt
        then \@tempcntb := \@tempcnta + DELTA2
          \hbox { \char \@tempcntb }
        else \kern \@ovdy \kern \@ovro
      fi
    }
  END

\@ovhorz ==
  BEGIN
    \hb@xt@ \@ovxx{
      \kern \@ovro
      if @ovr
        then
        else \kern \@ovdx
      fi
      \leaders \hrule height \@wholewidth \hfil

```

```

        if @ovl
        then
        else \kern \@ovdx
        fi
        \kern \@ovri
    }
END

\circle{DIAM} ==
BEGIN
    \begingroup
    \boxmaxdepth := maxdimen
    \@tempdimb := DIAM *\unitlength
    if \@tempdimb > 15.5pt
    then \@getcirc{\@tempdimb}
        \@ovro := \ht \@tempboxa
        \@tempboxa := \hbox{
            \@circlefnt
            \@tempcnta := \@tempcnta + 2
            \char \@tempcnta
            \@tempcnta := \@tempcnta - 1
            \char \@tempcnta
            \kern -2\@tempdima
            \@tempcnta := \@tempcnta + 2
            \raise \@tempdima \hbox { \char \@tempcnta }
            \raise \@tempdima \box\@tempboxa
        }
        \ht\@tempboxa := \dp\@tempboxa := 0
        \@put{-\@ovro}{-\@ovro}{\@tempboxa}
    else
        \@circ{\@tempdimb}{96}
    fi
    \endgroup
END

\circle*{DIAM} == \@dot{DIAM} ==
\@circ{DIAM*\unitlength}{112}

\@circ{DIAM}{CHAR} ==
BEGIN
    \@tempcnta := integer coercion of (DIAM + .5pt)/1pt.
    if \@tempcnta > 15 then \@tempcnta := 15 fi
    if \@tempcnta > 1 then \@tempcnta := \@tempcnta - 1 fi
    \@tempcnta := \@tempcnta + CHAR
    \@circlefnt
    \char \@tempcnta
END
End of historical LATEX 2.09 comments.

```

```

\if@ovt If producing the Top Bottom Left or Right of an oval.
\if@ovb 213 \newif\if@ovt
\if@ovl 214 \newif\if@ovb
\if@ovr 215 \newif\if@ovl
        216 \newif\if@ovr

\@ovxx
\@ovyy 217 \newdimen\@ovxx
\@ovdx 218 \newdimen\@ovyy
\@ovdy 219 \newdimen\@ovdx
\@ovro 220 \newdimen\@ovdy
\@ovri 221 \newdimen\@ovro
        222 \newdimen\@ovri

\advance\@tempdima 2pt\relax added 1 Nov 88 to fix bug in which size of
drawn circle not monotonic function of argument of \circle, caused by different
rounding for dimensions of large and small circles.

\@getcirc
223 \def\@getcirc#1{\@tempdima #1\relax \advance\@tempdima 2\p@
224 \@tempcnta\@tempdima
225 \@tempdima 4\p@ \divide\@tempcnta\@tempdima
226 \ifnum \@tempcnta >10\relax
227 \@picture@warn
228 \@tempcnta 10\relax
229 \fi
230 \ifnum \@tempcnta >\z@ \advance\@tempcnta\m@ne
Warn if requirements for oval or circle can't be met.
231 \else \@picture@warn \fi
232 \multiply\@tempcnta 4\relax
233 \setbox \@tempboxa \hbox{\@circlefnt
234 \char \@tempcnta}\@tempdima \wd \@tempboxa}

\@picture@warn Generic warning for lines, vectors (used in \@sline) and oval or circle (used in
\@getcirc) are not available at right size.
235 \def\@picture@warn{\@latex@warning{%
236 \string\oval, \string\circle, or \string\line\space
237 size unavailable}}

\@put
238 \def\@put#1#2#3{\raise #2\hb@xt@{\z@{\hskip #1#3\hss}}

\oval
239 \def\oval(#1,#2){\@ifnextchar[{\@oval(#1,#2)}{\@oval(#1,#2) []}}

240 \if2kernel)
241 \iflatexrelease)\IncludeInRelease{2016/03/31}%
242 \iflatexrelease) {\@ovhlinetrue}%
243 \iflatexrelease) {Avoid almost zero length leaders}%
244 \if*2kernel | latexrelease)

\if@ovvline Tests whether horizontal or vertical lines are needed.
\if@ovhline 245 \newif\if@ovvline \@ovvlinetrue
246 \newif\if@ovhline \@ovhlinetrue

```

\@oval

```

247 \def\@oval(#1,#2)[#3]{\begingroup\boxmaxdepth \maxdimen
248   \@ovttrue \@ovbtrue \@ovltrue \@ovrtrue

249   \@ovvlinefalse \@ovhlinefalse

250   \@tfor\reserved@a :=#3\do{\csname @ov\reserved@a false\endcsname}%
251   \@ovxx #1\unitlength
252   \@ovyy #2\unitlength

253   \@tempdimb \ifdim \@ovyy >\@ovxx \@ovxx \@ovvlinetrue
254   \else \@ovyy \ifdim \@ovyy =\@ovxx \else \@ovhlinetrue \fi\fi

255   \advance \@tempdimb -2\p@
256   \@getcirc \@tempdimb
257   \@ovro \ht\@tempboxa \@ovri \dp\@tempboxa
258   \@ovdx\@ovxx \advance\@ovdx -\@tempdima \divide\@ovdx \tw@
259   \@ovdy\@ovyy \advance\@ovdy -\@tempdima \divide\@ovdy \tw@

260   \ifdim \@ovdx >\z@ \@ovhlinetrue \fi
261   \ifdim \@ovdy >\z@ \@ovvlinetrue \fi

262   \@circlefnt \setbox\@tempboxa
263   \hbox{\if@ovr \@ovvert32\kern -\@tempdima \fi
264   \if@ovl \kern \@ovxx \@ovvert01\kern -\@tempdima \kern -\@ovxx \fi
265   \if@ovt \@ovhorz \kern -\@ovxx \fi
266   \if@ovb \raise \@ovyy \@ovhorz \fi}\advance\@ovdx\@ovro
267   \advance\@ovdy\@ovro \ht\@tempboxa\z@ \dp\@tempboxa\z@
268   \@put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}%
269   \endgroup}

```

\@ovvert

```

270 \def\@ovvert#1#2{\vbox to\@ovyy{%
271   \if@ovb \@tempcntb \@tempcnta \advance \@tempcntb #1\relax
272   \kern -\@ovro \hbox{\char \@tempcntb}\nointerlineskip
273   \else \kern \@ovri \kern \@ovdy \fi

274   \if@ovvline \leaders\vrule \@width \@wholewidth \fi

275   \vfil \nointerlineskip
276   \if@ovt \@tempcntb \@tempcnta \advance \@tempcntb #2\relax
277   \hbox{\char \@tempcntb}%
278   \else \kern \@ovdy \kern \@ovro \fi}}

```

\@ovhorz

```

279 \def\@ovhorz{\hb@xt@\@ovxx{\kern \@ovro
280   \if@ovr \else \kern \@ovdx \fi

281   \if@ovhline \leaders \hrule \@height \@wholewidth \fi

282   \hfil
283   \if@ovl \else \kern \@ovdx \fi
284   \kern \@ovri}}

285 \if2ekernel\latexrelease\
286 \if2ekernel\EndIncludeInRelease
287 \if2ekernel\IncludeInRelease{0000/00/00}%
288 \if2ekernel\{\@ovhlinetrue}%

```



```

289 \latexrelease\{Avoid almost zero length leaders}%
290 \latexrelease\let\if@ovvline\undefined
291 \latexrelease\let\if@ovhline\undefined
292 \latexrelease\def\@oval(#1,#2)[#3]{\begingroup\boxmaxdepth \maxdimen
293 \latexrelease\@ovttrue \@ovbtrue \@ovltrue \@ovrtrue
294 \latexrelease\@tfor\reserved@a :=#3\do
295 \latexrelease\{\csname @ov\reserved@a false\endcsname}%
296 \latexrelease\@ovxx #1\unitlength
297 \latexrelease\@ovyy #2\unitlength
298 \latexrelease\@tempdimb \ifdim \@ovyy >\@ovxx \@ovxx\else \@ovyy \fi
299 \latexrelease\advance \@tempdimb -2\p@
300 \latexrelease\@getcirc \@tempdimb
301 \latexrelease\@ovro \ht\@tempboxa \@ovri \dp\@tempboxa
302 \latexrelease\@ovdx\@ovxx \advance\@ovdx -\@tempdima \divide\@ovdx \tw@
303 \latexrelease\@ovdy\@ovyy \advance\@ovdy -\@tempdima \divide\@ovdy \tw@
304 \latexrelease\@circlefnt \setbox\@tempboxa
305 \latexrelease\hbox{\if@ovr \@ovvert32\kern -\@tempdima \fi
306 \latexrelease\if@ovl
307 \latexrelease\kern \@ovxx \@ovvert01\kern -\@tempdima \kern -\@ovxx
308 \latexrelease\fi
309 \latexrelease\if@ovt \@ovhorz \kern -\@ovxx \fi
310 \latexrelease\if@ovb \raise \@ovyy \@ovhorz \fi}\advance\@ovdx\@ovro
311 \latexrelease\advance\@ovdy\@ovro \ht\@tempboxa\z@ \dp\@tempboxa\z@
312 \latexrelease\@put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}%
313 \latexrelease\endgroup}
314 \latexrelease\def\@ovvert#1#2{\vbox to\@ovyy{%
315 \latexrelease\if@ovb \@tempcntb \@tempcnta \advance \@tempcntb #1\relax
316 \latexrelease\kern -\@ovro \hbox{\char \@tempcntb}\nointerlineskip
317 \latexrelease\else \kern \@ovri \kern \@ovdy \fi
318 \latexrelease\leaders\vrule \@width \@wholewidth\vfil \nointerlineskip
319 \latexrelease\if@ovt \@tempcntb \@tempcnta \advance \@tempcntb #2\relax
320 \latexrelease\hbox{\char \@tempcntb}%
321 \latexrelease\else \kern \@ovdy \kern \@ovro \fi}}
322 \latexrelease\def\@ovhorz{\hb@xt@\@ovxx{\kern \@ovro
323 \latexrelease\if@ovr \else \kern \@ovdx \fi
324 \latexrelease\leaders \hrule \@height \@wholewidth \hfil
325 \latexrelease\if@ovl \else \kern \@ovdx \fi
326 \latexrelease\kern \@ovri}}
327 \latexrelease\EndIncludeInRelease
328 \*2kernel)

```

\circle

```

329 \def\circle{\@inmatherr\circle\@ifstar\@dot\@circle}

```

\@circle

```

330 \def\@circle#1{%
331 \begingroup \boxmaxdepth \maxdimen \@tempdimb #1\unitlength
332 \ifdim \@tempdimb >15.5\p@ \@getcirc\@tempdimb
333 \ovro\ht\@tempboxa
334 \setbox\@tempboxa\hbox{\@circlefnt
335 \advance\@tempcnta\tw@ \char \@tempcnta
336 \advance\@tempcnta@m@ne \char \@tempcnta \kern -2\@tempdima
337 \advance\@tempcnta\tw@
338 \raise \@tempdima \hbox{\char\@tempcnta}\raise \@tempdima

```

```

339      \box\@tempboxa}\ht\@tempboxa\z@ \dp\@tempboxa\z@
340      \put{-\@ovro}{-\@ovro}{\box\@tempboxa}%
341      \else \@circ\@tempdimb{96}\fi\endgroup}

\@dot Internal form of \circle*.
342 \def\@dot#1{\@tempdimb #1\unitlength \@circ\@tempdimb{112}}

\@circ
343 \def\@circ#1#2{\@tempdima #1\relax \advance\@tempdima .5\p@
344 \@tempcnta\@tempdima \@tempdima \p@
345 \divide\@tempcnta\@tempdima
346 \ifnum\@tempcnta >15\relax \@tempcnta 15\relax \fi
347 \ifnum \@tempcnta >\z@ \advance\@tempcnta\m@ne\fi
348 \advance\@tempcnta #2\relax
349 \@circlefnt \char\@tempcnta}

\@xarg Counters used for manipulating the ‘slope’ arguments.
\@yarg
350 \newcount\@xarg
\@yyarg
351 \newcount\@yarg
352 \newcount\@yyarg

\@multicnt Counter used in \multiput, and also \multicolumn.
353 \newcount\@multicnt

\@xdim Length registers.
\@ydim
354 \newdimen\@xdim
355 \newdimen\@ydim

\@linechar Box for holding a line segment character, for sloping lines.
356 \newbox\@linechar

\@linelen Length of the line currently being built.
357 \newdimen\@linelen

\@clnwd Height and width of current line segment.
\@clnht
358 \newdimen\@clnwd
359 \newdimen\@clnht

\@dashdim \dashbox internal registers.
\@dashbox
360 \newdimen\@dashdim
\@dashcnt
361 \newbox\@dashbox
362 \newcount\@dashcnt

Initialization: “\thinline”
363 \let\@linefnt\tenln
364 \let\@circlefnt\tencirc
365 \@wholewidth\fontdimen8\tenln
366 \@halfwidth .5\@wholewidth

```

## 58.1 Curves

The new `\qbezier` command, based on the old `\bezier` defined in `bezier.sty`.  
*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\qbezier[N] == \bezier{N}

\bezier{N}(AX,AY)(BX,BY)(CX,CY) ==
BEGIN
  IF N = 0
    THEN \@xdima := |BX - AX|
        \@xb := |CX - BX|
        \@xa := Max(\@xa, \@xb)
        \@ya := |BY - AY|
        \@yb := |CY - BY|
        \@ya := Max(\@ya, \@yb)
        @sc := Max(\@xa, \@ya)
        %% The coefficient .5 below is the degree of overlap of
        %% successive points, where 1 is no overlap and 0 is
        %% complete overlap. A coefficient of C multiplies
        %% the number of points plotted by 1/C.
        %%
        \@xa := .5 * \@halfwidth
        @sc := @sc / \@halfwidth
        @sc := Max(@sc, qbeziermax)
    ELSE @sc := N
  @scp := @sc+1
  \@xb := 2 * (BX - AX) * \unitlength
  \@xa := ((CX-AX)*\unitlength - \@xb)/@sc
  \@yb := 2 * (BY - AY) * \unitlength
  \@ya := ((CY-AY)*\unitlength - \@yb)/@sc
  \@pictdot := square rule of width \@wholewidth
  \count@ := 0
  WHILE \count@ < @scp
    DO \@xdim := ((\count@*\@xa + @xb) / @sc) * \count@
        \@ydim := ((\count@*\@ya + @yb) / @sc) * \count@
        plot pt with relative coords (\@xdim,\@ydim)
        \count@ := \count@+1
  OD
```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\qbeziermax` The maximum number of points to plot.  
 367 `\def\qbeziermax{500}`

In the code below, to save registers `\@a...` are not used. Instead other registers are reused.

```
\newcounter{@sc} -> \c@multicnt
\newcounter{@scp} -> \@tempcnta
\newdimen\@xa -> \@ovxx
```

```

\newdimen\@xb -> \@ovdx
\newdimen\@ya -> \@ovyy
\newdimen\@yb -> \@ovdy
\newsavebox{\@pictdot} -> \@tempboxa

\qbezier Main user-level command to plot quadratic bezier curves. #2 should be (.
368 \newcommand\qbezier[2][0]{\bezier{#1}#2}

\bezier Form of \bezier compatible with 2.09 bezier.sty, but modified to ignore spaces
between its arguments. #2 should be white space, and #4 should be (.
369 \def\bezier#1)#2(#3)#4({\@bezier#1)(#3){}

\@bezier
370 \def\@bezier#1(#2,#3)(#4,#5)(#6,#7){%
371   \ifnum #1=\z@
372     \@ovxx #4\unitlength
373     \advance\@ovxx -#2\unitlength
374     \ifdim \@ovxx<\z@ \@ovxx -\@ovxx \fi
375     \@ovdx #6\unitlength
376     \advance\@ovdx -#4\unitlength
377     \ifdim \@ovdx<\z@ \@ovdx -\@ovdx \fi
378     \ifdim \@ovxx<\@ovdx \@ovxx \@ovdx \fi
379     \@ovyy #5\unitlength
380     \advance\@ovyy -#3\unitlength
381     \ifdim \@ovyy<\z@ \@ovyy -\@ovyy \fi
382     \@ovdy #7\unitlength
383     \advance\@ovdy -#5\unitlength
384     \ifdim \@ovdy<\z@ \@ovdy -\@ovdy \fi
385     \ifdim \@ovyy<\@ovdy \@ovyy \@ovdy \fi
386     \@multicnt
387     \ifdim \@ovxx>\@ovyy \@ovxx \else \@ovyy \fi
388     \@ovxx .5\@halfwidth \divide\@multicnt\@ovxx
389     \ifnum \qbeziermax<\@multicnt \@multicnt\qbeziermax\relax \fi
390   \else \@multicnt#1\relax \fi
391   \@tempcnta\@multicnt \advance\@tempcnta\@ne
392   \@ovdx #4\unitlength \advance\@ovdx -#2\unitlength
393   \multiply\@ovdx \tw@
394   \@ovxx #6\unitlength \advance\@ovxx -#2\unitlength
395   \advance\@ovxx -\@ovdx \divide\@ovxx\@multicnt
396   \@ovdy #5\unitlength \advance\@ovdy -#3\unitlength
397   \multiply\@ovdy \tw@
398   \@ovyy #7\unitlength \advance\@ovyy -#3\unitlength
399   \advance\@ovyy -\@ovdy \divide\@ovyy\@multicnt

400   \setbox\@tempboxa\hbox{%
401     \hspace -\@halfwidth
402     \vrule \@height\@halfwidth
403     \@depth \@halfwidth
404     \@width \@wholewidth}%
405   \put(#2,#3){%
406     \count@\z@
407     \@whilenum{\count@<\@tempcnta}\do
408       {\@xdim\count@\@ovxx
409        \advance\@xdim\@ovdx

```

```

410          \divide\@xdim\@multicnt
411          \multiply\@xdim\count@
412          \@ydim\count@\@ovvy
413          \advance\@ydim\@ovdy
414          \divide\@ydim\@multicnt
415          \multiply\@ydim\count@
416          \raise \@ydim
417          \hb@xt@\z@{\kern\@xdim
418                  \unhcopy\@tempboxa\hss}%
419          \advance\count@\@ne}}

```

As the commands above all use “picture” interface we couldn’t define them with `\DeclareRobustCommand` so we do that now.

```

420 \</2ekernel>
421 \<*2ekernel | latexrelease>
422 \<latexrelease>\IncludeInRelease{2019/10/01}%
423 \<latexrelease>          {\bezier}{Make commands robust}%
424 \MakeRobust\bezier
425 \MakeRobust\circle
426 \MakeRobust\dashbox
427 \MakeRobust\line
428 \MakeRobust\linethickness
429 \MakeRobust\multiput
430 \MakeRobust\oval
431 \MakeRobust\put
432 \MakeRobust\qbezier
433 \MakeRobust\shortstack
434 \MakeRobust\thinline
435 \MakeRobust\vector
436 \</2ekernel | latexrelease>
437 \<latexrelease>\EndIncludeInRelease
438 \<latexrelease>\IncludeInRelease{0000/00/00}%
439 \<latexrelease>          {\bezier}{Make commands robust}%
440 \<latexrelease>
441 \<latexrelease>\kernel@make@fragile\bezier
442 \<latexrelease>\kernel@make@fragile\circle
443 \<latexrelease>\kernel@make@fragile\dashbox
444 \<latexrelease>\kernel@make@fragile\line
445 \<latexrelease>\kernel@make@fragile\linethickness
446 \<latexrelease>\kernel@make@fragile\multiput
447 \<latexrelease>\kernel@make@fragile\oval
448 \<latexrelease>\kernel@make@fragile\put
449 \<latexrelease>\kernel@make@fragile\qbezier
450 \<latexrelease>\kernel@make@fragile\shortstack
451 \<latexrelease>\kernel@make@fragile\thinline
452 \<latexrelease>\kernel@make@fragile\vector
453 \<latexrelease>
454 \<latexrelease>\EndIncludeInRelease
455 \<*2ekernel>
456 \</2ekernel>

```

## File E

# ltthm.dtx

## 59 Theorem Environments

The user creates his own theorem-like environments with the command

`\newtheorem{<name>}{<text>}[<counter>]` or

`\newtheorem{<name>}[<oldname>]{<text>}`

This defines the environment `<name>` to be just as one would expect a theorem environment to be, except that it prints `<text>` instead of “Theorem”.

If `<oldname>` is given, then environments `<name>` and `<oldname>` use the same counter, so using a `<name>` environment advances the number of the next `<name>` environment, and vice-versa.

If `<counter>` is given, then environment `<name>` is numbered within `<counter>`.

E.g., if `<counter> = subsection`, then the first `<name>` in subsection 7.2 is numbered `<text> 7.2.1`.

The way `<name>` environments are numbered can be changed by redefining `\the<name>`.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

### DOCUMENT STYLE PARAMETERS

`\@thmcounter{COUNTER}` : A command such that

`\edef\theCOUNTER{\@thmcounter{COUNTER}}`

defines `\theCOUNTER` to produce a number for a theorem environment.

The default is:

`BEGIN \noexpand\arabic{COUNTER} END`

`\@thmcountersep` : A separator placed between a theorem number and the number of the counter within which it is numbered.

E.g., to make the third theorem of section 7.2 be numbered 7.2-3, `\@thmcountersep` should be `\def`'ed to `'-'`. Its default is `'.'`.

`\@begintheorem{NAME}{NUMBER}` : A command that begins a theorem

environment for a 'theorem' named 'NAME NUMBER' – e.g., `\@begintheorem{Lemma}{3.7}` starts Lemma 3.7.

`\@opargbegintheorem{NAME}{NUMBER}{OPARG}` :

A command that begins a theorem

environment for a 'theorem' named 'NAME NUMBER' with optional

argument OPARG – e.g., `\@begintheorem{Lemma}{3.7}{Jones}` starts 'Lemma 3.7 (Jones)'.  
starts 'Lemma 3.7 (Jones)'.

`\@endtheorem` : A command that ends a theorem environment.

```

\newtheorem{NAME}{TEXT}[COUNTER] ==
  BEGIN
    if \NAME is definable
      then \@definecounter{NAME}
        if COUNTER present
          then \@newctr{NAME}[COUNTER] fi
          \theNAME == BEGIN \theCOUNTER \@thmcountersep
                        eval\@thmcounter{NAME}
        END
      else \theNAME == BEGIN eval\@thmcounter{NAME} END
      \NAME == \@thm{NAME}{TEXT}
      \endNAME == \@endtheorem
    else error
  fi
END

\newtheorem{NAME}[OLDNAME]{TEXT}==
  BEGIN
    if counter OLDNAME nonexistent
      then ERROR
    else
      if \NAME is definable
        then BEGIN
          \theNAME == \theOLDNAME
          \NAME == \@thm{OLDNAME}{TEXT}
          \endNAME == \@endtheorem
          END
        else error
      fi
    fi
  END

\@thm{NAME}{TEXT} ==
  BEGIN
    \refstepcounter{NAME}
    if next char = [
      then \@ythm{NAME}{TEXT}
      else \@xthm{NAME}{TEXT}
    fi
  END

\@xthm{NAME}{TEXT} ==
  BEGIN
    \@begintheorem{TEXT}{\theNAME}
    \ignorespaces
  END

\@ythm{NAME}{TEXT}[OPARG] ==
  BEGIN
    \@opargbegintheorem{TEXT}{\theNAME}{OPARG}

```

```

\ignorespaces
END
End of historical LATEX 2.09 comments.

\newtheorem \newtheorem ought really be allowed only in the preamble Which would be good
document style, and allow some main memory to be saved by declaring these
commands to be \@onlypreamble. Unfortunately the LATEX book indicates that
\newtheorem may be used anywhere in the document...
1 \(*2ekernel)
2 \def\newtheorem#1{%
3   \@ifnextchar[{\@othm{#1}}{\@nthm{#1}}}%

\@nthm
4 \def\@nthm#1#2{%
5   \@ifnextchar[{\@xnthm{#1}{#2}}{\@ynthm{#1}{#2}}}%

\@xnthm 92/09/18 RmS: Changed \@addtoreset to \@newctr to produce error message if
counter #3 does not exist (to be consistent with behaviour of \newcounter)
6 \def\@xnthm#1#2[#3]{%
7   \expandafter\@ifdefinable\csname #1\endcsname
8     {\@definecounter{#1}\@newctr{#1}[#3]}%
9     \expandafter\xdef\csname the#1\endcsname{%
10      \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
11      \@thmcounter{#1}}}%
12   \global\@namedef{#1}{\@thm{#1}{#2}}}%
13   \global\@namedef{end#1}{\@endtheorem}}}%

\@ynthm
14 \def\@ynthm#1#2{%
15   \expandafter\@ifdefinable\csname #1\endcsname
16     {\@definecounter{#1}%
17      \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}}%
18     \global\@namedef{#1}{\@thm{#1}{#2}}}%
19     \global\@namedef{end#1}{\@endtheorem}}}%

\@othm
20 \def\@othm#1[#2]#3{%
21   \@ifundefined{c#2}{\@nocounterr{#2}}}%
22   {\expandafter\@ifdefinable\csname #1\endcsname
23     {\global\@namedef{the#1}{\@nameuse{the#2}}}%
24     \global\@namedef{#1}{\@thm{#2}{#3}}}%
25     \global\@namedef{end#1}{\@endtheorem}}}%

\@thm
26 \def\@thm#1#2{%
27   \refstepcounter{#1}%
28   \@ifnextchar[{\@ythm{#1}{#2}}{\@xthm{#1}{#2}}}%

\@xthm
\@ythm 29 \def\@xthm#1#2{%
30   \@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}
31 \def\@ythm#1#2[#3]{%
32   \@opargbegintheorem{#2}{\csname the#1\endcsname}{#3}\ignorespaces}

```



## Default values

```

\@thmcounter
\@thmcountersep 33 \def\@thmcounter#1{\noexpand\arabic{#1}}
                 34 \def\@thmcountersep{.}

\@begintheorem Providing theorem defaults.
\@opargbegintheorem 35 \def\@begintheorem#1#2{\trivlist
\@endtheorem        36   \item[\hskip \labelsep{\bfseries #1\ #2}]\itshape}
                    37 \def\@opargbegintheorem#1#2#3{\trivlist
                    38   \item[\hskip \labelsep{\bfseries #1\ #2\ (#3)}]\itshape}
                    39 \def\@endtheorem{\endtrivlist}
                    40 \endkernel

```

# File F

## ltsect.dtx

### 60 Sectioning Commands

This file defines the declarations such as `\author` which are used by `\maketitle`. `\maketitle` itself is defined by each class, not in the L<sup>A</sup>T<sub>E</sub>X kernel.

The second part of the file defines the generic commands used for defining sectioning commands such as `\chapter`. Again the actual document level commands are defined in the class files, in terms of these commands.

```
1 <*2ekernel>
2 \message{title,}
```

#### 60.1 The Title

```
\title The user defines the title and author by the declarations \title{<name>},
\author \author{<name>}
\date Similarly the date is declared with \date{<date>}.
\thanks Inside these, the \thanks{<footnote text>} command may be used to make
\and acknowledgements, notice of address, etc. in a footnote. If there are multiple
\maketitle authors, they have to be separated with the \and command.
And finally, the \maketitle command produces the actual title, using the
information previously saved with the other commands.

3 </2ekernel>
4 <*2ekernel | latexrelease>
5 <latexrelease>\IncludeInRelease{2019/10/01}%
6 <latexrelease> {\title}{Make commands robust}%

\title \title for use in \maketitle. If not given \maketitle will produce an error
message.
7 \DeclareRobustCommand\title[1]{\gdef\@title{#1}}

\author \author for use in \maketitle. If not given \maketitle will produce a warning
message.
8 \DeclareRobustCommand\author[1]{\gdef\@author{#1}}

\date \date for use in \maketitle. If not given \maketitle will produce \today as the
default.
9 \DeclareRobustCommand\date[1]{\gdef\@date{#1}}

\thanks
10 \DeclareRobustCommand\thanks[1]{\footnotemark
11 \protected@xdef\@thanks{\@thanks
12 \protect\footnotetext[\the\c@footnote]{#1}}%
13 }
```

```

\and
14 \DeclareRobustCommand\and{%    % \begin{tabular}
15   \end{tabular}}%
16   \hskip 1em \@plus.17fil%
17   \begin{tabular}[t]{c}}%      % \end{tabular}

18 \</2ekernel | latexrelease>
19 \<latexrelease>\EndIncludeInRelease
20 \<latexrelease>\IncludeInRelease{0000/00/00}%
21 \<latexrelease>                {\title}{Make commands robust}%
22 \<latexrelease>
23 \<latexrelease>\kernel@make@fragile\title
24 \<latexrelease>\kernel@make@fragile\author
25 \<latexrelease>\kernel@make@fragile\date
26 \<latexrelease>\kernel@make@fragile\thanks
27 \<latexrelease>\kernel@make@fragile\and
28 \<latexrelease>
29 \<latexrelease>\EndIncludeInRelease
30 \<*2ekernel>

\@title
31 \def\@title{\@latex@error{No \noexpand\title given}\@ehc}

\@author
32 \def\@author{\@latex@warning@no@line{No \noexpand\author given}}

\@date
33 \gdef\@date{\today}

\@thanks
34 \let\@thanks\@empty
35 \message{sectioning,}

```

## 60.2 Sectioning

```

\@secpenalty
36 \newcount\@secpenalty
37 \@secpenalty = -300

\if@noskipsec \@noskipsectrue
Way back in 1991 (08/26) FMi & RmS set the \@noskipsec switch to true for the
preamble and to false in \document. This was done to trap lists and related text
in the preamble but it does not catch everything.
38 \newif\if@noskipsec \@noskipsectrue

\@startsection
The \@startsection{\<name>}{\<level>}{\<indent>}{\<before skip>}
{\<after skip>}{\<style>}*[\<altheading> ]{\<heading>} command is the mother of all
the user level sectioning commands. The part after the *, including the * is
optional.

```

**name:** e.g., 'subsection'

**level:** a number, denoting depth of section – e.g., chapter = 0, section = 1, etc.

**indent:** Indentation of heading from left margin

**beforeskip:** Absolute value = skip to leave above the heading. If negative, then paragraph indent of text following heading is suppressed.

**afterskip:** if positive, then skip to leave below heading, else negative of skip to leave to right of run-in heading.

**style:** Commands to set style. Since June 1996 release the *last* command in this argument may be a command such as `\MakeUppercase` or `\fbox` that takes an argument. The section heading will be supplied as the argument to this command. So setting `#6` to, say, `\bfseries\MakeUppercase` would produce bold, uppercase headings.

If ‘\*’ is missing, then increment the counter. If it is present, then there should be no [*altheading*] argument. The command uses the counter ‘secnumdepth’. It contains a pointer to the highest section level that is to be numbered.

**Warning:** The `\@startsection` command should be at the same or higher grouping level as the text that follows it. For example, you should *not* do something like

```
\def\foo{ \begingroup ...
           \paragraph{...}
           \endgroup}
```

Pseudocode for the `\@startsection` command *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\@startsection
{NAME}{LEVEL}{INDENT}{BEFORESKIP}{AFTERSKIP}{STYLE} ==
BEGIN
  IF @noskipsec = T THEN \leavevmode FI
                                % true if previous section had no body.

  \par
  \@tempskipa := BEFORESKIP
  @afterindent := T
  IF \@tempskipa < 0 THEN \@tempskipa := -\@tempskipa
                        @afterindent := F
  FI
  IF @nobreak = true
    THEN \everypar == null
    ELSE \addpenalty{\@secpenalty}
         \addvspace{\@tempskipa}
  FI
  IF * next
    THEN \ssect{INDENT}{BEFORESKIP}{AFTERSKIP}{STYLE}
    ELSE \dblarg{\@sect
                {NAME}{LEVEL}{INDENT}
                {BEFORESKIP}{AFTERSKIP}{STYLE}}
  FI
END
```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

39 \def\@startsection#1#2#3#4#5#6{%
40   \if@noskipsec \leavevmode \fi
41   \par
42   \@tempskipa #4\relax
43   \@afterindenttrue
44   \ifdim \@tempskipa <\z@
45     \@tempskipa -\@tempskipa \@afterindentfalse
46   \fi
47   \if@nobreak
48     \everypar{}%
49   \else
50     \addpenalty\@secpenalty\addvspace\@tempskipa
51   \fi
52   \ifstar
53     {\@ssect{#3}{#4}{#5}{#6}}%
54     {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}
```

`\@sect` Pseudocode for the `\@sect` command *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```

\@sect{NAME}{LEVEL}
  {INDENT}{BEFORESKIP}{AFTERSKIP}
  {STYLE}[ARG1]{ARG2}
  ==
BEGIN
  IF LEVEL > \c@secnumdepth
    THEN \@svsec :=L null
    ELSE \refstepcounter{NAME}
         \@svsec :=L BEGIN \@secntformat{#1}\relax END
  FI
  IF AFTERSKIP > 0
    THEN \begingroup
         STYLE
         \@hangfrom{\hskip INDENT\@svsec}
         {\interlinepenalty 10000 ARG2\par}
       \endgroup
       \NAMEmark{ARG1}
       \addcontentsline{toc}{NAME}
       { IF LEVEL > \c@secnumdepth
         ELSE \protect\numberline{\theNAME} FI
         ARG1 }
    ELSE \@svsechd == BEGIN STYLE
         \hskip INDENT\@svsec
         ARG2
         \NAMEmark{ARG1}
         \addcontentsline{toc}{NAME}
         { IF LEVEL > \c@secnumdepth
           ELSE

\protect\numberline{\theNAME}

FI
```

ARG1 }

END

FI

\@xsect{AFTERSKIP}

END

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```
55 \def\@sect#1#2#3#4#5#6[#7]#8{%
56   \ifnum #2>\c@secnumdepth
57     \let\@svsec\@empty
58   \else
59     \refstepcounter{#1}%
```

Since \@secntformat might end with an improper \hskip which is scanning forward for plus or minus we end the definition of \@svsec with \relax as a precaution.

```
60   \protected@edef\@svsec{\@secntformat{#1}\relax}%
61   \fi
62   \@tempskipa #5\relax
63   \ifdim \@tempskipa>\z@
64     \begingroup
```

This { used to be after the argument to \@hangfrom but was moved here to allow commands such as \MakeUppercase to be used at the end of #6.

```
65     #6{%
66       \@hangfrom{\hskip #3\relax\@svsec}%
67       \interlinepenalty \@M #8\@par}%
68   \endgroup
69   \csname #1mark\endcsname{#7}%
70   \addcontentsline{toc}{#1}{%
71     \ifnum #2>\c@secnumdepth \else
72       \protect\numberline{\csname the#1\endcsname}%
73     \fi
74     #7}%
75   \else
```

\relax added 2 May 90

```
76   \def\@svsechd{%
77     #6{\hskip #3\relax
78     \@svsec #8}%
79     \csname #1mark\endcsname{#7}%
80     \addcontentsline{toc}{#1}{%
81       \ifnum #2>\c@secnumdepth \else
82         \protect\numberline{\csname the#1\endcsname}%
83       \fi
84       #7}}%
85   \fi
86   \@xsect{#5}}
```

\@xsect Pseudocode for the \@xsect command *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\@xsect{AFTERSKIP} ==
BEGIN
  IF AFTERSKIP > 0
  THEN \par \nobreak
```

```

        \vskip AFTERSKIP
        \@afterheading
ELSE @nobreak :=G F
    @noskipsec :=G T
    \everypar{ IF @noskipsec = T
        THEN @noskipsec :=G F
            \clubpenalty := 10000 % local
            \hskip -\parindent
            \begingroup
            \@svsechd
            \endgroup
            \unskip
            \hskip -AFTERSKIP \relax
            %% relax added 14 Jan 91
        ELSE \clubpenalty := \@clubpenalty % local
            \everypar := NULL
        FI
    }
FI

END
End of historical LATEX 2.09 comments.

87 \def\xsect#1{%
88   \@tempkipa #1\relax
89   \ifdim \@tempkipa>\z@

Why not combine \@sect and \xsect and save doing the same test twice? It is
not possible to change this now as these have become hooks!
This \par seems unnecessary.

90   \par \nobreak
91   \vskip \@tempkipa
92   \@afterheading
93   \else

94   \@nobreakfalse
95   \global\noskipsecttrue
96   \everypar{%
97     \ifnoskipsec
98       \global\noskipsecfalse
99       {\setbox\z@\lastbox}%
100      \clubpenalty\@M
101      \begingroup \@svsechd \endgroup
102      \unskip
103      \@tempkipa #1\relax
104      \hskip -\@tempkipa
105    \else
106      \clubpenalty \@clubpenalty
107      \everypar{}%
108    \fi}%
109 \fi
110 \ignorespaces}

```

```

\@secntformat This command formats the section number including the space following it.
111 \def\@secntformat#1{\csname the#1\endcsname\quad}

Pseudocode for the \@ssect command Historical LATEX 2.09 comments (not necessarily accurate any more):
\@ssect{INDENT}{BEFORESKIP}{AFTERSKIP}{STYLE}{ARG} ==
BEGIN
  IF AFTERSKIP > 0
    THEN \begingroup
          STYLE
          \@hangfrom{\hskip INDENT}
                {\interlinepenalty 10000 ARG\par}
        \endgroup
    ELSE \@svsechd == BEGIN STYLE
                          \hskip INDENT
                          ARG
                        END
  FI
  \@xsect{AFTERSKIP}
END
End of historical LATEX 2.09 comments.

Pseudocode for the \@afterheading command Historical LATEX 2.09 comments (not necessarily accurate any more):
\@afterheading ==
BEGIN
  @nobreak :=G true
  \everypar := BEGIN IF @nobreak = T
                    THEN @nobreak :=G false
                      \clubpenalty := 10000 % local
                      IF @afterindent = F
                        THEN remove \lastbox
                      FI
                    ELSE \clubpenalty := \@clubpenalty % local
                      \everypar := NULL
                    FI
  END
END
End of historical LATEX 2.09 comments.

\@ssect
112 \def\@ssect#1#2#3#4#5{%
113   \@tempskipa #3\relax
114   \ifdim \@tempskipa>\z@
115     \begingroup
This { used to be after the argument to \@hangfrom but was moved here to allow
commands such as \MakeUppercase to be used at the end of #4.
116     #4{%
117       \@hangfrom{\hskip #1}%
118       \interlinepenalty \@M #5\@@par}%
119     \endgroup
120   \else

```



```

121     \def\@svsechd{#4{\hskip #1\relax #5}}%
122     \fi
123     \@xsect{#3}}

\if@afterindent
\@afterindenttrue 124 \newif\if@afterindent \@afterindenttrue

\@afterheading This hook is used in setting up custom-built headings in classes.dtx.
125 \def\@afterheading{%
126     \@nobreaktrue
127     \everypar{%
128         \if@nobreak
129             \@nobreakfalse
130             \clubpenalty \@M
131             \if@afterindent \else
132                 {\setbox\z@\lastbox}%
133             \fi
134         \else
135             \clubpenalty \@clubpenalty
136             \everypar{}%
137         \fi}}

\@hangfrom \def\@hangfrom{<text>} : Puts <text> in a box, and makes a hanging indentation of
the following material up to the first \par. Should be used in vertical mode.
138 \def\@hangfrom#1{\setbox\@tempboxa\hbox{#1}}%
139     \hangindent \wd\@tempboxa\noindent\box\@tempboxa}

\c@secnumdepth
\c@tocdepth 140 \newcount\c@secnumdepth
141 \newcount\c@tocdepth

\secdef \secdef{\unstarcmds}{\unstarcmds}{\starcmds}
When defining a \chapter or \section command without using \@startsection,
you can use \secdef as follows:
1. \def\chapter{ ... \secdef \<starcmd> \<unstarcmd> }
2. \def\<starcmd>[#1]#2{ ... } % Command to define \chapter[...]{...}
3. \def\<unstarcmd>#1{ ... } % Command to define \chapter*{...}
142 \def\secdef#1#2{\@ifstar{#2}{\@dblarg{#1}}}
```

### 60.2.1 Initializations

```

\sectionmark
\subsectionmark 143 \let\sectionmark\@gobble
\subsubsectionmark 144 \let\subsectionmark\@gobble
\paragraphmark 145 \let\subsubsectionmark\@gobble
\subparagraphmark 146 \let\paragraphmark\@gobble
147 \let\subparagraphmark\@gobble

148 \message{contents,}
```

## 60.3 Table of Contents etc.

### 60.3.1 Convention

`\tf@{foo}` = file number for output for table foo. The file is opened only if `@filesw = true`.

### 60.3.2 Commands

A `\l@{type}{<entry>}{<page>}` Macro needs to be defined by document style for making an entry of type `<type>` in a table of contents, etc. E.g., the document style should define `\l@chapter`, `\l@section`, etc.

**Note:** When the `\protect` command is used in the `<entry>` or `<text>` of one of the commands below, it causes the following control sequence to be written on the file without being expanded. The sequence will be expanded when the table of contents entry is processed.

**Surprise:** Inside an `\addcontentsline` or `\addtocontents` command argument, the commands: `\index`, `\glossary`, and `\label` are no-ops. This could cause a problem if the user puts an `\index` or `\label` into one of the commands he writes, or into the optional ‘short version’ argument of a `\section` or `\caption` command.

`\@starttoc` The `\@starttoc{<ext>}` command is used to define the commands: `\tableofcontents`, `\listoffigures`, etc.

For example: `\@starttoc{lof}` is used in `\listoffigures`. This command reads the `.<ext>` file and sets up to write the new `.<ext>` file.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\@starttoc{EXT} ==
BEGIN
  \begingroup
    \makeatletter
    read file \jobname.EXT
    IF @filesw = true
      THEN open \jobname.EXT as file \tf@EXT
    FI
    @nobreak :=G FALSE %% added 24 May 89
  \endgroup
END
```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```
149 \def\@starttoc#1{%
150   \begingroup
151     \makeatletter
152     \@input{\jobname.#1}%
153     \if@filesw
154       \expandafter\newwrite\csname tf@#1\endcsname
155       \immediate\openout \csname tf@#1\endcsname \jobname.#1\relax
156     \fi
157     \@nobreakfalse
158   \endgroup}
```

`\addcontentsline` The `\addcontentsline{<table>}{<type>}{<entry>}` command allows the user to add his/her own entry to a table of contents, etc. The command adds the entry `\contentsline{<type>}{<entry>}{<page>}` to the `.<table>` file.

This macro is implemented as an application of `\addtocontents`. Note that `\thepage` is not expandable during `\protected@write` therefore one gets the page number at the time of the `\shipout`.

```
159 </2ekernel>
160 <*2ekernel | latexrelease>
161 <latexrelease>\IncludeInRelease{2018/12/01}%
162 <latexrelease>          {\addcontentsline}{Mask line endings}%
163 \def\addcontentsline#1#2#3{%
164   \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}%
```

We add `\protected@file@percent` at the end which is turned inside `\writefile` into a percent character to mask the newline after the closing argument brace.

```
165           \protected@file@percent}}
166 </2ekernel | latexrelease>
167 <latexrelease>\EndIncludeInRelease
168 <latexrelease>\IncludeInRelease{0000/00/00}%
169 <latexrelease>          {\addcontentsline}{Mask line endings}%
170 <latexrelease>\def\addcontentsline#1#2#3{%
171 <latexrelease>   \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}}}
172 <latexrelease>\EndIncludeInRelease
173 <*2ekernel>
```

`\addtocontents` The `\addtocontents{<table>}{<text>}` command adds `<text>` to the `.<table>` file, with no page number.

```
174 \long\def\addtocontents#1#2{%
175   \protected@write\@auxout
176     {\let\label\@gobble \let\index\@gobble \let\glossary\@gobble}%
177     {\string\@writefile{#1}{#2}}}
```

`\contentsline` The `\contentsline{<type>}{<entry>}{<page>}` macro produces a `<type>` entry in a table of contents, etc. It will appear in the `.toc` or other file. For example, The entry for subsection 1.4.3 in the table of contents for example, might be produced by:

```
\contentsline{subsection}
{\makebox{30pt}[r]{1.4.3} Gnats and Gnus}{22}
```

The `\protect` command causes command sequences to be written without expanding them.

```
178 \def\contentsline#1{\csname l@#1\endcsname}
```

`\@dottedtocline{<level>}{<indent>}{<numwidth> }{<title>}{<page>}`: Macro to produce a table of contents line with the following parameters:

**level** If `<level> > \c@tocdepth`, then no line produced.

**indent** Total indentation from the left margin.

**numwidth** Width of box for number if the *<title>* has a `\numberline` command.  
 As of 25 Jan 1988, this is also the amount of extra indentation added to second and later lines of a multiple line entry.

**title** Contents of entry.

**page** Page number.

Uses the following parameters, which must be set by the document style. They should be defined with `\def`'s.

**pnumwidth** Width of box in which page number is set.

**tocrmarg** Right margin indentation for all but last line of multiple-line entries.

**dotsep** Separation between dots, in mu units. Should be `\def`'d to a number like 2 or 1.7

`\@dottedtocline`

```

179 </2kernel>
180 (*2kernel | latexrelease)
181 (latexrelease)\IncludeInRelease{2018/12/01}%
182 (latexrelease)          {\@dottedtocline}{Prevent protrusion}%
183 \def\@dottedtocline#1#2#3#4#5{%
184   \ifnum #1>\c@tocdepth \else
185     \vskip \z@ \@plus.2\p@
186     {\leftskip #2\relax \rightskip \@tocrmarg \parfillskip -\rightskip
187      \parindent #2\relax\@afterindenttrue
188      \interlinepenalty\@M
189      \leavevmode
190      \@tempdima #3\relax
191      \advance\leftskip \@tempdima \null\nobreak\hskip -\leftskip
192      {#4}\nobreak
193      \leaders\hbox{$\m@th
```

If a document uses fonts other than computer modern, the use of a dot from math can be very disturbing despite the fact that this might be the only place in a document that then uses computer modern. Therefore we surround the dot with an `\hbox` to escape to the surrounding text font.

```

194       \mkern \@dotsep mu\hbox{.}\mkern \@dotsep
195       mu$}\hfill
196     \nobreak
197     \hb@xt@\@pnumwidth{\hfil\normalfont \normalcolor #5%
```

We finish off by preventing any protrusion if that is enabled. If protrusion happens the number may shift to the right and as a result you may end up with an additional dot in the toc line in some situations.

```

198                               \kern-\p@\kern\p@}%
199     \par}%
200   \fi}
```

`\noptrusion` This command, if placed directly to the right (or left) of a word, will prevent prevent protrusion of that word into the margin. It is used in the toc entry lines as they shouldn't protrude. It is implemented as to kerns that cancel each other

but being there hide the word so that protrusion is not added. Note that a zero kern or an empty box would not work as the protrusion mechanism will skip over those.

```

201 \DeclareRobustCommand\noprotrusion{\leavevmode\kern-\p@\kern\p@}

202 \if2kernel\latexrelease\
203 \latexrelease\EndIncludeInRelease
204 \latexrelease\IncludeInRelease{0000/00/00}%
205 \latexrelease\@dottedtocline{Prevent protrusion}%
206 \latexrelease\def\@dottedtocline#1#2#3#4#5{%
207 \latexrelease\ifnum #1>\c@tocdepth \else
208 \latexrelease\vskip \z@ \@plus.2\p@
209 \latexrelease\leftskip #2\relax \rightskip \@tocrmarg \parfillskip -\rightskip
210 \latexrelease\parindent #2\relax\@afterindenttrue
211 \latexrelease\interlinepenalty\@M
212 \latexrelease\leavevmode
213 \latexrelease\@tempdima #3\relax
214 \latexrelease\advance\leftskip \@tempdima \null\nobreak\hskip -\leftskip
215 \latexrelease\#4\ nobreak
216 \latexrelease\leaders\hbox{$\m@th
217 \latexrelease\mkern \@dotsep mu\hbox{.}\mkern \@dotsep
218 \latexrelease\mu$}\hfill
219 \latexrelease\nobreak
220 \latexrelease\hb@xt@\@pnumwidth{\hfil\normalfont \normalcolor #5}%
221 \latexrelease\par}%
222 \latexrelease\fi}
223 \latexrelease
224 \latexrelease\let\noprotrusion\undefined
225 \latexrelease\EndIncludeInRelease
226 \if2kernel\

```

**Note:** \nobreak's added 7 Jan 86 to prevent bad line break that left the page number dangling by itself at left edge of a new line.

Changed 25 Jan 88 to use \leftskip instead of \hangindent so leaders of multiple-line contents entries would line up properly.

**\numberline** \numberline{<number>}: For use in a \contentsline command. It puts <number> flushleft in a box of width \@tempdima (Before 25 Jan 88 change, it also added \@tempdima to the hanging indentation.)

```

227 \def\numberline#1{\hb@xt@\@tempdima{#1\hfil}}
228 \if2kernel\

```

# File G

## ltfloat.dtx

### 61 Floats

The different types of floats are identified by a  $\langle type \rangle$  name, which is the name of the counter for that kind of float. For example, figures are of type ‘figure’ and tables are of type ‘table’. Each  $\langle type \rangle$  has associated a positive  $\langle type\ number \rangle$ , which is a power of two. E.g., figures might have type number 1, tables type number 2, programs type number 4, etc.

The locations where a float can go are specified by a  $\langle placement\ specifier \rangle$ , which is a list of the possible locations, each denoted by a letter as follows:

h : here	— at the current location in the text.
t : top	— at the top of a text page.
b : bottom	— at the bottom of a text page.
p : page	— on a separate float page

In addition, in conjunction with these, you can use ‘!’ which means that the current values of the float positioning parameters are ignored for this float. (Has no effect on ‘p’, float page positioning.) For example, ‘pht’ specifies that the float can appear in any of three locations: page, here or top.

#### 61.1 Floating Environments

```
1 \*2ekernel
2 \message{floats,}
```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

Where floats may appear on a page, and how many may appear there are specified by the following float placement parameters. The numbers are named like counters so the user can set them with the ordinary counter-setting commands.

<code>\c@topnumber</code>	: Number of floats allowed at the top of a column.
<code>\topfraction</code>	: Fraction of column that can be devoted to floats.
<code>\c@dbltopnumber, \dbltopfraction</code>	: Same as above, but for double-column floats.
<code>\c@bottomnumber, \bottomfraction</code>	: Same as above for bottom of page.
<code>\c@totalnumber</code>	: Number of floats allowed in a single column, including in-text floats.
<code>\textfraction</code>	: Minimum fraction of column that must contain text.
<code>\floatpagefraction</code>	: Minimum fraction of page that must be taken up by float page.
<code>\dblfloatpagefraction</code>	: Same as above, for double-column floats.

The document style must define the following.

`\fps@TYPE` : The default placement specifier for floats of type TYPE.

`\ftype@TYPE` : The type number for floats of type TYPE.

`\ext@TYPE` : The file extension indicating the file on which the contents list for float type TYPE is stored.  
For example, `\ext@figure = 'lof'`.

`\fnum@TYPE` : A macro to generate the figure number for a caption.  
For example, `\fnum@TYPE == Figure \thefigure`.

`\@makecaption{NUM}{TEXT}` :  
A macro to make a caption, with NUM the value produced by `\fnum@...` and TEXT the text of the caption. It can assume it's in a `\parbox` of the appropriate width.

`\@float{TYPE}[PLACEMENT]` : This macro begins a float environment for a

single-column float of type TYPE with PLACEMENT as the placement

specifier. The default value of PLACEMENT is defined by `\fps@TYPE`. The environment is ended by `\end@float`.

E.g., `\figure == \@float{figure}, \endfigure == \end@float`.

`\@float{TYPE}[PLACEMENT] ==`

BEGIN

if hmode then `\@bsphack`

`\@floatpenalty := -10002`

else `\@floatpenalty := -10003`

fi

`\@captype ==L TYPE`

`\@dblflset`

`\@fps ==L PLACEMENT`

`\@onelevel@sanitize \@fps`

add default PLACEMENT if at most ! in PLACEMENT ==

`\@fpsadddefault`

if inner

then LaTeX Error: 'Not in outer paragraph mode.'

`\@floatpenalty := 0`

else if `\@freelist` nonempty

then `\@currbox :=L head of \@freelist`

`\@freelist :=G tail of \@freelist`

`\count\@currbox :=G 32*\ftype@TYPE +`

bits determined by

PLACEMENT

else `\@floatpenalty := 0`

LaTeX Error: 'Too many unprocessed floats'

```

        fi
    fi
    \@currbox :=G    \color@vbox
                    \normalcolor
                    \vbox{
                        %% 15 Dec 87 -
                        %% removed \boxmaxdepth :=L 0pt
                        %% that made box 0 depth because it screwed
                        %% things up. Instead, added \vskip0pt at
end
                                \hsize = \columnwidth
                                \@parboxrestore
                                \@floatboxreset

END

\caption ==
BEGIN
    \refstepcounter{\@capttype}
    \@dblarg{\@caption{\@capttype}}
END

```

In following definition, `\par` moved from after `\addcontentsline` to before `\addcontentsline` because the `\write` could cause an extra blank line to be added to the paragraph above the caption. (Change made 12 Jun 87)

```

\@caption{TYPE}[STEXT]{TEXT} ==
BEGIN
    \par

\addcontentsline{\ext@TYPE}{TYPE}{\numberline{\theTYPE}{STEXT}}
    \begingroup
        \@parboxrestore
        \@normalsize
        \@makecaption{\fnum@TYPE}{TEXT}
        \par
    \endgroup
END

```

`\@dblfloat{TYPE}[PLACEMENT]` : Macro to begin a float environment for

a double-column float of type TYPE with PLACEMENT as the placement

specifier. The default value of PLACEMENT is 'tp'

The environment is ended by `\end@dblfloat`.

E.g., `\figure* == \@dblfloat{figure}`,

`\endfigure* == \end@dblfloat`.

```

\@dblfloat{TYPE}[PLACEMENT] ==

```



Identical to `\@float{TYPE}[PLACEMENT]` except `\hsize` and `\linewidth` are set to `\textwidth`.  
*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\@floatpenalty`

```
3 \newcount\@floatpenalty
```

`\caption` This is set to be an error message outside a float since no `capttype` is defined there; this may need to be changed by some classes.

```
4 \def\caption{%
5   \ifx\@capttype\undefined
6     \latexerror{\noexpand\caption outside float}\@ehd
7     \expandafter\@gobble
8   \else
9     \refstepcounter\@capttype
10    \expandafter\@firstofone
11  \fi
12  {\@dblarg{\@caption\@capttype}}%
13 }
```

`\@caption`

```
14 \long\def\@caption#1[#2]#3{%
15   \par
16   \addcontentsline{\csname ext@#1\endcsname}{#1}%
17   {\protect\numberline{\csname the#1\endcsname}{\ignorespaces #2}}%
18   \begingroup
```

The paragraph setting parameters are normalised at this point, however `\@parboxrestore` resets `\everypar` which is not correct in this context so `\@setminipage` is called if needed.

The float mechanism, like `minipage`, sets the flag `@minipage` true before executing the user-supplied text. Many L<sup>A</sup>T<sub>E</sub>X constructs test for this flag and do not add vertical space when it is true. The intention is that this emulates T<sub>E</sub>X's 'top of page' behaviour. The flag must be set false at the start of the first paragraph. This is achieved by a redefinition of `\everypar`, but the call to `\@parboxrestore` removes that redefinition, so it is re-inserted if needed. If the flag is already false then the `\caption` was not the first entry in the float, and so some other paragraph has already activated the special `\everypar`. In this case no further action is needed.

```
19   \@parboxrestore
20   \if@minipage
21     \@setminipage
22   \fi
23   \normalsize
24   \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par
25   \endgroup}
```

`\@float`

`\@dblflset`

```
26 \def\@float#1{%
27   \ifnextchar[%
28     {\@xfloat{#1}}%
29     {\edef\reserved@a{\noexpand\@xfloat{#1}[\csname fps@#1\endcsname}}%
30     \reserved@a}}
```

`\@dblfloat`

```
31 \def\@dblfloat{%
32   \if@twocolumn\let\reserved@a\@dbflt\else\let\reserved@a\@float\fi
33   \reserved@a}
```

`\fps@dbl` Note that all double floats have default fps ‘tp’.

`\@setfps` This sets the fps, dealing with error conditions by adding the default.

`\@xfloat` The first part of this sets the count register that stores all the information about the type and fps of the float.

We assume here that the default specifiers already contain no active characters.

It may be better to store the defaults as numbers, rather than symbol strings.

```
34 \if2kernel
35 \if@twocolumn\let\reserved@a\@dbflt\else\let\reserved@a\@float\fi
36 \if@twocolumn\let\reserved@a\@dbflt\else\let\reserved@a\@float\fi
37 \if2kernel\let\reserved@a\@dbflt\else\let\reserved@a\@float\fi
38 \def\@xfloat #1[#2]{%
39   \nodocument
40   \def \@captype {#1}%
41   \def \@fps {#2}%
42   \@onelevel@sanitize \@fps
43   \def \reserved@b {}%
44   \ifx \reserved@b \@fps
45     \fpsadddefault
46   \else
47     \ifx \@fps \empty
48       \fpsadddefault
49     \fi
50   \fi
51   \ifhmode
52     \bsphack
53     \@floatpenalty -\@Mii
54   \else
55     \@floatpenalty-\@Miii
56   \fi
57   \ifinner
58     \@parmoderr\@floatpenalty\z@
59   \else
60     \@next\@currbox\@freelist
61     {%
62       \@tempcnta \sixt@@n
63       \expandafter \@tfor \expandafter \reserved@a
64       \expandafter :\expandafter =\@fps
65       \do
```

Start of changes, use a nested if structure, ending in an error.

```
66     {%
67       \if \reserved@a h%
68         \ifodd \@tempcnta
69         \else
70           \advance \@tempcnta \@ne
71         \fi
72       \else\if \reserved@a t%
```

```

73         \@setfpsbit \tw@
74         \else\if \reserved@a b%
75             \@setfpsbit 4%
76         \else\if \reserved@a p%
77             \@setfpsbit 8%
78         \else\if \reserved@a !%
79             \ifnum \@tempcnta>15
80                 \advance\@tempcnta -\sixt@@n\relax
81             \fi
82         \else
83             \@latex@error{Unknown float option '\reserved@a'}%
84             {Option '\reserved@a' ignored and 'p' used.}%
85             \@setfpsbit 8%
86         \fi\fi\fi\fi\fi
87     }%

```

End of changes

```

88     \@tempcntb \csname ftype@\@capytype \endcsname
89     \multiply \@tempcntb \@xxxii
90     \advance \@tempcnta \@tempcntb
91     \global \count\@currbox \@tempcnta
92 }%
93 \fltovf
94 \fi

```

The remainder sets up the box in which the float is typeset, and the typesetting environment to be used. It is essential to have the extra box to avoid the unwanted space that would otherwise often be put at the top of the float.

It ends with a hook; not sure how useful this is but it is needed at present to deal with double-column floats.

```

95 \global \setbox\@currbox
96 \color@vbox
97 \normalcolor
98 \vbox \bgroup
99 \hsize\columnwidth
100 \@parboxrestore
101 \@floatboxreset
102 }%
103 </2ekernel | latexrelease>
104 <latexrelease>\EndIncludeInRelease
105 <latexrelease>\IncludeInRelease{0000/00/00}%
106 <latexrelease>          {\@xfloat}{Check float options}%
107 <latexrelease>\def\@xfloat #1[#2]{%
108 <latexrelease>  \@nodocument
109 <latexrelease>  \def \@capytype {#1}%
110 <latexrelease>  \def \@fps {#2}%
111 <latexrelease>  \@onelevel@sanitize \@fps
112 <latexrelease>  \def \reserved@b {!}%
113 <latexrelease>  \ifx \reserved@b \@fps
114 <latexrelease>      \fpsadddefault
115 <latexrelease>  \else
116 <latexrelease>      \ifx \@fps \@empty
117 <latexrelease>          \fpsadddefault
118 <latexrelease>      \fi
119 <latexrelease>  \fi

```

```

120 \latexrelease\ \ifhmode
121 \latexrelease\ \@bsphack
122 \latexrelease\ \@floatpenalty -\@Mii
123 \latexrelease\ \else
124 \latexrelease\ \@floatpenalty-\@Miii
125 \latexrelease\ \fi
126 \latexrelease\ \ifinner
127 \latexrelease\ \@parmoderr\@floatpenalty\z@
128 \latexrelease\ \else
129 \latexrelease\ \@next\@currbox\@freelist
130 \latexrelease\ {%
131 \latexrelease\ \@tempcnta \sixt@@n
132 \latexrelease\ \expandafter \@tfor \expandafter \reserved@a
133 \latexrelease\ \expandafter :\expandafter =\@fps
134 \latexrelease\ \do
135 \latexrelease\ {%
136 \latexrelease\ \if \reserved@a h%
137 \latexrelease\ \ifodd \@tempcnta
138 \latexrelease\ \else
139 \latexrelease\ \advance \@tempcnta \@ne
140 \latexrelease\ \fi
141 \latexrelease\ \fi
142 \latexrelease\ \if \reserved@a t%
143 \latexrelease\ \@setfpsbit \tw@
144 \latexrelease\ \fi
145 \latexrelease\ \if \reserved@a b%
146 \latexrelease\ \@setfpsbit 4%
147 \latexrelease\ \fi
148 \latexrelease\ \if \reserved@a p%
149 \latexrelease\ \@setfpsbit 8%
150 \latexrelease\ \fi
151 \latexrelease\ \if \reserved@a !%
152 \latexrelease\ \ifnum \@tempcnta>15
153 \latexrelease\ \advance\@tempcnta -\sixt@@n\relax
154 \latexrelease\ \fi
155 \latexrelease\ \fi
156 \latexrelease\ }%
157 \latexrelease\ \@tempcntb \csname ftype@\@capttype \endcsname
158 \latexrelease\ \multiply \@tempcntb \@xxxii
159 \latexrelease\ \advance \@tempcnta \@tempcntb
160 \latexrelease\ \global \count\@currbox \@tempcnta
161 \latexrelease\ }%
162 \latexrelease\ \@fltovf
163 \latexrelease\ \fi
164 \latexrelease\ \global \setbox\@currbox
165 \latexrelease\ \color@vbox
166 \latexrelease\ \normalcolor
167 \latexrelease\ \vbox \bgroup
168 \latexrelease\ \hsize\columnwidth
169 \latexrelease\ \@parboxrestore
170 \latexrelease\ \@floatboxreset
171 \latexrelease\}%
172 \latexrelease\ \EndIncludeInRelease
173 \*2kernel)

```

`\@floatboxreset` The rationale for allowing these normally global flags to be set locally here, via `\@parboxrestore`, was stated originally by Donald Arseneau and extended by Chris Rowley. It is because these flags are only set globally to true by section commands, and these should never appear within marginals or floats or, indeed, in any group; and they are only ever set globally to false when they are definitely true.

If anyone is unhappy with this argument then both flags should be treated as in `\set@nobreak`; otherwise this command will be redundant.

```
174 \def \@floatboxreset {%
175     \reset@font
176     \normalsize
177     \@setminipage
178 }
```

`\@setnobreak`

```
179 \def \@setnobreak{%
180     \if@nobreak
181         \let\outer@nobreak\@nobreaktrue
182         \@nobreakfalse
183     \fi
184 }
```

`\@setminipage`

```
185 \def \@setminipage{%
186     \@minipagetrue
187     \everypar{\@minipagefalse\everypar{}}%
188 }
```

`\end@float`

```
189 \def\end@float{%
190     \@endfloatbox
191     \ifnum\@floatpenalty <\z@
192         \@largefloatcheck
193         \@cons\@currlist\@currbox
194         \ifnum\@floatpenalty <-\@Mii
195             \penalty -\@Miv
```

Saving and restoring `\prevdepth` added 26 May 87 to prevent extra vertical space when used in vertical mode.

```
196         \@tempdima\prevdepth
197         \vbox{}%
198         \prevdepth\@tempdima
199         \penalty\@floatpenalty

200     \else
201         \vadjust{\penalty -\@Miv \vbox{}\penalty\@floatpenalty}\@Esphack
202     \fi
203 \fi
204 }
```

\end@dblfloat

```
205 </2ekernel>
206 <latexrelease>\IncludeInRelease{2015/01/01}%
207 <latexrelease>          {\end@dblfloat}{float order in 2-column}%
208 <*2ekernel|latexrelease>
209 \def\end@dblfloat{%
210   \if@twocolumn
211     \@endfloatbox
212     \ifnum\@floatpenalty <\z@
213       \@largefloatcheck
214       \global\dp\@currbox1sp %
215       \global\dp\@currbox1sp %
216       \ifnum\@floatpenalty <-\@Mii
217         \penalty -\@Miv
218         \@tempdima\prevdepth
219         \vbox{}%
220         \prevdepth\@tempdima
221         \penalty\@floatpenalty
222       \else
223         \vadjust{\penalty -\@Miv \vbox{}}\penalty\@floatpenalty\@Esphack
224       \fi
225     \fi
226   \else
227     \end@float
228   \fi
229 }%
230 </2ekernel|latexrelease>
231 <latexrelease>\EndIncludeInRelease
232 <latexrelease>\IncludeInRelease{0000/00/00}%
233 <latexrelease>          {\end@dblfloat}{float order in 2-column}%
234 <latexrelease>\def\end@dblfloat{%
235 <latexrelease>\if@twocolumn
236 <latexrelease>  \@endfloatbox
237 <latexrelease>  \ifnum\@floatpenalty <\z@
238 <latexrelease>    \@largefloatcheck
239 <latexrelease>    \@cons\@dbldeferlist\@currbox
240 <latexrelease>    \fi
241 <latexrelease>    \ifnum \@floatpenalty ==-\@Mii \@Esphack\fi
242 <latexrelease>\else
243 <latexrelease>  \end@float
244 <latexrelease>\fi
245 <latexrelease>}%
246 <latexrelease>\EndIncludeInRelease
247 <*2ekernel>
```

Force the depth of two column float boxes.

What follows is essentially \end@float without a starting \@endfloatbox.

We make sure that we never exceed \textheight, otherwise float will never get typeset (91/03/15 FMi).

RmS 92/03/18 changed \@esphack to \@Esphack.

```

\@endfloatbox This macro is not intended to be a hook; it is designed to help maintain the
               integrity of this code, which is used twice and, as can be seen, is subject to
               frequent changes.
248 \def \@endfloatbox{%
249     \par\vskip\z@skip      %% \par\vskip\z@ added 15 Dec 87
250     \@minipagefalse
251     \outer@nobreak
252     \egroup                %% end of vbox
253     \color@endbox
254 }

\outer@nobreak
255 \let\outer@nobreak\@empty

\@largefloatcheck This calculates by how much a float is oversize for the page and prints this in a
                   warning message.
256 \def \@largefloatcheck{%
257     \ifdim \ht\@currbox>\textheight
258         \@tempdima -\textheight
259         \advance \@tempdima \ht\@currbox

260         \@latex@warning {Float too large for page by \the\@tempdima}%
261         \ht\@currbox \textheight
262     \fi
263 }

\@dbflt
\@xdblfloat 264 \def\@dbflt#1{\@ifnextchar[{\@xdblfloat{#1}}{\@xdblfloat{#1}[tp]}}
265 \def\@xdblfloat#1[#2]{%
266     \@xfloat{#1}[#2]\hsize\textwidth\linewidth\textwidth}

               Moved to ltoutput 93/12/16
267 %\newcount\c@topnumber
268 %\newcount\c@dbltopnumber
269 %\newcount\c@bottomnumber
270 %\newcount\c@totalnumber

\@floatplacement An analysis of \@floatplacement:
                  This should be called whenever \@colht has been set.
271 \def\@floatplacement{\global\@topnum\c@topnumber
272     % Textpage bit, global:
273     \global\@toproom \topfraction\@colht
274     \global\@botnum \c@bottomnumber
275     \global\@botroom \bottomfraction\@colht
276     \global\@colnum \c@totalnumber
277     % Floatpage bit, local:
278     \@fpmin \floatpagefraction\@colht}
279 \endkernel)

\@dblfloatplacement This should be called only within a group. Now changed to provide extra checks
                    in \@addtodblcol, needed when processing a BANG float.
280 \ifx\@floatplacement\@floatplacement\@floatplacement\@floatplacement\@floatplacement\@floatplacement
281 \ifx\@floatplacement\@floatplacement\@floatplacement\@floatplacement\@floatplacement\@floatplacement
282 \ifx\@floatplacement\@floatplacement\@floatplacement\@floatplacement\@floatplacement\@floatplacement

```

```

283 \def\@dblfloatplacement{\global\@dbltopnum\cdbltopnumber
284   \global\@dbltoproom \dbltopfraction\@colht
285   \@textmin \@colht
286   \advance \@textmin -\@dbltoproom
287   \@fpmmin \dblfloatpagefraction\textheight
288   \@fptop \dblfpptop
289   \@fpsep \dblfpsep
290   \@fpbot \dblfpbot

\f@depth is used in \@testwrongwidth to look for either column or
column floats. A value of 1sp signals the latter. Because of this setting
\@dblfloatplacment needs to be called inside a group which is a question
design.

291   \def\f@depth{1sp}}%

292 </2kernel | latexrelease>
293 <latexrelease>\EndIncludeInRelease
294 <latexrelease>\IncludeInRelease{0000/00/00}%
295 <latexrelease>           {\@dblfloatplacement}{float order in 2-column}%
296 <latexrelease>\def \@dblfloatplacement {%
```

```

297 \global \@dbltopnum \c@dbltopnumber
298 \global \@dbltoproom \dbltopfraction\@colht

```

```

299 \latexrelease \textmin \colht
300 \latexrelease \advance \textmin -\dbltoproom

```

```

301 \latexrelease) \@fpmmin \dblfloatpagefraction\textheight
302 \latexrelease) \@fptop \@dblftop
303 \latexrelease) \@fpsep \@dblpsep
304 \latexrelease) \@fpbot \@dblfpbot
305 \latexrelease)}}%
306 \latexrelease)\EndIncludeInRelease
307 \*2ekernel)

```

Marginal notes use the same mechanism as floats to communicate with the `\output` routine. Marginal notes are distinguished from floats by having a negative placement specification. The command `\marginpar [LTEXT]{RTEXT}` generates a marginal note in a parbox, using LTEXT if it's on the left and RTEXT if it's on the right. (Default is RTEXT = LTEXT.) It uses the following parameters.

File G: 1tfloat.dtx Date: 2015/02/21 Version v1.2c



```

\hskip -\marginparwidth \hskip -\marginparsep .
\marginparpush : Minimum vertical separation between \marginpar's

```

Marginal notes are normally put on the outside of the page if @mparswitch = true, and on the right if @mparswitch = false. The command `\reversemarginpar` reverses the side where they are put. `\normalmarginpar` undoes `\reversemarginpar`. These commands have no effect for two-column output.

SURPRISE: if two marginal notes appear on the same line of text, then the second one could appear on the next page, in a funny position.

```

\marginpar [LTEXT]{RTEXT} ==
BEGIN
  if hmode then \bsphack
    \floatpenalty := -10002
  else \floatpenalty := -10003
  fi
  if inner
    then LaTeX Error: 'Not in outer paragraph mode.'
    \floatpenalty := 0
  else if \@freelist has two elements:
    then get \@marbox, \@currbox from \@freelist
    \count\@marbox :=G -1
  else \floatpenalty := 0
    LaTeX Error: 'Too many unprocessed floats'
    \@currbox, \@marbox := \@tempboxa    %%use \def
  fi
  fi
  if optional argument
    then %% \@xmpar ==
      \savemarbox\@marbox{LTEXT}
      \savemarbox\@currbox{RTEXT}
    else %% \@ympar ==
      \savemarbox\@marbox{RTEXT}
      \box\@currbox :=G \box\@marbox
    fi
  \xympar
END

\reversemarginpar == BEGIN \@mparbottom :=G 0
                      @reversemargin :=G true
                      END

\normalmarginpar == BEGIN \@mparbottom :=G 0
                      @reversemargin :=G false
                      END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\marginpar`

```

308 \def\marginpar{%
309   \ifhmode
310     \bsphack
311     \@floatpenalty -\@Mii
312   \else
313     \@floatpenalty-\@Miii
314   \fi
315   \ifinner
316     \@parmoderr
317     \@floatpenalty\z@
318   \else
319     \@next\@currbox\@freelist{}\{}%
320     \@next\@marbox\@freelist{\global\count\@marbox\m@ne}%
321     {\@floatpenalty\z@
322       \fltovf\def\@currbox{\@tempboxa}\def\@marbox{\@tempboxa}}%
323   \fi
324   \@ifnextchar [\@xmpar\@ympar}

```

`\@xmpar`

```

325 \long\def\@xmpar[#1]#2{%
326   \@savemarbox\@marbox{#1}%
327   \@savemarbox\@currbox{#2}%
328   \@xympar}

```

`\@ympar`

```

329 \long\def\@ympar#1{%
330   \@savemarbox\@marbox{#1}%
331   \global\setbox\@currbox\copy\@marbox
332   \@xympar}

```

`\@savemarbox`

```

333 \long\def \@savemarbox #1#2{%
334   \global\setbox #1%
335     \color@vbox
336     \vtop{%
337       \hsize\marginparwidth
338       \@parboxrestore
339       \@marginparreset
340       #2%
341       \@minipagefalse
342       \outer@nobreak
343     }%
344   \color@endbox
345 }

```

`\@marginparreset`

The rationale for allowing these normally global flags to be set locally here, via `\@parboxrestore` was stated originally by Donald Arsenau and extended by Chris Rowley. It is because these flags are only set globally to true by section commands, and these should never appear within marginals or floats or, indeed, in any group; and they are only ever set globally to false when they are definitely true.

If anyone is unhappy with this argument then both flags should be treated as in `\set@nobreake`; otherwise this command will be redundant.

```

346 \def \@marginparreset {%
347     \reset@font
348     \normalsize
349 %     \let@if@nobreake\iffalse
350 %     \let@if@noskipsec\iffalse
351 %     \@setnobreake
352     \@setminipage
353 }
```

`\@xympar`

Setting the box here is done only because the code uses `\end@float`; it will be empty and gets discarded.

```

354 \def \@xympar{%
355     \ifnum\@floatpenalty <\z@\@cons\@currlist\@marbox\fi
356     \setbox\@tempboxa
357     \color@vbox
358     \vbox \bgroup
359     \end@float
360     \@ignorefalse
361     \@esphack
362 }
```

`\reversemarginpar`

`\normalmarginpar`

```

363 \def\reversemarginpar{\global\@mparbottom\z@ \@reversemargintrue}
364 \def\normalmarginpar{\global\@mparbottom\z@ \@reversemarginfalse}

365 \message{footnotes,}
```

## 61.2 Footnotes

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

`\footnote{NOTE}` : User command to insert a footnote.

`\footnote[NUM]{NOTE}`: User command to insert a footnote numbered *NUM*, where *NUM* is a number – 1, 2, etc. For example, if footnotes are numbered \*, \*\*, etc. within pages, then `\footnote[2]{...}` produces footnote '\*\*'. This command does not step the footnote counter.

`\footnotemark[NUM]` : Command to produce just the footnote mark in the text, but no footnote. With no argument, it steps the footnote counter before generating the mark.

`\footnotetext[NUM]{TEXT}` : Command to produce the footnote but no mark. `\footnote` is equivalent to `\footnotemark \footnotetext` .

As in PLAIN, footnotes use `\insert\footins`, and the following parameters:

- `\footnotesize` : Size-changing command for footnotes.
- `\footnotesep` : The height of a strut placed at the beginning of every footnote.
- `\skip\footins` : Space between main text and footnotes. The rule separating footnotes from text occurs in this space. This space lies above the strut of height `\footnotesep` which is at the beginning of the first footnote.
- `\footnoterule` : Macro to draw the rule separating footnotes from text. It is executed right after a `\vspace` of `\skip\footins`. It should take zero vertical space—i.e., it should to a negative skip to compensate for any positive space it occupies. (See PLAIN.TEX.)
- `\interfootnotelinepenalty` : Interline penalty for footnotes.
- `\thefootnote` : In usual LaTeX style, produces the footnote number. If footnotes are to be numbered within pages, then the document style file must include an `\@addtoreset` command to cause the footnote counter to be reset when the page counter is stepped. This is not a good idea, though, because the counter will not always be reset in time to ensure that the first footnote on a page is footnote number one.
- `\@thefnmark` : Holds the current footnote's mark—e.g., `\dag` or `'1'` or `'a'`.
- `\@mpfnnumber` : A macro that generates the numbers for `\footnote` and `\footnotemark` commands. It == `\thefootnote` outside a minipage environment, but can be changed inside to generate numbers for `\footnote`'s.
- `\@makefnmark` : A macro to generate the footnote marker from `\@thefnmark`. The default definition was `\hbox{$^\@thefnmark$}`.
- This is now replaced by  
`\textsuperscript{\@thefnmark}`
- `\@makefntext{NOTE}` :  
Must produce the actual footnote, using `\@thefnmark` as the mark of the footnote and NOTE as the text. It is called when

effectively inside a `\parbox`, with `\hsize = \columnwidth`.

For example, it might be as simple as

```
$^{\@thefnmark}$ NOTE
```

In a minipage environment, `\footnote` and `\footnotetext` are redefined so that

(a) they use the counter `mpfootnote`

(b) the footnotes they produce go at the bottom of the minipage.

The switch is accomplished by letting `\@mpfn == footnote` or `mpfootnote` and `\thempfn == \thefootnote` or `\thempfootnote`, and by redefining `\@footnotetext` to be `\@mpfootnotetext` in the minipage.

```
\footnote{NOTE} ==
BEGIN
  \stepcounter{\@mpfn}
  begingroup
    \protect == \noexpand
    \@thefnmark :=G eval (\thempfn)
  endgroup
  \@footnotemark
  \@footnotetext{NOTE}
END

\footnote[NUM]{NOTE} ==
BEGIN
  begingroup
    \protect == \noexpand
    counter \@mpfn :=L NUM
    \@thefnmark :=G eval (\thempfn)
  endgroup
  \@footnotemark
  \@footnotetext{NOTE}
END

\footnotemark ==
BEGIN \stepcounter{footnote}
  begingroup
    \protect == \noexpand
    \@thefnmark :=G eval(\thefootnote)
  endgroup
  \@footnotemark
END
```

```
\footnotemark[NUM] ==
BEGIN
  begingroup
    footnote counter :=L NUM
    \protect == \noexpand
    \@thefnmark :=G eval(\thefootnote)
  endgroup
```

```

\@footnotemark
END

\@footnotemark ==
BEGIN
\leavevmode
IF hmode THEN \@x@sf := \the\spacefactor FI
\@makefnmark          % put number in main text
IF hmode THEN \spacefactor := \@x@sf FI
END

\footnotetext ==
BEGIN begingroup \protect == \noexpand
\@thefnmark :=G eval (\thempfn)
endgroup
\@footnotetext
END

\footnotetext[ NUM] ==
BEGIN begingroup counter \@mpfn :=L NUM
\protect == \noexpand
\@thefnmark :=G eval (\thempfn)
endgroup
\@footnotetext
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

\footins LATEX does use the same insert for footnotes as PLAIN.
366 \newinsert\footins
      LATEX leaves these initializations for the \footins insert.
367 \skip\footins=\bigskipamount % space added when footnote is present
368 \count\footins=1000 % footnote magnification factor (1 to 1)
369 \dimen\footins=8in % maximum footnotes per page

\footnoterule LATEX keeps PLAIN TEX's \footnoterule as the default.
370 \def\footnoterule{\kern-3\p@
371   \hrule \@width 2in \kern 2.6\p@} % the \hrule is .4pt high

\thefootnote
372 \@definecounter{footnote}
373 \def\thefootnote{\@arabic\c@footnote}

\thempfootnote The default display for the footnote counter in minipages is to use italic letters.
                We use \itshape not \textit as the latter would add an italic correction.
374 \@definecounter{mpfootnote}
375 \def\thempfootnote{{\itshape\@alph\c@mpfootnote}}

\@makefnmark Default definition.
376 %\def\@makefnmark{\hbox{\$~{\@thefnmark}\m@th}}
377 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}

```

`\textsuperscript` This command provides superscript characters in the current text font. It's implementation might change!!!

```

378 \DeclareRobustCommand*\textsuperscript[1]{%
379   \textsuperscript{\selectfont#1}}

```

`\@textsuperscript` This command should not be used directly, but may be used to define other commands `\textsuperscript`, `\@makefnmark`. #1 should always start with a font selection command, to activate the font size switch.

```

380 \def\@textsuperscript#1{%
381   {\m@th\ensuremath{^{\mbox{\fontsize\sfontsize\z@#1}}}}}

```

`\textsubscript`

```

382 \if2kernel
383 \iflatexrelease\IncludeInRelease{2015/01/01}%
384 \iflatexrelease\textsubscript{\textsubscript}%
385 \if2kernel\iflatexrelease
386 \DeclareRobustCommand*\textsubscript[1]{%
387   \textsubscript{\selectfont#1}}%

```

`\@textsubscript`

```

388 \def\@textsubscript#1{%
389   {\m@th\ensuremath_{\mbox{\fontsize\sfontsize\z@#1}}}}}
390 \if2kernel\iflatexrelease
391 \iflatexrelease\EndIncludeInRelease
392 \iflatexrelease\IncludeInRelease{0000/00/00}%
393 \iflatexrelease\textsubscript{\textsubscript}%
394 \iflatexrelease\let\textsubscript\@undefined
395 \iflatexrelease\let\@textsubscript\@undefined
396 \iflatexrelease\EndIncludeInRelease
397 \if2kernel

```

`\footnotesep`

```

398 \newdimen\footnotesep

```

`\footnote`

```

399 \def\footnote{\ifnextchar[\@xfootnote{\stepcounter\@mpfn
400   \protected@xdef\@thefnmark{\thempfn}%
401   \@footnotemark\@footnotetext}}

```

`\@xfootnote`

```

402 \def\@xfootnote[#1]{%
403   \begingroup
404     \csname c@\@mpfn\endcsname #1\relax
405     \unrestored@protected@xdef\@thefnmark{\thempfn}%
406   \endgroup
407   \@footnotemark\@footnotetext}

```

`\@footnotetext`

```

408 \long\def\@footnotetext#1{\insert\footins{%
409   \reset@font\footnotesize
410   \interlinepenalty\interfootnotelinepenalty

```

```

411 \splittopskip\footnotesep
412 \splitmaxdepth \dp\strutbox \floatingpenalty \MM
413 \hsize\columnwidth \@parboxrestore
414 \protected@edef\@currentlabel{%
415 \csname p@footnote\endcsname\@thefnmark
416 }%
417 \color@begingroup
418 \makefnmark{%
419 \rule\z@{\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
420 \color@endgroup}}%

\footnotemark

421 \def\footnotemark{%
422 \ifnextchar[\@xfootnotemark
423 {\stepcounter{footnote}%
424 \protected@xdef\@thefnmark{\thefootnote}%
425 \@footnotemark}}

\@xfootnotemark

426 \def\@xfootnotemark[#1]{%
427 \begingroup
428 \c@footnote #1\relax
429 \unrestored@protected@xdef\@thefnmark{\thefootnote}%
430 \endgroup
431 \@footnotemark}

\@footnotemark

432 \def\@footnotemark{%
433 \leavevmode
434 \ifhmode\edef\@x@sf{\the\spacefactor}\nobreak\fi
435 \makefnmark
436 \ifhmode\spacefactor\@x@sf\fi
437 \relax}

\footnotetext

438 \def\footnotetext{%
439 \ifnextchar [\@xfootnotenext
440 {\protected@xdef\@thefnmark{\thempfn}%
441 \@footnotetext}}

\@xfootnotenext

442 \def\@xfootnotenext[#1]{%
443 \begingroup
444 \csname c@\@mpfn\endcsname #1\relax
445 \unrestored@protected@xdef\@thefnmark{\thempfn}%
446 \endgroup
447 \@footnotetext}

\thempfn
\@mpfn
448 \def\@mpfn{footnote}
449 \def\thempfn{\thefootnote}
450 /2ekernel

```



# File H

## ltidxglo.dtx

### 62 Index and Glossary Generation

Index and Glossary commands.

```

\makeindex      A preamble command to turn on indexing.
\makeglossary   A preamble command to turn on making glossary entries.
  \index        Make an index entry for #1.
  \glossary     Make a glossary entry for #1.
Historical LATEX 2.09 comments (not necessarily accurate any more):
\makeindex ==
  BEGIN
    \index == BEGIN \@bsphack
              \begingroup
              \protect{X} == \string X\space
              %% added 3 Feb 87 for \index
commands
              %% in \footnotes
              re-\catcode special characters
              to 'other'
              \@wrindex

  END

\@wrindex{ITEM} ==
  BEGIN
    write of {\indexentry{ITEM}{page number}}
    \endgroup
    \@esphack
  END

INITIALIZATION:

\index == BEGIN \@bsphack
          \begingroup
          re-\catcode special characters (in case '%' there)
          \@index
        END

\@index{ITEM} == BEGIN \endgroup \@esphack END

Changes made 14 Apr 89 to write \glossaryentry's instead of
\indexentry's on the .glo file.
End of historical LATEX 2.09 comments.
1 (*2ekernel)
2 \message{index,}

```

\makeindex

```
3 \def\makeindex{%
4   \newwrite\@indexfile
5   \immediate\openout\@indexfile=\jobname.idx
6   \def\index{\@bsphack\begingroup
7     \@sanitize
8     \@wrindex}\typeout
9     {Writing index file \jobname.idx}}%
```

Opening the write channel should be done only once since on some OS multiple opens are forbidden and in any case it is useless. So we turn this into a no-op after use.

```
10 \let\makeindex\@empty
11 }
12 \@onlypreamble\makeindex
```

\@wrindex

```
13 \def\@wrindex#1{%
14   \protected@write\@indexfile{%
15     {\string\indexentry{#1}{\thepage}}%
16   \endgroup
17   \@esphack}
```

\index

```
18 \def\index{\@bsphack\begingroup \@sanitize\@index}
```

\@index

```
19 \def\@index#1{\endgroup\@esphack}
```

\makeglossary

```
20 \def\makeglossary{%
21   \newwrite\@glossaryfile
22   \immediate\openout\@glossaryfile=\jobname.glo
23   \def\glossary{\@bsphack\begingroup
24     \@sanitize
25     \@wrglossary}\typeout
26     {Writing glossary file \jobname.glo }}%
```

Opening the write channel should be done only once since on some OS multiple opens are forbidden and in any case it is useless. So we turn this into a no-op after use.

```
27 \let\makeglossary\@empty
28 }
29 \@onlypreamble\makeglossary
```

\@wrglossary

```
30 \def\@wrglossary#1{%
31   \protected@write\@glossaryfile{%
32     {\string\glossaryentry{#1}{\thepage}}%
33   \endgroup
34   \@esphack}
```

\glossary

```
35 \def\glossary{\@bsphack\begingroup\@sanitize\@index}
36 </2ekernel>
```

# File I

## ltbibl.dtx

### 63 Bibliography Generation

A bibliography is created by the `thebibliography` environment, which generates a title such as “References”, and a list of entries. The `BIBTEX` program will create a file containing such an environment, which will be read in by the `\bibliography` command. With `BIBTEX`, the following commands will be used.

<code>\bibliography</code>	<code>\bibliography{⟨file1,file2, ...,filen⟩}</code> : specifies the bibdata files. Writes a <code>\bibdata</code> entry on the <code>.aux</code> file and tries to read in <code>mainfile.bbl</code> .
<code>\bibliographystyle</code>	<code>\bibliographystyle{⟨style⟩}</code> : Writes a <code>\bibstyle</code> entry on the <code>.aux</code> file.
<code>thebibliography</code>	The <code>thebibliography</code> environment is a list environment. To save the use of an extra counter, it should use <code>enumiv</code> as the item counter. Instead of using <code>\item</code> , items in the bibliography are produced by the following commands: <code>\bibitem{⟨name⟩}</code> : Produces a numbered entry cited as <code>⟨name⟩</code> . <code>\bibitem[⟨label⟩]{⟨name⟩}</code> : Produces an entry labeled by <code>⟨Label⟩</code> and cited by <code>⟨name⟩</code> .

The former is used for bibliographies with citations like [1], [2], etc.; the latter is used for citations like [Knuth82].

The document class must define the `thebibliography` environment. This environment has a single argument, which is the widest bibliography label— e.g., if the [Knuth67] is the widest entry, then this argument will be Knuth67. The `\thebibliography` command must begin a list environment, which the `\endthebibliography` command ends.

<code>\cite</code>	Entries are cited by the command <code>\cite{⟨name⟩}</code> .
<code>\nocite</code>	<code>\nocite{⟨citations⟩}</code> puts information on the <code>.aux</code> file that causes <code>BIBTEX</code> to include the <code>{⟨citations⟩}</code> list in the bibliography, but puts nothing in the text. <code>\nocite{*}</code> is special: it tells <code>BIBTEX</code> to put the whole of a collection of references into the bibliography.

```
1 (*2ekernel)
2 \message{bibliography,}
```

*Historical  $\TeX$  2.09 comments (not necessarily accurate any more):*  
PARAMETERS

<code>@cite</code>	: A macro such that <code>\@cite{LABEL1,LABEL2}{NOTE}</code> produces the output for a <code>\cite[NOTE]{FOO1,FOO2}</code> command,
where entry	FOOi is defined by <code>\bibitem[LABELi]{FOOi}</code> . The switch <code>@tempswa</code> is true if the optional NOTE argument
is present.	
The default definition is :	
	<code>\@cite{LABELS}{NOTE} ==</code> <code>BEGIN [LABELS</code> <code>IF @tempswa = T THEN , NOTE FI</code> <code>]</code>

END

`\@biblabel` : A macro to produce the label in the bibliography entry. For `\bibitem[LABEL]{NAME}`, the label is generated by `\@biblabel{LABEL}`. It has the default definition `\@biblabel{LABEL} -> [LABEL]`.

CONVENTION

`\b@FOO` : The name or number of the reference created by `\cite{FOO}`  
E.g., if `\cite{FOO} -> [17]` , then `\b@FOO -> 17`.

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\bibitem`

```
3 \def\bibitem{\@ifnextchar[\@lbibitem\@bibitem}
```

`\@lbibitem`

```
4 \def\@lbibitem[#1]#2{\item[\@biblabel{#1}\hfill]\if@filesw
5     {\let\protect\noexpand
6      \immediate
7      \write\@auxout{\string\bibcite{#2}{#1}}}\fi\ignorespaces}
```

`\@bibitem`

```
8 \def\@bibitem#1{\item\if@filesw \immediate\write\@auxout
9     {\string\bibcite{#1}{\the\value{\@listctr}}}\fi\ignorespaces}
```

`\bibcite`

```
10 \def\bibcite{\@newl@bel b}
```

`\citation`

```
11 \let\citation\@gobble
```

`\cite`

```
12 \DeclareRobustCommand\cite{%
13   \@ifnextchar [{\@tempswatrue\@citex}{\@tempswafalse\@citex[]}]}
```

`\@citex` \penalty\@m added to definition of `\@citex` to allow a line break after the ‘,’ in citations like [Jones80,Smith77] (Added 23 Oct 86)  
space added after the ‘,’ (21 Nov 87)

```
14 \def\@citex[#1]#2{\leavevmode
15   \let\@citea\@empty
16   \@cite{\@for\@citeb:=#2\do
17     {\@citea\def\@citea{,\penalty\@m\ }%
18     \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}}%
19   \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi
```

Using `\hbox` instead of `\mbox` is fine because of the `\leavevmode` above. In fact the use of a box around the citation contents is more than questionable in my view (FMi), but within 2e I have to keep that for compatibility reasons as it would probably change too many existing documents. Its main reason is to avoid hyphenation of labels such as [FOOB89] into [FOO- B89] so in certain styles it

makes sense; but, for example, in author year citations it becomes more than questionable.

So Chris added yet another hook here, as suggested by, at least, Donald Arsenaui. Note that this one is inside the first argument of the `\@cite` hook. This decouples the top-level typesetting of the citation from the details of the other business conducted here. All this really needs a complete rethink to get the right modularity.

```

20      \ifundefined{b@\@citeb}{\hbox{\reset@font\bfseries ?}}%
21      \G@refundefinedtrue
22      \@latex@warning
23      {Citation ‘\@citeb’ on page \thepage \space undefined}}%
24      {\@cite@ofmt{\csname b@\@citeb\endcsname}}}{#1}}

```

`\bibdata`

`\bibstyle`

```

25 \let\bibdata=\@gobble
26 \let\bibstyle=\@gobble

```

`\bibliography`

```

27 \def\bibliography#1{%
28   \if@filesw
29     \immediate\write\@auxout{\string\bibdata{\zap@space#1 \@empty}}%
30   \fi
31   \@input{\jobname.bbl}}

```

`\bibliographystyle`

```

32 \def\bibliographystyle#1{%
33   \ifx\@begindocumenthook\undefined\else
34     \expandafter\AtBeginDocument
35   \fi
36   {\if@filesw
37     \immediate\write\@auxout{\string\bibstyle{#1}}%
38   \fi}}

```

`\nocite` (Added 14 Jun 85)

This puts information on the `.aux` file that causes BibTeX to include the citation list in the bibliography, but puts nothing in the text.

RmS 93/08/06: Made loop for `\nocite` like that for `\citex`, to get rid of leading spaces.

```

39 \def\nocite#1{\@bsphack

```

With the implementation designed already in L<sup>A</sup>T<sub>E</sub>X 2.09 the `\nocite` command will not work before `\begin{document}` since it tries to write to the `.aux` file which is not open before that point. As a result the “reference” will appear on the terminal and nothing else will happen.

This would be easy to fix, but then a document using the fix will silently fail on an older release of L<sup>A</sup>T<sub>E</sub>X, missing all citations done with `\nocite`. Thus we do only generate an error message and leave the fix for a L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> successor.

```

40   \ifx\@onlypreamble\document

```

Since we are after `\begin{document}` we can do the citations:

```

41     \@for\@citeb:=#1\do{%
42       \edef\@citeb{\expandafter\@firstofone\@citeb}%

```

```

43     \if@files\immediate\write\@auxout{\string\citation{\@citeb}}\fi
44     \@ifundefined{b@\@citeb}{\G@refundefinedtrue
45       \latex@warning{Citation '\@citeb' undefined}}{}%
46   \else

```

But before `\begin{document}` we raise an error message:

```

47     \latex@error{Cannot be used in preamble}\@eha

```

Without the compatibility problems we could fix the problem as follows:

```

48     % \AtBeginDocument{\nocite{#1}}
49   \fi
50   \esphack}

```

Since `\nocite{*}` should not produce a warning about undefined citation keys (see PR 557), we need to set the control sequence `'\b@*'` to something other than `\relax`. As a result `\cite{*}` will not warn either (but that never worked with  $\text{\LaTeX}$  in the first place).

```

51 \expandafter\let\csname b@*\endcsname\@empty

```

### 63.1 Default definitions

This hook determines the ‘relative formatting’ of the two logical parts of a citation with comment.

`\@cite`

```

52 \def\@cite#1#2{[{\#1\if@tempswa , #2\fi}]}

```

`\@cite@ofmt` This is, in general, a command that appears to have one argument whose value is, in the kernel, a single cs whose name is the expansion of `b@\@citeb`; the expansion of this cs will typically be some hmode material that produces the detailed typeset form of just the citations themselves.

```

53 \let\@cite@ofmt\hbox

```

`\@biblabel`

```

54 \def\@biblabel#1{[#1]}
55 \</2ekernel>

```

## File J

# ltpage.dtx

## 64 Page styles and related commands

### 64.1 Page Style Commands

`\pagestyle{<style>}` : sets the page style of the current and succeeding pages to *style*

`\thispagestyle{<style>}` : sets the page style of the current page only to *style*.

To define a page style *style*, you must define `\ps@style` to set the page style parameters.

### 64.2 How a page style makes running heads and feet

The `\ps@...` command defines the macros `\@oddhead`, `\@oddfoot`, `\@evenhead`, and `\@evenfoot` to define the running heads and feet. (See output routine.) To make headings determined by the sectioning commands, the page style defines the commands `\chaptermark`, `\sectionmark`, etc., where `\chaptermark{<text>}` is called by `\chapter` to set a mark. The `\...mark` commands and the `\...head` macros are defined with the help of the following macros.

(All the `\...mark` commands should be initialized to no-ops.)

### 64.3 marking conventions

L<sup>A</sup>T<sub>E</sub>X extends T<sub>E</sub>X's `\mark` facility by producing two kinds of marks a 'left' and a 'right' mark, using the following commands:

`\markboth{<left>}{<right>}` : Adds both marks.

`\markright{<right>}` : Adds a 'right' mark.

`\leftmark` : Used in the output routine, gets the current 'left' mark. Works like T<sub>E</sub>X's `\botmark`.

`\rightmark` : Used in the output routine, gets the current 'right' mark. Works like T<sub>E</sub>X's `\firstmark`. The marking commands work reasonably well for right marks 'numbered within' left marks—e.g., the left mark is changed by a `\chapter` command and the right mark is changed by a `\section` command. However, it does produce somewhat anomalous results if 2 `\markboth`'s occur on the same page.

Commands like `\tableofcontents` that should set the marks in some page styles use a `\mkboth` command, which is `\let` by the `pagestyle` command (`\ps@...`) to `\markboth` for setting the heading or to `\@gobbletwo` to do nothing.

1 (\*2ekernel)

`\pagestyle` User command to set the page style for this and following pages.

```
2 \def\pagestyle#1{%
3   \@ifundefined{ps@#1}%
4     \undefinedpagestyle
5     {\@nameuse{ps@#1}}}
```

`\thispagestyle` User command to set the page style for this page only.

```

6 \def\thispagestyle#1{%
7   \ifundefined{ps@#1}%
8     \undefinedpagestyle
9     {\global\@specialpagetrue\gdef\@specialstyle{#1}}}
```

`\ps@empty` The empty page style: No head or foot line.

```

10 \def\ps@empty{%
11   \let\@mkboth\@gobbletwo\let\@oddhead\@empty\let\@oddfoot\@empty
12   \let\@evenhead\@empty\let\@evenfoot\@empty}
```

`\ps@plain` The plain page style: No head, centred page number in foot.

```

13 \def\ps@plain{\let\@mkboth\@gobbletwo
14   \let\@oddhead\@empty\def\@oddfoot{\reset@font\hfil\thepage
15   \hfil}\let\@evenhead\@empty\let\@evenfoot\@oddfoot}
```

`\@leftmark` We implement `\@leftmark` and `\@rightmark` in terms of already defined commands to save token space. We can't get rid of them since they are sometimes used in applications.

```

16 \let\@leftmark\@firstoftwo
17 \let\@rightmark\@secondoftwo

18 \</2ekernel>
19 \<2ekernel | latexrelease>
20 \<latexrelease>\IncludeInRelease{2019/10/01}%
21 \<latexrelease>          {\markboth}{Make commands robust}%
```

`\markboth` User commands for setting L<sup>A</sup>T<sub>E</sub>X marks.

`\markright` Test for `\@nobreak` added 15 Apr 86 in `\markboth` and `\markright` letting `\label` and `\index` to `\relax` added 22 Feb 86 so these commands can appear in sectioning command arguments RmS 91/06/21 Same for `\glossary`

```

22 \DeclareRobustCommand\markboth[2]{%
23   \begingroup
24     \let\label\relax \let\index\relax \let\glossary\relax
25     \unrestored@protected@xdef\@themark {{#1}{#2}}%
26     \@temptokena \expandafter{\@themark}%
27     \mark{\the\@temptokena}%
28   \endgroup
29   \if@nobreak\ifvmode\nobreak\fi\fi}

30 \DeclareRobustCommand\markright[1]{%
31   \begingroup
32     \let\label\relax \let\index\relax \let\glossary\relax

Protection is handled inside \@markright.
33   \expandafter\@markright\@themark {#1}%
34   \@temptokena \expandafter{\@themark}%
35   \mark{\the\@temptokena}%
36 \endgroup
37 \if@nobreak\ifvmode\nobreak\fi\fi}

38 \</2ekernel | latexrelease>
39 \<latexrelease>\EndIncludeInRelease
40 \<latexrelease>\IncludeInRelease{0000/00/00}%
```



```

41 \latexrelease)                {\markboth}{Make commands robust}%
42 \latexrelease)
43 \latexrelease)\kernel@make@fragile\markboth
44 \latexrelease)\kernel@make@fragile\markright
45 \latexrelease)
46 \latexrelease)\EndIncludeInRelease
47 \<*2ekernel)

\@markright
\leftmark 48 \def\@markright#1#2#3{\@temptokena {#1}%
\rightmark 49 \unrestored@protected@xdef\@themark{\the\@temptokena}{#3}}
50 \def\leftmark{\expandafter\@leftmark\botmark\@empty\@empty}
51 \def\rightmark{\expandafter\@rightmark\firstmark\@empty\@empty}

\@themark Initialise LATEX's marks without setting a TEX mark <whatsit>.
52 \def\@themark{}{}

\mark Test versions of LATEX 2ε initialised TEX's \mark system at this point, but this
was removed before the first release.

\AtBeginDocument{\mark{}{}}

\raggedbottom \raggedbottom typesets pages with no vertical stretch, so they have their natural
height instead of all being exactly the same height. (Uses a space of .0001fil to
avoid interfering with the 1fil space of \newpage.)

53 \DeclareRobustCommand\raggedbottom{%
54 \def\@textbottom{\vskip \z@ \@plus.0001fil}\let\@texttop\relax}

\flushbottom \flushbottom: Inverse of \raggedbottom — makes all pages the same height.

55 \DeclareRobustCommand\flushbottom{%
56 \let\@textbottom\relax \let\@texttop\relax}

\sloppy \sloppy will never (well, hardly ever) produce overfull boxes, but may produce
underfull ones. (14 June 85)

57 \DeclareRobustCommand\sloppy{%
58 \tolerance 9999%
59 \emergencystretch 3em%
60 \hfuzz .5\p@
61 \vfuzz\hfuzz}

sloppypar A sloppypar environment is equivalent to {\par \sloppy ... \par}.

62 \def\sloppypar{\par\sloppy}
63 \def\endsloppypar{\par}

\fussy Resets TEX's parameters to their normal finicky values.

64 \DeclareRobustCommand\fussy{%
65 \emergencystretch\z@
66 \tolerance 200%
67 \hfuzz .1\p@
68 \vfuzz\hfuzz}

\overfullrule LATEX default is no overfull box rule. Changed by document class option.

69 \overfullrule 0pt

70 \</2ekernel)

```

# File K

## ltoutput.dtx

### 65 Output Routine

#### 65.1 Floats

The ‘2ekernel’ code ensures that a `\usepackage{autoout1}` is essentially ignored if a ‘full’ format is being used that has the autoloader file mode already in the format.

```

1 \def\begingroup
2 \def\makeatletter
3 \def\nfss@catcodes
4 (2ekernel)\expandafter\let\csname ver@autoout1.sty\endcsname\fmtversion

```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```

5 (*2ekernel)
6 \message{output,}

*****
*                               *
*                               *
*                               *
*****

```

#### PAGE LAYOUT PARAMETERS

```

\topmargin      : Extra space added to top of page.
@twoside       : boolean. T if two-sided printing
\oddsidemargin : IF @twoside = T
                  THEN extra space added to left of odd-numbered
                  pages.
                  ELSE extra space added to left of all pages.
\evensidemargin : IF @twoside = T
                  THEN extra space added to left of
even-numbered
                  pages.
\headheight    : height of head
\headsep       : separation between head and text
\footskip      : distance separation between baseline of last
                  line of text and baseline of foot.
                  Note difference between \footSKIP and \headSEP.
\textheight    : height of text on page, excluding head and foot
\textwidth     : width of printing on page
\columnsep     : IF @twocolumn = T
                  THEN width of space between columns
\columnseprule : IF @twocolumn = T
                  THEN width of rule between columns (0 if none).
\columnwidth   : IF @twocolumn = T
                  THEN (\textwidth - \columnsep)/2
                  ELSE \textwidth

```

It is set by the `\twocolumn` and `\onecolumn` commands.

`\@textbottom` : Command executed at bottom of vbox holding text of page (including figures). The `\raggedbottom` command almost `\let`'s this to `\vfil` (actually sets it to `\vskip \z@ plus.0001fil`). Should have depth 0pt.

`\@texttop` : Command executed at top of vbox holding text of page (including figures). Used by letter style; can also be used to produce centered pages. Let to `\relax` by `\raggedbottom` and `\flushbottom`.

Page layout must initialize `\@colht` and `\@colroom` to `\textheight`.

#### PAGE STYLE PARAMETERS:

`\floatsep` : Space left between floats.

`\textfloatsep` : Space between last top float or first bottom float and the text.

`\topfigrule` : Command to place rule (or whatever) between floats at top of page and text. Executed in inner vertical mode right before the `\textfloatsep` skip separating the floats from the text. Must occupy zero vertical space. (See `\footnoterule`.)

`\botfigrule` : Same as `\topfigrule`, but put after the `\textfloatsep` skip separating text from the floats at bottom of page.

`\intextsep` : Space left on top and bottom of an in-text float.

`\dblfloatsep` : Space between double-column floats.

`\dbltextfloatsep` : Space between top double-column floats and text.

`\dblfigrule` : Similar to `\topfigrule`, but for double-column floats.

`\@fptop` : Glue to go at top of float column – must be 0pt + stretch

`\@fpsep` : Glue to go between floats in a float column.

`\@fpbot` : Glue to go at bottom of float column  
– must be 0pt + stretch

`\@dblfpptop`, `\@dblfpsep`, `\@dblfpbot`  
: Analogous for double-column float page in two-column format.

FOOTNOTES: As in PLAIN, footnotes use `\insert\footins`.

#### PAGE LAYOUT SWITCHES AND MACROS

`@twocolumn` : Boolean. T if two columns per page globally.

## PAGE STYLE MACROS AND SWITCHES

`\@oddhead` : IF `@twoside = T`  
THEN macro to generate head of  
odd-numbered  
pages.  
ELSE macro to generate head of all pages.  
`\@evenhead` : IF `@twoside = T`  
THEN macro to generate head of  
even-numbered  
pages.  
`\@oddfoot` : IF `@twoside = T`  
THEN macro to generate foot of  
odd-numbered  
pages.  
ELSE macro to generate foot of all pages.  
`\@evenfoot` : IF `@twoside = T`  
THEN macro to generate foot of  
even-numbered  
pages.  
`@specialpage` : boolean. T if current page is to have a special  
format.  
`\@specialstyle` : If its value is `foo` then  
IF `@specialpage = T`  
THEN the command `\ps@foo` is executed to  
temporarily reset the page style parameters  
before composing the current page.  
This command should execute only `\def`'s  
and  
`\edef`'s, making only local definitions.

## FLOAT PLACEMENT PARAMETERS

The following parameters are set by the macro `\@floatplacement`.  
When `\@floatplacement` is called,

`\@colht` is the height of the page or column being built. I.e.:

\* For single-column page it equals `\textheight`.

\* For double-column page it equals `\textheight - height`  
of double-column floats on page.

Note that some are set globally and some locally:

`\@topnum` :=G Maximum number of floats allowed on the top of a  
column.

`\@toproom` :=G Maximum amount of top of column devoted to floats—  
excluding `\textfloatsep` separation below the floats  
and `\floatsep` separation between them. For  
two-column output, should be computed as a function  
of `\@colht`.

`\@botnum`, `\@botroom`

`:` Analogous to above.  
`\@colnum` :=G Maximum number of floats allowed in a column,  
including in-text floats.  
`\@textmin` :=L Minimum amount of text (excluding footnotes) that  
must appear on a text page.  
`%% 27 Sep 85 : made local to`  
`%% \@addtocurcol and \@addtonextcol`  
It is now also used locally in processing double  
floats.  
`\@fpmin` :=L Minimum height of floats in a float column.

The macro `\dblfloatplacement` sets the following parameters.

`\@dbltopnum` :=G Maximum number of double-column floats allowed  
at

the top of a two-column page.

`\@dbltoproom` :=G Maximum height of double-column floats allowed at  
top of two-column page.

`\@fpmin` :=L Minimum height of floats in a float column.

It should also perform the following local assignments where necessary  
– i.e., where the new value differs from the old one:

`\@fptop` :=L `\dblfpptop`  
`\@fpsep` :=L `\dblfpsep`  
`\@fpbot` :=L `\dblfpbot`

## OUTPUT ROUTINE VARIABLES

`\colht` : The total height of the current column. In single column  
style, it equals `\textheight`. In two-column style, it is  
`\textheight` minus the height of the double-column floats  
on the current page. MUST BE INITIALIZED TO  
`\textheight`.

`\colroom` : The height available in the current column for text and  
footnotes. It equals `\colht` minus the height of all  
floats committed to the top and bottom of the current  
column.

`\textfloatsheight` : The total height of in-text floats on the  
current page.

`\footins` : Footnote insertion number.

`\maxdepth` : Saved value of TeX's `\maxdepth`. Must be set  
when any routine sets `\maxdepth`.

## CALLING THE OUTPUT ROUTINE

The output routine is called either by TeX's normal page-breaking  
mechanism, or by a macro putting a penalty `< or = -10000` in the output

list. In the latter case, the penalty indicates why the output routine was called, using the following code.

penalty	reason
-10000	<code>\pagebreak</code> <code>\newpage</code>
-10001	<code>\clearpage</code> ( <code>\penalty -10000 \vbox{} \penalty -10001</code> )
-10002	float insertion, called from horizontal mode
-10003	float insertion, called from vertical mode.
-10004	float insertion.

Note: A float or marginpar puts the following sequence in the output list: (i) a penalty of -10004, (ii) a null `\vbox` (iii) a penalty of -10002 or -10003.

This solves two special problems:

1. If the float comes right after a `\newpage` or `\clearpage`, then the first penalty is ignored, but the second one invokes the output routine.
2. If there is a split footnote on the page, the second 'page' puts out the rest of the footnote.

## THE OUTPUT ROUTINE

### FUNCTIONS USED IN THE OUTPUT ROUTINE:

`\@outputpage` : Produces an output page with the contents of box `\@outputbox` as the text part.

Also sets `\@colht :=G \textheight`.

The page style is determined as follows.

IF `@thispagestyle = true`

THEN use `\thispagestyle` style

ELSE use ordinary page style.

`\@tryfcolumn\FLIST` : Tries to form a float column composed of floats from `\FLIST` (if nonempty) with the following parameters:

`\@colht` : height of box

`\@fpmin` : minimum height of floats in the box

`\@fpsep` : interfloat space

`\@fptop` : glue at top of box

`\@fpbot` : glue at bottom of box.

If it succeeds, then it does the following:

\* `\@outputbox :=L` the composed float box.

\* `@fcolmade :=G true`

\* `\FLIST :=G \FLIST` - floats put in box

\* `\@freelist :=G \@freelist + floats put in box`

If it fails, then:

\* `@fcolmade :=G false`

NOTE: BIT MUST BE A SINGLE TOKEN!

`\@makefcolumn \FLIST` : Same as `\@tryfcolumn` except that it fails to make a float column only if `\FLIST` is empty. Otherwise, it makes a float column containing at least the first box in `\FLIST`, disregarding `\@fpmin`.

`\@startcolumn` :  
Calls `\@tryfcolumn\@deferlist`. If `\@tryfcolumn` returns with (globally set) `@fcolmade = false`, then:  
\* Globally sets `\@toplist` and `\@botlist` to floats from `\@deferlist` to go at top and bottom of column, deleting them from `\@deferlist`. It does this using `\@colht` as the total height, the page style parameters `\@floatsep` and `\@textfloatsep`, and the float placement parameters `\@topnum`, `\@toproom`, `\@botnum`, `\@botroom`, `\@colnum` and `\textfraction`.  
\* Globally sets `\@colroom` to `\@colht` minus the height of the added floats.

`\@startdblcolumn` :  
Calls `\@tryfcolumn\@dbldeferlist{8}`. If `\@tryfcolumn` returns with (globally set) `@fcolmade = false`, then:  
\* Globally sets `\@dbltoplist` to floats from `\@dbldeferlist` to go at top and bottom of column, deleting them from `\@dbldeferlist`. It does this using `\textheight` as the total height, and the parameters `\@dblfloatsep`, etc.  
\* Globally sets `\@colht` to `\textheight` minus the height of the added floats.

`\@combinefloats` : Combines the text from box `\@outputbox` with the floats from `\@toplist` and `\@botlist`, putting the new box in `\@outputbox`. It uses `\floatsep` and `\textfloatsep` for the appropriate separations. It puts the elements of `\TOPLIST` and `\BOTLIST` onto `\@freelist`, and makes those lists null.

`\@makecol` : Makes the contents of `\box255` plus the accumulated footnotes, plus the floats in `\@toplist` and `\@botlist`, into a single column of height `\@colht` (unless the page height has been locally changed), which it puts into box `\@outputbox`. It puts boxes in `\@midlist` back onto `\@freelist` and restores `\maxdepth`.

`\@opcol` : Outputs a column whose text is in box `\@outputbox`. If `@twocolumn = false`, then it calls `\@outputpage`, sets `\@colht := G \textheight`, and calls `\@floatplacement`.

If @twocolumn = true, then:

If @firstcolumn = true, then it puts box \@outputbox into \@leftcolumn and sets @firstcolumn :=G false.

If @firstcolumn = false, then it puts out the current two-column page, any possible two-column float pages, and determines \@dbltoplist for the next page.

## USER COMMANDS THAT CALL OR AFFECT THE OUTPUT ROUTINE

---

```
\newpage == BEGIN \par\vfil\penalty -10000 END
```

```
\clearpage == BEGIN \newpage
                  \write -1{}      % Part of hack to make sure no
                  \vbox{}          % \write's get lost.
                  \penalty -10001
            END
```

```
\cleardoublepage == BEGIN \clearpage
                        if @twoside = true and c@page is even
                        then \hbox{} \newpage fi
            END
```

`\twocolumn[BOX]` : starts a new page, changing to twocolumn setting and puts BOX in a parbox of width `\textwidth` across the top. Useful for full-width titles for double-column pages.

SURPRISE: The stretch from `\@dbltextfloatsep` will be inserted between the BOX and the top of the two columns.

## FLOAT-HANDLING MECHANISMS

---

The float environment obtains an insertion number B from the `\@freelist` (see below for a description of list manipulation), puts the float into box B and sets `\count B` to a FLOAT SPECIFIER. For a normal (not double-column) float, it then causes a page break in one of the following two ways:

- In outer hmode: `\vadjust{\penalty -10002}`
- In vmode : `\penalty -10003`.

For a double-column float, it puts B onto the `\@dbldeferlist`.

The float specifier has two components:

- \* A PLACEMENT SPECIFICATION, describing where the float may be placed.



\* A TYPE, which is a power of two—e.g., figures might be type 1 floats, tables type 2 floats, programs type 4 floats, etc. The float specifier is encoded as follows, where bit 0 is the least significant bit.

Bit	Meaning
0	1 iff the float may go where it appears in the text.
1	1 iff the float may go on the top of a page.
2	1 iff the float may go on the bottom of a page.
3	1 iff the float may go on a float page.
4	1 unless the PLACEMENT includes a !
5	1 iff a type 1 float
6	1 iff a type 2 float
etc.	

A negative float specifier is used to indicate a marginal note.

## MACROS AND DATA STRUCTURES FOR PROCESSING FLOATS

A FLOAT LIST consisting of the floats in boxes `\boxa ... \boxN` has the form:

```
\@elt \boxa ... \@elt \boxN
```

where `\boxI` is defined by

```
\newinsert\boxI
```

Normally, `\@elt` is `\let` to `\relax`. A test can be performed on the entire float list by locally `\def`'ing `\@elt` appropriately and executing the list.

This is a lot more efficient than looping through the list.

The following macros are used for manipulating float lists.

```
\@next \CS \LIST {NONEMPTY}{EMPTY} == %% NOTE: ASSUME
\@elt = \relax
  BEGIN  assume that \LIST == \@elt \B1 ... \@elt \Bn
        if n = 0
        then EMPTY
        else \CS      :=L \B1
              \LIST :=G \@elt \B2 ... \@elt \Bn
              NONEMPTY
        fi
  END
```

`\@bitor\NUM\LIST` : Globally sets switch `@test` to the disjunction for all I of bit `log2 \NUM` of the float specifiers of all the floats in `\LIST`.  
 I.e., `@test` is set to true iff there is at least one float in `\LIST` having bit `log2 \NUM` of its float specifier

equal to 1.

Note:  $\log_2 [(\text{\count I})/32]$  is the bit number corresponding to the type of float I. To see if there is any float in `\LIST` having the same type as float I, you run `\@bitor` with

`\NUM = [(\count I)/32] * 32.`

```
\@bitor\NUM\LIST ==
BEGIN
  @test :=G false
  { \@elt \CTR == if \NUM <> 0 then
                    if \count\CTR / \NUM is odd
                    then @test := true          fi fi
    \LIST
  }
END
```

`\@cons\LIST\NUM` : Globally sets `\LIST := \LIST * \@elt \NUM`

```
\@cons\LIST\NUM ==
BEGIN { \@elt == \relax
        \LIST :=G \LIST \@elt \NUM
      }
```

#### BOX LISTS FOR FLOAT-PLACEMENT ALGORITHMS

```
\@freelist      : List of empty boxes for placing new floats.
\@toplist       : List of floats to go at top of current column.
\@midlist       : List of floats in middle of current column.
\@botlist       : List of floats to go at bottom of current column.
\@deferlist     : List of floats to go after current column.
\@dbltoplist    : List of double-col. floats to go at top of current
                  page.
\@dbldeferlist  : List of double-column floats to go on subsequent
                  pages.
```

#### FLOAT-PLACEMENT ALGORITHMS

`\@addtobot` : Tries to put insert `\@currbox` on `\@botlist`.

Called only when:

- \* `\ht BOX < \@colroom`
- \* type of `\@currbox` not on `\@deferlist`
- \* `\@colnum > 0`
- \* `@insert = false`

If it succeeds, then:

- \* sets `@insert true`
- \* decrements `\@botroom` by `\ht BOX`
- \* decrements `\@botnum` and `\@colnum` by 1

```

* decrements \@colroom by \ht BOX + either
\floatsep
    or \textfloatsep, as appropriate.
* sets \maxdepth to 0pt

\@addtotoporbot : Tries to put insert \@currbox on \@toplist or
                  \@botlist.
                  Called only under same conditions as \@addtobot.
                  If it succeeds, then:
                    * sets @insert true
                    * decrements \@toproom or \@botroom by \ht
BOX
                    * decrements \@colnum and either \@topnum or
                      \@botnum by 1
                    * decrements \@colroom by \ht BOX +
\floatsep
    or \textfloatsep, as appropriate.

\@addtocurcol : Tries to add \@currbox to current column, setting
                @insert true if it succeeds, false otherwise.
                It will add \@currbox to top only if bit 0 of
                \count \@currbox is 0, and to the bottom only if
                bit 0 = 0 or an earlier float of the same type is
                put on the bottom.
                If the float is put in the text, then
                \penalty\interlinepenalty is put
                right after the float, before the following \vskip,
                and \outputpenalty :=L 0.

\@addtonextcol : Tries to add \@currbox to the next column, setting
                @insert true if it succeeds, false otherwise.

\@addtodblcol : Tries to add \@currbox to the next double-column page,
                adding it to \@dbltoplist if it succeeds and
                \@dbldeferlist if it fails.

\@addmarginpar ==
BEGIN
  if \@currlist nonempty
  then remove \@marbox from \@currlist
    add \@marbox and \@currbox to \@freelist
    %% NOTE: \@currbox = left box
  else LaTeX error: ? %% shouldn't happen
  fi
  \@tempcnta := 1      %% 1 = right, -1 = left
  if @twocolumn = true
  then if @firstcolumn = true
    then \@tempcnta := -1
  fi

```

```

else if @mparswitch = true
  then if count0 odd
    else \@tempcnta := -1
    fi
  fi
  if @reversemargin = true
    then \@tempcnta := -\@tempcnta
    fi
  fi
  if \@tempcnta < 0 then \box\@marbox :=G \box\@currbox
  fi
  \@tempdima :=L maximum(\@mparbottom - \@pageht
                        + ht of \@marbox, 0)
  if \@tempdima > 0 then LaTeX warning: 'marginpar moved' fi
  \@mparbottom :=G \@pageht + \@tempdima + depth of \@marbox
                + \marginparpush
  \@tempdima :=L \@tempdima - ht of \@marbox
  \box\@marbox :=G \box\@currbox
                  \vbox { \vskip \@tempdima
                          \box\@marbox
                          }
  height of \@marbox :=G depth of \@marbox :=G 0
  \kern -\@pagedp
  \nointerlineskip
  \hbox{ if @tempcnta > 0 then \hskip \columnwidth
                \hskip \marginparsep
                else \hskip -\marginparsep
                \hskip -\marginparwidth
                fi
        \box\@marbox \hss
      }
  \nobreak
  \nointerlineskip
  \hbox{\vrule height 0 width 0 depth \@pagedp}
END

```

Floats and marginpars add a lot of dead cycles.  
*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

7 \maxdeadcycles = 100
8 \let\@elt\relax
9 \def\@next#1#2#3#4{\ifx#2\@empty #4\else
10 \expandafter\@xnext #2\@#1#2#3\fi}
11 \def\@xnext \@elt #1#2\@#3#4{\def#3{#1}\gdef#4{#2}}
12 \def\@testfalse{\global\let@if@test\iffalse}
13 \def\@testtrue {\global\let@if@test\iftrue}
14 \@testfalse
15 \def\@bitor#1#2{\@testfalse {\let\@elt\@xbitor
16 \@tempcnta #1\relax #2}}

```



```

68 \gdef\@deferlist{}
69 \gdef\@dbltoplist{}

```

The new algorithm stores page wide floats together with column floats in a single `\@deferlist` list. We keep `\@dbldeferlist` initialised as empty so that packages that are testing for deferred floats can use the same code for old or new float handling.

```

70 \gdef\@dbldeferlist{}

PAGE LAYOUT PARAMETERS

71 \newdimen\topmargin
72 \newdimen\oddsidemargin
73 \newdimen\evensidemargin
74 \let\@themargin=\oddsidemargin
75 \newdimen\headheight
76 \newdimen\headsep
77 \newdimen\footskip
78 \newdimen\textheight
79 \newdimen\textwidth
80 \newdimen\columnwidth
81 \newdimen\columnsep
82 \newdimen\columnseprule
83 \newdimen\marginparwidth
84 \newdimen\marginparsep
85 \newdimen\marginparpush

```

`\AtBeginDvi` We use a box register in which to put stuff that must appear before anything else in the .dvi file.

The stuff in the box should not add any typeset material to the page when it is unboxed.

```

86 \newbox\@begindvibox
87 \DeclareRobustCommand \AtBeginDvi [1]{%
88   \global \setbox \@begindvibox
89     \vbox{\unvbox \@begindvibox #1}%
90 }

```

`\@maxdepth` This is not the right place to set this; it needs to be set in a class/style file when `\maxdepth` is set.

Also, many settings to `\maxdepth` should be to `\@maxdepth`, probably?

```

91 \newdimen\@maxdepth
92 \@maxdepth = \maxdepth

```

`\paperheight` New `\paper...` registers.

```

\paperwidth 93 \newdimen\paperheight
94 \newdimen\paperwidth

```

`\if@insert` Local switches first:

```

\if@fcolmade 95 \newif \if@insert

```

`\if@specialpage` These should definitely be global:

```

\if@firstcolumn 96 \newif \if@fcolmade
\if@twocolumn 97 \newif \if@specialpage \@specialpagefalse
\if@twoside

```

```

\if@reversemarginpar
\if@mparswitch
\col@number

```

These should be global but are not always set globally in other files.

```
98 \newif \if@firstcolumn \@firstcolumntrue
99 \newif \if@twocolumn \@twocolumnfalse
```

Not sure about these: two questions. Should things which must apply to a whole document be local or global (they probably should be ‘preamble only’ commands)? Are these three such things?

```
100 \newif \if@twoside \@twosidefalse
101 \newif \if@reversemargin \@reversemarginfalse
102 \newif \if@mparswitch \@mparswitchfalse
```

This counter has been imported from ‘multicol’.

```
103 \newcount \col@number
104 \col@number \@ne
```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

INTERNAL REGISTERS

```
105 \newcount\@topnum
106 \newdimen\@toproom
107 \newcount\@dbltopnum
108 \newdimen\@dbltoproom
109 \newcount\@botnum
110 \newdimen\@botroom
111 \newcount\@colnum
112 \newdimen\@textmin
113 \newdimen\@fpmin
114 \newdimen\@colht
115 \newdimen\@colroom
116 \newdimen\@pageht
117 \newdimen\@pagedp
118 \newdimen\@mparbottom \@mparbottom\z@
119 \newcount\@currtype
120 \newbox\@outputbox
121 \newbox\@leftcolumn
122 \newbox\@holdpg

123 \def\@thehead{\@oddhead} % initialization
124 \def\@thefoot{\@oddfoot}
```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\clearpage` The tests at the beginning are an experimental attempt to avoid a completely empty page after a `\twocolumn[...]`. This prevents the text from the argument vanishing into a float box, never to be seen again. We hope that it does not produce wrong formatting in other cases.

```
125 \def\clearpage{%
126   \ifvmode
127     \ifnum \@dbltopnum =\m@ne
128       \ifdim \pagetotal <\topskip
129         \hbox{}%
130       \fi
131     \fi
132   \fi
```

```

133 \newpage
134 \write\m@ne{}%
135 \vbox{}%
136 \penalty -\@Mi
137 }

\cleardoublepage

138 \def\cleardoublepage{\clearpage\if@twoside \ifodd\c@page\else
139 \hbox{}\newpage\if@twocolumn\hbox{}\newpage\fi\fi\fi}
140 </2ekernel>

\onecolumn

141 <*2ekernel | fltrace>
142 \def\onecolumn{%
143 \clearpage
144 \global\columnwidth\textwidth
145 \global\hsize\columnwidth
146 \global\linewidth\columnwidth
147 \global\@twocolumnfalse
148 \col@number \@ne
149 \@floatplacement}

\newpage The two checks at the beginning ensure that an item label or run-in section title
immediately before a \newpage get printed on the correct page, the one before
the page break.

All three tests are largely to make error processing more robust; that is why
they all reset the flags explicitly, even when it would appear that this would be
done by a \leavevmode.

150 </2ekernel | fltrace>
151 <latexrelease>\IncludeInRelease{2017/04/15}%
152 <latexrelease> \{\newpage\}{Check depth of page}%
153 <*2ekernel | latexrelease | fltrace>
154 \def \newpage {%
155 \if@noskipsec
156 \ifx \@nodocument\relax
157 \leavevmode
158 \global \@noskipsecfalse
159 \fi
160 \fi
161 \if@inlabel
162 \leavevmode
163 \global \@inlabelfalse
164 \fi
165 \if@nobreak \@nobreakfalse \everypar{}\fi
166 \par

The \vfil at the end of the macro before the break penalty will normally result
in the page being run short, even with \flushbottom in effect (in contrast to the
behavior of \pagebreak). However, if there is some explicit stretch on the page,
say, a \vfill, it has the undesired side-effect, that the last line will not align
at its baseline if it contains characters going below the baseline, as the value of
\prevdepth is no longer taken into account by TEX. So we back up by that amount
(or by \maxdepth if it is really huge), to mimic the normal behavior without the
\newpage.

```



```

167 \ifdim\prevdepth>\z@
168 \vskip -%
169 \ifdim\prevdepth>\maxdepth
170 \maxdepth
171 \else
172 \prevdepth
173 \fi
174 \fi
175 \vfil
176 \penalty -\@M}
177 </2ekernel | latexrelease | fltrace>
178 <latexrelease>\EndIncludeInRelease
179 <latexrelease>\IncludeInRelease{0000/00/00}%
180 <latexrelease> \newpage}{Check depth of page}%
181 <latexrelease>\def \newpage {%
182 <latexrelease> \if@noskipsec
183 <latexrelease> \ifx \@nodocument\relax
184 <latexrelease> \leavevmode
185 <latexrelease> \global \@noskipsecfalse
186 <latexrelease> \fi
187 <latexrelease> \fi
188 <latexrelease> \if@inlabel
189 <latexrelease> \leavevmode
190 <latexrelease> \global \@inlabelfalse
191 <latexrelease> \fi
192 <latexrelease> \if@nobreak \@nobreakfalse \everypar{}\fi
193 <latexrelease> \par
194 <latexrelease> \vfil
195 <latexrelease> \penalty -\@M}
196 <latexrelease>\EndIncludeInRelease
197 <*2ekernel | fltrace>

```

\@emptycol It may be better to use an invisible rule rather than an empty box here.

```
198 \def \@emptycol {\vbox{}\penalty -\@M}
```

\twocolumn There are several bug fixes to the two-column stuff here.

```

\@topnewpage 199 \def \twocolumn {%
200 \clearpage
201 \global\columnwidth\textwidth
202 \global\advance\columnwidth-\columnsep
203 \global\divide\columnwidth\tw@
204 \global\hsize\columnwidth
205 \global\linewidth\columnwidth
206 \global\@twocolumntrue
207 \global\@firstcolumntrue
208 \col@number \tw@

```

There is no reason to put a \@dblfloatplacement here since \@topnewpage ignores these settings. The \@floatplacement is needed in case this comes after some changes.

```

209 \@ifnextchar [\@topnewpage\@floatplacement
210 }

```

Note that here, getting a box from the freelist can assume success since this comes just after a \clearpage.

```

211 \long\def \@topnewpage [#1]{%
212   \@nodocument
213   \@next\@currbox\@freelist{}-{}%
214   \global \setbox\@currbox
215     \color@vbox
216     \normalcolor
217     \vbox {%
218       \hsize\textwidth
219       \@parboxrestore
220       \col@number \@ne
221       #1%
222       \vskip -\dbltextfloatsep
223     }%
224   \color@endbox

```

Added size test and warning message; perhaps we should use an error message.

```

225   \ifdim \ht\@currbox>\textheight
226     \ht\@currbox \textheight
227   \fi

```

This next line is not essential but it is more robust to make this value non-zero, in case of weird errors.

This next bit is what is needed from `\@addtodblcol`, plus some extra checks for error trapping.

```

228   \global \count\@currbox \tw@
229   \@tempdima -\ht\@currbox
230   \advance \@tempdima -\dbltextfloatsep
231   \global \advance \@colht \@tempdima
232   \ifx \@dbltoplist \@empty
233   \else
234     \@latexerr{Float(s) lost}\@ehb
235     \let \@dbltoplist \@empty
236   \fi
237   \@cons \@dbltoplist \@currbox

```

This setting of `\@dbltopnum` is used only to change the typesetting in `\@combinedblfloats`.

```

238   \global \@dbltopnum \m@ne
239   (*trace)
240     \fl@trace{dbltopnum set to -1 (= \the \@dbltopnum) (topnewpage)}%
241   (/trace)

```

At points such as this we need to check that there is still a minimal amount of room left on the page; this uses an arbitrary small value at present; but note that this value is larger than that used when checking that page is too full of normal floats.

If there is little room left we just force a page-break, OK? This involves producing two empty columns. The second empty column may be produced by `\output`, in which case an extra, misleading, warning will be generated, OK? (This happens only when there is too little room left on the page for any float.) Otherwise (i.e. if the size is such that it is allowed as a normal float) the extra `\@emptycol` will be invoked in the second column by the conditional code guarded by the `\if@firstcolumn` test.

I now think that the cut-off point here should be `3\baselineskip`, but we make it a bit less so that 3 lines of text will be allowed, OK?

Since this happens only when there is nothing on the page but the ‘top-box’, the empty box should not cause any problem other than some overfull box messages, which is not entirely misleading.

Here we need two page-ends since both columns need to be empty.

```

242 \ifdim \@colht<2.5\baselineskip
243 \latex@warning@no@line {Optional argument of \noexpand\twocolumn
244 too tall on page \thepage}%
245 \emptycol
246 \if@firstcolumn
247 \else
248 \emptycol
249 \fi
250 \else
251 \global \vsize \@colht
252 \global \@colroom \@colht
253 \floatplacement
254 \fi
255 }

```

`\output` This needs some small adjustments. We cannot guarantee that the float mechanism will interact correctly with this stuff, but that mechanism does not always work properly with footnotes already.

RmS 91/09/29:

added reset of `\par` to the output routine. This avoids problems when the output routine is called within a list where `\par` may be a no-op.

```

256 \output {%
257 \let \par \@par
258 \ifnum \outputpenalty<-\@M
259 \specialoutput
260 \else
261 \makecol
262 \opcol

```

Moved to `\@opcol: \@floatplacement`.

```

263 \@startcolumn

```

This loop could be replaced by an `\expandafter` tail recursion in `\@startcolumn`.

```

264 \@whilesw \if@fcolmade \fi
265 {%
266 (*trace)
267 \fl@trace{PAGE: float \if@twocolumn column \else page \fi
268 completed}%
269 (/trace)
270 \@opcol\@startcolumn}%
271 \fi
272 \ifnum \outputpenalty>-\@Miv

```

At points such as this we need to check that there is still a minimal amount of room left on the page; this uses an arbitrary small value at present. If there is little room left we just force a page-break, OK?

This bit is essential only if a float has just been processed so maybe it should be moved; but this is the natural place at which to set the `vsize` and a test would need to be done anyway. A check has been added to ensure that there really has been a change in the value of `\@colroom`.

Since this happens only when there is nothing on the page but floats, the empty box should not cause any problem other than some overfull box messages, which is not entirely misleading.

The twocolumn case does not need any extra code here since this is the `\output` itself; in the second column there will still not be enough room left so `\@emptycol` will be executed again when the OR is called by the page builder when it gets to the penalty inserted by the first execution. (The page-builder is never invoked whilst the OR is being executed since it builds a inner vlist; thus any conditional code for the two-column case within `\output` may not get executed with the correct value of `\if@firstcolumn`.)

```

273 \ifdim \@colroom<1.5\baselineskip
274 \ifdim \@colroom<\textheight
275 \latex@warning@no@line {Text page \thepage\space
276 contains only floats}%
277 \@emptycol
278 % \if@twocolumn
279 % \if@firstcolumn
280 % \else
281 % \@emptycol
282 % \fi
283 % \fi
284 \else
285 \global \vsize \@colroom
286 \fi
287 \else
288 \global \vsize \@colroom
289 \fi
290 \else
291 \global \vsize \maxdimen
292 \fi
293 }

```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

CHANGES TO `\@specialoutput`:

\* `\penalty\z@` changed to `\penalty\interlinepenalty` so `\samepage` works properly with figure and table environments.  
(Changed 23 Oct 86)

\* Definition of `\@specialoutput` changed 26 Feb 88 so `\@pageht` and `\@pagedp` aren't changed for a marginal note.  
(Change suggested by Chris Rowley.)

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

294 \gdef\@specialoutput{%
295 \ifnum \outputpenalty>-\@Mii
296 \doclearpage
297 \else
298 \ifnum \outputpenalty<-\@Miii
299 \ifnum \outputpenalty<-\@MM \deadcycles \z@ \fi
300 \global \setbox\@holdpg \vbox {\unvbox\@cclv}%
301 \else

```

Note that `\boxmaxdepth` should not be set here since we wish to record the natural depth of the holdpg box.

This is changed so as to not lose anything, such as writes and marks, which may get into box 255 and should be returned to the list. This should only happen when the first penalty in the mechanism is discarded and therefore `\@holdpg` should always be void in this case. This can happen because a penalty is discarded whenever there is no box on the list.

It was just: `\setbox\@tempboxa \box \ccclv`.

The last box which is removed is the box put there by the double-penalty mechanism. The `\unskip` then removes the `\topskip` which is put there since the box is the first on the page.

```
302      \global \setbox\@holdpg \vbox{%
303              \unvbox\@holdpg
304              \unvbox\ccclv
```

We must now remove the box added by the float mechanism and the `\topskip` glue therefore added above it by `TEX`.

```
305              \setbox\@tempboxa \lastbox
306              \unskip
307              }%
```

These two are needed as separate dimensions only by `\@addmarginpar`; for other purposes we put the whole size into `\@pageht` (see below).

```
308      \@pagedp \dp\@holdpg
309      \@pageht \ht\@holdpg
310      \unvbox \@holdpg
311      \@next\@currbox\@currlist{%
312      \ifnum \count\@currbox>\z@
```

Putting the whole size into `\@pageht` (see above).

```
313      \advance \@pageht \@pagedp
314      \ifvoid\footins \else
315      \advance \@pageht \ht\footins
316      \advance \@pageht \skip\footins
317      \advance \@pageht \dp\footins
318      \fi
319      \ifvbox \@kludgeins
```

We want to make the adjustment due to this insert only if the non-star form is used. The `*`-form will probably not work with floats, but maybe it still could make some adjustment here even so?

```
320      \ifdim \wd\@kludgeins=\z@
321      \advance \@pageht \ht\@kludgeins
322  (*trace)
323      \fl@trace {Extra size added: \the \ht\@kludgeins}%
324  (/trace)
325      \fi
326      \fi
```

This version puts the inserts back just before the additional material; it could be moved earlier, before unboxing the page-so-far. Neither is guaranteed not to put things on the wrong page. This version is similar to the original version.

```
327      \@reinserts
328      \@addtocurcol
329      \else
330      \@reinserts
331      \@addmarginpar
```

```

332         \fi
333     }\@latexbug

```

A 2e change: use `\addpenalty` instead of `\penalty` here. Some penalty is needed to create a potential break-point immediately after the reinserts (or the marginal). Otherwise there can be no possibility to break here and this can cause the reinserts or the marginal to appear on the next page (which is often incorrect). However, if the `nobreak` flag is true, a `\nobreak` must be correct.

```

334         \ifnum \outputpenalty<\z@
335             \if@nobreak
336                 \nobreak
337             \else
338                 \addpenalty \interlinepenalty
339             \fi
340         \fi
341     \fi
342 \fi
343 }
344 \if2ekernel | fltrace)

```

`\@testwrongwidth` Test if the float box has the wrong width when trying to place it into some area.  
`\f@depth` (Actually the test is for a conventional depth setting rather than for the width of the float. For that reason the box depth was explicitly tailored when the float was created).

```

345 \if@latexrelease\IncludeInRelease{2015/01/01}%
346 \if@latexrelease\@testwrongwidth{float order in 2-column}%
347 \if2ekernel | latexrelease | fltrace)

348 \def\@testwrongwidth #1{%
349     \ifdim\dp#1=\f@depth
350     (*trace)
351         \fl@trace{\string#1
352             \ifdim\f@depth=\z@ single \else double \fi
353             column float -- ok}%
354     \iftraced
355     \else
356         \global\@testtrue
357     (*trace)
358         \fl@trace{\string#1
359             \ifdim\f@depth=\z@ double \else single \fi
360             column float -- wrong}%
361     \iftraced
362     \fi}%

```

Normally looking for single column floats, which have zero depth.

```

363 \let\f@depth\z@
364 \if2ekernel | latexrelease | fltrace)
365 \if@latexrelease\EndIncludeInRelease
366 \if@latexrelease\IncludeInRelease{0000/00/00}%
367 \if@latexrelease\@testwrongwidth{float order in 2-column}%
368 \if@latexrelease\let\@testwrongwidth\@undefined
369 \if@latexrelease\let\f@depth\@undefined
370 \if@latexrelease\EndIncludeInRelease

```

`\@doclearpage` This is a very much an emergency action, just dumping everything: footnotes first then floats. A more sophisticated version is needed; but even more urgent is a bug-free version (see, for example, pr/3528).

Also, it puts any left-over non-boxes (writes, specials, etc.) back after any float pages created: this is a very bad bug since, for example, a kludge insert will be in quite the wrong place and, worse, be irremovable and uncancelable.

All the remaining changes are replacing the double column defer list or inserting the extra test `\@testwrongwidth{<box>}` at suitable places. That is at places where a box is taken off the deferlist.

```

371 \latexrelease\IncludeInRelease{2015/01/01}{\@doclearpage}%
372 \latexrelease\float order in 2-column}%
373 \*2ekernel|latexrelease
374 \def \@doclearpage {%
375     \ifvoid\footins

376     \ifvbox\@kludgeins
377         {\setbox \@tempboxa \box \@kludgeins}%
378 (*trace)
379         \fl@trace {kludgeins box made void}%
380 /trace)
381     \fi
382     \setbox\@tempboxa\vsplit\@cclv to\z@ \unvbox\@tempboxa
383     \setbox\@tempboxa\box\@cclv
384     \xdef\@deferlist{\@toplist\@botlist\@deferlist}%
385     \global \let \@toplist \@empty
386     \global \let \@botlist \@empty
387     \global \@colroom \@colht
388     \ifx \@currlist\@empty
389     \else
390         \@latexerr{Float(s) lost}\@ehb
391         \global \let \@currlist \@empty
392     \fi
393     \@makefcolumn\@deferlist
394     \@whiles\if@fcolmade \fi{\@opcol\@makefcolumn\@deferlist}%
395     \if@twocolumn
396         \if@firstcolumn
397             \xdef\@deferlist{\@dbltoplist\@deferlist}%
398             \global \let \@dbltoplist \@empty
399             \global \@colht \textheight
400             \begingroup
401                 \@dblfloatplacement
402                 \@makefcolumn\@deferlist
403                 \@whiles\if@fcolmade \fi{\@outputpage
404                     \@makefcolumn\@deferlist}%
405             \endgroup
406         \else
407             \vbox{}\clearpage
408         \fi
409     \fi

```

the next line is needed to avoid losing floats in certain circumstances a single call to the original `\doclearpage` will now no longer output all floats.

```

410     \ifx\@deferlist\@empty \else\clearpage \fi
411     \else
412     \setbox\@cclv\vbox{\box\@cclv\vfil}%
413     \@makecol\@opcol
414     \clearpage
415     \fi
416 }%
417 //2kernel | latexrelease>
418 <latexrelease>\EndIncludeInRelease
419 <latexrelease>\IncludeInRelease{0000/00/00}{\@docclearpage}%
420 <latexrelease>                                {float order in 2-column}%
421 <latexrelease>\def \@docclearpage {%
422 <latexrelease>    \ifvoid\footins
We empty any left over kludge insert box here; this is a temporary fix. It should
perhaps be applied to one page of cleared floats, but who cares? The whole of this
stuff needs completely redoing for many such reasons.
423 <latexrelease>    \ifvbox\@kludgeins
424 <latexrelease>        {\setbox \@tempboxa \box \@kludgeins}%
425 <*trace>
426 <latexrelease>        \fl@trace {kludgeins box made void}%
427 </trace>
428 <latexrelease>    \fi
429 <latexrelease>    \setbox\@tempboxa\vsplit\@cclv to\z@ \unvbox\@tempboxa
430 <latexrelease>    \setbox\@tempboxa\box\@cclv
431 <latexrelease>    \xdef\@deferlist{\@toplist\@botlist\@deferlist}%

432 <latexrelease>    \global \let \@toplist \@empty
433 <latexrelease>    \global \let \@botlist \@empty
434 <latexrelease>    \global \colroom \colht
435 <latexrelease>    \ifx \@currlist\@empty
436 <latexrelease>    \else
437 <latexrelease>        \@latexerr{Float(s) lost}\@ehb

438 <latexrelease>    \global \let \@currlist \@empty
439 <latexrelease>    \fi
440 <latexrelease>    \@makefcolumn\@deferlist
441 <latexrelease>    \@whilesw\if@fcolmade \fi
442 <latexrelease>        {\@opcol\@makefcolumn\@deferlist}%
443 <latexrelease>    \if@twocolumn
444 <latexrelease>        \if@firstcolumn
445 <latexrelease>            \xdef\@dbldeferlist{\@dbltoplist\@dbldeferlist}%

446 <latexrelease>    \global \let \@dbltoplist \@empty
447 <latexrelease>    \global \@colht \textheight
448 <latexrelease>    \begingroup
449 <latexrelease>        \@dblfloatplacement
450 <latexrelease>        \@makefcolumn\@dbldeferlist
451 <latexrelease>        \@whilesw\if@fcolmade \fi
452 <latexrelease>            {\@outputpage\@makefcolumn\@dbldeferlist}%
453 <latexrelease>    \endgroup
454 <latexrelease>    \else
455 <latexrelease>        \vbox{}\clearpage
456 <latexrelease>    \fi
457 <latexrelease>    \fi

```



```

458 \latexrelease\else
459 \latexrelease\setbox\@cclv\vbox{\box\@cclv\vfil}%
460 \latexrelease\@makecol\@opcol
461 \latexrelease\clearpage
462 \latexrelease\fi
463 \latexrelease}%
464 \latexrelease\EndIncludeInRelease

```

`\@opcol` Several changes in detail here.

```

465 (*2ekernel|fltrace)
466 \def \@opcol {%
467   \if@twocolumn
468     \@outputdblcol
469   \else
470     \@outputpage
471 (*trace)
472   \fl@trace{PAGE: one column (float? see above) page completed}%
473 /trace)

```

Not needed since it comes after `\@outputpage`:

```

474 % \global\@colht\textheight
475 \fi

```

These do not need to be done every time `\@opcol` is used: they should be grouped together since they all need to be done at the end of the non-special output routine, or at the end of a clearpage one.

```

476 \global\@mparbottom\z@ \global\@textfloatsheight\z@
477 \floatplacement
478 }
479 /2ekernel|fltrace)

```

`\@makecol` We must rewrite this macro to allow for variations in page-makeup required by changes in page-length.

This uses a different macro if a special-length column is being produced.

```

480 (*2ekernel)
481 \gdef \@makecol {%
482   \ifvoid\footins
483     \setbox\@outputbox\box\@cclv
484   \else
485     \setbox\@outputbox\vbox{%

```

This `\boxmaxdepth` setting is to ensure that deep footnotes do not overwrite the footer (on account of the negative skip added later): it should use `\@maxdepth` otherwise the change is pointless when there are footnotes.

But see also its use when combining floats.

```

486     \boxmaxdepth \@maxdepth

487 %     \@tempdima\dp\@cclv
488     \unvbox \@cclv
489 %     \vskip-\@tempdima
490     \vskip \skip\footins

491     \color@begingroup
492     \normalcolor

```

```

493         \footnoterule
494         \unvbox \footins
495         \color@endgroup
496     }%
497 \fi

```

The h floats have now been finally committed to this page so we can reset their list. The top and bottom floats are then added to the page.

```

498     \let\@elt\relax
499     \xdef\@freelist{\@freelist\@midlist}%

500 \global \let \@midlist \@empty
501 \@combinefloats

```

The variations start here in case \enlargethispage has been used.

```

502 \ifvbox\@kludgeins
503     \@makespecialcolbox
504 \else

```

This extra reboxing is only needed to add the \@texttop and \@textbottom but this could be done earlier, when the floats are added.

The \boxmaxdepth resetting here will have no effect unless \@textbottom ends with a box or rule. So is this (or possibly \@maxdepth) the correct value?

The \vskip -\dimen@ ensures that the visible depth of the box does not affect the placement of anything on the page. Thus very deep pages will overprint the footer; but these should have been prevented by suitable settings of the maxdepths at appropriate times.

If \@textbottom ends with a box or rule of non-zero depth then this skip adjustment should be done again after it.

I think that the final boxing of the main text page could have a common ending which may make it simpler to see what is going on.

This needs further investigation, especially in the ‘special case’.

Also, the \boxmaxdepth setting here affects what happens within \@texttop and \@textbottom, should it? Is it needed at all?

RmS 91/10/22: Replaced \dimen128 by \dimen@.

```

505     \setbox\@outputbox \vbox to\@colht {%
506 %         \boxmaxdepth \maxdepth           %??
507         \@texttop
508         \dimen@ \dp\@outputbox
509         \unvbox \@outputbox
510         \vskip -\dimen@
511         \@textbottom
512     }%
513 \fi
514 \global \maxdepth \@maxdepth
515 }

```

**\@reinserts** This is the code which reinserts the inserts. It puts them all in one place; this can make some of them come out on the wrong page. It has been put into a separate macro to expedite experimentation.

```

516 \gdef \@reinserts{%
517     \ifvoid\footins\else\insert\footins{\unvbox\footins}\fi
518     \ifvbox\@kludgeins\insert\@kludgeins

```

```

519             {\unvbox\@kludgeins}\fi
520 }
521 \end{2kernel}

```

\@makespecialcolbox This implements certain variations in page-makeup.

```

522 (*2kernel | fltrace)
523 \gdef \@makespecialcolbox {%
524 (*trace)
525   \fl@trace{Kludgeins ht \the\ht\@kludgeins\space
526             dp \the\dp\@kludgeins\space
527             wd \the\wd\@kludgeins}%
528 \end{trace}

```

First we find the natural height of the column.

See above for discussion of what is happening here.

This needs further investigation, especially in this ‘special case’.

```

529   \setbox\@outputbox \vbox {%
530     \texttop
531     \dimen@ \dp\@outputbox
532     \unvbox\@outputbox
533     \vskip-\dimen@
534   }%
535   \@tempdima \@colht
536   \ifdim \wd\@kludgeins>\z@

```

Note that in this case (the \*-version), the height of the \@kludgeins box is not used since its value is somewhat arbitrary: it need only be big enough to ensure that the page-break is not taken prematurely.

Here we calculate how much vertical space needs to be added in order to enable the column to fit into a box of size \@colht using the best information we have about the amount of shrink available (another thing which is known internally about a box, but cannot be accessed at the T<sub>E</sub>X level!).

This needs T<sub>E</sub>X3 otherwise \pageshrink is zero anyway; it may not be exactly the figure we wish as it is the total available from the all the material collected before the page-break decision is made. It will, we think, always be an overestimate of the actual shrink in the box; therefore this should always force the shortest possible column with the possibility of an overfull box.

This should work for both the flush- and ragged-bottom setting since it makes the contents no smaller than the size (\@colht) of the box into which they are put.

Their should perhaps be an upper limit, of 0pt?, on the extra space added to force shrinking.

See above for a discussion of the \boxmaxdepth setting here.

```

537   \advance \@tempdima -\ht\@outputbox
538   \advance \@tempdima \pageshrink
539 (*trace)
540   \fl@trace {Natural ht of col: \the \ht\@outputbox}%
541   \fl@trace {\string \@colht: \the \@colht}%
542   \fl@trace {Pageshrink added: \the \pageshrink}%
543   \fl@trace {Hence, space added: \the \@tempdima}%
544 \end{trace}
545   \setbox\@outputbox \vbox to \@colht {%
546 %       \boxmaxdepth \maxdepth

```

```

547      \unvbox\@outputbox
548      \vskip \@tempdima
549      \@textbottom
550      }%

```

For the unstarred version, the final size of the page is precisely specified. Therefore, at least for the flush-bottom case, we need to ensure that, visually, it has this size exactly.

Thus we calculate this size and set the material in a box of this size, which is then put into a box of size \@colht with \vss at the bottom.

```

551      \else
552      \advance \@tempdima -\ht\@kludgeins
553      (*trace)
554      \fl@trace {Natural ht of col: \the \ht\@outputbox}%
555      \fl@trace {\string \@colht: \the \@colht}%
556      \fl@trace {Extra size added: -\the \ht \@kludgeins}%
557      \fl@trace {Hence, height of inner box: \the \@tempdima}%
558      \fl@trace {Max? pageshrink available: \the \pageshrink}%
559      (/trace)

```

This type of final packaging could be done always; this may simplify all of this page-makeup.

It is not necessary to set \boxmaxdepth here since the \@outputbox ends with glue.

```

560      \setbox \@outputbox \vbox to \@colht {%
561      \vbox to \@tempdima {%
562      \unvbox\@outputbox
563      \@textbottom}%
564      \vss}%
565      \fi

```

Finally we need to explicitly make the insert box void.

```

566      {\setbox \@tempboxa \box \@kludgeins}%
567      (*trace)
568      \fl@trace {kludgeins box made void}%
569      (/trace)
570      }
571      (/2ekernel | fltrace)

```

\@texttop These do nothing as a default.

```

\@textbottom 572 (*2ekernel)
573 \let \@texttop \relax
574 \let \@textbottom \relax

```

\@resetactivechars RmS 93/09/06: added hook to protect against certain active characters in the output routine. Default checks are for active space and end-of-line.

```

\@activechar@info
575 \def\@activechar@info #1{%
576     \@latex@info@no@line {Active #1 character found while
577                           output routine is active
578                           \MessageBreak
579                           This may be a bug in a package file
580                           you are using}%
581 }

```

Do not put any spaces in this next bit!

```
582 \begingroup
583 \obeylines\obeyspaces%
584 \catcode'\'\active%
585 \gdef\@resetactivechars{%
586 \def^^M{\@activechar@info{EOL}\space}%
587 \def {\@activechar@info{space}\space}%
588 \let'\active@math@prime}%
589 \endgroup
```

`\@outputpage` The `\color@hbox` hooks here are used to avoid putting just a colour special into an otherwise empty box (in a header or footer). These boxes are often set to be completely empty and so adding a special produces a very underfull box message.

`\@shipoutsetup` There has been extensive tidying up of the old code here; including the removal of a level of grouping.

`\@writsetup` The setting of `\protect` immediately before the `\shipout` is needed so that protected commands within `\writes` are handled correctly.

Within `shipout`'s vbox it is reset to its default value, `\relax`.

Resetting it to its default value after the `shipout` has been completed (and the contents of the `writes` have been expanded) must be done by use of `\aftergroup`. This is because it must have the value `\relax` before macros coming from other uses of `\aftergroup` within this box are expanded.

Putting this into the `\aftergroup` token list does not affect the definition used in expanding the `\writes` because the `aftergroup` token list is only constructed when popping the save-stack, it is not expanded until after the `shipout` is completed.

Question: should things from an `\aftergroup` within the shipped out box be executed in the environment set up for the `writes`, or after it finishes?

A lot of this code has been in-lined to prevent mis-use of internal commands as hooks.

```
590 \</2ekernel>
591 \<latexrelease>\IncludeInRelease{2017/04/15}%
592 \<latexrelease> {\@outputpage}{Reset language for hyphenation}%
593 \<*2ekernel|latexrelease>
594 \def\@outputpage{%
```

The `\endgroup` is put in by `\aftergroup`.

```
595 \begingroup
```

Now all the set-up stuff has been in-lined for Frank.

First the stuff for the `writes`.

From here ... was in the command `\@writsetup`.

```
596 \let \protect \noexpand
```

RmS 93/08/19: Redefined accents to allow changes in font encoding; but exactly why was this needed?

Reset `\language` to the value current at `\begin{document}`. In particular this ensures that a pagebreak in `verbatim` does not prevent hyphenation in the page head.

```
597 \language\document@default@language
```

The `\catcode'\ = 10` was removed as it was considered useless (presumably because nothing gets tokenised during `shipout`).

This was put in as some error produced active spaces in a mark, I think.  
Why was the hyphen reset?

```
598 \resetactivechars
```

If a page break happens between the start of a list and its first item the `@newlist` will be true and this will mess up any list that is used in the header or footer of the page. So we have to reset that flag.

```
599 \global\let\@if@newlist\if@newlist
600 \global\@newlistfalse
```

This next hook replaces the following:

```
\let\-\@dischyph
\let'\@acci\let'\@accii\let\=\@acciii
\let\\@normalcr
\let\par\@par %% 15 Sep 87 (this was once inside the box)
```

and it does more than they did; in particular it sets:

```
\parindent\z@
\parskip\z@skip
\everypar{}\%
\leftskip\z@skip
\rightskip\z@skip
\parfillskip\@flushglue
\lineskip\normallineskip
\baselineskip\normalbaselineskip
\sloppy
```

```
601 \@parboxrestore
```

... to here was in the command `\@writesetup`.

```
602 \shipout \vbox{%
603   \set@typeset@protect
604   \aftergroup \endgroup
```

Correct? or just restore by ending the group?

```
605   \aftergroup \set@typeset@protect
```

This first bit has been moved inside the shipped out box.

Now the setup inside the shipped out box; this should contain all the stuff that could only affect typesetting; other stuff may need to be reset for the writes also.

From here ... was in the command `\@shipoutsetup`.

```
606 \if@specialpage
607   \global\@specialpagefalse\@nameuse{ps@\@specialstyle}%
608 \fi
609 \if@twoside
610   \ifodd\count\z@ \let\@thehead\@oddhead \let\@thefoot\@oddfoot
611     \let\@themargin\oddsidemargin
612   \else \let\@thehead\@evenhead
613     \let\@thefoot\@evenfoot \let\@themargin\evensidemargin
614   \fi
615 \fi
```

The rest was always inside the box.

RmS 91/08/15: aded this line:

```
616 \reset@font
```

RmS 93/08/06 Added `\lineskiplimit=0pt` to guard against it being nonzero:  
e.g. by `\offinterlineskip` being in effect.

There are probably lots of other things that may need resetting.

```
617 \normalsize
```

Reset the space factors.

```
618 \normalsfcodes
```

Reset these here (previously reset separately for head and foot)

```
619 \let\label\@gobble
```

```
620 \let\index\@gobble
```

```
621 \let\glossary\@gobble
```

```
622 \baselineskip\z@skip \lineskip\z@skip \lineskiplimit\z@
```

... to here was in the command `\@shipoutsetup`.

```
623 \@beginndvi
```

```
624 \vskip \topmargin
```

```
625 \moveright\@themargin \vbox {%
```

```
626 \setbox\@tempboxa \vbox to\headheight{%
```

```
627 \vfil
```

```
628 \color@hbox
```

```
629 \normalcolor
```

```
630 \hb@xt@\textwidth{\@thehead}%
```

```
631 \color@endbox
```

22 Feb 87

```
632 }%
```

```
633 \dp\@tempboxa \z@
```

```
634 \box\@tempboxa
```

```
635 \vskip \headsep
```

```
636 \box\@outputbox
```

```
637 \baselineskip \footskip
```

```
638 \color@hbox
```

```
639 \normalcolor
```

```
640 \hb@xt@\textwidth{\@thefoot}%
```

```
641 \color@endbox
```

```
642 }%
```

```
643 }%
```

`\endgroup` now inserted by `\aftergroup`

Restore `\if@newlist`

```
644 \global\let\if@newlist\@if@newlist
```

```
645 \global \colht \textheight
```

```
646 \stepcounter{page}%
```

It is now clear that this does something useful, thanks to Piet van Oostrum. It is needed because a float page is made without using TeX's page-builder; thus the output routine is never called so the marks are not updated.

```
647 \let\firstmark\botmark
```

```
648 }
```

```

649 </2ekernel | latexrelease>
650 <latexrelease>\EndIncludeInRelease
651 <latexrelease>\IncludeInRelease{0000/00/00}%
652 <latexrelease> {\@outputpage}{Reset language for hyphenation}%
653 <latexrelease>\def\@outputpage{%
654 <latexrelease>\begingroup
655 <latexrelease> \let \protect \noexpand
656 <latexrelease> \@resetactivechars
657 <latexrelease> \global\let\@@if@newlist@if@newlist
658 <latexrelease> \global\@newlistfalse
659 <latexrelease> \@parboxrestore
660 <latexrelease> \shipout \vbox{%
661 <latexrelease> \set@typeset@protect
662 <latexrelease> \aftergroup \endgroup
663 <latexrelease> \aftergroup \set@typeset@protect
664 <latexrelease> \if@specialpage
665 <latexrelease> \global\@specialpagefalse\@nameuse{ps@\@specialstyle}%
666 <latexrelease> \fi
667 <latexrelease> \if@twoside
668 <latexrelease> \ifodd\count\z@
669 <latexrelease> \let\@thehead\@oddhead \let\@thefoot\@oddfoot
670 <latexrelease> \let\@themargin\oddsidemargin
671 <latexrelease> \else \let\@thehead\@evenhead
672 <latexrelease> \let\@thefoot\@evenfoot \let\@themargin\evensidemargin
673 <latexrelease> \fi
674 <latexrelease> \fi
675 <latexrelease> \reset@font
676 <latexrelease> \normalsize
677 <latexrelease> \normalsfcodes
678 <latexrelease> \let\label\@gobble
679 <latexrelease> \let\index\@gobble
680 <latexrelease> \let\glossary\@gobble
681 <latexrelease> \baselineskip\z@skip \lineskip\z@skip \lineskiplimit\z@
682 <latexrelease> \@beginndvi
683 <latexrelease> \vskip \topmargin
684 <latexrelease> \moveright\@themargin \vbox {%
685 <latexrelease> \setbox\@tempboxa \vbox to\headheight{%
686 <latexrelease> \vfil
687 <latexrelease> \color@hbox
688 <latexrelease> \normalcolor
689 <latexrelease> \hb@xt@\textwidth{\@thehead}%
690 <latexrelease> \color@endbox
691 <latexrelease> }%
692 <latexrelease> \dp\@tempboxa \z@
693 <latexrelease> \box\@tempboxa
694 <latexrelease> \vskip \headsep
695 <latexrelease> \box\@outputbox
696 <latexrelease> \baselineskip \footskip
697 <latexrelease> \color@hbox
698 <latexrelease> \normalcolor
699 <latexrelease> \hb@xt@\textwidth{\@thefoot}%
700 <latexrelease> \color@endbox
701 <latexrelease> }%
702 <latexrelease> }%

```



```

703 <latexrelease> \global\let@if@newlist\@if@newlist
704 <latexrelease> \global \colht \textheight
705 <latexrelease> \stepcounter{page}%
706 <latexrelease> \let\firstmark\botmark
707 <latexrelease>}
708 <latexrelease>\EndIncludeInRelease
709 <*2kernel>

```

**\@beginndvi** This unboxes stuff that must appear before anything else in the .dvi file, then returns that box register to the free list and cancels itself.

The stuff in the box should not add any typeset material to the page.

```

710 \def \@beginndvi{%
711   \unvbox \@beginndvibox
712   \global\let \@beginndvi \@empty
713 }

```

**\@combinefloats** The `\boxmaxdepth` setting here was not made local to a box so was dangerous. It is needed only within the box made by `\@cflt` (and not normally even there), so **\@cflt** it has been moved there; this also agrees with the original pseudocode.

```

714 \def \@combinefloats {%
715 %   \boxmaxdepth \maxdepth
716   \ifx \@toplist\@empty \else \@cflt \fi
717   \ifx \@botlist\@empty \else \@cflb \fi
718 }

719 \def \@cflt{%
720   \let \@elt \@comflelt
721   \setbox\@tempboxa \vbox{%
722     \@toplist
723     \setbox\@outputbox \vbox{%
724       \boxmaxdepth \maxdepth
725       \unvbox\@tempboxa
726       \vskip -\floatsep
727       \topfigrule
728       \vskip \textfloatsep
729       \unvbox\@outputbox
730     }%
731     \let\@elt\relax
732     \xdef\@freelist{\@freelist\@toplist}%
733     \global\let\@toplist\@empty
734 }

735 \def \@cflb {%
736   \let\@elt\@comflelt
737   \setbox\@tempboxa \vbox{%
738     \@botlist
739     \setbox\@outputbox \vbox{%
740       \unvbox\@outputbox
741       \vskip \textfloatsep
742       \botfigrule
743       \unvbox\@tempboxa
744       \vskip -\floatsep
745     }%
746     \let\@elt\relax

```

```

747 \xdef\@freelist{\@freelist\@botlist}%
748 \global \let \@botlist\@empty
749 }

```

```

\@comflelt
\@comdblfilelt
\@combinedblfloats
750 \def\@comflelt#1{\setbox\@tempboxa
751 \vbox{\unvbox\@tempboxa\box #1\vskip\floatsep}}
752 \def\@comdblfilelt#1{\setbox\@tempboxa
753 \vbox{\unvbox\@tempboxa\box #1\vskip\dblfloatsep}}
754 \def \@combinedblfloats{%
755 \ifx \@dbltoplist \@empty
756 \else
757 \setbox\@tempboxa \vbox{}%
758 \let \@elt \@comdblfilelt
759 \@dbltoplist
760 \let \@elt \relax
761 \xdef \@freelist {\@freelist\@dbltoplist}%
762 \global\let \@dbltoplist \@empty
763 \setbox\@outputbox \vbox to\textheight

```

The setting of `\boxmaxdepth` here has no effect since the `\@outputbox` should already have depth zero. Even so, it would have no effect on the layout of the page.

```

764 {\boxmaxdepth\maxdepth %% probably not needed, CAR
765 \unvbox\@tempboxa\vskip-\dblfloatsep

```

Here we need different typesetting if the top float comes from `\@topnewpage`.

```

766 \ifnum \@dbltopnum>\m@ne
767 \dblfigrule
768 \fi
769 \vskip \dbltextfloatsep

```

If pdf links are present in the galley and those links get broken across pages they have to end up being on the same level of boxing (even if not actually in the same structure) due to some engine restrictions in pdfTeX and LuaTeX. We therefore unbox `\@outputbox` here (which only contains a single `\hbox`) so that this case has the same boxing level as a normal twocolumn page without top floats.

```

770 \unvbox\@outputbox
771 }%
772 \fi
773 }
774 \end{kernel}

```

`\@startcolumn` We could combine (most of) these two into `\@startcol <list>`. Note that `\@xstartcol` was only used once (i.e. in `\@startcolumn`); it has therefore been removed. This is not quite as efficient but it now has the same structure as `\@startdblcolumn`.

The empty-list test has been moved to `\@tryfcolumn`.

```

775 \if*2ekernel|ftrace)
776 \def \@startcolumn {%
777 \global \@colroom \@colht
778 \@tryfcolumn \@deferlist
779 \if@fcolmade

```

```

780 <*trace>
781   \fl@trace{PAGE: float \if@twocolumn column \else page \fi
782             completed}%
783 </trace>
784 \else

785   \begingroup
786     \let \reserved@b \@deferlist
787     \global \let \@deferlist \@empty
788     \let \@elt \@scolelt
789     \reserved@b
790   \endgroup
791 \fi
792 }

```

This one does not need to set \@colht.

```

793 </2ekernel | fltrace>
794 <latexrelease | fltrace>\IncludeInRelease{2015/01/01}%
795 <latexrelease | fltrace> {\@startdblcolumn}{float order in 2-column}%
796 <*2ekernel | latexrelease | fltrace>
797 \def \@startdblcolumn {%
798   \@tryfcolumn \@deferlist
799   \if@fcolmade
800 <fltrace>   \fl@trace{PAGE: double float page completed}%
801 \else
802   \begingroup
803     \let \reserved@b \@deferlist
804     \global \let \@deferlist \@empty
805     \let \@elt \@sdblcolelt
806     \reserved@b
807   \endgroup
808 \fi
809 }%
810 </2ekernel | latexrelease | fltrace>
811 <latexrelease | fltrace>\EndIncludeInRelease
812 <latexrelease | fltrace>\IncludeInRelease{0000/00/00}%
813 <latexrelease | fltrace> {\@startdblcolumn}{float order in 2-column}%
814 <latexrelease | fltrace>\def \@startdblcolumn {%

```

Not needed since this always comes after \@outputpage:

```

815 <latexrelease | fltrace>% \global \@colht \textheight
816 <latexrelease | fltrace> \@tryfcolumn \@dbldeferlist
817 <latexrelease | fltrace> \if@fcolmade
818 <*trace>
819 <latexrelease | fltrace>   \fl@trace{PAGE: double float page completed}%
820 </trace>
821 <latexrelease | fltrace> \else

822 <latexrelease | fltrace>   \begingroup
823 <latexrelease | fltrace>     \let \reserved@b \@dbldeferlist
824 <latexrelease | fltrace>     \global \let \@dbldeferlist \@empty
825 <latexrelease | fltrace>     \let \@elt \@sdblcolelt
826 <latexrelease | fltrace>     \reserved@b
827 <latexrelease | fltrace>   \endgroup
828 <latexrelease | fltrace> \fi

```

```

829 \latexrelease | fltrace\}%
830 \latexrelease | fltrace\EndIncludeInRelease
831 \*2ekernel | fltrace)

\@tryfccolumn Now tests if its list is empty before any further exertion.

832 \def \@tryfccolumn #1{%
833   \global \@fcolmadefalse
834   \ifx #1\@empty
835     \else
836     \*trace)
837     \fl@trace{PAGE: try float \if@twocolumn column/page\else page\fi
838             ---\string #1}%
839     \fl@trace{----- \string #1: #1}%
840 \</trace)

841   \xdef\@trylist{#1}%
842   \global \let \@failedlist \@empty
843   \begingroup
844     \let \@elt \@xtryfc \@trylist
845   \endgroup
846   \if@fcolmade
847     \@vtryfc #1%
848   \fi
849 \fi
850 }
851 \</2ekernel | fltrace)

852 \*2ekernel)

\@scolelt
853 \def\@scolelt#1{\def\@currbox{#1}\@addtonextcol}

\@sdblcolelt
854 \def\@sdblcolelt#1{\def\@currbox{#1}\@addtodblcol}

\@vtryfc
855 \def\@vtryfc #1{%
856   \global\setbox\@outputbox\vbox{}%
857   \let\@elt\@wtryfc
858   \@flsucceed
859   \global\setbox\@outputbox \vbox to\@colht{%
860     \vskip \@fptop
861     \vskip -\@fpsep
862     \unvbox \@outputbox
863     \vskip \@fpbot}%
864   \let\@elt\relax
865   \xdef #1{\@failedlist\@flfail}%
866   \xdef\@freelist{\@freelist\@flsucceed}}

\@wtryfc
867 \def\@wtryfc #1{%
868   \global\setbox\@outputbox\vbox{%
869     \unvbox\@outputbox
870     \vskip\@fpsep
871     \box #1}}

```

\@xtryfc

```
872 </2ekernel>
873 <latexrelease>\IncludeInRelease{2015/01/01}{\@xtryfc}%
874 <latexrelease>                                     {float order in 2-column}%
875 <*2ekernel|latexrelease>
876 \def\@xtryfc #1{%
877   \@next\reserved@a\@trylist{}{}%
878   \@currtype \count #1%
879   \divide\@currtype\@xxxii
880   \multiply\@currtype\@xxxii
881   \@bitor \@currtype \@failedlist
882   \@testfp #1%
883   \@testwrongwidth #1%
884   \ifdim \ht #1>\@colht
885     \@testtrue
886   \fi
887   \if@test
888     \@cons\@failedlist #1%
889   \else
890     \@ytryfc #1%
891   \fi}%
892 </2ekernel|latexrelease>
893 <latexrelease>\EndIncludeInRelease
894 <latexrelease>\IncludeInRelease{0000/00/00}{\@xtryfc}%
895 <latexrelease>                                     {float order in 2-column}%
896 <latexrelease>\def\@xtryfc #1{%
897 <latexrelease>   \@next\reserved@a\@trylist{}{}%
898 <latexrelease>   \@currtype \count #1%
899 <latexrelease>   \divide\@currtype\@xxxii
900 <latexrelease>   \multiply\@currtype\@xxxii
901 <latexrelease>   \@bitor \@currtype \@failedlist
902 <latexrelease>   \@testfp #1%
903 <latexrelease>   \ifdim \ht #1>\@colht
904 <latexrelease>     \@testtrue
905 <latexrelease>   \fi
906 <latexrelease>   \if@test
907 <latexrelease>     \@cons\@failedlist #1%
908 <latexrelease>   \else
909 <latexrelease>     \@ytryfc #1%
910 <latexrelease>   \fi}%
911 <latexrelease>\EndIncludeInRelease
912 <*2ekernel>
```

\@ytryfc

```
913 \def\@ytryfc #1{%
914   \begingroup
915   \gdef\@flsucceed{\@elt #1}%
916   \global\let\@flfail\@empty
917   \@tempdima\ht #1%
918   \let\@elt\@ztryfc
919   \@trylist
920   \ifdim \@tempdima >\@fpmin
921     \global\@fcolmadetrue
```

```

922 \else
923 \cons\@failedlist #1%
924 \fi
925 \endgroup
926 \if@fcolmade
927 \let\@elt\@gobble
928 \fi}

\@ztryfc
929 (/2ekernel)
930 \latexrelease\IncludeInRelease{2015/01/01}\@ztryfc}%
931 \latexrelease\float order in 2-column}%
932 (*2ekernel| latexrelease)
933 \def\@ztryfc #1{%
934 \tempcnta\count #1%
935 \divide\tempcnta\xxxii
936 \multiply\tempcnta\@xxxii
937 \bitor \tempcnta {\@failedlist \flfail}%
938 \testfp #1%
939 \testwrongwidth #1%
940 \tempdimb\tempdima
941 \advance\tempdimb\ht #1%
942 \advance\tempdimb\fpsep
943 \ifdim \tempdimb >\colht
944 \testtrue
945 \fi
946 \if@test
947 \cons\flfail #1%
948 \else
949 \cons\flsucceed #1%
950 \tempdima\tempdimb
951 \fi}%
952 (/2ekernel| latexrelease)
953 \latexrelease\EndIncludeInRelease
954 \latexrelease\IncludeInRelease{0000/00/00}\@ztryfc}%
955 \latexrelease\float order in 2-column}%
956 \latexrelease\def\@ztryfc #1{%
957 \latexrelease\tempcnta \count#1%
958 \latexrelease\divide\tempcnta\@xxxii
959 \latexrelease\multiply\tempcnta\@xxxii
960 \latexrelease\bitor \tempcnta {\@failedlist \flfail}%
961 \latexrelease\testfp #1%
962 \latexrelease\tempdimb\tempdima
963 \latexrelease\advance\tempdimb \ht#1%
964 \latexrelease\advance\tempdimb\fpsep
965 \latexrelease\ifdim \tempdimb >\colht
966 \latexrelease\testtrue
967 \latexrelease\fi
968 \latexrelease\if@test
969 \latexrelease\cons\flfail #1%
970 \latexrelease\else
971 \latexrelease\cons\flsucceed #1%

```

```

972 \latexrelease) \@tempdima\@tempdimb
973 \latexrelease) \fi}%
974 \latexrelease)\EndIncludeInRelease

```

The major changes for float suppression and the changes to the float mechanism to make it conform to the documentation are in these next macros.

`\@addtobot` Lots of changes.

```

975 (*2kernel | fltrace)
976 \def \@addtobot {%
977 (*trace)
978   \fl@trace{***Start addtobot}%
979 /trace)
980   \@getfpsbit 4\relax
981 (*trace)
982   \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi bot:
983                                           \the \@fpstype}%
984 /trace)
985   \ifodd \@tempcnta
986     \@flsetnum \@botnum
987     \ifnum \@botnum>\z@
988       \@tempswafalse
989       \@flcheckspace \@botroom \@botlist
990       \if@tempswa

```

This next line means that this page is produced with box 255 having depth zero, rather than the normal maxdepth: is this needed, useful?

```

991     \global \maxdepth \z@
992     \@flupdates \@botnum \@botroom \@botlist
993 (*trace)
994     \fl@trace{colroom (after-bot) = \the \@colroom}%
995     \fl@trace{colnum (after-bot) = \the \@colnum}%
996     \fl@trace{botnum (after-bot) = \the \@botnum}%
997     \fl@trace{***Success: bot}%
998 /trace)
999     \inserttrue
1000   \fi
1001 (*trace)
1002   \else
1003     \fl@trace{Fail: botnum = \the \@botnum:
1004                                     fpstype \the \@fpstype=ORD?}%
1005     \ifnum \@fpstype<\sixt@n
1006       \fl@trace{ERROR: !b float not successful (addtobot)}%
1007     \fi
1008 /trace)
1009   \fi
1010   \fi
1011 }

```

`\@addtotoporbot` Lots of changes.

```

1012 \def \@addtotoporbot {%
1013 (*trace)
1014   \fl@trace{***Start addtotoporbot}%
1015 /trace)

```

```

1016 \getfpsbit \tw@
1017 (*trace)
1018 \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi top:
1019 \the \@fpstype}%
1020 /trace)
1021 \ifodd \@tempcnta
1022 \flsetnum \@topnum
1023 \ifnum \@topnum>\z@
1024 \@tempwafalse
1025 \flcheckspace \@toproom \@toplist
1026 \if@tempswa
1027 \bitor\@currtype{\@midlist\@botlist}%
1028 (*trace)
1029 \fl@trace{(mid+bot)list: \@midlist, \@botlist:
1030 (addtotoporbot-before)}%
1031 /trace)
1032 \if@test
1033 (*trace)
1034 \fl@trace{type already on list: mid or bot---sent to addtobot}%
1035 /trace)
1036 \else
1037 \flupdates \@topnum \@toproom \@toplist
1038 (*trace)
1039 \fl@trace{colroom (after-top) = \the \@colroom}%
1040 \fl@trace{colnum (after-top) = \the \@colnum}%
1041 \fl@trace{topnum (after-top) = \the \@topnum}%
1042 \fl@trace{***Success: top}%
1043 /trace)
1044 \@inserttrue
1045 \fi
1046 \fi
1047 (*trace)
1048 \else
1049 \fl@trace{Fail: topnum = \the \@topnum: fpstype
1050 \the \@fpstype=ORD?}%
1051 \ifnum \@fpstype<\sist@n
1052 \fl@trace{ERROR: !t float not successful (addtotoporbot)}%
1053 \fi
1054 /trace)
1055 \fi
1056 \fi
1057 \if@insert
1058 \else
1059 (*trace)
1060 \fl@trace{sent to addtobot (addtotoporbot)}%
1061 /trace)
1062 \@addtobot
1063 \fi
1064 }
1065 /2kernel | fltrace)

```

\@addtocurcol Lots of changes.

```

1066 <latexrelease | fltrace | flafter>\IncludeInRelease{2015/01/01}%
1067 <latexrelease | fltrace | flafter> {\@addtocurcol}{float order in 2-column}%

```



```

1068 (*2ekernel | latexrelease | fltrace | flafter)
1069 \def \@addtocurcol {%
1070 (*trace)
1071   \fl@trace{***Start addtocurcol}%
1072 /trace)
1073   \@insertfalse
1074   \@setfloatypecounts
1075   \ifnum \@fpstype=8
1076 (*trace)
1077   \fl@trace{fpstype !p only (addtocurcol): \the \@fpstype = 8?}%
1078 /trace)
1079   \else
1080   \ifnum \@fpstype=24
1081 (*trace)
1082   \fl@trace{fpstype p only (addtocurcol): \the \@fpstype = 24?}%
1083 /trace)
1084   \else
1085   \flsettextmin

```

This is a new adjustment which is quite a major change in functionality; but it implements the documentation. Note that `\@reqcolroom` will include the whole of the page-so-far, and hence includes `\@textfloatsheight` of floats, so before comparing it with `\@textmin`, we add this to `\@textmin` also.

```

1086 (*trace)
1087   \fl@trace{textfloatsheight (before) = \the \@textfloatsheight}%
1088 /trace)
1089   \advance \@textmin \@textfloatsheight
1090   \@reqcolroom \@pageht

```

This line must be removed since `\@specialoutput` changed.

```

1091 %       \advance \@reqcolroom \@pagedp
1092 (*trace)
1093   \fl@trace{textmin + textfloatsheight: \the \@textmin}%
1094   \fl@trace{page-so-far: \the \@reqcolroom}%
1095 /trace)
1096   \ifdim \@textmin>\@reqcolroom
1097     \@reqcolroom \@textmin
1098 (*trace)
1099   \fl@trace{ORD? textmin being used}%
1100 /trace)
1101   \fi
1102   \advance \@reqcolroom \ht\@currbox
1103 (*trace)
1104   \fl@trace{float size = \the \ht \@currbox (addtocurcol)}%
1105   \fl@trace{colroom = \the \@colroom (addtocurcol)}%
1106   \fl@trace{reqcolroom = \the \@reqcolroom (addtocurcol)}%
1107 /trace)
1108   \ifdim \@colroom>\@reqcolroom
1109     \flsetnum \@colnum
1110     \ifnum \@colnum>\z@
1111       \bitor\@currtype\@deferlist

```

We need to defer the float also if its width doesn't fit.

```

1112   \@testwrongwidth\@currbox

```

```

1113 (*trace)
1114 \fl@trace{deferlist: \@deferlist: (addtocurcol-before)}%
1115 (/trace)
1116 \if@test
1117 (*trace)
1118 \fl@trace{type already on list: defer (addtocurcol)}%
1119 (/trace)
1120 \else
1121 \@bitor\@currtype\@botlist
1122 (*trace)
1123 \fl@trace{botlist: \@botlist: (addtocurcol-before)}%
1124 (/trace)
1125 \if@test
1126 (*trace)
1127 \fl@trace{type already on list: bot---sent to addtobot}%
1128 (/trace)
1129 \@addtobot
1130 \else
1131 (*trace)
1132 \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi
1133 here: \the \@fpstype}%
1134 (/trace)
1135 \ifodd \count\@currbox
1136 \advance \@reqcolroom \intextsep
1137 \ifdim \@colroom>\@reqcolroom
1138 \global \advance \@colnum \m@ne
1139 \global \advance \@textfloatsheight \ht\@currbox

```

This may sometimes give an overestimate.

```

1140 \global \advance \@textfloatsheight 2\intextsep
1141 \@cons \@midlist \@currbox
1142 (*trace)
1143 \fl@trace{***Success: here}%
1144 \fl@trace{textfloatsheight (after-here) =
1145 \the \@textfloatsheight}%
1146 \fl@trace{colnum (after-here) = \the \@colnum}%
1147 (/trace)

```

CHANGE TO \@addtocurcol:

\penalty\z@ changed to \penalty\interlinepenalty so \samepage works properly with figure and table environments. (Changed 23 Oct 86)

There is also an \addpenalty\interlinepenalty above.

Since in 2e \samepage is no longer supported, these could be removed.

Although it is best to use \addvspace in case two h floats come together, this makes other spacing more difficult to adjust; whereas if a user specifies two h floats together then they can more easily get the spacing correct by ad hoc commands.

It is necessary to adjust for the addition of \parskip here in case the float is added between paragraphs (i.e. when in vertical mode).

If the nobreak switch is true we need to reset it and clear \everypar since the float may not reset the flag and cannot reset the \everypar globally.

Typesetting starts here (we are in vertical mode).

```

1148 \if@nobreak
1149 \nobreak
1150 \@nobreakfalse

```

```

1151             \everypar{}%
1152         \else
1153             \addpenalty \interlinepenalty
1154         \fi
1155         \vskip \intextsep
1156         \box\@currbox
1157         \penalty\interlinepenalty
1158         \vskip\intextsep
1159         \ifnum\outputpenalty <-\@Mii \vskip -\parskip\fi

Typesetting ends here.

1160         \outputpenalty \z@
1161         \@inserttrue
1162 (*trace)
1163         \else
1164             \fl@trace{Fail---no room at 2nd test of colroom
1165                 (addtocorcol \string\intextsep)}%
1166         </trace>
1167         \fi
1168         \fi
1169         \if@insert
1170         \else

Next set of docstrip guards are a bit weird, essentially \@addtotoporbot ends
up inside the kernel and the fltrace package and \@addtobot shows up in the
flafter package. Guess that could have been done a bit more obvious :- )

1171 (*2ekernel | fltrace | latexrelease)
1172 (*trace)
1173             \fl@trace{not here: sent to addtotoporbot}%
1174 </trace>
1175             \@addtotoporbot
1176 </2ekernel | fltrace | latexrelease>
1177 (*!2ekernel&!fltrace&!latexrelease)
1178 (*trace)
1179             \fl@trace{not here: sent to addtobot}%
1180 </trace>
1181             \@addtobot
1182 </!2ekernel&!fltrace&!latexrelease>
1183             \fi
1184             \fi
1185             \fi
1186 (*trace)
1187         \else
1188             \fl@trace{Fail: colnum = \the \@colnum:
1189                 fpstype \the \@fpstype=ORD?}%
1190             \ifnum \@fpstype<\sist@n
1191                 \fl@trace{ERROR: BANG float not successful (addtocurcol)}%
1192             \fi
1193 </trace>
1194             \fi
1195 (*trace)
1196         \else
1197             \fl@trace{Fail---no room: fl box ht: \the \ht \@currbox
1198                 (addtocurcol)}%
1199 </trace>

```

```

1200     \fi
1201     \fi
1202     \fi
1203     \if@insert
1204     \else
1205         \@resetfps
1206     (*trace)
1207         \fl@trace{put on deferlist (addtocurcol)}%
1208     (/trace)
1209     \@cons\@deferlist\@currbox
1210     (*trace)
1211         \fl@trace{deferlist: \@deferlist: (addtocurcol-after)}%
1212     (/trace)
1213     \fi
1214 }%
1215 (/2kernel | latexrelease | fltrace | flafter)
1216 (latexrelease | fltrace | flafter)\EndIncludeInRelease
1217 (latexrelease | fltrace | flafter)\IncludeInRelease{0000/00/00}%
1218 (latexrelease | fltrace | flafter) {\@addtocurcol}{float order in 2-column}%
1219 (latexrelease | fltrace | flafter)\def \@addtocurcol {%
1220 (*trace)
1221 (latexrelease | fltrace | flafter) \fl@trace{***Start addtocurcol}%
1222 (/trace)
1223 (latexrelease | fltrace | flafter) \@insertfalse
1224 (latexrelease | fltrace | flafter) \@setfloattypescounts
1225 (latexrelease | fltrace | flafter) \ifnum \@fpstype=8
1226 (*trace)
1227 (latexrelease | fltrace | flafter) \fl@trace{fpstype !p only (addtocurcol):
1228 (latexrelease | fltrace | flafter) \the \@fpstype = 8?}%
1229 (/trace)
1230 (latexrelease | fltrace | flafter) \else
1231 (latexrelease | fltrace | flafter) \ifnum \@fpstype=24
1232 (*trace)
1233 (latexrelease | fltrace | flafter) \fl@trace{fpstype p only (addtocurcol):
1234 (latexrelease | fltrace | flafter) \the \@fpstype = 24?}%
1235 (/trace)
1236 (latexrelease | fltrace | flafter) \else
1237 (latexrelease | fltrace | flafter) \@flsettextmin

```

This is a new adjustment which is quite a major change in functionality; but it implements the documentation. Note that `\@reqcolroom` will include the whole of the page-so-far, and hence includes `\@textfloatsheight` of floats, so before comparing it with `\@textmin`, we add this to `\@textmin` also.

```

1238 (*trace)
1239 (latexrelease | fltrace | flafter) \fl@trace{textfloatsheight (before) =
1240 (latexrelease | fltrace | flafter) \the \@textfloatsheight}%
1241 (/trace)
1242 (latexrelease | fltrace | flafter) \advance \@textmin \@textfloatsheight
1243 (latexrelease | fltrace | flafter) \@reqcolroom \@pageht

```

This line must be removed since `\@specialoutput` changed.

```

1244 % \advance \@reqcolroom \@pagedp
1245 (*trace)
1246 (latexrelease | fltrace | flafter) \fl@trace{textmin + textfloatsheight:
1247 (latexrelease | fltrace | flafter) \the \@textmin}%

```

```

1248 \latexrelease | fltrace | flafter> \fl@trace{page-so-far: \the \@reqcolroom}%
1249 \latexrelease | fltrace | flafter>
1250 /trace>
1251 \latexrelease | fltrace | flafter> \ifdim \@textmin>\@reqcolroom
1252 \latexrelease | fltrace | flafter> \@reqcolroom \@textmin
1253 /*trace>
1254 \latexrelease | fltrace | flafter> \fl@trace{ORD? textmin being used}%
1255 /trace>
1256 \latexrelease | fltrace | flafter> \fi
1257 \latexrelease | fltrace | flafter> \advance \@reqcolroom \ht\@currbox
1258 /*trace>
1259 \latexrelease | fltrace | flafter> \fl@trace{float size =
1260 \latexrelease | fltrace | flafter> \the \ht \@currbox (addtocurcol)}}%
1261 \latexrelease | fltrace | flafter> \fl@trace{colroom =
1262 \latexrelease | fltrace | flafter> \the \@colroom (addtocurcol)}}%
1263 \latexrelease | fltrace | flafter> \fl@trace{reqcolroom =
1264 \latexrelease | fltrace | flafter> \the \@reqcolroom (addtocurcol)}}%
1265 /trace>
1266 \latexrelease | fltrace | flafter> \ifdim \@colroom>\@reqcolroom
1267 \latexrelease | fltrace | flafter> \@flsetnum \@colnum
1268 \latexrelease | fltrace | flafter> \ifnum \@colnum>\z@
1269 \latexrelease | fltrace | flafter> \@bitor\@currtype\@deferlist
1270 /*trace>
1271 \latexrelease | fltrace | flafter> \fl@trace{deferlist:
1272 \latexrelease | fltrace | flafter> \@deferlist: (addtocurcol-before)}}%
1273 /trace>
1274 \latexrelease | fltrace | flafter> \if@test
1275 /*trace>
1276 \latexrelease | fltrace | flafter> \fl@trace{type already on list:
1277 \latexrelease | fltrace | flafter> defer (addtocurcol)}}%
1278 /trace>
1279 \latexrelease | fltrace | flafter> \else
1280 \latexrelease | fltrace | flafter> \@bitor\@currtype\@botlist
1281 /*trace>
1282 \latexrelease | fltrace | flafter> \fl@trace{botlist: \@botlist:
1283 \latexrelease | fltrace | flafter> (addtocurcol-before)}}%
1284 /trace>
1285 \latexrelease | fltrace | flafter> \if@test
1286 /*trace>
1287 \latexrelease | fltrace | flafter> \fl@trace{type already on list:
1288 \latexrelease | fltrace | flafter> bot---sent to addtobot}%
1289 /trace>
1290 \latexrelease | fltrace | flafter> \@addtobot
1291 \latexrelease | fltrace | flafter> \else
1292 /*trace>
1293 \latexrelease | fltrace | flafter> \fl@trace{fpstype
1294 \latexrelease | fltrace | flafter> \ifodd \@tempcnta OK \else not \fi
1295 \latexrelease | fltrace | flafter> here: \the \@fpstype}%
1296 /trace>
1297 \latexrelease | fltrace | flafter> \ifodd \count\@currbox
1298 \latexrelease | fltrace | flafter> \advance \@reqcolroom \intextsep
1299 \latexrelease | fltrace | flafter> \ifdim \@colroom>\@reqcolroom
1300 \latexrelease | fltrace | flafter> \global \advance \@colnum \m@ne
1301 \latexrelease | fltrace | flafter> \global \advance

```

```

1302 <latexrelease | fltrace | flafter>          \@textfloatsheight\ht\@currbox
This may sometimes give an overestimate.
1303 <latexrelease | fltrace | flafter>          \global \advance
1304 <latexrelease | fltrace | flafter>          \@textfloatsheight 2\intextsep
1305 <latexrelease | fltrace | flafter>          \@cons \@midlist \@currbox
1306 <*trace>
1307 <latexrelease | fltrace | flafter>          \fl@trace{***Success: here}%
1308 <latexrelease | fltrace | flafter>          \fl@trace{textfloatsheight
1309 <latexrelease | fltrace | flafter>              (after-here) =
1310 <latexrelease | fltrace | flafter>              \the \@textfloatsheight}%
1311 <latexrelease | fltrace | flafter>          \fl@trace{colnum (after-here) =
1312 <latexrelease | fltrace | flafter>              \the \@colnum}%
1313 </trace>
CHANGE TO \@addtocurcol:
\penalty\z@ changed to \penalty\interlinepenalty so \samepage works
properly with figure and table environments. (Changed 23 Oct 86)
There is also an \addpenalty\interlinepenalty above.
Since in 2e \samepage is no longer supported, these could be removed.
Although it is best to use \addvspace in case two h floats come together, this
makes other spacing more difficult to adjust; whereas if a user specifies two h floats
together then they can more easily get the spacing correct by ad hoc commands.
It is necessary to adjust for the addition of \parskip here in case the float is
added between paragraphs (i.e. when in vertical mode).
If the nobreak switch is true we need to reset it and clear \everypar since the
float may not reset the flag and cannot reset the \everypar globally.
Typesetting starts here (we are in vertical mode).
1314 <latexrelease | fltrace | flafter>          \if@nobreak
1315 <latexrelease | fltrace | flafter>          \nobreak
1316 <latexrelease | fltrace | flafter>          \@nobreakfalse
1317 <latexrelease | fltrace | flafter>          \everypar{}%
1318 <latexrelease | fltrace | flafter>          \else
1319 <latexrelease | fltrace | flafter>          \addpenalty\interlinepenalty
1320 <latexrelease | fltrace | flafter>          \fi
1321 <latexrelease | fltrace | flafter>          \vskip \intextsep
1322 <latexrelease | fltrace | flafter>          \box\@currbox
1323 <latexrelease | fltrace | flafter>          \penalty\interlinepenalty
1324 <latexrelease | fltrace | flafter>          \vskip\intextsep
1325 <latexrelease | fltrace | flafter>          \ifnum\outputpenalty
1326 <latexrelease | fltrace | flafter>              <-\@Mii \vskip
1327 <latexrelease | fltrace | flafter>          -\parskip\fi
Typesetting ends here.
1328 <latexrelease | fltrace | flafter>          \outputpenalty \z@
1329 <latexrelease | fltrace | flafter>          \inserttrue
1330 <*trace>
1331 <latexrelease | fltrace | flafter>          \else
1332 <latexrelease | fltrace | flafter>          \fl@trace{Fail---no room at 2nd test of colroom
1333 <latexrelease | fltrace | flafter>              (addtocorcol \string\intextsep)}%
1334 </trace>
1335 <latexrelease | fltrace | flafter>          \fi
1336 <latexrelease | fltrace | flafter>          \fi
1337 <latexrelease | fltrace | flafter>          \if@insert

```

```

1338 <latexrelease | fltrace | flafter>          \else
Next set of docstrip guards are a bit weird, essentially \@addtotoporbot ends up
inside the kernel and the fltrace package and \@addtotoporbot shows up in the
flafter package. Guess that could have been done a bit more obvious :-)
1339 <*2ekernel | fltrace>
1340 <*trace>
1341 <latexrelease | fltrace | flafter>          \fl@trace{not here: sent to addtotoporbot}%
1342 </trace>
1343 <latexrelease | fltrace | flafter>          \@addtotoporbot
1344 </2ekernel | fltrace>
1345 <*!2ekernel&!autoload&!fltrace>
1346 <*trace>
1347 <latexrelease | fltrace | flafter>          \fl@trace{not here: sent to addtobot}%
1348 </trace>
1349 <latexrelease | fltrace | flafter>          \@addtobot
1350 </!2ekernel&!autoload&!fltrace>
1351 <latexrelease | fltrace | flafter>          \fi
1352 <latexrelease | fltrace | flafter>          \fi
1353 <latexrelease | fltrace | flafter>          \fi
1354 <*trace>
1355 <latexrelease | fltrace | flafter>          \else
1356 <latexrelease | fltrace | flafter>          \fl@trace{Fail: colnum = \the \@colnum:
1357 <latexrelease | fltrace | flafter>          fpstype \the \@fpstype=ORD?}%
1358 <latexrelease | fltrace | flafter>          \ifnum \@fpstype<\sist@n
1359 <latexrelease | fltrace | flafter> \fl@trace{ERROR: BANG float not successful
1360 <latexrelease | fltrace | flafter>          (addtocurcol)}}%
1361 <latexrelease | fltrace | flafter>          \fi
1362 </trace>
1363 <latexrelease | fltrace | flafter>          \fi
1364 <*trace>
1365 <latexrelease | fltrace | flafter>          \else
1366 <latexrelease | fltrace | flafter>          \fl@trace{Fail---no room: fl box ht:
1367 <latexrelease | fltrace | flafter>          \the \ht \@currbox (addtocurcol)}}%
1368 </trace>
1369 <latexrelease | fltrace | flafter>          \fi
1370 <latexrelease | fltrace | flafter>          \fi
1371 <latexrelease | fltrace | flafter>          \fi
1372 <latexrelease | fltrace | flafter>          \if@insert
1373 <latexrelease | fltrace | flafter>          \else
1374 <latexrelease | fltrace | flafter>          \@resetfps
1375 <*trace>
1376 <latexrelease | fltrace | flafter>          \fl@trace{put on deferlist (addtocurcol)}}%
1377 </trace>
1378 <latexrelease | fltrace | flafter>          \@cons\@deferlist\@currbox
1379 <*trace>
1380 <latexrelease | fltrace | flafter>          \fl@trace{deferlist: \@deferlist:
1381 <latexrelease | fltrace | flafter>          (addtocurcol-after)}}%
1382 </trace>
1383 <latexrelease | fltrace | flafter>          \fi
1384 <latexrelease | fltrace | flafter>          }%
1385 <latexrelease | fltrace | flafter>\EndIncludeInRelease

```

\@addtonextcol Lots of changes.

```

1386 \latexrelease | fltrace \IncludeInRelease{2015/01/01}
1387 \latexrelease | fltrace \{@addtonextcol\}{float order in 2-column}%
1388 \*2ekernel | latexrelease | fltrace)
1389 \def\@addtonextcol{%
1390   \begingroup
1391   \*trace)
1392   \fl@trace{***Start addtonextcol}%
1393 \}trace)
1394   \@insertfalse
1395   \@setfloattypescounts
1396   \ifnum \@fpstype=8
1397 \*trace)
1398   \fl@trace{fpstype not curcol: \the \@fpstype = 8?}%
1399 \}trace)
1400   \else
1401   \ifnum \@fpstype=24
1402 \*trace)
1403   \fl@trace{fpstype not curcol: \the \@fpstype = 24?}%
1404 \}trace)
1405   \else
1406   \@flsettextmin
1407 \*trace)
1408   \fl@trace{text-so-far: Opt (top of col)}%
1409 \}trace)
1410   \@reqcolroom \ht\@currbox
1411 \*trace)
1412   \fl@trace{float size: \the \@reqcolroom (addtonextcol)}%
1413 \}trace)
1414   \advance \@reqcolroom \@textmin
1415 \*trace)
1416   \fl@trace{colroom = \the \@colroom (addtonextcol)}%
1417   \fl@trace{reqcolroom = \the \@reqcolroom (addtonextcol)}%
1418 \}trace)
1419   \ifdim \@colroom>\@reqcolroom
1420   \@flsetnum \@colnum
1421   \ifnum \@colnum>\z@
1422     \@bitor\@currtype\@deferlist
1423 \*trace)
1424     \fl@trace{deferlist: \@deferlist: (addtonextcol-before)}%
1425 \}trace)
1426   \@testwrongwidth\@currbox
1427   \if@test
1428 \*trace)
1429     \fl@trace{type already on list: defer (addtonextcol)}%
1430 \}trace)
1431   \else
1432 \*trace)
1433     \fl@trace{sent to addtotoporbot (addtonextcol)}%
1434 \}trace)
1435     \@addtotoporbot
1436   \fi
1437 \fi
1438 \*trace)

```



```

1439         \else
1440             \fl@trace{Fail---no room: fl box ht: \the \ht \@currbox
1441                                     (addtonextcol)}%
1442         \trace>
1443         \fi
1444         \fi
1445         \fi
1446         \if@insert
1447         \else
1448         (*trace>
1449             \fl@trace{put back on deferlist (addtonextcol)}%
1450         \trace>
1451             \@cons\@deferlist\@currbox
1452         (*trace>
1453             \fl@trace{deferlist: \@deferlist: (addtonextcol-after)}%
1454         \trace>
1455         \fi
1456         (*trace>
1457             \fl@trace{End of addtonextcol -- locally counts:}%
1458             \fl@trace{col: \the\@colnum. top: \the \@topnum. bot: \the \@botnum.}%
1459         \trace>
1460         \endgroup
1461         (*trace>
1462             \fl@trace{End of addtonextcol -- globally counts:}%
1463             \fl@trace{col: \the\@colnum. top: \the \@topnum. bot: \the \@botnum.}%
1464         \trace>
1465         }%
1466         \2ekernel | latexrelease | fltrace>
1467         \latexrelease | fltrace>\EndIncludeInRelease
1468         \latexrelease | fltrace>\IncludeInRelease{0000/00/00}%
1469         \latexrelease | fltrace> {\@addtonextcol}{float order in 2-column}%
1470         \latexrelease | fltrace>\def\@addtonextcol{%
1471         \latexrelease | fltrace> \begingroup
1472         (*trace>
1473         \latexrelease | fltrace> \fl@trace{***Start addtonextcol}%
1474         \trace>
1475         \latexrelease | fltrace> \insertfalse
1476         \latexrelease | fltrace> \setfloattypecounts
1477         \latexrelease | fltrace> \ifnum \@fpstype=8
1478         (*trace>
1479         \latexrelease | fltrace> \fl@trace{fpstype not curcol:
1480         \latexrelease | fltrace> \the \@fpstype = 8?}%
1481         \trace>
1482         \latexrelease | fltrace> \else
1483         \latexrelease | fltrace> \ifnum \@fpstype=24
1484         (*trace>
1485         \latexrelease | fltrace> \fl@trace{fpstype not curcol:
1486         \latexrelease | fltrace> \the \@fpstype = 24?}%
1487         \trace>
1488         \latexrelease | fltrace> \else
1489         \latexrelease | fltrace> \flsettextmin
1490         (*trace>
1491         \latexrelease | fltrace> \fl@trace{text-so-far: Opt (top of col)}%
1492         \trace>

```

```

1493 \latexrelease | fltrace> \@reqcolroom \ht\@currbox
1494 \*trace>
1495 \latexrelease | fltrace> \fl@trace{float size:
1496 \latexrelease | fltrace> \the \@reqcolroom (addtonextcol)}%
1497 \latexrelease | fltrace>
1498 \*trace>
1499 \latexrelease | fltrace> \advance \@reqcolroom \@textmin
1500 \*trace>
1501 \latexrelease | fltrace> \fl@trace{colroom =
1502 \latexrelease | fltrace> \the \@colroom (addtonextcol)}%
1503 \latexrelease | fltrace> \fl@trace{reqcolroom =
1504 \latexrelease | fltrace> \the \@reqcolroom (addtonextcol)}%
1505 \*trace>
1506 \latexrelease | fltrace> \ifdim \@colroom>\@reqcolroom
1507 \latexrelease | fltrace> \@flsetnum \@colnum
1508 \latexrelease | fltrace> \ifnum\@colnum>\z@
1509 \latexrelease | fltrace> \@bitor\@currtype\@deferlist
1510 \*trace>
1511 \latexrelease | fltrace> \fl@trace{deferlist: \@deferlist:
1512 \latexrelease | fltrace> (addtonextcol-before)}%
1513 \*trace>
1514 \latexrelease | fltrace> \if@test
1515 \*trace>
1516 \latexrelease | fltrace> \fl@trace{type already on list:
1517 \latexrelease | fltrace> defer (addtonextcol)}%
1518 \*trace>
1519 \latexrelease | fltrace> \else
1520 \*trace>
1521 \latexrelease | fltrace> \fl@trace{sent to addtotoporbot
1522 \latexrelease | fltrace> (addtonextcol)}%
1523 \*trace>
1524 \latexrelease | fltrace> \@addtotoporbot
1525 \latexrelease | fltrace> \fi
1526 \latexrelease | fltrace> \fi
1527 \*trace>
1528 \latexrelease | fltrace> \else
1529 \latexrelease | fltrace> \fl@trace{Fail---no room: fl box ht:
1530 \latexrelease | fltrace> \the \ht \@currbox (addtonextcol)}%
1531 \*trace>
1532 \latexrelease | fltrace> \fi
1533 \latexrelease | fltrace> \fi
1534 \latexrelease | fltrace> \fi
1535 \latexrelease | fltrace> \if@insert
1536 \latexrelease | fltrace> \else
1537 \*trace>
1538 \latexrelease | fltrace> \fl@trace{put back on deferlist
1539 \latexrelease | fltrace> (addtonextcol)}%
1540 \*trace>
1541 \latexrelease | fltrace> \@cons\@deferlist\@currbox
1542 \*trace>
1543 \latexrelease | fltrace> \fl@trace{deferlist: \@deferlist:
1544 \latexrelease | fltrace> (addtonextcol-after)}%
1545 \*trace>
1546 \latexrelease | fltrace> \fi

```

```

1547 (*trace)
1548 (latexrelease|fltrace) \fl@trace{End of addtonextcol --
1549 (latexrelease|fltrace) locally counts:}%
1550 (latexrelease|fltrace) \fl@trace{col: \the \@colnum.
1551 (latexrelease|fltrace) top: \the \@topnum. bot: \the \@botnum.}%
1552 (/trace)
1553 (latexrelease|fltrace) \endgroup
1554 (*trace)
1555 (latexrelease|fltrace) \fl@trace{End of addtonextcol --
1556 (latexrelease|fltrace) globally counts:}%
1557 (latexrelease|fltrace) \fl@trace{col: \the \@colnum.
1558 (latexrelease|fltrace) top: \the \@topnum. bot: \the \@botnum.}%
1559 (/trace)
1560 (latexrelease|fltrace)}%
1561 (latexrelease|fltrace)\EndIncludeInRelease

```

\@addtodblcol Lots of changes.

```

1562 (latexrelease|fltrace)\IncludeInRelease{2015/01/01}%
1563 (latexrelease|fltrace) {\@addtodblcol}{float order in 2-column}%
1564 (*2ekernel|latexrelease|fltrace)
1565 \def\@addtodblcol{%
1566 \begingroup
1567 (*trace)
1568 \fl@trace{***Start addtodblcol}%
1569 (/trace)
1570 \@insertfalse
1571 \@setfloatypecounts
1572 \@getfpsbit \tw@
1573 (*trace)
1574 \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi dbltop:
1575 \the \@fpstype}%
1576 (/trace)
1577 \ifodd\@tempcnta
1578 \@flsetnum \@dbltopnum
1579 \ifnum \@dbltopnum>\z@
1580 \@tempswafalse
1581 \ifdim \@dbltoproom>\ht\@currbox
1582 \@tempswatrue
1583 (*trace)
1584 \fl@trace{Space OK: \@dbltoproom =
1585 \the \@dbltoproom > \the \ht \@currbox
1586 (dbltoproom)}%
1587 (/trace)
1588 \else
1589 (*trace)
1590 \fl@trace{fpstype: \the \@fpstype (addtodblcol)}%
1591 (/trace)
1592 \ifnum \@fpstype<\sist@n
1593 (*trace)
1594 \fl@trace{BANG float ignoring \@dbltoproom}%
1595 \fl@trace{\@spaces \@dbltoproom = \the \@dbltoproom.
1596 Ht float: \the \ht \@currbox-BANG}%
1597 (/trace)

```

Need to check that there is room on the page, using the local value of \@textmin

to make the necessary adjustment to \@dbltoproom.

```

1598      \advance \@dbltoproom \@textmin
1599 (*trace)
1600      \fl@trace{Local value of texmin: \the \@textmin}%
1601      \fl@trace{\@spaces space on page = \the \@dbltoproom.
1602                Ht float: \the \ht \@currbox-BANG}%
1603 (/trace)
1604      \ifdim \@dbltoproom>\ht \@currbox
1605        \@tempwattrue
1606 (*trace)
1607        \fl@trace{Space OK BANG: space on page =
1608                  \the \@dbltoproom > \the \ht \@currbox}%
1609      \else
1610        \fl@trace{fpstype: \the \@fpstype}%
1611        \fl@trace{Fail---no room dbltoproom-BANG?:}%
1612        \fl@trace{\@spaces space on page = \the \@dbltoproom.
1613                  Ht float: \the \ht \@currbox}%
1614 (/trace)
1615      \fi
1616      \advance \@dbltoproom -\@textmin
1617 (*trace)
1618      \else
1619        \fl@trace{fpstype: \the \@fpstype}%
1620        \fl@trace{Fail---no room dbltoproom-ORD?:}%
1621        \fl@trace{\@spaces \@dbltoproom = \the \@dbltoproom.
1622                  Ht float: \the \ht \@currbox}%
1623 (/trace)
1624      \fi
1625      \fi
1626      \if@tempwa
1627        \@bitor \@currtype \@deferlist
1628 (*trace)
1629        \fl@trace{(dbl)deferlist: \@deferlist: (before)}%
1630 (/trace)
1631      not in fixfloats?
1632      \if@test
1633 (*trace)
1634        \fl@trace{type already on list: (dbl)defer}%
1635 (/trace)
1636      \else
1637        \@tempdima -\ht \@currbox
1638        \advance \@tempdima
1639        -\ifx \@dbltoplist\@empty \dbltextfloatsep \else
1640          \dblfloatsep \fi
1641        \global \advance \@dbltoproom \@tempdima
1642        \global \advance \@colht \@tempdima
1643        \global \advance \@dbltopnum \m@ne
1644        \@cons \@dbltoplist \@currbox
1645 (*trace)
1646        \fl@trace{dbltopnum (after) = \the \@dbltopnum}%
1647        \fl@trace{***Success: dbltop}%
1648 (/trace)

```

```

1649             \@inserttrue
1650         \fi
1651     \fi
1652 (*trace)
1653     \else
1654         \fl@trace{Fail: dbltopnum = \the \@dbltopnum: fpstype
1655                                     \the \@fpstype=ORD?}%
1656         \ifnum \@fpstype<\sixt@n
1657             \fl@trace{ERROR: !t float not successful (addtodblcol)}%
1658         \fi
1659 /trace)
1660 \fi
1661 \fi
1662 \if@insert
1663 \else
1664 (*trace)
1665     \fl@trace{put on deferlist}%
1666 /trace)
1667     \@cons\@deferlist\@currbox
1668 (*trace)
1669     \fl@trace{(dbl)deferlist: \@deferlist: (after)}%
1670 /trace)
1671 \fi
1672 (*trace)
1673     \fl@trace{End of addtodblcol -- locally count:}%
1674     \fl@trace{dbltop: \the \@dbltopnum.}%
1675 /trace)
1676 \endgroup
1677 (*trace)
1678     \fl@trace{End of addtodblcol -- globally count:}%
1679     \fl@trace{dbltop: \the \@dbltopnum.}%
1680 /trace)
1681 }%
1682 /2ekernel | latexrelease | fltrace)
1683 (latexrelease | fltrace)\EndIncludeInRelease
1684 (latexrelease | fltrace)\IncludeInRelease{0000/00/00}%
1685 (latexrelease | fltrace) {\@addtodblcol}{float order in 2-column}%
1686 (latexrelease | fltrace)\def\@addtodblcol{%
1687 (latexrelease | fltrace) \begingroup
1688 (*trace)
1689 (latexrelease | fltrace) \fl@trace{***Start addtodblcol}%
1690 /trace)
1691 (latexrelease | fltrace) \@insertfalse
1692 (latexrelease | fltrace) \@setfloattypescounts
1693 (latexrelease | fltrace) \@getfpsbit \tw@
1694 (*trace)
1695 (latexrelease | fltrace) \fl@trace{fpstype \ifodd \@tempcnta OK
1696 (latexrelease | fltrace) \else not \fi dbltop: \the \@fpstype}%
1697 /trace)
1698 (latexrelease | fltrace) \ifodd\@tempcnta
1699 (latexrelease | fltrace) \@flsetnum \@dbltopnum
1700 (latexrelease | fltrace) \ifnum \@dbltopnum>\z@
1701 (latexrelease | fltrace) \@tempswafalse
1702 (latexrelease | fltrace) \ifdim \@dbltoproom>\ht\@currbox

```

```

1703 <latexrelease | fltrace>          \@tempswatrue
1704 < *trace>
1705 <latexrelease | fltrace>          \fl@trace{Space OK: \@dbltoproom =
1706 <latexrelease | fltrace>          \the \@dbltoproom > \the \ht \@currbox
1707 <latexrelease | fltrace>          (dbltoproom)}%
1708 < /trace>
1709 <latexrelease | fltrace>          \else
1710 < *trace>
1711 <latexrelease | fltrace>          \fl@trace{fpstype: \the \@fpstype (addtodblcol)}%
1712 < /trace>
1713 <latexrelease | fltrace>          \ifnum \@fpstype<\sixt@@n
1714 < *trace>
1715 <latexrelease | fltrace>          \fl@trace{BANG float ignoring \@dbltoproom}%
1716 <latexrelease | fltrace>          \fl@trace{\@spaces \@dbltoproom =
1717 <latexrelease | fltrace>          \the \@dbltoproom.
1718 <latexrelease | fltrace>          Ht float: \the \ht \@currbox-BANG}%
1719 < /trace>

```

Need to check that there is room on the page, using the local value of \@textmin to make the necessary adjustment to \@dbltoproom.

```

1720 <latexrelease | fltrace>          \advance \@dbltoproom \@textmin
1721 < *trace>
1722 <latexrelease | fltrace>          \fl@trace{Local value of texmin: \the \@textmin}%
1723 <latexrelease | fltrace>          \fl@trace{\@spaces space on page =
1724 <latexrelease | fltrace>          \the \@dbltoproom.
1725 <latexrelease | fltrace>          Ht float: \the \ht \@currbox-BANG}%
1726 < /trace>
1727 <latexrelease | fltrace>          \ifdim \@dbltoproom>\ht \@currbox
1728 <latexrelease | fltrace>          \@tempswatrue
1729 < *trace>
1730 <latexrelease | fltrace>          \fl@trace{Space OK BANG: space on page =
1731 <latexrelease | fltrace>          \the \@dbltoproom > \the \ht \@currbox}%
1732 <latexrelease | fltrace>          \else
1733 <latexrelease | fltrace>          \fl@trace{fpstype: \the \@fpstype}%
1734 <latexrelease | fltrace>          \fl@trace{Fail---no room dbltoproom-BANG?:}%
1735 <latexrelease | fltrace>          \fl@trace{\@spaces space on page =
1736 <latexrelease | fltrace>          \the \@dbltoproom.
1737 <latexrelease | fltrace>          Ht float: \the \ht \@currbox}%
1738 < /trace>
1739 <latexrelease | fltrace>          \fi
1740 <latexrelease | fltrace>          \advance \@dbltoproom -\@textmin
1741 < *trace>
1742 <latexrelease | fltrace>          \else
1743 <latexrelease | fltrace>          \fl@trace{fpstype: \the \@fpstype}%
1744 <latexrelease | fltrace>          \fl@trace{Fail---no room dbltoproom-ORD?:}%
1745 <latexrelease | fltrace>          \fl@trace{\@spaces \@dbltoproom =
1746 <latexrelease | fltrace>          \the \@dbltoproom.
1747 <latexrelease | fltrace>          Ht float: \the \ht \@currbox}%
1748 < /trace>
1749 <latexrelease | fltrace>          \fi
1750 <latexrelease | fltrace>          \fi
1751 <latexrelease | fltrace>          \if@tempswa
1752 <latexrelease | fltrace>          \@bitor \@currtype \@dbldeferlist
1753 < *trace>

```

```

1754 \latexrelease|fltrace> \fl@trace{dbldeferlist:
1755 \latexrelease|fltrace> \@dbldeferlist: (before)}%
1756 \trace>
1757 \latexrelease|fltrace> \if@test
1758 \*trace>
1759 \latexrelease|fltrace> \fl@trace{type already on list: dbldefer}%
1760 \trace>
1761 \latexrelease|fltrace> \else
1762 \latexrelease|fltrace> \@tempdima -\ht\@currbox
1763 \latexrelease|fltrace> \advance\@tempdima
1764 \latexrelease|fltrace> -\ifx \@dbltoplist\@empty
1765 \latexrelease|fltrace> \dbltextfloatsep
1766 \latexrelease|fltrace> \else \dblfloatsep \fi
1767 \latexrelease|fltrace> \global \advance \@dbltoproom \@tempdima
1768 \latexrelease|fltrace> \global \advance \@colht \@tempdima
1769 \latexrelease|fltrace> \global \advance \@dbltopnum \m@ne
1770 \latexrelease|fltrace> \@cons \@dbltoplist \@currbox
1771 \*trace>
1772 \latexrelease|fltrace> \fl@trace{dbltopnum (after) =
1773 \latexrelease|fltrace> \the \@dbltopnum}%
1774 \latexrelease|fltrace> \fl@trace{***Success: dbltop}%
1775 \trace>
1776 \latexrelease|fltrace> \@inserttrue
1777 \latexrelease|fltrace> \fi
1778 \latexrelease|fltrace> \fi
1779 \*trace>
1780 \latexrelease|fltrace> \else
1781 \latexrelease|fltrace> \fl@trace{Fail: dbltopnum = \the \@dbltopnum:
1782 \latexrelease|fltrace> fpstype \the \@fpstype=ORD?}%
1783 \latexrelease|fltrace> \ifnum \@fpstype<\sist@n
1784 \latexrelease|fltrace> \fl@trace{ERROR: !t float not successful
1785 \latexrelease|fltrace> (addtodblcol)}%
1786 \latexrelease|fltrace> \fi
1787 \trace>
1788 \latexrelease|fltrace> \fi
1789 \latexrelease|fltrace> \fi
1790 \latexrelease|fltrace> \if@insert
1791 \latexrelease|fltrace> \else
1792 \*trace>
1793 \latexrelease|fltrace> \fl@trace{put on dbldeferlist}%
1794 \trace>
1795 \latexrelease|fltrace> \@cons\@dbldeferlist\@currbox
1796 \*trace>
1797 \latexrelease|fltrace> \fl@trace{dbldeferlist: \@dbldeferlist: (after)}%
1798 \trace>
1799 \latexrelease|fltrace> \fi
1800 \*trace>
1801 \latexrelease|fltrace> \fl@trace{End of addtodblcol -- locally count:}%
1802 \latexrelease|fltrace> \fl@trace{ dbltop: \the \@dbltopnum.}%
1803 \trace>
1804 \latexrelease|fltrace> \endgroup
1805 \*trace>
1806 \latexrelease|fltrace> \fl@trace{End of addtodblcol -- globally count:}%
1807 \latexrelease|fltrace> \fl@trace{dbltop: \the \@dbltopnum.}%

```

```

1808 </trace>
1809 <latexrelease | fltrace>}%
1810 <latexrelease | fltrace>\EndIncludeInRelease

```

\@addmarginpar

```

1811 (*2ekernel)
1812 \def\@addmarginpar{\@next\@marbox\@currlist{\@cons\@freelist\@marbox
1813   \@cons\@freelist\@currbox}\@latexbug\@tempcnta\@ne
1814   \if@twocolumn
1815     \if@firstcolumn \@tempcnta\m@ne \fi
1816   \else
1817     \if@mparswitch
1818       \ifodd\c@page \else\@tempcnta\m@ne \fi
1819     \fi
1820     \if@reversemargin \@tempcnta -\@tempcnta \fi
1821   \fi
1822   \ifnum\@tempcnta <\z@ \global\setbox\@marbox\box\@currbox \fi
1823   \@tempdima\@mparbottom
1824   \advance\@tempdima -\@pageht
1825   \advance\@tempdima\ht\@marbox
1826   \ifdim\@tempdima >\z@
1827     \@latex@warning@no@line {Marginpar on page \thepage\space moved}%
1828   \else
1829     \@tempdima\z@
1830   \fi
1831   \global\@mparbottom\@pageht
1832   \global\advance\@mparbottom\@tempdima
1833   \global\advance\@mparbottom\dp\@marbox
1834   \global\advance\@mparbottom\marginparpush
1835   \advance\@tempdima -\ht\@marbox

```

Putting box movement inside the ‘marbox’:

```

1836 \global\setbox \@marbox
1837         \vbox {\vskip \@tempdima
1838             \box \@marbox}%
1839 \global \ht\@marbox \z@
1840 \global \dp\@marbox \z@

```

Sticking (rather than gluing:-) the ‘marbox’ to the line above, changed vskip to kern:

```

1841 \kern -\@pagedp
1842 \nointerlineskip
1843 \hb@xt@\columnwidth
1844   {\ifnum \@tempcnta >\z@
1845     \hskip\columnwidth \hskip\marginparsep
1846   \else
1847     \hskip -\marginparsep \hskip -\marginparwidth
1848   \fi
1849   \box\@marbox \hss}%

```

For this reason the following code can vanish:

```

\ nobreak           %% No longer needed. CAR92/12
\ vskip -\@tempdima %% No longer needed. CAR92/12

1850 \nointerlineskip
1851 \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}}

```



### 65.1.1 Kludgeins

This part of the file is part of the implementation of the following two new commands for L<sup>A</sup>T<sub>E</sub>X2e.

`\enlargethispage{<dim>}`

Adds <dim> to the height of the current column only. On the printed page the bottom of this column is extended downwards by exactly <dim> without having any effect on the placement of the footer; this may result in an overprinting.

`\enlargethispage*{<dim>}`

Similar to `\enlargethispage` but it tries to squeeze the column to be printed in as small a space as possible, ie it uses any shrinkability in the column. If the column was not explicitly broken (e.g. with `\pagebreak`) this may result in an overfull box message but except for this it will come out as expected (if you know what to expect).

The star form of this command is dedicated to Leslie Lamport, the other we need for ourselves (FMi, CAR).

These commands may well have unwanted effects if used soon before a `\clearpage`: please give keep them clear of such places.

`\@kludgeins` The insert which makes T<sub>E</sub>X do a lot of the necessary work. All we need to put into it is the amount by which the pagegoal should be changed.

```
1852 \newinsert \@kludgeins
1853 \global\dimen\@kludgeins \maxdimen
1854 \global\count\@kludgeins 1000
```

`\enlargethispage` The user command.

```
\enlargethispage* 1855 \gdef \enlargethispage {%
1856     \ifstar
1857     {%
1858     (*trace)
1859         \fl@trace{Enlarging page height * }%
1860     </trace>
1861         \@enlargepage{\hbox{\kern\p@}}}%
1862     {%
1863     (*trace)
1864         \fl@trace{Enlarging page height exactly---}%
1865     </trace>
1866         \@enlargepage\@empty}%
1867 }
```

`\@enlargepage` This actually inserts the insert, after checking for extreme values of the change.

```
1868 \gdef\@enlargepage#1#2{%
1869 (*trace)
1870     \fl@trace{\@spaces\@spaces by #2}%
1871 </trace>
1872     \@tempskipa#2\relax
1873     \ifdim \@tempskipa>.5\maxdimen
```

```

1874     \@latexerr{Suggested\space extra\space height\space
1875                 (\the\@tempskipa)\space dangerously\space
1876                 large}\@eha
1877     \else
1878         \ifdim \vsize<.5\maxdimen
1879 (*trace)
1880     \fl@trace {Kludgeins added--pagegoal before: \the\pagegoal}%
1881 (/trace)
1882     \@bsphack
1883     \insert\@kludgeins{#1\vskip-\@tempskipa}%
1884     \@esphack
    This next bit is for tracing only:
1885 (*trace)
1886     \ifvmode \par
1887     \fl@trace {Kludgeins added--pagegoal after: \the\pagegoal}%
1888     \fi
1889 (/trace)
1890     \else
1891     \@latexerr{Page\space height\space already\space
1892                 too\space large}\@eha
1893     \fi
1894 \fi
1895 }
1896 (/2ekernel)

```

### 65.1.2 Float control

This part implements controllable floats and other changes to the float mechanism.

It provides, at the document level, the following command for inclusion in L<sup>A</sup>T<sub>E</sub>X2e.

```
\suppressfloats
```

This suppresses all further floats on the current page.

With an optional argument it suppresses only floats only in certain positions on the current page.

[t] suppresses only floats at the top of the page [b] suppresses only floats at the bottom of the page

It also enables the use of an extra specifier, !, in the location optional argument of a float. If this is present then, just for this particular float, whenever it is processed by the float mechanism the followinghg are ignored:

- all restrictions on the number of floats which can appear;
- all explicit restrictions on the amount of space which should (not) be occupied by floats and/or text.

The mechanism will still attempt to ensure that pages are not overfull.

These specifiers override, for the single float, the suppression commands described above.

In its current form, it also supplies a reasonably exhaustive, and somewhat baroque, means of tracing some aspects of the float mechanism.

More tracing.

```

\fl@trace Set-up tracing for floats independent of other tracing as it produces mega-output.
\tracefloatsoff Default is no tracing.
\tracefloats 1897 \def \fl@trace
\fl@traceval 1898 \def \fl@tracemessage #1{\let\@elt\@empty\typeout{LaTeX2e: #1}}
\tracefloatvals 1899 \def \tracefloats{\let \fl@trace \fl@tracemessage}
\fl@tracemessage 1900 \def \tracefloatsoff {\let \fl@trace \@gobble}
1901 \tracefloatsoff
1902 \def \fl@traceval #1{\fl@trace{\string #1 = \the #1}}
1903 \IncludeInRelease{2015/01/01}{\tracefloatvals}%
1904 {trace float vals}%
1905 \def \tracefloatvals{%

```

As `\@dblfloatplacement` sets `\f@depth` it needs to be run inside a group, otherwise the float placement will test for the wrong value.<sup>9</sup>

```

1906 \begingroup
1907 \@dblfloatplacement
1908 \@floatplacement
1909 \fl@trace{***Float placement parameters:}%
1910 \fl@traceval\@colnum
1911 \fl@traceval\@colroom
1912 \fl@traceval\@topnum
1913 \fl@traceval\@toproom
1914 \fl@traceval\@botnum
1915 \fl@traceval\@botroom
1916 \fl@traceval\@fpmin
1917 \fl@trace{\string\textfraction = \textfraction}%
1918 \fl@traceval\@dbltopnum
1919 \fl@traceval\@dbltoproom
1920 \fl@trace{\string\textfraction = \textfraction}%
1921 \fl@trace{toplist: \@toplist}%
1922 \fl@trace{botlist: \@botlist}%
1923 \fl@trace{midlist: \@midlist}%
1924 \fl@trace{deferlist: \@deferlist}%
1925 \fl@trace{dbltoplist: \@dbltoplist}%
1926 %Fmi \fl@trace{dbldeferlist: \@dbldeferlist}%
1927 \endgroup
1928 }
1929 \EndIncludeInRelease
1930 \IncludeInRelease{0000/00/00}{\tracefloatvals}%
1931 {trace float vals}%
1932 \def \tracefloatvals{%
1933 \begingroup
1934 \@dblfloatplacement
1935 \@floatplacement
1936 \fl@trace{***Float placement parameters:}%
1937 \fl@traceval\@colnum
1938 \fl@traceval\@colroom
1939 \fl@traceval\@topnum

```

---

<sup>9</sup>This is a somewhat questionable design.

```

1940 \fl@traceval\@toproom
1941 \fl@traceval\@botnum
1942 \fl@traceval\@botroom
1943 \fl@traceval\@fpmin
1944 \fl@trace{\string\textfraction = \textfraction}%
1945 \fl@traceval\@dbltopnum
1946 \fl@traceval\@dbltoproom
1947 \fl@trace{\string\textfraction = \textfraction}%
1948 \fl@trace{toplist: \@toplist}%
1949 \fl@trace{botlist: \@botlist}%
1950 \fl@trace{midlist: \@midlist}%
1951 \fl@trace{deferlist: \@deferlist}%
1952 \fl@trace{dbltoplist: \@dbltoplist}%
1953 % next line only in old releases
1954 \fl@trace{dbldeferlist: \@dbldeferlist}%
1955 \endgroup
1956 }
1957 \EndIncludeInRelease

```

We need to make sure that `fltrace` comes before `flafter` to make the tracing work.

```

1958 \@ifpackageloaded{flafter}
1959 {
1960   \PackageWarningNoLine
1961     {fltrace}{Load 'fltrace' before 'flafter'\MessageBreak
              Attempting to recover by reloading 'flafter'}}%

```

Hide the fact that `flafter` was already loaded and then request it anew.

```

1962 \expandafter\let\csname ver@flafter.sty\endcsname\relax
1963 \def\reserved@a#1{%
1964   \expandafter\let\csname\string#1+flafter+IIR\endcsname\relax}%
1965 \reserved@a\@addtocurcol
1966 \reserved@a\@addtonextcol
1967 \RequirePackage{flafter}}{}
1968 \fltrace

```

As the code for `flafter` will contain tracing calls so that it works in conjunction with `fltrace` we need to provide a dummy definition for `\fl@trace` in that package.

```

1969 (*flafter)
1970 \providecommand\fl@trace[1]{}
1971 \flafter

```

`\suppressfloats` Float suppression commands: these set the relevant counter globally to zero. Thus `\@flstop` they are overridden for a particular float by an `!` specifier.

```

1972 (*2ekernel)
1973 \def \suppressfloats {%
1974   \ifnextchar [%
1975     \@flstop
1976     {\global \@colnum \z@}%
1977 }

```

Maybe this should be a loop over `#1`?

```

1978 \def \@flstop [#1]{%
1979   \if t#1%
1980     \global \@topnum \z@

```

```

1981 \fi
1982 \if b#1%
1983 \global \@botnum \z@
1984 \fi
1985 }

```

Manipulation of float placement and type; both their strings and the corresponding count registers.

`\@fpstype` First a new count register to go with `\@currtype`.  
`\@reqcolroom` Then a new skip register, for information needed to remove the `\@maxsep`  
`\@textfloatsheight` conservatism: it is possible that this could use a temporary register.

Finally a dimension register to hold the total height of in-text floats on the current page. This is needed to implement a major change in the functionality of `\@addtocurcol` which is, nevertheless, a bug fix. It is not local and therefore cannot be a temporary register.

```

1986 \newcount \@fpstype
1987 \newdimen \@reqcolroom
1988 \newdimen \@textfloatsheight
1989 \if2kernel

```

`\@fpsadddefault` Adds the default placement to what is already there.  
Should not need to change this, but could do it as follows:

```

\def \@fpsadddefault {%
  \@temptokena \expandafter\expandafter\expandafter
    {\csname fps@\@captype \endcsname}%
  \edef \reserved@a {\the\@temptokena}%
  \@onelevel@sanitize \reserved@a
  \edef \@fps {\@fps\reserved@a}%
}

```

```

1990 \if2kernel\iftraced
1991 \def \@fpsadddefault {%
1992 \iftraced
1993 \if@trace{fps changed from: \@fps}%
1994 \iftraced
1995 \edef \@fps {\@fps\csname fps@\@captype \endcsname}%
1996 \if@latex@warning {%
1997 No positions in optional float specifier.\MessageBreak
1998 Default added (so using '\@fps')}%
1999 }

```

`\@setfloattypescounts` Sets counters `\@fpstype` and `\@currtype`.  
BANG == bit4 of `\count\@currbox` = 0.

```

2000 \def \@setfloattypescounts {%
2001 \if@currtype \count\@currbox
2002 \if@fpstype \count\@currbox
2003 \divide\@currtype\@xxxii \multiply\@currtype\@xxxii
2004 \advance \@fpstype -\@currtype
2005 \iftraced
2006 \if@trace{(mod 32) fpstype: \the \@fpstype}%
2007 \if@trace{(mult of 32) currtype: \the \@currtype}%

```

```

2008 % Tracing only: but some should be changed into real errors/warnings?
2009 \ifnum \@fpstype<\sist@n
2010 \ifnum \@fpstype=\z@
2011 \fl@trace{ERROR: no PLACEMENT, fpstype = \the \@fpstype = 0?}%
2012 \fi
2013 \ifnum \@fpstype=\@ne
2014 \fl@trace{WARNING: only h, fpstype = \the \@fpstype = 1?}%
2015 \fi
2016 \fl@trace{BANG float}%
2017 \else
2018 \ifnum \@fpstype=\sist@n
2019 \fl@trace{ERROR: no PLACEMENT, fpstype = \the \@fpstype = 16?}%
2020 \fi
2021 \ifnum \@fpstype=17
2022 \fl@trace{WARNING: only h, fpstype = \the \@fpstype = 17?}%
2023 \fi
2024 \fl@trace{ORD float}%
2025 \fi
2026 \trace
2027 }
2028 \end{kernel} \end{fltrace}

```

Macros for getting, testing and setting bits of the fps.

`\@getfpsbit` Sets `\@tempcnta` to required bit of `\count\@currbox`.

```

2029 (*2kernel)
2030 \def \@getfpsbit {%
2031 \boxfpsbit \@currbox
2032 }

```

`\@boxfpsbit` Used above.

```

2033 \def \@boxfpsbit #1#2{%
2034 \@tempcnta \count#1
2035 \divide \@tempcnta #2\relax
2036 }

```

`\@testfp` New definition of the float page test.

```

2037 \def \@testfp #1{%
2038 \@boxfpsbit #1\relax % Really ‘#1 8’ for human readers!
2039 \ifodd \@tempcnta
2040 \else
2041 \@testtrue
2042 \fi
2043 }

```

`\@setfpsbit` Sets required bit of `\@tempcnta` (to 1).

```

2044 \def \@setfpsbit #1{%
2045 \@tempcntb \@tempcnta
2046 \divide \@tempcntb #1\relax
2047 \ifodd \@tempcntb
2048 \else
2049 \advance \@tempcnta #1\relax
2050 \fi

```

```

2051 }
2052 </2ekernel>

```

**\@resethfps** Globally adds t as a possible location for an h or !h only placement: this must be done using the count.

Although it will leave \@fpstype set to 17 even if it was originally 1, this does not matter since it is the last thing in \@addtocurcol.

```

2053 (*2ekernel | fltrace)
2054 \def \@resethfps {%
2055   \let\reserved@a\@empty
2056   \ifnum \@fpstype=\@ne
2057     \def \reserved@a {!}%
2058     \@fpstype 17
2059   \fi
2060   \ifnum \@fpstype=17
2061     \global \advance \count\@currbox \tw@
2062     \@latex@warning@no@line {%
2063       '\reserved@a h' float specifier changed to '\reserved@a ht'}%
2064   (*trace)
2065     \fl@trace{%
2066       't' added to '\reserved@a h'- new Count: \the \count\@currbox}%
2067   </trace>
2068   \fi
2069 }

```

Special stuff for BANG floats.

**\@flsetnum** Ignores any zero float counter value in case BANG.

It uses a local assignment to the normally global counter: a bit naughty, perhaps?

These assignments are safe so long as the counter involved is only consulted once (i.e. only for the 'bang float') with the changed value. This is the case within \@addtocurcol because it is used only once within a call of the output routine (which forms a group).

For \@addtonextcol this is achieved by putting a group around its code; this is needed because it is called (by \@startcolumn) for each float which was on the deferlist. Almost identical considerations pertain to \@addtodblcol. There may be more efficient ways to handle this, but the group seems to be the simplest.

```

2070 \def \@flsetnum #1{%
2071   (*trace)
2072     \fl@trace{fpstype: \the \@fpstype (flsetnum \string#1)}%
2073   </trace>
2074   \ifnum \@fpstype<\sist@n
2075     \ifnum #1=\z@
2076   (*trace)
2077     \fl@trace{BANG float resetting \string#1 to 1}%
2078   </trace>
2079     #1\@ne
2080   \fi
2081   \fi
2082   (*trace)
2083     \fl@trace{#1 (before) = \the #1}%
2084   </trace>

```

2085 }

\@flsettextmin This ignores \textfraction space restriction in case BANG.

```

2086 \def \@flsettextmin {%
2087 (*trace)
2088   \fl@trace{fpstype: \the \@fpstype (flsettextmin)}%
2089 (/trace)
2090   \ifnum \@fpstype<\sixt@@n
2091 (*trace)
2092     \fl@trace{BANG ignoring textmin}%
2093 (/trace)
2094     \@textmin \z@
2095   \else
2096     \@textmin \textfraction\@colht
2097 (*trace)
2098     \fl@trace{ORD textmin = \the \@textmin}%
2099 (/trace)
2100   \fi
2101 }
```

\@flcheckspace This ignores space restriction in case BANG; this is still slightly conservative since it does not allow for the fact that, if there is no text in the column then \textfloatsep is not needed. Sets @tempswa true if there is room for \@currbox.

```

2102 \def \@flcheckspace #1#2{%
2103   \advance \@reqcolroom
2104   \ifx #2\@empty \textfloatsep \else \floatsep \fi
2105 (*trace)
2106   \fl@trace{colroom = \the \@colroom
2107                                     (flcheckspace \string#1 \string#2)}%
2108   \fl@trace{reqcolroom = \the \@reqcolroom
2109                                     (flcheckspace \string#1 \string#2)}%
2110 (/trace)
2111   \ifdim \@colroom>\@reqcolroom
2112     \ifdim #1>\ht\@currbox
2113       \@tempwattrue
2114 (*trace)
2115       \fl@trace{Space OK: #1 = \the #1 > \the \ht \@currbox
2116                                     (flcheckspace \string#1 \string#2)}%
2117 (/trace)
2118   \else
2119 (*trace)
2120     \fl@trace{fpstype: \the \@fpstype
2121                                     (flcheckspace \string#1 \string#2)}%
2122 (/trace)
2123     \ifnum \@fpstype<\sixt@@n
2124 (*trace)
2125       \fl@trace{BANG float ignoring #1
2126                                     (flcheckspace \string#1 \string#2):}%
2127       \fl@trace{\@spaces #1 = \the #1. Ht float: \the \ht \@currbox
2128                                     BANG}%
2129 (/trace)
2130     \@tempwattrue
2131 (*trace)
```



```

2132     \else
2133     \fl@trace{Fail---no room (flcheckspace \string#1 \string#2)
2134             (fpstype \the \@fpstype=ORD?):}%
2135     \fl@trace{\@spaces #1 = \the #1. Ht float: \the \ht \@currbox
2136             ORD?:}%
2137 \end{trace}
2138 \fi
2139 \fi
2140 \end{trace}
2141 \else
2142     \fl@trace{Fail---no room at 2nd test of colroom
2143             (flcheckspace \string#1 \string#2):}%
2144 \end{trace}
2145 \fi
2146 }
2147 \end{2kernel} \end{fltrace}

```

`\@flupdates` This updates everything when a float is placed.

```

2148 \end{2kernel}
2149 \def \@flupdates #1#2#3{%
2150   \global \advance #1\m@ne
2151   \global \advance \@colnum \m@ne
2152   \tempdima -\ht\@currbox
2153   \advance \@tempdima
2154   -\ifx #3\@empty \textfloatsep \else \floatsep \fi
2155   \global \advance #2\@tempdima
2156   \global \advance \@colroom \@tempdima
2157   \@cons #3\@currbox
2158 }
2159 \end{2kernel}

```

Interesting facts about float mechanisms past and present, together with a summary of various features, some unresolved:

1. The value `\textfraction` does not affect the processing of doublecol floats: this seems sensible, but should be documented.
2. `\twocolumn` floatplacement was wrong: `dbl` not needed, `ord` needed.
3. `\floatplacement` was not called after `\startdblcol` or `\topnewpage`. This has been changed; it is clearly a bug fix.
4. The use `\@topnewpage` when `\dblfigrule` is non-trivial produced a rule in the wrong place. This has been fixed by not using `\dblfigrule` when processing the ‘float’ from `\@topnewpage`.
5. If the specifier was just `h` and the float could not be put here, it went on the deferlist and stayed there until a clearpage. It now gets changed to a ‘th’: this is only an error-recovery action, putting just `h` or `!h` should be deprecated.
6. `\@dblmaxsep` was ‘the maximum of `\dblfloatsep` and `\dbltextfloatsep`’. But it was never used! Now gone completely, like `\@maxsep`.

7. After an h float is put on a page, it was counted as text when applying the `\textfraction` test; this is possibly too big a change although it is a bug fix?
8. Two consecutive h floats are separated by twice `\intertextsep`: this could be changed to one by use of `\addvspace`, OK? Note that it would also mean that less space is put in if an h float immediately follows other spaces. This is also possibly too big a change, at least for compatibility mode? Or it may be simply wrong! It has not been changed.
9. Now `\@addtocurcol` checks first for just p fps. I think that this is an increase in efficiency, but maybe the coding should be made even more efficient.
10. `\@tryfcolumn` now tests if the list is empty first, otherwise lots of wasted time! Thus this test has been removed from `\@startcolumn`. As Frank pointed out, this makes `\@startcolumn` less efficient. But it is now the same as `\@startdblcolumn`: I can see no reason why they should be different, but which is best?
11. Why is `\@colroom` set in `\@docclearpage`?
12. Footnotes. Check what `\clearpage` does when footnotes are left over. Footnotes are not put on float pages and, also, `\@addtonextcol` ignores the existence of held-over footnotes in deciding what floats can go on the page. Not changed.
13. `\clearpage` can still lose non-boxes, at least when floats are involved. It also moves some to the ‘wrong page’, but this may be a coding problem.
14. The `!` option makes it necessary to check in `\output` that there is enough room left on the page after adding a float. (This would have been necessary anyway if anyone set `\@textmin` too close to zero! A similar danger existed also if the text in a `\twocolumn[text]` entity gets too large.) The current implementation of this also makes the normal case a little less efficient, OK? Not enough room means, at present, less than `\baselineskip`, with a warning: is this OK? Should it be made generic (another parameter)?
15. There are four possibilities for supporting this:  
`\twocolumn[\maketitle more text]`  
One is to change `\maketitle` slightly to allow this. Another is to change `\@topnewpage` so that more than one `\twocolumn[]` command is allowed; in this case `\maketitle\twocolumn[more text]` will work. The former is more robust from the user’s viewpoint, but makes the code for `\maketitle` rather ad hoc (maybe it is already?). Another is to misuse the global `twocolumn` flag locally within `\@topnewpage`. Yet another is to move the column count register from the `multicol` package into the kernel. This has been done.
16. Where should the reinserts be put to maximise the probability that footnotes come out on the correct page? Or should we go for as much compatibility as possible (but see next item)?

17. Should we continue to support (as much as possible) `\samepage`? Some of its intended functionality is now advertised as being provided by `\enlargethispage`. Use of either is likely to result in wrongly placed footnotes, marginals, etc. Which should have priority: obeying the pagination instructions, or correct placement of notes/marginalia?
18. Is the adjustment of space to cause shrinking in the kludge-\* case correct? Should it be limited to 0pt?
19. Is the setting of `\boxmaxdepth` in `makecol` and friends needed? It only has any effect if `\@textbottom` ends with a box or rule, in which case the `vskip` to allow for its depth should also be added. If it is kept, it should probably be the last thing in the box. It has now been removed.  
  
It would perhaps be better to document that `\@textbottom` and `\@texttop` must have natural height 0pt.
20. I cannot see why the `vskip` adjustment for the depth is needed if `boxmaxdepth` is used to ensure that there is never a too deep box.
21. The value of `\boxmaxdepth` should be explicitly set whenever necessary: it is too risky to assume that it has any particular value. Care is needed in deciding what to set it to.  
  
It is interesting to note that the value of `\boxmaxdepth` is unique in being read before the local settings for the box group are reset; all other parameter settings which affect the box construction use their values outside the box group.
22. Should `\@maxdepth` store the setting of `\maxdepth` from `lplain`? Or should we provide a proper interface to class files for setting these?

An analysis of various other macros.

`\@opcol` should do `\@floatplacement`, but where? Right at the end, since it always occurs at the start of a column.

```
\def\@opcol{%
  % Why is this done first?
  \global \@mparbottom \z@
  \if@twocolumn
    \@outputdblcol
  \else
    \@outputpage
    % This is not needed since it is done at the end of
    %   |\@outputpage|:
    \global \@colht \textheight
  \fi}
```

Only tracing has been added to these.

```
2160 <latexrelease | fltrace>\IncludeInRelease{2017/01/01}%
2161 <latexrelease | fltrace> {\@makefcolumn}{negative height floats}%
2162 <*2ekernel | fltrace | latexrelease>
2163 \def\@makefcolumn #1{%
2164   \begingroup
```

```

2165 \@fpmin -\maxdimen
2166 \let \@testfp \@gobble
2167 \@tryfcolumn #1%
2168 \endgroup
2169 \*trace)
2170 \if@fcolmade
2171 \fl@trace{PAGE: in \string\clearpage
2172 \if@twocolumn ---twocolumn\fi---}%
2173 \fl@trace{----- float column/page completed from \string#1}%
2174 \fi
2175 \*trace)
2176 }

2177 \*trace) \fl@trace\EndIncludeInRelease
2178 \*trace) \fl@trace\IncludeInRelease{0000/00/00}%
2179 \*trace) \fl@trace {\@makefcolumn}{negative height floats}%
2180 \*trace) \fl@trace \def\@makefcolumn #1{%
2181 \*trace) \fl@trace \begin{group
2182 \*trace) \fl@trace \@fpmin \z@
2183 \*trace) \fl@trace \let \@testfp \@gobble
2184 \*trace) \fl@trace \@tryfcolumn #1%
2185 \*trace) \fl@trace \end{group
2186 \*trace)
2187 \*trace) \fl@trace \if@fcolmade
2188 \*trace) \fl@trace \fl@trace{PAGE: in \string\clearpage
2189 \*trace) \fl@trace \if@twocolumn ---twocolumn\fi---}%
2190 \*trace) \fl@trace \fl@trace{----- float column/page completed
2191 \*trace) \fl@trace from \string#1}%
2192 \*trace) \fl@trace \fi
2193 \*trace)
2194 \*trace) \fl@trace}
2195 \*trace) \fl@trace\EndIncludeInRelease
2196 \*trace) \fl@trace \*trace) \fl@trace

```

This will line up the last baselines in the two columns provided they are constructed in the normal way: i.e. ending in a skip of minus the original depth, with `\@textbottom` adding nothing.

Thus again it is essential for `\@textbottom` to have depth 0pt.

```

2197 \*trace) \fl@trace\IncludeInRelease{2015/01/01}%
2198 \*trace) \fl@trace {\@outputdblcol}{2 column marks}%
2199 \*trace) \fl@trace \*trace) \fl@trace

```

This is just a change to the single command `\@outputdblcol` so that it saves mark information for the first column and restores it in the second column.

```

2200 \def\@outputdblcol{%
2201 \if@firstcolumn
2202 \global\@firstcolumnfalse

```

Save the left column

```

2203 \global\setbox\@leftcolumn\copy\@outputbox
2204 \fl@trace{PAGE: first column boxed}%

```

Remember the marks from the first column

```

2205 \splitmaxdepth\maxdimen
2206 \vbadness\maxdimen

```

In case of `\enlargethispage` we will have infinite negative glue at the bottom of the page (coming from `\vss`) and that will earn us an error message if we `\vsplit` to get at the marks. So we need to remove the last glue (if any) at the end of `\@outputbox` as we are only interested in marks that change doesn't matter.

```
2207 \setbox\@outputbox\vbox{\unvbox\@outputbox\unskip}%
2208 \setbox\@outputbox\vsplit\@outputbox to\maxdimen
```

One minor difference from the current `fixmarks` package, pass the marks through a token register to stop any `#` tokens causing an error in a `\def`.

```
2209 \toks@{\expandafter{\topmark}}%
2210 \xdef\@firstcoltopmark{\the\toks@}%
2211 \toks@{\expandafter{\splitfirstmark}}%
2212 \xdef\@firstcolfirstmark{\the\toks@}%
```

This test does not work if truly empty marks have been inserted, but  $\text{\LaTeX}$  marks should always have (at least) two brace groups. (Except before the first mark is used, when the marks are empty, but that is OK here.)

```
2213 \ifx\@firstcolfirstmark\@empty
2214 \global\let\@setmarks\relax
2215 \else
2216 \gdef\@setmarks{%
2217 \let\firstmark\@firstcolfirstmark
2218 \let\topmark\@firstcoltopmark}%
2219 \fi
```

End of change

```
2220 \else
2221 \global\@firstcolumntrue
2222 \setbox\@outputbox\vbox{%
2223 \hb@xt@\textwidth{%
2224 \hb@xt@\columnwidth{\box\@leftcolumn \hss}%
2225 \hfil
```

The color of the `\vrule` should be `\normalcolor` as to not inherit the color from the column.

```
2226 {\normalcolor\vrule \@width\columnseprule}%
2227 \hfil
2228 \hb@xt@\columnwidth{\box\@outputbox \hss}}}%
2229 \fl@trace{PAGE: second column also boxed}%
2230 \@combinedblfloats
```

Override current first and top with those of first column if necessary

```
2231 \@setmarks
```

End of change

```
2232 \@outputpage
2233 \fl@trace{PAGE: two column page completed}%
2234 \begingroup
2235 \@dblfloatplacement
2236 \startdblcolumn
2237 \@whilesw\if@fcolmade \fi{\@outputpage
2238 \fl@trace{PAGE: double float page completed}%
2239 \startdblcolumn}%
2240 \endgroup
2241 \fi}%
```

```

2242 <latexrelease | fltrace>\EndIncludeInRelease
2243 <latexrelease | fltrace>\IncludeInRelease{0000/00/00}%
2244 <latexrelease | fltrace> {\@outputdblcol}{2 column marks}%
2245 <latexrelease | fltrace>\def\@outputdblcol{%
2246 <latexrelease | fltrace> \if@firstcolumn
2247 <latexrelease | fltrace> \global \@firstcolumnfalse
2248 <latexrelease | fltrace> \global \setbox\@leftcolumn \box\@outputbox
2249 <*trace>
2250 <latexrelease | fltrace> \fl@trace{PAGE: first column boxed}%
2251 </trace>
2252 <latexrelease | fltrace> \else
2253 <latexrelease | fltrace> \global \@firstcolumntrue
2254 <latexrelease | fltrace> \setbox\@outputbox \vbox {%
2255 <latexrelease | fltrace> \hb@xt@\textwidth {%
2256 <latexrelease | fltrace> \hb@xt@\columnwidth {%
2257 <latexrelease | fltrace> \box\@leftcolumn \hss}%
2258 <latexrelease | fltrace> \hfil
2259 <latexrelease | fltrace> {\normalcolor\vrule
2260 <latexrelease | fltrace> \@width\columnseprule}%
2261 <latexrelease | fltrace> \hfil
2262 <latexrelease | fltrace> \hb@xt@\columnwidth {%
2263 <latexrelease | fltrace> \box\@outputbox \hss}%
2264 <latexrelease | fltrace> }%
2265 <latexrelease | fltrace> }%
2266 <*trace>
2267 <latexrelease | fltrace> \fl@trace{PAGE: second column also boxed}%
2268 </trace>
2269 <latexrelease | fltrace> \@combinedblfloats
2270 <latexrelease | fltrace> \@outputpage
2271 <*trace>
2272 <latexrelease | fltrace> \fl@trace{PAGE: two column page completed}%
2273 </trace>
2274 <latexrelease | fltrace> \begingroup
2275 <latexrelease | fltrace> \@dblfloatplacement
2276 <latexrelease | fltrace> \@startdblcolumn

This loop could be replaced by an \expandafter tail recursion in
\@startdblcolumn.

2277 <latexrelease | fltrace> \@whilesw\if@fcolmade \fi
2278 <latexrelease | fltrace> {\@outputpage
2279 <*trace>
2280 <latexrelease | fltrace> \fl@trace{PAGE: double float page completed}%
2281 </trace>
2282 <latexrelease | fltrace> \@startdblcolumn}%
2283 <latexrelease | fltrace> \endgroup
2284 <latexrelease | fltrace> \fi
2285 <latexrelease | fltrace> }%
2286 <latexrelease | fltrace>\EndIncludeInRelease
2287 </2ekernel | fltrace | latexrelease>

```

### 65.1.3 Float placement parameters

The main purpose of this section is to ensure that all the float-placement parameters which need to be set in a class file or package have been declared. It

also describes their use and sets values for them which are reasonable for typical documents using US letter or A4 sized paper.

### Limits for the placement of floating objects

<code>\c@topnumber</code>	This counter holds the maximum number of floats that can appear at the top of a text page or column. 2288 (*2ekernel) 2289 <code>\newcount\c@topnumber</code> 2290 <code>\setcounter{topnumber}{2}</code>
<code>\topfraction</code>	This macro holds the maximum proportion (as a decimal number) of a text page or column that can be occupied by floats at the top. 2291 <code>\newcommand\topfraction{.7}</code>
<code>\c@bottomnumber</code>	This counter holds the maximum number of floats that can appear at the bottom of a text page or column. 2292 <code>\newcount\c@bottomnumber</code> 2293 <code>\setcounter{bottomnumber}{1}</code>
<code>\bottomfraction</code>	This macro holds the maximum proportion (as a decimal number) of a text page or column that can be occupied by floats at the bottom. 2294 <code>\newcommand\bottomfraction{.3}</code>
<code>\c@totalnumber</code>	This counter holds the maximum number of floats that can appear on any text page or column. 2295 <code>\newcount\c@totalnumber</code> 2296 <code>\setcounter{totalnumber}{3}</code>
<code>\textfraction</code>	This macro holds the minimum proportion (as a decimal number) of a text page or column that must be occupied by text. 2297 <code>\newcommand\textfraction{.2}</code>
<code>\floatpagefraction</code>	This macro holds the minimum proportion (as a decimal number) of a page or column that must be occupied by floating objects before a ‘float page’ is produced. 2298 <code>\newcommand\floatpagefraction{.5}</code>
<code>\c@dbltopnumber</code>	This counter holds the maximum number of double-column floats that can appear on the top of a two-column text page. 2299 <code>\newcount\c@dbltopnumber</code> 2300 <code>\setcounter{dbltopnumber}{2}</code>
<code>\dbltopfraction</code>	This macro holds the maximum proportion (as a decimal number) of a two-column text page that can be occupied by double-column floats at the top. 2301 <code>\newcommand\dbltopfraction{.7}</code>
<code>\dblfloatpagefraction</code>	This macro holds the minimum proportion (as a decimal number) of a page that must be occupied by double-column floating objects before a ‘double-column float page’ is produced. 2302 <code>\newcommand\dblfloatpagefraction{.5}</code>

## Floats on a text page

`\floatsep` When a floating object is placed on a page with text, these parameters control the separation between the float and the other objects on the page. These parameters are used for both one-column mode and single-column floats in two-column mode. They are all rubber lengths.

`\floatsep` is the space between adjacent floats that are placed at the top or bottom of the text page or column.

`\textfloatsep` is the space between the main text and floats at the top or bottom of the page or column.

`\intextsep` is the space between in-text floats and the text.

```
2303 \newskip\floatsep
2304 \newskip\textfloatsep
2305 \newskip\intextsep
2306 \setlength\floatsep {12\p@ \@plus 2\p@ \@minus 2\p@}
2307 \setlength\textfloatsep{20\p@ \@plus 2\p@ \@minus 4\p@}
2308 \setlength\intextsep {12\p@ \@plus 2\p@ \@minus 2\p@}
```

`\dblfloatsep` When double-column floats (floating objects that span the whole `\textwidth`) are placed at the top of a text page in two-column mode, the separation between the float and the text is controlled by `\dblfloatsep` and `\dbltextfloatsep`. They are rubber lengths.

`\dblfloatsep` is the space between adjacent double-column floats placed at the top of the text page.

`\dbltextfloatsep` is the space between the main text and double-column floats at the top of the page.

```
2309 \newskip\dblfloatsep
2310 \newskip\dbltextfloatsep
2311 \setlength\dblfloatsep {12\p@ \@plus 2\p@ \@minus 2\p@}
2312 \setlength\dbltextfloatsep{20\p@ \@plus 2\p@ \@minus 4\p@}
```

## Floats on their own page or column

`\@fptop` When floating objects are placed on a separate page or column, called a ‘float page’, the layout of the page is controlled by these parameters, which are rubber lengths.

At the top of the page `\@fptop` is inserted; typically this supplies some stretchable whitespace. At the bottom of the page `\@fpbot` is inserted. Between adjacent floats `\@fpsep` is inserted.

These parameters are used for all floating objects on a ‘float page’ in one-column mode, and for single-column floats in two-column mode.

Note that at least one of the two parameters `\@fptop` and `\@fpbot` should contain a `plus ...fil` so as to fill the remaining empty space.

```
2313 \newskip\@fptop
2314 \newskip\@fpsep
2315 \newskip\@fpbot
2316 \setlength\@fptop{0\p@ \@plus 1fil}
2317 \setlength\@fpsep{8\p@ \@plus 2fil}
2318 \setlength\@fpbot{0\p@ \@plus 1fil}
```

`\@dblftop` Double-column ‘float pages’ in two-column mode use similar parameters.  
`\@dblfpsep`  
`\@dblfpbot`



```

2319 \newskip\@dblftop
2320 \newskip\@dblpsep
2321 \newskip\@dblpbot
2322 \setlength\@dblftop{0\p@ \@plus 1fil}
2323 \setlength\@dblpsep{8\p@ \@plus 2fil}
2324 \setlength\@dblpbot{0\p@ \@plus 1fil}

\topfigrule The macros can be used to put in rules between floats and text; whatever they
\botfigrule insert should be vertical mode material which takes up zero space.
\dblfigrule 2325 \let\topfigrule=\relax
2326 \let\botfigrule=\relax
2327 \let\dblfigrule=\relax
2328 \endkernel

```

# File L

## ltclass.dtx

### 66 Introduction

This file implements the following declarations, which replace `\documentstyle` in  $\text{\LaTeX}$  2<sub>ε</sub> documents.

Note that old documents containing `\documentstyle` will be run using a compatibility option—thus keeping everyone happy, we hope!

The overall idea is that there are two types of ‘style files’: ‘class files’ which define elements and provide a default formatting for them; and ‘packages’ which provide extra functionality. One difference between  $\text{\LaTeX}$  2<sub>ε</sub> and  $\text{\LaTeX}$  2.09 is that  $\text{\LaTeX}$  2<sub>ε</sub> packages may have options. Note that options to classes/packages may be implemented such that they input files, but these file names are not necessarily directly related to the option name.

### 67 User interface

`\documentclass[⟨main-option-list⟩]{⟨class⟩}[⟨version⟩]`

There must be exactly one such declaration, and it must come first. The `⟨main-option-list⟩` is a list of options which can modify the formatting of elements which are defined in the `⟨class⟩` file as well as in all following `\usepackage` declarations (see below). The `⟨version⟩` is a version number, beginning with a date in the format `YYYY/MM/DD`. If an older version of the class is found, a warning is issued.

`\documentstyle[⟨main-option-list⟩]{⟨class⟩}[⟨version⟩]`

The `\documentstyle` declaration is kept in order to maintain upward compatibility with  $\text{\LaTeX}$  2.09 documents. It is similar to `\documentclass`, but it causes all options in `⟨main-option-list⟩` that the `⟨class⟩` does not use to be passed to `\RequirePackage` after the options have been processed. This maintains compatibility with the 2.09 behaviour. Also a flag is set to indicate that the document is to be processed in  $\text{\LaTeX}$  2.09 compatibility mode. As far as most packages are concerned, this only affects the warnings and errors  $\text{\LaTeX}$  generates. This flag does affect the definition of font commands, and `\sloppy`.

`\usepackage[⟨package-option-list⟩]{⟨package-list⟩}[⟨version⟩]`

There can be any number of these declarations. All packages in `⟨package-list⟩` are called with the same options.

Each `⟨package⟩` file defines new elements (or modifies those defined in the `⟨class⟩`), and thus extends the range of documents which can be processed. The `⟨package-option-list⟩` is a list of options which can modify the formatting of elements defined in the `⟨package⟩` file. The `⟨version⟩` is a version number, beginning with a date in the format `YYYY/MM/DD`. If an older version of the package is found, a warning is issued.

Each package is loaded only once. If the same package is requested more than once, nothing happens, unless the package has been requested with options that were not given the first time it was loaded, in which case an error is produced.

As well as processing the options given in the  $\langle package-option-list \rangle$ , each package processes the  $\langle main-option-list \rangle$ . This means that options that affect all of the packages can be given globally, rather than repeated for every package.

Note that class files have the extension `.cls`, packages have the extension `.sty`.

`filecontents`

The environment `filecontents` is intended for passing the contents of packages, options, or other files along with a document in a single file. It has one argument, which is the name of the file to create. If that file already exists (maybe only in the current directory if the OS supports a notion of a ‘current directory’ or ‘default directory’) then nothing happens (except for an information message) and the body of the environment is bypassed. Otherwise, the body of the environment is written verbatim to the file name given as the first argument, together with some comments about how it was produced.

The environment can also be called with an optional argument which is used to alter some of its behavior: option `force` or `overwrite` will allow for overwriting existing files, option `nosearch` will only check the current directory when looking if the file exists. This can be useful if you want to generate a local (modified) copy of some file that is already in the search tree of  $\text{\TeX}$ . Finally, you can use `nopreamble` to prevent it from writing the standard blurb at the top of the file (this is actually the same as using the star form of the environment).

The environment is now allowed anywhere in the document, but to ensure that all packages or options necessary are available when the document is run, it is normally best to place it at the top of your file (before `\documentclass`). A possible use case for using it inside the document body is if you want to reuse some text several times in the document you could then write it and later use `\input` to retrieve it where needed.

The begin and end tags should each be on a line by itself.

## 67.1 Option processing

When the options are processed, they are divided into two types: *local* and *global*:

- For a class, the options in the `\documentclass` command are local.
- For a package, the options in the `\usepackage` command are local, and the options in the `\documentclass` command are global.

The options for `\documentclass` and `\usepackage` are processed in the following way:

1. The local and global options that have been declared (using `\DeclareOption` as described below) are processed first.

In the case of `\ProcessOptions`, they are processed in the order that they were declared in the class or package.

In the case of `\ProcessOptions*`, they are processed in the order that they appear in the option-lists. First the global options, and then the local ones.

2. Any remaining local options are dealt with using the default option (declared using the `\DeclareOption*` declaration described below). For document classes, this usually does nothing, but records the option on a list of unused options. For packages, this usually produces an error.

Finally, when `\begin{document}` is reached, if there are any global options which have not been used by either the class or any package, the system will produce a warning.

## 68 Class and Package interface

### 68.1 Class name and version

`\ProvidesClass` A class can identify itself with the `\ProvidesClass{<name>}[<version>]` command. The `<version>` should begin with a date in the format `YYYY/MM/DD`.

### 68.2 Package name and version

`\ProvidesPackage` A package can identify itself with the `\ProvidesPackage{<name>}[<version>]` command. The `<version>` should begin with a date in the format `YYYY/MM/DD`.

### 68.3 Requiring other packages

`\RequirePackage` Packages or classes can load other packages using `\RequirePackage[<options>]{<name>}[<version>]`. If the package has already been loaded, then nothing happens unless the requested options are not a subset of the options with which it was loaded, in which case an error is called.

`\LoadClass` Similar to `\RequirePackage`, but for classes, may not be used in package files.  
`\PassOptionsToPackage` Packages can pass options to other packages using:

`\PassOptionsToPackage{<options>}{<package>}`.

`\PassOptionsToClass` This adds the `<options>` to the options list of any future `\RequirePackage` or `\usepackage` command. For example:

```
\PassOptionsToPackage{foo,bar}{fred}
\RequirePackage[baz]{fred}
```

is the same as:

```
\RequirePackage[foo,bar,baz]{fred}
```

`\LoadClassWithOptions` `\LoadClassWithOptions{<name>}[<version>]:`

This is similar to `\LoadClass`, but it always calls class `<name>` with exactly the same option list that is being used by the current class, rather than an option explicitly supplied or passed on by `\PassOptionsToClass`.

`\RequirePackageWithOptions` `\RequirePackageWithOptions` is the analogous command for packages.

This is mainly intended to allow one class to simply build on another, for example:

```
\LoadClassWithOptions{article}
```

This should be contrasted with the slightly different construction

```
\DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
\ProcessOptions
\LoadClass{article}
```

As used here, the effects are more or less the same, but the version using `\LoadClassWithOptions` is slightly quicker (and less to type). If, however, the class declares options of its own then the two constructions are different; compare, for example:

```
\DeclareOption{landscape}{...}
\ProcessOptions
\LoadClassWithOptions{article}
```

with:

```
\DeclareOption{landscape}{...}
\DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
\ProcessOptions
\LoadClass{article}
```

In the first case, the `article` class will be called with option `landscape` precisely when the current class is called with this option; but in the second example it will not as in that case `article` is only passed options by the default option handler, which is not used for `landscape` as that option is explicitly declared.

<pre>\@ifpackageloaded \@ifclassloaded \@ifpackagelater \@ifclasslater \@ifpackagewith \@ifclasswith</pre>	<p>To find out if a package has already been loaded, use <code>\@ifpackageloaded{&lt;package&gt;}{&lt;true&gt;}{&lt;false&gt;}</code>.</p> <p>To find out if a package has already been loaded with a version equal to or more recent than <code>&lt;version&gt;</code>, use <code>\@ifpackagelater{&lt;package&gt;}{&lt;version&gt;}{&lt;true&gt;}{&lt;false&gt;}</code>.</p> <p>To find out if a package has already been loaded with at least the options <code>&lt;options&gt;</code>, use <code>\@ifpackagewith{&lt;package&gt;}{&lt;options&gt;}{&lt;true&gt;}{&lt;false&gt;}</code>.</p> <p>There exists one package that can't be tested with the above commands: the <code>fontenc</code> package pretends that it was never loaded to allow for repeated reloading with different options (see <code>ltoutenc.dtx</code> for details).</p>
--	--

## 68.4 Declaring new options

Options for classes and packages are built using the same macros.

<pre>\DeclareOption \DeclareOption*</pre>	<p>To define a builtin option, use <code>\DeclareOption{&lt;name&gt;}{&lt;code&gt;}</code>.</p> <p>To define the default action to perform for local options which have not been declared, use <code>\DeclareOption*{&lt;code&gt;}</code>.</p>
---	--

*Note:* there should be no use of

`\RequirePackage`, `\DeclareOption`, `\DeclareOption*` or `\ProcessOptions` inside `\DeclareOption` or `\DeclareOption*`.

Possible uses for `\DeclareOption*` include:

```
\DeclareOption*{}
```

Do nothing. Silently accept unknown options. (This suppresses the usual warnings.)

```
\DeclareOption*{\@unknownoptionerror}
```

Complain about unknown local options. (The initial setting for package files.)

```
\DeclareOption*{\PassOptionsToPackage{\CurrentOption}{<pkg-name>}}
```

Handle the the current option by passing it on to the package `<pkg-name>`, which will presumably be loaded via `\RequirePackage` later in the file. This is useful for building ‘extension’ packages, that perhaps handle a couple of new options, but then pass everything else on to an existing package.

```

\DeclareOption*{\InputIfFileExists{xx-\CurrentOption.yyy}%
{}%
{\OptionNotUsed}}

```

Handle the option foo by loading the file `xx-foo.yyy` if it exists, otherwise do nothing, but declare that the option was not used. Actually the `\OptionNotUsed` declaration is only needed if this is being used in class files, but does no harm in package files.

## 68.5 Safe Input Macros

<code>\InputIfFileExists</code>	<code>\InputIfFileExists{&lt;file&gt;}{&lt;then&gt;}{&lt;else&gt;}</code> Inputs <i>&lt;file&gt;</i> if it exists. Immediately before the input, <i>&lt;then&gt;</i> is executed. Otherwise <i>&lt;else&gt;</i> is executed.
<code>\IfFileExists</code>	As above, but does not input the file. One thing you might like to put in the <i>&lt;else&gt;</i> clause is
<code>\@missingfileerror</code>	This starts an interactive request for a filename, supplying default extensions. Just hitting return causes the whole input to be skipped and entering <code>x</code> quits the current run,
<code>\input</code>	This has been redefined from the L <sup>A</sup> T <sub>E</sub> X2.09 definition, in terms of the new commands <code>\InputIfFileExists</code> and <code>\@missingfileerror</code> .
<code>\listfiles</code>	Giving this declaration in the preamble causes a list of all files input via the ‘safe input’ commands to be listed at the end. Any strings specified in the optional argument to <code>\ProvidesPackage</code> are listed alongside the file name. So files in standard (and other non-standard) distributions can put informative strings in this argument.

## 69 Implementation

```

1 (*2kernel)

\if@compatibility The flag for compatibility mode.
2 \newif\if@compatibility

\@documentclasshook The hook called after the first \documentclass command. By default this checks
to see if \@normalsize is undefined, and if so, sets it to \normalsize.
3 \def\@documentclasshook{%
4   \ifx\@normalsize\undefined
5     \let\@normalsize\normalsize
6   \fi
7 }

\@declaredoptions This list is automatically built by \DeclareOption. It is the list of options (separated by commas) declared in the class or package file and it defines the order in which the the corresponding \ds@<option> commands are executed. All local <option>s which are not declared will be processed in the order defined by the optional argument of \documentclass or \usepackage.
8 \let\@declaredoptions\@empty

\@classoptionslist List of options of the main class.
9 \let\@classoptionslist\relax
10 \onlypreamble\@classoptionslist

```

`\@unusedoptionlist` List of options of the main class that haven't been declared or loaded as class option files.

```

11 \let\@unusedoptionlist\@empty
12 \@onlypreamble\@unusedoptionlist

```

`\CurrentOption` Name of current package or option.

```

13 \let\CurrentOption\@empty

```

`\@currname` Name of current package or option.

```

14 \let\@currname\@empty

```

`\@currentx` The current file extension.

```

15 \global\let\@currentx=\@empty

```

`\@clsextension` The two possible values of `\@currentx`.

`\@pkgextension`

```

16 \def\@clsextension{cls}
17 \def\@pkgextension{sty}
18 \@onlypreamble\@clsextension
19 \@onlypreamble\@pkgextension

```

`\@pushfilename` Commands to push and pop the file name and extension.

`\@popfilename` #1 current name.

`\@currnamestack` #2 current extension.  
#3 current catcode of @.  
#4 Rest of the stack.

```

20 \def\@pushfilename{%
21   \xdef\@currnamestack{%
22     {\@currname}%
23     {\@currentx}%
24     {\the\catcode'\@}%
25     \@currnamestack}}
26 \@onlypreamble\@pushfilename
27 \def\@popfilename{\expandafter\@p@pfilename\@currnamestack\@nil}
28 \@onlypreamble\@popfilename
29 \def\@p@pfilename#1#2#3#4\@nil{%
30   \gdef\@currname{#1}%
31   \gdef\@currentx{#2}%
32   \catcode'\@#3\relax
33   \gdef\@currnamestack{#4}}
34 \@onlypreamble\@p@pfilename
35 \gdef\@currnamestack{}
36 \@onlypreamble\@currnamestack

```

`\@optionlist` Returns the option list of the file.

```

37 \def\@optionlist#1{%
38   \@ifundefined{opt@#1}\@empty{\csname opt@#1\endcsname}}
39 \@onlypreamble\@optionlist

```

`\@ifpackageloaded` `\@ifpackageloaded{<name>}` Checks to see whether a file has been loaded.

`\@ifclassloaded`

```

40 \def\@ifpackageloaded{\@ifl@aded\@pkgextension}
41 \def\@ifclassloaded{\@ifl@aded\@clsextension}
42 \@onlypreamble\@ifpackageloaded
43 \@onlypreamble\@ifclassloaded

```

```

44 \def\@ifl@aded#1#2{%
45   \expandafter\ifx\csname ver@#2.#1\endcsname\relax
46     \expandafter\@secondoftwo
47   \else
48     \expandafter\@firstoftwo
49   \fi}
50 \onlypreamble\@ifl@aded

\@ifpackagelater \@ifpackagelater{\<name>}{YYYY/MM/DD} Checks that the package loaded is
\@ifclasslater more recent than the given date.

51 \def\@ifpackagelater{\@ifl@ter\@pkgextension}
52 \def\@ifclasslater{\@ifl@ter\@clsextension}
53 \onlypreamble\@ifpackagelater
54 \onlypreamble\@ifclasslater

55 \def\@ifl@ter#1#2{%
56   \expandafter\@ifl@t@r
57   \csname ver@#2.#1\endcsname}
58 \onlypreamble\@ifl@ter
59 </2ekernel>

This internal macro is also used in \NeedsTeXFormat.

60 <latexrelease>\IncludeInRelease{2018/04/01}%
61 <latexrelease> \ifl@t@r{Guard against bad input}%
62 <*2ekernel | latexrelease>
63 \def\@ifl@t@r#1#2{%
64   \ifnum\expandafter\@parse@version@#1//00\@nil<%
65     \expandafter\@parse@version@#2//00\@nil
66     \expandafter\@secondoftwo
67   \else
68     \expandafter\@firstoftwo
69   \fi}
70 \def\@parse@version@#1{\@parse@version0#1}
71 </2ekernel | latexrelease>
72 <latexrelease>\EndIncludeInRelease
73 <latexrelease>\IncludeInRelease{0000/00/00}%
74 <latexrelease> \ifl@t@r{Guard against bad input}%
75 <latexrelease>\def\@ifl@t@r#1#2{%
76 <latexrelease> \ifnum\expandafter\@parse@version#1//00\@nil<%
77 <latexrelease> \expandafter\@parse@version#2//00\@nil
78 <latexrelease> \expandafter\@secondoftwo
79 <latexrelease> \else
80 <latexrelease> \expandafter\@firstoftwo
81 <latexrelease> \fi}
82 <latexrelease>\let\@parse@version@\@undefined
83 <latexrelease>\EndIncludeInRelease
84 <*2ekernel>

85 \onlypreamble\@ifl@t@r

86 </2ekernel>
87 <*2ekernel | latexreleasefirst>
88 \def\@parse@version#1/#2/#3#4#5\@nil{%
89 \@parse@version@dash#1-#2-#3#4\@nil
90 }

```



The `\if` test here ensures that an argument with no `/` or `-` produces 0 (actually 00).

```

91 \def\@parse@version@dash#1-#2-#3#4#5\@nil{%
92   \if\relax#2\relax\else#1\fi#2#3#4 }
93 </2ekernel | latexreleasefirst>
94 <*2ekernel>

```

`\@ifpackagewith` `\@ifclasswith` `\@ifpackagewith{<name>}{<option-list>}` Checks that `<option-list>` is a subset of the options **with** which `<name>` was loaded.

```

95 \def\@ifpackagewith{\@ifoptions\@pkgextension}
96 \def\@ifclasswith{\@ifoptions\@clsextension}
97 \@onlypreamble\@ifpackagewith
98 \@onlypreamble\@ifclasswith

99 \def\@ifoptions#1#2{%
100   \@expandtwoargs\@if@pti@ns{\@optionlist{#2.#1}}
101 \@onlypreamble\@ifoptions

```

Probably shouldn't use `\CurrentOption` here... (changed to `\reserved@b`.)

```

102 </2ekernel>
103 <latexrelease>\IncludeInRelease{2017/01/01}%
104 <latexrelease>           {\@if@pti@ns}{Spaces in option clash check}%
105 <*2ekernel | latexrelease>
106 \def\@if@pti@ns#1#2{%
107   \let\reserved@a\@firstoftwo

108   \edef\reserved@b{\zap@space#2 \@empty}%
109   \@for\reserved@b:=\reserved@b\do{%
110     \ifx\reserved@b\@empty
111       \else
112         \expandafter\in@\expandafter{\expandafter,\reserved@b,}{, #1,}%
113         \ifin@
114         \else
115           \let\reserved@a\@secondoftwo
116         \fi
117       \fi
118     }%
119     \reserved@a}
120 </2ekernel | latexrelease>
121 <latexrelease>\EndIncludeInRelease
122 <latexrelease>\IncludeInRelease{0000/00/00}%
123 <latexrelease>           {\@if@pti@ns}{Spaces in option clash check}%
124 <latexrelease>\def\@if@pti@ns#1#2{%
125 <latexrelease> \let\reserved@a\@firstoftwo
126 <latexrelease> \@for\reserved@b:=#2\do{%
127 <latexrelease> \ifx\reserved@b\@empty
128 <latexrelease>   \else
129 <latexrelease>   \expandafter\in@\expandafter
130 <latexrelease>           {\expandafter,\reserved@b,}{, #1,}%
131 <latexrelease>   \ifin@
132 <latexrelease>   \else
133 <latexrelease>   \let\reserved@a\@secondoftwo
134 <latexrelease>   \fi
135 <latexrelease> \fi
136 <latexrelease> }%

```

```

137 <latexrelease> \reserved@a}
138 <latexrelease>\EndIncludeInRelease
139 <*2ekernel>

140 \@onlypreamble\@if@pti@ns

\ProvidesPackage Checks that the current filename is correct, and defines \ver@filename.
141 \def\ProvidesPackage#1{%
142   \xdef\@gtempa{#1}%
143   \ifx\@gtempa\@currname\else
144     \@latex@warning@no@line{You have requested
145       \cls@pkg\space'\@currname',\MessageBreak
146       but the \cls@pkg\space provides '#1'}%
147   \fi
148   \@ifnextchar[\@pr@videpackage{\@pr@videpackage[]}]%
149   \@onlypreamble\ProvidesPackage

150 \def\@pr@videpackage[#1]{%
151   \expandafter\xdef\csname ver@\@currname.\@currentx\endcsname{#1}%
152   \ifx\@currentx\@clsextension
153     \typeout{Document Class: \@gtempa\space#1}%
154   \else
155     \wlog{Package: \@gtempa\space#1}%
156   \fi}
157 \@onlypreamble\@pr@videpackage

\ProvidesClass Like \ProvidesPackage, but for classes.
158 \let\ProvidesClass\ProvidesPackage
159 \@onlypreamble\ProvidesClass

\ProvidesFile Like \ProvidesPackage, but for arbitrary files. Do not apply \@onlypreamble to
these, as we may want to label files input during the document.

\@providesfile
160 \def\ProvidesFile#1{%
161   \begingroup
162     \catcode'\ 10 %
163     \ifnum \endlinechar<256 %
164       \ifnum \endlinechar>\m@ne
165         \catcode\endlinechar 10 %
166       \fi
167     \fi
168     \@makeother\/%
169     \@makeother\&%

170     \kernel@ifnextchar[{\@providesfile{#1}}{\@providesfile{#1}[]}]

During initex a special version of \@providesfile is used. The real definition
is installed right at the end, in ltfinal.dtx.

\def\@providesfile#1[#2]{%
  \wlog{File: #1 #2}%
  \expandafter\xdef\csname ver@#1\endcsname{#2}%
  \endgroup}

```

`\PassOptionsToPackage` If the package has been loaded, we check that it was first loaded with the options.  
`\PassOptionsToClass` Otherwise we add the option list to that of the package.

```
171 \def\@passOptions#1#2#3{%
172   \expandafter\xdef\csname opt@#3.#1\endcsname{%
173     \@ifundefined{opt@#3.#1}\@empty
174     {\csname opt@#3.#1\endcsname,}%
175     \zap@space#2 \@empty}}
176 \@onlypreamble\@passOptions
177 \def\PassOptionsToPackage{\@passOptions\@pkgextension}
178 \def\PassOptionsToClass{\@passOptions\@clsextension}
179 \@onlypreamble\PassOptionsToPackage
180 \@onlypreamble\PassOptionsToClass
```

`\DeclareOption` Adds an option as a `\ds@` command, or the default `\default@ds` command.

```
\DeclareOption* 181 \def\DeclareOption{%
182   \let\@fileswith@pti@ns\@badrequireerror
183   \@ifstar\@defdefault@ds\@declareoption}
184 \long\def\@declareoption#1#2{%
185   \xdef\@declaredoptions{\@declaredoptions,#1}%
186   \toks@{#2}%
187   \expandafter\edef\csname ds@#1\endcsname{\the\toks@}}
188 \long\def\@defdefault@ds#1{%
189   \toks@{#1}%
190   \edef\default@ds{\the\toks@}}
191 \@onlypreamble\DeclareOption
192 \@onlypreamble\@declareoption
193 \@onlypreamble\@defdefault@ds
```

`\OptionNotUsed` If we are in a class file, add `\CurrentOption` to the list of unused options. Otherwise, in a package file do nothing.

```
194 \def\OptionNotUsed{%
195   \ifx\@currentx\@clsextension
196     \xdef\@unusedoptionlist{%
197       \ifx\@unusedoptionlist\@empty\else\@unusedoptionlist,\fi
198       \CurrentOption}%
199   \fi}
200 \@onlypreamble\OptionNotUsed
```

`\default@ds` The default default option code. Set by `\@onefilewithoptions` to either `\OptionNotUsed` for classes, or `\@unknownoptionerror` for packages. This may be reset in either case with `\DeclareOption*`.

```
201 % \let\default@ds\OptionNotUsed
```

`\ProcessOptions` `\ProcessOptions` calls `\ds@option` for each known package option, then calls  
`\ProcessOptions*` `\default@ds` for each option on the local options list. Finally resets all the declared options to `\relax`. The empty option does nothing, this has to be reset on the off chance it's set to `\relax` if an empty element gets into the `\@declaredoptions` list.

The star form is similar but executes options given in the order specified in the document, not the order they are declared in the file. In the case of packages, global options are executed before local ones.

```
202 \def\ProcessOptions{%
```

```

203 \let\ds@\empty
204 \edef\@curroptions{\@optionlist{\@currname.\@currentt}}%
205 \ifstar\@xprocessoptions\@processoptions}
206 \@onlypreamble\ProcessOptions

207 \def\@processoptions{%
208   \for\CurrentOption:=\@declaredoptions\do{%
209     \ifx\CurrentOption\empty\else
210       \@expandtwoargs\in@{,\CurrentOption,}{%
211         ,\ifx\@currentt\@clsextension\else\@classoptionslist,\fi
212         \@curroptions,}%
213       \ifin@
214         \@use@option
215         \expandafter\let\csname ds@\CurrentOption\endcsname\empty
216       \fi
217     \fi}%
218   \@processoptions}
219 \@onlypreamble\@processoptions

220 \def\@xprocessoptions{%
221   \ifx\@currentt\@clsextension\else
222     \for\CurrentOption:=\@classoptionslist\do{%
223       \ifx\CurrentOption\empty\else
224         \@expandtwoargs\in@{,\CurrentOption,}{,\@declaredoptions,}%
225       \ifin@
226         \@use@option
227         \expandafter\let\csname ds@\CurrentOption\endcsname\empty
228       \fi
229     \fi}%
230   \fi
231   \@processoptions}
232 \@onlypreamble\@xprocessoptions

```

The common part of \ProcessOptions and \ProcessOptions\*.

```

233 \def\@processoptions{%
234   \for\CurrentOption:=\@curroptions\do{%
235     \ifundefined{ds@\CurrentOption}%
236       {\@use@option
237        \default@ds}%

```

There should not be any non-empty definition of \CurrentOption at this point, as all the declared options were executed earlier. This is for compatibility with 2.09 styles which use \def\ds@... directly, and so have options which do not appear in \@declaredoptions.

```

238     \@use@option}%

```

Clear all the definitions for option code. First set all the declared options to \relax, then reset the ‘default’ and ‘empty’ options. and the lst of declared options.

```

239   \for\CurrentOption:=\@declaredoptions\do{%
240     \expandafter\let\csname ds@\CurrentOption\endcsname\relax}%

241   \let\CurrentOption\empty
242   \let\@fileswith@pti@ns\@fileswith@pti@ns
243   \AtEndOfPackage{\let\@unprocessedoptions\relax}}
244 \@onlypreamble\@processoptions

```

`\@options` `\@options` is a synonym for `\ProcessOptions*` for upward compatibility with L<sup>A</sup>T<sub>E</sub>X 2.09 style files.

```

245 \def\@options{\ProcessOptions*}
246 \@onlypreamble\@options

```

`\@use@option` Execute the code for the current option.

```

247 \def\@use@option{%
248   \@expandtwoargs\@removeelement\CurrentOption
249   \@unusedoptionlist\@unusedoptionlist
250   \csname ds@\CurrentOption\endcsname}
251 \@onlypreamble\@use@option

```

`\ExecuteOptions` `\ExecuteOptions{<option-list>}` executes the code declared for each option.

```

252 \<2kernel>
253 \<latexrelease>\IncludeInRelease{2017/01/01}%
254 \<latexrelease>          {\ExecuteOptions}{Spaces in \ExecuteOptions}%
255 \<*2kernel | latexrelease>
256 \def\ExecuteOptions#1{%

```

Use `\@fortmp` here as it is anyway cleared during `\@for` loop so does not change any existing names.

```

257   \edef\@fortmp{\zap@space#1 \@empty}%
258   \def\reserved@a##1\@nil{%
259     \@for\CurrentOption:=\@fortmp\do
260       {\csname ds@\CurrentOption\endcsname}%
261     \edef\CurrentOption{##1}}%
262   \expandafter\reserved@a\CurrentOption\@nil}
263 \<2kernel | latexrelease>
264 \<latexrelease>\EndIncludeInRelease
265 \<latexrelease>\IncludeInRelease{0000/00/00}%
266 \<latexrelease>          {\ExecuteOptions}{Spaces in \ExecuteOptions}%
267 \<latexrelease>\def\ExecuteOptions#1{%
268 \<latexrelease>   \def\reserved@a##1\@nil{%
269 \<latexrelease>     \@for\CurrentOption:=#1\do
270 \<latexrelease>       {\csname ds@\CurrentOption\endcsname}%
271 \<latexrelease>     \edef\CurrentOption{##1}}%
272 \<latexrelease>   \expandafter\reserved@a\CurrentOption\@nil}
273 \<latexrelease>\EndIncludeInRelease
274 \<*2kernel>
275 \@onlypreamble\ExecuteOptions

```

The top-level commands, which just set some parameters then call the internal command, `\@fileswithoptions`.

`\documentclass` The main new-style class declaration.

```

276 \def\documentclass{%
277   \let\documentclass\@twoclasseserror
278   \if@compatibility\else\let\usepackage\RequirePackage\fi
279   \@fileswithoptions\@clsextension}
280 \@onlypreamble\documentclass

```

`\documentstyle` 2.09 style class ‘style’ declaration.

```

281 \def\documentstyle{%

```

```

282 \makeatletter\input{latex209.def}\makeatother
283 \documentclass}
284 \@onlypreamble\documentstyle

\RequirePackage Load package if not already loaded.
285 \def\RequirePackage{%
286   \@fileswithoptions\@pkgextension}
287 \@onlypreamble\RequirePackage

\LoadClass Load class.
288 \def\LoadClass{%
289   \ifx\@current\@pkgextension
290     \@latex@error
291       {\noexpand\LoadClass in package file}%
292       {You may only use \noexpand\LoadClass in a class file.}%
293   \fi
294   \@fileswithoptions\@clsextension}
295 \@onlypreamble\LoadClass

\@loadwithoptions Pass the current option list on to a class or package. #1 is \@cls-or-pkgextension,
#2 is \RequirePackage or \LoadClass, #3 is the class or package to be loaded.
296 \def\@loadwithoptions#1#2#3{%
297   \expandafter\let\csname opt@#3.#1\expandafter\endcsname
298     \csname opt@#3.\@currname.\@current\endcsname
299   #2{#3}}
300 \@onlypreamble\@loadwithoptions

\LoadClassWithOptions Load class ‘#1’ with the current option list.
301 \def\LoadClassWithOptions{%
302   \@loadwithoptions\@clsextension\LoadClass}
303 \@onlypreamble\LoadClassWithOptions

\RequirePackageWithOptions Load package ‘#1’ with the current option list.
304 \def\RequirePackageWithOptions{%
305   \AtEndOfPackage{\let\@unprocessedoptions\relax}%
306   \@loadwithoptions\@pkgextension\RequirePackage}
307 \@onlypreamble\RequirePackageWithOptions

\usepackage To begin with, \usepackage produces an error. This is reset by \documentclass.
308 \def\usepackage#1{%
309   \@latex@error
310     {\noexpand \usepackage before \string\documentclass}%
311     {\noexpand \usepackage may only appear in the document
312       preamble, i.e.,\MessageBreak
313       between \noexpand\documentclass and
314       \string\begin{document}.}%
315   \@gobble}
316 \@onlypreamble\usepackage

\NeedsTeXFormat Check that the document is running on the correct system.
317 \def\NeedsTeXFormat#1{%
318   \def\reserved@a{#1}%

```

```

319 \ifx\reserved@a\fmtname
320 \expandafter\@needsformat
321 \else
322 \latex@error{This file needs format '\reserved@a'%
323 \MessageBreak but this is '\fmtname'}{%
324 The current input file will not be processed
325 further,\MessageBreak
326 because it was written for some other flavor of
327 TeX.\MessageBreak\@ehd}%

```

If the file is not meant to be processed by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> we stop inputting it, but we do not end the run. We just end inputting the current file.

```

328 \endinput \fi}
329 \@onlypreamble\NeedsTeXFormat

330 \def\@needsformat{%
331 \@ifnextchar[%]
332 \@needsformat
333 {}
334 \@onlypreamble\@needsformat

335 \def\@needsformat[#1]{%
336 \@ifl@t@r\fmtversion{#1}{}%
337 {\latex@warning@no@line
338 {You have requested release '#1' of LaTeX,\MessageBreak
339 but only release '\fmtversion' is available}}}
340 \@onlypreamble\@needsformat

```

`\zap@space` `\zap@space foo`*space*`\@empty` removes all spaces from `foo` that are not protected by `{ }` groups.

```

341 \def\zap@space#1 #2{%
342 #1%
343 \ifx#2\@empty\else\expandafter\zap@space\fi
344 #2}

```

`\@fileswithoptions` The common part of `\documentclass` and `\usepackage`.

```

345 \def\@fileswithoptions#1{%
346 \@ifnextchar[%]
347 {\@fileswithoptions#1}%
348 {\@fileswithoptions#1[]}}
349 \@onlypreamble\@fileswithoptions

350 \def\@fileswithoptions#1[#2]#3{%
351 \@ifnextchar[%]
352 {\@fileswithoptions#1[{#2}]#3}%
353 {\@fileswithoptions#1[{#2}]#3[]}}
354 \@onlypreamble\@fileswithoptions

```

Then we do some work.

First of all, we define the global variables. Then we look to see if the file has already been loaded. If it has, we check that it was first loaded with at least the current options. If it has not, we add the current options to the package options, set the default version to be 0000/00/00, and load the file if we can find it. Then we check the version number.

Finally, we restore the old file name, reset the default option, and we set the catcode of @.

For classes, we can immediately process the file. For other types, #2 could be a comma separated list, so loop through, processing each one separately.

```

355 </2ekernel>
356 <latexrelease>\IncludeInRelease{2017/01/01}%
357 <latexrelease>      {\@fileswith@pti@ns}{ifx tests in \@fileswith@pti@ns}%
358 <*2ekernel | latexrelease>
359 \def\@fileswith@pti@ns#1[#2]#3[#4]{%
360   \ifx#1\@clsextension
361     \ifx\@classoptionslist\relax
362       \xdef\@classoptionslist{\zap@space#2 \@empty}%
363       \def\reserved@a{%
364         \@onefilewithoptions#3[#{#2}][#{#4}]#1%
365         \@documentclasshook}%
366     \else
367       \def\reserved@a{%
368         \@onefilewithoptions#3[#{#2}][#{#4}]#1%
369     \fi
370   \else

```

build up a list of calls to \@onefilewithoptions (one for each package) without thrashing the parameter stack.

```

371   \def\reserved@b##1,{%

```

If #1 is \@nnil we have reached the end of the list (older version used \@nil here but \@nil is undefined so \ifx equal to all undefined commands)

```

372   \ifx\@nnil##1\relax\else

```

If \ifx\@nnil##1\n@nil is true then #1 is (presumably) empty (Older code used \relax which is slightly easier to get into #1 by mistake, which would spoil this test.)

```

373       \ifx\@nnil##1\@nnil\else
374         \noexpand\@onefilewithoptions##1[#{#2}][#{#4}]%
375         \noexpand\@pkgextension
376       \fi
377       \expandafter\reserved@b
378     \fi}%
379     \edef\reserved@a{\zap@space#3 \@empty}%
380     \edef\reserved@a{\expandafter\reserved@b\reserved@a,\@nnil,}%
381   \fi
382   \reserved@a}
383 </2ekernel | latexrelease>

```

```

384 <latexrelease>\EndIncludeInRelease
385 <latexrelease>\IncludeInRelease{0000/00/00}%
386 <latexrelease>      {\@fileswith@pti@ns}{ifx tests in \@fileswith@pti@ns}%
387 <latexrelease>\def\@fileswith@pti@ns#1[#2]#3[#4]{%
388 <latexrelease>   \ifx#1\@clsextension
389 <latexrelease>     \ifx\@classoptionslist\relax
390 <latexrelease>       \xdef\@classoptionslist{\zap@space#2 \@empty}%
391 <latexrelease>       \def\reserved@a{%
392 <latexrelease>         \@onefilewithoptions#3[#{#2}][#{#4}]#1%
393 <latexrelease>         \@documentclasshook}%
394 <latexrelease>     \else

```



```

395 \latexrelease\def\reserved@a{%
396 \latexrelease\@onefilewithoptions#3[#{#2}][#{#4}]#1}%
397 \latexrelease\fi
398 \else
399 \latexrelease\def\reserved@b##1,{%
400 \latexrelease\ifx\@nil##1\relax\else
401 \latexrelease\ifx\relax##1\relax\else
402 \latexrelease\noexpand\@onefilewithoptions##1[#{#2}][#{#4}]%
403 \latexrelease\noexpand\@pkgextension
404 \latexrelease\fi
405 \latexrelease\expandafter\reserved@b
406 \latexrelease\fi}%
407 \latexrelease\edef\reserved@a{\zap@space#3 \@empty}%
408 \latexrelease\edef\reserved@a{%
409 \latexrelease\expandafter\reserved@b\reserved@a,\@nil,}%
410 \latexrelease\fi
411 \latexrelease\reserved@a}
412 \latexrelease\EndIncludeInRelease
413 \*2kernel)
414 \@onlypreamble\@fileswith@ptions

```

Have the main argument as #1, so we only need one \expandafter above.

```

415 \def\@onefilewithoptions#1[#2][#3]#4{%
416 \pushfilename
417 \xdef\@currname{#1}%
418 \global\let\@currentx#4%
419 \let\CurrentOption\@empty
420 \reset@ptions
421 \makeatletter

```

Grab everything in a macro, so the parameter stack is popped before any processing begins.

```

422 \def\reserved@a{%
423 \ifl@aded\@currentx{#1}%
424 {\@if@ptions\@currentx{#1}{#2}{}}%
425 {\@latex@error
426 {Option clash for \@cls@pkg\space #1}%
427 {The package #1 has already been loaded
428 with options:\MessageBreak
429 \space\space[\@optionlist{#1.\@currentx}]\MessageBreak
430 There has now been an attempt to load it
431 with options:\MessageBreak
432 \space\space[#2]\MessageBreak
433 Adding the global options:\MessageBreak
434 \space\space
435 \@optionlist{#1.\@currentx},#2\MessageBreak
436 to your \noexpand\documentclass declaration may fix this.%
437 \MessageBreak
438 Try typing \space <return> \space to proceed.}}}%
439 {\@pass@ptions\@currentx{#2}{#1}%
440 \global\expandafter
441 \let\csname ver@\@currname.\@currentx\endcsname\@empty

```

We initialize \dots-h@@k here and only if we load the file so that it remains undefined otherwise.

```

442 \expandafter\let\csname\@currname.\@current-h@@k\endcsname\@empty
443 \InputIfFileExists
444 {\@currname.\@current}%
445 {}%
446 {\@missingfileerror\@currname\@current}%

```

\@unprocessedoptions will generate an error for each specified option in a package unless a \ProcessOptions has appeared in the package file.

```

447 \let\@unprocessedoptions\@unprocessedoptions
448 \csname\@currname.\@current-h@@k\endcsname
449 \expandafter\let\csname\@currname.\@current-h@@k\endcsname
450 \undefined
451 \@unprocessedoptions}%
452 \@ifl@ter\@current{#1}{#3}{}%
453 {\@latex@warning@no@line
454 {You have requested,\on@line,
455 version\MessageBreak
456 '#3' of \@cls@pkg\space #1,\MessageBreak
457 but only version\MessageBreak
458 '\csname ver@#1.\@current\endcsname'\MessageBreak
459 is available}}%
460 \ifx\@current\@clsextension\let\LoadClass\@twoloadclasserror\fi
461 \@popfilename
462 \@reset@ptions}%
463 \reserved@a}
464 \@onlypreamble\@onefilewithoptions

```

\@@fileswith@pti@ns Save the definition (for error checking).

```

465 \let\@@fileswith@pti@ns\@fileswith@pti@ns
466 \@onlypreamble\@@fileswith@pti@ns

```

\@reset@ptions Reset the default option, and clear lists of declared options.

```

467 \def\@reset@ptions{%
468 \global\ifx\@current\@clsextension
469 \let\default@ds\OptionNotUsed
470 \else
471 \let\default@ds\@unknownoptionerror
472 \fi
473 \global\let\ds@\@empty
474 \global\let\@declaredoptions\@empty}
475 \@onlypreamble\@reset@ptions

```

## 69.1 Hooks

Allow code do be saved to be executed at specific later times.

Save things in macros, I considered using toks registers, (and \addto@hook from the NFSS code, that would require stacking the contents in the case of required packages, so just generate a new macro for each package.

\@begindocumenthook Stuff to appear at the beginning or end of the document.

```

\@enddocumenthook
476 \ifx\@begindocumenthook\undefined
477 \let\@begindocumenthook\@empty

```

```

478 \fi
479 \let\@enddocumenthook\@empty

\g@addto@macro Globally add to the end of a macro.
480 \long\def\g@addto@macro#1#2{%
481   \begingroup
482     \toks@\expandafter{#1#2}%
483     \xdef#1{\the\toks@}%
484   \endgroup}

\AtEndOfPackage The access functions.
\AtEndOfClass 485 \def\AtEndOfPackage{%
\AtBeginDocument 486   \expandafter\g@addto@macro\csname\@currname.\@currentx-h\endcsname}
\AtEndDocument 487 \let\AtEndOfClass\AtEndOfPackage
488 \@onlypreamble\AtEndOfPackage
489 \@onlypreamble\AtEndOfClass

490 \DeclareRobustCommand\AtBeginDocument{\g@addto@macro\@begindocumenthook}
491 \DeclareRobustCommand\AtEndDocument{\g@addto@macro\@enddocumenthook}
492 \@onlypreamble\AtBeginDocument

\@cls@pkg The current file type.
493 \def\@cls@pkg{%
494   \ifx\@currentx\@clsextension
495     document class%
496   \else
497     package%
498   \fi}
499 \@onlypreamble\@cls@pkg

\@unknownoptionerror Bad option.
500 \def\@unknownoptionerror{%
501   \@latex@error
502     {Unknown option ‘\CurrentOption’ for \@cls@pkg\space‘\@currname’}%
503     {The option ‘\CurrentOption’ was not declared in
504       \@cls@pkg\space‘\@currname’, perhaps you\MessageBreak
505       misspelled its name.
506       Try typing \space <return>
507       \space to proceed.}}
508 \@onlypreamble\@unknownoptionerror

\@@unprocessedoptions Declare an error for each option, unless a \ProcessOptions occurred.
509 \def\@@unprocessedoptions{%
510   \ifx\@currentx\@pkgextension
511     \edef\@curroptions{\@optionlist{\@currname.\@currentx}}%
512     \@for\CurrentOption:=\@curroptions\do{%
513       \ifx\CurrentOption\@empty\else\@unknownoptionerror\fi}%
514   \fi}
515 \@onlypreamble\@unprocessedoptions
516 \@onlypreamble\@@unprocessedoptions

\@badrequireerror \RequirePackage or \LoadClass occurs in the options section.
517 \def\@badrequireerror#1[#2]#3[#4]{%
518   \@latex@error

```

```

519     {\noexpand\RequirePackage or \noexpand\LoadClass
520      in Options Section}%
521     {The \@cls@pkg\space '@currname' is defective.\MessageBreak
522      It attempts to load '#3' in the options section, i.e.,\MessageBreak
523      between \noexpand\DeclareOption and \string\ProcessOptions.}}
524 \@onlypreamble\@badrequireerror

\@twoloadclasserror Two \LoadClass in a class.
525 \def\@twoloadclasserror{%
526   \@latex@error
527   {Two \noexpand\LoadClass commands}%
528   {You may only use one \noexpand\LoadClass in a class file}}
529 \@onlypreamble\@twoloadclasserror

\@twoclasseserror Two \documentclass or \documentstyle.
530 \def\@twoclasseserror#1{%
531   \@latex@error
532   {Two \noexpand\documentclass or \noexpand\documentstyle commands}%
533   {The document may only declare one class.}\@gobble}
534 \@onlypreamble\@twoclasseserror

```

## 69.2 Providing shipment

```

\two@digits Prefix a number less than 10 with '0'.
535 \def\two@digits#1{\ifnum#1<10 0\fi\number#1}

\filecontents This environment implements inline files. The star-form does not write extra
\endfilecontents comments into the file.

536 % \changes{v1.3a}{2019/07/01}{Support UTF8 and spaces in
537 %                               filecontents environment file name}
538 % \changes{v1.3b}{2019/08/27}{Make various commands robust}
539 % \changes{v1.3c}{2019/09/11}{Support optional argument for filecontents}
540 %
541 (/2ekernel)
542 (*2ekernel | latexrelease)
543 (latexrelease)\IncludeInRelease{2019/10/01}%
544 (latexrelease)      {\filec@ntents}{Spaces in file names + optional arg}%
545 %

We use @tempswa to mean no preamble writing and reuse @filesw to indicate no
overwriting:

546 \def\filecontents{\@tempswatrue\@fileswtrue
547   \@ifnextchar[\filec@ntents@opt\filec@ntents
548 }
549 \@namedef{filecontents*}{\@tempswafalse\@fileswtrue
550   \@ifnextchar[\filec@ntents@opt\filec@ntents
551 }

To handle the optional argument we execute for each option the command
\filec@ntents@OPTION if it exist or complain about unknown option.

552 \def\filec@ntents@opt[#1]{%
553   \@for\@tempa:=#1\do{%
554     \ifcsname filec@ntents@\@tempa\endcsname

```

```

555     \csname filec@ntents@\@tempa\endcsname
556     \else
557     \@latex@error{Unknown filecontents option #1}%
558     {Valid options are force (or overwrite), nosearch, noheader}%
559     \fi}%
560 \filec@ntents
561 }

```

Option `force`) (or `overwrite`) changes the overwriting switch

```

562 \let\filec@ntents@force\@fileswfalse
563 \let\filec@ntents@overwrite\@fileswfalse % alternative name

```

and option `noheader` the preamble switch (which is equivalent to using the star form of the environment).

```

564 \let\filec@ntents@noheader\@tempswafalse

```

Option `nosearch` only checks the current directory not the how T<sub>E</sub>X tree for the existence of the file to write.

```

565 \def\filec@ntents@nosearch{%
566   \let\filec@ntents@checkdir\@currdir
567   \def\filec@ntents@where{in current directory}}

```

By default we search the whole tree:

```

568 \let\filec@ntents@checkdir\@empty
569 \def\filec@ntents@where{exists on the system}

```

```

570 \begingroup%
571 \@tempcnta=1
572 \loop
573   \catcode\@tempcnta=12 %
574   \advance\@tempcnta@ne %
575   \ifnum\@tempcnta<32 %
576   \repeat %
577   \catcode'\*=11 %
578   \catcode'\^^M\active%
579   \catcode'\^^L\active\let^^L\relax%
580   \catcode'\^^I\active%

581 \gdef\filec@ntents#1{%
582   \set@curr@file{\filec@ntents@checkdir#1}%
583   \edef\q@curr@file{\expandafter\quote@name\expandafter{\@curr@file}}%
584   \openin\@inputcheck\q@curr@file \space %
585   \ifeof\@inputcheck%
586     \@latex@warning@no@line%
587     {Writing file '\@currdir\@curr@file'}%

588   \chardef\reserved@c15 %
589   \ch@ck7\reserved@c\write%
590   \immediate\openout\reserved@c\q@curr@file\relax%
591   \else%

592   \if@filesw%
593     \@latex@warning@no@line%
594     {File '\@curr@file' already \filec@ntents@where.\MessageBreak%
595     Not generating it from this source}%
596     \let\write\@gobbletwo%
597     \let\closeout\@gobble%
598   \else%

```

If we are overwriting, we try to make sure that the user is not by mistake overwriting the input file (`\jobname`). Of course, this only works for input files ending in `.tex`. If a different extension is used there is no way to see that we are overwriting ourselves!

```

599      \edef\reserved@a{#1}%
600      \edef\reserved@a{\detokenize\expandafter{\reserved@a}}%
601      \edef\reserved@b{\detokenize\expandafter{\jobname}}%
602      \ifx\reserved@a\reserved@b%
603        \@fileswtrue%
604      \else%
605        \edef\reserved@b{\reserved@b\detokenize{.tex}}%
606        \ifx\reserved@a\reserved@b
607          \@fileswtrue%
608        \fi%
609      \fi%

```

We allocate a write channel but we open it only if it is (hopefully) safe. If not opened that means we are going to write on the terminal.

```

610      \chardef\reserved@c15 %
611      \ch@ck7\reserved@c\write%
612      \if@filesw% % Foul ... trying to overwrite \jobname!
613      \@latex@error{Trying to overwrite '\jobname.tex'}{You can't %
614        write to the file you a reading from!\MessageBreak%
615        Data is written to screen instead.}%
616      \else%
617        \@latex@warning@no@line%
618        {Writing or overwriting file '@currdir\currfile'}%
619        \immediate\openout\reserved@c#1\relax%
620      \fi%
621    \fi%
622  \fi%

```

Closing the `\@inputcheck` is done here to avoid having to do this in each branch.

```

623  \closein\@inputcheck%
624  \if@tempsw%
625    \immediate\write\reserved@c{%
626      \@percentchar\@percentchar\space%
627      \expandafter\@gobble\string\LaTeX2e file '@currfile'^^J%
628      \@percentchar\@percentchar\space generated by the %
629      '@currenvir' \expandafter\@gobblefour\string\newenvironment^^J%
630      \@percentchar\@percentchar\space from source '\jobname' on %
631      \number\year/\two@digits\month/\two@digits\day.^~J%
632      \@percentchar\@percentchar}%
633  \fi%
634  \let\do\@makeother\dospecials%

```

If there are active characters in the upper half (e.g., from `inputenc` there would be confusion so we render everything harmless.

```

635  \count@ 128\relax%
636  \loop%
637    \catcode\count@ 11\relax%
638    \advance\count@ \@ne%
639    \ifnum\count@<\ccclvi%
640  \repeat%

```

```

641 \edef\E{\@backslashchar end\string{\@currentenv\string}}%
642 \edef\reserved@b{%
643   \def\noexpand\reserved@b%
644     #####1\E####2\E####3\relax}%
645 \reserved@b{%
646   \ifx\relax##3\relax%

There was no \end{filecontents}

647   \immediate\write\reserved@c{##1}%
648   \else%

There was a \end{filecontents}, so stop this time.

649   \edef^^M{\noexpand\end{\@currentenv}}}%
650   \ifx\relax##1\relax%
651   \else%

Text before the \end, write it with a warning.

652     \latex@warning{Writing text '##1' before %
653       \string\end{\@currentenv}\MessageBreak as last line of \@curr@file}%
654     \immediate\write\reserved@c{##1}%
655     \fi%
656     \ifx\relax##2\relax%
657     \else%

Text after the \end, ignore it with a warning.

658     \latex@warning{%
659       Ignoring text '##2' after \string\end{\@currentenv}}%
660     \fi%
661     \fi%
662     ^^M}%

663 \catcode'\^^L\active%
664 \let\L\@undefined%
665 \def^^L{\expandafter\ifx\csname L\endcsname\relax\fi ^^J^^J}%
666 \catcode'\^^I\active%
667 \let\I\@undefined%
668 \def^^I{\expandafter\ifx\csname I\endcsname\relax\fi\space}%
669 \catcode'\^^M\active%
670 \edef^^M##1^^M{%
671   \noexpand\reserved@b##1\E\E\relax}}%
672 \endgroup%

673 </2ekernel | latexrelease>
674 <latexrelease>\EndIncludeInRelease
675 <latexrelease>\IncludeInRelease{0000/00/00}%
676 <latexrelease>      {\filecontents}{Spaces in file names + optional arg}%
677 <latexrelease>
678 <latexrelease>\let\filecontents@opt      \@undefined
679 <latexrelease>\let\filecontents@force    \@undefined
680 <latexrelease>\let\filecontents@overwrite \@undefined
681 <latexrelease>\let\filecontents@noheader  \@undefined
682 <latexrelease>\let\filecontents@nosearch  \@undefined
683 <latexrelease>\let\filecontents@checkdir  \@undefined
684 <latexrelease>\let\filecontents@where    \@undefined
685 <latexrelease>
686 <latexrelease>\begingroup%

```

```

687 \latexrelease\@tempcnta=1
688 \latexrelease\loop
689 \latexrelease\catcode\@tempcnta=12 %
690 \latexrelease\advance\@tempcnta\@ne %
691 \latexrelease\ifnum\@tempcnta<32 %
692 \latexrelease\repeat %
693 \latexrelease\catcode'\*=11 %
694 \latexrelease\catcode'\^M\active%
695 \latexrelease\catcode'\^L\active\let\^L\relax%
696 \latexrelease\catcode'\^I\active%
697 \latexrelease
698 \latexrelease\gdef\filecontents#1{%
699 \latexrelease\openin\@inputcheck#1 %
700 \latexrelease\ifeof\@inputcheck%
701 \latexrelease\@latex@warning@no@line%
702 \latexrelease{Writing file '\currdir#1'}%
703 \latexrelease\chardef\reserved@c15 %
704 \latexrelease\ch@ck7\reserved@c\write%
705 \latexrelease\immediate\openout\reserved@c#1\relax%
706 \latexrelease\else%
707 \latexrelease\closein\@inputcheck%
708 \latexrelease\@latex@warning@no@line%
709 \latexrelease{File '#1' already exists on the system.\MessageBreak%
710 \latexreleaseNot generating it from this source}%
711 \latexrelease\let\write\@gobbletwo%
712 \latexrelease\let\closeout\@gobble%
713 \latexrelease\fi%
714 \latexrelease\if@tempswa%
715 \latexrelease\immediate\write\reserved@c{%
716 \latexrelease\@percentchar\@percentchar\space%
717 \latexrelease\expandafter\@gobble\string\LaTeX2e file '#1'^^J%
718 \latexrelease\@percentchar\@percentchar\space generated by the %
719 \latexrelease'\@currenvir' \expandafter\@gobblefour\string\newenvironment^^J%
720 \latexrelease\@percentchar\@percentchar\space from source '\jobname' on %
721 \latexrelease\number\year/\two@digits\month/\two@digits\day.^^J%
722 \latexrelease\@percentchar\@percentchar}%
723 \latexrelease\fi%
724 \latexrelease\let\do\@makeother\dospecials%
725 \latexrelease\count@ 128\relax%
726 \latexrelease\loop%
727 \latexrelease\catcode\count@ 11\relax%
728 \latexrelease\advance\count@ \@ne%
729 \latexrelease\ifnum\count@<\ccclvi%
730 \latexrelease\repeat%
731 \latexrelease\edef\E{\@backslashchar end\string{\@currenvir\string}}%
732 \latexrelease\edef\reserved@b{%
733 \latexrelease\def\noexpand\reserved@b%
734 \latexrelease####1\E####2\E####3\relax}%
735 \latexrelease\reserved@b{%
736 \latexrelease\ifx\relax##3\relax%
737 \latexrelease\immediate\write\reserved@c{##1}%
738 \latexrelease\else%
739 \latexrelease\edef^^M{\noexpand\end{\@currenvir}}%
740 \latexrelease\ifx\relax##1\relax%

```



```

741 \latexrelease> \else%
742 \latexrelease> \latex@warning{Writing text ‘##1’ before %
743 \latexrelease> \string\end{\@currenvir}\MessageBreak as last line of #1}%
744 \latexrelease> \immediate\write\reserved@c{##1}%
745 \latexrelease> \fi%
746 \latexrelease> \ifx\relax##2\relax%
747 \latexrelease> \else%
748 \latexrelease> \latex@warning{%
749 \latexrelease> Ignoring text ‘##2’ after \string\end{\@currenvir}}%
750 \latexrelease> \fi%
751 \latexrelease> \fi%
752 \latexrelease> ^^M}%
753 \latexrelease>
754 \latexrelease> \catcode‘^^L\active%
755 \latexrelease> \let\L\undefined%
756 \latexrelease> \def^^L{\expandafter\ifx\csname L\endcsname\relax\fi ^^J^^J}%
757 \latexrelease> \catcode‘^^I\active%
758 \latexrelease> \let\I\undefined%
759 \latexrelease> \def^^I{\expandafter\ifx\csname I\endcsname\relax\fi\space}%
760 \latexrelease> \catcode‘^^M\active%
761 \latexrelease> \edef^^M##1^^M{%
762 \latexrelease> \noexpand\reserved@b##1\E\E\relax}}%
763 \latexrelease> \endgroup%
764 \latexrelease> \EndIncludeInRelease
765 \<2ekernel)

766 \beginingroup
767 \catcode‘|= \catcode‘\%
768 \catcode‘\%=12
769 \catcode‘\*=11
770 \gdef\@percentchar{%
771 \gdef\endfilecontents{|
772 \immediate\closeout\reserved@c
773 \def\T##1##2##3{|
774 \ifx##1\@undefined\else
775 \latex@warning@no@line{##2 has been converted to Blank ##3e}|
776 \fi}|
777 \T\L{Form Feed}{Lin}|
778 \T\I{Tab}{Spac}|
779 \immediate\write\@unused{}}
780 \global\let\endfilecontents*\endfilecontents

We no longer prevent the code to be used after begin document (no rollback needed
for this change).

781 %\@onlypreamble\filecontents
782 %\@onlypreamble\endfilecontents
783 %\@onlypreamble\filecontents*
784 %\@onlypreamble\endfilecontents*
785 \endgroup
786 %\@onlypreamble\filec@ntents

```

## 70 Package/class rollback mechanism

```
787 \</2ekernel)
```

```

788 (*2ekernel | latexreleasefirst)

\pkgcls@debug For testing we have a few extra lines of code that by default do nothing but one
              can set \pkgcls@debug to \typeout to get extra info. Sometime in the future
              this will be dropped.
789 (*tracerollback)
790 %\let\pkgcls@debug\typeout
791 \let\pkgcls@debug\@gobble
792 </tracerollback>

\requestedLaTeXdate The macro (!) \requestedLaTeXdate holds the globally requested rollback date
                    (via latexrelease) or zero if no such request was made.
793 \def\requestedLaTeXdate{0}

\pkgcls@targetdate If a rollback for a package or class is requested then \pkgcls@targetdate holds the
\pkgcls@targetlabel requested date as a number YYYYMMDD (if there was one, otherwise the value
\pkgcls@innerdate of \requestedLaTeXdate) and \pkgcls@targetlabel will be empty. If there was
                    a request for a named version then \pkgcls@targetlabel holds the version name
                    and \pkgcls@targetdate is set to 1.
                    \pkgcls@targetdate=0 is used to indicate that there was no rollback request.
                    While loading an old release \pkgcls@targetdate is also reset to zero so that
                    \DeclareRelease declarations are bypassed.
                    In contrast \pkgcls@innerdate will always hold the requested date (in a macro
                    not a counter) if there was one, otherwise, e.g., if there was no request or a request
                    to a version name it will contain TeX largest legal number. While loading a file
                    this can be used to provide conditionals that select code based on the request.

794 \ifx\pkgcls@targetdate\@undefined
795   \newcount\pkgcls@targetdate
796 \fi
797 \let\pkgcls@targetlabel\@empty
798 \def\pkgcls@innerdate{\maxdimen}

\pkgcls@candidate When looping through the \DeclareRelease declarations we record if the release
\pkgcls@releasedate is the best candidate we have seen so far. This is recorded in \pkgcls@candidate
                    and we update it whenever we see a better one.
                    In \pkgcls@releasedate we keep track of the release date of that candidate.

799 \let\pkgcls@candidate\@empty
800 \let\pkgcls@releasedate\@empty

\load@onefilewithoptions the best place to add the rollback code is at the point where \@onefilewithoptions
\@onefilewithoptions is called to load a single class or package.
                    To make things easy we save the old definition as \load@onefilewithoptions
                    and then provide a new interface.
                    Important: as this code is also unconditionally placed into latexrelease we can
                    only do this name change once otherwise both macros will contain the same code.

801 \ifx\load@onefilewithoptions\@undefined
802   \let\load@onefilewithoptions\@onefilewithoptions

803   \def\@onefilewithoptions#1[#2][#3]#4{%

First a bit of tracing normally disabled.
804 (*tracerollback)

```

```

805 \pkgcls@debug{--- File loaded request (\noexpand\usepackage or ...)}%
806 \pkgcls@debug{\@spaces 1: #1}%
807 \pkgcls@debug{\@spaces 2: #2}%
808 \pkgcls@debug{\@spaces 3: #3}%
809 \pkgcls@debug{\@spaces 4: #4}%
810 /tracereollback)

```

Two of the arguments are needed later on in error/warning messages so we save them.

```

811 \def\pkgcls@name{#1}%           % for info message
812 \def\pkgcls@arg {#3}%          % for info message

```

then we parse the final optional argument to determine if there is a specific rollback request for the current file. This will set `\pkgcls@targetdate`, `\pkgcls@targetlabel` and `\pkgcls@mindate`.

```

813 \pkgcls@parse@date@arg{#3}%

```

When determining the correct release to load we keep track of candidates in `\pkgcls@candidate` and initially we don't have any:

```

814 \let\pkgcls@candidate\@empty

```

If we had a rollback request then #3 may contain data but not necessarily a “minimal date” so instead of passing it on we pass on the content of `\pkgcls@mindate`. We need to pass the value not the command, otherwise nested packages may pick up the wrong information.

```

815 \begingroup
816 \edef\reserved@a{%
817   \endgroup
818   \unexpanded{\load@onefilewithoptions#1[#2]}%
819   [\pkgcls@mindate]%
820   \unexpanded{#4}}%
821 \reserved@a
822 }
823 \fi

```

`\pkgcls@parse@date@arg` The `\pkgcls@parse@date@arg` command parses the second optional argument of `\usepackage`, `\RequirePackage` or `\documentclass` for a rollback request setting the values of `\pkgcls@targetdate` and `\pkgcls@targetlabel`.

This optional argument has a dual purpose: If it just contains a date string then this means that the package should have at least that date (to ensure that a certain feature is actually available, or a certain bug has been fixed). When the package gets loaded the information in `\Provides...` will then be checked against this request.

But if it starts with an equal sign followed by a date string or followed by a version name then this means that we should roll back to the state of the package at the date or to the version with the requested name.

If there was no optional argument or the optional argument does not start with “=” then the `\pkgcls@targetdate` is set to the date of the overall rollback request (via `latexrelease`) or if that was not given it is set to 0. In either case `\pkgcls@targetlabel` will be made empty.

If the argument doesn't start with “=” then it is supposed to be a “minimal date” and we therefore save the value in `\pkgcls@mindate`, otherwise this macro is made empty.

So in summary we have:

Input	<code>\pkgcls@targetdate</code>	<code>\pkgcls@targetlabel</code>	<code>\pkgcls@mindate</code>
<code>&lt;empty&gt;</code>	<code>→ &lt;global-rollbackdate-as-number&gt;</code>	<code>&lt;empty&gt;</code>	<code>&lt;empty&gt;</code>
<code>&lt;date&gt;</code>	<code>→ &lt;global-rollbackdate-as-number&gt;</code>	<code>&lt;empty&gt;</code>	<code>&lt;date&gt;</code>
<code>=&lt;date&gt;</code>	<code>→ &lt;date-as-number&gt;</code>	<code>&lt;empty&gt;</code>	<code>&lt;empty&gt;</code>
<code>=&lt;version&gt;</code>	<code>→ 1</code>	<code>&lt;version&gt;</code>	<code>&lt;empty&gt;</code>
<code>&lt;other&gt;</code>	<code>→ &lt;global-rollbackdate-as-number&gt;</code>	<code>&lt;empty&gt;</code>	<code>&lt;other&gt;</code>

where `<global-rollbackdate-as-number>` is a date request given via `latexrelease` or if there wasn't one 0.

```
824 \def\pkgcls@parse@date@arg #1{%
```

If the argument is empty we use the rollback date from `latexrelease` which has the value of zero if there was no rollback request. The label and the minimal date is made empty in that case.

```
825 \ifx\@nil#1\@nil
826 \pkgcls@targetdate\requestedLaTeXdate\relax
827 \let\pkgcls@targetlabel\@empty
828 \let\pkgcls@mindate\@empty
```

Otherwise we parse the argument further, checking for a = as the first character. We append a = at the end so that there is at least one such character in the argument.

```
829 \else
830 \pkgcls@parse@date@arg#1=\@nil\relax
831 \fi
832 }
```

The actual parsing work then happens in `\pkgcls@parse@date@arg@:`

```
833 \def\pkgcls@parse@date@arg@#1=#2\@nil{%
```

We set `\pkgcls@targetdate` depending on the parsing result; the code is expandable so we can do the parsing as part of the assignment.

```
834 \pkgcls@targetdate
```

If a = was in first position then #1 will be empty. In that case #2 will be the original argument with a = appended.

This can be parsed with `\@parse@version`, the trailing character is simply ignored. This macro returns the parsed date as a number (or zero if it wasn't a date) and accepts both YYYY/MM/DD and YYYY-MM-DD formats.

```
835 \ifx\@nil#1\@nil
836 \@parse@version0#2//00\@nil\relax
```

Whatever is returned is thus assigned to `\pkgcls@targetdate` and therefore we can now test its value. If the value is zero we assume that the remaining argument string represents a version and change `\pkgcls@targetdate` and set `\pkgcls@targetlabel` to the version name (after stripping off the trailing =).

```
837 \ifnum \pkgcls@targetdate=\z@
838 \pkgcls@targetdate\@ne
839 \def\pkgcls@innerdate{\maxdimen}%
840 \pkgcls@parse@date@arg@version#2%
841 \else
842 \edef\pkgcls@innerdate{\the\pkgcls@targetdate}%
843 \fi
844 \let\pkgcls@mindate\@empty
845 \else
```

If #1 was not empty then there wasn't a = character in first position so we are dealing either with a “minimum date” or with some incorrect data. We assume the former and make the following assignments (the first one finishing the assignment of \pkgcls@targetdate):

```
846 \requestedLaTeXdate\relax
847 \let\pkgcls@targetlabel\empty
848 \def\pkgcls@innerdate{\maxdimen}%
849 \def\pkgcls@mindate{#1}%
```

If the min-date is after the requested rollback date (if there is any, i.e., if it is not zero) then we have a conflict and therefore issue a warning.

```
850 \ifnum \pkgcls@targetdate > \z@
851 \ifnum \@parse@version0#1//00\@nil > \pkgcls@targetdate
852 \latex@warning@no@line{Suspicious rollback/min-date date given\MessageBreak
853 A minimal date of #1 has been specified for
854 \ccls@pkg\MessageBreak '\pkgcls@name'.\MessageBreak
855 But this is in conflict
856 with a rollback request to \requestedpatchdate}
857 \fi
858 \fi
859 \fi
860 }
```

Strip off the trailing = and assign the version name to \pkgcls@targetlabel.

```
861 \def\pkgcls@parse@date@arg@version#1={%
862 \def\pkgcls@targetlabel{#1}}
```

**\DeclareRelease** First argument is the “name” of the release and it can be left empty if one doesn't like to give a name to the release. The second argument is that from which on this release was available (or should be used in case of minor updates). The final argument is the external file name of this release, by convention this should be *<pkg/cls-name>-<date>.<extension>* but this is not enforced and through this argument one can overwrite it.

```
863 \def\DeclareRelease#1#2#3{%
864 \ifnum\pkgcls@targetdate>\z@ % some sort of rollback request
865 (*traceroollback)
866 \pkgcls@debug{---\string\DeclareRelease:}%
867 \pkgcls@debug{\@spaces 1: #1}%
868 \pkgcls@debug{\@spaces 2: #2}%
869 \pkgcls@debug{\@spaces 3: #3}%
870 </traceroollback>
```

If the date argument #2 is empty we are dealing with a special release that should be only accessible via its name; a typical use case would be a “beta” release. So if we are currently processing a date request we ignore it and otherwise we check if we can match the name and if so load the corresponding release file.

```
871 \ifx\@nil#2\@nil
872 \ifnum\pkgcls@targetdate=\@ne % named request
873 \def\reserved@a{#1}%
874 \ifx\pkgcls@targetlabel\reserved@a
875 \pkgcls@use@this@release{#3}{}%
876 (*traceroollback)
877 \else
878 \pkgcls@debug{Label doesn't match}%
```

```

879 </tracerollback>
880     \fi
881 < *tracerollback>
882     \else
883         \pkgcls@debug{Date request: ignored}%
884 </tracerollback>
885     \fi
886     \else

```

If the value of `\pkgcls@targetdate` is greater than 1 (or in reality greater than something like 19930101) we are dealing with a rollback request to a specific date.

```

887     \ifnum\pkgcls@targetdate>\@ne % a real request

```

So we parse the date of this release to check if it is before or after the request date.

```

888         \ifnum\@parse@version#2//00\@nil
889             >\pkgcls@targetdate

```

If it is after we have to distinguish between two cases: If there was an earlier candidate we use that one because the other is too late, but if there wasn't one (i.e., if current release is the oldest that exists) we use it as the best choice. However in that case something is wrong (as there shouldn't be a rollback to a date where a package used doesn't yet exists. So we make a complained to the user.

```

890         \ifx\pkgcls@candidate\@empty
891             \pkgcls@rollbackdate@error{#2}%
892             \pkgcls@use@this@release{#3}{#2}%
893         \else
894             \pkgcls@use@this@release\pkgcls@candidate
895                                     \pkgcls@releasedate
896         \fi
897     \else

```

Otherwise, if the release date of this version is before the target rollback and we record it as a candidate. But we don't use it yet as there may be another release which is still before the target rollback.

```

898         \def\pkgcls@candidate{#3}%
899         \def\pkgcls@releasedate{#2}%
900 < *tracerollback>
901         \pkgcls@debug{New candidate: #3}%
902 </tracerollback>
903     \fi
904     \else

```

If we end up in this branch we have a named version request. So we check if `\pkgcls@targetlabel` matches the current name and if yes we use this release immediately, otherwise we do nothing as a later declaration may match it.

```

905         \def\reserved@a{#1}%
906         \ifx\pkgcls@targetlabel\reserved@a
907             \pkgcls@use@this@release{#3}{#2}%
908 < *tracerollback>
909         \else
910             \pkgcls@debug{Label doesn't match}%
911 </tracerollback>
912         \fi
913     \fi

```

```

914 \fi
915 \fi
916 }

```

`\pkgcls@use@this@release` If a certain release has been selected (stored in the external file given in #1) we need to input it and afterwards stop reading the current file.

```

917 \def\pkgcls@use@this@release#1#2{%

```

Before that we record the selection made inside the transcript.

```

918 \pkgcls@show@selection{#1}{#2}%

```

We then set the `\pkgcls@targetdate` to zero so that any `\DeclareRelease` or `\DeclareCurrentRelease` in the file we now load are bypassed<sup>10</sup> and then we finally load the correct release.

After loading that file we need to stop reading the current file so we issue `\endinput`. Note that the `\relax` before that is essential to ensure that the `\endinput` is only happening after the file has been fully processed, otherwise it would act after the first line of the `\@@input`!

```

919 \pkgcls@targetdate\z@
920 \@@input #1\relax
921 \endinput
922 }

```

`\pkgcls@show@selection` This command records what selection was made. As that is needed in two places (and it is rather lengthy) it was placed in a separate command. The first argument is the name of the external file that is being loaded and is only needed for debugging. The second argument is the date that corresponds to this file and it is used as part of the message.

```

923 \def\pkgcls@show@selection#1#2{%
924 (*traceroollback)
925 \pkgcls@debug{Result: use #1}%
926 /traceroollback)
927 \GenericInfo
928 {\@spaces\@spaces\space}{Rollback for
929 \@cls@pkg\space'\@currname' requested ->
930 \ifnum\pkgcls@targetdate>\@ne
931 date
932 \ifnum\requestedLaTeXdate=\pkgcls@targetdate
933 \requestedpatchdate
934 \else
935 \expandafter\@gobble\pkgcls@arg
936 \fi.\MessageBreak

```

Instead of “best approximation” we could say that we have been able to exactly match the date (if it is exact), but that would mean extra tests without much gain, so not done.

```

937 Best approximation is
938 \else
939 version '\pkgcls@targetlabel'.\MessageBreak
940 This corresponds to

```

---

<sup>10</sup>The older release may also have such declarations inside if it was a simply copy of the `.sty` or `.cls` file current at that date. Removing these declarations would make the file load a tiny bit faster, but this way it works in any case.

```

941 \fi
942 \ifx\@nil#2\@nil
943     a special release%
944 \else
945     the release introduced on #2%
946 \fi
947 \@gobble}%
948 }

```

**\pkgcls@rollbackdate@error** This is called if the requested rollback date is earlier than the earliest known release of a package or class.

A similar error is given if global rollback date and min-date on a specific package conflict with each other, but that case is happens only once so it is inlined.

```

949 \def\pkgcls@rollbackdate@error#1{%
950 \latex@error{Suspicious rollback date given}%
951 {The \cls@pkg\space'\@currname' claims that it
952 came into existence on #1 which\MessageBreak
953 is after your requested rollback date --- so
954 something is wrong here.\MessageBreak
955 Continue and we use the earliest known release.}}

```

**\DeclareCurrentRelease** This declares the date (and possible name) of the current version of a package or class.

```

956 \def\DeclareCurrentRelease#1#2{%

```

First we test if **\pkgcls@targetdate** is greater than zero, otherwise this code is bypassed (as there is no rollback request).

```

957 \ifnum\pkgcls@targetdate>\z@ % some sort of rollback request
958 (*tracerollback)
959 \pkgcls@debug{---DeclareCurrentRelease}%
960 \pkgcls@debug{ 1: #1}%
961 \pkgcls@debug{ 2: #2}%
962 /tracerollback)

```

If the value is greater than 1 we have to deal with a date request, so we parse **#2** as a date and compare it with **\pkgcls@targetdate**.

```

963 \ifnum\pkgcls@targetdate>\@ne % a date request
964 \ifnum\@parse@version#2//00\@nil
965 >\pkgcls@targetdate

```

If it is greater that means the release date if this file is later than the requested rollback date. Again we have two cases: If there was a previous candidate release we use that one as the current release is too young, but if there wasn't we have to use this release nevertheless as there isn't any alternative.

However this case can only happen if there is a **\DeclareCurrentRelease** but no declared older releases (so basically the use of the declaration is a bit dubious).

```

966 \ifx\pkgcls@candidate\@empty
967 \pkgcls@rollbackdate@error{#2}%
968 \else
969 \pkgcls@use@this@release\pkgcls@candidate
970 \pkgcls@releasedate
971 \fi

```



Otherwise the current file is the right release, so we record that in the transcript and then carry on.

```

972     \else
973     \pkgcls@show@selection{current version}{#2}%
974     \fi
975     \else % a label request

```

Otherwise we have a rollback request to a named version so we check if that fits the current name and if not give an error as this was the last possible opportunity.

```

976     \def\reserved@a{#1}%
977     \ifx\pkgcls@targetlabel\reserved@a
978     \pkgcls@show@selection{current version}{#2}%
979     \else
980     \@latex@error{Requested version '\pkgcls@targetlabel' for
981     \cls@pkg\space'\@currname' is unknown}\@ehc
982     \fi
983     \fi
984 \fi
985 }

```

**\IfTargetDateBefore** This enables a simple form of conditional code inside a class or package file. If there is a date request and the request date is earlier than the first argument the code in the second argument is processed otherwise the code in the third argument is processed. If there was no date request then we also execute the third argument, i.e., we will get the “latest” version of the file.

Most often the second argument (before-date-code) will be empty.

```

986 \DeclareRobustCommand\IfTargetDateBefore[1]{%
987   \ifnum\pkgcls@innerdate <%
988     \expandafter\@parse@version\expandafter0#1//00\@nil
989     \typeout{Exclude code introduced on #1}%
990     \expandafter\@firstoftwo
991   \else
992     \typeout{Include code introduced on #1}%
993     \expandafter\@secondoftwo
994   \fi
995 }

996 </2ekernel | latexreleasefirst>

```

## 71 After Preamble

Finally we declare a package that allows all the commands declared above to be `\onlypreamble` to be used after `\begin{document}`.

```

997 (*afterpreamble)
998 \NeedsTeXFormat{LaTeX2e}
999 \ProvidesPackage{pkgindoc}
1000     [1994/10/20 v1.1 Package Interface in Document (DPC)]
1001 \def\reserved@a#1\do\@classoptionslist#2\do\filecontents#3\relax{%
1002   \gdef\@preamblecmds{#1#3}}
1003 \expandafter\reserved@a\@preamblecmds\relax
1004 </afterpreamble>

```

## File M

# lthyphen.dtx

This file contains the code for loading hyphenation patterns into L<sup>A</sup>T<sub>E</sub>X. Most of this will end up in a file called `hyphen.ltx`. If you wish to customize your L<sup>A</sup>T<sub>E</sub>X system in respect of hyphenation patterns, write a file `hyphen.cfg`. If this file exists, it will be loaded instead of `hyphen.ltx`. See the comments below for additional information.

To produce the printed version of this file the following code is used. It can be extracted with the DOCSTRIP program, or one can run this file directly through L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

```
1 (*driver)
2 \documentclass{ltxdoc}
3 \begin{document}
4 \DocInput{lthyphen.dtx}
5 \end{document}
6 \</driver>
```

The default file `hyphen.ltx` loads hyphenation patterns for US english. If you want to load additional or other hyphenation patterns, you should create a file `hyphen.cfg`. This is best done by starting from `hyphen.ltx`.

For backward compatibility, the default file, `hyphen.ltx`, first tries to load the file `hyphen.tex`. If this file exists, an information message is issued and the appropriate defaults for T<sub>E</sub>X's internal parameters are set: `\language` is initialized to 0, and `\lefthyphenmin` and `\righthyphenmin` to 2 and 3, respectively, to disallow x- or -xx breaks.

```
7 (*default)
8 \InputIfFileExists{hyphen.tex}%
9   {\message{Loading hyphenation patterns for US english.}}%
10   \language=0
11   \lefthyphenmin=2 \righthyphenmin=3 }%
```

Otherwise, since we cannot do anything without any hyphenation patterns, an error message is printed and the IniT<sub>E</sub>X run is terminated by invoking `\@@end` (which is the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> name for T<sub>E</sub>X's `\end` primitive).

```
12   {\errhelp{The configuration for hyphenation is incorrectly
13             installed.^^J%
14             If you don't understand this error message you need
15             to seek^^Jexpert advice.}%
16   \errmessage{OOPS! I can't find any hyphenation patterns for
17             US english.^^J \space Think of getting some or the
18             latex2e setup will never succeed}\@@end}
19 \</default>
```

The following example describes the possible contents of a file `hyphen.cfg` that will load both US English and German hyphenation patterns, making the former the default. It sets `\language` to 0 for the US patterns and to 1 for the German patterns. Then `\language` is set to 0 to make this the default and the default values of `\lefthyphenmin` and `\righthyphenmin` are set.

```
\language=0
\input hyphen % (or \input ushyphen1 if the file has been renamed)
```

```
\language=1
\input ghyph31
\language=0
\lefthyphenmin=2
\righthyphenmin=3
\endinput
```

Another possibility is to use the package `babel`, by Johannes Braams. That package is distributed with a suitable `hyphen.cfg` file.

## File N

# ltxuatex.dtx

## 72 Overview

LuaTeX adds a number of engine-specific functions to TeX. Several of these require set up that is best done in the kernel or need related support functions. This file provides *basic* support for LuaTeX at the L<sup>A</sup>TeX 2<sub>ε</sub> kernel level plus as a loadable file which can be used with plain TeX and L<sup>A</sup>TeX.

This file contains code for both TeX (to be stored as part of the format) and Lua (to be loaded at the start of each job). In the Lua code, the kernel uses the namespace `ltxuatexbase`.

The following `\count` registers are used here for register allocation:

```
\e@alloc@attribute@count Attributes (default 258)
\e@alloc@ccodetable@count Category code tables (default 259)
\e@alloc@luafunction@count Lua functions (default 260)
  \e@alloc@whatsit@count User whatsits (default 261)
  \e@alloc@bytecode@count Lua bytecodes (default 262)
  \e@alloc@luachunk@count Lua chunks (default 263)
```

(`\count 256` is used for `\newmarks` allocation and `\count 257` is used for `\newXeTeXintercharclass` with XeTeX, with code defined in `ltxfinal.dtx`). With any L<sup>A</sup>TeX 2<sub>ε</sub> kernel from 2015 onward these registers are part of the block in the extended area reserved by the kernel (prior to 2015 the L<sup>A</sup>TeX 2<sub>ε</sub> kernel did not provide any functionality for the extended allocation area).

## 73 Core TeX functionality

The commands defined here are defined for possible inclusion in a future L<sup>A</sup>TeX format, however also extracted to the file `ltxuatex.tex` which may be used with older L<sup>A</sup>TeX formats, and with plain TeX.

<code>\newattribute</code>	<code>\newattribute{&lt;attribute&gt;}</code> Defines a named <code>\attribute</code> , indexed from 1 ( <i>i.e.</i> <code>\attribute0</code> is never defined). Attributes initially have the marker value <code>-1</code> ('unset') set by the engine.
<code>\newcatcodetable</code>	<code>\newcatcodetable{&lt;catcodetable&gt;}</code> Defines a named <code>\catcodetable</code> , indexed from 1 ( <code>\catcodetable0</code> is never assigned). A new catcode table will be populated with exactly those values assigned by IniTeX (as described in the LuaTeX manual).
<code>\newluafunction</code>	<code>\newluafunction{&lt;function&gt;}</code> Defines a named <code>\luafunction</code> , indexed from 1. (Lua indexes tables from 1 so <code>\luafunction0</code> is not available).
<code>\newwhatsit</code>	<code>\newwhatsit{&lt;whatsit&gt;}</code> Defines a custom <code>\whatsit</code> , indexed from 1.
<code>\newluabytecode</code>	<code>\newluabytecode{&lt;bytecode&gt;}</code>

	Allocates a number for Lua bytecode register, indexed from 1.
<code>\newluachunkname</code>	<code>newluachunkname{⟨chunkname⟩}</code> Allocates a number for Lua chunk register, indexed from 1. Also enters the name of the register (without backslash) into the <code>lua.name</code> table to be used in stack traces.
<code>\catcodetable@initex</code>	Predefined category code tables with the obvious assignments. Note that the
<code>\catcodetable@string</code>	<code>latex</code> and <code>atletter</code> tables set the full Unicode range to the codes predefined by
<code>\catcodetable@latex</code>	the kernel.
<code>\catcodetable@atletter</code>	<code>\setattribute{⟨attribute⟩}{⟨value⟩}</code>
<code>\setattribute</code>	<code>\unsetattribute{⟨attribute⟩}</code>
<code>\unsetattribute</code>	Set and unset attributes in a manner analogous to <code>\setlength</code> . Note that attributes take a marker value when unset so this operation is distinct from setting the value to zero.

## 74 Plain T<sub>E</sub>X interface

The `luatex` interface may be used with plain T<sub>E</sub>X using `\input{luatex}`. This inputs `luatex.tex` which inputs `etex.src` (or `etex.sty` if used with L<sup>A</sup>T<sub>E</sub>X) if it is not already input, and then defines some internal commands to allow the `luatex` interface to be defined.

The `luatexbase` package interface may also be used in plain T<sub>E</sub>X, as before, by inputting the package `\input luatexbase.sty`. The new version of `luatexbase` is based on this `luatex` code but implements a compatibility layer providing the interface of the original package.

## 75 Lua functionality

### 75.1 Allocators in Lua

<code>new_attribute</code>	<code>luatexbase.new_attribute(⟨attribute⟩)</code> Returns an allocation number for the <code>⟨attribute⟩</code> , indexed from 1. The attribute will be initialised with the marker value <code>-0x7FFFFFFF</code> ('unset'). The attribute allocation sequence is shared with the T <sub>E</sub> X code but this function does <i>not</i> define a token using <code>\attributedef</code> . The attribute name is recorded in the <code>attributes</code> table. A metatable is provided so that the table syntax can be used consistently for attributes declared in T <sub>E</sub> X or Lua.
<code>new_whatsit</code>	<code>luatexbase.new_whatsit(⟨whatsit⟩)</code> Returns an allocation number for the custom <code>⟨whatsit⟩</code> , indexed from 1.
<code>new_bytecode</code>	<code>luatexbase.new_bytecode(⟨bytecode⟩)</code> Returns an allocation number for a bytecode register, indexed from 1. The optional <code>⟨name⟩</code> argument is just used for logging.
<code>new_chunkname</code>	<code>luatexbase.new_chunkname(⟨chunkname⟩)</code> Returns an allocation number for a Lua chunk name for use with <code>\directlua</code> and <code>\latelua</code> , indexed from 1. The number is returned and also <code>⟨name⟩</code> argument is added to the <code>lua.name</code> array at that index.
<code>new_luafunction</code>	<code>luatexbase.new_luafunction(⟨functionname⟩)</code> Returns an allocation number for a lua function for use with <code>\luafunction</code> , <code>\lateluafunction</code> , and <code>\luaodef</code> , indexed from 1. The optional <code>⟨functionname⟩</code> argument is just used for logging.

These functions all require access to a named T<sub>E</sub>X count register to manage their allocations. The standard names are those defined above for access from T<sub>E</sub>X, *e.g.* “e@alloc@attribute@count, but these can be adjusted by defining the variable `<type>_count_name` before loading `ltluatex.lua`, for example

```
local attribute_count_name = "attributetracker"
require("ltluatex")
```

would use a T<sub>E</sub>X `\count` (`\countdef`’d token) called `attributetracker` in place of “e@alloc@attribute@count.

## 75.2 Lua access to T<sub>E</sub>X register numbers

`registernumber` `luatexbase.registernumber(<name>)`  
Sometimes (notably in the case of Lua attributes) it is necessary to access a register *by number* that has been allocated by T<sub>E</sub>X. This package provides a function to look up the relevant number using LuaT<sub>E</sub>X’s internal tables. After for example `\newattribute\myattrib`, `\myattrib` would be defined by (say) `\myattrib=\attribute15`. `luatexbase.registernumber("myattrib")` would then return the register number, 15 in this case. If the string passed as argument does not correspond to a token defined by `\attributedef`, `\countdef` or similar commands, the Lua value `false` is returned.

As an example, consider the input:

```
\newcommand\test[1]{%
\typeout{#1: \expandafter\meaning\csname#1\endcsname^^J
\space\space\space\space
\directlua{tex.write(luatexbase.registernumber("#1") or "bad input")}%
}%

\test{undefinedrubbish}

\test{space}

\test{hbox}

\test{@MM}

\test{@tempdima}
\test{@tempdimb}

\test{strutbox}

\test{sixt@@n}

\attributedef\myattr=12
\myattr=200
\test{myattr}
```

If the demonstration code is processed with LuaL<sub>A</sub>T<sub>E</sub>X then the following would be produced in the log and terminal output.

```

undefinedrubbish: \relax
    bad input
space: macro:->
    bad input
hbox: \hbox
    bad input
@MM: \mathchar"4E20
    20000
@tempdima: \dimen14
    14
@tempdimb: \dimen15
    15
strutbox: \char"B
    11
sixt@@n: \char"10
    16
myattr: \attribute12
    12

```

Notice how undefined commands, or commands unrelated to registers do not produce an error, just return `false` and so print `bad input` here. Note also that commands defined by `\newbox` work and return the number of the box register even though the actual command holding this number is a `\chardef` defined token (there is no `\boxdef`).

### 75.3 Module utilities

`provides_module` `luatexbase.provides_module(<info>)`

This function is used by modules to identify themselves; the `info` should be a table containing information about the module. The required field `name` must contain the name of the module. It is recommended to provide a field `date` in the usual L<sup>A</sup>T<sub>E</sub>X format `yyyy/mm/dd`. Optional fields `version` (a string) and `description` may be used if present. This information will be recorded in the log. Other fields are ignored.

`module_info` `luatexbase.module_info(<module>, <text>)`  
`module_warning` `luatexbase.module_warning(<module>, <text>)`  
`module_error` `luatexbase.module_error(<module>, <text>)`

These functions are similar to L<sup>A</sup>T<sub>E</sub>X's `\PackageError`, `\PackageWarning` and `\PackageInfo` in the way they format the output. No automatic line breaking is done, you may still use `\n` as usual for that, and the name of the package will be prepended to each output line.

Note that `luatexbase.module_error` raises an actual Lua error with `error()`, which currently means a call stack will be dumped. While this may not look pretty, at least it provides useful information for tracking the error down.

### 75.4 Callback management

`add_to_callback` `luatexbase.add_to_callback(<callback>, <function>, <description>)` Registers the *<function>* into the *<callback>* with a textual *<description>* of the function. Functions are inserted into the callback in the order loaded.

`remove_from_callback` `luatexbase.remove_from_callback(<callback>, <description>)` Removes the call-

back function with  $\langle description \rangle$  from the  $\langle callback \rangle$ . The removed function and its description are returned as the results of this function.

<code>in_callback</code>	<code>luatexbase.in_callback(<math>\langle callback \rangle</math>, <math>\langle description \rangle</math>)</code> Checks if the $\langle description \rangle$ matches one of the functions added to the list for the $\langle callback \rangle$ , returning a boolean value.
<code>disable_callback</code>	<code>luatexbase.disable_callback(<math>\langle callback \rangle</math>)</code> Sets the $\langle callback \rangle$ to <code>false</code> as described in the LuaTeX manual for the underlying <code>callback.register</code> built-in. Callbacks will only be set to <code>false</code> (and thus be skipped entirely) if there are no functions registered using the callback.
<code>callback_descriptions</code>	A list of the descriptions of functions registered to the specified callback is returned. <code>{}</code> is returned if there are no functions registered.
<code>create_callback</code>	<code>luatexbase.create_callback(<math>\langle name \rangle</math>,metatype,<math>\langle default \rangle</math>)</code> Defines a user defined callback. The last argument is a default function or <code>false</code> .
<code>call_callback</code>	<code>luatexbase.call_callback(<math>\langle name \rangle</math>,...)</code> Calls a user defined callback with the supplied arguments.

## 76 Implementation

```
1  $\langle *2ekernel | tex | latexrelease \rangle$ 
2  $\langle 2ekernel | latexrelease \rangle \ifx \directlua \@undefined \else$ 
```

### 76.1 Minimum LuaTeX version

LuaTeX has changed a lot over time. In the kernel support for ancient versions is not provided: trying to build a format with a very old binary therefore gives some information in the log and loading stops. The cut-off selected here relates to the tree-searching behaviour of `require()`: from version 0.60, LuaTeX will correctly find Lua files in the `texmf` tree without ‘help’.

```
3  $\langle latexrelease \rangle \backslash IncludeInRelease \{2015/10/01\}$ 
4  $\langle latexrelease \rangle \backslash newluafunction \{LuaTeX\} \%$ 
5  $\backslash ifnum \luatexversion < 60 \%$ 
6  $\backslash wlog \{*****\}$ 
7  $\backslash wlog \{* LuaTeX version too old for l\luatex support *\}$ 
8  $\backslash wlog \{*****\}$ 
9  $\backslash expandafter \endinput$ 
10  $\backslash fi$ 
```

### 76.2 Older L<sup>A</sup>T<sub>E</sub>X/Plain T<sub>E</sub>X setup

```
11  $\langle *tex \rangle$ 
```

Older L<sup>A</sup>T<sub>E</sub>X formats don’t have the primitives with ‘native’ names: sort that out. If they already exist this will still be safe.

```
12  $\backslash directlua \{tex.enableprimitives("",tex.extraprimitives("luatex"))\}$ 
13  $\backslash ifx \e@alloc \@undefined$ 
14  $\backslash ifx \documentclass \@undefined$ 
15  $\backslash ifx \loccount \@undefined$ 
16  $\backslash input \{etex.src\} \%$ 
17  $\backslash fi$ 
18  $\backslash catcode '\@=11 \%$ 
```

In pre-2014 L<sup>A</sup>T<sub>E</sub>X, or plain T<sub>E</sub>X, load `etex.{sty,src}`.



```

19 \outer\expandafter\def\csname newfam\endcsname
20 \csname fam\chardef\et@xmaxfam}
21 \else
22 \RequirePackage{etex}
23 \expandafter\def\csname newfam\endcsname
24 \csname fam\chardef\et@xmaxfam}
25 \expandafter\let\expandafter\new@mathgroup\csname newfam\endcsname
26 \fi

```

### 76.2.1 Fixes to etex.src/etex.sty

These could and probably should be made directly in an update to `etex.src` which already has some Lua<sub>T</sub><sub>E</sub>X-specific code, but does not define the correct range for Lua<sub>T</sub><sub>E</sub>X.

2015-07-13 higher range in luatex.

```
27 \edef \et@xmaxregs {\ifx\directlua\@undefined 32768\else 65536\fi}
```

luatex/xetex also allow more math fam.

```
28 \edef \et@xmaxfam {\ifx\Umathchar\@undefined\sixt@@n\else\@cclvi\fi}
```

```

29 \count 270=\et@xmaxregs % locally allocates \count registers
30 \count 271=\et@xmaxregs % ditto for \dimen registers
31 \count 272=\et@xmaxregs % ditto for \skip registers
32 \count 273=\et@xmaxregs % ditto for \muskip registers
33 \count 274=\et@xmaxregs % ditto for \box registers
34 \count 275=\et@xmaxregs % ditto for \toks registers
35 \count 276=\et@xmaxregs % ditto for \marks classes

```

and 256 or 16 fam. (Done above due to plain/L<sup>A</sup>T<sub>E</sub>X differences in l<sub>t</sub>uatex.)

```
36 % \outer\def\newfam{\alloc@8\fam\chardef\et@xmaxfam}
```

End of proposed changes to `etex.src`

### 76.2.2 luatex specific settings

Switch to global cf `luatex.sty` to leave room for inserts not really needed for luatex but possibly most compatible with existing use.

```

37 \expandafter\let\csname newcount\expandafter\expandafter\endcsname
38 \csname globcount\endcsname
39 \expandafter\let\csname newdimen\expandafter\expandafter\endcsname
40 \csname globdimen\endcsname
41 \expandafter\let\csname newskip\expandafter\expandafter\endcsname
42 \csname globskip\endcsname
43 \expandafter\let\csname newbox\expandafter\expandafter\endcsname
44 \csname globbox\endcsname

```

Define `\e@alloc` as in latex (the existing macros in `etex.src` hard to extend to further register types as they assume specific 26x and 27x count range. For compatibility the existing register allocation is not changed.

```

45 \chardef\e@alloc@top=65535
46 \let\e@alloc\chardef\chardef
47 \def\e@alloc#1#2#3#4#5#6{%
48 \global\advance#3\@ne
49 \e@ch@ck{#3}{#4}{#5}#1%
50 \allocationnumber#3\relax
51 \global#2#6\allocationnumber

```

```

52 \wlog{\string#6=\string#1\the\allocationnumber}}%
53 \gdef\e@ch@ck#1#2#3#4{%
54 \ifnum#1<#2\else
55 \ifnum#1=#2\relax
56 #1\@cclvi
57 \ifx\count#4\advance#1 10 \fi
58 \fi
59 \ifnum#1<#3\relax
60 \else
61 \errmessage{No room for a new \string#4}%
62 \fi
63 \fi}%

```

Two simple L<sup>A</sup>T<sub>E</sub>X macros used in `lAtex.sty`.

```

64 \long\def\@gobble#1{}
65 \long\def\@firstofone#1{#1}

```

Fix up allocations not to clash with `etex.src`.

```

66 \expandafter\csname newcount\endcsname\@alloc@attribute@count
67 \expandafter\csname newcount\endcsname\@alloc@ccodetable@count
68 \expandafter\csname newcount\endcsname\@alloc@luafunction@count
69 \expandafter\csname newcount\endcsname\@alloc@whatsit@count
70 \expandafter\csname newcount\endcsname\@alloc@bytecode@count
71 \expandafter\csname newcount\endcsname\@alloc@luachunk@count

```

End of conditional setup for plain T<sub>E</sub>X / old L<sup>A</sup>T<sub>E</sub>X.

```

72 \fi
73 \</tex>

```

## 76.3 Attributes

`\newattribute` As is generally the case for the LuaT<sub>E</sub>X registers we start here from 1. Notably, some code assumes that `\attribute0` is never used so this is important in this case.

```

74 \ifx\@alloc@attribute@count\@undefined
75 \countdef\@alloc@attribute@count=258
76 \fi
77 \def\newattribute#1{%
78 \e@alloc@attribute\attributedef
79 \e@alloc@attribute@count\m@ne\@alloc@top#1%
80 }
81 \e@alloc@attribute@count=\z@

```

`\setattribute` Handy utilities.

```

\unsetattribute 82 \def\setattribute#1#2{#1=\numexpr#2\relax}
83 \def\unsetattribute#1{#1=-"7FFFFFFF\relax}

```

## 76.4 Category code tables

`\newcatcodetable` Category code tables are allocated with a limit half of that used by LuaT<sub>E</sub>X for everything else. At the end of allocation there needs to be an initialisation step. Table 0 is already taken (it's the global one for current use) so the allocation starts at 1.

```

84 \ifx\e@alloc@ccodetable@count\@undefined
85 \countdef\e@alloc@ccodetable@count=259
86 \fi
87 \def\newcatcodetable#1{%
88   \e@alloc\catcodetable\chardef
89   \e@alloc@ccodetable@count\m@ne{"8000}#1%
90   \initcatcodetable\allocationnumber
91 }
92 \e@alloc@ccodetable@count=\z@

```

`\catcodetable@initex` Save a small set of standard tables. The Unicode data is read here in using a parser  
`\catcodetable@string` simplified from that in load-unicode-data: only the nature of letters needs to  
`\catcodetable@latex` be detected.  
`\catcodetable@atletter`

```

93 \newcatcodetable\catcodetable@initex
94 \newcatcodetable\catcodetable@string
95 \begingroup
96   \def\setrangecatcode#1#2#3{%
97     \ifnum#1>#2 %
98       \expandafter\@gobble
99     \else
100       \expandafter\@firstofone
101     \fi
102     {%
103       \catcode#1=#3 %
104       \expandafter\setrangecatcode\expandafter
105       {\number\numexpr#1 + 1\relax}{#2}{#3}
106     }%
107   }
108   \@firstofone{%
109     \catcodetable\catcodetable@initex
110     \catcode0=12 %
111     \catcode13=12 %
112     \catcode37=12 %
113     \setrangecatcode{65}{90}{12}%
114     \setrangecatcode{97}{122}{12}%
115     \catcode92=12 %
116     \catcode127=12 %
117     \savecatcodetable\catcodetable@string
118   \endgroup
119   }%
120 \newcatcodetable\catcodetable@latex
121 \newcatcodetable\catcodetable@atletter
122 \begingroup
123   \def\parseunicodedataI#1;#2;#3;#4\relax{%
124     \parseunicodedataII#1;#3;#2 First>\relax
125   }%
126   \def\parseunicodedataII#1;#2;#3 First>#4\relax{%
127     \ifx\relax#4\relax
128       \expandafter\parseunicodedataIII
129     \else
130       \expandafter\parseunicodedataIV
131     \fi
132     {#1}#2\relax%

```

```

133 }%
134 \def\parseunicodedataIII#1#2#3\relax{%
135   \ifnum 0%
136     \if L#21\fi
137     \if M#21\fi
138     >0 %
139     \catcode"#1=11 %
140   \fi
141 }%
142 \def\parseunicodedataIV#1#2#3\relax{%
143   \read\unicoderead to \unicodedataline
144   \if L#2%
145     \count0="#1 %
146     \expandafter\parseunicodedataV\unicodedataline\relax
147   \fi
148 }%
149 \def\parseunicodedataV#1;#2\relax{%
150   \loop
151     \unless\ifnum\count0>"#1 %
152       \catcode\count0=11 %
153       \advance\count0 by 1 %
154   \repeat
155 }%
156 \def\storedpar{\par}%
157 \chardef\unicoderead=\numexpr\count16 + 1\relax
158 \openin\unicoderead=UnicodeData.txt %
159 \loop\unless\ifeof\unicoderead %
160   \read\unicoderead to \unicodedataline
161   \unless\ifx\unicodedataline\storedpar
162     \expandafter\parseunicodedataI\unicodedataline\relax
163   \fi
164 \repeat
165 \closein\unicoderead
166 \@firstofone{%
167   \catcode64=12 %
168   \savecatcodetable\catcodetable@latex
169   \catcode64=11 %
170   \savecatcodetable\catcodetable@atletter
171 }
172 \endgroup

```

## 76.5 Named Lua functions

`\newluafunction` Much the same story for allocating Lua<sub>TEX</sub> functions except here they are just numbers so they are allocated in the same way as boxes. Lua indexes from 1 so once again slot 0 is skipped.

```

173 \ifx\e@alloc@luafunction@count\undefined
174   \countdef\e@alloc@luafunction@count=260
175 \fi
176 \def\newluafunction{%
177   \e@alloc@luafunction\e@alloc@chardef
178   \e@alloc@luafunction@count\m@ne\e@alloc@top
179 }

```

```
180 \e@alloc@luafunction@count=\z@
```

## 76.6 Custom whatsits

`\newwhatsit` These are only settable from Lua but for consistency are definable here.

```
181 \ifx\e@alloc@whatsit@count\@undefined
182 \countdef\e@alloc@whatsit@count=261
183 \fi
184 \def\newwhatsit#1{%
185   \e@alloc\whatsit\e@alloc@chardef
186   \e@alloc@whatsit@count\m@ne\e@alloc@top#1%
187 }
188 \e@alloc@whatsit@count=\z@
```

## 76.7 Lua bytecode registers

`\newluabytocode` These are only settable from Lua but for consistency are definable here.

```
189 \ifx\e@alloc@bytocode@count\@undefined
190 \countdef\e@alloc@bytocode@count=262
191 \fi
192 \def\newluabytocode#1{%
193   \e@alloc\luabytocode\e@alloc@chardef
194   \e@alloc@bytocode@count\m@ne\e@alloc@top#1%
195 }
196 \e@alloc@bytocode@count=\z@
```

## 76.8 Lua chunk registers

`\newluachunkname` As for bytecode registers, but in addition we need to add a string to the `lua.name` table to use in stack tracing. We use the name of the command passed to the allocator, with no backslash.

```
197 \ifx\e@alloc@luachunk@count\@undefined
198 \countdef\e@alloc@luachunk@count=263
199 \fi
200 \def\newluachunkname#1{%
201   \e@alloc\luachunk\e@alloc@chardef
202   \e@alloc@luachunk@count\m@ne\e@alloc@top#1%
203   {\escapechar\m@ne
204    \directlua{lua.name[\the\allocationnumber]="\string#1"}}%
205 }
206 \e@alloc@luachunk@count=\z@
```

## 76.9 Lua loader

Load the Lua code at the start of every job. For the conversion of  $\TeX$  into numbers at the Lua side we need some known registers: for convenience we use a set of systematic names, which means using a group around the Lua loader.

```
207 <2ekernel>\everyjob\expandafter{%
208 <2ekernel> \the\everyjob
209 \begingroup
210 \attributedef\attributezero=0 %
211 \chardef \charzero =0 %
```

Note name change required on older luatex, for hash table access.

```

212 \countdef \CountZero =0 %
213 \dimendef \dimenzero =0 %
214 \mathchardef \mathcharzero =0 %
215 \muskipdef \muskipzero =0 %
216 \skipdef \skipzero =0 %
217 \toksdef \tokszero =0 %
218 \directlua{require("ltnuatex")}
219 \endgroup
220 (2ekernel)}
221 \latexrelease\EndIncludeInRelease

222 \latexrelease\IncludeInRelease{0000/00/00}
223 \latexrelease {\newluafunction}{LuaTeX}%
224 \latexrelease\let\@alloc@attribute@count\@undefined
225 \latexrelease\let\newattribute\@undefined
226 \latexrelease\let\setattribute\@undefined
227 \latexrelease\let\unsetattribute\@undefined
228 \latexrelease\let\@alloc@ccodetable@count\@undefined
229 \latexrelease\let\newcatcodetable\@undefined
230 \latexrelease\let\catcodetable@initex\@undefined
231 \latexrelease\let\catcodetable@string\@undefined
232 \latexrelease\let\catcodetable@latex\@undefined
233 \latexrelease\let\catcodetable@atletter\@undefined
234 \latexrelease\let\@alloc@luafunction@count\@undefined
235 \latexrelease\let\newluafunction\@undefined
236 \latexrelease\let\@alloc@luafunction@count\@undefined
237 \latexrelease\let\newwhatsit\@undefined
238 \latexrelease\let\@alloc@whatsit@count\@undefined
239 \latexrelease\let\newluabytecode\@undefined
240 \latexrelease\let\@alloc@bytecode@count\@undefined
241 \latexrelease\let\newluachunkname\@undefined
242 \latexrelease\let\@alloc@luachunk@count\@undefined
243 \latexrelease\directlua{luatexbase.uninstall()}
244 \latexrelease\EndIncludeInRelease

In \everyjob, if luaotfload is available, load it and switch to TU.
245 \latexrelease\IncludeInRelease{2017/01/01}%
246 \latexrelease {\fontencoding}{TU in everyjob}%
247 \latexrelease\fontencoding{TU}\let\encodingdefault\f@encoding
248 \latexrelease\ifx\directlua\@undefined\else
249 (2ekernel)\everyjob\expandafter{%
250 (2ekernel) \the\everyjob
251 (*2ekernel, latexrelease)
252 \directlua{%
253 if xpcall(function ()%
254 require('luaotfload-main')%
255 end, texio.write_nl) then %
256 local _void = luaotfload.main ()%
257 else %
258 texio.write_nl('Error in luaotfload: reverting to OT1')%
259 tex.print('\string\def\string\encodingdefault{OT1}')%
260 end %
261 }%
262 \let\f@encoding\encodingdefault

```

```

263 \expandafter\let\csname ver@luaotfload.sty\endcsname\fmtversion
264 </2ekernel, latexrelease>
265 <latexrelease>\fi
266 <2ekernel> }
267 <latexrelease>\EndIncludeInRelease
268 <latexrelease>\IncludeInRelease{0000/00/00}%
269 <latexrelease> \fontencoding{TU in everyjob}%
270 <latexrelease>\fontencoding{OT1}\let\encodingdefault\f@encoding
271 <latexrelease>\EndIncludeInRelease

272 <2ekernel | latexrelease>\fi
273 </2ekernel | tex | latexrelease>

```

## 76.10 Lua module preliminaries

```
274 <*lua>
```

Some set up for the Lua module which is needed for all of the Lua functionality added here.

**luatexbase** Set up the table for the returned functions. This is used to expose all of the public functions.

```

275 luatexbase      = luatexbase or { }
276 local luatexbase = luatexbase

```

Some Lua best practice: use local versions of functions where possible.

```

277 local string_gsub      = string.gsub
278 local tex_count        = tex.count
279 local tex_setattribute  = tex.setattribute
280 local tex_setcount     = tex.setcount
281 local texio_write_nl   = texio.write_nl

282 local luatexbase_warning
283 local luatexbase_error

```

## 76.11 Lua module utilities

### 76.11.1 Module tracking

**modules** To allow tracking of module usage, a structure is provided to store information and to return it.

```
284 local modules = modules or { }
```

**provides\_module** Local function to write to the log.

```

285 local function luatexbase_log(text)
286   texio_write_nl("log", text)
287 end

```

Modelled on `\ProvidesPackage`, we store much the same information but with a little more structure.

```

288 local function provides_module(info)
289   if not (info and info.name) then
290     luatexbase_error("Missing module name for provides_module")
291   end
292   local function spaced(text)
293     return text and (" " .. text) or ""

```

```

294 end
295 luatexbase_log(
296   "Lua module: " .. info.name
297   .. spaced(info.date)
298   .. spaced(info.version)
299   .. spaced(info.description)
300 )
301 modules[info.name] = info
302 end
303 luatexbase.provides_module = provides_module

```

### 76.11.2 Module messages

There are various warnings and errors that need to be given. For warnings we can get exactly the same formatting as from  $\TeX$ . For errors we have to make some changes. Here we give the text of the error in the  $\LaTeX$  format then force an error from Lua to halt the run. Splitting the message text is done using `\n` which takes the place of `\MessageBreak`.

First an auxiliary for the formatting: this measures up the message leader so we always get the correct indent.

```

304 local function msg_format(mod, msg_type, text)
305   local leader = ""
306   local cont
307   local first_head
308   if mod == "LaTeX" then
309     cont = string_gsub(leader, ".", " ")
310     first_head = leader .. "LaTeX: "
311   else
312     first_head = leader .. "Module " .. msg_type
313     cont = "(" .. mod .. ")"
314     .. string_gsub(first_head, ".", " ")
315     first_head = leader .. "Module " .. mod .. " " .. msg_type .. ":"
316   end
317   if msg_type == "Error" then
318     first_head = "\n" .. first_head
319   end
320   if string.sub(text,-1) ~= "\n" then
321     text = text .. " "
322   end
323   return first_head .. " "
324   .. string_gsub(
325     text
326     .. "on input line "
327     .. tex.inputlineno, "\n", "\n" .. cont .. " "
328   )
329   .. "\n"
330 end

```

```

module_info Write messages.
module_warning 331 local function module_info(mod, text)
module_error 332   texio_write_nl("log", msg_format(mod, "Info", text))
333 end
334 luatexbase.module_info = module_info

```



```

335 local function module_warning(mod, text)
336   texio_write_nl("term and log",msg_format(mod, "Warning", text))
337 end
338 luatexbase.module_warning = module_warning
339 local function module_error(mod, text)
340   error(msg_format(mod, "Error", text))
341 end
342 luatexbase.module_error = module_error

```

Dedicated versions for the rest of the code here.

```

343 function luatexbase_warning(text)
344   module_warning("luatexbase", text)
345 end
346 function luatexbase_error(text)
347   module_error("luatexbase", text)
348 end

```

## 76.12 Accessing register numbers from Lua

Collect up the data from the T<sub>E</sub>X level into a Lua table: from version 0.80, LuaT<sub>E</sub>X makes that easy.

```

349 local luaregisterbasetable = { }
350 local registermap = {
351   attributezero = "assign_attr"    ,
352   charzero      = "char_given"    ,
353   CountZero     = "assign_int"     ,
354   dimenzero     = "assign_dimen"   ,
355   mathcharzero  = "math_given"     ,
356   muskipzero    = "assign_mu_skip" ,
357   skipzero      = "assign_skip"    ,
358   tokszero      = "assign_toks"    ,
359 }
360 local createtoken
361 if tex.luatexversion > 81 then
362   createtoken = token.create
363 elseif tex.luatexversion > 79 then
364   createtoken = newtoken.create
365 end
366 local hashtokens = tex.hashtokens()
367 local luatexversion = tex.luatexversion
368 for i,j in pairs (registermap) do
369   if luatexversion < 80 then
370     luaregisterbasetable[hashtokens[i][1]] =
371       hashtokens[i][2]
372   else
373     luaregisterbasetable[j] = createtoken(i).mode
374   end
375 end

```

**registernumber** Working out the correct return value can be done in two ways. For older LuaT<sub>E</sub>X releases it has to be extracted from the `hashtokens`. On the other hand, newer LuaT<sub>E</sub>X's have `newtoken`, and whilst `.mode` isn't currently documented, Hans Hagen pointed to this approach so we should be OK.

```

376 local registernumber
377 if luatexversion < 80 then
378   function registernumber(name)
379     local nt = hashtokens[name]
380     if(nt and luaregisterbasetable[nt[1]]) then
381       return nt[2] - luaregisterbasetable[nt[1]]
382     else
383       return false
384     end
385   end
386 else
387   function registernumber(name)
388     local nt = createtoken(name)
389     if(luaregisterbasetable[nt.cmdname]) then
390       return nt.mode - luaregisterbasetable[nt.cmdname]
391     else
392       return false
393     end
394   end
395 end
396 luatexbase.registernumber = registernumber

```

## 76.13 Attribute allocation

**new\_attribute** As attributes are used for Lua manipulations its useful to be able to assign from this end.

```

397 local attributes=setmetatable(
398 {},
399 {
400   __index = function(t,key)
401     return registernumber(key) or nil
402   end}
403 )
404 luatexbase.attributes = attributes
405 local attribute_count_name =
406   attribute_count_name or "e@alloc@attribute@count"
407 local function new_attribute(name)
408   tex_setcount("global", attribute_count_name,
409     tex_count[attribute_count_name] + 1)
410   if tex_count[attribute_count_name] > 65534 then
411     luatexbase_error("No room for a new \\attribute")
412   end
413   attributes[name]= tex_count[attribute_count_name]
414   luatexbase_log("Lua-only attribute " .. name .. " = " ..
415     tex_count[attribute_count_name])
416   return tex_count[attribute_count_name]
417 end
418 luatexbase.new_attribute = new_attribute

```

## 76.14 Custom whatsit allocation

**new\_whatsit** Much the same as for attribute allocation in Lua.

```

419 local whatsit_count_name = whatsit_count_name or "e@alloc@whatsit@count"

```

```

420 local function new_whatsit(name)
421   tex_setcount("global", whatsit_count_name,
422               tex_count[whatsit_count_name] + 1)
423   if tex_count[whatsit_count_name] > 65534 then
424     luatexbase_error("No room for a new custom whatsit")
425   end
426   luatexbase_log("Custom whatsit " .. (name or "") .. " = " ..
427                 tex_count[whatsit_count_name])
428   return tex_count[whatsit_count_name]
429 end
430 luatexbase.new_whatsit = new_whatsit

```

## 76.15 Bytecode register allocation

**new\_bytecode** Much the same as for attribute allocation in Lua. The optional *<name>* argument is used in the log if given.

```

431 local bytecode_count_name =
432     bytecode_count_name or "e@alloc@bytecode@count"
433 local function new_bytecode(name)
434   tex_setcount("global", bytecode_count_name,
435               tex_count[bytecode_count_name] + 1)
436   if tex_count[bytecode_count_name] > 65534 then
437     luatexbase_error("No room for a new bytecode register")
438   end
439   luatexbase_log("Lua bytecode " .. (name or "") .. " = " ..
440                 tex_count[bytecode_count_name])
441   return tex_count[bytecode_count_name]
442 end
443 luatexbase.new_bytecode = new_bytecode

```

## 76.16 Lua chunk name allocation

**new\_chunkname** As for bytecode registers but also store the name in the `lua.name` table.

```

444 local chunkname_count_name =
445     chunkname_count_name or "e@alloc@luachunk@count"
446 local function new_chunkname(name)
447   tex_setcount("global", chunkname_count_name,
448               tex_count[chunkname_count_name] + 1)
449   local chunkname_count = tex_count[chunkname_count_name]
450   chunkname_count = chunkname_count + 1
451   if chunkname_count > 65534 then
452     luatexbase_error("No room for a new chunkname")
453   end
454   lua.name[chunkname_count]=name
455   luatexbase_log("Lua chunkname " .. (name or "") .. " = " ..
456                 chunkname_count .. "\n")
457   return chunkname_count
458 end
459 luatexbase.new_chunkname = new_chunkname

```

## 76.17 Lua function allocation

`new_luafunction` Much the same as for attribute allocation in Lua. The optional  $\langle name \rangle$  argument is used in the log if given.

```
460 local luafunction_count_name =
461     luafunction_count_name or "e@alloc@luafunction@count"
462 local function new_luafunction(name)
463     tex_setcount("global", luafunction_count_name,
464         tex_count[luafunction_count_name] + 1)
465     if tex_count[luafunction_count_name] > 65534 then
466         luatexbase_error("No room for a new luafunction register")
467     end
468     luatexbase_log("Lua function " .. (name or "") .. " = " ..
469         tex_count[luafunction_count_name])
470     return tex_count[luafunction_count_name]
471 end
472 luatexbase.new_luafunction = new_luafunction
```

## 76.18 Lua callback management

The native mechanism for callbacks in LuaTeX allows only one per function. That is extremely restrictive and so a mechanism is needed to add and remove callbacks from the appropriate hooks.

### 76.18.1 Housekeeping

The main table: keys are callback names, and values are the associated lists of functions. More precisely, the entries in the list are tables holding the actual function as `func` and the identifying description as `description`. Only callbacks with a non-empty list of functions have an entry in this list.

```
473 local callbacklist = callbacklist or { }
```

Numerical codes for callback types, and name-to-value association (the table keys are strings, the values are numbers).

```
474 local list, data, exclusive, simple = 1, 2, 3, 4
475 local types = {
476     list      = list,
477     data      = data,
478     exclusive = exclusive,
479     simple    = simple,
480 }
```

Now, list all predefined callbacks with their current type, based on the LuaTeX manual version 1.01. A full list of the currently-available callbacks can be obtained using

```
\directlua{
  for i,_ in pairs(callback.list()) do
    texio.write_nl("- " .. i)
  end
}
```

`\bye`

in plain LuaTeX. (Some undocumented callbacks are omitted as they are to be removed.)

```
481 local callbacktypes = callbacktypes or {
```

Section 8.2: file discovery callbacks.

```
482 find_read_file      = exclusive,
483 find_write_file     = exclusive,
484 find_font_file      = data,
485 find_output_file    = data,
486 find_format_file    = data,
487 find_vf_file        = data,
488 find_map_file       = data,
489 find_enc_file       = data,
490 find_pk_file        = data,
491 find_data_file      = data,
492 find_opentype_file  = data,
493 find_truetype_file  = data,
494 find_type1_file     = data,
495 find_image_file     = data,
```

```
496 open_read_file      = exclusive,
497 read_font_file      = exclusive,
498 read_vf_file        = exclusive,
499 read_map_file       = exclusive,
500 read_enc_file       = exclusive,
501 read_pk_file        = exclusive,
502 read_data_file      = exclusive,
503 read_truetype_file  = exclusive,
504 read_type1_file     = exclusive,
505 read_opentype_file  = exclusive,
```

Not currently used by luatex but included for completeness. may be used by a font handler.

```
506 find_cidmap_file   = data,
507 read_cidmap_file    = exclusive,
```

Section 8.3: data processing callbacks.

```
508 process_input_buffer = data,
509 process_output_buffer = data,
510 process_jobname      = data,
```

Section 8.4: node list processing callbacks.

```
511 contribute_filter   = simple,
512 buildpage_filter     = simple,
513 build_page_insert    = exclusive,
514 pre_linebreak_filter = list,
515 linebreak_filter     = exclusive,
516 append_to_vlist_filter = exclusive,
517 post_linebreak_filter = list,
518 hpack_filter         = list,
519 vpack_filter         = list,
520 hpack_quality        = list,
521 vpack_quality        = list,
522 pre_output_filter    = list,
523 process_rule         = exclusive,
```

```

524 hyphenate          = simple,
525 ligaturing         = simple,
526 kerning            = simple,
527 insert_local_par   = simple,
528 mlist_to_hlist     = exclusive,
529 new_graf           = simple,

```

Section 8.5: information reporting callbacks.

```

530 pre_dump           = simple,
531 start_run           = simple,
532 stop_run            = simple,
533 start_page_number   = simple,
534 stop_page_number    = simple,
535 show_error_hook     = simple,
536 show_warning_message = simple,
537 show_error_message  = simple,
538 show_lua_error_hook = simple,
539 start_file          = simple,
540 stop_file           = simple,
541 call_edit           = simple,
542 finish_synctex      = simple,
543 wrapup_run          = simple,

```

Section 8.6: PDF-related callbacks.

```

544 finish_pdffile      = data,
545 finish_pdfpage      = data,
546 page_objnum_provider = data,
547 process_pdf_image_content = data,

```

Section 8.7: font-related callbacks.

```

548 define_font         = exclusive,
549 glyph_not_found     = exclusive,
550 glyph_stream_provider = exclusive,
551 make_extensible     = exclusive,
552 font_descriptor_objnum_provider = exclusive,

```

```

553 }

```

```

554 luatexbase.callbacktypes=callbacktypes

```

**callback.register** Save the original function for registering callbacks and prevent the original being used. The original is saved in a place that remains available so other more sophisticated code can override the approach taken by the kernel if desired.

```

555 local callback_register = callback_register or callback.register
556 function callback.register()
557   luatexbase_error("Attempt to use callback.register() directly\n")
558 end

```

## 76.18.2 Handlers

The handler function is registered into the callback when the first function is added to this callback's list. Then, when the callback is called, the handler takes care of running all functions in the list. When the last function is removed from the callback's list, the handler is unregistered.

More precisely, the functions below are used to generate a specialized function (closure) for a given callback, which is the actual handler.

The way the functions are combined together depends on the type of the callback. There are currently 4 types of callback, depending on the calling convention of the functions the callback can hold:

**simple** is for functions that don't return anything: they are called in order, all with the same argument;

**data** is for functions receiving a piece of data of any type except node list head (and possibly other arguments) and returning it (possibly modified): the functions are called in order, and each is passed the return value of the previous (and the other arguments untouched, if any). The return value is that of the last function;

**list** is a specialized variant of *data* for functions filtering node lists. Such functions may return either the head of a modified node list, or the boolean values **true** or **false**. The functions are chained the same way as for *data* except that for the following. If one function returns **false**, then **false** is immediately returned and the following functions are *not* called. If one function returns **true**, then the same head is passed to the next function. If all functions return **true**, then **true** is returned, otherwise the return value of the last function not returning **true** is used.

**exclusive** is for functions with more complex signatures; functions in this type of callback are *not* combined: An error is raised if a second callback is registered..

Handler for **data** callbacks.

```
559 local function data_handler(name)
560   return function(data, ...)
561     for _,i in ipairs(callbacklist[name]) do
562       data = i.func(data,...)
563     end
564     return data
565   end
566 end
```

Handler for **exclusive** callbacks. We can assume `callbacklist[name]` is not empty: otherwise, the function wouldn't be registered in the callback any more.

```
567 local function exclusive_handler(name)
568   return function(...)
569     return callbacklist[name][1].func(...)
570   end
571 end
```

Handler for **list** callbacks.

```
572 local function list_handler(name)
573   return function(head, ...)
574     local ret
575     local alltrue = true
576     for _,i in ipairs(callbacklist[name]) do
577       ret = i.func(head, ...)
578       if ret == false then
579         luatexbase_warning(
580           "Function '" .. i.description .. "' returned false\n"
```

```

581         .. "in callback '" .. name ..'"
582     )
583     break
584 end
585 if ret ~= true then
586     alltrue = false
587     head = ret
588 end
589 end
590 return alltrue and true or head
591 end
592 end

```

Handler for simple callbacks.

```

593 local function simple_handler(name)
594     return function(...)
595         for _,i in ipairs(callbacklist[name]) do
596             i.func(...)
597         end
598     end
599 end

```

Keep a handlers table for indexed access.

```

600 local handlers = {
601     [data]      = data_handler,
602     [exclusive] = exclusive_handler,
603     [list]      = list_handler,
604     [simple]     = simple_handler,
605 }

```

### 76.18.3 Public functions for callback management

Defining user callbacks perhaps should be in package code, but impacts on `add_to_callback`. If a default function is not required, it may be declared as `false`. First we need a list of user callbacks.

```

606 local user_callbacks_defaults = { }

```

`create_callback` The allocator itself.

```

607 local function create_callback(name, ctype, default)
608     if not name or name == ""
609     or not ctype or ctype == ""
610     then
611         luatexbase_error("Unable to create callback:\n" ..
612             "valid callback name and type required")
613     end
614     if callbacktypes[name] then
615         luatexbase_error("Unable to create callback '" .. name ..
616             "':\ncallback is already defined")
617     end
618     if default ~= false and type (default) ~= "function" then
619         luatexbase_error("Unable to create callback '" .. name ..
620             "':\ndefault is not a function")
621     end
622     user_callbacks_defaults[name] = default

```



```

623  callbacktypes[name] = types[ctype]
624 end
625 luatexbase.create_callback = create_callback

call_callback  Call a user defined callback. First check arguments.
626 local function call_callback(name,...)
627   if not name or name == "" then
628     luatexbase_error("Unable to create callback:\n" ..
629       "valid callback name required")
630   end
631   if user_callbacks_defaults[name] == nil then
632     luatexbase_error("Unable to call callback '" .. name
633       .. "':\nunknown or empty")
634   end
635   local l = callbacklist[name]
636   local f
637   if not l then
638     f = user_callbacks_defaults[name]
639     if l == false then
640       return nil
641     end
642   else
643     f = handlers[callbacktypes[name]](name)
644   end
645   return f(...)
646 end
647 luatexbase.call_callback=call_callback

add_to_callback  Add a function to a callback. First check arguments.
648 local function add_to_callback(name, func, description)
649   if not name or name == "" then
650     luatexbase_error("Unable to register callback:\n" ..
651       "valid callback name required")
652   end
653   if not callbacktypes[name] or
654     type(func) ~= "function" or
655     not description or
656     description == "" then
657     luatexbase_error(
658       "Unable to register callback.\n\n"
659       .. "Correct usage:\n"
660       .. "add_to_callback(<callback>, <function>, <description>)"
661     )
662   end

  Then test if this callback is already in use. If not, initialise its list and register the
  proper handler.
663   local l = callbacklist[name]
664   if l == nil then
665     l = { }
666     callbacklist[name] = l

  If it is not a user defined callback use the primitive callback register.
667   if user_callbacks_defaults[name] == nil then
668     callback_register(name, handlers[callbacktypes[name]](name))

```

```

669     end
670 end

```

Actually register the function and give an error if more than one **exclusive** one is registered.

```

671 local f = {
672     func      = func,
673     description = description,
674 }
675 local priority = #l + 1
676 if callbacktypes[name] == exclusive then
677     if #l == 1 then
678         luatexbase_error(
679             "Cannot add second callback to exclusive function\n'" ..
680             name .. "'"")
681     end
682 end
683 table.insert(l, priority, f)

```

Keep user informed.

```

684 luatexbase_log(
685     "Inserting '" .. description .. "' at position "
686     .. priority .. " in '" .. name .. "'"")
687 )
688 end
689 luatexbase.add_to_callback = add_to_callback

```

**remove\_from\_callback** Remove a function from a callback. First check arguments.

```

690 local function remove_from_callback(name, description)
691     if not name or name == "" then
692         luatexbase_error("Unable to remove function from callback:\n" ..
693             "valid callback name required")
694     end
695     if not callbacktypes[name] or
696         not description or
697         description == "" then
698         luatexbase_error(
699             "Unable to remove function from callback.\n\n"
700             .. "Correct usage:\n"
701             .. "remove_from_callback(<callback>, <description>)"
702         )
703     end
704     local l = callbacklist[name]
705     if not l then
706         luatexbase_error(
707             "No callback list for '" .. name .. "'\n")
708     end

```

Loop over the callback's function list until we find a matching entry. Remove it and check if the list is empty: if so, unregister the callback handler.

```

709     local index = false
710     for i,j in ipairs(l) do
711         if j.description == description then
712             index = i
713             break

```

```

714     end
715 end
716 if not index then
717     luatexbase_error(
718         "No callback '" .. description .. "' registered for '" ..
719         name .. "'\n")
720 end
721 local cb = l[index]
722 table.remove(l, index)
723 luatexbase_log(
724     "Removing '" .. description .. "' from '" .. name .. "'."
725 )
726 if #l == 0 then
727     callbacklist[name] = nil
728     callback_register(name, nil)
729 end
730 return cb.func,cb.description
731 end
732 luatexbase.remove_from_callback = remove_from_callback

```

**in\_callback** Look for a function description in a callback.

```

733 local function in_callback(name, description)
734     if not name
735     or name == ""
736     or not callbacklist[name]
737     or not callbacktypes[name]
738     or not description then
739         return false
740     end
741     for _, i in pairs(callbacklist[name]) do
742         if i.description == description then
743             return true
744         end
745     end
746     return false
747 end
748 luatexbase.in_callback = in_callback

```

**disable\_callback** As we subvert the engine interface we need to provide a way to access this functionality.

```

749 local function disable_callback(name)
750     if(callbacklist[name] == nil) then
751         callback_register(name, false)
752     else
753         luatexbase_error("Callback list for " .. name .. " not empty")
754     end
755 end
756 luatexbase.disable_callback = disable_callback

```

**callback\_descriptions** List the descriptions of functions registered for the given callback.

```

757 local function callback_descriptions (name)
758     local d = {}
759     if not name
760     or name == ""

```

```

761     or not callbacklist[name]
762     or not callbacktypes[name]
763     then
764         return d
765     else
766         for k, i in pairs(callbacklist[name]) do
767             d[k]= i.description
768         end
769     end
770     return d
771 end
772 luatexbase.callback_descriptions =callback_descriptions

```

**uninstall** Unlike at the T<sub>E</sub>X level, we have to provide a back-out mechanism here at the same time as the rest of the code. This is not meant for use by anything other than `latexrelease`: as such this is *deliberately* not documented for users!

```

773 local function uninstall()
774     module_info(
775         "luatexbase",
776         "Uninstalling kernel luatexbase code"
777     )
778     callback.register = callback_register
779     luatexbase = nil
780 end
781 luatexbase.uninstall = uninstall
782  $\langle$ /lua $\rangle$ 

```

Reset the catcode of @.

```

783  $\langle$ tex $\rangle$ \catcode'\@=\etatcatcode\relax

```

# File O

## ltxfinal.dtx

### 77 Final settings

This section contains the final settings for L<sup>A</sup>T<sub>E</sub>X. It initialises some debugging and typesetting parameters, sets the default `\catcodes` and `uc/lc` codes, and inputs the hyphenation file.

#### 77.1 Debugging

By default, L<sup>A</sup>T<sub>E</sub>X shows statistics:

```
1 \*2ekernel)
2 \tracingstats1
```

#### 77.2 Typesetting parameters

```
\@lowpenalty These are penalties used internally.
\@medpenalty 3 \newcount\@lowpenalty
\@highpenalty 4 \newcount\@medpenalty
5 \newcount\@highpenalty

\newmarks Allocate extended marks types if etex is active. Placed here at the end of the
format to increase compatibility with count allocations in earlier releases.
6 \*2ekernel)
7 \*2ekernel | latexrelease)
8 \*2ekernel) \IncludeInRelease{2015/01/01}%
9 \*2ekernel) \newmarks}{Extended Allocation}%
10 \ifx\marks\@undefined\else
11 \def\newmarks{%
12 \e@alloc\marks \e@alloc@chardef{\count256}\m@ne\e@alloc@top}
13 \fi
14 \*2ekernel | latexrelease)
15 \*2ekernel) \EndIncludeInRelease
16 \*2ekernel) \IncludeInRelease{0000/00/00}%
17 \*2ekernel) \newmarks}{Extended Allocation}%
18 \*2ekernel) \let\newmarks\@undefined
19 \*2ekernel) \EndIncludeInRelease
20 \*2ekernel)

\newXeTeXintercharclass Allocate \XeTeXintercharclass types if xetex is active. previously defined in
\XeTeXintercharclass xetex.ini.
\XeTeXintercharclass
\XeTeXintercharclass@top
21 \*2ekernel)
22 \*2ekernel | latexrelease)
23 \*2ekernel) \IncludeInRelease{2015/01/01}%
24 \*2ekernel) \newXeTeXintercharclass}{Extended Allocation}%

Classes allocated 1 to 4094 (or 254 on older xetex) (In earlier XeLaTeX versions
1, 2 and 3 were pre-set for CJK).
25 \ifx\XeTeXcharclass\@undefined
26 \else
```

```

27 \ifdim\the\XeTeXversion\XeTeXrevision\p@>0.99993\p@
28   \chardef\xe@alloc@intercharclass@top=4095
29 \else
30   \chardef\xe@alloc@intercharclass@top=255
31 \fi

32 \def\newXeTeXintercharclass{%
33   \e@alloc\XeTeXcharclass
34   \chardef\xe@alloc@intercharclass\m@ne\xe@alloc@intercharclass@top}
35 \fi

36 \</2ekernel | latexrelease>
37 \<latexrelease>\EndIncludeInRelease
38 \<latexrelease>\IncludeInRelease{0000/00/00}%
39 \<latexrelease>      {\newXeTeXintercharclass}{Extended Allocation}%
40 \<latexrelease> \ifx\XeTeXcharclass\@undefined
41 \<latexrelease> \else
42 \<latexrelease>   \def\xe@alloc@#1#2#3#4#5{\global\advance#1\@ne
43 \<latexrelease>     \xe@ch@ck#1#4#2%
44 \<latexrelease>     \allocationnumber#1%
45 \<latexrelease>     \global#3#5\allocationnumber
46 \<latexrelease>     \wlog{\string#5=\string#2\the\allocationnumber}}
47 \<latexrelease>   \def\xe@ch@ck#1#2#3{%
48 \<latexrelease>     \ifnum#1<#2\else
49 \<latexrelease>       \errmessage{No room for a new #3}%
50 \<latexrelease>     \fi}
51 \<latexrelease>   \def\newXeTeXintercharclass{%
52 \<latexrelease>     \xe@alloc@\xe@alloc@intercharclass
53 \<latexrelease>       \XeTeXcharclass\chardef\@cclv}
54 \<latexrelease> \fi
55 \<latexrelease>\EndIncludeInRelease
56 \<*/2ekernel | latexrelease>
57 \<latexrelease>\IncludeInRelease{2016/02/01}%
58 \<latexrelease> {\xe@alloc@intercharclass}{Start of XeTeX class allocator}%
59 \ifx\XeTeXcharclass\@undefined
60 \else
61   \countdef\xe@alloc@intercharclass=257
62   \xe@alloc@intercharclass=\z@
63 \fi
64 \</2ekernel | latexrelease>
65 \<latexrelease>\EndIncludeInRelease
66 \<latexrelease>\IncludeInRelease{2015/01/01}%
67 \<latexrelease> {\xe@alloc@intercharclass}{Start of XeTeX class allocator}%
68 \<latexrelease> \ifx\XeTeXcharclass\@undefined
69 \<latexrelease> \else
70 \<latexrelease>   \xe@alloc@intercharclass=\thr@@
71 \<latexrelease> \fi
72 \<latexrelease>\EndIncludeInRelease
73 \<latexrelease>\IncludeInRelease{0000/00/00}%
74 \<latexrelease> {\xe@alloc@intercharclass}{Start of XeTeX class allocator}%
75 \<latexrelease> \ifx\XeTeXcharclass\@undefined
76 \<latexrelease> \else
77 \<latexrelease>   \newcount\xe@alloc@intercharclass
78 \<latexrelease>   \xe@alloc@intercharclass=\thr@@
79 \<latexrelease> \fi

```

```

80 <latexrelease>\EndIncludeInRelease
81 <*2ekernel>

```

The default values of the picture and \fbox parameters:

```

82 \unitlength = 1pt
83 \fboxsep = 3pt
84 \fboxrule = .4pt

```

The saved value of T<sub>E</sub>X's \maxdepth:

```

85 \@maxdepth = \maxdepth

```

\vsize initialized because a \clearpage with \vsize < \topskip causes trouble. \@colroom and \@colht also initialized because \vsize may be set to them if a \clearpage is done before the \begin{document}

```

86 \vsize = 1000pt
87 \@colroom = \vsize
88 \@colht = \vsize

```

Initialise \textheight \textwidth and page style, to avoid internal errors if they are not set by the class.

```

89 \textheight=.5\maxdimen
90 \textwidth=\textheight
91 \ps@empty

```

### 77.3 Lccodes for hyphenation

For 7- and 8-bit engines the assumption of T1 encodings is the basis for the hyphenation patterns. That's not the case for the Unicode engines, where the assumption is engine-native working. The common loader system provides access to data from the Unicode Consortium covering not only \lccode but also other related data. The \lccode part of that at least needs to be loaded before hyphenation is tackled: XeT<sub>E</sub>X follows the standard T<sub>E</sub>X route of building patterns into the format. LuaT<sub>E</sub>X doesn't require this data be loaded *here* but it does need to be loaded somewhere. Rather than test for the Unicode engines by name, the approach here is to look for the extended math mode handling both provide: any other engine developed in this area will presumably also provide \Umathcode.

```

92 \ifnum 0%
93   \ifx\Umathcode\@undefined\else 1\fi
94   \ifx\XeTeXmathcode\@undefined\else 1\fi
95   >\z@
96   \message{ Unicode character data,}
97   \input{load-unicode-data}
98 </2ekernel>
99 <latexrelease>\IncludeInRelease{2016/02/01}%
100 <latexrelease> {\XeTeXintercharclasses}{XeTeX character classes}%
101 <latexrelease> \ifx\XeTeXinterchartoks\undefined
102 <latexrelease> \else
103 <latexrelease>   \begingroup
104 <latexrelease>     \chardef\XeTeXcharclassID = 0 %
105 <latexrelease>     \chardef\XeTeXcharclassOP = 0 %
106 <latexrelease>     \chardef\XeTeXcharclassCL = 0 %
107 <latexrelease>     \chardef\XeTeXcharclassEX = 0 %
108 <latexrelease>     \chardef\XeTeXcharclassIS = 0 %

```

```

109 \latexrelease \chardef\XeTeXcharclassNS = 0 %
110 \latexrelease \chardef\XeTeXcharclassCM = 0 %
111 \latexrelease \input{load-unicode-xetex-classes}
112 \latexrelease \endgroup
113 \latexrelease \global\let\xtxHanGlue\undefined
114 \latexrelease \global\let\xtxHanSpace\undefined
115 \latexrelease \global\XeTeXinterchartoks 0 1 = {}
116 \latexrelease \global\XeTeXinterchartoks 0 2 = {}
117 \latexrelease \global\XeTeXinterchartoks 0 3 = {}
118 \latexrelease \global\XeTeXinterchartoks 1 0 = {}
119 \latexrelease \global\XeTeXinterchartoks 2 0 = {}
120 \latexrelease \global\XeTeXinterchartoks 3 0 = {}
121 \latexrelease \global\XeTeXinterchartoks 1 1 = {}
122 \latexrelease \global\XeTeXinterchartoks 1 2 = {}
123 \latexrelease \global\XeTeXinterchartoks 1 3 = {}
124 \latexrelease \global\XeTeXinterchartoks 2 1 = {}
125 \latexrelease \global\XeTeXinterchartoks 2 2 = {}
126 \latexrelease \global\XeTeXinterchartoks 2 3 = {}
127 \latexrelease \global\XeTeXinterchartoks 3 1 = {}
128 \latexrelease \global\XeTeXinterchartoks 3 2 = {}
129 \latexrelease \global\XeTeXinterchartoks 3 3 = {}
130 \latexrelease \fi
131 \latexrelease \EndIncludeInRelease
132 \latexrelease \IncludeInRelease{0000/00/00}%
133 \latexrelease {\XeTeXintercharclasses}{\XeTeX character classes}%
134 \latexrelease \ifx\XeTeXinterchartoks\undefined
135 \latexrelease \else
136 \latexrelease \input{load-unicode-xetex-classes}
137 \latexrelease \gdef\xtxHanGlue{\hskip0pt plus 0.1em\relax}
138 \latexrelease \gdef\xtxHanSpace{\hskip0.2em plus 0.2em minus 0.1em\relax}
139 \latexrelease \global\XeTeXinterchartoks 0 1 = {\xtxHanSpace}
140 \latexrelease \global\XeTeXinterchartoks 0 2 = {\xtxHanSpace}
141 \latexrelease \global\XeTeXinterchartoks 0 3 = {\nobreak\xtxHanSpace}
142 \latexrelease \global\XeTeXinterchartoks 1 0 = {\xtxHanSpace}
143 \latexrelease \global\XeTeXinterchartoks 2 0 = {\nobreak\xtxHanSpace}
144 \latexrelease \global\XeTeXinterchartoks 3 0 = {\xtxHanSpace}
145 \latexrelease \global\XeTeXinterchartoks 1 1 = {\xtxHanGlue}
146 \latexrelease \global\XeTeXinterchartoks 1 2 = {\xtxHanGlue}
147 \latexrelease \global\XeTeXinterchartoks 1 3 = {\nobreak\xtxHanGlue}
148 \latexrelease \global\XeTeXinterchartoks 2 1 = {\nobreak\xtxHanGlue}
149 \latexrelease \global\XeTeXinterchartoks 2 2 = {\nobreak\xtxHanGlue}
150 \latexrelease \global\XeTeXinterchartoks 2 3 = {\xtxHanGlue}
151 \latexrelease \global\XeTeXinterchartoks 3 1 = {\xtxHanGlue}
152 \latexrelease \global\XeTeXinterchartoks 3 2 = {\xtxHanGlue}
153 \latexrelease \global\XeTeXinterchartoks 3 3 = {\nobreak\xtxHanGlue}
154 \latexrelease \fi
155 \latexrelease \EndIncludeInRelease
156 \(*2ekernel)

```

There is one over-ride that makes sense here (see below for the same for 8-bit engines): setting the lccode for - to itself.

```
157 \lccode'\- ='\- % default hyphen char
```

The alternative is that a “traditional” engine is in use.

```
158 \else
```



We set things up so that hyphenation files can assume that the default (T1) lccodes are in use (at present this also sets up the uccodes). We temporarily define `\reserved@a` to apply `\reserved@c` to all the numbers in the range of its arguments.

```

159 \def\reserved@a#1#2{%
160   \@tempcnta#1\relax
161   \@tempcntb#2\relax
162   \reserved@b
163 }
164 \def\reserved@b{%
165   \ifnum\@tempcnta>\@tempcntb\else
166     \reserved@c\@tempcnta
167     \advance\@tempcnta\@ne
168     \expandafter\reserved@b
169   \fi
170 }

```

Depending on the T<sub>E</sub>X version, we might not be allowed to do this for non-ASCII characters.

```

171 \def\reserved@c#1{%
172   \count@=#1\advance\count@ by -"20
173   \uccode#1=\count@
174   \lccode#1=#1
175 }
176 \reserved@a{'\a}{'\z}
177 \reserved@a{"A0}{\BC}
178 \reserved@a{"E0}{\FF}

```

The upper case characters need their `\uccode` and `\lccode` values set, and their `\sfcode` set to 999.

```

179 \def\reserved@c#1{%
180   \count@=#1\advance\count@ by "20
181   \uccode#1=#1
182   \lccode#1=\count@
183   \sfcode#1=999
184 }
185 \reserved@a{'\A}{'\Z}
186 \reserved@a{"80}{\9C}
187 \reserved@a{"C0}{\DF}

```

Well, it would be nice if that were correct, but unfortunately, the Cork encoding contains some odd slots whose uccode or lccode isn't quite what you'd expect.

```

188 \uccode'\^^Y='^I      % dotless i
189 \lccode'\^^Y='^Y      % dotless i
190 \uccode'\^^Z='^J      % dotless j, ae in OT1
191 \lccode'\^^Z='^Z      % dotless j, ae in OT1
192 \lccode'\^^9d='^i     % dotted I
193 \uccode'\^^9d='^9d    % dotted I
194 \lccode'\^^9e='^9e    % d-bar
195 \uccode'\^^9e='^d0    % d-bar

```

Finally here is one that helps hyphenation in the OT1 encoding.

```

196 \lccode'\^^[='^^[    % oe in OT1

```

And we also set the `\lccode` of `\-` and `\textcompwordmark` so that they do not prevent hyphenation in the remainder of the word (as suggested by Lars Helström).

```
197 \lccode'\- ='\- % default hyphen char
198 \lccode 127=127 % alternate hyphen char
199 \lccode 23 =23 % textcompwordmark in T1
```

End of the conditional to select either Unicode or T1 encoding defaults.

```
200 \fi
```

This is as good a place as any to active a few XeTeX-specific settings

```
201 \ifx\XeTeXuseglyphmetrics\@undefined
202 \else
203   \XeTeXuseglyphmetrics=1 %
204   \XeTeXdashbreakstate=1 %
205 \fi
```

## 77.4 Hyphenation

The following code will be compiled into the format file. It checks for the existence of `hyphen.cfg` in inputs that file if found. Otherwise it inputs `hyphen.ltx`. Note that these are loaded in *before* the `\catcodes` are set, so local hyphenation files can use 8-bit input.

We try to load the customized hyphenation description file.

```
206 \InputIfFileExists{hyphen.cfg}
207   {\typeout{=====^J%
208             Local configuration file hyphen.cfg used^J%
209             =====}%
210   \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
211   }
212   {\input{hyphen.ltx}}
213 \let\@addtofilelist\@gobble
```

```
\l@nohyphenation
```

```
214 \ifx\l@nohyphenation \@undefined
215   \newlanguage\l@nohyphenation
216 \fi
```

`\document@default@language` Default document language. -1 acts as language 0, but used as a flag in `\document` to see if it has been set in the preamble.

```
217 \</2ekernel>
218 \<*2ekernel | latexrelease>
219 \<latexrelease>\IncludeInRelease{2017/04/15}%
220 \<latexrelease>          {\document@default@language}{Save language for hyphenation}%
221 \let\document@default@language\m@ne
222 \</2ekernel | latexrelease>
223 \<latexrelease>\EndIncludeInRelease
224 \<latexrelease>\IncludeInRelease{0000/00/00}%
225 \<latexrelease>          {\document@default@language}{Save language for hyphenation}%
226 \<latexrelease>\let\document@default@language\@undefined
227 \<latexrelease>\EndIncludeInRelease
228 \<*2ekernel>
```

## 77.5 Font loading

Fonts loaded during the formatting process might already have changed the `\font@submax` from 0pt to something higher. If so, we put out a bold warning.

```
229 \ifdim \font@submax >\z@
230   \@font@warning{Size substitutions with differences\MessageBreak
231                 up to \font@submax\space have occurred.\MessageBreak
232                 \MessageBreak
233                 Please check the transcript file
234                 carefully\MessageBreak
235                 and redo the format generation if necessary!
236                 \@gobbletwo}%
237 \errhelp{Only stopped, to give you time to
238         read the above message.}
239 \errmessage{}
```

We reset the macro. Otherwise every user will get a warning on every job.

```
240 \def\font@submax{0pt}
241 \fi
```

## 77.6 Input encoding

Starting with the 2018 L<sup>A</sup>T<sub>E</sub>X release default the inputencoding to UTF-8. Unless the format is being used with luatex, xetex, enc<sub>te</sub>x or ml<sub>te</sub>x.

This is done in a way largely compatible with older releases: `utf8.def` is input just as if

```
\usepackage[utf8]{inputenc}
```

had been used, however rather than input the whole package a minimal core part just enough to support loading the UTF-8 encoding files is defined here.

If a document re-specifies UTF-8 this is silently ignored.

```
242 (/2ekernel)
243 (*2ekernel | latexrelease)
```

Check that a classic 8-bit tex engine is being used (LaTeX or PDFLaTeX).

```
244 (latexrelease)\IncludeInRelease{2018/04/01}%
245 (latexrelease)      {\UTFviii@invalid}{UTF-8 default}%
```

Skip this section in Unicode TeX, or if MLTeX and EncTeX are enabled.

```
246 \ifnum0%
247   \ifx\Umathchar\@undefined\else 1\fi
248   \ifx\mubyte\@undefined\else 1\fi
249   \ifx\charsubdef\@undefined\else 1\fi
250   =\z@

251 \def\saved@space@catcode{10}
252 \let\@inpenctest\relax
253 \def\IeC{%
254   \ifx\protect\@typeset@protect
255     \expandafter\@firstofone
256   \else
257     \noexpand\IeC
258   \fi
259 }
```

Make characters active for UTF-8 input formats

```

260 \@tempcnta=1
261 \loop
262   \catcode\@tempcnta=13 %
263   \advance\@tempcnta\@ne %
264   \ifnum\@tempcnta<32 %
265   \repeat %
266 \catcode0=15 % null
267 \catcode9=10 % tab
268 \catcode10=12 % ctrl J
269 \catcode12=13 % ctrl L
270 \catcode13=5 % newline
271 \@tempcnta=128
272 \loop
273   \catcode\@tempcnta=13
274   \advance\@tempcnta\@ne
275   \ifnum\@tempcnta<256
276   \repeat

```

**\UseRawInputEncoding** Reset 8 bit characters to catcode 12 so the input encoding matches the “Raw” font encoding. Useful for special behaviours, or for compatibility with older L<sup>A</sup>T<sub>E</sub>X formats.

```

277 \def\UseRawInputEncoding{%
278 \let\inputencodingname\undefined % revert
279 \let\DeclareFontEncoding\DeclareFontEncoding@saved % revert
280 \let\DeclareUnicodeCharacter\undefined % revert
281 \@tempcnta=1
282 \loop
283   \catcode\@tempcnta=15 %
284   \advance\@tempcnta\@ne %
285   \ifnum\@tempcnta<32 %
286   \repeat %
287 \catcode0=15 % null
288 \catcode9=10 % tab
289 \catcode10=12 % ctrl J
290 \catcode12=13 % ctrl L
291 \catcode13=5 % newline
292 \@tempcnta=128
293 \loop
294   \catcode\@tempcnta=12
295   \advance\@tempcnta\@ne
296   \ifnum\@tempcnta<256
297   \repeat
298 }

```

**\DeclareFontEncoding@saved** Saved version of `\DeclareFontEncoding@` before `utf8.def` modifies it for use in `\UseRawInputEncoding` above.

```

299 \let\DeclareFontEncoding@saved\DeclareFontEncoding@

300 \edef\inputencodingname{utf8}%
301 \input{utf8.def}
302 \let\UTFviii@undefined@err@@\UTFviii@undefined@err
303 \let\UTFviii@invalid@err@@\UTFviii@invalid@err

```

```

304 \let\UTFviii@two@octets@@\UTFviii@two@octets
305 \let\UTFviii@three@octets@@\UTFviii@three@octets
306 \let\UTFviii@four@octets@@\UTFviii@four@octets
307 (2ekernel)\def\UTFviii@undefined@err#1{\@gobble#1}%
308 (2ekernel)\let\UTFviii@invalid@err\string
309 (2ekernel)\let\UTFviii@two@octets\string
310 (2ekernel)\let\UTFviii@three@octets\string
311 (2ekernel)\let\UTFviii@four@octets\string
312 (2ekernel)\everyjob\expandafter{\the\everyjob
313 (2ekernel)\let\UTFviii@undefined@err\UTFviii@undefined@err@@
314 (2ekernel)\let\UTFviii@invalid@err\UTFviii@invalid@err@@
315 (2ekernel)\let\UTFviii@two@octets\UTFviii@two@octets@@
316 (2ekernel)\let\UTFviii@three@octets\UTFviii@three@octets@@
317 (2ekernel)\let\UTFviii@four@octets\UTFviii@four@octets@@
318 (2ekernel)}
319 \let\@inpenc@test\@undefined
320 \let\saved@space@catcode\@undefined

```

For formats not set up for UTF-8 default, set the C0 controls to catcode 15.

```

321 \else
322 \@tempcnta=0
323 \loop
324   \catcode\@tempcnta=15 %
325   \advance\@tempcnta@ne %
326   \ifnum\@tempcnta<32 %
327   \repeat %
328 \catcode0=15 % null
329 \catcode9=10 % tab
330 \catcode10=12 % ctrl J
331 \catcode12=13 % ctrl L
332 \catcode13=5 % newline
333 \let\UseRawInputEncoding\relax

```

This ends the skipped code in Unicode engines:

```

334 \fi
335 (/2ekernel|latexrelease)
336 (latexrelease)\EndIncludeInRelease
337 (latexrelease)\IncludeInRelease{0000/00/00}%
338 (latexrelease)      {\UTFviii@invalid}{UTF-8 default}%

```

The first block of commands got only introduced in 2019 but we revert all of Unicode support in one go not jump to the intermediate version.

```

339 (latexrelease) \let\UTFviii@two@octets@combine\@undefined
340 (latexrelease) \let\UTFviii@three@octets@combine\@undefined
341 (latexrelease) \let\UTFviii@four@octets@combine\@undefined
342 (latexrelease) \let\UTFviii@two@octets@string\@undefined
343 (latexrelease) \let\UTFviii@three@octets@string\@undefined
344 (latexrelease) \let\UTFviii@four@octets@string\@undefined
345 (latexrelease) \let\UTFviii@two@octets@noexpand\@undefined
346 (latexrelease) \let\UTFviii@three@octets@noexpand\@undefined
347 (latexrelease) \let\UTFviii@four@octets@noexpand\@undefined
348 (latexrelease)\@tempcnta=0
349 (latexrelease)\loop
350 (latexrelease) \catcode\@tempcnta=15

```

```

351 \latexrelease \advance\@tempcnta\@ne
352 \latexrelease \ifnum\@tempcnta<32
353 \latexrelease \repeat %
354 \latexrelease \catcode9=10 % tab
355 \latexrelease \catcode10=12 % ctrl J
356 \latexrelease \catcode12=13 % ctrl L
357 \latexrelease \catcode13=5 % newline
358 \latexrelease \@tempcnta=128
359 \latexrelease \loop
360 \latexrelease \catcode\@tempcnta=12
361 \latexrelease \advance\@tempcnta\@ne
362 \latexrelease \ifnum\@tempcnta<256
363 \latexrelease \repeat
364 \latexrelease \let\IeC\@undefined
365 \latexrelease \def\DeclareFontEncoding@#1#2#3{%
366 \latexrelease \expandafter
367 \latexrelease \ifx\csname T@#1\endcsname\relax
368 \latexrelease \def\cdp@elt{\noexpand\cdp@elt}%
369 \latexrelease \xdef\cdp@list{\cdp@list\cdp@elt{#1}%
370 \latexrelease {\default@family}{\default@series}%
371 \latexrelease {\default@shape}}%
372 \latexrelease \expandafter\let\csname#1-cmd\endcsname\@changed@cmd
373 \latexrelease \else
374 \latexrelease \@font@info{Redeclaring font encoding #1}%
375 \latexrelease \fi
376 \latexrelease \global\@namedef{T@#1}{#2}%
377 \latexrelease \global\@namedef{M@#1}{\default@M#3}%
378 \latexrelease \xdef\LastDeclaredEncoding{#1}%
379 \latexrelease }
380 \latexrelease \let\UseRawInputEncoding\@undefined
381 \latexrelease \let\DeclareFontEncoding@saved\@undefined
382 \latexrelease \let\inputencodingname\@undefined
383 \latexrelease \EndIncludeInRelease
384 \*2kernel)
385 % \begin{macrocode}
386 %
387 % We temporarily define |\reserved@a| to apply |\reserved@c| to all the
388 % numbers in the range of its arguments.
389 % \begin{macrocode}
390 \def\reserved@a#1#2{%
391 \@tempcnta#1\relax
392 \@tempcntb#2\relax
393 \reserved@b
394 }
395 \def\reserved@b{%
396 \ifnum\@tempcnta>\@tempcntb\else
397 \reserved@c\@tempcnta
398 \advance\@tempcnta\@ne
399 \expandafter\reserved@b
400 \fi
401 }

```

Set the special catcodes (although some of these are useless, since an error will have occurred if the catcodes have changed). Note that ^^J has catcode ‘other’

for use in warning messages.

```
402 \catcode'\ =10
403 \catcode'\#=6
404 \catcode'\$=3
405 \catcode'\%=14
406 \catcode'\&=4
407 \catcode'\\=0
408 \catcode'\^=7
409 \catcode'\_ =8
410 \catcode'\{=1
411 \catcode'\}=2
412 \catcode'\~=13
413 \catcode'\@=11
414 \catcode'\^^I=10
415 \catcode'\^^J=12
416 \catcode'\^^L=13
417 \catcode'\^^M=5
```

Set the ‘other’ catcodes.

```
418 \def\reserved@c#1{\catcode#1=12\relax}
419 \reserved@c{'\!}
420 \reserved@c{'\"}
421 \reserved@a{'\' }{'\?}
422 \reserved@c{'\[]
423 \reserved@c{'\]}
424 \reserved@c{'\' }
425 \reserved@c{'\|}
```

Set the ‘letter’ catcodes.

```
426 \def\reserved@c#1{\catcode#1=11\relax}
427 \reserved@a{'\A}{'\Z}
428 \reserved@a{'\a}{'\z}
```

All the characters in the range 0–31 and 127–255 are illegal, *except* tab ( $\text{\textasciitilde I}$ ), nl ( $\text{\textasciitilde J}$ ), ff ( $\text{\textasciitilde L}$ ) and cr ( $\text{\textasciitilde M}$ ).

## 77.7 Lccodes and uccodes

We now again set up the default (T1) uc/lccodes. The lower case characters need their `\uccode` and `\lccode` values set. Some of this is a repeat of the set-up before loading hyphenation files. Depending on the  $\text{\TeX}$  version, we might not be allowed to do this for non-ASCII characters. For the Unicode engines ( $\text{\XeTeX}$  and  $\text{\LuaTeX}$ ) there is no need to do any of this: they use hyphenation data which does not alter any of the set up and so this entire block is skipped.

```
429 \ifnum 0%
430   \ifx\Umathcode\@undefined\else 1\fi
431   \ifx\XeTeXmathcode\@undefined\else 1\fi
432   >\z@
433 \else
434 \def\reserved@c#1{%
435   \count@=#1\advance\count@ by -"20
436   \uccode#1=\count@
437   \lccode#1=#1
438 }
```

```

439 \reserved@a{'\a}{'\z}
440 \reserved@a{"A0}{\BC}
441 \reserved@a{"E0}{\FF}

```

The upper case characters need their \uccode and \lccode values set, and their \sfcode set to 999.

```

442 \def\reserved@c#1{%
443   \count@=#1\advance\count@ by "20
444   \uccode#1=#1
445   \lccode#1=\count@
446   \sfcode#1=999
447 }
448 \reserved@a{'\A}{'\Z}
449 \reserved@a{"80}{\9C}
450 \reserved@a{"C0}{\DF}

```

Well, it would be nice if that were correct, but unfortunately, the Cork encoding contains some odd slots whose uccode or lccode isn't quite what you'd expect.

```

451 \uccode'\^^Y='I      % dotless i
452 \lccode'\^^Y='^^Y    % dotless i
453 \uccode'\^^Z='J      % dotless j, ae in OT1
454 \lccode'\^^Z='^^Z    % dotless j, ae in OT1
455 \lccode'\^^9d='i     % dotted I
456 \uccode'\^^9d='^^9d % dotted I
457 \lccode'\^^9e='^^9e % d-bar
458 \uccode'\^^9e='^^d0 % d-bar

```

Finally here is one that helps hyphenation in the OT1 encoding.

```

459 \lccode'\^^[='^^[   % oe in OT1
460 \fi % End of reset block for 8-bit engines

```

\MakeUppercase And whilst we're doing things with uc/lc tables, here are two commands to upper- and lower-case a string.

\MakeUppercase

\@uclclist

*Note* that this implementation is subject to change! At the moment we're not providing any way to extend the list of uc/lc commands, since finding a good interface is difficult. These commands have some nasty features, such as uppercasing mathematics, environment names, labels, etc. A much better long-term solution is to use all-caps fonts, but these aren't generally available.

```

461 \DeclareRobustCommand{\MakeUppercase}[1]{%
462   \def\i{I}\def\j{J}%
463   \def\reserved@a##1##2{\let##1##2\reserved@a}%
464   \expandafter\reserved@a\@uclclist\reserved@b{\reserved@b\@gobble}%

```

Tell UTF-8 processing to process chars even though we are in an \protected@edef.

```

465   \let\UTF@two@octets@noexpand\@empty
466   \let\UTF@three@octets@noexpand\@empty
467   \let\UTF@four@octets@noexpand\@empty
468   \protected@edef\reserved@a{\uppercase{#1}}%
469   \reserved@a
470 }
471 \DeclareRobustCommand{\MakeLowercase}[1]{%
472   \def\reserved@a##1##2{\let##2##1\reserved@a}%
473   \expandafter\reserved@a\@uclclist\reserved@b{\reserved@b\@gobble}%
474   \let\UTF@two@octets@noexpand\@empty

```



```

475 \let\UTF@three@octets@noexpand\@empty
476 \let\UTF@four@octets@noexpand\@empty
477 \protected@edef\reserved@a{\lowercase{#1}}%
478 \reserved@a
479 }}
480 \def\@uclclist{\oe\OE\o\O\ae\AE
481 \dh\DH\dj\DJ\l\L\ng\NG\ss\SS\th\TH}

```

The above code works, but has the nasty side-effect that if you say something like:

```

\markboth{\MakeUppercase\contentsname}
{\MakeUppercase\contentsname}

```

then the uppercasing is only done to the first letter of the contents name, since the mark expands out to:

```

\mark{\protect\MakeUppercase Table of Contents}
{\protect\MakeUppercase Table of Contents}

```

In order to get round this, we redefine `\MakeUppercase` and `\MakeLowercase` to grab their argument and brace it. This is a very low-level hack, and is *not* recommended practice! This is an instance of a general problem that makes it unsafe to grab arguments unbraced, and probably needs a more general solution. For the moment though, this hack will do:

```

482 \protected@edef\MakeUppercase#1{\MakeUppercase{#1}}
483 \protected@edef\MakeLowercase#1{\MakeLowercase{#1}}

```

## 77.8 Applying Patch files

Between major releases, small patches will be distributed in files `ltpatch.ltx` which must be added at this point.

Patch file code removed.

```

484 %\IfFileExists{ltpatch.ltx}
485 % {\typeout{=====^~J%
486 %      Applying patch file ltpatch.ltx^~J%
487 %      =====}}
488 % \def\fmtversion@topatch{unknown}
489 % \input{ltpatch.ltx}
490 % \ifx\fmtversion\fmtversion@topatch
491 % \ifx\patch@level\@undefined
492 % \typeout{^~J^~J^~J%
493 %      !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!^~J%
494 %      !! Patch file 'ltpatch.ltx' not suitable for this^~J%
495 %      !! version of LaTeX.^~J^~J%
496 %      !! Please check if initex found an old patch file:^~J%
497 %      !! --- if so, rename it or delete it, and redo the^~J%
498 %      !! initex run.^~J%
499 %      !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!^~J}%
500 % \batchmode \@@end
501 % \else

```

The code below adds the 'patch level' string to the first `\typeout` in the startup banner.

```

502 % \def\fmtversion@topatch{0}%

```



## 77.11 Initialise file list

`\@providesfile` Initialise for use in the document. During `initex` a modified version has been used which leaves debugging information for `latexbug.tex`.

```
538 \def\@providesfile#1[#2]{%
539     \wlog{File: #1 #2}%
540     \expandafter\xdef\csname ver@#1\endcsname{#2}%
541     \endgroup}
```

`\@filelist` Reset `\@filelist` so files input while making the format are not listed. The list  
`\@addtofilelist` built up so far may take up a lot of memory and so it is moved to `\reserved@a` where it will be overwritten as soon as almost any L<sup>A</sup>T<sub>E</sub>X command is issued in a class file. However the `latexbug.tex` program will be able to access this information and insert it into a bug report.

```
542 \let\@filelist\@gobble
543 \def\@addtofilelist#1{\xdef\@filelist{\@filelist,#1}}%
```

## 77.12 Dumping the format

Finally we make `@` into a letter, ensure the format will be in the ‘normal’ error mode, and dump everything into the format file.

```
544 \makeatother
545 \errorstopmode
546 \dump
547 </2ekernel>
```

# Change History

1985-11-04 ltmath.dtx LaTeX2.09		
General: produce warning message if line extends into margin. Doesn't warn about formula overprinting equation number.	302	
1989-04-10 ltfssbas.dtx v1.0a		
General: Starting with version numbers! <code>\ifmmode</code> added in <code>\math@group</code> . . . . .	163	
1989-04-10 ltfssbas.dtx v1.0b		
General: <code>\preload@sizes</code> added.	163	
<code>\wrong@fontshape</code> changed to define substitution font/shape macro. . . . .	163	
1989-04-10 ltfssini.dtx v1.0a		
General: Starting with version numbers <code>\newif</code> for <code>\@tempswa</code> added since this switch is unknown at the time when this file is read in. (latex.tex is loaded later.) <code>\math@famname</code> changed to <code>\math@version</code> . .	237	
1989-04-14 ltfssbas.dtx v1.0c		
General: More documentation added. . . . .	163	
1989-04-15 ltfssini.dtx v1.0b		
General: <code>\mathfontset</code> renamed to <code>\mathversion</code> . . . . .	237	
1989-04-19 ltfssbas.dtx v1.0d		
General: Even more doc. . . . .	163	
1989-04-21 ltfssbas.dtx v1.0e		
General: Documentation is fun! Parameters of <code>\define@mathalphabet</code> changed. . . . .	163	
1989-04-21 ltfssini.dtx v1.0c		
General: Changed to conform to fam.tex. . . . .	237	
1989-04-23 ltfssbas.dtx v1.0f		
General: % in <code>\getanddefinefonts</code> added.	163	
1989-04-26 ltfssini.dtx v1.0d		
General: <code>\xpt</code> added. . . . .	237	
1989-04-27 ltfssbas.dtx v1.0g		
General: Documentation revised.	163	
1989-04-27 ltfssini.dtx v1.0e		
General: Definitions of L <sup>A</sup> T <sub>E</sub> X symbols corrected. . . . .	237	
1989-04-29 ltfssbas.dtx v1.0h		
General: Documented problem with <code>\halign</code> , and <code>\noalign</code>	163	
<code>\mathversion</code> : Test if version defined added. . . . .	171	
1989-04-29 ltfssbas.dtx v1.0i		
General: Removed the <code>\halign</code> <code>\noalign</code> correction (wasn't bugfree) . . . . .	163	
1989-04-29 ltfssini.dtx v1.0f		
General: Corrections to L <sup>A</sup> T <sub>E</sub> X tabular env. added. . . . .	237	
1989-05-01 ltfssbas.dtx v1.0j		
General: Default for <code>\baselinestretch</code> added. . .	163	
1989-05-22 ltfssbas.dtx v1.0k		
General: Lines longer than 72 characters folded. . . . .	163	
1989-05-22 ltfssini.dtx v1.0g		
General: Lines shortened to 72 characters . . . . .	237	
1989-09-14 ltfssbas.dtx v1.0m		
General: Global replacement: <code>\group</code> to <code>\mathgroup</code> . . . .	163	
<code>\mathversion</code> : Corrected typo: <code>\endscname</code> to <code>\endcsname</code> . .	171	
1989-11-07 ltfssini.dtx v1.0i		
General: All family, series, and shape names abbreviated. . .	237	
1989-11-08 ltfssbas.dtx v1.0o		
General: First parameter of <code>\define@mathalphabet</code> and <code>\define@mathgroup</code> changed from string to control sequence. . . . .	163	
1989-11-14 ltfssbas.dtx v1.0p		
<code>\math@version</code> : Math version prefix 'mv@' added. . . . .	171	
1989-11-19 ltfssbas.dtx v1.0q		
<code>\define@newfont</code> : Group added.	173	
<code>\wrong@fontshape</code> : Instead of calling <code>\family\default@family</code> , etc. we directly set <code>\f@family</code> , etc.	176	
1989-11-22 ltfssbas.dtx v1.0r		
<code>\math@version</code> : <code>\def</code> → <code>\edef</code> for <code>\math@version</code> . . . . .	171	
1989-11-25 ltfssbas.dtx v1.0s		
General: All <code>\edef\font@name</code> changed to <code>\xdef\font@name</code> .		

Necessary after introduction of <code>\begin@group/\endgroup</code> in v1.0q. . . . .	163	1990-01-21 ltfssstrc.dtx v1.2b <code>\use@mathgroup</code> : Macro added to allow cleaner interface. . . . .	195
extra// $\rightarrow$ + in <code>\extra@def</code> . . . . .	163	1990-01-23 ltfssbas.dtx v1.2c General: <code>\no@version@warning</code> renamed to <code>\no@alphabet@error</code> . . . . .	163
1989-11-26 ltfssbas.dtx v1.0t <code>\select@group:\bgroup/\egroup</code> changed to <code>\begin@group/\endgroup</code> to avoid empty Ord atom on math list. . . . .	179	Macro <code>\no@alphabet@help</code> added . . . . .	163
1989-12-02 ltfssini.dtx v1.1b General: <code>\rmmath</code> renamed to <code>\mathrm</code> . . . . .	237	<code>\no@alphabet@error</code> : Changed to error call . . . . .	163
1989-12-03 ltfssini.dtx v1.1c General: Some internal macros renamed to make them inaccessible. . . . .	237	1990-01-25 ltfssini.dtx v1.1e <code>\nfss@text</code> : Macro added. . . . .	240
1989-12-05 ltfssbas.dtx v1.0u <code>\addto@hook:\addto@hook</code> added. . . . .	183	1990-01-27 ltfssbas.dtx v1.2d <code>\DeclarePreloadSizes</code> : Font identifier set to <code>\relax</code> . . . . .	168
1989-12-05 ltfssstrc.dtx v1.0u fam.dtx <code>\every@math@size</code> : Hook <code>\every@size</code> added. . . . .	192	1990-01-28 ltfssbas.dtx v1.2e <code>\mathgroup:\newfam</code> let to <code>\new@mathgroup</code> . . . . .	163
1989-12-13 ltfssstrc.dtx v1.0f <code>\use@mathgroup:\expandafter</code> added before final <code>\fi</code> . . . . .	195	1990-01-28 ltfssbas.dtx v1.2f <code>\define@newfont</code> : Added call to <code>\curr@fontshape</code> macro to allow substitution. . . . .	174
1989-12-16 ltfssbas.dtx v1.1a <code>\select@group:\relax</code> in front added. . . . .	179	<code>\wrong@fontshape</code> : Warning message slightly changed. . . . .	176
Now four arguments. . . . .	179	1990-01-28 ltfssini.dtx v1.2b <code>\em</code> : Call to <code>\@nomath</code> added. . . . .	238
Redefinition of alphabet now simpler. . . . .	179	1990-02-08 ltfssini.dtx v1.1g General: Protected the commands <code>\family</code> , <code>\series</code> , <code>\shape</code> , <code>\size</code> , <code>\selectfont</code> , and <code>\mathversion</code> . . . . .	237
Usage of ‘=’ macro added. . . . .	179	1990-02-16 ltfssbas.dtx v1.2g General: Support for changes of <code>\baselineskip</code> without changing the size. . . . .	163
1989-12-16 ltfssstrc.dtx v1.1a <code>\selectfont</code> : Changed order of calls. . . . .	189	<code>\math@version:\@nomath</code> added. . . . .	171
<code>\use@mathgroup</code> : Redefinition of alphabet now simpler. . . . .	195	1990-02-16 ltfssstrc.dtx v1.0i <code>\selectfont</code> : Changed <code>\f@size</code> to <code>\lcl@currsz</code> (see fam file). . . . .	189
Usage of ‘=’ macro added. . . . .	195	1990-02-18 ltfssstrc.dtx v1.0j General: Redefine unprotected version <code>\p@selectfont</code> instead of <code>\selectfont</code> . . . . .	189
1990-01-18 ltfssstrc.dtx v1.0h General: <code>\tracingfonts</code> meaning changed. . . . .	185	1990-03-14 ltfssstrc.dtx v1.0k General: Added code for TeX3. . . . .	185
1990-01-20 ltfssbas.dtx v1.2a <code>\math@bgroup</code> : Def. placed in this file. . . . .	181	<code>\extract@font</code> : Added code for TeX3. . . . .	188
<code>\math@egroup</code> : Def. placed in this file. . . . .	181	<code>\selectfont</code> : Added code for TeX3. . . . .	189
<code>\select@group</code> : Def for alph id changed. . . . .	179	1990-03-30 ltfssbas.dtx v1.2h <code>\math@egroup</code> : Changed to have one arg. . . . .	181
1990-01-21 ltfssbas.dtx v1.2b <code>\select@group</code> : Code moved to <code>\use@mathgroup</code> . . . . .	179		

1990-03-30 ltfssstrc.dtx v1.2h	1990-08-27 ltfssstrc.dtx 1.0r
<code>\use@mathgroup</code> : Third argument removed (see <code>\math@egroup</code> ). 195	<code>\type@restoreinfo</code> : Some extra tracing info. 191
1990-04-01 ltfssbas.dtx v1.2i	1990-08-27 ltfssstrc.dtx v1.0r
General: Code added from	<code>\getanddefine@fonts</code> : Correcting missing name after
tracefnt.dtx. 163	<code>\tracingon</code> . 196
Support for TeX3. 163	
1990-04-01 ltfssstrc.dtx v1.0l	1991-03-28 ltfssini.dtx v1.1m
General: Part of code moved to	<code>\copyright</code> : Extra braces added. 240
fam.dtx. 185	1991-03-30 ltfssini.dtx v1.2g
<code>\tracingfonts</code> : Check if	<code>\newfont</code> : Definition added. 239
<code>\tracingfonts</code> already defined. 186	<code>\symbol</code> : Definition added. 239
1990-04-01 ltfssstrc.dtx v1.0o	1991-07-24 ltmiscen.dtx LaTeX2.09
<code>\tracingfonts</code> : Check if	<code>\@verbatim</code> : Added
<code>\tracingfonts</code> defined	<code>\penalty\interlinepenalty</code>
removed again. 186	to definition of <code>\par</code> so that
1990-04-02 ltfssini.dtx v1.1i	<code>\samepage</code> works 289
General: <code>\input</code> of files now	1991-08-14 ltmath.dtx LaTeX2.09
handled by docstrip. 237	<code>\cases</code> : (RmS) inserted extra
1990-04-05 ltfssstrc.dtx v1.0m	braces around entry for NFSS 298
<code>\selectfont</code> : Call <code>\tracingon</code>	1991-08-14 ltpictur.dtx LaTeX2.09
only if <code>\tracingfonts</code> greater	General: (RmS) inserted extra
than 3. 189	braces around entry for NFSS 360
1990-05-05 ltfssstrc.dtx v1.0n	1991-08-14 ltthm.dtx LaTeX2.09
<code>\selectfont</code> : <code>\tracingon</code> with	<code>\@endtheorem</code> : Moved <code>\itshape</code>
new syntax. 189	after <code>\item</code> to make it work
1990-06-23 ltfssini.dtx v1.1k	with NFSS 383
<code>\nfss@text</code> : Changed to <code>\mbox</code> . 240	1991-08-26 ltfssini.dtx v1.1n
1990-06-24 ltfssbas.dtx v1.2j	<code>\p@reset@font</code> : Macro introduced 240
<code>\DeclarePreloadSizes</code> : Missing	1991-08-26 ltmiscen.dtx LaTeX2.09
percent added. 167	<code>\@verbatim</code> : <code>\@@par</code> added 289
1990-06-24 ltfssstrc.dtx v1.0o	1991-08-26 ltpictur.dtx LaTeX2.09
<code>\baselinestretch</code> : Moved to	<code>\endpicture</code> : (RmS & FmI) extra
tracefnt.dtx. 192	boxing level around <code>\@picbox</code>
<code>\getanddefine@fonts</code> : Adding	to guard against unboxing in
tracing code. 196	math mode (proposed by John
<code>\Macro</code> moved from fam.dtx. 196	Hobby) 359
Adding debug code. 196	1991-08-26 ltplain.dtx LaTeX2.09
<code>\use@mathgroup</code> : Tracing code	<code>\tracingall</code> : Added <code>\errorcon-</code>
added. 195	<code>textlines=\maxdimen</code> ,
1990-06-30 ltfssbas.dtx v1.2l	suggested by J. Schrod 30
<code>\showhyphens</code> : Macro added. 181	1991-09-29 ltboxes.dtx LaTeX2.09
1990-06-30 ltfssstrc.dtx v1.0p	<code>\@mpfootnotetext</code> : (RmS) added
<code>\use@mathgroup</code> : Added <code>\relax</code>	<code>\reset@font</code> 332
after math group number. 195	1991-09-29 ltfloat.dtx LaTeX2.09
1990-07-07 ltfssstrc.dtx v1.0q	<code>\@footnotetext</code> : (RmS) added
<code>\getanddefine@fonts</code> : Group	<code>\reset@font</code> 413
number added to tracing. 196	1991-09-29 ltmath.dtx LaTeX2.09
<code>\math@egroup</code> : Tracing code	<code>\@eqnnum</code> : RmS: <code>\reset@font</code>
added. 195	added. 301
<code>\use@mathgroup</code> : Group number	1991-09-29 ltsect.dtx LaTeX2.09
added to tracing. 195	<code>\@dottedtocline</code> : (RmS) added
	<code>\reset@font</code> for page number 394

- 1991-10-17 ltcntrl.dtx LaTeX2.09  
`\@tfor`: (Rms) `\xdef` replaced by  
`\def` (See FMI's array.doc) . . . 59
- 1991-10-25 ltbibl.dtx LaTeX2.09  
`\@citex`: added `\reset@font`,  
suggested by Bernd Raichle. 418
- 1991-11-01 ltfloat.dtx LaTeX2.09  
`\footnote`: (RmS) Added  
`\let\protect\noexpand` in  
`\footnote`, `\footnotemark`,  
and `\footnotetext`, since  
`\xdef` is used . . . . . 413
- 1991-11-04 ltlists.dtx LaTeX2.09  
`\makelabel`: (RmS) added default  
definition for `\makelabel`, to  
produce an error message. . . 319
- 1991-11-04 ltplain.dtx RmS  
General: Removed `\itemitem` since  
never needed/useful with  
 $\LaTeX$ . . . . . 28
- 1991-11-06 ltbibl.dtx LaTeX2.09  
`\@citex`: added code to remove a  
leading blank . . . . . 418
- 1991-11-13 ltbibl.dtx LaTeX2.09  
`\@bibitem`: Changed counter  
enumi to enumiv, as it says in  
the comment above . . . . . 418
- 1991-11-21 ltssini.dtx v1.1o  
`\p@reset@font`: Added extra  
braces for robustness. . . . . 240  
Changed to protected version of  
macro. . . . . 240
- 1991-11-22 ltfloat.dtx LaTeX2.09  
`\footnote`: (RmS) Added  
`\let\protect\noexpand` in  
`\@xfootnote`,  
`\@xfootnotemark`, and  
`\@xfootnotetext` . . . . . 413
- 1991-11-22 ltlists.dtx LaTeX2.09  
`\@item`: (RmS) Changed second  
call to `\makelabel` to  
`\unhbox\@tempboxa`. Avoids  
problems with side effects in  
`\makelabel` and is more  
efficient. . . . . 319
- 1991-11-27 ltssbas.dtx v1.3a  
General: All `\family`, `\shape` etc.  
renamed to `\fontfamily` etc. 163
- 1991-11-27 ltssini.dtx v1.2a  
General: All `\family`, `\shape` etc.  
renamed to `\fontfamily` etc. 237
- 1992-01-06 ltssini.dtx v1.2c  
General: added `slitex` code . . . . . 237
- 1992-01-10 ltbibl.dtx LaTeX2.09  
`\@bibitem`: Changed `\c@enumiv` to  
`\value of \@listctr` . . . . . 418
- 1992-01-10 ltmath.dtx LaTeX2.09  
`equation`: RmS: put `\hbox` around  
`\@eqnnum` to typeset the  
equation number in text mode  
(as in the `eqnarray` env.) . . . 301
- 1992-01-10 ltthm.dtx LaTeX2.09  
`\@othm`: (RmS) Check for existence  
of theorem environment . . . 382
- 1992-01-14 ltbibl.dtx LaTeX2.09  
`\@biblabel`: removed `\hfill` . . . 420
- 1992-01-14 ltsect.dtx 0.0  
`\starttoc`: (RmS) added  
`\immediate` to `\openout` as all  
`\write` commands are also  
executed `\immediate` . . . . . 392
- 1992-02-26 ltbibl.dtx LaTeX2.09  
`\@lbibitem`: Added `\hfill` to  
restore left-alignment of  
bibliography labels in alpha  
style . . . . . 418
- 1992-03-18 ltdefns.dtx LaTeX2.09  
General: (RMS) changed input  
channel from 0 to  
`\inputcheck` to avoid  
conflicts with other channels  
allocated by `\newread` . . . . . 37
- 1992-03-18 ltfloat.dtx LaTeX2.09  
`\xympar`: (RmS) added  
`\global\@ignorefalse` . . . . . 409  
`\end@float`: (RmS) changed  
`\@esphack` to `\@Esphack` . . . 403
- 1992-03-18 ltlists.dtx 0.0  
General: RmS: added  
`\@nmbrlistfalse` . . . . . 316
- 1992-03-18 ltmiscen.dtx LaTeX2.09  
`\begin`: Changed `\@ignoretrue` to  
`\@ignorefalse` (as  
documented) . . . . . 284
- 1992-03-21 ltssini.dtx v1.2d  
General: Renamed `\text` to  
`\nfss@text` to make it  
internal. . . . . 237
- 1992-05-12 ltssbas.dtx v1.3c  
`\extract@alph@from@version`:  
Macro added. . . . . 180  
`\select@group`: Added call to `\ex-  
tract@alph@from@version`. . . 179
- 1992-07-26 ltssbas.dtx v1.9a  
`\curr@fontshape`: . . . . . 173  
`\DeclareFontShape`: Introduced  
`\DeclareFontShape` . . . . . 164

<code>\define@newfont:</code> . . . . .	173	<code>\seccntformat</code> . . . . .	388
<code>\math@fonts:</code> . . . . .	179	1992-09-18 ltlists.dtx LaTeX2.09	
<code>\select@group:</code> . . . . .	179, 180	General: (RmS) Added warning if	
<code>\split@name:</code> Added splitting into		<code>\item</code> is used in math mode	317
<code>\f@encoding:</code> . . . . .	173	1992-09-18 lttab.dtx LaTeX2.09	
<code>\wrong@fontshape:</code> . . . . .	176, 177	<code>\@array:</code> Changed <code>\par</code> to	
1992-07-26 ltfsstrc.dtx v2.0b		<code>\@empty</code> to avoid starting new	
<code>\sfct@:</code> . . . . .	204	row e.g. after <code>\hline</code> . . . . .	347
<code>\sfct@sub:</code> . . . . .	205	1992-09-19 ltfsstrc.dtx v2.0c	
<code>\selectfont:</code> . . . . .	189	<code>\try@simple@size:</code> . . . . .	198
<code>\try@simple@size:</code> . . . . .	198, 199	1992-09-21 ltssini.dtx v1.4d	
<code>\try@size@range:</code> . . . . .	202	<code>\not@math@alphabet:</code> Macro	
<code>\use@mathgroup:</code> . . . . .	195	defined. . . . .	238
1992-08-14 ltbibl.dtx LaTeX2.09		1992-09-22 ltssbas.dtx v1.91a	
<code>\citex:</code> added missing argument		General: Introduced <code>\tf@size</code> for	
braces around <code>\hbox</code> , found by		math size. . . . .	163
Ed Sznyter . . . . .	418	1992-09-22 ltfsstrc.dtx v2.1a	
1992-08-14 ltboxes.dtx LaTeX2.09		<code>\getanddefine@fonts:</code> Introduced	
<code>\endminipage:</code> (RmS) replaced		<code>\tf@size</code> for math size. . . . .	196
<code>\vskip</code> – <code>\lastskip</code> by <code>\unskip</code>		1992-11-13 ltssini.dtx v?	
(proposed by FMi) . . . . .	331	<code>\hexnumber@:</code> Made expandable. .	239
1992-08-17 ltbibl.dtx LaTeX2.09		1992-11-23 ltcounts.dtx LaTeX2.09	
<code>\citex:</code> simplified code for		<code>\stepcounter:</code> Replaced <code>{}</code> in	
removing leading blanks in		<code>\stepcounter</code> by <code>\begingroup</code>	
citation key (proposed by		<code>\endgroup</code> to avoid adding an	
Frank Jensen and Kresten		empty ord in math mode . . .	156
Krab Thorup) . . . . .	418	1992-11-26 ltboxes.dtx LaTeX2.09	
1992-08-19 ltsect.dtx 0.0		<code>\@mpfootnotetext:</code> (RmS) added	
<code>\xsect:</code> (RmS) corrected bug:		protection for <code>\edef</code> . . . . .	332
stretch and shrink in argument		1992-11-26 ltfloat.dtx LaTeX2.09	
to <code>\hskip</code> previously not		<code>\@footnotetext:</code> (RmS) added	
negated . . . . .	389	protection for <code>\edef</code> . . . . .	413
1992-08-19 ltthm.dtx LaTeX2.09		<code>\footnote:</code> (RmS) Changed all to	
<code>\oohm:</code> (RmS) Changed error		<code>'def'protect'noexpand'protect'noexpand</code>	
message to complain about		. . . . .	413
undefined counter . . . . .	382	1992-12-03 ltssini.dtx v?	
1992-08-20 ltssini.dtx v1.4b		<code>\hexnumber@:</code> Make it accept	
<code>\setsize:</code> Added <code>\@currsize.</code> .	239	counters. . . . .	239
1992-08-24 ltdefns.dtx LaTeX2.09		1993-03-08 preload.dtx v2.0b	
<code>\ifnextchar:</code> (Rms)		General: Added 12pt preloads . .	262
<code>\ifnextchar</code> didn't work if its		1993-03-18 ltssbas.dtx v2.0c	
first argument was an equal		General: Changed all <code>\@tempdima</code>	
sign. . . . .	50	in <code>\@tempdimb</code> to avoid killing	
1992-08-24 ltmiscen.dtx LaTeX2.09		<code>\numberline</code> . . . . .	163
<code>\begin:</code> Added code to <code>\begin</code> to		1993-03-18 ltfsstrc.dtx v2.1b	
remember line number. Used		General: Changed all <code>\@tempdima</code>	
by <code>\@badend</code> to display position		in <code>\@tempdimb</code> to avoid killing	
of non-matching <code>\begin.</code> . . .	284	<code>\numberline</code> . . . . .	185
<code>\verb:</code> Changed <code>\verb</code> and		Changed all <code>\@tempdimb</code> in	
<code>\@sverb</code> to work correctly in		<code>\@tempdimx</code> to avoid killing	
math mode . . . . .	292	<code>\numberline</code> . . . . .	185
1992-08-25 ltsect.dtx LaTeX2.09		1993-03-18 ltfsstrc.dtx v2.1c	
<code>\sect:</code> (FMi) replaced explicit		<code>\DeclareSizeFunction:</code> Added all	
setting of <code>\svsec</code> by call to		args to avoid blanks problems	201



1993-04-09 ltterror.dtx v1.0e		message of <code>\SetSymbolFont</code> . . . . .	219
<code>\@latexerr</code> : Mention The Companion . . . . .	65	1993-09-02 ltfsstrc.dtx v2.1i	
1993-04-11 ltterror.dtx v1.0f		General: Corrected name of sgen size function. . . . .	185
<code>\@latexerr</code> : Remove setting of errorcontextlines . . . . .	65	1993-09-03 ltmiscen.dtx LaTeX2.09	
1993-05-05 ltfntcmd.dtx v2.0b		<code>\verbatim@nolig@list</code> : Replaced <code>\@noligs</code> by extensible list . . . . .	293
General: Removed all LaTeX related cmds . . . . .	266	1993-09-07 ltmiscen.dtx LaTeX2.09	
1993-05-16 ltfsbas.dtx v2.0e		<code>\verb@balance@group</code> : (RmS) Changed definition of <code>\verb</code> so that it detects a missing second delimiter. . . . .	292
<code>\showhyphens</code> : Use <code>\reset@font</code> . . . . .	181	1993-09-08 ltmiscen.dtx LaTeX2.09	
1993-07-16 ltfsstrc.dtx v2.1h		<code>\enddocument</code> : Added warning in case of undefined references. . . . .	280
General: Changed layout of info messages . . . . .	185	1993-09-15 ltfsbas.dtx v2.0g	
1993-07-17 ltoutenc.dtx 1.0d		<code>\DeclareFontEncoding</code> : Corrected: <code>\default@T</code> to <code>\default@M</code> . . . . .	166
General: changed <code>\catcoding @</code> . . . . .	105	1993-09-15 ltfsstrc.dtx v2.1j	
1993-08-03 ltmiscen.dtx LaTeX2.09		General: Corrected spelling of <code>\noexpand</code> . . . . .	185
<code>\enddocument</code> : Changed redefinition of <code>\global</code> to redefinition of <code>\@setckpt</code> . . . . .	280	1993-09-19 ltterror.dtx LaTeX2.09	
1993-08-05 ltpictur.dtx LaTeX2.09		<code>\@invalidchar</code> : (RmS) Error message for invalid input characters. . . . .	67
<code>\circle</code> : (RMS) Added error message if <code>\circle</code> is used in math mode. . . . .	375	1993-11-02 ltmath.dtx LaTeX2.09	
1993-08-05 ltsect.dtx LaTeX2.09		General: RmS: Corrected description of <code>\@eqnset</code> , moved <code>\@eqnset</code> accordingly and removed extra <code>\tabskip</code> assignment. . . . .	302
<code>\@sect</code> : (RmS) Made sure that <code>\protect</code> works correctly in expansion of <code>\the counter</code> . . . . .	388	1993-11-03 ltmath.dtx LaTeX2e	
1993-08-05 ltspace.dtx LaTeX2e		General: RmS: Initialized <code>\everycr</code> to empty . . . . .	302
<code>\@hspace</code> : (RmS) Removed superfluous <code>\leavevmode</code> in <code>\@hspace</code> and <code>\@hspacer</code> , as suggested by CAR. . . . .	85	1993-11-03 ltpictur.dtx LaTeX2.09	
1993-08-05 lttab.dtx latex2e		General: (RmS) changed <code>\halign</code> to <code>\ialign</code> to initialize <code>\tabskip</code> and <code>\everycr</code> . . . . .	360
<code>\tabular*</code> : Replaced <code>\expandafter\def</code> by <code>\@namedef</code> . . . . .	346	1993-11-11 ltfsini.dtx v2.1a	
1993-08-06 ltbibl.dtx LaTeX2.09		<code>\normalfont</code> : Macro added . . . . .	240
<code>\@citex</code> : Moved writing to .aux file in loop over citation keys so that leading blanks are removed there as well. . . . .	418	1993-11-11 ltfsstrc.dtx v2.2a	
1993-08-13 ltoutenc.dtx 1.0f		General: Option concept added for LaTeX2e . . . . .	185
General: Protected against active <code>@</code> sign. . . . .	105	1993-11-14 ltclass.dtx v0.2a	
1993-08-13 preload.dtx v2.0c		<code>\@current</code> : Name changed from <code>\@currentextension</code> . . . . .	501
General: Added <code>\relax</code> at end of font names. . . . .	263	<code>\@fileswithoptions</code> : Moved resetting of <code>\default@ds</code> , <code>\ds@</code> and <code>\@declaredoptions</code> here, from the end of <code>\ProcessOptions</code> . . . . .	511
1993-08-16 ltoutenc.dtx 1.0g		<code>\@reset@options</code> : macro added . . . . .	512
General: Needs space after <code>\string</code> . . . . .	105	<code>\AtEndDocument</code> : Included extension in the generated	
1993-08-18 ltfsdcl.dtx v2.0e			
<code>\new@mathversion</code> : Exchanged names of encodings in warning			

macro name for package and class hooks. . . . .	513	1993-11-22 ltclass.dtx v0.2f	
\documentstyle: Added		\@fileswithoptions: Made the default [] not	
\RequirePackage		[\@unknownversion] . . . . .	509
\@unusedoptionlist stuff. . .	507	Made the initial version [] not	
\g@addto@macro: Made global . .	513	[\@unknownversion] . . . . .	511
\NeedsTeXFormat: made more robust for alternative syntax for other formats. . . . .	508	\@ifclasslater: Added //00 so parsing never produces a runaway argument. . . . .	502
\ProcessOptions*: Optimise 'empty option' code. . . . .	505	General: \@unknownversion removed . . . . .	496
Stop adding the global option list inside class files. . . . .	505	1993-11-22 ltdefs.dtx LaTeX2e	
1993-11-15 ltclass.dtx v0.2b		\@minus: Macro added . . . . .	36
\documentstyle: Modified to match \ProcessOption* . . .	507	\@plus: Macro added . . . . .	36
\ProcessOptions*: Star form added. . . . .	505	\CheckCommand: Macro added . . .	43
1993-11-17 ltclass.dtx v0.2c		\providecommand: Macro added . .	43
\@@fileswith@pti@ns: Macro added . . . . .	512	1993-11-22 lterror.dtx LaTeX2e	
\@badrequireerror: Macro added	513	\c@errorcontextlines: Macro added . . . . .	64
\@fileswithoptions: Added trap for two \LoadClass commands. . . . .	512	1993-11-22 ltfiles.dtx LaTeX2e	
\@twoloadclasserror: Macro added . . . . .	514	\listfiles: Removed checking for \@unknownversion . . . . .	100
\CurrentOption: Name changed from \@curroption . . . . .	501	1993-11-22 llength.dtx LaTeX2e	
\DeclareOption*: Error checking added . . . . .	505	\@settodim: Macro added . . . . .	162
\NeedsTeXFormat: Name changed from \NeedsFormat . . . . .	508	\@settopoint: Macro added . . . .	162
\ProcessOptions*: restoring \@fileswith@pti@ns added. . . . .	505	\settodepth: Macro added . . . .	162
1993-11-18 ltclass.dtx v0.2d		\settoheight: Macro added . . . .	162
\documentstyle: Modified		1993-11-22 ltlogos.dtx LaTeX2e	
\RequirePackage stuff. . . . .	507	\LaTeXe: Macro added . . . . .	87
\ExecuteOptions: Use		1993-11-23 ltclass.dtx v0.2g	
\CurrentOption not		\@use@option: Name changed from \@executeoption . . . . .	507
\reserved@a . . . . .	507	General: Various macros now moved to latex.tex. . . . .	500
\NeedsTeXFormat: \fmtname		Warnings and errors now directly coded. . . . .	500
\fmtversion not \@... . . . .	508	1993-11-23 ltdefs.dtx LaTeX2e	
1993-11-21 ltfiles.dtx LaTeX2e		\@argdef: Macro added . . . . .	39
\@missingfileerror: Stop infinite looping on \@er@ext . . . . .	99	\@ifundefined: Redefined to remove a trailing \fi . . . . .	48
1993-11-21 ltmiscen.dtx v0.9a		\@newcommand: Macro added . . . .	39
\@verbatim: use \verbatim@font instead of \tt . . . . .	290	\@newenv: Macro interface changed	42
\verb: Use \verbatim@font instead of \tt. . . . .	292	\@xargdef: Macro interface changed . . . . .	39
\verbatim@font: Macro added . .	290	\@yargdf: Avoid \@?@? token . .	40
		Macro interface changed . . . . .	40
		\newcommand: Macro reimplemented and extended . .	39
		\renewcommand: Macro reimplemented and extended . .	41
		\renewenvironment: Macro reimplemented and extended . .	42
		\two@digits: Macro added . . . .	36

- 1993-11-23 ltoutput.dtx v0.1a  
   \paperheight: Register added . . 436  
   \paperwidth: Register added . . . 436
- 1993-11-23 ltoutput.dtx v0.1c  
   \@enlargepage: Command added 479  
   \@kludgeins: Insert added . . . . 479  
   \@makecol: Command changed . . 447  
   \@specialoutput: Command  
     changed . . . . . 441  
   \enlargethispage\*: Commands  
     added . . . . . 479
- 1993-11-24 ltfntcmd.dtx v2.1a  
   \maybe@ic@: Use \t@st@ic . . . . 271  
   \t@st@ic: Macro added . . . . . 271
- 1993-11-24 ltfssini.dtx v2.1a  
   General: Removed \xpt stuff . . . 240
- 1993-11-24 ltlogos.dtx LaTeX2e  
   \LaTeX: Macro changed . . . . . 87
- 1993-11-28 ltclass.dtx v0.2h  
   \@twoclasseserror: Macro added 514  
   General: Assorted commands now  
     in the kernel removed. . . . . 500  
   Directory syntax checing moved  
     to dircheck.dtx . . . . . 500  
   Primitive filenames now  
     terminated by space not  
     \relax. . . . . 500  
   \endfilecontents: Don't globally  
     allocate a write stream (always  
     use 15) . . . . . 514
- 1993-11-28 ltfiles.dtx LaTeX2e  
   \@missingfileerror: Use filename  
     parser from dircheck . . . . . 99
- 1993-11-29 ltoutput.dtx v1.0b  
   \@makecol: \@makespecialcolbox  
     added . . . . . 447  
   \@makespecialcolbox: Command  
     added . . . . . 449
- 1993-11-29 ltplain.dtx LaTeX2e  
   General: All accents in decimals;  
     suggested by Paul Taylor . . . . 29
- 1993-11-30 ltoutput.dtx v1.0c  
   \fl@tracemessage: Commands  
     added . . . . . 481
- 1993-12-01 fontdef.dtx v2.1a  
   General: Update for LaTeX2e . . . 243
- 1993-12-01 ltoutput.dtx v1.0e  
   \@reinserts: Command added . . 448
- 1993-12-03 ltboxes.dtx v0.1a  
   \@argsbox: macro removed . . . . 333  
   \@begin@tempboxa: macro added 324  
   \@end@tempboxa: macro added . . 324  
   \@iirsbox: redefined to support  
     \height . . . . . 333
- \@imakebox: macro modified . . . 324  
   \@iirsbox: redefined to support  
     \height . . . . . 333  
   \@isavebox: color support . . . . 326  
     extra group . . . . . 326  
   \@isavepicbox: extra group . . . . 326  
   \@makebox: default changed from x  
     to c . . . . . 324  
   \@makepicbox: macro modified . . 325  
   \@savebox: default c not x . . . . 326  
   \bm@b: macros added . . . . . 324  
   \endlrbox: macro added . . . . . 326  
   \fbbox: extra group . . . . . 327  
   \lrbox: color support . . . . . 326  
     macro added . . . . . 326  
   \makebox: modified . . . . . 323  
   \mbox: extra group . . . . . 324  
   \minipage: Redefined to support  
     extra optional arguments . . . 331  
   \newsavebox: Pass the whole of  
     arg 1 to \@ifdefinable . . . . 325  
   \parbox: Redefined to support  
     extra optional arguments . . . 328  
   \raisebox: redefined to support  
     \height . . . . . 333  
   \sbox: color support . . . . . 326  
     extra group . . . . . 326  
   \set@color: color support . . . . 325  
     macro added . . . . . 325
- 1993-12-03 ltclass.dtx v0.2i  
   \@cls@pkg: Name changed to avoid  
     clash with output routine. . . 513  
   General: \@onlypreamble: Many  
     commands declared. . . . . 500  
   Removed obsolete  
     \@documentclass . . . . . 500
- 1993-12-03 lterror.dtx v1.0b  
   \@latexerr: Set  
     \c@errorcontextlines to -1 . . 65
- 1993-12-03 ltfssini.dtx v2.1a  
   General: update for LaTeX2e . . . 237
- 1993-12-04 ltfiles.dtx v0.9b  
   \@iinput: Macro reimplemented . . 99  
   \@input: Macro reimplemented . . 99  
   \IfFileExists@: Macro added . . 97  
   \input: Macro reimplemented . . 98  
   \InputIfFileExists: Macro  
     added . . . . . 98
- 1993-12-05 ltfloat.dtx LaTeX2e  
   \@dblfloatplacement: Command  
     changed . . . . . 405  
   \@xfloat: Command changed . . 400
- 1993-12-05 ltoutput.dtx v1.0f  
   \@addtobot: Command changed . . 461

<code>\@addtocurcol</code> : Command	1993-12-07 ltclass.dtx v0.2m
changed . . . . . 462	<code>\@fileswithoptions</code> : Reset
<code>\@addtodblcol</code> : Command	<code>\CurrentOption</code> . . . . . 511
changed . . . . . 473	1993-12-07 ltoutenc.dtx 1.1
<code>\@addtonextcol</code> : Command	General: Protected all special
changed . . . . . 469	characters with <code>\string</code> . . . . . 105
<code>\@addtotoporbot</code> : Command	1993-12-07 ltoutenc.dtx v1.1
changed . . . . . 461	General: Made all character
<code>\@boxfpsbit</code> : Command added . 484	numbers decimal. . . . . 102
<code>\@flcheckspace</code> : Command	Removed a lot of equal signs
added . . . . . 486	and the like. . . . . 102
<code>\@flsetnum</code> : Command added . . 485	1993-12-08 ltboxes.dtx v0.1b
<code>\@flsettextmin</code> : Command	<code>\@begin@tempboxa</code> : Extra braces
added . . . . . 486	for color support (braces
<code>\@flstop</code> : Commands added . . . 482	removed from other macros) . . . . . 324
<code>\@flupdates</code> : Command added . 487	<code>\@irsbox</code> : fix typo . . . . . 333
<code>\@fpsadddefault</code> : Command	<code>\@parboxto</code> : <code>\endgraf</code> added due
added . . . . . 483	to extra group in
<code>\@getfpsbit</code> : Command added . 484	<code>\@begin@tempboxa</code> . . . . . 329
<code>\@opcol</code> : Command changed . . . 447	<code>\lrbox</code> : move <code>\@endpefalse</code> out of
Hook added . . . . . 447	the inner group . . . . . 326
<code>\@outputpage</code> : Command	1993-12-08 ltfntcmd.dtx v2.1b
changed . . . . . 451	General: Macros <code>\rm</code> , <code>\bf</code> and <code>\sf</code>
<code>\@resethfps</code> : Command added . 485	moved to classes.dtx . . . . . 273
<code>\@setfloattypecounts</code> : Command	1993-12-08 ltlists.dtx LaTeX2e
added . . . . . 483	<code>\@item</code> : use <code>\sbox</code> to support
<code>\@setfpsbit</code> : Command added . 484	colour . . . . . 319
<code>\@shipoutsetup</code> : Command	1993-12-08 ltspace.dtx LaTeX2e
added . . . . . 451	<code>\@bsphack</code> : Command
<code>\@startcolumn</code> : Command	reimplemented . . . . . 77
changed . . . . . 456	Command reimplemented; late
<code>\@startdblcolumn</code> : Command	birthday present for Chris . . . . . 77
changed . . . . . 456	<code>\@vbsphack</code> : Command added . . 80
<code>\@testfp</code> : Command added . . . . 484	1993-12-09 ltboxes.dtx v0.1c
<code>\@textfloatsheight</code> : Commands	<code>\@irsbox</code> : fix another typo . . . . . 333
added . . . . . 483	1993-12-09 ltclass.dtx v0.2n
<code>\@topnewpage</code> : Commands	<code>\documentstyle</code> : input 209
changed . . . . . 439	compatibility file. . . . . 507
<code>\@tryfcolumn</code> : Command	1993-12-09 ltfiles.dtx v0.9e
changed . . . . . 458	<code>\document</code> : Hook added . . . . . 90
<code>\@writesetup</code> : <code>\@startpagehook</code>	1993-12-09 ltmiscen.dtx v0.9e
added . . . . . 451	<code>\enddocument</code> : Hook added . . . . . 280
<code>\output</code> : Command changed . . . 441	1993-12-10 ltoutenc.dtx v1.2
1993-12-06 ltclass.dtx v0.2k	General: Added source code for
<code>\ExecuteOptions</code> : Preserve	<code>tlenc.sty</code> . . . . . 102
<code>\CurrentOption</code> . . . . . 507	1993-12-11 ltfntcmd.dtx v3.0a
1993-12-06 ltoutput.dtx v1.0f	General: Complete reworking of all
<code>\@specialoutput</code> : Unboxing of 255	text commands, using just one
added to rescue writes . . . . . 441	creator function . . . . . 266
1993-12-06 ltoutput.dtx v1.0g	italic correction now put in front
<code>\@topnewpage</code> : <code>\@floatplacement</code>	of penalty before glue . . . . . 266
placement bug fixed . . . . . 439	newcommands replaced by defs . . . . . 266
1993-12-07 ltclass.dtx v0.2l	newfontswitch command
<code>\ProvidesFile</code> : Macro added . . . 504	corrected and changed . . . . . 266

<code>\DeclareTextFontCommand</code> : Macro changed . . . . .	268	<code>\IfFileExists</code> : Removed interactive prompting for current directory syntax . . . .	10
<code>\emph</code> : Macro changed . . . . .	269	<code>\strip@prefix</code> : modified, name changed from <code>\stripmeaning</code> . . .	5
<code>\fix@penalty</code> : Macro added . . . .	271	1993-12-13 <code>ltlists.dtx</code> latex2e	
<code>\maybe@ic</code> : Macro name changed	270	<code>\trivlist</code> : Initialised	
<code>\maybe@ic@</code> : Macro and name changed . . . . .	270	<code>\@itemlabel</code> . . . . .	316
<code>\sw@slant</code> : Macro changed . . . .	271	1993-12-13 <code>ltmiscen.dtx</code> v0.9h	
<code>\textup</code> : Macros changed . . . . .	269	<code>\@noligs</code> : Readded <code>\@noligs</code> . . .	293
1993-12-11 <code>ltmath.dtx</code> v0.9g		<code>\@verbatim</code> : Readded <code>\@noligs</code> .	290
General: Added a group around the first argument of <code>\frac</code> to prevent changes (for example font changes) from modifying the contents of the second argument. . . . .	302	Removed optional argument of <code>\item</code> . . . . .	289
1993-12-11 <code>ltoutenc.dtx</code> v1.2a		<code>center</code> : Removed optional argument of <code>\item</code> . . . . .	288
General: Corrected for <code>tlenc</code> , <code>math</code> . . . . .	102	<code>flushleft</code> : Removed optional argument of <code>\item</code> . . . . .	288
1993-12-11 <code>ltsect.dtx</code> LaTeX2e		<code>flushright</code> : Removed optional argument of <code>\item</code> . . . . .	288
<code>\author</code> : Added default . . . . .	384	1993-12-13 <code>ltoutenc.dtx</code> v1.2b	
<code>\title</code> : Added default . . . . .	384	General: Corrected file name in driver code. . . . .	102
1993-12-11 <code>ltxref.dtx</code> LaTeX2e		1993-12-13 <code>lftab.dtx</code> latex2e	
<code>\@setref</code> : Macro added . . . . .	277	<code>\tabbing</code> : Removed optional argument of <code>\item</code> . . . . .	341
<code>\pageref</code> : Macro reimplemented .	277	1993-12-14 <code>ltoutput.dtx</code> v1.0i	
<code>\ref</code> : Macro reimplemented . . . .	277	General: Section added to declare all parameters . . . . .	492
1993-12-12 <code>ltoutput.dtx</code> v1.0h		1993-12-15 <code>ltboxes.dtx</code> v0.1d	
<code>\@cflb</code> : <code>boxmaxdepth</code> setting moved . . . . .	455	<code>\@iminipage</code> : Changed default from ‘c’ to ‘s’ . . . . .	331
defs changed to <code>lets</code> . . . . .	455	<code>\@iparbox</code> : Changed default from ‘c’ to ‘s’ . . . . .	329
<code>\@cflt</code> : name changed . . . . .	455	<code>\minipage</code> : Changed default from ‘c’ to ‘s’ . . . . .	331
<code>\@docclearpage</code> : defs changed to <code>lets</code> . . . . .	446	extra space removed. . . . .	331
<code>\@makecol</code> : defs changed to <code>lets</code> .	448	<code>\parbox</code> : Changed default from ‘c’ to ‘s’ . . . . .	328
<code>\@resethfps</code> : Warnings added: minimal . . . . .	485	1993-12-15 <code>ltclass.dtx</code> v0.2p	
<code>\@startdblcolumn</code> : defs changed to <code>lets</code> . . . . .	457	General: Removed extra ‘.’s from <code>\@@warnings</code> . . . . .	500
<code>\@topnewpage</code> : braces removed . .	439	1993-12-16 <code>ltlogos.dtx</code> LaTeX2e	
<code>\@tryfcolumn</code> : defs changed to <code>lets</code> . . . . .	458	<code>\LaTeXe</code> : Extended logo by DPC	87
<code>\fl@tracemessage</code> : Commands changed . . . . .	481	1993-12-16 <code>ltmath.dtx</code> v0.9i	
1993-12-13 <code>ltclass.dtx</code> v0.2o		<code>\@eqnocr</code> : use <code>\refstepcounter</code> instead of shortcut . . . . .	303
General: Removed setting <code>\errorcontextlines</code> (now in <code>latex.tex</code> ) . . . . .	500	General: use <code>\refstepcounter</code> instead of shortcut . . . . .	302
<code>\documentstyle</code> : compatibility file now <code>latex209.sty</code> . . . . .	507	1993-12-16 <code>ltmiscen.dtx</code> v0.9i	
<code>\usepackage</code> : Fixed error handling . . . . .	508	General: <code>\literal</code> added . . . . .	293
1993-12-13 <code>ltdirchk.dtx</code> v0.2a		1993-12-16 <code>ltpage.dtx</code> LaTeX2e	
General: on the ‘docstrip’ pass, do not check <code>openin</code> path . . . . .	10	<code>\mark</code> : Init <code>\mark</code> at begin document . . . . .	423

1993-12-16 ltspace.dtx LaTeX2e	initializing mark until the problem is solved. . . . .	423
\@bsphack: Corrected optimisation :-)		77
1993-12-16 lttab.dtx latex2e	General: Fixed typos with \ProvidesPackage lines. Added the \NeedsTeXFormat line. Added the last argument to \DeclareEncoding. Moved the use of the encodings to after their declaration. . . . .	105
\@xhline: Measure from middle of vertical rules . . . . .	Replaced the missing last argument to \DeclareFontEncoding. . . . .	117, 120
1993-12-17 ltclass.dtx v0.2q		
\@documentclasshook: Macro added . . . . .		500
\@fileswithoptions: Add \@compatibility hook . . . .		510
\documentstyle: Match Alan's new code. . . . .		507
1993-12-17 ltoutenc.dtx 1.3		
General: Added this section . . . .		106
Removed all the hackery for use in \DeclareFontEncoding, and redid everything using \DeclareTextFoo. . . . .		117, 120
Removed the catcode hackery, since the file is only read as a package in the preamble, and removed all the messages on the screen, which just confuse users. Replaced them by the appropriate \ProvidesPackage commands. Added XXXenc. . . .		105
1993-12-17 ltoutenc.dtx v1.3		
General: Added \EncodingSpecificAccent, \EncodingSpecificAccent-edLetter and \EncodingSpecificCommand. . . .		102
Made Rokicki's encoding a proper encoding scheme rather than a variant of OT1. . . . .		102
1993-12-17 ltoutput.dtx v1.0j		
\@opcol: Hook removed . . . . .		447
\@specialoutput: Page room test added . . . . .		442
\@topnewpage: check for vsize too small added . . . . .		439
Page room test added . . . . .		441
\@writesetup: —and then removed . . . . .		451
\fl@tracemessage: tracefloatvals made a document command . . . .		481
1993-12-17 ltpage.dtx LaTeX2e		
\mark: Removed init \mark at begin document, since it doesn't work. . . . .		423
\rightmark: Stopgap solution to mark \leftmark and \rightmark work without		
1993-12-18 ltoutenc.dtx 1.3b		
1993-12-18 ltoutenc.dtx 1.3c		
General: Rewrote for the new syntax of \EncodingSpecific. . . . .		117, 120
Split \EncodingSpecificAccent up into \EncodingSpecific and \DeclareAccent. . . . .		106
1993-12-18 ltoutenc.dtx v1.3a		
General: Replaced OT3 by XXX . . . .		102
1993-12-18 ltoutenc.dtx v1.3b		
General: Corrected typos. . . . .		102
Replaced the missing last argument to \DeclareFontEncoding. . . .		102
1993-12-18 ltoutenc.dtx v1.3c		
General: A new syntax, separating accent-definitions from encoding-specific definitions, and allowing encoding-specific \chardef, \let, etc. . . . .		102
Rewrote for the new syntax of \EncodingSpecific. . . . .		102
1993-12-18 ltoutenc.dtx v1.3d		
General: Some T1 stuff had drifted into the OT1 file. . . . .		102
1993-12-18 ltpage.dtx LaTeX2e		
\sloppy: Added \emergencystretch . . . . .		423
1993-12-19 ltclass.dtx v0.2r		
\endfilecontents: Different message when ignoring a file . . . .		514
1993-12-19 ltfntcmd.dtx v3.0b		
General: \pdef command added . . . .		266
Added by ASAJ. . . . .		273
Made \@newfontswitch produce an error if command already exists, and added \@renewfontswitch, ASAJ . . . .		266
Other tidying . . . . .		266
Some more tidying done . . . . .		266



Untidying added, so this is now a TEMPORARY version. . .	266	<code>\math@version</code> : New math font setup . . . . .	171
Wording changes by CAR. . .	273	1994-01-17 <code>ltfssini.dtx</code> v2.1e <code>\not@math@alphabet</code> : Message changed . . . . .	238
<code>\DeclareOldFontCommand</code> : Corrected and tidied . . . . .	273	1994-01-17 <code>ltfssstrc.dtx</code> v2.3a General: New math font setup . .	185
<code>\DeclareTextFontCommand</code> : Corrected and tidied . . . . .	268	<code>\check@mathfonts</code> : New math font setup . . . . .	194
1993-12-19 <code>ltspace.dtx</code> LaTeX2e <code>\@bsphack</code> : There seem to be problems with selfmade birthday presents . . . . .	78	<code>\glb@currsz</code> : New math font setup . . . . .	191
1993-12-20 <code>ltdefns.dtx</code> LaTeX2e <code>\@reargdef</code> : Kept old version of <code>\@reargdef</code> , for <code>array.sty</code> . . .	41	<code>\restglb@settings</code> : New math font setup . . . . .	194
1993-12-20 <code>ltfiles.dtx</code> v0.9m <code>\@obsoletefile</code> : Added this command, removed <code>@oldfilewarning</code> . . . . .	100	1994-01-18 <code>ltbibl.dtx</code> LaTeX2e <code>\bibliography</code> : Use <code>\@input@</code> so include files are listed. . . . .	419
1994-01-05 <code>fontdef.dtx</code> v2.1d General: Removed <code>nf</code> prefix from file names. . . . .	245	1994-01-18 <code>ltclass.dtx</code> v0.2t <code>\@ifclassloaded</code> : Fix typo <code>\@pkgetension</code> . . . . .	501
1994-01-13 <code>ltmath.dtx</code> v0.9o <code>\@eqnocr</code> : correcting 0.9i . . . . .	303	1994-01-18 <code>ltfiles.dtx</code> v0.9p <code>\@iffileonpath</code> : Macro added . .	97
General: correcting 0.9i . . . . .	302	<code>\@input</code> : do not use a different definition for <code>\input@path</code> . .	99
1994-01-14 <code>ltdirchk.dtx</code> v0.2d <code>\IfFileExists</code> : Close the <code>texsys.aux</code> output stream . . .	10	<code>\@input@</code> : Macro added . . . . .	99
1994-01-15 <code>ltfiles.dtx</code> v0.9o <code>\document</code> : move <code>\@preamblecmds</code> after document hook . . . . .	92	<code>\IfFileExists@</code> : New Definition <code>\include</code> : Use <code>\@input@</code> so include files are listed. . . . .	94
1994-01-17 <code>ltclass.dtx</code> v0.2s <code>\@fileswithoptions</code> : Modify to reduce parameter stack usage . . . . .	510, 511	<code>\InputIfFileExists</code> : New Definition . . . . .	98
General: Added many more <code>\@onlypreamble</code> commands . .	500	1994-01-18 <code>ltfssini.dtx</code> v2.1f <code>\not@math@alphabet</code> : Message corrected . . . . .	238
Wrapped long lines to column 72 . . . . .	500	1994-01-18 <code>ltmiscen.dtx</code> v0.9p <code>\@verbatim</code> : Add <code>\global\@inlabelfalse</code> . . .	289
1994-01-17 <code>ltfiles.dtx</code> LaTeX2e <code>\listfiles</code> : New Version, adds ' <code>.tex</code> ' if needed, and lines up columns . . . . .	100	Only add <code>\penalty</code> if in <code>hmode</code> .	289
1994-01-17 <code>ltfssbas.dtx</code> v2.1a General: New math font setup . .	163	1994-01-19 <code>fontdef.dtx</code> v2.1e General: Added missing setting for symbols in bold version. . . .	249
<code>\curr@math@size</code> : New math font setup . . . . .	172	1994-01-19 <code>ltdirchk.dtx</code> v0.2e <code>\IfFileExists</code> : name changed from <code>\test</code> . . . . .	9
<code>\everydisplay</code> : New math font setup . . . . .	172	<code>\input@path</code> : No longer check that an empty group is in the path .	11
<code>\everymath</code> : New math font setup	172	<code>\strip@prefix</code> : name changed from <code>\strip@meaning</code> , to match NFSS. . . . .	5
<code>\frozen@everydisplay</code> : New math font setup . . . . .	172	1994-01-19 <code>ltmath.dtx</code> v1.0n classes <code>\mathindent</code> : Deferred setting of <code>\mathindent</code> . . . . .	304
<code>\frozen@everymath</code> : New math font setup . . . . .	172	1994-01-20 <code>ltdirchk.dtx</code> v0.2f General: <code>\@copytexsys</code> and the <code>texsys.new</code> file removed . . . .	9
		Modify all of <code>ltxcheck</code> . . . . .	14

<code>\IfFileExists: \copytexsys</code>	1994-01-31 <code>lftntcmd.dtx v3.1b</code>
removed . . . . . 10	General: <code>\@normalsize</code> no longer defined . . . . . 266
1994-01-21 <code>ltclass.dtx v0.2u</code>	1994-02-01 <code>ltpage.dtx LaTeX2e</code>
<code>\documentstyle: compatibility file</code>	<code>\pagestyle: (DPC)</code> Modify to get nicer error message . . . . . 421
now <code>latex209.def</code> . . . . . 507	<code>\thispagestyle: (DPC)</code> Modify to get nicer error message . . . . . 422
1994-01-21 <code>ltdirchk.dtx v0.2g</code>	1994-02-02 <code>ltclass.dtx v0.2x</code>
General: Improve documentation, reorganise docstrip module . . . 1	<code>\@fileswithoptions: Only run</code> the hook and options check if the file was loaded. . . . . 512
<code>\filename@parse: Minor changes, and add Mac version (:)</code> . . . . 11	1994-02-03 <code>ltoutput.dtx v1.0k</code>
<code>\today: Name changed from</code> <code>\stamp</code> , to save memory . . . . . 9	<code>\@makespecialcolbox: correct</code> mistakes in the documentation . . . . . 450
1994-01-21 <code>ltfloat.dtx LaTeX2e</code>	1994-02-07 <code>ltclass.dtx v0.2y</code>
<code>\@xfloat: Added missing percent</code> characters. . . . . 400	<code>\@fileswithoptions: Run</code> <code>\@compatibility</code> on the first class to start (not the first to finish) . . . . . 510
1994-01-21 <code>ltmiscen.dtx v0.9s</code>	<code>\@ifclasswith: Add extra ,s so</code> ‘two’ is not matched with ‘twocolumn’ . . . . . 503
<code>\verbatim@font: Removed</code> unnecessary category code hackery. . . . . 290	<code>\ProcessOptions*: Add extra ,s so</code> ‘two’ is not matched with ‘twocolumn’ . . . . . 506
1994-01-24 <code>ltdirchk.dtx v0.2h</code>	1994-02-07 <code>ltfssbas.dtx v2.1c</code>
<code>\IfFileExists: Stop testing once</code> <code>texsys.aux</code> has been found . . . 10	<code>\DeclareFontEncoding: revert</code> catcode settings earlier . . . . 165
1994-01-24 <code>ltpage.dtx LaTeX2e</code>	<code>\DeclareFontShape: revert</code> catcode settings earlier . . . . 164
<code>\pagestyle: (DPC)</code> Complain if <code>pagestyle</code> is undefined. . . . . 421	1994-02-08 <code>ltoutput.dtx v1.0k</code>
1994-01-25 <code>ltdirchk.dtx v0.2i</code>	<code>\@makespecialcolbox:</code> <code>boxmaxdepth</code> setting added . . 449
General: Protect against looping on <code>\@@input</code> and <code>\@@end</code> . . . . . 2	<code>boxmaxdepth</code> setting removed . . 449
1994-01-25 <code>ltfssbas.dtx v2.1b</code>	General: Documentation and tasks tidied. . . . . 424
<code>\math@version: Corrections for</code> math setup . . . . . 172	1994-02-10 <code>ltclass.dtx v0.2z</code>
1994-01-25 <code>ltmath.dtx LaTeX2e</code>	<code>\@documentclasshook: Changed</code> the name from <code>\@compatibility</code> to <code>\@documentclasshook</code> , and added the check for whether <code>\@normalsize</code> has been defined. ASAJ. . . . . 500
<code>\bordermatrix: Removed</code>	<code>\@fileswithoptions: Renamed</code> <code>\@compatibility</code> to <code>\@documentclasshook</code> . ASAJ. 510
<code>\p@renwd</code> . . . . . 298	1994-02-10 <code>ltfssbas.dtx v2.1d</code>
1994-01-26 <code>ltfsssrc.dtx v2.3c</code>	<code>\addto@hook: Made \addto@hook</code> long. . . . . 183
<code>\check@mathfonts: Correct trace</code> info placement . . . . . 194	
<code>\restglb@settings: Correct trace</code> info placement . . . . . 194	
1994-01-27 <code>lftntcmd.dtx v3.1a</code>	
<code>\nocorrlist: Only ., used as</code> default for cm fonts . . . . . 272	
1994-01-29 <code>ltclass.dtx v0.2v</code>	
<code>\@unprocessedoptions: Macro</code> added. . . . . 513	
<code>\@fileswithoptions: All options</code> raise error if no <code>\ProcessOptions</code> appears . . 512	
1994-01-31 <code>ltclass.dtx v0.2w</code>	
<code>\g@addto@macro: Use toks register</code> to avoid ‘hash’ problems . . . 513	
1994-01-31 <code>ltfiles.dtx v0.9t</code>	
<code>\document: set \@normalsize or</code> <code>\normalsize</code> if necessary . . . . 91	



1994-02-10 ltfsncmp.dtx v2.1d	Long lines wrapped to 72 columns . . . . .	88
\scan@fontshape: scan away stuff after pt . . . . .		208
1994-02-22 ltfsini.dtx v2.1g	General: Add code from the old dump.dtx . . . . .	567
General: Correct error message . .	Initial version, split from latex.dtx . . . . .	555
1994-02-24 ltfsbas.dtx v2.1e	move code here from lhyphen.dtx . . . . .	560
\DeclareFontShape: Separate restoration of catcodes for fd cmds . . . . .	Remove oldcomments environment . . . . .	555
\define@newfont: Separate restoration of catcodes for fd cmds . . . . .	use \InputIfFileExists not \IfFileExists . . . . .	560
\nfss@catcodes: Separate restoration of catcodes for fd cmds . . . . .		174
1994-02-25 ltdirchk.dtx v0.2j	1994-03-07 ltfloat.dtx v1.0a	
General: Remove need for drv file .	\endfloatbox: (DPC) Extra group for colour . . . . .	405
1994-03-01 ltdirchk.dtx v0.2k	\@footnotetext: (DPC) Extra group for colour . . . . .	413
General: Add unstripped module, so that dircheck.dtx may be used with initex . . . . .	\@xfloat: (DPC) Extra group for colour . . . . .	401
1994-03-02 ltboxes.dtx v0.1e	1994-03-07 lthyphen.dtx v0.1c	
General: Add 2kernel module . .	General: move the 2kernel code to ltfinal.dtx . . . . .	528
Remove need for drv file . . . .	1994-03-07 ltlength.dtx v1.0a	
1994-03-02 ltclass.dtx v0.3a	\@settodim: (DPC) Extra group for colour . . . . .	162
General: Remove need for driver file . . . . .	1994-03-07 ltlists.dtx v1.0a	
1994-03-03 ltboxes.dtx v0.1f	General: Initial version, split from latex.dtx . . . . .	308
\@irsbox: Replaced a missing \else . . . . .	Long lines wrapped to 72 columns . . . . .	308
1994-03-04 ltfloat.dtx v1.0a	1994-03-07 ltpage.dtx v1.0a	
General: Initial version, split from latex.dtx . . . . .	General: Initial version, split from ltherest.dtx . . . . .	421
1994-03-04 ltsect.dtx v1.0a	1994-03-07 ltpictur.dtx v0.1a	
General: Initial version, split from latex.dtx . . . . .	General: Initial version, split from latex.dtx . . . . .	357
1994-03-04 lttab.dtx v1.0a	Long lines wrapped to 72 columns . . . . .	357
General: Initial version, split from latex.dtx . . . . .	1994-03-07 ltsect.dtx v1.0a	
1994-03-04 ltvers.dtx v1.0a	\@hangfrom: (DPC)Extra groups for colour . . . . .	391
General: Initial version, split from latex.dtx . . . . .	1994-03-07 lttab.dtx v1.0a	
1994-03-07 ltboxes.dtx v0.1a	General: Long lines wrapped to 72 columns . . . . .	335
\@mpfootnotetext: Extra group for colour . . . . .	1994-03-08 ltclass.dtx v0.3b	
1994-03-07 ltboxes.dtx v1.0a	General: Modify driver code into 'new style' . . . . .	500
General: Unify format with other Kernel files . . . . .	1994-03-08 ltdirchk.dtx v1.0a	
1994-03-07 ltdefs.dtx v1.0a	General: Reorganise driver module into 'new style' . . . . .	1
\@italiccorr: Macro added . . .	1994-03-08 ltplain.dtx v1.0a	
1994-03-07 ltfiles.dtx v1.0a	General: Remove need for a driver file. . . . .	15
General: Initial version, split from latex.dtx . . . . .		88

1994-03-10 ltffsbas.dtx v2.2f	1994-03-13 ltfiles.dtx v0.3b
$\backslash$ math@egroup: Changed	$\backslash$ InputIfFileExists: Use new
$\backslash$ begingroup/ $\backslash$ endgroup to	cmd $\backslash$ @addtofilelist . . . . . 98
$\backslash$ bgroup/ $\backslash$ egroup. . . . . 181	1994-03-13 ltffsbas.dtx v2.1g
1994-03-11 ltssdcl.dtx v2.1b	General: add 2ekernel module to
$\backslash$ DeclareSymbolFontAlphabet@:	omit repeated code . . . . . 163
Added check against use of	1994-03-13 ltssdcl.dtx v2.1c
alphabet switch outside of	General: add 2ekernel module to
math mode. . . . . 236	omit repeated code . . . . . 211
$\backslash$ SetMathAlphabet@: Changed	1994-03-14 ltboxes.dtx v1.0b
parameter template in	$\backslash$ @isavebox: Use
temporary macro to catch	$\backslash$ color@setgroup . . . . . 326
check add below. . . . . 224	$\backslash$ @isavepicbox: Use
1994-03-12 ltclass.dtx v0.3c	$\backslash$ color@setgroup . . . . . 326
$\backslash$ @fileswithoptions: Do not use	$\backslash$ color@begingroup: macro added
$\backslash$ @pr@videpackage to avoid	for colour support . . . . . 325
timeout . . . . . 511	$\backslash$ color@endgroup: macro added for
General: Change name from	colour support . . . . . 325
docclass to ltclass . . . . . 500	$\backslash$ lrbox: Use $\backslash$ color@setgroup . . 326
$\backslash$ ProvidesFile: Add $\backslash$ wlog . . . 504	$\backslash$ sbox: Use $\backslash$ color@setgroup . . . 326
$\backslash$ ProvidesPackage: Add $\backslash$ wlog . . 504	1994-03-14 ltfloat.dtx 1.0c
use $\backslash$ @gtempa . . . . . 504	$\backslash$ @xympar: (DPC) Use
1994-03-12 ltdefs.dtx v1.0b	$\backslash$ color@begingroup . . . . . 409
$\backslash$ @reargdef: New defn, in terms of	1994-03-14 ltfloat.dtx v1.0c
$\backslash$ @yargdef . . . . . 41	$\backslash$ @endfloatbox: (DPC) Use
$\backslash$ @yargd@f: Name changed from	$\backslash$ color@endgroup . . . . . 405
$\backslash$ XXX@argdef . . . . . 40	$\backslash$ @footnotetext: (DPC) Use
1994-03-12 ltdirchk.dtx v1.0b	$\backslash$ color@begingroup, add
General: Change name from	$\backslash$ endgraf . . . . . 413
dircheck.dtx . . . . . 1	$\backslash$ @savemarbox: (DPC) Use
Minor edits to the timeouts in	$\backslash$ color@begingroup . . . . . 408
ltxcheck . . . . . 1	$\backslash$ @xfloat: (DPC) Use
1994-03-12 ltfloat.dtx v1.0b	$\backslash$ color@begingroup . . . . . 401
$\backslash$ @savemarbox: (DPC) Extra group	1994-03-15 ltfiles.dtx LaTeX2e
for colour . . . . . 408	$\backslash$ @missingfileerror: Quit on x or
$\backslash$ @xympar: (DPC) Extra bgroup for	X just like a real error . . . . . 99
colour . . . . . 409	1994-03-15 ltfntcmd.dtx v3.2a
1994-03-12 ltplain.dtx v1.0b	General: Adapted to mass
General: Name changed from	formatting . . . . . 266
lplain. The end of an era . . . . 15	Changed $\backslash$ / to $\backslash$ @italiccorr 266
1994-03-12 ltplain.dtx v1.0e	Removed $\backslash$ @renewfontswitch . 266
General: Replaced remaining	Removed defs of short-forms and
width, height, depth by L <sup>A</sup> T <sub>E</sub> X	all sizes except $\backslash$ normalize . 266
macro names to save tokens. . . 15	1994-03-15 ltoutput.dtx v1.0l
1994-03-13 ltcntrl.dtx v1.0c	$\backslash$ @addtocurcol: Changed
$\backslash$ @tfor: (DPC) Add $\backslash$ @tfor so a	$\backslash$ addvspace to $\backslash$ skip . . 464, 468
single group is correctly	$\backslash$ @combinedblfloats: Removed
treated. . . . . 59	boxmaxdepth setting. . . . . 456
1994-03-13 ltfiles.dtx LaTeX2e	$\backslash$ @makecol: $\backslash$ maxdepth changed to
$\backslash$ @addtofilelist: Macro added . 100	$\backslash$ @maxdepth . . . . . 447
$\backslash$ listfiles: Reset	Removed boxmaxdepth setting. 448
$\backslash$ @addtofilelist at begin	$\backslash$ @makespecialcolbox: Removed
document . . . . . 101	boxmaxdepth setting. . . . . 449

<code>\@topnewpage</code> : Corrected and amended warning message . .	440	1994-03-28 ltsect.dtx v1.0b	
Warning added: it should be improved . . . . .	441	General: Split further from ltherest.dtx . . . . .	384
General: Added some warnings when page gets full of top floats. . . . .	424	1994-03-28 lttab.dtx v1.0b	
Driver added and further tidying. . . . .	424	General: Improve documentation	335
Removed duplicated code and corrected docstrip options. . .	424	1994-03-28 ltthm.dtx v1.0a	
Some boxmaxdepth settings removed. . . . .	424	General: Initial version, split from latex.dtx . . . . .	380
1994-03-16 ltclass.dtx v0.3f		1994-03-29 ltcounts.dtx v1.0c	
General: Add pkgindoc package .	527	General: Create file from parts of ltmiscen and ltherest. . . . .	155
1994-03-16 ltfiles.dtx LaTeX2e		1994-03-29 ltlength.dtx v1.0c	
<code>\listfiles</code> : Move this code directly into <code>\document</code> . . . .	101	General: Create file ltcntlen from parts of ltmiscen and ltherest.	162
1994-03-16 ltfiles.dtx v1.0c		1994-03-29 ltmiscen.dtx v1.0d	
<code>\document</code> : (DPC) directly add file list settings . . . . .	91	General: Remove counter macros to ltcntlen . . . . .	279
1994-03-16 ltmiscen.dtx v1.0b		1994-03-29 ltpageno.dtx v1.0c	
<code>\@verbatim</code> : Remove <code>\global\@inlabelfalse</code> again. . . . .	289	General: Create file ltcntlen from parts of ltmiscen and ltherest.	274
1994-03-28 ltalloc.dtx v1.0d		1994-03-29 ltxref.dtx v1.0c	
General: Redefinition of ‘new’ allocations removed. . . . .	54	General: Create file ltcntlen from parts of ltmiscen and ltherest.	275
1994-03-28 ltdirchk.dtx v1.0d		1994-03-31 ltbibl.dtx v1.0a	
General: Improve documentation .	1	General: Initial version of ltidxbib.dtx, split from ltherest.dtx . . . . .	417
1994-03-28 lterror.dtx v1.0d		1994-03-31 ltidxglo.dtx v1.0a	
<code>\@invalidchar</code> : (DPC) Comment out (use catcode15 instead) . .	67	General: Initial version of ltidxbib.dtx, split from ltherest.dtx . . . . .	415
General: Remove test for <code>\inputlineno</code> undefined. . . . .	64	1994-04-09 ltcounts.dtx v1.0d	
1994-03-28 ltfiles.dtx v1.0d		<code>\@newctr</code> : <code>\@nocnterr</code> now has counter name argument . . . .	156
<code>\document</code> : (DPC) Use <code>\normalsize</code> not <code>\@normalsize</code> . . . . .	91	<code>\addtocounter</code> : <code>\@nocnterr</code> now has counter name argument .	156
(DPC) remove <code>\@normalsize</code> check . . . . .	91	<code>\setcounter</code> : <code>\@nocnterr</code> now has counter name argument . . . .	156
1994-03-28 ltfloat.dtx v1.0b		<code>\stepcounter</code> : Use <code>\addtocounter</code> to have name checked . . . . .	156
<code>\caption</code> : Use <code>\normalsize</code> not <code>\@normalsize</code> . . . . .	399	1994-04-09 ltthm.dtx v1.0b	
General: Split further from ltherest.dtx . . . . .	396	<code>\@othm</code> : Use standard counter error message (FMi) . . . . .	382
1994-03-28 ltlists.dtx v1.0b		1994-04-11 ltclass.dtx v0.3g	
General: Improve documentation	307	<code>\endfilecontents</code> : Add star form, dont write <code>\endinput</code> at the end of the file. . . . .	514
1994-03-28 ltmiscen.dtx v1.0c		<code>\ProvidesFile</code> : Protect against weird catcodes. . . . .	504
General: Improve Documentation	279	1994-04-11 ltfsbas.dtx v2.1h	
1994-03-28 ltplain.dtx v1.0c		General: Added <code>\defaultscriptratio</code> and <code>\defaultscriptscriptratio</code> . ASAJ. . . . .	163
<code>\newlanguage</code> : Remove some <code>\outer</code> declarations. . . . .	17		

<code>\defaultscriptratio</code> : Macro added . . . . .	181	<code>\no@alphabet@error</code> : Use std LaTeX error macro . . . . .	163
<code>\defaultscriptscriptratio</code> : Macro added . . . . .	181	1994-04-18 <code>ltfssdcl.dtx</code> ???	
1994-04-12 <code>ltboxes.dtx</code> v1.0c		<code>\DeclareMathAlphabet</code> : Pass correct arg (2 not 3) . . . . .	222
General: Remove <code>\@acci</code> , now defined in <code>ltplain.dtx</code> . . . . .	329	1994-04-18 <code>ltfssdcl.dtx</code> v2.1d	
Remove <code>\@dischyph</code> , now defined in <code>ltinit.dtx</code> . . . . .	329	General: Removed surplus <code>\no@alphabet@error</code> (see <code>fam.dtx</code> ) . . . . .	211
1994-04-12 <code>ltdefs.dtx</code> v1.0g		1994-04-18 <code>ltfstrc.dtx</code> v2.3d	
<code>\@dischyph</code> : Define <code>\@dischyph</code> , was previously in <code>ltboxes.dtx</code> . . . . .	51	General: Changed to new error/warning scheme . . . . .	185
1994-04-12 <code>ltplain.dtx</code> v1.0d		<code>\font@submax</code> : Changed dimen to macro . . . . .	202
General: Define <code>\@acci</code> . . . . .	29	<code>\fontsubfuzz</code> : Changed dimen to macro . . . . .	202
1994-04-12 <code>ltvers.dtx</code> v1.0b		<code>\subst@size</code> : <code>\font@submax</code> and <code>\fontsubfuzz</code> now macros . . . . .	203
General: Have version info generated automatically. . . . .	33	1994-04-19 <code>ltpage.dtx</code> v1.0b	
1994-04-14 <code>ltfntcmd.dtx</code> v3.2b		General: Improve documentation . . . . .	421
General: Macros renamed to non-private forms, JB . . . . .	266	1994-04-20 <code>ltfntcmd.dtx</code> v3.3a	
<code>\DeclareOldFontCommand</code> : Renamed from <code>\@newfontswitch</code> . . . . .	272	General: Documentation up-dated . . . . .	266
1994-04-15 <code>ltboxes.dtx</code> v1.0d		New implementation of <code>\nocorr</code> . . . . .	266
<code>\@isavebox</code> : Added missing procent character. . . . .	326	<code>\check@nocorr@</code> : Macros added . . . . .	269
1994-04-17 <code>ltcounts.dtx</code> v1.0e		<code>\maybe@ic@</code> : <code>\nocorr</code> etc removed from list of tokens to check, leaving only punctuation characters . . . . .	271
<code>\@newctr</code> : Use <code>\@nocounterr</code> instead of <code>\@nocnterr</code> . . . . .	156	1994-04-20 <code>ltmiscen.dtx</code> v1.0e	
<code>\addtocounter</code> : Use <code>\@nocounterr</code> instead of <code>\@nocnterr</code> . . . . .	156	<code>\enddocument</code> : Changed logic for producing warning messages . . . . .	281
<code>\setcounter</code> : Use <code>\@nocounterr</code> instead of <code>\@nocnterr</code> . . . . .	156	1994-04-21 <code>ltboxes.dtx</code> v1.0e	
1994-04-17 <code>lterror.dtx</code> v1.0h		<code>\@iiiminipage</code> : Extra <code>\bgroup</code> for colour . . . . .	331
<code>\@nocounterr</code> : New name for error message, old error message (without arg) kept . . . . .	65	<code>\@mpfootnotetext</code> : Extra <code>\endgraf</code> for colour . . . . .	332
1994-04-17 <code>ltthm.dtx</code> v1.0c		<code>\endminipage</code> : Extra <code>\egroup</code> for colour . . . . .	331
<code>\@othm</code> : Use new std counter error message (FMi) . . . . .	382	1994-04-21 <code>ltfinal.dtx</code> v0.1c	
1994-04-18 <code>ltfinal.dtx</code> v0.1b		General: Added comments, set the catcodes of 128–255. . . . .	555
General: Initialise <code>\textheight</code> , <code>\textwidth</code> and page style . . . . .	557	1994-04-22 <code>ltfssini.dtx</code> v2.1g	
1994-04-18 <code>ltfloat.dtx</code> v1.0d		<code>\not@math@alphabet</code> : Message changed again . . . . .	238
<code>\@footnotetext</code> : (DPC) Remove Colour support . . . . .	413	1994-04-23 <code>ltfinal.dtx</code> v0.1d	
<code>\@savemarbox</code> : (DPC) Remove Colour support . . . . .	408	General: Check that <code>\font@submax</code> is still zero . . . . .	555
1994-04-18 <code>ltfssbas.dtx</code> v2.1i		1994-04-24 <code>ltoutput.dtx</code> v1.0m	
General: Macro <code>\no@alphabet@help</code> removed again . . . . .	163	<code>\@resetfps</code> : Number 2 changed to <code>\tw@</code> . . . . .	485
<code>\calculate@math@sizes</code> : Changed message to log only . . . . .	181	Warning changed . . . . .	485

<p><code>\@specialoutput</code>: Message changed to give more info and ‘top’ removed . . . . . 442</p> <p><code>\@topnewpage</code>: Message changed to give more info . . . . . 441</p> <p>Warning message removed as it will be generated later . . . . 440</p> <p>General: Changed <code>\@normalsize</code> to <code>\normalsize</code>. . . . . 424</p> <p>Corrected unverbbed commands in documentation. . . . . 424</p> <p>Removed some long lines and other aesthetic changes. . . . 424</p> <p>Warning messages changed/corrected. . . . . 424</p> <p>1994-04-24 ltpictur.dtx v0.1b</p> <p>General: Removed surplus spaces after <code>\hbox to</code> in several cases . . . . . 357</p> <p>1994-04-25 ltclass.dtx v0.3h</p> <p>General: Removed spurious extra ‘.’s at the end of error messages . . . . . 500</p> <p>1994-04-25 ltfloat.dtx v1.0e</p> <p><code>\@largefloatcheck</code>: Changed warning message to give more info . . . . . 405</p> <p>Command added . . . . . 405</p> <p>General: Changed warning messages . . . . . 396</p> <p>Removed obsolete tracing code 396</p> <p>1994-04-27 ltfsstrc.dtx v2.3e</p> <p>General: Corrected item that was forgotten in last change. . . . 185</p> <p>1994-04-28 lterror.dtx v1.0j</p> <p><code>\@inmatherr</code>: Macro added . . . . 67</p> <p>1994-04-28 lterror.dtx v1.1c</p> <p><code>\@inmatherr</code>: Replaced <code>\noexpand</code> with <code>\protect</code>. . . . . 67</p> <p>1994-04-28 ltssdcl.dtx v2.1e</p> <p>General: Removed all <code>\uppercase</code> in hex num parsing macros . 211</p> <p>1994-04-28 ltlists.dtx v1.0c</p> <p>General: Replaced <code>\@ltxnomath</code> by <code>\@inmatherr</code> . . . . . 317</p> <p>1994-04-28 ltpictur.dtx v0.1c</p> <p>General: bezier curves added . . . 377</p> <p><code>\multiput</code>: (DPC) Ignore spaces between )( . . . . . 359</p> <p>(DPC) Macro added . . . . . 359</p> <p><code>\picture</code>: (DPC) Ignore spaces before ( . . . . . 358</p>	<p>1994-04-28 ltplain.dtx v1.0g</p> <p>General: Turn off overfull box tracing in log . . . . . 25</p> <p>1994-04-29 ltclass.dtx v1.0a</p> <p>General: Change version number to 1 (no other change) . . . . 500</p> <p>1994-04-29 ltmiscen.dtx v1.0f</p> <p><code>\@verbatim</code>: <code>\leavevmode</code> added 289</p> <p>Change to <code>\everypar</code> added . . 290</p> <p>1994-04-29 ltoutenc.dtx 1.4a</p> <p>General: Removed</p> <p><code>\EncodingSpecific</code>. Renamed all the commands. Added</p> <p><code>\DeclareTextGlyph</code> and</p> <p><code>\UndeclareTextCommand</code>. . . . 106</p> <p>Removed Rokicki’s OT1 variant encoding. Moved the driver to the top. . . . . 105</p> <p>1994-04-30 ltfontcmd.dtx v3.3b</p> <p>General: Documentation up-dated and tidied . . . . . 266</p> <p>Prefix frag@ changed to frag in</p> <p><code>\@protecteddef</code> . . . . . 266</p> <p>Title changed . . . . . 266</p> <p>Warning changed to info message in <code>\@protecteddef</code> . 266</p> <p>1994-04-30 ltoutput.dtx v1.0n</p> <p><code>\@activechar@info</code>:</p> <p><code>\@activechar@warning</code> changed to</p> <p><code>\@activechar@info</code> . . . . . 450</p> <p><code>\@combinedblfloats</code>: Removed rule in topnewpage case . . . . 456</p> <p><code>\@emptycol</code>: Empty column action added: <code>\@emptycol</code> . . . . . 439</p> <p><code>\@flsetnum</code>: Rogue space removed . . . . . 485</p> <p><code>\@specialoutput</code>: Cut-off point changed to 2<code>\baselineskip</code> . 442</p> <p>Empty column action added:</p> <p><code>\@emptycol</code> . . . . . 442</p> <p>Extra empty column added for twocolumn case . . . . . 442</p> <p>Extra empty column added for twocolumn case (wrong, see below) . . . . . 442</p> <p><code>\@topnewpage</code>: Added setting of <code>\col@number</code> . . . . . 439</p> <p>Cut-off point changed to 3<code>\baselineskip</code> . . . . . 441</p> <p>Empty column action added:</p> <p><code>\@emptycol</code> . . . . . 441</p> <p>Message changed for Frank . . . 441</p>
---	--

General: <code>\@activechar@warning</code>	Set all the catcodes . . . . .	555
changed to an info message. . . . .	1994-05-02 <code>ltfinal.dtx</code> v0.1f	
Added <code>\col@number</code> . . . . .	General: Set the catcode of	
Documentation tidied. . . . .	control-J. . . . .	564
Empty column action added. . . . .	1994-05-02 <code>ltmiscen.dtx</code> v1.0g	
Fixed bug from <code>\dblfigrule</code>	General: Changed 91 to 1991 and	
with <code>\@topnewpage</code> . . . . .	moved some bits . . . . .	279
Full of floats action improved. . . . .	1994-05-02 <code>ltoutput.dtx</code> v1.0o	
<code>\col@number</code> : Added	<code>\@resethfps</code> : Code shortened . . . . .	485
<code>\col@number</code> . . . . .	General: Code of <code>\@resethfps</code>	
<code>\onecolumn</code> : Added setting of	shortened. . . . .	424
<code>\col@number</code> . . . . .	1994-05-03 <code>ltbibl.dtx</code> v1.0b	
1994-05-01 <code>lterror.dtx</code> v1.0k	<code>\nocite</code> : Make <code>\nocite</code> issue a	
<code>\@latexerr</code> : (CAR) Added draft	warning for an undefined	
<code>\@latexinfo</code> . . . . .	citation key. . . . .	419
1994-05-01 <code>ltoutenc.dtx</code> 1.4a	1994-05-03 <code>ltfinal.dtx</code> v0.1f	
General: Added the <code>\a</code> command. . . . .	General: Set the catcode of	
Added the <code>\SaveAtCatcode</code> and	control-J to be ‘other’, for use	
<code>\RestoreAtCatcode</code>	in messages. . . . .	555
commands. . . . .	1994-05-03 <code>lfloat.dtx</code> v1.0f	
Removed the <code>uc/lc</code> table	General: (CAR) Added	
settings, since the T1 <code>uc/lc</code>	<code>\@largefloatcheck</code> . . . . .	396
table is now the default. . . . .	Removed unnecessary braces	
Rewrote for the new	from arguments of	
syntax. . . . .	<code>\@ifnextchar</code> . . . . .	396
1994-05-01 <code>ltoutenc.dtx</code> v1.4a	<code>\end@dblfloat</code> :	
General: Removed Rokicki’s	<code>\@largefloatcheck</code> added . . . . .	404
encoding. . . . .	<code>\end@float</code> : (CAR) Added	
Renamed the commands,	<code>\@largefloatcheck</code> . . . . .	403
removed the	1994-05-03 <code>ltfssdcl.dtx</code> v2.1f	
<code>\EncodingSpecific</code> command.	General: Renamed	
Turned all slots into decimal.	<code>\@@DeclareMathDelimiter</code> to	
Added <code>\a</code> . . . . .	<code>\@DeclareMathDelimiter</code> . . . . .	211
1994-05-02 <code>ltcntrl.dtx</code> v1.0l	1994-05-03 <code>ltlists.dtx</code> v1.0d	
<code>\@break@tfor</code> : Macro added (from	<code>\@item</code> : <code>\hskip</code> changed to <code>\kern</code> . . . . .	318
<code>ltfiles.dtx</code> ) . . . . .	General: Removed superfluous	
1994-05-02 <code>ltdefns.dtx</code> v1.1f	braces . . . . .	317
<code>\renewcommand</code> : Removed surplus	1994-05-03 <code>ltmiscen.dtx</code> v1.0h	
<code>\space</code> in error . . . . .	<code>\@centercr</code> : <code>\@badcrerr</code> replaced	
<code>\renewenvironment</code> : Removed	by <code>\@nolnerr</code> . . . . .	287
surplus <code>\space</code> in error . . . . .	1994-05-03 <code>lftab.dtx</code> v1.0d	
1994-05-02 <code>ltfiles.dtx</code> v1.0f	<code>\endpbox</code> : Use <code>\@finalstrut</code>	
<code>\@iffilenamepath</code> : <code>\@break@loop</code>	based on depth of	
renamed to <code>\@break@tfor</code> . . . . .	<code>\@arstrutbox</code> . . . . .	356
<code>\@obsoletefile</code> : Make	1994-05-04 <code>ltclass.dtx</code> v1.0b	
<code>\@onlypreamble</code> . . . . .	<code>\NeedsTeXFormat</code> : Changed	
1994-05-02 <code>ltfinal.dtx</code> v0.1e	wording of the warning . . . . .	509
General: Added setting the ‘letter’	1994-05-04 <code>lterror.dtx</code> v1.0m	
catcodes. . . . .	<code>\@badcrerr</code> : Error message	
Added setting the ‘other’	removed . . . . .	67
catcodes. . . . .	1994-05-05 <code>ltbibl.dtx</code> v1.0c	
Added setting the special	<code>\@citex</code> : Set switch for warning	
catcodes. . . . .	and end of run. . . . .	418
Made slot 127 illegal . . . . .		



<code>\nocite</code> : Do not write page number in <code>\nocite</code> warning message. . . . .	419	<code>\@iiiminipage</code> : Use new <code>\color@setgroup</code> concept. . .	331
Set switch for warning and end of run. . . . .	419	<code>\@mpfootnotetext</code> : Use new <code>\color@setgroup</code> concept. . .	332
1994-05-05 ltfinal.dtx v0.1g		Use new <code>\normalcolor</code> and <code>\@finalstrut</code> . . . . .	332
General: Added empty errhelp. . .	555	General: Superfluous braces removed from several commands . . . . .	323
<code>\errhelp</code> : Set error help empty. .	568	<code>\color@setgroup</code> : macro added for colour support . . . . .	325
1994-05-05 ltfntcmd.dtx v3.3c		<code>\endminipage</code> : Use new <code>\color@setgroup</code> concept. . .	331
<code>\@math@egroup</code> : Corrected <code>\@fontswitch</code> and added saved versions . . . . .	273	1994-05-11 ltclass.dtx v1.0c	
General: Corrected <code>\@fontswitch</code>	266	<code>\endfilecontents</code> : Add checks for form feed and tab . . . . .	514
1994-05-05 ltmiscen.dtx v1.0i		1994-05-11 ltdirchk.dtx v1.0e	
General: Removed braces from <code>ifnextchar</code> and <code>ifstar</code> arguments . . . . .	279	General: Add <code>\ProvidesFile</code> as used in fd files. . . . .	4
1994-05-07 lttab.dtx v1.0c		1994-05-11 lterror.dtx v1.0o	
<code>\@maxtab</code> : Changed <code>\@firsttab</code> to <code>\chardef</code> . . . . .	339	<code>\@latexerr</code> : (ASAJ) Removed one of the extra blank lines to <code>\@latexerr</code> . . . . .	65
Changed <code>\@maxtab</code> to <code>\chardef</code>	339	1994-05-11 ltlogos.dtx v1.0o	
General: Removed definition of <code>\+</code>	335	<code>\LaTeX</code> : Use <code>\DeclareProtectedCommand</code> . ASAJ. . . . .	87
Removed surplus braces from <code>\@ifnextchar</code> constructs . . .	335	<code>\LaTeXe</code> : Use <code>\DeclareProtectedCommand</code> . ASAJ. . . . .	87
1994-05-08 ltfntcmd.dtx v3.3d		1994-05-11 ltoutenc.dtx 1.5a	
General: Removed <code>\@undefinedfonterror</code> . . . .	266	General: Made T1 and OT1 generate packages rather than def files. Renamed the ‘package’ module to ‘teststy’. . .	105
<code>\normalsize</code> : Removed <code>\@undefinedfonterror</code> . . . .	273	1994-05-11 ltoutenc.dtx v1.5a	
1994-05-09 ltfntcmd.dtx v3.3f		General: Reimplemented <code>\DeclareTextCommand</code> using <code>\@changed@cmd</code> and <code>\DeclareProtectedCommand</code> . . .	106
General: Replaced all <code>\next</code> by <code>\@let@token</code> and undo change 3.3e, whatever that was. . . .	266	Renamed the commands again. Made the encoding part of the command syntax. Added the <code>\DeclareTextCommand</code> interface. Used <code>\DeclareProtectedCommand</code> . . .	102
1994-05-10 ltdefns.dtx v1.0n		<code>\DeclareTextAccent</code> : Reimplemented using <code>\DeclareTextCommand</code> . . . .	108
General: (ASAJ) Added <code>\DeclareProtectedCommand</code> . . .	36	1994-05-11 ltspc.dtx v1.0o	
Added <code>\DeclareProtectedCommand</code> . .	44	<code>\,</code> : Use <code>\DeclareRobustCommand</code> . ASAJ. . . . .	85
Removed braces around <code>\@ifundefined</code> argument. ASAJ. . . . .	41	<code>\hspace</code> : Use <code>\DeclareRobustCommand</code> .	
<code>\makeatother</code> : Added <code>\makeatletter</code> and <code>\makeatother</code> ASAJ. . . . .	51		
1994-05-10 lterror.dtx v1.0n			
<code>\@latexerr</code> : (ASAJ) Added extra blank lines to <code>\@latexerr</code> . . . .	65		
1994-05-10 ltmiscen.dtx v1.0j			
<code>\@sverb</code> : Slight change in error message text. . . . .	291		
1994-05-11 ltboxes.dtx v1.0f			
<code>\@begin@tempboxa</code> : Use new <code>\color@setgroup</code> concept. . .	324		

ASAJ. . . . .	85	1994-05-12 ltfsstrc.dtx v2.3f	
1994-05-12 ltboxes.dtx v1.0g		<code>\selectfont</code> : Use	
<code>\@finalstrut</code> : macro added . . . .	334	<code>\DeclareRobustCommand</code> . . .	189
<code>\fbox</code> : New definition, merged		1994-05-12 ltoutenc.dtx 1.5a	
with <code>\framebox</code> . . . . .	327	General: Removed the	
<code>\framebox</code> : Merged <code>\fbox</code> and		<code>\SaveAtCatcode</code> and	
<code>\framebox</code> . . . . .	327	<code>\RestoreAtCatcode</code>	
<code>\normalcolor</code> : macro added for		commands. . . . .	117
colour support . . . . .	325	Rewrote for the new	
1994-05-12 ltdefns.dtx v1.0p		syntax. . . . .	117, 120
General: (ASAJ) Fixed a bug with		1994-05-12 ltoutput.dtx v1.0p	
<code>\relax</code> which was using		<code>\@writsetup</code> :	
<code>\@gobble</code> before defining it. . .	36	<code>\normalcoloradded</code> . . . . .	451
Fixed a bug with <code>\relax</code> which		General: <code>\normalcoloradded</code> in	
was using <code>\@gobble</code> before		various places (DPC). . . . .	424
defining it. . . . .	44	1994-05-13 ltboxes.dtx v1.0h	
1994-05-12 ltfsbas.dtx v2.1j		<code>\@arrayparboxrestore</code> : New	
General: New baselinestretch		accent system, use <code>\let</code> not	
concept . . . . .	163	<code>\def</code> . . . . .	330
Replaced hand-protected		1994-05-13 ltcounts.dtx v1.0f	
commands by		General: Removed <code>\@Ialph</code> . . . .	159
<code>\DeclareRobustCommand</code> defs	163	Removed <code>\@ialph</code> . . . . .	159
<code>\f@linespread</code> : New macro . . . .	171	1994-05-13 ltdefns.dtx v1.0q	
<code>\fontencoding</code> : Use		General: (ASAJ) Renamed	
<code>\DeclareRobustCommand</code> . . . .	169	<code>\DeclareProtectedCommand</code> to	
<code>\fontfamily</code> : Use		<code>\DeclareRobustCommand</code> .	
<code>\DeclareRobustCommand</code> . . . .	170	Removed	
<code>\fontseries</code> : Use		<code>\@if@short@command</code> . . . . .	36
<code>\DeclareRobustCommand</code> . . . .	170	(ASAJ) Replaces <code>\space</code> by ‘ ’	
<code>\fontshape</code> : Use		in <code>\csname</code> . . . . .	36
<code>\DeclareRobustCommand</code> . . . .	170	Renamed	
<code>\fontsize</code> : Redefined to use		<code>\DeclareProtectedCommand</code> to	
<code>\set@fontsize</code> . . . . .	171	<code>\DeclareRobustCommand</code> .	
<code>\linespread</code> : New macro . . . . .	171	Removed <code>\@if@short@command</code> .	
<code>\mathversion</code> : Use		Moved to after the definition of	
<code>\DeclareRobustCommand</code> . . . .	171	<code>\@gobble</code> . . . . .	44
1994-05-12 ltfsdcl.dtx v2.1g		1994-05-13 ltdefns.dtx v1.0r	
General: Allow <code>\relax</code> as		General: (ASAJ) Added logging	
undefined command . . . . .	211	message to	
Allow <code>\relax</code> ’ed cmds to be		<code>\DeclareProtectedCommand</code> . . .	36
declared . . . . .	211	Added logging message to	
1994-05-12 ltfsini.dtx v2.1i		<code>\DeclareProtectedCommand</code> . . .	44
General: Moved <code>\fontencoding</code> to		1994-05-13 ltdefns.dtx v1.0s	
fam.dtx . . . . .	237	General: (ASAJ) Added	
Moved <code>\fontfamily</code> to fam.dtx	237	<code>\@backslashchar</code> . . . . .	36
Moved <code>\fontseries</code> to fam.dtx	237	(ASAJ) Coded <code>\@ifdefinable</code>	
Moved <code>\fontshape</code> to fam.dtx	237	more efficiently. . . . .	36
Moved <code>\fontsize</code> to fam.dtx .	237	Coded more efficiently, thanks	
Moved <code>\mathversion</code> to		to FMI. . . . .	41
fam.dtx . . . . .	237	1994-05-13 ltfiles.dtx LaTeX2e	
Moved <code>\selectfont</code> to		<code>\listfiles</code> : Stop <code>\listfiles</code>	
tracefnt.dtx . . . . .	237	being run twice . . . . .	100



1994-05-13 ltfiles.dtx v1.0g		1994-05-14 ltssbas.dtx v2.1m	
\document: Added execution of		\enc@update: Macro added . . . .	170
\every@size . . . . .	91	1994-05-14 ltssbas.dtx v2.1n	
1994-05-13 ltfinal.dtx v0.1h		General: Set defaults for all	
General: Added package otlenc,		\fo... . . . .	171
and defined \@acci, \@accii		\DeclareErrorFont: Don't set	
and \@acciii. . . . .	555	\fo@encoding . . . . .	175
1994-05-13 ltfinal.dtx v1.0h		\DeclareFontEncoding: Log if	
General: Added output enc stuff .	567	encoding is redeclared . . . .	166
1994-05-13 ltfloat.dtx v1.0g		Only init enc change cmd when	
\@footnotetext: (DPC) Add new		new encoding . . . . .	166
style colour support:		1994-05-14 ltssini.dtx v2.1k	
\normalcolor . . . . .	413	General: Init error font just before	
(DPC) Use \@finalstrut . . . .	413	checking for fontdef.cfg . . . .	241
\@xfloat: (DPC) Use		\p@reset@font: Remove surplus	
\normalcolor . . . . .	401	braces . . . . .	240
1994-05-13 ltfntcmd.dtx v3.3g		1994-05-14 ltssstrc.dtx v2.3h	
General: Replaced \@protecteddef		\selectfont: Added	
by \DeclareRobustCommand .	266	\enc@update . . . . .	190
1994-05-13 ltssbas.dtx v2.1k		1994-05-14 ltoutenc.dtx 1.5d	
General: Remove File identification		General: Moved the driver to the	
'typeout' . . . . .	163	top. . . . .	105
1994-05-13 ltssbas.dtx v2.1l		1994-05-14 ltoutenc.dtx v1.5c	
\DeclareFontEncoding: Init		General: Added the fontenc	
encoding change command .	166	package . . . . .	142
\define@newfont: Use \@input@		Added the fontenc package. . .	102
for fd files . . . . .	174	Fixed a bug which caused an	
1994-05-13 ltssdcl.dtx v2.1h		infinite loop if \fo@encoding	
General: Removed file		was incorrectly set. . . .	102, 106
identification typeout . . . .	211	Moved fontsmpl to its own dtx	
1994-05-13 ltssini.dtx v2.1j		file. . . . .	102
General: Removed file		1994-05-14 ltoutenc.dtx v1.5d	
identification typeout . . . .	237	General: Rewrote	
1994-05-13 ltssstrc.dtx v2.3g		\DeclareTextCommand to define	
General: Removed typeouts as		its argument to use the current	
\ProvidesPackage writes to		encoding by default, rather	
log. . . . .	185	than the encoding provided to	
1994-05-13 ltoutenc.dtx v1.5b		\DeclareTextCommand. . .	102, 106
General: Added \{, \} and \\$. . .	102	Tidied up the documentation. .	102
Renamed		1994-05-14 ltoutenc.dtx v1.5e	
\DeclareProtectedCommand to		General: Replaced \ENC@cmd by	
\DeclareRobustCommand. . . .	102	\ENC-cmd. . . . .	102
Replaces \space by ' ' in		1994-05-15 ltssbas.dtx v2.1o	
\csname. . . . .	102	General: encoding cmds changed	
1994-05-13 ltpictur.dtx v0.1d		to enc-cmd . . . . .	163
General: Removed surplus braces		1994-05-16 fontdef.dtx v2.1g	
from \if.. constructions . .	357	General: Removed	
1994-05-13 lttab.dtx v1.0d		\DeclareFontEncoding for ot1	
\@contfield: Colour support . . .	341	and t1 and input .def files	
\@startfield: Colour support . .	340	instead . . . . .	245
\@stopfield: Colour support . . .	341	1994-05-16 ltalloc.dtx v1.1a	
\@: moved to ltoutenc . . . . .	339	General: (ASAJ) Split from	
1994-05-14 fontdef.dtx v2.1f		ltinit.dtx. . . . .	54
General: Removed .def files. . . .	245		

1994-05-16 ltcntrl.dtx v1.0a	1994-05-16 ltoutput.dtx v1.0q
General: (ASAJ) Split from ltinit.dtx. . . . . 56	<code>\@writesetup</code> : Changed setting of accents (FMi): with the new encoding setup they can use <code>\let</code> . It could also use the new internal commands? . . . . . 452
1994-05-16 ltdefns.dtx v1.1a	General: Changed setting of accents (FMi). . . . . 424
General: (ASAJ) Split from ltinit.dtx. . . . . 36	1994-05-16 ltpar.dtx v1.1a
1994-05-16 lterror.dtx v1.1a	General: (ASAJ) Split from ltinit.dtx. . . . . 69
General: (ASAJ) Completely new error interface. . . . . 60	1994-05-16 ltplain.dtx v1.0h
(ASAJ) Split from ltinit.dtx. . . 60	General: Comment out encoding specific commands . . . . . 29
1994-05-16 ltfinal.dtx v1.0i	Remove <code>\@acci</code> and friends again . . . . . 29
General: moved output enc stuff to lfont . . . . . 567	Remove unnecessary def for <code>\item</code> . . . . . 28
1994-05-16 ltffsbas.dtx v2.1p	<code>\loop</code> : Use Kabelschacht method 27
<code>\fontsize</code> : Pass <code>\baselinestretch</code> not <code>\f@linespread</code> . . . . . 171	<code>\m@th</code> : Remove unnecessary space 28
<code>\linespread</code> : Remove surplus braces . . . . . 171	1994-05-16 ltspc.dtx v1.1a
1994-05-16 ltffsini.dtx v2.1m	General: (ASAJ) Split from ltinit.dtx. . . . . 71
<code>\@acciii</code> : Define saved versions of accents . . . . . 242	1994-05-17 ltclass.dtx v1.0e
1994-05-16 ltlogos.dtx v1.1a	<code>\useoption</code> : Execute option after removing from list, not before 507
General: (ASAJ) Split from ltinit.dtx. . . . . 87	1994-05-17 ltdefns.dtx 1.1b
1994-05-16 ltmath.dtx v1.0k	General: (ASAJ) Added the <code>\@protect@...</code> commands. . . 45
<code>\ensuremath</code> : Use <code>\DeclareRobustCommand</code> and add extra braces in math mode . . . . . 303	1994-05-17 ltdefns.dtx v1.1b
1994-05-16 ltoutenc.dtx 1.5h	General: (ASAJ) Added definitions for protect. . . . . 36
General: <code>\pounds</code> was still using u rather than ui shape. . . . . 117	(ASAJ) Removed warnings and logging to lterror.dtx. . . . . 36
1994-05-16 ltoutenc.dtx v1.5f	Added the discussion of protected commands, defined the values that <code>\protect</code> should have. . . . . 44
General: enc files now have uc encoding name parts (FMi) . . 102	1994-05-17 ltdefns.dtx v1.1c
Revert code so that the encoding given is used in <code>\DeclareTextCommand</code> (FMi) 102	General: (ASAJ) Redid definitions for protect. . . . . 36
1994-05-16 ltoutenc.dtx v1.5g	1994-05-17 lterror.dtx v1.1b
General: Made fontenc.sty use the new mixed-case encoding files. 102	General: (ASAJ) Moved error stuff from ltdefns.dtx. . . . . 60
Removed the lowercasing of the filename. . . . . 142	1994-05-17 ltffsini.dtx v2.1n
1994-05-16 ltoutenc.dtx v1.5h	<code>\copyright</code> : Really add extra braces . . . . . 240
General: Added <code>\NG</code> , <code>\ng</code> , <code>\TH</code> , <code>\th</code> , <code>\DH</code> , <code>\dh</code> , <code>\DJ</code> and <code>\dj</code> . . . . 102	<code>\nfss@text</code> : Added braces to allow use in subscripts . . . . . 240
Added <code>\r</code> (ring accent) and <code>\k</code> (ogonek) accents. . . . . 102	1994-05-17 ltmath.dtx v1.0i
Fixed a bug with <code>\pounds</code> . . . . 102	General: Replaced <code>\let</code> by <code>\gdef</code> , for indirect definition. . . . . 299
Removed <code>\P</code> from the OT1 definitions file. . . . . 102	
1994-05-16 ltoutenc.dtx v1.5i	
General: Fixed a bug with <code>\d</code> . . . 102	

1994-05-17 ltoutenc.dtx v1.5j		1994-05-19 ltplain.dtx v0.1k ltfinal	
General: Added braces to <code>\pounds</code>		<code>\showoutput</code> : used <code>\maxdimen</code> not	
so it works as a subscript. . .	102	99999 . . . . .	30
1994-05-18 ltdefns.dtx 1.1c		<code>\showoverfull</code> : used <code>\one</code> not 1 .	30
General: (ASAJ) Renamed the		1994-05-19 ltxref.dtx v1.1a	
commands, and removed one		General: Extract file ltxref from	
which is no longer needed. . . .	45	ltcntlen. . . . .	275
1994-05-18 ltdefns.dtx v1.1c		1994-05-20 ltdefns.dtx v1.1e	
General: Redid the discussion and		General: Changed command name	
definitions, in line with the		from <code>\@checkcommand</code> to	
proposed new setting of		<code>\CheckCommand</code> . . . . .	36
<code>\protect</code> in the output		<code>\CheckCommand</code> : Changed name	
routine. . . . .	44	from <code>\@checkcommand</code> to	
1994-05-18 ltfinal.dtx v0.1j		<code>\CheckCommand</code> . . . . .	43
General: Corrected the lcode for		1994-05-20 lterror.dtx v1.1c	
d-bar. . . . .	555	General: (ASAJ) Added	
1994-05-18 ltlogos.dtx v1.1b		<code>\@latex@info@no@line</code> . . . .	60
General: (ASAJ) Added the $\TeX$		(ASAJ) Added missing full	
logo. . . . .	87	stops. . . . .	60
(ASAJ) Made the $\LaTeX 2_{\epsilon}$ logo		(ASAJ) Fixed a bug with	
use the text font ‘2’ rather		<code>\@inmatherr</code> . . . . .	60
than the math font ‘2’. . . . .	87	1994-05-20 ltfinal.dtx v0.1l	
1994-05-18 ltoutenc.dtx v1.5k		General: Use new font warning	
General: Made dotted-i produce		commands . . . . .	561
‘i’. . . . .	102	1994-05-20 ltfloat.dtx v1.0h	
Removed braces from <code>\pounds</code>		<code>\@endfloatbox</code> : Restore outer	
and <code>\dollar</code> . . . . .	102	value of <code>@nobreak</code> switch. . .	405
Replaced <code>\defaultencoding</code>		<code>\outer@nobreak</code> : Macro added:	
with <code>\encodingdefault</code> . . . .	102	default is to do nothing. . . .	405
1994-05-19 ltbibl.dtx v1.1a		1994-05-20 ltfntcmd.dtx v3.3h	
General: Initial version of		General: Use new error commands	266
ltbibl.dtx, split from		1994-05-20 ltfsbas.dtx v2.1q	
ltxbib.dtx . . . . .	417	General: Use new error commands	163
1994-05-19 ltcounts.dtx v1.1a		1994-05-20 ltfsstrc.dtx v2.3i	
General: Extracted file from		General: Use new error command	
ltcntlen. . . . .	155	names . . . . .	185
1994-05-19 ltdefns.dtx v1.1d		1994-05-20 ltmiscen.dtx v1.0l	
General: (RmS) Added definitions		<code>\@writefile</code> : Added correct	
for <code>\@namedef</code> and <code>\@nameuse</code>		setting of <code>\protect</code> . . . . .	283
again. . . . .	36	1994-05-20 ltmiscen.dtx v1.0m	
1994-05-19 ltfinal.dtx v0.1k		General: Use new warning	
General: Removed <code>\makeat</code> . . .	555	commands . . . . .	279
1994-05-19 ltxglo.dtx v1.1a		1994-05-20 ltoutput.dtx v1.0s	
General: Initial version of		<code>\@writsetup</code> : Added setting of	
ltxglo.dtx, split from		<code>\protect</code> during <code>\shipout</code> . .	451
ltxbib.dtx . . . . .	415	General: Added setting of	
1994-05-19 ltlength.dtx v1.1a		<code>\protect</code> during <code>\shipout</code> . .	424
General: Extract file ltlength from		1994-05-20 ltpage.dtx v1.0d	
ltcntlen. . . . .	162	<code>\markright</code> : Changed setting for	
1994-05-19 ltpageno.dtx v1.1a		<code>\protect</code> . . . . .	422
General: Extract file ltpageno from		1994-05-20 ltsect.dtx v1.0c	
ltcntlen. . . . .	274	General: Correct setting of	
		<code>\protect</code> . . . . .	393

<code>\addcontentsline</code> : Correct setting of <code>\protect</code> . . . . .	393	(DPC) New version using long command name. . . . .	60
1994-05-21 <code>ltbibl.dtx</code> v1.1b		1994-05-22 <code>ltfloat.dtx</code> v1.0i	
General: Use new warning commands . . . . .	417	General: Use new warning commands . . . . .	396
1994-05-21 <code>lterror.dtx</code> v1.1d		1994-05-22 <code>ltoutput.dtx</code> v1.0t	
General: (ASAJ) Made the error commands robust. . . . .	60	General: Changed warnings and infos to new commands. . . .	424
1994-05-21 <code>ltfiles.dtx</code> v1.0h		1994-05-22 <code>ltpictur.dtx</code> v0.1e	
General: Use new error commands	88	General: Use new warning cmds .	357
1994-05-21 <code>ltlists.dtx</code> v1.0f		1994-05-23 <code>ltclass.dtx</code> v1.0h	
General: Use new error commands	307	<code>\NeedsTeXFormat</code> : Don't stop completely when format is wrong . . . . .	509
1994-05-21 <code>ltmiscen.dtx</code> v1.0n		<code>\usepackage</code> : Remove argument if possible . . . . .	508
General: Use new error commands	279	1994-05-23 <code>ltdirchk.dtx</code> v1.0f	
1994-05-21 <code>ltsct.dtx</code> v1.0d		General: Document <code>\@TeXversion</code>	1
General: Use new error commands	384	1994-05-23 <code>ltsfstrc.dtx</code> v2.3j	
1994-05-21 <code>ltsab.dtx</code> v1.0f		General: Removed def of <code>\f@warn@break</code> . . . . .	202
General: Use new error commands	335	1994-05-23 <code>ltoutput.dtx</code> v1.0u	
1994-05-21 <code>ltxref.dtx</code> v1.1b		<code>\@activechar@info</code> : Added <code>\MessageBreak</code> . . . . .	450
General: Use new warning commands . . . . .	275	<code>\@writsetup</code> : Changed resetting of <code>\protect</code> after shipout to use <code>\aftergroup</code> . . . . .	451
<code>\newlabel</code> : Use new warning commands . . . . .	277	General: Added <code>\MessageBreak</code> . .	424
1994-05-22 <code>ltclass.dtx</code> v1.0f		Changed resetting of <code>\protect</code> after shipout. . . . .	424
General: Use new warning and error commands . . . . .	496	1994-05-24 <code>lterror.dtx</code> v1.2e	
1994-05-22 <code>ltdefns.dtx</code> v1.1f		<code>\@latex@info@no@oline</code> : Macro added . . . . .	63
General: Use new warning and error cmds . . . . .	36	1994-05-24 <code>lterror.dtx</code> v1.2f	
1994-05-22 <code>lterror.dtx</code> v1.1e		General: (DPC) wrap long lines .	60
General: (ASAJ) Replaced <code>bgroup</code> by <code>begingroup</code> in error messages, to stop extra <code>mathords</code> creeping into <code>math</code> mode. . . . .	60	1994-05-24 <code>lftntcmd.dtx</code> v3.3i	
1994-05-22 <code>lterror.dtx</code> v1.2a		General: Tidying and typos fixed	266
General: (ASAJ) Made <code>\GenericError</code> , <code>\GenericWarning</code> and <code>\GenericInfo</code> robust. . . . .	60	1994-05-24 <code>ltmiscen.dtx</code> v1.0q	
(ASAJ) Replaced <code>\@generic@message</code> and <code>\@generic@error</code> by <code>\GenericError</code> , <code>\GenericWarning</code> and <code>\GenericInfo</code> . . . . .	60	<code>\@currenvline</code> : Use <code>\@empty</code> as outer default . . . . .	286
(ASAJ) Replaced <code>\</code> and tilde by <code>\MessageBreak</code> and <code>\space</code> . .	60	1994-05-25 <code>ltdirchk.dtx</code> v1.0g	
(ASAJ) Replaces <code>\string</code> by <code>\protect</code> in some messages. .	60	<code>\filename@parse</code> : Mac parser had " typo for : . . . . .	12
1994-05-22 <code>lterror.dtx</code> v1.2d		1994-05-25 <code>lftntcmd.dtx</code> v3.3j	
<code>\GenericError</code> : (DPC) Alternative version added for old TeXs . .	60	General: Insertion of <code>\aftergroups</code> to implement <code>\nocorr</code> moved to the end of the group . . . .	266
		<code>\check@icr</code> : Macros added . . . .	269
		<code>\check@nocorr@</code> : Insertion of <code>\aftergroups</code> moved and defaults set up for efficiency .	269
		<code>\DeclareTextFontCommand</code> : <code>\expandafter</code> inserted . . . .	268

Insertion of <code>\aftergroups</code> moved . . . . .	268	1994-06-09 <code>ltfinal.dtx</code> v1.0n General: For $\TeX$ 2, do not set codes for higher half of character table. . . . .	559, 565
1994-05-25 <code>ltoutput.dtx</code> v1.0v General: Extra documentation. . .	424	1994-06-09 <code>ltfntcmd.dtx</code> v3.3k General: Tidying and typos fixed in documentation . . . . .	266
1994-05-25 <code>ltsect.dtx</code> v1.0e <code>\@dottedtocline</code> : Put braces around argument 4 (the actual toc entry) to avoid font (and possibly other) changes leaking out to the leaders. . . . .	394	1994-06-18 <code>ltfntcmd.dtx</code> v3.3l General: Added check for empty text . . . . .	266
1994-05-25 <code>ltthm.dtx</code> v1.0c General: Modify documentation .	380	<code>\check@nocorr@</code> : Added check for empty text . . . . .	269
1994-05-25 <code>ltvers.dtx</code> v1.0d General: Remove PRELIMINARY TEST RELEASE from startup banner (spring is here) . . . .	33	1994-06-22 <code>ltfntcmd.dtx</code> v3.3m General: Removed space from <code>\nfss@text</code> . . . . .	266
1994-05-25 <code>ltxref.dtx</code> v1.1c General: Modify documentation .	275	Renamed <code>\check@nocorr</code> . . . .	266
1994-05-26 <code>ltfiles.dtx</code> LaTeX2e <code>\@missingfileerror</code> : Modify message format . . . . .	99	<code>\check@nocorr@</code> : Renamed <code>\check@nocorr</code> to <code>\text@command</code> to improve <code>\long</code> error message . . . . .	269
1994-05-26 <code>ltlogos.dtx</code> v1.1c General: Remove <code>\SLiTeX</code> logo . .	87	<code>\DeclareTextFontCommand</code> : Removed space from <code>\nfss@text</code> . . . . .	268
1994-05-26 <code>ltmiscen.dtx</code> v1.0r General: <code>\literal</code> removed . . . .	293	1994-06-22 <code>ltmath.dtx</code> v1.2t classes <code>\mathindent</code> : Set <code>\mathindent</code> at the end of the class instead of at begin document . . . . .	304
1994-05-26 <code>ltplain.dtx</code> v1.1m <code>\iterate</code> : (CAR) added <code>\long</code> . .	27	1994-07-20 <code>ltlogos.dtx</code> v1.1e <code>\LaTeX</code> : Save a few tokens . . . .	87
<code>\underbar</code> : (CAR/FMi) changed to use box <code>\tw@</code> . . . . .	28	<code>\LaTeXe</code> : Save a few tokens . . . .	87
1994-05-26 <code>ltplain.dtx</code> v1.1p <code>\underbar</code> : (DPC) changed to use <code>\sbox</code> . . . . .	28	1994-07-20 <code>ltpage.dtx</code> v1.0h <code>\sloppy</code> : Save a few tokens . . . .	423
1994-05-29 <code>ltfssdcl.dtx</code> v2.1j General: Use new error commands	211	1994-09-16 <code>ltfssbas.dtx</code> v2.1s <code>\nfss@catcodes</code> : Reset [ and ] as well, just in case . . . . .	175
1994-05-31 <code>ltfinal.dtx</code> v1.0n General: Renamed <code>lthyphen.*</code> to <code>lthyphen.*</code> . . . . .	555	1994-10-07 <code>ltoutenc.dtx</code> v1.5l General: Moved the ogonek accent. . . . .	102
1994-06-01 <code>ltboxes.dtx</code> v1.0i <code>\@frameb@x</code> : Macro added. . . . .	328	1994-10-11 <code>ltdirchk.dtx</code> v1.0h <code>\@TeXversion</code> : Check for $\TeX$ 3.14	13
<code>\@ifframebox</code> : New version, so <code>\width</code> is correct in <code>\framebox</code> . . . . .	328	General: Modify all of <code>ltxcheck</code> again . . . . .	14
<code>\fbox</code> : New version, using <code>\@frameb@x</code> . . . . .	327	1994-10-12 <code>ltsect.dtx</code> v1.0f General: Doc. typos . . . . .	384
<code>\framebox</code> : New version, so <code>\width</code> is correct in <code>\framebox</code> . . . .	327	1994-10-14 <code>fontdef.dtx</code> v2.2a General: New coding . . . . .	243
1994-06-01 <code>ltlogos.dtx</code> v1.1d <code>\LaTeX</code> : Add <code>\m@th</code> to force math size calculations . . . . .	87	1994-10-14 <code>ltfssini.dtx</code> v2.2a General: New coding for <code>cfg</code> files .	237
1994-06-01 <code>ltoutput.dtx</code> v1.0w General: Tidied up typesetting. .	424	1994-10-14 <code>ltmiscen.dtx</code> v1.0s General: Move math to other file	279
1994-06-08 <code>ltfinal.dtx</code> v1.0m General: Add patch file system . .	567	1994-10-14 <code>ltplain.dtx</code> v1.1a General: Moved code to other files.	15

1994-10-15 ltfsbas.dtx v2.1t	1994-10-24 ltboxes.dtx v1.0k
<code>\extract@alph@from@version:</code>	<code>\fbox:</code> Inner braces added (to fix
Warn if math alpha is used	latex/1061) . . . . . 327
outside math . . . . . 181	1994-10-25 fontdef.dtx v2.2c
1994-10-18 ltboxes.dtx v1.0j	General: Added OMSenc.def . . . 245
<code>\@frameb@x:</code> <code>\leavevmode</code> added . 328	1994-10-25 ltboxes.dtx v1.0l
<code>\@ifframebox:</code> <code>\leavevmode</code> moved	<code>\@isavepicbox:</code> missing percent
to <code>\@frameb@x</code> . . . . . 328	(moved from ltpatch) . . . . . 326
<code>\@parboxto:</code> Macro added to	1994-10-25 ltdefns.dtx v1.2b
remove misuse of <code>\@empty</code> . . 329	General: Documentation
General: stuff from ltpatch done . 323	improvements . . . . . 36
<code>\fbox:</code> <code>\long</code> added . . . . . 327	1994-10-25 ltoutenc.dtx 1.6a
<code>\mbox:</code> <code>\long</code> added . . . . . 324	General: Added <code>\textdollar</code> ,
<code>\sbox:</code> <code>\long</code> added . . . . . 326	<code>\textlbrace</code> , <code>\textrbrace</code> ,
1994-10-18 ltclass.dtx v1.0j	<code>\textsterling</code> ,
General: Move <code>\listfiles</code> to	<code>\textunderline</code> . . . . . 120
ltfiles.dtx . . . . . 496	Removed <code>\textlbrace</code> ,
1994-10-18 ltdefns.dtx v1.2a	<code>\textrbrace</code> , <code>\textunderline</code>
<code>\@star@or@long:</code> macro added . . 38	to give them their proper
General: Add extra test for	names. . . . . 120
<code>\endgraf</code> . . . . . 36	1994-10-25 ltoutenc.dtx v1.6a
Add star-forms for all commands 36	General: Added
<code>\renew@environment:</code> reset end	<code>\ProvideTextCommand</code> ,
command . . . . . 42	<code>\UseTextSymbol</code> ,
1994-10-18 ltfiles.dtx v1.0i	<code>\UseTextAccent</code> ,
<code>\listfiles:</code> code moved here from	<code>\DeclareTextSymbolDefault</code> ,
ltclass . . . . . 100	<code>\DeclareTextAccentDefault</code> ,
1994-10-18 ltoutenc.dtx v1.5l	<code>\DeclareTextCommandDefault</code> ,
General: Added new definitions of	and <code>\ProvideTextCommandDe-</code>
<code>\patterns</code> and <code>\hyphenation</code> . 113	fault. . . . . 102
1994-10-18 ltoutenc.dtx v1.5m	Added the <code>\Provide</code> commands,
General: Added new definitions of	and the default definitions. . . 106
<code>\patterns</code> and <code>\hyphenation</code> . 102	Added the defaults. . . . . 114
1994-10-18 ltsect.dtx v1.0g	Added the files OTlenc.def,
<code>\@dottedtocline:</code> Added	Tlenc.def and OMSenc.def. . . 114
<code>\normalcolor</code> for page	Added the OMS encoding. . . . 125
number . . . . . 394	1994-10-27 ltoutenc.dtx 1.6b
General: Added <code>\normalcolor</code> . . 384	General: Added <code>\textasciicircum</code>
1994-10-19 ltfsbas.dtx v2.1t	<code>\textasciitilde</code>
<code>\DeclareFontEncoding:</code> Add	<code>\textbackslash</code> <code>\textbar</code>
missing <code>\relax</code> . . . . . 165	<code>\textbraceleft</code>
1994-10-23 ltfsstrc.dtx v23.k	<code>\textbraceright</code>
<code>\every@math@size:</code> Renamed to	<code>\textcompwordmark</code>
<code>\every@math@size</code> . . . . . 192	<code>\textemdash</code> <code>\textendash</code>
1994-10-23 ltmath.dtx v1.0l	<code>\textexclamdown</code>
<code>\@eqnnum:</code> Added <code>\normalcolor</code>	<code>\textgreater</code>
since <code>\eqno</code> introduces a	<code>\textthyphenchar</code> <code>\textthyphen</code>
subgroup of the displayed math	<code>\textless</code> <code>\textquestiondown</code>
group . . . . . 301	<code>\textquotedblleft</code>
<code>\ensuremath:</code> Remove extra	<code>\textquotedblright</code>
braces: but see p 168 of	<code>\textquotedbl</code>
Leslie's book . . . . . 303	<code>\textquoteleft</code>
	<code>\textquoteright</code>



<code>\textunderscore</code>	1994-10-30 ltdefs.dtx v1.2f
<code>\textvisiblespace</code> . . . . . 120	General: (DPC)\newwrite's moved to ltfiles . . . . . 36
Added: <code>\textemdash</code>	1994-10-30 ltmath.dtx v1.0n
<code>\textendash</code> <code>\textexclamdown</code>	General: ASAJ: Moved the new commands to ltoutenc. . . . . 299
<code>\textthyphenchar</code> <code>\textthyphen</code>	1994-10-30 ltoutenc.dtx v1.6d
<code>\textquestiondown</code>	General: Added <code>\DeclareTextCom-</code>
<code>\textquotedblleft</code>	<code>positeCommand</code> . . . . . 102
<code>\textquotedblright</code>	Added <code>\textcircled</code> . 102, 115, 125
<code>\textquoteright</code> . . . . . 117	Added <code>\t</code> . . . . . 115
1994-10-27 ltoutenc.dtx v1.5d	Added math commands. . . . . 102
General: Rewrote	Added OML encoding. . . 102, 115
<code>\DeclareTextSymbol</code> to define	Added the OML encoding. . . 126
its argument to use the current	Made <code>\textless</code> and
encoding by default, to fit with	<code>\textgreater</code> come from
<code>\DeclareTextCommand</code> . . . . . 106	OML. . . . . 115
1994-10-27 ltoutenc.dtx v1.6b	Moved math commands here
General: Added <code>\textbackslash</code> . 125	from ltmath. . . . . 117
Added more defaults for OT1. 114	Removed <code>\textregistered</code> . . . 115
Removed the enc.def files . . . . 102	Rewrote <code>\copyright</code> to use
Removed the files OT1enc.def,	<code>\textcircled</code> . . . . . 115
OT1enc.def and OMSenc.def. . . 114	1994-10-31 fontdef.dtx v2.2d
Renamed <code>\textlbrace</code> to	General: Added OMLenc.def ... . 245
<code>\textbraceleft</code> and	1994-10-31 fontdef.dtx v2.2e
<code>\textrbrace</code> to	General: ... and moved further
<code>\textbraceright</code> . . . . . 125	down . . . . . 245
1994-10-29 ltmath.dtx 1.0m	1994-10-31 lfloat.dtx v1.1a
General: ASAJ: Added	<code>\@dblfloat</code> : Major changes since
<code>\DeclareMathOperator</code> . . . . . 294	two-column and one-column
ASAJ: Tidied up	cases merged . . . . . 400
documentation. . . . . 300	<code>\@dblfloatset</code> : Macro added . . . . . 399
1994-10-29 ltmath.dtx v1.0m	Major changes to parameter
General: ASAJ: Added	parsing, setting of local
<code>\mathellipsis</code> , <code>\mathdollar</code>	variables, etc; two-column and
and <code>\mathsterling</code> . . . . . 299	one-column cases merged;
ASAJ: Removed <code>\dag</code> , <code>\ddag</code> . . 299	space hacks moved . . . . . 399
ASAJ: Renamed <code>\S</code> and <code>\P</code> to	<code>\@endfloatbox</code> : (DPC/CAR)
<code>\mathsection</code> and	Extra box added to remove
<code>\mathparagraph</code> and made	colour resetting from vmode . 405
them <code>\mathchardefs</code> . . . . . 299	<code>\@floatboxreset</code> : Macro added . 403
1994-10-29 ltoutenc.dtx v1.6c	<code>\@footnotetext</code> : (DPC/CAR)
General: Added commands like	Move colour setting to output
<code>\dots</code> for use in text and	routine . . . . . 413
math. . . . . 114	<code>\@savemarbox</code> : (DPC/CAR) Extra
Renamed <code>\P</code> , <code>\S</code> , <code>\dag</code> and	box added for colour . . . . . 408
<code>\ddag</code> to <code>\textparagraph</code> ,	<code>\@setfps</code> : Macro added . . . . . 400
<code>\textsection</code> , <code>\textdagger</code>	<code>\@xdblfloat</code> : Macros removed:
and <code>\textdaggerdbl</code> . . . . . 102	<code>\@dblft</code> , <code>\@xdblfloat</code> . . . . . 405
1994-10-30 ltdefs.dtx v1.2c	<code>\@xfloat</code> : (DPC/CAR) Extra box
<code>\@onelevel@sanitize</code> : Macro	added to remove colour
added . . . . . 51	resetting from vmode . . . . . 401
General:	Major changes, removing setting
(CAR)\@onelevel@sanitize	of local variables, space hacks
added . . . . . 36	

etc; two-column and one-column cases merged . . .	400	1994-11-04 ltfloat.dtx v1.1b \@footnotetext: (ASAJ) Added \protected@edef. . . . .	413
Reset hook added . . . . .	401	\footnotemark: Added \protected@xdef to \footnotemark. . . . .	414
\@xympar: (DPC/CAR) Extra box added since needed for floats	409	1994-11-04 ltidxglo.dtx v1.1b \@wrglossary: Added \protected@write to \@wrglossary. . . . .	416
\fps@dbl: Macro added . . . . .	400	\@wrindex: Added \protected@write to \@wrindex. . . . .	416
1994-10-31 ltoutput.dtx v1.1a \@makecol: (DPC/CAR) Colour resetting moved to here . . . .	447	General: Removed \if@filesw from \makeindex. . . . .	415
\@topnewpage: (DPC/CAR) Extra box added to remove colour resetting from vmode . . . . .	439	\makeglossary: Removed \if@filesw from \makeglossary. . . . .	416
(DPC/CAR) Use \color@begingroup for colour	439	1994-11-04 ltmiscen.dtx v1.0t \@writefile: Removed setting of \protect. ASAJ. . . . .	283
(DPC/CAR) Use \normalcolor . . . . .	439	1994-11-04 ltoutenc.dtx v1.6f General: Added \_. . . . .	116
1994-11-02 ltoutenc.dtx v1.6d General: Wrapped lines longer than 70 characters. . . . .	102	Added \mathunderscore. . . . .	117
1994-11-03 ltclass.dtx v1.0k General: Move \@missingfileerror to ltfiles	500	1994-11-04 ltpage.dtx v1.0e \markright: Added \@unexpandable@protect. ASAJ. . . . .	422
1994-11-03 ltdirchk.dtx v1.0i General: Generate an error if latex.ltx not used with clean initex . . . . .	1	1994-11-04 ltsect.dtx 1.0h \@sect: (ASAJ) Added \protected@edef. . . . .	388
1994-11-03 ltfiles.dtx v1.0j \@missingfileerror: Move here from ltclass . . . . .	99	General: (ASAJ) Added \protected@xdef to \thanks. . . . .	384
1994-11-04 ltboxes.dtx v1.0m \@mpfootnotetext: Added \protected@edef. ASAJ. . . .	332	1994-11-04 ltsect.dtx v1.0h General: Added \protected@write to \addtocontents. ASAJ. . . .	393
1994-11-04 ltdefs.dtx v1.2e General: Added \set@display@protect to \typeout. ASAJ. . . . .	36	\addcontentsline: Added \protected@write to \addcontentsline. ASAJ. . . .	393
Added commands for setting and restoring \protect. ASAJ.	46	1994-11-04 lttab.dtx v1.0h \@mkpream: (ASAJ) Added \@unexpandable@protect to \@mkpream. . . . .	353
Rewrote protected short commands using \x@protect. ASAJ. . . . .	45	\multicolumn: (ASAJ) added \set@typeset@protect. . . .	349
1994-11-04 lterror.dtx v1.2g General: Added \set@display@protect to \Generic* commands. ASAJ.	60	1994-11-04 ltxref.dtx v1.1d \label: (ASAJ)Added \protected@edef . . . . .	277
1994-11-04 ltfiles.dtx v1.0k \nofiles: Added setting of \protected@write, \makeindex and \makeglossary to \nofiles. ASAJ. . . . .	93	\protected@write . . . . .	277
\protected@write: Macro added ASAJ. . . . .	94	1994-11-05 ltboxes.dtx v1.0n \@mpfootnotetext: Colour resetting for footnotes moved	



to endminipage: as for main page. . . . .	332	1994-11-06 ltssini.dtx v2.2b	
<code>\color@endbox</code> : macro added for colour support . . . . .	325	<code>\@setsize</code> : Use	
<code>\color@hbox</code> : macro added for colour support . . . . .	325	<code>\@typeset@protect</code> . . . . .	239
<code>\endminipage</code> : Colour resetting for footnotes moved to here: as for main page. . . . .	331	1994-11-06 ltssstrc.dtx v2.3k	
1994-11-05 ltboxes.dtx v1.0o		<code>\glb@currsiz</code> : New implementation . . . . .	191
<code>\@mpfootnotetext</code> : Colour groups restored here. . . . .	332	<code>\try@simples</code> : New implementation . . . . .	202
1994-11-05 ltfloat.dtx v1.1c		<code>\try@size@substitution</code> : New implementation . . . . .	202
<code>\@dblflset</code> : Add compatibility with old version of <code>\@xfloat</code> . . . . .	399	<code>\tryis@simple</code> : New implementation . . . . .	202
<code>\@endfloatbox</code> : Use new <code>\color@hbox</code> concept. . . . .	405	1994-11-07 fontdef.dtx v2.2f	
<code>\@footnotetext</code> : Removed <code>\normalcolor</code> (again) . . . . .	413	General: (DPC) Add	
<code>\@savemarbox</code> : Use new <code>\color@hbox</code> concept. . . . .	408	<code>\DeclareMathSizes</code> declarations . . . . .	249
<code>\@setfps</code> : Add compatibility with old version of <code>\@xfloat</code> . . . . .	400	(DPC) Updated to use	
<code>\@xfloat</code> : Add compatibility with old version of <code>\@xfloat</code> : but the arguments, provided at exorbitant cost, are now completely ignored . . . . .	400	<code>\ProvidesFile</code> . . . . .	245
Use new <code>\color@hbox</code> concept. . . . .	401	1994-11-07 ltfiles.dtx v1.0l	
<code>\@xympar</code> : Use new <code>\color@hbox</code> concept. . . . .	409	<code>\@unused</code> : move here from ltdefns, remove duplicate <code>\@mainaux</code> . . . . .	90
1994-11-05 ltoutenc.dtx v1.6g		1994-11-07 ltfiles.dtx v1.0m	
General: Added setting of <code>\@typeset@protect</code> to <code>\patterns</code> and <code>\hyphenation</code> . . . . .	113	<code>\document</code> : Renamed <code>\every@size</code> to <code>\every@math@size</code> . . . . .	91
1994-11-05 ltoutput.dtx v1.1b		1994-11-07 preload.dtx v2.1e	
<code>\@topnewpage</code> : Use new <code>\color@hbox</code> concept. . . . .	439	General: (DPC) Updated to use	
<code>\@writsetup</code> : Change protect settings for new-style, protect-free aux-files. . . . .	451	<code>\ProvidesFile</code> . . . . .	262
Use new <code>\color@hbox</code> concept. . . . .	451	1994-11-09 ltboxes.dtx v1.0p	
1994-11-05 ltoutput.dtx v1.1c		<code>\@finalstrut</code> : Revert	
<code>\@beginDvi</code> : Added macro . . . . .	455	<code>\finalstrut</code> to 2.09 equivalent (from ltpatch) . . . . .	334
<code>\@beginDvibox</code> : Added macro . . . . .	436	General: more colour changes. . . . .	323
<code>\@writsetup</code> : Add new <code>\AtBeginDvi</code> concept . . . . .	451	1994-11-09 ltssbas.dtx v2.1v	
<code>\AtBeginDvi</code> : Added macro . . . . .	436	<code>\@vpt</code> : (DPC) macros added, from <code>setsize.dtx</code> . . . . .	183
1994-11-06 ltssbas.dtx v2.1u		(DPC) reduce save stack usage latex/1742 . . . . .	183
<code>\cf@encoding</code> : New macro . . . . .	171	1994-11-10 ltbibl.dtx v1.1c	
<code>\DeclareFixedFont</code> : Renamed <code>\every@size</code> to <code>\every@math@size</code> . . . . .	164	General: Fix <code>\nocite{*}</code> . . . . .	417
		<code>\nocite</code> : Fix <code>\nocite{*}</code> . . . . .	419
		1994-11-10 ltmath.dtx v1.2v classes	
		<code>eqnarray</code> : Added value of <code>\parskip</code> to <code>\abovedisplayskip</code> to compensate for negative <code>\topsep</code> . . . . .	305
		1994-11-10 ltoutput.dtx v1.1e	
		<code>\@writsetup</code> : Modify <code>\protect</code> setting . . . . .	451
		1994-11-10 ltplain.dtx v1.1b	
		General: (CAR) added patch to <code>\loop</code> . . . . .	15
		<code>\iterate</code> : (CAR) added extra <code>\relax</code> . . . . .	27

1994-11-11 ltspace.dtx v1.2a		1994-11-17 ltdirchk.dtx v1.0j	
\\: (DPC) Make robust . . . . .	75	General: \@tempa to \reserved@a .	1
1994-11-12 ltfntcmd.dtx v3.3o		1994-11-17 lterror.dtx v1.2h	
\normalsize: Added		General: \@tempa to \reserved@a	60
\MessageBreak . . . . .	273	1994-11-17 ltfiles.dtx v1.0n	
1994-11-12 ltlists.dtx v1.2b ltspace		General: \@tempa to \reserved@a	88
\endtrivlist: Changed order of		1994-11-17 ltfinal.dtx v1.0o	
tests to make \@noitemerror		General: \@tempa to \reserved@a	555
correct: end of an era. . . . .	316	1994-11-17 ltfloat.dtx v1.1e	
1994-11-12 ltmiscen.dtx v1.0u		General: \@tempa to \reserved@a	396
center: Changed end macro to		1994-11-17 ltfntcmd.dtx v3.3p	
\def: safer and consistent . .	288	General: \@tempa to \reserved@a	266
flushleft: Changed end macro to		1994-11-17 ltfsbas.dtx v2.1w	
\def: safer and consistent . .	288	General: \@tempa to \reserved@a	163
flushright: Changed end macro		1994-11-17 ltfsdcl.dtx v2.1m	
to \def: safer and consistent	288	General: \@tempa to \reserved@a	211
1994-11-12 ltplain.dtx v1.1c		1994-11-17 ltfsstrc.dtx v2.3l	
General: Comment out more		General: \@tempa to \reserved@a	185
encoding specific commands .	29	1994-11-17 ltmath.dtx v1.0o	
1994-11-12 ltspace.dtx v1.2b		General: \@tempa to \reserved@a	294
\addpenalty: Corrected error		1994-11-17 ltmiscen.dtx v1.0v	
message . . . . .	81	General: \@tempa to \reserved@a	279
\addvspace: Corrected error		1994-11-17 ltoutenc.dtx v1.6h	
message . . . . .	81	General: (DPC) \@tempa to	
1994-11-13 ltspace.dtx v1.2c		\reserved@a . . . . .	102
\addpenalty: Recorrected error		1994-11-17 ltoutput.dtx v1.1h	
message . . . . .	81	General: \@tempa to \reserved@a.	424
\addvspace: Recorrected error		1994-11-17 ltpictur.dtx v1.0f	
message . . . . .	81	General: \@tempa to \reserved@a	357
1994-11-14 ltoutput.dtx v1.1f		1994-11-17 ltsect.dtx v1.0i	
\@beginvdi: Use normal box		General: \@tempa to \reserved@a	384
register: why a box? . . . . .	455	1994-11-17 lttab.dtx v1.0j	
\@beginvibox: Use normal box		General: \@tempa to \reserved@a	335
register: why a box? . . . . .	436	1994-11-18 ltboxes.dtx v1.0r	
\@writsetup: Modify new		\color@vbox: macro added for	
\AtBeginDvi concept . . . . .	451	colour support . . . . .	325
General: Removed old definition of		1994-11-18 ltfinal.dtx v1.0n	
\@testfp. . . . .	424	General: re-allow slots 127–255 . .	565
1994-11-14 ltspace.dtx v1.2d		1994-11-18 ltfsbas.dtx v2.1x	
\\: (DPC) Macro modified . . . . .	75	General: (DPC) use \reserved@f	
1994-11-14 lttab.dtx v1.0i		not \next . . . . .	163
\tabularnewline: (DPC) Macro		1994-11-18 ltfsdcl.dtx v2.1m	
added . . . . .	348	\DeclareMathDelimiter: (DPC)	
1994-11-16 fontdef.dtx v2.2h		\expandafter instead of	
General: (DPC) Removed \{ and		\next . . . . .	228
\} . . . . .	245	1994-11-18 ltfsstrc.dtx v2.3m	
1994-11-17 ltboxes.dtx v1.0q		General: \next to \reserved@f .	185
General: \@tempa to \reserved@a	323	1994-11-18 ltmath.dtx v1.0p	
1994-11-17 ltclass.dtx v1.0l		\phantom: (DPC) colour support	296
General: \@tempa to \reserved@a	496	(DPC) use \expandafter	
1994-11-17 ltctrl.dtx v1.0b		instead of \next . . . . .	296
General: \@tempa to \reserved@a	56	\prime@s: (DPC) use \@let@token	
1994-11-17 ltdefs.dtx v1.0g		instead of \next and	
General: \@tempa to \reserved@a	36	\expandafter instead of \nxt	299

<code>\smash</code> : (DPC) colour support . . . . .	297	1994-11-30 <code>ltfiles.dtx</code> v1.0o	
(DPC) use <code>\expandafter</code>		<code>\@dofilelist</code> : Macro added . . . . .	101
instead of <code>\next</code> . . . . .	297	<code>\listfiles</code> : Use <code>\@dofilelist</code> . . . . .	100
1994-11-21 <code>ltfloat.dtx</code> v1.1f		<code>\nofiles</code> : There is no	
<code>\@endfloatbox</code> : Added reset of		<code>\@gobblethree</code> . . . . .	93
minipage flag . . . . .	405	1994-11-30 <code>ltfssbas.dtx</code> v2.1y	
Corrected position of		<code>\fontshape</code> : Use <code>\@currentcmd</code> in	
<code>\outer@nobreak</code> . . . . .	405	<code>\@enc@update</code> . ASAJ. . . . .	170
<code>\@marginparreset</code> : Macro added	408	1994-11-30 <code>ltmath.dtx</code> 1.0q	
<code>\@savemarbox</code> : Added		General: ASAJ:	
<code>\@setminipage</code> etc . . . . .	408	<code>\DeclareMathOperator</code> moved	
Added resetting of size and font	408	to AMS $\LaTeX$ . . . . .	294
Changed to <code>\color@vbox</code> . . . . .	408	1994-11-30 <code>ltmiscen.dtx</code> v1.0w	
Use <code>\@setnobreak</code> etc . . . . .	408	<code>\enddocument</code> : (DPC) Do	
<code>\@setminipage</code> : Macro added . . . . .	403	warnings even for <code>\nofiles</code> . . . . .	281
<code>\@setnobreak</code> : Macro added . . . . .	403	(DPC) Use <code>\@dofilelist</code> . . . . .	281
<code>\@xfloat</code> : Added <code>\@setminipage</code>	401	1994-11-30 <code>ltoutenc.dtx</code> 1.7a	
Added resetting of size and font	401	General: Redefined <code>\a</code> for the new	
Changed to <code>\color@vbox</code> so		scheme. . . . .	113
that large floats overflow at the		1994-11-30 <code>ltoutenc.dtx</code> v1.6g	
bottom . . . . .	401	General: Removed new definitions	
Missing percents reinserted after		of <code>\patterns</code> and	
4, 8: these are not numbers. . . . .	400	<code>\hyphenation</code> , since	
Use <code>\@setnobreak</code> . . . . .	401	encoding-specific commands	
<code>\@xympar</code> : Changed to		now expand in the mouth. . . . .	113
<code>\color@vbox</code> . . . . .	409	1994-11-30 <code>ltoutenc.dtx</code> v1.7a	
1994-11-21 <code>ltoutput.dtx</code> v1.1i		General: Added new code for	
<code>\@addtocurcol</code> : Added		encoding-specific commands.	
<code>\if@nobreak</code> test before float		These now expand in the	
box . . . . .	464, 468	mouth, which means that	
<code>\@specialoutput</code> : Added		ligaturing and kerning can	
<code>\if@nobreak</code> test . . . . .	444	happen. . . . .	102
<code>\@topnewpage</code> : Changed to		Always load the <code>enc.def</code> file, so	
<code>\color@vbox</code> . . . . .	439	that the default encoding for	
1994-11-22 <code>ltfssdcl.dtx</code> v2.1o		the commands will change. . . . .	142
General: wrap long lines . . . . .	211	Redefined <code>\@changed@cmd</code> to	
1994-11-22 <code>ltoutenc.dtx</code> v1.6i		expand in the mouth. . . . .	106
General: Corrected <code>\dots</code> so that		Removed <code>\@changed@x@mouth</code>	
there's no kerning in		since <code>\@changed@x</code> now	
monowidth fonts. . . . .	102	expands in the mouth. . . . .	106
Corrected typo with		Rewrote <code>\@text@composite</code> so it	
<code>\mathunderscore</code> . . . . .	102	allows an empty argument, or	
Fixed empty accents. Again. . . . .	102	an argument containing lots of	
1994-11-24 <code>ltdefns.dtx</code> v1.2h		commands. . . . .	108
<code>\@newenv</code> : Added test for <code>\endgraf</code>	42	1994-12-01 <code>ltfinal.dtx</code> v1.0p	
1994-11-25 <code>ltplain.dtx</code> v1.1f		General: Renamed <code>lthyphen.*</code> to	
General: (DPC) Comment out lots		<code>hyphen.*</code> . . . . .	555
of obsolete code . . . . .	15	1994-12-01 <code>lthyphen.dtx</code> v1.0g	
1994-11-26 <code>ltfloat.dtx</code> v1.1b		General: Rename <code>lthyphen.ltx/cfg</code>	
<code>\footnote</code> : (ASAJ) Added		to <code>hyphen.ltx/cfg</code> . . . . .	528
<code>\protected@xdef</code> . . . . .	413	1994-12-01 <code>ltplain.dtx</code> v1.1g	
1994-11-28 <code>ltcntrl.dtx</code> v1.0c		General: (DPC) More doc changes	15
General: Documentation			
improvements . . . . .	56		

1994-12-02 fontdef.dtx v2.2i	1994-12-10 ltfntcmd.dtx v3.3q
General: Commented out <code>\ldots</code> .	<code>\@@math@egroup</code> : Don't read
ASAJ. . . . . 243	arguments . . . . . 273
1994-12-02 ltffssini.dtx v2.2c	<code>\check@nocorr@</code> : Use <code>\space</code>
<code>\copyright</code> : <code>\copyright</code> is now in	command for comparison . . . 270
ltoutenc. ASAJ . . . . . 240	1994-12-10 ltffssdcl.dtx v2.1p
1994-12-02 ltlists.dtx v1.0e	<code>\document@select@group</code> :
<code>\@trivlist</code> : RmS: Added check	Surround with braces (add
for looping . . . . . 315	fourth arg) . . . . . 215
1994-12-02 ltoutenc.dtx 1.7b	<code>\select@group</code> : Surround with
General: Redefined <code>\a</code> properly. . 113	braces (add fourth arg) . . . 213
1994-12-02 ltoutenc.dtx v1.7b	1994-12-10 ltoutenc.dtx v1.7e
General: Fixed a bug with <code>\a</code> . . . 102	General: Added documentation for
1994-12-04 lthyphen.dtx v1.0h	the OML encoding. . . . . 102
General: Documentation edits for	Replaced width with <code>\@width</code>
/1989 . . . . . 528	and ditto height in vrules. . . 102
1994-12-05 ltoutenc.dtx v1.7c	1994-12-14 ltoutenc.dtx v1.7f
General: Added braces to	General: Added braces to
<code>\textcircled</code> . . . . . 102	<code>\copyright</code> so it works
1994-12-06 ltffssbas.dtx v2.1z	unbraced in subscripts. . . . 102
<code>\DeclareFontEncoding</code> : use	Added check for math mode in
<code>\nfss@catcodes</code> . . . . . 165	<code>\@changed@cmd</code> . . . . . 102
<code>\nfss@catcodes</code> : Added tab char	Commented out
as well . . . . . 175	<code>\textasciicircum</code> ,
1994-12-08 ltoutenc.dtx v1.7d	<code>\textasciitilde</code> ,
General: Added <code>\null</code> and <code>\sh@ft</code>	<code>\textbackslash</code> , <code>\textbar</code> ,
to <code>\b</code> and <code>\d</code> . . . . . 102	<code>\textgreater</code> ,
1994-12-08 lttab.dtx v1.0k	<code>\textthyphenchar</code> ,
<code>\@array</code> : Add <code>\tabularnewline</code> . 347	<code>\textthyphen</code> and <code>\textless</code> to
<code>\tabularnewline</code> : (DPC) Made it	save memory. . . . . 102
<code>\relax</code> . . . . . 348	1995-01-12 ltmath.dtx v1.2y classes
1994-12-09 ltbibl.dtx v1.1d	<code>\eqnum</code> : Added <code>\normalcolor</code> . 304
<code>\bibliographystyle</code> : (DPC)	1995-03-03 ltoutenc.dtx 1.7g
Allow use in preamble. . . . 419	General: Corrected an error in
1994-12-10 ltfloat.dtx v1.1g	documentation referring to the
<code>\dblfloat</code> : Old version reinstated	tabular rather than the
temporarily . . . . . 400	tabbing environment. . . . . 113
<code>\dblflset</code> : Macro removed	1995-04-02 ltfntcmd.dtx v3.3r
temporarily . . . . . 399	<code>\@@math@egroup</code> : Read them again
Old version reinstated	to be able to add <code>\relax</code> . . . 273
temporarily . . . . . 399	1995-04-02 ltffssdcl.dtx v2.1q
<code>\setfps</code> : Macro removed	<code>\document@select@group</code> : fix
temporarily . . . . . 400	problem for pr/1275 . . . . . 215
<code>\xdblfloat</code> : Macros reinserted	<code>\select@group</code> : fix problem for
temporarily . . . . . 405	pr/1275 . . . . . 213
<code>\xfloat</code> : Old version reinstated	<code>\set@mathdelimiter</code> : fix pr/1329 232
temporarily . . . . . 400	1995-04-02 ltffssini.dtx v2.2d
Sanitisation added temporarily 400	<code>\not@math@alphabet</code> : add
General: Some temps reinserted	<code>\noexpand</code> to second part of
temporarily . . . . . 396	message . . . . . 238
<code>\fps@dbl</code> : Macro removed	1995-04-21 ltclass.dtx v1.0m
temporarily . . . . . 400	<code>\DeclareOption*</code> : Made long
	/1498 . . . . . 505

<code>\endfilecontents</code> : Close input check stream: latex/1487 ...	514	1995-04-25 ltsect.dtx v1.0k <code>\@dottedtocline</code> : Added <code>\hbox</code> around dots. ....	394
1995-04-21 ltfinal.dtx v1.0q General: Allow initial patch level 0 .....	567	1995-04-27 ltboxes.dtx v1.0s <code>\@framebox</code> : Move <code>\leavevmode</code> for graphics/1512 .....	328
1995-04-21 ltoutenc.dtx v1.7h General: Added <code>\null \k</code> latex/1274 .....	102	<code>\@ifframebox</code> : Move <code>\leavevmode</code> for graphics/1512 .....	328
1995-04-22 ltfiles.dtx v1.0p <code>\includeonly</code> : Allow blanks in argument .....	94	<code>\@iirsbox</code> : Move <code>\leavevmode</code> for graphics/1512 .....	333
1995-04-22 ltmiscen.dtx v1.0x General: Removed extra def of <code>\@gobble</code> .....	279	<code>\@irsbox</code> : Move <code>\leavevmode</code> for graphics/1512 .....	333
1995-04-23 ltsect.dtx v1.0j <code>\addcontentsline</code> : Use <code>\contentsline</code> internally. ..	393	<code>\fbox</code> : Move <code>\leavevmode</code> for graphics/1512 .....	327
1995-04-24 ltbibl.dtx v1.1e <code>\@citex</code> : Add <code>\mbox</code> to undefined case: latex/1239. ....	418	<code>\raisebox</code> : Move <code>\leavevmode</code> for graphics/1512 .....	333
1995-04-24 ltbibl.dtx v1.1f <code>\bibcite</code> : Make <code>\@onlypreamble</code> /1388. ....	418	1995-04-27 ltfiles.dtx v1.0r <code>\document</code> : Added <code>\global</code> to support groups in hook .....	91
1995-04-24 ltcntrl.dtx v1.0d <code>\@for</code> : Dont expand second argument with <code>\edef</code> : /1317 (DPC) .....	58	1995-04-27 ltmiscen.dtx v1.0y <code>\enddocument</code> : <code>\@checkend</code> moved after hook .....	280
1995-04-24 ltoutput.dtx v1.1j <code>\fl@tracemessage</code> : Do not add to kernel unless ‘trace’ specified	481	1995-04-27 ltplain.dtx v1.1i General: Move <code>\hang</code> and <code>\textindent</code> to latex209.def .	28
1995-04-24 ltoutput.dtx v1.1l <code>\@begindvibox</code> : Add <code>\vbox</code> latex/1392 .....	436	1995-04-29 ltcntrl.dtx v1.0e General: Moved init of <code>\protect</code> to ltdefns.dtx .....	59
<code>\@writeseup</code> : Reset <code>\</code> latex/1451 (DPC) .....	452	Removed unused defs for <code>\@setprotect</code> and <code>\@resetprotect</code> .....	59
1995-04-24 ltpage.dtx v1.0f <code>\fussy</code> : reset <code>\emergencystretch</code> latex/1344 .....	423	1995-04-29 ltdefns.dtx v1.2j <code>\protect</code> : Init <code>\protect</code> here ...	46
1995-04-24 ltplain.dtx v1.1h <code>\newlanguage</code> : Remove remaining <code>\outer</code> declarations. ....	17	1995-04-29 ltpar.dtx v1.1b General: (TO) Comments clean-up. ....	69
1995-04-24 ltxref.dtx v1.1e <code>\newlabel</code> : Make <code>\@onlypreamble</code> for /1388. ....	277	1995-05-02 ltsect.dtx v1.0l <code>\@dottedtocline</code> : Don’t reset to <code>\rmfamily</code> .....	394
1995-04-25 ltdefns.dtx v1.2i <code>\@checkc</code> : Make <code>\long</code> for latex/1346 .....	43	1995-05-03 ltsect.dtx v1.0m General: TO: Promoted documentation to doc.sty standard .....	384
<code>\new@environment</code> : Parse arguments slowly but safely /1507 .....	41	1995-05-06 ltsect.dtx 1.0n <code>\@seccntformat</code> : Use <code>\quad</code> instead of <code>\hskip</code> .....	390
1995-04-25 ltfiles.dtx v1.0q <code>\document</code> : Removed execution of <code>\every@size</code> latex/1407 ....	91	<code>\@sect</code> : Added <code>\relax</code> after <code>\@seccntformat</code> just in case	388
		1995-05-07 ltboxes.dtx v1.0t General: Use <code>\hb@xt@</code> .....	323
		1995-05-07 ltdefns.dtx v1.2k <code>\hb@xt@</code> : Macro added .....	36
		1995-05-07 ltmath.dtx v1.0r General: Use <code>\hb@xt@</code> .....	294

1995-05-07 ltoutput.dtx v1.1m		1995-05-17 ltclass.dtx v1.0o	
General: Use <code>\hb@xt@</code> . . . . .	424	<code>\g@addto@macro</code> : Make long for	
1995-05-07 ltpictur.dtx v1.0g		<code>latex/1522</code> . . . . .	513
General: Use <code>\hb@xt@</code> . . . . .	357	1995-05-17 ltlists.dtx v1.0g	
1995-05-07 ltplain.dtx v1.1j		<code>\@item</code> : Removed surplus braces .	319
General: Use <code>\hb@xt@</code> . . . . .	15	<code>\@nbitem</code> : Removed surplus	
1995-05-07 ltsect.dtx v1.0o		braces . . . . .	319
General: Use <code>\hb@xt@</code> . . . . .	384	<code>enumerate</code> : Use <code>\thr@@</code> and	
1995-05-07 lttab.dtx v1.0l		remove surplus braces . . . . .	320
General: Use <code>\hb@xt@</code> . . . . .	335	<code>itemize</code> : Use <code>\thr@@</code> . . . . .	321
1995-05-08 ltbibl.dtx v1.1g		1995-05-18 ltfloat.dtx v1.1j	
<code>\@citex</code> : Use <code>\@firstofone</code> . . . .	418	<code>\@makefnmark</code> : Added	
<code>\bibitem</code> : Removed unnecessary		<code>\normalfont</code> . . . . .	412
braces . . . . .	418	<code>\thempfootnote</code> : Added	
<code>\nocite</code> : Use <code>\@firstofone</code> . . . .	419	<code>\itshape</code> . . . . .	412
1995-05-08 ltdefns.dtx v1.2k		1995-05-19 ltpictur.dtx v1.1a	
<code>\typein</code> : Use <code>\@firstofone</code> . . . .	37	General: Support autoloading	
1995-05-08 ltdefns.dtx v1.2l		feature . . . . .	357
<code>\typein</code> : Remove unnecessary		1995-05-20 ltcounts.dtx v1.1b	
braces . . . . .	37	<code>\@definecounter</code> : Streamlined	
Replace <code>\def</code> by <code>\let</code> . . . . .	37	code . . . . .	157
1995-05-08 ltfsssrc.dtx v2.3n		<code>\@fnsymbol</code> : Allowing both text	
<code>\ifnot@nil</code> : Use <code>\@firstofone</code> .	197	and math . . . . .	160
1995-05-11 fontdef.dtx v2.2j		<code>\fnsymbol</code> : Streamlined code . . .	159
General: Updates to some plain		1995-05-20 ltcounts.dtx v1.1c	
macros . . . . .	243	<code>\@definecounter</code> : And do it right	157
1995-05-12 ltclass.dtx v1.0n		1995-05-20 ltfloat.dtx v1.1k	
<code>\DeclareOption*</code> : Use <code>\toks@</code> to		<code>\@makefnmark</code> : Moved	
remove need to double hash		<code>\normalfont</code> back and use	
<code>/1557</code> . . . . .	505	<code>\@textsuperscript</code> . . . . .	412
1995-05-12 ltfloat.dtx v1.1h		Moved <code>\normalfont</code> to	
<code>\@footnotemark</code> : Add <code>\nobreak</code> to		<code>\textsuperscript</code> . . . . .	412
allow hyphenation. <code>latex/1605</code>	414	<code>\textsuperscript</code> : Use	
1995-05-12 ltpictur.dtx v1.0h		<code>\normalfont</code> . . . . .	413
<code>\pictur@</code> : Macro added for		1995-05-21 ltfssdcl.dtx v2.1t	
<code>latex/1355</code> . . . . .	358	<code>\DeclareMathRadical</code> : Allow for	
1995-05-12 ltvers.dtx v1.0e		undefined cs names . . . . .	233
General: Add autoload docstrip		1995-05-21 ltlists.dtx v1.0f	
guards . . . . .	33	General: Moved to doc.sty	
Check for format older than 1		standard . . . . .	307
year . . . . .	33	1995-05-21 ltmath.dtx v1.0r	
1995-05-13 ltfsssrc.dtx v2.3o		<code>\@sqrt</code> : Use <code>\sqrtsign</code> . . . . .	302
General: Use single hash mark in		General: Remove <code>\mathhexbox</code>	
<code>\DeclareOption</code> . . . . .	186	from this file . . . . .	299
1995-05-16 ltfloat.dtx v1.1i		Update some plain macros . . .	294
<code>\@makefnmark</code> : Now use		<code>\lefteqn</code> : Use <code>\rlap</code> . . . . .	303
<code>\textsuperscript</code> . . . . .	412	<code>\r@t</code> : Use <code>\sqrtsign</code> instead of	
<code>\textsuperscript</code> : Command		<code>\sqrt</code> . . . . .	296
added./pr1503 . . . . .	413	1995-05-21 ltoutenc.dtx v1.7h	
<code>\thefootnote</code> : Streamlined parts		<code>\@inmathwarn</code> : Added several	
of code. . . . .	412	<code>\@onlypreamble</code> . . . . .	106
1995-05-17 ltboxes.dtx v1.0u		1995-05-21 ltoutenc.dtx v1.7j	
<code>\@irsbox</code> : Removed surplus		General: Updated some plain	
braces . . . . .	333	macros . . . . .	118



1995-05-21 ltplain.dtx v1.1j	1995-05-25 ltclass.dtx v1.0p
General: Moved some code to	<code>\endfilecontents</code> : Delete
other files . . . . . 15	<code>\filecontents</code> after preamble 514
1995-05-22 ltplain.dtx v1.1k	1995-05-25 ltfiles.dtx v1.0s
General: Definitions of <code>\footins</code>	<code>\document</code> : Added check for
and <code>\footnoterule</code> moved to	<code>\topskip</code> zero . . . . . 91
ltfloat. . . . . 30	1995-05-25 ltfiles.dtx v1.0t
1995-05-22 lttab.dtx v1.1a	<code>\@iffileonpath</code> : (CAR) added
General: Support autoloading	<code>\long</code> . . . . . 97
feature . . . . . 335	<code>\document</code> : Corrected typo . . . . 91
1995-05-23 ltssini.dtx v2.2e	<code>\IfFileExists</code> : (CAR) added
<code>\newfont</code> : Font assignment made	<code>\long</code> . . . . . 97
local again. . . . . 239	<code>\InputIfFileExists</code> : (CAR)
1995-05-24 ltdefns.dtx v1.1l	added <code>\long</code> . . . . . 98
<code>\newif</code> : (DPC) New	<code>\nofiles</code> : (CAR) added <code>\long</code> .. 93
implementation . . . . . 42	<code>\protected@write</code> : (CAR) added
1995-05-24 ltdefns.dtx v1.2m	<code>\long</code> . . . . . 94
<code>\typein</code> : (DPC) New	1995-05-25 ltfloat.dtx v1.1m
implementation . . . . . 37	<code>\@savemarbox</code> : (CAR) Resettings
1995-05-24 ltfloat.dtx v1.1l	moved to hook . . . . . 408
<code>\@textsuperscript</code> : Command	<code>\xfloat</code> : (CAR) Resettings
added. . . . . 413	moved to hook . . . . . 401
General: Moved definition of	1995-05-25 ltlists.dtx v1.0i
<code>\footins</code> and <code>\footnoterule</code>	<code>\endtrivlist</code> : Macros moved from
from ltplain. . . . . 412	ltspace.dtx . . . . . 316
<code>\textsuperscript</code> : Use	1995-05-25 ltmath.dtx v1.3c classes
<code>\@textsuperscript</code> . . . . 413	<code>\@eqnnum</code> : replace
1995-05-24 ltssbas.dtx v3.0a	<code>\reset@font\rmfamily</code> with
General: (DPC) Make file from	<code>\normalfont</code> (PR 1578) . . . 304
previous file, fam.dtx	1995-05-25 ltspace.dtx v1.2f
1995/05/20 v2.2d . . . . . 163	<code>\@vbsphack</code> : (CAR) not used so
<code>\mathgroup</code> : (DPC) No need to	‘removed’. . . . . 80
redefine <code>\newfam</code> as not outer 163	<code>\@vspacer</code> : (CAR) <code>\@restorepar</code>
1995-05-24 ltsscmp.dtx v3.0a	added to avoid possible infinite
General: (DPC) Make file from	tail recursion caused by a typo
previous file, fam.dtx	in the argument. . . . . 83
1995/05/20 v2.2d . . . . . 207	(CAR) macros modified to be
1995-05-24 ltssdcl.dtx v3.0a	more efficient . . . . . 83
General: (DPC) Make file from	General: Macros moved to
previous file, latint.dtx	ltlists.dtx . . . . . 71
1995/05/21 v2.1t . . . . . 211	1995-05-26 ltdefns.dtx v1.2n
1995-05-24 ltssini.dtx v3.0a	<code>\@gobblefour</code> : (CAR) Added
General: (DPC) Make file from	<code>\longs</code> . . . . . 44
previous file, lfonts.dtx	1995-05-26 ltmath.dtx v1.0s
1995/05/23 v2.2e . . . . . 237	<code>\@eqnnum</code> : Removed <code>\rmfamily</code>
<code>\cal</code> : (DPC) Remove definition . 242	(PR 1578), replaced
<code>\mit</code> : (DPC) Remove definition . 242	<code>\reset@font</code> with
1995-05-24 ltssstrc.dtx v3.0a	<code>\normalfont</code> . . . . . 301
General: (DPC) Make file from	1995-05-26 ltpage.dtx v1.0g
previous file, tracefmt	<code>\ps@plain</code> : removed <code>\rmfamily</code>
1995/05/16 v2.3o . . . . . 185	(PR 1578) . . . . . 422
1995-05-24 ltssstrc.dtx v3.0b	1995-05-27 ltssbas.dtx v3.0b
General: (DPC) Fix	<code>\mathgroup</code> : (FMi) But a need to
<code>\ProvidesFile</code> usage . . . . 185	define <code>\new@mathgroup</code> . . . . 163

1995-06-05 fontdef.dtx v2.2k		1995-06-19 ltbibl.dtx v1.1h	
General: Moved math commands		<b>\biblecite</b> : Call <b>\@newl@bel</b> so	
from ltoutenc.dtx. . . . .	260	repeated keys produce better	
1995-06-05 ltfinal.dtx v1.0r		warning. . . . .	418
General: Added <b>\MakeUppercase</b>		1995-06-19 ltclass.dtx v1.0q	
and <b>\MakeLowercase</b> . . . . .	555	<b>\documentclass</b> : Dont redefine	
1995-06-05 ltoutenc.dtx v1.7k		<b>\usepackage</b> in compat mode	
<b>\@inmathwarn</b> : Removed		for /1634 . . . . .	507
<b>\protected@cmd</b> and replaced		1995-06-19 ltxref.dtx v1.1e	
with explicit <b>\noexpand</b> . . . .	106	<b>\newlabel</b> : Use <b>\@newl@bel</b> to	
General: Allowed		share code with <b>\biblecite</b> . .	277
<b>\ProvideTextCommandDefault</b>		1995-06-28 ltfssini.dtx v3.0b	
after the preamble. . . . .	108	General: (DPC) Fix	
Commented out <b>\textless</b> and		documentation typos . . . . .	237
<b>\textgreater</b> . . . . .	115	1995-06-28 ltmath.dtx v1.0t	
Moved math commands to		General: minor doc edits . . . . .	294
fontdef.dtx. . . . .	117	1995-07-02 ltplain.dtx v1.1n	
Save some tokens in		General: Removed surplus ‘by’ and	
<b>\textvisiblespace</b> and		‘=’ in various places . . . . .	15
<b>\textunderscore</b> . . . . .	115	<b>\offinterlineskip</b> : Replaced	
1995-06-06 ltfinal.dtx v1.0s		1000 by <b>\@m</b> . . . . .	27
General: Made <b>\MakeUppercase</b>		<b>\showoutput</b> : Use <b>\showoverfull</b>	
and <b>\MakeLowercase</b> brace		to save space . . . . .	30
their argument. . . . .	555	<b>\tracingall</b> : Use <b>\showoutput</b> to	
1995-06-09 ltoutenc.dtx v1.7l		save space . . . . .	30
<b>\DeclareTextComposite</b> : Rewrote		1995-07-03 ltdefs.dtx v1.2o	
<b>\DeclareTextComposite</b> to		<b>\set@typeset@protect</b> : Use	
define the composite as a		<b>\@typeset@protect</b> for init . .	46
no-argument command rather		1995-07-03 ltfntcmd.dtx v3.3s	
than a two-argument		<b>\t@st@ic</b> : Use clean interface for	
command. . . . .	109	jump . . . . .	271
1995-06-11 ltspc.dtx v1.2g		1995-07-05 ltfntcmd.dtx v3.3s	
<b>\restorecr</b> : (CAR) <b>\relax</b> added		<b>\t@st@ic</b> : Renamed from	
to stop silent eating of *. . . .	86	<b>\test@next</b> . . . . .	271
1995-06-13 ltfinal.dtx v1.0t		1995-07-05 ltspc.dtx v1.2h	
General: Add patch level string		<b>\@gnewline</b> : Use <b>\break</b> . . . . .	76
more carefully . . . . .	567	<b>\@no@pgbk</b> : Macro replaces <b>\@pgbk</b>	
Call <b>\errorstopmode</b> . . . . .	569	and <b>\@nopgbk</b> . . . . .	75
1995-06-13 ltpictur.dtx v1.1b		<b>\nopagebreak</b> : Reimplemented	
General: Use <b>\ProvidesFile</b> in		both using <b>\@no@pgbk</b> . . . . .	74
autoload . . . . .	357	1995-07-09 ltcntrl.dtx v1.0f	
1995-06-14 lttab.dtx v1.1b		<b>\@iforloop</b> : Reimplemented using	
General: Use <b>\ProvidesFile</b> in		Kabelschacht method . . . . .	59
autoload . . . . .	335	<b>\@iwhiledim</b> : Reimplemented	
1995-06-15 ltfssbas.dtx v3.0c		using Kabelschacht method . .	57
General: (DPC) minor		<b>\@iwhilenum</b> : Reimplemented	
documentation changes . . . .	163	using Kabelschacht method . .	57
1995-06-15 ltfsscnp.dtx v3.0b		<b>\@iwhilesw</b> : Reimplemented using	
General: (DPC) minor		Kabelschacht method . . . . .	57
documentation edits . . . . .	207	<b>\@tfor</b> : Reimplemented using	
1995-06-15 ltfssdcl.dtx v3.0b		Kabelschacht method . . . . .	59
General: (DPC) minor		1995-07-09 ltlists.dtx v1.0j	
documentation changes . . . .	211	<b>enumerate</b> : Use <b>\expandafter</b> . .	321
		<b>itemize</b> : Use <b>\expandafter</b> . . .	321



1995-07-12 ltpictur.dtx v1.1d	1995-08-16 ltcentrl.dtx v1.0g
General: allow 2e commands in 209	\@break@tfor: Made long . . . . . 59
mode. latex/1737 . . . . . 357	\@forloop: Made defs long . . . . . 58
1995-07-13 ltdefns.dtx v1.0p	\@fornoop: Made defs long . . . . . 58
General: Updates to	\@iforloop: Made defs long . . . . . 59
documentation . . . . . 36	\@iwhiledim: Made defs long . . . 57
1995-07-13 ltfiles.dtx v1.0u	Removed \@whilenoop . . . . . 57
General: Updates to docu . . . . . 88	\@iwhilenum: Made defs long . . . 57
1995-07-13 ltfsbas.dtx v3.0d	Removed \@whilenoop . . . . . 57
\@defaultsubs: macro added . . 178	\@iwhilesw: Removed
\@defaultsubs: macro added . . . 178	\@whileswnoop . . . . . 57
General: minor documentation	\@tfor: Made defs long . . . . . 59
changes . . . . . 163	1995-08-16 ltfiles.dtx v1.0v
\wrong@fontshape: Change a	\document: set \@maxdepth . . . . 91
macro not a switch to flag	set \do globally . . . . . 92
default font substitutions . . . 177	set \topskip globally . . . . . 91
1995-07-13 ltmiscen.dtx v1.0z	1995-08-24 ltfsbas.dtx v3.0f
\@centercr: Use \nobreak . . . . 287	General: Added autoload code . . 163
\@writefile: Added missing	1995-08-24 ltfsstrc.dtx v3.0c
percent and use \relax in the	General: Macro
THEN case . . . . . 283	\gobble@font@spec removed . 197
\@xobeyssp: Use \nobreak . . . . 289	\tryis@simple: . . . . . 204
General: Improve Documentation . 279	1995-08-25 ltoutput.dtx v1.1p
\enddocument: Set \@setckpt to	General: Support autoloading
\@gobbletwo instead of	feature (FMi). . . . . 424
defining it by hand . . . . . 280	1995-09-01 lterror.dtx v1.2i
Shorten redefinition of \bibtex	General: Add autoload support . . 60
and \newlabel . . . . . 281	1995-09-01 ltplain.dtx v1.1m
Use \@defaultsubs instead of	\empty: Use \let to save space . . 27
switch . . . . . 281	\I: Use \let to save space . . . . 26
1995-07-14 ltbibl.dtx v1.1i	1995-09-14 ltplain.dtx v1.1o
\bibtex: Remove	General: Moved \multispan to
\@onlypreamble so still defined	lftab.dtx . . . . . 15
in new \enddocument . . . . . 418	1995-09-14 lftab.dtx v1.1c
1995-07-14 ltxref.dtx v1.1g	\cline: (DPC) New
\newlabel: Remove	implementation . . . . . 355
\@onlypreamble so still defined	1995-09-15 ltssini.dtx v3.0e
in new \enddocument . . . . . 277	General: (DPC) Modify TeX2
1995-07-19 ltssini.dtx v3.0d	message . . . . . 241
General: (DPC) TeX2 support . . 241	1995-09-19 ltmiscen.dtx v1.1a
1995-07-20 ltboxes.dtx v1.0v	\verb: Put \@noligs after
\@isavebox: Use \sbox . . . . . 326	\verbatim@font where it
\@isavepicbox: Use \sbox . . . . 326	belongs. . . . . 292
1995-07-21 ltoutput.dtx v1.1o	1995-10-01 ltfiles.dtx LaTeX2e
\@writesetup: Command added . . 451	\@addtofilelist: Macro added . . 100
New, experimental, versions:	1995-10-02 ltdefns.dtx v1.2q
need in-lining . . . . . 451	\@ifnch: Use \@let@token for
1995-08-09 ltmath.dtx v1.0u	internal/924, save \reserved@e . 50
General: Added code for class	\@ifnextchar: Use \@let@token . 50
options leqno and fleqn . . . . 303	\@protected@testopt: Macro
1995-08-11 ltlength.dtx v1.1b	added . . . . . 40
General: Doc typos fixed for	\@testopt: Macro added . . . . . 39
latex/753 . . . . . 162	\@xargdef: New implementation,
	using \@test@opt . . . . . 39

1995-10-03 fontdef.dtx v2.2l		1995-10-16 ltssini.dtx v3.0f	
General: \@@sqr from patch file		\p@reset@font: Added \relax	
for /1701 . . . . .	243	after \usefont, as the latter	
1995-10-03 ltdefns.dtx v1.2r		eats up spaces. . . . .	240
\typein: Add missing \@typein		1995-10-16 ltmath.dtx v1.0y	
for /1710 (from patch file) . . .	38	\@yeqncr: (DPC) Use \@testopt	
1995-10-03 ltpictur.dtx v1.1e		/1911 . . . . .	302
General: New autoloader code . . . .	357	\sqr: (DPC) Make robust /1808	302
1995-10-04 ltssbas.dtx v3.0g		1995-10-16 ltspac.dtx v1.2j	
General: Modify autoloader code . .	163	\nolinebreak: (DPC) Use	
1995-10-04 ltssstrc.dtx v3.0d		\@testopt /1911 . . . . .	74
General: (DPC) Modify autoloader		\nopagebreak: (DPC) Use	
code . . . . .	185	\@testopt /1911 . . . . .	74
1995-10-04 lttab.dtx v1.1d		1995-10-16 ltthm.dtx v1.0g	
General: Modify autoloader support	335	General: Revert to previous	
1995-10-06 ltfiles.dtx v1.0w		\newtheorem behaviour . . . .	380
\@missingfileerror: Autoloader		1995-10-17 ltclass.dtx v1.0r	
error . . . . .	99	\@providesfile: Delay definition	
1995-10-09 lterror.dtx v1.2j		of \ProvidesFile till ltfinal	504
General: Modify autoloader support	60	\ProcessOptions*: Reset	
1995-10-09 ltoutenc.dtx v1.7m		\CurrentOption for	
\@inmathwarn: Autoloader error . .	107	graphics/1873 . . . . .	506
1995-10-10 ltssbas.dtx v3.0h		1995-10-17 ltdirchk.dtx v1.0l	
\showhyphens: Use \normalfont		General: Modify initex version of	
and make colour safe, and		\ProvidesFile . . . . .	4
autoloader . . . . .	181	1995-10-17 ltfinal.dtx v1.0v	
1995-10-10 ltssdcl.dtx v3.0c		\@providesfile: reset macro . . .	569
\non@alpherr: (DPC) autoloader		\reserved@b: reset here after the	
error message . . . . .	215	\input above . . . . .	568
1995-10-10 ltplain.dtx v1.1r		1995-10-17 ltplain.dtx v1.1s	
General: Autoloader tracing code . .	15	\@eject: Move \supereject to	
1995-10-10 ltthm.dtx v1.0f		compat file . . . . .	28
General: Make \newtheorem ‘only		1995-10-17 lttab.dtx v1.1e	
preamble’ . . . . .	380	\@cline: (DPC) Use \@multicnt	356
1995-10-11 ltoutput.dtx v1.1r		\@multispan: (DPC) Macro	
\clearpage: Added a check so that		added. . . . .	356
it does not lose the argument		1995-10-19 ltfinal.dtx v1.0w	
of \twocolumn[...] . . . . .	437	\@filelist: Move after	
1995-10-16 ltbibl.dtx v1.1j		\reserved@a setting;-) . . . .	569
\cite: (DPC) Make robust . . . .	418	1995-10-20 ltbibl.dtx v1.1k	
1995-10-16 ltboxes.dtx v1.0w		\@citex: Removed redefined	
General: Clarify makebox		flag . . . . .	418
description . . . . .	323	\nocite: Removed redefined	
1995-10-16 ltdefns.dtx v1.2u		flag . . . . .	419
\ifstar: (DPC) New		1995-10-20 ltclass.dtx v1.0s	
implementation, for /1910 . . .	50	\@begindocumenthook: Make	
\new@command: (DPC) Use		setting conditional, for	
\@testopt /1911 . . . . .	39	autoloader version . . . . .	512
\new@environment: (DPC) Use		1995-10-20 ltssbas.dtx v3.0i	
\@testopt /1911 . . . . .	41	General: (DPC) Modify autoloader	
\typein: (DPC) Use \@testopt		code, change \undefined . . .	163
/1911 . . . . .	37	1995-10-20 ltssstrc.dtx v3.0e	
		General: (DPC) Modify autoloader	
		code . . . . .	185

1995-10-22 ltfsbas.dtx v3.0j		<code>\end@dblfloat</code> : (CAR) unify code for double and single versions 404
General: (RmS) New size function macro <code>\genb@sfcnt</code> needs to be disabled at <code>\document.</code> . . . 163		<code>\end@float</code> : (CAR) unify code for double and single versions . . . 403
1995-10-22 ltfsstrc.dtx v3.0f		1995-10-25 ltidxglo.dtx v1.1d
General: Added ‘genb’ and ‘sgenb’ size functions to support new DC font naming scheme. . . . 185		General: Doc cleanup . . . . . 415
1995-10-23 lttab.dtx v1.1f		1995-10-25 ltsect.dtx v1.0q
<code>\@settab</code> : (CAR)Ensure that <code>\@hightab</code> increases by at most one . . . . . 342		<code>\subparagraphmark</code> : Use <code>\let</code> not <code>\def</code> to save space. . . . . 391
<code>\@startline</code> : (CAR)Ensure that <code>\@nxctabmar</code> is never larger than <code>\@hightab</code> . . . . . 340		1995-10-27 ltpictur.dtx v1.1f
<code>\@poptabs</code> : (CAR)Ensure that <code>\@curtab</code> is never larger than <code>\@hightab</code> . . . . . 343		General: Move initialisation to kernel from autoloading file . . . 376
<code>\@tabbing</code> : (CAR)Make <code>\@hightab</code> consistently a local variable . 341		1995-10-31 ltboxes.dtx v1.0x
1995-10-24 ltfiles.dtx v1.1a		<code>\@finalstrut</code> : Add <code>\nobreak</code> in horiz mode to allow hyphenation. internal/1931 . 334
<code>\document</code> : Removed multiplelabels switch . . . . . 91		1995-11-01 fontdef.dtx v2.2m
Removed refunddefined switch . 91		General: add <code>\nfss@catcodes</code> for internal/1932 . . . . . 246
1995-10-24 ltfsbas.dtx v3.0k		1995-11-01 ltdirchk.dtx v1.0n
<code>\@@defaults</code> : macro removed 178		General: Initialise <code>\@addtofilelist</code> to <code>\@gobble</code> . 4
<code>\wrong@fontshape</code> : Make this code inline since it happens only here . . . . . 177		1995-11-01 ltfinal.dtx v1.0x
1995-10-24 ltmiscen.dtx v1.1b		General: (DPC) Switch meaning of <code>\@addtofilelist</code> for cfg files 560
<code>\enddocument</code> : Changed logic for producing warning messages and removed switch . . . . . 281		1995-11-01 ltfsbas.dtx v3.0m
Use <code>\@refunddefined</code> instead of switch . . . . . 281		<code>\DeclareFontShape</code> : (DPC) Test for <code>\relax</code> not <code>\undefined</code> , internal/1933 . . . . . 164
1995-10-24 ltxref.dtx v1.1h		1995-11-01 ltssini.dtx v3.0g
<code>\@multiplelabels</code> : Switch for multiplelabels removed . . . . 277		General: (DPC) Switch meaning of <code>\@addtofilelist</code> for cfg files 241
<code>\@newl@bel</code> : Switch for multiplelabels replaced by inline code . . . . . 277		1995-11-02 ltfsbas.dtx v3.0n
<code>\@refunddefined</code> : Switch for refunddefined replaced . . . . . 276		<code>\wrong@fontshape</code> : (DPC) Remove extra space with <code>\string</code> for latex/1676 . . . . 177
<code>\@setref</code> : Switch for refunddefined renamed . . . . . 277		1995-11-02 ltoutenc.dtx v1.7n
<code>\if@multiplelabels</code> : Macro removed . . . . . 277		General: Changed internal name <code>\a</code> to <code>\@tabacckludge</code> to protect against redefinition by malicious users. . . . . 113
1995-10-25 ltalloc.dtx v1.1b		1995-11-07 ltlists.dtx v1.0k
General: General doc improvements . . . . . 54		<code>\@doendpe</code> : Enclosed <code>\setbox0</code> assignment by a group so that it leaves the contents of box 0 intact. . . . . 317
1995-10-25 ltfloat.dtx v1.1n		1995-11-07 ltoutenc.dtx v1.7o
<code>\@endfloatbox</code> : (CAR) macro added: to unify code for double and single versions . . . . . 405		General: Added <code>\leavevmode</code> at start of <code>\c</code> , otherwise the output routine might be invoked within the macro. . . 118
		Changed <code>\char32</code> to <code>\@xxxii</code> (two tokens less). . . . . 118

Replaced octal number 27 by decimal number 23 to protect against the quote character being active. . . . .	118	<code>\textasciitilde</code> , <code>\textbackslash</code> , <code>\textbar</code> , <code>\textgreater</code> and <code>\textless</code> . 121
Replaced some 0's by <code>\z@</code> (faster). . . . .	118	Added <code>\textasciicircum</code> , <code>\textasciitilde</code> , <code>\textregistered</code> and <code>\texttrademark</code> . . . . .
1995-11-10 ltoutput.dtx v1.1s <code>\@shipoutsetup</code> : Command removed . . . . .	451	Added <code>\textbackslash</code> and <code>\textbar</code> . . . . .
<code>\@writsetup</code> : Command removed . . . . .	451	Added <code>\textless</code> and <code>\textgreater</code> . . . . .
In-lined . . . . .	451	1995-12-01 ltoutenc.dtx v1.7u General: Made <code>\SS</code> a Default, rather than having the default point to the OT1 definition. 115
1995-11-14 ltclass.dtx v1.0t <code>\@unprocessedoptions</code> : Allow empty option . . . . .	513	1995-12-04 ltspace.dtx v1.2k <code>\nobreakspace</code> : (Macro added . . . . .
<code>\@loadwithoptions</code> : macro added . . . . .	508	1995-12-04 ltspace.dtx v1.2l <code>\@xobeysp</code> : (braces added to definition of tilde . . . . .
<code>\@loadclasswithoptions</code> : macro added . . . . .	508	1995-12-04 preload.dtx v2.4e General: Ulrik Vieth. added 12pt OMS and OML preloads /1989 . . . . .
<code>\@requirepackagewithoptions</code> : macro added . . . . .	508	1995-12-05 ltdefns.dtx 1.2w <code>\@unexpandable@protect</code> : Removed <code>\unexpandable@noexpand</code> as never used. internal/1733 . . . . .
1995-11-17 ltffsbas.dtx v3.0m <code>\@wrong@font@char</code> : (DPC) Macro added. latex/1676 . . . . .	178	1995-12-05 ltfiles.dtx v1.1c <code>\document</code> : <code>\ignorespaces</code> added for latex/1933 . . . . .
<code>\define@newfont</code> : Redefine <code>\typeout</code> latex/1676 . . . . .	173	1995-12-05 ltfloat.dtx v1.1n <code>\@textsuperscript</code> : Use <code>\ensuremath</code> for latex/1984. 413
<code>\@wrong@fontshape</code> : Support <code>\@wrong@font@char</code> latex/1676 . . . . .	177	1995-12-05 ltoutenc.dtx v1.7v <code>\@inmathwarn</code> : Changed <code>\TextSymbolUnavailable</code> text 107
1995-11-17 ltoutenc.dtx v1.7p <code>\UseTextSymbol</code> : Support <code>\@wrong@font@char</code> latex/1676 . . . . .	111	1995-12-06 ltffsbas.dtx v3.00 <code>\nfss@catcodes</code> : Reset hat, for typeouts etc in fd files . . . . .
1995-11-18 ltoutenc.dtx v1.7q <code>\UseTextSymbol</code> : Modify message slightly . . . . .	111	1995-12-07 ltbibl.dtx v1.1l <code>\@citex</code> : Restored name of <code>\G@refundefinedtrue</code> . . . . .
1995-11-21 fontdef.dtx v2.2n General: Incorporate changed figures, as in plain.tex . . . . .	258	1995-12-07 ltfloat.dtx v1.1m <code>\@textsuperscript</code> : Move <code>\m@th</code> out of the <code>\ensuremath</code> for latex/1984. . . . .
1995-11-27 ltffsbas.dtx v3.0n <code>\nfss@catcodes</code> : Reset hash, for definitions in fd files . . . . .	175	1995-12-07 ltxref.dtx v1.1i <code>\@setref</code> : Switch for refundefined restored . . . . .
1995-11-28 ltfloat.dtx v1.1n General: documentation fixes . . . . .	396	<code>\G@refundefinedtrue</code> : Renamed (back) from <code>\G@refundefined</code> 276
1995-11-28 ltfsstrc.dtx v3.0g General: documentation fixes . . . . .	185	
1995-11-28 ltoutenc.dtx v1.7r General: Added math mode checks to text commands. . . . .	106	
doc fixes . . . . .	102	
Renamed <code>\@changed@x@err</code> to <code>\TextSymbolUnavailable</code> . . . . .	106	
1995-11-29 ltoutenc.dtx v1.7t General: Added <code>\textasciicircum</code> ,		

1995-12-11 ltoutenc.dtx v1.7w	1996-05-18 ltoutenc.dtx v1.7x
General: Modified <code>\copyright</code> .. 115	General: Produce error if encoding not found. pr/2054 ..... 142
1995-12-13 ltdefs.dtx 1.2x	1996-05-21 ltoutenc.dtx v1.7y
<code>\-</code> : Documentation changed. .... 51	General: Corrected error message (CAR) ..... 142
1996-01-10 ltfiles.dtx v1.1d	1996-05-21 ltsect.dtx v1.0s
<code>\@iffileonpath</code> : Change argument handling to not require doubled hash. latex/2024 ..... 97	<code>\@sect</code> : (DPC) Added extra braces for internal/2148 ..... 388
1996-01-20 ltidxglo.dtx v1.1e	(DPC) Moved brace to allow commands like <code>\MakeUppercase</code> in 6th argument. Changed <code>\par</code> to <code>\endgraf</code> to allow non-long commands. internal/2148 .. 388
<code>\makeglossary</code> : Make no-op after use pr/2048 ..... 416	<code>\@sssect</code> : (DPC) Added extra braces for internal/2148 .... 391
<code>\makeindex</code> : Make no-op after use pr/2048 ..... 416	(DPC) Moved brace to allow commands like <code>\MakeUppercase</code> in 4th argument. Changed <code>\par</code> to <code>\endgraf</code> to allow non-long commands. internal/2148 .. 390
1996-01-20 ltspace.dtx v1.2m	1996-05-23 ltoutenc.dtx v1.7z
<code>\vspace</code> : Made robust ..... 83	<code>\@strip@args</code> : <code>\expandafter</code> added to match other changes for latex/2133 ..... 111
1996-03-25 ltmath.dtx v1.1a	<code>\add@accent</code> : macro added. latex/2133 ..... 108
<code>\@ensuredmath</code> : Macro added for amslatex/2104 ..... 303	<code>\DeclareTextAccent</code> : Reimplemented using <code>\add@accent</code> to save space latex/2133 ..... 108
<code>\ensuremath</code> : Reimplement for amslatex/2104 ..... 303	<code>\DeclareTextCompositeCommand</code> : Modified to cope with new <code>\add@accent</code> command: required removal of check for one argument-command ... 109
1996-04-18 ltpage.dtx v1.0i	1996-05-24 ltoutput.dtx v1.1t
General: Improve documentation 421	<code>\@specialoutput</code> : Check that <code>\@colroom</code> is less than <code>\vsize</code> , indicating that a float has been added ..... 442
1996-04-22 ltmiscen.dtx v1.1c	Cut-off point changed to 1.5 <code>\baselineskip</code> ..... 442
General: Improve Documentation 279	<code>\@topnewpage</code> : Cut-off point changed to 2.5 <code>\baselineskip</code> 441
1996-04-22 ltspace.dtx v1.2n	1996-05-25 ltoutput.dtx v1.1u
General: Documentation Improvements ..... 71	<code>\@specialoutput</code> : Correct the above check ..... 442
1996-04-22 lttab.dtx v1.1g	1996-06-03 ltmiscen.dtx v1.1d
<code>\@tabclassz</code> : (DPC) Extra <code>\hskip</code> keeps <code>tabcolsep</code> in empty columns internal/2122 ..... 354	<code>\@verbatim</code> : Exchanged the following two code lines so that <code>\dospecials</code> cannot reset the
1996-04-23 ltcounts.dtx v1.1d	
General: Documentation improvements ..... 155	
1996-04-24 ltfiles.dtx v1.1e	
<code>\document</code> : (DPC) Reset <code>\AtBeginDocument</code> eg for latex/1297 ..... 91	
1996-05-08 ltfssstrc.dtx v3.0h	
<code>\math@egroup</code> : Use <code>\bgroup</code> instead of <code>\begingroup</code> to match a kernel change made in 1994!! ..... 195	
1996-05-09 ltfntcmd.dtx v3.3t	
<code>\check@icr</code> : Default definitions added ..... 269	
1996-05-17 fontdef.dtx v2.2o	
General: <code>\@sqrt</code> removed, at last ..... 243, 258	
1996-05-17 ltfiles.dtx v1.1f	
<code>\nofiles</code> : added <code>\write</code> to <code>\protected@write</code> for latex/2146 ..... 93	

category code of characters handled by <code>\@noligs</code> . . . . .	290	<code>\@savemarbox</code> : remove unnecessary <code>\global</code> before <code>\@minipage</code> ... . . . .	408
General: Move setting of verbatim font and <code>\@noligs</code> . . . . .	279	<code>\@setminipage</code> : remove unnecessary <code>\global</code> before <code>\@minipage</code> ... . . . .	403
<code>\verb</code> : Put setting of verbatim font after <code>\dospecials</code> so that <code>\dospecials</code> cannot reset the category code of characters handled by <code>\@noligs</code> . . . . .	292	<code>\@setnobreak</code> : remove unnecessary <code>\global</code> before <code>\@nobreak</code> ... . . . .	403
1996-06-10 <code>ltboxes.dtx</code> v1.0y <code>\@parboxto</code> : (DPC) Changed <code>\endgraf</code> to <code>\@@par</code> . . . . .	329	1996-07-26 <code>ltfssbas.dtx</code> v3.0p <code>\@DeclareMathSizes</code> : use faster <code>\if</code> test . . . . .	168
1996-06-10 <code>ltssect.dtx</code> v1.0t <code>\@sect</code> : (DPC) Changed <code>\endgraf</code> to <code>\@@par</code> . . . . .	388	<code>\nfss@catcodes</code> : omit <code>\relax</code> as not needed . . . . .	175
<code>\@sect</code> : (DPC) Changed <code>\endgraf</code> to <code>\@@par</code> . . . . .	390	1996-07-26 <code>ltfssdcl.dtx</code> v3.0e <code>\init@restore@version</code> : Removed <code>\ifrestore@version</code> switch and replaced by <code>\init@restore@version</code> . . . . .	215
1996-06-13 <code>ltdirchk.dtx</code> v1.0r General: documentation improvements mainly from internal/2174 . . . . .	1	1996-07-26 <code>ltfssstrc.dtx</code> v3.0i <code>\init@restore@glb@settings</code> : macro added replacing <code>\if@inmath</code> switch . . . . .	194
1996-06-14 <code>lttab.dtx</code> v1.1h <code>\@tabclassz</code> : (DPC) Change both <code>\z@skip</code> to <code>1sp</code> for latex/2160 . . . . .	354	1996-07-26 <code>ltlists.dtx</code> v1.0l <code>\@item</code> : Remove unnecessary <code>\global</code> before <code>\@minipage</code> ... . . . .	318
1996-06-22 <code>ltspace.dtx</code> v1.2o General: Documentation of problems added . . . . .	71	Remove unnecessary <code>\global</code> before <code>\@nobreak</code> ... . . . .	319
1996-07-10 <code>ltfinal.dtx</code> v1.0y <code>\@toks</code> : Free up memory from scratch registers /2213 . . . . .	568	1996-07-26 <code>ltmath.dtx</code> v1.1b General: Removed <code>\global</code> before <code>\@ignoretrue</code> in various places. . . . .	294
1996-07-19 <code>ltoutenc.dtx</code> v1.8a <code>\@strip@args</code> : Use char 0 not @ as carrier for <code>\lowercase</code> /2197 . . . . .	111	1996-07-26 <code>ltmiscen.dtx</code> v1.1e <code>\@ignorefalse</code> : put <code>\global</code> into definition . . . . .	280
1996-07-26 <code>ltboxes.dtx</code> v1.0z <code>\if@minipage</code> : put <code>\global</code> into definition . . . . .	331	<code>\begin</code> : remove <code>\global</code> before <code>\@ignore</code> ... . . . .	284
1996-07-26 <code>ltclass.dtx</code> v1.0u <code>\@classoptionslist</code> : made only preamble . . . . .	500	<code>\end</code> : remove <code>\global</code> before <code>\@ignore</code> ... . . . .	286
<code>\@unusedoptionlist</code> : made only preamble . . . . .	501	<code>\ignorespacesafterend</code> : user level macro added . . . . .	280
1996-07-26 <code>ltdefns.dtx</code> v1.2y <code>\@reargdef</code> : third arg picked up by <code>\@yargdef</code> . . . . .	41	1996-07-26 <code>ltoutput.dtx</code> v1.1v <code>\@testfp</code> : remove <code>\global</code> before <code>\@test</code> ... . . . .	484
<code>\renew@command</code> : use <code>\noexpand</code> instead of <code>\string</code> . . . . .	41	<code>\@xtryfc</code> : remove <code>\global</code> before <code>\@test</code> ... . . . .	459
use <code>\relax</code> in place of empty arg . . . . .	41	<code>\@ztryfc</code> : remove <code>\global</code> before <code>\@test</code> ... . . . .	460
<code>\renew@environment</code> : use <code>\relax</code> in place of empty arg . . . . .	42	General: put <code>\global</code> into definition . . . . .	434
1996-07-26 <code>ltfloat.dtx</code> v1.1n <code>\@endfloatbox</code> : remove unnecessary <code>\global</code> before <code>\@minipage</code> ... . . . .	405	remove <code>\global</code> before <code>\@test</code> ... . . . .	434, 435
		<code>\clearpage</code> : add number of missing percents . . . . .	437



1996-07-26 ltplain.dtx v1.1t		1996-09-29 ltsect.dtx 1.0w	
\sh@ft: replace \dimen\z@ by		\@noskipsectrue: Added	
\dimen@ . . . . .	29	documentation . . . . .	385
1996-07-26 ltsect.dtx v1.0u		1996-09-30 ltoutput.dtx v1.1y	
\@starttoc: removed \global		\newpage: Checks for noskipsec	
before \@nobreak . . . . .	392	and inlabel removed pending	
\@xsect: Removed \global before		further tests . . . . .	438
\@nobreak . . . . .	389	1996-10-04 ltclass.dtx v1.0v	
1996-07-26 ltspace.dtx v1.2p		\RequirePackageWithOptions:	
\if@nobreak: put \global inside		Reset \@unprocessedoptions	
definition . . . . .	76	for /2269 . . . . .	508
1996-07-27 ltssbas.dtx v3.0q		1996-10-05 ltfiles.dtx v1.1h	
General: \if@inmath switch		\@clubpenalty: Added setting its	
removed . . . . .	172	value . . . . .	90
1996-07-27 ltspace.dtx v1.2q		1996-10-08 ltfntcmd.dtx v3.3u	
General: Further documentation of		\DeclareTextFontCommand:	
problems . . . . .	71	Removed \check@icr when in	
1996-07-27 ltspace.dtx v1.2r		vmode since it causes various	
General: Correct documentation of		errors (see pr/2157) . . . . .	268
problems . . . . .	71	1996-10-21 lttab.dtx v1.1i	
1996-08-02 ltfloat.dtx v1.1o		\@array: Use	
\@xympar: Remove \global before		\set@typeset@protect . . . .	347
\@ignore . . . . .	409	General: Moved the code	
1996-08-02 ltsect.dtx v1.0v		associated with \@mkpream into	
\@afterheading: Removed		the group provided by the box,	
\global before \@nobreak . .	391	for robustness (latex/2183) .	347
1996-08-02 ltspace.dtx v1.2s		\multicolumn: Make	
\@Esphack: Remove \global		\multicolumn long	
before \@ignore . . . . .	79	(latex/2180) . . . . .	349
1996-08-25 ltssbas.dtx v3.0r		\tabbing: Moved the \indent so	
\nfss@catcodes: Reset the acute,		that the \everypar can remove	
grave and double quote chars		it when necessary; this is	
as well . . . . .	175	needed because the code for	
1996-09-21 ltoutput.dtx v1.1w		items in lists has changed (see	
\@writeseup: Added		pr/22111) . . . . .	341
\@parboxrestore and made		1996-10-23 ltlists.dtx v1.0m	
consequent deletions: wait for		\@item: \@nobreak . . . moved into	
the howls of protest . . . . .	451	the \everypar and not	
1996-09-25 ltdirchk.dtx v1.0t		executed unconditionally, see	
General: Move ltxcheck to separate		above . . . . .	319
file . . . . .	14	\kern . . . changed to	
1996-09-28 ltmiscen.dtx v1.1f		\setbox . . . . .	318
\@xobeysp: Moved to ltspace.dtx	289	Added setting of \@clubpenalty	
1996-09-28 ltspace.dtx v1.2t		and set \@nobreakfalse only	
\@xobeysp: Moved from		when necessary . . . . .	319
ltmiscen.dtx and redefined to		1996-10-23 ltsect.dtx v1.0x	
use \@nobreakspace . . . . .	84	\@xsect: Replaced \hskip . . .	
1996-09-29 ltfiles.dtx v1.1g		with \setbox . . . as used in	
\document: Added disabling of		\@afterheading . . . . .	389
\@nodocument . . . . .	92	1996-10-24 ltboxes.dtx v1.1a	
1996-09-29 ltoutput.dtx v1.1x		\@arrayparboxrestore: Added	
\newpage: Checks for noskipsec		local settings of flags:	
and inlabel added . . . . .	438	dangerous! . . . . .	330

<code>\@iiiminipage</code> : Use it or lose it ( <code>\@setminpage</code> ): Frank will want to lose it . . . . .	331
1996-10-24 <code>ltfloat.dtx</code> v1.1p	
<code>\@floatboxreset</code> : Added local settings of flags: dangerous! .	403
<code>\@marginparreset</code> : Added local settings of flags: dangerous! .	409
<code>\@xfloat</code> : Added <code>\@nodocument</code> to trap floats in the preamble .	400
1996-10-24 <code>ltoutput.dtx</code> v1.1z	
<code>\@addtocurcol</code> : Added <code>\nobreak</code> , etc as appropriate . . . . .	464, 468
<code>\@specialoutput</code> : Added <code>\nobreak</code> as appropriate . . .	444
<code>\@topnewpage</code> : Added <code>\@nodocument</code> to trap <code>\twocolumn</code> in the preamble	439
<code>\newpage</code> : Better checks for <code>noskipsec</code> and <code>inlabel</code> added, plus <code>nobreak</code> . . . . .	438
1996-10-25 <code>ltlists.dtx</code> v1.0n	
<code>\endtrivlist</code> : Change <code>\indent</code> to <code>\leavevmode</code> . . . . .	316
Reset flags explicitly . . . . .	316
1996-10-25 <code>ltoutput.dtx</code> v1.2a	
<code>\newpage</code> : Reset all flags explicitly . . . . .	438
1996-10-26 <code>ltlists.dtx</code> v1.0o	
<code>\endtrivlist</code> : Correct typo . . . .	316
1996-10-27 <code>ltoutenc.dtx</code> v1.8c	
<code>\@strip@args</code> : Removed macro .	109
General: Added <code>\r A</code> . . . . .	119
Added <code>\textasteriskcentered</code> . . . . .	115, 125
Corrected syntax descriptions .	103
Removed <code>\aa</code> and <code>\AA</code> . . . . .	114, 118, 121
1996-10-28 <code>ltplain.dtx</code> v1.1u	
General: (CAR) More doc changes	15
<code>\dotfill</code> : Removed math mode .	30
1996-10-29 <code>ltplain.dtx</code> v1.1v	
<code>\dotfill</code> : Got arithmetic correct (CAR) . . . . .	30
1996-10-29 <code>ltspace.dtx</code> v1.2u	
<code>\@gnewline</code> : Added macro . . . . .	76
<code>\@no@lnbk</code> : Macro replaces <code>\@lnbk</code> and <code>\@no@lnbk</code> . . . . .	75
<code>\@</code> : Corrected and rationalised code	75
<code>\nolinebreak</code> : Reimplemented both using <code>\@no@lnbk</code> . . . . .	74
1996-10-31 <code>ltfinal.dtx</code> v1.0z	
General: Added extra <code>\lcode</code> , hoping it does no harm in T1 (pr/1969) . . . . .	559, 566
1996-10-31 <code>ltlists.dtx</code> v1.0p	
<code>\@trivlist</code> : Added check for missing item in outer list . . .	315
1996-10-31 <code>ltsect.dtx</code> v1.0y	
General: Corrected and tidied documentation; removed long lines . . . . .	384
1996-11-03 <code>ltplain.dtx</code> v1.1w	
<code>\dotfill</code> : Saved tokens by using <code>\hb@xt@</code> . . . . .	30
1996-11-04 <code>lterror.dtx</code> v1.2m	
<code>\@nodocument</code> : Always define <code>\@nodocument</code> in kernel, so that it can be cleared by <code>\document</code> .	66
1996-11-04 <code>ltlists.dtx</code> v1.0q	
<code>\@trivlist</code> : Moved check for missing item: only checked when not <code>inlabel</code> flag is false	315
1996-11-05 <code>ltfiles.dtx</code> v1.1i	
<code>\nofiles</code> : Standard <code>\if@nobreak</code> test added . . . . .	93
1996-11-09 <code>ltmath.dtx</code> v1.1c	
<code>\@ensuredmath</code> : Made long, as it was before. /2104 . . . . .	303
1996-11-18 <code>ltfssbas.dtx</code> v3.0s	
<code>\define@newfont</code> : (DPC) lowercase fd file names. internal/1044 . . . . .	174
1996-11-18 <code>ltoutenc.dtx</code> v1.8d	
General: (DPC) lowercase external file names. internal/1044 . . .	142
1996-11-20 <code>fontdef.dtx</code> v2.2p	
General: lowercase fd and enc.def file names /1044 . . . . .	243
1996-11-20 <code>ltvers.dtx</code> v1.0f	
General: Check for old format modified /2319 . . . . .	33
1996-11-23 <code>ltoutenc.dtx</code> v1.8e	
General: Corrected description . .	103
Extended description . . . . .	104
1996-11-28 <code>ltvers.dtx</code> v1.0g	
General: Check for old format modified /2319 . . . . .	33
1996-12-06 <code>ltdirchk.dtx</code> v1.0u	
<code>\IfFileExists</code> : *** removed from various messages for GNU Make. internal/2338 . . . . .	10
1996-12-06 <code>ltfloat.dtx</code> v1.1r	
<code>\@caption</code> : Call <code>\@setminpage</code> if needed. latex/2318 . . . . .	399
1996-12-06 <code>ltfssini.dtx</code> v3.0h	
General: (DPC) Remove *** from messages internal/2338 . . . .	241



1996-12-17 ltclass.dtx v1.0w	Modified <code>\underscore</code> , removing <code>\mathunderscore</code> .	116
<code>\g@addto@macro</code> : Use <code>\begingroup</code> to save making a <code>mathord</code> ..		513
1996-12-20 ltsect.dtx v1.0z	General: Added <code>\leavevmode</code> to <code>\textunderscore</code> .....	115
<code>\dottedtocline</code> : Added <code>\nobreak</code> for latex/2343 ...		394
1997-01-08 fontdef.dtx v2.2q	General: Use <code>\DeclareMathDelimiter</code> to set delimiter codes .....	252
<code>\mathparagraph</code> : Define using <code>\DeclareMathSymbol</code> .....		260
1997-01-08 ltfiles.dtx v1.1j	<code>\include</code> : reset <code>\deadcycles</code> latex/2365 .....	95
1997-01-08 ltmath.dtx v1.1d	<code>\root</code> : (DPC) Remove spurious space tokens from plain $\TeX$ definition /2359 .....	296
1997-02-05 ltclass.dtx v1.0x	<code>\g@addto@macro</code> : missing percent /2402 .....	513
1997-02-21 ltlists.dtx v1.0r	<code>\@item</code> : <code>\ifvoid</code> check added for <code>\noindent</code> . latex/2414 ....	318
1997-03-21 ltcounts.dtx v1.1e	<code>\fnsymbol</code> : Use <code>\mathsection</code> and <code>\mathparagraph</code> . latex/2445	159
1997-04-14 ltfiles.dtx v1.1k	<code>\document</code> : Set the document space factor defaults. latex/2404 .....	91
<code>\normalsfcodes</code> : Macro added (from patch file) latex/2404 ..		93
1997-04-14 ltoutput.dtx v1.2b	<code>\@writsetup</code> : Call <code>\normalsfcodes</code> (from patch file) latex/2404 .....	453
Move <code>\label</code> and <code>\index</code> (from patch file) .....		453
1997-04-24 ltbibl.dtx v1.1m	<code>\citex</code> : <code>\@empty</code> to avoid primitive error on empty cite keys. latex/2432 .....	418
1997-04-30 ltoutenc.dtx v1.9a	General: Changed <code>\textsc</code> to <code>\scshape</code> .....	116
Introduced <code>\textcopyright</code> and modified <code>\copyright</code> .....		115
Introduced <code>\textcopyright</code> and modify <code>\copyright</code> .....		116
Modified <code>\textunderscore</code> , removing <code>\mathunderscore</code> .		115
1997-04-30 ltoutenc.dtx v1.9b	General: Added <code>\leavevmode</code> to <code>\textunderscore</code> .....	115
1997-05-04 ltoutenc.dtx v1.9c	General: Added ‘hex index tabs’ . Added TS1 encoding v2.2.beta	122 128
1997-05-07 ltoutenc.dtx v1.9d	General: Added <code>\leavevmode</code> to <code>\textcompwordmark</code> .....	115
1997-05-07 ltspace.dtx v1.2v	<code>\newline</code> : Made completely robust. ....	76
1997-05-29 ltfstrc.dtx v3.0j	General: Replaced <code>\</code> by <code>\MessageBreak</code> , as suggested by Donald Arseneau. ....	187
1997-05-29 ltlogos.dtx v1.1f	$\LaTeX$ : Added <code>\m@th</code> so that the $\LaTeX$ 2 $\epsilon$ logo works with non-zero values of <code>\mathsurround</code> . ....	87
1997-06-16 ltdirchk.dtx v1.0v	General: documentation improvements mainly from internal/2520 .....	1
1997-06-16 ltfloat.dtx v1.1s	General: documentation fixes ...	396
1997-06-16 ltfntcmd.dtx v3.3v	General: Fix typo in documentation. ....	266
1997-08-05 ltoutenc.dtx v1.9e	General: Corrected order of arguments in <code>\UseTextSymbol</code> example. ....	103
1997-08-29 ltoutenc.dtx v1.9f	General: Added OT4 encoding, provided by Marcin Woliński.	102
1997-09-09 ltdefns.dtx v1.2z	<code>\providecommand</code> : Use <code>\begingroup</code> to avoid generating math ords if used in math mode. pr/2573 .....	43
1997-09-15 ltpictur.dtx v1.1g	<code>\getcirc</code> : Warn if lines become invisible pr/2524 .....	373
<code>\@picture@warn</code> : Macro added pr/2524 .....		373
<code>\@sline</code> : Warn if lines become invisible pr/2524 .....		364
1997-10-06 ltcounts.dtx v1.1f	<code>\@Roman</code> : Change <code>\@Roman</code> to be fully expandable, so that the	

- result is written properly to files. . . . . 159
- `\@slowromancap`: Macro added. . 159
- 1997-10-08 `ltlogos.dtx` v1.1h
- `\LaTeX`: Simplify macro (force loading of suitable math fonts once). . . . . 87
- 1997-10-10 `ltclass.dtx` v1.0y
- `\endfilecontents`: `\@currenvir` in banner . . . . . 516
- `\reserved@c` not `\verbatim@out` to save a csname . . . . . 515
- Check for text before or after `\end` environment. `latex/2636` 517
- Use `\@gobbletwo` . . . . . 515
- 1997-10-17 `lftntcmd.dtx` v3.3w
- `\check@nocorr@`: Check for vertical mode moved here, from `\DeclareTextFontCommand` (see `PR/2646`). . . . . 270
- `\DeclareTextFontCommand`: Reinstalled `\check@icr` as check is now done in `\check@nocorr@` (see `PR/2646`). . . . . 268
- 1997-10-20 `ltfinal.dtx` v1.1a
- `\@uclclist`: Removed `\aa` and `\AA` from `\@uclclist` as these are macros. . . . . 566
- 1997-10-21 `ltdefns.dtx` v1.2z1
- `\renew@command`: Use `\begingroup`/`\endgroup` rather than braces for grouping, to avoid generating empty math atom. . . . . 41
- 1997-10-21 `ltfssbas.dtx` v3.0t
- `\define@newfont`: Move `\makeatletter` to `\nfss@catcodes`. . . . . 174
- `\nfss@catcodes`: Moved `\makeatletter` from `\try@load@font@shape`. . . . 175
- 1997-11-09 `ltoutput.dtx` v1.2c
- `\@specialoutput`: Remove incorrect code: only one `\@emptycol` is needed here . . 442
- `\@topnewpage`: Documentation of `vsiz` check enhanced . . . . 439
- 1997-11-13 `ltfssdcl.dtx` v3.0f
- `\DeclareSymbolFont`: (DPC) Really update `\group@list` dont leave new version in `\toks@`. `latex/2661` . . . . . 219
- `\stepcounter`: (DPC) Remove as never used. (Re)defined in `ltcounts` . . . . . 213
- 1997-11-19 `ltfloat.dtx` v1.1t
- `\@footnotetext`: Missing percent, again . . . . . 413
- 1997-11-19 `ltoutput.dtx` v1.2d
- `\@vtryfc`: Reindent code, to be understandable(DPC). . . . 458
- 1997-11-20 `ltfssdcl.dtx` v3.0g
- `\document@select@group`: (DPC) inline use of `\stepcounter` (faster, and saves a csname per math version as no reset list) 215
- `\select@group`: (DPC) inline use of `\stepcounter` (faster, and saves a csname per math version as no reset list) . . . . 213
- 1997-11-23 `ltoutenc.dtx` v1.9g
- General: Use `\textperthousand`, `\textpertenthousand` and `\textfractionsolidus` not `\textpermill`, `\textpertenmill` and `\textfraction`. `/2673` . . . . 128
- 1997-12-17 `ltoutenc.dtx` v1.9h
- General: Added `\textperthousand` and `\textpertenthousand` . . 120
- Added code for `textcomp.sty`. . 142
- Added section. . . . . 142
- Added `textcomp.sty`. . . . . 102
- As in OT1, Added `\leavevmode` at start of `\c`, otherwise the output routine might be invoked within the macro. . . 120
- Changed to decimal codes in `\ooalign`. . . . . 130
- Changed to decimal codes. . . 126
- Documentation changes and additions. . . . . 102
- Example corrected, braces removed. . . . . 102
- Removed default settings, see next section. . . . . 128
- 1997-12-19 `ltoutenc.dtx` v1.9i
- General: Documentation corrections. . . . . 102
- 1997-12-20 `fontdef.dtx` v2.2s
- General: Added documentation . 245
- 1997-12-31 `ltoutenc.dtx` v1.9k
- General: Further correction . . . 103
- 1998-01-12 `ltoutenc.dtx` v1.9k
- General: Added `\ProvidesPackage` for `textcomp.sty` . . . . . 102

Adding missing braces and <code>\ushape</code> . . . . .	130	1998-05-07 ltclass.dtx v1.1b <code>\@fileswithoptions</code> : Modify help message for latex/2805 . . . .	511
1998-01-16 ltoutenc.dtx v1.9m General: fixed decimal codes. latex/2734 . . . . .	126	1998-05-18 lttab.dtx v1.1j <code>\@endpbox</code> : Use <code>\setlength</code> to set <code>\hsize</code> , so that the changes in the calc package apply here. . . .	356
1998-03-04 ltdefns.dtx v1.2z2 <code>\@xargdef</code> : Unnecessary <code>\expandafter</code> removed: pr/2758 . . . . .	39	<code>\tabular*</code> : Use <code>\setlength</code> , so that calc extensions apply. . . .	346
1998-03-05 ltoutenc.dtx v1.9n General: Added masc/fem ords as in pr/2579 . . . . .	116	1998-05-20 ltfinal.dtx v1.1b General: Set up lccodes before loading hyphenation files: pr/2639 . . . . .	559
1998-03-20 ltdefns.dtx v1.2z3 <code>\@thirdofthree</code> : Macro added . .	44	Set up uc/lccodes after loading hyphenation files: pr/2639 . .	565
1998-03-20 ltoutenc.dtx v1.9o General: Added various <code>\UndeclareTextCommand</code> declarations for pr/2783 . . .	152	1998-05-28 lterror.dtx v1.2n <code>\@notdefinable</code> : Added message re ‘end...’ pr/1555 . . . . .	65
Documentation added about order of decls . . . . .	105	1998-06-04 ltboxes.dtx v1.1c <code>\@rule</code> : Support calc-expressions .	332
Documentation added for pr/2783 . . . . .	104	1998-06-12 ltoutenc.dtx v1.9p General: Corrected 130 and 131, see pr/2834 . . . . .	130
Load decls after defaults for speed. . . . .	152	Renamed <code>\textmacron</code> pr/2840 . . . . .	132, 148
<code>\UndeclareTextCommand</code> : Macro added for pr/2783 . . . . .	112	1998-06-12 ltoutenc.dtx v1.9q <code>\add@accent</code> : Explicitly set <code>\spacefactor</code> after <code>\accent</code> (pr/2877) . . . . .	109
1998-03-21 ltclass.dtx v1.0z General: Added to documentation of filecontents . . . . .	496	1998-06-18 lttab.dtx v1.1k General: Small addition to documentation . . . . .	335
1998-03-21 ltclass.dtx v1.1a <code>\@providesfile</code> : Allow &. Internal/2702 . . . . .	504	1998-07-06 lttab.dtx v1.1l General: Small correction to documentation . . . . .	335
General: Correct to new onlypreamble command list . .	527	1998-08-17 ltboxes.dtx v1.1e General: (RmS) Minor Documentation fixes. . . . .	322
1998-03-25 ltffsbas.dtx v3.0u <code>\showhyphens</code> : Suppress unnecessary error when used in preamble . . . . .	181	1998-08-17 ltclass.dtx v1.1c General: (RmS) Minor documentation fixes. . . . .	496
1998-04-11 fontdef.dtx v2.2t General: Added <code>\mathring</code> accent (pr2785) . . . . .	258	1998-08-17 ltdirchk.dtx v1.0w General: (RmS) Documentation improvements. . . . .	1
1998-04-15 fontdef.dtx v2.2u General: Use new syntax for <code>\DeclareMathDelimiter</code> . . .	252	1998-08-17 ltfntcmd.dtx v3.3x General: (RmS) Minor documentation fixes. . . . .	266
1998-04-15 ltffsdcl.dtx v3.0h <code>\@xxDeclareMathDelimiter</code> : Macro added (pr/2662) . . . .	229	1998-08-17 ltffsbas.dtx v3.0v General: (RmS) Documentation fixes. . . . .	163
1998-04-17 fontdef.dtx v2.2v General: Reinsert symbol defs for < and > chars. . . . .	252	1998-08-17 ltffsdcl.dtx v3.0i General: (RmS) Corrected minor glitches in changes entries. . .	211

1998-08-17 ltffsini.dtx v3.0i	1999-01-07 ltdefns.dtx v1.3b
General: (RmS) Minor	<code>\@ifnextchar</code> : extra <code>\long</code> .
documentation fixes. . . . . 237	latex/2902 . . . . . 50
1998-08-17 ltlogos.dtx v1.1i	1999-01-07 ltoutenc.dtx v1.9r
General: (RmS) Minor	General: Hackery to allow using
documentation fixes. . . . . 87	fontenc several times . . . . . 144
1998-08-17 ltmath.dtx v1.1c	Hackery to temp support cyrillic
General: (RmS) Minor	uc/lc . . . . . 142
documentation fixes. . . . . 294	1999-01-13 ltoutenc.dtx v1.9s
1998-08-17 ltmiscen.dtx v1.1g	<code>\@strip@args</code> : Simplified solution
General: (RmS) Minor	for latex/2930 . . . . . 111
documentation fixes. . . . . 279	1999-01-18 ltdefns.dtx v1.3c
1998-08-17 ltspace.dtx v1.2w	<code>\@yargd@f</code> : New implementation
General: Documentation fixes. . . 71	DPC /2942 . . . . . 40
1998-08-17 preload.dtx v2.1g	1999-02-09 ltdefns.dtx v1.3d
General: (RmS) Minor	<code>\@yargd@f</code> : catch bad argument
documentation fixes. . . . . 262	forms by re-inserting #3 . . . . 40
1998-09-19 ltoutenc.dtx v1.9r	1999-02-12 ltffsini.dtx v3.0j
<code>\a</code> : Added <code>\string</code> (pr/2878) . . . 114	<code>\oldstylenums</code> : Use <code>\rmdefault</code>
1998-11-13 lttab.dtx v1.1m	instead of <code>cmm</code> (pr/2954) . . . 239
<code>\@array</code> : Check for hmode to see if	1999-02-24 ltoutenc.dtx v1.9t
something went wrong during	General: Corrected hackery cyrillic
parsing (pr/2884) . . . . . 347	uc/lc list . . . . . 142
1999-01-05 fontdef.dtx v2.2x	1999-03-01 ltdefns.dtx v1.3e
General: Need special protection	<code>\@ifnextchar</code> : remove extra
for character > in <code>\changes</code>	<code>\long</code> . internal/2967 . . . . . 50
entry. . . . . 243	1999-04-15 ltpictur.dtx v1.1h
1999-01-06 ltffsbas.dtx v3.0w	<code>\@getlarrow</code> : Replaced octal
<code>\DeclareFontEncoding</code> : Added	number, CAR . . . . . 365
<code>\LastDeclaredEncoding</code> to	<code>\@upvector</code> : Replaced octal
support cyrillic integration	number, CAR . . . . . 366
(pr/2988) . . . . . 166	General: Replaced octal number,
<code>\LastDeclaredEncoding</code> : Added	CAR . . . . . 365, 366
<code>\LastDeclaredEncoding</code> to	Replaced octal numbers, CAR 357
support cyrillic integration	1999-04-19 ltfloat.dtx v1.1u
(pr/2988) . . . . . 166	<code>\caption</code> : Made caption an error
1999-01-06 ltoutenc.dtx v1.9r	outside a float: latex/2815 . . 399
<code>\@strip@args</code> : New impl for	1999-04-27 ltboxes.dtx v1.1f
latex/2930 . . . . . 111	<code>\@parboxto</code> : (CAR) Changed
General: Minor documentation	<code>\@empty</code> to <code>\relax</code> as flag for
fix. . . . . 130	natural width: pr/2975 . . . . 329
1999-01-06 ltoutput.dtx v1.2e	1999-04-29 ltdefns.dtx v1.3f
<code>\@makecol</code> : Added negative vskip,	<code>\@yargd@f</code> : Full expansion and
as when processing outputbox	conversion needed for digit in
below: suggested by Fred	new version, see pr/3013 . . . . 40
Bartlett pr/2892 . . . . . 447	New macro added . . . . . 40
1999-01-07 ltdefns.dtx v1.3a	1999-06-10 ltoutenc.dtx v1.9u
<code>\@ifnextchar</code> : made long . . . . . 50	General: Ensure that we also
<code>\@newenvb</code> : made long and brace	forget old options (pr/2888) . 144
optional arg. latex/2896 . . . . 42	1999-06-12 ltoutenc.dtx v1.9v
<code>\@testopt</code> : made long and brace	General: Extend <code>\@uclclist</code> only
optional arg. latex/2896 . . . . 39	once . . . . . 143

1999-10-09 ltmath.dtx v1.1e		<code>\markright</code> : Reimplementation to fix expansion error (pr/3203). 422
<code>\active@math@prime</code> : Macro added, see PR 3104. . . . . 299		<code>\rightmark</code> : Use <code>\@empty</code> instead of brace group (pr/3203). . . 423
<code>\prime@s</code> : Introduce <code>\active@math@prime</code> . . . . . 299		2000-06-02 ltpage.dtx v1.0k
1999-10-09 ltoutput.dtx 1.2f		<code>\@markright</code> : Small adjustment to give slightly less expansion, CAR . . . . . 423
<code>\activechar@info</code> : Reset definition of active prime character (used in math mode) . . . . . 451		<code>\markright</code> : Small adjustment to give slightly less expansion, CAR . . . . . 422
1999-10-28 ltoutenc.dtx v1.9w		Tidied 1.0j reimplementation, CAR . . . . . 422
<code>\add@accent</code> : Give <code>\accent@spacefactor</code> a default definition (pr/3084) . 109		2000-07-11 ltmiscen.dtx v1.1j
1999-12-08 ltoutenc.dtx v1.9x		<code>\enddocument</code> : Fix typo in warning . . . . . 281
General: Changed <code>\CYRRHOOK</code> and <code>\cyrrhook</code> to <code>\CYRRHK</code> and <code>\cyrrhk</code> as name changed in the cyrillic bundle for naming consistency with other “hook” glyphs. . . . . 142		2000-07-12 ltoutput.dtx 1.2g
2000-01-07 ltmiscen.dtx v1.1h		General: Ensure that rule is in <code>\normalcolor</code> . . . . . 490
<code>\@verbatim</code> : Disable hyphenation even if the font allows it. . . . 290		2000-07-12 ltoutput.dtx 1.2i
2000-01-15 ltpictur.dtx v1.1i		<code>\@makecol</code> : Removed negative vskip, as it gives unacceptable results when the depth is large: pr/3189 . . . . . 447
<code>\@upvector</code> : Removed space at end-of-line, CAR . . . . . 366		2000-07-19 ltoutput.dtx v1.2h
2000-01-30 ltfntcmd.dtx v3.3y		<code>\@writesetup</code> : Reset and restore <code>\@if@newlist</code> for internal/3231 . . . . . 452
<code>\DeclareTextFontCommand</code> : Use <code>\hmode@bgroup</code> now (pr/3160) 268		2000-08-23 ltfinal.dtx v1.1c
2000-01-30 ltoutenc.dtx v1.9y		General: Fix typo in warning . . . 561
General: Use <code>\hmode@bgroup</code> where applicable (pr/3160) 118–120, 125–128, 130		2000-08-30 ltoutenc.dtx v1.91
<code>\add@accent</code> : Use <code>\hmode@bgroup</code> where applicable (pr/3160) . 108		<code>\@use@text@encoding</code> : Rearranged but no change to final code, CAR (pr/3160) . . . . . 111
<code>\hmode@bgroup</code> : Macro added . . . 109		<code>\add@accent</code> : Rearranged but no change to final code, CAR (pr/3160) . . . . . 108
2000-01-30 ltoutenc.dtx v1.9z		2000-09-01 ltfinal.dtx v1.1d
<code>\@use@text@encoding</code> : Macro reimplemented (pr/3160) . . . 111		<code>\errhelp</code> : Set error help empty at very end (pr/449 done correctly). . . . . 568
<code>\add@accent</code> : Macro reimplemented (pr/3160) . . . 108		2000-09-24 ltfloat.dtx v1.2b
<code>\hmode@start@before@group</code> : Macro added (pr/3160) . . . . 112		<code>\end@dblfloat</code> : FMI: use output routine to defer float . . . . . 404
2000-05-19 ltmiscen.dtx v1.1i		2000-09-24 ltoutput.dtx v1.2b
<code>\enddocument</code> : Reset <code>\AtEndDocument</code> for latex/3060 . . . . . 280		<code>\@doclearpage</code> : FMI: ensure <code>\doclearpage</code> is called again until all floats are output. . . 445
2000-05-26 ltpage.dtx v1.0j		2000-09-24 ltoutput.dtx v1.2n
<code>\@markright</code> : Reimplementation to fix expansion error (pr/3203). 423		<code>\@addtocurcol</code> : FMI: test for wide float was in wrong place . . . 463
<code>\leftmark</code> : Use <code>\@empty</code> instead of brace group (pr/3203). . . . . 423		2001-01-07 ltoutput.dtx v1.2j
		<code>\@writesetup</code> : And do it in the right macro (pr/3286) . . . . . 452

2001-02-16 ltxref.dtx v1.1k	Added default for <code>\textbardbl</code> (pr/3400) . . . . .	115
<code>\@newl@bel</code> : Added an extra grouplevel (PR3250), jlb . . .	277	
2001-05-25 ltclass.dtx v1.1d		
<code>\@providesfile</code> : Explicitly set catcode of <code>\endlinechar</code> to 10 (pr/3334) . . . . .	504	
2001-05-25 ltdirchk.dtx v1.0x		
General: Explicitly set catcode of <code>\endlinechar</code> to 10 (pr/3334) .	4	
2001-05-28 ltoutenc.dtx v1.93		
General: Added composites for compatibility with T1, pr/3295 . . . . .	119	
Changed the effect of <code>\.i</code> , pr/3295 . . . . .	122	
2001-06-02 fontdef.dtx v2.2y		
General: Provide default cfg files (pr/3264) . . . . .	261	
2001-06-04 fontdef.dtx v2.2z		
General: Guard against math active equal and pipe sign in <code>\models</code> (pr/3333) . . . . .	257	
Guard against math active equal sign in <code>\Relbar</code> (pr/3333) . .	257	
2001-06-04 ltclass.dtx v1.1e		
<code>\@providesfile</code> : But only if it is a char (pr/3334) . . . . .	504	
2001-06-04 ltdirchk.dtx v1.0y		
General: But only if it is a char (pr/3334) . . . . .	4	
2001-06-04 ltpictur.dtx v1.1j		
<code>\@sline</code> : Don't warn for exactly zero pr/3318 . . . . .	364	
2001-06-04 ltvers.dtx v1.0i		
General: Check for old format disabled . . . . .	33	
2001-06-05 ltoutenc.dtx v1.94		
General: Text composite Commands need kludges for ‘,’ – see tlb1903.lvt . . . . .	119	
2001-08-26 ltclass.dtx v1.1f		
<code>\@providesfile</code> : Readded setting of space char (pr/3353) . . . .	504	
2002-02-24 ltplain.dtx v1.1x		
<code>\loggingall</code> : Macro added . . . .	30	
<code>\loggingoutput</code> : Macro added . .	30	
<code>\showoutput</code> : Use newly added <code>\loggingoutput</code> . . . . .	30	
<code>\tracingall</code> : Use newly added <code>\loggingoutput</code> . . . . .	30	
2002-06-16 ltoutenc.dtx v1.95		
General: Added <code>\textbardbl</code> (pr/3400) . . . . .	125	
2002-06-17 ltoutenc.dtx v1.95		
General: Corrected <code>\c</code> for T1 (pr/3442) . . . . .	120	
Definition of <code>\textexclamdown</code> changed (pr/3368) . . . . .	118	
Definition of <code>\textquestiondown</code> changed (pr/3368) . . . . .	118	
2002-06-18 ltoutenc.dtx v1.95		
General: Changed def for <code>\textregistered</code> to avoid small caps (pr/3420) . . . . .	116	
2002-10-01 ltfloat.dtx v1.1v		
<code>\thempfootnote</code> : Use braces around <code>\itshape</code> to keep font change local (pr/3460). . . . .	412	
2002-10-02 ltffsbas.dtx v3.0x		
<code>\DeclareFontSubstitution</code> : Adding <code>\LastDeclaredEncoding</code> introduced a bug as on some occasions that macro name was stored in the internal lists instead of the actual encoding. (pr/3459) . . . . .	166	
2002-10-28 ltlists.dtx v1.0s		
<code>\endtrivlist</code> : Check for math mode (pr/3437) . . . . .	316	
2002-10-28 ltoutenc.dtx v1.96		
General: coding change, to follow bug fix by DEK in plain.tex (pr/3469) . . . . .	119, 127	
2002-12-13 ltbibl.dtx v1.1n		
<code>\@citex</code> : Added <code>\leavevmode</code> in case citation is at start of paragraph (pr/3486) . . . . .	418	
2003-01-01 ltfntcmd.dtx v3.3z		
General: Code checked and documentation extended by Chris . . . . .	268	
2003-05-18 ltbibl.dtx v1.1o		
<code>\nocite</code> : Check if we are after <code>\document</code> . . . . .	419	
2003-08-27 ltpictur.dtx v1.1k		
<code>\@bezier</code> : added missing displacement pr/3566 . . . . .	378	
<code>\@sline</code> : check for <code>\@linechar</code> being empty pr/3570 . . . . .	364	
2003-10-13 ltfinal.dtx v1.1e		
General: Added extra <code>\lccode</code> for <code>\-</code> and <code>\textcompwordmark</code> .	560	



2003-12-16 ltoutput.dtx v1.2k	2004-02-13 ltoutenc.dtx v1.99e
\@makecol: Ensure that \@elt has	General: Documentation fixes:
a defined state (pr/3586) . . . 448	typos . . . . . 102
2003-12-30 ltpictur.dtx v1.1j	2004-02-15 ltbibl.dtx v1.1q
\@getcirc: issue warning if circle	\@cite@ofmt: Added hook with
size can't be met pr/3473 . . 373	default value \hbox . . . . . 420
2004-01-03 ltoutenc.dtx v1.99b	\@citex: Changed to use a hook
General: Added	with default value \hbox . . . 419
\textogonekcentered	2004-02-15 ltspace.dtx v1.3a
(pr/3532) . . . . . 120	\nobreakdashes: (Added
Added composites for \k	spacefactor setting . . . . . 84
(pr/3532) . . . . . 125	2004-10-20 ltoutput.dtx v1.2m
Use \ooalign for \k (pr/3532) 120	\@makecol: Removed dead code . 447
2004-01-04 ltbibl.dtx v1.1p	2005-07-27 ltfssdcl.dtx v3.0j
\nocite: Changed error message 419	\DeclareMathAlphabet: (MH)
2004-01-04 ltoutenc.dtx v1.99c	Make document commands
General: More adjustments for	robust . . . . . 221
ogonek (pr/3532) . . . . . 120	\DeclareSymbolFontAlphabet:
2004-01-23 ltdefns.dtx v1.1g	(MH) Make document
\@newenva: Use kernel version of	commands robust . . . . . 234
\@ifnextchar (pr/3501) . . . . 42	\new@mathalphabet: (MH) Make
\@testopt: Use kernel version of	document commands robust 222
\@ifnextchar (pr/3501) . . . . 40	\non@alpherr: (MH) Change
\@xargdef: Use kernel version of	because command is now
\@ifnextchar (pr/3501) . . . . 39	properly robust . . . . . 215
\@xdblarg: Use kernel version of	\SetMathAlphabet: (MH) Make
\@ifnextchar (pr/3501) . . . . 51	document commands robust 223
2004-01-23 ltdefns.dtx v1.3g	2005-09-27 ltoutenc.dtx v1.99g
\kernel@ifnextchar: Added	General: Replace \sh@ft by
macro (pr/3501) . . . . . 50	\ltx@sh@ft . . . . . 118, 120, 126
2004-01-28 ltclass.dtx v1.1g	2005-09-27 ltplain.dtx v1.1y
\@providesfile: Use kernel	\ltx@sh@ft: New macro . . . . . 29
version of \@ifnextchar	\sh@ft: Macro no longer used but
(pr/3501) . . . . . 504	left for compatibility . . . . . 29
2004-01-28 ltvers.dtx v1.0k	2005-11-08 ltoutenc.dtx v1.99h
General: Check for old format	General: Added \ij and \IJ from
made 5 years (pr/3601) . . . . 33	babel. (pr/3771) . . 114, 119, 121
2004-02-02 fontdef.dtx v2.3	2005-11-10 ltmath.dtx v1.1g
General: Many things from here on	\[: (MH) Fixed potential problem
made robust . . . . . 256	in \[ (pr/3399). . . . . 300
2004-02-02 ltoutenc.dtx v1.99	General: (MH) Minor
General: Added \textbigcircle 125	documentation fixes. . . . . 294
2004-02-04 fontdef.dtx v2.3a	2006-05-18 ltboxes.dtx v1.1g
General: Added bigtriangle	\@parboxto: Ensure \@parboxto
synonyms for stmaryrd . . . . 254	holds the value of \@tempdimb
2004-02-04 ltspace.dtx v1.3	not the register itself
\nobreakdashes: (Macro added . 84	(pr/3867) . . . . . 329
2004-02-06 ltoutenc.dtx v1.99d	2006-09-13 ltoutput.dtx v1.1m
\@inmathwarn: New command	General: Ensure that rule is in
added to fix severe bug:	\normalcolor . . . . . 491
pr/3563 . . . . . 106	2007-08-05 ltclass.dtx v1.1h
2004-02-07 ltoutput.dtx v1.2l	\@fileswithoptions: Prevent loss
\@docclearpage: Empty kludgeins	of brackets PR/3965 . . . 509, 510
box if necessary, pr/3528 . . . 446	

2007-08-06 ltcntrl.dtx v1.0h		provide as package . . . . .	481
\@fornoop: Really make defs long	58	2014-04-27 ltfloat.dtx v1.2b	
2007-08-31 ltfssdcl.dtx v3.0l		\end@dblfloat: Inline the code to	
\SetSymbolFont@: Font warning		allow some coexistence with	
changed to info for encoding		packages that hook into	
change (pr/3975) . . . . .	220	\end@float and do not know	
2009-09-24 ltvers.dtx v1.0l		about the algorithm change .	404
General: Stop checking for old		2014-06-10 ltfloat.dtx v1.2b	
format . . . . .	33	\end@dblfloat: missing \fi	
2009-10-20 ltfssdcl.dtx v3.0m		added . . . . .	404
\in@: More robust thanks to		2014-12-30 ltfinal.dtx v2.0a	
Heiko. . . . .	211	\newmarks: macro added . . . . .	555
2009-10-28 ltoutenc.dtx v1.99k		\newXeTeXintercharclass: macro	
General: Added Latin Modern and		added . . . . .	555
TeX Gyre subsets . . . . .	153	2014-12-30 ltfloat.dtx v1.2a	
2009-11-04 ltoutenc.dtx v1.99l		\@textsubscript: Command	
General: Added more Latin		added (latexrelease) . . . . .	413
Modern and TeX Gyre subsets	153	\textsubscript: Command added	
2009-12-14 ltfntcmd.dtx v3.4a		(latexrelease) . . . . .	413
\ifmaybe@ic: Macro added . . . .	270	2014-12-30 ltfssbas.dtx v3.0y	
\maybe@ic@: Use switch		\mathgroup: move allocation to	
\ifmaybe@ic instead of		ltplain. . . . .	163
\if@tempswa . . . . .	270	2014-12-30 ltoutput.dtx v1.2m	
\t@st@ic: Use switch \ifmaybe@ic		General: Command updated	
instead of \if@tempswa . . . .	271	(latexrelease) . . . . .	490
2010-08-17 ltmiscen.dtx v1.1k		2014-12-30 ltplain.dtx v2.0a	
\enddocument: Use braces around		\e@alloc: macro added . . . . .	20
\input arg (pr/4124) . . . . .	281	\e@alloc@chardef: macro added	19
2010-08-17 ltmiscen.dtx v1.1l		\e@alloc@top: macro added . . . .	19
\enddocument: Change of plan: use		\e@ch@ck: macro added . . . . .	20
\@@input instead (pr/4124) .	281	\extrafloats: macro added . . . .	20
2011-05-08 ltfssdcl.dtx v3.0n		\newlanguage: New engine-specific	
\in@: Simplified thanks to Bruno.	211	allocation scheme	
2011-08-19 ltclass.dtx v1.1i		(latexrelease) . . . . .	18
\@ifclasswith: Re-jig definition		2014-12-30 ltspac.dtx v1.3b	
after more stringent \in@ test.	503	\@: \@ discards spaces when	
2011-09-03 ltfssdcl.dtx v3.0o		moving (pr3039)(latexrelease)	85
\new@mathversion: (Will) Remove		2015-01-03 ltdefs.dtx v1.4a	
\global before \newcount		\typein: use modified definition in	
(unnecessary and caused etex		luatex . . . . .	38
bug). . . . .	218	2015-01-03 ltdirchk.dtx v1.1	
2012-01-20 ltplain.dtx v2.0b		General: Enable extra primitives	
\loggingall: etex tracing if		when LuaTeX is used . . . . .	3
available . . . . .	30	2015-01-03 ltfinal.dtx v2.0a	
2013-07-07 ltclass.dtx v1.1i		General: Skip resetting codes with	
General: Correctly describe how		Unicode engines . . . . .	565
the date in \@ifpackagelater		Unicode data loading added . .	557
is used . . . . .	499	2015-01-07 ltvers.dtx v1.0n	
2014-04-18 ltoutput.dtx v1.1o		\IncludeInRelease: macro added	34
General: Handle infinite glue from		2015-01-08 ltboxes.dtx v1.1h	
\enlargethispage (pr/4023)	491	\framebox: Make Robust	
2014-04-24 ltoutput.dtx v1.2n		(latexrelease) . . . . .	327
\fl@tracemessage: Renamed		\makebox: Make Robust	
internal trace commands;		(latexrelease) . . . . .	323



<code>\parbox</code> : Make Robust (latexrelease) . . . . .	328	2015-01-14 ltoutput.dtx v1.2n <code>\@addtocurcol</code> : float order in 2-column (latexrelease) . . . .	462
<code>\raisebox</code> : Make Robust (latexrelease) . . . . .	333	<code>\@addtodblcol</code> : float order in 2-column (latexrelease) . . . .	473
<code>\rule</code> : Make Robust (latexrelease) . . . . .	332	<code>\@addtonextcol</code> : float order in 2-column (latexrelease) . . . .	469
<code>\savebox</code> : Make Robust (latexrelease) . . . . .	325	<code>\@docclearpage</code> : Empty kludgeins box if necessary, pr/3528 . . .	445
2015-01-08 ltdefns.dtx v1.4a <code>\MakeRobust</code> : Added macro . . . .	47	float order in 2-column (latexrelease) . . . . .	445
2015-01-08 ltlength.dtx v1.1c <code>\setlength</code> : to ensure first length argument is terminated. (latexrelease) . . . . .	162	<code>\@startdblcolumn</code> : float order in 2-column (latexrelease) . . . .	457
2015-01-08 ltmath.dtx v1.1h <code>\)</code> : Make Robust (latexrelease) . .	300	<code>\@xtryfc</code> : float order in 2-column (latexrelease) . . . . .	459
<code>\]</code> : Make Robust (latexrelease) . .	300	<code>\@ztryfc</code> : float order in 2-column (latexrelease) . . . . .	460
2015-01-09 ltfssini.dtx v3.1a <code>\em</code> : Allow <code>\emph</code> to produce small caps (latexrelease) . . . . .	238	2015-01-14 ltspace.dtx v1.3e <code>\addpenalty</code> : Avoid adding redundant skips (DPC) . . . . .	82
<code>\emminnershape</code> : macro added (latexrelease) . . . . .	238	2015-01-17 ltvers.dtx v1.0m <code>\IncludeInRelease</code> : modified with <code>\currname</code> . . . . .	34
2015-01-09 ltspace.dtx v1.1h <code>\addpenalty</code> : Donald Arseneau's fix from PR/377703 (latexrelease) . . . . .	81	2015-01-19 ltvers.dtx v1.0o <code>\IncludeInRelease</code> : Optional argument . . . . .	34
2015-01-10 ltcounts.dtx v1.1h <code>\@fnsymbol</code> : Unse <code>\TextOrMath</code> (latexrelease) . . . . .	160	2015-01-20 ltoutput.dtx v1.2m <code>\fl@tracemessage</code> : Reset <code>\IncludeInRelease</code> flags . . .	482
<code>\@stpelt</code> : Reset all within counters in one go (latexrelease) . . . . .	157	2015-01-22 ltvers.dtx v1.0p General: Preserve any <code>\everyjob</code> material inserted by a loader (.ini file) . . . . .	34
2015-01-11 ltcounts.dtx v1.1h <code>\TextOrMath</code> : Add command to solve robustness issues (pr/3752) (latexrelease) . . . .	160	2015-01-23 ltfinal.dtx v2.0b <code>\newmarks</code> : use reserved count 256	555
2015-01-11 ltfloat.dtx v1.2b <code>\@dblfloatplacement</code> : float order in 2-column (latexrelease) . .	405	<code>\newXeTeXintercharclass</code> : use reserved count 257 . . . . .	555
<code>\@xfloat</code> : Check for valid option (latexrelease) . . . . .	400	2015-01-23 ltplain.dtx v2.0c <code>\extrafloats</code> : reserve counts 256–265 . . . . .	20
<code>\end@dblfloat</code> : float order in 2-column (latexrelease) . . . .	404	2015-01-24 ltfinal.dtx v2.0c General: Skip T1-code entirely with Unicode engines . . . . .	557
2015-01-11 ltfssbas.dtx v3.0y <code>\@DeclareMathSizes</code> : Allow arbitrary units (latexrelease)	168	2015-02-03 ltfinal.dtx v2.0d General: Set <code>\lccode</code> for – with Unicode engines . . . . .	558
2015-01-11 ltspace.dtx v1.3d <code>\@Esphack</code> : Allow hyphenation (Donald Arseneau pr/3498) (latexrelease) . . . . .	79	2015-02-16 ltoutenc.dtx v1.99m General: Added <code>\textcommabelow</code> latex/4414 . . . . .	116
<code>\@esphack</code> : Allow hyphenation (Donald Arseneau pr/3498) (latexrelease) . . . . .	78	Added lmtt (Heiko Oberdiek) latex/4415 . . . . .	153
		2015-02-16 ltoutenc.dtx v1.99n General: Added <code>\textcommaabove</code> Added composites for ç . . . .	117 125

Added composites for <code>\c</code> . . . . .	119	2015-03-10 <code>ltplain.dtx</code> v2.0g	
2015-02-19 <code>ltvers.dtx</code> v1.0q		<code>\hideoutput</code> : macro added . . . . .	31
<code>\IncludeInRelease</code> : Swap		<code>\loggingall</code> : Reorganise to be less	
argument order . . . . .	34	noisy . . . . .	30
2015-02-20 <code>ltplain.dtx</code> v2.0d		<code>\tracingnone</code> : macro added . . . . .	31
<code>\loggingall</code> : Spell commands		2015-03-12 <code>ltoutput.dtx</code> v1.2m	
correctly :-). . . . .	30	General: initialise <code>\@dbldeferlist</code>	
2015-02-21 <code>ltdefns.dtx</code> v1.4b		again . . . . .	436
General: Removed autoload		2015-03-18 <code>ltfssdcl.dtx</code> v3.0q	
support . . . . .	36	<code>\DeclareSymbolFont</code> : Restrict	
2015-02-21 <code>lterror.dtx</code> v1.2o		Symbol fonts to 0-15 . . . . .	219
General: Removed autoload		<code>\document@select@group</code> :	
support . . . . .	60	Introduce <code>\e@mathgroup@top</code> . . . . .	215
2015-02-21 <code>ltfiles.dtx</code> v1.1m		<code>\select@group</code> : Introduce	
General: Removed autoload		<code>\e@mathgroup@top</code> . . . . .	213
support . . . . .	88	2015-03-26 <code>ltfinal.dtx</code> v2.0d	
2015-02-21 <code>ltfssbas.dtx</code> v3.0z		General: Use renamed	
General: Removed autoload code . . . . .	163	<code>unicode-letters.def</code> . . . . .	557
2015-02-21 <code>ltfsscmp.dtx</code> v3.0d		2015-04-07 <code>ltfssbas.dtx</code> v3.1a	
General: Removed autoload code . . . . .	207	<code>\wrong@fontshape</code> : Try loading <code>fd</code>	
2015-02-21 <code>ltfssdcl.dtx</code> v3.0p		file if family has changed . . . . .	177
General: Removed autoload code . . . . .	211	2015-04-28 <code>ltfinal.dtx</code> v2.0f	
2015-02-21 <code>ltfssstrc.dtx</code> v3.0k		<code>\newXeTeXintercharclass</code> : define	
General: Removed autoload code . . . . .	185	<code>\xe@alloc@intercharclass</code> for	
2015-02-21 <code>ltoutenc.dtx</code> v1.99m		compatibility with older	
General: Removed autoload code . . . . .	102	xelatex initialisation . . . . .	555
2015-02-21 <code>ltoutput.dtx</code> v1.2n		2015-05-10 <code>ltlists.dtx</code> v1.0t	
General: Removed autoload code . . . . .	424	<code>\@doendpe</code> : Explicitly reset	
<code>\f@depth</code> : macro		<code>\clubpenalty</code> before clearing	
added( <code>latexrelease</code> ) . . . . .	444	<code>\everypar</code> ; see also <code>pr/0462</code>	
2015-02-21 <code>ltpictur.dtx</code> v1.1k		and <code>pr/4065</code> . . . . .	317
General: Removed autoload code . . . . .	357	2015-06-19 <code>ltfinal.dtx</code> v2.0g	
2015-02-21 <code>ltplain.dtx</code> v2.0e		<code>\e@alloc@intercharclass@top</code> :	
General: Removed autoload code . . . . .	15	Use <code>-1</code> for first range to get	
2015-02-21 <code>lftab.dtx</code> v1.1n		contiguous allocation . . . . .	555
General: Removed autoload code . . . . .	335	<code>\newmarks</code> : Use <code>-1</code> for first range	
2015-02-21 <code>ltvers.dtx</code> v1.0r		to get contiguous allocation . . . . .	555
General: Removed autoload code . . . . .	33	2015-06-19 <code>ltplain.dtx</code> v2.0h	
2015-02-21 <code>ltvers.dtx</code> v1.0w		General: delete spurious old	
<code>\IncludeInRelease</code> : set		definition of <code>\newtoks</code> . . . . .	23
<code>\@currname</code> empty here (in		<code>\e@alloc</code> : extra braces in case	
case <code>\IncludeInRelease</code> input		arguments not single token . . . . .	20
early) . . . . .	34	<code>\newlanguage</code> : Use <code>-1</code> for first	
2015-02-22 <code>ltfsscmp.dtx</code> v3.0e		range to get contiguous	
General: Moved all code into		allocation . . . . .	18
<code>latexrelease</code> - obsolete		2015-06-23 <code>ltfinal.dtx</code> v2.0h	
commands are no longer		General: set <code>\patch@level</code> in	
automatically part of the		<code>ltvers</code> rather than in	
kernel . . . . .	207	<code>ltfinal/ltpatch</code> . . . . .	567
2015-03-02 <code>ltplain.dtx</code> v2.0f		2015-06-23 <code>ltvers.dtx</code> v1.0t	
<code>\e@mathgroup@top</code> : macro added . . . . .	19	General: set <code>\patch@level</code> in	
<code>\newlanguage</code> : allow 255 math		<code>ltvers</code> rather than in	
groups in Unicode engines . . . . .	18	<code>ltfinal/ltpatch</code> . . . . .	33

2015-08-06 ltplain.dtx v2.0i	2015-10-02 ltluatex.dtx v1.0b
<code>\extrafloats</code> : Add <code>\string</code> in	General: Fix backing out of $\TeX$
case argument is not an	code ..... 540
unexpandable primitive ..... 21	2015-10-02 ltluatex.dtx v1.0c
2015-08-23 ltdirchk.dtx v1.2	General: Allow backing out of Lua
General: Do not use luatex prefix . 3	code ..... 540
2015-08-23 ltvers.dtx v1.0v	2015-10-02 ltluatex.dtx v1.0e
General: Allow negative patchlevel	<code>uninstall</code> : Function added .... 554
for pre-release ..... 34	2015-10-03 ltluatex.dtx v1.0f
2015-08-30 ltplain.dtx v2.1a	<code>provides_module</code> : use
<code>\newinsert</code> : new <code>\newinsert</code>	<code>luatexbase_log</code> ..... 541
implementation ..... 22	2015-10-27 ltplain.dtx v2.1b
2015-09-205 ltoutput.dtx v1.3a	<code>\extrafloats</code> : Use global
General: extended <code>\@freelist</code> .. 435	assignment when switching to
2015-09-24 ltluatex.dtx v1.0a	extended range ..... 20
<code>call_callback</code> : Function added . 551	2015-11-07 ltspc.dtx v1.3f
<code>callback_register</code> : Function	<code>\@esphack</code> : Only space if there is
modified ..... 548	no space at the end of the hlist
<code>callback_descriptions</code> : Function	<code>latex/4443</code> ..... 78
added ..... 553	2015-11-14 ltluatex.dtx v1.0g
<code>\catcodetable@atletter</code> : Macro	General: Track Lua $\TeX$ changes
added ..... 537	for <code>(new)token.create</code> .... 543
<code>\catcodetable@initex</code> : Macro	2015-11-18 ltplain.dtx v2.2a
added ..... 537	<code>\newlanguage</code> : Extended stream
<code>\catcodetable@latex</code> : Macro	allocation in luatex (0.85) ... 18
added ..... 537	2015-11-19 ltplain.dtx v2.2b
<code>\catcodetable@string</code> : Macro	<code>\newlanguage</code> : Only extend
added ..... 537	allocation of write streams (see
<code>add_to_callback</code> : Function	luatex list) ..... 18
added ..... 551	2015-11-27 ltluatex.dtx v1.0h
<code>remove_from_callback</code> : Function	<code>callback_descriptions</code> : Match
added ..... 552	test in in-callback <code>latex/4445</code> 553
<code>new_attribute</code> : Function added . 544	<code>in_callback</code> : Guard against
<code>disable_callback</code> : Function	undefined list <code>latex/4445</code> ... 553
added ..... 553	2015-11-29 ltluatex.dtx v1.0i
<code>in_callback</code> : Function added ... 553	General: Declare this as local
<code>\newattribute</code> : Macro added ... 536	before used in the module error
<code>\newcatcodetable</code> : Macro added 536	definitions (PHG) ..... 541
<code>\newluabytecode</code> : Macro added . 539	<code>call_callback</code> : Check name is not
<code>\newluachunkname</code> : Macro added 539	nil in error message (PHG) . 551
<code>\newluafunction</code> : Macro added . 538	<code>create_callback</code> : Check name is
<code>\newwhatsit</code> : Macro added .... 539	not nil in error message
<code>module_error</code> : Function added .. 542	(PHG) ..... 550
<code>module_info</code> : Function added ... 542	2015-12-02 ltluatex.dtx v1.0j
<code>module_warning</code> : Function added 542	General: Adjust hashtokens to
<code>modules</code> : Function modified .... 541	store the result of
<code>create_callback</code> : Function	<code>tex.hashtokens()</code> ), not the
added ..... 550	function (PHG) ..... 543
<code>provides_module</code> : Function	Assorted typos fixed (PHG) .. 534
added ..... 541	Declaration/use of <code>first.head</code>
<code>luatexbase</code> : Table added ..... 541	fixed (PHG) ..... 542
2015-10-02 ltdirchk.dtx v1.2a	Remove nonlocal iteration
General: Allow backing out of	variables (PHG) ..... 534
unprefixed names ..... 3	

Remove unreachable code after calls to error() (PHG) . . . . .	534	2016-02-18 ltffssdcl.dtx v3.0r	
2015-12-02 ltluatex.dtx v1.0k		<code>\@DeclareMathDelimiter</code> : Check for delimiter not <code>\delimiter</code> . . . . .	229
General: resolve name and i.description (PHG) . . . . .	549	<code>\DeclareMathAccent</code> : Check for mathaccent not <code>\mathaccemt</code> . . . . .	225
<code>call_callback</code> : Give more specific error messages (PHG) . . . . .	551	<code>\DeclareMathRadical</code> : Check for radical not <code>\radical</code> . . . . .	233
<code>add_to_callback</code> : Give more specific error messages (PHG) . . . . .	551	<code>\DeclareMathSymbol</code> : Check for mathchar not <code>\mathchar</code> . . . . .	227
<code>remove_from_callback</code> : adjust initialisation of cb local (PHG) . . . . .	552	2016-03-13 ltluatex.dtx v1.0n	
Give more specific error messages (PHG) . . . . .	552	General: contribute.filter added . . . . .	547
<code>create_callback</code> : Give more specific error messages (PHG) . . . . .	550	<code>insert_local_par</code> added . . . . .	547
2015-12-10 ltfinal.dtx v2.0i		2016-03-29 ltpictur.dtx v1.1l	
General: Use new common Unicode data loaders . . . . .	557	<code>\@oval</code> : add setting of line tests . . . . .	374
2015-12-18 ltluatex.dtx v1.0l		initialise tests . . . . .	374
General: Load Unicode data from source . . . . .	537	<code>\@ovhorz</code> : use glue not leaders if horizontal line not required . . . . .	374
2016-01-04 ltfinal.dtx v2.0j		<code>\@ovvert</code> : use glue not leaders if vertical line not required . . . . .	374
General: Do not set up inter character classes for XeTeX . . . . .	557	<code>\if@ovhline</code> : macro added (latex/4452) . . . . .	373
<code>\e@alloc@intercharclass@top</code> : Start allocation at one not three . . . . .	555	<code>\if@ovvline</code> : macro added (latex/4452) . . . . .	373
2016-01-05 ltfinal.dtx v2.0k		2016-04-22 ltfinal.dtx v2.0q	
<code>\e@alloc@intercharclass@top</code> : Remove duplicated code . . . . .	555	<code>\e@alloc@intercharclass@top</code> : XeTeX 0.99996 has 4096 char classes not 256 . . . . .	555
2016-01-05 ltfinal.dtx v2.0l		2016-06-19 ltoutenc.dtx v1.99m	
General: Correct latexrelease guards . . . . .	557	General: OT1 definition (was duplicate T1 definition) . . . . .	119
Ensure old definitions for inter-character class toks are available using latexrelease . . . . .	557	2016-06-20 ltclass.dtx v1.1j	
Missing brace . . . . .	557	<code>\@ifclasslater</code> : don't declare as <code>\@onlypreamble</code> . . . . .	502
2016-01-05 ltfinal.dtx v2.0m		2016-07-29 ltplain.dtx v2.2c	
General: Undefine XeTeX classes when using patching an older kernel . . . . .	557	<code>\extrafloats</code> : use <code>\global</code> <code>\chardef</code> . . . . .	21
2016-01-05 ltfinal.dtx v2.0p		<code>\newinsert</code> : fix for tlb-newinsert-001 . . . . .	22
General: Only apply XeTeX change if XeTeX is in use . . . . .	557	2016-10-02 ltclass.dtx v1.2a	
2016-02-11 ltluatex.dtx v1.0m		<code>\@ifclasswith</code> : Ignore spaces while checking for option clash . . . . .	503
General: pdf_stream_filter_callback removed . . . . .	548	<code>\ExecuteOptions</code> : Ignore spaces in argument . . . . .	507
process_rule, [hv]pack_quality append_to_vlist_filter added . . . . .	547	2016-10-15 ltdirchk.dtx v1.2b	
read_cidmap_file added . . . . .	547	General: Require eTeX . . . . .	4
show_warning_message added . . . . .	548	2016-10-15 lterror.dtx v1.2p	
token_filter removed . . . . .	547	General: Require eTeX . . . . .	60
		2016-10-15 ltfinal.dtx v2.0r	
		General: Require eTeX . . . . .	555
		2016-10-15 ltfinal.dtx v2.0s	
		General: Tidy up status of char 127 . . . . .	555
		2016-10-15 ltffssini.dtx v3.1b	
		General: Require eTeX . . . . .	237

2016-10-15 ltplain.dtx v2.2d			
General: Require eTeX	15	<code>new_chunkname</code> : Parameterise	
2016-10-16 ltplain.dtx v2.3a		count used in tracking	545
<code>\newlanguage</code> : Allow languages up		<code>new_whatshit</code> : Parameterise count	
to 16383 in luatex	18	used in tracking	544
2016-10-19 ltcounts.dtx v1.1j		2017-02-19 ltoutenc.dtx v2.0f	
<code>\TextOrMath</code> : Test directly for		General: add <code>\@empty</code> to guard	
<code>\protected</code>	160	against 3rd argument being	
2016-11-06 ltplain.dtx v2.3b		empty	119
General: Drop <code>\outer</code> entirely	15	declare composites with empty	
2016-11-09 ltclass.dtx v2.1b		base for hat and tilde, use same	
<code>\@fileswithoptions</code> : Improve		slots for <code>\textasciicircum</code> ans	
<code>\ifx</code> tests PR/4497	510	<code>\textasciitilde</code>	132
2016-11-17 ltluatex.dtx v1.0p		declare straight quotes using	
General: <code>calledit</code> added	548	new <code>\remove@tlig</code> command	132
2016-12-03 fontdef.dtx v3.0a		2017-02-22 ltoutenc.dtx v2.0g	
General: (DPC) Default to TU		General: Fix typo introduced at	
encoding for Unicode TeX		2.0f	132
engines	245	2017-02-24 ltoutenc.dtx v2.0h	
<code>\shapedefault</code> : (DPC) Default to		General: introduce	
TU encoding for Unicode TeX		<code>\DeclareUnicodeAccent</code>	132
engines	248	<code>\DeclareTextCompositeCommand</code> :	
2016-12-04 ltoutenc.dtx v2.0a		add check whether the accent	
General: Added TU encoding	132	command is defined for this	
2017-01-01 ltoutput.dtx v1.3b		encoding	109
General: make <code>fpmin</code> negative so		2017-03-08 ltclass.dtx v1.2c	
ignored even if float height is		<code>\@ifclasslater</code> : add	
negative	490	<code>\@parse@version@dash</code> to	
2017-01-10 ltssbas.dtx v3.2a		support yyyy-mm-dd as well as	
<code>\showhyphens</code> : Add version of		yyyy/mm/dd	502
<code>\showhyphens</code> that works with		2017-03-09 ltfinal.dtx v2.0t	
XeTeX.	181	<code>\l@nohyphenation</code> : ensure	
2017-01-23 ltoutenc.dtx v2.0b		<code>\l@nohyphenation</code> is defined.	560
General: Added TU specific		2017-03-09 ltmiscen.dtx v1.1m	
commands in ASCII range		<code>\@verbatim</code> : Use <code>\language</code> not	
pr/4500	132	<code>\hyphenchar</code>	290
2017-01-24 ltoutenc.dtx v2.0c		<code>\verb</code> : Use <code>\language</code> to stop	
General: Declare TU composites		hyphenation	292
for i and j	132	2017-03-10 ltfiles.dtx v1.1n	
Make <code>\textasteriskcentered</code>		<code>\document</code> : Save language default	91
U+2217 not U+204E	132	2017-03-10 ltoutput.dtx v1.3c	
TeX ligature syntax for xetex		<code>\@writsetup</code> : Reset <code>\language</code>	451
and luatex reversed	132	2017-03-13 ltdefs.dtx v1.5a	
2017-01-24 ltoutenc.dtx v2.0d		<code>\-:</code> : Define <code>\-</code> in terms of	
General: Declare macron		<code>\hyphenchar</code>	51
composites for <code>YyGg</code>	132	2017-03-27 ltdefs.dtx v1.5b	
2017-02-12 ltoutenc.dtx v2.0e		<code>\@dischyph</code> : Define <code>\@dischyph</code>	
General: Declare fallback code for		after <code>\-</code>	51
<code>\textasteriskcentered</code>	132	2017-03-28 ltluatex.dtx v1.1e	
2017-02-18 ltluatex.dtx v1.1c		General: <code>glyph_stream_provider</code>	
<code>new_attribute</code> : Parameterise		added	548
count used in tracking	544	2017-03-29 ltboxes.dtx v1.3a	
<code>new_bytecode</code> : Parameterise count		<code>\@arrayparboxrestore</code> : Reset	
used in tracking	545	<code>\lineskiplimit</code>	330

2017-04-05 ltoutenc.dtx v2.0i	2018-04-08 ltclass.dtx v1.2h
\DeclareTextCompositeCommand:	\@onefilewithoptions: Pass
Declare accent command if not	expanded date . . . . . 521
already declared when	2018-04-08 ltfinal.dtx v2.1d
declaring a composite. . . . . 109	General: Delay full UTF-8
2017-04-10 ltplain.dtx v2.3c	handling to \everyjob . . . . 562
\newlanguage: Correction to code	2018-04-11 ltcounts.dtx v1.1l
to skip write18 in luatex . . . . 18	\counterwithin: Correct default
2017-04-11 ltoutput.dtx v2.4a	(issue/38) . . . . . 158
\newpage: account for the depth of	2018-05-02 ltuatex.dtx v1.1g
the last row of the page . . . . 438	General: find_sfd_file removed . . . 547
2017-12-17 ltoutput.dtx v1.4b	finish_synctex_callback added . . 548
\@addtonextcol: fix doc guards . . 469	glyph_not_found added . . . . . 548
2018-01-06 ltdefs.dtx 1.5c	read_sfd_file removed . . . . . 547
\@ifundefined: Avoid defining	2018-05-08 ltclass.dtx v1.2i
undefined commands to \relax 49	\pkgcls@parse@date@arg: Make
2018-02-18 ltclass.dtx v1.2d	suspicious rollback a warning
\@ifclasslater: Added 0 up front	not error: github issue 43 . . 523
to make bad data come out as	2018-05-11 ltfinal.dtx v2.18
0. . . . . 502	General: Make invalid UTF-8 also
General: Introduce rollback	safe, for legacy filesystem
concept . . . . . 520	encodings . . . . . 562
2018-03-08 ltcounts.dtx v1.1k	2018-05-29 ltclass.dtx v1.2j
\@ifbothcounters: Interface	\endfilecontents: use \csname
added . . . . . 158	not \@undefined . . . . . 517
\@removefromreset: Interface	2018-08-11 ltoutenc.dtx v2.0j
added . . . . . 157	General: Provide \guillemetleft
\counterwithin: Interface added 158	and
\counterwithout: Interface	\guillemetright . . 121, 127, 135
added . . . . . 158	2018-08-18 ltuatex.dtx v1.1h
2018-03-24 ltclass.dtx v1.2e	General: append_to_vlist_filter is
\pkgcls@use@this@release: Use	exclusive . . . . . 547
full file name for old release . . 525	2018-08-24 ltfinal.dtx v2.1f
2018-03-25 ltfinal.dtx v2.1a	\document@default@language:
General: default to UTF-8 . . . . . 561	Add to latexrelease
\UseRawInputEncoding: Macro	(github/68) . . . . . 560
added . . . . . 562	2018-09-02 ltsect.dtx v1.1b
2018-03-27 ltclass.dtx v1.2f	\@dottedtocline: Prevent
\endfilecontents: Use full file	protrusion
name for old release . . . . . 516	( <a href="https://tex.stackexchange.com/q/172785/10109">https://tex.stackexchange.com/q/172785/10109</a> ) . . . . . 394
2018-04-06 ltfinal.dtx v2.1b	2018-09-24 fontdef.dtx v3.0b
\UseRawInputEncoding: Undo	General: Start LR-mode if
changes to	necessary (git/49) . . . . . 260
\DeclareFontEncoding@ and	2018-09-24 ltmath.dtx v1.2b
definition of	\smash: Start LR-mode if
\DeclareUnicodeCharacter . . 562	necessary (git/49) . . . . . 297
2018-04-07 ltfinal.dtx v2.1c	\vphantom: Start LR-mode if
\UseRawInputEncoding: Undefine	necessary (git/49) . . . . . 297
\inputencodingname . . . . . 562	2018-09-24 ltspace.dtx v1.3h
2018-04-08 ltclass.dtx v1.2g	\enspace: Start LR-mode if
\@ifclasslater: Strip leading	necessary (git/49) . . . . . 85
spaces from dates. . . . . 502	\leavevmode@ifvmode: Macro
	added (git/49) . . . . . 85



2018-09-26 ltdefs.dtx v1.5e	2018-11-09 ltbibl.dtx LaTeX2e
<code>\renewcommand</code> : Always explicitly	<code>\bibliography</code> : Zap spaces in the
generate a space after the	argument as BibTeX doesn't
cname and not rely on	support them (github/88) . . . 419
<code>\noexpand</code> to save tokens	2018-11-18 ltoutenc.dtx v2.0k
(git/41) . . . . . 41	General: Provide <code>\Hwithstroke</code>
2018-09-26 ltmiscen.dtx v1.1n	and <code>\hwithstroke</code> . . . . . 136
<code>\writefile</code> : Sometimes mask the	2018-11-19 ltoutenc.dtx v2.0k
endline char when writing to	General: Added <code>\Hwithstroke</code> and
files (github/73) . . . . . 283	<code>\hwithstroke</code> . . . . . 120
<code>\addpercent@to@temptokena</code> :	2018-11-28 ltoutput.dtx v1.4d
Sometimes mask the endline	<code>\@combinedblfloats</code> : Unbox
char when writing to files	<code>\@outputbox</code> to preserve
(github/73) . . . . . 282	boxing level (github/94) . . . 456
<code>\protected@file@percent</code> :	2018-12-30 lttab.dtx v1.1p
Sometimes mask the endline	<code>\@tabclassz</code> : Add extra <code>\hskip</code> to
char when writing to files	guard against an <code>\unskip</code> at
(github/73) . . . . . 282	the start of a c-column cell
2018-09-26 ltsect.dtx v1.1c	(gh/102) . . . . . 353
<code>\addcontentsline</code> : Sometimes	2019-02-07 ltfiles.dtx v1.1o
mask the endline char when	<code>\@swaptwoargs</code> : Helper macro
writing to files (github/73) . . 393	added . . . . . 98
2018-10-10 ltspace.dtx v1.3i	<code>\InputIfFileExists</code> : Expand
<code>\esphack</code> : Don't introduce	<code>\@filef@und</code> before executing
breakpoints if <code>@nobreak</code> is true	second argument (github/109) 98
and after sections . . . . . 78	2019-02-07 ltfssbas.dtx v3.2b
2018-10-11 ltmiscen.dtx v1.1o	<code>\define@newfont</code> : Changed
<code>\@setupverbvisiblespace</code> :	wording of warning
Provide visible space in <code>\verb*</code>	(github/107) . . . . . 174
also for XeTeX and LuaTeX	2019-06-18 ltluatex.dtx v1.1j
(github/69) . . . . . 291	General: finish_synctex_callback
<code>\@sverb</code> : Provide visible space in	renamed finish_synctex . . . . 548
<code>\verb*</code> also for XeTeX and	font_descriptor_objnum_provider
LuaTeX (github/69) . . . . . 291	added . . . . . 548
<code>\@verbvisiblespacebox</code> : Provide	make_extensible added . . . . . 548
visible space in <code>\verb*</code> also for	new_graf added . . . . . 547
XeTeX and LuaTeX	page_objnum_provider added . . 548
(github/69) . . . . . 291	process_pdf_image_content
<code>\asciispace</code> : Provide visible space	added . . . . . 548
in <code>\verb*</code> also for XeTeX and	wrapup_run added . . . . . 548
LuaTeX (github/69) . . . . . 290	2019-07-01 ltfiles.dtx v1.2a
<code>verbatim*</code> : Provide visible space	<code>\IfFileExists</code> : Support UTF-8 . . 97
in <code>\verb*</code> also for XeTeX and	<code>\includeonly</code> : Support UTF-8 . . 94
LuaTeX (github/69) . . . . . 292	<code>\set@curr@file</code> : Support UTF-8 96
<code>\verbvisiblespace</code> : Provide	2019-07-09 ltfssbas.dtx v3.2c
<code>\verbvisiblespace</code> such that	<code>\DeclareErrorFont</code> : Don't set any
it is usable in normal text	<code>\f@...</code> macros . . . . . 175
(github/70) . . . . . 290	2019-07-09 ltfssini.dtx v3.1c
Provide visible space in <code>\verb*</code>	General: Explicitly set some
also for XeTeX and LuaTeX	defaults . . . . . 241
(github/69) . . . . . 290	2019-08-22 ltxref.dtx v1.1l
2018-10-21 ltluatex.dtx v1.1i	<code>\labelformat</code> : Commanded moved
<code>new_luafunction</code> : Function	from <code>varioref.sty</code> . . . . . 278
added . . . . . 546	

<code>\Ref</code> : Commanded moved from <code>varioref.sty</code> . . . . .	278	2019-08-27 ltpage.dtx v1.0l General: Make various commands robust . . . . .	421
<code>\refstepcounter</code> : Allow <code>\p@...</code> to have an argument . . . . .	278	2019-08-27 ltpictur.dtx v1.1m General: Make various commands robust . . . . .	357
2019-08-27 fontdef.dtx v3.0c General: Various commands made robust throughout the file . .	254	Remove several unnecessary <code>\gdef</code> definitions . . . . .	357
2019-08-27 ltboxes.dtx v1.3b General: Various commands made robust . . . . .	322	2019-08-27 ltsect.dtx v1.1d General: Make various commands robust . . . . .	384
2019-08-27 ltdefns.dtx v1.5f General: Make various commands robust . . . . .	52	2019-08-27 ltspc.dtx v1.3j General: Make various commands robust . . . . .	71
<code>\MakeRobust</code> : Make the assignments global as we may need to apply them inside a group . . . . .	47	2019-08-27 lttab.dtx v1.1q General: Make various commands robust . . . . .	335
2019-08-27 ltfiles.dtx v1.2b <code>\IfFileExists</code> : Make command robust . . . . .	97	Remove several unnecessary <code>\gdef</code> definitions . . . . .	335
<code>\InputIfFileExists</code> : Make command robust . . . . .	98	2019-08-30 lterror.dtx v1.2q <code>\conditionally@traceoff</code> : Macro added . . . . .	68
2019-08-27 ltfsbas.dtx v3.2d General: Make various commands robust . . . . .	163	<code>\conditionally@traceon</code> : Macro added . . . . .	68
2019-08-27 ltssdcl.dtx v3.0s <code>\DeclareMathDelimiter</code> : Make math delimiters robust . . . .	229	2019-09-09 ltssdcl.dtx v3.0s <code>\DeclareMathSymbol</code> : Allow definition if the math symbol was a command already robust . . . . .	227
<code>\DeclareMathAccent</code> : Make math accents robust . . . . .	225	2019-09-14 ltfinal.dtx v2.1h <code>\ucclclist</code> : Expand UTF8 chrs when case changing (github/177) . . . . .	566
2019-08-27 ltssini.dtx v3.1d General: Make various commands robust . . . . .	237	2019-09-16 ltxref.dtx v1.1m General: Correctly revert the <code>\p@...</code> change . . . . .	278
2019-08-27 ltidxglo.dtx v1.1f General: Make <code>\index</code> and <code>\gloassary</code> robust . . . . .	415	2019-09-21 fontdef.dtx v3.0d General: Distangle alias (gh/184) . . . . .	255, 259
2019-08-27 ltlength.dtx v1.1d General: Make various command robust . . . . .	162	2019-10-02 ltfinal.dtx v2.2 General: Load <code>ltxexpl</code> . . . . .	568
2019-08-27 ltlogos.dtx v1.1j <code>\TeX</code> : Make <code>\TeX</code> command robust	87	2019-10-02 ltluatex.dtx v1.1k General: <code>linebreak_filter</code> is <code>exclusive</code> . . . . .	547
2019-08-27 ltmath.dtx v1.2c General: Make various commands robust . . . . .	294	<code>mlist_to_hlist</code> is <code>exclusive</code> . . .	547
2019-08-27 ltmiscen.dtx v1.1p General: Make various commands robust . . . . .	279	<code>process_rule</code> is <code>exclusive</code> . . . .	547
<code>\begin</code> : Make command robust .	284	2019-10-07 lttab.dtx v1.1q <code>\extracolsep</code> : This needs to expand . . . . .	346
<code>\end</code> : Make command robust . . .	286	2019-10-11 ltfiles.dtx v1.2c <code>\set@curr@file</code> : Remove one brace group . . . . .	96
2019-08-27 ltoutput.dtx v1.4e <code>\@beginvibox</code> : Make <code>\AtBeginDvi</code> robust . . . . .	436		



2019-10-18 ltclass.dtx v1.3d	first . . . . .	12
\@fileswithoptions: Initialize	2019-11-02 ltmiscen.dtx v1.1s	
\...-h@@k only when loading	\@centercr: Make \@centercr	
the package or class (gh/198)	robust (gh/203) . . . . .	287
2019-10-22 ltuatex.dtx v1.1j	2019-11-02 ltspace.dtx v1.3k	
General: page_objnum_provider	\@normalcr: Make also	
and process_pdf_image_content	\@normalcr robust . . . . .	75
classified data . . . . .	2019-11-09 ltfiles.dtx v1.2e	
2019-10-25 ltmiscen.dtx v1.1q	\set@curr@file: expand and	
\add@percent@to@temptokena:	\string before removing	
Allow unbalanced conditionals	quotes . . . . .	96
in #1 (gh/202) . . . . .	2019-11-10 ltmiscen.dtx v1.1r	
2019-10-26 ltfiles.dtx v1.2d	\add@percent@to@temptokena: fix	
\@iffileonpath: quote on openin	to special comment catcodes	
\IfFileExists: dont quote name	(gh/202) . . . . .	282
\IfFileExists@: quote on openin	2019-11-11 ltfiles.dtx v1.2f	
\set@curr@file: remove quotes .	\@iffileonpath: make	
2019-11-01 ltdirchk.dtx v1.3a	\@filef@und match quoting	
\filename@parse: take last . not	used on \openin . . . . .	97

# Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
$\backslash!$ . . . . .	b353, b355, <u>z201</u> , O419
$\backslash"$ . . . . .	l224, l375, l413, l451, l462, l570, l602, l629, l637, l643, l647, l653, l657, l663, l669, l676, l677, l683, l687, l737, l783, l1183, l1201, l1207, l1211, l1217, l1221, l1227, l1233, l1240, l1241, l1247, l1251, l1253, l1360, o349, O420
$\backslash\#$ . . . . .	a62, a75, b6, b14, b420, d387, o336, O403
$\backslash\$$ . . . . .	a74, b4, b13, d386, l304, l438, l445, l559, l795, l802, O404
$\backslash\%$ . . . . .	a75, a105, a107, a127, b14, b418, d387, l485, l487, o338, y56, L767, L768, O405
$\backslash\&$ . . . . .	a74, b5, b13, b419, d386, L169, O406
$\backslash'$ . . . . .	b440, l225, l376, l415, l449, l459, l572, l582, l588, l590, l593, l595, l603, l609, l615, l617, l620, l622, l630, l634, l641, l645, l650, l655, l658, l660, l667, l672, l673, l680, l685, l688, l738, l785, l804, l806, l807, l808, l811, l813, l814, l815, l817, l818, l1177, l1198, l1205, l1209, l1214, l1219, l1222, l1224, l1231, l1236, l1237, l1244, l1249, l1252, l1260, l1261, l1308, l1309, l1314, l1315, l1326, l1327, l1332, l1333, l1361, l1362, l1386, l1387, o348, s152, t223, y351, z208, B245, B266, C60, K584, O421
$\backslash($ . . . . .	<u>z225</u> , z299
$\backslash)$ . . . . .	b440, <u>z225</u> , z300
$\backslash*$ . . . . .	o341, <u>z205</u> , L577, L693, L769
$\backslash+$ . . . . .	C60
$\backslash,$ . . . . .	b354, b356, i335, t467, y351, z7, z8, z40, z154, z156, z159, z184, z201
$\backslash-$ . . . . .	b322, d9, <u>d394</u> , i326, l410, l411, l565, l779, l780, o343, y351, B244, B265, C60, O157, O197
$\backslash.$ . . . . .	b353, b355, k43, k101, l226, l377, l446, l447, l468, l578, l579, l605, l606, l632, l739, l809, l816, l1182, l1264, l1265, l1274, l1275, l1284, l1285, l1302, l1363, l1364, l1394, l1395, o342
$\backslash/$ . . . . .	a97, d10, o290, o344, L168
$\backslash:$ . . . . .	b354, b356, d381, d382, <u>z206</u>
$\backslash;$ . . . . .	b354, b356, t461, z185, <u>z201</u>
$\backslash<$ . . . . .	l566, l730, o339, y351, C59, C97
$\backslash=$ . . . . .	l227, l378, l467, l740, l1180, l1254, l1255, l1270, l1271, l1293, l1294, l1295, l1320, l1321, l1346, l1347, l1376, l1377, l1392, l1393, l1400, l1401, s152, B245, B266, C59
$\backslash>$ . . . . .	l563, l731, o340, y351, <u>z201</u> , z206, C59
$\backslash?$ . . . . .	b353, b355, O421
$\backslash@$ . . . . .	a65, d392, d393, g19, <u>i338</u> , j2, L24, L32, N18, N783, O413
$\backslash@@$ . . . . .	a331, a332, f15, f19, f20, f21, f22, f24, f27, f28, f30, f31, k389, k405, p464, p466, p467, C214, C215, C216, C226, K10, K11
$\backslash@@defaultsubs$ . . . . .	<u>o459</u>
$\backslash@@enc@update$ . . . . .	l181, o223, <u>o227</u>
$\backslash@@end$ . . . . .	a69, a222, d8, k369, k370, y39, y86, M18, O500, O521
$\backslash@@endpbox$ . . . . .	C181, C212, <u>C362</u>
$\backslash@@eqnocr$ . . . . .	<u>z334</u> , <u>z352</u> , <u>z355</u> , <u>z460</u>
$\backslash@@fileswith@pti@ns$ . . . . .	L242, <u>L465</u>
$\backslash@@hyph$ . . . . .	<u>d9</u>
$\backslash@@hyphenation$ . . . . .	<u>l203</u>
$\backslash@@if@newlist$ . . . . .	K599, K644, K657, K703
$\backslash@@if@definable$ . . . . .	<u>d107</u> , l17
$\backslash@@input$ . . . . .	a68, d7, k319, k327, k332, k358, y19, L920
$\backslash@@italiccorr$ . . . . .	<u>d10</u> , v96, v100
$\backslash@@line$ . . . . .	<u>B402</u>
$\backslash@@math@bgroup$ . . . . .	v114, v121
$\backslash@@math@egroup$ . . . . .	<u>v111</u> , <u>v111</u>
$\backslash@@par$ . . . . .	<u>69</u> , <u>d6</u> , h4, y86, y222, y227, y230, y244, y248, y251, A82, A85, B221, B243, B264, C187, F67, F118, K257
$\backslash@@patterns$ . . . . .	<u>l203</u>
$\backslash@@protect$ . . . . .	d228, d234, d243
$\backslash@@startpbox$ . . . . .	C181, C212, <u>C362</u>
$\backslash@@underline$ . . . . .	<u>B358</u> , B361, B362
$\backslash@@unprocessedoptions$ . . . . .	L447, <u>L509</u>
$\backslash@@warning$ . . . . .	<u>g166</u>
$\backslash@Alph$ . . . . .	m106, <u>m122</u>
$\backslash@DeclareMathDelimiter$ . . . . .	r752, <u>r771</u>
$\backslash@DeclareMathSizes$ . . . . .	<u>o170</u> , <u>o171</u> , <u>o173</u>

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx, e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx, j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx, o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx, t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx, y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx, D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx, I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx, N=ltluatex.dtx, O=ltfinal.dtx

- \@Esphack . . . . [i164](#), [G201](#), [G223](#), [G241](#)
- \@IncludeInRelease . . . . . [c79](#), [c80](#)
- \@IncludeInRelease . . . . . [c77](#), [c78](#), [c79](#)
- \@M . . . . . [b21](#), [b397](#), [b398](#),  
[d22](#), [d24](#), [i11](#), [i12](#), [i13](#), [i14](#), [i15](#),  
[i16](#), [i17](#), [i18](#), [i93](#), [o528](#), [o535](#),  
[p393](#), [p406](#), [z344](#), [A194](#), [C56](#),  
[F67](#), [F100](#), [F118](#), [F130](#), [F188](#),  
[F211](#), [K176](#), [K195](#), [K198](#), [K258](#)
- \@MM . . . . . [b21](#), [G412](#), [K299](#)
- \@Mi . . . . . [e3](#), [K136](#)
- \@Mii . . . . . [e3](#), [G53](#), [G122](#), [G194](#), [G216](#),  
[G241](#), [G311](#), [K295](#), [K1159](#), [K1326](#)
- \@Miii . . . . . [e3](#), [G55](#), [G124](#), [G313](#), [K298](#)
- \@Miv . . . . . [e3](#), [G195](#), [G201](#), [G217](#), [G223](#), [K272](#)
- \@Roman . . . . . [m104](#), [m110](#)
- \@TeXversion . . . . . [1](#), [6](#), [a326](#), [g28](#)
- \@acci . . . . . [s152](#), [B245](#), [B266](#)
- \@accii . . . . . [s152](#), [B245](#), [B266](#)
- \@acciii . . . . . [s152](#), [B245](#), [B266](#)
- \@acol . . . . . [C156](#),  
[C166](#), [C236](#), [C237](#), [C249](#), [C250](#),  
[C253](#), [C270](#), [C285](#), [C293](#), [C303](#)
- \@acolampacol . . . . . [C234](#), [C251](#),  
[C253](#), [C260](#), [C268](#), [C302](#), [C305](#)
- \@activechar@info . . . . . [K575](#)
- \@addamp . . . . . [C227](#), [C236](#),  
[C237](#), [C252](#), [C266](#), [C303](#), [C304](#)
- \@addfield . . . . . [C43](#),  
[C53](#), [C74](#), [C81](#), [C113](#), [C128](#), [C130](#)
- \@addmarginpar . . . . . [K331](#), [K1811](#)
- \@addtobot . . . . . [K975](#), [K1062](#),  
[K1129](#), [K1181](#), [K1290](#), [K1349](#)
- \@addtocurcol . . . . . [K328](#), [K1066](#), [K1965](#)
- \@addtodblcol . . . . . [K854](#), [K1562](#)
- \@addtofilelist . . . . .  
. [a101](#), [a103](#), [k61](#), [k116](#), [k319](#),  
[k327](#), [k386](#), [s128](#), [s131](#), [s138](#),  
[s141](#), [s148](#), [s151](#), [O210](#), [O213](#), [O542](#)
- \@addtonextcol . . . . . [K853](#), [K1386](#), [K1966](#)
- \@addtopreamble . . . . . [C287](#), [C300](#),  
[C306](#), [C307](#), [C308](#), [C310](#), [C322](#)
- \@addtoreset . . . . . [m16](#), [m39](#), [m44](#), [m79](#), [m82](#)
- \@addtotoporbot . . . . . [K1012](#),  
[K1175](#), [K1343](#), [K1435](#), [K1524](#)
- \@afterheading . . . . . [F92](#), [F125](#)
- \@afterindentfalse . . . . . [F45](#)
- \@afterindenttrue . . . . .  
. . . . . [F43](#), [F124](#), [F187](#), [F210](#)
- \@alph . . . . . [m105](#), [m118](#), [G375](#)
- \@ampacol . . . . . [C234](#), [C251](#), [C262](#), [C305](#)
- \@arabic . . . . .  
. . . . . [m43](#), [m76](#), [m87](#), [m102](#), [m108](#), [G373](#)
- \@argarraycr . . . . . [C191](#), [C192](#)
- \@argdef . . . . . [d55](#)
- \@argsbox . . . . . [B382](#)
- \@argtabularcr . . . . . [C198](#), [C199](#)
- \@array . . . . . [C169](#), [C170](#)
- \@arrayacol . . . . . [C156](#), [C234](#)
- \@arrayclassiv . . . . . [C157](#), [C307](#)
- \@arrayclassz . . . . . [C156](#), [C251](#)
- \@arraycr . . . . . [C158](#), [C189](#), [C191](#)
- \@arrayparboxrestore . . . . . [B235](#), [B277](#), [C360](#)
- \@arrayrule . . . . . [C285](#),  
. . . . . [C287](#), [C291](#), [C293](#), [C295](#), [C322](#)
- \@arstrut . . . . . [C180](#), [C213](#), [C319](#)
- \@arstrutbox . . . . . [C173](#), [C206](#), [C319](#), [C361](#)
- \@author . . . . . [F8](#), [F32](#)
- \@auxout . . . . .  
. . . . . [k145](#), [k157](#), [k172](#), [k191](#), [k206](#),  
[x33](#), [F175](#), [I7](#), [I8](#), [I19](#), [I29](#), [I37](#), [I43](#)
- \@backslashchar . . . . .  
. . . . . [d193](#), [g185](#), [g187](#), [t236](#), [L641](#), [L731](#)
- \@badcrrr . . . . . [g227](#)
- \@badend . . . . . [g198](#), [y150](#)
- \@badlinearg . . . . . [g217](#), [D59](#),  
[D68](#), [D69](#), [D73](#), [D117](#), [D122](#), [D133](#)
- \@badmath . . . . . [g201](#), [z229](#), [z231](#), [z236](#),  
[z239](#), [z248](#), [z260](#), [z265](#), [z274](#),  
[z287](#), [z292](#), [z384](#), [z396](#), [z412](#), [z421](#)
- \@badpoptabs . . . . . [g205](#), [C73](#), [C139](#)
- \@badrequireerror . . . . . [L182](#), [L517](#)
- \@badtab . . . . . [g208](#),  
. . . . . [C22](#), [C75](#), [C96](#), [C102](#), [C109](#), [C136](#)
- \@begin@tempboxa . . . . .  
. . . . . [B27](#), [B42](#), [B158](#), [B221](#), [B383](#), [B391](#)
- \@begindocumenthook . . . . . [k55](#),  
. . . . . [k58](#), [k110](#), [k113](#), [L476](#), [L490](#), [I33](#)
- \@beginndvi . . . . . [K623](#), [K682](#), [K710](#)
- \@beginndvibox . . . . . [K86](#), [K711](#)
- \@beginparpenalty . . . . .  
. . . . . [i14](#), [z387](#), [z399](#), [z425](#), [A23](#), [A170](#)
- \@begintheorem . . . . . [E30](#), [E35](#)
- \@bezier . . . . . [D369](#), [D370](#)
- \@bibitem . . . . . [I3](#), [I8](#)
- \@biblabel . . . . . [I4](#), [I54](#)
- \@bitor . . . . . [K15](#), [K881](#),  
[K901](#), [K937](#), [K960](#), [K1027](#),  
[K1111](#), [K1121](#), [K1269](#), [K1280](#),  
[K1422](#), [K1509](#), [K1627](#), [K1752](#)
- \@botlist . . . . . [K65](#),  
[K384](#), [K386](#), [K431](#), [K433](#), [K717](#),  
[K738](#), [K747](#), [K748](#), [K989](#), [K992](#),  
[K1027](#), [K1029](#), [K1121](#), [K1123](#),  
[K1280](#), [K1282](#), [K1922](#), [K1949](#)
- \@botnum . . . . . [G274](#),  
. . . . . [K109](#), [K986](#), [K987](#), [K992](#), [K996](#),

File Key: a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- K1003, K1458, K1463, K1551,  
 K1558, K1914, K1941, K1983  
 \@botroom ..... G275,  
 K110, K989, K992, K1915, K1942  
 \@boxfpsbit .... K2031, K2033, K2038  
 \@break@tfor .... f31, k265, k304, v81  
 \@bsphack ..... i36, i99, i286,  
 i302, x32, G52, G121, G310,  
 H6, H18, H23, H35, K1882, I39  
 \@caption ..... G12, G14  
 \@capttype ..... G5, G9,  
 G12, G40, G88, G109, G157, K1995  
 \@car ..... 37, d38, j14, l87, l108  
 \@carcube ..... d40, d110  
 \@cclv ..... b16, K300, K304,  
 K382, K383, K412, K429, K430,  
 K459, K483, K487, K488, O53  
 \@ccarvi b21, b57, b82, b93, b95, b99,  
 b159, b173, L639, L729, N28, N56  
 \@cdr ..... 37, d38, d362, d363  
 \@centercr ... y153, y179, y183, y187  
 \@centering ..... z314,  
 z315, z322, z325, z328, z453, z457  
 \@cflb ..... K714  
 \@cflt ..... K714  
 \@changed@cmd .....  
 .... l3, l63, l221, o95, o231, O372  
 \@changed@x ..... l3, l209, l217  
 \@changed@x@mouth ..... l209, l217  
 \@charlb ..... k209, k217  
 \@charrb ..... k211, k217  
 \@chclass C247, C248, C311, C324, C329  
 \@check@IncludeInRelease .....  
 ..... c105, c107, c109  
 \@check@c ..... d164, d166  
 \@check@eq ..... d170, d171, d175  
 \@checkend ..... y11, y137, y149  
 \@chnum ..... C255,  
 C274, C311, C326, C327, C328  
 \@circ ..... D341, D342, D343  
 \@circle ..... D329, D330  
 \@circlefnt ..... D37, D39, D233,  
 D262, D304, D334, D349, D364  
 \@cite ..... I16, I52  
 \@cite@ofmt ..... I24, I53  
 \@citea ..... I15, I17  
 \@citeb ..... I16, I18, I19,  
 I20, I23, I24, I41, I42, I43, I44, I45  
 \@citex ..... I13, I14  
 \@classi ..... C247, C283  
 \@classii ..... C247, C297  
 \@classiii ..... C247, C302  
 \@classiv ..... C157, C168, C248  
 \@classoptionslist L9, L211, L222,  
 L361, L362, L389, L390, L1001  
 \@classv ..... C248, C308  
 \@classz ..... C156, C167, C247  
 \@cline ..... C343  
 \@clnht ..... D75, D76, D84,  
 D86, D88, D98, D105, D131, D358  
 \@clnwd D77, D83, D87, D89, D90, D358  
 \@cls@pkg ..... L145,  
 L146, L426, L456, L493, L502,  
 L504, L521, L854, L929, L951, L981  
 \@clsextension ..... L16,  
 L41, L52, L96, L152, L178,  
 L195, L211, L221, L279, L294,  
 L302, L360, L388, L460, L468, L494  
 \@clubpenalty ..... k9,  
 k23, k80, A128, A196, F106, F135  
 \@colht .... k20, k77, G273, G275,  
 G278, G284, G285, G298,  
 G299, K114, K231, K242, K251,  
 K252, K387, K399, K434, K447,  
 K474, K505, K535, K541, K545,  
 K555, K560, K645, K704, K777,  
 K815, K859, K884, K903, K943,  
 K965, K1642, K1768, K2096, O88  
 \@colnum ..... G276, K111,  
 K995, K1040, K1109, K1110,  
 K1138, K1146, K1188, K1267,  
 K1268, K1300, K1312, K1356,  
 K1420, K1421, K1458, K1463,  
 K1507, K1508, K1550, K1557,  
 K1910, K1937, K1976, K2151  
 \@colroom ..... k21, k78,  
 K115, K252, K273, K274, K285,  
 K288, K387, K434, K777, K994,  
 K1039, K1105, K1108, K1137,  
 K1262, K1266, K1299, K1416,  
 K1419, K1502, K1506, K1911,  
 K1938, K2106, K2111, K2156, O87  
 \@combinedblfloats K750, K2230, K2269  
 \@combinefloats ..... K501, K714  
 \@comdbflelt ..... K750  
 \@comflelt ..... K720, K736, K750  
 \@cons ..... 37, b196, b213, d37,  
 m44, G193, G215, G239, G355,  
 K237, K888, K907, K923, K947,  
 K949, K969, K971, K1141,  
 K1209, K1305, K1378, K1451,  
 K1541, K1644, K1667, K1770,  
 K1795, K1812, K1813, K2157  
 \@contfield ..... C50, C129, C141  
 \@ctrerr g194, m121, m125, m139, m147  
 \@curfield ..... C16, C41,  
 C47, C51, C52, C54, C118, C119

File Key: a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

<code>\@curline</code> .....	L298, L417, L441, L442, L444, L446, L448, L449, L486, L502, L504, L511, L521, L929, L951, L981
<code>\@curr@enc</code> .....	l152, l154
<code>\@curr@file</code> .....	k153, k161, k222, k241, k339, L583, L587, L594, L618, L627, L653
<code>\@currbox</code> .....	b264, b265, b266, G60, G91, G95, G129, G160, G164, G193, G214, G215, G239, G257, G259, G261, G319, G322, G327, G331, K213, K214, K225, K226, K228, K229, K237, K311, K312, K853, K854, K1102, K1104, K1112, K1135, K1139, K1141, K1156, K1197, K1209, K1257, K1260, K1297, K1302, K1305, K1322, K1367, K1378, K1410, K1426, K1440, K1451, K1493, K1530, K1541, K1581, K1585, K1596, K1602, K1604, K1608, K1613, K1622, K1631, K1637, K1644, K1667, K1702, K1706, K1718, K1725, K1727, K1731, K1737, K1747, K1762, K1770, K1795, K1813, K1822, K2001, K2002, K2031, K2061, K2066, K2112, K2115, K2127, K2135, K2152, K2157
<code>\@currdir</code> .....	1, 6, a108, a130, a132, a138, a140, a146, a148, a153, a155, a165, a178, a243, a256, a269, L566, L587, L618, L702
<code>\@current@cmd</code> .....	l25, o235
<code>\@currentlabel</code> .....	x34, x41, x53, x61, z318, z438, B330, G414
<code>\@currenvir</code> .....	g199, y3, y96, y113, y150, A112, B104, L629, L641, L649, L653, L659, L719, L731, L739, L743, L749
<code>\@currenvline</code> .....	g199, y97, y114, y151, B105
<code>\@current</code> L15, L23, L31, L151, L152, L195, L204, L211, L221, L289, L298, L418, L423, L424, L429, L435, L439, L441, L442, L444, L446, L448, L449, L452, L458, L460, L468, L486, L494, L510, L511	
<code>\@currlist</code> .....	G193, G215, G355, K67, K311, K388, K391, K435, K438, K1812
<code>\@currname</code> .....	c66, c82, c90, k397, k398, L14, L22, L30, L143, L145, L151, L204,
	L298, L417, L441, L442, L444, L446, L448, L449, L486, L502, L504, L511, L521, L929, L951, L981
<code>\@currnamestack</code> .....	L20
<code>\@curroptions</code> .....	L204, L212, L234, L511, L512
<code>\@currsz</code> .....	s72
<code>\@currtype</code> .....	K119, K878, K879, K880, K881, K898, K899, K900, K901, K1027, K1111, K1121, K1269, K1280, K1422, K1509, K1627, K1752, K2001, K2003, K2004, K2007
<code>\@curtab</code> .....	C11, C26, C74, C75, C76, C82, C83, C86, C90, C91, C95, C134, C135
<code>\@curtabmar</code> .....	C11, C25, C26, C38, C44, C77, C90, C94, C95
<code>\@d@r</code> .....	a161, a162
<code>\@dashbox</code> .....	D176, D177, D178, D179, D180, D183, D186, D188, D197, D199, D200, D201, D202, D205, D208, D211, D360
<code>\@dashcnt</code> .....	D170, D171, D172, D173, D174, D175, D185, D187, D190, D191, D192, D193, D195, D196, D207, D210, D360
<code>\@dashdim</code> .....	D169, D170, D171, D172, D174, D177, D179, D180, D181, D185, D187, D189, D190, D191, D192, D195, D199, D201, D202, D203, D209, D212, D360
<code>\@date</code> .....	F9, F33
<code>\@dbflt</code> .....	G32, G264
<code>\@dblarg</code> .....	37, d384, F54, F142, G12
<code>\@dbldeferlist</code> .....	G239, K70, K445, K450, K452, K816, K823, K824, K1752, K1755, K1795, K1797, K1926, K1954
<code>\@dblfloat</code> .....	G31
<code>\@dblfloatplacement</code> .....	k29, k87, G280, K401, K449, K1907, K1934, K2235, K2275
<code>\@dblflset</code> .....	G26
<code>\@dblfpbot</code> .....	G290, G304, K2319
<code>\@dblfpsep</code> .....	G289, G303, K2319
<code>\@dblftop</code> .....	G288, G302, K2319
<code>\@dbltoplist</code> .....	K69, K232, K235, K237, K397, K398, K445, K446, K755, K759, K761, K762, K1639, K1644, K1764, K1770, K1925, K1952
<code>\@dbltopnum</code> .....	G283, G297, K107, K127, K238, K240, K766,

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

K1578, K1579, K1643, K1646,  
 K1654, K1674, K1679, K1699,  
 K1700, K1769, K1773, K1781,  
 K1802, K1807, K1918, K1945  
 \@dbltoproom . . . G284, G286, G298,  
 G300, K108, K1581, K1584,  
 K1585, K1594, K1595, K1598,  
 K1601, K1604, K1608, K1612,  
 K1616, K1621, K1641, K1702,  
 K1705, K1706, K1715, K1716,  
 K1717, K1720, K1724, K1727,  
 K1731, K1736, K1740, K1745,  
 K1746, K1767, K1919, K1946  
 \@dec@text@cmd . . . . . [l3](#)  
 \@declaredoptions . . . . .  
[L8](#), [L185](#), [L208](#), [L224](#), [L239](#), [L474](#)  
 \@declareoption . . . [L183](#), [L184](#), [L192](#)  
 \@defaultsubs . . . [o413](#), [o447](#), [o459](#), [y26](#)  
 \@defaultunits . . . . . [o178](#), [o182](#),  
[o183](#), [o184](#), [o199](#), [o261](#), [p133](#), [p135](#)  
 \@defdefault@ds . . . [L183](#), [L188](#), [L193](#)  
 \@deferlist . . . . .  
[K68](#), [K384](#), [K393](#), [K394](#), [K397](#),  
[K402](#), [K404](#), [K410](#), [K431](#), [K440](#),  
[K442](#), [K778](#), [K786](#), [K787](#), [K798](#),  
[K803](#), [K804](#), [K1111](#), [K1114](#),  
[K1209](#), [K1211](#), [K1269](#), [K1272](#),  
[K1378](#), [K1380](#), [K1422](#), [K1424](#),  
[K1451](#), [K1453](#), [K1509](#), [K1511](#),  
[K1541](#), [K1543](#), [K1627](#), [K1629](#),  
[K1667](#), [K1669](#), [K1924](#), [K1951](#)  
 \@definecounter . . . . .  
 . [m12](#), [m36](#), [z303](#), [A227](#), [A228](#),  
[A229](#), [A230](#), [E8](#), [E16](#), [G372](#), [G374](#)  
 \@depth . . . . . [d11](#), [p145](#),  
[t519](#), [t520](#), [t522](#), [t523](#), [B357](#),  
[B401](#), [C175](#), [C207](#), [D107](#), [D158](#),  
[D161](#), [D176](#), [D183](#), [D403](#), [K1851](#)  
 \@dir . . . . . [a160](#), [a163](#), [a165](#), [a167](#), [a168](#)  
 \@dischyrph [d394](#), [d409](#), [d414](#), [B244](#), [B265](#)  
 \@docclearpage . . . . . [K296](#), [K371](#)  
 \@documentclasshook . . . [L3](#), [L365](#), [L393](#)  
 \@doendpe . . . . . [y138](#), [A123](#)  
 \@dofilelist . . . . . [k395](#), [k411](#), [y21](#)  
 \@donoparitem . . . . . [A144](#), [A158](#)  
 \@dot . . . . . [D329](#), [D342](#)  
 \@dotsep . . . . . [F194](#), [F217](#)  
 \@dottedtocline . . . . [F179](#), [F205](#), [F206](#)  
 \@downline . . . . . [D155](#), [D159](#), [D164](#)  
 \@downvector . . . . . [D126](#), [D164](#)  
 \@eha . . . . . [d252](#), [d279](#),  
[g170](#), [g188](#), [g190](#), [g192](#), [g200](#),  
[g202](#), [g232](#), [k158](#), [k173](#), [l52](#), [l82](#),  
[l1566](#), [l1576](#), [o24](#), [o66](#), [o108](#),  
[o151](#), [o217](#), [o272](#), [p106](#), [r25](#), [r70](#),  
[r99](#), [r161](#), [r192](#), [r293](#), [r314](#), [r346](#),  
[r387](#), [r432](#), [r437](#), [r492](#), [r610](#),  
[r614](#), [r618](#), [r653](#), [r657](#), [r661](#),  
[r718](#), [r728](#), [r819](#), [r824](#), [r827](#),  
[r876](#), [r881](#), [r884](#), [r918](#), [r921](#),  
[r993](#), [r996](#), [r999](#), [r1066](#), [r1072](#),  
[v129](#), [y95](#), [y112](#), [K1876](#), [K1892](#), [l47](#)  
 \@ehb . . . . . [g170](#), [g195](#), [g220](#),  
[g222](#), [g224](#), [K234](#), [K390](#), [K437](#)  
 \@ehc . . . . . [d103](#), [d130](#), [g170](#),  
[g227](#), [g230](#), [g236](#), [g238](#), [y288](#),  
[y314](#), [y327](#), [z359](#), [A220](#), [F31](#), [L981](#)  
 \@ehd . . . [g170](#), [g197](#), [g204](#), [g207](#), [g209](#),  
[g215](#), [r118](#), [C88](#), [C97](#), [G6](#), [L327](#)  
 \@elt . . . . . [d37](#),  
[k210](#), [m20](#), [m35](#), [m53](#), [m56](#), [K8](#),  
[K11](#), [K15](#), [K27](#), [K30](#), [K31](#), [K32](#),  
[K33](#), [K38](#), [K39](#), [K40](#), [K41](#), [K42](#),  
[K43](#), [K44](#), [K45](#), [K47](#), [K51](#), [K57](#),  
[K58](#), [K59](#), [K60](#), [K498](#), [K720](#),  
[K731](#), [K736](#), [K746](#), [K758](#), [K760](#),  
[K788](#), [K805](#), [K825](#), [K844](#), [K857](#),  
[K864](#), [K915](#), [K918](#), [K927](#), [K1898](#)  
 \@empty . . . . . [f14](#)  
 \@emptycol . . . . .  
 . . . [K198](#), [K245](#), [K248](#), [K277](#), [K281](#)  
 \@end@check@IncludeInRelease . . .  
 . . . . . [c106](#), [c108](#)  
 \@end@tempboxa . . . . .  
[B36](#), [B45](#), [B163](#), [B234](#), [B389](#), [B399](#)  
 \@enddocumenthook . . . [y10](#), [L476](#), [L491](#)  
 \@endfloatbox [G190](#), [G211](#), [G236](#), [G248](#)  
 \@endparenv . . . . . [A120](#), [A123](#)  
 \@endparpenalty . . . . .  
 . . . [i15](#), [z388](#), [z400](#), [z426](#), [A23](#), [A124](#)  
 \@endpbox . . . . . [C181](#),  
[C212](#), [C242](#), [C309](#), [C360](#), [C363](#)  
 \@endpfalse . . . . . [y100](#), [y117](#), [A129](#),  
[A131](#), [A135](#), [A136](#), [A138](#), [B107](#)  
 \@endpeltrue . . . . . [A138](#)  
 \@endpetrue . . . . . [A124](#), [A126](#), [A134](#)  
 \@endtheorem . . . . . [E13](#), [E19](#), [E25](#), [E35](#)  
 \@enlargepage . . . [K1861](#), [K1866](#), [K1868](#)  
 \@ensuredmath . . . . . [z370](#), [z372](#)  
 \@enumctr . . . . . [A234](#), [A237](#), [A238](#)  
 \@enumdepth . . . [A226](#), [A232](#), [A233](#), [A234](#)  
 \@eqcnt . . . . . [z311](#),  
[z356](#), [z361](#), [z440](#), [z455](#), [z456](#), [z458](#)  
 \@eqncr . . . . . [z323](#), [z341](#), [z362](#), [z363](#), [z442](#)  
 \@eqnnum . . . [z305](#), [z306](#), [z360](#), [z374](#), [z433](#)  
 \@eqnswfalse . . . . . [z311](#), [z454](#)  
 \@eqnswtrue . . . . . [z313](#), [z319](#), [z361](#), [z439](#)

File Key: a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

`\@eqpen` ..... [z311](#), [z344](#), [z346](#), [z353](#)  
`\@err@` ..... [g37](#),  
           [g41](#), [g44](#), [g52](#), [g64](#), [g68](#), [g71](#), [g79](#)  
`\@esphack`    [i38](#), [i105](#), [i291](#), [i308](#), [x35](#),  
           [G361](#), [H17](#), [H19](#), [H34](#), [K1884](#), [I50](#)  
`\@evenfoot`    .... [J12](#), [J15](#), [K613](#), [K672](#)  
`\@evenhead`    .... [J12](#), [J15](#), [K612](#), [K671](#)  
`\@expandtwoargs` .....  
           .... [d191](#), [L100](#), [L210](#), [L224](#), [L248](#)  
`\@expast` ..... [C215](#), [C243](#)  
`\@failedlist` .....  
           .... [K842](#), [K865](#), [K881](#), [K888](#),  
               [K901](#), [K907](#), [K923](#), [K937](#), [K960](#)  
`\@fcolmadefalse` ..... [K833](#)  
`\@fcolmadetrue` ..... [K921](#)  
`\@filef@und` ..... [k252](#),  
           [k262](#), [k290](#), [k301](#), [k319](#), [k327](#), [k358](#)  
`\@filelist` .....  
           . [k60](#), [k115](#), [k385](#), [k386](#), [k397](#),  
           [s128](#), [s138](#), [s148](#), [O210](#), [O526](#), [O542](#)  
`\@fileswfalse` ..... [k128](#), [L562](#), [L563](#)  
`\@fileswith@pti@ns` .....  
           .... [L182](#), [L242](#), [L352](#), [L353](#),  
               [L357](#), [L359](#), [L386](#), [L387](#), [L414](#), [L465](#)  
`\@fileswith@ptions` .....  
           ..... [L347](#), [L348](#), [L350](#), [L354](#)  
`\@fileswithoptions` .....  
           ..... [L279](#), [L286](#), [L294](#), [L345](#)  
`\@fileswtrue` [k7](#), [L546](#), [L549](#), [L603](#), [L607](#)  
`\@finalstrut` . [B334](#), [B400](#), [C361](#), [G419](#)  
`\@firstampfalse` ... [C230](#), [C253](#), [C270](#)  
`\@firstamptrue` ..... [C238](#)  
`\@firstcolfirstmark` .....  
           ..... [K2212](#), [K2213](#), [K2217](#)  
`\@firstcoltopmark` .... [K2210](#), [K2218](#)  
`\@firstcolumnfalse` .... [K2202](#), [K2247](#)  
`\@firstcolumntrue` ..... [k26](#),  
           [k84](#), [K98](#), [K207](#), [K2221](#), [K2253](#)  
`\@firstofone` .....  
           .... [d186](#), [k54](#), [k109](#), [k233](#), [l68](#),  
               [l151](#), [p300](#), [r53](#), [r81](#), [r142](#), [r172](#),  
               [r763](#), [y9](#), [z368](#), [C348](#), [G10](#), [N65](#),  
               [N100](#), [N108](#), [N166](#), [O255](#), [I18](#), [I42](#)  
`\@firstoftwo` ..... [a87](#),  
           [d186](#), [d336](#), [d346](#), [d356](#), [d383](#),  
           [k263](#), [k302](#), [l131](#), [l1538](#), [l1554](#),  
           [m157](#), [m162](#), [r767](#), [x19](#), [J16](#),  
           [L48](#), [L68](#), [L80](#), [L107](#), [L125](#), [L990](#)  
`\@firstttab` [C2](#), [C62](#), [C63](#), [C64](#), [C94](#), [C106](#)  
`\@flcheckspace` .. [K989](#), [K1025](#), [K2102](#)  
`\@flfail` ..... [K865](#),  
           [K916](#), [K937](#), [K947](#), [K960](#), [K969](#)  
`\@float` ..... [G26](#), [G32](#)  
`\@floatboxreset` ... [G101](#), [G170](#), [G174](#)

`\@floatpenalty` .....  
           .... [G3](#), [G53](#), [G55](#), [G58](#), [G122](#),  
               [G124](#), [G127](#), [G191](#), [G194](#),  
               [G199](#), [G201](#), [G212](#), [G216](#),  
               [G221](#), [G223](#), [G237](#), [G241](#),  
               [G311](#), [G313](#), [G317](#), [G321](#), [G355](#)  
`\@floatplacement` .....  
           ..... [k29](#), [k87](#), [G271](#), [K149](#),  
               [K209](#), [K253](#), [K477](#), [K1908](#), [K1935](#)  
`\@flsetnum` ..... [K986](#),  
           [K1022](#), [K1109](#), [K1267](#), [K1420](#),  
           [K1507](#), [K1578](#), [K1699](#), [K2070](#)  
`\@flsettextmin` ..... [K1085](#),  
           [K1237](#), [K1406](#), [K1489](#), [K2086](#)  
`\@flstop` ..... [K1972](#)  
`\@flsucceed` .....  
           .. [K858](#), [K866](#), [K915](#), [K949](#), [K971](#)  
`\@fltovf` ..... [g223](#), [G93](#), [G162](#), [G322](#)  
`\@flupdates` ..... [K992](#), [K1037](#), [K2148](#)  
`\@flushglue` ..... [e17](#), [y180](#), [y183](#),  
           [y188](#), [y221](#), [y243](#), [A76](#), [B251](#), [B272](#)  
`\@fnsymbol` ..... [m107](#), [m126](#)  
`\@font@info` ..... [o97](#),  
           [o135](#), [o141](#), [o299](#), [o316](#), [o495](#),  
           [p30](#), [p38](#), [p46](#), [p74](#), [p87](#), [p126](#),  
           [p154](#), [p168](#), [p179](#), [p193](#), [p209](#),  
           [p215](#), [p228](#), [p235](#), [p242](#), [p247](#),  
           [p257](#), [p269](#), [p281](#), [p445](#), [p457](#),  
           [p462](#), [p469](#), [p494](#), [p502](#), [r202](#),  
           [r217](#), [r251](#), [r297](#), [r366](#), [r372](#),  
           [r416](#), [r429](#), [r512](#), [r601](#), [r644](#),  
           [r709](#), [r809](#), [r866](#), [r1034](#), [r1063](#), [O374](#)  
`\@font@warning` [o3](#), [o409](#), [o414](#), [o441](#),  
           [o448](#), [p19](#), [p33](#), [p41](#), [p49](#), [p61](#),  
           [p77](#), [p430](#), [p444](#), [p456](#), [p461](#),  
           [p468](#), [p493](#), [p501](#), [q30](#), [y23](#), [O230](#)  
`\@fontswitch` ..... [v109](#), [v111](#)  
`\@footnotemark` .....  
           .. [G401](#), [G407](#), [G425](#), [G431](#), [G432](#)  
`\@footnotetext` ..... [B304](#),  
           [G401](#), [G407](#), [G408](#), [G441](#), [G447](#)  
`\@for` ..... [f16](#), [k187](#), [k397](#), [L109](#),  
           [L126](#), [L208](#), [L222](#), [L234](#), [L239](#),  
           [L259](#), [L269](#), [L512](#), [L553](#), [I16](#), [I41](#)  
`\@forloop` ..... [f19](#), [f20](#)  
`\@fornoop` ..... [f15](#), [f23](#), [f29](#)  
`\@fortmp` .... [f17](#), [f18](#), [f26](#), [L257](#), [L259](#)  
`\@fpbot` .... [G290](#), [G304](#), [K863](#), [K2313](#)  
`\@fpmin` ..... [G278](#),  
           [G287](#), [G301](#), [K113](#), [K920](#),  
           [K1916](#), [K1943](#), [K2165](#), [K2182](#)  
`\@fps` ..... [G41](#), [G42](#), [G44](#),  
           [G47](#), [G64](#), [G110](#), [G111](#), [G113](#),  
           [G116](#), [G133](#), [K1993](#), [K1995](#), [K1998](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx



`\@fpsaddddefault` .....  
     ... [G45](#), [G48](#), [G114](#), [G117](#), [K1990](#)  
`\@fpsep` ..... [G289](#), [G303](#),  
     [K861](#), [K870](#), [K942](#), [K964](#), [K2313](#)  
`\@fpstype` ..... [K983](#),  
     [K1004](#), [K1005](#), [K1019](#), [K1050](#),  
     [K1051](#), [K1075](#), [K1077](#), [K1080](#),  
     [K1082](#), [K1133](#), [K1189](#), [K1190](#),  
     [K1225](#), [K1228](#), [K1231](#), [K1234](#),  
     [K1295](#), [K1357](#), [K1358](#), [K1396](#),  
     [K1398](#), [K1401](#), [K1403](#), [K1477](#),  
     [K1480](#), [K1483](#), [K1486](#), [K1575](#),  
     [K1590](#), [K1592](#), [K1610](#), [K1619](#),  
     [K1655](#), [K1656](#), [K1696](#), [K1711](#),  
     [K1713](#), [K1733](#), [K1743](#), [K1782](#),  
     [K1783](#), [K1986](#), [K2002](#), [K2004](#),  
     [K2006](#), [K2009](#), [K2010](#), [K2011](#),  
     [K2013](#), [K2014](#), [K2018](#), [K2019](#),  
     [K2021](#), [K2022](#), [K2056](#), [K2058](#),  
     [K2060](#), [K2072](#), [K2074](#), [K2088](#),  
     [K2090](#), [K2120](#), [K2123](#), [K2134](#)  
`\@fptop` .... [G288](#), [G302](#), [K860](#), [K2313](#)  
`\@frameb@x` ..... [B134](#), [B162](#), [B164](#)  
`\@framebox` ..... [B141](#), [B148](#), [B152](#)  
`\@framepicbox` ..... [B141](#), [B148](#), [B185](#)  
`\@freelist` . [b196](#), [b213](#), [b264](#), [G60](#),  
     [G129](#), [G319](#), [G320](#), [K29](#), [K34](#),  
     [K48](#), [K56](#), [K213](#), [K499](#), [K732](#),  
     [K747](#), [K761](#), [K866](#), [K1812](#), [K1813](#)  
`\@getcirc` ... [D223](#), [D256](#), [D300](#), [D332](#)  
`\@getfpsbit` ..... [K980](#),  
     [K1016](#), [K1572](#), [K1693](#), [K2029](#)  
`\@getlarrow` ..... [D124](#), [D132](#), [D134](#)  
`\@getlinechar` ..... [D70](#), [D109](#)  
`\@getpen` ..... [i34](#), [i37](#), [i46](#), [i91](#)  
`\@getrarrow` ..... [D125](#), [D132](#), [D141](#)  
`\@glossaryfile` ..... [H21](#), [H22](#), [H31](#)  
`\@gnewline` ..... [i82](#), [i84](#), [i85](#)  
`\@gobble` ..... [d86](#),  
     [d108](#), [d183](#), [d193](#), [d210](#), [d214](#),  
     [d249](#), [d255](#), [d258](#), [d267](#), [d276](#),  
     [d282](#), [d285](#), [d294](#), [d309](#), [d313](#),  
     [d315](#), [f6](#), [f9](#), [g101](#), [g127](#), [g153](#),  
     [g162](#), [i75](#), [i381](#), [k61](#), [k116](#), [k236](#),  
     [k238](#), [k385](#), [l29](#), [l1516](#), [o410](#),  
     [o443](#), [p299](#), [q26](#), [r28](#), [r30](#), [r255](#),  
     [r266](#), [r330](#), [r377](#), [r378](#), [r407](#),  
     [r413](#), [r421](#), [r426](#), [r444](#), [r458](#),  
     [r468](#), [r477](#), [r490](#), [r507](#), [r516](#),  
     [r590](#), [r592](#), [r596](#), [r604](#), [r638](#),  
     [r647](#), [r699](#), [r701](#), [r712](#), [r800](#),  
     [r801](#), [r804](#), [r812](#), [r859](#), [r869](#),  
     [r951](#), [r956](#), [r1025](#), [r1056](#), [s131](#),  
     [s141](#), [s151](#), [y104](#), [F143](#), [F144](#),  
     [F145](#), [F146](#), [F147](#), [F176](#), [G7](#),  
     [K619](#), [K620](#), [K621](#), [K678](#), [K679](#),  
     [K680](#), [K927](#), [K1900](#), [K2166](#),  
     [K2183](#), [L315](#), [L533](#), [L597](#),  
     [L627](#), [L712](#), [L717](#), [L791](#), [L935](#),  
     [L947](#), [N64](#), [N98](#), [O213](#), [O307](#),  
     [O464](#), [O473](#), [O542](#), [I11](#), [I25](#), [I26](#)  
`\@gobble@IncludeInRelease` .....  
     ..... [c86](#), [c94](#), [c103](#)  
`\@gobblecr` ..... [i379](#), [i380](#)  
`\@gobblefour` ..... [d183](#),  
     [r24](#), [r252](#), [r368](#), [r370](#), [r374](#), [r376](#),  
     [r386](#), [r390](#), [r514](#), [r566](#), [L629](#), [L719](#)  
`\@gobbletwo` . [d150](#), [d151](#), [d183](#), [f12](#),  
     [k30](#), [k88](#), [o415](#), [o449](#), [r132](#), [y16](#),  
     [y24](#), [J11](#), [J13](#), [L596](#), [L711](#), [O236](#)  
`\@gtempa` ..... [d101](#),  
     [d102](#), [d156](#), [d158](#), [k366](#), [k367](#),  
     [k369](#), [k370](#), [k371](#), [C3](#), [C5](#), [C6](#),  
     [C7](#), [C8](#), [L142](#), [L143](#), [L153](#), [L155](#)  
`\@halfwidth` ..... [D2](#), [D38](#),  
     [D40](#), [D42](#), [D107](#), [D157](#), [D160](#),  
     [D176](#), [D183](#), [D197](#), [D207](#), [D210](#),  
     [D366](#), [D388](#), [D401](#), [D402](#), [D403](#)  
`\@halignto` .. [C158](#), [C162](#), [C165](#), [C179](#)  
`\@changfrom` ..... [F66](#), [F117](#), [F138](#)  
`\@height` ..... [b391](#), [d11](#), [i296](#),  
     [i304](#), [l290](#), [l292](#), [p144](#), [t309](#),  
     [t519](#), [t520](#), [t522](#), [t523](#), [B118](#),  
     [B123](#), [B171](#), [B181](#), [B357](#), [B401](#),  
     [C174](#), [C207](#), [C335](#), [C352](#), [D107](#),  
     [D158](#), [D161](#), [D176](#), [D183](#), [D199](#),  
     [D206](#), [D281](#), [D324](#), [D402](#), [K1851](#)  
`\@highpenalty` ..... [i92](#), [O3](#)  
`\@hightab` ... [C11](#), [C21](#), [C23](#), [C62](#),  
     [C74](#), [C83](#), [C84](#), [C99](#), [C134](#), [C135](#)  
`\@hline` ..... [D61](#), [D106](#), [D123](#)  
`\@holdpg` ..... [K122](#), [K300](#),  
     [K302](#), [K303](#), [K308](#), [K309](#), [K310](#)  
`\@hspace` ..... [i350](#), [i351](#)  
`\@hspacer` ..... [i350](#), [i352](#)  
`\@hvector` ..... [D119](#), [D123](#)  
`\@icentercr` ..... [y170](#), [y171](#)  
`\@iden` ..... [d189](#)  
`\@if` ..... [d146](#), [d147](#), [d149](#)  
`\@if@pti@ns` ..... [L100](#),  
     [L104](#), [L106](#), [L123](#), [L124](#), [L140](#)  
`\@if@ptions` . [L95](#), [L96](#), [L99](#), [L101](#), [L424](#)  
`\@ifatmargin` ..... [C55](#), [C94](#)  
`\@ifbothcounters` .....  
     . [m61](#), [m69](#), [m71](#), [m79](#), [m81](#), [m93](#)  
`\@ifclasslater` ..... [499](#), [L51](#)  
`\@ifclassloaded` ..... [499](#), [L40](#)  
`\@ifclasswith` ..... [499](#), [L95](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=ltpictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx



- \@ifdefinable ..... 37, d59,  
d61, d105, d107, d212, l14, l17,  
m11, n3, s68, B70, E7, E15, E22
- \@iffilenamepath k248, k256, k286, k295
- \@ifl@aded .. L40, L41, L44, L50, L423
- \@ifl@t@r .....  
L56, L61, L63, L74, L75, L85, L336
- \@ifl@ter ..... l1499,  
l1500, L51, L52, L55, L58, L452
- \@ifl@ter@@ ..... l1499, l1500
- \@ifnch ..... d368, d370, d382
- \@ifnextchar ..... 37, a98, d364,  
d369, d383, i80, i380, k332,  
m13, p365, y169, z309, A143,  
B9, B11, B18, B20, B26, B47,  
B76, B77, B83, B84, B91, B95,  
B140, B141, B147, B148, B153,  
B186, B194, B202, B209, B213,  
B282, B286, B290, B341, B346,  
B369, B376, B381, C57, C169,  
C191, C198, D10, D43, D54,  
D239, E3, E5, E28, G27, G264,  
G324, G399, G422, G439,  
K209, K1974, L148, L331,  
L346, L351, L547, L550, I3, I13
- \@iforloop ..... f21, f22
- \@ifpackagelater ..... 499, L51
- \@ifpackageloaded .. 499, K1958, L40
- \@ifpackagewith ..... 499, L95
- \@ifframebox ..... B154, B155, B156
- \@ifframepicbox ..... B186, B187
- \@ifstar 37, d48, d383, i59, i71, i280,  
i350, m67, m77, o170, q121,  
y158, y165, y338, y347, z343,  
C56, C190, C197, D53, D329,  
F52, F142, K1856, L183, L205
- \@ifundefin@d@i d326, d327, d344, d347
- \@ifundefin@d@ii ... d326, d329, d332
- \@ifundefined .... 37, d102, d109,  
d129, d136, d158, d169, d249,  
d255, d276, d282, d309, d321,  
l1518, m3, m7, m16, m50, m62,  
m64, o64, o150, p378, r287,  
x23, y62, y79, y94, y111, E21,  
J3, J7, L38, L173, L235, I20, I44
- \@ignorefalse y4, y99, y116, y139, G360
- \@ignoretrue ..... i174,  
i187, y4, y7, z302, z305, z337, z463
- \@iiiminipage .....  
.. B284, B288, B291, B292, B293
- \@iiparbox ..... B196, B204,  
B211, B214, B215, B216, B321
- \@iiminipage ..... B287, B289
- \@iinput ..... k332, k333
- \@iiparbox ..... B210, B212
- \@iirsbox ..... B381, B390
- \@imakebox ..... B26, B41, B93
- \@imakepicbox ... B47, B48, B98, B188
- \@iminipage ..... B283, B285
- \@include ..... k161, k174, k178
- \@includeinreleasefalse .....  
..... c69, c74, c99, c104, d418
- \@includeinreleasetrue ..... c89
- \@index ..... H18, H19, H35
- \@indexfile ..... H4, H5, H14
- \@inlabelfalse .....  
... A28, A104, A184, K163, K190
- \@inlabeltrue ..... A28, A178
- \@inmatherr .. g233, A112, A142, D329
- \@inmathwarn ..... l3
- \@inpenc@test ..... O252, O319
- \@input .... k32, k90, k181, k357, F152
- \@input@ ..... k196, k359, o326, I31
- \@inputcheck a70, a191, a192, a195,  
a203, d23, d30, k3, k243, k244,  
k251, k260, k261, k264, k281,  
k282, k289, k299, k300, k303,  
L584, L585, L623, L699, L700, L707
- \@insertfalse ..... K1073, K1223,  
K1394, K1475, K1570, K1691
- \@inserttrue ..... K999, K1044,  
K1161, K1329, K1649, K1776
- \@invalidchar ..... g238
- \@iparbox ..... B195, B203, B208
- \@iirsbox .... B369, B376, B381, B382
- \@isavebox ..... B91, B92
- \@isavepicbox ..... B96, B97
- \@ishortstack ..... D44, D52
- \@istackcr ..... D54, D55
- \@itabcr ..... C57, C58
- \@item ..... A143, A156
- \@itemdepth .. A241, A243, A244, A245
- \@itemfudge ..... C38, C44, C70
- \@itemitem ..... A245, A248
- \@itemlabel ..... A44, A96, A143
- \@itempenalty ..... i16, A23, A175
- \@iwhiledim ..... f7
- \@iwhilenum ..... f3
- \@iwhileswh ..... f10
- \@ixpt ..... o591
- \@ixstackcr ..... D53
- \@killglue ..... D22, D30, D36
- \@kludgeins ..... K319,  
K320, K321, K323, K376, K377,  
K423, K424, K502, K518, K519,  
K525, K526, K527, K536,  
K552, K556, K566, K1852, K1883

File Key: a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

`\@labels` ..... [A27](#),  
[A146](#), [A147](#), [A189](#), [A206](#), [A207](#)  
`\@largefloatcheck` .....  
[G192](#), [G213](#), [G238](#), [G256](#)  
`\@lastchclass` ..... [C238](#),  
[C248](#), [C249](#), [C251](#), [C259](#), [C284](#),  
[C298](#), [C302](#), [C311](#), [C324](#), [C325](#)  
`\@latex@error` ... [d103](#), [d130](#), [d250](#),  
[d277](#), [g136](#), [g168](#), [g184](#), [g190](#),  
[g192](#), [g195](#), [g197](#), [g199](#), [g202](#),  
[g204](#), [g206](#), [g209](#), [g213](#), [g218](#),  
[g222](#), [g224](#), [g226](#), [g227](#), [g229](#),  
[g232](#), [g236](#), [g238](#), [k158](#), [k173](#),  
[l50](#), [l82](#), [o5](#), [o24](#), [o66](#), [o108](#),  
[o151](#), [o217](#), [o272](#), [p105](#), [q100](#),  
[q111](#), [r23](#), [r68](#), [r97](#), [r117](#), [r159](#),  
[r190](#), [r213](#), [r229](#), [r293](#), [r314](#),  
[r346](#), [r386](#), [r390](#), [r432](#), [r437](#),  
[r492](#), [r560](#), [r566](#), [r610](#), [r614](#),  
[r618](#), [r653](#), [r657](#), [r661](#), [r718](#),  
[r728](#), [r819](#), [r824](#), [r827](#), [r876](#),  
[r881](#), [r884](#), [r918](#), [r921](#), [r993](#),  
[r996](#), [r999](#), [r1066](#), [r1072](#), [s50](#),  
[s100](#), [v126](#), [y95](#), [y112](#), [y288](#),  
[y314](#), [y326](#), [z359](#), [A219](#), [C88](#),  
[C97](#), [F31](#), [G6](#), [G83](#), [L290](#), [L309](#),  
[L322](#), [L425](#), [L501](#), [L518](#), [L526](#),  
[L531](#), [L557](#), [L613](#), [L950](#), [L980](#), [I47](#)  
`\@latex@info` .....  
[d198](#), [d269](#), [d296](#), [d397](#), [g136](#), [l83](#)  
`\@latex@info@no@line` .... [g136](#), [K576](#)  
`\@latex@warning` ..... [g136](#), [g166](#),  
[l55](#), [x14](#), [D235](#), [G260](#), [K1996](#),  
[L652](#), [L658](#), [L742](#), [L748](#), [I22](#), [I45](#)  
`\@latex@warning@no@line` .....  
[d177](#), [g136](#), [g167](#),  
[k17](#), [k74](#), [k383](#), [x8](#), [x26](#), [x27](#),  
[y31](#), [F32](#), [K243](#), [K275](#), [K1827](#),  
[K2062](#), [L144](#), [L337](#), [L453](#), [L586](#),  
[L593](#), [L617](#), [L701](#), [L708](#), [L775](#), [L852](#)  
`\@latex@bug` ..... [g225](#), [K333](#), [K1813](#)  
`\@latex@err` ..... [g166](#),  
[K234](#), [K390](#), [K437](#), [K1874](#), [K1891](#)  
`\@lbbibitem` ..... [I3](#), [I4](#)  
`\@ldots` ..... [t465](#), [t467](#)  
`\@leftcolumn` ..... [K121](#),  
[K2203](#), [K2224](#), [K2248](#), [K2257](#)  
`\@leftmark` ..... [J16](#), [J50](#)  
`\@let@token` ..... [d368](#),  
[d371](#), [d374](#), [d382](#), [i320](#), [i321](#),  
[i328](#), [v66](#), [v79](#), [z210](#), [z212](#), [z215](#)  
`\@lign` ..... [z195](#), [z197](#)  
`\@linechar` ..... [D70](#),  
[D71](#), [D72](#), [D76](#), [D77](#), [D79](#), [D84](#),  
[D86](#), [D87](#), [D88](#), [D89](#), [D91](#), [D95](#),  
[D96](#), [D99](#), [D100](#), [D105](#), [D130](#), [D356](#)  
`\@linefnt` ..... [D37](#), [D39](#), [D70](#),  
[D123](#), [D131](#), [D162](#), [D165](#), [D363](#)  
`\@linelen` ..... [D58](#),  
[D59](#), [D83](#), [D90](#), [D99](#), [D101](#),  
[D106](#), [D107](#), [D108](#), [D116](#), [D117](#),  
[D158](#), [D161](#), [D163](#), [D164](#), [D357](#)  
`\@listctr` ..... [A202](#), [A225](#), [I9](#)  
`\@listdepth` .....  
[A23](#), [A35](#), [A38](#), [A43](#), [A99](#), [B305](#)  
`\@listfiles` .... [k59](#), [k114](#), [k389](#), [k404](#)  
`\@loadwithoptions` . [L296](#), [L302](#), [L306](#)  
`\@lowpenalty` ..... [i91](#), [O3](#)  
`\@ltab` ..... [C59](#), [C94](#)  
`\@m` ..... [b21](#), [b351](#), [b353](#),  
[b354](#), [b387](#), [b388](#), [i238](#), [i342](#),  
[i347](#), [k43](#), [k101](#), [A80](#), [D93](#), [D97](#), [I17](#)  
`\@mainaux` ..... [k5](#), [k35](#),  
[k36](#), [k93](#), [k94](#), [k145](#), [k181](#), [k206](#), [y15](#)  
`\@makebox` ..... [B11](#), [B20](#), [B25](#)  
`\@makecaption` ..... [G24](#)  
`\@makecol` ... [K261](#), [K413](#), [K460](#), [K480](#)  
`\@makefcolumn` . [K393](#), [K394](#), [K402](#),  
[K404](#), [K440](#), [K442](#), [K450](#), [K452](#),  
[K2161](#), [K2163](#), [K2179](#), [K2180](#)  
`\@makefnmark` ..... [G376](#), [G435](#)  
`\@makefntext` ..... [B333](#), [G418](#)  
`\@makeother` .. [a76](#), [a97](#), [a126](#), [d386](#),  
[d387](#), [o339](#), [o340](#), [o341](#), [o342](#),  
[o343](#), [o344](#), [o345](#), [o346](#), [o347](#),  
[o348](#), [o349](#), [y232](#), [y253](#), [y320](#),  
[y335](#), [y345](#), [L168](#), [L169](#), [L634](#), [L724](#)  
`\@makepicbox` .... [B10](#), [B19](#), [B46](#), [D212](#)  
`\@makespecialcolbox` .... [K503](#), [K522](#)  
`\@marbox` . [G320](#), [G322](#), [G326](#), [G330](#),  
[G331](#), [G355](#), [K1812](#), [K1822](#),  
[K1825](#), [K1833](#), [K1835](#), [K1836](#),  
[K1838](#), [K1839](#), [K1840](#), [K1849](#)  
`\@marginparreset` ..... [G339](#), [G346](#)  
`\@markright` ..... [J33](#), [J48](#)  
`\@maxdepth` .....  
[k57](#), [k112](#), [K91](#), [K486](#), [K514](#), [O85](#)  
`\@maxtab` ..... [C2](#), [C82](#)  
`\@medpenalty` ..... [i92](#), [O3](#)  
`\@midlist` ..... [K66](#),  
[K499](#), [K500](#), [K1027](#), [K1029](#),  
[K1141](#), [K1305](#), [K1923](#), [K1950](#)  
`\@minipagefalse` .... [A181](#), [B278](#),  
[B280](#), [B318](#), [G187](#), [G250](#), [G341](#)  
`\@minipagerestore` ..... [B306](#), [B308](#)  
`\@minipagetrue` ..... [B279](#), [G186](#)  
`\@minus` ..... [d11](#), [K2306](#),  
[K2307](#), [K2308](#), [K2311](#), [K2312](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltbibtput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- \@missingfileerror .....  
       500, k340, k351, k360, L446
- \@mkboth ..... J11, J13
- \@mklab ..... A45, A140
- \@mkpream ..... C177, C210, C238
- \@mparbottom ..... G363,  
       G364, K118, K476, K1823,  
       K1831, K1832, K1833, K1834
- \@mpargs ..... B297, B321
- \@mparswitchfalse ..... K102
- \@mpfn . B303, G399, G404, G444, G448
- \@mpfootins ..... B312,  
       B313, B316, B322, B325, B326
- \@mpfootnotetext ..... B304, B324
- \@mplistdepth ..... B305, B322
- \@multicnt .....  
       C346, C348, C349, C350, C357,  
       C358, C359, D30, D31, D33,  
       D353, D386, D388, D389, D390,  
       D391, D395, D399, D410, D414
- \@multiplelabels .....  
       k31, k89, x25, x31, y29, y35
- \@multiput ..... D28, D29
- \@multispan ..... C347, C351, C355
- \@namedef ... 37, d35, k216, l1521,  
       o99, o100, o124, p372, x28,  
       y110, y136, y294, y303, z363,  
       z364, C163, E12, E13, E18, E19,  
       E23, E24, E25, L549, O376, O377
- \@nameuse ..... 37, d36,  
       k204, k215, E23, J5, K607, K665
- \@nbitem ..... A168, A221
- \@ne ..... b16
- \@needsf@rmat ..... L332, L335, L340
- \@needsformat ..... L320, L330, L334
- \@negargfalse ..... D66
- \@negargtrue ..... D65
- \@newcommand ..... d54, d55
- \@newctr ..... m13, m15, E8
- \@newenv ..... d125, d126, d135
- \@newenva ..... d123, d124
- \@newenvb ..... d125, d126
- \@newl@bel ..... x22, y17, I10
- \@newline ..... i81, i83
- \@newlistfalse .....  
       A29, A33, A108, A182, K600, K658
- \@newlisttrue ..... A29, A33, A87
- \@next ..... b264,  
       G60, G129, G319, G320, K9,  
       K213, K311, K877, K897, K1812
- \@nextchar .....  
       C245, C246, C306, C307, C308
- \@nil ..... a161, a162,  
       c13, c19, c83, c84, d38, d39,  
       d40, d110, d362, d363, f13, f19,  
       f27, j14, l87, l108, 1975, 1979,  
       l1010, l1022, l1024, o291, o302,  
       o359, o374, o478, o481, o482,  
       o490, p304, p305, p307, p320,  
       p326, p330, p331, p367, p388,  
       p393, p473, p487, q26, q44,  
       q53, q57, r40, r356, r364, r397,  
       r1077, r1079, v41, v45, C343,  
       C344, L27, L29, L64, L65, L76,  
       L77, L88, L89, L91, L258, L262,  
       L268, L272, L400, L409, L825,  
       L830, L833, L835, L836, L851,  
       L871, L888, L942, L964, L988
- \@nmbrlistfalse ..... A33, A46, A91
- \@nmbrlisttrue ..... A225
- \@nnil ..... f13,  
       f20, f21, f22, f28, o178, o182,  
       o183, o184, o199, p133, p135,  
       p299, p301, p313, p315, p320,  
       p334, p336, p343, p354, p355,  
       p357, p388, p393, L372, L373, L380
- \@no@font@optfalse ..... q17, q129
- \@no@lnbk ..... i9, i10, i40
- \@no@pgbk ..... i7, i8, i32
- \@nobreakfalse ..... i94,  
       i96, A193, F94, F129, F157,  
       G182, K165, K192, K1150, K1316
- \@nobreaktrue ..... i95, F126, G181
- \@nocnterr ..... g191
- \@nocounterr .....  
       g191, m4, m8, m16, m62, m64, E21
- \@nodocument ..... g196, k65, k120,  
       y87, G39, G108, K156, K183, K212
- \@noitemargfalse ..... A32, A200
- \@noitemargtrue ..... A32, A143
- \@noitemerr ..... g228,  
       i218, i253, i276, A69, A81, A107
- \@noligs . y233, y254, y336, y346, y357
- \@nolnerr ... g189, i42, i87, y157, y164
- \@nomath o1, o270, s35, s42, s63, s65, s70
- \@noparitemfalse ..... A30, A145
- \@noparitemtrue ..... A30, A66
- \@noparlistfalse ..... A31, A70
- \@noparlisttrue ..... A31, A67
- \@normalcr ..... i52, i79, B277
- \@normalsize ..... L4, L5
- \@noskipsecfalse .....  
       k52, k107, F98, K158, K185
- \@noskipsectrue ..... F38, F95
- \@notdefinable d111, d112, d116, g183
- \@notprerr ..... g231, k63, k118
- \@nthm ..... E3, E4

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

`\nxttabmar` ..... [C11](#), [C21](#), [C23](#),  
[C25](#), [C63](#), [C99](#), [C100](#), [C106](#), [C107](#)  
`\obsoletefile` ..... [k382](#)  
`\oddfoot` .....  
. [J11](#), [J14](#), [J15](#), [K124](#), [K610](#), [K669](#)  
`\oddhead` . [J11](#), [J14](#), [K123](#), [K610](#), [K669](#)  
`\onefilewithoptions` .....  
. .... [L364](#), [L368](#), [L374](#),  
[L392](#), [L396](#), [L402](#), [L415](#), [L464](#), [L801](#)  
`\onelevel@sanitize` . [d388](#), [G42](#), [G111](#)  
`\onlypreamble` .....  
. .... [d41](#), [d163](#), [d165](#), [d174](#),  
[d182](#), [k125](#), [k134](#), [k155](#), [k384](#),  
[k410](#), [l23](#), [l24](#), [l61](#), [l62](#), [l66](#), [l123](#),  
[l143](#), [l187](#), [l188](#), [l202](#), [l1522](#),  
[o17](#), [o79](#), [o81](#), [o87](#), [o103](#), [o131](#),  
[o146](#), [o167](#), [o172](#), [o214](#), [o386](#),  
[p373](#), [q28](#), [q36](#), [q42](#), [q79](#), [q83](#),  
[q88](#), [q93](#), [q98](#), [q108](#), [q126](#), [q127](#),  
[q128](#), [q134](#), [q138](#), [q142](#), [r17](#), [r19](#),  
[r44](#), [r46](#), [r107](#), [r116](#), [r136](#), [r243](#),  
[r244](#), [r247](#), [r279](#), [r317](#), [r319](#),  
[r321](#), [r334](#), [r349](#), [r396](#), [r398](#),  
[r440](#), [r479](#), [r495](#), [r572](#), [r666](#),  
[r675](#), [r731](#), [r734](#), [r737](#), [r757](#),  
[r770](#), [r889](#), [r924](#), [r934](#), [r948](#),  
[r1002](#), [r1022](#), [r1026](#), [r1090](#),  
[v123](#), [v124](#), [x30](#), [H12](#), [H29](#), [L10](#),  
[L12](#), [L18](#), [L19](#), [L26](#), [L28](#), [L34](#),  
[L36](#), [L39](#), [L42](#), [L43](#), [L50](#), [L53](#),  
[L54](#), [L58](#), [L85](#), [L97](#), [L98](#), [L101](#),  
[L140](#), [L149](#), [L157](#), [L159](#), [L176](#),  
[L179](#), [L180](#), [L191](#), [L192](#), [L193](#),  
[L200](#), [L206](#), [L219](#), [L232](#), [L244](#),  
[L246](#), [L251](#), [L275](#), [L280](#), [L284](#),  
[L287](#), [L295](#), [L300](#), [L303](#), [L307](#),  
[L316](#), [L329](#), [L334](#), [L340](#), [L349](#),  
[L354](#), [L414](#), [L464](#), [L466](#), [L475](#),  
[L488](#), [L489](#), [L492](#), [L499](#), [L508](#),  
[L515](#), [L516](#), [L524](#), [L529](#), [L534](#),  
[L781](#), [L782](#), [L783](#), [L784](#), [L786](#), [I40](#)  
`\opargbegintheorem` ..... [E32](#), [E35](#)  
`\opcol` ..... [K262](#), [K270](#),  
[K394](#), [K413](#), [K442](#), [K460](#), [K465](#)  
`\options` ..... [L245](#)  
`\othm` ..... [E3](#), [E20](#)  
`\outerparskip` .....  
. .... [A8](#), [A88](#), [A117](#), [A152](#), [A222](#)  
`\outputbox` [K120](#), [K483](#), [K485](#), [K505](#),  
[K508](#), [K509](#), [K529](#), [K531](#), [K532](#),  
[K537](#), [K540](#), [K545](#), [K547](#), [K554](#),  
[K560](#), [K562](#), [K636](#), [K695](#), [K723](#),  
[K729](#), [K739](#), [K740](#), [K763](#), [K770](#),  
[K856](#), [K859](#), [K862](#), [K868](#), [K869](#),  
[K2203](#), [K2207](#), [K2208](#), [K2222](#),  
[K2228](#), [K2248](#), [K2254](#), [K2263](#)  
`\outputdblcol` ..... [K468](#),  
[K2198](#), [K2200](#), [K2244](#), [K2245](#)  
`\outputpage` .....  
. .... [K403](#), [K452](#), [K470](#), [K590](#),  
[K2232](#), [K2237](#), [K2270](#), [K2278](#)  
`\oval` ..... [D239](#), [D247](#), [D292](#)  
`\ovbtrue` ..... [D248](#), [D293](#)  
`\ovdx` ..... [D217](#),  
[D258](#), [D260](#), [D266](#), [D268](#), [D280](#),  
[D283](#), [D302](#), [D310](#), [D312](#), [D323](#),  
[D325](#), [D375](#), [D376](#), [D377](#),  
[D378](#), [D392](#), [D393](#), [D395](#), [D409](#)  
`\ovdy` ..... [D217](#),  
[D259](#), [D261](#), [D267](#), [D268](#), [D273](#),  
[D278](#), [D303](#), [D311](#), [D312](#), [D317](#),  
[D321](#), [D382](#), [D383](#), [D384](#),  
[D385](#), [D396](#), [D397](#), [D399](#), [D413](#)  
`\ovhlinefalse` ..... [D249](#)  
`\ovhlinetrue` .....  
. . [D242](#), [D246](#), [D254](#), [D260](#), [D288](#)  
`\ovhorz` ..... [D265](#),  
[D266](#), [D279](#), [D309](#), [D310](#), [D322](#)  
`\ovltrue` ..... [D248](#), [D293](#)  
`\ovri` ..... [B33](#), [D217](#), [D257](#),  
[D273](#), [D284](#), [D301](#), [D317](#), [D326](#)  
`\ovro` ..... [D217](#),  
[D257](#), [D266](#), [D267](#), [D272](#), [D278](#),  
[D279](#), [D301](#), [D310](#), [D311](#),  
[D316](#), [D321](#), [D322](#), [D333](#), [D340](#)  
`\ovrtrue` ..... [D248](#), [D293](#)  
`\ovttrue` ..... [D248](#), [D293](#)  
`\ovvert` ..... [D263](#),  
[D264](#), [D270](#), [D305](#), [D307](#), [D314](#)  
`\ovvlinefalse` ..... [D249](#)  
`\ovvlinetrue` ..... [D245](#), [D253](#), [D261](#)  
`\ovvxx` ..... [D217](#), [D251](#), [D253](#),  
[D254](#), [D258](#), [D264](#), [D265](#), [D279](#),  
[D296](#), [D298](#), [D302](#), [D307](#), [D309](#),  
[D322](#), [D372](#), [D373](#), [D374](#), [D378](#),  
[D387](#), [D388](#), [D394](#), [D395](#), [D408](#)  
`\ovvy` ..... [D217](#),  
[D252](#), [D253](#), [D254](#), [D259](#), [D266](#),  
[D270](#), [D297](#), [D298](#), [D303](#), [D310](#),  
[D314](#), [D379](#), [D380](#), [D381](#),  
[D385](#), [D387](#), [D398](#), [D399](#), [D412](#)  
`\p@pfilename` ..... [L27](#), [L29](#), [L34](#)  
`\p@papedp` ..... [K117](#), [K308](#), [K313](#),  
[K1091](#), [K1244](#), [K1841](#), [K1851](#)  
`\p@pageht` ..... [K116](#), [K309](#),  
[K313](#), [K315](#), [K316](#), [K317](#), [K321](#),  
[K1090](#), [K1243](#), [K1824](#), [K1831](#)  
`\@par` ..... [h3](#), [h5](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdc1.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- \@parboxrestore . . . . B221, B277,  
B302, B329, G19, G100, G169,  
G338, G413, K219, K601, K659
- \@parboxto . . . . . B216
- \@parmoderr . . . . g221, G58, G127, G316
- \@parse@version . . . . .  
. . . . c83, c84, L70, L76, L77,  
L88, L836, L851, L888, L964, L988
- \@parse@version@ . . . . L64, L65, L70, L82
- \@parse@version@dash . . . . L89, L91
- \@partaux . . . . k5, k157, k172, k191,  
k193, k194, k200, k209, k211, k214
- \@partlist . . . . . k153, k169, k187
- \@partswfalse . . . . . k8
- \@partswtrue . . . . . k151, k168
- \@pass@options . . . . .  
. . . . L171, L176, L177, L178, L439
- \@pboxswfalse . . . . . B219, B295
- \@pboxswtrue . . . . . B229
- \@penup . . . . . z186, z187
- \@percentchar . . . . .  
. . . . a106, L626, L628, L630,  
L632, L716, L718, L720, L722, L770
- \@picbox . . . . . D6, D13, D19, D20
- \@picht . . . . . D6, D12, D19
- \@picture . . . . . D10, D11
- \@picture@warn D103, D227, D231, D235
- \@pkgextension . . . . .  
. . . . L16, L40, L51, L95, L177,  
L286, L289, L306, L375, L403, L510
- \@plus . . . . d11, i356, F16, F185, F208,  
J54, K2306, K2307, K2308,  
K2311, K2312, K2316, K2317,  
K2318, K2322, K2323, K2324
- \@pnumwidth . . . . . F197, F220
- \@popfilename . . . . . L20, L461
- \@pr@videpackage . . . . L148, L150, L157
- \@preamble . . . . . C178, C180,  
C188, C213, C232, C234, C235,  
C239, C254, C272, C273, C310
- \@preamblecmds . . . . .  
. . . . d41, k64, k119, L1002, L1003
- \@preamerr . . . . g210, C187, C250, C331
- \@process@pti@ns . . . . .  
. . . . L218, L231, L233, L244
- \@process@ptions . . . . L205, L207, L219
- \@protected@testopt . . . . d64, d76
- \@providesfile . . . . a98, a99, L160, O538
- \@ptionlist . . . . .  
L37, L100, L204, L429, L435, L511
- \@pushfilename . . . . . L20, L416
- \@put . . . . . D238, D268, D312, D340
- \@qend . . . . . d111, d362, g187
- \@qrelax . . . . . d112, d362
- \@rc@ifdefinable d105, d107, d212, l14
- \@reargdef . . . . . d97
- \@refundefined . . . . k53, k108, x3, y27
- \@reinserts . . . . . K327, K330, K516
- \@remove@tlig . . . . . 1975, 1983
- \@remove@tlig@ . . . . . 1975, 1976
- \@remove@tlig@@ . . . . . 1976, 1979
- \@removeelement . . . . . f32, L248
- \@removefromreset . . . . .  
. . . . m46, m69, m72, m91, m92
- \@reqcolroom . . . . . K1090, K1091,  
K1094, K1096, K1097, K1102,  
K1106, K1108, K1136, K1137,  
K1243, K1244, K1248, K1251,  
K1252, K1257, K1264, K1266,  
K1298, K1299, K1410, K1412,  
K1414, K1417, K1419, K1493,  
K1496, K1499, K1504, K1506,  
K1986, K2103, K2108, K2111
- \@reset@ptions . . . . L420, L462, L467
- \@resetactivechars . . . . K575, K598, K656
- \@resethfps . . . . K1205, K1374, K2053
- \@restorepar . . . . .  
. . . . 69, h5, i287, i303, A127, A135
- \@reversemarginfalse . . . . G364, K101
- \@reversemargintrue . . . . G363
- \@rightmark . . . . . J16, J51
- \@rightskip y183, y201, A75, B250, B271
- \@rjfieldfalse . . . . . C34, C65
- \@rjfieldtrue . . . . . C113
- \@roman . . . . . m103, m109
- \@rsbox . . . . . B369, B376, B380
- \@rtab . . . . . C59, C74
- \@rule . . . . . B341, B346, B350
- \@sanitize . . . . d386, H7, H18, H24, H35
- \@savebox . . . . . B77, B84, B90
- \@savemarbox . . . . G326, G327, G330, G333
- \@savepicbox . . . . . B77, B84, B94
- \@savsf . . . . . i97, i103,  
i112, i131, i145, i157, i171, i185
- \@savsk . . . . . i97, i102,  
i113, i132, i146, i158, i172, i186
- \@scolelt . . . . . K788, K853
- \@sdblcolelt . . . . K805, K825, K854
- \@secCNTformat . . . . . F60, F111
- \@secondoftwo a88, d186, d331, d338,  
d358, k257, k296, l129, l1540,  
l1556, m156, m161, x21, J17,  
L46, L66, L78, L115, L133, L993
- \@secpenalty . . . . . i17, F36, F50
- \@sect . . . . . F54, F55
- \@seqncr . . . . . z362
- \@setckpt . . . . . k209, k216, y16

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltboutput.dtx, L=ltclass.dtx, M=ltthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- \@setfloattypecounts ..... K1074, K1224, K1395,  
K1476, K1571, K1692, K2000
- \@setfontsize ..... s70
- \@setfps ..... G34
- \@setfpsbit ..... G73, G75, G77,  
G85, G143, G146, G149, K2044
- \@setmarks .... K2214, K2216, K2231
- \@setminipage .....  
.. B307, G21, G177, G185, G352
- \@setnobreak ..... G179, G351
- \@setpar ..... 69, h3, A78
- \@setref ..... x10
- \@setsize ..... s70
- \@settab ..... C59, C81
- \@settodim ..... n17
- \@settopoint ..... n22
- \@setupverbvisiblespace .....  
..... y274, y292, y295, y307
- \@sharp .. C184, C211, C241, C256,  
C257, C277, C279, C281, C309
- \@shipoutsetup ..... K590
- \@shortstack ..... D43, D44
- \@sline ..... D61, D64, D127
- \@slowromancap ..... m110, m111
- \@spaces ..... g169
- \@specialoutput ..... K256
- \@specialpagefalse . K97, K607, K665
- \@specialpagetrue ..... J9
- \@specialstyle ..... J9, K607, K665
- \@sptoken ..... d371, d381
- \@sqrt ..... z309
- \@ssect ..... F53, F112
- \@stackcr ..... D50, D53
- \@star@or@long ..... d47, d52,  
d99, d121, d127, d153, d162, d195
- \@startcolumn ..... K263, K270, K775
- \@startdblcolumn ..... K775,  
K2236, K2239, K2276, K2282
- \@startfield .....  
.. C28, C46, C80, C92, C113, C121
- \@startline . C20, C57, C58, C71, C142
- \@startpbox ..... C181,  
C212, C242, C308, C360, C362
- \@startsection ..... F39
- \@starttoc ..... F149
- \@stopfield .. C32, C48, C74, C81,  
C113, C115, C128, C130, C142
- \@stopline ..... C30, C56, C73
- \@stpelt ..... m20, m23
- \@strip@args ..... l74
- \@svector ..... D119, D127
- \@sverb .. y284, y310, y338, y347, y350
- \@svsec ..... F57, F60, F66, F78
- \@svsechd ..... F76, F101, F121
- \@swaptwoargs ..... k318, k320, k329
- \@sxverbatim ..... y209, y296, y303
- \@tabacckludge .. l221, l223, l448, l449
- \@tabacol ..... C166, C234
- \@tabarray ..... C158, C168, C169
- \@tabclassiv ..... C168, C306
- \@tabclassz ..... C167, C258
- \@tabcr ..... C56, C61
- \@tabfbox ..... C16, C68, C70
- \@tablab ..... C60, C114
- \@tabminus ..... C60, C105
- \@tabplus ..... C60, C98
- \@tabpush .....  
C11, C65, C73, C128, C131, C133
- \@tabrj ..... C60, C112
- \@tabular ..... C162, C165, C166
- \@tabularcr ..... C168, C196
- \@tempa ... x45, x46, L553, L554, L555
- \@tempboxa .... e13, l69, n17, n18,  
A205, A211, A212, A214, B29,  
B30, B31, B32, B37, B38, B39,  
B40, B130, B160, B167, B177,  
B298, B321, B386, B387, B388,  
B395, B396, B397, B398, D162,  
D163, D233, D234, D257, D262,  
D267, D268, D301, D304, D311,  
D312, D333, D334, D339, D340,  
D400, D418, F138, F139, G322,  
G356, K305, K377, K382, K383,  
K424, K429, K430, K566, K626,  
K633, K634, K685, K692, K693,  
K721, K725, K737, K743, K750,  
K751, K752, K753, K757, K765
- \@tempcnta ... e7, r739, r740, r741,  
r742, r746, C218, C219, C220,  
C221, D67, D68, D94, D95,  
D96, D109, D110, D111, D112,  
D114, D115, D128, D129, D134,  
D136, D137, D138, D139, D140,  
D143, D145, D146, D147, D148,  
D149, D150, D151, D152, D153,  
D154, D184, D185, D186, D187,  
D188, D206, D207, D208, D209,  
D210, D211, D224, D225, D226,  
D228, D230, D232, D234, D271,  
D276, D315, D319, D335, D336,  
D337, D338, D344, D345, D346,  
D347, D348, D349, D391, D407,  
G62, G68, G70, G79, G80,  
G90, G91, G131, G137, G139,  
G152, G153, G159, G160, K16,  
K18, K20, K934, K935, K936,  
K937, K957, K958, K959, K960,

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=ltthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx



K982, K985, K1018, K1021,  
 K1132, K1294, K1574, K1577,  
 K1695, K1698, K1813, K1815,  
 K1818, K1820, K1822, K1844,  
 K2034, K2035, K2039, K2045,  
 K2049, L571, L573, L574, L575,  
 L687, L689, L690, L691, O160,  
 O165, O166, O167, O260, O262,  
 O263, O264, O271, O273, O274,  
 O275, O281, O283, O284, O285,  
 O292, O294, O295, O296, O322,  
 O324, O325, O326, O348, O350,  
 O351, O352, O358, O360, O361,  
 O362, O391, O396, O397, O398  
 \@tempcntb . . . e7, r740, r744, r746,  
 D137, D138, D139, D141, D142,  
 D143, D271, D272, D276, D277,  
 D315, D316, D319, D320, G88,  
 G89, G90, G157, G158, G159,  
 K17, K20, K21, K2045, K2046,  
 K2047, O161, O165, O392, O396  
 \@tempdima . e10, o183, o188, z173,  
 z176, z182, B43, B44, B159,  
 B160, B165, B166, B167, B169,  
 B220, B221, B296, B300, B353,  
 B356, B357, B384, B386, B392,  
 B395, C35, C36, C37, C76, C77,  
 C78, C79, C206, C207, D90,  
 D91, D93, D94, D95, D96, D97,  
 D98, D223, D224, D225, D234,  
 D258, D259, D263, D264, D302,  
 D303, D305, D307, D336, D338,  
 D343, D344, D345, F190, F191,  
 F213, F214, F227, G196, G198,  
 G218, G220, G258, G259,  
 G260, K229, K230, K231, K487,  
 K489, K535, K537, K538, K543,  
 K548, K552, K557, K561, K917,  
 K920, K940, K950, K962, K972,  
 K1637, K1638, K1641, K1642,  
 K1762, K1763, K1767, K1768,  
 K1823, K1824, K1825, K1826,  
 K1829, K1832, K1835, K1837,  
 K2152, K2153, K2155, K2156  
 \@tempdimb . . . . . e10, o184,  
 o189, o498, o502, p133, p134,  
 p391, p414, p415, p424, p425,  
 p429, p447, p450, p453, p455,  
 B223, B224, B354, B357, B385,  
 B387, B393, B396, D91, D92,  
 D253, D255, D256, D298, D299,  
 D300, D331, D332, D341, D342,  
 K940, K941, K942, K943, K950,  
 K962, K963, K964, K965, K972  
 \@tempdimc . e10, p408, p409, p411,  
 p412, p414, p415, B355, B356, B357  
 \@tempskipa . . . . .  
 . . e14, i44, i47, i48, i235, i242,  
 i244, i247, p135, p136, A116,  
 A117, A118, A150, A152, A153,  
 A154, A222, A223, A224, F42,  
 F44, F45, F50, F62, F63, F88,  
 F89, F91, F103, F104, F113,  
 F114, K1872, K1873, K1875, K1883  
 \@tempskipb . . . e14, i194, i196, i198,  
 i201, i203, i213, i233, i235, i236,  
 i240, i242, i244, i245, i268, i271  
 \@tempswafalse . . . . . a78,  
 b251, k185, o58, o547, r281,  
 r336, r400, r481, r1065, r1071,  
 y18, y224, y245, K988, K1024,  
 K1580, K1701, L549, L564, I13  
 \@tempswatru . . . . . a79,  
 b257, k183, k188, o61, o548,  
 o549, o552, o555, r284, r339,  
 r403, r484, r1028, y42, y229,  
 y250, K1582, K1605, K1703,  
 K1728, K2113, K2130, L546, I13  
 \@temptokena e16, y54, y58, y67, y80,  
 y81, J26, J27, J34, J35, J48, J49  
 \@testdef . . . . . y17, y40  
 \@testfalse . . . . . K12, K14, K15  
 \@testfp . . . . . K882, K902,  
 K938, K961, K2037, K2166, K2183  
 \@testopt . . . . . d18, d54,  
 d74, d78, d123, i7, i8, i9, i10, z349  
 \@testpach . . . . . C246, C324  
 \@testpatch . . . . . C324  
 \@testtrue . . . . . K13, K21, K356,  
 K885, K904, K944, K966, K2041  
 \@testwrongwidth . . . . . K345,  
 K883, K939, K1112, K1426, K1631  
 \@text@composite . . . . . 174, I1017, I1022  
 \@text@composite@x . . . . . 174  
 \@textbottom . . . . .  
 J54, J56, K511, K549, K563, K572  
 \@textfloatsheight . . . . .  
 . K476, K1087, K1089, K1139,  
 K1140, K1145, K1240, K1242,  
 K1302, K1304, K1310, K1986  
 \@textmin G285, G286, G299, G300,  
 K112, K1089, K1093, K1096,  
 K1097, K1242, K1247, K1251,  
 K1252, K1414, K1499, K1598,  
 K1600, K1616, K1720, K1722,  
 K1740, K2094, K2096, K2098  
 \@textsubscript . . . G387, G388, G395  
 \@textsuperscript . G377, G379, G380

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

- \@texttop . J54, J56, K507, K530, K572
- \@tf@r . . . . . f25, f26
- \@tfor . . . . . f25, k258, k297, k391, v71,  
B52, C244, D250, D294, G63, G132
- \@tforloop . . . . . f27, f28, f30
- \@thanks . . . . . F11, F34
- \@thefnmark . . . . . B331,  
G376, G377, G400, G405,  
G415, G424, G429, G440, G445
- \@thefoot . . . . . K124, K610,  
K613, K640, K669, K672, K699
- \@thehead . . . . . K123, K610,  
K612, K630, K669, K671, K689
- \@themargin . . . . . K74, K611,  
K613, K625, K670, K672, K684
- \@themark . . . . . J25, J26, J33, J34, J49, J52
- \@thirdofthree . . . . . d190, l195
- \@thm . . . . . E12, E18, E24, E26
- \@thmcounter . . . . . E11, E17, E33
- \@thmcountersep . . . . . E10, E33
- \@title . . . . . F7, F31
- \@tocrmarg . . . . . F186, F209
- \@toodeep . . . . . g203, A36, A232, A243
- \@toplist . . . . . K64, K384, K385, K431,  
K432, K716, K722, K732, K733,  
K1025, K1037, K1921, K1948
- \@topnewpage . . . . . K199
- \@topnum . . . . . G271, K105,  
K1022, K1023, K1037, K1041,  
K1049, K1458, K1463, K1551,  
K1558, K1912, K1939, K1980
- \@toproom . . . . . G273, K106,  
K1025, K1037, K1913, K1940
- \@topsep . . . . . A1, A71, A73, A171
- \@topsepadd . . . . . A1, A59, A61, A71, A124
- \@totalleftmargin . . . . .  
. . . . . y220, y242, A9, A53,  
A54, B249, B270, C35, C64, C69
- \@trivlist . . . . . A48, A57, A92
- \@tryfcolumn . . . . . K778,  
K798, K816, K832, K2167, K2184
- \@trylist . . . . . K841, K844, K877, K897, K919
- \@twoclasseserror . . . . . L277, L530
- \@twocolumnfalse . . . . . K99, K147
- \@twocolumntrue . . . . . K206
- \@twoloadclasserror . . . . . L460, L525
- \@twosidefalse . . . . . K100
- \@typein . . . . . d17, d18, d25, d33
- \@typeset@protect . . . . .  
d77, d217, d224, d226, l26, l32,  
l208, l216, s71, y103, y121, O254
- \@uclclist . . . . . l1439, l1440, l1487, O461
- \@undefined . . . . . a68, a69, a108, a109,  
a110, a131, a139, a147, a154,  
a205, a209, a235, a242, a326,  
a327, b65, b81, b105, b106,  
b121, b122, b127, b136, b149,  
b184, b189, b222, b223, b235,  
b245, b280, b448, b491, b537,  
b538, c49, c57, d19, d197, d301,  
d315, d333, d340, g28, i372,  
k58, k59, k113, k114, k245,  
k273, k274, k275, k276, k278,  
k283, k329, l193, l195, l330,  
l332, l334, l336, l338, l340, l342,  
l344, l346, l348, l367, l369, l371,  
l452, l691, l694, m170, o410,  
o443, o507, o514, q4, q5, q6,  
q7, q8, q9, q10, q11, q12, q13,  
q14, q15, q16, q17, q18, q19,  
q20, r597, r704, r804, s44, t14,  
t42, t57, v105, x56, x57, y74,  
y75, y76, y77, y268, y305, y306,  
y307, y308, z237, z240, z283,  
z296, B21, B85, B149, B205,  
B347, B377, D290, D291, F224,  
G5, G394, G395, K36, K368,  
K369, L4, L82, L450, L476,  
L664, L667, L678, L679, L680,  
L681, L682, L683, L684, L755,  
L758, L774, L794, L801, N2,  
N13, N14, N15, N27, N28, N74,  
N84, N173, N181, N189, N197,  
N224, N225, N226, N227, N228,  
N229, N230, N231, N232, N233,  
N234, N235, N236, N237, N238,  
N239, N240, N241, N242, N248,  
O10, O18, O25, O40, O59,  
O68, O75, O93, O94, O201,  
O214, O226, O247, O248, O249,  
O278, O280, O319, O320, O339,  
O340, O341, O342, O343, O344,  
O345, O346, O347, O364, O380,  
O381, O382, O430, O431, O491,  
O527, O528, O529, O530, O531, I33
- \@unexpandable@protect . . . . .  
d194, d229, d235, d240, k139, C240
- \@unknownoptionerror . . . . . L471, L500, L513
- \@unprocessedoptions . . . . .  
. . . . . L243, L305, L447, L451, L515
- \@unused . . . . . d4, g15, g32, g59, k3, L779
- \@unusedoptionlist . . . . . k16, k18,  
k73, k75, L11, L196, L197, L249
- \@upline . . . . . D155, D156, D162
- \@upordown . . . . . D75, D76, D84, D105, D131
- \@upvector . . . . . D126, D162
- \@use@option . . . . .  
. . . . . L214, L226, L236, L238, L247

File Key: a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx



- \@use@text@encoding . . . . . [1148](#), [11793](#)
- \@vbsphack . . . . . [i193](#)
- \@verb . . . . . [y338](#), [y347](#), [y350](#)
- \@verbatim . . . . . [y214](#), [y260](#), [y294](#), [y303](#)
- \@verbvisiblespacebox . . . . .  
     . . . . . [y279](#), [y280](#), [y283](#), [y308](#)
- \@vereq . . . . . [t418](#), [t419](#)
- \@viipt . . . . . [o590](#)
- \@viipt . . . . . [o589](#)
- \@vipt . . . . . [o588](#)
- \@vline . . . . . [D60](#), [D155](#)
- \@vobeyspaces . . . . .  
     . . . . . [y207](#), [y260](#), [y292](#), [y296](#), [y350](#)
- \@vpt . . . . . [o587](#)
- \@vspace . . . . . [i280](#)
- \@vspacer . . . . . [i280](#)
- \@vtryfc . . . . . [K847](#), [K855](#)
- \@vvector . . . . . [D118](#), [D126](#)
- \@warning . . . . . [g166](#)
- \@wckptelt . . . . . [k210](#), [k213](#)
- \@whiledim . . . . . [f7](#), [D36](#), [D83](#)
- \@whilenoop . . . . . [f3](#)
- \@whilenum . . . . . [f3](#), [C220](#), [D31](#),  
     [D185](#), [D187](#), [D207](#), [D210](#), [D407](#)
- \@whilesw . . . . . [f10](#), [K264](#), [K394](#),  
     [K403](#), [K441](#), [K451](#), [K2237](#), [K2277](#)
- \@whileswnoop . . . . . [f10](#)
- \@wholewidth . . . . . [B115](#), [B117](#), [B118](#),  
     [B120](#), [B122](#), [B123](#), [B124](#), [B125](#),  
     [D2](#), [D38](#), [D40](#), [D42](#), [D157](#),  
     [D160](#), [D198](#), [D205](#), [D274](#), [D281](#),  
     [D318](#), [D324](#), [D365](#), [D366](#), [D404](#)
- \@width . . . . . [b394](#),  
     [d11](#), [i352](#), [l288](#), [l291](#), [p146](#),  
     [t579](#), [B120](#), [B122](#), [B173](#), [B180](#),  
     [B357](#), [B401](#), [C176](#), [C207](#), [C323](#),  
     [C342](#), [D107](#), [D157](#), [D160](#), [D177](#),  
     [D184](#), [D198](#), [D205](#), [D274](#), [D318](#),  
     [D404](#), [G371](#), [K1851](#), [K2226](#), [K2260](#)
- \@wrglossary . . . . . [H25](#), [H30](#)
- \@wrindex . . . . . [H8](#), [H13](#)
- \@writeckpt . . . . . [k198](#), [k207](#)
- \@writefile . . . . . [k30](#), [k88](#), [y61](#), [F177](#)
- \@writesetup . . . . . [K590](#)
- \@wrong@font@char [1159](#), [o411](#), [o445](#), [o458](#)
- \@wtryfc . . . . . [K857](#), [K867](#)
- \@x@protect . . . . . [d80](#), [d216](#)
- \@x@sfs . . . . . [G434](#), [G436](#)
- \@xDeclareMathDelimiter . . . . . [r769](#), [r890](#)
- \@xaddvskip . . . . . [i193](#), [i214](#)
- \@xarg . . . . . [D57](#), [D60](#), [D65](#),  
     [D69](#), [D70](#), [D106](#), [D108](#), [D113](#),  
     [D114](#), [D118](#), [D124](#), [D132](#), [D350](#)
- \@xargarraycr . . . . . [C193](#), [C202](#), [C206](#)
- \@xargdef . . . . . [d55](#)
- \@xarraycr . . . . . [C190](#), [C191](#)
- \@xbitor . . . . . [K15](#), [K17](#)
- \@xcentercr . . . . . [y158](#), [y165](#), [y169](#)
- \@xdblarg . . . . . [d384](#)
- \@xdblfloat . . . . . [G264](#)
- \@xdim . . . . . [D26](#), [D32](#), [D34](#), [D354](#),  
     [D408](#), [D409](#), [D410](#), [D411](#), [D417](#)
- \@xeqncr . . . . . [z341](#)
- \@exnoop . . . . . [C214](#), [C224](#)
- \@expast . . . . . [C215](#), [C216](#)
- \@xfloat . . . . . [G28](#), [G29](#), [G34](#), [G266](#)
- \@xfootnote . . . . . [G399](#), [G402](#)
- \@xfootnotemark . . . . . [G422](#), [G426](#)
- \@xfootnotenext . . . . . [G439](#), [G442](#)
- \@xhline . . . . . [C336](#), [C337](#)
- \@xifnch . . . . . [d372](#), [d382](#)
- \@xiipt . . . . . [o594](#), [t134](#), [t136](#), [t137](#)
- \@xipt . . . . . [o593](#), [t133](#)
- \@xivpt . . . . . [o595](#), [t135](#), [t137](#)
- \@xmpar . . . . . [G324](#), [G325](#)
- \@xnewline . . . . . [i60](#), [i61](#), [i72](#), [i73](#), [i80](#)
- \@xnext . . . . . [K10](#), [K11](#)
- \@xnthm . . . . . [E5](#), [E6](#)
- \@xobeysp [i330](#), [y208](#), [y209](#), [y276](#), [y280](#)
- \@xprocessOptions . . . . . [L205](#), [L220](#), [L232](#)
- \@xpt . . . . . [o592](#), [t132](#), [t135](#), [t136](#)
- \@xssect . . . . . [F86](#), [F87](#), [F123](#)
- \@xtabcr . . . . . [C56](#), [C57](#)
- \@xtabularcr . . . . . [C197](#), [C198](#)
- \@xthm . . . . . [E28](#), [E29](#)
- \@xtryfc . . . . . [K844](#), [K872](#)
- \@xtypein . . . . . [d18](#), [d20](#), [d27](#)
- \@xverbatim . . . . . [y209](#), [y260](#)
- \@xvipt . . . . . [o596](#), [t136](#), [t138](#)
- \@xxDeclareMathDelimiter . . . . . [r754](#), [r758](#)
- \@xxpt . . . . . [o597](#), [t137](#), [t138](#)
- \@xxvpt . . . . . [o598](#), [t138](#)
- \@xxxii . . . . . [e2](#), [l419](#), [l421](#), [G89](#),  
     [G158](#), [K879](#), [K880](#), [K899](#), [K900](#),  
     [K935](#), [K936](#), [K958](#), [K959](#), [K2003](#)
- \@xympar . . . . . [G328](#), [G332](#), [G354](#)
- \@yarg . . . . . [D57](#),  
     [D61](#), [D65](#), [D66](#), [D75](#), [D113](#),  
     [D119](#), [D126](#), [D128](#), [D155](#), [D350](#)
- \@yargarraycr . . . . . [C194](#), [C204](#), [C208](#)
- \@yargd@f . . . . . [d82](#)
- \@yargdef . . . . . [d59](#), [d69](#), [d82](#), [d98](#)
- \@ydim . . . . . [D27](#), [D32](#), [D34](#), [D355](#),  
     [D412](#), [D413](#), [D414](#), [D415](#), [D416](#)
- \@yeqncr . . . . . [z341](#)
- \@ympar . . . . . [G324](#), [G329](#)
- \@ynthm . . . . . [E5](#), [E14](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- $\backslash$ @ythm ..... E28, [E29](#)  
 $\backslash$ @tryfc ..... K890, K909, [K913](#)  
 $\backslash$ @yyarg D65, D66, D67, D70, D132, [D350](#)  
 $\backslash$ @ztryfc ..... K918, [K929](#)  
 $\backslash$ [ ..... o345, [z243](#), z301, [z382](#), O422  
 $\backslash$ \ ..... 71, a45, a46,  
a74, a247, a248, a249, a250,  
a253, a260, a261, a262, a263,  
a266, a273, a274, a275, a276,  
a279, a286, a292, a293, a297,  
a299, a300, a304, a309, a310,  
a313, a319, b13, d193, d386,  
g227, [i52](#), i378, k390, k405,  
l554, o333, t221, y179, y183,  
y187, y211, z323, z442, B277,  
B385, B387, C61, C158, C168,  
C182, D50, N259, N411, O407  
 $\backslash$ { a3, a7, a74, b2, b13, g22, l305, l556,  
o334, t219, y210, z59, z154, O410  
 $\backslash$ } ..... a8, a74, b3, b13, g21, l306,  
l557, o335, t220, y210, z59, O411  
 $\backslash$ ] .. b440, o346, [z243](#), z302, [z406](#), O423  
 $\backslash$ ^ ..... a63, a72, a75, a119, a330,  
b7, b9, b11, b14, b359, b360,  
b374, b375, d5, d387, i378,  
i380, i382, l229, l284, l379, l450,  
l460, l552, l635, l642, l646, l651,  
l656, l661, l668, l674, l675, l681,  
l686, l741, l1178, l1195, l1199,  
l1206, l1210, l1215, l1220, l1225,  
l1232, l1238, l1239, l1245, l1250,  
l1262, l1263, l1280, l1281, l1288,  
l1289, l1303, l1304, l1305, l1334,  
l1335, l1356, l1357, l1358, l1359,  
o331, o332, o337, y48, y57,  
L578, L579, L580, L663, L666,  
L669, L694, L695, L696, L754,  
L757, L760, O188, O189, O190,  
O191, O192, O193, O194, O195,  
O196, O408, O414, O415, O416,  
O417, O451, O452, O453, O454,  
O455, O456, O457, O458, O459  
 $\backslash$ \_ ..... a75, b8, b14,  
d387, l311, t224, z223, z224, O409  
 $\backslash$ ^ ..... l230, l380, l414, l448, l458,  
l571, l633, l640, l644, l649, l654,  
l659, l666, l670, l671, l679, l684,  
l742, l784, l1176, l1197, l1204,  
l1208, l1213, l1218, l1223, l1230,  
l1234, l1235, l1243, l1248, o347,  
s152, y351, B245, B266, C60, O424  
 $\backslash$ | . l555, m135, m146, t534, t535, O425  
 $\backslash$ ~ ..... a75, b10, b14,  
d387, g20, i332, l237, l285, l381,  
l461, l553, l636, l648, l652, l662,  
l678, l682, l743, l1179, l1196,  
l1200, l1212, l1216, l1226, l1242,  
l1246, l1290, l1291, l1292, l1344,  
l1345, y286, y312, y355, O412  
 $\backslash$ \\_ ..... a74, a91,  
b13, b359, b377, d386, g19, g20,  
g21, g22, g25, i331, o330, o521,  
o557, o582, t222, y207, y208,  
y291, E36, E38, L162, O402, I17  

**A**

 $\backslash$ A ..... O185, O427, O448  
 $\backslash$ a ..... [l221](#), [C1](#), O176, O428, O439  
 $\backslash$ AA ..... [b365](#), l238, l422, l520  
 $\backslash$ aa ..... [b365](#), l243, l416, l530  
 $\backslash$ abovedisplayshortskip .. b340, z450  
 $\backslash$ abovedisplayskip ..... b339,  
z443, z445, z447, z448, z449, z450  
 $\backslash$ accent ..... l71, l390, l417, l473, l754  
 $\backslash$ accent@spacefactor ..... l70, l71, l72  
 $\backslash$ active ..... a64, a119, a330,  
b10, b11, b374, b375, b377,  
y207, y208, y285, y291, y311,  
y353, z208, z223, K584, L578,  
L579, L580, L663, L666, L669,  
L694, L695, L696, L754, L757, L760  
 $\backslash$ active@math@prime .. [z207](#), z208, K588  
 $\backslash$ acute ..... t477  
 $\backslash$ add@accent ..... l65, [l67](#)  
 $\backslash$ add@percent@to@temptokena .....  
..... [y48](#), y64, y66, y75  
 $\backslash$ add@unicode@accent ..... l996, l1000  
 $\backslash$ add\_to\_callback ..... 533, [N648](#)  
 $\backslash$ addcontentsline F70, F80, [F159](#), G16  
 $\backslash$ addpenalty .... [i220](#), A124, A170,  
A175, F50, K338, K1153, K1319  
 $\backslash$ addto@hook ..... o116,  
o118, [o586](#), r263, r359, r363,  
r380, r504, r510, r518, r534,  
r537, r540, r1037, r1044, r1047  
 $\backslash$ addtocontents .... F164, F171, [F174](#)  
 $\backslash$ addtocounter ..... 155, [m6](#), m18  
 $\backslash$ addtolength .... 162, [n16](#), z445, z447  
 $\backslash$ addtoversion ..... q20, [q139](#)  
 $\backslash$ addvspace ..... [i207](#), y169, A124,  
A171, A172, A176, A224, F50  
 $\backslash$ adjdemerits ..... b319  
 $\backslash$ AE ..... l239,  
l395, l521, l759, l1075, l1376, O480  
 $\backslash$ ae ..... l244,  
l398, l531, l763, l1081, l1377, O480

**File Key:** a=lttdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdc1.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- `\afterassignment` . . . . . [b390](#), [b393](#),  
                                  [d230](#), [d236](#), [l210](#), [l218](#), [o261](#), [z186](#)
  - `\aftergroup` . . . . .  
                                  . . . [o55](#), [o275](#), [p156](#), [p222](#), [r114](#),  
                                  [r121](#), [r129](#), [v47](#), [y289](#), [y315](#),  
                                  [B103](#), [K604](#), [K605](#), [K662](#), [K663](#)
  - `\aleph` . . . . . [t278](#)
  - `\alloc@` . . . . . [b90](#), [b91](#),  
                                  [b92](#), [b93](#), [b94](#), [b95](#), [b96](#), [b97](#),  
                                  [b98](#), [b99](#), [b226](#), [o14](#), [N20](#), [N24](#), [N36](#)
  - `\allocationnumber` . . . . .  
                                  . . . . . [b37](#), [b57](#), [b69](#), [b71](#), [b143](#),  
                                  [b144](#), [b145](#), [b195](#), [b196](#), [b228](#),  
                                  [b229](#), [b230](#), [b241](#), [b242](#), [b243](#),  
                                  [b260](#), [b266](#), [b272](#), [b273](#), [b286](#),  
                                  [b287](#), [b288](#), [C4](#), [C9](#), [N50](#), [N51](#),  
                                  [N52](#), [N90](#), [N204](#), [O44](#), [O45](#), [O46](#)
  - `\allowbreak` . . . . .  
                                  [b397](#), [d422](#), [d423](#), [d442](#), [d444](#), [z40](#)
  - `\Alpha` . . . . . [155](#), [m106](#)
  - `\alpha` . . . . . [155](#), [m105](#)
  - `\alpha` . . . . . [t238](#)
  - `\alpha@elt` . . . . .  
                                  [r45](#), [r267](#), [r454](#), [r556](#), [r1036](#), [r1037](#)
  - `\alpha@list` . . . . .  
                                  [r41](#), [r43](#), [r276](#), [r442](#), [r454](#), [r499](#),  
                                  [r554](#), [r555](#), [r1032](#), [r1038](#), [r1039](#)
  - `\amalg` . . . . . [t344](#)
  - `\and` . . . . . [384](#), [F14](#), [F27](#)
  - `\angle` . . . . . [t306](#)
  - `\approx` . . . . . [t386](#)
  - `\arabic` . . . . . [155](#), [m102](#), [E33](#)
  - `\arccos` . . . . . [z13](#)
  - `\arcsin` . . . . . [z10](#)
  - `\arctan` . . . . . [z16](#)
  - `\arg` . . . . . [z26](#)
  - `\array` . . . . . [C156](#)
  - `\arraycolsep` . . . . .  
                                  [z326](#), [z327](#), [z455](#), [z456](#), [C234](#), [C314](#)
  - `\arrayrulewidth` . . . . .  
                                  . . . . . [C300](#), [C314](#), [C322](#), [C323](#),  
                                  [C335](#), [C339](#), [C342](#), [C352](#), [C354](#)
  - `\arraystretch` . . . . . [C174](#), [C175](#), [C318](#)
  - `\Arrowvert` . . . . . [t530](#)
  - `\arrowvert` . . . . . [t528](#)
  - `\asciispace` . . . . .  
                                  [y267](#), [y269](#), [y272](#), [y275](#), [y276](#), [y305](#)
  - `\ast` . . . . . [t202](#), [t360](#)
  - `\asympt` . . . . . [t410](#)
  - `\AtBeginDocument` . . . . .  
                                  . . . . . [k54](#), [k109](#), [L485](#), [I34](#), [I48](#)
  - `\AtBeginDvi` . . . . . [K86](#)
  - `\AtEndDocument` . . . . . [y9](#), [L485](#)
  - `\AtEndOfClass` . . . . . [z381](#), [L485](#)
  - `\AtEndOfPackage` . . . . . [L243](#), [L305](#), [L485](#)
  - `\atopwithdelims` . . . . . [z57](#), [z58](#), [z59](#)
  - `\attribute` . . . . . [N78](#)
  - `\attributedef` . . . . . [N78](#), [N210](#)
  - `\attributezero` . . . . . [N210](#)
  - `\author` . . . . . [384](#), [F8](#), [F24](#), [F32](#)
- B**
- `\b` . . . . . [l231](#), [l386](#), [l469](#), [l750](#), [l1187](#)
  - `\backslash` . . . . . [t221](#), [t551](#)
  - `\bar` . . . . . [t481](#)
  - `\baselineskip` . . . . .  
                                  . . . . . [b358](#), [b388](#), [b424](#), [p140](#), [p141](#),  
                                  [p142](#), [p144](#), [p145](#), [t471](#), [z158](#),  
                                  [z159](#), [z178](#), [z184](#), [z188](#), [B254](#),  
                                  [B273](#), [C186](#), [D47](#), [D167](#), [K242](#),  
                                  [K273](#), [K622](#), [K637](#), [K681](#), [K696](#)
  - `\baselinestretch` . . . . .  
                                  . . . . . [o252](#), [p118](#), [p119](#), [p138](#), [p199](#)
  - `\batchmode` . . . . . [k369](#), [k370](#), [q106](#), [O500](#), [O521](#)
  - `\begin` . . . . . [g197](#), [g199](#), [k314](#),  
                                  [p7](#), [t4](#), [u4](#), [y88](#), [y89](#), [z386](#), [z398](#),  
                                  [F14](#), [F17](#), [L314](#), [M3](#), [O385](#), [O389](#)
  - `\belowdisplayshortskip` . . . . . [b342](#), [z449](#)
  - `\belowdisplayskip` . . . . . [b341](#), [z448](#)
  - `\best@size` . . . . . [p392](#), [p416](#), [p422](#), [p428](#)
  - `\beta` . . . . . [t239](#)
  - `\bezier` . . . . . [357](#), [D368](#),  
                                  [D369](#), [D423](#), [D424](#), [D439](#), [D441](#)
  - `\bfdefault` . . . . . [s15](#), [t84](#)
  - `\bfseries` . . . . .  
                                  . . . . . [s13](#), [s14](#), [v19](#), [x13](#), [E36](#), [E38](#), [I20](#)
  - `\bgroup` . . . . . [b372](#)
  - `\bibcite` . . . . . [I7](#), [I9](#), [I10](#)
  - `\bibdata` . . . . . [I25](#), [I29](#)
  - `\bibitem` . . . . . [I3](#)
  - `\bibliography` . . . . . [417](#), [I27](#)
  - `\bibliographystyle` . . . . . [417](#), [I32](#)
  - `\bibstyle` . . . . . [I25](#), [I37](#)
  - `\Big` . . . . . [t584](#), [t587](#), [t596](#), [t598](#), [z44](#), [z45](#), [z46](#)
  - `\big` . . . . . [t585](#), [t597](#), [z41](#)
  - `\bigbreak` . . . . . [b404](#), [d424](#), [d445](#)
  - `\bigcap` . . . . . [t314](#)
  - `\bigcirc` . . . . . [t357](#)
  - `\bigcup` . . . . . [t315](#)
  - `\Bigg` . . . . . [t591](#), [t600](#), [z50](#), [z51](#), [z52](#)
  - `\bigg` . . . . . [t589](#), [t599](#), [z47](#), [z48](#), [z49](#)
  - `\Biggl` . . . . . [z50](#)
  - `\biggl` . . . . . [z47](#)
  - `\Biggm` . . . . . [z51](#)
  - `\biggm` . . . . . [z48](#)
  - `\Biggr` . . . . . [z52](#)
  - `\biggr` . . . . . [z49](#)
  - `\Bigl` . . . . . [z44](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltboutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

<code>\bigl</code>	z41	<code>\bx@DD</code>	K40
<code>\Bigm</code>	z45	<code>\bx@E</code>	K30, K57
<code>\bigm</code>	z42	<code>\bx@EE</code>	K40
<code>\bigodot</code>	t322	<code>\bx@F</code>	K31, K58
<code>\bigoplus</code>	t321	<code>\bx@FF</code>	K41
<code>\bigotimes</code>	t320	<code>\bx@G</code>	K31, K58
<code>\Bigr</code>	z46	<code>\bx@GG</code>	K41
<code>\bigr</code>	z43	<code>\bx@H</code>	K31, K58
<code>\bigskip</code>	b409, i310	<code>\bx@HH</code>	K41
<code>\bigskipamount</code>	b408, i312, i313, G367	<code>\bx@I</code>	K31, K58
<code>\bigskipcup</code>	t325	<code>\bx@II</code>	K41
<code>\bigtriangledown</code>	t330, t331	<code>\bx@J</code>	K31, K58
<code>\bigtriangleup</code>	t329, t332	<code>\bx@JJ</code>	K41
<code>\biguplus</code>	t313	<code>\bx@K</code>	K32, K59
<code>\bigvee</code>	t311	<code>\bx@KK</code>	K42
<code>\bigwedge</code>	t312	<code>\bx@L</code>	K32, K59
<code>\binoppenalty</code>	b310	<code>\bx@LL</code>	K42
<code>\bm@b</code>	B37	<code>\bx@M</code>	K32, K59
<code>\bm@c</code>	B37	<code>\bx@MM</code>	K42
<code>\bm@l</code>	B37	<code>\bx@N</code>	K32, K59
<code>\bm@r</code>	B37	<code>\bx@NN</code>	K42
<code>\bm@s</code>	B37	<code>\bx@O</code>	K33, K60
<code>\bm@t</code>	B37	<code>\bx@OO</code>	K43
<code>\bmod</code>	z35	<code>\bx@P</code>	K33, K60
<code>\boldmath</code>	j14, s63	<code>\bx@PP</code>	K43
<code>\bordermatrix</code>	z172	<code>\bx@Q</code>	K33, K60
<code>\bot</code>	t291	<code>\bx@QQ</code>	K43
<code>\botfigrule</code>	K742, K2325	<code>\bx@R</code>	K33, K60
<code>\botmark</code>	J50, K647, K706	<code>\bx@RR</code>	K43
<code>\bottomfraction</code>	G275, K2294	<code>\bx@S</code>	K38
<code>\bowtie</code>	t443	<code>\bx@SS</code>	K44
<code>\Box</code>	s106	<code>\bx@T</code>	K38
<code>\boxmaxdepth</code>	b333, D247, D292, D331, K486, K506, K546, K715, K724, K764	<code>\bx@TT</code>	K44
<code>\brace</code>	z59	<code>\bx@U</code>	K38
<code>\braced</code>	t514, t518, t519, t521, t523	<code>\bx@UU</code>	K44
<code>\bracelu</code>	t516, t520, t522	<code>\bx@V</code>	K38
<code>\bracerd</code>	t515, t520, t522	<code>\bx@VV</code>	K44
<code>\braceru</code>	t517, t519, t523	<code>\bx@W</code>	K39
<code>\bracevert</code>	t569	<code>\bx@WW</code>	K45
<code>\brack</code>	z58	<code>\bx@X</code>	K39
<code>\break</code>	b397, b402, d425, d446, i89	<code>\bx@XX</code>	K45
<code>\breve</code>	t482	<code>\bx@Y</code>	K39
<code>\brokenpenalty</code>	b315, o540	<code>\bx@YY</code>	K45
<code>\buildrel</code>	t430, z149	<code>\bx@Z</code>	K39
<code>\bullet</code>	t346	<code>\bx@ZZ</code>	K25, K45, K55
<code>\bx@A</code>	K30, K57		
<code>\bx@AA</code>	K40		
<code>\bx@B</code>	K30, K57		
<code>\bx@BB</code>	K40		
<code>\bx@C</code>	K30, K57		
<code>\bx@CC</code>	K40		
<code>\bx@D</code>	K30, K57		

## C

<code>\c</code>	l232, l332, l334, l336, l338, l340, l342, l344, l346, l348, l369, l371, l389, l453, l472, l597, l599, l624, l626, l639, l665, l692, l695, l696, l697, l698, l699, l700, l701, l702, l703, l753, l1189, l1203, l1229, l1286, l1287, l1306, l1307,
-----------------	--

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdc1.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltbput.dtx, L=ltclass.dtx, M=ltthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- [11310](#), [11311](#), [11316](#), [11317](#), [11328](#),  
[11329](#), [11336](#), [11337](#), [11340](#), [11341](#)  
`\c@bottomnumber` .. [G269](#), [G274](#), [K2292](#)  
`\c@dbltopnumber` .....  
..... [G268](#), [G283](#), [G297](#), [K2299](#)  
`\c@enumi` ..... [A227](#)  
`\c@enumii` ..... [A227](#), [A227](#)  
`\c@enumiv` ..... [A227](#)  
`\c@equation` ..... [z303](#), [z336](#), [z462](#)  
`\c@errorcontextlines` ..... [g163](#)  
`\c@footnote` ..... [F12](#), [G373](#), [G428](#)  
`\c@mpfootnote` ..... [B303](#), [G375](#)  
`\c@ncel` ..... [t422](#), [t423](#)  
`\c@page` .... [w3](#), [w6](#), [w7](#), [K138](#), [K1818](#)  
`\c@secnumdepth` .. [F56](#), [F71](#), [F81](#), [F140](#)  
`\c@tocdepth` ..... [F140](#), [F184](#), [F207](#)  
`\c@topnumber` ..... [G267](#), [G271](#), [K2288](#)  
`\c@totalnumber` ... [G270](#), [G276](#), [K2295](#)  
`\cal` ..... [s153](#)  
`\calculate@math@sizes` ... [o494](#), [p173](#)  
`\call_callback` ..... [534](#), [N626](#)  
`\callback.register` ..... [N555](#)  
`\callback_descriptions` ... [534](#), [N757](#)  
`\cap` ..... [t337](#)  
`\capitalacute` ..... [l830](#), [l1595](#)  
`\capitalbreve` ..... [l837](#), [l1602](#)  
`\capitalcaron` ..... [l836](#), [l1601](#)  
`\capitalcedilla` ..... [l823](#), [l1592](#)  
`\capitalcircumflex` ..... [l831](#), [l1596](#)  
`\capitaldieresis` ..... [l833](#), [l1598](#)  
`\capitaldotaccent` ..... [l839](#), [l1604](#)  
`\capitalgrave` ..... [l829](#), [l1594](#)  
`\capitalhungarumlaut` .... [l834](#), [l1599](#)  
`\capitalmacron` ..... [l838](#), [l1603](#)  
`\capitalnewtie` .... [l843](#), [l1669](#), [l1670](#)  
`\capitalogonek` ..... [l826](#), [l1593](#)  
`\capitalring` ..... [l835](#), [l1600](#)  
`\capitaltie` ..... [l841](#), [l1665](#), [l1666](#)  
`\capitaltilde` ..... [l832](#), [l1597](#)  
`\caption` ..... [G4](#)  
`\cases` ..... [z153](#), [z154](#), [z164](#), [z166](#)  
`\catcodetable` ..... [N88](#), [N109](#)  
`\catcodetable@atletter` [531](#), [N93](#), [N233](#)  
`\catcodetable@initex` . [531](#), [N93](#), [N230](#)  
`\catcodetable@latex` .. [531](#), [N93](#), [N232](#)  
`\catcodetable@string` . [531](#), [N93](#), [N231](#)  
`\cdot` ..... [t359](#)  
`\cdotp` ..... [t463](#), [t469](#)  
`\cdots` ..... [t469](#)  
`\cdp@elt` ..... [o60](#), [o80](#),  
[o91](#), [o92](#), [o113](#), [o116](#), [o118](#), [r201](#),  
[r283](#), [r338](#), [r402](#), [r483](#), [O368](#), [O369](#)  
`\cdp@list` [o62](#), [o78](#), [o92](#), [o120](#), [o121](#),  
[r219](#), [r285](#), [r340](#), [r404](#), [r485](#), [O369](#)  
`\center` ..... [y172](#)  
`center (environment)` ..... [y172](#)  
`\centering` [y172](#), [y177](#), [y178](#), [y193](#), [y195](#)  
`\centerline` ..... [B402](#)  
`\cf@encoding` ..... [l34](#), [l41](#), [l44](#),  
[l51](#), [l152](#), [o220](#), [o230](#), [o240](#), [o259](#)  
`\ch@ck` ..... [b206](#), [b207](#), [b208](#),  
[b209](#), [b227](#), [b237](#), [b238](#), [b239](#),  
[b240](#), [b268](#), [b270](#), [b282](#), [b283](#),  
[b284](#), [b285](#), [b291](#), [L589](#), [L611](#), [L704](#)  
`\changes` ..... [L536](#), [L538](#), [L539](#)  
`\char` ... [d402](#), [l388](#), [l391](#), [l424](#), [l427](#),  
[l438](#), [l445](#), [l471](#), [l475](#), [l480](#), [l483](#),  
[l485](#), [l487](#), [l724](#), [l752](#), [l755](#), [l788](#),  
[l795](#), [l802](#), [l825](#), [l828](#), [l876](#), [l985](#),  
[l998](#), [l1155](#), [s69](#), [y267](#), [y356](#),  
[z205](#), [D112](#), [D140](#), [D154](#), [D162](#),  
[D165](#), [D234](#), [D272](#), [D277](#), [D316](#),  
[D320](#), [D335](#), [D336](#), [D338](#), [D349](#)  
`\chardef` ..... [a64](#), [a70](#), [a71](#),  
[b10](#), [b16](#), [b17](#), [b18](#), [b19](#), [b20](#),  
[b58](#), [b64](#), [b66](#), [b73](#), [b79](#), [b82](#),  
[b84](#), [b94](#), [b96](#), [b97](#), [b98](#), [b99](#),  
[b108](#), [b114](#), [b115](#), [b128](#), [b130](#),  
[b194](#), [b242](#), [b246](#), [b248](#), [b272](#),  
[b287](#), [b418](#), [b419](#), [b420](#), [e2](#), [k50](#),  
[l18](#), [o14](#), [C4](#), [C9](#), [L588](#), [L610](#),  
[L703](#), [N20](#), [N24](#), [N36](#), [N45](#),  
[N46](#), [N88](#), [N157](#), [N211](#), [O28](#),  
[O30](#), [O34](#), [O53](#), [O104](#), [O105](#),  
[O106](#), [O107](#), [O108](#), [O109](#), [O110](#)  
`\chardef@text@cmd` ..... [l3](#)  
`\charsubdef` ..... [O249](#)  
`\charzero` ..... [N211](#)  
`\check` ..... [t483](#)  
`\check@command` ..... [d162](#), [d164](#)  
`\check@icl` .....  
... [v9](#), [v27](#), [v32](#), [v38](#), [v46](#), [v53](#), [v55](#)  
`\check@icr` .....  
... [v9](#), [v27](#), [v33](#), [v39](#), [v47](#), [v56](#), [v61](#)  
`\check@mathfonts` ..... [j5](#), [l299](#),  
[l325](#), [l357](#), [l1193](#), [o281](#), [o283](#), [p204](#)  
`\check@nocorr@` ..... [v29](#)  
`\check@range` ..... [p333](#), [p334](#)  
`\check@single` ..... [p332](#), [p354](#)  
`\CheckCommand` ..... [d162](#)  
`\CheckEncodingSubset` [l1533](#), [l1590](#),  
[l1591](#), [l1659](#), [l1776](#), [l1779](#), [l1793](#)  
`\chi` ..... [t258](#)  
`\choose` ..... [z57](#)  
`\circ` ..... [t356](#)  
`\circle` ..... [D236](#), [D329](#), [D425](#), [D442](#)  
`\citation` ..... [l11](#), [l19](#), [l43](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdc1.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

`\cite` ..... 417, [I12](#)  
`\cl@ckpt` ..... [k210](#), [m35](#)  
`\cl@page` ..... [w4](#)  
`\ClassError` ..... [g84](#)  
`\ClassInfo` ..... [g84](#)  
`\ClassWarning` ..... [g84](#)  
`\ClassWarningNoLine` ..... [g84](#)  
`\cleaders` ..... [b438](#), [t509](#), [t512](#)  
`\cleardoublepage` ..... [K138](#)  
`\clearpage` .....  
     ... [k179](#), [k197](#), [y12](#), [y86](#), [K125](#),  
     [K138](#), [K143](#), [K200](#), [K407](#), [K410](#),  
     [K414](#), [K455](#), [K461](#), [K2171](#), [K2188](#)  
`\cline` ..... [C343](#)  
`\clubpenalty` ..... [b312](#), [k10](#),  
     [k23](#), [k80](#), [o538](#), [A128](#), [A194](#),  
     [A196](#), [F100](#), [F106](#), [F130](#), [F135](#)  
`\clubsuit` ..... [t300](#)  
`\col@number` ... [K95](#), [K148](#), [K208](#), [K220](#)  
`\colon` ..... [t464](#)  
`\color@begingroup` ... [o517](#), [o577](#),  
     [z104](#), [z134](#), [B29](#), [B63](#), [B131](#),  
     [B299](#), [B332](#), [C47](#), [C51](#), [G417](#), [K491](#)  
`\color@endbox` .. [B63](#), [G253](#), [G344](#),  
     [K224](#), [K631](#), [K641](#), [K690](#), [K700](#)  
`\color@endgroup` .....  
     ... [o522](#), [o583](#), [z104](#), [z134](#),  
     [B29](#), [B63](#), [B89](#), [B110](#), [B133](#),  
     [B319](#), [B335](#), [C49](#), [G420](#), [K495](#)  
`\color@hbox` .....  
     ... [B63](#), [K628](#), [K638](#), [K687](#), [K697](#)  
`\color@setgroup` ..... [B63](#), [B89](#), [B108](#)  
`\color@vbox` ..... [B63](#),  
     [G96](#), [G165](#), [G335](#), [G357](#), [K215](#)  
`\columnsep` ..... [k25](#), [k82](#), [K81](#), [K202](#)  
`\columnseprule` ... [K82](#), [K2226](#), [K2260](#)  
`\columnwidth` ... [k22](#), [k25](#), [k26](#), [k28](#),  
     [k79](#), [k82](#), [k83](#), [k86](#), [B301](#), [B328](#),  
     [G99](#), [G168](#), [G413](#), [K80](#), [K144](#),  
     [K145](#), [K146](#), [K201](#), [K202](#), [K203](#),  
     [K204](#), [K205](#), [K1843](#), [K1845](#),  
     [K2224](#), [K2228](#), [K2256](#), [K2262](#)  
`\conditionally@traceoff` ..... [g239](#)  
`\conditionally@traceon` ..... [g239](#)  
`\cong` ..... [t418](#)  
`\contentsline` ..... [F164](#), [F171](#), [F178](#)  
`\coprod` ..... [t310](#)  
`\copyright` ..... [l283](#), [l313](#), [s89](#)  
`\cos` ..... [z12](#)  
`\cosh` ..... [z14](#)  
`\cot` ..... [z18](#)  
`\coth` ..... [z19](#)  
`\count@` ..... [a66](#), [a179](#),  
     [a180](#), [a181](#), [a186](#), [b41](#), [b191](#),  
     [b192](#), [b197](#), [b199](#), [b205](#), [b206](#),  
     [b207](#), [b208](#), [b209](#), [b210](#), [b394](#),  
     [b395](#), [c14](#), [c15](#), [c16](#), [c17](#), [c18](#),  
     [c20](#), [d144](#), [d148](#), [o551](#), [o557](#),  
     [o559](#), [p22](#), [p256](#), [p258](#), [p280](#),  
     [p281](#), [r260](#), [r262](#), [r266](#), [r585](#),  
     [r586](#), [r587](#), [r633](#), [r634](#), [r635](#),  
     [r694](#), [r695](#), [r696](#), [r742](#), [r743](#),  
     [r744](#), [r786](#), [r787](#), [r788](#), [r794](#),  
     [r795](#), [r796](#), [r845](#), [r846](#), [r847](#),  
     [r853](#), [r854](#), [r855](#), [r901](#), [r902](#),  
     [r903](#), [r909](#), [r910](#), [r911](#), [r969](#),  
     [r970](#), [r971](#), [r977](#), [r978](#), [r979](#),  
     [v98](#), [v101](#), [D406](#), [D407](#), [D408](#),  
     [D411](#), [D412](#), [D415](#), [D419](#), [L635](#),  
     [L637](#), [L638](#), [L639](#), [L725](#), [L727](#),  
     [L728](#), [L729](#), [O172](#), [O173](#), [O180](#),  
     [O182](#), [O435](#), [O436](#), [O443](#), [O445](#)  
`\countdef` . [a66](#), [b37](#), [b38](#), [b39](#), [b41](#),  
     [b51](#), [b90](#), [w3](#), [N75](#), [N85](#), [N174](#),  
     [N182](#), [N190](#), [N198](#), [N212](#), [O61](#)  
`\counterwithin` ..... [155](#), [m77](#), [m97](#)  
`\counterwithin@s` .... [m77](#), [m78](#), [m98](#)  
`\counterwithin@x` .... [m77](#), [m80](#), [m99](#)  
`\counterwithout` ..... [155](#), [m67](#), [m94](#)  
`\counterwithout@s` ... [m67](#), [m68](#), [m95](#)  
`\counterwithout@x` ... [m67](#), [m70](#), [m96](#)  
`\CountZero` ..... [N212](#)  
`\cr` .... [b368](#), [l494](#), [l500](#), [l510](#), [l516](#),  
     [l1582](#), [l1586](#), [z175](#), [z179](#), [z331](#),  
     [z361](#), [z459](#), [C180](#), [C191](#), [C198](#),  
     [C207](#), [C208](#), [C353](#), [D52](#), [D54](#), [D55](#)  
`\crrcr` ..... [b425](#), [l324](#), [l359](#), [l360](#),  
     [l387](#), [l391](#), [l394](#), [l470](#), [l474](#), [l478](#),  
     [l480](#), [l483](#), [l723](#), [l751](#), [l755](#), [l758](#),  
     [l825](#), [l828](#), [l875](#), [l1192](#), [l1587](#),  
     [s91](#), [t306](#), [t307](#), [t309](#), [t420](#), [t423](#),  
     [t427](#), [t491](#), [t492](#), [t493](#), [t494](#),  
     [t495](#), [t496](#), [t498](#), [t499](#), [t500](#),  
     [t501](#), [t502](#), [t504](#), [z155](#), [z157](#),  
     [z158](#), [z159](#), [z175](#), [z177](#), [z178](#),  
     [z179](#), [z197](#), [z198](#), [C159](#), [C160](#), [D52](#)  
`\create_callback` ..... [534](#), [N607](#)  
`\csc` ..... [z21](#)  
`\cup` ..... [t338](#)  
`\curr@fontshape` ..... [l178](#),  
     [o52](#), [o296](#), [o304](#), [o308](#), [o310](#),  
     [o393](#), [o399](#), [o402](#), [o411](#), [o418](#),  
     [o420](#), [o428](#), [o434](#), [o437](#), [o445](#),  
     [o452](#), [o454](#), [p92](#), [p100](#), [p121](#),  
     [p431](#), [p451](#), [p483](#), [p496](#), [r223](#), [r228](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltboutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx



<code>\curr@math@size</code> .....	11446
..... <a href="#">o285</a> , <a href="#">p210</a> , <a href="#">p216</a> , <a href="#">p221</a> , <a href="#">p238</a>	
<code>\CurrentOption</code> .....	11469, 11471,
..... <a href="#">11483</a> , <a href="#">L13</a> , <a href="#">L198</a> , <a href="#">L208</a> , <a href="#">L209</a> ,	
..... <a href="#">L210</a> , <a href="#">L215</a> , <a href="#">L222</a> , <a href="#">L223</a> , <a href="#">L224</a> ,	
..... <a href="#">L227</a> , <a href="#">L234</a> , <a href="#">L235</a> , <a href="#">L239</a> , <a href="#">L240</a> ,	
..... <a href="#">L241</a> , <a href="#">L248</a> , <a href="#">L250</a> , <a href="#">L259</a> , <a href="#">L260</a> ,	
..... <a href="#">L261</a> , <a href="#">L262</a> , <a href="#">L269</a> , <a href="#">L270</a> , <a href="#">L271</a> ,	
..... <a href="#">L272</a> , <a href="#">L419</a> , <a href="#">L502</a> , <a href="#">L503</a> , <a href="#">L512</a> , <a href="#">L513</a>	
<code>\CYRA</code> .....	11441
<code>\cyra</code> .....	11441, 11486
<code>\CYRABHCH</code> .....	11441
<code>\cyrabhch</code> .....	11441
<code>\CYRABHCHDSC</code> .....	11441
<code>\cyrabhchdsc</code> .....	11441
<code>\CYRABHDZE</code> .....	11442
<code>\cyrabhdze</code> .....	11441
<code>\CYRABHHA</code> .....	11442
<code>\cyrabhha</code> .....	11442
<code>\CYRAE</code> .....	11442
<code>\cyrae</code> .....	11442
<code>\CYRB</code> .....	11442
<code>\cyrb</code> .....	11442
<code>\CYRBYUS</code> .....	11443
<code>\cyrbyus</code> .....	11442
<code>\CYRC</code> .....	11443
<code>\cyrc</code> .....	11443
<code>\CYRCH</code> .....	11443
<code>\cyrch</code> .....	11443
<code>\CYRCHLDSC</code> .....	11443
<code>\cyrchldsc</code> .....	11443
<code>\CYRCHRDSC</code> .....	11444
<code>\cyrchrdsc</code> .....	11443
<code>\CYRCHVCRS</code> .....	11444
<code>\cyrchvcrs</code> .....	11444
<code>\CYRD</code> .....	11444
<code>\cyrd</code> .....	11444
<code>\CYRDELTA</code> .....	11444
<code>\cyrdelta</code> .....	11444
<code>\CYRDJE</code> .....	11445
<code>\cyrdje</code> .....	11445
<code>\CYRDZE</code> .....	11445
<code>\cyrdze</code> .....	11445
<code>\CYRDZHE</code> .....	11445
<code>\cyrdzhe</code> .....	11445
<code>\CYRE</code> .....	11445
<code>\cyre</code> .....	11445
<code>\CYREPS</code> .....	11446
<code>\cyreps</code> .....	11445
<code>\CYREREV</code> .....	11446
<code>\cyrerev</code> .....	11446
<code>\CYRERY</code> .....	11446
<code>\cyrery</code> .....	11446
<code>\CYRF</code> .....	11446
<code>\cyrf</code> .....	11446
<code>\CYRFITA</code> .....	11447
<code>\cyrfita</code> .....	11446
<code>\CYRG</code> .....	11447
<code>\cyrg</code> .....	11447
<code>\CYRGDSC</code> .....	11447
<code>\cyrgdsc</code> .....	11447
<code>\CYRGDSCHCRS</code> .....	11447
<code>\cyrgdschcrs</code> .....	11447
<code>\CYRGHCRS</code> .....	11448
<code>\cyrghcrs</code> .....	11448
<code>\CYRGHK</code> .....	11448
<code>\cyrghk</code> .....	11448
<code>\CYRGUP</code> .....	11448
<code>\cyrgup</code> .....	11448
<code>\CYRH</code> .....	11448
<code>\cyrh</code> .....	11448
<code>\CYRHDSC</code> .....	11449
<code>\cyrhdsc</code> .....	11449
<code>\CYRHHCRS</code> .....	11449
<code>\cyrhhcrs</code> .....	11449
<code>\CYRHHK</code> .....	11449
<code>\cyrhhk</code> .....	11449
<code>\CYRHRDSN</code> .....	11450
<code>\cyrhrdsn</code> .....	11449
<code>\CYRI</code> .....	11450
<code>\cyri</code> .....	11450
<code>\CYRIE</code> .....	11450
<code>\cyrie</code> .....	11450
<code>\CYRII</code> .....	11450
<code>\cyrii</code> .....	11450
<code>\CYRISHRT</code> .....	11450
<code>\cyrishrt</code> .....	11450
<code>\CYRISHRTDSC</code> .....	11451
<code>\cyrishrtdsc</code> .....	11451
<code>\CYRIZH</code> .....	11451
<code>\cyrizh</code> .....	11451
<code>\CYRJE</code> .....	11451
<code>\cyrje</code> .....	11451
<code>\CYRK</code> .....	11451
<code>\cyrk</code> .....	11451
<code>\CYRKBEAK</code> .....	11452
<code>\cyrkbeak</code> .....	11452
<code>\CYRKDSC</code> .....	11452
<code>\cyrkdsc</code> .....	11452
<code>\CYRKHCRS</code> .....	11452
<code>\cyrkhcrs</code> .....	11452
<code>\CYRKHK</code> .....	11453
<code>\cyrkhk</code> .....	11452
<code>\CYRKVCRS</code> .....	11453
<code>\cyrkvcrs</code> .....	11453
<code>\CYRL</code> .....	11453
<code>\cyrl</code> .....	11453
<code>\CYRLDSC</code> .....	11453

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=ltthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

\cyrldsc	11453	\cyrsh	11460
\CYRLHK	11454	\CYRSHCH	11460
\cyrllhk	11453	\cyrshch	11460
\CYRLJE	11454	\CYRSHHA	11460
\cyrllje	11454	\cyrshha	11460
\CYRM	11454	\CYRT	11461
\cyrm	11454	\cyrt	11461
\CYRMDSC	11454	\CYRTDSC	11461
\cyrmdsc	11454	\cyrt dsc	11461
\CYRMHK	11454	\CYRTETSE	11461
\cyrnhk	11454	\cyrtetse	11461
\CYRN	11455	\CYRTSHE	11461
\cyrn	11455	\cyrtshe	11461
\CYRNDSC	11455	\CYRU	11462
\cyrndsc	11455	\cyru	11462
\CYRNG	11455	\CYRUSHRT	11462
\cyrng	11455	\cyrushrt	11462
\CYRNHK	11455	\CYRV	11462
\cyrnhk	11455	\cyrv	11462
\CYRNJE	11456	\CYRW	11462
\cyrnje	11455	\cyrw	11462
\CYRNLHK	11456	\CYRY	11462
\cyrnlhk	11456	\cyry	11462
\CYRO	11456	\CYRYA	11463
\cyro	11456	\cyrya	11463
\CYROTLD	11456	\CYRYAT	11463
\cyrotld	11456	\cyryat	11463
\CYRP	11456	\CYRYHCRS	11463
\cyrp	11456	\cyrhcrs	11463
\CYRPHK	11457	\CYRYI	11463
\cyrphk	11457	\cyryi	11463
\CYRQ	11457	\CYRYO	11464
\cyrq	11457	\cyryo	11463
\CYRR	11457	\CYRYU	11464
\cyrr	11457	\cyryu	11464
\CYRRDSC	11457	\CYRZ	11464
\cyr rdsc	11457	\cyrz	11464
\CYRRHK	11458	\CYRZDSC	11464
\cyr rhk	11457	\cyrz dsc	11464
\CYRTICK	11458	\CYRZH	11464
\cyrtick	11458	\cyrzh	11464
\CYRS	11458	\CYRZHDSC	11465
\cyr s	11458	\cyrzhdsc	11465
\CYRSACRS	11458		
\cyr sacrs	11458		
\CYRSCHWA	11459		
\cyr schwa	11459		
\CYRSDSC	11459		
\cyr sdsc	11459		
\CYRSEMISFTSN	11459		
\cyr semisftsn	11459		
\CYRSFTSN	11460		
\cyr sftsn	11460		
\CYRSH	11460		

## D

\d	1233, 1392, 1476, 1756, 11188, 11396, 11397, 11398, 11399, 11402, 11403, 11404, 11405, 11406, 11407, 11408, 11409, 11410, 11411, 11412, 11413, 11414, 11415, 11416, 11417, 11418, 11419, 11420, 11421, 11422, 11423, 11424, 11425, 11426, 11427, 11428, 11429, 11430, 11431, 11432, 11433, 11434, 11435
----	---

**File Key:** a=lt dirchk.dtx, b=lt plain.dtx, c=lt vers.dtx, d=lt defns.dtx,  
e=lt alloc.dtx, f=lt cntrl.dtx, g=lt error.dtx, h=lt par.dtx, i=lt space.dtx,  
j=lt logos.dtx, k=lt files.dtx, l=lt outenc.dtx, m=lt counts.dtx, n=lt length.dtx,  
o=lt fssbas.dtx, p=lt fssstrc.dtx, q=lt fssc mp.dtx, r=lt fssdc l.dtx, s=lt fssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=lt fntcmd.dtx, w=lt pageno.dtx, x=lt xref.dtx,  
y=lt miscen.dtx, z=lt math.dtx, A=lt lists.dtx, B=lt boxes.dtx, C=lt tab.dtx,  
D=lt pictur.dtx, E=lt thm.dtx, F=lt sect.dtx, G=lt float.dtx, H=lt id xglo.dtx,  
I=lt bibl.dtx, J=lt page.dtx, K=lt output.dtx, L=lt class.dtx, M=lt hyphen.dtx,  
N=lt luatex.dtx, O=lt final.dtx



`\dag` ..... l309  
`\dagger` ..... l309,  
     m131, m137, m145, m146, t340  
`\dashbox` ..... D167, D426, D443  
`\dashv` ..... t368  
`\date` ..... 384, F9, F25  
`\day` ..... a185, c11, L631, L721  
`\dblfigrule` ..... K767, K2325  
`\dblfloatpagefraction` .....  
     G287, G301, K2302  
`\dblfloatsep` .....  
     K753, K765, K1640, K1766, K2309  
`\dbltextfloatsep` ..... K222,  
     K230, K769, K1639, K1765, K2309  
`\dbltopfraction` .. G284, G298, K2301  
`\ddag` ..... l310  
`\ddagger` ..... l310,  
     m132, m138, m145, m147, t339  
`\ddot` ..... t479  
`\ddots` ..... t474  
`\deadcycles` ..... k203, y39, y86, K299  
`\declare@robustcommand` ..... d195  
`\DeclareCurrentRelease` ..... L956  
`\DeclareEncodingSubset` ... l1517,  
     l1524, l1525, l1526, l1527, l1803,  
     l1804, l1805, l1806, l1807, l1808,  
     l1809, l1810, l1811, l1812, l1813,  
     l1814, l1815, l1816, l1817, l1818,  
     l1819, l1820, l1821, l1822, l1823,  
     l1824, l1825, l1826, l1827, l1828,  
     l1829, l1830, l1831, l1832, l1833,  
     l1834, l1835, l1836, l1837, l1838,  
     l1839, l1840, l1841, l1842, l1843,  
     l1844, l1845, l1846, l1847, l1848,  
     l1849, l1850, l1851, l1852, l1853,  
     l1854, l1855, l1856, l1857, l1858,  
     l1859, l1860, l1861, l1862, l1863  
`\DeclareErrorFont` o351, r232, s115, t41  
`\DeclareFixedFont` ..... o39  
`\DeclareFontEncoding` .....  
     ... l374, l457, l707, l729, l735,  
     l821, l995, o82, t96, t97, t98, t99  
`\DeclareFontEncoding@` .....  
     o86, o88, o103, O279, O299, O365  
`\DeclareFontEncoding@saved` .....  
     O279, O299, O381  
`\DeclareFontEncodingDefaults` ...  
     ... o132, q90, q91, t28  
`\DeclareFontFamily` .... o57, q85, q86  
`\DeclareFontShape` .....  
     ... o18, o20, q25, q27, q81, q82  
`\DeclareFontShape@` ..... o21, o22  
`\DeclareFontSubstitution` .....  
     ... l736, l822, o105, t19,  
     t26, t29, t30, t100, t101, t102, t103  
`\DeclareMathAccent` r573, t477, t478,  
     t479, t480, t481, t482, t483,  
     t484, t485, t486, t487, t488, t489  
`\DeclareMathAlphabet` .....  
     ... q119, q123, q125, q132,  
     r399, r562, t121, t122, t123, t124  
`\DeclareMathAlphabetCharacter` . r748  
`\DeclareMathDelimiter` .....  
     ... r750, t225, t226, t227,  
     t228, t229, t230, t233, t235,  
     t236, t524, t526, t528, t530,  
     t532, t535, t537, t539, t541,  
     t543, t545, t547, t549, t551,  
     t553, t555, t557, t559, t561,  
     t563, t565, t567, t569, t571, t573  
`\DeclareMathRadical` ..... r949, t490  
`\DeclareMathSizes` .....  
     ... o169, o175, o197, t127,  
     t128, t129, t130, t131, t132,  
     t133, t134, t135, t136, t137, t138  
`\DeclareMathSizes*` ..... o169  
`\DeclareMathSymbol` .... r686, r749,  
     r766, t139, t140, t141, t142,  
     t143, t144, t145, t146, t147,  
     t148, t149, t150, t151, t152,  
     t153, t154, t155, t156, t157,  
     t158, t159, t160, t161, t162,  
     t163, t164, t165, t166, t167,  
     t168, t169, t170, t171, t172,  
     t173, t174, t175, t176, t177,  
     t178, t179, t180, t181, t182,  
     t183, t184, t185, t186, t187,  
     t188, t189, t190, t191, t192,  
     t193, t194, t195, t196, t197,  
     t198, t199, t200, t201, t202,  
     t203, t204, t205, t206, t207,  
     t208, t209, t210, t211, t212,  
     t213, t214, t215, t216, t217,  
     t218, t219, t220, t221, t231,  
     t232, t234, t238, t239, t240,  
     t241, t242, t243, t244, t245,  
     t246, t247, t248, t249, t250,  
     t251, t252, t253, t254, t255,  
     t256, t257, t258, t259, t260,  
     t261, t262, t263, t264, t265,  
     t266, t267, t268, t269, t270,  
     t271, t272, t273, t274, t275,  
     t276, t277, t278, t279, t280,  
     t281, t282, t283, t284, t285,  
     t286, t287, t288, t289, t290,  
     t291, t292, t293, t294, t295,

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

t297, t298, t299, t300, t301,  
 t302, t303, t310, t311, t312,  
 t313, t314, t315, t316, t318,  
 t319, t320, t321, t322, t323,  
 t325, t326, t327, t328, t329,  
 t330, t333, t335, t337, t338,  
 t339, t340, t341, t342, t343,  
 t344, t345, t346, t347, t348,  
 t349, t350, t351, t352, t353,  
 t354, t355, t356, t357, t358,  
 t359, t360, t361, t362, t363,  
 t364, t365, t366, t367, t368,  
 t369, t370, t371, t372, t373,  
 t374, t375, t376, t380, t382,  
 t384, t385, t386, t387, t388,  
 t389, t390, t391, t392, t393,  
 t394, t396, t397, t398, t399,  
 t400, t402, t404, t406, t407,  
 t408, t409, t410, t411, t412,  
 t413, t414, t415, t416, t438,  
 t440, t462, t463, t464, t514,  
 t515, t516, t517, t575, t576, t577  
 \DeclareMathVersion . . . . . [r245](#), s2, s3  
 \DeclareOldFontCommand . . . [v108](#), [v124](#)  
 \DeclareOption . . . . .  
 . . . . . [499](#), [l1468](#), [l1524](#), [l1525](#),  
[l1526](#), [l1527](#), [l1528](#), [l1530](#), p29,  
 p37, p45, p53, p56, p60, [L181](#), [L523](#)  
 \DeclareOption\* . . . . . [499](#), [L181](#)  
 \DeclarePreloadSizes . . . . .  
 . . . . . [o149](#), q95, q96, u19, u21,  
 u22, u23, u25, u26, u27, u28,  
 u29, u30, u34, u38, u43, u45,  
 u49, u50, u53, u54, u57, u58, u64  
 \DeclareRelease . . . . . [L863](#)  
 \DeclareRobustCommand [d195](#), d392,  
 d393, d400, g4, g11, g30, g57,  
 i7, i8, i9, i10, i11, i68, i79, i280,  
 i316, i330, i335, i350, i361, i362,  
 i363, j2, j3, j13, k239, k315,  
 l148, l156, l304, l305, l306, l307,  
 l308, l309, l310, l311, l313, l315,  
 l317, l1788, m155, n19, n20,  
 n21, o215, o243, o244, o245,  
 o246, o249, o251, o269, o515,  
 o524, p113, s4, s7, s10, s13, s16,  
 s19, s22, s25, s28, s34, s41, s63,  
 s65, s69, s78, s89, s93, t304,  
 t305, t306, t317, t324, t377,  
 t379, t405, t417, t421, t424,  
 t429, t431, t433, t436, t439,  
 t441, t442, t444, t446, t448,  
 t450, t452, t454, t456, t458,  
 t460, t466, t468, t470, t473,  
 t491, t494, t497, t501, t505,  
 t508, t511, t518, t521, t578,  
 t579, t580, t585, t587, t589,  
 t591, v3, v109, x45, y93, y178,  
 y182, y186, y267, y271, z3, z4,  
 z5, z6, z7, z8, z9, z10, z11, z12,  
 z13, z14, z15, z16, z17, z18, z19,  
 z20, z21, z22, z23, z24, z25, z26,  
 z27, z28, z29, z30, z31, z32, z33,  
 z34, z35, z39, z41, z42, z43, z44,  
 z45, z46, z47, z48, z49, z50,  
 z51, z52, z81, z82, z83, z84,  
 z126, z154, z156, z160, z205,  
 z228, z230, z246, z257, z307,  
 z308, z309, z366, z383, z407,  
 B7, B24, B75, B88, B111, B112,  
 B128, B139, B193, B341, B359,  
 B367, B403, B404, B405, B406,  
 B407, C127, C130, C142, D37,  
 D39, D41, F7, F8, F9, F10,  
 F14, F201, G378, G386, J22,  
 J30, J53, J55, J57, J64, K87,  
 L490, L491, L986, O461, O471, I12  
 \DeclareSizeFunction . . . [p371](#), p444,  
 p445, p456, p457, p461, p462,  
 p468, p469, p493, p494, p501, p502  
 \DeclareSymbolFont . . . . .  
 . . . . . [q136](#), [r280](#), t111, t112, t113, t114  
 \DeclareSymbolFontAlphabet . . . . .  
 . . . . . [r1023](#), t118, t119, t120  
 \DeclareSymbolFontAlphabet@ . . . . .  
 . . . . . [r1024](#), [r1027](#)  
 \DeclareTextAccent . . . . . [l64](#), l375,  
 l376, l377, l378, l379, l380, l381,  
 l382, l383, l384, l385, l458, l459,  
 l460, l461, l462, l463, l464, l465,  
 l466, l467, l468, l732, l737, l738,  
 l739, l740, l741, l742, l743, l744,  
 l745, l746, l747, l829, l830, l831,  
 l832, l833, l834, l835, l836, l837,  
 l838, l839, l840, l841, l842, l843  
 \DeclareTextAccentDefault . . . . .  
 . . . . . [l183](#), l224, l225,  
 l226, l227, l228, l229, l230, l231,  
 l232, l233, l234, l235, l236, l237,  
 l277, l280, l1592, l1593, l1594,  
 l1595, l1596, l1597, l1598, l1599,  
 l1600, l1601, l1602, l1603, l1604  
 \DeclareTextCommand . . . . . [l3](#), l58,  
 l65, l81, l386, l389, l392, l408,  
 l409, l416, l418, l420, l422, l428,  
 l430, l432, l439, l469, l472, l476,  
 l479, l481, l484, l486, l488, l504,  
 l721, l748, l750, l753, l756, l789,

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

1796, 1823, 1826, 1873, 11000,  
11026, 11028, 11030, 11154, 11191

`\DeclareTextCommandDefault` . . . . .  
 . . . . . 157, 1184,  
 1186, 1281, 1284, 1285, 1286, 1287,  
 1289, 1293, 1297, 1298, 1300, 1301,  
 1302, 1303, 1323, 1352, 11658,  
 11660, 11661, 11663, 11665, 11667,  
 11669, 11671, 11673, 11675, 11677,  
 11679, 11681, 11683, 11685, 11687,  
 11689, 11691, 11693, 11695, 11697,  
 11699, 11701, 11703, 11705, 11707,  
 11709, 11711, 11713, 11715, 11717,  
 11719, 11721, 11723, 11725, 11727,  
 11729, 11731, 11733, 11735, 11737,  
 11739, 11741, 11743, 11745, 11747,  
 11749, 11751, 11753, 11755, 11757,  
 11759, 11761, 11763, 11765, 11767,  
 11769, 11771, 11773, 11775, 11778

`\DeclareTextComposite` . . . . .  
 . . . . . 174, 1446, 1447, 1578,  
 1579, 1580, 1581, 1582, 1583, 1584,  
 1585, 1586, 1587, 1588, 1589, 1590,  
 1591, 1592, 1593, 1594, 1595, 1596,  
 1597, 1598, 1599, 1600, 1601, 1602,  
 1603, 1604, 1605, 1606, 1607, 1608,  
 1609, 1610, 1611, 1612, 1613, 1614,  
 1615, 1616, 1617, 1618, 1619, 1620,  
 1621, 1622, 1623, 1624, 1625, 1626,  
 1627, 1628, 1629, 1630, 1631, 1632,  
 1633, 1634, 1635, 1636, 1637, 1638,  
 1639, 1640, 1641, 1642, 1643, 1644,  
 1645, 1646, 1647, 1648, 1649, 1650,  
 1651, 1652, 1653, 1654, 1655, 1656,  
 1657, 1658, 1659, 1660, 1661, 1662,  
 1663, 1664, 1665, 1666, 1667, 1668,  
 1669, 1670, 1671, 1672, 1673, 1674,  
 1675, 1676, 1677, 1678, 1679, 1680,  
 1681, 1682, 1683, 1684, 1685, 1686,  
 1687, 1688, 1803, 1804, 1805, 1806,  
 1807, 1808, 1809, 1810, 1811, 1812,  
 1813, 1814, 1815, 1816, 1817, 1818

`\DeclareTextCompositeCommand` . . . . .  
 . . . . . 174, 1425, 1448,  
 1449, 1450, 1451, 1453, 1689, 1690,  
 1692, 1695, 1696, 1697, 1698, 1699,  
 1700, 1701, 1702, 1703, 1786, 11006

`\DeclareTextFontCommand` . . . . .  
 . . . . . v1, v15, v16, v17, v18, v19,  
 v20, v21, v22, v23, v24, v25, v123

`\DeclareTextSymbol` . . . . .  
 . . . . . 13, 1395, 1396, 1397, 1398,  
 1399, 1400, 1401, 1402, 1403, 1404,  
 1405, 1406, 1407, 1410, 1411, 1412,  
 1413, 1414, 1415, 1520, 1521, 1522,  
 1523, 1524, 1525, 1526, 1527, 1528,  
 1529, 1530, 1531, 1532, 1533, 1534,  
 1535, 1537, 1538, 1539, 1540, 1541,  
 1542, 1543, 1544, 1545, 1546, 1547,  
 1548, 1549, 1550, 1551, 1552, 1553,  
 1554, 1555, 1556, 1557, 1558, 1559,  
 1560, 1561, 1562, 1563, 1564, 1565,  
 1566, 1567, 1568, 1569, 1570, 1571,  
 1572, 1573, 1574, 1575, 1576, 1577,  
 1708, 1709, 1710, 1711, 1712, 1713,  
 1714, 1715, 1716, 1717, 1718, 1719,  
 1720, 1730, 1731, 1759, 1760, 1761,  
 1762, 1763, 1764, 1765, 1767, 1768,  
 1769, 1770, 1771, 1772, 1773, 1774,  
 1775, 1776, 1777, 1778, 1779, 1780,  
 1781, 1782, 1783, 1784, 1785, 1844,  
 1845, 1846, 1847, 1848, 1849, 1850,  
 1851, 1852, 1853, 1854, 1855, 1856,  
 1857, 1858, 1859, 1860, 1861, 1862,  
 1863, 1864, 1865, 1866, 1867, 1868,  
 1869, 1870, 1871, 1872, 1879, 1880,  
 1881, 1882, 1883, 1884, 1885, 1886,  
 1887, 1888, 1889, 1890, 1891, 1892,  
 1893, 1894, 1895, 1896, 1897, 1898,  
 1899, 1900, 1901, 1902, 1903, 1904,  
 1905, 1906, 1907, 1908, 1909, 1910,  
 1911, 1912, 1913, 1914, 1915, 1916,  
 1917, 1918, 1919, 1920, 1921, 1922,  
 1923, 1924, 1925, 1926, 1927, 1928,  
 1929, 1930, 1931, 1932, 1933, 1934,  
 1935, 1936, 1937, 1938, 1939, 1940,  
 1941, 1942, 1943, 1944, 1945, 1946,  
 1947, 1948, 1949, 1950, 1951, 1952,  
 1953, 1954, 1955, 1956, 1957, 1958,  
 11032, 11033, 11034, 11035, 11036,  
 11037, 11038, 11039, 11040, 11041,  
 11042, 11043, 11044, 11045, 11046,  
 11047, 11048, 11049, 11050, 11051,  
 11052, 11054, 11055, 11056, 11057,  
 11058, 11059, 11060, 11061, 11062,  
 11063, 11064, 11065, 11066, 11067,  
 11068, 11070, 11071, 11072, 11073,  
 11074, 11075, 11076, 11077, 11078,  
 11079, 11080, 11081, 11082, 11083,  
 11084, 11085, 11086, 11087, 11088,  
 11089, 11090, 11091, 11092, 11093,  
 11094, 11095, 11096, 11097, 11098,  
 11099, 11100, 11101, 11102, 11103,  
 11104, 11105, 11106, 11107, 11108,  
 11109, 11110, 11111, 11112, 11113,  
 11114, 11115, 11116, 11117, 11118,  
 11119, 11120, 11121, 11122, 11123,  
 11124, 11125, 11126, 11127, 11128,

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=ltpictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

l1129, l1130, l1131, l1132, l1133,  
 l1134, l1135, l1136, l1137, l1138,  
 l1139, l1140, l1141, l1142, l1143,  
 l1144, l1145, l1146, l1147, l1148,  
 l1149, l1150, l1152, l1153, l1165,  
 l1166, l1167, l1168, l1169, l1170,  
 l1171, l1172, l1173, l1174, l1175  
 \DeclareTextSymbolDefault .....  
     ..... l183, l238, l239, l240,  
     l241, l242, l243, l244, l245, l246,  
     l247, l248, l249, l250, l251, l252,  
     l253, l254, l255, l256, l257, l258,  
     l259, l260, l261, l262, l263, l264,  
     l265, l266, l267, l268, l269, l270,  
     l271, l272, l273, l274, l275, l276,  
     l278, l279, l1605, l1606, l1607,  
     l1608, l1609, l1610, l1611, l1612,  
     l1613, l1614, l1615, l1616, l1617,  
     l1618, l1619, l1620, l1621, l1622,  
     l1623, l1624, l1625, l1626, l1627,  
     l1628, l1629, l1630, l1631, l1632,  
     l1633, l1634, l1635, l1636, l1637,  
     l1638, l1639, l1640, l1641, l1642,  
     l1643, l1644, l1645, l1646, l1647,  
     l1648, l1649, l1650, l1651, l1652,  
     l1653, l1654, l1655, l1656, l1657  
 \DeclareUnicodeAccent ..... l999,  
     l1176, l1177, l1178, l1179, l1180,  
     l1181, l1182, l1183, l1184, l1185,  
     l1186, l1187, l1188, l1189, l1190  
 \DeclareUnicodeCharacter ..... O280  
 \DeclareUnicodeComposite .....  
     ..... l1004, l1195,  
     l1196, l1197, l1198, l1199, l1200,  
     l1201, l1202, l1203, l1204, l1205,  
     l1206, l1207, l1208, l1209, l1210,  
     l1211, l1212, l1213, l1214, l1215,  
     l1216, l1217, l1218, l1219, l1220,  
     l1221, l1222, l1223, l1224, l1225,  
     l1226, l1227, l1228, l1229, l1230,  
     l1231, l1232, l1233, l1234, l1235,  
     l1236, l1237, l1238, l1239, l1240,  
     l1241, l1242, l1243, l1244, l1245,  
     l1246, l1247, l1248, l1249, l1250,  
     l1251, l1252, l1253, l1254, l1255,  
     l1256, l1257, l1258, l1259, l1260,  
     l1261, l1262, l1263, l1264, l1265,  
     l1266, l1267, l1268, l1269, l1270,  
     l1271, l1272, l1273, l1274, l1275,  
     l1276, l1277, l1278, l1279, l1280,  
     l1281, l1282, l1283, l1284, l1285,  
     l1286, l1287, l1288, l1289, l1290,  
     l1291, l1292, l1293, l1294, l1295,  
     l1296, l1297, l1298, l1299, l1300,  
     l1301, l1302, l1303, l1304, l1305,  
     l1306, l1307, l1308, l1309, l1310,  
     l1311, l1312, l1313, l1314, l1315,  
     l1316, l1317, l1318, l1319, l1320,  
     l1321, l1322, l1323, l1324, l1325,  
     l1326, l1327, l1328, l1329, l1330,  
     l1331, l1332, l1333, l1334, l1335,  
     l1336, l1337, l1338, l1339, l1340,  
     l1341, l1342, l1343, l1344, l1345,  
     l1346, l1347, l1348, l1349, l1350,  
     l1351, l1352, l1353, l1354, l1355,  
     l1356, l1357, l1358, l1359, l1360,  
     l1361, l1362, l1363, l1364, l1365,  
     l1366, l1367, l1368, l1369, l1370,  
     l1371, l1372, l1373, l1374, l1375,  
     l1376, l1377, l1378, l1379, l1380,  
     l1381, l1382, l1383, l1384, l1385,  
     l1386, l1387, l1388, l1389, l1390,  
     l1391, l1392, l1393, l1394, l1395,  
     l1396, l1397, l1398, l1399, l1400,  
     l1401, l1402, l1403, l1404, l1405,  
     l1406, l1407, l1408, l1409, l1410,  
     l1411, l1412, l1413, l1414, l1415,  
     l1416, l1417, l1418, l1419, l1420,  
     l1421, l1422, l1423, l1424, l1425,  
     l1426, l1427, l1428, l1429, l1430,  
     l1431, l1432, l1433, l1434, l1435  
 \default@ds .....  
     ... L190, L201, L237, L469, L471  
 \default@family ..... o93, o125,  
     o361, o375, o378, o403, o438, O370  
 \default@M o100, o140, o143, o147, O377  
 \default@mextra ..... q10, q89  
 \default@series ..... o93, o126,  
     o362, o376, o379, o400, o435, O370  
 \default@shape ..... o94, o127,  
     o363, o377, o380, o398, o433, O371  
 \default@T .... o134, o137, o147, o236  
 \defaultthyphenchar ..... b322, d403  
 \defaultscriptratio ..... o498, o505  
 \defaultscriptscriptratio o499, o505  
 \defaultskewchar ..... b323  
 \define@mathalphabet ..... q18, q131  
 \define@mathgroup ..... q19, q135  
 \define@newfont ..... o288, o297  
 \deg ..... z34  
 \delcode ..... r947  
 \delimiter .... r800, r859, r930, r941  
 \delimiterfactor ..... b324  
 \delimitershortfall ..... b334  
 \Delta ..... t268  
 \delta ..... t241  
 \depth ..... B32, B35  
 \det ..... z30

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

- `\detokenize` .....  
     1977, 1997, y51, L600, L601, L605  
`\development@branch@name` .....  
     .. [c11](#), c49, c50, c51, c57, c58, c59  
`\DH` ..... l522, l1076, O481  
`\dh` ..... l532, l1082, O481  
`\Diamond` ..... s107  
`\diamond` ..... t345  
`\diamondsuit` ..... t301  
`\dim` ..... z28  
`\dimen@` [b41](#), b391, b392, b428, b429,  
     b431, b433, g28, g29, i295, i300,  
     l423, l424, l426, l427, l787, l788,  
     l1583, l1585, o178, o180, o186,  
     o199, o202, o206, o497, o498,  
     o499, o503, p405, p406, p407,  
     p408, p412, z72, z73, z186, z187,  
     z188, z189, B394, B397, C164,  
     C165, K508, K510, K531, K533  
`\dimen@i` ..... [b41](#)  
`\dimen@ii` ..... [b41](#), o182, o187  
`\dimendef` [b42](#), b43, b44, b52, b91, N213  
`\dimenzero` ..... N213  
`\dimexpr` ..... l497, l513, l1158, l1161  
`\directlua` ..... a9, a12,  
     a17, a20, a25, b65, b81, b105,  
     b245, d19, d340, N2, N12, N27,  
     N204, N218, N243, N248, N252  
`\disable_callback` ..... [534](#), [N749](#)  
`\discretionary` ..... d401, d413, z205  
`\displ@y` ..... z191, z195, z196  
`\displaylines` ..... [z190](#)  
`\displaymath` ..... z301  
`displaymath (environment)` ..... [z299](#)  
`\displaystyle` ... t493, t496, t500,  
     t502, z62, z197, z325, z328,  
     z365, z390, z402, z430, z454, z457  
`\displaywidowpenalty` ..... b314  
`\displaywidth` .. z197, z324, z377, z433  
`\div` ..... t348  
`\DJ` ..... l523, l1086, O481  
`\dj` ..... l533, l1087, O481  
`\do` ..... a74, a75,  
     a126, b13, b14, d44, f3, f7, f16,  
     f26, k63, k66, k118, k121, k187,  
     k259, k298, k391, k397, v73,  
     y232, y253, y335, y345, y351,  
     y357, B52, C220, C245, D31,  
     D36, D83, D186, D188, D208,  
     D211, D250, D294, D407, G65,  
     G134, L109, L126, L208, L222,  
     L234, L239, L259, L269, L512,  
     L553, L634, L724, L1001, l16, l41  
`\do@add@percent@to@temptokena` ..  
     ..... y52, y58, y76  
`\do@noligs` ..... [y352](#), [y357](#)  
`\do@subst@correction` . [o48](#), [p436](#), [p491](#)  
`\DocInput` ..... p8, t5, u5, M4  
`\document` ..... 88, [k11](#), l40  
`\document@default@language` .....  
     ..... k49, k50, K597, [O217](#)  
`\document@select@group` ... [r137](#), [r236](#)  
`\documentclass` .....  
     ..... p2, t2, u2, [L276](#), [L283](#),  
     L310, L313, L436, L532, M2, N14  
`\documentstyle` ..... [L281](#), [L532](#)  
`\dont@add@percent@to@temptokena` .  
     ..... y51, y53, y77  
`\dorestore@version` ..... [r114](#), [r119](#)  
`\dospecials` ..... a74, a126, b13,  
     y232, y253, y335, y345, L634, L724  
`\dot` ..... t486  
`\doteq` ..... t430  
`\dotfill` ..... [b435](#), d426, d447  
`\dots` ..... l317, l319  
`\doublehyphendemerits` ..... b317  
`\doublerulesep` .... C287, [C314](#), C338  
`\Downarrow` ..... t547  
`\downarrow` ..... t541  
`\downbracefill` ..... t499, t518  
`\ds@` ..... L203, L473  
`\dt@pfalse` ..... z192  
`\dt@ptrue` ..... z191  
`\dump` ..... O546
- ## E
- `\E` . L641, L644, L671, L731, L734, L762  
`\e@alloc` .. b51, b52, b53, b55, b56,  
     b63, b64, b66, b68, b79, b82,  
     b84, [b138](#), N13, N47, N78, N88,  
     N177, N185, N193, N201, O12, O33  
`\e@alloc@attribute@count` .....  
     . N66, N74, N75, N79, N81, N224  
`\e@alloc@bytecode@count` ... N70,  
     N189, N190, N194, N196, N240  
`\e@alloc@ccodetable@count` .....  
     . N67, N84, N85, N89, N92, N228  
`\e@alloc@chardef` .....  
     ..... b60, [b102](#), b210, b211,  
     N46, N177, N185, N193, N201, O12  
`\e@alloc@intercharclass@top` ... [O21](#)  
`\e@alloc@luachunk@count` ... N71,  
     N197, N198, N202, N206, N242  
`\e@alloc@luafunction@count` .....  
     ..... N68, N173,  
     N174, N178, N180, N234, N236

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdc1.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

`\e@alloc@top` ..... b55,  
           b63, [b102](#), b188, b248, N45,  
           N79, N178, N186, N194, N202, O12  
`\e@alloc@whatsit@count` .... N69,  
           N181, N182, N186, N188, N238  
`\e@ch@ck` ..... b142, [b152](#), N49, N53  
`\e@insert@top` . b246, b248, b265, b280  
`\e@mathgroup@top` b79, [b124](#), r56, r145  
`\egroup` ..... [b372](#)  
`\eject` ..... [b402](#)  
`\ell` ..... t281  
`\em` ..... [s31](#), v25  
`\emergencystretch` ..... J59, J65  
`\emminershape` ..... [s31](#)  
`\emph` ..... [v25](#)  
`\empty` ..... [b370](#)  
`\empty@sfcnt` .....  
           p444, p445, p446, p460, p465, p499  
`\emptyset` ..... t288  
`\enc@update` o221, o223, o239, [o242](#), p129  
`\encodingdefault` l970, l1469, l1495,  
           r237, s94, [t42](#), N247, N262, N270  
`\end` .... a69, d8, d362, g200, p9, t6,  
           u6, y92, [y118](#), y211, y212, z411,  
           z420, [A112](#), F15, F17, L649,  
           L653, L659, L739, L743, L749, M5  
`\end@dblfloat` ..... [G205](#)  
`\end@float` .. [G189](#), [G227](#), G243, G359  
`\endarray` ..... [C159](#)  
`\endcenter` ..... [y173](#)  
`\enddisplaymath` ..... [z302](#)  
`\enddocument` ..... [y8](#)  
`\endenumerate` ..... A240  
`\endeqnarray` ..... [z333](#), [z364](#)  
`\endequation` ..... [z305](#)  
`\endfilecontents` ..... [L536](#)  
`\endflushleft` ..... [y203](#)  
`\endflushright` ..... [y205](#)  
`\endgraf` ..... [b367](#)  
`\EndIncludeInRelease` ..... a22,  
           a50, a306, a316, b87, b101,  
           b118, b123, b133, b137, b147,  
           b150, b167, b181, b185, b219,  
           b224, b277, b289, b480, b487,  
           b534, b539, c97, c103, d273,  
           d299, d302, d318, d351, d360,  
           d411, d415, d440, d461, i20,  
           i30, i64, i77, i125, i139, i151,  
           i162, i179, i191, i256, i278,  
           i344, i348, i366, i373, k69, k123,  
           k164, k176, k269, k308, k322,  
           k330, k345, k355, l101, l121,  
           l166, l173, l327, l349, l364, l372,  
           m28, m33, m89, m100, m142,  
           m148, m168, m171, n10, n14,  
           o195, o212, o366, o384, o423,  
           o456, o572, o584, q21, q143,  
           r77, r105, r168, r198, r622,  
           r664, r677, r684, r831, r887,  
           r936, r944, s39, s45, t72, t82,  
           t594, t601, x48, x59, y71, y84,  
           y141, y147, y160, y167, y191,  
           y199, y237, y258, y299, y318,  
           y340, y348, z86, z95, z117,  
           z124, z143, z147, z162, z170,  
           z233, z241, z270, z297, z393,  
           z405, z414, z423, A132, A137,  
           B13, B22, B79, B86, B143,  
           B150, B198, B206, B257, B275,  
           B343, B348, B371, B378, C144,  
           C152, D286, D327, D437, D454,  
           F19, F29, F167, F172, F203,  
           F225, G104, G172, G231, G246,  
           G293, G306, G391, G396, J39,  
           J46, K53, K62, K178, K196,  
           K365, K370, K418, K464, K650,  
           K708, K811, K830, K893, K911,  
           K953, K974, K1216, K1385,  
           K1467, K1561, K1683, K1810,  
           K1929, K1957, K2177, K2195,  
           K2242, K2286, L72, L83,  
           L121, L138, L264, L273, L384,  
           L412, L674, L764, N221, N244,  
           N267, N271, O15, O19, O37,  
           O55, O65, O72, O80, O131,  
           O155, O223, O227, O336, O383  
`\EndIncludeRelease` ..... c73  
`\enditemize` ..... A251  
`\endline` ..... [b367](#), [z175](#)  
`\endlinechar` a92, a93, a94, a204, d22,  
           d24, d29, k365, L163, L164, L165  
`\endlist` ..... [A98](#), A240, A251  
`\endlrbox` ..... [B110](#)  
`\endmath` ..... [z300](#)  
`\endminipage` ..... [B309](#)  
`\endpicture` ..... [D17](#)  
`\endsloppypar` ..... J63  
`\endtabbing` ..... [C72](#)  
`\endtabular` ..... [C159](#)  
`\endtabular*` ..... [C159](#)  
`\endtrivlist` .... y173, y203, y205,  
           y261, z435, A100, [A101](#), C73, E39  
`\endverbatim` ..... [y260](#), [y297](#)  
`\enlargethispage` ..... [K1855](#)  
`\enlargethispage*` ..... [K1855](#)  
`\enskip` ..... [i375](#)  
`\enspace` ..... [i361](#), [i371](#)  
`\ensuremath` .. m144, [z366](#), G381, G389

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx



- `\enumerate` ..... [A231](#)
  - `enumerate (environment)` ..... [A231](#)
  - environments:
    - `center` ..... [y172](#)
    - `displaymath` ..... [z299](#)
    - `enumerate` ..... [A231](#)
    - `eqnarray` ..... [z311](#), [z436](#)
    - `eqnarray*` ..... [z362](#)
    - `equation` ..... [z303](#), [z424](#)
    - `filecontents` ..... [497](#)
    - `flushleft` ..... [y202](#)
    - `flushright` ..... [y204](#)
    - `itemize` ..... [A242](#)
    - `lrbox` ..... [322](#)
    - `math` ..... [z299](#)
    - `minipage` ..... [323](#)
    - `sloppypar` ..... [J62](#)
    - `thebibliography` ..... [417](#)
    - `verbatim*` ..... [y294](#)
  - `\epsilon` ..... [t242](#)
  - `\eqnarray` ..... [z316](#), [z363](#)
  - `eqnarray (environment)` ..... [z311](#), [z436](#)
  - `eqnarray* (environment)` ..... [z362](#)
  - `\eqno` ..... [z305](#)
  - `\equation` ..... [z304](#)
  - `equation (environment)` ..... [z303](#), [z424](#)
  - `\equiv` ..... [t409](#)
  - `\err@rel@i` ..... [q12](#), [q99](#), [q132](#), [q136](#)
  - `\errhelp` ..... [a217](#), [c31](#), [g39](#), [g66](#), [M12](#), [O237](#), [O537](#)
  - `\errmessage` ..... [a4](#), [a58](#), [a222](#), [b164](#), [b178](#), [b293](#), [c32](#), [g47](#), [g72](#), [o395](#), [o430](#), [p379](#), [p479](#), [q65](#), [M16](#), [N61](#), [O49](#), [O239](#)
  - `\error@fontshape` ..... [o356](#), [o371](#), [o396](#), [o431](#), [p107](#), [p481](#), [r222](#)
  - `\errorcontextlines` ..... [b327](#), [b454](#), [b470](#), [b485](#), [b498](#), [b515](#), [g163](#)
  - `\errorstopmode` ..... [b443](#), [O545](#)
  - `\escapechar` ..... [d101](#), [d144](#), [d148](#), [d156](#), [k228](#), [o300](#), [o465](#), [p183](#), [r58](#), [r86](#), [r147](#), [r177](#), [r221](#), [N203](#)
  - `\et@xmaxfam` ..... [N20](#), [N24](#), [N28](#), [N36](#)
  - `\et@xmaxregs` ..... [N27](#), [N29](#), [N30](#), [N31](#), [N32](#), [N33](#), [N34](#), [N35](#)
  - `\eta` ..... [t244](#)
  - `\etatcatcode` ..... [N783](#)
  - `\eTeXversion` ..... [a57](#)
  - `\evensidemargin` ... [K73](#), [K613](#), [K672](#)
  - `\every@math@size` ... [o42](#), [p189](#), [p201](#)
  - `\everycr` .. [b423](#), [z192](#), [z195](#), [z324](#), [z451](#)
  - `\everydisplay` ..... [o278](#), [o279](#), [o284](#)
  - `\everyjob` ..... [c37](#), [c42](#), [c47](#), [r241](#), [N207](#), [N208](#), [N249](#), [N250](#), [O312](#), [O506](#), [O507](#), [O509](#)
  - `\everymath` ..... [o277](#), [o279](#), [o282](#)
  - `\everypar` ..... [69](#), [k41](#), [k99](#), [o518](#), [o531](#), [o578](#), [y87](#), [y234](#), [y256](#), [A129](#), [A131](#), [A135](#), [A136](#), [A180](#), [A197](#), [B247](#), [B268](#), [C69](#), [F48](#), [F96](#), [F107](#), [F127](#), [F136](#), [G187](#), [K165](#), [K192](#), [K1151](#), [K1317](#)
  - `\execute@size@function` ..... [p316](#), [p344](#), [p358](#), [p375](#)
  - `\ExecuteOptions` ..... [l1531](#), [p57](#), [p70](#), [L252](#)
  - `\exhyphenpenalty` ..... [b309](#), [b396](#)
  - `\exists` ..... [t294](#)
  - `\exp` ..... [z31](#)
  - `\external@font` ..... [p84](#), [p87](#), [p98](#), [p102](#), [p104](#), [p345](#), [p359](#), [p421](#), [p455](#), [p505](#), [p507](#), [p509](#)
  - `\extra@def` ..... [q9](#), [q84](#)
  - `\extracolsep` ..... [C155](#)
  - `\extract@alph@from@version` ..... [o471](#), [o477](#), [r151](#), [r182](#)
  - `\extract@default@composite` ..... [l1009](#), [l1016](#)
  - `\extract@default@composite@a` ... [l1018](#), [l1022](#)
  - `\extract@default@composite@b` ... [l1020](#), [l1024](#)
  - `\extract@font` ..... [o311](#), [p81](#)
  - `\extract@fontinfo` ..... [p312](#), [p319](#)
  - `\extract@rangefontinfo` ..... [p329](#), [p336](#), [p355](#), [p388](#)
  - `\extract@sizefn` ..... [p304](#), [p326](#)
  - `\extrafloats` ..... [b152](#), [b189](#), [b263](#)
- ## F
- `\f@baselineskip` ..... [l1159](#), [o250](#), [o257](#), [o382](#), [p119](#), [p136](#), [p140](#), [p155](#), [p169](#), [p180](#), [p194](#)
  - `\f@depth` ..... [G291](#), [K345](#)
  - `\f@encoding` ..... [l176](#), [o215](#), [o234](#), [o237](#), [o238](#), [o240](#), [o259](#), [o291](#), [o296](#), [o315](#), [o317](#), [o319](#), [o324](#), [o326](#), [o360](#), [o392](#), [o427](#), [p91](#), [p261](#), [p471](#), [r207](#), [N247](#), [N262](#), [N270](#)
  - `\f@family` ..... [l1548](#), [l1551](#), [l1565](#), [l1575](#), [l1581](#), [l1796](#), [o243](#), [o253](#), [o292](#), [o296](#), [o315](#), [o317](#), [o319](#), [o324](#), [o326](#), [o378](#), [o403](#), [o438](#), [p91](#), [r207](#)
  - `\f@linespread` ... [o253](#), [p118](#), [p137](#), [p138](#), [p141](#), [p149](#), [p152](#), [p163](#), [p166](#)
  - `\f@series` ..... [j14](#), [o243](#), [o254](#), [o293](#), [o296](#), [o379](#), [o400](#), [o435](#), [s81](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx, e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx, j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx, o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx, t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx, y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx, D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx, I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx, N=ltluatex.dtx, O=ltfinal.dtx

`\f@shape` ..... [o243](#),  
                   [o255](#), [o294](#), [o296](#), [o380](#), [o398](#), [o433](#)  
`\f@size` [l178](#), [l1158](#), [l1583](#), [o52](#), [o250](#),  
                   [o256](#), [o295](#), [o381](#), [o420](#), [o454](#),  
                   [o496](#), [o497](#), [o500](#), [o501](#), [p119](#),  
                   [p121](#), [p134](#), [p154](#), [p169](#), [p172](#),  
                   [p175](#), [p180](#), [p187](#), [p194](#), [p206](#),  
                   [p209](#), [p215](#), [p221](#), [p238](#), [p239](#),  
                   [p242](#), [p247](#), [p313](#), [p320](#), [p339](#),  
                   [p341](#), [p356](#), [p407](#), [p409](#), [p411](#),  
                   [p427](#), [p428](#), [p433](#), [p447](#), [p459](#),  
                   [p464](#), [p476](#), [p484](#), [p489](#), [p497](#), [p511](#)  
`\f@user@size` .. [p427](#), [p432](#), [p476](#), [p489](#)  
`\fam` ..... [b98](#), [o15](#), [N20](#), [N24](#), [N36](#)  
`\familydefault` ..... [r238](#), [s95](#), [t90](#)  
`\fbox` ..... [322](#), [B128](#), [B141](#), [B148](#)  
`\fboxrule` ..... [B126](#), [B162](#), [B165](#),  
                   [B171](#), [B173](#), [B180](#), [B181](#), [O84](#)  
`\fboxsep` ..... [B126](#), [B132](#),  
                   [B161](#), [B166](#), [B176](#), [B178](#), [O83](#)  
`\filbreak` ..... [b400](#)  
`\filec@ntents` .....  
                   ..... [L544](#), [L547](#), [L550](#), [L560](#),  
                   [L581](#), [L676](#), [L698](#), [L786](#), [L1001](#)  
`\filec@ntents@checkdir` .....  
                   ..... [L566](#), [L568](#), [L582](#), [L683](#)  
`\filec@ntents@force` ..... [L562](#), [L679](#)  
`\filec@ntents@noheader` .. [L564](#), [L681](#)  
`\filec@ntents@nosearch` .. [L565](#), [L682](#)  
`\filec@ntents@opt` .....  
                   ..... [L547](#), [L550](#), [L552](#), [L678](#)  
`\filec@ntents@overwrite` . [L563](#), [L680](#)  
`\filec@ntents@where` .....  
                   ..... [L567](#), [L569](#), [L594](#), [L684](#)  
`\filecontents` ..... [L536](#)  
`filecontents (environment)` ..... [497](#)  
`\filename@area` .. [a246](#), [a252](#), [a259](#),  
                   [a265](#), [a272](#), [a278](#), [a285](#), [k341](#),  
                   [k352](#), [k376](#), [k379](#), [k393](#), [k405](#), [k407](#)  
`\filename@base` .. [a295](#), [a302](#), [a315](#),  
                   [k341](#), [k352](#), [k376](#), [k379](#), [k400](#), [k405](#)  
`\filename@dot` ..... [a313](#), [a319](#)  
`\filename@dots` ..... [a297](#), [a299](#), [a304](#)  
`\filename@ext` .....  
                   . [a294](#), [a301](#), [a311](#), [a313](#), [k342](#),  
                   [k353](#), [k372](#), [k373](#), [k376](#), [k379](#), [k401](#)  
`\filename@parse` ..... [1](#), [6](#),  
                   [a110](#), [a242](#), [k339](#), [k350](#), [k371](#), [k398](#)  
`\filename@path` .. [a247](#), [a248](#), [a253](#),  
                   [a260](#), [a261](#), [a266](#), [a273](#), [a274](#), [a279](#)  
`\filename@simple` .... [a250](#), [a263](#),  
                   [a276](#), [a286](#), [a290](#), [a292](#), [a307](#), [a309](#)  
`\fill` ..... [i354](#)  
`\finalhyphendemerits` ..... [b318](#)

`\finph@nt` .....  
                   [z104](#), [z106](#), [z110](#), [z111](#), [z119](#), [z120](#)  
`\finsm@sh` .....  
                   [z134](#), [z136](#), [z140](#), [z141](#), [z145](#), [z146](#)  
`\firstmark` .. [J51](#), [K647](#), [K706](#), [K2217](#)  
`\fix@penalty` ..... [v84](#)  
`\fixed@sfcnt` ..... [p501](#), [p502](#), [p503](#)  
`\fl@trace` ..... [K240](#),  
                   [K267](#), [K323](#), [K351](#), [K358](#), [K379](#),  
                   [K426](#), [K472](#), [K525](#), [K540](#), [K541](#),  
                   [K542](#), [K543](#), [K554](#), [K555](#), [K556](#),  
                   [K557](#), [K558](#), [K568](#), [K781](#), [K800](#),  
                   [K819](#), [K837](#), [K839](#), [K978](#), [K982](#),  
                   [K994](#), [K995](#), [K996](#), [K997](#),  
                   [K1003](#), [K1006](#), [K1014](#), [K1018](#),  
                   [K1029](#), [K1034](#), [K1039](#), [K1040](#),  
                   [K1041](#), [K1042](#), [K1049](#), [K1052](#),  
                   [K1060](#), [K1071](#), [K1077](#), [K1082](#),  
                   [K1087](#), [K1093](#), [K1094](#), [K1099](#),  
                   [K1104](#), [K1105](#), [K1106](#), [K1114](#),  
                   [K1118](#), [K1123](#), [K1127](#), [K1132](#),  
                   [K1143](#), [K1144](#), [K1146](#), [K1164](#),  
                   [K1173](#), [K1179](#), [K1188](#), [K1191](#),  
                   [K1197](#), [K1207](#), [K1211](#), [K1221](#),  
                   [K1227](#), [K1233](#), [K1239](#), [K1246](#),  
                   [K1248](#), [K1254](#), [K1259](#), [K1261](#),  
                   [K1263](#), [K1271](#), [K1276](#), [K1282](#),  
                   [K1287](#), [K1293](#), [K1307](#), [K1308](#),  
                   [K1311](#), [K1332](#), [K1341](#), [K1347](#),  
                   [K1356](#), [K1359](#), [K1366](#), [K1376](#),  
                   [K1380](#), [K1392](#), [K1398](#), [K1403](#),  
                   [K1408](#), [K1412](#), [K1416](#), [K1417](#),  
                   [K1424](#), [K1429](#), [K1433](#), [K1440](#),  
                   [K1449](#), [K1453](#), [K1457](#), [K1458](#),  
                   [K1462](#), [K1463](#), [K1473](#), [K1479](#),  
                   [K1485](#), [K1491](#), [K1495](#), [K1501](#),  
                   [K1503](#), [K1511](#), [K1516](#), [K1521](#),  
                   [K1529](#), [K1538](#), [K1543](#), [K1548](#),  
                   [K1550](#), [K1555](#), [K1557](#), [K1568](#),  
                   [K1574](#), [K1584](#), [K1590](#), [K1594](#),  
                   [K1595](#), [K1600](#), [K1601](#), [K1607](#),  
                   [K1610](#), [K1611](#), [K1612](#), [K1619](#),  
                   [K1620](#), [K1621](#), [K1629](#), [K1634](#),  
                   [K1646](#), [K1647](#), [K1654](#), [K1657](#),  
                   [K1665](#), [K1669](#), [K1673](#), [K1674](#),  
                   [K1678](#), [K1679](#), [K1689](#), [K1695](#),  
                   [K1705](#), [K1711](#), [K1715](#), [K1716](#),  
                   [K1722](#), [K1723](#), [K1730](#), [K1733](#),  
                   [K1734](#), [K1735](#), [K1743](#), [K1744](#),  
                   [K1745](#), [K1754](#), [K1759](#), [K1772](#),  
                   [K1774](#), [K1781](#), [K1784](#), [K1793](#),  
                   [K1797](#), [K1801](#), [K1802](#), [K1806](#),  
                   [K1807](#), [K1859](#), [K1864](#), [K1870](#),  
                   [K1880](#), [K1887](#), [K1897](#), [K1993](#),

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=ltpictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx



- K2006, K2007, K2011, K2014,  
 K2016, K2019, K2022, K2024,  
 K2065, K2072, K2077, K2083,  
 K2088, K2092, K2098, K2106,  
 K2108, K2115, K2120, K2125,  
 K2127, K2133, K2135, K2142,  
 K2171, K2173, K2188, K2190,  
 K2204, K2229, K2233, K2238,  
 K2250, K2267, K2272, K2280  
 \fl@tracemessage ..... [K1897](#)  
 \fl@traceval ..... [K1897](#)  
 \flat ..... [t297](#)  
 \float@count .. [b51](#), [b52](#), [b53](#), [b62](#),  
                   [b188](#), [b205](#), [b210](#), [b212](#), [b213](#), [b222](#)  
 \floatingpenalty ..... [G412](#)  
 \floatpagefraction ..... [G278](#), [K2298](#)  
 \floatsep ..... [K726](#),  
                   [K744](#), [K751](#), [K2104](#), [K2154](#), [K2303](#)  
 \flushbottom ..... [J55](#)  
 \flushleft ..... [y202](#)  
 flushleft (environment) ..... [y202](#)  
 \flushright ..... [y204](#)  
 flushright (environment) ..... [y204](#)  
 \fmtname ..... [c1](#), [c38](#),  
                   [c40](#), [c43](#), [c45](#), [c48](#), [c56](#), [L319](#), [L323](#)  
 \fmtversion .. [c1](#), [c19](#), [c38](#), [c40](#), [c43](#),  
                   [c45](#), [c48](#), [c56](#), [c84](#), [g2](#), [C1](#), [D1](#),  
                   [K4](#), [L336](#), [L339](#), [N263](#), [O490](#), [O516](#)  
 \fmtversion@topatch ..... [O488](#),  
                   [O490](#), [O502](#), [O503](#), [O515](#), [O523](#)  
 \fnsymbol ..... [155](#), [m107](#)  
 \font ..... [b428](#), [b433](#), [d402](#), [d405](#),  
                   [l294](#), [l295](#), [l296](#), [l433](#), [l440](#), [l790](#),  
                   [l797](#), [l982](#), [l983](#), [l1007](#), [l1155](#),  
                   [o45](#), [o51](#), [o53](#), [p84](#), [s35](#), [s42](#),  
                   [s68](#), [s80](#), [u8](#), [u9](#), [u10](#), [v68](#), [y255](#)  
 \font@info .... [p99](#), [p319](#), [p388](#), [p393](#)  
 \font@name ..... [l177](#),  
                   [l180](#), [o50](#), [o158](#), [o160](#), [o287](#),  
                   [o302](#), [o419](#), [o453](#), [p84](#), [p88](#),  
                   [p90](#), [p105](#), [p120](#), [p123](#), [p126](#),  
                   [p284](#), [p285](#), [p286](#), [p287](#), [p288](#), [p293](#)  
 \font@submax ..... [p395](#), [p424](#),  
                   [p425](#), [y22](#), [y24](#), [O229](#), [O231](#), [O240](#)  
 \fontdimen ..... [b428](#), [b433](#), [l294](#),  
                   [l295](#), [l296](#), [l433](#), [l440](#), [l790](#), [l797](#),  
                   [s35](#), [s42](#), [s80](#), [v68](#), [D38](#), [D40](#), [D365](#)  
 \fontencding ..... [l1495](#), [o215](#),  
                   [o246](#), [r237](#), [t15](#), [t18](#), [t59](#), [t66](#),  
                   [t75](#), [t77](#), [N246](#), [N247](#), [N269](#), [N270](#)  
 \fontfamily ..... [l1567](#), [o243](#), [r238](#),  
                   [s6](#), [s9](#), [s12](#), [s118](#), [t50](#), [t61](#), [t68](#), [t79](#)  
 \fontname ..... [l983](#), [o53](#)  
 \fontseries .. [o243](#), [r239](#), [s15](#), [s18](#), [s119](#)  
 \fontshape ..... [l443](#), [l800](#),  
                   [o243](#), [r240](#), [s21](#), [s24](#), [s27](#), [s30](#), [s120](#)  
 \fontsize ..... [j6](#), [l299](#),  
                   [l325](#), [l357](#), [l1157](#), [l1193](#), [l1585](#),  
                   [o43](#), [o251](#), [s74](#), [s121](#), [G381](#), [G389](#)  
 \fontsubfuzz ..... [p395](#), [p429](#), [y22](#)  
 \footins ..... [G366](#), [G408](#),  
                   [K314](#), [K315](#), [K316](#), [K317](#), [K375](#),  
                   [K422](#), [K482](#), [K490](#), [K494](#), [K517](#)  
 \footnote ..... [G399](#)  
 \footnotemark ..... [F10](#), [G421](#)  
 \footnoterule ..... [B315](#), [G370](#), [K493](#)  
 \footnotesep . [B334](#), [G398](#), [G411](#), [G419](#)  
 \footnotesize ..... [B327](#), [G409](#)  
 \footnotetext ..... [F12](#), [G438](#)  
 \footskip ..... [K77](#), [K637](#), [K696](#)  
 \forall ..... [t293](#)  
 \fps@dbl ..... [G34](#)  
 \frac ..... [z308](#)  
 \frame ..... [B112](#), [B188](#)  
 \framebox ..... [322](#), [B135](#)  
 \frenchspacing ..... [b353](#), [d427](#),  
                   [d448](#), [k44](#), [k102](#), [y260](#), [y296](#), [y350](#)  
 \frown ..... [t412](#)  
 \frozen@everydisplay .... [o277](#), [o283](#)  
 \frozen@everymath ..... [o277](#), [o281](#)  
 \fussy ..... [J64](#)  
 \futurelet ..... [d368](#),  
                   [d382](#), [i320](#), [i328](#), [v66](#), [z210](#), [C335](#)
- ## G
- \g@addto@macro [L480](#), [L486](#), [L490](#), [L491](#)  
 \G@refundefinedfalse ..... [x5](#)  
 \G@refundefinedtrue . [x3](#), [x12](#), [l21](#), [l44](#)  
 \Gamma ..... [t267](#)  
 \gamma ..... [t240](#)  
 \gcd ..... [z33](#)  
 \ge ..... [t383](#)  
 \gen@sfcnt ..... [p456](#), [p457](#), [p458](#)  
 \genb@sfcnt ..... [p461](#), [p462](#), [p463](#)  
 \genb@x ..... [p464](#), [p466](#)  
 \genb@y ..... [p466](#)  
 \GenericError [g18](#), [g85](#), [g111](#), [g137](#), [p62](#)  
 \GenericInfo .....  
                   [c85](#), [c88](#), [c93](#), [g4](#), [g104](#), [g130](#),  
                   [g155](#), [p31](#), [p34](#), [p39](#), [p75](#), [L927](#)  
 \GenericWarning ..... [g11](#),  
                   [g94](#), [g120](#), [g146](#), [p42](#), [p47](#), [p50](#), [p78](#)  
 \geq ..... [t382](#), [t383](#)  
 \get@cdp ..... [r356](#), [r364](#), [r397](#)  
 \get@external@font ... [p83](#), [p96](#), [p490](#)  
 \getanddefine@fonts .. [o466](#), [o484](#),  
                   [p274](#), [r59](#), [r87](#), [r132](#), [r148](#), [r178](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

- r263, r327, r361, r363, r380,  
 r503, r504, r536, r537, r1043, r1044  
 \GetFileInfo ..... t3  
 \gets ..... t401  
 \gg ..... t396  
 \glb@currsiz ..... k39, k97,  
 o274, p171, p206, p210, p216, p239  
 \glb@settings . o275, p171, p218, p249  
 \globaldefs .....  
 .. o467, p185, r60, r89, r149, r180  
 \glossary ..... 415, F176,  
 H23, H35, J24, J32, K621, K680  
 \glossaryentry ..... H32  
 \goodbreak ..... b400, d428, d449  
 \grave ..... t478  
 \group@elt ..... r35,  
 r261, r298, r299, r320, r324, r1075  
 \group@list ..... r265, r305, r318,  
 r323, r324, r353, r579, r627,  
 r688, r777, r780, r836, r839,  
 r892, r895, r960, r963, r1030, r1081  
 \guillemetleft ..... l534, l764, l1052  
 \guillemetright .... l535, l765, l1068  
 \guillemotleft ..... l537, l767, l1054  
 \guillemotright .... l538, l768, l1070  
 \guilsinglleft ..... l539, l1122  
 \guilsinglright ..... l540, l1123
- ## H
- \H ..... g24, l228, l382,  
 l463, l592, l600, l619, l627, l744,  
 l1185, l1324, l1325, l1352, l1353  
 \h@false ..... z81  
 \h@true ..... z82, z83  
 \halign ... b423, z127, z197, z324, z451  
 \hangindent ..... F139  
 \hat ..... t484  
 \hb@xt@ ..... b438,  
 d14, l419, z197, z329, z375,  
 z390, z402, z429, z459, B44,  
 B59, B160, B402, B406, B407,  
 C37, D13, D23, D32, D123,  
 D157, D160, D163, D165, D167,  
 D238, D279, D322, D417, F197,  
 F220, F227, K630, K640, K689,  
 K699, K1843, K2223, K2224,  
 K2228, K2255, K2256, K2262  
 \hbadness b305, o521, o528, o563, o582  
 \hbar ..... t304  
 \headheight ..... K75, K626, K685  
 \headsep ..... K76, K635, K694  
 \heartsuit ..... t302  
 \height ..... l1161, B31, B34
- \hexnumber@ ..... r600, r608, r643,  
 r651, r672, r682, r708, r716,  
 r724, r733, r736, r745, r746,  
 r789, r797, r848, r856, r904,  
 r912, r930, r931, r941, r942,  
 r947, r973, r981, r986, r988, s85  
 \hfuzz .. b328, o529, J60, J61, J67, J68  
 \hgl@ ..... b393, b394  
 \hglue ..... b390  
 \hideoutput ..... b488  
 \hideskip ..... b296, b414  
 \hidewidth ..... b414, l324,  
 l326, l355, l359, l387, l388, l391,  
 l394, l470, l471, l475, l478, l480,  
 l483, l495, l500, l516, l751, l752,  
 l755, l758, l825, l828, l1192, l1194  
 \hline ..... C334, C337  
 \hmode@bgroup ..... l67,  
 l73, l324, l353, l387, l393, l421,  
 l432, l439, l470, l477, l480, l482,  
 l490, l506, l721, l751, l757, l789,  
 l796, l824, l827, l873, l1192, v7  
 \hmode@start@before@group .....  
 ..... l68, l149, l151, l157, l182  
 \hom ..... z29  
 \hookleftarrow ..... t441  
 \hookrightarrow ..... t439  
 \hphantom ..... z75  
 \hrule ..... b391, b435,  
 i296, i304, l288, l291, t309,  
 t579, B118, B123, B171, B181,  
 C335, C352, D281, D324, G371  
 \hrulefill ..... b435, d429, d450  
 \hspace ..... i350  
 \Hwithstroke ..... l488, l1152  
 \hwithstroke ..... l504, l1153  
 \hyphenation ..... l203  
 \hyphenchar d395, d402, d405, d412, y255  
 \hyphenpenalty ..... b308, o535, o567
- ## I
- \I b359, L667, L758, L778, O188, O451  
 \i ..... l245, l399,  
 l446, l447, l448, l449, l450, l451,  
 l541, l578, l579, l671, l673, l675,  
 l677, l769, l1088, l1234, l1236,  
 l1238, l1240, l1291, l1294, l1297,  
 l1300, l1370, O192, O455, O462  
 \ialign ..... b423, b425,  
 t306, t420, t491, t494, t498,  
 t501, z155, z157, z176, C179, D52  
 \IeC ..... O253, O257, O364  
 \if@afterindent ..... F124, F131  
 \if@compatibility ..... L2, L278

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltboutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

`\if@endpe` ..... [y138](#), [A138](#)  
`\if@eqnsw` ..... [z311](#), [z360](#)  
`\if@fcolmade` ..... [K95](#),  
[K264](#), [K394](#), [K403](#), [K441](#), [K451](#),  
[K779](#), [K799](#), [K817](#), [K846](#), [K926](#),  
[K2170](#), [K2187](#), [K2237](#), [K2277](#)  
`\if@filesw` [k7](#), [k34](#), [k92](#), [k180](#), [k192](#),  
[k199](#), [k208](#), [y14](#), [y28](#), [F153](#),  
[L592](#), [L612](#), [I4](#), [I8](#), [I19](#), [I28](#), [I36](#), [I43](#)  
`\if@firstamp` ..... [C227](#)  
`\if@firstcolumn` [K95](#), [K246](#), [K279](#),  
[K396](#), [K444](#), [K1815](#), [K2201](#), [K2246](#)  
`\if@ignore` ..... [y4](#), [y139](#)  
`\if@includeinrelease` [c68](#), [c71](#), [c98](#), [d417](#)  
`\if@inlabel` ..... [A28](#), [A65](#),  
[A102](#), [A160](#), [A183](#), [K161](#), [K188](#)  
`\if@insert` ..... [K95](#), [K1057](#),  
[K1169](#), [K1203](#), [K1337](#), [K1372](#),  
[K1446](#), [K1535](#), [K1662](#), [K1790](#)  
`\if@minipage` ..... [i209](#), [i226](#), [i261](#),  
[y219](#), [y241](#), [A149](#), [B278](#), [C67](#), [G20](#)  
`\if@mparswitch` ..... [K95](#), [K1817](#)  
`\if@multiplelabels` ..... [x31](#)  
`\if@negarg` .... [D56](#), [D78](#), [D92](#), [D131](#)  
`\if@newlist` ..... [y261](#),  
[A29](#), [A33](#), [A69](#), [A78](#), [A106](#),  
[A166](#), [K599](#), [K644](#), [K657](#), [K703](#)  
`\if@nmbrlist` ..... [A33](#), [A201](#)  
`\if@no@font@opt` ..... [q16](#), [q110](#), [q129](#)  
`\if@nobreak` .....  
[i94](#), [i121](#), [i228](#), [i263](#), [k131](#), [k143](#),  
[A167](#), [A192](#), [B241](#), [B262](#), [F47](#),  
[F128](#), [G180](#), [G349](#), [J29](#), [J37](#),  
[K165](#), [K192](#), [K335](#), [K1148](#), [K1314](#)  
`\if@noitemarg` ..... [A32](#), [A199](#)  
`\if@noparitem` ..... [A30](#), [A157](#)  
`\if@noparlist` ..... [A31](#), [A114](#)  
`\if@noskipsec` [i121](#), [A58](#), [B242](#), [B263](#),  
[F38](#), [F40](#), [F97](#), [G350](#), [K155](#), [K182](#)  
`\if@ovb` [D213](#), [D266](#), [D271](#), [D310](#), [D315](#)  
`\if@ovhline` ..... [D245](#), [D281](#), [D291](#)  
`\if@ovl` [D213](#), [D264](#), [D283](#), [D306](#), [D325](#)  
`\if@ovr` [D213](#), [D263](#), [D280](#), [D305](#), [D323](#)  
`\if@ovt` [D213](#), [D265](#), [D276](#), [D309](#), [D319](#)  
`\if@ovvline` ..... [D245](#), [D274](#), [D290](#)  
`\if@partsw` ..... [k7](#), [k184](#)  
`\if@pboxsw` ..... [B233](#), [B336](#)  
`\if@reversemargin` ..... [K101](#), [K1820](#)  
`\if@reversemarginpar` ..... [K95](#)  
`\if@rjfield` ..... [C19](#), [C33](#)  
`\if@specialpage` ... [K95](#), [K606](#), [K664](#)  
`\if@tempswa` ..... [a78](#), [a79](#),  
[a80](#), [b259](#), [e9](#), [k190](#), [o63](#), [o561](#),  
[r286](#), [r341](#), [r405](#), [r486](#), [r1074](#),  
[y30](#), [y226](#), [y247](#), [K990](#), [K1026](#),  
[K1626](#), [K1751](#), [L624](#), [L714](#), [I52](#)  
`\if@test` ..... [K12](#), [K13](#), [K887](#),  
[K906](#), [K946](#), [K968](#), [K1032](#),  
[K1116](#), [K1125](#), [K1274](#), [K1285](#),  
[K1427](#), [K1514](#), [K1632](#), [K1757](#)  
`\if@twocolumn` ..... [k24](#), [k81](#),  
[G32](#), [G210](#), [G235](#), [K95](#), [K139](#),  
[K267](#), [K278](#), [K395](#), [K443](#), [K467](#),  
[K781](#), [K837](#), [K1814](#), [K2172](#), [K2189](#)  
`\if@twoside` ... [K95](#), [K138](#), [K609](#), [K667](#)  
`\ifcsname` ..... [d326](#), [d343](#), [L554](#)  
`\ifdt@p` ..... [z190](#), [z192](#)  
`\iff` ..... [t461](#)  
`\IfFileExists` ..... [88](#), [500](#), [a178](#),  
[k239](#), [k280](#), [k316](#), [k326](#), [k358](#), [O484](#)  
`\IfFileExists@` ..... [k241](#), [k242](#), [k278](#)  
`\iffontchar` ..... [l1007](#), [l1155](#)  
`\ifG@refundefined` ..... [x3](#), [x4](#), [x5](#)  
`\ifh@` ..... [z76](#), [z114](#), [z123](#)  
`\ifin@` ..... [l1485](#), [l1488](#),  
[q50](#), [q52](#), [r1](#), [r22](#), [r250](#), [r352](#),  
[r354](#), [r415](#), [r428](#), [r498](#), [r500](#),  
[r528](#), [r580](#), [r594](#), [r628](#), [r640](#),  
[r689](#), [r705](#), [r778](#), [r781](#), [r803](#),  
[r837](#), [r840](#), [r861](#), [r893](#), [r896](#),  
[r958](#), [r961](#), [r964](#), [r1031](#), [r1033](#),  
[r1062](#), [L113](#), [L131](#), [L213](#), [L225](#)  
`\ifinner` ..... [z231](#),  
[z239](#), [z259](#), [z286](#), [G57](#), [G126](#), [G315](#)  
`\ifmath@fonts` ..... [o168](#), [p176](#)  
`\ifmaybe@ic` ..... [v65](#), [v74](#)  
`\ifnot@nil` ..... [p297](#), [p314](#), [p335](#)  
`\ifodd` ..... [r1005](#), [D172](#), [D192](#),  
[G68](#), [G137](#), [K21](#), [K138](#), [K610](#),  
[K668](#), [K982](#), [K985](#), [K1018](#),  
[K1021](#), [K1132](#), [K1135](#), [K1294](#),  
[K1297](#), [K1574](#), [K1577](#), [K1695](#),  
[K1698](#), [K1818](#), [K2039](#), [K2047](#)  
`\IfTargetDateBefore` ..... [L986](#)  
`\iftc@forced` ..... [l1523](#), [l1533](#), [l1802](#)  
`\ifv@` ..... [z75](#), [z113](#), [z122](#)  
`\ifvbox` [K319](#), [K376](#), [K423](#), [K502](#), [K518](#)  
`\ignorespaces` . [i49](#), [i117](#), [i136](#), [i148](#),  
[i159](#), [i175](#), [i188](#), [i381](#), [k67](#), [k122](#),  
[o248](#), [y139](#), [y170](#), [y171](#), [z267](#),  
[z294](#), [A55](#), [A217](#), [B109](#), [B334](#),  
[C57](#), [C58](#), [C71](#), [C80](#), [C93](#), [C97](#),  
[C104](#), [C111](#), [C113](#), [C122](#), [C142](#),  
[C213](#), [C277](#), [C279](#), [C281](#), [C308](#),  
[D16](#), [D24](#), [D35](#), [D54](#), [D55](#), [E30](#),  
[E32](#), [F110](#), [G17](#), [G24](#), [G419](#), [I7](#), [I9](#)  
`\ignorespacesafterend` ..... [y7](#)  
`\IJ` ..... [l248](#), [l430](#), [l544](#), [l1089](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

`\ij` ..... 1247, 1428, 1543, 11090  
`\Im` ..... t284  
`\imath` ..... t279  
`\in` ..... t393, t422  
`\in@` ..... 11483, 11486,  
q49, q51, r1, r21, r249, r351,  
r353, r411, r424, r497, r499,  
r526, r578, r589, r626, r637,  
r687, r701, r776, r779, r799,  
r835, r838, r858, r891, r894,  
r955, r959, r962, r1029, r1032,  
r1060, L112, L129, L210, L224  
`\in@@` ..... r5, r6, r7, r9  
`\in@false` ..... r10  
`\in@true` ..... r12  
`\in_callback` ..... 534, N733  
`\include` ..... 88, k156, k171, k173  
`\IncludeInRelease` .....  
..... a18, a23, a290, a307,  
b49, b88, b103, b119, b125,  
b134, b139, b148, b154, b168,  
b182, b186, b220, b233, b278,  
b446, b481, b488, b535, c66,  
d246, d274, d300, d306, d322,  
d352, d395, d412, d421, d441,  
i5, i21, i54, i65, i106, i126, i140,  
i152, i165, i180, i221, i257, i339,  
i345, i359, i367, k12, k70, k148,  
k165, k224, k270, k311, k323,  
k335, k346, l75, l102, l146, l167,  
l321, l329, l350, l366, m24, m30,  
m46, m90, m127, m143, m151,  
m169, n5, n11, o174, o196,  
o353, o367, o388, o424, o511,  
o573, q2, q22, r49, r78, r138,  
r169, r575, r623, r669, r678,  
r773, r832, r927, r937, s32, s40,  
t55, t73, t583, t595, x38, x49,  
y45, y72, y91, y142, y155, y161,  
y176, y192, y216, y238, y265,  
y300, y331, y341, z79, z87,  
z109, z118, z139, z144, z152,  
z163, z226, z234, z244, z271,  
z382, z394, z406, z415, A125,  
A133, B4, B14, B72, B80, B136,  
B144, B190, B199, B236, B258,  
B338, B344, B364, B372, C125,  
C145, D241, D287, D422, D438,  
F5, F20, F161, F168, F181,  
F204, G35, G105, G206, G232,  
G280, G294, G383, G392, J20,  
J40, K24, K54, K151, K179,  
K345, K366, K371, K419,  
K591, K651, K794, K812, K873,  
K894, K930, K954, K1066,  
K1217, K1386, K1468, K1562,  
K1684, K1903, K1930, K2160,  
K2178, K2197, K2243, L60,  
L73, L103, L122, L253, L265,  
L356, L385, L543, L675, N3,  
N222, N245, N268, O8, O16,  
O23, O38, O57, O66, O73, O99,  
O132, O219, O224, O244, O337  
`\includeonly` .... 88, k146, k166, k167  
`\indent` ..... i364, A161, C69  
`\index` ..... 415, F176,  
H6, H18, J24, J32, K620, K679  
`\indexentry` ..... H15  
`\inf` ..... z25  
`\infty` ..... t286  
`\init@restore@glb@settings` .....  
..... p219, p222, p224  
`\init@restore@version` .....  
..... r62, r91, r108, r123, r124  
`\initcatcodetable` ..... N90  
`\input` ..... 88, 500,  
a68, a174, a177, a234, d7, k332,  
l1781, p16, q106, s130, s140,  
s150, t10, t11, t12, t13, t17, t22,  
t23, t24, t33, t34, t38, t39, t106,  
t107, t108, t109, t615, t616,  
t617, L282, N16, O97, O111,  
O136, O212, O301, O489, O525  
`\input@path` .....  
. 1, 6, a109, a131, a133, a139,  
a141, a147, a149, a154, a156,  
a166, a233, k245, k259, k283, k298  
`\inputencodingname` . O278, O300, O382  
`\InputIfFileExists` ..... 88, 500,  
k310, k324, k325, k338, k349,  
k359, k375, l1473, l1864, o324,  
s122, s132, s142, L443, M8, O206  
`\inputlineno` ..... a327, g165  
`\insc@unt` ..... b37, b51,  
b52, b53, b62, b90, b91, b92,  
b94, b236, b237, b238, b239,  
b240, b241, b252, b253, b254,  
b255, b256, b260, b262, b281,  
b282, b283, b284, b285, b286, K61  
`\insert` ... b243, b268, b270, b273,  
b288, G408, K517, K518, K1883  
`\install@mathalphabet` .....  
. o461, o478, o485, r269, r272,  
r358, r359, r456, r508, r511,  
r518, r533, r534, r541, r1045, r1047  
`\int` ..... t317  
`\interdisplaylinepenalty` .....  
..... i13, z55, z194, z346

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- `\interfootlinepenalty` ..... [b349](#)  
`\interfootnotelinepenalty` .....  
                                   **b349**, **i18**, **G410**  
`\interlinepenalty` .... **i11**, **o537**,  
                           **y227**, **y230**, **y248**, **y251**, **F67**,  
                           **F118**, **F188**, **F211**, **G410**, **K338**,  
                           **K1153**, **K1157**, **K1319**, **K1323**  
`\intertextsep` . **K1136**, **K1140**, **K1155**,  
                   **K1158**, **K1165**, **K1298**, **K1304**,  
                   **K1321**, **K1324**, **K1333**, [K2303](#)  
`\intop` ..... **t316**, **t317**  
`\iota` ..... **t246**  
`\is@range` ..... **p330**, [p331](#)  
`\ishortstack` ..... [D43](#)  
`\itdefault` ..... **s30**, [t86](#)  
`\item` ..... **g230**, **y172**, **y202**, **y204**,  
                   **y218**, **y240**, **z389**, **z401**, **z428**,  
                   [A141](#), **A219**, **C66**, **E36**, **E38**, **I4**, **I8**  
`\itemindent` . [A9](#), **A42**, **A95**, **A187**, **A208**  
`\itemize` ..... **A242**  
`itemize (environment)` ..... [A242](#)  
`\itemsep` ..... [A1](#), **A176**  
`\iterate` ..... **a81**, **a82**, [b379](#)  
`\itshape` ..... **l441**, **l798**, **s28**,  
                   **s29**, **s36**, **s43**, **v21**, **E36**, **E38**, **G375**
- J**
- `\J` ..... **O190**, **O453**  
`\j` ..... **l246**, **l400**,  
                   **l542**, **l770**, **l1098**, **l1304**, **l1384**, **O462**  
`\jmath` ..... **t280**  
`\Join` ..... **s105**  
`\joinrel` **t432**, **t439**, **t441**, **t443**, **t445**,  
                   **t447**, **t449**, **t451**, **t453**, **t457**, **t459**  
`\jot` ..... [z53](#), **z191**, **z353**
- K**
- `\k` ..... **l479**, **l581**, **l586**, **l608**,  
                   **l613**, **l689**, **l690**, **l748**, **l749**, **l803**,  
                   **l805**, **l810**, **l812**, **l1190**, **l1258**,  
                   **l1259**, **l1276**, **l1277**, **l1299**, **l1300**,  
                   **l1301**, **l1354**, **l1355**, **l1382**, **l1383**  
`\kappa` ..... **t247**  
`\ker` ..... **z27**  
`\kernel@ifnextchar` ..... **c76**,  
                   **d56**, **d75**, **d125**, [d369](#), **d384**, **L170**  
`\kernel@make@fragile` .....  
                   ..... [d304](#), **d444**, **d445**,  
                   **d446**, **d447**, **d448**, **d449**, **d450**,  
                   **d451**, **d452**, **d453**, **d454**, **d455**,  
                   **d456**, **d457**, **d458**, **d459**, **i24**, **i25**,  
                   **i26**, **i27**, **i28**, **l170**, **l171**, **y144**,  
                   **y145**, **y195**, **y196**, **y197**, **z90**,  
                   **z91**, **z92**, **z93**, **z166**, **z167**, **z168**,  
                   **C148**, **C149**, **C150**, **D441**, **D442**,  
                   **D443**, **D444**, **D445**, **D446**, **D447**,  
                   **D448**, **D449**, **D450**, **D451**, **D452**,  
                   **F23**, **F24**, **F25**, **F26**, **F27**, **J43**, **J44**  
`\kill` ..... **C142**, **C150**
- L**
- `\L` ..... **l240**, **l418**, **l524**,  
                   **l762**, **l1091**, **L664**, **L755**, **L777**, **O481**  
`\l` .. **l249**, **l420**, **l545**, **l771**, **l1092**, **O481**  
`\l@ngrel@x` .. **d49**, **d50**, [d51](#), **d95**, **d142**  
`\l@nohyphenation` .. **y223**, **y337**, [Q214](#)  
`\label` [x32](#), **F176**, **J24**, **J32**, **K619**, **K678**  
`\labelformat` .. **276**, **x39**, [x44](#), **x50**, **x56**  
`\labelsep` .. [A9](#), **A210**, **A216**, **E36**, **E38**  
`\labelwidth` [A9](#), **A93**, **A209**, **A211**, **A214**  
`\Lambda` ..... **t270**  
`\lambda` ..... **t248**  
`\land` ..... **t334**  
`\langle` ..... **t555**  
`\language` ..... **b35**, **b82**, **b84**,  
                   **b99**, **k50**, **y223**, **y337**, **K597**, **M10**  
`\last@fontshape` **o394**, **o412**, **o429**, **o446**  
`\lastbox` .. **o555**, **z180**, **z181**, **A130**,  
                   **A136**, **A185**, **F99**, **F132**, **K305**  
`\LastDeclaredEncoding` **o101**, [o104](#), **O378**  
`\lastnamedcs` ..... **d344**  
`\lastnodetype` .. **o548**, **o549**, **o550**, **o554**  
`\lastpenalty` ..... **o551**, **v95**, **v98**  
`\lastskip` ..... **b403**, **b404**,  
                   **b406**, **b408**, **i44**, **i102**, **i114**, **i133**,  
                   **i194**, **i195**, **i199**, **i201**, **i202**, **i210**,  
                   **i230**, **i233**, **i265**, **i268**, **i269**, **v85**,  
                   **v88**, **A115**, **A116**, **A150**, **A151**, **D36**  
`\LaTeX` ..... [j3](#), **j15**, **L627**, **L717**  
`\LaTeXe` ..... [j13](#)  
`\latexreleaseversion` ..... [c1](#)  
`\lbrace` ..... **l305**, **t559**  
`\lbrack` ..... [b363](#)  
`\lccode` ..... **g19**, **g20**, **g21**,  
                   **g22**, **g23**, **g24**, **l138**, **l1012**, **y286**,  
                   **y312**, **y355**, **O157**, **O174**, **O182**,  
                   **O189**, **O191**, **O192**, **O194**, **O196**,  
                   **O197**, **O198**, **O199**, **O437**, **O445**,  
                   **O452**, **O454**, **O455**, **O457**, **O459**  
`\lceil` ..... **t563**  
`\ldotp` ..... **t462**, **t465**, **t580**  
`\ldots` ..... **l319**, **t466**  
`\le` ..... **t381**  
`\leaders` ..... **b435**, **t309**, **t519**,  
                   **t520**, **t522**, **t523**, **C352**, **D274**,  
                   **D281**, **D318**, **D324**, **F193**, **F216**  
`\leadsto` ..... **s108**

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- \leavevmode    [b394](#), [b421](#), [b424](#), [b435](#),  
                  [b437](#), [i317](#), [i331](#), [l73](#), [l182](#), [l286](#),  
                  [l288](#), [l390](#), [l419](#), [l423](#), [l426](#), [l473](#),  
                  [l754](#), [l787](#), [l1579](#), [v106](#), [y227](#),  
                  [y248](#), [y261](#), [y272](#), [y280](#), [y333](#),  
                  [y343](#), [y356](#), [z389](#), [z401](#), [z428](#),  
                  [A58](#), [A103](#), [B8](#), [B17](#), [B24](#), [B111](#),  
                  [B113](#), [B129](#), [B157](#), [B218](#), [B294](#),  
                  [B351](#), [B368](#), [B375](#), [C166](#), [D45](#),  
                  [D167](#), [F40](#), [F189](#), [F201](#), [F212](#),  
                  [G433](#), [K157](#), [K162](#), [K184](#), [K189](#), [I14](#)
- \leavevmode@ifvmode    .....
- ... [i361](#), [i362](#), [i363](#), [i364](#), [i372](#),  
          [t585](#), [t587](#), [t589](#), [t591](#), [z115](#), [z141](#)
- \left    .. [t586](#), [t588](#), [t590](#), [t592](#), [t597](#),  
          [t598](#), [t599](#), [t600](#), [z154](#), [z160](#), [z182](#)
- \Leftarrow    .....
- \leftarrow    .....
- . [t400](#), [t401](#), [t441](#), [t451](#), [t457](#), [t511](#)
- \leftarrowfill    .....
- \lefteqn    .....
- \leftharpoonup    .....
- \leftharpoondown    .....
- \leftharpoonup    .....
- \lefthyphenmin    .....
- \leftline    .....
- \leftmargin    .....
- . [A9](#), [A52](#), [A53](#), [A94](#), [A146](#), [A148](#)
- \leftmargini    .....
- \leftmarginii    .....
- \leftmarginiii    .....
- \leftmarginiv    .....
- \leftmarginv    .....
- \leftmarginvi    .....
- \leftmark    .....
- \Leftrightarrow    .....
- \leftrightharpoonup    .....
- \leftskip    .. [b416](#), [o532](#), [y180](#), [y184](#),  
          [y188](#), [y220](#), [y242](#), [A74](#), [B250](#),  
          [B271](#), [F186](#), [F191](#), [F209](#), [F214](#)
- \leq    .....
- \lfloor    .....
- \lg    .....
- \lgroup    .....
- \lhd    .....
- \lhook    .....
- \lim    .....
- \liminf    .....
- \limits    .....
- \limsup    .....
- \line    ... [g219](#), [D57](#), [D236](#), [D427](#), [D444](#)
- \linebreak    .....
- \linepenalty    .....
- \lineskip    .....
- b357**, [b389](#),  
          **b424**, [t419](#), [z187](#), [B252](#), [B272](#),  
          **C59**, [C186](#), [D47](#), [D168](#), [K622](#), [K681](#)
- \lineskiplimit    .. [b358](#), [b389](#), [b426](#),  
          **b427**, [t419](#), [t471](#), [z189](#), [z193](#),  
          **B238**, [B253](#), [B260](#), [K622](#), [K681](#)
- \linespread    .....
- \linethickness    .....
- \linewidth    .. [k28](#), [k86](#), [z252](#), [z278](#),  
          [z390](#), [z402](#), [z429](#), [z433](#), [z451](#),  
          **A15**, [A51](#), [A52](#), [A54](#), [B248](#),  
          **B269**, [C36](#), [G266](#), [K146](#), [K205](#)
- \list    .....
- \listfiles    .....
- \listparindent    .....
- \ll    .....
- \llap    .....
- \lmoustache    .....
- \ln    .....
- \lnot    .....
- \load@onefilewithoptions    .....
- \LoadClass    .....
- L288**, [L302](#), [L460](#), [L519](#), [L527](#), [L528](#)
- \LoadClassWithOptions    .....
- \loccount    .....
- \log    .....
- \loggingall    .....
- \loggingoutput    .....
- \Longleftarrow    .....
- \longleftarrow    .....
- \Longleftrightarrow    .....
- \longleftrightarrow    .....
- \longmapsto    .....
- \Longrightarrow    .....
- \longrightarrow    .....
- \loop    .....
- a81**, [b379](#),  
          **o546**, [C358](#), [L572](#), [L636](#), [L688](#),  
          **L726**, [N150](#), [N159](#), [O261](#), [O272](#),  
          **O282**, [O293](#), [O323](#), [O349](#), [O359](#)
- \lor    .....
- \lower    .....
- D15**, [D76](#), [D163](#), [D164](#), [D201](#), [D202](#)
- \lower@bound    .....
- \lowercase    .. [g26](#), [l139](#), [l1013](#), [l1471](#),  
          **o265**, [o323](#), [y290](#), [y316](#), [y356](#), [O477](#)
- \lq    .....
- \lrbox    .....
- lrbox (environment)    .....
- \ltx@sh@ft    .....
- l387**, [l394](#), [l470](#), [l478](#), [l751](#), [l758](#)
- \luabytecode    .....
- \luachunk    .....
- \luafunction    .....
- \luatexbase    .....

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=ltthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx



- `\luatexluafunction` ..... a18, a23  
`\luatexversion` ..... a11, N5
- M**
- `\M` ..... [b359](#)  
`\m@ne` ..... [b39](#)  
`\m@th` ..... [b410](#), [b422](#),  
[j13](#), [t306](#), [t420](#), [t422](#), [t423](#), [t426](#),  
[t467](#), [t491](#), [t494](#), [t498](#), [t501](#),  
[t508](#), [t511](#), [t518](#), [t521](#), [t603](#),  
[z68](#), [z71](#), [z106](#), [z136](#), [z154](#), [z156](#),  
[z172](#), [z191](#), [z320](#), [z390](#), [z402](#),  
[z429](#), [z439](#), [B233](#), [B362](#), [C169](#),  
[F193](#), [F216](#), [G376](#), [G381](#), [G389](#)  
`\magstep` ..... [b350](#)  
`\magstephalf` ..... [b350](#)  
`\makeatletter` .... [d392](#), [k30](#), [k88](#),  
[o329](#), [y19](#), [F151](#), [K2](#), [L282](#), [L421](#)  
`\makeatother` ..... [d392](#), [L282](#), [O544](#)  
`\makebox` ..... [322](#), [z252](#), [z278](#), [B3](#)  
`\makeglossary` ..... [415](#), [k133](#), [H20](#)  
`\makeindex` ..... [415](#), [k132](#), [H3](#)  
`\makelabel` .....  
[A45](#), [A97](#), [A205](#), [A218](#), [A238](#), [A249](#)  
`\MakeLowercase` ..... [O471](#), [O483](#)  
`\makeph@nt` ..... [z101](#), [z103](#)  
`\MakeRobust` ..... [d245](#),  
[d423](#), [d424](#), [d425](#), [d426](#), [d427](#),  
[d428](#), [d429](#), [d430](#), [d431](#), [d432](#),  
[d433](#), [d434](#), [d435](#), [d436](#), [d437](#),  
[d438](#), [r673](#), [r932](#), [D424](#), [D425](#),  
[D426](#), [D427](#), [D428](#), [D429](#), [D430](#),  
[D431](#), [D432](#), [D433](#), [D434](#), [D435](#)  
`\makesm@sh` ..... [z131](#), [z133](#)  
`\maketitle` ..... [384](#)  
`\MakeUppercase` ..... [x46](#), [O461](#), [O461](#)  
`\mandatory@arg` ..... [p368](#), [p455](#),  
[p459](#), [p464](#), [p471](#), [p473](#), [p478](#),  
[p480](#), [p485](#), [p487](#), [p498](#), [p505](#), [p507](#)  
`\mapsto` ..... [t405](#)  
`\mapstochar` ..... [t404](#), [t405](#), [t455](#)  
`\marginpar` ..... [G308](#)  
`\marginparpush` ..... [K85](#), [K1834](#)  
`\marginparsep` .... [K84](#), [K1845](#), [K1847](#)  
`\marginparwidth` ... [G337](#), [K83](#), [K1847](#)  
`\mark` ..... [J27](#), [J35](#), [J53](#)  
`\markboth` ..... [J21](#), [J22](#), [J41](#), [J43](#)  
`\markright` ..... [J22](#), [J44](#)  
`\marks` ..... [N35](#), [O10](#), [O12](#)  
`\math` ..... [z299](#)  
`math` (environment) ..... [z299](#)  
`\math@bgroup` [o492](#), [p260](#), [p266](#), [r53](#),  
[r81](#), [r142](#), [r172](#), [v113](#), [v114](#), [v121](#)  
`\math@egroup` .....  
[o492](#), [p264](#), [p265](#), [v114](#), [v115](#), [v122](#)  
`\math@fonts` ..... [o462](#), [o467](#),  
[p186](#), [p290](#), [r60](#), [r89](#), [r149](#), [r180](#)  
`\math@fontsfalse` [j7](#), [l299](#), [l326](#), [l357](#),  
[l1194](#), [l1584](#), [o41](#), [o170](#), [o180](#), [o203](#)  
`\math@fontstrue` ..... [o168](#), [o504](#)  
`\math@version` .... [o7](#), [o269](#), [o466](#),  
[o470](#), [o472](#), [o473](#), [o475](#), [p184](#),  
[r56](#), [r59](#), [r64](#), [r65](#), [r69](#), [r84](#), [r88](#),  
[r93](#), [r94](#), [r98](#), [r111](#), [r112](#), [r113](#),  
[r126](#), [r127](#), [r128](#), [r145](#), [r148](#),  
[r152](#), [r154](#), [r156](#), [r160](#), [r175](#),  
[r179](#), [r183](#), [r185](#), [r187](#), [r191](#), [s67](#)  
`\mathaccent` .... [r590](#), [r638](#), [r672](#), [r682](#)  
`\mathalpha` [r760](#), [r1003](#), [t139](#), [t140](#),  
[t141](#), [t142](#), [t143](#), [t144](#), [t145](#),  
[t146](#), [t147](#), [t148](#), [t149](#), [t150](#),  
[t151](#), [t152](#), [t153](#), [t154](#), [t155](#),  
[t156](#), [t157](#), [t158](#), [t159](#), [t160](#),  
[t161](#), [t162](#), [t163](#), [t164](#), [t165](#),  
[t166](#), [t167](#), [t168](#), [t169](#), [t170](#),  
[t171](#), [t172](#), [t173](#), [t174](#), [t175](#),  
[t176](#), [t177](#), [t178](#), [t179](#), [t180](#),  
[t181](#), [t182](#), [t183](#), [t184](#), [t185](#),  
[t186](#), [t187](#), [t188](#), [t189](#), [t190](#),  
[t191](#), [t192](#), [t193](#), [t194](#), [t195](#),  
[t196](#), [t197](#), [t198](#), [t199](#), [t200](#),  
[t267](#), [t268](#), [t269](#), [t270](#), [t271](#),  
[t272](#), [t273](#), [t274](#), [t275](#), [t276](#),  
[t277](#), [t477](#), [t478](#), [t479](#), [t480](#),  
[t481](#), [t482](#), [t483](#), [t484](#), [t486](#), [t489](#)  
`\mathbf` ..... [s14](#), [t121](#)  
`\mathbin` ..... [r1008](#),  
[t202](#), [t203](#), [t205](#), [t327](#), [t328](#),  
[t329](#), [t330](#), [t333](#), [t335](#), [t337](#),  
[t338](#), [t339](#), [t340](#), [t341](#), [t342](#),  
[t343](#), [t344](#), [t345](#), [t346](#), [t347](#),  
[t348](#), [t349](#), [t350](#), [t351](#), [t352](#),  
[t353](#), [t354](#), [t355](#), [t356](#), [t357](#),  
[t358](#), [t359](#), [t360](#), [t361](#), [t362](#), [z37](#)  
`\mathcal` ..... [t120](#)  
`\mathchar` .....  
[b422](#), [r701](#), [r745](#), [t304](#), [t305](#), [t578](#)  
`\mathchar@type` .. [r672](#), [r682](#), [r733](#),  
[r736](#), [r745](#), [r761](#), [r930](#), [r941](#), [r1004](#)  
`\mathchardef` .....  
[b21](#), [b22](#), [b23](#), [b24](#), [b107](#), [b110](#),  
[b111](#), [e3](#), [e4](#), [e5](#), [e6](#), [l70](#), [r736](#), [N214](#)  
`\mathcharzero` ..... [N214](#)  
`\mathchoice` ..... [z61](#)  
`\mathclose` ..... [r1011](#), [t201](#),  
[t210](#), [t212](#), [t215](#), [t220](#), [t226](#),

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- t228, t230, t527, t554, t558,  
 t562, t566, t572, z43, z46, z49, z52  
 \mathcode ..... r733, t222, t223, t224  
 \mathdollar ..... l304, t575  
 \mathellipsis ..... l318, t580  
 \mathgroup . b79, l1791, o14, p257,  
 p263, p269, p270, p281, s82, t604  
 \mathhexbox ..... b422, s92  
 \mathindent z379, z391, z403, z431, z441  
 \mathinner .... t465, t469, t474, t580  
 \mathit ..... s29, t123, t126, t578  
 \mathnormal ..... t119  
 \mathop ..... r1007,  
 t310, t311, t312, t313, t314,  
 t315, t316, t318, t319, t320,  
 t321, t322, t323, t325, t326,  
 t498, t501, z3, z4, z5, z6, z7, z8,  
 z9, z10, z11, z12, z13, z14, z15,  
 z16, z17, z18, z19, z20, z21, z22,  
 z23, z24, z25, z26, z27, z28, z29,  
 z30, z31, z32, z33, z34, z149, z307  
 \mathopen .....  
 . r1010, t211, t214, t219, t225,  
 t227, t229, t525, t556, t560,  
 t564, t568, t570, z41, z44, z47, z50  
 \mathord ..... r760, r1006,  
 t206, t213, t216, t221, t233,  
 t234, t235, t237, t238, t239,  
 t240, t241, t242, t243, t244,  
 t245, t246, t247, t248, t249,  
 t250, t251, t252, t253, t254,  
 t255, t256, t257, t258, t259,  
 t260, t261, t262, t263, t264,  
 t265, t266, t278, t279, t280,  
 t281, t282, t283, t284, t285,  
 t286, t287, t288, t289, t290,  
 t291, t292, t293, t294, t295,  
 t297, t298, t299, t300, t301,  
 t302, t303, t485, t487, t488,  
 t510, t511, t514, t515, t516,  
 t517, t529, t531, t533, t536,  
 t538, t552, t574, t575, t576, t577  
 \mathpalette .....  
 t418, t422, t425, z60, z69, z99, z129  
 \mathparagraph l307, m134, m146, t575  
 \mathph@nt ..... z99, z105  
 \mathpunct .....  
 r1012, t204, t208, t462, t463, t464  
 \mathrel ..... r1009, t207, t209,  
 t217, t218, t231, t232, t307,  
 t363, t364, t365, t366, t367,  
 t368, t369, t370, t371, t372,  
 t373, t374, t375, t376, t380,  
 t382, t384, t385, t386, t387,  
 t388, t389, t390, t391, t392,  
 t393, t394, t396, t397, t398,  
 t399, t400, t402, t404, t406,  
 t407, t408, t409, t410, t411,  
 t412, t413, t414, t415, t416,  
 t418, t422, t425, t432, t434,  
 t437, t438, t440, t443, t445,  
 t540, t542, t544, t546, t548,  
 t550, z42, z45, z48, z51, z149, z307  
 \mathring ..... t489  
 \mathrm ..... s5, t118  
 \mathsection .. l308, m133, m145, t575  
 \mathsf ..... s8, t122, t125  
 \mathsm@sh ..... z129, z135  
 \mathsterling ..... l316, t575  
 \mathstrut ..... z84, z93, z158, z159  
 \mathsurround ..... b410  
 \mathsymbol ..... r738  
 \mathtt ..... s11, t124  
 \mathunderscore ..... t575  
 \mathversion ..... o269, s64, s66  
 \matrix ..... z156, z160, z167  
 \max ..... z22  
 \maxdeadcycles ..... K7  
 \maxdepth b331, i237, k57, k112, K92,  
 K169, K170, K506, K514, K546,  
 K715, K724, K764, K991, O85  
 \maxdimen ..... b296, b332, b333,  
 b389, b427, b443, b454, b470,  
 b485, o519, o529, o564, o579,  
 p338, p391, t419, D247, D292,  
 D331, K291, K1853, K1873,  
 K1878, K2165, K2205, K2206,  
 K2208, L798, L839, L848, O89  
 \maybe@ic ..... v46, v47, v66  
 \maybe@ic@ ..... v66  
 \maybe@icfalse ..... v80  
 \maybe@ictrue ..... v70  
 \mb@b ..... B50, B60  
 \mb@l ..... B50, B54, B59, D48, D52  
 \mb@r ..... B50, B54, B59, D48, D52  
 \mb@t ..... B51, B58  
 \mbox 322, b422, j13, l290, s88, t467,  
 B11, B20, B24, D20, G381, G389  
 \mddefault ..... s18, t84, t91  
 \mdseries ..... s16, s17, s91, v20  
 \meaning ..... a219,  
 a228, a323, d202, d261, d288,  
 d390, r412, r425, r526, r591,  
 r638, r702, r801, r859, r956, r1060  
 \medbreak ..... b404, d430, d451  
 \medmuskip ..... t606, z36, z38, z202  
 \medskip ..... b407, i310  
 \medskipamount ..... b406, i311, i313

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx



- `\MessageBreak` ..... d179,  
           d251, d278, g3, g6, g13, g33,  
           g46, g60, g73, g171, g173, g179,  
           g186, l159, l968, l1476, l1479,  
           l1503, l1505, l1506, l1507, l1509,  
           l1511, l1512, l1513, l1514, l1515,  
           l1564, l1566, l1574, l1581, l1796,  
           o410, o444, p20, p21, p67, p88,  
           p281, p432, p452, p484, p497,  
           p510, q31, q33, r367, r376, r514,  
           v127, y23, K578, K1960, K1997,  
           L145, L312, L323, L325, L327,  
           L338, L428, L429, L431, L432,  
           L433, L435, L437, L455, L456,  
           L457, L458, L504, L521, L522,  
           L594, L614, L653, L709, L743,  
           L852, L854, L936, L939, L952,  
           L954, O230, O231, O232, O234  
`\mho` ..... s104  
`\mid` ..... t367  
`\min` ..... z23  
`\minipage` ..... B281  
`minipage (environment)` ..... 323  
`\mit` ..... s153  
`\mkern` ..... t304,  
           t307, t309, t423, t432, t474,  
           t475, t476, t506, t507, t508,  
           t509, t510, t511, t512, t513,  
           z36, z37, z40, z73, z74, F194, F217  
`\models` ..... t445  
`\module_error` ..... 533, N331  
`\module_info` ..... 533, N331  
`\module_warning` ..... 533, N331  
`\modules` ..... N284  
`\month` ..... a185, c11, c17, L631, L721  
`\moveright` ..... K625, K684  
`\mp` ..... t354  
`\mscount` ..... C355  
`\mskip` ..... i336,  
           z36, z38, z201, z202, z203, z204  
`\mu` ..... t249  
`\mubyte` ..... O248  
`\multicolumn` ..... C209  
`\multiput` ..... D25, D29, D429, D446  
`\multispan` ..... C209, C355  
`\muskip` . b29, b55, b93, t506, t507, N32  
`\muskipdef` ..... b55, b93, N215  
`\muskipzero` ..... N215  
  

N

`\n` ..... N318, N320, N327,  
           N329, N456, N557, N580, N611,  
           N628, N650, N658, N659, N679,  
           N692, N699, N700, N707, N719  
`\n@space` ..... t586, t588, t590,  
           t592, t597, t598, t599, t600, t603  
`\nabla` ..... t289  
`\narrower` ..... b415  
`\natural` ..... t298  
`\ncallback` ..... N616  
`\ndefault` ..... N620  
`\ne` ..... t378, t379  
`\nearrow` ..... t370  
`\NeedsTeXFormat` .... p12, L317, L998  
`\neg` ..... t295, t296  
`\negthinspace` ..... i361, i370  
`\neq` ..... t377, t378  
`\new@command` .....  
           . d52, d53, d106, d140, d159, d213  
`\new@environment` ... d121, d122, d134  
`\new@fontshape` ..... q2, q4, q22, q24  
`\new@mathalphabet` ... r409, r430, r441  
`\new@mathgroup` .....  
           b78, b80, b98, b100, o14, r289, N25  
`\new@mathversion` .... r20, r246, r248  
`\new@symbolfont` ..... r290, r322  
`\new_attribute` ..... 531, N397  
`\new_bytecode` ..... 531, N431  
`\new_chunkname` ..... 531, N444  
`\new_luafunction` ..... 531, N460  
`\new_whatsit` ..... 531, N419  
`\newattribute` ..... 530, N74, N225  
`\newbox` ..... b47, b301, b412,  
           e13, y283, z66, A27, B70, C16,  
           C17, C18, C319, D6, D356,  
           D361, K86, K120, K121, K122  
`\newcatcodetable` ..... 530,  
           N84, N93, N94, N120, N121, N229  
`\newcommand` ..... 37, d52, l4, t43,  
           t44, t45, t46, t48, t49, t51, t52,  
           t84, t85, t86, t87, t88, t89, t90,  
           t91, t92, D368, K2291, K2294,  
           K2297, K2298, K2301, K2302  
`\newcount` b47, b349, e7, e8, i98, k9,  
           m36, p25, r27, r254, z55, z311,  
           z312, A23, A24, A25, A26, A56,  
           A226, A241, B322, C11, C12,  
           C13, C14, C15, C311, C312,  
           C313, D350, D351, D352, D353,  
           D362, F36, F140, F141, G3,  
           G267, G268, G269, G270, K103,  
           K105, K107, K109, K111, K119,  
           K1986, K2289, K2292, K2295,  
           K2299, L795, O3, O4, O5, O77  
`\newcounter` ..... 155, m10  
`\newdimen` ..... b47, b296,  
           b298, b299, b348, e10, e11, e12,  
           i97, p352, p353, z53, z380, A9,

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

- A10, A11, A12, A13, A14, A15,  
 A16, A17, A18, A19, A20, A21,  
 A22, B126, B127, C3, C5, C6,  
 C7, C8, C154, C314, C315,  
 C316, C317, D3, D4, D5, D7,  
 D217, D218, D219, D220, D221,  
 D222, D354, D355, D357, D358,  
 D359, D360, G398, K71, K72,  
 K73, K75, K76, K77, K78, K79,  
 K80, K81, K82, K83, K84, K85,  
 K91, K93, K94, K106, K108,  
 K110, K112, K113, K114, K115,  
 K116, K117, K118, K1987, K1988  
 \newenvironment . 37, [d121](#), L629, L719  
 \newfam . . . . . [b47](#), o16, N36  
 \newfont . . . . . [s68](#)  
 \newgroup . . . . . [r47](#)  
 \newhelp . . . . . [b295](#)  
 \newif . . . . . c68, [d143](#), d417, e9,  
 k7, k8, l1523, o168, r15, v65, x3,  
 z75, z76, z190, z313, A28, A29,  
 A30, A31, A32, A33, A138,  
 B336, C19, C227, D56, D213,  
 D214, D215, D216, D245, D246,  
 F38, F124, K95, K96, K97,  
 K98, K99, K100, K101, K102, L2  
 \newinsert . . . . . b193,  
[b231](#), B323, G366, K27, K1852  
 \newlabel . . . . . [x22](#), x34  
 \newlanguage . . . . . [b47](#), O215  
 \newlength . . . . . [162](#), [n3](#)  
 \newline . . . . . [i79](#)  
 \newlinechar . . . . . [a72](#), [d5](#)  
 \newluabytecode . . . . . 530, [N189](#), N239  
 \newluachunkname . . . . . 531, [N197](#), N241  
 \newluafunction . . . . .  
 . . . . . 530, N4, [N173](#), N223, N235  
 \newmarks . . . . . [O6](#)  
 \newmathalphabet . . . . . [q13](#), [q109](#)  
 \newmathalphabet@ . . . . . [q14](#)  
 \newmathalphabet@@ . . . . . [q109](#)  
 \newmathalphabet@@@ . . . . . [q15](#), [q109](#)  
 \newmuskip . . . . . [b47](#)  
 \newpage . . . . . K133, K139, [K150](#)  
 \newread . . . . . [b47](#), k3  
 \newsavebox . . . . . [322](#), [B70](#)  
 \newskip . . . . . [b47](#), b297,  
 b300, b346, b347, e14, e15, e17,  
 i313, i314, i315, i354, n3, y201,  
 z314, A2, A3, A4, A5, A6,  
 A7, A8, K2303, K2304, K2305,  
 K2309, K2310, K2313, K2314,  
 K2315, K2319, K2320, K2321  
 \newtheorem . . . . . [E1](#)  
 \newtie . . . . . l842, l1667, l1668  
 \newtoks [b47](#), b295, e16, o279, o280, p201  
 \newwhatsit . . . . . 530, [N181](#), N237  
 \newwrite [b47](#), k4, k5, k6, F154, H4, H21  
 \newXeTeXintercharclass . . . . . [O21](#)  
 \nfss@catcodes . . . . . o19, o84, o320,  
 o321, o328, t21, t32, t37, t105, K3  
 \nfss@text l312, l314, [s88](#), v5, [v105](#), x13  
 \NG . . . . . l525, l1093, O481  
 \ng . . . . . l546, l1094, O481  
 \ni . . . . . t394, t395  
 \no@alphabet@error . . . . . [o4](#), r268, r270,  
 r446, r447, r461, r470, r556, r557  
 \noaccents@ . . . . . [o507](#), t99  
 \noalign . . . . . t308,  
 t492, t495, t498, t499, t503,  
 t504, z158, z159, z175, z178,  
 z192, z353, C208, C335, C354, D55  
 \nobreak . . . . . b392, b395, [b397](#),  
 d431, d452, i59, i71, i89, i115,  
 i121, i134, i147, i173, i297, i305,  
 i324, i331, i352, k131, k143,  
 l429, l431, y158, y165, B401,  
 F90, F191, F192, F196, F214,  
 F215, F219, G434, J29, J37,  
 K336, K1149, K1315, O141,  
 O143, O147, O148, O149, O153  
 \nobreakdashes . . . . . [i316](#)  
 \nobreakspace . . . . . [i330](#)  
 \nocite . . . . . [417](#), [I39](#)  
 \nocorr . . . . . [v26](#), v41, v45, v48  
 \nocorrlist . . . . . v72, [v104](#)  
 \nofiles . . . . . 88, [k127](#)  
 \noindent . . . . . o542, o568, F139  
 \nointerlineskip . . . . .  
 . . . . . [b387](#), t308, t492, t495,  
 t499, t503, z251, z277, D272,  
 D275, D316, D318, K1842, K1850  
 \nolimits . . . . . t317, t324,  
 z3, z4, z5, z9, z10, z11, z12, z13,  
 z14, z15, z16, z17, z18, z19, z20,  
 z21, z26, z27, z28, z29, z31, z34  
 \nolinebreak . . . . . 71, [i9](#), i27  
 \non@alpherr . . . . . o486, o488,  
 r72, r101, [r117](#), r163, r194, r1082  
 \nonfrenchspacing . . . . .  
[b353](#), b541, d432, d453, k46, k104  
 \nonscript . . . . . z36, z38  
 \nonumber . . . . . [z340](#), z363, z364  
 \nopagebreak . . . . . 71, [i7](#), i25  
 \noprotusion . . . . . [F201](#), F224  
 \normalbaselines . . . . . [b357](#), z154, z156  
 \normalbaselineskip . . . . .  
 . . . . . [b346](#), b358, p142, B254, B273

File Key: a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

- `\normalcolor` ..... z306,  
           z376, [B63](#), B314, F197, F220,  
           G97, G166, K216, K492, K629,  
           K639, K688, K698, K2226, K2259  
`\normalfont` .. o520, o580, [s93](#), v18,  
           y262, z306, z376, F197, F220, G377  
`\normallineskip` [b346](#), b357, B252, B272  
`\normallineskiplimit` ..... [b346](#),  
           b358, z193, B237, B253, B259  
`\normalmarginpar` ..... [G363](#)  
`\normalsfcodes` .... k42, k44, k46,  
           k100, k102, k104, [k126](#), K618, K677  
`\normalsize` ..... k40, k98, [v125](#),  
           G23, G176, G348, K617, K676, L5  
`\not` ..... t307, t377, t379, t398  
`\not@base` ..... s100,  
           s104, s105, s106, s107, s108,  
           s109, s110, s111, s112, s113, s114  
`\not@math@alphabet` ..... s5, s8,  
           s11, s14, s17, s20, s23, s26, s29, [s47](#)  
`\notin` ..... t422  
`\nu` ..... t250  
`\null` ..... [b371](#), l324, l360,  
           l480, l483, l825, l828, l1192,  
           x17, y227, y248, y333, y343,  
           z112, z121, z156, z185, F191, F214  
`\nulldelimiterspace` ..... b335, t603  
`\nullfont` ..... y88  
`\number` .....  
           a86, d2, d89, m108, o470, o473,  
           p393, r64, r93, r113, r128, r153,  
           r184, s85, L535, L631, L721, N105  
`\numberline` ..... F72, F82, [F227](#), G17  
`\numexpr` .. b189, b205, b215, b235,  
           d333, 1991, K36, N82, N105, N157  
`\nunknown` ..... N633  
`\narrow` ..... t372
- O**
- `\O` .. l242, l397, l527, l761, l1078, O480  
`\o` .. l251, l402, l548, l772, l1084, O480  
`\o@lign` ..... [b424](#),  
           l387, l394, l470, l478, l751, l758  
`\oalign` ..... [b424](#)  
`\obeycr` ..... [i378](#)  
`\obeylines` ..... [b374](#), d433,  
           d454, y233, y254, y324, y325, K583  
`\obeyspaces` ... [b374](#), d434, d455, K583  
`\oddsidemargin` K72, K74, K611, K670  
`\odot` ..... t349  
`\OE` .. l241, l396, l526, l760, l1095, O480  
`\oe` .. l250, l401, l547, l773, l1096, O480  
`\of` ..... z67, z310  
`\offinterlineskip` ..... [b387](#)
- `\oint` ..... t324  
`\ointop` ..... t323, t324  
`\oldstylenums` ..... l1788, [s78](#)  
`\Omega` ..... t277  
`\omega` ..... t260  
`\ominus` ..... t352  
`\omit` z178, z179, C345, C348, C355, C359  
`\on@line` ..... g8,  
           g15, [g165](#), y97, y114, B105, L454  
`\onecolumn` ..... [K141](#)  
`\OnlyDescription` ..... p5, u3  
`\oalign` ..... [b424](#),  
           l324, l354, l391, l474, l480, l482,  
           l493, l509, l722, l755, l825,  
           l828, l874, l1192, s90, t423, t426  
`\openup` ..... [z186](#), z191  
`\operator@font` .....  
           t604, z3, z4, z5, z6, z7,  
           z8, z9, z10, z11, z12, z13, z14,  
           z15, z16, z17, z18, z19, z20, z21,  
           z22, z23, z24, z25, z26, z27, z28,  
           z29, z30, z31, z32, z33, z34, z37, z40  
`\oplus` ..... t353  
`\optional@arg` .....  
           p369, p448, p450, p504, p507  
`\OptionNotUsed` .... [L194](#), L201, L469  
`\oslash` ..... t350  
`\OT` ..... l369  
`\otimes` ..... t351  
`\outer` ..... N19, N36  
`\outer@nobreak` [G181](#), [G251](#), [G255](#), G342  
`\outerparskip` ..... [A1](#)  
`\output` ..... [K256](#)  
`\outputpenalty` ..... K258,  
           K272, K295, K298, K299, K334,  
           K1159, K1160, K1325, K1328  
`\oval` ..... D236, [D239](#), D430, D447  
`\over` ..... t430, z149, z308  
`\overbrace` ..... t497  
`\overfullrule` ..... b330, [J69](#)  
`\overleftarrow` ..... t494  
`\overrightarrow` ..... t491  
`\owns` ..... t395
- P**
- `\P` ..... l307  
`\p@` ..... [b298](#)  
`\p@equation` ..... z318, z438  
`\p@reset@font` ..... [s93](#)  
`\p@selectfont` ..... p117  
`\PackageError` ..... c72,  
           c101, c110, [g84](#), l1474, l1529, l1573  
`\PackageInfo` ..... [g84](#),  
           l1503, l1519, l1520, l1580, l1865

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=ltthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

- \PackageWarning . . . . [g84](#), [l1530](#), [l1794](#)
- \PackageWarningNoLine [g84](#), [l966](#), [K1959](#)
- \pagebreak . . . . . [71](#), [i6](#), [i7](#), [i22](#), [i24](#)
- \pagegoal . . . . . [K1880](#), [K1887](#)
- \pagenumbering . . . . . [274](#), [w5](#)
- \pageref . . . . . [x10](#)
- \pageshrink . . . . . [K538](#), [K542](#), [K558](#)
- \pagestyle . . . . . [J2](#)
- \pagetotal . . . . . [K128](#)
- \paperheight . . . . . [K93](#)
- \paperwidth . . . . . [K93](#)
- \par . . . . . [a120](#),  
[b11](#), [b367](#), [b375](#), [b376](#), [b391](#),  
[b400](#), [b401](#), [b402](#), [b404](#), [b406](#),  
[b408](#), [d6](#), [h3](#), [h4](#), [h5](#), [o545](#), [y86](#),  
[y158](#), [y165](#), [y225](#), [y246](#), [A63](#),  
[A110](#), [A127](#), [A129](#), [A135](#), [A161](#),  
[A164](#), [B243](#), [B264](#), [B310](#), [C183](#),  
[C361](#), [F41](#), [F90](#), [F199](#), [F221](#),  
[G15](#), [G24](#), [G249](#), [J62](#), [J63](#),  
[K166](#), [K193](#), [K257](#), [K1886](#), [N156](#)
- \par@deathcycles [A56](#), [A77](#), [A79](#), [A80](#)
- \paragraphmark . . . . . [F143](#)
- \parallel . . . . . [t366](#)
- \parbox . . . . . [322](#), [B189](#)
- \parboxrestore . . . . . [B277](#)
- \parfillskip . . . . . [b345](#), [o519](#),  
[o534](#), [o579](#), [y181](#), [y189](#), [y221](#),  
[y243](#), [A76](#), [B251](#), [B272](#), [F186](#), [F209](#)
- \parindent . . . . . [b337](#), [b416](#),  
[b417](#), [y181](#), [y185](#), [y189](#), [y221](#),  
[y243](#), [A50](#), [B246](#), [B267](#), [F187](#), [F210](#)
- \parsep . . . . . [A1](#), [A49](#), [A90](#)
- \parseunicodedataI . . . . . [N123](#), [N162](#)
- \parseunicodedataII . . . . . [N124](#), [N126](#)
- \parseunicodedataIII . . . . . [N128](#), [N134](#)
- \parseunicodedataIV . . . . . [N130](#), [N142](#)
- \parseunicodedataV . . . . . [N146](#), [N149](#)
- \parshape . . . . . [A54](#)
- \parskip . . . . .  
[b338](#), [y169](#), [y219](#), [y221](#), [y241](#),  
[y243](#), [z447](#), [A49](#), [A73](#), [A88](#),  
[A90](#), [A117](#), [A153](#), [A172](#), [A223](#),  
[B246](#), [B267](#), [C67](#), [K1159](#), [K1327](#)
- \partial . . . . . [t285](#)
- \partopsep . . . . . [z445](#), [A1](#), [A61](#)
- \PassOptionsToClass . . . . . [498](#), [L171](#)
- \PassOptionsToPackage . . . . . [498](#), [L171](#)
- \patch@level . . . . . [c1](#), [c36](#), [c41](#), [c43](#),  
[c45](#), [c48](#), [c56](#), [O491](#), [O503](#), [O505](#)
- \patterns . . . . . [l203](#)
- \penalty . . . . . [b396](#), [b397](#), [b398](#),  
[b399](#), [b400](#), [b401](#), [b405](#), [b407](#),  
[b409](#), [i34](#), [i37](#), [i46](#), [i231](#), [i241](#),  
[i266](#), [i270](#), [v101](#), [y227](#), [y230](#),  
[y248](#), [y251](#), [z37](#), [z194](#), [z353](#),  
[A190](#), [C56](#), [G195](#), [G199](#), [G201](#),  
[G217](#), [G221](#), [G223](#), [K136](#), [K176](#),  
[K195](#), [K198](#), [K1157](#), [K1323](#), [I17](#)
- \perp . . . . . [t408](#)
- \ph@nt . . . . . [z81](#), [z82](#), [z83](#), [z97](#)
- \phantom . . . . . [z75](#)
- \Phi . . . . . [t275](#)
- \phi . . . . . [t257](#)
- \Pi . . . . . [t272](#)
- \pi . . . . . [t252](#)
- \pickup@font . . . . . [l179](#), [o159](#), [o286](#),  
[o421](#), [o455](#), [p122](#), [p285](#), [p287](#), [p289](#)
- \pictur@ . . . . . [D8](#)
- \picture . . . . . [D8](#)
- \pkgcls@arg . . . . . [L812](#), [L935](#)
- \pkgcls@candidate . . . . . [L799](#),  
[L814](#), [L890](#), [L894](#), [L898](#), [L966](#), [L969](#)
- \pkgcls@debug . . . . . [L789](#), [L805](#),  
[L806](#), [L807](#), [L808](#), [L809](#), [L866](#),  
[L867](#), [L868](#), [L869](#), [L878](#), [L883](#),  
[L901](#), [L910](#), [L925](#), [L959](#), [L960](#), [L961](#)
- \pkgcls@innerdate . . . . .  
. . . [L794](#), [L839](#), [L842](#), [L848](#), [L987](#)
- \pkgcls@mindate [L819](#), [L828](#), [L844](#), [L849](#)
- \pkgcls@name . . . . . [L811](#), [L854](#)
- \pkgcls@parse@date@arg . . . [L813](#), [L824](#)
- \pkgcls@parse@date@arg@ . . [L830](#), [L833](#)
- \pkgcls@parse@date@arg@version . . . . .  
. . . . . [L840](#), [L861](#)
- \pkgcls@releasedate . . . . .  
. . . . . [L799](#), [L895](#), [L899](#), [L970](#)
- \pkgcls@rollbackdate@error . . . . .  
. . . . . [L891](#), [L949](#), [L967](#)
- \pkgcls@show@selection . . . . .  
. . . . . [L918](#), [L923](#), [L973](#), [L978](#)
- \pkgcls@targetdate . . . [L794](#), [L826](#),  
[L834](#), [L837](#), [L838](#), [L842](#), [L850](#),  
[L851](#), [L864](#), [L872](#), [L887](#), [L889](#),  
[L919](#), [L930](#), [L932](#), [L957](#), [L963](#), [L965](#)
- \pkgcls@targetlabel . . . . .  
. . . . . [L794](#), [L827](#), [L847](#),  
[L862](#), [L874](#), [L906](#), [L939](#), [L977](#), [L980](#)
- \pkgcls@use@this@release . . [L875](#),  
[L892](#), [L894](#), [L907](#), [L917](#), [L969](#)
- \pm . . . . . [t355](#)
- \pmatrix . . . . . [z160](#), [z168](#)
- \pmod . . . . . [z39](#)
- \poptabs . . . . . [g206](#), [C130](#), [C149](#)
- \poptracing . . . . . [p130](#), [p294](#)
- \postdisplaypenalty . . . . .  
. . . . . [i12](#), [z388](#), [z400](#), [z426](#)
- \pounds . . . . . [l315](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=ltpictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- `\Pr` ..... [z32](#)  
`\pr@@s` ..... [z213](#), [z221](#)  
`\pr@@t` ..... [z216](#), [z222](#)  
`\pr@m@s` ..... [z210](#), [z211](#)  
`\prec` ..... [t385](#)  
`\preceq` ..... [t388](#)  
`\predisplaypenalty` .....  
                   ..... [b316](#), [z387](#), [z399](#), [z425](#)  
`\preload@sizes` ..... [q11](#), [q94](#)  
`\pretolerance` .. [b303](#), [o521](#), [o536](#), [o581](#)  
`\prevdepth` .....  
                   ..... [b387](#), [b391](#), [b392](#), [i237](#), [i238](#),  
                           ..... [i295](#), [i300](#), [z192](#), [G196](#), [G198](#),  
                           ..... [G218](#), [G220](#), [K167](#), [K169](#), [K172](#)  
`\prim@s` ..... [z207](#), [z209](#), [z221](#)  
`\prime` ..... [t223](#), [t287](#), [z210](#)  
`\prime@s` ..... [z208](#)  
`\process@table` ..... [k38](#), [k96](#), [r200](#)  
`\ProcessOptions` .....  
                   ..... [l1494](#), [l1532](#), [p71](#), [L202](#), [L245](#), [L523](#)  
`\ProcessOptions*` ..... [L202](#)  
`\prod` ..... [t318](#)  
`\propto` ..... [t363](#)  
`\protect` [d77](#), [d194](#), [d208](#), [d217](#), [d222](#),  
                   ..... [d225](#), [d226](#), [d228](#), [d229](#), [d234](#),  
                   ..... [d235](#), [d240](#), [d243](#), [d244](#), [d266](#),  
                   ..... [d293](#), [g197](#), [g199](#), [g200](#), [g206](#),  
                   ..... [g212](#), [g219](#), [g227](#), [g230](#), [g236](#),  
                   ..... [k139](#), [l26](#), [l32](#), [l51](#), [l55](#), [l207](#),  
                   ..... [l215](#), [r475](#), [r1087](#), [s71](#), [v126](#),  
                   ..... [x12](#), [y103](#), [y106](#), [y121](#), [y131](#),  
                   ..... [C240](#), [F12](#), [F72](#), [F82](#), [F164](#),  
                   ..... [F171](#), [G17](#), [K596](#), [K655](#), [O254](#), [I5](#)  
`\protected` . [i56](#), [i364](#), [m160](#), [y47](#), [y157](#)  
`\protected@edef` ..... [d227](#),  
                   ..... [m158](#), [x41](#), [x45](#), [x53](#), [B330](#), [F60](#),  
                   ..... [G414](#), [O468](#), [O477](#), [O482](#), [O483](#)  
`\protected@file@percent` .....  
                   ..... [y43](#), [y50](#), [y65](#), [y73](#), [y74](#), [F165](#)  
`\protected@write` .....  
                   ..... [k130](#), [k135](#), [x33](#), [F175](#), [H14](#), [H31](#)  
`\protected@xdef` .....  
                   ..... [d227](#), [F11](#), [G400](#), [G424](#), [G440](#)  
`\provide@command` ..... [d153](#), [d154](#)  
`\providecommand` . [d153](#), [l6](#), [l961](#), [K1970](#)  
`\provides_module` ..... [533](#), [N285](#)  
`\ProvidesClass` ..... [498](#), [L158](#)  
`\ProvidesFile` .....  
                   ..... [a89](#), [t626](#), [t628](#), [t629](#), [t630](#), [L160](#)  
`\ProvidesPackage` .....  
                   ..... [498](#), [p13](#), [L141](#), [L158](#), [L999](#)  
`\ProvideTextCommand` ..... [l3](#), [l60](#)  
`\ProvideTextCommandDefault` ..... [l57](#)  
`\ps@empty` ..... [J10](#), [O91](#)
- `\ps@plain` ..... [J13](#)  
`\Psi` ..... [t276](#)  
`\psi` ..... [t259](#)  
`\pushtabs` [g206](#), [C126](#), [C127](#), [C146](#), [C148](#)  
`\pushtracing` ..... [p115](#), [p275](#)  
`\put` ..... [D21](#),  
                   ..... [D177](#), [D178](#), [D179](#), [D180](#), [D185](#),  
                   ..... [D187](#), [D199](#), [D200](#), [D201](#), [D202](#),  
                   ..... [D207](#), [D210](#), [D405](#), [D431](#), [D448](#)
- ### Q
- `\q@curr@file` ..... [L583](#), [L584](#), [L590](#)  
`\qbezier` ..... [357](#), [D368](#), [D432](#), [D449](#)  
`\qbeziermax` ..... [D367](#), [D389](#)  
`\quad` ..... [i375](#)  
`\quad` ..... [i375](#), [z155](#), [z157](#), [z177](#), [F111](#)  
`\quote@name` ..... [k236](#), [k274](#)  
`\quote@name` [k236](#), [k260](#), [k262](#), [k273](#), [L583](#)  
`\quotedblbase` ..... [l549](#), [l774](#), [l1115](#)  
`\quotesinglbase` ..... [l550](#), [l1112](#)
- ### R
- `\r` [b365](#), [b366](#), [l234](#), [l385](#), [l425](#), [l464](#),  
                   ..... [l601](#), [l628](#), [l638](#), [l664](#), [l747](#), [l786](#),  
                   ..... [l1184](#), [l1202](#), [l1228](#), [l1350](#), [l1351](#)  
`\r@@t` ..... [z66](#)  
`\radical` ..... [r953](#), [r956](#), [r986](#)  
`\raggedbottom` ..... [J53](#)  
`\raggedleft` ..... [y186](#), [y197](#), [y204](#)  
`\raggedright` ..... [y182](#), [y196](#), [y202](#)  
`\raise` ..... [l324](#), [l356](#), [l424](#),  
                   ..... [l427](#), [l723](#), [l788](#), [l875](#), [l1192](#),  
                   ..... [s91](#), [t426](#), [t474](#), [t476](#), [z73](#), [B386](#),  
                   ..... [B395](#), [D22](#), [D32](#), [D75](#), [D163](#),  
                   ..... [D238](#), [D266](#), [D310](#), [D338](#), [D416](#)  
`\raisebox` ..... [323](#), [l1161](#), [B363](#)  
`\rangle` ..... [t553](#)  
`\rbrace` ..... [l306](#), [t557](#)  
`\rbrack` ..... [b363](#)  
`\rceil` ..... [t561](#)  
`\Re` ..... [t283](#)  
`\Ref` ..... [276](#), [x39](#), [x45](#), [x50](#), [x57](#)  
`\ref` ..... [x10](#), [x45](#)  
`\refstepcounter` .....  
                   ..... [155](#), [x39](#), [x40](#), [x50](#), [x52](#),  
                   ..... [z304](#), [z427](#), [A202](#), [E27](#), [F59](#), [G9](#)  
`\registernumber` ..... [532](#), [N376](#)  
`\Relbar` ..... [t437](#), [t445](#), [t447](#), [t453](#)  
`\relbar` ..... [t434](#), [t449](#), [t451](#)  
`\relpenalty` ..... [b311](#)  
`\rem@pt` ..... [o262](#)  
`\remove@angles` ..... [p301](#), [p324](#)  
`\remove@nil` ..... [r36](#)  
`\remove@star` ..... [p301](#), [p307](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdc1.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx

`\remove@tlig` ..... 1980,  
                   1982, 1984, 1991, 11027, 11029, 11031  
`\remove@to@nnil` o261, p301, p327, p440  
`\remove_from_callback` .... 533, N690  
`\removelastskip` b403, b405, b407, b409  
`\renew@command` . d99, d100, d160, d168  
`\renew@environment` ..... d127, d128  
`\renewcommand` ..... 37, d99, t58,  
                   t60, t62, t63, t65, t67, t69, t70,  
                   t76, t78, t80, t81, z375, z395, z416  
`\renewenvironment` 37, d127, z424, z436  
`\repeat` ..... a81, a83, b379,  
                   o562, C358, L576, L640, L692,  
                   L730, N154, N164, O265, O276,  
                   O286, O297, O327, O353, O363  
`\requestedLaTeXdate` .....  
                   ..... L793, L826, L846, L932  
`\requestedpatchdate` ..... L856, L933  
`\RequirePackage` ..... 498, K1967,  
                   L278, L285, L306, L519, N22  
`\RequirePackageWithOptions` 498, L304  
`\reserved@a` ..... a121,  
                   a125, a126, a195, a196, a199,  
                   a217, a221, a243, a250, a253,  
                   a255, a256, a263, a266, a268,  
                   a269, a276, a279, a281, a331,  
                   a332, a333, b193, c13, c19, c34,  
                   d92, d95, d108, d109, d110,  
                   d112, d159, d160, d161, d167,  
                   d168, d169, d170, d173, d192,  
                   d200, d204, d259, d263, d286,  
                   d290, d366, d375, f33, f37, g185,  
                   i319, i322, k140, k141, k187,  
                   k188, k246, k248, k253, k255,  
                   k257, k263, k267, k284, k286,  
                   k291, k293, k296, k302, k306,  
                   k340, k343, k351, k354, k369,  
                   k370, k374, k380, k399, k403,  
                   k407, l79, l80, l84, l87, l95,  
                   l105, l108, l117, l136, l141, l974,  
                   l978, l1005, l1014, o29, o32,  
                   o35, o69, o72, o74, o111, o115,  
                   o322, o325, o393, o394, o409,  
                   o412, o417, o428, o429, o442,  
                   o446, o451, o478, o481, o482,  
                   o490, p150, p152, p154, p164,  
                   p166, p169, p298, p299, p312,  
                   p313, q53, q57, r356, r365, r367,  
                   r411, r414, r424, r427, r525,  
                   r527, r589, r593, r637, r639,  
                   r700, r703, r799, r802, r858,  
                   r860, r955, r957, r1059, r1061,  
                   r1077, r1079, r1080, r1085, v30,  
                   v31, v36, v37, v48, v51, v71,  
                   v78, y41, y42, y95, y96, y100,  
                   y112, y113, y117, y149, y150,  
                   z355, z356, z357, z358, z360,  
                   B52, B53, B56, B100, B106,  
                   C217, C221, C226, C245, C336,  
                   C337, D79, D81, D85, D250,  
                   D294, D295, G29, G30, G32,  
                   G33, G63, G67, G72, G74, G76,  
                   G78, G83, G84, G132, G136,  
                   G142, G145, G148, G151, K37,  
                   K46, K48, K50, K877, K897,  
                   K1963, K1965, K1966, K2055,  
                   K2057, K2063, K2066, L107,  
                   L115, L119, L125, L133, L137,  
                   L258, L262, L268, L272, L318,  
                   L319, L322, L363, L367, L379,  
                   L380, L382, L391, L395, L407,  
                   L408, L409, L411, L422, L463,  
                   L599, L600, L602, L606, L816,  
                   L821, L873, L874, L905, L906,  
                   L976, L977, L1001, L1003,  
                   O159, O176, O177, O178, O185,  
                   O186, O187, O387, O390, O421,  
                   O427, O428, O439, O440, O441,  
                   O448, O449, O450, O463, O464,  
                   O468, O469, O472, O473, O477,  
                   O478, O504, O507, O508, O526  
`\reserved@b` .. a122, a123, d84, d86,  
                   d93, d110, d111, d201, d202,  
                   d204, d260, d261, d263, d287,  
                   d288, d290, d367, d377, f33,  
                   f34, f37, i320, i321, i328, k186,  
                   k188, k258, k260, k262, k297,  
                   k299, k301, k402, k408, l88,  
                   l95, l110, l117, l977, l978, l1014,  
                   l1023, l1025, o59, o61, o114,  
                   o115, o479, o490, q47, q54, q71,  
                   q73, r282, r284, r337, r339,  
                   r364, r365, r366, r401, r403,  
                   r482, r484, r529, r530, r531,  
                   r538, r698, r702, r704, v35, v36,  
                   v49, v51, v78, v79, C222, C224,  
                   C226, G43, G44, G112, G113,  
                   K786, K789, K803, K806, K823,  
                   K826, L108, L109, L110, L112,  
                   L126, L127, L130, L371, L377,  
                   L380, L399, L405, L409, L601,  
                   L602, L605, L606, L642, L643,  
                   L645, L671, L732, L733, L735,  
                   L762, O162, O164, O168, O393,  
                   O395, O399, O464, O473, O526  
`\reserved@c` ..... a123, a128, d372,  
                   d375, d377, d380, k391, k392,  
                   o60, o61, o480, o483, q48, q55,

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
 e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
 j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
 o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
 t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
 y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
 D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
 I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
 N=ltluatex.dtx, O=ltfinal.dtx



- q61, q68, r33, r37, r283, r284,  
r338, r339, r402, r403, r483,  
r484, r506, r515, r530, r544,  
r789, r808, r817, r848, r865,  
r874, r904, r915, r972, r985,  
r987, v50, v52, v59, L588, L589,  
L590, L610, L611, L619, L625,  
L647, L654, L703, L704, L705,  
L715, L737, L744, L772, O166,  
O171, O179, O387, O397, O418,  
O419, O420, O422, O423, O424,  
O425, O426, O434, O442, O528
- `\reserved@d` .....  
a126, a129, d365, d374, k390,  
k392, q61, q68, q70, q74, r797,  
r808, r817, r856, r865, r874,  
r912, r915, r980, r985, r989, O529
- `\reserved@e` .....  
i57, i59, i69, i71, i83, i89, q39,  
q45, q70, q73, q74, r34, r39, O530
- `\reserved@f` ..... i58, i59,  
i70, i71, i89, l1470, l1471, l1472,  
l1473, l1475, l1482, o154, o156,  
o162, o163, p336, p347, p351,  
p355, p361, p364, p403, p440,  
p443, q27, q38, q45, q71, q73, O531
- `\reset@font` . s93, x13, B327, G175,  
G347, G409, J14, K616, K675, I20
- `\restgbl@settings` ..... p222, p232
- `\restore@mathversion` .....  
r107, r110, r125, r133
- `\restore@protect` ..... d227
- `\restorecr` ..... i378
- `\reversemarginpar` ..... G363
- `\rfloor` ..... t565
- `\rgroup` ..... t569
- `\rhd` ..... s113
- `\rho` ..... t253
- `\rhook` ..... t440, t441
- `\right` . t586, t588, t590, t592, t597,  
t598, t599, t600, z155, z160, z184
- `\Rightarrow` ..... t376, t447, t459
- `\rightarrow` ..... t402,  
t403, t405, t439, t449, t457, t510
- `\rightarrowfill` ..... t492, t508
- `\rightharpoonowdown` ..... t416
- `\rightharpoonup` ..... t415, t427
- `\righthyphenmin` ..... M11
- `\rightleftharpoons` ..... t425
- `\rightline` ..... B402
- `\rightmargin` ..... A9, A40, A51
- `\rightmark` ..... J48
- `\rightskip` ..... b417,  
o533, y180, y183, y188, y220,  
y242, A75, B250, B271, F186, F209
- `\rlap` ..... l424,  
l427, l788, z365, z376, B406, C69
- `\rlh@` ..... t425, t426
- `\rmdefault` ..... s6, s81, t42, t90
- `\rmfamily` ..... s4, s5, v15
- `\rmoustache` ..... t526
- `\Roman` ..... 155, m104
- `\roman` ..... 155, m103
- `\romannumeral` ..... m109,  
m110, y120, A43, A234, A245
- `\root` ..... z66, z310
- `\rootbox` ..... z66
- `\rq` ..... b361
- `\rule` ..... 323, B334, B337, G419
- S**
- `\S` ..... l308
- `\s@fct@` ..... p380, p444
- `\s@fct@fixed` ..... p501
- `\s@fct@gen` ..... p456
- `\s@fct@genb` ..... p461
- `\s@fct@sgen` ..... p456
- `\s@fct@sgenb` ..... p461
- `\s@fct@sub` ..... p468
- `\s@fct@subf` ..... p493
- `\samepage` ..... 71, i11, i28
- `\savebox` ..... 322, B71
- `\savecatcodetable` . N117, N168, N170
- `\saved@space@catcode` ... O251, O320
- `\sb` ..... z199
- `\sbox` ..... 322, b411, j4, l492, l508,  
A205, B77, B84, B88, B93, B98
- `\scan@fontshape` ..... q7, q40, q43
- `\scan@fontshape` ..... q6, q26, q37
- `\scdefault` ..... s27, t86
- `\scriptfont` ..... p292
- `\scriptfont@name` ..... p287, p292
- `\scriptscriptfont` ..... p293
- `\scriptscriptstyle` ..... z65, z68
- `\scriptspace` ..... b336
- `\scriptstyle` ..... t306, z64
- `\scshape` ..... l297, s25, s26, v23
- `\searrow` ..... t371
- `\sec` ..... z20
- `\secdef` ..... F142
- `\sectionmark` ..... F143
- `\select@group` o463, o482, r48, r236,  
r273, r411, r464, r473, r511, r543
- `\selectfont` .....  
j7, l299, l326, l357, l443, l800,

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- l1160, l1194, l1495, l1567, l1585,
- o247, p112, s6, s9, s12, s15, s18,
- s21, s24, s27, s30, s74, G379, G387
- \seriesdefault ..... r239, s96, t90
- \set@mathdelimiter ..... r913, r946
- \set@color ..... B62
- \set@curr@file ..... k152,
- k160, k222, k240, k271, k276, L582
- \set@display@protect ..... d3, d225, g7, g14, g34, g61
- \set@fontsize . o250, o252, p119, p132
- \set@mathaccent ..... r598, r606, r641, r649, r667
- \set@mathchar ..... r722, r732
- \set@mathdelimiter ..... r805, r814, r862, r871, r925
- \set@mathradical ..... r244, r982
- \set@mathsymbol ..... r706, r714, r735
- \set@simple@size@args ..... p302, p315, p322, p343, p357
- \set@size@funct@args p305, p307, p365
- \set@size@funct@args@ ..... p365
- \set@typeset@protect ..... d225, d244, C185,
- C211, K603, K605, K661, K663
- \setattribute ..... 531, N82, N226
- \setcounter ..... 155, k215, m2, m37, A225,
- K2290, K2293, K2296, K2300
- \setlength 162, n4, z443, z448, z449,
- z450, B43, B159, B220, B223,
- B296, B353, B354, B355, B384,
- B385, B392, B393, B394, C164,
- C360, K2306, K2307, K2308,
- K2311, K2312, K2316, K2317,
- K2318, K2322, K2323, K2324
- \SetMathAlphabet ..... o11, q140, q141, r480, t125, t126
- \SetMathAlphabet@ ... r418, r487, r496
- \setminus ..... t358
- \setrangecatcode ..... N96, N104, N113, N114
- \SetSymbolFont . r335, t115, t116, t117
- \SetSymbolFont@ ..... r308, r342, r350
- \settodepth ..... 162, n17
- \settoheight ..... 162, n17
- \settowidth ..... 162, n17
- \sf@size ..... j6, l299, o188,
- o207, o502, p282, p286, G381, G389
- \sfcode ... b353, b354, b355, b356,
- b440, i326, k43, k101, O183, O446
- \sfdefault ..... s9, t42
- \sffamily ..... s7, s8, v16
- \sh@ft ..... b428
- \shapedefault ..... r240, s97, t90
- \sharp ..... t299
- \shipout ..... K602, K660
- \shortstack ..... D43, D433, D450
- \showboxbreadth ..... b325, b443, b496, b513, b529
- \showboxdepth ..... b326, b443,
- b495, b512, b530, o521, o565, o582
- \showhyphens ..... o510
- \showoutput ..... b442
- \showoverfull . b441, b444, b478, b486
- \Sigma ..... t273
- \sigma ..... t254
- \sim ..... t406, t418
- \simeq ..... t407
- \sin ..... z9
- \sinh ..... z11
- \sixt@n a71, b16, b64, b66, b96, b97,
- b98, o14, r84, r175, r584, r586,
- r632, r634, r693, r695, r741,
- r743, r785, r787, r793, r795,
- r844, r846, r852, r854, r900,
- r902, r908, r910, r968, r970,
- r976, r978, D136, D151, D153,
- G62, G80, G131, G153, K1005,
- K1051, K1190, K1358, K1592,
- K1656, K1713, K1783, K2009,
- K2018, K2074, K2090, K2123, N28
- \size@update .. p128, p139, p158, p160
- \sizefn@info ..... p306, p308, p316, p344, p358
- \skew ..... t505
- \skip b28, b53, b92, b208, b239, b284,
- B313, G367, K316, K490, N31
- \skip@ ..... b41,
- b390, b392, b393, b395, v88, v91
- \skipdef ..... b45, b53, b92, N216
- \skipzero ..... N216
- \slash ..... b396, d435, d456
- \sldefault ..... s24, t86
- \sloppy ..... B255, B274, J57, J62
- \sloppypar ..... J62
- sloppypar (environment) ..... J62
- \slshape ..... l434, l791, s22, s23, v22
- \smallbreak ..... b404, d436, d457
- \smallint ..... t326
- \smallskip ..... b405, i310
- \smallskipamount .... b404, i310, i313
- \smash t434, t508, t509, t512, t513, z126
- \smile ..... t411
- \sp ..... z199
- \sp@n ..... C355
- \space ..... b369

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx, e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx, j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx, o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx, t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx, y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx, D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx, I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx, N=ltluatex.dtx, O=ltfinal.dtx



- \spacefactor [b394](#), [b395](#), [i103](#), [i112](#),  
[i131](#), [i145](#), [i157](#), [i171](#), [i185](#), [i326](#),  
[i342](#), [i347](#), [i70](#), [i71](#), [G434](#), [G436](#)
  - \spaceskip ..... [s80](#)
  - \spadesuit ..... [t303](#)
  - \span ..... [C359](#)
  - \split@name .....  
[o290](#), [o302](#), [o357](#), [o372](#), [p473](#), [p487](#)
  - \splitfirstmark ..... [K2211](#)
  - \splitmaxdepth ... [b332](#), [G412](#), [K2205](#)
  - \splittopskip ..... [b344](#), [G411](#)
  - \sqcap ..... [t341](#)
  - \sqcup ..... [t342](#)
  - \sqrt ..... [z309](#)
  - \sqrtsign ..... [t490](#), [z71](#), [z309](#)
  - \sqsubset ..... [s109](#)
  - \sqsubseteq ..... [t364](#)
  - \sqsupset ..... [s110](#)
  - \sqsupseteq ..... [t365](#)
  - \SS ..... [i301](#), [i528](#), [i1105](#), [O481](#)
  - \ss . [i252](#), [i403](#), [i551](#), [i775](#), [i1080](#), [O481](#)
  - \ssf@size ..... [i325](#), [i357](#),  
[i1193](#), [o189](#), [o208](#), [o503](#), [p282](#), [p288](#)
  - \stackrel ..... [z307](#)
  - \star ..... [t362](#)
  - \stepcounter ..... [i155](#), [m17](#), [m27](#),  
[o475](#), [r48](#), [x40](#), [x52](#), [z317](#), [z360](#),  
[z437](#), [G399](#), [G423](#), [K646](#), [K705](#)
  - \stop ..... [y86](#)
  - \storedpar ..... [N156](#), [N161](#)
  - \stretch ..... [i356](#)
  - \strip@prefix ..... [a111](#), [a228](#),  
[a323](#), [d202](#), [d261](#), [d288](#), [d389](#), [o460](#)
  - \strip@pt ..... [b432](#),  
[o180](#), [o186](#), [o187](#), [o188](#), [o189](#),  
[o202](#), [o206](#), [o262](#), [o502](#), [o503](#), [p134](#)
  - \strut [b412](#), [d437](#), [d458](#), [z178](#), [z179](#), [C29](#)
  - \strutbox ..... [b412](#), [p143](#),  
[B334](#), [C174](#), [C175](#), [G412](#), [G419](#)
  - \sub@sfcnt ..... [p468](#), [p469](#), [p470](#)
  - \subf@sfcnt ..... [p493](#), [p494](#), [p495](#)
  - \subparagraphmark ..... [F143](#)
  - \subsectionmark ..... [F143](#)
  - \subset ..... [t390](#)
  - \subseteq ..... [t392](#)
  - \subst@correction ..... [o49](#), [o55](#)
  - \subst@fontshape ..... [q8](#), [q80](#)
  - \subst@size ..... [p419](#)
  - \subsubsectionmark ..... [F143](#)
  - \succ ..... [t384](#)
  - \succeq ..... [t387](#)
  - \sum ..... [t319](#)
  - \sup ..... [z24](#)
  - \suppressfloats ..... [K1972](#)
  - \supset ..... [t389](#)
  - \supseteq ..... [t391](#)
  - \surd ..... [t305](#)
  - \sw@slant ..... [v74](#), [v84](#)
  - \swarrow ..... [t373](#)
  - \symbol ..... [i160](#), [s68](#)
  - \symletters ..... [i1791](#), [s82](#)
  - \symoperators ..... [t604](#)
- T**
- \T ..... [g23](#), [i332](#),  
[i334](#), [i336](#), [i338](#), [i340](#), [i342](#), [i344](#),  
[i346](#), [i348](#), [i371](#), [L773](#), [L777](#), [L778](#)
  - \t . . [i280](#), [i732](#), [i840](#), [i1511](#), [i1778](#), [i1780](#)
  - \t@st@ic ..... [v73](#), [v77](#)
  - \tabbing ..... [C59](#)
  - \tabbingsep ..... [C118](#), [C120](#), [C154](#)
  - \tabcolsep ..... [C235](#), [C314](#)
  - \tabskip ..... [b423](#), [z195](#),  
[z196](#), [z322](#), [z325](#), [z328](#), [z330](#),  
[z441](#), [z454](#), [z457](#), [z459](#), [C155](#), [C180](#)
  - \tabular ..... [C162](#)
  - \tabular\* ..... [C163](#)
  - \tabularnewline ..... [C182](#), [C195](#)
  - \tan ..... [z15](#)
  - \tanh ..... [z17](#)
  - \tau ..... [t255](#)
  - \tc@check@accent .....  
[i1590](#), [i1666](#), [i1668](#), [i1670](#)
  - \tc@check@symbol ..... [i1590](#),  
[i1660](#), [i1662](#), [i1664](#), [i1672](#), [i1674](#),  
[i1676](#), [i1678](#), [i1680](#), [i1682](#), [i1684](#),  
[i1686](#), [i1688](#), [i1690](#), [i1692](#), [i1694](#),  
[i1696](#), [i1698](#), [i1700](#), [i1702](#), [i1704](#),  
[i1706](#), [i1708](#), [i1710](#), [i1712](#), [i1714](#),  
[i1716](#), [i1718](#), [i1720](#), [i1722](#), [i1724](#),  
[i1726](#), [i1728](#), [i1730](#), [i1732](#), [i1734](#),  
[i1736](#), [i1738](#), [i1740](#), [i1742](#), [i1744](#),  
[i1746](#), [i1748](#), [i1750](#), [i1752](#), [i1754](#),  
[i1756](#), [i1758](#), [i1760](#), [i1762](#), [i1764](#),  
[i1766](#), [i1768](#), [i1770](#), [i1772](#), [i1774](#)
  - \tc@error ..... [i1570](#), [i1591](#)
  - \tc@errorwarn ..... [i1529](#), [i1530](#), [i1563](#)
  - \tc@fake@euro ..... [i1578](#), [i1659](#)
  - \tc@forcedfalse ..... [i1523](#)
  - \tc@forcedtrue ..... [i1528](#)
  - \tc@subst ..... [i1562](#), [i1590](#)
  - \tencirc ..... [u10](#), [D37](#), [D364](#)
  - \tencircw ..... [u10](#), [D39](#)
  - \tenln ..... [u9](#), [D37](#), [D38](#), [D363](#), [D365](#)
  - \tenlnw ..... [u9](#), [D39](#), [D40](#)
  - \TeX ..... [j1](#), [j12](#)
  - \TeXOrMath ..... [m127](#), [m143](#)
  - \text@command ..... [v8](#), [v29](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

`\textacutedbl` . . . . . 1895, 11101, 11623  
`\textascendercompwordmark` 1845, 11606  
`\textasciicircum` . . . . . 1945, 11062, 11647  
`\textasciibreve` . . . . . 1893, 11100, 11620  
`\textasciicaron` . . . . . 1894, 11099, 11621  
`\textasciicircum` . . . . . 1284, 1552, 11036  
`\textasciidieresis` . . . . . 1933, 11049, 11637  
`\textasciigrave` . . . . . 1884, 11028, 11618  
`\textasciimacron` . . . . . 1940, 11057, 11642  
`\textasciitilde` . . . . . 1285, 1553, 11041  
`\textasteriskcentered` . . . . . 1265,  
1708, 1855, 11154, 11613, m130, m136  
`\textbackslash` . . . . . 1266, 1554, 1709, 11035  
`\textbaht` . . . . . 1919, 11104, 11753, 11754  
`\textbar` . . . . . 1267, 1555, 1710, 11039  
`\textbardbl` . . . . . 1268, 1711, 1899, 11109, 11626, m135  
`\textbf` . . . . . v19  
`\textbigcircle` . . . . . 1720, 1872, 11171, 11705, 11706  
`\textblank` . . . . . 1852, 11168, 11675, 11676  
`\textborn` . . . . . 1885, 11711, 11712  
`\textbraceleft` . . . . . 1269, 1305, 1556, 1712, 11038  
`\textbraceright` . . . . . 1270, 1306, 1557, 1713, 11040  
`\textbrokenbar` . . . . . 1931, 11047, 11635  
`\textbullet` 1271, 1714, 1901, 11118, 11628  
`\textcapitalcompwordmark` . . . . . 1844, 11605  
`\textcelsius` . . . . . 1902, 11137, 11629  
`\textcent` . . . . . 1927, 11043, 11632  
`\textcentoldstyle` . . . . . 1904, 11727, 11728  
`\textcircled` . . . . . 1277, 1281, 1297,  
1298, 1721, 1873, 11510, 11775, 11777  
`\textcircledP` . . . . . 1938, 11139, 11769, 11770  
`\textcolonmonetary` . . . . . 1906, 11130, 11729, 11730  
`\textcommaabove` . . . . . 1350, 1352,  
1366, 1367, 1452, 1453, 1691, 1692  
`\textcommabelow` . . . . . 1321, 1323,  
1329, 1330, 1694, 1695, 1696, 1697,  
1698, 1699, 1700, 1701, 1702, 1703,  
11191, 11388, 11389, 11390, 11391  
`\textcompsubstdefault` . . . . . 11567, 11569  
`\textcompwordmark` . . . . . 1286, 1558, 11106  
`\textcopyleft` . . . . . 1936, 11767, 11768  
`\textcopyright` . . . . . 1281, 1314, 1934, 11050, 11638  
`\textcurrency` . . . . . 1929,  
11045, 11505, 11509, 11663, 11664  
`\textdagger` . . . . . 1273, 1309,  
1716, 1897, 11116, 11624, m131, m137  
`\textdaggerdbl` . . . . . 1272, 1310,  
1715, 1898, 11117, 11625, m132, m138  
`\textdblhyphen` . . . . . 1856, 11677, 11678  
`\textdblhyphenchar` . . . . . 1892, 11723, 11724  
`\textdegree` . . . . . 1941, 11058, 11643  
`\textdied` . . . . . 1887, 11715, 11716  
`\textdiscount` . . . . . 1921, 11129, 11757, 11758  
`\textdiv` . . . . . 1958, 11083, 11657  
`\textdivorced` . . . . . 1886, 11174, 11713, 11714  
`\textdollar` . . . . . 1253, 1304, 1432, 1559,  
1789, 1853, 11032, 11611, 11783, 11785  
`\textdollaroldstyle` 1903, 11725, 11726  
`\textdong` . . . . . 1915, 11134, 11747, 11748  
`\textdownarrow` 1883, 11149, 11709, 11710  
`\texteightoldstyle` . . . . . 1866, 11695, 11696  
`\textellipsis` . . . . . 1293, 1318, 11119  
`\textemdash` 1254, 1404, 1560, 1776, 11108  
`\textendash` 1255, 1405, 1561, 1777, 11107  
`\textestimated` . . . . . 1922, 11145, 11508, 11661, 11662  
`\texteuro` 1956, 11135, 11506, 11658, 11659  
`\textexclamdown` . . . . . 1256, 1406, 1408, 1562, 1778, 11042  
`\textfiveoldstyle` . . . . . 1863, 11689, 11690  
`\textfloatsep` . . . . . K728, K741, K2104, K2154, K2303  
`\textflorin` . . . . . 1905, 11097, 11630  
`\textfont` . . . . . p291, z205  
`\textfont@name` . . . . . p285, p291  
`\textfouroldstyle` . . . . . 1862, 11687, 11688  
`\textfraction` . . . . . K1917, K1920,  
K1944, K1947, K2096, K2297  
`\textfractionsolidus` 1857, 11126, 11614  
`\textgravedbl` . . . . . 1896, 11102, 11622  
`\textgreater` . . . . . 1279, 1563, 1731, 11034  
`\textguarani` . . . . . 1909, 11735, 11736  
`\textheight` . . . . . k20,  
k21, k77, k78, G257, G258,  
G261, G287, G301, K78, K225,  
K226, K274, K399, K447, K474,  
K645, K704, K763, K815, O89, O90  
`\texthyphen` . . . . . 1258, 1411, 1565, 1780  
`\texthyphenchar` . . . . . 1257, 1410, 1564, 1779  
`\textinterrobang` . . . . . 1913, 11125, 11743, 11744  
`\textinterrobangdown` . . . . . 1914, 11175, 11745, 11746  
`\textit` . . . . . v21  
`\textlangle` . . . . . 1868, 11166, 11699, 11700  
`\textlbrackdbl` . . . . . 1880, 11616  
`\textleaf` . . . . . 1888, 11717, 11718  
`\textleftarrow` 1850, 11146, 11671, 11672  
`\textless` . . . . . 1278, 1566, 1730, 11033  
`\textlira` . . . . . 1911, 11131, 11739, 11740  
`\textlnot` . . . . . 1937, 11055, 11640  
`\textlquill` . . . . . 1925, 11127, 11763, 11764

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfsssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=ltthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- \textmarried .. 1889, 11173, 11719, 11720
- \textmd ..... v19
- \textmho ..... 1871, 11144, 11703, 11704
- \textminus ..... 1869, 11150, 11615
- \textmu ..... 1946, 11063, 11648
- \textmusicalnote .....
  - ..... 1890, 11172, 11721, 11722
- \textnaira ... 1908, 11132, 11733, 11734
- \textnineoldstyle . 1867, 11697, 11698
- \textnormal ..... v15
- \textnumero ... 1920, 11138, 11755, 11756
- \textogonekcentered .. 1481, 1689, 1690
- \textohm ..... 1879, 11143, 11507, 11660
- \textonehalf ..... 1954, 11072, 11654
- \textoneoldstyle .. 1859, 11681, 11682
- \textonequarter ... 1953, 11071, 11653
- \textonesuperior .. 1950, 11066, 11651
- \textopenbullet 1923, 11170, 11759, 11760
- \textordfeminine 1302, 1935, 11051, 11639
- \textordmasculine .....
  - ..... 1303, 1951, 11067, 11652
- \TextOrMath ..... m130,
  - m131, m132, m133, m134,
  - m135, m136, m137, m138, m150
- \textparagraph ..... 1274,
  - 1307, 1717, 1947, 11064, 11649, m134
- \textperiodcentered .....
  - ..... 1275, 1718, 1948, 11065, 11650
- \textpertenthousand ..... 1486,
  - 1917, 11121, 11749, 11750, 11787
- \textperthousand .....
  - ... 1484, 1900, 11120, 11627, 11786
- \textpeso .... 1910, 11136, 11737, 11738
- \textpilcrow ..... 1918, 11751, 11752
- \textpm ..... 1942, 11059, 11644
- \textquestiondown .....
  - . 1259, 1407, 1409, 1567, 1781, 11074
- \textquotedbl ..... 1570, 11030
- \textquotedblleft .....
  - ..... 1260, 1412, 1568, 1782, 11113
- \textquotedblright .....
  - ..... 1261, 1413, 1569, 1783, 11114
- \textquoteleft .....
  - ..... 1262, 1414, 1571, 1784, 11110
- \textquoteright .....
  - ..... 1263, 1415, 1572, 1785, 11111
- \textquotesingle .. 1854, 11026, 11612
- \textquotestraightbase .. 1846, 11607
- \textquotestraightdblbase 1847, 11608
- \textrangle ... 1870, 11167, 11701, 11702
- \textrbrackdbl ..... 1881, 11617
- \textrecipe ... 1912, 11140, 11741, 11742
- \textreferencemark .....
  - ..... 1949, 11124, 11771, 11772
- \textregistered .....
  - ..... 1297, 1298, 1939, 11056, 11641
- \textrightarrow 1851, 11148, 11673, 11674
- \textrm ..... v15
- \textrquill ... 1926, 11128, 11765, 11766
- \textsc ..... v21
- \textsection ..... 1276, 1308,
  - 1573, 1719, 1932, 11048, 11636, m133
- \textservicemark .....
  - ..... 1924, 11141, 11761, 11762
- \textsevenoldstyle . 1865, 11693, 11694
- \textsf ..... v15
- \textsixoldstyle .. 1864, 11691, 11692
- \textsl ..... v21
- \textsterling 1264, 1316, 1439, 1574,
  - 1796, 1928, 11044, 11633, 11782, 11784
- \textstyle ..... j15, t430, z63
- \textsubscript .... G382, G393, G394
- \textsuperscript 1300, 1302, 1303, G378
- \textsurd .... 1952, 11165, 11773, 11774
- \TextSymbolUnavailable .... 13, 1749
- \textthreeoldstyle . 1861, 11685, 11686
- \textthreequarters . 1955, 11073, 11655
- \textthreequartersemdash . 1849, 11610
- \textthreesuperior . 1944, 11061, 11646
- \texttildelow ..... 1891, 11103, 11619
- \texttimes ..... 1957, 11077, 11656
- \texttrademark 1300, 1916, 11142, 11631
- \texttt ..... v15
- \texttwelvewardash ..... 1848, 11609
- \texttwooldstyle .. 1860, 11683, 11684
- \texttwosuperior .. 1943, 11060, 11645
- \textunderscore 1287, 1312, 1575, 11037
- \textup ..... v21
- \textuparrow .. 1882, 11147, 11707, 11708
- \textvisiblespace .. 1289, 1576, 11169
- \textwidth .....
  - .. k22, k79, B301, G266, K79,
  - K144, K201, K218, K630, K640,
  - K689, K699, K2223, K2255, O90
- \textwon ..... 1907, 11133, 11731, 11732
- \textyen ..... 1930, 11046, 11634
- \textzerooldstyle . 1858, 11679, 11680
- \tf@size . o187, o207, o501, p282, p284
- \TH ..... 1529, 11079, O481
- \th ..... 1577, 11085, O481
- \thanks ..... 384, F10, F26
- thebibliography (environment) .. 417
- \theequation ... z306, z318, z377, z438
- \thefootnote . G372, G424, G429, G449
- \thempfn ..... B303,
  - G400, G405, G440, G445, G448
- \thempfootnote ..... B303, G374

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx, e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx, j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx, o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx, t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx, y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx, D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx, I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx, N=ltluatex.dtx, O=ltfinal.dtx

- \thepage ..... [k137](#),  
[w6](#), [x14](#), [x34](#), [F164](#), [F171](#), [H15](#),  
[H32](#), [J14](#), [K244](#), [K275](#), [K1827](#), [I23](#)
- \Theta ..... [t269](#)
- \theta ..... [t245](#)
- \thicklines ..... [D37](#)
- \thickmuskip ..... [t607](#), [z203](#)
- \thinline ..... [D37](#), [D434](#), [D451](#)
- \thinmuskip .... [i336](#), [t605](#), [z201](#), [z204](#)
- \thinspace ..... [i336](#),  
[i360](#), [i361](#), [i368](#), [i369](#), [z176](#), [z205](#)
- \thispagestyle ..... [J6](#)
- \thr@@ . [b16](#), [b473](#), [p58](#), [p208](#), [p214](#),  
[p227](#), [p234](#), [p241](#), [p246](#), [z329](#),  
[z458](#), [A232](#), [A243](#), [D145](#), [D146](#),  
[D148](#), [D149](#), [D181](#), [D203](#), [O70](#), [O78](#)
- \tilde ..... [t480](#)
- \time ..... [a179](#), [a183](#)
- \times ..... [t361](#)
- \title .... [384](#), [F6](#), [F7](#), [F21](#), [F23](#), [F31](#)
- \to ..... [t403](#)
- \today .... [a184](#), [a188](#), [a196](#), [a199](#), [F33](#)
- \toks ..... [b31](#), [b63](#), [b95](#),  
[r453](#), [r454](#), [r464](#), [r473](#), [N34](#), [O532](#)
- \toks@ ..... [b41](#), [c81](#), [c85](#),  
[c88](#), [c93](#), [i318](#), [i319](#), [i324](#), [o112](#),  
[o116](#), [o118](#), [o121](#), [o185](#), [o190](#), [r6](#),  
[r7](#), [r259](#), [r263](#), [r269](#), [r272](#), [r277](#),  
[r323](#), [r324](#), [r326](#), [r327](#), [r357](#),  
[r359](#), [r363](#), [r380](#), [r383](#), [r442](#),  
[r454](#), [r455](#), [r456](#), [r502](#), [r504](#),  
[r510](#), [r518](#), [r522](#), [r534](#), [r537](#),  
[r540](#), [r548](#), [r550](#), [r1035](#), [r1037](#),  
[r1039](#), [r1042](#), [r1044](#), [r1047](#),  
[r1050](#), [r1082](#), [r1083](#), [K2209](#),  
[K2210](#), [K2211](#), [K2212](#), [L186](#),  
[L187](#), [L189](#), [L190](#), [L482](#), [L483](#)
- \toksdef ..... [b46](#), [b63](#), [b95](#), [N217](#)
- \tokszero ..... [N217](#)
- \tolerance .....  
[b304](#), [o521](#), [o566](#), [o581](#), [J58](#), [J66](#)
- \top ..... [t290](#)
- \topfigrule ..... [K727](#), [K2325](#)
- \topfraction ..... [G273](#), [K2291](#)
- \topmargin ..... [K71](#), [K624](#), [K683](#)
- \topmark ..... [K2209](#), [K2218](#)
- \topsep ..... [z443](#), [A2](#), [A59](#)
- \topskip ... [b343](#), [k56](#), [k111](#), [A1](#), [K128](#)
- \totalheight ..... [B33](#), [B34](#), [B35](#)
- \tracefloats ..... [K1897](#)
- \tracefloatsoff ..... [K1897](#)
- \tracefloatvals ..... [K1897](#)
- \tracingall ..... [b446](#)
- \tracingassigns ..... [b475](#), [b508](#)
- \tracingcommands .....  
[b457](#), [b473](#), [b482](#), [b494](#), [b511](#)
- \tracingfonts ..... [p17](#), [p54](#), [p58](#),  
[p86](#), [p116](#), [p125](#), [p148](#), [p178](#),  
[p192](#), [p208](#), [p214](#), [p227](#), [p234](#),  
[p241](#), [p246](#), [p255](#), [p268](#), [p276](#), [p279](#)
- \tracinggroups ..... [b466](#), [b519](#)
- \tracingifs ..... [b467](#), [b518](#)
- \tracinglostchars .....  
[b320](#), [b452](#), [b464](#), [b483](#), [b502](#), [b522](#)
- \tracingmacros .....  
[b456](#), [b472](#), [b484](#), [b501](#), [b521](#)
- \tracingnesting ..... [b469](#), [b516](#)
- \tracingnone ..... [b488](#)
- \tracingoff ..... [p116](#), [p276](#)
- \tracingon ..... [p117](#), [p277](#)
- \tracingonline .....  
[b441](#), [b493](#), [b510](#), [b531](#), [o530](#)
- \tracingoutput [b442](#), [b497](#), [b514](#), [b528](#)
- \tracingpages .....  
[b451](#), [b463](#), [b483](#), [b503](#), [b523](#)
- \tracingparagraphs .....  
[b453](#), [b465](#), [b484](#), [b500](#), [b520](#)
- \tracingrestores .....  
[b458](#), [b474](#), [b484](#), [b499](#), [b509](#)
- \tracingscantokens .....  
[b448](#), [b468](#), [b491](#), [b517](#)
- \tracingstats .....  
[b450](#), [b462](#), [b482](#), [b504](#), [b524](#), [O2](#)
- \triangle ..... [t292](#)
- \triangleleft ..... [t327](#), [t443](#)
- \triangleright ..... [t328](#), [t443](#)
- \trivlist . [y172](#), [y202](#), [y204](#), [y218](#),  
[y240](#), [z428](#), [A89](#), [C66](#), [E35](#), [E37](#)
- \try@load@fontshape .....  
[o305](#), [o313](#), [o405](#), [p474](#), [r208](#), [r225](#)
- \try@simple@size ..... [p310](#), [p435](#)
- \try@simples ..... [p393](#), [p399](#), [p403](#)
- \try@size@range .... [p101](#), [p310](#), [p386](#)
- \try@size@substitution .. [p103](#), [p390](#)
- \tryif@simple ..... [p401](#), [p402](#)
- \tryis@simple ..... [p402](#)
- \ttdefault ..... [s12](#), [t42](#)
- \ttfamily ..... [s10](#), [s11](#), [v17](#), [y262](#)
- \tw@ ..... [b16](#)
- \two@digits ..... [a86](#), [a185](#),  
[a186](#), [d2](#), [p466](#), [L535](#), [L631](#), [L721](#)
- \twocolumn ..... [K199](#)
- \type@restoreinfo ..... [p156](#), [p161](#)
- \typein ..... [37](#), [37](#), [d16](#)
- \typeout . [37](#), [a73](#), [a116](#), [a172](#), [a197](#),  
[a199](#), [a211](#), [a226](#), [a233](#), [a244](#),  
[a257](#), [a270](#), [a283](#), [a321](#), [c21](#), [c38](#),

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdc1.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- c43, c48, [d3](#), d21, d28, g74,  
k129, k358, k359, k361, k396,  
k406, k409, o299, s123, s133,  
s143, t9, t95, H8, H25, K1898,  
L153, L790, L989, L992, O207,  
O485, O492, O504, O505, O513
- U**
- [\u](#) ..... l235,  
l383, l466, l580, l587, l607, l614,  
l745, l1181, l1256, l1257, l1272,  
l1273, l1282, l1283, l1296, l1297,  
l1298, l1322, l1323, l1348, l1349
- [\uccode](#) ..... O173, O181,  
O188, O190, O193, O195, O436,  
O444, O451, O453, O456, O458
- [\uchyph](#) ..... b321
- [\Umathchar](#) .. t14, t42, t57, N28, O247
- [\Umathcode](#) ... b127, y268, O93, O430
- [\unboldmath](#) ..... s65
- [\UndeclareTextCommand](#) [l189](#), l1782,  
l1783, l1784, l1785, l1786, l1787
- [\undefined](#) . a9, a11, a17, a57, m92,  
m93, m94, m95, m96, m97,  
m98, m99, O101, O113, O114, O134
- [\undefinedpagestyle](#) ..... J4, J8
- [\underbar](#) ..... [b411](#), d438, d459
- [\underbrace](#) ..... t501
- [\underline](#) .... [323](#), b411, B358, [B359](#)
- [\unexpanded](#) ... y102, y119, L818, L820
- [\unhcopy](#) ..... b413, C321, D418
- [\unicodedataline](#) .....  
.. N143, N146, N160, N161, N162
- [\UnicodeEncodingName](#) .....  
. 1961, 1967, 1995, l1006, l1010,  
l1026, l1028, l1030, l1032, l1033,  
l1034, l1035, l1036, l1037, l1038,  
l1039, l1040, l1041, l1042, l1043,  
l1044, l1045, l1046, l1047, l1048,  
l1049, l1050, l1051, l1052, l1054,  
l1055, l1056, l1057, l1058, l1059,  
l1060, l1061, l1062, l1063, l1064,  
l1065, l1066, l1067, l1068, l1070,  
l1071, l1072, l1073, l1074, l1075,  
l1076, l1077, l1078, l1079, l1080,  
l1081, l1082, l1083, l1084, l1085,  
l1086, l1087, l1088, l1089, l1090,  
l1091, l1092, l1093, l1094, l1095,  
l1096, l1097, l1098, l1099, l1100,  
l1101, l1102, l1103, l1104, l1105,  
l1106, l1107, l1108, l1109, l1110,  
l1111, l1112, l1113, l1114, l1115,  
l1116, l1117, l1118, l1119, l1120,  
l1121, l1122, l1123, l1124, l1125,  
l1126, l1127, l1128, l1129, l1130,  
l1131, l1132, l1133, l1134, l1135,  
l1136, l1137, l1138, l1139, l1140,  
l1141, l1142, l1143, l1144, l1145,  
l1146, l1147, l1148, l1149, l1150,  
l1152, l1153, l1154, l1165, l1166,  
l1167, l1168, l1169, l1170, l1171,  
l1172, l1173, l1174, l1175, l1176,  
l1177, l1178, l1179, l1180, l1181,  
l1182, l1183, l1184, l1185, l1186,  
l1187, l1188, l1189, l1190, l1191
- [\UnicodeFontFile](#) ..... 1993
- [\UnicodeFontName](#) ..... 1994
- [\UnicodeFontTeXLigatures](#) .. 1973, 1990
- [\unicoderead](#) ..... N143,  
N157, N158, N159, N160, N165
- [\uninstall](#) ..... [N773](#)
- [\unitlength](#) B49, B59, [D5](#), D12, D13,  
D14, D15, D22, D23, D26, D27,  
D34, D58, D116, D169, D171,  
D184, D189, D191, D206, D208,  
D211, D251, D252, D296, D297,  
D331, D342, D372, D373, D375,  
D376, D379, D380, D382, D383,  
D392, D394, D396, D398, O82
- [\unkern](#) ..... o549
- [\unless](#) ..... N151, N159, N161
- [\unlhd](#) ..... s112
- [\unpenalty](#) o552, o556, v99, y234, y256
- [\unquote@name](#) ..... k230, [k236](#), k275
- [\unrestored@protected@xdef](#) .....  
[d227](#), G405, G429, G445, J25, J49
- [\unrhd](#) ..... s114
- [\unsetattribute](#) ..... [531](#), [N82](#), N227
- [\unvcopy](#) ..... z180
- [\Uparrow](#) ..... t545
- [\uparrow](#) ..... t539
- [\upbracefill](#) ..... t504, t521
- [\update@ucl@with@cyrillic](#) .....  
..... l1438, l1466, l1490, l1496
- [\updefault](#) ..... s21, [t86](#), t92
- [\Updownarrow](#) ..... t549
- [\updownarrow](#) ..... t543
- [\uplus](#) ..... t343
- [\upper@bound](#) .. p337, p338, p339, [p352](#)
- [\uppercase](#) ..... O468
- [\upshape](#) ..... l436, l723, l793,  
l875, s19, s20, s37, s43, s91, v24
- [\Upsilon](#) ..... t274
- [\upsilon](#) ..... t256
- [\use@mathgroup](#) .....  
.. o469, o487, o489, p253, r63,  
r92, r424, r526, r529, r1060, r1084
- [\usebox](#) ..... [B111](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx

- `\usecounter` ..... [A225](#), [A238](#)  
`\usefont` [o44](#), [o246](#), [o526](#), [s81](#), [s94](#), [y272](#)  
`\usepackage` ..... [L278](#), [L308](#), [L805](#)  
`\UseRawInputEncoding` [O277](#), [O333](#), [O380](#)  
`\UseTextAccent` ... [l147](#), [l148](#), [l186](#),  
[l1591](#), [l1776](#), [l1777](#), [l1779](#), [l1780](#)  
`\UseTextSymbol` [l148](#), [l184](#), [l1590](#), [l1659](#)  
`\UTFfour@octets@noexpand` [O467](#), [O476](#)  
`\UTFthree@octets@noexpand` .....  
[O466](#), [O475](#)  
`\UTFtwo@octets@noexpand` [O465](#), [O474](#)  
`\UTFviii@four@octets` [O306](#), [O311](#), [O317](#)  
`\UTFviii@four@octets@@` . [O306](#), [O317](#)  
`\UTFviii@four@octets@combine` . [O341](#)  
`\UTFviii@four@octets@noexpand` [O347](#)  
`\UTFviii@four@octets@string` .. [O344](#)  
`\UTFviii@invalid` ..... [O245](#), [O338](#)  
`\UTFviii@invalid@err` [O303](#), [O308](#), [O314](#)  
`\UTFviii@invalid@err@@` . [O303](#), [O314](#)  
`\UTFviii@three@octets` .....  
[O305](#), [O310](#), [O316](#)  
`\UTFviii@three@octets@@` [O305](#), [O316](#)  
`\UTFviii@three@octets@combine` [O340](#)  
`\UTFviii@three@octets@noexpand` [O346](#)  
`\UTFviii@three@octets@string` . [O343](#)  
`\UTFviii@two@octets` [O304](#), [O309](#), [O315](#)  
`\UTFviii@two@octets@@` .. [O304](#), [O315](#)  
`\UTFviii@two@octets@combine` .. [O339](#)  
`\UTFviii@two@octets@noexpand` . [O345](#)  
`\UTFviii@two@octets@string` ... [O342](#)  
`\UTFviii@undefined@err` .....  
[O302](#), [O307](#), [O313](#)  
`\UTFviii@undefined@err@@` [O302](#), [O313](#)
- V**
- `\v` ..... [l236](#), [l384](#), [l465](#),  
[l583](#), [l584](#), [l585](#), [l589](#), [l591](#), [l594](#),  
[l596](#), [l598](#), [l604](#), [l610](#), [l611](#), [l612](#),  
[l616](#), [l618](#), [l621](#), [l623](#), [l625](#), [l631](#),  
[l746](#), [l1186](#), [l1266](#), [l1267](#), [l1268](#),  
[l1269](#), [l1278](#), [l1279](#), [l1312](#), [l1313](#),  
[l1318](#), [l1319](#), [l1330](#), [l1331](#), [l1338](#),  
[l1339](#), [l1342](#), [l1343](#), [l1365](#), [l1366](#),  
[l1367](#), [l1368](#), [l1369](#), [l1370](#), [l1371](#),  
[l1372](#), [l1373](#), [l1374](#), [l1375](#), [l1378](#),  
[l1379](#), [l1380](#), [l1381](#), [l1384](#), [l1385](#)  
`\v@false` ..... [z82](#)  
`\v@true` ..... [z81](#), [z83](#)  
`\vadjust` ..... [i37](#),  
[i59](#), [i71](#), [i83](#), [i287](#), [i303](#), [G201](#), [G223](#)  
`\valign` ..... [l1582](#)  
`\value` ..... [l155](#), [m14](#), [l9](#)  
`\varbigtriangledown` ..... [t331](#)  
`\varbigtriangleup` ..... [t332](#)
- `\varepsilon` ..... [j15](#), [t261](#)  
`\varphi` ..... [t266](#)  
`\varpi` ..... [t263](#)  
`\varrho` ..... [t264](#)  
`\varsigma` ..... [t265](#)  
`\vartheta` ..... [t262](#)  
`\vbadness` ..... [b306](#), [K2206](#)  
`\vdash` ..... [t369](#)  
`\vdots` ..... [t471](#)  
`\vec` ..... [t485](#)  
`\vector` ..... [g219](#), [D113](#), [D435](#), [D452](#)  
`\vee` ..... [t335](#), [t336](#)  
`\verb` ..... [y288](#), [y314](#), [y327](#), [y329](#)  
`\verb@balance@group` .....  
[y287](#), [y289](#), [y313](#), [y315](#), [y321](#), [y322](#)  
`\verb@egroup` .....  
[y287](#), [y290](#), [y313](#), [y316](#), [y322](#), [y326](#)  
`\verb@eol@error` .... [y323](#), [y335](#), [y345](#)  
`\verbatim` ..... [y260](#)  
`verbatim*` (environment) ..... [y294](#)  
`\verbatim@font` .....  
[y233](#), [y254](#), [y262](#), [y336](#), [y346](#)  
`\verbatim@nolig@list` .... [y351](#), [y357](#)  
`\verbvisiblespace` .....  
[y266](#), [y268](#), [y275](#), [y279](#), [y301](#), [y306](#)  
`\version@elt` [r18](#), [r31](#), [r32](#), [r256](#), [r257](#),  
[r306](#), [r326](#), [r417](#), [r455](#), [r547](#), [r1040](#)  
`\version@list` ..... [r16](#),  
[r21](#), [r32](#), [r249](#), [r257](#), [r311](#), [r332](#),  
[r351](#), [r422](#), [r467](#), [r497](#), [r552](#), [r1053](#)  
`\Vert` ..... [t532](#), [t534](#)  
`\vert` ..... [t537](#)  
`\vfil` ..... [b400](#),  
[l1583](#), [l1586](#), [D275](#), [D318](#), [K175](#),  
[K194](#), [K412](#), [K459](#), [K627](#), [K686](#)  
`\vfilneg` ..... [b400](#)  
`\vfuzz` ..... [b329](#), [J61](#), [J68](#)  
`\vgl@` ..... [b390](#), [b391](#)  
`\vglue` ..... [b390](#)  
`\vline` ..... [C342](#)  
`\voidb@x` ..... [b298](#), [b421](#), [n18](#)  
`\vphantom` ..... [l491](#), [l507](#), [z75](#)  
`\vrule` ..... [b394](#), [i352](#), [l290](#), [l292](#),  
[l496](#), [l512](#), [p144](#), [t519](#), [t520](#),  
[t522](#), [t523](#), [B120](#), [B122](#), [B173](#),  
[B180](#), [B357](#), [B401](#), [C174](#), [C207](#),  
[C323](#), [C342](#), [D107](#), [D157](#), [D160](#),  
[D176](#), [D183](#), [D198](#), [D205](#), [D274](#),  
[D318](#), [D402](#), [K1851](#), [K2226](#), [K2259](#)  
`\vspace` ..... [i280](#), [i310](#), [i311](#), [i312](#)  
`\vsplit` ..... [K382](#), [K429](#), [K2208](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfsscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=lthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx



- W**
- `\warn@rel@i` ..... [q5](#), [q25](#),  
[q29](#), [q81](#), [q85](#), [q90](#), [q95](#), [q119](#), [q140](#)
  - `\wedge` ..... [t333](#), [t334](#)
  - `\whatsit` ..... [N185](#)
  - `\widehat` ..... [t488](#)
  - `\widetilde` ..... [t487](#)
  - `\widowpenalties` ..... [b106](#)
  - `\widowpenalty` ..... [b313](#), [o539](#)
  - `\width` ..... [B30](#)
  - `\wlog` ..... [a100](#), [b40](#),  
[b145](#), [b230](#), [b243](#), [b273](#), [b288](#),  
[L155](#), [N6](#), [N7](#), [N8](#), [N52](#), [O46](#), [O539](#)
  - `\wp` ..... [t282](#)
  - `\wr` ..... [t347](#)
  - `\wrong@fontshape` ..... [o309](#), [o387](#)
- X**
- `\x` ..... [o266](#), [o267](#)
  - `\x@protect` ... [d205](#), [d216](#), [d264](#), [d291](#)
  - `\xe@alloc@` ..... [O42](#), [O52](#)
  - `\xe@alloc@intercharclass` ..... [O21](#)
  - `\xe@ch@ck` ..... [O43](#), [O47](#)
  - `\XeTeXcharclass` ..... [o514](#), [O25](#),  
[O33](#), [O40](#), [O53](#), [O59](#), [O68](#), [O75](#)
  - `\XeTeXcharclassCL` ..... [O106](#)
  - `\XeTeXcharclassCM` ..... [O110](#)
  - `\XeTeXcharclassEX` ..... [O107](#)
  - `\XeTeXcharclassID` ..... [O104](#)
  - `\XeTeXcharclassIS` ..... [O108](#)
  - `\XeTeXcharclassNS` ..... [O109](#)
  - `\XeTeXcharclassOP` ..... [O105](#)
  - `\XeTeXcharglyph` ..... [1991](#)
  - `\XeTeXdashbreakstate` ..... [O204](#)
  - `\XeTeXglyph` ..... [1991](#)
  - `\XeTeXintercharclasses` . [O100](#), [O133](#)
  - `\XeTeXinterchartoks` . [O101](#), [O115](#),  
[O116](#), [O117](#), [O118](#), [O119](#), [O120](#),  
[O121](#), [O122](#), [O123](#), [O124](#), [O125](#),  
[O126](#), [O127](#), [O128](#), [O129](#), [O134](#),  
[O139](#), [O140](#), [O141](#), [O142](#), [O143](#),  
[O144](#), [O145](#), [O146](#), [O147](#), [O148](#),  
[O149](#), [O150](#), [O151](#), [O152](#), [O153](#)
  - `\XeTeXmathcode` ..... [O94](#), [O431](#)
  - `\XeTeXrevision` ..... [O27](#)
  - `\XeTeXuseglyphmetrics` .. [O201](#), [O203](#)
  - `\XeTeXversion` ..... [O27](#)
  - `\Xi` ..... [t271](#)
  - `\xi` ..... [t251](#)
  - `\xtxHanGlue` ..... [O113](#),  
[O137](#), [O145](#), [O146](#), [O147](#), [O148](#),  
[O149](#), [O150](#), [O151](#), [O152](#), [O153](#)
  - `\xtxHanSpace` .. [O114](#), [O138](#), [O139](#),  
[O140](#), [O141](#), [O142](#), [O143](#), [O144](#)
- Y**
- `\year` ..... [a185](#), [c11](#), [c14](#), [L631](#), [L721](#)
  - `\yxdim` ..... [D354](#)
- Z**
- `\Z` ..... [O185](#), [O427](#), [O448](#)
  - `\z` ..... [O176](#), [O428](#), [O439](#)
  - `\z@` ..... [b298](#)
  - `\z@skip` ..... [b298](#)
  - `\zap@space` .....  
[k152](#), [k169](#), [L108](#), [L175](#), [L257](#),  
[L341](#), [L362](#), [L379](#), [L390](#), [L407](#), [I29](#)
  - `\zeta` ..... [t243](#)

**File Key:** a=ltldirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltdefns.dtx,  
e=ltalloc.dtx, f=ltcntrl.dtx, g=lterror.dtx, h=ltpar.dtx, i=ltspace.dtx,  
j=ltlogos.dtx, k=ltfiles.dtx, l=ltoutenc.dtx, m=ltcounts.dtx, n=ltlength.dtx,  
o=ltfssbas.dtx, p=ltfssstrc.dtx, q=ltfssscmp.dtx, r=ltfssdcl.dtx, s=ltfssini.dtx,  
t=fontdef.dtx, u=preload.dtx, v=ltfntcmd.dtx, w=ltpageno.dtx, x=ltxref.dtx,  
y=ltmiscen.dtx, z=ltmath.dtx, A=ltlists.dtx, B=ltboxes.dtx, C=lttab.dtx,  
D=lt pictur.dtx, E=ltthm.dtx, F=ltsect.dtx, G=ltfloat.dtx, H=ltidxglo.dtx,  
I=ltbibl.dtx, J=ltpage.dtx, K=ltoutput.dtx, L=ltclass.dtx, M=ltthyphen.dtx,  
N=ltluatex.dtx, O=ltfinal.dtx