

The `telprint` package

Heiko Oberdiek*

2016/05/16 v1.11

Abstract

Package `telprint` provides `\telprint` for formatting German phone numbers.

Contents

1	Documentation	2
1.1	Introduction	2
1.2	Short overview in English	2
1.2.1	Configuration	2
1.3	Documentation in German	2
2	Implementation	3
2.1	Reload check and package identification	3
2.2	Catcodes	5
2.3	Package macros	5
3	Test	8
3.1	Catcode checks for loading	8
4	Installation	9
4.1	Download	9
4.2	Bundle installation	10
4.3	Package installation	10
4.4	Refresh file name databases	10
4.5	Some details for the interested	10
5	History	11
	[1996/11/28 v1.0]	11
	[1997/09/16 v1.1]	11
	[1997/10/16 v1.2]	11
	[1997/12/09 v1.3]	11
	[2004/11/02 v1.4]	11
	[2005/09/30 v1.5]	11
	[2006/02/12 v1.6]	12
	[2006/08/26 v1.7]	12
	[2007/04/11 v1.8]	12
	[2007/09/09 v1.9]	12
	[2008/08/11 v1.10]	12
	[2016/05/16 v1.11]	12

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 Documentation

1.1 Introduction

This is a very old package that I have written to format phone numbers. It follows German conventions and the documentation is mainly in German.

1.2 Short overview in English

L^AT_EX:

```
\usepackage{telprint}
\telprint{123/456-789}
```

plain T_EX:

```
\input telprint.sty
\telprint{123/456-789}
```

\telprint **\telprint{...}** formats the explicitly given number. Digits, spaces and some special characters ('+', '/', '-', '(', ')', '~', ' ') are supported. Numbers are divided into groups of two digits from the right. Examples:

```
\telprint{0761/12345}      ==> 07\,61/1\,23\,45
\telprint{01234/567-89}    ==> 0\,12\,34/5\,67\leavevmode\hbox{-
}89
\telprint{+49 (6221) 297} ==> +49~(62\,21)~2\,97
```

1.2.1 Configuration

The output of the symbols can be configured by **\telhyphen**, **\telslash**, **\telleftparen**, **\telrightparen**, **\telplus**, **\teltilde**. Example:

```
\telslash{\,/\/,}\ \telprint{12/34} ==> 12\,/\/,34
```

\telspace **\telspace** configures the space between digit groups.
\telnumber **\telnumber** only formats a number in digit groups; special characters are not recognized.

1.3 Documentation in German

\telprint • **telprint#1**
Der eigentliche Anwenderbefehl zur formatierten Ausgabe von Telefonnummern. Diese dürfen dabei nur als Zahlen angegeben werden(, da sie tokenweise analysiert werden). Als Trenn- oder Sonderzeichen werden unterstützt: '+', '/', '-', '(', ')', '~', ' ' Einfache Leerzeichen werden erkannt und durch Tilden ersetzt, um Trennungen in der Telefonnummer zu verhindern. (Man beachte aus gleichem Grunde die **\hbox** bei '-'). Beispiele:

```
\telprint{0761/12345}      ==> 07\,61/1\,23\,45
\telprint{01234/567-89}    ==> 0\,12\,34/5\,67\leavevmode\hbox{-
}89
\telprint{+49 (6221) 297} ==> +49~(62\,21)~2\,97
```

Der Rest enthält eher Technisches:

<code>\telspace</code>	<ul style="list-style-type: none"> • <code>\telspace#1</code> Mit diesem Befehl wird der Abstand zwischen den Zifferngruppen angegeben (Default: \,). (Durch <code>\telspace{}</code> kann dieser zusätzliche Abstand abgestellt werden.)
<code>\telhyphen</code>	<ul style="list-style-type: none"> • <code>\telhyphen#1</code> Dieser Befehl gibt die Art des Bindestriches, wie er ausgegeben werden soll. In der Eingabe darf jedoch nur der einfache Bindestrich stehen: <code>\telprint{123-45}</code>, jedoch NIE <code>\telprint{123--45}</code>! Kopka-Bindestrich-Fans geben an: <code>\telhyphen{\leavevmode\hbox{--}}</code>
<code>\telslash</code> <code>\telleftparen</code> <code>\telrightparen</code> <code>\telplus</code> <code>\teltilde</code> <code>\telnumber</code>	<ul style="list-style-type: none"> • <code>\telslash#1, \telleftparen#1, \telrightparen#1, \telplus#1, \teltilde</code> Diese Befehle konfigurieren die Zeichen '/', '(', ')', '+' und '~. Sie funktionieren analog zu <code>\telhyphen</code>. • <code>\telnumber#1</code> Richtung interner Befehl: Er dient dazu, eine Zifferngruppe in Zweiergruppen auszugeben. Die einzelnen Zahlen werden im Tokenregister <code>\TELtoks</code> gespeichert. Abwechselnd werden dabei zwischen zwei Token (Zahlen) <code>\TELx</code> bzw. <code>\TELy</code> eingefügt, abhängig von dem wechselnden Wert von <code>\TELswitch</code>. Zum Schluss kann dann einfach festgestellt werden ob die Nummer nun eine geradzahlige oder ungeradzahlige Zahl von Ziffern aufwies. Dem entsprechend wird <code>\TELx</code> mit dem Zusatzabstand belegt und <code>\TELy</code> leer definiert oder umgekehrt.) • <code>\TEL...</code> interne Befehle, Technisches: <code>\TELsplit</code> dient zur Aufteilung einer zusammengesetzten Telefonnummer (Vorwahl, Hauptnummer, Nebenstelle). In dieser Implementation werden als Trennzeichen nur '/' und '-' erkannt. Die einzelnen Bestandteile wie Vorwahl werden dann dem Befehl <code>\telnumber</code> zur Formatierung uebergeben. • Die Erkennung von einfachen Leerzeichen ist um einiges schwieriger: Die Tokentrennung ueber Parameter <code>#1#2</code> funktioniert nicht für einfache Leerzeichen, da TeX sie <i>niemals</i> als eigenständige Argumente behandelt! (The TeXbook, Chapter 20, p. 201) (Anmerkung am Rande: Deshalb funktionieren die entsprechenden Tokenmakros auf S. 149 des Buches „Einführung in TeX“ von N. Schwarz (3. Aufl.) nicht, wenn im Tokenregister als erstes ein einfaches Leerzeichen steht!)

2 Implementation

```
1 \<*package>
```

2.1 Reload check and package identification

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^~M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
```

```

12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@telprint.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17 \def\empty{}%
18 \ifx\x\empty % LaTeX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
25 \else
26 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27 \fi
28 \x{telprint}{The package is already loaded}%
29 \aftergroup\endinput
30 \fi
31 \fi
32 \endgroup%

```

Package identification:

```

33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^^M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51 \def\x#1#2#3[#4]{\endgroup
52 \immediate\write-1{Package: #3 #4}%
53 \xdef#1{#4}%
54 }%
55 \else
56 \def\x#1#2[#3]{\endgroup
57 #2[{#3}]%
58 \ifx#1\@undefined
59 \xdef#1{#3}%
60 \fi
61 \ifx#1\relax
62 \xdef#1{#3}%
63 \fi
64 }%
65 \fi
66 \expandafter\x\csname ver@telprint.sty\endcsname
67 \ProvidesPackage{telprint}%
68 [2016/05/16 v1.11 Format German phone numbers (H0)]%

```

2.2 Catcodes

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^^M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76   \expandafter\edef\csname TELAtEnd\endcsname{%
77     \endlinechar=\the\endlinechar\relax
78     \catcode13=\the\catcode13\relax
79     \catcode32=\the\catcode32\relax
80     \catcode35=\the\catcode35\relax
81     \catcode61=\the\catcode61\relax
82     \catcode64=\the\catcode64\relax
83     \catcode123=\the\catcode123\relax
84     \catcode125=\the\catcode125\relax
85   }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95   \edef\TELAtEnd{%
96     \TELAtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{33}{12}% !
102 \TMP@EnsureCode{36}{3}% $
103 \TMP@EnsureCode{40}{12}% (
104 \TMP@EnsureCode{41}{12}% )
105 \TMP@EnsureCode{42}{12}% *
106 \TMP@EnsureCode{43}{12}% +
107 \TMP@EnsureCode{44}{12}% ,
108 \TMP@EnsureCode{45}{12}% -
109 \TMP@EnsureCode{46}{12}% .
110 \TMP@EnsureCode{47}{12}% /
111 \TMP@EnsureCode{91}{12}% [
112 \TMP@EnsureCode{93}{12}% ]
113 \TMP@EnsureCode{126}{13}% ~ (active)
114 \edef\TELAtEnd{\TELAtEnd\noexpand\endinput}

```

2.3 Package macros

```

115 \ifx\DeclareRobustCommand\UnDeFiNeD
116   \def\DeclareRobustCommand*#1[1]{\def#1##1}%
117   \def\TELreset{\let\DeclareRobustCommand=\UnDeFiNeD}%
118   \input infwarerr.sty\relax
119   \@PackageInfo{telprint}{%
120     Macros are not robust!%
121   }%
122 \else

```

```

123 \let\TELreset=\relax
124 \fi

\telspace
125 \DeclareRobustCommand*\telspace[1]{\def\TELspace{#1}}
126 \telspace{ }$ \, $ { }

\telhyphen
127 \DeclareRobustCommand*\telhyphen[1]{\def\TELhyphen{#1}}
128 \telhyphen{\leavevmode\hbox{-}}% \hbox zur Verhinderung der Trennung

\telslash
129 \DeclareRobustCommand*\telslash[1]{\def\TELslash{#1}}
130 \telslash{/}%

\telleftparen
131 \DeclareRobustCommand*\telleftparen[1]{\def\TELleftparen{#1}}
132 \telleftparen{(}%

\telrightparen
133 \DeclareRobustCommand*\telrightparen[1]{\def\TELrightparen{#1}}
134 \telrightparen{)}%

\telplus
135 \DeclareRobustCommand*\telplus[1]{\def\TELplus{#1}}
136 \telplus{+}%

\teltilde
137 \DeclareRobustCommand*\teltilde[1]{\def\TELtilde{#1}}
138 \teltilde{~}%

\TELtoks
139 \newtoks\TELtoks

\TELnumber
140 \def\TELnumber#1#2\TELnumberEND{%
141 \begingroup
142 \def\0{#2}%
143 \expandafter\endgroup
144 \ifx\0\empty
145 \TELtoks=\expandafter{\the\TELtoks#1}%
146 \ifnum\TELswitch=0 %
147 \def\TELx{\TELspace}\def\TELy{ }%
148 \else
149 \def\TELx{ }\def\TELy{\TELspace}%
150 \fi
151 \the\TELtoks
152 \else
153 \ifnum\TELswitch=0 %
154 \TELtoks=\expandafter{\the\TELtoks#1\TELx}%
155 \def\TELswitch{1}%
156 \else
157 \TELtoks=\expandafter{\the\TELtoks#1\TELy}%
158 \def\TELswitch{0}%
159 \fi
160 \TELnumber#2\TELnumberEND
161 \fi
162 }

```

```

\telnumber
163 \DeclareRobustCommand*\telnumber}[1]{%
164   \TELtoks={}%
165   \def\TELswitch{0}%
166   \TELnumber#1{}\TELnumberEND
167 }

\TELsplit
168 \def\TELsplit{\futurelet\TELfuture\TELdosplit}

\TELdosplit
169 \def\TELdosplit#1#2\TELsplitEND
170 {%
171   \def\TELsp{ }%
172   \expandafter\ifx\TELsp\TELfuture
173     \let\TELfuture=\relax
174     \expandafter\telnumber\expandafter{\the\TELtoks}~%
175     \telprint{#1#2}% Das Leerzeichen kann nicht #1 sein!
176   \else
177     \def\TELfirst{#1}%
178     \ifx\TELfirst\empty
179       \expandafter\telnumber\expandafter{\the\TELtoks}%
180       \TELtoks={}%
181     \else\if-\TELfirst
182       \expandafter\telnumber\expandafter{\the\TELtoks}\TELhyphen
183       \telprint{#2}%
184     \else\if/\TELfirst
185       \expandafter\telnumber\expandafter{\the\TELtoks}\TELslash
186       \telprint{#2}%
187     \else\if\TELfirst
188       \expandafter\telnumber\expandafter{\the\TELtoks}\TELleftparen
189       \telprint{#2}%
190     \else\if)\TELfirst
191       \expandafter\telnumber\expandafter{\the\TELtoks}\TELrightparen
192       \telprint{#2}%
193     \else\if+\TELfirst
194       \expandafter\telnumber\expandafter{\the\TELtoks}\TELplus
195       \telprint{#2}%
196     \else\def\TELtemp{~}\ifx\TELtemp\TELfirst
197       \expandafter\telnumber\expandafter{\the\TELtoks}\TELtilde
198       \telprint{#2}%
199     \else
200       \TELtoks=\expandafter{\the\TELtoks#1}%
201       \TELsplit#2{}\TELsplitEND
202       \fi\fi\fi\fi\fi\fi\fi
203   \fi
204 }

\telprint
205 \DeclareRobustCommand*\telprint}[1]{%
206   \TELtoks={}%
207   \TELsplit#1{}\TELsplitEND
208 }

209 \TELreset\let\TELreset=\UnDeFiNeD

210 \TELatEnd%
211 \endpackage

```

3 Test

3.1 Catcode checks for loading

```
212 \test1)
213 \catcode\{=1 %
214 \catcode\}=2 %
215 \catcode\#=6 %
216 \catcode\@=11 %
217 \expandafter\ifx\csname count@\endcsname\relax
218   \countdef\count@=255 %
219 \fi
220 \expandafter\ifx\csname @gobble\endcsname\relax
221   \long\def@gobble#1{%
222 \fi
223 \expandafter\ifx\csname @firstofone\endcsname\relax
224   \long\def@firstofone#1{#1}%
225 \fi
226 \expandafter\ifx\csname loop\endcsname\relax
227   \expandafter@firstofone
228 \else
229   \expandafter@gobble
230 \fi
231 {%
232   \def\loop#1\repeat{%
233     \def\body{#1}%
234     \iterate
235   }%
236   \def\iterate{%
237     \body
238     \let\next\iterate
239   \else
240     \let\next\relax
241   \fi
242   \next
243 }%
244 \let\repeat=\fi
245 }%
246 \def\RestoreCatcodes{}
247 \count@=0 %
248 \loop
249   \edef\RestoreCatcodes{%
250     \RestoreCatcodes
251     \catcode\the\count@=\the\catcode\count@\relax
252   }%
253 \ifnum\count@<255 %
254   \advance\count@ 1 %
255 \repeat
256
257 \def\RangeCatcodeInvalid#1#2{%
258   \count@=#1\relax
259   \loop
260     \catcode\count@=15 %
261     \ifnum\count@<#2\relax
262       \advance\count@ 1 %
263     \repeat
264 }
265 \def\RangeCatcodeCheck#1#2#3{%
```



```

266 \count@=#1\relax
267 \loop
268 \ifnum#3=\catcode\count@
269 \else
270 \errmessage{%
271 Character \the\count@\space
272 with wrong catcode \the\catcode\count@\space
273 instead of \number#3%
274 }%
275 \fi
276 \ifnum\count@<#2\relax
277 \advance\count@ 1 %
278 \repeat
279 }
280 \def\space{ }
281 \expandafter\ifx\csname LoadCommand\endcsname\relax
282 \def\LoadCommand{\input telprint.sty\relax}%
283 \fi
284 \def\Test{%
285 \RangeCatcodeInvalid{0}{47}%
286 \RangeCatcodeInvalid{58}{64}%
287 \RangeCatcodeInvalid{91}{96}%
288 \RangeCatcodeInvalid{123}{255}%
289 \catcode`\@=12 %
290 \catcode`\=0 %
291 \catcode`\%=14 %
292 \LoadCommand
293 \RangeCatcodeCheck{0}{36}{15}%
294 \RangeCatcodeCheck{37}{37}{14}%
295 \RangeCatcodeCheck{38}{47}{15}%
296 \RangeCatcodeCheck{48}{57}{12}%
297 \RangeCatcodeCheck{58}{63}{15}%
298 \RangeCatcodeCheck{64}{64}{12}%
299 \RangeCatcodeCheck{65}{90}{11}%
300 \RangeCatcodeCheck{91}{91}{15}%
301 \RangeCatcodeCheck{92}{92}{0}%
302 \RangeCatcodeCheck{93}{96}{15}%
303 \RangeCatcodeCheck{97}{122}{11}%
304 \RangeCatcodeCheck{123}{255}{15}%
305 \RestoreCatcodes
306 }
307 \Test
308 \csname @@end\endcsname
309 \end
310 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/telprint.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/telprint.pdf Documentation.

¹CTAN:pkg/telprint

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps.

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex telprint.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>telprint.sty</code>	→ <code>tex/generic/oberdiek/telprint.sty</code>
<code>telprint.pdf</code>	→ <code>doc/latex/oberdiek/telprint.pdf</code>
<code>test/telprint-test1.tex</code>	→ <code>doc/latex/oberdiek/test/telprint-test1.tex</code>
<code>telprint.dtx</code>	→ <code>source/latex/oberdiek/telprint.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your T_EX distribution (teT_EX, miK_TE_X, ...) relies on file name databases, you must refresh these. For example, teT_EX users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{telprint.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex telprint.dtx
makeindex -s gind.ist telprint.idx
pdflatex telprint.dtx
makeindex -s gind.ist telprint.idx
pdflatex telprint.dtx
```

5 History

[1996/11/28 v1.0]

- Erste lauffähige Version.
- Nur ‘-’ und ‘/’ als zulässige Sonderzeichen.

[1997/09/16 v1.1]

- Dokumentation und Kommentare (Posting in de.comp.text.tex).
- Erweiterung um Sonderzeichen ‘(,)’, ‘+’, ‘~’ und ‘.’
- Trennungsverhinderung am ‘hyphen’.

[1997/10/16 v1.2]

- Schutz vor wiederholtem Einlesen.
- Unter L^AT_EX 2_ε Nutzung des `\DeclareRobustCommand`-Features.

[1997/12/09 v1.3]

- Temporäre Variable eingespart.
- Posted in newsgroup `de.comp.text.tex`:
“Re: Generisches Markup für Telefonnummern?”²

[2004/11/02 v1.4]

- Fehler in der Dokumentation korrigiert.

[2005/09/30 v1.5]

- Konfigurierbare Symbole: ‘/’, ‘(,)’, ‘+’ und ‘~’.

²Url: <https://groups.google.com/group/de.comp.text.tex/msg/86b3a86140007309>

[2006/02/12 v1.6]

- LPPL 1.3.
- Kurze Übersicht in Englisch.
- CTAN.

[2006/08/26 v1.7]

- New DTX framework.

[2007/04/11 v1.8]

- Line ends sanitized.

[2007/09/09 v1.9]

- Catcode section added.
- Missing docstrip tag added.

[2008/08/11 v1.10]

- Code is not changed.
- URLs updated.

[2016/05/16 v1.11]

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols		B	
<code>\#</code>	215	<code>\body</code>	233, 237
<code>\%</code>	291		
<code>\,</code>	126		
<code>\@</code>	216, 289		
<code>\@PackageInfo</code>	119		
<code>\@firstofone</code>	224, 227		
<code>\@gobble</code>	221, 229		
<code>\@undefined</code>	58		
<code>\%</code>	290		
<code>\{</code>	213		
<code>\}</code>	214		
Numbers		C	
<code>\0</code>	142, 144	<code>\catcode</code>	2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 69, 70, 72, 73, 74, 78, 79, 80, 81, 82, 83, 84, 87, 88, 90, 91, 92, 93, 97, 99, 213, 214, 215, 216, 251, 260, 268, 272, 289, 290, 291
		<code>\count@</code>	218, 247, 251, 253, 254, 258, 260, 261, 262, 266, 268, 271, 272, 276, 277
		<code>\countdef</code>	218
A		<code>\csname</code>	14, 21, 50, 66, 76, 217, 220, 223, 226, 281, 308
<code>\advance</code>	254, 262, 277		
<code>\aftergroup</code>	29		

D		T	
\DeclareRobustCommand	115, 116, 117, 125, 127, 129, 131, 133, 135, 137, 163, 205	\TELAtEnd	95, 96, 114, 210
E		\TEldosplit	168, 169
\empty	17, 18, 144, 178	\TELfirst	177, 178, 181, 184, 187, 190, 193, 196
\end	309	\TELfuture	168, 172, 173
\endcsname	14, 21, 50, 66, 76, 217, 220, 223, 226, 281, 308	\TELhyphen	127, 182
\endinput	29, 114	\telhyphen	3, 127
\endlinechar	4, 35, 71, 77, 89	\TELleftparen	131, 188
\errmessage	270	\telleftparen	3, 131
F		\TELnumber	140, 166
\futurelet	168	\telnumber	2, 3, 163, 174, 179, 182, 185, 188, 191, 194, 197
H		\TELnumberEND	140, 160, 166
\hbox	128	\TELplus	135, 194
I		\telplus	3, 135
\if	181, 184, 187, 190, 193	\telprint	2, 2, 175, 183, 186, 189, 192, 195, 198, 205
\ifnum	146, 153, 253, 261, 268, 276	\TELreset	117, 123, 209
\ifx	15, 18, 21, 50, 58, 61, 115, 144, 172, 178, 196, 217, 220, 223, 226, 281	\TELrightparen	133, 191
\immediate	23, 52	\telrightparen	3, 133
\input	118, 282	\TELslash	129, 185
\iterate	234, 236, 238	\telslash	3, 129
L		\TELsp	171, 172
\leavevmode	128	\TELspace	125, 147, 149
\LoadCommand	282, 292	\telspace	2, 3, 125
\loop	232, 248, 259, 267	\TELsplit	168, 201, 207
N		\TELsplitEND	169, 201, 207
\newtoks	139	\TELswitch	146, 153, 155, 158, 165
\next	238, 240, 242	\TELtemp	196
\number	273	\TELtilde	137, 197
P		\teltilde	3, 137
\PackageInfo	26	\TELToks	139, 145, 151, 154, 157, 164, 174, 179, 180, 182, 185, 188, 191, 194, 197, 200, 206
\ProvidesPackage	19, 67	\TELx	147, 149, 154
R		\TELy	147, 149, 157
\RangeCatcodeCheck	265, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304	\Test	284, 307
\RangeCatcodeInvalid	257, 285, 286, 287, 288	\the	77, 78, 79, 80, 81, 82, 83, 84, 97, 145, 151, 154, 157, 174, 179, 182, 185, 188, 191, 194, 197, 200, 251, 271, 272
\repeat	232, 244, 255, 263, 278	\TMP@EnsureCode	94, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113
\RestoreCatcodes	246, 249, 250, 305	U	
S		\UnDeFiNeD	115, 117, 209
\space	271, 272, 280	W	
X		\write	23, 52
\x	14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87	X	