

The flags package

Heiko Oberdiek*

2016/05/16 v0.5

Abstract

Package `flags` allows the setting and clearing of flags in bit fields and converts the bit field into a decimal number. Currently the bit field is limited to 31 bits.

Contents

1	Documentation	1
1.1	User interface	2
1.2	Requirements	2
1.3	ToDo	2
2	Implementation	3
3	Installation	6
3.1	Download	6
3.2	Bundle installation	6
3.3	Package installation	6
3.4	Refresh file name databases	6
3.5	Some details for the interested	7
4	History	7
	[2007/02/18 v0.1]	7
	[2007/03/07 v0.2]	7
	[2007/03/31 v0.3]	7
	[2007/09/30 v0.4]	7
	[2016/05/16 v0.5]	7

1 Documentation

A new powerful package `bitset` is written by me and supersedes this package:

- The bit range is not restricted to 31 bits, only index numbers are objected to T_EX's number limit.
- Many more operations are available.
- No dependency of ε -T_EX.

Therefore I consider this package as obsolete and have stopped the development of this package.

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1.1 User interface

Flag positions are one-based, thus the flag position must be a positive integer.
Currently supported range: 1..31

`\resetflags {⟨fname⟩}`

The bit field $\langle fname \rangle$ is cleared. Currently is also used for initialization, because a `\newflags` macro is not implemented.

`\setflag {⟨fname⟩} {⟨position⟩}`

The flag at bit position $\langle position \rangle$ is set in the bit field $\langle fname \rangle$.

`\clearflag {⟨fname⟩} {⟨position⟩}`

The flag at bit position $\langle position \rangle$ is cleared in the bit field $\langle fname \rangle$.

`\printflags {⟨fname⟩}`

The bit field $\langle fname \rangle$ is converted to a decimal number. The macro is expandible.

`\extractflag {⟨fname⟩} {⟨position⟩}`

Extracts the flag setting at bit position $\langle position \rangle$. `\extractflag` expands to 1 if the flag is set and 0 otherwise.

`\queryflag {⟨fname⟩} {⟨position⟩} {⟨set part⟩} {⟨clear part⟩}`

It is a wrapper for `\extractflag`. $\langle set part \rangle$ is called if `\extractflag` returns 1. Otherwise $\langle clear part \rangle$ is executed.

Example. See package `bookmark`. It uses package `flags` for its font style options.

1.2 Requirements

- ε -TeX (`\numexpr`)

1.3 ToDo

- Named positions.
- Setting positions by a key-value interface.
- Support for more than 31 bits while maintaining expandibility of `\printflags`.
- Eventually `\newflags`, `\newflagstype`.

2 Implementation

```

1 \*package
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{flags}%
4 [2016/05/16 v0.5 Setting/clearing of flags in bit fields (HO)]%

5 \begingroup\expandafter\expandafter\expandafter\endgroup
6 \expandafter\ifx\csname numexpr\endcsname\relax
7   \PackageError{flags}{%
8     Missing e-TeX, package loading aborted%
9   }{%
10    This packages makes heavy use of \string\numexpr.%
11  }%
12 \expandafter\endinput
13 \fi

\resetflags

14 \newcommand*\resetflags[1]{%
15   \expandafter\let\csname flags@#1\endcsname\empty
16 }

\printflags Macro \printflags converts the bit field into a decimal number.

17 \newcommand*\printflags[1]{%
18   \expandafter\@printflags\csname flags@#1\endcsname
19 }
20 \def\@printflags#1{%
21   \expandafter\@firstofone\expandafter{%
22     \number\numexpr
23     \ifx#1\empty
24       0%
25     \else
26       \expandafter\@printflags#1%
27     \fi
28   }%
29 }
30 \def\@@printflags#1#2\fi{%
31   \fi
32   #1%
33   \ifx\#2\%
34   \else
35     +2*\numexpr\expandafter\@printflags#2%
36   \fi
37 }

\setflag

38 \newcommand*\setflag[2]{%
39   \ifnum#2>\z@
40     \expandafter\setflag\csname flags@#1\expandafter\endcsname
41     \expandafter{\romannumeral\number\numexpr#2-1\relax000}%
42   \else
43     \PackageError{flags}{Position must be a positive number}\@ehc
44   \fi
45 }
46 \def\@setflag#1#2{%
47   \ifx#1\relax
48     \let#1\empty
49   \fi
50   \edef#1{%

```

```

51 \expandafter\@@setflag\expandafter{#1}{#2}%
52 }%
53 }
54 \def\@@setflag#1#2{%
55 \ifx\#1\%
56 \FLAGS@zero#2\relax
57 1%
58 \else
59 \ifx\#2\%
60 1\@gobble#1%
61 \else
62 \@@setflag#1|#2%
63 \fi
64 \fi
65 }
66 \def\@@@setflag#1#2|#3#4\fi\fi{%
67 \fi\fi
68 #1%
69 \@@setflag{#2}{#4}%
70 }

\clearflag

71 \newcommand*\clearflag[2]{%
72 \ifnum#2>\z@
73 \expandafter\clearflag\csname flags@#1\expandafter\endcsname
74 \expandafter{\romannumeral\number\numexpr#2-1\relax000}%
75 \else
76 \PackageError{flags}{Position must be a positive number}\@ehc
77 \fi
78 }
79 \def\clearflag#1#2{%
80 \ifx#1\relax
81 \let#1\@empty
82 \fi
83 \edef#1{%
84 \expandafter\clearflag\expandafter{#1}{#2}%
85 }%
86 }
87 \def\@@clearflag#1#2{%
88 \ifx\#1\%
89 \else
90 \ifx\#2\%
91 0\@gobble#1%
92 \else
93 \@@clearflag#1|#2%
94 \fi
95 \fi
96 }
97 \def\@@@clearflag#1#2|#3#4\fi\fi{%
98 \fi\fi
99 #1%
100 \@@clearflag{#2}{#4}%
101 }

102 \def\FLAGS@zero#1{%
103 \ifx#1\relax
104 \else
105 0%
106 \expandafter\FLAGS@zero

```

```

107 \fi
108 }

\queryflag
109 \newcommand*{\queryflag}[2]{%
110 \ifnum\extractflag{#1}{#2}=\@ne
111 \expandafter\@firstoftwo
112 \else
113 \expandafter\@secondoftwo
114 \fi
115 }

\extractflag
116 \newcommand*{\extractflag}[1]{%
117 \expandafter\@extractflag\csname flags@#1\endcsname
118 }
119 \def\@extractflag#1#2{%
120 \ifx#1\@undefined
121 0%
122 \else
123 \ifx#1\relax
124 0%
125 \else
126 \ifx#1\@empty
127 0%
128 \else
129 \expandafter\expandafter\expandafter\@@extractflag
130 \expandafter\expandafter\expandafter{%
131 \expandafter#1\expandafter
132 }\expandafter{%
133 \romannumeral\number\numexpr#2-1\relax000%
134 }%
135 \fi
136 \fi
137 \fi
138 }
139 \def\@@extractflag#1#2{%
140 \ifx\\#1\\%
141 0%
142 \else
143 \ifx\\#2\\%
144 \@car#1\@nil
145 \else
146 \@@@extractflag#1|#2%
147 \fi
148 \fi
149 }
150 \def\@@@extractflag#1#2|#3#4\fi\fi{%
151 \fi\fi
152 \@@extractflag{#2}{#4}%
153 }

154 \</package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/flags.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/flags.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps.

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex flags.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
flags.sty → tex/latex/oberdiek/flags.sty
flags.pdf → doc/latex/oberdiek/flags.pdf
flags.dtx → source/latex/oberdiek/flags.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your T_EX distribution (teT_EX, miK_TE_X, ...) relies on file name databases, you must refresh these. For example, teT_EX users run `texhash` or `mktextlsr`.

¹[CTAN:pkg/flags](#)

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{flags.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex flags.dtx
makeindex -s gind.ist flags.idx
pdflatex flags.dtx
makeindex -s gind.ist flags.idx
pdflatex flags.dtx
```

4 History

[2007/02/18 v0.1]

- First version.

[2007/03/07 v0.2]

- Raise an error if ϵ -T_EX is not detected.

[2007/03/31 v0.3]

- `\queryflag` and `\extractflag` added.
- Raise an error if position is not positive in case of `\setflag` and `\clearflag`.

[2007/09/30 v0.4]

- Package is deprecated because of new more powerful package `bitset`.

[2016/05/16 v0.5]

- Documentation updates.

5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols		F	
\@@@clearflag	93, 97	\FLAGS@zero	56, 102, 106
\@@@extractflag	146, 150		
\@@@setflag	62, 66	I	
\@clearflag	84, 87, 100	\ifnum	39, 72, 110
\@extractflag	129, 139, 152	\ifx	6, 23, 33, 47, 55, 59, 80,
\@printflags	26, 30, 35		88, 90, 103, 120, 123, 126, 140, 143
\@setflag	51, 54, 69		
\@car	144	N	
\@clearflag	73, 79	\NeedsTeXFormat	2
\@ehc	43, 76	\newcommand	14, 17, 38, 71, 109, 116
\@empty	15, 23, 48, 81, 126	\number	22, 41, 74, 133
\@extractflag	117, 119	\numexpr	10, 22, 35, 41, 74, 133
\@firstofone	21		
\@firstoftwo	111	P	
\@gobble	60, 91	\PackageError	7, 43, 76
\@ne	110	\printflags	2, <u>17</u>
\@nil	144	\ProvidesPackage	3
\@printflags	18, 20		
\@secondoftwo	113	Q	
\@setflag	40, 46	\queryflag	2, <u>109</u>
\@undefined	120		
\@	33, 55, 59, 88, 90, 140, 143	R	
		\resetflags	2, <u>14</u>
C		\romannumeral	41, 74, 133
\clearflag	2, <u>71</u>		
\csname	6, 15, 18, 40, 73, 117	S	
		\setflag	2, <u>38</u>
E			
\endcsname	6, 15, 18, 40, 73, 117	Z	
\endinput	12	\z@	39, 72
\extractflag	2, 110, <u>116</u>		