

The `picture` package

Heiko Oberdiek*

2016/05/16 v1.4

Abstract

There are macro and environment arguments that expect numbers that will internally be multiplied with `\unitlength`. This package extends the syntax of these arguments that `dimens` with calculation support can be added for these arguments.

Contents

1	User interface	2
1.1	Introduction	2
1.2	Options	2
1.3	Example	2
1.4	Supported packages	2
2	Implementation	3
2.1	Identification	3
2.2	Options	3
2.3	Calculation method	3
2.3.1	Method <code>calc</code>	3
2.3.2	Method <code>etex</code>	4
2.3.3	Method <code>plain</code>	4
2.3.4	Help macros	5
2.4	Redefinitions	5
2.4.1	<code>L^AT_EX</code> base macros	6
2.4.2	Package <code>pspicture</code>	6
2.5	Check package loading order	7
3	Installation	7
3.1	Download	7
3.2	Bundle installation	7
3.3	Package installation	8
3.4	Refresh file name databases	8
3.5	Some details for the interested	8
4	History	8
	[2006/08/26 v1.0]	8
	[2007/04/11 v1.1]	9
	[2008/11/26 v1.2]	9
	[2009/10/11 v1.3]	9
	[2016/05/16 v1.4]	9

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 User interface

1.1 Introduction

The environment `picture` and macros such as `\put`, `\line`, `\vector` and other macros have arguments that expect numbers that are used as factor for `\unitlength`. This package redefines such macros and adds code that detects whether such an argument is given as number or as length. In the latter case, the length is used directly without multiplying with `\unitlength`.

1.2 Options

Depending on the available features, also length expressions can be given. Option `calc` loads package `calc`. Then expressions of these package may be used. Otherwise `etex` wraps the length argument inside `\dimexpr...\relax`, if ϵ -TeX is available. Otherwise option `plain` uses plain assignments without calculation support.

The default is `calc` if package `calc` is loaded before package `picture`. If you specify option `calc` the loading of `calc` is ensured. Otherwise package `picture` looks whether `\dimexpr` is available and uses then option `etex` as default. If ϵ -TeX also could not be found, then `plain` is used.

1.3 Example

```
1 \(*example)
2 \documentclass{article}
3
4 \usepackage[calc]{picture}
5
6 \begin{document}
7
8 \setlength{\unitlength}{1pt}
9
10 \begin{picture}(\widthof{Hello World}, 10mm)
11   \put(0, 0){\makebox(0,0)[lb]{Hello World}}%
12   \put(0, \heightof{Hello World} + \fboxsep){%
13     \line(1, 0){\widthof{Hello World}}}%
14   }%
15   \put(\widthof{Hello World}, 10mm){%
16     \line(0, -1){10mm}}%
17   }%
18 \end{picture}
19
20 \end{document}
21 \(*example)
```

1.4 Supported packages

Packages `pspicture` and `pict2e` are supported, but they must be loaded before package `picture`.

New macros can be supported by `\picture@redefine`. The first argument is the macro which contains the arguments in its parameter text that you want to support by package `picture`. The second argument contains the parameter text. Change `#` to `&` for the arguments in question. Examples (already used by package `picture`):

```
\picture@redefine\put{(&1,&2)}
\picture@redefine\line{(#1,#2)&3}
```

2 Implementation

2.1 Identification

```
22 \*package
23 \NeedsTeXFormat{LaTeX2e}
24 \ProvidesPackage{picture}%
25 [2016/05/16 v1.4 Dimens for picture macros (HO)]%
```

2.2 Options

```
26 \def\Pc@calcname{calc}
27 \def\Pc@etexname{etex}
28 \def\Pc@plainname{plain}
```

`\Pc@method` Macro `\Pc@method` stores the method to use for calculations. Check which features are available and set the default for `\Pc@method`.

```
29 \@ifpackageloaded{calc}{%
30   \let\Pc@method\Pc@calcname
31 }{%
32   \begingroup\expandafter\expandafter\expandafter\endgroup
33   \expandafter\ifx\csname dimexpr\endcsname\relax
34     \let\Pc@method\Pc@plainname
35   \else
36     \let\Pc@method\Pc@etexname
37   \fi
38 }

39 \DeclareOption{plain}{%
40   \let\Pc@method\Pc@plainname
41 }
42 \DeclareOption{etex}{%
43   \begingroup\expandafter\expandafter\expandafter\endgroup
44   \expandafter\ifx\csname dimexpr\endcsname\relax
45     \PackageError{picture}{%
46       e-TeX is not available%
47     }\@ehc
48   \else
49     \let\Pc@method\Pc@etexname
50   \fi
51 }
52 \DeclareOption{calc}{%
53   \let\Pc@method\Pc@calcname
54 }
55 \ProcessOptions*
56 \begingroup
57   \let\online\@empty
58   \PackageInfo{picture}{Calculation method: \Pc@method}%
59 \endgroup
```

2.3 Calculation method

```
60 \ifx\Pc@method\Pc@calcname
61   \RequirePackage{calc}%
62 \fi
```

2.3.1 Method calc

```
63 \ifx\Pc@method\Pc@calcname
64   \def\Pc@tokslength#1{%
```

```

65 \beginingroup
66 \let\calc@error\Pc@calc@error
67 \setlength\dimen@{#1\unitlength}\Pc@next\Pc@nil{#1}%
68 }%
69 \let\PcOrg@calc@error\calc@error
70 \@ifpackagelater{calc}{2007/08/22}{% v4.3
71 \def\Pc@calc@error#1{%
72 \expandafter\ifx\expandafter\unitlength\noexpand#1\relax
73 \def\calc@next##1!{%
74 \endgroup
75 \aftergroup\afterassignment
76 \aftergroup\Pc@next
77 }%
78 \expandafter\@firstoftwo
79 \else
80 \expandafter\@secondoftwo
81 \fi
82 {%
83 \calc@next{#1}%
84 }{%
85 \PcOrg@calc@error{#1}%
86 }%
87 }%
88 }{%
89 \def\Pc@calc@error#1{%
90 \expandafter\ifx\expandafter\unitlength\noexpand#1\relax
91 \def\calc@next##1!{%
92 \endgroup
93 \aftergroup\afterassignment
94 \aftergroup\Pc@next
95 }%
96 \expandafter\@gobble
97 \else
98 \expandafter\@firstofone
99 \fi
100 {%
101 \PcOrg@calc@error{#1}%
102 }%
103 }%
104 }%
105 \fi

```

2.3.2 Method etex

```

106 \ifx\Pc@method\Pc@etexname
107 \def\Pc@tokslength#1{%
108 \beginingroup
109 \afterassignment\Pc@next
110 \dimen@=\dimexpr#1\unitlength\Pc@nil{#1}%
111 }%
112 \fi

```

2.3.3 Method plain

```

113 \ifx\Pc@method\Pc@plainname
114 \def\Pc@tokslength#1{%
115 \beginingroup
116 \afterassignment\Pc@next
117 \dimen@=#1\unitlength\Pc@nil{#1}%
118 }%

```

```
119 \fi
```

2.3.4 Help macros

```
120 \def\Pc@next#1\Pc@nil#2{%
121   \ifx\\#1\\%
122     \endgroup
123     \Pc@addtoks{#2}%
124   \else
125     \expandafter\endgroup
126     \expandafter\Pc@addtoks\expandafter{%
127       \expandafter{\the\dimen@\@gobble}%
128     }%
129   \fi
130 }
```

`\Pc@nil` `\Pc@nil` must not have the meaning of `\relax` because of `\dimexpr`.

```
131 \let\Pc@nil\message
```

`\Pc@addtoks`

```
132 \def\Pc@addtoks#1{%
133   \toks@=\expandafter{\the\toks@#1}%
134 }
```

`\Pc@init`

```
135 \def\Pc@init#1{%
136   \begingroup
137   \toks@={#1}%
138 }
```

`\Pc@finish`

```
139 \def\Pc@finish#1{%
140   \expandafter\endgroup
141   \expandafter#1\the\toks@
142 }
```

2.4 Redefinitions

`\picture@redefine` #1: command name
#2: parameter text, length parameter with & instead of #

```
143 \def\picture@redefine#1#2{%
144   \begingroup
145   \edef\reserved@a{%
146     \noexpand\noexpand
147     \expandafter\noexpand
148     \csname PcOrg@\expandafter\@gobble\string#1\endcsname
149   }%
150   \toks0{#1}%
151   \Pc@first#2&0%
152 }
```

`\Pc@first`

```
153 \def\Pc@first#1&{%
154   \toks1={#1}%
155   \toks2={\Pc@init{#1}}%
156   \Pc@scanlength
157 }
```

```

\Pc@scanlength #1: number of length parameter or zero
158 \def\Pc@scanlength#1{%
159   \ifcase#1 %
160     \expandafter\Pc@last
161   \else
162     \toks1=\expandafter{\the\toks1 ###1}%
163     \toks2=\expandafter{\the\toks2 \Pc@tokslength{###1}}%
164     \expandafter\Pc@scannext
165   \fi
166 }

\Pc@scannext
167 \def\Pc@scannext#1&{%
168   \ifx\#1\%
169   \else
170     \toks1=\expandafter{\the\toks1 #1}%
171     \toks2=\expandafter{\the\toks2 \Pc@addtoks{#1}}%
172   \fi
173   \Pc@scanlength
174 }

\Pc@last
175 \def\Pc@last{%
176   \edef\x{%
177     \endgroup
178     \let\reserved@a\the\toks0 %
179     \def\the\toks0 \the\toks1 {%
180       \the\toks2 %
181       \noexpand\Pc@finish\reserved@a
182     }%
183   }%
184   \x
185 }

```

2.4.1 L^AT_EX base macros

```

186 \picture@redefine\@picture{(&1,&2)(&3,&4)}
187 \picture@redefine\put{(&1,&2)}
188 \picture@redefine\multiput{(&1,&2)}
189 \picture@redefine\@multiput{(&1,&2)}
190 \picture@redefine\line{(#1,#2)&3}
191 \picture@redefine\vector{(#1,#2)&3}
192 \picture@redefine\dashbox{&1(&2,&3)}
193 \picture@redefine\@circle{&1}
194 \picture@redefine\@dot{&1}
195 \picture@redefine\@bezier{#1(&2,&3)(&4,&5)(&6,&7)}
196 \picture@redefine\@makepicbox{(&1,&2)}

```

2.4.2 Package pspicture

Package pspicture changes the signature of \@oval by adding an optional argument.

```

197 \@ifpackageloaded{pspicture}{%
198   \picture@redefine\@oval{[&1](&2,&3)}%
199   \picture@redefine\Line{(&1,&2)}%
200   \picture@redefine\Curve{(&1,&2)}%
201   \picture@redefine\Vector{(&1,&2)}%
202 }{%

```

```

203 \picture@redefine\@oval{(&1,&2)}%
204 }

```

2.5 Check package loading order

\PC@checkpackage

```

205 \def\Pc@checkpackage#1{%
206   \@ifpackageloaded{#1}{%
207     }{%
208       \AtBeginDocument{%
209         \@ifpackageloaded{#1}{%
210           \PackageWarningNoLine{picture}{%
211             Package `#1' is loaded after `picture'.\MessageBreak
212             Load package `picture' afterwards to get full support%
213             \MessageBreak
214             of its additional syntax with length specifications%
215           }%
216         }{%
217       }%
218     }%
219   }

220 \Pc@checkpackage{pict2e}
221 \Pc@checkpackage{pspicture}
222 \</package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/picture.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/picture.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

¹[CTAN:pkg/picture](#)

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TEX`:

```
tex picture.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
picture.sty      → tex/latex/oberdiek/picture.sty
picture.pdf      → doc/latex/oberdiek/picture.pdf
picture-example.tex → doc/latex/oberdiek/picture-example.tex
picture.dtx      → source/latex/oberdiek/picture.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your `TEX` distribution (`TEX Live`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `TEX Live` users run `texhash` or `mktextlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{picture.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdfLATEX`:

```
pdflatex picture.dtx
makeindex -s gind.ist picture.idx
pdflatex picture.dtx
makeindex -s gind.ist picture.idx
pdflatex picture.dtx
```

4 History

[2006/08/26 v1.0]

- First released version. (First start of the project was June/July 2002.)

[2007/04/11 v1.1]

- Line ends sanitized.

[2008/11/26 v1.2]

- Package pict2e added to documentation section “Supported packages”.
- Package order of supported packages is checked.

[2009/10/11 v1.3]

- Fix because of new version v4.3 of package calc.

[2016/05/16 v1.4]

- Documentation updates.

5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols			
<code>\@bezier</code>	195	<code>\DeclareOption</code>	39, 42, 52
<code>\@circle</code>	193	<code>\dimen@</code>	67, 110, 117, 127
<code>\@dot</code>	194	<code>\dimexpr</code>	110
<code>\@ehc</code>	47	<code>\documentclass</code>	2
<code>\@empty</code>	57	E	
<code>\@firstofone</code>	98	<code>\end</code>	18, 20
<code>\@firstoftwo</code>	78	<code>\endcsname</code>	33, 44, 148
<code>\@gobble</code>	96, 127, 148	F	
<code>\@ifpackagelater</code>	70	<code>\fboxsep</code>	12
<code>\@ifpackageloaded</code>	29, 197, 206, 209	H	
<code>\@imakepicbox</code>	196	<code>\heightof</code>	12
<code>\@multitup</code>	189	I	
<code>\@oval</code>	198, 203	<code>\ifcase</code>	159
<code>\@picture</code>	186	<code>\ifx</code>	33, 44, 60, 63, 72, 90, 106, 113, 121, 168
<code>\@secondoftwo</code>	80	L	
<code>\@</code>	121, 168	<code>\Line</code>	199
A		<code>\line</code>	13, 16, 190
<code>\afterassignment</code>	75, 93, 109, 116	M	
<code>\aftergroup</code>	75, 76, 93, 94	<code>\makebox</code>	11
<code>\AtBeginDocument</code>	208	<code>\message</code>	131
B		<code>\MessageBreak</code>	211, 213
<code>\begin</code>	6, 10	<code>\multitup</code>	188
C		N	
<code>\calc@error</code>	66, 69	<code>\NeedsTeXFormat</code>	23
<code>\calc@next</code>	73, 83, 91	O	
<code>\csname</code>	33, 44, 148	<code>\on@line</code>	57
<code>\Curve</code>	200		
D			
<code>\dashbox</code>	192		

P		\put 11, 12, 15, 187	
\PackageError	45	R	
\PackageInfo	58	\RequirePackage	61
\PackageWarningNoLine	210	\reserved@a	145, 178, 181
\Pc@addtoks	123, 126, <u>132</u> , 171	S	
\Pc@calc@error	66, 71, 89	\setlength	8, 67
\Pc@calcname	26, 30, 53, 60, 63	T	
\PC@checkpackage	<u>205</u>	\the	127, 133, 141,
\Pc@checkpackage	205, 220, 221		162, 163, 170, 171, 178, 179, 180
\Pc@etexname	27, 36, 49, 106	\toks	150, 154, 155,
\Pc@finish	<u>139</u> , 181		162, 163, 170, 171, 178, 179, 180
\Pc@first	151, <u>153</u>	\toks@	133, 137, 141
\Pc@init	<u>135</u> , <u>155</u>	U	
\Pc@last	160, <u>175</u>	\unitlength ...	8, 67, 72, 90, 110, 117
\Pc@method	<u>29</u> ,	\usepackage	4
	40, 49, 53, 58, 60, 63, 106, 113	V	
\Pc@next	67, 76, 94, 109, 116, 120	\Vector	201
\Pc@nil	67, 110, 117, 120, <u>131</u>	\vector	191
\Pc@plainname	28, 34, 40, 113	W	
\Pc@scanlength	156, <u>158</u> , 173	\widthof	10, 13, 15
\Pc@scannext	164, <u>167</u>	X	
\Pc@tokslength	64, 107, 114, 163	\x	176, 184
\PcOrg@calc@error	69, 85, 101		
\picture@redefine <u>143</u> , 186, 187, 188,			
	189, 190, 191, 192, 193, 194,		
	195, 196, 198, 199, 200, 201, 203		
\ProcessOptions	55		
\ProvidesPackage	24		