

# The **selinput** package

Heiko Oberdiek\*

2016/05/17 v1.4

## Abstract

This package selects the input encoding by specifying between input characters and their glyph names.

## Contents

<b>1</b>	<b>Documentation</b>	<b>1</b>
1.1	Introduction . . . . .	1
1.2	User interface . . . . .	2
1.3	Options . . . . .	3
1.4	Encodings . . . . .	3
<b>2</b>	<b>Implementation</b>	<b>4</b>
<b>3</b>	<b>Test</b>	<b>8</b>
<b>4</b>	<b>Installation</b>	<b>10</b>
4.1	Download . . . . .	10
4.2	Bundle installation . . . . .	10
4.3	Package installation . . . . .	10
4.4	Refresh file name databases . . . . .	11
4.5	Some details for the interested . . . . .	11
<b>5</b>	<b>References</b>	<b>11</b>
<b>6</b>	<b>History</b>	<b>11</b>
	[2007/06/16 v1.0] . . . . .	11
	[2007/06/20 v1.1] . . . . .	11
	[2007/09/09 v1.2] . . . . .	12
	[2016/05/16 v1.3] . . . . .	12
	[2016/05/17 v1.4] . . . . .	12

## 1 Documentation

### 1.1 Introduction

L<sup>A</sup>T<sub>E</sub>X supports the direct use of 8-bit characters by means of package `inputenc`. However you must know and specify the encoding, e.g.:

---

\*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

```

\documentclass{article}
\usepackage[latin1]{inputenc}
% or \usepackage[utf8]{inputenc}
% or \usepackage[??]{inputenc}
\begin{document}
  Umlauts: ÄÖÜäöüß
\end{document}

```

If the document is transferred in an environment that uses a different encoding, then there are programs that convert the input characters. Examples for conversion of file `test.tex` from encoding latin1 (ISO-8859-1) to UTF-8:

```

recode ISO-8859-1..UTF-8 test.tex
recode latin1..utf8 test.tex
iconv --from-code ISO-8859-1
      --to-code UTF-8
      --output testnew.tex
      test.tex
iconv -f latin1 -t utf8 -o testnew.tex test.tex

```

However, the encoding name for package `inputenc` must be changed:

```

\usepackage[latin1]{inputenc} → \usepackage[utf8]{inputenc}

```

Of course, unless you are using some clever editor that knows package `inputenc`, recodes the file and adjusts the option at the same time. But most editors can perhaps recode the file, but they let the option untouched.

Therefore package `selinput` chooses another way for specifying the input encoding. The encoding name is not needed at all. Some 8-bit characters are identified by their glyph name and the package chooses an appropriate encoding, example:

```

\documentclass{article}
\usepackage{selinput}
\SelectInputMappings{
  adieresis={ä},
  germandbls={ß},
  Euro={€},
}
\begin{document}
  Umlauts: ÄÖÜäöüß
\end{document}

```

## 1.2 User interface

`\SelectInputEncodingList {⟨encoding list⟩}`

`\SelectInputEncodingList` expects a comma separated list of encoding names. Example:

```

\SelectInputEncodingList{utf8,ansinew,mac-roman}

```

The encodings of package `inputenx` are used as default.

`\SelectInputMappings {⟨mapping pairs⟩}`

A mapping pair consists of a glyph name and its input character:

```

\SelectInputMappings{
  adieresis={ä},
  germandbls={ß},
  Euro={€},
}

```

The supported glyph names can be found in file `ix-name.def` of project `inputenx` [1]. The names are basically taken from Adobe’s glyphlists [2, 3]. As many pairs are needed as necessary to identify the encoding. Example with insufficient pairs:

```

\SelectInputEncodingSet{latin1,latin9}
\SelectInputMappings{
  adieresis={ä},
  germandbls={ß},
}
Umlauts: ÄÖÜäöüß and Euro: ¤ (wrong)

```

The first encoding `latin1` passes the constraints given by the mapping pairs. However the Euro symbol is not part of the encoding. Thus a mapping pair with the Euro symbol solves the problem. In fact the symbol alone already succeeds in selecting between `latin1` and `latin9`:

```

\SelectInputEncodingSet{latin1,latin9}
\SelectInputMappings{
  Euro={€},
}
Umlauts: ÄÖÜäöüß and Euro: €

```

### 1.3 Options

**warning:** The selected encoding is written by `\PackageInfo` into the `.log` file only. Option `warning` changes it to `\PackageWarning`. Then the selected encoding is shown on the terminal as well.

**ucs:** The encoding file `utf8x` of package `\ucs` requires that the package itself is loaded before. If the package is not loaded, then the option `ucs` will load package `ucs` if the detected encoding is UTF-8 (limited to the preamble, packages cannot be loaded later).

**utf8=...:** The option allows to specify other encoding files for UTF-8 than L<sup>A</sup>T<sub>E</sub>X’s `utf8.def`. For example, `utf8=utf-8` will load `utf-8.def` instead.

### 1.4 Encodings

Package `stringenc` [4] is used for testing the encoding. Thus the encoding name must be known by this package. Then the found encoding is loaded by `\inputencoding` by package `inputenc` or `\InputEncoding` if package `inputenx` is loaded.

The supported encodings are present in the encoding list, thus usually the encoding names do not matter. If the list is set by `\SelectInputEncodingList`, then you can use the names that work for package `inputenc` and are known by package `stringenc`, for example: `latin1`, `x-iso-8859-1`. Encoding file names of package `inputenx` are prefixed with `x-`. The prefix can be dropped, if package `inputenx` is loaded.

## 2 Implementation

```

1 (*package)
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{selinput}
4 [2016/05/17 v1.4 Semi-automatic input encoding detection (HO)]%

5 \RequirePackage{inputenc}
6 \RequirePackage{kvsetkeys}[2006/10/19]
7 \RequirePackage{stringenc}[2007/06/16]
8 \RequirePackage{kvoptions}

\SelectInputEncodingList

9 \newcommand*\SelectInputEncodingList}{%
10 \let\SIE@EncodingList\@empty
11 \kvsetkeys{SelInputEnc}%
12 }

\SelectInputMappings

13 \newcommand*\SelectInputMappings}[1]{%
14 \SIE@LoadNameDefs
15 \let\SIE@StringUnicode\@empty
16 \let\SIE@StringDest\@empty
17 \kvsetkeys{SelInputMap}{#1}%
18 \ifx\SIE@StringUnicode\SIE@StringDest\%
19 \PackageError{selinput}{%
20 No mappings specified%
21 }\@ehc
22 \else
23 \EdefUnescapeHex\SIE@StringUnicode\SIE@StringUnicode
24 \let\SIE@Encoding\@empty
25 \@for\SIE@EncodingTest:=\SIE@EncodingList\do{%
26 \ifx\SIE@Encoding\@empty
27 \StringEncodingConvertTest\SIE@temp\SIE@StringUnicode
28 {utf16be}\SIE@EncodingTest{%
29 \ifx\SIE@temp\SIE@StringDest
30 \let\SIE@Encoding\SIE@EncodingTest
31 \fi
32 }{}%
33 \fi
34 }%
35 \ifx\SIE@Encoding\@empty
36 \StringEncodingConvertTest\SIE@temp\SIE@StringDest
37 {ascii}{utf16be}{%
38 \def\SIE@Encoding{ascii}%
39 \SIE@Info{selinput}{%
40 Matching encoding not found, but input characters%
41 \MessageBreak
42 are 7-bit (possibly editor replacements).%
43 \MessageBreak
44 Hence using ascii encoding%
45 }%
46 }{}%
47 \fi
48 \ifx\SIE@Encoding\@empty
49 \PackageError{selinput}{%
50 Cannot find a matching encoding%
51 }\@ehd
52 \else

```

```

53 \ifx\SIE@Encoding\SIE@EncodingUTFviii
54 \SIE@LoadUnicodePackage
55 \ifx\SIE@UseUTFviii\@empty
56 \else
57 \let\SIE@Encoding\SIE@UseUTFviii
58 \fi
59 \fi
60 \begingroup\expandafter\expandafter\expandafter\endgroup
61 \expandafter\ifx\csname InputEncoding\endcsname\relax
62 \inputencoding\SIE@Encoding
63 \else
64 \InputEncoding\SIE@Encoding
65 \fi
66 \SIE@Info{selinput}{Encoding `\'SIE@Encoding' selected}%
67 \fi
68 \fi
69 }

```

\SIE@LoadNameDefs

```

70 \def\SIE@LoadNameDefs{%
71 \begingroup
72 \endlinechar=\m@ne
73 \catcode92=0 % backslash
74 \catcode123=1 % left curly brace/beginning of group
75 \catcode125=2 % right curly brace/end of group
76 \catcode37=14 % percent/comment character
77 \@makeother\[
78 \@makeother\]
79 \@makeother\.%
80 \@makeother\(%
81 \@makeother\)%
82 \@makeother\/%
83 \@makeother\-%
84 \let\InputenxName\SelectInputDefineMapping
85 \InputIfFileExists{ix-name.def}{\}%
86 \PackageError{selinput}{\%
87 Missing `ix-name.def' (part of package `inputenx')%
88 }\@ehd
89 }%
90 \global\let\SIE@LoadNameDefs\relax
91 \endgroup
92 }

```

\SelectInputDefineMapping

```

93 \newcommand*{\SelectInputDefineMapping}[1]{%
94 \expandafter\gdef\csname SIE@@#1\endcsname
95 }

96 \kv@set@family@handler{SelInputMap}{\%
97 \@onelevel@sanitize\kv@key
98 \ifx\kv@value\relax
99 \PackageError{selinput}{\%
100 Missing input character for `\'kv@key'%
101 }\@ehc
102 \else
103 \@onelevel@sanitize\kv@value
104 \ifx\kv@value\@empty
105 \PackageError{selinput}{\%

```

```

106      Input character got lost?\MessageBreak
107      Missing input character for `~\kv@key'%
108    }~\@ehc
109  ~\else
110    ~\@ifundefined{SIE@@\kv@key}{~%
111      ~\PackageWarning{selinput}{~%
112        Missing definition for `~\kv@key'%
113      }~%
114    }~%
115    ~\edef\SIE@StringDest{~%
116      ~\SIE@StringDest
117      ~\kv@value
118    }~%
119    ~\edef\SIE@StringUnicode{~%
120      ~\SIE@StringUnicode
121      ~\csname SIE@@\kv@key\endcsname
122    }~%
123  }~%
124  ~\fi
125  ~\fi
126 }

127 ~\kv@set@family@handler{SelInputEnc}{~%
128   ~\@onelevel@sanitize\kv@key
129   ~\ifx\kv@value~\relax
130     ~\ifx\SIE@EncodingList~\@empty
131       ~\let\SIE@EncodingList\kv@key
132     ~\else
133       ~\edef\SIE@EncodingList{~\SIE@EncodingList,~\kv@key}~%
134     ~\fi
135   ~\else
136     ~\@onelevel@sanitize\kv@value
137     ~\PackageError{selinput}{~%
138       Illegal key value pair (~\kv@key=~\kv@value)\MessagBreak
139       in encoding list~%
140     }~\@ehc
141   ~\fi
142 }

```

\SIE@LoadUnicodePackage

```

143 ~\def\SIE@LoadUnicodePackage{~%
144   ~\@ifpackageloaded\SIE@UnicodePackage}{~%
145     ~\RequirePackage\SIE@UnicodePackage~\relax
146   }~%
147   ~\SIE@PatchUCS
148   ~\global~\let\SIE@LoadUnicodePackage~\relax
149 }

150 ~\let\SIE@show~\show
151 ~\def\SIE@PatchUCS{~%
152   ~\AtBeginDocument{~%
153     ~\expandafter~\ifx~\csname ver@ucsencs.def\endcsname~\relax
154     ~\else
155       ~\let~\show~\SIE@show
156     ~\fi
157   }~%
158 }

159 ~\SIE@PatchUCS

160 ~\AtBeginDocument{~%

```

```

161 \let\SIE@LoadUnicodePackage\relax
162 }

\SIE@EncodingUTFviii
163 \def\SIE@EncodingUTFviii{utf8}
164 \@onelevel@sanitize\SIE@EncodingUTFviii

\SIE@EncodingUTFviiix
165 \def\SIE@EncodingUTFviiix{utf8x}
166 \@onelevel@sanitize\SIE@EncodingUTFviiix

167 \let\SIE@UnicodePackage\@empty
168 \let\SIE@UseUTFviii\@empty
169 \let\SIE@Info\PackageInfo

170 \SetupKeyvalOptions{%
171   family=SelInput,%
172   prefix=SelInput%
173 }
174 \define@key{SelInput}{utf8}{%
175   \def\SIE@UseUTFviii{#1}%
176   \@onelevel@sanitize\SIE@UseUTFviii
177 }
178 \DeclareBoolOption{ucs}
179 \DeclareVoidOption{warning}{%
180   \let\SIE@Info\PackageWarning
181 }
182 \ProcessKeyvalOptions{SelInput}
183 \ifSelInput@ucs
184   \def\SIE@UnicodePackage{ucs}%
185   \ifx\SIE@UseUTFviii\@empty
186     \let\SIE@UseUTFviii\SIE@EncodingUTFviiix
187   \fi
188 \else
189   \ifx\SIE@UseUTFviii\@empty
190     \ifpackageloaded{ucs}{%
191       \let\SIE@UseUTFviii\SIE@EncodingUTFviiix
192     }{%
193       \let\SIE@UseUTFviii\SIE@EncodingUTFviii
194     }%
195   \fi
196 \fi

\SIE@EncodingList
197 \edef\SIE@EncodingList{%
198   utf8,%
199   x-iso-8859-1,%
200   x-iso-8859-15,%
201   x-cp1252,% ansinew
202   x-mac-roman,%
203   x-iso-8859-2,%
204   x-iso-8859-3,%
205   x-iso-8859-4,%
206   x-iso-8859-5,%
207   x-iso-8859-6,%
208   x-iso-8859-7,%
209   x-iso-8859-8,%
210   x-iso-8859-9,%
211   x-iso-8859-10,%

```

```

212 x-iso-8859-11,%
213 x-iso-8859-13,%
214 x-iso-8859-14,%
215 x-iso-8859-15,%
216 x-mac-centeuro,%
217 x-mac-cyrillic,%
218 x-koi8-r,%
219 x-cp1250,%
220 x-cp1251,%
221 x-cp1257,%
222 x-cp437,%
223 x-cp850,%
224 x-cp852,%
225 x-cp855,%
226 x-cp858,%
227 x-cp865,%
228 x-cp866,%
229 x-nextstep,%
230 x-dec-mcs%
231 }%
232 \@onelevel@sanitize\SIE@EncodingList
233 \</package>

```

### 3 Test

```

234 \<test>
235 \NeedsTeXFormat{LaTeX2e}
236 \documentclass{minimal}
237 \usepackage{textcomp}
238 \usepackage{qstest}

239 \<test1 j test2 j test3>
240 \makeatletter
241 \let\BeginDocumentText\@empty
242 \def\TestEncoding#1#2{%
243   \SelectInputMappings{#2}%
244   \Expect*{\SIE@Encoding}{#1}%
245   \Expect*{\inputencodingname}{#1}%
246   \g@addto@macro\BeginDocumentText{%
247     \SelectInputMappings{#2}%
248     \Expect*{\SIE@Encoding}{#1}%
249     \textbf{\SIE@Encoding:} %
250     \kvsetkeys{test}{#2}\par
251   }%
252 }
253 \def\TestKey#1#2{%
254   \define@key{test}{#1}{%
255     \sbox0{##1}%
256     \sbox2{#2}%
257     \Expect*{wd:\the\wd0, ht:\the\ht0, dp:\the\dp0}%
258     *{wd:\the\wd2, ht:\the\ht2, dp:\the\dp2}%
259     [#1=##1] % hash-ok
260   }%
261 }
262 \RequirePackage{keyval}
263 \TestKey{adieresis}{\a}
264 \TestKey{germandbls}{\ss}

```



```

265 \TestKey{Euro}{\texteuro}
266 \makeatother
267 \usepackage[
268   warning,%
269   <test2> utf8=utf-8,
270   <test3> ucs,
271 ]{selinput}
272 <test1 j test3> \inputencoding{ascii}
273 <test2> \inputencoding{utf-8}
274 <test3> \usepackage{ucs}
275 \begin{qstest}{preamble}{}
276   \TestEncoding{x-iso-8859-15}{%
277     adieresis=^e4,%
278     germandbls=^df,%
279     Euro=^a4,%
280   }%
281   \TestEncoding{x-cp1252}{%
282     adieresis=^e4,%
283     germandbls=^df,%
284     Euro=^80,%
285   }%
286 <test1> \TestEncoding{utf8}{%
287 <test2> \TestEncoding{utf-8}{%
288 <test3> \TestEncoding{utf8x}{%
289   adieresis=^c3^a4,%
290   germandbls=^c3^9f,%
291 !<test2> Euro=^e2^82^ac,
292   }%
293 \end{qstest}
294 <test3> \let\ifUnicodeOptiongraphics\iffalse
295 \begin{document}
296 \begin{qstest}{document}{}
297 <test3> \makeatletter
298   \BeginDocumentText
299 \end{qstest}
300 </test1 j test2 j test3>
301 (*test4)
302 \usepackage[warning,ucs]{selinput}
303 \SelectInputMappings{%
304   adieresis=^c3^a4,%
305   germandbls=^c3^9f,%
306   Euro=^e2^82^ac,%
307 }
308 \begin{qstest}{encoding}{}
309   \Expect*{\inputencodingname}{utf8x}%
310 \end{qstest}
311 \begin{document}
312   adieresis=^c3^a4, %
313   germandbls=^c3^9f, %
314   Euro=^e2^82^ac%
315 </test4>
316 (*test5)
317 \usepackage[warning,ucs]{selinput}
318 \SelectInputMappings{%
319   adieresis={\a},%
320   germandbls={\ss},%
321   Euro=\texteuro{},%
322 }

```

```

323 \begin{qstest}{encoding}{}
324   \Expect*{\inputencodingname}{ascii}%
325 \end{qstest}
326 \begin{document}
327   adieresis={"a}, %
328   germandbls={{\ss}}, %
329   Euro=\texteuro{}%
330 \end{document}
331 \end{document}
332 \end{test}

```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/selinput.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/selinput.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

### 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

### 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T<sub>E</sub>X:

```
tex selinput.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```

selinput.sty      → tex/latex/oberdiek/selinput.sty
selinput.pdf      → doc/latex/oberdiek/selinput.pdf
test/selinput-test1.tex → doc/latex/oberdiek/test/selinput-test1.tex
test/selinput-test2.tex → doc/latex/oberdiek/test/selinput-test2.tex
test/selinput-test3.tex → doc/latex/oberdiek/test/selinput-test3.tex
test/selinput-test4.tex → doc/latex/oberdiek/test/selinput-test4.tex
test/selinput-test5.tex → doc/latex/oberdiek/test/selinput-test5.tex
selinput.dtx      → source/latex/oberdiek/selinput.dtx

```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

---

<sup>1</sup>[CTAN:pkg/selinput](#)

## 4.4 Refresh file name databases

If your T<sub>E</sub>X distribution (T<sub>E</sub>X Live, mikT<sub>E</sub>X, ...) relies on file name databases, you must refresh these. For example, T<sub>E</sub>X Live users run `texhash` or `mktextlsr`.

## 4.5 Some details for the interested

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The `.dtx` chooses its action depending on the format:

**plain T<sub>E</sub>X:** Run `docstrip` and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for `docstrip` (really, `docstrip` does not need L<sup>A</sup>T<sub>E</sub>X), then inform the `autodetect` routine about your intention:

```
latex \let\install=y\input{selinput.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex selinput.dtx
makeindex -s gind.ist selinput.idx
pdflatex selinput.dtx
makeindex -s gind.ist selinput.idx
pdflatex selinput.dtx
```

## 5 References

- [1] Heiko Oberdiek: *The inputenx package*; 2007-04-11 v1.1; [CTAN:pkg/inputenx](#).
- [2] Adobe: *Adobe Glyph List*; 2002-09-20 v2.0; <https://github.com/adobe-type-tools/agl-aglfn/blob/master/glyphlist.txt>.
- [3] Adobe: *Adobe Glyph List For New Fonts*; 2005-11-18 v1.5; <https://github.com/adobe-type-tools/agl-aglfn/blob/master/aglfn.txt>.
- [4] Heiko Oberdiek: *The stringenc package*; 2007-06-16 v1.1; [CTAN:pkg/stringenc](#).

## 6 History

[2007/06/16 v1.0]

- First version.

[2007/06/20 v1.1]

- Requested date for package `stringenc` fixed.

[2007/09/09 v1.2]

- Line end fixed.

[2016/05/16 v1.3]

- Documentation updates.

[2016/05/17 v1.4]

- Documentation updates: Avoid T1 encoding with Unicode T<sub>E</sub>X.

## 7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols		E	
\"	263, 319, 327	\EdefUnescapeHex	23
\(	80	\end	293, 299, 310, 325, 331
\)	81	\endcsname	61, 94, 121, 153
\-	83	\endlinechar	72
\.	79	\Expect	244, 245, 248, 257, 309, 324
\/	82		
\@ehc	21, 101, 108, 140	G	
\@ehd	51, 88	\g@addto@macro	246
\@empty	10, 15, 16, 24, 26, 35, 48, 55, 104, 130, 167, 168, 185, 189, 241	\gdef	94
\@for	25	H	
\@ifpackageloaded	144, 190	\ht	257, 258
\@ifundefined	110	I	
\@makeoother	77, 78, 79, 80, 81, 82, 83	\iffalse	294
\@onelevel@sanitize	97, 103, 128, 136, 164, 166, 176, 232	\ifSelInput@ucs	183
\[	77	\ifUnicodeOptiongraphics	294
\]	18	\ifx	18, 26, 29, 35, 48, 53, 55, 61, 98, 104, 129, 130, 153, 185, 189
\]	78	\InputEncoding	64
A		\inputencoding	62, 272, 273
\AtBeginDocument	152, 160	\inputencodingname	245, 309, 324
B		\InputenxName	84
\begin	275, 295, 296, 308, 311, 323, 326	\InputIfFileExists	85
\BeginDocumentText	241, 246, 298	K	
C		\kv@key	97, 100, 107, 110, 112, 121, 128, 131, 133, 138
\catcode	73, 74, 75, 76	\kv@set@family@handler	96, 127
\csname	61, 94, 121, 153	\kv@value	98, 103, 104, 117, 129, 136, 138
D		\kvsetkeys	11, 17, 250
\DeclareBoolOption	178	M	
\DeclareVoidOption	179	\m@ne	72
\define@key	174, 254	\makeatletter	240, 297
\do	25	\makeatother	266
\documentclass	236	\MessageBreak	138
\dp	257, 258	\MessageBreak	41, 43, 106

<b>N</b>		\SIE@EncodingUTFviiiix ..	165, 186, 191
\NeedsTeXFormat .....	2, 235	\SIE@Info .....	39, 66, 169, 180
\newcommand .....	9, 13, 93	\SIE@LoadNameDefs .....	14, 70
<b>P</b>		\SIE@LoadUnicodePackage ..	54, 143, 161
\PackageError ..	19, 49, 86, 99, 105, 137	\SIE@PatchUCS .....	147, 151, 159
\PackageInfo .....	169	\SIE@show .....	150, 155
\PackageWarning .....	111, 180	\SIE@StringDest ..	16, 18, 29, 36, 115, 116
\par .....	250	\SIE@StringUnicode ..	15, 23, 27, 119, 120
\ProcessKeyvalOptions .....	182	\SIE@temp .....	27, 29, 36
\ProvidesPackage .....	3	\SIE@UnicodePackage ..	144, 145, 167, 184
<b>R</b>		\SIE@UseUTFviii .....	55, 57, 168, 175, 176, 185, 186, 189, 191, 193
\RequirePackage ...	5, 6, 7, 8, 145, 262	\ss .....	264, 320, 328
<b>S</b>		\StringEncodingConvertTest ..	27, 36
\sbox .....	255, 256	<b>T</b>	
\SelectInputDefineMapping ...	84, 93	\TestEncoding .....	242, 276, 281, 286, 287, 288
\SelectInputEncodingList .....	2, 9	\TestKey .....	253, 263, 264, 265
\SelectInputMappings .....	2, 13, 243, 247, 303, 318	\textbf .....	249
\SetupKeyvalOptions .....	170	\texteuro .....	265, 321, 329
\show .....	150, 155	\the .....	257, 258
\SIE@Encoding ...	24, 26, 30, 35, 38, 48, 53, 57, 62, 64, 66, 244, 248, 249	<b>U</b>	
\SIE@EncodingList .....	10, 25, 130, 131, 133, 197	\usepackage ..	237, 238, 267, 274, 302, 317
\SIE@EncodingTest .....	25, 28, 30	<b>W</b>	
\SIE@EncodingUTFviii ..	53, 163, 193	\wd .....	257, 258