

The ltxcmds package

Heiko Oberdiek*

2016/05/16 v1.23

Abstract

The package `ltxcmds` exports some utility macros from the \LaTeX kernel into a separate namespace and also provides them for other formats such as plain- \TeX .

Contents

1	Documentation	3
1.1	Introduction	3
1.2	Numbers	3
1.3	Scratch registers	3
1.4	Argument killers	3
1.5	Argument grabbers	4
1.6	List helpers	5
1.7	Tail recursion	5
1.8	Empty macro	6
1.9	Characters	6
1.10	Boolean switch	6
1.11	Command definitions	6
1.12	Stripping	7
1.13	File management	7
	1.13.1 File extensions	7
	1.13.2 Load check	7
	1.13.3 Version date check	8
1.14	Macro additions	8
1.15	Next character detection	8
1.16	<code>\ltx@leavevmode</code> , <code>\ltx@mbox</code>	9
1.17	Expandable test for emptiness	9
1.18	Stripping spaces	9
1.19	Check for emptiness of boxes	10
2	Implementation	10
2.1	Identification	10
2.2	Numbers	12
2.3	Scratch registers	12
2.4	Argument killers	14
2.5	Argument grabbers	15
2.6	List helpers	15
2.7	Tail recursion	17

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

2.8	Empty macro	17
2.9	Characters	17
2.10	Boolean switch	18
2.11	Command definitions	19
2.12	Stripping	20
2.13	File management	20
2.13.1	File extensions	20
2.13.2	Load check	20
2.13.3	Version date check	21
2.14	Macro additions	22
2.15	Next character detection	23
2.16	<code>\ltx@leavevmode</code> , <code>\ltx@mbox</code>	24
2.17	Help macros	25
2.18	Expandable test for emptiness	25
2.18.1	Vanilla \TeX	25
2.18.2	With <code>\detokenize</code>	26
2.18.3	<code>\ltx@ifblank</code>	26
2.19	<code>\ltx@zapspace</code>	27
2.20	<code>\ltx@ifBoxEmpty</code>	27
3	Installation	28
3.1	Download	28
3.2	Bundle installation	29
3.3	Package installation	29
3.4	Refresh file name databases	29
3.5	Some details for the interested	29
4	References	30
5	History	30
[2009/08/05 v1.0]		30
[2009/12/12 v1.1]		30
[2010/01/28 v1.2]		31
[2010/03/01 v1.3]		31
[2010/03/09 v1.4]		31
[2010/04/08 v1.5]		31
[2010/04/16 v1.6]		31
[2010/04/26 v1.7]		31
[2010/09/11 v1.8]		31
[2010/10/25 v1.9]		31
[2010/10/31 v1.10]		31
[2010/11/12 v1.11]		32
[2010/12/02 v1.12]		32
[2010/12/04 v1.13]		32
[2010/12/07 v1.14]		32
[2010/12/12 v1.15]		32
[2011/02/04 v1.16]		32
[2011/02/05 v1.17]		32
[2011/03/16 v1.18]		32
[2011/04/14 v1.19]		32
[2011/04/18 v1.20]		32
[2011/08/22 v1.21]		32
[2011/11/09 v1.22]		33
[2016/05/16 v1.23]		33

1 Documentation

1.1 Introduction

Many of my packages also support other formats such as plain-TeX. Because I am rather familiar with the utility macros from L^AT_EX's kernel (e.g. `\@gobble`, `\@firstoftwo`), I found myself rewriting them again and again, because they are lacking in plain-TeX.

Therefore this package provides often used macros and similar ones with the name prefix `\ltx@`. This avoids also faulty redefinitions. I remember an example where a package redefined `\@firstoftwo` with forgetting `\long`.

1.2 Numbers

<code>\ltx@zero</code>	→ 0
<code>\ltx@one</code>	→ 1
<code>\ltx@two</code>	→ 2
<code>\ltx@ccclv</code>	→ 255
<code>\ltx@minusone</code>	→ -1

These commands are numbers 0, 1, 2, 255 and -1. They are not digits and a space is not gobbled afterwards. Macro `\ltx@minusone` is available since version 2010/12/12 v1.15.

1.3 Scratch registers

Following the conventions of plain TeX and L^AT_EX the first ten registers are free to use. Even numbered registers are for local, odd numbered for global use.

<code>\ltx@(Loc, Glob)(Toks, Dimen, Skip)(A, B, C, D, E)</code>

The name consists of the prefix `\ltx@`, then `Loc` or `Glob` for local or global usage follows. The register type is given by `Toks` for token register, `Dimen` for dimen register and `Skip` for skip register. As last part the registers are numbered from A to E. Example: `\ltx@LocToksA`.

Since 2011/04/14 v1.19.

1.4 Argument killers

<code>\ltx@gobble {⟨1⟩}</code>	→
<code>\ltx@gobbletwo {⟨1⟩} {⟨2⟩}</code>	→
<code>\ltx@gobblethree {⟨1⟩} {⟨2⟩} {⟨3⟩}</code>	→
<code>\ltx@gobblefour {⟨1⟩} {⟨2⟩} {⟨3⟩} {⟨4⟩}</code>	→

<code>\ltx@GobbleNum {⟨num⟩} {⟨1⟩} {⟨2⟩} ... {⟨⟨num⟩⟩}</code>	→
---	---

The first argument `⟨num⟩` of macro `\ltx@GobbleNum` specifies, how many following arguments are eaten. Macro `\ltx@GobbleNum` is expandable in exact two

expansion steps.

1.5 Argument grabbers

<code>\ltx@firstofone</code>	<code>{\langle 1 \rangle}</code>	\rightarrow	$\langle 1 \rangle$
<code>\ltx@firstoftwo</code>	<code>{\langle 1 \rangle} {\langle 2 \rangle}</code>	\rightarrow	$\langle 1 \rangle$
<code>\ltx@secondoftwo</code>	<code>{\langle 1 \rangle} {\langle 2 \rangle}</code>	\rightarrow	$\langle 2 \rangle$
<code>\ltx@firstofthree</code>	<code>{\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle}</code>	\rightarrow	$\langle 1 \rangle$
<code>\ltx@secondofthree</code>	<code>{\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle}</code>	\rightarrow	$\langle 2 \rangle$
<code>\ltx@thirdofthree</code>	<code>{\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle}</code>	\rightarrow	$\langle 3 \rangle$
<code>\ltx@firstoffour</code>	<code>{\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} {\langle 4 \rangle}</code>	\rightarrow	$\langle 1 \rangle$
<code>\ltx@secondoffour</code>	<code>{\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} {\langle 4 \rangle}</code>	\rightarrow	$\langle 2 \rangle$
<code>\ltx@thirdoffour</code>	<code>{\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} {\langle 4 \rangle}</code>	\rightarrow	$\langle 3 \rangle$
<code>\ltx@fourthoffour</code>	<code>{\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} {\langle 4 \rangle}</code>	\rightarrow	$\langle 4 \rangle$

Macros `\ltx@firstofthree`, `\ltx@secondofthree` and `\ltx@thirdofthree` were added in version 2010/11/12 v1.11. Macros `\ltx@firstoffour`, ..., `\ltx@fourthoffour` were added in version 2011/02/04 v1.16.

1.6 List helpers

<code>\ltx@carzero ... \@nil</code>	\rightarrow
<code>\ltx@cdrzero ... \@nil</code>	$\rightarrow \dots$

<code>\ltx@car {\langle 1 \rangle} ... \@nil</code>	$\rightarrow \langle 1 \rangle$
<code>\ltx@cdr {\langle 1 \rangle} ... \@nil</code>	$\rightarrow \dots$

<code>\ltx@cartwo {\langle 1 \rangle} {\langle 2 \rangle} ... \@nil</code>	$\rightarrow \langle 1 \rangle \langle 2 \rangle$
<code>\ltx@carsecond {\langle 1 \rangle} {\langle 2 \rangle} ... \@nil</code>	$\rightarrow \langle 2 \rangle$
<code>\ltx@cdrtwo {\langle 1 \rangle} {\langle 2 \rangle} ... \@nil</code>	$\rightarrow \dots$

<code>\ltx@carthree {\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} ... \@nil</code>	$\rightarrow \langle 1 \rangle \langle 2 \rangle \langle 3 \rangle$
<code>\ltx@carthird {\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} ... \@nil</code>	$\rightarrow \langle 3 \rangle$
<code>\ltx@cdrthree {\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} ... \@nil</code>	$\rightarrow \dots$

<code>\ltx@carfour {\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} {\langle 4 \rangle} ... \@nil</code>	$\rightarrow \langle 1 \rangle \langle 2 \rangle \langle 3 \rangle \langle 4 \rangle$
<code>\ltx@carfourth {\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} {\langle 4 \rangle} ... \@nil</code>	$\rightarrow \langle 4 \rangle$
<code>\ltx@cdrfour {\langle 1 \rangle} {\langle 2 \rangle} {\langle 3 \rangle} {\langle 4 \rangle} ... \@nil</code>	$\rightarrow \dots$

<code>\ltx@CarNum {\langle num \rangle} {\langle 1 \rangle} ... {\langle \langle num \rangle \rangle} {\langle \langle num \rangle + 1 \rangle} ... \@nil</code>	$\rightarrow \{\langle 1 \rangle\} \dots \{\langle \langle num \rangle \rangle\} \dots$
<code>\ltx@CarNumth {\langle num \rangle} {\langle 1 \rangle} ... {\langle \langle num \rangle \rangle} {\langle \langle num \rangle + 1 \rangle} ... \@nil</code>	$\rightarrow \{\langle \langle num \rangle \rangle\} \dots$
<code>\ltx@CdrNum {\langle num \rangle} {\langle 1 \rangle} ... {\langle \langle num \rangle \rangle} {\langle \langle num \rangle + 1 \rangle} ... \@nil</code>	$\rightarrow \{\langle \langle num \rangle + 1 \rangle\} \dots$

Macros with uppercase letters are expandable in two expansion steps. Changes in version 2016/05/16 v1.23:

- Macros `\ltx@carsecond`, `\ltx@carthird`, `\ltx@carfourth`, `\ltx@CarNumth` added.
- Macros `\ltx@cdr`, `\ltx@cdrtwo`, `\ltx@cdrthree`, `\ltx@cdrfour`, `\ltx@CdrNum` are expandable in two expansion steps and retain spaces and braces after the first gobbled arguments.

1.7 Tail recursion

<code>\ltx@ReturnAfterFi {\langle 1 \rangle} \fi</code>	$\rightarrow \fi \langle 1 \rangle$
<code>\ltx@ReturnAfterElseFi {\langle 1 \rangle} \else {\langle 2 \rangle} \fi</code>	$\rightarrow \fi \langle 1 \rangle$

1.8 Empty macro

<code>\ltx@empty</code>	→
-------------------------	---

1.9 Characters

<code>\ltx@space</code>	→	<code>\</code>
<code>\ltx@percentchar</code>	→	<code>%</code>
<code>\ltx@backslashchar</code>	→	<code>\</code>
<code>\ltx@hashchar</code>	→	<code>#</code> (since v1.7)
<code>\ltx@leftbracechar</code>	→	<code>{</code> (since v1.8)
<code>\ltx@rightbracechar</code>	→	<code>}</code> (since v1.8)

1.10 Boolean switch

<code>\ltx@newif {<cmd>}</code>

`\ltx@newif` defines a new boolean switch `<cmd>` like `\newif`. Unlike plain \TeX 's `\newif`, `\ltx@newif` is not `\outer`. The command `<cmd>` must start with the two characters `if`.

<code>\ltx@newglobalif {<cmd>}</code>

`\ltx@newglobalif` defines a new boolean switch `<cmd>` like `\ltx@newif`. However the switch setting commands, `<cmd>` without the prefix `if` and followed by `true` or `false` are acting globally.

1.11 Command definitions

<code>\ltx@ifundefined {<cmd>} {<yes>} {<no>}</code>
--

If $\varepsilon\text{-}\TeX$ is available, `\ifcsname` is used that does not have the side effect of defining undefined commands with meaning of `\relax`. This command is always expandable. Change in version 1.1: Also the meaning `\relax` is always considered “undefined”.

<code>\ltx@ifUndefined {<cmd>} {<yes>} {<no>}</code>
--

If $\varepsilon\text{-}\TeX$ is available, `\ifcsname` is used that does not have the side effect of defining undefined commands with meaning of `\relax`. Also it always checks for the meaning of `\relax` and considers this as undefined. This macro is not expandable without $\varepsilon\text{-}\TeX$.

<code>\ltx@LocalExpandAfter</code>

It expands the token after the next token but in a local context. That is the difference to `\expandafter`. The local context discards the side effect of `\csname` and let the command undefined after the expansion step.

1.12 Stripping

<code>\ltx@RemovePrefix</code> <code>\ltx@StripPrefix</code>

All tokens up to and including the next available character ‘>’ are thrown away. Usually it is used to strip the first part of the output of the commands `\meaning` or `\pdflastmatch`. Macro `\ltx@RemovePrefix` has the same meaning as L^AT_EX’s `\strip@prefix`, whereas macro `\ltx@StripPrefix` expands the next token once before stripping the prefix.

<code>\ltx@onelevel@sanitize {⟨macro⟩}</code>

Macro `\ltx@onelevel@sanitize` provides L^AT_EX’s `\@onelevel@sanitize`. The macro is expanded once and the contents is converted to characters with catcode 12 (other) and space tokens with catcode 10 (space). Then the sanitized contents is stored into the macro again. Since version 1.12.

1.13 File management

All macros in this section are expandable like the counterparts of the L^AT_EX kernel. Also they can be used after the preamble.

1.13.1 File extensions

<code>\ltx@clsextension</code> <code>\ltx@pkgextension</code>
--

Macros `\ltx@clsextension` and `\ltx@styextension` stores the strings `cls` and `sty`. In opposite to L^AT_EX’s `\@clsextension` and `\@styextension` they can also be used after `\begin{document}`.

1.13.2 Load check

<code>\ltx@ifclassloaded {⟨class⟩} {⟨yes⟩} {⟨no⟩}</code> <code>\ltx@ifpackageloaded {⟨package⟩} {⟨yes⟩} {⟨no⟩}</code>
--

Macros `\ltx@ifclassloaded`/`\ltx@ifpackageloaded` execute `⟨yes⟩`, if the `⟨class⟩` or `⟨package⟩` is loaded, otherwise `⟨no⟩` is called. Both `⟨class⟩` and `⟨package⟩` are specified without extension. The macros can also be used after `\begin{document}`.

<code>\ltx@iffileloaded {⟨file⟩} {⟨yes⟩} {⟨no⟩}</code>
--

If L^AT_EX’s `\ProvidesFile` macro was called before using `⟨file⟩` as argument, then `\ltx@iffileloaded` calls `⟨yes⟩`, otherwise `⟨no⟩`. Therefore it is possible that the `⟨file⟩` is loaded, but `⟨no⟩` is executed because of a missing `\ProvidesFile`. The L^AT_EX kernel does not have a counterpart of `\ltx@iffileloaded`.

Note that the file name used in `\ProvidesFile` and `\ltx@iffileloaded` must match. For example, if T_EX’s default extension `.tex` was given in the first command, then it must also be specified in the latter command and vice versa.

1.13.3 Version date check

<pre>\ltx@ifclasslater {<class>} {<date>} {<yes>} {<no>} \ltx@ifpackagelater {<package>} {<date>} {<yes>} {<no>} \ltx@iffilelater {<file>} {<date>} {<yes>} {<no>}</pre>
--

If a `\ProvidesClass`/`\ProvidesPackage`/`\ProvidesFile` command with exact the same class/package/file was executed before with an optional argument that starts with a L^AT_EX version date, then this version date is compared with the argument `<date>`. If they are equal or if the version date is the later date, then `<yes>` is called. In all other cases `<no>` is executed.

A L^AT_EX date has the format YYYY/MM/DD with YYYY as year with four digits, MM as month with two digits and DD as day with two digits. If pdfT_EX's `\pdfmatch` is available, then it is used to detect the version date, to reject invalid date formats and to reject some invalid dates. Dates before 1994/01/01 are always invalid, because version dates are introduced with L^AT_EX 2_ε in 1994.

1.14 Macro additions

<pre>\ltx@GlobalAppendToMacro {<cmd>} {<addition>} \ltx@LocalAppendToMacro {<cmd>} {<addition>}</pre>

The `<addition>` is appended to the parameterless macro `<cmd>`. If `<cmd>` is undefined or has the meaning `\relax`, then it will be initialized as empty macro beforehand. Due to a bug `<addition>` must not contain `\par` before version 2010/10/25 v1.9.

<pre>\ltx@GlobalPrependToMacro {<cmd>} {<addition>} \ltx@LocalPrependToMacro {<cmd>} {<addition>}</pre>

The `<addition>` is prepended to the parameterless macro `<cmd>`. If `<cmd>` is undefined or has the meaning `\relax`, then it will be initialized as empty macro beforehand. The macros were added in version 2011/08/22 v1.21.

1.15 Next character detection

<pre>\ltx@ifnextchar {<char>} {<yes>} {<no>}</pre>
--

If next character is `<char>` then `<yes>` is called, otherwise `<no>`. The character is not removed. Spaces are silently removed when looking for `<char>` as L^AT_EX's version `\kernel@ifnextchar` does. But there are also small differences:

- The space can be used as `<char>`. In this case optional spaces before `<char>` are not supported of course.
- If the optional space is a command that is a character (defined by `\let` or `\futurelet`), then `\kernel@ifnextchar` breaks with an T_EX error. `\ltx@ifnextchar` silently removes this token as optional space.

Since 2010/03/01 v1.3.

`\ltx@ifnextchar@nospace {<char>} {<yes>} {<no>}`

Macro `\ltx@ifnextchar@nospace` behaves like macro `\ltx@ifnextchar` with the exception that optional spaces are not supported before `<char>`. Since 2011/04/14 v1.19.

1.16 `\ltx@leavevmode`, `\ltx@mbox`

`\ltx@leavevmode`

Macro `\ltx@leavevmode` calls pdfTeX's `\quitvmode`. Otherwise `\leavevmode` is used and defined if it is necessary.

`\ltx@mbox`

Macro `\ltx@mbox` reimplements `\mbox` with two changes. Instead of `\leavevmode` it uses `\ltx@leavevmode` and stops right after `\hbox`. Especially it does not grab the argument and allows the extended syntax of `\hbox`.

1.17 Expandable test for emptiness

`\ltx@ifempty {<stuff>} {<yes>} {<no>}`

Macro `\ltx@ifempty` checks in exact two expansion steps whether `<stuff>` is empty or contains token. Depending on the result `<yes>` or `<no>` is executed. The token in `<stuff>` may contain `\par` and unmatched conditionals (`\if`, `\else`, `\fi`, ...). Since version 2010/11/12 v1.11.

`\ltx@ifblank {<stuff>} {<yes>} {<no>}`

Macro `\ltx@ifblank` tests in exact two expansion steps if `<stuff>` is empty or contain only blank spaces. In this case argument `<yes>` is called. If `<stuff>` contains other tokens than spaces then `<no>` is executed. Since version 2010/12/04 v1.13.

1.18 Stripping spaces

`\ltx@zapspace {<stuff>}`

Macro `\ltx@zapspace` strips spaces from `<stuff>` that are not hidden inside curly braces. Like L^AT_EX's `\zap@space` it is expandable. Differences:

- Syntax: `\zap@space` also expects a space token and `\@empty` after `<stuff>`.
- Macro `\ltx@zapspace` is expandable in exact two expansion steps.
- Macro `\ltx@zapspace` always retains curly braces.
- Macro `\zap@space` has a bug. It stops stripping spaces after a token group in curly braces if the first two tokens inside the group are equal.
- Macro `\ltx@zapspace` also works with `\par` and conditionals (`\if`, `\else`, `\fi`, ...).

Macro `\ltx@zapspace` is available since version 2010/12/07 v1.14.

1.19 Check for emptiness of boxes

`\ltx@ifboxempty {<box register number>} {<yes>} {<no>}`

Macro `\ltx@ifboxempty` calls `<yes>` if the box exists (`\ifvoid` returns false) and the box does not contain any content. Otherwise if the box is void or contains something, then `<no>` is executed. Thus being empty means that the box exists and is either an `\hbox` or a `\vbox` and may even have dimensions other than 0.0 pt, but the box does not contain anything. Macro `\ltx@ifboxempty` is available since 2010/02/04 v1.16.

`\ltx@ifboxvoidoreempty {<box register number>} {<yes>} {<no>}`

Macro `\ltx@ifboxvoidoreempty` calls `<yes>` if the box is either void or does not contain any content. Otherwise `<no>` is executed. Macro `\ltx@ifboxvoidoreempty` is available since 2010/02/04 v1.16.

2 Implementation

2.1 Identification

```
1 <*package>
```

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@ltxcmds.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17   \def\empty{}%
18   \ifx\x\empty % LaTeX, first loading,
19     % variable is initialized, but \ProvidesPackage not yet seen
20   \else
21     \expandafter\ifx\csname PackageInfo\endcsname\relax
22       \def\x#1#2{%
23         \immediate\write-1{Package #1 Info: #2.}%
24       }%
25     \else
26       \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27     \fi
28     \x{ltxcmds}{The package is already loaded}%
29   \aftergroup\endinput
30 \fi
31 \fi
32 \endgroup%
```

Package identification:

```

33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^~M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51 \def\x#1#2#3[#4]{\endgroup
52 \immediate\write-1{Package: #3 #4}%
53 \xdef#1{#4}%
54 }%
55 \else
56 \def\x#1#2[#3]{\endgroup
57 #2[#3]}%
58 \ifx#1\@undefined
59 \xdef#1{#3}%
60 \fi
61 \ifx#1\relax
62 \xdef#1{#3}%
63 \fi
64 }%
65 \fi
66 \expandafter\x\csname ver@ltxcmds.sty\endcsname
67 \ProvidesPackage{ltxcmds}%
68 [2016/05/16 v1.23 LaTeX kernel commands for general use (HO)]%
69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70 \catcode13=5 % ^~M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76 \expandafter\edef\csname LTXcmds@AtEnd\endcsname{%
77 \endlinechar=\the\endlinechar\relax
78 \catcode13=\the\catcode13\relax
79 \catcode32=\the\catcode32\relax
80 \catcode35=\the\catcode35\relax
81 \catcode61=\the\catcode61\relax
82 \catcode64=\the\catcode64\relax
83 \catcode123=\the\catcode123\relax
84 \catcode125=\the\catcode125\relax
85 }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^~M
89 \endlinechar=13 %

```

```

90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95   \edef\LTXcmds@AtEnd{%
96     \LTXcmds@AtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{36}{3}% $
102 \TMP@EnsureCode{38}{4}% &
103 \TMP@EnsureCode{40}{12}% (
104 \TMP@EnsureCode{41}{12}% )
105 \TMP@EnsureCode{45}{12}% -
106 \TMP@EnsureCode{46}{12}% .
107 \TMP@EnsureCode{47}{12}% /
108 \TMP@EnsureCode{60}{12}% <
109 \TMP@EnsureCode{62}{12}% >
110 \TMP@EnsureCode{91}{12}% [
111 \TMP@EnsureCode{96}{12}% '
112 \TMP@EnsureCode{93}{12}% ]
113 \TMP@EnsureCode{94}{12}% ^ (superscript) (!)
114 \TMP@EnsureCode{124}{12}% |
115 \edef\LTXcmds@AtEnd{\LTXcmds@AtEnd\noexpand\endinput}

```

2.2 Numbers

```

\ltx@zero
116 \chardef\ltx@zero=0 %

\ltx@one
117 \chardef\ltx@one=1 %

\ltx@two
118 \chardef\ltx@two=2 %

\ltx@active
119 \chardef\ltx@active=13 %

\ltx@cclv
120 \chardef\ltx@cclv=255 %

\ltx@minusone
121 \def\ltx@minusone{%
122   -\ltx@one
123 }

```

2.3 Scratch registers

```

\ltx@LocToksA
124 \toksdef\ltx@LocToksA=0 %

\ltx@LocToksB
125 \toksdef\ltx@LocToksB=2 %

```

```

\ltx@LocToksC
126 \toksdef\ltx@LocToksC=4 %

\ltx@LocToksD
127 \toksdef\ltx@LocToksD=6 %

\ltx@LocToksE
128 \toksdef\ltx@LocToksE=8 %

\ltx@GlobToksA
129 \toksdef\ltx@GlobToksA=1 %

\ltx@GlobToksB
130 \toksdef\ltx@GlobToksB=3 %

\ltx@GlobToksC
131 \toksdef\ltx@GlobToksC=5 %

\ltx@GlobToksD
132 \toksdef\ltx@GlobToksD=7 %

\ltx@GlobToksE
133 \toksdef\ltx@GlobToksE=9 %

\ltx@LocDimenA
134 \dimendef\ltx@LocDimenA=0 %

\ltx@LocDimenB
135 \dimendef\ltx@LocDimenB=2 %

\ltx@LocDimenC
136 \dimendef\ltx@LocDimenC=4 %

\ltx@LocDimenD
137 \dimendef\ltx@LocDimenD=6 %

\ltx@LocDimenE
138 \dimendef\ltx@LocDimenE=8 %

\ltx@GlobDimenA
139 \dimendef\ltx@GlobDimenA=1 %

\ltx@GlobDimenB
140 \dimendef\ltx@GlobDimenB=3 %

\ltx@GlobDimenC
141 \dimendef\ltx@GlobDimenC=5 %

\ltx@GlobDimenD
142 \dimendef\ltx@GlobDimenD=7 %

\ltx@GlobDimenE
143 \dimendef\ltx@GlobDimenE=9 %

\ltx@LocSkipA
144 \skipdef\ltx@LocSkipA=0 %

```

```

\ltx@LocSkipB
145 \skipdef\ltx@LocSkipB=2 %

\ltx@LocSkipC
146 \skipdef\ltx@LocSkipC=4 %

\ltx@LocSkipD
147 \skipdef\ltx@LocSkipD=6 %

\ltx@LocSkipE
148 \skipdef\ltx@LocSkipE=8 %

\ltx@GlobSkipA
149 \skipdef\ltx@GlobSkipA=1 %

\ltx@GlobSkipB
150 \skipdef\ltx@GlobSkipB=3 %

\ltx@GlobSkipC
151 \skipdef\ltx@GlobSkipC=5 %

\ltx@GlobSkipD
152 \skipdef\ltx@GlobSkipD=7 %

\ltx@GlobSkipE
153 \skipdef\ltx@GlobSkipE=9 %

```

2.4 Argument killers

```

\ltx@gobble
154 \long\def\ltx@gobble#1{}

\ltx@gobbletwo
155 \long\def\ltx@gobbletwo#1#2{}

\ltx@gobblethree
156 \long\def\ltx@gobblethree#1#2#3{}

\ltx@gobblefour
157 \long\def\ltx@gobblefour#1#2#3#4{}

\ltx@GobbleNum
158 \def\ltx@GobbleNum#1{%
159   \romannumeral
160   \csname ltx@zero%
161   \expandafter\LTXcmds@GobbleNum
162   \romannumeral\LTXcmds@num{#1}000{m\endcsname}%
163 }

\LTXcmds@GobbleNum
164 \def\LTXcmds@GobbleNum#1{%
165   \csname LTXcmds@G#1\LTXcmds@GobbleNum
166 }

\LTXcmds@Gm
167 \long\def\LTXcmds@Gm#1{%
168   \endcsname
169 }

```

2.5 Argument grabbers

```
\ltx@firstofone
170 \long\def\ltx@firstofone#1{#1}

\ltx@firstoftwo
171 \long\def\ltx@firstoftwo#1#2{#1}

\ltx@secondoftwo
172 \long\def\ltx@secondoftwo#1#2{#2}

\ltx@firstofthree
173 \long\def\ltx@firstofthree#1#2#3{#1}

\ltx@secondofthree
174 \long\def\ltx@secondofthree#1#2#3{#2}

\ltx@thirdofthree
175 \long\def\ltx@thirdofthree#1#2#3{#3}%

\ltx@firstoffour
176 \long\def\ltx@firstoffour#1#2#3#4{#1}

\ltx@secondoffour
177 \long\def\ltx@secondoffour#1#2#3#4{#2}

\ltx@thirdoffour
178 \long\def\ltx@thirdoffour#1#2#3#4{#3}%

\ltx@fourthoffour
179 \long\def\ltx@fourthoffour#1#2#3#4{#4}%
```

2.6 List helpers

```
\ltx@carzero
180 \long\def\ltx@carzero#1\@nil{}%

\LTxcmds@cdrzero
181 \long\def\LTxcmds@cdrzero#1\@nil{#1}

\ltx@cdrzero
182 \def\ltx@cdrzero{%
183   \romannumeral\LTxcmds@cdrzero\ltx@zero
184 }

\ltx@car
185 \long\def\ltx@car#1#2\@nil{#1}

\ltx@cdr
186 \long\def\ltx@cdr#1{%
187   \romannumeral\LTxcmds@cdrzero\ltx@zero
188 }

\ltx@cartwo
189 \long\def\ltx@cartwo#1#2#3\@nil{#1#2}
```

```

\ltx@carsecond
    190 \long\def\ltx@carsecond#1#2#3\@nil{#2}

\ltx@cdrtwo
    191 \long\def\ltx@cdrtwo#1#2{%
    192   \romannumeral\LTXcmds@cdrzero\ltx@zero
    193 }

\ltx@carthree
    194 \long\def\ltx@carthree#1#2#3#4\@nil{#1#2#3}

\ltx@carthird
    195 \long\def\ltx@carthird#1#2#3#4\@nil{#3}

\ltx@cdrthree
    196 \long\def\ltx@cdrthree#1#2#3{%
    197   \romannumeral\LTXcmds@cdrzero\ltx@zero
    198 }

\ltx@carfour
    199 \long\def\ltx@carfour#1#2#3#4#5\@nil{#1#2#3#4}

\ltx@carfourth
    200 \long\def\ltx@carfourth#1#2#3#4#5\@nil{#4}

\ltx@cdrfour
    201 \long\def\ltx@cdrfour#1#2#3#4{%
    202   \romannumeral\LTXcmds@cdrzero\ltx@zero
    203 }

\ltx@CarNum
    204 \def\ltx@CarNum#1{%
    205   \romannumeral
    206   \csname LTXcmds@CarNumFinish%
    207   \expandafter\LTXcmds@CarNum
    208   \romannumeral\LTXcmds@num{#1}000{x\endcsname}%
    209 }

\LTXcmds@CarNum
    210 \def\LTXcmds@CarNum#1{%
    211   \csname LTXcmds@C#1\LTXcmds@CarNum
    212 }

\LTXcmds@Cm
    213 \long\def\LTXcmds@Cm#1#2{%
    214   \endcsname{#1#2}%
    215 }

\LTXcmds@Cx
    216 \def\LTXcmds@Cx#1{%
    217   \endcsname{#1}%
    218 }

\LTXcmds@CarNumFinish
    219 \long\def\LTXcmds@CarNumFinish#1#2\@nil{%
    220   \ltx@zero
    221   #1%
    222 }

```


`\ltx@CarNumth`

```
223 \def\ltx@CarNumth#1{%
224   \romannumeral
225   \expandafter\expandafter\expandafter
226   \LTXcmds@CarNumth
227   \ltx@GobbleNum{#1}{}%
228 }
```

`\LTXcmds@CarNumth`

```
229 \long\def\LTXcmds@CarNumth#1#2\@nil{%
230   \ltx@zero
231   #1%
232 }
```

`\ltx@CdrNum`

```
233 \def\ltx@CdrNum#1{%
234   \romannumeral%
235   \expandafter\expandafter\expandafter\ltx@cdrzero
236   \expandafter\expandafter\expandafter\ltx@zero
237   \ltx@GobbleNum{#1}%
238 }
```

2.7 Tail recursion

`\ltx@ReturnAfterFi`

```
239 \long\def\ltx@ReturnAfterFi#1\fi{\fi#1}
```

`\ltx@ReturnAfterElseFi`

```
240 \long\def\ltx@ReturnAfterElseFi#1\else#2\fi{\fi#1}
```

2.8 Empty macro

`\ltx@empty`

```
241 \def\ltx@empty{}
```

2.9 Characters

`\ltx@space`

```
242 \def\ltx@space{ }
```

`\ltx@percentchar`

```
243 \begingroup
244   \lccode'0='%\relax
245 \lowercase{\endgroup
246   \def\ltx@percentchar{0}%
247 }
```

`\ltx@backslashchar`

```
248 \begingroup
249   \lccode'0='\\relax
250 \lowercase{\endgroup
251   \def\ltx@backslashchar{0}%
252 }
```

\ltx@hashchar

```
253 \begingroup
254   \lccode'0='#\relax
255 \lowercase{\endgroup
256   \def\ltx@hashchar{0}%
257 }
```

\ltx@leftbracechar

```
258 \begingroup
259   \lccode'0='{%\relax
260 \lowercase{\endgroup
261   \def\ltx@leftbracechar{0}%
262 }
```

\ltx@rightbracechar

```
263 \begingroup
264   \lccode'0='}\relax
265 \lowercase{\endgroup
266   \def\ltx@rightbracechar{0}%
267 }
```

2.10 Boolean switch

\ltx@newif

```
268 \def\ltx@newif#1{%
269   \begingroup
270     \escapechar=-1 %
271   \expandafter\endgroup
272   \expandafter\LTXcmds@newif\string#1\@nil
273 }
```

\LTXcmds@newif

```
274 \begingroup
275   \escapechar=-1 %
276 \expandafter\endgroup
277 \expandafter\def\expandafter\LTXcmds@newif\string\if#1\@nil{%
278   \expandafter\edef\csname#1true\endcsname{%
279     \let
280     \expandafter\noexpand\csname if#1\endcsname
281     \noexpand\iftrue
282   }%
283   \expandafter\edef\csname#1false\endcsname{%
284     \let
285     \expandafter\noexpand\csname if#1\endcsname
286     \noexpand\iffalse
287   }%
288   \csname#1false\endcsname
289 }
```

\ltx@newglobalif

```
290 \def\ltx@newglobalif#1{%
291   \begingroup
292     \escapechar=-1 %
293   \expandafter\endgroup
294   \expandafter\LTXcmds@newglobalif\string#1\@nil
295 }
```

\LTXcmds@newglobalif

```
296 \begingroup
297   \escapechar=-1 %
298 \expandafter\endgroup
299 \expandafter
300 \def\expandafter\LTXcmds@newglobalif\string\if#1\@nil{%
301   \expandafter\edef\csname#1true\endcsname{%
302     \global\let
303     \expandafter\noexpand\csname if#1\endcsname
304     \noexpand\iftrue
305   }%
306   \expandafter\edef\csname#1false\endcsname{%
307     \global\let
308     \expandafter\noexpand\csname if#1\endcsname
309     \noexpand\iffalse
310   }%
311   \csname#1false\endcsname
312 }
```

2.11 Command definitions

\ltx@LocalExpandAfter

```
313 \def\ltx@LocalExpandAfter{%
314   \begingroup
315     \expandafter\expandafter\expandafter
316   \endgroup
317   \expandafter
318 }
```

```
319 \ltx@LocalExpandAfter
320 \ifx\csname ifcsname\endcsname\relax
```

\ltx@ifundefined

```
321 \def\ltx@ifundefined#1{%
322   \expandafter\ifx\csname #1\endcsname\relax
323     \expandafter\ltx@firstoftwo
324   \else
325     \expandafter\ltx@secondoftwo
326   \fi
327 }
```

\ltx@ifundefined

```
328 \def\ltx@ifundefined#1{%
329   \begingroup\expandafter\expandafter\expandafter\endgroup
330   \expandafter\ifx\csname #1\endcsname\relax
331     \expandafter\ltx@firstoftwo
332   \else
333     \expandafter\ltx@secondoftwo
334   \fi
335 }%

336 \expandafter\ltx@gobble
337 \else
338   \expandafter\ltx@firstofone
339 \fi
340 {%
```

`\ltx@ifundefined`

```
341 \def\ltx@ifundefined#1{%
342   \ifcsname #1\endcsname
343   \expandafter\ifx\csname #1\endcsname\relax
344   \expandafter\expandafter\expandafter\ltx@firstoftwo
345   \else
346   \expandafter\expandafter\expandafter\ltx@secondoftwo
347   \fi
348   \else
349   \expandafter\ltx@firstoftwo
350   \fi
351 }%
```

`\ltx@ifUndefined`

```
352 \let\ltx@ifUndefined\ltx@ifundefined
353 }
```

2.12 Stripping

`\ltx@RemovePrefix`

```
354 \def\ltx@RemovePrefix#1>{}
```

`\ltx@StripPrefix`

```
355 \def\ltx@StripPrefix{%
356   \expandafter\ltx@RemovePrefix
357 }
```

`\ltx@onelevel@sanitize`

```
358 \def\ltx@onelevel@sanitize#1{%
359   \edef#1{%
360     \expandafter
361     \ltx@RemovePrefix\meaning#1%
362   }%
363 }
```

2.13 File management

2.13.1 File extensions

`\ltx@clsextension`

```
364 \def\ltx@clsextension{cls}
```

`\ltx@pkgextension`

```
365 \def\ltx@pkgextension{sty}
```

2.13.2 Load check

`\ltx@iffileloaded`

```
366 \def\ltx@iffileloaded#1{%
367   \ltx@ifundefined{ver@#1}\ltx@secondoftwo\ltx@firstoftwo
368 }
```

`\ltx@ifclassloaded`

```
369 \def\ltx@ifclassloaded#1{%
370   \ltx@iffileloaded{#1.\ltx@clsextension}%
371 }
```

\ltx@ifpackageloaded

```
372 \def\ltx@ifpackageloaded#1{%
373   \ltx@iffileloaded{#1.\ltx@pkgextension}%
374 }
```

2.13.3 Version date check

\ltx@iffilelater

```
375 \def\ltx@iffilelater#1#2{%
376   \ltx@iffileloaded{#1}{%
377     \expandafter\LTXcmds@IfLater\expandafter{%
378       \number
379       \expandafter\expandafter\expandafter\LTXcmds@ParseVersion
380       \expandafter\expandafter\expandafter{%
381         \csname ver@#1\endcsname
382       }%
383     \expandafter}\expandafter{%
384       \number
385       \expandafter\LTXcmds@ParseVersion\expandafter{#2}%
386     }%
387   }\ltx@secondoftwo
388 }
```

\LTXcmds@IfLater

```
389 \def\LTXcmds@IfLater#1#2{%
390   \ifcase 0%
391     \ifnum#1<19940101 %
392     \else
393       \ifnum#2<19940101 %
394       \else
395         \ifnum#2>#1 %
396         \else
397           1%
398         \fi
399       \fi
400     \fi
401     \ltx@space
402     \expandafter\ltx@secondoftwo
403   \else
404     \expandafter\ltx@firstoftwo
405   \fi
406 }
```

\ltx@ifclasslater

```
407 \def\ltx@ifclasslater#1{%
408   \ltx@iffilelater{#1.\ltx@clsextension}%
409 }
```

\ltx@ifpackagelater

```
410 \def\ltx@ifpackagelater#1{%
411   \ltx@iffilelater{#1.\ltx@pkgextension}%
412 }
413 \ltx@ifundefined{pdfmatch}{%
```

\LTXcmds@ParseVersion

```
414   \def\LTXcmds@ParseVersion#1{%
415     \LTXcmds@@ParseVersion#10000/00/00\@nil
416   }%
```

\LTXcmds@ParseVersion

```
417 \def\LTXcmds@ParseVersion#1#2#3#4/#5#6/#7#8#9\nil{%
418   #1#2#3#4#5#6#7#8%
419 }%
420 }
```

\LTXcmds@ParseVersion

```
421 \def\LTXcmds@ParseVersion#1{%
422   \ifnum\pdfmatch{%
423     ~%
424     (199[4-9]|[2-9][0-9][0-9][0-9])/%
425     (0[1-9]|1[0-2])/%
426     (0[1-9]|[1-2][0-9]|3[0-1])%
427   }{#1}=1 %
428   \ltx@StripPrefix\pdflastmatch1 %
429   \ltx@StripPrefix\pdflastmatch2 %
430   \ltx@StripPrefix\pdflastmatch3 %
431   \else
432     0%
433   \fi
434 }%
435 }
```

2.14 Macro additions

\ltx@GlobalAppendToMacro

```
436 \long\def\ltx@GlobalAppendToMacro#1#2{%
437   \ifx\ltx@undefined#1%
438     \let#1\ltx@empty
439   \else
440     \ifx\relax#1%
441       \let#1\ltx@empty
442     \fi
443   \fi
444   \begingroup
445     \ltx@LocToksA\expandafter{#1#2}%
446     \xdef#1{\the\ltx@LocToksA}%
447   \endgroup
448 }
```

\ltx@LocalAppendToMacro

```
449 \long\def\ltx@LocalAppendToMacro#1#2{%
450   \global\let\LTXcmds@gtemp#1%
451   \ifx\ltx@undefined\LTXcmds@gtemp
452     \global\let\LTXcmds@gtemp\ltx@empty
453   \else
454     \ifx\relax\LTXcmds@gtemp
455       \global\let\LTXcmds@gtemp\ltx@empty
456     \fi
457   \fi
458   \begingroup
459     \ltx@LocToksA\expandafter{\LTXcmds@gtemp#2}%
460     \xdef\LTXcmds@gtemp{\the\ltx@LocToksA}%
461   \endgroup
462   \let#1\LTXcmds@gtemp
463 }
```

`\ltx@GlobalPrependToMacro`

```
464 \long\def\ltx@GlobalPrependToMacro#1#2{%
465   \ifx\ltx@undefined#1%
466     \let#1\ltx@empty
467   \else
468     \ifx\relax#1%
469       \let#1\ltx@empty
470     \fi
471   \fi
472   \begingroup
473     \ltx@LocToksA{#2}%
474     \ltx@LocToksB\expandafter{#1}%
475     \xdef#1{\the\ltx@LocToksA\the\ltx@LocToksB}%
476   \endgroup
477 }
```

`\ltx@LocalPrependToMacro`

```
478 \long\def\ltx@LocalPrependToMacro#1#2{%
479   \global\let\LTXcmds@gtemp#1%
480   \ifx\ltx@undefined\LTXcmds@gtemp
481     \global\let\LTXcmds@gtemp\ltx@empty
482   \else
483     \ifx\relax\LTXcmds@gtemp
484       \global\let\LTXcmds@gtemp\ltx@empty
485     \fi
486   \fi
487   \begingroup
488     \ltx@LocToksA{#2}%
489     \ltx@LocToksB\expandafter{\LTXcmds@gtemp}%
490     \xdef\LTXcmds@gtemp{\the\ltx@LocToksA\the\ltx@LocToksB}%
491   \endgroup
492   \let#1\LTXcmds@gtemp
493 }
```

2.15 Next character detection

`\ltx@ifnextchar`

```
494 \long\def\ltx@ifnextchar#1#2#3{%
495   \begingroup
496   \let\LTXcmds@CharToken= #1\relax
497   \ltx@LocToksA{\endgroup#2}%
498   \ltx@LocToksB{\endgroup#3}%
499   \futurelet\LTXcmds@LetToken\LTXcmds@ifnextchar
500 }
```

`\LTXcmds@ifnextchar`

```
501 \def\LTXcmds@ifnextchar{%
502   \ifx\LTXcmds@LetToken\LTXcmds@CharToken
503     \the\expandafter\ltx@LocToksA
504   \else
505     \expandafter
506       \ifx\csname\LTXcmds@LetToken\endcsname\LTXcmds@SpaceToken
507       \expandafter\expandafter\expandafter\LTXcmds@@ifnextchar
508     \else
509       \the\expandafter\expandafter\expandafter\ltx@LocToksB
510     \fi
511   \fi
512 }
```

`\LTXcmds@ifnextchar` `\futurelet` does not distinguish between a character and a command that is a character (defined by using `\let` or `\futurelet`). Therefore the space is caught by `\romannumeral` with negative character constant that gobbles one optional space.

```
513 \def\LTXcmds@ifnextchar{%
514   \expandafter\futurelet
515   \expandafter\LTXcmds@LetToken
516   \expandafter\LTXcmds@ifnextchar
517   \romannumeral-'\.%
518 }
```

`\LTXcmds@SpaceToken`

```
519 \ltx@firstofone{\let\LTXcmds@SpaceToken= } %
```

`\ltx@ifnextchar@nospace`

```
520 \long\def\ltx@ifnextchar@nospace#1#2#3{%
521   \begingroup
522   \let\LTXcmds@CharToken= #1\relax
523   \ltx@LocToksA{\endgroup#2}%
524   \ltx@LocToksB{\endgroup#3}%
525   \futurelet\LTXcmds@LetToken\LTXcmds@ifnextchar@nospace
526 }
```

`\LTXcmds@ifnextchar@nospace`

```
527 \def\LTXcmds@ifnextchar@nospace{%
528   \the
529   \ifx\LTXcmds@LetToken\LTXcmds@CharToken
530     \expandafter\ltx@LocToksA
531   \else
532     \expandafter\ltx@LocToksB
533   \fi
534 }
```

2.16 `\ltx@leavevmode`, `\ltx@mbox`

`\ltx@leavevmode`

```
535 \ltx@ifundefined{quitvmode}{%
536   \ltx@ifundefined{leavevmode}{%
537     \ltx@ifundefined{voidb@x}{%
538       \ltx@ifundefined{newbox}{%
539         \def\ltx@leavevmode{%
540           \begingroup
541             \setbox\ltx@zero=\hbox{}%
542           \begingroup
543             \setbox\ltx@zero=\hbox{\box\ltx@zero}%
544           \endgroup
545           \unhbox\ltx@zero
546         \endgroup
547       }%
548     }{%
549       \csname newbox\endcsname\LTXcmds@VoidBox
550       \ifvoid\LTXcmds@VoidBox
551       \else
552         \setbox\LTXcmds@VoidBox=\hbox{}%
553       \begingroup
554         \setbox\LTXcmds@VoidBox=\hbox{\box\LTXcmds@VoidBox}%
555       \endgroup
```



```

556         \fi
557         \def\ltx@leavevmode{\unhbox\LTxcmds@VoidBox}%
558     }%
559 }{%
560     \def\ltx@leavevmode{\unhbox\voidb@x}%
561 }%
562 }{%
563     \let\ltx@leavevmode\leavevmode
564 }%
565 }{%
566     \let\ltx@leavevmode\quitvmode
567 }

```

\ltx@mbox

```

568 \def\ltx@mbox{%
569     \ltx@leavevmode
570     \hbox
571 }

```

2.17 Help macros

\LTxcmds@num

```

572 \ltx@ifundefined{numexpr}{%
573     \def\LTxcmds@num#1{%
574         \expandafter\ltx@firstofone\expandafter{%
575             \number#1%
576         }%
577     }%
578 }{%
579     \def\LTxcmds@num#1{%
580         \expandafter\ltx@firstofone\expandafter{%
581             \the\numexpr#1%
582         }%
583     }%
584 }

```

2.18 Expandable test for emptiness

```

585 \ltx@ifundefined{detokenize}{%

```

2.18.1 Vanilla T_EX

\ltx@ifempty The macro is based on \@ifempty of Robert R. Schneck [1] and \@ifnull of Ulrich Diez [2]. There are three cases to consider:

1. #1 is empty,
2. #1 is not empty and the first token is not a begingroup character,
3. #1 starts with a begingroup character (catcode 1).

```

586 \def\LTxcmds@temp#1{%
587     \long\def\ltx@ifempty##1{%
588         \romannumeral0%
589         \iffalse{\fi
590             \expandafter\ltx@gobble\expandafter{%
591                 \expandafter{\string##1}%
592                 \expandafter\ltx@gobble\string
593             }%
594             \expandafter\ltx@firstofthree\expandafter
595             {\iffalse}\fi
596             \expandafter#1\ltx@secondoftwo

```

```

597     }%
598     \expandafter#1\ltx@firstoftwo
599 }%

\ltx@ifblank
600 \long\def\ltx@ifblank##1{%
601   \romannumeral0%
602   \iffalse{\fi
603     \expandafter\expandafter\expandafter\ltx@gobble
604     \expandafter\expandafter\expandafter{%
605       \expandafter\expandafter\expandafter{%
606         \expandafter\string\ltx@gobble##1.%
607       }%
608       \expandafter\ltx@gobble\string
609     }%
610     \expandafter\ltx@firstofthree\expandafter
611     {\iffalse}\fi
612     \expandafter#1\ltx@secondoftwo
613   }%
614   \expandafter#1\ltx@firstoftwo
615 }%
616 }%
617 \LTXcmds@temp{ }%

618 }{%

```

2.18.2 With \detokenize

Ahmed Musa provided `\ifstrempy` using `\detokenize` and `\pdfstrcmp` [3]. Ulrich Diez, GL, Heiko Oberdiek improved it further by removing `\pdfstrcmp` and taking three arguments [4, 5, 6, 7, 8].

```

\ltx@ifempty
619 \long\def\ltx@ifempty#1{%
620   \romannumeral%
621   \csname
622     LTXcmds@ifempty%
623     \ifcat$\detokenize{#1}$%
624     @%
625     \fi
626   \endcsname
627 }%

\LTXcmds@ifempty@
628 \long\def\LTXcmds@ifempty@#1#2{0 #1}%

\LTXcmds@ifempty
629 \long\def\LTXcmds@ifempty#1#2{0 #2}%

```

2.18.3 \ltx@ifblank

```

\ltx@ifblank
630 \long\def\ltx@ifblank#1{%
631   \romannumeral%
632   \csname
633     LTXcmds@ifempty%
634     \ifcat$\detokenize\expandafter{\ltx@gobble#1.}$%

```

```

635      @%
636      \fi
637      \endcsname
638    }%

639 }

```

2.19 \ltx@zapspace

\ltx@zapspace

```

640 \long\def\ltx@zapspace#1{%
641   \romannumeral
642   \LTxcmds@zapspace\ltx@zero#1 \@nil
643 }

```

\LTxcmds@zapspace

```

644 \long\def\LTxcmds@zapspace#1 #2\@nil{%
645   \ltx@ifempty{#2}{%
646     #1%
647   }{%
648     \LTxcmds@zapspace#1#2\@nil
649   }%
650 }

```

2.20 \ltx@ifboxempty

In case of ε -TeX the test for an empty box is done via `\lastnodetype` as suggested by David Kastrup [9].

```

651 \ltx@ifundefined{lastnodetype}{%
652   \catcode'\$=9 %
653   \catcode'\&=14 %
654 }{%
655   \catcode'\$=14 %
656   \catcode'\&=9 %
657 }

```

\ltx@ifboxempty

```

658 \def\ltx@ifboxempty#1{%
659   \ifvoid#1\relax
660   \expandafter\ltx@secondoftwo
661   \else

```

Implementation using ε -TeX's `\lastnodetype`.

```

662 & \begingroup
663 &   \setbox\ltx@zero=\ifhbox#1\hbox\else\vbox\fi{%
664 &     \ifhmode\unhcopy\else\unvcopy\fi#1\relax
665 &     \expandafter
666 &   }%
667 & \expandafter\endgroup
668 & \ifnum\lastnodetype<\ltx@zero
669 &   \expandafter\expandafter\expandafter\ltx@firstoftwo
670 & \else
671 &   \expandafter\expandafter\expandafter\ltx@secondoftwo
672 & \fi

```

Implementation without ε -TeX using a signature at the beginning of the test box.

```

673 $ \begingroup
674 $   \setbox\ltx@zero=\ifhbox#1\hbox\else\vbox\fi{%

```

```

675 $      \penalty\ltx@one
676 $      \ifhmode\unhcopy\else\unvcopy\fi#1\relax
677 $      \expandafter
678 $      }%
679 $      \ifnum\lastpenalty=\ltx@one
Box 0 has been changed and is restored by closing the group.
680 $      \endgroup
681 $      \begingroup
682 $      \setbox\ltx@zero=\ifhbox#1\hbox\else\vbox\fi{%
683 $          \penalty\ltx@two
684 $          \ifhmode\unhcopy\else\unvcopy\fi#1\relax
685 $          \expandafter
686 $          }%
687 $          \ifnum\lastpenalty=\ltx@two
688 $          \def\next{\endgroup\expandafter\ltx@firstoftwo}%
689 $          \else
690 $          \def\next{\endgroup\expandafter\ltx@secondoftwo}%
691 $          \fi
692 $      \else
693 $      \def\next{\endgroup\expandafter\ltx@secondoftwo}%
694 $      \fi
695 $      \next
696 \fi
697 }

```

`\ltx@ifboxvoidoreempty`

```

698 \def\ltx@ifboxvoidoreempty#1{%
699   \ifvoid#1\relax
700     \expandafter\ltx@thirdoffour
701   \fi
702   \ltx@ifboxempty{#1}%
703 }

704 \LTXcmds@AtEnd%
705 \endpackage

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/ltxcmds.dtx](https://ctan.org/ctan/ctan:macros/latex/contrib/oberdiek/ltxcmds.dtx) The source file.

[CTAN:macros/latex/contrib/oberdiek/ltxcmds.pdf](https://ctan.org/ctan/ctan:macros/latex/contrib/oberdiek/ltxcmds.pdf) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](https://ctan.org/ctan/ctan:install/macros/latex/contrib/oberdiek.tds.zip)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:pkg/texmf](https://ctan.org/ctan:pkg/texmf)). Directories with `texmf` in their name are usually organized this way.

¹[CTAN:pkg/ltxcmds](https://ctan.org/ctan:pkg/ltxcmds)

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TeX`:

```
tex ltxcmds.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
ltxcmds.sty → tex/generic/oberdiek/ltxcmds.sty
ltxcmds.pdf → doc/latex/oberdiek/ltxcmds.pdf
ltxcmds.dtx → source/latex/oberdiek/ltxcmds.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your `TeX` distribution (`TeX Live`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `TeX Live` users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain `TeX`: Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{ltxcmds.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf \LaTeX` :

```
pdflatex ltxcmds.dtx
makeindex -s gind.ist ltxcmds.idx
pdflatex ltxcmds.dtx
makeindex -s gind.ist ltxcmds.idx
pdflatex ltxcmds.dtx
```

4 References

- [1] Robert R. Schneck: *Re: \ifempty solution (was Macro puzzle: maximally general \ifempty)*; newsgroup `comp.text.tex`, `news:3eef1ada_6@corp.newsgroups.com`, 2003-06-17.
<https://groups.google.com/group/comp.text.tex/msg/be03a159ec374895>
- [2] Ulrich Diez: *Re: TeX refuses to strip outer braces in argument*; newsgroup `comp.text.tex`, `news:ibk3t8$ee7$1@news.albasani.net`, 2010-11-12.
<https://groups.google.com/group/comp.text.tex/msg/803bd57221a04996>
- [3] Ahmed Musa: *Re: TeX refuses to strip outer braces in argument*; newsgroup `comp.text.tex`, `news:f5496afe-40ed-42bd-b629-a2419ecf7c0d@o14g2000prn.googlegroups.com`, 2010-12-03.
<https://groups.google.com/group/comp.text.tex/msg/fbf7d61a0c3a807d>
- [4] Ulrich Diez: *Re: TeX refuses to strip outer braces in argument*; newsgroup `comp.text.tex`, `news:idbo94uka1@four.albasani.net`, 2010-12-03.
<https://groups.google.com/group/comp.text.tex/msg/0c230ee479487962>
- [5] Ulrich Diez: *Re: TeX refuses to strip outer braces in argument*; newsgroup `comp.text.tex`, `news:idbpu4cgl1@news.albasani.net`, 2010-12-03.
<https://groups.google.com/group/comp.text.tex/msg/bbef4263390d647b>
- [6] Ulrich Diez: *Re: TeX refuses to strip outer braces in argument*; newsgroup `comp.text.tex`, `news:idd4ga$r83$1@four.albasani.net`, 2010-12-04.
<https://groups.google.com/group/comp.text.tex/msg/00dfd1ec103cd272>
- [7] GL: *Re: TeX refuses to strip outer braces in argument*; newsgroup `comp.text.tex`, `news:4cfa2e27$0$7389$426a74cc@news.free.fr`, 2010-12-04.
<https://groups.google.com/group/comp.text.tex/msg/d3a75995c1cf267e>
- [8] Heiko Oberdiek: *Re: TeX refuses to strip outer braces in argument*; newsgroup `comp.text.tex`, `news:iddhq1$3kj$1@news.eternal-september.org`, 2010-12-04.
<https://groups.google.com/group/comp.text.tex/msg/5f7a23e3ab70e347>
- [9] David Kastrup: *How to detect if \vbox is empty*; newsgroup `comp.text.tex`, 2011-02-04.
<https://groups.google.com/group/comp.text.tex/msg/8d3cb89496a4d86d>

5 History

[2009/08/05 v1.0]

- First version.

[2009/12/12 v1.1]

- Short title shortened.
- `\ltx@ifundefined` added.

[2010/01/28 v1.2]

- `\ltx@RemovePrefix` and `\ltx@StripPrefix` added.
- `\ltx@ifclassloaded`, `\ltx@ifpackageloaded`, `\ltx@iffileloaded`, `\ltx@ifclasslater`, `\ltx@ifpackagelater`, `\ltx@iffilelater`, `\ltx@clsextension`, `\ltx@pkgextension` added.
- `\ltx@GlobalAppendToMacro`, `\ltx@LocalAppendToMacro` added.

[2010/03/01 v1.3]

- `\ltx@newif` added.
- `\ltx@ifnextchar` added.
- Numbers `\ltx@zero`, `\ltx@one`, `\ltx@two`, `\ltx@cclv` added.

[2010/03/09 v1.4]

- `\ltx@pkgextension` and `\ltx@clsextension` are hardcoded to avoid trouble with `\@onlypreamble`.

[2010/04/08 v1.5]

- `\ltx@cartwo`, `\ltx@cdrtwo`, `\ltx@carthree`, `\ltx@cdrthree`, `\ltx@carfour`, `\ltx@cdrfour` added.
- `\ltx@ReturnAfterFi` and `\ltx@ReturnAfterElseFi` fixed.

[2010/04/16 v1.6]

- `\ltx@leavevmode`, `\ltx@mbox` added.

[2010/04/26 v1.7]

- `\ltx@GobbleNum`, `\ltx@CdrNum`, `\ltx@CarNum` added.
- `\ltx@carzero`, `\ltx@cdrzero` added.
- `\ltx@hashchar` added.

[2010/09/11 v1.8]

- `\ltx@leftbracechar`, `\ltx@rightbracechar` added.

[2010/10/25 v1.9]

- `\ltx@LocalAppendToMacro` and `\ltx@GlobalAppendToMacro` are now `\long`.

[2010/10/31 v1.10]

- `\ltx@newglobalif` added.

[2010/11/12 v1.11]

- `\ltx@ifempty` added.
- `\ltx@firstofthree`, `\ltx@secondofthree`, `\ltx@thirdofthree` added.

[2010/12/02 v1.12]

- `\ltx@onelevel@sanitize` added.
- `\LTXcmds@num` fixed for the case with `\numexpr` (bug found by GL).

[2010/12/04 v1.13]

- `\ltx@ifblank` added.
- Optimization for `\ltx@ifempty`.

[2010/12/07 v1.14]

- `\ltx@zapspace` added.

[2010/12/12 v1.15]

- `\ltx@minusone` added.

[2011/02/04 v1.16]

- `\ltx@ifBoxEmpty` and `\ltx@ifBoxVoidOrEmpty` added.
- `\ltx@firstoffour`, ..., `\ltx@fourthoffour` added.

[2011/02/05 v1.17]

- `\ltx@ifBoxEmpty`: an empty box may have non-zero dimensions.

[2011/03/16 v1.18]

- `\ltx@ifclasslater` fixed.

[2011/04/14 v1.19]

- `\ltx@ifnextchar`: detection of optional spaces modified.
- `\ltx(Loc,Glob)(Toks,Dimen,Skip)(A,B,C,D,E)` added.

[2011/04/18 v1.20]

- `\ltx@ifnextchar` with conditional support (thanks GL for bug report).

[2011/08/22 v1.21]

- `\ltx@GlobalPrependToMacro`, `\ltx@LocalPrependToMacro` added (feature request of Martin Münch).

[2011/11/09 v1.22]

- `\ltx@carsecond`, `\ltx@carthird`, `\ltx@carfourth`, `\ltx@CarNumth` added.
- `\ltx@cdrzero`, `\ltx@cdr`, `\ltx@cdrtwo`, `csltx@cdrthree`, `\ltx@cdrfour`, `\ltx@CdrNum` modified to retain braces and spaces. They are expandable in two expansion steps.

[2016/05/16 v1.23]

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	E
<code>\#</code> 254	<code>\empty</code> 17, 18
<code>\\$</code> 652, 655	<code>\endcsname</code> 14, 21, 50, 66,
<code>\%</code> 244	76, 162, 168, 208, 214, 217, 278,
<code>\&</code> 653, 656	280, 283, 285, 288, 301, 303,
<code>\.</code> 517	306, 308, 311, 320, 322, 330,
<code>\@nil</code> 180, 181, 185, 189, 190, 194, 195,	342, 343, 381, 506, 549, 626, 637
199, 200, 219, 229, 272, 277,	<code>\endinput</code> 29, 115
294, 300, 415, 417, 642, 644, 648	<code>\endlinechar</code> 4, 35, 71, 77, 89
<code>\@undefined</code> 58	<code>\escapechar</code> 270, 275, 292, 297
<code>\%</code> 249	
<code>\{</code> 259	F
<code>\}</code> 264	<code>\futurelet</code> 499, 514, 525
A	H
<code>\aftergroup</code> 29	<code>\hbox</code> 541,
	543, 552, 554, 570, 663, 674, 682
B	
<code>\box</code> 543, 554	
	I
C	<code>\if</code> 277, 300
<code>\catcode</code> 2, 3, 5, 6, 7, 8,	<code>\ifcase</code> 390
9, 10, 11, 12, 13, 33, 34, 36, 37,	<code>\ifcat</code> 623, 634
38, 39, 40, 41, 42, 43, 44, 45, 46,	<code>\ifcsname</code> 342
47, 48, 49, 69, 70, 72, 73, 74, 78,	<code>\iffalse</code> .. 286, 309, 589, 595, 602, 611
79, 80, 81, 82, 83, 84, 87, 88, 90,	<code>\ifhbox</code> 663, 674, 682
91, 92, 93, 97, 99, 652, 653, 655, 656	<code>\ifhmode</code> 664, 676, 684
<code>\chardef</code> 116, 117, 118, 119, 120	<code>\ifnum</code> 391, 393, 395, 422, 668, 679, 687
<code>\csname</code> 14, 21,	<code>\iftrue</code> 281, 304
50, 66, 76, 160, 165, 206, 211,	<code>\ifvoid</code> 550, 659, 699
278, 280, 283, 285, 288, 301,	<code>\ifx</code> . 15, 18, 21, 50, 58, 61, 320, 322,
303, 306, 308, 311, 320, 322,	330, 343, 437, 440, 451, 454,
330, 343, 381, 506, 549, 621, 632	465, 468, 480, 483, 502, 506, 529
	<code>\immediate</code> 23, 52
D	L
<code>\detokenize</code> 623, 634	<code>\lastnodetype</code> 668
<code>\dimendef</code> 134, 135, 136,	<code>\lastpenalty</code> 679, 687
137, 138, 139, 140, 141, 142, 143	<code>\lccode</code> 244, 249, 254, 259, 264

\leavevmode	563	\ltx@ifblank	9, 600, 630
\letLTXcmds@gtmp	455, 484	\ltx@ifBoxEmpty	10, 658, 702
\lowercase	245, 250, 255, 260, 265	\ltx@ifBoxVoidOrEmpty	10, 698
\ltx@(Loc, Glob)(Toks, Dimen, Skip)(A, B, C, D, E)	3	\ltx@ifclasslater	8, 407
\ltx@active	119	\ltx@ifclassloaded	7, 369
\ltx@backslashchar	248	\ltx@ifempty	9, 586, 619, 645
\ltx@car	5, 185	\ltx@iffilelater	375, 408, 411
\ltx@carfour	5, 199	\ltx@iffileloaded	7, 366, 370, 373, 376
\ltx@carfourth	200	\ltx@ifnextchar	8, 494
\ltx@CarNum	5, 204	\ltx@ifnextchar@nospace	9, 520
\ltx@CarNumth	223	\ltx@ifpackagelater	410
\ltx@carsecond	190	\ltx@ifpackageloaded	372
\ltx@carthird	195	\ltx@ifUndefined	6, 328, 352, 413, 535, 536, 537, 538, 572, 585, 651
\ltx@carthree	5, 194	\ltx@ifundefined	6, 321, 341, 352, 367
\ltx@cartwo	5, 189	\ltx@leavevmode	9, 535, 569
\ltx@carzero	5, 180	\ltx@leftbracechar	258
\ltx@cclv	120	\ltx@LocalAppendToMacro	449
\ltx@cdr	186	\ltx@LocalExpandAfter	6, 313, 319
\ltx@cdrfour	201	\ltx@LocalPrependToMacro	478
\ltx@CdrNum	233	\ltx@LocDimenA	134
\ltx@cdrthree	196	\ltx@LocDimenB	135
\ltx@cdrtwo	191	\ltx@LocDimenC	136
\ltx@cdrzero	182, 235	\ltx@LocDimenD	137
\ltx@clsextension	7, 364, 370, 408	\ltx@LocDimenE	138
\ltx@empty	6, 241, 438, 441, 452, 455, 466, 469, 481, 484	\ltx@LocSkipA	144
\ltx@firstoffour	176	\ltx@LocSkipB	145
\ltx@firstofone	4, 170, 338, 519, 574, 580	\ltx@LocSkipC	146
\ltx@firstofthree	173, 594, 610	\ltx@LocSkipD	147
\ltx@firstoftwo	171, 323, 331, 344, 349, 367, 404, 598, 614, 669, 688	\ltx@LocSkipE	148
\ltx@fourthoffour	179	\ltx@LocToksA	124, 445, 446, 459, 460, 473, 475, 488, 490, 497, 503, 523, 530
\ltx@GlobalAppendToMacro	8, 436	\ltx@LocToksB	125, 474, 475, 489, 490, 498, 509, 524, 532
\ltx@GlobalPrependToMacro	8, 464	\ltx@LocToksC	126
\ltx@GlobDimenA	139	\ltx@LocToksD	127
\ltx@GlobDimenB	140	\ltx@LocToksE	128
\ltx@GlobDimenC	141	\ltx@mbox	9, 568
\ltx@GlobDimenD	142	\ltx@minusone	121
\ltx@GlobDimenE	143	\ltx@newglobalif	6, 290
\ltx@GlobSkipA	149	\ltx@newif	6, 268
\ltx@GlobSkipB	150	\ltx@one	117, 122, 675, 679
\ltx@GlobSkipC	151	\ltx@onelevel@sanitize	7, 358
\ltx@GlobSkipD	152	\ltx@percentchar	243
\ltx@GlobSkipE	153	\ltx@pkgextension	365, 373, 411
\ltx@GlobToksA	129	\ltx@RemovePrefix	7, 354, 356, 361
\ltx@GlobToksB	130	\ltx@ReturnAfterElseFi	240
\ltx@GlobToksC	131	\ltx@ReturnAfterFi	5, 239
\ltx@GlobToksD	132	\ltx@rightbracechar	263
\ltx@GlobToksE	133	\ltx@secondoffour	177
\ltx@gobble	3, 154, 336, 590, 592, 603, 606, 608, 634	\ltx@secondofthree	174
\ltx@gobblefour	157	\ltx@secondoftwo	172, 325, 333, 346, 367, 387, 402, 596, 612, 660, 671, 690, 693
\ltx@GobbleNum	3, 158, 227, 237	\ltx@space	6, 242, 401
\ltx@gobblethree	156	\ltx@StripPrefix	355, 428, 429, 430
\ltx@gobbletwo	155	\ltx@thirdoffour	178, 700
\ltx@hashchar	253		

\ltx@thirdofthree	175	\numexpr	581
\ltx@two	118, 683, 687		
\ltx@undefined	437, 451, 465, 480	P	
\ltx@zapspace	9, 640	\PackageInfo	26
\ltx@zero	3, 116, 183, 187, 192, 197, 202, 220, 230, 236, 541, 543, 545, 642, 663, 668, 674, 682	\pdflastmatch	428, 429, 430
\LTXcmds@ifnextchar	507, 513	\pdfmatch	422
\LTXcmds@ParseVersion	415, 417	\penalty	675, 683
\LTXcmds@AtEnd	95, 96, 115, 704	\ProvidesPackage	19, 67
\LTXcmds@CarNum	207, 210	Q	
\LTXcmds@CarNumFinish	219	\quitvmode	566
\LTXcmds@CarNumth	226, 229		
\LTXcmds@cdrzero	181, 183, 187, 192, 197, 202	R	
\LTXcmds@CharToken	496, 502, 522, 529	\romannumeral	159, 162, 183, 187, 192, 197, 202, 205, 208, 224, 234, 517, 588, 601, 620, 631, 641
\LTXcmds@Cm	213		
\LTXcmds@Cx	216	S	
\LTXcmds@Gm	167	\setbox	541, 543, 552, 554, 663, 674, 682
\LTXcmds@GobbleNum	161, 164	\skipdef	144, 145, 146, 147, 148, 149, 150, 151, 152, 153
\LTXcmds@gtemp	450, 451, 452, 454, 459, 460, 462, 479, 480, 481, 483, 489, 490, 492	T	
\LTXcmds@ifempty	629	\the	77, 78, 79, 80, 81, 82, 83, 84, 97, 446, 460, 475, 490, 503, 509, 528, 581
\LTXcmds@ifempty@	628	\TMP@EnsureCode	94, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114
\LTXcmds@ifLater	377, 389	\toksdef	124, 125, 126, 127, 128, 129, 130, 131, 132, 133
\LTXcmds@ifnextchar	499, 501, 516		
\LTXcmds@ifnextchar@nospace	525, 527	U	
\LTXcmds@LetToken	499, 502, 515, 525, 529	\unhbox	545, 557, 560
\LTXcmds@newglobalif	294, 296	\unhcopy	664, 676, 684
\LTXcmds@newif	272, 274	\unvcopy	664, 676, 684
\LTXcmds@num	162, 208, 572	V	
\LTXcmds@ParseVersion	379, 385, 414, 421	\vbox	663, 674, 682
\LTXcmds@SpaceToken	506, 519	\voidb@x	560
\LTXcmds@temp	586, 617		
\LTXcmds@VoidBox	549, 550, 552, 554, 557	W	
\LTXcmds@zapspace	642, 644	\write	23, 52
M		X	
\meaning	361	\x	14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87
N			
\next	688, 690, 693, 695		
\number	378, 384, 575		