

# Lwarp

## LATEX HTML5

### The lwarp package

LATEX to HTML

v0.80 — 2020/02/19

© 2016–2020 Brian Dunn  
bd@BDTechConcepts.com

#### Abstract

The `lwarp` package converts LATEX to HTML by using LATEX to process the user's document and directly generate HTML tags. External utility programs are only used for the final conversion of text and images. Math may be represented by SVG images or MathJax. Hundreds of LATEX packages are supported.

Documents may be produced by DVI or PDF LATEX, LuaLATEX, XeLATEX; by several CJK engines, classes, and packages; or by customized systems such as `perltx` and `pythontex`. A `texlua` script automates compilation, index, glossary, and batch image processing, and also supports `latexmk`. Configuration is semi-automatic at the first manual compile. Support files are self-generated. Print and HTML versions of each document may coexist.

Assistance is provided for HTML import into EPUB conversion software and word processors.

Requirements include the commonly-available POPPLER utilities (included with MIKTEX) and PERL. Detailed installation instructions are included for each of the major operating systems and TEX distributions.

A quick-start tutorial is provided, as well as extensive documentation for special cases, a general index, and a troubleshooting index. Automatic error testing is provided for configuration files, package load order, and image generation.

SVG math and many other generated images include LATEX expressions in the alt tags. MATHJAX may be used with advanced equation numbering under the direct control of `lwarp`.

Complicated tables are supported, which copy/paste well into LIBREOFFICE WRITER.

Supported classes and packages include `memoir` and `koma-script`, `cleveref`, `caption`, `mdframed`, `siunitx`, and many popular packages for tabulars, floats, graphics, theorems, the title page, bibliography, indexing, footnotes, and editorial work, as well as a number of CJK-related classes and packages.

TEX is a self-modifying tokenized macro-expansion language. Since `lwarp` is written directly in LATEX, it is able to interpret the document's meaning at a deeper level than external conversions which merely approximate TEX. HTML5 and CSS3 are leveraged to provide advanced features such as `booktabs` trim, multicolumns, side-by-side minipages, and JAVASCRIPT-free navigation.

For a list of supported features, see [table 2: Supported packages and features](#).

To update existing projects, see [section 1: Updates](#).

**Lwarp is still in development. Changes are likely.**

#### License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

## Support TeX development

TeX and related projects:

- are mostly open-sourced and a volunteer effort;
- benefit students, academics, scientists, engineers, and businesses;
- help drive education, public and private research, and commercial activity;
- are used in the fields of mathematics, science, engineering, and humanities;
- are international in reach;
- span decades of development;
- are enduring — many older packages are still actively used and maintained;
- are largely backwards compatible;
- are portable across all the major computing platforms;
- are usable even on older computers and away from internet access;
- are continuing to maintain relevance with modern improvements;
- require no yearly subscription fees;
- and are supported by an active community of knowledgeable volunteers.

Please consider helping by joining and/or contributing to the TeX Users Group, a United States 501(c)(3) tax-exempt charitable organization. Contributions are accepted by credit card, check, or Pay Pal, via the United Way, or by USA or European bank transfer. Membership in TUG supports the development of TeXLive, the major TeX distribution.

Donations may be directed towards individual projects:

**TUG Bursary Fund:** Assistance for attending annual TUG meetings.

**CTAN:** The Comprehensive TeX Archive Network—Central storage for TeX.

**TeX Development Fund:** Support for specific projects.

**EduTeX:** Teaching and using TeX in schools and universities.

**GUST e-foundry fonts:** Enhanced for math and additional language groups.

**LaTeX Project:** Modernizing the L<sup>A</sup>T<sub>E</sub>X core.

**Libre Font Fund:** Fonts, tools (FontForge), and distribution (the Open Font Library).

**LuaTeX:** Combining the pdfTeX engine and the Lua language.

**MetaPost:** Postscript graphics.

**MacTeX:** TeX for Mac.

**PDF Accessibility:** Modern PDF standards.

**Other:** Additional projects may be specified.

To make a contribution:

<https://www.tug.org/donate.html>

For country-specific TeX users groups:

<http://tug.org/usergroups.html>

For users of MiKTeX:

<https://miktex.org/donations.html>

## Contents

<b>Support T<small>EX</small> development</b>	2
<b>List of Figures</b>	40
<b>List of Tables</b>	40
<b>1 Updates</b>	41
<b>2 Introduction</b>	65
2.1 Typesetting conventions	67
2.2 Supported packages and features	68
<b>3 Alternatives</b>	74
3.1 internet class	74
3.2 TEX4HT	74
3.3 Translators	74
3.4 ASCIIDOC and ASCIIDOCTOR	75
3.4.1 ASCIIDOCTOR-L <small>ATEX</small>	75
3.5 PANDOC	75
3.6 Word processors	75
3.7 Commercial systems	75
3.8 Comparisons	75
<b>4 Installation</b>	77
4.1 Installing the <i>lwarf</i> package	79
4.2 Installing the <i>lwarpmk</i> utility	80
4.2.1 Using a local copy of <i>lwarpmk</i>	82
4.3 Installing additional utilities	82
<b>5 Tutorial</b>	84
5.1 Starting a new project	84
5.2 Compiling the print version with <i>lwarpmk</i>	88
5.3 Compiling the HTML version with <i>lwarpmk</i>	89
5.4 Generating the SVG images	90

5.5	Using MATHJAX for math . . . . .	91
5.6	Changing the css style . . . . .	92
5.7	Customizing the HTML output . . . . .	92
5.8	Using <i>latexmk</i> . . . . .	93
5.9	Using X <sub>E</sub> LATEX or L <sub>A</sub> TEX . . . . .	94
5.10	Using DVI LATEX . . . . .	94
5.11	Using a glossary . . . . .	95
5.11.1	gloss package . . . . .	95
5.11.2	glossaries package . . . . .	95
5.12	Cleaning auxiliary files . . . . .	96
5.13	Cleaning auxiliary and output files . . . . .	96
5.14	Cleaning the images from the <project>-images directory . . . . .	96
5.15	Converting PDF or EPS images to svg . . . . .	96
5.16	Creating HTML from an incomplete compile . . . . .	96
5.17	Processing multiple projects in the same directory . . . . .	96
5.18	Using the <i>make</i> utility . . . . .	97
5.19	What next? . . . . .	98
6	Converting an existing document . . . . .	99
7	Additional details . . . . .	100
7.1	Localization . . . . .	100
7.2	Accessibility . . . . .	100
7.3	Shell escape . . . . .	101
7.4	Font and UTF-8 support . . . . .	101
7.4.1	Indexes, glossaries, and encoding . . . . .	103
7.5	lwarp package loading and options . . . . .	104
7.6	Customizing the HTML output . . . . .	109
7.6.1	Example HTML file naming . . . . .	115
7.7	Customizing the css . . . . .	115
7.8	Selecting the operating system . . . . .	117

7.9	Selecting actions for print, HTML, or MATHJAX output . . . . .	117
7.10	Commands to be placed into the <code>\warpprint</code> environment . . . . .	118
7.11	Title page . . . . .	119
7.12	HTML page meta descriptions . . . . .	119
7.13	HTML homepage meta title . . . . .	120
7.14	HTML page meta author . . . . .	120
<b>8</b>	<b>Special cases and limitations . . . . .</b>	<b>121</b>
8.1	Things to avoid . . . . .	121
8.1.1	Invalid HTML . . . . .	122
8.2	Formatting . . . . .	122
8.2.1	Text formatting . . . . .	122
8.2.2	Horizontal space . . . . .	122
8.2.3	Text alignment . . . . .	122
8.2.4	Accents. . . . .	123
8.2.5	<code>textcomp</code> package . . . . .	123
8.2.6	Superscripts and other non-math uses of math mode . . . . .	123
8.2.7	Empty <code>\item</code> followed by a new line of text or a nested list: . . . . .	123
8.2.8	Filenames and URLs in lists or footnotes . . . . .	123
8.2.9	<code>relsize</code> package . . . . .	123
8.3	Boxes and minipages . . . . .	124
8.3.1	<code>Marginpars</code> . . . . .	124
8.3.2	<code>Save Boxes</code> . . . . .	124
8.3.3	<code>Minipages</code> . . . . .	124
8.3.4	Side-by-side minipages . . . . .	125
8.3.5	Framed minipages and other environments . . . . .	125
8.3.6	<code>fancybox</code> package . . . . .	126
8.3.7	<code>mdframed</code> package . . . . .	127
8.4	Section names . . . . .	128

8.5	Cross-references . . . . .	129
8.5.1	Page references . . . . .	129
8.5.2	cleveref and varioref packages . . . . .	129
8.5.3	Hyperlinks, hyperref, and url . . . . .	130
8.5.4	Footnotes and page notes . . . . .	130
8.5.5	xr, xr-hyper, and xcite packages . . . . .	131
8.6	Front and back matter . . . . .	132
8.6.1	Custom classes with multiple authors and affiliations . . . . .	132
8.6.2	Starred chapters and sections . . . . .	132
8.6.3	abstract package . . . . .	133
8.6.4	titling and authblk . . . . .	133
8.6.5	tocloft package . . . . .	133
8.6.6	appendix package . . . . .	133
8.6.7	pagenote package . . . . .	133
8.6.8	endnotes package . . . . .	133
8.6.9	BibTeX . . . . .	134
8.6.10	xcite package. . . . .	134
8.6.11	gloss package . . . . .	134
8.6.12	glossaries package . . . . .	134
8.6.13	nomencn package . . . . .	135
8.6.14	Indexing overview . . . . .	135
8.6.15	Indexing with basic LATEX and makeidx. . . . .	136
8.6.16	Indexing with index . . . . .	137
8.6.17	Indexing with splitidx . . . . .	137
8.6.18	Indexing with imakeidx . . . . .	139
8.6.19	Indexes with memoir . . . . .	142
8.6.20	Using a custom makeindex style file . . . . .	145
8.6.21	Using a custom xindy style file. . . . .	146
8.6.22	Additional indexing limitations . . . . .	146

8.6.23	<b>Index positions, toc, tocbibind</b>	147
8.7	<b>Math</b>	148
8.7.1	<b>Math in section names</b>	148
8.7.2	<b>Rendering tradeoffs</b>	148
8.7.3	<b>svg option</b>	149
8.7.4	<b>MATHJAX option</b>	149
8.7.5	<b>Customizing MATHJAX</b>	150
8.7.6	<b>MATHJAX limitations</b>	151
8.7.7	<b>Catcode changes</b>	151
8.7.8	<b>Complicated inline math objects</b>	152
8.7.9	<b>Complicated display math objects</b>	152
8.7.10	<b>ntheorem package</b>	152
8.7.11	<b>mathtools package</b>	152
8.7.12	<b>siunitx package</b>	153
8.7.13	<b>units and nicefrac packages</b>	154
8.7.14	<b>physics package</b>	154
8.7.15	<b>newtxmath package</b>	155
8.8	<b>Graphics</b>	155
8.8.1	<b>tikz package</b>	156
8.8.2	<b>grffile package</b>	157
8.8.3	<b>color package</b>	157
8.8.4	<b>xcolor package</b>	157
8.8.5	<b>epstopdf package</b>	157
8.8.6	<b>pstricks package</b>	157
8.8.7	<b>pdftricks package</b>	158
8.8.8	<b>psfrag package</b>	158
8.8.9	<b>pstool package</b>	158
8.8.10	<b>asymptote package</b>	159
8.8.11	<b>overpic package</b>	159

8.8.12	Multimedia packages . . . . .	159
8.9	Tabbing . . . . .	160
8.10	Tabular . . . . .	160
8.10.1	tabular environment . . . . .	160
8.10.2	multirow package . . . . .	162
8.10.3	longtable package . . . . .	163
8.10.4	threeparttablex package . . . . .	163
8.10.5	supertabular and xtab packages . . . . .	164
8.10.6	colortbl package . . . . .	164
8.10.7	ctable package . . . . .	164
8.10.8	bigdelim package . . . . .	165
8.11	Floats . . . . .	165
8.11.1	Float contents alignment . . . . .	165
8.11.2	float, trivfloat, and/or algorithmicx together . . . . .	165
8.11.3	caption and subcaption packages . . . . .	165
8.11.4	subfig package . . . . .	166
8.11.5	floatrow package . . . . .	166
8.11.6	keyfloat package . . . . .	167
8.12	KOMA-SCRIPT classes . . . . .	167
8.13	MEMOIR class . . . . .	167
8.14	International languages . . . . .	168
8.15	Miscellaneous packages . . . . .	168
8.15.1	verse and memoir . . . . .	168
8.15.2	newclude package . . . . .	169
8.15.3	babel package . . . . .	169
8.15.4	polyglossia package . . . . .	169
8.15.5	todonotes and luatodonotes packages . . . . .	169
8.15.6	fixme . . . . .	170
8.15.7	chemfig package . . . . .	170

8.15.8	<b>chemformula package</b>	170
8.15.9	<b>mhchem package</b>	170
8.15.10	<b>xparse package</b>	170
8.15.11	<b>kotex package</b>	171
<b>9</b>	<b>Compiling using custom shell commands</b>	<b>172</b>
9.1	<b>Command options</b>	172
9.2	<b>Literal character macros</b>	172
9.3	<b>latexmk</b>	173
9.4	<b>perltex package</b>	174
9.5	<b>pythontex package</b>	174
9.6	<b>Other packages</b>	174
9.7	<b>make program</b>	175
9.8	<b>UTF-8 locale</b>	175
<b>10</b>	<b>EPUB conversion</b>	<b>176</b>
<b>11</b>	<b>Word-processor conversion</b>	<b>178</b>
11.1	<b>Activating word-processor conversion</b>	178
11.2	<b>Additional modifications</b>	179
11.3	<b>Recommendations</b>	181
11.4	<b>Limitations</b>	182
<b>12</b>	<b>Modifying l warp</b>	<b>183</b>
12.1	<b>Creating a development system</b>	183
12.2	<b>Modifying a package for l warp</b>	184
12.2.1	<b>Adding a package to the l warp.dtx file</b>	185
12.2.3	<b>Modifying a class for l warp</b>	185
12.4	<b>Testing l warp</b>	186
12.5	<b>Modifying l warpmk</b>	186
<b>13</b>	<b>Troubleshooting</b>	<b>188</b>
13.1	<b>l warp package error conditions and warnings</b>	188
13.1.1	<b>Configuration file l warpmk.conf</b>	188

13.1.2	Image generation with <code>l warpmk l images</code>	188
13.1.3	Default bitmapped font	189
13.1.4	Packages	189
13.1.5	Compiling	189
13.2	Using the <code>l warp</code> package	190
13.2.1	Debug tracing output	194
13.3	Compiling the <code>l warp.dtx</code> file	194
14	Trademarks	195
1	<b><code>l warp.sty</code></b>	196
15	Implementation	196
16	Section depths and HTML headings	197
17	Source code	198
18	Detecting the <code>TEX</code> engine — <code>pdflatex</code> , <code>lualatex</code> , <code>xelatex</code>	199
19	Early package requirements	199
20	Package load order	199
20.1	Tests of package load order	200
20.2	Error for disallowed packages and classes loaded before <code>l warp</code>	202
20.3	Enforcing package loading after <code>l warp</code>	203
21	MD5 hashing	212
22	<code>pdfLATEX T1</code> and <code>UTF-8</code> encoding	212
23	Unicode input characters	213
24	Avoid a bitmapped font	214
25	Upright quotes	214
26	Miscellaneous tools	215
26.1	Lengths and units	215
26.2	Counters	215
26.3	Patching	215
26.4	Chinese text isolation	216
26.5	Inserting vertical space	216

26.6	Argument selection . . . . .	216
26.7	Global boxes . . . . .	216
26.8	Converting a macro name to a cs name . . . . .	217
<b>27</b>	<b>Operating-System portability</b> . . . . .	<b>217</b>
27.1	Literal characters . . . . .	218
27.2	Common portability code . . . . .	219
27.3	UNIX, LINUX, and MAC OS . . . . .	219
27.4	MS-WINDOWS . . . . .	219
<b>28</b>	<b>Package options</b> . . . . .	<b>220</b>
28.1	Additional options support . . . . .	224
28.2	Conditional compilation . . . . .	226
<b>29</b>	<b>Required packages</b> . . . . .	<b>227</b>
<b>30</b>	<b>Loading packages</b> . . . . .	<b>233</b>
<b>31</b>	<b>Additional required packages</b> . . . . .	<b>239</b>
<b>32</b>	<b>File handles</b> . . . . .	<b>239</b>
<b>33</b>	<b>Include a file</b> . . . . .	<b>240</b>
<b>34</b>	<b>Copying a file</b> . . . . .	<b>241</b>
<b>35</b>	<b>Debugging messages</b> . . . . .	<b>241</b>
<b>36</b>	<b>Defining print and HTML versions of macros and environments</b> . . . . .	<b>242</b>
<b>37</b>	<b>HTML-conversion output modifications</b> . . . . .	<b>247</b>
37.1	User-level controls . . . . .	247
37.2	Heading adjustments . . . . .	249
<b>38</b>	<b>Remembering original formatting macros</b> . . . . .	<b>250</b>
<b>39</b>	<b>Accents</b> . . . . .	<b>252</b>
<b>40</b>	<b>Configuration files</b> . . . . .	<b>253</b>
40.1	Decide whether to generate configuration files . . . . .	253
40.2	<project>.html.tex . . . . .	254
40.3	<i>l warpmk</i> configuration files . . . . .	254
40.3.1	Helper macros . . . . .	254

40.3.2	<code>lwarfpmk.conf</code>	260
40.3.3	<code>&lt;project&gt;.lwarfpmkconf</code>	260
40.4	<code>lwarf.css</code>	260
40.5	<code>lwarf_sagebrush.css</code>	290
40.6	<code>lwarf_formal.css</code>	294
40.7	<code>sample_project.css</code>	298
40.8	<code>lwarf.ist</code>	299
40.9	<code>lwarf.xdy</code>	299
40.10	<code>lwarf_one_limage.cmd</code>	300
40.11	<code>lwarf_mathjax.txt</code>	301
40.12	<code>lwarfpmk.lua</code> — <code>lwarfpmk</code> option	303
<b>41</b>	<b>Stacks</b>	<b>321</b>
41.1	Assigning depths	321
41.2	Closing actions	322
41.3	Closing depths	322
41.4	Pushing and popping the stack	323
<b>42</b>	<b>Data arrays</b>	<b>324</b>
<b>43</b>	<b>Localizing catcodes</b>	<b>324</b>
<b>44</b>	<b>Localizing dynamic math</b>	<b>325</b>
<b>45</b>	<b>HTML entities</b>	<b>326</b>
<b>46</b>	<b>HTML filename generation</b>	<b>327</b>
<b>47</b>	<b>Homepage link</b>	<b>329</b>
<b>48</b>	<b>\LWRPrintStack diagnostic tool</b>	<b>331</b>
<b>49</b>	<b>Closing stack levels</b>	<b>331</b>
<b>50</b>	<b>PDF pages and styles</b>	<b>332</b>
<b>51</b>	<b>HTML tags, spans, divs, elements</b>	<b>333</b>
51.1	Mapping L <sup>A</sup> T <sub>E</sub> X sections to HTML sections	334
51.2	Babel-French tag modifications	334
51.3	HTML output formatting	335

51.4	<b>HTML tags</b>	336
51.5	<b>Block tags and comments</b>	337
51.6	<b>Div class and element class</b>	338
51.7	<b>Single-line elements</b>	340
51.8	<b>HTML5 semantic elements</b>	340
51.9	<b>High-level block and inline classes</b>	340
51.10	<b>Closing HTML tags</b>	342
<b>52</b>	<b>Paragraph handling</b>	<b>343</b>
<b>53</b>	<b>Paragraph start/stop handling</b>	<b>347</b>
<b>54</b>	<b>Indentfirst</b>	<b>349</b>
<b>55</b>	<b>Page headers and footers</b>	<b>349</b>
<b>56</b>	<b>css</b>	<b>350</b>
<b>57</b>	<b>MathJax script</b>	<b>350</b>
<b>58</b>	<b>Title, HTML meta author, HTML meta description</b>	<b>351</b>
<b>59</b>	<b>Footnotes</b>	<b>352</b>
59.1	Regular page footnotes	353
59.2	Minipage footnotes	353
59.3	Titlepage thanks	353
59.4	Regular page footnote implementation	353
59.5	Minipage footnote implementation	356
59.6	Printing pending footnotes	357
<b>60</b>	<b>Marginpars</b>	<b>358</b>
<b>61</b>	<b>Splitting HTML files</b>	<b>359</b>
61.1	Sanitizing expressions for HTML	364
61.2	Customizing MATHJAX	366
<b>62</b>	<b>Sectioning</b>	<b>372</b>
62.1	User-level starred section commands	372
62.2	Book class commands	373
62.3	Sectioning support macros	373

62.4	Pre- and post- sectioning names . . . . .	380
62.5	\section and friends . . . . .	381
<b>63</b>	<b>Starting a new file . . . . .</b>	<b>382</b>
<b>64</b>	<b>Starting HTML output . . . . .</b>	<b>386</b>
<b>65</b>	<b>Ending HTML output . . . . .</b>	<b>389</b>
<b>66</b>	<b>Title page . . . . .</b>	<b>391</b>
66.1	Setting the title, etc. . . . .	391
66.2	\if@titlepage . . . . .	392
66.3	Changes for \affiliation . . . . .	392
66.4	Printing the thanks . . . . .	393
66.5	Printing the title, etc. in HTML . . . . .	394
66.6	Printing the title, etc. in print form . . . . .	395
66.7	\maketitle for HTML output . . . . .	395
66.8	\published and \subtitle . . . . .	398
<b>67</b>	<b>Abstract . . . . .</b>	<b>399</b>
<b>68</b>	<b>Quote and verse . . . . .</b>	<b>400</b>
68.1	Attributions . . . . .	400
68.2	Quotes, quotations . . . . .	401
68.3	Verse . . . . .	401
68.3.1	IATEX core verse environment . . . . .	402
68.3.2	verse and memoir . . . . .	402
<b>69</b>	<b>Verbatim and tabbing . . . . .</b>	<b>402</b>
<b>70</b>	<b>Theorems . . . . .</b>	<b>405</b>
<b>71</b>	<b>Lists . . . . .</b>	<b>406</b>
71.1	List environment . . . . .	406
71.2	Itemize . . . . .	410
71.3	Enumerate . . . . .	410
71.4	Description . . . . .	411
71.5	Patching the lists . . . . .	411

<b>72</b>	<b>Tabular</b>	<b>413</b>
72.1	Limitations	413
72.2	Temporary package-related macros	415
72.2.1	arydshln	415
72.3	Token lookahead	415
72.4	Tabular variables	416
72.4.1	Multicolumn variables	419
72.4.2	Longtable variables	419
72.4.3	Midrule variables	420
72.5	Handling &, @, !, and bar	420
72.5.1	Handling &	422
72.5.2	Filling an unfinished row	422
72.6	Handling \\	424
72.7	Looking ahead in the column specifications	425
72.8	Parsing @, >, <, !, bar columns	426
72.9	Parsing 'l', 'c', or 'r' columns	429
72.10	Parsing 'p', 'm', or 'b' columns	430
72.11	Parsing 'w' columns	430
72.12	Parsing '*' columns	431
72.13	Parsing 'D' columns	431
72.14	Expanding the star column specifications	431
72.15	Parsing the column specifications	433
72.16	colortbl and xcolor tabular color support	437
72.17	Starting a new row	439
72.18	Printing vertical bar tags	439
72.19	Printing @ or ! tags	440
72.20	Data opening tag	441
72.21	Midrules	443
72.22	Cell colors	448

72.23	Multicolumns . . . . .	452
72.23.1	Parsing multicolumns . . . . .	452
72.23.2	Multicolumn factored code . . . . .	455
72.23.3	Multicolumn . . . . .	458
72.23.4	Longtable captions . . . . .	459
72.23.5	Counting HTML tabular columns . . . . .	461
72.24	Multirow if not loaded . . . . .	463
72.25	Multicolumnrow . . . . .	463
72.26	Utility macros inside a table . . . . .	464
72.27	Special-case tabular markers . . . . .	465
72.28	Checking for a new table cell . . . . .	466
72.29	\mrowcell . . . . .	468
72.30	\mcolrowcell . . . . .	469
72.31	HTML tabular environment . . . . .	469
<b>73</b>	<b>Cross-references . . . . .</b>	<b>476</b>
73.1	Setup . . . . .	476
73.2	New l warp labels . . . . .	478
73.3	Labels . . . . .	479
73.4	References . . . . .	481
73.5	Hyper-references . . . . .	483
<b>74</b>	<b>FLOATS . . . . .</b>	<b>488</b>
74.1	Float environment . . . . .	488
74.2	Float tracking . . . . .	490
74.3	Caption inside a float environment . . . . .	492
74.4	Caption and LOF linking and tracking . . . . .	492
<b>75</b>	<b>Table of Contents, LOF, LOT . . . . .</b>	<b>495</b>
75.1	Reading and printing the TOC . . . . .	496
75.2	High-level TOC commands . . . . .	499
75.3	Side TOC . . . . .	499

75.4	Low-level toc line formatting . . . . .	500
<b>76</b>	<b>Index and glossary . . . . .</b>	<b>504</b>
<b>77</b>	<b>Bibliography presentation . . . . .</b>	<b>507</b>
<b>78</b>	<b>Restoring original formatting . . . . .</b>	<b>508</b>
<b>79</b>	<b>Math . . . . .</b>	<b>510</b>
79.1	Limitations . . . . .	510
79.2	HTML alt tag names . . . . .	510
79.3	Inline and display math . . . . .	511
79.4	MATHJAX support . . . . .	524
79.5	Equation environment . . . . .	526
79.6	\displaymathnormal and \displaymathother . . . . .	529
79.7	AMS Math environments . . . . .	530
79.7.1	Support macros . . . . .	530
79.7.2	Environment patches . . . . .	531
<b>80</b>	<b>Lateximages . . . . .</b>	<b>534</b>
80.1	Description . . . . .	534
80.2	Support counters and macros . . . . .	535
80.3	Font size . . . . .	536
80.4	Equation numbers . . . . .	536
80.5	HTML alt tags . . . . .	537
80.6	lateximage environment . . . . .	538
<b>81</b>	<b>center, flushleft, flushright . . . . .</b>	<b>544</b>
<b>82</b>	<b>Preloaded packages . . . . .</b>	<b>546</b>
<b>83</b>	<b>siunitx . . . . .</b>	<b>547</b>
<b>84</b>	<b>Graphics print-mode modifications . . . . .</b>	<b>549</b>
84.1	General limitations . . . . .	549
84.2	Print-mode modifications . . . . .	550
<b>85</b>	<b>xcolor boxes . . . . .</b>	<b>551</b>
<b>86</b>	<b>chemmacros environments . . . . .</b>	<b>554</b>

87	<b>cleveref</b>	554
88	<b>picture environment</b>	557
89	<b>Minipages and Boxes</b>	558
89.1	Computed lengths	559
89.2	Virtual page size	559
89.3	Footnote handling	559
89.4	Minipage handling	560
89.5	\parbox, \mbox, \makebox, \framebox, \fbox, \raisebox	563
90	<b>Direct formatting</b>	569
91	<b>Skips, spaces, font sizes</b>	581
92	<b>\phantomsection</b>	589
93	<b>\LaTeX and other logos</b>	589
94	<b>\AtBeginDocument, \AtEndDocument</b>	593
95	<b>Loading KOMA-SCRIPT class patches</b>	593
96	<b>Loading MEMOIR class patches</b>	593
97	<b>ut* class patches</b>	594
98	<b>CTEX patches</b>	595
99	<b>kotexutf patches</b>	596
100	<b>babel and polyglossia warnings</b>	596
101	<b>MATHJAX warnings</b>	597
2	<b>l warp-2in1.sty</b>	600
3	<b>l warp-2up.sty</b>	600
4	<b>l warp-a4.sty</b>	600
5	<b>l warp-a4wide.sty</b>	601
6	<b>l warp-a5comb.sty</b>	601
7	<b>l warp-abstract.sty</b>	601
8	<b>l warp-academicons.sty</b>	603
9	<b>l warp-afterpage.sty</b>	604

10	<b>l warp-accessibility.sty</b>	604
11	<b>l warp-accsupp.sty</b>	605
12	<b>l warp-acro.sty</b>	605
13	<b>l warp-acronym.sty</b>	607
14	<b>l warp-adjmulticol.sty</b>	608
15	<b>l warp-addlines.sty</b>	609
16	<b>l warp-afterpage.sty</b>	610
17	<b>l warp-algorithm2e.sty</b>	610
18	<b>l warp-algorithmicx.sty</b>	614
19	<b>l warp-alltt.sty</b>	615
20	<b>l warp-amsmath.sty</b>	615
21	<b>l warp-amsthm.sty</b>	619
22	<b>l warp-anonchap.sty</b>	622
23	<b>l warp-anyfontsize.sty</b>	623
24	<b>l warp-appendix.sty</b>	623
25	<b>l warp-ar.sty</b>	624
26	<b>l warp-arabicfront.sty</b>	625
27	<b>l warp-array.sty</b>	626
28	<b>l warp-arydshln.sty</b>	626
29	<b>l warp-asymptote.sty</b>	628
30	<b>l warp-atbegshi.sty</b>	629
31	<b>l warp-attachfile.sty</b>	630
32	<b>l warp-attachfile2.sty</b>	631
33	<b>l warp-authblk.sty</b>	633
34	<b>l warp-autobreak.sty</b>	634
35	<b>l warp-autonum.sty</b>	634
36	<b>l warp-awesomebox.sty</b>	635

37	<b>l warp-axessibility.sty</b>	636
38	<b>l warp-axodraw2.sty</b>	637
39	<b>l warp-backnaur.sty</b>	637
40	<b>l warp-backref.sty</b>	637
41	<b>l warp-balance.sty</b>	638
42	<b>l warp-bbding.sty</b>	638
43	<b>l warp-biblatex.sty</b>	643
44	<b>l warp-bibunits.sty</b>	644
45	<b>l warp-bigdelim.sty</b>	645
46	<b>l warp-bigfoot.sty</b>	646
47	<b>l warp-bigstrut.sty</b>	647
48	<b>l warp-bitpattern.sty</b>	647
49	<b>l warp-blowup.sty</b>	648
50	<b>l warp-bm.sty</b>	648
51	<b>l warp-booklet.sty</b>	648
52	<b>l warp-bookmark.sty</b>	649
53	<b>l warp-booktabs.sty</b>	649
54	<b>l warp-bophook.sty</b>	651
55	<b>l warp-bounddvi.sty</b>	652
56	<b>l warp-boxedminipage2e.sty</b>	652
57	<b>l warp-braket.sty</b>	652
58	<b>l warp-breakurl.sty</b>	653
59	<b>l warp-breqn.sty</b>	653
60	<b>l warp-bsheaders.sty</b>	655
61	<b>l warp-bxpaper size.sty</b>	655
62	<b>l warp-bytefield.sty</b>	655
63	<b>l warp-cancel.sty</b>	656

<b>64</b>	<b>l warp-canoniclayout.sty</b>	<b>657</b>
<b>65</b>	<b>l warp-caption.sty</b>	<b>657</b>
<b>66</b>	<b>l warp-cases.sty</b>	<b>660</b>
<b>67</b>	<b>l warp-centernot.sty</b>	<b>661</b>
<b>68</b>	<b>l warp-changebar.sty</b>	<b>661</b>
<b>69</b>	<b>l warp-changelayout.sty</b>	<b>662</b>
<b>70</b>	<b>l warp-changepage.sty</b>	<b>662</b>
<b>71</b>	<b>l warp-changes.sty</b>	<b>663</b>
<b>72</b>	<b>l warp-chappg.sty</b>	<b>665</b>
<b>73</b>	<b>l warp-chapterbib.sty</b>	<b>666</b>
<b>74</b>	<b>l warp-chemfig.sty</b>	<b>666</b>
<b>75</b>	<b>l warp-chemformula.sty</b>	<b>668</b>
<b>76</b>	<b>l warp-chemgreek.sty</b>	<b>673</b>
<b>77</b>	<b>l warp-chemmacros.sty</b>	<b>673</b>
<b>177</b>	<b>chemmacros</b>	<b>673</b>
177.1	Changes to the user's document	674
177.2	Code	674
177.3	Loading modules	674
177.4	New environments	675
177.5	Acid-base	675
177.6	Charges	677
177.7	Nomenclature	677
177.8	Particles	679
177.9	Phases	680
177.10	Mechanisms	681
177.11	Newman	683
177.12	Orbital	683
177.13	Reactions	684

177.14	Redox . . . . .	684
177.15	Scheme . . . . .	685
177.16	Spectroscopy . . . . .	686
177.17	Thermodynamics . . . . .	690
<b>78</b>	<b>l warp-chemnum.sty</b> . . . . .	<b>692</b>
<b>79</b>	<b>l warp-chkfloat.sty</b> . . . . .	<b>693</b>
<b>80</b>	<b>l warp-chngpage.sty</b> . . . . .	<b>693</b>
<b>81</b>	<b>l warp-cite.sty</b> . . . . .	<b>693</b>
<b>82</b>	<b>l warp-CJK.sty</b> . . . . .	<b>694</b>
<b>83</b>	<b>l warp-CJKutf8.sty</b> . . . . .	<b>694</b>
<b>84</b>	<b>l warp-clrdblpg.sty</b> . . . . .	<b>694</b>
<b>85</b>	<b>l warp-cmdtrack.sty</b> . . . . .	<b>694</b>
<b>86</b>	<b>l warp-color.sty</b> . . . . .	<b>695</b>
<b>87</b>	<b>l warp-colortbl.sty</b> . . . . .	<b>695</b>
<b>88</b>	<b>l warp-continue.sty</b> . . . . .	<b>697</b>
<b>89</b>	<b>l warp-copyrightbox.sty</b> . . . . .	<b>697</b>
<b>90</b>	<b>l warp-crop.sty</b> . . . . .	<b>698</b>
<b>91</b>	<b>l warp-ctable.sty</b> . . . . .	<b>698</b>
<b>92</b>	<b>l warp-cuted.sty</b> . . . . .	<b>701</b>
<b>93</b>	<b>l warp-cutwin.sty</b> . . . . .	<b>701</b>
<b>94</b>	<b>l warp-dblfloatfix.sty</b> . . . . .	<b>702</b>
<b>95</b>	<b>l warp-dblfnote.sty</b> . . . . .	<b>702</b>
<b>96</b>	<b>l warp-dcolumn.sty</b> . . . . .	<b>702</b>
<b>97</b>	<b>l warp-diagbox.sty</b> . . . . .	<b>703</b>
<b>98</b>	<b>l warp-dingbat.sty</b> . . . . .	<b>704</b>
<b>99</b>	<b>l warp-dprogress.sty</b> . . . . .	<b>705</b>
<b>100</b>	<b>l warp-draftcopy.sty</b> . . . . .	<b>705</b>

101	<b>l warp-draftfigure.sty</b>	706
102	<b>l warp-draftwatermark.sty</b>	706
103	<b>l warp-easy-todo.sty</b>	707
104	<b>l warp-ebook.sty</b>	707
105	<b>l warp-ed.sty</b>	708
106	<b>l warp-ellipsis.sty</b>	709
107	<b>l warp-embrac.sty</b>	709
108	<b>l warp-emptypage.sty</b>	710
109	<b>l warp-endfloat.sty</b>	710
110	<b>l warp-endheads.sty</b>	711
111	<b>l warp-endnotes.sty</b>	711
112	<b>l warp-enumerate.sty</b>	712
113	<b>l warp-enumitem.sty</b>	712
114	<b>l warp-epigraph.sty</b>	713
115	<b>l warp-epsfig.sty</b>	714
116	<b>l warp-epstopdf.sty</b>	715
117	<b>l warp-epstopdf-base.sty</b>	715
118	<b>l warp-eqlist.sty</b>	716
119	<b>l warp-eqparbox.sty</b>	716
120	<b>l warp-errata.sty</b>	717
121	<b>l warp-eso-pic.sty</b>	719
122	<b>l warp-eurosym.sty</b>	719
123	<b>l warp-everypage.sty</b>	720
124	<b>l warp-everyshi.sty</b>	720
125	<b>l warp-extarrows.sty</b>	720
126	<b>l warp-extramarks.sty</b>	721
127	<b>l warp-fancybox.sty</b>	721

128	<b>l warp-fancyhdr.sty</b>	726
129	<b>l warp-fancyref.sty</b>	727
130	<b>l warp-fancytabs.sty</b>	728
131	<b>l warp-fancyvrb.sty</b>	728
132	<b>l warp-fewerfloatpages.sty</b>	735
133	<b>l warp-figcaps.sty</b>	735
134	<b>l warp-figsize.sty</b>	735
135	<b>l warp-fitbox.sty</b>	736
136	<b>l warp-fix2col.sty</b>	736
137	<b>l warp-fixme.sty</b>	736
138	<b>l warp-fixmetodonotes.sty</b>	738
139	<b>l warp-flafter.sty</b>	738
140	<b>l warp-flippdf.sty</b>	738
141	<b>l warp-float.sty</b>	739
142	<b>l warp-floatflt.sty</b>	740
143	<b>l warp-floatpag.sty</b>	741
144	<b>l warp-floatrow.sty</b>	742
145	<b>l warp-fltrace.sty</b>	747
146	<b>l warp-flushend.sty</b>	747
147	<b>l warp-fnbreak.sty</b>	747
148	<b>l warp-fncychap.sty</b>	748
149	<b>l warp-fnlineno.sty</b>	748
150	<b>l warp-fnpara.sty</b>	749
151	<b>l warp-fnpos.sty</b>	749
152	<b>l warp-fontawesome.sty</b>	749
153	<b>l warp-fontawesome5.sty</b>	751
154	<b>l warp-fontaxes.sty</b>	751

155	<b>l warp - fontenc.sty</b>	752
156	<b>l warp - footmisc.sty</b>	752
157	<b>l warp - footnote.sty</b>	753
158	<b>l warp - footnotebackref.sty</b>	754
159	<b>l warp - footnotehyper.sty</b>	754
160	<b>l warp - footnoterange.sty</b>	755
161	<b>l warp - footnpag.sty</b>	755
162	<b>l warp - foreign.sty</b>	755
163	<b>l warp - forest.sty</b>	755
164	<b>l warp - fouridx.sty</b>	756
165	<b>l warp - framed.sty</b>	756
166	<b>l warp - ftcap.sty</b>	759
167	<b>l warp - ftnright.sty</b>	759
168	<b>l warp - fullminipage.sty</b>	759
169	<b>l warp - fullpage.sty</b>	759
170	<b>l warp - fullwidth.sty</b>	760
171	<b>l warp - fwlw.sty</b>	760
172	<b>l warp - gensymb.sty</b>	760
173	<b>l warp - gentombow.sty</b>	761
174	<b>l warp - geometry.sty</b>	761
175	<b>l warp - ghsystem.sty</b>	762
176	<b>l warp - gloss.sty</b>	762
177	<b>l warp - glossaries.sty</b>	763
178	<b>l warp - gmeometric.sty</b>	765
179	<b>l warp - graphics.sty</b>	765
279	<b>graphics</b>	765
279.1	Graphics extensions	766

279.2	Length conversions and graphics options . . . . .	766
279.3	Printing HTML styles . . . . .	769
279.4	\includegraphics . . . . .	769
279.5	Boxes . . . . .	775
<b>180</b>	<b>l warp-graphicx.sty</b> . . . . .	<b>778</b>
<b>181</b>	<b>l warp-grffile.sty</b> . . . . .	<b>778</b>
<b>182</b>	<b>l warp-grid.sty</b> . . . . .	<b>778</b>
<b>183</b>	<b>l warp-grid-system.sty</b> . . . . .	<b>779</b>
<b>184</b>	<b>l warp-gridset.sty</b> . . . . .	<b>779</b>
<b>185</b>	<b>l warp-hang.sty</b> . . . . .	<b>779</b>
<b>186</b>	<b>l warp-hanging.sty</b> . . . . .	<b>781</b>
<b>187</b>	<b>l warp-hhline.sty</b> . . . . .	<b>782</b>
<b>188</b>	<b>l warp-hypbmsec.sty</b> . . . . .	<b>782</b>
<b>189</b>	<b>l warp-hypcap.sty</b> . . . . .	<b>782</b>
<b>190</b>	<b>l warp-hypdestopt.sty</b> . . . . .	<b>783</b>
<b>191</b>	<b>l warp-hypernat.sty</b> . . . . .	<b>783</b>
<b>192</b>	<b>l warp-hyperref.sty</b> . . . . .	<b>783</b>
<b>193</b>	<b>l warp-hyperxmp.sty</b> . . . . .	<b>788</b>
<b>194</b>	<b>l warp-hyphenat.sty</b> . . . . .	<b>788</b>
<b>195</b>	<b>l warp-idxlayout.sty</b> . . . . .	<b>789</b>
<b>196</b>	<b>l warp-ifoddpage.sty</b> . . . . .	<b>790</b>
<b>197</b>	<b>l warp-imakeidx.sty</b> . . . . .	<b>790</b>
<b>198</b>	<b>l warp-index.sty</b> . . . . .	<b>794</b>
<b>199</b>	<b>l warp-inputrc.sty</b> . . . . .	<b>796</b>
<b>200</b>	<b>l warp-intopdf.sty</b> . . . . .	<b>796</b>
<b>201</b>	<b>l warp-karnaugh-map.sty</b> . . . . .	<b>797</b>
<b>202</b>	<b>l warp-keyfloat.sty</b> . . . . .	<b>800</b>

203	<b>l warp-layaureo.sty</b>	805
204	<b>l warp-layout.sty</b>	805
205	<b>l warp-layouts.sty</b>	806
206	<b>l warp-leading.sty</b>	808
207	<b>l warp-leftidx.sty</b>	809
208	<b>l warp-letterspace.sty</b>	809
209	<b>l warp-lettrine.sty</b>	809
210	<b>l warp-lineno.sty</b>	810
211	<b>l warp-lips.sty</b>	813
212	<b>l warp-listings.sty</b>	813
213	<b>l warp-listliketab.sty</b>	817
214	<b>l warp-lltjext.sty</b>	817
215	<b>l warp-longtable.sty</b>	818
216	<b>l warp-lscape.sty</b>	821
217	<b>l warp-ltablex.sty</b>	822
218	<b>l warp-ltcaption.sty</b>	822
219	<b>l warp-ltxgrid.sty</b>	823
220	<b>l warp-ltxtable.sty</b>	823
221	<b>l warp-lua-check-hyphen.sty</b>	823
222	<b>l warp-lua-visual-debug.sty</b>	824
223	<b>l warp-luacolor.sty</b>	824
224	<b>l warp-luatodonotes.sty</b>	824
225	<b>l warp-lyluatex.sty</b>	826
226	<b>l warp-magaz.sty</b>	828
227	<b>l warp-makeidx.sty</b>	829
228	<b>l warp-manyfoot.sty</b>	829
229	<b>l warp-marginal.sty</b>	831

230	<b>l warp-marginfit.sty</b>	831
231	<b>l warp-marginfix.sty</b>	832
232	<b>l warp-marginnote.sty</b>	832
233	<b>l warp-marvosym.sty</b>	833
234	<b>l warp-mathcomp.sty</b>	833
235	<b>l warp-mathdots.sty</b>	834
236	<b>l warp-mathfixs.sty</b>	834
237	<b>l warp-mathtools.sty</b>	834
238	<b>l warp-mcaption.sty</b>	839
239	<b>l warp-mdframed.sty</b>	839
339	<b>mdframed</b>	839
339.1	Limitations	840
339.2	Package loading	840
339.3	Patches	840
339.4	Initial setup	841
339.5	Color and length HTML conversion	841
339.6	Environment encapsulation	842
339.7	Mdframed environment	843
339.8	Titles and subtitles	844
339.9	New environments	846
240	<b>l warp-media9.sty</b>	848
241	<b>l warp-memhfixc.sty</b>	851
242	<b>l warp-metalogo.sty</b>	851
243	<b>l warp-metalogox.sty</b>	851
244	<b>l warp-mhchem.sty</b>	852
245	<b>l warp-microtype.sty</b>	855
246	<b>l warp-midfloat.sty</b>	855

247	<b>l warp-midpage.sty</b>	856
248	<b>l warp-minibox.sty</b>	856
249	<b>l warp-minitoc.sty</b>	857
250	<b>l warp-mismath.sty</b>	857
251	<b>l warp-morefloats.sty</b>	861
252	<b>l warp-moreverb.sty</b>	861
253	<b>l warp-movie15.sty</b>	862
254	<b>l warp-mparhack.sty</b>	864
255	<b>l warp-multicap.sty</b>	864
256	<b>l warp-multicol.sty</b>	864
257	<b>l warp-multicolrule.sty</b>	865
258	<b>l warp-multimedia.sty</b>	866
259	<b>l warp-multirow.sty</b>	867
260	<b>l warp-multitoc.sty</b>	870
261	<b>l warp-musicography.sty</b>	871
262	<b>l warp-nameauth.sty</b>	874
263	<b>l warp-nameref.sty</b>	875
264	<b>l warp-natbib.sty</b>	875
265	<b>l warp-nccfancyhdr.sty</b>	876
266	<b>l warp-nccmath.sty</b>	877
267	<b>l warp-needspace.sty</b>	878
268	<b>l warp-nextpage.sty</b>	878
269	<b>l warp-nfssext-cfr.sty</b>	879
270	<b>l warp-nicefrac.sty</b>	887
271	<b>l warp-niceframe.sty</b>	888
272	<b>l warp-noitcrl.sty</b>	889
273	<b>l warp-nomencl.sty</b>	889



287	<b>l warp-parallel.sty</b>	906
288	<b>l warp-parcolumns.sty</b>	908
289	<b>l warp-parnotes.sty</b>	910
290	<b>l warp-parskip.sty</b>	911
291	<b>l warp-pbox.sty</b>	911
292	<b>l warp-pdfcol.sty</b>	911
293	<b>l warp-pdfcolfoot.sty</b>	912
294	<b>l warp-pdfcolmk.sty</b>	912
295	<b>l warp-pdfcolparallel.sty</b>	912
296	<b>l warp-pdfcolparcolumns.sty</b>	913
297	<b>l warp-pdfcomment.sty</b>	913
298	<b>l warp-pdfcrypt.sty</b>	914
299	<b>l warp-pdflandscape.sty</b>	914
300	<b>l warp-pdfmarginpar.sty</b>	915
301	<b>l warp-pdfpages.sty</b>	915
302	<b>l warp-pdfprivacy.sty</b>	917
303	<b>l warp-pdfrender.sty</b>	918
304	<b>l warp-pdfsync.sty</b>	918
305	<b>l warp-pdftricks.sty</b>	918
306	<b>l warp-pdfx.sty</b>	919
307	<b>l warp-perpage.sty</b>	919
308	<b>l warp-pfnote.sty</b>	920
309	<b>l warp-phfqt.sty</b>	921
310	<b>l warp-physics.sty</b>	921
311	<b>l warp-pifont.sty</b>	927
312	<b>l warp-placeins.sty</b>	928
313	<b>l warp-plarydshln.sty</b>	928

314	<b>l warp-plext.sty</b>	928
315	<b>l warp-plextrydshln.sty</b>	929
316	<b>l warp-plextcolortbl.sty</b>	929
317	<b>l warp-prelim2e.sty</b>	930
318	<b>l warp-prettyref.sty</b>	930
319	<b>l warp-preview.sty</b>	930
320	<b>l warp-psfrag.sty</b>	931
321	<b>l warp-psfragx.sty</b>	931
322	<b>l warp-pst-eps.sty</b>	932
323	<b>l warp-pstool.sty</b>	932
324	<b>l warp-pstricks.sty</b>	933
325	<b>l warp-pxatbegshi.sty</b>	933
326	<b>l warp-pxeveryshi.sty</b>	933
327	<b>l warp-pxftnright.sty</b>	934
328	<b>l warp-pxjahyper.sty</b>	934
329	<b>l warp-quotchap.sty</b>	934
330	<b>l warp-quoting.sty</b>	935
331	<b>l warp-ragged2e.sty</b>	936
332	<b>l warp-realscripts.sty</b>	936
333	<b>l warp-refcheck.sty</b>	937
334	<b>l warp-register.sty</b>	938
335	<b>l warp-relsize.sty</b>	939
336	<b>l warp-repeatindex.sty</b>	940
337	<b>l warp-resizegather.sty</b>	941
338	<b>l warp-rmathbr.sty</b>	941
339	<b>l warp-rmpage.sty</b>	941
340	<b>l warp-romanbar.sty</b>	942

341	<b>l warp-romanbarpage number.sty</b>	942
342	<b>l warp-rotating.sty</b>	942
343	<b>l warp-rotfloat.sty</b>	943
344	<b>l warp-rviewport.sty</b>	944
345	<b>l warp-savetrees.sty</b>	944
346	<b>l warp-scalefnt.sty</b>	944
347	<b>l warp-schemata.sty</b>	944
348	<b>l warp-scrextend.sty</b>	945
349	<b>l warp-scrhack.sty</b>	948
350	<b>l warp-scrlayer.sty</b>	948
351	<b>l warp-scrlayer-notecolumn.sty</b>	949
352	<b>l warp-scrlayer-scrpage.sty</b>	950
353	<b>l warp-scrpage2.sty</b>	951
354	<b>l warp-section.sty</b>	952
355	<b>l warp-sectionbreak.sty</b>	953
356	<b>l warp-sectsty.sty</b>	953
357	<b>l warp-semantic-markup.sty</b>	954
358	<b>l warp-setspace.sty</b>	955
359	<b>l warp-shadow.sty</b>	956
360	<b>l warp-shapepar.sty</b>	956
361	<b>l warp-showidx.sty</b>	957
362	<b>l warp-showkeys.sty</b>	957
363	<b>l warp-showtags.sty</b>	957
364	<b>l warp-sidecap.sty</b>	957
365	<b>l warp-sidenotes.sty</b>	958
366	<b>l warp-SIunits.sty</b>	960
367	<b>l warp-siunitx.sty</b>	960

368	<b>l warp-slantsc.sty</b>	971
369	<b>l warp-slashed.sty</b>	971
370	<b>l warp-soul.sty</b>	972
371	<b>l warp-soulpos.sty</b>	973
372	<b>l warp-soulutf8.sty</b>	974
373	<b>l warp-splitidx.sty</b>	974
374	<b>l warp-srcltx.sty</b>	976
375	<b>l warp-srctex.sty</b>	976
376	<b>l warp-stabular.sty</b>	976
377	<b>l warp-stackengine.sty</b>	977
378	<b>l warp-steinmetz.sty</b>	979
379	<b>l warp-stffloats.sty</b>	979
380	<b>l warp-struktex.sty</b>	980
381	<b>l warp-subcaption.sty</b>	980
382	<b>l warp-subfig.sty</b>	981
383	<b>l warp-subfigure.sty</b>	986
384	<b>l warp-subsupscripts.sty</b>	986
385	<b>l warp-supertabular.sty</b>	987
386	<b>l warp-svg.sty</b>	989
387	<b>l warp-syntonly.sty</b>	989
388	<b>l warp-tabfigures.sty</b>	990
389	<b>l warp-tablefootnote.sty</b>	990
390	<b>l warp-tables.sty</b>	990
391	<b>l warp-tabularx.sty</b>	991
392	<b>l warp-tabulary.sty</b>	991
393	<b>l warp-tascmac.sty</b>	992
394	<b>l warp-textarea.sty</b>	993

395	<b>l warp-textcomp.sty</b>	994
396	<b>l warp-textfit.sty</b>	997
397	<b>l warp-textpos.sty</b>	998
398	<b>l warp-theorem.sty</b>	998
399	<b>l warp-thinsp.sty</b>	1002
400	<b>l warp-threadcol.sty</b>	1002
401	<b>l warp-threeparttable.sty</b>	1003
402	<b>l warp-threeparttablex.sty</b>	1004
403	<b>l warp-thumb.sty</b>	1005
404	<b>l warp-thumbs.sty</b>	1005
405	<b>l warp-tikz.sty</b>	1005
406	<b>l warp-titleps.sty</b>	1007
407	<b>l warp-titleref.sty</b>	1010
408	<b>l warp-titlesec.sty</b>	1010
409	<b>l warp-titletoc.sty</b>	1012
410	<b>l warp-titling.sty</b>	1013
411	<b>l warp-tocbasic.sty</b>	1018
412	<b>l warp-tocbibind.sty</b>	1018
413	<b>l warp-tocdata.sty</b>	1020
414	<b>l warp-toccenter.sty</b>	1022
415	<b>l warp-tocloft.sty</b>	1022
416	<b>l warp-tocstyle.sty</b>	1028
417	<b>l warp-todo.sty</b>	1028
418	<b>l warp-todonotes.sty</b>	1029
419	<b>l warp-topcapt.sty</b>	1031
420	<b>l warp-tram.sty</b>	1031
421	<b>l warp-transparent.sty</b>	1032

422	<b>l warp-trimclip.sty</b>	1032
423	<b>l warp-trivfloat.sty</b>	1033
424	<b>l warp-truncate.sty</b>	1034
425	<b>l warp-turnthepage.sty</b>	1034
426	<b>l warp-twoup.sty</b>	1034
427	<b>l warp-typearea.sty</b>	1035
428	<b>l warp-typicons.sty</b>	1035
429	<b>l warp-ulem.sty</b>	1036
430	<b>l warp-umoline.sty</b>	1037
431	<b>l warp-underscore.sty</b>	1038
432	<b>l warp-unicode-math.sty</b>	1038
433	<b>l warp-units.sty</b>	1040
434	<b>l warp-unitsdef.sty</b>	1041
435	<b>l warp-upref.sty</b>	1041
436	<b>l warp-url.sty</b>	1042
437	<b>l warp-uspace.sty</b>	1042
438	<b>l warp-verse.sty</b>	1042
439	<b>l warp-versonotes.sty</b>	1044
440	<b>l warp-vertbars.sty</b>	1044
441	<b>l warp-vmargin.sty</b>	1045
442	<b>l warp-vowel.sty</b>	1045
443	<b>l warp-vpe.sty</b>	1046
444	<b>l warp-vwcol.sty</b>	1046
445	<b>l warp-wallpaper.sty</b>	1048
446	<b>l warp-watermark.sty</b>	1049
447	<b>l warp-widetable.sty</b>	1049
448	<b>l warp-widows-and-orphans.sty</b>	1049

449	<b>lwarp-witharrows.sty</b>	1049
450	<b>lwarp-wrapfig.sty</b>	1051
451	<b>lwarp-xbmks.sty</b>	1052
452	<b>lwarp-xcolor.sty</b>	1053
552	<b>xcolor</b>	1053
552.1	Limitations	1053
552.2	xcolor definitions: location and timing	1053
552.3	Package loading	1055
552.4	Remembering and restoring original definitions	1055
552.5	\normalcolor	1056
552.6	HTML color style	1056
552.7	HTML border	1057
552.8	High-level macros	1057
552.9	Row colors	1062
453	<b>lwarp-xexchangebar.sty</b>	1063
454	<b>lwarp-xellipsis.sty</b>	1063
455	<b>lwarp-xetexko-vertical.sty</b>	1064
456	<b>lwarp-xfakebold.sty</b>	1064
457	<b>lwarp-xfrac.sty</b>	1065
458	<b>lwarp-xltabular.sty</b>	1067
459	<b>lwarp-xltxtra.sty</b>	1068
460	<b>lwarp-xmpincl.sty</b>	1068
461	<b>lwarp-xpiano.sty</b>	1069
462	<b>lwarp-xpinyin.sty</b>	1069
463	<b>lwarp-xr.sty</b>	1070
464	<b>lwarp-xr-hyper.sty</b>	1070
465	<b>lwarp-xtab.sty</b>	1071

466	<b>l warp-xunicode.sty</b>	1072
467	<b>l warp-xurl.sty</b>	1073
468	<b>l warp-xy.sty</b>	1074
469	<b>l warp-zhlineskip.sty</b>	1075
470	<b>l warp-zwpagelayout.sty</b>	1075
471	<b>l warp-patch-komascript.sty</b>	1076
472	<b>l warp-patch-memoir.sty</b>	1078
572	<b>patch-memoir</b>	1078
572.1	Packages	1079
572.2	Preliminary setup	1080
572.3	Page layout	1081
572.4	Text and fonts	1083
572.5	Titles	1084
572.6	Abstracts	1084
572.7	Document divisions	1084
572.8	Pagination and headers	1087
572.9	Paragraphs and lists	1088
572.10	Contents lists	1089
572.11	Floats and captions	1093
572.12	Page notes	1096
572.13	Decorative text	1097
572.14	Poetry	1097
572.15	Boxes, verbatims and files	1098
572.16	Cross referencing	1099
572.17	Back matter	1099
572.18	Miscellaneous	1101
572.19	<i>ccaption</i> emulation	1101
572.20	Final patchwork	1103

<b>473 l warp-common-multimedia.sty . . . . .</b>	<b>1103</b>
<b>    Change History . . . . .</b>	<b>1109</b>
<b>574 Chg Hist . . . . .</b>	<b>1109</b>
<b>    Index of Objects . . . . .</b>	<b>1140</b>
<b>    General Index . . . . .</b>	<b>1161</b>
<b>    Troubleshooting Index. . . . .</b>	<b>1165</b>
<b>    Index of Indexes . . . . .</b>	<b>1171</b>

## List of Figures

1	tutorial.tex listing	85
---	----------------------	----

## List of Tables

1	Typesetting conventions	67
2	L <sup>A</sup> T <sub>E</sub> X l warp package — Supported features	68
3	Required software programs	78
4	Configuration files created by print version	87
5	l warp package options	105
6	HTML settings	110
7	Literal character macros	173
8	Section HTML headings for word-processor conversion	181
9	Section depths and HTML headings	197
10	Tabular baseline	433
11	Tabular HTML column conversions	434
12	Cross-referencing data structures	477
13	Float data structures	488
14	amsthm package—css styling of theorems and proofs	619
15	Ntheorem package—css styling of theorems and proofs	892
16	Theorem package—css styling of theorems and proofs	999

## 1 Updates

The following is a summary of updates to lwarf, highlighting new features and any special changes which must be made due to improvements or modifications in lwarf itself.

For a detailed list of the most recent changes, see the end of the Change History on page [1139](#).

### v0.80: MATHJAX, biblatex.

- MATHJAX**
- Added docs and warning/info messages re: avoiding slow MATHJAX compilation. See section [8.7.5, Customizing MATHJAX](#).
  - Added MATHJAX emulation for accessibility, autobreak, centernot, extarrows, fouridx, gensymb, leftidx, mathcomp, mathdots, mathfixs, mismath, nccmath, noitcrl, pdfcomment, relsize, rmathbr, subsupscripts, xfrac.
  - Improved MATHJAX emulation for unicode-math.
- packages**
- biblatex, url: Now create hyperlinks.
  - amsmath: Fix to center starred environments.
  - xcolor, graphics: Made more macros robust.
  - colortbl: Fix: Rule color in a lateximage.
  - chemmacros: Updated to v5.10.
  - Added fewerfloatpages, ghsystem, hhline, mismath, nccmath.

### v0.79: MATHJAX, nested tabular.

- MATHJAX**
- Added or improved MATHJAX emulation for amsmath, ar, arydshln, bm, bigdelim, bigstrut, booktabs, braket, mathtools, multirow, physics, siunitx, slashed, unicode-math, xfakebold.
  - Warn if using certain packages not supported by MATHJAX.
- core**
- tabular: Now may be nested.
  - minipage, \parbox, fminipage, \makebox, \framebox: Fix: Adjust for virtual page size.
  - Uses new iftex.
- packages**
- graphicx: Fix: Negative angles.
  - caption: Fix: \captionlistentry with longtable.
  - multirow: Fix: Centered vertical alignment.
  - siunitx: Fix: \square, \cubed.
  - booktabs: Fix: memoir with lateximage.
  - babel and polyglossia: Added troubleshooting warnings.
  - fontawesome, fontawesome5: Supports text color and size.
  - transparent: Fix: lateximages.
  - epigraph: Updated to v1.5e.
  - xurl: Updated to v0.08.

- `subcaption`: Fixed with `memoir`.
- `floatrow`: Fix: `\linewidth`. No longer require `float`, `graphics`.
- `floatflt`, `wrapfig`, `niceframe`: Fix: Adjust for virtual page size.
- Added `widetable`, `witharrows`, `steinmetz`.
- Added `awesomebox`, `catoptions`.
- Added `svg`, supports `svg-extract`.
- Added `parcolumns`, `pdfcolparcolumns`,
- Added `parallel`, `pdfcolparallel`.
- Added `pdfcol`, `pdfcolfoot`, `pdfcolmk`.

**v0.78:** Fixes for support files, `alt` tags, hyperlinks, and the 2019/10 L<sup>A</sup>T<sub>E</sub>X release.

- docs**
- Docs: Improved documentation regarding package options. See section 8.1.
  - Fix to overwrite existing support files using new `filecontents` environment.

- packages**
- `breqn`: Previously broken by the 2019/10 L<sup>A</sup>T<sub>E</sub>X update, but now working again.
  - `graphics`: Fix for `\includegraphics alt` tags.
  - `babel-french`: Fix for hyperlinks.
  - `media9`, `movie15`, `multimedia`: Fix for the 2019/10 L<sup>A</sup>T<sub>E</sub>X update.
  - `accessibility`: Added.

**v0.77:** Updates to fix recently-broken packages.

- `booktabs`: Updated to v1.6180339.
- `chemformula`: Updated to v4.15.

**v0.76:** MATHJAX, updates for L<sup>A</sup>T<sub>E</sub>X 2019/10 release.

- docs**
- Docs: Expanded documentation regarding the use of multiple projects in the same directory. See section 5.17.

- MATHJAX**
- MATHJAX: Updated to v2.7.6.

- packages**
- `xr`: Updated to v5.05.
  - `xr-hyper`: Updated to v6.1.
  - Verified works as-is with `xcite`.
  - `acro`: Updated to v2.10.

- ⚠️ broken**
- Currently broken in print mode by the 2019/10 L<sup>A</sup>T<sub>E</sub>X update, and waiting for fixes: `breqn`, `grffile`, `multimedia`, `movie15`.

**v0.75: keyfloat, wrapfig**

- packages**
- `\minipage`: Fix for `\linewidth`.
  - `keyfloat`: Improved color control.
  - `wrapfig`: Fix for `\linewidth`.

**v0.74:** Docs, svg math, *lwarpmk*, HTML alt and title text, lyluatex

docs

- Added to the tutorial the section [What next?](#). See section [5.19](#).
- Added documentation about localization options. See section [7.1](#).
- Added documentation about accessibility options. See section [7.2](#).
- Renamed and updated HTML alt text macros:

⚠ **HTML alt text  
changed names**

Old	New
(hard coded as “image”)	\ImageAltText
\mathimagename	\MathImageAltText
\pacakgediagramname	\PackageDiagramAltText

- Added \ImageAltText for the default HTML alt text for an image. See section [7.6](#).
- Added \ThisAltText, which may be used to assign a one-time HTML alt tag to the very next image generated by *l warp*, such as a *lateximage*, *picture*, *tikzpicture*, an image generated by various chemistry or engineering packages, or an SVG math image. This macro also adds a title tag to a reference or hyperlink. See section [7.6](#).

svg math

- Adjusted \LateximageFontSize default from .75 to 1.
- Fix: Font control for SVG math.

misc

- Fix: Ignores negative \hspace.
- Warning if SideTOCDepth < FileDepth.

*lwarpmk*

- *lwarpmk*: *lwarpmk clean* removes additional files.
- *lwarpmk*: *lwarpmk epstopdf* and *lwarpmk pdftosvg* now honor directories.

packages

- lyluatex: Split images by system or per fullpage, improved margins and scaling.
- Tested to work as-is with *mathspec*, *unicode-math*.

**v0.73:** \include, memoir, koma-script, caption, xy, datatool, music scores.

packages

- Fix for \include.
- Warning for a tabular inside a <span>.
- \color: Added HTML support for rules and frames, but not inline text. Use \textcolor if possible.
- Improved many HTML tags, reducing *tidy* warnings. See Change History.
- memoir: Fixes for \frontmatter\* and \mainmatter\*. Added \book.
- koma-script: Fix for starred captions in the toc.
- caption: Fix for starred captions.
- datatool: Added pie, bar, and plot charts.
- threeparttable: Added measuredfigure.
- intopdf: Updated to v0.2.1.
- tocdata: Updated to v2.03.
- quotchap: Updated to v1.2.

- `veronotes`: Updated to v0.4.
- `backnaur`: Now uses SVG images. Updated to v3.1.
- `xy`: Fix for `\xybox`, improved `xy`, also now compatible with `qcircuit`.
- `fancyvrb`: Fix for label HTML tags.
- Added `stackengine`.

**music**

- Added `lyluatex`. (Music scores.)
- `musicography`: Updated to 2019/05/28. Added support for `lateximages`.

**v0.72:** Font control, `\multicolumn`, `xr` and `xr-hyper`.

**⚠️ images**

- Due to internal changes, images for inline SVG math and `lateximages` will have new hash values, and will have to be regenerated using

Enter ⇒ **`lwarpmk cleanimages`**

and

Enter ⇒ **`lwarpmk limages`**

**packages**

- Docs: Color-codes package names in the table of supported packages and features, table 2, according to each package's level of support by `lwarf`.
- `\multicolumn`: Fix for paragraph columns.
- `xr`, `xr-hyper`: Fixes for references, `\externaldocument`.
- `soulutf8`: Fix: Loads `soul` for emulation.
- `boxedminipage2e`: Added support for `lateximages`.
- `zhlineskip`: Updated to v1.0e.
- Added `fontaxes`, `slantsc`, `tabfigures`.
- Added `nfssext-cfr`, thus supporting `cfr-lm` and several other font packages.
- Added `backnaur`, `hypbmsec`, `minibox`, `pdfcrypt`, `shapepar`.

**v0.71:** Error handling, multimedia, tabular.

**packages**

- `tabular`: Added support for '\*' columns. Fix for paragraph tags.
- `quotation`: Fix for HTML tag.
- Docs: Added a section about error conditions tested by `lwarf`. See section 13.1.
- `lwarpmk`: If file `lwarpmk.conf` is an older version, or the incorrect operating system, displays the print command to use to recompile.

**multimedia**

- `chemfig`: Updated for v1.4.
- `endfloat`: Updated for v2.7.
- `textpos`: Updated for v1.9.1.
- Added `media9`, `movie15`, `multimedia`.

**v0.70:** Error handling, MATHJAX, mathtools.

- Error handling for “Label(s) changed.” Refuses to `lwarpmk limages` until recompile first.
  - Fix: If Computer Modern font is used, ensures `cm-super` or `lmodern` is used.
  - Fixes for `\makebox`.
  - Fixes for `\parbox` inside a `<span>`.
  - MATHJAX: Updated to v2.7.5. Loads the `autoload-all.js` extension. Added `\MathJaxFilename` to select custom scripts.
- packages**
- `textcomp`, `xunicode`: Fix for `\textinterrobang`.
  - `mhchem`: Works with MATHJAX. See section [344](#).
  - `changes`: Updated to v3.1.2.
  - Added `autonum`, `changefont`, `inputrc`, `mathtools`, `metalogox`.

**v0.69:** Error handling, many fixes, improved keyfloat / tocdata.

- Fix for HTML corruption of `lateximage` displays.
  - `\makebox`, `\framebox`: Fix for `(<width,height>)` arguments.
  - `fminipage`: Honors `\minipagewidth`.
- packages**
- `array`, `longtable`: Fix for `\tabularnewline`.
  - `tabularx`, `tabulary`: Fix to require the `array` package.
  - `supertabular`, `xtab`: Fix to clear caption after use.
  - `graphics`: Added a warning if used the `\includegraphics scale` option.
  - `multirow`: Added an error if didn't use `\mrowcell` or `\mcolrowcell` when using `\multirow` or `\multicolumnrow`.
  - `keyfloat`: Updated for v2.00, additional improvements.
  - Added `ctable`, `eqlist`, `eqparbox`, `ftcap`, `listliketab`, `minitoc`, `tocdata`, `topcapt`.

**v0.68:** Error handling, tabulars, footnotes.

- lwarpmk***
- `lwarpmk`: Improved error handling for image generation if compile was incomplete.
  - `tabular`: Fix for `\warpprintonly`.
- packages**
- `longtable`: Improved flexibility for `\endhead`, etc. Improved error reporting if `\endhead`, etc. incorrect for `l warp`.
  - `threeparttable`: Fix for caption type.
  - `hyperref`: Fix for options with braces.
  - `morefloats`: Fix to be loaded early for print output.
  - `listings`: Updated for v1.7.
  - Added `bigfoot`, `fnpara`, `footnotebackref`, `manyfoot`, `tablefootnote`, `threeparttablex`.
  - Added `layouts`, `niceframe`, `perpage`, `showtags`.
  - Prevented `alg`, `algorithmic`, `pdfcprot`, `fncylab`.

**v0.67:** Filename generation, symbol fonts.

- docs**
  - Documentation fix for <project>-images, <project>-images.txt.
  - Added discussion regarding section names. See section 8.4.
- filenames**
  - Added \FilenameNullify and \FilenameSimplify for filename generation. See section 8.4.
  - Core, textcomp, xunicode: Nullified additional symbols during filename generation.
- packages**
  - color: Fix for version number warnings.
  - Added academicicons, bbding, dingbat, eurosym, fontawesome, fontawesome5, marvosym, pifont, typicons.
  - Added changes, easyReview, fitbox, foreign, gloss, karnaugh-map, multicap, nomencl, notes, struktex, umoline, xfakebold.
  - Tested to work as-is with askmaps, curves, euro, karnaughmap, tikz-karnaugh.

**v0.66:** xr, multiple projects, image names/directory, HTML formatting

⚠ Reset the configuration

**lateximage**

⚠ existing projects

⚠ Possible filename changes

**WINDOWS**

**floats**

**lists, table notes**

**tabular**

**indexing**

**minipage**

**colors**

**HTML**

**docs**

- Due to changes in *lwarpmk*, **recompile any existing project a single time using pdflatex filename.tex** or similar, after which *lwarpmk* may then be used with the new configuration files.
- Adds options ImagesDirectory and ImagesName to assign directory and name prefixes for lateximage images. The new defaults include the job-name, allowing the image directories for multiple projects to coexist.
- To reuse existing lateximage directories, add l warp options

```
\usepackage[
    ImagesDirectory={lateximages},
    ImagesName={lateximage-}
]{l warp}
```

If not reused, the existing lateximages directory and lateximages.txt file may be removed.

- Added \FilenameLimit to control the maximum length of the filenames generated by l warp.

- Improved filename generation when special characters or macros are used in section names.

- Fix for **lwarpmk cleanimages** with WINDOWS.

- Fixes for floats in the home page.

- Improved css for definition lists, table notes.

- tabular: Fixes for \par in column specifier, minipage inside tabular.

- Indexing: Fix for a long line of multiple entries.

- \minipagefullwidth: Fix for global changes.

- Added \UseMinipageWidths and \IgnoreMinipageWidths. See section 8.3.3.

- Improved \fbox, \fboxBlock, \fminipage to use current text color.

- Improved HTML output formatting.

- Added discussion regarding invalid HTML. See section 8.1.1.

- Added discussion regarding math in section names, `\imagegraphics scale` option. See section 6.

- Added discussion regarding international languages in section names. See section 8.14.

**packages**

- `caption`: Fix for options clash.
- `xr, xr-hyper`: Now compatible.
- `subcaption`: Improved horizontal spacing.
- `multicol`: Fix for minipage inside `multicols`.
- `multicolrule`: Updated for v1.2.
- `tocbasic`: Minor update.
- `acronym`: Fix for acronym in float caption.
- `kotexutf`: Patch with `pdflatex` and new `lwarp` labels.
- `extramarks, fancyhdr`: Updated for v3.10.
- `memoir`: Added docs regarding version numbers. See section 8.13.
- `zref`: No longer required.
- Added `ar, ed, indentfirst, nameauth, truncate`.
- Verified to work as-is with `changelog`.
- Prevented `colortab, epsf, hyper, picinpar, picins, sistyle, ucs`.

**v0.65:** css layout, alt tags, Japanese.

**page layout**

- Moved the sidetoc to the left side, allowing improved css for margin notes.
- Improved page layout css.

**image alt tags**

- `graphicx \includegraphics`: Added the `alt` key to assign an `alt` tag to an image. Default is “image”, assigned to pass validation.

**duplicate HTML files**

- Detects and causes an error if duplicate HTML file names are generated, caused by identical or similar sectioning names.

**fixes**

- Fix for `tabular*`.
- Fix for `tabular` border colors.
- Fixes `\quad, \enskip`, and figure captions to pass validation.

**Japanese**

- Added `ltj*` classes, `bounddvi, gentombow, lltext, plarydshln, plex, plectarydshln, plectcolortbl, pxatbegshi, pxeveryshi, pxftnright, pxjahyper, tascmac`.
- Verified to work with `plarray, plautopatch, plectarray, plextdearray, pxgentombow, plsiunitx, pxpdfpages, pxpgfrcs, pxpgfmark`.

**packages**

- Added support for `fontspec \textsi` and `\sisshape`.
- Added `multicol`'s `\docolaction`.
- Added `embrac, footnoterange, multicolrule, versonotes`.

**v0.64:** Koma-Script, Japanese, Chinese.

- Japanese
  - Added `utarticle` and related classes.
  - Improved `ujarticle` and related classes.
- Chinese
  - Fix for `biblatex` with CTEX and other classes.
- Koma-Script
  - Fixes for `scrlayer`, `scrlayer-scrpage`.
  - `addlines`: Updated to v0.3.
  - Added `bsheaders`, `gmeometric`, `marginal`, `rmpage`, `scrpage2`.
- packages

**v0.63:** mdframed, Chinese, Japanese, Korean

- localization
  - Added `\linkhomename`: A user-definable name for the **Home** link.
  - Documented `\sidetocname`: A user-definable name for the sidetoc.
  - Fix: `\LinkHome` for print output.
- fixes
- optimizations
  - Moved package load checks to the `l warp` core to reduce the number of `l warp-*` files.
- packages
  - `mdframed`: Fix with `amsthm`, improved titles and font control. Improved rule widths.
- Chinese
  - Fixes for `xeCJK`.
  - Added `xpinyin`, `zhlineskip`.
  - Verified to work with `cjkpunct`, `upzhangsoku`, `zhspacing`.
- Japanese
  - Verified to work with `zxjatype`, `l uatexja`, `l uatexja-fontspec`.
  - Added `bxjsarticle` and related classes.
  - Added `ltjsarticle` and related classes.
  - Added `pLATEX`, `upLATEX`, `ujarticle` and related classes.
  - Prevented `utarticle` and related classes.
  - Prevented `bxckatype`.
- Korean
  - Verified to work with `kotex`, `xetexko`, `l uatexko`.

**v0.62:** MiK $\bar{T}$ E $\bar{X}$  docs, HTML title, CTEX, xeCJK, bitpattern.

- docs
  - Docs: Setting a UTF-8 locale. See section [9.8](#).
  - MiK $\bar{T}$ E $\bar{X}$ : Docs for *MiK $\bar{T}$ E $\bar{X}$  Console* and `miktex-poppler-bin`.
  - HTML subpage titles: Added `\HTMLTitleBeforeSection` and `\HTMLTitleAfterSection` to select whether the HTML `<title>` displays the website name before or after the section name. See section [7.6](#).
- MiK $\bar{T}$ E $\bar{X}$
- HTML `<title>`
  - Fix for package options handling.
  - Fixes for horizontal white space between `fminipage`, `fcolorminipage`, `colorboxBlock`, `fcolorboxBlock`.
  - Logos: Fix for X $\bar{T}$ E $\bar{X}$  logo, improved css, made robust, improved search-engine optimization.
  - `\\\[$1]`: Additional HTML `<br>` if  $$1 > 0$  pt.
  - Fixes for `\includgraphics` filename, and with `FormatWP`.
  - Fix: css for `\textup`.
- fixes

- Fix: Added `\sllshape`.
- Chinese packages**
- Added `ctex` package and related classes, `xeCJK`.
  - Prevented `CJK`, `CJKutf8` unless `xeCJK`, `ctex` are used.
  - `chemfig`: Docs for new macro `\polymerdelim`.
  - `asymptote`: Docs for compilation.
  - `chngpage`: Fix to load `l warp-changepage`.
  - `algorithm2e`: Fix with non-book classes.
  - `register`: Updated to v1.8.
  - `nicefrac`: Improved font control and css, honors nice and ugly.
  - `units`: Improved font control and css, honors tight and loose.
  - `xfrac`: Improved css.
  - `textcomp` and `xunicode`: Fix conflicts with `\textcircled`.
  - `ulem`: Improved compatibility with `CJKulem`, `lateximage`.
  - `MathJax` and `siunitx`: Removed inoperable extension.
  - Added `bitpattern`, `pdfcomment`, `pdfmarginpar`, `tram`, `unitsdef`, `xexchangebar`.
  - Added `musicography`, `octave`, `semantic-markup`.
  - Added `2in1`, `flippdf`, `notespages`, `rviewport`, `twoup`.

**v0.61:** Custom compilation, EPS-related packages, documentation, indexes.

- docs**
- Split index into multiple indexes.
  - Improved documentation regarding font selection. See section [7.4](#).
  - Added documentation regarding debugging options. See section [35](#).
  - Added documentation regarding HTML entities inside program listings. See section [8.2.1](#).
  - Added options to specify the shell commands to execute for `l warpmk print` and `l warpmk html`, allowing the use of `l warp` with `perltx`, `pythontex`, etc. If not specified, these are set automatically depending on the LATEX engine, `--shell-escape`, and `l warp` options. See section [9](#).
  - Changed macro names to match `\displaymathother`, `\displaymathnormal`:

Old	New
<code>\StartDynamicMath</code>	<code>\inlinemathother</code>
<code>\StopDynamicMath</code>	<code>\inlinemathnormal</code>

- custom compiling**
- ⚠ changed names**
- fixes**
- Fix: Paragraph tags in a `tabular`.
  - Fix: `supertabular` and `xtab` captions.
  - Fix: DVI LATEX `\includegraphics` EPS images.
  - Fix: `newfloat` lists.
  - Fix: css footnotes text align, minipage tabular and footnote margins.
- packages**
- Added `epsfig`, `psfrag`, `psfragx`, `pstool`.
  - Added `copyrightbox`, `pdfprivacy`, `thinsp`, `threadcol`, `uspace`.
  - Added `chkfloat`, `cmdtrack`, `dprogress`, `lua-visual-debug`, `refcheck`, `srcltx`, `srtex`, `vpe`, `xbmks`.

**v0.60:** Fixes for longtable, listings.

- **fixes** longtable, etc.: Fixes for slowdown and memory management for very long tables.

- **listings:** Fix for HTML entities, and also when used inside a list.
- **diagbox:** Fix for incorrect HTML par tags.

- **packages** Added 2up, booklet.

- Added bophook, draftfigure, fullminipage, grid-system, layaureo.
- Added leading, widows-and-orphans.
- Added fancytabs, thumb, thumbs.

**v0.59:** DVI *latex*, MATHJAX, asymptote, pdftricks and pstricks, epstopdf, brqen.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, **recompile any existing project a single time** using **pdflatex filename.tex** or similar, after which *lwarpmk* may then be used with the new configuration files.

*lwarpmk*

- Added an error if *lwarpmk.conf*'s format has changed and the document must be recompiled.
- Added a warning if the *lwarpmk.conf* configuration file appears to be for the wrong operating system, in case files are transferred between systems.
- Added

*lwarpmk epstopdf <list-of-EPS-files>*

to quickly convert a document's EPS images to PDF or SVG. See section 8.8.

DVI *latex*

- Added support for DVI *latex*. See section 7.5.

*latemxmk*

- Fix for --shell-escape with *latemxmk*.

math

- Updated MathJax script to v2.7.4.
- Fix: Mathjax chapter number removed from non-numeric tagged equations.
- Added MathJax support for nicefrac, units.
- Fix for \[ and \] with \displaymathnormal.

images

- Fix for \includegraphics filename expansion.
- \includegraphics now works with .pdf and .eps filename extensions.

packages

- Moved amsmath out of the l warp core.
- Fix for chemformula \NMR.
- Added asymptote, pdftricks, pstricks, pst-eps.
- Added breqn, Slunits.
- Added bxpapersize, canoniclayout, draftcopy, fnbreak, nccfancyhdr.
- Added accsupp, axessibility.
- Added xunicode.
- Improved and now supports epstopdf.
- Tested to work as-is: eepic, sepfootnotes.
- Added information about setting up a development version of l warp.

docs

**v0.58:** Extensive improvements in indexing, glossaries. Adds PDF-inclusion packages.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, **recompile any existing project a single time** using `pdflatex filename.tex` or similar, after which *lwarpmk* may then be used with the new configuration files.
- *lwarpmk*: Added the `-p` option to specify the project name.
- *lwarpmk*: Now uses *makeglossaries* for glossary generation, allowing the processing of multiple glossaries at once.
- Added lwarf option `GlossaryCmd` to specify the shell command used by `lwarpmk printglossary` and `lwarpmk htmlglossary`. Defaults to `makeglossaries`.
- Docs: Extra indexing options. See section 8.6.14.
- Added support for *makeindex*. (Previously supported only *xindy*.) Also added indexing packages listed below.
- Added lwarf options `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to specify shell commands used by `lwarpmk printindex`, `lwarpmk htmlindex`, and `latexmk`. May be preset with the `makeindex` or `xindy` lwarf options. See section 7.5.
- Added lwarf options `makeindex` and `xindy` to set `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to sensible values for a typical single index. See section 7.5.
- Added lwarf option `makeindexStyle` to tell *lwarpmk* to use a custom style instead of *lwarf.ist*. See section 8.6.20.
- Fix for index entries with `\see`, `\seealso`, `\emph`, `\textbf`, etc.
- Replaced each `\csuse` with `\@nameuse` for improved error detection.
- Additional internal print/HTML macro selection improvements.
- Fix: `\printindex` finishes pending `\index` writes first.
- Fixes for *memoir*: `makeidx`, `ccaption`, multiple indexes, `\specialindex`.
- Fixes for *komascript*: Indexing improvements.
- Added `imakeidx`, `index`, `repeatindex`, `splitidx`.
- Added `attachfile`, `attachfile2`, `intopdf`, `pdfpages`, `pdfx`.
- Added `cases`.
- Tested to work as-is: `notes2bib`, `hvindex`.

**v0.57:** algorithm2e, float styles, tabular packages, internal improvements.

MathJax

math macros

dynamic math

⚠ new name

- Added support for MathJax equations with `\footnote`, `\footnotemark`.
- Added `\StartDefiningMath` and `\StopDefiningMath` for use when defining macros in the preamble which contain \$. See section 8.7.7.
- Added `\inlinemathother` and `\inlinemathnormal` to delimit math expressions which depend on a variable condition such as a counter. Such expressions will not be hashed for reuse, and will be converted to SVG math images even when MathJax is enabled. See section 8.7.8.
- Renamed `\EndDefiningTabulars` to `\StopDefiningTabulars`.

- latextimage alt tags**
    - Improved localization for `latextimage` HTML alt tags. For SVG math images, the alt tag under some conditions will be set to `\MathImageAltText`, which defaults to `math image`. For packages, the alt tag is set using the package name followed by `\PackageDiagramAltText`, which defaults to `diagram`.  
Ex:  

$$(-xy- \text{ diagram})$$

See section [7.6](#).
    - Fix: Improved print/HTML macro selection.
  - misc. fixes**
    - Fix: `\href` text catcodes.
    - Fix: `\subref` text.
    - Fixes: Colored `\rule` and `\boxframe`.
  - packages**
    - `float, rotfloat`: Adds support for float styles `ruled` and `boxed`.
    - `float`: Fix: Do not create `\l@<type>` until `\listof` is used.
    - `marginnote`: Fix: Long optional argument.
    - `ellipsis`: Adds `\midwordellipsis`.
    - `breakurl`: Fix for text catcodes.
    - Added `algorithm2e, register, ltablex, xltabular, xellipsis, trimclip, errata, vowel, xpiano`.
    - Prevents `glossary`.
    - Tested to work as-is with `gauss, phonrule, piano, Slunits, tikzcodeblocks`.
- v0.56:** Shell escape, tabular packages.
- lwarfmk**
    - Added  
`lwarfmk pdftosvg <list-of-PDF-files>`  
 to quickly convert a document's PDF images to SVG, for use with HTML. See section [8.8](#).
    - Added support for `--shell-escape`. See section [7.3](#).
  - tabular**
    - Added support for `array w` and `W` columns.
    - Fix: `\multicolumn` parameter handling.
    - Added support for double `\hlines`, `\midrules`, and vertical rules.
    - Added support for `arydshln` dashed lines with `HTML tabular`, but reverts to plain rules for `latextimage` and `SVG math array`.
  - misc. fixes**
    - Fix: `\thinspace`.
    - Fix: `paralist` compact environments.
  - packages**
    - Added `parnotes, quoting, lua-check-hyphen, toccenter, underscore`.
    - Added `bibunits`.
    - Tested to work as-is with `babelbib, bodegraph, fast-diagram, nicematrix, structmech`.

**v0.55:** Various fixes.

- |            |  |
|------------|--|
| misc fixes | <ul style="list-style-type: none"> <li>Fix: Extraneous space in file links, which also prevented <i>Calibre</i> EPUB conversions.</li> <li>Fix: Float optional argument regression.</li> <li>Fix: \ForceHTMLTOC with \phantomsection.</li> <li>Fix: Overfull boxes in lateximages.</li> <li>Fix: QED symbols in lateximage.</li> </ul> |
| packages   | <ul style="list-style-type: none"> <li>koma-script: Fix: Figure with \centering, etc.</li> <li>Added clrdblpg.</li> </ul>  |

**v0.54:** Float \centering, improved image checks.

- | <b>⚠ Reset the configuration</b>          | <ul style="list-style-type: none"> <li>Due to changes in <i>lwarfmk</i>, <b>recompile any existing project a single time using pdflatex filename.tex</b> or similar, after which <i>lwarfmk</i> may then be used with the new configuration files.</li> </ul>  |                    |                    |             |            |               |               |   |               |   |              |
|---|--|--------------------|--------------------|-------------|------------|---------------|---------------|---|---------------|---|--------------|
| <i>lwarfmk</i>                            | <ul style="list-style-type: none"> <li><i>lwarfmk</i> limages checks for the presence of the HTML version of the document and valid image references before attempting to create the lateximages.</li> <li><i>lwarfmk</i>: Improved error message if configuration file does not exist.</li> </ul>   |                    |                    |             |            |               |               |   |               |   |              |
| <b>BibTeX</b>                             | <ul style="list-style-type: none"> <li>Added documentation for avoiding error with BibTeX and \etalchar. See section 8.6.9.</li> </ul>   |                    |                    |             |            |               |               |   |               |   |              |
| <b>polyglossia</b>                        | <ul style="list-style-type: none"> <li>Added documentation regarding polyglossia. See section 8.15.4.</li> </ul>   |                    |                    |             |            |               |               |   |               |   |              |
| <b>macros in section names</b>            | <ul style="list-style-type: none"> <li>Added documentation regarding the use of macros in section names. See section 8.1.</li> </ul>   |                    |                    |             |            |               |               |   |               |   |              |
| <b>document encoding</b>                  | <ul style="list-style-type: none"> <li>Renamed and added package options:</li> </ul>   |                    |                    |             |            |               |               |   |               |   |              |
| <b>⚠ New and revised encoding options</b> | <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center; padding: 2px;">Old Package Option</th> <th style="text-align: center; padding: 2px;">New Package Option</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; padding: 2px;">xdyFilename</td> <td style="text-align: center; padding: 2px;">xindyStyle</td> </tr> <tr> <td style="text-align: center; padding: 2px;">IndexLanguage</td> <td style="text-align: center; padding: 2px;">xindyLanguage</td> </tr> <tr> <td style="text-align: center; padding: 2px;">—</td> <td style="text-align: center; padding: 2px;">xindyCodepage</td> </tr> <tr> <td style="text-align: center; padding: 2px;">—</td> <td style="text-align: center; padding: 2px;">pdftotextEnc</td> </tr> </tbody> </table> | Old Package Option | New Package Option | xdyFilename | xindyStyle | IndexLanguage | xindyLanguage | — | xindyCodepage | — | pdftotextEnc |
| Old Package Option                        | New Package Option   |                    |                    |             |            |               |               |   |               |   |              |
| xdyFilename                               | xindyStyle   |                    |                    |             |            |               |               |   |               |   |              |
| IndexLanguage                             | xindyLanguage  |                    |                    |             |            |               |               |   |               |   |              |
| —   | xindyCodepage  |                    |                    |             |            |               |               |   |               |   |              |
| —   | pdftotextEnc   |                    |                    |             |            |               |               |   |               |   |              |
| <b>floats with \centering, etc.</b>       | <p>Use these options along with inputenc or inputenx to process documents in an encoding other than UTF-8. See section 7.4.</p> <ul style="list-style-type: none"> <li>Floats now honor \centering, \raggedright, \raggedleft, and their ragged2e equivalents, when placed directly after:</li> </ul> <pre>\begin{floattype} \centering</pre>  |                    |                    |             |            |               |               |   |               |   |              |
| <b>misc. fixes</b>                        | <ul style="list-style-type: none"> <li>tikz: \pgfpicture, fit, align, font.</li> <li>ragged2e: \centering etc.</li> <li>hyperref: \hypertarget was creating duplicate of \label.</li> <li>hyperref: Active chars inside \hyperref, \hyperlink.</li> <li>hyperref: \ref inside \hyperlink caused a nested HTML link.</li> <li>glossaries: Fix when not using babel or polyglossia.</li> </ul>   |                    |                    |             |            |               |               |   |               |   |              |

- `textcomp`: `\textperthousand`.
- L<sup>A</sup>T<sub>E</sub>X core verse environment: line spacing.
-  **packages**
- Removed `\citetitle`, adjusted `\attribution`.
- `memoir`: Minor update for v3.7g.
- Added `inputenx`, `bibunits`, `chngpage`, `forest`, `magaz`, `gridset`.
- Prevents loading `ae`, `aecc`, `t1enc`, and `wasysym`.

**v0.53:** Improved image checks.

- lwarpmk***
- `lwarpmk`: Added a warning about corrupted images due to the need to recompile the document one more time.
  - `lwarpmk`: Added the `lwarpmk cleanimages` command.
  - Added documentation for `lwarpmk cleanimages` and `lwarpmk pdftohtml`.

**v0.52:** Improved footnotes, SVG math.

- documentation**
- Improved install instructions regarding `l warp_baseline_marker.png`.
  - Added documentation regarding footnotes in section headings, and footnotes with `\VerbatimFootnotes` from `fancybox`, `fancyvrb`. See section 8.5.4.
  - Added documentation regarding font selection when using X<sub>E</sub>L<sup>A</sup>T<sub>E</sub>X or L<sup>A</sup>u<sub>L</sub>AT<sub>E</sub>X with `fontspec` and traditional font packages. See section 7.4.
- SVG math**
- Fix: Limit the number of background tasks when generating `lateximages`.
  - Added user-adjustable SVG math font scaling. See section 80.3.
  - Added warnings if `l warp_baseline_marker.png` is not present, or if `graphicx` or `graphics` is not loaded.
  - Improved `\ensuremath` hashing expansion.
  - Fix: `equation*` with `split`.
  - tabbing now works inside a `lateximage`. Use for math in tabbing.
- MathJax**
- Fix: MathJax script was not executing in some conditions.
  - Added `\CustomizeMathJax` to add custom functions. See section 8.7.
- footnotes**
- Fix: Footnote numbering when using `HTMLDebugComments`.
  - Fix: Footnote paragraph tags.
  - Fix: `FootnoteDepth` defaults to `\subsubsection`.
- misc. fixes**
- Fix: `\kill` in a `lateximage`.
  - Fix: `\FileDepth`, misc. others, when input encoding is not `utf8`.
  - Fix: `\texorpdfstring` in a section name.
- packages**
- `hyperref` emulation: Fix for #, %, &, ~, \_ characters in URLs.
  - `fancybox`, `fancyvrb`: Initial support for `\VerbatimFootnotes`.
  - `nicefrac`: Added with fix for `\ensuremath`.
  - `graphicx`: Fix for option defaults. Added v1.1a/b options.
  - `endfloat`: Updated for v2.6.
  - `url`: Fixes for active characters.

**v0.51:** Improved svg math, added numerous chemistry packages.

documentation	<ul style="list-style-type: none"><li>Docs: Added <a href="#">Things to avoid</a>.</li><li>Docs: Added to <a href="#">Converting an existing document</a>.</li><li>Docs: Multiple authors and affiliations with custom classes. See section <a href="#">8.6.1</a>.</li><li>Docs: tikz with matrices. See section <a href="#">8.8.1</a>.</li></ul>
SVG math	<ul style="list-style-type: none"><li>Improved svg math baseline.</li><li>Improved svg math font and color.</li><li>Faster svg math rendering.</li><li>Improved support for display math containing complicated math objects, such as <code>tikz-cd</code>. See section <a href="#">8.7.9</a>.</li><li>Fix: <code>\addcontentsline</code> inside svg math.</li><li>Fix: SVG math containing an embedded <code>lateximage</code>.</li></ul>
MathJax	<ul style="list-style-type: none"><li>MathJax now handles <code>\ensuremath</code> in expressions.</li></ul>
misc. fixes	<ul style="list-style-type: none"><li>Fix: Added <code>alignat</code> environment.</li><li>Fix: <code>afterpackage</code> no longer required, which conflicted with <code>scrlfile</code>.</li><li>Fix: <code>titling</code> <code>\thanks</code> mark.</li><li>Fix: <code>fancybox</code> improvements.</li><li>Fix: <code>tikz</code> <code>\tikz</code> macro. (Previously only the <code>tikzpicture</code> environment worked.)</li><li>Fix: <code>tikz</code> with optional argument.</li></ul>
packages	<ul style="list-style-type: none"><li>Added <code>mhchem</code>, <code>chemfig</code>, <code>chemformula</code>, <code>chemmacros</code>, <code>chemnum</code>, <code>chemgreek</code>, <code>epstopdf-base</code>, <code>grid</code>, <code>ltxgrid</code>.</li></ul>

**v0.50:** Improved svg math.

svg math	<ul style="list-style-type: none"><li>SVG math and other <code>lateximages</code> now are converted to SVG using parallel background tasks, utilizing all available CPU cores.</li><li>Inline SVG math image file names now are MD5 hashes made from their source LATEX code. Identical inline math expressions, such as multiple instance of <code>\$x\$</code>, now share a single image file. This reduces the number of images to store, transmit, process, and display. Each image file is only converted to SVG a single time, and reused if it already exists. Display math and other forms of SVG image such as <code>picture</code> and <code>Tikz</code> still use individual image files which are recreated each time <code>lwarfmk limages</code> is run.</li><li>Fixes: SVG math and/or <code>\underline</code> in a sectioning file name.</li><li>Improved svg display math and tags.</li><li>Improved svg math and <code>siunitx</code> <code>alt</code> tags.</li><li>Improved <code>siunitx</code> units.</li><li>Fix: <code>\ensuremath</code> with MathJax now creates a <code>lateximage</code>.</li><li>Fix: <code>\centering</code>, etc. in svg math, <code>lateximage</code>, <code>Tikz</code>.</li></ul>
misc. fixes	<ul style="list-style-type: none"><li>Fix: Made various macros robust, additionally fixing <code>authblk</code>.</li><li>Fix: <code>ntheorem</code> if neither standard nor <code>amsthm</code> selected.</li></ul>

- Fix: `listings`: Improved column alignment.
  - Fix: Load `fontspec` if necessary.
- packages**
- Added `xy`, `epstopdf`, `diagbox`, `pbox`, `bytefield`, `axodraw2`, `phfqt`, `schemata`, `dblfloatfix`, `nonfloat`, `morefloats`.

**v0.49:**

- tabular**
- Added `xcolor \rowcolors`.
  - Fix: `\noalign` inside a `tabular`.
- math**
- Fix: `\eqref` in a caption.
- misc fixes**
- Fix: Incorrect PDF font size changes caused occasional HTML corruption.
  - Fix: `printlen` changes are now grouped for HTML output.
- packages**
- Added `vwcol`, `verbbars`, `hyphenat`, `lineno`, `fnlineno`, `figsize`, `hypdestopt`, `pagegrid`, `pdfrender`, `luacolor`, `resizegather`.

**v0.48:**

- documentation**
- Added some documentation regarding converting an existing document.  
See section 6.
- cleveref**
- Updated compatibility for new `cleveref` v0.21.
- tabular**
- Fix: Ignores optional tabular column arguments.
- minor updates**
- Added `\leftline`, `\centerline`, `\rightline`.
  - Lists have improved font control via `\makelabel`.
  - Print-mode `lateximage` now boxed to the natural width of its multiline contents.
  - `abstract` now allows an optional name, as required by some classes.
- math**
- Fix: Improved spacing, `\mbox`, and font sizes with SVG math, Tikz.
  - `siunitx`: Improved SVG math, fraction compatibility, color output.
- misc. fixes**
- Fix: LOF/LOT links.
  - Fix: Virtual page size grouping caused excessive PDF page breaks.
  - Fix: Parsing similar package names in a single `\usepackage`.
  - Fix: Adapts to classes without `\part`.
  - Fix: `\newline` in `\title` was causing `<br>` in window title.
  - Fix: `\maketitle` with `\cr`, `\crr`, `\noalign`, for `IEEEtran` class.
  - Fix: `xfrac` neutralized `BlockClass` and others.
  - Fix: `todonotes` and `luatodonotes`: Improved `\todototoc`.
- packages**
- Added `colortbl`, `chapterbib`, `acro`, `acronym`, `hypernat`, `hypcap`, `stfloats`, `vmargin`, `fancyheadings`.
  - `fancyref`: Now directly supported.

**v0.47:**

- |  |   |
|--|---|
| <a href="#">math</a><br><a href="#">packages</a> | <ul style="list-style-type: none"><li>• Improved SVG math baseline and sizing.</li><li>• Fixes: <code>svgmath</code> in captions, subcaptions, <code>\nameref</code>.</li><li>• Fixes: Line wrap at hyphen in HTML output.</li></ul> <ul style="list-style-type: none"><li>• Added <code>endheads</code>, <code>multitoc</code>, <code>sectionbreak</code>, <code>blowup</code>, <code>xurl</code>.</li></ul> |
|--|---|

**v0.46:**

- |   |  |
|---|--|
| <a href="#"><span style="color: red;">⚠</span> name change</a><br><a href="#">misc. fixes</a> | <ul style="list-style-type: none"><li>• <code>\PrintStack</code> changed to <code>\LWRPrintStack</code>.</li><li>• Fix: Empty lines between tabular rows.</li><li>• Fix: Stack unnesting.</li><li>• Fix: SVG math and <code>lateximages</code> in numerous situations.</li><li>• Fix: Spaces in <code>\usepackage</code>.</li><li>• Fix: Now allows MATHJAX inside <code>verse</code>.</li></ul> |
|---|--|

**v0.45:**

- |  |   |
|--|---|
| <a href="#">documentation</a><br><a href="#">memoir</a><br><a href="#">cross-references</a><br><a href="#">math</a><br><a href="#">bibliography</a><br><a href="#">misc. fixes</a> | <ul style="list-style-type: none"><li>• Improved <i>MiKTeX</i> install instructions.</li><li>• Improved graphics and <code>epstopdf</code> instructions.</li><li>• Updates to the <a href="#">Introduction</a>.</li><li>• Added <code>memoir</code>, <code>memhfixc</code>. See section <a href="#">8.13</a>.</li><li>• Fix: Now allows underscores in labels.</li><li>• Fix: <code>\_</code> and <code>\&lt;blank&gt;</code> in section/file names.</li><li>• Fix: Now allows MATHJAX inside tabbing.</li><li>• Fix: Bibliography <code>\em</code> names.</li><li>• Added <code>cite</code>, <code>natbib</code>, <code>backref</code>. (Also works as-is with <code>biblatex</code>.)</li><li>• Fix: Empty lines between tabular rows.</li><li>• Fix: “Improper <code>\prevdepth</code>” with <code>minipages</code>, lists.</li><li>• Fix: Incorrect SVG math and <code>lateximages</code> with <code>subfig</code>.</li><li>• Fix: <code>Lateximages</code> from incorrect pages with <code>Mathjax</code>.</li><li>• Fix: Missing <code>sitetoc</code> if using <code>listings</code>.</li><li>• Fix: Added an <code>array</code> emulation package.</li></ul> |
| <a href="#">packages</a>   | <ul style="list-style-type: none"><li>• Added <code>subfigure</code>, <code>prettyref</code>, <code>hanging</code>, <code>midpage</code>, <code>flafter</code>, <code>fltrace</code>, <code>changebar</code>, <code>endfloat</code>, <code>continue</code>, <code>fwlw</code>, <code>turnthepage</code>, <code>footnpag</code>, <code>pagesel</code>, <code>textfit</code>, <code>titleref</code>.</li></ul>  |

**v0.44:**

- |  |   |
|--|---|
| <a href="#">koma-script</a><br><a href="#">HTML title and author</a> | <ul style="list-style-type: none"><li>• Added koma-script classes (except <code>scrlltr2</code>, <code>scrjura</code>).</li><li>• Added <code>scrextend</code>, <code>scrlayer</code>, <code>scrlayer-notecolumn</code>, <code>scrlayer-scrpage</code>, <code>scrhack</code>, <code>tocstyle</code>, <code>tocbasic</code>.</li><li>• Added <code>\HTMLTitle</code>. Fixed web page title if <code>\HTMLTitle</code> empty and no <code>\title</code> given and not using <code>titling</code> package.</li><li>• Fixed web page author if <code>\HTMLAuthor</code> is empty and <code>\author</code> is not given.</li></ul> |
|--|---|

- encodings**
  - If using `pdflatex`, automatically loads T1 and UTF-8 encodings. (Additional `fontenc` encodings may be loaded after `l warp`.)
- lists**
  - Added `list` and `trivlist` environments, `hang`.
- tabular**
  - Fix: `\multicolumn` alignment if formatting for a word processor.
  - Added `ltxtable`.
- math**
  - Fix: MATHJAX combined with `lateximages`.
  - `algorithmicx`: Improved comment symbol and floating.
- packages**
  - Completed `todonotes` and `luatodonotes`.
  - Added `todo`, `easy-todo`, `fixmetodonotes`, `fixme`.
  - Added `soulutf8`, `soulpos`, `cancel`.
  - Added `section`, `fancyref`, `ifoddpage`.
  - Added `preview`, `atbegshi`, `watermark`.
  - Improved `tocloft` `\newlistof` and `\newlistentry`.

**v0.43:**

- footnotes**
  - Docs: Reorganized HTML customization, added an HTML settings table. See section 7.6.
  - Added `FootnoteDepth` to control the placement of pending footnotes before section breaks. By default, pending footnotes are printed before each `\ subparagraph` or higher.
- sectioning**
  - Fix: Expansion in section name.
- tabular**
  - Fix: Ignore spaces in tabular column specification.
  - Fix: Tabular rules at bottom or when finishing incomplete rows.
  - Fix: `\multicolumn` at/bang/before/after specifications, trim, and vertical rules.
  - Fix: `supertabular` and `xtab` column misalignment.
- math**
  - Fix: `equation*`.
  - Fix: SVG math in a section name.
  - Fix: `\ref` and `\eqref` in SVG math.
- packages**
  - Added `todonotes` and `luatodonotes` (but only disabled).
  - Added `breakurl`.
  - `hyperref`: Fix: Several macros were made robust, `\Gauge` added.

**v0.42:**

- Support TEX!**
  - Added TEX development support page. (See page 2.)
  - Improved assistance for word-processor conversions when boolean `FormatWP` is set true. See section 11.
    - The boolean `FormatWordProcessor` has been renamed `FormatWP`.
    - The boolean `HTMLMarkFloats` has been renamed `WPMarkFloats`.
    - New booleans control whether to place additional marks around minipages, at the table of contents, at the LOF and LOT, and whether to print math as LATEX source for copy/paste into the *LibreOffice Writer TeXMaths* extension.
- word-processor conversion**
  - ⚠️ name change
  - ⚠️ name change

- Improved formatting for numerous objects. See section 11.

`tabbing`

- Add: tabbing environment.

`overpic`

- Add: overpic package. See section 382.

`math`

- Fix: Text copy/paste of  $\mathcal{M}\mathcal{S}$  math environment numbers and names.

- Improved `\ensuremath`.

- MATHJAX with `siunitx`: Updated script and documentation.

`symbols`

- `textcomp`: Improved `\textinterrobangdown`.

- `realscripts`: Fix for subscripts in a `lateximage`.

`load order`

- `morewrites`: Enforces loading before `l warp`.

#### v0.41:

`tabular`

- Added tabular vertical rules, subject to some limitations. See the rules section of section 8.10.1.

- Improved booktabs: Width and trim are honored.

$\triangle$  `new syntax`

- Added `\mcolrowcell` for empty cells inside a `\multicolumnrow`. Use `\mcolrowcell` instead of `\mrowcell` for two-dimensional cells created by `\multicolumnrow`. Continue to use `\mrowcell` for empty cells in a `\multirow`. See section 359.2 on page 869.

- Fix: Unfinished tabular rows are automatically filled.

- Fix for tabular column specifiers while using babel-french. (`\NoAutoSpacing` is activated then nullified inside the tabular, due to a conflict with the tabular column parsing code.)

#### v0.40:

`graphics, graphicx`

- `graphics` and `graphicx` have been moved from the `l warp` core, and are only loaded if requested with `\usepackage`.

`\includegraphics path`

- Improved `graphics` `\graphicspath` support. Multiple image directories may now be used. Refer to .pdf files without a file extension to allow the HTML version to use a .svg, .png, .jpg, or .gif version instead. See section 8.8.

- `grffile` is now directly supported instead of emulated.

- Fix for `bigdelim`, and improved documentation. See section 145.

- Improved LATEX and `textcomp` symbols.

- Fix for LATEX logos and `\InLineClass`, etc. inside a `lateximage`.

- Fix for `xltextra` with X-LATEX.

- Fixes for `tocbibind` with `\simplechapter`, etc.

- Fixes for `\multicolumnrow` and `\nullfonts` with older versions of `multirow` and `xparse`.

- Added `\underline`.

- Added `adjmulticol`.

- Added `cuted`, `midfloat`.

- Added `pfnote`, `fnpos`, `dblfnote`.

- Added `stabular`, `tabls`.

`sectioning`

- Added `sectsty`, `anonchap`, `quotchap`.

**v0.39:****title pages**

 \published and  
  \subtitle

 load order

**tabular****multi column/row cell**

 macros inside tabular

 tabular defined inside  
  another environment

**tabular****margins****page layout**

- Improved the titlepage HTML code, \thanks notes, and \maketitle. `titling` is no longer required, but is still supported. The \published and \subtitle fields are no longer provided, but \AddSubtitlePublished replicates them using `titling`. See section 66.8. `authblk` is added, and should be loaded before `titling`. See section 66.
- \multirow now supports the new optional vpos argument.
- Added \multicolumnrow for combined \multicolumn and \multirow. See section 359.2.
- Tabular special cases:
  - Added \TabularMacro to mark custom macros inside tabular data cells, avoiding row corruption. See section 8.10.1.
  - Added \ResumeTabular for use when a tabular environment is defined inside another environment. See section 8.10.1.
- Added supertabular, xtab, bigstrut, bigdelim.
- Added fullwidth.
- Added addlines, anysize, a4, a4wide, a5comb, textarea, zwpagelayout, typearea, ebook.

**v0.38:****forced single-pass compile**

- Added `lwarpmk print1` and `lwarpmk html1` actions to force a compile of the project a single time. Useful when multiple passes are not needed, or changes were not detected.

**starred sections**

- Added \ForceHTMLPage and \ForceHTMLTOC to force a starred sectional unit onto its own HTML page and with its own TOC entry. See section 8.6.2.

**updated tutorial**

- Modified the tutorial to use the new \ForceHTMLPage and \ForceHTMLTOC macros.

**packages****font size**

- Added appendix, tocbibind, fncychap, fix2col.

- Added relsize, scalefnt.

- Added realscripts, metalogo, xltxtra.

- Added grffile, romanbar.

- Added arabicfront, chappg, nonumonpart, nopageno, romanbarpagenumber.

- Docs: Improved description of the use of front/back matter. See section 8.6.

- Fix: color requests xcolor.

- Fix: \part for article class.

**v0.37:****\include for HTML****latexmk**

- \include now maintains independent .aux files for HTML versions.

- comment, used by lwarp, now maintains independent cut files for print and HTML versions, helping latexmk to better know whether to recompile.

- Improved support for L<sup>A</sup>T<sub>E</sub>X accents, textcomp, siunitx symbols.

- Improved babel-french handling for load order and ~ tilde.

**accents and symbols****babel-french**

**v0.36:**

- Recorganized the documentation section regarding special cases and limitations. (Section 8)
- Improved source formatting.
- \fbox and related now use \fboxsep and \fboxrule.
- \makebox and \framebox now use width and position.
- \fcolorbox and related now work inside a lateximage.
- boxes and frames**
- babel-french: Improvements for French variants, load order, footnotes, ellipses.
- babel-french**
- footnotes
- Improved footnote numbering. lateximage footnotes now appear as regular footnotes to match the numbering of the print version. Also fixed a regression with MATHJAX.
- siunitx
- Improved siunitx units.
- Fix for filenames while using MATHJAX.
- Fix for \rule when xcolor is not loaded.
- Added transparent, upref.

**v0.35:** Fix: \textbf and related.

**v0.34:****⚠ Optional arguments**

- BlockClass's optional argument has been moved in front of the mandatory argument:

BlockClass[style]{class} (NEW)

instead of:

BlockClass{class}[style] (OLD)

This change makes it more consistent with L<sup>A</sup>T<sub>E</sub>X standards, and avoids problems with space between arguments.

- Likewise, \InlineClass's optional argument now comes before the mandatory arguments:

\InlineClass[style]{class}{text}

- Improved compatibility between spans, minipages, lists, frames, and math. Handles minipages and lists inside an HTML span, such as an \fbox containing a minipage, although with minimal HTML fomatting. See section 8.3.3. \fboxBlock is added to frame minipages, tables, and lists with full HTML formatting but no longer inline, and behaves as \fbox for print output. The fminipage environment is added for framed minipages, as an environment with full HTML formatting, and draws a framed minipage in print output. See section 8.3.5. \fbox and minipages now often work in svg math and lateximages. MATHJAX supports \fbox, but not \fboxBlock nor fminipage.

**spans with minipages**

- Improved compatibility between lateximage and minipage, \parbox, \makebox, \fbox, \framebox, \raisebox, \scalebox, \reflectbox, tabular, booktabs.

**framing minipages**

- Improved font control for lateximagees and svg math.
- Added the eqnarray environments.
- fancyvrb is no longer required (preloaded), but is still supported.

**lateximage, svg math, tabular****eqnarray****verbatim packages**

- Added `verbatim` and `moreverb`.
- Added `fancybox`, `boxedminipage2e` and `shadow`.
- `enumitem` is no longer required, but is still supported.
- Added `enumerate` and `paralist`.
- `titleps` is no longer required, but is still supported.
- Added `crop`.
- Added `rotfloat`, `marginfit`, and several minor packages; see the change log.
- Adds fixed-width HTML spaces around punctuation when using `babel-french`. LuaTEX does not yet use the extra punctuation spacing.

**v0.33:**

- Tabular @ and ! columns now have their own HTML columns.
- & catcode changes are localized, perhaps causing errors about the tab alignment character &, so any definitions of macros or environments which themselves contain `tabular` and & must be enclosed within `\StartDefiningTabulars` and `\StopDefiningTabulars` (previously called `\EndDefiningTabulars`). See section 43. This change is not required for the routine use of tables, but only when a table is defined inside another macro or environment, and while also using the & character inside the definition. This may include the use inside conditional expressions.
- Several math environments were incorrectly placed inline. Also, for `amsmath` with SVG math, the `fleqn` option has been removed, resulting in improved spacing for aligned equations.
- Bug fixes; see the changelog.

**v0.32:** Bug fixes; no source changes needed:

- `lwarpmk` has been adjusted to work with the latest `luatex`.
- Spaces in the `\usepackage` and `\RequirePackage` package lists are now accepted and ignored.
- Fix for the `glossaries` package and `\glo@name`.

**v0.31:** Bug fix; no source changes needed:

- Improved compatibility with `keyfloat`, including the new `keywrap` environment.

**v0.30:****⚠ l warp-newproject**

- `l warp-newproject` has been removed, and its functions have been combined with `l warp`.

To modify existing documents, remove from the document source:

```
\usepackage{l warp-newproject}
```

The `l warp` package now produces the configuration files during print output, and also accepts the option `lwarpmk` if desired.

**⚠ HTML setup changes.**

- A number of macros related to HTML settings have been converted to options, and other macros and options have been renamed to create a consistent syntax:

Old Macro	New Package Option
\HomeHTMLFileName \HTMLFileName \useLatexmk \warpOSwindows	HomeHTMLFilename HTMLFilename \latexmk OSWindows
Old Package Option	New Package Option
lwarpmklang (new)	xindyLanguage xindyStyle
Old Macro	New Macro
\MetaLanguage \HTMLAuthor \NewHTMLDescription \SetFirstPageTop \SetPageTop \SetPageBottom \NewCSS	\HTMLLanguage \HTMLAuthor \HTMLDescription \HTMLFirstPageTop \HTMLPageTop \HTMLPageBottom \CSSFilename

- Per the above changes, in existing documents, modify the package load of `lwarp`, such as:
 

```
\usepackage[
  HomeHTMLFilename=index,
  HTMLFilename={},
  xindyLanguage=english
]{lwarp}
```
- The file `lwarp_html.xdy` has been renamed `lwarp.xdy`. To update each document's project:
  1. Make the changes shown above.
  2. Recompile the document in print mode. This updates the project's configuration files, and also generates the new file `lwarp.xdy`.
  3. The old file `lwarp_html.xdy` may be deleted.
- The new `lwarp` package option `xindyStyle` may be used to tell `lwarpmk` to use a custom .xdy file instead of `lwarp.xdy`. See section [8.6.21](#).
- Improvements in index processing:
  - `xindy`'s language is now used for index processing as well as glossary.
  - Print mode without `latextmk` now uses `xindy` instead of `makeindex`.
  - `texindy/xindy` usage depends on `pdflatex` vs `xelatex`, `lualatex`.
  - For `pdflatex` and `texindy`, the `-C utf8` option is used. This is supported in modern distributions, but a customized `lwarpmk.lua` may need to be created for use with older distributions.

**v0.29:**

- Add: `lwarpmklang` option for `lwarp-newproject` and `lwarp`. Sets the language to use while processing the glossary. (As of v0.30, this has been changed to the `IndexLanguage` option.) (As of v0.54, this has been changed to the `xindyLanguage` option.)

- Fix: \includegraphics when no optional arguments.

**v0.28:**

- \HTMLAuthor {<*name*>} assigns HTML meta author if non-empty. Defaults to \theauthor.
- Boolean HTMLDebugComments controls whether HTML comments are added for closing <div>s, opening and closing sections, etc.
- Boolean FormatEPUB changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.
- Boolean FormatWordProcessor changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Name changed to FormatWP as of v0.42.
- Boolean HTMLMarkFloats adds text marks around floats only if the boolean FormatWordProcessor is true. These make it easier to identify float boundaries, which are to be manually converted to word-processor frames. Name changed to WPMarkFloats as of v0.42.
- Updated for the new MATHJAX CDN repository.
- Adds tabulary.
- Supports the options syntax for graphics.
- Improved index references, now pointing exactly to their target.
- Adds glossaries. *lwarpmk* is modified to add printglossary and htmlglossary actions.

## 2 Introduction

The `lwarp` project aims to allow a rich L<sup>A</sup>T<sub>E</sub>X document to be converted to a reasonable HTML5 interpretation, with only minor intervention on the user's part. No attempt has been made to force L<sup>A</sup>T<sub>E</sub>X to provide for every HTML-related possibility, and HTML cannot exactly render every possible L<sup>A</sup>T<sub>E</sub>X concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the HTML conversion.

Several “modern” features of HTML5, css3, and svg are employed to allow a fairly feature-rich document without relying on the use of JAVASCRIPT. Limited testing on older browsers shows that these new features degrade gracefully.

---

`lwarp` is a native L<sup>A</sup>T<sub>E</sub>X package, and operates by either patching or emulating various functions. Source-level compatibility is a major goal, but occasional user intervention is required in certain cases.

As a package running directly in L<sup>A</sup>T<sub>E</sub>X, `lwarp` has some advantages over other methods of HTML conversion. T<sub>E</sub>X itself is still used, allowing a wider range of T<sub>E</sub>X trickery to be understood. Lua expressions are still available with LuaT<sub>E</sub>X. Entire categories of L<sup>A</sup>T<sub>E</sub>X packages work as-is when used with `lwarp`: definitions, file handling, utilities, internal data structures and calculations, specialized math-mode typesetting for various fields of science and engineering, and anything generating plain-text output. Blocks of PDF output may be automatically converted to svg images while using the same font and spacing as the original print document, directly supporting Tikz and picture. Numerous packages are easily adapted for HTML versions, either by loading and patching the originals, or by creating nullified or emulated replacements, and all without resorting to external programming. As a result, several hundred packages have already been adapted (table 2), and an uncounted number more work as-is.

Packages have been selected according to several criteria: perceived importance, popularity lists, recent CTAN updates, CTAN topics, mention in other packages, support by other HTML conversion methods, and from sample documents taken from public archives. These include some “obsolete” packages as well.<sup>1</sup>

---

Assistance is also provided for modifying the HTML output to suit the creation of EPUB documents, and for modifying the HTML output to ease import into a word processor.

---

`pdflatex`, `xelatex`, or `lualatex` may be used, allowing `lwarp` to process the usual image formats. While generating HTML output, svg files are used in place of PDF. Other formats such as PNG and JPG are used as-is.

---

<sup>1</sup>An amazing number of decades-old packages are still in use today.

SVG images may be used for math, and are also used for picture, Tikz, and similar environments. The SVG format has better browser and e-book support than MathML (as of this writing), while still allowing for high-quality display and printing of images (again, subject to potentially bug-ridden<sup>2</sup> browser support).

Furthermore, SVG images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by `<alt>` tags holding the LATEX source for the expression, allowing it to be copy/pasted into other documents.<sup>3</sup> Custom LATEX macros may be used as-is in math expressions, since the math is evaluated entirely inside LATEX. An MD5 hash is used to combine multiple instances of the same inline math expression into a single image file, which then needs to be converted to SVG only a single time.

The MATHJAX JavaScript display engine may be selected for math display instead of using SVG images. Subject to browser support and Internet access, MATHJAX allows an HTML page to display math without relying on a large number of external image files.<sup>4</sup> lwarf maintains LATEX control for cross-referencing and equation numbering, and attempts to force MATHJAX to tag equations accordingly.

---

A *texlua* program called *lwarpmk* is used to process either the print or HTML version of the document. A few external utility programs are used to finish the conversion from a LATEX-generated PDF file which happens to have HTML5 tags, to a number of HTML5 plain-text files and accompanying images.

lwarf automatically generates the extra files necessary for the HTML conversion, such as css and .xdy files, and configuration files for the utility *lwarpmk*. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects HTML output and then inputs the user's own source. This process allows both the printed and HTML versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during HTML conversion, lwarf first looks to see if it has its own modified version to use instead of the standard LATEX version. These lwarf-packagename.sty files contain code used to emulate or replace functions for HTML output.

---

<sup>2</sup>FIREFOX has had an on-again/off-again bug for quite some time regarding printing svgs at high resolution.

<sup>3</sup>There seems to be some debate as to whether MathML is actually an improvement over LATEX for sharing math. The author has no particular opinion on the matter, except to say that in this case LATEX is much easier to implement!

<sup>4</sup>One SVG image file per math expression, except that duplicate inline math expressions are combined into a single file according to the MD5 hash function of its contents. A common scientific paper can easily include several thousand files, and in one case the MD5 hash cut the number of files in half and the rendering time by 30%.

## 2.1 Typesetting conventions

Font weight, family, and style are used to indicate various objects:

Table 1: Typesetting conventions

<b>package</b>	L <small>A</small> T <small>E</small> X package.
<i>program</i>	Program's executable name.
<i>option</i>	Program or package option.
<b>filename</b>	File name in the operating system.
<b>BRAND NAME</b>	Proper name for a program, operating system, etc.
<b>commands</b>	Commands to be entered by the user.
<i>code</i>	Program code.
\macro	L <small>A</small> T <small>E</small> X macro.
<b>environment</b>	L <small>A</small> T <small>E</small> X environment.
<b>counter</b>	L <small>A</small> T <small>E</small> X counter.
<b>boolean</b>	L <small>A</small> T <small>E</small> X boolean.
<b>&lt;element&gt;</b>	HTML element.
<b>attribute</b>	HTML attribute.
<b>User Interface</b>	A user-interface item.
<b>ACRO</b>	Acronym.

## 2.2 Supported packages and features

Table 2 lists some of the various L<sup>A</sup>T<sub>E</sub>X features and packages which may be used.

Package names are colored according to their support level:

**name:** Supported as-is.

**name:** Modified to work with HTML output, and also as print output in `svg` math or `lateximage` environments.

**name:** Emulated for HTML output.

**name:** Ignored for HTML output, but provides source-level compatibility.

**MJ:** Emulated for MATHJAX, subject to limitations.

Table 2: L<sup>A</sup>T<sub>E</sub>X l warp package — Supported features

Category	Status and supported features.
Engines:	DVI L <sup>A</sup> T <sub>E</sub> X, pdfL <sup>A</sup> T <sub>E</sub> X, X <sub>E</sub> L <sup>A</sup> T <sub>E</sub> X, LuaL <sup>A</sup> T <sub>E</sub> X, upL <sup>A</sup> T <sub>E</sub> X
Compiling:	<i>latexmk</i> , <i>perltex</i> , <i>pythontex</i> , <i>make</i> , etc.
Classes:	article, book, report, scrartcl, scrbook, scrreprt, memoir, CJK-related as listed below.
Koma-script:	<i>scrextend</i> , <i>scrhack</i> , <i>scrlayer</i> . Others as listed below.
Memoir:	memhfixc
Languages:	<i>babel</i> , <i>polyglossia</i> , <i>cjkpunct</i> , <i>xeCJK</i> .
Chinese:	CT <sub>E</sub> X, <i>ctex</i> , <i>upzhkinsoku</i> , <i>xpinyin</i> , <i>zhlineskip</i> , <i>zhspacing</i> .
Japanese:	upL <sup>A</sup> T <sub>E</sub> X, LuaT <sub>E</sub> X-ja, gentombow, <i>lltjext</i> , <i>plarray</i> , <i>plarydshln</i> , <i>plautopatch</i> , <i>plex</i> , <i>plexarray</i> , <i>plexarydshln</i> , <i>plextcolortbl</i> , <i>plextdearray</i> , <i>pxatbegshi</i> , <i>pxeveryshi</i> , <i>pxftnright</i> , <i>pxgentombow</i> , <i>pxjahyper</i> , <i>pxpdfpages</i> , <i>pxpgfrcs</i> , <i>pxpgfmark</i> , <i>tascmac</i> , <i>zxjatype</i> . <i>bxsarticle</i> and related, <i>ltjsarticle</i> and related, <i>luatexja</i> , <i>luatexja-fontspec</i> , <i>ujarticle</i> and related, <i>utarticle</i> and related.
Korean:	<i>kotex</i> , <i>luatexko</i> , <i>xetexko</i> .

## l warp Supported Functions — continued

Category	Status
Page layout:	2in1, 2up, a4, a4wide, a5comb, addlines, anysize, <b>atbegshi</b> , blowup, booklet, bophook, bounddvi, bxpapersize, canoniclayout, <b>changelayout</b> , <b>changepage</b> , chngpage, clrdblpg, continue, draftcopy, draftfigure, draftwatermark, ebook, everyshi, <b>fancyhdr</b> , fancytabs, flippdf, fullminipage, fullpage, fwlw, geometry, gmeometric, grid, <b>grid-system</b> , gridset, layaureo, layout, layouts, leading, ltxgrid, nccfancyhdr, notespages, nowidow, pagegrid, pagesel, <b>parallel</b> , <b>parcolumns</b> , pdfcolparallel, pdfcolparcolumns, pdfcrypt, pdfprivacy, preview, <b>ragged2e</b> , rmpage, <b>scrlayer-scrpage</b> , <b>scrpage2</b> , <b>setspace</b> , textarea, threadcol, thumb, thumbs, titleps, toccenter, turnthepage, twoup, typearea, underlin, vmargin, watermark, widows-and-orphans, zwpagelayout.
Sectioning:	Adds <b>FileDepth</b> for splitting the <b>HTML</b> output. Files may be numbered sequentially or named according to section name. Common short words and punctuation are removed from the file-names. <b>anonchap</b> , <b>bsheaders</b> , <b>fncychap</b> , <b>hypbmsec</b> , <b>indentfirst</b> , <b>quotchap</b> , <b>section</b> , <b>sectionbreak</b> , <b>secdot</b> , <b>sectsty</b> , <b>titlesec</b> .
Table of contents, figures, tables:	Supported, with hyperlinks. <b>minitoc</b> , <b>multitoc</b> , <b>shorttoc</b> , <b>titletoc</b> , <b>tocbasic</b> , <b>tocbibind</b> , <b>tocdata</b> , <b>tocloft</b> , <b>tocstyle</b> .
Title page:	\maketitle, <b>titlepage</b> , <b>authblk</b> , <b>titling</b> .
Front & back matter:	<b>abstract</b> , <b>appendix</b> .
Indexing:	<b>makeindex</b> and <b>xindy</b> are supported, with hyperlinks. <b>hvindex</b> , <b>idxlayout</b> , <b>imakeidx</b> , <b>index</b> , <b>makeidx</b> , <b>repeatindex</b> , <b>splitidx</b> .
Glossary:	<b>gloss</b> , <b>glossaries</b> and <b>xindy</b> , <b>nomencl</b> .
Bibliography:	<b>babelbib</b> , <b>backref</b> , <b>biblatex</b> , <b>bibunits</b> , <b>chapterbib</b> , <b>cite</b> , <b>hypernat</b> , <b>natbib</b> , <b>notes2bib</b> , <b>showtags</b> .
Cross-references:	bookmark, <b>breakurl</b> , <b>cleveref</b> , <b>fancyref</b> , <b>hypdestopt</b> , <b>hyperref</b> , <b>perpage</b> , <b>prettyref</b> , <b>titleref</b> , <b>url</b> , <b>varioref</b> , <b>xcite</b> , <b>xr</b> , <b>xr-hyper</b> , <b>xurl</b> .
Margin notes:	marginal, marginfit, marginfix, <b>scrlayer-notecolumn</b> , <b>versonotes</b> .

## l warp Supported Functions — continued

Category	Status
Footnotes:	Adds FootnoteDepth to print footnotes at section breaks. <code>bigfoot</code> , <code>dblfnote</code> , <code>endheads</code> , <code>endnotes</code> , <code>fixfoot</code> , <code>fnbreak</code> , <code>fnpara</code> , <code>fnpos</code> , <code>footmisc</code> , <code>footnote</code> , <code>footnotebackref</code> , <code>footnoterange</code> , <code>footnpag</code> , <code>manyfoot</code> , <code>marginnote</code> , <code>nccfoots</code> , <code>pagenote</code> , <code>parnotes</code> , <code>pdfcolfoot</code> , <code>pfnote</code> , <code>sepfootnotes</code> , <code>sidenotes</code> , <code>tablefootnote</code> .
Math:	Converted to SVG images with HTML <code>&lt;alt&gt;</code> tags containing the L <sup>A</sup> T <sub>E</sub> X source for the math expression. MATHJAX supported as an alternative. <code>amsmath</code> <sup>MJ</sup> : $\mathcal{A}\mathcal{M}\mathcal{S}$ environments are supported. User-defined macros are available during conversion, due to native L <sup>A</sup> T <sub>E</sub> X processing.
Theorems:	Native L <sup>A</sup> T <sub>E</sub> X theorems, <code>amsthm</code> , <code>ntheorem</code> , <code>theorem</code> .
Additional math:	Math fonts via SVG images, <code>amscd</code> , <code>autobreak</code> <sup>MJ</sup> , <code>autonum</code> , <code>backnaur</code> , <code>bm</code> <sup>MJ</sup> , <code>braket</code> <sup>MJ</sup> , <code>breqn</code> , <code>cases</code> , <code>centernot</code> <sup>MJ</sup> , <code>delarray</code> , <code>extarrows</code> <sup>MJ</sup> , <code>fouridx</code> <sup>MJ</sup> , <code>guass</code> , <code>jkmath</code> , <code>leftidx</code> <sup>MJ</sup> , <code>mathcomp</code> <sup>MJ</sup> , <code>mathdots</code> <sup>MJ</sup> , <code>mathfixs</code> <sup>MJ</sup> , <code>mathspec</code> , <code>mathtools</code> <sup>MJ</sup> , <code>mismath</code> <sup>MJ</sup> , <code>nccmath</code> <sup>MJ</sup> , <code>nicematrix</code> , <code>noitcrl</code> <sup>MJ</sup> , <code>pb-diagram</code> , <code>resizegather</code> , <code>rmathbr</code> <sup>MJ</sup> , <code>subsupscripts</code> <sup>MJ</sup> , <code>unicode-math</code> <sup>MJ</sup> , <code>witharrows</code> <sup>MJ</sup> , <code>xfakebold</code> <sup>MJ</sup> , <code>xy</code> . Many others work as-is.
Display math with <code>\displaymathother</code> :	Complicated math objects in display math, such as <code>tikz-cd</code> , etc.
Units and fractions:	<code>nicefrac</code> <sup>MJ</sup> , <code>Slunits</code> , <code>siunitx</code> <sup>MJ</sup> , <code>units</code> <sup>MJ</sup> , <code>unitsdef</code> , <code>xfrac</code> <sup>MJ</sup> .
Floats:	Appear where declared. <code>capt-of</code> , <code>caption</code> , <code>cutwin</code> , <code>dblfloatfix</code> , <code>endfloat</code> , <code>fewerfloatpages</code> , <code>fix2col</code> , <code>flafter</code> , <code>float</code> , <code>floatflt</code> , <code>floatrow</code> , <code>fltrace</code> , <code>ftcap</code> , <code>hypcap</code> , <code>keyfloat</code> , <code>morefloats</code> , <code>multicap</code> , <code>newfloat</code> , <code>nonfloat</code> , <code>placeins</code> , <code>rotfloat</code> , <code>stfloats</code> , <code>subcaption</code> , <code>subfig</code> , <code>subfigure</code> , <code>subfloat</code> , <code>topcapt</code> , <code>trivfloat</code> , <code>wrapfig</code> .
Tabular:	tabular environment, <code>array</code> <sup>MJ</sup> , <code>arydshln</code> <sup>MJ</sup> , <code>bigdelim</code> <sup>MJ</sup> , <code>bigstrut</code> <sup>MJ</sup> , <code>booktabs</code> <sup>MJ</sup> , <code>colortbl</code> , <code>ctable</code> , <code>diagbox</code> , <code>hhline</code> <sup>MJ</sup> , <code>longtable</code> , <code>ltablex</code> , <code>ltxtable</code> , <code>multirow</code> <sup>MJ</sup> , <code>supertabular</code> , <code>tabularx</code> , <code>tabulary</code> , <code>threeparttable</code> , <code>threeparttablex</code> , <code>widetable</code> , <code>xltabular</code> , <code>xtab</code> .

## l warp Supported Functions — continued

Category	Status
Graphics:	<code>graphics</code> and <code>graphicx</code> . <code>\includegraphics</code> supports <code>width</code> , <code>height</code> , <code>origin</code> , <code>angle</code> , and <code>scale</code> tags, and adds <code>class</code> . References to PDF files are changed to SVG, other image types are accepted as well. <code>\rotatebox</code> and <code>\scalebox</code> are supported as well as HTML can handle. <code>rotating</code> is emulated but all objects are unrotated. <code>picture</code> , <code>tikz</code> , and <code>xy</code> are converted to an SVG image. <code>asymptote</code> , <code>curves</code> , <code>datatool</code> , <code>eepic</code> , <code>epsfig</code> , <code>epstopdf</code> , <code>fysize</code> , <code>fitbox</code> , <code>grffile</code> , <code>media9</code> , <code>movie15</code> , <code>multimedia</code> , <code>overpic</code> , <code>psfrag</code> , <code>psfrags</code> , <code>pst-eps</code> , <code>pstool</code> , <code>pstricks</code> , <code>rviewport</code> , <code>svg</code> , <code>svg-extract</code> , <code>tikz-3dplot</code> .
<code>xcolor</code> :	Full package color names, any color models, and mixing. <code>\textcolor</code> , <code>\colorbox</code> , <code>\fcolorbox</code> . Enhanced for HTML compatibility.
Lists:	Standard L <sup>A</sup> T <sub>E</sub> X environments, <code>enumerate</code> , <code>enumitem</code> , <code>eqlist</code> , <code>hang</code> , <code>listliketab</code> , <code>paralist</code> .
Environments:	Standard L <sup>A</sup> T <sub>E</sub> X environments.
<code>minipage</code> , <code>\parbox</code> :	Some HTML5-imposed limitations. Nested minipages are supported. <code>eqparbox</code> , <code>minibox</code> , <code>pbox</code> , <code>shapepar</code> .
Quotations:	<code>copyrightbox</code> , <code>csquotes</code> , <code>epigraph</code> , <code>quoting</code> , <code>verse</code> .
Verbatim:	<code>fancyvrb</code> , <code>moreverb</code> , <code>shortvrb</code> , <code>verbatim</code> .
Frames:	<code>boxedminipage2e</code> , <code>fancybox</code> , <code>framed</code> , <code>mdframed</code> , <code>niceframe</code> , <code>shadow</code> , <code>vertbars</code> .
Multi-columns:	<code>adjmulticol</code> , <code>multicol</code> , <code>multicolrule</code> , <code>vwcol</code> .
Margins:	<code>fullwidth</code> , <code>hanging</code> , <code>midpage</code> .
Line numbering:	<code>fnlineno</code> , <code>lineno</code> .
Direct formatting:	<code>\emph</code> , <code>\textsuperscript</code> , <code>\textbf</code> , etc are supported. <code>\bfseries</code> , etc. are only supported in some cases. <code>cancel</code> , <code>ellipsis</code> , <code>embrac</code> , <code>enparen</code> , <code>hyphenat</code> , <code>lettrine</code> , <code>lips</code> , <code>lua-check-hyphen</code> , <code>luacolor</code> , <code>magaz</code> , <code>normalcolor</code> , <code>pdfcol</code> , <code>pdfcolmk</code> , <code>pdfrender</code> , <code>realscripts</code> , <code>relsize</code> <sup>MJ</sup> , <code>scalefont</code> , <code>soul</code> , <code>soulpos</code> , <code>soulutf8</code> , <code>stackengine</code> , <code>textfit</code> , <code>thinsp</code> , <code>trimclip</code> , <code>truncate</code> , <code>ulem</code> , <code>umoline</code> , <code>underscore</code> , <code>uspace</code> , <code>xellipsis</code> .
Acronyms:	<code>acro</code> , <code>acronym</code> .

## l warp Supported Functions — continued

Category	Status
Ordinals:	<code>engord</code> , <code>fmtcount</code> , <code>nth</code> .
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for thin-unbreakable, unbreakable, \enskip, \quad, \qquad, \hspace.
Rules:	\rule with width, height, raise, text color.
HTML reserved characters:	\&, \textless, and \textgreater are converted to HTML entities.
Fonts:	Used as-is. Appear in SVG math expressions or embedded image environments. <code>fontaxes</code> , <code>nfssext-cfr</code> , <code>slantsc</code> , <code>tabfigures</code> . Tested to work as-is: Special font macros in <code>cfr-lm</code> and others which use <code>nfssext-cfr</code> .
Symbols:	Native LATEX diacriticals, <code>academicons</code> , <code>bding</code> , <code>chemgreek</code> , <code>dingbat</code> , <code>euro</code> , <code>eurosym</code> , <code>fontawesome</code> , <code>fontawesome5</code> , <code>gensymb</code> <sup>MJ</sup> , <code>marvosym</code> , <code>mathcomp</code> <sup>MJ</sup> , <code>metabolo</code> , <code>metalogox</code> , <code>pifont</code> , <code>textalpha</code> , <code>textcomp</code> , <code>textgreek</code> , <code>typicons</code> , <code>xunicode</code> .
Files:	<code>attachfile</code> , <code>attachfile2</code> , <code>hyperxmp</code> , <code>inputrc</code> , <code>intopdf</code> , <code>pdffiles</code> , <code>pdfx</code> , <code>xmpincl</code> .
Science and engineering:	<code>algorithm2e</code> , <code>algorithmicx</code> , <code>ar</code> <sup>MJ</sup> , <code>askmaps</code> , <code>axodraw2</code> , <code>bitpattern</code> , <code>blochsphere</code> , <code>bodegraph</code> , <code>bohr</code> , <code>bytefield</code> , <code>chemfig</code> , <code>chemformula</code> , <code>chemgreek</code> , <code>chemmacros</code> , <code>chemnum</code> , <code>circuitikz</code> , <code>elements</code> , <code>englcc</code> , <code>fast-diagram</code> , <code>ghsystem</code> , <code>hepnicenames</code> , <code>heppennames</code> , <code>karnaughmap</code> , <code>karnaugh-map</code> , <code>listings</code> , <code>linop</code> , <code>mhchem</code> <sup>MJ</sup> , <code>pgfgantt</code> , <code>phfqit</code> , <code>physics</code> <sup>MJ</sup> , <code>qcircuit</code> , <code>register</code> , <code>simpler-wick</code> , <code>slashed</code> <sup>MJ</sup> , <code>steinmetz</code> <sup>MJ</sup> , <code>structmech</code> , <code>struktex</code> , <code>tikz-karnaugh</code> , <code>tikzcodeblocks</code>
Arts and humanities:	<code>foreign</code> , <code>forest</code> , <code>lyluatex</code> , <code>musicography</code> , <code>nameauth</code> , <code>octave</code> , <code>phonrule</code> , <code>piano</code> , <code>schemata</code> , <code>semantic-markup</code> , <code>tikz-dependency</code> , <code>vowel</code> , <code>xpiano</code>
Admonitions:	<code>awesomelbox</code> , <code>notes</code> .

## l warp Supported Functions — continued

Category	Status
Editorial:	changebar, changelog, changes, easy-todo, easyReview, ed, errata, fixme, fixmetodonotes, pdfcomment <sup>MJ</sup> , pdfmarginpar, todo, todonotes, tram, xexchangebar.
Accessibility:	accessibility <sup>MJ</sup> , pdfcomment <sup>MJ</sup> .
Package handling:	catoptions.
Debug:	chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.
Working as-is:	Various utility, calculation, file, and text-only packages, such as calc, fileerr, somedefs, trace, xspace. Also, most math-only packages, including specialized typesetting for various fields of science and engineering.

### 3 Alternatives

Summarized below are several other ways to convert a L<sup>A</sup>T<sub>E</sub>X or other document to HTML. Where an existing L<sup>A</sup>T<sub>E</sub>X document is to be converted to HTML, lwarf may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

#### 3.1 internet class

**Cls** `internet` The closest to lwarf in design principle is the `internet` class by Andrew Stacey—an interesting project which directly produces several versions of markdown, and also HTML and EPUB. <https://github.com/loopspace/latex-to-internet>

#### 3.2 TEX4HT

**Prog** `TeX4ht` <http://tug.org/tex4ht/>  
**Prog** `htlatex`

This system uses native L<sup>A</sup>T<sub>E</sub>X processing to produce a DVI file containing special commands, and then uses additional post-processing for the HTML conversion by way of numerous configuration files. In some cases lwarf provides a better HTML conversion, and it supports a different set of packages. TeX4ht produces several other forms of output beyond HTML, including ODT and a direct path to EPUB, and is still being developed.

#### 3.3 Translators

These systems use external programs to translate a subset of L<sup>A</sup>T<sub>E</sub>X syntax into HTML. Search for each on CTAN (<http://ctan.org>).

<b>Prog</b>	<b>Hevea</b>	<b>H<sup>E</sup>v<sup>F</sup>a:</b> <a href="http://hevea.inria.fr/">http://hevea.inria.fr/</a> (not on CTAN)
<b>Prog</b>	<b>TtH</b>	<b>T<sub>T</sub>H:</b> <a href="http://hutchinson.belmont.ma.us/tth/">http://hutchinson.belmont.ma.us/tth/</a>
<b>Prog</b>	<b>GELLMU</b>	<b>GELLMU:</b> <a href="http://www.albany.edu/~hammond/gellmu/">http://www.albany.edu/~hammond/gellmu/</a>
<b>Prog</b>	<b>LaTeXML</b>	<b>L<sup>A</sup>TeXML:</b> <a href="http://dlmf.nist.gov/LaTeXML/">http://dlmf.nist.gov/LaTeXML/</a>
<b>Prog</b>	<b>Plastex</b>	<b>PlasTeX:</b> <a href="https://github.com/tiarno/plastex">https://github.com/tiarno/plastex</a>
<b>Prog</b>	<b>LaTeX2HTML</b>	<b>L<sup>A</sup>TeX2HTML:</b> <a href="http://www.latex2html.org/">http://www.latex2html.org/</a> and <a href="http://ctan.org/pkg/latex2html">http://ctan.org/pkg/latex2html</a> .
<b>Prog</b>	<b>TeX2page</b>	<b>TeX2page:</b> <a href="http://ds26gte.github.io/tex2page/index.html">http://ds26gte.github.io/tex2page/index.html</a>

Finally, GladTeX may used to directly insert L<sup>A</sup>T<sub>E</sub>X math into HTML:

**Prog** `GladTeX` **GladTeX:** <http://humenda.github.io/GladTeX/>

### 3.4 ASCII DOC and ASCIIDOCTOR

AsciiDoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes LATEX and HTML.

Prog AsciiDoc **Asciidoc:** <http://asciidoc.org/> (More active.)

Prog AsciiDoctor **AsciiDoc:** <http://asciidoc.org/> (The original project.)

#### 3.4.1 ASCIIDOCTOR-LATEX

The Asciidoc-LaTeX project is developing additional LATEX-related features.

##### Asciidoc-LaTeX:

<http://www.noteshare.io/book/asciidoc-latex-manual>

<https://github.com/asciidoc/asciidoc-latex>

### 3.5 PANDOC

Prog Pandoc A markup system which also reads and writes LATEX and HTML.

**Pandoc:** <http://pandoc.org/>

(Watch for improvements in cross-references to figures and tables.)

### 3.6 Word processors

Prog Word It should be noted that the popular word processors have advanced through the years in their abilities to represent math with a LATEX-ish input syntax, unicode math fonts, and high-quality output, and also generate HTML with varying success. See recent developments in MICROSOFT® *Word*® and LIBREOFFICE™ *Writer*.

### 3.7 Commercial systems

Prog Adobe Likewise, several professional systems exist whose abilities have been advancing in the areas of typesetting, cross-referencing, and HTML generation. See ADOBE® *FrameMaker*®, ADOBE *InDesign*®, and MADCAP *Flare*™.

Prog InDesign

Prog Flare

Prog Madcap

### 3.8 Comparisons

AsciiDoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to

require many combinations of special characters, resulting in a complicated mess of syntax. By contrast, L<sup>A</sup>T<sub>E</sub>X spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that L<sup>A</sup>T<sub>E</sub>X is comparably easy to learn, while L<sup>A</sup>T<sub>E</sub>X provides many more advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of L<sup>A</sup>T<sub>E</sub>X vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a L<sup>A</sup>T<sub>E</sub>X back end, yielding high-quality results especially when the L<sup>A</sup>T<sub>E</sub>X template is adjusted, but they lose the ability to use L<sup>A</sup>T<sub>E</sub>X macros and other L<sup>A</sup>T<sub>E</sub>X source-document features.

The effort required to customize the output of each markup system varies. For print output, L<sup>A</sup>T<sub>E</sub>X configuration files are usually used. For HTML output, a css file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of lwarp, css is used, and much HTML output is adjusted through the usual L<sup>A</sup>T<sub>E</sub>X optional macro parameters, but further customization may require patching L<sup>A</sup>T<sub>E</sub>X code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

## 4 Installation

Table 3 shows the tools which are used for the L<sup>A</sup>T<sub>E</sub>X to HTML conversion. In most cases, these will be available via the standard package-installation tools.

Detailed installation instructions follow.

Table 3: Required software programs

**Provided by your L<sup>A</sup>T<sub>E</sub>X distribution:**

From T<sub>E</sub>XLive: <http://tug.org/texlive/>.

**L<sup>A</sup>T<sub>E</sub>X:** *pdflatex*, *xelatex*, or *lualatex*.

**The l warp package:** This package.

**The *lwarpmk* utility:** Provided along with this package. This should be an operating-system executable in the same way that *pdflatex* or *latexmk* is. It is possible to have the l warp package generate a local copy of *lwarpmk* called *lwarpmk.lua*. See table 4.

***luatex*:** Used by the *lwarpmk* program to simplify and automate document generation.

***xindy*:** The *xindy* program is used by l warp to create indexes. On a MiK<sup>T</sup>E<sub>X</sub> system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

***latexmk*:** Optionally used by *lwarpmk* to compile L<sup>A</sup>T<sub>E</sub>X code. On a MiK<sup>T</sup>E<sub>X</sub> system, *Perl* may need to be installed first.

***pdfcrop*:** Used to pull images out of the L<sup>A</sup>T<sub>E</sub>X PDF.

**POPPLEER PDF utilities:**

***pdftotext*:** Used to convert PDF to text.

***pdfseparate*:** Used to pull images out of the L<sup>A</sup>T<sub>E</sub>X PDF.

***pdftocairo*:** Used to convert images to SVG.

These might be provided by your operating-system package manager, and MiK<sup>T</sup>E<sub>X</sub> provides *miktex-poppler-bin-\** packages.

From POPPLER: [poppler.freedesktop.org](http://poppler.freedesktop.org).

For MACOS®, see <https://brew.sh/>, install *Homebrew*, then

Enter ⇒ **brew install poppler**

For WINDOWS, see Mik<sup>T</sup>E<sub>X</sub> *miktex-poppler-bin-\**, or:

<https://sourceforge.net/projects/poppler-win32/> and:

<http://blog.alivate.com.au/poppler-windows/>

**Perl:**

This may be provided by your operating-system package manager, and may be required for some of the POPPLER PDF utilities.

[strawberryperl.com](http://strawberryperl.com) (recommended), [perl.org](http://perl.org)

**Automatically downloaded from the internet as required:**

**MATHJAX:** Optionally used to display math. From: [mathjax.org](http://mathjax.org)

## 4.1 Installing the l warp package

There are several ways to install l warp. These are listed here with the preferred methods listed first:

**Pre-installed:** Try entering into a command line:

Enter ⇒ `kpsewhich l warp.sty`

If a path to l warp.sty is shown, then l warp is already installed and you may skip to the next section.

**TEX Live:** If using a TEX Live distribution, try installing via `tlmgr`:

Enter ⇒ `tlmgr install l warp`

**MiKTEX:**

1. For newer versions of MiKTEX, install or update l warp using the *MiKTeX Console* program.
2. For older versions of MiKTEX, to install l warp the first time, use the *MiKTeX Package Manager (Admin)*. To update l warp, use *MiKTeX Update (Admin)*.
3. Either way, also update the package `miktex-misc`, which will install and update the `lwarpmk` executable.

**Operating-system package:** The operating-system package manager may already have l warp, perhaps as part of a set of TEX-related packages.

**CTAN TDS archive:** l warp may be downloaded from the Comprehensive TEX Archive:

1. See <http://ctan.org/pkg/l warp> for the l warp package.
2. Download the TDS archive: `l warp.tds.zip`
3. Find the TEX local directory:

**TEX Live:**

Enter ⇒ `kpsewhich -var-value TEXMFLOCAL`

**MiKTEX:**

In the **Settings** window, **Roots** tab, look for a local TDS root.

This should be something like:

`/usr/local/texlive/texmf-local/`

4. Unpack the archive in the TDS local directory.
5. Renew the cache:

Enter ⇒ `mktexlsr`

— or —

Enter ⇒ `texhash`

Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.

**CTAN .dtx and .ins files:** Another form of TEX package is .dtx and .ins source files. These files are used to create the documentation and .sty files.

1. See <http://ctan.org/pkg/lwarp> for the l warp package.
2. Download the zip archive l warp.zip into your own l warp directory.
3. Unpack l warp.zip.
4. Locate the contents l warp.dtx and l warp.ins
5. Create the .sty files:  
Enter ⇒ **pdflatex l warp.ins**
6. Create the documentation:

---

```
pdflatex l warp.dtx (several times)
makeindex -s gglo.ist -o l warp.gls l warp.glo
makeindex -s gind.ist l warp.idx
pdflatex l warp.dtx (several times)
```

---

7. Copy the .sty files somewhere such as the T E X Live local tree found in the previous CTAN TDS section, under the subdirectory:  
    <texlocal>/tex/latex/local/l warp
8. Copy l warp\_baseline\_marker.png and l warp\_baseline\_marker.eps to the same place as the .sty files.
9. Copy the documentation l warp.pdf to a source directory in the local tree, such as:  
    <texlocal>/doc/local/l warp
10. Renew the cache:  
    Enter ⇒ **mktexlsr**  
    — or —  
    Enter ⇒ **texhash**  
Or, for WINDOWS MiK T E X, start the program called *MiK T E X Settings (Admin)* and click on the button called **Refresh FNDB**.
11. See section 4.2.1 to generate your local copy of l warpmk.
12. Once the local version of l warpmk.lua is installed, it may be made available system-wide as per section 4.2.

**Project-local CTAN .dtx and .ins files:** The .dtx and .ins files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant \*.sty and l warpmk.lua files may be used as-is, so long as they are in the same directory as the document source. The files l warp\_baseline\_marker.png and l warp\_baseline\_marker.eps must also be copied as well. This approach is especially useful if you would like to temporarily test l warp before deciding whether to permanently install it.

Just testing!

## 4.2 Installing the l warpmk utility

(Note: If l warpmk is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 4.2.1.)

After the l warp package is installed, you may need to setup the l warpmk utility:

1. At a command line, try executing **lwarpmk**. If the *lwarpmk* help message appears, then *lwarpmk* is already set up. If not, it is easiest to generate and use a local copy. See section 4.2.1.
2. For MiK<sub>T</sub>E<sub>X</sub>, try updating the *miktex-misc* package. This may install the *lwarpmk* executable for you.

Otherwise, continue with the following:

3. Locate the file *lwarpmk.lua*, which should be in the *scripts* directory of the TDS tree. On a *TEX Live* or MiK<sub>T</sub>E<sub>X</sub> system you may use

Enter ⇒ **kpsewhich lwarpmk.lua**

(If the file is not found, you may also generate a local copy and use it instead. See section 4.2.1.)

4. Create *lwarpmk*:

**Unix:** Create a symbolic link and make it executable:

- (a) Locate the *TEX Live* binaries:

Enter ⇒ **kpsewhich -var-value TEXMFROOT**

This will be something like:

*/usr/local/texlive/<year>*

The binaries are then located in the *bin/<arch>* directory under the root:

*/usr/local/texlive/<year>/bin/<architecture>/*

In this directory you will find programs such as *pdflatex* and *makeindex*.

- (b) In the binaries directory, create a new symbolic link from the binaries directory to *lwarpmk.lua*:

Enter ⇒ **ln -s <pathtolwarpmk.lua> lwarpmk**

- (c) Make the link executable:

Enter ⇒ **chmod 0755 lwarpmk**

**WINDOWS *TEX Live*:** Create a new *lwarpmk.exe* file:

- (a) Locate the *TEX Live* binaries as shown above for UNIX.

- (b) In the binaries directory, make a *copy* of *runscript.exe* and call it *lwarpmk.exe*. This will call the *copy* of *lwarpmk.lua* which is in the *scripts* directory of the distribution.

**WINDOWS MiK<sub>T</sub>E<sub>X</sub>:** Create a new *lwarpmk.bat* file:

- (a) Locate the MiK<sub>T</sub>E<sub>X</sub> binaries. These will be in a directory such as:

*C:\Program Files\MiK<sub>T</sub>E<sub>X</sub> 2.9\miktex\bin\x64*

In this directory you will find programs such as *pdflatex.exe* and *makeindex.exe*.

- (b) Create a new file named *lwarpmk.bat* containing:

*texlua "C:\Program Files\MiK<sub>T</sub>E<sub>X</sub> 2.9\scripts\lwarpmk.lua" %\**

This will call the *copy* of *lwarpmk.lua* which is in the *scripts* directory of the distribution.

#### 4.2.1 Using a local copy of *lwarpmk*

It is also possible to use a local version of *lwarpmk*:

1. When compiling the tutorial in section 5, use the `lwarpmk` option for the `l warp` package:

```
\usepackage[lwarpmk]{l warp}
```

2. When the tutorial is compiled with `pdflatex`, the file `lwarpmk.lua` will be generated along with the other configuration files.
3. `lwarpmk.lua` may be used for this project:

##### **Unix:**

- (a) Make `lwarpmk.lua` executable:

Enter ⇒ `chmod 0755 lwarpmk.lua`

- (b) Compile documents with

Enter ⇒ `./lwarpmk.lua html`

Enter ⇒ `./lwarpmk.lua print`

etc.

- (c) It may be useful to rename or link to a version without the `.lua` suffix.

##### **WINDOWS:**

Compile documents with either of the following, depending on which command shell is being used:

Enter ⇒ `texlua lwarpmk.lua html`

Enter ⇒ `texlua lwarpmk.lua print`

etc.

Or:

Enter ⇒ `lwarpmk html`

Enter ⇒ `lwarpmk print`

etc.

### 4.3 Installing additional utilities

#### To test for the existence of the additional utilities:

Enter the following in a command line. If each programs' version is displayed, then that utility is already installed. See table 3 on page 78.

```
Enter ⇒ luatex --version
Enter ⇒ xindy --version
Enter ⇒ latexmk --version
Enter ⇒ perl --version
Enter ⇒ pdfcrop --version
Enter ⇒ pdftotext -v
Enter ⇒ pdfseparate --version
Enter ⇒ pdftocairo -v
```

### To install *xindy*, *latexmk*, and *pdfcrop*:

The TeX utilities *xindy*, *latexmk*, and *pdfcrop* may be installed in *TexLive* with *tlmgr*, installed by *MiKTeX*, provided by your operating system's package manager, or downloaded from the *CTAN* archive:

<http://ctan.org/pkg/xindy>  
<http://ctan.org/pkg/latexmk>  
<http://ctan.org/pkg/pdfcrop>

Prog [requirement] pdftotext **To install the POPPLER utilities to a UNIX/LINUX system:**

The tools from the POPPLER project should be provided by your operating system's package manager.

### To install the POPPLER utilities to a MACOS machine:

1. Install *Homebrew* from <https://brew.sh/>:

```
/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"
```

2. Install the POPPLER utilities:

Enter ⇒ **brew install poppler**

### To install the POPPLER utilities to a WINDOWS machine:

If using MikTEX, install a *miktex-poppler-bin-\** package. Otherwise:

1. See table 3 on page 78.
2. Download and extract the POPPLER utilities *pdftotext*, *pdfseparate*, and *pdfsepate* to a directory, such as Poppler.
3. In the **Start** window, type "Path" to search for results related to Path. Or, open the control panel and search for "Path".
4. Choose **Edit the system environment variables** in the control panel.
5. Choose the **Environment Variables** button.
6. Choose the **Path** variable, then the **Edit** button.
7. Choose the **New** button to make an additional entry.
8. Enter the bin directory of the POPPLER utilities, such as:  
 C:\Users\<myname>\Desktop\Poppler\poppler-0.5\_x86\poppler-0.5\bin  
 Be sure to include \bin.
9. Click **Ok** when done.

Prog [requirement] perl **To install PERL to a WINDOWS machine:**

1. Download and install a version of PERL, such as STRAWBERRY PERL, to a directory without a space in its name, such as C:\Strawberry.
2. Edit the **Path** as seen above for the POPPLER utilities.
3. Enter the bin directory of the *perl* utility, such as:  
 C:\Strawberry\perl\bin  
 Be sure to include \bin.
4. Click **Ok** when done.

**Any utilities installed by hand must be added to the PATH.**

## 5 Tutorial

This section shows an example of how to create an `lwarp` document.

Need help?

---

See the [General Index](#) for “how-to”, and the [Troubleshooting Index](#) if something doesn’t work. A [Troubleshooting](#) section is also available. The [Index of Objects](#) contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

---

### 5.1 Starting a new project

1. Create a new project directory called `tutorial`.
- File `tutorial.tex`
2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

**Copy from the documentation PDF:**

A listing is in fig. 1, which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

**Copy from the `lwarp` documentation directory:**

Another copy may be found by entering into a command line:

Enter ⇒ `texdoc -l lwarp_tutorial.txt`

This should be in the `doc/latex/lwarp/` directory along with this PDF documentation. Copy `lwarp_tutorial.txt` directly into your `tutorial` directory, renamed as `tutorial.tex`.

⚠ **Bad formatting!**

*When using Windows, use an editor other than Notepad, since Notepad does not accept the end-of-line from a UNIX text file.*

3. Compile the project:
 

Enter ⇒ `pdflatex tutorial.tex`  
(several times)

(`xelatex` or `lualatex` may be used as well. `lwarp` also supports DVI `latex` for use with .eps images.)
4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in table 4. These files are created by the `lwarp` package.

(Two of the new files are configuration files for the helper program `lwarpmk`. Whenever a print version of the document is created, the configuration files for `lwarpmk` are updated to record the operating system, L<sup>A</sup>T<sub>E</sub>X engine (`latex`, `pdflatex`, `xelatex`, or `lualatex`), the filenames of the source code and HTML output, and whether the additional helper program `latexmk` will be used to compile the document.)

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarp package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern}           % pdflatex or dvi latex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec}          % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
%   HomeHTMLfilename=index,      % Filename of the homepage.
%   HTMLfilename={node-},        % Filename prefix of other pages.
%   IndexLanguage=english,       % Language for xindy index, glossary.
%   latexmk,                   % Use latexmk to compile.
%   OSWindows,                 % Force Windows. (Usually automatic.)
%   mathjax,                   % Use MathJax to display math.
]{lwarp}
% \boolfalse{FileSectionNames} % If false, numbers the files.

% --- LOAD PDFLATEX MATH FONTS HERE ---

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor}           % (Demonstration purposes only.)
\usepackage{hyperref,cleveref} % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarp Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2}       % Include subsections in the \TOC.
\setcounter{secnumdepth}{2}     % Number down to subsections.
\setcounter{FileDepth}{1}       % Split \HTML files at sections
\booltrue{CombineHigherDepths} % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1}    % Include subsections in the side\TOC
\HTMLTitle{Webpage Title}     % Overrides \title for the web page.
\HTMLAuthor{Some Author}      % Sets the HTML meta author tag.
\HTMLLanguage{en-US}          % Sets the HTML meta language.
\HTMLDescription{A description.}% Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSfilename{lwarp_sagebrush.css}
```

```

\begin{document}

\maketitle % Or titlepage/titlingpage environment.

% An article abstract would go here.

\tableofcontents % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math: $r = r_0 + vt - \frac{1}{2}at^2$  

followed by display math:  

\begin{equation}
a^2 + b^2 = c^2
\end{equation}

\begin{warpprint} % For print output ...
\cleardoublepage % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage % HTML index will be on its own page.
\ForceHTMLTOC % HTML index will have its own toc entry.
\printindex

\end{document}

```

Table 4: Configuration files created by print version

**tutorial.pdf:** The PDF output from L<sup>A</sup>T<sub>E</sub>X. The print version of the document.

**tutorial\_html.tex:** A small .tex file used to create a parallel HTML version of the document, which co-exists with usual the PDF version, and which will have its own auxiliary files. In this way, both PDF and HTML documents may co-exist side-by-side.

**Auxiliary files:** The usual L<sup>A</sup>T<sub>E</sub>X files .aux, .log, .out, .toc, .lof, .idx. When an HTML version of the document is created, \_html versions of the auxiliary files will also be generated.

**lwarpmk.conf:** A configuration file for *lwarpmk*, which is used to automate the compilation of PDF or HTML versions of the document.

**tutorial.lwarpmkconf:** Another configuration file used by *lwarpmk*, which is only useful if you wish to have several projects residing in the same directory.

**.css files:** lwarp.css, lwarp\_formal.css, lwarp\_sagebrush.css These files are standard for lwarp, and are not meant to be modified by the user.

**sample\_project.css:** An example of a user-customized css file, which may be used for project-specific changes to the lwarp defaults.

**lwarp.ist:** Used by lwarp while creating an index using *makeindex*. This file should not be modified by the user. A custom file may be used instead, if necessary.

**lwarp.xdy:** Used by lwarp while creating an index using *xindy*. This file should not be modified by the user. A custom file may be used instead, if necessary.

**lwarp\_one\_limage.txt:** For WINDOWS only. Used to process SVG images in the background. Copied to lwarp\_one\_limage.cmd when images are generated.

**lwarp\_mathjax.txt:** Inserted into the HTML files when MATHJAX is used to display math. This file should not be modified by the user.

**comment.cut:** A temporary file used by lwarp to conditionally process blocks of text. This file may be ignored.

When the *lwarpmk* option is given to the *lwarp* package:

**lwarpmk.lua:** A local copy of the *lwarpmk* utility.

On UNIX-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

## 5.2 Compiling the print version with *lwarpmk*

The *lwarpmk* utility program is used to compile either the printed or the HTML version of the document.

`lwarpmk print` is used to recompile a printed version of the document.

1. Re-compile the print version:

Enter ⇒ **`lwarpmk print`**

*lwarpmk* prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then *lwarpmk* informs you of that fact and then exits.

2. Make a small change in the original document, such as adding a space character.
3. Recompile again.

Enter ⇒ **`lwarpmk print`**

The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

4. Force a recompile to occur.

Enter ⇒ **`lwarpmk again`**

Enter ⇒ **`lwarpmk print`**

*lwarpmk again* updates the date code for the file, triggering a recompile the next time the document is made.<sup>5</sup>

5. Process the index.<sup>6</sup> <sup>7</sup>

Enter ⇒ **`lwarpmk printindex`**

6. Recompile again to include the index.

Enter ⇒ **`lwarpmk print`**

7. To force a single recompile when needed, even if no changes were detected:

Enter ⇒ **`lwarpmk print1`**

Note that the HTML customization commands are ignored while making the print version.

---

<sup>5</sup>Although, when using the utility *latexpmk* (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

<sup>6</sup>The command `lwarpmk printglossary` is also available to process a glossary produced with the *glossaries* package. See section 8.6.12.

<sup>7</sup>Also see section 8.6.15 for index options.

### 5.3 Compiling the HTML version with *lwarpmk*

`lwarpmk html` is used to recompile an HTML version of the document.

1. Compile the HTML version:

Enter ⇒ **lwarpmk html**

- (a) *lwarpmk* uses L<sup>A</sup>T<sub>E</sub>X to process `tutorial_html.tex` to create `tutorial_html.pdf`.
- (b) *pdftotext* is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.
- (c) *lwarpmk* manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`<sup>8</sup>, `Some-math.html`, and the document's index in `_Index.html`.<sup>9</sup>

2. View the HTML page in a web browser.

Open the file `tutorial.html` in a web browser.

**math**

Note that math is still displayed as its alt tag, which is the plain-text L<sup>A</sup>T<sub>E</sub>X source, until the images of the math expressions have been generated. Math may be displayed as SVG images or by a MATHJAX script, as seen in sections 5.4 and 5.5.

3. Force a recompile:

Enter ⇒ **lwarpmk again**

Enter ⇒ **lwarpmk html**

Enter ⇒ **lwarpmk print**

4. Process the HTML index and recompile:<sup>10</sup><sup>11</sup>

Enter ⇒ **lwarpmk htmlindex**

Enter ⇒ **lwarpmk html**

`_Index.html` is updated for the new L<sup>A</sup>T<sub>E</sub>X index.

5. Reload the web page to see the added index.

6. To force a single recompile when needed, even if no changes were detected:

Enter ⇒ **lwarpmk html1**

---

<sup>8</sup>`First-chapter.html` also contains the first section, even though the second section is its own HTML page. This behavior is controlled by the boolean `CombineHigherDepths`.

<sup>9</sup>`index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

<sup>10</sup>The command `lwarpmk htmlglossary` is also available to process a glossary produced with the `glossaries` package. See section 8.6.12.

<sup>11</sup>Also see section 8.6.15 for index options.

## 5.4 Generating the svg images

**math as svg images** By default lwarf represents math as SVG images, with the L<sup>A</sup>T<sub>E</sub>X source included in alt attributes. In this way, the math is displayed as it was drawn by L<sup>A</sup>T<sub>E</sub>X, and the L<sup>A</sup>T<sub>E</sub>X source may be copied and pasted into other documents.

**picture and Tikz** lwarf uses the same mechanism for picture and Tikz environments.

1. Create the SVG images:

Enter ⇒ **lwarpmk limages**

Enter ⇒ **lwarpmk html**

2. Move to the tutorial's HTML math page and reload the document in the browser.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the L<sup>A</sup>T<sub>E</sub>X source.

**⚠ adding/removing** When a math expression, picture, or Tikz environment is added or removed, the SVG images must be re-created by entering **lwarpmk limages** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Tikz may move to new image numbers when the document is changed.

**recompile first** Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.<sup>12</sup> If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the L<sup>A</sup>T<sub>E</sub>X recompile warnings.

**⚠ HTML instead of images** If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

**⚠ page counter** Incorrect SVG images will also occur if the document changes the page counter:

`\setcounter{page}{<value>}`

The page counter must *not* be adjusted by the user.

Expressing math as SVG images has the advantage of representing the math exactly as L<sup>A</sup>T<sub>E</sub>X would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarf uses an MD5 hash on its L<sup>A</sup>T<sub>E</sub>X source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as picture and Tikz require one image file each. For a document with a large amount of math, see section 5.5 to use MATHJAX instead.

---

<sup>12</sup>This becomes important when dealing with a document containing thousands of images.

## 5.5 Using MATHJAX for math

**math with MATHJAX** Math may also be represented using the MATHJAX JAVASCRIPT project.

1. In the tutorial's source code, uncomment the `mathjax` package option for `lwarf`:

```
mathjax, % Use MathJax to display math.
```

2. Recompile

```
Enter ⇒ lwarfmk html
```

3. Reload the math page.

### ⚠ MATHJAX requirements

MATHJAX requires web access unless a local copy of MATHJAX is available, and it also requires that JAVASCRIPT is enabled for the web page. The math is rendered by MATHJAX. Right-click on math to see several options for rendering, and for copying the LATEX source.

While using MATHJAX has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as LATEX, and it may not support some math-related packages.

## 5.6 Changing the css style

For a formal css style, add to the preamble:

```
\usepackage{lwarp}
...
\CSSFilename{lwarp_formal.css}
...
\begin{document}
```

For a modern css style, `lwarp_sagebrush.css` is also provided:

```
\CSSFilename{lwarp_sagebrush.css}
```

See section [7.7](#) for more information about modifying the css styling of the document.

## 5.7 Customizing the HTML output

A number of settings may be made to control the HTML output, including filename generation, automatic compilation, math output, document splitting, meta data, and page headers and footers.

See section [7.6](#) for more information.

## 5.8 Using *latexmk*

*latexmk* is a L<sup>A</sup>T<sub>E</sub>X utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the `latexmk` option for the `lwarp` package:

`latexmk, % Use latexmk to compile.`

2. Recompile the printed version of the document.

Enter ⇒ **`lwarpmk print`**

`lwarp` updates its own configuration files (`lwarpmk.conf` and `tutorial.lwarpmkconf`) whenever the printed version of the document is compiled. These configuration files remember that `lwarpmk` should use `latexmk` to compile the document.

3. Recompile the document.

Enter ⇒ **`lwarpmk print`**

and/or

Enter ⇒ **`lwarpmk html`**

Changes are detected by comparing checksums rather than modification times, so `lwarpmk` again will not trigger a recompile, but `latexmk` has a much better awareness of changes than the `lwarpmk` utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source, and a single recompile may be forced with:

Enter ⇒ **`lwarpmk print1`**

and/or

Enter ⇒ **`lwarpmk html1`**

**forced single-pass recompile**

## 5.9 Using X<sub>E</sub>LATEX or LuaLATEX

X<sub>E</sub>LATEX or LuaLATEX may be used instead of LATEX.

1. Remove the auxiliary files for the project:

Enter ⇒ **lwarfmk cleanall**

2. Use *xelatex* or *lualatex* to compile the printed version a single time.

Enter ⇒ **xelatex tutorial.tex**

-or-

Enter ⇒ **lualatex tutorial.tex**

When the compile occurs, the configuration files for *lwarfmk* are modified to remember which TeX engine was used. X<sub>E</sub>LATEX or LuaLATEX will be used for future runs of *lwarfmk*.

3. To recompile the document:

Enter ⇒ **lwarfmk print**

-and-

Enter ⇒ **lwarfmk html**

4. Also remember to update the indexes and recompile again:

Enter ⇒ **lwarfmk htmlindex**

Enter ⇒ **lwarfmk html**

Enter ⇒ **lwarfmk printindex**

Enter ⇒ **lwarfmk print**

## 5.10 Using DVI LATEX

Traditional DVI LaTeX may also be used along with .eps image files. An SVG version of each image must also be provided. *lwarfmk* may be used to convert image formats.

To convert EPS files to PDF:

Enter ⇒ **lwarfmk epstopdf \*.eps**      (or a list of files)

To convert PDF files to SVG:

Enter ⇒ **lwarfmk pdftosvg \*.pdf**      (or a list of files)

⚠ bitmapped fonts See section 7.4 regarding font selection to avoid the use of bitmapped fonts.

## 5.11 Using a glossary

lwarp supports the `gloss` and `glossaries` packages, although this tutorial does not supply an example.

### 5.11.1 `gloss` package

See section [8.6.11](#).

### 5.11.2 `glossaries` package

To process the glossary for the print version:

Enter ⇒ **lwarpmk printglossary**

⚠ (If `makeglossaries` is not found, see section [8.6.12](#).)

To process the glossary for the HTML version:

Enter ⇒ **lwarpmk htmlglossary**

In each case, the document will have to be recompiled afterwards:

Enter ⇒ **lwarpmk html1**

Enter ⇒ **lwarpmk html**

Enter ⇒ **lwarpmk print1**

Enter ⇒ **lwarpmk print**

See section [8.6.12](#) to set options for processing glossaries.

## 5.12 Cleaning auxiliary files

To remove the auxiliary files .aux, .toc, .lof, .lot, .idx, .ind, .log, and .gl\*, and a few others:

Enter ⇒ **lwarfmk clean**

## 5.13 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the .pdf and .html files:

Enter ⇒ **lwarfmk cleanall**

## 5.14 Cleaning the images from the <project>-images directory

The <project>-images directory contains svg images automatically generated for inline and display math, tikz, etc. To remove all the images from the lateximages directory:

Enter ⇒ **lwarfmk cleanimages**

## 5.15 Converting PDF or EPS images to SVG

HTML cannot display PDF or EPS images, so any external PDF graphics images must be converted to SVG format. *pdftocairo* and *epstopdf* may be used one image at a time, but *lwarfmk* also provides a way to convert PDF or EPS images in bulk:

Enter ⇒ **lwarfmk epstopdf \*.eps**      (or a list of files)

Enter ⇒ **lwarfmk pdftosvg \*.pdf**      (or a list of files)

Be sure to always provide SVG files for HTML output.

## 5.16 Creating HTML from an incomplete compile

During testing it may be useful to finish the HTML conversion even when the document had errors and did not compile successfully. To attempt an HTML conversion of an incomplete document:

Enter ⇒ **lwarfmk pdftohtml [-p project]**

## 5.17 Processing multiple projects in the same directory

⚠ **xr, xr-hyper, xcite**

It is possible to have several projects in the same directory. *lwarfmk* has an optional parameter which is the document to compile.

To create each project:

Enter ⇒ **pdflatex project\_a**

Enter ⇒ **pdflatex project\_b**

Each project is given its own configuration file:

`project_a.lwarpmkconf`, `project_b.lwarpmkconf`

To compile each project with `lwarkmk`:

Enter ⇒ **lwarpmk print -p project\_a**

Enter ⇒ **lwarpmk print -p project\_b**

Enter ⇒ **lwarpmk html -p project\_a**

Enter ⇒ **lwarpmk html -p project\_b**

To generate each project's images:

Enter ⇒ **lwarpmk limages -p project\_a**

Enter ⇒ **lwarpmk limages -p project\_b**

To clean each project's images:

Enter ⇒ **lwarpmk cleanlimages -p project\_a**

Enter ⇒ **lwarpmk cleanlimages -p project\_b**

To clean each project's auxiliary files:

Enter ⇒ **lwarpmk cleanall -p project\_a**

Enter ⇒ **lwarpmk cleanall -p project\_b**

If using *bibtex*, for example, the HTML version must also be processed:

Enter ⇒ **bibtex project\_a.html**

## 5.18 Using the *make* utility

*lwarpmk* has an action which may be useful for integration with the common *make* utility:

`lwarpmk pdftohtml [-p project]`

*make* may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then *lwarpmk* may be used to convert each target to HTML files.

## 5.19 What next?

**How do I do something?** See the [General Index](#).

**Something do not work!** See the [Troubleshooting Index](#) or section 13: [Troubleshooting](#).

**Package options:** See section 28, [Package options](#).

**HTML and filename settings:** See section 7.6, [Customizing the HTML output](#).

**Footnote placement:** See section 7.6, [Customizing the HTML output](#).

**Title page, indexing, glossaries:** See section 8.6, [Front and back matter](#).

**Shell escape:** See section 7.3, [Shell escape](#).

**css customization:** See section 7.7, [Customizing the css](#).

**MATHJAX customization:** See section 8.7.5, [Customizing MATHJAX](#).

**Localization:** (languages) — See section 7.1, [Localization](#).

**Accessibility:** (alt and title tags) — See section 7.2, [Accessibility](#).

**Converting an existing document:** See section 6, [Converting an existing document](#).

**EPUB conversion:** See section 10, [EPUB conversion](#).

**Word processor conversion:** See section 11, [Word-processor conversion](#).

## 6 Converting an existing document

To convert an existing document for use with l warp:

1. Arrange the document in the following order:
  - (a) Declare the \documentclass.
  - (b) Load text fonts.
  - (c) Load inputenc or inputenx, fontenc, or fontspec.
  - (d) Load l warp.
  - (e) Load remaining packages.
2. Modify the document:
  - (a) If using named HTML files, in section names use paren math  $\backslash(x+y\backslash)$  instead of dollar math  $\$x+y\$$ . (Dollar math works, but appears in the file-name.) Or, use a short name for the toc entry without the math, or use \texorpdfstring:
 

```
\section{A name with math
    \texorpdfstring{\$1+2=3\$}{text description}}
```
  - (b) Avoid using the \includegraphics scale option. Change:
 

```
\includegraphics[scale=<xx>]{...}
```

 to:
 

```
\includegraphics[width=<yy>\linewidth]{...}
```
  - (c) Possible changes to tabular environments include: \* columns, multirow, longtable, supertabular, xtab, bigdelim. See section 8.10.1.
  - (d) If using braces in package options, such as with caption, see section 8.1.
  - (e) Possible option clashes with memoir. See section 8.13.
  - (f) If using indexes, see section 8.6.15.
  - (g) If using many indexes, glossaries, . aux files, etc., see section 8.6.15 regarding morewrites. If morewrites is already used, be sure to add the setup with allocate=10.
  - (h) Other changes as per Special cases and limitations, section 8.
3. Convert any PDF images to SVG. See section 8.8.
4. Manually compile the print version with *latex*, *pdflatex*, *lualatex*, or *xelatex*.
5. l warpmk print to finish the print version.
6. l warpmk html to create the HTML version.
7. l warpmk limages to create the SVG images of any SVG math, lateximage, Tikz, etc.

Need help?

---

See the General Index for “how-to”, and the Troubleshooting Index if something doesn’t work. A Troubleshooting section is also available. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

## 7 Additional details

### 7.1 Localization

Regional localization is supported by lwarp via the following package options and macros:

**Object names:** L<sup>A</sup>T<sub>E</sub>X provides redefinable names for various objects, and lwarp adds a few more. Use \renewcommand to change these.

\abstractname: This macro is honored by lwarp.

\linkhomename: Displayed by the link to the homepage.

\sidetocname: Displayed at the head of the sidetoc.

**HTML settings:** See table 6 and section 7.6 for details.

\HTMLLanguage: The language to declare for each web page.

\ImageAltText, \MathImageAltText, \PackageDiagramAltText, \AltTextOpen,  
  \AltTextClose: The defaults used for HTML alt text for images. See section 7.2.

\CSSFilename: The name of the css file to use.

\MathJaxFilename: The name of the MATHJAX script to use.

#### Package options:

**ImagesName and ImagesDirectory:** These options control the filenames used by lwarp when it automatically generates images. See table 5 and section 7.5.

**xindyStyle, xindyLanguage, xindyCodepage:** When using *xindy*, these options may be set according to local use. See section 8.6.21.

**pdftotextEnc:** To adjust the encoding of *pdftotext*.

### 7.2 Accessibility

lwarp provides several methods for improving access to the document using tools such as text-only browsers, copy / paste, text-to-speech readers, or Braille readers. HTML provides the alt text attribute for images, which is used by lwarp as described below. HTML also provides the title attribute, which usually generates a pop-up text. lwarp can add this to a reference or hyperlink. MATHJAX also has provisions for improved accessibility as well.

**\ImageAltText:** The default HTML alt text for \includegraphics and \textrm{images}. Set with \renewcommand.

**\includegraphics alt key:** For \includegraphics, lwarp adds the alt key / value. For example:

---

```
\includegraphics[alt={Some text.}]{filename}
```

**svg math:** For simple SVG math, `lwarp` places the L<sup>A</sup>T<sub>E</sub>X math expression in the alt text, so that the L<sup>A</sup>T<sub>E</sub>X expression may be copied and pasted to another document as plain text.

**\MathImageAltText:** For complicated SVG math, such as enclosed in `\InlineMathOther` / `\InlineMathNormal`, or `\DisplayMathOther` / `\DisplayMathNormal`, the HTML alt text will be set to `\MathImageAltText`. Set with `\renewcommand`.

**MATHJAX:** For MATHJAX, the accessibility tools provided by MATHJAX are enabled by default by `lwarp`'s MATHJAX scripts.

**\PackageDiagramAltText:** Various packages create diagrams which `lwarp` converts into SVG images. These are given alt text set to `\PackageDiagramAltText`. Set with `\renewcommand`.

**custom alt text \ThisAltText:** The HTML alt text of the next image may be set with:

```
\ThisAltText{Custom text about the image.}
<SVG math, Tikz, picture, etc.>
```

The next single image will be generated with the given text, and the following images will revert to back to their defaults.

#### references and links

`\ThisAltText` may also be used to assign an HTML title to the next reference or hyperlink.

```
\ThisAltText{Custom text about the link.}
Text ... \ref{label_name} ... text.
```

See section 7.6.

**\AltTextOpen and \AltTextClose:** By default, HTML alt text is enclosed by parentheses. This may be changed by redefining `\AltTextOpen` and `\AltTextClose`. Set with `\renewcommand`.

## 7.3 Shell escape

**Opt --shell-escape** Some documents require the use of an external program, which is allowed when using the `--shell-escape` command-line option. When the document is first compiled manually, and also whenever the print version is recompiled, `lwarp` detects and remembers whether shell escape is enabled. If so, it will also be enabled when the document is recompiled with `lwarpmk`.

## 7.4 Font and UTF-8 support


### ⚠ type 3 bitmap fonts

`lwarp` uses `pdftotext` to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which may prevent the use of older “type 3” bit-mapped fonts, and of older packages such as `ae`. The `lwarp` option `pdftotextEnc` may be useful in some situations. See section 7.5.

### vector fonts

While using DVI `latex` or PDF `pdflatex`, if no font-related package is specified then the

**Computer Modern** default COMPUTER MODERN font is used, which may be a “type 3” bit-mapped font which may not convert well to plain text. A “type 1” vector font is required.

**pdflatex****Pkg DVI latex**

To use the updated cm-super’s type 1 fonts instead of Computer Modern, install the cm-super font package.

**Pkg lmodern** To use Latin Modern instead, add

```
\usepackage{lmodern}
```

to the preamble.

**Pkg dejavu** Another useful option is the Deja Vu series of fonts, which have an increased coverage of language and glyphs:

```
\usepackage{dejavu}
```

**latex, pdflatex, T1, UTF8** While using DVI *latex* or PDF *pdflatex*, l warp automatically loads *fontenc* with T1 encoding. *fontenc* may be loaded with an additional encoding after l warp. *inputenc* is automatically loaded with UTF8 encoding if it has not yet been loaded, but may also be specified with another encoding such as latin1. See the next section regarding index encoding.



**xelatex and lualatex** X<sub>E</sub>LATEX and LuaLATEX users must use the *fntspec* package. Do NOT use *fontenc*!

Place *fntspec* or *fontenc*, *xunicode*, and other font and UTF-8 related commands after the \documentclass command and before \usepackage{l warp}.



**package conflicts** In some cases, a package conflict may require that a font package be loaded after l warp, which should work as well:

1. *documentclass{article/book/report}* comes first, followed by any of:

2. Font and UTF-8 related commands:

- For X<sub>E</sub>LATEX or LuaLATEX:

**Pkg fntspec**

- *fntspec* and font choices

**ligatures**

l warp sets the following to turn off TeX ligatures during the generation of HTML tags, and turn off common ligatures in regular text, since older browsers may not display them correctly and newer browsers can automatically re-create them.

---

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
```

---

- For *pdflatex*:

**Pkg lmodern**

- (a) \usepackage{lmodern}, or other font-related packages

**Pkg fontenc**

- (b) \usepackage[T1]{fontenc}

**Pkg inputenc**

- (c) \usepackage[utf8]{inputenc}, or latin1, etc. Or use inputenx.

**Pkg inputenx**

- (d) \usepackage{newunicodechar} along with related definitions.

**Pkg newunicodechar**

- (e) To assist with the PDF-HTML conversion:

- i. \input glyptounicode.tex

**File glyptounicode.tex**

- ii. `\input glyptounicode-cmr.tex%` from the `pdfx` package
- iii. `\pdfgentounicode=1`

(f) Another option to assist with the PDF-HTML conversion:

Pkg	cmap
Pkg	textcomp

– `\usepackage{cmap}`

(g) `\usepackage{textcomp}`

3. `\usepackage{l warp}` (section 7.5) goes after any of the above, followed by:
4. `\usepackage{newtxmath}` or other math-related font packages. Many of these load `amsmath`, which must be loaded after `l warp`, so they must also be loaded after `l warp`.
5. `\setmonofont{TeX Gyre Cursor}` or similar may be required if using X<sub>E</sub>L<sup>A</sup>T<sub>E</sub>X or L<sup>A</sup>U<sub>L</sub>AT<sub>E</sub>X and `fontspec` along with traditional font packages such as `txfonts`, `newtxtext`, etc. This is required to turn off the monospaced font's ligatures with `fontspec` after loading the traditional font packages. Monospaced output ligatures must be turned off to produce the correct HTML characters.
6. ... the rest of the preamble and the main document.

**⚠️ fontspec with traditional font packages** In some cases, an external program may require a UTF-8 “locale”. See section 9.8.

#### 7.4.1 Indexes, glossaries, and encoding

`l warp` uses the `xindy` program to processes indexes. `xelatex` and `lualatex` use `xindy` and `pdflatex` uses `texindy`.

The `l warp` option `xindyLanguage` may be used to set the language option for `xindy`, and the `xindyCodepage` option may be used to set the codepage option for `xindy`. These are used for index generation.

## 7.5 l warp package loading and options

l warp supports book, report, and article classes, as well as the equivalent Koma-script classes and memoir, and various CJK-related classes and packages.

Load the l warp package immediately after the font and UTF-8 setup commands.

Package options may be set while loading l warp, or later with

```
\l warpmksetup{<key=value, . . . >}
```

Pkg l warp l warp package options are as follows:

Opt mathsvg **mathsvg**, **mathjax**: For math display, select mathsvg (default) or mathjax. For more information about the math options, see section 8.7.

Opt latexmk **latexmk**: Tells l warpmk to use latexmk to recompile the document several times if necessary. Otherwise, l warpmk attempts to determine for itself whether to recompile. See section 7.6.

Opt dvips **dvips**: Tells l warpmk to use dvips and ps2pdf to convert DVI output to PDF.  
Default: false

Opt dvipdfm **dvipdfm**: Tells l warpmk to use dvipdfm to convert DVI output to PDF.  
Default: false

Opt dvipdfmx **dvipdfmx**: Tells l warpmk to use dvipdfmx to convert DVI output to PDF.  
Default: false

Opt HomeHTMLFilename **HomeHTMLFilename**: See section 7.6.  
Default: {}

Opt HTMLFilename **HTMLFilename**: See section 7.6.  
Default: {}

Opt ImagesName **ImagesName**: The prefix for the images automatically generated by l warp for objects such as SVG math and lateximages.  
Default: image-

Opt ImagesDirectory **ImagesDirectory**: The directory for the images automatically generated by l warp for objects such as SVG math and lateximages. By default, these images will appear in a directory named <jobname>-images, and the images will be named and numbered image-<nn>.  
Default: \jobname-images

Opt PrintLatexCmd **PrintLatexCmd**: Sets the shell commands executed by l warpmk print. If not specified, will automatically be set according to the detected LATEX engine and the use of --shell-escape.  
Default: <automatic>

Opt HTMLLatexCmd **HTMLLatexCmd**: Sets the shell commands executed by l warpmk html. If not specified, will automatically be set according to the detected LATEX engine and the use of --shell-escape.  
Default: <automatic>

Opt makeindex **makeindex**: Sets PrintIndexCmd, HTMLIndexCmd, and LatexmkImageCmd to use makeindex  
Default: makeindex

Table 5: lwarp package options

Option	Description
<code>mathsvg</code>	Show math using SVG images.
<code>mathjax</code>	Show math using MATHJAX.
<code>latexmk</code>	Use <i>latexmk</i> for compiling documents.
<code>dvips</code>	Use <i>dvips</i> and <i>ps2pdf</i> to convert DVI documents.
<code>dvipdfm</code>	Use <i>dvipdfm</i> to convert DVI documents.
<code>dvipdfmx</code>	Use <i>dvipdfmx</i> to convert DVI documents.
<code>HomeHTMLFilename</code>	The filename of the home page.
<code>HTMLFilename</code>	A prefix for the filenames of the remaining web pages.
<code>ImagesName</code>	A prefix for the filenames of generated images.
<code>ImagesDirectory</code>	The directory used to hold generated images.
<code>PrintLatexCmd</code>	The shell commands for <code>lwarpmk print</code> .
<code>HTMLLatexCmd</code>	The shell commands for <code>lwarpmk html</code> .
For indexing (section 8.6.15) and glossaries (section 8.6.12):	
<code>makeindex</code>	Use <i>makeindex</i> to generate indices.
<code>xindy</code>	Use <i>xindy</i> to generate indices.
<code>makeindexStyle</code>	Set a custom style for <i>makeindex</i> .
<code>xindyStyle</code>	Set a custom style for <i>xindy</i> .
<code>xindyLanguage</code>	The <i>xindy</i> language option used for index generation.
<code>xindyCodepage</code>	The <i>xindy</i> codepage option used for index generation.
<code>PrintIndexCmd</code>	Shell commands executed by <code>lwarpmk printindex</code> .
<code>HTMLIndexCmd</code>	Shell commands executed by <code>lwarpmk htmlindex</code> .
<code>LatexmkIndexCmd</code>	Shell commands executed by <i>latexmk</i> .
<code>GlossaryCmd</code>	Shell command executed by <code>lwarpmk printglossary</code> and <code>lwarpmk htmlglossary</code> .
Seldom necessary:	
<code>OSWindows</code>	Force compatibility with MS-WINDOWS.
<code>pdftotextEnc</code>	Set the encoding for <i>pdftotext</i> .
<code>lwarpmk</code>	Generate a local copy of <code>lwarpmk.lua</code> .
Used internally by <code>lwarp</code> :	
<code>warpprint</code>	Generate print output, and also generate configuration files.
<code>warpHTML</code>	Generate HTML output.
<code>BaseJobname</code>	The \jobname to use. Set to the \jobname of the printed version even while generating HTML.

when generating indexes with **lwarpmk printindex**, **lwarpmk htmlindex**, or **latexmk**. If neither `makeindex` nor `xindy` is used, `makeindex` is assumed.

**Opt** `xindy` **xindy:** Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use `xindy` when generating indexes with **lwarpmk printindex**, **lwarpmk htmlindex**, or **latexmk**.  
**Default:** `makeindex`

**Opt** `makeindexStyle` **makeindexStyle:** If you wish to use a custom `.ist` file for index generation, see section 28.  
**Default:** `lwarp.ist`

**Opt** `xindyStyle` **xindyStyle:** If you wish to use a custom `.xdy` file for index generation, see section 28.  
**Default:** `lwarp.xdy`

**Opt** `xindyLanguage` **xindyLanguage:** If using an index or glossary, see section 28.  
**Default:** `english`

**Opt** `xindyCodepage` **xindyCodepage:** If using an index, see section 28.  
**Default:** `utf8`

**Opt** `PrintIndexCmd` **PrintIndexCmd:** Sets the shell commands executed by **lwarpmk printindex**. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 8.6.15.  
**Default:** `<automatic>`

Examples:

```
makeindex -s lwarp.ist projectname.idx          (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname.idx    (xindy)
```

### automatic setting

The use of the `makeindex` or `xindy` options sets `PrintIndexCmd` to sensible values for each of those programs while compiling a single index. `lwarp`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified.

#### ⚠️ xindy

If specifying `PrintIndexCmd` manually, be sure to assign an `xindy` language and codepage with the `-L` and `-C` `xindy` options, as the `lwarp` `xindyLanguage` and `xindyCodepage` options are not used for the `PrintIndexCmd` option when it is set manually.

This option is stored in the configuration files `lwarpmk.conf` and `*.lwarpmkconf`, and is then passed by the **lwarpmk printindex** command to the operating system to compile the print indexes. Since the command string is parsed by TeX, written to a file, read from the file by LuaTeX, and finally passed to the operating system, any attempt at quoting will be problematic. For complicated commands, it would be best to create a shell script, and simply refer to the script with the `lwarp PrintIndexCmd` option.

### Opt `HTMLIndexCmd` **HTMLIndexCmd:** Sets the shell commands executed by **lwarpmk htmlindex**. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 8.6.15. **Default:** `<automatic>`

#### ⚠️ filenames

Example settings are similar to `PrintIndexCmd`, but append `_html` to the filenames:

```
makeindex -s lwarp.ist projectname_html.idx      (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname_html.idx  (xindy)
```

### automatic setting

The use of the `makeindex` or `xindy` options sets `HTMLIndexCmd` to sensible values for each of those programs while compiling a single index. `lwarp`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified.

**⚠️ xindy**

If specifying `HTMLIndexCmd` manually, be sure to assign an `xindy` language and codepage with the `-L` and `-C xindy` options, as the `lwarf xindyLanguage` and `xindyCodepage` options are not used for the `HTMLIndexCmd` option when it is set manually.

As with `PrintIndexCmd`, to generate complicated indexes it may be worthwhile to use a shell script, then refer to that script with `HTMLIndexCmd`.

Opt `LatexmkIndexCmd`  
Default: `<automatic>`

**LatexmkIndexCmd:** Sets the shell commands executed by `latexmk`. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `LatexmkIndexCmd` does not include any filenames, which will be provided instead by `latexmk`. See section 8.6.15.

Example settings are similar to `PrintIndexCmd`, but without a filename:

<code>makeindex -s lwarf.ist</code>	<i>(makeindex)</i>
<code>xindy -M lwarf.xdy -L english -C utf8</code>	<i>(xindy)</i>

**automatic setting**

The use of the `makeindex` or `xindy` options sets `LatexmkIndexCmd` to either of the two settings show above. `lwarf`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `latexmk` uses either of the single-line settings of `LatexmkIndexCmd` shown above to compile each of multiple indexes if necessary.

**⚠️ xindy**

If specifying `LatexmkIndexCmd` manually, be sure to assign an `xindy` language and codepage with the `-L` and `-C xindy` options, as the `lwarf xindyLanguage` and `xindyCodepage` options are not used for the `LatexmkIndexCmd` option when it is set manually.

Opt `GlossaryCmd`  
Default: `makerglossaries`

**GlossaryCmd:** Sets the shell command executed by `lwarpmk printglossary` and `lwarpmk htmlglossary`. The print or HTML glossary filename is appended to this command. See section 8.6.12.

Opt `OSWindows`

**OSWindows:** `lwarf` attempts to automatically sense WINDOWS, but it may be forced with this option. See section 7.8.

Opt `pdftotextEnc`  
Default: `UTF-8`

**pdftotextEnc:** Used to specify the encoding used by `pdftotext` during the PDF-HTML conversion. In most situations, the default is the correct choice.

Opt `lwarpmk`

**lwarpmk:** If you wish to have `lwarf` generate a local copy of `lwarpmk.lua` for archival or local-installation purposes, compile the print version with the `lwarpmk` option set. See section 28.

---

The following options are used internally by `lwarf`, and usually are not used in the user's document:

---

Opt `warpprint`  
Opt `warpHTML`

**warpprint and warpHTML:** Usually controlled by `lwarpmk`, and not set in the document. Select the `warpprint` option to generate print output (default), or the `warpHTML` option to generate HTML5 output. The default is print output, so the print version may be compiled with the usual `pdflatex`, etc. When `lwarf` is loaded in print mode, it creates `<project>.html.tex`, which sets the `warpHTML` option before calling the user's source code `<project>.tex`. In this way, `<project>.tex` can `\usepackage{lwarf}` without any options to create a printed version, while `<project>.html.tex` will create an HTML version.

**BaseJobname:** Not intended for the user. Used internally by `lwarp` when creating the `*_html.tex` file used to compile the `HTML` version. See section 28.

## 7.6 Customizing the HTML output

Table 6 shows several settings may be used to customize the HTML output. Watch for the correct placement of each!

**⚠ Placement!** Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:

Enter ⇒ **lwarfmk clearall**

2. Recompile the print version in order to recreate the configuration files for *lwarfmk*:

Enter ⇒ **lwarfmk print**

3. Finally, recompile the HTML version with the new settings:

Enter ⇒ **lwarfmk html**

### Options for the lwarf package:

Use the following as options for \usepackage[<options>]{lwarf}:

Opt **HomeHTMLFilename**  
Default: \BaseJobname

**HomeHTMLFilename:** Filename of the homepage, without the “.html” suffix. Defaults to the \BaseJobname. A common setting is:

HomeHTMLFilename=index

filename underscores

causing the homepage to be the file index.html. Underscores are allowed in HomeHTMLFilename and HTMLFilename options, but may need to be escaped elsewhere, such as when appearing in a list:

\item [ \href{file\\_name.pdf}{text} ] \

See section 7.6.1 for examples of naming and numbering HTML files.

Opt **HTMLFilename**  
Default: <empty>

**HTMLFilename:** A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty. See section 7.6.1 for examples of naming and numbering HTML files.

Opt **latexmk**  
Default: false

**latexmk:** Controls whether lwarf uses *latexmk* to compile the document. This setting is written to *lwarfmk*'s configuration files.

Opt **mathsvg**  
Default: true

**mathsvg:** Selects SVG display for math output. (The default.)

Opt **mathjax**  
Default: false

**mathjax:** Selects MATHJAX for math output.

Opt **makeindex**

**makeindex:** Selects *makeindex* for index generation by *lwarfmk*.

Default: **makeindex**

Opt **xindy**

**xindy:** Selects *xindy* for index generation by *lwarfmk*.

Default: **makeindex**

### Placed in the preamble before \begin{document}:

\linkhomename  
Default: Home

**\linkhomename:** Name of the link to the home page. Paragraphs are allowed. Redefine with \renewcommand.

Table 6: HTML settings

Macro/Cntr/Bool	Description
\linkhomename	Name of the link to the homepage.
SideTOCDepth	Sectioning depth of the sidetoc.
\sidetocname	Name of the sidetoc.
FileDepth	Sectioning depth of the file splits.
CombineHigherDepths	Combine higher section levels.
FileSectionNames	Use section names for file names, else use numbers.
\FilenameLimit	Maximum length of the generated filenames.
FootnoteDepth	Sectioning depth of footnotes.
\abstractname	The name of the abstract.
\ImageAltText	\includegraphics and other images' alt tag.
\ThisAltText {<text>}	Assigns an alt/title tag for the next image or link.
\MathImageAltText	The SVG math image \teximage alt tag.
\PackageDiagramAltText	The suffix for a package's \teximage alt tags.
\AltTextOpen	Start an HTML alt tag.
\AltTextClose	End an HTML alt tag.
\CSSFilename	The css for the following files.
\MathJaxFilename	The MathJax script for the following files.
\HTMLLanguage	The HTML lang tag.
\HTMLTitle	The homepage's <title>, overriding \title.
\HTMLTitleBeforeSection	Set subpage <title>s to \HTMLTitle - sectionname
\HTMLTitleAfterSection	Set subpage <title>s to sectionname - \HTMLTitle
\HTMLAuthor	The HTML author meta tag, overriding \author.
\HTMLDescription	The HTML description meta tag.
\HTMLFirstPageTop	Heading for the home page.
\HTMLPageTop	Heading for the other pages.
\HTMLPageBottom	Footing for all pages.
HTMLDebugComments	Boolean to generate HTML comments.

Ctr tocdepth

**tocdepth:** Sectioning depth of the table of contents. See section 16 for a list of LATEX stack depths.

Ctr SideTOCDepth

Default: 1

**SideTOCDepth:** Sectioning depth of the sidetoc. Defaults to 1, causing the sidetoc to show sections but not subsections.

sideroc

Each subpage of the website has its own small table of contents on the side (the “sidetoc”). Its depth is set by SideTOCDepth. This sidetoc is only shown if the browser display is wide enough. When using a narrow web browser window, “responsive web design” is used to show the sidetoc at the top of the page, as well as a link back to **Home** at the top and bottom.

It is recommended to set:

SideTOCDepth=FileDepth

or

SideTOCDepth=FileDepth+1

### ⚠️ inaccessible pages

If SideTOCDepth < FileDepth, web pages will be inaccessible via the sidetoc.

\\sidetocname  
Default: Contents

**\\sidetocname:** Name of the sidetoc. Paragraphs are allowed. Redefine with \\renewcommand.

Ctr FileDepth  
Default: -5

**FileDepth:** Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.

- To place the entire file into one HTML page, use:  
 $\setcounter{FileDepth}{-5}$
- To split the HTML file at \\section depth, use:  
 $\setcounter{FileDepth}{1}$
- To ensure that the HTML pages/files are accessible:  
Place a \\tableofcontents somewhere before the first section break (therefore in the “home page”), and set  
 $tocdepth \geq FileDepth$

Bool CombineHigherDepths  
Default: true

**CombineHigherDepths:** Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

### ⚠️ Inaccesible pages!

### ⚠️ Lost in an old page!

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (lwarpmk cleanall), change FileDepth

and/or `CombineHigherDepths`, then finally recompile and renavigate to the desired page using the new file structure.

`Bool FileSectionNames`  
`Default: true`

 **Unique filename!**

**FileSectionNames:** If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the `HTMLFilename` option is used as a prefix. See section [7.6.1](#) for examples of naming and numbering HTML files. The user must ensure that filenames are unique after begin sanitized. For example, `math` in the section name is removed before creating the filename, so the rest of the filename must be sufficiently unique to avoid name collisions.

`\FilenameLimit`  
`Default: 80`

**\FilenameLimit:** The maximum length of the filenames generated by `lwarp`. `".html"` is added to this length. Redefine with `\renewcommand`.

`Ctr FootnoteDepth`  
`Default: 3`

**FootnoteDepth:** Determines where to place pending footnotes. 3 places footnotes before each break down to the `\subsubsection` level. 1 places footnotes before each `\section` break. Any pending footnotes are also placed at the bottom of each page before each file break.

`Bool HTMLDebugComments`  
`Default: false`

**HTMLDebugComments:** Set true to generate HTML comments, such as which section or `<div>` is being opened or closed.

`\abstractname`  
`Default: Abstract`

**\abstractname:** The name of the abstract. This may also be over-written by the `babel` package. Defaults to `"Abstract"`. Redefine with `\renewcommand`.

**Placed before `\begin{document}`, or before any sectioning command which causes a file break:**

`\CSSFilename`  
`Default: lwarp.css`

**\CSSFilename:** `{<filename.css>}` Sets the css file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The css styles of the web pages are set by the `\CSSFilename` command. If `\CSSFilename` is not used, a default plain style is used to mimic printed L<sup>A</sup>T<sub>E</sub>X output. `lwarp_sagebrush.css` is a semi-fancy colored style as shown in this tutorial. Change it to `lwarp_formal.css` for a more formal look, or comment out the `\CSSFilename` command to see the default. `\CSSFilename` may be used before each file break to set the css for individual pages of the website.

`\MathJaxFilename`  
`Default: lwarp_mathjax.txt`

**\MathJaxFilename:** `{<filename>}` Sets the MathJax script file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The MathJax script file is copied into the head of each HTML file. This may be used to point to a local repository, add extensions, or change the script somewhere in the middle of the document. `\MathJaxFilename` may be used before each file break to set the script file for individual pages of the website.

`\HTMLLanguage`  
`Default: en-US`

**\HTMLLanguage:** `{<language>}` The HTML file's HTML lang meta tag. Defaults to en-US.

`\HTMLTitle`  
`Default: \thetitle`

**\HTMLTitle:** `{<title>}` Overrides `\title` for the HTML header's meta title. De-

faults to `\thetitle`, which is set by `\title`, or empty otherwise. Unlike the author, `\thetitle` is set by `\title` even if not using the `titling` package.

`\HTMLTitleBeforeSection`  
Default: `\HTMLTitleBeforeSection`

`\HTMLTitleAfterSection`

`custom <title>`

To customize subpage `<title>`s, redefine `\theHTMLTitleSection`, which defaults to:

```
\def\theHTMLTitleSection{%
  \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
}
```

`\HTMLAuthor`  
Default: `\theauthor`

`\HTMLAuthor: {<author>}` The HTML header's meta author. Defaults to `\theauthor`, which is set by `\author` if using the `titling` package, but is empty otherwise. There are several ways to represent the author and affiliations, especially if using the `authblk` package, most of which do not result in a sensible `\theauthor`, so `\HTMLAuthor` is useful to create a list of authors without their affiliations.

`\HTMLDescription`  
Default: `<empty>`

`\HTMLDescription: {<description>}` Sets the HTML description tag for the following files. May be changed before each sectioning command which would cause a file split.

`\HTMLFirstPageTop`  
Default: `<empty>`

`\HTMLFirstPageTop: {<contents>}` A user-definable custom action applied to the top of the home page. Useful for logos, etc. Defaults empty. Ignored in print output.

`\HTMLPageTop`  
Default: `<empty>`

`\HTMLPageTop: {<contents>}` A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. `\LinkHome` may be used to place a link back to the homepage. Ignored in print output.

`\HTMLPageBottom`  
Default: `<empty>`

`\HTMLPageBottom: {<contents>}` A user-definable custom action applied to the bottom of each web page. Useful for authors, copyright notices, contact information, etc. Defaults empty. `\LinkHome` may be used to place a link back to the homepage. Ignored in print output.

**Placed in the home page before the first sectioning command which causes a file break:**

`\tableofcontents`  
⚠ TOC on the homepage!

`\tableofcontents:` Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage.

Links to each chapter/section are provided, as selected by `tocdepth`.

**Placed in the document wherever necessary:**

`\ImageAltText`  
Default: `image`

`\ImageAltText:` Redefine with `\renewcommand`. `\includegraphics` and other images are assigned an HTML alt tag according to `\ImageAltText` along

with `\AltTextOpen` and `\AltTextClose`. This text is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `\includegraphics` and other images.

`\ThisAltText`

**`\ThisAltText:`** `{<text>}` `\ThisAltText` can be used to assign an HTML alt text attribute to the next image generated by a `lateximage`, `picture`, `tikzpicture`, or any other similar environment which generates an image, or the next SVG math expression. This tag is cleared after use. The tag is also cleared after each MATHJAX expression, in case the user changes between SVG math and MATHJAX.

`\ThisAltText` also may be used to add an HTML title to a reference or hyperlink, such as a `\ref`, `\cref`, `\href`, `\url`, `\hyperref`, or `\hyperlink`. In each case, the alternative text is cleared after use.

`\MathImageAltText`  
Default: `math image`

**`\MathImageAltText:`** Redefine with `\renewcommand`. When creating an SVG math image, its HTML alt tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the alt tag is set to `\MathImageAltText`, along with `\AltTextOpen` and `\AltTextClose`, and the image is not reused.

This alt expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “math image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

`\PackageDiagramAltText`  
Default: `diagram`

**`\PackageDiagramAltText:`** Redefine with `\renewcommand`. For many packages, the output is placed inside a `lateximage` with an HTML alt tag set to the package name followed by `\PackageDiagramAltText`. For example:

`(-xy- diagram)`

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “diagram”, and may it be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

`\AltTextOpen`  
Default: `(`  
`\AltTextClose`  
Default: `)`

**`\AltTextOpen:`** Redefine with `\renewcommand`.

**`\AltTextClose:`** Redefine with `\renewcommand`. HTML alt text is enclosed by the macros `\AltTextOpen` and `\AltTextClose`, which default to an opening and closing parenthesis.

Env `warpprint`

**`warpprint:`** An environment which is only used while generating print output. Place inside anything which does not apply to HTML and which may cause problems with `lwarp`. If `lwarp` knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won’t have to be placed inside a `warpprint` environment, but unknown packages may cause problems which may be isolated from `lwarp` using this environment.



*Do not place anything else on the same line as \end{warpprint}.*

Env warpHTML

**warpHTML:** An environment which is only used while generating HTML output.  
This is useful for website logos and other items which have no purpose in printed output.



*Do not place anything else on the same line as \end{warpHTML}.*

\warpprintonly

**\warpprintonly:** {\<contents>} A macro version of the warpprint environment.

\warpHTMLonly

**\warpHTMLonly:** {\<contents>} A macro version of the warpHTML environment.

### 7.6.1 Example HTML file naming

Examples of ways to name or number HTML files:

#### Numbered HTML nodes:

Example: Homepage index.html, and node-1, node-2.<sup>13</sup>

---

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={node-}
]{lwarp}
\boolfalse{FileSectionNames}
```

---

#### Named HTML sections, no prefix:

Example: index.html, and About.html, Products.html

---

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={}
]{lwarp}
\booltrue{FileSectionNames}
```

---

#### Named HTML sections, with prefix:

Example: Homepage mywebsite.html, and additional pages such as mywebsite-About.html, mywebsite-Products, etc.

---

```
\usepackage[
    HomeHTMLFilename=mywebsite,
    HTMLFilename={mywebsite-}
]{lwarp}
\booltrue{FileSectionNames}
```

---

## 7.7 Customizing the css

\CSSFilename {<filename>}

Default: lwarp.css

---

<sup>13</sup>See \SetHTMLFileName to number in groups by chapter, for example.

\CSSFilename may be used to choose which .css file is used to display each page of the web site. Use \CSSFilename before \begin{document} to assign the style of the home page. If different parts of the website should have different styles, call \CSSFilename again before each section heading which creates a new file. This may be changed numerous times throughout the file, resulting in different HTML pages having different css files assigned:

```
...
\CSSFilename{myCSS.css}
\chapter{Another Chapter}
...
```

The styles provided by lwarp include:

**lwarp.css:** A default style if \CSSFilename is not used. This style is comparable to a plain LATEX document. To set this style, you may use \CSSFilename{lwarp.css}, or no \CSSFilename call at all.

**lwarp\_formal.css:** A formal style with a serif fonts and a traditional look.

**lwarp\_sagebrush.css:** A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the \CSSFilename entry in the tutorial, lwarpmk html again, and then reload the tutorial webpage.

**Custom css** A customized style may also be created. For each new project a file called sample\_project.css is generated. This may be renamed to <project>.css then used by assigning \CSSFilename{<project>.css}.

**⚠ Rename it!** Note that sample\_project.css is overwritten whenever lwarp is loaded in print mode. It is therefore important to rename the file to something like <project>.css before using it, so that your own changes are not overwritten.

<project>.css has an entry which loads lwarp.css, and this entry may be changed to load lwarp\_formal.css or lwarp\_sagebrush.css if desired. Additional changes to the css may be made by making entries later in the <project>.css file.

File lwarp.css File project.css File sample_project.css	It is best to make a local project-specific css file such as project.css, containing only things which are different from lwarp.css. The file project.css should refer to lwarp.css as follows:
---	---

---

```
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
```

---

```
/* . . . */

/* ( --- End of project.css --- ) */
```

---

Finally use \CSSFilename{<project>.css} in the document to activate the custom CSS.

## 7.8 Selecting the operating system

- Prog Unix lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as “UNIX” in the configuration files), and MS-WINDOWS is supported as well.
- Prog Mac OS
- Prog Linux
- Prog MS-Windows If MS-WINDOWS is not correctly detected, use the lwarp option OSWindows.
- Prog Windows
- Opt OSWindows When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean usingOSWindows is set true. This boolean may be tested by the user for later use.

## 7.9 Selecting actions for print, HTML, or MATHJAX output

The following environments and macros are used to select actions which only apply to either traditional L<sup>A</sup>T<sub>E</sub>X print-formatted PDF generation, or to HTML generation, or to HTML with MATHJAX.

For most of built-in L<sup>A</sup>T<sub>E</sub>X and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which lwarp does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

- Env warpHTML Anything which is to be done only for HTML5 output is surrounded by a warpHTML environment:

---

```
\begin{warpHTML}
... something to be done only during \HTML\ generation
\end{warpHTML}
```

---

 **\end{warpHTML}** Do *not* place anything else on the same line as \end{warpHTML}. The exact phrase is used to mark the end of the environment.

- Env warpprint Anything which is to be done only for print output is surrounded by a warpprint environment:

---

```
\begin{warpprint}
  ... something to be done only during traditional \PDF\ generation
\end{warpprint}
```

---

 `\end{warpprint}` As above, do not place anything else on the line with `\end{warpprint}`.

`Env` `warpall` Anything which is to be done for any output may be surrounded by a `warpall` environment. Doing so is optional.

---

```
\begin{warpall}
  ... something to be done during print \PDF\ or \HTML\ output
\end{warpall}
```

---

As above, do not place anything else on the line with `\end{warpall}`.

Macros are also provided for print-only or HTML-only code:

`\warpprintonly {<actions>}`

Performs the given actions only when print output is being generated.

`\warpHTMLonly {<actions>}`

Performs the given actions only when HTML output is being generated.

`Env` `warpMathJax` Anything which is to be done only while using HTML output with MATHJAX is surrounded by a `warpMathJax` environment. Usually, this is `\CustomizeMathJax`, used to add emulation macros.

## 7.10 Commands to be placed into the `warpprint` environment

Certain print-related commands should always be placed inside a `warpprint` environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: `\parindent` `\parskip`
- Manual page positions such as the `textpos` package, which is emulated but only in a limited way.
- Anything changing the page counter. `lwarp` requires that the page counter not be adjusted during HTML output.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 13: [Troubleshooting](#).

## 7.11 Title page

In the preamble, place an additional block of code to set the following:

---

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
        Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

---

The title is used in the meta tags in the `HTML` files, unless overridden by `\HTMLTitle`, and the rest are used in `\maketitle`. To use a `\subtitle` or `\published` field, see section 66.8.

`\maketitle` Use `\maketitle` just after the `\begin{document}`, as this will establish the title of the homepage. Optionally, use a `titlepage` environment instead.

`Env titlepage` The `titlepage` environment may be used to hold a custom title page. The `titlepage` will be set in a `<div>` class `titlepage`, and `\printtitle`, etc. may be used inside this environment.

`Env titlingpage` Another form of custom title page, where `\maketitle` is allowed, and additional information may be included as well.

`\title {\langle title\rangle}`

⚠ **HTML corrupted** Avoid newlines in the `\title`; these will interfere with the file break and css detection.

⚠ **newlines** Use a `\subtitle` command instead (section 66.8). The title will appear in the document `\maketitle` as a heading `<h1>`. The `HTML` meta `title` tag will also have this title, unless `\HTMLTitle` is used to set the meta title to something else instead.

`\author {\langle author\rangle}`

In `\author`, `\protect` may be needed before some formatting commands. In `HTML`, the author will appear in a `<div>` of class `author` in the `\maketitle`. If the `titling` package is used, the author will also appear in a `HTML` meta tag, but `\HTMLAuthor` may be necessary to create a plain list of names if `\author` had affiliations added. `\affiliation` is a new addition to `lwarf`.

`\date {\langle date\rangle}`

`\date` works as expected. In `HTML`, this will appear in a `<div>` class `titledate`.

`\thanks {\langle text\rangle}`

`\thanks` are allowed in the `titlepage` fields, and will be rendered as `HTML` notes at the bottom of the title page.

## 7.12 HTML page meta descriptions

`\HTMLDescription {\langle A description of the web page.\rangle}`  
Default: (none)

**limitations** Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character (").

**placement** Use \HTMLDescription just before \begin{document} to set the description of the home page, and also just before each sectioning command such as \chapter or \section where a new file will be generated, depending on FileDepth. For example, if FileDepth is 1, use \HTMLDescription just before each \section command, and that description will be placed inside the HTML page for that \section. The same description will be used for all following HTML files as well, until reset by a new \HTMLDescription. It is best to use a unique description for each HTML file.

**disabling** To disable the generation of HTML description meta tags, use:

```
\HTMLDescription{}
```

## 7.13 HTML homepage meta title

\HTMLTitle {\langle title\rangle}

Default: \HTMLtitle{\thetitle}

Sets the contents of the web page <meta name="title"> element. May be set empty to cancel the meta title tag.

See section 7.6 for \HTMLTitleBeforeSection and \HTMLTitleAfterSection, used to set the title for HTML subpages.

## 7.14 HTML page meta author

\HTMLAuthor {\langle author\rangle}

Default: \HTMLAuthor{\theauthor}

Sets the contents of the web page <meta name="author"> element. May be set empty to cancel the meta author tag.

\author may be used to create a list of authors and their affiliations, in several formats if using authblk, and these may not successfully parse properly into a sensible list for \theauthor. \HTMLAuthor may be used to set the meta tag to a simple list of names.

## 8 Special cases and limitations

Some commonly-used L<sup>A</sup>T<sub>E</sub>X expressions should be modified as follows to allow for a smooth conversion to both HTML and print-formatted outputs.

Need help?

---

See the [General Index](#) for “how-to”, and the [Troubleshooting Index](#) if something doesn’t work. A [Troubleshooting](#) section is also available. The [Index of Objects](#) contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

---

### 8.1 Things to avoid

In the document, avoid the following:



options with braces

**Package options:** Package options may cause problems with l warp, especially if they include curly braces.

If selecting options with braces in \usepackage does not work:

```
\usepackage[font={it,small}]{caption}% does not work  
... try instead selecting the package options before loading l warp:  
 \PassOptionsToPackage{font={it,small}}{caption}  
 . . .  
 \usepackage{l warp}  
 . . .  
 \usepackage{caption}
```

... or try setting package options after the package has been loaded:

```
\usepackage{caption}  
 \captionsetup{font={it,small}}
```

**page counter:** Do not adjust the page counter. If doing so is required for the print version, place the adjustment inside a warpprint environment.

**Custom math environment macros:** Do not use expressions such as \beq as a replacement for \begin{equation}.

**Custom macros in section, figure, table names:** Custom macros which appear in sectioning commands or float captions then appear in the .toc, .lof, and .lot lists, and should be made robust using \newrobustcmd or \robustify from xetoolbox, xparse, etc.

When setting FileSectionNames to true to name the HTML files from the section names, the file names are created from sanitized versions of the chapter or section names, but the section names must be plain text or something which expands into plain text. Robust macros will not work at the sectioning level which is used for file names, but a robust macro or other complicated name may be used for the mandatory argument of \chapter, \section, etc., if a plain-text version is also included in the optional argument:

```
\chapter[Plain Name]{\ARobustMacro{Fancy Name}}
```

### 8.1.1 Invalid HTML

Additionally, some objects are valid L<sup>A</sup>T<sub>E</sub>X, but invalid HTML. An example is a tabular inside \textbf, since HTML does not allow a table inside a span. l warp will create the table, and the browser may support it, but the result is technically invalid.

## 8.2 Formatting

### 8.2.1 Text formatting

 **\bfseries, etc.** \textbf, etc. are supported, but \bfseries, etc. work only in some situations.

 **HTML special chars** &, <, and > have special meanings in HTML. If \&, \textless, and \textgreater are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

**program listings** For program listings, the listings package is supported, and its literate option is used to convert &, <, and > to proper HTML entities.

**verbatim** The various verbatim-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

### 8.2.2 Horizontal space

\hspace \hspace is converted to an inline HTML span of the given width, except that 0 width is ignored, a width of .16667em is converted to an HTML thin breakable space (U+2009), and a \fill is converted to a \quad.

\, \~ and \, are converted to HTML entities.

\kern \kern and \hskip are entered into the HTML PDF output as-is, then interpreted by \hskip *pdftotext*, and thus usually appear as a single space.

### 8.2.3 Text alignment

Use the environments center, flushright, flushleft instead of the macros \centering, \raggedright, \raggedleft.

 **figure & table alignment** \centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
...

```

### 8.2.4 Accents

Native L<sup>A</sup>T<sub>E</sub>X accents such as \" will work, but many more kinds of accents are available when using Unicode-aware X<sup>E</sup>L<sup>A</sup>T<sub>E</sub>X and LuaL<sup>A</sup>T<sub>E</sub>X.

### 8.2.5 textcomp package

Pkg textcomp Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

 **missing symbols** Many textcomp symbols are not supported by many system/browser fonts. In the css try referencing fonts which are more complete, but expect to see gaps in coverage.

### 8.2.6 Superscripts and other non-math uses of math mode

Use \textsuperscript{x} instead of \${}^x\$

### 8.2.7 Empty \item followed by a new line of text or a nested list:

lists Use a trailing backslash: \item[label] \\

### 8.2.8 Filenames and urls in lists or footnotes

filename underscore Escape underscores in the filenames:

```
\item[\href{file\_name.pdf}{text}]
```

### 8.2.9 relsize package

Pkg relsize For HTML, only the inline macros are supported: \textlarger, \textsmaller, and \textscale. Each becomes an inline span of a modified font-size.

\relsize, \larger, \smaller, and \relscale are ignored.

While creating SVG math for HTML, the original definitions are temporarily restored, and so should work as expected.

 **not small** The HTML browser's setting for minimum font size may limit how small the output will be displayed.

## 8.3 Boxes and minipages

### 8.3.1 Marginpars

\marginpar [⟨left⟩] {⟨right⟩} \marginpar may contain paragraphs, but in order to remain inline with the surrounding text l warp nullifies block-related macros inside the \marginpar. Paragraph breaks are converted to <br /> tags.

\marginparBlock [⟨left⟩] {⟨right⟩} To include block-related macros, use \marginparBlock, which takes the same arguments but creates a <div> instead of a <span>. A line break will occur in the text where the \marginBlock occurs.

### 8.3.2 Save Boxes

#### ⚠️ HTML corrupted

##### ⚠️ boxes

TEX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. l warp uses methods which help avoid this problem.

⚠️ minipage, \parbox \savebox and related do not (yet) support minipage or \parbox.

### 8.3.3 Minipages

#### ⚠️ inline

A line of text with an inline minipage or \parbox will have the minipage or \parbox placed onto its own line, because a paragraph is a block element and cannot be made inline-block.

#### placement

minipages and \parboxes will be placed side-by-side in HTML unless you place a \newline between them.

#### side-by-side

Side-by-side minipages may be separated by \quad, \quad, \enskip, \hspace, \hfill, or a \rule. When inside a center environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.

#### ⚠️ minipage in a span

There is limited support for minipages inside an HTML <span>. An HTML <div> cannot appear inside a <span>. While in a <span>, minipages, and \parboxes, and any enclosed lists have limited HTML tags, resulting in an “inline” format, without markup except for HTML breaks. Use \newline or \par for an HTML break.

#### ⚠️ minipage size

When using minipage, \parbox, and fminipage, a virtual 6 × 9 inch text area is used for \linewidth, \textwidth, and \textheight, both for sizing the minipage, and also for its contents.

#### if width is \linewidth

If a minipage or \parbox is assigned a width of exactly \linewidth, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

#### full-width if HTML

A new macro \minipagefullwidth requests that, during HTML output, the next single minipage or \parbox be generated without an HTML width attribute, allowing it to be

the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

- ⚠ **tabular, multicols** Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every `minipage` or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell `lwarp` to honor the specified widths of all following `minipages` and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell `lwarp` to ignore the specified widths.
- ⚠ **multicol** Inside a `multicols`, `\linewidth` is divided by the specified number of columns.
- ⚠ **text alignment** Nested `minipages` adopt their parent's text alignment in HTML, whereas in regular L<sup>A</sup>T<sub>E</sub>X PDF output they do not. Use a `flushleft` or similar environment in the child `minipage` to force a text alignment.

### 8.3.4 Side-by-side minipages

Place side-by-side minipages inside a `center` environment, with horizontal space between them, such as `\quad`, `\quad\quad`, `\hspace`, or `\hfill`. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

### 8.3.5 Framed minipages and other environments

`\fbox` can only be used around inline `<span>` items during HTML output, but HTML cannot place a block element such as a `<div>` for a minipage or a list inside of a `<span>`. Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

- `\fbox` For a framed object, options include:
- `\fboxBlock`
- `Env` `fminipage`
- To remove the frame in HTML output:** Place the `\fbox` command and its closing brace inside `warpprint` environments. This will nullify the frame for HTML output.
- To frame the contents inline with some formatting losses in HTML:** This is the default action of `\fbox` when enclosing a `minipage`. During HTML output, `\fbox` nullifies the HTML tags for `minipage`, `\parbox`, and lists. The contents are included as inline text inside the `\fbox`'s `<span>` of class `framebox`. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.
- To frame the contents on their own line with improved formatting in HTML:** A new command `\fboxBlock` is included, intended to be a direct replacement for `\fbox` for cases where the `\fbox` surrounds a `minipage`, `table`, or `list`. For print output, this behaves as `\fbox`. For HTML output, the contents are placed inside an HTML `<div>` with the class `framed`, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and minipages look nicer, and valid HTML is created for a

For inline `minipage` and `lists`:

tabular. While an \fbox containing a tabular is valid L<sup>A</sup>T<sub>E</sub>X code, the result in HTML is problematic since a table is a <div> not a <span>, so use \fboxBlock around a tabular, or else place the tabular inside a minipage, or use fminipage, described next. Also see below regarding the “Misplaced alignment tab character &.” error.

For display tabular,  
minipages, and lists:

**To create a framed minipage in both print and HTML:** A new environment fminipage is included. For print output, this is identical to minipage, except that it is also framed. For HTML output, this forms a <div> of class framed, the contents preserve their HTML formatting, and valid HTML is created for a tabular. Also see section 85 for a new environment fcolorminipage. Also see below regarding the “Misplaced alignment tab character &.” error.

colored boxes and frames:

**To create colored frames and boxes:** See section 552 for xcolor’s \colorbox and \fcolorbox, and l warp’s additional \colorboxBlock and \fcolorboxBlock.

**To frame tables or verbatim environments:** Place the contents inside a fminipage, or perhaps a \fboxBlock for a tabular. Also, if using \fboxblock with tabular, you will have to use \StartDefiningTabulars before the start of the macro which uses \fboxBlock and the tabular, and \StopDefiningTabulars afterwards. Also see the l warp documentation for the fancybox package.

**To frame equations:** See section 227 for the fancybox package.

**For fancy framed minipages:** See packages boxedminipage2e, shadow, fancybox, framed, mdframed.

**Custom environments:** Use a custom environment to create a sidebar, containing a BlockClass environment with custom css formatting, and \warpprintonly{\hrule} command:

---

```
\begin{BlockClass}{frameminipage}% ignored in print output
    % use \CSS\ to format div class framedminipage
    \warpprintonly{\hrule} % only appears in print output
    Contents
    \warpprintonly{\hrule} % only appears in print output
\end{BlockClass}
```

---

### 8.3.6 fancybox package

Pkg fancybox  
framed equation example

fancybox’s documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \latexitimage at the very start of FramedEqn’s beginning code, and \endlatexitimage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

---

```
\newenvironment{FramedEqn}
{
\latextimage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]}
\endlatextimage% NEW
}
```

**framing alternatives** \fbox works with **fancybox**. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

**framed table example** The **fancybox** documentation's example framed table using an \fbox containing a tabular does not work with lwarp, but the **FramedTable** environment does work if \fbox is replaced by \fboxBlock. This method loses HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

**⚠️ framed verbatim** lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The **fancybox** documentation's example **FramedVerb** may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
\VerbatimEnvironment
\fminipage{#1}
\begin{Verbatim}
\end{Verbatim}
\end{fminipage}
}
```

**framed \VerbBox** fancybox's \VerbBox may be used inside \fbox.

**indented alignment** LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

### 8.3.7 mdframed package

Pkg **mdframed** Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and

thickness, border radius, and shadow. CSS classes are created for `mdframed` environments and frame titles.

 **loading** When used, `l warp` loads `mdframed` in HTML with `framemethod=none`.

**font** For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the `mdframed` source). Since `l warp` does not support `\bfseries` and friends, only one font selection may be made at a time.

**theoremtitlefont** `theoremtitlefont` is not supported, since the following text is not in braces in the `mdframed` source.

**ignored options** `userdefinedwidth` and `align` are currently ignored.

**css classes** Environments created or encapsulated by `mdframed` are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class `|mdframedtitle|`. Subtitles are in a `<div>` of class `|mdframedsubtitle|`, and likewise for subsubtitles.

## 8.4 Section names

If using named HTML files, by selecting `\booltrue{FileSectionNames}`, the generated filenames may be simplified by using `\FilenameSimplify` and `\FilenameNullify`:

`\FilenameSimplify \{\langle text \rangle\}`

To remove common short words from the automatically-generated filenames, replacing each with a single hyphen “-”, use `\FilenameSimplify`:

```
\FilenameSimplify*{-in-}
\FilenameSimplify*{A-}
```

The first example removes the word “in” in the middle of a filename, and the second example removes “A” at the start of the filename. The star forces the arguments to be detokenized, which is required for a plain-text comparison. (The unstarred form is used for a token-sensitive comparison, which is seldom required by the user.) After simplification, repeated hyphen characters will be further simplified to a single hyphen “-”. Finally, single hyphens at the start or end of the filename are removed.

`\FilenameNullify \{\langle macros \rangle\}`

 **macros in section names** Macro names may appear in the automatically-generated file names. To remove these, create *non-robust* nullified versions of the macros, ensuring that each line ends with a

percent character % as shown below. These are placed inside \FilenameNullify, which adds them to the list of macros which are nullified during filename generation. Low-level macros such as \begingroup will cause problems when nullified. Many macros such as \textbf are already nullified. lwarp also already nullifies built-in symbol and textcomp macros, including if defined by xunicode, but not all xunicode macros. See the definition of \LWR@nullfonts for a complete list.

```
\FilenameNullify{%
  \renewcommand*{\macroname}[1]{#1}%
  \renewcommand*{\anothermacro}{}%
}
```

**⚠ duplicate filename** Avoid duplicate file names. Section names at levels which result in HTML file splits must be unique. lwarp will generate an error if a duplicate HTML filename is generated. Use the optional toc caption entry parameter for formatting. Remember to \protect \LaTeX commands which appear in section names and TOC captions.

**⚠ math in section names** If using named HTML files, in section names use paren math  $(x+y)$  instead of dollar math  $x+y$$ . (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use \texorpdfstring:

```
\section{A name with math
\texorpdfstring{$1+2=3$}{text description}}
```

## 8.5 Cross-references

**labels** Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).

**⚠ label characters** \nameref refers to the most recently-used section where the \label was defined. If no section has been defined before the \label, the link will be empty. Index entries also use \nameref and have the same limitation.

### 8.5.1 Page references

**⚠ \LaTeX page numbers** The printed page does not translate to the HTML page, so \pageref references are converted to parentheses containing \pagerefPageFor, which defaults to “see”, followed by a hyperlink to the appropriate object.

Ex:

\ref{sec:name} on page \pageref{sec:name}  
in HTML becomes:

“Sec. 1.23 on page (see sec. 1.23)”.

\pagerefPageFor may be redefined to “page for”, empty, etc. See page 483.

### 8.5.2 cleveref and varioref packages

Pkg cleveref cleveref and varioref are supported, but printed page numbers do not map to HTML,  
Pkg varioref

**⚠ cleveref page numbers**

so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

Ex:

```
\cpageref{tab:first,tab:second}
in html becomes:
“pages for table 4.1 and for table 4.2”
```

See `\cpagerefFor` at page 556 to redefine the message which is printed for page number references.

### 8.5.3 Hyperlinks, `hyperref`, and `url`

`Pkg hyperref` `lwarp` emulates `hyperref`, including the creation of active hyperlinks, but does not require that `hyperref` be loaded by the document.

`Pkg url` `lwarp` can also load `url`, but `url` should not be used at the same time as `hyperref`, since they both define the `\url` command. `lwarp` does not (yet) attempt to convert `url` links into hyperlinks during HTML output, nor does the print version of `url` create hyperlinks.

**⚠ comments between arguments** Do not place a comment with a % character between arguments for `\hyperref`, etc., as it is neutralized for inclusion in HTML URLs.

`lwarp` can also load `url`, but `url` should not be used at the same time as `hyperref`, since they both define the `\url` command. `lwarp` does not (yet) attempt to convert `url` links into hyperlinks during HTML output, nor does the print version of `url` create hyperlinks.

**⚠ `backref`** When generating HTML, `lwarp`’s emulation of `hyperref` does not automatically load `backref`, so `backref` must be loaded explicitly.

### 8.5.4 Footnotes and page notes

`lwarp` uses native L<sup>A</sup>T<sub>E</sub>X footnote code, although with its own `\box` to avoid the L<sup>A</sup>T<sub>E</sub>X output routine. The usual functions mostly work as-is.

**footnote numbering** To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For `bigfoot`, `manyfoot`, or `perpage`:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `\FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

**footmisc** The `footmisc` `stable` option is emulated by `lwarp`.

**⚠ sectioning commands** When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the `footmisc` package with the `stable` option, provide a short TOC entry, and `\protect` the `\footnote`:

---

```
\usepackage[stable]{footmisc}
...
\subsection[Subsection Name]
{Subsection Name\protect\footnote{A footnote.}}
```

**memoir with footmisc** **memoir**

If using **memoir** class, with which **lwarp** preloads **footmisc**, the **stable** option must be declared before **lwarp** is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
```

...

Do not use a starred sectioning command. As an alternative, it may be possible to adjust **\secnumdepth** instead.

**fancybox, fancyvrb** **\VerbatimFootnotes** **sectioning or displaymath**

If using **fancybox** or **fancyvrb** with **\VerbatimFootnotes**, and using footnotes in a sectioning command or display math, use **\footnotemark** and **\footnotetext**:

```
\subsection[Subsection Name]
{Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbatim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when **\VerbatimFootnotes** are selected. The browser usually compensates.

**pfnote** **pfnote numbers**

While emulating **pfnote**, **lwarp** is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. **lwarp** therefore uses continuous footnote numbering even for **pfnote**.

**bigfoot, manyfoot** **verbatim**

**Verbatim** footnotes are not yet supported.

If using the **bigfoot** package, and possibly also **manyfoot**, problems may occur with counter allocation because **lwarp** uses many counters, and there is a difference in how counters numbered 256 and up are handled in **pdfLATEX**. With **bigfoot** this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining **bigfoot** or **manyfoot** footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use **X<sub>EL</sub>LATEX** or **Lu<sub>EL</sub>LATEX** instead of **pdfLATEX**.

### 8.5.5 xr, xr-hyper, and xcite packages

See section 5.17.

## 8.6 Front and back matter

### 8.6.1 Custom classes with multiple authors and affiliations

Some classes allow multiple authors and affiliations. Often it is possible to emulate these using a standard class along with `authblk`:

```
%\documentclass{customclass} % for print document  
\documentclass{article} % for html document  
  
\usepackage{lwarp}  
\begin{warpHTML}  
\usepackage{authblk}  
\let\affiliation\affil % maybe required  
\end{warpHTML}
```

### 8.6.2 Starred chapters and sections

The following describes `\ForceHTMLPage` and `\ForceHTMLTOC`, which may be used for `endnotes`, `glossaries`, `tocbibind`, `bibliographies`, and the `index`. See the following sections where applicable. Continue here if interested in the reason for adding these commands to `lwarp`.

Some packages use `\chapter*` or `\section*` to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own HTML pages, and they are not given TOC entries.

`lwarp` provides a method to cause a starred section to be on its own HTML page, subject to `FileDepth`, and also a method to cause the starred section to have its own TOC entry during HTML output.

`\ForceHTMLPage` To place a starred section on its own HTML page, use `\ForceHTMLPage` just before the `\chapter*` or `\section*`. `lwarp` will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using `\phantomsection` and `\addcontentsline` works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created, or when creating an EPUB where the TOC entry will point to the page before the starred section. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is created.

`\ForceHTMLTOC` To automatically force the HTML version of the document to have a TOC entry for a starred section, use `\ForceHTMLTOC` just before the `\chapter*` or `\section*`, and place `\phantomsection` and `\addcontentsline` inside a `warpprint` environment.

For print output, `\ForceHTMLTOC` and `\ForceHTMLPage` have no effect.

 **inaccessible HTML page**

### 8.6.3 abstract package

Pkg abstract

⚠ missing TOC

If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

### 8.6.4 titling and authblk

Pkg titling

Pkg authblk

package support

⚠ load order

\published and \subtitle

lwarf supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

### 8.6.5 tocloft package

Opt[tocloft] titles

Pkg tocloft

Pkg tocloft

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its titles option, which tells tocloft to use standard L<sup>A</sup>T<sub>E</sub>X commands to create the titles, allowing other packages to work with it.

⚠ tocloft & other packages

### 8.6.6 appendix package

Pkg appendix

⚠ incorrect toc link

During HTML conversion, the option toc without the option page results in a toc link to whichever section was before the appendices environment. It is recommended to use both toc and also page at the same time.

### 8.6.7 pagenote package

Pkg pagenote

pagenote works as-is, but the page option is disabled.

### 8.6.8 endnotes package

Pkg endnotes

To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*\notesname{Endnotes} % optional
```

table of contents

HTML page

To additionally have the endnotes on their own HTML page, if FileDepth allows:

```
\ForceHTMLPage
\theendnotes
```

### 8.6.9 BibTeX

\etalchar Displays a superscript “+” to indicate “and others”.

- ⚠️ Modify \*.bib** When enough authors are cited for a source, BibTeX may use the \etalchar command to display a math superscript with a + character to indicate “and others”. Without modification, this will result in an “Improper \prevdepth” error. At present, l warp requires that \etalchar be replaced by a text superscript. To do so, add to the start of the .bib file the following:

```
@PREAMBLE{"\let\etalchar\relax \newcommand{\etalchar}[1]{\textsuperscript{#1}}"}
```

### 8.6.10 xcite package

See section 5.17.

### 8.6.11 gloss package

Pkg gloss To process the HTML glossary:

- ⚠️ compiling**      `bibtex <projectname>_html.gls`

### 8.6.12 glossaries package

Pkg glossaries  
**processing glossaries**  
 Opt GlossaryCmd  
 Default: `makeglossaries`

`l warp [l warpmk] printglossary`  
`l warp [l warpmk] htmlglossary`

*l warpmk* has the commands `l warpmk printglossary` and `l warpmk htmlglossary`, which process the glossaries created by the `glossaries` package using that package’s `makeglossaries` program.

The shell command to execute is set by the `l warp` option `GlossaryCmd`, which defaults to `makeglossaries`. The print or HTML glossary filename is appended to this command.

- ⚠️ makeglossaries not found** In some situations it may be required to modify the default command, such as to add the `perl` command in front:

```
\usepackage[  
    GlossaryCmd={perl makeglossaries},  
] {l warp}
```

*xindy* language To set the language to use for processing glossaries with *xindy*:

```
\usepackage[  
    GlossaryCmd={makeglossaries -L english},  
] {l warp}
```

Other options for `makeglossaries` may be set as well.

**placement and toc options** The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

**Numbered section, on its own HTML page:**

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
...
\printglossaries
```

**Unnumbered section, inline with the current HTML page:**

```
\usepackage[xindy,toc]{glossaries}
...
\printglossaries
```

**Unnumbered section, on its own HTML page:**

```
\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries
```

 **glossary style** The default `style=item` option for `glossaries` conflicts with `lwarp`, so the style is forced to `index` instead.

 **number list** The page number list in the printed form would become `\nameref`s in `HTML`, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

**print/HTML versions** The print and `HTML` versions of the glossary differ in their internal page numbers. Separate commands for generating print and `HTML` glossaries are used, even though the page number is currently ignored.

**8.6.13 nomencl package**

**Pkg** `nomencl` To process the `HTML` nomenclature:

```
makeindex <project>_html.nlo -s nomencl.list -o <project>_html.nls
```

**8.6.14 Indexing overview**

There are many ways to process indexes for a `LATEX` document, including native `LATEX` capabilities, a number of packages and classes, the possible availability of shell escape and `latexmk`, and the need to process print and `HTML` versions. `lwarp` attempts to provide easy recompilation of indexes along with the rest of the document, but the various indexing options must be set correctly. Numerous examples are given below. Some differ in minor details, so the important parts are highlighted in red, and options are in green.

Once set up properly, the entire document may be recompiled with `lwarpmk print` and `lwarpmk html`. In some cases, it will also be necessary to compile the indexes with `lwarpmk printindex` and `lwarpmk htmlindex`. A recompile may then be forced with `lwarpmk print1` and `lwarpmk html1`.

**manual processing** The user may continue to process indexes manually or by shell script without the use of `lwarpmk`, but adjustments will be required to process `HTML` indexes as well. In

general, \*.idx and \*.ind files will be accompanied by \*\_html.idx and \*\_html.ind files.

**custom index style** If using a custom indexing style file, see sections [8.6.20](#) and [8.6.21](#).

**source code** See section [76](#) for lwarf's core index and glossary code, section [298](#) for index, section [473](#) for splitidx, section [297](#) for imakeidx, section [512](#) for tocbibind, and section [572.17](#) for memoir's indexing patches.

### 8.6.15 Indexing with basic L<sup>A</sup>T<sub>E</sub>X and makeidx

**lwarpmk processing** The following allow the user to process indexes automatically, or using *lwarpmk*'s commands:

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

**For a single index using makeindex:**

```
\usepackage[makeindex,latexmk] {lwarf}
```

The usual .idx and .ind files will be used, along with the new lwarf.ist style file. When creating the HTML index, “\_html” is automatically appended to each of the names.

*lwarpmk* will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

**For a single index using xindy:**

```
\usepackage[
    xindy,
    xindyLanguage=english,                      <optional>
    xindyCodepage=utf8,                         <optional>
    latexmk                                         <optional>
]{lwarf}
```

The usual .idx and .ind files will be used, along with the new lwarf.xdy style file.

*lwarpmk* will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

### 8.6.16 Indexing with index

lwarf is told how to use *makeindex* using the PrintIndexCmd and HTMLIndexCmd options. The file lwarf.ist is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

#### For multiple indexes using *makeindex* and *index*:

(Assuming that the second index has file extensions .sist and .sind)

```
\usepackage[
    makeindex, latexmk,
    PrintIndexCmd={
        makeindex -s lwarf.ist <projectname>.idx ;
        makeindex -s lwarf.ist
        -o <projectname>.sind <projectname>.sidx
    },
    HTMLIndexCmd={
        makeindex -s lwarf.ist <projectname>_html.idx ;
        makeindex -s lwarf.ist
        -o <projectname>_html.sind <projectname>_html.sidx
    }
]{lwarf}
\usepackage{index}
...
\makeindex
\newindex{secondname}{sidx}{sind}{Second Index}
```

 **WINDOWS**

For Windows, replace the two “;” characters with “&”.

When creating the HTML index, “\_html” is automatically appended to the index filenames.

Use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

If the *latexmk* option is selected for lwarf, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

### 8.6.17 Indexing with splitidx

lwarf is told how to use *splitindex* using the PrintIndexCmd and HTMLIndexCmd options. The file lwarf.ist is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

If the *latexmk* option is selected for lwarf, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

 \thepage When using \AtWriteToIndex or \AtNextWriteToIndex, the user must not refer to

\thepage during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\lWR@new@label{\lWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 572.17 in the lwarf-patch-memoir package for the \@@wrspindexhyp macro as an example.

#### For multiple indexes using *makeindex* and *splitidx*:

```
\usepackage[
    makeindex, latexmk,
    PrintIndexCmd={
        splitindex <projectname> -- -s lwarf.ist
    },
    HTMLIndexCmd={
        splitindex <projectname>_html -- -s lwarf.ist
    }
]{lwarf}
\usepackage{splitidx}
...
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, “\_html” is automatically appended to each of the names.

Use

```
Enter ⇒ lwarfmk printindex
Enter ⇒ lwarfmk htmlindex
```

to compile the indexes.

**For multiple indexes using *xindy* and *splitidx*:**

```
\usepackage[
    xindy, latexmk,
    PrintIndexCmd={
        splitindex -m xindy <projectname> -- -M lwarp.xdy
        -L english -C utf8                                <optional>
    },
    HTMLIndexCmd={
        splitindex -m xindy <projectname>_html -- -M lwarp.xdy
        -L english -C utf8                                <optional>
    }
]{lwarp}
\usepackage{splitidx}
...
\makeindex
\newindex[Second Index]{secondname}
```

When creating the *HTML* index, “\_html” is automatically appended to each of the names.

Use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

### 8.6.18 Indexing with *imakeidx*

Due to the number of methods which may be used to process multiple indexes, the options for style file and *xindy* language and codepage must be specified in one of several different ways. These are described in detail later in this section, but are summarized here.

If shell escape is used, *imakeidx* will automatically compile the indexes by itself. Options specifying a custom style file and *xindy* language and codepage must be specified for each *\makeindex* command using its *options=* option, which must include *lwarp*'s special *lwarp.ist* or *lwarp.xdy* file, or a file based on them. If using a custom indexing style file, see sections 8.6.20 and 8.6.21. The *splitindex* option is also available if shell escape is used, in which case the *splitidx* package and *splitindex* program will also be used.

If shell escape is not possible, *latexmk* may be used to automatically compile the indexes. The style, language, and codepage options are specified with *lwarp*'s *makeindexStyle*, *xindyStyle*, *xindyLanguage*, and *xindyCodepage* options. These are passed to *latexmk* by *lwarpmk*'s *lwarpmk printindex* and *lwarpmk htmlindex* commands.

Where shell escape and *latexmk* are not possible, *lwarpmk* may be used to manually compile the indexes. *lwarp*'s *PrintIndexCmd* and *HTMLIndexCmd* options are used.

### For a single or multiple indexes using `makeindex` and `imakeidx`:

The index style `lwarf.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk]{lwarf}
\usepackage[makeindex]{imakeidx}
...
\makeindex[options={-s lwarf.ist}]
\makeindex[name=secondname,options={-s lwarf.ist}]
```

`imakeidx` will automatically compile the indexes. Shell escape is not required while using `makeindex`. `latexmk` may be specified, and if so it will be used for `lwarpmk print` and `lwarpmk html`, but `imakeidx` will actually create the indexes.

### For a single or multiple indexes using `makeindex` and `splitindex` with `imakeidx`:

The index style `lwarf.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk]{lwarf}
\usepackage[makeindex,splitindex]{imakeidx}
...
\makeindex[options={-s lwarf.ist}]
\makeindex[name=secondname,options={-s lwarf.ist}]
```

#### ⚠ enable shell escape

Shell escape is required while using `splitindex`. For the first compile, use

```
Enter ⇒ pdflatex --shell-escape projectname.tex
Enter ⇒ pdflatex --enable-write18 projectname.tex (MiKTeX)
```

or similar with `xelatex` or `lualatex`. `lwarf` will remember that shell escape was used.

`imakeidx` will automatically execute `splitindex`, and will also use `makeindex` to compile the indexes.

`latexmk` may be specified, and if so it will be used for `lwarpmk print` and `lwarpmk html`, but `imakeidx` will actually create the indexes.

### For multiple indexes using `xindy` and `imakeidx`, using shell escape:

Options may be given to `imakeidx`'s `\makeindex` command. The style file `lwarf.xdy` is automatically used for HTML output, and is not necessary for print output since the output will be similar. If language or codepage must be set, they should be specified as options for `\makeindex`, since `imakeidx` will process the indexes.

```
\usepackage[xindy,latexmk] {lwarp}
\usepackage[xindy,splitindex]{imakeidx}
...
\makeindex[
  options={ -M lwarp.xdy -L english -c utf8 }
]
\makeindex[
  name=secondname,
  options={ -M lwarp.xdy -L english -c utf8 }
]
```

⚠ enable shell escape

For the first compile, use

```
Enter ⇒ pdflatex --shell-escape projectname.tex
Enter ⇒ pdflatex --enable-write18 projectname.tex (MiKTeX)
```

or similar with *xelatex* or *lualatex*. *lwarp* will remember that shell escape was used.

*imakeidx* will automatically execute *splitindex* if selected, and will also use *xindy* to compile the indexes.

If selected, *latexmk* will automatically recompile the entire document as necessary.

**For indexes using *xindy* and *imakeidx*, without shell escape, but with *latexmk*:**

*lwarp*'s options are used, and are passed to *latexmk*.

```
\usepackage[
  xindy,
  xindyLanguage=english,                                <optional>
  xindyCodepage=utf8,                                 <optional>
  latexmk,
]{lwarp}
\usepackage[xindy]{imakeidx}
...
\makeindex
\makeindex[name=secondname]
```

*latexmk* will create the indexes automatically when **lwarpmk print** and **lwarpmk html** are executed.

**For indexes using *xindy* and *imakeidx*, without shell escape, and *without latexmk*:**

*lwarpmk* must be told how to create the indexes:

```
\usepackage[
    xindy,
    PrintIndexCmd={
        xindy -M lwarp.xdy -L english -C utf8
        <projectname>.idx ;
        xindy -M lwarp.xdy -L english -C utf8
        secondname.idx
    },
    HTMLIndexCmd={
        xindy -M lwarp.xdy -L english -C utf8
        <projectname>_html.idx ;
        xindy -M lwarp.xdy -L english -C utf8
        secondname_html.idx
    }
]{lwarp}
\usepackage[xindy]{imakeidx}
...
\makeindex
\makeindex[name=secondname]
```

### ⚠ WINDOWS

For Windows, replace the two “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name\_html.idx.

Use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

### 8.6.19 Indexes with memoir

**For a single index with *memoir* and *makeindex*:**

```
\documentclass{memoir}
\usepackage[makeindex, latexmk]{lwarp}
...
\makeindex
```

The usual .idx and .ind files will be used, along with the *lwarp.ist* style file.

*lwarpmk* will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

**For multiple indexes with memoir and makeindex, using *latexmk*:**

*lwarp*'s options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[makeindex, latexmk]{lwarp}
...
\makeindex
\makeindex[secondname]
```

*lwarpmk* will use *latexmk* to create the indexes automatically when the user executes **lwarpmk print** and **lwarpmk html**.

**For multiple indexes with memoir and makeindex, without *latexmk*:**

*lwarpmk* must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  makeindex,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist secondname.idx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist secondname_html.idx
  }
]{lwarp}
...
\makeindex
\makeindex[secondname]
```



WINDOWS

For Windows, replace the two ";" characters with "&".

<projectname> is the \jobname: if compiling "name.tex", use the filenames name.idx and name\_html.idx.

Use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

**For a single index with memoir and xindy:**

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                                <optional>
    xindyCodepage=utf8,                                 <optional>
    latexmk                                              <optional>
]{lwarp}
...
\xindyindex
\makeindex
```

The usual .idx and .ind files will be used, along with the `lwarp.xdy` style file.

`lwarpmk` will use `latexmk` if specified, in which case `latexmk` will create the index automatically. Otherwise, use

```
Enter ⇒ lwarpmk printindex
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

**For multiple indexes with memoir and xindy, using latexmk:**

`lwarp`'s options are used, and are passed to `latexmk`.

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                                <optional>
    xindyCodepage=utf8,                                 <optional>
    latexmk
]{lwarp}
...
\xindyindex
\makeindex
\makeindex[secondname]
```

`lwarpmk` will use `latexmk` to create the indexes automatically.

### For multiple indexes with memoir and xindy, *without latexmk*:

*lwarpmk* must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
    xindy,
    PrintIndexCmd={
        xindy -M l warp.xdy -L english -C utf8
        <projectname>.idx ;
        xindy -M l warp.xdy -L english -C utf8
        secondname.idx
    },
    HTMLIndexCmd={
        xindy -M l warp.xdy -L english -C utf8
        <projectname>_html.idx ;
        xindy -M l warp.xdy -L english -C utf8
        secondname_html.idx
    }
]{l warp}
...
\xindyindex
\makeindex
\makeindex[secondname]
```

#### ⚠ WINDOWS

For Windows, replace the four “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name\_html.idx.

Use

```
Enter ⇒ l warpmk printindex
Enter ⇒ l warpmk htmlindex
```

to compile the indexes.

### 8.6.20 Using a custom *makeindex* style file

Prog makeindex When using *makeindex*, *lwarpmk* uses the file *l warp.ist* to process the index. This file is over-written by *l warp* whenever a print version of the document is processed.  
File *l warp.ist*

To use a custom *makeindex* style file:

1. Copy *l warp.ist* to a new filename such as *projectname.ist*
2. Make changes to *projectname.ist*. Keep the lines which refer to \hyperindexref. These lines creates the hyperlinks for the HTML index. During print output \hyperindexref becomes a null function.
3. In the document source use the *makeindexStyle* option for *l warp*:

```
\usepackage[
    ... other options ...
    \textred{makeindexStyle=projectname.ist},
]{l warp}
```

Opt *makeindexStyle*

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

- Recompile the print version, which causes `lwarp` to rewrite the `lwarpmk.conf` configuration file. This tells `lwarpmk` to use the custom `projectname.ist` file instead of `lwarp.ist`.

### 8.6.21 Using a custom *xindy* style file

**Prog** `xindy` When using *xindy*, `lwarpmk` uses the file `lwarp.xdy` to process the index. This file is over-written by `lwarp` whenever a print version of the document is processed.  
**File** `lwarp.xdy`

To use a custom *xindy* style file:

- Copy `lwarp.xdy` to a new filename such as `projectname.xdy`
- Make changes to `projectname.xdy`.

Keep the lines which refer to `\hyperindexref`:

```
(define-attributes ((hyperindexref)))
(markup-locref :open "\hyperindexref{" :close "}")
...
(markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
```

These lines create the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

To create custom styles, refer to the lines for `\textbf` and `\textit`.

**Opt** `xindyStyle` 3. In the document source use the `xindyStyle` option for `lwarp`:

```
\usepackage[
    ... other options ...
    \textred{xindyStyle=projectname.xdy},
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

- Recompile the print version, which causes `lwarp` to rewrite the `lwarpmk.conf` configuration file. This tells `lwarpmk` to use the custom `projectname.xdy` file instead of `lwarp.xdy`.

### 8.6.22 Additional indexing limitations

**⚠ xindy with hyperref** *xindy* and `hyperref` may not work well together for print output with “see”, “see also”, reference ranges, or stylized index references. It may be necessary to turn off hyper-referencing for indexes:

```
\usepackage[hyperindex=false]{hyperref}
```

**⚠ empty index** If an HTML index is empty, it may be necessary to add the following before `lwarp` is

loaded:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
...
\usepackage{lwarf}
```

**makeindex** custom display styles When using *makeindex*, custom display styles are possible:

```
\begin{warpprint}
\newcommand{\notesstyle}[1]{#1nn}
\end{warpprint}

\begin{warpHTML}
\makeatletter
\newcommand{\notesstyle}[1]{\LWR@doindexentry{#1} notes }
\makeatother
\end{warpHTML}
...
A sentence.\index{key|notesstyle}
```

**xindy** custom display styles For custom styles with *xindy*, see *lwarf.xdy* for \textbf and \textit as examples.

### 8.6.23 Index positions, toc, tocbibind

**placement and toc options** An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual toc entry:**

A commonly-used method to introduce an index in a L<sup>A</sup>T<sub>E</sub>X document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual toc entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic toc entry:**

The *tocbibind* package may be used to automatically place an entry in the toc.

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg `tocbibind` **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

`Opt [tocbibind] numindex numbered index section` Use the `tocbibind numindex` option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as `imakeidx`, may also have options for including the index in the Table of Contents.

Pkg `tocloft` If using `tocloft` with `tocbibind`, `anonchap`, `fncychap`, or other packages which change chapter title formatting, load `tocloft` with its `titles` option, which tells `tocloft` to use standard L<sup>A</sup>T<sub>E</sub>X commands to create the titles, allowing other packages to work with it.

⚠ **tocloft & other packages**

## 8.7 Math

### 8.7.1 Math in section names

⚠ **math in section names** If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
\texorpdfstring{$1+2=3$}{text description}}
```

### 8.7.2 Rendering tradeoffs

**Math rendering** Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.

**SVG files** Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

**SVG inline** The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

**PNG files** Others L<sup>A</sup>T<sub>E</sub>X-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

<b>MathML</b>	Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 10 regarding EPUB output with MATHJAX.
---------------	---

### 8.7.3 svg option

<b>SVG math option</b>	For SVG math, math is rendered as usual by LATEX into the initial PDF file using the current font <sup>14</sup> , then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LATEX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML alt attribute carries the LATEX code which generated the math, allowing copy/paste of the LATEX math expression into other documents.
------------------------	--

<b>SVG image font size</b>	For the lateximage environment, the size of the math and text used in the SVG image may be adjusted by setting \LateximageFontSizeName to a font size name— <i>without the backslash</i> , which defaults to:
----------------------------	---

\renewcommand{\LateximageFontSizeName}{\normalsize}

For inline SVG math, font size is instead controlled by \LateximageFontSizeScale, which defaults to:

\newcommand\*{\LateximageFontSizeScale}{.75}

<b>SVG math copy/paste</b>	For SVG math, text copy/paste from the HTML <alt> tags lists the equation number or tag for single equations, along with the LATEX code for the math expression. For AMS environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred AMS environment, although the \tag macro will still appear inside the LATEX math expression.
----------------------------	---

<b>⚠ SVG math in TeX boxes</b>	SVG math does not work inside TeX boxes, since a \newpage is required before and after each image.
--------------------------------	--

### 8.7.4 MATHJAX option

<b>MATHJAX math option</b>	The popular MATHJAX alternative ( <a href="http://mathjax.org">mathjax.org</a> ) may be used to display math.
----------------------------	---

Prog MathJax When MATHJAX is enabled, math is rendered twice:

1. As regular LATEX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LATEX, and
2. As detokenized printed LATEX commands placed directly into the HTML output for interpretation by the MATHJAX display scripts. An additional script is used to pre-set the equation number format and value according to the current LATEX

<sup>14</sup>See section 557 regarding fonts and fractions.

values, and the MATHJAX cross-referencing system is ignored in favor of the L<sup>A</sup>T<sub>E</sub>X internal system, seamlessly integrating with the rest of the L<sup>A</sup>T<sub>E</sub>X code.

### 8.7.5 Customizing MATHJAX

**global customizations** MATHJAX does not have preexisting support every possible math function. Additional MATHJAX function definitions may be defined in the preamble. These will be declared at the start of each HTML page, and thus will have a global effect across all HTML pages.

Examples:

```
\begin{warpMathJax}
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arcsinh}{\text{arcsinh}}}
\CustomizeMathJax{\newcommand{\arccosh}{\text{arccosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
\end{warpMathJax}
```

**⚠ slow compilation** To avoid a slowdown in compile speed, use the `warpMathJax` environment to prevent its contents from being processed in print or SVG math output. Also, place each new definition inside its own `\CustomizeMathJax`. A warning to this effect is issued if an overly-long definition is attempted.

l warp already provides MATHJAX customizations for some packages.

**siunitx** When using siunitx, a similar process may be used to add custom units:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\myunit}{\mathrm{WXYZ}}}
\CustomizeMathJax{\newcommand{\umyunit}{\mathrm{\mu\myunit}}}
\end{warpMathJax}
```

**advanced control** For more advanced control over dynamically creating custom definitions, see as an example the l warp definition for `\DeclarePairedDelimiterX`, in section 337, mathtools.

**local customizations** For customizations local to the current HTML page only, macros may be defined as follows:

```
\begin{warpMathJax}
\(\newcommand{\macroname}{...} \)
\(\newcommand{\anothername}{...} \)
\end{warpMathJax}
```

To maintain compile speed, use the `warpMathJax` environment, and use a separate math environment for each definition.

**⚠ starred macros** Starred macros are generally not supported by MathJax or the l warp emulations.

### 8.7.6 MATHJAX limitations

#### MATHJAX limitations

Prog MathJax

⚠ \multicolumn, multirow

⚠ subequations

⚠ footnotes in math

⚠ references in math

#### latextimage

- MATHJAX does not support `\multicolumn` or `multirow`. These may be used in text tabulars or SVG math, but in MATHJAX math arrays they are emulated. `\multicolumn` only fills a single cell, resulting in a short row. `\multirow` simply prints its text on the first line.

- MATHJAX does not support subequations. This may be improved by parsing the L<sup>E</sup>T<sub>E</sub>X math expression to manually insert tags, but this has not yet been done.

- Footnotes inside equations are not yet supported while using MATHJAX. l warp provides a basic emulation for MATHJAX.

- Inside a MATHJAX expression, references to equations work within the same HTML web page, but do not work when referring to an equation in a different HTML web page. Outside of a MATHJAX expression, in the text body, references work as expected.

- Math appearing inside a latextimage, and therefore also inside a Tikz or picture environment, is rendered as SVG math even if MATHJAX is used in the rest of the document.

- For siunitx, see [siunitx package](#), section 8.7.12.

- For physics, see [physics package](#), section 8.7.14.

- A tabbing environment is emulated using an HTML `<pre>`. While MATHJAX is enabled inside tabbing, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

- Other math-related macros and packages are not directly supported by MATHJAX, including `\ensuremath` and `bigdelim`, and occasionally-used macros such as `\relax`. While using MATHJAX, l warp provides emulation for footnotes, bm, mathtools, nicefrac, siunitx, and units.

- Starred macros are generally not supported by MathJax or the l warp emulations.

### 8.7.7 Catcode changes

#### preamble macros with math

The math shift character \$ is not set for HTML output until after the preamble. Macros defined in the preamble which contain \$ must be enclosed between `\StartDefiningMath` and `\StopDefiningMath` to temporarily change to the HTML meaning of \$:

```
\StartDefiningMath
\newcommand{...}
\StopDefiningMath
```

As an alternative, use `\(` and `\)` instead of \$, in which case `\StartDefiningMath` and `\StopDefiningMath` are not necessary.

If a package defines macros using \$, it may be necessary to use `\StartDefiningMath` and `\StopDefiningMath` before and after loading the package.

### 8.7.8 Complicated inline math objects

\inlinemathnormal \inlinemathother changing contents complicated alt tag	An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as $x+1$ , so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an alt tag. The macro \inlinemathother may be used before a dynamic math expression, and \inlinemathnormal after. Doing so tells lwarp to use an unhashed SVG math image, even if MathJax is in use. See section 44.
---	--

### 8.7.9 Complicated display math objects

\displaymathnormal MathJax unsupported complicated alt tag	By default, or when selecting \displaymathnormal, MATHJAX math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Tikz pictures, compilation will fail.
\displaymathother MathJax unsupported complicated alt tag	When selecting \displaymathother, it is assumed that the contents are more complicated than “pure” math. An example is an elaborate Tikz picture, which will not render in MATHJAX and will not make sense as an HTML alt tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Tikz pictures are more likely to compile successfully.

### 8.7.10 ntheorem package

Pkg ntheorem ⚠ Font control	This conversion is not total. Font control is via css, and the custom LATEX font settings are ignored.
⚠ Equation numbering	ntheorem has a bug with equation numbering in AMS environments when the option thref is used. lwarp does not share this bug, so equations with \split, etc, are numbered correctly with lwarp’s HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem’s thref option.

### 8.7.11 mathtools package

Pkg mathtools ⚠ equation numbering ⚠ italic correction	showonlyrefs is disabled, as it conflicts with cleveref, which is used by lwarp. Equation numbers may not match the print version. mathic is not emulated for HTML.
⚠ MATHJAX	If using MATHJAX:

- Starred macros are not available. Starred environments do work.
- `mathtools disallowspaces` does not work for MATHJAX. Protect brackets which are not optional arguments, such as:
 

```
\begin{gathered}{}\\ [p]=1 . . . \\ \end{gathered}
```
- `showonlyrefs` does not work in MATHJAX, and will result in a difference in equation numbering compared to the print version.
- Due to MATHJAX limitations, the following do not render well: `\overbracket`, `\underbracket`, `\overbrace`, `\underbrace`, `rcases`, `drcases`, `\Aboxed`, and `\ArrowBetweenLines`.
- For the new cases-like environments, `\text` must be used to set the normal roman font if desired.
- `alignat` in MATHJAX requires math mode, but in LATEXit doesn't. It may be required to use `warpHTML` and `warpprint` to isolate a version for each mode.
- `\DeclareParedDelimiter` and related must be in the preamble before `\begin{document}`. The starred versions of each macro are not created.

### 8.7.12 siunitx package

Pkg    `siunitx`    Due to `pdftotext` limitations, fraction output is replaced by symbol output for per-mode and quotient-mode.

⚠ **math mode required** Some units will require that the expression be placed inside math mode.

⚠ **tabular** Tabular S columns are rendered as simple c columns, and tabular s columns are not supported. These may be replaced by c columns with each cell contained in `\num` or `\si`.

⚠ **MathJax** For math mode with SVG display, the original `siunitx` code is used while generating the SVG image. For text mode, `lwarp` uses an emulation which provides a very effective HTML interpretation of `siunitx`. For math expressions while using MATHJAX, a limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. `siunitx` macros with more than one optional value cannot absorb the second optional value, and complicated parsing such as for `\ang` is not supported. The result usually looks fine, and otherwise is enough to get the meaning across.

`lwarp`'s MATHJAX emulation for `siunitx` is meant to be a stop-gap measure until an extension is included in MATHJAX. As of this writing, the third-party `siunitx` extension for MATHJAX is not currently hosted at any public CDN, thus `siunitx` is not usable with this extension unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJAX script, but `lwarp`'s emulation would have to be disabled as well.

Document modifications required for MATHJAX:

- custom units**
- Custom units may be added with `\CustomizeMathJax`. See the `lwarp-siunitx` code for examples.

- ⚠ `unit spacing`
  - Units work better using `~` between units instead of using periods.
- ⚠ `\square, \cubic`
  - To square or cube compound units, enclose the following compound units in braces:

`\cubic{\centi\meter}`

Single units do not require braces.

Also see [MATHJAX option](#), section [8.7.4](#).

### 8.7.13 units and nicefrac packages

Pkg    `units`    `units` and `nicefrac` work with `l warp`, but MATHJAX does not have an extension for `units` or `nicefrac`. These packages do work with `l warp`'s option `svgmath`.

### 8.7.14 physics package

Pkg    `physics`    `physics` works as-is for HTML with SVG math.

For MATHJAX, emulation is provided via MATHJAX macros. These are not the same as the third-party MATHJAX extension.

- The `notrig` option is honored.
- ⚠ • Starred macros are not yet detected.
- ⚠ • Most macros don't work with `\big`, etc.
- ⚠ • Macros do not auto-detect variable numbers of mandatory arguments. Provide empty {} arguments for those which are not used.
- ⚠ • Many of the macros do not work with auto-detected delimiters. Use the delimiter-specific versions instead. Some macros do not even consider the following arguments, so they may work as expected.
- ⚠ • For `\Re` and `\Im`, the arguments must be in braces.
- ⚠ • For `\functionalderivative`, for the example in the manual with  $(E - TS)$ , enclose the parens in braces.
- ⚠ • `\expectationvalue` requires and uses two mandatory arguments, unlike the third-party MATHJAX `physics` extension.
- Each of `\matrixquantity`, `\smallmatrixquantity`, and `\matrixdeterminant` work, while `\identitymatrix` and the following simply print a place-holder, and must be replaced by hand.

### 8.7.15 newtxmath package

Pkg newtxmath The proper load order is:

 loading sequence

```
...
\usepackage{lwarp}
...
\usepackage{amsthm}
\usepackage{newtxmath}
...
```

## 8.8 Graphics

Pkg graphics Avoid using the `\includegraphics scale` option. Change:

Pkg graphicx  scale

to:

```
\includegraphics[width=<yy>\linewidth]{...}
```

 \includegraphics file formats For `\includegraphics` with .pdf or .eps files, the user must provide a .pdf or .eps image file for use in print mode, and also a .svg, .png, or .jpg version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, `lwarp` will automatically choose the .pdf or .eps format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf or .eps image is referred to with its file extension, the extension will be changed to .svg for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo To convert a PDF image to SVG, use the utility `pdftocairo`:

 PDF to SVG

Enter ⇒ `pdftocairo -svg filename.pdf`

Prog lwarpmk pdftosvg For a large number of images, use `lwarpmk`:

Enter ⇒ `lwarpmk pdftosvg *.pdf` (or a list of filenames)

Prog lwarpmk epstopdf For EPS images converted to PDF using the package `epstopdf`, use

 `epstopdf` package

Enter ⇒ `lwarpmk pdftosvg *.PDF`

to convert to SVG images.

 DVI latex When using DVI `latex`, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ `lwarpmk epstopdf *.eps` (or a list of filenames)

---

Enter ⇒ **lwarfmk pdftosvg \*.pdf     (or a list of filenames)**

**PNG and JPG** For PNG or JPG while using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

**GIF** GIF files may be used for HTML, but another format must also be provided for print output.

**file extension priorities** If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

**⚠ graphics vs. graphicx** If using the older *graphics* syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer *graphicx* syntax. Note that viewports are not supported by *lwarf*—the entire image will be shown.



### viewport



### viewport units

For `\includegraphics`, avoid px and % units for width and height, or enclose them inside *warpHTML* environments. For font-proportional image sizes, use ex or em. For fixed-sized images, use cm, mm, in, pt, or pc. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

**options** `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys.

**HTML class** With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

**HTML alt tags** Likewise, the `\includegraphics alt` key adds an HTML alt tag to an image, and is ignored for print output. If not assigned, each image is given an alt tag according to `\ImageAltText`.

**\rotatebox** `\rotatebox` accepts the optional `origin` key.

**⚠ browser support** `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The css3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LATEX, so expect some ugly results for scaling and rotating.

## 8.8.1 tikz package

**Pkg tikz** If using display math with `tikzpicture` or `\tikz`, along with matrices with the & character, the document must be modified as follows:

**⚠ displaymath and matrices**

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of & in the tikz expression must be replaced with \&.

### 8.8.2 grffile package

Pkg grffile

**⚠ matching PDF and SVG** grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

### 8.8.3 color package

Pkg color

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

### 8.8.4 xcolor package

Pkg xcolor

\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a <div> instead of a <span>. These <div>s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none

\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes required.

colored tables

\rowcolors is supported, except that the optional argument is ignored so far.

colored text and boxes

\textcolor, \colorbox, and \fcolorbox are supported.

\color and \pagecolor

\color and \pagecolor are ignored. Use css or \textcolor where possible.

### 8.8.5 epstopdf package

Pkg epstopdf

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

### 8.8.6 pstricks package

Pkg pstricks

All pstricks content should be contained inside a pspicture environment.

**⚠ use pspicture**

### 8.8.7 pdftricks package

Pkg pdftricks

⚠ convert image files

The pdftricks image files <jobname>-fig\*.pdf must be converted to .svg, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **l warpmk pdftosvg <jobname>-fig\*.pdf**

### 8.8.8 psfrag package

Pkg psfrag

⚠ use psfrags

The psfrags environment is modified to use `\teximage` to encapsulate the image. Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by l warp.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

### 8.8.9 pstool package

Pkg pstool \graphicspath is ignored, and the file directory must be stated.

⚠ path and filename The filename must not have a file extension.

Use

Enter ⇒ **l warpmk html**

followed by

Enter ⇒ **l warpmk limages**

### 8.8.10 asymptote package

Pkg asymptote To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

### 8.8.11 overpic package

Pkg overpic The macros `\overpic[fontsize]` and `\overpic[fontskip]` are used during HTML generation. These are sent to `\fontsize` to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the `overpic` and Overpic environments.



#### scaling

### 8.8.12 Multimedia packages

Pkg multimedia The packages `multimedia`, `movie15`, and `media9` are supported.

Pkg movie15

HTML5 `<audio>` and `<video>` objects are created for `.mp3` and `.mp4` files.

Pkg media9

HTML5 `<embed>` objects are created for `http` and `ftp` links.

`\href` links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For `media9`, a multimedia object is inserted for each `addresource=`, as well as each `flashvars source=` and `src=`. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside `\warpprintonly` or the `warpprint` environment.

Each HTML multimedia object includes the poster text, except for `<embed>` objects. For `movie15`, the `text` option is supported to specify the poster text.

The `width`, `height`, and `totalheight` options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

`media9 \addmediapath` is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each `<audio>` and `<video>` object.

`media9` slideshows are not supported.

`\hyperlink{movie}`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YouTube™ video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

## 8.9 Tabbing

The tabbing environment works, except that `svg` math and `latexitimages` do not yet work inside the environment.

 **math in tabbing** If math is used inside tabbing, place tabbing inside a `latexitimage` environment, which will render the entire environment as a single `svg` image.

## 8.10 Tabular

### 8.10.1 tabular environment

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, `siunitx` S columns, or the packages `multirow`, `longtable`, `supertabular`, or `xtab`.

#### Defining macros and environments:

 **Misplaced alignment  
tab character &**

- When defining environments or macros which include `tabular` and instances of the `&` character, it may be necessary to make `&` active before the environment or macro is defined, then restore `&` to its default catcode after, using the following commands. These are ignored in print mode.

`\StartDefiningTabulars`

`<define macros or environments using tabular and & here>`

`\StopDefiningTabulars`

 **floatrow**

This includes before and after defining any macro which used `\ttabbox` from `floatrow`.

 **tabular inside another  
environment**

- When creating a new environment which contains a `tabular` environment, `lwarp`'s emulation of the `tabular` does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a
definition
\newenvironment{outerenvironment}
{
\begin{tabular}{cc}
left & right \\
\end{tabular}
}
\TabularMacro\ResumeTabular
left & right \\
\end{tabular}
}
\StopDefiningTabulars
```

**Cell contents:****⚠ macro in a table**

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

\TabularMacro\somemacro & more row contents \\

**Column specifiers:****@ and !**

- Only one each of @ and ! is used at each column, and they are used in that order.

**\multirow**

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

**⚠ \newcolumntype**

- \newcolumntype is ignored; unknown column types are set to l.

**Rules:****vertical rules**

- Doubled \hlines, \midrules, and vertical rules are supported.
- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

**width and trim**

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

**combined rules**

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

\cmidrule{2-3} \\[-2ex]

\bottomrule

The optional -2ex is ignored in HTML, but improves the visual formatting in the print output.

- For \toprule and \bottomrule, when combined with a \warpprint or \warppHTML environment, if a “Misplaced \noalign” error occurs, change

This & That \endhead

to

\warpprintonly{This & That \endhead}

**⚠ \warpprintonly****⚠ Misplaced \noalign**

and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevant to HTML output.

#### Other:

- `tabularx` ignores the width, but X columns do produce paragraph columns or multicolumns.

#### longtable headings

##### ⚠ S columns

- For `longtable`, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.
- For S columns (from the `siunitx` package), while producing print output, anything non-numeric must be placed inside {} braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by `lwarp`'s tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

- In L<sup>A</sup>T<sub>E</sub>X, a `tabular` may be placed inside a `minipage`, but in HTML a `<table>` may not be inside a `<span>`. If this situation is detected, a warning is printed instructing the user to isolate the `<span>` using `\warpprintonly` or the `warpprint` environment.

#### 8.10.2 multirow package

#### vposn

- Note that recent versions of `multirow` include a new optional `vposn` argument.

#### multirow cells

- For `multirow`, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
... & \multirow{2}{.5in}{text} & ...
... & \mrowcell & ...
```

#### colored cells

- The `multirow` documentation regarding colored cells recommends using a negative number of rows. This will not work with `lwarp`, so `\warpprintonly` and `\warpHTMLonly` must be used to make versions for print and HTML.

- See section 359.2 for `\multicolumnrow`.

`lwarp` does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0][1in][0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines, `\mcolrowcell` must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

#### with \multicolumn

##### ⚠ \multicolumn & \multirow

##### ⚠ skipped cells

##### ⚠ empty cells

---

```
    . . . & \multicolumn{2}{c}{\multirow{3}{*}{\begin{array}{|c|c|} \hline 0pt \\ \hline \end{array}}}
```

```
    . . . & \mcolrowcell & \mcolrowcell & . . .
    . . . & \mcolrowcell & \mcolrowcell & . . .
```

**⚠ MathJax**

- MATHJAX does not support `multirow`, so it is emulated to only print its text on the first row. `\multirow` works as expected in text tabulars or SVG math.

**8.10.3 longtable package**

**Pkg** `longtable` Use one of either `\endhead` or `\endfirsthead` for both print and HTML, and use a `\warpprintonly` macro to disable the other head phrase, and also the `\endfoot` and `\endfirstfoot` phrases. (See section 8.10.4 if using `threeparttablex`.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[ . . . ] \endhead % or \endfirsthead
[ . . . ] \endfoot
[ <lastfoot macros> ] \endlastfoot
}
. . . table contents . .
\warpHTMLonly{
[ <lastfoot macros> ] % HTML last footer, without \endfoot
% or \endlastfoot.
}
\end{longtable}
```

**⚠ Misplaced \noalign**

Use the `\warpprintonly` macro instead of the `warpprint` environment. Doing so helps avoid “Misplaced `\noalign`” when using `\begin{warpprint}`.

**⚠ \kill**

`\kill` is ignored, place a `\kill` line inside

```
\begin{warpprint} . . . \end{warpprint}
```

or place it inside `\warpprintonly`.

**⚠ lateximage**

`longtable` is not supported inside a `lateximage`.

**8.10.4 threeparttablex package**

**Pkg** `threeparttablex` `threeparttablex` is used with `longtable` and `booktabs` as follows:

---

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
[ . . . ] \endhead     % or \endfirsthead
[ . . . ] \endfoot
\bottomrule \insertTableNotes \endlastfoot
}
... table contents ...
\warpHTMLonly{           % HTML last footer
\bottomrule
\UseMinipageWidths      % optional
\insertTableNotes
\endlastfoot
}
\end{longtable}
```

**table width** The table notes are created using a `\multicolumn`. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarf guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use `\UseMinipageWidths` before `\insertTableNotes`. The width is then specified, and in many cases the result is an improvement in overall table layout.

### 8.10.5 supertabular and xtab packages

Pkg supertabular For `\tablefirsthead`, etc., enclose them as follows:

Pkg xtab

⚠ Misplaced alignment tab character &

```
\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a `lateximage`.

### 8.10.6 colortbl package

Pkg colortbl Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.

⚠ row/cell color colortbl ignores the overhang arguments.

### 8.10.7 ctable package

⚠ Misplaced alignment tab character & Use `\StartDefiningTabulars` before one or more `\ctables`, and `\StopDefiningTabulars` after. These change the meaning of the ampersand & character.

### 8.10.8 bigdelim package

Pkg bigdelim \ldelim and \rdelim use \multirow, so \mrowcell must be used in the proper number of empty cells in the same column below \ldelim or \rdelim, but not in cells which are above or below the delimiter:

---

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

---

<->	a    b			
left {	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="padding-right: 10px;">c    d</td></tr> <tr><td style="padding-right: 10px;">e    f</td></tr> <tr><td style="padding-right: 10px;">g    h</td></tr> </table>	c    d	e    f	g    h
c    d				
e    f				
g    h				
<->	i    j			

---

For MATHJAX, limited emulation is provided which merely prints the delimiter and optional text in the first row.

## 8.11 Floats

### 8.11.1 Float contents alignment

⚠ figure & table alignment \centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
...
```

### 8.11.2 float, trivfloat, and/or algorithmicx together

Pkg float If using \newfloat, trivfloat, and/or algorithmicx together, see section 523.1.

Pkg trivfloat

Pkg algorithmicx

⚠ package conflicts

Pkg caption

Package options may cause problems with lwrap, especially if they include curly braces.

Pkg subcaption

If selecting options with braces in \usepackage does not work:

---

```
\usepackage[font={it,small}]{caption}% does not work
```

... try instead selecting the package options before loading lwrap:

```
\PassOptionsToPackage{font={it,small}}{caption}
...
\usepackage{lwrap}
...
\usepackage{caption}
```

... or try setting package options after the package has been loaded:

```
\usepackage{caption}
\captionsetup{font={it,small}}
```

 **numbering** To ensure proper float numbering, set caption positions such as:

```
\captionsetup[figure]{position=bottom}
\captionsetup[subfigure]{position=bottom}
\captionsetup[table]{position=top}
\captionsetup[subtable]{position=top}
```

Similarly for `longtable`. These positions depend on where the user places the `\caption` command inside each float.

#### 8.11.4 subfig package

Pkg subfig

 **lof/lotdepth** At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

In the document source, use `\hfill` and `\hspace*` subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

#### 8.11.5 floatrow package

Pkg floatrow

 **Misplaced alignment**  
tab character &  
 **subfig package**

Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 8.10.1.

When combined with the `subfig` package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

 **\FBwidth, \FBheight**

The emulation of `floatrow` does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. `lwrap` will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.

- Inside a `\warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

### 8.11.6 keyfloat package

Pkg `keyfloat` If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a `minipage`, which internally adjusts for a virtual 6-inch wide `minipage`, which then corrupts the `lw` option.)

## 8.12 KOMA-SCRIPT classes

Cls `komascript` Many features are ignored during the HTML conversion. The goal is source-level compatibility.

`\titlehead`, `\subject`, `\captionformat`, `\figureformat`, and `\tableformat` are not yet emulated.

⚠ Not fully tested! [Please send bug reports!](#)

Some features have not yet been tested. Please contact the author with any bug reports.

## 8.13 MEMOIR class

Cls `memoir` While emulating `memoir`, `lwarf` pre-loads a number of packages (section 572.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading `lwarf`:

```
\documentclass{memoir}
...
\PassOptionsToPackage{options_list}{package_name}
...
\usepackage{lwarf}
...
\usepackage{package_name}
```

⚠ version numbers `memoir` emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since `lwarf` is intended to support the freestanding packages, which are often newer than the date declared by `memoir`, it is hoped that `memoir` will update and change its emulated version numbers to match.

`\verbfootnote` is not supported.

`\newfootnoteseries`, etc. are not supported.

`lwarf` loads `pagenote` to perform `memoir`'s `pagenote` functions, but there are minor differences in `\pagenotesubhead` and related macros.

Poem numbering is not supported.

The `verbatim` environment does not yet support the `memoir` enhancements. It is currently recommended to load and use `fancyvrb` instead.

The `memoir` glossary system is not yet supported by `lwarpmk`. The `glossaries` package may be used instead, but does require the glossary entries be changed from the `memoir` syntax to the `glossaries` syntax.

## 8.14 International languages

### ⚠ section and file names

If using `pdflatex` with the setting `\booltrue{FileSectionNames}`, non-ASCII text in section names can result in corrupted HTML file names. `pdflatex` may be used if setting `\boolfalse{FileSectionNames}`, in which case HTML file numbers will be generated.

For correct HTML file names, use `xelatex`, `lualatex`, or dedicated document classes / engines.

(As of this writing, this warning is only relevant to the `kotex` package.)

## 8.15 Miscellaneous packages

### 8.15.1 verse and memoir

Pkg `verse` When using `verse` or `memoir`, always place a `\\"` after each line.

Cls `memoir`  
 \attrib The documentation for the `verse` and `memoir` packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. `lwarf` provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len `\vleftskip` These lengths are used by `verse` and `memoir` to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

### ⚠ spacing

Horizontal spacing relies on `pdftotext`'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

### 8.15.2 newclude package

Pkg newclude newclude modifies \label in a non-adaptive way, so newclude must be loaded before l warp is loaded:

```
\documentclass{article}
. . . <font setup>
\usepackage{newclude}
\usepackage[warpHTML]{l warp}
. . .
```

### 8.15.3 babel package

Pkg babel When French is used, the caption separator is changed to a dash. The following may be used to restore it to a colon:

```
\renewcommand*\CaptionSeparator{:-}
```

punctuation spaces Also when French is used, l warp creates fixed-width space around punctuation by patching \FBcolonspace, \FBthinspace, \FBguillspace, \FBmedkern, \FBthickkern, \FBtextellipsis, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a warpprint environment so that the user's changes do not affect the HTML output.

⚠ customized spacing

### 8.15.4 polyglossia package

Pkg polyglossia l warp uses cleveref, which has some limitations when using polyglossia, possibly resulting in the error

```
! Undefined control sequence. . . . \@begindocumenthook
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by cleveref, then select other languages using \setotherlanguages.

Once the print version works with cleveref and polyglossia, the HTML version should work as well using l warp.

### 8.15.5 todonotes and luatodonotes packages

Pkg todonotes The documentation for todonotes and luatodonotes have an example with a todo

Pkg luatodonotes

inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

### 8.15.6 `fixme`

Pkg `fixme` External layouts (`\fxloadlayouts`) are not supported.

#### ⚠️ external layouts

User control is provided for setting the HTML styling of the “faces”. The defaults are as follows, and may be changed in the preamble after `fixme` is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

### 8.15.7 `chemfig` package

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```
\begin{lateximage}[-chemfig-~\PackageDiagramAltText]
\chemfig{...}
\polymerdelim[...]{...}
\end{lateximage}
```

### 8.15.8 `chemformula` package

#### ⚠️ `chemformula` with `MATHJAX`

`chemformula` works best without MATHJAX. If MATHJAX is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The `chemformula` package adapts to `array`, but does not know about MATHJAX, and MATHJAX does not know about `chemformula`.)

While using MATHJAX, `\displaymathother` may also be used for other forms of display and inline math which contain `chemformula` expressions.

### 8.15.9 `mhchem` package

See section 344.

### 8.15.10 `xparse` package

Pkg `xparse` To remove from the log any warnings about redeclaring objects, place the following before `lwarp` is loaded:

```
\usepackage[log-declarations=false]{xparse}
```

### 8.15.11 kotex package

Pkg    kotex    See section 8.14 regarding *pdflatex* and Korean section names.

⚠    Korean section names

## 9 Compiling using custom shell commands

*lwarp* and *lwarpmk* try to make it easy to process print and HTML compilation tasks in most situations. Depending on the operating system, command-line options, *TEX* engine, and *lwarp* options, the commands ***lwarpmk print*** and ***lwarpmk html*** are automatically set up to correctly recompile the project. These actions may be overridden using *lwarp* options, thus allowing the use of packages such as *perltx* and *pythontex*.

### 9.1 Command options

Opt **PrintLatexCmd** The *lwarp* options **PrintLatexCmd** and **HTMLLatexCmd** are used to set customized commands to be executed by ***lwarpmk print*** and ***lwarpmk html***.

**PrintLatexCmd** should be set to shell commands which take *project.tex* and generate *project.pdf*.

**HTMLLatexCmd** should be set to take *project\_html.tex* and generate *project\_html.pdf*. *lwarpmk* will then take *project\_html.pdf* and automatically convert it and generate *project.html*.

### 9.2 Literal character macros

The *lwarp* package options are parsed by *TEX*, and so some characters require the use of a special macro to represent them. See table 7. *\LWRopquote* and *\LWRopseq* may be used to increase operating-system portability. *\jobname* must have *\_html* appended for processing HTML. *\space* may be necessary between other macros.

 **macro not found** To use these macros, either *kvoptions-patch* must be loaded before *lwarp*:

---

```
\usepackage{kvoptions-patch}
\usepackage[
    PrintLatexCmd={ ... } ,
    HTMLLatexCmd={ ... }
]{lwarp}
```

---

Table 7: Literal character macros

Character	Macro	Comment
%	\LWRpercent	
\$	\LWRdollar	
&	\LWRamp	
%	\LWRhash	
\	\LWRbackslash	
' or "	\LWRopquote	Depends on the operating system.
& or &&	\LWRopseq	Depends on the operating system.
(space)	\space	Forces an extra space.
(jobname)	\jobname	Without file extension.

or \lwarpsetup must be used to set PrintLatexCmd and HTMLLatexCmd:

---

```
\usepackage[...]{lwarp}
\lwarpsetup{
  PrintLatexCmd=
  {
    latex tm \LWRopseq
    dvips -o tm-pics.ps tm.dvi \LWRopseq
    ps2pdf tm-pics.ps \LWRopseq
    pdflatex tm.tex
  },
  HTMLLatexCmd=
  {
    latex tm_html \LWRopseq
    dvips -o tm_html-pics.ps tm_html.dvi \LWRopseq
    ps2pdf tm_html-pics.ps \LWRopseq
    pdflatex tm_html.tex
  }
}
```

---

### 9.3 *latexmk*

Prog latexmk If *latexmk* is used for a project, it may be easiest to continue using it.

**latexmk project.tex** would create *project.pdf* as normal.

**latexmk project\_html.tex** would create *project\_html.pdf*, then

**lwarpmk pdftohtml project\_html.pdf** would take *project\_html.pdf* and convert it to *project.html*.

Pkg sagetex *latexmk* may simplify the use of packages such as `sagetex`.

## 9.4 perltex package

Pkg perltex The `l warp` package option settings to use `perltx` would be similar to:

```
\usepackage[
  ...
  PrintLatexCmd={perltx -latex=pdflatex project.tex} ,
  HTMLLatexCmd={perltx -latex=pdflatex project_html.tex} ,
  ...
]{l warp}
```

⚠ “impure” math Place `perltx` math expressions between `\displaymathother` and `\displaymathnormal`, or `\inlinemathother` and `\inlinemathnormal`. See section 8.7.9.

## 9.5 pythontex package

Pkg pythontex An example using `pythontex`:

```
\usepackage[
  ...
  PrintLatexCmd={
    pdflatex project.tex \LWRopseq
    pythontex project \LWRopseq
    pdflatex project.tex
  } ,
  HTMLLatexCmd={
    pdflatex project_html.tex \LWRopseq
    pythontex project_html \LWRopseq
    pdflatex project_html.tex
  } ,
  ...
]{l warp}
```

Another possibility is to use `latexmk`, placing the `\Latexmk ...` commands in the `PrintLatexCmd` and `HTMLLatexCmd` options. While using these options, the `l warp` option `latexmk` would not be used.

⚠ “impure” math No attempt has yet been made to make `pythontex` robust with HTML output. Some math objects must be surrounded by `\displaymathother ... \displaymathnormal`, or `\inlinemathother ... \inlinemathnormal`. Displays of code may have to be enclosed

⚠ HTML look-alike inside a `lateximage` environment to prevent `<`, `>` and similar from being interpreted by the browser as HTML entities.

## 9.6 Other packages

Pkg sympytex Other packages such as `sympytex` and `rterface` would be set up similar to `pythontex`,

Pkg rterface

and the same warnings would apply.

## 9.7 *make* program

- Prog make To use *lwarp* with the *make* program, have the *makefile* take *project.tex* and generate the print version *project.pdf*, as normal. `\usepackage{lwarp}` must be used, and it generates *lwarpmk.conf* when the print version is created.

To generate HTML, first have *project\_html.tex* be compiled to generate *project\_html.pdf*. This must be in PDF format. Finally, have *project\_html.pdf* be converted to HTML using `lwarpmk pdftohtml project_html.pdf`, and convert SVG math with `lwarpmk limages`.

## 9.8 UTF-8 locale

-  **UTF-8 locale** *lwarpmk* uses the *texlua* program, which sets the “locale” to “C”, including for external operating-system calls such as when executing `lwarpmk html`. In some cases, an external program called from the user’s document may require the use of a UTF-8 “locale”. For UNIX-related operating systems, it may be required to use *lwarp*’s custom compilation options to add a locale change:

```
\usepackage{lwarp}[
  PrintLatexCmd={
    env LC_CTYPE=en_US.UTF-8
    xelatex -shell-escape project.tex
  }
  HTMLLatexCmd={
    env LC_CTYPE=en_US.UTF-8
    xelatex -shell-escape project_html.tex
  }
]
```

- Pkg *dita*a The only example seen so far where this is required is the *dita*a package, where the locale change allows the use of UTF-8 with Xe<sup>L</sup>A<sub>E</sub>T<sub>X</sub> and *dita*a. To use Lu<sup>A</sup>L<sub>E</sub>T<sub>X</sub> instead, the locale change would have to be made inside the *dita*a package where its calls the *dita*a program.

## 10 EPUB conversion

lwarf does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

**<meta> author** To assign the author's name for regular lwarf HTML files, and also for the EPUB, use \HTMLAuthor {\<name>}. This assigns the name to the <meta> author element. It may be set empty, and it defaults to \theauthor.

A special boolean is provided to simplify the process of converting lwarf HTML output to EPUB:

### FormatEPUB

---

Bool FormatEPUB  
Default: false

FormatEPUB changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

---

To help convert lwarf HTML output to EPUB, add

```
\booltrue{FormatEPUB}
```

to the project's source preamble after \usepackage{lwarf}. The EPUB version of the document cannot co-exist with the regular HTML version, so

```
Enter ⇒ lwarpmk cleanall
```

```
Enter ⇒ lwarpmk html
```

```
Enter ⇒ lwarpmk limages
```

to recompile with the FormatEPUB boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.

The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program *Calibre* (<https://calibre-ebook.com/>).

 **search order** The EPUB conversion program must know what order the files are included. For lwarf projects, set the EPUB conversion software to do a breadth-first search of the files. For *Calibre*, this option is found in

**Preferences → Plugins → File type plugins → HTML to Zip**

 **encoding** Check the box Add linked files in breadth first order. Set the document encoding as utf-8, which is what lwarf generates for HTML, even if the original printed document uses some other encoding.

**⚠ section breaks**

The EPUB-conversion program must also know where the section breaks are located. For a list of lwarf's section headings, see table 9. For example, an article class document would break at \section, which is mapped to HTML heading level <h4>, whereas a book class document would break at \chapter, which is HTML heading level <h3>. For *Calibre*, this option is found in

**Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)**

Select the “magic wand” to the right of this entry box, and set the first entry

**Match HTML tags with tag name:**

to “h4”. (Or “h3” for document classes with \chapters.) The Detect chapters at field should then show

**//h:h4 — or — //h:h3**

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the lwarf-generated HTML files may be loaded by *Calibre*, and then converted to an EPUB.

---

**MATHJAX support**

---

MATHJAX may be used in EPUB documents. Some e-readers include MATHJAX, but any given reader may or may not have a recent version, and may or may not include extensions such as support for siunitx.

lwarf adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader's version of MATHJAX, so lwarf requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn't work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MATHJAX, especially for equations numbered by chapter, or where siunitx support is important.

---

## 11 Word-processor conversion

lwarf may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LibreOffice works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. lwarf provides some assistance in locating these frame boundaries, as shown below.

### 11.1 Activating word-processor conversion

A special boolean is provided to simplify the process of converting lwarf HTML output to EPUB:

FormatWP	
Bool FormatWP Default: false	Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Additionally, honors the booleans WPMarkFloats, WPMarkMinipages, WPMarkTOC, and WPMarkLOFT.

---

To help modify lwarf HTML output for easier import to a word processor, add

`\booltrue{FormatWP}`

to the project's source preamble after lwarf is loaded. The following changes are then made to the HTML output:

- If using a class without chapters, \section and lower are shifted up in level for the HTML heading tags. The css has not been changed, so the section heading formats will not match the normal HTML output, but when imported to *LibreOffice Writer* the higher section headings will import as **Heading 1** for the title, **Heading 2** for \section, etc.
- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and <div>s, but they are no longer useful when the document has been imported into a word processor.
- An additional <div> with an id encapsulates each float and minipage, which on import into *LibreOffice Writer* causes a thin frame to appear around the text block for each.
- Float captions are given an explicit italic formatting.

- Tabular rule borders are made explicit for *LibreOffice Writer*. LIBREOFFICE displays a light border around each cell while editing, even those which have no border when printed, and lwarp also uses a light border for thin rules, so it will be best to judge the results using the print preview instead of while editing in LIBREOFFICE.
- \includegraphics and svg math width and height are made explicit for LIBREOFFICE.
- \hspace is approximated by a number of \quads, and rules are approximated by a number of underscores.
- Explicit HTML styles are given to:
  - \textsc, etc.
  - \underline, soul and ulem markup.
  - center, flushleft, flushright.
  - \marginpar, keyfloat, sidenotes, floatflt, and wrapfig.
  - fancybox \shadowbox, etc.
  - The LATEX and TEX logos.
- Honors several booleans:

**WPMarkFloats:** Marks the begin and end of floats.

**WPMarkMinipages:** Marks the begin and end of minipages.

**WPMarkTOC:** Marks the location of the Table of Contents.

**WPMarkLOFT:** Marks the locations of the List of Figures/Tables.

**WPMarkMath:** Prints LATEX math instead of using images.

**WPTitleHeading:** Adjusts title and section headings.

Several of these may be used to add markers to the HTML text which help determine where to adjust the word processor document after import.

## 11.2 Additional modifications

### WPMarkFloats

---

Bool WPMarkFloats  
Default: false

Adds

```
==== begin table ====
. .
==== end ====
or
```

```
==== begin figure ====
. .
==== end ====

```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.

---

---

### WPMarkMinipages

---

Bool WPMarkMinipages

Default: false

Adds

```
==== begin minipage ====
. . .
==== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

---

### WPMarkTOC

---

Bool WPMarkTOC

Default: true

While formatting for word processors, adds

```
==== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

*If set false, the actual TOC is printed instead.*

---

### WPMarkLOFT

---

Bool WPMarkLOFT

Default: false

While formatting for word processors, adds

```
==== list of figures ==== and/or
==== list of tables ====
```

where each of these lists would have been. This helps identify where to insert the actual lists.

*If set false, the actual lists are printed instead.*

---

### WPMarkMath

---

siunitx

Bool WPMarkMath

Default: false

Prog TeXMaths

While formatting for word processors, prints math as L<sup>A</sup>T<sub>E</sub>X code instead of creating SVG images or MATHJAX. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

When using the siunitx package, enter

```
\usepackage{siunitx}
```

in the *TeXMaths* preamble. Equation numbering is problematic for *AMS* math environments.

---

Table 8: Section HTML headings for word-processor conversion

Section	HTML headings*			
	With \chapter		Without \chapter	
	WPTitleHeading	WPTitleHeading	WPTitleHeading	WPTitleHeading
Title	<h1>	plain	<h1>	plain
\book	<div>	<div>	<div>	<div>
\part	<h2>	<h1>	<h2>	<h1>
\chapter	<h3>	<h2>	—	—
\section	<h4>	<h3>	<h3>	<h2>
\subsection	<h5>	<h4>	<h4>	<h3>
\paragraph	<h6>	<h5>	<h5>	<h4>
\ subparagraph	<span>	<h6>	<h6>	<h5>

\* For default depths when not FormatWP, see table 9 on page 197.

### WPTitleHeading

Bool WPTitleHeading  
 Default: false  
 section headings

While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LIBREOFFICE. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 181.

## 11.3 Recommendations

TOC, LOF, LOT For use with *LibreOffice Writer*, it is recommended to:

1. Set \booltrue{FormatWP}
2. Set \booltrue{WPMarkTOC} and \boolfalse{WPMarkLOFT}
3. Use `lwarp` to generate the HTML document.
4. Copy/paste from the HTML document into an empty *LibreOffice Writer* document.
5. Manually insert a LIBREOFFICE TOC in the LIBREOFFICE document.
6. Manually add frames around each float, adding a caption which is cut/pasted from each float's simulated caption.
7. Manually create cross references.

This process yields a document with an actual LIBREOFFICE Table of Contents, but a simulated List of Figures and List of Tables.

**siunitx** For **siunitx**, remember to adjust the preamble as mentioned above.

**LO view border options** LIBREOFFICE has options in the **View** menu to turn on/off the display of thin borders around table cells and text objects.

## 11.4 Limitations

Floats and captions are not explicitly converted to LIBREOFFICE floats with their own captions. Floats are surrounded by a thin frame in the LIBREOFFICE editor, and may be marked with WPMarkFloats, but are not given a proper LIBREOFFICE object frame. Captions are given an explicit italic formatting, but not a proper LIBREOFFICE paragraph style.

Cross references are not actual LIBREOFFICE linked cross references.

The List of Figures and List of Tables are not linked. The pasted pseudo LOF and LOT match the numbering of the L<sup>A</sup>T<sub>E</sub>X and HTML versions.

Equation numbering is not automatic, but the equation numbers in SVG math will match the L<sup>A</sup>T<sub>E</sub>X and HTML output. SVG math is recommended when using the *AMS* environments, which may have multiple numbered equations per object.

As of when last checked, LIBREOFFICE ignores the following:

- Minipage alignment.
  - Tabular cell vertical alignment.
  - Image rotation and scaling.
  - Rounded border corners, which are also used by:
    - \textcircled
    - booktabs trim
  - \hspace and rules, also used by algorithmic.
  - Coloring of text decorations, used by soul and ulem.
  - Overline text decoration, used by romanbar.

LIBREOFFICE also has limitations with frames and backgrounds:

- Multiple lines in an object are framed individually instead of as a whole.
  - Nested frames are not handled correctly.
  - Images inside boxes are not framed correctly.
  - Spans with background colors and frames are not displayed correctly.

## 12 Modifying l warp

**locating something** To quickly find the source for a package in `l warp.dtx`, search for `*packagename`, such as `*siunitx`.

Likewise, to quickly find the source for a file in `l warp.dtx`, search for `*filename`, such as `*l warp.css`.

Purely text-based packages probably will work as-is when generating HTML.

Look to existing code for ideas on how to expand into new code.

**image of TeX output** An environment may be converted to a `\teximage` then displayed with an image of the resulting L<sup>A</sup>T<sub>E</sub>X output. See section 88 for an example of the `picture` environment.

**css classes** To create a custom HTML block or inline css class, see section 51.9.

**print/HTML macros** To create print and HTML versions of the same macro or environment, see section 36.

**⚠ TEX boxes** Any TeX boxes must be undone, as `svg` math or `\teximages` require `\newpage`, which will not work in a TeX box.

**index recreation** To recreate the index for the `l warp` documentation:

---

```
makeindex -s gglo.ist -o l warp.gls l warp.glo
splitindex l warp.idx -- -s gind.ist
```

---

### 12.1 Creating a development system

The following creates a local development system for `l warp` on a TeXLive system in a UNIX-like environment. Doing so allows anything requesting `l warp` to use the development version instead of whichever version is installed in TeXLive.

#### Create a development directory:

Place into this directory `l warp.dtx` and `l warp.ins`.

To create `l warp.sty`, execute

Enter ⇒ **`pdflatex l warp.ins`**

which creates `l warp.sty` and several hundred additional `l warp-*.sty` files for the various packages which are supported.

To create the documentation `l warp.pdf`, execute

Enter ⇒ **`pdflatex l warp.dtx`**

#### To make the development files visible to other projects:

Create the directory

`/usr/local/texlive/texmf-local/tex/latex/local/l warp`

---

Inside this directory, create the file update, containing:

---

```
ln -s /path_to_dev_directory/lwarp*.sty .
ln -s /path_to_dev_directory/lwarp_baseline_marker.png .
ln -s /path_to_dev_directory/lwarp_baseline_marker.eps .
mktexlsr
```

---

Run ./update now, and whenever a new lwarp-\* package is added.

**To make the development version of *lwarpmk* visible to other projects:**

---

```
cd /opt
ln -s /usr/local/texlive/texmf-local/bin/x86_64-linux texbin_local
cd texbin_local
ln -s ../../scripts/lwarp/lwarpmk.lua lwarpmk
cd /usr/local/texlive/texmf-local/scripts/
mkdir lwarp
cd lwarp
ln -s /path_to_dev_directory/lwarpmk.lua lwarpmk
```

---

Verify that the correct version is found with

Enter ⇒ **which lwarpmk**

**To make the local versions visible to the shell:**

Paths must be set by the shell startup, such as in .bashrc and .cshrc:

In .bashrc:

---

```
PATH=/opt/texbin_local:/opt/texbin:$PATH
```

---

In .cshrc:

---

```
setenv PATH ${HOME}/bin:/opt/texbin_local:/opt/texbin:${PATH}
```

---

## 12.2 Modifying a package for lwarp

If a class loads additional packages, it will be required to modify the class for **lwarp**, since **lwarp** must be loaded before most other packages.

To work with **lwarp**, a class must first set up anything which replicates the functions of the basic L<sup>A</sup>T<sub>E</sub>X classes, load any required fonts, then load **lwarp**, then finally load and adjust any other required packages.

When creating **HTML**, **lwarp** redefines the \usepackage and \RequirePackage macros such that it first looks to see if a **lwarp-<packagename>.sty** version exists. If so, the **lwarp** version is used instead. This modular system allows users to create their own versions of packages for **lwarp** to use for **HTML**, simply by creating a new package with a **lwarp-** prefix. If placed in the local directory along with the source code, it will be

seen by that project alone. If placed alongside the other `lwarp-` packages where `TEX` can see it, then the user's new package will be seen by any documents using `lwarp`. (Remember `mktexlsr` or `texhash`.)

An `lwarp-<packagename>.sty` package is only used during `HTML` generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful `HTML` conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing `lwarp-` packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new `lwarp-` package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a “local” prefix according to the package name, and @ characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for `HTML` output. Only the “user-facing” macros need to be nullified or emulated.

Each `lwarp-*` package should first call either of:

```
\LWR@ProvidesPackageDrop  
-or-  
\LWR@ProvidesPackagePass
```

If “Drop”ped, the original print-version package is ignored, and only the `lwarp-` version is used. Use this where the original print version is useless for `HTML`. If “Pass”ed, the original package is loaded first, with the user-supplied options, then the `lwarp-` version continues loading as well. See section 380 (`ntheorem`) for an example of selectively disabling user options for a package. Use this when `HTML` output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a `lwarp-` version.

### 12.2.1 Adding a package to the `lwarp.dtx` file

When adding a package to `lwarp.dtx` for permanent including in `lwarp`, provide the `lwarp-<packagename>` code in `lwarp.dtx`, add its entry into `lwarp.ins`, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to `lwarp.dtx` in section 20.1. This causes `lwarp` to stop with an error if `packagename` is loaded before `lwarp`. Finally, add an entry in table 2, `Supported packages and features`, and also the Updates section.

## 12.3 Modifying a class for `lwarp`

If a class loads additional packages, it will be required to modify the class for `lwarp`, since `lwarp` must be loaded before most other packages.

To work with **lwarp**, a class must first set up anything which replicates the functions of the basic L<sup>A</sup>T<sub>E</sub>X classes, load any required fonts, then load **lwarp**, then finally load and adjust any other required packages.

## 12.4 Testing **lwarp**

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

Remember that the configuration files are only rewritten when compiling the printed version of the document.

When changing the source to **lwarpmk** or a css file in **lwarp.dtx**:

1. Change the source in **lwarp.dtx**.
2. `pdflatex lwarp.ins`
3. `pdflatex lwarp.dtx`
4. If modifying **lwarpmk** the new version should now be active.
5. If modifying css files:
  - (a) For the document, **lwarpmk** print to update the css files in the project.
  - (b) Reload the HTML document to see the effect of the new css files.

Sometimes it is worth checking the `<project>.html.pdf` file, which is the PDF containing HTML tags. Also, `<project>.html.html` has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and css code.

## 12.5 Modifying **lwarpmk**

Prog   **lwarpmk**    In most installations, **lwarpmk.lua** is an executable file located somewhere the operating system knows about, and it is called by typing **lwarpmk** into a terminal.  
File   **lwarpmk.lua**

A project-local copy of **lwarpmk.lua** may be generated, modified, and then used to compile documents:

1. Add the **lwarpmk** option to the **lwarp** package.
2. Recompile the printed version of the document. The **lwarpmk** option causes **lwarp** to create a local copy of **lwarpmk.lua**
3. The **lwarpmk** option may now be removed from the **lwarp** package.

4. Copy and rename `lwarpmk.lua` to a new file such as `mymake.lua`.
5. Modify `mymake.lua` as desired.
6. If necessary, make `mymake.lua` executable.
7. Use `mymake.lua` instead of `lwarpmk.lua`.

## 13 Troubleshooting

### 13.1 l warp package error conditions and warnings

l warp tests for a number of error conditions and prints appropriate warnings. The following is a summary of these conditions.

#### 13.1.1 Configuration file `lwarpmk.conf`

**File does not exist:** The configuration file must exist for `lwarpmk`.

**Incorrect Unix /Windows selection:** The operating system which was detected by l warp. So far only Unix and Windows are supported.

**Incorrect delimiter characters.** Older versions of `lwarpmk` used a different delimiter.

**Source name is set to l warp:** l warp has recently been recompiled in this directory, which overwrote the project's configuration files. This also occurs if `lwarpmk` is executed in l warp's source directory.

**Incorrect operating system:** The configuration file was set for a different operating system, perhaps due to sharing in a collaborative project.

**Outdated configuration files:** l warp has been updated since this project was last compiled. If there appears to be a valid print command in the file, `lwarpmk` displays this to instruct the user how to recompile the print version, which then updates the configuration files.

**The designated source file does not exist:** For whatever reason...

**Unknown engine:** l warp cannot determine which engine is being used. Supported are DVI L<sup>A</sup>T<sub>E</sub>X, PDF L<sup>A</sup>T<sub>E</sub>X, XE<sup>L</sup>L<sup>A</sup>T<sub>E</sub>X, L<sup>A</sup>U<sup>L</sup>TEX, and upL<sup>A</sup>T<sub>E</sub>X.

#### 13.1.2 Image generation with `lwarpmk limages`

**“Wait a moment for the images to complete before reloading page.”:**

Images are generated by background tasks. If the document is reloaded before these tasks are complete, some images may not yet be generated. `lwarpmk` tries to wait for background tasks to complete before exiting.

**HTML version does not exist:** Images are extracted from the HTML version, which must be compiled before images are generated.

**\*-images.txt does not exist:** This file tells which images to extract from the HTML file. If the file does not exist, it may be that no SVG math or lateximages were used. If so, `lwarpmk limages` is not necessary.

**Cross references are not correct:** The document must have up-to-date cross references to locate the images to extract. A number of conditions may cause incorrect cross references.

**“WARNING: Images will be incorrect.”:** An image reference was not found. Recompile.

**l warpmk epstopdf \*** or **l warpmk pdftosvg \***: Errors if filenames are not found.

### 13.1.3 Default bitmapped font

l warp requires the use of a vector font. If l warp detects that the document uses the default COMPUTER MODERN font, and the cm-super package is not installed, it is assumed that the font is bitmapped. An error is generated, along with the recommendation to install cm-super or use lmodern.

### 13.1.4 Packages

**Loaded before l warp:** Some packages and classes must be loaded before l warp. These include input and font encoding, morewrites and newclude, and a number of CJK-related packages and classes.

**Loaded after l warp:** Most packages which are modified by l warp must be loaded after l warp.

**Loaded never:** Some packages do not work with l warp. An error is generated, along with a list of alternatives to consider.

**Specific packages:** Some packages enforce a specific load order vs. certain other packages.

**Patching error:** l warp tries to patch some packages using xpatch. If the original package has been updated more recently than l warp, a patch may not work. It may be necessary to use an older version of the package until l warp is updated.

**longtable:** l warp’s longtable package issues detailed error messages regarding the use of the table headers and footers.

**polyglossia:** If used, an informative message is printed to instruct the user to be sure to set a language, without which an error will occur.

**babel or polyglossia:** An informative message is printed to note that not all languages are supported by cleveref.

### 13.1.5 Compiling

**SideTOCDepth < FileDepth:** A warning is displayed if these counters are set such that the sidetoc will not be able to access all pages of the website.

**Duplicate filenames:** l warp may generate file names from section names. While doing so, the filenames are simplified and special characters are removed. If this process generates a duplicate filename, an error is generated, describing the filename and which section name generated it.

- ⚠ **HTML corrupted**
- Multirow:** When `\multirow` or `\multicolumn` are used, `\mrowcell` or `\mcolrowcell` must be placed in the appropriate cells to avoid corrupted HTML output.
  - (width,height) missing a comma:** `\makebox` and `\framebox` can accept a parenthesis-delimited width and height, which must be separated by a comma.
  - “Load graphicx or graphics for improved SVG math baselines.”:** SVG math baselines are improved if either of these packages are used.
  - “Load graphicx or graphics for improved XeTeX logo.”:** If these packages are loaded, the Xe<sup>T</sup>E<sub>X</sub> logo can use the reversed “E”.
  - “It is recommended to use [width=xx\linewidth] instead of [scale=yy] ”:** Browser support of scale does not have the same effect as in L<sup>T</sup>E<sub>X</sub>.

## 13.2 Using the l warp package

The following address problems which may occur, and possible solutions to each.

Also see:

- [Section 7.10: Commands to be placed into the warpprint environment](#)
- [Section 8: Special cases and limitations](#)

- ⚠ **HTML corrupted** **Text is not converting correctly / corrupted HTML tags:**

- Font-related UTF-8 information must be embedded in the PDF file. See section [7.4](#) regarding bitmapped vs. vector fonts.
- See section [8.2.1](#) regarding HTML entities and the characters &, <, and >.

**Undefined HTML settings:**

- See the warning regarding the placement of the HTML settings at section [7.6](#).

**Tabular problems:** See section [8.10.1](#).

**Obscure error messages:**

**Print first:** Be sure that a print version of the document compiles and that your document's L<sup>T</sup>E<sub>X</sub> code is correct, before attempting to generate an HTML version.

**\end{warpHTML}, \end{warpprint}, \end{warpall}:** Each of these must be without any other characters on the same line.

**Options clash:** If using memoir, see section [8.13](#).

**“Missing \begin{document}.”:** Some packages require that their options be specified before l warp is loaded, or via the package's setup macro, especially if these options include the use of braces. See section [8.1](#).

**“No room for a new \write.”:** Before `\usepackage{l warp}`, add:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
```

**”! TeX capacity exceeded, sorry [text input levels=15].”:** Packages were nested too many levels deep. Locate the file `texmf.cnf` for your distribution, and add the line

```
max_in_open = 30
```

**”Missing \$ inserted.”:** If using a filename or URL in a footnote or `\item`, escape underscores with `\_`.

**”Label(s) may have changed. Rerun to get cross-references right.”:**

This warning may repeat endlessly if a math expression is used in a caption. Simple math expressions such as `$X=1$` may be replaced with

```
\textit{X},=,1
```

**”Leaders not followed by proper glue”:**

This can be caused by a missing `\@fleattype` or `\@sectiontype` definition. See `lwarp`'s definitions for examples.

**”Improper \prevdepth”:** `lateximages` and `svg` math require `\newpage`, which cannot work inside `TEX` boxes or `\ensuremath`. Anything using `\newsavebox`, `\newbox`, `\rbox`, `\savebox`, `\hbox`, `\vbox`, `\usebox`, `\sbox`, etc., must be modified to work without box commands.

If you find something using `\ensuremath`, have it temporarily set:

```
\LetLtxMacro\@ensuredmath\LWR@origensuredmath
```

inside a group first.

Also, custom macros which appear inside a section, figure, or table name should be made robust since they appear inside the `.toc`, `.lof`, or `.lot` files. Use `\newrobustcmd` or `\robustify` from `etoolbox`, `xparse`, etc.

If using BibTeX, see section 8.6.9.

**”! Undefined control sequence. . . . \@begindocumenthook”:**

See section 8.15.4 if using polyglossia.

**”\begin{equation} ended by \end{document}”:** Do not use custom macros such as `\beq` and `\eeq` to replace

```
\begin{equation}
...
\end{equation}
```

**”Misplaced \omit”:** If using `\LWR@formatted` to define new macros for print and HTML modes, see section 36 regarding `\LWR@expandableformatted`.

**Complicated objects inside math:** Some objects, such as Tikz, may not compile in `lwarp`'s normal math emulation. Insert

```
\displaymathother -or- \inlinemathother
```

before the math, and then

```
\displaymathnormal -or- \inlinemathnormal
```

when displaying “normal” math. See section 8.7.9.

**Slow compilation of math objects:** Complicated math objects can also cause problems with alt tags, resulting in very slow compilation, large alt tags,

⚠ macros in  
section,table,figure names

⚠ BibTeX

⚠ polyglossia

⚠ custom macros for  
environments

⚠ \LWR@formatted

⚠ “impure” math objects

and possible crashes. Use `\inlinemathother ... \inlinemathnormal` or `\displaymathother ... \displaymathnormal` around the math expression.

 **MATHJAX** **Incorrect MATHJAX:** Some objects do not convert to MATHJAX. Use `\displaymathother` before these objects, then `\displaymathnormal` to return to “normal” display math. See section 8.7.9.

**Missing sections:** See section 7.6 regarding the `FileDepth` and `SideTOCDepth` counters, and the use of `\tableofcontents` in the home page.

**Misnumbered footnotes from section headings:** See section 8.5.4.

**Missing HTML files:**

- See the warning regarding changes to the HTML settings at section 7.6.
- Ensure that the filenames are unique after math and short words are removed. See `FileSectionNames` at section 7.6.

**Missing / incorrect cross-references:**

- Use `lwarfmk` again followed by `lwarfmk html` or `lwarfmk print` to compile the document one more time.
- Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French). `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.
- `cleveref` and `varioref` are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

Ex:

`\cpageref{tab:first,tab:second}`

in `html` becomes:

“pages for table 4.1 and for table 4.2”

See `\cpagerefFor` at page 556 to redefine the message which is printed for page number references.

**BibTeX errors with `\etalchar`:** See section 8.6.9.

**Malformed URLs:** Do not use the % character between arguments of `\hyperref`, etc., as this character is among those which is neutralized for inclusion in HTML URLs.

**Em-dashes or En-dashes in listing captions and titles:**

Use X<sub>E</sub>LATEX or LuaLATEX.

**Floats out of sequence:**

**Mixed “Here” and floating:** Floats [H]ere and regular floats may become out of order. `\clearpage` if necessary.

**Caption setup:** With `\captionsetup` set the positions for the captions above or below to match their use in the source code.

**Images are appearing in strange places:**

 **labels**  
 **label characters**  
 **\nameref**  
 **empty link**

 **cleveref** page numbers

- Enter `lwarpmk limages` to refresh the `\teximage` images.

#### SVG images:

 **adding/removing**

When a math expression, picture, or Tikz environment is added or removed, the SVG images must be re-created by entering `lwarpmk limages` to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Tikz may move to new image numbers when the document is changed.

**recompile first**

Before attempting to create the SVG image files, `lwarpmk` verifies that the HTML version of the document exists and has correct internal image references.<sup>15</sup> If it is necessary to recompile the document's HTML version one more time, `lwarpmk` usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the L<sup>A</sup>T<sub>E</sub>X recompile warnings.

 **HTML instead of images**

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

 **page counter**

Incorrect SVG images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

Expressing math as SVG images has the advantage of representing the math exactly as L<sup>A</sup>T<sub>E</sub>X would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarf uses an MD5 hash on its L<sup>A</sup>T<sub>E</sub>X source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as picture and Tikz require one image file each. For a document with a large amount of math, see section 5.5 to use MATHJAX instead.

#### Plain-looking document:

- The document's CSS stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFilename` statements point to a valid CSS file.

 **HTML corrupted**

#### Broken fragments of HTML:

- Check the PDF file used to create HTML to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

#### Changes do not seem to be taking effect:

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the HTML settings at section 7.6.
- Verify that the proper CSS is actually being used.
- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

---

<sup>15</sup>This becomes important when dealing with a document containing thousands of images.

**Un-matched conditional compiles:**

- Verify the proper begin/end of warpprint, warpHTML, and warpall environments.

**13.2.1 Debug tracing output**

\tracingl warp When \tracingl warp is used, l warp will add extra tracing messages to the .log file. The last several messages may help track down errors.

Place \tracingl warp just after \usepackage{l warp} to activate tracing.

**13.3 Compiling the l warp.dtx file**

**l warp\_tutorial.tex:** Copy or link l warp\_tutorial.txt from the TDS doc directory to the source directory, or wherever you wish to compile the documentation. This file is included verbatim in the documentation, but is in the doc directory so that it may be found by *texdoc* and copied by the user.

**Illogical error messages caused by an out-of-sync l warp.sty file:**

1. Delete the l warp.sty file.
2. Enter **pdflatex l warp.ins** to generate a new l warp.sty file.
3. Enter **pdflatex l warp.dtx** to recompile the l warp.pdf documentation.

**Un-nested environments:**

Be sure to properly nest:

- \begin{macrocode} and \end{macrocode}
- \begin{macro} and \end{macro}
- \begin{environment} and \end{environment}

## 14 Trademarks

- TeX is a trademark of American Mathematical Society.
- ADOBE® and ADOBE *Framemaker*® are either registered trademarks or trademarks of ADOBE SYSTEMS INCORPORATED in the United States and/or other countries.
- LINUX® is the registered trademark of Linus Torvalds in the U.S. and other countries.
- MAC OS® is a trademark of APPLE INC.
- MADCAP FLARE™ is the property of MADCAP SOFTWARE, INC.
- MATHJAX is copyright 2009 and later. The MATHJAX CONSORTIUM is a joint venture of the AMERICAN MATHEMATICAL SOCIETY (AMS) and the SOCIETY FOR INDUSTRIAL AND APPLIED MATHEMATICS (SIAM) to advance mathematical and scientific content on the web.
- MICROSOFT®, ENCARTA, MSN, and WINDOWS® are either registered trademarks or trademarks of MICROSOFT CORPORATION in the United States and/or other countries.
- UNIX® is a registered trademark of THE OPEN GROUP.
- YOUTUBE™ is trademark of GOOGLE LLC.

File 1 **lwarp.sty**

## 15 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of crude hacks clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include `xcolor` with its color models and conversion to `HTML` color output, and `siunitx` which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by `pdftotext`.

Packages were emulated where their primary purpose was visual formatting which is not relevant to `HTML` output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in `HTML` output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a `lateximage` environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

Table 9: Section depths and HTML headings

Section	LATEX depth	HTML headings *
Title of the entire website		<h1>
(none)	-5	new for this package
book	-2	<div class = "book">
part	-1	<h2>
chapter	0	<h3>
section	1	<h4>
subsection	2	<h5>
subsubsection	3	<h6>
paragraph	4	<span class = "paragraph">
subparagraph	5	<span class = "subparagraph">
listitem	7	new for this package, used for list items

\* If FormatWP is true, section headings may be adjusted, depending on WPTitleHeading. See table 8 on page 181.

## 16 Section depths and HTML headings

Stacks are created to track depth inside the LATEX document structure. This depth is translated to HTML headings as shown in table 9. “Depth” here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the LATEX document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Support for the memoir package will require the addition of a book level, which may push the HTML headings down a step, and also cause subsubsection to become a <div> due to a limit of six HTML headings.

It is possible to use HTML5 <section> and <h1> for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the css to remain fixed as well.

## 17 Source code

This is where the documented source code for lwarf begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the lwarf package.

**line numbers** The small numbers at the left end of a line refer to line numbers in the lwarf.sty file.

**subjects** Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph.

**objects** Black-colored tags in the left margin are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are

**index entries** command macros. Each of these also appears in the index as individual entries, and are also listed together under “files”, “packages”, “environments”, “booleans”, and “counters”.

 **warnings** Special warnings are marked with a warning icon.

**for HTML output:** Green-colored tags in the left margin show which sections of source code apply to the generation of HTML, print, or both forms of output.

**for PRINT output:**

**for HTML & PRINT:**

## 18 Detecting the **TEX** engine — *pdflatex*, *lualatex*, *xelatex*

See: <http://tex.stackexchange.com/a/47579>.

Detects XETEX and LUALXETEX:

```

1 \RequirePackage{iftex}[2019/11/07]
2
3 \newif\ifxetexorluate
4
5 \ifXeTeX
6     \xetexorluatetrue
7 \else
8     \ifLuaTeX
9         \xetexorluatetrue
10    \else
11        \xetexorluatefalse
12    \fi
13 \fi

```

## 19 Early package requirements

Pkg `etoolbox` Provides `\ifbool` and other functions.

Pkg `xpatch` Patches macros with optional arguments.

```

14 \RequirePackage{etoolbox}[2011/01/03]%
15 \RequirePackage{xpatch}

```

Pkg `ifplatform` Provides `\ifwindows` to try to automatically detect WINDOWS OS.

```
16 \RequirePackage{ifplatform}%

```

Pkg `letltxmacro`

```
17 \RequirePackage{letltxmacro}
```

## 20 Package load order

Several packages must never be used with `l warp`, others should only be loaded before `l warp`, and others should only be loaded after. The `l warp` core checks most of these cases. In some `l warp-*` packages, `\LWR@loadbefore` is used to trigger an error if they are loaded after `l warp`, while additional code provides necessary patches for when they are loaded before.

Packages which must be loaded after `l warp` are enfoed by a large number of `\LWR@loadafter` statements, below. Some packages are emulated by `memoir`, and

so these are tested by \LWR@notmemoirloadafter, which does not cause an error if memoir is used.

\LWR@checkloadfilename is used to check each filename to see if it must never be loaded, or must always be loaded before l warp.

## 20.1 Tests of package load order

\LWR@loadafter {*packagename*} Error if this package was loaded before l warp.

```

18 \newcommand*{\LWR@loadafter}[1]{%
19 \@ifpackageloaded{#1}%
20 {%
21   \PackageError{l warp}%
22   {%
23     Package #1,\MessageBreak
24     or one which uses #1,\MessageBreak
25     must be loaded after l warp
26   }%
27   {Move \detokenize{\usepackage}{#1} after
28   \detokenize{\usepackage}{l warp}.\MessageBreak
29   Package #1 may also be loaded by something else,\MessageBreak
30   which must also be moved after l warp.}%
31 }%
32 {}%
33 }
```

\LWR@notmemoirloadafter {*packagename*} Error if not memoir class and this package was loaded before l warp.

memoir emulates many packages, and pretends that they have already been loaded.

```

34 \@ifclassloaded{memoir}%
35 {\newcommand*{\LWR@notmemoirloadafter}[1]{}}
36 {\LetLtxMacro{\LWR@notmemoirloadafter}\LWR@loadafter}
```

\LWR@notltjloadafter {*packagename*} Error if not a ltjs\* class and this package was loaded before l warp.

```

37 \LetLtxMacro{\LWR@notltjloadafter}\LWR@loadafter
38
39 \@ifclassloaded{ltjarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}}
40 \@ifclassloaded{ltjbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
41 \@ifclassloaded{ltjreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
42 \@ifclassloaded{ltjsarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
43 \@ifclassloaded{ltjsbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
44 \@ifclassloaded{ltjsreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
45 \@ifclassloaded{ltjspf}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
46 \@ifclassloaded{ltjskiyou}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
47 \@ifclassloaded{ltjtarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
48 \@ifclassloaded{ltjtbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
49 \@ifclassloaded{ltjtreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}{}{}}
```

\LWR@loadbefore {*packagename*} Error if this package is loaded after lwarf.

```

50 \newcommand*{\LWR@Loadbefore}[1]{%
51 \@ifpackageloaded{#1}%
52 {}%
53 {%
54 \PackageError{lwarf}%
55 {Package #1 must be loaded before lwarf}%
56 {Move \detokenize{\usepackage}{#1} before \detokenize{\usepackage}{lwarf}.}%
57 }%
58 }
```

\LWR@checkloadbefore {*thispackagename*} {*packagename*}

If package names match, error if it is loaded after lwarf.

```

59 \newcommand*{\LWR@checkloadbefore}[2]{%
60     \edef\LWR@tempone{#1}%
61     \ifdefstring{\LWR@tempone}{#2}{%
62         \LWR@loadbefore{#1}%
63     }{}%
64 }
```

\LWR@loadnever {*badpackagename*} {*replacementpkgnames*}

The first packages is not supported, so tell the user to use the second instead.

```

65 \newcommand*{\LWR@Loadnever}[2]{%
66 \PackageError{lwarf}%
67 {}%
68     Package #1 is not supported\MessageBreak
69     by lwarf's HTML conversion.\MessageBreak
70     Package(s) #2 may be useful instead%
71 }%
72 {}%
73     Package #1 might conflict with lwarf in some way,\MessageBreak
74     or is superceded by another package.\MessageBreak
75     For a possible alternative, see package(s) #2.
76 }%
77 }
```

\LWR@checkloadnever {*thispackagename*} {*badpackagename*} {*replacementpkgnames*}

If this package name is the bad packagename, suggest the replacements instead.

```

78 \newcommand*{\LWR@checkloadnever}[3]{%
79     \edef\LWR@tempone{#1}%
80     \ifdefstring{\LWR@tempone}{#2}{%
81         \LWR@loadnever{#2}{#3}%
82     }{}%
83 }
```

\LWR@earlyloadnever {*badpackagename*} {*replacementpkgname*}

The first package is not supported, so tell the user to use the second instead. This version checks immediately for packages which may have been loaded before lwarp.

```
84 \newcommand*{\LWR@earlyloadnever}[2]{%
85     \@ifpackageloaded{#1}{%
86         \LWR@loadnever{#1}{#2}%
87     }{%
88 }
```

```
\LWR@earlyclassloadnever {\langle badclassname \rangle} {\langle replacementclassname \rangle}
```

The first class is not supported, so tell the user to use the second instead. This version checks immediately for classes which may have been loaded before lwarp.

```
89 \newcommand*{\LWR@earlyclassloadnever}[2]{%
90 \@ifclassloaded{#1}{%
91 \PackageError{lwarp}%
92 {%
93     Class #1 is not supported.\MessageBreak
94     by lwarp's HTML conversion.\MessageBreak
95     Class(es) #2 may be useful instead
96 }%
97 {%
98     Class #1 might conflict with lwarp in some way, \MessageBreak
99     or is superceded by another class.\MessageBreak
100    For a possible alternative, see class(es) #2.
101 }%
102 }{}}%
103 }
```

## 20.2 Error for disallowed packages and classes loaded before lwarp

```
104 \LWR@earlyclassloadnever{jarticle}{ujarticle}
105 \LWR@earlyclassloadnever{jbook}{ujbook}
106 \LWR@earlyclassloadnever{jreport}{ujreport}
107 \LWR@earlyclassloadnever{tarticle}{utarticle}
108 \LWR@earlyclassloadnever{tbook}{utbook}
109 \LWR@earlyclassloadnever{treport}{utreport}
110 \LWR@earlyloadnever{ae}{cm-super, lmodern}
111 \LWR@earlyloadnever{aecmpl}{cm-super, lmodern}
112 \LWR@earlyloadnever{aecc}{cm-super, lmodern}
113 \LWR@earlyloadnever{alg}{algorithm2e, algorithmicx}
114 \LWR@earlyloadnever{algorithmic}{algorithm2e, algorithmicx}
115 \LWR@earlyloadnever{bitfield}{bytefield}
116 \LWR@earlyloadnever{boxedminipage}{boxedminipage2e}
117 \LWR@earlyloadnever{caption2}{caption}
118 % \LWR@earlyloadnever{ccaption}{caption} might be preloaded by memoir
119 \LWR@earlyloadnever{colortab}{colortbl}
120 \LWR@earlyloadnever{doublespace}{setspace}
121 \LWR@earlyloadnever{epsf}{graphicx}
122 \LWR@earlyloadnever{fancyheadings}{fancyhdr}
123 \LWR@earlyloadnever{fncylab}{cleveref}
```

```

124 \LWR@earlyloadnever{formula}{siunitx}
125 \LWR@earlyloadnever{glossary}{glossaries}
126 \LWR@earlyloadnever{hyper}{hyperref}
127 \LWR@earlyloadnever{newthm}{ntheorem}
128 \LWR@earlyloadnever{pdfcprot}{microtype}
129 \LWR@earlyloadnever{picinpar}{floatflt, wrapfig}
130 \LWR@earlyloadnever{picsins}{floatflt, wrapfig}
131 \LWR@earlyloadnever{rplain}{fancyhdr}
132 \LWR@earlyloadnever{shadethm}{mdframed}
133 \LWR@earlyloadnever{si}{siunitx}
134 \LWR@earlyloadnever{sistyle}{siunitx}
135 \LWR@earlyloadnever{slashbox}{diagbox}
136 \LWR@earlyloadnever{t1enc}{fontenc, inputenc, inputenx}
137 \LWR@earlyloadnever{ucs}{inputenc, inputencx}
138 \LWR@earlyloadnever{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}

```

The older CJK and CJKutf8 only work with xeCJK:

```

139 \@ifpackageloaded{xeCJK}{}{
140     \LWR@earlyloadnever{CJK}{ctex, xeCJK}
141     \LWR@earlyloadnever{CJKutf8}{ctex, xeCJK}
142 }

```

bxcjkjatype is based on CJK:

```
143 \LWR@earlyloadnever{bxcjkjatype}{upLaTeX, bxjsarticle, ujarticle, utarticle}
```

hangul is not in TeXLive, and is not tested:

```
144 \LWR@earlyloadnever{hangul}{kotex, xetexko, luatexko}
```

### 20.3 Enforcing package loading after l warp

Packages which should only be loaded after l warp are tested here to trip an error if they have already been loaded.

The following packages must be loaded after l warp:

```

145 \LWR@loadafter{2in1}
146 \LWR@loadafter{2up}
147 \LWR@loadafter{a4}
148 \LWR@loadafter{a4wide}
149 \LWR@loadafter{a5comb}
150 \LWR@notmemoirloadafter{abstract}
151 \LWR@loadafter{academicons}
152 \LWR@loadafter{accessibility}
153 \LWR@loadafter{accsupp}
154 \LWR@loadafter{acro}
155 \LWR@loadafter{acronym}
156 \LWR@loadafter{adjmulticol}
157 \LWR@loadafter{addlines}
158 \LWR@loadafter{afterpage}
159 \LWR@loadafter{algorithm2e}
160 \LWR@loadafter{algorithmicx}

```

```
161 \LWR@loadafter{alltt}
162 \LWR@loadafter{amsmath}
163 \LWR@loadafter{amsthm}
164 \LWR@loadafter{anonchap}
165 \LWR@loadafter{any size}
166 \LWR@notmemoirloadafter{appendix}
167 \LWR@loadafter{ar}
168 \LWR@loadafter{arabicfront}
169 \LWR@notmemoirloadafter{array}
170 \LWR@loadafter{arydshln}
171 \LWR@loadafter{asymptote}
172 % \LWR@loadafter{atbegshi}% used by morewrites
173 \LWR@loadafter{attachfile}
174 \LWR@loadafter{attachfile2}
175 \LWR@loadafter{authblk}
176 \LWR@loadafter{autobreak}
177 \LWR@loadafter{autonum}
178 \LWR@loadafter{awesomebox}
179 \LWR@loadafter{axessibility}
180 \LWR@loadafter{axodraw2}
181 \LWR@loadafter{backnaur}
182 \LWR@loadafter{backref}
183 \LWR@loadafter{balance}
184 \LWR@loadafter{bbding}
185 \LWR@loadafter{bigdelim}
186 \LWR@loadafter{bigfoot}
187 \LWR@loadafter{bigstrut}
188 \LWR@loadafter{bitpattern}
189 \LWR@loadafter{blowup}
190 \LWR@loadafter{bm}
191 \LWR@loadafter{booklet}
192 \LWR@loadafter{bookmark}
193 \LWR@notmemoirloadafter{booktabs}
194 \LWR@loadafter{bophook}
195 \LWR@loadafter{bounddvi}
196 \LWR@loadafter{boxedminipage2e}
197 \LWR@loadafter{braket}
198 \LWR@loadafter{breakurl}
199 \LWR@loadafter{breqn}
200 \LWR@loadafter{bsheaders}
201 \LWR@loadafter{bxpapersize}
202 \LWR@loadafter{bytefield}
203 \LWR@loadafter{cancel}
204 \LWR@loadafter{canoniclayout}
205 \LWR@loadafter{caption}
206 \LWR@loadafter{caption2}
207 \LWR@loadafter{cases}
208 % \LWR@loadafter{ccaption}% may be preloaded by memoir
209 \LWR@loadafter{changebar}
210 \LWR@loadafter{changelayout}
211 \LWR@notmemoirloadafter{changepage}
212 \LWR@loadafter{changes}
213 \LWR@loadafter{chappg}
214 \LWR@loadafter{chapterbib}
215 \LWR@loadafter{chemfig}
```

```
216 \LWR@loadafter{chemformula}
217 \LWR@loadafter{chemgreek}
218 \LWR@loadafter{chemmacros}
219 \LWR@loadafter{chemnum}
220 \LWR@loadafter{chkfloat}
221 \LWR@notmemoirloadafter{chngpage}
222 \LWR@loadafter{cite}
223 \LWR@loadafter{cmdtrack}
224 \LWR@loadafter{color}
225 \LWR@loadafter{colortbl}
226 \LWR@loadafter{continue}
227 \LWR@loadafter{copyrightbox}
228 \LWR@notmemoirloadafter{crop}
229 % ctex must be loaded before lwarf
230 \LWR@loadafter{ctable}
231 \LWR@loadafter{cuted}
232 \LWR@loadafter{cutwin}
233 \LWR@loadafter{dblfloatfix}
234 \LWR@loadafter{dblfnote}
235 \LWR@notmemoirloadafter{dcolumn}
236 \LWR@loadafter{diagbox}
237 \LWR@loadafter{dingbat}
238 \LWR@loadafter{dprogress}
239 \LWR@loadafter{draftcopy}
240 \LWR@loadafter{draftfigure}
241 \LWR@loadafter{draftwatermark}
242 \LWR@loadafter{easy-todo}
243 \LWR@loadafter{ebook}
244 \LWR@loadafter{ed}
245 \LWR@loadafter{ellipsis}
246 \LWR@loadafter{embrac}
247 \LWR@loadafter{emptypage}
248 \LWR@loadafter{endfloat}
249 \LWR@loadafter{endheads}
250 \LWR@loadafter{endnotes}
251 \LWR@notmemoirloadafter{enumerate}
252 \LWR@loadafter{enumitem}
253 \LWR@notmemoirloadafter{epigraph}
254 \LWR@loadafter{epsfig}
255 \LWR@loadafter{epstopdf}
256 \LWR@loadafter{epstopdf-base}
257 \LWR@loadafter{eqlist}
258 \LWR@loadafter{eqparbox}
259 \LWR@loadafter{errata}
260 \LWR@loadafter{eso-pic}
261 \LWR@loadafter{eurosym}
262 \LWR@loadafter{everypage}
263 \LWR@loadafter{everyshi}
264 \LWR@loadafter{extarrows}
265 \LWR@loadafter{extramarks}
266 \LWR@loadafter{fancybox}
267 \LWR@loadafter{fancyhdr}
268 \LWR@loadafter{fancyref}
269 \LWR@loadafter{fancytabs}
270 \LWR@loadafter{fancyvrb}
```

```
271 \LWR@loadaft{fewerfloatpages}
272 \LWR@loadaft{figcaps}
273 \LWR@loadaft{figsize}
274 \LWR@loadaft{fitbox}
275 \LWR@loadaft{fix2col}
276 \LWR@loadaft{fixme}
277 \LWR@loadaft{fixmetodonotes}
278 \LWR@loadaft{flafter}
279 \LWR@loadaft{flippdf}
280 \LWR@loadaft{float}
281 \LWR@loadaft{floatflt}
282 \LWR@loadaft{floatpag}
283 \LWR@loadaft{floatrow}
284 \LWR@loadaft{fltrace}
285 \LWR@loadaft{flushend}
286 \LWR@loadaft{fnbreak}
287 \LWR@loadaft{fncychap}
288 \LWR@loadaft{fnlineno}
289 \LWR@loadaft{fnpara}
290 \LWR@loadaft{fnpos}
291 \LWR@loadaft{fontawesome}
292 \LWR@loadaft{fontawesome5}
293 % fontenc must be loaded before lwarf
294 % fontspe must be loaded before lwarf
295 \LWR@loadaft{footmisc}
296 \LWR@loadaft{footnote}
297 \LWR@loadaft{footnotebackref}
298 \LWR@loadaft{footnotehyper}
299 \LWR@loadaft{footnoterange}
300 \LWR@loadaft{footnpag}
301 \LWR@loadaft{foreign}
302 \LWR@loadaft{forest}
303 \LWR@loadaft{fouridx}
304 \LWR@loadaft{framed}
305 \LWR@loadaft{ftcap}
306 \LWR@loadaft{ftnright}
307 \LWR@loadaft{fullminipage}
308 \LWR@loadaft{fullpage}
309 \LWR@loadaft{fullwidth}
310 \LWR@loadaft{fwlw}
311 \LWR@loadaft{gensymb}
312 \LWR@loadaft{gentombow}
313 % geometry is always loaded by lwarf, and lwarf-geometry is AtBeginDocument
314 \LWR@loadaft{ghsystem}
315 \LWR@loadaft{glossaries}
316 \LWR@loadaft{gmeometric}
317 % \LWR@loadaft{graphics}% pre-loaded by xunicode
318 % \LWR@loadaft{graphicx}% pre-loaded by xunicode
319 \LWR@loadaft{gloss}
320 \LWR@loadaft{glossary}
321 \LWR@loadaft{grffile}
322 \LWR@loadaft{grid}
323 \LWR@loadaft{grid-system}
324 \LWR@loadaft{gridset}
325 \LWR@loadaft{hang}
```

```
326 \LWR@loadaft{hanging}
327 \LWR@loadaft{hhline}
328 \LWR@loadaft{hypbmsec}
329 \LWR@loadaft{hypcap}
330 \LWR@loadaft{hypdestopt}
331 \LWR@loadaft{hypernat}
332 \LWR@loadaft{hyperref}
333 \LWR@loadaft{hyperxmp}
334 \LWR@loadaft{hyphenat}
335 \LWR@loadaft{idxlayout}
336 \LWR@loadaft{ifoddpage}
337 \LWR@loadaft{imakeidx}
338 \LWR@notmemoirloadaft{index}
339 % inputenc must be loaded before lwarf
340 % inputenx must be loaded before lwarf
341 % inputtrc may be loaded before lwarf
342 \LWR@loadaft{intopdf}
343 \LWR@loadaft{karnaugh-map}
344 \LWR@loadaft{keyfloat}
345 \LWR@loadaft{layaureo}
346 \LWR@loadaft{layout}
347 \LWR@loadaft{layouts}
348 \LWR@loadaft{leading}
349 \LWR@loadaft{leftidx}
350 \LWR@loadaft{letterspace}
351 \LWR@loadaft{lettrine}
352 \LWR@loadaft{lineno}
353 \LWR@loadaft{lips}
354 \LWR@loadaft{listings}
355 \LWR@loadaft{listliketab}
356 \LWR@loadaft{longtable}
357 \LWR@loadaft{lscape}
358 \LWR@loadaft{ltablex}
359 \LWR@loadaft{ltcaption}
360 \LWR@loadaft{ltxgrid}
361 \LWR@loadaft{ltxtable}
362 \LWR@loadaft{lua-check-hyphen}
363 \LWR@loadaft{lua-visual-debug}
364 \LWR@loadaft{luacolor}
365 \LWR@loadaft{luatodonotes}
366 \LWR@loadaft{lyluatex}
367 \LWR@loadaft{magaz}
368 \LWR@notmemoirloadaft{makeidx}
369 \LWR@loadaft{manyfoot}
370 \LWR@loadaft{marginfit}
371 \LWR@loadaft{marginfix}
372 \LWR@loadaft{marginnote}
373 \LWR@loadaft{marvosym}
374 \LWR@loadaft{mathcomp}
375 \LWR@loadaft{mathfixs}
376 \LWR@loadaft{mathtools}
377 \LWR@loadaft{mcaption}
378 \LWR@loadaft{mdframed}
379 \LWR@loadaft{media9}
380 \LWR@loadaft{memhfixc}
```

```
381 \LWR@loadafter{metalogo}
382 \LWR@loadafter{metalogox}
383 \LWR@loadafter{mhchem}
384 \LWR@loadafter{microtype}
385 \LWR@loadafter{midfloat}
386 \LWR@loadafter{midpage}
387 \LWR@loadafter{minibox}
388 \LWR@loadafter{minitoc}
389 \LWR@loadafter{mismath}
390 % morefloats must be allowed early for print mode
391 \LWR@notmemoirloadafter{moreverb}
392 % morewrites must be loaded before lwarp
393 \LWR@notmemoirloadafter{movie15}
394 \LWR@notmemoirloadafter{mparhack}
395 \LWR@loadafter{multicap}
396 \% \LWR@loadafter{multicol} \% loaded by ltxdoc
397 \LWR@loadafter{multicolrule}
398 \LWR@loadafter{multimedia}
399 \LWR@loadafter{multirow}
400 \LWR@loadafter{multitoc}
401 \LWR@loadafter{musicography}
402 \LWR@loadafter{nameauth}
403 \LWR@loadafter{nameref}
404 \LWR@loadafter{natbib}
405 \LWR@notmemoirloadafter{nccfancyhdr}
406 \LWR@loadafter{nccmath}
407 \LWR@notmemoirloadafter{needspace}
408 % newclue must be loaded before lwarp
409 \LWR@loadafter{newtxmath}
410 % newunicodechar must be loaded before lwarp
411 \LWR@notmemoirloadafter{nextpage}
412 \LWR@loadafter{nicefrac}
413 \LWR@loadafter{niceframe}
414 \LWR@loadafter{noitcrl}
415 \LWR@loadafter{nomencl}
416 \LWR@loadafter{nonfloat}
417 \LWR@loadafter{nonumonpart}
418 \LWR@loadafter{nopageno}
419 \LWR@loadafter{notes}
420 \LWR@loadafter{notespages}
421 \LWR@loadafter{nowidow}
422 \LWR@loadafter{ntheorem}
423 \LWR@loadafter{octave}
424 \LWR@loadafter{overpic}
425 \LWR@loadafter{pagegrid}
426 \LWR@notmemoirloadafter{pagenote}
427 \LWR@loadafter{pagesel}
428 \LWR@loadafter{paralist}
429 \LWR@loadafter{parallel}
430 \LWR@loadafter{parcolumns}
431 \LWR@loadafter{parnotes}
432 \LWR@notmemoirloadafter{parskip}
433 \LWR@loadafter{pbox}
434 \LWR@loadafter{pdfcol}
435 \LWR@loadafter{pdfcolfoot}
```

```
436 \LWR@loadaft{pdfcolmk}
437 \LWR@loadaft{pdfcolparallel}
438 \LWR@loadaft{pdfcolparcolumns}
439 \LWR@loadaft{pdfcomment}
440 \LWR@loadaft{pdfcrypt}
441 \LWR@loadaft{pdflandscape}
442 \LWR@loadaft{pdfmarginpar}
443 \LWR@loadaft{pdfpages}
444 \LWR@loadaft{pdfprivacy}
445 \LWR@loadaft{pdfrender}
446 \LWR@loadaft{pdfsync}
447 \LWR@loadaft{pdftricks}
448 \LWR@loadaft{pdfx}
449 \LWR@loadaft{perpage}
450 \LWR@loadaft{pfnote}
451 \LWR@loadaft{phfqt}
452 \LWR@loadaft{physics}
453 \LWR@loadaft{pifont}
454 \LWR@loadaft{placeins}
455 \LWR@loadaft{plarray}
456 \LWR@loadaft{plarydshln}
457 \LWR@loadaft{plexarray}
458 \LWR@loadaft{plexarydshln}
459 \LWR@loadaft{plcolortbl}
460 \LWR@loadaft{plextdelarray}
461 \LWR@loadaft{prelim2e}
462 \LWR@loadaft{prettyref}
463 \LWR@loadaft{preview}
464 \LWR@loadaft{psfrag}
465 \LWR@loadaft{psfragx}
466 \LWR@loadaft{pst-eps}
467 \LWR@loadaft{pstool}
468 \LWR@loadaft{pstricks}
469 % \LWR@loadaft{pxatbegshi} may be used by morewrites
470 \LWR@loadaft{pxeveryshi}
471 \LWR@loadaft{pxftnright}
472 \LWR@loadaft{pxjahyper}
473 \LWR@loadaft{quotchap}
474 \LWR@loadaft{quoting}
475 \LWR@loadaft{ragged2e}
476 \LWR@loadaft{realscripts}
477 \LWR@loadaft{refcheck}
478 \LWR@loadaft{register}
479 \LWR@loadaft{relsize}
480 \LWR@loadaft{repeatindex}
481 \LWR@loadaft{resizegather}
482 \LWR@loadaft{rmathbr}
483 \LWR@loadaft{rmpage}
484 \LWR@loadaft{romanbar}
485 \LWR@loadaft{romanbarpagenumber}
486 \LWR@loadaft{rotating}
487 \LWR@loadaft{rotfloat}
488 \LWR@loadaft{rviewport}
489 \LWR@loadaft{savetrees}
490 % scalefnt is loaded by babel-french
```

```
491 \LWR@loadafterschemata}
492 \LWR@loadafterscrextend}
493 \LWR@loadafterscrhack}
494 \LWR@loadafterscrlayer}
495 \LWR@loadafterscrlayer-notecolumn}
496 \LWR@loadafterscrlayer-scrpage}
497 \LWR@loadafterscrpage2}
498 \LWR@loadaftersetion}
499 \LWR@loadaftersetionbreak}
500 \LWR@loadaftersetsty}
501 \LWR@loadaftersetantic-markup}
502 \LWR@notmemoirloadaftersetospace}
503 \LWR@loadaftershadow}
504 \LWR@loadaftershapepar}
505 \LWR@notmemoirloadaftershowidx}
506 \LWR@loadaftershowkeys}
507 \LWR@loadaftershowtags}
508 \LWR@loadaftersidecap}
509 \LWR@loadaftersidenotes}
510 \LWR@loadaftersIunits}
511 \LWR@loadaftersiunitx}
512 \LWR@loadafterslantsc}
513 \LWR@loadafterslashed}
514 \LWR@loadaftersoul}
515 \LWR@loadaftersoulpos}
516 \LWR@loadaftersoulutf8}
517 \LWR@loadaftersplitidx}
518 \LWR@loadaftersrcctx}
519 \LWR@loadaftersrctex}
520 \LWR@loadaftersstabular}
521 \LWR@loadaftersstackengine}
522 \LWR@loadaftersteinmetz}
523 \LWR@notltjloadaftersstfloats}
524 \LWR@loadaftersstruktex}
525 \LWR@loadaftersubcaption}
526 \LWR@loadaftersubfig}
527 \LWR@loadaftersubfigure}
528 \LWR@loadaftersubsupscripts}
529 \LWR@loadaftersupertabular}
530 \LWR@loadaftersvg}
531 \LWR@loadaftert1inc}
532 \LWR@loadaftertabfigures}
533 \LWR@loadaftertabls}
534 \LWR@loadaftertablefootnote}
535 \LWR@notmemoirloadaftertabularx}
536 \LWR@loadaftertabulary}
537 \LWR@loadaftertascmac}
538 \LWR@loadaftertextarea}
539 % \LWR@loadaftertextcomp% maybe before lwarp with font packages
540 \LWR@loadaftertextfit}
541 \LWR@loadaftertextpos}
542 \LWR@loadaftertextorem}
543 \LWR@loadaftertextinsp}
544 \LWR@loadaftertexthreadcol}
545 \LWR@loadaftertextrepartable}
```

```
546 \LWR@loadaft{threeparttablex}
547 \LWR@loadaft{thumb}
548 \LWR@loadaft{thumbs}
549 \LWR@loadaft{tikz}
550 \LWR@loadaft{titleps}
551 \LWR@loadaft{titlesec}
552 \LWR@loadaft{titletoc}
553 \LWR@notmemoirloadaft{titling}
554 % \LWR@loadaft{tocbasic}% preloaded by koma-script classes
555 \LWR@notmemoirloadaft{tocbibind}
556 \LWR@loadaft{tocdata}
557 \LWR@loadaft{toccenter}
558 \LWR@notmemoirloadaft{tocloft}
559 \LWR@loadaft{tocstyle}
560 \LWR@loadaft{todo}
561 \LWR@loadaft{todonotes}
562 \LWR@loadaft{topcapt}
563 \LWR@loadaft{tram}
564 \LWR@loadaft{transparent}
565 \LWR@loadaft{trimclip}
566 \LWR@loadaft{trivfloat}
567 \LWR@loadaft{truncate}
568 \LWR@loadaft{turnthepage}
569 \LWR@loadaft{twoup}

570 % \LWR@loadaft{typearea}% preloaded by koma-script classes
571 \LWR@loadaft{typicons}
572 % \LWR@loadaft{ulem}% preloaded by ctexart and related classes
573 \LWR@loadaft{umoline}
574 \LWR@loadaft{underscore}
575 \LWR@loadaft{unicode-math}
576 \LWR@loadaft{units}
577 \LWR@loadaft{unitsdef}
578 \LWR@loadaft{upref}
579 \LWR@loadaft{url}
580 \LWR@loadaft{uspace}
581 \LWR@loadaft{variorref}% no lwarf package provided
582 \LWR@notmemoirloadaft{verse}
583 \LWR@loadaft{versonotes}
584 \LWR@loadaft{vertbars}
585 \LWR@loadaft{vmargin}
586 \LWR@loadaft{vowel}
587 \LWR@loadaft{vpe}
588 \LWR@loadaft{vwcol}
589 \LWR@loadaft{wallpaper}
590 \LWR@loadaft{watermark}
591 \LWR@loadaft{widetable}
592 \LWR@loadaft{widows-and-orphans}
593 \LWR@loadaft{witharrows}
594 \LWR@loadaft{wrapfig}
595 \LWR@loadaft{xbmks}
596 \LWR@loadaft{xcolor}
597 \LWR@loadaft{xexchangebar}
598 \LWR@loadaft{xellipsis}
599 % xetexko-vertical must be loaded before lwarf
```

---

```

600 \LWR@loadaft{xfakebold}
601 \LWR@loadaft{xfrc}
602 \LWR@loadaft{xltabular}
603 \LWR@loadaft{xltxt}
604 \LWR@loadaft{xmpincl}
605 \LWR@loadaft{xpiano}
606 \LWR@loadaft{xpinyin}
607 \LWR@loadaft{xr}
608 \LWR@loadaft{xr-hyper}
609 \LWR@loadaft{xtab}
610 % xunicode must be loaded before lwarp
611 \LWR@loadaft{xurl}
612 \LWR@loadaft{xy}
613 \LWR@loadaft{zwpagelayout}

```

## 21 MD5 hashing

The MD5 hash is used for `lateximage` filenames for SVG math.

```

614 \newcommand{\LWR@mdfive}[1]{%
615 \PackageError{lwarp}%
616 {No MD5 macro was found}%
617 {Lwarp must find the macros pdfmdfivesum or mdfivesum.}%
618 }

```

The default for `pdfLATEX`, `DVILATEX`, `upLATEX`, etc:

```
619 \let\LWR@mdfive\pdfmdfivesum
```

For `LuaLATEX`:

```

620 \ifLuaTeX
621 \RequirePackage{pdftexcmds}
622 \let\LWR@mdfive\pdf@mdfivesum
623 \fi

```

For `XeLATEX`:

```

624 \ifXeTeX
625 \@ifundefined{pdffivesum}{}%
626   {\let\LWR@mdfive\pdfmdfivesum}%
627 \@ifundefined{mdfivesum}{}%
628   {\let\LWR@mdfive\mdfivesum}%
629 \fi

```

## 22 pdfLATEX T1 and UTF-8 encoding

When using `pdfLATEX`, `lwarp` requires T1 font encoding, and recommends UTF-8 input encoding.

If some other input encoding is already defined, l warp will try to use it instead, and hope for the best.

X E L A T E X and L u a L A T E X are both U T F - 8 by nature.

\ L W R @ p d f e n c o d i n g Sets T 1 , and also u t f 8 if not already set.

```

630 \newcommand*{\LWR@pdfencoding}{%
631     \RequirePackage[T1]{fontenc}
632
633     \@ifpackageloaded{inputenc}{}{%
634         \@ifpackageloaded{inputenx}{}{%
635             \RequirePackage[utf8]{inputenc}
636         }%
637     }%
638 }

639 \ifPDFTeX% pdflatex or dvi latex
640     \LWR@pdfencoding
641 \fi
642
643 \ifpTeX
644     \LWR@pdfencoding
645 \fi

```

## 23 Unicode input characters

**for HTML & PRINT:** If using *pdflatex*, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be \texttt{times}.

The first arguments of \newunicodechar below are text ligatures in the source code, even though they are not printed in the following listing.

```

646 \ifpTeX
647 \else
648 \RequirePackage{newunicodechar}
649
650 \newunicodechar{x}{\texttimes}
651
652 \ifPDFTeX% pdflatex or dvi latex
653 \newunicodechar{ff}{ff}% Here, the first arguments are ligatures.
654 \newunicodechar{fi}{fi}
655 \newunicodechar{fl}{fl}
656 \newunicodechar{ffi}{ffi}
657 \newunicodechar{ffl}{ffl}
658 \newunicodechar{--}{--}
659 \newunicodechar{--}{--}
660 \fi
661
662 \fi

```

## 24 Avoid a bitmapped font

If DVI or PDF L<sup>A</sup>T<sub>E</sub>X, and if the default Computer Modern is the selected font family, ensure that cm-super or lmodern is used to provide a vector font.

```

663 \ifxetexorluatex
664 \else
665   \ifdefstring{\f@family}{cmr}{
666     \IfFileExists{type1ec.sty}{% found in cm-super
667     {}%
668     {% cm-super not installed
669       \IfFileExists{lmodern.sty}{%
670         \PackageInfo{l warp}{cm-super not installed, loading lmodern}
671         \RequirePackage{lmodern}%
672       }%
673       \PackageError{l warp}%
674       {%
675         L warp requires a vector font.\MessageBreak
676         Install and load cm-super, lmodern, or another\MessageBreak
677         Type-1 vector font before loading l warp%
678       }%
679       {%
680         Install cm-super or lmodern.\MessageBreak
681         If lmodern, load it before l warp:\MessageBreak
682           \space\space\protect\usepackage{lmodern}\MessageBreak
683           \space\space\protect\usepackage{l warp}%
684       }%
685     }%
686     }% cm-super not installed
687   }{}% f@family
688 \fi

```

## 25 Upright quotes

In PDFTEX, preserve upright quotes in verbatim text. upquote also loads textcomp.

```

689 \ifPDFTeX
690 \RequirePackage{upquote}
691 \fi
692
693 \ifpTeX
694   \RequirePackage{upquote}
695 \fi

```

## 26 Miscellaneous tools

### 26.1 Lengths and units

\LWR@providelength {⟨lengthname⟩} Provides the length if it isn't defined yet.

Used to provide source compatibility for lengths which will be ignored, but might or might not be already provided by other packages.

```
696 \newcommand*\LWR@providelength[1]{%
697     \ifdefined\length{#1}{\newlength{#1}}%
698 }
```

\LWR@convertto {⟨dest unit⟩} {⟨length⟩}

Prints a length in the given units, without printing the unit itself.

```
699 \newcommand*{\LWR@convertto}[2]{\strip@pt\dimexpr #2*65536/\number\dimexpr 1#1}
```

\LWR@printpercentlength {⟨smaller⟩} {⟨larger⟩}

Prints a percent ratio of the two lengths.

```
700 \newcommand*{\LWR@printpercentlength}[2]{%
701     \setcounter{\LWR@tempcountone}{100*\ratio{#1}{#2}}%
702     \arabic{\LWR@tempcountone}%
703 }
```

### 26.2 Counters

\defaddtocounter {⟨name⟩} {⟨value⟩}

Locally add to a counter.

```
704 \providecommand*{\defaddtocounter}[2]{%
705     \defcounter{#1}{\value{#1}+#2}%
706 }
```

### 26.3 Patching

\LWR@patcherror {⟨packagename⟩} {⟨macroname⟩}

Prints an error if could not patch a macro.

```
707 \newcommand*{\LWR@patcherror}[2]{%
708 \PackageError{lwarp}{%
709 {Unable to patch package #1, macro #2}%
710 {Please contact the author of the Lwarp package.}%
711 }}
```

## 26.4 Chinese text isolation

\LWR@isolate {*text*} Isolates Chinese characters from the surrounding text. This is required to avoid extra spaces on either side of the Chinese characters, especially when written to a file.

```

712 \newcommand{\LWR@isolate}[1]{#1}%
713 @ifpackageloaded{ctexpatch}{%
714   \renewcommand{\LWR@isolate}[1]{\null#1\null}%
715 }{}%
716 }{}%
717 @ifpackageloaded{xeCJK}{%
718   \renewcommand{\LWR@isolate}[1]{\null#1\null}%
719 }{}%
720 }{}%
```

## 26.5 Inserting vertical space

\LWR@forceemptyline Extra vertical space in the HTML output. Use after \LWR@stopars.

```

721 \newcommand*{\LWR@forceemptyline}{%
722   \LWR@origrule{0pt}{1\baselineskip}%
723   \LWR@orignewline%
724 }
```

## 26.6 Argument selection

\LWR@firstoffour {*first*} {*second*} {*third*} {*fourth*}

\LWR@secondoffour {*first*} {*second*} {*third*} {*fourth*}

\LWR@thirdoffour {*first*} {*second*} {*third*} {*fourth*}

\LWR@fourthoffour {*first*} {*second*} {*third*} {*fourth*}

Expands to the nth of the four arguments. Used for extra cross referencing.

```

725 \long\def\LWR@firstoffour#1#2#3#4{#1}%
726 \long\def\LWR@secondoffour#1#2#3#4{#2}%
727 \long\def\LWR@thirdoffour#1#2#3#4{#3}%
728 \long\def\LWR@fourthoffour#1#2#3#4{#4}
```

## 26.7 Global boxes

\LWR@gsavebox {*macroname*} {*contents*}

From <https://tex.stackexchange.com/questions/288702/savebox-forgets-its-content-across-columns-inside-align>

```

729 \DeclareRobustCommand{\LWR@gsavebox}[1]{%
730   \@ifnextchar(%)
731     {\LWR@gsavepicbox#1}{\@ifnextchar[{\LWR@gsavebox#1}{\LWR@gsbox#1}}}
732 \long\def\LWR@gsbox#1#2{\global\setbox#1\hbox{%
733   \color@setgroup#2\color@endgroup}}
734 \def\LWR@gsavebox#1[#2]{%
735   \@ifnextchar [{\LWR@igsavebox#1[#2]}{\LWR@igsavebox#1[#2][c]}}
736 \long\def\LWR@igsavebox#1[#2][#3]{%
737   \LWR@gsbox#1{\imakebox[#2][#3]{#4}}}
738 \def\LWR@gsavepicbox#1(#2,#3){%
739   \@ifnextchar[%]
740     {\LWR@igsavepicbox#1(#2,#3)}{\LWR@igsavepicbox#1(#2,#3)[[]]}}
741 \long\def\LWR@igsavepicbox#1(#2,#3)[#4]{%
742   \LWR@gsbox#1{\imakepicbox(#2,#3)[#4]{#5}}}

Env \LWR@glrbox {\langle macroname\rangle}

743 \def\LWR@glrbox#1{%
744   \edef\reserved@a{%
745     \endgroup
746     \global\setbox#1\hbox{%
747       \begingroup\aftergroup}%
748       \def\noexpand\@currenvir{\currenvir}%
749       \def\noexpand\@currenvline{\on@line}%
750     \reserved@a
751     \endpfalse
752     \color@setgroup
753     \ignorespaces}
754 \let\LWR@endglrbox\LWR@endlrbox

```

## 26.8 Converting a macro name to a cs name

\macro{csname} {\langle macro name with backslash\rangle}

Results in the macro name without the leading backslash.

Ref: <https://tex.stackexchange.com/questions/42318/removing-a-backslash-from-a-character-sequence>

```

755 \newcommand*{\macro{csname}}[1]{%
756   \ifcat\relax\noexpand#1%
757     \expandafter\expandafter\expandafter\@gobble\expandafter\string
758   \fi
759   #1%
760 }

```

## 27 Operating-System portability

Prog Unix lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX

Prog Mac OS

Prog Linux

is the default (collectively referred to as “UNIX” in the configuration files), and MS-WINDOWS is supported as well.

Prog MS-Windows If MS-WINDOWS is not correctly detected, use the `lwarp` option `OSWindows`.

Prog Windows When detected or specified, the operating-system path separator used by `lwarp` is modified, and the boolean `usingOSWindows` is set true. This boolean may be tested by the user for later use.

## 27.1 Literal characters

Literal characters to be used in `PrintLatexCmd` and `HTMLLatexCmd`. These are defined without @ to easily allow their inclusion in the user’s document.

The literal % character:

761 \let\LWRpercent\@percentchar

The literal \$ character:

762 \catcode`\\$=12  
763 \def\LWRdollar{\\$}  
764 \catcode`\\$=3

The literal & character:

765 \catcode`\&=12  
766 \def\LWRamp{\&}  
767 \catcode`\&=4

The literal \ character. The ampersand is temporarily set to the escape character during the definition of the backslash macro.

768 \catcode`\&=0  
769 &\catcode`\&=12  
770 &\def&\LWRbackslash{\}  
771 &\catcode`\&=0  
772 \catcode`\&=4

The literal { character. The ampersand is temporarily set to the begin group character during the definition of the leftbrace macro.

773 \catcode`\&=1  
774 \catcode`\{=12  
775 \def\LWRleftbrace&{  
776 \catcode`\{=1  
777 \catcode`\&=4

The literal } character. The ampersand is temporarily set to the end group character during the definition of the leftbrace macro.

778 \catcode`\&=2

---

```
779 \catcode`}=12
780 \def\LWRrightbrace{}&
781 \catcode`}=2
782 \catcode`\&=4
```

The literal # character:

```
783 \catcode`\#=12
784 \def\LWRhash{#}
785 \catcode`\#=6
```

\LWRopquote The operating system's quote mark, UNIX default. For WINDOWS, see \LWR@setOSWindows, below.

```
786 \def\LWRopquote{'}
```

\LWRopseq The operating system's sequential execution command, UNIX default. For WINDOWS, see \LWR@setOSWindows, below.

```
787 \def\LWRopseq{\space\LWRamp\LWRamp\space\space}
```

## 27.2 Common portability code

Bool usingOSWindows Set if the OSWindows option is used, or if WINDOWS is automatically detected.

```
788 \newbool{usingOSWindows}
789 \boolfalse{usingOSWindows}
```

## 27.3 UNIX, LINUX, and MAC OS

\OSPathSymbol Symbol used to separate directories in a path.

```
790 \newcommand*{\OSPathSymbol}{/}
```

## 27.4 MS-WINDOWS

For MS-WINDOWS:

\LWR@setOSWindows Set defaults for the MS-WINDOWS operating system. lwarp attempts to auto-detect the operating system, and the OSWindows option may also be used to force MS-WINDOWS compatibility.

```
791 \newcommand*{\LWR@setOSWindows}
792 {
793 \booltrue{usingOSWindows}
794 \renewcommand*{\OSPathSymbol}{\@backslashchar}
```

---

```
795 \def\LWRopquote{"
796 \def\LWRopseq{\space\LWRamp\space\space}
797 }
```

Test for windows during compile. The user may also specify OSWindows package option in case this test fails.

```
798 \ifwindows
799 \LWR@setOSWindows
800 \fi
```

## 28 Package options

Pkg kvoptions Allows key/value package options.

```
801 \RequirePackage{kvoptions}
802 \SetupKeyvalOptions{family=LWR,prefix=LWR@}
```

\l warpsetup A user interface to set the keys:

```
803 \newcommand{\l warpsetup}[1]{\setkeys{LWR}{#1}}
```

Bool warpingprint

Bool warpingHTML

Bool mathjax

Bool LWR@origmathjax

Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax.

LWR@origmathjax remembers the original setting to be restored by \displaymathnormal.

```
804 \newbool{warpingprint}
805 \newbool{warpingHTML}
806 \newbool{mathjax}
807 \newbool{LWR@origmathjax}
```

**defaults** The default is print output, and SVG math if the user chose HTML output.

```
808 \booltrue{warpingprint}%
809 \boolfalse{warpingHTML}%
810 \boolfalse{mathjax}%
```

Opt warpprint If the warpprint option is given, boolean warpingprint is true and boolean warpingHTML is false, and may be used for \ifbool tests.

```
811 \DeclareVoidOption{warpprint}{%
812 \PackageInfo{l warp}{Using option 'warpprint'}%
813 \booltrue{warpingprint}%
814 \boolfalse{warpingHTML}%
815 }
```

Opt warpHTML Anything in the warpHTML environment will be generated for HTML output only.

Opt warpHTML If the warpHTML option is given, boolean warpingHTML is true and boolean warpingprint is false, and may be used for \ifbool tests.

```
816 \DeclareVoidOption{warpHTML}{%
817 \PackageInfo{lwarp}{Using option 'warpHTML'}%
818 \booltrue{warpingHTML}%
819 \boolfalse{warpingprint}%
820 }
```

Opt mathsvg Option mathsvg selects SVG math display: If the mathsvg option is given, boolean mathjax is false, and may be used for \ifbool tests.

```
821 \DeclareVoidOption{mathsvg}{%
822 \PackageInfo{lwarp}{Using option 'mathsvg'}%
823 \boolfalse{mathjax}%
824 \boolfalse{LWR@origmathjax}%
825 }
```

Opt mathjax Option mathjax selects MATHJAX math display: If the mathjax option is given, boolean mathjax is true, may be used for \ifbool tests.

```
826 \DeclareVoidOption{mathjax}{%
827 \PackageInfo{lwarp}{Using option 'mathjax'}%
828 \booltrue{mathjax}%
829 \booltrue{LWR@origmathjax}%
830 }
```

Opt BaseJobname Option BaseJobname sets the \BaseJobname for this document.

Default: \jobname

This is the \jobname of the printed version, even if currently compiling the HTML version. I.e. this is the \jobname without \_html appended. This is used to set \HomeHTMLFilename if the user did not provide one.

```
831 \DeclareStringOption[\jobname]{BaseJobname}
```

Opt ImagesDirectory Option ImagesDirectory sets the name of the directory to use for the lateximage images.

Default: \jobname-images

```
832 \DeclareStringOption[\BaseJobname-images]{ImagesDirectory}
```

Opt ImagesName Option ImagesName sets the prefix to use for the lateximage images.

Default: image-

```
833 \DeclareStringOption[image-]{ImagesName}
```

Opt makeindexStyle Selects a custom .ist file. A customized file should be based on lwarp.ist, and must retain the lines related to \hyperindexref.

Default: lwarp.ist

```
834 \DeclareStringOption[lwarp.ist]{makeindexStyle}
```

Opt `xindyStyle` Selects a custom .xdy file. A customized file should be based on `lwarf.xdy`, and must retain the line  
 Default: `lwarf.xdy`

```
(markup-locref :open "\hyperindexref{" :close "}")
```

```
835 \DeclareStringOption[lwarf.xdy]{xindyStyle}
```

Opt `xindyLanguage` Sets the `xindy` language to be assigned in `lwarpmk`'s configuration files. This is then used by `lwarpmk` while processing the index and glossary.  
 Default: `english`

```
836 \DeclareStringOption[english]{xindyLanguage}
```

Opt `xindyCodepage` Sets the `xindy` codepage to be assigned in `lwarpmk`'s configuration files. This is then used by `lwarpmk` while processing the index.  
 Default: `utf8`

```
837 \DeclareStringOption[utf8]{xindyCodepage}
```

Opt `pdftotextEnc` The option `pdftotextEnc` sets the encoding used by `pdftotext`. This is passed to `pdftotext` using its `-enc` option, and is used when converting L<sup>A</sup>T<sub>E</sub>X PDF output with HTML tags into a plain-text file with HTML tags.  
 Default: `UTF-8`

```
838 \DeclareStringOption[UTF-8]{pdftotextEnc}
```

Opt `lwarpmk` Tells `lwarf` to generate a local copy of `lwarpmk` called `lwarpmk.lua`. Useful for archiving for future use. This file may be made executable and acts just like `lwarpmk`.

If `lwarpmk` option, creates a local copy of `lwarpmk.lua`:

```
839 \newbool{LWR@creatinglwarpmk}
840 \boolfalse{LWR@creatinglwarpmk}
841
842 \DeclareVoidOption{lwarpmk}{}
843 \PackageInfo{lwarf}{Using option 'lwarpmk'}
844 \booltrue{LWR@creatinglwarpmk}
845 }
```

Opt `OSWindows` Tells `lwarf` to use MS-WINDOWS compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated `lwarpmk.conf` file to find out whether the operating system was detected correctly.

```
846 \DeclareVoidOption{OSWindows}{}
847 \PackageInfo{lwarf}{Using option 'OSWindows'}
848 \LWR@setOSWindows
849 }
```

Opt `HomeHTMLFilename` The filename of the homepage. The default is the jobname. This option is stored into `\LWR@HomeHTMLFilename`, and later transferred into `\HomeHTMLFilename` for internal use.  
 Default: `\BaseJobname`

```
850 \DeclareStringOption[]{}{HomeHTMLFilename}
```

Opt	HTMLFilename	The filename prefix of web pages after the homepage. The default is empty, no prefix. This option is stored into \LWR@HTMLFilename, and later transferred into \HTMLFilename for internal use.
	Default: <empty>	
		851 \DeclareStringOption[]\{HTMLFilename\}
Opt	PrintLatexCmd	The shell commands to use to compile the print document.
	Default: <automatic>	
		852 \DeclareStringOption[]\{PrintLatexCmd\}
Opt	HTMLLatexCmd	The shell commands to use to compile the HTML document.
	Default: <automatic>	
		853 \DeclareStringOption[]\{HTMLLatexCmd\}
Opt	PrintIndexCmd	The shell commands to use to compile the print indexes.
	Default: <empty>	
		854 \DeclareStringOption[]\{PrintIndexCmd\}
Opt	HTMLIndexCmd	The shell commands to use to compile the HTML indexes.
	Default: <empty>	
		855 \DeclareStringOption[]\{HTMLIndexCmd\}
Opt	LatexmkIndexCmd	The shell commands to be used by <i>latexmk</i> to compile the print indexes. Unlike PrintIndexCmd and HTMLIndexCmd, LatexmkIndexCmd does not include the filename, which will be provided by <i>latexmk</i> .
	Default: <empty>	
		856 \DeclareStringOption[]\{LatexmkIndexCmd\}
Opt	makeindex	Tells <b>lwarp</b> to use <b>makeindex</b> for index generation. When <b>lwarpmk.conf</b> and <b>*.lwarpmkconf</b> are generated, PrintIndexCmd and HTMLIndexCmd will be set for <b>makeindex</b> with a single index file.
		857 \DeclareBoolOption[false]\{makeindex\}
Opt	xindy	Tells <b>lwarp</b> to use <b>xindy</b> for index generation. When <b>lwarpmk.conf</b> and <b>*.lwarpmkconf</b> are generated, PrintIndexCmd and HTMLIndexCmd will be set for <b>xindy</b> with a single index file.
		858 \DeclareBoolOption[false]\{xindy\}
Opt	GlossaryCmd	The shell command to use to compile the glossary. The print or HTML version of the glossary filename will be appended to this command.
	Default: <b>makeglossaries</b>	
		859 \DeclareStringOption[makeglossaries]\{GlossaryCmd\}
Opt	latexmk	Option <b>latexmk</b> tells <b>lwarpmk</b> to use <b>latexmk</b> when compiling documents.
		860 \DeclareBoolOption[false]\{latexmk\}

Opt dvips Option dvips tells *lwarfmk* to use *dvips* when compiling DVI *latex* documents.

```
861 \DeclareBoolOption[false]{dvips}
```

Opt dvipdfm Option dvipdfm tells *lwarfmk* to use *dvipdfm* when compiling DVI *latex* documents.

```
862 \DeclareBoolOption[false]{dvipdfm}
```

Opt dvipdfmx Option dvipdfmx tells *lwarfmk* to use *dvipdfmx* when compiling DVI *latex* documents.

```
863 \DeclareBoolOption[false]{dvipdfmx}
```

**Execute options** Execute the package options, with the defaults which have been set just above:

```
864 \ProcessKeyvalOptions*\relax
```

## 28.1 Additional options support

Assign the \BaseJobname if the user hasn't provided one:

```
865 \providecommand*{\BaseJobname}{\LWR@BaseJobname}
```

Defaults unless already over-ridden by the user:

```
866 \ifcsempty{\LWR@HomeHTMLFilename}{
867   \newcommand*{\HomeHTMLFilename}{\BaseJobname}
868 }{
869   \csedef{HomeHTMLFilename}{\LWR@HomeHTMLFilename}
870 }
871
872 \csedef{HTMLFilename}{\LWR@HTMLFilename}
```

Special handling for underscores in labels and filenames.

\LWR@sanitized The sanitized version of what was given to \LWR@sanitize. Characters are set to their detokenized versions. Required for underscores in labels and filenames.

```
873 \newcommand*{\LWR@sanitized}{}%
```

\LWR@sanitize {<text>}

Sanitizes the text and returns the result in \LWR@sanitized.

```
874 \newcommand*{\LWR@sanitize}[1]{
875   \edef\LWR@sanitized{\detokenize\expandafter{\LWR@sanitized}}%
876 }
877 }
```

Sanitize some string options to neutralize underscores.

```

878 \LWR@sanitize{\LWR@BaseJobname}
879 \edef\LWR@BaseJobname{\LWR@sanitized}
880
881 \LWR@sanitize{\LWR@ImagesDirectory}
882 \edef\LWR@ImagesDirectory{\LWR@sanitized}
883
884 \LWR@sanitize{\LWR@ImagesName}
885 \edef\LWR@ImagesName{\LWR@sanitized}
```

\LWR@PrintIndexCmd and \LWR@HTMLIndexCmd are tested to see if they are empty. If so, they are set to a reasonable defaults for a single index using *makeindex*, then possibly set to defaults for *xindy* if the **lwarp xindy** option was selected.

```

886 \ifdefempty{\LWR@PrintIndexCmd}%
887   \renewcommand{\LWR@PrintIndexCmd}{%
888     makeindex -s \LWR@makeindexStyle \space \jobname.idx%
889   }
890   \ifbool{\LWR@xindy}{%
891     \renewcommand{\LWR@PrintIndexCmd}{%
892       xindy
893       -M \LWR@xindyStyle \space
894       -L \LWR@xindyLanguage \space
895       -C \LWR@xindyCodepage \space
896       \jobname.idx%
897     }
898   }{}
899 }{}%
900
901 \ifdefempty{\LWR@HTMLIndexCmd}%
902   \renewcommand{\LWR@HTMLIndexCmd}{%
903     makeindex -s \LWR@makeindexStyle \space \jobname_html.idx%
904   }
905   \ifbool{\LWR@xindy}{%
906     \renewcommand{\LWR@HTMLIndexCmd}{%
907       xindy
908       -M \LWR@xindyStyle \space
909       -L \LWR@xindyLanguage \space
910       -C \LWR@xindyCodepage \space
911       \jobname_html.idx%
912     }
913   }{}
914 }{}%
915
916 \ifdefempty{\LWR@LatexmkIndexCmd}%
917   \renewcommand{\LWR@LatexmkIndexCmd}{%
918     makeindex -s \LWR@makeindexStyle%
919   }
920   \ifbool{\LWR@xindy}{%
921     \renewcommand{\LWR@LatexmkIndexCmd}{%
922       xindy
923       -M \LWR@xindyStyle \space
924       -L \LWR@xindyLanguage \space
925       -C \LWR@xindyCodepage%
```

```
926      }
927  }{ }
928 }{ }
```

## 28.2 Conditional compilation

\warpprintonly {*contents*}

Only process the contents if producing printed output.

```
929 \newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{}}
```

\warpHTMLonly {*contents*}

Only process the contents if producing HTML output.

```
930 \newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{}}
```

Pkg comment Provides conditional code blocks.

Attempts to use **versions** or **verbatim** fail in some cases, and do not provide much of a speed benefit even when they do work.

```
931 \RequirePackage{comment}
```

Use **comment\_print.cut** for print mode, and **comment\_html.cut** for HTML mode. This helps **latexmk** to more reliably know whether to recompile.

```
932 \ifbool{warpingHTML}{
933   \def\DefaultCutFileName{\def\CommentCutFile{comment_html.cut}}
934 }{ }
935
936 \ifbool{warpingprint}{
937   \def\DefaultCutFileName{\def\CommentCutFile{comment_print.cut}}
938 }{ }
```

Env warpall Anything in the **warpall** environment will be generated for print or HTML outputs.

```
939 \includecomment{warpall}
```

Env warpHTML For HTML output:

```
940 \ifbool{warpingHTML}%
941   {\includecomment{warpHTML}}%
942   {\excludecomment{warpHTML}}%
```

Env warpprint Anything in the **warpprint** environment will be generated for print output only.

```
943 \ifbool{warpingprint}
```

---

```
944     {\includecomment{warpprint}}
945     {\excludecomment{warpprint}}
```

Env `warpMathJax` Only if MATHJAX is being used along with HTML.

```
946 \begin{warpprint}
947 \excludecomment{warpMathJax}
948 \end{warpprint}
949
950 \begin{warpHTML}
951 \ifbool{mathjax}
952     {\includecomment{warpMathJax}}
953     {\excludecomment{warpMathJax}}
954 \end{warpHTML}
```

Env `LWR@creatinglwarpmk` Optionally generate a local copy of *lwarpmk*. Default to no.

```
955 \ifbool{LWR@creatinglwarpmk}
956     {\includecomment{LWR@createlwarpmk}}
957     {\excludecomment{LWR@createlwarpmk}}
```

## 29 Required packages

These packages are automatically loaded by l warp when generating HTML output. Some of them are also automatically loaded when generating print output, but some are not.

**for HTML output:** 958 `\begin{warpHTML}`

Load `fontspec` if necessary:

```
959 \ifxetexorluatex
960 \@ifpackageloaded{fontspec}{}{
961     \usepackage[no-math]{fontspec}
962 }
```

The monospaced font is used for HTML tags, so turn off its TeX ligatures and common ligatures:

```
963 \defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
964 \defaultfontfeatures[\sfamily]{Ligatures={NoCommon,TeX}}
965 \defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
966 \else
```

***pdflatex* only:** Only pre-loaded if *pdflatex* is being used.

Pkg `microtype`

**ligatures** Older browsers don't display ligatures. Turn off letter ligatures, keeping LATEX dash

---

and quote ligatures, which may fail on older browsers but at least won't corrupt written words.

```

967 \RequirePackage {microtype}
968
969 \microtypesetup{
970     protrusion=false,
971     expansion=false,
972     tracking=false,
973     kerning=false,
974     spacing=false}
975
976 \DisableLigatures[f,q,t,T,Q]{encoding = *,family = *}

977 \fi

978 \end{warpHTML}
```

Pkg `geometry` Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

**for HTML output:** 979 `\begin{warpHTML}`

If `geometry` has not yet been loaded, use the preexisting page and text sizes to be preserved for later reuse. These will be replaced by `lwarp \AtBeginDocument` with a very large page size to reduce HTML tag overflow off the page.

```

980 \@ifpackageloaded{geometry}
981 {}{
982     \RequirePackage[
983         reset,
984         paperwidth=\paperwidth,
985         paperheight=\paperheight,
986         textwidth=\textwidth,
987         textheight=\textheight,
988         left=\oddsidemargin,
989         top=\topmargin,
990         marginparsep=\marginparsep,
991         marginparwidth=\marginparwidth,
992     ]{geometry}
993 }
```

Remember the original definitions for later reuse. If the `geometry` package is loaded by the user, `lwarp-geometry` will nullify the user-level originals.

---

```

994 \LetLtxMacro{\LWR@origgeometry}{\geometry}
995 \LetLtxMacro{\LWR@orignewgeometry}{\newgeometry}
996 \LetLtxMacro{\LWR@origrestoregeometry}{\restoregeometry}
997 \LetLtxMacro{\LWR@origsavegeometry}{\savegeometry}
998 \LetLtxMacro{\LWR@origloadgeometry}{\loadgeometry}

```

**Bool** `LWR@allowanothergeometry` **geometry** may be loaded by the user before `l warp`, after `l warp`, or not at all. If before `l warp`, it will have already been loaded by now and its page layout has already been saved. If `geometry` is loaded after `l warp`, its layout will be set at that time and the user macros nullified. `\AtEndPreamble` this layout will be saved. If the user never loads `geometry`, `l warp-geometry` will be loaded `\AtBeginDocument`, but it should not change the page layout set here. This is controlled by the boolean `LWR@allowanothergeometry`. Geometry may be adjusted throughout the preamble until `\AtEndPreamble`, when this boolean is set false.

```

999 \newbool{LWR@allowanothergeometry}
1000 \booltrue{LWR@allowanothergeometry}

```

Use `\AtEndPreamble` to avoid class and option conflict by changing settings after other packages load, instead of using `geometry` package options:

```
1001 \AtEndPreamble{
```

Whatever geometry choices the user has made in the preamble, either before or after `l warp` was loaded, are now saved for possible temporary reuse, such as by `lyluatex`.

See the `l warp-geometry` section for what happens if `geometry` is loaded after `l warp`.

```
1002 \LWR@origsavegeometry{\LWR@usergeometry}
```

The user's paper size is saved for later reuse, such as by the `pdfpages` or `parallel` packages.

```

1003 \newlength{\LWR@userspaperwidth}
1004 \setlength{\LWR@userspaperwidth}{\paperwidth}
1005
1006 \newlength{\LWR@userspaperheight}
1007 \setlength{\LWR@userspaperheight}{\paperheight}
1008
1009 \newlength{\LWR@usersmarginparwidth}
1010 \setlength{\LWR@usersmarginparwidth}{\marginparwidth}
1011
1012 \newlength{\LWR@userstextwidth}
1013 \setlength{\LWR@userstextwidth}{\textwidth}
1014
1015 \newlength{\LWR@userstextheight}
1016 \setlength{\LWR@userstextwidth}{\textheight}

```

For `l warp`, use a very large page and margins to help avoid letting HTML tags run off the edge:

```

1017 \LWR@origgeometry{
1018     reset,

```

```

1019     paperheight=190in,
1020     paperwidth=20in,
1021     left=2in,
1022     right=6in,
1023     top=1in,
1024     bottom=1in,
1025     heightrounded,%  

1026 }
```

The `lwarp` page geometry is saved for future restore:

```
1027 \LWR@origsavegeometry{\LWR@lwarpgeometry}
```

No longer adjust the page layout when `lwarp-geometry` is loaded `\AtBeginDocument`:

```
1028 \boolfalse{\LWR@allowanothergometry} %
```

`ltjsbook` and other classes can print vertically, and require these to be reset by `lwarp`:

```

1029 \setlength{\textheight}{0.8\paperheight}
1030 \setlength{\textwidth}{0.7\paperwidth}
1031
1032 \@twosidefalse
1033 @mparswitchfalse
1034 }% \AtEndPreamble
1035
1036 \end{warpHTML}
```

**for HTML & PRINT:** 1037 `\begin{warpall}`

Pkg `xparse`

LATEX3 command argument parsing

```
1038 \RequirePackage{xparse}
```

Pkg `calc`

```
1039 \RequirePackage{calc}
```

```
1040 \end{warpall}
```

**for HTML output:** 1041 `\begin{warpHTML}`

Pkg `expl3`

LATEX3 programming

```
1042 \RequirePackage{expl3}
```

Pkg `gettitlestring`

Used to emulate `\nameref`.

```
1043 \RequirePackage{gettitlestring}
```

Pkg everyhook

**everyhook** is used to patch paragraph handling.

```
1044 \@ifundefined{bxjs@everypar}{}{\let\everypar\bxjs@everypar}
1045
1046 \RequirePackage{everyhook}
1047 \end{warpHTML}
```

**for HTML & PRINT:** 1048 \begin{warpall}

Pkg filecontents

Used to write helper files while creating the print version.

Recent versions of L<sup>A</sup>T<sub>E</sub>X (as of Fall 2019) now include the functionality of the **filecontents** package, but with a new optional argument used to specify whether to force the overwriting of an existing file. If an older L<sup>A</sup>T<sub>E</sub>X kernel is used, the original **filecontents** package is used, but it is patched to throw away the new optional argument.

```
1049 \@ifundefined{filec@ntents@opt}{% older kernel, discard optional args
1050
1051     \RequirePackage{filecontents}
1052
1053     \LetLtxMacro{\LWR@orig@filec@ntents}{\filec@ntents}
1054
1055     \@ifpackagelater{filecontents}{2011/10/08}
1056     {
```

For a newer version of the **filecontents** package, simply discard the optional argument.

```
1057         \renewcommand*{\filec@ntents}[1][]{\LWR@orig@filec@ntents}
1058     }
1059     {% patch older package for morewrites
```

For an older version of **filecontents**, discard the optional argument, and also patch to work with **morewrites**, per <https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910>

```
1060     \newwrite\fcwrite
1061     \renewcommand*{\filec@ntents}[1][]{%
1062         \def\chardef##1\write{\let\reserved@c\fcwrite}%
1063         \LWR@orig@filec@ntents%
1064     }
1065 }
1066
1067 }% older kernel
1068 {% newer kernel
```

For a newer kernel with a `filecontents` environment which accepts the optional `overwrite` argument, use the environment as-is.

1069 }% newer kernel, `filecontents` env accepts optional args, do not load package

1070 `\end{warpall}`

**for HTML output:** 1071 `\begin{warpHTML}`

Pkg `xifthen`

1072 `\RequirePackage{xifthen}`

Pkg `verbatim`

1073 `\RequirePackage{verbatim}`

Pkg `refcount`

Provides `\setcounterref`, `\setcounterpageref`, etc.

1074 `\RequirePackage{refcount}`

Pkg `newfloat`

1075 `\RequirePackage{newfloat}`

1076 `\end{warpHTML}`

**for HTML & PRINT:** 1077 `\begin{warpall}`

Pkg `xstring` There was a short-term bug in `xstring` regarding `\IfInteger` which affected `lwarp`'s index generation. The updated version is requested here.

 **index** 1078 `\RequirePackage{xstring}[2019/02/01]`

Pkg `environ` Used to encapsulate math environments for re-use in HTML `<alt>` text.

1079 `\RequirePackage{environ}`

1080 `\end{warpall}`

**for HTML output:** 1081 `\begin{warpHTML}`

Pkg `printlen` Used to convert lengths for image width/height options.

1082 `\RequirePackage{printlen}`

`\LWR@printlength {⟨length⟩}`

Prints a length using a locally-controlled unit and space. Rounding is used unless the length is small.

```
1083 \newrobustcmd*{\LWR@printlength}[1]{%
1084     \begingroup%
1085     \uselengthunit{PT}%
1086     \renewcommand*{\unitspace}{ }%
1087     \ifdimless{#1}{10pt}{%
1088         \printlength{#1}%
1089     }{%
1090         \rndprintlength{#1}%
1091     }%
1092     \endgroup%
1093 }
```

1094 \end{warpHTML}

**for PRINT output:** 1095 \begin{warpprint}

Pkg varwidth Used for print-mode lateximage.

1096 \RequirePackage{varwidth}

1097 \end{warpprint}

## 30 Loading packages

**for HTML & PRINT:** 1098 \begin{warpall}

Remember the original \RequirePackage:

```
1099 \LetLtxMacro{\LWR@origRequirePackage}{\RequirePackage}
1100 \LetLtxMacro{\LWR@origRequirePackageWithOptions}{\RequirePackageWithOptions}
```

\LWR@requirepackagenames Stores the list of required package names.

1101 \newcommand\*{\LWR@requirepackagenames}{}

\LWR@parsedrequirepackagenames Stores the parsed list of required package names after spaces are removed and l warp- is prepended.

1102 \newcommand\*{\LWR@parsedrequirepackagenames}{}

\LWR@nullifycomment Remove the preexisting comment environment. Certain packages define it for their own use.

```
1103 \newcommand*{\LWR@nullifycomment}{%
1104     \PackageInfo{l warp}{%
```

```

1105      {Nullifying the comment environment before loading \LWR@strresulttwo,}%
1106      \let\comment\relax%
1107      \let\endcomment\relax%
1108 }

```

\LWR@findword [*<1: separator>*] [*<2: list>*] [*<3: index>*] [*<4: destination>*]

Note that argument 4 is passed directly to \StrBetween.

```

1109 \newcommand*\LWR@findword[3][,]{%
1110     \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}%
1111 }

```

\LWR@checkloadfilename {[*filename*]} Checks if this filename should be loaded after lwarp, or never at all.

The following should never be loaded:

```

1112 \newcommand*\LWR@checkloadfilename[1]{%
1113 \LWR@checkloadnever{#1}{ae}{cm-super, lmodern}%
1114 \LWR@checkloadnever{#1}{aecc}{cm-super, lmodern}%
1115 \LWR@checkloadnever{#1}{ae compl}{cm-super, lmodern}%
1116 \LWR@checkloadnever{#1}{alg}{algorithm2e, algorithmicx}%
1117 \LWR@checkloadnever{#1}{algorithmic}{algorithm2e, algorithmicx}%
1118 \LWR@checkloadnever{#1}{bitfield}{bytefield}%
1119 \LWR@checkloadnever{#1}{boxedminipage}{boxedminipage2e}%
1120 \LWR@checkloadnever{#1}{caption2}{caption}%
1121 \LWR@checkloadnever{#1}{ccaption}{caption}%
1122 \LWR@checkloadnever{#1}{colortab}{colortbl}%
1123 \LWR@checkloadnever{#1}{doublespace}{setspace}%
1124 \LWR@checkloadnever{#1}{epsf}{graphicx}%
1125 \LWR@checkloadnever{#1}{fancyheadings}{fancyhdr}%
1126 \LWR@checkloadnever{#1}{fncylab}{cleveref}%
1127 \LWR@checkloadnever{#1}{formula}{siunitx}%
1128 \LWR@checkloadnever{#1}{glossary}{glossaries}%
1129 \LWR@checkloadnever{#1}{hyper}{hyperref}%
1130 \LWR@checkloadnever{#1}{newthm}{ntheorem}%
1131 \LWR@checkloadnever{#1}{pdfcprot}{microtype}%
1132 \LWR@checkloadnever{#1}{picinpar}{floatflt, wrapfig}%
1133 \LWR@checkloadnever{#1}{picins}{floatflt, wrapfig}%
1134 \LWR@checkloadnever{#1}{rplain}{fancyhdr}%
1135 \LWR@checkloadnever{#1}{shadethm}{mdframed}%
1136 \LWR@checkloadnever{#1}{si}{siunitx}%
1137 \LWR@checkloadnever{#1}{sistyle}{siunitx}%
1138 \LWR@checkloadnever{#1}{slashbox}{diagbox}%
1139 \LWR@checkloadnever{#1}{t1enc}{fontenc, inputenc, inputenx}%
1140 \LWR@checkloadnever{#1}{ucs}{inputenc, inputencx}%
1141 \LWR@checkloadnever{#1}{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}%
1142 \LWR@checkloadnever{#1}{bxCJKjatype}{upLaTeX, bxjsarticle, ujarticle, utarticle}%
1143 \LWR@checkloadnever{#1}{hangul}{kotex, xetexko, luatexko}

```

The following should only be loaded before lwarp:

```

1144 \LWR@checkloadbefore{#1}{ctex}%
1145 \LWR@checkloadbefore{#1}{fontspec}%

```

```

1146 \LWR@checkloadbefore{#1}{inputenc}
1147 \LWR@checkloadbefore{#1}{inputenx}
1148 \LWR@checkloadbefore{#1}{nfssext-cfr}
1149 \LWR@checkloadbefore{#1}{fontaxes}
1150 \LWR@checkloadbefore{#1}{kotex}
1151 \LWR@checkloadbefore{#1}{luatexja}
1152 \LWR@checkloadbefore{#1}{luatexja-fontspec}
1153 \LWR@checkloadbefore{#1}{luatexko}
1154 \LWR@checkloadbefore{#1}{morewrites}
1155 \LWR@checkloadbefore{#1}{newclude}
1156 \LWR@checkloadbefore{#1}{newunicodechar}
1157 \LWR@checkloadbefore{#1}{plext}
1158 \LWR@checkloadbefore{#1}{xeCJK}
1159 \LWR@checkloadbefore{#1}{xetexko}
1160 \LWR@checkloadbefore{#1}{zxjatype}
1161 }

```

\LWR@lookforpackagename {*index*}

If **HTML**, and if this is an **lwarp**-supported package name, re-direct it to the **lwarp** version by renaming it **lwarp-** followed by the original name.

Looks *index* deep into the list of package names, \LWR@requirepackagenames, and builds \LWR@parsedrequirepackagenames which is the modified list of names.

```
1162 \newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the *index*'th package name from the list:

```
1163 \LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in **LWR@strresult** and the final name with no blanks goes into **LWR@strresulttwo**.

```
1164 \StrSubstitute[100]{\LWR@strresult}{}{}[\LWR@strresulttwo]%
```

See if the package name was found:

```

1165 \IfStrEq{\LWR@strresulttwo}{}%
1166 {}% no filename
1167 {}% yes filename was found

```

Possible adjustments before loading the package. Maybe nullify the **comment** environment if the new package will be redefining it for a new purpose.

```

1168 \ifdefstring{\LWR@strresulttwo}{easyReview}{\LWR@nullifycomment}{}%
1169 \ifdefstring{\LWR@strresulttwo}{changes}{\LWR@nullifycomment}{}%

```

If **HTML**, check if the package should be loaded before **lwarp**, or never at all:

```
1170 \ifbool{warpingHTML}{\LWR@checkloadfilename{\LWR@strresulttwo}}{}%
```

If **HTML**, and if found, and if an **lwarp**-equivalent name exists, use **lwarp-\*** instead.

```

1171 \ifboolexpr{
1172   bool{warpingHTML} and
1173   test{\IfFileExists{l warp-\LWR@strresulttwo.sty}}
1174 }%
1175 {%
1176   l warp-* file found
1177   \ifdefvoid{\LWR@parsedrequirepackagenames}{%
1178     \edef\LWR@parsedrequirepackagenames{l warp-\LWR@strresulttwo}%
1179   }{%
1180     \edef\LWR@parsedrequirepackagenames{%
1181       \LWR@parsedrequirepackagenames,\LWR@strresulttwo%
1182     }%
1183   }%
1184 }%

```

Otherwise, use the current package name.

```

1185 \ifdefvoid{\LWR@parsedrequirepackagenames}{%
1186   \edef\LWR@parsedrequirepackagenames{\LWR@strresulttwo}%
1187 }{%
1188   \edef\LWR@parsedrequirepackagenames{%
1189     \LWR@parsedrequirepackagenames,\LWR@strresulttwo%
1190   }%
1191 }%
1192 }% no l warp-* file
1193 }% yes filename
1194 }

```

\RequirePackage [⟨1: options⟩] {⟨2: package names⟩} [⟨3: version⟩]

For each of many package names in a comma-separated list, if an l warp version of a package exists, select it instead of the L<sup>A</sup>T<sub>E</sub>X version.

```
1195 \RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to twenty names:<sup>16</sup>

```

1196 \renewcommand*\LWR@requirepackagenames{#2}%
1197 \renewcommand*\LWR@parsedrequirepackagenames{}%
1198 \LWR@lookforpackagename{1}%
1199 \LWR@lookforpackagename{2}%
1200 \LWR@lookforpackagename{3}%
1201 \LWR@lookforpackagename{4}%
1202 \LWR@lookforpackagename{5}%
1203 \LWR@lookforpackagename{6}%
1204 \LWR@lookforpackagename{7}%
1205 \LWR@lookforpackagename{8}%
1206 \LWR@lookforpackagename{9}%
1207 \LWR@lookforpackagename{10}%
1208 \LWR@lookforpackagename{11}%
1209 \LWR@lookforpackagename{12}%
1210 \LWR@lookforpackagename{13}%

```

---

<sup>16</sup>This was originally nine names, but then I came across a package which used twelve...

```

1211 \LWR@lookforpackagename{14}%
1212 \LWR@lookforpackagename{15}%
1213 \LWR@lookforpackagename{16}%
1214 \LWR@lookforpackagename{17}%
1215 \LWR@lookforpackagename{18}%
1216 \LWR@lookforpackagename{19}%
1217 \LWR@lookforpackagename{20}%

```

\RequirePackage depending on the options and version:

```

1218 \IfValueTF{#1}%
1219 { % options given
1220   \IfValueTF{#3}{% version given?
1221     {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}{#3}}%
1222     {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}}%
1223 }%
1224 { % no options given
1225   \IfValueTF{#3}{% version given?
1226     {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}{#3}}%
1227     {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}}%
1228 }%
1229 }
1230 \LetLtxMacro\usepackage\RequirePackage
1231 \end{warpall}

```

**for HTML output:** 1232 \begin{warpHTML}

\LWR@ProvidesPackagePass {*pkgnname*} [*version*]

Uses the original package, including options.

```

1233 \NewDocumentCommand{\LWR@ProvidesPackagePass}{m o} {
1234   \PackageInfo{l warp} {%
1235     Using package '#1' and adding l warp modifications, \MessageBreak
1236     including options, }%
1237   \IfValueTF{#2}{%
1238     {\ProvidesPackage{l warp-#1}{#2}}%
1239     {\ProvidesPackage{l warp-#1}}%
1240   \DeclareOption*{%
1241     \PassOptionsToPackage{\CurrentOption}{#1}}%
1242 }%
1243 \ProcessOptions\relax%

```

If using `catoptions`, an error occurs if a package is loaded with an option then loaded again with no options. `l warp` does this if a package is preloaded then later patched. To avoid an error while using `catoptions`, if a package has already been loaded, it is loaded again with its original options.

```

1244   \@ifpackageloaded{#1}{%
1245     \edef\LWR@tempone{\csuse{opt@#1.sty}}%
1246     \IfValueTF{#2}{%
1247       {%
1248         \expandafter\LWR@origRequirePackage%

```

```

1249           \expandafter[\LWR@tempone]{#1}[#2]%
1250       }%
1251   {%
1252       \expandafter\LWR@origRequirePackage%
1253           \expandafter[\LWR@tempone]{#1}%
1254       }%
1255   }{%
1256       \IfValueTF{#2}%
1257           {\LWR@origRequirePackage{#1}[#2]}%
1258           {\LWR@origRequirePackage{#1}}%
1259   }%

```

In some cases, the following seems to be required to avoid an “unknown option” error, such as when loading `xcolor` with options.

```

1260 \DeclareOption*{}%
1261 \ProcessOptions\relax%
1262 }

```

`\LWR@ProvidesPackageDropA {<name>} {<date or -NoValue->}`

Declares the package. Factored for reuse.

```

1263 \newcommand*{\LWR@ProvidesPackageDropA}[2]{%
1264     \PackageInfo{lwarp}{%
1265         Replacing package ‘#1’ with the lwarp version,\MessageBreak
1266         and discarding options,%
1267     }%
1268     \IfValueTF{#2}%
1269     {\ProvidesPackage{lwarp-#1}[#2]}%
1270     {\ProvidesPackage{lwarp-#1}}%
1271 }

```

`\LWR@ProvidesPackageDropB` Nullifies then processes the options.

Seems to be required when options contain curly braces, which were causing “Missing `\begin{document}`”.

```

1272 \newcommand*{\LWR@ProvidesPackageDropB}{%
1273 % \ProcessOptions\relax% original LaTeX code
1274 \let\ds@\empty% from the original \ProcessOptions
1275 \edef\@curroptions{}% lwarp modification to \ProcessOptions
1276 \processoptions\relax% from the original \ProcessOptions
1277 }

```

`\LWR@ProvidesPackageDrop {<pkgnname>} [<version>]`

Ignores the original package and uses lwarp’s version instead. Drops/discards all options.

```
1278 \NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o}{
```

Declare the package:

```
1279 \LWR@ProvidesPackageDropA{\#1}{\#2}
```

Ignore all options:

```
1280 \DeclareOption*{}
```

Process the options:

```
1281 \LWR@ProvidesPackageDropB  
1282 }
```

```
1283 \end{warpHTML}
```

## 31 Additional required packages

**for HTML output:** 1284 \begin{warpHTML}

Pkg caption

```
1285 \LWR@origRequirePackage{caption}  
1286 \AtBeginDocument{\RequirePackage{lwarp-caption}}%
```

```
1287 \end{warpHTML}
```

## 32 File handles

Defines file handles for writes.

**for HTML & PRINT:** 1288 \begin{warpall}

\LWR@quickfile For quick temporary use only. This is reused in several places.

```
1289 \newwrite\LWR@quickfile%
```

```
1290 \end{warpall}
```

**for HTML output:** 1291 \begin{warpHTML}

\LWR@lateximagesfile For <project>-images.txt:

```
1292 \newwrite\LWR@lateximagesfile
```

```
1293 \end{warpHTML}
```

### 33 Include a file

During HTML output, `\include{<filename>}` causes the following to occur:

1. lwarp creates `<filename>_html_inc.tex` whose contents are:  
`\input <filename>.tex`
2. `<filename>_html_inc.tex` is then `\included` instead of `<filename>.tex`.
3. `<filename>_html_inc.aux` is automatically generated and used by L<sup>A</sup>T<sub>E</sub>X.

**for HTML output:** 1294 `\begin{warpHTML}`

`\@include {<filename>}` Modified to load \_html\_inc files.

(Below, `\clearpage` caused missing text, and was changed to `\newpage`.)

```
1295 \def\@include#1 {%
1296   \immediate\openout\LWR@quickfile #1_html_inc.tex% lwarp
1297   \immediate\write\LWR@quickfile{\string\input{#1.tex}}% lwarp
1298   \immediate\closeout\LWR@quickfile% lwarp
1299 \LWR@orignewpage% changed from clearpage
1300 \if@files
1301   \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
1302 \fi
1303 \@tempswattrue
1304 \if@partsw
1305   \tempswafalse
1306   \edef\reserved@b{#1}%
1307   \for\reserved@a:=\partlist\do
1308     {\ifx\reserved@a\reserved@b\@tempswattrue\fi}%
1309 \fi
1310 \if@tempswa
1311   \let\@auxout\@partaux
1312   \if@files
1313     \immediate\openout\@partaux #1_html_inc.aux % changed
1314     \immediate\write\@partaux{\relax}%
1315   \fi
1316   \input{#1_html_inc.tex}% changed
1317   \LWR@orignewpage% changed from clearpage
1318   \writeckpt{#1}%
1319   \if@files
1320     \immediate\closeout\@partaux
1321   \fi
1322 \else
1323   \deadcycles{z}
1324   \nameuse{cp}{#1}%
1325 \fi
1326 \let\@auxout\@mainaux%
1327 }
1328 \end{warpHTML}
```

## 34 Copying a file

**for HTML output:** 1329 \begin{warpHTML}

\LWR@copyfile {*source filename*} {*destination filename*}

Used to copy the .toc file to .sidetoc to re-print the TOC in the sidetoc navigation pane.

```

1330 \newwrite\LWR@copyoutfile % open the file to write to
1331 \newread\LWR@copyinfile    % open the file to read from
1332
1333 \newcommand*{\LWR@copyfile}[2]{%
1334 \LWR@traceinfo{\LWR@copyfile: copying #1 to #2}
1335
1336 \immediate\openout\LWR@copyoutfile=#2
1337 \openin\LWR@copyinfile=#1
1338 \begingroup\endlinechar=-1
1339 \makeatletter
1340
1341 \LWR@traceinfo{\LWR@copyfile: about to loop}
1342
1343 \loop\unless\ifeof\LWR@copyinfile
1344   \LWR@traceinfo{\LWR@copyfile: one line}
1345   \read\LWR@copyinfile to\LWR@fileline % Read one line and store it into \LWR@fileline
1346 %   \LWR@fileline\par                  % print the content into the pdf
1347 % print the content:
1348   \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
1349 \repeat
1350 \immediate\closeout\LWR@copyoutfile
1351 \LWR@traceinfo{\LWR@copyfile: done}
1352 \endgroup
1353 }

1354 \end{warpHTML}

```

## 35 Debugging messages

**HTML comments** To have the HTML output include additional HTML comments, such as which <div> is closing, use

\booltrue{HTMLDebugComments}

**debugging information** To have debug information written to the log, use

\tracinglwarp

**for HTML & PRINT:** 1355 \begin{warpall}

Bool LWR@tracinglwarp True if tracing is turned on.

---

```
1356 \newbool{LWR@tracingl warp}
```

\tracingl warp Turns on the debug tracing messages.

```
1357 \newcommand{\tracingl warp}{\booltrue{LWR@tracingl warp}}
```

\LWR@traceinfo {⟨text⟩} If tracing is turned on, writes the text to the .log file.

```
1358 \newcommand{\LWR@traceinfo}[1]{%
1359 \ifbool{LWR@tracingl warp}{%
1360 {%
1361     \typeout{*** l warp: #1}%
1362 }%
1363 {}%
1364 }
```

Bool HTMLDebugComments Add comments in HTML about closing <div>s, sections, etc.

**Default:** false

```
1365 \newbool{HTMLDebugComments}
1366 \boolfalse{HTMLDebugComments}
```

If \tracingl warp, show where preamble hooks occur:

```
1367 \AfterEndPreamble{%
1368 \LWR@traceinfo{AfterEndPreamble}%
1369 }%
1370 %
1371 \AtBeginDocument{%
1372 \LWR@traceinfo{AtBeginDocument}%
1373 }%
```

```
1374 \end{warpall}
```

## 36 Defining print and HTML versions of macros and environments

The following refers to defining objects inside l warp, and is not for the user's document.

Many macros and environments must be provided as both print and HTML versions.

While generating the print version of a document, the original macros as defined by LATEX and its packages are used as-is.

While generating the HTML version of a document, the original macro or environment is redefined to call a new HTML version or a copy of the original print version. The new HTML versions of macros and environments are used most of the time. Copies of the print versions are used inside a `lateximage` environment, which draws and remembers an image of the printed output, and also several other places. The copies

---

of the print versions may also be used by the HTML versions, such as when the HTML version merely encloses the print version inside HTML tags.

The general structure for providing print and HTML versions of a macro or environment is as follows:

**For a preexisting macro, not defined with xparse:** An HTML version is provided with a special name, inside a `\begin{warpHTML}` environment, then `\LWR@formatted` is used to redefine and patch various macros:

---

```
\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may also use xparse

\LWR@formatted{name}
\end{warpHTML}
```

---

`\LWR@formatted{name}` copies the original print version, then redefines `\name` to use either the print or HTML version depending on which mode `lwarp` is using. `xparse` may be used to define the new HTML version, even if the original did not use `xparse`.

**For a preexisting environment, not defined with xparse:** The process is similar. Note the use of `\LWR@formattedenv` instead of `\LWR@formatted`.

---

```
\begin{warpHTML}
\newenvironment{\LWR@HTML@name}{...}% may also use xparse

\LWR@formattedenv{name}
\end{warpHTML}
```

---

**If the original used xparse:** A copy must be made using a new name:

---

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@name}{...}{...}% copy the original

\NewDocumentCommand{\LWR@HTML@name}{...}{...}% or use \newcommand

\LWR@formatted{name}
\end{warpHTML}
```

---

Similar for an environment, using `\LWR@formattedenv`. (`\LWR@formatted` and `\LWR@formattedenv` use `\LetLtxMacro` to copy the original print definition, which may not work with macros and environments created by `xparse`, so the print version must be manually recreated in the `lwarp` source.)

**For a new macro or environment, not using xparse for the print version:**

---

```
\begin{warpall}
\newcommand{\name}{...}% NOT xparse!
```

---

---

```
\end{warpall}

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may use xparse for HTML

\LWR@formatted{name}
\end{warpHTML}
```

---

Similar for an environment. The plain `\name` or environment name is used for the printed version, and is placed inside `warpall`. `xparse` may be used for the `\LWR@HTML@<name>` version.

**For a new macro or environment, using xparse:** It is possible to use `xparse` for an entirely new macro or environment by defining the `\LWR@print@<name>` version with `xparse`, along with `\name` defined without `xparse` to refer directly to the `\LWR@print` version:

---

```
\begin{warpall}
\NewDocumentCommand{\LWR@print@name}{...} {...}%
\NewDocumentEnvironment{\LWR@print@name}{...} {...} { ... }

% Simply a call to \LWR@print@name:
\newcommand{\name}{\LWR@print@name}%
\newenvironment{name}{\LWR@print@name}{\endLWR@print@name}
\end{warpall}

\begin{warpHTML}
\NewDocumentCommand{\LWR@HTML@name}{...} {...}%
\NewDocumentEnvironment{\LWR@HTML@name}{...} {...} { ... }

\LWR@formatted{name}%
\LWR@formattedenv{name}
\end{warpHTML}
```

---

In general, `\LWR@formatted` or `\LWR@formattedenv` are placed inside a `warpHTML` environment, and while producing an HTML document they do the following:

- Macros are modified:
  1. The pre-existing print version `\name` is saved as `\LWR@print@<name>`, unless `\LWR@print@<name>` is already defined.
  2. The original `\name` is redefined to call either the print or HTML version depending on which format is in use at the moment, as set by `\LWR@formatting`, which is defined as either “print” or “HTML”.
- When `lwarp` is producing a print document, the original definitions are used, as well as any new definitions defined in `warpall` above.
- When `lwarp` is generating HTML output, `\LWR@formatting` is set to “HTML”, and `\name` is directed to `\LWR@HTML@<name>`.

- When `lwarp` is generating HTML output but enters a `\teximage` environment, or for some other reason needs to draw images using the original print definitions, `\LWR@formatting` is changed to “print” and `\name` is then redirected to `\LWR@print@<name>`, which was the original `\name`.

Since arguments are not handled by the new `\name`, any star and other arguments are processed by the print or HTML version.

Expandable versions are also provided as well. These usually are necessary for anything which could appear inside a `tabular`, without which a “Misplaced `\omit`” error may occur.

`\LWR@expandableformatted`  
`\LWR@expandableformattedenv`

(Older versions of `lwarp` used `\LetLtxMacro` for everything, but this could fail when using macros defined by `xparse`. This older system is still in use for many definitions.)

**for HTML output:** 1375 `\begin{warpHTML}`

`\LWR@formatting` Remembers if selected print/HTML formatting.

Used while `\LWR@restoreorigformatting`, such as in an `\teximage`. May be set to either “print” or “HTML”.

1376 `\newcommand*{\LWR@formatting}{HTML}`

`\LWR@formatted {<macroname>}` No backslash in the macro name.

If not yet defined, defines `\LWR@print@<name>` as the original print-mode `\<name>`. Also redefines `\<name>` to use `\LWR@<format>@<name>`, where `<format>` is set by `\LWR@formatting`, and is print or HTML.

```
1377 \newcommand*{\LWR@formatted}[1]{%
1378   \ifcsundef{\LWR@print@#1}{%
1379     \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
1380     \csname#1\endcsname%
1381   }{%
1382   \ifcsundef{#1}{%
1383     \expandafter\newrobustcmd\csname #1\endcsname{%
1384       \nameuse{\LWR@\LWR@formatting @#1}%
1385     }%
1386   }{%
1387     \expandafter\renewrobustcmd\csname #1\endcsname{%
1388       \nameuse{\LWR@\LWR@formatting @#1}%
1389     }%
1390   }%
1391 }
```

`\LWR@expandableformatted {<macroname>}` No backslash in the macro name.

An expandable version of `\LWR@formatted`.

```

1392 \newcommand*{\LWR@expandableformatted}[1]{%
1393     \ifcsundef{\LWR@print@#1}{%
1394         \expandafter\LetLtxMacro\csname \LWR@print@#1\expandafter\endcsname%
1395             \csname#1\endcsname%
1396     }{%
1397     \ifcsundef{#1}{%
1398         \expandafter\newcommand\csname #1\endcsname{%
1399             \@nameuse{\LWR@\LWR@formatting @#1}%
1400         }%
1401     }{%
1402         \expandafter\renewcommand\csname #1\endcsname{%
1403             \@nameuse{\LWR@\LWR@formatting @#1}%
1404         }%
1405     }%
1406 }

```

\LWR@formattedenv {*<environmentname>*}

If not yet defined, defines the environment `\LWR@print@<name>` as the original print-mode `<name>`. Also redefines the environment `<name>` to use environment `\LWR@<format>@<name>`, where `<format>` is set by `\LWR@formatting`, and is print or HTML.

```

1407 \newcommand*{\LWR@formattedenv}[1]{%
1408     \ifcsundef{\LWR@print@#1}{%
1409         \expandafter\LetLtxMacro\csname \LWR@print@#1\expandafter\endcsname%
1410             \csname#1\endcsname%
1411         \csletcs{endLWR@print@#1}{end#1}%
1412     }{%
1413         \DeclareDocumentEnvironment{#1}{}{%
1414             {%
1415                 \@nameuse{\LWR@\LWR@formatting @#1}%
1416             }%
1417             {%
1418                 \@nameuse{endLWR@\LWR@formatting @#1}%
1419             }%
1420 }

```

\LWR@expandableformattedenv {*<environmentname>*}

An expandable version of `\LWR@formattedenv`.

```

1421 \newcommand*{\LWR@expandableformattedenv}[1]{%
1422     \ifcsundef{\LWR@print@#1}{%
1423         \expandafter\LetLtxMacro\csname \LWR@print@#1\expandafter\endcsname%
1424             \csname#1\endcsname%
1425         \csletcs{endLWR@print@#1}{end#1}%
1426     }{%
1427         \DeclareExpandableDocumentEnvironment{#1}{}{%
1428             {%
1429                 \@nameuse{\LWR@\LWR@formatting @#1}%
1430             }%
1431             {%
1432                 \@nameuse{endLWR@\LWR@formatting @#1}%
1433             }%

```

```
1434 }  
1435 \end{warpHTML}
```

## 37 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

for HTML & PRINT: 1436 \begin{warpall}

### 37.1 User-level controls

Bool FormatEPUB Changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.  
Default: false

```
1437 \newbool{FormatEPUB}  
1438 \boolearn{FormatEPUB}
```

Bool FormatWP Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.  
Default: false

```
1439 \newbool{FormatWP}  
1440 \boolearn{FormatWP}
```

Bool WPMarkFloats Adds  
Default: false  
===== begin table =====  
...  
===== end =====  
or  
===== begin figure =====  
...  
===== end =====

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.<sup>17</sup>

```
1441 \newbool{WPMarkFloats}  
1442 \boolearn{WPMarkFloats}
```

Bool WPMarkMinipages Adds  
Default: false  
===== begin minipage =====  
...  
===== end minipage =====

---

<sup>17</sup>Perhaps some day word processors will have HTML import options for identifying <figure> and caption tags for figures and tables.

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

```
1443 \newbool{WPMarkMinipages}  
1444 \boolfalse{WPMarkMinipages}
```

Bool WPMarkTOC While formatting for word processors, adds  
**Default: true**  
==== table of contents ===

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

*If set false, the actual toc is printed instead.*

```
1445 \newbool{WPMarkTOC}  
1446 \booltrue{WPMarkTOC}
```

Bool WPMarkLOFT While formatting for word processors, adds  
**Default: false**  
==== list of figures === and/or  
==== list of tables ===

where each of these lists would have been. This helps identify where to insert the actual lists.

*If set false, the actual lists are printed instead.*

```
1447 \newbool{WPMarkLOFT}  
1448 \boolfalse{WPMarkLOFT}
```

Bool WPMarkMath While formatting for word processors, prints math as L<sup>A</sup>T<sub>E</sub>X code instead of creating SVG images or MATHJAX. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

```
1449 \newbool{WPMarkMath}  
1450 \boolfalse{WPMarkMath}
```

Bool WPTitleHeading While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LIBREOFFICE. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 181.

```
1451 \newbool{WPTitleHeading}  
1452 \boolfalse{WPTitleHeading}
```

```
1453 \end{warpall}
```

## 37.2 Heading adjustments

If formatting the HTML for a word processor, adjust heading levels.

If `WPTitleHeading` is true, adjust so that part is **Heading 1**.

If `WPTitleHeading` is false, use `<h1>` for the title, and set part to **Heading 2**.

**for HTML output:** 1454 `\begin{warpHTML}`

```
1455 \AtBeginDocument{  
1456 \ifbool{FormatWP}{  
1457 \@ifundefined{chapter}{  
1458 \ifbool{WPTitleHeading}{% part and section starting at h2  
1459 \renewcommand*\{\LWR@tagtitle\}{h1}  
1460 \renewcommand*\{\LWR@tagtitleend\}{/h1}  
1461 \renewcommand*\{\LWR@tagpart\}{h2}  
1462 \renewcommand*\{\LWR@tagpartend\}{/h2}  
1463 \renewcommand*\{\LWR@tagsection\}{h3}  
1464 \renewcommand*\{\LWR@tagsectionend\}{/h3}  
1465 \renewcommand*\{\LWR@tagsubsection\}{h4}  
1466 \renewcommand*\{\LWR@tagsubsectionend\}{/h4}  
1467 \renewcommand*\{\LWR@tagsubsubsection\}{h5}  
1468 \renewcommand*\{\LWR@tagsubsubsectionend\}{/h5}  
1469 \renewcommand*\{\LWR@tagparagraph\}{h6}  
1470 \renewcommand*\{\LWR@tagparagraphend\}{/h6}  
1471 \renewcommand*\{\LWR@tagsubparagraph\}{span class="subparagraph"}  
1472 \renewcommand*\{\LWR@tagsubparagraphend\}{/span}  
1473 }% WPTitleHeading  
1474 {% not WPTitleHeading, part and section starting at h1  
1475 \renewcommand*\{\LWR@tagtitle\}{div class="title"}  
1476 \renewcommand*\{\LWR@tagtitleend\}{/div}  
1477 \renewcommand*\{\LWR@tagpart\}{h1}  
1478 \renewcommand*\{\LWR@tagpartend\}{/h1}  
1479 \renewcommand*\{\LWR@tagsection\}{h2}  
1480 \renewcommand*\{\LWR@tagsectionend\}{/h2}  
1481 \renewcommand*\{\LWR@tagsubsection\}{h3}  
1482 \renewcommand*\{\LWR@tagsubsectionend\}{/h3}  
1483 \renewcommand*\{\LWR@tagsubsubsection\}{h4}  
1484 \renewcommand*\{\LWR@tagsubsubsectionend\}{/h4}  
1485 \renewcommand*\{\LWR@tagparagraph\}{h5}  
1486 \renewcommand*\{\LWR@tagparagraphend\}{/h5}  
1487 \renewcommand*\{\LWR@tagsubparagraph\}{h6}  
1488 \renewcommand*\{\LWR@tagsubparagraphend\}{/h6}  
1489 }% not WPTitleHeading  
1490 }% chapter undefined  
1491 {% chapter defined  
1492 \ifbool{WPTitleHeading}{}  
1493 {% not WPTitleHeading, part and chapter starting at h1  
1494 \renewcommand*\{\LWR@tagtitle\}{div class="title"}  
1495 \renewcommand*\{\LWR@tagtitleend\}{/div}  
1496 \renewcommand*\{\LWR@tagpart\}{h1}  
1497 \renewcommand*\{\LWR@tagpartend\}{/h1}  
1498 \renewcommand*\{\LWR@tagchapter\}{h2}  
1499 \renewcommand*\{\LWR@tagchapterend\}{/h2}
```

---

```

1500 \renewcommand*{\LWR@tagsection}{h3}
1501 \renewcommand*{\LWR@tagsectionend}{/h3}
1502 \renewcommand*{\LWR@tagsubsection}{h4}
1503 \renewcommand*{\LWR@tagsubsectionend}{/h4}
1504 \renewcommand*{\LWR@tagsubsubsection}{h5}
1505 \renewcommand*{\LWR@tagsubsubsectionend}{/h5}
1506 \renewcommand*{\LWR@tagparagraph}{h6}
1507 \renewcommand*{\LWR@tagparagraphend}{/h6}
1508 \renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
1509 \renewcommand*{\LWR@tagsubparagraphend}{/span}
1510 }% not WPTitleHeading
1511 }% chapter defined
1512 }{ }% FormatWP
1513 }% AtBeginDocument

1514 \end{warpHTML}

```

## 38 Remembering original formatting macros

**for HTML output:** 1515 \begin{warpHTML}

Remember original definitions of formatting commands. Will be changed to HTML commands for most uses. Will be temporarily restored to original meaning inside any `lateximage` environment. Also nullify unused commands.

Some packages redefine `\#`, which is used to generate HTML, so the original must be remembered here.

```

1516 \chardef\LWR@origpound='\#
1517 \let\LWR@origcomma\
1518 \let\LWR@origthinspace\thinspace
1519 \let\LWR@orignegthinspace\negthinspace
1520 \let\LWR@origtilde\
1521 \let\LWR@origskip\enskip
1522 \let\LWR@origquad\quad
1523 \let\LWR@origqquad\qquad
1524 \let\LWR@orighfil\hfil
1525 \let\LWR@orighss\hss
1526 \let\LWR@origllap\llap
1527 \let\LWR@origrlap\rlap
1528 \let\LWR@orighfilneg\hfilneg
1529 \let\LWR@orighspace\hspace
1530
1531 \let\LWR@origrule\rule
1532
1533 \let\LWR@origmedskip\medskip
1534 \let\LWR@origbigskip\bigskip
1535
1536 \let\LWR@origtextellipsis\textellipsis
1537 \let\LWR@orig@textquotedbl\textquotedbl
1538

```

```
1539 \LetLtxMacro{\LWR@origttfamily}{\ttfamily}
1540
1541 \LetLtxMacro{\LWR@origem}{\em}
1542
1543 \LetLtxMacro{\LWR@orignormalfont}{\normalfont}
1544
1545 \let{\LWR@origonecolumn}{\onecolumn}
1546
1547 \let{\LWR@origsp}{\sp}
1548 \let{\LWR@origsb}{\sb}
1549 \LetLtxMacro{\LWR@origtextsuperscript}{\textsuperscript}
1550 \LetLtxMacro{\LWR@orig@textsuperscript}{\textsuperscript@textsuperscript}
1551
1552 \AtBeginDocument{
1553 \LetLtxMacro{\LWR@origtextsubscript}{\textsubscript}
1554 \LetLtxMacro{\LWR@orig@textsubscript}{\textsubscript@textsubscript}
1555 }
1556
1557 \LetLtxMacro{\LWR@origunderline}{\underline}

1558 \let{\LWR@orignewpage}{\newpage}
1559
1560 \let{\LWR@origpagestyle}{\pagestyle}
1561 \let{\LWR@origthispagestyle}{\thispagestyle}
1562 \LetLtxMacro{\LWR@origpagenumbering}{\pagenumbering}
1563
1564 \let{\LWR@orignewline}{\newline}
1565
1566
1567 \AtBeginDocument{\% in case packages change definition
1568 \let{\LWR@orig@trivlist}{\@trivlist}
1569 \let{\LWR@origtrivlist}{\trivlist}
1570 \let{\LWR@origendtrivlist}{\endtrivlist}
1571 \LetLtxMacro{\LWR@origitem}{\item}
1572 \LetLtxMacro{\LWR@origitemize}{\itemize}
1573 \LetLtxMacro{\LWR@endorigitemize}{\enditemize}
1574 \LetLtxMacro{\LWR@origenumerate}{\enumerate}
1575 \LetLtxMacro{\LWR@endorigenumerate}{\endenumerate}
1576 \LetLtxMacro{\LWR@origdescription}{\description}
1577 \LetLtxMacro{\LWR@endorigdescription}{\enddescription}
1578 \let{\LWR@orig@mklab}{\@mklab}
1579 \let{\LWR@origmakelabel}{\makelabel}
1580 \let{\LWR@orig@donoparitem}{\@donoparitem}
1581 \LetLtxMacro{\LWR@orig@item}{\item}
1582 \let{\LWR@orig@nbitem}{\@nbitem}
1583 }
1584
1585 \let{\LWR@origpar}{\par}
1586
1587 \LetLtxMacro{\LWR@origfootnote}{\footnote}
1588 \let{\LWR@orig@mpfootnotetext}{\@mpfootnotetext}
1589
1590
1591 \AtBeginDocument{\% in case packages change definition
1592 \LetLtxMacro{\LWR@orighline}{\hline}
```

---

```

1593 \LetLtxMacro{\LWR@origcline}{\line}
1594 }

1595 \end{warpHTML}
```

## 39 Accents

Native L<sup>A</sup>T<sub>E</sub>X accents such as \" will work, but many more kinds of accents are available when using Unicode-aware X<sup>E</sup>L<sup>A</sup>T<sub>E</sub>X and LuaL<sup>A</sup>T<sub>E</sub>X.

**for HTML output:** 1596 \begin{warpHTML}

Without \AtBeginDocument, \t was being re-defined somewhere.

```
1597 \AtBeginDocument{
```

The following are restored for print when inside a `lateximage`.

For Unicode engines, only \t needs to be redefined:

```
1598 \LetLtxMacro{\LWR@origt}{\t}
```

For pdfL<sup>A</sup>T<sub>E</sub>X, additional work is required:

```

1599 \ifPDFTeX% pdflatex or dvi latex
1600 \LetLtxMacro{\LWR@origequalaccent}{%
1601 \LetLtxMacro{\LWR@origdotaccent}{.}%
1602 \LetLtxMacro{\LWR@origu}{u}%
1603 \LetLtxMacro{\LWR@origv}{v}%
1604 \LetLtxMacro{\LWR@origc}{c}%
1605 \LetLtxMacro{\LWR@origd}{d}%
1606 \LetLtxMacro{\LWR@origb}{b}
```

The HTML redefinitions follow.

For pdfL<sup>A</sup>T<sub>E</sub>X, Unicode diacritical marks are used:

```

1607 \renewcommand*{\=}[1]{\#1\HTMLunicode{0305}}%
1608 \renewcommand*{\.\ }[1]{\#1\HTMLunicode{0307}}%
1609 \renewcommand*{\u}[1]{\#1\HTMLunicode{0306}}%
1610 \renewcommand*{\v}[1]{\#1\HTMLunicode{030C}}%
1611 \renewcommand*{\c}[1]{\#1\HTMLunicode{0327}}%
1612 \renewcommand*{\d}[1]{\#1\HTMLunicode{0323}}%
1613 \renewcommand*{\b}[1]{\#1\HTMLunicode{0331}}%
1614 \fi
```

For all engines, a Unicode diacritical tie is used:

```

1615 \def\LWR@t#1{\#1\HTMLunicode{0361}\#2}%
1616 \renewcommand*{\t}[1]{\LWR@t#1}
```

\LWR@restoreorigaccents Called from \restoreoriginalformatting when a `lateximage` is begun.

```

1617 \ifPDFTeX% pdflatex or dvi latex
1618 \newcommand*{\LWR@restoreorigaccents}{%
1619 \LetLtxMacro{\LWR@origequalaccent}%
1620 \LetLtxMacro{\LWR@origdotaccent}%
1621 \LetLtxMacro{\LWR@origu}%
1622 \LetLtxMacro{\LWR@origv}%
1623 \LetLtxMacro{\LWR@origt}%
1624 \LetLtxMacro{\c}{\LWR@origc}%
1625 \LetLtxMacro{\d}{\LWR@origd}%
1626 \LetLtxMacro{\b}{\LWR@origb}%
1627 }%
1628 \else% XeLaTeX, LuaLaTeX:
1629 \newcommand*{\LWR@restoreorigaccents}{%
1630 \LetLtxMacro{\LWR@origt}%
1631 }%
1632 \fi%
1633 }% AtBeginDocument

1634 \end{warpHTML}

```

## 40 Configuration files

### 40.1 Decide whether to generate configuration files

Configuration files are only written if processing the print version of the document, and not processing a `pstool` image. `pstool` uses an additional compile for each image using the original document's preamble, which includes `lwarp`, so the `lwarp` configuration files are turned off if `-pstool` is part of the `\jobname`.

Default to no configuration files:

```
1635 \excludecomment{LWRwriteconf}
```

Generate configuration files if print mode and not `-pstool`:

```

for PRINT output: 1636 \begin{warpprint}
1637 \fullexpandarg%
1638 \IfSubStr*{\jobname}{-pstool}
1639   {
1640     \PackageInfo{lwarp}{%
1641       Jobname with -pstool is found.\MessageBreak
1642       Not generating lwarp configuration files,%
1643     }
1644   }
1645   {
1646     \PackageInfo{lwarp}{Generating lwarp configuration files,}%
1647     \includecomment{LWRwriteconf}
1648   }
1649 \end{warpprint}

```

## 40.2 <project>.html.tex

File \*\_html.tex Used to allow an HTML version of the document to exist alongside the print version.

**Config file:**

```

1650 \begin{LWRwriteconf}
1651 \immediate\openout\LWR@quickfile=\jobname_html.tex
1652 \immediate\write\LWR@quickfile{%
1653 \detokenize{\PassOptionsToPackage}{%
1654 {warpHTML,BaseJobname=\jobname}{l warp}}%
1655 }
1656 \immediate\write\LWR@quickfile{%
1657 \detokenize{\input}\string{\jobname.tex}\string }%
1658 }
1659 \immediate\closeout\LWR@quickfile
1660 \end{LWRwriteconf}
```

## 40.3 l warpmk configuration files

**Config file:**

```
1661 \begin{LWRwriteconf}
```

\LWR@lwarpmkversion The version number of the configuration file, allowing *l warpmk* to detect an obsolete configuration file format. Incremented by one each time the configuration file format changes. (This is NOT the same as the *l warp* version number.)

```
1662 \newcommand*\LWR@lwarpmkversion[2]{\def\lwarpmkversion{\jobname.luar}}
```

### 40.3.1 Helper macros

\LWR@shellescapecmd The LaTeX compile option for shell escape, if used.

```

1663 \ifshellescape
1664     \def\LWR@shellescapecmd{--shell-escape }
1665 \else
1666     \def\LWR@shellescapecmd{}
1667 \fi
```

\LWR@compilecmd {\langle engine\rangle} {\langle suffix\rangle}

Used to form the basic compilation command for a document, adding the optional shell escape.

Engine is *pdflatex*, etc. Suffix is empty or \_html

```

1668 \newcommand*\LWR@compilecmd[2]{%
1669     \def\LWR@shellescapecmd{\jobname#2}%
1670 }
```

\LWR@addcompilecmd {\langle cmd\rangle} {\langle suffix\rangle}

Adds to the compilation command.

Cmd is *dvipdfmx*, etc. Suffix is empty or \_html

```
1671 \newcommand*{\LWR@addcompilecmd}[2]{%
1672     \LWRop{sed}
1673     #1 \jobname#2%
1674 }
```

\LWR@unknownengine Error message if not sure which L<sup>A</sup>T<sub>E</sub>X engine is being used.

```
1675 \newcommand*{\LWR@unknownengine}{%
1676     \PackageError{l warp}%
1677     {Unknown LATEX engine.}%
1678     {L warp only knows about pdflatex, dvi latex, xelatex, lualatex, and upLateX.}%
1679 }
```

\LWR@latexmkvar {<varname>} {<value>}

Adds a *latexmk* variable assignment.

```
1680 \newcommand*{\LWR@latexmkvar}[2]{%
1681     -e
1682     \LWRop{quote}%
1683     \LWRdollar #1=q/#2/%
1684     \LWRop{quote}
1685 }
```

\LWR@latexmkcmd {<latextmk options>}

Sets a call to *latexmk* with the given options, possibly adding --shell-escape, and also adding the indexing program.

```
1686 \newcommand*{\LWR@latexmkcmd}[1]{%
1687     latexmk \space \LWR@shellescapecmd \space #1 \space
1688     -recorder \space
1689     \LWR@latexmkvar{makeindex}{\LWR@LatexmkIndexCmd}
1690 }
```

\LWR@latexmkdvipdfm {<dvipdfm or dvipdfmx>}

Adds the options settings for *dvipdfm* or *dvipdfmx*.

```
1691 \newcommand*{\LWR@latexmkdvipdfm}[1]{%
1692     -pdfdvi \space
1693     \LWR@latexmkvar{dvipdf}{%
1694         #1
1695         \@percentchar 0
1696         -o \@percentchar D
1697         \@percentchar S%
1698     }
1699 }
```

---

\LWR@compileuplatex Sets compile options for upLATEX with ujarticle or related classes.

```

1700 \newcommand*\LWR@compileuplatex{%
1701     \def\LWR@tempprintlatexcmd{%
1702         \LWR@compilecmd{uplatex}{}%
1703         \LWR@addcompilecmd{dvipdfmx}{}%
1704     }%
1705     \def\LWR@tempHTMLlatexcmd{%
1706         \LWR@compilecmd{uplatex}{_html}%
1707         \LWR@addcompilecmd{dvipdfmx}{_html}%
1708     }%
1709 }
```

\LWR@PrintLatexCmd If not set by the user, the following sets the command to use to compile the source to PDF form.  
 \LWR@HTMLLatexCmd

If using *latexmk*, a complicated string is created, eventually resulting in something such as:

For *xelatex* with --shell-escape:

---

```
[[latexmk -xelatex --shell-escape -recorder
-e '$makeindex = q/makeindex -s lwarp.ist/' <jobname>.html]]
```

---

For *dvipdfmx*:

---

```
[[latexmk -pdfdvi -e '$dvipdf=q/dvipdfmx %o -o %D %S/'
-recorder
-e '$makeindex=q/makeindex -s lwarp.ist/' <jobname>.html]]
```

---

For the following, temporary values are computed, but the permanent values are only set if the originals were not assigned by the user.

```
1710 \ifbool{\LWR@latexmk}{
```

For *latexmk* with *pdflatex* or *lualatex*:

```
1711     \ifpdf
```

For *latexmk* with *pdflatex*:

```
1712     \ifPDFTeX
1713         \def\LWR@latextcmd{\LWR@latexmkcmd{-pdf -dvi- -ps-}}
1714     \else
```

For *latexmk* with *lualatex*:

```
1715     \ifLuaTeX
```

```

1716           \def\LWR@latexcmd{\LWR@latexmkcmd{-lualatex}}
1717           \else
1718             \LWR@unknownengine
1719           \fi
1720         \fi
1721     \else% \ifpdf

```

For *latexmk* with *xelatex* or DVI *latex*:

```
1722     \ifXeTeX
```

For *latexmk* with *xelatex*:

```

1723           \def\LWR@latexcmd{\LWR@latexmkcmd{-xelatex}}
1724     \else% \ifXeTeX

```

For *latexmk* with DVI *latex*:

```

1725           \ifbool{LWR@dvipdfm}{
1726             \def\LWR@latexcmd{%
1727               \LWR@latexmkcmd{%
1728                 \LWR@latexmkdvipdfm{dvipdfm}%
1729               }
1730             }
1731           }{
1732             \ifbool{LWR@dvipdfmx}{
1733               \def\LWR@latexcmd{%
1734                 \LWR@latexmkcmd{%
1735                   \LWR@latexmkdvipdfm{dvipdfmx}%
1736                 }
1737               }
1738             }{
1739               \def\LWR@latexcmd{\LWR@latexmkcmd{-pdffps}}
1740             }
1741           }
1742         \fi
1743     \fi% \ifpdf

```

The final assignment if *latexmk*:

```

1744   \def\LWR@tempprintlatexcmd{\LWR@latexcmd \space \jobname}
1745   \def\LWR@tempHTMLlatexcmd{\LWR@latexcmd \space \jobname_html}
1746 }% latexmk

```

Without *latexmk*, the compiling command is simply the compiler name and the optional shell escape:

```

1747 {%
1748   \ifpdf

```

For *pdflatex* or *lualatex*:

```
1749     \ifPDFTeX
```

For *pdflatex*:

```
1750      \def\LWR@tempprintlatexcmd{\LWR@compilecmd{pdflatex}{}}  
1751      \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{pdflatex}{_html}}  
1752      \else  
1753          \ifLuaTeX
```

For *lualatex*:

```
1754      \def\LWR@tempprintlatexcmd{\LWR@compilecmd{lualatex}{}}  
1755      \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{lualatex}{_html}}  
1756      \else  
1757          \LWR@unknownengine  
1758      \fi  
1759      \fi  
1760  \else% \ifpdf
```

For dvi *latex* or *xelatex*:

```
1761      \ifXeTeX
```

For *xelatex*:

```
1762      \def\LWR@tempprintlatexcmd{\LWR@compilecmd{xelatex}{}}  
1763      \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{xelatex}{_html}}  
1764  \else
```

For dvi *latex*. Default to *dvisps*, unless told to use *dvipdfm* or *dvipdfmx*:

```
1765      \ifbool{\LWR@dvipdfm}{
```

For dvi *latex* with *dvipdfm*:

```
1766      \def\LWR@tempprintlatexcmd{  
1767          \LWR@compilecmd{latex}{}  
1768          \LWR@addcompilecmd{dvipdfm}{}  
1769      }  
1770      \def\LWR@tempHTMLlatexcmd{  
1771          \LWR@compilecmd{latex}{_html}  
1772          \LWR@addcompilecmd{dvipdfm}{_html}  
1773      }  
1774  }{  
1775      \ifbool{\LWR@dvipdfmx}{
```

For dvi *latex* with *dvipdfmx*:

```
1776      \def\LWR@tempprintlatexcmd{  
1777          \LWR@compilecmd{latex}{}  
1778          \LWR@addcompilecmd{dvipdfmx}{}  
1779      }  
1780      \def\LWR@tempHTMLlatexcmd{  
1781          \LWR@compilecmd{latex}{_html}  
1782          \LWR@addcompilecmd{dvipdfmx}{_html}  
1783      }
```

```
1784 }% dvips
```

For dvi *latex* with *dvips* and *ps2pdf*:

```
1785 \def\LWR@tempprintlatexcmd{%
1786   \LWR@compilecmd{latex}{}
1787   \LWR@addcompilecmd{dvips}{}
1788   \LWR@addcompilecmd{ps2pdf}{}.ps
1789 }
1790 \def\LWR@tempHTMLlatexcmd{%
1791   \LWR@compilecmd{latex}{_html}
1792   \LWR@addcompilecmd{dvips}{_html}
1793   \LWR@addcompilecmd{ps2pdf}{_html}.ps
1794 }
1795 }
1796 }
1797 \fi% \ifXeTeX
1798 \fi% \ifpdf
1799 }% latexmk
```

For *ujarticle*, *utarticle*, and related, using up<sup>L</sup>TeX and *dvipdfmx*:

```
1800 \@ifclassloaded{ujarticle}{\LWR@compileuplateX}{}
1801 \@ifclassloaded{ujbook}{\LWR@compileuplateX}{}
1802 \@ifclassloaded{ujreport}{\LWR@compileuplateX}{}
1803 \@ifclassloaded{utarticle}{\LWR@compileuplateX}{}
1804 \@ifclassloaded{utbook}{\LWR@compileuplateX}{}
1805 \@ifclassloaded{utreport}{\LWR@compileuplateX}{}
```

Only make the setting permanent if the original was empty:

```
1806 \ifdefempty{\LWR@PrintLatexCmd}{%
1807   \def\LWR@PrintLatexCmd{\LWR@tempprintlatexcmd}
1808 }
1809 \ifdefempty{\LWR@HTMLLatexCmd}{%
1810   \def\LWR@HTMLLatexCmd{\LWR@tempHTMLlatexcmd}
1811 }
```

\LWR@writeconf {<filename>}

Common code for each of *lwarfpmk.conf* and <project>.lwarfpmkconf. Each entry is a variable name, the equal sign, and a quoted string inside [[ and ]], which are *lua*'s long quote characters, allowing the use of single and double quotes inside.

```
1812 \newcommand{\LWR@writeconf}[1]{%
1813 \ifcsdef{\LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
1814 \immediate\openout\LWR@quickfile=#1
1815 \immediate\write\LWR@quickfile{confversion = [[\LWR@lwarfconfversion]]}
1816 \ifbool{usingOSWindows}{%
1817   \immediate\write\LWR@quickfile{opsystem = [[Windows]]}
1818 }{%
1819   \immediate\write\LWR@quickfile{opsystem = [[Unix]]}
1820 }
1821 \immediate\write\LWR@quickfile{sourcename = [[\jobname]]}
```

```

1822 \immediate\write\LWR@quickfile{homehtmlfilename = [[\HomeHTMLFilename]]}
1823 \immediate\write\LWR@quickfile{htmlfilename = [[\HTMLFilename]]}
1824 \immediate\write\LWR@quickfile{imagesdirectory = [[\LWR@ImagesDirectory]]}
1825 \immediate\write\LWR@quickfile{imagesname = [[\LWR@ImagesName]]}
1826 \immediate\write\LWR@quickfile{latexmk = [[\ifbool{\LWR@Latexmk}{true}{false}]]}
1827 \immediate\write\LWR@quickfile{printlatexcmd = [[\LWR@PrintLatexCmd]]}
1828 \immediate\write\LWR@quickfile{HTMLlatexcmd = [[\LWR@HTMLLatexCmd]]}
1829 \immediate\write\LWR@quickfile{printindexcmd = [[\LWR@PrintIndexCmd]]}
1830 \immediate\write\LWR@quickfile{HTMLindexcmd = [[\LWR@HTMLIndexCmd]]}
1831 \immediate\write\LWR@quickfile{Latexmkindexcmd = [[\LWR@LatexmkIndexCmd]]}
1832 \immediate\write\LWR@quickfile{glossarycmd = [[\LWR@GlossaryCmd]]}
1833 \immediate\write\LWR@quickfile{pdftotextenc = [[\LWR@pdftotextEnc]]}
1834 \immediate\closeout\LWR@quickfile
1835 }
1836
1837 \end{LWRwriteconf}

```

### 40.3.2 lwarpmk.conf

**File** lwarpmk.conf **lwarpmk.conf** is automatically (re-)created by the *lwarf* package when executing `pdflatex <project.tex>`, or similar for *xelatex* or *lualatex*, in print-document generation mode, which is the default unless the `warpHTML` option is given. *lwarpmk.conf* is then used by the utility *lwarpmk*.

**Config file:** 1838 `\begin{LWRwriteconf}`  
 1839  
 1840 `\AtBeginDocument{\LWR@writeconf{lwarpmk.conf}}`  
 1841  
 1842 `\end{LWRwriteconf}`

### 40.3.3 <project>.lwarpmkconf

**File** project.lwarpmkconf A project-specific configuration file for *lwarpmk*.

The `makeindex` and `xindy` options have already been handled for *lwarf.conf*.

**Config file:** 1843 `\begin{LWRwriteconf}`  
 1844  
 1845 `\AtBeginDocument{\LWR@writeconf{\jobname.lwarpmkconf}}`  
 1846  
 1847 `\end{LWRwriteconf}`

## 40.4 lwarf.css

**File** lwarf.css This is the base css layer used by *lwarf*.

This must be present both when compiling the project and also when distributing the HTML files.

**Config file:**

```
1848 \begin{LWRwriteconf}
1849 \begin{filecontents*}[overwrite]{lwarf.css}
1850 /*
1851   CSS stylesheet for the LaTeX Lwarf package
1852   Copyright 2016-2020 Brian Dunn - BD Tech Concepts LLC
1853 */
1854
1855
1856 /* a fix for older browsers: */
1857 header, section, footer, aside, nav, main,
1858   article, figure { display: block; }
1859
1860
1861 A:link {color:#000080 ; text-decoration: none ; }
1862 A:visited {color:#800000 ; }
1863 A:hover {color:#000080 ; text-decoration: underline ;}
1864 A:active {color:#800000 ; }
1865
1866 a.tocbook {display: inline-block ; margin-left: 0em ;
1867   font-weight: bold ; margin-top: 1ex ; margin-bottom: 1ex ; }
1868 a.tocpart {display: inline-block ; margin-left: 0em ;
1869   font-weight: bold ;}
1870 a.tocchapter {display: inline-block ; margin-left: 0em ;
1871   font-weight: bold ;}
1872 a.tocsection {display: inline-block ; margin-left: 1em ;
1873   text-indent: -.5em ; font-weight: bold ;}
1874 a.tocsubsection {display: inline-block ; margin-left: 2em ;
1875   text-indent: -.5em ;}
1876 a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
1877   text-indent: -.5em ;}
1878 a.tocparagraph {display: inline-block ; margin-left: 4em ;
1879   text-indent: -.5em ;}
1880 a.tocsubparagraph {display: inline-block ; margin-left: 5em ;
1881   text-indent: -.5em ;}
1882 a.tocfigure {margin-left: 0em}
1883 a.tocsubfigure {margin-left: 2em}
1884 a.tocitable {margin-left: 0em}
1885 a.tocsubtable {margin-left: 2em}
1886 a.toctheorem {margin-left: 0em}
1887 a.toclstlisting {margin-left: 0em}
1888
1889 body {
1890   font-family: "DejaVu Serif", "Bitstream Vera Serif",
1891     "Lucida Bright", Georgia, serif;
1892   background: #FAF7F4 ;
1893   color: black ;
1894   margin:0em ;
1895   padding:0em ;
1896   font-size: 100% ;
1897   line-height: 1.2 ;
1898 }
1899
1900 p {margin: 1.5ex 0em 1.5ex 0em ;}
1901 table p {margin: .5ex 0em .5ex 0em ;}
1902
1903 /* Holds a section number */
```

```
1904 span.sectionnumber { margin-right: 0em }
1905
1906 /* Inserted in front of index lines */
1907 span.indexitem {margin-left: 0em}
1908 span.indexsubitem {margin-left: 2em}
1909 span.indexsubsubitem {margin-left: 4em}
1910
1911 div.hidden, span.hidden { display: none ; }
1912
1913 kbd, span.texttt {
1914     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
1915             "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
1916             "Courier New", monospace;
1917     font-size: 100% ;
1918 }
1919
1920 pre { padding: 3pt ; }
1921
1922 span.strong, span.textbf, div.strong, div.textbf { font-weight: bold; }
1923
1924 span.textit, div.textit { font-style: italic; }
1925
1926 span.textmd, div.textmd { font-weight: normal; }
1927
1928 span.texteb { font-weight: bolder; }
1929
1930 span.textlg { font-weight: lighter; }
1931
1932 span.textup, div.textup {
1933     font-style: normal;
1934     font-variant: normal;
1935     font-variant-numeric: normal ;
1936 }
1937
1938 span.textsc, div.textsc {
1939     font-variant: small-caps;
1940     font-variant-numeric: oldstyle-nums ;
1941 }
1942
1943 span.textulc, div.textulc {
1944     font-variant: normal ;
1945     font-variant-numeric: normal ;
1946 }
1947
1948 span.textsl, div.textsl { font-style: oblique; }
1949
1950 span.textrm, div.textrm {
1951     font-family: "DejaVu Serif", "Bitstream Vera Serif",
1952         "Lucida Bright", Georgia, serif;
1953 }
1954
1955 span.textsf, div.textsf {
1956     font-family: "DejaVu Sans", "Bitstream Vera Sans",
1957         Geneva, Verdana, sans-serif ;
1958 }
```

```
1959
1960 span.textcircled { border: 1px solid black ; border-radius: 1ex ; }
1961
1962 span.underline {
1963     text-decoration: underline ;
1964     text-decoration-skip: auto ;
1965 }
1966
1967 span.overline {
1968     text-decoration: overline ;
1969     text-decoration-skip: auto ;
1970 }
1971
1972
1973 /* for vertical text: */
1974 div.verticalrl { writing-mode: vertical-rl }
1975 div.horizontaltb { writing-mode: horizontal-tb }
1976
1977
1978 /* for diagbox */
1979 div.diagboxtileN { border-bottom: 1px solid gray }
1980 div.diagboxtileS { border-top: 1px solid gray }
1981
1982 div.diagboxE {
1983     padding-left: 2em ;
1984     text-align: right ;
1985 }
1986
1987 div.diagboxW {
1988     padding-right: 2em ;
1989     text-align: left ;
1990 }
1991
1992
1993
1994 /* For realscripts */
1995 .supsubscript {
1996     display: inline-block;
1997     text-align:left ;
1998 }
1999
2000 .supsubscript sup,
2001 .supsubscript sub {
2002     position: relative;
2003     display: block;
2004     font-size: .5em;
2005     line-height: 1;
2006 }
2007
2008 .supsubscript sup {
2009     top: .5em;
2010 }
2011
2012 .supsubscript sub {
2013     top: .5em;
```

```
2014 }
2015
2016 div.attribution p {
2017     text-align: right ;
2018     font-size: 80%
2019 }
2020
2021 span.poemtitle {
2022     font-size: 120% ; font-weight: bold;
2023 }
2024
2025 pre.tabbing {
2026     font-family: "Linux Libertine Mono O", "Lucida Console",
2027             "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
2028             "Liberation Mono", "FreeMono", "Andale Mono",
2029             "Nimbus Mono L", "Courier New", monospace;
2030 }
2031
2032 blockquote {
2033     display: block ;
2034     margin-left: 2em ;
2035     margin-right: 2em ;
2036 }
2037
2038 /* quotchap is for the quotchap package */
2039 div.quotchap {
2040     display: block ;
2041     font-style: oblique ;
2042     overflow-x: auto ;
2043     margin-left: 2em ;
2044     margin-right: 2em ;
2045 }
2046
2047 blockquote p, div.quotchap p {
2048     line-height: 1.5;
2049     text-align: left ;
2050     font-size: .85em ;
2051 }
2052
2053 /* qauthor is for the quotchap package */
2054 div.qauthor {
2055     display: block ;
2056     text-align: right ;
2057     margin-left: auto ;
2058     margin-right: 2em ;
2059     font-size: 80% ;
2060     font-variant: small-caps;
2061 }
2062
2063 div.qauthor p {
2064     text-align: right ;
2065 }
2066
2067 div.epigraph, div.dictum {
2068     line-height: 1.2;
```

```
2069     text-align: left ;
2070     padding: 3ex 1em 0ex 1em ;
2071 /*      margin: 3ex auto 3ex auto ; /* Epigraph centered */
2072     margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
2073 /*      margin: 3ex 1em 3ex 1em ; /* /* Epigraph to the left */
2074     font-size: .85em ;
2075     max-width: 27em ;
2076 }
2077
2078 div.epigraphsource, div.dictumauthor {
2079     text-align:right ;
2080     margin-left:auto ;
2081 /*      max-width: 50% ; */
2082     border-top: 1px solid #A0A0A0 ;
2083     padding-bottom: 3ex ;
2084     line-height: 1.2;
2085 }
2086
2087 div.epigraph p, div.dictum p { padding: .5ex ; margin: 0ex ;}
2088 div.epigraphsource p, div.dictumauthor p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
2089 div.dictumauthor { font-style:italic }
2090
2091
2092 /* copyrightbox package */
2093 div.copyrightbox { margin: .5ex .5em }
2094 div.copyrightbox p {margin: 0px .5em ; padding: 0px}
2095 div.copyrightboxnote {text-align: left ; font-size: 60%}
2096
2097
2098 /* lettrine package: */
2099 span.lettrine { font-size: 4ex ; float: left ; }
2100 span.lettrinetext { font-variant: small-caps ; }
2101
2102 /* ulem, soul, umoline packages: */
2103 span.uline {
2104     text-decoration: underline ;
2105     text-decoration-skip: auto ;
2106 }
2107
2108 span.uunderline {
2109     text-decoration: underline ;
2110     text-decoration-skip: auto ;
2111     text-decoration-style: double ;
2112 }
2113
2114 span.uwave {
2115     text-decoration: underline ;
2116     text-decoration-skip: auto ;
2117     text-decoration-style: wavy ;
2118 }
2119
2120 span.sout {
2121     text-decoration: line-through ;
2122 }
2123
```

```
2124 span.oline {
2125     text-decoration: overline ;
2126     text-decoration-skip: auto ;
2127 }
2128
2129 span.xout {
2130     text-decoration: line-through ;
2131 }
2132
2133 span.dashuline {
2134     text-decoration: underline ;
2135     text-decoration-skip: auto ;
2136     text-decoration-style: dashed ;
2137 }
2138
2139 span.dotuline {
2140     text-decoration: underline ;
2141     text-decoration-skip: auto ;
2142     text-decoration-style: dotted ;
2143 }
2144
2145 span.letterspacing { letter-spacing: .2ex ; }
2146
2147 span.capsspacing {
2148     font-variant: small-caps ;
2149     letter-spacing: .1ex ;
2150 }
2151
2152 span.highlight { background: #F8E800 ; }
2153
2154
2155
2156
2157 html body {
2158     margin: 0 ;
2159     line-height: 1.2;
2160 }
2161
2162
2163 body div {
2164     margin: 0ex;
2165 }
2166
2167
2168 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
2169 {
2170     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2171             "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2172             "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2173             "Times New Roman", serif;
2174     font-style: normal ;
2175     font-weight: bold ;
2176     text-align: left ;
2177 }
2178
```

```
2179 h1 { /* title of the entire website, used on each page */
2180     text-align: center ;
2181     font-size: 2.5em ;
2182     padding: .4ex 0em 0ex 0em ;
2183 }
2184
2185 div.book {
2186     text-align: center ;
2187     font-size: 2.325em ;
2188     padding: .4ex 0em 0ex 0em ;
2189 }
2190
2191 h2 { font-size: 2.25em }
2192 h3 { font-size: 2em }
2193 h4 { font-size: 1.75em }
2194 h5 { font-size: 1.5em }
2195 h6 { font-size: 1.25em }
2196 span.paragraph {font-size: 1em ; font-variant: normal ;
2197     margin-right: 1em ; }
2198 span.subparagraph {font-size: 1em ; font-variant: normal ;
2199     margin-right: 1em ; }
2200
2201 div.minisec {
2202     font-family: "DejaVu Sans", "Bitstream Vera Sans",
2203         Geneva, Verdana, sans-serif ;
2204     font-style: normal ;
2205     font-weight: bold ;
2206     text-align: left ;
2207 }
2208
2209 h1 {
2210     margin: 0ex 0em 0ex 0em ;
2211     line-height: 1.3;
2212     text-align: center ;
2213 }
2214
2215 h2 {
2216     margin: 1ex 0em 1ex 0em ;
2217     line-height: 1.3;
2218     text-align: center ;
2219 }
2220
2221 h3 {
2222     margin: 3ex 0em 1ex 0em ;
2223     line-height: 1.3;
2224 }
2225
2226 h4 {
2227     margin: 3ex 0em 1ex 0em ;
2228     line-height: 1.3;
2229 }
2230
2231 h5 {
2232     margin: 3ex 0em 1ex 0em ;
2233     line-height: 1.3;
```

```
2234 }
2235
2236 h6 {
2237   margin: 3ex 0em 1ex 0em ;
2238   line-height: 1.3;
2239 }
2240
2241
2242 div.titlepage {
2243   text-align: center ;
2244 }
2245
2246 .footnotes {
2247   text-align: left ;
2248   font-size: .85em ;
2249   margin: 3ex 2em 0ex 2em ;
2250   border-top: 1px solid silver ;
2251 }
2252
2253 .marginpar, .marginparblock {
2254   max-width: 50%;
2255   float: right ;
2256   clear: both ;
2257   text-align: left ;
2258   margin: 1ex 0.5em 1ex 1em ;
2259   padding: 1ex 0.5em 1ex 0.5em ;
2260   font-size: 85% ;
2261   border-top: 1px solid silver ;
2262   border-bottom: 1px solid silver ;
2263   overflow-x: auto ;
2264 }
2265
2266 .marginpar br { margin-bottom: 2ex ; }
2267
2268 div.marginblock, div.marginparblock {
2269   max-width:50%;
2270   min-width: 10em; /* room for caption */
2271   float:right;
2272   text-align:left;
2273   margin: 1ex 0.5em 1ex 1em ;
2274   padding: 1ex 0.5em 1ex 0.5em ;
2275   overflow-x: auto;
2276 }
2277
2278 div.marginblock div.minipage,
2279 div.marginparblock div.minipage {
2280   display: inline-block ;
2281   margin: 0pt auto 0pt auto ;
2282 }
2283
2284 div.marginblock div.minipage p ,
2285 div.marginparblock div.minipage p
2286   { font-size: 85%}
2287
2288 div.marginblock br ,
```

```
2289 div.marginparblock br
2290     { margin-bottom: 2ex ; }
2291
2292 div.bodycontainer {
2293     float: left ;
2294     width: 80% ;
2295 }
2296
2297 div.bodywithoutsidetoc div.bodycontainer {
2298     float: none ;
2299     width: 100% ;
2300 }
2301
2302 section.textbody div.footnotes{
2303     margin: 3ex 2em 0ex 2em ;
2304     border-bottom: 2px solid silver ;
2305 }
2306
2307 .footnoteheader {
2308     border-top: 2px solid silver ;
2309     margin-top: 3ex ;
2310     padding-top: 1ex ;
2311     font-weight: bold ;
2312 }
2313
2314 .mpfootnotes {
2315     text-align: left ;
2316     font-size: .85em ;
2317     margin-left: 1em ;
2318     border-top: 1px solid silver ;
2319 }
2320
2321 /* Remove footnote top border in the title page. */
2322 div.titlepage div.mpfootnotes {
2323     border-top: none ;
2324 }
2325
2326
2327
2328 ul, ol {
2329     margin: 1ex 1em 1ex 0em;
2330     line-height: 1.2;
2331 }
2332
2333 body dir, body menu {
2334     margin: 3ex 1em 3ex 0em;
2335     line-height: 1.2;
2336 }
2337
2338 li { margin: 0ex 0em 1ex 0em; }
2339
2340 html {
2341     margin: 0;
2342     padding: 0;
2343 }
```

```
2344
2345 .programlisting {
2346     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2347             "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2348             "Courier New", monospace;
2349     margin: 1ex 0ex 1ex 0ex ;
2350     padding: .5ex 0pt .5ex 0pt ;
2351     overflow-x: auto;
2352 }
2353
2354 section.textbody>pre.programlisting {
2355 border-top: 1px solid silver ;
2356 border-bottom: 1px solid silver ;
2357 }
2358
2359
2360 div.displaymath {
2361     text-align: center ;
2362 }
2363
2364 div.displaymathnumbered {
2365     text-align: right ;
2366     margin-left: 5% ;
2367     margin-right: 5% ;
2368     min-width: 2.5in ;
2369 }
2370
2371 @media all and (min-width: 400px) {
2372     div.displaymathnumbered {
2373         margin-left: 10% ;
2374         margin-right: 10% ;
2375     }
2376 }
2377
2378 @media all and (min-width: 800px) {
2379     div.displaymathnumbered {
2380         margin-right: 20% ;
2381     }
2382 }
2383
2384 @media all and (min-width: 1200px) {
2385     div.displaymathnumbered {
2386         margin-right: 30% ;
2387     }
2388 }
2389
2390
2391 .inlineprogramlisting {
2392     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2393             "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2394             "Courier New", monospace;
2395     overflow-x: auto;
2396 }
2397
2398 span.listinglabel {
```

```
2399     display: inline-block ;
2400     font-size: 70% ;
2401     width: 4em ;
2402     text-align: right ;
2403     margin-right: 2em ;
2404 }
2405
2406 div.abstract {
2407   margin: 2em 5% 2em 5% ;
2408   padding: 1ex 1em 1ex 1em ;
2409 /*  font-weight: bold ; */
2410   font-size: 90% ;
2411   text-align: left ;
2412 }
2413
2414 div.abstract dl {line-height:1.5;}
2415 div.abstract dt {color:#304070;}
2416
2417 div.abstracttitle{
2418   font-family: "URW Classico", Optima, "Linux Biolinum 0",
2419     "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
2420     "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2421   font-weight:bold;
2422   font-size:1.25em;
2423   text-align: center ;
2424 }
2425
2426 span.abstractrunintitle{
2427   font-family: "URW Classico", Optima, "Linux Biolinum 0",
2428     "Linux Libertine 0", "Liberation Serif", "Nimbus Roman No 9 L",
2429     "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2430   font-weight:bold;
2431 }
2432
2433
2434 .verbatim {
2435   overflow-x: auto ;
2436 }
2437
2438 .alltt {
2439   overflow-x: auto ;
2440 }
2441
2442
2443 .bverbatim {
2444   margin: 1ex 0pt 1ex 0pt ;
2445   padding: .5ex 0pt .5ex 0pt ;
2446   overflow-x: auto ;
2447 }
2448
2449 .lverbatim {
2450   margin: 1ex 0pt 1ex 0pt ;
2451   padding: .5ex 0pt .5ex 0pt ;
2452   overflow-x: auto ;
2453 }
```

```
2454
2455 .fancyvrb {
2456     font-size:.85em ;
2457     margin: 3ex 0pt 3ex 0pt
2458 }
2459
2460 .fancyvrblabel {
2461     font-size: .85em ;
2462     text-align: center ;
2463     font-weight: bold ;
2464     margin-top: 1ex ;
2465     margin-bottom: 1ex ;
2466 }
2467
2468
2469 .verse {
2470     font-family: "Linux Libertine Mono O", "Lucida Console",
2471         "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
2472         "Liberation Mono", "FreeMono", "Andale Mono",
2473         "Nimbus Mono L", "Courier New", monospace;
2474     margin-left: 1em ;
2475 }
2476
2477
2478 div.singlespace { line-height: 1.2 ; }
2479 div.onehalfspace { line-height: 1.5 ; }
2480 div.doublespace { line-height: 2 ; }
2481
2482
2483 /* Word processor format output: */
2484 div.wpfigure { border: 1px solid red ; margin: .5ex ; padding: .5ex ; }
2485 div.wptable { border: 1px solid blue ; margin: .5ex ; padding: .5ex ; }
2486 div.wpmminipage { border: 1px solid green ; margin: .5ex ; padding: .5ex ; }
2487
2488
2489
2490
2491 /* Minipage environments, vertically aligned to top, center, bottom: */
2492 .minipage, .fminipage, .fcolorminipage {
2493     /* display: inline-block ; */
2494         /* Mini pages which follow each other will be tiled. */
2495     margin: .25em .25em .25em .25em;
2496     padding: .25em .25em .25em .25em;
2497     display: inline-flex;
2498     flex-direction: column ;
2499     overflow: auto;
2500 }
2501
2502 .inlineminipage {
2503     display: inline-block ;
2504     text-align: left
2505 }
2506
2507 /* Paragraphs in the flexbox did not collapse their margins. */
2508 /* Have not yet researched this. */
```

```
2509 .minipage p {margin: .75ex 0em .75ex 0em ;}
2510
2511 .fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
2512 .fcolorbox .minipage, .fcolorboxBlock .minipage
2513   {border: none ; background: none;}
2514
2515 .fbox, .fboxBlock { border: 1px solid black ; }
2516
2517 .fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
2518 .fminipage, .fcolorminipage
2519   {display: inline-block;}
2520
2521 .shadowbox, .shabox {
2522   border: 1px solid black;
2523   box-shadow: 3px 3px 3px #808080 ;
2524   border-radius: 0px ;
2525   padding: .4ex .3em .4ex .3em ;
2526   margin: 0pt .3ex 0pt .3ex ;
2527   display: inline-block ;
2528 }
2529
2530 .doublebox {
2531   border: 3px double black;
2532   border-radius: 0px ;
2533   padding: .4ex .3em .4ex .3em ;
2534   margin: 0pt .3ex 0pt .3ex ;
2535   display: inline-block ;
2536 }
2537
2538 .ovalbox, .Ovalbox {
2539   border: 1px solid black;
2540   border-radius: 1ex ;
2541   padding: .4ex .3em .4ex .3em ;
2542   margin: 0pt .3ex 0pt .3ex ;
2543   display: inline-block ;
2544 }
2545
2546 .Ovalbox { border-width: 2px ; }
2547
2548 .framebox {
2549   border: 1px solid black;
2550   border-radius: 0px ;
2551   padding: .3ex .2em 0ex .2em ;
2552   margin: 0pt .1ex 0pt .1ex ;
2553   display: inline-block ;
2554 }
2555
2556
2557 .mdframed {
2558   padding: 0ex ;
2559   margin: 2ex 0em 2ex 0em ;
2560 }
2561
2562 .mdframed p { padding: 0ex .5em 0ex .5em ; }
2563
```

```
2564 .mdframed dl { padding: 1ex .5em 0ex .5em ; }
2565
2566 .mdframedtitle {
2567     padding: .5ex 0pt 0pt 0pt ;
2568     border-radius: 10pt 10pt 0pt 0pt ;
2569     display: block ;
2570     margin-bottom: 1ex ;
2571 }
2572
2573 .mdframedsubtitle {
2574     display: block ;
2575 }
2576
2577 .mdframedsubsubtitle {
2578     display: block ;
2579 }
2580
2581 .mdtheorem {
2582     padding: 0ex .5em 0ex .5em ;
2583     margin: 3ex 5% 3ex 5% ;
2584 }
2585
2586
2587 /* framed package */
2588 .framed, pre.boxedverbatim, fcolorbox {
2589     margin: 3ex 0em 3ex 0em ;
2590     border: 1px solid black;
2591     border-radius: 0px ;
2592     padding: .3ex 1em 0ex 1em ;
2593     display: block ;
2594 }
2595
2596 .shaded {
2597     margin: 3ex 0em 3ex 0em ;
2598     padding: .3ex 1em .3ex 1em ;
2599     display: block ;
2600 }
2601
2602 .snugframed {
2603     margin: 3ex 0em 3ex 0em ;
2604     border: 1px solid black;
2605     border-radius: 0px ;
2606     display: block ;
2607 }
2608
2609 .framedleftbar {
2610     margin: 3ex 0em 3ex 0em ;
2611     border-left: 3pt solid black;
2612     border-radius: 0px ;
2613     padding: .3ex .2em .3ex 1em ;
2614     display: block ;
2615 }
2616
2617 .framedtitle {
2618     margin: 0em ;
```

```
2619     padding: 0em ;
2620     font-size: 130%
2621 }
2622
2623 .framedtitle p { padding: .3em }
2624
2625
2626 /* For the niceframe package: */
2627
2628 div.niceframe, div.curlyframe, div.artdecoframe, div.generalframe {
2629     padding: 1ex ;
2630     margin: 2ex auto ;
2631     border-radius: 2ex ;
2632 }
2633
2634 div.niceframe {
2635     border: 6px groove black ;
2636 }
2637
2638 div.curlyframe {
2639     border-left: 3px dotted black ;
2640     border-right: 3px dotted black ;
2641     border-radius: 6ex ;
2642 }
2643
2644 div.artdecoframe {
2645     border-left: 10px double black ;
2646     border-right: 10px double black ;
2647     border-radius: 6ex ;
2648 }
2649
2650 div.generalframe {
2651     border: 6px groove black ;
2652 }
2653
2654
2655
2656 dl {
2657     margin: 1ex 2em 1ex 0em;
2658     line-height: 1.3;
2659 }
2660
2661 dl dt {
2662     display: block ;
2663     float:left ;
2664     font-weight: bold;
2665     padding-right: 1em ;
2666 }
2667
2668 dl dd { display: block ; }
2669
2670 dl dd:after { content: "" ; display: block ; clear: both }
2671
2672 dl dd p { margin-top: 0em; }
2673
```

```
2674 dd ul, dd ol, dd dl { clear: both ; padding-top: 1ex }
2675
2676
2677 nav {
2678     font-family: "URW Classico", Optima, "Linux Biolinum 0",
2679             "DejaVu Sans", "Bitstream Vera Sans",
2680             Geneva, Verdana, sans-serif ;
2681     margin-bottom: 4ex ;
2682 }
2683
2684 nav p {
2685     line-height: 1.2 ;
2686     margin-top:.5ex ;
2687     margin-bottom:.5ex;
2688     font-size: .9em ;
2689 }
2690
2691
2692
2693 img, img.hyperimage, img.borderimage {
2694     max-width: 600px;
2695     border: 1px solid silver;
2696     box-shadow: 3px 3px 3px #808080 ;
2697     padding: .5% ;
2698     margin: .5% ;
2699     background: none ;
2700 }
2701
2702 img.inlineimage{
2703     padding: 0px ;
2704     box-shadow: none ;
2705     border: none ;
2706     background: none ;
2707     margin: 0px ;
2708     display: inline-block ;
2709     border-radius: 0px ;
2710 }
2711
2712 img.logoimage{
2713     max-width: 300px ;
2714     box-shadow: 3px 3px 3px #808080 ;
2715     border: 1px solid black ;
2716     background:none ;
2717     padding:0 ;
2718     margin:.5ex ;
2719     border-radius: 10px ;
2720 }
2721
2722
2723 .section {
2724 /*
2725     To have each section float relative to each other:
2726 */
2727 /*
2728     display: block ;
```

```
2729     float: left ;
2730     position: relative ;
2731     background: white ;
2732     border: 1px solid silver ;
2733     padding: .5em ;
2734 */
2735     margin: 0ex .5em 0ex .5em ;
2736     padding: 0 ;
2737 }
2738
2739
2740 figure {
2741     margin: 5ex auto 5ex auto ;
2742     padding: 1ex 1em 1ex 1em ;
2743     overflow-x: auto ;
2744 }
2745
2746
2747 /* To automatically center images in figures: */
2748 /*
2749 figure img.inlineimage {
2750     margin: 0ex auto 0ex auto ;
2751     display: block ;
2752 }
2753 */
2754
2755 /* To automatically center minipages in figures: */
2756 /*
2757 figure div.minipage, figure div.minipage div.minipage {
2758     margin: 1ex auto 1ex auto ;
2759     display: block ;
2760 }
2761 */
2762
2763 figure figure { margin: 0pt }
2764
2765 figure div.minipage p { font-size: 85% ; }
2766
2767 figure.subfigure, figure.subtable {
2768     display: inline-block ; margin: 3ex 1em 3ex 1em ;
2769 }
2770
2771 div.figurecaption .minipage { margin:0 ; padding: 0 }
2772
2773 div.minipage figure { border: none ; box-shadow: none ; }
2774 div.minipage figure.table { margin: 0ex }
2775 div.minipage div.footnotes { margin: 1ex 2em 0ex 2em }
2776
2777 div.floatrow { text-align: center; }
2778
2779 div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }
2780
2781 div.floatfoot { font-size: .85em ;
2782     border-top: 1px solid silver ; line-height: 1.2 ; }
2783
```

```
2784 div.figurecaption , .lstlistingtitle {  
2785     font-size: .85em ;  
2786     text-align: center ;  
2787     font-weight: bold ;  
2788     margin-top: 1ex ;  
2789     margin-bottom: 1ex ;  
2790 }  
2791  
2792 figure.subfigure div.figurecaption, figure.subtable div.figurecaption {  
2793     border-bottom: none ; background: none ;  
2794 }  
2795  
2796 div.nonfloatcaption {  
2797     margin: 1ex auto 1ex auto ;  
2798     font-size: .85em ;  
2799     text-align: center ;  
2800     font-weight: bold ;  
2801 }  
2802  
2803 /* For a \RawCaption inside a minipage inside a figure's floatrow: */  
2804 figure div.floatrow div.minipage div.figurecaption {  
2805     border: none ;  
2806     background: none ;  
2807 }  
2808  
2809  
2810 /* For packages such as float, rotfloat, and algorithm2e: */  
2811  
2812 figure.boxed, figure.boxruled {  
2813     border: 1px solid black ;  
2814 }  
2815  
2816 figure.ruled {  
2817     border-top: 1px solid black ;  
2818     border-bottom: 1px solid black ;  
2819     border-left: 0px ;  
2820     border-right: 0px ;  
2821     border-radius: 0px ;  
2822     background: none ;  
2823     box-shadow: none ;  
2824 }  
2825  
2826 figure.ruled div.figurecaption, figure.boxruled div.figurecaption {  
2827     border-top: 1px solid silver ;  
2828     border-bottom: 1px solid silver ;  
2829 }  
2830  
2831  
2832 table {  
2833     margin: 1ex auto 1ex auto ;  
2834     border-collapse: separate ;  
2835     border-spacing: 0px ;  
2836     line-height: 1.3 ;  
2837 }  
2838
```

```
2839 table > tbody > tr.hline > td {border-top: 1px solid #808080 ; margin-top: 0ex ;  
2840     margin-bottom: 0ex ; } /* for \hline */  
2841  
2842 tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;  
2843     margin-bottom: 0ex ; } /* for \toprule, \bottomrule */  
2844  
2845 td {padding: .5ex .5em .5ex .5em ;}  
2846  
2847 table td.tdl { text-align: left ; vertical-align: middle ; }  
2848 table td.tdc { text-align: center ; vertical-align: middle ; }  
2849 table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }  
2850 table td.tdbang { text-align: center ; vertical-align: middle ; }  
2851 table td.tdr { text-align: right ; vertical-align: middle ; }  
2852 table td.tdp { text-align: left ; vertical-align: bottom ; }  
2853 table td.tdm { text-align: left ; vertical-align: middle ; }  
2854 table td.tdb { text-align: left ; vertical-align: top ; }  
2855 table td.tdP { text-align: center ; vertical-align: bottom ; }  
2856 table td.tdM { text-align: center ; vertical-align: middle ; }  
2857 table td.tdB { text-align: center ; vertical-align: top ; }  
2858  
2859 table td.tvertbarl { border-left: 1px solid black }  
2860 table td.tvertbarldouble { border-left: 4px double black }  
2861 table td.tvertbarr { border-right: 1px solid black }  
2862 table td.tvertbarrdouble { border-right: 4px double black }  
2863  
2864 table td.tvertbarldash { border-left: 1px dashed black }  
2865 table td.tvertbarldoubledash { border-left: 2px dashed black }  
2866 table td.tvertbarrdash { border-right: 1px dashed black }  
2867 table td.tvertbarrdoubledash { border-right: 2px dashed black }  
2868  
2869  
2870 /* for cmidrules: */  
2871 table td.tdrule {  
2872     border-top: 1px solid #A0A0A0 ;  
2873 }  
2874  
2875 table td.tdrulel {  
2876     border-top-left-radius:.5em ;  
2877     border-top: 1px solid #A0A0A0 ;  
2878 }  
2879  
2880 table td.tdruler {  
2881     border-top-right-radius:.5em ;  
2882     border-top: 1px solid #A0A0A0 ;  
2883 }  
2884  
2885 table td.tdrulelr {  
2886     border-top-left-radius:.5em ;  
2887     border-top-right-radius:.5em ;  
2888     border-top: 1px solid #A0A0A0 ;  
2889 }  
2890  
2891  
2892 /* Margins of paragraphs inside table cells: */  
2893 td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
```

```
2894     padding-bottom: 1ex ; margin: 0ex ; }
2895 td.tdm p , td.tmbrule p , td.tdm p , td.tdMrule p { padding-top: 1ex ;
2896     padding-bottom: 1ex ; margin: 0ex ; }
2897 td.tdb p , td.tdbrule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
2898     padding-bottom: 1ex ; margin: 0ex ; }
2899
2900 td.tdp , td.tdprule , td.tdP , td.tdPrule
2901     { padding: 0ex .5em 0ex .5em ; }
2902 td.tdm , td.tdmrule , td.tdM , td.tdMrule
2903     { padding: 0ex .5em 0ex .5em ; }
2904 td.tdb , td.tdbrule , td.tdB , td.tdBrule
2905     { padding: 0ex .5em 0ex .5em ; }
2906
2907
2908 /* table notes: */
2909 .tnotes {
2910     margin: 0ex 5% 1ex 5% ;
2911     padding: 0.5ex 1em 0.5ex 1em;
2912     font-size:.80em;
2913     text-align: left ;
2914 }
2915
2916 .minipage .tnotes {
2917     margin: 0pt ;
2918     padding: 0pt ;
2919 }
2920
2921 .tnotes dl dt p {margin-bottom:0px;}
2922
2923 .tnoteitemheader {margin-right: 1em;}
2924
2925
2926 /* for colortbl and cell color */
2927 div.cellcolor {
2928     width: 100% ;
2929     padding: .5ex .5em .5ex .5em ;
2930     margin: -.5ex -.5em -.5ex -.5em ;
2931 }
2932
2933
2934 /* for lyluatex */
2935 span.lyluatex {
2936     display: inline-block ;
2937 }
2938
2939 div.lyluatex p span.lateximagesource img {
2940     display: block ;
2941     margin-top: 3ex ;
2942     margin-bottom: 3ex ;
2943 }
2944
2945
2946 /* for bigdelim */
2947 .ldelim, .rdelim { font-size: 200% }
2948
```

```
2949
2950 /* center, flushleft, flushright environments */
2951 div.center{text-align:center;}
2952 div.center table {margin-left:auto;margin-right:auto;}
2953 div.flushleft{text-align:left;}
2954 div.flushleft table {margin-left:0em ; margin-right:auto;}
2955 div.flushright{text-align:right;}
2956 div.flushright table {margin-left:auto ; margin-right: 0em ;}
2957
2958
2959 /* Fancybox */
2960 div.Btrivlist table tr td {
2961     padding: .2ex 0em ;
2962 }
2963
2964
2965 /* program listing callouts: */
2966 span.callout {
2967     font-family: "DejaVu Sans", "Bitstream Vera Sans",
2968         Geneva, Verdana, sans-serif ;
2969     border-radius: .5em;
2970     background-color:black;
2971     color:white;
2972     padding:0px .25em 0px .25em;
2973     margin: 0 ;
2974     font-weight: bold;
2975     font-size:.72em ;
2976 }
2977
2978 div.programlisting pre.verbatim span.callout{
2979     font-size: .85em ;
2980 }
2981
2982 span.verbatim {
2983     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2984         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2985         "Courier New", monospace;
2986 }
2987
2988
2989
2990 div.published
2991 {
2992     text-align: center ;
2993     font-variant: normal ;
2994     font-style: italic ;
2995     font-size: 1em ;
2996     margin: 1ex 0em 1ex 0em ;
2997 }
2998
2999 div.subtitle
3000 {
3001     text-align: center ;
3002     font-variant: normal ;
3003     font-style: italic ;
```

```
3004     font-size: 1.25em ;
3005     margin: 1ex 0em 1ex 0em ;
3006 }
3007
3008 div.subtitle p { margin: 1ex ; }
3009
3010 div.author
3011 {
3012     font-variant: normal ;
3013     font-style: normal ;
3014     font-size: 1em ;
3015     margin: 1ex 0em 1ex 0em ;
3016 }
3017
3018 div.oneauthor {
3019     display: inline-block ;
3020     margin: 0ex 1em 0ex 1em ;
3021 }
3022
3023 /*
3024 div.author table {
3025     margin: 1ex auto 0ex auto ;
3026     background: none ;
3027 }
3028
3029 div.author table tbody tr td { padding: .25ex ; }
3030 */
3031
3032 span.affiliation {font-size: .85em ; font-variant: small-caps; }
3033
3034 div.titledate {
3035     text-align: center ;
3036     font-size: .85em ;
3037     font-style: italic;
3038     margin: 1ex 0em 1ex 0em ;
3039 }
3040
3041
3042 nav.topnavigation{
3043     text-align: left ;
3044     padding: 0.5ex 1em 0.5ex 1em ;
3045 /*     margin: 2ex 0em 3ex 0em ; */
3046     margin: 0 ;
3047     border-bottom: 1px solid silver ;
3048     border-top: 1px solid silver ;
3049     clear:both ;
3050 }
3051
3052 nav.botnavigation{
3053     text-align: left ;
3054     padding: 0.5ex 1em 0.5ex 1em ;
3055 /*     margin: 3ex 0em 2ex 0em ; */
3056     margin: 0 ;
3057     border-top: 1px solid silver ;
3058     border-bottom: 1px solid silver ;
```

```
3059     clear:both ;
3060 }
3061
3062
3063 header {
3064     line-height: 1.2 ;
3065     font-size: 1em ;
3066     border-bottom: 1px solid silver ;
3067     margin: 0px ;
3068     padding: 2ex 1em 2ex 1em ;
3069     text-align:left ;
3070 }
3071
3072
3073 footer {
3074     font-size: .85em ;
3075     line-height: 1.2 ;
3076     margin-top: 1ex ;
3077     border-top: 1px solid silver ;
3078     padding: 2ex 1em 2ex 1em ;
3079     clear:both ;
3080     text-align:left ;
3081 }
3082
3083
3084 a.linkhome { font-weight:bold ; font-size: 1em ;}
3085
3086
3087 div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }
3088
3089 img.lateximage{
3090     padding: 0pt ;
3091     margin: 0pt ;
3092     box-shadow: none ;
3093     border: none ;
3094     background: none ;
3095     max-width: 100% ;
3096     border-radius: 0ex ;
3097     border: none ;
3098 }
3099
3100
3101 /* The -1px right margin compensates for the 1px right border. */
3102 /* Without this -1px margin, the body container appears below instead */
3103 /* of floating to the side. */
3104 div.sidetoccontainer {
3105     font-family: "DejaVu Serif", "Bitstream Vera Serif",
3106     "Lucida Bright", Georgia, serif;
3107     float: left ;
3108     width: 20%;
3109     margin: 0pt -1px 3ex 0pt ;
3110     border-right: 1px solid silver;
3111     border-bottom: 1px solid silver;
3112     background: #FAF7F4 ;
3113     font-size:.9em ;
```

```
3114     border-radius: 0px 0px 20px 0px ;
3115 }
3116
3117 div.sidetoccontents {
3118     overflow-y: auto ;
3119     width: 100% ;
3120     text-align: left ;
3121 }
3122
3123
3124 nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;
3125     text-indent: 0 ; }
3126
3127 nav.sidetoc p a {color:black ; font-size: .7em ;}
3128
3129 div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;
3130     border-bottom: 1px solid silver ;    }
3131
3132 nav.sidetoc a:hover {text-decoration: underline ; }
3133
3134
3135
3136 section.textbody { margin: 0ex 1em 0ex 1em ;}
3137
3138
3139 div.multicolsheading { -webkit-column-span: all;
3140     -moz-column-span: all; column-span: all; }
3141 div.multicols { -webkit-columns: 3 380px ;
3142     -moz-columns: 3 380px ; columns: 3 380px ; }
3143 div.multicols p {margin-top: 0ex}
3144
3145
3146 /* Used for xfrac and nicefrac: */
3147 span.numerator {
3148     font-size: 60% ;
3149     vertical-align: .4em ;
3150 }
3151
3152 span.denominator {
3153     font-size: 60%
3154 }
3155
3156
3157 /* Used for algorithm2e: */
3158 div.alg2evline{
3159     margin-left: 1em ;
3160     padding-left: 1em ;
3161     border-left: 1px solid black ;
3162     border-radius: 0px 0px 0px 1ex ;
3163 }
3164
3165 div.alg2evsline{
3166     margin-left: 1em ;
3167     padding-left: 1em ;
3168     border-left: 1px solid black ;
```

```
3169 }
3170
3171 div.alg2enoline{
3172     margin-left: 1em ;
3173     padding-left: 1em ;
3174 }
3175
3176 span.alg2elinenumber{
3177     margin-right: .5em ;
3178     font-size: 50% ;
3179     color: red ;
3180 }
3181
3182
3183 /* Used for algorithmicx: */
3184 span.floatright { float: right ; }
3185
3186
3187 /* keyfloat and tocdata: */
3188 .floatnotes {
3189     margin: 0ex 5% 0ex 5% ;
3190     padding: 0ex 1em 0ex 1em ;
3191     font-size:.80em ;
3192     text-align: left ;
3193 }
3194
3195 .authorartist{
3196     display:block ;
3197     font-size:.70em ;
3198     font-style: italic;
3199 }
3200
3201 nav .authorartist{ display:inline; }
3202
3203
3204
3205 /* Native LaTeX theorems: */
3206
3207 .theoremcontents { font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ; }
3208 .theoremlabel { font-style: normal; font-weight: bold ; margin-right: .5em ; }
3209
3210
3211 /* theorem, amsthm, and ntheorem packages */
3212
3213 span.theoremheader,
3214 span.theoremheaderplain,
3215 span.theoremheaderdefinition,
3216 span.theoremheaderbreak,
3217 span.theoremheadermarginbreak,
3218 span.theoremheaderchangebreak,
3219 span.theoremheaderchange,
3220 span.theoremheadermargin
3221 {
3222     font-style:normal ; font-weight: bold ; margin-right: 1em ;
3223 }
```

```
3224
3225 span.amsthmnameplain,
3226 span.amsthmnamedefinition,
3227 span.amsthmnumberplain,
3228 span.amsthmnumberdefinition
3229 {
3230     font-style:normal ; font-weight: bold ;
3231 }
3232
3233
3234 span.amsthmnameremark,
3235 span.amsthmnumberremark
3236 {font-style:italic ; font-weight: normal ; }
3237
3238
3239 span.amsthmnoteplain,
3240 span.amsthmnotedefinition
3241 {font-style:normal ;}
3242
3243
3244 span.theoremheaderremark,
3245 span.theoremheaderproof,
3246 span.amsthmproofname
3247 {font-style:italic ; font-weight: normal ; margin-right: 1em ; }
3248
3249 span.theoremheadersc
3250 {
3251     font-style:normal ;
3252     font-variant: small-caps ;
3253     font-weight: normal ;
3254     margin-right: 1em ;
3255 }
3256
3257 .theoremendmark {float:right}
3258
3259 div.amsthmbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
3260 div.theorembodybreak, div.theorembodynonumberbreak,
3261 div.theorembodymarginbreak,
3262 div.theorembodychangebreak,
3263 div.theorembodychange,
3264 div.theorembodymargin
3265 {
3266     font-style:italic;
3267     margin-top: 3ex ; margin-bottom: 3ex ;
3268 }
3269
3270 div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
3271 div.theorembodyplainupright, nonumberplainuprightsc,
3272 div.amsthmbodydefinition, div.amsthmbodyremark,
3273 div.amsthmproof
3274 {
3275     font-style: normal ;
3276     margin-top: 3ex ; margin-bottom: 3ex ;
3277 }
3278
```

```
3279 span.amsthmnoteremark {}
3280
3281
3282 /* For the backnaur package: */
3283 div.backnaur {
3284     display: block ;
3285     margin: 2ex 2em 2ex 2em ;
3286 }
3287
3288 div.backnaur p {
3289     margin: .25ex 0ex .25ex 0ex ;
3290 }
3291
3292 div.backnaurprod {
3293     display: inline-block ;
3294     min-width: 8em ;
3295     text-align:right ;
3296 }
3297
3298 div.backnaurdesc {
3299     display: inline-block ;
3300 }
3301
3302
3303 /* For the notes package: */
3304 div.notesimportantnote, div.noteswarningnote, div.notesinformationnote {
3305     clear: both ;
3306     margin: 2ex 2em 2ex 2em ;
3307     border: 1px solid silver ;
3308 }
3309
3310 div.notesicon {
3311     float:left ;
3312     display: inline-block ;
3313     background: gold ;
3314     padding: 0ex 1em 0ex 1em ;
3315     margin-right: 1em ;
3316     font-weight: bold ;
3317 }
3318
3319 div.notescontents { font-style: italic }
3320
3321
3322 /*
3323 For CSS LaTeX and related logos:
3324 Based on spacing demonstrated by the metafont package.
3325 */
3326
3327 .latexlogofont {
3328     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3329             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3330     font-variant: normal ;
3331 }
3332
3333 .latexlogo {
```

```
3334     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3335         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3336     font-size: 1.1em;
3337 }
3338
3339 .latexlogosup {
3340   text-transform: uppercase;
3341   letter-spacing: .03em ;
3342   font-size: 0.7em;
3343   vertical-align: 0.25em;
3344   margin-left: -0.4em;
3345   margin-right: -0.15em;
3346 }
3347
3348 .latexlogosub {
3349   text-transform: uppercase;
3350   vertical-align: -0.27ex;
3351   margin-left: -0.08em;
3352   margin-right: -0.07em;
3353   font-size: 1em;
3354 }
3355
3356 .latexlogotwoe {
3357   text-transform: none ;
3358   font-variant-numeric: oldstyle-nums ;
3359 }
3360
3361 .latexlogotwoesub {
3362   font-style:italic ;
3363   vertical-align: -0.27ex;
3364   margin-left: -0.11em;
3365   margin-right: -0.1em;
3366   font-size: 1em;
3367 }
3368
3369 .xelatexlogo {
3370   font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3371       "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3372   letter-spacing: .03em ;
3373   font-size: 1.1em;
3374 }
3375
3376 .xelatexlogosub {
3377   vertical-align: -0.27ex;
3378   margin-left: -0.0667em;
3379   margin-right: -.05em;
3380   font-size: 1em;
3381   letter-spacing: .03em ;
3382 }
3383
3384 .amslogo {
3385   font-family: "TeXGyreChorus","URW Chancery L",
3386       "Apple Chancery","ITC Zapf Chancery","Monotype Corsiva",
3387       "Linux Libertine O", "Nimbus Roman No 9 L", "FreeSerif",
3388       "Hoefler Text", Times, "Times New Roman", serif ;
```

```
3389     font-style: italic ;
3390 }
3391
3392 .lyxlogo {
3393     font-family: "URW Classico", Optima, "Linux Biolinum 0",
3394         "DejaVu Sans", "Bitstream Vera Sans", Geneva,
3395         Verdana, sans-serif ;
3396 }
3397
3398
3399 /* Only display top and bottom navigation if a small screen: */
3400 /* Hide the sidetoc if a small screen: */
3401 nav.topnavigation { display:none; }
3402 nav.botnavigation { display:none; }
3403
3404 /* Only display the sidetoc's webpage title if a small screen */
3405 span.sidetocthetitle { display: none }
3406
3407 @media screen and (max-width: 50em) {
3408     div.sidetoccontainer {
3409         float: none ;
3410         width: 100% ;
3411         padding: 0 ;
3412         border-radius: 0 ;
3413         border-bottom: 1px solid black ;
3414         border-top: 1px solid black ;
3415         box-shadow: none ;
3416     }
3417     span.sidetocthetitle { display: inline }
3418     nav.botnavigation { display:block }
3419     div.bodycontainer { width: 100% }
3420     .marginpar {
3421         max-width: 100%;
3422         float: none;
3423         display:block ;
3424         margin: 1ex 1em 1ex 1em ;
3425     }
3426 }
3427
3428 @media print {
3429     body {
3430         font-family: "Linux Libertine O",
3431             "DejaVu Serif", "Bitstream Vera Serif",
3432             "Liberation Serif", "Nimbus Roman No 9 L",
3433             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3434     }
3435     div.sidetoccontainer { display:none; }
3436     nav.topnavigation { display: none; }
3437     nav.botnavigation { display: none; }
3438     div.bodycontainer { width: 100% }
3439 }
3440
3441 @media handheld {
3442     div.sidetoccontainer { display:none; }
3443     nav.topnavigation { display:block }
```

```
3444     nav.botnavigation { display:block }
3445     div.bodycontainer { width: 100% }
3446 }
3447
3448 @media projection {
3449     div.sidetoccontainer { display:none; }
3450     nav.topnavigation { display:block }
3451     nav.botnavigation { display:block }
3452     div.bodycontainer { width: 100% }
3453 }
3454 \end{filecontents*}
3455 % \end{Verbatim}% for syntax highlighting
3456 \end{LWRwriteconf}
```

## 40.5 lwarp\_sagebrush.css

File lwarp\_sagebrush.css An optional css which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

**Config file:** 3457 \begin{LWRwriteconf}  
3458 \begin{filecontents\*}[overwrite]{lwarp\_sagebrush.css}  
3459 @import url("lwarp.css") ;  
3460  
3461  
3462 A:link {color:#105030 ; text-decoration: none ; }  
3463 A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}  
3464 A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}  
3465 A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}  
3466  
3467  
3468  
3469 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph  
3470 {  
3471 font-family: "URW Classico", Optima, "Linux Biolinum 0",  
3472 "Linux Libertine O", "Liberation Serif",  
3473 "Nimbus Roman No 9 L", "FreeSerif",  
3474 "Hoefler Text", Times, "Times New Roman", serif;  
3475 font-variant: small-caps ;  
3476 font-weight: normal ;  
3477 color: #304070 ;  
3478 text-shadow: 2px 2px 3px #808080;  
3479 }  
3480  
3481 h1 { /\* title of the entire website, used on each page \*/  
3482 font-variant: small-caps ;  
3483 color: #304070 ;  
3484 text-shadow: 2px 2px 3px #808080;  
3485 background-color: #F7F7F0 ;  
3486 background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);  
3487 }  
3488  
3489 h1 {

```
3490 border-bottom: 1px solid #304070;
3491 /* border-top: 2px solid #304070; */
3492 }
3493
3494 h2 {
3495 border-bottom: 1px solid #304070;
3496 /* border-top: 2px solid #304070; */
3497 background-color: #F7F7F0 ;
3498 background-image: linear-gradient(to bottom, #F7F7F0, #DAD0C0);
3499 }
3500
3501
3502
3503 div.abstract {
3504 background: #f5f5eb ;
3505 background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3506
3507 border: 1px solid silver;
3508 border-radius: 1em ;
3509 }
3510
3511 div.abstract dl {line-height:1.5;}
3512 div.abstract dt {color:#304070;}
3513
3514 div.abstracttitle{
3515 font-family: "URW Classico", Optima, "Linux Biolinum O",
3516 "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3517 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3518 font-weight:bold;
3519 font-variant: small-caps ;
3520 font-size:1.5em;
3521 border-bottom: 1px solid silver ;
3522 color: #304070 ;
3523 text-align: center ;
3524 text-shadow: 1px 1px 2px #808080;
3525 }
3526
3527 span.abstractrunintitle{
3528 font-family: "URW Classico", Optima, "Linux Biolinum O",
3529 "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3530 "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3531 font-weight:bold;
3532 }
3533
3534
3535 div.epigraph, div.dictum {
3536 background: #f5f5eb ;
3537 background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3538
3539 border: 1px solid silver ;
3540 border-radius: 1ex ;
3541 box-shadow: 3px 3px 3px #808080 ;
3542 }
3543
3544
```

```
3545 .example {
3546     background-color: #f5f5eb ;
3547     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3548
3549 }
3550
3551 div.exampletitle{
3552     font-family: "URW Classico", Optima, "Linux Biolinum 0",
3553         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3554         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3555     font-weight:bold;
3556     font-variant: small-caps ;
3557     border-bottom: 1px solid silver ;
3558     color: #304070 ;
3559     text-align: center ;
3560     text-shadow: 1px 1px 2px #808080;
3561 }
3562
3563
3564 .sidebar {
3565     background-color: #f5f5eb ;
3566     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3567
3568 }
3569
3570 div.sidebartitle{
3571     font-family: "URW Classico", Optima, "Linux Biolinum 0",
3572         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3573         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3574     font-weight:bold;
3575     font-variant: small-caps ;
3576     border-bottom: 1px solid silver ;
3577     color: #304070 ;
3578     text-align: center ;
3579     text-shadow: 1px 1px 2px #808080;
3580 }
3581
3582
3583 .fancyvrblabel {
3584     font-family: "URW Classico", Optima, "Linux Biolinum 0",
3585         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3586         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3587     font-weight:bold;
3588     font-variant: small-caps ;
3589     font-size: 1.5em ;
3590     color: #304070 ;
3591     text-align: center ;
3592     text-shadow: 1px 1px 2px #808080;
3593 }
3594
3595 div.minipage {
3596     background-color: #eeeeee7 ;
3597     border: 1px solid silver ;
3598     border-radius: 1ex ;
3599 }
```

```
3600
3601 table div.minipage { background: none ; border: none ; }
3602
3603 div.framebox div.minipage {border:none ; background:none}
3604
3605 section.textbody > div.minipage {
3606     box-shadow: 3px 3px 3px #808080 ;
3607 }
3608
3609 div.fboxBlock div.minipage { box-shadow: none ; }
3610
3611 .framed .minipage , .framedleftbar .minipage {
3612     border: none ;
3613     background: none ;
3614     padding: 0ex ;
3615     margin: 0ex ;
3616 }
3617
3618 figure.figure .minipage, div.figurecaption .minipage { border: none; }
3619
3620 div.marginblock div.minipage ,
3621 div.marginparblock div.minipage
3622     { border: none; }
3623
3624 figure , div.marginblock {
3625     background-color: #eeeeee7 ;
3626     border: 1px solid silver ;
3627     border-radius: 1ex ;
3628     box-shadow: 3px 3px 3px #808080 ;
3629 }
3630
3631 figure figure {
3632     border: 1px solid silver ;
3633     margin: 0em ;
3634     box-shadow: none ;
3635 }
3636
3637 /*
3638 div.figurecaption {
3639     border-top: 1px solid silver ;
3640     border-bottom: 1px solid silver ;
3641     background-color: #e8e8e8 ;
3642 }
3643 */
3644
3645
3646 div.table {
3647     box-shadow: 3px 3px 3px #808080 ;
3648 }
3649
3650 /*
3651 .tnotes {
3652     background: #e8e8e8;
3653     border: 1px solid silver;
3654 }
```

```
3655 */
3656
3657
3658 nav.topnavigation{
3659     background-color: #b0b8b0 ;
3660     background-image: linear-gradient(to bottom,#e0e0e0,#b0b8b0) ;
3661 }
3662
3663 nav.botnavigation{
3664     background-color: #b0b8b0 ;
3665     background-image: linear-gradient(to top,#e0e0e0,#b0b8b0) ;
3666 }
3667
3668
3669
3670 header{
3671     background-color: #F7F7F0 ;
3672     background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
3673 }
3674
3675 footer{
3676     background-color: #F7F7F0 ;
3677     background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
3678 }
3679
3680
3681
3682 div.sidetoccontainer {
3683     background-color: #F7F7F0 ;
3684     background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
3685     box-shadow: 3px 3px 3px #808080 ;
3686 }
3687
3688 div.sidetotitle {color: #304070 ; }
3689
3690 nav.sidetoc a:hover {
3691     color:#006000 ;
3692     text-decoration: none ;
3693     text-shadow:0px 0px 2px #a0a0a0;
3694 }
3695
3696
3697 @media screen and (max-width: 45em) {
3698     div.sidetoccontainer { border-radius: 0 ; }
3699 }
3700
3701
3702 \end{filecontents*}
3703 % \end{Verbatim}%
3704 \end{LWRwriteconf}
```

## 40.6 lwarp\_formal.css

File lwarp\_formal.css An optional css which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

**Config file:**

```
3705 \begin{LWRwriteconf}
3706 \begin{filecontents*}[overwrite]{lwarp_formal.css}
3707 @import url("lwarp.css") ;
3708
3709
3710
3711 A:link {color:#802020 ; text-decoration:none; }
3712 A:visited {color:#802020 ; text-shadow:none ;}
3713 A:hover {color:#400000 ; text-shadow:none ;}
3714 A:active {color:#C00000 ; text-shadow:none ;}
3715
3716
3717 body {
3718     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3719         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3720         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3721         "Times New Roman", serif;
3722     background: #fffcf5;
3723 }
3724
3725 span.textrm {
3726     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3727         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3728         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3729         "Times New Roman", serif;
3730 }
3731
3732 span.textsf {
3733     font-family: "DejaVu Sans", "Bitstream Vera Sans",
3734         Geneva, Verdana, sans-serif ;
3735 }
3736
3737
3738
3739 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
3740 {
3741     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3742         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3743         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3744         "Times New Roman", serif;
3745     color: #800000 ;
3746     text-shadow: none ;
3747 }
3748
3749 h1, h2 {
3750     background-color: #fffcf5 ;
3751     background-image: none ;
3752     border-bottom: 1px solid #808080;
3753 /*     border-top: 2px solid #808080; */
3754 }
3755
3756 div.abstracttitle {
3757     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
```

```
3758         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3759         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3760         "Times New Roman", serif;
3761     color: black ;
3762     text-shadow: none ;
3763 }
3764
3765 span.abstractrunintitle {
3766     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3767         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3768         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3769         "Times New Roman", serif;
3770     color: black ;
3771     text-shadow: none ;
3772 }
3773
3774 div.abstract { font-size: 100% }
3775
3776 .sidebar {
3777     background: #fffcf5;
3778     background-image: none ;
3779     margin: 2em 5% 2em 5%;
3780     padding: 0.5em 1em;
3781     border: none ;
3782     border-top : 1px solid silver;
3783     border-bottom : 1px solid silver;
3784     font-size: 90% ;
3785 }
3786
3787 div.sidebartitle{
3788     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3789         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3790         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3791         "Times New Roman", serif;
3792     color: #800000 ;
3793     text-shadow: none ;
3794     border: none ;
3795 }
3796
3797 .example {
3798     background: #fffcf5;
3799     background-image: none ;
3800     margin: 2em 5% 2em 5%;
3801     padding: 0.5em 1em;
3802     border: none ;
3803     border-top : 1px solid silver;
3804     border-bottom : 1px solid silver;
3805 }
3806
3807 div.exampletitle{
3808     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3809         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3810         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3811         "Times New Roman", serif;
3812     color: #800000 ;
```

```
3813     text-shadow: none ;
3814     border: none ;
3815 }
3816
3817 div.fancyvrblabel{
3818     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3819         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3820         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3821         "Times New Roman", serif;
3822     color: #800000 ;
3823     text-shadow: none ;
3824     border: none ;
3825 }
3826
3827
3828
3829 figure {
3830     margin: 5ex 5% 5ex 5% ;
3831     padding: 1ex 1em 1ex 1em ;
3832     background-color: #ffffcf5 ;
3833     overflow-x: auto ;
3834     border: none ;
3835 /*     border-top: 1px solid silver; */
3836 /*     border-bottom: 1px solid silver; */
3837 }
3838
3839
3840 div.figurecaption , .lstlisting {
3841     border: none ;
3842 /*     border-top: 1px solid silver ; */
3843 /*     border-bottom: 1px solid silver ; */
3844     background-color: #ffffcf5 ;
3845 }
3846
3847 .tnotes {
3848     background: #ffffcf5 ;
3849     border-top: 1px solid silver ;
3850     border-bottom: 1px solid silver ;
3851 }
3852
3853 .theorem {
3854     background: none ;
3855 }
3856
3857 .minipage {
3858     background-color: #ffffcf5 ;
3859     border: none ;
3860 }
3861
3862 div.floatrow figure { border: none ; }
3863
3864 figure figure { border: none ; }
3865
3866
3867 nav.toc, nav.lof, nav.lot, nav.lol {
```

```

3868     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3869         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3870         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3871         "Times New Roman", serif;
3872 }
3873
3874 div.sidetoccontainer {
3875     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3876         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3877         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
3878         "Times New Roman", serif;
3879     background-image: linear-gradient(to bottom, #ffffcf5, #C0C0C0);
3880 }
3881
3882 div.sidetoctitle{
3883     color: #800000 ;
3884 }
3885
3886 header{
3887     background-color: #e0e0e0 ;
3888     background-image: linear-gradient(to top, #ffffcf5, #b0b0b0);
3889     text-align:center ;
3890 }
3891
3892 footer{
3893     background-color: #e0e0e0 ;
3894     background-image: linear-gradient(to bottom, #ffffcf5, #b0b0b0);
3895     padding: 2ex 1em 2ex 1em ;
3896     text-align:left ;
3897 }
3898
3899 nav.botnavigation {
3900     background: #dedcd5 ;
3901     border-top: 1px solid black ;
3902 }
3903 \end{filecontents*}
3904 % \end{Verbatim}% for syntax highlighting
3905 \end{LWRwriteconf}

```

## 40.7 sample\_project.css

File sample\_project.css The project-specific css file. Use with \CSSFilename.

If used, this must be present both when compiling the project and also when distributing the HTML files.

**Config file:**

```

3906 \begin{LWRwriteconf}
3907 \begin{filecontents*}[overwrite]{sample_project.css}
3908 /* ( --- Start of project.css --- ) */
3909 /* ( --- A sample project-specific CSS file for lwarp --- ) */
3910
3911 /* Uncomment one of the following: */
3912 @import url("lwarp.css") ;
3913 /* @import url("lwarp_formal.css") ; */

```

```
3914 /* @import url("lwarp_sagebrush.css") ; */
3915
3916 /* Project-specific CSS setting follow here. */
3917 /* . . . */
3918
3919 /* ( --- End of project.css --- ) */
3920 \end{filecontents}
3921 % \end{Verbatim} for syntax highlighting
3922 \end{LWRwriteconf}
```

## 40.8 lwarp.ist

File `lwarp.ist` Used to modify the index for `lwarp`.

This must be present when compiling the project, but does not need to be present when distributing the resulting `HTML` files.

The page compositor line is for `memoir`'s `\specialindex`.

**Config file:**

```
3923 \begin{LWRwriteconf}
3924 \begin{filecontents*}[overwrite]{lwarp.ist}
3925 preamble
3926 "\\begin{theindex}
3927   \\providecommand*\\lettergroupDefault[1]{}%
3928   \\providecommand*\\lettergroup[1]{%
3929     \\par\\textbf{\#1}\\par
3930     \\nopagebreak
3931   }
3932 "
3933 headings_flag 1
3934 heading_prefix "
3935 \\lettergroup{"
3936 heading_suffix "}"
3937 delim_0 ", \\hyperindexref{"
3938 delim_1 ", \\hyperindexref{"
3939 delim_2 ", \\hyperindexref{"
3940 delim_n "}, \\hyperindexref{"
3941 delim_r "} -- \\hyperindexref{"
3942 delim_t "}"
3943 page_compositor "."
3944 \end{filecontents*}
3945 % \end{Verbatim} for syntax highlighting
3946 \end{LWRwriteconf}
```

## 40.9 lwarp.xdy

File `lwarp.xdy` Used to modify the index for `lwarp`.

This must be present when compiling the project, but does not need to be present when distributing the resulting `HTML` files.

See:

[https://tex.stackexchange.com/questions/80300/  
how-can-i-convince-hyperref-and-xindy-to-play-together-nicely](https://tex.stackexchange.com/questions/80300/how-can-i-convince-hyperref-and-xindy-to-play-together-nicely)

**Config file:**

```

3947 \begin{LWRwriteconf}
3948 \begin{filecontents*}[overwrite]{lwarp.xdy}
3949 (require "tex/inputenc/latin.xdy")
3950 (merge-rule "\PS *" "Postscript")
3951 (require "texindy.xdy")
3952 (require "page-ranges.xdy")
3953 (require "book-order.xdy")
3954 (define-location-class "arabic-page-numbers"
3955     ("arabic-numbers") :min-range-length 1)
3956 (require "makeindex.xdy")
3957 (define-attributes ((hyperindexref)))
3958 (markup-locref :open "\hyperindexref{" :close "}")
3959 (markup-locref :open "\hyperindexref{" :close "}" :attr "hyperpage")
3960 (markup-locref :open "\textbf{\hyperindexref{" :close "}}" :attr "textbf")
3961 (markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
3962 (define-location-class-order ("roman-page-numbers"
3963     "arabic-page-numbers"
3964     "alpha-page-numbers"
3965     "Roman-page-numbers"
3966     "Alpha-page-numbers"
3967     "see"
3968     "seealso"))
3969 \end{filecontents*}
3970 % \end{Verbatim} for syntax highlighting
3971 \end{LWRwriteconf}
```

## 40.10 lwarp\_one\_limage.cmd

File lwarp\_one\_limage.cmd Used by lwarp to help make lateximages when using WINDOWS.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The arguments are each of the three fields from <project>-images.txt, and also the base name of the source file.

*MiKTeX* does not allow file lwarp\_one\_limage.cmd to be created directly by *lwarpmk*, so lwarp\_one\_limage.txt is created instead, then copied to lwarp\_one\_limage.cmd by *lwarpmk*. This occurs each time *lwarpmk* used to create lateximages.

**Config file:**

```

3972 \begin{LWRwriteconf}
3973 \immediate\openout\LWR@quickfile=lwarp_one_limage.txt
3974 \immediate\write\LWR@quickfile{%
3975     pdfseparate -f \LWRpercent 1 -l \LWRpercent 1 \LWRpercent 4_html.pdf %
3976     \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent\LWRpercent d.pdf%
3977 }
3978 \immediate\write\LWR@quickfile{%
3979     pdfcrop --hires \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf %
3980     \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
3981 }
```

---

```

3982 \immediate\write\LWR@quickfile{%
3983   pdftocairo -svg -noshrink \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf %
3984   \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.svg%
3985 }
3986 \immediate\write\LWR@quickfile{%
3987   del \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
3988 }
3989 \immediate\write\LWR@quickfile{%
3990   del \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf%
3991 }
3992 \immediate\write\LWR@quickfile{exit}
3993 \immediate\closeout\LWR@quickfile
3994 \end{LWRwriteconf}

```

## 40.11 lwarp\_mathjax.txt

**File** `lwarp_mathjax.txt` The default MathJax script used by `lwarp` when using `MATHJAX`. A recent version of MathJax is used, as served by the recommended repository. Adjustments are made to allow `LATEX` to control the equation tags.

`\MathJaxFilename` determines which script file is copied into the `HTML` pages, and defaults to `lwarp_mathjax.txt`. The script files must be present when compiling the project, but do not need to be present when distributing the resulting `HTML` files.

**custom script** To generate a custom script, such as to use a local repository, copy `lwarp_mathjax.txt` to a new file, make changes while keeping `lwarp`'s adjustments for equation numbering, and use `\MathJaxFilename` to select new filename.

**Config file:**

```

3995 \begin{LWRwriteconf}
3996 \begin{filecontents*}[overwrite]{lwarp_mathjax.txt}
3997 <!-- https://groups.google.com/forum/#!topic/
3998   mathjax-users/jUtewUcE2bY -->
3999 <script type="text/x-mathjax-config">
4000 MathJax.Hub.Register.StartupHook("TeX AMSmath Ready",function () {
4001   var seteqsectionDefault = {name: "", num: 0};
4002   var seteqsections = {}, seteqsection = seteqsectionDefault;
4003   var TEX = MathJax.InputJax.Tex, PARSE = TEX.Parse;
4004   var AMS = MathJax.Extension["TeX/AMSmash"];
4005   TEX.Definitions.Add({
4006     macros: {
4007       seteqsection: "mySection",
4008       seteqnumber: "mySetEqNumber"
4009     }
4010   });
4011
4012   PARSE.Augment({
4013     mySection: function (name) {
4014       seteqsection.num = AMS.number;
4015       var n = this.GetArgument(name);
4016       if (n === "") {
4017         seteqsection = seteqsectionDefault;
4018       } else {
4019         if (!seteqsections["_"+n])

```

```
4020             seteqsections["_"+n] = {name:n, num:0};
4021             seteqsection = seteqsections["_"+n];
4022         }
4023         AMS.number = seteqsection.num;
4024     },
4025     mySetEqNumber: function (name) {
4026         var n = this.GetArgument(name);
4027         if (!n || !n.match(/^[0-9]+ */))
4028             n = "";
4029         else
4030             n = parseInt(n)-1;
4031         <!-- $ syntax highlighting -->
4032         if (n === "" || n < 1)
4033             TEX.Error
4034             ("Argument to "+name+" should be a positive integer");
4035         AMS.number = n;
4036     }
4037 });
4038 MathJax.Hub.Config({
4039     TeX: {
4040         equationNumbers: {
4041             formatTag: function (n) {
4042                 <!-- if not numeric, don't include the chapter -->
4043                 if (!n.match(/^[0-9]+ */))
4044                     <!-- $ syntax highlighting -->
4045                     return "(+"+n.replace(/\./,"")+")" ;
4046                 else
4047                     return "("+(seteqsection.name+"."+n).replace(/\./,"")+")" ;
4048             },
4049             formatID: function (n) {
4050                 n = (seteqsection.name+'.'+n).replace
4051                     (/[:'<>&]/g,"").replace(/\./,"");
4052                     return 'mjx-eqn-' + n;
4053             }
4054         }
4055     }
4056 });
4057 });
4058</script>
4059
4060<!-- http://docs.mathjax.org/en/latest/options/ThirdParty.html -->
4061<script type="text/x-mathjax-config">
4062     MathJax.Ajax.config.path["Contrib"] =
4063         "https://cdn.mathjax.org/mathjax/contrib";
4064</script>
4065
4066<script type="text/x-mathjax-config">
4067 MathJax.Hub.Config({
4068     TeX: {
4069         extensions: ["autoload-all.js"] ,
4070         equationNumbers: {
4071             autoNumber: "AMS"
4072         }
4073     }
4074 });
4075
```

```

4075 </script>
4076
4077 <!-- Alternative CDN provider: -->
4078 <script type="text/javascript" async
4079 src="https://cdnjs.cloudflare.com/ajax/libs/mathjax/2.7.6/MathJax.js?config=TeX-AMS_HTML-full">
4080 </script>
4081
4082 <!-- No longer supported after April 30, 2017: -->
4083 <!--
4084 <script
4085 src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-AMS_HTML-full">
4086 </script>
4087 -->
4088
4089 \end{filecontents*}
4090 % \end{Verbatim}% for syntax highlighting
4091 \end{LWRwriteconf}

```

## 40.12 lwarpmk.lua — lwarpmk option

Opt	<code>lwarpmk</code>	Creates a local copy of <i>lwarpmk</i> .
Prog	<code>lwarpmk</code>	Command-line utility to process lwarf files and images.
parallel processing		lateximages and svg math images are generated using multiple processes in parallel. For UNIX and LINUX, every 32 images the wait command is issued to wait for the previous batch of images to finish processing before starting a new batch. For WINDOWS, every 32 images one task is dispatched with

START /B /WAIT /BELOWNORMAL

which causes the operating system to wait until this lesser-priority tasks finishes, hopefully also waiting for the normal priority tasks which were already in progress to also complete. Afterwards, the next batch of images is started.

The following is only generated if the `lwarpmk` option was given to `lwarf`.

```

4092 \begin{LWR@createlwarpmk}

4093 \begin{filecontents*}[overwrite]{lwarpmk.lua}
4094 #!/usr/bin/env texlua
4095
4096 -- Copyright 2016–2020 Brian Dunn
4097
4098
4099 printversion = "v0.80"
4100 requiredconfversion = "2" -- also at *lwarpmk.conf
4101
4102 function printhelp ()
4103 print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help.") ;
4104 end
4105
4106

```

```
4107 function printusage ()
4108 --
4109 -- Print the usage of the lwarpmk command:
4110 --
4111 print ( [[
4112
4113 lwarpmk print [-p project]: Compile the print version if necessary.
4114 lwarpmk print1 [-p project]: Forced single compile of the print version.
4115 lwarpmk printindex [-p project]: Process print indexes.
4116 lwarpmk printglossary [-p project]: Process the glossary for the print version.
4117 lwarpmk html [-p project]: Compile the HTML version if necessary.
4118 lwarpmk html1 [-p project]: Forced single compile of the HTML version.
4119 lwarpmk htmlindex [-p project]: Process HTML indexes.
4120 lwarpmk htmlglossary [-p project]: Process the glossary for the html version.
4121 lwarpmk again [-p project]: Touch the source code to trigger recompiles.
4122 lwarpmk limages [-p project]: Process the "lateximages" created by lwarp.sty.
4123 lwarpmk pdftohtml [-p project]:
4124     For use with latexmk or a Makefile:
4125     Converts project_html.pdf to project_html.html and individual HTML files.
4126     Finishes the HTML conversion even if there was a compile error.
4127 lwarpmk pdftosvg <list of file names>: Converts each PDF file to SVG.
4128 lwarpmk epstopdf <list of file names>: Converts each EPS file to PDF.
4129 lwarpmk clean [-p project]: Remove *.aux, *.toc, *.lof/t,
4130     *.idx, *.ind, *.log, *_html_inc.*., .gl*,
4131     *_html.pdf, *_html.html, *_html.sideloc
4132 lwarpmk cleanall [-p project]: Remove auxiliary files, project.pdf, *.html
4133 lwarpmk cleanlimages: Removes all images from the "lateximages" directory.
4134 lwarpmk -h: Print this help message.
4135 lwarpmk --help: Print this help message.
4136
4137 ]] )
4138 -- printconf ()
4139 end
4140
4141
4142 function splitfilename ( pathandfilename )
4143 --
4144 -- Separates out the path and extension from a filename.
4145 -- Returns path, filename with extension, and extension.
4146 -- Ex: thispath, thisfilename, thisextension = splitfilename ("path/to/filename.ext")
4147 --
4148 -- https://www.fhug.org.uk/wiki/wiki/doku.php?id=plugins:code_snippets:
4149 --     split_filename_in_to_path_filename_and_extension
4150 --
4151     if lfs.attributes(pathandfilename,"mode") == "directory" then
4152         local strPath = pathandfilename:gsub("[\\/]$","",) -- $ (syntax highlighting)
4153         return strPath.."\\","",""
4154     end
4155     pathandfilename = pathandfilename..
4156     return pathandfilename:match("^(.-)([^\\/]%-).([^\\\/.]%-)%?$")
4157 end
4158
4159
4160 function splitfile (destfile,sourcefile)
4161 --
```

```
4162 -- Split one large sourcefile into a number of files,
4163 -- starting with destfile.
4164 -- The file is split at each occurance of <!--|Start file|newfilename|*
4165 --
4166 print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
4167 local sfile = io.open(sourcefile)
4168 io.output(destfile)
4169 for line in sfile:lines() do
4170 i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*)|")
4171 if ( (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then
4172     -- split the file
4173     io.output(newfilename) ;
4174 else
4175     -- not a splitpoint
4176     io.write (line .. "\n") ;
4177 end
4178 end -- do
4179 io.close(sfile)
4180 end -- function
4181
4182
4183 function cvalueerror ( line, linenum , cvalue )
4184 --
4185 -- Incorrect value, so print an error and exit.
4186 --
4187     print ("lwarpmk: ===")
4188     print ("lwarpmk: " .. linenum .. " : " .. line ) ;
4189     print (
4190         "lwarpmk: incorrect variable value \".. cvalue ..
4191         \" in lwarpmk.conf.\n"
4192     ) ;
4193     print ("lwarpmk: ===")
4194 --     printconf () ;
4195     os.exit(1) ;
4196 end
4197
4198
4199 function printhowtorecompile ()
4200 -- Tells the user how to recompile to regenerate the configuration files.
4201     print ("lwarpmk: The configuration files lwarpmk.conf and "..sourcename.."lwarpmkconf" )
4202     print ("lwarpmk: must be updated. To do so, recompile" )
4203     print ("lwarpmk: " , sourcename.."tex" )
4204     if ( printlatexcmd == "" ) then
4205         print ("lwarpmk: using xe/lua/pdflatex," )
4206     else
4207         print ("lwarpmk: using the command:")
4208         print ("lwarpmk: " , printlatexcmd )
4209     end
4210     print ("lwarpmk: then use lwarpmk again.")
4211 end -- printhowtorecompile
4212
4213
4214 function ignoreconf ()
4215 -- Global argument index
4216 argindex = 2
```

```
4217 end
4218
4219 function loadconf ()
4220 --
4221 -- Load settings from the project's "lwarpmk.conf" file:
4222 --
4223 -- Default configuration filename:
4224 local conffile = "lwarpmk.conf"
4225 local confroot = "lwarpmk"
4226 -- Global argument index
4227 argindex = 2
4228 -- Optional configuration filename:
4229 if ( arg[argindex] == "-p" ) then
4230     argindex = argindex + 1
4231     confroot = arg[argindex]
4232     conffile = confroot.."lwarpmkconf"
4233     argindex = argindex + 1
4234 end
4235 -- Additional defaults:
4236 confversion = "0"
4237 opsystem = "Unix"
4238 imagesdirectory = "lateximages"
4239 imagesname = "image-"
4240 latexmk = "false"
4241 printlatexcmd = ""
4242 HTMLlatexcmd = ""
4243 printindexcmd = ""
4244 HTMLindexcmd = ""
4245 latexmkindexcmd = ""
4246 -- to be removed:
4247 -- indexprog = "makeindex"
4248 -- makeindexstyle = "lwarp.ist"
4249 -- xindylanguage = "english"
4250 -- xindycodepage = "utf8"
4251 -- xindystyle = "lwarp.xdy"
4252 -- pdftotextenc = "UTF-8"
4253 glossarycmd = "makeglossaries"
4254 -- Verify the file exists:
4255 if (lfs.attributes(conffile,"mode")==nil) then
4256     -- file not exists
4257     print ("lwarpmk: ===")
4258     print ("lwarpmk: File \\" .. conffile .. "\\" does not exist.")
4259     print ("lwarpmk: Move to the project's source directory,")
4260     print ("lwarpmk: recompile using pdflatex, xelatex, or lualatex,")
4261     print ("lwarpmk: then try using lwarpmk again.")
4262     if ( arg[argindex] ~= nil ) then
4263         print (
4264             "lwarpmk: (\\" .. confroot ..
4265             "\\" does not appear to be a project name.)"
4266         )
4267     end
4268     print ("lwarpmk: ===")
4269     printhelp () ;
4270     os.exit(1) -- exit the entire lwarpmk script
4271 else -- file exists
```

```
4272 -- Read the file:
4273 print ("lwarpmk: Reading " .. conffile .. ".")
4274 local cfile = io.open(conffile)
4275 -- Scan each line, parsing each line as: name = [[string]]
4276 local linenum = 0
4277 for line in cfile:lines() do -- scan lines
4278   linenum = linenum + 1
4279   i,j,cvarname,cvalue = string.find (line,"([%w-_]*)%s*=%s*%[%([%^%]*)&%]%)");
4280 -- Error if incorrect enclosing characters:
4281 if ( i == nil ) then
4282   print ("lwarpmk: ===")
4283   print ("lwarpmk: " .. linenum .. " : " .. line );
4284   print ("lwarpmk: Incorrect entry in " .. conffile .. ".\n");
4285   print ("lwarpmk: ===")
4286   -- printconf ();
4287   os.exit(1);
4288 end -- nil
4289 if ( cvarname == "confversion" ) then
4290   confversion = cvalue
4291 elseif ( cvarname == "opsystem" ) then
4292   -- Verify choice of opsystem:
4293   if ( (cvalue == "Unix") or (cvalue == "Windows") ) then
4294     opsystem = cvalue
4295   else
4296     cvalueerror ( line, linenum , cvalue )
4297   end
4298 elseif ( cvarname == "sourcename" ) then sourcename = cvalue
4299 elseif ( cvarname == "homehtmlfilename" ) then homehtmlfilename = cvalue
4300 elseif ( cvarname == "htmlfilename" ) then htmlfilename = cvalue
4301 elseif ( cvarname == "imagesdirectory" ) then imagesdirectory = cvalue
4302 elseif ( cvarname == "imagesname" ) then imagesname = cvalue
4303 elseif ( cvarname == "latexmk" ) then latexmk = cvalue
4304 elseif ( cvarname == "printlatexcmd" ) then printlatexcmd = cvalue
4305 elseif ( cvarname == "HTMLlatexcmd" ) then HTMLlatexcmd = cvalue
4306 elseif ( cvarname == "printindexcmd" ) then printindexcmd = cvalue
4307 elseif ( cvarname == "HTMLindexcmd" ) then HTMLindexcmd = cvalue
4308 elseif ( cvarname == "latexmkindexcmd" ) then latexmkindexcmd = cvalue
4309 elseif ( cvarname == "glossarycmd" ) then glossarycmd = cvalue
4310 elseif ( cvarname == "pdftotextenc" ) then pdftotextenc = cvalue
4311 else
4312   print ("lwarpmk: ===")
4313   print ("lwarpmk: " .. linenum .. " : " .. line );
4314   print (
4315     "lwarpmk: Incorrect variable name \" .. cvarname .. \" in \" ..
4316     conffile .. ".\n"
4317   );
4318   print ("lwarpmk: ===")
4319 --   printconf ();
4320 os.exit(1);
4321 end -- cvarname
4322 end -- do scan lines
4323 io.close(cfile)
4324 end -- file exists
4325 -- Error if sourcename is "lwarp".
4326 -- This could happen if a local copy of lwarp has recently been recompiled.
```

```
4327 if sourcename=="lwarp" then
4328     print ("lwarpmk: ===")
4329     print ("lwarpmk: lwarp.sty has recently been recompiled in this directory,")
4330     print ("lwarpmk: and \"lwarpmk.conf\" is no longer set for your own project.")
4331     print ("lwarpmk: Recompile your own project using pdf/lua/xelatex <projectname>.")
4332     print ("lwarpmk: After a recompile, \"lwarpmk.conf\" will be set for your project,")
4333     print ("lwarpmk: and you may again use lwarpmk.")
4334     print ("lwarpmk: ===")
4335     os.exit(1)
4336 end -- sourcename of "lwarp"
4337 -- Select some operating-system commands:
4338 if opsystem=="Unix" then -- For Unix / Linux / Mac OS:
4339     rmname = "rm"
4340     mvname = "mv"
4341     cpname = "cp"
4342     touchnamepre = "touch"
4343     touchnamepost = ""
4344     newtouchname = "touch"
4345     dirslash = "/"
4346     opquote= "\'"
4347     cmdgroupopenname = " ( "
4348     cmdgroupclosename = " ) "
4349     seqname = " && "
4350     bgname = " &"
4351 elseif opsystem=="Windows" then -- For Windows
4352     rmname = "DEL"
4353     mvname = "MOVE"
4354     cpname = "COPY"
4355     touchnamepre = "COPY /b"
4356     touchnamepost = "+,,"
4357     newtouchname = "echo empty >"
4358     dirslash = "\\"
4359     opquote= "\""
4360     cmdgroupopenname = ""
4361     cmdgroupclosename = ""
4362     seqname = " & "
4363     bgname = ""
4364 else
4365     print ("lwarpmk: ===")
4366     print ("lwarpmk: Select Unix or Windows for opsystem. ")
4367     print ("lwarpmk: ===")
4368     os.exit(1)
4369 end --- for Windows
4370 -- Warning if the operating system does not appear to be correct,
4371 -- in case files were transferred to another system.
4372 if ( (package.config:sub(1,1)) ~= dirslash ) then
4373     print ("lwarpmk: ===")
4374     print ("lwarpmk: It appears that lwarpmk.conf is for a different operating system. ")
4375     printhowtorecompile ()
4376     print ("lwarpmk: ===")
4377     os.exit(1)
4378 end
4379 -- Error if the configuration file's version is not current:
4380 if ( confversion ~= requiredconfversion ) then
4381     print ("lwarpmk: ===")
```

```
4382     printhowtorecompile ()
4383     print ("lwarpmk: ===")
4384     os.exit(1)
4385 end
4386 end -- loadconf
4387
4388
4389 function executecheckerror ( executecommands , errormessage )
4390 --
4391 -- Execute an operating system call,
4392 -- and maybe exit with an error message.
4393 --
4394 local err
4395 err = os.execute ( executecommands )
4396 if ( err ~= 0 ) then
4397     print ("lwarpmk: ===")
4398     print ("lwarpmk: " .. errormessage )
4399     print ("lwarpmk: ===")
4400     os.exit(1)
4401 end
4402 end -- executecheckerror
4403
4404
4405 function refreshdate ()
4406 os.execute(touchnamepre .. " " .. sourcename .. ".tex" .. touchnamepost)
4407 end
4408
4409
4410
4411 function reruntoget (filesource)
4412 --
4413 -- Scan the LaTeX log file for the phrase "Rerun to get",
4414 -- indicating that the file should be compiled again.
4415 -- Return true if found.
4416 --
4417 local fsource = io.open(filesource)
4418 for line in fsource:lines() do
4419 if ( string.find(line,"Rerun to get") ~= nil ) then
4420     io.close(fsource)
4421     return true
4422 end -- if
4423 end -- do
4424 io.close(fsource)
4425 return false
4426 end
4427
4428
4429
4430 function onetime (latexcmd, fsuffix)
4431 --
4432 -- Compile one time, return true if should compile again.
4433 -- fsuffix is "" for print, "_html" for HTML output.
4434 --
4435 print("lwarpmk: Compiling with: " .. latexcmd)
4436 executecheckerror (
```

```
4437     latexcmd ,
4438     "Compile error."
4439 )
4440 return (reruntoget(sourcename .. fsuffix .. ".log") ) ;
4441 end
4442
4443
4444 function manytimes (latexcmd, fsuffix)
4445 --
4446 -- Compile up to five times.
4447 -- fsuffix is "" for print, "_html" for HTML output
4448 --
4449 if onetime(latexcmd, fsuffix) == true then
4450 if onetime(latexcmd, fsuffix) == true then
4451 if onetime(latexcmd, fsuffix) == true then
4452 if onetime(latexcmd, fsuffix) == true then
4453 if onetime(latexcmd, fsuffix) == true then
4454 end end end end
4455 end
4456
4457
4458 function verifyfileexists (filename)
4459 --
4460 -- Exit if the given file does not exist.
4461 --
4462 if (lfs.attributes ( filename , "modification" ) == nil ) then
4463   print ("lwarpmk: ===")
4464   print ("lwarpmk: " .. filename .. " not found." ) ;
4465   print ("lwarpmk: ===")
4466   os.exit (1) ;
4467 end
4468 end
4469
4470
4471
4472 function pdftohtml ()
4473 --
4474 -- Convert <project>_html.pdf into HTML files:
4475 --
4476 -- Convert to text:
4477 print ("lwarpmk: Converting " .. sourcename
4478   .. "_html.pdf to " .. sourcename .. "_html.html")
4479 os.execute("pdftotext -enc " .. pdftotextenc .. " -nopgbrk -layout "
4480   .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
4481 -- Split the result into individual HTML files:
4482 splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
4483 end
4484
4485
4486 function removeauxs ()
4487 --
4488 -- Remove auxiliary files:
4489 -- All .aux files are removed since there may be many bbl*.aux files.
4490 -- Also removes sourcename_html.pdf, sourcename_html.html,
4491 -- and sourcename_html.sidetoc.
```

```
4492 --
4493 os.execute ( rmname .. " *.aux " ..
4494     sourcename .. ".toc" .. sourcename .. "_html.toc" ..
4495     sourcename .. ".lof" .. sourcename .. "_html.lof" ..
4496     sourcename .. ".lot" .. sourcename .. "_html.lot" ..
4497     " *.idx" ..
4498     " *.ind" ..
4499     sourcename .. ".ps" .. sourcename .. "_html.ps" ..
4500     sourcename .. ".log" .. sourcename .. "_html.log" ..
4501     sourcename .. ".gl*" .. sourcename .. "_html.gl*" ..
4502     sourcename .. "_html.pdf" ..
4503     sourcename .. "_html.html" ..
4504     sourcename .. "_html.sidetoc" ..
4505     " *_html_inc.*"
4506   )
4507 end
4508
4509 function checkhtmlpdfexists ()
4510 --
4511 -- Error if the HTML document does not exist.
4512 -- The lateximages are drawn from the HTML PDF version of the document,
4513 -- so "lwarpmk html" must be done before "lwarpmk limages".
4514 --
4515 local htmlpdffile = io.open(sourcename .. "_html.pdf", "r")
4516 if ( htmlpdffile == nil ) then
4517   print ("")
4518   print ("lwarpmk: ===")
4519   print ("lwarpmk: The HTML version of the document does not exist.")
4520   print ("lwarpmk: Enter \"lwarpmk html\" to compile the HTML version.")
4521   print ("lwarpmk: ===")
4522   os.exit(1)
4523 end
4524 io.close (htmlpdffile)
4525 end -- checkhtmlpdfexists
4526
4527
4528 function warnlimages ()
4529 --
4530 -- Warning of a missing <sourcename>-images.txt file:
4531   print ("lwarpmk: ===")
4532   print ("lwarpmk: \" .. sourcename .. "-images.txt\" does not exist.")
4533   print ("lwarpmk: Your project does not use SVG math or other lateximages,")
4534   print ("lwarpmk: or the file has been deleted somehow.")
4535   print ("lwarpmk: Use \"lwarpmk html1\" to recompile your project")
4536   print ("lwarpmk: and recreate \" .. sourcename .. "-images.txt\"")
4537   print ("lwarpmk: If your project does not use SVG math or other lateximages,")
4538   print ("lwarpmk: then \" .. sourcename .. "-images.txt\" will never exist, and")
4539   print ("lwarpmk: \"lwarpmk limages\" will not be necessary.")
4540   print ("lwarpmk: ===")
4541 end -- warnlimages
4542
4543
4544 function warnlimagesrecompile ()
4545 -- Warning if must recompile before creating limages:
4546   print ("")
```

```
4547     print ("lwarpmk: ===")
4548     print ("lwarpmk: Cross-references are not yet correct.")
4549     print ("lwarpmk: The document must be recompiled before creating the lateximages.")
4550     print ("lwarpmk: Enter \"lwarpmk html1\" again, then try \"lwarpmk limages\" again.")
4551     print ("lwarpmk: ===")
4552 end --warnlimagesrecompile
4553
4554
4555 function checklimages ()
4556 --
4557 -- Check <sourcename>.txt to see if need to recompile first.
4558 -- If any entry has a page number of zero, then there were incorrect images.
4559 --
4560 print ("lwarpmk: Checking for a valid " .. sourcename .. "-images.txt file.")
4561 local limagesfile = io.open(sourcename .. "-images.txt", "r")
4562 if ( limagesfile == nil ) then
4563     warnlimages ()
4564     os.exit(1)
4565 end
4566 -- Track warning to recompile if find a page 0
4567 local pagezerowarning = false
4568 -- Scan <sourcename>.txt
4569 for line in limagesfile:lines() do
4570     -- lwimgpage is the page number in the PDF which has the image
4571     -- lwimghash is true if this filename is a hash
4572     -- lwimgname is the lateximage filename root to assign for the image
4573     i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
4574     -- For each entry:
4575     if ( (i~=nil) ) then
4576         -- If the page number is 0, image references are incorrect
4577         -- and must recompile the source document:
4578         if ( lwimgpage == "0" ) then
4579             pagezerowarning = true
4580         end
4581     end -- if i~=nil
4582 end -- do
4583 -- The last line should be |end|end|end|.
4584 -- If not, the compile must have aborted, and the images are incomplete.
4585 if ( lwimgpage ~= "end" ) then
4586     warnlimagesrecompile()
4587     os.exit(1) ;
4588 end
4589 if ( pagezerowarning ) then
4590     warnlimagesrecompile()
4591     os.exit(1) ;
4592 end -- pagezerowarning
4593 end -- checklimages
4594
4595
4596 function createuniximage ( lwimgfullname )
4597 --
4598 -- Create one lateximage for Unix / Linux / Mac OS.
4599 --
4600 executecheckerror (
4601     cmdgroupopenname ..
```

```
4602     "pdfseparate -f " .. lwimgpage .. " -l " .. lwimgpage .. " " ..
4603         sourcename .. "_html.pdf" ..
4604         imagesdirectory .. dirslash .. "lateximagetemp-%d" .. ".pdf" ..
4605         seqname ..
4606     -- Crop the image:
4607     "pdffcrop --hires " .. imagesdirectory .. dirslash .. "lateximagetemp-" ..
4608         lwimgpage .. ".pdf" ..
4609         imagesdirectory .. dirslash .. lwimgname .. ".pdf" ..
4610         seqname ..
4611     -- Convert the image to svg:
4612     "pdftocairo -svg -noshrink " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf" ..
4613         imagesdirectory .. dirslash .. lwimgname .. ".svg" ..
4614         seqname ..
4615     -- Remove the temporary files:
4616     rmname .. " " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf" .. seqname ..
4617     rmname .. " " .. imagesdirectory .. dirslash .. "lateximagetemp-" .. lwimgpage .. ".pdf" ..
4618     cmdgroupclose .. " >/dev/null " .. bgnname
4619     ,
4620     "File error trying to convert " .. lwimgfullname
4621 )
4622 -- Every 32 images, wait for completion at below normal priority,
4623 -- allowing other image tasks to catch up.
4624 numimageprocesses = numimageprocesses + 1
4625 if ( numimageprocesses > 32 ) then
4626     numimageprocesses = 0
4627     print ( "lwarpmk: waiting" )
4628     executecheckerror ( "wait" , "File error trying to wait." )
4629 end
4630 end -- createuniximage
4631
4632
4633 function createwindowsimage ( lwimgfullname )
4634 --
4635 -- Create one lateximage for Windows.
4636 --
4637 -- Every 32 images, wait for completion at below normal priority,
4638 -- allowing other image tasks to catch up.
4639 numimageprocesses = numimageprocesses + 1
4640 if ( numimageprocesses > 32 ) then
4641     numimageprocesses = 0
4642     thiswaitcommand = "/WAIT /BELOWNORMAL"
4643     print ( "lwarpmk: waiting" )
4644 else
4645     thiswaitcommand = ""
4646 end
4647 -- Execute the image generation command
4648 executecheckerror (
4649     "start /B " .. thiswaitcommand .. " \"\" lwarp_one_limage " ..
4650     lwimgpage .. " " ..
4651     lwimghash .. " " ..
4652     lwimgname .. " " ..
4653     sourcename .. " <nul >nul"
4654     ,
4655     "File error trying to create image."
4656 )
```

```
4657 end -- createwindowsimage
4658
4659
4660 function createonelateximage ( line )
4661 --
4662 -- Given the next line of <sourcename>.txt, convert a single image.
4663 --
4664 -- lwimgpage is the page number in the PDF which has the image
4665 -- lwimghash is true if this filename is a hash
4666 -- lwimgname is the lateximage filename root to assign for the image
4667 i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
4668 -- For each entry:
4669 if ( (i~nil) ) then
4670     -- Skip if the page number is 0:
4671     if ( lwimgpage == "0" ) then
4672         pagezerowarning = true
4673     -- Skip if the page number is "end":
4674     else if ( lwimgpage == "end" ) then
4675     else
4676         -- Skip if this image is hashed and already exists:
4677         local lwimgfullname = imagesdirectory .. dirslash .. lwimgname .. ".svg"
4678         if (
4679             (lwimghash ~= "true") or
4680             (lfs.attributes(lwimgfullname,"mode")==nil) -- file not exists
4681         )
4682         then -- not hashed or not exists:
4683             -- Print the name of the file being generated:
4684             print ( "lwarpmk: " .. lwimgname )
4685             -- Touch/create the dest so that only once instance tries to build it:
4686             executecheckerror (
4687                 newtouchname .. " " .. lwimgfullname ,
4688                 "File error trying to touch " .. lwimgfullname
4689             )
4690             -- Separate out the image into its own single-page pdf:
4691             if opsystem=="Unix" then
4692                 createuniximage (lwimgfullname)
4693             elseif opsystem=="Windows" then
4694                 createwindowsimage (lwimgfullname)
4695             end
4696             end -- not hashed or not exists
4697         end -- not page "end"
4698         end -- not page 0
4699     end -- not nil
4700 end -- createonelateximage
4701
4702
4703 function createlateximages ()
4704 --
4705 -- Create lateximages based on <sourcename>-images.txt:
4706 --
4707 -- See if the document must be recompiled first:
4708 checklimages ()
4709 -- See if the HTML version exists:
4710 checkhtlpdfexists ()
4711 -- Attempt to create the lateximages:
```

```
4712 print ("lwarpmk: Creating lateximages.")
4713 local limagesfile = io.open(sourcename .. "-images.txt", "r")
4714 if ( limagesfile == nil ) then
4715     warnlimages ()
4716     os.exit(1)
4717 end
4718 -- Create the lateximages directory, ignore error if already exists
4719 err = os.execute("mkdir " .. imagesdirectory)
4720 -- For Windows, create lwarp_one_limage.cmd from lwarp_one_limage.txt:
4721 if opsystem=="Windows" then
4722     executecheckerror (
4723         cpname .. " lwarp_one_limage.txt lwarp_one_limage.cmd" ,
4724         "File error trying to copy lwarp_one_limage.txt to lwarp_one_limage.cmd"
4725     )
4726 end -- create lwarp_one_limage.cmd
4727 -- Track the number of parallel processes
4728 numimageprocesses = 0
4729 -- Track warning to recompile if find a page 0
4730 pagezerowarning = false
4731 -- Scan <sourcename>.txt
4732 for line in limagesfile:lines() do
4733     createonelateximage ( line )
4734 end -- do
4735 io.close(limagesfile)
4736 print ( "lwarpmk limages: ===" )
4737 print ( "lwarpmk limages: Wait a moment for the images to complete" )
4738 print ( "lwarpmk limages: before reloading the page." )
4739 print ( "lwarpmk limages: ===" )
4740 print ( "lwarpmk limages: Done." )
4741 if ( pagezerowarning == true ) then
4742     print ( "lwarpmk limages: WARNING: Images will be incorrect." )
4743     print ( "lwarpmk limages: Enter \"lwarpmk cleanimages\", then" )
4744     print ( "lwarpmk limages: recompile the document one more time, then" )
4745     print ( "lwarpmk limages: repeat \"lwarpmk images\" again." )
4746 end -- pagezerowarning
4747 end -- function
4748
4749
4750 function convertepstopdf ()
4751 --
4752 -- Converts EPS files to PDF files.
4753 -- The filenames are arg[argindex] and up.
4754 -- arg[1] is the command "epstopdf".
4755 --
4756 ignoreconf ()
4757 for i = argindex , #arg do
4758     if (lfs.attributes(arg[i],"mode")==nil) then
4759         print ("lwarpmk: File \" .. arg[i] .. \" does not exist.")
4760     else
4761         print ("lwarpmk: Converting \" .. arg[i] .. \"")
4762         thispath, thisfilename, thisextension = splitfilename(arg[i])
4763         if ( thispath == nil ) then
4764             os.execute ( "epstopdf " .. arg[i] )
4765         else
4766             os.execute (
```

```
4767           "epstopdf" ..
4768           thispath .. thisfilename .. "." .. thisextension .. " " ..
4769           thispath .. thisfilename .. ".pdf"
4770       )
4771   end
4772 end -- if
4773 end -- do
4774 end --function
4775
4776
4777 function convertpdftosvg ()
4778 --
4779 -- Converts PDF files to SVG files.
4780 -- The filenames are arg[argindex] and up.
4781 -- arg[1] is the command "pdftosvg".
4782 --
4783 ignoreconf ()
4784 for i = argindex , #arg do
4785     if (lfs.attributes(arg[i],"mode")==nil) then
4786         print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
4787     else
4788         print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
4789         thispath, thisfilename, thisextension = splitfilename(arg[i])
4790         if ( thispath == nil ) then
4791             os.execute ( "pdftocairo -svg" .. arg[i] )
4792         else
4793             os.execute (
4794                 "pdftocairo -svg" ..
4795                 thispath .. thisfilename .. "." .. thisextension .. " " ..
4796                 thispath .. thisfilename .. ".svg"
4797             )
4798         end
4799     end -- if
4800 end -- do
4801 end --function
4802
4803
4804 -- Force an update and conclude processing:
4805 function updateanddone ()
4806 print ("lwarpmk: Forcing an update of " .. sourcename .. ".tex.")
4807 refreshdate ()
4808 print ("lwarpmk: " .. sourcename .. ".tex is ready to be recompiled.")
4809 print ("lwarpmk: Done.")
4810 end -- function
4811
4812
4813 -- Start of the main code: --
4814
4815
4816 -- lwarpmk --version :
4817
4818 if (arg[1] == "--version") then
4819 print ( "lwarpmk: " .. printversion )
4820
4821 else -- not --version
```

```
4822
4823
4824 -- print intro:
4825
4826 print ("lwarpmk: .. printversion .. " Automated make for the LaTeX Lwarp package.")
4827
4828
4829 -- lwarpmk print:
4830
4831 if arg[1] == "print" then
4832 loadconf ()
4833 if ( latexmk == "true" ) then
4834     print ("lwarpmk: Compiling with: .. printlatexcmd")
4835     executecheckerror (
4836         printlatexcmd ,
4837         "Compile error."
4838     )
4839     print ("lwarpmk: Done.")
4840 else -- not latexmk
4841     verifyfileexists (sourcename .. ".tex") ;
4842     -- See if up to date:
4843     if (
4844         ( lfs.attributes ( sourcename .. ".pdf" , "modification" ) == nil ) or
4845         (
4846             lfs.attributes ( sourcename .. ".tex" , "modification" ) >
4847             lfs.attributes ( sourcename .. ".pdf" , "modification" )
4848         )
4849     ) then
4850         -- Recompile if not yet up to date:
4851         manytimes(printlatexcmd, "")
4852         print ("lwarpmk: Done.");
4853     else
4854         print ("lwarpmk: .. sourcename .. ".pdf is up to date.");
4855     end
4856 end -- not latexmk
4857
4858
4859 -- lwarpmk print1:
4860
4861 elseif arg[1] == "print1" then
4862     loadconf ()
4863     verifyfileexists (sourcename .. ".tex") ;
4864     onetime(printlatexcmd, "")
4865     print ("lwarpmk: Done.");
4866
4867
4868 -- lwarpmk printindex:
4869 -- Compile the index then touch the source
4870 -- to trigger a recompile of the document:
4871
4872 elseif arg[1] == "printindex" then
4873 loadconf ()
4874 os.execute ( printindexcmd )
4875 print ("lwarpmk: -----")
4876 updateanddone ()
```

```
4877
4878
4879 -- lwarpmk printglossary:
4880 -- Compile the glossary then touch the source
4881 -- to trigger a recompile of the document:
4882
4883 elseif arg[1] == "printglossary" then
4884 loadconf ()
4885 print ("lwarpmk: Processing the glossary.")
4886
4887 os.execute(glossarycmd .. " " .. sourcename)
4888 updateanddone ()
4889
4890
4891 -- lwarpmk html:
4892
4893 elseif arg[1] == "html" then
4894 loadconf ()
4895 if ( latexmk == "true" ) then
4896     print ("lwarpmk: Compiling with: " .. HTMLLatexcmd)
4897     executecheckerror (
4898         HTMLLatexcmd ,
4899         "Compile error."
4900     )
4901     pdftohtml ()
4902     print ("lwarpmk: Done.")
4903 else -- not latexmk
4904     verifyfileexists ( sourcename .. ".tex" ) ;
4905     -- See if exists and is up to date:
4906     if (
4907         ( lfs.attributes ( homehtmlfilename .. ".html" , "modification" ) == nil ) or
4908         (
4909             lfs.attributes ( sourcename .. ".tex" , "modification" ) >
4910             lfs.attributes ( homehtmlfilename .. ".html" , "modification" )
4911         )
4912     ) then
4913         -- Recompile if not yet up to date:
4914         manytimes(HTMLLatexcmd, "_html")
4915         pdftohtml ()
4916         print ("lwarpmk: Done.")
4917     else
4918         print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
4919     end
4920 end -- not latexmk
4921
4922
4923 -- lwarpmk html1:
4924
4925 elseif arg[1] == "html1" then
4926     loadconf ()
4927     verifyfileexists ( sourcename .. ".tex" ) ;
4928     onetime(HTMLLatexcmd, "_html")
4929     pdftohtml ()
4930     print ("lwarpmk: Done.")
4931
```

```
4932
4933 -- lwarpmk pdftohtml:
4934 elseif arg[1] == "pdftohtml" then
4935     loadconf ()
4936     pdftohtml ()
4937
4938
4939 -- lwarpmk htmlindex:
4940 -- Compile the index then touch the source
4941 -- to trigger a recompile of the document:
4942
4943 elseif arg[1] == "htmlindex" then
4944 loadconf ()
4945 os.execute ( HTMLIndexcmd )
4946 print ("lwarpmk: -----")
4947 updateanddone ()
4948
4949
4950 -- lwarpmk htmlglossary:
4951 -- Compile the glossary then touch the source
4952 -- to trigger a recompile of the document.
4953 -- The <sourcename>.xdy file is created by the glossaries package.
4954
4955 elseif arg[1] == "htmlglossary" then
4956 loadconf ()
4957 print ("lwarpmk: Processing the glossary.")
4958 os.execute(glossarycmd .. " " .. sourcename .. "_html")
4959 updateanddone ()
4960
4961
4962 -- lwarpmk limages:
4963 -- Scan the <sourcename>.txt file to create lateximages.
4964
4965 elseif arg[1] == "limages" then
4966 loadconf ()
4967 print ("lwarpmk: Processing images.")
4968 createlateximages ()
4969 print ("lwarpmk: Done.")
4970
4971
4972 -- lwarpmk again:
4973 -- Touch the source to trigger a recompile.
4974
4975 elseif arg[1] == "again" then
4976 loadconf ()
4977 updateanddone ()
4978
4979
4980 -- lwarpmk clean:
4981 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*., .gl*
4982
4983 elseif arg[1] == "clean" then
4984 loadconf ()
4985 removeaux ()
4986 print ("lwarpmk: Done.")
```

```
4987
4988
4989 -- lwarpmk cleanall
4990 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.* , .gl*
4991 --     and also project.pdf, project.dvi, *.html
4992
4993 elseif arg[1] == "cleanall" then
4994 loadconf ()
4995 removeaux ()
4996 os.execute ( rmname .. " " ..
4997     sourcename .. ".pdf" .. sourcename .. "_html.pdf" ..
4998     sourcename .. ".dvi" .. sourcename .. "_html.dvi" ..
4999     "*.html"
5000 )
5001 print ("lwarpmk: Done.")
5002
5003
5004 -- lwarpmk cleanimages
5005 -- Remove images from the imagesdirectory.
5006
5007 elseif arg[1] == "cleanimages" then
5008 loadconf ()
5009 os.execute ( rmname .. " " .. imagesdirectory .. dirslash .. "*" )
5010 print ("lwarpmk: Done.")
5011
5012 -- lwarpmk epstopdf <list of file names>
5013 -- Convert EPS files to PDF using epstopdf
5014 elseif arg[1] == "epstopdf" then
5015 convertepstopdf ()
5016 print ("lwarpmk: Done.")
5017
5018
5019 -- lwarpmk pdftosvg <list of file names>
5020 -- Convert PDF files to SVG using pdftocairo
5021 elseif arg[1] == "pdftosvg" then
5022 convertpdftosvg ()
5023 print ("lwarpmk: Done.")
5024
5025
5026 -- lwarpmk with no argument :
5027
5028 elseif (arg[1] == nil) then
5029 printhelp ()
5030
5031
5032 -- lwarpmk -h or lwarpmk --help :
5033
5034 elseif (arg[1] == "-h" ) or (arg[1] == "--help") then
5035 printusage ()
5036
5037
5038 -- Unknown command:
5039
5040 else
5041 printhelp ()
```

---

```

5042 print ("\nlwarpmk: ***** Unknown command \"..arg[1]..\". *****\n")
5043 end
5044
5045 end -- not --version
5046 \end{filecontents*}
5047 % \end{Verbatim}% for syntax highlighting

5048 \end{LWR@createlwarpmk}

```

## 41 Stacks

**for HTML output:** 5049 \begin{warpHTML}

⚠️ Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (un-nested) in proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new \section would close any currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an enumerate, for example. Depths to be recorded in \LWR@closedepthone, etc.

### 41.1 Assigning depths

initial depths for empty stack entries:

```
5050 \newcommand*\{\LWR@depthnone\}{-5}
```

All sectioning depths are deeper than \LWR@depthfinished:

```

5051 \newcommand*\{\LWR@depthfinished\}{-4}
5052 \newcommand*\{\LWR@depthbook\}{-2}
5053 \newcommand*\{\LWR@depthpart\}{-1}
5054 \newcommand*\{\LWR@depthchapter\}{0}
5055 \newcommand*\{\LWR@depthsection\}{1}
5056 \newcommand*\{\LWR@depthsubsection\}{2}
5057 \newcommand*\{\LWR@depthsubsubsection\}{3}
5058 \newcommand*\{\LWR@depthparagraph\}{4}
5059 \newcommand*\{\LWR@depthsubparagraph\}{5}

```

Used by \itemize, \enumerate, \description:

```
5060 \newcommand*\{\LWR@depthlist\}{6}
```

Used by \item:

---

```
5061 \newcommand*{\LWR@depthlistitem}{7}
5062 \let\LWR@depthdescitem\LWR@depthlistitem
```

## 41.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to `\pushclose` and `\popclose` as well.

```
5063 \newcommand*{\LWR@closeone}{}% top of the stack
5064 \newcommand*{\LWR@closetwo}{}%
5065 \newcommand*{\LWR@closethree}{}%
5066 \newcommand*{\LWR@closefour}{}%
5067 \newcommand*{\LWR@closefive}{}%
5068 \newcommand*{\LWR@closesix}{}%
5069 \newcommand*{\LWR@closeseven}{}%
5070 \newcommand*{\LWR@closeeight}{}%
5071 \newcommand*{\LWR@closenine}{}%
5072 \newcommand*{\LWR@closeten}{}%
5073 \newcommand*{\LWR@closeeleven}{}%
5074 \newcommand*{\LWR@closetwelve}{}%
```

## 41.3 Closing depths

A stack to record the depth of each level:

 Note that nested L<sup>A</sup>T<sub>E</sub>X structures may push depths which are non-sequential.

*Ex:*

---

```
\begin{itemize}
  \item{A}
    \begin{description}
      \item{B}
    \end{description}
  \end{itemize}
```

---

```
5075 \newcommand*{\LWR@closedepthonne}{}% top of the stack
5076 \newcommand*{\LWR@closedepthtwo}{}{\LWR@depthnone}
5077 \newcommand*{\LWR@closedepththree}{}{\LWR@depthnone}
5078 \newcommand*{\LWR@closedepthfour}{}{\LWR@depthnone}
5079 \newcommand*{\LWR@closedepthfive}{}{\LWR@depthnone}
5080 \newcommand*{\LWR@closedepthsix}{}{\LWR@depthnone}
5081 \newcommand*{\LWR@closedepthseven}{}{\LWR@depthnone}
5082 \newcommand*{\LWR@closedeptheight}{}{\LWR@depthnone}
5083 \newcommand*{\LWR@closedepthonne}{}{\LWR@depthnone}
5084 \newcommand*{\LWR@closedepthten}{}{\LWR@depthnone}
5085 \newcommand*{\LWR@closedeptheleven}{}{\LWR@depthnone}
5086 \newcommand*{\LWR@closedepthtwelve}{}{\LWR@depthnone}
```

## 41.4 Pushing and popping the stack

\LWR@pushclose {*<sectiontype>*}

Pushes one return action and its L<sup>A</sup>T<sub>E</sub>X depth onto the stacks.

```

5087 \NewDocumentCommand{\LWR@pushclose}{m}
5088 {%
5089 \global\let\LWR@closetwelve\LWR@closeeleven%
5090 \global\let\LWR@closeeleven\LWR@closeten%
5091 \global\let\LWR@closeten\LWR@closenine%
5092 \global\let\LWR@closenine\LWR@closeeight%
5093 \global\let\LWR@closeeight\LWR@closeseven%
5094 \global\let\LWR@closeseven\LWR@closesix%
5095 \global\let\LWR@closesix\LWR@closefive%
5096 \global\let\LWR@closefive\LWR@closefour%
5097 \global\let\LWR@closefour\LWR@closethree%
5098 \global\let\LWR@closethree\LWR@closetwo%
5099 \global\let\LWR@closetwo\LWR@closeone%
5100 \global\csletcs{\LWR@closeone}{\LWR@printclose#1}%
5101 \global\let\LWR@closedepthtwelve\LWR@closedeptheleven%
5102 \global\let\LWR@closedeptheleven\LWR@closedepthten%
5103 \global\let\LWR@closedepthten\LWR@closedepthnine%
5104 \global\let\LWR@closedepthnine\LWR@closedeptheight%
5105 \global\let\LWR@closedeptheight\LWR@closedepthseven%
5106 \global\let\LWR@closedepthseven\LWR@closedepthsix%
5107 \global\let\LWR@closedepthsix\LWR@closedepthfive%
5108 \global\let\LWR@closedepthfive\LWR@closedepthfour%
5109 \global\let\LWR@closedepthfour\LWR@closedepththree%
5110 \global\let\LWR@closedepththree\LWR@closedepthtwo%
5111 \global\let\LWR@closedepthtwo\LWR@closedepthonne%
5112 \global\csletcs{\LWR@closedepthonne}{\LWR@depth#1}%
5113 }
```

\LWR@popclose Pops one action and its depth off the stacks.

```

5114 \newcommand*{\LWR@popclose}{%
5115 {%
5116 \global\let\LWR@closeone\LWR@closetwo%
5117 \global\let\LWR@closetwo\LWR@closethree%
5118 \global\let\LWR@closethree\LWR@closefour%
5119 \global\let\LWR@closefour\LWR@closefive%
5120 \global\let\LWR@closefive\LWR@closesix%
5121 \global\let\LWR@closesix\LWR@closeseven%
5122 \global\let\LWR@closeseven\LWR@closeeight%
5123 \global\let\LWR@closeeight\LWR@closenine%
5124 \global\let\LWR@closenine\LWR@closeten%
5125 \global\let\LWR@closeten\LWR@closeeleven%
5126 \global\let\LWR@closeeleven\LWR@closetwelve%
5127 \global\let\LWR@closetwelve\LWR@closedepthtwo%
5128 \global\let\LWR@closedepthtwo\LWR@closedepththree%
5129 \global\let\LWR@closedepththree\LWR@closedepthfour%
5130 \global\let\LWR@closedepthfour\LWR@closedepthfive%
5131 \global\let\LWR@closedepthfive\LWR@closedepthsix%
```

```

5132 \global\let\LWR@closedepthsix\LWR@closedepthseven%
5133 \global\let\LWR@closedepthseven\LWR@closedeptheight%
5134 \global\let\LWR@closedeptheight\LWR@closedepthnine%
5135 \global\let\LWR@closedepthnine\LWR@closedepthten%
5136 \global\let\LWR@closedepthten\LWR@closedeptheleven%
5137 \global\let\LWR@closedeptheleven\LWR@closedepthtwelve%
5138 }

5139 \end{warpHTML}

```

## 42 Data arrays

These macros are similar to the `arrayjobx` package, except that `\LWR@setexparray`'s argument is expanded only once when assigned.

`name` has no backslash, `index` can be a number or a text name, and an empty value must be `\relax` instead of empty.

To assign an empty value:

```
\LWR@setexparray{name}{index}{}{}
```

**for HTML output:** 5140 `\begin{warpHTML}`

```

\lWR@setexparray {<name>} {<index>} {<contents>}

5141 \NewDocumentCommand{\LWR@setexparray}{m m m}{%
5142   \let\LWR@temp@par\par%
5143   \let\par\relax%
5144   \edef\LWR@thisexparrayname{\#1\#2}%
5145   \ifstrempty{\#3}%
5146     {\csdef{\LWR@thisexparrayname}{}%}
5147     {\csedef{\LWR@thisexparrayname}{\#3}}%
5148   \let\par\LWR@temp@par%
5149 }

\lWR@getexparray {<name>} {<index>}

5150 \newcommand*{\LWR@getexparray}[2]{%
5151   \nameuse{\#1\#2}%
5152 }

5153 \end{warpHTML}

```

## 43 Localizing catcodes

**for HTML & PRINT:** 5154 `\begin{warpall}`

⚠ **Misplaced alignment tab character &**

Place `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error

Misplaced alignment tab character &.

`\StartDefiningTabulars` Place before defining something with & in it.

```
5155 \newcommand{\StartDefiningTabulars}{%
5156   \LWR@traceinfo{StartDefiningTabulars}%
5157   \warpHTMLonly{\catcode`\&=\active}%
5158 }
```

`\StopDefiningTabulars` Place after defining something with & in it.

```
5159 \newcommand{\StopDefiningTabulars}{%
5160   \LWR@traceinfo{StopDefiningTabulars}%
5161   \warpHTMLonly{\catcode`\&=4}%
5162 }
```

`Bool LWR@mathmacro` True if currently defining math macros. Used to disable SVG math hashing and MathJax math contents while defining a macro using inline math. Begin a macro, it is not guaranteed that the contents are static, and so the image must be unique. The contents also almost certainly will not be parsed correctly by MathJax.

```
5163 \newbool{LWR@mathmacro}
5164 \boolfalse{LWR@mathmacro}
```

`\StartDefiningMath` Place before defining something with \$ in it.

```
5165 \newcommand{\StartDefiningMath}{%
5166   \LWR@traceinfo{StartDefiningMath}%
5167   \warpHTMLonly{\catcode`\$=\active}%
5168 }
```

`\StopDefiningMath` Place after defining something with \$ in it.

```
5169 \newcommand{\StopDefiningMath}{%
5170   \LWR@traceinfo{StopDefiningMath}%
5171   \warpHTMLonly{\catcode`\$=3}% math shift
5172 }

5173 \end{warpall}
```

## 44 Localizing dynamic math

Inline SVG math usually uses a hash of its contents to generate `lateximages` which are reusable for multiple instances with the same contents. If the contents may change for

each use, such as depending on the current value of a counter, then `\inlinemathother` must be used before the inline math expression, and `\inlinemathnormal` must be used after.

For MathJax, the inline math expression is usually printed for MathJax to interpret. When marked as dynamic math, the following inline math expression will be displayed as an unhashed inline SVG image instead.

For existing code and packages, it may be possible to patch macros after they have been defined, using the `xpatch` package, which is pre-loaded by `lwarp`:

---

```
\xpatchcmd{\macro}
  {$math expression$}
  {\inlinemathother$math expression$\inlinemathnormal}
  {}
  {\typeout{Error patching macroname.}}
```

---

**for HTML & PRINT:** 5174 `\begin{warpall}`

`Bool LWR@dynamicmath` True to mark inline math which is dynamic in nature, thus should not be hashed for reuse.  
**Default:** `false`

```
5175 \newbool{LWR@dynamicmath}
5176 \boolfalse{LWR@dynamicmath}
```

`\inlinemathother` Place before using `$ ... $` or `\( ... \)` if the contents of the math are not static, depending on counters or dynamic macros.

```
5177 \newcommand{\inlinemathother}{%
5178 \LWR@traceinfo{inlinemathother}%
5179 \booltrue{LWR@dynamicmath}%
5180 }
```

`\inlinemathnormal` Place after using `$ ... $` or `\( ... \)` with dynamic contents.

```
5181 \newcommand{\inlinemathnormal}{%
5182 \LWR@traceinfo{inlinemathnormal}%
5183 \boolfalse{LWR@dynamicmath}%
5184 }
```

```
5185 \end{warpall}
```

## 45 HTML entities

**for HTML output:** 5186 `\begin{warpHTML}`

HTML Unicode entities:

```
5187 \let\LWR@origampersand\&
```

```
\HTMLentity {<entitytag>}

5188 \newcommand*{\HTMLentity}[1]{%
5189 % \LWR@traceinfo{HTMLentity} \detokenize{#1}}%
5190 \begingroup%
5191 \LWR@FBcancel%
5192 \LWR@origampersand#1;%
5193 \endgroup%
5194 % \LWR@traceinfo{HTMLentity done}}%
5195 }

\HTMLunicode {<hex_unicode>}

5196 \newcommand*{\HTMLunicode}[1]{\HTMLentity{\LWR@origpound{}x#1}{}}

\&

5197 \renewrobustcmd*{\&}{\HTMLentity{amp}{}}

\textless

5198 \let\LWR@origtextless\textless
5199 \renewrobustcmd*{\textless}{\HTMLentity{lt}{}}

\textgreater

5200 \let\LWR@origtextgreater\textgreater
5201 \renewrobustcmd*{\textgreater}{\HTMLentity{gt}{}}

5202 \end{warpHTML}
```

## 46 HTML filename generation

The filename of the homepage is set to `\HomeHTMLFilename.html`. The filenames of additional sections start with `\HTMLFilename`, to which is appended a section number or a simplified section name, depending on `FileSectionNames`.

<b>for HTML &amp; PRINT:</b>	5203 \begin{warpall}
<code>\BaseJobname</code>	The <code>\jobname</code> of the printed version, even if currently compiling the <code>HTML</code> version. I.e. this is the <code>\jobname</code> without <code>_html</code> appended. This is used to set <code>\HomeHTMLFilename</code> if the user did not provide one.
	5204 \providecommand*{\BaseJobname}{\jobname}
<code>\HTMLFilename</code>	The prefix for all generated <code>HTML</code> files other than the home page, defaulting to empty. See section 7.6.1.
	5205 \providecommand*{\HTMLFilename}[]

\HomeHTMLFilename The filename of the home page, defaulting to the \BaseJobname. See section [7.6.1](#).

```
5206 \providecommand*{\HomeHTMLFilename}{\BaseJobname}
```

\SetHTMLFileName {*number*}

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
5207 \newcommand*{\SetHTMLFileName}[1]{%
5208 \setcounter{LWR@htmlfilename}{#1}%
5209 }
```

Bool FileSectionNames Selects how to create HTML file names.

Defaults to use section names in the filenames.

```
5210 \newbool{FileSectionNames}
5211 \booltrue{FileSectionNames}

5212 \end{warpall}
```

**for HTML output:** 5213 \begin{warpHTML}

Ctr LWR@htmlfilename Records the number of each HTML file as it is being created. Number 0 is the home page.

```
5214 \newcounter{LWR@htmlfilename}
5215 \setcounter{LWR@htmlfilename}{0}
```

\LWR@htmlsectionfilename {*htmlfilename or name*}

Prints the filename for a given section: \HTMLFilename{}filename/name.html

```
5216 \newcommand*{\LWR@htmlsectionfilename}[1]{%
5217 \LWR@traceinfo{\LWR@htmlsectionfilename A !\detokenize{#1}!}%
```

Section 0 or empty is given the home filename. The filename must be detokenized for underscores.

```
5218 % \LWR@traceinfo{about to assign temp}%
5219 \LWR@sanitize{#1}%
5220 \LWR@traceinfo{about to compare with ??}%
5221 \ifthenelse{\equal{\LWR@sanitized}{??}}{%
5222   {\LWR@traceinfo{found ??}}%
5223   {\LWR@traceinfo{not found ??}}%
5224 \LWR@traceinfo{about to compare with zero or empty}%
5225 \ifthenelse{%
5226   \equal{\LWR@sanitized}{0}%
5227   \OR \equal{\LWR@sanitized}{}}%
```

```

5228      \OR \equal{\LWR@sanitized}{??}%
5229 }%
5230 {%
5231     \LWR@traceinfo{\LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
5232     \HomeHTMLFilename.html%
5233 }%

```

For a L<sup>A</sup>T<sub>E</sub>X section named “Index” or “index” without a prefix, create a filename with a leading underscore to avoid colliding with the HTML filename `index.html`:

```

5234 {%
5235     \LWR@traceinfo{\LWR@htmlsectionfilename C \LWR@sanitized}%
5236     \ifthenelse{%
5237         \equal{\HTMLFilename}{} \AND
5238         \equal{\LWR@sanitized}{Index} \OR
5239         \equal{\LWR@sanitized}{index}%
5240     }%
5241     {%
5242         \LWR@traceinfo{Prefixing the index name with an underscore.}%
5243         \_\LWR@sanitized.html%
5244     }%

```

Otherwise, create a filename with the chosen prefix:

```

5245     {%
5246         \HTMLFilename\LWR@isolate{\LWR@sanitized}.html%
5247     }%
5248 }%
5249 \LWR@traceinfo{\LWR@htmlsectionfilename Z}%
5250 }

```

`\LWR@htmlrefsectionfilename {<label>}`

Prints the filename for the given label

```

5251 \newcommand*{\LWR@htmlrefsectionfilename}[1]{%
5252 \LWR@traceinfo{\LWR@htmlrefsectionfilename: !\detokenize{#1}!}%

```

`\LWR@nullfonts` to allow math in a section name.

```

5253 \begingroup%
5254 \LWR@nullfonts%
5255 \LWR@htmlsectionfilename{\LWR@htmlfileref{#1}}%
5256 \endgroup%
5257 \LWR@traceinfo{\LWR@htmlrefsectionfilename: done}%
5258 }

5259 \end{warpHTML}

```

## 47 Homepage link

for HTML & PRINT: `5260 \begin{warpall}`

\linkhomename Holds the default name for the home link.

```
5261 \newcommand{\linkhomename}{Home}
```

```
5262 \end{warpall}
```

**for HTML output:** 5263 \begin{warpHTML}

\LinkHome May be used wherever you wish to place a link back to the homepage. The filename must be detokenized for underscores.

```
5264 \newcommand*\LinkHome{%
5265 \LWR@subhyperrefclass{\HomeHTMLfilename.html}{\linkhomename}{linkhome}%
5266 }
```

```
5267 \end{warpHTML}
```

**for PRINT output:** 5268 \begin{warpprint}

\LinkHome May be used wherever you wish to place a link back to the homepage. For print output, if `hyperref` is available a hyperlink to the first page is used, named by `\linkhomename`. If `hyperref` is not available, a pageref is used instead.

\BaseJobname is included in the link label in case multiple documents are cross-referenced.

```
5269 \AtBeginDocument{
5270 \@ifundefined{hyperref}{
5271     \newcommand*\LinkHome{%
5272         \linkhomename\ --- page \pageref{\BaseJobname-page-LWRfirstpage}%
5273     }
5274 }{
5275     \newcommand*\LinkHome{%
5276         \hyperref[\BaseJobname-page-LWRfirstpage]{\linkhomename}%
5277     }
5278 }
5279 }
5280
5281 \AfterEndPreamble{\label{\BaseJobname-page-LWRfirstpage}}
```

```
5282 \end{warpprint}
```

**for HTML output:** 5283 \begin{warpHTML}

\LWR@topnavigation Creates a link to the homepage at the top of the page for use when the window is too narrow for the sidetoc.

```
5284 \newcommand*\LWR@topnavigation{%
5285 \LWR@htmlelementclassline{nav}{topnavigation}{\LinkHome}%
5286 }
```

---

\LWR@botnavigation Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sideroc.

```
5287 \newcommand*\{\LWR@botnavigation\}{  
5288 \LWR@htmlelementclassline{nav}{botnavigation}{\LinkHome}  
5289 }  
  
5290 \end{warpHTML}
```

## 48 \LWRPrintStack diagnostic tool

 Diagnostics tool: Prints the LATEX nesting depth values for the stack levels. \LWR@startpars is used before printing the stack, so that \LWRPrintStack may be called from anywhere in the normal text flow.

**for HTML output:** 5291 \begin{warpHTML}

\LWRPrintStack Prints the closedepth stack.

```
5292 \newcommand*\{\LWR@subprintstack\}{  
5293 \LWR@closedepthonen\ \LWR@closedepthtwo\ \LWR@closedepththree\  
5294 \LWR@closedepthfour\ \LWR@closedepthfive\ \LWR@closedepthsix\  
5295 \LWR@closedepthseven\ \LWR@closedeptheight\ \LWR@closedeptnine\  
5296 \LWR@closedepthten\ \LWR@closedeptheleven\ \LWR@closedepthtwelve\  
5297 }  
5298  
5299 \newcommand*\{\LWRPrintStack\}{  
5300 \LWR@startpars  
5301 \LWR@subprintstack  
5302 }  
  
5303 \end{warpHTML}
```

**for PRINT output:** 5304 \begin{warpprint}

```
5305 \newcommand*\{\LWRPrintStack\}{}  
  
5306 \end{warpprint}
```

## 49 Closing stack levels

**for HTML output:** 5307 \begin{warpHTML}

Close one nested level:

```
5308 \newcommand*\{\LWR@closeoneprevious\}{%  
5309
```

---

```

5310 \LWR@closeone
5311
5312 \LWR@popclose
5313 }

```

\LWR@closeprevious {*<sectintype>*} Close everything up to the given depth:

```

5314 \newcommand*{\LWR@closeprevious}[1]{
5315 \LWR@traceinfo{%
5316     LWR@closeprevious to depth \csuse{LWR@depth#1}, %
5317     depths are \LWR@subprintstack%
5318 }%

```

Close any pending paragraph:

```
5319 \LWR@stopars%
```

Close anything nested deeper than the desired depth. First close anything deeper, then at most one of the same level.

```

5320 \whileboolexpr{test{\ifnumcomp{\LWR@closedepthone}{>}{\csuse{LWR@depth#1}}}}{%
5321 }%
5322     \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
5323     \LWR@closeoneprevious%
5324 }%
5325 \ifboolexpr{test{\ifnumcomp{\LWR@closedepthone}{=}{\csuse{LWR@depth#1}}}}{%
5326 }%
5327     \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
5328     \LWR@closeoneprevious%
5329 }{%
5330 \LWR@traceinfo{LWR@closeprevious: done, depths are \LWR@subprintstack}%
5331 }%
5332 \end{warpHTML}

```

## 50 PDF pages and styles

**for HTML output:** 5333 \begin{warpHTML}

\LWR@forcenewpage New PDF page a before major environment.

This is used just before major environments, such as *verse*. Reduces the chance of an environment overflowing the HTML PDF output page.

```

5334 \newcommand{\LWR@forcenewpage}{%
5335 \LWR@traceinfo{LWR@forcenewpage}%
5336 \ifinner\else%
5337 \LWR@stopars\LWR@orignewpage\LWR@startpars%
5338 \fi%
5339 }

```

\pagestyle, etc. are nullified for HTML output.

```
\pagestyle {\langle style \rangle}  
5340 \renewcommand*{\pagestyle}[1]{}
```

```
\thispagestyle {\langle style \rangle}  
5341 \renewcommand*{\thispagestyle}[1]{}
```

```
\markboth {\langle left \rangle} {\langle right \rangle}  
5342 \renewcommand*{\markboth}[2]{}  
  
\markright {\langle right \rangle}  
5343 \renewcommand*{\markright}[1]{}
```

```
\raggedbottom  
5344 \renewcommand*{\raggedbottom}{}
```

```
\flushbottom  
5345 \renewcommand*{\flushbottom}{}
```

```
\sloppy  
5346 \renewcommand*{\sloppy}{}
```

```
\fussy  
5347 \renewcommand*{\fussy}{}
```

```
\pagenumbering * {\langle commands \rangle}  
5348 \RenewDocumentCommand{\pagenumbering}{s m}{  
5349 \end{warpHTML}}
```

## 51 HTML tags, spans, divs, elements

**for HTML output:** 5350 \begin{warpHTML}

## 51.1 Mapping L<sup>A</sup>T<sub>E</sub>X sections to HTML sections

```

5351 \newcommand*\{\LWR@tagtitle\}{h1}
5352 \newcommand*\{\LWR@tagtitleend\}{/h1}
5353 \newcommand*\{\LWR@tagbook\}{div class="book"}
5354 \newcommand*\{\LWR@tagbookend\}{/div}
5355 \newcommand*\{\LWR@tagpart\}{h2}
5356 \newcommand*\{\LWR@tagpartend\}{/h2}
5357 \newcommand*\{\LWR@tagchapter\}{h3}
5358 \newcommand*\{\LWR@tagchapterend\}{/h3}
5359 \newcommand*\{\LWR@tagsection\}{h4}
5360 \newcommand*\{\LWR@tagsectionend\}{/h4}
5361 \newcommand*\{\LWR@tagsubsection\}{h5}
5362 \newcommand*\{\LWR@tagsubsectionend\}{/h5}
5363 \newcommand*\{\LWR@tagsubsubsection\}{h6}
5364 \newcommand*\{\LWR@tagsubsubsectionend\}{/h6}
5365 \newcommand*\{\LWR@tagparagraph\}{span class="paragraph"}
5366 \newcommand*\{\LWR@tagparagraphend\}{/span}
5367 \newcommand*\{\LWR@tagsubparagraph\}{span class="subparagraph"}
5368 \newcommand*\{\LWR@tagsubparagraphend\}{/span}
5369
5370 \newcommand*\{\LWR@tagregularparagraph\}{p}

```

## 51.2 Babel-French tag modifications

Adjust *babel-french* for HTML spaces. So far, this only works for *pdflatex* and *xelatex*.

(Emulates or patches code by DANIEL FLIPO.)

```

5371 \providecommand*\{\LWR@FBcancel\}{}%
5372
5373 \AtBeginDocument{%

```

In some circumstances, \NoAutoSpacing may be defined when \frenchbsetup is not.

```

5374 \@ifundefined{NoAutoSpacing}%
5375     {}%
5376     {%
5377         \LetLtxMacro{\LWR@FBcancel}{\NoAutoSpacing}%
5378     }%
5379
5380 \@ifundefined{frenchbsetup}%
5381 {}%
5382 {%
5383     \frenchbsetup{FrenchFootnotes=false}%
5384 %
5385     \renewrobustcmd*\{\FBcolonspace\}{%
5386         \begingroup%
5387         \LWR@FBcancel%
5388         \LWR@origampersand{}nbsp;%
5389     \endgroup%

```

```

5390      }%
5391      \renewrobustcmd*{\FBthinspace}{%
5392          \begingroup%
5393          \LWR@FBcancel%
5394          \LWR@origampersand\LWR@origpound{}x202f;% ,
5395          \endgroup%
5396      }%
5397      \renewrobustcmd*{\FBguillspace}{%
5398          \begingroup%
5399          \LWR@FBcancel%
5400          \LWR@origampersand{}nbsp;% ~, for \og xyz \fg{}%
5401          \endgroup%
5402      }%
5403      \DeclareDocumentCommand{\FBmedkern}{}{%
5404          \begingroup%
5405          \LWR@FBcancel%
5406          \LWR@origampersand\LWR@origpound{}x202f;% ,
5407          \endgroup%
5408      }%
5409      \DeclareDocumentCommand{\FBthickkern}{}{%
5410          \begingroup%
5411          \LWR@FBcancel%
5412          \LWR@origampersand{}nbsp;% ~
5413          \endgroup%
5414      }%
5415      \renewrobustcmd*{\~}{\HTMLentity{nbsp}}% was overwritten by babel-french
5416      \iffBunicode%
5417      \else%
5418          \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
5419          \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
5420      \fi%
5421 }%
5422 }

```

### 51.3 HTML output formatting

Helps format the output HTML code for human readability.

\LWR@indentHTML Newline and indent the output HTML code.

```

5423 \newcommand*{\LWR@indentHTML}{%
5424     \LWR@orignewline\LWR@origrule{2em}{0pt}%
5425 }

```

\LWR@indentHTMLtwo Newline and indent the output HTML code.

```

5426 \newcommand*{\LWR@indentHTMLtwo}{%
5427     \LWR@orignewline\LWR@origrule{4em}{0pt}%
5428 }

```

## 51.4 HTML tags

\LWR@htmltagc {*tag*} Break ligatures and use upright apostrophes in HTML tags.

\protect is in case the tag appears in TOC, LOF, LOT.

```

5429 \newcommand*{\LWR@htmltagc}[1]{%
5430 \LWR@traceinfo{\LWR@htmltagc !\detokenize{#1}!}%
5431 \begingroup%
5432 \LWR@FBcancel%
5433 \ifmmode\else\protect\LWR@origttfamily\fi%
5434 \protect\LWR@origtextless%
5435 \LWR@isolate{#1}%
5436 \protect\LWR@origtextgreater%
5437 \endgroup%
5438 }
```

Env \LWR@nestspan Disable minipage, \parbox, and HTML <div>s inside a <span>.

- ⚠ \begin{\LWR@nestspan} must follow the opening <span> tag to allow a paragraph to start if the span is at the beginning of a new paragraph.
- ⚠ \end{\LWR@nestspan} must follow the </span> or a <p> may appear inside the span.

```

5439 \newcommand*{\LWR@nestspanitem}{%
5440 \if@newlist\else{\LWR@htmltagc{br /}}\fi%
5441 \LWR@origitem%
5442 }
5443
5444 \newenvironment*{\LWR@nestspan}
5445 {%
5446 \LWR@traceinfo{\LWR@nestspan starting}%
5447 \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}%
5448 {%
5449   \LWR@traceinfo{\LWR@nestspan: inside a lateximage}%
5450 }%
5451 {%
5452   \LWR@traceinfo{\LWR@nestspan: NOT inside a lateximage}%
5453   \addtocounter{\LWR@spandepth}{1}%
5454   \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{%
5455     {\LWR@subhtmlelementclass{span}{inlineminipage}}%
5456     {\LWR@htmltagc{/span}}}%
5457   \RenewDocumentEnvironment{BlockClass}{o m}{%
5458     \renewcommand{\BlockClassSingle}[2]{##2}%
5459     \renewcommand{\LWR@forcenewpage}{}}%
5460   \renewcommand{\LWR@liststart}{%
5461     \let\item\LWR@nestspanitem%
5462   }%
5463   \renewcommand{\LWR@listend}{\LWR@htmltagc{br /}\LWR@htmltagc{br /}}%
5464   \renewenvironment{quote}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
5465   \renewenvironment{quotation}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
5466 }%
5467 \LWR@traceinfo{\LWR@nestspan starting: done}%
5468 }% starting env
```

```

5469 {%
  ending env
  \LWR@traceinfo{\LWR@nestspan ending}%
  \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}%
  {}%
  \addtocounter{\LWR@spandepth}{-1}%
  \LWR@traceinfo{\LWR@nestspan ending: done}%
}
5476
5477 \AfterEndEnvironment{\LWR@nestspan}{\global\let\par\LWR@closeparagraph}

```

\LWR@htmlspan {*tag*} {*text*}

 \LWR@spandepth is used to ensure that paragraph tags are not generated inside a span.  
The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```

5478 \NewDocumentCommand{\LWR@htmlspan}{m +m}{%
  \LWR@ensuredoingapar%
  \LWR@htmltagc{#1}%
  \begin{\LWR@nestspan}%
  #2%
  \LWR@htmltagc{/#1}%
  \end{\LWR@nestspan}%
}
5485 }

```

\LWR@htmlspanclass [*style*] {*class*} {*text*}

```

5486 \NewDocumentCommand{\LWR@htmlspanclass}{o m +m}{%
  \LWR@traceinfo{\LWR@htmlspanclass |#1|#2|}%
  \LWR@ensuredoingapar%
  \LWR@subhmtlelementclass{span}[#1]{#2}%
  \begin{\LWR@nestspan}%
  #3%
  \LWR@htmltagc{/span}%
  \LWR@traceinfo{\LWR@htmlspanclass done}%
  \end{\LWR@nestspan}%
}
5495 }

```

\LWR@htmltag {*tag*}

Print an HTML tag: <*tag*>

```

5496 \newcommand*{\LWR@htmltag}[1]{%
  \LWR@traceinfo{\LWR@htmltagb !\detokenize{#1}!}%
  \LWR@htmltagc{#1}%
  \LWR@traceinfo{\LWR@htmltagb: done}%
}
5500 }

```

## 51.5 Block tags and comments

In the following, \origttfamily breaks ligatures, which may not be used for HTML codes:

```

\LWR@htmlopencomment
\LWR@htmclosecomment
 5501 \newcommand*{\LWR@htmlopencomment}{%
 5502 {%
 5503 % \LWR@traceinfo{\LWR@htmlopencomment}%
 5504 \begingroup%
 5505 \LWR@FBcancel%
 5506 \ifmmode\else\protect\LWR@origttfamily\fi%
 5507 \LWR@print@mbbox{\LWR@origtextless{}!-/-}%
 5508 \endgroup%
 5509 }%
 5510 }
 5511
 5512 \newcommand*{\LWR@htmclosecomment}{%
 5513 {%
 5514 % \LWR@traceinfo{\LWR@htmclosecomment}%
 5515 \begingroup%
 5516 \LWR@FBcancel%
 5517 \ifmmode\else\protect\LWR@origttfamily\fi%
 5518 \LWR@print@mbbox{-/-\LWR@origtextgreater}%
 5519 \endgroup%
 5520 }%
 5521 }

\LWR@htmlcomment {<comment>}
 5522 \newcommand{\LWR@htmlcomment}[1]{%
 5523 \LWR@htmlopencomment{}%
 5524 {%
 5525 \LWR@origttfamily% break ligatures
 5526 #1%
 5527 }%
 5528 \LWR@htmclosecomment{}}

\LWR@htmlblockcomment {<comment>}
 5529 \newcommand{\LWR@htmlblockcomment}[1]
 5530 {\LWR@stoppars\LWR@htmlcomment{#1}\LWR@startpars}

\LWR@htmlblocktag {<tag>} print a stand-alone HTML tag
 5531 \newcommand*{\LWR@htmlblocktag}[1]{%
 5532 \LWR@stoppars%
 5533 \LWR@htmlltag{#1}%
 5534 \LWR@startpars%
 5535 }

```

## 51.6 Div class and element class

```
\LWR@subhtmlelementclass {<element>} [<style>] {<class>}
```

Factored and reused in several places.

The trailing spaces allow more places for a line break.

The use of \textquotedbl instead of " provides improved compatibility with xeCJK.

```
5536 \NewDocumentCommand{\LWR@subhtmlelementclass}{m O{} m}{%
5537 \LWR@traceinfo{\LWR@subhtmlelementclass !#1!#2!#3!}%
5538 \ifblank{#2}%
5539 {%
5540     \LWR@htmlltag{%
5541         #1 % space
5542         class=\textquotedbl#3\textquotedbl\ % space
5543     }%
5544 }%
5545 {%
5546     \LWR@htmlltag{%
5547         #1\LWR@indentHTML%
5548         class=\textquotedbl#3\textquotedbl\LWR@indentHTML%
5549         style=\textquotedbl#2\textquotedbl\LWR@newline%
5550     }%
5551 }%
5552 \LWR@traceinfo{\LWR@subhtmlelementclass done}%
5553 }
```

\LWR@htmlelementclass {<element>} {<class>} [<style>]

```
5554 \NewDocumentCommand{\LWR@htmlelementclass}{m o m}{%
5555 \LWR@stoppars%
5556 \LWR@forceemptyline%
5557 \LWR@subhtmlelementclass{#1}[#2]{#3}%
5558 \LWR@startpars%
5559 }
```

\LWR@htmlelementclassend {<element>} {<class>}

```
5560 \newcommand*{\LWR@htmlelementclassend}[2]{%
5561 \LWR@stoppars%
5562 \LWR@htmlltag{/#1}%
5563 \ifboolexpr{HTMLDebugComments}{%
5564     \LWR@htmllcomment{End of #1 ``#2''}%
5565 }{}}%
5566 \LWR@startpars%
5567 }
```

\LWR@htmldivclass [<style>] {<class>}

```
5568 \NewDocumentCommand{\LWR@htmldivclass}{o m}{%
5569 \LWR@htmlelementclass{div}[#1]{#2}%
5570 }
```

\LWR@htmldivclassend {<class>}

---

```
5571 \newcommand*{\LWR@htmldivclassend}[1]{%
5572 \LWR@htmlelementclassend{div}{#1}%
5573 }
```

## 51.7 Single-line elements

A single-line element, without a paragraph tag for the line of text:

```
\LWR@htmlelementclassline {\langle element\rangle} [\langle style\rangle] {\langle class\rangle} {\langle text\rangle}

5574 \NewDocumentCommand{\LWR@htmlelementclassline}{m o m +m}{%
5575 \LWR@stoppars
5576 \LWR@forceemptyline%
5577 \LWR@subhtmlelementclass{#1}[#2]{#3}%
5578 #4%
5579 \LWR@htmltag{/#1}
5580 \LWR@startpars
5581 }
```

## 51.8 HTML5 semantic elements

```
\LWR@htmlelement {\langle element\rangle}

5582 \newcommand*{\LWR@htmlelement}[1]{%
5583 \LWR@htmlblocktag{#1}
5584 }

\LWR@htmlelementend {\langle element\rangle}

5585 \newcommand*{\LWR@htmlelementend}[1]{%
5586 \LWR@stoppars
5587 \LWR@htmltag{/#1}
5588 \LWR@startpars
5589 }
5590
5591 \end{warpHTML}
```

## 51.9 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with css.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section [90](#).

Env `BlockClass`  $[\langle style \rangle] \{ \langle class \rangle \}$  High-level interface for `<div>` classes.

Ex: `\begin{BlockClass}{class} text \end{BlockClass}`

**for PRINT output:** 5592 `\begin{warpprint}`  
 5593 `\NewDocumentEnvironment{BlockClass}{o m}{}{}`%  
 5594 `\end{warpprint}`

**for HTML output:** 5595 `\begin{warpHTML}`  
 5596 `\NewDocumentEnvironment{LWR@print@BlockClass}{o m}{}{}`%  
 5597 `\NewDocumentEnvironment{LWR@HTML@BlockClass}{o m}{}{}`%  
 5598 `{%`  
 5599  `\LWR@htmldivclass[#1]{#2}%`  
 5600 `}`  
 5601 `{\LWR@htmldivclassend{#2}}`  
 5602  
 5603 `\LWR@formattedenv{BlockClass}`  
 5604 `\end{warpHTML}`

`\BlockClassSingle`  $\{ \langle class \rangle \} \{ \langle text \rangle \}$  A single-line `<div>`, without a paragraph tag for the line of text.

**for HTML & PRINT:** 5605 `\begin{warpall}`  
 5606 `\newcommand{\BlockClassSingle}[2]{#2}`  
 5607 `\end{warpall}`

**for HTML output:** 5608 `\begin{warpHTML}`  
 5609 `\newcommand{\LWR@HTML@BlockClassSingle}[2]{%`  
 5610  `\LWR@htmlelementclassline{div}{#1}{#2}%`  
 5611 `}`  
 5612  
 5613 `\LWR@formatted{BlockClassSingle}`  
 5614 `\end{warpHTML}`

`\InlineClass`  $(\langle WP \text{ style} \rangle) [\langle style \rangle] \{ \langle class \rangle \} \{ \langle text \rangle \}$

High-level interface for inline span classes.

$(\langle WP \text{ style} \rangle)$  is css styling to add when formatting for a word processor import.

$[\langle style \rangle]$  is the css styling to add when not formatting for a word processor.

**for PRINT output:** 5615 `\begin{warpprint}`  
 5616 `\NewDocumentCommand{\InlineClass}{D{()}{}} o m +m}{#4}%`  
 5617 `\end{warpprint}`

**for HTML output:** 5618 `\begin{warpHTML}`  
 5619 `\NewDocumentCommand{\LWR@print@InlineClass}{D{()}{}} o m +m}{#4}%`  
 5620  
 5621 `\NewDocumentCommand{\LWR@HTML@InlineClass}{D{()}{}} o m +m}{%`  
 5622 `\ifbool{FormatWP}{%`  
 5623  `\LWR@htmlspanclass[#1]{#3}{#4}%`  
 5624 `}{%`  
 5625  `\LWR@htmlspanclass[#2]{#3}{#4}%`  
 5626 `}`

```

5627 }
5628
5629 \LWR@formatted{InlineClass}
5630 \end{warpHTML}
```

Env LWR@BlockClassWP {*WPstyle*} {*HTMLstyle*} {*class*} Low-level interface for <div> classes with an automatic float ID. These are often used when \ifbool{FormatWP}.

The use of \textquotedbl instead of " provides improved compatibility with xeCJK.

**for PRINT output:** 5631 \begin{warpprint}
5632 \NewDocumentEnvironment{LWR@BlockClassWP}{m m m}{}{%
5633 \end{warpprint}}

**for HTML output:** 5634 \begin{warpHTML}
5635 \NewDocumentEnvironment{LWR@print@LWR@BlockClassWP}{m m m}{}{%
5636 \NewDocumentEnvironment{LWR@HTML@LWR@BlockClassWP}{m m m}%
5637 {%
5638 \LWR@stoppars%
5639 \ifbool{FormatWP}%
5640 {%
5641 \addtocounter{LWR@thisautoidWP}{1}%
5642
5643 \LWR@htmlltag{%
5644 div class=\textquotedbl#3\textquotedbl\ % space
5645 id=\textquotedbl%
5646 \LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}%
5647 \ifblank{#1}{}{ style=\textquotedbl#1\textquotedbl}%
5648 }%
5649 }% FormatWP
5650 {%
5651 \LWR@htmlltag{%
5652 div class=\textquotedbl#3\textquotedbl%
5653 \ifblank{#2}{}{ style=\textquotedbl#2\textquotedbl}%
5654 }%
5655 }% not FormatWP
5656 \LWR@startpars%
5657 }
5658 {\LWR@htmldivclassend{#3}}
5659
5660 \LWR@formattedenv{LWR@BlockClassWP}
5661 \end{warpHTML}

## 51.10 Closing HTML tags

**for HTML output:** 5662 \begin{warpHTML}

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```
5663 \newcommand*{\LWR@printclosebook}
```

---

```

5664     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing book}}{}}
5665 \newcommand*{\LWR@printclosepart}
5666     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
5667 \newcommand*{\LWR@printclosechapter}
5668     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
5669 \newcommand*{\LWR@printclosesection}
5670     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
5671 \newcommand*{\LWR@printclosesubsection}
5672     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
5673 \newcommand*{\LWR@printclosesubsubsection}
5674     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsubsection}}{}}
5675 \newcommand*{\LWR@printcloseparagraph}
5676     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
5677 \newcommand*{\LWR@printclosesubparagraph}
5678     {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}

```

Lists require closing HTML tags:

```

5679 \newcommand*{\LWR@printcloselistitem}
5680     {\LWR@htmlltag{/li}}
5681 \newcommand*{\LWR@printclosedescitem}
5682     {\LWR@htmlltag{/dd}}
5683 \newcommand*{\LWR@printcloseitemize}
5684     {\LWR@htmlltag{/ul}}
5685 \newcommand*{\LWR@printcloseenumerate}
5686     {\LWR@htmlltag{/ol}}
5687 \newcommand*{\LWR@printclosedescription}
5688     {\LWR@htmlltag{/dl}}

```

```
5689 \end{warpHTML}
```

## 52 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 53 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (\LWR@doingstartpars), tags are not generated until a L<sup>A</sup>T<sub>E</sub>X paragraph is being used (\LWR@doingapar). LWR@lateximagedepth is used to prevent nesting tags inside a *lateximage*. LWR@spandepth is used to prevent nesting paragraph tags inside a paragraph, which became important inside \fbox commands and other spans.

**for HTML output:** 5690 \begin{warpHTML}

Ctr LWR@spandepth Do not create paragraph tags inside of an HTML span.

```

5691 \newcounter{LWR@spandepth}
5692 \setcounter{LWR@spandepth}{0}

```

Bool LWR@doingstartpars Tells whether paragraphs may be generated.

```
5693 \newbool{LWR@doingstartpars}
5694 \boolearn{LWR@doingstartpars}
```

Bool LWR@doingapar Tells whether have actually generated and are currently processing paragraph text.

```
5695 \newbool{LWR@doingapar}
5696 \global\boolearn{LWR@doingapar}
```

\LWR@ensuredoingapar If are about to print something visible, and if allowed to start a new paragraph, ensure that are LWR@doingapar, so that paragraph tags are placed:

```
5697 \newcommand*{\LWR@ensuredoingapar}{%
5698 \ifbool{LWR@doingstartpars}{%
5699 {\global\boolearn{LWR@doingapar}}{%
5700 {}{%
5701 }}
```

\PN@parnotes@auto Redefined by parnotes to print paragraph notes at the end of each paragraph.

```
5702 \def\PN@parnotes@auto{}%
```

\LWR@openparagraph

```
5703 \newcommand*{\LWR@openparagraph}{%
5704 {}%
```

See if paragraph handling is enabled:

```
5705 \ifbool{LWR@doingstartpars}{%
5706 {}% handling pars}
```

See if have already started a `lateximage` or a `<span>`. If so, do not generate nested paragraph tags.

```
5707 \ifboolexpr{%
5708   test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}}{%
5709     test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}{%
5710   }% nested par tags?}}
```

If so: Do nothing if already started a `lateximage` page. Cannot nest a `lateximage`. Also do nothing if already inside a `<span>`. Do not nest paragraph tags inside a `<span>`.

```
5711 {}% no nested par tags
```

Else: No `lateximage` or `<span>` has been started yet, so it's OK to generate paragraph tags.

```
5712 {}% yes nest par tags
```

If `parnotes` is used, paragraph notes are inserted before starting the next paragraph:

```
5713 \PN@parnotes@auto%
```

The opening paragraph tag:

```
5714 \LWR@htmllagc{\LWR@tagregularparagraph}\LWR@orignewline%
```

Now have started a paragraph.

```
5715 \global\booltrue{\LWR@doingapar}%
```

At the end of each paragraph, generate closing tag and do regular /par stuff. (Attempting to use the `everyhook cr` hook for `\LWR@closeparagraph` does not work well.)

```
5716 \let\par{\LWR@closeparagraph%  
5717 }% end of yes nest par tags  
5718 }% end of handling pars  
5719 {}% not handling pars  
5720 }
```

`\LWR@closeparagraph@br` Add an HTML break if in a span, and not in a `lateximage`, and not in tabular metadata.  
Factored from `\LWR@closeparagraph`.

```
5721 \newcommand*{\LWR@closeparagraph@br}{  
5722 {}%  
5723 \ifboolexpr{  
5724 test {\ifnumcomp{\value{\LWR@spandepth}}{>}{0}} and  
5725 test {\ifnumcomp{\value{\LWR@lateximagedepth}}{=}{0}} and  
5726 not bool {\LWR@intabularmetadata}  
5727 }%  
5728 {\unskip\LWR@htmllagc{br /}}%  
5729 {}%  
5730 }
```

`\LWR@closeparagraph`

```
5731 \newcommand*{\LWR@closeparagraph}{  
5732 {}%  
5733 % \LWR@traceinfo{\LWR@closeparagraph}%
```

See if paragraph handling is enabled:

```
5734 \ifbool{\LWR@doingapar}{}
```

If currently in paragraph mode:

```
5735 {}% handling pars
```

See if already started a `lateximage` or a `<span>`:

```
5736 \ifboolexpr{  
5737 test {\ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}} or  
5738 test {\ifnumcomp{\value{\LWR@spandepth}}{>}{0}}  
5739 }%
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
5740      {% no nested par tags
5741          \LWR@closeparagraph@br%
5742      }% no nested par tags
```

If have not already started a `lateximage` or a `<span>`:

```
5743      {% yes nest par tags
```

Print a closing tag and some extra vertical space.

(The `fill` seems to be required to force the `caption` package to create flush left caption text in the HTML.)

```
5744      @hspacer{\fill}%
5745      \leavevmode\LWR@newline%
5746      \LWR@htmltagc{/LWR@tagregularparagraph}%
```

No longer doing a paragraph:

```
5747      \global\boolfalse{LWR@doingapar}%
```

Disable the special `minipage` & `\hspace` interaction until a new minipage is found:

```
5748      \global\boolfalse{LWR@minipagethispar}%
```

If `parnotes` is used, paragraph notes are inserted after ending the previous paragraph:

```
5749      \PN@parnotes@auto%
5750      }% end of yes nest par tags
5751 }% end of handling pars
```

Add a parbreak if in a span, not in a `lateximage`, and not in table metadata.

```
5752 {% not handling pars
5753     \LWR@closeparagraph@br%
5754 }% not handling pars
```

In most cases, finish with a L<sup>A</sup>T<sub>E</sub>X `\par`, but in the case of paragraphs between lines in a tabular fetch the next token instead:

```
5755 \ifboolexpr{%
5756     not bool {LWR@doingapar} and
5757     test {\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}} and
5758     test {
5759         \ifnumcomp{\value{LWR@tabulardepth}}{=}{\value{LWR@tabularpardepth}}
5760     } and
5761     bool {LWR@intabularmetadata} and
5762     not bool {LWR@tableparcell} and
5763     test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
5764 }%
5765 {%
```

---

```

5766     \LWR@getmynexttoken%
5767 }%
5768     \LWR@origpar%
5769 }%
5770 }

5771 \end{warpHTML}

```

## 53 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 52 has the commands which actually generate the tags.

The everyhook package is used to generate the opening paragraph tags. The closing tags are generated by \par.

**for HTML output:** 5772 \begin{warpHTML}

\LWR@startpars Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```

5773 \newcommand*\LWR@startpars{%
5774 {%
5775 % \LWR@traceinfo{\LWR@startpars}%

```

Ignore if inside a span:

```

5776 \ifnumcomp{\value{LWR@spandepth}}{>}{0}{%
5777 {}%
5778 {}%

```

See if currently handling HTML paragraphs:

```

5779 \ifbool{\LWR@doingstartpars}{%

```

If already in paragraph mode, do nothing.

```

5780 {}%

```

If not currently in paragraph mode:

```

5781 {}%

```

At the start of each paragraph, generate an opening tag:

```

5782 \PushPreHook{par}{\LWR@openparagraph}%

```

At the end of each paragraph, generate closing tag then do regular /par actions:

---

```

5783      \let\par\LWR@closeparagraph
5784
5785  }% an intentionally blank line

```

Are now handling paragraphs, but have not yet actually started one:

```

5786  \global\setbool{\LWR@doingstartpars}{true}%

```

No <par> tag yet to undo:

```

5787  \global\boolfalse{\LWR@doingapar}%
5788 }% nestspan
5789 % \LWR@traceinfo{\LWR@startpars: done}%
5790 }

```

\LWR@stopars Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```

5791 \newcommand*{\LWR@stopars}%
5792 {%

```

Ignore if inside a span:

```

5793 \ifnumcomp{\value{\LWR@spandepth}}{>}{0}%
5794 {}%
5795 {%

```

See if currently handling HTML paragraphs:

```

5796 \ifbool{\LWR@doingapar}%

```

if currently in an HTML paragraph:

```

5797 {%

```

Print a closing tag:

```

5798  \leavevmode\LWR@orignewline%
5799  \LWR@htmlltagc{/ \LWR@tagregularparagraph}%
5800  \LWR@orignewline%

```

No longer have an open HTML paragraph:

```

5801 \global\boolfalse{\LWR@doingapar}%

```

Disable the special `\minipage` & `\hspace` interaction until a new minipage is found:

```

5802 \global\boolfalse{\LWR@minipagethispar}%
5803 }%

```

If was not in an HTML paragraph:

```

5804 {}%

```

See if currently allowing HTML paragraphs:

```
5805 \ifbool{LWR@doingstartpars}{%
```

If so: clear the par hook to no longer catch paragraphs:

```
5806 {\ClearPreHook{par}}%
```

Else: Do nothing:

```
5807 {}%
```

No longer in paragraph mode:

```
5808 \global\setbool{LWR@doingstartpars}{false}{%
```

No <p> tag to undo:

```
5809 \global\boolfalse{LWR@doingapar}{%
5810 }% nestspan
5811 }
```

```
5812 \end{warpHTML}
```

## 54 Indentfirst

Pkg indentfirst indentfirst redefines \@afterindentfalse to be \@afterindenttrue. This is reversed \AtBeginDocument here.

for HTML output: 5813 \begin{warpHTML}

```
5814 \AtBeginDocument{
5815 \def\@afterindentfalse{\let\if@afterindent\iffalse}
5816 \@afterindentfalse
5817 }
5818 \let\LWR@afterindent@syntaxhighlight\fi% syntax highlighting

5819 \end{warpHTML}
```

## 55 Page headers and footers

for HTML & PRINT: 5820 \begin{warpall}

In the following, catcode is manually changed back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
5821 \newcommand{\LWR@firstpagetop}{} % for the home page alone
5822 \newcommand{\LWR@pagetop}{} % for all other pages
5823 \newcommand{\LWR@pagebottom}{}%
```

---

```
\HTMLFirstPageTop {<text and logos>}

5824 \newcommand{\HTMLFirstPageTop}[1]{%
5825     \renewcommand{\LWR@firstpagetop}{#1}%
5826 }

\HTMLPageTop {<text and logos>}

5827 \newcommand{\HTMLPageTop}[1]{%
5828     \renewcommand{\LWR@pagetop}{#1}%
5829 }

\HTMLPageBottom {<text and logos>}

5830 \newcommand{\HTMLPageBottom}[1]{%
5831     \renewcommand{\LWR@pagebottom}{#1}%
5832 }

5833 \end{warpall}
```

## 56 CSS

**for HTML output:** 5834 \begin{warpHTML}

\LWR@currentcss The css filename to use. This may be changed mid-document using \CSSFilename, allowing different css files to be used for different sections of the document.

```
5835 \newcommand*{\LWR@currentcss}{lwarp.css}
```

\CSSFilename {<new-css-filename.css>} Assigns the css file to be used by the following HTML pages.

```
5836 \newcommand*{\CSSFilename}[1]{%
5837 \renewcommand*{\LWR@currentcss}{#1}%
5838 @onelvel@sanitize\LWR@currentcss%
5839 }
5840
5841 \end{warpHTML}
```

**for PRINT output:** 5842 \begin{warpprint}
5843 \newcommand\*{\CSSFilename}[1]{}
5844 \end{warpprint}

## 57 MathJax script

**for HTML output:** 5845 \begin{warpHTML}

Default: `lwarp_mathjax.txt`

`\LWR@mathjaxfilename` The MathJax script filename to use. This file is copied into the head of each HTML page. This may be changed mid-document using `\MathJaxFilename`, allowing the use of a custom MathJax script, such as for a local repository, or different MathJax script files to be used for different sections of the document.

```
5846 \newcommand*{\LWR@mathjaxfilename}{lwarp_mathjax.txt}
```

`\MathJaxFilename {<filename>}` Assigns the MathJax script file to be used by the following HTML pages.

```
5847 \newcommand*{\MathJaxFilename}[1]{%
5848     \renewcommand*{\LWR@mathjaxfilename}{#1}%
5849     \@onelvel@sanitize\LWR@mathjaxfilename%
5850 }
5851
5852 \end{warpHTML}
```

**for PRINT output:** 5853 `\begin{warpprint}`  
 5854 `\newcommand*{\MathJaxFilename}[1]{}%`  
 5855 `\end{warpprint}`

## 58 Title, HTML meta author, HTML meta description

**for HTML output:** 5856 `\begin{warpHTML}`

`\title {<title>}` Modified to remember `\thetitle`, which is used to set the HTML page titles.

```
5857 \let\LWR@origtitle\title
5858
5859 \renewcommand*{\title}[1]{%
5860     \LWR@origtitle{#1}%
5861     \begingroup%
5862         \renewcommand{\thanks}[1]{}%
5863         \protected@xdef\thetitle{#1}%
5864     \endgroup%
5865 }
```

```
5866 \end{warpHTML}
```

**for HTML & PRINT:** 5867 `\begin{warpall}`

`\HTMLTitle {<Titlename>}` The Title to place into an HTML meta tag. The default is to use the document `\title`'s setting.

```
5868 \providecommand{\thetitle}{\BaseJobname}
5869
5870 \newcommand{\theHTMLTitle}{\thetitle}
5871
5872 \newcommand{\HTMLTitle}[1]{\renewcommand{\theHTMLTitle}{#1}}
```

---

\HTMLAuthor {⟨authorname⟩} The author to place into an HTML meta tag. If none given, the default is \theauthor, which is empty unless the `titling` package is used.

```
5873 \providecommand{\theauthor}{}
5874
5875 \newcommand{\theHTMLAuthor}{\theauthor}
5876
5877 \newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}
```

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using \HTMLDescription, allowing different HTML descriptions to be used for different sections of the document.

⚠ **HTML author** Do not use double quotes, and do not exceed 150 characters.

\HTMLDescription {⟨New HTML meta description.⟩} Assigns the HTML file's description meta tag.

```
5878 \newcommand{\LWR@currentHTMLDescription}{}
5879
5880 \newcommand{\HTMLDescription}[1]{%
5881 \renewcommand{\LWR@currentHTMLDescription}{#1}
5882 }
5883
5884 \end{warpall}
```

## 59 Footnotes

lwarp uses native L<sup>A</sup>T<sub>E</sub>X footnote code, although with its own \box to avoid the L<sup>A</sup>T<sub>E</sub>X output routine. The usual functions mostly work as-is.

**footnote numbering** To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For `bigfoot`, `manyfoot`, or `perpage`:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

**footmisc** The `footmisc` stable option is emulated by lwarp.

⚠ **sectioning commands** When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the `footmisc` package with the `stable` option, provide a short toc entry, and \protect the \footnote:

---

```
\usepackage[stable]{footmisc}
...
\subsection[Subsection Name]
{Subsection Name\protect\footnote{A footnote.}}
```

**memoir with footmisc** If using `memoir` class, with which `l warp` preloads `footmisc`, the `stable` option must be declared before `l warp` is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{l warp}
...
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handled differently.

## 59.1 Regular page footnotes

In `HTML` documents, footnotes are placed at the bottom of the web page or the section, depending on `FootnoteDepth`, using the `LATEX` box `\LWR@footnotebox`. Using this instead of the original `\footins` box avoids having footnotes be printed by the output routine, since footnotes should be printed per `HTML` page instead of per `PDF` page.

See section 59.4 for the implementation.

## 59.2 Minipage footnotes

See section 59.5 for how minipage footnotes are gathered. See section 89.4 for how minipage footnotes are placed into the document.

## 59.3 Titlepage thanks

See section 66.7 for titlepage footnotes.

## 59.4 Regular page footnote implementation

**for HTML & PRINT:** 5885 `\begin{warpall}`

**Ctrl** `FootnoteDepth` Determines how deeply to place footnotes in the `HTML` files, similar to `tocdepth`. The default of 3 places footnotes before each `\subsubsection` or higher. See table 9 for a table of `LATEX` section headings.

5886 `\newcounter{FootnoteDepth}`  
5887 `\setcounter{FootnoteDepth}{3}`

**Ctr footnoteReset** If non-zero, the footnote counter is reset to this value each time the footnotes are printed, as controlled by `FootnoteDepth`. For the `manyfoot` and `bigfoot` packages, additional counters such as `footnote<suffix>Reset` will be defined as well. These counters may be set non-zero by the user, and are also set if the `perpage`'s `\MakePerPage` or `\MakeSortedPerPage` macros are used for the footnote or `footnote<suffix>` counters.

(The name is not capitalized because it is made from the counter's name with "Reset" appended.)

```
5888 \newcounter{footnoteReset}
5889 \setcounter{footnoteReset}{0}

5890 \end{warpall}
```

**for HTML output:** 5891 `\begin{warpHTML}`

`\LWR@footnotebox` Patch L<sup>A</sup>T<sub>E</sub>X footnotes to use a new `\box` instead of an insert for `lwarp` footnotes. This avoids having the original `\footins` appear at the bottom of a `lateximage`, which is on its own new page.

```
5892 \newbox\LWR@footnotebox
```

Much of the following has unneeded print-mode formatting removed.

```
\@makefntext {\langle text\rangle}

5893 \long\def\@makefntext#1{\textsuperscript{\@thefnmark}~#1}

\@makefnmark

5894 \def\@makefnmark{%
5895   \textsuperscript{\@thefnmark}%
5896 }
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or `lateximage`, in which case paragraph tags must be added manually.

In a `lateximage` during HTML output, the `lateximage` is placed inside a print-mode `minipage`, but the footnotes are broken out by:

```
\def\@mpfn{footnote}
\def\thempfn{\thefootnote}
\let\@footnotetext\@LWR@footnotetext
```

`\LWR@@footnotetext` `\{\langle text\rangle\} \{\langle footnote box name\rangle\}`

Factored to allow multiple footnote boxes for `manyfoot`.

---

```
5897 \long\def\LWR@footnotetext#1#2{%
5898 \LWR@traceinfo{\LWR@footnotetext}%
5899 \global\setbox\csname #2\endcsname=\vbox{%
```

Add to any current footnotes:

```
5900 \unvbox\csname #2\endcsname%
```

Remember the footnote number for \ref:

```
5901 \protected@edef@\currentlabel{%
5902     \csname p@footnote\endcsname\@thefnmark%
5903 }% @currentlabel
```

Open a group:

```
5904 \color@begingroup%
```

Use HTML superscripts in the footnote even inside a `\textrimage`:

```
5905 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `\textrimage`:

```
5906 \ifthenelse{%
5907     \boolean{\LWR@doingstartpars} \AND%
5908     \cnttest{\value{\LWR@lateximagedepth}}{=}{0}%
5909 }%
5910 {}%
5911 {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
5912 \@makefntext{#1}%
```

Closing paragraph tag:

```
5913 \ifthenelse{%
5914     \boolean{\LWR@doingstartpars} \AND%
5915     \cnttest{\value{\LWR@lateximagedepth}}{=}{0}%
5916 }%
5917 {}%
5918 {\LWR@htmltagc{/}\LWR@tagregularparagraph}%
5919 \LWR@orignewline%
5920 }%
```

Close the group:

```
5922 \color@endgroup%
5923 }% vbox
```

Paragraph handling:

```

5924 \LWR@ensuredoingapar%
5925 }%  

\LWR@footnotetext {<text>}  

5926 \long\def\LWR@footnotetext#1{\LWR@footnotetext{#1}{\LWR@footnotebox}}  

\@footnotetext {<text>}  

5927 \LetLtxMacro\@footnotetext\LWR@footnotetext

```

## 59.5 Minipage footnote implementation

Patch L<sup>A</sup>T<sub>E</sub>X minipage footnotes to use a new `\box` instead of an insert for `lwarp` minipage footnotes. This avoids having the original `\@mpfootins` appear at the bottom of a `lateximage`, which is on its own new page.

```

5928 \newbox\LWR@mpfootnotes  

\@mpfootnotetext {<text>}  

5929 \long\def\@mpfootnotetext#1{%
5930 \LWR@traceinfo{@mpfootnotetext}%
5931 \global\setbox\@mpfootnotes\vbox{%
5932   \unvbox\@mpfootnotes%
5933   \reset@font\footnotesize%
5934   \hsize\columnwidth%
5935   \parboxrestore%
5936   \protected@edef\@currentlabel{%
5937     \csname p@mpfootnote\endcsname\@thefnmark}%
5938   \color@begingroup%

```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```

5939 \ifthenelse{%
5940   \boolean{\LWR@doingstartpars} \AND%
5941   \cnttest{\value{\LWR@lateximagedepth}}{=}{0}%
5942 }%
5943 {}%
5944 {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
  

5945 \@makefntext{%
5946   \ignorespaces#1%
5947 }%

```

Don't add the closing paragraph tag if are inside a `lateximage`:

```

5948 \ifthenelse{\cnttest{\value{\LWR@lateximagedepth}}{>}{0} }{%
5949 }%
5950 {}%

```

```

5951           \leavevmode\lwr@orignewline%
5952           \lwr@htmltagc{/ \lwr@tagregularparagraph}%
5953           \lwr@origpar%
5954       }%
5955   \color@endgroup%
5956 }% vbox

```

Paragraph handling:

```

5957 \lwr@ensuredoingapar%
5958 \lwr@traceinfo{@mpfootnotetext: done}%
5959 }

```

\thempfootnote Redefined to remove the \itshape, which caused an obscure compiling error in some situations.

```

5960 \AtBeginDocument{%
5961 \def\thempfootnote{\@alph\c@mpfootnote}%
5962 }

```

## 59.6 Printing pending footnotes

\lwr@@printpendingfootnotes {*<footnote counter name>*}

```

5963 \newcommand*{\lwr@@printpendingfootnotes}[1]{%
5964 \expandafter\ifvoid\csname \lwr@#1box\endcsname\else
5965   \lwr@forcenewpage
5966   \begin{BlockClass}{footnotes}
5967   \null
5968   \unvbox\csuse{\lwr@#1box}
5969   \setbox\csuse{\lwr@#1box}=\vbox{%
5970   \end{BlockClass}
5971   \ifltxcounter{\#1Reset}{%
5972     \ifnumgreater{\value{\#1Reset}}{0}{%
5973       \setcounter{\#1}{\value{\#1Reset}}%
5974       \addtocounter{\#1}{-1}%
5975     }{}%
5976   }{}%
5977 \fi
5978 }

```

\lwr@printpendingfootnotes Enclose the footnotes in a class, print, then clear. For **manynotes**, new footnotes may be added via \appto.

```

5979 \newcommand*{\lwr@printpendingfootnotes}{%
5980   \lwr@printpendingfootnotes{footnote}%
5981 }

```

\lwr@maybeprintpendingfootnotes {*<depth>*} Used to print footnotes before sections only if formatting for an EPUB or word processor:

---

```

5982 \newcommand*{\LWR@maybeprintpendingfootnotes}[1]{%
5983 \ifboolexpr{%
5984     not test{\ifnumcomp{#1}{>}{\value{FootnoteDepth}}} or
5985     bool{FormatEPUB} or
5986     bool{FormatWP}
5987 }%
5988 {\LWR@printpendingfootnotes}%
5989 {}%
5990 }

```

\LWR@printpendingmpfootnotes Enclose the minipage footnotes in a class, print, then clear.

```

5991 \newcommand*{\LWR@printpendingmpfootnotes}{%
5992 \ifvoid\LWR@mpfootnotes\else
5993     \LWR@forcenewpage
5994     \begin{BlockClass}{footnotes}
5995     \null
5996     \unvbox\LWR@mpfootnotes
5997     \setbox\LWR@mpfootnotes=\vbox{%
5998     \end{BlockClass}
5999 \fi
6000 }

6001 \end{warpHTML}

```

## 60 Marginpars

\marginpar [⟨left⟩] {⟨right⟩} \marginpar may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the \marginpar. Paragraph breaks are converted to <br /> tags.

\marginparBlock [⟨left⟩] {⟨right⟩} To include block-related macros, use \marginparBlock, which takes the same arguments but creates a <div> instead of a <span>. A line break will occur in the text where the \marginBlock occurs.

**for HTML output:** 6002 \begin{warpHTML}

```

\marginpar [⟨left⟩] {⟨right⟩}

6003 \renewcommand{\marginpar}[2][]{}%
6004 \ifbool{FormatWP}{%
6005 {}%
6006 \begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{\marginblock}
6007 #2
6008 \end{LWR@BlockClassWP}
6009 }%
6010 {}%
6011     \LWR@htmlspanclass{\marginpar}{#2}%
6012 }%
6013 }

```

```
\marginparBlock [⟨left⟩] {⟨right⟩}
```

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

HTML version.

```
6014 \newcommand{\marginparBlock}[2][]{%
6015 \LWR@stoppars%
6016 \ifbool{FormatWP}{%
6017 }{%
6018   \begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{marginblock}%
6019   #2%
6020   \end{LWR@BlockClassWP}%
6021 }{%
6022   \begin{BlockClass}[width:2in; float:right; margin:10pt]{marginparblock}%
6023   #2%
6024   \end{BlockClass}%
6025 }%
6026 \LWR@startpars%
6027 }
```

```
\reversemarginpar
```

```
6028 \renewcommand*{\reversemarginpar}{}%
```

```
\normalmarginpar
```

```
6029 \renewcommand*{\normalmarginpar}{}%
6030 \end{warpHTML}
```

**for PRINT output:** 6031 \begin{warpprint}

```
\marginparBlock [⟨left⟩] {⟨right⟩}
```

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

Print version.

```
6032 \LetLtxMacro\marginparBlock\marginpar%
6033 \end{warpprint}
```

## 61 Splitting HTML files

- Files are split according to `FileDepth` and `CombineHigherDepths`.
- Filenames are sanitized by `\LWR@filenamenoblanks`.

- \LWR@newhtmlfile finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

**for HTML & PRINT:** 6034 \begin{warpall}

Ctr FileDepth {*<section depth>*} determines how deeply to break into new HTML files, similar to tocdepth. The default of -5 produces one large HTML file.

6035 \newcounter{FileDepth}  
6036 \setcounter{FileDepth}{-5}

Bool CombineHigherDepths Comile higher-level sections together into one file?

6037 \newbool{CombineHigherDepths}  
6038 \booltrue{CombineHigherDepths}

\FilenameLimit Maximum length of the generated filenames.

6039 \newcommand\*\{\FilenameLimit}{80}  
6040 \end{warpall}

**for HTML output:** 6041 \begin{warpHTML}

\LWR@thisfilename The currently-active filename or number. At first, this is the homepage.

6042 \AtBeginDocument{  
6043 \ifbool{FileSectionNames}{%  
6044 {\newcommand\*\{\LWR@thisfilename}{\HomeHTMLFilename}}  
6045 {\newcommand\*\{\LWR@thisfilename}{0}}  
6046 }}

\LWR@thisnewfilename The filename being sanitized.

6047 \newcommand\*\{\LWR@thisnewfilename}{}{}

\LWR@simplifyname \* {*<expression>*} Simplify \LWR@thisnewfilename.

If starred, detokenizes the input expression. If found, changes the expression to a single detokenized dash.

6048 \NewDocumentCommand{\LWR@simplifyname}{s m}{%  
6049 \IfBooleanTF{#1}{%  
6050 \StrSubstitute{\LWR@thisnewfilename}{%  
6051 {\detokenize{#2}}}{%  
6052 {\detokenize{-}}[\LWR@thisnewfilename]}%  
6053 }{  
6054 \StrSubstitute{\LWR@thisnewfilename}{%  
6055 {\#2}}{  
6056 {\detokenize{-}}[\LWR@thisnewfilename]}%  
6057 }  
6058 }

---

\LWR@simplifycustom User-defined filename simplifications. Redefine with \newcommand.

6059 \newcommand\*\{\LWR@simplifycustom\}{}%

\FilenameSimplify \* {\i<phrase>} Assign a user-defined filename simplification. Appends to \LWR@simplifycustom.

```
6060 \NewDocumentCommand{\FilenameSimplify}{s m}{%
6061 \IfBooleanTF{#1}{%
6062     \appto{\LWR@simplifycustom}{%
6063         \LWR@simplifyname*{#2}}%
6064     }%
6065 }%
6066 \appto{\LWR@simplifycustom}{%
6067     \LWR@simplifyname{#2}}%
6068 }%
6069 }%
6070 }
```

\LWR@filenamenoblanks {\i<filename>}

Convert blanks into dashes, removes short words, store result in \LWR@thisfilename.

Also see \LWR@nullfonts for nullified macros.

```
6071 \newcommand*\{\LWR@filenamenoblanks\}[1]{%
6072 \begingroup
```

Locally temporarily disable direct-formatting commands, not used in filenames:

```
6073 \LWR@nullfonts%
6074 \renewcommand*\{\LWR@htmlltagc\}[1]{}%
```

```
6075 \edef\LWR@thisnewfilename{\#1}%
```

Replaces common macros with hyphens. (\& is done by \LWR@nullfonts.)

```
6076 \RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
6077 \LWR@simplifyname{\_}
6078 \LWR@simplifyname{\#}
6079 \LWR@simplifyname{\textbackslash}
6080 \LWR@simplifyname{\protect}
6081 \LWR@simplifyname{\ }
6082 \LWR@simplifyname{\textless}
6083 \LWR@simplifyname{\textgreater}
```

```
6084 \edef\LWR@thisnewfilename{\detokenize\expandafter{\LWR@thisnewfilename}}%
```

```
6085 \LWR@traceinfo{\LWR@filenamenoblanks \edef: !\LWR@thisnewfilename!}%
6086 \fullexpandarg%
```

Convert spaces into hyphens:

```
6087 \LWR@simplifyname*{ }
```

Convert punctuation into hyphens:

```
6088 \LWR@simplifyname*{!}
```

```
6089 \LWR@simplifyname*{,}
```

```
6090 \LWR@simplifyname*{'}
```

```
6091 \LWR@simplifyname*{+}
```

```
6092 \LWR@simplifyname*{,}
```

```
6093 \LWR@simplifyname*{/}
```

```
6094 \LWR@simplifyname*{:}
```

```
6095 \LWR@simplifyname*{;}
```

```
6096 \LWR@simplifyname*{=}
```

```
6097 \LWR@simplifyname*{?}
```

```
6098 \LWR@simplifyname*{@}
```

```
6099 \LWR@simplifyname*{^}
```

```
6100 \LWR@simplifyname*{&}
```

```
6101 \LWR@simplifyname*{"}
```

```
6102 \LWR@simplifyname*{<}
```

```
6103 \LWR@simplifyname*{>}
```

```
6104 \LWR@simplifyname{\LWRbackslash}
```

Braces are removed entirely to avoid extra dashes in the result.

```
6105 \StrSubstitute{\LWR@thisnewfilename}%
```

```
6106     {\LWRleftbrace}{}[\LWR@thisnewfilename]%
```

```
6107 \StrSubstitute{\LWR@thisnewfilename}%
```

```
6108     {\LWRrightbrace}{}[\LWR@thisnewfilename]%
```

```
6109 \LWR@simplifyname{\LWRpercent}
```

```
6110 \LWR@simplifyname{\LWRdollar}
```

```
6111 \LWR@simplifyname*{|}
```

```
6112 \LWR@simplifyname*{^}
```

```
6113 \LWR@simplifyname*{~}
```

```
6114 \LWR@simplifyname*{[]}
```

```
6115 \LWR@simplifyname*{[]}
```

```
6116 \LWR@simplifyname*{`}
```

Convert short words:

```
6117 \LWR@simplifyname*{-s-}
```

```
6118 \LWR@simplifyname*{-S-}
```

```
6119 \LWR@simplifyname*{-a-}
```

```
6120 \LWR@simplifyname*{-A-}
```

```
6121 \LWR@simplifyname*{-an-}
```

```
6122 \LWR@simplifyname*{-AN-}
```

```
6123 \LWR@simplifyname*{-to-}
```

```
6124 \LWR@simplifyname*{-TO-}
```

```
6125 \LWR@simplifyname*{-by-}
```

---

```

6126 \LWR@simplifyname*{-BY-}
6127 \LWR@simplifyname*{-of-}
6128 \LWR@simplifyname*{-OF-}
6129 \LWR@simplifyname*{-and-}
6130 \LWR@simplifyname*{-AND-}
6131 \LWR@simplifyname*{-for-}
6132 \LWR@simplifyname*{-FOR-}
6133 \LWR@simplifyname*{-the-}
6134 \LWR@simplifyname*{-THE-}

```

Convert custom words:

```
6135 \LWR@simplifycustom%
```

Convert multiple hyphens:

```

6136 \LWR@simplifyname*{----}
6137 \LWR@simplifyname*{---}
6138 \LWR@simplifyname*{--}
6139 \LWR@simplifyname*{--}

```

If pdflATEX and not utf8 encoding, don't try to convert emdash, endash:

```

6140 \ifPDFTeX% pdflatex or dvi latex
6141 \ifdefstring{\inputencodingname}{utf8}{%
6142 \LWR@simplifyname*{-}
6143 %      emdash
6144 \LWR@simplifyname*{-}
6145 %      endash
6146 }{}}%
6147 \else% not PDFTeX
6148 \LWR@simplifyname*{-}
6149 \LWR@simplifyname*{-}
6150 \fi%

```

If starts with a dash, remove the leading dash:

```

6151 \IfBeginWith{\LWR@thisnewfilename}{\detokenize{-}}{%
6152     \StrGobbleLeft{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
6153 }{}}%

```

If ends with a dash, remove the trailing dash:

```

6154 \IfEndWith{\LWR@thisnewfilename}{\detokenize{-}}{%
6155     \StrGobbleRight{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
6156 }{}}%

```

Limits the length of the filename:

```
6157 \StrLeft{\LWR@thisnewfilename}{\FilenameLimit}[\LWR@thisnewfilename]%
```

Return the global result:

```
6158 \global\let\LWR@thisfilename\LWR@thisnewfilename%
```

```

6159 \endgroup%
6160 \LWR@traceinfo{\LWR@filenamenoblanks: result is \LWR@thisfilename}%
6161 }

```

Ctr Remembers which autopage label was most recently generated. Used to avoid duplicates.  
 $\LWR@previousautopagelabel$

```

6162 \newcounter{\LWR@previousautopagelabel}
6163 \setcounter{\LWR@previousautopagelabel}{-1}

```

File  $*_{\text{html}}.aux$  A new entry in the  $*_{\text{html}}.aux$  file is used to help cross-references:

```
\newlabel{autopage- $<nnn>$ }{ $\{<x>\}<y>$ }
```

$\LWR@newautopagelabel$   $\{\langle \text{pagenumber counter} \rangle\}$

$\text{\BaseJobname}$  is added to the label in case  $\text{xr}$  or  $\text{xr-hyper}$  are used.

```

6164 \newcommand*{\LWR@newautopagelabel}[1]{%
6165 \ifnumequal{\value{\LWR@previousautopagelabel}}{\value{page}}{%
6166 {}% no action if this autopage label has already been defined
6167 {}%
6168 \label{\BaseJobname-autopage-\arabic{#1}}%
6169 \setcounter{\LWR@previousautopagelabel}{\value{page}}%
6170 }%
6171 }

```

## 61.1 Sanitizing expressions for HTML

Math expressions are converted to `lateximages`, and some math environments may contain &, <, or >, which should not be allowed inside an HTML `<alt>` tag, so must convert them to HTML entities.

$\LWR@subHTMLsanitize$   $\LWR@strresult$  must first be set by  $\LWR@HTMLsanitize$ ,  $\LWR@HTMLsanitizeexpand$ , or  $\CustomizeMathJax$ .

```
6172 \newcommand{\LWR@subHTMLsanitize}{%
```

The &, <, and > may be interpreted by the browser:

```

6173 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}{%
6174 {\detokenize{&}}{\detokenize{&}}[\LWR@strresult]}%
6175 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}{%
6176 {\detokenize{<}}{\detokenize{<}}[\LWR@strresult]}%
6177 \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}{%
6178 {\detokenize{>}}{\detokenize{>}}[\LWR@strresult]}%

```

The double quote occasionally causes problems.

```
6179     \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
6180         {\detokenize{"}}{\detokenize{"}}[\LWR@strresult]%
```

MathJax allows expressions to be defined with `\newcommand`. These expressions would appear with ## for each argument, and each must be changed to a single #. This must be done after all the above changes. Attempting another conversion after this causes an error upon further expansion.

```
6181     \protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
6182         {\detokenize{##}}{\LWR@origpound}[\LWR@strresult]%
6183 }
```

```
\LWR@HTMLsanitize {<text>}
```

```
6184 \newrobustcmd{\LWR@HTMLsanitize}[1]{%
```

Cancel French `babel` character handling, and fully expand the strings:

```
6185     \begingroup%
6186     \LWR@FBcancel%
6187     \fullexpandarg%
6188     \protect\StrSubstitute{\detokenize{#1}}%
6189         {\detokenize{\&}}{\detokenize{&}}[\LWR@strresult]%
6190     \LWR@subHTMLsanitize%
6191     \LWR@strresult%
6192     \endgroup%
6193 }
```

```
\LWR@HTMLsanitizeexpand {<text>}
```

This version expands the argument before sanitizing it.

```
6194 \newrobustcmd{\LWR@HTMLsanitizeexpand}[1]{%
```

Cancel French `babel` character handling, and fully expand the strings:

```
6195     \begingroup%
6196     \LWR@FBcancel%
6197     \fullexpandarg%
```

The difference between this and `\LWR@HTMLsanitize` (without “expand”) is the following `\expandafter`:

```
6198     \protect\StrSubstitute{\detokenize\expandafter{\#1}}%
6199         {\detokenize{\&}}{\detokenize{&}}[\LWR@strresult]%
6200     \LWR@subHTMLsanitize%
6201     \LWR@strresult%
6202     \endgroup%
6203 }
```

## 61.2 Customizing MATHJAX

\LWR@customizedMathJax Additional MATHJAX definitions to be added to the start of each HTML page.

```
6204 \newcommand*\LWR@customizedMathJax{}
```

Bool Used to issue only one warning about using a \CustomizeMathJax per macro.

```
LWR@warnedcustomizemathjax
6205 \newbool{LWR@warnedcustomizemathjax}
6206 \boolfalse{LWR@warnedcustomizemathjax}
```

\LWR@subcustomizedmathjax {*macro definition*}

```
6207 \newcommand*\LWR@subcustomizedmathjax[1]{%
6208     \begingroup%
6209     \LWR@FBcancel%
6210     \fullexpandarg%
6211     \protect\StrSubstitute{\detokenize{\#1}}{%
6212         {\detokenize{\&}}{\detokenize{\&}}[\LWR@strresult]%
6213     \LWR@subHTMLsanitize%
6214     \xdef\LWR@customizedMathJax{%
6215         \LWR@customizedMathJax%
6216         \LWR@strresult%
6217     }%
6218     \endgroup%
6219 }
6220 \@onlypreamble\LWR@subcustomizedmathjax
```

\CustomizeMathJax {*macro definition*}

A warning is issued if a very long argument is given.

```
6221 \newcommand*\CustomizeMathJax[1]{%
6222     \ifbool{LWR@warnedcustomizemathjax}{}{%
6223         \StrLen{\detokenize{\#1}}[\LWR@tempone]%
6224         \ifnumgreater{\LWR@tempone}{200}{%
6225             \AtBeginDocument{%
6226                 \PackageWarningNoLine{lwarp}{%
6227                     To ensure faster MathJax compilation, place each\MessageBreak
6228                     custom macro in its own \protect\CustomizeMathJax.\MessageBreak
6229                     See the Lwarp documentation regarding customizing\MessageBreak
6230                     MathJax%
6231                 }%
6232             }%
6233             \booltrue{LWR@warnedcustomizemathjax}%
6234         }{}%
6235     }%
6236     \appto{\LWR@customizedMathJax{\LWRbackslash()}}{%
6237         \LWR@subcustomizedmathjax{\#1}%
6238         \appto{\LWR@customizedMathJax{\LWRbackslash}\par}{%
6239     }%
6240 \@onlypreamble\CustomizeMathJax
```

---

\LWR@infoprocessingmathjax {*package name*}

```

6241 \newcommand*{\LWR@infoprocessingmathjax}[1]{%
6242 \typeout{Package lwarf: Processing MathJax customizations for #1.}
6243 \typeout{\space\space This may take a moment.}
6244 }
```

Default customizations:

```

6245 \begin{warpMathJax}
6246 \CustomizeMathJax{\newcommand\ensuremath[1]{#1}}
6247 \CustomizeMathJax{\newcommand\footnote[2][]{\text{( Footnote #1 )}}}
6248 \CustomizeMathJax{\newcommand\footnotemark[1][]{\text{( Footnote #1 )}}}
6249 \CustomizeMathJax{\% absorb two optional arguments
6250   \newcommand{\LWRframebox}[2][]{\fbox{#2}}
6251   \newcommand{\framebox}[1][]{\LWRframebox}
6252 }
6253 \CustomizeMathJax{\newcommand{\setlength}[2]{}}
6254 \CustomizeMathJax{\newcommand{\addtolength}[2]{}}
6255 \CustomizeMathJax{\newcommand{\setcounter}[2]{}}
6256 \CustomizeMathJax{\newcommand{\addtocounter}[2]{}}
6257 \CustomizeMathJax{\newcommand{\cline}[1]{}}
6258 \CustomizeMathJax{\newcommand{\directlua}[1]{\text{(directlua)}}}
6259 \CustomizeMathJax{\newcommand{\luatextdirectlua}[1]{\text{(directlua)}}}
6260 \end{warpMathJax}
```

\LWR@customizeMathJax Prints MathJax commands to the HTML output.

```

6261 \newcommand{\LWR@customizeMathJax}{%
6262 \ifbool{mathjax}{}

6263 \LWR@stoppars
6264 \LWR@htmlcomment{MathJax customizations:}
6265
6266 \typeout{---}
6267 \typeout{Package lwarf:}
6268 \typeout{Processing MathJax customizations. If this takes too long,}
6269 \typeout{see the Lwarf manual regarding customizing MathJax.}
6270 \begin{BlockClass}{hidden}
6271 \LWR@stoppars
6272 \LWR@customizedMathJax
6273 \LWR@startpars
6274 \end{BlockClass}
6275 \typeout{---}
6276
6277 \LWR@startpars
6278 }{}
6279 }

6280 \end{warpHTML}
```

**for PRINT output:** 6281 \begin{warpprint}

\CustomizeMathJax The print-mode version:

```
6282 \newcommand*\CustomizeMathJax[1]{}  
  
\FilenameSimplify * {\expression}  
6283 \NewDocumentCommand{\FilenameSimplify}{s m}{}  
  
6284 \end{warpprint}
```

**for HTML output:** 6285 \begin{warpHTML}

\LWR@newhtmlfile {\section name}

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and css are, then adds navigation, side toc, header, and starts the text body.

```
6286 \newcommand*\LWR@newhtmlfile[1]{  
6287 \LWR@traceinfo{\LWR@newhtmlfile}}
```

At the bottom of the ending file:

```
6288 \LWR@htmlelementclassend{section}{textbody}  
6289 \LWR@htmlelementclassend{div}{bodycontainer}  
6290 \LWR@htmlelementclassend{div}{bodyandsidetoc}  
6291  
6292 \LWR@printpendingfootnotes  
6293
```

No footer between files if EPUB:

```
6294 \ifbool{FormatEPUB}{  
6295 {}  
6296 {  
  
6297     \ifdefempty{\LWR@pagebottom}{%  
6298         \LWR@htmlelement{footer}  
6299     \LWR@pagebottom  
6301         \LWR@htmlelementend{footer}  
6303     }  
6304 }}
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
6305 \ifthenelse{\boolean{FormatEPUB} \OR \boolean{FormatWP}}{  
6306     {}  
6307     {\ifnumcomp{\value{LWR@htmlfilename}}{>}{0}{\LWR@botnavigation}{}}}
```

End of this HTML file:

```
6308 \LWR@stopars
6309 \LWR@htmntag{/body}\LWR@orignewline
6310 \LWR@htmntag{/html}\LWR@orignewline
6311 \LWR@traceinfo{\LWR@newhtmlfile: about to \LWR@orignewline}
6312 \LWR@orignewline
6313
6314 \addtocounter{\LWR@htmlfilenumber}{1}%
```

If using a filename based on section name, create a version without blanks. The filename without blanks will be placed into \LWR@thisfilename. Duplicates will be detected using MD5 hashes.

If not using a filename, the file number will be used instead.

```
6315 \ifbool{FileSectionNames}%
6316 {%
```

Convert the section name to a filename with blanks and common words removed. The resulting filename is in \LWR@thisfilename.

```
6317 \LWR@filenamenoblanks{#1}%
```

Create a macro name from the MD5 hash of the file name, to detect duplicates:

```
6318 \edef\LWR@hashedname{\LWR@mdfive{\LWR@thisfilename}}%
```

If the macro name is not yet defined, this filename is unique.

```
6319 \ifcsundef{\LWR@filename\LWR@hashedname}{%
```

If the filename is unique, create a macro using the hashed name, to be used to test for additional duplicates in the future.

```
6320 \csdef{\LWR@filename\LWR@hashedname}{}%
6321 }{%
```

If the filename is not unique, create an error.

```
6322 \PackageError{lwarp}%
6323   {%
6324     Section name\MessageBreak
6325     ‘‘#1’’,\MessageBreak
6326     at the line number listed below,\MessageBreak
6327     generates the filename\MessageBreak
6328     ‘‘\LWR@thisfilename’’,\MessageBreak
6329     which appears to be a duplicate.\MessageBreak
6330     There is a previous section with an\MessageBreak
6331     identical or similar name%
6332   }%
6333   {%
6334     Lwarp sanitizes most symbols and a few common short words
```

```
6335           when generating file names, and this may cause a conflict.  
6336       }  
6337   }  
6338 }
```

If using file numbers instead of names, the name is set to the next file number.

```
6339 {\renewcommand*{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}
```

Include an HTML comment to instruct lwarfpmk where to split the files apart. Uses pipe-separated fields for `split_html.gawk`. Uses monospaced font with ligatures disabled for everything except the title.

```
6340 \LWR@traceinfo{\LWR@newhtmlfile: about to print start file}%
```

\LWR@nullfonts to allow math in a section name.

```
6341 \begingroup%  
6342 \LWR@nullfonts%  
6343 \LWR@htmlblockcomment{  
6344 |Start file|}  
6345 \LWR@htmlsectionfilename{\LWR@thisfilename}|  
6346 }  
6347 \endgroup%
```

At the top of the starting file:

```
6348 \LWR@stopars  
6349
```

Start a new file with the given section name:

```
6350 \LWR@filestart[#1]  
6351
```

Track the page numbers:

```
6352 \setcounter{\LWR@latestautopage}{\value{page}}%  
6353 \LWR@newautopagelabel{\LWR@latestautopage}%
```

No navigation between files if formatting for an EPUB or word processor:

```
6354 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}  
6355   {}  
6356   {\LWR@topnavigation}  
6357
```

No header if between files if formatting for an EPUB or word processor:

```
6358 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}  
6359   {}  
6360   {
```

```
6361      \ifdefempty{\LWR@pagetop}{}{  
6362          \LWR@htmlelement{header}  
6363  
6364          \LWR@pagetop  
6365  
6366          \LWR@htmlelementend{header}  
6367      }  
6368  }  
6369
```

The container for the sidetoc and text body:

```
6370 \LWR@htmlelementclass{div}{bodyandsidetoc}
```

No sidetoc if formatting for an EPUB or word processor:

```
6371 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}{  
6372     {}  
6373     {\LWR@sidetoc}  
6374 }
```

Start of the <textbody>:

```
6375 \LWR@htmlelementclass{div}{bodycontainer}  
6376 \LWR@htmlelementclass{section}{textbody}  
6377
```

Print title only if there is one. Skip if formatting for an EPUB or word processor:

```
6378 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}{  
6379     {}%  
6380     {  
6381         \ifcvoid{\thetitle}{}{  
6382             \LWR@printthetitle%  
6383         }%  
6384     }%
```

Keep paragraph tags disabled for now:

```
6385 \LWR@stoppars  
6386
```

If using MATHJAX, print the customizations here.

```
6387 \LWR@customizeMathJax
```

```
6388 \LWR@traceinfo{\LWR@newhtmlfile: done}  
6389 }
```

```
6390 \end{warpHTML}
```

## 62 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing L<sup>A</sup>T<sub>E</sub>X code and packages. Formatting is handled by css, so the emulated code has much less work to do than the print versions.

- Unicode** Section names and the resulting filenames with accented characters are partially supported, depending on the ability of *pdflatex* to generate characters and *pdftotext* to read them. If extra symbols appear in the text, it may be that *pdflatex* is actually producing a symbol over or under a character, resulting in *pdftotext* picking up the accent symbol separately.

X<sup>A</sup>L<sup>A</sup>T<sub>E</sub>X and Lua<sup>A</sup>L<sup>A</sup>T<sub>E</sub>X directly support accented section and file names.

**for HTML output:** 6391 \begin{warpHTML}

### 62.1 User-level starred section commands

- \ForceHTMLPage For HTML output, forces the next section to be on its own HTML page, if FileDepth allows, even if starred. For use with \printindex and others which generate a starred section which should be on its own HTML page. Also see \ForceHTMLTOC.

For print output, no effect.

```
6392 \newbool{LWR@forcinghtmlpage}
6393 \boolfalse{LWR@forcinghtmlpage}
6394
6395 \newcommand*{\ForceHTMLPage}{%
6396 \global\booltrue{LWR@forcinghtmlpage}%
6397 }
```

- \ForceHTMLTOC For HTML output, forces the next section to have a TOC entry, even if starred. For use with \printindex and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with tocbibind. Also see \ForceHTMLPage.

For print output, no effect.

```
6398 \newbool{LWR@forcinghtmltoc}
6399 \boolfalse{LWR@forcinghtmltoc}
6400
6401 \newcommand*{\ForceHTMLTOC}{%
6402 \global\booltrue{LWR@forcinghtmltoc}%
6403 }

6404 \end{warpHTML}
```

**for PRINT output:** 6405 \begin{warpprint}
6406 \newcommand\*{\ForceHTMLPage}{}
6407 \newcommand\*{\ForceHTMLTOC}{}
6408 \end{warpprint}

**for HTML output:** 6409 \begin{warpHTML}

## 62.2 Book class commands

\mainmatter Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```
⚠ 6410 \newbool{LWR@mainmatter}
 6411 \DeclareDocumentCommand{\mainmatter}{}{%
 6412 \booltrue{LWR@mainmatter}%
 6413 }
```

\frontmatter Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```
6414 \DeclareDocumentCommand{\frontmatter}{}{%
 6415 \boolfalse{LWR@mainmatter}%
 6416 }
```

\backmatter Declare the back matter section of the document. Does not reset the page number.

```
6417 \DeclareDocumentCommand{\backmatter}{}{%
 6418 \boolfalse{LWR@mainmatter}%
 6419 }
```

## 62.3 Sectioning support macros

\LWR@sectionnumber {\<section type>}

Typeset a section number and its trailing space with css formatting:

```
6420 \newcommand*{\LWR@sectionnumber}[1]{%
 6421 \InlineClass{sectionnumber}{#1}%
 6422 }
```

autosec A tag used by the toc and index.

\LWR@createautosec {\<section type>}

Create an autosection tag.

```
6423 \newcommand*{\LWR@createautosec}[1]{%
 6424 \LWR@htmntag{%
 6425     #1 % space
 6426     id=\textquotedbl\LWR@print@mbox{autosec-\arabic{page}}\textquotedbl%
 6427 }%
 6428 }
```

\LWR@pushoneclose {*<sectiontype>*} Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

⚠ \LWR@stoppars must be executed first.

```
6429 \NewDocumentCommand{\LWR@pushoneclose}{m}{%
6430 \LWR@traceinfo{\LWR@pushoneclose #1}%
6431     \LWR@pushclose{#1}%
6432 }
```

\LWR@startnewdepth {*<sectiontype>*}

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

⚠ \LWR@stoppars must be executed first.

```
6433 \NewDocumentCommand{\LWR@startnewdepth}{m}{%
```

Close any stacked sections up to this new one.

```
6434 \LWR@closeprevious{#1}%
```

Push a new section depth:

```
6435 \LWR@pushoneclose{#1}%
6436 }
```

Ctr \LWR@prevFileDepth Remembers the previous LWR@FileDepth.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
6437 \newcounter{\LWR@prevFileDepth}
6438 \setcounter{\LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

\@seccntformat {*<sectiontype>*}

```
6439 \def\@seccntformat#1{\csname the#1\endcsname\quad}
```

\simplechapterdelim Used by tocbibind and anonchap.

```
6440 \newcommand*\simplechapterdelim{}
```

\@chapcntformat {*<sectiontype>*}

\let to \@seccntformat by default, but may be redefined by \simplechapter and \restorechapter from tocbibind or anonchap.

```
6441 \let\@chapcntformat\@seccntformat
```

---

\@partcntformat {*<sectiontype>*}

\let to \@secntformat by default, but may be redefined by ctex.

6442 \let\@partcntformat\@secntformat

\@partnameformat Prints “Part” for part sections.

Nullified by ctex.

6443 \newcommand\*{\@partnameformat}{\LWR@isolate{\partname}~}%

Ctr LWR@currentautosec Records the page number when the section was created. If a math expression is included in the section name, and SVG math is used, the corresponding `lateximage` will cause the page number to change by the time the following autosec label is created.

6444 \newcounter{LWR@currentautosec}  
6445 \setcounter{LWR@currentautosec}{1}

\LWR@section \* [*<TOC name>*] {*<name>*} {*<sectiontype>*}

The common actions for the high-level sectioning commands.

6446 \DeclareDocumentCommand{\LWR@section}{m m m m}{%  
6447 \IfValueTF{#2}{%  
6448 {\LWR@traceinfo{LWR@section: starting #4 #2}}%  
6449 {\LWR@traceinfo{LWR@section: starting #4 #3}}%  
6450 \LWR@maybeprintpendingfootnotes{\csuse{LWR@depth#4}}%  
6451 \LWR@stoppars%  
6452 \LWR@startnewdepth{#4}%

Cancel special `minipage` horizontal space interaction:

6453 \global\boolfalse{LWR@minipagethispar}%

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for `\part*`, for `appendix`.

Generate a new LATEX page so that TOC and index page number points to the section:

6454 \LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%  
6455 \IfBooleanT{#1}{\LWR@traceinfo{LWR@section: starred}}%  
6456 \ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}}{}%  
6457 \ifthenelse{  
6458 \(%  
6459 \\\NOT\equal{#1}{\BooleanTrue}\)\OR%  
6460 \\\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)\OR%  
6461 \\\boolean{LWR@forcinghtmlpage}\)%  
6462 \)%  
6463 \AND%

```

6464      \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{FileDepth}}%
6465      \AND%
6466      \(%
6467          \NOT\boolean{CombineHigherDepths}\OR%
6468          \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}%
6469      \)%
6470      \AND%

6471      \(% phantomsection
6472          \NOT\isempty{#3}%
6473          \OR%
6474          \(\NOT\equal{#1}{\BooleanTrue}\)%
6475      \)%
6476 }%

```

If so: start a new HTML file:

```

6477 {%
6478     \LWR@traceinfo{LWR@section: new HTML file}%

```

See if there was an optional TOC name entry:

```

6479     \IfNoValueTF{#2}%

```

If no optional entry

```

6480     {\LWR@newhtmlfile{#3}}%

```

If yes an optional entry

```

6481     {\LWR@newhtmlfile{#2}}%
6482 }% new file

```

Else: No new HTML file:

```

6483 {%

```

Generate a new L<sup>A</sup>T<sub>E</sub>X page so that TOC and index page number points to the section:

```

6484     \LWR@traceinfo{LWR@section: not a new HTML file, about to LWR@orignewpage}%
6485     \LWR@orignewpage%
6486 }% not new file
6487

```

Remember this section's name for \nameref:

```

6488 \IfValueT{#3}{%
6489     \LWR@traceinfo{LWR@section: about to LWR@setlatestname}%
6490     \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
6491 }%

```

Print an opening comment with the level and the name; ex: "section" "Introduction"  
Footnotes may be used in section names, which would also appear in the HTML section

opening comments, so the short TOC entry is used if possible, and a limited opening comment is made if the sectional unit is starred.

```

6492 \ifbool{HTMLDebugComments}{%
6493     \begingroup%
6494     \LWR@nullfonts%
6495     \IfBooleanTF{#1}{% starred
6496         {\LWR@htmlcomment{Opening #4*}}%
6497     }{%
6498         \IfNoValueTF{#2}{% short TOC
6499             {\LWR@htmlcomment{Opening #4 ``#3''}}%
6500             {\LWR@htmlcomment{Opening #4 ``#2''}}%
6501         }\LWR@newline%
6502     \endgroup%
6503 }{}}
```

For inline sections paragraph and subparagraph, start a new paragraph now:

```

6504 \ifthenelse{%
6505     \cnttest{@nameuse{\LWR@depth#4}}{>=}{\LWR@depthparagraph}%
6506 }{%
6507     {\LWR@startpars}%
6508 }{}
```

Create the opening tag with an autosec:

```

6509 \LWR@traceinfo{\LWR@section: about to \LWR@createautosec}%
6510 \LWR@createautosec{@nameuse{\LWR@tag#4}}%

6511 \setcounter{\LWR@currentautosec}{\value{page}}%
```

Check if starred:

```

6512 \IfBooleanTF{#1}{%
6513 }{%
6514     \LWR@traceinfo{\LWR@section: starred}%
}
```

Starred, but also forcing a TOC entry, so add unnumbered TOC name or regular name:

```

6515 \ifbool{\LWR@forcinghtmltoc}{%
6516 }{%
6517     \addcontentsline{toc}{#4}{%
6518         \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
6519     }%
6520 }{%
6521 }{%
6522 }% starred
```

Not starred, so step counter and add to TOC:

```
6523 { not starred
```

Only add a numbered TOC entry if section number is not too deep:

```

6524     \ifthenelse{%
6525         \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}}{%
6526     }%
6527     {%
6528         \if LWR@traceinfo{LWR@section: about to test main matter}%
6529             \ifbool{LWR@mainmatter}%
6530             {%
6531                 \LWR@traceinfo{LWR@section: yes mainmatter}%
6532                 \refstepcounter{#4}%
6533             }%
6534             \addcontentsline{toc}{#4}%
6535             {%
6536                 \protect\numberline{%
6537                     \@nameuse{pre#4name}}%
6538                     \@nameuse{the#4}%
6539                     \@nameuse{post#4name}}%
6540             }%
6541             {%
6542                 \ignorespaces%
6543                 \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
6544             }%
6545         }%
6546         \LWR@traceinfo{LWR@section: finished addcontentsline}%
6547     }%
6548     {%
6549         \LWR@traceinfo{LWR@section: no main matter}%
6550         \addcontentsline{toc}{#4}{%
6551             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
6552         }%
6553     }%
6554 }%

```

If in the main matter, step the counter and add the TOC entry. For article class, lwarp assumes that all is mainmatter.

```

6528             \LWR@traceinfo{LWR@section: about to test main matter}%
6529             \ifbool{LWR@mainmatter}%
6530             {%
6531                 \LWR@traceinfo{LWR@section: yes mainmatter}%
6532                 \refstepcounter{#4}%
6533             }%
6534             \addcontentsline{toc}{#4}%
6535             {%
6536                 \protect\numberline{%
6537                     \@nameuse{pre#4name}}%
6538                     \@nameuse{the#4}%
6539                     \@nameuse{post#4name}}%
6540             }%
6541             {%
6542                 \ignorespaces%
6543                 \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
6544             }%
6545         }%
6546         \LWR@traceinfo{LWR@section: finished addcontentsline}%
6547     }%
6548     {%
6549         \LWR@traceinfo{LWR@section: no main matter}%
6550         \addcontentsline{toc}{#4}{%
6551             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
6552         }%
6553     }%
6554 }%

```

Add main matter numbered TOC entry with the TOC name or the regular name:

```

6533             \LWR@traceinfo{LWR@section: about to addcontentsline}%
6534             \addcontentsline{toc}{#4}%
6535             {%
6536                 \protect\numberline{%
6537                     \@nameuse{pre#4name}}%
6538                     \@nameuse{the#4}%
6539                     \@nameuse{post#4name}}%
6540             }%
6541             {%
6542                 \ignorespaces%
6543                 \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
6544             }%
6545         }%
6546         \LWR@traceinfo{LWR@section: finished addcontentsline}%
6547     }%
6548     {%
6549         \LWR@traceinfo{LWR@section: no main matter}%
6550         \addcontentsline{toc}{#4}{%
6551             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
6552         }%
6553     }%
6554 }%

```

If not main matter, add unnumbered TOC name or regular name:

```

6548     {%
6549         \LWR@traceinfo{LWR@section: no main matter}%
6550         \addcontentsline{toc}{#4}{%
6551             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
6552         }%
6553     }%
6554 }%

```

Deeper than secnumdepth, so add an unnumbered TOC entry:

```

6555     {%
6556         \addcontentsline{toc}{#4}{%
6557             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
6558         }%
6559     }%

```

For part, print “Part”:

```

6560     \ifbool{LWR@mainmatter}%
6561     {%
6562         \LWR@traceinfo{LWR@section: about to test main matter}%
6563         \ifbool{LWR@mainmatter}%
6564         {%
6565             \LWR@traceinfo{LWR@section: yes mainmatter}%
6566             \refstepcounter{#4}%
6567             \addcontentsline{toc}{#4}{%
6568                 \protect\numberline{%
6569                     \@nameuse{pre#4name}}%
6570                     \@nameuse{the#4}%
6571                     \@nameuse{post#4name}}%
6572             }%
6573             {%
6574                 \ignorespaces%
6575                 \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
6576             }%
6577         }%
6578         \LWR@traceinfo{LWR@section: finished addcontentsline}%
6579     }%
6580     {%
6581         \LWR@traceinfo{LWR@section: no main matter}%
6582         \addcontentsline{toc}{#4}{%
6583             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
6584         }%
6585     }%
6586 }%

```

---

```

6562      \ifthenelse{%
6563          \(\cnttest{\@nameuse{LWR@depth#4}}\{<=\}%
6564          {\value{secnumdepth}}\)} \AND%
6565          \(\cnttest{\@nameuse{LWR@depth#4}}\{=\}{\LWR@depthpart}\)%
6566      }%
6567          {\@partnameformat}%
6568      {}%

```

Print the section number:

```

6569      \LWR@traceinfo{LWR@section: about to print section number}%
6570      \ifthenelse{%
6571          \cnttest{\@nameuse{LWR@depth#4}}\{<=\}{\value{secnumdepth}}%
6572      }%
6573      {}%
6574          \ifstreq{\#4}{part}%
6575          {\protect\LWR@sectionnumber{\@partcntformat{\#4}}}%
6576          {}%
6577          \ifstreq{\#4}{chapter}%
6578              {\protect\LWR@sectionnumber{\@chapcntformat{\#4}}}%
6579              {\protect\LWR@sectionnumber{\@seccntformat{\#4}}}%
6580          }%
6581      }%
6582      {}%
6583      \LWR@traceinfo{LWR@section: finished print section number}%
6584  }{}%
6585 }% end of not starred

```

Print the section name:

```

6586 \LWR@traceinfo{LWR@section: about to print the section name}%
6587 \LWR@isolate{\#3}%

```

Close the heading tag, such as /H2:

```

6588 \LWR@traceinfo{LWR@section: about to close the heading tag}%
6589 \LWR@htmlltag{\@nameuse{LWR@tag#4end}}%
6590 \LWR@orignewline%

```

Generate a L<sup>A</sup>T<sub>E</sub>X label:

```

6591 \LWR@traceinfo{LWR@section: about to create the LaTeX label}%
6592 \setcounter{LWR@latestautopage}{\value{page}}%
6593 \LWR@newautopagelabel{LWR@currentautosec}\LWR@orignewline%

```

Start paragraph handing unless is an inline paragraph or subparagraph:

```

6594 \ifthenelse{%
6595     \cnttest{\@nameuse{LWR@depth#4}}\{<\}{\LWR@depthparagraph}%
6596 }%
6597     {\LWR@startpars}%
6598     {}%

```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a `\part*` to start a new HTML page. This is used by `appendix`.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a `\listoftables` was tested in the middle of the document. The `\chapter*` for the list was not allowing a new HTML page for the section following it while `CombineHigherDepths` was true.

```
6599 \ifthenelse{%
6600   \NOT\equal{\#1}{\BooleanTrue}\OR%
6601   \cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}%
6602 }%
6603   {%
6604     \setcounter{LWR@prevFileDepth}{\@nameuse{LWR@depth#4}}%
6605   }%
6606 }
```

Reset to defaults if not a phantomsection:

```
6607 \ifstrempty{\#3}%
6608   {}%
6609   {%
6610     \global\boolfalse{LWR@forcinghtmlpage}%
6611     \global\boolfalse{LWR@forcinghtmltoc}%
6612   }%
6613 %
6614 \LWR@traceinfo{LWR@section: done}%
6615 }
```

## 62.4 Pre- and post- sectioning names

`\prebookname` Usually null, but is used by `uj*` and `ut*` Japanese classes.

`\postbookname`

```
6616 \providecommand*{\prebookname}{}%
6617 \providecommand*{\postbookname}{}%
```

`\prepartname` Usually null, but is used by `uj*` and `ut*` Japanese classes.

`\postpartname`

```
6618 \providecommand*{\prepartname}{}%
6619 \providecommand*{\postpartname}{}%
```

`\prechaptername` Usually null, but is used by `uj*` and `ut*` Japanese classes.

`\postchaptername`

```
6620 \providecommand*{\prechaptername}{}%
6621 \providecommand*{\postchaptername}{}%
```

`\presectionname` Always null, but provided here for algorithmic simplicity in `\LWR@section`.

`\postsectionname`

```
6622 \providecommand*{\presectionname}{}%
6623 \let\postsectionname\presectionname%
6624
```

```
6625 \let\presubsectionname\presectionname
6626 \let\postsubsectionname\postsectionname
6627
6628 \let\presubsubsectionname\presectionname
6629 \let\postsubsubsectionname\postsectionname
6630
6631 \let\preparagraphname\presectionname
6632 \let\postparagraphname\postsectionname
6633
6634 \let\presubparagraphname\presectionname
6635 \let\postsubparagraphname\postsectionname
```

## 62.5 \section and friends

For `memoir`, a second optional argument is allowed.

For `hypbmsec`, a second optional argument or either parenthesis argument is allowed.

Each of these additional arguments are for headers or PDF bookmarks, and are ignored for HTML output.

```
\part * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {<6:name>}
6636 \newcommand{\part@preamble}{}% for koma-script
6637
6638 \DeclareDocumentCommand{\part}{s d() o o d() m}%
6639     \LWR@section{#1}{#3}{#6}{part}%
6640
6641     \part@preamble% for koma-script
6642     \renewcommand{\part@preamble}{}%
6643 }

\chapter * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {<6:name>}
6644 \let@\printcites\relax% for quotchap package
6645
6646 \newcommand{\chapter@preamble}{}% for koma-script
6647
6648 \@ifundefined{chapter}
6649 {}
6650 %
6651     \DeclareDocumentCommand{\chapter}{s d() o o d() m}%
6652         \LWR@section{#1}{#3}{#6}{chapter}%
6653
6654     \printcites% for quotchap package
6655
6656     \chapter@preamble% for koma-script
6657     \renewcommand{\chapter@preamble}{}%
6658 }
6659 }
```

```

\section * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {<6:name>}

6660 \DeclareDocumentCommand{\section}{s d() o o d() m}{%
6661     \LWR@section{#1}{#3}{#6}{section}%
6662 }

\subsection * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {<6:name>}

6663 \DeclareDocumentCommand{\subsection}{s d() o o d() m}{%
6664     \LWR@section{#1}{#3}{#6}{subsection}%
6665 }

\subsubsection * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {<6:name>}

6666 \DeclareDocumentCommand{\subsubsection}{s d() o o d() m}{%
6667     \LWR@section{#1}{#3}{#6}{subsubsection}%
6668 }

\paragraph * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {<6:name>}

6669 \DeclareDocumentCommand{\paragraph}{s d() o o d() m}{%
6670     \LWR@section{#1}{#3}{#6}{paragraph}%
6671 }

\ subparagraph * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {<6:name>}

6672 \DeclareDocumentCommand{\ subparagraph}{s d() o o d() m}{%
6673     \LWR@section{#1}{#3}{#6}{subparagraph}%
6674 }

6675 \end{warpHTML}

```

## 63 Starting a new file

**for HTML & PRINT:** 6676 \begin{warpall}

\HTMLLanguage Default language for the HTML lang tag.

```

6677 \newcommand*{\LWR@currentHTMLLanguage}{en-US}
6678
6679 \newcommand*{\HTMLLanguage}[1]{%
6680 \renewcommand*{\LWR@currentHTMLLanguage}{#1}%
6681 }

```

\theHTMLTitleSeparator May be used inside \theHTMLTitleSection to separate the website's overall HTML title and the particular page's section name.

---

```

6682 \ifPDFTeX% pdflatex or dvi latex
6683   \ifdefstring{\inputencodingname}{utf8}{%
6684     \newcommand*{\theHTMLTitleSeparator}{ - }% EMdash
6685   }{%
6686     \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
6687   }%
6688 \else%
6689   \ifpTeX%
6690     \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
6691   \else%
6692     \newcommand*{\theHTMLTitleSeparator}{ - }% EMdash
6693   \fi%
6694 \fi%

```

**\HTMLTitleBeforeSection** Sets the **HTML** page's meta title tag to show the website title before the section name.

```

6695 \newcommand*{\HTMLTitleBeforeSection}{%
6696   \def\theHTMLTitleSection{%
6697     \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
6698   }%
6699 }

```

**\HTMLTitleAfterSection** Sets the **HTML** page's meta title tag to show the section name before the website title.

```

6700 \newcommand*{\HTMLTitleAfterSection}{%
6701   \def\theHTMLTitleSection{%
6702     \theHTMLSection\theHTMLTitleSeparator\theHTMLTitle%
6703   }%
6704 }

```

**\theHTMLTitleSection** Forms the **HTML** page's meta title tag. The default is to show the website title before the section name.

```
6705 \HTMLTitleBeforeSection
```

**\theHTMLSection** The section name is passed to **\LWR@filestart**, which then sets **\theHTMLSection** for use inside **\theHTMLTitleSection** to create an **HTML** meta title tag.

```

6706 \newcommand*{\theHTMLSection}{}%
6707 \end{warpall}

```

**for HTML output:** 6708 \begin{warpHTML}

**\LWR@filestart** [*<sectionname>*] Creates the opening **HTML** tags.

```

6709 \newcommand*{\LWR@filestart}[1][]{%
6710 \LWR@traceinfo{\LWR@filestart !#1!}%

```

Locally temporarily disable direct-formatting commands:

```
6711 \begingroup%
6712 \LWR@nullfonts%
```

Save the section name for use while creating the **HTML meta title** tag:

```
6713 \edef\theHTMLSection{\#1}%
```

Create the page's **HTML header**:

```
6714 \LWR@htmltag{!DOCTYPE html}\LWR@orignewline
```

The language is user-adjustable:

```
6715 \LWR@htmltag{%
6716   html lang=\LWR@orig@textquotedbl\LWR@currentHTMLLanguage\LWR@orig@textquotedbl%
6717 }\LWR@orignewline
```

Start of the meta data:

```
6718 \LWR@htmltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
6719 \LWR@htmltag{%
6720   meta charset=\LWR@orig@textquotedbl{}UTF-8\LWR@orig@textquotedbl\ /%
6721 }\LWR@orignewline
```

Author:

```
6722 \ifthenelse{\equal{\theHTMLAuthor}{}}{%
6723   {}%
6724   {%
6725     \LWR@htmltag{%
6726       meta name=\LWR@orig@textquotedbl{}author\LWR@orig@textquotedbl\ % space
6727       content=\LWR@orig@textquotedbl{}\theHTMLAuthor\LWR@orig@textquotedbl\ /%
6728     }\LWR@orignewline%
6729   }%
```

**lwarp** is the generator:

```
6730 \LWR@htmltag{%
6731   meta % space
6732   name=\LWR@orig@textquotedbl{}generator\LWR@orig@textquotedbl\ % space
6733   content=\LWR@orig@textquotedbl{}LaTeX Lwarp package\LWR@orig@textquotedbl\ /%
6734 }\LWR@orignewline%
```

If there is a description, add it now:

```
6735 \ifdefempty{\LWR@currentHTMLDescription}{%
6736   \LWR@htmltag{%
6737     meta name=\LWR@orig@textquotedbl{}description\LWR@orig@textquotedbl\ % space
6738     content=\LWR@orig@textquotedbl{}\LWR@currentHTMLDescription\LWR@orig@textquotedbl\ /%
6739   }\LWR@orignewline%
6740 }%
```

Mobile-friendly viewport:

```
6741 \LWR@htmltag{%
6742     meta % space
6743     name=\LWR@orig@textquotedbl{}viewport\LWR@orig@textquotedbl\ % space
6744     content=\LWR@orig@textquotedbl{}width=device-width, initial-scale=1.0\LWR@orig@textquotedbl\ /%
6745 }\LWR@orignewline
```

IE patch:

```
6746 \LWR@htmltag{!-/-[if lt IE 9]}\LWR@orignewline
6747 \LWR@htmltag{%
6748     script % space
6749     src=\LWR@orig@textquotedbl{}%
6750         http://html5shiv.googlecode.com/svn/trunk/html5.js%
6751     \LWR@orig@textquotedbl%
6752 }%
6753 \LWR@htmltag{/script}\LWR@orignewline
6754 \LWR@htmltag{![endif]-/-}\LWR@orignewline
```

The page's title, if there is one. A section name is also added if given.

```
6755 \ifthenelse{\equal{\theHTMLTitle}{}}{%
6756     {}%
6757     {%
6758         \LWR@htmltag{title}%
6759         \ifempty{\theHTMLSection}{%
6760             {\theHTMLTitle}%
6761             {\theHTMLTitleSection}%
6762         \LWR@htmltag{/title}\LWR@orignewline%
6763     }%
```

The page's stylesheet:

```
6764 \LWR@htmltag{%
6765     link % space
6766     rel=\LWR@orig@textquotedbl{}stylesheet\LWR@orig@textquotedbl\ % space
6767     type=\LWR@orig@textquotedbl{}text/css\LWR@orig@textquotedbl\ % space
6768     href=\LWR@orig@textquotedbl{}\LWR@currentcss\LWR@orig@textquotedbl\ /%
6769 }%
6770 \LWR@orignewline
```

Optional MATHJAX support. The HTML tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```
6771 \ifbool{mathjax}{%
6772 {%
6773     \begingroup%
6774     \LWR@restoreoriglists%
6775     \boolfalse{\LWR@verbtags}%
6776     \verbatiminput{\LWR@mathjaxfilename}%
6777 }
```

---

```

6777 \booltrue{\LWR@verbtags}%
6778 \endgroup%
6779 \LWR@stopars%
6780 }% end of mathjax
6781 {}%

```

End of the header:

```
6782 \LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```

6783 \LWR@htmltag{body}\LWR@orignewline
6784 \endgroup
6785 \LWR@traceinfo{\LWR@filestart: done}
6786 }%

```

```
6787 \end{warpHTML}
```

## 64 Starting HTML output

**for HTML output:** 6788 \begin{warpHTML}

\LWR@LwarpStart Executed at the beginning of the entire document.

The use of \textquotedbl instead of " improves compatibility with xeCJK.

```

6789 \catcode`\$=\active
6790 \newcommand*{\LWR@LwarpStart}{%
6791 {}%
6792 \LWR@traceinfo{\LWR@l warpStart}}

```

If formatting for a word processor, force filedepth to single-file only, force HTML debug comments off.

```

6793 \ifbool{FormatWP}{%
6794   \setcounter{FileDepth}{-5}%
6795   \boolfalse{HTMLDebugComments}%
6796 }{}%

```

Expand and detokenize \HomeHTMLFilename and \HTMLFilename:

```

6797 \edef\LWR@strresult{\HomeHTMLFilename}
6798 \edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
6799 \edef\LWR@strresult{\HTMLFilename}
6800 \edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}

```

Force onecolumn and empty page style:

```

6801 \LWR@origonecolumn%
6802 \LWR@origpagestyle{empty}%

```

No black box for overfull lines:

```
6803 \overfullrule=0pt
```

Reduce chance of line overflow when **HTML** tags are added:

```
6804 \LWR@print@footnotesize%
```

In **PDF** output, don't allow line breaks to interfere with **HTML** tags:

```
6805 \LWR@print@raggedright%
6806 \LetLtxMacro{\LWR@endofline}{}
```

Spread the lines for *pdftotext* to read them well:

```
6807 \linespread{1.3}%
```

For *pdftotext* to reliably identify paragraph splits:

```
6808 \setlength{\parindent}{0pt}
6809 \setlength{\parskip}{2ex}
```

For the **lateximage** record file:

```
6810 \immediate\openout\LWR@lateximagesfile=\BaseJobname-images.txt
```

Removes space around the caption in the **HTML**:

```
6811 \setlength{\belowcaptionskip}{0ex}
6812 \setlength{\abovecaptionskip}{0ex}
```

Redefine the plain page style to be empty when used by index pages:

```
6813 \renewcommand{\ps@plain}{}%
```

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Float captions:

```
6814 \let\LWR@origcaption\caption
```

Labels: `\ltx@label` is used in **amsmath** environments and is also patched by **cleveref**.

## Label in **HTML**

```
6815 \let\LWR@origltx@label\ltx@label
6816 \let\ltx@label\LWR@htmlmathlabel
```

Not yet started any paragraph handling:

```
6817 \global\boolfalse{\LWR@doingapar}
6818 \global\boolfalse{\LWR@doingstartpars}
```

Document and page settings:

```
6819 \mainmatter
6820 \LWR@origpagenumbering{arabic}
```

Start a new HTML file and a header:

```
6821 \LWR@traceinfo{\LWR@lwarpStart: Starting new file.}
6822 \LWR@filestart
6823 \LWR@traceinfo{\LWR@lwarpStart: Generating first header.}
```

```
6824 \ifdefempty{\LWR@firstpagetop}{}{%
6825   \LWR@htmlltag{header}\LWR@orignewline
6826   \LWR@startpars
6827   \LWR@firstpagetop
6828   \LWR@stoppars
6829   \LWR@htmlltag{/header}\LWR@orignewline
6830 }%
```

```
6831 \LWR@htmlelementclass{div}{bodywithoutsidetoc}
6832 \LWR@htmlelementclass{div}{bodycontainer}
6833 \LWR@traceinfo{\LWR@lwarpStart: Generating textbody.}
6834 \LWR@htmlelementclass{section}{textbody}
```

Patch the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native L<sup>A</sup>T<sub>E</sub>X environments, as well as those provided by `enumitem`, `enumerate`, and `paralist`.

```
6835 \LWR@patchlists
```

Ensure that math mode is active to call `lwarp`'s patches:

```
6836 \catcode`\$=\active
```

Required for `\nameref` to work with SVG math:

```
6837 \immediate\write\@mainaux{\catcode`\$=\active}%
6838 \LetLtxMacro{\LWR@syntaxhighlightone$}{% balance for editor syntax highlighting}
```

Allow HTML paragraphs to begin:

```
6839 \LWR@startpars
```

If using MATHJAX, disable `\ensuremath` by printing a nullified definition at the start of each file, and add further customizations:

```
6840 \LWR@customizeMathJax
```

First autopage label in case a figure occurs early.

```
6841 \setcounter{\LWR@latestautopage}{\value{page}}%
6842 \LWR@newautopagelabel{\LWR@currentautosec}%
```

---

```

6843 \LWR@traceinfo{\LWR@lwarpStart: done}
6844 }
6845 \catcode`\$=3% math shift until lwarp starts

6846 \end{warpHTML}

```

## 65 Ending HTML output

**for HTML output:** 6847 \begin{warpHTML}

\LWR@requesttoc {<boolean>} {<suffix>} Requests that a TOC, LOF, or LORbe generated.

```

6848 \newcommand*{\LWR@requesttoc}[2]{%
6849 \ifbooleq{#1}{%
6850 {%
6851     \expandafter\newwrite\@nameuse{tf@#2}%
6852     \immediate\openout \jobname.\#2\relax
6853 }{}%
6854 }

```

\LWR@LwarpEnd Final stop of all HTML output:

```

6855 \newcommand*{\LWR@LwarpEnd}{%
6856 {%
6857 \LWR@stopars
6858 \LWR@closeprevious{finished}

```

At the bottom of the ending file:

Close the textbody:

```

6859 \LWR@htmlelementclassend{section}{textbody}
6860 \LWR@htmlelementclassend{div}{bodycontainer}
6861 \LWR@htmlelementclassend{div}{bodyandsidetoc}

```

Print any pending footnotes:

```
6862 \LWR@printpendingfootnotes
```

Create the footer:

```

6863 \ifempty{\LWR@pagebottom}{}{%
6864     \LWR@htmlelement{footer}
6865
6866     \LWR@pagebottom
6867
6868     \LWR@htmlelementend{footer}
6869 }

```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```

6870 \ifthenelse{\boolean{FormatEPUB} \OR \boolean{FormatWP}}
6871   {}
6872   {
6873     \ifnumcomp{\value{LWR@htmlfilename}}{>}{0}{\LWR@botnavigation}{}
6874   }
6875 \LWR@stopars% final stop of all paragraphs

```

Finish the HTML file:

```

6876 \LWR@htmllag{/body}\LWR@orignewline
6877 \LWR@htmllag{/html}\LWR@orignewline

```

Seems to be required sometimes:

```

6878 \LWR@orignewline
6879 }

```

\enddocument If labels have not changed, mark successful completion of the `lateximages` file. Executed as everything is being shut down.

```

6880 \xpatchcmd{\enddocument}
6881   {%
6882     \if@tempswa
6883       \@latex@warning@no@line{Label(s) may have changed.
6884       Rerun to get cross-references right}%
6885     \fi
6886   }
6887   {%
6888     \if@tempswa
6889       \@latex@warning@no@line{Label(s) may have changed.
6890       Rerun to get cross-references right}%
6891     \else
6892       \immediate\write\LWR@lateximagesfile{%
6893         |end|end|end|%
6894       }%
6895     \fi
6896   }
6897   {}
6898   {
6899     \PackageWarningNoLine{lwarp}
6900     {%
6901       Could not patch \protect\enddocument.\MessageBreak
6902       If labels have changed, be sure to recompile before\MessageBreak
6903       creating lateximages with\MessageBreak
6904       \space\space lwarpmk limages,\MessageBreak
6905       or the images may be corrupt%
6906     }%
6907   }

```

---

6908 \end{warpHTML}

## 66 Title page

**package support** lwarp supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages `authblk` and `titling`. If both are used, `authblk` should be loaded before `titling`.

**\published and \subtitle** If using the `titling` package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 66.8.

**affiliation** lwarp provides for the `\author` macro an additional `\affiliation` macro to provide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using `titlingpage`'s `\theauthor` in the main text.

**reusing titlepage information** The `titling` package maintains the definitions of `\thetitle`, `\theauthor`, etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the `\thanks` and `\affiliation` removed, and for `\author` the `\and` is replaced to generate a simple inline list of authors separated by commas. Note: `\theauthor` does not work well with `authblk` unless the traditional L<sup>A</sup>T<sub>E</sub>X syntax is used.

**⚠ \theauthor, authblk**

**custom titlepages** `\printtitle`, `\printauthor`, etc., are provided for use inside a custom `titlepage` or `titlingpage` environment, and these retain the `\thanks` and `\affiliation`.

**\printthanks** `\printthanks` has been added to force the printing of thanks inside a `titlingpage` environment when `\maketitle` is not used.

**⚠ \thanks**

Inside a `\titlepage` or `\titlingpage` environment, use `\thanks` instead of `\footnote` for acknowledgements, etc.

### 66.1 Setting the title, etc.

The following provide setting commands for both HTML and print outputs.

**\author** {*<author>*} While using `\maketitle` and print mode, the author is treated as a single-column tabular and the `\and` feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as

```
\author{Name \\ Affiliation \and Second Name \\ Second Affiliation}
```

For HTML, the entire author block is placed inside a `<div>` of class `author`, and each individual author is inside a `<div>` of class `oneauthor`.

**\@title** `\@title`, `\@author`, and `\@date` store the values as originally assigned, including any `\thanks`, `\and`, or `\affiliation`. These are low-level macros intended to be used by other macros only inside a `titlepage` or `titlingpage`, and are used by `\maketitle`. The author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For HTML, these tabulars become

side-by-side `<div>`s of class `oneauthor`, all of which are combined into one `<div>` of class `author`.

<code>\printtitle</code>	<code>\printtitle</code> , etc. are user-level macros intended to be used in custom <code>titlepage</code> or <code>titlingpage</code> environments in cases where <code>\maketitle</code> is not desired. These commands preserve the <code>\thanks</code> , etc., and should not be used in the main text.
<code>\printauthor</code>	
<code>\printdate</code>	
<code>\thetitle</code>	<code>\thetitle</code> , <code>\theauthor</code> , and <code>\thedate</code> are available if <code>titling</code> has been loaded, and are sanitized user-level versions from which have been removed the <code>\thanks</code> and <code>\affiliation</code> , and <code>\and</code> is changed for inline text usage. The author is printed inline without <code>\affiliation</code> or <code>\thanks</code> , with <code>\and</code> placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each HTML page, such as:
<code>\HTMLPageBottom</code>	

```
\HTMLPageBottom{
  \begin{center}\textcopyright~20xx \theauthor\end{center}
}
```

⚠ `\theauthor`, `authblk` `\theauthor` does not work well if `authblk` is used. If `\theauthor` is important, it is recommended to use the standard L<sup>A</sup>T<sub>E</sub>X syntax for `\author`, optionally with `lwarp`'s `\affiliation` macro as well.

⚠ `affiliations` After `\maketitle` has completed, `\theauthor` retains the definition of the author, but `\and` is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

`\affiliation` A solution, provide here, is to define a macro `\affiliation` which, during `\maketitle`, starts a new row and adds the affiliation, but after `\maketitle` is finished `\affiliation` is re-defined to discard its argument, thus printing only the author names when `\author` is later used inline.

## 66.2 `\if@titlepage`

**for HTML & PRINT:** 6909 `\begin{warpall}`

`\if@titlepage` Some classes do not provide `\if@titlepage`. In this case, provide it and force it false.

```
6910 \ifcsvoid{@titlepagefalse}{
6911   \newif\if@titlepage
6912   \if@titlepagefalse
6913 {}}
6914 \end{warpall}
```

## 66.3 Changes for `\affiliation`

`\affiliation` `{<text>}`

Adds the affiliation to the author for use in \maketitle.

Inside titlepage, this macro prints its argument. Outside, it is null.

**for HTML & PRINT:** 6915 \begin{warpall}  
 6916 \providerobustcmd{\affiliation}[1]{  
 6917 \end{warpall}}

**for PRINT output:** 6918 \begin{warpprint}  
  
 6919 \AtBeginEnvironment{titlepage}{  
 6920 \renewrobustcmd{\affiliation}[1]{\textsc{\small#1}}}  
 6921 }  
 6922  
 6923 \AtBeginDocument{  
 6924 \@ifpackageloaded{titling}{  
 6925 \AtBeginEnvironment{titlingpage}{  
 6926 \renewrobustcmd{\affiliation}[1]{\textsc{\small#1}}}  
 6927 }  
 6928 }% titling loaded  
 6929 }% AtBeginDocument  
  
 6930 \end{warpprint}

**for HTML output:** 6931 \begin{warpHTML}

**Env titlepage** Sets up a <div> of class titlepage. Provided even for memoir class, since it is used by \maketitle.

6932 \DeclareDocumentEnvironment{titlepage}{}  
 6933 {  
 6934 \renewrobustcmd{\affiliation}[1]{\InlineClass{affiliation}{##1}}  
 6935 \LWR@printpendingfootnotes  
 6936 \LWR@forcenewpage  
 6937 \BlockClass{titlepage}  
 6938 }  
 6939 {  
 6940 \endBlockClass  
 6941 \LWR@printpendingfootnotes  
 6942 }  
  
 6943 \end{warpHTML}

## 66.4 Printing the thanks

**for HTML & PRINT:** 6944 \begin{warpall}

\printthanks Forces the \thanks to be printed.

This is necessary in a titlingpage environment when \maketitle was not used.

6945 \newcommand\*{\printthanks}{\LWR@stopars\@thanks\LWR@startpars}

```
6946 \end{warpall}
```

## 66.5 Printing the title, etc. in HTML

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in HTML:

**for HTML output:** 6947 `\begin{warpHTML}`

```
\printtitle
```

```
6948 \newcommand*\printtitle{  
6949 {  
6950     \LWR@stoppars%  
6951     \LWR@htmltag{\LWR@tagtitle}%  
6952     @title%  
6953     \LWR@htmltag{\LWR@tagtitleend}%  
6954     \LWR@startpars%  
6955 }
```

`\LWR@printthetitle` A private version which prints the title without footnotes, used to title each HTML page.

```
6956 \newcommand*\LWR@printthetitle{  
6957 {  
6958     \LWR@stoppars%  
6959     \LWR@htmltag{\LWR@tagtitle}%  
6960     @title%  
6961     \LWR@htmltag{\LWR@tagtitleend}%  
6962     \LWR@startpars%  
6963 }
```

`\printauthor` HTML version.

```
6964 \newcommand*\printauthor{
```

The entire author block is contained in a `<div>` named `author`:

```
6965 \begin{BlockClass}{author}
```

`\and` finishes one author and starts the next:

```
6966 \renewcommand{\and}{  
6967 \end{BlockClass}  
6968 \begin{BlockClass}{oneauthor}  
6969 }
```

Individual authors are contained in a `<div>` named `oneauthor`:

```
6970 \begin{BlockClass}{oneauthor}  
6971 @author  
6972 \end{BlockClass}  
6973 \end{BlockClass}  
6974 }
```

---

```
\printdate

6975 \newcommand*\{\printdate\}{%
6976 \begin{BlockClass}\titledate}
6977 \@date
6978 \end{BlockClass}
6979 }

6980 \end{warpHTML}
```

## 66.6 Printing the title, etc. in print form

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in print form:

**for PRINT output:** 6981 `\begin{warpprint}`

```
\printtitle

6982 \newcommand*\{\printtitle\}{{\Huge \@title}}
```

`\printauthor` Print mode.

```
6983 \newcommand*\{\printauthor\}
6984 {{\large\begin{tabular}[t]{c}\@author\end{tabular}}}
```

`\printdate`

```
6985 \newcommand*\{\printdate\}{{\small\textit{\@date}}}

6986 \end{warpprint}
```

## 66.7 \maketitle for HTML output

An HTML `<div>` of class `titlepage` is used.

`\thanks` are a form of footnotes used in the title page. See section 59 for other kinds of footnotes.

See `\thanksmarkseries{series}`, below, to set the style of the footnote marks.

**for HTML output:** 6987 `\begin{warpHTML}`

```
6988 \@ifclassloaded{memoir}
6989 {
6990 \newcommand{\LWR@setfootnoteseries}{%
6991 \renewcommand{\thefootnote}{\@arabic\c@footnote}%
6992 }
```

```

6993 }% not memoir
6994 \if@titlepage
6995 \newcommand{\LWR@setfootnoteseries}{%
6996     \renewcommand\thefootnote{\@arabic\c@footnote}%
6997 }
6998 \else
6999 \newcommand{\LWR@setfootnoteseries}{%
7000     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
7001 }
7002 \fi
7003 }% not memoir

```

\LWR@maketitlesetup Patches \thanks macros.

```
7004 \newcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```

7005 \LWR@setfootnoteseries%
7006 \def\@makefnmark{\textsuperscript{\thefootnote}}
    \thefootnote \Rightarrow \nameuse{arabic}{footnote}, or
    \thefootnote \Rightarrow \nameuse{fnsymbol}{footnote}

```

Redefine the footnote text:

```
7007 \long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```

7008 \textsuperscript{\@thefnmark}~%
    \makethanksmark \Rightarrow \thanksfootmark \Rightarrow \tmark \Rightarrow
    \thefnmark \Rightarrow \itshape a (or similar)

```

Print the text:

```

7009 ##1%
7010 }%
7011 }

```

\@fnsymbol {\langle counter\rangle}

Re-defined to use an HTML entity for the double vertical bar symbol. The original definition used \|\ which was not being seen by *pdftotext*.

```

7012 \def\@fnsymbol#1{\ifcase#1\or *\or \HTMLentity{dagger}\or \HTMLentity{Dagger}\or
7013 \HTMLentity{sect}\or \HTMLentity{para}\or \text{\HTMLunicode{2016}}\or
7014 **\or \HTMLentity{dagger}\HTMLentity{dagger}\or
7015 \HTMLentity{Dagger}\HTMLentity{Dagger}\else\@ctrerr\fi}

```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the `titling` package is adapted, simplified, and modified for HTML output.

7016 \renewcommand\*\maketitle}{%

An HTML titlepage <div> is used for all classes.

7017 \begin{titlepage}

Set up special patches:

7018 \LWR@maketitlesetup

Typeset the title, etc:

7019 \@maketitle

Immediately generate any \thanks footnotes:

7020 \LWR@stoppars@\thanks\LWR@startpars

Close the HTML titlepage div and cleanup:

7021 \end{titlepage}  
7022 \setcounter{footnote}{0}%  
7023 \global\let\thanks\relax  
7024 \global\let\maketitle\relax  
7025 \global\let@\maketitle\relax  
7026 \global\let@\thanks@\empty  
7027 \global\let@\author@\empty  
7028 \global\let@\date@\empty  
7029 \global\let@\title@\empty  
7030 \global\let\title\relax  
7031 \global\let\author\relax  
7032 \global\let\date\relax  
7033 \global\let\and\relax  
7034 }

\@maketitle HTML mode. Typesets the title, etc.:

7035 \DeclareDocumentCommand{\@maketitle}{}{  
7036 \LWR@stoppars%  
7037 \LWR@htmlltag{\LWR@tagtitle}%  
7038 \@title%  
7039 \LWR@htmlltag{\LWR@tagtitleend}%  
7040 \LWR@startpars%  
7041 \begin{BlockClass}\author%

For `IEEEtran` class:

7042 \renewcommand\*\cr{}%

---

```

7043 \renewcommand*\crcr}{%
7044 \renewcommand*\noalign}{}

7045 \renewcommand{\and}{%
7046 \end{BlockClass}%
7047 \begin{BlockClass}{oneauthor}%
7048 }%
7049 \begin{BlockClass}{oneauthor}%
7050 \author%
7051 \end{BlockClass}%
7052 \end{BlockClass}%
7053 \begin{BlockClass}{titledate}%
7054 \date%
7055 \end{BlockClass}%
7056 }

```

\LWR@titlingmaketitle \maketitle for use inside an HTML titlingpage environment.

```
7057 \newcommand*\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
7058 \LWR@stoppars\@thanks\LWR@startpars
```

Set up special patches:

```
7059 \LWR@maketitlesetup
```

Typeset the title, etc:

```
7060 \@maketitle
```

Immediately generate any \thanks footnotes:

```
7061 \LWR@stoppars\@thanks\LWR@startpars
7062 }
```

```
7063 \end{warpHTML}
```

## 66.8 \published and \subtitle

**\subtitle and \published** To add \subtitle and \published to the titlepage, load the `titling` package and use \AddSubtitlePublished in the preamble.

The default `lwarp.css` has definitions for the `published` and `subtitle` classes.

If `titling` is loaded, \AddSubtitlePublished creates a number of additional macros, and also assigns some of the `titling` hooks. If `titling` is not loaded, \AddSubtitlePublished creates null macros.

 **titling hooks** Do not use \AddSubtitlePublished if the user has patched the `titling` hooks for some

other reason. Portions are marked \warpprintonly to reduce extra tags in HTML. Similarly, BlockClass has no effect in print mode. Thus, the following may be marked warpall.

**for HTML & PRINT:** 7064 \begin{warpall}

\AddSubtitlePublished Adds \published and \subtitle, and related.

```

7065 \newcommand*\{\AddSubtitlePublished\}{%
7066 \@ifpackageloaded{titling}{% yes titling package
7067   \newcommand{\@published}{}%
7068   \newcommand{\published}[1]{\gdef\@published{\#1}}%
7069   \renewcommand*\{\maketitlehooka\}{\printpublished}%
7070   \newcommand*\{\printpublished\}{%
7071     \warpprintonly{\begin{center}\unskip}%
7072     \begin{BlockClass}{published}%
7073       \warpprintonly{\large\itshape}%
7074       \@published%
7075     \end{BlockClass}%
7076     \warpprintonly{\end{center}}%
7077   }%
7078   \newcommand{\@subtitle}{}%
7079   \newcommand{\subtitle}[1]{\gdef\@subtitle{\#1}}%
7080   \renewcommand*\{\maketitlehookb\}{\prints_subtitle}%
7081   \newcommand*\{\prints_subtitle\}{%
7082     \warpprintonly{\begin{center}\unskip}%
7083     \begin{BlockClass}{subtitle}%
7084       \warpprintonly{\Large\itshape}%
7085       \@subtitle%
7086     \end{BlockClass}%
7087     \warpprintonly{\end{center}}%
7088   }%
7089 }% yes titling package
7090 {%
7091   \newcommand{\published}[1]{}%
7092   \newcommand*\{\printpublished\}{%
7093   \newcommand{\subtitle}{}%
7094   \newcommand*\{\prints_subtitle\}{%
7095 }% no titling package
7096 }% \AddSubtitlePublished
7097 \end{warpall}

```

## 67 Abstract

The following code replaces the L<sup>A</sup>T<sub>E</sub>X default, and will itself be replaced later if the abstract package is loaded.

**for HTML output:** 7098 \begin{warpHTML}

\abstractname User-redefinable title for the abstract.

Also over-written by the `babel` package.

```
7099 \providecommand*\{\abstractname\}{Abstract}
```

Some classes allow an optional name, so it is allowed here.

```
Env abstract
7100 \DeclareDocumentEnvironment{abstract}{O{\abstractname}}
7101 {
7102 \LWR@forcenewpage
7103 \BlockClass{abstract}
7104 \BlockClassSingle{abstracttitle}{#1}
7105 }
7106 {
7107 \endBlockClass
7108 }

7109 \end{warpHTML}
```

## 68 Quote and verse

### 68.1 Attributions

```
\attribution {\langle name\rangle}
```

For use with quote, quotation, verse:

```
Ex: "A quotation." \attribution{\textsc{Author Name}\\\textsl{Book Title}}
```

**for HTML output:**

```
7110 \begin{warpHTML}
7111 \newcommand{\attribution}[1]{%
7112   \LWR@stoppars%
7113   \begin{BlockClass}{attribution}
7114   #1
7115   \end{BlockClass}
7116   \LWR@startpars%
7117 }
7118 \end{warpHTML}
```

**for PRINT output:**

```
7119 \begin{warpprint}
7120 \newcommand{\attribution}[1]{
7121   \begin{flushright}
7122   \unskip
7123   #1
7124   \end{flushright}%
7125 }
7126 \end{warpprint}
```

## 68.2 Quotes, quotations

**for HTML output:** 7127 \begin{warpHTML}

Env quote

```
7128 \renewenvironment*{quote}
7129 {
7130     \LWR@forcenewpage
7131     \LWR@htmlblocktag{blockquote}
7132 }
7133 {\LWR@htmlblocktag{/blockquote}}
```

Env quotation

```
7134 \renewenvironment*{quotation}
7135 {
7136     \LWR@forcenewpage
7137     \LWR@htmlblocktag{blockquote}
7138 }
7139 {\LWR@htmlblocktag{/blockquote}}
```

```
7140 \end{warpHTML}
```

## 68.3 Verse

When using `verse` or `memoir`, always place a `\\"` after each line.

- \attrib** The documentation for the `verse` and `memoir` packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. `lwarp` provides `\attribution`, which works for both print and `HTML` output. To combine the two so that `\attrib` is used for print and `\attribution` is used for `HTML`:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

- Len \vleftskip** These lengths are used by `verse` and `memoir` to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in `HTML` output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

- ⚠ spacing** Horizontal spacing relies on `pdftotext`’s ability to discern the layout (`-layout` option) of the text in the `HTML`-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

### 68.3.1 L<sup>A</sup>T<sub>E</sub>X core verse environment

**for HTML output:** 7141 \begin{warpHTML}

Env verse

```

7142 \renewenvironment{verse}
7143     {\let\\newline% l warp
7144         \list{}{\itemsep      \z@
7145             \itemindent   -1.5em%
7146             \listparindent\itemindent
7147             \rightmargin \leftmargin
7148             \advance\leftmargin 1.5em}%
7149         \item\relax}
7150     {\endlist}

7151 \end{warpHTML}

```

**for HTML & PRINT:** 7152 \begin{warpall}

### 68.3.2 verse and memoir

The following lengths are used by `verse` and `memoir`. They may be set in either print or HTML output, but are only used in HTML. This allows the user to set `\vleftskip` and `\leftmargini` for print output, and optionally select different values for HTML.

Len \HTMLvleftskip Sets `\vleftskip` inside a `verse` environment in HTML.

```

7153 \newlength{\HTMLvleftskip}
7154 \setlength{\HTMLvleftskip}{1em}

```

Len \HTMLleftmargini Sets `\leftmargini` inside a `verse` environment in HTML.

```

7155 \newlength{\HTMLleftmargini}
7156 \setlength{\HTMLleftmargini}{4.5em}

7157 \end{warpall}

```

## 69 Verbatim and tabbing

**for HTML & PRINT:** 7158 \begin{warpall}

Len \VerbatimHTMLWidth Width to use in HTML `Verbatim` environment.

This width is used when placing line numbers to the right. Ignored during print output.

```

7159 \newlength{\VerbatimHTMLWidth}
7160 \setlength{\VerbatimHTMLWidth}{4in}
7161 \end{warpall}

```

**for HTML output:** 7162 \begin{warpHTML}

Bool LWR@verbtags Used to temporarily turn off verbatim tags while doing \verbatiminput in the HTML head.

```
7163 \newbool{LWR@verbtags}
7164 \booltrue{LWR@verbtags}
```

\LWR@atbeginverbatim [⟨1: style⟩] {⟨2: negative \baselineskip \vspace⟩} {⟨3: class⟩}

Encloses a verbatim environment with the given css class.

The use of \textquotedbl instead of " improves compatibility with xeCJK.

```
7165 \newcommand*{\LWR@atbeginverbatim}[3][]{%
7166 {%
```

Avoid excessive space between lines:

```
7167 \setlength{\parskip}{0ex}%
```

Stop generating HTML paragraph tags:

```
7168 \LWR@stopars%
```

Create a new pre of the given class. The tags may temporarily be turned off for internal use, such as loading the MATHJAX script.

```
7169 \ifbool{LWR@verbtags}{}{%
7170   \LWR@htmltag{pre class=\textquotedbl#3\textquotedbl%}{%
7171     \ifthenelse{\equal{\#1}{}}{\style=\textquotedbl#1\textquotedbl%}{%
7172       }%
7173     \LWR@newline% pre
7174     \leavevmode\unskip\LWR@print@vspace*{-\#2\baselineskip}%
7175 }{}}
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the css for the verse class.

```
7176 \begingroup%
```

```
7177 % \LWR@print@normalsize%
7178 \LWR@origtfamily%
7179 \LWR@print@small%
```

Since inside a <pre>, restore the original list processing:

```
7180 \LWR@restoreoriglists%
```

Turn off babel-french extra space before punctuation:

```
7181 \LWR@FBcancel%
```

Do not produce HTML tags for \hspace inside a verse par. Restore plain L<sup>A</sup>T<sub>E</sub>X \hspace functionality:

```
7182 \LWR@select@print@hspace%
7183 }
```

\LWR@afterendverbatim {<*negative* \baselineskip \vspace>}

Finishes enclosing a verbatim environment.

```
7184 \newcommand*{\LWR@afterendverbatim}[1]{%
7185 \endgroup%
7186 \par%
```

At the end of the environment, close the pre:

```
7187 \ifbool{\LWR@verbtags}{%
7188   \LWR@print@vspace*{-\#1\baselineskip}%
7189   \noindent\LWR@htmltag{/pre}\LWR@orignewline% pre
7190 }{}}
```

Resume regular paragraph handling:

```
7191 \LWR@startpars%
7192 }
```

\verbatiminput {<*filename*>}

Patch \verbatiminput to add HTML tags:

```
7193 \let\LWRV@origverbatim@input\verbatim@input
7194
7195 \renewcommand{\verbatim@input}[2]{%
7196 \ifbool{\LWR@verbtags}{\LWR@forcenewpage}{%
7197 \LWR@atbeginverbatim{2.5}{Verbatim}%
7198 \LWRV@origverbatim@input{\#1}{\#2}%
7199 \LWR@afterendverbatim{1.5}%
7200 }}
```

Env verbatim

```
7201 \AfterEndPreamble{
7202 \LWR@traceinfo{Patching verbatim.}
7203 \AtBeginEnvironment{verbatim}{%
7204 \LWR@forcenewpage%
7205 \LWR@atbeginverbatim{2.5}{verbatim}%
7206 }
7207 \AfterEndEnvironment{verbatim}{%
7208 \LWR@afterendverbatim{1}%
7209 }
7210 }
```

`Env tabbing` The tabbing environment works, except that `svg` math and `lateximages` do not yet work inside the environment.

 `math in tabbing` If math is used inside `tabbing`, place `tabbing` inside a `lateximage` environment, which will render the entire environment as a single `svg` image.

```

7211 \newcommand*{\LWR@HTML@tabbing}{%
7212 \LWR@forcenewpage%
7213 \LWR@atbeginverbatim{3}{tabbing}%
7214 \LWR@print@tabbing%
7215 }
7216
7217 \newcommand*{\LWR@HTML@endtabbing}{%
7218     \LWR@print@endtabbing%
7219     \LWR@afterendverbatim{1}%
7220 }
7221
7222 \LWR@formatted{tabbing}
7223 \LWR@formatted{endtabbing}

7224 \end{warpHTML}

```

## 70 Theorems

`\newtheorem`  $\{\langle text \rangle\} [\langle counter \rangle]$  -or-  $[\langle oldname \rangle]$   $\{\langle text \rangle\}$

A few minor changes are made to supply `HTML` tags.

- The entire theorem is placed into a `<div>` of class `theoremcontents`.
- The label for each theorem is placed inside a `<span>` of class `theoremlabel`.
- The contents are placed inside a `<div>` of class `theoremcontents`.

**for HTML output:** 7225 `\begin{warpHTML}`

`\@begintheorem`  $\{\langle name \rangle\} \{\langle number \rangle\}$

```

7226 \renewcommand{\@begintheorem}[2]{%
7227 \LWR@forcenewpage
7228 \BlockClass{theoremcontents}
7229 \trivlist
7230 \item[\InlineClass{theoremlabel}{#1\ #2\ }]\itshape
7231 }

```

`\@opargbegintheorem`  $\{\langle name \rangle\} \{\langle number \rangle\} \{\langle oparg \rangle\}$

```

7232 \renewcommand{\@opargbegintheorem}[3]{%
7233 \LWR@forcenewpage

```

---

```

7234 \BlockClass{theoremcontents}
7235 \trivlist
7236 \item[\InlineClass{theoremlabel}{\#1\ #2\ (#3)\ }]\itshape
7237 }

\@endtheorem

7238 \renewcommand*{\@endtheorem}{%
7239 \endtrivlist
7240 \endBlockClass% theoremcontents
7241 }

7242 \end{warpHTML}

```

## 71 Lists

The environments `itemize`, `enumerate`, and `description` are patched when `lwarp` is started. These patches support the standard L<sup>A</sup>T<sub>E</sub>X environments, as well as those of `enumerate`, `enumitem`, and `paralist`, and at least the French version of `babel`. Additional patches are done on a package-specific basis.

The L<sup>A</sup>T<sub>E</sub>X source for `itemize` and `enumerate` are found in `source2e`, but the source for `description` is found in `article.cls`, etc.

**empty item** To have an empty item, use `\mbox{}` or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

---

```

begin{itemize}
item \mbox{}%
\begin{itemize}
...
\end{itemize}
item %
\begin{itemize}
...
\end{itemize}

```

---

`\makelabel` While inside a list environment, `lwarp` nullifies a number of T<sub>E</sub>X horizontal skip and fill commands, allowing the user to define `\makelabel` for print mode while HTML mode ignores those commands.

 **label font** When defining `\makelabel` in a list environment, use `\textbf` etc. instead of `\bfseries`.

### 71.1 List environment

**for HTML output:** 7243 `\begin{warpHTML}`

\LWR@printcloselist May be locally redefined by enumerate or description.

```
7244 \newcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
```

\LWR@printopenlist May be locally redefined by enumerate or description.

```
7245 \newcommand*{\LWR@printopenlist}{\ul style="\LWR@print@mbox{list-style-type:none}”}
```

\@mklab Removes PDF spacing.

```
7246 \AtBeginDocument{  
7247 \def\@mklab#1{  
7248 % \hfil %  
7249 #1}  
7250 \let\makelabel\@mklab  
7251 }
```

\@donoparitem Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
7252 \def\@donoparitem{  
7253 \@noparitemfalse  
7254 % \global\setbox\@labels\hbox{\hskip -\leftmargin  
7255 % \unhbox\@labels  
7256 % \hskip \leftmargin}%  
7257 % \if@minipage\else  
7258 % \tempskipa\lastskip  
7259 % \vskip -\lastskip  
7260 % \advance\tempskipa\outerparskip  
7261 % \advance\tempskipa -\parskip  
7262 % \vskip\tempskipa  
7263 % \fi  
7264 }
```

\@item Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
7265 \def\@item[#1]{  
7266 \LWR@traceinfo{@item}  
7267 \if@noparitem  
7268 \@donoparitem  
7269 \else  
7270 % \if@inlabel  
7271 % \indent  
7272 % \par  
7273 % \fi  
7274 \ifhmode  
7275 % \unskip\unskip  
7276 % \par  
7277 \fi  
7278 \if@newlist  
7279 \if@nobreak
```

```
7280      \@nbitem
7281      \else
7282 %       \addpenalty\@beginparpenalty
7283 %       \addvspace\@topsep
7284 %       \addvspace{-\parskip}%
7285      \fi
7286 \else
7287 %       \addpenalty\@itempenalty
7288 %       \addvspace\itemsep
7289      \fi
7290      \global\@inlabeltrue
7291 \fi
7292 % \everypar{%
7293 % \minipagefalse
7294 \global\@newlistfalse

7295 % \if@inlabel
7296 % \global\@inlabelfalse

7297 % {\setbox\z@\lastbox
7298 % \ifvoid\z@
7299 % \kern-\itemindent
7300 % \fi}%

7301 % \box\@labels
7302 % \penalty\z@
7303 \fi

7304 % \if@nobreak
7305 % \nobreakfalse
7306 % \clubpenalty \zM
7307 % \else
7308 % \clubpenalty \clubpenalty
7309 % \everypar{}%
7310 % \fi}%

7311 \if@noitemarg
7312 \noitemargfalse
7313 \if@nmbrlist

7314 \refstepcounter\@listctr
7315 \fi
7316 \fi

7317 \makelabel{\#1} % extra space
7318 % \sbox\@tempboxa{\makelabel{\#1}%
7319 % \global\setbox\@labels\hbox{%
7320 % \unhbox\@labels
7321 % \hskip \itemindent
7322 % \hskip -\labelwidth
7323 % \hskip -\labelsep
7324 % \ifdim \wd\@tempboxa >\labelwidth
7325 % \box\@tempboxa
```

---

```

7326 %      \else
7327 %      \hbox to\labelwidth {\unhbox\@tempboxa}%
7328 %      \fi
7329 %      \hskip \labelsep}%
7330 \ignorespaces%
7331 }

\@nbitem

7332 \def\@nbitem{%
7333 %  \@tempskipa\@outerparskip
7334 %  \advance\@tempskipa -\parskip
7335 %  \addvspace\@tempskipa
7336 }

```

\LWR@listitem [*<label>*]

Handles \item inside a list, itemize, or enumerate.

See \LWR@openparagraph where extra \hspace is used to leave room for the label while inside a list during paragraph construction.

```

7337 \newcommand*{\LWR@listitem}{%
7338 \LWR@stoppars%
7339 \LWR@startnewdepth{listitem}%
7340 \LWR@htmltag{li}%
7341 \LWR@startpars%
7342 \LWR@origitem%
7343 }

```

\LWR@nulllistfills Nullifies various TeX fill commands, in case they are used inside \makelabel. Problems are caused when these are nullified all the time.

```

7344 \newcommand*{\LWR@nulllistfills}{%
7345 \renewcommand*{\hss}{}%
7346 \renewcommand*{\llap}[1]{##1}%
7347 \renewcommand*{\rlap}[1]{##1}%
7348 \renewcommand*{\hfil}{}%
7349 \renewcommand*{\hfilneg}{}%
7350 \renewcommand*{\hfill}{}%
7351 }

```

Env list {*<label>*} {*commands*}

```

7352 \newcommand*{\LWR@liststart}{%
7353 \LWR@traceinfo{\LWR@liststart}%
7354 \LWR@stoppars%
7355 \LWR@pushoneclose{list}%
7356 \LWR@htmltag{\LWR@printopenlist}\LWR@orignewline%
7357 \LWR@startpars%
7358 \setlength{\topsep}{0pt}%
7359 \setlength{\partopsep}{0pt}%

```

---

```

7360 \setlength{\itemsep}{0pt}%
7361 \setlength{\parsep}{0pt}%
7362 \setlength{\leftmargin}{0pt}%
7363 \setlength{\rightmargin}{0pt}%
7364 \setlength{\listparindent}{0pt}%
7365 \setlength{\itemindent}{0pt}%
7366 \setlength{\labelsep}{1em}%
7367 \LWR@nulllistfills%
7368 }

7369 \newcommand*{\LWR@listend}{%
7370 \LWR@traceinfo{\LWR@listend}%
7371 \LWR@stoppars%
7372 \LWR@closeprevious{list}%
7373 \LWR@startpars%
7374 }

```

## 71.2 Itemize

\LWR@itemizeitem [<*label*>]

Handles \item inside an itemize or enumerate.

See \LWR@openparagraph where extra \hspace is used to leave room for the label while inside a list during paragraph construction.

```

7375 \newcommand*{\LWR@itemizeitem}{%
7376 \LWR@stoppars%
7377 \LWR@startnewdepth{listitem}%
7378 \LWR@htmlltag{li}%
7379 \LWR@startpars%
7380 \LWR@origitem%
7381 }

```

Env itemize [<*options*>]

```

7382 \newcommand*{\LWR@itemizestart}{%
7383 \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
7384 \renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
7385 \let\item\LWR@itemizeitem%
7386 \LWR@nulllistfills%
7387 }

```

## 71.3 Enumerate

An HTML unordered list is used with customized L<sup>A</sup>T<sub>E</sub>X-generated labels.

Env enumerate [<*options*>]

---

```

7388 \newcommand*{\LWR@enumeratestart}{%
7389 \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
7390 \renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
7391 \let\item\LWR@itemizeitem%
7392 \LWR@nulllistfills%
7393 }

```

## 71.4 Description

\LWR@descitem [*<label>*] Handles an \item inside a description.

```

7394 \newcommand*{\LWR@descitem}[1][]{%
7395 {%
7396 \LWR@stoppars%
7397 \LWR@setlatestname{#1}%
7398 \LWR@startnewdepth{descitem}%

```

While creating the label, encase it inside tags and disable \hspace, which is used by the standard classes to add space to the labels.

```

7399 \begingroup%
7400 \let\LWR@orig@desc@makelabel\makelabel
7401 \renewcommand*{\makelabel}[1]{%
7402     \LWR@htmlltag{dt}%
7403     \LWR@orig@desc@makelabel{#1}%
7404     \LWR@htmlltag{/dt}%
7405 }
7406 \LWR@select@html@nohspace%
7407 \LWR@origitem[#1]%
7408 \endgroup%
7409 \LWR@orignewline%
7410 \LWR@htmlltag{dd}%
7411 \LWR@startpars%
7412 }

```

Env description [*<options>*]

```

7413 \newcommand*{\LWR@descriptionstart}{%
7414 \renewcommand*{\LWR@printcloselist}{\LWR@printclosedescription}
7415 \renewcommand*{\LWR@printopenlist}{dl}
7416 \let\item\LWR@descitem%
7417 \LWR@nulllistfills%
7418 }

```

## 71.5 Patching the lists

\LWR@patchlists Patches list environments.

\LWR@patchlists remembers \item as defined by whatever packages have been loaded, then patches the itemize, enumerate, and description environments and

\item. This works with the native L<sup>A</sup>T<sub>E</sub>X environments, as well as those provided by `enumitem`, `enumerate`, and `paralist`.

```

7419 \newcommand*{\LWR@patchlists}{%
7420     \LetLtxMacro{\item}{\LWR@listitem}%
7421     \LetLtxMacro{\@item}{\LWR@HTML@item}%
7422     \renewcommand*{\@trivlist}{%
7423         \LWR@traceinfo{@trivlist start}%
7424         \LWR@liststart%
7425         \LWR@orig@trivlist%
7426         \LWR@traceinfo{@trivlist done}%
7427     }%
7428     \renewcommand*{\trivlist}{%
7429         \LWR@traceinfo{trivlist}%
7430         \LWR@origtrivlist%
7431     }%
7432     \renewcommand*{\endtrivlist}{%
7433         \LWR@traceinfo{endtrivlist start}%
7434         \LWR@origendtrivlist\LWR@listend%
7435         \LWR@traceinfo{endtrivlist done}%
7436     }%
7437     \renewcommand*{\itemize}{%
7438         \LWR@itemizestart\LWR@origitemize%
7439     }%
7440     \renewcommand*{\enumerate}{%
7441         \LWR@enumeratestart\LWR@origenumerate%
7442     }%
7443     \renewcommand*{\description}{%
7444         \LWR@descriptionstart\LWR@origdescription%
7445     }%
7446 }

```

\LWR@restoreoriglists Restores the original trivlist environment.

```

7447 \newcommand*{\LWR@restoreoriglists}{%
7448 \LWR@traceinfo{\LWR@restoreoriglists}%
7449 \LetLtxMacro{\item}{\LWR@origitem}%
7450 \LetLtxMacro{\@item}{\LWR@orig@item}%
7451 \let{@trivlist}{\LWR@orig@trivlist}%
7452 \let{trivlist}{\LWR@origtrivlist}%
7453 \let{endtrivlist}{\LWR@origendtrivlist}%
7454 \LetLtxMacro{\itemize}{\LWR@origitemize}%
7455 \LetLtxMacro{\enditemize}{\LWR@endorigitemize}%
7456 \LetLtxMacro{\enumerate}{\LWR@origenumerate}%
7457 \LetLtxMacro{\endenumerate}{\LWR@endorigenumerate}%
7458 \LetLtxMacro{\description}{\LWR@origdescription}%
7459 \LetLtxMacro{\enddescription}{\LWR@endorigdescription}%
7460 \let{@mklab}{\LWR@orig@mklab}%
7461 \let{makelabel}{\LWR@origmakelabel}%
7462 \let{@donoparitem}{\LWR@orig@donoparitem}%
7463 \let{@nbitem}{\LWR@orig@nbitem}%
7464 }

7465 \end{warpHTML}

```

## 72 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax of the L<sup>A</sup>T<sub>E</sub>X core and the various tabular-related packages.

### 72.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, `siunitx S` columns, or the packages `multirow`, `longtable`, `supertabular`, or `xtab`.

#### Defining macros and environments:

 Misplaced alignment tab character &

- When defining environments or macros which include tabular and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are ignored in print mode.

 floatrow

 tabular inside another environment

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

This includes before and after defining any macro which used `\ttabbox` from `floatrow`.

- When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a
definition
\newenvironment{outerenvironment}
{
\begin{tabular}{cc}
left & right \\
\end{tabular}
\begin{TabularMacro}\ResumeTabular
left & right \\
\end{TabularMacro}
\end{tabular}
\end{outerenvironment}
\StopDefiningTabulars
```

#### Cell contents:

 macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use `\TabularMacro` just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

#### Column specifiers:

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

⚠ \newcolumntype

- \newcolumntype is ignored; unknown column types are set to l.

**Rules:**

vertical rules

- Doubled \hlines, \midrules, and vertical rules are supported.
- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional -2ex is ignored in HTML, but improves the visual formatting in the print output.

- For \toprule and \bottomrule, when combined with a \warpprint or \warpHTML environment, if a “Misplaced \noalign” error occurs, change

This & That \endhead

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevant to HTML output.

**Other:**

longtable headings

- tabularx ignores the width, but X columns do produce paragraph columns or multicolumns.

- For longtable, place headings and footings which do not apply to HTML inside \warpprintonly{}.

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside {} braces, including commands such as \multirow. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

- In L<sup>A</sup>T<sub>E</sub>X, a tabular may be placed inside a minipage, but in HTML a <table> may not be inside a <span>. If this situation is detected, a warning is printed instructing the user to isolate the <span> using \warpprintonly or the \warpprint environment.

⚠ S columns

⚠ tabular inside a &lt;span&gt;

**for HTML output:** 7466 \begin{warpHTML}

## 72.2 Temporary package-related macros

These macros are temporary placeholders for macros defined by various packages. If the relevant package is not loaded, these placeholders are used instead.

### 72.2.1 arydshln

Emulated by the original L<sup>A</sup>T<sub>E</sub>X non-dashed versions.

```
7467 \LetLtxMacro\hdashline\hline
7468 \LetLtxMacro\cdashline\cline
7469 \LetLtxMacro\firsthdashline\hline
7470 \LetLtxMacro\lasthdashline\hline
```

## 72.3 Token lookahead

Used by \LWR@futureonospacelet to look at the next token.

\LWR@mynexttoken

```
7471 \newcommand{\LWR@mynexttoken}{\relax}
```

\futurelet copies the next token then executes a function to analyze it.

\LWR@futureonospacelet does the same, but ignores intervening white space

Based on the booktabs style:

\LWR@futureonospacelet

```
7472 \def{\LWR@futureonospacelet}{\def{\LWR@cs}{#1}%
7473 \afterassignment{\LWR@fnslone\let{\nexttoken= } }%
7474 %
7475 \def{\LWR@fnslone}{\expandafter{\futurelet{\LWR@cs}{\LWR@fnsltwo}}%
7476 %
7477 \def{\LWR@fnsltwo}{%
7478 \expandafter{\ifx{\LWR@cs}{\sptoken}\let{\next=\LWR@fnslthree}%
7479 \else\let{\next=\nexttoken}\fi\next}%
7480 %
7481 \def{\LWR@fnslthree}{\afterassignment{\LWR@fnslone\let{\next= } }%
```

\LWR@getmynexttoken Looks ahead and copies the next token into \LWR@mynexttoken.

```
7482 \newcommand*{\LWR@getmynexttoken}{%
7483 \LWR@traceinfo{\LWR@getmynexttoken} }
```

---

```

7484 % nothing must follow this next line
7485     \LWR@futurenonspacet\let\mynexttoken\LWR@tabledatacolumntag
7486 }

```

## 72.4 Tabular variables

In order to support nested tabulars, each of these is used locally. For local counters, etoolbox's \defcounter and lwarf's new \defaddtocounter are used.

Bool LWR@startedrow True if should print a row tag before this column.

```

7487 \newbool{LWR@startedrow}
7488 \boolefalse{LWR@startedrow}

```

Bool LWR@tabularcelladded True if have added a data cell for this position.

```

7489 \newbool{LWR@tabularcelladded}
7490 \boolefalse{LWR@tabularcelladded}

```

Ctr LWR@hlines Number of \hlines or \midrules above the next row.

```
7491 \newcounter{LWR@hlines}
```

Ctr LWR@hdashedlines Number of arydshln dashed lines above the next row.

```
7492 \newcounter{LWR@hdashedlines}
```

Bool LWR@doingtbrule True if the next row will have a top/bottom rule above it.

```

7493 \newbool{LWR@doingtbrule}
7494 \boolefalse{LWR@doingtbrule}

```

Bool LWR@doingcmidrule True if the next row will have a cmidrule above it.

This is used by \LWR@tabularfinishrow to force a final empty row to create the border for the \cmidrule.

```

7495 \newbool{LWR@doingcmidrule}
7496 \boolefalse{LWR@doingcmidrule}

```

Bool LWR@tableparcell True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

```
7497 \newbool{LWR@tableparcell}
```

Bool LWR@skippingmrowcell True if are doing an empty \multirow cell, and thus there is no data tag to close.

```
7498 \newbool{LWR@skippingmrowcell}
```

Bool LWR@skippingmcolrowcell True if are doing an empty \multicolumn{row} cell, and thus there is no data tag to close,

and do not print @ and ! columns.

```
7499 \newbool{LWR@skippingmcolrowcell}
```

Bool LWR@usedmultirow Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
7500 \newbool{LWR@usedmultirow}
```

Bool LWR@foundmrowcell Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
7501 \newbool{LWR@foundmrowcell}
```

Bool LWR@skipatbang True if just finished a \multicolumn so should not create the trailing @ or ! columns table data cells.

```
7502 \newbool{LWR@skipatbang}
```

Bool LWR@emptyatbang True if finishing a row and should print empty @ or ! column table data cells.

```
7503 \newbool{LWR@emptyatbang}
```

Bool LWR@intabularmetadata True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.

```
7504 \newbool{LWR@intabularmetadata}
```

```
7505 \boolefalse{LWR@intabularmetadata}
```

Bool LWR@exittingtabular When \end is found, turns off the next opening data tag.

```
7506 \newbool{LWR@exittingtabular}
```

Bool LWR@tabularmutemods Mutes HTML output for @, !, < and >.

This is used while printing the final row to generate \bottomrules.

```
7507 \newbool{LWR@tabularmutemods}
```

Bool LWR@validtablecol True if found a valid table column type.

```
7508 \newbool{LWR@validtablecol}
```

Bool LWR@opttablecol True if found a table column optional argument.

```
7509 \newbool{LWR@opttablecol}
```

Used to add a style to a table data cell:

```
7510 \newbool{LWR@tdhavecellstyle}
```

Ctr LWR@tabularDepth Tracks whether & is being used inside a tabular.

---

```
7511 \newcounter{LWR@tabulardepth}
7512 \setcounter{LWR@tabulardepth}{0}
```

- Ctr `LWR@tabularpardepth` Tracks whether should look ahead at the next token when encountering a `\par` while processing tabular contents.

When `LWR@tabularpardepth` is deeper than `LWR@tabulardepth` then `lwarp` has started looking at the contents of the tabular, and thus any `\pars` encountered must be followed by another token lookahead.

```
7513 \newcounter{LWR@tabularpardepth}
7514 \setcounter{LWR@tabularpardepth}{0}
```

```
7515 \newcommand*{\LWR@colsresult}{}%temp storage for column format results
7516 \newcommand*{\LWR@pposition}{}%
7517 \newcommand*{\LWR@pleft}{}%
7518 \newcommand*{\LWR@pright}{}%
```

- `LWR@tablecolspec` Holds the parsed column specification, of total width `LWR@tabletotalTeXcols`, not counting @ and ! columns.

Will contain a string such as `llrrccpc`, exactly one letter per L<sup>A</sup>T<sub>E</sub>X table column, without @, !, >, <, or the vertical bar.

- `\LWR@strresult` Holds the result of Str functions.

```
7519 \providecommand*{\LWR@strresult}{}%
7520 \providecommand*{\LWR@strresulttwo}{}%
```

- `\LWR@origcolspec` Holds the original column specs given to `tabular`.

```
7521 \newcommand*{\LWR@origcolspec}{}%
```

- Ctr `LWR@tablecolspecwidth` Holds the number of tokens in the table columns specification.

This is includes one for each @, !, <, > column, and also one for each of the parameters of p, @, !, <, > columns, and three for each D column.

(This is not the total # of L<sup>A</sup>T<sub>E</sub>X columns in the table.)

```
7522 \newcounter{LWR@tablecolspecwidth}
```

- Ctr `LWR@tablecolspecindex` While parsing the L<sup>A</sup>T<sub>E</sub>X table column specification, starts at 1 and is incremented per token of the specification.

```
7523 \newcounter{LWR@tablecolspecindex}
```

- Ctr `LWR@tableLaTeXcolindex` While producing the table, resets to 1 at the start of the table and also at each end of line, and is incremented by 1 by each ampersand.

```
7524 \newcounter{LWR@tableLaTeXcolindex}
```

Ctr LWR@tabletotalLaTeXcols While parsing a table column specification, begins at 0 and increments by 1 per *LATEX* table column. Eventually holds the final number of *LATEX* table columns in each row, not counting @ and ! columns. (In *HTML*, @ and ! cells become their own columns, but are not included in LWR@tabletotalLaTeXcols.)

```
7525 \newcounter{LWR@tabletotalLaTeXcols}
```

Ctr LWR@tabletotalLaTeXcolsnext Holds the next *LATEX* table column index while parsing, equal to one more than LWR@tabletotalLaTeXcols.

```
7526 \newcounter{LWR@tabletotalLaTeXcolsnext}
```

LWR@colatspec A data array of specifications for @ columns. The leftmost's index is lefthead, the others are counter values. See section 42.

LWR@colbangspec A data array of specifications for ! columns. The leftmost's index is lefthead, the others are counter values. See section 42.

LWR@colbeforespec A data array of specifications for > columns.

LWR@col afterspec A data array of specifications for < columns.

LWR@colbarspec A data array of specifications for vertical rules.

Ctr LWR@cellcolordepth Counts how many cell color <div>s were added to the current tabular data cell.

```
7527 \newcounter{LWR@cellcolordepth}
```

#### 72.4.1 Multicolumn variables

```
7528 \newcounter{LWR@tablemulticolwidth}
```

Indexes into the multicolumn specification:

```
7529 \newcounter{LWR@tablemulticolpos}
```

Remembers multicolumn vertical rules if found in the column spec.

```
7530 \newcounter{LWR@mcolvertbarsl}
7531 \newcounter{LWR@mcolvertbarsr}
7532 \newcounter{LWR@mcolvertbarsldash}
7533 \newcounter{LWR@mcolvertbarsrdash}
7534 \newbool{LWR@mcolvertbaronleft}
```

#### 72.4.2 Longtable variables

Bool LWR@starredlongtable Per the caption pacakge, step the counter if longtable\*.

```
7535 \newbool{LWR@starredlongtable}
7536 \boolfalse{LWR@starredlongtable}
```

### 72.4.3 Midrule variables

Ctr LWR@midrulecounter Indexes across the LWR@midrules and LWR@trim<l/r>rules data arrays.

```
7537 \newcounter{LWR@midrulecounter}
```

## 72.5 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:

<http://tex.stackexchange.com/questions/11638/where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860>

\LWR@insertatbangcols

```
7538 \newcommand*\LWR@insertatbangcols{%
7539     \ifbool{LWR@skipatbang}{%
7540         {}%
7541         {%
7542             \LWR@printatbang{at}{\arabic{LWR@tableLaTeXcolindex}}%
7543             \LWR@printatbang{bang}{\arabic{LWR@tableLaTeXcolindex}}%
7544         }%
7545     }}
```

\LWR@closetabledatacell If LWR@skippingmrowcell or LWR@skippingmcolrowcell then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
7546 \newcommand*\LWR@closetabledatacell{%
7547     \booltrue{LWR@intabularmetadata}%
7548     \ifbool{LWR@exittingtabular}{%
7549         {%
7550             \LWR@stoppars%
7551         }%
7552         {%
7553             \ifboolexpr{\bool{LWR@skippingmrowcell} \or \bool{LWR@skippingmcolrowcell}}{%
7554                 {%
7555                     \LWR@stoppars%
7556                 }%
7557             }%
7558             {\LWR@insertatbangcols}%
7559         }%
7560         {%
7561             \LWR@stoppars%
7562         }%
7563     }%
7564 }
```

If not skipping a \multicolumnrow cell, insert the @ and ! columns after this non-existent column.

```
7556     \ifbool{LWR@skippingmcolrowcell}{%
7557         {}%
7558         {\LWR@insertatbangcols}%
7559     }%
7560     {%
7561         \LWR@stoppars%
7562     }%
7563 }
```

Insert any < then any @ and ! column contents, unless muted for the \bottomrule or a \multicolumn:

```

7561      \unskip%
7562      \ifboolexpr{%
7563          bool{LWR@tabularmutemods} or
7564          bool{LWR@skipatbang} or
7565          bool{LWR@emptyatbang}
7566      }%
7567      {}%
7568      {}%
7569      \LWR@getexpparray{\LWR@colaferspec}%
7570      {\arabic{\LWR@tableLaTeXcolindex}}%
7571  }%

```

Close paragraphs:

```

7572      \LWR@stopars%
7573      \boolfalse{\LWR@tableparcell}%

```

Close the table data cell.

Close any color <div>s.

```

7574      \whileboolexpr{test {\ifnumcomp{\value{\LWR@cellcolordepth}}{>}{0}}}{{%
7575          \LWR@htmlltag{/div}\LWR@orignewline%
7576          \defaddtocounter{\LWR@cellcolordepth}{-1}%
7577      }}%

```

Skip the @ and ! cells if are closing a multicolumn cell.

```

7578      \leavevemode\unskip\LWR@htmlltag{/td}\LWR@orignewline%
7579      \global\booltrue{\LWR@tabularcelladded}%
7580      \LWR@insertatbangcols%
7581      }% not skipping mrowcell
7582      }% not exiting tabular
7583      \boolfalse{\LWR@skippingmrowcell}%
7584      \boolfalse{\LWR@skippingmcolrowcell}%
7585      \boolfalse{\LWR@skipatbang}%

```

Color control. Column is set by >{} for each cell, so it must be cleared here.

```

7586      \def\LWR@cellHTMLcolor{}%
7587      \def\LWR@columnHTMLcolor{}%
7588      \defcounter{\LWR@cellcolordepth}{0}%
7589 }%

```

When not used inside a tabular, & performs its original function as recorded here (with catcode 4 ).

```
7590 \let\LWR@origampmacro&
```

```
7591 \end{warpHTML}
```

### 72.5.1 Handling &

**for HTML output:** 7592 \begin{warpHTML}

- & Will behave depending on whether it is being used inside `tabular`.  
 & is redefined to test whether it is inside a tabular environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```
7593 \newcommand*{\LWR@tabularampersand}{%
7594     \LWR@traceinfo{\LWR@tabularampersand}%
7595     \ifnumcomp{\value{\LWR@tabulardepth}}{>}{0}%
7596     {%
```

If not skipping a multirow cell, close the current data cell.

```
7597     \unskip%
7598     \LWR@closetabledatcell%
```

Move to the next column.

```
7599     \defaddtocounter{\LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
7600     \global\boolfalse{\LWR@tabularcelladded}%
```

Look at the next token to decide multi or single column data tag.

```
7601     \LWR@getmynexttoken%
7602 }
```

If not inside a tabular, performs the original action:

```
7603     {%
7604         \LWR@origampmacro%
7605     }%
7606 }
```

& is left with its original catcode for now.

`tikz` package seems to require & be left alone until after `tikz` has been loaded. Also, `cleveref` uses the ampersand in one of its options.

& is made active inside a `tabular`.

& is left alone when in math alignments.

### 72.5.2 Filling an unfinished row

\LWR@tabularfinishrow Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
7607 \newcommand*{\LWR@tabularfinishrow}{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
7608     \ifboolexpr{%
7609         not bool{\LWR@exittingtabular} or%
7610         bool{\LWR@doingtbrule} or%
7611         bool{\LWR@doingscmidrule} or%
7612         test{\ifnumcomp{\value{\LWR@hlines}}{>}{0}} or%
7613         test{\ifnumcomp{\value{\LWR@hdashedlines}}{>}{0}} or%
7614         bool{\LWR@startedrow}%
7615     }{%
```

To temporarily turn off `\LWR@exittingtabular` so that table data tags will still be generated:

If generating a final row for the `\bottomrule` borders, turn off the @, !, <, and > column output:

```
7616     \ifbool{\LWR@exittingtabular}{%
7617         \booltrue{\LWR@tabularmutemods}%
7618     }{%
7619         \boolfalse{\LWR@tabularmutemods}%
7620     }%
```

Locally reenable the table data tags until finished with the final row:

```
7621     \boolfalse{\LWR@exittingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
7622     \whileboolexpr{%
7623         test{%
7624             \ifnumcomp{\value{\LWR@tableLaTeXcolindex}}{<}{%
7625                 \value{\LWR@tabletotalLaTeXcols}%
7626             } or %
7627             (%
7628                 bool{\LWR@intabularmetadata} and%
7629                 not bool{\LWR@tabularcelladded} and%
7630                 test{%
7631                     \ifnumcomp{\value{\LWR@tableLaTeXcolindex}}{=}{%
7632                         \value{\LWR@tabletotalLaTeXcols}%
7633                     }%
7634                 }%
7635             }%
7636             {%
7637                 \LWR@tabledatasinglecolumntag%
```

The following is essentially `\LWR@tabularampersand` with `\LWR@emptyatbang` added to empty the following cells:

```

7638      \LWR@closetabledatcell%
7639      \defaddtocounter{LWR@tableLaTeXcolindex}{1}%
7640      \global\boolfalse{LWR@tabularcelladded}%
7641      \booltrue{LWR@emptyatbang}%

```

Starts the next cell:

```

7642      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
7643          {\value{LWR@tabletotalLaTeXcols}}%
7644          {\LWR@getmynexttoken}%
7645          {}%
7646      }%

```

Reenable the original LWR@exitngtabular to close the entire table:

```

7647      \ifbool{LWR@tabularmutemods}{%
7648          \booltrue{LWR@exitngtabular}%
7649      }{%
7650          \boolfalse{LWR@exitngtabular}%
7651      }%
7652      \boolfalse{LWR@tabularmutemods}%

7653      \boolfalse{LWR@emptyatbang}%
7654      }{}% ifboolexpr
7655 }

```

## 72.6 Handling \\

Inside tabular, \\ is redefined to \LWR@tabularendofline

Throws away options \\[dim] or \\\*

\LWR@tabularendofline

```
7656 \NewDocumentCommand{\LWR@tabularendofline}{s o}{%
```

Finish the row:

```

7657      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
7658          {\value{LWR@tabletotalLaTeXcols}}%
7659          {\LWR@tabularfinishrow}%
7660          {\LWR@closetabledatcell}%
7661      \LWR@htmlltag{/tr}\LWR@orignewline%

```

xcolor row color support:

```
7662     \rowc@lors%
```

No longer inside a data cell:

```
7663     \booltrue{LWR@intabularmetadata}%
```

Not yet started a table row:

```
7664 \boolearn{\LWR@startedrow}{}
```

Additional setup:

```
7665 \defcounter{LWR@hlines}{0}%
7666 \defcounter{LWR@hdashedlines}{0}%
7667 \boolearn{\LWR@doingtbrule}{}
7668 \boolearn{\LWR@doingcmidrule}{}
7669 \LWR@clearmidrules%
```

```
7670 \def\LWR@rowHTMLcolor{}
```

Start at first column:

```
7671 \defcounter{LWR@tableTeXcolindex}{1}%
```

Have not yet added data in this column:

```
7672 \global\boolearn{\LWR@tabularcelladded}{}
```

Allow TeX to flush the pending paragraph. Not doing so causes a slowdown for very large tables.

```
7673 \LWR@stopars%
7674 \LWR@origpar%
```

Look at the next token to decide between single column data tag or a special case:

```
7675 \LWR@getmynexttoken%
7676 }
```

## 72.7 Looking ahead in the column specifications

```
\LWR@columnspeclookahead {\langle offset\rangle}
```

Looks offset tokens ahead in the column specification, setting \LWR@strresulttwo.

The w column alignment will be seen as a single unit such as {c}.

```
7677 \newcommand*{\LWR@columnspeclookahead}[1]{%
7678   \setcounter{LWR@tempcountone}{\value{\LWR@tablecolspeccolindex}}%
7679   \addtocounter{LWR@tempcountone}{#1}%
7680   \fullexpandarg%
7681   \StrChar{\LWR@origcolspec}{\arabic{LWR@tempcountone}}[\LWR@strresulttwo]%
```

Get the contents of the first group in \LWR@strresulttwo:

```
7682 \exporegroups%
7683 \StrChar{\LWR@strresulttwo}{1}[\LWR@strresulttwo]%
7684 \noexporegroups%
7685 }
```

## 72.8 Parsing @, >, <, !, bar columns

Holds the parsed argument for @, >, <, or ! columns:

```
7686 \newcommand*{\LWR@colparameter}{}%
```

\LWR@parseatcolumn Handles {@text} columns.

```
7687 \newcommand*{\LWR@parseatcolumn}{%
```

Move to the next token after the '@':

```
7688 \LWR@traceinfo{at column}%
7689 \defaddtocounter{\LWR@tablecolsindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
7690 \LWR@traceinfo{about to read the next token}%
7691 \expandarg%
7692 \StrChar{\LWR@origcolspec}%
7693 {\arabic{\LWR@tablecolsindex}}[\LWR@colparameter]%
7694 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
7695 \LWR@traceinfo{have now read the next token}%
7696 \ifnumcomp{\value{\LWR@tabletotalLaTeXcols}}{=}{0}%
7697 {%
7698   \LWR@traceinfo{at the left edge}%
7699   \LWR@setexparray{\LWR@colatspec}%
7700   {\leftedge}%
7701   {\expandafter\@firstofone\LWR@colparameter}%
7702   \LWR@traceinfo{at the left edge: \%}%
7703   \LWR@getexparray{\LWR@colatspec}{\leftedge}%
7704 }%
7705 {%
7706   \LWR@traceinfo{not at the left edge}%
7707   \LWR@setexparray{\LWR@colatspec}%
7708   {\arabic{\LWR@tabletotalLaTeXcols}}%
7709   {\expandafter\@firstofone\LWR@colparameter}%
7710   \LWR@traceinfo{at \arabic{\LWR@tabletotalLaTeXcols}: \%}%
7711   \LWR@getexparray{\LWR@colatspec}{\arabic{\LWR@tabletotalLaTeXcols}}%
7712 }%
7713 \let\LWR@colparameter\relax%
7714 \booltrue{\LWR@validtablecol}%
7715 }
```

\LWR@parsebangcolumn Handles !{@text} columns.

```
7716 \newcommand*{\LWR@parsebangcolumn}{%
```

Move to the next token after the '!':

```
7717 \LWR@traceinfo{bang column}%
7718 \defaddtocounter{\LWR@tablecolsindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
7719 \LWR@traceinfo{about to read the next token:}%
7720 \expandarg%
7721 \StrChar{\LWR@origcols}%
7722 {\arabic{\LWR@tablecolsindex}}[\LWR@colparameter]%
7723 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
7724 \LWR@traceinfo{have now read the next token}%
7725 \ifnumcomp{\value{\LWR@tabletotalLaTeXcols}}{=}{0}%
7726 {%
7727   \LWR@traceinfo{at the left edge}%
7728   \LWR@setexparray{\LWR@colbangspec}%
7729   {\leftedge}%
7730   {\expandafter\@firstofone\LWR@colparameter}%
7731 }%
7732 {%
7733   \LWR@traceinfo{not at the left edge}%
7734   \LWR@setexparray{\LWR@colbangspec}%
7735   {\arabic{\LWR@tabletotalLaTeXcols}}%
7736   {\expandafter\@firstofone\LWR@colparameter}%
7737   \LWR@traceinfo{bang \arabic{\LWR@tabletotalLaTeXcols}: \LWR@colparameter!}%
7738 }%
7739 \let\LWR@colparameter\relax%
7740 \booltrue{\LWR@validtablecol}%
7741 }
```

\LWR@parsebeforecolumn Handles >{text} columns.

```
7742 \newcommand*{\LWR@parsebeforecolumn}{%
```

Move to the next token after the '>':

```
7743 \defaddtocounter{\LWR@tablecolsindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```
7744 \expandarg%
7745 \StrChar{\LWR@origcols}%
7746 {\arabic{\LWR@tablecolsindex}}[\LWR@colparameter]%
7747 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
7748 \LWR@setexparray{\LWR@colbeforespec}%
7749 {\arabic{\LWR@tabletotalLaTeXcolsnext}}%
7750 {\expandafter\@firstofone\LWR@colparameter}%
7751 \let\LWR@colparameter\relax%
```

```
7752     \booltrue{LWR@validtablecol}%
7753 }
```

\LWR@parseaftercolumn Handles <{text} columns.

```
7754 \newcommand*{\LWR@parseaftercolumn}{%
```

Move to the next token after the '<':

```
7755 \defaddtocounter{LWR@tablecolsindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```
7756 \expandarg%
7757 \StrChar{\LWR@origcols}{%
7758   {\arabic{LWR@tablecolsindex}}[\LWR@colparameter]}%
7759 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
7760 \LWR@setexpparray{LWR@col afterspec}%
7761   {\arabic{LWR@tabletotalLaTeXcols}}%
7762   {\expandafter\@firstofone\LWR@colparameter}%
7763 \let\LWR@colparameter\relax%
7764 \booltrue{LWR@validtablecol}%
7765 }
```

\LWR@parsebarcolumn Handles vertical rules.

```
7766 \newcommand*{\LWR@parsebarcolumn}{%
7767   \LWR@traceinfo{\LWR@parsebarcolumn}}%
```

Remember the bar at this position:

```
7768 \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
7769   {% left edge of the table:
7770     \edef\LWR@tempone{\LWR@getexpparray{LWR@colbarspec}{leftedge}}%
7771     \ifdefstring{\LWR@tempone}{tvertbarl}%
7772       {\LWR@setexpparray{LWR@colbarspec}{leftedge}{tvertbarldouble}}%
7773       {\LWR@setexpparray{LWR@colbarspec}{leftedge}{tvertbarl}}%
7774   }%
7775   {% not at the left edge:
7776     \edef\LWR@tempone{%
7777       \LWR@getexpparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}}%
7778     \ifdefstring{\LWR@tempone}{tvertbarr}%
7779       {%
7780         \LWR@setexpparray{LWR@colbarspec}{%
7781           \arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdouble}}%
7782       {}%
7783     }%
7784   }%
7785 \LWR@setexpparray{LWR@colbarspec}{%
```

```

7786           {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarr}%
7787       }%
7788   }%
7789 \booltrue{LWR@validtablecol}%
7790 }

```

\LWR@parsecoloncolumn Handles vertical rules.

```

7791 \newcommand*{\LWR@parsecoloncolumn}{%
7792     \LWR@traceinfo{LWR@parsecoloncolumn}%

```

Remember the bar at this position:

```

7793 \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
7794     {% left edge of the table:
7795         \edef\LWR@tempone{\LWR@getexpparray{LWR@colbarspec}{leftedge}}%
7796         \ifdefstring{\LWR@tempone}{tvertbarldash}%
7797             {\LWR@setexpparray{LWR@colbarspec}{leftedge}{tvertbarldoubledash}}%
7798             {\LWR@setexpparray{LWR@colbarspec}{leftedge}{tvertbarldash}}%
7799     }%
7800     {% not at the left edge:
7801         \edef\LWR@tempone{%
7802             \LWR@getexpparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}}%
7803         \ifdefstring{\LWR@tempone}{tvertbarrdash}%
7804             {\LWR@setexpparray{LWR@colbarspec}{%
7805                 {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdoubledash}}}%
7806             {\LWR@setexpparray{LWR@colbarspec}{%
7807                 {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdash}}}%
7808         }%
7809     }%
7810 \booltrue{LWR@validtablecol}%
7811 }

```

\LWR@parsesemicoloncolumn Handles vertical rules.

```

7812 \newcommand*{\LWR@parsesemicoloncolumn}{%

```

Treat ; as a : column:

```

7813     \LWR@parsecoloncolumn%

```

Skip the following width token:

```

7814     \defaddtocounter{LWR@tablecolspeccindex}{1}%
7815 }

```

## 72.9 Parsing ‘l’, ‘c’, or ‘r’ columns

\LWR@parsonormalcolumn {*thiscolumn*}

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

```

7816 \newcommand*{\LWR@parsenormalcolumn}[1]{%
7817     \defaddtocounter{\LWR@tabletotalLaTeXcols}{1}%
7818     \defaddtocounter{\LWR@tabletotalLaTeXcolsnext}{1}%
7819     \LWR@setexpparray{\LWR@tablecolspec}{\arabic{\LWR@tabletotalLaTeXcols}}{#1}%
7820     \LWR@traceinfo{normal column \arabic{\LWR@tabletotalLaTeXcols}: #1}%
7821     \LWR@setexpparray{\LWR@colatspec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
7822     \LWR@setexpparray{\LWR@colbangspec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
7823     \LWR@setexpparray{\LWR@colbeforespec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
7824     \LWR@setexpparray{\LWR@colafterspec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
7825     \LWR@setexpparray{\LWR@colbarspec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
7826     \booltrue{\LWR@validtablecol}%
7827 }

```

## 72.10 Parsing ‘p’, ‘m’, or ‘b’ columns

\LWR@parsepcolumn {*thiscolumn*} The width will be ignored.

```
7828 \newcommand*{\LWR@parsepcolumn}[1]{%
```

Converts to the given column type:

```
7829     \LWR@parsenormalcolumn{#1}%

```

Skips the following width token:

```

7830     \defaddtocounter{\LWR@tablecolspecindex}{1}%
7831 }

```

## 72.11 Parsing ‘w’ columns

\LWR@parsewcolumn The width will be ignored.

```
7832 \newcommand*{\LWR@parsewcolumn}{}%
```

```

7833     \LWR@columnspecklookahead{1}%
7834     \expandafter\expandafter\expandafter{\LWR@strresulttwo}%

```

Skips the following width and alignment tokens:

```

7835     \defaddtocounter{\LWR@tablecolspecindex}{2}%
7836 }

```

## 72.12 Parsing '\*' columns

\LWR@parsestarcolumn Star columns should already have been expanded, so this should never be used.

```
7837 \newcommand*{\LWR@parsestarcolumn}{%
7838     \defaddtocounter{LWR@tablecolspecindex}{2}%
7839 }
```

## 72.13 Parsing 'D' columns

From the `dcolumn` package.

\LWR@parseDcolumn {<thiscolumn>} The three parameters will be ignored.

```
7840 \newcommand*{\LWR@parseDcolumn}[1]{%
```

Converts to the given column type.

```
7841     \LWR@parsenormalcolumn{#1}%
```

Skips the following three parameters.

```
7842     \defaddtocounter{LWR@tablecolspecindex}{3}%
7843 }
```

## 72.14 Expanding the star column specifications

Ctr \LWR@starcount Internal count for duplicating star columns.

```
7844 \newcount\LWR@starcount
```

\LWR@expcolspec Temporary storage used to build the expanded column specifier.

```
7845 \newcommand*{\LWR@expcolspec}{}%
```

Ctr \LWR@splitstarindex Indexes into the column specifiers.

```
7846 \newcounter{LWR@splitstarindex}
```

Ctr \LWR@splitstarcopies Number of copies.

```
7847 \newcounter{LWR@splitstarcopies}
```

\LWR@splitstarcontents Contents to duplicate.

```
7848 \newcommand*{\LWR@splitstarcontents}{}%
```

\expandcolspect Expands \LWR@origcolspect for star columns.

```
7849 \newcommand*{\expandcolspect}{%
```

Find the position of any star token.

```
7850     \StrPosition{\LWR@origcolspect}{*}[\LWR@tempone]%
```

Expand until no stars are found:

```
7851     \whileboolexpr{ test {\ifnumgreater{\LWR@tempone}{0}} }{%
7852         {%
```

Begin with any characters to the left of the star.

```
7853         \setcounter{\LWR@splitstarindex}{\LWR@tempone}%
7854         \addtocounter{\LWR@splitstarindex}{-1}%
7855         \StrLeft{\LWR@origcolspect}{\value{\LWR@splitstarindex}}[\LWR@expcolspect]%
```

Move past the star to remember its number of copies.

```
7856         \addtocounter{\LWR@splitstarindex}{2}%
7857         \StrChar{\LWR@origcolspect}{\value{\LWR@splitstarindex}}[\LWR@tempone]%
7858         \setcounter{\LWR@splitstarcopies}{\expandafter\@firstofone\LWR@tempone}%
```

Move past the number of copies and remember the contents.

```
7859         \addtocounter{\LWR@splitstarindex}{1}%
7860         \StrChar{\LWR@origcolspect}{\value{\LWR@splitstarindex}}[\LWR@splitstarcontents]%
```

For each copy, append the contents.

```
7861         \ifnumgreater{\value{\LWR@splitstarcopies}}{0}{%
7862             {%
7863                 \LWR@starcount=\value{\LWR@splitstarcopies}%
7864                 \loop
7865                     \appto{\LWR@expcolspect}{%
```

(Remove the enclosing braces.)

```
7866                     \expandafter\@firstofone\LWR@splitstarcontents}%
7867             }%
7868             \advance \LWR@starcount -1
7869             \ifnum \LWR@starcount>0 \repeat
7870         }{}}
```

Remove any token to the left, and append the rightmost remaining tokens.

```
7871         \StrGobbleLeft{\LWR@origcolspect}{\value{\LWR@splitstarindex}}[\colspectremainder]%
7872             \appto{\LWR@expcolspect}{\colspectremainder}%
```

Remember the final result.

```
7873         \edef{\LWR@origcolspect}{\LWR@expcolspect}%
```

Table 10: Tabular baseline

1	p	m	b	r
			bot	
			mid	bot
1	par	mid	bot	r
	par	mid		
		par		

See if more stars exist.

```
7874     \StrPosition{\LWR@origcolspec}{*}[\LWR@tempone]%
7875   }%
7876 }
```

## 72.15 Parsing the column specifications

### ⚠ tabular baselines

HTML CSS cannot exactly match the L<sup>A</sup>T<sub>E</sub>X concept of a baseline for a table row. Table 10 shows the L<sup>A</sup>T<sub>E</sub>X results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the p column specification in table 11 for details.

Table 11 describes how each kind of column is converted to HTML.

```
\LWR@parsetablecols {\<colspecs>}
```

Scans the column specification left to right.

Builds \LWR@tablecolspec with the final specification, one L<sup>A</sup>T<sub>E</sub>X column per entry. The final number of L<sup>A</sup>T<sub>E</sub>X columns in each row is stored in \LWR@tabletotalLaTeXcols, which is the number of & and \\ in each line, but which does not include @, !, <, > specifications in the count.

```
7877 \newcommand*{\LWR@parsetablecols}[1]{%
7878   \LWR@traceinfo{\LWR@parsetablecols}{%
```

Remember the original supplied column spec:

```
7879 \renewcommand*{\LWR@origcolspec}{#1}{%
```

Remove spaces:

```
7880 \expandarg%
7881 \StrSubstitute{\LWR@origcolspec}{ }{}[\LWR@origcolspec]{%
```

Expand any star columns:

```
7882 \expandcolspec{}
```

Table 11: Tabular HTML column conversions

- 
- l, r, c:** Converted to table cells without paragraph tags.  
Uses css vertical-align:middle so that top or bottom-aligned cells may go above or below this cell.
- p:** Converted to table cells with paragraph tags. Ref: Table 10, L<sup>A</sup>T<sub>E</sub>X places the top line of a parbox aligned with the rest of the text line, so css vertical-align:bottom is used to have the HTML result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the HTML conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the css may be desired, changing td.tdp, td.tdP, td.tdprule, and td.tdPrule to vertical-align: middle. Another possibility is to change L,R,C, and P to vertical-align: top and not worry about the alignment of B and M cells or trying to approximate L<sup>A</sup>T<sub>E</sub>X baselines.
- m:** With paragraph tags, css vertical-align:middle.
- b:** With paragraph tags, css vertical-align:top so that the bottom of the text is closest to the middle of the text line.
- P, M, B:** Horizontally-centered versions.
- S:** Converted to 'r'. Ignores optional argument. From the siunitx package.
- D:** Converted to 'c'. From the dcolumn package.
- @, !, >, <:** One each, in that order.
- |:** Vertical rule.
- Unknown:** Converted to 'l'.
- \newcolumn:** Currently treated as unknown.
-

The parsed column spec data array, `LWR@tablecols`, will be overwritten with new values.

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```

7883  \defcounter{LWR@tabletotalLaTeXcols}{0}%
7884  \defcounter{LWR@tabletotalLaTeXcolsnext}{1}%
7885  \LWR@setexparray{\LWR@colat{spec}}{\leftedge}{}%
7886  \LWR@setexparray{\LWR@colat{spec}}{1}{}%
7887  \LWR@setexparray{\LWR@colat{spec}}{2}{}%
7888  \LWR@setexparray{\LWR@colat{spec}}{3}{}%
7889  \LWR@setexparray{\LWR@colbang{spec}}{\leftedge}{}%
7890  \LWR@setexparray{\LWR@colbang{spec}}{1}{}%
7891  \LWR@setexparray{\LWR@colbang{spec}}{2}{}%
7892  \LWR@setexparray{\LWR@colbang{spec}}{3}{}%
7893  \LWR@setexparray{\LWR@colbefore{spec}}{1}{}%
7894  \LWR@setexparray{\LWR@colbefore{spec}}{2}{}%
7895  \LWR@setexparray{\LWR@colbefore{spec}}{3}{}%
7896  \LWR@setexparray{\LWR@colafterspec}{1}{}%
7897  \LWR@setexparray{\LWR@colafterspec}{2}{}%
7898  \LWR@setexparray{\LWR@colafterspec}{3}{}%
7899  \LWR@setexparray{\LWR@colbars}{\leftedge}{}%
7900  \LWR@setexparray{\LWR@colbars}{1}{}%
7901  \LWR@setexparray{\LWR@colbars}{2}{}%
7902  \LWR@setexparray{\LWR@colbars}{3}{}%

```

Starting at the first column specification:

```
7903  \defcounter{LWR@tablecolsindex}{1}%
```

Place the colspecs string length into `\LWR@strresult`, and remember the number of characters in the column specification:

```

7904  \expandarg%
7905  \StrLen{\LWR@origcolspec}[\LWR@strresult]%
7906  \fullexpandarg%
7907  \LWR@traceinfo{original column spec length: \LWR@strresult}%
7908  \defcounter{LWR@tablecolswidth}{\LWR@strresult}%

```

Haven't seen any optional arguments so far

```
7909  \boolfalse{LWR@opttablecol}%
```

Scan through the column specifications:

```

7910  \whileboolexpr{%
7911    not test{%
7912      \ifnumcomp{\value{LWR@tablecolsindex}}{>}{%
7913        \value{LWR@tablecolswidth}}%
7914      }%
7915    }%
7916    {%

```

Place the next single-character column type into \LWR@strresult:

```
7917     \expandarg%
7918     \StrChar{\LWR@origcolspec}{\arabic{LWR@tablecolspecindex}}[\LWR@strresult]%
7919     \LWR@traceinfo{position \arabic{LWR@tablecolspecindex}: \LWR@strresult}%
7920     \fullexpandarg%
```

Not yet found a valid column type:

```
7921     \boolearn{\LWR@validtablecol}%
```

Skip over any optional arguments, such as siunitx S column:

```
7922     \IfStrEq{\LWR@strresult}{}{\booltrue{\LWR@opttablecol}}{}
```

Throw away anything found inside the optional argument:

```
7923     \ifbool{\LWR@opttablecol}%
7924     {}% inside an optional argument
7925     {}% not an optional tabular argument
```

Not inside an optional argument, so consider the column type:

```
7926     \IfStrEq{\LWR@strresult}{l}{\LWR@parsenormalcolumn{l}}{%
7927     \IfStrEq{\LWR@strresult}{c}{\LWR@parsenormalcolumn{c}}{%
7928     \IfStrEq{\LWR@strresult}{r}{\LWR@parsenormalcolumn{r}}{%
7929     \IfStrEq{\LWR@strresult}{L}{\LWR@parsenormalcolumn{l}}{%
7930     \IfStrEq{\LWR@strresult}{C}{\LWR@parsenormalcolumn{c}}{%
7931     \IfStrEq{\LWR@strresult}{R}{\LWR@parsenormalcolumn{r}}{%
7932     \IfStrEq{\LWR@strresult}{J}{\LWR@parsenormalcolumn{l}}{%
7933     \IfStrEq{\LWR@strresult}{S}{\LWR@parsenormalcolumn{c}}{%
7934     \IfStrEq{\LWR@strresult}{s}{\LWR@parsenormalcolumn{c}}{%
7935     \IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@parseatcolumn}{%
7936     \IfStrEq{\LWR@strresult}{!}{\LWR@parsebangcolumn}{%
7937     \IfStrEq{\LWR@strresult}{>}{\LWR@parsebeforecolumn}{%
7938     \IfStrEq{\LWR@strresult}{<}{\LWR@parseaftercolumn}{%
7939     \IfStrEq{\LWR@strresult}{|}{\LWR@parsebarcolumn}{%
7940     \IfStrEq{\LWR@strresult}{:}{\LWR@parsecoloncolumn}{%
7941     \IfStrEq{\LWR@strresult}{;}{\LWR@parsesemicoloncolumn}{%
7942     \IfStrEq{\LWR@strresult}{p}{\LWR@parsepcolumn{p}}{%
7943     \IfStrEq{\LWR@strresult}{m}{\LWR@parsepcolumn{m}}{%
7944     \IfStrEq{\LWR@strresult}{b}{\LWR@parsepcolumn{b}}{%
7945     \IfStrEq{\LWR@strresult}{w}{\LWR@parsewcolumn}{%
7946     \IfStrEq{\LWR@strresult}{W}{\LWR@parsewcolumn}{}}
```

A star column:

```
7947     \IfStrEq{\LWR@strresult}{*}{\LWR@parsestarcolumn}{}
```

From the `dcolumn` package:

```
7948 \IfStrEq{\LWR@strresult}{D}{\LWR@parseDcolumn{c}}{}%
```

From the `tabularx` package. X column has no parameter, but will be given paragraph tags.

```
7949 \IfStrEq{\LWR@strresult}{X}{\LWR@parsenormalcolumn{X}}{}%
```

Many people define centered versions “P”, “M”, and “B”:

```
\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}
```

```
7950 \IfStrEq{\LWR@strresult}{P}{\LWR@parsepcolumn{P}}{}%
7951 \IfStrEq{\LWR@strresult}{M}{\LWR@parsepcolumn{M}}{}%
7952 \IfStrEq{\LWR@strresult}{B}{\LWR@parsepcolumn{B}}{}%
```

If this column was an invalid column type, convert it to an `l` column:

```
7953 \ifbool{\LWR@validtablecol}{}{%
7954   \LWR@traceinfo{invalid column type: \LWR@strresult}%
7955   \LWR@parsenormalcolumn{l}%
7956 }%
7957 }% not an optional column argument
```

If read the closing bracket, no longer inside the optional argument:

```
7958 \IfStrEq{\LWR@strresult}{}{\boolfalse{\LWR@opttablecol}}{}%
```

Move to the next character:

```
7959 \defaddtocounter{\LWR@tablecolsindex}{1}%
7960 }% whiledo
7961 }%
```

## 72.16 `colortbl` and `xcolor` tabular color support

These macros provide a minimal emulation of some `colortbl` macros which might appear between table cells. If `colortbl` is loaded, these macros will be replaced with functional versions.

For each of the `HTML` colors below, the text for the `HTML` color is set if requested, but the macro is empty if none has been set.

`\rownum` Reserve a counter register.

```
7962 \@ifndef{\rownum}{\newcount\rownum}{}%
```

\@rowcolors Emulated in case **xcolor** is not used.

7963 \newcommand\*{\@rowcolors}{}{}

\@rowc@lors Emulated in case **xcolor** is not used.

7964 \newcommand\*{\@rowc@lors}{}{}

\LWR@xcolorrowHTMLcolor Emulated **xcolor** row color.

7965 \newcommand\*{\LWR@xcolorrowHTMLcolor}{}{}

\LWR@columnHTMLcolor HTMLstyle code for the column color.

7966 \def\LWR@columnHTMLcolor{}{}

\LWR@rowHTMLcolor HTMLstyle code for the row color.

7967 \def\LWR@rowHTMLcolor{}{}

\LWR@cellHTMLcolor HTMLstyle code for the cell color.

7968 \def\LWR@cellHTMLcolor{}{}

\LWR@ruleHTMLcolor HTMLstyle code for the rule color.

7969 \newcommand\*{\LWR@ruleHTMLcolor}{}{}

\rowcolor [⟨model⟩] {⟨color⟩} [⟨left overhang⟩] [⟨right overhang⟩] Print version. The HTML version is in **lwarp-colortbl**. Used before starting a tabular data cell, thus \LWR@getmynexttoken.

7970 \newcommand\*{\rowcolor}{\LWR@getmynexttoken}%

\arrayrulecolor [⟨model⟩] {⟨color⟩}

\arrayrulecolornexttoken [⟨model⟩] {⟨color⟩}

Print versions for use outside and inside a tabular:

7971 \newcommand{\arrayrulecolor}[2][named]{}{}

7972 \newcommand{\arrayrulecolornexttoken}[2][named]{\LWR@getmynexttoken}

\doublerulesepcolor [⟨model⟩] {⟨color⟩}

\doublerulesepcolornexttoken [⟨model⟩] {⟨color⟩}

Print versions for use inside and outside a tabular:

7973 \newcommand{\doublerulesepcolor}[2][named]{}{}

7974 \newcommand{\doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}

## 72.17 Starting a new row

\LWR@maybenewtablerow If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for hline or tbrule if necessary.

```
7975 \newcommand*{\LWR@maybenewtablerow}{%
7976 {%
7977     \ifbool{\LWR@startedrow}{%
7978         {}% started the row
7979         {}% not started the row
7980             \booltrue{\LWR@startedrow}%
7981             \ifboolexpr{%
7982                 \ifnumcomp{\value{\LWR@hlines}}{>}{0}{} or%
7983                 \ifnumcomp{\value{\LWR@hdashedlines}}{>}{0}{}%
7984             }%
7985             {}%
7986             {}%
7987             \LWR@htmltag{tr class="hline"}%
7988             \LWR@orignewline%
7989             }%
7990             {}% not doing hline
7991             \ifbool{\LWR@doingtbrule}{%
7992                 {}%
7993                 \ifdefvoid{\LWR@ruleHTMLcolor}{%
7994                     \LWR@htmltag{tr class="tbrule"}%
7995                 }{%
7996                     \LWR@htmltag{%
7997                         tr class="tbrule" % space
7998                         style="border-top: 1px solid % space
7999                             \LWR@origpound\LWR@ruleHTMLcolor "%
8000                     }%
8001                 }%
8002                 \LWR@orignewline%
8003             }%
8004             {} \LWR@htmltag{tr}\LWR@orignewline}%
8005             }% end of not doing hline
8006             }% end of not started the row
8007 }
```

Remember that now have started the row:

```
7980             \booltrue{\LWR@startedrow}%
7981             \ifboolexpr{%
7982                 \ifnumcomp{\value{\LWR@hlines}}{>}{0}{} or%
7983                 \ifnumcomp{\value{\LWR@hdashedlines}}{>}{0}{}%
7984             }%
7985             {}%
7986             {}%
7987             \LWR@htmltag{tr class="hline"}%
7988             \LWR@orignewline%
7989             }%
7990             {}% not doing hline
7991             \ifbool{\LWR@doingtbrule}{%
7992                 {}%
7993                 \ifdefvoid{\LWR@ruleHTMLcolor}{%
7994                     \LWR@htmltag{tr class="tbrule"}%
7995                 }{%
7996                     \LWR@htmltag{%
7997                         tr class="tbrule" % space
7998                         style="border-top: 1px solid % space
7999                             \LWR@origpound\LWR@ruleHTMLcolor "%
8000                     }%
8001                 }%
8002                 \LWR@orignewline%
8003             }%
8004             {} \LWR@htmltag{tr}\LWR@orignewline}%
8005             }% end of not doing hline
8006             }% end of not started the row
8007 }
```

Create the row tag, with a class if necessary.

```
7981             \booltrue{\LWR@intabularmetadata}%
7982             \ifboolexpr{%
7983                 \test{\ifnumcomp{\value{\LWR@hlines}}{>}{0}{} or%
7984                     \test{\ifnumcomp{\value{\LWR@hdashedlines}}{>}{0}{}%
7985                 }%
7986                 {}%
7987                 \LWR@htmltag{tr class="hline"}%
7988                 \LWR@orignewline%
7989                 }%
7990                 {}% not doing hline
7991                 \ifbool{\LWR@doingtbrule}{%
7992                     {}%
7993                     \ifdefvoid{\LWR@ruleHTMLcolor}{%
7994                         \LWR@htmltag{tr class="tbrule"}%
7995                     }{%
7996                         \LWR@htmltag{%
7997                             tr class="tbrule" % space
7998                             style="border-top: 1px solid % space
7999                                 \LWR@origpound\LWR@ruleHTMLcolor "%
8000                         }%
8001                     }%
8002                     \LWR@orignewline%
8003                 }%
8004                 {} \LWR@htmltag{tr}\LWR@orignewline}%
8005                 }% end of not doing hline
8006                 }% end of not started the row
8007 }
```

## 72.18 Printing vertical bar tags

\LWR@printbartag {\langle index\rangle}

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```
8008 \newcommand*{\LWR@printbartag}[1]{%
```

```

8009  \LWR@traceinfo{\LWR@printbartag !#1!}%
8010  \ifboolexpr{bool{\LWR@tabularmutemods} or bool{\LWR@emptyatbang}}%
8011  {}% muting or empty
8012  {% not muting
8013      \edef\LWR@tempone{\LWR@getexparray{\LWR@colbarspec}{#1}}%
8014      \ifdefempty{\LWR@tempone}{}{\LWR@tempone}%
8015  }% not muting
8016  \LWR@traceinfo{\LWR@printbartag done}%
8017 }
```

## 72.19 Printing @ or ! tags

```
\LWR@printatbang {\langle at -or- bang\rangle} {\langle index\rangle}

8018 \newcommand*{\LWR@printatbang}[2]{%
```

Fetch the column at or bang spec:

```

8019  \xdef\LWR@atbangspec{\LWR@getexparray{\LWR@col#1spec}{#2}}%
8020  \LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}%
```

Only generate if is not empty:

```

8021  \ifdefempty{\LWR@atbangspec}%
8022  {}%
8023  {% not empty
8024      \LWR@htmltag{%
8025          td class="td#1"
8026          \LWR@subaddcmidruletrim{}{}%
8027          \LWR@printbartag{#2}%
8028          "%
8029          \LWR@tdstartstyles%
8030          \LWR@addcmidrulewidth%
8031          \LWR@addcdashline%
8032          \LWR@addtabularrulecolors%
8033          \LWR@tdendstyles%
8034      }%
```

Create an empty cell if muting for the \bottomrule:

```

8035  \ifboolexpr{bool{\LWR@tabularmutemods} or bool{\LWR@emptyatbang}}%
8036  {}%
8037  {\LWR@atbangspec}%
8038 %
8039  \LWR@htmltag{/td}\LWR@orignewline%
8040  \global\booltrue{\LWR@tabularcelladded}%
8041  }% not empty
8042 }%
```

```
\LWR@addleftmostbartag
```

```

8043 \newcommand*{\LWR@addleftmostbartag}{%
8044     \ifnumcomp{\value{\LWR@tableLaTeXcolindex}}{=}{1}{%
8045         \LWR@printbartag{leftedge}%
8046     }{}%
8047 }

\LWR@tabularleftedge

8048 \newcommand*{\LWR@tabularleftedge}{%
8049     \ifnumcomp{\value{\LWR@tableLaTeXcolindex}}{=}{1}{%
8050         \LWR@printatbang{at}{leftedge}%
8051         \LWR@printatbang{bang}{leftedge}%
8052     }% left edge
8053     {}% not left edge
8054 }
8055 }
```

## 72.20 Data opening tag

\LWR@thiscolspec Temporary storage.

```
8056 \newcommand*{\LWR@thiscolspec}{}%
```

\LWR@tabledatasinglecolumntag Print a table data opening tag with style for alignment and color.

```

8057 \newcommand*{\LWR@tabledatasinglecolumntag}{%
8058 {%
8059     \LWR@traceinfo{\LWR@tabledatasinglecolumntag}%
8060     \LWR@maybenewtablerow%
```

Don't start a new paragraph tag if have already started one:

```

8061     \ifbool{\LWR@intabularmetadata}{%
8062         \%
```

If have found the end of tabular command, do not create the next data cell:

```

8063         \ifbool{\LWR@exittingtabular}{}{%
8064             \% not exiting tabular}
```

Print the @ and ! contents before first column:

```
8065             \LWR@tabularleftedge%
```

Fetch the current column's alignment character into \LWR@strresult:

```

8066             \xdef\LWR@strresult{%
8067                 \LWR@getexparray{\LWR@tablecolspe}{\arabic{\LWR@tableLaTeXcolindex}}%
8068             }%
```

print the start of a new table data cell:

```
8069      \LWR@traceinfo{\LWR@tabledatasinglecolumntag: about to print td tag}%
8070          \LWR@htmltag{%
8071              td class="td%"
```

append this column's spec:

```
8072          \LWR@strresult%
```

If this column has a cmidrule, add “rule” to the end of the HTML class tag. Also add vertical bar tags.

```
8073          \LWR@addcmidruletrim%
8074          \LWR@addleftmostbartag%
8075          \LWR@printbartag{\arabic{\LWR@tableLaTeXcolindex}}%
8076          "%
```

Add styles for rules, alignment:

```
8077          \LWR@tdstartstyles%
8078          \LWR@addcmidrulewidth%
8079          \LWR@addcdashline%

8080          \xdef\LWR@thiscolspec{%
8081              \LWR@getexparray{\LWR@tablecolspec}%
8082                  {\arabic{\LWR@tableLaTeXcolindex}}%
8083          }%
8084          \LWR@addformatwpalignment{\LWR@thiscolspec}%
```

Add styles for cell and rule colors:

```
8085          \LWR@addtabularrowcolor%
8086          \LWR@addtabularrulecolors%

8087          \LWR@tdendstyles%
8088      }% HTML td
8089      \LWR@traceinfo{\LWR@tabledatasinglecolumntag: done printing td tag}%
```

If this is a p, m, b, or X column, allow paragraphs:

```
8090          \ifboolexpr{%
8091              test{ \ifdefstring{\LWR@strresult}{p} } or
8092              test{ \ifdefstring{\LWR@strresult}{m} } or
8093              test{ \ifdefstring{\LWR@strresult}{b} } or
8094              test{ \ifdefstring{\LWR@strresult}{P} } or
8095              test{ \ifdefstring{\LWR@strresult}{M} } or
8096              test{ \ifdefstring{\LWR@strresult}{B} } or
8097              test{ \ifdefstring{\LWR@strresult}{X} }
8098          }%
8099          {% allow pars
8100          \LWR@traceinfo{\LWR@tabledatasinglecolumntag: about to LWR@startpars}%
8101          \booltrue{\LWR@tableparcell}%
}
```

---

```

8102          \LWR@startpars%
8103          \LWR@traceinfo{\LWR@tabledata singlecolumn tag: done with \LWR@startpars}%
8104          }% allow pars
8105          {}% no pars

```

Print the > contents unless muted for the \bottomrule:

```

8106          \ifboolexpr{bool{\LWR@tabularmutemods} or bool{\LWR@emptyatbang}}%
8107          {}%
8108          {}%
8109          \LWR@getexparray{\LWR@colbeforespec}{\arabic{\LWR@tableLaTeXcolindex}}%
8110          }%
8111          \boolefalse{\LWR@intabularmetadata}%
8112          }% not exiting tabular
8113      }{}% in tabular metadata
8114      \LWR@traceinfo{\LWR@tabledata singlecolumn tag: done}%
8115 }%

```

## 72.21 Midrules

`LWR@midrules` `LWR@midrules` is a data array (section 42) of columns each containing a non-zero width if a midrule should be created for this column.

`LWR@trimlrules` `LWR@trimlrules` is a data array (section 42) of columns containing `l` if a midrule should be left trimmed for each column.

`LWR@trimrrules` `LWR@trimrrules` is a data array (section 42) of columns containing `r` if a midrule should be right trimmed for each column.

`LWR@cdashlines` `LWR@cdashlines` is a data array (section 42) of columns each containing a `Y` if an `arydshln` package "cdashed line" should be created for this column.

`Len \LWR@heavyrulewidth` The default width of the rule.

```

8116 \newlength{\LWR@heavyrulewidth}
8117 \setlength{\LWR@heavyrulewidth}{.08em}

```

`Len \LWR@lightrulewidth` The default width of the rule.

```

8118 \newlength{\LWR@lightrulewidth}
8119 \setlength{\LWR@lightrulewidth}{.05em}

```

`Len \LWR@cmidrulewidth` The default width of the rule.

```

8120 \newlength{\LWR@cmidrulewidth}
8121 \setlength{\LWR@cmidrulewidth}{.03em}

```

`Len \LWR@thiscmidrulewidth` The width of the next rule, defaulting to `\LWR@cmidrulewidth`.

If not `\LWR@cmidrulewidth`, a style will be used to generate the custom width.

Assigned from the `LWR@midrules` array.

```

8122 \newlength{\LWR@thiscmidrulewidth}
8123 \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}

```

\LWR@clearmidrules Start new midrules. Called at beginning of tabular and also at \\.

Clears all LWR@midrules and LWR@trimrules markers for this line.

```

8124 \newcommand*{\LWR@clearmidrules}
8125 {%
8126   \defcounter{LWR@midrulecounter}{1}%
8127   \whileboolexpr{%
8128     not test{%
8129       \ifnumcomp{\value{LWR@midrulecounter}}{>}{%
8130         {\value{LWR@tabletotalLaTeXcols}}%
8131       }%
8132     }%
8133   {%
8134     \LWR@setexpparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{0pt}%
8135     \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
8136     \LWR@setexpparray{LWR@trimlrules}{\arabic{LWR@midrulecounter}}{}%
8137     \LWR@setexpparray{LWR@trimrrules}{\arabic{LWR@midrulecounter}}{}%
8138     \LWR@setexpparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{N}%
8139     \defaddtocounter{LWR@midrulecounter}{1}%
8140   }%
8141 }

```

\LWR@subcmidrule {[*width*] [*trim*] {[*leftcolumn*] [*rightcolumn*]}}

Marks LWR@midrules data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```

8142 \newcommand*{\LWR@subcmidrule}[4]{%
8143   \defcounter{LWR@midrulecounter}{#3}%
8144   \whileboolexpr{%
8145     not test {%
8146       \ifnumcomp{\value{LWR@midrulecounter}}{>}{#4}%
8147     }%
8148   }%
8149   {%
8150     \LWR@setexpparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{#1}%
8151     \defaddtocounter{LWR@midrulecounter}{1}%
8152   }% whiledo
8153   \IfSubStr{#2}{l}{\LWR@setexpparray{LWR@trimlrules}{#3}{l}}{}%
8154   \IfSubStr{#2}{r}{\LWR@setexpparray{LWR@trimrrules}{#4}{r}}{}%
8155   \booltrue{LWR@doingcmidrule}%
8156 }

```

\LWR@docmidrule {[*width*] (*trim*) {[*leftcolumn-rightcolumn*]}}

Marks LWR@midrules array elements to be a non-zero width from left to right columns.  
Also marks trimming for the L and/or R columns.

```
8157 \NewDocumentCommand{\LWR@docmidrule}{%
8158   O{\LWR@cmidrulewidth} D(){} >{\SplitArgument{1}{-}m}%
8159   {\LWR@subcmidrule{#1}{#2}#3}
```

\LWR@subcdashline {<leftcolumn>} {<rightcolumn>}

Marks LWR@cdashlines data array elements to be Y from left to right columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
8160 \newcommand*{\LWR@subcdashline}[2]{%
8161   \defcounter{LWR@midrulecounter}{#1}%
8162   \whileboolexpr{%
8163     not test {%
8164       \ifnumcomp{\value{LWR@midrulecounter}}{>}{#2}%
8165     }%
8166   }%
8167   {%
8168     \LWR@setexpparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{Y}%
8169     \defaddtocounter{LWR@midrulecounter}{1}%
8170   }%
8171   \booltrue{LWR@doingcmidrule}%
8172 }
```

\LWR@docdashline {<leftcolumn-rightcolumn>}

Marks LWR@cdashlines data array elements to be Y from left to right columns.

```
8173 \NewDocumentCommand{\LWR@docdashline}{%
8174   >{\SplitArgument{1}{-}m}%
8175   {%
8176     \LWR@subcdashline#1%
8177   }}
```

Used to compute margins, tabular trims, column offsets:

```
8178 \newlength{\LWR@templengthone}%
8179 \newlength{\LWR@templengthtwo}%
8180 \newlength{\LWR@templengththree}%
8181 \newcounter{LWR@tempcountone}
```

\LWR@tdstartstyles Begins possibly adding a table data cell style.

```
8182 \newcommand*{\LWR@tdstartstyles}{\boolfalse{LWR@tdhavecellstyle}}
```

\LWR@tdaddstyle Starts adding a table data cell style.

```

8183 \newcommand*{\LWR@tdaddstyle}{%
8184     \ifbool{\LWR@tdhavecellstyle}{%
8185         {; }%
8186         { style="}%
8187     \booltrue{\LWR@tdhavecellstyle}%
8188 }

```

\LWR@tdendstyles Finishes possibly adding a table data cell style. Prints the closing quote.

```

8189 \newcommand*{\LWR@tdendstyles}{%
8190     \ifbool{\LWR@tdhavecellstyle}{%
8191         {%
8192             "%
8193             \boolfalse{\LWR@tdhavecellstyle}%
8194         }{}}%
8195 }

```

\LWR@subaddcmidruletrim {<lefttrim>} {<righttrim>} Adds a \cmidrule with optional trim.

```

8196 \newcommand*{\LWR@subaddcmidruletrim}[2]{%
8197     \setlength{\LWR@templengthone}{%
8198         \LWR@getexpparray{\LWR@midrules}{\arabic{\LWR@tableLaTeXcolindex}}{}}%
8199     }%
8200     \ifdimcomp{\LWR@templengthone}{>}{0pt}{%
8201         {%

```

Print the class with left and right trim letters appended:

```
8202         \LWR@origtilde tdrule#1#2%
```

Remember the width of the rule:

```

8203         \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
8204     }%
8205     {%
8206         \setlength{\LWR@thiscmidrulewidth}{0pt}%
8207     }%
8208 }

```

\LWR@addcmidruletrim Adds left or right trim to a \cmidrule.

```

8209 \newcommand*{\LWR@addcmidruletrim}{%
8210     \LWR@subaddcmidruletrim{%
8211         {\LWR@getexpparray{\LWR@trimlrules}{\arabic{\LWR@tableLaTeXcolindex}}{}}{}}%
8212         {\LWR@getexpparray{\LWR@trimrrules}{\arabic{\LWR@tableLaTeXcolindex}}{}}{}}%
8213 }

```

\LWR@addrulewidth {<thiswidth>} {<defaultwidth>}

If not default width, add a custom style with width and color depending on thiswidth.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
8214 \newcommand{\LWR@addrulewidth}[2]{%
```

Only add a custom width if `thiswidth` is different than the `defaultwidth`, or if a color is being used:

```
8215   \ifboolexpr{%
8216     test{\ifdimcomp{#1}{=}{0pt}} or
8217     (
8218       ( test{\ifdimcomp{#1}{=}{#2}} and not bool{FormatWP} )
8219       and ( test {\ifdefvoid{\LWR@ruleHTMLcolor}} )
8220     )
8221   }%
8222   {}% default width and color
8223   {% custom width and/or color
```

Ensure that the width is wide enough to display in the browser:

```
8224   \LWR@forceminwidth{#1}%
```

Begin adding another style:

```
8225   \LWR@tdaddstyle%
```

The style itself:

```
8226   border-top:\LWR@printlength{\LWR@atleastonept} solid % space
```

If default gray, the darkness of the color depends on the thickness of the rule:

```
8227   \ifdefvoid{\LWR@ruleHTMLcolor}{%
8228     \ifdimcomp{#1}{<}{\LWR@lightrulewidth}{%
8229       {\LWR@origpound{}A0A0A0}%
8230       {% lightrule or heaver
8231         \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}{%
8232           {\LWR@origpound{}808080}%
8233           {black}%
8234         {% lightrule or heavier
8235       }{%
8236         \LWR@origpound{\LWR@ruleHTMLcolor}%
8237       }%
8238     }% custom width and/or color
8239 }
```

`\LWR@addcmidrulewidth` Adds a style for the rule width.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
8240 \newcommand{\LWR@addcmidrulewidth}{%
8241   \LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
8242 }
```

\LWR@addcdashline Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```

8243 \newcommand{\LWR@addcdashline}{%
8244     \edef\LWR@tempone{%
8245         \LWR@getexparray[LWR@cdashlines]{\arabic{LWR@tableLaTeXcolindex}}%
8246     }%
8247     \ifdefstring{\LWR@tempone}{Y}{%
8248         \LWR@tdaddstyle%
8249         border-top: 1pt dashed %
8250         \ifdefvoid{\LWR@ruleHTMLcolor}{%
8251             {black}%
8252             {\LWR@origpound\LWR@ruleHTMLcolor}%
8253         }{%
8254     }%
8254 }

```

\LWR@WPcell {\text-align} {\vertical-align}

```

8255 \newcommand*{\LWR@WPcell}[2]{%
8256     \LWR@tdaddstyle%
8257     \LWR@print@mbox{text-align:#1}; \LWR@print@mbox{vertical-align:#2}%
8258 }

```

\LWR@addformatwpalignment If FormatWP, adds a style for the alignment.

Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```

8259 \newcommand*{\LWR@addformatwpalignment}[1]{%
8260     \ifbool{FormatWP}{%
8261         \IfSubStr{#1}{l}{\LWR@WPcell{left}{middle}}{}%
8262         \IfSubStr{#1}{c}{\LWR@WPcell{center}{middle}}{}%
8263         \IfSubStr{#1}{r}{\LWR@WPcell{right}{middle}}{}%
8264         \IfSubStr{#1}{p}{\LWR@WPcell{left}{bottom}}{}%
8265         \IfSubStr{#1}{m}{\LWR@WPcell{left}{middle}}{}%
8266         \IfSubStr{#1}{b}{\LWR@WPcell{left}{top}}{}%
8267         \IfSubStr{#1}{P}{\LWR@WPcell{center}{bottom}}{}%
8268         \IfSubStr{#1}{M}{\LWR@WPcell{center}{middle}}{}%
8269         \IfSubStr{#1}{B}{\LWR@WPcell{center}{top}}{}%
8270     }{%
8271 }

```

## 72.22 Cell colors

\LWR@addtabularrowcolor Adds a cell's row color style, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```

8272 \newcommand*{\LWR@addtabularrowcolor}{%
8273     \ifbool{LWR@tabularmutemods}{%
8274         \ifdefvoid{\LWR@rowHTMLcolor}{%
8275             \ifdefvoid{\LWR@xcolorrowHTMLcolor}{%
8276                 \% xcolor row color

```

```

8277          \LWR@tdaddstyle%
8278          background:\LWR@origpound\LWR@xcolorrowHTMLcolor%
8279      }%
8280  }%
8281 {%
8282     explicit row color
8283     \LWR@tdaddstyle%
8284     background:\LWR@origpound\LWR@rowHTMLcolor%
8285 }%
8286 }%
8287 }
```

\LWR@addtabularhrulecolor Adds a cell's horizontal rule color style, if needed.

```
8287 \newcommand*\LWR@addtabularhrulecolor{%
```

If either form of horizontal rule is requested:

```

8288 \ifboolexpr{%
8289     test{\ifnumcomp{\value{\LWR@hlines}}{>}{0}} or%
8290     test{\ifnumcomp{\value{\LWR@hdashedlines}}{>}{0}} or%
8291     bool{\LWR@doingtbrule}%
8292 }{%
```

If there is a no custom color:

```

8293 \ifdefvoid{\LWR@ruleHTMLcolor}{%
8294 }%
8295     \ifnumcomp{\value{\LWR@hlines}}{>}{1}{%
8296         \%
8297         \LWR@tdaddstyle%
8298         border-top: 4px double%
8299     }{%
8300     \ifnumcomp{\value{\LWR@hdashedlines}}{>}{1}{%
8301         \%
8302         \LWR@tdaddstyle%
8303         border-top: 2px dashed%
8304     }{%
8305     \ifnumcomp{\value{\LWR@hdashedlines}}{=}{1}{%
8306         \%
8307         \LWR@tdaddstyle%
8308         border-top: 1px dashed%
8309     }{}}{}}
```

If no color and not doubled or dashed, then add nothing, since a simpler rule is the default.

```
8310 }%
```

If there is a custom color:

```

8311 \%
8312 \ifnumcomp{\value{\LWR@hlines}}{>}{1}{%
8313 \%
8314 \LWR@tdaddstyle%
```

```

8315           border-top: 4px double \LWR@origpound\LWR@ruleHTMLcolor%
8316           }% else
8317           \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
8318           {%
8319             \LWR@tdaddstyle%
8320             border-top: 2px dashed \LWR@origpound\LWR@ruleHTMLcolor%
8321           }% else
8322           \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
8323           {%
8324             \LWR@tdaddstyle%
8325             border-top: 1px dashed \LWR@origpound\LWR@ruleHTMLcolor%
8326           }% else
8327             \LWR@tdaddstyle%
8328             border-top: 1px solid \LWR@origpound\LWR@ruleHTMLcolor%
8329           }%}
8330       }%
8331     }{%
8332   }

```

\LWR@addtabularrulecolors Adds a cell's rule color styles, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```
8333 \newcommand*{\LWR@addtabularrulecolors}{%
```

Custom horizontal rule color:

```
8334   \LWR@addtabularhrulecolor%
```

No vertical rules if finishing the tabular with a row of empty cells:

```
8335 \ifbool{LWR@tabularmutemods}{ }{%
```

If at the leftmost cell, possibly add a leftmost vertical rule:

```
8336 \ifnumequal{\value{LWR@tableLaTeXcolindex}}{1}{%
```

Fetch the left edge's vertical bar specification:

```
8337 \edef\LWR@tempone{\LWR@getexpparray{\LWR@colbarspec}{leftedge}}%
```

Add a custom style if a vertical bar was requested:

```

8338   \ifdefstring{\LWR@tempone}{tvertbarl}{%
8339     \LWR@tdaddstyle%
8340     border-left: 1px solid % space
8341     \LWR@vertruleHTMLcolor%
8342   }%
8343   \ifdefstring{\LWR@tempone}{tvertbarldouble}{%
8344     \LWR@tdaddstyle%
8345     border-left: 4px double % space
8346     \LWR@vertruleHTMLcolor%
8347   }%

```

```

8348         \ifdefstring{\LWR@tempone}{tvertbarldash}{%
8349             \LWR@tdaddstyle%
8350             border-left: 1px dashed % space
8351             \LWR@verruleHTMLcolor%
8352         }{%
8353         \ifdefstring{\LWR@tempone}{tvertbarldoubledash}{%
8354             \LWR@tdaddstyle%
8355             border-left: 2px dashed % space
8356             \LWR@verruleHTMLcolor%
8357         }{%
8358     }{%

```

Possibly add a right vertical rule for this cell:

```

8359         \edef\LWR@tempone{%
8360             \LWR@getexpparray{\LWR@colbarspec}{\arabic{\LWR@tableLaTeXcolindex}}%
8361         }%
8362         \ifdefstring{\LWR@tempone}{tvertbarr}{%

```

Add a custom style if a vertical bar was requested:

```

8363             \LWR@tdaddstyle%
8364             border-right: 1px solid \LWR@verruleHTMLcolor%
8365         }{%
8366         \ifdefstring{\LWR@tempone}{tvertbarrdouble}{%
8367             \LWR@tdaddstyle%
8368             border-right: 4px double \LWR@verruleHTMLcolor%
8369         }{%
8370         \ifdefstring{\LWR@tempone}{tvertbarrdash}{%
8371             \LWR@tdaddstyle%
8372             border-right: 1px dashed \LWR@verruleHTMLcolor%
8373         }{%
8374         \ifdefstring{\LWR@tempone}{tvertbarrdoubledash}{%
8375             \LWR@tdaddstyle%
8376             border-right: 2px dashed \LWR@verruleHTMLcolor%
8377         }{%
8378     }%
8379 }

```

\LWR@subaddtabularcellcolor {<HTML color>}

```

8380 \newcommand*{\LWR@subaddtabularcellcolor}[1]{%
8381     \LWR@htmltag{div class="cellcolor" style="%"
8382         background:\LWR@origpound{}{}#1 %
8383     }%
8384     \defaddtocounter{\LWR@cellcolordepth}{1}%
8385 }

```

\LWR@addtabularcellcolor Adds a cell color style, if needed.

```

8386 \newcommand*{\LWR@addtabularcellcolor}{%
8387     \ifdefvoid{\LWR@cellHTMLcolor}{%
8388     {%
8389         \ifdefvoid{\LWR@rowHTMLcolor}{%

```

```

8390      {%
8391          \ifdefvoid{\LWR@xcolorrowHTMLcolor}{%
8392              {%
8393                  \ifdefvoid{\LWR@columnHTMLcolor}{%
8394                      {}%
8395                      {\LWR@subaddtabularcellcolor{\LWR@columnHTMLcolor}}%
8396                  }%
8397                  {\LWR@subaddtabularcellcolor{\LWR@xcolorrowHTMLcolor}}%
8398              }%
8399              {\LWR@subaddtabularcellcolor{\LWR@rowHTMLcolor}}%
8400          }%
8401          {\LWR@subaddtabularcellcolor{\LWR@cellHTMLcolor}}%
8402      }

```

## 72.23 Multicolumns

### 72.23.1 Parsing multicolumns

\LWR@printmccoltype {*<colspec>*} Print any valid column type found. Does not print @, !, >, or < columns or their associated tokens.

This is printed as part of the table data tag's class.

```

8403 \newcommand*{\LWR@printmccoltype}[1]{%
8404     \LWR@traceinfo{lwr@printmccoltype -#1-}%

```

Get one token of the column spec:

```
8405     \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]
```

Add to the HTML tag depending on which column type is found:

```

8406     \IfStrEq{\LWR@strresult}{l}{l}{ }%
8407     \IfStrEq{\LWR@strresult}{c}{c}{ }%
8408     \IfStrEq{\LWR@strresult}{r}{r}{ }%
8409     \IfStrEq{\LWR@strresult}{p}{p}{ }%
8410     \IfStrEq{\LWR@strresult}{m}{m}{ }%
8411     \IfStrEq{\LWR@strresult}{b}{b}{ }%
8412     \IfStrEq{\LWR@strresult}{P}{P}{ }%
8413     \IfStrEq{\LWR@strresult}{M}{M}{ }%
8414     \IfStrEq{\LWR@strresult}{B}{B}{ }%

8415     \IfStrEq{\LWR@strresult}{w}{w}{ }%
8416     \IfStrEq{\LWR@strresult}{W}{W}{ }%

8417     \IfStrEq{\LWR@strresult}{S}{c}{ }%
8418     \IfStrEq{\LWR@strresult}{s}{c}{ }%

8419     \IfStrEq{\LWR@strresult}{X}{p}{ }%

```

```

8420   \IfStrEq{\LWR@strresult}{|}%
8421   {%
8422     \ifbool{LWR@mcolvertbaronleft}%
8423       {\defaddtocounter{LWR@mcolvertbarsl}{1}}% left edge
8424       {\defaddtocounter{LWR@mcolvertbarsr}{1}}% not left edge
8425   }%
8426   {%
8427     \IfStrEq{\LWR@strresult}{:}%
8428     {%
8429       \ifbool{LWR@mcolvertbaronleft}%
8430         {\defaddtocounter{LWR@mcolvertbarsldash}{1}}% left edge
8431         {\defaddtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
8432     }%
8433     {%
8434       \IfStrEq{\LWR@strresult}{;}%
8435       {%
8436         \ifbool{LWR@mcolvertbaronleft}%
8437           {\defaddtocounter{LWR@mcolvertbarsldash}{1}}% left edge
8438           {\defaddtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
8439       }%
8440       {\boolfalse{LWR@mcolvertbaronleft}}%
8441     }%
8442   }%
8443   \LWR@traceinfo{lwr@printmccoltype done}%
8444 }

```

\LWR@multicolpartext {*num parameters*} Print the data with paragraph tags, advance to bypass the given number of parameters.

```

8445 \newcommand*{\LWR@multicolpartext}[1]{%
8446   \LWR@startpars%
8447   \LWR@multicoltext%
8448   \defaddtocounter{LWR@tablemulticolspos}{#1}%
8449   \LWR@stoppars%
8450 }

```

\LWR@multicolother {*colspec*} For @, !, >, <, print the next token without paragraph tags:

```

8451 \newcommand*{\LWR@multicolother}[1]{%
8452   \defaddtocounter{LWR@tablemulticolspos}{1}%
8453   \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
8454   \LWR@strresult%

```

A valid column data type was found:

```

8455   \booltrue{LWR@validtablecol}%
8456 }

```

\LWR@multicolskip Nothing to print for this column type.

```

8457 \newcommand*{\LWR@multicolskip}{%

```

A valid column data type was found:

```
8458     \booltrue{LWR@validtablecol}%
8459 }
```

\LWR@printmccoldata {<colspec>} Print the data for any valid column type found.

```
8460 \newcommand*\LWR@printmccoldata[1]{%
8461     \LWR@traceinfo{lwr@printmccoldata -#1}%
```

Not yet found a valid column type:

```
8462 \boolfalse{LWR@validtablecol}%
```

Get one token of the column spec, into a local copy in case nested.

```
8463 \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
8464 \edef\LWR@printmccoldatatoken{\LWR@strresult}%
```

Print the text depending on which column type is found. Also handles @, >, < as it comes to them.

```
8465 \IfStrEq{\LWR@printmccoldatatoken}{l}{\LWR@multicoltext}{}
8466 \IfStrEq{\LWR@printmccoldatatoken}{c}{\LWR@multicoltext}{}
8467 \IfStrEq{\LWR@printmccoldatatoken}{r}{\LWR@multicoltext}{}
8468 \IfStrEq{\LWR@printmccoldatatoken}{D}{%
8469     \defaddtocounter{LWR@tablemulticolspos}{3}%
8470     \LWR@multicoltext%
8471 }{}
```

```
8472 \IfStrEq{\LWR@printmccoldatatoken}{p}{\LWR@multicolpartext{2}}{%
8473 \IfStrEq{\LWR@printmccoldatatoken}{m}{\LWR@multicolpartext{2}}{%
8474 \IfStrEq{\LWR@printmccoldatatoken}{b}{\LWR@multicolpartext{2}}{%
8475 \IfStrEq{\LWR@printmccoldatatoken}{P}{\LWR@multicolpartext{2}}{%
8476 \IfStrEq{\LWR@printmccoldatatoken}{M}{\LWR@multicolpartext{2}}{%
8477 \IfStrEq{\LWR@printmccoldatatoken}{B}{\LWR@multicolpartext{2}}{}}
```

```
8478 \IfStrEq{\LWR@printmccoldatatoken}{w}{\LWR@multicolpartext{3}}{%
8479 \IfStrEq{\LWR@printmccoldatatoken}{W}{\LWR@multicolpartext{3}}{}}
```

```
8480 \IfStrEq{\LWR@printmccoldatatoken}{S}{\LWR@multicoltext}{%
8481 \IfStrEq{\LWR@printmccoldatatoken}{s}{\LWR@multicoltext}{}}
```

```
8482 \IfStrEq{\LWR@printmccoldatatoken}{X}{\LWR@multicolpartext{1}}{%
8483 \IfStrEq{\LWR@printmccoldatatoken}{|}{\LWR@multicolskip}{%
8484 \IfStrEq{\LWR@printmccoldatatoken}{:}{\LWR@multicolskip}{%
8485 \IfStrEq{\LWR@printmccoldatatoken}{;}{%
8486     \LWR@multicolskip%
8487     \defaddtocounter{LWR@tablemulticolspos}{1}%
8488 }{}}%
8489 \IfStrEq{\LWR@printmccoldatatoken}{\detokenize{@}}{\LWR@multicolother{#1}}{%
8490 \IfStrEq{\LWR@printmccoldatatoken}{\detokenize{!}}{\LWR@multicolother{#1}}{}}
```

```
8491  \IfStrEq{\LWR@printmccoldatatoken}{\detokenize{>}}{\LWR@multicolother{\#1}}{}%
8492  \IfStrEq{\LWR@printmccoldatatoken}{\detokenize{<}}{\LWR@multicolother{\#1}}{}%
```

If an invalid column type:

```
8493  \ifbool{LWR@validtablecol}{}{\LWR@multicoltext{}}%
```

Tracing:

```
8494  \LWR@traceinfo{lwr@printmccoldata done}%
8495 }
```

\parsemulticolumnalignment {⟨1: colspec⟩} {⟨2: printresults⟩}

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a p{spec} column, or @, >, <, is a token list which will NOT match l, c, r, or p.

```
8496 \newcommand*{\LWR@parsemulticolumnalignment}[2]{%
8497   \defcounter{LWR@tablemulticolspos}{1}%
8498   \StrLen{\#1}[\LWR@strresult]%
8499   \defcounter{LWR@tablemulticolswidth}{\LWR@strresult}%
```

Scan across the tokens in the column spec:

```
8500  \whileboolexpr{%
8501    not test {%
8502      \ifnumcomp{\value{LWR@tablemulticolspos}}{>}{%
8503        \value{LWR@tablemulticolswidth}%
8504      }%
8505    }%
8506  }%
```

Execute the assigned print function for each token in the column spec:

```
8507  #2{\#1}%
```

Move to the next token in the column spec:

```
8508  \defaddtocounter{LWR@tablemulticolspos}{1}%
8509 }%
8510 }
```

### 72.23.2 Multicolumn factored code

\LWR@addmulticolverrulecolor

```
8511 \newcommand*{\LWR@addmulticolverrulecolor}{%
```

No vertical rules if finishing the tabular with a row of empty cells:

```
8512  \ifbool{LWR@tabularmutemods}{}{%
```

Left side:

```

8513      \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{%
8514          \LWR@tdaddstyle%
8515          border-left: 1px solid \LWR@verruleHTMLcolor%
8516      }{%
8517      \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{%
8518          \LWR@tdaddstyle%
8519          border-left: 4px double \LWR@verruleHTMLcolor%
8520      }{%
8521      \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{%
8522          \LWR@tdaddstyle%
8523          border-left: 1px dashed \LWR@verruleHTMLcolor%
8524      }{%
8525      \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
8526          \LWR@tdaddstyle%
8527          border-left: 2px dashed \LWR@verruleHTMLcolor%
8528      }{%

```

Right side:

```

8529      \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{%
8530          \LWR@tdaddstyle%
8531          border-right: 1px solid \LWR@verruleHTMLcolor%
8532      }{%
8533      \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{%
8534          \LWR@tdaddstyle%
8535          border-right: 4px double \LWR@verruleHTMLcolor%
8536      }{%
8537      \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{%
8538          \LWR@tdaddstyle%
8539          border-right: 1px dashed \LWR@verruleHTMLcolor%
8540      }{%
8541      \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
8542          \LWR@tdaddstyle%
8543          border-right: 2px dashed \LWR@verruleHTMLcolor%
8544      }{%
8545  }%
8546 }

```

```
8547 \newcommand{\LWR@multicoltext}{} 
```

To find multicolumn right trim:

```
8548 \newcounter{LWR@lastmulticolumn}
```

```
\LWR@domulticolumn {[<1: vpos>] [<2: #rows>] [<3: numLaTeXcols>] [<4: numHTMLcols>] [<5: colspec>]
{<6: text>}
```

```
8549 \NewDocumentCommand{\LWR@domulticolumn}{o o m m +m}{%
8550     \LWR@traceinfo{\LWR@domulticolumn -#1- -#2- -#4- -#5-}%
```

Remember the text to be inserted, and remember that a valid column type was found:

```

8551      \renewcommand{\LWR@multicoltext}{%
8552          #6%
8553          \booltrue{\LWR@validtablecol}%
8554      }%

```

Compute the rightmost column to be included. This is used to create the right trim.

```

8555      \defcounter{\LWR@lastmulticolumn}{\value{\LWR@tableLaTeXcolindex}}%
8556      \defaddtocounter{\LWR@lastmulticolumn}{#3}%
8557      \defaddtocounter{\LWR@lastmulticolumn}{-1}%

```

Row processing:

```
8558      \LWR@maybenewtablerow%
```

Begin the opening table data tag:

```

8559      \LWR@htmlltag{%
8560          td colspan="#4" %

8561          \IfValueT{#2}{ % rows?
8562              rowspan="#2" %

8563              \IfValueT{#1}{% vpos?
8564                  \ifstreq{\#1}{b}%
8565                      {style="\LWR@print@mbox{vertical-align:bottom}" }{}%
8566                  \ifstreq{\#1}{t}%
8567                      {style="\LWR@print@mbox{vertical-align:top}" }{}%
8568              }% vpos?
8569              }% rows?

8570          class="td%

```

Print the column type and vertical bars:

```

8571      \defcounter{\LWR@mcolvertbarsl}{0}%
8572      \defcounter{\LWR@mcolvertbarsr}{0}%
8573      \defcounter{\LWR@mcolvertbarsldash}{0}%
8574      \defcounter{\LWR@mcolvertbarsrdash}{0}%
8575      \booltrue{\LWR@mcolvertbaronleft}%
8576      \LWR@parsemulticolumnalignment{#5}{\LWR@printmccoltype}%

```

If this column has a cmidrule, add “rule” to the end of the HTML class tag.

If this position had a “Y” then add “rule” for a horizontal rule:

```

8577      \LWR@subaddcmidruletrim%
8578          {%
8579              \LWR@getexpparray{\LWR@trimlrules}%
8580                  {\arabic{\LWR@tableLaTeXcolindex}}%
8581          }%
8582          {%
8583              \LWR@getexpparray{\LWR@trimrrules}%

```

```

8584           {\arabic{LWR@lastmulticolumn}}%
8585       }%

```

Also add vertical bar class.

```

8586           \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{ tvertbarl}{ }%
8587           \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{ tvertbarldouble}{ }%
8588           \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{ tvertbarr}{ }%
8589           \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{ tvertbarrdouble}{ }%
8590           \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{ tvertbarldash}{ }%
8591           \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
8592               { tvertbarldoubledash}{ }%
8593           \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{ tvertbarrdash}{ }%
8594           \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
8595               { tvertbarrdoubledash}{ }%

```

Close the class tag's opening quote:

```

8596       "%
8597       \LWR@tdstartstyles%
8598       \LWR@addtabulararrowcolor%
8599       \LWR@addcmidrulewidth%
8600       \LWR@addcdashline%
8601       \LWR@addtabularhrulecolor%
8602       \LWR@addmulticolvertrulecolor%
8603       \LWR@addformatwpalignment{#5}%
8604       \LWR@tdendstyles%
8605   }% end of the opening table data tag
8606   \boolfalse{LWR@intabularmetadata}%
8607   \LWR@parsemulticolumnalignment{#5}{\LWR@printmccoldata}%
8608 }

```

### 72.23.3 Multicolumn

```

\LWR@htmlmulticolumn  {\langle numcols\rangle} {\langle alignment\rangle} {\langle text\rangle}
8609 \NewDocumentCommand{\LWR@htmlmulticolumn}{m m +m}{%
8610 }%

```

Figure out how many extra HTML columns to add for @ and ! columns:

```

8611     \LWR@tabularhtmlcolumns{\arabic{LWR@tableTeXcolindex}}{#1}%

```

Create the multicolumn tag:

```

8612     \LWR@domulticolumn{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#3}%

```

Move to the next L<sup>A</sup>T<sub>E</sub>X column:

```
8613 \defaddtocounter{LWR@tableLaTeXcolindex}{#1}%
8614 \defaddtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
8615 \booltrue{LWR@skipatbang}%
8616 }
```

#### 72.23.4 Longtable captions

longtable captions use \multicolumn.

Per the caption package. User-redefinable float type.

```
8617 \providecommand*\LTcaptype{table}
\LTcaptype * [<toc entry>] {<caption>}
8618 \NewDocumentCommand{\longtabledatacaptiontag}{s o +m}%
8619 {%
```

Remember the latest name for \nameref:

```
8620 \IfValueTF{#2}{% optional given?
8621     \ifblank{#2}{% optional empty?
8622         {\LWR@setlatestname{#3}}% empty
8623         {\LWR@setlatestname{#2}}% given and non-empty
8624     }% optional given
8625     {\LWR@setlatestname{#3}}% no optional}
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for @ and ! columns found between the first and the last column:

```
8626 \LWR@tabularhtmlcolumns{1}{\arabic{LWR@tabletotalLaTeXcols}}%
```

Create the multicolumn tag:

```
8627 \LWR@domulticolumn{\arabic{LWR@tabletotalLaTeXcols}}%
8628     {\arabic{LWR@tabhtmlcoltotal}}%
8629     {P}%
8630     { \LWR@domulticolumn
8631     \IfBooleanTF{#1}{star?}
```

Star version, show a caption but do not make a LOT entry:

```
8632 { yes star
8633 \LWR@figcaption%
```

```

8634      \LWR@isolate{#3}%
8635      \endLWR@figcaption%
8636  }%
8637  {%

```

Not the star version:

Don't step the counter if \caption[]{}{A caption.}

```

8638      \ifbool{LWR@starredlongtable}%
8639      {%
8640          \ifblank{#2}{% TOC entry
8641              {}%
8642              {}%
8643                  \refstepcounter{\LTcaptype}%
8644                  \protected@edef{@currentlabel{%
8645                      \@nameuse{p@\LTcaptype}\@nameuse{the\LTcaptype}}%
8646                  }%
8647              }%
8648          }%

```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```

8649      \LWR@figcaption%
8650      \LWR@isolate{@nameuse{fnum@\LTcaptype}}%
8651      \CaptionSeparator%
8652      \LWR@isolate{#3}%
8653      \endLWR@figcaption%

```

See if an optional caption was given:

```
8654      \ifblank{#2}{% TOC entry empty}
```

if the optional caption was given, but empty, do not form a TOC entry

```
8655      {}%
```

If the optional caption was given, but might only be []:

```

8656      {%
8657          TOC entry not empty
8658          \IfNoValueTF{#2}{% No TOC entry?}

```

The optional caption is []:

```

8658      {%
8659          No TOC entry
8660          \addcontentsline{%
8661              @nameuse{ext@\LTcaptype}}{%
8662                  \LTcaptype}%
8663          }%
8664          \protect\newline{%
8665              \LWR@isolate{@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}{%
8666                  \ignorespaces \LWR@isolate{#3}\protect\relax}%
8667          }%
8668      }% end of No TOC entry

```

The optional caption has text enclosed:

```

8668      {%
8669          yes TOC entry
8670          \addcontentsline%
8671          {\@nameuse{ext@\LTcaptype}}%
8672          {\LTcaptype}%
8673          {%
8674              \protect\newline%
8675              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
8676              {\ignorespaces \LWR@isolate{\#2}\protect\relax}%
8677          }%
8678      }% end of yes TOC entry
8679      }% end of TOC entry not empty
8679  }% end of no star

```

Skip any trailing @ or ! columns for this cell:

```

8680  \booltrue{\LWR@skipatbang}%
8681  }% end of \LWR@domulticolumn
8682  \defaddtocounter{\LWR@tableLaTeXcolindex}{\value{\LWR@tabletotalLaTeXcols}}%
8683  \defaddtocounter{\LWR@tableLaTeXcolindex}{-1}
8684
8685 }

```

### 72.23.5 Counting HTML tabular columns

The L<sup>A</sup>T<sub>E</sub>X specification for a table includes a number of columns separated by the & character. These columns differ in content from line to line. Additional virtual columns may be specified by the special @ and ! columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, @ and ! columns are placed into their own tabular columns. Thus, a L<sup>A</sup>T<sub>E</sub>X \multicolumn command may span several additional @ and ! columns in HTML output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```

8686 \newcounter{\LWR@tabhtmlcolindex}
8687 \newcounter{\LWR@tabhtmlcolend}
8688 \newcounter{\LWR@tabhtmlcoltotal}

```

\LWR@subtabularhtmlcolumns {<index>}

Factored from \LWR@tabularhtmlcolumns, which follows.

```
8689 \newcommand*{\LWR@subtabularhtmlcolumns}[1]{%
```

Temporarily define a macro equal to the @ specification for this column:

```
8690 \edef\LWR@atbangspec{\LWR@getexarray{\LWR@colatspec}{#1}}%
```

If the @ specification is not empty, add to the count:

---

```

8691     \ifdefempty{\LWR@atbangspec}%
8692         {}%
8693         {\defaddtocounter{\LWR@tabhtmlcoltotal}{1}}%

```

Likewise for the ! columns:

```

8694     \edef\LWR@atbangspec{\LWR@getexparray{\LWR@colbangspec}{#1}}%
8695     \ifdefempty{\LWR@atbangspec}%
8696         {}%
8697         {\defaddtocounter{\LWR@tabhtmlcoltotal}{1}}%
8698 }

```

\LWR@tabularhtmlcolumns {*<starting L<sup>A</sup>T<sub>E</sub>X column>*} {*<number L<sup>A</sup>T<sub>E</sub>X columns>*}

Compute the total number of HTML columns being spanned, considering the starting L<sup>A</sup>T<sub>E</sub>X table column and the number of L<sup>A</sup>T<sub>E</sub>X tabular columns being spanned. Any @ and ! columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter LWR@tabhtmlcoltotal.

```
8699 \newcommand*{\LWR@tabularhtmlcolumns}[2]{%
```

Count the starting index, compute ending index, and begin with the count being the L<sup>A</sup>T<sub>E</sub>X span, to which additional @ and ! columns may be added:

```

8700     \defcounter{\LWR@tabhtmlcolindex}{#1}%
8701     \defcounter{\LWR@tabhtmlcoltotal}{#2}%
8702     \defcounter{\LWR@tabhtmlcolend}{#1}%
8703     \defaddtocounter{\LWR@tabhtmlcolend}{#2}%

```

If at the left edge, add the at/bang columns for the left edge:

```

8704     \ifnumcomp{\value{\LWR@tabhtmlcolindex}}{=}{1}{%
8705         \LWR@subtabularhtmlcolumns{leftedge}%
8706     }{%

```

Walk across the L<sup>A</sup>T<sub>E</sub>X columns looking for @ and ! columns:

```

8707     \whileboolexpr{%
8708         test {%
8709             \ifnumcomp{\value{\LWR@tabhtmlcolindex}}{<}{\value{\LWR@tabhtmlcolend}}{%
8710                 }%
8711             }%
8712             {%
8713                 \LWR@subtabularhtmlcolumns{\arabic{\LWR@tabhtmlcolindex}}%
8714                 \defaddtocounter{\LWR@tabhtmlcolindex}{1}%
8715             }%
8716         }%
8717     }%
8718 \end{warpHTML}

```

## 72.24 Multirow if not loaded

A default defintion in case `multirow` is not loaded. This is used during table parsing.

```
8718 \begin{warpHTML}
8719 \newcommand{\multirow}[2][c]{}
8720 \end{warpHTML}
```

## 72.25 Multicolumnrow

A print-mode version is defined here, and is also used during HTML output while inside a `lateximage`.

See section 359 for the HTML versions.

**for HTML & PRINT:** 8721 `\begin{warpall}`

```
\multicolumnrow {\{1:cols\}} {\{2:halign\}} [\{3:vpos\}] {\{4:numrows\}} [\{5:bigstruts\}] {\{6:width\}} [\{7:fixup\}]
{\{8:text\}}
```

For discussion of the use of `\DeclareExpandableDocumentCommand`, see:

<https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex>

`\AtBeginDocument` to adjust after the user may have loaded `multirow`, which requires several tests to determine which version is loaded and thus which options are available.

```
8722 \AtBeginDocument{
```

`\@ifundefined{@xmultirow}` determines if `multirow` was never loaded.

Null action if not loaded:

```
8723 \@ifundefined{@xmultirow}
8724 {
8725 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}{%
8726 {+m +m +0{c} +m +0{0} +m +0{0pt} +m}%
8727 {}%
8728 }% no version of multirow was loaded
8729 {% \@xmultirow defined, so some version of multirow was loaded
```

`\@ifpackageloaded{multirow}` determines if v2.0 or later of `multirow` was used, which included the `\ProvidesPackage` macro.

The print version:

```
8730 \@ifpackageloaded{multirow}{% v2.0 or newer
8731 \@ifpackagelater{multirow}{2016/09/01}{2016/09/27 for v2.0}
8732 {% v2.0+:
8733 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}{%
8734 {+m +m +0{c} +m +0{0} +m +0{0pt} +m}%
8735 {\multicolumn{\#1}{\#2}{\@xmultirow[\#3]{\#4}{\#5}{\#6}{\#7}{\#8}}}}%
```

---

```

8736 }
8737 {%
8738   loaded but older, probably not executed:
8739   \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}{%
8740     +m +m +O{c} +m +O{0} +m +O{0pt} +m}%
8741   {\multicolumn{#1}{#2}{\xmultirow{#4}{#5}{#6}{#7}{#8}}}}%
8742 }% package loaded{multirow}

```

If not `\ifpackage{multirow}` but `\xmultirow` is defined, then this must be v1.6 or earlier, which did not `\ProvidesPackage{multirow}`, and did not have the `vposn` option.

```

8743 {%
8744   v1.6 or older did not \ProvidePackage
8745   \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}{%
8746     +m +m +O{c} +m +O{0} +m +O{0pt} +m}%
8747   {\multicolumn{#1}{#2}{\xmultirow{#4}{#5}{#6}{#7}{#8}}}}%
8748
8749 }% \undefined{xmultirow}
8750
8751 \providecommand*{\multicolumnrow}{\LWR@print@multicolumnrow}
8752
8753 }% AtBeginDocument

```

```
8754 \end{warpall}
```

## 72.26 Utility macros inside a table

**for HTML output:** 8755 `\begin{warpHTML}`

Used to prevent opening a tabular data cell if the following token is one which does not create tabular data:

```
8756 \newcommand*{\LWR@donothing}{}%
```

In case `array` is not loaded:

```

8757 \let\firsthline\relax
8758 \let\lasthline\relax
8759 \newcommand*{\firsthline}{}%
8760 \newcommand*{\lasthline}{}%

```

In case `bigdelim` is not loaded:

```

8761 \newcommand*{\ldelim}{}%
8762 \newcommand*{\rdelim}{}%

```

```
8763 \end{warpHTML}
```

## 72.27 Special-case tabular markers

**for HTML & PRINT:** 8764 \begin{warpall}

\TabularMacro Place this just before inserting a custom macro in a table data cell. Doing so tells lwarp not to automatically start a new HTML table data cell yet. See section 8.10.1.

8765 \newcommand\*\{\TabularMacro\}{}

8766 \end{warpall}

\ResumeTabular Used to resume tabular entries after resuming an environment.

**⚠ tabular inside another environment** When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
  \tabular{cc}
  left & right \\
}
{
  \TabularMacro\ResumeTabular
  left & right \\
  \endtabular
}
\StopDefiningTabulars
```

**for HTML output:** 8767 \begin{warpHTML}

```
8768 \newcommand*\{\ResumeTabular\}{%
  \boolfalse{LWR@existingtabular}%
  \boolfalse{LWR@tabularmutemods}%
  \LWR@getmynexttoken%
}
```

8773 \end{warpHTML}

**for PRINT output:** 8774 \begin{warpprint}

8775 \newcommand\*\{\ResumeTabular\}{}

8776 \end{warpprint}

## 72.28 Checking for a new table cell

**for HTML output:** 8777 \begin{warpHTML}

\LWR@tabledatacolumntag Open a new HTML table cell unless the next token is for a macro which does not create data, such as \hline, \toprule, etc:

```
8778 \newcommand*\LWR@tabledatacolumntag{%
8779 {%
8780     \LWR@traceinfo{\LWR@tabledatacolumntag}{%
```

\show\LWR@mynexttoken to see what tokens to look for

If not any of the below, start a new table cell:

```
8781     \global\let\LWR@mynextaction\LWR@tabledatasinglecolumntag%
```

If exiting the tabular:

```
8782     \ifdefequal{\LWR@mynexttoken}{\end}{%
8783         {\booltrue{\LWR@exittingtabular}}{}}
```

longtable can have a caption in a cell

```
8784     \ifdefequal{\LWR@mynexttoken}{\caption}{%
8785         {\global\let\LWR@mynextaction\LWR@donothing}{}}
```

Look for other things which would not start a table cell:

```
8786     \ifdefequal{\LWR@mynexttoken}{\multicolumn}{%
8787         {\global\let\LWR@mynextaction\LWR@donothing}{}}{%
8788     \ifdefequal{\LWR@mynexttoken}{\multirow}{%
8789         {\global\let\LWR@mynextaction\LWR@donothing}{}}{%
8790     \ifdefequal{\LWR@mynexttoken}{\multicolumnrow}{%
8791         {\global\let\LWR@mynextaction\LWR@donothing}{}}{%
8792     \ifdefequal{\LWR@mynexttoken}{\noalign}{%
8793         {\global\let\LWR@mynextaction\LWR@donothing}{}}{}}
```

If an \mrowcell, this is a cell to be skipped over:

```
8794     \ifdefequal{\LWR@mynexttoken}{\mrowcell}{%
8795         {\global\let\LWR@mynextaction\LWR@donothing}{}}
```

If an \mcolrowcell, this is a cell to be skipped over:

```
8796     \ifdefequal{\LWR@mynexttoken}{\mcolrowcell}{%
8797         {\global\let\LWR@mynextaction\LWR@donothing}{}}{%
8798     \ifdefequal{\LWR@mynexttoken}{\TabularMacro}{%
8799         {\global\let\LWR@mynextaction\LWR@donothing}{}}{}}
```

```
8800 \ifdefequal{\LWR@mynexttoken}{\hline}%
8801   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8802 \ifdefequal{\LWR@mynexttoken}{\firsthline}%
8803   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8804 \ifdefequal{\LWR@mynexttoken}{\lasthline}%
8805   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8806 \ifdefequal{\LWR@mynexttoken}{\toprule}%
8807   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8808 \ifdefequal{\LWR@mynexttoken}{\midrule}%
8809   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8810 \ifdefequal{\LWR@mynexttoken}{\cmidrule}%
8811   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8812 \ifdefequal{\LWR@mynexttoken}{\morecmidrules}%
8813   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8814 \ifdefequal{\LWR@mynexttoken}{\specialrule}%
8815   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8816 \ifdefequal{\LWR@mynexttoken}{\cline}%
8817   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8818 \ifdefequal{\LWR@mynexttoken}{\bottomrule}%
8819   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8820 \ifdefequal{\LWR@mynexttoken}{\hhline}%
8821   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8822 \ifdefequal{\LWR@mynexttoken}{\rowcolor}%
8823   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8824 \ifdefequal{\LWR@mynexttoken}{\arrayrulecolor}%
8825   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8826 \ifdefequal{\LWR@mynexttoken}{\doublerulesepcolor}%
8827   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8828 \ifdefequal{\LWR@mynexttoken}{\warpprintonly}%
8829   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8830 \ifdefequal{\LWR@mynexttoken}{\warpHTMLonly}%
8831   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
8832 \ifdefequal{\LWR@mynexttoken}{\ldelim}%
8833   {\global\let\LWR@mynextaction\LWR@donothing}{ }
```

---

```
8834 \ifdefequal{\LWR@mynexttoken}{\rdelim}%
8835   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
```

For `arydshln`:

```
8836 \ifdefequal{\LWR@mynexttoken}{\hdashline}%
8837   {\global\let\LWR@mynextaction\LWR@donothing}{ }%

8838 \ifdefequal{\LWR@mynexttoken}{\cdashline}%
8839   {\global\let\LWR@mynextaction\LWR@donothing}{ }%

8840 \ifdefequal{\LWR@mynexttoken}{\firstdashline}%
8841   {\global\let\LWR@mynextaction\LWR@donothing}{ }%

8842 \ifdefequal{\LWR@mynexttoken}{\lastdashline}%
8843   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
```

Ignore an empty line between rows:

```
8844 \ifdefequal{\LWR@mynexttoken}{\par}%
8845   {\global\let\LWR@mynextaction\LWR@donothing}{ }%
```

No action for an `\end` token.

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```
8846 \LWR@traceinfo{\LWR@tabledatacolumntag: about to do mynext}%
8847 \LWR@mynextaction%
8848 \LWR@traceinfo{\LWR@tabledatacolumntag: done}%
8849 }

8850 \end{warpHTML}
```

## 72.29 \mrowcell

**for HTML & PRINT:** 8851 `\begin{warpall}`

**⚠ multirow cells** The user must insert `\mrowcell` into any `\multirow` cells which must be skipped. This command has no action during print output.

```
8852 \newcommand*{\mrowcell}{}%
8853 \end{warpall}
```

## 72.30 \mcolrowcell

**for HTML & PRINT:** 8854 \begin{warpall}

⚠ \mcolrowcell The user must insert \mcolrowcell into any \multicolumn cells which must be skipped. This command has no action during print output.

8855 \newcommand\*\{\mcolrowcell}{}{}

8856 \end{warpall}

## 72.31 HTML tabular environment

**for HTML output:** 8857 \begin{warpHTML}

These are default definitions in case booktabs is not loaded, and are not expected to be used, but must exist as placeholders. memoir may have already loaded booktabs.

```
8858 \providetcommand*\{\toprule}[1][]{\hline}
8859 \providetcommand*\{\midrule}[1][]{\hline}
8860 \providetcommand*\{\cmidrule}{\cline}
8861 \providetcommand*\{\bottomrule}[1][]{\hline}
8862 \providetcommand*\{\addlinespace}[1][]{}
8863 \providetcommand*\{\morecmidrules}){}
8864 \providetcommand*\{\specialrule}[3]{\hline}
```

\noalign {⟨text⟩} Redefined for use inside tabular.

```
8865 \LetLtxMacro{\LWR@orignoalign}{\noalign}
8866
8867 \newcommand{\LWR@tabularnoalign}[1]{%
8868   \advance\rownum\m@ne%
8869   \LetLtxMacro{\LWR@save@xcolorrowHTMLcolor}{\LWR@xcolorrowHTMLcolor}%
8870   \renewcommand*\{\LWR@xcolorrowHTMLcolor}{}%
8871   \multicolumn{\value{\LWR@tabletotalLaTeXcols}}{l}{#1} \\
8872   \LetLtxMacro{\LWR@xcolorrowHTMLcolor}{\LWR@save@xcolorrowHTMLcolor}%
8873   % \@rowc@lors%
8874   \LWR@getmynexttoken%
8875 }
```

\LWR@HTMLhline The definition of \hline depends on whether tabs has been loaded. If so, optional space below the line may be specified, but will be ignored.

```
8876 \AtBeginDocument{
8877
8878 \@ifpackageloaded{lwarp-tables}
8879 {
8880   \newcommand*\{\LWR@HTMLhline}[1][]{%
8881     \ifbool{FormatWP}{}{%
8882       {\LWR@docmidrule{1-\arabic{\LWR@tabletotalLaTeXcols}}}{}%
```

```

8883           {\defaddtocounter{LWR@hlines}{1}}%
8884           \LWR@getmynexttoken}%
8885 }
8886 {
8887   \newcommand*{\LWR@HTMLhline}{%
8888     \ifbool{FormatWP}{%
8889       {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}}{%
8890       {\defaddtocounter{LWR@hlines}{1}}%
8891       \LWR@getmynexttoken}%
8892 }
8893
8894 }% AtBeginDocument

\LWR@HTMLcline {<columns>}

8895 \NewDocumentCommand{\LWR@HTMLcline}{m}{%
8896   {\LWR@docmidrule{#1}\LWR@getmynexttoken}%

```

\LWR@tabular@warpprintonly {<contents>}

Only process the contents if producing printed output. Modified inside a `tabular` to grab the next token.

```

8897 \newcommand{\LWR@tabular@warpprintonly}[1]{%
8898   \ifbool{warpingprint}{#1}{%
8899     \LWR@getmynexttoken%
8900   }

```

\LWR@nullifyNoAutoSpacing For `babel-french`, turn off auto spacing at the start of the `tabular`, then nullify the autospacing commands inside the `tabular`, since they were not compatible with the `tabular` column parsing code, which uses `xstring`.

```

8901 \AtBeginDocument{
8902 @ifundefined{NoAutoSpacing}%
8903 {%
8904   no babel-french
8905 }%
8906 yes babel-french
8907 \newcommand*{\LWR@nullifyNoAutoSpacing}{}%
8908   \NoAutoSpacing%
8909   \renewcommand*{\NoAutoSpacing}{}%
8910   \renewcommand*{\LWR@FBcancel}{}%
8911 }
8912 yes babel-french
8913 }% AtBeginDocument

```

Env `tabular` <direction> [<vertposition>] {<colspecs>}

The <direction> is from `plex` for Japanese documents, and is ignored.

```

8914 \StartDefiningTabulars
8915

```

```
8916 \NewDocumentCommand{\LWR@HTML@@tabular}{d<> o m}
8917 {%
8918     \LWR@traceinfo{LWR@HTML@@tabular started}%
```

- ⚠ **<table> inside <span>** In L<sup>A</sup>T<sub>E</sub>X, a tabular may be placed inside a minipage, but in HTML a <table> may not be inside a <span>. Since there may be several nested <span>s, with an unknown number of other objects between, it is hard to undo all these <span>s before the <table> then redo them after. The browser probably compensates for this situation, but formatting may be lost inside the <table> because several things are neutralized inside a <span>. Furthermore, in the HTML output, the entire <table> is placed on a single line of HTML code, since the line breaking commands are neutralized inside a <span>. Since this is such a sloppy situation, a warning is issued here instructing the user to please isolate the <span> to print-only.

```
8919     \ifnumcomp{\value{LWR@spandepth}}{>}{0}{%
8920         \PackageWarning{l warp}{%
8921             A tabular is being used inside a span such as\MessageBreak
8922             a minipage. Some formatting may not be correct\MessageBreak
8923             in the tabular.\MessageBreak
8924             It is recommended to use \protect\warpprintonly\space or the\MessageBreak
8925                 warpprint environment to isolate the span to\MessageBreak
8926                 print-only,%
8927         }%
8928     }{%
8929     \addtocounter{LWR@tabulardepth}{1}}%
```

Not yet started a table row:

```
8930     \boolfalse{LWR@startedrow}%
```

Not yet doing any rules:

```
8931     \defcounter{LWR@hlines}{0}%
8932     \defcounter{LWR@hdashedlines}{0}%
8933     \boolfalse{LWR@doingtbrule}%
8934     \boolfalse{LWR@doingscmidrule}%
```

For babel-french, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the tabular parsing code.

```
8935     \LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of tabular command. Unmute the @ and ! columns.

```
8936     \boolfalse{LWR@exittingtabular}%
8937     \boolfalse{LWR@tabularmutemods}%
```

Error if failed to use \mrowcell or \mcolrowcell when needed.

```
8938     \boolfalse{LWR@usedmultirow}%
8939     \boolfalse{LWR@foundmrowcell}%

8940     \renewcommand*\{\LWR@multicoltext}{}%
```

Create the table tag:

```
8941 \booltrue{\LWR@intabularmetadata}%
8942 \LWR@traceinfo{\LWR@tabular: About to \LWR@forecenewpage.}%
8943 \LWR@forcenewpage
8944 \LWR@htmlblocktag{table}%
```

Parse the table columns:

```
8945 \LWR@parsetablecols{\#3}%
```

Table col spec is: \LWR@tablecols which is a string of llccrr, etc.

Do not place the table inside a paragraph:

```
8946 \LWR@stoppars%
```

Track column #:

```
8947 \defcounter{\LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
8948 \global\boolfalse{\LWR@tabularcelladded}%
```

Start looking for midrules:

```
8949 \LWR@clearmidrules%
```

\\" becomes a macro to end the table row:

```
8950 \LetLtxMacro{\\"}{\LWR@tabularendofline}%
```

\warpprintonly inside a tabular must grab the next token.

```
8951 \LetLtxMacro{\warpprintonly}{\LWR@tabular@warpprintonly}%
```

The following adjust for colortbl.

```
8952 \LetLtxMacro{\arrayrulecolor}{\arrayrulecolornexttoken}%
8953 \LetLtxMacro{\doublerulesepcolor}{\doublerulesepcolornexttoken}%
8954 \def{\LWR@columnHTMLcolor}{}%
8955 \def{\LWR@rowHTMLcolor}{}%
8956 \def{\LWR@cellHTMLcolor}{}%
8957 \@rowcolors%
```

The vertical rules are set to the color active at the start of the tabular. \arrayrulecolor will then affect horizontal rules inside the tabular, but not the vertical rules.

```
8958 \ifdefvoid{\LWR@ruleHTMLcolor}%
8959   {\edef{\LWR@vertruleHTMLcolor}{black}}%
8960   {\edef{\LWR@vertruleHTMLcolor}{\LWR@origpound\LWR@ruleHTMLcolor}}%
```

Tracking the depth of cell color <div>s:

```
8961 \defcounter{LWR@cellcolordepth}{0}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with \LWR@getmynexttoken to see if the next token might create a new data cell:

The optional parameter for \hline supports the **tbls** package.

```
8962 \LWR@traceinfo{LWR@@HTML@tabular: redefining macros}%
8963 \LetLtxMacro\noalign{\LWR@tabularnoalign}%
8964 \LetLtxMacro\hline{\LWR@HTMLhline}%
8965 \LetLtxMacro\cline{\LWR@HTMLcline}%

8966 \DeclareDocumentCommand{\hdashline}{o}{%
8967   \ifboolexpr{FormatWP}{%
8968     {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}{%
8969       {\defaddtocounter{LWR@hdashedlines}{1}}{%
8970         \LWR@getmynexttoken}}%
8971   }%
8972 \DeclareDocumentCommand{\cdashline}{m}{%
8973   \LWR@docdashline{##1}\LWR@getmynexttoken}%
8974 }%
8975 \DeclareDocumentCommand{\firstdashline}{o}{%
8976   \ifboolexpr{FormatWP}{%
8977     {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}{%
8978       {\defaddtocounter{LWR@hdashedlines}{1}}{%
8979         \LWR@getmynexttoken}}%
8980   }%
8981 \DeclareDocumentCommand{\lastdashline}{o}{%
8982   \ifboolexpr{FormatWP}{%
8983     {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}{%
8984       {\defaddtocounter{LWR@hdashedlines}{1}}{%
8985         \LWR@getmynexttoken}}%
8986   }%
```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use \LWR@getmynexttoken.

```
8987 \renewcommand{\multicolumn}{\LWR@htmlmulticolumn}%
8988 \renewcommand*\mrowcell{%
8989   \LWR@maybenewtablerow%
8990   \LWR@tabularleftedge%
8991   \booltrue{\LWR@skippingmrowcell}%
8992   \booltrue{\LWR@foundmrowcell}%
8993 }%
8994 \renewcommand*\mcolrowcell{%
8995   \LWR@maybenewtablerow%
8996   \booltrue{\LWR@skippingmcolrowcell}%
8997   \booltrue{\LWR@foundmrowcell}%
}
```

---

```
8998      }%
8999      \LetLtxMacro\caption\lwr@longtabledatacaptiontag%
```

Reset for new processing:

```
9000      \boolfalse{\lwr@tableparcell}%
9001      \boolfalse{\lwr@skippingmrowcell}%
9002      \boolfalse{\lwr@skippingmcolrowcell}%
9003      \boolfalse{\lwr@skipatbang}%
9004      \boolfalse{\lwr@emptyatbang}%
```

Set & for its special meaning inside the tabular:

```
9005      \StartDefiningTabulars%
9006      \protected\gdef&{\lwr@tabularampersand}%
```

Locally force any minipages to be fullwidth, until the end of the tabular:

```
9007      \booltrue{\lwr@forceminipagefullwidth}%
```

Nest one level deeper of tabular paragraph handling:

```
9008      \addtocounter{\lwr@tabularpardepth}{1}%
```

Look ahead for a possible table data cell:

```
9009      \lwr@traceinfo{\lwr@@HTML@tabular: about to \lwr@getmynexttoken}%
9010      \lwr@getmynexttoken%
9011 }%
```

Ending the environment:

```
9012 \newcommand*{\lwr@HTML@endtabular}%
9013 {%
9014     \lwr@traceinfo{\lwr@HTML@endtabular}%
}
```

Unnest one level of tabular paragraph handling:

```
9015      \addtocounter{\lwr@tabularpardepth}{-1}%
9016      \ifboolexpr{%
9017          test {%
9018              \ifnumcomp{\value{\lwr@tableLaTeXcolindex}}{<}%
9019                  {\value{\lwr@tabletotalLaTeXcols}}%
9020          } or %
9021          (%
9022              \bool{\lwr@intabularmetadata} and%
9023              not \bool{\lwr@tabularcelladded} and%
9024              test {%
9025                  \ifnumcomp{\value{\lwr@tableLaTeXcolindex}}{=}%
9026                      {\value{\lwr@tabletotalLaTeXcols}}%
9027              }%
9028          )%
9029      }%
9030  }%
```

---

```

9031      \LWR@tabularfinishrow%
9032  }%
9033  {%
9034      \LWR@closetabledatacell%
9035  }%
9036  \LWR@htmlblocktag{/tr}%

```

xcolor row color support:

```

9037  \@rowc@lors%
9038  \LWR@htmlblocktag{/table}%
9039  \boolfalse{\LWR@intabularmetadata}%

```

Unnest one level of tabular:

```

9040  \addtocounter{\LWR@tabulardepth}{-1}%

```

Restore & to its usual meaning:

```

9041  \ifnumequal{\value{\LWR@tabulardepth}}{0}{%
9042      \protected\gdef&{\LWR@origampmacro}%
9043      \StopDefiningTabulars%
9044  }{ }%

```

Error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```

9045  \ifbool{\LWR@usedmultirow}{%
9046      \ifbool{\LWR@foundmrowcell}{%
9047          {}%
9048          {}%
9049          \PackageError{lwarp}{%
9050              }{%
9051                  When using \protect\multirow, \protect\multicolumnrow, \MessageBreak
9052                      or the bigdelim package, \MessageBreak
9053                      place \protect\mrowcell\space or \protect\mcolrowcell\MessageBreak
9054                          in empty cells which are to be skipped.\MessageBreak
9055                          See the Lwarp package documentation:\MessageBreak
9056                          "Special cases and limitations" -> "Tabular"
9057          }%
9058          {}%
9059          See the Lwarp package documentation:\MessageBreak
9060          "Special cases and limitations" -> "Tabular".
9061      }%
9062      }%
9063  }{ }%
9064  \LWR@traceinfo{\LWR@HTML@endtabular finished}%
9065 }%
9066 \csletcs{\LWR@HTML@endtabular*}{\LWR@HTML@endtabular}%
9068 \StopDefiningTabulars

```

`siunitx` may redefine `tabular`, so set the following later:

```

9070 \AtBeginDocument{
9071   \LetLtxMacro{\LWR@origendtabular}{\endtabular}
9072   \csletcs{\LWR@origendtabular*}{\endtabular*}
9073   \LWR@formatted{@tabular}
9074   \LWR@formatted{endtabular}
9075   \LWR@formatted{endtabular*}
9076 }

9077 \end{warpHTML}
```

## 73 Cross-references

Sectioning commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

**File** `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and `lateximage` depth and number for each label:

```
\newlabel{<labelname>}@lwarp}{{<section name>}{{<filename>}}
{<limagedepth>}{{<limage number>}}}
```

Table 12 shows the data structures related to cross-referencing.

**for HTML output:** 9078 `\begin{warpHTML}`

### 73.1 Setup

`\@currentlabelname` To remember the most recently defined section name, description, or caption, for `\nameref`.

```
9079 \providecommand*{\@currentlabelname}{}%
```

`\LWR@stripperiod` `{<text>} [<.>]`

Removes a trailing period.

```
9080 \def\LWR@stripperiod#1.\ltx@empty#2@nil{#1}%
```

`\LWR@setlatestname` `{<object name>}`

Removes `\label`, strips any final period, and remembers the result.

```
9081 \newcommand*{\LWR@setlatestname}[1]{%
```

Table 12: Cross-referencing data structures

Original L <sup>A</sup> T <sub>E</sub> X:	(print and HTML)
<b>\refstepcounter:</b> Steps the counter and sets \currentlabel.	
<b>\@currentlabel:</b> \p@<ctr>\the<ctr> Updated by \refstepcounter.	
<b>\label:</b> Writes to the .aux file: \newlabel{<label>}{{\@currentlabel}{\thepage}}	
<b>\newlabel:</b> When the .aux file is read, sets \r@<label>.	
<b>\r@&lt;label&gt;:</b> Set to: {{\@currentlabel}{\thepage}}	
<b>\ref:</b> Returns the first part of \r@<label>.	
<b>\pageref:</b> Returns the second part of \r@<label>.	
Added by l warp:	(HTML only)
<b>\label:</b> Adds HTML tags (section 73.3), and another .aux entry (section 73.2).	
<b>\newlabel:</b> Unchanged. When the .aux file is read, sets \r@<label>@l warp.	
<b>\r@&lt;label&gt;@l warp:</b> Set to {{section_name}{file_name}{depth}{number}}: \LWR@nameref: The section name for this label. \LWR@htmlfileref: The filenumber or name for this label. \LWR@lateximagedepthref: The lateximagedepth for this label. \LWR@lateximagenumberref: The lateximagenumber for this label.	
<b>\nameref:</b> Emulated from hyperref for l warp. See section 73.4.	
<b>\ref and \nameref:</b> Adds HTML tags. See section 73.4.	
Added by amsmath:	(print and HTML)
<b>\label:</b> Execution is delayed until the math environment is completed.	
<b>\ltx@label:</b> L <sup>A</sup> T <sub>E</sub> X \label, (HTML: patched by l warp,) later patched by cleveref.	
Added by cleveref:	(print and HTML)
<b>\refstepcounter:</b> Added: sets \cref@currentlabel.	
<b>\cref@currentlabel:</b> (<type>=<ctr> unless an alias is used): [<type>][\arabic{<ctr>}][<parent ctrs>]{\p@<ctr>\the<ctr>} Also see section 59.4 for use with footnotes.	
<b>\label:</b> Writes to the .aux file: \newlabel{<label>@\cref}{{\cref@currentlabel}{\thepage}}	
<b>\newlabel:</b> Unchanged. When the .aux file is read, sets \r@<label>@\cref.	
<b>\r@&lt;label&gt;@\cref:</b> Set to: {{\cref@currentlabel}{\thepage}}	
<b>Utility functions:</b> See \cref@getlabel, \cref@gettype, \cref@getcounter, \cref@getprefix.	
<b>Cross-referencing names:</b> \crefname and \Crefname assign human-readable names for references to this counter type.	
Additionally patched by l warp:	(HTML only)
<b>\cref, etc.:</b> Modified for l warp. See section 87.	
<b>\label inside math:</b> See section 79.7.1.	
<b>Footnotes:</b> See \noteentry in section 59.4.	

Remove \label and other commands from the name, the strip any final period. See `gettitledstring`.

```
9082     \GetTitleStringExpand{#1}%
9083     \edef\@currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
9084     \edef\@currentlabelname{%
9085         \expandafter\LWR@stripperiod\@currentlabelname%
9086         \ltx@empty.\ltx@empty@nil%
9087     }%
9088 }
```

### 73.2 New lwarp labels.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{{<filename>}%
{<limagedepth>}{{<limagenumber>}}}
```

See:

<http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference>

`\LWR@setref {<args list>} {<selector>} {<label>}`

`@setref` without the `\null` (`\hbox`), and without the warning messages. Each caused problems with `lwarp` references. The regular reference will cause the warning.

```
9089 \def\LWR@setref#1#2#3{%
9090   \ifx#1\relax%
9091     ??%
9092   \else%
9093     \expandafter#2#1%
9094   \fi}
```

`\LWR@nameref {<label>}` Returns the section name for this label:

```
9095 \newcommand*{\LWR@nameref}[1]{%
9096   \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@firstoffour{#1}%
9097 }
```

`\LWR@htmlfileref {<label>}` Returns the file number or name for this label:

```
9098 \newcommand*{\LWR@htmlfileref}[1]{%
9099   \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@secondoffour{#1}%
9100 }
```

`\LWR@lateximagedepthref {<label>}` Returns the `lateximagedepth` for this label:

```

9101 \newcommand*{\LWR@lateximagedepthref}[1]{%
9102     \expandafter\LWR@setref\csname r@#1@l warp\endcsname\LWR@thirdoffour{#1}%
9103 }

```

\LWR@lateximagenumberref {*label*} Returns the lateximagenumber for this label:

```

9104 \newcommand*{\LWR@lateximagenumberref}[1]{%
9105     \expandafter\LWR@setref\csname r@#1@l warp\endcsname\LWR@fourthoffour{#1}%
9106 }

```

\LWR@lwarplabel {*label*} Sanitize the name and then creates the label:

```

9107 \newcommand*{\LWR@lwarplabel}[1]{%
9108     \LWR@traceinfo{\LWR@lwarplabel !#1!}%
9109     \LWR@setlatestname{\@currentlabelname}%
9110         \@bsphack%
9111         \protected@write\@auxout{}{%
9112             {%
9113                 \string\newlabel{#1@l warp}{%
9114                     {\@currentlabelname}%
9115                     {%
9116                         \ifbool{FileSectionNames}%
9117                             {\LWR@thisfilename}%
9118                             {\arabic{\LWR@htmlfilenumber}}%
9119                         }%
9120                         {\arabic{\LWR@lateximagedepth}}%
9121                         {\arabic{\LWR@lateximagenumber}}%
9122                     }%
9123                 }%
9124             \@esphack%
9125 }

```

### 73.3 Labels

\LWR@sublabel {*label*} Creates an HTML id tag.

\detokenize is used to allow underscores in the labels.

```

9126 \newcommand*{\LWR@sublabel}[1]{%
9127     \LWR@traceinfo{\LWR@sublabel !#1!}%

```

Create an HTML id tag unless are inside a lateximage, since it would appear in the image:

```

9128     \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}%
9129     {}%
9130     {% not lateximage

```

If not doing a lateximage, create an HTML ID tag: (To be factored...)

```

9131     \LWR@sanitize{#1}%

```

```
9132 \ifbool{\LWR@doingstartpars}{%
9133   {%
9134     \ifbool{\LWR@doingapar}{%
9135       {%
9136         \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}}%
9137         \LWR@htmltag{/a}}%
9138       }%
9139     {%
9140       \LWR@stoppars%
9141       \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}}%
9142       \LWR@htmltag{/a}%
9143       \LWR@restartpars%
9144     }%
9145   }%
9146   {%
9147     \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}}%
9148     \LWR@htmltag{/a}}%
9149   }%
9150 }%
9151 }
```

\LWR@new@label ((*bookmark*) {*label*} [*type*])

\label during HTML output when not in SVG math mode, removing extra spaces around the label, as done by a regular L<sup>A</sup>T<sub>E</sub>X \label.

The `\label` is also used during a `\textrm{image}`, including `svg` math, since the special label handling is required, but `\LWR@sublabel` does not generate `HTML` tags inside a `\textrm{image}`.

`\clevereref` later encases this to add its own cross-referencing.

The optional *<bookmark>* is per the memoir class, and is ignored.

The optional  $\langle type \rangle$  is per the `ntheorem` package, and is ignored.

```
9152 \NewDocumentCommand{\LWR@new@label}{d() m o}{%
9153     \LWR@traceinfo{LWR@new@label: starting}%
9154     \LWR@traceinfo{LWR@new@label: !#2!}%
9155 \%bsphack%
```

Create a traditional LATEX label, as modified by cleveref:

9156 \LWR@orig@label{#2}%

Create a special label which holds the section number, LWR@htmlfilenumber, LWR@lateximagedepth, and LWR@lateximagenumber:

```
9157     \LWR@traceinfo{%
9158         LWR@new@label: filesectionnames is %
9159         \ifbool{FileSectionNames}{true}{false}%
9160     }%
9161     \LWR@traceinfo{%
9162         LWR@new@label: LWR@thisfilename is !\LWR@thisfilename!%
9163     }%
```

```

9164   \LWR@traceinfo{%
9165     LWR@new@label: LWR@htmlfilename is \arabic{LWR@htmlfilename}%
9166   }%
9167   \LWR@lwarplabel{#2}%
9168   \LWR@sublabel{#2}%
9169   % \esphack%
9170   \LWR@traceinfo{LWR@new@label: done}%
9171 }

```

### 73.4 References

\LWR@addlinktitle

```

9172 \newcommand*{\LWR@addlinktitle}{%
9173   \ifdefvoid{\LWR@ThisAltText}{}{ % space
9174     title="\LWR@ThisAltText" % space
9175     \gdef\LWR@ThisAltText{}%
9176   }%
9177 }

```

\LWR@startref {*label*} (Common code for \ref and \nameref.)

Open an HTML tag reference to a filename, # character, and a label.

```

9178 \newcommand*{\LWR@startref}[1]
9179 {%
9180   \LWR@sanitize{#1}%
9181   \LWR@traceinfo{LWR@startref A: !#1!}%

```

Create the filename part of the link:

```

9182   \LWR@htmlltag{a href="%"
9183   \LWR@traceinfo{LWR@startref B}%
9184   \LWR@print@mbox{\LWR@htmlrefsectionfilename{#1}}%
9185   \LWR@traceinfo{LWR@startref C}%
9186   \LWR@origpound%

```

Create the destination id:

See if LWR@lateximagedepth is unknown:

```

9187   \LWR@traceinfo{LWR@startref D: !#1!}%
9188   \ifcsundef{r@#1@lwarp}%

```

“??” if LWR@lateximagedepth is unknown, so create a link with an unknown destination:

```

9189   {%
9190     \LWR@traceinfo{LWR@startref D0: ??}%
9191     ??%
9192   }%

```

If `\LWR@lateximagedepth` is known. Use a `\textrimage` if the depth is greater than zero, or a regular link otherwise:

```

9193      {%
9194          \ifthenelse{\cnttest{\LWR@lateximagedepthref{#1}}{>}{0}}{%
9195              {%
9196                  \LWR@ImagesName\LWR@lateximagenumberref{#1}%
9197              }%
9198          {%
9199              \LWR@traceinfo{\LWR@startref D3}%

```

`\detokenize` is used to allow underscores in the labels:

```

9200          \LWR@print@mbox{\LWR@sanitized}%
9201      }%
9202  }%
9203  \LWR@traceinfo{\LWR@startref E}%

```

Closing quote:

```
9204      "%
```

Maybe add a title:

```

9205      \LWR@addlinktitle%
9206  }%
9207  \LWR@traceinfo{\LWR@startref F}%
9208 }%

```

`\LWR@subnewref {<label>} {<label or sub@label>}`

Factored for the `subfig` package. Uses the original label for the hyper-reference, but prints its own text, such as “1(b)”.

```

9209 \NewDocumentCommand{\LWR@subnewref}{m m}{%
9210     \LWR@traceinfo{\LWR@subnewref #1 #2}%
9211     \LWR@startref{#1}%
9212     \LWR@print@ref{#2}%
9213     \LWR@htmltag{/a}%
9214 }%

```

`\ref * {<label>}`    \ref is redefined to `\LWR@HTML@ref`, except inside the text part of a `\hyperref`, where it is redefined to `\LWR@ref@ignorestar`.

`\LWR@HTML@ref * {<label>}` Create an internal document reference link, or without a link if starred per `\hyperref`.

```

9215 \NewDocumentCommand{\LWR@HTML@ref}{s m}{%
9216     \LWR@traceinfo{\LWR@HTML@ref !#2!}%
9217     \IfBooleanTF{#1}{%
9218         {\LWR@print@ref{#2}}%
9219         {\LWR@subnewref{#2}{#2}}%

```

```

9220 }
9221
9222 \LWR@formatted{ref}
```

\LWR@ref@ignorestar \* {*label*} For use inside \hyperref. Ignores the star, then uses the original \ref.

```

9223 \NewDocumentCommand{\LWR@ref@ignorestar}{s m}{%
9224     \LWR@print@ref{#2}%
9225 }
```

\pagerefPageFor Text for page references.

```
9226 \newcommand*{\pagerefPageFor}{see }
```

\pageref \* {*label*} Create an internal document reference, or just the unlinked number if starred, per hyperref.

```

9227 \NewDocumentCommand{\LWR@new@pageref}{s m}{%
9228     \IfBooleanTF{#1}{%
9229         {(\pagerefPageFor\LWR@print@ref{#2})}%
9230         {(\cpageref{#2})}%
9231 }
```

\nameref {*label*}

```

9232 \newrobustcmd*{\nameref}[1]{%
9233     \LWR@traceinfo{nameref}%
9234     \LWR@startref{#1}%
9235     \LWR@traceinfo{nameref B}%
9236     \LWR@nameref{#1}%
9237     \LWR@traceinfo{nameref C}%
9238     \LWR@htmltag{/a}%
9239     \LWR@traceinfo{nameref: done}%
9240 }
```

\Nameref {*label*} In print, adds the page number. In HTML, does not.

```
9241 \LetLtxMacro{\Nameref}{\nameref}
```

### 73.5 Hyper-references

 Note that the code currently only sanitizes the underscore character. Additional characters should be rendered inert as well. See the `hyperref.sty` definition of `\gdef\hyper@normalise` for an example.

Pkg `hyperref`

 Do not tell other packages that `hyperref` is emulated. Some packages patch various

commands if `hyperref` is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

```
9242 % DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:  
9243 % \EmulatesPackage{hyperref}[2015/08/01]% Disabled. Do not do this.
```

Emulates `hyperref`:

`\@currentHref` Added to support backref.

```
9244 \AtBeginDocument{  
9245  
9246 \def\@currentHref{  
9247     autopage-\theLWR@currentautosec%  
9248 }  
9249  
9250 }
```

`\LWR@linkcatcodes` Sets catcodes before processing macros which have hyperlinks as arguments.

```
9251 \newcommand*{\LWR@linkcatcodes}{%  
9252     \catcode`\#=12%  
9253     \catcode`\%=12%  
9254     \catcode`\&=12%  
9255     \catcode`\~=12%  
9256     \catcode`\_=12%
```

For `babel-french`:

```
9257     \LWR@FBcancel%  
9258 }
```

`\LWR@linkmediacatcodes` Sets catcodes before processing macros which have hyperlinks as arguments. Modified for multimedia links.

```
9259 \newcommand*{\LWR@linkmediacatcodes}{%  
9260     \catcode`\#=12%  
9261     \catcode`\%=12%  
9262 %     \catcode`\&=12% left alone for splitting flash variables  
9263     \catcode`\~=12%  
9264     \catcode`\_=12%
```

For `babel-french`:

```
9265     \LWR@FBcancel%  
9266 }
```

`\LWR@subhyperref`  $\{\langle URL \rangle\}$

Starts a link for `\LWR@hrefb`. A group must have been opened first, with nullified catcodes. The text name is printed afterwards, after the group is closed and catcodes restored.

```

9267 \NewDocumentCommand{\LWR@subhyperref}{m}{%
9268   \LWR@traceinfo{\LWR@subhyperref !#1!}%
9269   \LWR@sanitize{#1}%
9270   \LWR@htmltag{%
9271     a href="\LWR@sanitized" % space
9272     \LWR@addlinktitle % space
9273     target="_{}blank" % space
9274   }%
9275 }

```

\LWR@subhyperreftext {*text*}

Finishes the hyperref for \LWR@hrefb. Catcodes must have been restored already. To be used after \LWR@subhyperref, and after its group has been closed.

```

9276 \newcommand{\LWR@subhyperreftext}[1]{%
9277   #1%
9278   \LWR@htmltag{/a}%
9279   \LWR@ensuredoingapar%
9280 }

```

\LWR@subhyperrefclass {*URL*} {*text*} {*htmlclass*}

```

9281 \NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
9282   \LWR@htmltag{%
9283     a % space
9284     href="\begingroup\@sanitize#1\endgroup" % space
9285     class="#3" % space
9286     \LWR@addlinktitle % space
9287   }\LWR@orignewline%
9288   #2%
9289   \LWR@htmltag{/a}%
9290   \LWR@ensuredoingapar%
9291 }

```

\href [*options*] {*URL*}

Create a link with accompanying text:

```

9292 \DeclareDocumentCommand{\LWR@hrefb}{O{} m}{%
9293   \LWR@ensuredoingapar%
9294   \LWR@subhyperref{#2}%
9295   \endgroup% restore catcodes
9296   \LWR@subhyperreftext%
9297 }
9298
9299 \newrobustcmd*\href{%
9300   \begingroup%
9301   \LWR@linkcatcodes%
9302   \LWR@hrefb%
9303 }

```

\nolinkurl {*URL*}

Print the name of the link without creating the link:

```

9304 \newcommand*{\LWR@nolinkurlb}[1]{%
9305     \LWR@ensuredoingapar%
9306     \def\LWR@templink{\#1}%
9307     @onelvel@sanitize\LWR@templink%
9308     \LWR@templink%
9309     \endgroup%
9310 }
9311
9312 \newrobustcmd*{\nolinkurl}{%
9313     \begingroup%
9314     \LWR@linkcatcodes%
9315     \LWR@nolinkurlb%
9316 }
```

\url {<URL>}

Create a link whose text name is the address of the link.

The url package may redefine \url, so it is \let to \LWR@urlahere and also redefined by lwarp-url.

```

9317 \DeclareDocumentCommand{\LWR@urlb}{m}{%
9318     \LWR@ensuredoingapar%
9319     \def\LWR@templink{\#1}%
9320     @onelvel@sanitize\LWR@templink%
9321     \href{\LWR@templink}{\LWR@templink}%
9322     \endgroup%
9323 }
9324
9325 \newrobustcmd*{\url}{%
9326     \begingroup%
9327     \LWR@linkcatcodes%
9328     \LWR@urlb%
9329 }
```

\LWR@subinlineimage {<alt> tag} {<class>} {<filename>} {<extension>} {<CSS style>}

Factored from lateximage.

```

9330 \newcommand*{\LWR@subinlineimage}[5]{%
9331     \ifblank{\#1}%
9332     {%
9333         \LWR@htmltag{img \LWR@indentHTML
9334             src="#3.#4" \LWR@indentHTML
9335             alt="#3" \LWR@indentHTML
9336             style="#5" \LWR@indentHTML
9337             class="#2" \LWR@orignewline
9338         }%
9339     }%
9340     {%
9341         \LWR@htmltag{img \LWR@indentHTML
9342             src="#3.#4" \LWR@indentHTML
9343         }%
9344     }%
9345 }
```

```
9343      alt="#1" \LWR@indentHTML
9344      style="#5" \LWR@indentHTML
9345      class="#2" \LWR@newline
9346      }%
9347      }%
9348 }

9349 \end{warpHTML}
```

Table 13: Float data structures

---

For each <type> of float (figure, table, etc.) there exists the following:

---

**counter <type>**: A counter called <type>, such as figure, table.

\<type>name: Name. \figurename prints “Figure”, etc.

\ext@<type>: File extension. \ext@figure prints “lof”, etc.

\fps@<type>: Placement.

\the<type>: Number. \thetable prints the number of the table, etc.

\p@<type>: Parent’s number. Prints the number of the [within] figure, etc.

\fnum@<type>: Prints the figure number for the caption.

\<type>name \the<type>, “Figure 123”.

\<type>: Starts the float environment. \figure or \begin{figure}

\end<type>: Ends the float environment. \endfigure or \end{figure}

\tf@<ext>: The L<sup>A</sup>T<sub>E</sub>X file identifier for the output file.

**LWR@have<type>**: A boolean remembering whether a \listof was requested for a float of this type.

**File with extension lo<f,t,a-z>**: An output file containing the commands to build the \listof<type> “table-of-contents” structure.

**Cross-referencing names**: For cleveref’s \cref and related, \crefname and \Crefname assign human-readable names for references to this float type.

---

## 74 Floats

Floats are supported, although partially through emulation.

Table 13 shows the data structure associated with each <type> of float.

\@makecaption is redefined to print the float number and caption text, separated by \CaptionSeparator, which works with the babel package to adjust the caption separator according to the language. French, for example, uses an en-dash instead of a colon: “Figure 123 – Caption text”.

### 74.1 Float environment

**for HTML output:** 9350 \begin{warpHTML}

\LWR@floatbegin {\<type>} [<placement>]      Begins a \newfloat environment.

---

```

9351 \NewDocumentCommand{\LWR@floatbegin}{m o}{%
9352     \ifbool{FormatWP}{\newline}{}
9353     \LWR@stoppars%

```

There is a new float, so increment the unique float counter:

```

9354     \addtocounter{\LWR@thisautoid}{1}%
9355     \booltrue{\LWR@freezethisautoid}%

9356     \begingroup%

```

Settings while inside the environment:

```

9357     \LWR@print@raggedright%

```

Open an **HTML** figure tag. The figure is assigned a **class** equal to its type, and another class according to the **float** package style, if used. Note that **\csuse** returns an empty string if **\LWR@floatstyle@<type>** is not defined.

```

9358     \LWR@htmltag{%
9359         figure id="\LWR@print@mbox{autoid-\arabic{\LWR@thisautoid}}" % space
9360         class="#1 \nameuse{\LWR@floatstyle@#1}"%
9361     }%
9362     \ifbool{FormatWP}{%
9363         \LWR@newline%
9364         \LWR@BlockClassWP{}{}{wp#1}%
9365     }{%

```

Update the caption type:

```

9366     \renewcommand*{\@capttype}{\#1}%
9367     \caption@settype{\#1}%

```

Mark the float for a word processor conversion:

```

9368     \LWR@startpars%
9369     \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%
9370
9371     === begin #1 ===
9372
9373 }{%

```

Look for **\centering**, etc:

```

9374     \LWR@futurenonspacet\let\LWR@mynexttoken\LWR@floatalignment%
9375 }

```

For koma-script. The following does not work for tables.

```

9376 \AtBeginDocument{%
9377
9378 \@ifpackagelloaded{tocbasic}{%

```

```

9379
9380 \appto\figure@atbegin{%
9381     \LWR@futureonospacelet\LWR@mynexttoken\LWR@floatalignment%
9382 }
9383
9384 }{}% tocbasic
9385
9386 }% AtBeginDocument

```

\@float Support packages which create floats directly.  
 \@dblfloat  
 9387 \let\@float\LWR@floatbegin  
 9388 \let\@dblfloat\LWR@floatbegin

\LWR@floatend Ends a \newfloat environment.

```
9389 \newcommand*\LWR@floatend{%
```

If saw a \centering, finish the center environment:

```
9390 \LWR@endfloatalignment%
```

Mark the float end for a word processor conversion:

```

9391 \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%
9392 === end ===
9394
9395 }{}%
9396 \LWR@stoppars%

```

Close an HTML figure tag:

```

9397 \ifbool{FormatWP}{\endLWR@BlockClassWP}{}
9398 \LWR@htmlelementend{figure}%
9399 \endgroup%
9400 \boolfalse{\LWR@freezethisautoid}%
9401 \LWR@startpars%
9402 \ifbool{FormatWP}{\newline}{}
9403 }

```

\end@float Support packages which create floats directly.  
 \@enddblfloat  
 9404 \let\end@float\LWR@floatend  
 9405 \let\end@dblfloat\LWR@floatend

## 74.2 Float tracking

Ctr \LWR@thisautoid A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
9406 \newcounter{\LWR@thisautoid}
```

Ctr `\LWR@thisautoidWP` A sequential counter for all word processor conversion <div>s. This is used to convince LIBREOFFICE to form a frame around this element.

```
9407 \newcounter{\LWR@thisautoidWP}
```

Bool `\LWR@freezethisautoid` Prevents multiple increments of `\LWR@thisautoid` inside a float.

```
9408 \newbool{\LWR@freezethisautoid}
9409 \boolfalse{\LWR@freezethisautoid}
```

`\LWR@forcenewautoidanchor` Adds a new <autoid> anchor.

```
9410 \newcommand*{\LWR@forcenewautoidanchor}{%
9411     \addtocounter{\LWR@thisautoid}{1}%
9412     \LWR@htmlltag{a id="\LWR@print@mbox{autoid-\arabic{\LWR@thisautoid}}"}%
9413     \LWR@htmlltag{/a}%
9414 }
```

`\LWR@newautoidanchor` Sometimes adds a new <autoid> anchor.

```
9415 \newcommand*{\LWR@newautoidanchor}{%
9416     \ifnumcomp{\value{\LWR@lateximagedepth}}{0}%
9417         {}%
9418         {\ifbool{\LWR@freezethisautoid}{\LWR@forcenewautoidanchor}}%
9419 }
```

`\@capttype` Remembers which float type is in use.

```
9420 \newcommand*{\@capttype}{}%
```

`\LWR@floatalignmentname` Set to center, flushleft, or flushright if saw `\centering`, `\raggedright`, or `\raggedleft`.

```
9421 \newcommand*{\LWR@floatalignmentname}{}%
```

`\LWR@floatalignment` If sees a `\centering`, `\raggedleft`, or `\raggedright`, creates a center, flushright, or flushleft environment.

```
9422 \newcommand*{\LWR@floatalignment}{%
9423     \ifdefstreq{\LWR@mynexttoken}{\centering}{%
9424         \center%
9425         \renewcommand*{\LWR@floatalignmentname}{center}%
9426     }%
9427     \ifdefstreq{\LWR@mynexttoken}{\raggedright}{%
9428         \flushleft%
9429         \renewcommand*{\LWR@floatalignmentname}{flushleft}%
9430     }%
9431     \ifdefstreq{\LWR@mynexttoken}{\raggedleft}{%
9432         \flushright%
9433         \renewcommand*{\LWR@floatalignmentname}{flushright}%
9434     }%
9435 }
```

\LWR@endfloatalignment Closes an environment from \LWR@floatalignment.

```

9436 \newcommand*\LWR@endfloatalignment{%
9437     \ifdefvoid{\LWR@floatalignmentname}{%
9438         {}%
9439         {\@nameuse{end\LWR@floatalignmentname}}%
9440     \renewcommand*\LWR@floatalignmentname{}%
9441 }
```

### 74.3 Caption inside a float environment

\CaptionSeparator How to separate the float number and the caption text.

```
9442 \AtBeginDocument{\providecommand*\CaptionSeparator{:\~}}
```

\@makecaption {\langle name and num\rangle} {\langle text\rangle}

Prints the float type and number, the caption separator, and the caption text.

```

9443 \AtBeginDocument{\renewcommand{\@makecaption}[2]{%
9444     \LWR@traceinfo{@makecaption}%
9445     \LWR@isolate{\#1}\CaptionSeparator\LWR@isolate{\#2}%
9446     \LWR@traceinfo{@makecaption: done}%
9447 }%
9448 }
```

### 74.4 Caption and LOF linking and tracking

When a new HTML file is marked in the L<sup>A</sup>T<sub>E</sub>X PDF file, the L<sup>A</sup>T<sub>E</sub>X page number at that point is stored in LWR@latestautopage, (and the associated filename is remembered by the special L<sup>A</sup>T<sub>E</sub>X labels). This page number is used to generate an autopage HTML <id> in the HTML output at the start of the new HTML file. Meanwhile, there is a float counter used to generate an HTML autoid <id> at the start of the float itself in the HTML file. The autopage and autoid values to use for each float are written to the .lof, etc. files just before each float's entry. These values are used by \l@figure, etc. to create the HTML links in the List of Figures, etc.

Ctr LWR@nextautoid Tracks autoid for floats. Tracks autopage for floats.

Ctr LWR@nextautopage These are updated per float as the .lof, .lot file is read.

```

9449 \newcounter{LWR@nextautoid}
9450 \newcounter{LWR@nextautopage}
```

\LWRsetnextfloat {\langle autopage\rangle} {\langle float autoid\rangle}

File \*\_html.lof This is written to the \*\_html.lof or \*\_html.lot file just before each float's usual entry. The autopage and the float's autoid are remembered for \l@figure to use when creating the HTML links.

```

9451 \newcommand*{\LWRsetnextfloat}[2]{%
9452     \setcounter{LWR@nextautopage}{#1}%
9453     \setcounter{LWR@nextautoid}{#2}%
9454 }

```

Ctr `LWR@latestautopage` Updated each time a new `HTML` file is begun. `\LWRsetnextfloat` is written with this and the autoid by the modified `\addcontentsline` just before each float's entry.

```

9455 \newcounter{LWR@latestautopage}
9456 \setcounter{LWR@latestautopage}{1}

```

Env `LWR@figcaption` An `HTML` `<figcaption>` is not allowed in places where `LATEX` does allow a figure caption, such as inside a `longtable` where the tabular has already started, or inside a `center` environment. Therefore, a `<div>` of class `figurecaption` is used instead.

```

9457 \newenvironment*{LWR@figcaption}{%
9458     \ifbool{FormatWP}{%
9459         \BlockClass[font-style:italic]{figurecaption}{%
9460             \LWR@print@vspace*\baselineskip}%
9461     }{%
9462         \BlockClass{figurecaption}{%
9463             \LWR@print@vspace*\baselineskip}%
9464     }%
9465 }%
9466 {\endBlockClass}

```

`\LWR@HTML@caption@begin {<type>}`

Low-level code to create `HTML` tags for captions.

The print versions are from the `caption` package.

```

9467 \newcommand*{\LWR@HTML@caption@begin}[1]{%
9468 {%
9469     \LWR@traceinfo{\LWR@HTML@caption@begin}%
}

```

Keep `par` and `minipage` changes local:

```

9470     \begingroup%

```

No need for a `minipage` or `\parbox` inside the caption:

```

9471     \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{%
9472     \RenewDocumentCommand{\parbox}{O{t} O{} O{t} m +m}##5}%

```

Enclose the original caption code inside an `HTML` tag:

```

9473     \LWR@figcaption%
9474     \LWR@traceinfo{\LWR@HTML@caption@begin: about to LWR@origcaption@begin}%
9475     \LWR@print@caption@begin{#1}%
9476     \LWR@traceinfo{\LWR@HTML@caption@begin: done}%
9477 }

```

\LWR@HTML@caption@end Low-level patches to create HTML tags for captions.

```
9478 \newcommand*\LWR@HTML@caption@end{%
9479 {%
9480   \LWR@traceinfo{\LWR@HTML@caption@end}%
9481   \LWR@print@caption@end%
```

Closing tag:

```
9482   \endLWR@figcaption%
9483   \endgroup%
9484   % \leavevmode% avoid bad space factor (0) error
9485   \LWR@traceinfo{\LWR@HTML@caption@end: done}%
9486 }
```

\caption@begin Low-level patches to create HTML tags for captions. These are assigned \AtBeginDocument  
 \caption@end so that other packages which modify captions will have already been loaded before saving the print-mode version.

```
9487 \AtBeginDocument{%
9488 \LWR@formatted{caption@begin}%
9489 \LWR@formatted{caption@end}%
9490 }
```

\captionlistentry Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```
9491 \let\origcaptionlistentry\captionlistentry
9492
9493 \renewcommand*\captionlistentry{%
9494   \LWR@ensuredoingapar%
9495   \origcaptionlistentry%
9496 }

9497 \def\LWR@LTcaptionlistentry{%
9498   \LWR@ensuredoingapar%
9499   \LWR@forcenewlineautoidanchor%
9500   \bgroup
9501   \@ifstar{\egroup\LWR@LT@captionlistentry}{%
9502     {\egroup\LWR@LT@captionlistentry}%
9503 }%
9504
9505 \def\LWR@LT@captionlistentry#1{%
9506   \caption@listentry@\firstoftwo[\LTcaptype]{#1}%
9507 }%
```

\addcontentsline Patched to write the autopage and autoid before each float's entry. No changes if writing .toc For a theorem, automatically defines \ext@<type> as needed, to mimic and reuse the float mechanism.

---

```

9508 \let\LWR@origaddcontentsline\addcontentsline
9509
9510 \renewcommand*\{\addcontentsline}{3}{%
9511     \ifstrequal{\#1}{toc}{% not TOC
9512         \ifnumcomp{\value{\LWR@lateximagedepth}}{0}{%
9513             {}%
9514             {\LWR@newautoianchor}%
9515         \ifcsvvoid{ext@#2}{\csdef{ext@#2}{\#1}}{}%
9516         \addtocontents{\@nameuse{ext@#2}}{%
9517             \protect\LWRsetnextfloat%
9518             {\arabic{\LWR@latestautopage}}%
9519             {\arabic{\LWR@thisautoid}}%
9520         }%
9521     }% not TOC
9522     \LWR@origaddcontentsline{\#1}{\#2}{\#3}%
9523 }

```

Pkg capt-of Either package provides `\captionof`, which is later patched at the beginning of the document.

`\captionof` Patched to handle paragraph tags.

```

9524 \AtBeginDocument{
9525
9526 \let\LWR@origcaptionof\captionof
9527
9528 \renewcommand*\{\captionof}{%
9529     \LWR@stoppars%
9530     \LWR@origcaptionof%
9531 }
9532
9533 }% AtBeginDocument

9534 \end{warpHTML}

```

## 75 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The `.toc`, `.lof`, and `.lot` files are named by the source code `\jobname`.

In HTML, the printed tables are placed inside a `<div>` of class `toc`, `lof`, or `lot`.

A “`sitetoc`” is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular L<sup>A</sup>T<sub>E</sub>X infrastructure is used for toc, along with some patches to generate HTML output.

**for HTML output:** 9535 \begin{warpHTML}

## 75.1 Reading and printing the toc

\LWR@myshorttoc {\langle toc/lof/lot/sidetoc\rangle}

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the @ character into a normal letter to allow formatting commands in the section names.

Unlike in regular L<sup>A</sup>T<sub>E</sub>X, the file is not reset after being read, since the sidetoc may be referred to again in each HTML page.

```
9536 \newcommand*{\LWR@myshorttoc}[1]{%
9537   \LWR@traceinfo{\LWR@myshorttoc: #1}%
9538   \LWR@ensuredoingapar%
```

Only if the file exists:

```
9539   \IfFileExists{\jobname.\#1}{%
9540     \LWR@traceinfo{\LWR@myshorttoc: loading}%
9541     \begingroup%
9542     \makeatletter%
```

 Many of the commands in the file will have @ characters in them, so @ must be made a regular letter.

```
9541   \begingroup%
9542   \makeatletter%
```

Read in the TOC file:

```
9543   \@input{\jobname.\#1}%
9544   \endgroup%
9545   }%
9546   {}%
9547   \LWR@traceinfo{\LWR@myshorttoc: done}%
9548 }
```

\LWR@subtableofcontents {\langle toc/lof/lot\rangle} {\langle sectionstarname\rangle}

Places a TOC/LOF/LOT at the current position.

```
9549 \NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
9550   \@ifundefined{chapter}%
9551     {\LWR@closeprevious{section}}%
9552     {\LWR@closeprevious{chapter}}%
```

Prints any pending footnotes so that they appear above the potentially large TOC:

```
9553 \LWR@printpendingfootnotes%
```

Place the list into its own chapter (if defined) or section:

```
9554 \@ifundefined{chapter}{\section*{\#2}}{\chapter*{\#2}}%
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
9555 \LWR@htmlelementclass{nav}{\#1}%
```

Create the actual list:

```
9556 \LWR@myshorttoc{\#1}%
```

Close the nav:

```
9557 \LWR@htmlelementclassend{nav}{\#1}%
9558 }
```

\@starttoc {\langle ext \rangle}

Patch \@starttoc to encapsulate the TOC inside HTML tags:

```
9559 \let\LWR@orig@starttoc\@starttoc
9560
9561 \renewcommand{\@starttoc}[1]{
9562   \LWR@htmlelementclass{nav}{\#1}%
9563   \LWR@orig@starttoc{\#1}%
9564   \LWR@htmlelementclassend{nav}{\#1}%
9565 }
```

Bool LWR@copiedsidetoc Used to only copy the TOC file to the sidetoc a single time.

(listings and perhaps other packages would re-use \tableofcontents for their own purposes, causing the sidetoc to be copied more than once, and thus end up empty.)

```
9566 \newbool{LWR@copiedsidetoc}
9567 \boolfalse{LWR@copiedsidetoc}
```

\tableofcontents Patch \tableofcontents, etc. to print footnotes first. newfloat uses \listoffigures for all future float types.

```
9568 \AtBeginDocument{
9569
9570 \let\LWR@origtableofcontents\tableofcontents
9571
9572 \renewcommand*{\tableofcontents}{%
```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```
9573 \ifboolexpr{bool{FormatWP} and bool{WPMarkTOC}}{  
9574     === table of contents ===  
9575 }  
9576 {  
9577 }
```

Copy the .toc file to .sidetoc for printing the sideroc. The original .toc file is renewed when \tableofcontents is finished.

```
9579 \ifbool{LWR@copiedsidetoc}{}{  
9580     \LWR@copyfile{\jobname.toc}{\jobname.sidetoc}  
9581     \booltrue{LWR@copiedsidetoc}  
9582 }  
9583 \LWR@printpendingfootnotes  
9584 \LWR@origtableofcontents  
9585 }  
9586 }% \tableofcontents  
9587  
9588 }% AtBeginDocument
```

#### \listoffigures

```
9589 \let\LWR@origlistoffigures\listoffigures  
9590  
9591 \renewcommand*{\listoffigures}{  
9592     \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{  
9593         === list of figures ===  
9594     }  
9595     {  
9596         \LWR@printpendingfootnotes  
9597         \LWR@origlistoffigures  
9598     }  
9599 }  
9600 }  
9601 }
```

#### \listoftables

```
9602 \let\LWR@origlistoftables\listoftables  
9603  
9604 \renewcommand*{\listoftables}{  
9605     \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{  
9606         === list of tables ===  
9607     }  
9608     {  
9609         \LWR@printpendingfootnotes  
9610         \LWR@origlistoftables  
9611     }  
9612 }  
9613 }  
9614 }
```

## 75.2 High-level toc commands

\listof {⟨type⟩} {⟨title⟩}

Emulate the \listof command from the float package (section 241). Used to create lists of custom float types. Also used to redefine the standard L<sup>A</sup>T<sub>E</sub>X \listoffigures and \listoftables commands.

```
9615 \NewDocumentCommand{\listof}{m +m}{%
9616   \@ifundefined{l@#1}{%
9617     \csdef{l@#1##1##2}{\hypertocfloat{1}{#1}{\@nameuse{ext@#1}}{##1}{##2}}%
9618   }{%
9619     \LWR@subtableofcontents{\@nameuse{ext@#1}}{#2}%
9620     \expandafter\newwrite\csname tf@\csname ext@#1\endcsname\endcsname%
9621     \immediate\openout \csname tf@\csname ext@#1\endcsname\endcsname\endcsname%
9622     \jobname.\@nameuse{ext@#1}\relax%
9623 }
```

## 75.3 Side toc

The “side toc” is a table-of-contents positioned to the side.

It may be renamed by redefining \sidetocname, and may contain paragraphs.

css may be used to format the sidetoc:

*CSS related to sidetoc:*

---

**div.sidetoccontainer:** The entire sidetoc.  
**div.sidetoctitle:** The title.  
**div.sidetoccontents:** The table of contents.

---

```
9624 \end{warpHTML}
```

**for HTML & PRINT:** 9625 \begin{warpall}

**Ctr SideTOCDepth** Controls how deep the side-TOC gets. Use a standard L<sup>A</sup>T<sub>E</sub>X section level similar to tocdepth. Warn if parts of the website may be inaccessible.

```
9626 \newcounter{SideTOCDepth}
9627 \setcounter{SideTOCDepth}{1}
9628
9629 \AtBeginDocument{%
9630   \ifnumcomp{\value{SideTOCDepth}}{<}{\value{FileDepth}}{%
9631     \PackageWarningNoLine{lwarp}
9632     {%
9633       SideTOCDepth is less than FileDepth, \MessageBreak
9634       so some website pages may be inaccessible%
9635     }}
```

---

```
9636     }{}
```

```
9637 }
```

\sidetocname Holds the default name for the sidetoc.

```
9638 \newcommand{\sidetocname}{Contents}
```

```
9639 \end{warpall}
```

**for HTML output:** 9640 \begin{warpHTML}

\LWR@sidetoc Creates the actual side-TOC.

```
9641 \newcommand*{\LWR@sidetoc}{%
```

```
9642     \LWR@forcenewpage
```

```
9643     \LWR@stoppars
```

```
9644 }
```

The entire sidetoc is placed into a nav of class sidetoc.

```
9645     \LWR@htmlelementclass{div}{sidetoccontainer}
```

```
9646     \LWR@htmlelementclass{nav}{sidetoc}
```

```
9647 
```

```
9648     \setcounter{tocdepth}{\value{SideTOCDepth}}
```

```
9649 }
```

The title is placed into a <div> of class sidetoctitle, and may contain paragraphs.

```
9650     \begin{BlockClass}{sidetoctitle}
```

```
9651     \ifcsvvoid{\thetitle}{}{\InlineClass{sidetocthetitle}{\thetitle}\par}
```

```
9652     \sidetocname
```

```
9653     \end{BlockClass}
```

The table of contents is placed into a <div> of class sidetoccontents.

```
9654     \begin{BlockClass}{sidetoccontents}
```

```
9655     \LinkHome
```

```
9656 
```

```
9657     \LWR@myshorttoc{sidetoc}
```

```
9658     \end{BlockClass}
```

```
9659     \LWR@htmlelementclassend{nav}{sidetoc}
```

```
9660     \LWR@htmlelementclassend{div}{sidetoccontainer}
```

```
9661 }
```

## 75.4 Low-level toc line formatting

\numberline {⟨number⟩}

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```
9662 \newcommand*{\LWR@numberline}[1]{%
9663     \LWR@sectionnumber{#1}\quad%
9664 }
9665
9666 \LetLtxMacro\numberline\LWR@numberline
```

\LWR@maybetocdata Replaced by `tocdata`. Adds author name.

```
9667 \newcommand*{\LWR@maybetocdata}{}%
```

\hypertoc {<1: depth>} {<2: type>} {<3: name>} {<4: page>}

Called by `\l@section`, etc. to create a hyperlink to a section.

The `autopage` label is always created just after the section opens.

**#1** is depth

**#2** is section, subsection, etc.

**#3** the text of the caption

**#4** page number

```
9668 \NewDocumentCommand{\hypertoc}{m m +m m}{%
9669     \LWR@traceinfo{hypertoc !#1!#2!#3!#4!}}%
```

Respond to `tocdepth`:

```
9670     \ifthenelse{\c@nttest{#1}{<=}{\value{tocdepth}}}{%
9671         %
9672         \LWR@startpars%
```

Create an `HTML` link to `<filename>#autosec-(page)`, with the name, of the given `HTML` class.

`\BaseJobname` is added to the label in case `xr` or `xr-hyper` are used.

```
9673             \LWR@subhyperrefclass{%
9674                 \LWR@htmlrefsectionfilename{\BaseJobname-autopage-#4}%
9675                 \LWR@origpound\LWR@print@mbox{autosec-#4}%
9676             }{#3}{toc#2}}%
9677
9678             \LWR@maybetocdata%
9679             }%
9680             {}%
9681             \LWR@traceinfo{hypertoc done}%
9682 }
```

ctr lofdepth toc depth for figures.

```
9683 \@ifclassloaded{memoir}{}{  
9684     \newcounter{lofdepth}  
9685     \setcounter{lofdepth}{1}  
9686 }
```

ctr lotdepth toc depth for tables.

```
9687 \@ifclassloaded{memoir}{}{  
9688     \newcounter{lotdepth}  
9689     \setcounter{lotdepth}{1}  
9690 }
```

\hypertocfloat {\langle 1: depth\rangle} {\langle 2: type\rangle} {\langle 3: ext of parent\rangle} {\langle 4: caption\rangle} {\langle 5: page\rangle}

#1 is depth

#2 is figure, table, etc.

#3 is lof, lot, of the parent.

#4 the text of the caption

#5 page number

```
9691 \newcommand{\hypertocfloat}[5]{%  
9692     \LWR@startpars%
```

If some float-creation package has not yet defined the float type's lofdepth counter, etc, define it here:

```
9693     \@ifundefined{c@#3depth}{%  
9694         \newcounter{#3depth}%%  
9695         \setcounter{#3depth}{1}%%  
9696     }{}%
```

Respond to lofdepth, etc.:

```
9697     \LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%  
9698     \ifthenelse{\cnttest{#1}{<=}{\arabic{#3depth}}}{%  
9699     }%  
9700     \LWR@startpars%
```

Create an HTML link to filename#autoid-(float number), with text of the caption, of the given HTML class.

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
9701             \LWR@subhyperrefclass{  
9702                 \LWR@htmrefsectionfilename{  
9703                     \BaseJobname-autopage-\arabic{\LWR@nextautopage}}%
```

```

9704          }%
9705          \LWR@origpound\LWR@print@mbox{autoid-\arabic{LWR@nextautoid}}}}}%
9706          {#4}{toc#2}%

9707          \LWR@maybetocdata%

9708          \LWR@stopars%
9709          }%
9710          {}%
9711 }

```

Automatically called by \contentsline:

```
\l@book  {\langle name\rangle} {\langle page\rangle}
```

Uses \DeclareDocumentCommand in case the class does not happen to have a \book.

```
9712 \DeclareDocumentCommand{\l@book}{m m}{\hypertoc{-2}{book}{#1}{#2}}
```

```
\l@part  {\langle name\rangle} {\langle page\rangle}
```

Uses \DeclareDocumentCommand in case the class does not happen to have a \part.

```
9713 \DeclareDocumentCommand{\l@part}{m m}{\hypertoc{-1}{part}{#1}{#2}}
```

```
\l@chapter {\langle name\rangle} {\langle page\rangle}
```

Uses \DeclareDocumentCommand in case the class does not happen to have a \chapter.

```

9714 \@ifundefined{chapter}
9715 {}
9716 {
9717 \DeclareDocumentCommand{\l@chapter}{m m}
9718   {\hypertoc{0}{chapter}{#1}{#2}}
9719 }

```

```
\l@section  {\langle name\rangle} {\langle page\rangle}
```

```
9720 \renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
```

```
\l@subsection {\langle name\rangle} {\langle page\rangle}
```

```
9721 \renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
```

```
\l@subsubsection {\langle name\rangle} {\langle page\rangle}
```

```
9722 \renewcommand{\l@subsubsection}[2]{\hypertoc{3}{subsubsection}{#1}{#2}}
```

---

```
\l@paragraph {\langle name\rangle} {\langle page\rangle}

9723 \renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}


\l@subparagraph {\langle name\rangle} {\langle page\rangle}

9724 \renewcommand{\l@subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}


\l@figure {\langle name\rangle} {\langle page\rangle}

9725 \renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}


\l@table {\langle name\rangle} {\langle page\rangle}

9726 \renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}


9727 \end{warpHTML}
```

## 76 Index and glossary

See:

[http://tex.stackexchange.com/questions/187038/  
how-to-mention-section-number-in-index-created-by-imakeidx](http://tex.stackexchange.com/questions/187038/how-to-mention-section-number-in-index-created-by-imakeidx)

Index links are tracked by the counter `LWR@autoindex`. This counter is used to create a label for each index entry, and a reference to this label for each entry in the index listing. This method allows each index entry to link directly to its exact position in the document.

```
for HTML output: 9728 \begin{warpHTML}

9729 \newcounter{LWR@autoindex}
9730 \setcounter{LWR@autoindex}{0}
9731
9732 \newcounter{LWR@autoglossary}
9733 \setcounter{LWR@autoglossary}{0}

Env theindex

9734 \@ifundefined{chapter}
9735   {\newcommand*{\LWR@indexsection}[1]{\section*{#1}}}
9736   {\newcommand*{\LWR@indexsection}[1]{\chapter*{#1}}}
9737
9738
9739 \AtBeginDocument{
9740
9741 \ renewenvironment*{theindex}{%
9742   \LWR@indexsection{\indexname}%
9743   \let\item\LWR@indexitem%
```

```
9744     \let\subitem\LWR@indexsubitem%
9745     \let\subsubitem\LWR@indexsubsubitem%
9746 }{%
9747
9748 }% AtBeginDocument
```

\LWR@indexitem [*index key*] The optional argument is added to support `repeatindex`.

```
9749 \newcommand{\LWR@indexitem}[1][\emptyset]{%
9750
9751     \InlineClass{indexitem}{\LWR@htmlcomment{}#1}%
9752 }
```

\LWR@indexsubitem

```
9753 \newcommand{\LWR@indexsubitem}{%
9754
9755     \InlineClass{indexsubitem}{\LWR@htmlcomment{}%}
9756 }
```

\LWR@indexsubsubitem

```
9757 \newcommand{\LWR@indexsubsubitem}{%
9758
9759     \InlineClass{indexsubsubitem}{\LWR@htmlcomment{}%}
9760 }
```

\@wrindex {*term*} Redefined to write the `LWR@autoindex` counter instead of page.

```
9761 \def\LWR@wrindex#1{%
9762     \addtocounter{LWR@autoindex}{1}%
9763     \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
9764     \protected@write{\indexfile}{}{%
9765         \string\indexentry{\arabic{LWR@autoindex}}{}}%
9766     \endgroup%
9767     \esphack%
9768 }
9769
9770 \AtBeginDocument{%
9771 \let\@wrindex\LWR@wrindex
9772 }
```

\@wrglossary {*term*} Redefined to write the `LWR@latestautopage` counter instead of page.

```
9773 \def\@wrglossary#1{%
9774     \addtocounter{LWR@autoglossary}{1}%
9775     \LWR@new@label{LWRglossary-\theLWR@autoglossary}}%
9776     \protected@write{\glossaryfile}{}{%
9777         \string\glossaryentry{\theLWR@autoglossary}}%
9778     \endgroup%
9779     \esphack%
9780 }
```

---

```
\LWR@indexnameref {<LWR@autoindex>}
```

Creates a hyperlink based on the given entry's autoindex.

```
9781 \newcommand*{\LWR@indexnameref}[1]{\nameref{LWRindex-\#1}}
```

```
\LWR@doindexentry {<LWR@autoindex, or macros.>}
```

Creates a hyperlink, or handles \see, \textbf{etc}.

```
9782 \newrobustcmd{\LWR@doindexentry}[1]{%
9783     \IfInteger{#1}{%
9784         {\LWR@indexnameref{#1}}%
9785     {#1}%
9786 }}
```

```
\LWR@hyperindexrefnullified Handles macros commonly seen inside an \index entry. Each macro is redefined to
create and format a link to its entry.
```

⚠ **index formatting** To handle additional macros:

```
\appto{\LWR@hyperindexrefnullified}{...}
```

```
9787 \newcommand{\LWR@hyperindexrefnullified}{%
9788     \renewrobustcmd{\emph}[1]{\LWR@HTML@emph{\LWR@doindexentry{\#1}}}%
9789     \renewrobustcmd{\textbf}[1]{\LWR@HTML@textbf{\LWR@doindexentry{\#1}}}%
9790     \renewrobustcmd{\texteb}[1]{\LWR@HTML@texteb{\LWR@doindexentry{\#1}}}%
9791     \renewrobustcmd{\textlg}[1]{\LWR@HTML@textlg{\LWR@doindexentry{\#1}}}%
9792     \renewrobustcmd{\textrm}[1]{\LWR@HTML@textrm{\LWR@doindexentry{\#1}}}%
9793     \renewrobustcmd{\textsf}[1]{\LWR@HTML@textsf{\LWR@doindexentry{\#1}}}%
9794     \renewrobustcmd{\texttt}[1]{\LWR@HTML@texttt{\LWR@doindexentry{\#1}}}%
9795     \renewrobustcmd{\textup}[1]{\LWR@HTML@textup{\LWR@doindexentry{\#1}}}%
9796     \renewrobustcmd{\textsc}[1]{\LWR@HTML@textsc{\LWR@doindexentry{\#1}}}%
9797     \renewrobustcmd{\textulc}[1]{\LWR@HTML@textulc{\LWR@doindexentry{\#1}}}%
9798     \renewrobustcmd{\textsi}[1]{\LWR@HTML@textsi{\LWR@doindexentry{\#1}}}%
9799     \renewrobustcmd{\textit}[1]{\LWR@HTML@textit{\LWR@doindexentry{\#1}}}%
9800     \renewrobustcmd{\textsl}[1]{\LWR@HTML@textsl{\LWR@doindexentry{\#1}}}%
9801 }
```

```
\hyperindexref {<LWR@autoindex>}
```

\hyperindexref{LWR@autoindex} is inserted into \*.ind by the `makeindex` style file `lwarf.ist` or the `xindy` style file `lwarf.xdy`.

```
9802 \newcommand{\hyperindexref}[1]{%
```

In long index lines with numerous entries, `makeindex` can insert a newline before the page number, resulting in an extra space before the first digit. If the first character is a space, remove it first.

```
9803 \def\LWR@tempone{#1}%
9804 \IfBeginWith{\LWR@tempone}{ }{%
```

---

```
9805     \StrGobbleLeft{\LWR@tempone}{1}[\LWR@tempone]%
9806 }%}
```

If a numeric entry, create a link. If not numeric, such as \see, use the entry as-is. \emph, \textit, etc. have been redefined above to create and format the entry.

```
9807 \IfInteger{\LWR@tempone}%
9808   {\LWR@indexnameref{\LWR@tempone}}%
9809   {%
9810     \begingroup%
9811     \LWR@hyperindexrefnullified%
9812     #1%
9813     \endgroup%
9814   }%
9815 }

9816 \end{warpHTML}
```

**for PRINT output:** A null command for print mode, in case `hyperref` was not used:

```
9817 \begin{warpprint}
9818 \newcommand{\hyperindexref}[1]{#1}
9819 \end{warpprint}
```

**for HTML & PRINT:** For the `glossaries` package, try to prevent an error where `\glo@name` was not found:

```
9820 \begin{warpall}
9821 \providecommand{\glo@name}{}%
9822 \end{warpall}
```

## 77 Bibliography presentation

**for HTML output:** 9823 `\begin{warpHTML}`

```
\bibliography {\langle filenames\rangle}
```

Modified to use the base jobname instead of the `_html` jobname.

```
9824 \def\bibliography#1{%
9825   \if@filesw
9826     \immediate\write\@auxout{\string\bibdata{#1}}%
9827   \fi
9828 %     \input{\jobname.bbl}% original
9829   \begingroup%
9830   \input{\BaseJobname.bbl}% lwarp
9831   \endgroup%
9832 }
```

```
@biblabel {\langle text-refnumber\rangle}
```

```
9833 \renewcommand{\@biblabel}[1]{[#1]\quad}
```

**Env thebibliography** To emphasize document titles in the bibliography, the following redefines \em inside thebibliography to gather everything until the next closing brace, then display these tokens with \textit.

*Adapted from embracedef.sty, which is by TAKAYUKI YATO:*

<https://gist.github.com/zr-tex8r/b72555e3e7ad2f0a37f1>

```

9834 \AtBeginDocument{
9835
9836 \AtBeginEnvironment{thebibliography}{

9837
9838 \providecommand*\LWR@newem}[1]{\textit{\#1}}
9839
9840 \renewrobustcmd{\em}{%
9841   \begingroup
9842     \gdef\LWR@em@after{\LWR@em@finish\LWR@newem}%
9843     \afterassignment\LWR@em@after
9844     \toks@\bgroup
9845 }
9846
9847 \def\LWR@em@finish#1{%
9848   \xdef\LWR@em@after{\noexpand#1{\the\toks@}}%
9849 }
9850 \LWR@em@after\egroup
9851 }
9852
9853 }% \AtBeginEnvironment{thebibliography}
9854
9855 }% \AtBeginDocument

9856 \end{warpHTML}

```

## 78 Restoring original formatting

**\LWR@restoreorigformatting** Used to temporarily restore the print-mode meaning of a number of formatting, graphics, and symbols-related macros while generating SVG math or a `lateximage`.

Must be used inside a group.

Sets `\LWR@formatting` to print until the end of the group.

A number of packages will `\appto` additional actions to this macro.

Various packages add to this macro using `\appto`.

**for HTML output:** 9857 `\begin{warpHTML}`

```

9858 \newcommand*\LWR@restoreorigformatting}{%
9859   \LWR@traceinfo{\LWR@restoreorigformatting}%

```

Numerous macros change their print/HTML meaning depending on `\LWR@formatting`:

```

9860  \renewcommand*\{LWR@formatting}{print}%
9861  \linespread{1}%
9862  \let\par\LWR@origpar%
9863  \LWR@select@print@hskip%
9864  \LetLtxMacro\hfil\LWR@orighfil%
9865  \let\hss\LWR@orighss%
9866  \let\llap\LWR@origllap%
9867  \let\rlap\LWR@origrlap%
9868  \let\hfilneg\LWR@orighfilneg%
9869  \let\,\LWR@origcomma% disable HTML short unbreakable space
9870  \let\thinspace\LWR@origthinspace% disable HTML short unbreakable space
9871  \let\negthinspace\LWR@orignegthinspace% disable HTML negative short unbreakable space
9872  \let\textellipsis\LWR@origtextellipsis%
9873  \let\textless\LWR@origtextless%
9874  \let\textgreater\LWR@origtextgreater%
9875  \let\&\LWR@origampersand%
9876  \LetLtxMacro\em\LWR@origem%
9877  \LetLtxMacro\normalfont\LWR@orignormalfont%
9878  \let\sp\LWR@origsp%
9879  \let\sb\LWR@origsb%
9880  \LetLtxMacro\textsuperscript\LWR@origtextsuperscript%
9881  \LetLtxMacro@textsuperscript\LWR@orig@textsuperscript%
9882  \LetLtxMacro\textsubscript\LWR@origtextsubscript%
9883  \LetLtxMacro@textsubscript\LWR@orig@textsubscript%
9884  \LetLtxMacro\underline\LWR@origunderline%
9885  \let~\LWR@origtilde%
9886  \let\enskip\LWR@origenskip%
9887  \let\quad\LWR@origquad%
9888  \let\qquad\LWR@origqquad%

```

\endtabular must be restored to its original, instead of relying on lwarp's \LWR@formatted mechanism:

```

9889  \LetLtxMacro\endtabular\LWR@origendtabular%
9890  \csletcs{\endtabular}{\LWR@origendtabular}%
9891  \LetLtxMacro\noalign\LWR@orignoalign%
9892  \LetLtxMacro\hline\LWR@orighline%
9893  \let\newline\LWR@orignewline%
9894  \LetLtxMacro\includegraphics\LWR@origincludegraphics%
9895  \LetLtxMacro{@ensuredmath}\LWR@origensuredmath%

```

---

```

9896   \let\math\LWR@orig@math%
9897   \let\endmath\LWR@orig@endmath%
9898   \let\displaymath\LWR@orig@displaymath%
9899   \let\enddisplaymath\LWR@orig@enddisplaymath%
9900 %
9901   \LWR@restoreorigaccents%
9902   \LWR@restoreoriglists%
9903 %
9904   \LWR@FBcancel%
9905 }

9906 \end{warpHTML}

```

## 79 Math

### 79.1 Limitations

See [Math](#), section 8.7.

### 79.2 HTML alt tag names

Redefinable names for the HTML alt tags, for translation according to the reader's native language.

**for HTML & PRINT:** 9907 \begin{warpall}

\AltTextOpen The opening part of HTML alt tag for an image. The default is a left parenthesis.

Default: (

```
9908 \newcommand*\{\AltTextOpen\}{{()}}
```

\AltTextClose The closing part of HTML alt tag for an image. The default is a right parenthesis.

Default: (

```
9909 \newcommand*\{\AltTextClose\}{})
```

\ImageAltText The HTML alt tag for an image.

Default: image

```
9910 \newcommand*\{\ImageAltText\}{image}
```

\MathImageAltText The HTML alt tag for an SVG math image.

Default: "math image"

```
9911 \newcommand*\{\MathImageAltText\}{math image}
```

---

\LWR@ThisAltText The HTML alt tag for the next image. Cleared after use, and also after each `\lateximage`, `\LWR@subsingle$`, and each use of MATHJAX.

```
9912 \newcommand*\LWR@ThisAltText{}
```

```
\ThisAltText {\langle text \rangle}
```

Assigns the HTML alt tag for the next image generated by `lwarp`, such as a `\lateximage`, `picture`, or SVG math.

```
9913 \newcommand*\ThisAltText[1]{%
9914     \renewcommand{\LWR@ThisAltText}{#1}%
9915 }
```

\PackageDiagramAltText Appended to the `\lateximage` HTML alt tag for the images generated by many packages.

Default: “diagram”

```
9916 \newcommand*\PackageDiagramAltText[1]{diagram}
```

```
9917 \end{warpall}
```

### 79.3 Inline and display math

**for HTML output:** 9918 `\begin{warpHTML}`

Ctr `\LWR@externalfilecnt` Counter for the external files which are generated and then referenced from the HTML:

```
9919 \newcounter{\LWR@externalfilecnt}
```

Bool `\LWR@indisplaymathimage` True if processing display math for SVG output. Inside a `\lateximage`, display math is only set to print-mode output if `\LWR@indisplaymathimage` is false. Used to avoid nullifying display math before it has been completed.

```
9920 \newbool{\LWR@indisplaymathimage}
```

Bool `\LWR@xfakebold` True if `\xfakebold` `\setBold` is in use.

```
9921 \newbool{\LWR@xfakebold}
9922 \boolfalse{\LWR@xfakebold}
```

`\LWR@orig@setBold` Redefined by `lwarp-xfakebold`.

```
9923 \newcommand*\LWR@orig@setBold{}
```

`\LWR@orig@unsetBold` Redefined by `lwarp-xfakebold`.

```
9924 \newcommand*\LWR@orig@unsetBold{}
```

\LWR@applyxfakebold Redefined by lwarp-xfakebold.

```
9925 \newcommand*{\LWR@applyxfakebold}{}%
```

\LWR@setcurrentfont Sets the actual L<sup>A</sup>T<sub>E</sub>X font to that which was selected for HTML output. Ex: In HTML mode, \bfseries sets \LWR@f@series to “bf”. This sets the PDF output here for use inside a *lateximage*.

```
9926 \newcommand*{\LWR@setcurrentfont}{%
9927   \LWR@traceinfo{Using font family \LWR@f@family}%
9928   \nameuse{\LWR@print@\LWR@f@family family}%
9929   \LWR@traceinfo{Using font series \LWR@f@series}%
9930   \nameuse{\LWR@print@\LWR@f@series series}%
9931   \LWR@traceinfo{Using font shape \LWR@f@shape}%
9932   \nameuse{\LWR@print@\LWR@f@shape shape}%
9933   \LWR@traceinfo{Using font caps shape \LWR@f@shapecaps}%
9934   \nameuse{\LWR@print@\LWR@f@shapecaps shape}%
9935 }
```

\\$ Plain dollar signs appearing in the HTML output may be interpreted by MATHJAX to be math shifts. For a plain text dollar \\$, use an HTML entity to avoid it being interpreted by MATHJAX, unless are inside a *lateximage*, in which case it will not be seen by MATHJAX.

```
9936 \let\LWR@origtextdollar\$
9937
9938 \renewcommand*{\$}{%
9939   \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}{%
9940     {\LWR@origtextdollar}%
9941     {\HTMLunicode{00024}}%
9942 }}
```

**File** `lwarp_baseline_marker.png` A marker to be used to help *pdfcrop* identify the inline math baseline and width. If either *graphicx* or *graphics* is loaded, this marker is placed at the lower left and lower right corners of the inline math. *pdfcrop* is then able to identify the width of the image, and also the height of an image such as a horizontal dash which does not otherwise touch the baseline.

**File** `lwarp_baseline_marker.eps` A marker with alpha or opacity of 0% is not registered by *pdfcrop*, so the marker is a small square block of 1% alpha, which seems to work while still being effectively invisible in the final SVG image.

If *graphicx* is loaded, this marker is sized as a tiny 1 sp square. If *graphics* is loaded, this marker is used at its default size of around .25 pt. If neither *graphics* package is loaded, the marker is replaced by a 10 sp horizontal space, and there is no assistance for determining baseline or width of the inline math image. The best results are obtained when using *graphicx*.

\LWR@addbaselinemarker Places a small marker in an svg inline image. If *graphics* or *graphicx* are loaded, the marker is a mostly transparent image. If neither is loaded, no marker is used.

```
9943 \AtBeginDocument{
```

```

9944
9945 \ifpdf
9946     \newcommand*{\LWR@baselinename}{l warp_baseline_marker.png}
9947 \else
9948     \ifXeTeX
9949         \newcommand*{\LWR@baselinename}{l warp_baseline_marker.png}
9950     \else
9951         \newcommand*{\LWR@baselinename}{l warp_baseline_marker.eps}
9952     \fi
9953 \fi
9954
9955 \IfFileExists{\LWR@baselinename}%
9956 {
9957     \@ifpackageloaded{graphicx}{%
9958         \newcommand*{\LWR@addbaselinemarker}{%
9959             \LWR@originincludegraphics{\LWR@baselinename}%
9960         }%
9961     }%
9962     \@ifpackageloaded{graphics}{%
9963         \newcommand*{\LWR@addbaselinemarker}{%
9964             \LWR@originincludegraphics{\LWR@baselinename}%
9965         }%
9966     }%
9967     \PackageWarningNoLine{l warp}{Load graphicx or graphics
9968         for improved\MessageBreak
9969         SVG math baselines}%
9970     }%
9971     \newcommand*{\LWR@addbaselinemarker}{}%
9972 }
9973 }%
9974 }% l warp_baseline_marker.png or .eps is not present
9975 \PackageWarningNoLine{l warp}{%
9976     File \LWR@baselinename\space is not installed\MessageBreak
9977     alongside the l warp-*.sty files,\MessageBreak
9978     so SVG math baselines may not be accurate}%
9979 \newcommand*{\LWR@addbaselinemarker}{}%
9980 }
9981
9982 }% AtBeginDocument

```

**Bool** `\LWR@unknownmathsize` If `Tikz` or other objects are used inside math mode, the resulting image may exceed the `TeX` box, resulting in an incorrect measurement of the size of the resulting image. If this is so, the `HTML` styles for image size and depth will be neutralized.

```
9983 \newbool{\LWR@unknownmathsize}
```

`\LWR@singledollarmeasure`  $\{\langle \text{math expression} \rangle\}$

Measures the size of the image of the math expression.

(In some circumstances `SVG` math is used even if `MATHJAX` is preferred.)

**SVG math:** `\LWR@origensuredmath` is part of argument #4.

**SVG math \ensuremath:**  $\backslash LWR@origensuredmath$  is part of argument #4.

**SVG dynamic math:**  $\backslash LWR@origensuredmath$  is part of argument #4.

**Mathjax:** Argument #4 is the contents of the math expression without  $\backslash LWR@origensuredmath$ .  
This case is handled above.

**Mathjax \ensuremath:**  $\backslash LWR@origensuredmath$  is part of argument #4.

**Mathjax dynamic math:** Argument #4 is the contents of the math expression without  
 $\backslash LWR@origensuredmath$ , so  $\backslash LWR@origensuredmath$  is added below.

**\ifmmode:** Included “just in case”.

Factored from  $\backslash LWR@subsingledollarsvg$ .

```
9984 \newcommand*{\LWR@singledollarmeasure}[1]{%
9985     \begingroup%
```

Temporarily disable formatting while measuring the image parameters:

```
9986     \LWR@restoreorigformatting%
9987     \RenewDocumentEnvironment{lateximage}{s o s o o}{}{}% inside group
9988     \LWR@print@normalsize%
```

Temporarily set font for the HTML PDF output:

```
9989     \LWR@setcurrentfont%
```

`lateximagedepth` must be nested to avoid generating paragraph tags. *AMS* math modifies the `\text` macro such that `\addtocounter` does not always occur as expected.  
Lower-level code is used instead.

```
9990     \global\advance\c@LWR@lateximagedepth 1\relax%
```

Typeset the math in a box. While doing so, some macros or environments may set  $\LWR@unknownmathsize$ , in which case this will be used to cancel the HTML styles being generated here.

```
9991     \boolfalse{\LWR@unknownmathsize}%
9992     \ifmmode%
9993         \global\sbox{\LWR@singledollarbox}{#1}%
9994     \else%
9995         \ifbool{\LWR@dynamicmath}{%
9996             \ifbool{\mathjax}{%
9997                 \global\sbox{\LWR@singledollarbox}{%
9998                     {\LWR@origensuredmath{#1}}%
9999                 }%
10000                 \global\sbox{\LWR@singledollarbox}{#1}%
10001             }%
10002         }{%
10003             \global\sbox{\LWR@singledollarbox}{#1}%
10004         }%
10005     \fi%
```

Add a small and almost transparent marker at the depth of the image.

A math minus sign has the same depth as a plus, even though it does not draw anything below the baseline. This means that *pdfcrop* would crop the image without depth. The marker below the baseline is seen by *pdfcrop* and preserves the depth.

```
10006 \global\sbox{\LWR@singledollarbox}{%
10007   \usebox{\LWR@singledollarbox}%
10008   \raisebox{-\dp\LWR@singledollarbox}{%
10009     \LWR@addbaselinemarker}%
10010   }%
10011 }
```

More low-level code to undo the counter change.

```
10012 \global\advance\c@LWR@lateximagedepth -1\relax% Due to AmS \text macro.
```

Measure the depth:

```
10013 \setlength{\LWR@singledollardepth}{%
10014   \LateximageFontSize\dp\LWR@singledollarbox}%
10015 }
```

Make the length a global change:

```
10016 \global\let\LWR@singledollardepth=\LWR@singledollardepth%
```

Likewise for width:

```
10017 \setlength{\LWR@singledollarwidth}{%
10018   \LateximageFontSize\wd\LWR@singledollarbox}%
10019 }%
10020 \global\let\LWR@singledollarwidth=\LWR@singledollarwidth%
```

Likewise for total height:

```
10021 \setlength{\LWR@singledollarheight}{%
10022   \LateximageFontSize\ht\LWR@singledollarbox}%
10023 }%
10024 \addtolength{\LWR@singledollarheight}{%
10025   \LateximageFontSize\dp\LWR@singledollarbox}%
10026 }%
10027 \global\let\LWR@singledollarheight=\LWR@singledollarheight%
```

```
10028 \endgroup%
10029 }
```

\LWR@subsingledollarsvg \* {*2: alt text*} {*3: add'l hashing*} {*4: math expression*}

For inline math. Uses SVG math. The image is measured and adjusted to the baseline of the HTML output, and placed inside a *Lateximage*.

(In some circumstances SVG math is used even if MATHJAX is preferred.)

Factored from `\LWR@subsingle dollar`.

```
10030 \newcommand*{\LWR@subsingle dollarsvg}[4]{%
```

Measure the depth, width, and height of the math image:

```
10031     \LWR@singledollarmeasure{#4}%
```

Set a style for the the height or width. The `em` unit is used so that the math scales according to the user's selected font size.

Start with the greater of the width or the height, biased towards the width:

```
10032     \ifdimgreater{\LWR@singledollarwidth}{.7\LWR@singledollarheight}{%
10033         \def\LWR@singledollarstyle{%
10034             width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
10035         }%
10036     }{%
10037         \def\LWR@singledollarstyle{%
10038             height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
10039         }%
10040     }%
```

If a very narrow width, use the height.

```
10041     \ifdimless{\LWR@singledollarwidth}{.2em}{%
10042     }{%
10043         \def\LWR@singledollarstyle{%
10044             height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
10045         }%
10046     }%
10047     {}%
```

If very wide and short, use the width:

```
10048     \ifdimless{\LWR@singledollarheight}{.2em}{%
10049     }{%
10050         \def\LWR@singledollarstyle{%
10051             width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
10052         }%
10053     }%
10054     {}%
```

If there is significant text depth, add the depth to the style.

```
10055     \ifdimgreater{\LWR@singledollardepth}{0.05ex}{%
10056         \def\LWR@singledollardepthstyle{%
10057             \ ; % extra space
10058             \LWR@print@mbox{%
10059                 vertical-align:-\LWR@convertto{em}{\the\LWR@singledollardepth} em%
10060             } % extra space
10061         }%
10062     }{%
10063         \def\LWR@singledollardepthstyle{}%
10064     }%
```

If using certain Tikz actions inside math, the resulting image may exceed the TEX boundaries, so the HTML size styles may be incorrect, and must be neutralized.

```
10065 \ifbool{LWR@unknownmathsize}{%
10066   \def\LWR@singledollarstyle{}%
10067   \def\LWR@singledollardepthstyle{}%
10068 }{}
```

Create the `lateximage` using the alternate tag and the computed size and depth. The star causes `lateximage` to use an MD5 hash as the filename. When hashing, also include the current font and color in the hash.

```
10069 \ifbool{LWR@dynamicmath}{%
10070   \LWR@traceinfo{subsingledollar: dynamic}%
10071   \begin{lateximage}%
10072     [\MathImageAltText]%
10073     []% no add'l hashing
10074     [\LWR@singledollarstyle \LWR@singledollardepthstyle]%
10075   }%
10076   \LWR@traceinfo{subsingledollar: static}%
10077   \IfValueTF{\#1}{%
10078     \LWR@findcurrenttextcolor%
       sets \LWR@tempcolor
     }
```

Support for `xfakebold`:

```
10079 \ifbool{LWR@xfakebold}{%
10080   {\def\LWR@tempone{Y}%
10081   {\def\LWR@tempone{N}%
10082     \begin{lateximage}%
10083       [#2]%
10084       *% do not add open/closing braces
10085       [% addl' hashing
10086         #3%
10087         FM\LWR@f@family%
10088         SR\LWR@f@series%
10089         SH\LWR@f@shape%
10090         SHC\LWR@f@shapecaps%
10091         CL\LWR@tempcolor%
10092         FB\LWR@tempone% xfakebold
10093       ]%
10094       [\LWR@singledollarstyle \LWR@singledollardepthstyle]%
10095     }%
10096     \begin{lateximage}%
10097       [#2]%
10098       []% no add'l hashing
10099       [\LWR@singledollarstyle \LWR@singledollardepthstyle]%
10100     }%
10101   }%
10102 }
```

Place small and almost transparent markers on the baseline at the left and right edges of the image. These markers are seen by `pdfcrop`, and force vertically-centered objects such as a dash to be raised off the baseline in the cropped image, and also force the total width and left/right margins to be correct. (Except that in some fonts a

character may exceed the bounding box, and thus may appear wider than expected when converted to an image.)

```
10102 \LWR@addbaselinemarker%
```

Support for `xfakebold`:

```
10103 \LWR@applyxfakebold%
```

Typeset the contents:

```
10104 \usebox{\LWR@singledollarbox}%
```

The closing baseline marker:

```
10105 \LWR@addbaselinemarker%
```

```
10106 \end{lateximage}%
10107 %
10108 }
```

```
\LWR@subsingledollar * {\langle 2: alt text\rangle} {\langle 3: add'l hashing\rangle} {\langle 4: math expression\rangle}
```

For inline math. Uses MathJax, or for SVG math the image is measured and adjusted to the baseline of the HTML output, and placed inside a `lateximage`.

**SVG math:** `\LWR@origensuredmath` is part of argument #4.

**SVG math \ensuremath:** `\LWR@origensuredmath` is part of argument #4.

**SVG dynamic math:** `\LWR@origensuredmath` is part of argument #4.

**Mathjax:** Argument #4 is the contents of the math expression without `\LWR@origensuredmath`. This case is handled above.

**Mathjax \ensuremath:** `\LWR@origensuredmath` is part of argument #4.

**Mathjax dynamic math:** Argument #4 is the contents of the math expression without `\LWR@origensuredmath`, so `\LWR@origensuredmath` is added below.

**image filename hashing** If starred, a hashed filename is used. If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TeX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing

argument in order to make the hash unique according to the set of options, even if the simple alt tag is still the same.

```

10109 \newlength{\LWR@singledollarwidth}
10110 \newlength{\LWR@singledollarheight}
10111 \newlength{\LWR@singledollardepth}
10112
10113 \newsavebox{\LWR@singledollarbox}
10114
10115 \NewDocumentCommand{\LWR@subsingledollar}{s m m m}{%
10116     \LWR@traceinfo{\LWR@subsingledollar}%
10117     \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}{%
10118         {%
10119             \LWR@traceinfo{\LWR@subsingledollar: already in a lateximage}%
10120             #4% contents
10121         }%
10122         {%
10123             \begingroup%

```

### Support for `xfakebold`:

```
10124     \LWR@applyxfakebold%
```

MathJax cannot parse the often complicated T<sub>E</sub>X expressions which appear in the various uses of `\ensuredmath`. `\ensuremath` forces the alt tag to “(math image)”, as translated according to `\MathImageAltText`. If this is the case, force the use of a `lateximage` even if MathJax. Likewise for `siunitx` if `parse-numbers=false`.

If MathJax, or if formatting math for a word processor, and not `\ensuredmath`, and not a dynamic math expression, print the math expression:

```

10125     \ifboolexpr{%
10126         (
10127             bool{mathjax} or
10128             ( bool{FormatWP} and bool{WPMarkMath} )
10129         ) and
10130         ( not test {
10131             \ifstrequal{#2}{ from \ensuredmath
10132                 {\AltTextOpen\MathImageAltText\AltTextClose}
10133             }
10134         ) and
10135         ( not bool{LWR@dynamicmath} )
10136     }%

```

For MATHJAX, print the math between `\(` and `\)`:

```

10137     {%
10138         \LWR@traceinfo{\LWR@subsingledollar: Mathjax}%
10139         {\textbackslash(\textbackslashHTMLsanitize{#4}\textbackslash)}%
10140     }% mathjax

```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the L<sup>A</sup>T<sub>E</sub>X code, and a css style to control the baseline adjustment.

```
10141      {%
10142          not mathjax
10143          \LWR@traceinfo{%
10144              \LWR@subsingledollar: NOT mathjax, or is ensuremath, or is dynamic%
10145          }%
10146          \LWR@subsingledollarsvg{#1}{#2}{#3}{#4}%
10147      }%
10148      not in a lateximage
```

Clear the single-use alt text:

```
10149      \gdef\LWR@ThisAltText{}%
10150      \LWR@traceinfo{\LWR@subsingledollar: done}%
10151 }

10152 \LetLtxMacro{\LWR@origdollar$}
10153 \LetLtxMacro{\LWR@secondorigdollar$}{% balance for editor syntax highlighting

10154 \LetLtxMacro{\LWR@origopenparen}{%
10155 \LetLtxMacro{\LWR@origcloseparen}{%
10156 \LetLtxMacro{\LWR@origopenbracket}{%
10157 \LetLtxMacro{\LWR@origclosebracket}{}}
```

\$ Redefine the dollar sign to place math inside a `lateximage`, or use MATHJAX:  
\$\$

```
10158 \begingroup
10159 \catcode`\$=\active%
10160 \protected\gdef\${\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%

```

Used by `chemformula` to escape single-dollar math:

```
10161 \protected\gdef\LWR@newsingledollar{\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%

```

`\LWR@doubledollar` Redefine the double dollar sign to place math inside a `lateximage`, or use MATHJAX:

```
10162 \protected\gdef\LWR@doubledollar$#1$$%
```

If MATHJAX or formatting for a word processor, print the L<sup>A</sup>T<sub>E</sub>X expression:

```
10163 \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{}
```

For MATHJAX, print the math between `\[` and `\]`:

```
10164 {
10165
10166     \textbackslash[%
10167     \LWR@HTMLsanitize{#1}%
10168     \textbackslash]%
10169
10170 }% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the L<sup>A</sup>T<sub>E</sub>X code:

```

10171 {%
10172   not mathjax
10173   \begin{BlockClass}{displaymath}%
10174   \LWR@newautoidanchor%
10175   \booltrue{\LWR@indisplaymathimage}%
10176   \begin{lateximage}%
10177     \textbackslash{}% extra space
10178     \LWR@HTMLsanitize{\#1}% extra space
10179     \textbackslash{}%
10180   ]%
10181   *% do not add open/closing braces

```

Support for `xfakebold`:

```

10182   \LWR@applyxfakebold%
10183   \LWR@origdollar\LWR@origdollar#1\LWR@origdollar\LWR@origdollar%
10184   \end{lateximage}%
10185   \end{BlockClass}%
10186 }% not mathjax

```

Clear the single-use alt text:

```

10187 \gdef\LWR@ThisAltText{}%
10188 }%
10189 \LWR@singledollar {\langle alt text\rangle} {\langle math expression\rangle}
10190 \protected\gdef\LWR@singledollar#1$%
10191 \ifbool{mathjax}{%
10192   \LWR@subsingledollar*%
10193   {%
10194     \textbackslash{}%
10195     \LWR@HTMLsanitize{\#1}% extra space
10196     \textbackslash{}%
10197     {singledollar}% add'l hashing
10198     {\#1}% contents
10199   }%
10200   not mathjax
10201   \LWR@subsingledollar*%
10202   {%
10203     \textbackslash{}%
10204     \LWR@HTMLsanitize{\#1}% extra space
10205     \textbackslash{}%
10206     {singledollar}% add'l hashing
10207     {\LWR@origensuredmath{\#1}}% contents
10208 }%

```

Clear the single-use alt text:

```

10209 \gdef\LWR@ThisAltText{}%
10210 }

\(\ Redefine to the above dollar macros.
\[
10211 \AtBeginDocument{
10212 \protected\gdef\(#1\){$#1$}
10213 \protected\gdef\[#1]{###1##}
10214 }
10215
10216 \endgroup

10217 \AtBeginDocument{
10218 \LetLtxMacro{\LWR@openbracketnormal}{[
10219 \LetLtxMacro{\LWR@closebracketnormal}{]}
10220 }

```

\@ensuredmath {*<expression>*}

If MathJax, a `lateximage` is used, since `\ensuremath` is often used for complex TEX expressions which MathJax may not render. If SVG math, a hashed file is used with a simple alt tag, but additional hashing provided by the contents.

```

10221 \LetLtxMacro{\LWR@origensuredmath}{\@ensuredmath}
10222
10223 \renewcommand{\@ensuredmath}[1]{%
10224     \ifbool{mathjax}{%
10225         \LWR@subsingle-dollar*\{\AltTextOpen\MathImageAltText\AltTextClose\}{%
10226             \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
10227         }{\relax%
10228             \LWR@origensuredmath{#1}%
10229         }%
10230     }{%
10230     }% SVG math

```

If already inside a `lateximage` in math mode, continue as-is.

```

10231     \ifmmode%
10232         \LWR@origensuredmath{#1}%
10233     \else%

```

Create an inline math `lateximage` with a simple alt tag and additional hashing according to the contents.

```

10234         \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}{%
10235             {\LWR@origensuredmath{#1}}%
10236             {%
10237                 \LWR@subsingle-dollar*%
10238                     {\AltTextOpen\MathImageAltText\AltTextClose}%
10239                     {\protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}}%
10240                     {\LWR@origensuredmath{#1}}%
10241             }%
10242         \fi%
10243     }%

```

Clear the single-use alt text:

```
10244     \gdef\LWR@ThisAltText{}%
10245 }
```

Remember then remove the old `math` and `displaymath` environments:

```
10246 \let\LWR@orig@math\math
10247 \let\LWR@orig@endmath\endmath
10248 \let\LWR@orig@displaymath\displaymath
10249 \let\LWR@orig@enddisplaymath\enddisplaymath
10250
10251 \let\math\relax
10252 \let\endmath\relax
10253 \let\displaymath\relax
10254 \let\enddisplaymath\relax
```

**Env `math`** Set math mode then typeset the body of what was between the begin/end. See the `environ` package for `\BODY`.

```
10255 \NewEnviron{math}{\expandafter(\BODY)}
```

**Env `LWR@displaymathnormal`** Set math mode then typeset the body of what was between the begin/end. See the `environ` package for `\BODY`.

```
10256 \NewEnviron{LWR@displaymathnormal}{\expandafter[\BODY]\ignoretrue}
```

Set the default `displaymath` to the normal version:

```
10257 \LetLtxMacro[\LWR@openbracketnormal%
10258 \LetLtxMacro]\LWR@closebracketnormal%
10259 \LetLtxMacro\displaymath\LWR@displaymathnormal%
10260 \LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
```

**Env `LWR@displaymathother`** A version of `displaymath` which can handle complicated objects, but does not supply `MATHJAX` or `HTML` alt tags.

```
10261 \newenvironment{LWR@displaymathother}%
10262 {%
10263     \begin{BlockClass}{displaymath}%
10264     \LWR@newautoidanchor%
10265     \booltrue{\LWR@indisplaymathimage}%
10266     \begin{lateximage}%
10267     [\MathImageAltText]%
10268     \LWR@origdollar\LWR@origdollar%
10269 }%
10270 {%
10271     \LWR@origdollar\LWR@origdollar%
10272     \end{lateximage}%
10273     \end{BlockClass}%
10274 }
```

Env LWR@equationother A version of displaymath which can handle complicated objects, but does not supply MATHJAX or HTML alt tags.

```

10275 \newenvironment{LWR@equationother}
10276 {%
10277   \begin{BlockClass}{displaymathnumbered}%
10278   \LWR@newautoidanchor%
10279   \booltrue{LWR@indisplaymathimage}%
10280   \begin{latentimage}[\MathImageAltText]%
10281   \LWR@origequation%
10282 }%
10283 {%
10284   \LWR@origendequation%
10285   \end{latentimage}%
10286   \end{BlockClass}%
10287 }
```

## 79.4 MATHJAX support

Ctr LWR@nextequation Used to add one to compute the next equation number.

```
10288 \newcounter{LWR@nextequation}
```

\LWR@syncmathjax Sets the MATHJAX equation format and number for the following equations.

These MATHJAX commands are printed inside “\(`” and “\)`” characters. They are printed to HTML output, not interpreted by LATEX.

```
10289 \newcommand*{\LWR@syncmathjax}{%
```

If using chapters, place the chapter number in front of the equation. Otherwise, use the simple equation number.

```

10290   \ifcsdef{thechapter}%
10291     \InlineClass{hidden}{%
10292       \textbackslash(%
10293       \textbackslashtextbackslash{}seteqsection \{\thechapter\}%
10294       \textbackslashtextbackslash)%
10295     }%
10296   }%
10297 {}% not using chapters
```

MATHJAX doesn't allow setting the equation number to 1:

```

10298   \ifthenelse{\cnttest{\value{equation}}>0}%
10299   {
```

Tell MATHJAX that the next set of equations begins with the current LATEX equation number, plus one.

```

10300   \setcounter{LWR@nextequation}{\value{equation}}%
10301   \addtocounter{LWR@nextequation}{1}
```

Place the MATHJAX command inside “\(`” and “\)`” characters, to be printed to HTML, not interpreted by L<sup>A</sup>T<sub>E</sub>X.

```
10302      \InLineClass{hidden}{
10303          \textbackslash(
10304          \textbackslash{}seteqnumber \{\arabic{LWR@nextequation}\}
10305          \textbackslash)
10306      }
10307  }{}% not eq > 0
10308 }
```

\LWR@hidelatexequation {⟨environment⟩} {⟨contents⟩}

Creates the L<sup>A</sup>T<sub>E</sub>X version of the equation inside an HTML comment.

```
10309 \NewDocumentCommand{\LWR@hidelatexequation}{m +m}{%
```

Stop HTML paragraph handling and open an HTML comment:

```
10310  \LWR@stoppars
10311  \LWR@htmlopencomment
10312
```

Start the L<sup>A</sup>T<sub>E</sub>X math environment inside the HTML comment:

```
10313  \begingroup
10314  \nameuse{\LWR@orig#1}
```

While in the math environment, restore various commands to their L<sup>A</sup>T<sub>E</sub>X meanings.

```
10315  \LWR@restoreorigformatting
```

See \LWR@htmlmathlabel in section 79.7.1.

Print the contents of the equation:

```
10316  #2
```

End the L<sup>A</sup>T<sub>E</sub>X math environment inside the HTML comment:

```
10317  \nameuse{\LWR@origend#1}
10318  \endgroup
10319
```

Close the HTML comment and resume HTML paragraph handling:

```
10320  \LWR@htmlclosecomment
10321  \LWR@startpars
10322 }
```

\LWR@addmathjax {⟨environment⟩} {⟨contents⟩}

Given the name of a math environment and its contents, create a MATHJAX instance. The contents are printed to HTML output, not interpreted by L<sup>A</sup>T<sub>E</sub>X.

```
10323 \NewDocumentCommand{\LWR@addmathjax}{m +m}{%
```

Enclose the MATHJAX environment inside printed “\(`” and “\)`” characters.

```
10324     \LWR@origtilde\LWR@orignewline
10325     \textbackslash{}begin\{\#1\}
```

Print the contents, sanitizing for HTML special characters.

```
10326     \LWR@HTMLsanitizeexpand{\detokenize\expandafter{\#2}}
```

Close the MATHJAX environment:

```
10327     \textbackslash{}end\{\#1\}
10328     \LWR@orignewline
10329 }
```

## 79.5 Equation environment

Remember existing equation environment, after redefined by `amsmath`, if loaded.

```
10330 \AtBeginDocument{
10331 \let\LWR@origequation\equation
10332 \let\LWR@origendequation\endequation
10333 \csletcs{\LWR@origequation*}{equation*}
10334 \csletcs{\LWR@origendequation*}{endequation*}
10335 }
```

```
\LWR@doequation {\langle env contents \rangle} {\langle env name \rangle}
```

For SVG math output, the contents are typeset using the original equation inside a `lateximage`, along with an `<alt>` tag containing a detokenized copy of the L<sup>A</sup>T<sub>E</sub>X source for the math.

For MATHJAX output, the contents are typeset in an original equation environment placed inside a HTML comment, with special processing for `\labels`. The contents are also printed to the HTML output for processing by the MATHJAX script.

```
10336 \newcommand*{\LWR@doequation}[2]{%
10337 }
```

If `mathjax` or `FormatWP`, print the L<sup>A</sup>T<sub>E</sub>X expression:

```
10338     \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{%
```

MATHJAX output:

```
10339     {
```

Print commands to synchronize MATHJAX's equation number and format to the current L<sup>A</sup>T<sub>E</sub>X chapter/section and equation number:

```
10340 \LWR@syncmathjax
```

Print the L<sup>A</sup>T<sub>E</sub>X math inside an HTML comment:

```
10341 \LWR@hidelatexequation{#2}{#1}
10342 }
```

SVG output: Create the `lateximage` along with an HTML `<alt>` tag having an equation number, the L<sup>A</sup>T<sub>E</sub>X equation environment commands, and the contents of the environment's `\BODY`.

```
10343 {%
```

Begin the `lateximage` with an `<alt>` tag containing the math source:

```
10344 \ifstrequal{#2}{equation*}{%
10345   \begin{BlockClass}{displaymath}%
10346 }{%
10347   \begin{BlockClass}{displaymathnumbered}%
10348 }%
10349 \LWR@newautoanchor%
10350 \booltrue{\LWR@indisplaymathimage}%
10351 \begin{lateximage}[%]
10352   \ifstrequal{#2}{equation*}{%
10353     \ifdefequal{\LWR@equationtag}{\theequation}{%
10354       % no tag was given
10355     }{%
10356       (\LWR@equationtag) % tag was given
10357     }%
10358   }{%
10359     (\LWR@equationtag) % automatic numbering
10360   }%
10361   \textbackslash\begin{#2} % extra space
10362   \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#1}} % extra space
10363   \textbackslash\end{#2}%
10364 ]* alt tag}
```

Support for `xfakebold`:

```
10365 \LWR@applyxfakebold%
```

Create the actual L<sup>A</sup>T<sub>E</sub>X-formatted equation inside the `lateximage` using the contents of the environment.

```
10366 @nameuse{\LWR@orig#2}%
10367 #1% contents collected by \collect@body
10368 @nameuse{\LWR@origend#2}%
10369 \end{lateximage}%
10370 \end{BlockClass}%
10371 }% not mathjax
```

Clear the single-use alt text:

```
10372     \gdef\LWR@ThisAltText{}%
10373 }
```

After the environment, if MATHJAX, print the math to the HTML output for MATHJAX processing:

```
10374 \newcommand*{\LWR@doendequation}[1]{%
10375     \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{%
10376         {%
10377             \LWR@addmathjax{\#1}{\BODY}%
10378         }{%
10379     }}
```

Clear the single-use alt text:

```
10380     \gdef\LWR@ThisAltText{}%
10381 }
```

Remove existing equation environment:

```
10382 \AtBeginDocument{%
10383 \let\equation\relax
10384 \let\endequation\relax
10385 \csletcs{equation*}{\relax}
10386 \csletcs{\endequation*}{\relax}
10387 }
```

**Env equation** The new equation environment is created with `\NewEnviron` (from the `environ` package), which stores the contents of its environment in a macro called `\BODY`.

```
10388 \AtBeginDocument{%
10389
10390 \NewEnviron{equation}{%
10391     {\LWR@doequation{\BODY}{equation}}%
10392     [\LWR@doendequation{equation}]%
10393
10394 \LetLtxMacro{\LWR@equationnormal}{\equation}
10395 \LetLtxMacro{\endLWR@equationnormal}{\endequation}
10396
10397 }% AtBeginDocument
```

**Env equation\***

```
10398 \AtBeginDocument{%
10399
10400 \NewEnviron{equation*}{%
10401     {\LWR@doequation{\BODY}{equation*}}%
10402     [\LWR@doendequation{equation*}]%
10403
10404 \csletcs{\LWR@equationnormalstar}{equation*}
```

```

10405 \csletcs{LWR@endequationnormalstar}{endequation*}
10406
10407 }% AtBeginDocument

```

Remember the “less” version of equation, which uses MATHJAX and alt tags, but does not support complicated contents such as some Tikz expressions.

```

10408 \AtBeginDocument{
10409 \LetLtxMacro{\LWR@equationless}{\equation
10410 \LetLtxMacro{\endLWR@equationless}{\endequation
10411 \csletcs{LWR@equationlessstar}{equation*}
10412 \csletcs{LWR@endequationlessstar}{endequation*}
10413 }

```

## 79.6 \displaymathnormal and \displaymathother

**\displaymathnormal** By default, or when selecting \displaymathnormal, MATHJAX math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Tikz pictures, compilation will fail.

**\displaymathother  
MathJax unsupported  
complicated alt tag** When selecting \displaymathother, it is assumed that the contents are more complicated than “pure” math. An example is an elaborate Tikz picture, which will not render in MATHJAX and will not make sense as an HTML alt tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Tikz pictures are more likely to compile successfully.

**\displaymathnormal  
simple math objects** Use when display math environments have simple math which is to sent to MATHJAX or included in HTML alt tags.

```

10414 \newcommand*{\displaymathnormal}{%
10415   \ifbool{LWR@origmathjax}{\booltrue{mathjax}}{\boolfalse{mathjax}}%
10416   \LetLtxMacro{[}{\LWR@openbracketnormal}%
10417   \LetLtxMacro{]}{\LWR@closebracketnormal}%
10418   \LetLtxMacro{\displaymath}{\LWR@displaymathnormal}%
10419   \LetLtxMacro{\enddisplaymath}{\endLWR@displaymathnormal}%
10420   \LetLtxMacro{\equation}{\LWR@equationnormal}%
10421   \LetLtxMacro{\endequation}{\endLWR@equationnormal}%
10422   \csletcs{equation*}{\LWR@equationnormalstar}%
10423   \csletcs{endequation*}{\LWR@endequationnormalstar}%
10424 }

```

**\displaymathother  
complicated math objects** Use when display math environments have complicated objects which will not work with MathJax or should not be included in HTML alt tags. Complicated contents are more likely to compile correctly.

```
10425 \newcommand*{\displaymathother}{%
```

```

10426  \boolfalse{mathjax}%
10427  \LetLtxMacro\displaymath\LWR@displaymathother%
10428  \LetLtxMacro\enddisplaymath\endLWR@displaymathother%
10429  \LetLtxMacro\[ \LWR@displaymathother%
10430  \LetLtxMacro\]\endLWR@displaymathother%
10431  \LetLtxMacro\equation\LWR@equationother%
10432  \LetLtxMacro\endequation\endLWR@equationother%
10433  \csletcs{equation*}{displaymath}%
10434  \csletcs{endequation*}{enddisplaymath}%
10435 }

10436 \end{warpHTML}

```

**for PRINT output:** 10437 \begin{warpprint}

Print-mode versions:

```

10438 \newcommand*\displaymathnormal(){}
10439 \newcommand*\displaymathother(){}
10440 \end{warpprint}

```

**for HTML output:** 10441 \begin{warpHTML}

## 79.7 AMS Math environments

### 79.7.1 Support macros

Bool LWR@amsmultiline True if processing a multiline environment.

To compensate for multiline-specific code, LWR@amsmultiline is used to add extra horizontal space in \LWR@htmlmathlabel if it is used in an amsmath environment which is not a multiline environment and not an equation.

```

10442 \newbool{LWR@amsmultiline}
10443 \boolfalse{LWR@amsmultiline}

```

\LWR@htmlmathlabel {\langle label \rangle}

lwarp points \ltx@label here. This is used by \label when inside a LATEX AMS math environment's math display environment.

\LWR@origltx@label points to the LATEX original, modified by lwarp, then by amsmath, then by cleveref.

```

10444 \newcommand*\LWR@htmlmathlabel[1]{%
10445   \LWR@traceinfo{\LWR@htmlmathlabelb #1}%

```

If mathjax or FormatWP, print the LATEX expression:

```
10446     \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
10447     {%
```

The combined L<sup>A</sup>T<sub>E</sub>X & HTML label is printed in a \text field:

```
10448     \text{%
```

Shift the label over to the right side of the environment to avoid over-printing the math:

```
10449     \ifbool{LWR@amsmultiline}{}{\hspace*\{\totwidth@}\}%
```

Temporarily end the HTML comment, insert the L<sup>A</sup>T<sub>E</sub>X & HTML label, then resume the HTML comment. \@firstofone is required to remove extra braces introduced by the amsmath package.)

```
10450     \LWR@htmclosecomment%
10451     \LWR@origltx@label{#1}%
10452     \LWR@htmopencomment%
10453     }% text
10454     }% mathjax
10455     {%
10456     \LWR@origltx@label{#1}%
10457     }%
10458 }
```

\LWR@beginhideamsmath Starts hiding L<sup>A</sup>T<sub>E</sub>X math inside an HTML comment.

```
10459 \newcommand*{\LWR@beginhideamsmath}{%
10460     \LWR@stoppars
10461     \LWR@origtilde\LWR@orignewline
10462     \LWR@htmopencomment
10463
10464     \begingroup
10465     \LWR@restoreorigformatting
10466 }
```

\LWR@endhideamsmath Ends hiding L<sup>A</sup>T<sub>E</sub>X math inside an HTML comment.

```
10467 \newcommand*{\LWR@endhideamsmath}{%
10468     \endgroup
10469
10470     \LWR@htmclosecomment
10471     \LWR@orignewline
10472     \LWR@startpars
10473 }
```

### 79.7.2 Environment patches

The amsmath environments already collect their contents in \@envbody for further processing. eqnarray is not an *AMS* package, and thus requires special handling.

For SVG math: Each environment is encapsulated inside a `\lateximage` environment, along with a special optional argument of `\LWR@amsmathbody` or `\LWR@amsmathbodynumbered` telling `\lateximage` to use as the `HTML <alt>` tag the environment's contents which were automatically captured by the `\AMS` environment.

For MATHJAX: Each environment is synched with L<sup>A</sup>T<sub>E</sub>X's equation numbers, typeset with L<sup>A</sup>T<sub>E</sub>X inside an `HTML` comment, then printed to `HTML` output for MATHJAX to process.

`Env eqnarray` This environment is not an `\AMS` environment and thus its body is not automatically captured, so the `environ` package is used to capture the environment into `\BODY`.

```
10474 \let\LWR@origeqnarray\eqnarray
10475 \let\LWR@origendeqnarray\endeqnarray
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
10476 \newbool{\LWR@numbereqnarray}
10477 \booltrue{\LWR@numbereqnarray}
```

Common code used by `eqnarray` and `Beqnarray` (from `fancybox`):

```
10478 \newcommand{\LWR@eqnarrayfactor}{%
```

If `mathjax` or `FormatWP`, print the L<sup>A</sup>T<sub>E</sub>X expression:

```
10479 \ifboolexpr{\bool{mathjax} \or (\ bool{FormatWP} \and \bool{WPMarkMath} ) }%
10480 {%
```

If MATHJAX, the environment contents (the `\BODY`) are executed in a `HTML` comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for MATHJAX to interpret:

```
10481 \LWR@syncmathjax%
10482 \boolfalse{\LWR@amsmultiline}%
10483 \ifbool{\LWR@numbereqnarray}%
10484 {%
```

If numbering the equations, execute a copy inside an `HTML` comment block:

```
10485 \LWR@beginhideamsmath%
10486 \LWR@origeqnarray%
10487 \BODY%
10488 \LWR@origendeqnarray%
10489 \LWR@endhideamsmath%
```

Then print the (sanitized) contents to the output for MATHJAX to interpret:

```
10490 \LWR@addmathjax{eqnarray}{\BODY}%
10491 }%
10492 {%\ not \LWR@numbereqnarray
```

If not numbering equations, just create the contents for MATHJAX:

```

10493      \LWR@addmathjax{eqnarray*}{\BODY}%
10494      }% LWR@numbereqnarray
10495      }% mathjax
10496      {%
10497      \ifbool{LWR@numbereqnarray}{%
10498      {%

```

For numbered SVG equations, first create a `lateximage` with an `alt` attribute containing sanitized copy of the source code:

```

10499      \begin{BlockClass}{displaymathnumbered}%
10500      \LWR@newautoidanchor%
10501      \booltrue{LWR@indisplaymathimage}%
10502      \begin{lateximage}[(\LWR@startingequationtag--\LWR@equationtag)%
10503      \LWR@addmathjax{eqnarray}{\BODY}]*%

```

Support for `xfakebold`:

```
10504      \LWR@applyxfakebold%
```

Create the image contents using an actual `eqnarray`:

```

10505      \LWR@origeqnarray%
10506      \BODY%
10507      \LWR@origendeqnarray%
10508      \end{lateximage}%
10509      \end{BlockClass}%
10510      }%
10511      {%
10511      \not LWR@numbereqnarray

```

If not numbered, do the same, but an extra `\nonumber` seems to be required:

```

10512      \begin{BlockClass}{displaymath}%
10513      \LWR@newautoidanchor%
10514      \booltrue{LWR@indisplaymathimage}%
10515      \begin{lateximage}[(\LWR@addmathjax{eqnarray*}{\BODY}]*%

```

Support for `xfakebold`:

```

10516      \LWR@applyxfakebold%
10517      \def\@eqncr{\nonumber\@seqncr}%
10518      \csuse{LWR@origeqnarray}%
10519      \BODY%
10520      \nonumber\csuse{LWR@origendeqnarray}%
10521      \end{lateximage}%
10522      \end{BlockClass}%
10523      }% LWR@numbereqnarray
10524      }% not mathjax

```

Default to number equations in the future:

---

```
10525 \booltrue{LWR@numbereqnarray}%
```

Clear the single-use alt text:

```
10526 \gdef\LWR@ThisAltText{}%
10527 }
```

eqnarray itself is made with a blank line before and after to force it to be on its own line:

```
10528 \RenewEnviron{eqnarray}{%
10529 {%
10530 \LWR@eqnarrayfactor%
10532 }%
10533 }
```

The starred version is patched to turn off the numbering:

```
10534 \csgpreto{eqnarray*}{\boolfalse{LWR@numbereqnarray}}%
10535 \end{warpHTML}
```

## 80 Lateximages

### 80.1 Description

**Env lateximage** A `lateximage` is a piece of the document which is typeset in L<sup>A</sup>T<sub>E</sub>X then included in the HTML output as an image. This is used for math if SVG math is chosen, and also for the `picture`, `tikzpicture`, and other environments.

Before typesetting the `lateximage` a large number of formatting, graphics, and symbols-related macros are temporarily restored to their print-mode meaning by `\LWR@restoreorigformatting`. (See section 78.)

A `lateximage` is typeset on its own PDF page inside an HTML comment which starts on the preceding page and ends on following page, and instructions are written to `lateximage.txt` for `lwarpmk` to extract the `lateximage` from the page of the PDF file then generate an accompanying .svg file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML `<span>` is created to hold both the HTML comment, which will have the `pdftotext` conversion, and also the link to the final .svg image.

A L<sup>A</sup>T<sub>E</sub>X label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

**HTML alt tag** The HTML alt tag is set to the L<sup>A</sup>T<sub>E</sub>X source for SVG math, some chemistry expressions,

and perhaps some other expressions which make sense for text copy/paste. In some other cases, the `alt` tag is set according to the package name.

When creating an SVG math image, its `HTML alt` tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the `alt` tag is set to `\MathImageAltText`, along with `\AltTextOpen` and `\AltTextClose`, and the image is not reused.

This `alt` expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “math image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

For many packages, the output is placed inside a `\textrimage` with an `HTML alt` tag set to the package name followed by `\PackageDiagramAltText`. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “diagram”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

#### SVG image font size

For the `\textrimage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name—*without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{\normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontSize`, which defaults to:

```
\newcommand*\LateximageFontSize{.75}
```

## 80.2 Support counters and macros

**for HTML output:** 10536 `\begin{warpHTML}`

Ctr LWR@`\textrimage` Sequence the images.

```
10537 \newcounter{LWR@textrimagecounter}
10538 \setcounter{LWR@textrimagecounter}{0}
```

Ctr LWR@`\textrimage` Do not create `\textrimage` inside of `\textrimage`.

```
10539 \newcounter{LWR@textrimagedepth}
10540 \setcounter{LWR@textrimagedepth}{0}
```

A few utility macros to write special characters:

```
10541 \edef\LWR@hashmark{\string#} % for use in \write
```

---

10542 \edef\LWR@percent{\@percentchar} % for use in \write

Ctr LWR@LIpage Used to reference the PDF page number of a lateximage to be written into <project>-images.txt.

10543 \newcounter{LWR@LIpage}

10544 \end{warpHTML}

### 80.3 Font size

**for HTML & PRINT:** 10545 \begin{warpall}

\LateximageFontSizeName Declares how large to write text in \latexitimages. The .svg file text size should blend well with the surrounding HTML text size.

⚠ no backslash *Do not include the leading backslash in the name.*

10546 \newcommand\*\LateximageFontSizeName{normalsize}

\LateximageFontScale Declares how large to scale inline svg math images. The .svg file text size should blend well with the surrounding HTML text size. The default is 1, but it may be redefined as needed depending on the HTML font.

10547 \newcommand\*\LateximageFontScale{1}

10548 \end{warpall}

### 80.4 Equation numbers

**for HTML output:** 10549 \begin{warpHTML}

Ctr LWR@startingequation For use with lateximage and multi-line numbered equations. Remembers the next equation number so that it may be printed in the alt tag.

```

10550 \newcounter{LWR@startingequation}
10551
10552 \@ifundefined{chapter}
10553 {
10554 \renewcommand{\theLWR@startingequation}{%
10555 \arabic{LWR@startingequation}%
10556 }
10557 }
10558 {% chapter defined
10559 \renewcommand{\theLWR@startingequation}{%
10560 \ifnumcomp{\value{chapter}}{>}{0}{\arabic{chapter}. }{}%
10561 \arabic{LWR@startingequation}%
10562 }
10563 }
```

Bool `\LWR@isstartingequation` True for the first equation tag, false for later tags in the same environment.

```
10564 \newbool{\LWR@isstartingequation}
```

`\LWR@startingequationtag` Prints the starting equation number or tag.

```
10565 \let\theLWR@startingequationtag\theLWR@startingequation
```

`\LWR@equationtag` Prints the ending equation number or tag.

This is reset by `\teximage`, may be temporarily overwritten by `\tag` calling `\LWR@remembertag`.

```
10566 \newcommand*{\LWR@equationtag}{}%
```

Only if SVG math, patch `\tag` after packages have loaded, in case someone else modified `\tag`.

```
10567 \AtBeginDocument{%
10568   \ifbool{\mathjax}{\% not mathjax}{%
10569     \ifbool{\LWR@isstartingequation}{%
10570       \NewDocumentCommand{\LWR@remembertag}{m}{%
10571         \ifbool{\LWR@isstartingequation}{%
10572           \def\theLWR@startingequationtag{\#1}%
10573           \def\theLWR@equationtag{\#1}%
10574         }{%
10575           \def\theLWR@startingequationtag{\#1}%
10576           \def\theLWR@equationtag{\#1}%
10577         }%
10578       }{%
10579     }%
10580   }%
10581 }
```

`\LWR@remembertag {<tag>}`

For use inside the math environments while using SVG math. Sets `\theLWR@startingequation` and `\theequation` to the given tag.

```
10580 \NewDocumentCommand{\LWR@remembertag}{m}{%
10581   \ifbool{\LWR@isstartingequation}{%
10582     \global\boolfalse{\LWR@isstartingequation}%
10583     \xdef\theLWR@startingequationtag{\#1}%
10584     \xdef\theLWR@equationtag{\#1}%
10585   }%
10586 }%
10587 }%
10588 }%
10589 }%
10590 }
```

## 80.5 HTML alt tags

`\LWR@amsmathbody {<envname>}` For use inside the optional argument to a `\teximage` to add the contents of a AMS math environment to the `<alt>` tag.

```
10580 \newcommand*{\LWR@amsmathbody}[1]{%
10581   \textbackslash\begin{\#1}\% extra space%
10582   \LWR@HTMLsanitizeexpand{\detokenize\expandafter{\the\@envbody}}%
10583   \textbackslash\end{\#1}\%%
10584 }
```

---

\LWR@amsmathbodynumbered {*envname*} For use inside the optional argument to a `lateximage` to add the contents of a AMS math environment to the alt tag, prefixed by the equation numbers.

```

10586 \newcommand*{\LWR@amsmathbodynumbered}[1]{%
10587 {%
10588     \ifnumcomp{\value{\LWR@startingequation}}{=}{\value{equation}}{%
10589         {(\LWR@equationtag)}{%
10590             {(\LWR@startingequationtag--\LWR@equationtag)} % extra space
10591             \LWR@amsmathbody{#1} % extra space
10592 }}}
```

## 80.6 `lateximage` environment

\LWR@lateximage@oneimageb {*1: alt text*} {*2: filename*} {*3: CSS style*} Creates the image for the `lateximage`.

```

10593 \newcommand{\LWR@lateximage@oneimageb}[3]{%
10594     \LWR@subinlineimage{#1}{\textrm{lateximage}}{%
10595     {%
10596         \LWR@print@embox{%
10597             \LWR@ImagesDirectory\OSPathSymbol{%
10598                 #2}%
10599             }{%
10600             \{svg\}{#3}}%
10601 }}
```

\LWR@lateximage@oneimage {*1: alt text*} {*2: filename*} {*3: css style*} {*4: delimit?*}

Creates an image for the `lateximage`, whose alt text depends on the circumstances.

```

10602 \newcommand{\LWR@lateximage@oneimage}[4]{%
10603     \ifdefvoid{\LWR@ThisAltText}{%
10604         \IfBooleanTF{#4}{%
10605             \LWR@lateximage@oneimageb{#1}{#2}{#3}{%
10606             }{%
10607                 \LWR@lateximage@oneimageb{%
10608                     {\AltTextOpen#1\AltTextClose}{%
10609                         {#2}{#3}}%
10610                     }{%
10611             }{%
10612                 \LWR@lateximage@oneimageb{%
10613                     {\AltTextOpen\LWR@ThisAltText\AltTextClose}{%
10614                         {#2}{#3}}%
10615                 }{%
10616             }}}}}}
```

Env `lateximage` \* [*2: <alt> tag*] \* [*4: add'l hashing*] [*5: css style*]

Typesets the contents and then renders the result as an svg file. Star #1 causes the image to be hashed for reuse. Star #3 causes the alt tag to not include `\AltTextOpen` and `\AltTextClose`, for use with math expressions.

The optional `<alt>` tag is included in the HTML code for use with copy/paste.

**image filename hashing**

If starred, a hashed filename is used. If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated `TEX` expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

File `*_html.aux` A new label is placed into the file `*_html.aux`:

```
\newlabel{LWR@lateximage-<BaseJobname>-<number>}{{<x>}{<y>}}
```

This is used to find the image in the `PDF` file, according to its name.

File `*-images.txt` A list of images to generate is created in `<jobname>-images.txt`. Each line has three pipe-delimited fields, containing the `PDF` page number from `<jobname>_html.pdf`, where the image is located, a boolean indicating whether the image is hashed, and the filename of the image. The last line has “end” in each field, and is used to detect an incomplete compile.

```
10617 \catcode`\$=\active%
10618
10619 \NewDocumentEnvironment{lateximage}{s 0{\ImageAltText} s 0{} 0{}}
10620 {%
10621 \LWR@traceinfo{lateximage: starting on \jobname.pdf page \arabic{page}}%
10622 \LWR@traceinfo{lateximage: entering depth is \arabic{LWR@lateximagedepth}}%
```

Nested `lateximages` remain one large `lateximage`:

```
10623 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}{%
```

If nesting inside an already-existing `lateximage`, simply record one more level. *AMS* packages redefine `\addtocounter` to do nothing if inside a `\text`, so lower-level `TEX` macros are used for tracking nested `lateximages`.

```
10624 {%
10625 %      \addtocounter{LWR@lateximagedepth}{1}%
10626      \global\advance\c@LWR@lateximagedepth 1\relax% Due to AmS \text macro.
10627 }%
```

Otherwise, this is the outer-most `lateximage`:

```
10628 {% start of outer-most lateximage
```

Remember the next equation number to be allocated, in case it must be printed in a multi-equation environment:

```
10629      \LWR@traceinfo{lateximage: starting outer-most lateximage}%
10630      \setcounter{LWR@startingequation}{\value{equation}}%
10631      \addtocounter{LWR@startingequation}{1}%
10632      \booltrue{LWR@isstartingequation}%
10633      \let\LWR@startingequationtag\theLWR@startingequation%
```

The default equation tag, unless overwritten by \tag:

```
10634      \let\LWR@equationtag\theequation%
```

Starting a new lateximage:

```
10635      \addtocounter{LWR@lateximagenumber}{1}%
10636      \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{LWR@lateximagenumber}}%
```

While inside a lateximage, locally do not use mathjax:

```
10637      \boolfalse{mathjax}%
```

Be sure that are doing a paragraph:

```
10638      \LWR@ensuredoingapar%
```

Next file:

```
10639      \addtocounter{LWR@externalfilecnt}{1}%
10640      \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{LWR@externalfilecnt}}%
```

Figure out what the next page number will be. \setcounterpageref assigns LWR@LIpage to the page number for the reference LWR@lateximage-BaseJobname-XXX:

```
10641      \setcounterpageref{LWR@LIpage}{%
10642          LWR@lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}}%
10643      }%
10644      \LWR@traceinfo{lateximage: LWR@LIpage is \arabic{LWR@LIpage}}%
```

Create an HTML span which will hold the comment which contains the *pdftotext* translation of the image's page, and also will hold the link to the .svg file:

```
10645      \LWR@htmlltag{span\LWR@indentHTML%
10646          id="lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}"\LWR@indentHTML%
10647          class="lateximagesource"\LWR@orignewline%
10648      }%
```

Write instructions to the <ImagesDirectory>.txt file:

```
10649      \LWR@traceinfo{lateximage: about to write to \BaseJobname-images.txt}%
10650      \IfBooleanTF{#1}{}% starred
10651      {% hash
```

Compute and save the hashed file name for later use:

```

10652      \ifdefvoid{\LWR@ThisAltText}{%
10653          \IfBooleanTF{#3}{%
10654              \edef\LWR@hashedname{%
10655                  \LWR@mdfive{\detokenize\expandafter{#2}-!-#4}%
10656              }%
10657          }{%
10658              \edef\LWR@hashedname{%
10659                  \LWR@mdfive{\detokenize\expandafter{\AltTextOpen#2\AltTextClose}-!-#4}%
10660              }%
10661          }%
10662      }{%
10663          \edef\LWR@hashedname{%
10664              \LWR@mdfive{\detokenize\expandafter{\AltTextOpen\LWR@ThisAltText\AltTextClose}-!-#4}%
10665          }%
10666      }%
10667      \LWR@traceinfo{lateximage: hash is \LWR@hashedname}%

```

Write the page, hashing, and hashed name:

```

10668      \immediate\write\LWR@lateximagesfile{%
10669          |\arabic{\LWR@LIPage}|true|\LWR@hashedname|%
10670          }%
10671      }% hash
10672      {%- no hash

```

No hash, so write the page, no hashing, and the image number:

```

10673      \LWR@traceinfo{lateximage: hash false}%
10674      \immediate\write\LWR@lateximagesfile{%
10675          |\arabic{\LWR@LIPage}|false|\LWR@ImagesName\arabic{\LWR@externalfilecnt}|%
10676          }%
10677      }% no hash

```

Place an open comment tag. This will hide any traces of the lateximage PDF page which were picked up by *pdftotext*.

```

10678      \LWR@traceinfo{lateximage: about to create open comment}%
10679      \LWR@htmlopencomment%

```

One level deeper. At this outer-most lateximage, it is known that this is not being used inside an *AMS* \text, since the outer-most level will never be in math mode.

```
10680      \addtocounter{\LWR@lateximagedepth}{1}%
```

Start the new PDF page:

```

10681      \LWR@traceinfo{lateximage: about to create a new page}%
10682      \LWR@orignewpage%

```

If the current page is larger, typeset the image in a “standard” width page and font size:

```

10683 \LWR@traceinfo{lateximage: about to create minipage}%
10684 \ifdimless{\linewidth}{6in}{%
10685   \LWR@print@minipage{\linewidth}%
10686 }{%
10687   \LWR@print@minipage{6in}%
10688 }%
10689 \nameuse{\LWR@print@\LateximageFontSizeName}%

```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for \\hspace, etc. inside a lateximage.

```

10690 \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
10691 \LWR@restoreorigformatting%

```

Use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```

10692 \def\@mpfn{footnote}%
10693 \def\thempfn{\thefootnote}%
10694 \LetLtxMacro\@footnotetext{\LWR@footnotetext}%

```

Create the LWRlateximage<number> label:

```

10695 \LWR@traceinfo{lateximage: about to create label}%
10696 \LWR@orig@label{\LWRlateximage-\BaseJobname-\arabic{\LWR@lateximagenumber}}%
10697 \LWR@traceinfo{lateximage: finished creating the label}%

```

Adjust the rule color to match HTML:

```

10698 \ifdefvoid{\LWR@ruleHTMLcolor}{}{%
10699   \LWR@print@arrayrulecolor[HTML]{\LWR@ruleHTMLcolor}%
10700 }%

```

Enable print-mode math functions:

```

10701 \LetLtxMacro$\LWR@origdollar%
10702 \catcode`\$=3% math shift
10703 \LetLtxMacro\(\LWR@origopenparen%
10704 \LetLtxMacro\)\LWR@origcloseparen%

```

Only enable print-mode display math if are not already inside display math:

```

10705 \ifbool{\LWR@indisplaymathimage}{}{%
10706   \LetLtxMacro[\LWR@origopenbracket]%
10707   \LetLtxMacro\]\LWR@origclosebracket%
10708   \let\equation\LWR@origequation%
10709   \let\endequation\LWR@origendequation%
10710   \csletcs{equation*}{\LWR@origequation*}%
10711   \csletcs{endequation*}{\LWR@origendequation*}%
10712 }%

```

For chemformula:

```

10713 \LetLtxMacro\LWR@newsingledollar$%
10714 \LetLtxMacro\LWR@newsingledollar$% syntax highlighting

```

```

10715 }% end of outer-most lateximage
10716 \LWR@traceinfo{lateximage: finished start of environment}%
10717 }% end of \begin{lateximage}

```

\end{lateximage} When the environment closes:

```

10718 {% start of \end{lateximage}
10719 \LWR@traceinfo{lateximage: starting end of lateximage}%

```

Nested more than one deep?

```

10720 \LWR@traceinfo{lateximage: internal depth was \arabic{LWR@lateximagedepth}}%
10721 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%

```

If nesting inside an already existing lateximage, simply record one less level. Uses a lower-level TEX macro due to *AMS* \text change of \addtocounter.

```

10722 {%
10723     \LWR@traceinfo{lateximage: unnesting}%
10724     \global\advance\c@LWR@lateximagedepth -1\relax%
10725 }%

```

If this is the outer-most lateximage:

```
10726 {% end of outer-most lateximage
```

Finish the lateximage minipage and start a new PDF page:

```

10727 \LWR@traceinfo{lateximage: ending outer-most lateximage}%
10728     \endLWR@print@minipage%
10729     \LWR@orignewpage%

```

Close the HTML comment which encapsulated any traces of the lateximage picked up by *pdftotext*:

```

10730     \LWR@print@vspace*{.5\baselineskip}%
10731     \LWR@htmlclosecomment%
10732     \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%

```

Create a link to the lateximage, allowing its natural height:

```

10733     \IfBooleanTF{#1}{ starred
10734     {%
10735         \LWR@lateximage@oneimage{#2}{\LWR@hashedname}{#5}{#3}%
10736     }%
10737     {%
10738         \LWR@lateximage@oneimage{#2}{\LWR@ImagesName\theLWR@externalfilecnt}{#5}{#3}%
10739     }%

```

Be sure that are doing a paragraph:

```
10740     \LWR@ensuredoingapar%
```

Close the HTML span which has the `pdftotext` comment and also the link to the .svg image:

```
10741     \LWR@htmltag{/span}%
10742     \ifbool{HTMLDebugComments}{%
10743         \LWR@htmlcomment{End of lateximage}%
10744     }{}%
```

Undo one lateximage level. This is not inside an  $\text{\textit{AMS}}\text{\texttt{\textbackslash}text}$ , so regular `\addtocounter` may be used here.

```
10745     \addtocounter{LWR@lateximagedepth}{-1}%
```

Clear the single-use alt text:

```
10746     \gdef\LWR@ThisAltText{}%
10747 }% end of outer-most lateximage
10748 \LWR@traceinfo{lateximage: exiting depth is \arabic{LWR@lateximagedepth}}%
10749 \LWR@traceinfo{lateximage: done}%
10750 }%
10751 \catcode`\$=3% math shift
10752 \end{warpHTML}
```

**for PRINT output:** 10753 `\begin{warpprint}`

Env `lateximage` \* [`<alt> tag`] \* [`add'l hashing`] [`css style`]

`varwidth` is used to create a box of the natural width of its contents.

```
10754 \NewDocumentEnvironment{lateximage}{s o s o o}
10755     {\begin{varwidth}[b]{\linewidth}}
10756     {\end{varwidth}}
10757 \end{warpprint}
```

## 81 center, flushleft, flushright

**for HTML output:** 10758 `\begin{warpHTML}`

Env `center` Replace center functionality with css tags:

```
10759 \renewenvironment*{center}
10760 {
10761     \LWR@forcenewpage
10762     \ifbool{FormatWP}{%
10763         {\BlockClass[\LWR@print@mbox{text-align:center}]{center}}%
10764         {\BlockClass{center}}%
10765     }%
10766 {\endBlockClass}}
```

Env flushright

```
10767 \renewenvironment*{flushright}{%
10768   \LWR@forcenewpage%
10769   \ifbool{FormatWP}{%
10770     {\BlockClass[\LWR@print@mbox{text-align:right}]{flushright}}%
10771     {\BlockClass{flushright}}%
10772   }%
10773 }%
10774 {\endBlockClass}
```

Env flushleft

```
10775 \renewenvironment*{flushleft}{%
10776   \LWR@forcenewpage%
10777   \ifbool{FormatWP}{%
10778     {\BlockClass[\LWR@print@mbox{text-align:left}]{flushleft}}%
10779     {\BlockClass{flushleft}}%
10780   }%
10781 }%
10782 {\endBlockClass}
```

\centering, \raggedleft, and \raggedright usually have no effect on the HTML output, but they may be used to compare with the next token to identify their use at the start of a float. See \LWR@floatalignment.

\centering

```
10783 \newcommand*{\LWR@HTML@centering}{%
10784   \ifbool{HTMLDebugComments}{%
10785     \LWR@htmlcomment{centering}%
10786   }{}%
10787 }%
10788 \LWR@formatted{centering}
```

\raggedleft

```
10789 \newcommand*{\LWR@HTML@raggedleft}{%
10790   \ifbool{HTMLDebugComments}{%
10791     \LWR@htmlcomment{raggedleft}%
10792   }{}%
10793 }%
10794 \LWR@formatted{raggedleft}
```

\raggedright

```
10795 \newcommand*{\LWR@HTML@raggedright}{%
10796   \ifbool{HTMLDebugComments}{%
10797     \LWR@htmlcomment{raggedright}%
10798   }{}%
10799 }%
10800 \LWR@formatted{raggedright}
```

```
\leftline {\text{}}
```

10801 \renewcommand{\leftline}[1]{\begin{flushleft}\#1\end{flushleft}}

```
\centerline {\text{}}
```

10802 \renewcommand{\centerline}[1]{\begin{center}\#1\end{center}}

```
\rightline {\text{}}
```

10803 \renewcommand{\rightline}[1]{\begin{flushright}\#1\end{flushright}}

10804 \end{warpHTML}

## 82 Preloaded packages

**for HTML output:** 10805 \begin{warpHTML}

If the given package was loaded before or by l warp, load the l warp version as well.

```
\LWR@PreloadedPackage {\packagename}
```

10806 \newcommand\*{\LWR@PreloadedPackage}[1]{%

10807 \@ifpackageloaded{\#1}{%

10808 {%

10809 \AtBeginDocument{

10810 \LWR@origRequirePackage{l warp-\#1}{%

10811 }

10812 }%

10813 {}%

10814 }

If inputrc was loaded before l warp, as is usually done, explicitly load the l warp patches now:

10815 \LWR@PreloadedPackage{inputrc}

If textcomp was loaded before l warp, perhaps as part of the font-related packages, explicitly load the l warp patches now:

10816 \LWR@PreloadedPackage{textcomp}

If xunicode was loaded before l warp, perhaps as part of the font-related packages, explicitly load the l warp patches now:

10817 \LWR@PreloadedPackage{xunicode}

If `graphics` or `graphicx` were loaded before `l warp`, perhaps by `xunicode`, explicitly load the `l warp` patches now:

```
10818 \LWR@PreloadedPackage{graphics}
10819 \LWR@PreloadedPackage{graphicx}
```

`fontaxes` must be preloaded so that `l warp` may patch it for `HTML`.

```
10820 \LWR@PreloadedPackage{fontaxes}
```

`nfssext-cfr` may be preloaded by `cfm-lm` or related font packages.

```
10821 \LWR@PreloadedPackage{nfssext-cfr}
```

`ulem` may be preloaded by `ctex`, `ctexart`, and related classes.

```
10822 \LWR@PreloadedPackage{ulem}
```

`xetexko-vertical` may be preloaded by `xetexko`.

```
10823 \LWR@PreloadedPackage{xetexko-vertical}
```

`geometry` is preloaded by `l warp`, and perhaps by various classes.

```
10824 \LWR@PreloadedPackage{geometry}
```

`plex` is preloaded by some CJK classes.

```
10825 \LWR@PreloadedPackage{plex}
```

`stfloats` is preloaded by `ltj*` classes.

```
10826 \LWR@PreloadedPackage{stfloats}
```

`lltjext` is preloaded by `ltj*` classes.

```
10827 \LWR@PreloadedPackage{lltjext}
```

```
10828 \end{warpHTML}
```

## 83 siunitx

Pkg `siunitx` The `l warp` core passes a few options to `siunitx`.

**fractions** Due to `pdftotext` limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

 **math mode required** Some units will require that the expression be placed inside math mode.

 **tabular** Tabular S columns are rendered as simple c columns, and tabular s columns are not

supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

**⚠ MathJax** For math mode with SVG display, the original `siunitx` code is used while generating the SVG image. For text mode, `lwarp` uses an emulation which provides a very effective HTML interpretation of `siunitx`. For math expressions while using MATHJAX, a limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. `siunitx` macros with more than one optional value cannot absorb the second optional value, and complicated parsing such as for `\ang` is not supported. The result usually looks fine, and otherwise is enough to get the meaning across.

`lwarp`'s MATHJAX emulation for `siunitx` is meant to be a stop-gap measure until an extension is included in MATHJAX. As of this writing, the third-party `siunitx` extension for MATHJAX is not currently hosted at any public CDN, thus `siunitx` is not usable with this extension unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJax script, but `lwarp`'s emulation would have to be disabled as well.

Document modifications required for MATHJAX:

#### custom units

- Custom units may be added with `\CustomizeMathJax`. See the `lwarp-siunitx` code for examples.

#### ⚠ unit spacing

- Units work better using `~` between units instead of using periods.

#### ⚠ \square, \cubic

- To square or cube compound units, enclose the following compound units in braces:

```
\cubic{\centi\meter}
```

Single units do not require braces.

Also see [MATHJAX option](#), section 8.7.4.

**for HTML output:** 10829 `\begin{warpHTML}`

Options for `siunitx`:

```
10830 \newrobustcmd{\LWR@siunitx@textcelsius}{\HTMLentity{deg}C}
10831 \newrobustcmd{\LWR@siunitx@textdegree}{\HTMLentity{deg}}
10832 \newrobustcmd{\LWR@siunitx@textprime}{\HTMLunicode{2032}}
10833 \newrobustcmd{\LWR@siunitx@textdblprime}{\HTMLunicode{2033}}
10834 \newrobustcmd{\LWR@siunitx@textplanckbar}{\text{\textit{\HTMLunicode{0127}}}}}
10835
10836 \appto{\LWR@restoreorigformatting}{%
10837 \renewrobustcmd{\LWR@siunitx@textcelsius}{\text{\ensuremath{^\circ}C}}%
10838 \renewrobustcmd{\LWR@siunitx@textdegree}{\text{\ensuremath{^\circ}}}%
10839 \renewrobustcmd{\LWR@siunitx@textprime}{\text{\ensuremath{^{\prime}}}}%
10840 \renewrobustcmd{\LWR@siunitx@textdblprime}{\text{\ensuremath{^{\prime\prime}}}}%
10841 \renewrobustcmd{\LWR@siunitx@textplanckbar}{\text{\ensuremath{\hbar}}}}%
10842 }
10843
10844 \PassOptionsToPackage{
10845   detect-mode=true,
10846   per-mode=symbol, % fraction is not seen by pdftotext
```

```

10847   text-celsius = {\LWR@siunitx{textcelsius}},
10848   text-degree = {\LWR@siunitx{textdegree}},
10849   text-arcminute = {\LWR@siunitx{textprime}} ,
10850   text-arcsecond = {\LWR@siunitx{textdblprime}} ,
10851 }{siunitx}

10852 \end{warpHTML}

```

## 84 Graphics print-mode modifications

### 84.1 General limitations

**⚠ scale** Avoid using the `\includegraphics[scale=<xx>]{...}`

to:

```
\includegraphics[width=<yy>\linewidth]{...}
```

**\includegraphics file formats** For `\includegraphics` with .pdf or .eps files, the user must provide a .pdf or .eps image file for use in print mode, and also a .svg, .png, or .jpg version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, `lwarp` will automatically choose the .pdf or .eps format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf or .eps image is referred to with its file extension, the extension will be changed to .svg for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

**Prog pdftocairo** To convert a PDF image to SVG, use the utility `pdftocairo`:

**PDF to SVG** Enter ⇒ `pdftocairo -svg filename.pdf`

**Prog lwarpmk pdftosvg** For a large number of images, use `lwarpmk`:

Enter ⇒ `lwarpmk pdftosvg *.pdf` (**or a list of filenames**)

**Prog lwarpmk epstopdf** For EPS images converted to PDF using the package `epstopdf`, use

**epstopdf package** Enter ⇒ `lwarpmk pdftosvg *.PDF`

to convert to SVG images.

**DVI latex** When using DVI `latex`, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ `lwarpmk epstopdf *.eps` (**or a list of filenames**)

---

Enter ⇒ **l warpmk pdftosvg \*.pdf (or a list of filenames)**

**PNG and JPG** For PNG or JPG while using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

**GIF** GIF files may be used for HTML, but another format must also be provided for print output.

**file extension priorities** If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

**⚠ graphics vs. graphicx** If using the older *graphics* syntax, use both optional arguments for *\includegraphics*. A single optional parameter is interpreted as the newer *graphicx* syntax. Note that viewports are not supported by *l warp*—the entire image will be shown.



### viewport



### viewport units

For *\includegraphics*, avoid px and % units for width and height, or enclose them inside *warpHTML* environments. For font-proportional image sizes, use ex or em. For fixed-sized images, use cm, mm, in, pt, or pc. Use the keys *width=.5\linewidth*, or similar for *\textwidth* or *\textheight* to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the *scale* option, since it is not well supported by HTML browsers.

**options** *\includegraphics* accepts *width* and *height*, *origin*, *rotate* and *scale*, plus new *class* and *alt* keys.

**HTML class** With HTML output, *\includegraphics* accepts an optional *class=xyz* keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

**HTML alt tags** Likewise, the *\includegraphics alt* key adds an HTML alt tag to an image, and is ignored for print output. If not assigned, each image is given an alt tag according to *\ImageAltText*.

**\rotatebox** *\rotatebox* accepts the optional *origin* key.

**⚠ browser support** *\rotatebox*, *\scalebox*, and *\reflectbox* depend on modern browser support. The css3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LATEX, so expect some ugly results for scaling and rotating.

## 84.2 Print-mode modifications

**for PRINT output:** For print output, accept and then discard the new *class* key:

```
10853 \begin{warpprint}
10854 \define@key{Gin}{class}{}
10855 \define@key{Gin}{alt}{}
```

Print-mode additions for the *overpic* package. See section 382 for the HTML version.

```
10856 \AtBeginDocument{
10857 @ifpackageloaded{overpic}{}
```

---

```
10858 \newcommand*{\overpicfontsize}{12}
10859 \newcommand*{\overpicfontskip}{14}
10860 }{ }
10861 }
10862 \end{warpprint}
```

## 85 xcolor boxes

**Pkg** xcolor A few new definitions are provided for enhanced HTML colored boxes, and \fcolorbox is slightly modified. Print-mode version are also provided.

Print-mode versions of new xcolor defintions. These are defined inside warpall because they are also used for HTML while inside a `\teximage`. They are defined `\AtBeginDocument` so that the xcolor originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of none, in which case only the frame is drawn, allowing the background page color to show.

**for HTML & PRINT:** 10863 `\begin{warpall}`

After `xparse` may have been loaded ...

```
10864 \AtBeginDocument{
```

... and *only* if xcolor was loaded:

```
10865 \@ifpackageloaded{xcolor}{
10866 \LWR@traceinfo{patching xcolor}
```

The print version:

`\colorboxBlock` `\colorboxBlock` is the same as `\colorbox`:

```
10867 \LetLtxMacro\colorboxBlock\colorbox
```

The original definition is reused by the new versions:

```
10868 \LetLtxMacro\LWR@orig@print\fcolorbox\fcolorbox
```

`\fcolorbox` [`\<framemode>`] [`\<framecolor>`] [`\<boxmodel>`] [`\<boxcolor>`] [`\<text>`]

In print mode, `\fcolorbox` is modified to accept a background color of none.

(`\fcolorbox` is particular about its optional arguments, thus the elaborate combinations of `\ifthenelse`.)

```
10869 \newsavebox{\LWR@colorminipagebox}
10870
10871 \NewDocumentCommand{\LWR@print\fcolorbox}{o m o m +m}{%
10872 \LWR@traceinfo{\LWR@print\fcolorbox #2 #4}}%
```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
10873 \begin{lrbox}{\LWR@colorminipagebox}%
10874 #5%
10875 \end{lrbox}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
10876 \ifstreq{\#4}{none}%
10877 {%
10878   \LWR@traceinfo{background is none}%
10879   {%
10880     \colorlet{\LWR@currentcolor}{.}%
10881     \color{\#2}%
10882     \fbox{%
10883       \color{\LWR@currentcolor}%
10884       \usebox{\LWR@colorminipagebox}%
10885     }%
10886   }%
10887 }%
10888 {%
10889 \LWR@traceinfo{background not none}%
10890 \IfValueTF{\#1}%
10891 {%
10892   \IfValueTF{\#3}%
10893   {\LWR@orig@print@fcolorbox[\#1][\#2][\#3][\#4]{\usebox{\LWR@colorminipagebox}}}%
10894   {\LWR@orig@print@fcolorbox[\#1][\#2][\#4]{\usebox{\LWR@colorminipagebox}}}%
10895 }%
10896 {%
10897   \IfValueTF{\#1}%
10898   {\LWR@orig@print@fcolorbox[\#2][\#3][\#4]{\usebox{\LWR@colorminipagebox}}}%
10899   {\LWR@orig@print@fcolorbox[\#2][\#4]{\usebox{\LWR@colorminipagebox}}}%
10900 }%
10901 {%
10902 \LWR@traceinfo{\LWR@print@fcolorbox done}%
10903 }%
10904 \renewrobustcmd*\fcolorbox{\LWR@print@fcolorbox}%
```

\fcolorboxBlock [⟨framemodel⟩] {⟨framecolor⟩} [⟨boxmodel⟩] {⟨boxcolor⟩} {⟨text⟩}

In print mode, \fcolorboxBlock is the same as \fcolorbox.

```
10905 \newcommand*\fcolorboxBlock{\LWR@print@fcolorboxBlock}
```

```
10906 \newrobustcmd*\fcolorboxBlock{\LWR@print@fcolorboxBlock}
```

```
Env  fcolorminipage  [⟨1:framemodel⟩] {⟨2:framecolor⟩} [⟨3:boxmodel⟩] {⟨4:boxcolor⟩} [⟨5:align⟩] [⟨6:height⟩]
      [⟨7:inner-align⟩] {⟨8:width⟩}
```

In print mode, becomes a `\fcolorbox` containing a `minipage`:

```
10907 \NewDocumentEnvironment{LWR@print@fcolorminipage}{o m o m O{c} O{} o m}
10908 {%
10909 \LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%
```

Pre-load the contents into an LR box so that they can be used inside a `\fcolorbox`:

```
10910 \begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```
10911 \IfValueTF{#7}%
10912 {\begin{minipage}[#5][#6][#7]{#8}}%
10913 {\begin{minipage}[#5][#6][#5]{#8}}%
10914 }%
10915 {%
10916 \end{minipage}%
10917 \end{lrbox}%
10918 \LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a `\fcolorbox`.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
10919 \ifstreq{#4}{none}%
10920 {%
10921   {%
10922     \colorlet{LWR@currentcolor}{.}%
10923     \color{#2}%
10924     \fbox{%
10925       \color{LWR@currentcolor}%
10926       \usebox{\LWR@colorminipagebox}%
10927     }%
10928   }%
10929 }%
10930 {%
10931   \IfValueTF{#1}%
10932   {%
10933     \IfValueTF{#3}%
10934     {\LWR@orig@print@fcolorbox[#1][#2][#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
10935     {\LWR@orig@print@fcolorbox[#1][#2]{#4}{\usebox{\LWR@colorminipagebox}}}%
10936   }%
10937   {%
10938     \IfValueTF{#3}%
10939     {\LWR@orig@print@fcolorbox[#2][#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
10940     {\LWR@orig@print@fcolorbox[#2]{#4}{\usebox{\LWR@colorminipagebox}}}%
10941   }%
10942 }%
10943 \LWR@traceinfo{*** finished end fcolorminipage}%
10944 }
```

```

10945 \NewDocumentEnvironment{fcolorminipage}{}  

10946     {\LWR@print@fcolorminipage}  

10947     {\endLWR@print@fcolorminipage}  

10948 \LWR@traceinfo{xcolor patches done}  

10949 }{}% xcolor loaded  

10950 }% AtBeginDocument  

10951 \end{warpall}

```

## 86 chemmacros environments

`\makepolymerdelims` and redox reactions must be enclosed in a `lateximage` during HTML output. These environments are provided here in print mode, and in the `chemmacros` code in HTML mode, as a high-level semantic syntax which automatically embeds the contents in a `lateximage` with an appropriate alt tag.

**for PRINT output:** 10952 `\begin{warpprint}`

```

10953 \AtBeginDocument{  

10954 @ifpackageloaded{chemmacros}{  


```

Env `polymerdelims`

```

10955 \DeclareDocumentEnvironment{polymerdelims}{}  

10956     {}{}

```

Env `redoxreaction` {*space above*} {*space below*}

For print output, extra space is include above and below the image, and a `lateximage` is not necessary. This extra space must be enforced, even inside a float, so zero-width rules are used.

For the HTML version, see section [177.4](#).

```

10957 \DeclareDocumentEnvironment{redoxreaction}{m m}  

10958     {\rule{0pt}{#1}}{\rule[-#2]{0pt}{#2}}

```

```

10959 }{}% chemmacros  

10960 }% AtBeginDocument

```

```
10961 \end{warpprint}
```

## 87 cleveref

Pkg `cleveref` `cleveref` package is used as-is with minor patches.

**⚠ cleveref page numbers** `cleveref` and `varioref` are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

Ex:

```
\cpageref{tab:first,tab:second}
in html becomes:
“pages for table 4.1 and for table 4.2”
```

See \cpagerefFor at page 556 to redefine the message which is printed for page number references.

**loading order** cleveref and the following associated macro patches are automatically preloaded at the end of the preamble via \AtEndPreamble and \AfterEndPreamble. This is done because the HTML conversion requires cleveref. The user's document may not require cleveref, thus the user may never explicitly load it, so during HTML output lwarp loads it last. If the user's document preamble uses cleveref options, or functions such as \crefname, then cleveref may be loaded in the user's preamble near the end, and lwarp's additional loading of cleveref will have no effect.

Table 12 on page 477 shows the data structure of the label/reference system as revised by lwarp and cleveref.

A few patches allow cleveref to work as-is:

**for HTML output:** 10962 \begin{warpHTML}

\AtEndPreamble forces cleveref to be loaded last:

```
10963 \AtEndPreamble{
10964     \RequirePackage{cleveref}
10965 }
```

The following patches are applied after cleveref has loaded, and after \AtBeginDocument. Print-mode versions are not required since they all come down to \ref eventually, and \ref has a print-mode version.

```
10966 \AfterEndPreamble{
10967 \LWR@traceinfo{Patching cleveref.}
```

\@@@setcref {<kindofref>} {<label>}

\@templatelabel becomes the section number.

```
10968 \def\LWR@orig@@@setcref#1#2{\cref@getlabel{#2}{\@templatelabel}#1{\@templatelabel}{}{}%  
10969  
10970 \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% before v0.21
10971     \renewcommand*{\@@@setcref}[2]{#1{\ref{#2}}{}{}}
10972 }{
10973     \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% as of v0.21
10974         \renewcommand*{\@@@setcref}[2]{#1{\ref{#2}}{}{}}
10975 }{
10976     \PackageWarning{lwarp-cleveref}%
10977         Unknown version of cleveref.
10978         \protect\cref\space will fail.
10979 }%
```

```

10980      }
10981 }

\@@@setcrefrange {⟨text⟩} {⟨label⟩} {⟨label⟩}

10982 \def\LWR@orig@@@setcrefrange#1#2#3{%
10983   \cref@getlabel{#2}{\@labela}%
10984   \cref@getlabel{#3}{\@labelb}%
10985   #1{\@labela}{\@labelb}{\{}{\}}{}}%
10986
10987 \ifdefequal{\@@@setcrefrange}{\LWR@orig@@@setcrefrange}{%
10988   \renewcommand{\@@@setcrefrange}[3]{%
10989     #1{\ref{#2}}{\ref{#3}}{\{}{\}}{}}%
10990 }
10991 }{%
10992   \ifdefequal{\@@@setcrefrange}{\LWR@orig@@@setcrefrange}{%
10993     \renewcommand{\@@@setcrefrange}[3]{%
10994       #1{\ref{#2}}{\ref{#3}}{\{}{\}}{}}%
10995   }%
10996 }{%
10997   \PackageWarning{lwarf-cleveref}{%
10998     Unknown version of cleveref.%
10999     \protect\crefrange\space will fail.%
11000   }%
11001 }
11002 }
11003

```

\cpagerefFor Redefinable word between “page(s)” and the page numbers.

```
11004 \newcommand*{\cpagerefFor}{for}
```

\@@@setcpageref {⟨typeofref⟩} {⟨label⟩}, where typeofref is “page” or “pages”

```

11005 \def\LWR@orig@@@setcpageref#1#2{%
11006   \cref@getpageref{#2}{\@temppage}#1{\@temppage}{\{}{\}}{}}%
11007
11008 \def\LWR@orig@@@setcpageref#1#2{%
11009   \cpageref@getlabel{#2}{\@temppage}#1{\@temppage}{\{}{\}}{}}%
11010
11011 \ifdefequal{\@@@setcpageref}{\LWR@orig@@@setcpageref}{%
11012   \renewcommand*{\@@@setcpageref}[2]{%
11013     #1{\cpagerefFor\ \cref{#2}}{\{}{\}}{}}%
11014 }
11015 }{%
11016   \ifdefequal{\@@@setcpageref}{\LWR@orig@@@setcpageref}{%
11017     \renewcommand*{\@@@setcpageref}[2]{%
11018       #1{\cpagerefFor\ \cref{#2}}{\{}{\}}{}}%
11019   }%
11020 }
11021 }{%
11022   \PackageWarning{lwarf-cleveref}{%

```

```

11023           Unknown version of cleveref.
11024           \protect\cpageref\space will fail.
11025       }
11026   }
11027 }

11028 \def\LWR@orig@@setcpagerefrange#1#2#3{%
11029   \cref@getpageref{\#2}{\@pagea}%
11030   \cref@getpageref{\#3}{\@pageb}%
11031   #1{\@pagea}{\@pageb}{\{}{\}}{\}%
11032
11033 \def\LWR@orig@@setcpagerefrange#1#2#3{%
11034   \cpageref@getlabel{\#2}{\@pagea}%
11035   \cpageref@getlabel{\#3}{\@pageb}%
11036   #1{\@pagea}{\@pageb}{\{}{\}}{\}%
11037
11038 \ifdefequal{\@@setcpagerefrange}{\LWR@orig@@setcpagerefrange}{%
11039   \renewcommand*{\@@setcpagerefrange}[3]{%
11040     #1{\cpagerefFor\ \cref{\#2}}{\cref{\#3}}{\{}{\}}{\}%
11041   }
11042 }%
11043 \ifdefequal{\@@@setcpagerefrange}{\LWR@orig@@@setcpagerefrange}{%
11044   \renewcommand*{\@@@setcpagerefrange}[3]{%
11045     #1{\cpagerefFor\ \cref{\#2}}{\cref{\#3}}{\{}{\}}{\}%
11046   }
11047 }%
11048 {
11049   \PackageWarning{lwarp-cleveref}{%
11050     Unknown version of cleveref.
11051     \protect\cpagerefrange\space will fail.
11052   }
11053 }
11055
11056 }% AfterEndPreamble

```

Remember and patch some label-related definitions. These will be further encased and patched by other packages later.

\label and \pageref do NOT change their behavior according to print or HTML output, and thus do not use the \LWR@formatted system.

```

11057 \LetLtxMacro{\LWR@orig@label}{\label}
11058 \RenewDocumentCommand{\label}{\{}{\LWR@new@label\}}
11059
11060 \LetLtxMacro{\LWR@orig@pageref}{\pageref}
11061 \RenewDocumentCommand{\pageref}{\{}{\LWR@new@pageref\}}
11062 \end{warpHTML}

```

## 88 picture environment

`Env picture` The picture environment is enclosed inside a \latextimage.

---

**for HTML output:** 11063 \begin{warpHTML}

```
Env  picture

11064 \BeforeBeginEnvironment{picture}{\begin{lateximage}[picture]}
11065
11066 \AfterEndEnvironment{picture}{\end{lateximage}}

11067 \end{warpHTML}
```

## 89 Minipages and Boxes

A css flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

**⚠ inline** A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

**placement** `minipages` and `\parboxes` will be placed side-by-side in `HTML` unless you place a `\newline` between them.

**side-by-side** Side-by-side `minipages` may be separated by `\quad`, `\quad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and `HTML`. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

**⚠ minipage in a span** There is limited support for `minipages` inside an `HTML <span>`. An `HTML <div>` cannot appear inside a `<span>`. While in a `<span>`, `minipages`, and `\parboxes`, and any enclosed lists have limited `HTML` tags, resulting in an “`inline`” format, without markup except for `HTML` breaks. Use `\newline` or `\par` for an `HTML` break.

**⚠ minipage size** When using `minipage`, `\parbox`, and `fminipage`, a virtual  $6 \times 9$  inch text area is used for `\linewidth`, `\textwidth`, and `\textheight`, both for sizing the `minipage`, and also for its contents.

**if width is `\linewidth`** If a `minipage` or `\parbox` is assigned a width of exactly `\linewidth`, in `HTML` it is automatically given no `HTML` width, thus allowed to fill the line as needed, similar to how it appears in print output.

**full-width if `HTML`** A new macro `\minipagefullwidth` requests that, during `HTML` output, the next single `minipage` or `\parbox` be generated without an `HTML` `width` attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version’s width makes no sense in `HTML`.

**⚠ tabular, multicols** Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every `minipage` or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell `lwarp` to honor the specified widths of all following `minipages` and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell `lwarp` to ignore the specified widths.

- ⚠ **multicol** Inside a `multicols`, `\linewidth` is divided by the specified number of columns.
- ⚠ **text alignment** Nested `minipages` adopt their parent's text alignment in `HTML`, whereas in regular `LATEX PDF` output they do not. Use a `flushleft` or similar environment in the child `minipage` to force a text alignment.

**for HTML output:** 11068 `\begin{warpHTML}`

## 89.1 Computed lengths

Len `\LWR@minipagewidth` Used to convert the width into printable units.

11069 `\newlength{\LWR@minipagewidth}`

Len `\LWR@minipageheight` Used to convert the height into printable units.

11070 `\newlength{\LWR@minipageheight}`

## 89.2 Virtual page size

Ctr `\LWR@virtualpagedepth` Used to only reset the line width at the outermost `minipage`.

11071 `\newcounter{\LWR@virtualpagedepth}`  
 11072 `\setcounter{\LWR@virtualpagedepth}{0}`

Env `\LWR@setvirtualpage * [<columns>]`

If not nesting a `minipage`, adjust `\linewidth`, `\textwidth`, and `\textheight` for a virtual  $6 \times 9$  page, and start on a new `PDF` page to help prevent page overflows.

If starred, force a new page in the `PDF` before generating more `HTML`. This may be done to reduce the chance of page overflow when starting a new `minipage`.

The optional number of columns defaults to 1.

```
11073 \NewDocumentEnvironment{\LWR@setvirtualpage}{s 0{1}}{%
  11074   \ifnumequal{\value{\LWR@virtualpagedepth}}{0}{%
    11075     \IfBooleanT{#1}{\LWR@orignewpage}%
    11076     \setlength{\linewidth}{6in/#2}%
    11077     \setlength{\textwidth}{6in}%
    11078     \setlength{\textheight}{9in}%
  11079   }{}%
  11080   \addtocounter{\LWR@virtualpagedepth}{1}%
  11081 }%
  11082 {\addtocounter{\LWR@virtualpagedepth}{-1}}
```

## 89.3 Footnote handling

Also see section 59 for other forms of footnotes. `Minipage` footnotes are gathered in section 59.5, and then placed into the document in section 89.4.

## 89.4 Minipage handling

Bool LWR@minipagefullwidth Should the next minipage have no HTML width?

```
11083 \newbool{LWR@minipagefullwidth}
11084 \boolefalse{LWR@minipagefullwidth}
```

Bool LWR@forceminipagefullwidth Should the next minipage have no HTML width? Used to force full width for all minipages in an environment such as `tabular` or `multicols`, where the actual width depends on the browser width. Controlled by `\useminipagewidths` and `\ignoreminipagewidths`.

```
11085 \newbool{LWR@forceminipagefullwidth}
11086 \boolefalse{LWR@forceminipagefullwidth}
```

`\minipagefullwidth` Requests that the next minipage have no width tag in HTML:

**for HTML output:** 11087 `\newcommand*{\minipagefullwidth}{\global\booltrue{LWR@minipagefullwidth}}`

`\UseMinipageWidths` Locally requests that minipage widths be honored.

```
11088 \newcommand*{\UseMinipageWidths}{\boolefalse{LWR@forceminipagefullwidth}}
```

`\IgnoreMinipageWidths` Locally requests that minipage widths be ignored.

```
11089 \newcommand*{\IgnoreMinipageWidths}{\booltrue{LWR@forceminipagefullwidth}}
11090 \end{warpHTML}
```

**for PRINT output:** 11091 `\begin{warpprint}`  
 11092 `\newcommand*{\minipagefullwidth}{}{}`  
 11093 `\newcommand*{\UseMinipageWidths}{}{}`  
 11094 `\newcommand*{\IgnoreMinipageWidths}{}{}`  
 11095 `\end{warpprint}`

**for HTML output:** 11096 `\begin{warpHTML}`

Bool LWR@minipagethispar Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.

```
11097 \newbool{LWR@minipagethispar}
11098 \boolefalse{LWR@minipagethispar}
```

Env `minipage` [*vert position*] [*height*] [*inner vert position*] [*width*]

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using `\linewidth`, `\textwidth`, or `\textheight`, these are scaled proportionally to a 6x9 inch text area.

```
11099 \NewDocumentEnvironment{LWR@HTML@sub@minipage}{m m m m}
```

```
11100 {%
11101 \LWR@traceinfo{minipage}%

```

Start an environment, in which width and height is computed based on a virtual page size instead of the extra-large PDF page used during `HTML` tag generation.

```
11102 \begin{\LWR@setvirtualpage}*%
```

Save the requested width now that `\linewidth`, etc. are adjusted to virtual size.

```
11103 \setlength{\LWR@minipagewidth}{#4}%
11104 \ifnumequal{\value{\LWR@virtualpagedepth}}{1}{%
11105   \addtolength{\LWR@minipagewidth}{3em}%
11106 }{%
11107 \LWR@traceinfo{computed width is \LWR@printlength{\LWR@minipagewidth}}%
```

Compute height:

```
11108 \setlength{\LWR@minipageheight}{\textheight}%
11109 \ifblank{#2}{%
  \setlength{\LWR@minipageheight}{#2}%
}
```

`LATEX` wants to start a paragraph for the virtual minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

```
11110 \ifbool{FormatWP}{\newline}{%
11111 \LWR@stopars%
```

If `FormatWP`, add a text frame:

```
11112 \ifbool{FormatWP}{%
11113 %
11114 \addtocounter{\LWR@thisautoidWP}{1}%
11115 \LWR@htmltag{%
11116   div id="\LWR@print@mbox{autoidWP-\arabic{\LWR@thisautoidWP}}" %
11117   class="wpminipage"%
11118 }%
11119 %
11120 }{}}
```

Create the `<div>` tag with optional alignment style:

```
11121 \LWR@traceinfo{minipage: creating div class}%
11122 \LWR@htmltag{div class="minipage" style="%"%
11123 \ifthenelse{\equal{#1}{t}}{\LWR@print@mbox{vertical-align:bottom} ; }{%
11124 \ifthenelse{\equal{#1}{c}}{\LWR@print@mbox{vertical-align:middle} ; }{%
11125 \ifthenelse{\equal{#1}{b}}{\LWR@print@mbox{vertical-align:top} ; }{%
11126 \ifthenelse{\equal{#3}{t}}{\LWR@print@mbox{justify-content:flex-start} ; }{%
11127 \ifthenelse{\equal{#3}{c}}{\LWR@print@mbox{justify-content:center} ; }{%
11128 \ifthenelse{\equal{#3}{b}}{\LWR@print@mbox{justify-content:flex-end} ; }{%
11129 \ifthenelse{\equal{#3}{s}}{\LWR@print@mbox{justify-content:space-between} ; }{}}
```

Print the width and optional height styles:

```

11130 \LWR@traceinfo{minipage: about to print the width of \LWR@printlength{\LWR@minipagewidth}}%
11131 \ifbool{\LWR@minipagefullwidth}%
11132 {\global\boolfalse{\LWR@minipagefullwidth}}%
11133 {%
11134   \ifbool{\LWR@forceminipagefullwidth}%
11135     {}%
11136     {%
11137       \ifdimequal{#4}{\linewidth}%
11138         {}%
11139         {width:\LWR@printlength{\LWR@minipagewidth} ; }%
11140       {}%
11141 }%
11142 \LWR@traceinfo{minipage: about to print the height}%
11143 \ifblank{#2}{}{height:\LWR@printlength{\LWR@minipageheight} ; }%
11144 "}

```

Finish with an empty line to start the contents on a new line.

```

11145
11146 % The preceding empty line is required.

```

Set the user-accessible line and text width and height values inside the virtual minipage. These do not affect the actual size of the PDF output, but are used by any reference to \linewidth, etc. inside the virtual minipage being created here. \LWR@minipagewidth was the original then padded by 3em, which is restored here. This is done instead of settings back to #4, in case #4 was \linewidth, which was changed to 6in above.

```

11147 \ifnumequal{\value{\LWR@virtualpagedepth}}{1}{%
11148   \addtolength{\LWR@minipagewidth}{-3em}% undo frame padding
11149 }{%
11150 \setlength{\linewidth}{\LWR@minipagewidth}%

```

\raggedright cancels hyphenation, which will be done by HTML instead.

```
11151 \LWR@print@raggedright%
```

Set minipage footnotes:

```

11152 \def\mpfn{mpfootnote}%
11153 \def\thempfn{\thempfootnote}\c@mpfootnote\z@%
11154 \let\footnotetext\mpfootnotetext%

```

Resume paragraph tag handling for the contents of the minipage:

```

11155 \LWR@startpars%
11156 \ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%
11157
11158 === begin minipage ===
11159
11160 }{%
11161 \LWR@traceinfo{minipage: finished starting the minipage}%
11162 }% finished \minipage
11163 { \% \endminipage

```

Print pending minipage footnotes:

```
11164 \LWR@printpendingmpfootnotes%
```

End the environment with closing tag:

```
11165 \ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%
11166
11167 === end minipage ===
11168
11169 }{ }%
11170 \LWR@stoppars%
11171
11172 \ifbool{FormatWP}{%
11173
11174 \LWR@htmlelementend{div}%
11175
11176 }{ }%
11177 \LWR@htmldivclassend{minipage}%
11178
11179 \end{\LWR@setvirtualpage}%
11180 \LWR@startpars%
11181 \ifbool{FormatWP}{\newline}{ }%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
11182 \global\booltrue{\LWR@minipagethispar}%
11183 \LWR@traceinfo{\LWR@minipage: done}%
11184 }
11185
11186 \NewDocumentEnvironment{\LWR@HTML@minipage}{O{t} O{} O{t} m}
11187     {\LWR@HTML@sub@minipage[#1]{#2}{#3}{#4}}
11188     {\end{\LWR@HTML@sub@minipage}}
11189
11190 \LWR@formattedenv{minipage}
```

## 89.5 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox

**for HTML output:**

```
\parbox [⟨pos⟩] [⟨height⟩] [⟨inner-pos⟩] {⟨width⟩} {⟨text⟩}
```

A parbox uses the minipage code:

```
11191 \NewDocumentCommand{\LWR@HTML@parbox}{O{t} O{} O{t} m +m}%
11192 {
11193 \LWR@traceinfo{parbox of width #4}%
11194 \begin{minipage}[#1][#2][#3]{#4}%
11195 #5
11196 \end{minipage}%
11197 }
11198
11199 \LWR@formatted{parbox}
```

\mbox {*text*} Nullified for HTML.

```
11200 \newcommand*{\LWR@HTML@mbox}[1]{#1}
11201
11202 \LWR@formatted{mbox}
```

\LWR@@makebox@paren {*width*} , {*height*}

Adds to the style in \LWR@temptwo.

```
11203 \NewDocumentCommand{\LWR@@makebox@paren}{m m}{%
11204 \IfValueTF{#2}{%
11205   \setlength{\LWR@tempwidth}{#1\unitlength}%
11206   \setlength{\LWR@tempheight}{#2\unitlength}%
11207   \appto{\LWR@temptwo}{%
11208     \LWR@print@mbox{width:\LWR@printlength{\LWR@tempwidth}} ; % space
11209     \LWR@print@mbox{height:\LWR@printlength{\LWR@tempheight}} ; % space
11210   }%
11211 }{%
11212   \PackageError{lwarp}{%
11213     {(\width,\height) is missing a comma ',' character}%
11214     {\protect\makebox\space and \protect\framebox\space accept
11215       a size in the format (\width,\height).}%
11216 }%
11217 }
```

\LWR@@makebox@align {*alignment character*}

Adds to the style in \LWR@temptwo.

```
11218 \newcommand*{\LWR@@makebox@align}[1]{%
11219   \def\LWR@align{center}%
11220   \ifstrequal{#1}{l}{\def\LWR@align{left}}{}%
11221   \ifstrequal{#1}{r}{\def\LWR@align{right}}{}%
11222   \ifstrequal{#1}{s}{\def\LWR@align{justify}}{}%
11223   \appto{\LWR@temptwo}{%
11224     \LWR@print@mbox{text-align:\LWR@align} ; %
11225   }%
11226 }
```

\makebox {*width,height*} [*width*] [*pos*] {*text*}

```
11227 \NewDocumentCommand{\LWR@HTML@makebox}{>{\SplitArgument{1}{,}}d() o o +m}{%
```

Build the style depending on arguments:

```
11228   \begin{\LWR@setvirtualpage}%
11229     \def\LWR@temptwo{}%
11230     \IfValueTF{#1}{%
11231       {%
11232         \LWR@@makebox@paren #1%
11233         \IfValueT{#2}{%
11234           {%
11235             \LWR@@makebox@posn
```

```

11235           \LWR@@makebox@align{#2}%
11236       }%
11237   }%
11238   {%
11239     [width]
11240     \IfValueT{#2}{ [width]
11241       \setlength{\LWR@tempwidth}{#2}%
11242       \ifdimgreater{\LWR@tempwidth}{0pt}{%
11243         \appto{\LWR@temptwo}{%
11244           width:\LWR@printlength{\LWR@tempwidth} ; % space
11245         }%
11246       }{%
11247         }%
11248       }%
11249     \IfValueT{#3}{%
11250       {%
11251         [width] [posn]
11252         \LWR@@makebox@align{#3}%
11253       }%
11254       \InlineClass[%
11255         \LWR@print@mbox{display:inline-block} ; %
11256         \LWR@temptwo%
11257       ]%
11258       {makebox}%
11259       {#4}%
11260     }%
11261   \end{\LWR@setvirtualpage}%
11262 }%
11263 \LWR@formatted{makebox}

```

\framebox ((*width,height*) [*width*] [*pos*] {*text*})

```

11262 \NewDocumentCommand{\LWR@HTML@framebox}{d() o o +m}{%
11263   \fbox{\makebox[#1][#2][#3]{#4}}%
11264 }
11265
11266 \LWR@formatted{framebox}

```

\LWR@forceminwidth {*length*}

Sets \LWR@atleastonept to be at least 1pt.

```

11267 \newlength{\LWR@atleastonept}
11268
11269 \newcommand*{\LWR@forceminwidth}[1]{%
11270   \setlength{\LWR@atleastonept}{#1}%
11271   \ifthenelse{%
11272     \lengthtest{\LWR@atleastonept>0pt}\AND%
11273     \lengthtest{\LWR@atleastonept<1pt}%
11274   }{%
11275     \setlength{\LWR@atleastonept}{1pt}%
11276   }%
11277 }

```

\LWR@fboxstyle Prints the HTML attributes for a black border and padding.

\LWR@forceminwidth must be used first in order to set the border width.

```
11278 \newcommand*{\LWR@fboxstyle}{%
11279 \LWR@findcurrenttextcolor%
11280 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@origpound\LWR@tempcolor ; %
11281 padding:\LWR@printlength{\fboxsep} ; %
11282 color:\LWR@origpound\LWR@tempcolor%
11283 }
```

\fbox {*text*}

Creates a framed inline span enclosing the text.

Create a new HTML version, but don't use it until after xcolor may have loaded:

```
11284 \newcommand{\LWR@HTML@fbox}[1]{%
11285 \LWR@traceinfo{HTML_fbox}%
11286 \LWR@forceminwidth{\fboxrule}%
11287 \InlineClass[%
11288     \LWR@print@mbox{display:inline-block} ; %
11289     \LWR@fboxstyle%
11290 ]{\fbox}{#1}%
11291 }
```

xcolor \lets things to \fbox when it is loaded, and this must remain even for HTML output while in a lateximage, so \fbox is not modified until \AtBeginDocument:

```
11292 \AtBeginDocument{\LWR@formatted{fbox}}
```

\fboxBlock {*text*} Creates a framed HTML <div> of the text.

First, a print-mode version. This is newly defined for print mode, so it is defined inside warpall.

**for HTML & PRINT:**

```
11293 \end{warpHTML}%
11294 \begin{warpall}%
11295 \let\fboxBlock\fbox%
11296 \end{warpall}%
11297%
11298 \begin{warpHTML}
```

**for HTML output:** Next, an HTML version:

```
11299 \newcommand{\LWR@HTML@fboxBlock}[1]{%
11300 \LWR@forceminwidth{\fboxrule}%
11301 \LWR@stoppars%
11302 \begin{BlockClass}[%%
11303 \LWR@fboxstyle%
11304 ]{\fboxBlock}%
11305 #1%
11306 \end{BlockClass}%
11307 \LWR@startpars%
11308 }%
11309
```

```

11310 \LWR@formatted{fboxBlock}
11311
11312 \end{warpHTML}
```

**Env fminipage** [*align*] [*height*] [*align*] {*width*}

Creates a framed HTML <div> around its contents.

**for HTML & PRINT:** Print version:

```

11313 \begin{warpall}
11314
11315 \newsavebox{\LWR@fminipagebox}
11316
11317 \NewDocumentEnvironment{\LWR@print@fminipage}{O{t} o O{t} m}
11318 {%
```

An outer minipage will be used for vertical alignment. An inner minipage will be framed with \fbox.

If the optional inner alignment is not given, use the outer instead:

```

11319 \IfValueTF{#3}%
11320 {\def\LWR@thisalign{#3}}
11321 {\def\LWR@thisalign{#1}}%
```

Form the outer minipage depending on whether a height was given. Make the outer minipage larger to compensate for the frame.

```

11322 \IfValueTF{#2}%
11323 {\minipage[#1][#2+2\fboxsep+2\fboxrule][\LWR@thisalign]{#4+2\fboxsep+2\fboxrule}}%
11324 {\minipage[#1]{#4+2\fboxsep+2\fboxrule}}%
```

Capture the contents of the environment:

```
11325 \begin{lrbox}{\LWR@fminipagebox}%
```

Nest the contents inside an inner minipage of the desired size:

```

11326 \IfValueTF{#2}%
11327 {\minipage[#1][#2][\LWR@thisalign]{#4}}%
11328 {\minipage[#1]{#4}}%
11329 }
11330 {%
```

Close the inner minipage and the LR box with the contents:

```

11331 \endminipage%
11332 \end{lrbox}%
```

Create a frame around the contents of the environment:

```
11333 \fbox{\usebox{\LWR@fminipagebox}}%
```

The entire thing is placed inside the outer minipage:

```

11334 \endminipage%
11335 }
11336
11337 \LetLtxMacro\fminipage\LWR@print@fminipage
11338 \LetLtxMacro\endfminipage\endLWR@print@fminipage
11339 % \newenvironment{fminipage}{\LWR@print@fminipage}{\endLWR@print@fminipage}
11340
11341 \end{warpall}
```

HTML version:

**for HTML output:**

```

11342 \begin{warpHTML}
11343
11344 \NewDocumentEnvironment{\LWR@HTML@fminipage}{O{t} o O{t} m}
11345 {%
11346 \LWR@traceinfo{fminipage #1 #2 #3 #4}%
```

Locally change to the virtual page size before processing the requested sizes:

```

11347 \begin{LWR@setvirtualpage}*
11348 \setlength{\LWR@tempwidth}{#4}%
11349 \IfValueT{#2}{\setlength{\LWR@tempheight}{#2}}%
```

Use a rule of at least one pixel in width:

```

11350 \LWR@forceminwidth{\fboxrule}%
11351 \LWR@stoppars%
11352 \begin{BlockClass}{%
11353 \LWR@fboxstyle ; %
11354 \IfValueT{#2}{height:\LWR@printlength{\LWR@tempheight} ; }%
11355 \ifbool{\LWR@minipagefullwidth}{%
11356 {\global\boolfalse{\LWR@minipagefullwidth}}%
11357 {%
11358   \ifbool{\LWR@forceminipagefullwidth}{%
11359     {}%
11360     {%
11361       \ifdimequal{\LWR@tempwidth}{\linewidth}{%
11362         {}%
11363         {width:\LWR@printlength{\LWR@tempwidth} ; }%
11364       }%
11365     }%
11366   ]{fminipage}%
11367 }%
11368 {%
11369 \end{BlockClass}%
11370 \end{LWR@setvirtualpage}%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

---

```

11371 \global\booltrue{LWR@minipagethispar}%
11372 \LWR@traceinfo{fminipage done}%
11373 }%
11374
11375 \LWR@formattedeenv{fminipage}

\raisebox {⟨raiselen⟩} [⟨height⟩] [⟨depth⟩] {⟨text⟩}

11376 \NewDocumentCommand{\LWR@HTML@raisebox}{m o o m}{%
11377 #4%
11378 }%
11379
11380 \LWR@formattede{raisebox}

11381 \end{warpHTML}

```

## 90 Direct formatting

⚠ **\bfseries, etc.** `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ **HTML special chars** &, <, and > have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

**program listings** For program listings, the `listings` package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.

**verbatim** The various `verbatim`-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

For high-level block and inline custom CSS classes, see section [51.9](#).

**for HTML output:** 11382 `\begin{warpHTML}`

```

\emph {⟨text⟩}

11383 \DeclareRobustCommand{\LWR@HTML@emph}[1]{%
11384   {%
11385     \LWR@HTML@itshape%
11386     \LWR@htmlspan{em}{#1}%
11387   }%
11388 }
11389
11390 \LWR@formattede{emph}
11391
11392 \newcommand{\LWR@null@emph}[1]{#1}

\textmd {⟨text⟩}

```

```
11393 \DeclareRobustCommand{\LWR@HTML@textmd}[1]{%
11394     {%
11395         \LWR@HTML@mdseries%
11396         \InlineClass{font-weight:normal}{textmd}{#1}%
11397     }%
11398 }
11399
11400 \LWR@formatted{textmd}
11401
11402 \newcommand{\LWR@null@textmd}[1]{#1}
```

\textbf{ \{*text*\}}

```
11403 \DeclareRobustCommand{\LWR@HTML@textbf}[1]{%
11404     {%
11405         \LWR@HTML@bfseries%
11406         \LWR@htmlspan{b}{#1}%
11407     }%
11408 }
11409
11410 \LWR@formatted{textbf}
11411
11412 \newcommand{\LWR@null@textbf}[1]{#1}
```

\textbf{ \{*text*\}} From **nfssext-cfr**.

```
11413 \DeclareRobustCommand{\LWR@HTML@texteb}[1]{%
11414     {%
11415         \LWR@HTML@ebweight%
11416         \InlineClass{texteb}{#1}%
11417     }%
11418 }
11419
11420 \LWR@formatted{texteb}
11421
11422 \newcommand{\LWR@null@texteb}[1]{#1}
```

\textbf{ \{*text*\}} From **nfssext-cfr**.

```
11423 \DeclareRobustCommand{\LWR@HTML@textlg}[1]{%
11424     {%
11425         \LWR@HTML@lgweight%
11426         \InlineClass{textlg}{#1}%
11427     }%
11428 }
11429
11430 \LWR@formatted{textlg}
11431
11432 \newcommand{\LWR@null@textlg}[1]{#1}
```

\textbf{ \{*text*\}}

```
11433 \DeclareRobustCommand{\LWR@HTML@textrm}[1]{%
11434     {%
11435         \LWR@HTML@rmfamily%
11436         \InlineClass(font-family:serif){textrm}{#1}%
11437     }%
11438 }
11439
11440 \LWR@formatted{textrm}
11441
11442 \newcommand{\LWR@null@textrm}[1]{#1}

\textsf  {\langle text\rangle}

11443 \DeclareRobustCommand{\LWR@HTML@textsf}[1]{%
11444     {%
11445         \LWR@HTML@sffamily%
11446         \InlineClass(font-family:sans){textsf}{#1}%
11447     }%
11448 }
11449
11450 \LWR@formatted{textsf}
11451
11452 \newcommand{\LWR@null@textsf}[1]{#1}

\texttt  {\langle text\rangle}

11453 \DeclareRobustCommand{\LWR@HTML@texttt}[1]{%
11454     {%
11455         \LWR@HTML@ttfamily%
11456         \LWR@htmlspan{kbd}{#1}%
11457     }%
11458 }
11459
11460 \LWR@formatted{texttt}
11461
11462 \newcommand{\LWR@null@texttt}[1]{#1}

\textup  {\langle text\rangle}

11463 \DeclareRobustCommand{\LWR@HTML@textup}[1]{%
11464     {%
11465         \LWR@HTML@upshape%
11466         \InlineClass(font-style:normal){textup}{#1}%
11467     }%
11468 }
11469
11470 \LWR@formatted{textup}
11471
11472 \newcommand{\LWR@null@textup}[1]{#1}

\textit  {\langle text\rangle}
```

```
11473 \DeclareRobustCommand{\LWR@HTML@textit}[1]{%
11474     {%
11475         \LWR@HTML@itshape%
11476         \LWR@htmlspan{i}{#1}%
11477     }%
11478 }
11479
11480 \LWR@formatted{textit}
11481
11482 \newcommand{\LWR@null@textit}[1]{#1}
```

\textsc {\textit{*text*}}

```
11483 \DeclareRobustCommand{\LWR@HTML@textsc}[1]{%
11484     {%
11485         \LWR@HTML@scshape%
11486         \InlineClass{textsc}{#1}%
11487     }%
11488 }
11489
11490 \LWR@formatted{textsc}
11491
11492 \newcommand{\LWR@null@textsc}[1]{#1}
```

\textulc {\textit{*text*}} From fontaxes.

```
11493 \DeclareRobustCommand{\LWR@HTML@textulc}[1]{%
11494     {%
11495         \LWR@HTML@ulcshape%
11496         \InlineClass{textulc}{#1}%
11497     }%
11498 }
11499
11500 \LWR@formatted{textulc}
11501
11502 \newcommand{\LWR@null@textulc}[1]{#1}
```

\textssi {\textit{*text*}}

```
11503 @ifundefined{textssi}{
11504     \LetLtxMacro{\LWR@print@textsi}{\LWR@print@textsc
11505 }{%
11506
11507 \DeclareRobustCommand{\LWR@HTML@textssi}[1]{%
11508     {%
11509         \LWR@HTML@sishape%
11510         \textsc{\textit{#1}}%
11511 %         \InlineClass{
11512 %             font-style: italic;
11513 %             font-variant: small-caps ;
11514 %             font-variant-numeric: oldstyle-nums ;
11515 %             ){textssi}{#1}%
11516     }%
```

```

11517 }
11518
11519 \LWR@formatted{textsi}
11520
11521 \newcommand{\LWR@null@textsi}[1]{#1}

\textsl {<text>}

11522 \DeclareRobustCommand{\LWR@HTML@textsl}[1]{%
11523   {%
11524     \slshape%
11525     \InLineClass(font-style:oblique){textsl}{#1}%
11526   }%
11527 }
11528
11529 \LWR@formatted{textsl}
11530
11531 \newcommand{\LWR@null@textsl}[1]{#1}

\textnormal {<text>}

11532 \DeclareRobustCommand{\LWR@HTML@textnormal}[1]{\textmd{\textrm{\textup{#1}}}}%
11533
11534 \LWR@formatted{textnormal}
11535
11536 \newcommand{\LWR@null@textnormal}[1]{#1}

11537 \newcommand{\LWR@null@rmfamily}{}
11538 \newcommand{\LWR@null@sffamily}{}
11539 \newcommand{\LWR@null@ttfamily}{}
11540 \newcommand{\LWR@null@bfseries}{}
11541 \newcommand{\LWR@null@ebweight}{}
11542 \newcommand{\LWR@null@lgweight}{}
11543 \newcommand{\LWR@null@mdseries}{}
11544 \newcommand{\LWR@null@upshape}{}
11545 \newcommand{\LWR@null@slshape}{}
11546 \newcommand{\LWR@null@scshape}{}
11547 \newcommand{\LWR@null@itshape}{}
11548 \newcommand{\LWR@null@normalfont}{}

11549 \newcommand{\LWR@null@em}{}

\LWR@nullfonts Removes formatting during filename operations, file references, and HTML comments.

```

△ **Use only inside a group.**

The following are *not* made robust, since they must be expanded to their nullified versions.

```

11550 \catcode`\$=\active% redefining $ below
11551 \catcode`\_=12% redefining \_ below
11552 \newcommand*\LWR@nullfonts{%

```

11553 \LetLtxMacro{\emph}{\LWR@null@emph}%  
11554 \LetLtxMacro{\textmd}{\LWR@null@textmd%  
11555 \LetLtxMacro{\textbf}{\LWR@null@textbf%  
11556 \LetLtxMacro{\textrm}{\LWR@null@textrm%  
11557 \LetLtxMacro{\textsf}{\LWR@null@textsf%  
11558 \LetLtxMacro{\texttt}{\LWR@null@texttt%  
11559 \LetLtxMacro{\textup}{\LWR@null@textup%  
11560 \LetLtxMacro{\textit}{\LWR@null@textit%  
11561 \LetLtxMacro{\textsc}{\LWR@null@textsc%  
11562 \LetLtxMacro{\textulc}{\LWR@null@textulc%  
11563 \LetLtxMacro{\textsi}{\LWR@null@textsi%  
11564 \LetLtxMacro{\textsl}{\LWR@null@textsl%  
11565 \LetLtxMacro{\textnormal}{\LWR@null@textnormal%  
11566 \LetLtxMacro{\rmfamily}{\LWR@null@rmfamily%  
11567 \LetLtxMacro{\sffamily}{\LWR@null@sffamily%  
11568 \LetLtxMacro{\ttfamily}{\LWR@null@ttfamily%  
11569 \LetLtxMacro{\bfseries}{\LWR@null@bfseries%  
11570 \LetLtxMacro{\mdseries}{\LWR@null@mdseries%  
11571 \LetLtxMacro{\upshape}{\LWR@null@upshape%  
11572 \LetLtxMacro{\slshape}{\LWR@null@slshape%  
11573 \LetLtxMacro{\scshape}{\LWR@null@scshape%  
11574 \LetLtxMacro{\ulcshape}{\LWR@null@ulcshape%  
  
11575 \LetLtxMacro{\sishape}{\LWR@null@sishape%  
  
11576 \LetLtxMacro{\itshape}{\LWR@null@itshape%  
11577 \LetLtxMacro{\normalfont}{\LWR@null@normalfont%  
11578 \LetLtxMacro{\em}{\LWR@null@em%

## Various built-in symbols.

```
11579 \renewcommand*{\$}{-}%
11580 \renewcommand*{\%}{-}%
11581 \renewcommand*{\_}{-}%
11582 \renewcommand*{\}}{-}%
11583 \renewcommand*{\}{-}%
11584 \renewcommand*{\&}{and}%
11585 \renewcommand*{\#}{-}%
11586 \renewcommand*{\,}{-}%
11587 \renewcommand*{\~}{-}%
11588 \renewcommand*{\^}[1]{-}%
11589 \renewcommand*{\~}[1]{-}%
11590 \renewcommand*{\newline}{-}%
11591 \renewcommand*{\textasciicircum}{-}%
11592 \renewcommand*{\textasciitilde}{-}%
11593 \renewcommand*{\textasteriskcentered}{-}%
11594 \renewcommand*{\textbackslash}{-}%
11595 \renewcommand*{\textbar}{-}%
11596 \renewcommand*{\textbardbl}{-}%
11597 \renewcommand*{\textbigcircle}{-}%
11598 \renewcommand*{\textbraceleft}{-}%
11599 \renewcommand*{\textbraceright}{-}%
11600 \renewcommand*{\textbullet}{-}%
11601 \renewcommand*{\textcopyright}{-}%
```

```
11602 \renewcommand*\{\textdagger}{-}%
11603 \renewcommand*\{\textdaggerdbl}{-}%
11604 \renewcommand*\{\textdollar}{-}%
11605 \renewcommand*\{\textellipsis}{-}%
11606 \renewcommand*\{\textemdash}{-}%
11607 \renewcommand*\{\textendash}{-}%
11608 \renewcommand*\{\textexclamdown}{-}%
11609 \renewcommand*\{\textgreater}{-}%
11610 \renewcommand*\{\textless}{-}%
11611 \renewcommand*\{\textordfeminine}{-}%
11612 \renewcommand*\{\textordmasculine}{-}%
11613 \renewcommand*\{\textparagraph}{-}%
11614 \renewcommand*\{\textperiodcentered}{-}%
11615 \renewcommand*\{\textpertenthousand}{-}%
11616 \renewcommand*\{\textperthousand}{-}%
11617 \renewcommand*\{\textquestiondown}{-}%
11618 \renewcommand*\{\textquotedblleft}{-}%
11619 \renewcommand*\{\textquotedblright}{-}%
11620 \renewcommand*\{\textquoteright}{-}%
11621 \renewcommand*\{\textquoteright}{-}%
11622 \renewcommand*\{\textregistered}{-}%
11623 \renewcommand*\{\textsection}{-}%
11624 \renewcommand*\{\textsterling}{-}%
11625 \renewcommand*\{\texttrademark}{-}%
11626 \renewcommand*\{\textunderscore}{-}%
11627 \renewcommand*\{\textvisiblespace}{-}%
11628 \renewcommand*\{\copyright}{-}%
11629 \renewcommand*\{\dag}{-}%
11630 \renewcommand*\{\ddag}{-}%
11631 \renewcommand*\{\dots}{-}%
11632 \renewcommand*\{\P}{-}%
11633 \renewcommand*\{\pounds}{-}%
11634 \renewcommand*\{\S}{-}%
11635 \renewcommand*\{\aa}{a}%
11636 \renewcommand*\{\AA}{A}%
11637 \renewcommand*\{\AE}{AE}%
11638 \renewcommand*\{\ae}{ae}%
11639 \renewcommand*\{\dh}{d}%
11640 \renewcommand*\{\DH}{D}%
11641 \renewcommand*\{\DJ}{D}%
11642 \renewcommand*\{\dj}{d}%
11643 \renewcommand*\{\IJ}{IJ}%
11644 \renewcommand*\{\ij}{ij}%
11645 \renewcommand*\{\L}{L}%
11646 \renewcommand*\{\l}{l}%
11647 \renewcommand*\{\NG}{NG}%
11648 \renewcommand*\{\ng}{ng}%
11649 \renewcommand*\{\O}{O}%
11650 \renewcommand*\{\o}{o}%
11651 \renewcommand*\{\oe}{oe}%
11652 \renewcommand*\{\OE}{OE}%
11653 \renewcommand*\{\ss}{ss}%
11654 \renewcommand*\{\SS}{SS}%
11655 \renewcommand*\{\th}{th}%
11656 \renewcommand*\{\TH}{TH}%
```

```

11657 \renewcommand*\{\guillemotleft\}{ }%
11658 \renewcommand*\{\guilsinglleft\}{ }%
11659 \renewcommand*\{\quotedblbase\}{ }%
11660 \renewcommand*\{\textquotedbl\}{ }%
11661 \renewcommand*\{\guillemotright\}{ }%
11662 \renewcommand*\{\guilsinglright\}{ }%
11663 \renewcommand*\{\quotenglbase\}{ }%

11664 \renewcommand*\{\HTMLunicode\}[1]{ }%
11665 \renewcommand*\{\HTMLentity\}[1]{ }%

11666 \renewcommand{\textsuperscript}[1]{##1}%
11667 \renewcommand{\textsubscript}[1]{##1}%

11668 \renewcommand{\underline}[1]{##1}%

11669 \RenewDocumentCommand{\hspace}{s m}{ }%
11670 \RenewDocumentCommand{\LWR@htmlspanclass}{o m +m}{##3}%
11671 \DeclareExpandableDocumentCommand{\InlineClass}{D{(){}{}} o m +m}{##4}%

```

Nullify math macros.

```

11672 \def\(\##1\){ }%
11673 \def\[##1\]{ }%
11674 \RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{ }%
11675 \protected\def$##1\${ }%

```

Nullify logos:

```

11676 \renewcommand*\{\TeX\}{TeX}%
11677 \renewcommand*\{\LaTeX\}{LaTeX}%
11678 \renewcommand*\{\LaTeXe\}{LaTeXe}%
11679 \renewcommand*\{\LuaTeX\}{LuaTeX}%
11680 \renewcommand*\{\LuaLaTeX\}{LuaLaTeX}%
11681 \renewcommand*\{\XeTeX\}{XeTeX}%
11682 \renewcommand*\{\XeLaTeX\}{XeLaTeX}%
11683 \renewcommand*\{\ConTeXt\}{ConTeXt}%
11684 \renewcommand*\{\BibTeX\}{BibTeX}%
11685 \renewcommand*\{\MakeIndex\}{MakeIndex}%
11686 \renewcommand*\{\AmS\}{AmS}%
11687 \renewcommand*\{\MiKTeX\}{MiKTeX}%
11688 \renewcommand*\{\LyX\}{LyX}%

```

Use the simpler form with `\texorpdfstring`:

```

11689 \let\texorpdfstring\relax%
11690 \newcommand{\texorpdfstring}[2]{##2}%
11691 }%
11692 \catcode`\$=3%
11693 \catcode`\_=8%

```

---

```
\FilenameNullify {⟨redefinitions⟩}
```

Adds more nullifying definitions for filename generation.

```
11694 \newcommand*\{\FilenameNullify}[1]{%
11695     \appto{\LWR@nullfonts}{#1}%
11696 }
```

Remembers the current font family, series, and shape. `fontaxes` support is integrated here.

```
11697 \newcommand*\{\LWR@f@family\}{rm}%
11698 \newcommand*\{\LWR@f@series\}{md}%
11699 \newcommand*\{\LWR@f@shape\}{up}%
11700 \newcommand*\{\LWR@f@shapecaps\}{ulc}
```

```
\LWR@textcurrentfont {⟨text⟩}
```

Prints the text with the current font choices. Avoids nesting repeated font selections.

```
11701 \newcounter{\LWR@textcurrentfontdepth}
11702 \setcounter{\LWR@textcurrentfontdepth}{0}
11703
11704 \newcommand*\{\LWR@textcurrentfont}[1]{%
11705     \ifnumcomp{\value{\LWR@textcurrentfontdepth}}{>}{0}%
11706         {%
11707             \addtocounter{\LWR@textcurrentfontdepth}{1}%
11708             #1%
11709             \addtocounter{\LWR@textcurrentfontdepth}{-1}%
11710         }%
11711     {%
11712         \addtocounter{\LWR@textcurrentfontdepth}{1}%
11713         \InlineClass{%
11714             text\LWR@f@family\LWR@origtilde{}%
11715             text\LWR@f@series\LWR@origtilde{}%
11716             text\LWR@f@shape\LWR@origtilde{}%
11717             text\LWR@f@shapecaps%
11718         }%
11719         {#1}%
11720         \addtocounter{\LWR@textcurrentfontdepth}{-1}%
11721     }%
11722 }
```

Env `LWR@blocktextcurrentfont` Prints the contents with the current font choices.

```
11723 \newenvironment*\{\LWR@blocktextcurrentfont\}{%
11724 \LWR@stoppars%
11725 \BlockClass{%
11726     text\LWR@f@family\LWR@origtilde{}%
11727     text\LWR@f@series\LWR@origtilde{}%
11728     text\LWR@f@shape\LWR@origtilde{}%
11729     text\LWR@f@shapecaps%
11730 }}
```

```
11731 }{\endBlockClass\LWR@startpars}
```

#### \mdseries

```
11732 \newrobustcmd*{\LWR@HTML@mdseries}{\renewcommand*{\LWR@f@series}{md}}  
11733 \LWR@formatted{mdseries}
```

#### \bfseries

```
11734 \newrobustcmd*{\LWR@HTML@bfseries}{\renewcommand*{\LWR@f@series}{bf}}  
11735 \LWR@formatted{bfseries}
```

#### \ebweight From nfssext-cfr.

```
11736 \newrobustcmd*{\LWR@HTML@ebweight}{\renewcommand*{\LWR@f@series}{eb}}  
11737 \LWR@formatted{ebweight}
```

#### \lgweight From nfssext-cfr.

```
11738 \newrobustcmd*{\LWR@HTML@lgweight}{\renewcommand*{\LWR@f@series}{lg}}  
11739 \LWR@formatted{lgweight}
```

#### \rmfamily

```
11740 \newrobustcmd*{\LWR@HTML@rmfamily}{\renewcommand*{\LWR@f@family}{rm}}  
11741 \LWR@formatted{rmfamily}
```

#### \sffamily

```
11742 \newrobustcmd*{\LWR@HTML@sffamily}{\renewcommand*{\LWR@f@family}{sf}}  
11743 \LWR@formatted{sffamily}
```

#### \ttfamily

```
11744 \newrobustcmd*{\LWR@HTML@ttfamily}{\renewcommand*{\LWR@f@family}{tt}}  
11745 \LWR@formatted{ttfamily}
```

#### \upshape

```
11746 \newrobustcmd*{\LWR@HTML@upshape}{\renewcommand*{\LWR@f@shape}{up}}  
11747 \LWR@formatted{upshape}
```

#### \itshape

```
11748 \newrobustcmd*{\LWR@HTML@itshape}{\renewcommand*{\LWR@f@shape}{it}}  
11749 \LWR@formatted{itshape}
```

\scshape

```
11750 \newrobustcmd*{\LWR@HTML@scshape}{\renewcommand*{\LWR@f@shapecaps}{sc}}
11751 \LWR@formatted{scshape}
```

\ulcshape From fontaxes.

```
11752 \@ifundefined{ulcshape}{
11753     \LetLtxMacro{\ulcshape}{\upshape}
11754 }{}
11755 \newrobustcmd*{\LWR@HTML@ulcshape}{\renewcommand*{\LWR@f@shapecaps}{ulc}}
11756 \LWR@formatted{ulcshape}
```

\sishape

```
11757 \@ifundefined{sishape} {
11758     \LetLtxMacro{\sishape}{\scshape}
11759 } {}
11760 \newrobustcmd*{\LWR@HTML@sishape}{%
11761     \renewcommand*{\LWR@f@shape}{it}
11762     \renewcommand*{\LWR@f@shapecaps}{sc}%
11763 }
11764 \LWR@formatted{sishape}
```

\slshape

```
11765 \newrobustcmd*{\LWR@HTML@slshape}{\renewcommand*{\LWR@f@shape}{sl}}
11766 \LWR@formatted{slshape}
```

\normalfont

```
11767 \newrobustcmd*{\LWR@HTML@normalfont}{\rmfamily\mdseries\upshape\ulcshape}
11768 \LWR@formatted{normalfont}
```

\sp {*text*}

For **siunitx**. Must work in math mode.

```
11769 \renewcommand{\sp}[1]{\text{\textsuperscript{\#1}}}
```

\sb {*text*}

For **siunitx**. Must work in math mode.

```
11770 \renewcommand{\sb}[1]{\text{\textsubscript{\#1}}}
```

\textsuperscript {*text*}

```
11771 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

```
\@textsuperscript {<text>}

11772 \renewcommand{\@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}


\textsubscript {<text>}

11773 \AtBeginDocument{
11774 \renewrobustcmd{\textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
11775 }

\@textsubscript {<text>}

11776 \AtBeginDocument{
11777 \renewcommand{\@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
11778 }
```

\up {<text>} Prints superscript.

This is \let at the beginning of the document in case some other package has changed the definition.

```
11779 \AtBeginDocument{\let\up\textsuperscript}
```

\fup {<text>} Prints superscript.

Supports **fmtcount** package.

This is \let at the beginning of the document in case some other package has changed the definition.

```
11780 \AtBeginDocument{\let\fup\textsuperscript}
```

\underline {<text>}

```
11781 \renewcommand{\underline}[1]{%
11782     \InlineClass{%
11783         (text-decoration:underline; text-decoration-skip: auto)%
11784         {underline}{#1}%
11785 }}
```

\LWR@overline {<text>}

```
11786 \newcommand{\LWR@overline}[1]{%
11787     \InlineClass{%
11788         (text-decoration:overline; text-decoration-skip: auto)%
11789         {overline}{#1}%
11790 }}
```

\LWR@currenttextcolor The color to use for text and \rule, defaulting to black:

```
11791 \newcommand*\LWR@currenttextcolor{black}
```

---

\LWR@tempcolor The color converted to HTML colorspace.  
\LWR@tempcolortwo

```
11792 \newcommand*\{\LWR@tempcolor\}{}  
11793 \newcommand*\{\LWR@tempcolortwo\}{}  
11794 \newcommand*\{\LWR@findcurrenttextcolor\}{%  
11795 \renewcommand{\LWR@tempcolor}{000000}%  
11796 }
```

\LWR@findcurrenttextcolor Sets \LWR@tempcolor to the current color.

```
11794 \newcommand*\{\LWR@findcurrenttextcolor\}{%  
11795 \renewcommand{\LWR@tempcolor}{000000}%  
11796 }
```

\LWR@textcurrentcolor {\langle text\rangle} Like \textcolor but uses the current \color instead.

```
11797 \NewDocumentCommand{\LWR@textcurrentcolor}{m}{%  
11798     \renewcommand*\{\LWR@currenttextcolor\}{black}%  
11799     #1%  
11800 }  
11801 \end{warpHTML}
```

**for PRINT output:** 11802 \begin{warpprint}

\LWR@textcurrentfont {\langle text\rangle}

Prints the text with the current font choices.

```
11803 \newcommand*\{\LWR@textcurrentfont\}[1]{#1}
```

Env \LWR@blocktextcurrentfont Prints the contents with the current font choices.

```
11804 \newenvironment*\{\LWR@blocktextcurrentfont\}{}{}
```

\FilenameNullify {\langle macros to nullify\rangle}

```
11805 \newcommand*\{\FilenameNullify\}[1]{}  
11806 \end{warpprint}
```

## 91 Skips, spaces, font sizes

**for HTML output:** 11807 \begin{warpHTML}

\, and \thinspace may be redefined by other packages, so are redefined \AtBeginDocument here.

Direct-formatting space commands become HTML entities:

```

11808 \AtBeginDocument{
11809 \renewrobustcmd*{\,}{\HTMLunicode{202f}} % HTML thin non-breakable space
11810 \renewrobustcmd*{\thinspace}{\HTMLunicode{202f}} % HTML thin non-breakable space
11811 \renewrobustcmd*{\negthinspace}{\HTMLunicode{202f}} % HTML thin non-breakable space
11812 \renewrobustcmd*{\~}{\HTMLentity{nbsp}}
11813 \renewrobustcmd*{\textellipsis}{\HTMLunicode{2026}}
11814 }

```

Direct-formatting font sizes are remembered for future use:

```

11815 \newcommand*{\LWR@font@size}{\normalsize}
11816
11817 \newrobustcmd*{\LWR@HTML@normalsize}{\renewcommand*{\LWR@font@size}{\normalsize}}
11818 \LWR@formatted{normalsize}
11819
11820 \newrobustcmd*{\LWR@HTML@small}{\renewcommand*{\LWR@font@size}{\small}}
11821 \LWR@formatted{small}
11822
11823 \newrobustcmd*{\LWR@HTML@footnotesize}{\renewcommand*{\LWR@font@size}{\footnotesize}}
11824 \LWR@formatted{footnotesize}
11825
11826 \newrobustcmd*{\LWR@HTML@scriptsize}{\renewcommand*{\LWR@font@size}{\scriptsize}}
11827 \LWR@formatted{scriptsize}
11828
11829 \newrobustcmd*{\LWR@HTML@tiny}{\renewcommand*{\LWR@font@size}{\tiny}}
11830 \LWR@formatted{tiny}
11831
11832 \newrobustcmd*{\LWR@HTML@large}{\renewcommand*{\LWR@font@size}{\large}}
11833 \LWR@formatted{large}
11834
11835 \newrobustcmd*{\LWR@HTML@Large}{\renewcommand*{\LWR@font@size}{\Large}}
11836 \LWR@formatted{Large}
11837
11838 \newrobustcmd*{\LWR@HTML@LARGE}{\renewcommand*{\LWR@font@size}{\LARGE}}
11839 \LWR@formatted{LARGE}
11840
11841 \newrobustcmd*{\LWR@HTML@huge}{\renewcommand*{\LWR@font@size}{\huge}}
11842 \LWR@formatted{huge}
11843
11844 \newrobustcmd*{\LWR@HTML@Huge}{\renewcommand*{\LWR@font@size}{\Huge}}
11845 \LWR@formatted{Huge}

11846 \DeclareDocumentCommand{\onecolumn}{}{ {} }
11847
11848 \DeclareDocumentCommand{\twocolumn}{O{}}{ {} }
11849
11850 #1
11851
11852 }

\hfill

11853 \newcommand*{\LWR@HTML@hfill}{\qquad}
11854 \LWR@formatted{hfill}

```

```
\hrulefill
```

```
11855 \newcommand*{\LWR@HTML@hrulefill}{\rule{1in}{1pt}}
11856 \LWR@formatted{hrulefill}
```

```
\dotfill
```

```
11857 \newcommand*{\LWR@HTML@dotfill}{\dots}
11858 \LWR@formatted{dotfill}
```

```
\newpage
```

```
11859 \renewcommand*{\newpage}{
11860
11861 }
```

\newline Uses the HTML <br /> element.

```
11862 \newrobustcmd*{\LWR@newlinebr}{\unskip\LWR@htmltag{br /}\LWR@orignewline}%
11863 \LetLtxMacro{\newline}{\LWR@newlinebr}
```

\\\ Redefined to \LWR@endofline or \LWR@tabularendofline.

```
\LWR@endofline * [<len>]
```

\\\ is assigned to \LWR@endofline at \LWR@LwarpStart.

Inside tabular, \\\ is temporarily changed to \LWR@tabularendofline.

```
11864 \LetLtxMacro{\LWR@origendofline} \\
11865 \NewDocumentCommand{\LWR@endofline}{s O{0pt}} \\
11866 {%
11867 \newline%
```

```
11868 \setlength{\LWR@templengthone}{#2}%
11869 \ifdimgreater{\LWR@templengthone}{0pt}{\newline}{}%
11870 }
```

\LWR@minipagestartpars Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a <div> to be inside a p, paragraphs must be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, lwarp correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to be on its own line. Since people often place small horizontal space between minipages, it is desirable to maintain this space if possible. lwarp tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around \hspace, \enskip, \quad, and \quadquad until the end of the paragraph, when the closing p tag is created.

When a minipage is seen, the boolean `LWR@minipagethispar` is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. `LWR@minipagethispar` is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before `\hspace`, `\quad`, or `\qquad`'s HTML output.

```
11871 \newcommand*{\LWR@minipagestartpars}{%
11872 \ifbool{LWR@minipagethispar}{\LWR@startpars}{}%
11873 }
```

`\LWR@minipagestopars` Placed just after `\hspace`, `\quad`, or `\qquad`'s HTML output.

```
11874 \newcommand*{\LWR@minipagestopars}{%
11875 \ifbool{LWR@minipagethispar}{\LWR@stopars}{}%
11876 }
```

`\quad` Handles special minipage & horizontal space interactions. Uses 2003 EM SPACE to pass validation.

```
11877 \renewrobustcmd*{\quad}{%
11878 \LWR@minipagestopars%
11879 \HTMLunicode{2003}%
11880 \LWR@minipagestartpars%
11881 }
```

`\qquad` Handles special minipage & horizontal space interactions.

```
11882 \renewrobustcmd*{\qquad}{\quad\quad}
```

`\enskip` Handles special minipage & horizontal space interactions.

```
11883 \renewrobustcmd*{\enskip}{%
11884 \LWR@minipagestopars%
11885 \HTMLunicode{2002}%
11886 \LWR@minipagestartpars%
11887 }
```

`\Len \LWR@tempwidth` Used to compute span width, height, raise for `\hspace` and `\rule`:

```
Len \LWR@tempheight 11888 \newlength{\LWR@tempwidth}
Len \LWR@tempraise 11889 \newlength{\LWR@tempheight}
11890 \newlength{\LWR@tempraise}
```

`\LWR@select@html@\hspace * {\<length>} * {\<length>}`

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

`\hspace{\fill}` is converted to `\hspace{2em}`, equal to `\qquad`.

```
11891 \newcommand{\LWR@select@html@hspace}{%
11892 \RenewDocumentCommand{\hspace}{s m}{%
11893 \setlength{\LWR@tempwidth}{##2}}%
```

If `\fill`, change to `\qquad`:

```
11894 \ifnum\gluestretchorder\LWR@tempwidth>0%
11895 \setlength{\LWR@tempwidth}{2em}%
11896 \fi%
```

Only if the width is greater than zero:

```
11897 \ifdimcomp{\LWR@tempwidth}{>}{0pt}{%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
11898 \LWR@minipagestoppars%
```

Support the HTML thin wrappable space:

```
11899 \ifdimcomp{\LWR@tempwidth}{=}{.16667em}%
11900 {%
11901 \HTMLunicode{2009}% thin breakable space
11902 }%
```

Print the span with the converted width. Not rounded.

```
11903 {%
11904 \LWR@htmtagc{%
11905 span style="width:\LWR@printlength{\LWR@tempwidth}; % extra space
11906 display:inline-block"%
11907 }%
```

If formatting for a word processor, approximate with a number of `\quads`, in case a span of a given width is not supported:

```
11908 \ifbool{FormatWP}{%
11909 \setlength{\LWR@templengthone}{\LWR@tempwidth}%
11910 \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
11911 \quad\%
11912 \addtolength{\LWR@templengthone}{-1em}%
11913 }%
11914 }%
```

If NOT formatting for a word processor, include an empty comment to avoid an empty span:

```
11915 {\LWR@htmcomment{}%
```

Close the span:

```
11916 \LWR@htmtagc{/span}%
11917 }%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
11918      \LWR@minipagestartpars%
11919 }{}% width greater than 0
11920 }%
11921 }
```

\LWR@select@html@nohspace \* {*<length>*}
\hspace
Used to disable \hspace while creating description \items.

```
11922 \newcommand{\LWR@select@html@nohspace}{%
11923     \RenewDocumentCommand{\hspace}{s m}{%
11924 }}
```

\LWR@select@print@hspace

```
11925 \newcommand*{\LWR@select@print@hspace}{%
11926     \renewrobustcmd\hspace{\@ifstar\@hspacer\@hspace}%
11927 }
```

\hspace \* {*<length>*}

Handles special minipage & horizontal space interactions.

```
11928 \LWR@select@html@hspace
```

\LWR@vspace \* {*<length>*} Nullified vspace.

```
11929 \NewDocumentCommand{\LWR@HTML@vspace}{s m}{}
11930
11931 \LWR@formatted{vspace}
```

\linebreak [*num*] Inserts an HTML br tag.

```
11932 \renewcommand*{\linebreak}[1][]{\newline}
```

\nolinebreak [*num*]

```
11933 \renewcommand*{\nolinebreak}[1][]{}
```

\pagebreak [*num*] Starts a new paragraph.

```
11934 \renewcommand*{\pagebreak}[1][]{
11935
11936 }
```

\nopagebreak [*num*]

```
11937 \renewcommand*{\nopagebreak}[1][]{}
```

```
\enlargethispage * {\len}
```

```
11938 \RenewDocumentCommand{\enlargethispage}{s m}{}{}
```

```
\clearpage  
\cleardoublepage
```

```
11939 \renewcommand*{\clearpage}{}{}
```

```
11940 \renewcommand*{\cleardoublepage}{}{}
```

```
\rule [\raise] {\width} {\height}
```

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

\fill is zero-width, so \hspace{\fill} is ignored.

```
11941 \newcommand*{\LWR@HTML@rule}[3][]{%
```

The width is copied into a temporary L<sup>A</sup>T<sub>E</sub>X length, from which comparisons and conversions may be made:

```
11942 \setlength{\LWR@tempwidth}{#2}%
```

If it's zero-width then skip the entire rule:

```
11943 \ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}%  
11944 {}% zero- width  
11945 {}% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
11946 \ifthenelse{  
11947   \lengthtest{\LWR@tempwidth>0pt}\AND%  
11948   \lengthtest{\LWR@tempwidth<1pt}%  
11949 }%  
11950   {\setlength{\LWR@tempwidth}{1pt}}%  
11951 }
```

Likewise with height:

```
11952 \setlength{\LWR@tempheight}{#3}%  
11953 \ifthenelse{  
11954   \lengthtest{\LWR@tempheight>0pt}\AND%  
11955   \lengthtest{\LWR@tempheight<1pt}%  
11956 }%  
11957   {\setlength{\LWR@tempheight}{1pt}}%  
11958 }
```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```
11959 \LWR@minipagestoppars%
```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in L<sup>A</sup>T<sub>E</sub>X code.

```
11960 \LWR@findcurrenttextcolor%
11961 \LWR@htmntagcf%
11962 span\LWR@indentHTML%
11963 style="%
```

The HTML background color is used to draw the filled rule according to the L<sup>A</sup>T<sub>E</sub>X foreground color set by \textcolor.

```
11964 \ifbool{FormatWP}{}{background:\LWR@currenttextcolor ; }%
```

The width and height are printed, converted to PT:

```
11965 width:\LWR@printlength{\LWR@tempwidth} ; %
11966 height:\LWR@printlength{\LWR@tempheight} ; %
```

The raise height is converted to a css transform. The \*2 raise multiplier is to approximately match HTML output's X height. Conversion to a L<sup>A</sup>T<sub>E</sub>X length allows a typical L<sup>A</sup>T<sub>E</sub>X expression to be used as an argument for the raise, whereas printing the raise argument directly to HTML output without conversion to a L<sup>A</sup>T<sub>E</sub>X length limits the allowable syntax. To do: A superior method would compute a ratio of L<sup>A</sup>T<sub>E</sub>X ex height, then print that to HTML with an ex unit.

```
11967 \ifblank{#1}%
11968 {}%
11969 {%
11970 \setlength{\LWR@tempraise}{0pt-#1}%
11971 \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
11972 \LWR@indentHTML%
11973 -ms-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
11974 \LWR@indentHTML%
11975 -webkit-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
11976 \LWR@indentHTML%
11977 transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
11978 \LWR@indentHTML%
11979 }%
```

Display inline-block to place the span inline with the text:

```
11980 display:inline-block;"\LWR@orignewline%
11981 }%
```

If formatting for a word processor, approximate with a number of underscores, in case a span of a given width is not supported:

```
11982 \ifbool{FormatWP}{%
11983 \setlength{\LWR@templengthone}{\LWR@tempwidth}%
11984 \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
11985 \_{}%}
```

---

```

11986           \addtolength{\LWR@templengthone}{-1em}%
11987           }%
11988       }%

```

If NOT formatting for a word processor, add a comment to avoid an empty <span>:

```

11989     {\LWR@htmlcomment{}}

```

Close the span:

```

11990     \LWR@htmlltagc{/span}%

```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```

11991     \LWR@minipagestartpars%
11992 }% non-zero width
11993 }
11994
11995 \LWR@formatted{rule}

11996 \end{warpHTML}

```

## 92 \phantomsection

**for HTML output:** 11997 \begin{warpHTML}

\phantomsection Emulate the hyperref \phantomsection command, often used to insert the bibliography into the table of contents. Ignores \ForceHTMLTOC.

```

11998 \DeclareDocumentCommand{\phantomsection}{}{%
11999 \begingroup%
12000 \boolfalse{\LWR@forcinghtmltoc}%
12001 \section*{}%
12002 \endgroup%
12003 }

12004 \end{warpHTML}

```

## 93 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally set by \LWR@formatted.

For css conversions, see:

<http://edward.oconnor.cx/2007/08/tex-poshlet>

<http://nitens.org/taraborelli/texlogo>

and the spacing described in the `metafont` package documentation.

```
for HTML & PRINT: 12005 \begin{warpall}
12006 \newrobustcmd*\{\Xe}
12007 {X\hspace{-.1667em}\raisebox{-.5ex}{E}}
12008
12009 \AtBeginDocument{
12010 \@ifpackageloaded{graphics}{
12011   \@ifpackageloaded{metalogo}{}{
12012     \renewrobustcmd*\{\Xe}
12013     {X\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}}}
12014   }
12015 }{
12016   \PackageWarningNoLine{lwarp}{Load graphicx or graphics
12017   for improved XeTeX logo}
12018 }
12019 }
12020
12021 \providerobustcmd*\{\XeTeX\}{\mbox{\Xe\hspace{-.125em}\TeX}}
12022 \providerobustcmd*\{\XeLaTeX\}{\mbox{\Xe\hspace{-.125em}\LaTeX}}
12023 \providerobustcmd*\{\AMs\}{%
12024   \leavevmode\hbox{$\mathcal A$\kern-.2em\lower.376ex%
12025   \hbox{$\mathcal M$}\kern-.2em$\mathcal S$}%
12026 }
12027 \newrobustcmd*\{\LyX\}{\textsf{LyX}}
12028 \providerobustcmd*\{\LuaTeX\}{\mbox{\Lua\TeX}}
12029 \providerobustcmd*\{\LuaLaTeX\}{\mbox{\Lua\LaTeX}}
12030 \providerobustcmd*\{\BibTeX\}{\mbox{B\textsc{it}\TeX}}
12031 \providerobustcmd*\{\MakeIndex\}{\mbox{\textit{\MakeIndex}}}
12032 \providerobustcmd*\{\ConTeXt\}{\mbox{\ConTeXt{}t}}
12033 \providerobustcmd*\{\MiKTeX\}{\mbox{\MiK\TeX}}
12034 \end{warpall}

for HTML output: 12035 \begin{warpHTML}
```

The print-mode versions of the following may be changed by `metalogo`, so their print formatting is recorded `\AtBeginDocument`.

\TeX \TeX

`latexlogo` is a css class used to properly typeset the E and A in L<sup>A</sup>T<sub>E</sub>X and friends.

`latexlogofont` is a css class used to select the font for the rest of the logo in L<sup>A</sup>T<sub>E</sub>X, LuaTeX, ConTeXt, etc.

```
12036 \newrobustcmd*\{\LWR@HTML@TeX\}
12037 {%
12038   \InLineClass{latexlogofont}%
12039   {%
12040     \InLineClass{latexlogo}%
12041     {%
12042       T%
```

```
12043          \InlineClass{latexlogosub}{e}%
12044          X%
12045      }%
12046  }%
12047 }
12048 \AtBeginDocument{\LWR@formatted{TeX}}% may have been patched by metalogo

\LaTeX \LATEX, \LATEX2\varepsilon
\LaTeXe
12049 \newrobustcmd*\LWR@HTML@LaTeX}
12050 {%
12051     \InlineClass{latexlogofont}%
12052     {%
12053         \InlineClass{latexlogo}%
12054         {%
12055             L%
12056             \InlineClass{latexlogosup}{a}%
12057             T%
12058             \InlineClass{latexlogosub}{e}%
12059             X%
12060         }%
12061     }%
12062 }
12063
12064 \AtBeginDocument{\LWR@formatted{LaTeX}}% may have been patched by metalogo
12065
12066
12067 \newrobustcmd*\LWR@HTML@LaTeXe}
12068 {%
12069     \LaTeX%
12070     \InlineClass{latexlogofont}{%
12071         \InlineClass{latexlogotwoe}{%
12072             2%
12073             \InlineClass{latexlogotwoesub}{\HTMLunicode{03B5}}%
12074         }%
12075     }%
12076 }
12077 \AtBeginDocument{\LWR@formatted{LaTeXe}}% may have been patched by metalogo

\LuaTeX \LuaTeX, \LuaLATEX
\LuaLaTeX
12078 \newrobustcmd*\LWR@HTML@LuaTeX}{\InlineClass{latexlogofont}{Lua}\TeX}
12079 \AtBeginDocument{\LWR@formatted{LuaTeX}}% may have been patched by metalogo
12080
12081 \newrobustcmd*\LWR@HTML@LuaLaTeX}{\InlineClass{latexlogofont}{Lua}\LaTeX}
12082 \AtBeginDocument{\LWR@formatted{LuaLaTeX}}% may have been patched by metalogo

\xetex \XETEX, \XELATEX
\xelatex
xetexlogo is a css class which aligns the backwards E in \XETEX and spaces \TeX appropriately.
```

`xelatexlogo` is a css class which aligns the backwards E in X<sub>E</sub>LATEX and spaces LATEX appropriately.

```

12083 \newrobustcmd*{\LWR@HTML@Xe}{%
12084     {%
12085         X%
12086         \InlineClass{xelatexlogosub}{\HTMLunicode{18e}}%
12087     }%
12088 \AtBeginDocument{\LWR@formatted{Xe}}% may have been patched by metalogo
12089
12090 \newrobustcmd*{\LWR@HTML@XeTeX}{\InlineClass{xelatexlogo}{\Xe}\TeX}%
12091 \AtBeginDocument{\LWR@formatted{XeTeX}}% may have been patched by metalogo
12092
12093 \newrobustcmd*{\LWR@HTML@XeLaTeX}{\InlineClass{xelatexlogo}{\Xe}\LaTeX}%
12094 \AtBeginDocument{\LWR@formatted{XeLaTeX}}% may have been patched by metalogo

```

### \ConTeXt ConTeXt

```

12095 \newrobustcmd*{\LWR@HTML@ConTeXt}{%
12096     \InlineClass{latexlogofont}{Con}\TeX{}%
12097     \InlineClass{latexlogofont}{t}%
12098 }%
12099 \LWR@formatted{ConTeXt}

```

```

\BibTeX BIBTeX, MakeIndex
\MakeIndex
12100 \newrobustcmd*{\LWR@HTML@BibTeX}{%
12101     {\InlineClass{latexlogofont}{B}\textsc{ib}}\TeX}%
12102 \LWR@formatted{BibTeX}
12103
12104 \newrobustcmd*{\LWR@HTML@MakeIndex}{%
12105     {\InlineClass{latexlogofont}{\textit{MakeIndex}}}%
12106 \LWR@formatted{MakeIndex}

```

### \AmS \mathcal{A}\mathcal{M}\mathcal{S}

`amslogo` is a css class used for the  $\mathcal{A}\mathcal{M}\mathcal{S}$  logo.

```

12107 \AtBeginDocument{%
12108 \newrobustcmd*{\LWR@HTML@AmS}{%
12109 {%
12110     \InlineClass{amslogo}{%
12111         \textit{%
12112             A%
12113             \InlineClass{latexlogosub}{M}%
12114             S%
12115         }%
12116     }%
12117 }%
12118 \LWR@formatted{AmS}
12119 }

```

\MiKTeX MiKTeX

```
12120 \newrobustcmd*{\LWR@HTML@MiKTeX}{\InlineClass{latexlogofont}{MiK}\TeX}
12121 \LWR@formatted{MiKTeX}
```

\LyX LyX

lyxlogo is a css class used for the LyX logo.

```
12122 \newrobustcmd*{\LWR@HTML@LyX}{\InlineClass{lyxlogo}{LyX}}
12123 \LWR@formatted{LyX}
```

```
12124 \end{warpHTML}
```

## 94 \AtBeginDocument, \AtEndDocument

**for HTML output:** 12125 \begin{warpHTML}

\LWR@LwarpStart Automatically sets up the HTML-related actions for the start and end of the document.  
\LWR@LwarpEnd

```
12126 \AfterEndPreamble{\LWR@LwarpStart}
12127 \AtEndDocument{\LWR@LwarpEnd}
```

```
12128 \end{warpHTML}
```

## 95 Loading KOMA-SCRIPT class patches

Load patches to koma-script.

**for HTML output:** 12129 \begin{warpHTML}

```
12130 \@ifclassloaded{scrbook}{\RequirePackage{lwarp-patch-komascript}}{}
12131 \@ifclassloaded{scratcl}{\RequirePackage{lwarp-patch-komascript}}{}
12132 \@ifclassloaded{scrreprt}{\RequirePackage{lwarp-patch-komascript}}{}

12133 \end{warpHTML}
```

## 96 Loading MEMOIR class patches

Load patches to memoir.

**for HTML output:** 12134 \begin{warpHTML}

```
12135 \@ifclassloaded{memoir}{\RequirePackage{lwarp-patch-memoir}}{}

12136 \end{warpHTML}
```

## 97 ut\* class patches

Load patches to `uj*` and `ut*` classes, as well as `lj*` classes.

**for HTML output:** 12137 `\begin{warpHTML}`

```
12138 \newcommand*\LWR@patchujtclasses{  
  
    uj/t does not use \partname  
  
    12139     \def\@partnameformat{}  
  
    12140     \def\@partcntformat##1{  
    12141         \prepartname%  
    12142         \csname the##1\endcsname%  
    12143         \postpartname%  
    12144         \quad%  
    12145     }  
    12146     \@ifundefined{chapter}{}{  
    12147         \def\@chapcntformat##1{  
    12148             \prechaptername%  
    12149             \csname the##1\endcsname%  
    12150             \postchaptername%  
    12151             \quad%  
    12152     }  
    12153 }
```

Use decimal points instead of centered dots:

```
12154     \renewcommand{\thepart}{\@Roman\c@part}  
12155     \@ifundefined{chapter}{  
12156         \renewcommand{\thesection}{\@arabic\c@section}  
12157     }{  
12158         \renewcommand{\thechapter}{\@arabic\c@chapter}  
12159         \renewcommand{\thesection}{\thechapter.\@arabic\c@section}  
12160     }  
12161     \renewcommand{\thesubsection}{\thesection.\@arabic\c@subsection}  
12162     \renewcommand{\thesubsubsection}{  
12163         \thesubsection.\@arabic\c@subsubsection}  
12164     \renewcommand{\theparagraph}{  
12165         \thesubsubsection.\@arabic\c@paragraph}  
12166     \renewcommand{\thesubparagraph}{  
12167         \theparagraph.\@arabic\c@subparagraph}  
12168     \@ifundefined{chapter}{  
12169         \renewcommand{\thefigure}{\@arabic\c@figure}  
12170         \renewcommand{\thetable}{\@arabic\c@table}  
12171     }{  
12172         \renewcommand{\thefigure}{%  
12173             \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@figure}  
12174         \renewcommand{\thetable}{%  
12175             \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@table}  
12176     }  
12177 }
```

```

12178
12179 \@ifclassloaded{ujarticle}{\LWR@patchujtclasses}{}%
12180 \@ifclassloaded{ujbook}{\LWR@patchujtclasses}{}%
12181 \@ifclassloaded{ujreport}{\LWR@patchujtclasses}{}%
12182 \@ifclassloaded{utarticle}{\LWR@patchujtclasses}{}%
12183 \@ifclassloaded{utbook}{\LWR@patchujtclasses}{}%
12184 \@ifclassloaded{utreport}{\LWR@patchujtclasses}{}%
12185 \@ifclassloaded{ltjarticle}{\LWR@patchujtclasses}{}%
12186 \@ifclassloaded{ltjbook}{\LWR@patchujtclasses}{}%
12187 \@ifclassloaded{ltjreport}{\LWR@patchujtclasses}{}%
12188 \@ifclassloaded{ltjsarticle}{\LWR@patchujtclasses}{}%
12189 \@ifclassloaded{ltjsbook}{\LWR@patchujtclasses}{}%
12190 \@ifclassloaded{ltjsreport}{\LWR@patchujtclasses}{}%
12191 \@ifclassloaded{ltjskiyou}{\LWR@patchujtclasses}{}%
12192 \@ifclassloaded{ltjspf}{\LWR@patchujtclasses}{}%
12193 \@ifclassloaded{ltjtarticle}{\LWR@patchujtclasses}{}%
12194 \@ifclassloaded{ltjtbook}{\LWR@patchujtclasses}{}%
12195 \@ifclassloaded{ltjtreport}{\LWR@patchujtclasses}{}%

12196 \end{warpHTML}

```

## 98 CTEX patches

Patches for ctex and related classes, which are loaded before lwarp.

All CTEX classes and the ctex package seem to load ctexpatch, so its presence is used to decide whether to have lwarp patch CTEX.

**for HTML output:** 12197 \begin{warpHTML}

\AtBeginDocument in case the user set FileSectionNames in the preamble.

```

12198 \AtBeginDocument{%
12199     \@ifpackageloaded{ctexpatch}{%
12200         \def\@partcntformat#1{%
12201             \LWR@isolate{\CTEX@partname}~%
12202             \CTEX@part@aftername%
12203         }%
12204     \def\@partnameformat{}%
12205     \def\@chapcntformat#1{%
12206         \def\@chapcntformat#1{%
12207             \LWR@isolate{\CTEX@chaptername}~%
12208             \CTEX@chapter@aftername%
12209         }%
12210     }%
12211 }%
12212 }

12213 \end{warpHTML}

```

## 99 kotexutf patches

Patch for `kotexutf`, which is loaded before `l warp`.

`kotexutf`'s `\@setref` was conflicting with `l warp`'s cross references.

**for HTML output:** 12214 `\begin{warpHTML}`

If `kotexutf`'s version of `\@setref` is detected, it is reverted to the original.

```

12215 \AtBeginDocument{
12216 \@ifpackageloaded{kotexutf}){
12217     \def\LWR@kotexutf@setref#1#2#3{%
12218         \@setref@dhucs@orig{#1}{#2}{#3}%
12219         \ifx#1\relax\else
12220             \bgroup
12221             \dhucs@make@cjckchar@null
12222             \edef@\temp{\expandafter#2#1}\global\josatoks\expandafter{\@temp}%
12223             \egroup
12224         \fi%
12225     }%
12226
12227     \ifdefequal{\@setref}{\LWR@kotexutf@setref}{
12228         \let\@setref\@setref@dhucs@orig
12229     }{}%
12230 }{}%
12231 }

12232 \end{warpHTML}

```

## 100 babel and polyglossia warnings

`l warp` prints a message instructing the user how to avoid the following error.

(These are not `\PackageWarnings` because there may not be a problem.)

`l warp` uses `cleveref`, which has some limitations when using `polyglossia`, possibly resulting in the error

```
! Undefined control sequence. . . . \begindocumenthook
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by `cleveref`, then select other languages using `\setotherlanguages`.

Once the print version works with `\cleveref` and `\polyglossia`, the HTML version should work as well using `\lwarp`.

```
for HTML output: 12233 \begin{warpHTML}
12234 \AtBeginDocument{
12235
12236 \@ifpackageloaded{polyglossia}{
12237     \PackageWarningNoLine{\lwarp}
12238     {%
12239         Polyglossia has been loaded. Lwarp also uses \cleveref.\MessageBreak
12240         See the \cleveref documentation regarding\MessageBreak
12241         polyglossia support. Some languages are not supported%
12242     }
12243     \typeout{---}
12244     \typeout{Package \lwarp:}
12245     \typeout{If the error}
12246     \typeout{\space\space'! Undefined control sequence.
12247             \space ... \space \protect\@begindocumenthook'}
12248     \typeout{occurs here, use the polyglossia macro:}
12249     \typeout{\space\space\protect\setmainlanguage\protect{...}\protect}}
12250     \typeout{---}
12251 }%
12252 \@ifpackageloaded{babel}%
12253     \PackageWarningNoLine{\lwarp}
12254     {%
12255         Babel has been loaded. Lwarp also uses \cleveref.\MessageBreak
12256         See the \cleveref documentation regarding\MessageBreak
12257         babel support. Some languages are not supported%
12258     }
12259 }{}%
12260 }
12261
12262 }
12263 \end{warpHTML}
```

## 101 MATHJAX warnings

```
\LWR@mathjaxwarn {\langle packagename\rangle} {\langle More text.\rangle}
```

To be done `\AtBeginDocument`.

```
12264 \newcommand*{\LWR@mathjaxwarn}[2]{%
12265     \@ifpackageloaded{\lwarp-\#1}{%
12266         \ifblank{\#2}{%
12267             \PackageWarningNoLine{\lwarp}
12268             {%
12269                 Lwarp provides emulation for MathJax when used\MessageBreak
12270                 with the \#1 package%
12271             }
12272         }{%
12273             \PackageWarningNoLine{\lwarp}
12274             {%
12275                 Lwarp provides emulation for MathJax when used\MessageBreak
12276             }
12277         }
12278     }
12279 }
```

```
12276           with the #1 package.\MessageBreak
12277           #2%
12278       }
12279   }%
12280 {}%
12281 }
12282
12283 \AtBeginDocument{
12284     \ifbool{mathjax}{
12285         \LWR@mathjaxwarn{arydshln}
12286             {In a math array, do not use the optional argument\MessageBreak
12287             for \protect\cdashline.\space\space
12288             Furthermore, \protect\cline\space is not\MessageBreak
12289             supported by MathJax}
12290         \LWR@mathjaxwarn{autonum}
12291             {MathJax does not support equation+.\MessageBreak
12292             You may use the warpprint and warpHTML\MessageBreak
12293             environments to isolate the package load\MessageBreak
12294             and the equation+ environments}
12295         \LWR@mathjaxwarn{backnaur}
12296             {You may enclose its uses inside\MessageBreak
12297             lateximage environments to force SVG output,\MessageBreak
12298             but this also changes the print output}
12299         \LWR@mathjaxwarn{bigdelim}
12300             {Delimiters appear only of the first line}
12301         \LWR@mathjaxwarn{booktabs}
12302             {In a math array, do not use (trim) for \protect\cmidrule}
12303         \LWR@mathjaxwarn{breqn}
12304             {Each environment becomes an SVG image}
12305         \LWR@mathjaxwarn{delarray}
12306             {Enclose its uses inside lateximage\MessageBreak
12307             environments to force SVG output}
12308         \LWR@mathjaxwarn{jkmath}{}
12309         \LWR@mathjaxwarn{mathspec}{}
12310         \LWR@mathjaxwarn{mathtools}
12311             {Avoid starred macros.\MessageBreak
12312             See the Lwarp manual for other limitations}
12313         \LWR@mathjaxwarn{multirow}
12314             {Multirow works as expected in text mode, but\MessageBreak
12315             limited emulation is provided for MathJax math.\MessageBreak
12316             \protect\multirow\space ignores all arguments except\MessageBreak
12317             the text}
12318         \LWR@mathjaxwarn{pb-diagram}
12319             {Enclose its uses inside lateximage environments\MessageBreak
12320             to force SVG output}
12321         \LWR@mathjaxwarn{physics}
12322             {The third-party extension is not yet used.\MessageBreak
12323             Avoid starred macros and automatic delimiters.\MessageBreak
12324             Use all mandatory arguments, adding empty as needed.\MessageBreak
12325             See the Lwarp manual for details}
12326         \LWR@mathjaxwarn{unicode-math}
12327             {Not all characters are encoded correctly.\MessageBreak
12328             Some symbol fonts are not supported by MathJax,\MessageBreak
12329             and are only approximated}
12330         \LWR@mathjaxwarn{witharrows}
```

```
12331 {Arrows can only point to the next line.\MessageBreak
12332   Text is only placed on a single line}
12333 \LWR@mathjaxwarn{xy}
12334   {xy works in text, but in math you must\MessageBreak
12335     enclose its uses inside lateximage\MessageBreak
12336     environments to force SVG output}
12337 }()
12338 }
```

---

**File 2 l warp-2in1.sty**

§ 102      Package    **2in1**

Pkg 2in1 2in1 is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{2in1}

---

**File 3 l warp-2up.sty**

§ 103      Package    **2up**

Pkg 2up 2up is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{2up}[2010/05/15]

```
2 \def\source#1#2#3{}  
3 \def\target#1#2#3{}  
4 \def\targetlayout#1{}  
5 \newdimen\pageseplength  
6 \newdimen\pagesepwidth  
7 \newdimen\pagesepoffset  
8 \def\twoupemptypage{}  
9 \def\twoupclearpage{}  
10 \def\twoupeject{}  
11 \def\twouparticle{}  
12 \def\twoupplain{}  
13 \def\twouplegaltarget{}  
14 \def\twouplandscape{}  
15 \def\TwoupWrites{}
```

---

**File 4 l warp-a4.sty**

§ 104      Package    **a4**

Pkg a4 a4 is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{a4}[2004/04/15]

```
2 \newcommand*\WideMargins{}
```

---

**File 5 l warp-a4wide.sty****§ 105 Package a4wide**

Pkg a4wide a4wide is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{a4wide}[1994/08/30]

---

**File 6 l warp-a5comb.sty****§ 106 Package a5comb**

Pkg a5comb a5comb is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{a5comb}

---

**File 7 l warp-abstract.sty****§ 107 Package abstract**

(Emulates or patches code by PETER WILSON.)

Pkg abstract abstract is supported and patched by l warp.

⚠ **missing TOC** If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

**for HTML output:** memoir provides an abstract environment even though it is not an article or report class. Meanwhile, l warp loads book to emulate memoir, but book does not have an abstract environment, so when the abstract package is loaded for emulation there is no pre-existing abstract to redefine, which would cause an error. Thus, a null abstract is provide here:

1 \ProvideDocumentEnvironment{abstract}{}{}

Accept all options for l warp-abstract:

2 \LWR@ProvidesPackagePass{abstract}[2009/06/08]

3 \AtBeginDocument{  
4 \BeforeBeginEnvironment{abstract}{  
5 \LWR@forcenewpage  
6 \BlockClass{abstract}  
7 }

```
8 \AfterEndEnvironment{abstract}{\endBlockClass}
9 }
10
11 \renewcommand{\@bsruntitl}{%
12 \hspace*{\abstitleskip}%
13 {\abstractnamefont%
14 \InlineClass{abstractrunintitle}{\abstractname}%
15 \@bslabeldelim}%
16 }
17
18 \@ifclassloaded{memoir}
19 {
20   \renewenvironment{abstract}{%
21 %     \titlepage
22   \null\vfil
23   \begin{par} \lowpenalty
24   \if@bsrunin
25   \else
26     \if@bsstyle
27       \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}%
28     \else
29       \ifnumber@bs
30         \num@bs
31       \else
32         \begin{\absnamepos}%
33         \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}%
34         \end{par} \lowpenalty\@M
35         \end{\absnamepos}%
36 %       \vspace{\abstitleskip}%
37       \fi
38       \fi
39       \vspace{\abstitleskip}%
40     \fi
41   \put@bsintoc%
42   \begin{\bstr@ctlist}\if@bsrunin\@bsruntitl\fi\abstracttextfont}%
43   {\par\end{\bstr@ctlist}\vfil\null%\endtitlepage
44 }
45 }{%
46 \if@titlepage
47   \renewenvironment{abstract}{%
48 %     \titlepage
49   \null\vfil
50   \begin{par} \lowpenalty
51   \if@bsrunin
52   \else
53     \if@bsstyle
54       \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}%
55     \else
56       \ifnumber@bs
57         \num@bs
58       \else
59         \begin{\absnamepos}%
60         \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}%
61         \end{par} \lowpenalty\@M
62         \end{\absnamepos}%
63 }
```

```

63 %      \vspace{\abstitleskip}%
64      \fi
65      \fi
66      \vspace{\abstitleskip}%
67 \fi
68 \put@bsintoc%
69 \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
70 {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
71 }
72 \else
73 \renewenvironment{abstract}{%
74 \if@bsrunin
75 \else
76 \if@bststyle
77 \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}%
78 \else
79 \ifnumber@bs
80 \num@bs
81 \else
82 \begin{\absnamepos}%
83 \abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
84 \end\absnamepos%
85 %      \vspace{\abstitleskip}%
86      \fi
87      \fi
88      \vspace{\abstitleskip}%
89 \fi
90 \put@bsintoc%
91 \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
92 {\par\end{@bstr@ctlist}}
93 \fi
94 }% not memoir

```

#### File 8 l warp-academicons.sty

### § 108 Package **academicons**

(Emulates or patches code by DIOGO A. B. FERNANDES.)

Pkg academicons academicons is patched for use by l warp.

If \aiicon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

**for HTML output:** 1 \LWR@ProvidesPackagePass{academicons}[2018/06/27]

```

2 \LetLtxMacro{\LWR@orig@symbol}{\symbol}
3
4 \let\LWR@academicons@orig@AI\AI
5
6 \newcommand*{\LWR@academicons@symbol}[1]{%
7   \begin{latentimage}*[academicon][academicons#1]%
8     \begingroup%

```

---

```

9      \LWR@academicons@orig@AI%
10     \LWR@orig@symbol{\#1}%
11     \endgroup%
12     \end{lateximage}%
13 }
14
15 \renewcommand*\{AI}{%
16     \LetLtxMacro\symbol\LWR@academicons@symbol%
17 }
18
19 \renewcommand*\{aiicon}[1]
20 {%
21     \begin{lateximage}*[#1 icon][academicons#1]%
22     \AI\csname aiicon@\#1\endcsname%
23     \end{lateximage}%
24 }

```

---

### File 9 **l warp-afterpage.sty**

#### § 109 Package **afterpage**

*(Emulates or patches code by DAVID CARLISLE.)*

Pkg **afterpage** **afterpage** is emulated.

**for HTML output:** Discard all options for **l warp-afterpage**:

```

1 \LWR@ProvidesPackageDrop{afterpage}[2014/10/28]

2 \newcommand{\afterpage}[1]{#1}

```

---

### File 10 **l warp-accessibility.sty**

#### § 110 Package **accessibility**

Pkg **accessibility** **accessibility** is emulated.

**for HTML output:** Discard all options for **l warp-accessibility**:

```

1 \LWR@ProvidesPackageDrop{accessibility}[2019/10/14]

2 \newcommand{\alt}[1]{\ThisAltText{\#1}}
3 \newcommand{\newhref}[3]{\ThisAltText{\#2}\href{\#1}{\#3}}%
4 \providecommand{\thead}[1]{\textbf{\#1}}

```

For MATHJAX:

```

5 \begin{warpMathJax}
6 \CustomizeMathJax{\newcommand{\alt}[1]{}}

```

---

```

7 \CustomizeMathJax{\newcommand{\thead}[1]{\text{\textbf{#1}}}}
8 \end{warpMathJax}

```

---

File 11 **l warp-accsupp.sty**

§ 111 Package **accsupp**

Pkg accsupp accsupp is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{accsupp}[2018/03/28]

```

2 \newcommand*\{ \BeginAccSupp}[1] {}
3 \newcommand*\{ \EndAccSupp}[1] {}

```

---

File 12 **l warp-acro.sty**

§ 112 Package **acro**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg acro acro is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{acro}[2019/10/12]

\DeclareAcronym is used in the preamble, where l warp has not yet made the dollar active, so temporarily enable l warp math catcode just for this definition:

```

2 \ExplSyntaxOn
3 \NewDocumentCommand \LWR@DeclareAcronym {mm}
4 {
5     \acro_declare_acronym:nn {#1} {#2}
6     \catcode`\$=3% l warp
7 }
8 \ExplSyntaxOff
9
10 \RenewDocumentCommand{\DeclareAcronym}{}{
11     \catcode`\$=\active% l warp
12     \LWR@DeclareAcronym
13 }

```

Modified to activate the current font:

```

14 \ExplSyntaxOn
15 \@ifpackagelater{acro}{2019/09/23}%
16 {% v2.10 or later
17 \cs_gset_protected:Npn \__acro_typeset:nn #1#2
18 {
19     \mode_if_horizontal:F { \leavevmode }
20     \group_begin:

```

```
21      \use:x
22      {
23          \bool_if:cTF {\l__acro_custom_#1_format_bool}
24              { \exp_not:v {\l__acro_custom_#1_format_tl} }
25              { \exp_not:v {\l__acro_#1_format_tl} }
26              {\exp_not:N\lWR@textcurrentfont{#2}}% lwarp
27      }
28      \group_end:
29  }
30
31 \cs_gset_protected:Npn \__acro_ending_format:nn #1#2
32 {
33     \bool_if:NTF \l__acro_include_endings_format_bool
34     {
35         \str_case:nn {#1}
36         {
37             {long}
38             {
39                 \bool_if:NTF \l__acro_custom_long_format_bool
40                     { \l__acro_custom_long_format_tl }
41                     {
42                         \bool_if:NTF \l__acro_first_instance_bool
43                             { \l__acro_first_long_format_tl }
44                             { \l__acro_long_format_tl }
45                     }
46                 }
47             {short}
48             {
49                 \bool_if:NTF \l__acro_custom_short_format_bool
50                     { \l__acro_custom_short_format_tl }
51                     { \l__acro_short_format_tl }
52             }
53             {alt}
54             {
55                 \bool_if:NTF \l__acro_custom_alt_format_bool
56                     { \l__acro_custom_alt_format_tl }
57                     { \l__acro_alt_format_tl }
58             }
59         }
60     }
61     { \use:n }
62     {\exp_not:N\lWR@textcurrentfont{#2}}% lwarp
63 }
64 }% v2.10 or later
65 {% before v2.10
66 \cs_gset_protected:Npn \acro_write_short:nn #1#2
67 {
68     \mode_if_horizontal:F { \leavevmode }
69     \group_begin:
70         \bool_if:NTF \l__acro_custom_format_bool
71             { \l__acro_custom_format_tl }
72             { \l__acro_short_format_tl }
73             {\lWR@textcurrentfont{#2}}% lwarp
74     \group_end:
75 }
```

```

76
77 \cs_gset_protected:Npn \acro_write_alt:nn #1#2
78 {
79     \mode_if_horizontal:F { \leavevmode }
80     \group_begin:
81         \bool_if:NTF \l__acro_custom_format_bool
82             { \l__acro_custom_format_tl }
83             { \l__acro_alt_format_tl }
84             {\LWR@textcurrentfont{#2}}% l warp
85     \group_end:
86 }
87
88 \cs_gset_protected:Npn \acro_write_long:nn #1#2
89 {
90     \mode_if_horizontal:F { \leavevmode }
91     \group_begin:
92         \bool_if:NTF \l__acro_custom_long_format_bool
93             { \l__acro_custom_long_format_tl }
94             { \use:n }
95     {
96         \use:x
97         {
98             \exp_not:n {#1}
99             {
100                 \bool_if:NTF \l__acro_first_upper_bool
101                     { \exp_not:N \__acro_first_upper_case:n { \exp_not:n {
102                         \LWR@textcurrentfont{#2}}% l warp
103                     } } }
104                     { \exp_not:n { \LWR@textcurrentfont{#2} } }% l warp
105             }
106         }
107     }
108     \group_end:
109 }
110 }% before v2.10
111 \ExplSyntaxOff

```

### File 13 **l warp-acronym.sty**

§ 113 Package **acronym**

*(Emulates or patches code by TOBIAS OETIKER.)*

Pkg acronym acronym is patched for use by l warp.

⚠ multiply-defined labels \acresetall does not work with cleveref, causing multiply-defined labels. l warp patches acronym for HTML, but not for print mode.

for HTML output: 1 \LWR@ProvidesPackagePass{acronym}[2015/03/21]

Uses \textit instead of \itshape:

2 \renewcommand{\acfia}[1]{%

---

```
3 { \textit{\AC@acl{#1}} } (\ifAC@starred\acs*{#1}\else\acs{#1}\fi)}
```

Removes the `mbox` to allow math inside:

```
4 \renewcommand*\AC@acs[1]{%
5 %       \mbox{%
6 \expandafter\AC@get\csname fn@\#1\endcsname\@firstoftwo{#1}%
7 }}
```

Fix for acronym labels in the captions of floats.

```
8 \renewcommand{@starttoc}[1]{
9 \LWR@htmlelementclass{nav}{#1}
10 \LetLtxMacro{\verridelabel}{\gobble}
11 \LWR@orig@starttoc{#1}
12 \LWR@htmlelementclassend{nav}{#1}
13 }
```

Modified for `cleveref` and `lwarp`:

```
14 \renewcommand*\AC@und@newl@bel[3]{%
15     \@ifundefined{#1@#3}%
16     {%
17         \global\expandafter\let\csname#2@#3\endcsname\@nnil
18         \global\expandafter\let\csname#2@#3@lwarp\endcsname\@nnil% lwarp
19         \global\expandafter\let\csname#2@#3@cref\endcsname\@nnil% lwarp
20     }%
21     {%
22         \global\expandafter\let\csname#1@#3\endcsname\relax
23         \global\expandafter\let\csname#1@#3@lwarp\endcsname\relax% lwarp
24         \global\expandafter\let\csname#1@#3@cref\endcsname\relax% lwarp
25     }%
26 }%
```

---

#### File 14 **lwarp-adjmulticol.sty**

## § 114 Package **adjmulticol**

(Emulates or patches code by BORIS VEYTSMAN.)

Pkg **adjmulticol** **adjmulticol** is emulated.

Emulation similar to `multicols` is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, `lwarp` allows a variable number of columns up to three.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{adjmulticol}[2012/01/20]

```
2 \RequirePackage{multicol}
```

```
adjmulticols * {\langle numcols \rangle} {\langle left margin \rangle} {\langle right margin \rangle}
```

---

```

3 \NewDocumentEnvironment{adjmulticols}{s m m m}
4 {%

```

Compute the margins, and limit to positive only:

```

5 \setlength{\LWR@templengthone}{#3}%
6 \ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{}%
7 \setlength{\LWR@templengthtwo}{#4}%
8 \ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{}%

```

If one column is specified, use a <div> of class `singlecolumn`, else use `multicols`:

```

9 \newcommand*{\LWR@mcoltype}{multicols}%
10 \ifnumcomp{#2}{=}{1}{\renewcommand*{\LWR@mcoltype}{singlecolumn}}{}%

```

Help avoid page overflow:

```
11 \LWR@forcenewpage%
```

Create the <div> with the given margin and class:

```

12 \BlockClass[%]
13 \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
14 \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%
15 ]{\LWR@mcoltype}%
16 }
17 {\endBlockClass}

```

---

## File 15 lwarp-addlines.sty

### § 115 Package **addlines**

*(Emulates or patches code by WILL ROBERTSON.)*

Pkg **addlines** **addlines** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{addlines}[2018/12/05]

```

2 \newcommand\addlines{@ifstar\addlines@a\addlines@a}%
3 \newcommand\addlines@a[1][1]{}%
4 \let\addline\addlines
5 \newcommand\removelines{@ifstar\removelines@a\removelines@a}%
6 \newcommand\removelines@a[1][1]{}%
7 \let\removeline\removelines
8 \newcommand\squeeze[1][0]{}%

```

---

**File 16 l warp-afterpage.sty****§ 116 Package afterpage**

(Emulates or patches code by DAVID CARLISLE.)

Pkg afterpage afterpage is emulated.

**for HTML output:** Discard all options for l warp-afterpage:

```
1 \LWR@ProvidesPackageDrop{afterpage}[2014/10/28]  
2 \newcommand{\afterpage}[1]{#1}
```

---

**File 17 l warp-algorithm2e.sty****§ 117 Package algorithm2e**

(Emulates or patches code by CHRISTOPHE FIORIO.)

Pkg algorithm2e algorithm2e is patched for use by l warp.

For print output, captions are placed according to package options, but for HTML output captions are placed where used. Therefore, to have captions appear at the top of the algorithms for both print and HTML, place each captions at the top of each algorithm.

**for HTML output:** 1 \LWR@ProvidesPackagePass{algorithm2e}[2017/07/18]

For the list-of entries:

```
2 \renewcommand{\l@algocf}[2]{\hypertocfloat{1}{\algocf}{\loa}{#1}{#2}}
```

Select the l warp float style according to the algorithm2e style:

```
3 \newcommand*{\LWR@floatstyle@algocf}{ruled}  
4  
5 \ifdefstring{\algocf@style}{boxed}{%  
6 \renewcommand*{\LWR@floatstyle@algocf}{boxed}  
7 }{}  
8  
9 \ifdefstring{\algocf@style}{boxruled}{%  
10 \renewcommand*{\LWR@floatstyle@algocf}{boxruled}  
11 }{}  
12  
13 \ifdefstring{\algocf@style}{plain}{%  
14 \renewcommand*{\LWR@floatstyle@algocf}{plain}  
15 }{}}
```

Paragraph handling to allow line numbers under certain conditions:

```

16 \newbool{LWR@algocf@dopars}
17 \booltrue{LWR@algocf@dopars}
18
19 \renewcommand{\algocf@everypar}{%
20 \ifbool{LWR@algocf@dopars}{%
21   \ifbool{LWR@doingstartpars}{%
22     \ifnumcomp{\value{LWR@lateximagedepth}}{0}{%
23       }{%
24       \algocf@everyparnl\algocf@everyparhanging%
25     }{%
26   }{%
27 }{%
28 }{%
29 }

```

lwarp caption handling:

```

30 \renewcommand{\algocf@makecaption}[2]{%
31 \LWR@HTML@caption@begin{\algocf}%
32 \LWR@isolate{\algocf@captiontext{\#1}{\#2}}%
33 \LWR@HTML@caption@end%
34 }

```

Print any caption where it is declared:

```

35 \renewcommand{\algocf@makecaption@plain}[2]{%
36   \LWR@HTML@caption@begin{\algocf}%
37   \LWR@isolate{\algocf@captiontext{\#1}{\#2}}%
38   \LWR@HTML@caption@end%
39 }
40
41 \renewcommand{\algocf@makecaption@boxed}[2]{%
42   \LWR@HTML@caption@begin{\algocf}%
43   \LWR@isolate{\algocf@captiontext{\#1}{\#2}}%
44   \LWR@HTML@caption@end%
45 }
46
47 \renewcommand{\algocf@makecaption@ruled}[2]{%
48   \LWR@HTML@caption@begin{\algocf}%
49   \LWR@isolate{\algocf@captiontext{\#1}{\#2}}%
50   \LWR@HTML@caption@end%
51 }

```

Turn off line numbering while making the caption:

```

52 \long\def\algocf@latexcaption#1[#2]#3{%
53   \boolexpr{LWR@algocf@dopars}{%
54     \par%
55     \addcontentsline{\csname ext@#1\endcsname}{#1}%
56     {\protect\numberline{\csname the#1\endcsname}{\ignorespaces \LWR@isolate{#2}}}}%
57     \begingroup%
58     \parboxrestore%
59     \if@minipage%

```

```

60      \setminipage%
61      \fi%
62      \normalsize%
63      \makecaption{\csname fnum@\#1\endcsname}{\ignorespaces #3}\par%
64      \endgroup%
65 \booltrue{LWR@algocf@dopars}%
66 }%

```

Line numbers are printed in a <span> of class alg2elinenumber:

```

67 \renewcommand{\algocf@printnl}[1]{%
68     \InlineClass{alg2elinumber}{\NlSty{\#1}}{}%
69 }%

```

While initializing an algorithm environment, locally declare the style of a regular figure to be the same as the algorithm style, in case the figure option was used.

```

70 \preto{\algocf@init}{%
71     \edef\LWR@floatstyle@figure{\LWR@floatstyle@algocf}%
72 }%

```

For `lwarp`, the algorithm is not assembled inside a box, since `\textrimage`s would not work, so the captions are printed where declared.

```

73 \renewcommand{\@algocf@start}{%
74     \let{@mathsemicolon}=;\def{}{\ifmmode{@mathsemicolon}\else{\endalgoln}\fi}%
75 %     \raggedright%
76     \AlFnt{}%
77     \booltrue{LWR@algocf@dopars}%
78 }%
79
80 \renewcommand{\@algocf@finish}{%
81     \boolfalse{LWR@algocf@dopars}%
82     \lineskip\normallineskip\setlength{\skiptotal}{\@defaultskiptotal}%
83     \let{}=\@mathsemicolon%
84     \let[]={\emathdisplay}%
85 }%

```

Use an HTML break:

```

86 \renewcommand{\BlankLine}{%
87 \LWR@stoppars%
88 \LWR@htmlltagc{br /}%
89 \LWR@startpars%
90 }%

```

Simplified for HTML. The paragraph handling must be preserved.

```

91 \renewcommand{\SetKwInOut}[2]{%
92     \algocf@newcommand{\#1}[1]{%
93         \ifthenelse{\boolean{algocf@hanginginout}}{%
94             \relax%
95             \algocf@seteveryparhanging{\relax}}{%
96             \ifthenelse{\boolean{algocf@inoutnumbered}}{%

```

```

97      {\relax}%
98      {\algocf@seteveryparnl{\relax}}%
99  {%
100      \KwSty{#2\algocf@typo:}%
101      ~##1\par%
102  }%
103      \algocf@linesnumbered% reset the numbering of the lines
104      \ifthenelse{\boolean{\algocf@hanginginout}}{%
105          {\relax}%
106          {\algocf@reseteveryparhanging}%
107      }%
108 }%
109
110 \renewcommand{\ResetInOut}[1]{}

```

Each of the following creates a <div> of a given class, and turns off line numbering while creating the <div> tags:

```

111 \renewcommand{\algocf@Vline}[1]{%
112 \boolfalse{LWR@algocf@dopars}%
113 \begin{BlockClass}{alg2evline}%
114 \booltrue{LWR@algocf@dopars}%
115 #1
116 \boolfalse{LWR@algocf@dopars}%
117 \end{BlockClass}%
118 \booltrue{LWR@algocf@dopars}%
119 }

120 \renewcommand{\algocf@Vsline}[1]{%
121 \boolfalse{LWR@algocf@dopars}%
122 \begin{BlockClass}{alg2evsline}%
123 \booltrue{LWR@algocf@dopars}%
124 #1
125 \boolfalse{LWR@algocf@dopars}%
126 \end{BlockClass}%
127 \booltrue{LWR@algocf@dopars}%
128 }

129 \renewcommand{\algocf@Noline}[1]{%
130 \boolfalse{LWR@algocf@dopars}%
131 \begin{BlockClass}{alg2enoline}%
132 \booltrue{LWR@algocf@dopars}%
133 #1
134 \boolfalse{LWR@algocf@dopars}%
135 \end{BlockClass}%
136 \booltrue{LWR@algocf@dopars}%
137 }

```

The [H] environment is converted to a regular float, which in HTML is placed where declared. Reusing the regular float allows the [H] version to reuse the ruled and boxed options.

```

138 \LetLtxMacro{\algocf@Here}{\algocf
139 \LetLtxMacro{\endalgocf@Here}{\endalgocf
140 }

```

---

**File 18 l warp-algorithmicx.sty****§ 118 Package algorithmicx**

(Emulates or patches code by Szász János.)

Pkg algorithmicx algorithmicx is supported with minor adjustments.

**for HTML output:** 1 \LWR@ProvidesPackagePass{algorithmicx}[2005/04/27]

Inside the `algorithmic` environment, level indenting is converted to a `<span>` of the required length, and comments are placed inside a `<span>` which is floated right.

 **package conflicts** If using `\newfloat`, `trivfloat`, and/or `algorithmicx` together, see section 523.1.

**for HTML output:** 2 \begin{warpHTML}

```
3 \AtBeginEnvironment{algorithmic}{%
4 %
5 \let\origALG@doentity\ALG@doentity%
6 %
7 \renewcommand*\ALG@doentity{%
8 \origALG@doentity%
9 \LWR@htmltagc{%
10 span style="width:\LWR@printlength{\ALG@thistlm}; display:inline-block;"%
11 }%
12 \ifbool{FormatWP}{%
13 \setlength{\LWR@templengthone}{\the\ALG@thistlm}%
14 \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
15 \quad%
16 \addtolength{\LWR@templengthone}{-1em}%
17 }%
18 }{%
19 \LWR@htmltagc{/span}%
20 }%
21
22 \let\LWR@origComment\Comment%
23
24 \renewcommand{\Comment}[1]{%
25   \InlineClass{floatright}{\LWR@origComment{#1}}%
26 }%
27 }
28
29 \renewcommand\algorithmiccomment[1]{%
30 \hfill\HTMLunicode{25B7} #1% white right triangle
31 }%
32 \end{warpHTML}
```

File 19 **l warp-alltt.sty**

§ 119 Package **alltt**

*(Emulates or patches code by JOHANNES BRAAMS.)*

Pkg alltt alltt is patched for use by l warp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{alltt}[1997/06/16]

2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching alltt.}
4 \AtBeginEnvironment{alltt}{%
5 \LWR@forcenewpage
6 \LWR@atbeginverbatim{3}{alltt}%
7 }
8 \AfterEndEnvironment{alltt}{%
9   \LWR@afterendverbatim{2}%
10 }
11 }
```

File 20 **l warp-amsmath.sty**

§ 120 Package **amsmath**

*(Emulates or patches code by AMERICAN MATHEMATICAL SOCIETY, LATEX3 PROJECT.)*

Pkg amsmath amsmath is patched for use by l warp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{amsmath}[2017/09/02]
```

Patches to allow \eqref inside a caption:

```

2 \def\maketag@@#1{\text{#1}}
3 \def\tagform@#1{\maketag@@{(\ignorespaces#1\unskip)}}
```

Patches for AMS math \tag macro to remember the first tag:

```

4 \ifbool{mathjax}{}{%
5   \LetLtxMacro{\LWR@origmake@df@tag@@}{\make@df@tag@@}
6   \LetLtxMacro{\LWR@origmake@df@tag@@@}{\make@df@tag@@@}
7   \renewcommand*{\make@df@tag@@}[1]{%
8     \LWR@remembertag{#1}%
9     \LWR@origmake@df@tag@@{#1}%
10    }%
11  }%
12 }
```

```

13
14 \renewcommand*{\make@df@tag@@@}[1]{%
15 \LWR@remembertag{#1}%
16 \LWR@origmake@df@tag@@@{#1}%
17 }
18
19 }% not mathjax

```

For nesting  $\mathcal{AM}$ S environments:

```

20 \newcounter{LWR@amsmathdepth}
21 \setcounter{LWR@amsmathdepth}{0}

```

The following  $\mathcal{AM}$ S environments are patched in-place:

`\LWR@amsmathenv@@before * {<environment name>}`

\* if the environment was starred.

Embeds the environment inside a `lateximage`.

```

22 \NewDocumentCommand{\LWR@amsmathenv@@before}{s m}{%
23   \IfBooleanTF{#1}{%
24     \begin{BlockClass}{displaymath}
25   }{%
26     \begin{BlockClass}{displaymathnumbered}
27   }
28   \LWR@newautoidanchor%
29   \booltrue{\LWR@indisplaymathimage}%
30   \begin{lateximage}[\LWR@amsmathbodynumbered{#1}]*
31   \LWR@applyxfakebold%
32 }

```

`\LWR@amsmathenv@@before * {<environment name>}`

\* if the environment was starred.

Embeds the environment with MATHJAX or a `lateximage`.

```

33 \NewDocumentCommand{\LWR@amsmathenv@@before}{s m}{%
34   \ifnumequal{\value{LWR@amsmathdepth}}{0}{%
35     \LWR@stoppars%
36     \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{%
37       \LWR@syncmathjax
38       \boolfalse{\LWR@amsmultiline}
39       \ifstrequal{#2}{multiline}{\booltrue{\LWR@amsmultiline}}{}%
40       \ifstrequal{#2}{multiline*}{\booltrue{\LWR@amsmultiline}}{}%
41     }

```

⚠ autonum's "+" environments are not supported by MATHJAX.

```

42   \LWR@beginhideamsmath
43 }
44 {
45   \IfBooleanTF{#1}{%
46     \LWR@amsmathenv@@before*{#2}
47   }{%
48     \LWR@amsmathenv@@before{#2}

```

```

49          }
50      }
51  }{}
52  \addtocounter{LWR@amsmathdepth}{1}
53 }
```

\LWR@amsmathenv@@after

Embeds the environment inside a `lateximage`.

```

54 \newcommand*\{\LWR@amsmathenv@@after\}{%
55   \end{lateximage}\end{BlockClass}\LWR@startpars%
56 }
```

\LWR@amsmathenv@@after \* {*environment name*}

\* if the environment was starred. Ignored here, only used for a consistent syntax.

Embeds the environment with `MATHJAX` or a `lateximage`.

```

57 \NewDocumentCommand{\LWR@amsmathenv@@after}{s m}{%
58   \ifnumequal{\value{LWR@amsmathdepth}}{1}{%
59     \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }{%
60       {
61         \LWR@endhideamsmath
62         \boolfalse{LWR@amsmultline}
63         \LWR@addmathjax{#2}{\the\@envbody}
64       }
65     }{\LWR@amsmathenv@@after}}
```

Clear the single-use alt text:

```

66   \gdef\LWR@ThisAltText{}%
67   }{%
68   \addtocounter{LWR@amsmathdepth}{-1}
69 }
```

Env `multiline`

```

70 \BeforeBeginEnvironment{multiline}{\LWR@amsmathenv@before{multiline}}
71
72 \AfterEndEnvironment{multiline}{\LWR@amsmathenv@after{multiline}}
```

Env `multiline*`

```

73 \BeforeBeginEnvironment{multiline*}{\LWR@amsmathenv@before*{multiline*}}
74
75 \AfterEndEnvironment{multiline*}{\LWR@amsmathenv@after*{multiline*}}
76
```

Env `gather`

```

77 \BeforeBeginEnvironment{gather}{\LWR@amsmathenv@before{gather}}
78
79 \AfterEndEnvironment{gather}{\LWR@amsmathenv@after{gather}}
```

```
Env  gather*
80 \BeforeBeginEnvironment{gather*}{\LWR@amsmathenv@before*{gather*}}
81
82 \AfterEndEnvironment{gather*}{\LWR@amsmathenv@after*{gather*}}


Env  align
83 \BeforeBeginEnvironment{align}{\LWR@amsmathenv@before{align}}
84
85 \AfterEndEnvironment{align}{\LWR@amsmathenv@after{align}}


Env  align*
86 \BeforeBeginEnvironment{align*}{\LWR@amsmathenv@before*{align*}}
87
88 \AfterEndEnvironment{align*}{\LWR@amsmathenv@after*{align*}}


Env  flalign
89 \BeforeBeginEnvironment{flalign}{\LWR@amsmathenv@before{flalign}}
90
91 \AfterEndEnvironment{flalign}{\LWR@amsmathenv@after{flalign}}


Env  flalign*
92 \BeforeBeginEnvironment{flalign*}{\LWR@amsmathenv@before*{flalign*}}
93
94 \AfterEndEnvironment{flalign*}{\LWR@amsmathenv@after*{flalign*}}


Env  alignat
95 \BeforeBeginEnvironment{alignat}{\LWR@amsmathenv@before{alignat}}
96
97 \AfterEndEnvironment{alignat}{\LWR@amsmathenv@after{alignat}}


Env  alignat*
98 \BeforeBeginEnvironment{alignat*}{\LWR@amsmathenv@before*{alignat*}}
99
100 \AfterEndEnvironment{alignat*}{\LWR@amsmathenv@after*{alignat*}}
```

For MATHJAX:

```
101 \begin{warpMathJax}
102 \CustomizeMathJax{\newcommand{\intertext}[1]{\\ \text{#1}\notag \\}}
103 \end{warpMathJax}
```

---

File 21 **l warp-amsthm.sty**

§ 121 Package **amsthm**

*(Emulates or patches code by PUBLICATIONS TECHNICAL GROUP—AMERICAN MATHEMATICAL SOCIETY.)*

The original source code is located in `amsclass.dtx`, and printed in `amsclass.pdf`.

Pkg `amsthm` `amsthm` is patched for use by `l warp`.

---

Table 14: `amsthm` package—css styling of theorems and proofs

**Theorem:** `<div>` of class `amsthmbody<theoremstyle>`

**Theorem Name:** `<span>` of class `amsthmname<theoremstyle>`

**Theorem Number:** `<span>` of class `amsthmnumber<theoremstyle>`

**Theorem Note:** `<span>` of class `amsthmnote<theoremstyle>`

**Proof:** `<div>` of class `amsthmproof`

**Proof Name:** `<span>` of class `amsthmproofname`

where `<theoremstyle>` is plain, definition, etc.

---

for HTML output: `amsthm` must be loaded before `mdframed`:

```

1 \@ifpackageloaded{mdframed}{
2   \PackageError{l warp}{%
3     {Package mdframed must be loaded after package amsthm}%
4   }%
5   Move \detokenize{\usepackage}{amsthm} before
6   \detokenize{\usepackage}{mdframed}. \MessageBreak
7   Package amsthm may be loaded by something else, \MessageBreak
8   which must also be moved before mdframed.%%
9 }
10 }
11 {}
```

12 \LWR@ProvidesPackagePass{amsthm}[2017/10/31]

Storage for the style being used for new theorems:

13 \newcommand{\LWR@newtheoremstyle}{plain}

Patched to remember the style being used for new theorems:

```

14 \renewcommand{\theoremstyle}[1]{%
15   \@ifundefined{th@#1}{%
```

```

16   \PackageWarning{amsthm}{Unknown theoremstyle '#1'}%
17   \thm@style{plain}%
18   \renewcommand{\LWR@newtheoremstyle}[1]{\thm@style{#1}}% l warp
19 }{%
20   \thm@style{#1}%
21   \renewcommand{\LWR@newtheoremstyle}[1]{\thm@style{#1}}% l warp
22 }%
23 }

```

Patched to remember the style for this theorem type:

```

24 \def\xnethm#1#2{%
25   \csedef{\LWR@thmstyle#2}{\LWR@newtheoremstyle}% l warp
26   \let\tempa\relax
27   \expandafter\ifdefinable\csname #2\endcsname{%
28     \global\expandafter\let\csname end#2\endcsname\endtheore
29     \ifx *#1% unnumbered, need to get one more mandatory arg
30       \edef\tempa##1{%
31         \gdef\expandafter\csname#2\endcsname{%
32           \expandafter\at\thm{\expandafter\csname the\thm@style\endcsname}%
33           {##1}}%
34     \else % numbered theorem, need to check for optional arg
35       \def\tempa{\oparg{\ynthm{#2}}[]}% l warp
36     \fi
37   \AtBeginEnvironment{#2}{\edef\LWR@thisthmstyle{\nameuse{\LWR@thmstyle#2}}}% l warp
38 }%
39 \tempa
40 }

```

Patched to enclose with css:

```

41 \newcommand{\LWR@haveamsthmname}{%
42 \renewcommand{\thmname}[1]{\InlineClass{amsthmname}\LWR@thisthmstyle{##1}}%
43 }%
44
45 \newcommand{\LWR@haveamsthmnumber}{%
46 \renewcommand{\thmnumber}[1]{\InlineClass{amsthmnumber}\LWR@thisthmstyle{##1}}%
47 }%
48
49 \newcommand{\LWR@haveamsthmnote}{%
50 \renewcommand{\thmnote}[1]{\InlineClass{amsthmnote}\LWR@thisthmstyle{##1}}%
51 }%
52
53 \LWR@haveamsthmname
54 \LWR@haveamsthmnumber
55 \LWR@haveamsthmnote

```

Patches for css:

```

56 \def\begintheorem#1#2[#3]{%
57   \item[%
58 %   \deferred@thm@head{%
59 %     \the\thm@headfont \thm@indent
60   \ifempty{#1}{\let\thmname@gobble{\LWR@haveamsthmname}}% l warp
61   \ifempty{#2}{\let\thmnumber@gobble{\LWR@haveamsthmnumber}}% l warp

```

```

62  \@ifempty{#3}{\let\thmnote\@gobble}{\LWR@haveamsthmnote}% lwarp
63  \thm@swap\swappedhead\thmhead{#1}{#2}{#3}%
64  \the\thm@headpunct~%
65  \thmheadnl % possibly a newline.
66  \hskip\thm@headsep
67 }%
68 ]
69 \ignorespaces}

```

Patched for css:

```

70 \def\@thm#1#2#3{%
71   \ifhmode\unskip\unskip\par\fi
72   \normalfont
73   \LWR@forcenewpage% lwarp
74   \BlockClass{amsthmbody}\LWR@thisthmstyle}% lwarp
75   \trivlist
76   \let\thmheadnl\relax
77   \let\thm@swap\@gobble
78   \thm@notefont{\fontseries\mddefault\upshape}%
79   \thm@headpunct{.}% add period after heading
80   \thm@headsep 5\p@ plus\p@ minus\p@\relax
81   \thm@space@setup
82   #1% style overrides
83   \topsep \thm@preskip          % used by thm head
84   \topsepadd \thm@postskip      % used by \endparenv
85   \def\@tempa{#2}\ifx\@empty\@tempa
86     \def\@tempa{\oparg{\begin{theorem}{#3}[]}}%
87   \else
88     \refstepcounter{#2}%
89     \def\@tempa{\oparg{\begin{theorem}{#3}{\csname the#2\endcsname}[]}}%
90   \fi
91   \@tempa
92 }

```

`cleveref` patches `\@thm` to do `\cref@thmoptarg` if an optional argument is given. `lwarp` then patches `\cref@thmoptarg` `\AtBeginDocument`.

```

93 \AtBeginDocument{%
94 \def\cref@thmoptarg[#1]#2#3#4{%
95   \ifhmode\unskip\unskip\par\fi%
96   \normalfont%
97   \LWR@forcenewpage% lwarp
98   \BlockClass{amsthmbody}\LWR@thisthmstyle}% lwarp
99   \trivlist
100  \let\thmheadnl\relax%
101  \let\thm@swap\@gobble%
102  \thm@notefont{\fontseries\mddefault\upshape}%
103  \thm@headpunct{.}% add period after heading
104  \thm@headsep 5\p@ plus\p@ minus\p@\relax%
105  \thm@space@setup%
106  #2% style overrides
107  \topsep \thm@preskip          % used by thm head
108  \topsepadd \thm@postskip      % used by \endparenv
109  \def\@tempa{#3}\ifx\@empty\@tempa%

```

```

110      \def\@tempa{\@oparg{\@begintheorem{#4}{}}[]}%
111  \else%
112      \refstepcounter[#1]{#3}% << cleveref modification
113      \def\@tempa{\@oparg{\@begintheorem{#4}{\csname the#3\endcsname}}[]}%
114  \fi%
115  \@tempa
116 }%
117 }% AtBeginDocument
118
119 \def\@endtheorem{\endtrivlist\endBlockClass\@endpefalse }

```

Proof QED symbol:

```

120 \AtBeginDocument{
121 \@ifundefined{LWR@orig@openbox}%
122 \LetLtxMacro{\LWR@orig@openbox}{\openbox}
123 \LetLtxMacro{\LWR@orig@blacksquare}{\blacksquare}
124 \LetLtxMacro{\LWR@orig@Box}{\Box}
125
126 \def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
127 \def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
128 \def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box
129
130 \appto{\LWR@restoreorigformatting}{%
131 \LetLtxMacro{\openbox}{\LWR@orig@openbox}%
132 \LetLtxMacro{\blacksquare}{\LWR@orig@blacksquare}%
133 \LetLtxMacro{\Box}{\LWR@orig@Box}%
134 }% appto
135 }{}% @ifundefined
136 }% AtBeginDocument

```

Patched for css:

```

137 \renewenvironment{proof}[1][\proofname]{\par
138 \LWR@forcenewpage% lwarp
139     \BlockClass{amsthmproof}% lwarp
140     \pushQED{\qed}%
141     \normalfont \topsep6\p@\relax
142     \trivlist
143     \item[
144         \InlineClass{amsthmproofname}{\#1\@addpunct{.}}]\ignorespaces% changes
145     }{%
146     \InlineClass{theoremendmark}{\popQED}\endtrivlist%
147     \endBlockClass% lwarp
148     \endpefalse
149 }

```

## File 22 **lwarp-anonchap.sty**

§ 122 Package **anonchap**

(Emulates or patches code by PETER WILSON.)

Pkg anonchap anonchap is emulated.

Pkg tocloft If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its titles option, which tells tocloft to use standard L<sup>A</sup>T<sub>E</sub>X commands to create the titles, allowing other packages to work with it.

**⚠ tocloft & other packages** The code is shared by tocbibind.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{anonchap}[2009/08/03]

```
2 \newcommand{\simplechapter}[1][\empty]{%
3   \def\@chapcntformat##1{%
4     #1\csname the##1\endcsname\simplechapterdelim\quad%
5   }%
6 }
7
8 \newcommand{\restorechapter}{%
9 \let\@chapcntformat\@seccntformat%
10 }
```

---

#### File 23 l warp-any size .sty

### § 123 Package **any size**

(Emulates or patches code by MICHAEL SALZENBERG, THOMAS ESSER.)

Pkg anysize anysize is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{any size}[1994/08/13]

```
2 \def\papersize#1#2{%
3 \def\marginsize#1#2#3#4{}
```

---

#### File 24 l warp-appendix .sty

### § 124 Package **appendix**

(Emulates or patches code by PETER WILSON.)

Pkg appendix appendix is patched for use by l warp.

**⚠ incorrect toc link** During HTML conversion, the option toc without the option page results in a toc link to whichever section was before the appendices environment. It is recommended to use both toc and also page at the same time.

**for HTML output:** 1 \LWR@ProvidesPackagePass{appendix}[2009/09/02]

```
2 \renewcommand*\@chap@pppage{%
3 \part*\{\appendixpagename}
```

---

```

4 \if@dotoc@pp
5 \addappheadtotoc
6 \fi
7 }
8
9 \renewcommand*{\@sec@pppage}{%
10 \part*{\appendixpagename}
11 \if@dotoc@pp
12 \addappheadtotoc
13 \fi
14 }
```

---

### File 25 **l warp-ar.sty**

§ 125 Package **ar**

*(Emulates or patches code by AGOSTINO DE MARCO.)*

Pkg ar ar is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{ar}[2012/01/23]

Measure and print the width of the supplied glyph.

```

2 \newlength{\LWR@ar@width}
3
4 \newcommand*{\LWR@ar@printwidth}[1]{%
5   \setlength{\LWR@ar@width}{\widthof{#1}}%
6   width:%
7   \LWR@convertto{em}{\the\LWR@ar@width}em%
8 }
```

The HTML version of \AR:

```
9 \newrobustcmd*{\LWR@HTML@AR}{%
```

Start a hashed \teximage, additionally hashed by the font series, with a width depending on the given glyph:

```
10 \begin{teximage}*[\AR][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@AR}]%
```

For text mode, set the font series according to the HTML font series:

```
11 \ifmmode\else\csuse{\LWR@orig\LWR@f@series series}\fi%
```

Print the original glyph using the newly set font series:

```
12 \LWR@print@AR%
```

Done.

```

13     \end{lateximage}%
14 }

```

Combine the print and HTML versions:

```

15 \LWR@formatted{AR}

16 \newrobustcmd*{\LWR@HTML@ARb}{%
17     \begin{lateximage}*[AR][b][\LWR@ar@printwidth{\LWR@print@ARb}]%
18     \LWR@print@ARb%
19     \end{lateximage}%
20 }
21 \LWR@formatted{ARb}

22 \newrobustcmd*{\LWR@HTML@ARss}{%
23     \begin{lateximage}*[ARss][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@ARss}]%
24     \ifmmode\else\csuse{\LWR@orig}\LWR@f@series series\fi%
25     \LWR@print@ARss%
26     \end{lateximage}%
27 }
28 \LWR@formatted{ARss}

29 \newrobustcmd*{\LWR@HTML@ARssb}{%
30     \begin{lateximage}*[AR][ssb][\LWR@ar@printwidth{\LWR@print@ARssb}]%
31     \LWR@print@ARssb%
32     \end{lateximage}%
33 }
34 \LWR@formatted{ARssb}

35 \newrobustcmd*{\LWR@HTML@ARtt}{%
36     \begin{lateximage}*[AR][tt][\LWR@ar@printwidth{\LWR@print@ARtt}]%
37     \LWR@print@ARtt%
38     \end{lateximage}%
39 }
40 \LWR@formatted{ARtt}

```

For MATHJAX:

```

41 \begin{warpMathJax}
42 \CustomizeMathJax{\newcommand{\AR}{\mathit{A}!`!R}}
43 \CustomizeMathJax{\newcommand{\ARB}{\boldsymbol{A}!`!R}}
44 \end{warpMathJax}

```

#### File 26 lwarp-arabicfront.sty

§ 126 Package **arabicfront**

Pkg arabicfront arabicfront is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{arabicfront}[2006/09/03]

---

File 27 **l warp-array.sty**

§ 127 Package **array**

Pkg array array is used as-is for print output, and emulated for HTML.

plarray and plectarray do not affect \firsthline or \lasthline, and so are not affected by the following.

Remove the default nullified macros:

```

1 \let\firsthline\relax
2 \let\lasthline\relax
3
4 \LWR@ProvidesPackagePass{array}[2018/12/30]

5 \newcommand*{\LWR@HTML@firsthline}{\LWR@HTMLhline}%
6 \LWR@expandableformatted{firsthline}
7
8 \newcommand*{\LWR@HTML@lasthline}{\LWR@HTMLhline}%
9 \LWR@expandableformatted{lasthline}

10 \providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
11 \LWR@formatted{tabularnewline}
```

For MATHJAX:

```

12 \CustomizeMathJax{
13   \newcommand{\multicolumn}[3]{#3}% only uses one cell
14 }
```

---

File 28 **l warp-arydshln.sty**

§ 128 Package **arydshln**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg arydshln arydshln heavily patches tabular code, so the actual package is not used. arydshln is emulated for HTML tabular, and reverts to solid rules for SVG math array and tabular in a lateximage.

css is not able to display a double-dashed border, so a single-dashed rule is displayed as a single-dashed border, and a double-dashed rule is displayed as a thicker single-dashed border.

For MATHJAX, limited emulation is provided for math mode.

for HTML output:

array is required to allow \newcolumn below.

```

1 \RequirePackage{array}

2 \LWR@ProvidesPackageDrop{arydshln}[2018/09/26]
```

Ignored, but included for source compatibility:

```

3 \newdimen\dashlinedash \dashlinedash4pt %
4 \newdimen\dashlinegap \dashlinegap4pt %
5 \let\hdashlinewidth\dashlinedash
6 \let\hdashlinegap\dashlinegap
7
8 \def\ADLnullwide{}
9 \def\ADLsomewide{}
10 \def\ADLnullwidehline{}
11 \def\ADLsomewidehline{}
12
13 \def\ADLactivate{}
14 \def\ADLinactivate{}
15 \newcommand*\{\ADLdrawingmode}[1]{}
16 \newcommand*\{\ADLno shorthanded}{}
17 \newcommand*\{\dashgapcolor}[2][]{}
18 \newcommand*\{\nodashgapcolor}{}
```

In a `lateximage`, revert to solid vertical rules:

```

19 \appto\LWR@restoreorigformatting{%
20 \newcolumntype{:}{|}%
21 \newcolumntype{;}{[]}{|}%
22 \LetLtxMacro{\dashline}{\hline}%
23 }
```

Some of these macros are already defined as temporary placeholders in the `lwarp` core, so they must be redefined here.

The emulated defaults also work for an emulated print mode inside a `lateximage`:

```

24 \def\hline{
25 %     \adl@hline\adl@ihline
26     \adl@hline\adl@inactivehdl
27 }
28 \def\adl@hline#1{\noalign{\ifnum0='}\fi
29 %         \ifadl@zhrule \vskip-\arrayrulewidth
30 %         \else
31 %             \adl@hline\adl@connect\arrayrulewidth
32 %                 \hrule \height \arrayrulewidth\ lwarp
33 %         \fi
34     \@ifnextchar[%
35         {#1}%
36         {#1[%
37 %             \dashlinedash/\dashlinegap
38             1pt/1pt
39         ]}}}
```

```

40 % \def\adl@ihdashline[#1/#2]{\ifnum0='{\fi}%
41 %           \multispan{\adl@columns}\unskip \adl@hcline\z@[#1/#2]%
42 %           \noalign{\ifnum0='}\fi
43 %           \futurelet@tempa\adl@xhline}
44 \def\adl@inactivehdl[#1/#2]{%
45 %           \ifadl@zwhrule \vskip-\arrayrulewidth \fi
46 %           \hrule\height\arrayrulewidth
47 %           \futurelet@tempa\adl@xhline}
48 \def\adl@xhline{\ifx@\tempa\hline \adl@ixhline\fi
49 %           \ifx@\tempa\vhdashline \adl@ixhline\fi
50 %           \ifnum0='{\fi}%
51 \def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
52 \def\adl@hline#1#2{%
53 %           \tempcpta#2
54 %           \global\advance\adl@totalheight\tempcpta
55 %           \xdef\adl@rowsL{\adl@rowsL
56 %           (#1/\number\tempcpta); }%
57 %           \xdef\adl@rowsR{\adl@rowsR
58 %           (#1/\number\tempcpta); }
59 }
60
61 \def\cdashline#1{\noalign{\ifnum0='}\fi
62 %           \@ifnextchar[%]
63 %           {\adl@cdline[#1]}%
64 %           {\adl@cdline[#1][\dashlinedash/\dashlinegap]}%
65 %           {\adl@inactivecdl[#1]}%
66 %           {\adl@inactivecdl[#1][\dashlinedash/\dashlinegap]}%
67 }
68
69 \def\adl@inactivecdl[#1-#2][#3]{\ifnum0='{\fi}\cline{#1-#2}}
70 \begin{warpMathJax}
71 \CustomizeMathJax{\newcommand{\firstdashline}[1][]{\hdashline}}
72 \CustomizeMathJax{\let\lastdashline\firstdashline}
73 \CustomizeMathJax{\let\cdashline\cline}
74 \end{warpMathJax}

```

File 29 **l warp-asymptote.sty**

§ 129 Package **asymptote**

(Emulates or patches code by ANDY HAMMERLINDL, JOHN BOWMAN, TOM PRINCE.)

Pkg **asymptote** **asymptote** is patched for use by **l warp**.

To compile:

```

pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

**for HTML output:** 1 \LWR@ProvidesPackagePass{asymptote}[2016/11/26]

```

2 \BeforeBeginEnvironment{asy}{%
3   \begin{lateximage}[-asymptote-\~\PackageDiagramAltText]%
4 }
5 \AfterEndEnvironment{asy}{\end{lateximage}}
6
7 \xpatchcmd{\asyinclude}
8   {\begingroup}
9   {\begin{lateximage}[-asymptote-\~\PackageDiagramAltText]}
10  {}
11  {\LWR@patcherror{asymptote}{asyinclude-begingroup}}
12
13 \xpatchcmd{\asyinclude}
14  {\endgroup}
15  {\end{lateximage}}
16  {}
17  {\LWR@patcherror{asymptote}{asyinclude-endgroup}}
```

### File 30 **l warp-atbegshi.sty**

§ 130      Package **atbegshi**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg atbegshi atbegshi is ignored.

**for HTML output:** Discard all options for **l warp-atbegshi**:

```

1 \LWR@ProvidesPackageDrop{atbegshi}[2011/10/05]

2 \newcommand*{\AtBeginShipout}[1]{}
3 \newbox\AtBeginShipoutBox
4 \newcommand*{\AtBeginShipoutNext}[1]{}
5 \newcommand*{\AtBeginShipoutFirst}[1]{}
```

---

```

6 \newcommand*{\AtBeginShipoutDiscard}{}
7 \newcommand*{\AtBeginShipoutInit}{}
8 \newcommand*{\AtBeginShipoutAddToBox}[1]{}
9 \newcommand*{\AtBeginShipoutAddToBoxForeground}[1]{}
10 \newcommand*{\AtBeginShipoutUpperLeft}[1]{}
11 \newcommand*{\AtBeginShipoutUpperLeftForeground}[1]{}
12 \newcommand*{\AtBeginShipoutOriginalShipout}[1]{}
13 \def\AtBeginShipoutBoxWidth{0pt}
14 \def\AtBeginShipoutBoxHeight{0pt}
15 \def\AtBeginShipoutBoxDepth{0pt}
16

```

---

### File 31 **lwarp-attachfile.sty**

#### § 131 Package **attachfile**

*(Emulates or patches code by SCOTT PAKIN.)*

Pkg **attachfile** **attachfile** is patched for use by **lwarp**.

 Metadata is ignored for now.

**for HTML output:** 1 \LWR@ProvidesPackagePass{attachfile}[2016/09/18]

Encloses each icon:

```

2 \newenvironment*{\LWR@attachfile@icon}
3 {
4     \begin{lateximage}%
5         [-attachfile-]%
6         [%
7             \detokenize\expandafter{\atfi@icon@icon}-%
8             \detokenize\expandafter{\atfi@color@rgb}%
9         ]%
10 }
11 {
12     \end{lateximage}
13 }

```

Each icon is enclosed inside a **\LWR@attachfile@icon** environment:

```

14 \xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
15 \xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}
16
17 \xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
18 \xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}
19
20 \xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
21 \xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}
22
23 \xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
24 \xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}

```

Disable PDF file embedding:

```
25 \DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an \attachfile reference:

```
26 \newcommand*{\LWR@attachfile@appearance}{}  
27  
28 \DeclareRobustCommand{\atfi@set@appearance}[1]{%  
29     \def\LWR@attachfile@appearance{\#1}%  
30 }
```

A file annotation becomes a reference:

```
31 \DeclareRobustCommand{\atfi@insert@file@annot}[1]{%  
32     \href{\#1}{\LWR@attachfile@appearance}%  
33 }
```

### File 32 l warp-attachfile2.sty

## § 132 Package **attachfile2**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg attachfile2 attachfile2 is patched for use by l warp.



Metadata is ignored for now.

**for HTML output:** 1 \LWR@ProvidesPackagePass{attachfile2}[2016/05/16]

Adds memory of the selected color:

```
2 \def\LWR@attachfiletwo@color{}%  
3  
4 \define@key{AtFi}{color}{%  
5     \def\LWR@attachfiletwo@color{\#1}%    l warp  
6     \HyColor@AttachfileColor{\#1}%  
7         \atfi@color@tex\atfi@color@color@inline\atfi@color@annot  
8         {attachfile2}{color}}%  
9 }
```

Encloses each icon:

```
10 \newenvironment*{\LWR@attachfile@icon}  
11 {  
12     \begin{latentimage}*%  
13         [-attachfile-]%
```

[%  
15 \detokenize\expandafter{\atfi@icon@icon}-%  
16 \detokenize\expandafter{\LWR@attachfiletwo@color}}%  
17 ]%

```
18 }
```

```

19 {
20     \end{lateximage}
21 }

```

Each icon is enclosed inside a `\LWR@attachfile@icon` environment:

```

22 \xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
23 \xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}
24
25 \xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
26 \xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}
27
28 \xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
29 \xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}
30
31 \xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
32 \xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}

```

Disable PDF file embedding:

```
33 \DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an `\attachfile` reference:

```

34 \newcommand*{\LWR@attachfile@appearance}{}%
35
36 \def\atfi@set@appearance@icon{%
37     \atfi@set@appearance{\csname atfi@acro\atfi@icon@icon\endcsname}%
38 }
39
40 \DeclareRobustCommand{\atfi@set@appearance}[1]{%
41     \def\LWR@attachfile@appearance{\#1}%
42 }

```

A file annotation becomes a reference:

```

43 \DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
44     \href{\#1}{\LWR@attachfile@appearance}%
45 }

```

Modified for text color:

```

46 \DeclareRobustCommand{\notextattachfile}[2][]{%
47     \begingroup
48     \atfi@setup{\#1}%
49     \ifatfi@print
50         \leavevmode
51         \begingroup
52             \HyColor@UseColor\atfi@color@tex
53             \LWR@textcurrentcolor{\#2}%
54             lwarp
55         \endgroup
56     \else
57         \sbox{\ltx@zero{\#2\strut}}%

```

```

58 %           \makebox[\wd0]{}
59   \fi
60 \endgroup
61 }

```

Modified to draw the icon:

```

62 \DeclareRobustCommand{\noattachfile}[1][]{%
63   \begingroup
64     \atfi@setup{#1}%
65     \atfi@set@appearance@icon
66     \ifatfi@print
67       \LWR@attachfile@appearance%    l warp
68 %       \expandafter
69 %       \atfi@refxform\csname atfi@appobj@\atfi@icon@icon\endcsname
70 %     \else
71 %       \makebox[\atfi@appearancewidth]{}
72     \fi
73   \endgroup
74 }

```

### File 33 **l warp-authblk.sty**

## § 133 Package **authblk**

*(Emulates or patches code by PATRICK W. DALY.)*

Pkg authblk authblk is patched for HTML.

**package support** l warp supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

**\published and \subtitle** If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

*(Emulates or patches code by PATRICK W. DALY.)*

**for HTML output:** Require that authblk be loaded before titling:

```

1 \@ifpackageloaded{titling}{%
2 \PackageError{l warp-authblk}{%
3 Package authblk must be loaded before titling}%
4 {Titling appends authblk's author macro, so authblk must be loaded first.}%
5 }%
6 {}

```

Load authblk:

```
7 \LWR@ProvidesPackagePass{authblk}[2001/02/27]
```

Patch to add a class for the affiliation:

---

```

8 \LetLtxMacro{\LWRAB@affil}{\affil}
9
10 \renewcommand{\affil}[2][]{%
11 \LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}%
12 }

```

Create an HTML break for an \authorcr:

```
13 \renewcommand*{\authorcr}{\protect\LWR@newlinebr}
```

---

#### File 34 **lwarp-autobreak.sty**

### § 134 Package **autobreak**

*(Emulates or patches code by TAKAHIRO UEDA.)*

Pkg **autobreak** **autobreak** is used as-is for SVG math, and nullified for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{autobreak}[2017/02/23]

For MATHJAX. The modified align environment is used for SVG math, but is reverted to its original for MATHJAX. (Extraneous commas were appearing in the result.)

```

2 \begin{warpMathJax}
3 \renewenvironment{autobreak}{\newcommand{\MoveEqLeft}[1]{}}
4 \let\start@align\@autobreak\oldstart@align
5 \let\endalign\@autobreak\oldendalign
6 \CustomizeMathJax{\newenvironment{autobreak}{}{}}
7 \CustomizeMathJax{\newcommand{\MoveEqLeft}[1][]{}}
8 \CustomizeMathJax{\newcommand{\everybeforeautobreak}[1]{}}
9 \CustomizeMathJax{\newcommand{\everyafterautobreak}[1]{}}
10 \end{warpMathJax}

```

---

#### File 35 **lwarp-autonum.sty**

### § 135 Package **autonum**

Pkg **autonum** **autonum** is ignored.

⚠ **numbering** All equations are numbered in HTML output.

MATHJAX does not support the “+” environments.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{autonum}[2015/01/18]

```

2 \RequirePackage{amsmath}
3
4
5 \newenvironment{equation+}{\equation}{\endequation}

```

```

6
7
8 \newenvironment{gather+}{\gather}{\endgather}
9
10 \BeforeBeginEnvironment{gather+}{\LWR@amsmathenv@@before{gather+}}
11
12 \AfterEndEnvironment{gather+}{\LWR@amsmathenv@@after}
13
14
15 \newenvironment{multiline+}{\multiline}{\endmultiline}
16
17 \BeforeBeginEnvironment{multiline+}{\LWR@amsmathenv@@before{multiline+}}
18
19 \AfterEndEnvironment{multiline+}{\LWR@amsmathenv@@after}
20
21
22 \newenvironment{flalign+}{\flalign}{\endflalign}
23
24 \BeforeBeginEnvironment{flalign+}{\LWR@amsmathenv@@before{flalign+}}
25
26 \AfterEndEnvironment{flalign+}{\LWR@amsmathenv@@after}
27
28
29 \newenvironment{align+}{\align}{\endalign}
30
31 \BeforeBeginEnvironment{align+}{\LWR@amsmathenv@@before{align+}}
32
33 \AfterEndEnvironment{align+}{\LWR@amsmathenv@@after}
34
35
36 \newenvironment{alignat+}{\alignat}{\endalignat}
37
38 \BeforeBeginEnvironment{alignat+}{\LWR@amsmathenv@@before{alignat+}}
39
40 \AfterEndEnvironment{alignat+}{\LWR@amsmathenv@@after}
41
42
43 \newenvironment{split+}{\split}{\endsplit}

```

---

### File 36 l warp-awesomebox.sty

#### § 136 Package **awesomebox**

(Emulates or patches code by ÉTIENNE DEPARIS.)

Pkg awesomebox awesomebox is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{awesomebox}[2019/07/27]

```

2 \newcommand*\{\LWR@awesomebox@boxborders\}{}%
3 \newcommand*\{\LWR@awesomebox@contentsborders\}{}%
4
5 \newcommand*\{\LWR@awesomebox@ruleborders\}%

```

```
6      border-top: 1px solid black ;
7      border-bottom: 1px solid black%
8 }
9
10 \% awesomebox[1:vrulecolor][2:hrule][3:title]{4:vrulewidth}{5:icon}{6:iconcolor}{7:content}
11 \RenewDocumentCommand \awesomebox { 0{abvrulecolor} 0{} o m m m +m }{%
12     \begin{awesomeblock}{#1}[#2][#3]{#4}{#5}{#6}
13     #7
14     \end{awesomeblock}
15 }
16
17 \% \begin{awesomeblock}[1:vrulecolor][2:hrule][3:title]{4:vrulewidth}{5:icon}{6:iconcolor}
18 \% <contents>
19 \% \end{awesomeblock}
20 \RenewDocumentEnvironment{awesomeblock}{ 0{abvrulecolor} 0{} o m m m }
21 {%
22     \LWR@forceminwidth{#4}%
23     \convertcolorspec{named}{#1}{HTML}\LWR@tempcolor%
24     \renewcommand*\{\LWR@awesomebox@boxborders\}{%
25     \renewcommand*\{\LWR@awesomebox@contentsborders\}{%
26     \ifdef\streq{\abShortLine}{#2}{%
27         \renewcommand*\{\LWR@awesomebox@contentsborders\}{\LWR@awesomebox@ruleborders}%
28     }{%
29     \ifdef\streq{\abLongLine}{#2}{%
30         \renewcommand*\{\LWR@awesomebox@boxborders\}{\LWR@awesomebox@ruleborders}%
31     }{%
32     \begin{BlockClass}[\LWR@awesomebox@boxborders]{awesomebox}
33     \begin{BlockClass}[% 
34         margin-left: 2\% ;
35         vertical-align: top
36     ]{minipage}
37         \color{#6}\Huge #5
38     \end{BlockClass}
39     \begin{BlockClass}[% 
40         width:75\% ;
41         vertical-align: top ;
42         padding-left: 1em ;
43         \LWR@awesomebox@contentsborders ;
44         border-left: \LWR@printlength{\LWR@atleastonept} %
45             solid \LWR@origpound\LWR@tempcolor%
46     ]{minipage}
47         \IfValueTF{#3}{#3\newline}{}
48 }
49 {%
50     \end{BlockClass}
51     \end{BlockClass}
52 }
```

---

File 37 **lwarp-axessibility.sty**

§ 137      Package **axessibility**

Pkg axessibility axessibility is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{axessibility}
2 \newcommand{\wrap}{1}{}

---


```

### File 38 **l warp-axodraw2.sty**

#### § 138 Package **axodraw2**

*(Emulates or patches code by JOHN C. COLLINS, J.A.M. VERMASEREN.)*

Pkg axodraw2 axodraw2 is patched for use by l warp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{axodraw2}[2018/02/15]
2 \BeforeBeginEnvironment{axopicture}{%
3   \begin{lateximage}[-axopicture-\~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{axopicture}{\end{lateximage}}

---


```

### File 39 **l warp-backnaur.sty**

#### § 139 Package **backnaur**

*(Emulates or patches code by ADRIAN P. ROBSON.)*

Pkg backnaur backnaur is patched for use by l warp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{backnaur}[2019/06/18]
2 \renewenvironment{bnf}{\eqnarray}{\endeqnarray}
3 \renewenvironment{bnf*}{\csuse{eqnarray*}}{\csuse{endeqnarray*}}

---


```

### File 40 **l warp-backref.sty**

#### § 140 Package **backref**

*(Emulates or patches code by DAVID CARLISLE AND SEBASTIAN RAHTZ.)*

Pkg backref backref is patched for use by l warp.

**⚠ loading** Note that backref must be explicitly loaded, and is not automatically loaded by hyperref when generating HTML output.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{backref}[2016/05/21]
```

Force the hyperref option:

```
2 \def\backref{}{\let\backrefxxx\hyper@section@backref}
```

#### File 41 **lwarf-balance.sty**

§ 141 Package **balance**

*(Emulates or patches code by PATRICK W. DALY.)*

Pkg **balance** **balance** is ignored.

for **HTML output**: Discard all options for **lwarf-balance**:

```
1 \LWR@ProvidesPackageDrop{balance}[1999/02/23]
2 \newcommand*\{balance}{}{}
3 \newcommand*\{nobalance}{}{}
```

#### File 42 **lwarf-bbding.sty**

§ 142 Package **bbding**

*(Emulates or patches code by KAREL HORAK, PETER MØLLER NEERGAARD.)*

Pkg **bbding** **bbding** is patched for use by **lwarf**.

for **HTML output**:  
1 \LWR@ProvidesPackagePass{bbding}[1999/04/15]

```
2 \newcommand*\{\LWR@bbdingsymbol}[2]{\HTMLunicode{#2}}{2701}
3
4 \newcommand{\LWR@HTML@ScissorRightBrokenBottom}{\LWR@bbdingsymbol{000}}{2702}
5 \newcommand{\LWR@HTML@ScissorRight}{\LWR@bbdingsymbol{001}}{2703}
6 \newcommand{\LWR@HTML@ScissorRightBrokenTop}{\LWR@bbdingsymbol{002}}{2704}
7 \newcommand{\LWR@HTML@ScissorLeftBrokenBottom}{\LWR@bbdingsymbol{003}}{2705}
8 \newcommand{\LWR@HTML@ScissorLeft}{\LWR@bbdingsymbol{004}}{2706}
9 \newcommand{\LWR@HTML@ScissorLeftBrokenTop}{\LWR@bbdingsymbol{005}}{2707}
10 \newcommand{\LWR@HTML@ScissorHollowRight}{\LWR@bbdingsymbol{006}}{2708}
11 \newcommand{\LWR@HTML@ScissorHollowLeft}{\LWR@bbdingsymbol{007}}{2709}
12 \newcommand{\LWR@HTML@Phone}{\LWR@bbdingsymbol{010}}{2710}
13 \newcommand{\LWR@HTML@PhoneHandset}{\LWR@bbdingsymbol{011}}{2711}
14 \newcommand{\LWR@HTML@Tape}{\LWR@bbdingsymbol{012}}{2712}
15 \newcommand{\LWR@HTML@Plane}{\LWR@bbdingsymbol{013}}{2713}
16 \newcommand{\LWR@HTML@Envelope}{\LWR@bbdingsymbol{014}}{2714}
17 \newcommand{\LWR@HTML@HandCuffRight}{\LWR@bbdingsymbol{015}}{2715}
18 \newcommand{\LWR@HTML@HandCuffLeft}{\LWR@bbdingsymbol{016}}{2716}
19 \newcommand{\LWR@HTML@HandCuffRightUp}{\LWR@bbdingsymbol{017}}{2717}
20 \newcommand{\LWR@HTML@HandCuffLeftUp}{\LWR@bbdingsymbol{020}}{2718}
21 \newcommand{\LWR@HTML@HandRight}{\LWR@bbdingsymbol{021}}{2719}
22 \newcommand{\LWR@HTML@HandLeft}{\LWR@bbdingsymbol{022}}{2720}
```

```
23 \newcommand{\LWR@HTML@HandRightUp}{\LWR@bbdingsymbol{023}} {261D}}
24 \newcommand{\LWR@HTML@HandLeftUp}{\LWR@bbdingsymbol{024}} {261F}}
25 \newcommand{\LWR@HTML@Peace}{\LWR@bbdingsymbol{025}} {270C}}
26 \newcommand{\LWR@HTML@HandPencilLeft}{\LWR@bbdingsymbol{026}} {270D}}
27 \newcommand{\LWR@HTML@PencilRight}{\LWR@bbdingsymbol{027}} {270F}}
28 \newcommand{\LWR@HTML@PencilLeft}{\LWR@bbdingsymbol{030}} {270F}}
29 \newcommand{\LWR@HTML@PencilRightUp}{\LWR@bbdingsymbol{031}} {2710}}
30 \newcommand{\LWR@HTML@PencilLeftUp}{\LWR@bbdingsymbol{032}} {2710}}
31 \newcommand{\LWR@HTML@PencilRightDown}{\LWR@bbdingsymbol{033}} {270E}}
32 \newcommand{\LWR@HTML@PencilLeftDown}{\LWR@bbdingsymbol{034}} {270E}}
33 \newcommand{\LWR@HTML@NibRight}{\LWR@bbdingsymbol{035}} {2711}}
34 \newcommand{\LWR@HTML@NibLeft}{\LWR@bbdingsymbol{036}} {2711}}
35 \newcommand{\LWR@HTML@NibSolidRight}{\LWR@bbdingsymbol{037}} {2712}}
36 \newcommand{\LWR@HTML@NibSolidLeft}{\LWR@bbdingsymbol{040}} {2712}}
37 \newcommand{\LWR@HTML@Checkmark}{\LWR@bbdingsymbol{041}} {2713}}
38 \newcommand{\LWR@HTML@CheckmarkBold}{\LWR@bbdingsymbol{042}} {2714}}
39 \newcommand{\LWR@HTML@XSolid}{\LWR@bbdingsymbol{043}} {2715}}
40 \newcommand{\LWR@HTML@XSolidBold}{\LWR@bbdingsymbol{044}} {2716}}
41 \newcommand{\LWR@HTML@XSolidBrush}{\LWR@bbdingsymbol{045}} {2717}}
42 \newcommand{\LWR@HTML@PlusOutline}{\LWR@bbdingsymbol{046}} {2719}}
43 \newcommand{\LWR@HTML@Plus}{\LWR@bbdingsymbol{047}} {271A}}
44 \newcommand{\LWR@HTML@PlusCenterOpen}{\LWR@bbdingsymbol{050}} {271C}}
45 \newcommand{\LWR@HTML@PlusThinCenterOpen}{\LWR@bbdingsymbol{051}} {271B}}
46 \newcommand{\LWR@HTML@Cross}{\LWR@bbdingsymbol{052}} {271D}}
47 \newcommand{\LWR@HTML@CrossOpenShadow}{\LWR@bbdingsymbol{053}} {271E}}
48 \newcommand{\LWR@HTML@CrossOutline}{\LWR@bbdingsymbol{054}} {271F}}
49 \newcommand{\LWR@HTML@CrossBoldOutline}{\LWR@bbdingsymbol{055}} {271F}}
50 \newcommand{\LWR@HTML@CrossMaltese}{\LWR@bbdingsymbol{056}} {2720}}
51 \newcommand{\LWR@HTML@DavidStarSolid}{\LWR@bbdingsymbol{057}} {2721}}
52 \newcommand{\LWR@HTML@DavidStar}{\LWR@bbdingsymbol{060}} {2721}}
53 \newcommand{\LWR@HTML@FourAsterisk}{\LWR@bbdingsymbol{061}} {2722}}
54 \newcommand{\LWR@HTML@JackStar}{\LWR@bbdingsymbol{062}} {2723}}
55 \newcommand{\LWR@HTML@JackStarBold}{\LWR@bbdingsymbol{063}} {2724}}
56 \newcommand{\LWR@HTML@CrossClowerTips}{\LWR@bbdingsymbol{064}} {2725}}
57 \newcommand{\LWR@HTML@FourStar}{\LWR@bbdingsymbol{065}} {2726}}
58 \newcommand{\LWR@HTML@FourStarOpen}{\LWR@bbdingsymbol{066}} {2727}}
59 \newcommand{\LWR@HTML@FiveStarLines}{\LWR@bbdingsymbol{067}} {2729}}
60 \newcommand{\LWR@HTML@FiveStar}{\LWR@bbdingsymbol{070}} {2605}}
61 \newcommand{\LWR@HTML@FiveStarOpen}{\LWR@bbdingsymbol{071}} {2729}}
62 \newcommand{\LWR@HTML@FiveStarOpenCircled}{\LWR@bbdingsymbol{072}} {272A}}
63 \newcommand{\LWR@HTML@FiveStarCenterOpen}{\LWR@bbdingsymbol{073}} {272B}}
64 \newcommand{\LWR@HTML@FiveStarOpenDotted}{\LWR@bbdingsymbol{074}} {272C}}
65 \newcommand{\LWR@HTML@FiveStarOutline}{\LWR@bbdingsymbol{075}} {272D}}
66 \newcommand{\LWR@HTML@FiveStarOutlineHeavy}{\LWR@bbdingsymbol{076}} {272E}}
67 \newcommand{\LWR@HTML@FiveStarConvex}{\LWR@bbdingsymbol{077}} {272F}}
68 \newcommand{\LWR@HTML@FiveStarShadow}{\LWR@bbdingsymbol{100}} {2730}}
69 \newcommand{\LWR@HTML@AsteriskBold}{\LWR@bbdingsymbol{101}} {2731}}
70 \newcommand{\LWR@HTML@AsteriskCenterOpen}{\LWR@bbdingsymbol{102}} {2732}}
71 \newcommand{\LWR@HTML@AsteriskThin}{\LWR@bbdingsymbol{103}} {273B}}
72 \newcommand{\LWR@HTML@AsteriskThinCenterOpen}{\LWR@bbdingsymbol{104}} {273C}}
73 \newcommand{\LWR@HTML@EightStarTaper}{\LWR@bbdingsymbol{105}} {2733}}
74 \newcommand{\LWR@HTML@EightStarConvex}{\LWR@bbdingsymbol{106}} {2735}}
75 \newcommand{\LWR@HTML@SixStar}{\LWR@bbdingsymbol{107}} {2736}}
76 \newcommand{\LWR@HTML@EightStar}{\LWR@bbdingsymbol{110}} {2737}}
77 \newcommand{\LWR@HTML@EightStarBold}{\LWR@bbdingsymbol{111}} {2738}}
```

```
78 \newcommand{\LWR@HTML@TwelweStar}{\LWR@bbdingsymbol{112}} {2739}}
79 \newcommand{\LWR@HTML@SixteenStarLight}{\LWR@bbdingsymbol{113}} {273A}}
80 \newcommand{\LWR@HTML@SixFlowerPetalRemoved}{\LWR@bbdingsymbol{114}} {273B}}
81 \newcommand{\LWR@HTML@SixFlowerOpenCenter}{\LWR@bbdingsymbol{115}} {273C}}
82 \newcommand{\LWR@HTML@Asterisk}{\LWR@bbdingsymbol{116}} {273D}}
83 \newcommand{\LWR@HTML@SixFlowerAlternate}{\LWR@bbdingsymbol{117}} {273E}}
84 \newcommand{\LWR@HTML@FiveFlowerPetal}{\LWR@bbdingsymbol{120}} {273F}}
85 \newcommand{\LWR@HTML@SixFlowerPetalDotted}{\LWR@bbdingsymbol{121}} {2740}}
86 \newcommand{\LWR@HTML@FiveFlowerOpen}{\LWR@bbdingsymbol{122}} {2740}}
87 \newcommand{\LWR@HTML@EightFlowerPetal}{\LWR@bbdingsymbol{123}} {2741}}
88 \newcommand{\LWR@HTML@SunshineOpenCircled}{\LWR@bbdingsymbol{124}} {2742}}
89 \newcommand{\LWR@HTML@SixFlowerAltPetal}{\LWR@bbdingsymbol{125}} {2743}}
90 \newcommand{\LWR@HTML@FourClowerOpen}{\LWR@bbdingsymbol{126}} {273F}}
91 \newcommand{\LWR@HTML@FourClowerSolid}{\LWR@bbdingsymbol{127}} {273F}}
92 \newcommand{\LWR@HTML@AsteriskRoundedEnds}{\LWR@bbdingsymbol{130}} {2749}}
93 \newcommand{\LWR@HTML@EightFlowerPetalRemoved}{\LWR@bbdingsymbol{131}} {274A}}
94 \newcommand{\LWR@HTML@EightAsterisk}{\LWR@bbdingsymbol{132}} {274B}}
95 \newcommand{\LWR@HTML@SixFlowerRemovedOpenPetal}{\LWR@bbdingsymbol{133}} {2740}}
96 \newcommand{\LWR@HTML@SparkleBold}{\LWR@bbdingsymbol{134}} {2748}}
97 \newcommand{\LWR@HTML@Sparkle}{\LWR@bbdingsymbol{135}} {2747}}
98 \newcommand{\LWR@HTML@SnowflakeChevron}{\LWR@bbdingsymbol{136}} {2744}}
99 \newcommand{\LWR@HTML@SnowflakeChevronBold}{\LWR@bbdingsymbol{137}} {2746}}
100 \newcommand{\LWR@HTML@Snowflake}{\LWR@bbdingsymbol{140}} {2744}}
101 \newcommand{\LWR@HTML@CircleSolid}{\LWR@bbdingsymbol{141}} {25CF}}
102 \newcommand{\LWR@HTML@Ellipse}{\LWR@bbdingsymbol{142}} {274D}}
103 \newcommand{\LWR@HTML@EllipseSolid}{\LWR@bbdingsymbol{143}} {25CF}}
104 \newcommand{\LWR@HTML@CircleShadow}{\LWR@bbdingsymbol{144}} {274D}}
105 \newcommand{\LWR@HTML@EllipseShadow}{\LWR@bbdingsymbol{145}} {274D}}
106 \newcommand{\LWR@HTML@Square}{\LWR@bbdingsymbol{146}} {25A1}}
107 \newcommand{\LWR@HTML@SquareSolid}{\LWR@bbdingsymbol{147}} {25A0}}
108 \newcommand{\LWR@HTML@SquareShadowBottomRight}{\LWR@bbdingsymbol{150}} {2751}}
109 \newcommand{\LWR@HTML@SquareShadowTopRight}{\LWR@bbdingsymbol{151}} {2752}}
110 \newcommand{\LWR@HTML@SquareShadowTopLeft}{\LWR@bbdingsymbol{152}} {2752}}
111 \newcommand{\LWR@HTML@SquareCastShadowBottomRight}{\LWR@bbdingsymbol{153}} {2751}}
112 \newcommand{\LWR@HTML@SquareCastShadowTopRight}{\LWR@bbdingsymbol{154}} {2752}}
113 \newcommand{\LWR@HTML@SquareCastShadowTopLeft}{\LWR@bbdingsymbol{155}} {2752}}
114 \newcommand{\LWR@HTML@TriangleUp}{\LWR@bbdingsymbol{156}} {25B2}}
115 \newcommand{\LWR@HTML@TriangleDown}{\LWR@bbdingsymbol{157}} {25BC}}
116 \newcommand{\LWR@HTML@DiamondSolid}{\LWR@bbdingsymbol{160}} {25C6}}
117 \newcommand{\LWR@HTML@OrnamentDiamondSolid}{\LWR@bbdingsymbol{161}} {2756}}
118 \newcommand{\LWR@HTML@HalfCircleRight}{\LWR@bbdingsymbol{162}} {25D7}}
119 \newcommand{\LWR@HTML@HalfCircleLeft}{\LWR@bbdingsymbol{163}} {25D6}}
120 \newcommand{\LWR@HTML@RectangleThin}{\LWR@bbdingsymbol{164}} {2758}}
121 \newcommand{\LWR@HTML@Rectangle}{\LWR@bbdingsymbol{165}} {2759}}
122 \newcommand{\LWR@HTML@RectangleBold}{\LWR@bbdingsymbol{166}} {275A}}
123 \newcommand{\LWR@HTML@ArrowBoldRightStrobe}{\LWR@bbdingsymbol{167}} {27A0}}
124 \newcommand{\LWR@HTML@ArrowBoldUpRight}{\LWR@bbdingsymbol{170}} {27A6}}
125 \newcommand{\LWR@HTML@ArrowBoldDownRight}{\LWR@bbdingsymbol{171}} {27A5}}
126 \newcommand{\LWR@HTML@ArrowBoldRightShort}{\LWR@bbdingsymbol{172}} {27A7}}
127 \newcommand{\LWR@HTML@ArrowBoldRightCircled}{\LWR@bbdingsymbol{173}} {27B2}}
128
129
130 \LWR@formatted{ScissorRightBrokenBottom}
131 \LWR@formatted{ScissorRight}
132 \LWR@formatted{ScissorRightBrokenTop}
```

```
133 \LWR@formatted{ScissorLeftBrokenBottom}
134 \LWR@formatted{ScissorLeft}
135 \LWR@formatted{ScissorLeftBrokenTop}
136 \LWR@formatted{ScissorHollowRight}
137 \LWR@formatted{ScissorHollowLeft}
138 \LWR@formatted{Phone}
139 \LWR@formatted{PhoneHandset}
140 \LWR@formatted{Tape}
141 \LWR@formatted{Plane}
142 \LWR@formatted{Envelope}
143 \LWR@formatted{HandCuffRight}
144 \LWR@formatted{HandCuffLeft}
145 \LWR@formatted{HandCuffRightUp}
146 \LWR@formatted{HandCuffLeftUp}
147 \LWR@formatted{HandRight}
148 \LWR@formatted{HandLeft}
149 \LWR@formatted{HandRightUp}
150 \LWR@formatted{HandLeftUp}
151 \LWR@formatted{Peace}
152 \LWR@formatted{HandPencilLeft}
153 \LWR@formatted{PencilRight}
154 \LWR@formatted{PencilLeft}
155 \LWR@formatted{PencilRightUp}
156 \LWR@formatted{PencilLeftUp}
157 \LWR@formatted{PencilRightDown}
158 \LWR@formatted{PencilLeftDown}
159 \LWR@formatted{NibRight}
160 \LWR@formatted{NibLeft}
161 \LWR@formatted{NibSolidRight}
162 \LWR@formatted{NibSolidLeft}
163 \LWR@formatted{Checkmark}
164 \LWR@formatted{CheckmarkBold}
165 \LWR@formatted{XSolid}
166 \LWR@formatted{XSolidBold}
167 \LWR@formatted{XSolidBrush}
168 \LWR@formatted{PlusOutline}
169 \LWR@formatted{Plus}
170 \LWR@formatted{PlusCenterOpen}
171 \LWR@formatted{PlusThinCenterOpen}
172 \LWR@formatted{Cross}
173 \LWR@formatted{CrossOpenShadow}
174 \LWR@formatted{CrossOutline}
175 \LWR@formatted{CrossBoldOutline}
176 \LWR@formatted{CrossMaltese}
177 \LWR@formatted{DavidStarSolid}
178 \LWR@formatted{DavidStar}
179 \LWR@formatted{FourAsterisk}
180 \LWR@formatted{JackStar}
181 \LWR@formatted{JackStarBold}
182 \LWR@formatted{CrossClowerTips}
183 \LWR@formatted{FourStar}
184 \LWR@formatted{FourStarOpen}
185 \LWR@formatted{FiveStarLines}
186 \LWR@formatted{FiveStar}
187 \LWR@formatted{FiveStarOpen}
```

```
188 \LWR@formatted{FiveStarOpenCircled}
189 \LWR@formatted{FiveStarCenterOpen}
190 \LWR@formatted{FiveStarOpenDotted}
191 \LWR@formatted{FiveStarOutline}
192 \LWR@formatted{FiveStarOutlineHeavy}
193 \LWR@formatted{FiveStarConvex}
194 \LWR@formatted{FiveStarShadow}
195 \LWR@formatted{AsteriskBold}
196 \LWR@formatted{AsteriskCenterOpen}
197 \LWR@formatted{AsteriskThin}
198 \LWR@formatted{AsteriskThinCenterOpen}
199 \LWR@formatted{EightStarTaper}
200 \LWR@formatted{EightStarConvex}
201 \LWR@formatted{SixStar}
202 \LWR@formatted{EightStar}
203 \LWR@formatted{EightStarBold}
204 \LWR@formatted{TwelweStar}
205 \LWR@formatted{SixteenStarLight}
206 \LWR@formatted{SixFlowerPetalRemoved}
207 \LWR@formatted{SixFlowerOpenCenter}
208 \LWR@formatted{Asterisk}
209 \LWR@formatted{SixFlowerAlternate}
210 \LWR@formatted{FiveFlowerPetal}
211 \LWR@formatted{SixFlowerPetalDotted}
212 \LWR@formatted{FiveFlowerOpen}
213 \LWR@formatted{EightFlowerPetal}
214 \LWR@formatted{SunshineOpenCircled}
215 \LWR@formatted{SixFlowerAltPetal}
216 \LWR@formatted{FourCloverOpen}
217 \LWR@formatted{FourCloverSolid}
218 \LWR@formatted{AsteriskRoundedEnds}
219 \LWR@formatted{EightFlowerPetalRemoved}
220 \LWR@formatted{EightAsterisk}
221 \LWR@formatted{SixFlowerRemovedOpenPetal}
222 \LWR@formatted{SparkleBold}
223 \LWR@formatted{Sparkle}
224 \LWR@formatted{SnowflakeChevron}
225 \LWR@formatted{SnowflakeChevronBold}
226 \LWR@formatted{Snowflake}
227 \LWR@formatted{CircleSolid}
228 \LWR@formatted{Ellipse}
229 \LWR@formatted{EllipseSolid}
230 \LWR@formatted{CircleShadow}
231 \LWR@formatted{EllipseShadow}
232 \LWR@formatted{Square}
233 \LWR@formatted{SquareSolid}
234 \LWR@formatted{SquareShadowBottomRight}
235 \LWR@formatted{SquareShadowTopRight}
236 \LWR@formatted{SquareShadowTopLeft}
237 \LWR@formatted{SquareCastShadowBottomRight}
238 \LWR@formatted{SquareCastShadowTopRight}
239 \LWR@formatted{SquareCastShadowTopLeft}
240 \LWR@formatted{TriangleUp}
241 \LWR@formatted{TriangleDown}
242 \LWR@formatted{DiamondSolid}
```

---

```

243 \LWR@formatted{OrnamentDiamondSolid}
244 \LWR@formatted{HalfCircleRight}
245 \LWR@formatted{HalfCircleLeft}
246 \LWR@formatted{RectangleThin}
247 \LWR@formatted{Rectangle}
248 \LWR@formatted{RectangleBold}
249 \LWR@formatted{ArrowBoldRightStrobe}
250 \LWR@formatted{ArrowBoldUpRight}
251 \LWR@formatted{ArrowBoldDownRight}
252 \LWR@formatted{ArrowBoldRightShort}
253 \LWR@formatted{ArrowBoldRightCircled}

```

---

#### File 43 l warp-biblatex.sty

### § 143 Package **biblatex**

*(Emulates or patches code by PHILIPP LEHMAN.)*

Pkg biblatex When **biblatex** is used, modifications from **newfloat** may have to be undone.

#### for HTML output:

1. **l warp** uses **newfloat**.
2. For classes with chapters which **newfloat** does not know about, such as CTEX-related classes, **newfloat** may modify **\addtocontents**.
3. **biblatex**, though, wants to patch **\addtocontents**, which causes an error if **\addtocontents** has been changed.
4. Therefore, **\addtocontents** is restored to its original here, since **biblatex** is about to be loaded.
5. This means that the **newfloat**'s **chapterlistsgaps** option may no longer work.

```

1 \ifdef{\newfloat@addtocontents@ORI}{%
2   \let\addtocontents\newfloat@addtocontents@ORI
3 }{}}

4 \LWR@ProvidesPackagePass{biblatex}[2018/03/04]

```

The following create hyperlinks to the references. The original code to use **hyperref** is recreated here, because **hyperref** is emulated.

```

5 \AfterPreamble{
6
7 \let\blx@anchors\empty
8 \protected\def\blx@anchor{%
9   \xifinlist{\the\c@refsection @\abx@field@entrykey}{\blx@anchors}%
10   {}%
11   {\listxadd{\blx@anchors}{\the\c@refsection @\abx@field@entrykey}%
12   \hypertarget{cite.\the\c@refsection @\abx@field@entrykey}{}}%
13 \protected\def\blx@imc@bibhyperref{%
14   \@ifnextchar[%

```

```
15      {\blx@bibhyperref}
16      {\blx@bibhyperref[\abx@field@entrykey]}%
17
18 \long\def\blx@bibhyperref[#1]{%
19 %          \blx@sfsave
20          \hyperlink{cite.\the\c@refsection}{#1}{%
21 %          \blx@sfrst
22          #2%
23 %          \blx@sfsave
24          }%
25 % \blx@sfrst%
26 }% \def\blx@nohyperref[#1]{#2}%
27
28 \protected\long\def\blx@imc@bibhyperlink#1{%
29 %          \blx@sfsave
30          \hyperlink{cite.\the\c@refsection}{#1}{%
31 %          \blx@sfrst
32          #2%
33 %          \blx@sfsave
34          }%
35 %          \blx@sfrst%
36 }%
37
38 \protected\long\def\blx@imc@bibhypertarget#1{%
39 %          \blx@sfsave%
40          \hypertarget{cite.\the\c@refsection}{#1}{%
41 %          \blx@sfrst
42          #2%
43 %          \blx@sfsave%
44          }%
45 %          \blx@sfrst%
46 }
47
48 \let\blx@ifhyperref@\firstoftwo
49 }
```

---

**File 44 l warp-bibunits.sty**

§ 144      Package **bibunits**

(Emulates or patches code by THORSTEN HANSEN.)

Pkg    bibunits    bibunits is patched for use by l warp.

**for HTML output:**    1 \LWR@ProvidesPackagePass{bibunits}[2004/05/12]  
                      2 \def\bu@bibdata{\BaseJobname}

---

**File 45 l warp-bigdelim.sty**

§ 145      Package **bigdelim**

*(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)*

Pkg **bigdelim** **bigdelim** is used as-is for print or `\textrimage`, and patched for `HTML`.

The delimiters are displayed in `HTML` by printing the delimiter, the text, and a thick border across the side of the `\multirow` which indicates the actual height of the delimiter. The delimiter character is given a `<span>` class of `l delim` or `r delim`, and the default css sets this to `font-size:200%`

 **use `\mrowcell`** `\l delim` and `\r delim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\l delim` or `\r delim`, but not in cells which are above or below the delimiter:

---

```
\begin{tabular}{lll}
<empty> & a & b \\
\l delim{\{}{\}}[.25in][left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

---

<->	a	b
	c	d
	e	f
	g	h
<->	i	j

---

For `MATHJAX`, limited emulation is provided which merely prints the delimiter and optional text in the first row.

**for HTML output** First, remove the temporary definitions of `\l delim` and `\r delim`, which were previously defined for tabular scanning in case `bigdelim` was not loaded:

```
1 \let\l delim\relax
2 \let\r delim\relax
```

Next, load the package's new definitions:

```
3 \LWR@ProvidesPackagePass{bigdelim}[2018/08/03]
```

```
\l delim {\langle 1:delimiter \rangle} {\langle 2:#rows \rangle} {\langle 3:width \rangle} [{\langle 4:text \rangle}]
\r delim
```

4 \NewDocumentCommand{\LWR@HTML@l delim}{m m m O{}}{%

---

```

5 \renewcommand{\LWR@multirowborder}{right}%
6 \multirow{#2}{#3}{#4 \InlineClass{l delim}{#1}}%
7 }
8
9 \LWR@formatted{l delim}
10
11 \NewDocumentCommand{\LWR@HTML@rdelim}{m m m O{} }{%
12 \renewcommand{\LWR@multirowborder}{left}%
13 \multirow{#2}{#3}{\InlineClass{r delim}{#1} #4}%
14 }
15
16 \LWR@formatted{r delim}

```

Limited emulation for MATHJAX. The delimiter is printed on the first row, along with any optional text.

```

17 \begin{warpMathJax}
18 % \ldelim ( [n]{width}[text]
19 \CustomizeMathJax{\newcommand{\LWRldelim}[1][]{\text{\#1}\sim\LWRbigdelim}}
20 \CustomizeMathJax{\def\ldelim#1#2#3{\def\LWRbigdelim{\#1}\LWRldelim}}
21 % \rdelim ) [n]{width}[text]
22 \CustomizeMathJax{\newcommand{\LWRrdelim}[1][]{\LWRbigdelim\sim\text{\#1}}}
23 \CustomizeMathJax{\def\rdelim#1#2#3{\def\LWRbigdelim{\#1}\LWRrdelim}}
24 \end{warpMathJax}

```

---

#### File 46 l warp-bigfoot.sty

§ 146 Package **bigfoot**

Pkg bigfoot bigfoot is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{bigfoot}[2015/08/30]

```

2 \RequirePackage{manyfoot}
3 \RequirePackage{perpage}
4
5 \def\RestyleFootnote#1#2{}
6 \def\FootnoteSpecific#1{}
7 \def\DefineFootnoteStack#1{}
8 \def\PushFootnoteMark#1{}
9 \def\PopFootnoteMark#1{}
10 \def\hfootfraction{0.9}
11 \def\vtypefraction{0.7}
12 \def\FootnoteMinimum{1sp}
13 \def\FootnoteMainMinimum{0pt}
14 \newcount\bigfoottolerance
15 \bigfoottolerance=100
16 \providecommand\footnotecarryratio{2}

```

---

**File 47 l warp-bigstrut.sty**

§ 147      Package **bigstrut**

*(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)*

Pkg **bigstrut** **bigstrut** is used as-is for print or `\textrimage`, and patched for `HTML`.

**for HTML output:** 1 \LWR@ProvidesPackagePass{bigstrut}[2018/08/03]

```
2 \LetLtxMacro{\LWR@origbigstrut}{\bigstrut}
3
4 \renewcommand{\bigstrut}[1][x]{}%
5
6 \appto{\LWR@restoreorigformatting}{%
7 \LetLtxMacro{\bigstrut}{\LWR@origbigstrut}%
8 }
9

10 \begin{warpMathJax}
11 \CustomizeMathJax{\newcommand{\bigstrut}[1][]{}}
12 \end{warpMathJax}
```

---

**File 48 l warp-bitpattern.sty**

§ 148      Package **bitpattern**

*(Emulates or patches code by JEAN-MARC BOURGUET.)*

Pkg **bitpattern** **bitpattern** is patched for use by **l warp**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{bitpattern}[2015/12/11]

```
2 \xpatchcmd{\bitpattern}
3   {\begingroup}
4   {\begin{\textrimage}[-bitpattern-\~\PackageDiagramAltText]}
5   {}
6   {\LWR@patcherror{bitpattern}{bitpattern}}
7
8 \xpatchcmd{\bp@Done}
9   {\endgroup}
10  {\end{\textrimage}}
11  {}
12  {\LWR@patcherror{bitpattern}{bp@Done}}
```

---

**File 49 l warp-blowup.sty****§ 149 Package blowup**

Pkg blowup blowup is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{blowup}[2018/01/02]  
2 \newcommand\*\blowUp[1]{}

---

**File 50 l warp-bm.sty****§ 150 Package bm**

(Emulates or patches code by DAVID CARLISLE, FRANK MITTELBACH.)

Pkg bm bm is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{bm}[2019/07/24]

\DeclareBoldMathCommand must only be used in the preamble, since it adds to the MATHJAX setup code.

```
2 \begin{warpMathJax}
3 \LetLtxMacro{\LWR@orig}{\DeclareBoldMathCommand}\ DeclareBoldMathCommand
4
5 \renewcommand{\DeclareBoldMathCommand}[3][bold]{%
6   \LWR@orig{\DeclareBoldMathCommand[#1]{#2}{#3}}%
7   \CustomizeMathJax{\newcommand{\bm}[1]{\boldsymbol{#1}}}{%
8   }%
9
10 \onlypreamble{\DeclareBoldMathCommand
11
12 \CustomizeMathJax{\newcommand{\bm}[1]{\boldsymbol{#1}}}{%
13 \end{warpMathJax}}
```

---

**File 51 l warp-booklet.sty****§ 151 Package booklet**

(Emulates or patches code by PETER WILSON.)

Pkg booklet booklet is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{booklet}[2009/09/02]

---

```

2 \newdimen\pageseplength
3 \newdimen\pagesepwidth
4 \newdimen\pagesepoffset
5 \newif\ifsidebyside    \sidebysidetrue
6 \newif\ifuselandscape \uselandscapefalse
7 \newif\ifprintoption   \printoptionfalse
8 \newcommand*\{\pagespersignature}[1]{}
9 \def\magstepminus#1{}
10 \newcommand*\{\target}[3]{}
11 \newcommand*\{\source}[3]{}
12 \newcommand*\{\setpdftargetpages}{}
13 \newcommand*\{\setdvipstargetpages}{}
14 \newcommand*\{\targettopbottom}{}
15 \newcommand*\{\twoupemptypage}{}
16 \newcommand*\{\twoupclearpage}{}
17 \newcommand*\{\checkforlandscape}{}

```

---

### File 52 l warp-bookmark.sty

#### § 152 Package **bookmark**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg bookmark **bookmark** is ignored.

**for HTML output:** Discard all options for l warp-bookmark:

```

1 \LWR@ProvidesPackageDrop{bookmark}[2016/05/17]

2 \newcommand*\{\bookmarksetup}[1]{}
3 \newcommand*\{\bookmarksetupnext}[1]{}
4 \newcommand*\{\bookmark}[2][]{}
5 \newcommand*\{\bookmarkdefinestyle}[2]{}
6 \newcommand*\{\bookmarkget}[1]{}
7 \newcommand{\BookmarkAtEnd}[1]{}

```

---

### File 53 l warp-booktabs.sty

#### § 153 Package **booktabs**

(Emulates or patches code by SIMON FEAR.)

Pkg booktabs **booktabs** is emulated during HTML output, and used as-is during print output and inside an HTML `lateximage`.

 **\cmidrule** For MATHJAX, emulation is provided in math mode, but `\cmidrule` trim must not be used.

**for HTML output:**

If `booktabs` has already been loaded before `lwarf`, such as by `memoir`, use it as-is. If not, the `lwarf` core will have placed some dummy macros which should be removed before loading the actual `booktabs` definitions.

```

1 \@ifpackageloaded{booktabs}{}{
2     \LetLtxMacro\toprule\relax
3     \LetLtxMacro\midrule\relax
4     \LetLtxMacro\cmidrule\cline
5     \LetLtxMacro\bottomrule\relax
6     \LetLtxMacro\addlinespace\relax
7     \LetLtxMacro\morecmidrules\relax
8     \LetLtxMacro\specialrule\relax
9 }
```

Next, load the `booktabs` package:

```
10 \LWR@ProvidesPackagePass{booktabs}[2019/10/08]
```

Adjust to work even if `xltabular` is loaded:

```

11 \% \def\LWR@HTML@@BLTrule{@BTnormal}
12 %
13 \% \LWR@formatted{@BLTrule}
14 \LetLtxMacro\@BLTrule@BTnormal

15 \DeclareDocumentCommand{\LWR@HTML@toprule}{o d()}{%
16     {%
17         \IfValueTF{#1}{%
18             {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
19                 {%
20                     \ifbool{FormatWP}{%
21                         {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
22                             {\booltrue{LWR@doingtbrule}}}{%
23                         }{%
24                         \LWR@getmynexttoken}%
25                     }%
26 \LWR@expandableformatted{toprule}%
27
28 \DeclareDocumentCommand{\LWR@HTML@midrule}{o d()}{%
29     {%
30         \IfValueTF{#1}{%
31             {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
32                 {%
33                     \ifbool{FormatWP}{%
34                         {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}{%
35                             {\defaddtocounter{LWR@hlines}{1}}}{%
36                         }{%
37                         \LWR@getmynexttoken}%
38
39 \LWR@expandableformatted{midrule}%
40
41 \DeclareDocumentCommand{\LWR@HTML@cmidrule}{O{\LWR@cmidrulewidth} d() m}{%
42     \LWR@docmidrule[#1](#2){#3}{%
43     \LWR@getmynexttoken%
```

For MATHJAX:

```

73 \begin{warpMathJax}
74 \CustomizeMathJax{\newcommand{\toprule}{1}[]{\hline}}
75 \CustomizeMathJax{\let\midrule\toprule}
76 \CustomizeMathJax{\let\bottomrule\toprule}
77 \CustomizeMathJax{\newcommand{\cmidrule}[2][]{}}% avoid (trim)
78 \CustomizeMathJax{\newcommand{\morecmidrules}{}}
79 \CustomizeMathJax{\newcommand{\specialrule}[3]{\hline}}
80 \CustomizeMathJax{\newcommand{\addlinespace}[1]{}}
81 \end{warpMathJax}

```

File 54 **lwarf-bophook.sty**

§ 154 Package **bophook**

Pkg bophook bophook is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{bophook}[2001/03/29]

```
2 \newcommand*{\AtBeginPage}[1]{}
3 \newcommand*{\PageLayout}[1]{}
```

---

**File 55 l warp-bounddvi.sty****§ 155 Package bounddvi**

Pkg bounddvi bounddvi is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{bounddvi}[2016/12/28]

---

**File 56 l warp-boxedminipage2e.sty****§ 156 Package boxedminipage2e**

(Emulates or patches code by SCOTT PAKIN.)

Pkg boxedminipage2e boxedminipage2e is emulated for HTML, and used as-is for lateximages.

**for HTML output:** Discard all options for l warp-boxedminipage2e:

```
1 \LWR@ProvidesPackagePass{boxedminipage2e}[2015/03/09]

2 \newenvironment{\LWR@HTML@boxedminipage}{%
3   \LWR@stoppars%
4   \begin{BlockClass}{framebox}%
5   \minipage{%
6   }%
7 {%
8   \endminipage%
9   \end{BlockClass}%
10 \LWR@startpars%
11 }%
12 \LWR@formattedenv{boxedminipage}
```

---

**File 57 l warp-braket.sty****§ 157 Package braket**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg braket braket works as-is for HTML with SVG math. For MATHJAX, emulation is provided by MATHJAX macros.

**for HTML output:** 1 \LWR@ProvidesPackagePass{braket} No date is provided by the file.

```
2 \begin{warpMathJax}%
3 \CustomizeMathJax{\newcommand{\bra}[1]{\langle#1|}}%
```

```

4 \CustomizeMathJax{\newcommand{\Bra}[1]{\left\langle \#1 \right|}}
5 \CustomizeMathJax{\newcommand{\ket}[1]{\left| \#1 \right\rangle}}
6 \CustomizeMathJax{\newcommand{\Ket}[1]{\left\langle \#1 \right\rangle}}
7 \CustomizeMathJax{\newcommand{\braket}[1]{\langle \#1 \rangle}}
8 \CustomizeMathJax{\newcommand{\Braket}[1]{\langle \#1 \rangle}}
9 \CustomizeMathJax{\newcommand{\set}[1]{\{ \#1 \}}}
10 \CustomizeMathJax{\newcommand{\Set}[1]{\{ \#1 \}}}
11 \end{warpMathJax}

```

## File 58 **lwarf-breakurl.sty**

§ 158 Package **breakurl**

(Emulates or patches code by VILAR CAMARA NETO.)

Pkg breakurl breakurl is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{breakurl}[2013/04/10]

```

2 \LetLtxMacro\burl\url
3
4 \NewDocumentCommand{\LWR@burlaltb}{O{} +m m}{%
5   \LWR@ensuredoingapar%
6   \LWR@subhyperref{#2}%
7   \LWR@subhyperreftext{#3}%
8   \endgroup% restore catcodes
9 }
10
11 \newrobustcmd*\burlalt{%
12   \begingroup%
13   \linkcatcodes%
14   \burlaltb%
15 }
16
17 \LetLtxMacro\urlalt\burlalt

```

File 59 **lwarf-breqn.sty**

§ 159 Package **breqn**

*(Emulates or patches code by MICHAEL J. DOWNES, MORTEN HØGHOLM.)*

Pkg breqn breqn is patched for use by l warp.

 **darray** darray is not supported, and in fact does not work in the print version either.

While using MATHJAX, `breqn` objects are converted to svg images.

**for HTML output:** 1 \LWR@ProvidesPackagePass{breqn}[2017/01/27]

```
2 \setkeys{breqn}{spread={5pt}}
3
4 \def\eqnumside{R}
5 % \def\eqnumplace{T}
6
7 \BeforeBeginEnvironment{dmath}{
8     \begin{BlockClass}{displaymathnumbered}
9         \LWR@newautoidanchor%
10        \booltrue{\LWR@indisplaymathimage}%
11        \begin{ lateximage }[-breqn dmath- \MathImageAltText]
12    }
13
14 \AfterEndEnvironment{dmath}{
15     \end{ lateximage }\end{BlockClass}
16 }
17
18 \BeforeBeginEnvironment{dmath*}{
19     \begin{BlockClass}{displaymath}
20         \LWR@newautoidanchor%
21        \booltrue{\LWR@indisplaymathimage}%
22        \begin{ lateximage }[-breqn dmath*- \MathImageAltText]
23    }
24
25 \AfterEndEnvironment{dmath*}{
26     \end{ lateximage }\end{BlockClass}
27 }
28
29 \BeforeBeginEnvironment{dseries}){
30     \begin{BlockClass}{displaymathnumbered}
31         \LWR@newautoidanchor%
32        \booltrue{\LWR@indisplaymathimage}%
33        \begin{ lateximage }[-breqn dseries- \MathImageAltText]
34    }
35
36 \AfterEndEnvironment{dseries}{
37     \end{ lateximage }\end{BlockClass}
38 }
39
40 \BeforeBeginEnvironment{dseries*}{
41     \begin{BlockClass}{displaymath}
42         \LWR@newautoidanchor%
43        \booltrue{\LWR@indisplaymathimage}%
44        \begin{ lateximage }[-breqn dseries*- \MathImageAltText]
45    }
46
47 \AfterEndEnvironment{dseries*}{
48     \end{ lateximage }\end{BlockClass}
49 }
50
51 \BeforeBeginEnvironment{dgroup}){
52     \begin{BlockClass}{displaymath}
53         \LWR@newautoidanchor%
54        \booltrue{\LWR@indisplaymathimage}%
55        \begin{ lateximage }[-breqn dgroup- \MathImageAltText]
56    }
```

```
57
58 \AfterEndEnvironment{dgroup}{
59   \end{lateximage}\end{BlockClass}
60 }
61
62 \BeforeBeginEnvironment{dgroup*}{
63   \begin{BlockClass}{displaymath}
64   \LWR@newautoidanchor%
65   \booltrue{\LWR@indisplaymathimage}%
66   \begin{lateximage}[-breqn dgroup*- \MathImageAltText]
67 }
68
69 \AfterEndEnvironment{dgroup*}{
70   \end{lateximage}\end{BlockClass}
71 }
```

---

**File 60 l warp-bsheaders.sty****§ 160 Package bsheaders**

Pkg bsheaders bsheaders is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{bsheaders}[1997/10/06]

---

**File 61 l warp-bxpapersize.sty****§ 161 Package bxpapersize**

Pkg bxpapersize bxpapersize is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{bxpapersize}[2017/10/08]

```
2 \providecommand*\papersizesetup{\bxpapersizesetup}
3 \newcommand*\bxpapersizesetup[1]{}
```

---

**File 62 l warp-bytefield.sty****§ 162 Package bytefield**

(Emulates or patches code by SCOTT PAKIN.)

Pkg bytefield bytefield is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{bytefield}[2017/09/15]

---

```

2 \BeforeBeginEnvironment{bytefield}{%
3   \begin{lateximage}[-bytefield-\~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{bytefield}{\end{lateximage}}

```

---

### File 63 **lwarp-cancel.sty**

#### § 163 Package **cancel**

Pkg **cancel** **cancel** is used as-is for SVG math, and emulated for HTML text output.

**for HTML output:**

```

1 \LWR@origRequirePackage{lwarp-xcolor}%
2 \LWR@ProvidesPackagePass{cancel}[2013/04/12]

```

\cancel to is math-only, so is used as-is.

```

3 \LetLtxMacro{\LWR@origcancel}{\cancel}
4 \LetLtxMacro{\LWR@origbcancel}{\bcancel}
5 \LetLtxMacro{\LWR@origxcancel}{\xcancel}
6
7 \appto{\LWR@restoreorigformatting}{%
8 \LetLtxMacro{\cancel}{\LWR@origcancel}%
9 \LetLtxMacro{\bcancel}{\LWR@origbcancel}%
10 \LetLtxMacro{\xcancel}{\LWR@origxcancel}%
11 }

```

\LWR@cancelcolor {⟨text⟩} {⟨color⟩} {⟨class⟩} {⟨colorstyle⟩} {⟨FormatWPstyle⟩}

Add colors if not empty:

```

12 \newcommand{\LWR@cancelcolor}[5]{%
13 \ifcsempty{#2}%
14 {\InlineClass{#5}{#3}{#1}}%
15 {\LWR@htmlspanclass[#5:#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}%
16 }

```

\cancel {⟨text⟩}

```

17 \DeclareRobustCommand{\cancel}[1]{%
18 \begingroup%
19 \CancelColor%
20 \LWR@findcurrenttextcolor%
21 \color{black}%
22 \LWR@cancelcolor{#1}{\LWR@tempcolor}{sout}{text-decoration-color}%
23   {text-decoration:line-through}%
24 \endgroup%
25 }
26
27 \LetLtxMacro{\bcancel}{\cancel}
28 \LetLtxMacro{\xcancel}{\cancel}

```

---

**File 64 l warp-canoniclayout.sty****§ 164 Package canoniclayout**

Pkg canoniclayout canoniclayout is ignored.

**for HTML output:** s1 \LWR@ProvidesPackageDrop{canoniclayout}[2011/11/05]

```
2 \newcommand*{\currentfontletters}{}  
3 \newcommand*{\charactersperpage}{}
```

---

**File 65 l warp-caption.sty****§ 165 Package caption**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg caption caption is patched for use by l warp.

**for HTML output:**

```
1 \typeout{---}  
2 \typeout{Packages l warp and caption:  
3 \typeout{If a ‘‘Missing \protect\begin\protect{document}\protect’’ error occurs here,  
4 \typeout{try using: \space \protect\usepackage\protect{caption\protect}\space\protect\captionsetup{opti  
5 \typeout{instead of: \protect\usepackage[options]\protect{caption\protect}.}  
6 \typeout{---}  
7  
8 \LWR@ProvidesPackagePass{caption}[2019/09/01]  
  
9 \renewcommand\caption@ibox[3]{%  
10  \@testopt{\caption@ibox{\#1}{\#2}{\#3}}{  
11 %          \wd\@tempboxa%  
12          \linewidth% l warp  
13 }%  
14 \% \LWR@traceinfo{caption@ibox: done}%  
15 }  
  
16 \long\def\caption@ibox#1#2#3[#4]{%  
17  \@testopt{\caption@iiibox{\#1}{\#2}{\#3}{\#4}}\captionbox@hj@default  
18 }  
  
19 \long\def\caption@iiibox#1#2#3#4[#5]{%  
20 \%  \setbox\@tempboxa\hbox{\#6}%  
21  \begingroup  
22 #1% set \caption@position  
23 \caption@iftop{  
24   \LWR@traceinfo{caption@iiibox top}%">  
25  \endgroup  
26  \parbox[t]{\#4}{%
```

```
27      #1\relax
28      \caption@setposition t%
29 %       \vbox{\caption#2{#3}}%
30 { \caption#2{#3} }% lwarp
31 %       \captionbox@hrule
32 %       \csname caption@hj@#5\endcsname
33 %       \unhbox\@tempboxa
34      #6% lwarp
35      }%
36 }{%
37   \LWR@traceinfo{caption@iiibox bottom}%
38 \endgroup
39 \parbox[b]{#4}{%
40      #1\relax
41      \caption@setposition b%
42 %       \csname caption@hj@#5\endcsname
43 %       \unhbox\@tempboxa
44      #6% lwarp
45 %       \captionbox@hrule
46 %       \vtop{\caption#2{#3}}%
47 { \caption#2{#3} }% lwarp
48      }%
49 }%
50 \LWR@traceinfo{caption@iiibox: done}%
51 }
52
53 % \def\caption@caption{%
54 %   \caption@iftype
55 %   {%
56 %     \caption@checkgrouplevel\@empty\caption
57 %     \caption@star
58 %     {\caption@refstepcounter\@capttype}%
59 %     {\caption@dblarg{\@caption\@capttype}}}%
60 %   {\caption@Error{\noexpand\caption outside float}%
61 %    \caption@gobble}%
62 % }
63
64 \long\def\caption@@caption#1[#2]#3{%
65   \ifcaption@star
66   \else
67   \caption@prepareanchor{#1}{#2}%
68   \memcaptioninfo{#1}{\csname the#1\endcsname}{#2}{#3}%
69   \nameuse{nag@hascaptiontrue}%
70 \fi
71
72 \par
73 \caption@beginex{#1}{#2}{#3}%
74   \caption@setfloatcapt{%
75     \caption@boxrestore
76     \if@minipage
77       \setminipage
78     \fi
79     \caption@normalsize
```

```
79      \ifcaption@star
80          \let\caption@makeanchor\@firstofone
81          #3%           lwarp
82      \else%           lwarp
83      \@makecaption{\csname fnum@\#1\endcsname}%
84                  {\ignorespaces\caption@makeanchor{#3}}%
85      \fi%           lwarp

86 % \par
87      \caption@if@minipage\@minipagetrue\@minipagefalse}%
88  \caption@end%
89 }

\caption@@@make {\langle caption label\rangle} {\langle caption text\rangle}

90 \renewcommand\caption@@@make[2]{%
91 \LWR@traceinfo{caption@@@make}%
92 %   \sbox{\tempboxa{\#1}}%
93 %   \ifdim\wd\tempboxa=\z@
94 %       \let\caption@lsep\relax
95 %   \fi
96   \caption@ifempty{#2}{%
97     \let\caption@lsep\empty
98     \let\caption@tfmt\@firstofone
99   }%
100 \caption@applyfont

\caption@fmt with plain format is defined as {\#1\#2\#3\par}:

101 %    \caption@fmt
102 { \ifcaption@star\else
103   \begin{group}
104     \captionlabelfont
105     #1%
106   \end{group}
107   \fi}%
108 { \ifcaption@star\else
109   \begin{group}
110     \caption@iflf\captionlabelfont
111     \relax
112     \caption@lsep
113   \end{group}
114   \fi}%
115 { \%
116   \captiontextfont
117 %   \caption@ifstrut
118 %   {\vrule\@height\ht\strutbox\@width\z@}%
119 %   {}%
120 %   \nobreak\hskip\z@skip % enable hyphenation
121   \caption@tfmt{#2}%
122 %   \caption@ifstrut
123 %   {\ifhmode\@finalstrut\strutbox\fi}%
124 %   {}%
125 }%
126 \LWR@traceinfo{caption@@@make done}%
```

```

127 }

\caption@@make@ { } { }

128 \renewcommand{\caption@@make@}[2]{%
129   \caption@stepthecounter
130   \caption@beginhook
131   \caption@@make{#1}{#2}%
132   \caption@endhook
133 }

\caption@makecaption

134 \long\def\caption@makecaption#1#2{%
135 %   \caption@iftop
136 %   {\vskip\belowcaptionskip}%
137 %   {\caption@rule\vskip\abovecaptionskip}%
138   \caption@@make{#1}{#2}%
139 %   \caption@iftop
140 %   {\vskip\abovecaptionskip\caption@rule}%
141 %   {\vskip\belowcaptionskip}%
142 }

143 % \DeclareCaptionBox{none}{#2}
144 \DeclareCaptionBox{parbox}{%
145 #2%
146 }
147 \DeclareCaptionBox{colorbox}{%
148 #2%
149 }

```

### File 66 **lwarp-cases.sty**

#### § 166 Package **cases**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg cases **cases** is patched for use by **lwarp**.

While using MATHJAX, **cases** objects are converted to SVG math images.

**for HTML output:** 1 \LWR@ProvidesPackagePass{cases}[2002/05/02]

```

2 \BeforeBeginEnvironment{numcases}{%
3   \begin{BlockClass}{displaymathnumbered}%
4   \LWR@newautoidanchor%
5   \booltrue{\LWR@indisplaymathimage}%
6   \begin{lateximage}[-cases- \MathImageAltText]%
7 }%
8 %
9 \AfterEndEnvironment{numcases}{%
10   \end{lateximage}\end{BlockClass}

```

---

```

11 }
12
13 \BeforeBeginEnvironment{subnumcases}{
14   \begin{BlockClass}{displaymathnumbered}
15   \LWR@newautoidanchor%
16   \booltrue{\LWR@indisplaymathimage}%
17   \begin{lateximage}[-cases- \MathImageAltText]
18 }
19
20 \AfterEndEnvironment{subnumcases}{
21   \end{lateximage}\end{BlockClass}
22 }
```

---

File 67 **l warp-centernot.sty**

§ 167 Package **centernot**

*(Emulates or patches code by HEIKO OBERDIEK.)*

Pkg centernot centernot is used as-is for SVG math, and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{centernot}[2016/05/16]

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\centernot}[1]{\not{\!#1\,}}}
4 \end{warpMathJax}
```

---

File 68 **l warp-changebar.sty**

§ 168 Package **changebar**

Pkg changebar changebar is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{changebar}[2018/03/09]

```

2 \newcommand*\cbstart(){}
3 \newcommand*\cbend(){}
4 \newenvironment*\changebar{}{}{}
5 \newcommand*\cbdelete(){}
6 \newcommand*\nochnagebars{}
7 \newcommand*\cbcolor[1] {}
8 \newlength{\changebarwidth}
9 \newlength{\deletebarwidth}
10 \newlength{\changebarsep}
11 \newcounter{changebargrey}
```

---

**File 69 l warp-changelayout.sty****§ 169 Package changelayout**

(Emulates or patches code by AHMED MUSA.)

Pkg changelayout changelayout is patched for use by l warp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{changelayout}[2009/10/07]

2 \renewrobustcmd\cpl@backtodefaults{}
3
4 \renewrobustcmd\cpl@checkifoddpage{%
5   \cpl@oddpagefalse%
6 }
7
8 \renewrobustcmd\changepagelayout[1]{%
9   \setkeys[KV]{changelay}{#1}%
10 }
11
12 \renewrobustcmd{\changetextlayout}[1]{\changepagelayout{#1}}
13
14 \renewrobustcmd\adjustpagelayout[1]{%
15   \setkeys[KV@X]{changelay}{#1}%
16 }
17
18 \renewrobustcmd{\adjusttextlayout}[1]{\adjustpagelayout{#1}}
19
20 \renewrobustcmd\adjusttextwidth[1]{%
21   \setkeys[KV]{changelay}{#1}%
22   \begin{BlockClass}[color:\LWR@colorstyle{named}]{\cpl@textcolor}{changelayout}
23     \color{\cpl@textcolor}%
24     \cpl@content
25   \end{BlockClass}
26 }
```

---

**File 70 l warp-changepage.sty****§ 170 Package changepage**

(Emulates or patches code by PETER WILSON.)

Pkg changepage changepage is ignored.

**for HTML output:** Discard all options for l warp-changepage:

```
1 \LWR@ProvidesPackageDrop{changepage}[2009/10/20]
```

---

```

2 \newif\ifoddpage
3 \DeclareRobustCommand{\checkoddpage}{\oddpagetrue}
4 \DeclareRobustCommand{\changetext}[5]{}
5 \DeclareRobustCommand{\changepage}[9]{}
6
7 \@ifundefined{adjustwidth}{}
8 \newenvironment{adjustwidth}[2]{}{}
9 \newenvironment{adjustwidth*}[2]{}{}
10 }{
11 \renewenvironment{adjustwidth}[2]{}{}
12 \renewenvironment{adjustwidth*}[2]{}{}
13 }

14 \DeclareDocumentCommand{\strictpagecheck}{}{}
15 \DeclareDocumentCommand{\easypagecheck}{}{}

```

---

### File 71 **l warp-changes.sty**

## § 171 Package **changes**

*(Emulates or patches code by EKKART KLEINOD.)*

Pkg changes changes is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{changes}[2019/01/26]

\BaseJobname is added to the label in case xr or xr-hyper are used.

```

2 \renewcommand{\ChangesListline}[4]{%
3   \IfSubStr{\Changes@loc@show}{#1}{%
4     \LWR@startpars%
5     #2: #3 \qquad%
6     \nameref{\BaseJobname-autopage-\#4}%
7     \LWR@stopars%
8   }{}%
9 }
10
11 \renewcommand{\Changes@summaryline}[4]{%
12   \IfSubStr{\Changes@loc@show}{#1}{%
13     \ifthenelse{\not\equal{\Changes@loc@style}{compactsummary} \or #2 > 0}{%
14       %
15       #3:~#2#4%
16     }{}%
17   }{}%
18 }
19
20 \xpatchcmd{\listofchanges}
21   {{\changesauthorname: \changesanonymousname}}
22   {{\LWR@textcurrentcolor{\changesauthorname: \changesanonymousname}}}
23   {}
24   {\LWR@patcherror{changes}{listofchanges A}}
25

```

```
26 \xpatchcmd{\listofchanges}
27   {\changesauthorname: \Changes@InID}
28   {\LWR@textcurrentcolor{\changesauthorname: \Changes@InID}}
29   {}
30   {\LWR@patcherror{changes}{listofchanges B}}
31
32 \xpatchcmd{\listofchanges}
33   {(\Changes@InName)}
34   {\LWR@textcurrentcolor{(\Changes@InName)}}
35   {}
36   {\LWR@patcherror{changes}{listofchanges C}}
37
38 \xpatchcmd{\listofchanges}
39   {\parbox{\Changes@summary@width}}
40   {}
41   {}
42   {\LWR@patcherror{changes}{listofchanges D}}
43
44 \xpatchcmd{\Changes@Markup@comment}
45   {%
46     \ifthenelse{\isAnonymous{#2}}%
47       {\textbf{[\arabic{Changes@commentCount}]}: } }%
48       {\textbf{[#3\arabic{Changes@commentCount}]}: } }%
49     #1%
50   }
51   {%
52     \LWR@textcurrentcolor{%
53       \ifthenelse{\isAnonymous{#2}}%
54         {\textbf{[\arabic{Changes@commentCount}]}: } }%
55         {\textbf{[#3\arabic{Changes@commentCount}]}: } }%
56     #1%
57   }%
58   {%
59   }
60   {\LWR@patcherror{changes}{\Changes@Markup@comment A}}
61
62 \xpatchcmd{\Changes@Markup@comment}
63   {%
64     \uwave{%
65       \ifthenelse{\isAnonymous{#2}}%
66         {\textbf{[\arabic{Changes@commentCount}]}: } }%
67         {\textbf{[#3\arabic{Changes@commentCount}]}: } }%
68     #1%
69   }%
70   {%
71     \LWR@textcurrentcolor{%
72       \uwave{%
73         \ifthenelse{\isAnonymous{#2}}%
74           {\textbf{[\arabic{Changes@commentCount}]}: } }%
75           {\textbf{[#3\arabic{Changes@commentCount}]}: } }%
76         #1%
77     }%
78   }%
79   {%
80   }
```

```

81      {}
82      {\LWR@patcherror{changes}{\Changes@Markup@comment_B}}
83
84 \xpatchcmd{\Changes@output}
85   {\Changes@Markup@author{\Changes@output@author{#2}{left}}}
86   {\LWR@textcurrentcolor{\Changes@Markup@author{\Changes@output@author{#2}{left}}}}
87   {}
88   {\LWR@patcherror{changes}{Changes@output_A}}
89
90 \xpatchcmd{\Changes@output}
91   {%
92     \ifthenelse{\equal{#1}{added}}{\Changes@Markup@added{#3}}{%
93     \ifthenelse{\equal{#1}{deleted}}{\Changes@Markup@deleted{#4}}{%
94     \ifthenelse{\equal{#1}{replaced}}{%
95       {\Changes@Markup@added{#3}}\allowbreak\Changes@Markup@deleted{#4}}{%
96     }{%
97     \ifthenelse{\equal{#1}{highlight}}{\Changes@Markup@highlight{#3}}{%
98   }{%
99     {%
100       \LWR@textcurrentcolor{%
101       \ifthenelse{\equal{#1}{added}}{\Changes@Markup@added{#3}}{%
102       \ifthenelse{\equal{#1}{deleted}}{\Changes@Markup@deleted{#4}}{%
103       \ifthenelse{\equal{#1}{replaced}}{%
104         {\Changes@Markup@added{#3}}\allowbreak\Changes@Markup@deleted{#4}}{%
105       }{%
106       \ifthenelse{\equal{#1}{highlight}}{\Changes@Markup@highlight{#3}}{%
107     }{%
108   }{%
109   {%
110     {\LWR@patcherror{changes}{Changes@output_B}}{%
111
112 \xpatchcmd{\Changes@output}
113   {\Changes@Markup@author{\Changes@output@author{#2}{right}}}
114   {\LWR@textcurrentcolor{\Changes@Markup@author{\Changes@output@author{#2}{right}}}}
115   {}
116   {\LWR@patcherror{changes}{Changes@output_C}}}
```

### File 72 lwarf-chappg.sty

§ 172 Package **chappg**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg chappg chappg is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{chappg}[2006/05/09]

```

2 \renewcommand{\pagenumbering}[2][]{}
3 \providecommand{\chappgsep}{--}
```

---

**File 73 l warp-chapterbib.sty****§ 173 Package chapterbib**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg chapterbib chapterbib is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{chapterbib}[2010/09/18]

```
2 \xdef\@savedjobname{\BaseJobname}
3 \let\@currentipfile\@savedjobname
```

---

**File 74 l warp-chemfig.sty****§ 174 Package chemfig**

(Emulates or patches code by CHRISTIAN TELLECHEA.)

Pkg chemfig chemfig is patched for use by l warp.

If using \polymerdelim to add delimiters to a \chemfig, wrap both inside a single \latextimage:

```
\begin{latextimage}[-chemfig-\~\PackageDiagramAltText]
\chemfig{...}
\polymerdelim[...]{...}
\end{latextimage}
```

The images are not hashed because they depend on external settings which may be changed at any time, and are unlikely to be reused inline anyhow.

**for HTML output:** 1 \LWR@ProvidesPackagePass{chemfig}

```
2
3 \catcode`\_=11
4
5 \@ifpackagelater{chemfig}{2019/04/18}%
6 {%
7   2019/04/18 or newer
8   \LetLtxMacro{\LWR@chemfig}{\origchemfig\chemfig}
9
10  \renewcommand*\chemfig[2][]{%
11    \begin{latextimage}[-chemfig-\~\PackageDiagramAltText]%
12      \LWR@chemfig{\origchemfig[#1]{#2}}%
13    \end{latextimage}%
14  }
15
```

```
16   \GlobalLetLtxMacro\LWR@chemfig@origCF_lewisc\CF_lewisc
17   \gdef\CF_lewisc#1,#2\_nil{%
18     \begin{ lateximage }[-chemfig-~\PackageDiagramAltText]%
19       \LWR@chemfig@origCF_lewisc#1,#2\_nil
20     \end{ lateximage }
21   }
22
23   \gpreto{\schemestart}{%
24     \begin{ lateximage }[-chemfig-~\PackageDiagramAltText]%
25   }
26   \gappto{\CF_schemestop}{\end{ lateximage }}
27
28 }% 2019/04/18 or newer
29 {% older than 2019/04/18
30
31   \LetLtxMacro\LWR@chemfig@origchemfig\chemfig
32
33   \DeclareDocumentCommand\chemfig{s O{} O{} m}{%
34     \begin{ lateximage }[-chemfig-~\PackageDiagramAltText]%
35     \IfBooleanTF{#1}{%
36       \LWR@chemfig@origchemfig*[#2][#3]{#4}%
37     }{%
38       \LWR@chemfig@origchemfig[#2][#3]{#4}%
39     }
40     \end{ lateximage }
41   }
42
43   \LetLtxMacro\CF@lewis@b\CF@lewis@b
44
45   \def\CF@lewis@b#1#2{%
46     \begin{ lateximage }[-chemfig-~\PackageDiagramAltText]%
47       \LWR@chemfig@origCF@lewis@b{#1}{#2}%
48     \end{ lateximage }
49   }
50
51   \preto{\schemestart}{%
52     \begin{ lateximage }[-chemfig-~\PackageDiagramAltText]%
53   }
54   \appto{\CF@schemestop}{\end{ lateximage }}
55
56 }% older than 2019/04/18
57
58 \catcode`\_=8%
59
60
61
62 \LetLtxMacro\LWR@chemfig@origchemleft\chemleft
63
64 \def\chemleft#1#2\chemright#3{%
65   \begin{ lateximage }[-chemfig-~\PackageDiagramAltText]%
66     \LWR@chemfig@origchemleft#1#2\chemright#3%
67   \end{ lateximage }
68 }
69
70 \LetLtxMacro\LWR@chemfig@origchemup\chemup
```

```

71
72 \def\chemup{\chemdown}{%
73 \begin{ lateximage }[-chemfig-~\PackageDiagramAltText]{%
74 \LWR@chemfig{origchemup}{\chemdown}{#3}%
75 \end{ lateximage }%
76 }

```

File 75 **l warp-chemformula.sty**

§ 175 Package **chemformula**

*(Emulates or patches code by CLEMENS NIEDERBERGER.)*

Pkg **chemformula** **chemformula** is patched for use by **l warp**.

The SVG images are hashed according to contents and local options. Global options are assumed to be constant document-wide.

⚠ **chemformula with MATHJAX** **chemformula** works best without MATHJAX. If MATHJAX is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The `chemformula` package adapts to `array`, but does not know about MATHJAX, and MATHJAX does not know about `chemformula`.)

While using MATHJAX, `\displaymathother` may also be used for other forms of display and inline math which contain `chemformula` expressions.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{chemformula}[2019/10/13]
2 \ExplSyntaxOn

```

`\ch` Enclose in an inline SVG image or MathJax. The `alt` tag is the contents of the `\ch` expression. The filename is hashed, and also has additional hashing information based on the local options.

```

3 \RenewDocumentCommand \ch { O{}m }
4 {%

```

To work inside `align` with `\displaymathother`, a simple version must be used to work with `chemformula`'s adaptation to `align`.

```

5 \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}{% l warp
6 {
7   \chemformula_ch:nn {#1}{#2}%
8 } original

```

If used as the outer level, must temporarily ensure MATHJAX is disabled:

```

9 {
10   \begingroup%
11   \boolfalse{mathjax}%

```

An inline image is used, adjusted for the baseline:

```
12 \LWR@subsingle$*{ l warp
```

```
13          \textbackslash{}ch\{\LWR@HTMLsanitize{\#2}\} % alt text
14      }%
15      \protect\LWR@HTMLsanitize{\detokenize\expandafter{\#1}}% add'l hashing
16  }%
17  {%
18      \chemformula_ch:nn {\#1} {\#2}%    original
19  }%
20  \endgroup%
21  }
22 }
```

\chcpd Similar to \ch.

```
23 \@ifpackagelater{chemformula}{2019/10/13}%
24 \cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
25 {
26     \begingroup%
27     \boolfalse{mathjax}%
28     \LWR@subsingledollar*{\% l warp
29         \textbackslash{}chcpd\{\LWR@HTMLsanitize{\#2}\}%
30     }%
31     \protect\LWR@HTMLsanitize{\detokenize\expandafter{\#1}}%
32 }% original
33 \group_begin:
34     \tl_if_blank:nF {\#2}
35     {
36         \keys_set:nn {chemformula} {\#1}
37         \__chemformula_save_catcodes:
38         \__chemformula_sanitize:Nn
39             \l__chemformula_chemformula_tmpa_tl
40             {\#2}
41         \__chemformula_input_compound_no_check:NV
42             \l__chemformula_compound_tl
43             \l__chemformula_chemformula_tmpa_tl
44         \__chemformula_prepare_output:NV
45             \l__chemformula_compound_tl
46             \l__chemformula_catcodes_tl
47         \chemformula_write:V \l__chemformula_compound_tl
48     }
49 \group_end:
50 }
51 \endgroup
52 }
53 }% later than 2019/10/13
54 {% earlier than 2019/10/13
55 \cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
56 {
57     \begingroup%
58     \boolfalse{mathjax}%
59     \LWR@subsingledollar*{\% l warp
60         \textbackslash{}chcpd\{\LWR@HTMLsanitize{\#2}\}%
61     }%
62         \protect\LWR@HTMLsanitize{\detokenize\expandafter{\#1}}%
63     }% original
64 \group_begin:
```

```

65      \tl_if_blank:nF {#2}
66      {
67          \keys_set:nn {chemformula} {#1}
68          \__chemformula_save_catcodes:
69          \__chemformula_sanitize:Nn
70          \l__chemformula_chemformula_tmpa_tl
71          {#2}
72          \__chemformula_input_compound_no_check:NV
73          \l__chemformula_compound_tl
74          \l__chemformula_chemformula_tmpa_tl
75          \__chemformula_prepare_output:N \l__chemformula_compound_tl
76          \chemformula_write:V \l__chemformula_compound_tl
77      }
78      \group_end:
79  }
80  \endgroup
81 }
82 }% earlier than 2019/10/13

```

\charrow If standalone, appears in a regular `lateximage`.

```

83 \RenewDocumentCommand \charrow { mO{}O{} }
84 {
85     \begin{latenteximage}[-chemformula- charrow]
86     \group_begin:
87         \__chemformula_draw_arrow:nnn {#1} {#2} {#3}
88     \group_end:
89     \end{latenteximage}
90 }

```

\chname If standalone, appears in a regular `latenteximage`, hashed according to contents.

```

91 \RenewDocumentCommand \chname { R(){}R(){} }
92 {
93     \begin{latenteximage}*[%
94         \textbackslash chname(\LWR@HTMLsanitize{#1})(\LWR@HTMLsanitize{#2})
95     ]*%
96         \chemformula_chwritebelow:nn {#1} {#2}
97     \end{latenteximage}
98 }

```

\chlewis Placed inline, hashed according to contents and options.

```

99 \RenewDocumentCommand \chlewis { O{}mm }
100 {
101     \begingroup%
102     \boolfalse{mathjax}%
103     \LWR@subsingle dollar*\textbackslash chlewis\{#2\}\{#3\}%
104     {
105         \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
106     }%
107         \chemformula_lewis:nnn {#1} {#2} {#3}%
108     }%
109     \endgroup%
110 }

```

`lwarp` redefines the \$ character, so special handling is required to escape math expressions inside `\ch`.

This boolean tracks a new kind of escaped math:

```
111 \bool_new:N      \l__chemformula_first_last_LWRdollar_bool
```

`\chemformula_input_escape_math`

Adds additional escaping for the new dollar definition:

```
112 \cs_gset_protected:Npn \__chemformula_input_escape_math:n #1
113 {
114     \__chemformula_first_last_math:n {#1}
115     \bool_if:NT \l__chemformula_first_last_dollar_bool
116     {
117         \bool_set_true:N \l__chemformula_first_last_math_bool
118         \__chemformula_read_escape_dollar:w #1 \q_nil
119     }
120     \bool_if:NT \l__chemformula_first_last_mathbraces_bool
121     {
122         \bool_set_true:N \l__chemformula_first_last_math_bool
123         \__chemformula_read_escape_mathbraces:w #1 \q_nil
124     }
```

Added by `lwarp`:

```
125 \bool_if:NT \l__chemformula_first_last_LWRdollar_bool%    lwarp
126 {
127     \bool_set_true:N \l__chemformula_first_last_math_bool%  lwarp
128     \__chemformula_read_escape_LWRdollar:w #1 \q_nil%      lwarp
129 }
130 }
```

`\chemformula_read_escape_LWRdollar`

The following parses the contents inside the new dollars.

`lwarp` keeps the dollar as its original math shift until the document starts. While `chemmacros` is being patched, the dollar must temporarily be set to its new meaning during the following definition.

```
131 \begingroup
132 \catcode`\$=\active
133
134 \cs_new_protected:Npn \__chemformula_read_escape_LWRdollar:w $#1$ \q_nil
135 {
136     \__chemformula_read_escape_math:n {#1}
137 }
138
139 \endgroup
```

`\chemformula_bool_set_if_first_last`

The following looks at the first and last tokens for delimiters to escape math inside \ch. The original definition is modified to look for the control sequences which are used by the new meaning of \$.

```

140 \cs_new_protected:Npn \__chemformula_bool_cs_set_if_first_last:NnNN #1#2#3#4
141  {
142    \int_zero:N \l__chemformula_tmpa_int
143    \int_zero:N \l__chemformula_tmpb_int
144    \int_set:Nn \l__chemformula_tmpa_int { \tl_count:n {#2} }
145    \tl_map_inline:nn {#2}
146    {
147      \int_incr:N \l__chemformula_tmpb_int
148      \int_compare:nT { \l__chemformula_tmpb_int = 1 }
149      {

```

At the start, the cs\_ version compares control sequences:

```

150          \ifdstrequal{##1}{#3}% lwarp
151          {
152            \bool_set_true:N #1
153          }% lwarp
154          {}
155        }

```

At the end, compare more control sequences:

```

156          \int_compare:nT { \l__chemformula_tmpb_int = \l__chemformula_tmpa_int }
157          {
158            \ifdstrequal{##1}{#4}
159            {}
160            {
161              \bool_set_false:N #1
162            }
163          }
164        }
165      }

```

## \chemformula\_first\_last\_math

Modified to check for the new meaning of \$ at first/last:

```

166 \cs_gset_protected:Npn \__chemformula_first_last_math:n #1
167  {
168    \bool_set_false:N \l__chemformula_first_last_math_bool
169    \bool_set_false:N \l__chemformula_first_last_dollar_bool
170    \bool_set_false:N \l__chemformula_first_last_LWRdollar_bool% lwarp
171    \bool_set_false:N \l__chemformula_first_last_mathbraces_bool
172    \__chemformula_bool_set_if_first_last:Nnnn
173    \l__chemformula_first_last_dollar_bool
174    {#1}
175    { $ } { $ }
176    \bool_if:NF \l__chemformula_first_last_dollar_bool
177    {
178      \__chemformula_bool_set_if_first_last:Nnnn
179      \l__chemformula_first_last_mathbraces_bool
180      {#1}
181      { \'( } { \) }

```

Added by l warp:

```

182      \bool_if:NF \l__chemformula_first_last_mathbraces_bool%    l warp
183      {
184          \__chemformula_bool_cs_set_if_first_last:NnNN
185          \l__chemformula_first_last_LWRdollar_bool
186          {#1}
187          { \LWR@newsingledollar } { \LWR@newsingledollar }
188      }% l warp
189  }
190 }

191 \ExplSyntaxOff

```

#### File 76 l warp-chemgreek.sty

### § 176 Package chemgreek

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemgreek chemgreek is patched for use by l warp.

**⚠ Greek symbols package selection** To use text-mode symbols, use packages `textalpha` or `textgreek`. Using the other packages supported by `chemgreek` will result in math-mode greek characters, which will result in SVG images being used. These images will be hashed.

**⚠ X<sub>E</sub>LATEX, L<sub>A</sub>TEX** If using X<sub>E</sub>LATEX or L<sub>A</sub>TEX, select the `fontspec` mapping:

```
\selectchemgreekmapping{fontspec}
```

**for HTML output:** 1 \LWR@ProvidesPackagePass{chemgreek}[2016/02/10]

```

2 \ExplSyntaxOn
3
4 \cs_gset_protected:Npn \chemgreek_text:n #1
5  { { \text {#1} } }
6
7 \appto\LWR@restoreorigformatting{%
8 \cs_set_protected:Npn \chemgreek_text:n #1%
9  { \ensuremath { \text {#1} } } }%
10 }
11
12 \ExplSyntaxOff

```

#### File 77 l warp-chemmacros.sty

### § 177 Package chemmacros

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemmacros chemmacros is patched for use by lwarp.

for HTML output 1 \LWR@ProvidesPackagePass{chemmacros}[2017/08/28]

SVG file hashing assumes that the relevant options are constant for the entire document.

### § 177.1 Changes to the user's document

⚠ \makepolymerdelims When using \makepolymerdelims, enclose the entire expression inside a polymerdelims environment, such as (from the chemmacros manual):

```
\begin{polymerdelims}
\chemfig{-[@{op,.75}]CH_2-CH(-[6]Cl)-[@{cl,0.25}]}
\makepolymerdelims{5pt}{27pt}{op}{cl}
\end{polymerdelims}
```

⚠ redox reactions Redox reactions must be enclosed inside a redoxreaction environment. For print output, extra space must be included above and/or below the result, so they are declared as arguments to the environment, instead of being manually entered as per the chemmacros manual. For HTML output, the extra space is ignored and a lateximage is used instead.

```
\begin{redoxreaction}{7mm}{7mm}
\OX{a,Na} $\rightarrow$ \OX{b,Na}\pch\redox(a,b){oxidation}
\end{redoxreaction}
```

### § 177.2 Code

### § 177.3 Loading modules

Patching chemmacros modules must be done \AtBeginDocument, since modules are invoked by the user in the preamble, and each patch is only done if the module is loaded.

```
2 \ExplSyntaxOn
3
4 \newcommand{\ifchemmacrosmoduleloaded}[1]{%
5   \@ifl@aded{\c__chemmacros_module_extension_tl}{\c__chemmacros_module_prefix_tl.\#1}%
6 }
7
8 \ExplSyntaxOff
```

## § 177.4 New environments

`\makepolymerdelims` and redox reactions must be enclosed in a `lateximage` during HTML output. These environments are provided here in HTML mode, and in the `l warp` core in print mode, as a high-level semantic syntax which automatically embeds the contents in a `lateximage` with an appropriate `alt` tag.

Env `polymerdelims`

```
9 \DeclareDocumentEnvironment{polymerdelims}{}  
10 {\begin{lateximage}[-chemmacros- polymer]}  
11 {\end{lateximage}}
```

Env `redoxreaction` *{<space above>} {<space below>}*

For HTML output, the above and below space is ignored, and a `lateximage` is used instead. For the print output version, see section 86.

```
12 \DeclareDocumentEnvironment{redoxreaction}{m m}  
13 {\begin{lateximage}[-chemmacros- redoxreaction]}  
14 {\end{lateximage}}
```

```
15 \ExplSyntaxOn
```

## § 177.5 Acid-base

```
16 \AtBeginDocument{  
17 @ifchemmacrosmoduleloaded[acid-base]{  
18 \PackageInfo{l warp}{Patching~chemmacros~module~acid-base}  
19  
20 \cs_gset_protected:Npn \chemmacros_p:n #1  
21 {  
22   \begingroup  
23   \boolfalse{mathjax}  
24   \LWR@subsingledollar*{  
25     \textbackslash{}p\{\LWR@HTMLsanitize{\#1}\}\}  
26   }{  
27     \chemmacrosp\protect\LWR@HTMLsanitize{\detokenize\expandafter{\#1}}%  
28   }{  
29   \group_begin:  
30     \mbox  
31     {  
32       \chemmacros_p_style:n {p}  
33       \ensuremath {\#1}  
34     }  
35   \group_end:  
36 }  
37 \endgroup  
38 }  
39  
40 \RenewDocumentCommand \pH {} {  
41   \begingroup  
42   \boolfalse{mathjax}  
43   \LWR@subsingledollar*{\textbackslash{}pH}{chemmacros}{  
44     \chemmacros_p:n { \chemmacros_chemformula:n {H} } }
```

```
45      }
46      \endgroup
47 }
48
49 \RenewDocumentCommand \pOH {} {
50   \begingroup
51   \boolfalse{mathjax}
52   \LWR@subsingledollar*\{\textbackslash{}pOH\}{chemmacros}%
53     \chemmacros_p:n { \chemmacros_chemformula:n {OH} }%
54   }
55   \endgroup
56 }
57
58 \RenewDocumentCommand \pKa {O{}} {
59   {
60     \begingroup
61     \boolfalse{mathjax}
62     \LWR@subsingledollar*\{\textbackslash{}pKa{[]}\}{chemmacros #1}%
63       \chemmacros_p:n
64       {
65         \Ka \ifblank {\#1} {}
66         { {} \c_math_subscript_token { \chemmacros_bold:n {\#1} } }%
67       }
68     }
69     \endgroup
70   }
71
72 \RenewDocumentCommand \pKb {O{}} {
73   {
74     \begingroup
75     \boolfalse{mathjax}
76     \LWR@subsingledollar*\{\textbackslash{}pKb{[]}\}{chemmacros #1}%
77       \chemmacros_p:n
78       {
79         \Kb \ifblank {\#1} {}
80         { {} \c_math_subscript_token { \chemmacros_bold:n {\#1} } }%
81       }
82     }
83     \endgroup
84   }
85
86 \LetLtxMacro \LWR@chemmacros@origKa \Ka
87 \renewcommand*{\Ka}{%
88   \begingroup
89   \boolfalse{mathjax}
90   \LWR@subsingledollar*\{\textbackslash{}Ka\}{chemmacros}%
91     \LWR@chemmacros@origKa%
92   }%
93   \endgroup
94 }
95
96 \LetLtxMacro \LWR@chemmacros@origKb \Kb
97 \renewcommand*{\Kb}{%
98   \begingroup
99   \boolfalse{mathjax}
```

```

100   \LWR@subsingledollar*\{\textbackslash\}Kb\}{chemmacros}\{%
101     \LWR@chemmacros@origKb\%
102   }%
103   \endgroup
104 }
105
106 \LetLtxMacro{\LWR@chemmacros@origKw\Kw
107 \renewcommand*\{\Kw}\{%
108   \begingroup
109   \boolfalse{mathjax}
110   \LWR@subsingledollar*\{\textbackslash\}Kw\}{chemmacros}\{%
111     \LWR@chemmacros@origKw
112   }%
113   \endgroup
114 }
115
116 }\}\%\@ifchemmacrosmoduleloaded
117 }\%\AtBeginDocument

```

## § 177.6 Charges

```

118 \AtBeginDocument{
119 \ifchemmacrosmoduleloaded{charges}\{
120 \PackageInfo{lwarp}{Patching~chemmacros~module~charges}
121
122 \cs_gset_protected:Npn \fplus {
123   \begingroup
124   \boolfalse{mathjax}
125   \LWR@subsingledollar*\{\textbackslash\}fplus\}{chemmacros}\{%
126   \LWR@origensuredmath{\chemformula_fplus:}%
127   \endgroup
128 }
129 \cs_gset_protected:Npn \fminus {
130   \begingroup
131   \boolfalse{mathjax}
132   \LWR@subsingledollar*\{\textbackslash\}fminus\}{chemmacros}\{%
133   \LWR@origensuredmath{\chemformula_fminus:}%
134   \endgroup
135 }
136
137 }\}\%\@ifchemmacrosmoduleloaded
138 }\%\AtBeginDocument

```

## § 177.7 Nomenclature

```

139 \AtBeginDocument{
140 \ifchemmacrosmoduleloaded{nomenclature}\{
141 \PackageInfo{lwarp}{Patching~chemmacros~module~nomenclature}
142
143 \cs_gset_protected:Npn \chemmacros_charge:n #1
144 {
145   \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}
146   {\chemmacros_chemformula:n { {}^{#1} } }
147   {
148     \ifmmode

```

```
149          {\chemmacros_chemformula:n { {}^{\#1} }}
```

```
150      \else
151          { \textsuperscript{\ensuremath{\#1}} }
```

```
152      \fi
153  }
154 }
155
156
157 \LetLtxMacro{\LWR@chemmacros@origchemprime}{\chemprime}
158
159 \protected\def\chemprime {\HTMLUnicode{2032}}
160
161 \appto{\LWR@restoreorigformatting}{%
162 \LetLtxMacro{\chemprime}{\LWR@chemmacros@origchemprime}%
163 }

164 \ChemCompatibilityFrom{5.8}
165 \cs_gset_protected:Npn \__chemmacros_cip:n #1
166 {
167     \tl_set:Nn \l__chemmacros_tmpa_tl {\#1}
168     \int_step_inline:nnnn {0} {1} {9}
169     {
170         \tl_replace_all:Nnn \l__chemmacros_tmpa_tl
171             {##1}
172             { \l__chemmacros_cip_number_tl ##1 }
173     }
174 {
175     \l__chemmacros_cip_inner_tl
176     \LWR@textcurrentcolor{\LWR@textcurrentfont\% lwarp
177         \l__chemmacros_tmpa_tl
178     }\% lwarp
179 }
180 }
181 \EndChemCompatibility

182 \RenewDocumentCommand \Sconf { O{S} } {
183 \begin{latextimage}[\textbackslash{}Sconf{[]}\#1{}]]*
184     \chemmacros_sconf:n {\#1}
185 \end{latextimage}
186 }
187
188 \RenewDocumentCommand \Rconf { O{R} } {
189 \begin{latextimage}[\textbackslash{}Rconf{[]}\#1{}]]*
190     \chemmacros_rconf:n {\#1}
191 \end{latextimage}
192 }

193 \cs_gset_protected:Npn \chemmacros_hapo:n #1
194 {
195     \begingroup
196     \boolfalse{mathjax}
197     \LWR@subsingleollar*\textbackslash{}hapo{\#1}{chemmacros}(
198         \chemmacros_coordination_symbol:nnnn
199         { \l__chemmacros_coord_use_hyphen_bool }
200         {
201             \chemmacros_if_compatibility:nnTF {>} {5.7}
```

```

202           { \c_true_bool }
203           { \c_false_bool }
204       }
205       { \chemeta }
206       {#1}
207   }
208   \endgroup
209 }
210
211 \cs_gset_protected:Npn \chemmacros_dento:n #1
212 {
213     \begingroup
214     \boolfalse{mathjax}
215     \LWR@subsingledollar*\{\textbackslash{}dento\{#1\}\}{chemmacros}%
216         \chemmacros_coordination_symbol:nnn
217         { \l_chemmacros_coord_use_hyphen_bool }
218         {
219             \chemmacros_if_compatibility:nTF {>} {5.7}
220             { \c_true_bool }
221             { \c_false_bool }
222         }
223         { \chemkappa }
224         {#1}
225     }
226     \endgroup
227 }
228
229 \cs_gset_protected:Npn \chemmacros_bridge:n #1
230 {
231     \begingroup
232     \boolfalse{mathjax}
233     \LWR@subsingledollar*\{\textbackslash{}bridge\{#1\}\}{chemmacros}%
234         \chemmacros_coordination_symbol:nnn
235         { \l_chemmacros_coord_use_hyphen_bool }
236         { \l_chemmacros_bridge_super_bool }
237         { \chemmu }
238         {#1}
239     }
240     \endgroup
241 }
242 }% \ifchemmacrosmoduleloaded
243 }% AtBeginDocument

```

## § 177.8 Particles

```

244 \AtBeginDocument{
245 @ifchemmacrosmoduleloaded{particles}%
246 \PackageInfo{lwarp}{Patching~chemmacros~module~particles}
247
248 \cs_gset_protected:Npn \chemmacros_declare_nucleophile:Nn #1#2
249 {
250     \cs_set_protected:cpx {__chemmacros_ \chemmacros_remove_underslash:N #1:}%
251     {
252         \bool_if:NTF \l_chemmacros_nucleophile_elpair_bool
253         {
254             \chemmacros_elpair:n { #2 }

```

```

255           \chemmacros_if_compatibility:nnT {>=}{5.3}
256           { \skip_horizontal:N \l__chemmacros_nucleophile_dim }
257           \chemmacros_chemformula:n { {}^{\{-\}} }
258       }
259       { \chemmacros_chemformula:n { #2^{\{-\}} } }
260   }
261 \DeclareDocumentCommand #1 {o}
262 {
263     \begin{latextimage}%
264     \group_begin:%
265         \IfNoValueF {##1}%
266         { \chemmacros_set_keys:nn {particles}{##1} }%
267         \use:c {__chemmacros_ \chemmacros_remove_backslash:N #1:}%
268     \group_end:%
269     \end{latextimage}%
270 }
271 }
272
273 \RenewChemNucleophile \Nuc {Nu}
274 \RenewChemNucleophile \ba {ba}
275
276 }{}% \ifchemmacrosmoduleloaded
277 }% AtBeginDocument

```

### § 177.9 Phases

```

278 \AtBeginDocument{
279 \ifchemmacrosmoduleloaded{phases}%
280 \PackageInfo{lwarp}{Patching~chemmacros~module~phases}
281
282 \cs_undefine:N \chemmacros_phase:n
283 \cs_new_protected:Npn \chemmacros_phase:n #1
284 {
285     \mode_leave_vertical:
286     \bool_if:NTF \l__chemmacros_phases_sub_bool
287     {
288         \ifnumequal{\value{LWR@latextimedepth}}{0}
289         {
290             \textsubscript{ (#1) }
291         }
292         {
293             \chemformula_subscript:n { (#1) }
294         }
295     }
296     {
297         \skip_horizontal:N \l__chemmacros_phases_space_dim
298         \chemmacros_text:n { (#1) }
299     }
300 }
301
302 }{}% \ifchemmacrosmoduleloaded
303 }% AtBeginDocument

```

## § 177.10 Mechanisms

```
304 \AtBeginDocument{  
305 \@ifchemmacrosmoduleloaded{mechanisms}{  
306 \PackageInfo{lwarp}{Patching~chemmacros~module~mechanisms}  
307  
308 \chemmacros_define_keys:nn {textmechanisms}  
309 {  
310     type      .choice: ,  
311     type /    .code:n   =  
312     {  
313         \__chemmacros_set_mechanisms:nnn { S }  
314         {  
315             \textsubscript{N}  
316         }  
317         { }  
318     } ,  
319     type / 1 .code:n   =  
320     {  
321         \__chemmacros_set_mechanisms:nnn { S }  
322         {  
323             \textsubscript{N}  
324             1  
325         }  
326         { }  
327     } ,  
328     type / 2 .code:n   =  
329     {  
330         \__chemmacros_set_mechanisms:nnn { S }  
331         {  
332             \textsubscript{N}  
333             2  
334         }  
335         { }  
336     } ,  
337     type / se .code:n   =  
338     {  
339         \__chemmacros_set_mechanisms:nnn { S }  
340         {  
341             \textsubscript{E}  
342         }  
343         { }  
344     } ,  
345     type / 1e .code:n   =  
346     {  
347         \__chemmacros_set_mechanisms:nnn { S }  
348         {  
349             \textsubscript{E}  
350             1  
351         }  
352         { }  
353     } ,  
354     type / 2e .code:n   =  
355     {  
356         \__chemmacros_set_mechanisms:nnn { S }  
357         { }
```

```
358           \textsubscript{E}
359           2
360       }
361     { }
362   } ,
363 type / ar .code:n    =
364 {
365   \chemmacros_set_mechanisms:nnn { S }
366   {
367     \textsubscript{E}
368   }
369   { Ar - }
370 } ,
371 type / e .code:n    =
372 { \chemmacros_set_mechanisms:nnn { E } { } { } } ,
373 type / e1 .code:n   =
374 { \chemmacros_set_mechanisms:nnn { E } { 1 } { } } ,
375 type / e2 .code:n   =
376 { \chemmacros_set_mechanisms:nnn { E } { 2 } { } } ,
377 type / cb .code:n   =
378 {
379   \chemmacros_set_mechanisms:nnn { E }
380   {
381     1
382     \textsubscript{cb}
383   }
384   { }
385 } ,
386 type      .default:n =
387 }
388
389 \cs_gset_protected:Npn \chemmacros_mechanisms:n #1
390 {
391   \tl_if_blank:nTF {#1}
392   { \chemmacros_set_keys:nn {textmechanisms} { type } }
393   { \chemmacros_set_keys:nn {textmechanisms} { type = #1 } }
394 \mbox
395 {
396   \tl_use:N \l_chemmacros_mechanisms_ar_tl
397   \tl_use:N \l_chemmacros_mechanisms_type_tl
398   \tl_use:N \l_chemmacros_mechanisms_mol_tl
399 }
400 }
401
402 \appto\LWR@restoreorigformatting{%
403 \cs_set_protected:Npn \chemmacros_mechanisms:n #1%
404 {
405   \tl_if_blank:nTF {#1}%
406   { \chemmacros_set_keys:nn {mechanisms} { type } }%
407   { \chemmacros_set_keys:nn {mechanisms} { type = #1 } }%
408 \mbox%
409 {
410   \tl_use:N \l_chemmacros_mechanisms_ar_tl%
411   \tl_use:N \l_chemmacros_mechanisms_type_tl%
412   \tl_use:N \l_chemmacros_mechanisms_mol_tl%
```

---

```

413      }%
414  }%
415 }
416
417 }{ }% \@ifchemmacrosmoduleloaded
418 }% AtBeginDocument

```

### § 177.11 Newman

```

419 \AtBeginDocument{
420 \@ifchemmacrosmoduleloaded{newman}{
421 \PackageInfo{lwarf}{Patching~chemmacros~module~newman}
422
423 \RenewDocumentCommand \newman {od()m}%
424 {
425   \IfValueTF{#2}
426   {\begin{ lateximage }[\textbackslash newman{#2}\{#3\}]*
427   {\begin{ lateximage }[\textbackslash newman\{#3\}]*
428     \group_begin:
429       \IfNoValueF {#1} { \chemmacros_set_keys:nn {newman} {#1} }
430       \IfNoValueTF {#2}
431         { \chemmacros_newman:nn { } {#3} }
432         { \chemmacros_newman:nn {#2} {#3} }
433     \group_end:
434     \end{ lateximage }
435   }%
436
437 }{ }% \@ifchemmacrosmoduleloaded
438 }% AtBeginDocument

```

### § 177.12 Orbital

```

439 \AtBeginDocument{
440 \@ifchemmacrosmoduleloaded{orbital}{
441 \PackageInfo{lwarf}{Patching~chemmacros~module~orbital}
442
443 \RenewDocumentCommand \orbital {om}%
444 {
445   \IfValueTF{#1}
446   {
447     \begin{ lateximage }[%]
448       \textbackslash orbital{[]}\LWR@HTMLsanitize{#1}{[]}\{#2\}%
449     ]*[[]][margin-left: 1em ; margin-right: 1em]
450   }
451   {
452     \begin{ lateximage }[%]
453       \textbackslash orbital\{#2\}%
454     ]*[[]][margin-left: 1em ; margin-right: 1em]
455   }
456   \group_begin:
457     \chemmacros_set_keys:nn {orbital/type} {#2}
458     \IfNoValueTF {#1}
459       { \chemmacros_orbital:n { } }
460       { \chemmacros_orbital:n {#1} }
461   \group_end:

```

```

462     \end{lateximage}
463 }
464
465 }{}% \@ifchemmacrosmoduleloaded
466 }% AtBeginDocument

```

### § 177.13 Reactions

```

\chemmacros_declare_reaction_env {<chem>} {<math>} {<args number>} {<argument list (#2){#3}...>}

467 \AtBeginDocument{
468 \@ifchemmacrosmoduleloaded{reactions}%
469 \PackageInfo{l warp}{Patching~chemmacros~module~reactions}
470
471 \cs_gset_protected:Npn \chemmacros_declare_reaction_env:nnnn #1#2#3#4
472 {
473     \exp_args:Nnx \DeclareDocumentEnvironment {#1} { O{} \prg_replicate:nn {#3+0} {m} }
474     {
475         \boolfalse{mathjax}%
476         \ifdefvoid{\LWR@ThisAltText}{%
477             \ThisAltText{-chemmacros~-reaction}%
478         }{}%
479         \chemmacros_add_reaction_description:n {##1}
480         \__chemmacros_begin_reaction:
481         \chemmacros_reaction_read:nw {#2} {#4}
482     }
483     {
484         \__chemmacros_end_reaction:
485         \gdef\!{\LWR@ThisAltText}{}%
486     }
487 }
488 \cs_generate_variant:Nn \chemmacros_declare_reaction_env:nnnn {nnnV}
489
490 \RenewChemReaction {reaction} {equation}
491 \RenewChemReaction {reaction*} {equation*}
492 \RenewChemReaction {reactions} {align}
493 \RenewChemReaction {reactions*} {align*}
494
495 }{}% \@ifchemmacrosmoduleloaded
496 }% AtBeginDocument

```

### § 177.14 Redox

```

497 \AtBeginDocument{
498 \@ifchemmacrosmoduleloaded{redox}%
499 \PackageInfo{l warp}{Patching~chemmacros~module~redox}
500
501 \NewDocumentCommand \LWR@chemmacros@ox { s m >{\SplitArgument{1}{,}}m }
502 {
503     \IfBooleanTF {#1}
504     { \chemmacros_ox:nnnn {#1} {#2} #3 }
505     { \chemmacros_ox:nnnn { } {#2} #3 }
506 }
507
508 \RenewDocumentCommand \ox { s O{} m }

```

```

509  {
510    \begingroup
511    \boolfalse{mathjax}
512    \IfBooleanTF {#1}
513    {
514      \LWR@subsingle$*{%
515        \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}}% alt
516      }{%
517        star \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
518      }{%
519        \LWR@chemmacros@ox* {#2} {#3}% contents
520      }%
521    }%
522    {%
523      \LWR@subsingle$*{%
524        \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}}% alt
525      }{%
526        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
527      }{%
528        \LWR@chemmacros@ox {#2} {#3}% contents
529      }%
530    }
531    \endgroup
532  }%
533 }{%
534 }% \ifchemmacrosmoduleloaded
535 }% AtBeginDocument

```

### § 177.15 Scheme

Fix for chemmacros as of v5.8b, when using newfloat and babel:

```

536 \AtBeginDocument{%
537 \ifchemmacrosmoduleloaded{scheme}{%
538 \PackageInfo{lwarp}{Patching~chemmacros~module~scheme}}
539 \ifdefstring{\schemename}{los}{%
540 \SetupFloatingEnvironment{scheme}{%
541 name = \chemmacros_translate:n {scheme-name}%
542 }%
543 }{%
544 }%
545 }% \ifchemmacrosmoduleloaded
546 }% AtBeginDocument
547 
```

### § 177.16 Spectroscopy

```
548 \AtBeginDocument{  
549 \@ifchemmacrosmoduleloaded{spectroscopy}{  
550 \PackageInfo{lwarf}{Patching~chemmacros~module~spectroscopy}  
551  
552 \ChemCompatibilityTo{5.8}  
553 \cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2  
554 {  
555     \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl  
556     {  
557         \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }  
558         \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }  
559     }  
560     \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}  
561 %     \chemmacros_chemformula:n { ^{#1} }  
562     \textsuperscript{#1}  
563     \bool_if:NTF \l__chemmacros_nmr_parse_bool  
564     { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }  
565     { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }  
566     \tl_use:N \l__chemmacros_nmr_element_method_connector_tl  
567     \tl_use:N \l__chemmacros_nmr_method_tl  
568 }  
569 \EndChemCompatibility  
570 \ChemCompatibilityFrom{5.8}  
571 \cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2  
572 {  
573     \group_begin:  
574         \tl_use:N \l__chemmacros_nmr_base_format_tl  
575         \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl  
576         {  
577             \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }  
578             \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }  
579         }  
580         \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}  
581 %         \chemmacros_chemformula:n { ^{#1} }  
582         \textsuperscript{#1}  
583         \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl  
584         {  
585             \bool_if:NTF \l__chemmacros_nmr_parse_bool  
586             { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }  
587             { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }  
588         }  
589         \tl_use:N \l__chemmacros_nmr_element_method_connector_tl  
590         \tl_use:N \l__chemmacros_nmr_method_tl  
591     \group_end:  
592 }  
593 \EndChemCompatibility  
594  
595  
596 \cs_gset_protected:Npn \chemmacros_nmr_position:n #1  
597 {  
598     \chemmacros_chemformula:x  
599     {  
600         \exp_not:V \g__chemmacros_nmr_element_tl  
601         \bool_if:NF \l__chemmacros_nmr_position_side_bool
```

```
602      {
603          \tl_if_eq:NnTF \l__chemmacros_nmr_position_tl {^}% lwarp
604          { \textsuperscript{\exp_not:n { \#1 } } }% lwarp
605          { \textsubscript{\exp_not:n { \#1 } } }% lwarp
606 %          \exp_not:V \l__chemmacros_nmr_position_tl
607 %          \exp_not:n { \#1 }
608      }
609  }
610 \bool_if:NT \l__chemmacros_nmr_position_side_bool
611  {
612      \tl_use:N \l__chemmacros_nmr_position_tl
613      \l__chemmacros_nmr_position:n {#1}
614  }
615 }
616
617 \cs_gset_protected:Npn \l__chemmacros_nmr_coupling:w (#1;#2)
618  {
619      \tl_set:Nn \l__chemmacros_nmr_coupling_bonds_tl
620      {
621          \l__chemmacros_nmr_coupling_bonds_pre_tl
622          #1
623          \l__chemmacros_nmr_coupling_bonds_post_tl
624      }
625 \bool_if:NTF \l__chemmacros_nmr_coupling_nuclei_sub_bool
626  {
627      \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
628      {
629 %          \c_math_subscript_token
630          \textsubscript% lwarp
631          {
632              \l__chemmacros_nmr_coupling_nuclei_pre_tl
633              \chemmacros_chemformula:n {#2}
634              \l__chemmacros_nmr_coupling_nuclei_post_tl
635          }
636      }
637  }
638  {
639      \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
640      {
641          \l__chemmacros_nmr_coupling_nuclei_pre_tl
642          \chemmacros_chemformula:n {#2}
643          \l__chemmacros_nmr_coupling_nuclei_post_tl
644      }
645  }
646  \l__chemmacros_nmr_coupling_aux_i:w
647 }
648 \AfterEndPreamble{%
649 % \NMR{<num>,<elem>}(<num>,<unit>)[<solvent>] ALL arguments are optional
650 % \NMR* same but without ": $delta$" at end
651 \cs_gset_protected:Npn \chemmacros_nmr:nnnn #1#2#3#4
652  {
653      \bool_if:NT \l__chemmacros_nmr_list_bool { \item \scan_stop: }
654      \group_begin:
655          \mode_leave_vertical:
```

```
656          \bool_set_false:N \l_chemmacros_nmr_frequency_bool
657          \bool_set_false:N \l_chemmacros_nmr_solvent_bool
658          \tl_if_empty:nF {#3}
659          { \bool_set_true:N \l_chemmacros_nmr_frequency_bool }
660          \tl_if_empty:nF {#4}
661          { \bool_set_true:N \l_chemmacros_nmr_solvent_bool }
662          \bool_if:nT
663          {
664              \l_chemmacros_nmr_frequency_bool
665              ||
666              \l_chemmacros_nmr_solvent_bool
667          }
668          { \bool_set_true:N \l_chemmacros_nmr_delimiters_bool }
669          \bool_if:nT
670          {
671              \l_chemmacros_nmr_frequency_bool
672              &&
673              \l_chemmacros_nmr_solvent_bool
674          }
675          { \bool_set_true:N \l_chemmacros_nmr_comma_bool }
676          \tl_if_empty:nTF {#2}
677          {
678              \__chemmacros_nmr_nucleus:VV
679              \l_chemmacros_nmr_isotope_default_tl
680              \l_chemmacros_nmr_element_default_tl
681          }
682          { \__chemmacros_nmr_nucleus:w #2 \q_stop }
683          \mode_if_math:TF
684          {
685              \text
686              {
687                  \group_begin:
688                  \tl_use:N \l_chemmacros_nmr_format_tl
689 \LWR@textcurrentcolor{\LWR@textcurrentfont{%
690             \__chemmacros_nmr_base:VV
691             \g__chemmacros_nmr_isotope_tl
692             \g__chemmacros_nmr_element_tl
693             \bool_if:NT \l_chemmacros_nmr_delimiters_bool
694             { ~ ( } }
695             \bool_if:NT \l_chemmacros_nmr_frequency_bool
696             { \__chemmacros_nmr_frequency:n {#3} }
697             \bool_if:NT \l_chemmacros_nmr_comma_bool
698             { , ~ }
699             \bool_if:NT \l_chemmacros_nmr_solvent_bool
700             { \chemmacros_chemformula:n {#4} }
701             \bool_if:NT \l_chemmacros_nmr_delimiters_bool
702             { ) }
703             \tl_if_blank:nT {#1} {::~}
704 }% lwarp
705             \group_end:
706         }
707         \tl_if_blank:nT {#1}
708         {
709             \delta
710             \text { \l_chemmacros_nmr_delta_tl }
```

```
711           \bool_if:NT \l__chemmacros_nmr_use_equal_bool {=}
712       }
713   }
714 {
715     \group_begin:
716     \tl_use:N \l__chemmacros_nmr_format_tl
717 \LWR@textcurrentcolor{\LWR@textcurrentfont{%
718   \lwarp
719   \g__chemmacros_nmr_base:VV
720   \g__chemmacros_nmr_isotope_tl
721   \g__chemmacros_nmr_element_tl
722   \bool_if:NT \l__chemmacros_nmr_delimiters_bool
723   {~()}
724   \bool_if:NT \l__chemmacros_nmr_frequency_bool
725   { \__chemmacros_nmr_frequency:n {#3} }
726   \bool_if:NT \l__chemmacros_nmr_comma_bool
727   {,~}
728   \bool_if:NT \l__chemmacros_nmr_solvent_bool
729   {
730     \bool_if:NTF \l__chemmacros_nmr_parse_bool
731
732 %           { \chemformula_ch:nn { } {#4} }% original
733           {\ch{#4}}% \lwarp
734           {#4}
735       }
736     \bool_if:NT \l__chemmacros_nmr_delimiters_bool
737     {()}

738 }% \lwarp
739 \tl_if_blank:nT {#1} {:}
740 \group_end:
741 \tl_if_blank:nT {#1}
742 {
743   \tl_use:N \c_space_tl
744   \c_math_toggle_token
745   \delta
746   \c_math_toggle_token
747   \l__chemmacros_nmr_delta_tl
748   \bool_if:NT \l__chemmacros_nmr_use_equal_bool {~=}
749 }
750 \group_end:
751 }% AfterEndPreamble
752
753
754 \RenewDocumentCommand \chemmacros_data:w { smo }
755 {
756   \bool_if:NT \l__chemmacros_nmr_list_bool { \item }
757   {
758 %       \tl_use:N \l__chemmacros_nmr_format_tl #2
759       \tl_use:N \l__chemmacros_nmr_format_tl
760       \LWR@textcurrentcolor{\LWR@textcurrentfont{%
761         \lwarp
762         #2
763         \IfNoValueF {#3} { ~ ( #3 ) }
764         \IfBooleanT {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { : } }
765       }}% \lwarp
```

```

765      }
766      \IfBooleanF {#1} { \bool_if:NT \l__chemm macros_nmr_use_equal_bool { ~ = } }
767  }
768
769 }{}% \@ifchemm macrosmoduleloaded
770 }% AtBeginDocument

```

### § 177.17 Thermodynamics

```

771 \AtBeginDocument{
772 \@ifchemm macrosmoduleloaded{thermodynamics}%
773 \PackageInfo{l warp}{Patching~chemm macros~module~thermodynamics}
774
775 \cs_gset_protected:Npn \chemm macros_state:nn #1#2
776 {
777   \group_begin:
778   \boolfalse{mathjax}
779   \chemm macros_set_keys:nn {thermodynamics} {#1}
780   \LWR@subsingle dollar*{%
781     \textbackslash state{\LWR@HTMLsanitize{#2}}%
782   }{%
783     chemm macros_state% add'l hashing
784     #1% options
785     LSP \tl_use:N \l__chemm macros_state_sp_left_tl% super/subscripts
786     LSB \tl_use:N \l__chemm macros_state_sb_left_tl
787     RSP \tl_use:N \l__chemm macros_state_sp_right_tl
788     RSB \tl_use:N \l__chemm macros_state_sb_right_tl
789   }
790   {
791     \LWR@origensuredmath{
792       \chemm macros_text:V \l__chemm macros_state_pre_tl
793       \c_math_superscript_token
794       { \chemm macros_text:V \l__chemm macros_state_sp_left_tl }

```

Only add the subscripts if they are being used. This avoids causing an incorrect depth, as the empty subscript will be measured by TeX but cropped out by *pdfcrop*.

```

795   \tl_if_empty:NTF \l__chemm macros_state_sb_left_tl
796   {}
797   {
798     \c_math_subscript_token
799     { \chemm macros_text:V \l__chemm macros_state_sb_left_tl }
800   }
801   #2
802   \c_math_superscript_token
803   { \chemm macros_text:V \l__chemm macros_state_sp_right_tl }
804   \tl_if_empty:NTF \l__chemm macros_state_sb_right_tl
805   {}
806   {
807     \c_math_subscript_token
808     { \chemm macros_text:V \l__chemm macros_state_sb_right_tl }
809   }
810   \chemm macros_text:V \l__chemm macros_state_post_tl
811 }
812 }

```

```

813     \group_end:
814 }
815 \cs_generate_variant:Nn \chemmacros_state:nn { nV }
816
817 \cs_gset_protected:Npn \chemmacros_declare_state:Nn #1#2
818 {
819     \chemmacros_define_keys:xn
820     {thermodynamics/\chemmacros_remove_backslash:N #1}
821     {
822         pre          .meta:nn = {chemmacros/thermodynamics} { pre = ##1 } ,
823         post         .meta:nn = {chemmacros/thermodynamics} { post = ##1 } ,
824         superscript-left .meta:nn = {chemmacros/thermodynamics} { superscript-left = ##1 } ,
825         superscript-right .meta:nn = {chemmacros/thermodynamics} { superscript-right = ##1 } ,
826         superscript    .meta:n  = { superscript-right = ##1 } ,
827         subscript-left .meta:nn = {chemmacros/thermodynamics} { subscript-left = ##1 } ,
828         subscript-right .meta:nn = {chemmacros/thermodynamics} { subscript-right = ##1 } ,
829         subscript      .meta:n  = { subscript-left = ##1 } ,
830         subscript-pos   .choices:nn =
831             { left , right }
832             { \tl_set_eq:NN \l__chemmacros_state_sb_pos_tl \l_keys_choice_tl } ,
833         symbol        .tl_set:N = \l__chemmacros_state_symbol_tl ,
834         unit          .tl_set:N = \l__chemmacros_state_unit_tl
835     }
836 \DeclareDocumentCommand #1 { sO{}D(){}m }
837 {
838     \group_begin:
839     \chemmacros_set_keys:xn
840     {thermodynamics/\chemmacros_remove_backslash:N #1}
841     {##2}
842     \tl_if_blank:nF {##3}
843     {
844         \chemmacros_set_keys:nx {thermodynamics}
845         { subscript-\l__chemmacros_state_sb_pos_tl = \exp_not:n {##3} }
846     }
847         \chemmacros_state:nV {##2} \l__chemmacros_state_symbol_tl
848         \chemmacros_set_keys_groups:nnn {thermodynamics} {variables} {##2}
849         \IfBooleanF {##1} { = ~ \SI {##4} { \l__chemmacros_state_unit_tl } }
850     \group_end:
851 }
852 }
```

The pre-existing macros are redefined with the new definition:

```

853 \RenewChemState \enthalpy { symbol = H , unit = \kilo\joule\per\mole }
854 \RenewChemState \entropy { symbol = S , unit = \joule\per\kelvin\per\mole , pre = }
855 \RenewChemState \gibbs { symbol = G , unit = \kilo\joule\per\mole }
856
857 }{ }% \ifchemmacrosmoduleloaded
858 }% AtBeginDocument
859 \ExplSyntaxOff
```

---

**File 78 l warp-chemnum.sty**

§ 178      Package **chemnum**

*(Emulates or patches code by CLEMENS NIEDERBERGER.)*

Pkg chemnum chemnum is patched for use by l warp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{chemnum}[2016/04/14]

2 \ExplSyntaxOn
3
4 \cs_gset_protected:Npn \chemnum_compound_write:n #1
5  {
6      \chemnum_get_compound_property:nn {#1} {pre-main-label-code}
7      \group_begin:
8          \bool_if:NTF \l_chemnum_compound_local_bool
9              { \l_chemnum_local_label_format_tl }
10             { \chemnum_get_compound_property:nn {#1} {label-format} }
11
12         \LWR@textcurrentfont{
13             \chemnum_get_compound_property:nn {#1} {counter-representation}
14         }
15     }
16     \group_end:
17     \chemnum_get_compound_property:nn {#1} {post-main-label-code}
18 }

19
20 \cs_gset_protected:Npn \chemnum_subcompound_write:nn #1#2
21  {
22      \group_begin:
23          \bool_if:NTF \l_chemnum_compound_local_bool
24              { \l_chemnum_local_label_format_tl }
25              { \chemnum_get_compound_property:nn {#1} {label-format} }
26
27          \LWR@textcurrentfont{
28              \chemnum_get_subcompound_property:nnn {#1} {#2}
29              {counter-representation}
30          }
31      }
32      \group_end:
33  }

34 \ExplSyntaxOff
```

---

**File 79 l warp-chkfloat.sty****§ 179 Package chkfloat**

Pkg chkfloat chkfloat is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{chkfloat}[2012/08/19]

---

**File 80 l warp-chngpage.sty****§ 180 Package chngpage**

(Emulates or patches code by PETER WILSON.)

Pkg chngpage chngpage is ignored.

**for HTML output:** Discard all options for l warp-chngpage:

1 \LWR@ProvidesPackageDrop{chngpage}[2009/10/20]  
2 \LWR@origRequirePackage{l warp-changepage}

---

**File 81 l warp-cite.sty****§ 181 Package cite**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg cite cite is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{cite}[2015/02/27]

For the [super] option, the \kern must be removed:

```
2 \def\LWRCT@biblabel#1{\@citess{#1}\kern-\labelsep,}  
3  
4 \ifdef\strequal{\@biblabel}{\LWRCT@biblabel}  
5 {  
6   \def\@biblabel#1{\@citess{#1}}  
7 }{}
```

For the [super] option, \textsuperscript is used instead of math superscript:

```
8 \def\@citess#1{\textsuperscript{#1}}  
9  
10 \DeclareDocumentCommand\citeref{}{\relax}
```

---

**File 82 l warp-CJK.sty****§ 182 Package CJK**

Pkg CJK CJK does not work with l warp unless called from ctex.

**for HTML output:**

```
1 \@ifpackageloaded{xeCJK}{}{  
2     \LWR@loadnever{CJK}{ctex, xeCJK}  
3 }  
4  
5 \LWR@ProvidesPackagePass{CJK}[2015/04/18]
```

---

**File 83 l warp-CJKutf8.sty****§ 183 Package CJKutf8**

Pkg CJKutf8 CJKutf8 does not work with l warp unless called from ctex.

**for HTML output:**

```
1 \@ifpackageloaded{xeCJK}{}{  
2     \LWR@loadnever{CJKutf8}{ctex, xeCJK}  
3 }  
4  
5 \LWR@ProvidesPackagePass{CJKutf8}[2015/04/18]
```

---

**File 84 l warp-clrdblpq.sty****§ 184 Package clrdblpq**

Pkg clrdblpq clrdblpq is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{clrdblpq}[2018/04/21]
```

---

**File 85 l warp-cmdtrack.sty****§ 185 Package cmdtrack**

Pkg cmdtrack cmdtrack is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{cmdtrack}[2012/12/18]
```

```
2 \newcommand{\untrack}{\relax}
```

---

**File 86 l warp-color.sty****§ 186 Package color**

Pkg color Allowed but ignored. xcolor is then required as well.

color is superceded by xcolor, and l warp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

**for HTML output:**  
1 \LWR@ProvidesPackageDrop{color}[2016/07/10]  
2 \RequirePackage{xcolor}

---

**File 87 l warp-colortbl.sty****§ 187 Package colortbl**

Pkg colortbl colortbl is used as-is for print output, and emulated for HTML.

**⚠ row/cell color** Only use \rowcolor and \cellcolor at the start of a row, in that order.

colortbl ignores the overhang arguments.

**for HTML output:** A placeholder definition is forgotten first:

1 \let\rowcolor\relax  
2  
3 \LWR@ProvidesPackagePass{colortbl}[2018/12/12]

The following \LWR@HTML versions are used inside an HTML tabular.

\columncolor [⟨model⟩] {⟨color⟩} [⟨left overhang⟩] [⟨right overhang⟩]  
\LWR@getmynexttoken is not used here because \columncolor is not used inside the data area of the tabular.  
4 \NewDocumentCommand{\LWR@HTML@columncolor}{O{named} m o o}{%  
5 \convertcolorspec{#1}{#2}{HTML}\LWR@columnHTMLcolor%  
6 \LWR@addtabularcellcolor%  
7 }  
8  
9 \AtBeginDocument{\LWR@formatted{columncolor}}

\LWR@getmynexttoken is used for \rowcolor because it is used inside the data area of the tabular.

\rowcolor [⟨model⟩] {⟨color⟩} [⟨left overhang⟩] [⟨right overhang⟩]  
10 \NewDocumentCommand{\LWR@HTML@rowcolor}{O{named} m o o}{%

```
11   \convertcolorspec{#1}{#2}{HTML}\LWR@rowHTMLcolor%
12   \LWR@getmynexttoken%
13 }
14
15 \AtBeginDocument{\LWR@expandableformatted{rowcolor}}
```

\cellcolor [*model*] {{*color*} [*left overhang*] [*right overhang*]}

```
16 \NewDocumentCommand{\LWR@HTML@cellcolor}{O{named} m o o}{%
17   \convertcolorspec{#1}{#2}{HTML}\LWR@cellHTMLcolor%
18   \LWR@addtabularcellcolor%
19 }
20
21 \AtBeginDocument{\LWR@formatted{cellcolor}}
```

\arrayrulecolor [*model*] {{*color*}}

The HTML version for use outside a tabular. Inside a tabular, \LWR@HTML@arrayrulecolornexttoken is used instead.

```
22 \newcommand{\LWR@HTML@arrayrulecolor}[2][named]{%
23   \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
24 }
25
26 \AtBeginDocument{\LWR@expandableformatted{arrayrulecolor}}
```

[*model*] {{*color*}}

The HTML version for use inside a tabular.

```
27 \newcommand{\LWR@HTML@arrayrulecolornexttoken}[2][named]{%
28   \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
29   \LWR@getmynexttoken%
30 }
31
32 \AtBeginDocument{\LWR@expandableformatted{arrayrulecolornexttoken}}
```

\doublerulesepcolor [*model*] {{*color*}}

The version for use outside a tabular.

```
33 \newcommand{\LWR@HTML@doublerulesepcolor}[2][named]{}%
34
35 \AtBeginDocument{\LWR@expandableformatted{doublerulesepcolor}}
```

[*model*] {{*color*}}

The version for use inside a tabular.

```
36 \newcommand{\LWR@HTML@doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}%
37
38 \AtBeginDocument{\LWR@expandableformatted{doublerulesepcolornexttoken}}
```

---

**File 88 l warp-continue.sty****§ 188 Package continue**

Pkg **continue** **continue** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{continue}[2018/12/09]

```
2 \newcommand{\flagcont}{}  
3 \newcommand{\flagend}{}  
4 \newcommand{\flagword}{}  
5 \newcommand{\preflagword}{}  
6 \newcommand{\postflagword}{}  
7 \newlength\contsep  
8 \newlength\contdrop
```

---

**File 89 l warp-copyrightbox.sty****§ 189 Package copyrightbox**

(Emulates or patches code by THOMAS FISCHER, IVES VAN DER FLAAS.)

Pkg **copyrightbox** **copyrightbox** is emulated for use by **l warp**.

The entire copyright box is placed inside a <div> of class **copyrightbox**.

The contents are placed inside a <div> of class **copyrightboxcontents**.

The copyright notice is placed inside a <div> of class **copyrightboxnote**.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{copyrightbox}[2011/11/27]

```
2 \newcommand{\copyrightbox}[3][r]{%  
3 \begin{BlockClass}[  
4 display: inline-flex;  
5 flex-direction: column ;  
6 ]{copyrightbox}  
7 \begin{BlockClass}{copyrightboxcontents}  
8 #2  
9 \end{BlockClass}  
10 \begin{BlockClass}{copyrightboxnote}  
11 #3  
12 \end{BlockClass}  
13 \end{BlockClass}  
14 }  
15  
16 \newcommand{\CRB@setcopyrightfont}{}  
17 \newcommand{\CRB@setcopyrightparagraphstyle}{}  
18
```

---

**File 90 l warp-crop.sty****§ 190 Package crop**

(Emulates or patches code by MELCHIOR FRANZ.)

Pkg crop crop is ignored.

**for HTML output:** Discard all options for l warp-crop:

```
1 \LWR@ProvidesPackageDrop{crop}[2003/05/20]
2 \newcommand*{\crop}[1][]{}
3 \newcommand*{\cropdef}[6][]{}
```

---

**File 91 l warp-ctable.sty****§ 191 Package ctable**

(Emulates or patches code by WYBO DEKKER.)

Pkg ctable ctable is patched for use by l warp.

⚠ **Misplaced alignment tab character &** Use \StartDefiningTabulars before one or more \ctables, and \StopDefiningTabulars after. These change the meaning of the ampersand & character.

**for HTML output:** 1 \LWR@ProvidesPackagePass{ctable}[2015/10/17]

The following is in the original:

```
2 \newcommand{\LWR@HTML@ctable}[4][]{%
3   \let\@CTtaborfig \dfltcTtaborfig
4   \let\@CTalign \dfltcTalign
5   \let\@CTsideways \dfltcTsideways
6   \let\@CTcontinued \empty
7   \let\@CTpos \dfltcTpos
8   \let\@CTcaption \empty
9   \let\@CTcap \undefined
10  \let\@CTlabel \empty
11  \let\@CTbotcap \dfltcTbotcap
12  \let\@CTstarred \dfltcTstarred
13  \let\@CTsuper \dfltcTsuper
14  \let\@CTnotespar \dfltcTnotespar
15  \let\@CTdoinside \dfltcTdoinside
16  \let\@CTbgopacity \dfltcTbgopacity
17  \let\@CTframerule \dfltcTframerule
18  \let\@CTcaptionskip \dfltcTcaptionskip
19  \let\@CTframesep \dfltcTframesep
```

```

20   \@CTwidth      \@dfltcTwidth
21   \@CTmaxwidth   \@dfltcTmaxwidth
22   \@CTmincapwidth \@dfltcTmincapwidth
23   \@CTfooterwidth \@dfltcTfooterwidth
24   \def\@CTfactual {@dfltcTframefg}%
25   \def\@CTbactual {@dfltcTframebg}%
26   \def\@CTbeg      {\begin{\@CTsideways\@CTtaborfig\@CTstarred}}%
27   \def\@CTbegin    {\@CTbeg}%
28   \def\@CTend     {\end{\@CTsideways\@CTtaborfig\@CTstarred}}%
29   \setkeys{CT}{#1}%
30   \ifx\@CTcap\undefined\let\@CTcap\@CTcaption\fi
31   \ifx\@CTcap\empty
32     \if@CTcaptionloaded\else
33       \PackageWarningNoLine{lwarf-ctable}{\MessageBreak
34         An empty cap= option prevents lot/loc entry only\MessageBreak
35         if the caption package is loaded!}
36     \fi
37   \fi
38   \if@CTinmemoir\else
39     \ifx\@CTbotcap\undefined
40       \PackageError{lwarf-ctable}{\MessageBreak
41         You can, currently, use the sidecap option only with\MessageBreak
42         memoir documents. Use topcap or botcap only}
43     \fi
44   \fi
45   \ifdim\@CTwidth=0pt\else
46     \ifdim\@CTmaxwidth=0pt\else
47       \PackageError{lwarf-ctable}{\MessageBreak
48         You may not use the width and maxwidth options together\MessageBreak
49         Use either width or maxwidth}
50     \fi
51   \fi
52   \ifx\@CTpos\empty
53     \ifx\@CTsideways\empty\else
54       \PackageError{lwarf-ctable}{\MessageBreak
55         You may not use the pos and sideways options together\MessageBreak
56         Rotated tables and figures are always typeset on a separate page}
57     \fi
58   \fi
59   \ifx\@CTcaption\empty
60     \ifx\@CTlabel\empty\else
61       \PackageError{lwarf-ctable}{\MessageBreak
62         You may not label a captionless table\MessageBreak
63         Such a label can't be referenced}
64     \fi
65   \fi

```

Some of the original, regarding computing the width of \CT@t, is removed here.

```

66   \@CTbegin
67     \ifx\@CTcontinued\empty\else\addtocounter{\@CTtaborfig}{-1}\fi
68     \@CTalign

```

lwarf's patches begin here:

```

69   \begin{center}
70     \setlength{\fboxrule}{\@CTframerule}
71     \setlength{\fboxsep}{\@CTframesep}
72     \LWR@forceminwidth{\fboxrule}%
73     \convertcolorspec{named}{\@CTbgactual}{HTML}\LWR@tempcolor% l warp
74     \begin{BlockClass}[% l warp
75       border:
76         \LWR@printlength{\LWR@atleastonept}
77         solid
78         \LWR@colorstyle{named}{\@CTfgactual} ; %
79         padding:\LWR@printlength{\fboxsep} ; %
80         \ifdefined{\LWR@tempcolor}{FFFFFF}{\{}%
81           background: \LWR@colorstyle{named}{\@CTbgactual} ; %
82         \}%
83     ]{\minipage}%
84     \ifx@\CTbotcap@\CTfalse@\CTCaption\vskip\@CTcaptionskip\fi
85     \ifx@\CTbotcap\undefined%
86       \begin{sidecaption}[\@CTcap]{\@CTcaption}[\@CTlabel]
87     \fi
88     \@CTdoinside
89     \begin{tabularx}{\linewidth}{#2}%
90       l warp
91       #4%
92     \end{tabularx}%
93     \def@\CTfootnotes{#3}%
94     \ifx#3\empty\else% append footnotes, if any
95       \begin{BlockClass}{tnotes}%
96         l warp
97       \end{BlockClass}%
98     \fi
99     \ifx@\CTbotcap\undefined\end{sidecaption}\fi
100    \ifx@\CTbotcap@\CTtrue\vskip\@CTcaptionskip\@CTCaption\fi
101    \end{BlockClass}%
102  \end{center}
103  \@CTend
104 }
105 \LWR@formatted{ctable}

```

Required to properly detect the toprule:

```
106 \LetLtxMacro\FL\toprule
```

Table notes are redefined for HTML:

```

107 \newcommand{\LWR@HTML@tmark}[1][a]{%
108   \textsuperscript{\textrm{\textit{#1}}}}
109 }
110 \LWR@formatted{tmark}
111
112 \newcommand{\LWR@HTML@tnote}[2][a]{%
113   \tmark[#1]\,,#2\par}
114 }
115 \LWR@formatted{tnote}

```

---

**File 92 l warp-cuted.sty**

§ 192      Package **cuted**

(Emulates or patches code by SIGITAS TOLUŠIS.)

Pkg cuted cuted is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{cuted}[2012/10/04]

2 \newenvironment{strip}{}{}
3 \newskip\stripsep
4 \def\oldcolsbreak#1{}
```

---

**File 93 l warp-cutwin.sty**

§ 193      Package **cutwin**

(Emulates or patches code by PETER WILSON AND ALAN HOENIG.)

Pkg cutwin cutwin is emulated.

for HTML output: Discard all options for l warp-cutwin:

```
1 \LWR@ProvidesPackageDrop{cutwin}[2010/09/29]

2 \newcommand*\opencutleft(){}
3 \newcommand*\opencutright){}
4 \newcommand*\opencutcenter){}
5 \newcommand*\cutfuzz}{}
6
7 \newenvironment{cutout}[4]
8 {\marginpar{\windowpagestuff}}
9 {}
10
11 \newcommand*\windowpagestuff){}
12
13 \newcommand*\pageinwindow}{%
14 % \begin{minipage}{.3\linewidth}
15 \windowpagestuff
16 % \end{minipage}
17 }
18
19 \newenvironment{shapedcutout}[3]
20 {\marginpar{\picinwindow}}
21 {}
22
23 \newcommand*\putstuffinpic){}
```

```
24
25 \newcommand*\picinwindow{%
26 \begin{picture}(0,0)
27 \putstuffinpic
28 \end{picture}}
```

---

**File 94 l warp-dblfloatfix.sty****§ 194 Package dblfloatfix**

Pkg dblfloatfix dblfloatfix is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{dblfloatfix}[2012/12/31]

---

**File 95 l warp-dblfnote.sty****§ 195 Package dblfnote**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg dblfnote dblfnote is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{dblfnote}[1999/07/14]

```
2 \newcounter{DFNsloppiness}
3 \newdimen\DFNcolumnsep
4 \newdimen\DFNcolumnwidth
5 \def\DFNallowcbreak{}
6 \def\DFNinhibitcbreak{}
7 \def\DFNtrysingle{}
8 \def\DFNalwaysdouble{}
9 \def\DFNruleboth{}
10 \def\DFNruleleft{}
```

---

**File 96 l warp-dcolumn.sty****§ 196 Package dcolumn**

Pkg dcolumn dcolumn is emulated by the l warp core.

1 \LWR@ProvidesPackageDrop{dcolumn}[2014/10/28]

---

File 97 **l warp-diagbox.sty**

§ 197 Package **diagbox**

*(Emulates or patches code by LEO LIU.)*

Pkg diagbox diagbox is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{diagbox}[2016/12/28]

To restore print-mode inside a lateximage:

```

2 \LetLtxMacro{\LWR@origdiagbox@double}{\diagbox@double}
3 \LetLtxMacro{\LWR@origdiagbox@triple}{\diagbox@triple}
4
5 \appto{\LWR@restoreorigformatting}{%
6 \LetLtxMacro{\diagbox@double}{\LWR@origdiagbox@double}%
7 \LetLtxMacro{\diagbox@triple}{\LWR@origdiagbox@triple}%
8 }
```

```

\LWR@diagbox@AB {\langle E/W \rangle} {\langle A \rangle} {\langle E/W \rangle} {\langle B \rangle}
9 \newcommand{\LWR@diagbox@AB}[4]{%
10 \begingroup%
11 \LetLtxMacro{\\\newline}{%
12 \BlockClassSingle{\diagbox#1}{#2}%
13 \BlockClassSingle{\diagbox#3}{#4}%
14 \endgroup%
15 \LWR@stoppars%
16 }
```

```

\LWR@diagboxNW {\langle A \rangle} {\langle B \rangle}
17 \newcommand{\LWR@diagboxNW}[2]{%
18 \LWR@diagbox@AB{E}{#2}{W}{#1}%
19 }
```

Likewise for NE, SW, SE:

```

20 \newcommand{\LWR@diagboxNE}[2]{%
21 \LWR@diagbox@AB{W}{#1}{E}{#2}%
22 }
23
24 \let{\LWR@diagboxSW}{\LWR@diagboxNE}
25 \let{\LWR@diagboxSE}{\LWR@diagboxNW}
```

```

\diagbox@double {\langle keys \rangle} {\langle A \rangle} {\langle B \rangle}
26 \def{\diagbox@double}{#1#2#3}{%
```

---

```

27 \setkeys{diagbox}{dir=NW,#1}%
28 \@nameuse{LWR@diagbox\diagbox@dir}{#2}{#3}%
29 }

\LWR@diagboxTNW {⟨title⟩} {⟨A⟩} {⟨B⟩}

30 \newcommand{\LWR@diagboxTNW}[3]{%
31 \BlockClassSingle{diagboxtitleN}{#1}%
32 \LWR@diagboxNW{#2}{#3}%
33 }

```

Likewise for NE, SW, SE:

```

34 \newcommand{\LWR@diagboxTNE}[3]{%
35 \BlockClassSingle{diagboxtitleN}{#1}%
36 \LWR@diagboxNE{#2}{#3}%
37 }
38
39 \newcommand{\LWR@diagboxTSW}[3]{%
40 \LWR@diagboxSW{#2}{#3}%
41 \BlockClassSingle{diagboxtitleS}{#1}%
42 \LWR@stoppars%
43 }
44
45 \newcommand{\LWR@diagboxTSE}[3]{%
46 \LWR@diagboxSE{#2}{#3}%
47 \BlockClassSingle{diagboxtitleS}{#1}%
48 \LWR@stoppars%
49 }

```

```

\diagbox@triple {⟨keys⟩} {⟨A⟩} {⟨T⟩} {⟨B⟩}

50 \def\diagbox@triple#1#2#3#4{%
51 \setkeys{diagbox}{dir=NW,#1}%
52 \@nameuse{LWR@diagboxT\diagbox@dir}{#3}{#2}{#4}%
53 }

```

---

### File 98 **lwarp-dingbat.sty**

§ 198      Package **dingbat**

*(Emulates or patches code by SCOTT PAKIN.)*

Pkg dingbat dingbat is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{dingbat}[2001/04/27]

```

2 \newcommand*\{\LWR@dingbatsymbol}[1]{\HTMLunicode{#1}}
3
4 \newcommand{\LWR@HTML@rightpointright}{\LWR@dingbatsymbol{261E}}
5 \newcommand{\LWR@HTML@leftpointright}{\LWR@dingbatsymbol{261E}}
6 \newcommand{\LWR@HTML@leftthumbsdown}{\LWR@dingbatsymbol{1F44E}}

```

---

```

7 \newcommand{\LWR@HTML@leftthumbsup}{\LWR@dingbatsymbol{1F44D}}
8 \newcommand{\LWR@HTML@rightpointleft}{\LWR@dingbatsymbol{261C}}
9 \newcommand{\LWR@HTML@rightthumbsdown}{\LWR@dingbatsymbol{1F44E}}
10 \newcommand{\LWR@HTML@rightthumbsup}{\LWR@dingbatsymbol{1F44D}}
11 \newcommand{\LWR@HTML@squarewithdots}{\LWR@dingbatsymbol{25C7}}
12 \newcommand{\LWR@HTML@filledsquarewithdots}{\LWR@dingbatsymbol{25C6}}
13 \newcommand{\LWR@HTML@Sborder}{\LWR@dingbatsymbol{271A}}
14 \newcommand{\LWR@HTML@Zborder}{\LWR@dingbatsymbol{274B}}
15 \newcommand{\LWR@HTML@largepencil}{\LWR@dingbatsymbol{270E}}
16 \newcommand{\LWR@HTML@anchor}{\LWR@dingbatsymbol{2693}}
17 \newcommand{\LWR@HTML@carriagereturn}{\LWR@dingbatsymbol{23CE}}
18 \newcommand{\LWR@HTML@checkmark}{\LWR@dingbatsymbol{2713}}
19 \newcommand{\LWR@HTML@eye}{\LWR@dingbatsymbol{1F441}}
20 \newcommand{\LWR@HTML@satellitedish}{\LWR@dingbatsymbol{1F4E1}}
21 \newcommand{\LWR@HTML@smallpencil}{\LWR@dingbatsymbol{270E}}
22
23 \LWR@formatted{rightpointright}
24 \LWR@formatted{leftpointright}
25 \LWR@formatted{leftthumbsdown}
26 \LWR@formatted{leftthumbsup}
27 \LWR@formatted{rightpointleft}
28 \LWR@formatted{rightthumbsdown}
29 \LWR@formatted{rightthumbsup}
30 \LWR@formatted{squarewithdots}
31 \LWR@formatted{filledsquarewithdots}
32 \LWR@formatted{Sborder}
33 \LWR@formatted{Zborder}
34 \LWR@formatted{largepencil}
35 \LWR@formatted{anchor}
36 \LWR@formatted{carriagereturn}
37 \LWR@formatted{checkmark}
38 \LWR@formatted{eye}
39 \LWR@formatted{satellitedish}
40 \LWR@formatted{smallpencil}

```

---

### File 99 **lwarf-dprogress.sty**

#### § 199 Package **dprogress**

Pkg dprogress dprogress is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{dprogress}[2008/02/21]

---

### File 100 **lwarf-draftcopy.sty**

#### § 200 Package **draftcopy**

Pkg draftcopy draftcopy is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{draftcopy}[2002/02/25]

---

```

2 \newcommand{\draftcopyVersion}[1]{}
3 \newcommand{\draftcopySetGrey}[1]{}
4 \newcommand{\draftcopySetScale}[1]{}
5 \newcommand{\draftcopySetScaleFactor}[1]{}
6 \newcommand{\draftcopyFirstPage}[1]{}
7 \newcommand{\draftcopyLastPage}[1]{}
8 \newcommand{\draftcopyName}[2]{}
9 \newcommand{\draftcopyPageTransform}[1]{}
10 \newcommand{\draftcopyBottomTransform}[1]{}
11 \newcommand{\draftcopyPageX}[1]{}
12 \newcommand{\draftcopyPageY}[1]{}
13 \newcommand{\draftcopyBottomX}[1]{}
14 \newcommand{\draftcopyBottomY}[1]{}

```

---

File 101 **l warp-draftfigure.sty**

§ 201 Package **draftfigure**

Pkg **draftfigure** **draftfigure** is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{draftfigure}[2017/07/19]
2 \RequirePackage{xkeyval}

3 \define@key{draftfigure}{code}{}
4 \define@key{draftfigure}{noframe}[true]{}
5 \define@key{draftfigure}{filename}[true]{}
6 \define@key{draftfigure}{content}{}[]
7 \define@key{draftfigure}{style}[normal]{}
8 \define@key{draftfigure}{position}[left]{}
9 \define@key{draftfigure}{size}[normal]{}
10 \newcommand\setdf[1]{\setkeys{draftfigure}{#1}}

```

---

File 102 **l warp-draftwatermark.sty**

§ 202 Package **draftwatermark**

(Emulates or patches code by SERGIO CALLEGARI.)

Pkg **draftwatermark** **draftwatermark** is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{draftwatermark}[2015/02/19]

2 \newcommand{\SetWatermarkAngle}[1]{}
3 \newcommand{\SetWatermarkColor}[1]{}
4 \newcommand{\SetWatermarkLightness}[1]{}
5 \newcommand{\SetWatermarkFontSize}[1]{}
6 \newcommand{\SetWatermarkScale}[1]{}
7 \newcommand{\SetWatermarkHorCenter}[1]{}
8 \newcommand{\SetWatermarkVertCenter}[1]{}
9 \newcommand{\SetWatermarkText}[1]{}

```

---

File 103 **l warp-easy-todo.sty**

§ 203 Package **easy-todo**

(Emulates or patches code by JUAN RADA-VILELA.)

Pkg easy-todo **easy-todo** is patched for use by **l warp**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{easy-todo}[2014/01/01]

\listoftodos Modified to correct buggy use of \flushright.

```
2 \let\LWR@origlistoftodos\listoftodos
3
4 \renewcommand{\listoftodos}{%
5 \begingroup
6 \renewcommand{\flushright}{}%
7 \LWR@origlistoftodos
8 \endgroup
9 }
```

\todoii Modified to use \textcolor instead of \color.

```
10 \renewcommand{\todoii}[2]{%
11 \ifthenelse{\equal{\@todoobeyfinal}{true}}{%
12   {%
13     \ifoptionfinal{\todoenable{false}}{\todoenable{true}}{%
14     }%
15   }%
16 \ifthenelse{\equal{\@todoenable}{true}}{%
17   {%
18     \refstepcounter{todos}%
19     \noindent{%
20       \todocolor{%
21         \LWR@textcurrentcolor{%
22           \normalfont\scriptsize{\bfseries{\thetodos.\#1}}%
23         }%
24       }%
25     \addcontentsline{lod}{todos}{\protect{\thetodos. }\LWR@isolate{\#2}}%
26     }%
27   }%
28 }
```

---

File 104 **l warp-ebook.sty**

§ 204 Package **ebook**

(Emulates or patches code by JØRGEN STEENSGAARD.)

Pkg ebook ebook is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{ebook}

2 \setcounter{secnumdepth}{0}
3 \setcounter{tocdepth}{2}
4
5 \providecommand{\pagefill}[1][0.001mm]{\noindent}
6
7 \providecommand{\ebook}{%
8 \setcounter{secnumdepth}{0}
9 \setcounter{tocdepth}{2}
10 }
```

---

File 105 **l warp-ed.sty**

§ 205 Package **ed**

(Emulates or patches code by MICHAEL KOHLHASE.)

Pkg ed ed is patched for use by l warp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{ed}[2012/01/29]
```

Bugs:

1. todolist fails with the hide option, as does \edexplanation.
2. \edstubURI is actually \edstuURI.

```
2 \RequirePackage{xcolor}
3
4 \renewenvironment{edstub}[2][The following blue text]
5 {%
6   \def\@test{\#1}%
7   \begin{center}%
8     \huge%
9     \textcolor{red}{%
10       \#1 is only a provisional stub\\Large
11       the Office document
12       \ifx\ed@stubURI\empty\else\href{\ed@stubURI}{\#2}\fi\
13       contains more text\\which will be merged for the final document%
14     }%
15   \end{center}%
16   \BlockClass{color:blue}{edstub}%
17 }
18 {\endBlockClass}
```

---

**File 106 l warp-ellipsis.sty****§ 206 Package ellipsis**

(Emulates or patches code by PETER J. HESLIN.)

Pkg ellipsis ellipsis is emulated.

```
1 \LWR@ProvidesPackageDrop{ellipsis}[2004/09/28]
2
3 \newcommand{\ellipsisgap}{0.1em}
4
5 \newcommand*{\midwordellipsis}{\textellipsis}
```

---

**File 107 l warp-embrac.sty****§ 207 Package embrac**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg embrac embrac is nullfied for HTML and used as-is for print.

**for HTML output:** 1 \LWR@ProvidesPackagePass{embrac}[2017/07/04]

```
2 \LetLtxMacro{\LWR@orig@HTML@emph}{\LWR@HTML@emph}
3 \RenewDocumentCommand{\LWR@HTML@emph}{s m}{\LWR@orig@HTML@emph{#2}}
4
5 \LetLtxMacro{\LWR@orig@HTML@textit}{\LWR@HTML@textit}
6 \RenewDocumentCommand{\LWR@HTML@textit}{s m}{\LWR@orig@HTML@textit{#2}}
7
8 \LetLtxMacro{\LWR@orig@HTML@textsl}{\LWR@HTML@textsl}
9 \RenewDocumentCommand{\LWR@HTML@textsl}{s m}{\LWR@orig@HTML@textsl{#2}}
10
11 \ifxetexorluatex
12   \LetLtxMacro{\LWR@orig@HTML@textsi}{\LWR@HTML@textsi}
13   \RenewDocumentCommand{\LWR@HTML@textsi}{s m}{%
14     \LWR@orig@HTML@textsi{#2}}
15 \fi
16
17 \AtBeginDocument{
18   \LWR@formatted{emph}
19   \LWR@formatted{textit}
20   \LWR@formatted{textsl}
21   \ifxetexorluatex
22     \LWR@formatted{textsi}
23   \fi
24 }
25
```

```
26 \newcommand{\LWR@HTML@EmbracOff}{}
27 \LWR@formatted{EmbracOff}
28
29 \newcommand{\LWR@HTML@EmbracOn}{}
30 \LWR@formatted{EmbracOn}
```

---

**File 108 l warp-emptypage.sty****§ 208 Package *emptypage***

Pkg *emptypage* *emptypage* is ignored.

**for HTML output:** Discard all options for *l warp-emptypage*:

```
1 \LWR@ProvidesPackageDrop{emptypage}[2010/05/30]
```

---

**File 109 l warp-endfloat.sty****§ 209 Package *endfloat***

Pkg *endfloat* *endfloat* is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{endfloat}[2019/04/15]

```
2 \newcommand\figureplace{}
3 \newcommand\tableplace{}
4 \newcommand\floatplace[1]{}
5 \newcounter{posttable}
6 \newcounter{postfigure}
7 \newcommand*\theposttbl(){}
8 \newcommand*\thepostfig(){}
9 \newcommand{\AtBeginFigures}[1]({})
10 \newcommand{\AtBeginTables}[1]({})
11 \newcommand{\AtBeginDelayedFloats}[1]({})
12 \newcommand*\processdelayedfloats(){}
13 \newcommand*\efloatseparator(){}
14 \def\efloatattype{}
15 \providecommand\efloatheading[1]({})
16 \providecommand\efloatpreamble){}
17 \providecommand\efloatpostamble){}
18 \NewDocumentCommand{\addtodelayedfloat}{s m m} {}
19 \providecommand{\efloatbegin}){}
20 \providecommand{\efloatend}){}
21 \providecommand{\efloatbeginlist}){}
22 \providecommand{\efloatendlist}{}{}
```

---

File 110 **l warp-endheads.sty**

§ 210 Package **endheads**

Pkg endheads **endheads** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{endheads}[2017/04/06]

```

2 \newcommand{\changesinglepageabbrev}[1]{}
3 \newcommand{\changemultiplepageabbrev}[1]{}
4 \newcommand{\changetitlesname}[1]{}
5 \newcommand{\changetitlesheader}[1]{}
6 \newcommand{\changetitlescontentsname}[1]{}
7 \newcommand{\changechaptertitlesline}[1]{}
8 \newcommand{\checknoteheaders}){}
9 \newif\ifnotesincontents \notesincontentsonfalse
10 \newcommand{\notesincontents}{\notesincontentsontrue}
11 \newif\ifendnoteheaderson \endnoteheadersonfalse
12 \newcommand{\setupendnoteheaders}{%
13   \endnoteheadersontrue%
14 }
15 \newif\iftitleinnotes \titleinnotestrue
16 \newcommand{\styleforchapternotebegin}(){}
17 \newcommand{\styleforchapternoteend}(){}
18 \newcommand{\setstyleforchapternotebegin}[1]{%
19   \renewcommand{\styleforchapternotebegin}{#1}%
20 }
21 \newcommand{\setstyleforchapternoteend}[1]{%
22   \renewcommand{\styleforchapternoteend}{#1}%
23 }
24 \newcommand{\resetendnotes} {}
25 \newif\ifnotesbychapteron \notesbychapteronfalse
26 \newcommand{\notesbychapter}{\notesbychapterontrue}

```

---

File 111 **l warp-endnotes.sty**

§ 211 Package **endnotes**

(Emulates or patches code by JOHN LAVAGNINO.)

Pkg endnotes Used as-is.

**table of contents** To place the endnotes in the TOC, use:

```

\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*\{\notesname}{Endnotes} % optional

```

[HTML page](#) To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes

for HTML output: 1 \LWR@ProvidesPackagePass{endnotes}

2 \def\enoteformat{%
3 % \rightskip\z@ \leftskip\z@ \parindent=1.8em
4 \leavevmode
5 % \llap{
6 \makeenmark
7 %
8 }
9
10 \def\@makeenmark{\hbox{\LWR@htmlspan{sup}{\normalfont\theenmark}}}
11 \def\makeenmark{\@makeenmark}
```

---

#### File 112 **lwarf-enumerate.sty**

##### § 212 Package **enumerate**

Pkg `enumerate` `enumerate` is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by `lwarf` and thus must no longer be dropped.

```
for HTML output: 1 \LWR@ProvidesPackagePass{enumerate}[2015/07/23]
```

---

#### File 113 **lwarf-enumitem.sty**

##### § 213 Package **enumitem**

(Emulates or patches code by JAVIER BEZOS.)

Pkg `enumitem` `enumitem` is supported with minor adjustments.

```
for HTML output: 1 \LWR@ProvidesPackagePass{enumitem}[2018/11/30]
```

```
for HTML output: 2 \begin{warpHTML}
```

```
\newlist {<name>} {<type>} {<maxdepth>}
\renewlist {<name>} {<type>} {<maxdepth>}
```

For `enumitem` lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

---

```

3 \let\LWR@enumitem@orignewlist\newlist
4
5 \renewcommand*{\newlist}[3]{%
6 \LWR@enumitem@orignewlist[#1]{#2}{#3}%
7 \AtBeginEnvironment{#1}{\nameuse{\LWR@#2start}}%
8 \AtEndEnvironment{#1}{\nameuse{\LWR@#2end}}%
9 }
10
11 \def\DrawEnumitemLabel{}

12 \end{warpHTML}

```

---

File 114 **lwarp-epigraph.sty**

§ 214 Package **epigraph**

*(Emulates or patches code by PETER WILSON.)*

Pkg epigraph epigraph is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{epigraph}[2009/09/02]

```

2 \DeclareDocumentCommand{\qitem}{m m}
3 {
4 \begin{BlockClass}{qitem}
5 #1
6 \LWR@stopars%
7 \ifbool{FormatWP}
8 {\begin{BlockClass}[border-top:1px solid gray]{epigraphsource}}
9 {\begin{BlockClass}{epigraphsource}}
10 #2
11 \end{BlockClass}
12 \end{BlockClass}
13 }

14 \DeclareDocumentCommand{\epigraph}{m m}
15 {
16 \begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{epigraph}
17 \qitem{#1}{#2}
18 \end{LWR@BlockClassWP}
19 }
20
21 \DeclareDocumentEnvironment{epigraphs}{}
22 {\LWR@BlockClassWP{\LWR@print@mbox{text-align:right}}{}{epigraph}}
23 {\endLWR@BlockClassWP}

```

Use css to format epigraphs.

The following are null commands for source compatibility:

```
24 \newenvironment*{flushpinormal}{}{}
```

---

```

25 \@ifclassloaded{memoir}{
26 \setlength{\epigraphwidth}{.5\linewidth}
27 \renewcommand{\textflush}{flushleft}
28 \renewcommand{\epigraphhead}[2][0]{#2}
29 \renewcommand{\dropchapter}[1]{}
30 \renewcommand*{\undodrop}{}
31 }% not memoir
32 \newlength{\epigraphwidth}
33 \setlength{\epigraphwidth}{.5\linewidth}
34 \newcommand{\textflush}{flushleft}
35 \newcommand{\epigraphflush}{flushright}
36 \newcommand{\sourceflush}{flushright}
37 \newcommand*{\epigraphsize}{\small}
38 \newlength{\epigraphrule}
39 \newlength{\beforeepigraphskip}
40 \newlength{\afterepigraphskip}
41 \newcommand{\epigraphhead}[2][0]{#2}
42 \newcommand{\dropchapter}[1]{}
43 \renewcommand*{\undodrop}{}
44 }% not memoir
45
46 \let\cleartoevenpage\relax% also in nextpage
47 \newcommand{\cleartoevenpage}[1][]{}

48 \newif\ifepigraphnoindent
49 \newcommand\epigraphnoindent{\epigraphnoindenttrue}

```

---

### File 115 **l warp-epsfig.sty**

#### § 215 Package **epsfig**

Pkg **epsfig** **epsfig** is emulated for use by **l warp**.

⚠ Only the L<sup>A</sup>T<sub>E</sub>X2e syntax is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{epsfig}[2017/06/25]

A few additional keys to capture the filename:

```

2 \RequirePackage{graphics}
3
4 \define@key{igraph}{file}{%
5   \xdef\LWR@epsfig@filename{\#1}%
6 }
7
8 \define@key{igraph}{figure}{%
9   \xdef\LWR@epsfig@filename{\#1}%
10 }
11
12 \define@key{igraph}{prolog}{}
13
14 \define@key{igraph}{silent}{}[]{}

```

The captured filename is used as the argument to `\includegraphics`:

```
15 \newcommand{\epsfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
16
17 \newcommand{\psfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
```

---

#### File 116 **l warp-epstopdf.sty**

#### § 216 Package **epstopdf**

Pkg epstopdf Previous versions of l warp had a nullified version, but now **epstopdf-base** is supported. l warp-**epstopdf** becomes a placeholder to overwrite previous versions.

See package **epstopdf-base** for details.

**for HTML output:** 1 \LWR@ProvidesPackagePass{epstopdf}[2016/05/15]

---

#### File 117 **l warp-epstopdf-base.sty**

#### § 217 Package **epstopdf-base**

Pkg epstopdf-base

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

⚠ **convert to .svg** Enter ⇒ `l warpmk pdftosvg <listofPDFfiles>`

to generate .svg versions.

**for HTML output:** 1 \LWR@ProvidesPackagePass{epstopdf-base}[2016/05/15]

Redefine to remember the image filename, replacing .pdf with .svg. Use the **epstopdf** print version inside a `lateximage`.

```
2 \newcommand*{\LWR@HTML@ETE@OrgGin@setfile}[3]{%
3   \edef\LWR@tempone{\#3}%
4   \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
5   \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
6   \xdef\LWR@parsedfilename{\LWR@tempone}%
7 }
8
9 \LWR@formatted{ETE@OrgGin@setfile}
```

`\includegraphics` in HTML mode redefines `\Gin@setfile` to be `\LWR@HTML@Gin@setfile`, which is now redirected to **epstopdf**'s version:

```
10 \renewcommand*{\LWR@HTML@Gin@setfile}[3]{%
11   \ETE@Gin@setfile{\#1}{\#2}{\#3}%
12 }
```

---

Allow .eps images to be found if a suffix is not provided:

```

13 \AtBeginDocument{
14 \DeclareGraphicsExtensions{%
15   .eps,.EPS,.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
16 }
17 \DeclareGraphicsRule{.svg}{svg}{.svg}{}
18 \DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
19 }
```

Likewise when inside a `lateximage`:

```

20 \appto\LWR@restoreorigformatting{%
21 \DeclareGraphicsExtensions{%
22   .eps,.EPS,.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
23 }%
24 }
```

---

### File 118 **l warp-eqlist.sty**

#### § 218 Package **eqlist**

Pkg `eqlist` `eqlist` is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{eqlist}[2002/08/15]

```

2 \newenvironment{eqlist}[1][]{\description}{\enddescription}
3 \newenvironment{eqlist*}[1][]{\description}{\enddescription}
4 \newenvironment{Eqlist}[2][]{\description}{\enddescription}
5 \newenvironment{Eqlist*}[2][]{\description}{\enddescription}
6 \newcommand*{\longitem}[1][]{\item[#1]}
7 \newcommand*{\eqlistinit}{}%
8 \newcommand*{\eqliststarinit}{}%
9 \newcommand*{\eqlistinitpar}{}%
10 \def\eqlistlabel#1{#1}
11 \newcommand{\eqlistauto}[1]{}
12 \newcommand{\eqlistnoauto}{}%
```

---

### File 119 **l warp-eqparbox.sty**

#### § 219 Package **eqparbox**

(Emulates or patches code by SCOTT PAKIN.)

Pkg `eqparbox` `eqparbox` is patched for use by `l warp`.

**for HTML output:** 1 \LWR@ProvidesPackagePass{eqparbox}[2017/09/03]

```

2 \NewDocumentCommand{\LWR@HTML@eqparbox}{O{t} O{} O{t} m +m}{%
```

```

3      {%
4          \minipagefullwidth%
5          \parbox[#1][#2][#3]{\linewidth}{#5}%
6      }%
7 }
8 \LWR@formatted{eqparbox}
9
10 \NewDocumentCommand{\LWR@HTML@eqmakebox}{o o m}{%
11     \makebox[#2]{#3}%
12 }
13 \LWR@formatted{eqmakebox}
14
15 \NewDocumentCommand{\LWR@HTML@eqframebox}{o o m}{%
16     \framebox[#2]{#3}%
17 }
18 \LWR@formatted{eqframebox}
19
20 \NewDocumentEnvironment{\LWR@HTML@eqminipage}{O{t} O{} O{t} m}{%
21 {%
22     \begingroup%
23     \minipagefullwidth%
24     \minipage[#1][#2][#3]{\linewidth}%
25 }%
26 {%
27     \endminipage%
28     \endgroup%
29 }
30
31 \newcommand*{\LWR@HTML@eqboxwidth}[1]{.25\linewidth}
32 \LWR@formatted{eqboxwidth}
33
34 \newcommand*{\LWR@HTML@eqsetminwidth}[2]{}
35 \newcommand*{\LWR@HTML@eqsetmaxwidth}[2]{}
36
37 \newcommand*{\LWR@HTML@eqsetminwidthto}[2]{}
38 \newcommand*{\LWR@HTML@eqsetmaxwidthto}[2]{}

```

#### File 120 **lwarf-errata.sty**

#### § 220 Package **errata**

*(Emulates or patches code by MICHAEL KOHLHASE.)*

Pkg errata errata is patched for use by lwarf.

This is for v0.3 of errata. A newer version of errata with more features is under development, at which time the lwarf version will have to be updated.

**for HTML output:** Macros are being defined with the math dollar, so enable the HTML version during package loading:

```
1 \StartDefiningMath
```

Now load the package:

```
2 \LWR@ProvidesPackagePass{errata}[2006/11/12]
```

Patches for dynamic inline math:

```

3 \xpatchcmd{\erratumAdd}
4   {$_a^{\arabic{erratum}}$}
5 %   {\inlinemathother{_a^{\arabic{erratum}}}\inlinemathnormal}
6   {\textsubscript{a}\textsuperscript{\arabic{erratum}}}
7   {}
8   {\LWR@patcherror{erratum}{erratumAdd}}
9
10 \xpatchcmd{\erratumDelete}
11   {$_d^{\arabic{erratum}}$}
12 %   {\inlinemathother{_d^{\arabic{erratum}}}\inlinemathnormal}
13   {\textsubscript{d}\textsuperscript{\arabic{erratum}}}
14   {}
15   {\LWR@patcherror{erratum}{erratumDelete}}
16
17 \xpatchcmd{\erratumReplace}
18   {$_r^{\arabic{erratum}}$}
19 %   {\inlinemathother{_r^{\arabic{erratum}}}\inlinemathnormal}
20   {\textsubscript{r}\textsuperscript{\arabic{erratum}}}
21   {}
22   {\LWR@patcherror{erratum}{erratumReplace}}
23
24 \xpatchcmd{\erratum}
25   {$_a$}
26 %   {\inlinemathother{_a}\inlinemathnormal}
27   {\textsubscript{a}}
28   {}
29   {\LWR@patcherror{erratum}{erratumDelete}}
30
31 \xpatchcmd{\erratum}
32   {$_d^{\@thefnmark}$}
33 %   {\inlinemathother{_d^{\@thefnmark}}\inlinemathnormal}
34   {\textsubscript{d}\textsuperscript{@thefnmark}}
35   {}
36   {\LWR@patcherror{erratum}{eDelete}}
37
38 \xpatchcmd{\erratum}
39   {$_r^{\@thefnmark}$}
40 %   {\inlinemathother{_r^{\@thefnmark}}\inlinemathnormal}
41   {\textsubscript{r}\textsuperscript{@thefnmark}}
42   {}
43   {\LWR@patcherror{erratum}{eReplace}}
```

Finish the current page's errata before closing and reloading the list:

```
44 \preto\PrintErrata{\LWR@orignewpage}
```

No longer defining math macros with the **HTML \$**:

```
45 \StopDefiningMath
```

---

**File 121 l warp-eso-pic.sty**

§ 221 Package **eso-pic**

(Emulates or patches code by ROLF NIEPRASCHK.)

Pkg eso-pic eso-pic is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{eso-pic}[2018/04/12]

```
2 \newcommand*\{\LenToUnit\}{}  
3 \newcommand{\AtPageUpperLeft}[1]{}  
4 \newcommand{\AtPageLowerLeft}[1]{}  
5 \newcommand{\AtPageCenter}[1]{}  
6 \newcommand{\AtStockLowerLeft}[1]{}  
7 \newcommand{\AtStockUpperLeft}[1]{}  
8 \newcommand{\AtStockCenter}[1]{}  
9 \newcommand{\AtTextUpperLeft}[1]{}  
10 \newcommand{\AtTextLowerLeft}[1]{}  
11 \newcommand{\AtTextCenter}[1]{}  
12 \NewDocumentCommand{\AddToShipoutPictureBG}{s +m}{}  
  
13 \newcommand{\AddToShipoutPicture}{\AddToShipoutPictureBG}  
14 \NewDocumentCommand{\AddToShipoutPictureFG}{s +m}{}  
15 \newcommand*\{\ClearShipoutPictureBG\}{}  
16 \newcommand*\{\ClearShipoutPicture\}{}  
17 \newcommand*\{\ClearShipoutPictureFG\}{}  
18 \newcommand{\gridSetup}[6]{}{}
```

---

**File 122 l warp-eurosym.sty**

§ 222 Package **eurosym**

(Emulates or patches code by HENRIK THEILING.)

Pkg eurosym eurosym is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{eurosym}[1998/08/06]

```
2 \renewrobustcmd{\official euro}{\HTMLentity{euro}}  
3 \let\geneuro\official euro  
4 \let\geneuronarrow\official euro  
5 \let\geneurowide\official euro  
6 \let\ euro\official euro  
7 \renewrobustcmd{\ eurobars\}{}  
8 \renewrobustcmd{\ eurobarsnarrow\}{}  
9 \renewrobustcmd{\ eurobarswide\}{}{}
```

---

**File 123 l warp-everypage.sty****§ 223 Package everypage**

(Emulates or patches code by SERGIO CALLEGARI.)

Pkg everypage everypage is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{everypage}[2007/06/20]

2 \newcommand\*{\AddEverypageHook}[1]{}  
3 \newcommand\*{\AddThispageHook}[1]{}

---

**File 124 l warp-everyshi.sty****§ 224 Package everyshi**

(Emulates or patches code by MARTIN SCHRÖDER.)

Pkg everyshi ignored.

**for HTML output:** Discard all options for l warp-everyshi:

1 \LWR@ProvidesPackageDrop{everyshi}[2001/05/15]  
2 \newcommand\*{\EveryShipout}[1]{}  
3 \newcommand\*{\AtNextShipout}[1]{}

---

**File 125 l warp-extarrows.sty****§ 225 Package extarrows**

(Emulates or patches code by HUYNH KY ANH.)

Pkg extarrows extarrows is used as-is for SVG math, and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{extarrows}[2008/05/15]

2 \begin{warpMathJax}  
3 \CustomizeMathJax{\Newextarrow\xLongleftarrow[10,10]{0x21D0}}  
4 \CustomizeMathJax{\Newextarrow\xLongrightarrow[10,10]{0x21D2}}  
5 \CustomizeMathJax{\Newextarrow\xLongleftrightarrow[10,10]{0x21D4}}  
6 \CustomizeMathJax{\Newextarrow\xLeftrightarrow[10,10]{0x21D4}}  
7 \CustomizeMathJax{\Newextarrow\xlongleftrightarrow[10,10]{0x2194}}  
8 \CustomizeMathJax{\Newextarrow\xleftrightarrow[10,10]{0x2194}}

---

```
9 \CustomizeMathJax{\let\xlongleftarrow\xleftarrow}
10 \CustomizeMathJax{\let\xlongrightarrow\xrightarrow}
11 \end{warpMathJax}
```

---

**File 126 l warp-extramarks.sty****§ 226 Package extramarks**

(Emulates or patches code by PIET VAN OOSTRUM.)

Pkg **extramarks** **extramarks** is ignored.

**for HTML output:** Discard all options for **l warp-extramarks**:

```
1 \LWR@ProvidesPackageDrop{extramarks}[2019/01/31]

2 \newcommand*\extramarks[2] {}
3 \newcommand*\firstleftxmark{}
4 \newcommand*\lastleftxmark{}
5 \newcommand*\firstrightxmark{}
6 \newcommand*\lastrightxmark{}
7 \newcommand*\firstxmark{}
8 \newcommand*\lastxmark{}
9 \newcommand*\topxmark{}
10 \newcommand*\topleftxmark{}
11 \newcommand*\toprightxmark{}
12 \newcommand*\firstleftmark{}
13 \newcommand*\lastrightmark{}
14 \newcommand*\firstrightmark{}
15 \newcommand*\lastleftmark{}
```

---

**File 127 l warp-fancybox.sty****§ 227 Package fancybox**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg **fancybox** **fancybox** is supported with some patches.

**framed equation example** **fancybox**'s documentation has an example `FramedEqn` environment which combines `math`, `\Sbox`, a `minipage`, and an `\fbox`. This combination requires that the entire environment be enclosed inside a `\lateximage`, which is done by adding `\latexitimage` at the very start of `FramedEqn`'s beginning code, and `\endlatexitimage` at the very end of the ending code. Unfortunately, the `HTML alt` attribute is not used here.

---

```
\newenvironment{FramedEqn}
{
\latextimage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]}
\endlatextimage% NEW
}
```

**framing alternatives** \fbox works with **fancybox**. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

**framed table example** The **fancybox** documentation's example framed table using an \fbox containing a tabular does not work with lwarp, but the **FramedTable** environment does work if \fbox is replaced by \fboxBlock. This method loses HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

**⚠️ framed verbatim** lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The **fancybox** documentation's example **FramedVerb** may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
\VerbatimEnvironment
\fminipage{#1}
\begin{Verbatim}
\end{Verbatim}
\end{fminipage}
}
```

**framed \VerbBox** fancybox's \VerbBox may be used inside \fbox.

**indented alignment** LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what **pdftotext** detects. Some lines may be off slightly in their left edge.

If using **fancybox** or **fancyvrb** with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
{Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbf+}
```

**⚠️ \VerbatimFootnotes**  
**⚠️ sectioning or**  
**displaymath**

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

```
1 \LWR@ProvidesPackagePass{fancybox}[2010/05/15]
```

After the preamble is loaded, after any patches to `\Verbatim`:

```
2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching fancybox.}
```

`\VerbatimFootnotes` Patched to use the new version.

```
4 \def\VerbatimFootnotes{%
5 \let\@footnotetext\@footnotetext%
6 \let\LWR@footnotetext\@footnotetext% lwarp
7 }
```

`\V@footnotetext` Patches in a subset of `lwarp`'s `\LWR@footnotetext` to the `fancyvrb` version of `\V@footnotetext`.

```
8 \def\V@footnotetext{%
9 \LWR@traceinfo{\V@footnotetext}%
10 \global\setbox\lWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
11 \unvbox\lWR@footnotebox%
```

Remember the footnote number for `\ref`:

```
12 \protected@edef\@currentlabel{%
13 \csname p@footnote\endcsname\@thefnmark%
14 }% @currentlabel
```

Use HTML superscripts in the footnote even inside a `\textrimage`:

```
15 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `\textrimage`:

```
16 \ifthenelse{%
17 \boolean{\LWR@doingstartpars} \AND%
18 \cnttest{\value{\LWR@lateximagedepth}}{=}{0}%
19 }%
20 {}%
21 {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
22 \makefntext{}
```

The footnote text will follow after `\V@@footnotetext` has completed.

```
23 \bgroup%
24 \aftergroup{\V@@footnotetext}%
25 \ignorespaces%
26 }%
```

```

27 }% AfterEndPreamble

28 \renewcommand*{\@shadowbox}[1]{%
29 \ifbool{FormatWP}{%
30 {\InlineClass[border:1px solid black]{shadowbox}{#1}}{%
31 {\InlineClass{shadowbox}{#1}}{%
32 }{%
33 }{%
34 \renewcommand*{\@doublebox}[1]{%
35 \ifbool{FormatWP}{%
36 {\InlineClass[border:1px double black]{doublebox}{#1}}{%
37 {\InlineClass{doublebox}{#1}}{%
38 }{%
39 }{%
40 \renewcommand*{\@ovalbox}[2]{%
41 \ifbool{FormatWP}{%
42 {\InlineClass[border:1px solid black; border-radius:1ex]{ovalbox}{#2}}{%
43 {%
44 \ifthenelse{\isequivalentto{#1}{\thinlines}}{%
45 {\InlineClass{ovalbox}{#2}}{%
46 {\InlineClass{Ovalbox}{#2}}{%
47 }{%
48 }

```

Convert minipages, parboxes, and lists into linear text using the `LWR@nestspan` environment:

```

49 \let\LWR@origSbox\Sbox
50
51 \def\Sbox{\LWR@origSbox\LWR@nestspan}
52
53
54 \let\LWR@origendSbox\endSbox
55
56 \def\endSbox{\endLWR@nestspan\LWR@origendSbox}

```

`Beqnarray` is adapted for MATHJAX or enclosed inside a `lateximage`:

```

57 \RenewEnviron{Beqnarray}{%
58 {\LWR@eqnarrayfactor}{%
59 }{%
60 \csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}}

```

`\GenericCaption` is enclosed in an HTML block:

```

61 \renewcommand{\GenericCaption}[1]{%
62 \LWR@figcaption{%
63 \LWR@isolate{#1}{%
64 \endLWR@figcaption}{%
65 }

```

`Btrivlist` is enclosed in an HTML block. This is a tabular, and does not use `\item`.

```

\trivlist {⟨l/c/r⟩} [⟨t/c/b⟩]
66 \RenewDocumentEnvironment{Btrivlist}{m o}
67 {%
68   \LWR@stoppars%
69   \begin{BlockClass}{Btrivlist}%
70   \tabular{#1}%
71 }
72 {%
73   \endtabular%
74   \end{BlockClass}%
75   \LWR@startpars%
76 }

```

Btrivlist is also neutralized when used inside a span:

```

77 \AtBeginEnvironment{\LWR@nestspan}{%
78 \RenewDocumentEnvironment{Btrivlist}{m o}{}{}%
79 }

```

lwarp's handling of \item is patched to accept fancybox's optional arguments:

```

80 \let\LWRFB@origitemizeitem\LWR@itemizeitem
81 \let\LWRFB@origdescitem\LWR@descitem
82
83 \RenewDocumentCommand{\LWR@itemizeitem}{d()o}{%
84   \IfValueTF{#2}{%
85     \LWRFB@origitemizeitem[#2]%
86   }{%
87     \LWRFB@origitemizeitem%
88   }%
89 }
90
91 \RenewDocumentCommand{\LWR@descitem}{d()o}{%
92   \IfValueTF{#2}{%
93     \LWRFB@origdescitem[#2]~%
94   }{%
95     \LWRFB@origdescitem%
96   }%
97 }

98 \RenewDocumentCommand{\LWR@nestspanitem}{d()}{%
99 \if@newlist\else{\LWR@htmltagc{br /}}\fi%
100 \LWR@origitem%
101 }

```

The various boxed lists become regular lists:

```

102 \renewenvironment{Bitemize}[1][]{\begin{itemize}}{\end{itemize}}
103 \renewenvironment{Benumerate}[1][]{\begin{enumerate}}{\end{enumerate}}
104 \renewenvironment{Bdescription}[1][]{\begin{description}}{\end{description}}

```

\boxput simply prints one then the other argument, side-by-side instead of above and behind:

```
105 \RenewDocumentCommand{\boxput}{s d() m m}{%
106 \IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
107 }
```

Neutralized commands:

```
108 \RenewDocumentCommand{\fancyput}{s d() m}{}
109 \RenewDocumentCommand{\thisfancyput}{s d() m}{}
110
111 \RenewDocumentCommand{\fancypage}{m m}{}
112 \RenewDocumentCommand{\thisfancypage}{m m}{}
113
114 \def\LandScape#1{}
115 \def\endLandScape{}
116 \def\@Landscape#1#2#3{}
117 \def\endLandscape{}
```

Low-level patches for `UseVerbatim` and friends:

```
118 \let\LWRFB@UseVerbatim\UseVerbatim
119 \renewcommand*{\UseVerbatim}[1]{%
120 \LWR@atbeginverbatim{3}{Verbatim}%
121 \LWRFB@UseVerbatim{#1}%
122 \LWR@afterendverbatim{.5}%
123 }
124
125 \let\LWRFB@LUseVerbatim\LUseVerbatim
126
127 \renewcommand*{\LUseVerbatim}[1]{%
128 \LWR@atbeginverbatim{3}{LVerbatim}%
129 \noindent%
130 \LWRFB@LUseVerbatim{#1}%
131 \LWR@afterendverbatim{.5}%
132 }
133
134 \def\@BUseVerbatim[#1]#2{%
135 \LWR@atbeginverbatim{3}{BVerbatim}%
136 \LWRFB@UseVerbatim{#2}%
137 \LWR@afterendverbatim{.5}%
138 }
```

### File 128 **lwarf-fancyhdr.sty**

#### § 228 Package **fancyhdr**

(Emulates or patches code by PIET VAN OOSTRUM.)

Pkg `fancyhdr` `fancyhdr` is ignored.

**for HTML output:** Discard all options for l warp-fancyhdr:

```

1 \LWR@ProvidesPackageDrop{fancyhdr}[2019/01/31]

2 \newcommand*\fancyhead[2][]{}
3 \newcommand*\fancyfoot[2][]{}
4 \newcommand*\fancyhf[2][]{}
5 \newcommand*\fancypagestyle[2](){}
6 \newcommand*\lhead[2][]{}
7 \newcommand*\chead[2][]{}
8 \newcommand*\rhead[2][]{}
9 \newcommand*\lfoot[2][]{}
10 \newcommand*\cfoot[2][]{}
11 \newcommand*\rfoot[2][]{}
12 \newcommand*\headrulewidth(){}
13 \newcommand*\footrulewidth(){}
14 \newcommand*\headrule(){}
15 \newcommand*\footrule(){}
16 \newlength{\headwidth}
17 \newcommand*\fancyheadoffset[2][]{}
18 \newcommand*\fancyfootoffset[2][]{}
19 \newcommand*\fancyhffoffset[2][]{}
20 \newcommand*\iffloatpage[2]{#2}
21 \newcommand*\iffloatfloat[2]{#2}
22 \newcommand*\iffbotfloat[2]{#2}
23 \newcommand*\iffootnote[2]{#2}
```

### File 129 l warp-fancyref.sty

§ 229 Package **fancyref**

Pkg fancyref fancyref is emulated.

**for HTML output:** 1 \LWR@ProvidesPackagePass{fancyref}[1999/02/03]

To remove the margin option, if \fancyrefhook is anything other than the paren option, then force it to the default instead. (Comparing to the margin option was not possible since l warp has revised the meaning of \mbox so the comparison failed.)

```

2 \newcommand*\LWRfref@parenfancyrefhook[1]{{#1}}
3
4 \ifdefstequal{\fancyrefhook}{\LWRfref@parenfancyrefhook}{}
5 {}{
6   \renewcommand*\fancyrefhook[1]{{#1}}%
7 }
```

Modified to ignore the page number and varioref.

```

8 \renewcommand*\@f@ref[4]{%
9   \@ifundefined{#1r@#2@#3}{%
10     \PackageError{l warp-fancyref}{%
11       \backslash\#1ref\space format ‘‘#2’’}}}
```

---

```

12     undefined\MessageBreak
13     for label type '#3'%}
14 }{%
15     The format '#2' was not defined for the label type
16     '#3'\MessageBreak
17     and the \backslashchar#1ref\space command. Perhaps
18     you have only misspelled its name.\MessageBreak
19     Otherwise you will have to define it with
20     \protect\new#1reformat\MessageBreak
21     prior to using it.%}
22 }%
23 }{%
24 \fancyrefhook{%
25     \nameuse{#1r@#2@#3}%
26     {\ref{#3\fancyrefargdelim#4}}%
27 %     {\pageref{#3\fancyrefargdelim#4}}% original
28 %     {@fancyref@page@ref{#3\fancyrefargdelim#4}}% original
29     {}% l warp
30     {}% l warp
31 }%
32 }%
33 }%

```

---

### File 130 **l warp-fancytabs.sty**

#### § 230 Package **fancytabs**

Pkg fancytabs fancytabs is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fancytabs}[2016/03/29]

```

2 \newcommand{\fancytab}[3][RIGHT]{}
3 \newcommand{\fancytabsStyle}[1]{}
4 \newcommand{\fancytabsHeight}[1]{}
5 \newcommand{\fancytabsWidth}[1]{}
6 \newcommand{\fancytabsCount}[1]{}
7 \newcommand{\fancytabsLeftColor}[1]{}
8 \newcommand{\fancytabsRightColor}[1]{}
9 \newcommand{\fancytabsTop}[1]{}
10 \newcommand{\fancytabsTextVPos}[1]{}
11 \newcommand{\fancytabsTextHPos}[1]{}
12 \newcommand{\fancytabsGap}[1]{}
13 \newcommand{\fancytabsFloor}[1]{}
14 \newcommand{\fancytabsRotate}[1]{}

```

---

### File 131 **l warp-fancyvrb.sty**

#### § 231 Package **fancyvrb**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg fancyvrb fancyvrb is supported with some patches.

**HTML classes** The fancy verbatim environment is placed inside a <div> of class fancyvrb. The label is placed inside a <div> of class fancyvrblabel. The verbatim text itself is placed inside a <div> of class verbatim.

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

**⚠ fancybox, fancyvrb**  
**⚠ \VerbatimFootnotes**  
**⚠ sectioning or displaymath**

```
\subsection[Subsection Name]
  {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbatim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
1 \RequirePackage{xcolor}%
2 for \convertcolorspec
3 \LWR@ProvidesPackagePass{fancyvrb}[2008/02/07]
```

Initial default patch for fancyvrb:

```
4 \fvset{frame=none}%
```

After the preamble is loaded, after any patches to Verbatim:

```
5 \AfterEndPreamble{
6 \LWR@traceinfo{Patching fancyvrb.}}
```

**\VerbatimFootnotes** Patched to use the new version.

```
7 \def\VerbatimFootnotes{%
8 \let\@footnotetext\@footnotetext%
9 \let\footnote\@footnote%
10 \let\@footnotetext\@footnotetext% l warp
11 }
```

**\V@footnotetext** Patches in a subset of l warp's \LWR@footnotetext to the fancyvrb version of \V@footnotetext.

```
12 \def\V@footnotetext{%
13 \LWR@traceinfo{\V@footnotetext}%
14 \global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
15 \unvbox\@footnotebox%
```

Remember the footnote number for \ref:

```
16 \protected@edef\@currentlabel{%
17   \csname p@footnote\endcsname\@thefnmark%
18 }% @currentlabel
```

Use HTML superscripts in the footnote even inside a `lateximage`:

```
19 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
20 \ifthenelse{%
21   \boolean{LWR@doingstartpars} \AND%
22   \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
23 }%
24 {}%
25 {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote mark to the list:

```
26 @makefnlist{}
```

The footnote text will follow after `\V@@@footnotetext` has completed.

```
27 \bgroup%
28 \aftergroup{\V@@@footnotetext}%
29 \ignorespaces%
30 }%
```

```
31 \preto\FVB@Verbatim{\LWR@forcenewpage}
32 \preto\FVB@LVerbatim{\LWR@forcenewpage}
33 % \preto\FVB@BVerbatim{\LWR@forcenewpage}% Fails, so done below.
```

Simplified to remove PDF formatting:

```
34 \def\fV@BeginListFrame@Single{%
35   \fV@SingleFrameLine{\z@}%
36 }
37
38 \def\fV@EndListFrame@Single{%
39   \fV@SingleFrameLine{\@ne}%
40 }
41
42 \def\fV@BeginListFrame@Lines{%
43   \fV@SingleFrameLine{\z@}%
44 }
45
46 \def\fV@EndListFrame@Lines{%
47   \fV@SingleFrameLine{\@ne}%
48 }
49
50 \renewcommand*\fV@SingleFrameSep{}
```

Adds HTML formatting:

```
51 \def\fV@BUseVerbatim#1{%
52   \LWR@atbeginverbatim{#1}{verbatim}%
53   \fV@BVerbatimBegin#1\fV@BVerbatimEnd%
54   \LWR@afterendverbatim{#1}%
55 }
```

`\LWR@FVstyle` Holds the style of the verbatim.

```
56 \newcommand*{\LWR@FVstyle}{}{}
```

The following patches to `\Verbatim` are executed at the start and end of the environment, depending on the choice of frame. Original code is from the `fancyvrb` package.

```
57 \newcommand*{\LWR@fvstartnone}{%
58 \LWR@traceinfo{fvstartnone}%
59 % \hbox to\z@{%
60 \BlockClass[\LWR@FVstyle]{fancyvrb}%
61 \LWR@stoppars%
62 \ifx\FV@LabelPositionTopLine\relax\else%
63   \ifx\FV@LabelBegin\relax\else%
64     \FancyVerbRuleColor{\LWR@FVfindbordercolor}%
65     \LWR@htmltagc{%
66       div class="fancyvrblabel" % extra space%
67         style="color: \LWR@origpound\LWR@tempcolor"%
68     }%
69     \LWR@print@textrm{\FV@LabelBegin}%
70     \LWR@htmltagc{/div}\LWR@orignewline%
71   \fi%
72 \fi%
73 \LWR@atbeginverbatim{0}{verbatim}%
74 }%
75 }%
76%
77 \newcommand*{\LWR@fvendnone}{%
78 \LWR@traceinfo{fvendnone}%
79 % \hbox to\z@{%
80 \LWR@afterendverbatim{0}%
81 \LWR@stoppars%
82 \ifx\FV@LabelPositionBottomLine\relax\else%
83   \ifx\FV@LabelEnd\relax\else%
84     \FancyVerbRuleColor{\LWR@FVfindbordercolor}%
85     \LWR@htmltagc{%
86       div class="fancyvrblabel" % extra space%
87         style="color: \LWR@origpound\LWR@tempcolor"%
88     }%
89     \LWR@print@textrm{\FV@LabelEnd}%
90     \LWR@htmltagc{/div}\LWR@orignewline%
91   \fi%
92 \fi%
93 \endBlockClass%
94 }%
95%
96 \newcommand*{\LWR@fvstartsingle}{%
97 \LWR@traceinfo{fvstartsingle}%
98 \LWR@fvstartnone%
99 \FV@BeginListFrame@Single%
100 }%
101%
102 \newcommand*{\LWR@fvendsingle}{%
103 \LWR@traceinfo{fvendsingle}%
104 \FV@EndListFrame@Single%
105 \LWR@fvendnone%
```

```

106 }
107
108 \newcommand*{\LWR@fvstartline}{%
109 \LWR@traceinfo{fvstartline}%
110 \LWR@fvstartnone%
111 % \setlength{\LWR@templengthone}{\baselineskip}%
112 \FV@BeginListFrame@Lines%
113 % \setlength{\baselineskip}{\LWR@templengthone}%
114 % \setlength{\baselineskip}{5pt}%
115 }
116
117 \newcommand*{\LWR@fvendline}{%
118 \LWR@traceinfo{fvendline}%
119 \FV@EndListFrame@Lines%
120 \LWR@fvendnone%
121 }

```

The following patches select the start/left/right/end behaviors depending on `frame`. Original code is from the `fancyvrb` package.

```

122 \newcommand*{\LWR@FVfindbordercolor}{%
123 \FancyVerbRuleColor%
124 \LWR@findcurrenttextcolor%
125 \color{black}%
126 }
127
128 % border width of \FV@FrameRule
129 \newcommand*{\LWR@FVborderstyle}[1]{%
130 padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ; % space
131 \LWR@FVfindbordercolor\LWR@indentHTMLtwo%
132 border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt % space
133 solid {\FancyVerbRuleColor{\LWR@origpound\LWR@tempcolor}} ; % space
134 }
135
136 \def\FV@Frame@none{%
137 \renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle}%
138 \let\FV@BeginListFrame\LWR@fvstartnone%
139 \let\FV@LeftListFrame\relax%
140 \let\FV@RightListFrame\relax%
141 \let\FV@EndListFrame\LWR@fvendnone}
142
143 \FV@Frame@none% default values
144
145 \def\FV@Frame@single{%
146 \renewcommand*{\LWR@FVstyle}{%
147     \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
148     \LWR@FVborderstyle{}%
149 }%
150 \let\FV@BeginListFrame\LWR@fvstartsingl%
151 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
152 \let\FV@RightListFrame\FV@RightListFrame@Single%
153 \let\FV@EndListFrame\LWR@fvendsingl}
154
155 \def\FV@Frame@lines{%
156 \renewcommand*{\LWR@FVstyle}{%

```

```

157      \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
158      \LWR@FVborderstyle{-top}%
159      \LWR@indentHTMLtwo%
160      \LWR@FVborderstyle{-bottom}%
161 }%
162 \let\FV@BeginListFrame\LWR@fvstartline%
163 \let\FV@LeftListFrame\relax%
164 \let\FV@RightListFrame\relax%
165 \let\FV@EndListFrame\LWR@fvendline}
166
167 \def\FV@Frame@topline{%
168 \renewcommand*\{\LWR@FVstyle}{%
169     \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
170     \LWR@FVborderstyle{-top}%
171 }%
172 \let\FV@BeginListFrame\LWR@fvstartline%
173 \let\FV@LeftListFrame\relax%
174 \let\FV@RightListFrame\relax%
175 \let\FV@EndListFrame\LWR@fvendnone}
176
177 \def\FV@Frame@bottomline{%
178 \renewcommand*\{\LWR@FVstyle}{%
179     \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
180     \LWR@FVborderstyle{-bottom}%
181 }%
182 \let\FV@BeginListFrame\LWR@fvstartnone%
183 \let\FV@LeftListFrame\relax%
184 \let\FV@RightListFrame\relax%
185 \let\FV@EndListFrame\LWR@fvendline}
186
187 \def\FV@Frame@leftline{%
188 \renewcommand*\{\LWR@FVstyle}{%
189     \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
190     \LWR@FVborderstyle{-left}%
191 }%
192 % To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)
193 \ifx\fancyVerbFillColor\relax%
194 \let\FV@FrameFillLine\relax%
195 \else%
196 \tempdima\FV@FrameRule\relax%
197 \multiply\tempdima-\tw@%
198 \edef\FV@FrameFillLine{%
199 {\noexpand\fancyVerbFillColor{\vrule@width\number\tempdima sp}}%
200 \kern-\number\tempdima sp}%
201 \fi%
202 \let\FV@BeginListFrame\LWR@fvstartnone%
203 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
204 \let\FV@RightListFrame\relax%
205 \let\FV@EndListFrame\LWR@fvendnone}

```

Adds the optional label to the top and bottom edges. Original code is from the **fancyvrb** package.

```

206 \def\FV@SingleFrameLine#1{%
207 % \hbox to\z@{%

```

```

208 %      \kern\leftmargin
209   \ifnum#1=\z@\relax
210     \let\FV@Label\FV@LabelBegin
211   \else
212     \let\FV@Label\FV@LabelEnd
213   \fi
214   \ifx\FV@Label\relax
215 %      \FancyVerbRuleColor{\vrule \@width\ linewidth \@height\ FV@FrameRule}%
216   \else
217     \ifnum#1=\z@
218 %        \setbox\z@\hbox{\strut\enspace\ FV@LabelBegin\enspace\strut}%
219         \ifx\ FV@LabelPositionTopLine\relax
220           \else
221             \fi
222           \else
223 %        \setbox\z@\hbox{\strut\enspace\ FV@LabelEnd\enspace\strut}%
224         \ifx\ FV@LabelPositionBottomLine\relax
225           \else
226             \fi
227           \fi
228   \fi
229 %      \hss
230 %    }
231 }

```

Processes each line, adding optional line numbers. Original code is from the `fancyvrb` package.

```

232 \def\FV@ListProcessLine#1{%
233   \hbox to \hsize{%
234 %      \kern\leftmargin
235   \hbox to \VerbatimHTMLWidth {%
236     \ifcscvoid{FV@LeftListNumber}{}{\kern 2.5em}%
237     \FV@LeftListNumber%
238 %      \FV@LeftListFrame
239     \FancyVerbFormatLine{#1}%
240     \hss%
241 %      \FV@RightListFrame
242     \FV@RightListNumber%
243   }%
244     \hss% required to avoid underfull hboxes
245 }
246 }

```

Env `BVerbatim`

```

247 \AtBeginEnvironment{BVerbatim}
248 {%
249 \LWR@forcenewpage% instead of \preto
250 \LWR@atbeginverbatim{0}{bverbatim}%
251 }
252
253 \AfterEndEnvironment{BVerbatim}
254 {%
255 \LWR@afterendverbatim{0}%

```

256 }

End of the modifications to make at the end of the preamble:

257 } % \AfterEndPreamble

---

### File 132 **l warp-fewerfloatpages.sty**

#### § 232 Package **fewerfloatpages**

Pkg fewerfloatpages **fewerfloatpages** is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{fewerfloatpages}[2020/02/14]
2 \newcommand\floatpagekeepfraction{\textfraction}
3 \newcounter{floatpagedeferlimit}
4 \newcounter{floatpagekeeplimit}
```

---

### File 133 **l warp-figcaps.sty**

#### § 233 Package **figcaps**

(Emulates or patches code by PATRICK W. DALY.)

Pkg figcaps **figcaps** is ignored.

**for HTML output:** Discard all options for **l warp-figcaps**:

```
1 \LWR@ProvidesPackageDrop{figcaps}[1999/02/23]
2 \newcommand*\figcapson(){}
3 \newcommand*\figcapsoff(){}
4 \newcommand*\printfigures(){}
5 \newcommand*\figmarkon(){}
6 \newcommand*\figmarkoff(){}
7 \def\figurecapname{Figure Captions}
8 \def\tablepagename{Tables}
9 \def\figurepagename{Figures}
```

---

### File 134 **l warp-figsize.sty**

#### § 234 Package **figsize**

(Emulates or patches code by ANTHONY A. TANBAKUCHI.)

Pkg figsize **figsize** is emulated.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{figsize}[2002/03/18]
```

---

Emulates a virtual 6×9 inch textsize.

```

2 \newlength{\figwidth}
3 \newlength{\figheight}
4
5 \newcommand{\SetFigLayout}[3][0]{%
6 \setlength{\figheight}{8in}%
7 \setlength{\figheight}{\figheight / #2}%
8 %
9 \setlength{\figwidth}{5.5in}%
10 \setlength{\figwidth}{\figwidth / #3}%
11 }

```

---

File 135 **l warp-fitbox.sty**

§ 235 Package **fitbox**

Pkg fitbox fitbox is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fitbox}[2019/02/20]

```

2 \NewDocumentCommand{\fitbox}{s o m}{%
3   \begin{BlockClass}{fitbox}
4     #3
5   \end{BlockClass}
6 }
7
8 \newcommand*\fitboxset[1] {}
9
10 \newdimen\fitboxnatheight
11 \newdimen\fitboxnatwidth
12
13 \newcommand\SetFitboxLayout[3][]{}

```

---

File 136 **l warp-fix2col.sty**

§ 236 Package **fix2col**

Pkg fix2col fix2col is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fix2col}[2015/11/13]

---

File 137 **l warp-fixme.sty**

§ 237 Package **fixme**

(Emulates or patches code by DIDIER VERRA.)

Pkg fixme fixme is patched for use by lwarf.

⚠ **external layouts** External layouts (\fxloadlayouts) are not supported.

User control is provided for setting the HTML styling of the “faces”. The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

**for HTML output:** 1 \LWR@ProvidesPackagePass{fixme}[2017/03/05]

Restore lwarf’s version of \@wrindex, ignoring the fixme package’s target option:

```
2 \let\@wrindex\LWR@wrindex
```

Float-related macros required by lwarf:

```
3 \newcommand{\ext@fixme}{\lox}
4
5 \renewcommand{\l@fixme}[2]{\hypertocfloat{1}{fixme}{lox}{#1}{#2}}
```

Other modifications:

```
6 \def\FXFaceInlineHTMLStyle{font-weight:bold}
7
8 \renewcommand*\FXLayoutInline[3]{ %
9 \InlineClass[\FXFaceInlineHTMLStyle]{fixmeinline}%
10 {\@fxtextrstd{#1}{#2}{#3}}%
11 }
12
13 \def\FXFaceEnvHTMLStyle{font-weight:bold}
14
15 \renewcommand*\FXEnvLayoutPlainBegin[2]{%
16 \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}%
17 \ignorespaces#2 \fxnotename{#1}: \ignorespaces}%
18
19 \renewcommand*\FXEnvLayoutPlainEnd[2]{\endBlockClass}%
20
21 \renewcommand*\FXEnvLayoutSignatureBegin[2]{%
22 \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}%
23 \fxnotename{#1}: \ignorespaces}%
24
25 \renewcommand*\FXEnvLayoutSignatureEnd[2]{\@fxsignature{#2}\endBlockClass}%
26
27 \def\FXFaceSignatureHTMLStyle{font-style:italic}
28
29 \DeclareRobustCommand*\@fxsignature[1]{%
30 \ifthenelse{\equal{#1}{}}{%
31 {}%
32 { -- \InlineClass[\FXFaceSignatureHTMLStyle]{fixmesignature}{#1}}%
33 }%
34 }
```

```
35
36 \def\FXFaceTargetHTMLStyle{font-style:italic}
37
38 \renewcommand\FXTargetLayoutPlain[2]{%
39     \InlineClass[\FXFaceTargetHTMLStyle]{fixmetarget}{#2}%
40 }
```

---

**File 138 l warp-fixmetodonotes.sty****§ 238 Package fixmetodonotes**

*(Emulates or patches code by GIOELE BARABUCCI.)*

Pkg fixmetodonotes fixmetodonotes is patched for use by l warp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{fixmetodonotes}[2013/04/28]

2 \renewcommand{\NOTES@addtolist}[2]{%
3     \refstepcounter{NOTES@note}%
4 %    \phantomsection% REMOVED
5     \addcontentsline{notes}{NOTES@note}{%
6         \protect\numberline{\theNOTES@note}{\#1}: \#2}%
7     }%
8 }
9
10 \renewcommand{\NOTES@marker}[2]{\fbox{%
11     \textcolor{#2}{% WAS \color
12         \textbf{\#1}}%
13 }}%
14
15 \renewcommand{\NOTES@colorline}[2]{%
16     \bgroup%
17         \ULon{\LWR@backgroundcolor{\#1}{\#2}}%
18 }
```

---

**File 139 l warp-flafter.sty****§ 239 Package flafter**

Pkg flafter flafter is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{flafter}[2018/01/08]
2 \providecommand\fl@trace[1]{}
```

---

**File 140 l warp-flippdf.sty****§ 240 Package flippdf**

Pkg flippdf flippdf is ignored.

---

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{flippdf}[2006/06/30]

2 \newcommand\FlipPDF{}
3 \newcommand\UnFlipPDF{}
```

---

File 141 **lwarp-float.sty**

§ 241      Package **float**

(Emulates or patches code by ANSELM LINGNAU.)

Pkg float float is emulated.

Float styles boxed and ruled are emulated by css and a float class according to style.

The HTML <figure> class is set to the float type, so css may also be used to format the float and its caption, according to float type. Furthermore, an additional class is set to the float style: plain, plaintop, boxed, or ruled, so css may be used to format by float style as well. Default formatting by css is provided for ruled and boxed styles.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{float}[2001/11/08]
```

\listof See section 75.2 for the \listof command.

\LWR@floatstyle The default float style:

```
2 \newcommand*\LWR@floatstyle[1]{plain}
```

\newfloat {<1: type>} {<2: placement>} {<3: ext>} [<4: within>]

Emulates the \newfloat command from the float package.

“placement” is ignored.

```
3 \NewDocumentCommand{\newfloat}{m m m o}{%
4 \IfValueTF{#4}{%
5 {\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}{%
6 {\DeclareFloatingEnvironment[fileext=#3]{#1}}{}}
```

Remember the float style:

```
7 \csedef{\LWR@floatstyle@#1}{\LWR@floatstyle}{%
```

**newfloat** package automatically creates the \listof command for new floats, but **float** does not, so remove \listof here in case it is manually created later.

```
8 \cslet{\listof#1s}\relax%
9 \cslet{\listof#1es}\relax%
```

Likesize, **newfloat** also creates \l@<type>, but **float** does not, so remove it here:

```
10 \cslet{\l@#1}\relax%
11 }
```

\floatname {⟨type⟩} {⟨name⟩}

Sets the text name of the float, such as “Figure”.

```
12 \NewDocumentCommand{\floatname}{m +m}{%
13     \SetupFloatingEnvironment{#1}{name=#2}%
14 }
```

\floatplacement {⟨type⟩} {⟨placement⟩}

Float placement is ignored.

```
15 \newcommand*{\floatplacement}[2]{%
16     \SetupFloatingEnvironment{#1}{placement=#2}%
17 }
```

\floatstyle {⟨style⟩}

Remember the style for future floats:

```
18 \newcommand{\floatstyle}[1]{%
19     \def\LWR@floatstyle{#1}%
20 }
```

\restylefloat \* {⟨type⟩}

Remember the style for this float:

```
21 \NewDocumentCommand{\restylefloat}{s m}{%
22     \csedef{LWR@floatstyle@#2}{\LWR@floatstyle}%
23 }
```

### File 142 lwarf-floatflt.sty

§ 242 Package **floatflt**

(Emulates or patches code by MATS DAHLGREN.)

Pkg floatflt floatflt is emulated.

**for HTML output:** Discard all options for lwarf-floatflt:

```
1 \LWR@ProvidesPackageDrop{floatflt}[1997/07/16]
```

Env [⟨⟩] offset {⟨type⟩} {⟨width⟩} Borrowed from the lwarf version of keyfloat:

```
2 \NewDocumentEnvironment{KFLTfloatflt@marginfloat}{O{-1.2ex} m m}%
3 {%
4     \begin{LWR@setvirtualpage}%
5     \ifblank{#3}{%
6         \LWR@BlockClassWP{%
7             float:right; %
8             width: 1.5in; % reasonable dummy width for word processor
9             margin:10pt%}
```

```

10      }{}%
11      {marginblock}%
12  }{%
13      \setlength{\LWR@templengthone}{#3}%
14      \LWR@BlockClassWP{%
15          float:right; %
16          width:\LWR@printlength{\LWR@templengthone}; % extra space
17          margin:10pt%
18      }{%
19          width:\LWR@printlength{\LWR@templengthone}%
20      }%
21      {marginblock}%
22  }%
23  \captionsetup{type=#2}%
24 }
25 {%
26     \endLWR@BlockClassWP%
27     \end{\LWR@setvirtualpage}%
28 }

```

**Env** floatingfigure [ $\langle placement \rangle$ ] [ $\langle width \rangle$ ]  
 29 \DeclareDocumentEnvironment{floatingfigure}{o m}  
 30 { \begin{KFLTfloatflt@marginfloat}{figure}{#2} }  
 31 { \end{KFLTfloatflt@marginfloat} }

**Env** floatingtable [ $\langle placement \rangle$ ]  
 32 \DeclareDocumentEnvironment{floatingtable}{o}  
 33 { \begin{KFLTfloatflt@marginfloat}{table}{} }  
 34 { \end{KFLTfloatflt@marginfloat} }

### File 143 **lwarf-floatpag.sty**

#### § 243 Package **floatpag**

(Emulates or patches code by VYTAS STATULEVIČIUS AND SIGITAS TOLUŠIS.)

Pkg floatpag floatpag is ignored.

for HTML output: Discard all options for lwarf-floatpag:

```

1 \LWR@ProvidesPackageDrop{floatpag}[2012/05/29]

2 \newcommand*\floatpagestyle[1]{}%
3 \newcommand*\rotfloatpagestyle[1]{}%
4 \newcommand*\thisfloatpagestyle[1]{}

```

---

File 144 **l warp-floatrow.sty**

§ 244 Package **floatrow**

(Emulates or patches code by OLGA LAPKO.)

Pkg floatrow floatrow is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{floatrow}[2008/08/02]

⚠ Misplaced alignment tab character & Use \StartDefiningTabulars and \StopDefiningTabulars before and after defining macros using \ttabbox with a tabular inside. See section 8.10.1.

⚠ subfig package When combined with the subfig package, while inside a subfloatrow \ffigbox and \ttabbox must have the caption in the first of the two of the mandatory arguments.

⚠ \FBwidth, \FBheight The emulation of floatrow does not support \FBwidth or \FBheight. These values are pre-set to .3\linewidth and 2in. Possible solutions include:

- Use fixed lengths. l warp will scale the HTML lengths appropriately.
- Use warpprint and warpHTML environments to select appropriate values for each case.
- Inside a warpHTML environment, manually change \FBwidth or \FBheight before the \ffigbox or \ttabbox. Use \FBwidth or \FBheight normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether subcaption was loaded. If not, it is assumed that subfig is used instead:

```

2 \newbool{\LWR@subcaptionloaded}
3
4 \AtBeginDocument{
5 \@ifpackageloaded{subcaption}
6 {\booltrue{\LWR@subcaptionloaded}}
7 {\boolfalse{\LWR@subcaptionloaded}}
8 }
```

\floatbox [⟨1 preamble⟩] {⟨2 captype⟩} [⟨3 width⟩] [⟨4 height⟩] [⟨5 vert pos⟩] {⟨6 caption⟩} {⟨7 object⟩}

Only parameters for captype, width, caption, and object are used.

LWR@insubfloatrow is true if inside a subfloatrow environment.

There are two actions, depending on the use of subcaption or subfig.

```
9 \NewDocumentCommand{\floatbox}{o m o o o +m +m}{%
```

```
10 \ifbool{LWR@subcaptionloaded}%
11 {%
  \subcaption
```

For `subcaption`:

```
12 \ifbool{LWR@insubfloatrow}%
13 {%
  \subcaption in a subfloatrow
```

`subfigure` and `subtable` environments take width as an argument.

```
14 \IfValueTF{#3}%
15 {%
  \nameuse{sub#2}{#3}%
  \nameuse{sub#2}{\linewidth}%
}%
17 {%
  subcaption in a subfloatrow%
}%
18 {%
  subcaption not in subfloatrow%
```

`figure` and `table` environments do not take a width argument.

```
19 \nameuse{#2}%
20 }%
21 #6%
22 %
23 #7
```

End the environments:

```
24 \ifbool{LWR@insubfloatrow}%
25 {%
  \nameuse{endsub#2}%
  \nameuse{end#2}%
}%
27 {%
  subcaption%
}%
28 {%
  assume subfig%
```

For `subfig`:

```
29 \ifbool{LWR@insubfloatrow}%
30 {%
  subfig in a subfloatrow%
```

`\subfloat` is a macro, not an environment.

Package `subfig`'s `\subfloat` command takes an optional argument which is the caption, but `\floatbox` argument #6 contains commands to create the caption and label, not the caption itself. Thus, `\caption` is temporarily disabled to return its own argument without braces.

```
31 \begingroup%
32 \let\caption\@firstofone%
33 \subfloat[#6]{#7}%
34 \endgroup%
35 }%
36 {%
  subfig in a subfloatrow%
}%
37 {%
  subfig package, but not a subfig%
```

`figure` and `table` are environments:

```
37 \nameuse{#2}%
38 #6%
39 %
40 #7%
41 \nameuse{end#2}%
42 }%
43 {%
  subfig package, but not a subfig%
}%
44 {%
  assume subfig%
```

Not used:

```

45 \newcommand*{\nocapbeside}{}%
46 \newcommand*{\capbeside}{}%
47 \newcommand*{\caption}{}%
48 \newlength{\FBwidth}%
49 \setlength{\FBwidth}{.3\linewidth}%
50 \newlength{\FBheight}%
51 \setlength{\FBheight}{2in}%
52 \newcommand*{\useFCwidth}{}%
53 \newcommand{\floatsetup}[2][]{%
54 \newcommand{\thisfloatsetup}[1]{%
55 \newcommand{\clearfloatsetup}[1]{%
56 \newcommand*{\killfloatstyle}{}%

```

\newfloatcommand {⟨1 command⟩} {⟨2 captype⟩} [⟨3 preamble⟩] [⟨4 default width⟩]

Preamble and default width are ignored.

```

57 \NewDocumentCommand{\newfloatcommand}{m m o o}{%
58 @namedef{#1}{%
59 \floatbox{#2}{%
60 }%
61 }%

```

\renewfloatcommand {⟨1 command⟩} {⟨2 captype⟩} [⟨3 preamble⟩] [⟨4 default width⟩]

Preamble and default width are ignored.

```

62 \NewDocumentCommand{\renewfloatcommand}{m m o o}{%
63 @namedef{#1}{%
64 \floatbox{#2}{%
65 }%
66 }%

```

\ffigbox [⟨width⟩] [⟨height⟩] [⟨vposn⟩] {⟨caption commands⟩} {⟨contents⟩}

```

67 \newfloatcommand{ffigbox}{figure}[\nocapbeside]{}%

```

\ttabbox [⟨width⟩] [⟨height⟩] [⟨vposn⟩] {⟨caption commands⟩} {⟨contents⟩}

```

68 \newfloatcommand{ttabbox}{table}[\caption][\FBwidth]{}%

```

\fcapside [⟨width⟩] [⟨height⟩] [⟨vposn⟩] {⟨caption commands⟩} {⟨contents⟩}

```

69 \newfloatcommand{fcapside}{figure}[\capbeside]{}%

```

Env floatrow [⟨numfloats⟩]

The row of floats is placed into a <div> of class floatrow.

```

70 \newenvironment*{floatrow}[1][2]{%
71 {%
72     \begin{LWR@setvirtualpage}*{%
73         \BlockClass{floatrow}}%

```

```

74 }
75 {
76     \endBlockClass%
77     \end{LWR@setvirtualpage}%
78 }
```

Keys for \DeclareNewFloatType:

```

79 \newcommand*\LWR@frowkeyplacement(){}
80 \newcommand*\LWR@frowkeyname(){}
81 \newcommand*\LWR@frowkeyfileext(){}
82 \newcommand*\LWR@frowkeywithin(){}
83 \newcommand*\LWR@frowkeycapstyle(){}
84
85 \define@key{frowkeys}{placement}{}
86 \define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}
87 \define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}
88 \define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}
89 \define@key{frowkeys}{relatedcapstyle}{}
```

\DeclareNewFloatType {⟨type⟩} {⟨options⟩}

Use \listof{type}{Title} to print a list of the floats.

```
90 \newcommand*\LWR@DeclareNewFloatType[2]{%
```

Reset key values:

```

91 \renewcommand*\LWR@frowkeyplacement(){}
92 \renewcommand*\LWR@frowkeyname(){}
93 \renewcommand*\LWR@frowkeyfileext){}
94 \renewcommand*\LWR@frowkeywithin){}
95 \renewcommand*\LWR@frowkeycapstyle}{}
```

Read new key values:

```

96 \LWR@traceinfo{about to setkeys frowkeys}%
97 \setkeys{frowkeys}{#2}%
98 \LWR@traceinfo{finished setkeys frowkeys}%

```

Create a new float with optional [within]:

```

99 \ifthenelse{\equal{\LWR@frowkeywithin}{}}{%
100 {%
101     \DeclareFloatingEnvironment[
102         placement=\LWR@frowkeyplacement,
103         fileext=\LWR@frowkeyfileext
104     ]{#1}%
105 }%
106 {%
107     \DeclareFloatingEnvironment[
108         placement=\LWR@frowkeyplacement,
109         fileext=\LWR@frowkeyfileext,
110         within=\LWR@frowkeywithin
111     ]{#1}%
112 %     \LWR@traceinfo{finished newfloat #1}%
113 }%
```

Rename the float if a name was given:

```
114 \ifthenelse{\equal{\LWR@frowkeyname}{}}{%
115   {}%
116   {}%
117   \SetupFloatingEnvironment[#1]{name={\LWR@frowkeyname}}%
118 }%
119 }
```

Not used:

```
120 \newcommand{\buildFbbox}[2]{}
121 \newcommand*{\CenterFloatBoxes}{}%
122 \newcommand*{\TopFloatBoxes}{}%
123 \newcommand*{\BottomFloatBoxes}{}%
124 \newcommand*{\PlainFloatBoxes}{}%
125
126 \newcommand{\capsubrowsettings}{}%
127
128 \NewDocumentCommand{\RawFloats}{o o}{}%
```

\RawCaption {*text*}

To be used inside a minipage or parbox.

```
129 \newcommand{\RawCaption}[1]{#1}
```

\floatfoot {*text*}

Places additional text inside a float, inside a css <div> of class floatfoot.

```
130 \NewDocumentCommand{\floatfoot}{s +m}{%
131 \begin{BlockClass}{floatfoot}%
132 #2%
133 \end{BlockClass}%
134 }
```

Used to compute \linewidth.

```
135 \newbool{\LWR@insubfloatrow}%
136 \boolfalse{\LWR@insubfloatrow}
```

Env subfloatrow [*num\_floats*]

```
137 \newenvironment*{subfloatrow}[1][2]%
138 {
```

The row of floats is placed into a <div> of class floatrow:

```
139 \LWR@forcenewpage%
140 \BlockClass{floatrow}
```

While inside the floatrow, LWR@insubfloatrow is set true, which tells \floatbox to use \subfigure or \subtable.

```
141 \begingroup%
142 \booltrue{\LWR@insubfloatrow}
```

```
143 }
144 {
145 \endgroup
146 \endBlockClass
147 \boolfalse{LWR@insubfloatrow}
148 }
```

---

File 145 **l warp-fltrace.sty**

§ 245 Package **fltrace**

Pkg fltrace fltrace is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fltrace}[2018/01/08]

```
2 \def\tracefloats{}
3 \def\tracefloatsoff{}
4 \def\tracefloatvals{}
```

---

File 146 **l warp-flushend.sty**

§ 246 Package **flushend**

(Emulates or patches code by SIGITAS TOLUŠIS.)

Pkg flushend flushend is ignored.

for HTML output: Discard all options for l warp-flushend:

```
1 \LWR@ProvidesPackageDrop{flushend}[2017/03/27]

2 \newcommand*\flushend(){}
3 \newcommand*\raggedend(){}
4 \newcommand*\flushcsend(){}
5 \newcommand*\raggedcsend(){}
6 \newcommand*\atColsBreak}[1]{}
7 \newcommand*\atColsEnd}[1]{}
8 \newcommand*\showcsendrule{}{}
```

---

File 147 **l warp-fnbreak.sty**

§ 247 Package **fnbreak**

Pkg fnbreak fnbreak is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{fnbreak}[2012/01/01]

```
2 \newcommand*{\fnbreakverbose}{}  
3 \newcommand*{\fnbreaknonverbose}{}  
4 \newcommand*{\fnbreaklabel}{}  
5 \newcommand*{\fnbreaknolabel}{}  


---


```

**File 148 l warp-fncychap.sty****§ 248 Package fncychap**

(Emulates or patches code by ULF A. LINDGREN.)

Pkg fncychap fncychap is ignored.

for HTML output Discard all options for l warp-fncychap:

```
1 \LWR@ProvidesPackageDrop{fncychap}[2007/07/30]  
  
2 \def\mghrulefill#1{}  
3 \def\ChNameLowerCase{}  
4 \def\ChNameUpperCase{}  
5 \def\ChNameAsIs{}  
6 \def\ChTitleLowerCase{}  
7 \def\ChTitleUpperCase{}  
8 \def\ChTitleAsIs{}  
9 \newcommand{\ChRuleWidth}[1]{}  
10 \newcommand{\ChNameVar}[1]{}  
11 \newcommand{\ChNumVar}[1]{}  
12 \newcommand{\ChTitleVar}[1]{}  
13 \newcommand{\TheAlphaChapter}{}  
14 \newcommand{\DOCH}{}  
15 \newcommand{\DOTI}[1]{}  
16 \newcommand{\DOTIS}[1]{}  
17 \newlength{\mylen}  
18 \newlength{\myhi}  
19 \newlength{\px}  
20 \newlength{\py}  
21 \newlength{\pyy}  
22 \newlength{\pxx}  
23 \newlength{\RW}  
24 \newcommand{\FmN}[1]{#1}  
25 \newcommand{\FmTi}[1]{#1}
```

---

**File 149 l warp-fnlineno.sty****§ 249 Package fnlineno**

Pkg fnlineno fnlineno is ignored.

for HTML output 1 \LWR@ProvidesPackageDrop{fnlineno}[2011/01/07]

---

File 150 **l warp-fnpara.sty**

§ 250 Package **fnpara**

Pkg fnpara fnpara is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fnpara}

---

File 151 **l warp-fnpos.sty**

§ 251 Package **fnpos**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg fnpos fnpos is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fnpos}[1999/07/14]

2 \newcommand\*{\makeFNbottom}{}  
3 \newcommand\*{\makeFNmid}{}  
4 \newcommand\*{\makeFNbelow}{}  
5 \newcommand\*{\makeFNabove}{}

---

File 152 **l warp-fontawesome.sty**

§ 252 Package **fontawesome**

(Emulates or patches code by XAVIER DANAUX.)

Pkg fontawesome fontawesome is patched for use by l warp.

Hashed inline images are used, as there may not be Unicode support for all icons.

⚠ **poppler syntax warning**

If using pdfLATEX, *poppler* may issue a syntax warning regarding parsing a ligature component. XeLATEX or LuaLATEX may be used to avoid this warning.

In the following, the general strategy is to intercept \symbol and embed it inside a lateximage. These changes are done inside a local group.

For pdfLATEX, the alt tag includes the icon (symbol) number. For XeLATEX and LuaLATEX, the alt tag is generic.

**for HTML output:** 1 \LWR@ProvidesPackagePass{fontawesome}[2016/05/15]

```
2 \LetLtxMacro{\LWR@orig@symbol}{\symbol}
3
4 \ifxetexorluatex
5
6 \newfontfamily{\LWR@orig@FA}{FontAwesome}
7
8 \newcommand*{\LWR@fontawesome@xelatex@symbol}[1]{%
9     \LWR@findcurrenttextcolor%
10    \begin{lateximage}*[icon][fontawesomexetex#1SZ\LWR@font@size{}CL\LWR@tempcolor]%
11        \csuse{\LWR@font@size}%
12        \LWR@orig@FA%
13        \LWR@orig@symbol{#1}%
14    \end{lateximage}%
15 }
16
17 \RenewDocumentCommand{\FA}{%
18     \LetLtxMacro{\symbol}{\LWR@fontawesome@xelatex@symbol}%
19 }
20
21 \else
22
23 \newcommand*{\LWR@fontawesome@symbolX}[2]{%
24     \LWR@findcurrenttextcolor%
25     \begin{lateximage}*[icon #1][fontawesome#2#1SZ\LWR@font@size{}CL\LWR@tempcolor]%
26         \csuse{\LWR@font@size}%
27         \fontencoding{U}\fontfamily{fontawesome#2}\selectfont%
28         \LWR@orig@symbol{#1}%
29     \end{lateximage}%
30 }
31
32 \newcommand*{\LWR@fontawesome@symbolone}[1]{%
33     \LWR@fontawesome@symbolX{#1}{one}%
34 }
35
36 \newcommand*{\LWR@fontawesome@symboltwo}[1]{%
37     \LWR@fontawesome@symbolX{#1}{two}%
38 }
39
40 \newcommand*{\LWR@fontawesome@symbolthree}[1]{%
41     \LWR@fontawesome@symbolX{#1}{three}%
42 }
43
44 \renewrobustcmd\FAone{%
45     \LetLtxMacro{\symbol}{\LWR@fontawesome@symbolone}%
46 }
47
48 \renewrobustcmd\FAtwo{%
49     \LetLtxMacro{\symbol}{\LWR@fontawesome@symboltwo}%
50 }
51
52 \renewrobustcmd\FAthree{%
53     \LetLtxMacro{\symbol}{\LWR@fontawesome@symbolthree}%
54 }
55 \fi
```

---

**File 153 l warp–fontawesome5.sty****§ 253 Package fontawesome5**

(Emulates or patches code by MARCEL KRÜGER.)

Pkg fontawesome5 fontawesome5 is patched for use by l warp.

Hashed inline images are used, as there may not be Unicode support for all icons.

The alt tag has the name of the icon.

**for HTML output:** 1 \LWR@ProvidesPackagePass{fontawesome5}[2018/07/27]

```
2 \ExplSyntaxOn
3 \cs_set:Nn\fontawesome_use_icon:n{%
4     \LWR@findcurrenttextcolor
5     \cs_if_exist:cTF{c__fontawesome_slot_#2_tl}{%
6         \begin{lateximage}*[#2][fontawesome5#1SZ\LWR@font@size{}CL\LWR@tempcolor]
7         \csuse{\LWR@font@size}
8         \exp_last_unbraced:Nv
9             \__fontawesome_icon_at:nnnn
10            {c__fontawesome_slot_#2_tl}
11            {#1}{#2}
12        \end{lateximage}
13    }{
14        \msg_error:nnxx{fontawesome5}{icon-not-found}{#2}{#1}
15    }
16 }
17 \ExplSyntaxOff
```

---

**File 154 l warp–fontaxes.sty****§ 254 Package fontaxes**

(Emulates or patches code by ANDREAS BÜHMANN, MICHAEL UMMELS.)

Pkg fontaxes fontaxes is emulated for HTML, and used as-is for print output.

Functionality for small caps is in the l warp core. Swashes and figure styles are ignored for HTML.

**for HTML output:** 1 \LWR@ProvidesPackagePass{fontaxes}[2014/03/23]

```
2 \newrobustcmd{\LWR@HTML@sscshape}{\LWR@HTML@scshape}
3 \LWR@formatted{sscshape}
4 \newcommand*{\LWR@null@sscshape}{}{5}
```

---

```

6 \newrobustcmd{\LWR@HTML@textssc}[1]{\textsc{#1}}
7 \LWR@formatted{textssc}
8 \newcommand*\LWR@null@textssc[1]{#1}
9
10 \ifdef{\LWR@HTML@swshape}{}{%
11   \newcommand{\LWR@HTML@swshape}{}
12   \LWR@formatted{swshape}
13   \newcommand*\LWR@null@swshape[1]{}
14
15   \newcommand{\LWR@HTML@textsw}[1]{#1}
16   \LWR@formatted{textsw}
17   \newcommand*\LWR@null@textsw[1]{#1}
18 }
19
20 \appto{\LWR@nullfonts}{%
21 \LetLtxMacro\sscsshape\LWR@null@sscsshape%
22 \LetLtxMacro\textssc\LWR@null@textssc%
23 \LetLtxMacro\swshape\LWR@null@swshape%
24 \LetLtxMacro\textsw\LWR@null@textsw%
25 }

```

---

### File 155 **l warp–fontenc.sty**

#### § 255 Package **fontenc**

Pkg **fontenc** If using pdflATEX, l warp used to require fontenc be loaded before l warp, but now l warp itself loads \fontenc with T1 encoding, which l warp requires. fontenc is now allowed to be loaded with another encoding after l warp.

l warp–fontenc is no longer necessary, but is still provided to overwrite older versions.

**for HTML output:** 1 \LWR@ProvidesPackagePass{fontenc}[2017/04/05]

---

### File 156 **l warp–footmisc.sty**

#### § 256 Package **footmisc**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg **footmisc** footmisc is emulated.

l warp incidentally happens to emulate the stable option.

1 \LWR@ProvidesPackageDrop{footmisc}[2011/06/06]

Some nullified commands:

```

2 \newcommand{\footnotelayout}{}
3 \newcommand{\setfnsymbol}[1]{}

```

```

4 \NewDocumentCommand{\DefineFNsymbols}{s m o m}{}%
5
6 \newdimen\footnotemargin
7 \footnotemargin1.8em\relax
8
9 \newcommand*\hangfootparskip{0.5\baselineskip}
10 \newcommand*\hangfootparindent{0em}%
11
12 \let\pagefootnoterule\footnoterule
13 \let\mpfootnoterule\footnoterule
14 \def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}
15
16 \providecommand*\multiplefootnotemarker}{3sp}
17 \providecommand*\multfootsep}{,}

```

Using `cleveref`:

```
18 \providecommand*\footref[1]{\labelcref{#1}}
```

The following work as-is:

```

19 \newcommand\mpfootnotemark{%
20   \@ifnextchar[%%
21     \@xmpfootnotemark%
22   {%
23     \stepcounter\@mpfn%
24     \protected@xdef\@thefnmark{\thempfn}%
25     \@footnotemark%
26   }%
27 }
28 \def\@xmpfootnotemark[#1]{%
29   \begingroup%
30   \csname c@\@mpfn\endcsname #1\relax%
31   \unrestored@protected@xdef\@thefnmark{\thempfn}%
32   \endgroup%
33   \@footnotemark%
34 }

```

### File 157 **lwarp-footnote.sty**

## § 257 Package **footnote**

(Emulates or patches code by MARK WOODING.)

Pkg **footnote** **footnote** is used with minor patches.

**for HTML output:** 1 \LWR@ProvidesPackagePass{footnote}[1997/01/28]

Removed print-version formatting:

```

2 \def\fn@startnote{%
3 %   \parboxrestore%

```

```

4 \protected@edef@\currentlabel{\csname p@\@mpfn\endcsname\@thefnmark}%
5 % \color@begingroup% *** conflicts with l warp
6 }
7
8 \% \let\fn@endnote\color@endgroup% *** conflicts with l warp
9 \def\fn@endnote{%
10 \LWR@htmltagc{/ \LWR@tagregularparagraph}%
11 \LWR@newline%
12 }

```

Removed print-version formatting:

```

13 \def\fn@startfntext{%
14   \setbox\z@\vbox\bgroup%
15     \fn@startnote%
16     \ignorespaces%
17 }

```

Removed print-version formatting, added closing paragraph tag:

```

18 \def\fn@endfntext{%
19   \LWR@htmltagc{/ \LWR@tagregularparagraph}%
20   \LWR@newline%
21   \egroup%
22   \begingroup%
23   \let\@makefntext\empty%
24   \let\@finalstrut\gobble%
25   \LetLtxMacro\rule\gobbletwo% *8* also the optional argument?
26   \@footnotetext{\unvbox\z@}%
27   \endgroup%
28 }

```

These have been redefined, so re-\let them again:

```

29 \let\endfootnote\fn@endfntext
30 \let\endfootnotetext\endfootnote

```

### File 158 **l warp-footnotebackref.sty**

#### § 258 Package **footnotebackref**

Pkg footnotebackref footnotebackref is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{footnotebackref}[2012/07/01]

### File 159 **l warp-footnotehyper.sty**

#### § 259 Package **footnotehyper**

Pkg footnotehyper footnotehyper is a hyperref-safe version of footnote. For l warp, footnotehyper is em-

ulated.

**for HTML output:** Discard all options for l warp-footnotehyper:

```
1 \RequirePackage{footnote}
2 \LWR@ProvidesPackageDrop{footnotehyper}[2018/01/23]
```

---

#### File 160 **l warp-footnoterange.sty**

#### § 260 Package **footnoterange**

(Emulates or patches code by H.-MARTIN MÜNCH.)

Pkg footnoterange footnoterange is patched for use by l warp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{footnoterange}[2012/02/17]
2 \csletcs{footnoterange}{footnoterange*}
3 \csletcs{endfootnoterange}{endfootnoterange*}
```

---

#### File 161 **l warp-footnpag.sty**

#### § 261 Package **footnpag**

Pkg footnpag footnpag is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{footnpag}
```

---

#### File 162 **l warp-foreign.sty**

#### § 262 Package **foreign**

(Emulates or patches code by PHILIP G. RATCLIFFE.)

Pkg foreign foreign is patched for use by l warp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{foreign}[2012/09/25]
2 \renewcommand\foreignabbrfont{\emph{}}
```

---

#### File 163 **l warp-forest.sty**

#### § 263 Package **forest**

(Emulates or patches code by SAŠO ŽIVANOVIC.)

Pkg forest forest is patched for use by lwarp.

⚠ \Forest\* The starred version of the macro \Forest\* is not supported. lwarp encases each lateximage in an environment, so the global results of the starred \Forest\* are lost.

**for HTML output:** 1 \LWR@ProvidesPackagePass{forest}[2017/07/14]

```

2 \BeforeBeginEnvironment{forest}{\begin{lateximage}[forest]}
3
4 \AfterEndEnvironment{forest}{\end{lateximage}}
5
6 \RenewDocumentCommand{\Forest}{s D(){} m}{%
7   \forest@config{#2}%
8   \IfBooleanTF{#1}{%
9     \PackageError{lwarp-forest}{%
10    {Starred } \Forest is not supported}%
11    {Lwarp uses an environment for images, but \Forest* cannot work in an environment.}%
12    \let\forest@next\forest@env%
13    }{\let\forest@next\forest@grouppar@env}%
14    \begin{lateximage}[-forest-\~\PackageDiagramAltText]{} lwarp
15  \forest@next{#3}%
16  \end{lateximage}%
17 } lwarp
17 }
```

---

#### File 164 lwarp-fouridx.sty

#### § 264 Package fouridx

(Emulates or patches code by STEFAN KARRMANN.)

Pkg fouridx fouridx works as-is with SVG math, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{fouridx}[2013/11/21]

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{%
4   \newcommand{\fourIdx}[5]{%
5     \vphantom{#5}^{#1}_{#2}{}_{#3}{}^{#4}{}_{#5}%
6   }%
7 }
8 \end{warpMathJax}
```

---

#### File 165 lwarp-framed.sty

#### § 265 Package framed

(Emulates or patches code by DONALD ARSENEAU.)

Pkg framed framed is supported and patched by lwarp.

**for HTML output:** Accept all options for l warp-framed:

```
1 \LWR@ProvidesPackagePass{framed}[2011/10/22]
2 \RequirePackage{xcolor}%
3
4 \renewenvironment{framed}{%
5 \LWR@forcenewpage
6 \BlockClass{framed}%
7 }
8 {\endBlockClass}
9
10 \renewenvironment{oframed}{%
11 \LWR@forcenewpage
12 \BlockClass{framed}%
13 }
14 {\endBlockClass}
15
16
17 \renewenvironment{shaded}{%
18 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
19 \LWR@forcenewpage
20 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
21 }
22 {\endBlockClass}
23
24 \renewenvironment{shaded*}{%
25 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
26 \LWR@forcenewpage
27 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
28 }
29 {\endBlockClass}
30
31
32 \renewenvironment{leftbar}{%
33 \LWR@forcenewpage
34     \BlockClass{framedleftbar}%
35     \def\FrameCommand{}%
36     \MakeFramed {}%
37 }%
38 {\endMakeFramed\endBlockClass}
39
40
41 \renewenvironment{snugshade}{%
42 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
43 \LWR@forcenewpage
44 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
45 }
46 {\endBlockClass}
47
48 \renewenvironment{snugshade*}{%
49 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
50 \LWR@forcenewpage
51 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
52 }
53 {\endBlockClass}
```

```
54
55 \let\oframed\framed
56 \let\endoframed\endframed
57
58
59 \RenewEnviron{titled-frame}[1]{%
60 \CustomFBox{\#1}{}{0pt}{0pt}{0pt}{\BODY}
61 }

\CustomFBox {\langle toptitle\rangle} {\langle bottitle\rangle} {\langle thicknessstop\rangle} {\langle bottom\rangle} {\langle left\rangle} {\langle right\rangle}
{\langle text contents\rangle}

62 \renewcommand{\CustomFBox}[7]{%
63 \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
64 \LWR@forcenewpage
65 \begin{BlockClass}[border: 3px solid \LWR@origpound\LWR@tempcolor]{framed}%
66 \ifthenelse{\isempty{\#1}}{}{%
67   \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
68     \textcolor{TFTTitleColor}{\textbf{\#1}}%
69   \end{BlockClass}%
70 }%
71 }%
72 #7
73
74 \ifthenelse{\isempty{\#2}}{}{%
75   \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
76   \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
77     \textcolor{TFTTitleColor}{\textbf{\#2}}%
78   \end{BlockClass}%
79 }%
80 \end{BlockClass}
81 }

\TitleBarFrame [\langle marker\rangle] {\langle title\rangle} {\langle contents\rangle}

82 \renewcommand{\TitleBarFrame}[3][]{%
83 \CustomFBox
84   {\#2}{}%
85   \fboxrule\fboxrule\fboxrule\fboxrule
86   {\#3}%
87 }

88 \renewcommand{\TF@Title}[1]{\#1}

MakeFramed {\langle settings\rangle}

89 \let\MakeFramed\relax
90 \let\endMakeFramed\relax
91
92 \NewEnviron{MakeFramed}[1]{%
93 \FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
94 }
```

```
\fb@put@frame {\frame cmd no split} {\frame cmd split}
```

```
95 \renewcommand*\{\fb@put@frame}[2]{%
96 \relax%
97 \@tempboxa%
98 }
```

---

File 166 **l warp-ftcap.sty**

§ 266 Package **ftcap**

Pkg **ftcap** **ftcap** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{ftcap}

---

File 167 **l warp-ftnright.sty**

§ 267 Package **ftnright**

Pkg **ftnright** **ftnright** is ignored.

**for HTML output:** Discard all options for **l warp-ftnright**:

```
1 \LWR@ProvidesPackageDrop{ftnright}[2014/10/28]
```

---

File 168 **l warp-fullminipage.sty**

§ 268 Package **fullminipage**

Pkg **fullminipage** **fullminipage** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fullminipage}[2014/07/06]

```
2 \newenvironment{fullminipage}[1][]{\{}{\}}
```

---

File 169 **l warp-fullpage.sty**

§ 269 Package **fullpage**

Pkg **fullpage** **fullpage** is ignored.

**for HTML output:** Discard all options for **l warp-fullpage**:

```
1 \LWR@ProvidesPackageDrop{fullpage}[1994/06/01]
```

---

**File 170 l warp-fullwidth.sty****§ 270 Package **fullwidth****

*(Emulates or patches code by MARCO DANIEL.)*

Pkg **fullwidth** **fullwidth** is emulated.

A minipage is used, of no HTML width.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fullwidth}[2011/11/18]

```
2 \newenvironment*{fullwidth}[1][]{%
3 \minipage{fullwidth}%
4 \minipage{\linewidth}%
5 }%
6 {%
7 \endminipage%
8 }
```

---

**File 171 l warp-fwlw.sty****§ 271 Package **fwlw****

Pkg **fwlw** **fwlw** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fwlw}

```
2 \newbox\FirstWordBox \global\setbox\FirstWordBox\hbox{}%
3 \newbox\NextWordBox \global\setbox\NextWordBox\hbox{}%
4 \newbox\LastWordBox \global\setbox\LastWordBox\hbox{}%
5 \def\ps@fwlwhead{}%
6 \def\ps@NextWordFoot{}
```

---

**File 172 l warp-gensymb.sty****§ 272 Package **gensymb****

*(Emulates or patches code by WALTER SCHMIDT.)*

Pkg **gensymb** **gensymb** works as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{gensymb}[2003/07/02]

---

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\degree}{\mathrm{^\circ}}}
4 \CustomizeMathJax{\newcommand{\celsius}{\text{\textnormal{\'{e}}}}}
5 \CustomizeMathJax{\newcommand{\perthousand}{\text{\textnormal{‰}}}}
6 \CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
7 \CustomizeMathJax{\newcommand{\micro}{\mathrm{\mu}}}
8 \end{warpMathJax}

```

---

File 173 **l warp-gentombow.sty**

§ 273 Package **gentombow**

Pkg gentombow gentombow is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{gentombow}[2018/05/17]

```

2 \newcommand{\settombowbanner}[1]{}
3 \newcommand{\settombowbannerfont}[1]{}
4 \newcommand{\settombowwidth}[1]{}
5 \newcommand{\settombowbleed}[1]{}
6 \newcommand{\settombowcolor}[1]{}

```

---

File 174 **l warp-geometry.sty**

§ 274 Package **geometry**

(Emulates or patches code by HIDEO UMEKI.)

Pkg geometry geometry is preloaded by l warp, but must be nullified as seen by the user's source code.

**for HTML output:** Discard all options for l warp-geometry:

1 \LWR@ProvidesPackageDropA{geometry}[2018/04/16]

If geometry is never loaded by the user, it will be loaded by l warp \AtBeginDocument. If this is the case, the page layout should not be changed but the user macros should still be nullified.

2 \ifbool{\LWR@allowanothergeometry}{%

Assign and set the selected geometry with reset prepended. \AtEndPreamble l warp will save this, then set its own geometry.

```

3 \edef\LWR@tempone{reset,\optionlist{@currname.\@currext}}%
4 \expandafter\lWR@origgeometry\expandafter{\LWR@tempone}%
5 }% \LWR@allowanothergeometry

```

The user-level commands are nullified:

```
6 \renewcommand*\{\geometry}{1}{}  
7 \renewcommand*\{\newgeometry}{1}{}  
8 \renewcommand*\{\restoregeometry}{}  
9 \renewcommand*\{\savegeometry}{1}{}  
10 \renewcommand*\{\loadgeometry}{1}{}  
_____
```

### File 175 **l warp-ghsystem.sty**

## § 275 Package **ghsystem**

*(Emulates or patches code by CLEMENS NIEDERBERGER.)*

Pkg **ghsystem** **ghsystem** is patched for use by **l warp**.

- ⚠ **\ghspic images** Images must be provided in SVG format, unless JPG is specified. It is recommended to create a local `images` directory, copy into it the relevant PDF **ghsystem** images, and then convert them with

Enter ⇒ **l warpmk pdftosvg images/\*.pdf**

**for HTML output:** 1 \LWR@ProvidesPackagePass{ghsystem}[2020/02/17]

```
2 \ExplSyntaxOn  
3  
4 \cs_set_protected:Npn \ghsystem_filler:n #1  
5   { \emph { \textless#1 \textgreater } }  
6  
7 \cs_set_protected:Npn \ghsystem_pic:n #1  
8  {  
9    \__ghsystem_includegraphics:xn  
10    {  
11      scale = \fp_to_tl:N \l__ghsystem_picture_scale_fp  
12      width = 1.25cm  
13      \exp_not:V \l__ghsystem_picture_includegraphics_tl  
14    }  
15    { ghsystem_ #1 . \l__ghsystem_picture_type_tl }  
16  }  
17  
18 \ExplSyntaxOff  
_____
```

### File 176 **l warp-gloss.sty**

## § 276 Package **gloss**

*(Emulates or patches code by JOSE LUIS DÍAZ, JAVIER BEZOS.)*

Pkg **gloss** **gloss** is patched for use by **l warp**.

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

**for HTML output:** 1 \LWR@ProvidesPackagePass{gloss}[2002/07/26]

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
2 \xpatchcmd{\gls@gloss@iii}
3   {\thepage}
4   {\theLWR@previousautopagelabel}
5   {}
6   {\LWR@patcherror{gloss}{\gls@gloss@iii}}
7
8 \def\gls@page@i#1#2{%
9   \endgroup%
10  \global\@namedef{glsp@#1}{\nameref{\BaseJobname-autopage-#2}}}%
```

### File 177 **lwarp-glossaries.sty**

## § 277 Package **glossaries**

(Emulates or patches code by NICOLA L.C. TALBOT.)

Pkg **glossaries**  
**processing glossaries**  
 Opt **GlossaryCmd**  
 Default: **makeglossaries**  
 Opt [lwarpmk] **printglossary**  
 Opt [lwarpmk] **htmlglossary**

**lwarpmk** has the commands **lwarpmk printglossary** and **lwarpmk htmlglossary**, which process the glossaries created by the **glossaries** package using that package's **makeglossaries** program.

The shell command to execute is set by the **lwarp** option **GlossaryCmd**, which defaults to **makeglossaries**. The print or HTML glossary filename is appended to this command.

**⚠ makeglossaries not found**

In some situations it may be required to modify the default command, such as to add the **perl** command in front:

```
\usepackage[
  GlossaryCmd={perl makeglossaries},
] {lwarp}
```

**xindy** language To set the language to use for processing glossaries with **xindy**:

```
\usepackage[
  GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for **makeglossaries** may be set as well.

### placement and toc options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

**Numbered section, on its own HTML page:**

---

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
...
\printglossaries
```

**Unnumbered section, inline with the current HTML page:**

```
\usepackage[xindy,toc]{glossaries}
...
\printglossaries
```

**Unnumbered section, on its own HTML page:**

```
\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries
```

 **glossary style** The default `style=item` option for `glossaries` conflicts with `lwarp`, so the style is forced to `index` instead.

 **number list** The page number list in the printed form would become `\nameref`s in `HTML`, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

**print/HTML versions** The print and `HTML` versions of the glossary differ in their internal page numbers. Separate commands for generating print and `HTML` glossaries are used, even though the page number is currently ignored.

**for HTML output:**

```
1 \PassOptionsToPackage{xindy}{glossaries}
2
3 \LWR@ProvidesPackagePass{glossaries}[2018/07/23]
4
5 \setupglossaries{nonumberlist}
6 \setglossarystyle{index}
```

Patched to fix `toc` pointing to the previous page:

```
7 \renewcommand*{\@p@glossarysection}[2]{%
8   \glsclearpage
9   \phantomsection
10  \ifdef\empty\@glossarysecstar
11  {%
12    \csname\@glossarysec\endcsname{#2}%
13  }%
14  {%
```

In the original, the `toc` entry was made before the section, thus linking to the `phantomsection` in the printed version, but for `HTML`, this caused the link to point to the page before the glossaries, which could be a different `HTML` file. Here, the `toc` entry is made after the section is created:

```
15      \csname\@glossarysec\endcsname{#2}%
16      \gls@toc{#1}{\@glossarysec}% Moved after the previous line.
17  }%
18  \@@glossaryseclabel
19 }
```

`lwarf`'s sectioning commands cannot handle robust macros when splitting HTML into named filenames. `glossaries` uses `\translate` in sectioning names, and `\translate` is robust and cannot be expanded. The following pre-expands the translations at this moment, making use of `\translatelet`.

```

20 \newcommand*{\LWR@comp@glossaryname}{\translate{Glossary}}
21
22 \ifdefined\glossaryname{\LWR@comp@glossaryname}{
23     \translatelet{\LWR@translatetemp}{Glossary}
24     \edef\glossaryname{\LWR@translatetemp}
25 }{}
26
27 \newcommand*{\LWR@comp@acronymname}{\translate{Acronym}}
28
29 \ifdefined\acronymname{\LWR@comp@acronymname}{
30     \translatelet{\LWR@translatetemp}{Acronym}
31     \edef\acronymname{\LWR@translatetemp}
32 }{}
33
34 \newcommand*{\LWR@comp@glssymbolsgroupname}{\translate{Symbols (glossaries)}}
35
36 \ifdefined\glssymbolsgroupname{\LWR@comp@glssymbolsgroupname}{
37     \translatelet{\LWR@translatetemp}{Symbols (glossaries)}
38     \edef\glssymbolsgroupname{\LWR@translatetemp}
39 }{}
40
41 \newcommand*{\LWR@comp@glsnumbersgroupname}{\translate{Numbers (glossaries)}}
42
43 \ifdefined\glsnumbersgroupname{\LWR@comp@glsnumbersgroupname}{
44     \translatelet{\LWR@translatetemp}{Numbers (glossaries)}
45     \edef\glsnumbersgroupname{\LWR@translatetemp}
46 }{}

```

### File 178 `lwarf-gmeometric.sty`

#### § 278 Package **gmeometric**

Pkg gmeometric `gmeometric` is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{gmeometric}[2008/11/22]
2 \RequirePackageWithOptions{geometry}

```

### File 179 `lwarf-graphics.sty`

#### § 279 Package **graphics**

(Emulates or patches code by D. P. CARLISLE.)

Pkg graphics `graphics` is emulated.

**for HTML output:** 1 \LWR@ProvidesPackagePass{graphics}[2017/06/25]

## § 279.1 Graphics extensions

\DeclareGraphicsExtensions {\langle list\rangle}

\AtBeginDocument allow SVG files instead of PDF:

```
2 \AtBeginDocument{  
3 \DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}  
4 \DeclareGraphicsRule{.svg}{svg}{.svg}{}  
5 \DeclareGraphicsRule{.SVG}{svg}{.SVG}{}  
6 }
```

Inside a `lateximage`, allow PDF instead of SVG:

```
7 \ifpdf  
8 \appto\lwr@restoreorigformatting{  
9 \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%  
10 }  
11 \else% \ifpdf  
12 \ifXeTeX  
13 \appto\lwr@restoreorigformatting{  
14 \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%  
15 }  
16 \else  
17 \appto\lwr@restoreorigformatting{  
18 \DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%  
19 }  
20 \fi  
21 \fi
```

## § 279.2 Length conversions and graphics options

**⚠ whitespace** A scaled image in L<sup>A</sup>T<sub>E</sub>X by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

Used to store the user's selected dimensions and HTML class.

The class defaults to "inlineimage" unless changed by a `class=xyx` option.

```
22 \newlength{\lwr@igwidth}  
23 \newlength{\lwr@igheight}  
24 \newcommand*{\lwr@igwidthstyle}{}  
25 \newcommand*{\lwr@igheightstyle}{}  
26 \newcommand*{\lwr@igorigin}{}  
27 \newcommand*{\lwr@igangle}{}  
28 \newcommand*{\lwr@igxscale}{1}  
29 \newcommand*{\lwr@igyscale}{1}  
30 \newcommand*{\lwr@igclass}{inlineimage}  
  
31 \newcommand*{\lwr@igalt}{\ImageAltText}
```

Set the actions of each of the key/value combinations for `\includegraphics`. Many are ignored.

If an optional width was given, set an HTML style:

```
32 \define@key{igraph}{width}{%
33 \setlength{\LWR@igwidth}{#1}%
34 \ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}{%
35 {%
```

Default to use the converted fixed length given:

```
36 \renewcommand*{\LWR@igwidthstyle}[width:\LWR@printlength{\LWR@igwidth}]%
```

If ex or em dimensions were given, use those instead:

```
37 \IfEndWith{#1}{ex}%
38 {\renewcommand*{\LWR@igwidthstyle}[width:#1]{} yes ex
39 {} not ex
40 \IfEndWith{#1}{em}%
41 {\renewcommand*{\LWR@igwidthstyle}[width:#1]{} yes em
42 {} not em
43 \IfEndWith{#1}{\%}%
44 {\renewcommand*{\LWR@igwidthstyle}[width:#1]{} yes percent
45 {} not percent
46 \IfEndWith{#1}{px}%
47 {\renewcommand*{\LWR@igwidthstyle}[width:#1]{} yes px
48 {} not px
49 }{} end of length > 0pt
50 }
```

If an optional height was given, set an HTML style:

```
51 \define@key{igraph}{height}{%
52 \setlength{\LWR@igheight}{#1}%
53 \ifthenelse{\lengthtest{\LWR@igheight > 0pt}}{%
54 {%
```

Default to use the converted fixed length given:

```
55 \renewcommand*{\LWR@igheightstyle}[%
56 height:\LWR@printlength{\LWR@igheight} % extra space
57 ]%
```

If ex or em dimensions were given, use those instead:

```
58 \IfEndWith{#1}{ex}%
59 {\renewcommand*{\LWR@igheightstyle}[height:#1]{} yes ex
60 {} not ex
61 \IfEndWith{#1}{em}%
62 {\renewcommand*{\LWR@igheightstyle}[height:#1]{} yes em
63 {} not em
64 \IfEndWith{#1}{\%}%
65 {\renewcommand*{\LWR@igheightstyle}[height:#1]{} yes percent
```

```

66      {}% not percent
67      \IfEndWith{\#1}{px}%
68      {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes px
69      {}% not px
70 }{}% end of length > opt
71 }

```

Handle origin key:

```

72 \define@key{igraph}{origin}[c]{%
73     \renewcommand*{\LWR@igorigin}{\#1}%
74 }

```

Handle angle key:

```
75 \define@key{igraph}{angle}{\renewcommand*{\LWR@igangle}{\#1}}
```

Handle class key:

```
76 \define@key{igraph}{class}{\renewcommand*{\LWR@igclass}{\#1}}
```

Handle alt key:

```
77 \define@key{igraph}{alt}{\renewcommand*{\LWR@igalt}{\#1}}
```

It appears that **graphicx** does not have separate keys for **xscale** and **yscale**. **scale** adjusts both at the same time.

```

78 \define@key{igraph}{scale}{%
79     \ifthenelse{\equal{\#1}{1}}{}{%
80         \PackageWarning{lwarp}{%
81             It is recommended to use\MessageBreak
82             [width=xx\protect\linewidth]\MessageBreak
83             instead of [scale=yy],%
84         }%
85     }%
86     \renewcommand*{\LWR@igxscale}{\#1}%
87     \renewcommand*{\LWR@igyscale}{\#1}%
88 }

```

Numerous ignored keys:

```

89 \define@key{igraph}{bb}(){}
90 \define@key{igraph}{bbllx}(){}
91 \define@key{igraph}{bbly}(){}
92 \define@key{igraph}{bburx}(){}
93 \define@key{igraph}{bbury}(){}
94 \define@key{igraph}{natwidth}(){}
95 \define@key{igraph}{natheight}(){}
96 \define@key{igraph}{hiresbb}[true] {}
97 \define@key{igraph}{viewport} {}
98 \define@key{igraph}{trim} {}
99 \define@key{igraph}{totalheight} {}
100 \define@key{igraph}{keepaspectratio}[true] {}

```

---

```

101 \define@key{igraph}{clip}[true]{}
102 \define@key{igraph}{draft}[true]{}
103 \define@key{igraph}{type}{}
104 \define@key{igraph}{ext}{}
105 \define@key{igraph}{read}{}
106 \define@key{igraph}{command}{}

```

New in v1.1a:

```

107 \define@key{igraph}{quite}{}
108 \define@key{igraph}{page}{}
109 \define@key{igraph}{pagebox}{}
110 \define@key{igraph}{interpolate}[true]{}

```

New in v1.1b:

```

111 \define@key{igraph}{decodearray}{}

```

### § 279.3 Printing HTML styles

\LWR@rotstyle {⟨prefix⟩} {⟨degrees⟩}

Prints the rotate style with the given prefix.

prefix is -ms- or -webkit- or nothing, and is used to generate three versions of the transform:rotate style.

```

112 \newcommand*{\LWR@rotstyle}[2]{%
113   \edef\LWR@tempone{\#2}%
114   \setcounter{LWR@tempcountone}{-1*\real{\LWR@tempone}} % space
115   #1transform:rotate(\arabic{LWR@tempcountone}deg); % space
116 }

```

\LWR@scalestyle {⟨prefix⟩} {⟨xscale⟩} {⟨yscale⟩}

Prints the scale style with the given prefix.

prefix is -ms- or -webkit- or nothing, and is used to generate three versions of the transform:scale style.

```

117 \newcommand*{\LWR@scalestyle}[3]{%
118   #1transform:scale(\#2,\#3);
119 }

```

### § 279.4 \includegraphics

\LWR@opacity For HTML, used only for \includegraphics.

\LWR@opacity may be set by the transparent package.

```

120 \def\LWR@opacity{1}

```

\LWR@imagesizebox Used to determine the actual image size if needed.

```

121 \newsavebox{\LWR@imagesizebox}

```

\LWR@HTML@Gin@setfile {⟨w⟩} {⟨h⟩} {⟨filename⟩} Sets the parsed filename for HTML output.

```

122 \newcommand*{\LWR@HTML@Gin@setfile}[3]{%
123     \xdef\LWR@parsedfilename{#3}%
124 }
```

Key [Gin] class css class for the image.

Define the new class key for the print-mode version of \includegraphics, which is enabled inside a \teximage.

```

125 \AtBeginDocument{%
126 \define@key{Gin}{class}{}
127 \define@key{Gin}{alt}{}
128 }
```

#### \LWR@replaceEPSSVG

Usually, references to EPS files become SVG files, but if the `epstopdf` package is being used, it automatically converts EPS to PDF, and the following must NOT be done.

```

129 \AtBeginDocument{%
130 \@ifpackageloaded{epstopdf}{%
131 {
132     \newcommand*{\LWR@replaceEPSSVG}{%
133 }{%
134     \newcommand*{\LWR@replaceEPSSVG}{%
135         \StrSubstitute{\LWR@tempone}{.eps}{.svg}[\LWR@tempone]%
136         \StrSubstitute{\LWR@tempone}{.EPS}{.SVG}[\LWR@tempone]%
137     }%
138 }%
139 }
```

\LWR@ig@wpimagesizes \* [<2: options>] [<3: options>] [<4: filename}]

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```

140 \newcommand*{\LWR@ig@wpimagesizes}[4]{%
141     \ifbool{FormatWP}{%
142         \begingroup%
143         \LWR@restoreorigformatting%
144         \ifpdf%
145             \appto{\LWR@restoreorigformatting}{%
146                 \DeclareGraphicsExtensions{%
147                     .pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
148                 }%
149             }%
150         \else%
151             \ifXeTeX%
152                 \appto{\LWR@restoreorigformatting}{%
153                     \DeclareGraphicsExtensions{%
154                         .pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
155                     }%
156                 }%
157             \else%
158                 \appto{\LWR@restoreorigformatting}{%
159                     \DeclareGraphicsExtensions{%
```

```
160           .eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
161       }%
162   }%
163   \fi%
164   \ifpdf
165   \define@key{Gin}{angle}{%
166   \IfBooleanTF{#1}%
167   {%
168       \IfValueTF{#3}%
169       {%
170           \global\sbox{\LWR@imagesizebox}{%
171               \LWR@originincludegraphics*[#2][#3]{#4}%
172           }%
173       }%
174   {%
175       \IfValueTF{#2}%
176       {%
177           \global\sbox{\LWR@imagesizebox}{%
178               \LWR@originincludegraphics*[#2]{#4}%
179           }%
180       }{%
181           \global\sbox{\LWR@imagesizebox}{%
182               \LWR@originincludegraphics*[#4]%
183           }%
184       }%
185   }%
186 }% starred
187 {%
188     \IfValueTF{#3}%
189     {%
190         \global\sbox{\LWR@imagesizebox}{%
191             \LWR@originincludegraphics[#2][#3]{#4}%
192         }%
193     }%
194     {%
195         \IfValueTF{#2}%
196         {%
197             \global\sbox{\LWR@imagesizebox}{%
198                 \LWR@originincludegraphics[#2]{#4}%
199             }%
200         }{%
201             \global\sbox{\LWR@imagesizebox}{%
202                 \LWR@originincludegraphics[#4]%
203             }%
204         }%
205     }%
206 }% not starred
207 \endgroup%
208 \settowidth{\LWR@igwidth}{\usebox{\LWR@imagesizebox}}%
209 \global\renewcommand*{\LWR@igwidthstyle}{%
210     width:\LWR@printlength{\LWR@igwidth}%
211 }%
212 \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
213 \global\renewcommand*{\LWR@igheightstyle}{%
214     height:\LWR@printlength{\LWR@igheight}%

```

```

215      }%
216  }% FormatWP
217 }
```

\LWR@ig@htmltag For the HTML reference, add the graphicspath, filename, extension, alt tag, style, and class.

```

218 \newcommand*\LWR@ig@htmltag{%
219     img\LWR@indentHTML%
220     src="%
221     \detokenize\expandafter{\LWR@parsedfilename}%
222     "\LWR@indentHTML%
```

Only include a style tag if a width, height, angle, or scale was given:

```

223 \ifthenelse{
224     \NOT\equal{\LWR@igwidthstyle}{} \OR
225     \NOT\equal{\LWR@igheightstyle}{} \OR
226     \NOT\equal{\LWR@igorigin}{} \OR
227     \NOT\equal{\LWR@igangle}{} \OR
228     \NOT\equal{\LWR@igxscale}{1} \OR
229     \NOT\equal{\LWR@igyscale}{1}
230 }%
231 {%
232     style="\LWR@indentHTML
233     \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{}%
234         {\LWR@igwidthstyle;\LWR@indentHTML}{}%
235     \ifthenelse{\NOT\equal{\LWR@igheightstyle}{}%
236         {\LWR@igheightstyle;\LWR@indentHTML}{}%
237     \ifthenelse{\NOT\equal{\LWR@igorigin}{}%
238         {%
239             transform-origin: \LWR@originnames{\LWR@igorigin};%
240             \LWR@indentHTML%
241         }%
242     \ifthenelse{\NOT\equal{\LWR@igangle}{}%
243     {%
244         \LWR@rotstyle{-ms-}{\LWR@igangle}\LWR@indentHTML
245         \LWR@rotstyle{-webkit-}{\LWR@igangle}\LWR@indentHTML
246         \LWR@rotstyle{}{\LWR@igangle }\LWR@indentHTML
247     }%
248     \ifthenelse{%
249         \NOT\equal{\LWR@igxscale}{1}\OR%
250         \NOT\equal{\LWR@igyscale}{1}%
251     }%
252     {%
253         \LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale}%
254         \LWR@indentHTML
255         \LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale}%
256         \LWR@indentHTML
257         \LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}%
258         \LWR@indentHTML
259     }%
260     %
261     \ifthenelse{\NOT\equal{\LWR@opacity}{1}}%
```

```

262           {opacity:\LWR@opacity;\LWR@indentHTML}{}%
263           %
264           "\LWR@indentHTML%
265       }{}%

```

Set the class and alt tag:

```

266   class="\LWR@igclass"\LWR@indentHTML%
267   alt="\AltTextOpen\LWR@igalt\AltTextClose" \LWR@orignewline%
268 }% end of image tags

```

\LWR@includegraphicsb \* [<2: options>] [<3: options>] [<4: filename]  
 graphics syntax is \includegraphics \* [<llx, lly>] [<urx, ury>] {[file]}  
 graphicx syntax is \includegraphics [<key values>] {[file]}

If #3 is empty, only one optional argument was given, thus graphicx syntax.

If using \epsfig or \psfig from the epsfig package, #4 will be \LWR@epsfig@filename, which will have been set by the file or figure keys. Therefore, #4 must not be used until after the keys have been processed.

```

269 \NewDocumentCommand{\LWR@includegraphicsb}{s o o m}
270 {%

```

Start the image tag on a new line, allow PDF output word wrap:

```
271   \LWR@origtilde \LWR@orignewline%
```

Temporarily compute \ linewidth, \textwidth, \textheight arguments with a 6x9 inch size until the next \endgroup.

```
272   \begin{LWR@setvirtualpage}%
```

For correct em sizing during the width and height conversions:

```
273   \large%
```

Reset some defaults, possibly will be changed below if options were given:

```

274   \setlength{\LWR@igwidth}{0pt}%
275   \setlength{\LWR@igheight}{0pt}%
276   \renewcommand*\{\LWR@igwidthstyle}{}%
277   \renewcommand*\{\LWR@igheightstyle}{}%
278   \renewcommand*\{\LWR@igorigin}{}%
279   \renewcommand*\{\LWR@igangle}{}%
280   \renewcommand*\{\LWR@igxscale}{1}%
281   \renewcommand*\{\LWR@igyscale}{1}%
282   \renewcommand*\{\LWR@igclass}{inlineimage}%

283   \ifdefvoid{\LWR@ThisAltText}{%
284     \edef\LWR@igalt{\ImageAltText}%
285   }{%
286     \edef\LWR@igalt{\LWR@ThisAltText}%
287   }%

```

If #3 is empty, only one optional argument was given, thus graphicx syntax:

```

288   \IfValueF{#3}{%
289     \IfValueTF{#2}{%
290       {\setkeys{igraph}{#2}}%

```

```

291           {\setkeys{igraph}{}}
292       }%

```

Fully expand and detokenize the filename, changing the file extension to .svg if necessary.

```

293   \begingroup%
294   \LetLtxMacro\Gin@setfile\LWR@HTML@Gin@setfile%
295   \edef\LWR@tempone{\#4}%
296   \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
297   \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
298   \LWR@replaceEPSSVG%
299   \xdef\LWR@parsedfilename{\LWR@tempone}%
300   \Ginclusion@graphics{\detokenize\expandafter{\LWR@tempone}}%
301   \endgroup%
302   \filename@parse{\LWR@parsedfilename}%
303   \LWR@traceinfo{\LWR@parsedfilename is \LWR@parsedfilename}%
304 % \LWR@sanitize{\LWR@parsedfilename}%

```

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```
305   \LWR@ig@wpimagesizes{\#1}{\#2}{\#3}{\#4}%
```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class:

```

306   \LWR@traceinfo{\LWR@includegraphicsb: about to create href}%
307   \href{\LWR@parsedfilename}%
308   {% start of href
309     \LWR@traceinfo{\LWR@includegraphicsb: about to \LWR@htmltag}%
310     \LWR@htmltag{\LWR@ig@htmltag}%
311   }% end of href

```

Return to original page size and font size:

```
312   \end{\LWR@setvirtualpage}%

```

Clear the single-use alt text:

```

313   \gdef\LWR@ThisAltText{}%
314   \LWR@traceinfo{\LWR@includegraphicsb done}%
315 }

```

\includegraphics [⟨key=val⟩] {⟨filename⟩}

Handles width and height, converted to fixed width and heights.

The user should always use no file suffix in the document source.

```

316 \AtBeginDocument{%
317 %
318 \LWR@traceinfo{Patching \includegraphics.}%
319 %
320 \LetLtxMacro\LWR@origin\includegraphics\includegraphics
321 %
322 }%

```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```
323 \LWR@traceinfo{includegraphics}%
324 \LWR@ensuredoingapar%
325 \LWR@includegraphicsb%
326 }% includegraphics
327 }% AtBeginDocument
```

## § 279.5 Boxes

\LWR@rotboxorigin Holds the origin key letters.

```
328 \newcommand*{\LWR@rotboxorigin}{}%
```

\LWR@originname {⟨letter⟩}

Given one L<sup>A</sup>T<sub>E</sub>X origin key value, translate into an HTML origin word:

```
329 \newcommand*{\LWR@originname}[1]{%
330   \ifthenelse{\equal{#1}{t}}{top}{}
331   \ifthenelse{\equal{#1}{b}}{bottom}{}
332   \ifthenelse{\equal{#1}{c}}{center}{}
333   \ifthenelse{\equal{#1}{l}}{left}{}
334   \ifthenelse{\equal{#1}{r}}{right}{}
335 }
```

\LWR@originnames {⟨letters⟩}

Given one- or two-letter L<sup>A</sup>T<sub>E</sub>X origin key values, translate into HTML origin words:

```
336 \newcommand*{\LWR@originnames}[1]{%
337 \StrChar{#1}{1}[\LWR@strresult]%
338 \LWR@originname{\LWR@strresult}%
339 \StrChar{#1}{2}[\LWR@strresult]%
340 \LWR@originname{\LWR@strresult}%
341 }
```

Handle the origin key for \rotatebox:

```
342 \define@key{krotbox}{origin}{%
343 \renewcommand*{\LWR@rotboxorigin}{#1}%
344 }
```

These keys are ignored:

```
345 \define@key{krotbox}{x}{}
346 \define@key{krotbox}{y}{}
347 \define@key{krotbox}{units}{}
```

\rotatebox [⟨keyval list⟩] {⟨angle⟩} {⟨text⟩}

```
348 \AtBeginDocument{
```

The HTML version:

---

349 \NewDocumentCommand{\LWR@HTML@rotatebox}{O{} m +m}{%

Reset the origin to “none-given”:

350 \renewcommand\*\LWR@rotboxorigin{}

Process the optional keys, which may set \LWR@rotateboxorigin:

351 \setkeys[krotbox]{#1}%

Select `inline-block` so that `HTML` will transform this span:

```
352 \LWR@htmltagc{%
353     span\LWR@indentHTML
354     style="\LWR@indentHTML
355     display: inline-block; \LWR@indentHTML
```

If an origin was given, translate and print the origin information:

```
356     \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{}}{%
357         {transform-origin: \LWR@originnames{\LWR@rotboxorigin}; \LWR@indentHTML}%
358     }%
```

Print the rotation information:

```
359     \LWR@rotstyle{-ms-}{#2}\LWR@indentHTML
360     \LWR@rotstyle{-webkit-}{#2}\LWR@indentHTML
361     \LWR@rotstyle{}{#2}"\LWR@orignewline%
362 }\LWR@orignewline%
```

Print the text to be rotated:

```
363 \begin{LWR@nestspan}%
364 #3%
```

Close the span:

```
365 \LWR@htmltagc{/span}%
366 \end{LWR@nestspan}%
367 }
```

The high-level interface:

```
368 \LWR@formatted{rotatebox}
369
370 }% AtBeginDocument

\scalebox {<h-scale>} [<v-scale>] {<text>}

371 \AtBeginDocument{
```

The `HTML` version:

---

372 \NewDocumentCommand{\LWR@HTML@scalebox}{m o m}{%

Select inline-block so that HTML will transform this span:

```
373 \LWR@htmltagc{%
374     span\LWR@indentHTML
375     style="\LWR@indentHTML
376     display: inline-block; \LWR@indentHTML
```

Print the scaling information:

```
377     \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
378     \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
379     \LWR@scalestyle{}{#1}{\IfNoValueTF{#2}{#1}{#2}}
380     "\LWR@orignewline
381 }\LWR@orignewline%
```

Print the text to be scaled:

```
382 \begin{\LWR@nestspan}%
383 #3%
```

Close the span:

```
384 \LWR@htmltagc{/span}%
385 \end{\LWR@nestspan}%
386 }
```

The high-level interface:

```
387 \LWR@formatted{scalebox}%
388
389 }% AtBeginDocument
```

\reflectbox {⟨text⟩}

```
390 \AtBeginDocument{
391
392 \newcommand{\LWR@HTML@reflectbox}[1]{%
393 \scalebox{-1}[1]{#1}%
394 }% \reflectbox
395
396 \LWR@formatted{reflectbox}
397
398 }% AtBeginDocument
```

\resizebox {⟨h-length⟩} {⟨v-length⟩} {⟨text⟩}

Simply prints its text argument.

```
399 \AtBeginDocument{
400
401 \NewDocumentCommand{\LWR@HTML@resizebox}{s m m}{%
```

```
402 #4%
403 }
404
405 \LWR@formatted{resizebox}
406
407 }% AtBeginDocument
```

---

### File 180 **l warp-graphicx.sty**

#### § 280 Package **graphicx**

Pkg **graphicx** **graphicx** is emulated.

**graphicx** loads **graphics**, which also loads **l warp-graphics**, which remembers the original graphics definitions for use inside a **lateximage**, and then patches them **\AtBeginDocument** for **HTML** output.

**l warp-graphics** handles the syntax of either **graphics** or **graphicx**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{graphicx}[2017/06/01]

---

### File 181 **l warp-grffile.sty**

#### § 281 Package **grffile**

Pkg **grffile** **grffile** is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each **PDF** image for print mode should be accompanied by an **SVG**, **PNG**, or **JPG** version for **HTML**.

**l warp-grffile** now exists as a placeholder since **grffile** used to be emulated by **l warp**, and thus older versions of **l warp-grffile** may exist and should be overwritten by this newer version.

**for HTML output:** 1 \LWR@ProvidesPackagePass{grffile}[2017/06/30]

---

### File 182 **l warp-grid.sty**

#### § 282 Package **grid**

Pkg **grid** **grid** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{grid}[2009/06/16]

2 \newenvironment\*{gridenv}{}{}

---

**File 183 l warp-grid-system.sty****§ 283 Package grid-system**

*(Emulates or patches code by MARCUS BITZL.)*

Pkg grid-system grid-system is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{grid-system}[2014/02/16]

(\ifdef is in case the older syntax is removed.)

```
2 \AtBeginEnvironment{Row}{\setlength{\ linewidth}{6in}}
3
4 \ifdef{\endrow}{}
5   \AtBeginEnvironment{row}{\setlength{\ linewidth}{6in}}
6 }()
7
8 \renewcommand{\gridsystem@finishcell}{\hspace{\gridsystem@cellsep}}
```

---

**File 184 l warp-gridset.sty****§ 284 Package gridset**

Pkg gridset gridset is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{gridset}

```
2 \newcommand*\gridbase(){}
3 \newcommand*\gridinterval(){}
4 \newcommand*\savepos[1]({})
5 \newcounter{gridcnt}
6 \newcommand*\vskipnextgrid(){}
7 \newcommand*\thegridinfo[1]({})
8 \newcommand*\theinfo[1]({})
9 \newcommand*\theypos[1]({}
```

---

**File 185 l warp-hang.sty****§ 285 Package hang**

*(Emulates or patches code by ANDREAS NOLDA.)*

Pkg hang hang is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{hang}[2017/02/18]

```
2 \newlength{\hangingindent}
3 \setlength{\hangingindent}{1em}
4 \newlength{\hangingleftmargin}
5 \setlength{\hangingleftmargin}{0em}
6
7 \newcommand*\LWR@findhangingleftmargin{%
8   \setlength{\LWR@templengthone}{\hangingleftmargin}%
9   \addtolength{\LWR@templengthone}{\hangingindent}%
10 }
11
12 \newenvironment{hangingpar}
13 {
14   \LWR@findhangingleftmargin%
15   \BlockClass[%  

16     \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
17     \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
18   ]%
19   {hangingpar}%
20 }
21 {\endBlockClass}
22
23 \newenvironment{hanginglist}
24 {%
25   \renewcommand*\LWR@printcloselist{\LWR@printcloseitemize}%
26   \renewcommand*\LWR@printopenlist{%
27     \LWR@findhangingleftmargin%
28     ul style=%
29       \LWR@print@mbox{list-style-type:none;} % extra space
30       \LWR@print@mbox{%
31         margin-left:\LWR@printlength{\LWR@templengthone}%
32       } ; % extra space
33       \LWR@print@mbox{%
34         text-indent:-\LWR@printlength{\hangingindent}%
35       }%
36     "%
37   }%
38   \let\item\LWR@itemizeitem%
39   \list{}{%
40 }
41 {\endlist}
42
43 \newenvironment{compacthang}
44 {\hanginglist}
45 {\endhanginglist}
46
47 \newlength{\labeledleftmargin}
48 \setlength{\labeledleftmargin}{0em}
49
50 \newenvironment{labeledpar}[2]
51 {%
52   \BlockClass[%  

53     \LWR@findhangingleftmargin%
54     \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
55     \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
56   ]{labeledpar}#2%
```

```
57 }
58 {\endBlockClass}
59
60 \newenvironment{labeledlist}[1]
61 {\begin{hanginglist}}
62 {\end{hanginglist}}
63
64 \newenvironment{compactlabel}[1]
65 {\begin{hanginglist}}
66 {\end{hanginglist}}
```

---

**File 186 l warp-hanging.sty****§ 286 Package hanging**

Pkg hanging hanging is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{hanging}[2009/09/02]

```
2 \@ifclassloaded{memoir}{
3 \let\hangpara\relax
4 \let\hangparas\relax
5 \let\endhangparas\relax
6 \let\hangpunct\relax
7 \let\endhangpunct\relax
8 }{}
```

\hangpara {\<indent>} {\<afternum>}

Use **hangparas** instead.

```
9 \newcommand*{\hangpara}[2]{}
```

Env hangparas {\<indent>} {\<afternum>}

```
10 \newenvironment*{\hangparas}[2]
11 {%
12   \BlockClass[%
13     \LWR@print@embox{margin-left:\LWR@printlength{\#1}} ; %
14     \LWR@print@embox{text-indent:-\LWR@printlength{\#1}}%
15   ]%
16   {hangingpar}%
17 }
18 {\endBlockClass}
```

Env hangpunct

```
19 \newenvironment*{\hangpunct}
20 {\BlockClass{\hangpunct}}
21 {\endBlockClass}
```

---

```
22 \newcommand{\nhpt}{.}
23 \newcommand{\nhlq}{`}
24 \newcommand{\nhrq}{'}
```

---

File 187 **l warp-hhline.sty**

§ 287 Package **hhline**

*(Emulates or patches code by DAVID CARLISLE.)*

Pkg **hhline** **hhline** is patched for use by **l warp**.

Only a rudimentary emulation is provided so far. If the argument contains any = characters, the result is a double \hline. If none, the result is a single \hline.

**for HTML output:** 1 \LWR@ProvidesPackagePass{hhline}[2014/10/28]

```
2 \newrobustcmd*\LWR@HTML@hhline}[1]{%
3   \edef\LWR@tempone{\detokenize\expandafter{\#1}}%
4   \IfSubStr[1]{\LWR@tempone}{=}{\hline\hline}{\hline}%
5 }
6 % ^^A or:
7 % ^^A \newrobustcmd*\LWR@HTML@hhline}[1]{\LWR@getmynexttoken}%
8
9 \AtBeginDocument{\LWR@expandableformatted{hhline}}
```

For **MATHJAX**. A simple \hline is used.

```
10 \begin{warpMathJax}
11 \CustomizeMathJax{\newcommand{\hhline}[1]{\hline}}
12 \end{warpMathJax}
```

---

File 188 **l warp-hypbmsec.sty**

§ 288 Package **hypbmsec**

Pkg **hypbmsec** **hypbmsec** is emulated by the **l warp** core.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{hypbmsec}[2016/05/16]

---

File 189 **l warp-hypcap.sty**

§ 289 Package **hypcap**

Pkg **hypcap** **hypcap** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{hypcap}[2016/05/16]

```
2 \newcommand*{\capstart}{}  
3 \newcommand*{\hypcapspace}{}  
4 \newcommand*{\hypcapref}[1]{}  
5 \newcommand*{\capstartfalse}{}  
6 \newcommand*{\capstartrue}{}  


---


```

File 190 **l warp-hypdestopt.sty**

§ 290 Package **hypdestopt**

Pkg hypdestopt hypdestopt is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{hypdestopt}[2016/05/21]

---

File 191 **l warp-hypernat.sty**

§ 291 Package **hypernat**

Pkg hypernat hypernat is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{hypernat}[2001/07/09]

---

File 192 **l warp-hyperref.sty**

§ 292 Package **hyperref**

(Emulates or patches code by SEBASTIAN RAHTZ, HEIKO OBERDIEK.)

Pkg hyperref hyperref is emulated.

for HTML output:  
1 % \LWR@ProvidesPackageDrop{hyperref}% not allowed  
2 % \ProvidesPackage{l warp-#1-#2}% not allowed  
3 \PackageInfo{l warp}{%  
4 Using the l warp HTML version of package ‘hyperref’ , \MessageBreak  
5 and discarding options.\MessageBreak  
6 (Not using \protect\ProvidesPackage, so that other packages\MessageBreak  
7 do not attempt to patch l warp’s version of ‘hyperref’.)\MessageBreak}  
8  
9 \DeclareOption\*{}  
  
10 % \ProcessOptions\relax  
11 \let\ds@\empty% from the original \ProcessOptions  
12 \edef\@curroptions{}% l warp modification to \ProcessOptions  
13 \@process@ptions\relax% from the original \ProcessOptions  
  
14 \newcommand\*{\hypersetup}[1]{}  
15 \newcommand\*{\hyperbaseurl}[1]{}

---

\hyperimage {⟨URL⟩} {⟨alt text⟩}

Insert an image with alt text:

```

16 \NewDocumentCommand{\LWR@hyperimageb}{m +m}{%
17   \LWR@ensuredoingapar%
18   \def\LWR@templink{\#1}%
19   @onelevel@sanitize\LWR@templink%
20   \LWR@htmlltag{img src="\LWR@templink" alt="#2" class="hyperimage"}%
21   \LWR@ensuredoingapar%
22   \endgroup%
23 }
24
25 \newrobustcmd*\hyperimage{%
26   \begingroup%
27   \LWR@linkcatcodes%
28   \LWR@hyperimageb%
29 }
30

```

\hyperdef {⟨1: category⟩} {⟨2: name⟩} {⟨3: text⟩}

Creates an **HTML** anchor to category.name with the given text.

```

31 \NewDocumentCommand{\LWR@hyperdefb}{m m +m}{%
32   \LWR@ensuredoingapar%
33   \LWR@slabel{\#1.\#2}%
34   #3%
35   \endgroup%
36 }
37
38 \newcommand*\hyperdef{%
39   \begingroup%
40   \LWR@linkcatcodes%
41   \LWR@hyperdefb%
42 }
43

```

\LWR@hyperrefb {⟨1: URL⟩} {⟨2: category⟩} {⟨3: name⟩} {⟨4: text⟩}

Creates an **HTML** link to URL#category.name with the given text.

```

44 \newcommand{\LWR@hyperreffinish}[1]{%
45   \begingroup%
46   \RenewDocumentCommand{\ref}{}{\LWR@ref@ignorestar}%
47   #1%
48   \endgroup%
49   \LWR@htmlltag{/a}%
50 }
51
52 \newcommand*\LWR@hyperrefbb[3]{%
53   \LWR@htmlltag{%
54     a href="%"
55       \detokenize\expandafter{\#1}\LWR@hashmark%
56       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
57     "%"
58   }
59 }
60
61 \newcommand*\LWR@hyperrefc[3]{%
62   \LWR@htmlltag{%
63     a href="%"
64       \detokenize\expandafter{\#1}\LWR@hashmark%
65       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
66     "%"
67   }
68 }
69
70 \newcommand*\LWR@hyperrefd[3]{%
71   \LWR@htmlltag{%
72     a href="%"
73       \detokenize\expandafter{\#1}\LWR@hashmark%
74       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
75     "%"
76   }
77 }
78
79 \newcommand*\LWR@hyperrefe[3]{%
80   \LWR@htmlltag{%
81     a href="%"
82       \detokenize\expandafter{\#1}\LWR@hashmark%
83       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
84     "%"
85   }
86 }
87
88 \newcommand*\LWR@hyperreff[3]{%
89   \LWR@htmlltag{%
90     a href="%"
91       \detokenize\expandafter{\#1}\LWR@hashmark%
92       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
93     "%"
94   }
95 }
96
97 \newcommand*\LWR@hyperrefg[3]{%
98   \LWR@htmlltag{%
99     a href="%"
100       \detokenize\expandafter{\#1}\LWR@hashmark%
101       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
102     "%"
103   }
104 }
105
106 \newcommand*\LWR@hyperrefh[3]{%
107   \LWR@htmlltag{%
108     a href="%"
109       \detokenize\expandafter{\#1}\LWR@hashmark%
110       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
111     "%"
112   }
113 }
114
115 \newcommand*\LWR@hyperrefi[3]{%
116   \LWR@htmlltag{%
117     a href="%"
118       \detokenize\expandafter{\#1}\LWR@hashmark%
119       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
120     "%"
121   }
122 }
123
124 \newcommand*\LWR@hyperrefj[3]{%
125   \LWR@htmlltag{%
126     a href="%"
127       \detokenize\expandafter{\#1}\LWR@hashmark%
128       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
129     "%"
130   }
131 }
132
133 \newcommand*\LWR@hyperrefk[3]{%
134   \LWR@htmlltag{%
135     a href="%"
136       \detokenize\expandafter{\#1}\LWR@hashmark%
137       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
138     "%"
139   }
140 }
141
142 \newcommand*\LWR@hyperrefl[3]{%
143   \LWR@htmlltag{%
144     a href="%"
145       \detokenize\expandafter{\#1}\LWR@hashmark%
146       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
147     "%"
148   }
149 }
150
151 \newcommand*\LWR@hyperrefm[3]{%
152   \LWR@htmlltag{%
153     a href="%"
154       \detokenize\expandafter{\#1}\LWR@hashmark%
155       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
156     "%"
157   }
158 }
159
160 \newcommand*\LWR@hyperrefn[3]{%
161   \LWR@htmlltag{%
162     a href="%"
163       \detokenize\expandafter{\#1}\LWR@hashmark%
164       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
165     "%"
166   }
167 }
168
169 \newcommand*\LWR@hyperrefo[3]{%
170   \LWR@htmlltag{%
171     a href="%"
172       \detokenize\expandafter{\#1}\LWR@hashmark%
173       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
174     "%"
175   }
176 }
177
178 \newcommand*\LWR@hyperrefp[3]{%
179   \LWR@htmlltag{%
180     a href="%"
181       \detokenize\expandafter{\#1}\LWR@hashmark%
182       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
183     "%"
184   }
185 }
186
187 \newcommand*\LWR@hyperrefq[3]{%
188   \LWR@htmlltag{%
189     a href="%"
190       \detokenize\expandafter{\#1}\LWR@hashmark%
191       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
192     "%"
193   }
194 }
195
196 \newcommand*\LWR@hyperrefr[3]{%
197   \LWR@htmlltag{%
198     a href="%"
199       \detokenize\expandafter{\#1}\LWR@hashmark%
200       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
201     "%"
202   }
203 }
204
205 \newcommand*\LWR@hyperrefs[3]{%
206   \LWR@htmlltag{%
207     a href="%"
208       \detokenize\expandafter{\#1}\LWR@hashmark%
209       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
210     "%"
211   }
212 }
213
214 \newcommand*\LWR@hyperreft[3]{%
215   \LWR@htmlltag{%
216     a href="%"
217       \detokenize\expandafter{\#1}\LWR@hashmark%
218       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
219     "%"
220   }
221 }
222
223 \newcommand*\LWR@hyperrefu[3]{%
224   \LWR@htmlltag{%
225     a href="%"
226       \detokenize\expandafter{\#1}\LWR@hashmark%
227       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
228     "%"
229   }
230 }
231
232 \newcommand*\LWR@hyperrefv[3]{%
233   \LWR@htmlltag{%
234     a href="%"
235       \detokenize\expandafter{\#1}\LWR@hashmark%
236       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
237     "%"
238   }
239 }
240
241 \newcommand*\LWR@hyperrefw[3]{%
242   \LWR@htmlltag{%
243     a href="%"
244       \detokenize\expandafter{\#1}\LWR@hashmark%
245       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
246     "%"
247   }
248 }
249
250 \newcommand*\LWR@hyperrefx[3]{%
251   \LWR@htmlltag{%
252     a href="%"
253       \detokenize\expandafter{\#1}\LWR@hashmark%
254       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
255     "%"
256   }
257 }
258
259 \newcommand*\LWR@hyperrefy[3]{%
260   \LWR@htmlltag{%
261     a href="%"
262       \detokenize\expandafter{\#1}\LWR@hashmark%
263       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
264     "%"
265   }
266 }
267
268 \newcommand*\LWR@hyperrefz[3]{%
269   \LWR@htmlltag{%
270     a href="%"
271       \detokenize\expandafter{\#1}\LWR@hashmark%
272       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
273     "%"
274   }
275 }
276
277 \newcommand*\LWR@hyperrefaa[3]{%
278   \LWR@htmlltag{%
279     a href="%"
280       \detokenize\expandafter{\#1}\LWR@hashmark%
281       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
282     "%"
283   }
284 }
285
286 \newcommand*\LWR@hyperrefab[3]{%
287   \LWR@htmlltag{%
288     a href="%"
289       \detokenize\expandafter{\#1}\LWR@hashmark%
290       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
291     "%"
292   }
293 }
294
295 \newcommand*\LWR@hyperrefac[3]{%
296   \LWR@htmlltag{%
297     a href="%"
298       \detokenize\expandafter{\#1}\LWR@hashmark%
299       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
300     "%"
301   }
302 }
303
304 \newcommand*\LWR@hyperrefad[3]{%
305   \LWR@htmlltag{%
306     a href="%"
307       \detokenize\expandafter{\#1}\LWR@hashmark%
308       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
309     "%"
310   }
311 }
312
313 \newcommand*\LWR@hyperrefae[3]{%
314   \LWR@htmlltag{%
315     a href="%"
316       \detokenize\expandafter{\#1}\LWR@hashmark%
317       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
318     "%"
319   }
320 }
321
322 \newcommand*\LWR@hyperrefaf[3]{%
323   \LWR@htmlltag{%
324     a href="%"
325       \detokenize\expandafter{\#1}\LWR@hashmark%
326       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
327     "%"
328   }
329 }
330
331 \newcommand*\LWR@hyperrefag[3]{%
332   \LWR@htmlltag{%
333     a href="%"
334       \detokenize\expandafter{\#1}\LWR@hashmark%
335       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
336     "%"
337   }
338 }
339
340 \newcommand*\LWR@hyperrefah[3]{%
341   \LWR@htmlltag{%
342     a href="%"
343       \detokenize\expandafter{\#1}\LWR@hashmark%
344       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
345     "%"
346   }
347 }
348
349 \newcommand*\LWR@hyperrefai[3]{%
350   \LWR@htmlltag{%
351     a href="%"
352       \detokenize\expandafter{\#1}\LWR@hashmark%
353       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
354     "%"
355   }
356 }
357
358 \newcommand*\LWR@hyperrefaj[3]{%
359   \LWR@htmlltag{%
360     a href="%"
361       \detokenize\expandafter{\#1}\LWR@hashmark%
362       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
363     "%"
364   }
365 }
366
367 \newcommand*\LWR@hyperrefak[3]{%
368   \LWR@htmlltag{%
369     a href="%"
370       \detokenize\expandafter{\#1}\LWR@hashmark%
371       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
372     "%"
373   }
374 }
375
376 \newcommand*\LWR@hyperrefal[3]{%
377   \LWR@htmlltag{%
378     a href="%"
379       \detokenize\expandafter{\#1}\LWR@hashmark%
380       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
381     "%"
382   }
383 }
384
385 \newcommand*\LWR@hyperrefam[3]{%
386   \LWR@htmlltag{%
387     a href="%"
388       \detokenize\expandafter{\#1}\LWR@hashmark%
389       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
390     "%"
391   }
392 }
393
394 \newcommand*\LWR@hyperrefan[3]{%
395   \LWR@htmlltag{%
396     a href="%"
397       \detokenize\expandafter{\#1}\LWR@hashmark%
398       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
399     "%"
400   }
401 }
402
403 \newcommand*\LWR@hyperrefao[3]{%
404   \LWR@htmlltag{%
405     a href="%"
406       \detokenize\expandafter{\#1}\LWR@hashmark%
407       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
408     "%"
409   }
410 }
411
412 \newcommand*\LWR@hyperrefap[3]{%
413   \LWR@htmlltag{%
414     a href="%"
415       \detokenize\expandafter{\#1}\LWR@hashmark%
416       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
417     "%"
418   }
419 }
420
421 \newcommand*\LWR@hyperrefaq[3]{%
422   \LWR@htmlltag{%
423     a href="%"
424       \detokenize\expandafter{\#1}\LWR@hashmark%
425       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
426     "%"
427   }
428 }
429
430 \newcommand*\LWR@hyperrefar[3]{%
431   \LWR@htmlltag{%
432     a href="%"
433       \detokenize\expandafter{\#1}\LWR@hashmark%
434       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
435     "%"
436   }
437 }
438
439 \newcommand*\LWR@hyperrefas[3]{%
440   \LWR@htmlltag{%
441     a href="%"
442       \detokenize\expandafter{\#1}\LWR@hashmark%
443       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
444     "%"
445   }
446 }
447
448 \newcommand*\LWR@hyperrefat[3]{%
449   \LWR@htmlltag{%
450     a href="%"
451       \detokenize\expandafter{\#1}\LWR@hashmark%
452       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
453     "%"
454   }
455 }
456
457 \newcommand*\LWR@hyperrefau[3]{%
458   \LWR@htmlltag{%
459     a href="%"
460       \detokenize\expandafter{\#1}\LWR@hashmark%
461       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
462     "%"
463   }
464 }
465
466 \newcommand*\LWR@hyperrefav[3]{%
467   \LWR@htmlltag{%
468     a href="%"
469       \detokenize\expandafter{\#1}\LWR@hashmark%
470       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
471     "%"
472   }
473 }
474
475 \newcommand*\LWR@hyperrefaw[3]{%
476   \LWR@htmlltag{%
477     a href="%"
478       \detokenize\expandafter{\#1}\LWR@hashmark%
479       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
480     "%"
481   }
482 }
483
484 \newcommand*\LWR@hyperrefax[3]{%
485   \LWR@htmlltag{%
486     a href="%"
487       \detokenize\expandafter{\#1}\LWR@hashmark%
488       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
489     "%"
490   }
491 }
492
493 \newcommand*\LWR@hyperrefay[3]{%
494   \LWR@htmlltag{%
495     a href="%"
496       \detokenize\expandafter{\#1}\LWR@hashmark%
497       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
498     "%"
499   }
500 }
501
502 \newcommand*\LWR@hyperrefaz[3]{%
503   \LWR@htmlltag{%
504     a href="%"
505       \detokenize\expandafter{\#1}\LWR@hashmark%
506       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
507     "%"
508   }
509 }
510
511 \newcommand*\LWR@hyperrefaa[3]{%
512   \LWR@htmlltag{%
513     a href="%"
514       \detokenize\expandafter{\#1}\LWR@hashmark%
515       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
516     "%"
517   }
518 }
519
520 \newcommand*\LWR@hyperrefab[3]{%
521   \LWR@htmlltag{%
522     a href="%"
523       \detokenize\expandafter{\#1}\LWR@hashmark%
524       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
525     "%"
526   }
527 }
528
529 \newcommand*\LWR@hyperrefac[3]{%
530   \LWR@htmlltag{%
531     a href="%"
532       \detokenize\expandafter{\#1}\LWR@hashmark%
533       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
534     "%"
535   }
536 }
537
538 \newcommand*\LWR@hyperrefad[3]{%
539   \LWR@htmlltag{%
540     a href="%"
541       \detokenize\expandafter{\#1}\LWR@hashmark%
542       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
543     "%"
544   }
545 }
546
547 \newcommand*\LWR@hyperrefae[3]{%
548   \LWR@htmlltag{%
549     a href="%"
550       \detokenize\expandafter{\#1}\LWR@hashmark%
551       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
552     "%"
553   }
554 }
555
556 \newcommand*\LWR@hyperrefaf[3]{%
557   \LWR@htmlltag{%
558     a href="%"
559       \detokenize\expandafter{\#1}\LWR@hashmark%
560       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
561     "%"
562   }
563 }
564
565 \newcommand*\LWR@hyperrefag[3]{%
566   \LWR@htmlltag{%
567     a href="%"
568       \detokenize\expandafter{\#1}\LWR@hashmark%
569       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
570     "%"
571   }
572 }
573
574 \newcommand*\LWR@hyperrefah[3]{%
575   \LWR@htmlltag{%
576     a href="%"
577       \detokenize\expandafter{\#1}\LWR@hashmark%
578       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
579     "%"
580   }
581 }
582
583 \newcommand*\LWR@hyperrefai[3]{%
584   \LWR@htmlltag{%
585     a href="%"
586       \detokenize\expandafter{\#1}\LWR@hashmark%
587       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
588     "%"
589   }
590 }
591
592 \newcommand*\LWR@hyperrefaj[3]{%
593   \LWR@htmlltag{%
594     a href="%"
595       \detokenize\expandafter{\#1}\LWR@hashmark%
596       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
597     "%"
598   }
599 }
599
600 \newcommand*\LWR@hyperrefak[3]{%
601   \LWR@htmlltag{%
602     a href="%"
603       \detokenize\expandafter{\#1}\LWR@hashmark%
604       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
605     "%"
606   }
607 }
608
609 \newcommand*\LWR@hyperrefal[3]{%
610   \LWR@htmlltag{%
611     a href="%"
612       \detokenize\expandafter{\#1}\LWR@hashmark%
613       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
614     "%"
615   }
616 }
617
618 \newcommand*\LWR@hyperrefam[3]{%
619   \LWR@htmlltag{%
620     a href="%"
621       \detokenize\expandafter{\#1}\LWR@hashmark%
622       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
623     "%"
624   }
625 }
626
627 \newcommand*\LWR@hyperrefan[3]{%
628   \LWR@htmlltag{%
629     a href="%"
630       \detokenize\expandafter{\#1}\LWR@hashmark%
631       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
632     "%"
633   }
634 }
635
636 \newcommand*\LWR@hyperrefao[3]{%
637   \LWR@htmlltag{%
638     a href="%"
639       \detokenize\expandafter{\#1}\LWR@hashmark%
640       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
641     "%"
642   }
643 }
644
645 \newcommand*\LWR@hyperrefap[3]{%
646   \LWR@htmlltag{%
647     a href="%"
648       \detokenize\expandafter{\#1}\LWR@hashmark%
649       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
650     "%"
651   }
652 }
653
654 \newcommand*\LWR@hyperrefaq[3]{%
655   \LWR@htmlltag{%
656     a href="%"
657       \detokenize\expandafter{\#1}\LWR@hashmark%
658       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
659     "%"
660   }
661 }
662
663 \newcommand*\LWR@hyperrefar[3]{%
664   \LWR@htmlltag{%
665     a href="%"
666       \detokenize\expandafter{\#1}\LWR@hashmark%
667       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
668     "%"
669   }
670 }
671
672 \newcommand*\LWR@hyperrefas[3]{%
673   \LWR@htmlltag{%
674     a href="%"
675       \detokenize\expandafter{\#1}\LWR@hashmark%
676       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
677     "%"
678   }
679 }
680
681 \newcommand*\LWR@hyperrefat[3]{%
682   \LWR@htmlltag{%
683     a href="%"
684       \detokenize\expandafter{\#1}\LWR@hashmark%
685       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
686     "%"
687   }
688 }
689
690 \newcommand*\LWR@hyperrefau[3]{%
691   \LWR@htmlltag{%
692     a href="%"
693       \detokenize\expandafter{\#1}\LWR@hashmark%
694       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
695     "%"
696   }
697 }
698
699 \newcommand*\LWR@hyperrefav[3]{%
700   \LWR@htmlltag{%
701     a href="%"
702       \detokenize\expandafter{\#1}\LWR@hashmark%
703       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
704     "%"
705   }
706 }
707
708 \newcommand*\LWR@hyperrefaw[3]{%
709   \LWR@htmlltag{%
710     a href="%"
711       \detokenize\expandafter{\#1}\LWR@hashmark%
712       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
713     "%"
714   }
715 }
716
717 \newcommand*\LWR@hyperrefax[3]{%
718   \LWR@htmlltag{%
719     a href="%"
720       \detokenize\expandafter{\#1}\LWR@hashmark%
721       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
722     "%"
723   }
724 }
725
726 \newcommand*\LWR@hyperrefay[3]{%
727   \LWR@htmlltag{%
728     a href="%"
729       \detokenize\expandafter{\#1}\LWR@hashmark%
730       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
731     "%"
732   }
733 }
734
735 \newcommand*\LWR@hyperrefaz[3]{%
736   \LWR@htmlltag{%
737     a href="%"
738       \detokenize\expandafter{\#1}\LWR@hashmark%
739       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
740     "%"
741   }
742 }
743
744 \newcommand*\LWR@hyperrefaa[3]{%
745   \LWR@htmlltag{%
746     a href="%"
747       \detokenize\expandafter{\#1}\LWR@hashmark%
748       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
749     "%"
750   }
751 }
752
753 \newcommand*\LWR@hyperrefab[3]{%
754   \LWR@htmlltag{%
755     a href="%"
756       \detokenize\expandafter{\#1}\LWR@hashmark%
757       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
758     "%"
759   }
760 }
761
762 \newcommand*\LWR@hyperrefac[3]{%
763   \LWR@htmlltag{%
764     a href="%"
765       \detokenize\expandafter{\#1}\LWR@hashmark%
766       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
767     "%"
768   }
769 }
770
771 \newcommand*\LWR@hyperrefad[3]{%
772   \LWR@htmlltag{%
773     a href="%"
774       \detokenize\expandafter{\#1}\LWR@hashmark%
775       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
776     "%"
777   }
778 }
779
780 \newcommand*\LWR@hyperrefae[3]{%
781   \LWR@htmlltag{%
782     a href="%"
783       \detokenize\expandafter{\#1}\LWR@hashmark%
784       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
785     "%"
786   }
787 }
788
789 \newcommand*\LWR@hyperrefaf[3]{%
790   \LWR@htmlltag{%
791     a href="%"
792       \detokenize\expandafter{\#1}\LWR@hashmark%
793       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
794     "%"
795   }
796 }
797
798 \newcommand*\LWR@hyperrefag[3]{%
799   \LWR@htmlltag{%
800     a href="%"
801       \detokenize\expandafter{\#1}\LWR@hashmark%
802       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
803     "%"
804   }
805 }
806
807 \newcommand*\LWR@hyperrefah[3]{%
808   \LWR@htmlltag{%
809     a href="%"
810       \detokenize\expandafter{\#1}\LWR@hashmark%
811       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
812     "%"
813   }
814 }
815
816 \newcommand*\LWR@hyperrefai[3]{%
817   \LWR@htmlltag{%
818     a href="%"
819       \detokenize\expandafter{\#1}\LWR@hashmark%
820       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
821     "%"
822   }
823 }
824
825 \newcommand*\LWR@hyperrefaj[3]{%
826   \LWR@htmlltag{%
827     a href="%"
828       \detokenize\expandafter{\#1}\LWR@hashmark%
829       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
830     "%"
831   }
832 }
833
834 \newcommand*\LWR@hyperrefak[3]{%
835   \LWR@htmlltag{%
836     a href="%"
837       \detokenize\expandafter{\#1}\LWR@hashmark%
838       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
839     "%"
840   }
841 }
842
843 \newcommand*\LWR@hyperrefal[3]{%
844   \LWR@htmlltag{%
845     a href="%"
846       \detokenize\expandafter{\#1}\LWR@hashmark%
847       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
848     "%"
849   }
850 }
851
852 \newcommand*\LWR@hyperrefam[3]{%
853   \LWR@htmlltag{%
854     a href="%"
855       \detokenize\expandafter{\#1}\LWR@hashmark%
856       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
857     "%"
858   }
859 }
860
861 \newcommand*\LWR@hyperrefan[3]{%
862   \LWR@htmlltag{%
863     a href="%"
864       \detokenize\expandafter{\#1}\LWR@hashmark%
865       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
866     "%"
867   }
868 }
869
870 \newcommand*\LWR@hyperrefao[3]{%
871   \LWR@htmlltag{%
872     a href="%"
873       \detokenize\expandafter{\#1}\LWR@hashmark%
874       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
875     "%"
876   }
877 }
878
879 \newcommand*\LWR@hyperrefap[3]{%
880   \LWR@htmlltag{%
881     a href="%"
882       \detokenize\expandafter{\#1}\LWR@hashmark%
883       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
884     "%"
885   }
886 }
887
888 \newcommand*\LWR@hyperrefaq[3]{%
889   \LWR@htmlltag{%
890     a href="%"
891       \detokenize\expandafter{\#1}\LWR@hashmark%
892       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
893     "%"
894   }
895 }
896
897 \newcommand*\LWR@hyperrefar[3]{%
898   \LWR@htmlltag{%
899     a href="%"
900       \detokenize\expandafter{\#1}\LWR@hashmark%
901       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
902     "%"
903   }
904 }
905
906 \newcommand*\LWR@hyperrefas[3]{%
907   \LWR@htmlltag{%
908     a href="%"
909       \detokenize\expandafter{\#1}\LWR@hashmark%
910       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
911     "%"
912   }
913 }
914
915 \newcommand*\LWR@hyperrefat[3]{%
916   \LWR@htmlltag{%
917     a href="%"
918       \detokenize\expandafter{\#1}\LWR@hashmark%
919       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
920     "%"
921   }
922 }
923
924 \newcommand*\LWR@hyperrefau[3]{%
925   \LWR@htmlltag{%
926     a href="%"
927       \detokenize\expandafter{\#1}\LWR@hashmark%
928       \detokenize\expandafter{\#2}.\detokenize\expandafter{\#3}%
929     "%"
930   }
931 }
932
933 \newcommand*\LWR@hyperrefav[3]{%
934  
```

```
58      \LWR@addlinktitle%
59  }%
60  \endgroup%
61  \LWR@hyperreffinish%
62 }
63
64 \newrobustcmd*\{\LWR@hyperrefb}{%
65   \begingroup%
66   \LWR@linkcatcodes%
67   \LWR@hyperrefbb%
68 }
```

\LWR@hyperrefc [⟨label⟩] {⟨text⟩}

Creates text as an `LATEX` link to the `LATEX` label.

```
69
70 \NewDocumentCommand{\LWR@hyperrefcb}{O{label}}{%
71   \LWR@startref{#1}%
72   \endgroup%
73   \LWR@hyperreffinish%
74 }
75
76 \newcommand*\{\LWR@hyperrefc}{%
77   \begingroup%
78   \LWR@linkcatcodes%
79   \LWR@hyperrefcb%
80 }
```

\hyperref {⟨1: URL⟩} {⟨2: category⟩} {⟨3: name⟩} {⟨4: text⟩} — or —  
[⟨1: label⟩] {⟨2: text⟩}

```
81 \DeclareRobustCommand*\{\hyperref}{%
82   \LWR@ensuredoingapar%
83   \Qifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
84 }
```

\hypertarget {⟨name⟩} {⟨text⟩}

Creates an anchor to name with the given text.

```
85 \NewDocumentCommand{\LWR@hypertargetb}{m +m}{%
86   \label{LWR-ht-#1}%
87   #2%
88   \endgroup%
89 }
90
91 \newcommand*\{\hypertarget}{%
92   \begingroup%
93   \LWR@linkcatcodes%
94   \LWR@hypertargetb%
95 }
```

\hyperlink {⟨name⟩} {⟨text⟩}

Creates a link to the anchor created by `hypertarget`, with the given link text.

Declared because also defined by memoir.

```
96 \DeclareDocumentCommand{\LWR@hyperlinkb}{m}{%
97     \LWR@hyperrefcb[LWR-ht-#1]%
98 }
99
100 \DeclareDocumentCommand{\hyperlink}{ }{%
101     \LWR@ensuredoingapar%
102     \begingroup%
103     \LWR@linkcatcodes%
104     \LWR@hyperlinkb%
105 }
```

\autoref \* {*<label>*}

For HTML, \cleveref is used instead.

```
106 \NewDocumentCommand{\autoref}{s m}{%
107     \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
108 }
```

\autopageref {*<label>*}

For HTML, \cleveref is used instead.

```
109 \NewDocumentCommand{\autopageref}{s m}{%
110     \IfBooleanTF{#1}{\cpageref{#2}}{\cref{#2}}%
111 }
```

\pdfstringdef {*<macroname>*} {*<TEXstring>*}

```
112 \newcommand{\pdfstringdef}[2]{}
```

\pdfbookmark [ *<level>*] {*<text>*} {*<name>*}

```
113 \newcommand{\pdfbookmark}[3][]{}
```

\currentpdfbookmark {*<text>*} {*<name>*}

```
114 \newcommand{\currentpdfbookmark}[2]{}{}
```

\subpdfbookmark {*<text>*} {*<name>*}

```
115 \newcommand{\subpdfbookmark}[2]{}{}
```

\belowpdfbookmark {*<text>*} {*<name>*}

```
116 \newcommand{\belowpdfbookmark}[2]{}{}
```

\texorpdfstring {*<TEXstring>*} {*<PDFstring>*}

```
117 \newcommand{\texorpdfstring}[2]{\#1}
```

```

\hypercalcbp  {\langle dimen\rangle}  From hyperref.

118 \def\hypercalcbp#1{%
119   \strip@pt\dimexpr .99626401\dimexpr(#1)\relax\relax
120 }%

\Acrobatmenu  {\langle menuoption\rangle} {\langle text\rangle}

121 \newcommand{\Acrobatmenu}[2]{}{}

\TextField  [\langle parameters\rangle] {\langle label\rangle}

122 \DeclareRobustCommand{\TextField}[2]{}{}

\CheckBox  [\langle parameters\rangle] {\langle label\rangle}

123 \DeclareRobustCommand{\CheckBox}[2]{}{}

\ChoiceMenu  [\langle parameters\rangle] {\langle label\rangle} {\langle choices\rangle}

124 \DeclareRobustCommand{\ChoiceMenu}[3]{}{}

\PushButton  [\langle parameters\rangle] {\langle label\rangle}

125 \DeclareRobustCommand{\PushButton}[2]{}{}

\Submit  [\langle parameters\rangle] {\langle label\rangle}

126 \DeclareRobustCommand{\Submit}[2]{}{}

\Reset  [\langle parameters\rangle] {\langle label\rangle}

127 \DeclareRobustCommand{\Reset}[2]{}{}

\Gauge  [\langle parameters\rangle] {\langle label\rangle}

128 \DeclareRobustCommand{\Gauge}[2]{}{}

\LayoutTextField  {\langle label\rangle} {\langle field\rangle}

129 \newcommand*\LayoutTextField[2]{}{}

\LayoutChoiceField  {\langle label\rangle} {\langle field\rangle}

130 \newcommand*\LayoutChoiceField[2]{}{}

\LayoutCheckField  {\langle label\rangle} {\langle field\rangle}

131 \newcommand*\LayoutCheckField[2]{}{}

```

---

```
\MakeRadioField  {\langle width\rangle} {\langle height\rangle}
132 \newcommand*{\MakeRadioField}[2]{}

\MakeCheckField {\langle width\rangle} {\langle height\rangle}
133 \newcommand*{\MakeCheckField}[2]{}

\MakeTextField  {\langle width\rangle} {\langle height\rangle}
134 \newcommand*{\MakeTextField}[2]{}

\MakeChoiceField {\langle width\rangle} {\langle height\rangle}
135 \newcommand*{\MakeChoiceField}[2]{}

\MakeFieldButton {\langle text\rangle}
136 \newcommand{\MakeFieldButton}[1]{}
```

---

### File 193 l warp-hyperxmp.sty

#### § 293 Package **hyperxmp**

Pkg hyperxmp **hyperxmp** is ignored.

**for HTML output:** Discard all options for l warp-hyperxmp:

```
1 \LWR@ProvidesPackageDrop{hyperxmp}[2018/11/27]
```

---

### File 194 l warp-hyphenat.sty

#### § 294 Package **hyphenat**

Pkg hyphenat **hyphenat** is emulated during HTML output, while the print-mode version is used inside a `lateXimage`.

**for HTML output:** 1 \LWR@ProvidesPackagePass{hyphenat}[2009/09/02]

```
2 \LetLtxMacro{\LWRHYNAT@origtextnhtt}{\textnhtt}
3 \LetLtxMacro{\LWRHYNAT@orignhttfamily}{\nhttfamily}
4 \LetLtxMacro{\LWRHYNAT@orignohyphens}{\nohyphens}
5 \LetLtxMacro{\LWRHYNAT@origbshyp}{\bshyp}
6 \LetLtxMacro{\LWRHYNAT@origfshyp}{\fshyp}
7 \LetLtxMacro{\LWRHYNAT@origdothyp}{\dothyp}
8 \LetLtxMacro{\LWRHYNAT@origcolonhyp}{\colonhyp}
9 \LetLtxMacro{\LWRHYNAT@orighyp}{\hyp}
```

---

```

10
11 \LetLtxMacro{textnhtt}{texttt}
12 \LetLtxMacro{nhttfamily}{ttfamily}
13
14 \renewcommand{\nohyphens}[1]{#1}
15 \renewrobustcmd{\bshyp}{%
16   \ifmmode\backslash else\textbackslash fi%
17 }
18 \renewrobustcmd{\fshyp}{/}
19 \renewrobustcmd{\dohyp}{.}
20 \renewrobustcmd{\colonhyp}{:}
21 \renewrobustcmd{\hyp}{-}
22
23 \appto{\LWR@restoreorigformatting}{%
24 \LetLtxMacro{textnhtt}{\LWRHYNAT@origtextnhtt}
25 \LetLtxMacro{nhttfamily}{\LWRHYNAT@orignhttfamily}
26 \LetLtxMacro{\nohyphens}{\LWRHYNAT@orignohyphens}
27 \LetLtxMacro{\bshyp}{\LWRHYNAT@origbshyp}
28 \LetLtxMacro{\fshyp}{\LWRHYNAT@origfshyp}
29 \LetLtxMacro{\dohyp}{\LWRHYNAT@origdohyp}
30 \LetLtxMacro{\colonhyp}{\LWRHYNAT@origcolonhyp}
31 \LetLtxMacro{\hyp}{\LWRHYNAT@orighyp}
32 }

```

---

### File 195 lwarf-idxlayout.sty

#### § 295 Package **idxlayout**

(Emulates or patches code by THOMAS TITZ.)

Pkg idxlayout idxlayout is emulated.

for HTML output Discard all options for lwarf-idxlayout:

```

1 \LWR@ProvidesPackageDrop{idxlayout}[2012/03/30]

2 \newcommand{\LWR@indexprenote}{}
3
4 \preto{\printindex}{}
5
6 \LWR@orignewpage
7 \LWR@startpars
8
9 \LWR@indexprenote
10
11 }
12
13 \newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
14 \newcommand*{\noindexprenote}{\renewcommand{\LWR@indexprenote}{}}
15
16 \newcommand{\idxlayout}[1]{}
17 \newcommand*{\indexfont}{}
18 \newcommand*{\indexjustific}{}

```

```
19 \newcommand*{\indexsubsdelim}{}  
20 \newcommand*{\indexstheadcase}{}  


---


```

File 196 **l warp-ifoddpage.sty**

§ 296 Package **ifoddpage**

(Emulates or patches code by MARTIN SCHARRER.)

Pkg ifoddpage ifoddpage is emulated.

for HTML output Discard all options for l warp-ifoddpage:

```
1 \LWR@ProvidesPackageDrop{ifoddpage}[2016/04/23]  
  
2 \newif\ifoddpage  
3  
4 \newif\ifoddpageoroneside  
5  
6 \DeclareRobustCommand{\checkoddpage}{\oddpage true\oddpageoroneside true}  
7  
8 \def\oddpage@page{1}  
9  
10 \def@ifoddpage{  
11     \expandafter\@firstoftwo  
12 }  
13  
14 \def@ifoddpageoroneside{  
15     \expandafter\@firstoftwo  
16 }
```

---

File 197 **l warp-imakeidx.sty**

§ 297 Package **imakeidx**

(Emulates or patches code by ENRICO GREGORIO.)

Pkg imakeidx imakeidx is patched for use by l warp.

letter headings When using *makeindex*, to match the print and HTML output's display of index letter headings, specify the l warp.ist style:

```
\makeindex[options={-s l warp.ist}]
```

(For HTML the l warp.ist style is used automatically, which displays letter headings.  
When using *xindy* the default style also displays letter headings.)

index setup See section 8.6.18 for how to setup l warpmk to process the indexes with imakeidx, both with and without shell escape.

for HTML output 1 \LWR@ProvidesPackagePass{imakeidx}[2016/10/15]

Use the new HTML suffix:

```
2 \catcode`\_=12%
3 \define@key{imki}{name}{\def\imki@name{\#1_html}}
4 \catcode`\_=8%
```

\printindex The HTML version of \printindex:

```
5 \catcode`\_=12%
6
7 \renewcommand*{\printindex}[1][\imki@jobname]{%
8 \LWR@orignewpage%
9 \LWR@startpars%
10 \ifstreq{\#1}{\imki@jobname}{%
11   \@ifundefined{\#1@idxfile}{%
12     \imki@error{\#1}%
13   }{%
14     \imki@putindex{\#1}%
15   }%
16 }{%
17   \@ifundefined{\#1_html@idxfile}{\imki@error{\#1_html}}{\imki@putindex{\#1_html}}%
18 }%
19 }
20
21 \catcode`\_=8%
```

\@index The HTML version of \@index:

```
22 \catcode`\_=12%
23
24 \def\@index[#1]{%
25   \ifstreq{\#1}{\imki@jobname}{%
26     {%
27       \@ifundefined{\#1@idxfile}{%
28         {%
29           \PackageWarning{lwarp-imakeidx}{Undefined index file '#1'}%
30           \begingroup
31             \@sanitize
32             \imki@nowrindex%
33         }%
34       }{%
35         \edef\@idxfile{\#1}%
36         \begingroup
37           \@sanitize
38           \wrindex{\@idxfile}%
39       }%
40     }%
41   }{%
42     \@ifundefined{\#1_html@idxfile}{%
43       {%
44         \PackageWarning{lwarp-imakeidx}{Undefined index file '#1_html'}%
45         \begingroup
46           \@sanitize
47           \imki@nowrindex%
48       }%
49     }%
50   }%
51 }
```

```

49      {%
50          \edef\@idxfile{\#1_html}%
51          \begingroup
52          \@sanitize
53          \wrindex\@idxfile%
54      }%
55  }%
56 }
57
58 \catcode`\_=8%

\item
\subitem
\subsubitem HTML versions of \item, etc.:

59 \appto\theindex{%
60     \let\item\LWR@indexitem%
61     \let\subitem\LWR@indexsubitem%
62     \let\subsubitem\LWR@indexsubsubitem%
63 }

\imki@wrindexentrysplit {\langle file\rangle} {\langle entry\rangle} {\langle page\rangle}
\imki@wrindexentryunique {\langle file\rangle} {\langle entry\rangle} {\langle page\rangle}

While writing index entries, adds an HTML label, and writes the label's index instead of
the page number:

64 \renewcommand\imki@wrindexentrysplit[3]{%
65 \addtocounter{LWR@autoindex}{1}%
66 \LWR@new@label{\LWRindex-\arabic{LWR@autoindex}}%
67 \expandafter\protected@write\csname\@idxfile\endcsname{%
68     {\string\indexentry{\#2}{\arabic{LWR@autoindex}}}}%
69 }
70
71 \renewcommand\imki@wrindexentryunique[3]{%
72 \addtocounter{LWR@autoindex}{1}%
73 \LWR@new@label{\LWRindex-\arabic{LWR@autoindex}}%
74 \protected@write\@idxfile{%
75     {\string\indexentry[\#1]{\#2}{\arabic{LWR@autoindex}}}}%
76 }
77
78 \def\imki@wrindexsplit#1#2{%
79 \imki@wrindexentrysplit{\#1}{\#2}{\thepage}%
80 \endgroup\imki@showidxentry{\#1}{\#2}%
81 \esphack%
82 }
83
84 \def\imki@wrindexunique#1#2{%
85 \imki@wrindexentryunique{\#1}{\#2}{\thepage}%
86 \endgroup\imki@showidxentry{\#1}{\#2}%
87 \esphack%
88 }
89

```

---

```
\LWR@imki@setxdydefopts
```

Sets the `xindy` HTML options, ignoring the user's settings.

```
90 \newcommand*{\LWR@imki@setxdydefopts}{%
91   \edef\imki@options{ \space %
92     -M \space \LWR@xindyStyle\space %
93     -L \space \LWR@xindyLanguage\space %
94     -C \space \LWR@xindyCodepage\space %
95   }%
96 }
```

```
\LWR@imki@setdefopts {<user options>}
```

Sets the HTML options, added to the user's settings, depending on whether `makeindex` or `xindy` are used.

For `makeindex`, the user's choice is ignored, and only the `l warp` version is used. (Only one style at a time is possible.)

For `xindy`, multiple modules may be specified, and the `l warp` version is appended.

```
97 \newcommand*{\LWR@imki@setdefopts}[1]{%
98 \ifblank{#1}{%
99   \edef\imki@options{\space -s \space \LWR@makeindexStyle \space}%
100  \ifdefstring{\imki@progdefault}{xindy}{\LWR@imki@setxdydefopts}{}}%
101  \ifdefstring{\imki@progdefault}{texindy}{\LWR@imki@setxdydefopts}{}}%
102  \ifdefstring{\imki@progdefault}{truedxindy}{\LWR@imki@setxdydefopts}{}}%
103 }{%
104   \edef\imki@options{\space #1 \space}%
105 }%
106 }
```

```
\imki@makeindex Use the new HTML options:
```

```
107 \xpatchcmd{\imki@makeindex}
108   {\let\imki@options\space}
109   {\LWR@imki@setdefopts{}}
110   {}
111   {\LWR@patcherror{imakeidx}{makeindex}}
```

Use the new HTML options.

```
112 \define@key{\imki}{options}{\LWR@imki@setdefopts{#1}}
```

```
\imki@resetdefaults Use the new HTML options:
```

```
113 \xpatchcmd{\imki@resetdefaults}
114   {\def\imki@options{ {}}
115   {\LWR@imki@setdefopts{}}
116   {}
117   {\LWR@patcherror{imakeidx}{resetdefaults}}}
```

`theindex` was already defined `\AtBeginDocument` by the `l warp` core, so it must be redefined here similarly, but patched for `imakeidx`:

```
Env theindex
```

```

118 \AtBeginDocument{
119 \renewenvironment*{theindex}{%
120   \imki@maybeaddtotoc
121   \imki@indexlevel{\indexname}
122   \let\item\LWR@indexitem%
123   \let\subitem\LWR@indexsubitem%
124   \let\subsubitem\LWR@indexsubsubitem%
125 }{}%
126 }% AtBeginDocument

```

Update to the new defaults:

```
127 \imki@resetdefaults
```

Update to the new patches:

\AtBeginDocument is because \@wrindex is previously defined as \AtBeginDocument in the l warp core.

```

128 \ifimki@splitindex
129   \let\imki@startidx\imki@startidxunique
130   \AtBeginDocument{\let@\wrindex\imki@wrindexunique}
131   \let\imki@putindex\imki@putindexunique
132   \let\imki@wrindexentry\imki@wrindexentryunique
133   \let\imki@startidxsplit@\undefined
134   \let\imki@wrindexsplit@\undefined
135   \let\imki@putindexsplit@\undefined
136 \else
137   \let\imki@startidx\imki@startidxsplit
138   \AtBeginDocument{\let@\wrindex\imki@wrindexsplit}
139   \let\imki@putindex\imki@putindexsplit
140   \let\imki@wrindexentry\imki@wrindexentrysplit
141   \let\imki@startidxunique@\undefined
142   \let\imki@wrindexunique@\undefined
143   \let\imki@putindexunique@\undefined
144 \fi

```

### File 198 l warp-index.sty

#### § 298 Package **index**

(Emulates or patches code by DAVID M. JONES.)

Pkg index index is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{index}[2004/01/20]

Use \theLWR@autoindex instead of \thepage. \@tempswattrue is used to force an immediate write to the index file instead of waiting until the end of the page.

```

2 \xpatchcmd{\newindex}
3   {\x@newindex[\thepage]}

```

```

4   {%
5     \@tempswatrue%
6     \x@newindex[theLWR@autoindex]%
7   }
8   {}
9   {\LWR@patcherror{index}{newindex}}
10
11 \xpatchcmd{\renewindex}
12   {\x@renewindex[thepage]}
13   {%
14     \@tempswatrue%
15     \x@renewindex[theLWR@autoindex]%
16   }
17   {}
18   {\LWR@patcherror{index}{renewindex}}

```

Patched to set a new autoindex:

```

19 \xpatchcmd{@wrindex}
20   {\begingroup}
21   {%
22     \addtocounter{LWR@autoindex}{1}%           lwarp
23     \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
24     \begingroup%
25   }
26   {}
27   {\LWR@patcherror{index}{@wrindex}}

```

\AtBeginDocument **lwarp** core \lets \@wrindex to \LWR@wrindex. Since the **index** package has been loaded, \let to its version instead:

```

28 \let\LWR@index@wrindex@\wrindex
29
30 \AtBeginDocument{
31 \let@\wrindex\LWR@index@wrindex
32 }

```

Modified to add \index@prologue:

```

33 \AtBeginDocument{
34 \renewenvironment*{theindex}{%
35   \LWR@indexsection{\indexname}%
36   \ifx\index@prologue\empty\else
37     \index@prologue
38     \bigskip
39   \fi
40   \let\item\LWR@indexitem%
41   \let\subitem\LWR@indexsubitem%
42   \let\subsubitem\LWR@indexsubsubitem%
43 }{}%
44 }% AtBeginDocument

```

Disabled:

```
45 \def@showidx#1{}
```

```
46 \let\@texttop\relax
47 \renewcommand*\{\raggedbottom}{}%
48 \renewcommand*\{\flushbottom}{}%
49 \renewcommand*\{\markboth}[2]{}%
50 \renewcommand*\{\markright}[1]{}%
```

---

**File 199 l warp-inputtrc.sty****§ 299 Package **inputtrc****

(Emulates or patches code by UWE LÜCK.)

Pkg **inputtrc** **inputtrc** is patched for use by **l warp**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{inputtrc}[2012/10/10]

Patched to remove extraneous spaces, which sometimes showed up in logos inside a `lateximage`.

```
2 \renewcommand*\{\IT@prim@input}[1]{%
3   \typeout{\IT@indent\IT@currfile INPUTTING #1}%
4 %... TODO: option to write to ‘.log’ only.
5   \xdef\IT@filestack{\{\IT@currfile}\IT@filestack}%
6   \xdef\IT@currfile{\#1}%
7   \expandafter \gdef\expandafter \IT@indent\expandafter{%
8     \IT@indent \IT@indent@unit}%
9     \IT@input#1%
10    \expandafter\IT@pop@indent\IT@indent \IT@input#1%
11    \expandafter\IT@pop@file \IT@filestack\IT@input#1%
12    \IT@maybe@returnmessage% v0.2%
13 }
```

---

**File 200 l warp-intopdf.sty****§ 300 Package **intopdf****

Pkg **intopdf** **intopdf** is emulated.

The filespec, MIME type, and description are ignored for now.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{intopdf}[2019/05/28]

```
2 \NewDocumentCommand{\attachandlink}{o m o m m}{%
3   \href{\#2}{\#5}%
4 }
```

---

File 201 **l warp-karnaugh-map.sty**

§ 301 Package **karnaugh-map**

*(Emulates or patches code by MATTIAS JACOBSSON.)*

Pkg karnaugh-map karnaugh-map is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{karnaugh-map}[2017/02/20]

(It is hard to patch this macro, so the entire thing is redefined here, with the l warp modifications identified in comments.)

```

2 \RenewDocumentEnvironment{karnaugh-map}{s 0{4} 0{4} 0{1} 0{$X_1X_0$} 0{$X_3X_2$} 0{$X_5X_4$}} {%
3   \begingroup
4     % store map size {[START]
5     \renewcommand{\@karnaughmap@var@mapsizex@}{#2}%
6     \renewcommand{\@karnaughmap@var@mapsizey@}{#3}%
7     \renewcommand{\@karnaughmap@var@mapsizel@}{#4}%
8   % [END]}
9   % determinate if markings should be color or black and white
10  \IfBooleanTF{#1}{%
11    % should be black and white
12    \renewcommand{\@karnaughmap@var@bw@}{1}%
13  }{%
14    % should be color
15    \renewcommand{\@karnaughmap@var@bw@}{0}%
16  }%
17  %
18  % find matching matrix template and alignment parameters {[START]
19  \newcommand{\@karnaughmap@local@matrixtemplate@}{0}'0' is considered as missing matrix template
20  \newcommand{\@karnaughmap@local@maprealignmentx@}{0}%
21  \newcommand{\@karnaughmap@local@maprealignmenty@}{0}%
22  \ifnum \@karnaughmap@var@mapsizex@=\@karnaughmap@var@mapsizel@=221
23    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
24      \&          0 \&          1 \& \phantom{0} \\
25      0 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&           \\
26      1 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&           \\
27      \phantom{0} \&           \&           \&           \\
28    }%
29  \fi
30  \ifnum \@karnaughmap@var@mapsizex@=\@karnaughmap@var@mapsizey@=\@karnaughmap@var@mapsizel@=241
31    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
32      \&          0 \&          1 \& \phantom{00} \\
33      00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&           \\
34      01 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&           \\
35      11 \& |(000110)| \phantom{0} \& |(000111)| \phantom{0} \&           \\
36      10 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \&           \\
37      \phantom{00} \&           \&           \&           \\
38    }%
39  \fi

```

```

40 \ifnum\@karnaughmap@var@mapsizex@=\@karnaughmap@var@mapsizey@=\@karnaughmap@var@mapsizex@=421
41     \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
42         \&          00 \&          01 \&          11 \&          10 \& \phantom{0}
43         0 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001)
44         1 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011)
45         \phantom{0} \&          \&          \&          \&          \&
46     }%
47 }
48 \ifnum\@karnaughmap@var@mapsizex@=\@karnaughmap@var@mapsizey@=\@karnaughmap@var@mapsizex@=441
49     \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
50         \&          00 \&          01 \&          11 \&          10 \& \phantom{0}
51         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001)
52         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011)
53         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(00111)
54         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(00101)
55         \phantom{0} \&          \&          \&          \&          \&
56     }%
57 }
58 \ifnum\@karnaughmap@var@mapsizex@=\@karnaughmap@var@mapsizey@=\@karnaughmap@var@mapsizex@=442
59     \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
60         \&          00 \&          01 \&          11 \&          10 \& \phantom{0}
61         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001)
62         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011)
63         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(00111)
64         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(00101)
65         \phantom{0} \&          \&          \&          \&          \&
66     }%
67     \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
68 }
69 \ifnum\@karnaughmap@var@mapsizex@=\@karnaughmap@var@mapsizey@=\@karnaughmap@var@mapsizex@=444
70     \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
71         \&          00 \&          01 \&          11 \&          10 \& \phantom{0}
72         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001)
73         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011)
74         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(00111)
75         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(00101)
76         \phantom{0} \&          \&          \&          \&          \&
77         00 \& |(100000)| \phantom{0} \& |(100001)| \phantom{0} \& |(100011)| \phantom{0} \& |(10001)
78         01 \& |(100100)| \phantom{0} \& |(100101)| \phantom{0} \& |(100111)| \phantom{0} \& |(10011)
79         11 \& |(101100)| \phantom{0} \& |(101101)| \phantom{0} \& |(101111)| \phantom{0} \& |(10111)
80         10 \& |(101000)| \phantom{0} \& |(101001)| \phantom{0} \& |(101011)| \phantom{0} \& |(10101)
81         \phantom{0} \&          \&          \&          \&          \&
82     }%
83     \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
84     \renewcommand{\@karnaughmap@local@maprealignmenty@}{-2.5}%
85 }
86 % [END]
87 % test if a matrix template is found or not(aka "\@karnaughmap@local@matrixtemplate@" equals to '0')
88 \ifdefstring{\@karnaughmap@Local@matrixtemplate@}{0}{% lwarp
89 %     \ifnum0=\@karnaughmap@local@matrixtemplate@% original
90 %         % print error if no template could be found
91 %         \PackageError{lwarp-karnaugh-map}{%
92 %             Can not find a template fitting your specification (\@karnaughmap@var@mapsizex@\space x \@karnaughma
93 %         }%
94     Existing templates have the following dimensions: 2x2x1, 2x4x1, 4x2x1, 4x4x1, 4x4x2, and 4x4x4.

```

```
95      }%
96 %     \fi    original
97 }{}%    lwarp
98 \begin{tikzpicture}
99   % grid
100  % for all dimensions
101 \draw [color=black, ultra thin] (0,0) grid (@karnaughmap@var@mapsizex@, @karnaughmap@var@mapsizey@);
102  % when there are 2 sub maps
103 \ifnum@karnaughmap@var@mapsizex@=2
104   \draw [color=black, ultra thin] (5,0) grid (9,4);
105 \fi
106  % when there are 4 sub maps
107 \ifnum@karnaughmap@var@mapsizex@=4
108   \draw [color=black, ultra thin] (5,0) grid (9,4);
109   \draw [color=black, ultra thin] (0,-5) grid (4,-1);
110   \draw [color=black, ultra thin] (5,-5) grid (9,-1);
111 \fi
112  % labels
113  % for all dimensions
114 \node[above] at (@karnaughmap@var@mapsizex@*0.5, @karnaughmap@var@mapsizey@+0.9) {\small{\#5}};
115 \node[left] at (-0.9, @karnaughmap@var@mapsizey@*0.5) {\small{\#6}};
116  % when there are 2 sub maps
117 \ifnum@karnaughmap@var@mapsizex@=2
118   \node[above] at (7,4.9) {\small{\#5}};
119   % extra sub maps labels
120   \node[below] at (2,-0.1) {\small{\#7$=0$}};
121   \node[below] at (7,-0.1) {\small{\#7$=1$}};
122 \fi
123  % when there are 4 sub maps
124 \ifnum@karnaughmap@var@mapsizex@=4
125   \node[above] at (7,4.9) {\small{\#5}};
126   \node[left] at (-0.9,-3) {\small{\#6}};
127   % extra sub maps labels
128   \node[below] at (2,-0.1) {\small{\#7$=00$}};
129   \node[below] at (7,-0.1) {\small{\#7$=01$}};
130   \node[below] at (2,-5.1) {\small{\#7$=10$}};
131   \node[below] at (7,-5.1) {\small{\#7$=11$}};
132 \fi
133  % data
134 \matrix[
135   matrix of nodes,
136   ampersand replacement=\&,
137   column sep={1cm,between origins},
138   row sep={1cm,between origins},
139 ] at (@karnaughmap@var@mapsizex@*0.5+\karnaughmap@local@maprealignmentx@, @karnaughmap@var@mapsizey@*0.5+\karnaughmap@local@matrixtemplate@%
140   \karnaughmap@local@matrixtemplate@%
141 ];
142 }{
143   \end{tikzpicture}
144 \endgroup
145 }
```

---

**File 202 l warp-keyfloat.sty****§ 302 Package keyfloat**

(Emulates or patches code by BRIAN DUNN.)

Pkg keyfloat keyfloat is supported with a considerable amount of hacking. (It's a mashup of l warp, keyfloat, and tocdata.)

⚠ keywrap If placing a \keyfig[H] inside a keywrap, use an absolute width for \keyfig, instead of \w-proportional widths. (The [H] option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the \w option.)

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{keyfloat}[2019/09/23]
2
3 \@ifpackagelater{keyfloat}{2019/09/23}{}{
4     \PackageError{l warp-keyfloat}
5     {%
6         The keyfloat package is out of date.\MessageBreak
7         Update to keyfloat v2.01 2019/09/23 or later%
8     }
9     {%
10        Please update the keyfloat package. It's worth it!%
11    }
12 }
```

After keyfloat has loaded:

```
13 \AtBeginDocument{

14 \providecommand*\KFLT@LWR@hook@boxouter(){}
15 \renewcommand*\KFLT@LWR@hook@boxouter{}{
16     \ifbool{\KFLT@keywrap}{%
17         }{%
18             \ifnumequal{\value{\KFLT@keyfloatdepth}}{0}{%
19                 \setlength{\ linewidth}{6in}%
20                 \setlength{\ textwidth}{6in}%
21                 \setlength{\ textheight}{9in}%
22             }{%
23         }%
24         \normalcolor%
25     }

26 \LetLtxMacro\KFLT@LWR@hook@keysubfloats\KFLT@LWR@hook@boxouter
27
28 \let\KFLT@LWR@hook@keyfloatsminipage\relax
29 \endKFLT@LWR@hook@keyfloatsminipage\relax
30 \newenvironment*\KFLT@LWR@hook@keyfloatsminipage}[1]{}{}
```

```

31 \LetLtxMacro{\KFLT@LWR@hook}{\keyfloats\KFLT@LWR@hook@boxouter}
32
33 \renewcommand*{\KFLT@maybeendfloatrow}{%
34     \ifnumless{\value{\KFLT@thiscol}}{\value{\KFLT@numcols}}{%
35         {}% thiscol < numcols
36         {}% >=
37         \defcounter{\KFLT@thiscol}{0}%
38     }%
39 }%
40
41 \renewcommand{\KFLT@trackrows}{%
42 }%

```

If are nested inside a keyfloats or a subfloat:

```

43     \ifboolexpr{%
44         test {\ifnumgreater{\value{\KFLT@keyfloatdepth}}{0}} or%
45         \bool{\KFLT@inkeys floats}%
46     }%
47     {}% nested

```

Tracks row start and end:

```
48     \KFLT@maybestartfloatrow%
```

Possibly fill space between columns:

```

49     \ifnumgreater{\value{\KFLT@thiscol}}{1}{%
50         {}%
51         \hfill%
52     }%
53     {}% nested
54 }% not nested
55 }%
56 }

57 \RenewDocumentCommand{\KFLT@onefigureimage}{m}{%
58 }%
59 \LWR@traceinfo{\KFLT@onefigureimage}%
60 % \begin{lrbox}{\KFLT@envbox}%
61 \ifthenelse{\NOT\equal{\KFLT@lw}{}}{%
62     {}%
63     \KFLT@frame{\includegraphics{%
64         [scale=\KFLT@s, width=\KFLT@imagewidth]{#1}}%
65     }%
66     {}% not linewidth
67     \ifthenelse{\dimtest{\KFLT@w}{>}0pt}{%
68         {}% width is given
69         \ifthenelse{\dimtest{\KFLT@h}{>}0pt}{%
70             {}% w and h
71             \KFLT@frame{\includegraphics{%
72                 [scale=\KFLT@s,%
73                 width=\KFLT@imagewidth, height=\KFLT@h]{#1}}%
74         }% w and h

```

```
75          {%
76              \KFLT@frame{\includegraphics{%
77                  [scale=\KFLT@s, width=\KFLT@imagewidth]{#1}}}%
78          }%
79      }%
80      {%
81          \ifthenelse{\dimtest{\KFLT@h}>0pt}{%
82              {%
83                  \KFLT@frame{\includegraphics{%
84                      [scale=\KFLT@s, height=\KFLT@h]{#1}}}%
85              }%
86          }%
87          \KFLT@frame{\includegraphics{%
88              [scale=\KFLT@s]{#1}}}%
89      }%
90      }%
91  }%
92 % \end{lrbox}%
93 % \unskip%
94 % \KFLT@findenvboxwidth%
95 % \begin{turn}{\KFLT@r}%
96 % \KFLT@frame{\usebox{\KFLT@envbox}}%
97 % \unskip%
98 % \end{turn}%
99 \LWR@traceinfo{KFLT@onefigureimage: done}%
100 }%  
  
101 \RenewDocumentEnvironment{KFLT@boxinner}{}  
102 {%
103     \LWR@traceinfo{KFLT@boxinner}%
104     \LWR@stoppars%
105     \minipagewidth%
106     \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{%
107         \fminipage{\KFLT@imagewidth}%
108     }{%
109         \minipage{\KFLT@imagewidth}%
110     }%
111 }%
112 {%
113     \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{%
114         \endfminipage%
115     }{%
116         \endminipage%
117     }%
118     \LWR@startpars%
119     \LWR@traceinfo{KFLT@boxinner: done}%
120 }%  
  
121 \newcommand*{\LWR@KFLT@settextalign}[1]{%
122     \def\LWR@KFLT@textalign{justify}%
123     \ifcsstring{KFLT@#1textalign}{centering}{%
124         \def\LWR@KFLT@textalign{center}%
125     }{%
126     \ifcsstring{KFLT@#1textalign}{raggedleft}{%
127         \def\LWR@KFLT@textalign{right}%
128     }{%
129     }%
130     }%
131 }
```

```

128      {}%
129      \ifcsstring{KFLT@#1textalign}{\raggedright}%
130          {\def\LWR@KFLT@textalign{left}}%
131      {}%
132 }
133
134 \renewcommand{\KFLT@addtext}[1]%
135 {%

```

Is there text to add?

```

136      \ifcseempty{KFLT@#1t}%
137          {}% no text
138          {}% text to add
139              {}% local

```

Add some space, then create a <div> to contain the text:

```

140      \addvspace{\smallskipamount}%
141      \LWR@KFLT@settextalign{#1}%
142      \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%

```

Set the alignment and some text parameters:

```

143 %      \csuse{KFLT@#1textalign}%
144 %      \footnotesize%
145      \setlength{\parskip}{1.5ex}%
146      \setlength{\parindent}{0em}%

```

Typeset the actual text:

```
147      \csuse{KFLT@#1t}%
```

Close it all out with a little more space:

```

148      \end{BlockClass}%
149 %      \par\addvspace{2ex}%
150 %      {}% local
151      {}% text to add
152 }
153
154 \@ifpackageloaded{tocdata}%
155 {}
156 {}% tocdata not loaded
157
158      \newcommand*\LWR@KFLT@setnamealign[1]{%
159          \def\LWR@KFLT@textalign{justify}%
160          \ifstreq{\#1}{\centering}%
161              {\def\LWR@KFLT@textalign{center}}%
162          {}%
163          \ifstreq{\#1}{\raggedleft}%
164              {\def\LWR@KFLT@textalign{right}}%
165          {}%
166          \ifstreq{\#1}{\raggedright}%

```

```

167           {\def\LWR@KFLT@textalign{left}}%
168           { }%
169       }
170
171   \renewcommand*{\KFLT@addartisttext}[3]{%
172

```

Add space and create the name inside a <div>:

```

173 %           \addvspace{\medskipamount}%
174   %           \begin{minipage}{\linewidth}%
175   %             \LWR@KFLT@setnamealign{#3}%
176   %             \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%
177

```

Text alignment is #3, and depends on artist or author:

```

178   %     #3%
179

```

#1 is empty or 'subgrp'  
#2 is empty for artist, 'u' for author:

```

180       \footnotesize\textsc{%
181           \KFLT@optionalname{\csuse{KFLT@#1a#2p}}%
182           \KFLT@optionalname{\csuse{KFLT@#1a#2f}}%
183           \csuse{KFLT@#1a#2l}%
184           \csuse{KFLT@#1a#2s}%
185       }%
186   %           \end{minipage}%
187   %           \end{BlockClass}%
188 %           \par\addvspace{2ex}%
189   }
190
191 }% tocdata not loaded

```

```

Env KFLT@marginfloat  [<offset>] {<type>}
192 \DeclareDocumentEnvironment{KFLT@marginfloat}{O{-1.2ex} m}%
193 {%
194   \uselengthunit{PT}%
195   \LWR@BlockClassWP%
196   {float:right; width:2in; margin:10pt}%
197   {}%
198   {marginblock}%
199   \captionsetup{type=#2}%
200   \minipage{\LWR@usersmarginparwidth}%
201   \setlength{\marginparwidth}{.95\LWR@usersmarginparwidth}%
202 }
203 {%
204   \endminipage%
205   \endLWR@BlockClassWP%
206 }

```

---

```

207 \DeclareDocumentEnvironment{marginfigure}{o}
208   {\begin{KFLT@marginfloat}{figure}}
209   {\end{KFLT@marginfloat}}
210
211 \DeclareDocumentEnvironment{marginable}{o}
212   {\begin{KFLT@marginfloat}{table}}
213   {\end{KFLT@marginfloat}}
214
Env keywrap  {\langle width\rangle} {\langle keyfloat\rangle}
214 \DeclareDocumentEnvironment{keywrap}{m +m}
215 {%
216   \begin{LWR@setvirtualpage}*
217   \setlength{\LWR@templengthone}{#1}%
218   \begin{LWR@BlockClassWP}%
219     {%
220       float:right; width:\LWR@printlength{\LWR@templengthone}; % extra space
221       margin:10pt%
222     }%
223     {%
224       \marginblock%
225       \setlength{\linewidth}{.95\LWR@templengthone}%
226       \booltrue{KFLT@keywrap}%
227     #2%
228     \end{LWR@BlockClassWP}%
229     \end{LWR@setvirtualpage}%
230   }
231 {}%
232 }% AtBeginDocument

```

---

#### File 203 **lwarf-layaureo.sty**

##### § 303 Package **layaureo**

Pkg layaureo layaureo is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{layaureo}[2004/09/16]

---

#### File 204 **lwarf-layout.sty**

##### § 304 Package **layout**

Pkg layout layout is ignored.

**for HTML output:** Discard all options for lwarf-layout:

1 \LWR@ProvidesPackageDrop{layout}[2014/10/28]

```
2 \NewDocumentCommand{\layout}{s}{}{}
```

---

File 205 **l warp-layouts.sty**

§ 305      Package **layouts**

Pkg    layouts    layouts is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop[layouts][2009/09/02]

```
2 \newif\ifoddpage layout
3   \oddpagelayouttrue
4 \newif\iftwocolumnlayout
5   \twocolumnlayoutfalse
6 \newif\ifdrawmarginpars
7   \drawmarginparstrue
8 \newif\ifdrawparameters
9   \drawparameterstrue
10 \newif\iflistaspara
11   \listasparatrue
12 \newif\ifruninhead
13   \runinheadfalse
14 \newif\ifprintparameters
15   \printparameterstrue
16 \newif\ifdrawdimensions
17   \drawdimensionsfalse
18 \newif\ifprintheadings
19   \printheadingstrue
20 \newcommand{\testdrawdimensions}{}{}
21 \newcommand{\testprintparameters}{}{}
22 \newcommand{\setlabelfont}[1]{}{}
23 \newcommand{\setparametertextfont}[1]{}{}
24 \newcommand{\setvaluesetextsize}[1]{}{}
25 \newcommand{\setLayoutscale}[1]{}{}
26 \newcommand{\setuplayouts}{}{}
27 \newcommand{\printinunitsof}[1]{}{}
28 \newcommand{\prntlen}[1]{}{}
29 \newcommand{\trypaperwidth}[1]{}{}
30 \newcommand{\trypaperheight}[1]{}{}
31 \newcommand{\tryhoffset}[1]{}{}
32 \newcommand{\tryvoffset}[1]{}{}
33 \newcommand{\trytopmargin}[1]{}{}
34 \newcommand{\tryheadheight}[1]{}{}
35 \newcommand{\tryheadsep}[1]{}{}
36 \newcommand{\trytextheight}[1]{}{}
37 \newcommand{\tryfootskip}[1]{}{}
38 \newcommand{\tryoddsidemargin}[1]{}{}
39 \newcommand{\tryevensidemargin}[1]{}{}
40 \newcommand{\trytextwidth}[1]{}{}
41 \newcommand{\trymarginparsep}[1]{}{}
42 \newcommand{\trymarginparwidth}[1]{}{}
43 \newcommand{\trymarginparpush}[1]{}{}
```

```
44 \newcommand{\trycolumnsep}[1]{}
45 \newcommand{\trycolumnseprule}[1]{}
46 \newcommand{\setfootbox}[2]{}
47 \newcommand{\currentpage}{}
48 \newcommand{\drawpage}{(draw page)}
49 \newcommand{\pagediagram}{(page diagram)}
50 \newcommand{\pagedesign}{(page design)}
51 \newcommand{\pagevalues}{(page values)}
52 \newcommand{\trystockwidth}[1]{}
53 \newcommand{\trystockheight}[1]{}
54 \newcommand{\trytrimedge}[1]{}
55 \newcommand{\trytrimtop}[1]{}
56 \newcommand{\tryuppermargin}[1]{}
57 \newcommand{\tryspinemargin}[1]{}
58 \newcommand{\currentstock}{}
59 \newcommand{\drawstock}{(draw stock)}
60 \newcommand{\stockdiagram}{(stock diagram)}
61 \newcommand{\stockdesign}{(stock design)}
62 \newcommand{\stockvalues}{(stock values)}
63 \newcommand{\tryitemindent}[1]{}
64 \newcommand{\trylabelwidth}[1]{}
65 \newcommand{\trylabelsep}[1]{}
66 \newcommand{\tryleftmargin}[1]{}
67 \newcommand{\tryrightmargin}[1]{}
68 \newcommand{\trylistparindent}[1]{}
69 \newcommand{\trytopsep}[1]{}
70 \newcommand{\tryparskip}[1]{}
71 \newcommand{\trypartopsep}[1]{}
72 \newcommand{\tryparsep}[1]{}
73 \newcommand{\tryitemsep}[1]{}
74 \newcommand{\currentlist}{}
75 \newcommand{\drawlist}{(draw list)}
76 \newcommand{\listdiagram}{(list diagram)}
77 \newcommand{\listdesign}{(list design)}
78 \newcommand{\listvalues}{(list values)}
79 \newcommand{\tryfootins}[1]{}
80 \newcommand{\tryfootnotesep}[1]{}
81 \newcommand{\tryfootnotebaseline}[1]{}
82 \newcommand{\tryfootruleheight}[1]{}
83 \newcommand{\tryfootrulefrac}[1]{}
84 \newcommand{\currentfootnote}{}
85 \newcommand{\drawfootnote}{(draw footnote)}
86 \newcommand{\footnotediagram}{(footnote diagram)}
87 \newcommand{\footnotedesign}{(footnote design)}
88 \newcommand{\footnotevalues}{(footnote values)}
89 \newcommand{\tryparindent}[1]{}
90 \newcommand{\tryparlinewidth}[1]{}
91 \newcommand{\tryparbaselineskip}[1]{}
92 \newcommand{\currentparagraph}{}
93 \newcommand{\drawparagraph}{(draw paragraph)}
94 \newcommand{\paragraphdiagram}{(paragraph diagram)}
95 \newcommand{\paragraphdesign}{(paragraph design)}
96 \newcommand{\paragraphvalues}{(paragraph values)}
97 \newcommand{\trybeforeskip}[1]{}
98 \newcommand{\tryafterskip}[1]{}
```

```

99 \newcommand{\tryindent}[1]{}
100 \newcommand{\currentheading}{}
101 \newcommand{\drawheading}[1]{(draw heading)}
102 \newcommand{\headingdiagram}[1]{(heading diagram)}
103 \newcommand{\headingdesign}[1]{(heading design)}
104 \newcommand{\headingvalues}{(heading values)}
105 \newcommand{\trytextfloatsep}[1]{}
106 \newcommand{\tryfloatsep}[1]{}
107 \newcommand{\tryintextsep}[1]{}
108 \newcommand{\trytopfigrule}[1]{}
109 \newcommand{\trybotfigrule}[1]{}
110 \newcommand{\currentfloat}{}
111 \newcommand{\drawfloat}{(draw float)}
112 \newcommand{\floatdiagram}{(float diagram)}
113 \newcommand{\floatdesign}{(float design)}
114 \newcommand{\floatvalues}{(float values)}
115 \newcommand{\trytotalnumber}[1]{}
116 \newcommand{\trytopnumber}[1]{}
117 \newcommand{\trybottomnumber}[1]{}
118 \newcommand{\trytopfraction}[1]{}
119 \newcommand{\trytextfraction}[1]{}
120 \newcommand{\trybottomfraction}[1]{}
121 \newcommand{\currentfloatpage}{}
122 \newcommand{\drawfloatpage}{(draw floatpage)}
123 \newcommand{\floatpagediagram}{(floatpage diagram)}
124 \newcommand{\floatpagedesign}{(floatpage design)}
125 \newcommand{\floatpagevalues}{(floatpage values)}
126 \newcommand{\trytocindent}[1]{}
127 \newcommand{\trytocnumwidth}[1]{}
128 \newcommand{\trytoclinewidth}[1]{}
129 \newcommand{\trytocrmarg}[1]{}
130 \newcommand{\trytocpnumwidth}[1]{}
131 \newcommand{\trytocdotsep}[1]{}
132 \newcommand{\currenttoc}{}
133 \newcommand{\drawtoc}{(draw toc)}
134 \newcommand{\tocdiagram}{(toc diagram)}
135 \newcommand{\tocdesign}{(toc design)}
136 \newcommand{\tocvalues}{(toc values)}
137 \newcommand{\drawaspread}[8][0]{(a spread)}
138 \newcommand{\drawfontframe}[1]{(font frame)}
139 \newcommand{\drawfontframelabel}[1]{}

```

File 206 **lwarf-leading.sty**

§ 306 Package **leading**

Pkg **leading** **leading** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{leading}[2008/12/11]

2 \newcommand{\leading}[1]{}

---

File 207 **l warp-leftidx.sty**

§ 307 Package **leftidx**

(Emulates or patches code by HARALD HARDERS.)

Pkg **leftidx** **leftidx** works as-is with SVG math, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{leftidx}[2003/09/24]

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\leftidx}[3]{\vphantom{#2}\smash{\overset{#1}{#2}}{#3}}}
4 \CustomizeMathJax{\newcommand{\ltrans}[1]{\leftidx{^{\mathrm{t}}}{#1}{}}}}
5 \end{warpMathJax}
```

---

File 208 **l warp-letterspace.sty**

§ 308 Package **letterspace**

(Emulates or patches code by R SCHLICHT.)

Pkg **letterspace** **letterspace** is a subset of microtype, which is pre-loaded by **l warp**. All user options and macros are ignored and disabled.

**for HTML output:** Discard all options for **l warp-letterspace**:

```
1 \LWR@ProvidesPackageDrop{letterspace}[2018/01/14]
2 \newcommand*\lsstyle{}
3 \newcommand\textrls[2][]{}
4 \def\textrls#1{}
5 \newcommand*\lslig[1]{#1}
```

---

File 209 **l warp-lettrine.sty**

§ 309 Package **lettrine**

(Emulates or patches code by DANIEL FLIPO.)

Pkg **lettrine** **lettrine** is emulated.

**for HTML output:** Discard all options for **l warp-lettrine**:

```
1 \LWR@ProvidesPackageDrop{lettrine}[2018-08-28]
```

The initial letter is in a <span> of class `letrine`, and the following text is in a <span> of class `letrinetext`. `\letrine[<keys>]{<letter>}{<additional text>}`

```

2 \DeclareDocumentCommand{\letrine}{o m m}{%
3 \InlineClass{letrine}{#2}\InlineClass{letrinetext}{#3} % extra space
4 }
5
6 \newcounter{DefaultLines}
7 \setcounter{DefaultLines}{2}
8 \newcounter{DefaultDepth}
9 \newcommand*{\DefaultOptionsFile}{\relax}
10 \newcommand*{\DefaultLoversize}{0}
11 \newcommand*{\DefaultLraise}{0}
12 \newcommand*{\DefaultLhang}{0}
13 \newdimen\DefaultFindent
14 \setlength{\DefaultFindent}{\z@}
15 \newdimen\DefaultNindent
16 \setlength{\DefaultNindent}{0.5em}
17 \newdimen\DefaultSlope
18 \setlength{\DefaultSlope}{\z@}
19 \newdimen\DiscardVskip
20 \setlength{\DiscardVskip}{0.2\p@}
21 \newif\ifLetrineImage
22 \newif\ifLetrineOnGrid
23 \newif\ifLetrineRealHeight
24
25 \newcommand*{\LetrineTextFont}{\scshape}
26 \newcommand*{\LetrineFontHook}{}
27 \newcommand*{\LetrineFont}[1]{\InlineClass{letrine}{#1}}
28 \newcommand*{\LetrineFontEPS}[1]{\includegraphics[height=1.5ex]{#1}}

```

### File 210 l warp-lineno.sty

§ 310 Package **lineno**

(Emulates or patches code by STEPHAN I. BÖTTCHER.)

Pkg **lineno** **lineno** is partly emulated, but mostly ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{lineno}[2005/11/02]

```

2 \newcommand*\resetlinenumber[1][\@ne]{}
3
4 \def\linenumbers{%
5   \@ifnextchar[\{\resetlinenumber\}%
6     {\@ifstar{\resetlinenumber}{}}\}%
7 }
8
9 \newcommand*{\nolinenumbers}{}
10
11 \namedef{linenumbers*}{\par\linenumbers*}
12 \namedef{runninglinenumbers*}{\par\runninglinenumbers*}
13

```

```
14 \def\endlinenumbers{\par}
15 \let\endrunninglinenumbers\endlinenumbers
16 \let\endpagewiselinenumbers\endlinenumbers
17 \expandafter\let\csname endlinenumbers*\endcsname\endlinenumbers
18 \expandafter\let\csname endrunninglinenumbers*\endcsname\endlinenumbers
19 \let\endnolinenumbers\endlinenumbers
20
21 \def\pagewiselinenumbers{\linenumbers\setpagewiselinenumbers}
22
23 \def\runninglinenumbers{\setrunninglinenumbers\linenumbers}
24
25 \def\setpagewiselinenumbers{}
26
27 \def\setrunninglinenumbers{}
28
29 \def\linenomath{}%
30 \namedef{linenomath*}{}%
31 \def\endlinenomath{}
32 \expandafter\let\csname endlinenomath*\endcsname\endlinenomath
33
34 \let\linelabel\label
35
36 \def\switchlinenumbers{@ifstar{}{}}
37 \def\setmakelinenumbers#1{@ifstar{}{}}
38
39 \def\leftlinenumbers{@ifstar{}{}}
40 \def\rightlinenumbers{@ifstar{}{}}
41
42 \newcounter{linenumber}
43 \newcount\c@pagewiselinumber
44 \let\c@runninglinenumber\c@linenumber
45
46 \def\runningpagewiselinenumbers{}
47 \def\realpagewiselinenumbers{}
48
49
50 \NewDocumentCommand\modulolinenumbers{s o}{}
51
52 \chardef\c@linenumbermodulo=5
53 \modulolinenumbers[1]
54
55 \newcommand*\firstlinenumber[1]{}
56
57 \newcommand\internallinenumbers{}
58 \let\endinternallinenumbers\endlinenumbers
59 \namedef{internallinenumbers*}{\internallinenumbers*}
60 \expandafter\let\csname endinternallinenumbers*\endcsname\endlinenumbers
61
62 \newcommand*{\linenoplacement}[1]{% redefine per language
63   (line number reference for \detokenize\expandafter{\#1})
64 }
65
66 \newcommand*{\lineref}[2][]{\linenoplacement{\#2}}
67 \newcommand*{\linerefpl}[2][]{\linenoplacement{\#2}}
68 \newcommand*{\linerefpr}[2][]{\linenoplacement{\#2}}
```

```
69
70 \newcommand\quotelinenumbers
71   {\@ifstar\linenumbers{\@ifnextchar[\linenumbers{\linenumbers*}}}
72
73 \newdimen\linenumbersep
74 \newdimen\linenumberwidth
75 \newdimen\quotelinumbersep
76
77 \quotelinumbersep=\linenumbersep
78 \let\quotelinumberfont\linenumberfont
79
80 \def\linenumberfont{\normalfont\tiny\sffamily}
81
82
83 \linenumberwidth=10pt
84 \linenumbersep=10pt
85
86 \def\thelinenumber{}
87
88 \def\LineNumber{}
89 \def\makeLineNumber{}
90 \def\makeLineNumberLeft{}
91 \def\makeLineNumberRight{}
92 \def\makeLineNumberOdd{}
93 \def\makeLineNumberEven{}
94 \def\makeLineNumberRunning{}
95
96
97 \newenvironment{numquote}    {\quote}{\endquote}
98 \newenvironment{numquotation} {\quotation}{\endquotation}
99 \newenvironment{numquote*}   {\quote}{\endquote}
100 \newenvironment{numquotation*}{\quotation}{\endquotation}
101
102 \newdimen\bframerule
103 \bframerule=\fboxrule
104
105 \newdimen\bframesep
106 \bframesep=\fboxsep
107
108 \newenvironment{bframe}
109 {%
110   \LWR@forceminwidth{\bframerule}%
111   \BlockClass[
112     border:\LWR@printlength{\LWR@atleastonept} solid black ; %
113     padding:\LWR@printlength{\bframesep}%
114   ]{bframe}
115 }
116 {\endBlockClass}
```

---

**File 211 l warp-lips.sty**

§ 311 Package **lips**

(Emulates or patches code by MATT SWIFT.)

Pkg lips lips is emulated.

```
1 \% \LWR@ProvidesPackageDrop{lips}
2 \PackageInfo{l warp}{Using the l warp version of package 'lips'.}%
3 \ProvidesPackage{l warp-lips}[2001/08/31]
4
5 \NewDocumentCommand{\Lips}{}{\textellipsis}
6
7 \NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}
8
9 \let\lips\Lips
10 \let\olips\lips
11
12 \DeclareOption*{}
13 \DeclareOption{mla}{%
14 \let\lips\BracketedLips
15 }
16 \ProcessOptions\relax
17
18 \newcommand \LPNobreakList {}
```

---

**File 212 l warp-listings.sty**

§ 312 Package **listings**

(Emulates or patches code by CARSTEN HEINZ, BROOKS MOSES, JOBST HOFFMANN.)

Pkg listings listings is supported with some limitations. Text formatting is not yet supported.

**for HTML output:** 1 \begin{warpHTML}

2 \LWR@ProvidesPackagePass{listings}[2018/09/02]

Force flexible columns. Fixed columns inserts spaces in the PDF output.

3 \lst@column@flexible

Patches to embed listings inside pre tags:

```
4 \let\LWR@origlst@Init\lst@Init
5 \let\LWR@origlst@DeInit\lst@DeInit
```

```

6
7 \let\LWR@origlstkEveryPar\lstk@EveryPar
8
9 \renewcommand{\l@lstlisting}[2]{\hypertocfloat{1}{lstlisting}{lol}{#1}{#2}}

```

\lstset {*options*}

Use the `listings` literate option to replace HTML entities:

```

10 \def\lstset#1{\endgroup%
11 %  \ifx\@empty#1%
12 %    \@\empty%
13 %  \else%
14    \setkeys{lst}{%
15      #1%
16      ,literate=%
17      {<}{\HTMLentity{lt}}{4}%
18      {>}{\HTMLentity{gt}}{4}%
19      {&}{\HTMLentity{amp}}{5}%
20    }%
21 %  \fi%
22 }

```

\lst@Init {*backslash-processing*} Done at the start of a listing.

```
23 \renewcommand{\lst@Init}[1]{%
```

Perform the `listings` initialization:

```

24 \LWR@traceinfo{lst@Init}%
25 \renewcommand*{\@capttype}{lstlisting}%
26 \let\lst@aboveskip\z@\let\lst@belowskip\z@%
27 \gdef\lst@boxpos{t}%
28 \let\lst@frame\@empty
29   \let\lst@frametshape\@empty
30   \let\lst@framershape\@empty
31   \let\lst@framebshape\@empty
32   \let\lst@framelshape\@empty
33 \lstframe@\lst@frameround ffff\relax%
34 \lst@multicols\@empty%
35 \LWR@origlst@Init{#1}\relax%

```

Avoids extra horizontal space:

```

36 \def\lst@framelr{}%
37 \LWR@traceinfo{finished origlst@Init}%
38 \lst@ifdisplaystyle%

```

Creating a display.

Disable line numbers, produce the `<pre>`, then reenable line numbers.

```

39 \LWR@traceinfo{About to create verbatim.}%
40 \let\lstk@EveryPar\relax%
41 \LWR@forcenewpage
42 \LWR@atbeginverbatim{2}{programlisting}%
43

```

```
44 \let\lst@EveryPar\LWR@origlst@EveryPar%
45 \else%
```

Inline, so open a <span>:

```
46 \ifbool{\LWR@verbtags}{\LWR@htmltag{span class="inlineprogramlisting"}{}}%
47 \fi%
48 }%
49
```

\lst@DeInit     Done at the end of a listing.

```
50 \renewcommand*\lst@DeInit{%
51 \lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```
52 \let\lst@EveryPar\relax%
53 \LWR@afterendverbatim{0}%
54 \let\lst@EveryPar\LWR@origlst@EveryPar%
55 \else%
```

Inline, so create the closing </span>:

```
56 \ifbool{\LWR@verbtags}{\noindent\LWR@htmltag{/span}}{}%
57 \fi%
```

Final listings deinit:

```
58 \LWR@origlst@DeInit%
59 }
```

\lst@MakeCaption     {*t/b*}

This is called BOTH at the top and at the bottom of each listing.

Patched for lwarp.

```
60 \def\lst@MakeCaption#1{%
61 \LWR@traceinfo{MAKING CAPTION at #1}%
62 \lst@ifdisplaystyle
63 \LWR@traceinfo{making a listings display caption}%
64 \ifx #1t%
65 \ifx\lst@caption\empty\expandafter\lst@HRefStepCounter \else
66 \expandafter\refstepcounter
67 \fi {\lstlisting}%
68 \LWR@traceinfo{About to assign label: !\lst@label!}%
69 % \ifx\lst@label\empty\else
70 % \label{\lst@label}\fi
71 \LWR@traceinfo{Finished assigning the label.}%
72 \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
73 \global\let\lst@name\lst@arg \global\let\lst@name\lst@name
74 \lst@ifnolol\else
75 \ifx\lst@caption\empty
76 \ifx\lst@caption\empty
77 \ifx\lst@intname\empty \else \def\lst@temp{ }%
78 \ifx\lst@intname\lst@temp \else
```

This code places a contents entry for a non-float. This would have to be modified for `lwarp`:

```
79 \LWR@traceinfo{addcontents lst@name: -\lst@name-}%
80 %                               \addcontentsline{lol}{lstlisting}{\lst@name}
81         \fi\fi
82         \fi
83     \else
```

This would have to be modified for `lwarp`:

```
84 \LWR@traceinfo{addcontents lst@caption: -\lst@caption-}%
85 %                               \addcontentsline{lol}{lstlisting}%
86 {\protect\numberline{\thelstlisting}%
87 {\protect\ignorespaces \LWR@isolate{\lst@caption} \protect\relax}%
88         \fi
89         \fi
90         \fi
91     \ifx\lst@caption\empty\else
92 \LWR@traceinfo{lst@caption not empty-}%
93     \lst@ifSubstring #1\lst@captionpos
94     {\begingroup
95 \LWR@traceinfo{at the selected position}%
```

These space and box commands are not needed for HTML output:

```
96 %           \let\@vskip\vskip
97 %           \def\vskip{\afterassignment\lst@vskip \tempskipa}%
98 %           \def\lst@vskip{\nobreak\@vskip\tempskipa\nobreak}%
99 %           \par\@parboxrestore\normalsize\normalfont \% \noindent (AS)
100 %           \ifx #1\allowbreak \fi
101           \ifx\lst@title\empty
```

New `lwarp` code to create a caption:

```
102           \LWR@stopars%
103           \lst@makecaption\fnum@lstlisting{\ignorespaces \lst@caption}%
104       \else
```

New `lwarp` code to create a title:

```
105 %           \lst@maketitle\lst@title \% (AS)
106 \LWR@traceinfo{Making title: \lst@title}%
107 \begin{BlockClass}{lstlistingtitle}\% lwarp
108 \lst@maketitle\lst@title\% lwarp
109 \end{BlockClass}\% lwarp
110         \fi
111 \LWR@traceinfo{About to assign label: !\lst@label!}%
112     \ifx\lst@label\empty\else
113 \leavevmode% gets rid of bad space factor error
114 \GetTitleStringExpand{\lst@caption}%
115 \edef\LWR@lntemp{\GetTitleStringResult}%
116 \edef@\currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
117 \label{\lst@label}\fi
118 \LWR@traceinfo{Finished assigning the label.}%
```

Not needed for `lwarp`:

```
119 %           \ifx #1b\allowbreak \fi
120           \endgroup\}{}%
```

```

121     \fi
122 \LWR@traceinfo{end of making a listings display caption}%
123 \else
124 \LWR@traceinfo{INLINE}%
125 \fi
126 \LWR@traceinfo{DONE WITH CAPTION at #1}%
127 }

```

**line numbers** Patched to keep left line numbers outside of the left margin, and place right line numbers in a field \VerbatimHTMLWidth wide.

```

128 \lst@Key{numbers}{none}{%
129     \let\lst@PlaceNumber\empty
130     \lstKV@SwitchCases{#1}%
131     {none:\%
132      left:\def\lst@PlaceNumber{%

```

For now, **lwarp** places left line numbers inline. Ideally the entire line would be moved to the right, but conflicts with list indenting occurs.

```

133 %          \LWR@origllap{%
134             \LWR@orignormalfont%
135             \lst@numberstyle{\thelstnumber}\kern\lst@numbersep%
136 %          }
137 }\\%
138     right:\def\lst@PlaceNumber{\LWR@origllap{\LWR@orignormalfont
139             \kern 6in \kern\lst@numbersep
140             \lst@numberstyle{\thelstnumber}}}%
141 }{\PackageError{lwarp-listings}{Numbers #1 unknown}@ehc}}
142 \end{warpHTML}

```

### File 213 **lwarp-listliketab.sty**

#### § 313 Package **listliketab**

Pkg **listliketab** **listliketab** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{listliketab}[2005/01/09]

```

2 \newcommand*\storestyleof}[1]{}%
3 \newcommand*\storeliststyle}{}%
4 \newenvironment{listliketab}{}{%

```

### File 214 **lwarp-lltjext.sty**

#### § 314 Package **lltjext**

(Emulates or patches code by THE LUATEX-JA PROJECT TEAM.)

Pkg lltjext lltjext is patched for use by l warp.

for HTML output 1 \LWR@ProvidesPackagePass{lltjext}[2018/10/07]

```

2 \protected\def\yoko{%
3   \directlua{luatexja.direction.set_list_direction(4, 'yoko')}%
4 }
5 \protected\def\tate{\yoko}
6 \protected\def\dtou{\yoko}
7 \protected\def\utod{\yoko}
8
9 \define@key[ltj]{japaram}{direction}{}%
10
11 \yoko
12
13 \DeclareExpandableDocumentCommand{\rensushi}{s o m}{#3}%
14
15 \DeclareDocumentCommand{\layoutfloat}{d() o m}{}%
16
17 \DeclareDocumentCommand{\DeclareLayoutCaption}{m d> d() o}{}%
18
19 \LetLtxMacro\pcaption\caption
20
21 \DeclareDocumentCommand{\layoutcaption}{d> d() o}{}%
22
23 \let\captiondir\relax
24 \RenewDocumentEnvironment{\LWR@HTML@minipage}{d> O{t} O{} O{t} m}%
25   {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}%
26   {\endLWR@HTML@sub@minipage}%
27
28 \RenewDocumentCommand{\LWR@HTML@parbox}{d> O{t} O{} O{t} m +m}%
29 {
30 \LWR@traceinfo{parbox of width #4}%
31 \begin{minipage}[#2][#3][#4]{#5}%
32 #6
33 \end{minipage}%
34 }
35
36 \RenewDocumentCommand{\pbox}{d> O{0pt} O{c} m}{%
37 \global\booltrue{\LWR@minipagefullwidth}%
38 \parbox{#2}{#4}}%
39 }
```

### File 215 l warp-longtable.sty

§ 315 Package **longtable**

(Emulates or patches code by DAVID CARLISLE.)

Pkg longtable longtable is emulated.

for HTML output 1 \LWR@ProvidesPackageDrop{longtable}[2014/10/28]

Use one of either `\endhead` or `\endfirsthead` for both print and HTML, and use a `\warpprintonly` macro to disable the other head phrase, and also the `\endfoot` and `\endfirstfoot` phrases. (See section 8.10.4 if using `threeparttablex`.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead    % or \endhead, for print and HTML
\warpprintonly{           % not used in HTML
[ . . . ] \endhead      % or \endfirsthead
[ . . . ] \endfoot
[ <lastfoot macros> ] \endlastfoot
}
... table contents ...
\warpHTMLonly{
[ <lastfoot macros> ]   % HTML last footer, without \endfoot
% or \endlastfoot.
}
\end{longtable}
```

⚠ **Misplaced `\noalign`** Use the `\warpprintonly` macro instead of the `warpprint` environment. Doing so helps avoid “Misplaced `\noalign`.” when using `\begin{warpprint}`.

⚠ **`\kill`** `\kill` is ignored, place a `\kill` line inside

```
\begin{warpprint} . . . \end{warpprint}
```

or place it inside `\warpprintonly`.

⚠ **`lateximage` `longtable`** `longtable` is not supported inside a `lateximage`.

See:

<http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable>

Used to detect more than one of `\endhead` and `\endfirsthead` in use for HTML at the same time.

```
2 \newbool{LWR@longtable@havehead}
3 \boolfalse{LWR@longtable@havehead}
```

**Env `longtable`** \* [*<horizontalignment>*] {*<colspec>*} Emulates the `longtable` environment.

Per the `caption` package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options [c], [l], and [r] are ignored.

```
4 \newenvironment{longtable*}[2][]{
5   \LWR@floatbegin{table}%
6   \setcaptiontype{\LTcotype}%
7   \caption@setoptions{longtable}%
8   \caption@setoptions{@longtable}%
9   \caption@LT@setup%
10  \booltrue{LWR@starredlongtable}%
11  \boolfalse{LWR@longtable@havehead}%
}
```

```

12   \let\captionlistentry\LWR@LTcaptionlistentry%
13   \tabular{#2}%
14 }
15 {\endtabular\LWR@floatend}
16
17 \newenvironment{longtable}[2][]{%
18   \LWR@floatbegin{table}%
19   \setcaptiontype{\LTcaptype}%
20   \caption@setoptions{longtable}%
21   \caption@setoptions{@longtable}%
22   \caption@LT@setup%
23   \refstepcounter{\LTcaptype}%
24   \boolfalse{\LWR@longtable@havehead}%
25   \let\captionlistentry\LWR@LTcaptionlistentry%
26   \tabular{#2}%
27 }
28 {\endtabular\LWR@floatend}

```

Provided for compatibility, but ignored:

```
29 \newcounter{LTchunksize}
```

Error for heads which should have been in \warpprintonly:

```

30 \newcommand*{\LWR@longtable@headerror}{%
31   \PackageError{lwarp}%
32   {For longtable:\MessageBreak
33    1: Keep either one of an \protect\endhead\space or
34      \protect\endfirsthead\space\MessageBreak
35      \space phrase as-is, to be used by both print and HTML.\MessageBreak
36    2: Place any other \protect\end... phrases inside a\MessageBreak
37      \space\protect\warpprintonly\space macro,
38      to be ignored by HTML.\MessageBreak
39    3: Add a final footer for HTML at the end of the table\MessageBreak
40      \space inside a \protect\warpHTMLonly\space macro.
41      This can be\MessageBreak
42      \space a copy of an \protect\endfoot\space or
43      \protect\endfirstfoot\space phrase,\MessageBreak
44      \space but without the actual \protect\endfoot\space
45      or \protect\endfirstfoot\MessageBreak
46      \space macros. If using threeparttable, add\MessageBreak
47      \space \protect\insertTableNotes\space here,
48      optionally with\MessageBreak
49      \space \protect\UseMinipageWidths\space in front.\MessageBreak
50   See the Lwarp documentation regarding longtables\MessageBreak
51   and threeparttablex}%
52   {See the Lwarp documentation regarding longtables and threeparttablex.}%
53 }

```

Error if more than one of \endhead or \endfirsthead is outside \warpprintonly.

```

54 \newcommand*{\LWR@longtable@maybeheaderror}{%
55 \ifbool{\LWR@longtable@havehead}%
56   {\LWR@longtable@headerror}%

```

```

57      {%
58          \booltrue{\LWR@longtable@havehead}
59          \LWR@tabularendofline% throws away options // [dim] and //*
60      }%
61 }

Error if more than one of these is outside of warpprint.

62 \def\endhead{\LWR@longtable@maybeheadererror}
63 \def\endfirsthead{\LWR@longtable@maybeheadererror}

Error if ANY of these is outside of warpprint.

64 \def\endfoot{\LWR@longtable@headererror}
65 \def\endlastfoot{\LWR@longtable@headererror}

66 \providecommand*\LWR@HTML@tabularnewline{\LWR@tabularendofline}
67 \LWR@formatted{tabularnewline}

68 \newcommand{\setlongtables}{}% Obsolete command, does nothing.
69 \newlength{\LTleft}
70 \newlength{\LTright}
71 \newlength{\LTpre}
72 \newlength{\LTpost}
73 \newlength{\LTcapwidth}

74 \LetLtxMacro{\LWR@origkill}{\kill}
75 \renewcommand*\kill{\LWR@tabularendofline}
76 \appto{\LWR@restoreorigformatting}{%
77 \LetLtxMacro{\kill}{\LWR@origkill}}
78 }

```

File 216 **l warp-lscape.sty**

§ 316 Package **lscape**

(Emulates or patches code by D. P. CARLISLE.)

Pkg **lscape** **lscape** is ignored.

**for HTML output:** Discard all options for **l warp-lscape**.

```

1 \LWR@ProvidesPackageDrop{lscape}[2000/10/22]
2 \newenvironment*{landscape}{}{}

```

---

**File 217 l warp-l tablex.sty****§ 317 Package l tablex**

(Emulates or patches code by ANIL K. GOEL.)

Pkg l tablex l tablex is emulated by l warp.

for HTML output Relies on tabularx.

```
1 \RequirePackage{longtable}
2 \RequirePackage{tabularx}
3
4 \LWR@ProvidesPackageDrop{l tablex}[2014/08/13]
5
6 \DeclareDocumentEnvironment{tabularx}{m o m}
7 {\longtable[#3]}
8 {\endlongtable}
9
10 \DeclareDocumentEnvironment{tabularx*}{m o m}
11 {\longtable[#3]}
12 {\endlongtable}
13
14 \newcommand*{\keepXColumns} {}
15 \newcommand*{\convertXColumns} {}
```

---

**File 218 l warp-l t caption.sty****§ 318 Package l t caption**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg l t caption l t caption is ignored.

for HTML output 1 \LWR@ProvidesPackageDrop{l t caption}[2018/08/26]

\LTcaptype is already defined by l warp.

longtable\* is already defined by l warp-longtable.

```
2 \newlength{\LTcapskip}
3 \newlength{\LTcapleft}
4 \newlength{\LTcapright}
5 \newcommand*{\LTcapmarginsfalse} {}
```

---

File 219 **l warp-ltxgrid.sty**

§ 319 Package **ltxgrid**

Pkg ltxgrid ltxgrid is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{ltxgrid}[2010/07/25]

```
2 \newcommand*\{\\onecolumngrid}{}
3 \newcommand*\{\\twocolumngrid}{}
4 \newcommand*\{\\removestuff}{}
5 \newcommand*\{\\addstuff}[2]{}
6 \newcommand*\{\\replacestuff}[2]{}
```

---

File 220 **l warp-ltxtable.sty**

§ 320 Package **ltxtable**

Pkg ltxtable ltxtable is emulated.

⚠ **table numbering** The print version does not seem to honor `longtable*` from the `caption` package, while l warp does.

**for HTML output:** 1 \RequirePackage{tabularx, longtable}
2 \LWR@ProvidesPackageDrop{ltxtable}[1995/12/11]

```
\LTXtable {\langle width\rangle} {\langle file\rangle}
3 \newcommand*\{\\LTXtable}[2]{%
4   \input{\#2}%
5 }
```

---

File 221 **l warp-lua-check-hyphen.sty**

§ 321 Package **lua-check-hyphen**

Pkg lua-check-hyphen lua-check-hyphen is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{lua-check-hyphen}[2018/04/19]
2 \newcommand\*\{\\LuaCheckHyphen}[1]{}

---

File 222 **lwarf-lua-visual-debug.sty**

§ 322 Package **lua-visual-debug**

Pkg lua-visual-debug lua-visual-debug is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{lua-visual-debug}[2016/05/30]

---

File 223 **lwarf-luacolor.sty**

§ 323 Package **luacolor**

Pkg luacolor luacolor is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{luacolor}[2016/05/16]

2 \newcommand{\luacolorProcessBox}[1]{}  

---

File 224 **lwarf-luatodonotes.sty**

§ 324 Package **luatodonotes**

(Emulates or patches code by FABIAN LIPP.)

Pkg luatodonotes luatodonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

**for HTML output:** 1 \LWR@ProvidesPackagePass{luatodonotes}[2017/09/30]

Nullify options:

2 \todonotes@additionalMarginEnabledfalse  
3 \if@todonotes@disabled  
4 \else  
5  
6 \newcommand{\ext@todo}{\text{tdo}}  
7  
8 \renewcommand{\l@todo}[2]{\hypertocfloat{1}{\text{todo}}{\l@odo}{#1}{#2}}

```
9 \let\LWRTODONOTES@orig@todototoc\todototoc
10
11 \renewcommand*{\todototoc}{%
12 \phantomsection%
13 \LWRTODONOTES@orig@todototoc%
14 }
15
16
17 \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
18 \fcolorbox{%
19     {\@todonotes@currentbordercolor}%
20     {\@todonotes@currentbackgroundcolor}%
21     {\arabic{@todonotes@numberoftodonotes}}%
22 }{\@todonotes@drawMarginNote}%
23 }
24
25 \renewcommand{\@todonotes@drawInlineNote}{%
26 \fcolorboxBlock{%
27     {\@todonotes@currentbordercolor}%
28     {\@todonotes@currentbackgroundcolor}%
29     {%
30         \if@todonotes@authorgiven%
31             {\@todonotes@author:\,}%
32         \fi%
33         \@todonotes@text%
34     }%
35 }
36
37 \newcommand{\@todonotes@drawMarginNote}{%
38     \if@todonotes@authorgiven%
39         \@todonotes@author\par%
40     \fi%
41     \arabic{@todonotes@numberoftodonotes}: %
42     \fcolorbox{%
43         {\@todonotes@currentbordercolor}%
44         {\@todonotes@currentbackgroundcolor}%
45         {%
46             \@todonotes@sizecommand%
47             \@todonotes@text %
48         }%
49 }%
50
51 \renewcommand{\missingfigure}[2][]{%
52 \setkeys{todonotes}{#1}%
53 \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
54 \fcolorboxBlock{%
55     {\@todonotes@currentbordercolor}%
56     {\@todonotes@currentfigcolor}%
57     {%
58         \setlength{\fboxrule}{4pt}%
59         \fcolorbox{red}{white}{Missing figure} \quad #2%
60     }%
61 }
62
63 \LetLtxMacro{\LWRTODONOTES@orig@todocommon}{\todocommon}
```

```

64
65 \RenewDocumentCommand{\@todocommon}{m m}{%
66 \begingroup%
67 \renewcommand*{\phantomsection}{}%
68 \LWRTODONOTES@orig@todocommon{#1}{#2}%
69 \endgroup%
70 }
71
72 \renewcommand{\todoarea}[3][]{%
73   \todonotes@areaselectedtrue%
74   \todocommon{#1}{#2}%
75   \todonotes@textmark@highlight{#3}%
76   \zref@label{\todonotes@arabic{\todonotes@numberoftodonotes}@end}%
77 }%
78
79
80 \DeclareDocumentCommand{\todonotes@textmark@highlight}{m}{%
81 \InlineClass[background:\LWR@origpound{}B3FFB3]{highlight}{#1}%
82 }
83
84 \fi% \if@todonotes@disabled

```

---

#### File 225 **l warp-lyluatex.sty**

§ 325      Package **lyluatex**

(Emulates or patches code by FR. JACQUES PERON, URS Liska, BR. SAMUEL SPRINGUEL.)

Pkg **lyluatex** **lyluatex** is patched for use by **l warp**.

For the first compile, to set *l warpmk*'s configuration, use:

```
lualatex --shell-escape <filename>
```

⚠ **images** After compiling the document with **l warpmk html**, use **l warpmk l images** to convert the Lilypond images for HTML.

**css** The option `insert=systems` results in an image per system. Each music image “system” is placed inside a `<span>` of class **lyluatex**, which defaults to `display: inline-block`.

⚠ **insert=fullpage** The option `insert=fullpage` results in a single image per page of printed output.  
**css** Each music “fullpage” image is placed inside a `<div>` of class **lyluatex**. To match the number of measures per line with the printed version, use the **geometry** package to select the page geometry, or use the **lyluatex** options for page and staff sizes.

⚠ **options** To use `\linewidth` or `\textwidth` inside the package options for **lyluatex**, use the **kvoptions-patch** package first:

```
\usepackage{kvoptions-patch}
\usepackage[...,\line-width-0.8\linewidth,...]{lyluatex}
```

⚠ **raw-pdf** If using **raw-pdf**, the resulting PDF images must be converted to SVG:

---

Enter ⇒ **lwarpmk pdftosvg tmp-ly/\*.pdf**

**for HTML output:**

```

1 \LWR@origRequirePackage{luacode}
2
3 \LWR@ProvidesPackagePass{lyluatex}[2019/05/27]
```

User-redefinable ALT tag:

```
4 \newcommand*{\LyluatexImageAltText}{-lilypond-\PackageDiagramAltText}
```

```
\ly@compilescore {⟨Lilypond object⟩}
5 \LetLtxMacro{\LWR@orig@ly@compilescore}{\ly@compilescore}
6
7 \renewcommand*{\ly@compilescore}[1]{%
```

A local group holds a number of changes:

```
8 \begingroup%
```

The user's original geometry and font size are restored to match the print version. This allows for correct spacing in the musical score.

```

9 \LWR@orignewpage%
10 \LWR@origloadgeometry{\LWR@usergeometry}%
11 \LWR@print@normalsize%
```

A local group holds a redefined `\includegraphics` which is used by *lyluatex.lua* to insert the *Lilypond* score if `insert=systems` is used. This is now placed inside a `lateximage`, which itself is placed inside a `<span>` of class *lyluatex*.

`\LWR@addbaselinemarker` preserves the left margins.

```

12 \renewcommand{\includegraphics}[2][]{%
13   \InLineClass{lyluatex}{%
14     \begin{lateximage}[\LyluatexImageAltText]%
15     \LWR@addbaselinemarker%
16     \LWR@origincludegraphics{##2}%
17     \end{lateximage}%
18   }%
19 }%
```

From the original:

```

20 \ly@setunits%
21 \directlua{
22   ly_opts:set_option('currfiledir', [[\currfiledir]])
23   ly_opts:set_option('twoside', '\ly@istwosided')
24   #1
25 }%
26 \ly@resetunits%
27 \ly@currentfonts%
```

The fullpage version is set inside an HTML `<div>`:

```

28 \directlua{
29   if (ly.score.insert == 'fullpage') then
30     tex.print{[[\string\begin{BlockClass}{lyluatex}]]}
31   end
32 }%
```

Generate the score:

```
33 \directlua{ly.score:process()}%
```

Close the <div>:

```
34 \directlua{
35     if (ly.score.insert == 'fullpage') then
36         tex.print{[[\string\end{BlockClass}]]}
37     end
38 }%
```

Move to a new page and renew the regular page geometry:

```
39 \LWR@orignewpage%
40 \LWR@origrestoregeometry%
```

End of the local group.

```
41 \endgroup%
42 }
```

In HTML the following generates an error, so is removed:

```
43 \xpatchcmd{\endly@bufferenv}
44     {\hspace{0pt}\\"}
45     {}
46     {}
47     {\LWR@patcherror{lyluatex}{endly@bufferenv}}
```

#### File 226 **lwarp-magaz.sty**

#### § 326 Package **magaz**

Pkg magaz magaz is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{magaz}[2011/11/24]

```
2 \newcommand\FirstLine[1]{%
3     \begingroup%
4     \FirstLineFont{%
5         \LWR@textcolor{%
6             \LWR@textfont{%
7                 #1%
8             }%
9         }%
10    }%
11    \endgroup%
12 }
13
14 \providecommand\FirstLineFont{\scshape}
```

---

**File 227 l warp-makeidx.sty****§ 327 Package makeidx**

(Emulates or patches code by LATEX PROJECT TEAM.)

Pkg makeidx makeidx is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{makeidx}[2014/09/29]

\@wrindex is redefined \AtBeginDocument by the l warp core.

\printindex

```
2 \preto\printindex{%
3   \LWR@orignewpage%
4   \LWR@startpars%
5 }
```

---

**File 228 l warp-manyfoot.sty****§ 328 Package manyfoot**

Pkg manyfoot manyfoot is emulated.

**bigfoot, manyfoot** Verbatim footnotes are not yet supported.



If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because l warp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLATEX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XELATEX or LuaLATEX instead of pdfLATEX.

l warp's emulation of bigfoot uses manyfoot, so some of the bigfoot enhancements are included here.

The bigfoot “default” footnote is ignored, using the l warp version instead.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{manyfoot}[2005/09/11]

```
2 \RequirePackage{nccfoots}
```

```

3
4 \newcommand{\extrafootnoterule}{}%
5
6 \let\defaultfootnoterule\footnoterule
7
8 \newcommand*\SelectFootnoteRule[2][0]{}%
9
10 \newcommand{\footnoterulepriority}{1}
11
12 \newcommand{\SetFootnoteHook}[1]{}
13 @onlypreamble\SetFootnoteHook
14
15 \newcommand{\SplitNote}{}%
16
17 \newcommand*\ExtraParaSkip[1]{}%
18
19 \newcommand*\newfootnote[2][plain]{}%
20     \ifstreq{\#2}{default}{}{%
21         \expandafter\newbox\csname LWR@footnote#2box\endcsname%
22         \appto{\LWR@printpendingfootnotes}{%
23             \LWR@printpendingfootnotes{footnote#2}%
24         }%
25         \long\csdef{Footnotetext#2}##1##2{%
26             \NCC@makefnmark{##1}%
27             \LWR@@footnotetext{##2}{LWR@footnote#2box}%
28         }%
29         \long\csdef{Footnotetext#2+}##1##2{%
30             \NCC@makefnmark{##1}%
31             \LWR@@footnotetext{##2}{LWR@footnote#2box}%
32         }%
33     }% not "default"
34 }
35 @onlypreamble\newfootnote
36
37 \newcommand*\DeclareNewFootnote[2][plain]{}%
38     \@ifnextchar[%
39         {\LWR@manyfoot@declare{\#1}{\#2}}%
40         {\LWR@manyfoot@declare{\#1}{\#2}[arabic]}%
41 }
42
43 \def\LWR@manyfoot@declare#1#2[#3]{}%
44 \ifstreq{\#2}{default}{}{%
45     \newfootnote[\#1]{\#2}%
46     \newcounter{footnote#2}%
47     \newcounter{footnote#2Reset}%
48     \setcounter{footnote#2Reset}{0}%
49     \csdef{thefootnote#2}{%
50         \expandafter\noexpand\csname @#3\endcsname%
51         \expandafter\noexpand\csname c@footnote#2\endcsname%
52     }%

```

For **bigfoot**, the footnote commands may be appended with one or two plusses or one or two minuses, which are ignored in HTML.

```
53     \expandafter\NewDocumentCommand\csname footnote#2\endcsname{t{+}t{+}t{-}t{-}}{%
```

---

```

54      \stepcounter{footnote#2}%
55      \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
56      \@footnotemark%
57      \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
58  }%
59  \csdef{footnotemark#2}{%
60      \stepcounter{footnote#2}%
61      \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
62      \@footnotemark%
63  }%
64  \expandafter\NewDocumentCommand\csname footnotetext#2\endcsname{t{+}t{+}t{-}t{-}}{%
65      \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
66      \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
67  }%
68  \csdef{Footnotemark#2}{%
69      \Footnotemark%
70  }%
71  \csdef{Footnote#2}##1{%
72      \Footnotemark{##1}%
73      \csuse{Footnotetext#2}{##1}%
74  }%
75 }% not "default"
76 }
77 \onlypreamble\DeclareNewFootnote

```

---

File 229 **l warp-marginal.sty**

§ 329 Package **marginal**

Pkg marginal **marginal** is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{marginal}

2 \newcommand*{\showlostmarginals}{}%
3 \newcommand*{\enlargefreelist}{}%
4 \newcommand*{\onesidemarginals}{}%

```

---

File 230 **l warp-marginfit.sty**

§ 330 Package **marginfit**

Pkg marginfit **marginfit** is ignored.

**for HTML output:** Discard all options for **l warp-marginal**:

```

1 \LWR@ProvidesPackageDrop{marginfit}[2018/06/08]

```

---

**File 231 l warp-marginfix.sty****§ 331 Package marginfix**

(Emulates or patches code by STEPHEN HICKS.)

Pkg marginfix marginfix is ignored.

**for HTML output:** Discard all options for l warp-marginfix:

```
1 \LWR@ProvidesPackageDrop{marginfix}[2013/09/08]

2 \newcommand*{\marginskip}[1]{}
3 \newcommand*{\clearmargin}{}
4 \newcommand*{\softclearmargin}{}
5 \newcommand*{\extendmargin}[1]{}
6 \newcommand*{\mparshift}[1]{}
7 \newdimen\marginheightadjustment
8 \newdimen\marginposadjustment
9 \newcommand*{\blockmargin}[1][]{}
10 \newcommand*{\unblockmargin}[1][]{}
11 \newcommand*{\marginphantom}[2][]{}
```

---

**File 232 l warp-marginnote.sty****§ 332 Package marginnote**

(Emulates or patches code by MARKUS KOHM.)

Pkg marginnote marginnote is emulated.

**for HTML output:** Discard all options for l warp-marginnote:

```
1 \LWR@ProvidesPackageDrop{marginnote}[2018/08/09]

2 \NewDocumentCommand{\marginnote}{+o +m o}{\marginpar{#2}{}}

3 \newcommand*{\marginnotefleftadjust}{}
4 \newcommand*{\marginnoterightadjust}{}
5 \newcommand*{\marginnotetextwidth}{}
6 \let\marginnotetextwidth\textwidth
7 \newcommand*{\marginnotevadjust}{}
8 \newcommand*{\marginfont}{}
9 \newcommand*{\raggedleftmarginnote}{}
10 \newcommand*{\raggedrightmarginnote}{}
```

---

**File 233 l warp-marvosym.sty****§ 333 Package marvosym**

(Emulates or patches code by THOMAS HENLICH, MOJCA MIKLAVEC.)

Pkg marvosym marvosym is patched for use by l warp.

Hashed inline images are used, as there may not be Unicode support for all icons.

**for HTML output:** 1 \LWR@ProvidesPackagePass{marvosym}[2011/07/20]

```
2 \renewcommand{\mvchr}[1]{%
3   \begin{lateximage}*[symbol #1][marvosym #1]%
4     \mvs\char#1%
5   \end{lateximage}%
6 }
7
8 \renewcommand{\textmvs}[1]{%
9   \begin{lateximage}%
10   \mvs #1%
11   \end{lateximage}%
12 }
```

---

**File 234 l warp-mathcomp.sty****§ 334 Package mathcomp**

(Emulates or patches code by TILMANN BÖß.)

Pkg mathcomp mathcomp is supported as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mathcomp}[2001/01/07]

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\tcohm}{\mathrm{\Omega}}}
4 \CustomizeMathJax{\newcommand{\tcelsius}{\mathrm{\mathit{x2103}}}}
5 \CustomizeMathJax{\newcommand{\tcmu}{\mathrm{\mathit{x00B5}}}}
6 \CustomizeMathJax{\newcommand{\tcpertousand}{\mathrm{\mathit{x2030}}}}
7 \CustomizeMathJax{\newcommand{\tcpertenthousand}{\mathrm{\mathit{x2031}}}}
8 \CustomizeMathJax{\newcommand{\tcdegree}{\mathrm{\mathit{^\circ}}}}
9 \CustomizeMathJax{\newcommand{\tcdigitoldstyle}[1]{\oldstyle{#1}}}
10 \end{warpMathJax}
```

---

**File 235 l warp-mathdots.sty****§ 335 Package mathdots**

(Emulates or patches code by DAN LUECKING.)

Pkg mathdots mathdots is used as-is for SVG math, and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mathdots}[2014/06/11]

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\iddots}{\unicode{x22F0}}}
4 \end{warpMathJax}
```

---

**File 236 l warp-mathfixs.sty****§ 336 Package mathfixs**

(Emulates or patches code by NIKLAS BEISERT.)

Pkg mathfixs mathfixs is used as-is for SVG math, and is emulated for MATHJAX.

 Greek letters are unchanged.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mathfixs}[2018/12/30]

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\rfrac}[2]{\tfrac{#1}{#2}}}
4 \CustomizeMathJax{\newcommand{\vfrac}[2]{\{}^{\#1}\!/\!\{\}_{\#2}}}
5 \CustomizeMathJax{\newcommand{\ProvideMathFix}[1]{}}
6 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
7 \CustomizeMathJax{\newcommand{\. }{\,}}
8 \end{warpMathJax}
```

---

**File 237 l warp-mathtools.sty****§ 337 Package mathtools**

(Emulates or patches code by MORTEN HØGHLØM, LARS MADSEN.)

Pkg mathtools mathtools is patched for use by l warp. Emulation macros are provided for MATHJAX.

 **equation numbering** showonlyrefs is disabled, as it conflicts with cleveref, which is used by l warp. Equation numbers may not match the print version.

 **italic correction** mathic is not emulated for HTML.

 **MATHJAX** If using MATHJAX:

- Starred macros are not available. Starred environments do work.
- `mathtools disallowspaces` does not work for MATHJAX. Protect brackets which are not optional arguments, such as:
 

```
\begin{gathered}{}[p]=1 . . .
\end{gathered}
```
- `showonlyrefs` does not work in MATHJAX, and will result in a difference in equation numbering compared to the print version.
- Due to MATHJAX limitations, the following do not render well: `\overbrace`, `\underbrace`, `\overbrace`, `\underbrace`, `rcases`, `drcases`, `\boxed`, and `\ArrowBetweenLines`.
- For the new cases-like environments, `\text` must be used to set the normal roman font if desired.
- `alignat` in MATHJAX requires math mode, but in L<sup>A</sup>T<sub>E</sub>Xit doesn't. It may be required to use `warpHTML` and `warpprint` to isolate a version for each mode.
- `\DeclareParedDelimiter` and related must be in the preamble before `\begin{document}`. The starred versions of each macro are not created.

**for HTML output:** 1 `\LWR@ProvidesPackagePass{mathtools}[2018/01/08]`

```
2 \RequirePackage{graphicx}

3 \MHInternalSyntaxOn
```

Forces `showonlyrefs` off because `l warp` uses `cleveref`, which is not compatible with `showonlyrefs`.

```
4 \renewcommand*\MT_showonlyrefs_true:{%
5   \PackageWarningNoLine{l warp}
6   {%
7     Mathtools \space showonlyrefs \space conflicts \space
8     with \space cleveref, \MessageBreak
9     which \space is \space used \space by \space l warp, \space
10    so \space showonlyrefs \space is \MessageBreak
11    forced \space off. \space\space
12    Equation \space numbers \space may \space not \space match%
13  }
14  \MT_showonlyrefs_false:
15 }
16 \mathtoolsset{showonlyrefs=false}
```

Forces math italic correction off. Not patched for `l warp`.

```
17 \renewcommand*{\MT_mathic_true:}{\MT_mathic_false:}
18 \mathtoolsset{mathic=false}
```

```
19 \MHInternalSyntaxOff
```

For MATHJAX:

```
20 \begin{warpMathJax}
21 \LWR@infoprocessingmathjax{mathtools}
22
23 \CustomizeMathJax{\newcommand{\mathllap}[2][]{\#1#2}}
24 \CustomizeMathJax{\newcommand{\mathrlap}[2][]{\#1#2}}
25 \CustomizeMathJax{\newcommand{\mathclap}[2][]{\#1#2}}
26 \CustomizeMathJax{\newcommand{\mathmbox}[1]{\#1}}
27 \CustomizeMathJax{\newcommand{\clap}[1]{\#1}}
28 \CustomizeMathJax{\newcommand{\LWRmathmakebox}[2][]{\#2}}
29 \CustomizeMathJax{\newcommand{\mathmakebox}[1][]{\LWRmathmakebox}}
30 \CustomizeMathJax{\newcommand{\cramped}[2][]{\#1#2}}
31 \CustomizeMathJax{\newcommand{\crampedllap}[2][]{\#1#2}}
32 \CustomizeMathJax{\newcommand{\crampedrlap}[2][]{\#1#2}}
33 \CustomizeMathJax{\newcommand{\crampedclap}[2][]{\#1#2}}
34 \CustomizeMathJax{\newenvironment{crampedsubarray}[1]{}{}}
35 \CustomizeMathJax{\newcommand{\crampedsubstack}{}}
36 \CustomizeMathJax{\newcommand{\smashoperator}[2][]{\#2}}
37 \CustomizeMathJax{\newcommand{\SwapAboveDisplaySkip}{}}
38
39 \CustomizeMathJax{\require{extpfeil}}
40 \CustomizeMathJax{\Newextarrow\xleftrightarrow{10,10}{0x2194}}
41 \CustomizeMathJax{\Newextarrow\xLeftarrow{10,10}{0x21d0}}
42 \CustomizeMathJax{\Newextarrow\xhookleftarrow{10,10}{0x21a9}}
43 \CustomizeMathJax{\Newextarrow\xmapsto{10,10}{0x21a6}}
44 \CustomizeMathJax{\Newextarrow\xRightarrow{10,10}{0x21d2}}
45 \CustomizeMathJax{\Newextarrow\xLeftrightarrow{10,10}{0x21d4}}
46 \CustomizeMathJax{\Newextarrow\xhookrightarrow{10,10}{0x21aa}}
47 \CustomizeMathJax{\Newextarrow\xrightharpoondown{10,10}{0x21c1}}
48 \CustomizeMathJax{\Newextarrow\xleftharpoondown{10,10}{0x21bd}}
49 \CustomizeMathJax{\Newextarrow\xrightleftharpoons{10,10}{0x21cc}}
50 \CustomizeMathJax{\Newextarrow\xrightharpoonup{10,10}{0x21c0}}
51 \CustomizeMathJax{\Newextarrow\xleftharpoonup{10,10}{0x21bc}}
52 \CustomizeMathJax{\Newextarrow\xleftrightharpoons{10,10}{0x21cb}}
53
54 \CustomizeMathJax{\newcommand{\LWRdounderbrace}[1]{\underline{\#1}}}
55 \CustomizeMathJax{\newcommand{\LWRunderbrace}[2][]{\LWRdounderbrace{\#2}}}
56 \CustomizeMathJax{\newcommand{\underbrace}[1][]{\LWRunderbrace{#1}}}
57 \CustomizeMathJax{\newcommand{\LWRdooverbrace}[1]{\overline{\#1}}}
58 \CustomizeMathJax{\newcommand{\LWRoverbrace}[2][]{\LWRdooverbrace{\#2}}}
59 \CustomizeMathJax{\newcommand{\overbrace}[1][]{\LWRoverbrace{#1}}}
60
61 \CustomizeMathJax{\newcommand{\LaTeXunderbrace}[1]{\underbrace{\#1}}}
62 \CustomizeMathJax{\newcommand{\LaTeXoverbrace}[1]{\overbrace{\#1}}}
63
64 \CustomizeMathJax{\newenvironment{matrix*}[1][]{\begin{matrix}}{\end{matrix}}}
65 \CustomizeMathJax{\newenvironment{pmatrix*}[1][]{\begin{pmatrix}}{\end{pmatrix}}}
66 \CustomizeMathJax{\newenvironment{bmatrix*}[1][]{\begin{bmatrix}}{\end{bmatrix}}}
67 \CustomizeMathJax{\newenvironment{Bmatrix*}[1][]{\begin{Bmatrix}}{\end{Bmatrix}}}
68 \CustomizeMathJax{\newenvironment{vmatrix*}[1][]{\begin{vmatrix}}{\end{vmatrix}}}
69 \CustomizeMathJax{\newenvironment{Vmatrix*}[1][]{\begin{Vmatrix}}{\end{Vmatrix}}}
70 \CustomizeMathJax{\newenvironment{smallmatrix*}[1][]{\begin{matrix}}{\end{matrix}}}
```

```

71 \CustomizeMathJax{\newenvironment{psmallmatrix*}[1][]{\begin{pmatrix}}{\end{pmatrix}}}
72 \CustomizeMathJax{\newenvironment{bsmallmatrix*}[1][]{\begin{bmatrix}}{\end{bmatrix}}}
73 \CustomizeMathJax{\newenvironment{Bsmallmatrix*}[1][]{\begin{Bmatrix}}{\end{Bmatrix}}}
74 \CustomizeMathJax{\newenvironment{vsmallmatrix*}[1][]{\begin{Vmatrix}}{\end{Vmatrix}}}
75 \CustomizeMathJax{\newenvironment{Vsmallmatrix*}[1][]{\begin{Vmatrix}}{\end{Vmatrix}}}
76 \CustomizeMathJax{\newenvironment{psmallmatrix}[1][]{\begin{pmatrix}}{\end{pmatrix}}}
77 \CustomizeMathJax{\newenvironment{bsmallmatrix}[1][]{\begin{bmatrix}}{\end{bmatrix}}}
78 \CustomizeMathJax{\newenvironment{Bsmallmatrix}[1][]{\begin{Bmatrix}}{\end{Bmatrix}}}
79 \CustomizeMathJax{\newenvironment{vsmallmatrix}[1][]{\begin{Vmatrix}}{\end{Vmatrix}}}
80 \CustomizeMathJax{\newenvironment{Vsmallmatrix}[1][]{\begin{Vmatrix}}{\end{Vmatrix}}}
81
82
83 \CustomizeMathJax{\newcommand{\LWRmultlined}[1][]{\begin{multline*}}}
84 \CustomizeMathJax{\newenvironment{multlined}[1][]{\LWRmultlined}{\end{multline*}}}
85
86 \CustomizeMathJax{\let\LWRorigshoveleft\shoveleft}
87 \CustomizeMathJax{\renewcommand{\shoveleft}[1][]{\LWRorigshoveleft}}
88 \CustomizeMathJax{\let\LWRorigshoveright\shoveright}
89 \CustomizeMathJax{\renewcommand{\shoveright}[1][]{\LWRorigshoveright}}
90
91 \CustomizeMathJax{\newenvironment{dcases}{\begin{cases}}{\end{cases}}}
92 \CustomizeMathJax{\newenvironment{dcases*}{\begin{cases}}{\end{cases}}}
93 \CustomizeMathJax{\newenvironment{rcases}{\begin{cases}}{\end{cases}}}
94 \CustomizeMathJax{\newenvironment{rcases*}{\begin{cases}}{\end{cases}}}
95 \CustomizeMathJax{\newenvironment{drcases}{\begin{cases}}{\end{cases}}}
96 \CustomizeMathJax{\newenvironment{drcases*}{\begin{cases}}{\end{cases}}}
97 \CustomizeMathJax{\newenvironment{cases*}{\begin{cases}}{\end{cases}}}
98
99 \CustomizeMathJax{\newcommand{\MoveEqLeft}[1][]{}}
100
101 \CustomizeMathJax{%
    special parsing to handle '&' in argument
102   \def\LWRboxed#1##1{\fbox{(#1)}\&\fbox{(#2)}}
103   \newcommand{\Aboxed}[1]{\LWRboxed{#1}##1}
104 }
105
106 \CustomizeMathJax{
107   \newcommand{\ArrowBetweenLines}[1][\Updownarrow]{#1}%
        no starred
108 }
109
110 \CustomizeMathJax{\newcommand{\shortintertext}[1]{\text{#1}\notag}}
111
112 \CustomizeMathJax{\newcommand{\vdotswithin}[1]{\hspace{.5em}\vdots}}
113 \CustomizeMathJax{\newcommand{\shortvdotswithin}[1]{\&\hspace{.5em}\vdots}}
114 \CustomizeMathJax{\newcommand{\MTFlushSpaceAbove}{}}
115 \CustomizeMathJax{\newcommand{\MTFlushSpaceBelow}{}}
116
117 % The following does not create a starred version of the macro:
118 \LetLtxMacro{\LWR@mathtools@orig}{\DeclarePairedDelimiter\DeclarePairedDelimiter}
119 \renewcommand{\DeclarePairedDelimiter}[3]{
120   \LWR@mathtools@orig{\DeclarePairedDelimiter{#1}{#2}{#3}}
121   \CustomizeMathJax{\newcommand{#1}[2][]{\#\#1\#2\#\#1\#3}}
122 }
123 \onlypreamble\DeclarePairedDelimiter
124
125 % (DeclarePairedDelimiterX is already defined to use \DeclarePairedDelimiterXPP.)

```

```
126
127 % The following does not create a starred version of the macro.
128 \LetLtxMacro{\LWR@mathtools@orig}{\DeclarePairedDelimiterXPP{\DeclarePairedDelimiterXPP}
129 \DeclareDocumentCommand{\DeclarePairedDelimiterXPP}{m O{1} m m m m m}{%
130     \LWR@mathtools@orig{\DeclarePairedDelimiterXPP{#1}[#2]{#3}{#4}{#5}{#6}{#7}}
131     \appto{\LWR@customizedMathJax}{\LWRbackslash{}}
132     \appto{\LWR@customizedMathJax}{%
133         \LWRbackslash{}newcommand{\LWRbackslash\macrotocname{#1}\LWRsub}\%
134     }%
135     \appto{\LWR@customizedMathJax}{[#2]\%}
136     \appto{\LWR@customizedMathJax}{\{\{\LWRbackslash{}delimsize\%\%
137     \LWR@subcustomizedmathjax{#3#4#7}\%
138     \appto{\LWR@customizedMathJax}{\LWRbackslash{}delimsize\%}
139     \LWR@subcustomizedmathjax{#5#6}\%
140     \appto{\LWR@customizedMathJax}{\{\}\}\%}
141     \appto{\LWR@customizedMathJax}{\LWRbackslash{}\par}\%
142     \appto{\LWR@customizedMathJax}{\LWRbackslash{}\%}
143     \appto{\LWR@customizedMathJax}{%
144         \LWRbackslash{}newcommand{\LWRbackslash\macrotocname{#1}\}[1]\[]\%
145     }%
146     \appto{\LWR@customizedMathJax}{%
147         \{%
148             \LWRbackslash{}def{\LWRbackslash{}delimsize\{\#1\}}%
149             \LWRbackslash\macrotocname{#1}\LWRsub
150         }\%
151     }%
152     \appto{\LWR@customizedMathJax}{\LWRbackslash{}\par}\%
153 }
154 \@onlypreamble{\DeclareParedDelimiterXPP}
155 \@onlypreamble{\DeclareParedDelimiterX}
156
157 \CustomizeMathJax{\newcommand{\lparen}{(}}
158 \CustomizeMathJax{\newcommand{\rparen}{)}}
159 \CustomizeMathJax{\newcommand{\vcentcolon}{:}}
160 \CustomizeMathJax{\newcommand{\ordinarycolon}{:}}
161
162 \CustomizeMathJax{\newcommand{\dblcolon}{\vcentcolon\vcentcolon}}
163 \CustomizeMathJax{\newcommand{\coloneqq}{\vcentcolon=}}
164 \CustomizeMathJax{\newcommand{\Coloneqq}{\dblcolon=}}
165 \CustomizeMathJax{\newcommand{\coloneq}{\vcentcolon{-}}}
166 \CustomizeMathJax{\newcommand{\Coloneq}{\dblcolon{-}}}
167
168 \CustomizeMathJax{\newcommand{\eqqcolon}{=\vcentcolon}}
169 \CustomizeMathJax{\newcommand{\Eqqcolon}{=\dblcolon}}
170 \CustomizeMathJax{\newcommand{\eqcolon}{\mathrel{-}\vcentcolon}}
171 \CustomizeMathJax{\newcommand{\Eqcolon}{\mathrel{-}\dblcolon}}
172
173 \CustomizeMathJax{\newcommand{\colonapprox}{\vcentcolon\approx}}
174 \CustomizeMathJax{\newcommand{\Colonapprox}{\dblcolon\approx}}
175 \CustomizeMathJax{\newcommand{\colonsim}{\vcentcolon\sim}}
176 \CustomizeMathJax{\newcommand{\Colonsim}{\dblcolon\sim}}
177
178 \CustomizeMathJax{\newcommand{\nuparrow}{\cancel{\uparrow}}}
179 \CustomizeMathJax{\newcommand{\ndownarrow}{\cancel{\downarrow}}}
180 \CustomizeMathJax{\newcommand{\bigtimes}{\Large\times}}
```

---

```

181
182 \CustomizeMathJax{\newcommand{\prescript}[3]{{}^{\#1}_{\#2}\#3}}
183
184
185 \CustomizeMathJax{\newenvironment{lgathered}{\begin{gathered}}{\end{gathered}}}
186 \CustomizeMathJax{\newenvironment{rgathered}{\begin{gathered}}{\end{gathered}}}
187
188 \LetLtxMacro{\LWR@mathtools@orig}{\newgathered\newgathered}
189 \renewcommand{\newgathered}[4]{%
190   \LWR@mathtools@orig{\newgathered{\#1}{\#2}{\#3}{\#4}}%
191   \appto{\LWR@customizedMathJax{\LWRbackslash}}{%
192     \LWR@subcustomizedmathjax{%
193       \newenvironment{\#1}{\begin{gathered}}{\end{gathered}}}}%
194   }%
195   \appto{\LWR@customizedMathJax{\LWRbackslash}}{%
196 }%
197 \onlypreamble\newgathered
198
199 \CustomizeMathJax{\newcommand{\splitfrac}[2]{{}^{\#1}_{\#2}}}
200 \CustomizeMathJax{\let\splitdfrac\splitfrac}
201 \end{warpMathJax}

```

---

File 238 **l warp-mcaption.sty**

§ 338 Package **mcaption**

*(Emulates or patches code by STEPHAN HENNIG.)*

Pkg **mcaption** **mcaption** is ignored.

**for HTML output:** Discard all options for **l warp-mcaption**:

```

1 \LWR@ProvidesPackageDrop{mcaption}[2009/03/13]

2 \newenvironment{margincap}{}{}
3 \newcommand*{\margincapalign}{}
4 \newlength{\margincapsep}

```

---

File 239 **l warp-mdframed.sty**

§ 339 Package **mdframed**

*(Emulates or patches code by MARCO DANIEL, ELKE SCHUBERT.)*

Pkg **mdframed** **mdframed** is loaded with options forced to **framemethod=none**.

### § 339.1 Limitations

**support** Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for `mdframed` environments and frame titles.

**⚠ loading** When used, `l warp` loads `mdframed` in HTML with `framemethod=none`.

**font** For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the `mdframed` source). Since `l warp` does not support `\bfseries` and friends, only one font selection may be made at a time.

**theoremtitlefont** `theoremtitlefont` is not supported, since the following text is not in braces in the `mdframed` source.

**ignored options** `userdefinedwidth` and `align` are currently ignored.

**css classes** Environments created or encapsulated by `mdframed` are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class `|mdframedtitle|`. Subtitles are in a `<div>` of class `|mdframedsubtitle|`, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

### § 339.2 Package loading

**for HTML output:**

```
1 \RequirePackage{xcolor}%
2 %
3 \LWR@ProvidesPackageDrop{mdframed}[2013/07/01]
```

Do not require `Tikz` or `pstricks`:

```
4 \LWR@origRequirePackage[framemethod=none]{mdframed}
```

### § 339.3 Patches

Patch to remove PDF formatting and add HTML tags:

```
5 \AtBeginDocument{
6 \def\mdf@trivlist#1{%
7   \edef\mdf@temp{%
8     \topsep=\the\topsep\relax%
9     \partopsep=\the\partopsep\relax%
10    \parsep=\the\parsep\relax%
```

```

11   }%
12 %   \setlength{\topsep}{#1}%
13 %   \topskip\z@%
14 %   \partopsep\z@%
15 %   \parsep\z@%
16 %   \enmbrlistfalse%
17 %   \@trivlist%
18 %   \labelwidth\z@%
19 %   \leftmargin\z@%
20 %   \itemindent\z@%
21 \let\@itemlabel\@empty%
22 \def\makelabel##1{##1}%
23 \item\relax\mdf@temp\relax%
24 }
25
26 \renewcommand*\endmdf@trivlist}{%
27 \LWR@traceinfo{endmdf@trivlist}%
28 % \endtrivlist%
29 \LWR@listend%
30 }
31 }% AtBeginDocument

```

#### § 339.4 Initial setup

To handle css and paragraphs, patch code at start and end of environment and contents. \LWR@print@raggedright helps avoid hyphenation.

```

32 \mdfsetup{%
33 startcode={\LWR@mdframedstart\LWR@print@raggedright},
34 endcode={\LWR@mdframedend},
35 startinnercode={\LWR@startpars\LWR@print@raggedright},
36 endinnercode={\LWR@stoppars},
37 }

```

#### § 339.5 Color and length HTML conversion

\LWR@mdfprintcolor {⟨mdfcolorkey⟩}

Given the mdframed key, print the color.

```

38 \newcommand*\LWR@mdfprintcolor[1]{%
39 \convertcolorspec[named]{\nameuse{mdf@#1}}{HTML}\LWR@tempcolor%
40 \LWR@origpound\LWR@tempcolor
41 }

```

\LWR@mdfprintlength {⟨mdflengthkey⟩}

Given the mdframed key, print the length.

```

42 \newcommand*\LWR@mdfprintlength[1]{%
43 \LWR@forceminwidth{\nameuse{mdf@#1@length}}%
44 \LWR@printlength{\LWR@atleastonept}%
45 }

```

## § 339.6 Environment encapsulation

\LWR@mdframedstart Actions before an mdframe starts.

Encapsulate a frame inside a <div> of the desired class.

```
46 \newcommand*{\LWR@mdframedstart}{%
47 \LWR@traceinfo{LWR@mdframedstart start}%
}
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
48 \LWR@stoppars%
```

Open a <div> and with custom class and custom style. A BlockClass environment is not used because this <div> is created by the mdframed startcode and endcode settings, which do not properly nest the <div> inside the mdframed environment.

```
49 \LWR@htmltagc{div class="%"
50 mdframed%
51 \ifdefstring{\LWR@mdthisenv}{mdframed}{}{ \LWR@mdthisenv}%
52 " \LWR@orignewline
53 style=" \LWR@orignewline
```

Convert and print the background color:

```
54 background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
55 border: \LWR@mdfprintlength{linewidth} solid
56 \LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
57 border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
58 \ifbool{mdf@shadow}{%
59   box-shadow:
60   \LWR@mdfprintlength{shadowsize}
61   \LWR@mdfprintlength{shadowsize}
62   \LWR@mdfprintlength{shadowsize}
63   \LWR@mdfprintcolor{shadowcolor} ;
64 }
65 {box-shadow: none ;}
66 \LWR@orignewline

67 "}
68 % \LWR@htmldivclass{\LWR@mdthisenv}
```

mdframed environment may not work with the HTML versions of the following, so restore them to their originals while inside mdframed:

```
69 \LWR@select@print@hspace%
70 \renewcommand*{\rule}{\LWR@print@rule}
71 \LetLtxMacro{\makebox}{\LWR@print@makebox}

72 \LWR@startpars%
73 \LWR@traceinfo{LWR@mdframedstart done}%
74 }
```

\LWR@mdframedend Actions after an mdframe ends.

After closing the <div>, globally restore to the default environment type:

```
75 \newcommand*{\LWR@mdframedend}{%
76 \LWR@traceinfo{\LWR@mdframedend start}%

```

Close the custom <div>:

```
77 \LWR@htmldivclassend{\LWR@mdthisenv}
```

Reset future custom class to the default:

```
78 \gdef\LWR@mdthisenv{mdframed}
```

Resume paragraph handling:

```
79 \LWR@startpars%
80 \LWR@traceinfo{\LWR@mdframedend done}%
81 }
```

## § 339.7 Mdframed environment

```
82 \renewenvironment{mdframed}[1][]{
83   \color@begingroup%
84   \mdfsetup{userdefinedwidth=\linewidth,#1}%
85   \mdf@startcode%
86   \mdf@prenvsetting%
87   \ifdefempty{\mdf@firstframetitle}{}
88     {\let\mdf@frametitlesave\mdf@frametitle%
89      \let\mdf@frametitle\mdf@firstframetitle%
90    }%
91   \ifvmode\nointerlineskip\fi%
92   \ifdefempty{\mdf@frametitle}{}
93     {\mdfframedtitleenv{\mdf@frametitle}%
94     \mdf@frametitle@use%
95   }%
96   \mdf@trivlist{\mdf@skipabove@length}%%
97   \mdf@settings%
98   \mdf@lrbox{\mdf@splitbox@one}%
99   \mdf@startinnercode%
100 }%
101 {%
102   \mdf@ignorelastdescenders%
103   \par%
104   \unskip\ifvmode\nointerlineskip\hrule \atheight\z@\atwidth\hsize\fi%
105   \ifmdf@footnoteinside%
106     \def\mdf@reserved@%
107       \mdf@footnoteoutput%
108     \mdf@endinnercode%
109     \endmdf@lrbox%
110     \ifdefempty{\mdf@frametitle}{}
111       {\mdfframedtitleenv{\mdf@frametitle}\mdf@frametitle@use}%
112     \detected@mdf@put@frame%
113   }%
114   \else%
115     \def\mdf@reserved@%
116   \mdf@endinnercode%
117   \endmdf@lrbox%
```

```

118 %           \ifdefempty{\mdf@frametitle}{()}%
119 %             {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
120 %           \detected@mdf@put@frame%
121           \mdf@footnoteoutput%
122         }%
123     \fi%
124   \mdf@reserveda%
125   \aftergroup\endmdf@trivlist%
126 \color@endgroup%
127 \mdf@endcode%
128 }

\mdf@footnoteoutput
129 \renewrobustcmd*\mdf@footnoteoutput{%
130   \LWR@printpendingmpfootnotes%
131 }

```

## § 339.8 Titles and subtitles

\mdfframedtitleenv {*<title>*}

Place the title inside a <div> of class mdframedtitle:

```

132 \newlength{\LWR@titleroundcorner}
133
134 \renewrobustcmd\mdfframedtitleenv[1]{%
135 \LWR@traceinfo{\LWR@mdframedtitleenv start}%

```

Open a <div> with a custom class and custom style:

136 \begin{BlockClass}[%

Convert and print the title background color:

```

137 background:
138 \LWR@mdfprintcolor{frametitlebackgroundcolor}
139 ; \LWR@orignewline

```

Convert and print the title rule:

```

140 \ifbool{\mdf@frametitlerule}{%
141   border-bottom:
142   \LWR@mdfprintlength{frametitlerulewidth}
143   solid
144   \LWR@mdfprintcolor{frametitlerulecolor}
145   ; \LWR@orignewline
146 }{}%

```

Finish the custom style and the opening <div> tag:

147 ]{mdframedtitle}%

Print the title inside the <div>:

148 \mdf@frametitlefont{\LWR@textcurrentfont{\#1}}%

Close the <div>:

```

149 \end{BlockClass}%
150 \LWR@traceinfo{\LWR@mdframedtitleenv end}%
151 }

```

---

```
\LWR@mdfsubtitlecommon {<sub -or- subsup>} [<options>] {<title>}
Common code for \LWR@mdfsubtitle and \LWR@mdfsubsubtitle.

Encapsulate the subtitle inside a <div> of class mdframedsubtitle:
152 \NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}
153 {%
154   the following empty line is required
155 \LWR@traceinfo{\LWR@mdframedsubtitlecommon start}%
}

Open a <div> with a custom class and custom style:
156 \begin{BlockClass}[%]

Convert and print the background color:
157 background:
158 \LWR@mdfprintcolor{#1titlebackgroundcolor}
159 ; \LWR@orignewline

Convert and print the above line:
160 \ifbool{mdf@#1titleaboveline}{%
161   border-top:
162   \LWR@mdfprintlength{#1titleabovelinewidth}
163   solid
164   \LWR@mdfprintcolor{#1titleabovelinecolor}
165   ; \LWR@orignewline
166 }{}%

Convert and print the below line:
167 \ifbool{mdf@#1titlebelowline}{%
168   border-bottom:
169   \LWR@mdfprintlength{#1titlebelowlinewidth}
170   solid
171   \LWR@mdfprintcolor{#1titlebelowlinecolor}
172   ; \LWR@orignewline
173 }{}%

Finish the custom style and the opening <div> tag:
174 ]{mdframed#1title}%

Perform the original subtitle action:
175 \IfNoValueTF{#2}
176 {%
177   \nameuse{\LWR@origmdf#1title}{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
178 {%
179   \nameuse{\LWR@origmdf#1title}[#2]{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%


Close the <div>:
180 \end{BlockClass}%
181 \newcommand*\LWR@mdfsubtitle{%
182 \LWR@mdfsubtitlecommon{sub}%
}

\LWR@mdfsubtitle [<options>] {<title>}
```

```
183 }
184 \let\mdfsubtitle\LWR@mdfsubtitle
```

```
\LWR@mdfsubsubtitle  [⟨options⟩] {⟨title⟩}
185 \newcommand*{⟨LWR@mdfsubsubtitle⟩}{%
186 \LWR@mdfsubtitlecommon{subsub}%
187 }
188 \let\mdfsubsubtitle\LWR@mdfsubsubtitle
```

### § 339.9 New environments

⟨LWR@mdthisenv⟩ Stores the environment of the frame about to be created:

```
189 \newcommand*{⟨LWR@mdthisenv⟩}{mdframed}
```

```
\newmdenv  [⟨options⟩] {⟨env-name⟩}
```

Modified from the original to remember the environment.

```
190 \renewrobustcmd*{\newmdenv}[2][]{%
191 \newenvironment{#2}%
192 {%
193 \mdfsetup{#1}%
194 \renewcommand*{⟨LWR@mdthisenv⟩}{md#2}%
195 \begin{mdframed}%
196 }%
197 {\end{mdframed}}%
198 }
```

```
\surroundwithmdframed  [⟨options⟩] {⟨environment⟩}
```

Modified from the original to remember the environment.

```
199 \renewrobustcmd*{\surroundwithmdframed}[2][]{%
200 \BeforeBeginEnvironment{#2}%
201 \renewcommand*{⟨LWR@mdthisenv⟩}{md#2}%
202 \begin{mdframed}[#1]}%
203 \AfterEndEnvironment{#2}{\end{mdframed}}%
204 }
```

```
\mdtheorem  [⟨mdframed-options⟩] {⟨envname⟩} [⟨numberedlike⟩] {⟨caption⟩} [⟨within⟩]
```

Modified from the original to remember the environment.

```
205 \DeclareDocumentCommand{\mdtheorem}{ O{} m o m o }{%
206 {\ifcsdef{#2}%
207 {\mdf@PackageWarning{Environment #2 already exists}\MessageBreak}%
208 {%
209 \IfNoValueTF {#3}%
210 {##3 not given -- number relationship}%
211 \IfNoValueTF {#5}%
212 {##3+##5 not given}%
213 \@definecounter{#2}%
214 \expandafter\xdef\csname the#2\endcsname{@thmcounter{#2}}%
215 \newenvironment{#2}[1][]{%
216 \refstepcounter{#2}}%
```

```
217      \ifstrempty{##1}%
218          {\let\@temptitle\relax}%
219          {%
220              \def\@temptitle{\mdf@theoremseparator%
221                          \mdf@theoremspace%
222                          \mdf@theoremtitlefont%
223                          \LWR@textcurrentfont{##1}}% lwarp
224              \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname}{##1}}%
225          }%
226          \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
227                                         \@temptitle}]]}%
228          {\end{mdframed}}%
229      \newenvironment{#2*}[1][]{%
230          \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
231          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]]}%
232          {\end{mdframed}}%
233      }%
234      {##5 given -- reset counter
235      \definecounter{#2}\newctr{#2}[#5]%
236      \expandafter\xdef\csname the#2\endcsname{@thmcounter{#2}}%
237      \expandafter\xdef\csname the#2\endcsname{%
238          \expandafter\noexpand\csname the#5\endcsname \@thmcOUNTERsep%
239          \@thmcounter{#2}}%
240      \newenvironment{#2}[1][]{%
241          \refstepcounter{#2}}%
242          \ifstrempty{##1}%
243              {\let\@temptitle\relax}%
244          {%
245              \def\@temptitle{\mdf@theoremseparator%
246                          \mdf@theoremspace%
247                          \mdf@theoremtitlefont%
248                          \LWR@textcurrentfont{##1}}% lwarp
249              \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname}{##1}}%
250          }%
251          \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
252                                         \@temptitle}]]}%
253          {\end{mdframed}}%
254      \newenvironment{#2*}[1][]{%
255          \ifstrempty{##1}%
256              {\let\@temptitle\relax}%
257          {%
258              \def\@temptitle{\mdf@theoremseparator%
259                          \mdf@theoremspace%
260                          \mdf@theoremtitlefont%
261                          \LWR@textcurrentfont{##1}}% lwarp
262              \mdf@thm@caption{#2}{\#4}{\csname the#2\endcsname}{##1}}%
263          }%
264          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]]}%
265          {\end{mdframed}}%
266      }%
267  }%
268  {##3 given -- number relationship
269  \global\@namedef{the#2}{\@nameuse{the#3}}%
270  \newenvironment{#2}[1][]{%
271      \refstepcounter{#3}}%
```

```

272      \ifstrempty{##1}%
273          {\let\@temptitle\relax}%
274      {%
275          \def\@temptitle{\mdf@theoremseparator%
276                      \mdf@theoremspace%
277                      \mdf@theoremtitlefont%
278                      \LWR@textcurrentfont{##1}}% lwarp
279          \mdf@thm@caption{#2}{##4}{\csname the#2\endcsname}{##1}}%
280      }
281      \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
282                                  \@temptitle}]]}%
283      {\end{mdframed}}%
284      \newenvironment{#2*}[1][]{%
285          \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:#1}}%
286          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
287      {\end{mdframed}}%
288  }%
289  \BeforeBeginEnvironment{#2}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
290  \BeforeBeginEnvironment{#2*}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
291 }%
292 }

```

\newmdtheoremenv [*1: mdframed-options*] [*2: envname*] [*3: numberedlike*] [*4: caption*] [*5: within*]

Modified from the original to remember the environment.

```

293 \DeclareDocumentCommand\newmdtheoremenv{O{} m o m o }{%
294     \Ifboolexpr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }{%
295         {\newtheorem{#2}{#4}}%
296     }{%
297         \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}%
298         \IfValueT{#5}{\newtheorem{#2}{#4}[#5]}%
299     }%
300 \BeforeBeginEnvironment{#2}{%
301 \renewcommand*{\LWR@mdthisenv}{md#2}%
302 \begin{mdframed}[#1]}%
303 \AfterEndEnvironment{#2}{%
304 \end{mdframed}}%
305 }

```

#### File 240 **lwarp-media9.sty**

#### § 340 Package **media9**

Pkg media9 **media9** is emulated.

The packages **multimedia**, **movie15**, and **media9** are supported.

HTML5 **<audio>** and **<video>** objects are created for **.mp3** and **.mp4** files.

HTML5 **<embed>** objects are created for **http** and **ftp** links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediopath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an “embedded” URL with .../embed/... instead of .../v/...

-  & in a URL Many special characters are converted to regular catcode 12 characters for use inside a URL. & is used in the flash variables fields, which are split with xparse \SplitList, which does not seem to work with a catcode 12 divider token, so & is not converted to catcode 12, and will not work in a URL with media9. Using & in a URL in a flashvars field may also cause parsing problems with print output, as well.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{media9}[2019/02/21]

```
2 \LWR@origRequirePackage{lwarp-common-multimedia}
3
4 \RequirePackage{xkeyval}
```

\addmediopath {<path>}

Supported.

```
5 \newcommand*{\LWR@medianine@path}{}  
6
7 \newcommand*{\addmediopath}[1]{\appto{\LWR@medianine@path}{\#1}}
```

The options and poster text are reused in several places.

```
8 \newcommand*{\LWR@medianine@postertext}{}  
9
```

```
9 \newcommand*{\LWR@medianine@options}{}{}
```

Each addresource can generate a multimedia object.

```
10 \define@key{LWR@medianine}{addresource}{%
11     \expandafter\lwr@multimedia\expandafter[\lwr@medianine@options]%
12         {\lwr@medianine@postertext}%
13         {#1}%
14 }
```

Each flashvars source can generate a multimedia object.

```
15 \newcommand*{\LWR@medianine@flashvarsb}[1]{%
16     \IfBeginWith{#1}{source=}{%
17         \StrGobbleLeft{#1}{7}[\lwr@tempone]%
18         \expandafter\lwr@multimedia\expandafter[\lwr@medianine@options]%
19             {\lwr@medianine@postertext}%
20             {\lwr@tempone}%
21     }{}%
22     \IfBeginWith{#1}{src=}{%
23         \StrGobbleLeft{#1}{4}[\lwr@tempone]%
24         \expandafter\lwr@multimedia\expandafter[\lwr@medianine@options]%
25             {\lwr@medianine@postertext}%
26             {\lwr@tempone}%
27     }{}%
28 }
29
30 \NewDocumentCommand{\LWR@medianine@flashvars}{ >{\SplitList{&}} m }{%
31     \ProcessList {#1}{\LWR@medianine@flashvarsb}%
32 }
33
34 \define@key{LWR@medianine}{flashvars}{%
35     \LWR@medianine@flashvars{#1}%
36 }
```

```
\includemedia [⟨options⟩] {⟨poster text⟩} {⟨file or URL⟩}
37 \newcommand*{\LWR@includemediab}[3][]{%
38     \let\input@path\lwr@medianine@path%
39     \renewcommand*{\lwr@medianine@options}{#1}%
40     \renewcommand*{\lwr@medianine@postertext}{#2}%
41     \setkeys{\lwr@medianine}{#1}%
42     \IfBeginWith{#3}{http}{\lwr@multimedia[#1]{#2}{#3}}{%
43     \IfBeginWith{#3}{HTTP}{\lwr@multimedia[#1]{#2}{#3}}{%
44     \IfBeginWith{#3}{ftp}{\lwr@multimedia[#1]{#2}{#3}}{%
45     \IfBeginWith{#3}{FTP}{\lwr@multimedia[#1]{#2}{#3}}{%
46     }}}}}%
47     \endgroup%
48 }
49
50 \newrobustcmd*{\includemedia}{%
51     \begingroup%
52     \lwr@linkmediacatcodes%
53     \lwr@includemediab%
54 }
```

```
\mediabutton  [⟨options⟩] {⟨text⟩}  
Ignored.  
55 \newcommand*\mediabutton}[2][]{}

---


```

#### File 241 **l warp-memhfixc.sty**

##### § 341 Package **memhfixc**

Pkg **memhfixc** **memhfixc** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{memhfixc}[2013/05/30]

---

#### File 242 **l warp-metalogo.sty**

##### § 342 Package **metalogo**

(Emulates or patches code by ANDREW GILBERT MOSCHOU.)

Pkg **metalogo** **metalogo** is used in print mode, and emulated in **HTML**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{metalogo}[2010/05/29]

```
2 \newcommand*\LWR@HTML@setlogokern}[2]{}  
3 \newcommand*\LWR@HTML@setlogodrop}[2][XeTeX]{}  
4 \newcommand*\LWR@HTML@setLaTeXa}[1]{}  
5 \newcommand*\LWR@HTML@setLaTeXee}[1]{}  
6 \newcommand*\LWR@HTML@seteverylogo}[1]{}  
7 \newcommand*\LWR@HTML@everylogo}[1]{}  
8  
9 \LWR@formatted{setlogokern}  
10 \LWR@formatted{setlogodrop}  
11 \LWR@formatted{setLaTeXa}  
12 \LWR@formatted{setLaTeXee}  
13 \LWR@formatted{seteverylogo}  
14 \LWR@formatted{everylogo}
```

---

#### File 243 **l warp-metalogox.sty**

##### § 343 Package **metalogox**

(Emulates or patches code by BRIAN DUNN.)

Pkg **metalogox** **metalogox** is patched for use by **l warp**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{metalogox}[2019/01/20]

\AtBeginDocument, adjust the logo setting according to the font which is active at that moment.

```
2 \AtBeginDocument{  
3   \let\LWR@metalogox@currentformatting\LWR@formatting  
4   \renewcommand*\LWR@formatting{\print} %  
5   \autoadjustlogos*  
6   \let\LWR@formatting\LWR@metalogox@currentformatting  
7 }
```

---

#### File 244 **l warp-mhchem.sty**

### § 344 Package **mhchem**

(Emulates or patches code by MARTIN HENSEL.)

Pkg mhchem mhchem is patched for use by l warp.

**without MATHJAX** Without MATHJAX, mhchem expressions are converted to SVG math. Inline expressions use hashed filenames to allow reuse, and assume that any mhchem options are global.

**MATHJAX with mhchem extension** For MATHJAX, the mhchem extension is used if the mhchem expression is used inside a math expression:

$\text{\ce{C6H5-CHO}}$

not inside math

If *not* used inside a math expression, l warp converts standalone mhchem expressions into SVG math images.

**MATHJAX without mhchem extension** If the MATHJAX mhchem extension is not used, expressions inside math must be placed between \displaymathother and \displaymathnormal:

```
\displaymathother  
\$[ \ce{ . . . } ] \$ . . . \$ \ce { . . . } \$  
\displaymathnormal
```

When producing HTML output without the MATHJAX mhchem extension, l warp does not support the use of nested dollar signs in mhchem expressions.

For some examples from the mhchem manual, change as follows:

$\text{\ce{NaOH(aq,$\infty)}}$$	% old
$\text{\ce{NaOH(aq,\infty)}}$$	% new
$\text{\ce{Fe(CN)_{\frac{6}{2}}}}$$	% old
$\text{\ce{Fe(CN)_{\frac{6}{2}}}}$$	% new
$\text{\ce{NO_{x}}}$$	% old
$\text{\ce{NO_x}}$$	% new
$\text{\ce{NO_{x}}}$$	% old

```

| $\ce{NO_{x}}$           % new
| $\ce{$cis${-}[PtCl2(NH3)2]}$   % old
| $\ce{\mathit{cis}{-}[PtCl2(NH3)2]}$ % new

```

**for HTML output:** 1 \LWR@ProvidesPackagePass{mhchem}[2018/06/22]

The original definition of \ce:

```
2 \LetLtxMacro{\LWR@mhchem@origce}\ce
```

The new definition, called from the new \ce after math shift is set. The starred `\teximage` uses a hashed filename for the SVG image. The alt tag is set to the `mhchem` expression.

```

3 \newcommand{\LWR@mhchem@HTML@ce}[1]{%
4 \LWR@findcurrenttextcolor% sets \LWR@tempcolor
5 \ifbool{\LWR@xfakebold}{%
6   {\def{\LWR@tempone{Y}}{%
7   {\def{\LWR@tempone{N}}{%
8 \begin{teximage}*[\textbackslash ce\{\LWR@HTMLsanitize{\#1}\}]*%
9   [%
10    FM\LWR@f@family%
11    SR\LWR@f@series%
12    SH\LWR@f@shape%
13    SHC\LWR@f@shapecaps%
14    CL\LWR@tempcolor%
15    FB\LWR@tempone% xfakebold
16   ]%
17 \LWR@setcurrentfont%
18 \LWR@mhchem@origce{\#1}%
19 \end{teximage}%
20 \endgroup%
21 \addtocounter{\LWR@mhchem@cedepth}{-1}%
22 }%

```

Only set math shift if outer depth:

```

23 \newcounter{\LWR@mhchem@cedepth}%
24 \setcounter{\LWR@mhchem@cedepth}{0}

```

The new \ce. Sets math shift then continues.

```

25 \renewcommand{\ce}{%
26 \begingroup%
27 \ifnumequal{\value{\LWR@mhchem@cedepth}}{0}{%
28   \catcode`\$=3% math shift
29 }{}%
30 \addtocounter{\LWR@mhchem@cedepth}{1}%
31 \LWR@mhchem@HTML@ce%
32 }

```

The original definition of \cesplit:

---

```
33 \LetLtxMacro{\LWR@mhchem@origcesplit}{\cesplit}
```

The new definition, called from the new `\cesplit` after math shift is set. The starred `\teximage` uses a hashed filename for the SVG image. The `alt` tag is set to the `mhchem` expression.

```
34 \newcommand*{\LWR@mhchem@HTML@cesplit}[2]
35 {%
36 \LWR@findcurrenttextcolor% sets \LWR@tempcolor
37 \ifboolex{\LWR@xfakebold}{%
38   {\def{\LWR@tempone{Y}}{}}%
39   {\def{\LWR@tempone{N}}{}}%
40 \begin{teximage}*[{\textbackslash cesplit{\LWR@HTMLsanitize{#2}}}]*%
41   [%
42     FM{\LWR@f@family}%
43     SR{\LWR@f@series}%
44     SH{\LWR@f@shape}%
45     SHC{\LWR@f@shapecaps}%
46     CL{\LWR@tempcolor}%
47     FB{\LWR@tempone{xfakebold}}%
48   ]%
49 \LWR@setcurrentfont%
50 \LWR@mhchem@origcesplit{#1}{#2}%
51 \end{teximage}%
52 \endgroup%
53 }
```

Only set math shift if outer depth:

```
54 \newcounter{\LWR@mhchem@cesplitdepth}
55 \setcounter{\LWR@mhchem@cesplitdepth}{0}
```

The new `\cesplit`. Sets math shift then continues.

```
56 \renewcommand{\cesplit}{%
57 \begingroup%
58 \ifnumequal{\value{\LWR@mhchem@cesplitdepth}}{0}{%
59   \catcode`\$=3% math shift
60 }{}}%
61 \addtocounter{\LWR@mhchem@cesplitdepth}{1}%
62 \LWR@mhchem@HTML@cesplit%
63 }
```

Resore originals inside a `\teximage`:

```
64 \appto{\LWR@restoreorigformatting}{%
65 \LetLtxMacro{\ce}{\LWR@mhchem@origce}%
66 \LetLtxMacro{\cesplit}{\LWR@mhchem@origcesplit}%
67 }
```

---

**File 245 l warp-microtype.sty****§ 345 Package microtype**

(Emulates or patches code by R SCHLICHT.)

Pkg **microtype** **microtype** is pre-loaded by **l warp**. All user options and macros are ignored and disabled.

**for HTML output:** Discard all options for **l warp-microtype**:

```
1 \LWR@ProvidesPackageDrop{microtype}[2018/01/14]

2 \DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m} {}
3 \DeclareDocumentCommand{\UseMicrotypeSet}{o m} {}
4 \DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m} {}
5 \DeclareDocumentCommand{\SetProtrusion}{o m m} {}
6 \DeclareDocumentCommand{\SetExpansion}{o m m} {}
7 \DeclareDocumentCommand{\SetTracking}{o m m} {}
8 \DeclareDocumentCommand{\SetExtraKerning}{o m m} {}
9 \DeclareDocumentCommand{\SetExtraSpacing}{o m m} {}
10 \DeclareDocumentCommand{\DisableLigatures}{o m} {}
11 \DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m} {}
12 \DeclareDocumentCommand{\DeclareMicrotypeVariants}{m} {}
13 \DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m} {}
14 \DeclareDocumentCommand{\LoadMicrotypefile}{m} {}
15 \DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m} {}
16 \DeclareDocumentCommand{\microtypsetup}{m} {}
17 \DeclareDocumentCommand{\microtypecontext}{m} {}
18 \DeclareDocumentCommand{\textmicrotypecontext}{m m} {#2}
19 @ifpackageloaded{letterspace}{\let\MT@textls\relax}%
20 \DeclareDocumentCommand{\lsstyle}{}{ }
21 \DeclareDocumentCommand{\textls}{o +m} {}
22 \DeclareDocumentCommand{\lslig}{m} {#1}
23 }
24 \def\DeclareMicrotypeSet#1{\gobbletwo}
25 \def\DeclareMicrotypeVariants#1{\gobble}
26 @onlypreamble\DeclareMicrotypeSet
27 @onlypreamble\UseMicrotypeSet
28 @onlypreamble\DeclareMicrotypeSetDefault
29 @onlypreamble\DisableLigatures
30 @onlypreamble\DeclareMicrotypeVariants
31 @onlypreamble\DeclareMicrotypeBabelHook
```

---

**File 246 l warp-midfloat.sty****§ 346 Package midfloat**

(Emulates or patches code by SIGITAS TOLUŠIS.)

Pkg midfloat midfloat is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{midfloat}[2012/05/29]

```
2 \newenvironment{strip}[1][]{\{}{\}}
3 \newskip\stripsep
```

---

File 247 **l warp-midpage.sty**

§ 347 Package **midpage**

Pkg midpage midpage is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{midpage}[2009/09/03]

```
2 \newenvironment{midpage}
3 {\begin{BlockClass}[%
4   \LWR@print@mbox{margin-top:6ex} ; \LWR@print@mbox{margin-bottom:6ex}%
5 ]{midpage}}
6 {\end{BlockClass}}
```

---

File 248 **l warp-minibox.sty**

§ 348 Package **minibox**

(Emulates or patches code by WILL ROBERTSON.)

Pkg minibox minibox is patched for use by l warp.

Due to HTML limitations regarding paragraphs and <div>s, miniboxes inline with other text will appear on their own line.

for HTML output: 1 \LWR@ProvidesPackagePass{minibox}[2013/06/21]

```
2 \ExplSyntaxOn
3 \newcommand{\LWR@HTML@minibox}[2][]{%
4   \LWR@stoppars%
5   \group_begin:
6   \keys_set:nn {minibox} {#1}
7   \bool_if:NTF \l_minibox_frame_bool
8   {
9     \setlength\fboxrule{\l_minibox_rule_dim}
10    \setlength\fboxsep{\l_minibox_pad_dim}
11    \fboxBlock{%
12      \begin{tabular}[\l_minibox_tabular_valign_tl]%
13        {\l_minibox_tabular_preamble_tl}%
14        {#2}%
15      \end{tabular}%
16    }%
}
```

---

```

17      }
18      {
19          \begin{BlockClass}[display:inline-block]{minibox}
20          \begin{tabular}[\l_minibox_tabular_valign_tl]%
21              {\l_minibox_tabular_preamble_tl}
22              {#2}
23          \end{tabular}
24      \end{BlockClass}
25  }
26  \group_end:
27  \LWR@startpars%
28 }
29 \ExplSyntaxOff
30
31 \LWR@formatted{minibox}

```

---

File 249 **lwarp-minitoc.sty**

§ 349 Package **minitoc**

Pkg **minitoc** **minitoc** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop[minitoc][2018/07/12]

**mtcoff** disables **minitoc**.

2 \usepackage{mtcoff}

---

File 250 **lwarp-mismath.sty**

§ 350 Package **mismath**

(Emulates or patches code by ANTOINE MISSIER.)

Pkg **mismath** **mismath** is patched for **SVG** math, and emulated for **MATHJAX**.

⚠ **MATHJAX** \number, \inumber, \jnumber, and \pinumber are ignored for **MATHJAX**, except that \itpi is made available as a clone of \pi.

For **MATHJAX**, \boldvect and \arrowvect are honored if in the preamble.

If \boldvectcommand is set to \mathbf in the preamble, it will be used for **MATHJAX**, otherwise it will default to \mathit. \boldvectcommand may also be set with \CustomizeMathJax in the preamble. See section 8.7.5. Note that as of this writing there is not a bold italic font across all **MATHJAX** fonts.

If \probastyle is set to \mathbb in the preamble, it will be used for **MATHJAX**, otherwise it will default to \mathrm. \probastyle may be set with \CustomizeMathJax in the preamble.

If `\mathset` is set to `\mathbb` in the preamble, it will be used for MATHJAX, otherwise it will default to `\mathbf`. `\mathset` may be set with `\CustomizeMathJax` in the preamble.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mismath}[2019/12/27]

For MATHJAX, used in the HTML comment before the environment.

```
2 \ifbool{mathjax}{%
3     \RenewEnviron{mathcols}{%
4         \preto{\BODY}{\begin{aligned}\displaystyle}
5         \appto{\BODY}{\end{aligned}}
6         \expandafter{(\BODY\}
7     }
8 }% mathjax
```

For svg math. The `lateximage` restores the original defintion of the `math` environment.

```
9 {%
10    \renewenvironment{mathcols}{%
11        \begin{lateximage}
12        \begin{math}
13        \begin{aligned}\displaystyle
14    }{
15        \end{aligned}%
16        \end{math}
17        \end{lateximage}
18    }
19 }% svg
20
21 \renewcommand{\changecol}{%
22     \end{aligned} \qquad
23     \begin{aligned}\displaystyle
24 }
25
26 \begin{warpMathJax}
27 \CustomizeMathJax{\newcommand{\mathup}[1]{\mathrm{#1}}}
28 \CustomizeMathJax{\newcommand{\mathbf}[1]{\mathbf{#1}}}
29 \CustomizeMathJax{\newcommand{\mathit}[1]{\mathrm{i}}}
30 \CustomizeMathJax{\newcommand{\mathj}[1]{\mathrm{j}}}
31
32 \CustomizeMathJax{\newcommand{\boldvect}{}}
33 \CustomizeMathJax{\newcommand{\arrowvect}{}}
34 \CustomizeMathJax{\newcommand{\pinumber}[1][]{#1}}
35 \CustomizeMathJax{\newcommand{\hvect}[1]{\vec{\vphantom{h}}{#1}}}
36 \CustomizeMathJax{\newcommand{\hvec}[1]{\vec{\vphantom{t}}{#1}}}
37 \CustomizeMathJax{%
38     \newcommand{\norm}[1]{\left\| #1 \right\|}}
39 }
40 \CustomizeMathJax{\newcommand{\di}{\mathop{}\!\mathrm{d}}}
41
42 \CustomizeMathJax{\newcommand{\operatorname{P}}{\operatorname{probastyle{P}}}}
43 \CustomizeMathJax{\newcommand{\operatorname{E}}{\operatorname{probastyle{E}}}}
44 \CustomizeMathJax{\newcommand{\operatorname{V}}{\operatorname{probastyle{V}}}}
45 \CustomizeMathJax{\newcommand{\operatorname{Par}}{\operatorname{unicode{x00B6}}}}
46
```

```
47 \CustomizeMathJax{\newcommand{\adj}{\mathrm{adj}}}
48 \CustomizeMathJax{\newcommand{\Aut}{\mathrm{Aut}}}
49 \CustomizeMathJax{\newcommand{\Conv}{\mathrm{Conv}}}
50 \CustomizeMathJax{\newcommand{\cov}{\mathrm{cov}}}
51 \CustomizeMathJax{\newcommand{\Cov}{\mathrm{Cov}}}
52 \CustomizeMathJax{\newcommand{\curl}{\operatorname{\mathit{vect}}{\mathit{curl}}}}
53 \CustomizeMathJax{\newcommand{\divg}{\mathrm{div}}}
54 \CustomizeMathJax{\newcommand{\End}{\mathrm{End}}}
55
56 \CustomizeMathJax{\newcommand{\erf}{\mathrm{erf}}}
57 \CustomizeMathJax{\newcommand{\grad}{\operatorname{\mathit{vect}}{\mathit{grad}}}}
58 \CustomizeMathJax{\newcommand{\id}{\mathrm{id}}}
59 \CustomizeMathJax{\newcommand{\Id}{\mathrm{Id}}}
60 \CustomizeMathJax{\newcommand{\im}{\mathrm{im}}}
61 \CustomizeMathJax{\let\oldIm\Im}
62 \CustomizeMathJax{\renewcommand{\Im}{\operatorname{\mathit{Im}}}}
63 \CustomizeMathJax{\newcommand{\lb}{\mathrm{lb}}}
64 \CustomizeMathJax{\newcommand{\lcm}{\mathrm{lcm}}}
65
66 \CustomizeMathJax{\newcommand{\rank}{\mathrm{rank}}}
67 \CustomizeMathJax{\let\oldRe\Re}
68 \CustomizeMathJax{\renewcommand{\Re}{\operatorname{\mathit{Re}}}}
69 \CustomizeMathJax{\newcommand{\rot}{\operatorname{\mathit{vect}}{\mathit{rot}}}}
70 \CustomizeMathJax{\newcommand{\sgn}{\mathrm{sgn}}}
71 \CustomizeMathJax{\newcommand{\spa}{\mathrm{span}}}
72 \CustomizeMathJax{\newcommand{\tr}{\mathrm{tr}}}
73 \CustomizeMathJax{\newcommand{\Var}{\mathrm{Var}}}
74 \CustomizeMathJax{\newcommand{\Zu}{\mathrm{Z}}}
75
76 \CustomizeMathJax{\newcommand{\arccot}{\mathrm{arccot}}}
77 \CustomizeMathJax{\newcommand{\sech}{\mathrm{sech}}}
78 \CustomizeMathJax{\newcommand{\csch}{\mathrm{csch}}}
79 \CustomizeMathJax{\newcommand{\arsinh}{\mathrm{arsinh}}}
80 \CustomizeMathJax{\newcommand{\arcosh}{\mathrm{arcosh}}}
81 \CustomizeMathJax{\newcommand{\artanh}{\mathrm{artanh}}}
82 \CustomizeMathJax{\newcommand{\arcoth}{\mathrm{arcoth}}}
83 \CustomizeMathJax{\newcommand{\arsech}{\mathrm{arsech}}}
84 \CustomizeMathJax{\newcommand{\arcsch}{\mathrm{arcsch}}}
85
86 \CustomizeMathJax{\newcommand{\bigO}{\mathcal{O}}}
87 \CustomizeMathJax{\newcommand{\bigo}{\mathit{O}}}
88 \CustomizeMathJax{\newcommand{\lito}{\mathit{o}}}
89
90 \CustomizeMathJax{\newcommand{\R}{\mathit{R}}}
91 \CustomizeMathJax{\newcommand{\C}{\mathit{C}}}
92 \CustomizeMathJax{\newcommand{\N}{\mathit{N}}}
93 \CustomizeMathJax{\newcommand{\Z}{\mathit{Z}}}
94 \CustomizeMathJax{\newcommand{\Q}{\mathit{Q}}}
95 \CustomizeMathJax{\newcommand{\F}{\mathit{F}}}
96 \CustomizeMathJax{\newcommand{\K}{\mathit{K}}}
97
98 \CustomizeMathJax{\newcommand{\ds}{\displaystyle}}
99 \CustomizeMathJax{\newcommand{\dlim}{\lim\limits}}
100 \CustomizeMathJax{\newcommand{\dsum}{\sum\limits}}
101 \CustomizeMathJax{\newcommand{\dprod}{\prod\limits}}
```

```

102 \CustomizeMathJax{\newcommand{\dcup}{\bigcup\limits}}
103 \CustomizeMathJax{\newcommand{\dcap}{\bigcap\limits}}
104 \CustomizeMathJax{\newcommand{\lbar}{\overline}}
105 \CustomizeMathJax{\newcommand{\hlbar}[1]{\overline{\vphantom{h}\#1}}}
106 \CustomizeMathJax{\newcommand{\eqdef}{\stackrel{\mathrm{def}}{=}}}
107 \CustomizeMathJax{\newcommand{\unbr}{\underbrace}}
108 \CustomizeMathJax{\newcommand{\iif}{\text{if and only if }}}
109
110 \CustomizeMathJax{\newcommand{\mul}{\mathord{\times}}}
111 \CustomizeMathJax{\newcommand{\then}{\rightarrow}}
112 \CustomizeMathJax{\newcommand{\txt}[1]{\quad\text{#1}\quad}}
113 \CustomizeMathJax{\newcommand{\paren}[1]{\left(\#1\right)}}
114 \CustomizeMathJax{\newcommand{\pow}[2]{\left(\#1\right)^{\! \#2}}}
115 \CustomizeMathJax{\newcommand{\abs}[1]{\left|\#1\right|}}
116 \CustomizeMathJax{\newcommand{\lfrac}[2]{\frac{\#1}{\#2}}}
117
118 \CustomizeMathJax{\newenvironment{system}[1][l]%
119   {\left(\begin{array}{@{.15em}\#1@{}}\right.}
120   \left.\end{array}\right.}
121 }
122
123 \CustomizeMathJax{\newenvironment{spmatrix}%
124   {\left(\begin{smallmatrix}\right.}
125   \left.\end{smallmatrix}\right)}
126 }
127
128 \CustomizeMathJax{%
129   \newenvironment{mathcols}%
130     {\begin{aligned}\displaystyle}
131     {\end{aligned}}
132 }
133 \CustomizeMathJax{\newcommand{\changecol}{\end{aligned}\qquad\begin{aligned}}}

```

User-adjustable settings, detected if in the preamble.

```

134 \AtBeginDocument{
135 \ifdef{\itpi}%
136   \CustomizeMathJax{\let\itpi\pi}
137 }%
138 \ifdefstring{\boldvectcommand}{\mathbf}%
139   \CustomizeMathJax{\newcommand{\boldvectcommand}[1]{\mathbf{#1}}}
140 }%
141   \CustomizeMathJax{\newcommand{\boldvectcommand}[1]{\boldsymbol{#1}}}
142 }%
143 \ifbool{arrowvect}%
144   \CustomizeMathJax{\newcommand{\vect}[1]{\overrightarrow{#1}}}
145 }%
146   \CustomizeMathJax{\newcommand{\vect}[1]{\boldsymbol{\mathrm{#1}}}}
147 }%
148 \ifdefstring{\probastyle}{\mathbb}%
149   \CustomizeMathJax{\newcommand{\probastyle}[1]{\mathbb{#1}}}
150 }%
151   \CustomizeMathJax{\newcommand{\probastyle}[1]{\mathrm{#1}}}
152 }%
153 \ifdefstring{\mathset}{\mathbb}%

```

```
154     \CustomizeMathJax{\newcommand{\mathset}[1]{\mathbb{#1}}}
155 }{
156     \CustomizeMathJax{\newcommand{\mathset}[1]{\mathbf{#1}}}
157 }
158 }
159 \end{warpMathJax}
```

---

**File 251 l warp-morefloats.sty****§ 351 Package morefloats**

Pkg morefloats morefloats is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{morefloats}[2015/07/22]

---

**File 252 l warp-moreverb.sty****§ 352 Package moreverb**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg moreverb moreverb is supported with some patches.

for HTML output: 1 \begin{warpHTML}

```
2 \LWR@ProvidesPackagePass{moreverb}[2008/06/03]

3 \BeforeBeginEnvironment{verbatimtab}{%
4 \LWR@forcenewpage
5 \LWR@atbeginverbatim{3}{Verbatim}%
6 }
7 \AfterEndEnvironment{verbatimtab}{%
8 \LWR@afterendverbatim{1}%
9 }
10
11
12 \LetLtxMacro{\LWRMV@orig@verbatimtabininput}{\verbatimtabininput}
13
14 \renewcommand{@verbatimtabininput}[2][]{%
15 \LWR@forcenewpage
16 \LWR@atbeginverbatim{3}{Verbatim}%
17 \LWRMV@orig@verbatimtabininput[#1]{#2}%
18 \LWR@afterendverbatim{1}%
19 }
20
21 \BeforeBeginEnvironment{listing}{%
22 \LWR@forcenewpage
23 \LWR@atbeginverbatim{3}{programlisting}%
24 }
25
```

```
26 \AfterEndEnvironment{listing}{%
27 \LWR@afterendverbatim{1}%
28 }
29
30 \BeforeBeginEnvironment{listingcont}{%
31 \LWR@forcenewpage
32 \LWR@atbeginverbatim{3}{programlisting}%
33 }
34
35 \AfterEndEnvironment{listingcont}{%
36 \LWR@afterendverbatim{1}%
37 }

38 \LetLtxMacro\LWRMV@{\listinginput@\listinginput
39
40 \renewcommand{@listinginput}[3][]{
41 \LWR@forcenewpage
42 \LWR@atbeginverbatim{3}{programlisting}%
43 \LWRMV@{\listinginput[#1]{#2}{#3}%
44 \LWR@afterendverbatim{1}%
45 }
46
47
48 \renewenvironment*{boxedverbatim}
49 {
50 \LWR@forcenewpage
51 \LWR@atbeginverbatim{3}{boxedverbatim}%
52 \verbatim%
53 }
54 {
55 \endverbatim%
56 \LWR@afterendverbatim{1}%
57 }

58 \end{warpHTML}
```

---

File 253 **lwarp-movie15.sty**

§ 353 Package **movie15**

Pkg movie15 movie15 is emualted.

The packages `multimedia`, `movie15`, and `media9` are supported.

`HTML5 <audio>` and `<video>` objects are created for `.mp3` and `.mp4` files.

`HTML5 <embed>` objects are created for `http` and `ftp` links.

`\href` links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by `HTML5`.)

For **media9**, a multimedia object is inserted for each **addresource=**, as well as each **flashvars source=** and **src=**. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside **\warpprintonly** or the **warpprint** environment.

Each **HTML** multimedia object includes the poster text, except for **<embed>** objects. For **movie15**, the **text** option is supported to specify the poster text.

The **width**, **height**, and **totalheight** options are supported. The **HTML** object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

**media9 \addmediapath** is supported. It is assumed that the same path structure will exist for the **HTML** document.

**HTML5** media controls are always specified for each **<audio>** and **<video>** object.

**media9** slideshows are not supported.

**\hyperlinkmovie**, **\movieref**, and **\mediabutton** are not supported.

3D objects are not supported.

If using a **YOUTUBE™** video, use an “embedded” URL with **.../embed/...** instead of **.../v/...**

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{movie15}[2012/05/16]
2 \LWR@origRequirePackage{lwarp-common-multimedia}
3
4 \RequirePackage{xkeyval}
5
6 \newcommand*{\LWR@moviefifteen@text}{}%
7
8 \define@key{\LWR@moviefifteen}{text}{\renewcommand{\LWR@moviefifteen@text}{#1}}
9
10 \newcommand*{\LWR@includemovieb}[4][]{%
11     \renewcommand{\LWR@moviefifteen@text}{(multimedia)}
12     \setkeys{\LWR@moviefifteen}{#1}%
13     \LWR@multimediacat[#1,width=#2,height=#3]{\LWR@moviefifteen@text}{#4}%
14 }
15
16 \newrobustcmd*{\includemovie}{%
17     \begingroup%
18     \LWR@linkmediacatcodes%
19     \LWR@includemovieb%
20 }
21
22
23 \newcommand*{\movieref}[3][]{}
24
25 \LetLtxMacro\movie\LWR@multimedia
26 % \LetLtxMacro\sound\LWR@multimedia% not in media15
27
```

```
28 \newcommand{\hyperlinkmovie}[3][]{}

---


```

File 254 **l warp-mparhack.sty**

§ 354 Package **mparhack**

Pkg mparhack mparhack is ignored.

for HTML output: Discard all options for l warp-mparhack:

```
1 \LWR@ProvidesPackageDrop{mparhack}[2005/04/17]

---


```

File 255 **l warp-multicap.sty**

§ 355 Package **multicap**

Pkg multicap multicap is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{multicap}[2002/05/04]

```
2 \newcommand*{\mfcaption}{\captionof{figure}}
3 \newcommand*{\mtcaption}{\captionof{table}}
4 \newcounter{mcapsize}
5 \newcounter{mcapskip}
6 \newlength{\abvmcapskip}
7 \newlength{\blwmcapskip}

---


```

File 256 **l warp-multicol.sty**

§ 356 Package **multicol**

(Emulates or patches code by FRANK MITTELBACH.)

Pkg multicol multicol is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{multicol}[2018/12/27]

Multicols are converted into a 1–3 column display, browser-supported.

The optional multicols heading is placed inside a <div> of class multcolsheading.

The content is placed inside a <div> of class multicol.

```
2 \begin{warpHTML}
```

```
Env multicols * {\langle numcols \rangle} [\langle heading \rangle]
3 \NewDocumentEnvironment{multicol}{s m o}
```

HTML <div> class to contain everything:

```
4 {
5   \LWR@forcenewpage
6   \BlockClass{multicols}
```

Optional HTML <div> class for the heading:

```
7   \IfValueT{#3}{\begin{BlockClass}{multicolsheading}#3\end{BlockClass}}%
```

Change \linewidth to compensate for expected size:

```
8   \setlength{\linewidth}{\linewidth/#2}
```

Locally force any minipages to be fullwidth:

```
9   \booltrue{\LWR@forceminipagefullwidth}
10 }
```

When done with the environment, close the <div>:

```
11 {\endBlockClass}
```

Emulated null functions which are not used in HTML:

```
12 \newcommand*{\columnbreak}(){}
13 \newcommand*{\RLmulticolcolumns}){}
14 \newcommand*{\LRmulticolcolumns}){}
15
16 \newlength{\premulticols}
17 \newlength{\postmulticols}
18 \newlength{\multicolsep}
19 \newlength{\multicolbaselineskip}
20 \newlength{\multicoltolerance}
21 \newlength{\multicolpretolerance}
22 \newcommand*{\columnseprulecolor}{\normalcolor}
23 \newcounter{columnbadness}
24 \newcounter{finalcolumnbadness}
25 \newcounter{collectmore}
26 \newcounter{unbalance}
27 \newlength{\multicolovershoot}
28 \newlength{\multicolundershoot}

29 \NewDocumentCommand{\docolaction}{s o m m}{%
30   \IfValueTF{#2}{#2}{#3}{%
31 }

32 \end{warpHTML}
```

File 257 **lwarp-multicolrule.sty**

§ 357      Package **multicolrule**

Pkg **multicolrule** **multicolrule** is ignored.

**for HTML output:**

```
1 \RequirePackage{multicol}
2
3 \LWR@ProvidesPackageDrop{multicolrule}[2019/01/01]

4 \newcommand*\SetMCRule[1]{}
5 \NewDocumentCommand{\DeclareMCRulePattern}{m m}{}

---


```

---

File 258 **l warp-multimedia.sty**

§ 358      Package **multimedia**

Pkg **multimedia** **multimedia** is emulated.

The packages **multimedia**, **movie15**, and **media9** are supported.

**HTML5** `<audio>` and `<video>` objects are created for `.mp3` and `.mp4` files.

**HTML5** `<embed>` objects are created for `http` and `ftp` links.

`\href` links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by **HTML5**.)

For **media9**, a multimedia object is inserted for each `addresource=`, as well as each `flashvars source=` and `src=`. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside `\warpprintonly` or the `warpprint` environment.

Each **HTML** multimedia object includes the poster text, except for `<embed>` objects. For **movie15**, the `text` option is supported to specify the poster text.

The `width`, `height`, and `totalheight` options are supported. The **HTML** object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

**media9** `\addmediopath` is supported. It is assumed that the same path structure will exist for the **HTML** document.

**HTML5** media controls are always specified for each `<audio>` and `<video>` object.

**media9** slideshows are not supported.

`\hyperlink{movie}`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a **YOUTUBE™** video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

**for HTML output:** 1 \LWR@ProvidesPackageDrop{multimedia}[2012/05/02]

---

```

2 \LWR@origRequirePackage{l warp-common-multimedia}
3
4 \LetLtxMacro\movie\LWR@multimedia
5 \LetLtxMacro\sound\LWR@multimedia
6
7 \newcommand{\hyperlinkmovie}[3][]{}

```

---

File 259 **l warp-multirow.sty**

§ 359 Package **multirow**

*(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)*

Pkg **multirow** **multirow** is emulated during **HTML** output, and used as-is while inside a **lateximage**.

- Note that recent versions of **multirow** include a new optional **vposn** argument.

**multirow cells** • For **multirow**, insert **\mrowcell** into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for **HTML** output. An error is generated if this is missed.

```

. . . & \multirow{2}{.5in}{text} & . . .
. . . & \mrowcell & . . .

```

**colored cells** • The **multirow** documentation regarding colored cells recommends using a negative number of rows. This will not work with **l warp**, so **\warpprintonly** and **\warpHTMLonly** must be used to make versions for print and **HTML**.

- See section 359.2 for **\multicolumnrow**.

**⚠** **\multicolumn & \multirow** **l warp** does not support directly combining **\multicolumn** and **\multirow**. Use **\multicolumnrow** instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}{c}{3}{0}{1in}{0pt}{Text}
```

The two arguments for **\multicolumn** come first, followed by the five arguments for **\multirow**, many of which are optional, followed by the contents.

As per **\multirow**, skipped cells to the right of the **\multicolumnrow** statement are not included in the source code on the same line. On the following lines, **\mcolrowcell** must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```

. . . & \multicolumnrow{2}{c}{c}{3}{0}{1in}{0pt}{Text} & . . .
. . . & \mcolrowcell & \mcolrowcell & . . .
. . . & \mcolrowcell & \mcolrowcell & . . .

```

- ⚠** **MathJax** • **MATHJAX** does not support **multirow**, so it is emulated to only print its text on the first row. **\multirow** works as expected in **text** **tabulars** or **SVG** **math**.

In a **lateximage**, **\LWR@restoreorigformatting** restores the original print-mode versions.

See section 72.25 for the print-mode versions.

**for HTML output:** Remove the placeholder macro which was used if `multirow` was not loaded:

```
1 \LetLtxMacro\multirow\relax
2 \LWR@ProvidesPackagePass{multirow}[2018/08/03]
```

`\LWR@multirowborder` Set to `left` or `right` to create a thick border for the cell, for use by `bigdelim`:

```
3 \newcommand{\LWR@multirowborder}{}%
```

### § 359.1 Multirow

`\multirow` [*vpos*] {*numrows*} [*bigstruts*] {*width*} [*fixup*] {*text*}

```
4 \NewDocumentCommand{\LWR@HTML@multirow}{O{c} m o m o +m}%
5 {%
6 \LWR@traceinfo{*** LWR@HTML@multirow #1 #2 #4}%

```

```
7 \booltrue{LWR@usedmultirow}%
8 \LWR@maybenewtablerow%
9 \LWR@tabularleftedge%
```

Print the start of a new table data cell:

```
10 \LWR@htmlltag{td rowspan="#2" %}
```

The vertical alignment, if given:

```
11 \ifstrequal{#1}{c}{\style=\\"LWR@print@mbox{vertical-align:middle}\"}{}%
12 \ifstrequal{#1}{b}{\style=\\"LWR@print@mbox{vertical-align:bottom}\"}{}%
13 \ifstrequal{#1}{t}{\style=\\"LWR@print@mbox{vertical-align:top}\"}{}%
```

The left/right border, if given:

```
14 \ifdefvoid{\LWR@multirowborder}{}{%
15 \style=\\"LWR@print@mbox{border-\LWR@multirowborder:\} 2px dotted black ; %
16 \LWR@print@mbox{padding-\LWR@multirowborder:\} 2px" %
17 }%
```

A class adds the column spec and the rule:

```
18 class="td%"
```

Append this column's spec:

```
19 \LWR@getexpararray{\LWR@tablecolspec}{\arabic{\LWR@tableLaTeXcolindex}}%
```

If this column has a cmidrule, add “rule” to the end of the `HTML` class tag. Also add the vertical bar class.

```

20 \LWR@addcmidruletrim%
21 \LWR@addleftmostbartag%
22 \LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
23 "%"

24 \LWR@tdstartstyles%
25 \LWR@addcmidrulewidth%
26 \LWR@addcdashline%
27 \LWR@addtabularrulecolors%
28 \LWR@tdendstyles%
29 }%
```

The column's < spec:

```
30 \LWR@getexparray{\LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
```

While printing the text, redefine \\ to generate a new line

```

31 \begingroup\LetLtxMacro{\\"}{\LWR@endofline}\#6\endgroup%
32 \LWR@stoppars%
33 \boolfalse{\LWR@intabularmetadata}%
34 \renewcommand{\LWR@multirowborder}{}%
35 \LWR@traceinfo{*** \LWR@HTML@multirow done}%
36 }%
37
38 \LWR@formatted{multirow}
```

## § 359.2 Combined multicolumn and multirow

```
\multicolumnrow {\langle 1:cols\rangle} {\langle 2:halign\rangle} [\langle 3:vpos\rangle] {\langle 4:numrows\rangle} [\langle 5:bigstruts\rangle] {\langle 6:width\rangle} [\langle 7:fixup\rangle]
{\langle 8:text\rangle}
```

`\@ifpackageloaded{multirow}` determines if v2.0 or later of `multirow` was used, which included the `\ProvidesPackage` macro.

The `HTML` version follows.

`\AtBeginDocument` because the print version had to see if `multirow` was loaded before determining how to define `\LWR@print@multicolumnrow`.

```

39 \AtBeginDocument{
40
41 \NewExpandableDocumentCommand{\LWR@HTML@multicolumnrow}{m m O{} m O{} m O{} +m}{%
42 \booltrue{\LWR@usedmultirow}}%
```

Figure out how many extra `HTML` columns to add for @ and ! columns:

```
43 \LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn/multirow tag, temporarily redefining the end of line. (Using a group caused problems with a nested tabular.

```
44 \LetLtxMacro{\\"}{\LWR@endofline}%
45 \LWR@domulticolumn[#3][#4]{#1}{\arabic{\LWR@tabhtmlcoltotal}}{#2}{#8}%
46 \LetLtxMacro{\\"}{\LWR@tabularendofline}%
```

Move to the next L<sup>A</sup>T<sub>E</sub>X column:

```
47 \defaddtocounter{\LWR@tableLaTeXcolindex}{#1}%
48 \defaddtocounter{\LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
49 \booltrue{\LWR@skipatbang}%
50 }%
51 \LWR@expandableformatted{multicolumnrow}%
52 \AtBeginDocument{%
53 }
```

For MATHJAX. Only the text is used. All other parameters are ignored.

```
55 \begin{warpMathJax}
56 % \multirow[vpos]{num}[bigstruts][width][vmove]{text}
57 \CustomizeMathJax{\newcommand{\LWRsubmultirow}[2][]{\#2}}
58 \CustomizeMathJax{\newcommand{\LWRmultirow}[2][]{\LWRsubmultirow}}
59 \CustomizeMathJax{\newcommand{\multirow}[2][]{\LWRmultirow}}
60 %
61 \CustomizeMathJax{\newcommand{\mrowcell}{}}
62 \CustomizeMathJax{\newcommand{\mcolrowcell}{}}
63 \CustomizeMathJax{\newcommand{\STneed}[1]{}}
64 \end{warpMathJax}
```

#### File 260 **lwarp-multitoc.sty**

#### § 360 Package **multitoc**

Pkg **multitoc** **multitoc** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{multitoc}[1999/06/08]

```
2 \newcommand{\multicolumntoc}{2}
3 \newcommand{\multicolumnlot}{2}
4 \newcommand{\multicolumnlof}{2}
5 \newcommand*{\immediateaddtocontents}[2]{}
```

---

File 261 **l warp-musicography.sty**

§ 361 Package **musicography**

(Emulates or patches code by ANDREW A. CASHNER.)

Pkg **musicography** **musicography** is patched for use by **l warp**.

Images are used for the meter symbols and fingered bass, since the HTML fonts tend not to be the correct size and HTML cannot stack items. The HTML alt tag copies C and 3/2, etc. Hashes are used for the meter images, which are then reused as necessary.

 Note that browser support for musical symbols may be buggy. ALT text and copy/paste into a text editor work well.

**for HTML output:** 1 \LWR@ProvidesPackagePass{musicography}[2019/05/28]

```
2 \NewDocumentCommand{\LWR@HTML@musSymbol}{ O{\musFont} m m m m }{%
3 \begin{ lateximage }%
4 {#1\kern#2\raisebox{#3}{#5}\kern#4}%
5 \end{ lateximage }%
6 }%
7 %
8 \LWR@formatted{musSymbol}%
9 %
10 \NewDocumentCommand{\LWR@HTML@musStemmedNote}{ m }{%
11 \begin{ lateximage }%
12 \musSymbol{0.05em}{0.5ex}{0.2em}{#1\musStem}%
13 \end{ lateximage }%
14 }%
15 %
16 \LWR@formatted{musStemmedNote}%
17 %
18 \NewDocumentCommand{\LWR@HTML@musFlaggedNote}{ m m }{%
19 \begin{ lateximage }%
20 \musSymbol{0.05em}{0.5ex}{0pt}{#1\musStem}%
21 \musSymbol{0pt}{0pt}{0.9em}{#2}%
22 \end{ lateximage }%
23 }%
24 %
25 \LWR@formatted{musFlaggedNote}%
26 %
27 \NewDocumentCommand{\LWR@HTML@musDottedNote}{ m }{%
28 \begin{ lateximage }%
29 #1\musDot%
30 \end{ lateximage }%
31 }%
32 %
33 \LWR@formatted{musDottedNote}%
34 %
35 \NewDocumentCommand{\LWR@HTML@musMeter}{ m m }{%
```

```
36 \begin{lateximage}*[#1/#2][#1#2]*%
37 \musStack{\#1 #2}\kern0.05em%
38 \end{lateximage}%
39 }
40
41 \LWR@formatted{\musMeter}
42
43 \NewDocumentCommand{\LWR@HTML@meterCplus}{ m }{%
44 \begin{lateximage}*[{C#1}]*%
45     \meterC{} \kern-0.7pt#1%
46 \end{lateximage}%
47 }
48
49 \LWR@formatted{\meterCplus}
50
51 \NewDocumentCommand{\LWR@HTML@meterC}{}{%
52 \begin{lateximage}*[C]*%
53 \musSymbolMeter{\symbol{83}}%
54 \end{lateximage}%
55 }
56
57 \LWR@formatted{\meterC}
58
59 \NewDocumentCommand{\LWR@HTML@meterCutC}{}{%
60 \begin{lateximage}*[C|]*%
61 \musSymbolMeter{\symbol{82}}%
62 \end{lateximage}%
63 }
64
65 \LWR@formatted{\meterCutC}
66
67 \NewDocumentCommand{\LWR@HTML@meterCThreeTwo}{}{%
68 \begin{lateximage}*[{C3/2}]*%
69 \meterCplus{\musStack{3 2}}%
70 \end{lateximage}%
71 }
72
73 \LWR@formatted{\meterCThreeTwo}
74
75 \NewDocumentCommand{\LWR@HTML@meter0}{}{\HTMLunicode{25EF}}
76
77 \LWR@formatted{\meter0}
78
79 \newcommand{\LWR@null@noFig}[1][]{}%
80
81 \NewDocumentCommand{\LWR@HTML@musFig}{ m }{%
82 \begin{lateximage}*[%}
83     { \% ALT text for copy/paste
84         \LetLtxMacro{\noFig}{\LWR@null@noFig}
85         \LetLtxMacro{\musSharp}{\LWR@HTML@musSharp}
86         \LetLtxMacro{\musDoubleSharp}{\LWR@HTML@musDoubleSharp}
87         \LetLtxMacro{\musFlat}{\LWR@HTML@musFlat}
88         \LetLtxMacro{\musDoubleFlat}{\LWR@HTML@musDoubleFlat}
89         \LetLtxMacro{\musNatural}{\LWR@HTML@musNatural}
90     {#1} \% braces here because \noFig uses []
91 }
```

```
91      }%
92 ]*%
93   \musStack[\musFigFont]{#1}%
94 \end{lateximage}%
95 }
96
97 \LWR@formatted{\musFig}
98
99 \NewDocumentCommand{\LWR@HTML@musFlat}      {}{\HTMLUnicode{266D}}
100 \NewDocumentCommand{\LWR@HTML@musDoubleFlat} {}{\HTMLUnicode{1D12B}}
101 \NewDocumentCommand{\LWR@HTML@musSharp}       {}{\HTMLUnicode{266F}}
102 \NewDocumentCommand{\LWR@HTML@musDoubleSharp}{}{\HTMLUnicode{1D12A}}
103 \NewDocumentCommand{\LWR@HTML@musNatural}     {}{\HTMLUnicode{266E}}
104
105 \LWR@formatted{\musFlat}
106 \LWR@formatted{\musDoubleFlat}
107 \LWR@formatted{\musSharp}
108 \LWR@formatted{\musDoubleSharp}
109 \LWR@formatted{\musNatural}
110
111 \NewDocumentCommand{\LWR@HTML@musWhole}        {}{\HTMLUnicode{1D15D}}
112 \NewDocumentCommand{\LWR@HTML@musHalf}          {}{\HTMLUnicode{1D15E}}
113 \NewDocumentCommand{\LWR@HTML@musQuarter}        {}{\HTMLUnicode{1D15F}}
114 \NewDocumentCommand{\LWR@HTML@musEighth}         {}{\HTMLUnicode{1D160}}
115 \NewDocumentCommand{\LWR@HTML@musSixteenth}      {}{\HTMLUnicode{1D161}}
116 \NewDocumentCommand{\LWR@HTML@musThirtySecond}    {}{\HTMLUnicode{1D162}}
117 \NewDocumentCommand{\LWR@HTML@musSixtyFourth}    {}{\HTMLUnicode{1D163}}
118
119 \LWR@formatted{\musWhole}
120 \LWR@formatted{\musHalf}
121 \LWR@formatted{\musQuarter}
122 \LWR@formatted{\musEighth}
123 \LWR@formatted{\musSixteenth}
124 \LWR@formatted{\musThirtySecond}
125 \LWR@formatted{\musSixtyFourth}
126
127 \NewDocumentCommand{\LWR@HTML@musWholeDotted}{}%
128   {\HTMLUnicode{1D15D}\HTMLUnicode{1D16D}}%
129 \NewDocumentCommand{\LWR@HTML@musHalfDotted}{}%
130   {\HTMLUnicode{1D15E}\HTMLUnicode{1D16D}}%
131 \NewDocumentCommand{\LWR@HTML@musQuarterDotted}{}%
132   {\HTMLUnicode{1D15F}\HTMLUnicode{1D16D}}%
133 \NewDocumentCommand{\LWR@HTML@musEighthDotted}{}%
134   {\HTMLUnicode{1D160}\HTMLUnicode{1D16D}}%
135 \NewDocumentCommand{\LWR@HTML@musSixteenthDotted}{}%
136   {\HTMLUnicode{1D161}\HTMLUnicode{1D16D}}%
137 \NewDocumentCommand{\LWR@HTML@musThirtySecondDotted}{}%
138   {\HTMLUnicode{1D162}\HTMLUnicode{1D16D}}%
139 \NewDocumentCommand{\LWR@HTML@musSixtyFourthDotted}{}%
140   {\HTMLUnicode{1D163}\HTMLUnicode{1D16D}}%
141
142 \LWR@formatted{\musWholeDotted}
143 \LWR@formatted{\musHalfDotted}
144 \LWR@formatted{\musQuarterDotted}
145 \LWR@formatted{\musEighthDotted}
```

```
146 \LWR@formatted{musSixteenthDotted}
147 \LWR@formatted{musThirtySecondDotted}
148 \LWR@formatted{musSixtyFourthDotted}
```

---

**File 262 l warp-nameauth.sty****§ 362 Package nameauth**

(Emulates or patches code by CHARLES P. SCHAUM.)

Pkg nameauth nameauth is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{nameauth}[2017/03/22]

l warp formatting is inserted in the following.

```
2 \renewcommand*\@nameauth@Hook[1]
3 {%
4   \if@nameauth@Lock
5     \@nameauth@InHooktrue%
6     \protected@edef\test{\#1}%
7     \expandafter\@nameauth@TestDot\expandafter{\test}%
8     \if@nameauth@InAKA
9       \if@nameauth@AlwaysFormat
10         \@nameauth@FirstFormattrue%
11     \else
12       \unless\if@nameauth@AKAFormat
13         \@nameauth@FirstFormatfalse\fi
14     \fi
15     \if@nameauth@MainFormat
16       \if@nameauth@FirstFormat
17         \bgroup\NamesFormat{%
18           \LWR@textcurrentcolor{\LWR@textcurrentfont{\#1}}% l warp
19         }\egroup%
20       \else
21         \bgroup\MainNameHook{%
22           \LWR@textcurrentcolor{\LWR@textcurrentfont{\#1}}% l warp
23         }\egroup%
24       \fi
25     \else
26       \if@nameauth@FirstFormat
27         \bgroup\FrontNamesFormat{%
28           \LWR@textcurrentcolor{\LWR@textcurrentfont{\#1}}% l warp
29         }\egroup%
30       \else
31         \bgroup\FrontNameHook{%
32           \LWR@textcurrentcolor{\LWR@textcurrentfont{\#1}}% l warp
33         }\egroup%
34       \fi
35     \fi
36   \else
37     \if@nameauth@AlwaysFormat
```

```

38      \@nameauth@FirstFormattrue%
39      \fi
40      \if@nameauth@MainFormat
41          \if@nameauth@FirstFormat
42              \bgroup\NamesFormat{%
43                  \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% l warp
44              }\egroup%
45      \else
46          \bgroup\MainNameHook{%
47              \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% l warp
48          }\egroup%
49      \fi
50  \else
51      \if@nameauth@FirstFormat
52          \bgroup\FrontNamesFormat{%
53              \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% l warp
54          }\egroup%
55      \else
56          \bgroup\FrontNameHook{%
57              \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% l warp
58          }\egroup%
59      \fi
60  \fi
61  \fi
62  \@nameauth@FirstFormatfalse%
63  \@nameauth@InHookfalse%
64 \fi
65 }

```

File 263 **l warp-nameref.sty**§ 363 Package **nameref**

Pkg nameref nameref is emulated by l warp.

**for HTML output:** Discard all options for l warp-nameref:

```

1 \PackageInfo{l warp}{%
2 Using the l warp HTML version of package ‘nameref’, \MessageBreak
3 and discarding options.\MessageBreak
4 (Not using \protect\ProvidesPackage, so that other packages\MessageBreak
5 do not attempt to patch l warp’s version of ‘nameref’.)\MessageBreak
6 }
7 \DeclareOption*{}
8 \ProcessOptions\relax

```

File 264 **l warp-natbib.sty**§ 364 Package **natbib**

(Emulates or patches code by PATRICK W. DALY.)

Pkg natbib natbib is patched for use by l warp.

for HTML output 1 \LWR@ProvidesPackagePass{natbib}[2010/09/13]

Replace math < and > with \textless and \textgreater:

A macro to compare:

2 \newcommand{\LWRNB@NAT@open}{\$<\$}

To patch \NAT@open and \NAT@close

```
3 \newcommand{\LWRNB@patchnatbibopenclose}{%
4 \ifdefined\NAT@open{\LWRNB@NAT@open}%
5 {%
6   \renewcommand{\NAT@open}{\textless}%
7   \renewcommand{\NAT@close}{\textgreater}%
8 }%
9 }
```

Do it now in case angle was selected as an option:

10 \LWRNB@patchnatbibopenclose

Also patch \setcitestyle to patch after settings are made:

```
11 \let\LWRNB@origsetcitestyle\setcitestyle
12
13 \renewcommand{\setcitestyle}[1]{%
14 \LWRNB@origsetcitestyle{\#1}%
15 \LWRNB@patchnatbibopenclose%
16 }
```

### File 265 l warp-nccfancyhdr.sty

#### § 365 Package nccfancyhdr

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg nccfancyhdr nccfancyhdr is ignored.

for HTML output 1 \LWR@ProvidesPackageDrop{nccfancyhdr}[2004/12/07]

```
2 \newcommand*\headrulewidth{}%
3 \newcommand*\footrulewidth{}%
4 \newcommand{\headstrutheight}{}%
5 \newcommand{\footstrutheight}{}%
6 \newcommand*\headrule{}%
7 \newcommand*\footrule{}%
8
9 \newdimen\headwidth
10 \newcommand*\extendedheaders{}
```

---

```

11 \newcommand*{\normalheaders}{}
12
13 \newcommand*{\fancyhead}[2][]{}
14 \newcommand*{\fancyfoot}[2][]{}
15 \newcommand*{\fancyhf}[2][]{}
16 \newcommand*{\fancypagestyle}[2]{}
17 \newcommand*{\lhead}[2][]{}
18 \newcommand*{\chead}[2][]{}
19 \newcommand*{\rhead}[2][]{}
20 \newcommand*{\lfoot}[2][]{}
21 \newcommand*{\cfoot}[2][]{}
22 \newcommand*{\rfoot}[2][]{}
23
24 \newcommand{\nouppercase}[1]{#1}
25
26 \NewDocumentCommand{\fancycenter}{o o m m m}{}
27
28 \NewDocumentCommand{\newpagestyle}{m o m}{}
29
30 \newcommand*{\iffloatpage}[2]{#2}
31 \newcommand*{\ifftopfloat}[2]{#2}
32 \newcommand*{\iffbotfloat}[2]{#2}

```

---

#### File 266 **l warp-nccmath.sty**

### § 366 Package **nccmath**

*(Emulates or patches code by ALEXANDER I. ROZHENKO.)*

Pkg nccmath nccmath is patched for use by l warp, and emulated for MATHJAX.

for HTML output:

```

1 \LWR@ProvidesPackagePass{nccmath}[2006/01/20]

2 \let\LWR@origeqnarray\eqnarray
3 \let\LWR@origendeqnarray\endeqnarray
4
5 \csletcs{\LWR@origeqnarraystar}{eqnarray*}
6 \csletcs{\LWR@origendeqnarraystar}{endeqnarray*}
7
8 \RenewEnviron{eqnarray}
9 {%
10   \LWR@eqnarrayfactor
11 }
12
13 }
14
15 \RenewEnviron{eqnarray*}
16 {%
17
18   \begingroup
19   \csletcs{\LWR@origeqnarray}{\LWR@origeqnarraystar}
20   \csletcs{\LWR@origendeqnarray}{\LWR@origendeqnarraystar}
21   \boolfalse{\LWR@numbereqnarray}

```

```

22     \LWR@eqnarrayfactor
23     \endgroup
24
25 }
26
27 \def\eqs{%
28     @ifstar{\LWR@nccmath@eqsstar}{\LWR@nccmath@eqs}%
29 }
30 \newcommand*{\LWR@nccmath@eqsstar}[2][]{\begin{eqnarray*}#2\end{eqnarray*}}
31 \newcommand*{\LWR@nccmath@eqs}[2][]{\begin{eqnarray}#2\end{eqnarray}}
32
33 \begin{warpMathJax}
34 \CustomizeMathJax{\renewcommand{\intertext}[2][]{\text{\#2}\notag}}
35 \CustomizeMathJax{\newenvironment{fleqn}[1]{}{}}
36 \CustomizeMathJax{\newenvironment{ceqn}{}{}}
37 \CustomizeMathJax{\newenvironment{darray}[2][c]{\begin{array}{#1}{#2}}{\end{array}}}
38 \CustomizeMathJax{\newcommand{\dmulticolumn}[3]{#3}}
39 \CustomizeMathJax{\newcommand{\nr}{\text{.5ex}}}
40 \CustomizeMathJax{\newcommand{\mrel}[1]{\begin{aligned}#1\end{aligned}}}
41 \CustomizeMathJax{\newcommand{\underrel}[2]{\#1_{\#2}}}
42 \CustomizeMathJax{\newcommand{\medmath}[1]{#1}}
43 \CustomizeMathJax{\newcommand{\medop}[1]{#1}}
44 \CustomizeMathJax{\newcommand{\medint}[1]{#1}}
45 \CustomizeMathJax{\newcommand{\medintcorr}[1]{#1}}
46 \CustomizeMathJax{\newcommand{\mfrac}[2]{\frac{#1}{#2}}}
47 \CustomizeMathJax{\newcommand{\mbinom}[2]{\binom{#1}{#2}}}
48 \newenvironment{mmatrix}{\begin{matrix}}{\end{matrix}}
49 \end{warpMathJax}

```

File 267 **lwarf-needspace.sty**

§ 367 Package **needspace**

*(Emulates or patches code by PETER WILSON.)*

Pkg    needspace    needspace is ignored.

**for HTML output:** Discard all options for lwarpc-needspace:

```
1 \LWR@ProvidesPackageDrop{needspace}[2010/09/12]
2
3 \DeclareDocumentCommand{\needspace}{m}{}
4 \DeclareDocumentCommand{\Needspace}{s m}{}
```

## File 268 **lwarf-nextpage.sty**

§ 368 Package **nextpage**

*(Emulates or patches code by PETER WILSON.)*

Pkg nextpage nextpage is ignored.

**for HTML output:** Discard all options for `\l warp-nexpage`.

```
1 \LWR@ProvidesPackageDrop{nexpage}[2009/09/03]

2 \DeclareDocumentCommand{\cleartoevenpage}{o}{}%
3 \DeclareDocumentCommand{\movetoevenpage}{o}{}%
4 \DeclareDocumentCommand{\cleartooddpage}{o}{}%
5 \DeclareDocumentCommand{\movetooddpage}{o}{}%
```

---

### File 269 **l warp-nfsext-cfr.sty**

§ 369      Package **nfsext-cfr**

*(Emulates or patches code by CLEA F. REES.)*

Pkg `nfsext-cfr` `nfsext-cfr` is emulated in `HTML`, and used as-is in print output.

Results depend on the browser's font.

**for HTML output:** `1 \LWR@ProvidesPackagePass{nfsext-cfr}[2017/03/28]`

Macros which are present in the `l warp` core are commented out here.

```
2 \newrobustcmd{\LWR@HTML@lnstyle}{}%
3 \newrobustcmd{\LWR@HTML@osstyle}{}%
4 \newrobustcmd{\LWR@HTML@instyle}{}%
5 \newrobustcmd{\LWR@HTML@sustyle}{}%
6 \newrobustcmd{\LWR@HTML@swstyle}{}%
7 \newrobustcmd{\LWR@HTML@pstyle}{}%
8 \newrobustcmd{\LWR@HTML@tistyle}{}%
9 \newrobustcmd{\LWR@HTML@ostyle}{\LWR@HTML@scshape}%
10 \newrobustcmd{\LWR@HTML@postyle}{\LWR@HTML@scshape}%
11 \newrobustcmd{\LWR@HTML@ltstyle}{}%
12 \newrobustcmd{\LWR@HTML@ofstyle}{}%
13 \newrobustcmd{\LWR@HTML@altstyle}{}%
14 \newrobustcmd{\LWR@HTML@regstyle}{}%
15 \newrobustcmd{\LWR@HTML@embossstyle}{}%
16 \newrobustcmd{\LWR@HTML@ornamentalstyle}{}%
17 \newrobustcmd{\LWR@HTML@qtstyle}{}%
18 \newrobustcmd{\LWR@HTML@shstyle}{}%
19 \newrobustcmd{\LWR@HTML@swashstyle}{}%
20 \newrobustcmd{\LWR@HTML@tmstyle}{}%
21 \newrobustcmd{\LWR@HTML@tvstyle}{\renewcommand*\LWR@f@family{tt}}%
22 \newrobustcmd{\LWR@HTML@tstyle}{}%
23 \newrobustcmd{\LWR@HTML@lstyle}{}%
24 \newrobustcmd{\LWR@HTML@tlstyle}{}%
25 \newrobustcmd{\LWR@HTML@plstyle}{}%
26 \newrobustcmd{\LWR@HTML@tostyle}{\LWR@HTML@scshape}%
27 % \newrobustcmd{\LWR@HTML@sishape}{}%
28 \newrobustcmd{\LWR@HTML@olshape}{}%
29 \newrobustcmd{\LWR@HTML@scolshape}{}%
30 \newrobustcmd{\LWR@HTML@ushape}{}%
```

```
31 \newrobustcmd{\LWR@HTML@scushape}{}  
32 \newrobustcmd{\LWR@HTML@uishape}{\LWR@HTML@itshape}  
33 \newrobustcmd{\LWR@HTML@rishape}{}  
34 \newrobustcmd{\LWR@HTML@regwidth}{}  
35 \newrobustcmd{\LWR@HTML@nwwidth}{}  
36 \newrobustcmd{\LWR@HTML@cdwidth}{}  
37 \newrobustcmd{\LWR@HTML@ecwidth}{}  
38 \newrobustcmd{\LWR@HTML@ucwidth}{}  
39 \newrobustcmd{\LWR@HTML@etwidth}{}  
40 \newrobustcmd{\LWR@HTML@epwidth}{}  
41 \newrobustcmd{\LWR@HTML@exwidth}{}  
42 \newrobustcmd{\LWR@HTML@uxwidth}{}  
43 \newrobustcmd{\LWR@HTML@mbweight}{\renewcommand*{\LWR@f@series}{md}}  
44 \newrobustcmd{\LWR@HTML@dbweight}{\renewcommand*{\LWR@f@series}{bf}}  
45 \newrobustcmd{\LWR@HTML@sbweight}{\renewcommand*{\LWR@f@series}{bf}}  
46 % \newrobustcmd{\LWR@HTML@ebweight}{\renewcommand*{\LWR@f@series}{eb}}  
47 \newrobustcmd{\LWR@HTML@ubweight}{\renewcommand*{\LWR@f@series}{eb}}  
48 % \newrobustcmd{\LWR@HTML@lgweight}{\renewcommand*{\LWR@f@series}{lg}}  
49 \newrobustcmd{\LWR@HTML@elweight}{\renewcommand*{\LWR@f@series}{lg}}  
50 \newrobustcmd{\LWR@HTML@ulweight}{\renewcommand*{\LWR@f@series}{lg}}  
51 % \newrobustcmd{\LWR@HTML@itshape}{}  
52 % \newrobustcmd{\LWR@HTML@scshape}{}  
53 % \newrobustcmd{\LWR@HTML@upshape}{}  
54 \newrobustcmd{\LWR@HTML@dfshape}{}  
55  
56 \ifdef{\LWR@HTML@swshape}{}% duplicated by fontaxes  
57     \newrobustcmd{\LWR@HTML@swshape}{}  
58 }  
59  
60 \newrobustcmd{\LWR@HTML@ornament}[1]{}  
61  
62 \LWR@formatted{lnstyle}  
63 \LWR@formatted{osstyle}  
64 \LWR@formatted{instyle}  
65 \LWR@formatted{sustyle}  
66 \LWR@formatted{swstyle}  
67 \LWR@formatted{pstyle}  
68 \LWR@formatted{tistyle}  
69 \LWR@formatted{ostyle}  
70 \LWR@formatted{postyle}  
71 \LWR@formatted{ltstyle}  
72 \LWR@formatted{ofstyle}  
73 \LWR@formatted{altstyle}  
74 \LWR@formatted{regstyle}  
75 \LWR@formatted{embossstyle}  
76 \LWR@formatted{ornamentalstyle}  
77 \LWR@formatted{qtstyle}  
78 \LWR@formatted{shstyle}  
79 \LWR@formatted{swashstyle}  
80 \LWR@formatted{tmstyle}  
81 \LWR@formatted{tvstyle}  
82 \LWR@formatted{tstyle}  
83 \LWR@formatted{lstyle}  
84 \LWR@formatted{tlstyle}  
85 \LWR@formatted{plstyle}
```

```
86 \LWR@formatted{tostyle}
87 % \LWR@formatted{sishape}
88 \LWR@formatted{olshape}
89 \LWR@formatted{scolshape}
90 \LWR@formatted{ushape}
91 \LWR@formatted{scushape}
92 \LWR@formatted{uishape}
93 \LWR@formatted{rishape}
94 \LWR@formatted{regwidth}
95 \LWR@formatted{newidth}
96 \LWR@formatted{cdwidth}
97 \LWR@formatted{ecwidth}
98 \LWR@formatted{ucwidth}
99 \LWR@formatted{etwidth}
100 \LWR@formatted{epwidth}
101 \LWR@formatted{exwidth}
102 \LWR@formatted{uxwidth}
103 \LWR@formatted{mbweight}
104 \LWR@formatted{dbweight}
105 \LWR@formatted{sbweight}
106 % \LWR@formatted{ebweight}
107 \LWR@formatted{ubweight}
108 % \LWR@formatted{lgweight}
109 \LWR@formatted{elweight}
110 \LWR@formatted{ulweight}
111 % \LWR@formatted{itshape}
112 % \LWR@formatted{scshape}
113 % \LWR@formatted{upshape}
114 \LWR@formatted{dfshape}
115
116 \ifdef{\LWR@HTML@swshape}{}% duplicated by fontaxes
117     \LWR@formatted{swshape}
118 }
119
120 \LWR@formatted{ornament}
121
122
123 \newcommand{\LWR@null@lnstyle}{}
124 \newcommand{\LWR@null@osstyle}{}
125 \newcommand{\LWR@null@instyle}{}
126 \newcommand{\LWR@null@sustyle}{}
127 \newcommand{\LWR@null@swstyle}{}
128 \newcommand{\LWR@null@pststyle}{}
129 \newcommand{\LWR@null@tistyle}{}
130 \newcommand{\LWR@null@ostyle}{}
131 \newcommand{\LWR@null@postyle}{}
132 \newcommand{\LWR@null@ltstyle}{}
133 \newcommand{\LWR@null@ofstyle}{}
134 \newcommand{\LWR@null@altstyle}{}
135 \newcommand{\LWR@null@regstyle}{}
136 \newcommand{\LWR@null@embossstyle}{}
137 \newcommand{\LWR@null@ornamentalstyle}{}
138 \newcommand{\LWR@null@qtstyle}{}
139 \newcommand{\LWR@null@shstyle}{}
140 \newcommand{\LWR@null@swashstyle}{}
```

```
141 \newcommand{\LWR@null@tmstyle}{}  
142 \newcommand{\LWR@null@tvstyle}{}  
143 \newcommand{\LWR@null@tstyle}{}  
144 \newcommand{\LWR@null@lstyle}{}  
145 \newcommand{\LWR@null@tlstyle}{}  
146 \newcommand{\LWR@null@plstyle}{}  
147 \newcommand{\LWR@null@tostyle}{}  
148 % \newcommand{\LWR@null@sishape}{}  
149 \newcommand{\LWR@null@olshape}{}  
150 \newcommand{\LWR@null@scolshape}{}  
151 \newcommand{\LWR@null@ushape}{}  
152 \newcommand{\LWR@null@scushape}{}  
153 \newcommand{\LWR@null@uishape}{}  
154 \newcommand{\LWR@null@rishape}{}  
155 \newcommand{\LWR@null@regwidth}{}  
156 \newcommand{\LWR@null@nwwidth}{}  
157 \newcommand{\LWR@null@cdwidth}{}  
158 \newcommand{\LWR@null@ecwidth}{}  
159 \newcommand{\LWR@null@ucwidth}{}  
160 \newcommand{\LWR@null@etwidth}{}  
161 \newcommand{\LWR@null@epwidth}{}  
162 \newcommand{\LWR@null@exwidth}{}  
163 \newcommand{\LWR@null@uxwidth}{}  
164 \newcommand{\LWR@null@mbweight}{}  
165 \newcommand{\LWR@null@dbweight}{}  
166 \newcommand{\LWR@null@sbweight}{}  
167 % \newcommand{\LWR@null@ebweight}{}  
168 \newcommand{\LWR@null@ubweight}{}  
169 % \newcommand{\LWR@null@lgweight}{}  
170 \newcommand{\LWR@null@elweight}{}  
171 \newcommand{\LWR@null@ulweight}{}  
172 % \newcommand{\LWR@null@itshape}{}  
173 % \newcommand{\LWR@null@scshape}{}  
174 % \newcommand{\LWR@null@upshape}{}  
175 \newcommand{\LWR@null@dfshape}{}  
176  
177 \ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes  
178     \newcommand{\LWR@null@swshape}{}  
179 }  
180  
181 \newcommand{\LWR@null@ornament}[1]{}  
182  
183 \appto{\LWR@nullfonts}{%  
184 \LetLtxMacro{\lnstyle}{\LWR@null@lnstyle}%  
185 \LetLtxMacro{\osstyle}{\LWR@null@osstyle}%  
186 \LetLtxMacro{\instyle}{\LWR@null@instyle}%  
187 \LetLtxMacro{\sustyle}{\LWR@null@sustyle}%  
188 \LetLtxMacro{\swstyle}{\LWR@null@swstyle}%  
189 \LetLtxMacro{\pstyle}{\LWR@null@pstyle}%  
190 \LetLtxMacro{\tistyle}{\LWR@null@tistyle}%  
191 \LetLtxMacro{\ostyle}{\LWR@null@ostyle}%  
192 \LetLtxMacro{\postyle}{\LWR@null@postyle}%  
193 \LetLtxMacro{\ltstyle}{\LWR@null@ltstyle}%  
194 \LetLtxMacro{\ofstyle}{\LWR@null@ofstyle}%  
195 \LetLtxMacro{\altstyle}{\LWR@null@altstyle}%
```

```
196 \LetLtxMacro\regstyle\LWR@null@regstyle%
197 \LetLtxMacro\embossstyle\LWR@null@embossstyle%
198 \LetLtxMacro\ornamentalstyle\LWR@null@ornamentalstyle%
199 \LetLtxMacro\qtstyle\LWR@null@qtstyle%
200 \LetLtxMacro\shstyle\LWR@null@shstyle%
201 \LetLtxMacro\swashstyle\LWR@null@swashstyle%
202 \LetLtxMacro\tmstyle\LWR@null@tmstyle%
203 \LetLtxMacro\tvstyle\LWR@null@tvstyle%
204 \LetLtxMacro\tsstyle\LWR@null@tsstyle%
205 \LetLtxMacro\lstyle\LWR@null@lstyle%
206 \LetLtxMacro\tlstyle\LWR@null@tlstyle%
207 \LetLtxMacro\plstyle\LWR@null@plstyle%
208 \LetLtxMacro\tostyle\LWR@null@tostyle%
209 % \LetLtxMacro\sishape\LWR@null@sishape%
210 \LetLtxMacro\olshape\LWR@null@olshape%
211 \LetLtxMacro\scolshape\LWR@null@scolshape%
212 \LetLtxMacro\ushape\LWR@null@ushape%
213 \LetLtxMacro\scushape\LWR@null@scushape%
214 \LetLtxMacro\uishape\LWR@null@uishape%
215 \LetLtxMacro\rishape\LWR@null@rishape%
216 \LetLtxMacro\regwidth\LWR@null@regwidth%
217 \LetLtxMacro\newidth\LWR@null@newidth%
218 \LetLtxMacro\cdwidth\LWR@null@cdwidth%
219 \LetLtxMacro\ecwidth\LWR@null@ecwidth%
220 \LetLtxMacro\ucwidth\LWR@null@ucwidth%
221 \LetLtxMacro\etwidth\LWR@null@etwidth%
222 \LetLtxMacro\epwidth\LWR@null@epwidth%
223 \LetLtxMacro\exwidth\LWR@null@exwidth%
224 \LetLtxMacro\uxwidth\LWR@null@uxwidth%
225 \LetLtxMacro\mbweight\LWR@null@mbweight%
226 \LetLtxMacro\dbweight\LWR@null@dbweight%
227 \LetLtxMacro\sbweight\LWR@null@sbweight%
228 % \LetLtxMacro\ebweight\LWR@null@ebweight%
229 \LetLtxMacro\ubweight\LWR@null@ubweight%
230 % \LetLtxMacro\lgweight\LWR@null@lgweight%
231 \LetLtxMacro\elweight\LWR@null@elweight%
232 \LetLtxMacro\ulweight\LWR@null@ulweight%
233 % \LetLtxMacro\itshape\LWR@null@itshape%
234 % \LetLtxMacro\scshape\LWR@null@scshape%
235 % \LetLtxMacro\upshape\LWR@null@upshape%
236 \LetLtxMacro\dfshape\LWR@null@dfshape%
237 \LetLtxMacro\swshape\LWR@null@swshape%
238 \LetLtxMacro\ornament\LWR@null@ornament%
239 }
240
241 \newrobustcmd{\LWR@HTML@textln}[1]{#1}
242 \newrobustcmd{\LWR@HTML@textos}[1]{\textsc{#1}}
243 \newrobustcmd{\LWR@HTML@textin}[1]{#1}
244 \newrobustcmd{\LWR@HTML@textsru}[1]{#1}
245 % \newrobustcmd{\LWR@HTML@textsri}[1]{#1}
246 \newrobustcmd{\LWR@HTML@textdf}[1]{#1}
247
248 \ifdef{\LWR@HTML@swshape}{}{%
249     % duplicated by fontaxes
250     \newrobustcmd{\LWR@HTML@textsw}[1]{#1}
251 }
```

```
251
252 \newrobustcmd{\LWR@HTML@textti}[1]{#1}
253 \newrobustcmd{\LWR@HTML@textlt}[1]{#1}
254 \newrobustcmd{\LWR@HTML@textof}[1]{#1}
255 \newrobustcmd{\LWR@HTML@textalt}[1]{#1}
256 \newrobustcmd{\LWR@HTML@textreg}[1]{#1}
257 \newrobustcmd{\LWR@HTML@emboss}[1]{#1}
258 \newrobustcmd{\LWR@HTML@textorn}[1]{#1}
259 \newrobustcmd{\LWR@HTML@textqt}[1]{#1}
260 \newrobustcmd{\LWR@HTML@textsh}[1]{#1}
261 \newrobustcmd{\LWR@HTML@texttm}[1]{#1}
262 \newrobustcmd{\LWR@HTML@texttv}[1]{\texttt{#1}}
263 \newrobustcmd{\LWR@HTML@textl}[1]{#1}
264 \newrobustcmd{\LWR@HTML@texto}[1]{#1}
265 \newrobustcmd{\LWR@HTML@textp}[1]{#1}
266 \newrobustcmd{\LWR@HTML@textt}[1]{#1}
267 \newrobustcmd{\LWR@HTML@textpl}[1]{#1}
268 \newrobustcmd{\LWR@HTML@textpo}[1]{\textsc{#1}}
269 \newrobustcmd{\LWR@HTML@texttl}[1]{#1}
270 \newrobustcmd{\LWR@HTML@textto}[1]{\textsc{#1}}
271 \newrobustcmd{\LWR@HTML@textol}[1]{#1}
272 \newrobustcmd{\LWR@HTML@textwash}[1]{#1}
273 \newrobustcmd{\LWR@HTML@textu}[1]{#1}
274 \newrobustcmd{\LWR@HTML@textscu}[1]{#1}
275 \newrobustcmd{\LWR@HTML@textui}[1]{\LWR@HTML@textit{#1}}
276 \newrobustcmd{\LWR@HTML@textri}[1]{#1}
277 \newrobustcmd{\LWR@HTML@textnw}[1]{#1}
278 \newrobustcmd{\LWR@HTML@textcd}[1]{#1}
279 \newrobustcmd{\LWR@HTML@textec}[1]{#1}
280 \newrobustcmd{\LWR@HTML@textuc}[1]{#1}
281 \newrobustcmd{\LWR@HTML@texttet}[1]{#1}
282 \newrobustcmd{\LWR@HTML@textep}[1]{#1}
283 \newrobustcmd{\LWR@HTML@textex}[1]{#1}
284 \newrobustcmd{\LWR@HTML@textux}[1]{#1}
285 \newrobustcmd{\LWR@HTML@textrw}[1]{#1}
286 \newrobustcmd{\LWR@HTML@textmb}[1]{\textmd{#1}}
287 \newrobustcmd{\LWR@HTML@textdb}[1]{\textbf{#1}}
288 \newrobustcmd{\LWR@HTML@texts}{\textbf{#1}}
289 % \newrobustcmd{\LWR@HTML@texteb}[1]{#1}
290 \newrobustcmd{\LWR@HTML@textub}[1]{\textbf{#1}}
291 % \newrobustcmd{\LWR@HTML@textlg}[1]{#1}
292 \newrobustcmd{\LWR@HTML@textel}[1]{\textbf{#1}}
293 \newrobustcmd{\LWR@HTML@textul}[1]{\textbf{#1}}
294
295 \LWR@formatted{textln}
296 \LWR@formatted{textos}
297 \LWR@formatted{textin}
298 \LWR@formatted{textsu}
299 % \LWR@formatted{textsi}
300 \LWR@formatted{textdf}
301 \LWR@formatted{textsw}
302 \LWR@formatted{textti}
303 \LWR@formatted{textlt}
304 \LWR@formatted{textof}
305 \LWR@formatted{textalt}
```

```
306 \LWR@formatted{textreg}
307 \LWR@formatted{emboss}
308 \LWR@formatted{textorn}
309 \LWR@formatted{textqt}
310 \LWR@formatted{textsh}
311 \LWR@formatted{texttm}
312 \LWR@formatted{texttv}
313 \LWR@formatted{textl}
314 \LWR@formatted{texto}
315 \LWR@formatted{textp}
316 \LWR@formatted{textt}
317 \LWR@formatted{textpl}
318 \LWR@formatted{textpo}
319 \LWR@formatted{texttl}
320 \LWR@formatted{textto}
321 \LWR@formatted{textol}
322 \LWR@formatted{textwash}
323 \LWR@formatted{textu}
324 \LWR@formatted{textscu}
325 \LWR@formatted{textui}
326 \LWR@formatted{textri}
327 \LWR@formatted{textnw}
328 \LWR@formatted{textcd}
329 \LWR@formatted{textec}
330 \LWR@formatted{textuc}
331 \LWR@formatted{texttet}
332 \LWR@formatted{texttep}
333 \LWR@formatted{texttex}
334 \LWR@formatted{texttux}
335 \LWR@formatted{textrw}
336 \LWR@formatted{textmb}
337 \LWR@formatted{textdb}
338 \LWR@formatted{textsb}
339 % \LWR@formatted{texteb}
340 \LWR@formatted{textub}
341 % \LWR@formatted{textlg}
342 \LWR@formatted{textel}
343 \LWR@formatted{textul}
344
345 \newrobustcmd{\LWR@null@textln}[1]{#1}
346 \newrobustcmd{\LWR@null@textos}[1]{#1}
347 \newrobustcmd{\LWR@null@textin}[1]{#1}
348 \newrobustcmd{\LWR@null@textsu}[1]{#1}
349 % \newrobustcmd{\LWR@null@textsii}[1]{#1}
350 \newrobustcmd{\LWR@null@textdf}[1]{#1}
351
352 \ifdef{\LWR@HTML@swshape}{}{\% duplicated by fontaxes
353     \newrobustcmd{\LWR@null@textsw}[1]{#1}
354 }
355
356 \newrobustcmd{\LWR@null@textti}[1]{#1}
357 \newrobustcmd{\LWR@null@textlt}[1]{#1}
358 \newrobustcmd{\LWR@null@textof}[1]{#1}
359 \newrobustcmd{\LWR@null@textalt}[1]{#1}
360 \newrobustcmd{\LWR@null@textreg}[1]{#1}
```

```
361 \newrobustcmd{\LWR@null@emboss}[1]{#1}
362 \newrobustcmd{\LWR@null@textorn}[1]{#1}
363 \newrobustcmd{\LWR@null@textqt}[1]{#1}
364 \newrobustcmd{\LWR@null@textsh}[1]{#1}
365 \newrobustcmd{\LWR@null@texttm}[1]{#1}
366 \newrobustcmd{\LWR@null@texttv}[1]{#1}
367 \newrobustcmd{\LWR@null@textl}[1]{#1}
368 \newrobustcmd{\LWR@null@texto}[1]{#1}
369 \newrobustcmd{\LWR@null@textp}[1]{#1}
370 \newrobustcmd{\LWR@null@textt}[1]{#1}
371 \newrobustcmd{\LWR@null@textpl}[1]{#1}
372 \newrobustcmd{\LWR@null@textpo}[1]{#1}
373 \newrobustcmd{\LWR@null@texttl}[1]{#1}
374 \newrobustcmd{\LWR@null@textto}[1]{#1}
375 \newrobustcmd{\LWR@null@textol}[1]{#1}
376 \newrobustcmd{\LWR@null@textwash}[1]{#1}
377 \newrobustcmd{\LWR@null@textu}[1]{#1}
378 \newrobustcmd{\LWR@null@textscu}[1]{#1}
379 \newrobustcmd{\LWR@null@textui}[1]{#1}
380 \newrobustcmd{\LWR@null@textri}[1]{#1}
381 \newrobustcmd{\LWR@null@textnw}[1]{#1}
382 \newrobustcmd{\LWR@null@textcd}[1]{#1}
383 \newrobustcmd{\LWR@null@textec}[1]{#1}
384 \newrobustcmd{\LWR@null@textuc}[1]{#1}
385 \newrobustcmd{\LWR@null@textet}[1]{#1}
386 \newrobustcmd{\LWR@null@textep}[1]{#1}
387 \newrobustcmd{\LWR@null@textex}[1]{#1}
388 \newrobustcmd{\LWR@null@textux}[1]{#1}
389 \newrobustcmd{\LWR@null@textrw}[1]{#1}
390 \newrobustcmd{\LWR@null@textmb}[1]{#1}
391 \newrobustcmd{\LWR@null@textdb}[1]{#1}
392 \newrobustcmd{\LWR@null@texts}{[1]{#1}}
393 % \newrobustcmd{\LWR@null@texteb}[1]{#1}
394 \newrobustcmd{\LWR@null@textub}[1]{#1}
395 % \newrobustcmd{\LWR@null@textlg}[1]{#1}
396 \newrobustcmd{\LWR@null@textel}[1]{#1}
397 \newrobustcmd{\LWR@null@textul}[1]{#1}
398
399 \appto{\LWR@nullfonts}{%
400 \LetLtxMacro{textln}{\LWR@null@textln}%
401 \LetLtxMacro{textos}{\LWR@null@textos}%
402 \LetLtxMacro{textin}{\LWR@null@textin}%
403 \LetLtxMacro{textsu}{\LWR@null@textsu}%
404 % \LetLtxMacro{textsi}{\LWR@null@textsi}%
405 \LetLtxMacro{textdf}{\LWR@null@textdf}%
406 \LetLtxMacro{textsw}{\LWR@null@textsw}%
407 \LetLtxMacro{textti}{\LWR@null@textti}%
408 \LetLtxMacro{textlt}{\LWR@null@textlt}%
409 \LetLtxMacro{textof}{\LWR@null@textof}%
410 \LetLtxMacro{textalt}{\LWR@null@textalt}%
411 \LetLtxMacro{textreg}{\LWR@null@textreg}%
412 \LetLtxMacro{emboss}{\LWR@null@emboss}%
413 \LetLtxMacro{textorn}{\LWR@null@textorn}%
414 \LetLtxMacro{textqt}{\LWR@null@textqt}%
415 \LetLtxMacro{textsh}{\LWR@null@textsh}%
```

---

```

416 \LetLtxMacro\texttm\LWR@null@texttm%
417 \LetLtxMacro\texttv\LWR@null@texttv%
418 \LetLtxMacro\textl\LWR@null@textl%
419 \LetLtxMacro\texto\LWR@null@texto%
420 \LetLtxMacro\textp\LWR@null@textp%
421 \LetLtxMacro\textt\LWR@null@textt%
422 \LetLtxMacro\textpl\LWR@null@textpl%
423 \LetLtxMacro\textpo\LWR@null@textpo%
424 \LetLtxMacro\texttl\LWR@null@texttl%
425 \LetLtxMacro\textto\LWR@null@textto%
426 \LetLtxMacro\textol\LWR@null@textol%
427 \LetLtxMacro\textwash\LWR@null@textwash%
428 \LetLtxMacro\textu\LWR@null@textu%
429 \LetLtxMacro\textscu\LWR@null@textscu%
430 \LetLtxMacro\textui\LWR@null@textui%
431 \LetLtxMacro\texttri\LWR@null@texttri%
432 \LetLtxMacro\textnw\LWR@null@textnw%
433 \LetLtxMacro\textcd\LWR@null@textcd%
434 \LetLtxMacro\textec\LWR@null@textec%
435 \LetLtxMacro\textuc\LWR@null@textuc%
436 \LetLtxMacro\textet\LWR@null@textet%
437 \LetLtxMacro\textep\LWR@null@textep%
438 \LetLtxMacro\textex\LWR@null@textex%
439 \LetLtxMacro\textux\LWR@null@textux%
440 \LetLtxMacro\textrw\LWR@null@textrw%
441 \LetLtxMacro\textmb\LWR@null@textmb%
442 \LetLtxMacro\textdb\LWR@null@textdb%
443 \LetLtxMacro\textsb\LWR@null@textsb%
444 % \LetLtxMacro\texteb\LWR@null@texteb%
445 \LetLtxMacro\textub\LWR@null@textub%
446 % \LetLtxMacro\textlg\LWR@null@textlg%
447 \LetLtxMacro\textel\LWR@null@textel%
448 \LetLtxMacro\textul\LWR@null@textul%
449 }
450
451 \providecommand*\{zeroslash}{0}
452 \newrobustcmd*\{\LWR@HTML@zeroslash}{0}
453 \LWR@formatted{zeroslash}

```

---

### File 270 l warp-nicefrac.sty

§ 370 Package **nicefrac**

(Emulates or patches code by AXEL REICHERT.)

Pkg nicefrac nicefrac is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{nicefrac}[1998/08/04]

```

2 \DeclareRobustCommand*\{\LWR@HTML@@UnitsNiceFrac}[3][]{%
3   {% localize font selection
4     #1{%
5       \LWR@textcurrentfont{%

```

```

6           \InlineClass{numerator}{#2}%
7           /%
8           \InlineClass{denominator}{#3}%
9       }%
10      }%
11      }%
12 }
13
14 \LWR@formatted{@UnitsNiceFrac}
15
16 \DeclareRobustCommand*\LWR@HTML@UnitsUglyFrac}[3][]{%
17   {% localize font selection
18     #1{\LWR@textcurrentfont{#2/#3}}%
19   }%
20 }
21
22 \LWR@formatted{@UnitsUglyFrac}

```

For Mathjax:

```

23 \begin{warpMathJax}
24 \CustomizeMathJax{\newcommand{\nicefrac}[3][]{{#2/#3}}}
25 \end{warpMathJax}

```

### File 271 lwarp-niceframe.sty

## § 371 Package niceframe

Pkg niceframe niceframe is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{niceframe}% the original date is in yyyy/dd/mm format

```

2 \newcommand{\LWR@niceframe}[3]{%
3   \begin{\LWR@setvirtualpage}*%
4   \setlength{\LWR@templengthone}{#1}%
5   \begin{BlockClass}[max-width:\LWR@printlength{\LWR@templengthone}]{#3}%
6   #2
7   \end{BlockClass}%
8   \end{\LWR@setvirtualpage}%
9 }
10
11 \newcommand{\niceframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{niceframe}}
12 \newcommand{\curlyframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{curlyframe}}
13 \newcommand{\artdecoframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{artdecoframe}}
14
15 \newcommand{\generalframe}[9]{\LWR@niceframe{\textwidth}{#9}{generalframe}}

```

---

**File 272 l warp-noitcru l .sty****§ 372 Package noitcru l**

(Emulates or patches code by PAUL EBERMANN.)

Pkg noitcru l noitcru l is used as-is for SVG and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{noitcru l}[2006/04/11]

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\noitUnderline}[1]{\underline{\#1}!}}
4 \end{warpMathJax}
```

---

**File 273 l warp-nomencl .sty****§ 373 Package nomencl**

(Emulates or patches code by BORIS VEYTSMAN, BERND SCHANDL, LEE NETHERTON, CV RADHAKRISHNAN.)

Pkg nomencl nomencl is patched for use by l warp.

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.list -o <project>_html.nls
```

**for HTML output:** 1 \LWR@ProvidesPackagePass{nomencl}[2005/09/22]

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
2 \def\@@nomenclature[#1]#2#3{%
3   \def\@tempa{#2}\def\@tempb{#3}%
4   \protected@write\@nomenclaturefile{}{%
5     \string\nomenclatureentry{\#1\@tempa\@tempb}%
6     \begingroup\@tempa\@tempb\protect\nomeref{\theequation}%
7     |nompageref|{\theLWR@previousautopagelabel}}% l warp
8   \endgroup
9   \esphack}%
10
11 \renewcommand*\pagedeclaration[1]{, \nameref{\BaseJobname-autopage-\#1}}%
```

---

**File 274 l warp-nonfloat .sty****§ 374 Package nonfloat**

(Emulates or patches code by KAI RASCHER.)

Pkg nonfloat nonfloat is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{nonfloat}[1999/07/05]

```
2 \LetLtxMacro\topcaption\caption
3 \newcommand{\figcaption}{\def\@cattyp{figure}\caption}
4 \newcommand{\tabcaption}{\def\@cattyp{table}\topcaption}
5 \newenvironment{narrow}[2]{}{}
```

---

File 275 **l warp-nonumonpart.sty**

§ 375 Package **nonumonpart**

Pkg nonumonpart nonumonpart is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nonumonpart}[2011/04/15]

---

File 276 **l warp-nopageno.sty**

§ 376 Package **nopageno**

Pkg nopageno nopageno is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nopageno}[1989/01/01]

---

File 277 **l warp-notes.sty**

§ 377 Package **notes**

Pkg notes notes is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{notes}[2002/10/29]

```
2 \newcommand*\LWR@notes@onenote[2]{%
3 \newenvironment{#1}
4   {
5     \BlockClass{notes#1}
6     \begin{BlockClass}{notesicon}\textcircled{~#2~}\end{BlockClass}
7     \BlockClass{notescontents}
8   }
9   {\endBlockClass\endBlockClass}
10 }
11
12 \LWR@notes@onenote{importantnote}{!}
13
14 \LWR@notes@onenote{warningnote}{--}
15
16 \LWR@notes@onenote{informationnote}{i}
```

## File 278 l warp-notespages.sty

§ 378 Package **notespages**

Pkg notespages notespages is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{notespages}[2016/08/21]

```

2 \newcommand*{\npnotesname}={}
3 \newcommand*{\npnotestext}={}
4 \newcommand*{\remainingtextheight}={}
5 \newdimen\remainingtextheight
6 \newcommand*{\notestitletext}={}
7 \newcommand*{\notesareatext}={}
8 \newcommand*{\npnpinfo}[1]{}
9 \newcommand*{\tracingnpmarks}={}
10 \newcommand*{\notespage}[1][]{}
11 \newcommand*{\notespages}[1][]{}
12 \newcommand*{\notesfill}[1][]{}
13 \newcommand*{\setnotespages}[1]{}
14 \newcommand*{\definenotesoption}[2]{}
15 \newcommand{\definenotesstyle}[2]{}
16 \newcommand{\definetitlestyle}[2]{}
17 \newcommand{\nppatchchapter}[1]{}
18 \newcommand{\npunpatchchapter}{}{}
```

File 279 **l warp-nowidow.sty**

§ 379 Package **nowidow**

*(Emulates or patches code by RAPHAËL PINSON.)*

Pkg nowidow nowidow is ignored.

Discard all options for lwarpc-nwidow:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{nowidow}[2011/09/20]

```
\nowidow      [⟨lines⟩]
\setnowidow   [⟨lines⟩]
                  2 \newcommand*{\nowidow}[1][]{}
                  3 \newcommand*{\setnowidow}[1]{}{}

\noclub       [⟨lines⟩]
\setnoclub    [⟨lines⟩]
```

---

```

4 \newcommand*{\noclub}[1][]{}
5 \newcommand*{\setnoclub}[1][]{}

```

---

File 280 **l warp-ntheorem.sty**

§ 380 Package **ntheorem**

*(Emulates or patches code by WOLFGANG MAY, ANDREAS SCHEDLER.)*

Pkg ntheorem ntheorem is patched for use by l warp.

Table 15: Ntheorem package — css styling of theorems and proofs

**Theorem:** <div> of class theorembody<theoremstyle>

**Theorem Header:** <span> of class theoremheader<style>

where <theoremstyle> is plain, break, etc.

---

§ 380.1 **Limitations**

⚠ **Font control** This conversion is not total. Font control is via css, and the custom L<sup>A</sup>T<sub>E</sub>X font settings are ignored.

⚠ **Equation numbering** ntheorem has a bug with equation numbering in A<sub>M</sub>S environments when the option thref is used. l warp does not share this bug, so equations with \split, etc, are numbered correctly with l warp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's thref option.

§ 380.2 **Options**

Options amsthm or standard choose which set of theorems and proofs to initialize.

⚠ **Disabled options** The options thmarks and amsmath are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option thref is disabled because cleveref functions are used instead. \thref is emulated.

Option hyperref is disabled because l warp emulated hyperref.

**for HTML output:** Some disabled options:

```

1 \DeclareOption{thref}{}
2
3
4 \newbool{LWR@ntheoremmarks}
5 \boolfalse{LWR@ntheoremmarks}
6
7 \DeclareOption{thmarks}{}
8 \booltrue{LWR@ntheoremmarks}

```

```

9 \newif\ifsetendmark\setendmarktrue
10 }
11
12
13 \newbool{LWR@ntheoremamsthm}
14 \boolfalse{LWR@ntheoremamsthm}
15
16 \DeclareOption{amsthm}{\booltrue{LWR@ntheoremamsthm}}
17
18
19 \DeclareOption{amsmath}={}
20 \DeclareOption{hyperref}={}
21
22 \LWR@ProvidesPackagePass{ntheorem}[2011/08/15]
```

### § 380.3 Remembering the theorem style

Storage for the style being used for new theorems.

```

23 \newcommand{\LWR@newtheoremstyle}[plain]

24 \AtBeginDocument{
25 \@ifpackageloaded{cleveref}{
26 \gdef@\thm#1#2#3{%
27   \if@thmmarks
28     \stepcounter{end\InTheoType ctr}%
29   \fi
30   \renewcommand{\InTheoType}{#1}%
31   \if@thmmarks
32     \stepcounter{curr#1ctr}%
33     \setcounter{end#1ctr}{0}%
34   \fi
35   \refstepcounter[#1]{#2}%
36   \theoremprework
37   \LWR@forcenewpage% l warp
38   \BlockClass{\theorembdy#1}\LWR@thisthmstyle% l warp
39   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
40   \ifuse@newframeskips % cf. latex.ltx for topsepadd: \@trivlist
41     \ifthm@inframe
42       \thm@topsep\theoreminframepreskipamount
43       \thm@topsepadd\theoreminframepostskipamount
44     \else
45       \thm@topsep\theorempreskipamount
46       \thm@topsepadd\theorempostskipamount
47     \fi
48   \else% oldframeskips
49     \thm@topsep\theorempreskipamount
50     \thm@topsepadd\theorempostskipamount
51     \ifvmode\advance\thm@topsepadd\partopsep\fi
52   \fi
53   \atopsep\thm@topsep
54   \atopsepadd\thm@topsepadd
55   \advance\linewidth -\theoremindent
56   \advance\linewidth -\theoremparindent
57   \advance\totalleftmargin \theoremindent
```

```

58   \parshape \one \@totallleftmargin \linewidth
59   \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
60 }
61 }% not @ifpackageloaded{cleveref}
62 \gdef\@thm#1#2#3{%
63   \if@thmmarks
64     \stepcounter{end\InTheoType ctr}%
65   \fi
66   \renewcommand{\InTheoType}{#1}%
67   \if@thmmarks
68     \stepcounter{curr#1ctr}%
69     \setcounter{end#1ctr}{0}%
70   \fi
71   \refstepcounter{#2}%
72   \theorem@prework
73   \LWR@forcenewpage% lwrap
74   \BlockClass{\theorembody#1}\LWR@thisthmstyle% lwrap
75   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
76   \ifuse@newframeskips % cf. latex.ltx for topsepadd: \@trivlist
77     \ifthm@inframe
78       \thm@topsep\theoreminframepreskipamount
79       \thm@topsepadd\theoreminframepostskipamount
80     \else
81       \thm@topsep\theorempreskipamount
82       \thm@topsepadd\theorempostskipamount
83     \fi
84   \else% oldframeskips
85     \thm@topsep\theorempreskipamount
86     \thm@topsepadd \theorempostskipamount
87     \ifvmode\advance\thm@topsepadd\partopsep\fi
88   \fi
89   \atopsep\thm@topsep
90   \atopsepadd\thm@topsepadd
91   \advance\linewidth -\theorem@indent
92   \advance\linewidth -\theorem@rightindent
93   \advance\@totallleftmargin \theorem@indent
94   \parshape \one \@totallleftmargin \linewidth
95   \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
96 }
97 }
98 }% AtBeginDocument

```

Patched to remember the style being used for new theorems:

```

99 \gdef\theoremstyle#1{%
100   \@ifundefined{th@#1}{\@warning
101     {Unknown theoremstyle '#1'. Using 'plain'}%
102     \theorem@style{plain}
103     \renewcommand{\LWR@newtheoremstyle}{plain}% lwrap
104     }%
105   {
106     \theorem@style{#1}
107     \renewcommand{\LWR@newtheoremstyle}{#1}% lwrap
108   }
109 }

```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

110
111 \gdef\@xnthm#1#2[#3]{%
112   \ifthm@tempif
113     \csedef{\LWR@thmstyle#1}{\LWR@newtheoremstyle}{% lwarp
114       \expandafter\@ifundefined{c@#1}%
115         {\@definecounter{#1}}{}%
116       \@newctr{#1}[#3]%
117       \expandafter\xdef\csname the#1\endcsname{%
118         \expandafter\noexpand\csname the#3\endcsname \atthmcntersep
119           {\noexpand\csname the\theoremnumbering\endcsname{#1}}}{}%
120       \expandafter\gdef\csname mkheader@#1\endcsname
121         {\csname setparms@#1\endcsname
122           \@thm{#1}{#1}{#2}
123         }%
124       \global\@namedef{end#1}{\@endtheorem}
125     \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{\LWR@thmstyle#1}}}{% lwarp
126   \fi
127 }
128
129 \gdef\@ynthm#1#2{%
130   \ifthm@tempif
131     \csedef{\LWR@thmstyle#1}{\LWR@newtheoremstyle}{% lwarp
132       \expandafter\@ifundefined{c@#1}%
133         {\@definecounter{#1}}{}%
134       \expandafter\xdef\csname the#1\endcsname
135         {\noexpand\csname the\theoremnumbering\endcsname{#1}}}{}%
136       \expandafter\gdef\csname mkheader@#1\endcsname
137         {\csname setparms@#1\endcsname
138           \@thm{#1}{#1}{#2}
139         }%
140       \global\@namedef{end#1}{\@endtheorem}
141     \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{\LWR@thmstyle#1}}}{% lwarp
142   \fi
143 }
144
145 \gdef\@othm[#2]{%
146   \ifundefined{c@#2}{\@nocounterr{#2}}{%
147     \ifthm@tempif
148       \csedef{\LWR@thmstyle#1}{\LWR@newtheoremstyle}{% lwarp
149         \global\@namedef{the#1}{\@nameuse{the#2}}%
150         \expandafter\protected\xdef\csname num@addtheoremline#1\endcsname{%
151           \noexpand\@num@addtheoremline{#1}{#3}}%
152         \expandafter\protected\xdef\csname nonum@addtheoremline#1\endcsname{%
153           \noexpand\@nonum@addtheoremline{#1}{#3}}%
154       \theoremkeyword{#3}%
155       \expandafter\protected\xdef\csname #1Keyword\endcsname
156         {\the\theoremkeyword}%
157       \expandafter\gdef\csname mkheader@#1\endcsname
158         {\csname setparms@#1\endcsname
159           \@thm{#1}{#2}{#3}
160         }%
161       \global\@namedef{end#1}{\@endtheorem}

```

```

162     \AtBeginEnvironment{\#1}{\edef\LWR@thisthmstyle{@nameuse[LWR@thmstyle#1]}% l warp
163     \fi}
164 }
```

#### § 380.4 HTML cross-referencing

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```

165 \newcommand{\LWR@inctheorem}{%
166 \addtocounter{LWR@thisautoid}{1}%
167 \LWR@stoppars%
168 \LWR@htmltag{a id="\LWR@print@obox{autoid-\arabic{LWR@thisautoid}}"\LWR@htmltag{/a}}%
169 \LWR@startpars%
170 }
```

#### § 380.5 \newtheoremstyle

The following are patched for css.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a BlockClass environment of class theorembody<style>.

Each header is encased in an \InlineClass of class theoremheader<style>.

```

171 \gdef\newtheoremstyle#1#2#3{%
172   \expandafter\ifundefined{th@#1}%
173   { \expandafter\gdef\csname th@#1\endcsname{%
174     \def\@begintheorem##1##2{%
175       \LWR@inctheorem% l warp
176       #2%
177       \def\@opargbegintheorem##1##2##3{%
178         \LWR@inctheorem% l warp
179         #3}%
180   }%
181 }%
182 {\PackageError{\basename}{Theorem style #1 already defined}\@eha}%
183 }
```

#### § 380.6 Standard styles

```

184 \renewtheoremstyle{plain}{%
185   {\item[%
186     \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
187   {\item[%
188     \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}%
189 }
190 \renewtheoremstyle{break}{%
191   {\item[%
192     \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
193   ]}%
194   {\item[%
195     \InlineClass{theoremheaderbreak}{}}%
```

```
196      {##1\ ##2\ (##3)\theorem@separator}\newline
197  ]}
198
199 \renewtheoremstyle{change}%
200  {\item[
201    \InlineClass{\theoremheaderchange}{##2\ ##1\theorem@separator}]}%
202  {\item[
203    \InlineClass{\theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]}%
204
205 \renewtheoremstyle{changebreak}%
206  {\item[
207    \InlineClass{\theoremheaderchangebreak}%
208    {##2\ ##1\theorem@separator}\newline
209  ]}
210  {\item[
211    \InlineClass{\theoremheaderchangebreak}%
212    {##2\ ##1\ (##3)\theorem@separator}\newline
213  ]}
214
215 \renewtheoremstyle{margin}%
216  {\item[
217    \InlineClass{\theoremheadermargin}{##2 \qquad ##1\theorem@separator}%
218  ]}
219  {\item[
220    \InlineClass{\theoremheadermargin}{##2 \qquad ##1\ (##3)\theorem@separator}%
221  ]}
222
223 \renewtheoremstyle{marginbreak}%
224  {\item[
225    \InlineClass{\theoremheadermarginbreak}%
226    {##2 \qquad ##1\theorem@separator}\newline
227  ]}
228  {\item[
229    \InlineClass{\theoremheadermarginbreak}%
230    {##2 \qquad ##1\ (##3)\theorem@separator}\newline
231  ]}
232
233 \renewtheoremstyle{nonumberplain}%
234  {\item[
235    \InlineClass{\theoremheaderplain}{##1\theorem@separator}]}%
236  {\item[
237    \InlineClass{\theoremheaderplain}{##1\ (##3)\theorem@separator}]}%
238
239 \renewtheoremstyle{nonumberbreak}%
240  {\item[
241    \InlineClass{\theoremheaderbreak}{##1\theorem@separator}\newline
242  ]}
243  {\item[
244    \InlineClass{\theoremheaderbreak}{##1\ (##3)\theorem@separator}\newline
245  ]}
246
247 \renewtheoremstyle{empty}%
248  {\item[]}%
249  {\item[
250    \InlineClass{\theoremheaderplain}{##3}]}%
```

```

251
252 \renewtheoremstyle{emptybreak}%
253 {\\item[]}%
254 {\\item[%
255     \\InLineClass{theoremheaderplain}{##3}] \\ \\newline}

```

### § 380.7 Additional objects

The following manually adjust the css for the standard configuration objects which are not a purely plain style:

```
256 \\ifbool{LWR@ntheoremamsthm}{}{%
```

Upright text via CSS:

```

257     \\newtheoremstyle{plainupright}%
258     {\\item[%
259         \\InLineClass{theoremheaderplain}{##1\\ ##2\\theorem@separator}]}%
260     {\\item[%
261         \\InLineClass{theoremheaderplain}{##1\\ ##2\\ (###3)\\theorem@separator}]}

```

Upright text and small caps header via CSS:

```

262     \\newtheoremstyle{nonumberplainuprightsc}%
263     {\\item[%
264         \\InLineClass{theoremheadersc}{##1\\theorem@separator}]}%
265     {\\item[%
266         \\InLineClass{theoremheadersc}{##1\\ (###3)\\theorem@separator}]}
267 }% not amsthm

```

### § 380.8 Renewed standard configuration

The following standard configuration is renewed using the new css:

```

268 \\ifbool{LWR@ntheoremamsthm}{}{%
269 \\ifx\\thm@usestd\\undefined
270 \\else
271     \\theoremnumbering{arabic}
272     \\theoremstyle{plain}
273     \\RequirePackage{latexsym}
274     \\theoremsymbol{\\Box}
275     \\theorembodyfont{\\itshape}
276     \\theoremheaderfont{\\normalfont\\bfseries}
277     \\theoremseparator{\\ }
278     \\renewtheorem{Theorem}{Theorem}
279     \\renewtheorem{theorem}{Theorem}
280     \\renewtheorem{Satz}{Satz}
281     \\renewtheorem{satz}{Satz}
282     \\renewtheorem{Proposition}{Proposition}
283     \\renewtheorem{proposition}{Proposition}
284     \\renewtheorem{Lemma}{Lemma}
285     \\renewtheorem{lemma}{Lemma}
286     \\renewtheorem{Korollar}{Korollar}

```

```

287 \renewtheorem{korollar}{Korollar}
288 \renewtheorem{Corollary}{Corollary}
289 \renewtheorem{corollary}{Corollary}
290
291 \theoremstyle{plainupright}
292 \theorembbodyfont{\upshape}
293 \theoremsymbol{\HTMLunicode{25A1}}% UTF-8 white box
294 \renewtheorem{Example}{Example}
295 \renewtheorem{example}{Example}
296 \renewtheorem{Beispiel}{Beispiel}
297 \renewtheorem{beispiel}{Beispiel}
298 \renewtheorem{Bemerkung}{Bemerkung}
299 \renewtheorem{bemerkung}{Bemerkung}
300 \renewtheorem{Anmerkung}{Anmerkung}
301 \renewtheorem{anmerkung}{Anmerkung}
302 \renewtheorem{Remark}{Remark}
303 \renewtheorem{remark}{Remark}
304 \renewtheorem{Definition}{Definition}
305 \renewtheorem{definition}{Definition}
306
307 \theoremstyle{nonumberplainuprightsc}
308 \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
309 \renewtheorem{Proof}{Proof}
310 \renewtheorem{proof}{Proof}
311 \renewtheorem{Beweis}{Beweis}
312 \renewtheorem{beweis}{Beweis}
313 \qedsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
314
315 \theoremsymbol{}
316 \fi
317 }% not amsthm

```

### § 380.9 **amsthm option**

Only if the `amsthm` option was given:

```

318 \ifbool{LWR@ntheoremamsthm}%
319
320 \gdef\th@plain{%
321   \def\theorem@headerfont{\normalfont\bfseries}\itshape%
322   \def@\begintheorem##1##2{%
323     \LWR@inctheorem% l warp
324     \item[%
325       \InLineClass{theoremheaderplain}{##1\ ##2.}%
326     ]}%
327   \def@\opargbegintheorem##1##2##3{%
328     \LWR@inctheorem% l warp
329     \item[%
330       \InLineClass{theoremheaderplain}{##1\ ##2\ (###3).}%
331     ]}%
332
333 \gdef\th@nonumberplain{%
334   \def\theorem@headerfont{\normalfont\bfseries}\itshape%
335   \def@\begintheorem##1##2{%
336     \LWR@inctheorem% l warp

```

```
337      \item[  
338  \InlineClass{theoremheaderplain}{##1.}  
339  ]}%  
340 \def\@opargbegintheorem##1##2##3{  
341   \LWR@inctheorem% l warp  
342   \item[  
343  \InlineClass{theoremheaderplain}{##1\ (###3).}  
344  ]}  
345  
346 \gdef\th@definition{  
347  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%  
348  \def\@begintheorem##1##2{  
349    \LWR@inctheorem% l warp  
350    \item[  
351  \InlineClass{theoremheaderdefinition}{##1\ ##2.}  
352  ]}  
353 \def\@opargbegintheorem##1##2##3{  
354  \LWR@inctheorem% l warp  
355  \item[  
356  \InlineClass{theoremheaderdefinition}{##1\ ##2\ (###3).}  
357  ]}  
358  
359 \gdef\th@nonumberdefinition{  
360  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%  
361  \def\@begintheorem##1##2{  
362    \LWR@inctheorem% l warp  
363    \item[  
364  \InlineClass{theoremheaderdefinition}{##1.}  
365  ]}  
366 \def\@opargbegintheorem##1##2##3{  
367  \LWR@inctheorem% l warp  
368  \item[  
369  \InlineClass{theoremheaderdefinition}{##1\ (###3).}  
370  ]}  
371  
372 \gdef\th@remark{  
373  \def\theorem@headerfont{\itshape}\normalfont%  
374  \def\@begintheorem##1##2{  
375    \LWR@inctheorem% l warp  
376    \item[  
377  \InlineClass{theoremheaderremark}{##1\ ##2.}  
378  ]}  
379 \def\@opargbegintheorem##1##2##3{  
380  \LWR@inctheorem% l warp  
381  \item[  
382  \InlineClass{theoremheaderremark}{##1\ ##2\ (###3).}  
383  ]}  
384  
385 \gdef\th@nonumberremark{  
386  \def\theorem@headerfont{\itshape}\normalfont%  
387  \def\@begintheorem##1##2{  
388    \LWR@inctheorem% l warp  
389    \item[  
390  \InlineClass{theoremheaderremark}{##1.}  
391  ]}
```

```

392 \def@opargbegintheorem##1##2##3{%
393     \LWR@inctheorem% l warp
394     \item[
395     \InlineClass{theoremheaderremark}{##1\ (###3).}
396     ]}}
397
398 \gdef\th@proof{%
399     \def\theorem@headerfont{\normalfont\bfseries}\itshape%
400     \def\begintheorem##1##2{%
401         \LWR@inctheorem% l warp
402         \item[
403         \InlineClass{theoremheaderproof}{##1.}
404         ]}%
405     \def@opargbegintheorem##1##2##3{%
406         \LWR@inctheorem% l warp
407         \item[
408         \InlineClass{theoremheaderproof}{##1\ (###3).}
409         ]}}
410
411
412
413 \newcounter{proof}%
414 \if@thmmarks
415     \newcounter{currproofctr}%
416     \newcounter{endproofctr}%
417 \fi
418
419 \gdef\proofSymbol{\openbox}
420
421 \newcommand{\proofname}{Proof}
422
423 \newenvironment{proof}[1][\proofname]{%
424     \th@proof
425     \def\theorem@headerfont{\itshape}%
426     \normalfont
427     \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
428     \atthm{proof}{proof}{#1}
429 }%
430 {\endtheorem}
431
432 }{}% amsthm option

```

### § 380.10 Ending a theorem

Patched for css:

```

433 \let\LWR@origendtheorem@\endtheorem
434 \renewcommand{\endtheorem}{%
435 \ifbool{\LWR@ntheoremarks}{%
436     \ifsetendmark%
437         \InlineClass{theoremendmark}{\csname\InTheoType Symbol\endcsname}%
438         \setendmarkfalse%
439     \fi%
440 }{}%
441 \LWR@origendtheorem% also does \endtrivlist

```

---

```
442 \ifbool{LWR@ntheoremmarks}{\global\setendmarktrue}{}%
443 \endBlockClass%
444 }
```

### § 380.11 \NoEndMark

```
445 \gdef\NoEndMark{\global\setendmarkfalse}
```

### § 380.12 List-of

Redefined to reuse the float mechanism to add list-of-theorem links:

```
\thm@thmline {\langle 1: printed type \rangle} {\langle 2: # \rangle} {\langle 3: optional \rangle} {\langle 4: page \rangle}
```

```
446 \renewcommand{\thm@thmline@noname}[4]{%
447 \hypertocfloat{1}{theorem}{thm}{#2 #3}{}%
448 }
449
450 \renewcommand{\thm@thmline@name}[4]{%
451 \hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}%
452 }
```

This was redefined by `ntheorem` when loaded, so it is now redefined for `lwarf`:

```
453 \def\thm@thmline{\thm@thmline@name}
```

Patch for css:

```
454 \def\listtheorems#1{
455 \LWR@htmlelementclass{nav}{lothm}%
456 \begingroup
457 \c@tocdepth=-2%
458 \def\thm@list{\#1}\thm@processlist
459 \endgroup
460 \LWR@htmlelementclassend{nav}{lothm}%
461 }
```

### § 380.13 Symbols

Proof QED symbol:

```
462 \newcommand{\qed}{\qquad\the\qedsymbol}
463
464 \AtBeginDocument{
465 \@ifundefined{LWR@orig@openbox}%
466 \LetLtxMacro{\LWR@orig@openbox}{\openbox}
467 \LetLtxMacro{\LWR@orig@blacksquare}{\blacksquare}
468 \LetLtxMacro{\LWR@orig@Box}{\Box}
469
470 \def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
471 \def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
472 \def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box
473
474 \appto{\LWR@restoreorigformatting}{%
```

---

```

475 \LetLtxMacro\openbox\LWR@orig@openbox%
476 \LetLtxMacro\blacksquare\LWR@orig@blacksquare%
477 \LetLtxMacro\Box\LWR@orig@Box%
478 }% appto
479 }{ }% @ifundefined
480 }% AtBeginDocument

```

### § 380.14 Cross-referencing

```

\thref {\langle label\rangle}

481 \newcommand*{\thref}[1]{\cref{#1}}%

```

---

File 281 **lwarp-octave.sty**

### § 381 Package **octave**

*(Emulates or patches code by ANDREW A. CASHNER.)*

Pkg octave octave is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{octave}[2017/10/31]

Remove the leading 1pt kern:

```

2 \RenewDocumentCommand{\@PrintTicks}{ m }{%
3 \kern-1pt% lwarp
4 \@TickNum = #1%
5 \loop
6 \@Tick{}%
7 \advance\@TickNum by -1
8 \ifnum\@TickNum > 0
9 \repeat
10 }

```

Use unicode for the prime character:

```
11 \RenewDocumentCommand{\@Tick}{}{\text{\textnormal{2032}}}
```

Catch the inline font:

```

12 \RenewDocumentCommand{\pitch}{ m o m }{%
13 \if@OctaveNumber%
14 {%
15   \pitchfont{%
16     \LWR@textcurrentfont% lwarp
17     \MakeUppercase{#1}%
18     \IfValueTF{#2}{#2}{\textsubscript{#3}}%
19   }%
20 }%
21 }%
22 \else%

```

```

23 {%
24     \pitchfont{%
25         \LWR@textcurrentfont{%
26             \GetOctaveTick{#1}{#2}{#3}%
27         }%
28     }%
29 }%
30 \fi%
31 }

```

The original was hard to adapt to l warp's handling of &.

```

32 \StartDefiningTabulars
33 \renewcommand{\octavetable}{%
34 \begin{tabular}{ll}
35 \octaveprimes \pitch{C}{0} & \octavenumbers \pitch{C}{0} \\
36 \octaveprimes \pitch{C}{1} & \octavenumbers \pitch{C}{1} \\
37 \octaveprimes \pitch{C}{2} & \octavenumbers \pitch{C}{2} \\
38 \octaveprimes \pitch{C}{3} & \octavenumbers \pitch{C}{3} \\
39 \octaveprimes \pitch{C}{4} & \octavenumbers \pitch{C}{4} \\
40 \octaveprimes \pitch{C}{5} & \octavenumbers \pitch{C}{5} \\
41 \octaveprimes \pitch{C}{6} & \octavenumbers \pitch{C}{6} \\
42 \octaveprimes \pitch{C}{7} & \octavenumbers \pitch{C}{7} \\
43 \end{tabular}
44 }
45 \StopDefiningTabulars

```

### File 282 l warp-overpic.sty

## § 382 Package overpic

(Emulates or patches code by ROLF NIEPRASCHK.)

Pkg overpic overpic is patched for use by l warp.

**⚠ scaling** The macros \overpicfontsize and \overpicfontskip are used during HTML generation. These are sent to \fontsize to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the overpic and Overpic environments.

See section 84.2 for the print-mode version of \overpicfontsize and \overpicfontskip.

**for HTML output:** 1 \LWR@ProvidesPackagePass{overpic}[2017/10/06]

```

2 \newcommand*\overpicfontsize{12}
3 \newcommand*\overpicfontskip{14}
4
5 \BeforeBeginEnvironment{overpic}{%
6     \begin{lateximage}%
7         \fontsize{\overpicfontsize}{\overpicfontskip}%
8         \selectfont%
9     }

```

```
10
11 \AfterEndEnvironment{overpic}{\end{lateximage}}
12
13 \BeforeBeginEnvironment{Overpic}{%
14   \begin{lateximage}%
15   \fontsize{\overpicfontsize}{\overpicfontskip}%
16   \selectfont%
17 }
18
19 \AfterEndEnvironment{Overpic}{\end{lateximage}}
```

---

File 283 **l warp-pagegrid.sty**

§ 383 Package **pagegrid**

Pkg pagegrid pagegrid is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pagegrid}[2016/05/16]  
2 \newcommand\*{\pagegridsetup}[1]{}

---

File 284 **l warp-pagenote.sty**

§ 384 Package **pagenote**

Pkg pagenote pagenote works as-is, but the page option is disabled.

for HTML output: 1 \DeclareOption{page}{}
2 \LWR@ProvidesPackagePass{pagenote}[2009/09/03]

---

File 285 **l warp-pagesel.sty**

§ 385 Package **pagesel**

Pkg pagesel pagesel is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pagesel}[2016/05/16]

---

File 286 **l warp-paralist.sty**

§ 386 Package **paralist**

(Emulates or patches code by BERND SCHANDL.)

Pkg **paralist** **paralist** is supported with minor changes.

**for HTML output:** 1 \LWR@ProvidesPackagePass{paralist}[2017/01/22]

The compact environments are identical to the regular ones:

```
2 \LetLtxMacro{\compactitem}{\itemize}
3 \LetLtxMacro{\compactenum}{\enumerate}
4 \LetLtxMacro{\compactdesc}{\description}
5 \LetLtxMacro{\endcompactitem}{\enditemize}
6 \LetLtxMacro{\endcompactenum}{\endenumerate}
7 \LetLtxMacro{\endcompactdesc}{\enddescription}
```

For the inline environments, revert `\item` to its original print-mode version:

```
8 \AtBeginEnvironment{inparaitem}{\LetLtxMacro{\item}{\LWR@origitem}}
9 \AtBeginEnvironment{inparaenum}{\LetLtxMacro{\item}{\LWR@origitem}}
10 \AtBeginEnvironment{inparadesc}{\LetLtxMacro{\item}{\LWR@origitem}}
```

Manual formatting of the description labels:

```
11 \def\paradescriptionlabel#1{{\normalfont\textrm{\bfseries}#1}}
```

### File 287 **l warp-parallel.sty**

## § 387 Package **parallel**

(Emulates or patches code by MATTHIAS ECKERMAN.)

Pkg **parallel** **parallel** is emulated.

Package options are ignored. Footnotes are treated as normal l warp footnotes.

Environment option c gives side-by-side <div>s of class minipage, each of whose width is a percent depending on the given left and right widths, proportional to `\linewidth`.

Inside each environment, `\linewidth` and `\textwidth` are set for the print-output sizes.

**for HTML output:** Discard all options for **l warp-parallel**:

```
1 \LWR@ProvidesPackageDrop{parallel}[2003/04/13]
2 \newcounter{\LWR@parallel@Lwidth}
3 \newcounter{\LWR@parallel@Rwidth}
4 \newcommand*{\LWR@parallel@border}{}
5
6 \newenvironment*{Parallel}[3][]{%
7   \%
8   \LWR@printpendingfootnotes%
9   \setlength{\ linewidth}{\LWR@userstextwidth}%
10  \setlength{\ textwidth}{\LWR@userstextwidth}%
}
```

```
11      \renewcommand*\{LWR@parallel@border}{}%
12      \ifstreq{\#1}{v}%
13          %
14          \renewcommand*\{LWR@parallel@border}{} ; border-left: 2px solid black}%
15          %
16          {}%
17      \ifblank{\#2}%
18          \ifblank{\#3}{}{%
19              \setcounter{LWR@parallel@Lwidth}{45}%
20              \setcounter{LWR@parallel@Rwidth}{45}%
21          }{}{%
22              \setlength{\LWR@templengthone}{\linewidth-\#3}%
23              \setcounter{LWR@parallel@Lwidth}{%
24                  90*\ratio{\LWR@templengthone}{\linewidth}%
25              }%
26              \setcounter{LWR@parallel@Rwidth}{%
27                  90*\ratio{\#3}{\linewidth}%
28              }%
29          }%
30          \setlength{\LWR@templengthone}{\linewidth-\#2}%
31      }% #2 blank
32      \setlength{\LWR@templengthone}{\linewidth-\#1}%
33      \ifblank{\#3}{}{%
34          \setcounter{LWR@parallel@Lwidth}{%
35              90*\ratio{\#2}{\linewidth}%
36          }%
37          \setlength{\LWR@templengthone}{\linewidth-\#2}%
38          \setcounter{LWR@parallel@Rwidth}{%
39              90*\ratio{\LWR@templengthone}{\linewidth}%
40          }%
41          \setlength{\LWR@templengthone}{\linewidth-\#1}%
42          \setcounter{LWR@parallel@Lwidth}{%
43              90*\ratio{\#2}{\linewidth}%
44          }%
45          \setcounter{LWR@parallel@Rwidth}{%
46              90*\ratio{\#3}{\linewidth}%
47          }%
48      }%
49      \setlength{\LWR@templengthone}{\linewidth-\#1}%
50      \ifblank{\#2}{}{%
51      }%
52  }%
53  \ParallelAtEnd%
54  \renewcommand*\{ParallelAtEnd}{}%
55  \LWR@printpendingfootnotes%
56  }%
57
58 \newcommand*\{ParallelText}[1]{%
59     \begin{BlockClass}[
60         width:\arabic{LWR@parallel@Lwidth}\% ; % space
61         padding: .5ex 1\% ; % space
62     ]{minipage}%
63     #1%
64     \end{BlockClass}%
65 }
```

---

```

66
67 \newcommand*{\ParallelRText}[1]{%
68     \begin{BlockClass}[%]
69         width:\arabic{LWR@parallel@Rwidth}\% ; % space
70         padding: .5ex 1\% ; % space
71         \LWR@parallel@border%
72     ]{\minipage}%
73     #1%
74     \end{BlockClass}%
75 }
76
77 \newcommand*{\ParallelPar}{\LWR@printpendingfootnotes}
78
79 \newcommand*{\ParallelAtEnd}{}  


```

---

File 288 **l warp-parcolumns.sty**

§ 388 Package **parcolumns**

*(Emulates or patches code by JONATHAN SAUER.)*

Pkg **parcolumns** **parcolumns** is emulated.

**rulebetween** is honored. The other keys are ignored, including **colwidths**.

Each column is placed inside a `<div>` of class `minipage`, each of whose width is fixed at 85% divided by the number of columns. In most cases, this results in side-by-side minipages adapting to the browser width. Inside each minipage, `\linewidth`, `\textwidth`, and `\textheight` are set for a virtual  $6 \times 9$  inch page, with `\linewidth` divided by the number of columns.

**for HTML output:** Discard all options for **l warp-parcolumns**:

```

1 \RequirePackage{keyval}%
2
3 \LWR@ProvidesPackageDrop{parcolumns}[2004/11/25]

4 \newcounter{LWR@parcolumns@numcols}
5 \newcounter{LWR@parcolumns@thiscol}
6 \newcounter{LWR@parcolumns@width}
7 \newbool{LWR@parcolumns@started}
8 \newbool{LWR@parcolumns@rule}
9
10 \define@key{LWRparcols}{colwidths}{}%
11 \define@key{LWRparcols}{distance}{}%
12 \define@key{LWRparcols}{rulebetween}[true]{%
13     \setbool{LWR@parcolumns@rule}{#1}%
14 }
15 \define@key{LWRparcols}{nofirstindent}{}%
16 \define@key{LWRparcols}{sloppy}{}%
17 \define@key{LWRparcols}{sloppyspaces}{}%
18
19 \newenvironment*{parcolumns}[2]{}  


```

```
20      {%
21          \begin{LWR@setvirtualpage}*[#2]%
22          \setcounter{LWR@parcolumns@numcols}{#2}%
23          \setcounter{LWR@parcolumns@thiscol}{1}%
24          \boolfalse{LWR@parcolumns@started}%
25          \boolfalse{LWR@parcolumns@rule}%
26          \setcounter{LWR@parcolumns@width}{%
27              85/#2
28          }%
29          \setkeys{LWR@parcols}{#1}%
30      }
31  {\end{LWR@setvirtualpage}}

32
33 \newcommand{\LWR@parcolumns@onecol}[1]{%
34     \ifbool{LWR@parcolumns@started}{%
35         {}
36         {%
37             \LWR@htmldivclass{parcolumns}%
38             \booltrue{LWR@parcolumns@started}%
39         }%
40     \ifboolexpr{%
41         bool {LWR@parcolumns@rule} and
42         test {%
43             \ifnumgreater
44                 {\value{LWR@parcolumns@thiscol}}%
45                 {1}
46         }%
47     }%
48     {\renewcommand{\LWR@tempone}{ ; border-left: 2px solid black}%
49     {\renewcommand{\LWR@tempone}{} }%
50     \begin{BlockClass}[%%
51         width:\arabic{LWR@parcolumns@width}\% ; % space
52         padding: .5ex 1\% ; % space
53         \LWR@tempone%
54     ]{minipage}%
55     #1%
56     \end{BlockClass}%
57     \addtocounter{LWR@parcolumns@thiscol}{1}%
58 }
59
60 \newcommand{\colchunk}[2][\value{LWR@parcolumns@thiscol}]{%
61     \whileboolexpr{%
62         test {%
63             \ifnumcomp
64                 {\value{LWR@parcolumns@thiscol}}
65                 {<}
66                 {#1}%
67         }%
68     }{%
69         \LWR@parcolumns@onecol{}%
70     }%
71     \LWR@parcolumns@onecol{#2}%
72 }
73
74 \newcommand*{\colplacechunks}{%
```

---

```

75 \ifbool{LWR@parcolumns@started}%
76   {%
77     \LWR@htmldivclassend{div}%
78     \boolfalse{LWR@parcolumns@started}%
79   }%
80   {}%
81 \setcounter{LWR@parcolumns@thiscol}{1}%
82 }

```

---

File 289 **lwarp-parnotes.sty**

§ 389 Package **parnotes**

*(Emulates or patches code by CHELSEA HUGHES.)*

Pkg **parnotes** **parnotes** is supported with some patches.

**for HTML output:** 1 \LWR@ProvidesPackagePass{parnotes}[2016/08/15]

```

2 \long\def\PN@parnote@real#1#2{%
3   \parnotemark{#1}%
4   % Unless this is the first parnote in \PN@text, add a separator first
5   \unless\ifx\PN@text\empty\g@addto@macro\PN@text{\parnoteintercmd}\fi
6   % Redefine \@currentlabel to the parnote label, so \label works
7   \g@addto@macro\PN@text{%
8     \phantomsection%
9     \def\@currentlabel{#1}%
10    \def\cref@currentlabel{%
11      \parnotemark[\arabic{parnotemark}][]\theparnotemark%
12    }%
13  }%
14  \g@addto@macro\PN@text{%
15    \LWR@textcurrentfont{%
16      \parnotemark{#1}\nolinebreak\thinspace#2%
17    }%
18  }%
19 }
20
21 \def\PN@parnotes@real{%
22   % We call \par later, so this avoids recursion with \PN@parnotes@auto
23   \PN@inparnotestru
24   \unless\ifvmode\par\fi
25   % Avoid page breaks between a paragraph and its parnotes
26   \nopagebreak\addvspace{\parnotevskip}%
27   \LWR@forcenewpage%           lwarp
28   \begin{BlockClass}{footnotes}%   lwarp
29   {\parnotefmt{\PN@text}\par}%
30   \end{BlockClass}%            lwarp
31   \global\def\PN@text{}%
32   \addvspace{\parnotevskip}%
33   %
34   % These can be enabled or disabled by package options
35   %

```

```
36   \PN@disable@indent
37   \PN@reset@optional
38   \PN@inparnotesfalse
39 }
40
41 \AtBeginDocument{
42 \crefname{parnotemark}{paragraph note}{paragraph notes}%
43 \Crefname{parnotemark}{Paragraph note}{Paragraph notes}
44 }
```

---

**File 290 l warp-parskip.sty****§ 390 Package **parskip****

Pkg **parskip** **parskip** is ignored.

**for HTML output:** Discard all options for **l warp-parskip**.

```
1 \LWR@ProvidesPackageDrop{parskip}[2001/04/09]
```

---

**File 291 l warp-pbox.sty****§ 391 Package **pbox****

(Emulates or patches code by SIMON LAW.)

Pkg **pbox** **pbox** is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pbox}[2011/12/07]

```
2 \NewDocumentCommand{\pbox}{O{t} O{} O{t} m +m}{%
3 \global\booltrue{LWR@minipagefullwidth}%
4 \parbox[#1][#2][#3]{#4}{#5}%
5 }
6
7 \newcommand{\settominwidth}[3][\columnwidth]{%
8 \settowidth{#2}{#3}%
9 }
10
11 \newcommand{\widthofpbox}[1]{%
12 \widthof{#1}%
13 }
```

---

**File 292 l warp-pdfcol.sty****§ 392 Package **pdfcol****

Pkg **pdfcol** **pdfcol** is ignored.

```
for HTML output: 1 \LWR@ProvidesPackageDrop{pdfcol}[2018/11/01]
2
3 \ltx@ifnewif\ifpdfcolAvailable
4 \pdfcolAvailablefalse
5
6 \def\pdfcolErrorNoStacks{
7   \PackageInfo{l warp-pdfcol}{Ignoring pdfcol for HTML output.}
8 }
9
10 \def\pdfcolInitStack#1{}%
11
12 \long\def\pdfcolIfStackExists#1#2#3{#3}%
13
14 \def\pdfcolSwitchStack#1{}%
15
16 \def\pdfcolSetcurrentColor{}%
17
18 \def\pdfcolSetCurrent#1{}%
```

---

File 293 **l warp-pdfcolfoot.sty**

§ 393 Package **pdfcolfoot**

Pkg pdfcolfoot pdfcolfoot is ignored.

```
for HTML output: 1 \LWR@ProvidesPackageDrop{pdfcolfoot}[2016/05/16]
2
3 \newcommand*\pdfcolfoot@switch{}%
4
5 \newcommand*\pdfcolfoot@current{}%
```

---

File 294 **l warp-pdfcolmk.sty**

§ 394 Package **pdfcolmk**

Pkg pdfcolmk pdfcolmk is ignored.

```
for HTML output: 1 \LWR@ProvidesPackageDrop{pdfcolmk}[2016/05/16]
```

---

File 295 **l warp-pdfcolparallel.sty**

§ 395 Package **pdfcolparallel**

Pkg pdfcolparallel pdfcolparallel is ignored.

```
for HTML output: 1 \RequirePackage{keyval}%
2
3 \LWR@ProvidesPackageDropA{pdfcolparallel}[2016/05/16]
```

Pass options to parallel:

```
4 \DeclareOption*{%
5   \PassOptionsToPackage{\CurrentOption}{parallel}%
6 }
```

Process the options:

```
7 \LWR@ProvidesPackageDropB
```

Require parallel with the given options:

```
8 \RequirePackage{parallel}[2003/04/13]
```

Ignore the new key:

```
9 \define@key{parallel}{rulebetweencolor}{}

---


```

#### File 296 **l warp-pdfcolparcolumns.sty**

#### § 396 Package **pdfcolparcolumns**

Pkg pdfcolparcolumns pdfcolparcolumns is ignored.

for HTML output: 1 \LWR@ProvidesPackageDropA{pdfcolparcolumns}{2016/05/16}

Pass options to parcolumns:

```
2 \DeclareOption*{%
3   \PassOptionsToPackage{\CurrentOption}{parcolumns}%
4 }
```

Process the options:

```
5 \LWR@ProvidesPackageDropB
```

Require parcolumns with the given options:

```
6 \RequirePackage{parcolumns}[2004/11/25]
```

Ignore the new key:

```
7 \define@key{LWRparcols}{rulebetweencolor}{}

---


```

#### File 297 **l warp-pdfcomment.sty**

#### § 397 Package **pdfcomment**

Pkg pdfcomment pdfcomment is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pdfcomment}[2016/06/13]

```

2 \newenvironment{pdfsidelinecomment}[2]{}{}{}
3 \newcommand{\pdfcomment}[2]{}{}{}
4 \newcommand{\pdfmargincomment}[2]{}{}{}
5 \newcommand{\pdfmarkupcomment}[3]{}{}{#2}
6 \newcommand{\pdffreetextcomment}[2]{}{}{}
7 \newcommand{\pdfsquarecomment}[2]{}{}{}
8 \newcommand{\pdfcirclecomment}[2]{}{}{}
9 \newcommand{\pdflinecomment}[2]{}{}{}
10 \newcommand{\pdftooltip}[3]{}{}{#2}
11 \newcommand{\pdfcommentsetup}[2]{}{}{}
12 \newcommand{\listofpdfcomments}[1]{}{}{}
13 \newcommand{\setliststyle}[1]{}{}{}
14 \newcommand{\defineliststyle}[2]{}{}{}
15 \newcommand{\defineavatar}[2]{}{}{}
16 \newcommand{\definestyle}[2]{}{}{}
```

For MATHJAX:

```

17 \begin{warpMathJax}
18 \CustomizeMathJax{\newcommand{\pdfmarkupcomment}[3]{}{}{#2}}
19 \CustomizeMathJax{\newcommand{\pdftooltip}[3]{}{}{#2}}
20 \end{warpMathJax}
```

---

File 298 **lwarf-pdfcrypt.sty**

§ 398 Package **pdfcrypt**

Pkg pdfcrypt pdfcrypt is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pdfcrypt}[2016/05/16]

```
2 \newcommand*{\pdfcryptsetup}[1]{}{}
```

---

File 299 **lwarf-pdflscape.sty**

§ 399 Package **pdflscape**

Pkg pdflscape pdflscape is ignored.

**for HTML output:** Discard all options for lwarf-pdflscape:

```
1 \LWR@ProvidesPackageDrop{pdflscape}[2016/05/14]
```

---

File 300 **l warp-pdfmarginpar.sty**

§ 400 Package **pdfmarginpar**

Pkg pdfmarginpar pdfmarginpar is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{pdfmarginpar}[2011/08/05]
2 \newcommand{\pdfmarginpar}[2][]{}
3 \newcommand{\pdfmarginparset}[1]{}
```

---

File 301 **l warp-pdfpages.sty**

§ 401 Package **pdfpages**

(Emulates or patches code by ANDREAS MATTHIAS.)

Pkg pdfpages pdfpages is patched for use by l warp.

Option link and linkname work:

---

```
\hyperlink{<filename>.pdf.<pagenumber>}{some text}
\hyperlink{<linkname>.<pagenumber>}{some text}
```

---

Options which make no sense in HTML are disabled.

for HTML output:

```
1 \LWR@ProvidesPackagePass{pdfpages}[2017-10-31]
```

Disable option which have no meaning for HTML output:

```
2 \define@key{pdfpages}{fitpaper}[false]{}
3 \define@key{pdfpages}{landscape}[false]{}
4 \define@key{pdfpages}{openright}[false]{}
5 \define@key{pdfpages}{signature}(){}
6 \define@key{pdfpages}{signature*}){}
7 \define@key{pdfpages}{booklet}[false]{}
8 \define@key{pdfpages}{rotateoversize}[false]{}
9 \define@key{pdfpages}{doublepages}[false]{}
10 \define@key{pdfpages}{doublepagestwist}[false]{}
11 \define@key{pdfpages}{doublepagestwistodd}[false]{}
12 \define@key{pdfpages}{doublepagestwist*}[false]{}
13 \define@key{pdfpages}{doublepagestwistodd*}[false]{}
14 \define@key{pdfpages}{duplicatepages}[2]{}
15 \define@key{pdfpages}{thread}[false]{}
16 \define@key{pdfpages}{threadname}{}{}
```

---

```

17 \define@key{pdfpages}{linkfit}{}
18 \define@key{pdfpages}{linktodoc}[false]{}
19 \define@key{pdfpages}{linktodocfit}{}
20 \define@key{pdfpages}{linkfilename}{}
21 \define@key{pdfpages}{survey}[false]{}
22 \define@key{pdfpages}{survey-nolink}[false]{}
23 \define@key{pdfpages}{newwindow}[false]{}

```

Use print mode while measuring the page numbers:

```
24 \xpretocmd{\AM@getpagecount}{\LWR@restoreorigformatting}{}{}
```

Emulate a bit of **eso-pic**:

```

25 \newif\ifESO@texcoord
26
27 \newcommand{\ESO@HookIIBG}{}
28
29 \renewcommand{\AM@AddToShipoutPicture}{\g@addto@macro{\ESO@HookIIBG}}
30
31 \renewcommand{\ClearShipoutPicture}{}

```

\LWR@esopic@newpage At each \newpage.

```
32 \newcommand*{\LWR@esopic@newpage}{%
```

Is there something to draw?

```

33 \ifdefvoid{\ESO@HookIIBG}%
34 {}%
35 {}%

```

If the **link** option was specified, add a hyper target:

```

36     \ifAM@link%
37         \hypertarget{\AM@linkname.\AM@page}{}%
38     \fi%

```

Draw inside a picture environment of the size of a virtual page:

```

39     \begingroup%
40     \setlength{\unitlength}{1in}%
41     \begin{picture}(8,10.5)%
42     \ESO@HookIIBG%
43     \end{picture}%
44     \endgroup%
45     \global\let\ESO@HookIIBG\empty%
46 }
47 }

```

\AM@output Patched to use \LWR@esopic@newpage.

```

48 \xpatchcmd{\AM@output}
49   {\newpage}
50   {\LWR@esopic@newpage}
51   {}

```

```

52      {\LWR@patcherror{pdfpages}{AM@output-1}}
53
54 \xpatchcmd{\AM@output}
55   {\newpage}
56   {\LWR@esopic@newpage}
57   {}
58   {\LWR@patcherror{pdfpages}{AM@output-2}}
59
60 \xpatchcmd{\AM@output}
61   {\newpage}
62   {\LWR@esopic@newpage}
63   {}
64   {\LWR@patcherror{pdfpages}{AM@output-3}}

```

\includepdf Patched to set the user's paper size.

```

65 \xpretocmd{\includepdf}{%
66   \begingroup%
67   \setlength{\paperwidth}{\LWR@userspaperwidth}%
68   \setlength{\paperheight}{\LWR@userspaperheight}%
69 }{}{%
70
71 \xapptocmd{\includepdf}{%
72   \endgroup%
73 }{}{%

```

\includepdfmerge Patched to set the user's paper size.

```

74 \xpretocmd{\includepdfmerge}{%
75   \begingroup%
76   \setlength{\paperwidth}{\LWR@userspaperwidth}%
77   \setlength{\paperheight}{\LWR@userspaperheight}%
78 }{}{%
79
80 \xapptocmd{\includepdfmerge}{%
81   \endgroup%
82 }{}{%

```

\AM@hyper@begin@i Hyper links are created by \LWR@esopic@newpage, so don't create them here:

```
83 \renewcommand{\AM@hyper@begin@i}{}  


```

### File 302 l warp-pdfprivacy.sty

§ 402 Package **pdfprivacy**

Pkg pdfprivacy pdfprivacy is ignored.

for HTML output 1 \LWR@ProvidesPackageDrop{pdfprivacy}[2017/12/03]

---

File 303 **l warp-pdfrender.sty**

§ 403 Package **pdfrender**

Pkg pdfrender pdfrender is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pdfrender}[2016/05/17]  
2 \newcommand\*\{\pdfrender}[1]{}  
3 \newcommand{\textpdfrender}[2]{#2}

---

File 304 **l warp-pdfsync.sty**

§ 404 Package **pdfsync**

(Emulates or patches code by J. LAURENS.)

Pkg pdfsync pdfsync is ignored.

for HTML output: Discard all options for l warp-pdfsync:

1 \LWR@ProvidesPackageDrop{pdfsync}[2008/01/26]  
2 \newcommand\*\{\pdfsync}{}  
3 \newcommand\*\{\pdfsyncstart}{}  
4 \newcommand\*\{\pdfsyncstop}{}

---

File 305 **l warp-pdftricks.sty**

§ 405 Package **pdftricks**

(Emulates or patches code by C. V. RADHAKRISHNAN, C. V. RAJAGOPAL, ANTOINE CHAMBERT-LOIR.)

Pkg pdftricks pdftricks is patched for use by l warp.

⚠ convert image files The pdftricks image files <jobname>-fig\*.pdf must be converted to .svg, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **l warpmk pdftosvg <jobname>-fig\*.pdf**

for HTML output: 1 \LWR@ProvidesPackagePass{pdftricks}[2003/08/10]

Reuse the print-mode images:

2 \def\PDFTfigname{\BaseJobname-fig\thepsfig}

---

If the .pdf images have not yet been converted to .svg then an error about a missing file will occur. Warn the user to convert the images.

```

3 \PackageWarning{l warp-pdftricks}{
4 When the pdftricks images change,
5 remember to convert PDF images to SVG using 'l warpmk pdftosvg *-fig.pdf',
6 }
7
8 \AfterEndDocument{\typeout{***}}
9 \AfterEndDocument{\typeout{*** Note: If pdftricks images are not found, new, or updated,}}
10 \AfterEndDocument{\typeout{*** \space use 'l warpmk pdftosvg \BaseJobname-fig*.pdf'}}
11 \AfterEndDocument{\typeout{***}}

```

---

File 306 **l warp-pdfx.sty**

§ 406 Package **pdfx**

Pkg pdfx pdfx is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pdfx}[2017/05/18]

---

File 307 **l warp-perpage.sty**

§ 407 Package **perpage**

(Emulates or patches code by DAVID KASTRUP.)

Pkg perpage perpage is mostly ignored, but support is added for footnote counters.

There is no page number in HTML, so most counters are not reset. If the document redefines \the<countername> to include \theperpage, it is necessary to place that redefinition inside a warpprint environment to avoid modifying the HTML definitions.

\AddAbsoluteCounter must not be inside warpprint, as the counter must be added for HTML also, although it is not incremented.

**footnote numbering** To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for

\alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

for HTML output: 1 \LWR@ProvidesPackageDrop{perpage}[2014/10/25]

```

2 \newcommand\AddAbsoluteCounter[1]
3 {
4     \@ifundefined{c@abs#1}{%
5         \expandafter\newcount\csname c@abs#1\endcsname
6         \global\value{abs#1}\@ne
7 %         \global\expandafter\let\csname cl@abs#1\endcsname\@empty
8         \expandafter\xdef\csname theabs#1\endcsname{%
9             \noexpand\number \csname c@abs#1\endcsname
10            }%
11 %         \global\@namedef{c@pabs@#1}{\pp@cl@begin
12 %         \stepcounter{abs#1}%
13 %         \pp@cl@end}%
14 %         \@addtoreset{pabs@#1}{#1}
15     }
16     {}
17 }
18
19 \AddAbsoluteCounter{page}
20 \def\theabspage{1}
21
22 \newcommand*\MakePerPage[2][1]{%
23     \ifltxcounter{#2Reset}{%
24         \setcounter{#2Reset}{#1}%
25     }%
26
27 }%
28 }
29
30 \newcommand*\MakeSorted[1]{}
31
32 \newcommand*\MakeSortedPerPage[2][1]{%
33     \ifltxcounter{#2Reset}{%
34         \setcounter{#2Reset}{#1}%
35     }%
36 }%
37 }
38
39 \newcommand*{\theperpage}{1}
```

File 308 **lwarf-pfnote.sty**

## § 408 Package **pfnote**

Pkg pfnote pfnote is ignored.

**pfnote** While emulating pfnote, lwarf is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarf therefore uses continuous footnote numbering even for pfnote.

**⚠ pfnote numbers**

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pfnote}[1999/07/14]

---

File 309 **l warp-phfqit.sty**

§ 409 Package **phfqit**

(Emulates or patches code by PHILIPPE FAIST.)

Pkg phfqit phfqit is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{phfqit}[2017/08/16]

```
2 \LetLtxMacro{\LWR@origbitstring}{\bitstring}
3
4 \renewcommand{\bitstring}[1]{%
5   \InlineClass[%
6     text-decoration: overline underline ;
7   ]{\bitstring}{#1}%
8   \phfqit@bitstring{#1}%
9 }
10
11 \appto{\LWR@restoreorigformatting}{%
12 \LetLtxMacro{\bitstring}{\LWR@origbitstring}%
13 }
```

---

File 310 **l warp-physics.sty**

§ 410 Package **physics**

(Emulates or patches code by SERGIO C. DE LA BARRERA.)

Pkg physics physics works as-is for HTML with SVG math.

For MATHJAX, emulation is provided via MATHJAX macros. These are not the same as the third-party MATHJAX extension.

- The `notrig` option is honored.
- ⚠ • Starred macros are not yet detected.
- ⚠ • Most macros don't work with `\big`, etc.
- ⚠ • Macros do not auto-detect variable numbers of mandatory arguments. Provide empty {} arguments for those which are not used.
- ⚠ • Many of the macros do not work with auto-detected delimiters. Use the delimiter-specific versions instead. Some macros do not even consider the following arguments, so they may work as expected.
- ⚠ • For `\Re` and `\Im`, the arguments must be in braces.

- For `\functionalderivative`, for the example in the manual with  $(E - TS)$ , enclose the parens in braces.

⚠

  - `\expectationvalue` requires and uses two mandatory arguments, unlike the third-party MATHJAX `physics` extension.
  - Each of `\matrixquantity`, `\smallmatrixquantity`, and `\matrixdeterminant` work, while `\identitymatrix` and the following simply print a place-holder, and must be replaced by hand.

**for HTML output:** 1 \LWR@ProvidesPackagePass{physics}% No date is provided by the package.

```

1 % doesn't work with \big, etc:
2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{physics}
4
5
6 \CustomizeMathJax{\newcommand{\quantity}{}}
7 \CustomizeMathJax{\let\qty\quantity}
8 \CustomizeMathJax{\newcommand{\pqty}[1]{\left(#1\right)}}
9 \CustomizeMathJax{\newcommand{\bqty}[1]{\left[lbrace#1\rbrace\right]}}
10 \CustomizeMathJax{\newcommand{\vqty}[1]{\left[\left.\right.^#1\right]}}
11 \CustomizeMathJax{\newcommand{\Bqty}[1]{\left\{#1\right\}}}
12
13 % doesn't work with \big, etc., no star
14 \CustomizeMathJax{\newcommand{\absolutevalue}[1]{\left|\left.\right.^#1\right|}}
15 \CustomizeMathJax{\let\abs\absolutevalue}
16
17 % doesn't work with \big, etc., no star
18 \CustomizeMathJax{\newcommand{\norm}[1]{%
19   \left|\left.\right.^#1\right|}}
20 }
21
22 % doesn't work with \big, etc., no star, no paren or bracket
23 \CustomizeMathJax{\newcommand{\evaluated}[1]{\left.\right.^#1}}
24 \CustomizeMathJax{\let\eval\evaluated}
25
26 % no \Big, star
27 \CustomizeMathJax{\newcommand{\order}[1]{\mathcal{O}\left(\left.\right.^#1\right)}}
28
29 % no \Big, star
30 \CustomizeMathJax{\newcommand{\commutator}[2]{\left[\left.\right.^#1,\left.\right.^#2\right]}}
31 \CustomizeMathJax{\let\comm\commutator}
32
33 % no \Big, star
34 \CustomizeMathJax{\newcommand{\anticommutator}[2]{%
35   \left\{#1,\left.\right.^#2\right\}}}
36 }
37 \CustomizeMathJax{\let\acomm\anticommutator}
38
39 % no \Big, star
40 \CustomizeMathJax{\let\poissonbracket\anticommutator}
41 \CustomizeMathJax{\let\pb\anticommutator}
42
43 % no star
44 \CustomizeMathJax{\newcommand{\vectorbold}[1]{\mathbf{#1}}}

```

```
45 \CustomizeMathJax{\let\vb\vectorbold}
46
47 % no star
48 \CustomizeMathJax{\newcommand{\vectorarrow}[1]{\vec{\mathbf{#1}}}}
49 \CustomizeMathJax{\let\va\vectorarrow}
50
51 % no star
52 \CustomizeMathJax{\newcommand{\vectorunit}[1]{\mathbf{\hat{#1}}}}
53 \CustomizeMathJax{\let\va\vectorunit}
54
55 \CustomizeMathJax{\newcommand{\dotproduct}{\boldsymbol{\cdot}}}
56 \CustomizeMathJax{\let\vdot\dotproduct}
57
58 \CustomizeMathJax{\newcommand{\crossproduct}{\boldsymbol{\times}}}
59 \CustomizeMathJax{\let\cross\crossproduct}
60 \CustomizeMathJax{\let\cp\crossproduct}
61
62 \CustomizeMathJax{\newcommand{\gradient}{\mathbf{\nabla}}}
63 \CustomizeMathJax{\let\grad\gradient}
64
65 \CustomizeMathJax{\let\divisionsymbol\div}
66
67 \CustomizeMathJax{\newcommand{\divergence}{\nabla\cdot}}
68 \CustomizeMathJax{\let\div\divergence}
69
70 \CustomizeMathJax{\newcommand{\curl}{\nabla\times}}
71
72 \CustomizeMathJax{\newcommand{\laplacian}{\nabla^2}}
73
74 % responds to notrig option
75 \ifx\trigopt 1
76     \CustomizeMathJax{\DeclareMathOperator{\sine}{sin}}
77     \CustomizeMathJax{\DeclareMathOperator{\cosine}{cos}}
78     \CustomizeMathJax{\DeclareMathOperator{\tangent}{tan}}
79     \CustomizeMathJax{\DeclareMathOperator{\cosecant}{csc}}
80     \CustomizeMathJax{\DeclareMathOperator{\secant}{sec}}
81     \CustomizeMathJax{\DeclareMathOperator{\cotangent}{cot}}
82     \CustomizeMathJax{\DeclareMathOperator{\arcsine}{arcsin}}
83     \CustomizeMathJax{\DeclareMathOperator{\arccosine}{arccos}}
84     \CustomizeMathJax{\DeclareMathOperator{\arctangent}{arctan}}
85     \CustomizeMathJax{\DeclareMathOperator{\hyp sine}{sinh}}
86     \CustomizeMathJax{\DeclareMathOperator{\hyp cosine}{cosh}}
87     \CustomizeMathJax{\DeclareMathOperator{\hyp tangent}{tanh}}
88     \CustomizeMathJax{\DeclareMathOperator{\hyp cotangent}{coth}}
89     \CustomizeMathJax{\DeclareMathOperator{\exponential}{exp}}
90     \CustomizeMathJax{\DeclareMathOperator{\logarithm}{log}}
91     \CustomizeMathJax{\DeclareMathOperator{\natural logarithm}{ln}}
92     \CustomizeMathJax{\DeclareMathOperator{\determinant}{det}}
93     \CustomizeMathJax{\DeclareMathOperator{\Probability}{Pr}}
94     \CustomizeMathJax{\newcommand{\sin}[1][{}]{\mathrm{sin}^{#1}}}
95     \CustomizeMathJax{\newcommand{\sinh}[1][{}]{\mathrm{sinh}^{#1}}}
96     \CustomizeMathJax{\newcommand{\arcsin}[1][{}]{\mathrm{arcsin}^{#1}}}
97     \CustomizeMathJax{\newcommand{\asin}[1][{}]{\mathrm{asin}^{#1}}}
98     \CustomizeMathJax{\newcommand{\cos}[1][{}]{\mathrm{cos}^{#1}}}
99     \CustomizeMathJax{\newcommand{\cosh}[1][{}]{\mathrm{cosh}^{#1}}}
```

```
100  \CustomizeMathJax{\newcommand{\arccos}[1][{}]{\mathrm{arccos}^{\#1}}}
101  \CustomizeMathJax{\newcommand{\acos}[1][{}]{\mathrm{acos}^{\#1}}}
102  \CustomizeMathJax{\newcommand{\tan}[1][{}]{\mathrm{tan}^{\#1}}}
103  \CustomizeMathJax{\newcommand{\tanh}[1][{}]{\mathrm{tanh}^{\#1}}}
104  \CustomizeMathJax{\newcommand{\arctan}[1][{}]{\mathrm{arctan}^{\#1}}}
105  \CustomizeMathJax{\newcommand{\atan}[1][{}]{\mathrm{atan}^{\#1}}}
106  \CustomizeMathJax{\newcommand{\csc}[1][{}]{\mathrm{csc}^{\#1}}}
107  \CustomizeMathJax{\newcommand{\csch}[1][{}]{\mathrm{csch}^{\#1}}}
108  \CustomizeMathJax{\newcommand{\arccsc}[1][{}]{\mathrm{arccsc}^{\#1}}}
109  \CustomizeMathJax{\newcommand{\acsc}[1][{}]{\mathrm{acsc}^{\#1}}}
110  \CustomizeMathJax{\newcommand{\sec}[1][{}]{\mathrm{sec}^{\#1}}}
111  \CustomizeMathJax{\newcommand{\sech}[1][{}]{\mathrm{sech}^{\#1}}}
112  \CustomizeMathJax{\newcommand{\arcsec}[1][{}]{\mathrm{arcsec}^{\#1}}}
113  \CustomizeMathJax{\newcommand{\asec}[1][{}]{\mathrm{asec}^{\#1}}}
114  \CustomizeMathJax{\newcommand{\cot}[1][{}]{\mathrm{cot}^{\#1}}}
115  \CustomizeMathJax{\newcommand{\coth}[1][{}]{\mathrm{coth}^{\#1}}}
116  \CustomizeMathJax{\newcommand{\arccot}[1][{}]{\mathrm{arccot}^{\#1}}}
117  \CustomizeMathJax{\newcommand{\acot}[1][{}]{\mathrm{acot}^{\#1}}}
118 \else
119  \CustomizeMathJax{\DeclareMathOperator{\arccsc}{arccsc}}
120  \CustomizeMathJax{\DeclareMathOperator{\arcsec}{arcsec}}
121  \CustomizeMathJax{\DeclareMathOperator{\arccot}{arccot}}
122  \CustomizeMathJax{\DeclareMathOperator{\asin}{asin}}
123  \CustomizeMathJax{\DeclareMathOperator{\acos}{acos}}
124  \CustomizeMathJax{\DeclareMathOperator{\atan}{atan}}
125  \CustomizeMathJax{\DeclareMathOperator{\acsc}{acsc}}
126  \CustomizeMathJax{\DeclareMathOperator{\asec}{asec}}
127  \CustomizeMathJax{\DeclareMathOperator{\acot}{acot}}
128  \CustomizeMathJax{\DeclareMathOperator{\csch}{csch}}
129  \CustomizeMathJax{\DeclareMathOperator{\sech}{sech}}
130  \CustomizeMathJax{\newcommand{\tr}{\text{\texttt{trace}}}}
131  \CustomizeMathJax{\newcommand{\Tr}{\text{\texttt{Trace}}}}
132  \CustomizeMathJax{\newcommand{\Res}{\text{\texttt{Reside}}}}
133 \fi
134
135 \CustomizeMathJax{\DeclareMathOperator{\trace}{tr}}
136 \CustomizeMathJax{\let\tr\text{\texttt{trace}}}
137 \CustomizeMathJax{\DeclareMathOperator{\Trace}{Tr}}
138 \CustomizeMathJax{\let\Tr\text{\texttt{Trace}}}
139 \CustomizeMathJax{\DeclareMathOperator{\rank}{rank}}
140 \CustomizeMathJax{\DeclareMathOperator{\erf}{erf}}
141 \CustomizeMathJax{\DeclareMathOperator{\Residue}{Res}}
142 \CustomizeMathJax{\newcommand{\principalvalue}{\mathcal{P}}}
143 \CustomizeMathJax{\let\pv\principalvalue}
144 \CustomizeMathJax{\newcommand{\PV}{\text{\texttt{P.V.}}}}
145 \CustomizeMathJax{\newcommand{\real}{\mathcal{R}}}
146 \CustomizeMathJax{\newcommand{\imaginary}{\mathcal{I}}}
147
148 % must be brace arguments
149 \CustomizeMathJax{\newcommand{\Re}[1]{\mathrm{Re}\left[1\right]\left.\mathrm{Re}\right\rvert_{\left.1\right.\vphantom{\left[1\right]}}\right.}}
150 \CustomizeMathJax{\newcommand{\Im}[1]{\mathrm{Im}\left[1\right]\left.\mathrm{Im}\right\rvert_{\left.1\right.\vphantom{\left[1\right]}}\right.}}
151
152 \CustomizeMathJax{\newcommand{\qqtext}[1]{\quad\mathrm{#1}\quad}}
153 \CustomizeMathJax{\let\qq\qqtext}
154 \CustomizeMathJax{\newcommand{\qqcomma}{\text{,}\quad}}
```

```
155 \CustomizeMathJax{\let\qc\qqcomma}
156 \CustomizeMathJax{\newcommand{\qcc}{\quad\text{c.c.}\quad}}
157 \CustomizeMathJax{\let\qcc}
158 \CustomizeMathJax{\newcommand{\qif}{\quad\text{if}\quad}}
159 \CustomizeMathJax{\newcommand{\qthen}{\quad\text{then}\quad}}
160 \CustomizeMathJax{\newcommand{\qelse}{\quad\text{else}\quad}}
161 \CustomizeMathJax{\newcommand{\qotherwise}{\quad\text{otherwise}\quad}}
162 \CustomizeMathJax{\newcommand{\qunless}{\quad\text{unless}\quad}}
163 \CustomizeMathJax{\newcommand{\qgiven}{\quad\text{given}\quad}}
164 \CustomizeMathJax{\newcommand{\qusing}{\quad\text{using}\quad}}
165 \CustomizeMathJax{\newcommand{\qassume}{\quad\text{assume}\quad}}
166 \CustomizeMathJax{\newcommand{\qsince}{\quad\text{since}\quad}}
167 \CustomizeMathJax{\newcommand{\qlet}{\quad\text{let}\quad}}
168 \CustomizeMathJax{\newcommand{\qfor}{\quad\text{for}\quad}}
169 \CustomizeMathJax{\newcommand{\qall}{\quad\text{all}\quad}}
170 \CustomizeMathJax{\newcommand{\qeven}{\quad\text{even}\quad}}
171 \CustomizeMathJax{\newcommand{\qodd}{\quad\text{odd}\quad}}
172 \CustomizeMathJax{\newcommand{\qinteger}{\quad\text{integer}\quad}}
173 \CustomizeMathJax{\newcommand{\qand}{\quad\text{and}\quad}}
174 \CustomizeMathJax{\newcommand{\qor}{\quad\text{or}\quad}}
175 \CustomizeMathJax{\newcommand{\qas}{\quad\text{as}\quad}}
176 \CustomizeMathJax{\newcommand{\qin}{\quad\text{in}\quad}}
177
178 \CustomizeMathJax{\newcommand{\differential}[1][]{\text{d}^{#1}}}
179 \CustomizeMathJax{\let\dd\differential}
180
181 \CustomizeMathJax{\newcommand{\derivative}[3][]{%
182   \frac{\text{d}^{#1}\#2}{\text{d}^{#1}\#3}%
183 }%
184 \CustomizeMathJax{\let\dv\derivative}
185
186 \CustomizeMathJax{\newcommand{\partialderivative}[3][]{%
187   \frac{\partial^{#1}\#2}{\partial^{#3}\#1}%
188 }%
189 \CustomizeMathJax{\let\pderivative\partialderivative}
190 \CustomizeMathJax{\let\pdv\partialderivative}
191
192 \CustomizeMathJax{\newcommand{\variation}{\delta}}
193 \CustomizeMathJax{\let\var\variation}
194
195 % Must provide two mandatory args.
196 % For the example in the manual with (E-TS), enclose the parens in braces
197 \CustomizeMathJax{\newcommand{\functionalderivative}[3][]{%
198   \frac{\delta^{#1}\#2}{\delta^{#3}\#1}%
199 }%
200 \CustomizeMathJax{\let\fdv\functionalderivative}
201
202
203 % use \braket to contract
204 \CustomizeMathJax{\newcommand{\bra}[1]{\langle #1\rvert}}
205 \CustomizeMathJax{\newcommand{\ket}[1]{\lvert #1\rangle}}
206
207 % must have two args
208 \CustomizeMathJax{\newcommand{\innerproduct}[2]{%
209   \left\langle #1\middle| #2\right\rangle%
```

```
210 }
211 \CustomizeMathJax{\let\braket\innerproduct}
212 \CustomizeMathJax{\let\ip\innerproduct}
213
214 % must have two args
215 \CustomizeMathJax{\newcommand{\outerproduct}[2]{%
216   \left\langle\middle\lvert\#1\middle\rangle\!\middle\langle\#2\right\rangle\!\middle\lvert\#2\middle\langle\right\rangle\%}
217 }
218 \CustomizeMathJax{\let\dyad\outerproduct}
219 \CustomizeMathJax{\let\op\outerproduct}
220
221 % must have two args, unlike the MathJax version
222 \CustomizeMathJax{\newcommand{\expectationvalue}[2]{%
223   \left\langle\middle\lvert\#2\middle\langle\#1\middle\lvert\middle\langle\#2\middle\lvert\right\rangle\%}
224 }
225 \CustomizeMathJax{\let\expval\expectationvalue}
226 \CustomizeMathJax{\let\ev\expectationvalue}
227
228 \CustomizeMathJax{\newcommand{\matrixelement}[3]{%
229   \left\langle\middle\lvert\#1\middle\lvert\middle\langle\#2\middle\lvert\middle\langle\#3\middle\lvert\right\rangle\%}
230 }
231 \CustomizeMathJax{\let\mel\matrixelement}
232
233 \CustomizeMathJax{\newcommand{\matrixquantity}[1]{\begin{matrix}\#1\end{matrix}}}
234 \CustomizeMathJax{\let\mqty\matrixquantity}
235 \CustomizeMathJax{\newcommand{\pmqty}[1]{\begin{pmatrix}\#1\end{pmatrix}}}
236 \CustomizeMathJax{\newcommand{\Pmqty}[1]{%
237   \left\langle\lgrou\begin{matrix}\#1\end{matrix}\right\rangle\%}
238 }
239 \CustomizeMathJax{\newcommand{\bmqty}[1]{\begin{bmatrix}\#1\end{bmatrix}}}
240 \CustomizeMathJax{\newcommand{\vmqty}[1]{\begin{vmatrix}\#1\end{vmatrix}}}
241
242 \CustomizeMathJax{\newcommand{\smallmatrixquantity}[1]{%
243   \begin{smallmatrix}\#1\end{smallmatrix}}}
244
245 \CustomizeMathJax{\let\smqty\smallmatrixquantity}
246 \CustomizeMathJax{\newcommand{\spmqty}[1]{%
247   \begin{smallmatrix}\#1\end{smallmatrix}}}
248 }
249 \CustomizeMathJax{\newcommand{\sPmqty}[1]{%
250   \left\langle\lgrou\begin{smallmatrix}\#1\end{smallmatrix}\right\rangle\%}
251 }
252 \CustomizeMathJax{\newcommand{\sbmqty}[1]{%
253   \begin{smallmatrix}\#1\end{smallmatrix}}}
254
255 \CustomizeMathJax{\newcommand{\svmqty}[1]{%
256   \begin{smallmatrix}\#1\end{smallmatrix}}}
257 }
258
259 \CustomizeMathJax{\let\matrixdeterminant\vmqty}
260 \CustomizeMathJax{\let\mdet\vmqty}
261 \CustomizeMathJax{\let\smdet\svmqty}
262
263 \CustomizeMathJax{\newcommand{\identitymatrix}[1]{\text{imat}\{\#1\}}}
264 \CustomizeMathJax{\let\imat\identitymatrix}
```

---

```

265
266 \CustomizeMathJax{\newcommand{\xmatrix}[3]{(\text{xmat}\{\}\{\#2\}\{\#3\})}}
267 \CustomizeMathJax{\let\xmat\xmatrix}
268
269 \CustomizeMathJax{\newcommand{\zeromatrix}[2]{(\text{zmat}\{\#1\}\{\#2\})}}
270 \CustomizeMathJax{\let\zmat\zeromatrix}
271
272 \CustomizeMathJax{\newcommand{\paulimatrix}[1]{(\text{pmat}\{\#1\})}}
273 \CustomizeMathJax{\let\pmat\paulimatrix}
274
275 \CustomizeMathJax{\newcommand{\diagonalmatrix}[2][]{%
276   \left(\text{dmat}\right)}%
277 }
278 \CustomizeMathJax{\let\dmat\diagonalmatrix}
279
280 \CustomizeMathJax{\newcommand{\antidiagonalmatrix}[2][]{%
281   \left(\text{admat}\right)}%
282 }
283 \CustomizeMathJax{\let\admat\antidiagonalmatrix}
284 \end{warpMathJax}

```

---

File 311 **l warp-pifont.sty**

§ 411 Package **pifont**

*(Emulates or patches code by WALTER SCHMIDT.)*

Pkg pifont pifont is patched for use by l warp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output 1 \LWR@ProvidesPackagePass{pifont}[2005/04/12]

```

2 \renewcommand{\Pisymbol}[2]{%
3   \begin{lateximage}*[Pisymbol][pisymbol#1#2]%
4   {\Pifont{\#1}\char#2}%
5   \end{lateximage}%
6 }
7
8 \newcommand{\LWR@HTML@Pifill}[2]{%
9   \Pisymbol{\#1}{\#2} \Pisymbol{\#1}{\#2} \Pisymbol{\#1}{\#2}%
10 }
11 \LWR@formatted{Pifill}
12
13 \newcommand{\LWR@HTML@Piline}[2]{%
14   \par\noindent\hspace*{0.5in}%
15   \Pifill{\#1}{\#2} \Pifill{\#1}{\#2} \Pifill{\#1}{\#2}%
16 }
17 \LWR@formatted{Piline}

```

---

**File 312 l warp-placeins.sty****§ 412 Package placeins**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg placeins placeins is ignored.

Discard all options for l warp-placeins:

for HTML output: 1 \LWR@ProvidesPackageDrop{placeins}[2005/04/18]  
2 \newcommand\*\{\FloatBarrier}{}

---

**File 313 l warp-plarydshln.sty****§ 413 Package plarydshln**

Pkg plarydshln plarydshln is emulated by l warp-arydshln.  
for HTML output: 1 \LWR@ProvidesPackageDrop{plarydshln}[2018/10/20]  
2 \LWR@origRequirePackage{l warp-arydshln}

---

**File 314 l warp-plex.sty****§ 414 Package plex**

Pkg plex plex is preloaded by jtarticle and related classes.

for HTML output: 1 \LWR@Loadbefore{plex}  
2  
3 \LWR@ProvidesPackagePass{plex}[2017/07/21]  
4 \let\tate\relax  
5  
6 \DeclareExpandableDocumentCommand{\rensucci}{s o m}{#3}  
7  
8 % \layoutfloat{width,height}[pos]#4  
9 \DeclareDocumentCommand{\layoutfloat}{d() o m}{}  
10  
11 % \DeclareLayoutCaption{type} <dir>(width)[pos1pos2]  
12 \DeclareDocumentCommand{\DeclareLayoutCaption}{m d> d() o}{}  
13  
14 \LetLtxMacro\pcaption\caption

---

```

15
16 % \layoutcaption<dir>(width)[pos]
17 \DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}
18
19 \let\captiondir\relax

```

Add the optional <t/y> direction:

```

20 \RenewDocumentEnvironment{LWR@HTML@minipage}{d<> 0{t} 0{} 0{t} m}
21   {\LWR@HTML@sub@minipage[#2]{#3}{#4}{#5}}
22   {\endLWR@HTML@sub@minipage}
23
24 \RenewDocumentCommand{\LWR@HTML@parbox}{d<> 0{t} 0{} 0{t} m +m}
25 {
26 \LWR@traceinfo{parbox of width #4}%
27 \begin{minipage}[#2][#3][#4]{#5}%
28 #6
29 \end{minipage}%
30 }
31
32 % \pbox <t/y> [width] [l/r] {contents}
33 \RenewDocumentCommand{\pbox}{d<> 0{0pt} 0{c} m}{%
34 \global\booltrue{LWR@minipagefullwidth}%
35 \parbox[#2]{#4}%
36 }

```

picture, as modified by pext, is encapsulated by the l warp core.

---

File 315 **l warp-plectarydshln.sty**

§ 415 Package **plectarydshln**

Pkg plectarydshln plectarydshln is emulated by l warp-arydshln.

**for HTML output:**

- 1 \LWR@ProvidesPackageDrop{plectarydshln}[2018/10/20]
- 2 \LWR@origRequirePackage{l warp-arydshln}

---

File 316 **l warp-plextcolortbl.sty**

§ 416 Package **plextcolortbl**

Pkg plectcolortbl plectcolortbl is emulated by l warp-colortbl.

**for HTML output:**

- 1 \LWR@ProvidesPackageDrop{plextcolortbl}[2018/09/19]
- 2 \LWR@origRequirePackage{l warp-colortbl}

---

**File 317 l warp-prelim2e.sty****§ 417 Package prelim2e**

(Emulates or patches code by MARTIN SCHRÖDER.)

Pkg prelim2e prelim2e is ignored.

for HTML output Discard all options for l warp-prelim2e:

```
1 \LWR@ProvidesPackageDrop{prelim2e}[2009/05/29]  
  
2 \newcommand{\PrelimText}{}  
3 \newcommand{\PrelimTextStyle}{}  
4 \newcommand{\PrelimWords}{}
```

---

**File 318 l warp-prettyref.sty****§ 418 Package prettyref**

(Emulates or patches code by KEVIN S. RULAND.)

Pkg prettyref prettyref is patched for use by l warp.

for HTML output 1 \LWR@ProvidesPackagePass{prettyref}[1998/07/09]  
  
2 \newreformat{fig}{Figure \ref{#1}}  
3 \newreformat{tab}{Table \ref{#1}}

---

**File 319 l warp-preview.sty****§ 419 Package preview**

Pkg preview preview is ignored.

for HTML output 1 \LWR@ProvidesPackageDrop{preview}[2017/04/24]  
  
2 \newenvironment{preview}{}{}  
3 \newenvironment{nopreview}{}{}  
4 \NewDocumentCommand{\PreviewMacro}{s o o +m}{}  
5 \NewDocumentCommand{\PreviewEnvironment}{s o o +m}{}  
6 \newcommand{\PreviewSnarfEnvironment}[2]{}  
7 \NewDocumentCommand{\PreviewOpen}{s o}{}  
8 \NewDocumentCommand{\PreviewClose}{s o}{}  
9 \let\ifPreview\iffalse \fi for syntax highlighting

---

**File 320 l warp-psfrag.sty****§ 420 Package psfrag**

(Emulates or patches code by MICHAEL C. GRANT, DAVID CARLISLE.)

Pkg psfrag psfrag is patched for use by l warp.

⚠ **use psfrags** The psfrags environment is modified to use lateximage to encapsulate the image. Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by l warp.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

**for HTML output:** 1 \LWR@ProvidesPackagePass{psfrag}[1998/04/11]

A lateximage captures the modified image from the document.

```
2 \BeforeBeginEnvironment{psfrags}{%
3   \begin{lateximage}[-psfrags-\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{psfrags}{\end{lateximage}}
```

---

**File 321 l warp-psfragx.sty****§ 421 Package psfragx**

(Emulates or patches code by PASCAL KOCKAERT.)

Pkg psfragx psfragx is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{psfragx}[2012/05/02]

A lateximage captures the modified image from the document.

```
2 \def\pfx@includegraphicx#1#2{%
3   \begin{lateximage}[-psfragx-\PackageDiagramAltText]%
4     \mbox{\pfx@overpix{#1}{#2}\endpfx@overpix}%
5   \end{lateximage}%
6 }
7
8 \def\@@overpix[#1]<#2>[#3]#4{%
9   \begin{lateximage}[-psfragx-\PackageDiagramAltText]%
10    \pfx@overpix{#1,ovpfgd={#2},ovpbgd={#3}}{#4}%
11 }
12
```

```
13 \def\endoverpix{%
14   \endpfx@overpix%
15   \end{lateximage}%
16 }
```

---

**File 322 l warp-pst-eps.sty****§ 422 Package pst-eps**

(Emulates or patches code by HERBERT VOSS.)

Pkg pst-eps pst-eps is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{pst-eps}[2005/05/20]

```
2 \renewenvironment{TeXtoEPS}{}{}
3 \renewcommand{\PSTtoEPS}[3][]{}
```

---

**File 323 l warp-pstool.sty****§ 423 Package pstool**

(Emulates or patches code by ZEBB PRIME, WILL ROBERTSON.)

Pkg pstool pstool is patched for use by l warp.

\graphicspath is ignored, and the file directory must be stated.

⚠ **path and filename** The filename must not have a file extension.

Use

Enter ⇒ **l warpmk html**

followed by

Enter ⇒ **l warpmk limages**

.

**for HTML output:** 1 \LWR@ProvidesPackagePass{pstool}[2018/01/20]

Each image is placed inside a lateximage to capture the results of psfrag.

```
2 \renewcommand{\pstool@alwaysprocess}[3][]{%
3   \begin{lateximage}[-pstool-\~\PackageDiagramAltText]%
4   \includegraphics{\#2.pdf}%
5   \end{lateximage}%
6 }
7 \LetLtxMacro{\pstool@neverprocess}{\pstool@alwaysprocess}
```

```
8 \LetLtxMacro{\pstool}{\maybeProcess{\pstool}{\alwaysProcess}}
9
10 \renewcommand{\pstool}{\psfragfig[4]{%
11   \begin{ lateximage }[-pstool-\~\PackageDiagramAltText]%
12   \includegraphics{\#2.pdf}%
13   \end{ lateximage }%
14 }}
```

---

**File 324 l warp-pstricks.sty****§ 424 Package pstricks**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg pstricks pstricks is patched for use by l warp.

⚠ **use pspicture** All pstricks content should be contained inside a pspicture environment.

**for HTML output:** 1 \LWR@ProvidesPackagePass{pstricks}[2018/01/06]

```
2 \BeforeBeginEnvironment{pspicture}{%
3   \begin{ lateximage }[pspicture]%
4   }%
5 \AfterEndEnvironment{pspicture}{\end{ lateximage }}
```

---

**File 325 l warp-pxatbegshi.sty****§ 425 Package pxatbegshi**

Pkg pxatbegshi pxatbegshi is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pxatbegshi}[2017/11/04]

```
2 \LWR@origRequirePackage{l warp-atbegshi}
```

---

**File 326 l warp-pxeveryshi.sty****§ 426 Package pxeveryshi**

Pkg pxeveryshi pxeveryshi is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pxeveryshi}[2012/05/19]

```
2 \LWR@origRequirePackage{l warp-everyshi}
```

---

File 327 **l warp-pxftnright.sty**

§ 427 Package **pxftnright**

Pkg pxftnright pxftnright is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pxftnright}[2017/02/28]  
2 \LWR@origRequirePackage{l warp-ftnright}

---

File 328 **l warp-pxjahyper.sty**

§ 428 Package **pxjahyper**

Pkg pjaxahyper pjaxahyper is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{pxjahyper}[2018/07/15]

---

File 329 **l warp-quotchap.sty**

§ 429 Package **quotchap**

(Emulates or patches code by KARSTEN TINNEFELD, JAN KLEVER.)

Pkg quotchap quotchap is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{quotchap}[2019/07/09]  
2 \newcommand{\@quotchap}{}  
3 \newlength{\LWR@quotchapwidth}  
4  
5 \let\@printcites\relax  
6  
7 \newcommand\*{\@iprintcites}{%

Place the quotes inside a <div> of class quotchap, of the maximum selected width:

8 \begin{BlockClass}[max-width: \LWR@printlength{\LWR@quotchapwidth}]{quotchap}  
9 %\begin{minipage}{\LWR@quotchapwidth}  
10 \@quotchap  
11 %\end{minipage}  
12 \end{BlockClass}

Deactivate the quote printing:

```
13 \global\let\@printcites\relax
14 }
15
16 \NewEnviron{savequote}[1][\linewidth]{%
```

Remember the width, adjusted for HTML, and make the length assignment global, per:  
<https://tex.stackexchange.com/questions/300823/why-is-setlength-ineffective-inside-a-tabular-environment>

```
17 \setlength{\LWR@quotchapwidth}{#1*2}%
18 \global\LWR@quotchapwidth=\LWR@quotchapwidth%
```

Remember the body, and activate the quote printing:

```
19 \global\let\@quotchap\BODY
20 \global\let\@printcites\@iprintcites%
21 }
```

The quotation author is placed inside a <div> of class qauthor:

```
22 \newcommand{\qauthor}[1]{%
23   \LWR@stoppars%
24   \begin{BlockClass}{qauthor}%
25   {#1}%
26   \end{BlockClass}%
27   \LWR@startpars%
28 }
```

Fonts are ignored. Use css.

```
29 \newcommand{\qsetcnfont}[1]{}
30 \providecommand*\quotefont{}%
31 \providecommand*\qauthorfont{}
```

### File 330 **lwarf-quoting.sty**

#### § 430 Package **quoting**

(Emulates or patches code by THOMAS TITZ.)

Pkg **quoting** **quoting** is patched for use by **lwarf**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{quoting}[2014/01/28]

```
2 \xpatchcmd{\quoting}{\quo@begintext}
3   {\begin{LWR@blocktextcurrentfont}\quo@begintext}
4   {}
5   {\LWR@patcherror{quoting}{quoting}}
6
```

```
7 \xpatchcmd{\endquoting}{\quo@endtext}
8   {\quo@endtext\end{LWR@blocktextcurrentfont}\LWR@stoppars}
9   {}
10  {\LWR@patcherror{imakeidx}{endquoting}}
```

---

**File 331 l warp-ragged2e.sty****§ 431 Package ragged2e**

(Emulates or patches code by MARTIN SCHRÖDER.)

Pkg **ragged2e** **ragged2e** is emulated.

Discard all options for **l warp-ragged2e**:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{ragged2e}[2009/05/21]

```
2 \LetLtxMacro\Centering\centering
3 \LetLtxMacro\RaggedLeft\raggedleft
4 \LetLtxMacro\RaggedRight\raggedright
5 \newcommand*\{justifyin}{}
6 \newlength{\CenteringLeftskip}
7 \newlength{\RaggedLeftLeftskip}
8 \newlength{\RaggedRightLeftskip}
9 \newlength{\CenteringRightskip}
10 \newlength{\RaggedLeftRightskip}
11 \newlength{\RaggedRightRightskip}
12 \newlength{\CenteringParfillskip}
13 \newlength{\RaggedLeftParfillskip}
14 \newlength{\RaggedRightParfillskip}
15 \newlength{\JustifyingParfillskip}
16 \newlength{\CenteringParindent}
17 \newlength{\RaggedLeftParindent}
18 \newlength{\RaggedRightParindent}
19 \newlength{\JustifyingParindent}
20 \newenvironment*{Center}{\center}{\endcenter}
21 \newenvironment*{FlushLeft}{\flushleft}{\endflushleft}
22 \newenvironment*{FlushRight}{\flushright}{\endflushright}
23 \newenvironment*{justify}{\justify}{\endjustify}
```

---

**File 332 l warp-realscripts.sty****§ 432 Package realscripts**

(Emulates or patches code by WILL ROBERTSON.)

Pkg **realscripts** **realscripts** is emulated. See **l warp.css** for the <span> of class supsubscript.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{realscripts}[2016/02/13]

```

2 \let\realsuperscript{textsuperscript}
3 \let\realsubscript{textsubscript}
4
5 \let\fakesuperscript{textsuperscript}
6 \let\fakesubscript{textsubscript}
7
8 \newlength{\subsupersep}
9
10 \newcommand*{\LWR@realscriptsalign}{}
11
12 \newcommand*{\LWR@setrealscriptsalign}[1]{%
13   \renewcommand*{\LWR@realscriptsalign}{}%
14   \ifthenelse{\equal{#1}{c}}{%
15     \renewcommand{\LWR@realscriptsalign}{%
16       \LWR@print@mbox{text-align:center} ; %
17     }%
18   }%
19   \ifthenelse{\equal{#1}{r}}{%
20     \renewcommand{\LWR@realscriptsalign}{%
21       \LWR@print@mbox{text-align:right} ; %
22     }%
23   }%
24 }
25
26 \DeclareDocumentCommand \textsubsuperscript {s O{l} mm} {%
27   \LWR@setrealscriptsalign{#2}%
28   \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
29     \textsuperscript{#4}\textsubscript{#3}%
30   }%
31 }
32
33 \DeclareDocumentCommand \textsupersubscript {s O{l} mm} {%
34   \LWR@setrealscriptsalign{#2}%
35   \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
36     \textsubscript{#4}\textsuperscript{#3}%
37   }%
38 }

```

---

File 333 **l warp-refcheck.sty**

§ 433 Package **refcheck**

Pkg refcheck refcheck is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{refcheck}[2013/02/14]

```

2 \def\showrefnames{}
3 \def\norefnames{}
4 \def\showcitenames{}
5 \def\nocitenames{}
6 \def\setonmsgs{}
7 \def\setoffmsgs{}

```

```
8 \def\checkunlbld{}  
9 \def\ignoreunlbld{}  
10 \newcommand*\refcheckxrdoc[2][]{}
```

---

**File 334 l warp-register.sty****§ 434 Package register**

(Emulates or patches code by MATTHEW LOVELL.)

Pkg register register is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{register}[2019/01/01]

```
2 \xpatchcmd{\register}{%  
3   {\centering}  
4   {}  
5   \begin{center}%
6   \begin{ lateximage }[-register-\~\PackageDiagramAltText]%
7   }
8   {}
9   {\LWR@patcherror{register}{register}}%
10
11 \xpatchcmd{\endregister}{%
12   {\leftskip}%
13   {}  
14   \end{ lateximage }\end{center}%
15   \leftskip%
16   }%
17   {}
18   {\LWR@patcherror{register}{endregister}}%
19
20 \expandafter\xapptocmd\csname register*\endcsname{%
21   {}  
22   \begin{center}%
23   \begin{ lateximage }[-register-\~\PackageDiagramAltText]%
24   }
25   {}
26   {\LWR@patcherror{register}{register*}}%
27
28 \expandafter\xpatchcmd\csname endregister*\endcsname{%
29   {\leftskip}%
30   {}  
31   \end{ lateximage }\end{center}%
32   \leftskip%
33   }%
34   {}
35   {\LWR@patcherror{register}{endregister*}}%
36
37 \setlength{\regWidth}{5in}
```

---

File 335 **l warp-relsize.sty**

§ 435 Package **relsize**

(Emulates or patches code by DONALD ARSENAU, BERNIE COSELL, MATT SWIFT.)

Pkg **relsize** **relsize** is patched for use by **l warp**, and emulated for MATHJAX.

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified font-size.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarily restored, and so should work as expected.

 **not small** The HTML browser's setting for minimum font size may limit how small the output will be displayed.

**for HTML output:** 1 \LWR@ProvidesPackagePass{relsize}[2013/03/29]

```
2 \let\LWR@origrelsize\relsize
3 \LetLtxMacro{\LWR@origlarger}{\larger}
4 \LetLtxMacro{\LWR@origsmaller}{\smaller}
5 \let\LWR@relscale\relscale
6 \LetLtxMacro{\LWR@origtextlarger}{\textlarger}
7 \LetLtxMacro{\LWR@origtextsmaller}{\textsmaller}
8 \let\LWR@textscale\textscale
9
10 \appto{\LWR@restoreorigformatting}{%
11   \let\relsize{\LWR@origrelsize}%
12   \LetLtxMacro{\larger}{\LWR@origlarger}%
13   \LetLtxMacro{\smaller}{\LWR@origsmaller}%
14   \let\relscale{\LWR@relscale}%
15   \LetLtxMacro{\textlarger}{\LWR@origtextlarger}%
16   \LetLtxMacro{\textsmaller}{\LWR@origtextsmaller}%
17   \let{textscale}{\LWR@textscale}%
18 }
19
20 \newcounter{LWR@relsize临时}
21
22 \renewcommand*{\relsize}[1]{}
23 \renewcommand*{\larger}[1][]{}
24 \renewcommand*{\smaller}[1][]{}
25 \renewcommand*{\relscale}[1]{}
26
27 \renewcommand*{\textlarger}[2][1]{%
28   \setcounter{LWR@relsize临时}{100+ (#1*20)}%
29   \InlineClass{font-size:\arabic{LWR@relsize临时}\%}{textlarger}{#2}%
30 }
31
```

```

32 \renewcommand*\textsmaller}[2][1]{%
33 \setcounter{LWR@relsize}{100-(#1*20)}%
34 \InlineClass[font-size:\arabic{LWR@relsize}\%]{textsmaller}{#2}%
35 }
36
37 \renewcommand*\textscale}[2]{%
38 \setcounter{LWR@relsize}{100*\real{#1}}%
39 \InlineClass[font-size:\arabic{LWR@relsize}\%]{textscale}{#2}%
40 }

```

For MATHJAX:

```

41 \begin{warpMathJax}
42 \CustomizeMathJax{\newcommand{\mathlarger}[1]{#1}}
43 \CustomizeMathJax{\newcommand{\mathsmaller}[1]{#1}}
44 \end{warpMathJax}

```

### File 336 **lwarf-repeatindex.sty**

#### § 436 Package **repeatindex**

Pkg repeatindex repeatindex is emulated for lwarf.

⚠ style file lwarf must be used with a special style file:

```
\usepackage[makeindex,makeindexStyle={lwarf_repeatindex}]{lwarf}
```

where lwarf\_repeatindex.ist may be copied from the following modified version of lwarf.ist:

```

preamble
"\begin{theindex}
\providecommand*\lettergroupDefault[1]{}
\providecommand*\lettergroup[1]{%
\par\textbf{\#1}\par
\nopagebreak
}
"
headings_flag 1
heading_prefix "
\lettergroup{
heading_suffix "}"
delim_0 "], \hyperindexref{"
delim_1 ", \hyperindexref{"
delim_2 ", \hyperindexref{"
delim_n "}, \hyperindexref{"
delim_r "} -- \hyperindexref{"
delim_t "}"

item_0 "\n \item ["

```

(The modifications are the `delim_0` and `item_0` entries.)

**for HTML output:** 1 \LWR@ProvidesPackageDrop{repeatindex}[2001/10/13]

In the `l warp` core, `\LWR@indexitem` is modified to accept the optional `\item` argument.

```
2 \RequirePackage{makeidx}
3 \def\entryprefix{\itshape}
4 \def\entrypostfix{\dots}
```

---

### File 337 **l warp-resizegather.sty**

#### § 437 Package **resizegather**

Pkg `resizegather` `resizegather` is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{resizegather}[2016/05/16]

```
2 \newcommand*\resizegathersetup[1]{}

---


```

### File 338 **l warp-rmathbr.sty**

#### § 438 Package **rmathbr**

(Emulates or patches code by DENIS RYABOV.)

Pkg `rmathbr` `rmathbr` is used as-is for SVG math, and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{rmathbr}[2016/04/10]

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\def\*{\~}}
4 \CustomizeMathJax{\newcommand{\cdott}{\cdot}}
5 \CustomizeMathJax{\newcommand{\nobr}{}}
6 \end{warpMathJax}

---


```

### File 339 **l warp-rmpage.sty**

#### § 439 Package **rmpage**

Pkg `rmpage` `rmpage` is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{rmpage}[1997/09/29]

---

**File 340 l warp-romanbar.sty****§ 440 Package romanbar**

(Emulates or patches code by H.-MARTIN MÜNCH.)

Pkg romanbar romanbar is patched for use by l warp.

An inline class with an overline and underline is used.

**for HTML output:** 1 \LWR@ProvidesPackagePass{romanbar}[2012/01/01]

```
2 \DeclareRobustCommand{\Roman@bar}[1]{% #1 is in Roman, i.e. MMXII
3 \InlineClass[%  
4   text-decoration: overline underline ;
5 ]{\romanbar}{#1}%
6 }
```

---

**File 341 l warp-romanbarpagenumber.sty****§ 441 Package romanbarpagenumber**

Pkg romanbarpagenumber romanbarpagenumber is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{romanbarpagenumber}[2015/02/06]

---

**File 342 l warp-rotating.sty****§ 442 Package rotating**

(Emulates or patches code by ROBIN FAIRBAIRNS, SEBASTIAN RAHTZ, LEONOR BARROCA.)

Pkg rotating rotating is emulated.

All rotations are ignored in HTML output.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{rotating}[2016/08/11]

```
2 \RequirePackage{graphicx}
```

```
3 \LetLtxMacro{\sidewaystable}{\table}
4 \let\endsidewaystable\endtable
5
6 \LetLtxMacro{\sidewaysfigure}{\figure}
7 \let\endsidewaysfigure\endfigure
8
```

---

```

9 \newenvironment*{sideways}{}{}
10 \newenvironment*{turn}[1]{}{}
11 \newenvironment*{rotate}[1]{}{}
12 \NewDocumentCommand{\turnbox}{m +m}{#2}
13 \let\rotcaption\caption
14 \let\@makerotcaption\@makecaption

```

---

File 343 **l warp-rotfloat.sty**

§ 443 Package **rotfloat**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg **rotfloat** **rotfloat** is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{rotfloat}[2004/01/04]
2
3 \RequirePackage{float}
```

\newfloat {\langle 1: type\rangle} {\langle 2: placement\rangle} {\langle 3: ext\rangle} [{\langle 4: within\rangle}]

Emulates the \newfloat command from the float package. Sideways floats are \let to the same as regular floats.

“placement” is ignored.

```

4 \RenewDocumentCommand{\newfloat}{m m m o}{%
5 \IfValueTF{#4}{%
6 {%
7   \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}{%
8 }{%
9 {%
10   \DeclareFloatingEnvironment[fileext=#3]{#1}{%
11 }{%
12 \csletcs{sideways}{#1}{#1}{%
13 \csletcs{endsideways}{#1}{end#1}{%
```

Remember the float style:

```

14 \csedef{\LWR@floatstyle@#1}{\LWR@floatstyle}%
15 \csedef{\LWR@floatstyle@sideways#1}{\LWR@floatstyle}%
```

**newfloat** package automatically creates the \listof command for new floats, but **float** does not, so remove \listof here in case it is manually created later:

```

16 \cslet{\listof#1s}\relax%
17 \cslet{\listof#1es}\relax%
18 \cslet{\listofsideways#1s}\relax%
19 \cslet{\listofsideways#1es}\relax%
20 }
```

---

File 344 **l warp-rviewport.sty**

§ 444 Package **rviewport**

Pkg rviewport rviewport is honored inside a `\teximage`, and otherwise ignored for HTML output.

If rviewport is important for an image, enclose the image inside a `\teximage` environment.

**for HTML output:** 1 \LWR@ProvidesPackagePass{rviewport}[2011/08/27]

2 \define@key{igraph}{rviewport}{}

---

File 345 **l warp-savetrees.sty**

§ 445 Package **savetrees**

Pkg savetrees savetrees is ignored.

**for HTML output:** Discard all options for l warp-savetrees:

1 \LWR@ProvidesPackageDrop{savetrees}[2016/04/13]

---

File 346 **l warp-scalefnt.sty**

§ 446 Package **scalefnt**

(Emulates or patches code by D. CARLISLE.)

Pkg scalefnt scalefnt is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{scalefnt}

2 \DeclareRobustCommand\scalefont[1]{}

---

File 347 **l warp-schemata.sty**

§ 447 Package **schemata**

(Emulates or patches code by CHARLES P. SCHAUM.)

Pkg schemata schemata is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{schemata}[2016/01/25]

---

```

2 \LetLtxMacro{\LWR@schemata@origschema}{\schema}
3 \LetLtxMacro{\LWR@schemata@origSchema}{\Schema}
4
5 \renewcommand{\schema}[3][open]{%
6 \begin{lateximage}%
7 \LWR@print@normalsize
8 \LWR@schemata@origschema[#1]{#2}{#3}%
9 \end{lateximage}%
10 }
11
12 \renewcommand{\Schema}[5][open]{%
13 \begin{lateximage}%
14 \LWR@print@normalsize
15 \LWR@schemata@origSchema[#1]{#2}{#3}{#4}{#5}%
16 \end{lateximage}%
17 }

```

---

File 348 **lwarp-scrextend.sty**

§ 448 Package **scrextend**

Pkg scrextend scrextend is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{scrextend}[2018/03/30]

```

2 \DeclareDocumentCommand{\setkomafont}{m m}{}
3 \DeclareDocumentCommand{\addkomafont}{m m}{}
4 \DeclareDocumentCommand{\usekomafont}{m}{}
5
6 \DeclareDocumentCommand{\usefontofkomafont}{m}{}
7 \DeclareDocumentCommand{\useencodingofkomafont}{m}{}
8 \DeclareDocumentCommand{\usesizeofkomafont}{m}{}
9 \DeclareDocumentCommand{\usefamilyofkomafont}{m}{}
10 \DeclareDocumentCommand{\useseriesofkomafont}{m}{}
11 \DeclareDocumentCommand{\useshapeofkomafont}{m}{}
12
13 \AtBeginDocument{
14     \let\LWR@koma@orig@maketitle\maketitle
15     \DeclareDocumentCommand{\maketitle}{o}{\LWR@koma@orig@maketitle}
16 }
17
18 \DeclareDocumentCommand{\extratitle}{m}{}
19 \DeclareDocumentCommand{\titlehead}{m}{}
20 \DeclareDocumentCommand{\subject}{m}{}
21 \DeclareDocumentCommand{\publishers}{m}{\published{#1}}
22 \DeclareDocumentCommand{\uppertitleback}{m}{}
23 \DeclareDocumentCommand{\lowertitleback}{m}{}
24 \DeclareDocumentCommand{\dedication}{m}{}

```

```
25
26 \DeclareDocumentCommand{\ifthispageodd}{m m}{#1}
27
28 \DeclareDocumentCommand{\titlepagestyle}{}{}
29
30 \DeclareDocumentCommand{\cleardoublepageusingstyle}{m}{}
31 \DeclareDocumentCommand{\cleardoubleemptypage}{}{}
32 \DeclareDocumentCommand{\cleardoubleplainpage}{}{}
33 \DeclareDocumentCommand{\cleardoublestandardpage}{}{}
34 \DeclareDocumentCommand{\cleardoubleoddpage}{}{}
35 \DeclareDocumentCommand{\cleardoubleoddpageusingstyle}{m}{}
36 \DeclareDocumentCommand{\cleardoubleoddemptypage}{}{}
37 \DeclareDocumentCommand{\cleardoubleoddplainpage}{}{}
38 \DeclareDocumentCommand{\cleardoubleoddstandardpage}{}{}
39 \DeclareDocumentCommand{\cleardoubleevenpage}{}{}
40 \DeclareDocumentCommand{\cleardoubleevenpageusingstyle}{m}{}
41 \DeclareDocumentCommand{\cleardoubleevenemptypage}{}{}
42 \DeclareDocumentCommand{\cleardoubleevenplainpage}{}{}
43 \DeclareDocumentCommand{\cleardoubleevenstandardpage}{}{}
44
45 \DeclareDocumentCommand{\multiplefootnoteseparator}{}{%
46   \begingroup\let\thefootnotemark\multfootsep\@makefnmark\endgroup
47 }
48
49 \DeclareDocumentCommand{\multfootsep}{}{,}
50
51 \DeclareDocumentCommand{\footref}{m}{%
52   \begingroup
53     \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
54   \endgroup
55   \@footnotemark
56 }
57
58 \DeclareDocumentCommand{\deffootnote}{o m m m}{}
59 \DeclareDocumentCommand{\deffootnotemark}{m}{}
60 \DeclareDocumentCommand{\setfootnoterule}{o m}{}
61 \DeclareDocumentCommand{\raggedfootnote}{}{}
```

```
62 \DeclareDocumentCommand{\dictum}{o m}{%
63   \begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{dictum}
64     #2
65     \IfValueT{#1}{%
66       {
67         \LWR@stoppars%
68         \ifbool{FormatWP}{%
69           \begin{BlockClass}[\LWR@print@mbox{border-top: 1px solid gray}{dictumauthor}]
70             \begin{BlockClass}{dictumauthor}
71               \dictumauthorformat{#1}
72             \end{BlockClass}
73           }%
74         \end{BlockClassWP}
75       }%
76     }%
77   \end{LWR@BlockClassWP}
78 }%
79
80 \DeclareDocumentCommand{\dictumwidth}{}{%
81   \DeclareDocumentCommand{\dictumauthorformat}{m}{(#1)}
```

```

79 \DeclareDocumentCommand{\dictumrule}{}{%
80 \DeclareDocumentCommand{\raggedictum}{}{%
81 \DeclareDocumentCommand{\raggedictumtext}{}{%
82 \DeclareDocumentCommand{\raggedictumauthor}{}{%
83
84 \DeclareDocumentEnvironment{labeling}{o m}%
85 {%
86 \def\sc@septext{\#1}%
87 \list{}{}%
88 \let\makelabel\labelinglabel%
89 }%
90 {%
91 \endlist%
92 }%
93
94 \DeclareDocumentCommand{\labelinglabel}{m}{%
95 \qquad \sc@septext{%
96 }%
97
98 \let\addmargin\relax%
99 \let\endaddmargin\relax%
100 \cslet{addmargin*}{\relax}%
101 \cslet{endaddmargin*}{\relax}%
102 \NewDocumentEnvironment{addmargin}{s O{} m}%
103 {%
104 \LWR@stoppars%
105 \setlength{\LWR@templengthtwo}{#3}%
106 \ifblank{#2}%
107 {%
108   \begin{BlockClass}[%
109     \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthtwo}} ;%
110     \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%
111   ]{addmargin}%
112 }%
113 {%
114   \setlength{\LWR@templengthone}{#2}%
115   \begin{BlockClass}[%
116     \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ;%
117     \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%
118   ]{addmargin}%
119 }%
120 }%
121 {\end{BlockClass}\LWR@startpars}%
122
123 \ExplSyntaxOn%
124 \cs_new:cpxn {addmargin*} {\addmargin*}%
125 \cs_new_eq:cN {endaddmargin*} \endaddmargin%
126 \ExplSyntaxOff%

```

Ref to create a starred environment:

<https://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment>

```

122
123 \ExplSyntaxOn%
124 \cs_new:cpxn {addmargin*} {\addmargin*}%
125 \cs_new_eq:cN {endaddmargin*} \endaddmargin%
126 \ExplSyntaxOff%

```

```
127  
128 \DeclareDocumentCommand{\marginline}{m}{\marginpar{#1}}
```

File 349 **lwarf-scrhack.sty**

§ 449 Package **scrhack**

Pkg scrhack scrhack is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{scrhack}[2018/03/30]

File 350 **lwarp-scrlayer.sty**

§ 450 Package **scrlayer**

*(Emulates or patches code by MARKUS KOHM.)*

Pkg scrlayer scrlayer is emulated.

 Not fully tested! Please send bug reports!

**for HTML output:** 1 \LWR@ProvidesPackageDrop{scrlayer}[2018/03/30]

```
2 \newcommand*{\DeclareSectionNumberDepth}[2]{}
3 \newcommand*{\DeclareLayer}[2][]{}
4 \newcommand*{\DeclareNewLayer}[2][]{}
5 \newcommand*{\ProvideLayer}[2][]{}
6 \newcommand*{\RedeclareLayer}[2][]{}
7 \newcommand*{\ModifyLayer}[2][]{}
8 \newcommand*{\layerhalign}={}
9 \newcommand*{\layervalign}={}
10 \newcommand*{\layerxoffset}={}
11 \newcommand*{\layeryoffset}={}
12 \newcommand*{\layerwidth}={}
13 \newcommand*{\layerheight}={}
14 \providecommand*{\LenToUnit}[1]{\strip@pt\dimexpr#1*\p@\/\unitlength}
15 \newcommand*{\putUL}[1]{}
16 \newcommand*{\putUR}[1]{}
17 \newcommand*{\putLL}[1]{}
18 \newcommand*{\putLR}[1]{}
19 \newcommand*{\putC}[1]{}
20 \newcommand*{\GetLayerContents}[1]{}
21 \newcommand{\IfLayerExists}[3]{#3}
22 \newcommand*{\DestroyLayer}[1]{}
23 \newcommand*{\layercontentsmeasure}={}
24 \newcommand*{\currentpagestyle}={}
25 \newcommand*{\BeforeSelectAnyPageStyle}[1]{}
26 \newcommand*{\AfterSelectAnyPageStyle}[1]{}
27 \newcommand*{\DeclarePageStyleAlias}[2]{}
28 \newcommand*{\DeclareNewPageStyleAlias}[2]{}
```

```

29 \newcommand*{\ProvidePageStyleAlias}[2]{}
30 \newcommand*{\RedeclarePageStyleAlias}[2]{}
31 \newcommand*{\DestroyPageStyleAlias}[1]{}
32 \newcommand*{\GetRealPageStyle}[1]{}
33 \newcommand*{\DeclarePageStyleByLayers}[3][]{}
34 \newcommand*{\DeclareNewPageStyleByLayers}[3][]{}
35 \newcommand*{\ProvidePageStyleByLayers}[3][]{}
36 \newcommand*{\RedeclarePageStyleByLayers}[3][]{}
37 \NewDocumentCommand{\ForEachLayerOfPageStyle}{s m m}){}
38 \newcommand*{\AddLayersToPageStyle}[2]{}
39 \newcommand*{\AddLayersAtBeginOfPageStyle}[2]{}
40 \newcommand*{\AddLayersAtEndOfPageStyle}[2]{}
41 \newcommand*{\RemoveLayersFromPageStyle}[2]{}
42 \newcommand*{\AddLayersToPageStyleBeforeLayer}[3]{}
43 \newcommand*{\AddLayersToPageStyleAfterLayer}[3]{}
44 \newcommand*{\UnifyLayersAtPageStyle}[1]{}
45 \newcommand*{\ModifyLayerPageStyleOptions}[2]{}
46 \newcommand*{\AddToLayerPageStyleOptions}[2]{}
47 \newcommand{\IfLayerPageStyleExists}[3]{#3}
48 \newcommand{\IfRealLayerPageStyleExists}[3]{#3}
49 \newcommand{\IfLayerAtPageStyle}[4]{#4}
50 \newcommand{\IfSomeLayerAtPageStyle}[4]{#4}
51 \newcommand{\IfLayersAtPageStyle}[4]{#4}
52 \newcommand*{\DestroyRealLayerPageStyle}[1]{}
53 \@ifundefined{footheight}{\newlength\footheight}{}
54 \DeclareDocumentCommand{\automark}{s o m}){}
55 \DeclareDocumentCommand{\manualmark}{}{}
56 \DeclareDocumentCommand{\MakeMarkcase}{m}{#1}

57 \newcommand{\partmarkformat}(){}
58 \if@chapter
59 \newcommand{\chaptermarkformat}(){}
60 \fi
61 \newcommand{\sectionmarkformat}(){}
62 \DeclareDocumentCommand{\GenericMarkFormat}{m} {}

63 \newcommand*{\@mkleft}[1]{}
64 \newcommand*{\@mkright}[1]{}
65 \newcommand*{\@mkdouble}[1]{}
66 \newcommand*{\@mkboth}[2]{}
67 \newcommand*{\scrlayerInitInterface}[1][]{}
68 \newcommand{\scrlayerAddToInterface}[3][]{}
69 \newcommand{\scrlayerAddCsToInterface}[3][]{}
70 \newcommand{\scrlayerOnAutoRemoveInterface}[2][]{}

```

File 351 **lwarp-scrlayer-notecolumn.sty**

§ 451 Package **scrlayer-notecolumn**

(Emulates or patches code by MARKUS KOHM.)

Pkg scrlayer-notecolumn scrlayer-notecolumn is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output: 1 \LWR@ProvidesPackageDrop{scrlayer-notecolumn}[2018/02/02]

```
2 \newcommand*\{\DeclareNoteColumn}{2}[]{}
3 \newcommand*\{\DeclareNewNoteColumn}{2}[]{}
4 \newcommand*\{\ProvideNoteColumn}{2}[]{}
5 \newcommand*\{\RedeclareNoteColumn}{2}[]{}
6 \NewDocumentCommand{\makenote}{s o m}{\marginpar{\#3}}
7 \newcommand*\{\syncwithnotecolumn}{1}[]{}
8 \newcommand*\{\syncwithnotecolumns}{1}[]{}
9 \newcommand*\{\clearnotecolumn}{1}[]{}
10 \newcommand*\{\clearnotecolumns}{1}[]{}

---


```

#### File 352 l warp-scrlayer-scrpage.sty

### § 452 Package scrlayer-scrpage

(Emulates or patches code by MARKUS KOHM.)

Pkg scrlayer-scrpage scrlayer-scrpage is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output: 1 \LWR@ProvidesPackageDrop{scrlayer-scrpage}[2018/03/30]

```
2 \@ifundefined{footheight}{\newlength\footheight}{}
3 \NewDocumentCommand{\lehead}{s o m}{}
4 \NewDocumentCommand{\cehead}{s o m}{}
5 \NewDocumentCommand{\rehead}{s o m}{}
6 \NewDocumentCommand{\lohead}{s o m}{}
7 \NewDocumentCommand{\cohead}{s o m}{}
8 \NewDocumentCommand{\rohead}{s o m}{}
9 \NewDocumentCommand{\lefoot}{s o m}{}
10 \NewDocumentCommand{\cefoot}{s o m}{}
11 \NewDocumentCommand{\refoot}{s o m}{}
12 \NewDocumentCommand{\lofoot}{s o m}{}
13 \NewDocumentCommand{\cofoot}{s o m}{}
14 \NewDocumentCommand{\rofoot}{s o m}{}
15 \NewDocumentCommand{\ohead}{s o m}{}
16 \NewDocumentCommand{\chead}{s o m}{}
17 \NewDocumentCommand{\ihead}{s o m}{}
18 \NewDocumentCommand{\ofoot}{s o m}{}
19 \NewDocumentCommand{\cfoot}{s o m}{}
20 \NewDocumentCommand{\ifoot}{s o m}{}
21 \DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
22 \newcommand*\{\defpairofpagestyles}{3}[]{}
23 \newcommand*\{\newpairofpagestyles}{3}[]{}
24 \newcommand*\{\renewpairofpagestyles}{3}[]{}
25 \newcommand*\{\providepairofpagestyles}{3}[]{}

---


```

```
26 \newcommand*\{\clearmainofpairofpagestyles}{}
```

---

```

27 \newcommand*{\clearplainofpairofpagestyles}{}%
28 \newcommand*{\clearpairofpagestyles}{}%
29 \newcommand*{\clearscrheadings}{}%
30 \newcommand*{\clearscrheadfoot}{}%
31 \newcommand*{\clearscrplain}{}%

32 \NewDocumentCommand{\deftriplepagestyle}{m o o m m m m m m}{}%
33 \NewDocumentCommand{\newtriplepagestyle}{m o o m m m m m}{}%
34 \NewDocumentCommand{\renewtriplepagestyle}{m o o m m m m m}{}%
35 \NewDocumentCommand{\providetriplepagestyle}{m o o m m m m m}{}%
36 \newcommand*{\defpagestyle}[3]{}%
37 \newcommand*{\newpagestyle}[3]{}%
38 \newcommand*{\providepagestyle}[3]{}%
39 \newcommand*{\renewpagestyle}[3]{}%

```

---

File 353 **lwarf-scrpage2.sty**

§ 453 Package **scrpage2**

*(Emulates or patches code by MARKUS KOHM.)*

Pkg scrpage2 **scrpage2** is ignored.

⚠ Not fully tested! [Please send bug reports!](#)

**for HTML output:** 1 \LWR@ProvidesPackageDrop{scrpage2}[2018/03/30]

```

2 \@ifundefined{fooheight}{\newlength\fooheight}{}%
3 \NewDocumentCommand{\lehead}{o m}{}%
4 \NewDocumentCommand{\cehead}{o m}{}%
5 \NewDocumentCommand{\rehead}{o m}{}%
6 \NewDocumentCommand{\lohead}{o m}{}%
7 \NewDocumentCommand{\cohead}{o m}{}%
8 \NewDocumentCommand{\rohead}{o m}{}%
9 \NewDocumentCommand{\lefoot}{o m}{}%
10 \NewDocumentCommand{\cefoot}{o m}{}%
11 \NewDocumentCommand{\refoot}{o m}{}%
12 \NewDocumentCommand{\lofoot}{o m}{}%
13 \NewDocumentCommand{\cofoot}{o m}{}%
14 \NewDocumentCommand{\rofoot}{o m}{}%
15 \NewDocumentCommand{\ohead}{o m}{}%
16 \NewDocumentCommand{\chead}{o m}{}%
17 \NewDocumentCommand{\ihead}{o m}{}%
18 \NewDocumentCommand{\ofoot}{o m}{}%
19 \NewDocumentCommand{\cfoot}{o m}{}%
20 \NewDocumentCommand{\ifoot}{o m}{}%
21 \DeclareDocumentCommand{\automark}{o m}{}%
22 \DeclareDocumentCommand{\manualmark}{}{}%
23 \DeclareDocumentCommand{\MakeMarkcase}{m}{\#1}%
24 \NewDocumentCommand{\deftripstyle}{m o o m m m m m}{}%
25 \NewDocumentCommand{\defpagestyle}{s m m m}{}%
26 \NewDocumentCommand{\newpagestyle}{s m m m}{}%

```

```
27 \NewDocumentCommand{\renewpagestyle}{s m m m}{}  
28 \NewDocumentCommand{\providepagestyle}{s m m m}{}  
29 \newcommand{\partmarkformat}{}  
30 \if@chapter  
31 \newcommand{\chaptermarkformat}{}  
32 \fi  
33 \newcommand{\sectionmarkformat}{}  
34 \newcommand{\subsectionmarkformat}{}  
35 \newcommand{\subsubsectionmarkformat}{}  
36 \newcommand{\paragraphmarkformat}{}  
37 \newcommand{\ subparagraphmarkformat}{}  
38  
39 \newcommand*{\clearscrheadings}{}  
40 \newcommand*{\clearscrheadfoot}{}  
41 \newcommand*{\clearscrplain}{}  


---


```

File 354 **l warp-section.sty**

§ 454      Package **section**

Pkg **section** **section** is ignored.

(Emulates or patches code by OLIVER PRETZEL.)

**for HTML output:** 1 \LWR@ProvidesPackageDrop{section}

```
2 \ifx\chapter\undefined  
3 \def\chsize{\Large}\def\hdsizes{\huge}\else  
4 \def\chsize{\huge}\def\hdsizes{\Huge}  
5 \fi  
6 \let\ttsize\LARGE  
7 \let\ausize\large  
8 \let\dasize\large  
9 \let\secsize\Large  
10 \let\subsize\large  
11 \let\hdpos\raggedright  
12 \newcounter{hddepth}  
13 \let\fpind\relax  
14 \def\ttfnt{}  
15 \def\hdfnt{}  
16 \def\fefnt{}  
17 \def\thfnt{}  
18 \def\pgfnt{}  
19 \def\hmkfnt{}  
20 \let\mkcse\uppercase  
21 \def\hddot{}  
22 \def\cpdot{:}  
23 \def\nmdot{}  
24 \ifx\secindent\undefined  
25 \newdimen\secindent  
26 \newskip\secpreskp  
27 \newskip\secpstskp  
28 \newdimen\subindent
```

```
29 \newskip\subpreskp
30 \newskip\subpstskp
31 \newskip\parpstskp
32 \newcount\c@hddepth
33 \fi
```

---

**File 355 l warp-sectionbreak.sty****§ 455 Package sectionbreak**

*(Emulates or patches code by MICHAL HOFTICH.)*

Pkg sectionbreak sectionbreak is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{sectionbreak}[2018-01-03]

```
2 \renewcommand\asterism{\HTMLunicode{2042}}
3
4 \renewcommand\pre@sectionbreak{}
5 \renewcommand\post@sectionbreak{}
6
7 \renewcommand\print@sectionbreak[1]{%
8 \begin{center}
9 #1
10 \end{center}
11 }
12
```

---

**File 356 l warp-sectsty.sty****§ 456 Package sectsty**

*(Emulates or patches code by ROWLAND McDONNELL.)*

Pkg sectsty sectsty is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{sectsty}[2002/02/25]

```
2 \newcommand*\partfont{} [1] {}
3 \newcommand*\partnumberfont{} [1] {}
4 \newcommand*\parttitlefont{} [1] {}
5 \newcommand*\chapterfont{} [1] {}
6 \newcommand*\chaptnumberfont{} [1] {}
7 \newcommand*\chapttitlefont{} [1] {}
8 \newcommand*\sectionfont{} [1] {}
9 \newcommand*\subsectionfont{} [1] {}
10 \newcommand*\subsubsectionfont{} [1] {}
11 \newcommand*\paragraphfont{} [1] {}
12 \newcommand*\subparagraphfont{} [1] {}
13 \newcommand*\minisecfont{} [1] {}
```

```

14 \newcommand*{\allsectionsfont}[1] {}
15 \newcommand{\nohang}{}

\sectionrule is only to be used in *font commands, thus it is ignored.

16 \newcommand*{\sectionrule}[5]{}
17
18 \def\ulemheading#1#2{}
```

File 357 **l warp-semantic-markup.sty**

§ 457 Package **semantic-markup**

*(Emulates or patches code by ANDREW A. CASHNER.)*

Pkg semantic-markup **semantic-markup** is patched for use by **l warp**.

 If using the endnotes option, add \theendnotes where desired.

**for HTML output:** 1 \LWR@ProvidesPackagePass{semantic-markup}[2018/05/21]

The endnotes must be printed by the user before the end of the document, since the end is after the HTML footer, etc.

```

2 \ifendnotes
3 \RenewDocumentCommand{\SetupEndnotes}{}{%
4   \let\footnote=\endnote
5   \AtEndDocument{\DoBeforeEndnotes{\EndnoteFont\theendnotes}}%
6 }
7 \fi
```

HTML unicode characters from **musicography** are used.

```

8 \RequirePackage{musicography}
9
10 \let\f\musFlat
11 \let\sh\musSharp
12 \let\na\musNatural
```

The \musfig is placed inside a hashed image, with a simple alt tag.

```

13 \RequirePackage{amsmath}
14
15 \RenewDocumentCommand{\musfig}{ m m }{%
16   \LWR@subsingledollar*%
17   {#1/#2}% alt tag
18   {\musfig}% addl' hashing
19   {%
20     \LWR@origensuredmath{%
21       \genfrac{}{}{0pt}{1}{\text{#1}}{\text{#2}}%
22     }%
23   }%
}
```

```
24 }
```

The \meter is taken from **musicography**, and becomes a hashed image with a simple alt tag.

```
25 \RenewDocumentCommand{\meter}{ m m }{%
26     \musMeter{\#1}{\#2}%
27 }
```

---

**File 358 l warp-setspace.sty****§ 458 Package setspace**

(Emulates or patches code by ROBIN FAIRBAIRNS.)

Pkg setspace setspace is emulated.

Discard all options for l warp-setspace:

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{setspace}[2011/12/19]
2
3 \newcommand*{\setstretch}[1]{}%
4 \newcommand*{\SetSinglespace}[1]{}%
5 \newcommand*{\singespacing}{}%
6 \newcommand*{\onehalfspacing}{}%
7 \newcommand*{\doublespacing}{}%
8
9 \newenvironment*{singlespace}
10 {
11 \LWR@forcenewpage
12 \BlockClass{singlespace}
13 }
14 {\endBlockClass}
15
16 \newenvironment*{singespacing*}
17 {
18 \LWR@forcenewpage
19 \BlockClass{singespacing}
20 }
21 {\endBlockClass}
22
23 \newenvironment*{spacing}[1]{%
24
25 }{%
26
27 }
28
29 \newenvironment*{onehalfspace}
30 {
31 \LWR@forcenewpage
32 \BlockClass{onehalfspace}
33 }
34 {\endBlockClass}
```

```
35
36 \newenvironment*{doublespace}
37 {
38 \LWR@forcenewpage
39 \BlockClass{doublespace}
40 }
41 {\endBlockClass}
```

---

**File 359 l warp-shadow.sty****§ 459 Package shadow**

*(Emulates or patches code by MAURO ORLANDINI.)*

Pkg shadow shadow is emulated.

**for HTML output:** Discard all options for l warp-shadow:

```
1 \LWR@ProvidesPackageDrop{shadow}[2003/02/19]

2 \newdimen\sboxsep
3 \newdimen\sboxrule
4 \newdimen\sdim
5
6 \newcommand{\shabox}[1]{%
7 \InlineClass{shabox}{#1}%
8 }
```

---

**File 360 l warp-shapepar.sty****§ 460 Package shapepar**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg shapepar shapepar is patched for use by l warp. Shapes appear in print mode, as well as inside a lateximage, but are ignored for HTML.

**for HTML output:** 1 \LWR@ProvidesPackagePass{shapepar}[2013/03/26]

```
2 \newcommand*{\LWR@HTML@shapepar}[2][]{}
3 \LWR@formatted{shapepar}
4
5 \NewDocumentCommand{\LWR@HTML@cutout}{m d()}{}
6 \LWR@formatted{cutout}
```

---

File 361 **l warp-showidx.sty**

§ 461 Package **showidx**

Pkg showidx **showidx** is ignored.

**for HTML output:** Discard all options for l warp-showidx:

1 \LWR@ProvidesPackageDrop{showidx}[2014/09/29]

\@wrindex is redefined \AtBeginDocument by the l warp core.

---

File 362 **l warp-showkeys.sty**

§ 462 Package **showkeys**

(Emulates or patches code by DAVID CARLISLE, MORTEN HØGHLØM.)

Pkg showkeys **showkeys** is ignored.

**for HTML output:** Discard all options for l warp-showkeys:

1 \LWR@ProvidesPackageDrop{showkeys}[2014/10/28]

2 \NewDocumentCommand{\showkeys}{s}{}

---

File 363 **l warp-showtags.sty**

§ 463 Package **showtags**

Pkg showtags **showtags** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{showtags}% no version is given

2 \newcommand{\thecitetag}{1}{}

---

File 364 **l warp-sidecap.sty**

§ 464 Package **sidecap**

(Emulates or patches code by ROLF NIEPRASCHK, HUBERT GÄSSLEIN.)

Pkg sidecap **sidecap** is emulated.

**for HTML output:** Discard all options for `\l warp-sidecap`.

```
1 \LWR@ProvidesPackageDrop{sidecap}[2003/06/06]
```

See:

<http://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment>  
regarding the creation of starred environments with `xparse`.

```
2 \NewDocumentEnvironment{SCtable}{soo}
3 {\IfValueTF{#3}{\table[#3]}{\table}}
4 {\endtable}
5
6 \ExplSyntaxOn
7 \cs_new:cpx {SCtable*} {\SCtable*}
8 \cs_new_eq:cN {endSCtable*} \endSCtable
9 \ExplSyntaxOff
10
11
12 \NewDocumentEnvironment{SCfigure}{soo}
13 {\IfValueTF{#3}{\figure[#3]}{\figure}}
14 {\endfigure}
15
16 \ExplSyntaxOn
17 \cs_new:cpx {SCfigure*} {\SCfigure*}
18 \cs_new_eq:cN {endSCfigure*} \endSCfigure
19 \ExplSyntaxOff
20
21
22 \newenvironment*{wide}{}{}
```

### File 365 `l warp-sidenotes.sty`

#### § 465 Package **sidenotes**

(Emulates or patches code by ANDY THOMAS, OLIVER SCHEBAUM.)

Pkg `sidenotes` Patched for `\l warp`.

**for HTML output:** Load the original package:

```
1 \LWR@ProvidesPackagePass{sidenotes}
```

The following patch `sidenotes` for use with `\l warp`:

```
\sidecaption * [<entry>] [<offset>] {<text>}
2 \RenewDocumentCommand \sidecaption {s o o +m}
3 {
4     \LWR@stoppars
5     \begingroup
6     \captionsetup{style=sidecaption}
```

```

7  \IfBooleanTF{#1}
8  { % starred
9    \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
10   \caption*{#4}
11   \end{BlockClass}
12 }
13 { % unstarred
14 \IfNoValueOrEmptyTF{#2}
15   {\def\@ sidenotes@ sidecaption@ tof{#4}}
16   {\def\@ sidenotes@ sidecaption@ tof{#2}}
17   \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
18   \caption[\@ sidenotes@ sidecaption@ tof]{#4}
19   \end{BlockClass}
20 }
21 \endgroup
22 \LWR@startpars
23 }
```

Borrowed from the `lwarp` version of `keyfloat`:

```

24 \NewDocumentEnvironment{KFLTsidenotes@marginfloat}{O{-1.2ex} m}
25 {%
26 \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
27 \captionsetup{type=#2}%
28 }
29 {%
30 \endLWR@BlockClassWP%
31 }
32
33 \RenewDocumentEnvironment{marginfigure}{o}
34 { \begin{KFLTsidenotes@marginfloat}{figure} }
35 { \end{KFLTsidenotes@marginfloat} }
36
37 \RenewDocumentEnvironment{margintable}{o}
38 { \begin{KFLTsidenotes@marginfloat}{table} }
39 { \end{KFLTsidenotes@marginfloat} }
```

The following were changed by `sidenotes`, and now are reset back to their `lwarp`-supported originals:

Restoring the definition from the `LATEX2E article.cls` source:

```

40 \renewenvironment{figure*}
41           {\@dblfloat{figure}}
42           {\end@dblfloat}
43
44 \renewenvironment{table*}
45           {\@dblfloat{table}}
46           {\end@dblfloat}
```

---

**File 366 l warp-SIunits.sty****§ 466 Package Slunits**

(Emulates or patches code by MARCEL HELDOORN.)

Pkg SIunits Slunits is patched for use by l warp.

It is recommended to use \unit where possible, which combines the entire expression into a single lateximage, and adds the alt tag containing the LATEX code, allowing for copy/paste. When units are used outside of the \unit macro, each unit macro will have its own lateximage, and each will have the alt tag set according to \MathImageAltText, which defaults to (math image).

**for HTML output:** 1 \LWR@ProvidesPackagePass{SIunits}[2007/12/02]

Patched for copy/paste with the HTML alt tag:

```
2 \DeclareRobustCommand{\unit}[2]{%
3 \@inunitcommandtrue%    original
4 \LWR@subsingle$*% l warp
5 {%
6   alt tag
7   \textbackslash{}unit\{\LWR@HTMLsanitize{\#1}\}%
8   \{ \LWR@HTMLsanitize{\#2}\}% extra space
9 }%
10 {%
11   \LWR@origensuredmath% l warp modification
12   \SI@fstyle{\#1\@qsk\period@active{\#2}}% original
13 }%
14 }% contents
15 \@inunitcommandfalse% original
16 }
```

---

**File 367 l warp-siunitx.sty****§ 467 Package siunitx**

(Emulates or patches code by JOSEPH WRIGHT.)

Pkg siunitx siunitx is patched for use by l warp.

**fractions** Due to *pdftotext* limitations, fraction output is replaced by symbol output for per-mode and quotient-mode.

**⚠ math mode required** Some units will require that the expression be placed inside math mode.

**⚠ tabular** Tabular S columns are rendered as simple c columns, and tabular s columns are not

supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

**⚠ MathJax** For math mode with SVG display, the original `siunitx` code is used while generating the SVG image. For text mode, `l warp` uses an emulation which provides a very effective HTML interpretation of `siunitx`. For math expressions while using MATHJAX, a limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. `siunitx` macros with more than one optional value cannot absorb the second optional value, and complicated parsing such as for `\ang` is not supported. The result usually looks fine, and otherwise is enough to get the meaning across.

`l warp`'s MATHJAX emulation for `siunitx` is meant to be a stop-gap measure until an extension is included in MATHJAX. As of this writing, the third-party `siunitx` extension for MATHJAX is not currently hosted at any public CDN, thus `siunitx` is not usable with this extension unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJax script, but `l warp`'s emulation would have to be disabled as well.

Document modifications required for MATHJAX:

#### custom units

- Custom units may be added with `\CustomizeMathJax`. See the `l warp-siunitx` code for examples.

#### ⚠ unit spacing

- Units work better using `~` between units instead of using periods.

#### ⚠ \square, \cubic

- To square or cube compound units, enclose the following compound units in braces:

`\cubic{\centi\meter}`

Single units do not require braces.

Also see [MATHJAX option](#), section 8.7.4.

#### for HTML output:

```

1 \RequirePackage{xcolor}%
2   for \convertcolorspec
3 \LWR@ProvidesPackagePass{siunitx}[2018/05/17]

4 \AtBeginDocument{%
5   in case textcomp was not loaded
6   \DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
7   \DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
8   \DeclareSIUnit\elementarycharge{\textit{e}}
9   \DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
10  \DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
11  \DeclareSIUnit\planckbar{\LWR@siunitx@\textit{h}}
12 }%
13 AtBeginDocument
14 
```

`\@ensuredmath` is not supported inside an `\hbox`, so it must temporarily be restored to its original. Similar for `\mbox`. SVG math is created explicitly when necessary, using `\LWR@subsingle$`.

```

12
13 \ExplSyntaxOn
14 %
```

Modified to set set HTML \textcolor if not black:

```
15 \cs_undefine:N \__siunitx_print_aux:
16 \cs_new_protected:Npn \__siunitx_print_aux:
17  {
18      \text
19      {
20          \__siunitx_ensure_ltr:n
21          {
22              \color@begingroup
23              \__siunitx_print_color:
24              \__siunitx_font_shape:
25              \__siunitx_font_weight:
26              \use:c
27              {
28                  @_ \l__siunitx_print_type_tl _ 
29                  text \l__siunitx_font_family_tl :
30              }
31              \bool_if:NTF \l__siunitx_font_math_mode_bool
32              { \__siunitx_print_math: }
33              {
34                  \LWR@findcurrenttextcolor% lwarp
35                  \ifdefstring{\LWR@tempcolor}{000000}% lwarp
36                  {\__siunitx_print_text:}% lwarp
37                  {% lwarp
38                      \LWR@textcurrentcolor% lwarp
39                      \__siunitx_print_text:
40                  }% lwarp
41                  }% lwarp
42              }
43              \color@endgroup
44          }
45      }
46  }
47
48
49 \cs_undefine:N \__siunitx_set_math_fam:n
50 \cs_new_protected:Npn \__siunitx_set_math_fam:n #1 {
51     \int_new:c { c__siunitx_math #1 _int }
52     \group_begin:% lwarp
53     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
54     \LetLtxMacro\mbox\lWR@print@mbox% lwarp
55     \hbox_set:Nn \l__siunitx_tmp_box
56     {
57         \ensuremath
58         {
59             \use:c { math #1 }
60             {
61                 \int_gset:cn { c__siunitx_math #1 _int } { \fam }
62             }
63         }
64     }
65     \group_end:% lwarp
66 }
```

```

68 \cs_undefine:N \__siunitx_combined_output:n
69 \cs_new_protected:Npn \__siunitx_combined_output:n #1 {
70     \group_begin:% l warp
71     \LetLtxMacro\@ensuredmath\lWR@origensuredmath% l warp
72     \LetLtxMacro\mbox\lWR@print@mbox% l warp
73     \bool_if:NTF \l__siunitx_number_parse_bool
74     {
75         \tl_clear:N \l__siunitx_number_out_tl
76         \bool_set_false:N \l__siunitx_number_compound_bool
77         \__siunitx_number_output_parse:n {#1}
78     }
79 }
```

For parse-numbers=false:

```

80     \__siunitx_unit_output_pre_print:
81     \begingroup% l warp
82         \boolfalse{mathjax}% l warp
83 %     \__siunitx_print:nn { number } { \ensuremath {#1} } %
84         \lWR@subsingle dollar% l warp
85         \textbackslash( \lWR@HTMLsanitize{#1} \textbackslash)% l warp
86         \{siunitx\}%
87             \__siunitx_print:nn { number } { %
88                 \lWR@origensuredmath{#1}%
89             }%
90         \} l warp
91     \endgroup% l warp
92     \__siunitx_unit_output_print:
93 }
94 \group_end:% l warp
95 }
```

For parse-numbers=false:

```

96 \cs_set_protected:Npn \__siunitx_range_numbers_aux:n #1
97 {
98     \bool_if:NTF \l__siunitx_number_parse_bool
99     {
100         \tl_clear:N \l__siunitx_number_out_tl
101         \tl_clear:N \l__siunitx_number_out_saved_tl
102         \bool_set_false:N \l__siunitx_number_compound_bool
103         \__siunitx_number_output_parse:n {#1}
104         \bool_if:NT \l__siunitx_number_compound_bool
105             \msg_error:nnx { siunitx } { multi-part-range } {#1} }
106     }
107     {
108         \__siunitx_unit_output_pre_print:
109         \begingroup% l warp
110             \boolfalse{mathjax}% l warp
111 %         \__siunitx_print:nn { number } {#1}
112             \lWR@subsingle dollar% l warp
113             \textbackslash( \lWR@HTMLsanitize{#1} \textbackslash)% l warp
114             \{siunitx\}%
115                 \__siunitx_print:nn { number } {
116                     \lWR@origensuredmath{#1} }
```

```

117          } % l warp
118          }% l warp
119      \endgroup% l warp
120      \__siunitx_unit_output_print:
121  }
122 }
```

For parse-numbers=false:

```

123 \cs_set_protected:Npn \__siunitx_angle_print_direct_aux:nn #1#2 {
124   \tl_if_empty:nF {#1}
125   {
126     \tl_set:Nn \l__siunitx_unit_tl {#2}
127     \begingroup%
128       \boolfalse{mathjax}%
129       \__siunitx_print:nn { number } {#1}
130       \LWR@subsingleollar{%
131         \textbackslash( \LWR@HTMLsanitize{#1} \textbackslash)%
132       }{siunitx}{%
133         \__siunitx_print:nn { number } {%
134           \LWR@origensuredmath{#1}%
135         }%
136       }%
137     \endgroup%
138     \__siunitx_unit_output_print:
139   }
140 }
141 %
```

For quotients, the fraction code is replaced by the symbol code:

```

142 \cs_undefine:N \__siunitx_number_output_quotient_fraction:
143 \cs_new_protected:Npn \__siunitx_number_output_quotient_fraction: {
144   \bool_set_true:N \l__siunitx_number_compound_bool
145   \__siunitx_number_output_quotient_aux_i:
146   \tl_set_eq:NN \l__siunitx_number_out_tl
147   \l__siunitx_number_numerator_tl
148   \tl_put_right:NV \l__siunitx_number_out_tl \l__siunitx_output_quotient_tl
149   \tl_put_right:NV \l__siunitx_number_out_tl
150   \l__siunitx_number_denominator_tl
151   \__siunitx_number_output_single_aux:
152 }
```

For units, the fraction code is replaced by the symbol code:

```

153 \cs_undefine:N \__siunitx_unit_format_fraction_fraction:
154 \cs_new_protected:Npn \__siunitx_unit_format_fraction_fraction: {
155   \__siunitx_unit_format_fraction_symbol_aux:
156   \int_compare:nNnT { \l__siunitx_unit_denominator_int } > { 1 }
157   {
158     \bool_if:NT \l__siunitx_unit_denominator_bracket_bool
159     {
160       \tl_put_left:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_open_tl
161       \tl_put_right:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_close_tl
162     }
163 }
```

```
163      }
164  \tl_set_eq:NN \l__siunitx_unit_tl \l__siunitx_unit_numerator_tl
165  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_per_symbol_tl
166  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_unit_denominator_tl
167 }

168 \cs_undefine:N \__siunitx_angle_print_astronomy_aux:
169 \cs_new_protected:Npn \__siunitx_angle_print_astronomy_aux: {
170   \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-integer }
171   \l__siunitx_tmpa_tl
172   { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
173 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
174 {%
175   \hbox_set:Nn \l__siunitx_angle_marker_box
176   {
177     \__siunitx_print:nn { number } { \l__siunitx_output_decimal_tl }
178   }
179   \hbox_set:Nn \l__siunitx_angle_unit_box
180   {
181     \__siunitx_print:nV { unit } \l__siunitx_unit_tl
182     \skip_horizontal:n { -\scriptspace }
183   }
184   \__siunitx_angle_print_astronomy_aux:n { marker }
185   \__siunitx_angle_print_astronomy_aux:n { unit }
186   \hbox_set:Nn \l__siunitx_angle_marker_box
187   {
188     \box_use:N \l__siunitx_angle_marker_box
189     \box_use:N \l__siunitx_angle_unit_box
190   }
191   \dim_compare:nNnTF
192   { \l__siunitx_angle_marker_dim } > { \l__siunitx_angle_unit_dim }
193   { \__siunitx_angle_print_astronomy_marker: }
194   { \__siunitx_angle_print_astronomy_unit: }
195 }%
196 {%
197   \__siunitx_print:nV { unit } \l__siunitx_unit_tl
198   \__siunitx_print:nn { number } { \l__siunitx_output_decimal_tl }
199 }%
200 \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-decimal }
201 \l__siunitx_tmpa_tl
202 { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
203 }

204 \cs_undefine:N \__siunitx_textsuperscript:n
205 \cs_new_protected:Npn \__siunitx_textsuperscript:n #1 {\textsuperscript{#1} }

206 \RenewDocumentCommand \num { o m } {
207   \leavevmode
208   \group_begin:% lwarp
209   \LetLtxMacro{@ensuredmath}{\LWR@origensuredmath}% lwarp
210   \LetLtxMacro{\mbox}{\LWR@print@mbox}% lwarp
211   \bool_set_false:N \l__siunitx_font_set_bool
212   \IfNoValueF {#1}
213   { \keys_set:nn { siunitx } {#1} }
```

```
214     \__siunitx_number_output:n {#2}
215     \group_end:% l warp
216 }
217
218 \RenewDocumentCommand \numrange { o m m } {
219     \leavevmode
220     \group_begin:% l warp
221     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% l warp
222     \LetLtxMacro\mbox\LWR@print@mbox% l warp
223     \bool_set_false:N \l__siunitx_font_set_bool
224     \IfNoValueF {#1}
225         { \keys_set:nn { siunitx } {#1} }
226         \__siunitx_range_numbers:nn {#2} {#3}
227     \group_end:% l warp
228 }
229
230 \RenewDocumentCommand \ang { o > { \SplitArgument { 2 } { ; } } m } {
231     \group_begin:% l warp
232     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% l warp
233     \LetLtxMacro\mbox\LWR@print@mbox% l warp
234     \IfNoValueF {#1}
235         { \keys_set:nn { siunitx } {#1} }
236         \__siunitx_angle_output:nnn #2
237     \group_end:% l warp
238 }
239
240 \RenewDocumentCommand \si { o m } {
241     \leavevmode
242     \group_begin:% l warp
243     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% l warp
244     \LetLtxMacro\mbox\LWR@print@mbox% l warp
245     \bool_set_false:N \l__siunitx_font_set_bool
246     \IfNoValueTF {#1}
247         { \__siunitx_unit_output:nn {#2} { } }
248         {
249             \keys_set:nn { siunitx } {#1}
250             \__siunitx_unit_output:nn {#2} {#1}
251         }
252     \group_end:% l warp
253 }
254
255
256 \RenewDocumentCommand{\SIRange}{o m m m}
257 {%
258     \leavevmode
259     \group_begin:% l warp
260     \LetLtxMacro\@ensuredmath\LWR@origensuredmath% l warp
261     \LetLtxMacro\mbox\LWR@print@mbox% l warp
262     \bool_set_false:N \l__siunitx_font_set_bool
263     \IfNoValueTF {#1}
264         { \__siunitx_range_unit:nnnn {#4} { } {#2} {#3} }
265         {
266             \keys_set:nn { siunitx } {#1}
267             \__siunitx_range_unit:nnnn {#4} {#1} {#2} {#3}
268         }
```

```

269 \group_end:% lwarp
270 }
271
272 \ExplSyntaxOff

```

For MATHJAX. (The following runs much faster as separate \CusomizeMathJax calls instead of one single call.)

```

273 \begin{warpMathJax}
274 \LWR@infoprocessingmathjax{siunitx}
275
276 \CustomizeMathJax{\newcommand{\ang}[2]{\mathrm{#2}\degree}}
277 \CustomizeMathJax{\newcommand{\num}[2]{\mathrm{#2}}}
278 \CustomizeMathJax{\newcommand{\si}[2]{\mathrm{#2}}}
279 %
280 % \SI[opt]{num}{preunit}{unit}
281 \CustomizeMathJax{\newcommand{\LWSI}[2]{\mathrm{\#1}\LWSInumber,\#2}}
282 \CustomizeMathJax{\newcommand{\SI}[2]{\def\LWSInumber{\#2}\LWSI}}
283 %
284 \CustomizeMathJax{\newcommand{\numlist}[2]{\mathrm{#2}}}
285 \CustomizeMathJax{\newcommand{\numrange}[3]{\mathrm{#2-- #3}}}
286 \CustomizeMathJax{\newcommand{\SIList}[3]{\mathrm{\#2\,,\#3}}}
287 \CustomizeMathJax{\newcommand{\SIRange}[4]{\mathrm{\#2\,,\#4-- #3\,,\#4}}}
288 \CustomizeMathJax{\newcommand{\tablenum}[2]{\mathrm{#2}}}
289 %
290 \CustomizeMathJax{\newcommand{\ampere}{\mathrm{A}}}
291 \CustomizeMathJax{\newcommand{\candela}{\mathrm{cd}}}
292 \CustomizeMathJax{\newcommand{\kelvin}{\mathrm{K}}}
293 \CustomizeMathJax{\newcommand{\kilogram}{\mathrm{kg}}}
294 \CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
295 \CustomizeMathJax{\newcommand{\mole}{\mathrm{mol}}}
296 \CustomizeMathJax{\newcommand{\second}{\mathrm{s}}}
297 %
298 \CustomizeMathJax{\newcommand{\becquerel}{\mathrm{Bq}}}
299 \CustomizeMathJax{\newcommand{\degreeCelsius}{\text{\textnormal{\textcircled{2103}}}}}
300 \CustomizeMathJax{\newcommand{\coulomb}{\mathrm{C}}}
301 \CustomizeMathJax{\newcommand{\farad}{\mathrm{F}}}
302 \CustomizeMathJax{\newcommand{\gray}{\mathrm{Gy}}}
303 \CustomizeMathJax{\newcommand{\hertz}{\mathrm{Hz}}}
304 \CustomizeMathJax{\newcommand{\henry}{\mathrm{H}}}
305 \CustomizeMathJax{\newcommand{\joule}{\mathrm{J}}}
306 \CustomizeMathJax{\newcommand{\katal}{\mathrm{kat}}}
307 \CustomizeMathJax{\newcommand{\lumen}{\mathrm{lm}}}
308 \CustomizeMathJax{\newcommand{\lux}{\mathrm{lx}}}
309 \CustomizeMathJax{\newcommand{\newton}{\mathrm{N}}}
310 \CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
311 \CustomizeMathJax{\newcommand{\pascal}{\mathrm{Pa}}}
312 \CustomizeMathJax{\newcommand{\radian}{\mathrm{rad}}}
313 \CustomizeMathJax{\newcommand{\siemens}{\mathrm{S}}}
314 \CustomizeMathJax{\newcommand{\sievert}{\mathrm{Sv}}}
315 \CustomizeMathJax{\newcommand{\steradian}{\mathrm{sr}}}
316 \CustomizeMathJax{\newcommand{\tesla}{\mathrm{T}}}
317 \CustomizeMathJax{\newcommand{\volt}{\mathrm{V}}}
318 \CustomizeMathJax{\newcommand{\watt}{\mathrm{W}}}
319 \CustomizeMathJax{\newcommand{\weber}{\mathrm{Wb}}}

```

```
320 \CustomizeMathJax{\newcommand{\day}{\mathrm{d}}}
321 \CustomizeMathJax{\newcommand{\degree}{\mathrm{^\circ}}}
322 \CustomizeMathJax{\newcommand{\hectare}{\mathrm{ha}}}
323 \CustomizeMathJax{\newcommand{\hour}{\mathrm{h}}}
324 \CustomizeMathJax{\newcommand{\litre}{\mathrm{l}}}
325 \CustomizeMathJax{\newcommand{\liter}{\mathrm{L}}}
326 \CustomizeMathJax{\newcommand{\arcminute}{^{\prime}}}
327 \CustomizeMathJax{\newcommand{\minute}{\mathrm{min}}}
328 \CustomizeMathJax{\newcommand{\arcsecond}{^{\prime\prime}}}
329 \CustomizeMathJax{\newcommand{\tonne}{\mathrm{t}}}
330 \CustomizeMathJax{\newcommand{\astronomicalunit}{\mathrm{au}}}
331 \CustomizeMathJax{\newcommand{\atomicmassunit}{\mathrm{u}}}
332 \CustomizeMathJax{\newcommand{\bohr}{\mathrm{a\_0}}}
333 \CustomizeMathJax{\newcommand{\clight}{\mathrm{c\_0}}}
334 \CustomizeMathJax{\newcommand{\dalton}{\mathrm{D}\_a}}
335 \CustomizeMathJax{\newcommand{\electronmass}{\mathrm{m}\_e}}
336 \CustomizeMathJax{\newcommand{\electronvolt}{\mathrm{eV}}}
337 \CustomizeMathJax{\newcommand{\elementarycharge}{\mathrm{e}}}
338 \CustomizeMathJax{\newcommand{\hartree}{\mathrm{E}\_\mathrm{h}}}
339 \CustomizeMathJax{\newcommand{\planckbar}{\mathrm{\hbar}}}
340 \CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\AA}}}
341 \CustomizeMathJax{\let\LRorigbar\bar}
342 \CustomizeMathJax{\newcommand{\bar}{\mathrm{bar}}}
343 \CustomizeMathJax{\newcommand{\barn}{\mathrm{b}}}
344 \CustomizeMathJax{\newcommand{\bel}{\mathrm{B}}}
345 \CustomizeMathJax{\newcommand{\decibel}{\mathrm{dB}}}
346 \CustomizeMathJax{\newcommand{\knot}{\mathrm{kn}}}
347 \CustomizeMathJax{\newcommand{\mmHg}{\mathrm{mmHg}}}
348 \CustomizeMathJax{\newcommand{\nauticalmile}{\mathrm{M}}}
349 \CustomizeMathJax{\newcommand{\neper}{\mathrm{Np}}}
350 %
351 \CustomizeMathJax{\newcommand{\yocto}{\mathrm{y}}}
352 \CustomizeMathJax{\newcommand{\zepto}{\mathrm{z}}}
353 \CustomizeMathJax{\newcommand{\atto}{\mathrm{a}}}
354 \CustomizeMathJax{\newcommand{\femto}{\mathrm{f}}}
355 \CustomizeMathJax{\newcommand{\pico}{\mathrm{p}}}
356 \CustomizeMathJax{\newcommand{\nano}{\mathrm{n}}}
357 \CustomizeMathJax{\newcommand{\micro}{\mathrm{\mu}}}
358 \CustomizeMathJax{\newcommand{\milli}{\mathrm{m}}}
359 \CustomizeMathJax{\newcommand{\centi}{\mathrm{c}}}
360 \CustomizeMathJax{\newcommand{\deci}{\mathrm{d}}}
361 \CustomizeMathJax{\newcommand{\deca}{\mathrm{da}}}
362 \CustomizeMathJax{\newcommand{\hecto}{\mathrm{h}}}
363 \CustomizeMathJax{\newcommand{\kilo}{\mathrm{k}}}
364 \CustomizeMathJax{\newcommand{\mega}{\mathrm{M}}}
365 \CustomizeMathJax{\newcommand{\giga}{\mathrm{G}}}
366 \CustomizeMathJax{\newcommand{\tera}{\mathrm{T}}}
367 \CustomizeMathJax{\newcommand{\peta}{\mathrm{P}}}
368 \CustomizeMathJax{\newcommand{\exa}{\mathrm{E}}}
369 \CustomizeMathJax{\newcommand{\zetta}{\mathrm{Z}}}
370 \CustomizeMathJax{\newcommand{\yotta}{\mathrm{Y}}}
371 %
372 \CustomizeMathJax{\newcommand{\percent}{\mathrm{\%}}}
373 %
374 \CustomizeMathJax{\newcommand{\meter}{\mathrm{m}}}
```

```
375 \CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
376 %
377 \CustomizeMathJax{\newcommand{\gram}{\mathrm{g}}}
378 \CustomizeMathJax{\newcommand{\kg}{\mathrm{kilo\,gram}}}
379 \CustomizeMathJax{\newcommand{\of}[1]{_{\mathrm{\#1}}}}
380 \CustomizeMathJax{\newcommand{\squared}{^2}}
381 \CustomizeMathJax{\newcommand{\square}{[1]\mathrm{\#1}^2}}
382 \CustomizeMathJax{\newcommand{\cubed}{^3}}
383 \CustomizeMathJax{\newcommand{\cubic}{[1]\mathrm{\#1}^3}}
384 \CustomizeMathJax{\newcommand{\per}{/}}
385 \CustomizeMathJax{\newcommand{\celsius}{\mathrm{\text{\scriptsize{u}}\kern-0.1em\scriptsize{x2103}}}}
386 %
387 \CustomizeMathJax{\newcommand{\fg}{\mathrm{femto\,gram}}}
388 \CustomizeMathJax{\newcommand{\pg}{\mathrm{pico\,gram}}}
389 \CustomizeMathJax{\newcommand{\ng}{\mathrm{nano\,gram}}}
390 \CustomizeMathJax{\newcommand{\ug}{\mathrm{micro\,gram}}}
391 \CustomizeMathJax{\newcommand{\mg}{\mathrm{milli\,gram}}}
392 \CustomizeMathJax{\newcommand{\g}{\mathrm{gram}}}
393 \CustomizeMathJax{\newcommand{\kg}{\mathrm{kilo\,gram}}}
394 %
395 \CustomizeMathJax{\newcommand{\amu}{\mathrm{u}}}
396 %
397 \CustomizeMathJax{\newcommand{\pm}{\mathrm{pico\,metre}}}
398 \CustomizeMathJax{\newcommand{\nm}{\mathrm{nano\,metre}}}
399 \CustomizeMathJax{\newcommand{\um}{\mathrm{micro\,metre}}}
400 \CustomizeMathJax{\newcommand{\mm}{\mathrm{milli\,metre}}}
401 \CustomizeMathJax{\newcommand{\cm}{\mathrm{centi\,metre}}}
402 \CustomizeMathJax{\newcommand{\dm}{\mathrm{deci\,metre}}}
403 \CustomizeMathJax{\newcommand{\m}{\mathrm{metre}}}
404 \CustomizeMathJax{\newcommand{\km}{\mathrm{kilo\,metre}}}
405 %
406 \CustomizeMathJax{\newcommand{\as}{\mathrm{atto\,second}}}
407 \CustomizeMathJax{\newcommand{\fs}{\mathrm{femto\,second}}}
408 \CustomizeMathJax{\newcommand{\ps}{\mathrm{pico\,second}}}
409 \CustomizeMathJax{\newcommand{\ns}{\mathrm{nano\,second}}}
410 \CustomizeMathJax{\newcommand{\us}{\mathrm{micro\,second}}}
411 \CustomizeMathJax{\newcommand{\ms}{\mathrm{milli\,second}}}
412 \CustomizeMathJax{\newcommand{\s}{\mathrm{second}}}
413 %
414 \CustomizeMathJax{\newcommand{\fmol}{\mathrm{femto\,mol}}}
415 \CustomizeMathJax{\newcommand{\pmol}{\mathrm{pico\,mol}}}
416 \CustomizeMathJax{\newcommand{\nmol}{\mathrm{nano\,mol}}}
417 \CustomizeMathJax{\newcommand{\umol}{\mathrm{micro\,mol}}}
418 \CustomizeMathJax{\newcommand{\mmol}{\mathrm{milli\,mol}}}
419 \CustomizeMathJax{\newcommand{\mol}{\mathrm{mol}}}
420 \CustomizeMathJax{\newcommand{\kmol}{\mathrm{kilo\,mol}}}
421 %
422 \CustomizeMathJax{\newcommand{\pA}{\mathrm{pico\,ampere}}}
423 \CustomizeMathJax{\newcommand{\nA}{\mathrm{nano\,ampere}}}
424 \CustomizeMathJax{\newcommand{\uA}{\mathrm{micro\,ampere}}}
425 \CustomizeMathJax{\newcommand{\mA}{\mathrm{milli\,ampere}}}
426 \CustomizeMathJax{\newcommand{\A}{\mathrm{ampere}}}
427 \CustomizeMathJax{\newcommand{\kA}{\mathrm{kilo\,ampere}}}
428 %
429 \CustomizeMathJax{\newcommand{\ul}{\mathrm{micro\,litre}}}
```

```
430 \CustomizeMathJax{\newcommand{\ml}{\milli\litre}}
431 \CustomizeMathJax{\newcommand{\l}{\litre}}
432 \CustomizeMathJax{\newcommand{\hl}{\hecto\litre}}
433 \CustomizeMathJax{\newcommand{\uL}{\micro\liter}}
434 \CustomizeMathJax{\newcommand{\mL}{\milli\liter}}
435 \CustomizeMathJax{\newcommand{\L}{\liter}}
436 \CustomizeMathJax{\newcommand{\hL}{\hecto\liter}}
437 %
438 \CustomizeMathJax{\newcommand{\mHz}{\milli\hertz}}
439 \CustomizeMathJax{\newcommand{\Hz}{\hertz}}
440 \CustomizeMathJax{\newcommand{\kHz}{\kilo\hertz}}
441 \CustomizeMathJax{\newcommand{\MHz}{\mega\hertz}}
442 \CustomizeMathJax{\newcommand{\GHz}{\giga\hertz}}
443 \CustomizeMathJax{\newcommand{\THz}{\tera\hertz}}
444 %
445 \CustomizeMathJax{\newcommand{\mN}{\milli\newton}}
446 \CustomizeMathJax{\newcommand{\N}{\newton}}
447 \CustomizeMathJax{\newcommand{\kN}{\kilo\newton}}
448 \CustomizeMathJax{\newcommand{\MN}{\mega\newton}}
449 %
450 \CustomizeMathJax{\newcommand{\Pa}{\pascal}}
451 \CustomizeMathJax{\newcommand{\kPa}{\kilo\pascal}}
452 \CustomizeMathJax{\newcommand{\MPa}{\mega\pascal}}
453 \CustomizeMathJax{\newcommand{\GPa}{\giga\pascal}}
454 %
455 \CustomizeMathJax{\newcommand{\mohm}{\milli\ohm}}
456 \CustomizeMathJax{\newcommand{\kohm}{\kilo\ohm}}
457 \CustomizeMathJax{\newcommand{\Mohm}{\mega\ohm}}
458 %
459 \CustomizeMathJax{\newcommand{\pV}{\pico\volt}}
460 \CustomizeMathJax{\newcommand{\nV}{\nano\volt}}
461 \CustomizeMathJax{\newcommand{\uV}{\micro\volt}}
462 \CustomizeMathJax{\newcommand{\mV}{\milli\volt}}
463 \CustomizeMathJax{\newcommand{\V}{\volt}}
464 \CustomizeMathJax{\newcommand{\kV}{\kilo\volt}}
465 %
466 \CustomizeMathJax{\newcommand{\W}{\watt}}
467 \CustomizeMathJax{\newcommand{\uW}{\micro\watt}}
468 \CustomizeMathJax{\newcommand{\mW}{\milli\watt}}
469 \CustomizeMathJax{\newcommand{\kW}{\kilo\watt}}
470 \CustomizeMathJax{\newcommand{\MW}{\mega\watt}}
471 \CustomizeMathJax{\newcommand{\GW}{\giga\watt}}
472 %
473 \CustomizeMathJax{\newcommand{\J}{\joule}}
474 \CustomizeMathJax{\newcommand{\uJ}{\micro\joule}}
475 \CustomizeMathJax{\newcommand{\mJ}{\milli\joule}}
476 \CustomizeMathJax{\newcommand{\kJ}{\kilo\joule}}
477 %
478 \CustomizeMathJax{\newcommand{\eV}{\electronvolt}}
479 \CustomizeMathJax{\newcommand{\meV}{\milli\electronvolt}}
480 \CustomizeMathJax{\newcommand{\keV}{\kilo\electronvolt}}
481 \CustomizeMathJax{\newcommand{\MeV}{\mega\electronvolt}}
482 \CustomizeMathJax{\newcommand{\GeV}{\giga\electronvolt}}
483 \CustomizeMathJax{\newcommand{\TeV}{\tera\electronvolt}}
484 %
```

---

```

485 \CustomizeMathJax{\newcommand{\kWh}{\kilo\watt\hour}}
486 %
487 \CustomizeMathJax{\newcommand{\F}{\farad}}
488 \CustomizeMathJax{\newcommand{\fF}{\femto\farad}}
489 \CustomizeMathJax{\newcommand{\pF}{\pico\farad}}
490 %
491 \CustomizeMathJax{\newcommand{\K}{\mathrm{K}}}
492 %
493 \CustomizeMathJax{\newcommand{\dB}{\mathrm{dB}}}
494 %
495 \CustomizeMathJax{\newcommand{\kibi}{\mathrm{Ki}}}
496 \CustomizeMathJax{\newcommand{\mebi}{\mathrm{Mi}}}
497 \CustomizeMathJax{\newcommand{\gibi}{\mathrm{Gi}}}
498 \CustomizeMathJax{\newcommand{\tebi}{\mathrm{Ti}}}
499 \CustomizeMathJax{\newcommand{\pebi}{\mathrm{Pi}}}
500 \CustomizeMathJax{\newcommand{\exbi}{\mathrm{Ei}}}
501 \CustomizeMathJax{\newcommand{\zebi}{\mathrm{Zi}}}
502 \CustomizeMathJax{\newcommand{\yobi}{\mathrm{Yi}}}
503 \end{warpMathJax}

```

---

File 368 **lwarf-slantsc.sty**

§ 468 Package **slantsc**

*(Emulates or patches code by HARALD HARDERS.)*

Pkg slantsc **slantsc** is emulated for HTML, and used as-is for print output.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{slantsc}[2012/01/01]

2 \newcommand*{\LWR@HTML@noscshape}{}%
3 \LWR@formatted{noscshape}%
4
5 \newcommand*{\LWR@null@noscshape}{}%
6
7 \appto{\LWR@nullfonts}{%
8 \LetLtxMacro\noscshape\LWR@null@noscshape%
9 }

```

---

File 369 **lwarf-slashed.sty**

§ 469 Package **slashed**

*(Emulates or patches code by DAVID CARLISLE.)*

Pkg slashed **slashed** works as-s for HTML SVG math. For MATHJAX, emulation is provided.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{slashed}[1997/01/16]

2 \begin{warpMathJax}

```

---

```

3 \CustomizeMathJax{\newcommand{\slashed}[1]{\cancel{#1}}}
4 \end{warpMathJax}
```

---

File 370 **lwarp-soul.sty**

§ 470 Package **soul**

*(Emulates or patches code by MELCHIOR FRANZ.)*

Pkg soul soul is emulated.

for HTML output 1 \LWR@ProvidesPackageDrop{soul}[2003/11/17]
2 \RequirePackage{xcolor}%
3 \convertcolorspec

Storage for the colors to use:

```

3 \newcommand*\LWR@soululcolor(){}
4
5 \newcommand*\LWR@soulstcolor(){}
6
7 % \definecolor{\LWR@soulhlcolordefault}{HTML}{F8E800}
8 % \newcommand*\LWR@soulhlcolor{\LWR@soulhlcolordefault}
9 \newcommand*\LWR@soulhlcolor{}
```

\so {\text{}}

Basic markup with css:

```

10 \newcommand{\so}[1]{%
11 \InlineClass(letter-spacing:.2ex){letterspacing}{#1}%
12 }
```

\caps {\text{}}

```

13 \newcommand{\caps}[1]{%
14 \InlineClass%
15 (font-variant:small-caps;letter-spacing:.1ex)%
16 {capspacing}{#1}%
17 }
```

\LWR@soulcolor {\text{}} {\color{color}} {\class{class}} {\colorstyle{colorstyle}} {\FormatWPstyle{}}

Add colors if not empty:

```

18 \newcommand{\LWR@soulcolor}[5]{%
19 \ifcsempty{#2}%
20 {%
21 \InlineClass(#5){#3}{#1}%
22 }%
23 {%
24 \convertcolorspec[named]{\nameuse{#2}}{HTML}\LWR@tempcolor%
25 \LWR@htmlspanclass[#5:#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}%
}
```

```

26 }%
27 }

28 \newcommand{\ul}[1]{%
29 \LWR@soulcolor{#1}{\LWR@soululcolor}{\uline}{text-decoration-color}%
30     {text-decoration:underline; text-decoration-skip: auto;}%
31 }
32
33 \newcommand{\st}[1]{%
34 \LWR@soulcolor{#1}{\LWR@soulstcolor}{\sout}{text-decoration-color}%
35     {text-decoration:line-through;}%
36 }
37
38 \newcommand{\hl}[1]{%
39 \LWR@soulcolor{#1}{\LWR@soulhlcolor}{\highlight}{background-color}%
40     {background:\LWR@origpound{}F8E800}%
41 }

```

Nullified:

```

42 \newcommand*\soulaccent}[1]{}%
43 \newcommand*\soulregister}[2]{}%
44 \newcommand\sloppyword}[1]{#1}%
45 \newcommand*\sodef}[5]{\DeclareRobustCommand#1[1]{\so{##1}}}%
46 \newcommand*\resetso}{}%
47 \newcommand*\capsdef}[5]{}%
48 \newcommand*\capsreset}{}%
49 \newcommand*\capssave}[1]{}%
50 \newcommand*\capsselect}[1]{}%
51 \newcommand*\setul}[2]{}%
52 \newcommand*\resetul}{}%
53 \newcommand*\setuldepth}[1]{}%
54 \newcommand*\setuloverlap}[1]{}%

```

Set colors:

```

55 \newcommand*\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}%
56 \newcommand*\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}%
57 \newcommand*\sethlcolor}[1]{\renewcommand{\LWR@soulhlcolor}{#1}}%

```

Long versions of the user-level macros:

```

58 \let\textso\so
59 \let\textul\ul
60 \let\texthl\hl
61 \let\textcaps\caps

```

File 371 **lwarp-soulpos.sty**

§ 471 Package **soulpos**

(Emulates or patches code by JAVIER BEZOS.)

Pkg soulpos soulpos is emulated.

**for HTML output:**

```

1 \RequirePackage{soul}
2 \RequirePackage{soulutf8}
3 \LWR@ProvidesPackageDrop{soulpos}[2012/02/25]

4 \NewDocumentCommand{\ulposdef}{m o m}(){}
5
6 \newdimen\ulwidth
7
8 \newcommand\ifulstarttype[1]{%
9 \expandafter\@secondoftwo%
10 }
11
12 \newcommand\ifulenctype[1]{%
13 \expandafter\@secondoftwo%
14 }
15
16 \newcommand{\ulstarttype}{0}
17 \newcommand{\ulenctype}{0}
18 \newcommand{\ulpostolerance}{0}%

```

#### File 372 **lwarf-soulutf8.sty**

### § 472 Package **soulutf8**

Pkg soulutf8 soulutf8 is emulated.

lwarf's HTML output naturally supports UTF-8 encoding.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{soulutf8}[2016/05/16]
2 \RequirePackage{soul}

```

#### File 373 **lwarf-splitidx.sty**

### § 473 Package **splitidx**

(Emulates or patches code by MARKUS KOHM.)

Pkg splitidx splitidx is patched for use by lwarf.

If the `latexmk` option is selected for lwarf, `latexmk` will compile the document but will not compile the indexes. `lwarpmk printindex` and `lwarpmk htmlindex` will still be required.

 `\thepage` When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to `\thepage` during HTML output, as the concept of a page number is meaningless. Instead, do

---

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{\LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 572.17 in the `lwarp-patch-memoir` package for the \@@wrsindexhyp macro as an example.

**for HTML output:** 1 \LWR@ProvidesPackagePass{splitidx}[2016/02/18]

```
2 \catcode`\_=12%
3 \xpatchcmd{\newindex}
4   {\jobname-#2.idx}
5   {\jobname-#2_html.idx}
6   {}
7   {\LWR@patcherror{splitidx}{@newindex}}
8 \catcode`\_=8%
```

Patched to use `lwarp`'s automatic indexing counter instead of \thepage:

```
9 \renewcommand*{\wrsindex}[2][]{%
10   \ifx\relax#1\relax
11   \if@splitidx
12     \wrsindex[\idx]{#2}%
13   \else
14     \def\@tempa{#2}%
15     \if@verbindex\onelevel@sanitize\@tempa\fi
16     \wrindex{\@tempa}%
17   \fi
18 \else
19   \def\@tempa{#2}%
20   \csname index@\#1@hook\endcsname
21 %   \expandafter\ifx\csname @wrsindex\endcsname\relax
22   \addtocounter{LWR@autoindex}{1}%           lwarp
23   \LWR@new@label{\LWRindex-\arabic{LWR@autoindex}}%    lwarp
24 %   \@@@wrsindex[#1]{\@tempa}{\thepage}%
25 %   \@@@wrsindex[#1]{\@tempa}{\arabic{LWR@autoindex}}%
26 %   \else
27 %     \def\@tempb{\wrsindex[#1]}%
28 %     \expandafter\@tempb\@tempa||\\%
29 %   \fi
30   \endgroup
31   \esphack
32 \fi
33 }
```

`lwarp` defines sectioning commands with `xparse`, so the below patches are done as temporary redefinitions instead of being `\let`.

```
34 \xpatchcmd{\printsubindex}
35   {\let\section\subsection}
36   {\renewcommand*{\section}{\subsection}}
37   {}
```

```
38      {\LWR@patcherror{splitidx}{printsubindex-section}}
39
40 \xpatchcmd{\printsubindex}
41   {\let\chapter\section}
42   {\renewcommand*{\chapter}{\section}}
43   {}
44   {\LWR@patcherror{splitidx}{printsubindex-chapter}}
45
46 \xpatchcmd{\printsubindex}
47   {\let\@makechapterhead\section}
48   {\def\@makechapterhead{\section}}
49   {}
50   {\LWR@patcherror{splitidx}{printsubindex-chapter}}
```

---

**File 374 l warp-srcltx.sty**

§ 474      Package **srcltx**

Pkg    srcltx    srcltx is ignored.

**for HTML output:**    1 \LWR@ProvidesPackageDrop{srcltx}[2006/11/12]

```
2 \newif\ifSRCOK \SRCOKfalse
3 \newcommand*\srcIncludeHook[1]{}
4 \newcommand*\srcInputHook[1]{}
5 \newcommand*\MainFile{}
6 \def\MainFile{\jobname.tex}
7 \newcommand*\CurrentInput{}
8 \gdef\CurrentInput{\MainFile}
9 \newcommand\Input{}
10 \let\Input\input
```

---

**File 375 l warp-srctex.sty**

§ 475      Package **srctex**

Pkg    srctex    srctex is ignored.

**for HTML output:**    1 \LWR@ProvidesPackageDrop{srctex}[2006/11/12]
2 \LWR@origRequirePackage{l warp-srcltx}

---

**File 376 l warp-stabular.sty**

§ 476      Package **stabular**

(Emulates or patches code by SIGITAS TOLUŠIS.)

```
Pkg  stabular  stabular is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{stabular}[2014/03/20]

Env stabular  [<vpos>] {<colspec>}

  2 \newenvironment{stabular}[2][c]
  3 {
  4 \begin{tabular}[#1]{#2}
  5 \renewcommand{\noalign}{\vphantom{#1}}
  6 }
  7 {\end{tabular}}
```

```
Env stabular  {<width>} [<vpos>] {<colspec>}

  8 \NewDocumentEnvironment{stabular*}{m o m}
  9 {
 10 \begin{tabular}[#2]{#3}
 11 \renewcommand{\noalign}{\vphantom{#1}}
 12 }
 13 {\end{tabular}}
```

---

### File 377 **l warp-stackengine.sty**

## § 477 Package **stackengine**

*(Emulates or patches code by STEVEN B. SEGETES.)*

Pkg stackengine stackengine is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{stackengine}[2017/02/13]

The original version is necessary for the patched \@stack and \stackanchor, where nesting lateximage does not work:

```
2 \LetLtxMacro{\LWR@orig@stackengine}{\stackengine}
3 \renewcommand*{\stackengine}[8]{%
4   \ifstreq{\#4}{0}{%
5     {\begin{ lateximage }[\ImageAltText] }%
6     {\begin{ lateximage }[\ImageAltText][]{vertical-align:top} }%
7     \LWR@orig@stackengine{#1}{#2}{#3}{#4}{#5}{#6}{#7}{#8}%
8     {\end{ lateximage }}%
9 }}
```

\@stack uses a lateximage with a vertical alignment:

```
10 \LetLtxMacro{\LWR@orig@stack}{\@stack}
11
12 \xpatchcmd{\LWR@orig@stack}{\stackengine}{\LWR@orig@stackengine}
13   {}
```

```

14      {\LWR@patcherror{stackengine}{\LWR@orig@@stack}}
15
16 \renewcommand*{\@stack}[4]{%
17     \ifstreq{\#3}{0}{%
18         {\begin{ lateximage }[\ImageAltText] }%
19         {\begin{ lateximage }[\ImageAltText][][vertical-align:top]}%
20     \LWR@orig@@stack{\#1}{\#2}{\#3}{\#4}%
21     \end{ lateximage }%
22 }

```

The lapping macros are disabled for HTML:

```

23 \newcommand*\LWR@HTML@@stacklap[4]{\#3}
24 \LWR@formatted{@stacklap}

```

\stackanchor is patched for two instances of \stackengine. A *lateximage* with vertical alignment is used.

```

25 \xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
26     {}
27     {\LWR@patcherror{stackengine}{stackanchor patch 1}}
28
29 \xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
30     {}
31     {\LWR@patcherror{stackengine}{stackanchor patch 2}}
32
33 \xpretocmd{\stackanchor}
34     {\begin{ lateximage }[\ImageAltText][][vertical-align:middle]}%
35     {}
36     {\LWR@patcherror{stackengine}{stackanchor pre}}%
37
38 \xapptocmd{\stackanchor}{\end{ lateximage }}%
39     {}
40     {\LWR@patcherror{stackengine}{stackanchor app}}

```

\Centerstack is simply placed inside a *lateximage* with a vertical alignment:

```

41 \xpretocmd{\Centerstack}
42     {\begin{ lateximage }[\ImageAltText][][vertical-align:middle]}%
43     {}
44     {\LWR@patcherror{stackengine}{Centerstack pre}}%
45
46 \xapptocmd{\Centerstack}{\end{ lateximage }}%
47     {}
48     {\LWR@patcherror{stackengine}{Centerstack app}}

```

\savestack reverts to print mode while saving the box, then places it inside a *lateximage* when used:

```

49 \renewcommand*\savestack[2]{%
50     \xdef\sv@name{\stack@macro@name{\#1}}%
51     \@ifundefined{\sv@name content}{%
52         \expandafter\newsavebox\expandafter{\csname\sv@name content\endcsname}%
53     }{}%

```

---

```

54 \begingroup%    l warp
55 \LWR@restoreorigformatting%    l warp
56 \RenewDocumentEnvironment{ lateximage }{ s o s o }{}{}% l warp: inside group
57 \expandafter\LWR@gsavebox\csname\sv@name content\endcsname{\#2}%
58 \expandafter\gdef\expandafter#1\expandafter{%
59     \expandafter\begin\expandafter{ lateximage \expandafter}%
60     \expandafter\usebox\expandafter{%
61         \csname\sv@name content\endcsname}%
62     \expandafter\end\expandafter{ lateximage \expandafter}%
63 }%
64 \endgroup%    l warp
65 }

```

---

File 378 **l warp-steinmetz.sty**

§ 478 Package **steinmetz**

*(Emulates or patches code by ENRICO GREGORIO.)*

Pkg **steinmetz** **steinmetz** is patched for use by **l warp**. Emulation is provided for MATHJAX

**for HTML output:** 1 \LWR@ProvidesPackagePass{steinmetz}[2009/06/14]

```

2 \begin{warpHTML}
3 \renewcommand{\phase}[2][]{%
4     \begin{lateximage}*[\steinmetz{\detokenize{\#2}}]
5     \ensuremath{\underline{/ \#2}}
6     \end{lateximage}
7 }
8 \end{warpHTML}
9
10 \begin{warpMathJax}
11 \CustomizeMathJax{\newcommand{\phase}[2][]{\underline{/ \#2}}}
12 \end{warpMathJax}

```

---

File 379 **l warp-stfloats.sty**

§ 479 Package **stfloats**

Pkg **stfloats** **stfloats** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{stfloats}[2017/03/27]

**stfloats** may have been preloaded by a **ltj\*** class.

The following are provided in case they have not yet been defined:

```

2 \providecommand*{\fnbelowfloat}{}
3 \providecommand*{\fnunderfloat}{}

```

```
4 \providecommand*\setbaselinefloat{}  
5 \providecommand*\setbaselinefixed{}
```

Nullified for HTML:

```
6 \renewcommand*\fnbelowfloat{}  
7 \renewcommand*\fnunderfloat{}  
8 \renewcommand*\setbaselinefloat{}  
9 \renewcommand*\setbaselinefixed{}
```

---

### File 380 **l warp-struktex.sty**

§ 480 Package **struktex**

(Emulates or patches code by JOBST HOFFMANN.)

Pkg struktex struktex is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{struktex}[2018/06/04]

```
2 \BeforeBeginEnvironment{struktogramm}{%  
3   \begin{lateximage}[-struktex-\PackageDiagramAltText]{%  
4 }  
5 \AfterEndEnvironment{struktogramm}{\end{lateximage}}  
6  
7 \newenvironment{\LWR@HTML@centerNss}{\begin{center}}{\end{center}}  
8 \LWR@formattedenv{centerNss}  
9  
10 \newcommand{\LWR@HTML@CenterNssFile}[1]{%  
11   \begin{center}  
12   \input{#1.nss}  
13   \end{center}  
14 }  
15 \LWR@formatted{CenterNssFile}  
16  
17 \newcommand{\LWR@HTML@centerNssfile}{\LWR@HTML@CenterNssFile}  
18 \LWR@formatted{centerNssfile}
```

---

### File 381 **l warp-subcaption.sty**

§ 481 Package **subcaption**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg subcaption subcaption is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{subcaption}[2018/05/01]

Tells `l warp` to ignore minipage widths inside a subfigure or subtable. In print mode the minipages are used to place the items next to each other. In HTML they are placed side-by-side automatically.

```

2 \ifdef{\subcaption@minipage}{
3     \xpatchcmd{\subcaption@minipage}
4         {\minipage}
5         {\minipagewidth\minipage}
6         {}
7     {\LWR@patcherror{subcaption}{subcaption@minipage}}
8 }{}
```

Likewise for a `\subcaptionbox`:

```

9 \ifdef{\subcaptionbox} {
10    \xpretocmd{\subcaptionbox}
11        {\minipagewidth}
12        {}
13    {\LWR@patcherror{subcaption}{subcaptionbox}}
14 }{}
```

### File 382 **l warp-subfig.sty**

## § 482 Package **subfig**

(Emulates or patches code by STEVEN DOUGLAS COCHRAN.)

Pkg `subfig` `subfig` is supported and patched by `l warp`.

⚠ `lof/lotdepth` At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

In the document source, use `\hfill` and `\hspace*` `subfig>inline` between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

**for HTML output:** Accept all options for `l warp-subfig`:

```
1 \LWR@ProvidesPackagePass{subfig}[2005/06/28]
```

`\sf@@@subfloat` `{<1 type>} [<2 LOF entry>] [<3 caption>] {<4 contents>}`

The outer minipage allows side-by-side subfloats with `\hfill` between.

```

2 \long\def\sf@@@subfloat#1[#2][#3]{%
3 \begin{minipage}{\linewidth}\l warp
4 \IfValueTF{#2}{%
5     \LWR@setlatestname{#2}%
6 }{%
7     \IfValueTF{#3}{%
8         \LWR@setlatestname{#3}%
}}}
```

```

9      }{)%
10 }%
11 \LWR@stoppars% lwarp
12   \@ifundefined{FBsc@max}{ }%
13     {\FB@readaux{\let\FBsuboheight\relax}}%
14   \atempccta=\@ne
15   \if@minipage
16     \atempccta=\z@
17   \else\ifdim \lastskip=\z@ \else
18     \atempccta=\tw@
19   \fi\fi
20   \ifmaincaptiontop
21     \sf@top=\sf@nearskip
22     \sf@bottom=\sf@farskip
23   \else
24     \sf@top=\sf@farskip
25     \sf@bottom=\sf@nearskip
26   \fi
27   \leavevmode

28 %   \setbox\atempboxa \hbox{#4}%
29 %   \atempdima=\wd\atempboxa
30 %   \@ifundefined{FBsc@max}{ }%
31 %     {\global\advance\Xhsizeneg\wd\atempboxa
32 %      \dimen@\ht\atempboxa
33 %      \advance\dimen@\dp\atempboxa
34 %      \ifdim\dimen@>\FBso@max
35 %        \global\FBso@max\dimen@
36 %      \fi}%

```

Do not use boxes, which interfere with `\textrimage`:

```

37 %   \vtop%
38   \bgroup
39 %   \vbox%
40   \bgroup
41   \ifcase\atempccta
42     \orminipagefalse
43   \or
44     \vskip\sf@top
45   \or
46     \ifdim \lastskip=\z@ \else
47       \atempskipb\sf@top\relax\xaddvskip
48     \fi
49   \fi
50   \sf@ifpositiontop{%
51     \ifx \empty\@empty\relax \else
52       \sf@subcaption{#1}{#2}{#3}%
53       \vskip\sf@capskip
54       \vskip\sf@captionadj
55     \fi\egroup
56   \hrule width0pt height0pt depth0pt
57   \LWR@startpars% lwarp
58 % \box\atempboxa
59   #4
60   \LWR@stoppars% lwarp

```

```
61      }{%
62      \LWR@startpars% lwarp
63      \@ifundefined{FBsc@max}%
64      {
65 % \box@\tempboxa
66          #4
67      }%
68      {\ifx\FBsuboheight\relax
69 %         \box@\tempboxa
70          #4
71      \else
72 %         \vbox to \FBsuboheight{\FBafil\box@\tempboxa\FBbfil}%
73          #4
74      \fi}%
75      \LWR@stoppars% lwarp
76      \egroup
77      \ifx \empty\relax \else
78 %         \vskip\sff@capskip
79 %         \hrule width0pt height0pt depth0pt
80         \sff@subcaption{#1}{#2}{#3}%
81     \fi
82 }%
83 %     \vskip\sff@bottom
84 \egroup
85 \@ifundefined{FBsc@max}{}%
86     {\addtocounter{FRobj}{-1}%
87     \ifnum\c@FRobj=0\else
88         \subfloatrowsep
89     \fi}%
90     \ifmaincaptiontop\else
91         \global\advance\nameuse{c}@capttype}\m@ne
92     \fi
93 \end{minipage}% lwarp
94 \LWR@startpars% lwarp
95 \endgroup\ignorespaces%
96 }%  
  
\sff@subcaption {<1 type>} {<2 LOF entry>} {<3 caption>}
97 \long\def\sff@subcaption#1#2#3{%
98 \LWR@stoppars% lwarp
99 \ifx\relax#2\relax \else
100 \bgroup
101     \let\label=\gobble
102     \let\protect=\string
103     \def\@subcaplabel{%
104         \caption@lstfmt{\nameuse{p#1}}{\nameuse{the#1}}%
105         \sff@updatecaptionlist{#1}{#2}{\the\value{\capttype}}{\the\value{#1}}%
106     }%
107 \egroup
108 \bgroup
109     \ifx\relax#3\relax
110         \let\captionlabelsep=\relax
111     \fi
112 %     \setbox0\vbox{%
```

```
113 %          \hb@xt@{\the\@tempdima}{%
114 %
115 %          \hss
116 %          \parbox[t]{\the\@tempdima}{%
117 %              \caption@make
118 %                  {\@nameuse{sub\@capttype name}}%
119 %                  {\@nameuse{thesub\@capttype}}%
120 %                  {#3}
121 %          }%
122 %          \hss
123 %      }
124 %  }%
125  \@ifundefined{FBsc@max}%
126  { \box0 }%
127  {
128 %  \parbox[t]{\the\@tempdima}{%
129 \LWR@traceinfo{sfsupcap B1}% lwarf
130          \LWR@figcaption% lwarf
131          \caption@make
132          {\@nameuse{sub\@capttype name}}%
133          {\@nameuse{thesub\@capttype}}%
134          {\LWR@isolate{#3}}%
135
136 \endLWR@figcaption% lwarf
137 \LWR@traceinfo{sfsupcap B2}% lwarf
138 }%
139 { \dimen@\ht0%
140   \advance\dimen@\dp0%
141   \ifdim\dimen@>\FBsc@max
142     \global\FBsc@max\dimen@
143   \fi
144   \FB@readaux{\let\FBsubcheight\relax}%
145   \ifx\FBsubcheight\relax
146     \def\next{
147 %  \parbox[t]{\the\@tempdima}
148     }%
149   \else
150     \def\next{
151 %  \parbox[t][\FBsubcheight][t]{\the\@tempdima}
152     }%
153   \fi
154   \vbox{%
155     \hb@xt@{\the\@tempdima}{%
156
157 %         \hss
158 %         \next{%
159 \LWR@traceinfo{sfsupcap C1}% lwarf
160         \caption@make
161         {\@nameuse{sub\@capttype name}}%
162         {\@nameuse{thesub\@capttype}}%
163         {#3}
164 \LWR@traceinfo{sfsupcap C1}% lwarf
165 }%
166 %         \hss
167
```

```

168 %   }
169 %           }
170         }%
171     \egroup
172 \LWR@startpars% lwarp
173 }

```

\subfloat@label Patches for \sf@sub@label:

```

174 \def\subfloat@label{%
175 \LWR@ensuredoingapar% lwarp
176 \@ifnextchar(% %) match left parenthesis
177 {\sf@sub@label}
178 {\sf@sub@label(Sub@\capttype\space
179 \ifundefined{thechapter}{}{\nameuse{thechapter}\space}%
180 \nameuse{p@sub@\capttype}%
181 \nameuse{thesub@\capttype}.)}}

```

Patches for \subref.

\sf@subref {*label*}

The unstarred version uses a \ref link whose printed text comes from the sub@<label>:

```

182 \renewcommand{\sf@subref}[1]{%
183 \LWR@subnewref{\#1}{sub@#1}%
184 }

```

\sf@@subref {*label*}

The starred version uses the printed sub@<label> which is stored as if it were a page number:

```
185 \renewcommand{\sf@@subref}[1]{\LWR@orig@pageref{sub@#1}}
```

Defining new subfloats. The l@sub<type> for each is redefined.

\@newsubfloat [*keys/values*] {*float name*}

```

186 \LetLtxMacro{\LWR@orig@newsubfloat}{\@newsubfloat}
187
188 \def\@newsubfloat[#1]#2{%
189 \LWR@orig@newsubfloat[#1]{#2}%
190 \renewcommand{\l@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
191 }

```

Pre-defined for figures and tables:

\l@subfigure {*text*} {*pagenum*}

```
192 \renewcommand{\l@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}
```

\l@subtable {*text*} {*pagenum*}

```
193 \renewcommand{\l@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
```

---

File 383 **l warp-subfigure.sty**

§ 483 Package **subfigure**

Pkg subfigure subfigure is emulated by subfig.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{subfigure}[2002/03/15]
2 \RequirePackage{subfig}

3 \LetLtxMacro{\subfigure}{\subfloat}
4 \LetLtxMacro{\subtable}{\subfloat}
5 \LetLtxMacro{\Subref}{\subref}
6 \@ifundefined{figuretopcaptrue}{\newif\iffiguretopcap{}}
7 \newif\ifsubfiguretopcap
8 \newif\ifsubcaphang
9 \newif\ifsubcapcenter
10 \newif\ifsubcapcenterlast
11 \newif\ifsubcapnooneline
12 \newif\ifsubcapraggedright
13 \newskip\subfigtopskip
14 \newskip\subfigcapskip
15 \newdimen\subfigcapadj
16 \newskip\subfigbottomskip
17 \newdimen\subfigcaptopmargin
18 \newskip\subfiglabelskip
19 \newcommand*\subcapsize{}
20 \newcommand*\subcaplabelfont{}
21 \newcommand*\subcapfont{}

```

---

File 384 **l warp-subsupscripts.sty**

§ 484 Package **subsupscripts**

(Emulates or patches code by RICCARDO BRESCIANI.)

Pkg subsupscripts subsupscripts is used as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{subsupscripts}[2009/10/27]

```

The larger skips are used here.

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{%
4   \newcommand{\fourscriptsC}[7]{%
5     {}^{\#2}{}_3\hspace{\#6}\#1\hspace{\#7}{}^{\#4}{}_5%
6   }%
7 }%
8 \CustomizeMathJax{%

```

```

9      \newcommand{\lrsubscriptsC}[5]{%
10         \fourscriptsC{#1}{ }{#2}{ }{#3}{#4}{#5}%
11     }
12 }
13 \CustomizeMathJax{%
14     \newcommand{\lsuperscriptsC}[5]{%
15         \fourscriptsC{#1}{#2}{ }{#3}{ }{#4}{#5}%
16     }
17 }
18 \CustomizeMathJax{%
19     \newcommand{\fourscripts}[5]{%
20         \fourscriptsC{#1}{#2}{#3}{#4}{#5}{0ex}{0ex}%
21     }
22 }
23 \CustomizeMathJax{%
24     \newcommand{\lrsubscripts}[3]{\fourscripts{#1}{ }{#2}{ }{#3}{}}
25 }
26 \CustomizeMathJax{%
27     \newcommand{\lsuperscripts}[3]{\fourscripts{#1}{#2}{ }{#3}{}}
28 }
29 \CustomizeMathJax{%
30     \newcommand{\twolscripts}[4][-.16ex]{\{}{\}^{#3}_{#4}\hspace{#1}#2\}
31 }
32 \CustomizeMathJax{%
33     \newcommand{\tworscripts}[4][-.07ex]{\#2\hspace{#1}{}^{#3}_{#4}\}}
34 }
35 \CustomizeMathJax{%
36     \newcommand{\lsubscript}[3][-.16ex]{\twolscripts{#1}{#2}{ }{#3}{}}
37 }
38 \CustomizeMathJax{%
39     \newcommand{\lsuperscript}[3][-.16ex]{\twolscripts{#1}{#2}{#3}{\}}
40 }
41 \CustomizeMathJax{%
42     \newcommand{\rsubscript}[3][-.07ex]{\tworscripts{#1}{#2}{ }{#3}{}}
43 }
44 \CustomizeMathJax{%
45     \newcommand{\rsuperscript}[3][-.07ex]{\tworscripts{#1}{#2}{#3}{\}}
46 }
47 \end{warpMathJax}

```

---

File 385 **lwarf-supertabular.sty**

§ 485 Package **supertabular**

(Emulates or patches code by JOHANNES BRAAMS, THEO JURRIENS.)

Pkg supertabular supertabular is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{supertabular}[2004/02/20]

⚠ Misplaced alignment tab character & For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars
```

See section 8.10.1.

 **lateximage** `supertabular` and `xtab` are not supported inside a `lateximage`.

```
2 \newcommand{\LWRST@firsthead}{}%
3
4 \newcommand{\tablefirsthead}[1]{%
5     \long\gdef\LWRST@firsthead{\#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}%
9 \newcommand{\tabletail}[1]{}%
10
11 \newcommand{\LWRST@lasttail}{}%
12
13 \newcommand{\tablelasttail}[1]{%
14     \long\gdef\LWRST@lasttail{\#1}%
15 }

16 \newcommand{\tablecaption}[2][]{%
17     \long\gdef\LWRST@caption{%
18         \ifblank{\#1}{%
19             {\caption{\#2}}%
20             {\caption[\#1]{\#2}}%
21         }%
22     }%
23
24 \let\topcaption\tablecaption
25 \let\bottomcaption\tablecaption

26 \newcommand*\LWRST@caption{}%
27
28 \newcommand*\shrinkheight[1]{}%
29
30 \NewDocumentEnvironment{supertabular}{s o m}%
31 {%
32 \LWR@traceinfo{supertabular}%
33 \begin{table}%
34 \LWRST@caption%
35 \begin{tabular}{#3}%
36 \TabularMacro\ifdefvoid{\LWRST@firsthead}%
37 {\LWR@getmynexttoken}%
38 {\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
39 }%
40 {%
41 \ifdefvoid{\LWRST@lasttail}%
42 {}%
43 {%
44 \TabularMacro\ResumeTabular%
45 \LWRST@lasttail%
```

```
46 }%
47 \end{tabular}%
48 \end{table}%

49 \gdef\LWRST@caption{}%

50 \LWR@traceinfo{supertabular done}%
51 }
52
53 \NewDocumentEnvironment{mpsupertabular}{s o m}
54 {\minipage{\linewidth}\supertabular{#3}}
55 {\endsupertabular\endminipage}
```

---

**File 386 l warp-svg.sty**

§ 486 Package **SVG**

(Emulates or patches code by PHILIP ILTEN, FALK HANISCH.)

Pkg svg **svg** is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{svg}[2019/10/22]

```
2 \xpretocmd{\includesvg}%
3   {\begin{lateximage}}%
4   {}%
5   {\LWR@patcherror{svg}{includesvg}}%
6
7 \xapptocmd{\includesvg}%
8   {\end{lateximage}}%
9   {}%
10  {\LWR@patcherror{svg}{includesvg}}%
11
12 \xpretocmd{\includeinkscape}%
13   {\begin{lateximage}}%
14   {}%
15   {\LWR@patcherror{svg}{includeinkscape}}%
16
17 \xapptocmd{\includeinkscape}%
18   {\end{lateximage}}%
19   {}%
20   {\LWR@patcherror{svg}{includeinkscape}}
```

---

**File 387 l warp-syntonly.sty**

§ 487 Package **syntonly**

(Emulates or patches code by FRANK MITTELBACH, RAINER SCHÖPF.)

Pkg syntonly syntonly is ignored.

for HTML output: Discard all options for l warp-syntonly:

```
1 \LWR@ProvidesPackageDrop{syntonly}[2017/06/30]
```

```
2 \newif\ifsyntax@
3 \syntax@false
4
5 \newcommand*\syntonly{}{}
6
7 \@onlypreamble\syntonly
```

---

### File 388 **l warp-tabfigures.sty**

#### § 488 Package **tabfigures**

Pkg tabfigures tabfigures is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{tabfigures}[2012/01/24]

---

### File 389 **l warp-tablefootnote.sty**

#### § 489 Package **tablefootnote**

Pkg tablefootnote tablefootnote is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{tablefootnote}[2014/01/26]

This works because in HTML tables are no longer floats.

```
2 \LetLtxMacro\tablefootnote\footnote
```

---

### File 390 **l warp-tables.sty**

#### § 490 Package **tables**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg tables tables is emulated. \LWR@hline is used to handle the optional argument when tables is loaded.

for HTML output: 1 \LWR@ProvidesPackageDrop{tables}

```
2 \newdimen\tablinesep  
3 \newdimen\arraylinesep  
4 \newdimen\extrarulesep
```

---

**File 391 l warp-tabularx.sty****§ 491 Package tabularx**

(Emulates or patches code by DAVID CARLISLE.)

Pkg tabularx tabularx is emulated by l warp.

for HTML output: Discard all options for l warp-tabularx:

```
1 \LWR@ProvidesPackageDrop{tabularx}[2016/02/03]  
2 \RequirePackage{array}  
  
3 \DeclareDocumentEnvironment{tabularx}{m o m}  
4 {\tabular{#3}}  
5 {\endtabular}  
6  
7 \DeclareDocumentEnvironment{tabularx*}{m o m}  
8 {\tabular{#3}}  
9 {\endtabular}
```

---

**File 392 l warp-tabulary.sty****§ 492 Package tabulary**

(Emulates or patches code by DAVID CARLISLE.)

Pkg tabulary tabulary is emulated by l warp.

for HTML output: Discard all options for l warp-tabulary.

Column types L, C, R, and J are emulated by l warp core code.

```
1 \LWR@ProvidesPackageDrop{tabulary}[2014/06/11]  
2 \RequirePackage{array}  
  
3 \NewDocumentEnvironment{tabulary}{m o m}  
4 {\tabular{#3}}  
5 {\endtabular}  
6  
7 \NewDocumentEnvironment{tabulary*}{m o m}  
8 {\tabular{#3}}  
9 {\endtabular}  
10  
11 \newdimen\tymin  
12 \newdimen\tymax  
13 \def\tyformat{}
```

---

File 393 **l warp-tascmac.sty**

§ 493 Package **tascmac**

Pkg tascmac tascmac is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{tascmac}[2018/03/09]

```
2 \newenvironment*{boxnote}
3   {
4     \BlockClass[
5       padding: .5ex ;
6       border: 1px solid black ;
7       border-top: 1px dashed black ;
8     ]{boxnote}
9   }
10  {\endBlockClass}
11
12 \newenvironment*{screen}[1][]
13  {
14    \BlockClass[
15      padding: .5ex ;
16      border: 1px solid gray ;
17      border-radius: 8pt
18    ]{boxnote}
19  }
20  {\endBlockClass}
21
22 \newenvironment*{itembox}[2][]
23  {
24    \BlockClass[
25      padding: .5ex ;
26      border: 1px solid gray ;
27      border-radius: 8pt
28    ]{boxnote}
29    \InlineClass{itemboxtitle}{#2}\par
30  }
31  {\endBlockClass}
32
33 \newenvironment*{shadebox}
34  {
35    \BlockClass[
36      padding: .5ex ;
37      border: 1px solid black ;
38      box-shadow: 3px 3px 3px \#808080 ;
39    ]{boxnote}
40  }
41  {\endBlockClass}
42
43 \newcommand*{\mask}[2]{%
44   \InlineClass[background: lightgray]{mask}{#1}%
```

```
45 }
46
47 \newcommand*{\maskbox}[5]{%
48     \InlineClass[background: lightgray]{mask}{#5}%
49 }
50
51 \newcommand*{\Maskbox}[6]{%
52     \InlineClass[%
53         background: lightgray ;
54         border: #5 solid black
55     ]{mask}{#6}%
56 }
57
58 \newcommand*{\keytop}[2][]{%
59     \InlineClass[% padding: .2ex ;
60         border: 1px solid black ;
61         border-radius: .7ex ;
62     ]{keytop}{#2}%
63 }
64 }
65
66 \def\yen{\HTMLUnicode{00A5}}
67
68 \def\return{\HTMLUnicode{23CE}}
69
70 \def\Return{\HTMLUnicode{23CE}}
71
72 \def\ascii{ASCII Corporation}
73
74 \def\Ascii{ASCII Corporation}
75
76 \def\ASCII{ASCII Corporation}
```

---

**File 394 lwarp-textarea.sty**

§ 494      Package **textarea**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg    textarea    **textarea** is ignored.

**for HTML output:**    1 \LWR@ProvidesPackageDrop{textarea}[2005/12/26]

```
2 \newcommand\StartFromTextArea{}
3 \newcommand\StartFromHeaderArea{}
4 \newcommand*\RestoreTextArea{}
5 \newcommand*\ExpandTextArea[1][*]{}
6 \let\NCC@restoretarea\empty
```

---

File 395 **l warp-textcomp.sty**

§ 495 Package **textcomp**

(Emulates or patches code by FRANK MITTELBACH, ROBIN FAIRBAIRNS, WERNER LEMBERG.)

Pkg **textcomp** **textcomp** is patched for use by **l warp**.

### § 495.1 Limitations

Some **textcomp** symbols do not have Unicode equivalents, and thus are not supported.

⚠ **missing symbols** Many **textcomp** symbols are not supported by many system/browser fonts. In the **css** try referencing fonts which are more complete, but expect to see gaps in coverage.

### § 495.2 Package loading

for **HTML output**: 1 \LWR@ProvidesPackagePass{textcomp}[2017/04/05]

### § 495.3 HTML symbols

For **HTML**, use **HTML** entities or direct **Unicode**, depending on the engine.

\AtBeginDocument improves support for **Lua<sup>A</sup>T<sub>E</sub>X** and **X<sub>E</sub><sup>A</sup>T<sub>E</sub>X**.

#### § 495.3.1 pdf<sup>A</sup>T<sub>E</sub>X symbols

```
2 \AtBeginDocument{  
3 \ifPDFTeX% pdfATEX or dvi latex  
4 \newcommand*{\LWR@HTML@textdegree}{\HTMLentity{deg}}  
5 \newcommand*{\LWR@HTML@textcelsius}{\HTMLunicode{2103}}  
6 \newcommand*{\LWR@HTML@textohm}{\HTMLunicode{2126}}  
7 \newcommand*{\LWR@HTML@textmu}{\HTMLunicode{00B5}}  
8 \newcommand*{\LWR@HTML@textlquill}{\HTMLunicode{2045}}  
9 \newcommand*{\LWR@HTML@textrquill}{\HTMLunicode{2046}}  
10 \newcommand*{\LWR@HTML@textcircledP}{\HTMLunicode{2117}}  
11 \newcommand*{\LWR@HTML@texttwelvedash}{\HTMLunicode{2014}}% emdash  
12 \newcommand*{\LWR@HTML@textthreequartersemdash}{\HTMLunicode{2014}}% emdash  
13 \newcommand*{\LWR@HTML@textmho}{\HTMLunicode{2127}}  
14 \newcommand*{\LWR@HTML@textnaira}{\HTMLunicode{20A6}}  
15 \newcommand*{\LWR@HTML@textpeso}{\HTMLunicode{20B1}}  
16 \newcommand*{\LWR@HTML@textrecipe}{\HTMLunicode{211E}}  
17 \newcommand*{\LWR@HTML@textinterrobang}{\HTMLunicode{203D}}  
18 \newcommand*{\LWR@HTML@textinterrobangdown}{\HTMLunicode{2E18}}  
19 \newcommand*{\LWR@HTML@textperthousand}{\HTMLunicode{2030}}  
20 \newcommand*{\LWR@HTML@textpertenthousand}{\HTMLunicode{2031}}  
21 \newcommand*{\LWR@HTML@textbaht}{\HTMLunicode{0E3F}}  
22 \newcommand*{\LWR@HTML@textdiscount}{\%}  
23 \newcommand*{\LWR@HTML@textservicemark}{\HTMLunicode{2120}}
```

24 \else

### § 495.3.2 X<sub>E</sub>La<sub>T</sub>E<sub>X</sub> and Lu<sub>A</sub>La<sub>T</sub>E<sub>X</sub> symbols

NOTE: Some of the following do not print well in the listing. Consult the .dtx or .sty file for the actual characters.

```
25 \newcommand*\{\LWR@HTML@textdegree}{°}
26 \newcommand*\{\LWR@HTML@textcelsius}{°C}
27 \newcommand*\{\LWR@HTML@textohm}{Ω}
28 \newcommand*\{\LWR@HTML@textmu}{μ}
29 \newcommand*\{\LWR@HTML@textlquill}{ℓ}
30 \newcommand*\{\LWR@HTML@textrquill}{ℓ}
31 \newcommand*\{\LWR@HTML@textcircledP}{©}
32 \newcommand*\{\LWR@HTML@texttwelveudash}{–}% emdash
33 \newcommand*\{\LWR@HTML@textthreequartersemdash}{–}% emdash
34 \newcommand*\{\LWR@HTML@textmho}{℧}
35 \newcommand*\{\LWR@HTML@textnaira}{₦}
36 \newcommand*\{\LWR@HTML@textpeso}{₱}
37 \newcommand*\{\LWR@HTML@textrecipe}{₹}
38 \newcommand*\{\LWR@HTML@textinterrobang}{⁇}
39 \newcommand*\{\LWR@HTML@textinterrobangdown}{⁇}
40 \newcommand*\{\LWR@HTML@textperthousand}{‰}
41 \newcommand*\{\LWR@HTML@textpertenthousand}{‰}
42 \newcommand*\{\LWR@HTML@textbaht}{฿}
43 \newcommand*\{\LWR@HTML@textdiscount}{٪}
44 \newcommand*\{\LWR@HTML@textservicemark}{℠}
45 \fi
46
47 \LWR@formatted{textdegree}
48 \LWR@formatted{textcelsius}
49 \LWR@formatted{textohm}
50 \LWR@formatted{textmu}
51 \LWR@formatted{textlquill}
52 \LWR@formatted{textrquill}
53 \LWR@formatted{textcircledP}
54 \LWR@formatted{texttwelveudash}
55 \LWR@formatted{textthreequartersemdash}
56 \LWR@formatted{textmho}
57 \LWR@formatted{textnaira}
58 \LWR@formatted{textpeso}
59 \LWR@formatted{textrecipe}
60 \LWR@formatted{textinterrobang}
61 \LWR@formatted{textinterrobangdown}
62 \LWR@formatted{textperthousand}
63 \LWR@formatted{textpertenthousand}
64 \LWR@formatted{textbaht}
65 \LWR@formatted{textdiscount}
66 \LWR@formatted{textservicemark}
```

## § 495.4 HTML diacritics

For HTML, Unicode diacritical marks are used:

```

67 \newcommand*{\LWR@HTML@capitalcedilla}[1]{\#1\HTMLunicode{0327}}
68 \newcommand*{\LWR@HTML@capitalogonek}[1]{\#1\HTMLunicode{0328}}
69 \newcommand*{\LWR@HTML@capitalgrave}[1]{\#1\HTMLunicode{0300}}
70 \newcommand*{\LWR@HTML@capitalacute}[1]{\#1\HTMLunicode{0301}}
71 \newcommand*{\LWR@HTML@capitalcircumflex}[1]{\#1\HTMLunicode{0302}}
72 \newcommand*{\LWR@HTML@capitaltilde}[1]{\#1\HTMLunicode{0303}}
73 \newcommand*{\LWR@HTML@capitaldieresis}[1]{\#1\HTMLunicode{0308}}
74 \newcommand*{\LWR@HTML@capitalhungarumlaut}[1]{\#1\HTMLunicode{30B}}
75 \newcommand*{\LWR@HTML@capitalring}[1]{\#1\HTMLunicode{30A}}
76 \newcommand*{\LWR@HTML@capitalcaron}[1]{\#1\HTMLunicode{30C}}
77 \newcommand*{\LWR@HTML@capitalbreve}[1]{\#1\HTMLunicode{306}}
78 \newcommand*{\LWR@HTML@capitalmacron}[1]{\#1\HTMLunicode{304}}
79 \newcommand*{\LWR@HTML@capitaldotaccent}[1]{\#1\HTMLunicode{307}}

```

\textcircled becomes a span with a rounded border. \providecommand is used to avoid conflict with xunicode.

```

80 \providecommand*{\LWR@HTML@textcircled}[1]{%
81 \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
82 }
83
84 \LWR@formatted{capitalcedilla}
85 \LWR@formatted{capitalogonek}
86 \LWR@formatted{capitalgrave}
87 \LWR@formatted{capitalacute}
88 \LWR@formatted{capitalcircumflex}
89 \LWR@formatted{capitaltilde}
90 \LWR@formatted{capitaldieresis}
91 \LWR@formatted{capitalhungarumlaut}
92 \LWR@formatted{capitalring}
93 \LWR@formatted{capitalcaron}
94 \LWR@formatted{capitalbreve}
95 \LWR@formatted{capitalmacron}
96 \LWR@formatted{capitaldotaccent}
97 \LWR@formatted{textcircled}

```

Nullify **textcomp** macros when generating filenames:

```

98 \FilenameNullify{%
99   \renewcommand*{\textdegree}{\textdegree}%
100  \renewcommand*{\textcelsius}{\textcelsius}%
101  \renewcommand*{\textohm}{\textohm}%
102  \renewcommand*{\textmu}{\textmu}%
103  \renewcommand*{\textlquill}{\textlquill}%
104  \renewcommand*{\textrquill}{\textrquill}%
105  \renewcommand*{\textcircledP}{\textcircledP}%
106  \renewcommand*{\texttwelvedash}{\texttwelvedash}%
107  \renewcommand*{\textthreequartersemdash}{\textthreequartersemdash}%
108  \renewcommand*{\textmho}{\textmho}%
109  \renewcommand*{\textnaira}{\textnaira}%
110  \renewcommand*{\textpeso}{\textpeso}%

```

---

```

111  \renewcommand*\{\textrecipie\}{}%
112  \renewcommand*\{\textinterrobang\}{}%
113  \renewcommand*\{\textinterrobangdown\}{}%
114  \renewcommand*\{\textperthousand\}{}%
115  \renewcommand*\{\textpertenthousand\}{}%
116  \renewcommand*\{\textbaht\}{}%
117  \renewcommand*\{\textdiscount\}{}%
118  \renewcommand*\{\textservicemark\}{}%
119  \renewcommand*\{\textcircled\}[1]{#1}%
120  \renewcommand*\{\capitalcedilla\}[1]{#1}%
121  \renewcommand*\{\capitalogonek\}[1]{#1}%
122  \renewcommand*\{\capitalgrave\}[1]{#1}%
123  \renewcommand*\{\capitalacute\}[1]{#1}%
124  \renewcommand*\{\capitalcircumflex\}[1]{#1}%
125  \renewcommand*\{\capitaltilde\}[1]{#1}%
126  \renewcommand*\{\capitaldieresis\}[1]{#1}%
127  \renewcommand*\{\capitalhungarumlaut\}[1]{#1}%
128  \renewcommand*\{\capitalring\}[1]{#1}%
129  \renewcommand*\{\capitalcaron\}[1]{#1}%
130  \renewcommand*\{\capitalbreve\}[1]{#1}%
131  \renewcommand*\{\capitalmacron\}[1]{#1}%
132  \renewcommand*\{\capitaldotaccent\}[1]{#1}%
133 }% FilenameNullify
134
135 }% AtBeginDocument

```

---

### File 396 **lwarf-textfit.sty**

§ 496 Package **textfit**

Pkg **textfit** **textfit** is emulated.

Text is placed into a <span> of class **textfit**. Sizes are approximated, and also limited by browser min/max font-size settings.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{textfit}[1994/04/15]

```

2 \newsavebox{\LWR@textfitbox}
3
4 \newcommand*\{\LWR@textfitscale\}[2]{%
5 \setlength{\LWR@templengthone}{#1}%
6 \setlength{\LWR@templengthone}{%
7   1em*\ratio{\LWR@templengthone}{\LWR@templengthtwo}%
8 }%
9 \InlineClass[font-size:\LWR@printlength{\LWR@templengthone}]{textfit}{#2}%
10 }
11
12 \newcommand*\{\scaletowidth\}[2]{%
13 \sbox{\LWR@textfitbox}{#2}%
14 \settowidth{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
15 \LWR@textfitscale{#1}{#2}%
16 }
17

```

```
18 \newcommand*{\scaletoheight}[2]{%
19 \sbox{\LWR@textfitbox}{#2}%
20 \settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
21 \LWR@textfitscale{#1}{#2}%
22 }
```

---

File 397 **l warp-textpos.sty**

§ 497 Package **textpos**

(Emulates or patches code by NORMAN GRAY.)

Pkg **textpos** **textpos** is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{textpos}[2019/04/15]

```
2 \NewDocumentEnvironment{textblock}{m o r(){}{}}
3 \NewDocumentEnvironment{textblock*}{m o r(){}{}}
4 \newcommand*{\TPGrid}[3][]{}
5 \NewDocumentCommand{\TPMargin}{s o}{}
6 \newcommand*{\textblockcolour}[1]({})
7 \newcommand*{\textblockrulecolour}[1]({})
8 \newcommand*{\textblockcolor}[1]({})
9 \newcommand*{\textblockrulecolor}[1]({})
10 \newcommand*{\tekstblockkulur}[1]({})
11 \newcommand*{\tekstblockrulekulur}[1]({})
12 \newlength{\TPHorizModule}
13 \newlength{\TPVertModule}
14 \newlength{\TPboxrulesize}
15 \newcommand{\textblocklabel}[1]({})
16 \newcommand*{\showtextsize}(){}
17 \newcommand*{\textblockorigin}[2]({})
18 \newcommand*{\TPoptions}[1]({})
19 \newcommand*{\TPreferencePosition}[1]({}
```

---

File 398 **l warp-theorem.sty**

§ 498 Package **theorem**

(Emulates or patches code by FRANK MITTELBACH.)

Pkg **theorem** **theorem** is patched for use by **l warp**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{theorem}[2014/10/28]

---

 Table 16: Theorem package—css styling of theorems and proofs

**Theorem:** <div> of class theorembody<theoremstyle>

**Theorem Header:** <span> of class theoremheader

where <theoremstyle> is plain, break, etc.

---

## § 498.1 Remembering the theorem style

Storage for the style being used for new theorems:

```
2 \newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
3 \gdef\theoremstyle#1{%
4   \@ifundefined{th@#1}{\@warning
5     {Unknown theoremstyle '#1'. Using 'plain'}%
6     \theorem@style{plain}%
7     \renewcommand{\LWR@newtheoremstyle}{plain}\% l warp
8   }%
9   {%
10     \theorem@style{#1}%
11     \renewcommand{\LWR@newtheoremstyle}{#1}\% l warp
12   }%
13   \begingroup
14     \csname th@\the\theorem@style \endcsname
15   \endgroup}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
16 \gdef\xntheorem#1#2[#3]{%
17   \expandafter\@if definable\csname #1\endcsname
18   {%
19     \csedef{\LWR@thmstyle#1}{\LWR@newtheoremstyle}\% l warp
20     \@definecounter{#1}\@newctr{#1}[#3]\%
21     \expandafter\xdef\csname the#1\endcsname
22       {\expandafter\noexpand\csname the#3\endcsname
23        \@thmcOUNTERsep\@thmcOUNTER{#1}}\%
24     \def\@tempa{\global\@namedef{#1}}\%
25     \expandafter\@tempa\expandafter{%
26       \csname th@\the\theorem@style
27         \expandafter\endcsname\the\theorem@bodyfont
28         \@thm{#1}{#2}}\%
29     \global\expandafter\let\csname end#1\endcsname\@endtheorem
30     \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{\LWR@thmstyle#1}}}\% l warp
31   }%
32
33 \gdef\yntheorem#1#2{%
34   \expandafter\@if definable\csname #1\endcsname
35   {
```

```

36 \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}{% lwarp
37 \@definecounter{#1}%
38 \expandafter\xdef\csname the#1\endcsname{\@thmcnter{#1}}%
39 \def\@tempa{\global\@namedef{#1}}\expandafter \atempa
40 \expandafter{\csname th@\the\@theorem@style \expandafter
41 \endcsname \the\@theorem@bodyfont \athm{#1}{#2}}%
42 \global \expandafter \let \csname end#1\endcsname \endtheorem
43 \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}{% lwarp
44 }%
45
46 \gdef\@othm#1[#2]{%
47 \expandafter\ifx\csname c@#2\endcsname\relax
48 \nocounterr{#2}%
49 \else
50 \expandafter\@ifdefinable\csname #1\endcsname
51 {%
52 \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}{% lwarp
53 \expandafter \xdef \csname the#1\endcsname
54 {\expandafter \noexpand \csname the#2\endcsname}%
55 \def\@tempa{\global\@namedef{#1}}\expandafter \atempa
56 \expandafter{\csname th@\the\@theorem@style \expandafter
57 \endcsname \the\@theorem@bodyfont \athm{#2}{#3}}%
58 \global \expandafter \let \csname end#1\endcsname \endtheorem
59 \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}{% lwarp
60 }%
61 \fi}

```

## § 498.2 css patches

The following are patched for css.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a BlockClass environment of class theorembody<style>.

Each header is encased in an \InlineClass of class theoremheader.

```

62 \gdef\th@plain{%
63 \def\@begintheorem##1##2{%
64 \item[%
65 \InlineClass{theoremheader}{##1\ ##2}%
66 ]%
67 }%
68 \def\@opargbegintheorem##1##2##3{%
69 \item[%
70 \InlineClass{theoremheader}{##1\ ##2\ (#3)}%
71 ]%
72 }%
73 }%
74
75 \gdef\th@break{%
76 \def\@begintheorem##1##2{%
77 \item[%
78 \InlineClass{theoremheader}{##1\ ##2}\newline%

```

```
79      ]
80      }%
81 \def\@opargbegintheorem##1##2##3{%
82   \item[
83     \InlineClass{theoremheader}{##1\ ##2\ (#3)}\newline
84   ]
85 }
86 }
87
88 \gdef\th@marginbreak{%
89   \def\@begintheorem##1##2{
90     \item[
91       \InlineClass{theoremheader}{##2 \qquad ##1}\newline
92     ]
93   }%
94 \def\@opargbegintheorem##1##2##3{%
95   \item[
96     \InlineClass{theoremheader}{##2 \qquad ##1\ %
97     (#3)}\newline
98   ]
99 }
100 }
101
102 \gdef\th@changebreak{%
103   \def\@begintheorem##1##2{
104     \item[
105       \InlineClass{theoremheader}{##2\ ##1}\newline
106     ]
107   }%
108 \def\@opargbegintheorem##1##2##3{%
109   \item[
110     \InlineClass{theoremheader}{##2\ ##1\ %
111     (#3)}\newline
112   ]
113 }
114 }
115
116 \gdef\th@change{%
117   \def\@begintheorem##1##2{
118     \item[
119       \InlineClass{theoremheader}{##2\ ##1}
120     ]
121   }%
122 \def\@opargbegintheorem##1##2##3{%
123   \item[
124     \InlineClass{theoremheader}{##2\ ##1\ (#3)}
125   ]
126 }
127 }
128
129 \gdef\th@margin{%
130   \def\@begintheorem##1##2{
131     \item[
132       \InlineClass{theoremheader}{##2 \qquad ##1}
133     ]
134 }
```

---

```

134      }%
135 \def\@opargbegintheorem##1##2##3{%
136   \item[%
137     \InlineClass{theoremheader}{##2 \qquad ##1\ (###3)}%
138   ]%
139 }
140 }
```

Patched for css:

```

141 \gdef\@thm#1{\refstepcounter{#1}%
142 \LWR@forcenewpage% l warp
143   \BlockClass{theorembdy}\LWR@thisthmstyle% l warp
144   \trivlist
145   \topsep \theorempreskipamount           % used by first \item
146   \topsepadd \theorempostskipamount       % used by \endparenv
147   \ifnextchar [%%
148   {\@ythm{#1}{#2}}%
149   {\@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}}%
150
151 \gdef\@endtheorem{%
152 \endtrivlist
153 \endBlockClass
154 }
```

---

### File 399 **l warp-thinsp.sty**

#### § 499 Package **thinsp**

Pkg thinsp thinsp is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{thinsp}[2016/10/02]

```

2 \AtBeginDocument{
3 \let\thinthinspace\relax% defined by some packages
4 \newcommand*\thinthinspace{\thinspace}
5 }
6
7 \newcommand*\stretchthinspace{\thinspace}
8 \newcommand*\stretchthinthinspace{\thinthinspace}
9 \newcommand*\stretchnegthinspace{\negthinspace}
```

---

### File 400 **l warp-threadcol.sty**

#### § 500 Package **threadcol**

Pkg threadcol threadcol is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{threadcol}[2013/01/06]

```
2 \newcommand{\setthreadname}[1]{}
```

---

File 401 **l warp-threeparttable.sty**

§ 501      Package **threeparttable**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg threeparttable threeparttable is emulated.

Table note are contained inside a css <div> of class tnotes. If enumitem is used, the note item labels are also individually highlighted with an additional css <span> of class tnoteitemheader, otherwise they are plain text.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{threeparttable}[2003/06/13]

Env threeparttable [ $\langle alignment \rangle$ ]

```
2 \newenvironment*{threeparttable}[1][b]
3   {\def\@captype{table}}
4 }
```

Env tablenotes [ $\langle options \rangle$ ]

```
5 \newenvironment*{tablenotes}[1][]{%
6   \LWR@forcenewpage
7   \BlockClass{tnotes}%
8   \description%
9 }
10 \enddescription%
11 \endBlockClass%
12 }
```

\tnote { $\langle text \rangle$ }

```
15 \newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}
```

Env measuredfigure [ $\langle alignment \rangle$ ]

```
16 \newenvironment*{measuredfigure}[1][t]
17   {\def\@captype{figure}}
18 }
```

---

File 402 **lwarp-threeparttablex.sty**

§ 502      Package **threeparttablex**

Pkg threeparttablex threeparttablex is patched for use by lwarp.

threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[ . . . ] \endhead % or \endfirsthead
[ . . . ] \endfoot
\bottomrule \insertTableNotes \endlastfoot
}
... table contents ...
\warpHTMLonly{ % HTML last footer
\bottomrule
\UseMinipageWidths % optional
\insertTableNotes
\endlastfoot
}
\end{longtable}
```

**table width** The table notes are created using a `\multicolumn`. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use `\UseMinipageWidths` before `\insertTableNotes`. The width is then specified, and in many cases the result is an improvement in overall table layout.

**for HTML output** 1 \LWR@ProvidesPackagePass{threeparttablex}[2013/07/23]

The width is guessed depending on the number of columns, then limited to a min/max.

```
2 \renewcommand\insertTableNotes{%
3   \setlength{\LWR@templengthone}{.375in*\value{LWR@tabletotalLaTeXcols}}%
4   \setlength{\LWR@templengthone}{\minof{\textwidth}{\LWR@templengthone}}%
5   \setlength{\LWR@templengthone}{\maxof{2.5in}{\LWR@templengthone}}%
6   \multicolumn{\value{LWR@tabletotalLaTeXcols}}{c}{%
7     \parbox{\LWR@templengthone}{%
8       \begin{tablenotes}[\TPTL@optarg]%
9         \TPTL@font%
10        \TPTL@body%
11       \end{tablenotes}%
12     }%
13   }%
14 }%
15
16 \renewcommand\TPTL@tnotex[2]{\tnote{\nameref{#2}}}
```

---

**File 403 l warp-thumb.sty****§ 503 Package thumb**

Pkg thumb thumb is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{thumb}[1997/12/24]
2 \newcommand*\Overviewpage(){}
3 \newlength{\thumbheight}
4 \newlength{\thumbwidth}
```

---

**File 404 l warp-thumbs.sty****§ 504 Package thumbs**

Pkg thumbs thumbs is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{thumbs}[2014/03/09]
2 \newcommand{\addthumb}[4]{}
3 \newcommand{\addtitlethumb}[5]{}
4 \newcommand{\stopthumb}{}
5 \newcommand{\continuethumb}{}
6 \newcommand{\thumbsoverview}[1]{}
7 \newcommand{\thumbsoverviewback}[1]{}
8 \newcommand{\thumbsoverviewverso}[1]{}
9 \newcommand{\thumbsoverviewdouble}[1]{}
10 \newcommand{\thumbnewcolumn}{}
11 \newcommand{\addthumbsoverviewtocontents}[2]{}
12 \newcommand{\thumbnophantom}{}
```

---

**File 405 l warp-tikz.sty****§ 505 Package tikz**

(Emulates or patches code by TILL TANTAU.)

Pkg tikz tikz is supported.

**⚠ displaymath and matrices** If using display math with `tikzpicture` or `\tikz`, along with matrices with the & character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of & in the tikz expression must be replaced with \&.

Accept all options for lwarp-tikz:

```
1 \LWR@ProvidesPackagePass{tikz}[2015/08/07]
```

**catcodes** lwarp changes the catcode of \$ for its own use. The Tikz babel library temporarily changes catcodes back to normal for Tikz's use. tikz v3.0.0 introduced the babel library which handles catcode changes. For older versions, lwarp must change \$'s catcode itself.

Also see:

<https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded>

```
2 \newbool{\LWR@tikzbabel}
3
4 \@ifpackagelater{tikz}{2013/12/20}%
5 {\usetikzlibrary{babel}\booltrue{\LWR@tikzbabel}}
6 {\boolfalse{\LWR@tikzbabel}}
```

**Env pgfpicture** The \pgfpicture environment is enclosed inside a \lateximage. Enclose the low-level \pgfpicture in a \lateximage. This is also used by the higher-level \tikz and tikzpicture.

```
7 \preto\pgfpicture{%
8   \begin{lateximage}[-tikz-\~\PackageDiagramAltText]%
9   \ifbool{\LWR@tikzbabel}{% Test for Tikz version v3.0.0
10   {}%
11   {\catcode`\$=3}% dollar sign is math shift
12 }
13
14 \appto\endpgfpicture{\end{lateximage}}
```

Tikz is placed inside an svg image, so use the original meanings of the following:

```
15 \LetLtxMacro\pgfutil@minipage\LWR@print@minipage
16 \let\pgfutil@endminipage\endLWR@print@minipage
17
18 \let\pgfutil@raggedleft\LWR@print@raggedleft
19 \let\pgfutil@raggedright\LWR@print@raggedright
20
21 \def\pgfutil@font@tiny{\LWR@printtiny}
22 \def\pgfutil@font@scriptsize{\LWR@printsizescript}
23 \def\pgfutil@font@footnotesize{\LWR@printfootnotesize}
24 \def\pgfutil@font@small{\LWR@print@small}
25 \def\pgfutil@font@normalsize{\LWR@print@normalsize}
26 \def\pgfutil@font@Large{\LWR@printlarge}
27 \def\pgfutil@font@Large{\LWR@printLarge}
28 \def\pgfutil@font@huge{\LWR@printhuge}
29 \def\pgfutil@font@Huge{\LWR@printHuge}
30
31 \def\pgfutil@font@itshape{\LWR@origitshape}
32 \def\pgfutil@font@bfseries{\LWR@origbfseries}
```

```
33  
34 \def\pgfutil@font@normalfont{\LWR@orignormalfont}
```

---

**File 406 l warp-**titleps**.sty**

§ 506      Package **titleps**

(Emulates or patches code by JAVIER BEZOS.)

Pkg **titleps** **titleps** is loaded and used by **l warp** during **HTML** output. All user options and macros are ignored and disabled.

Discard all options for **l warp-titleps**:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{titleps}[2016/03/15]

\pagestyle and \thispagestyle are already disabled in the **l warp** code.

\newpagestyle {⟨name⟩} [⟨style⟩] {⟨commands⟩}  
2 \NewDocumentCommand{\newpagestyle}{m o m}{}{}

\renewpagestyle {⟨name⟩} [⟨style⟩] {⟨commands⟩}  
3 \NewDocumentCommand{\renewpagestyle}{m o m}{}{}

\sethead [⟨el⟩] [⟨ec⟩] [⟨er⟩] {⟨ol⟩} {⟨oc⟩} {⟨or⟩}  
4 \NewDocumentCommand{\sethead}{o o o m m m}{}{}

\setfoot [⟨el⟩] [⟨ec⟩] [⟨er⟩] {⟨ol⟩} {⟨oc⟩} {⟨or⟩}  
5 \NewDocumentCommand{\setfoot}{o o o m m m}{}{}

\settitemarks \* {⟨names⟩}  
6 \NewDocumentCommand{\settitemarks}{s m}{}{}

\headrule  
7 \newcommand\*{\headrule}{}{}

\footrule  
8 \newcommand\*{\footrule}{}{}

\setheadrule {⟨length⟩}  
9 \newcommand\*{\setheadrule}[1]{}{}

```
\setfootrule  {\langle length\rangle}
10 \newcommand*{\setfootrule}[1]{}

\makeheadrule
11 \newcommand*{\makeheadrule}{}

\makefootrule
12 \newcommand*{\makefootrule}{}

\setmarkboth  {\langle code\rangle}
13 \newcommand{\setmarkboth}[1]{}

\widenhead
14 \NewDocumentCommand{\widenhead}{s o o m m}{}

\bottitlemarks
15 \newcommand*{\bottitlemarks}{}

\toptitlemarks
16 \newcommand*{\toptitlemarks}{}

\firstititlemarks
17 \newcommand*{\firstititlemarks}{}

\nexttitlemarks
18 \newcommand*{\nexttoptitlemarks}{}

\outertitlemarks
19 \newcommand*{\outertitlemarks}{}

\innertitlemarks
20 \newcommand*{\innertitlemarks}{}

\newtitlemark * {\langle name\rangle}
21 \NewDocumentCommand{\newtitlemark}{s m}{}

\pretitlemark  * {\langle section\rangle} {\langle text\rangle}
22 \NewDocumentCommand{\pretitlemark}{s m m}{}
```

```
\ifsamemark {⟨group⟩} {⟨command⟩} {⟨true⟩} {⟨false⟩}
23 \newcommand{\ifsamemark}[4]{}

\setfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨extra⟩} [⟨which⟩]
24 \NewDocumentCommand{\setfloathead}{s o o o m m m m}{}

\setfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨extra⟩} [⟨which⟩]
25 \NewDocumentCommand{\setfloatfoot}{s o o o m m m m}{}

\nextfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨extra⟩} [⟨which⟩]
26 \NewDocumentCommand{\nextfloathead}{s o o o m m m m}{}

\nextfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨extra⟩} [⟨which⟩]
27 \NewDocumentCommand{\nextfloatfoot}{s o o o m m m m}{}

\newmarkset {⟨markset⟩}
28 \newcommand{\newmarkset}[1]{}

\newextramark * {⟨markset⟩} {⟨macro-name⟩}
29 \NewDocumentCommand{\newextramarkset}{s m m}{}

\botextramarks {⟨markset⟩}
30 \newcommand{\botextramarks}[1]{}

\topextramarks {⟨markset⟩}
31 \newcommand{\topextramarks}[1]{}

\firstextramarks {⟨markset⟩}
32 \newcommand{\firstextramarks}[1]{}

\nextextramarks {⟨markset⟩}
33 \newcommand{\nexttopextramarks}[1]{}

\outerextramarks {⟨markset⟩}
34 \newcommand{\outerextramarks}[1]{}

\innerextramarks {⟨markset⟩}
35 \newcommand{\innerextramarks}[1]{}
```

---

**File 407 l warp-titleref.sty**

§ 507 Package **titleref**

Pkg titleref titleref is emulated.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{titleref}[2001/04/05]
2
3 \LetLtxMacro\titleref\nameref
4
5 \providecounter{LWR@currenttitle}
6
7 \newcommand*\currenttitle{%
8     \addtocounter{LWR@currenttitle}{1}%
9     \label{currenttitle}\arabic{LWR@currenttitle}}%
10    \nameref{currenttitle}\arabic{LWR@currenttitle}}%
11 }
12
13 \newcommand*\theTitleReference[2]{}%
```

---

**File 408 l warp-titlesec.sty**

§ 508 Package **titlesec**

(Emulates or patches code by JAVIER BEZOS.)

Pkg titlesec titlesec is emulated. All user options and macros are ignored and disabled.

Discard all options for l warp-titlesec:

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{titlesec}[2016/03/21]

\titelabel {\langle label-format\rangle}
2 \newcommand*\titleref[1]{}

\titleformat* {\langle command\rangle} {\langle format\rangle}

\titleformat {\langle command\rangle} [{\langle shape\rangle}] {\langle format\rangle} {\langle label\rangle} {\langle sep\rangle} {\langle before\rangle} [{\langle after\rangle}]
3 \newcommand\titleformat{%
4     @ifstar{\ttl@format@s}{%
5         {\ttl@format@i}}}
6 \newcommand{\ttl@format@s}[1]{}
7 \NewDocumentCommand{\ttl@format@i}{m o m m m o}{}%
```

\chaptertitlename

```

8 \@ifundefined{@chapapp}{\let\@chapapp\chaptername}{}
9 \newcommand\chaptertitlename{\@chapapp}

\titlespacing * {\langle command \rangle} {\langle left \rangle} {\langle before \rangle} {\langle after \rangle} [{\langle right \rangle}]
10 \NewDocumentCommand{\titlespacing}{s m m m o}{}

\filright
11 \newcommand*{\filright}{{}{}{}{}{}}

\filcenter
12 \newcommand*{\filcenter}{{}{}{}{}{}}

\filleft
13 \newcommand*{\filleft}{{}{}{}{}{}}

\fillast
14 \newcommand*{\fillast}{{}{}{}{}{}}

\filinner
15 \newcommand*{\filinner}{{}{}{}{}{}}

\filouter
16 \newcommand*{\filouter}{{}{}{}{}{}}

\wordsep
17 \newcommand\wordsep{\fontdimen\tw@\font \fontdimen\thr@@\font \fontdimen4\font}%
18 \fontdimen\thr@@\font \fontdimen4\font}%

\titleline * [{\langle align \rangle}] {\langle material \rangle}
19 \NewDocumentCommand{\titleline}{s o m}{}

\titlerule [{\langle height \rangle}]
20 \providecommand*\titlerule{\@ifstar{\@ttitle@row}{\@ttitle@rule}}
21 \newcommand*{\@ttitle@rule}[1][]{}
22 \newcommand*{\@ttitle@row}[2][]{}

\iftitlemeasuring {\langle true \rangle} {\langle false \rangle}
23 \newcommand{\iftitlemeasuring}[2]{#2}

\assignpagestyle {\langle command \rangle} {\langle pagestyle \rangle}

```

```
24 \newcommand{\assignpagestyle}[2]{#2}

\titleclass {⟨name⟩} [⟨startlevel⟩] {⟨class⟩} [⟨cmd⟩]
25 \NewDocumentCommand{\titleclass}{m o m o}{}
```

---

**File 409 l warp-titletoc.sty****§ 509 Package titletoc**

(Emulates or patches code by JAVIER BEZOS.)

Pkg titletoc titletoc is emulated. All user options and macros are ignored and disabled.

Discard all options for l warp-titletoc:

for HTML output: 1 \LWR@ProvidesPackageDrop{titletoc}[2011/12/15]

```
\dottedcontents {⟨section⟩} [⟨left⟩] {⟨above⟩} {⟨label⟩} {⟨leader⟩}
2 \NewDocumentCommand{\dottedcontents}{m o m m m}{}

\titlecontents * {⟨section⟩} [⟨left⟩] {⟨above⟩} {⟨numbered⟩} {⟨numberless⟩} {⟨filler⟩} [⟨below or
begin⟩] [⟨separator⟩] [⟨end⟩]
3 \newcommand{\titlecontents}{\ifstar{\@ttl@tcstar}{\@ttl@tcnostar}}
4 \NewDocumentCommand{\@ttl@tcstar}{m o m m m o o o}{}
5 \NewDocumentCommand{\@ttl@tcnostar}{m o m m m o}{}
```

```
\contentsmargin [⟨correction⟩] {⟨right⟩}
6 \newcommand{\contentsmargin}[2]{}{}
```

```
\thecontentslabel
7 \newcommand*{\thecontentslabel}{\thecontentslabel}
```

```
\thecontentspage
8 \newcommand*{\thecontentspage}{\thecontentspage}
```

```
\contentslabel [⟨format⟩] {⟨space⟩}
9 \newcommand{\contentslabel}[2][]{\thecontentslabel}
```

```
\contentspage [⟨format⟩]
10 \newcommand{\contentspage}[1][]{\thecontentspage}
```

```
\contentspush {⟨text⟩}
```

---

```

11 \newcommand{\contentspush}[1]{}

\contentsuse  {\langle name\rangle } {\langle text\rangle }

12 \newcommand{\contentsuse}[2]{}

\startcontents [⟨name⟩]
13 \newcommand*{\startcontents}[1][]{}

\stopcontents [⟨name⟩]
14 \newcommand*{\stopcontents}[1][]{}

\resumecontents [⟨name⟩]
15 \newcommand*{\resumecontents}[1][]{}

\printcontents [⟨name⟩] {⟨prefix⟩} {⟨start⟩} {⟨code⟩}
16 \newcommand{\printcontents}[4][]{}

\startlist [⟨name⟩] {⟨list⟩}
17 \newcommand{\startlist}[2][]{}

\stoplist [⟨name⟩] {⟨list⟩}
18 \newcommand{\stoplist}[2][]{}

\resumelist [⟨name⟩] {⟨list⟩}
19 \newcommand{\resumelist}[2][]{}

\printlist [⟨name⟩] {⟨list⟩} {⟨prefix⟩} {⟨code⟩}
20 \newcommand{\printlist}[4][]{}

```

---

File 410 **lwarp-titling.sty**

§ 510 Package **titling**

*(Emulates or patches code by PETER WILSON.)*

Pkg **titling**

**package support** lwarp supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.  
**⚠ load order**

**\published and \subtitle** If using the titling package, additional titlepage fields for \published and \subtitle

may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

The various `titling` footnote restyling commands have no effect.

Pass all options to `l warp-titling`:

**for HTML output:** 1 \LWR@ProvidesPackagePass{titling}[2009/09/04]

\@bsmtitleempty Patch \@bsmtitleempty:

```
2 \let\LWR@orig@bsmtitleempty\@bsmtitleempty
3 \renewcommand*\{@bsmtitleempty}{%
4 \LWR@orig@bsmtitleempty%
5 }
```

\keepthetitle Patch \keepthetitle:

```
6 \let\LWR@origkeepthetitle\keepthetitle
7 \renewcommand*\{keepthetitle}{%
8 \LWR@orig@keepthetitle%
9 }
```

\killtitle Patch \killtitle:

```
10 \let\LWR@origkilltitle\killtitle
11 \renewcommand*\{killtitle}{%
12 \LWR@orig@killtitle%
13 }
```

Env titlingpage

```
14 \renewenvironment*{titlingpage}
15 {%
```

Start an HTML titlepage div:

```
16 \LWR@printpendingfootnotes
17 \begin{titlepage}
```

Prepare for a custom version of \maketitle inside the titlingpage:

```
18 \LWR@maketitlesetup
19 \let\maketitle\LWR@titlingmaketitle
20 }
21 {
```

At the end of the environment, end the HTML titlepage div:

```
22 \end{titlepage}
23 }
```

Patch the pre/post title/author/date to add HTML tags, then initialize:

---

```

24
25 \pretitle{}
26 \posttitle{}
27
28 \preauthor{}
29 \postauthor{}
30
31 \predate{}
32 \postdate{}
```

\LWR@maketitlesetup Patches \thanks macros.

```
33 \renewcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
34 \def\makefnmark{\textsuperscript{\@thefnmark}}
```

```
\thefootnote \Rightarrow \nameuse{arabic}{footnote}, or
\thefootnote \Rightarrow \nameuse{fnsymbol}{footnote}
```

Redefine the footnote text:

```
35 \long\def\makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
36 \makethanksmark~%
```

```
\makethanksmark \Rightarrow \thanksfootmark \Rightarrow \tamark \Rightarrow
\@thefnmark \Rightarrow \itshape a (or similar)
```

Print the text:

```
37 ##1%
38 }% \makefntext
39 }
```

\thanksfootmark

```

40 \renewcommand{\thanksfootmark}{%
41 % \hb@xt@{\thanksmarkwidth{\hfil\normalfont%
42 % \thanksscript{%
43 % \thanksfootpre \tamark \thanksfootpost%
44 % }%
45 % }%
46 }
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the `titling` package is adapted, simplified, and modified for HTML output.

47 \renewcommand\*\maketitle}{%

An HTML titlepage <div> is used for all classes.

48 \begin{titlepage}

Select which kind of footnote marks to use:

49 \@bsmarkseries

Set up special patches:

50 \LWR@maketitlesetup

Typeset the title, etc:

51 \@maketitle

Immediately generate any \thanks footnotes:

52 \LWR@stopars@\thanks\LWR@startpars

Close the HTML titlepage div:

53 \end{titlepage}

Reset the footnote counter:

54 \@bscontmark  
55 }

\@maketitle Typesets the title, etc. Patched for HTML.

56 \DeclareDocumentCommand{\@maketitle}{}{  
57 \maketitlehooka  
58 {  
59 \LWR@stopars\LWR@htmlltag{\LWR@tagtitle}%  
60 \@bspretitle \@title \@bsposttitle%  
61 \LWR@htmlltag{\LWR@tagtitleend}\LWR@startpars%  
62 }  
63 \maketitlehookb  
64 {  
65 \begin{BlockClass}{author}  
66 \renewcommand{\and}{%  
67 \end{BlockClass}%  
68 \begin{BlockClass}{oneauthor}%  
69 }  
70 \begin{BlockClass}{oneauthor}%  
71 \@bspreauthor \@author \@bspostauthor%  
72 \end{BlockClass}%

---

```

73      \end{BlockClass}%
74  }
75  \maketitlehookc
76  {
77      \begin{BlockClass}{titledate}%
78      \@bspredate \@date \@bspostdate%
79      \end{BlockClass}%
80  }
81  \maketitlehookd
82 }
```

\LWR@titlingmaketitle \maketitle for use inside an HTML titlingpage environment.

```
83 \renewcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
84 \LWR@stoppars \@thanks \LWR@startpars
```

Select which kind of footnote marks to use:

```
85 \@bsmarkseries
```

Set up special patches:

```
86 \LWR@maketitlesetup
```

Typeset the title, etc:

```
87 \@maketitle
```

Immediately generate any \thanks footnotes:

```
88 \LWR@stoppars \@thanks \LWR@startpars
```

Reset the footnote counter:

```
89 \@bscontmark
90 }
```

\thanksmarkseries {\langle series \rangle}

Sets the type of footnote marks used by \thanks, where type is ‘arabic’, ‘roman’, ‘fn-symbol’, etc.

```
91 \renewcommand{\thanksmarkseries}[1]{%
92 \def\@bsmarkseries{\renewcommand{\thefootnote}{\@nameuse{\#1}{footnote}}}}
93 }
```

Set default titlepage thanks footnote marks. See section 66.7.

---

```

94 \@ifclassloaded{memoir}{
95   \thanksmarkseries{arabic}
96 }{% not memoir
97 \if@titlepage
98   \thanksmarkseries{arabic}
99 \else
100   \thanksmarkseries{fnsymbol}
101 \fi
102 }% not memoir

```

---

File 411 **l warp-tocbasic.sty**

§ 511 Package **tocbasic**

*(Emulates or patches code by MARKUS KOHM.)*

Pkg **tocbasic** **tocbasic** is nullified for **l warp**.

This package may be loaded standalone, but is also loaded automatically if **koma-script** classes are in use. **\DeclareDocumentCommand** is used to overwrite the **koma-script** definitions.

**for HTML output:** 1 \LWR@ProvidesPackagePass{tocbasic}[2018/12/30]

```

2 \DeclareDocumentCommand{\usetocbasicnumberline}{o}{}
3 \DeclareDocumentCommand{\DeclareTOCStyleEntry}{o m m}{}
4 \DeclareDocumentCommand{\DeclareTOCStyleEntries}{o m m}{}
5 \DeclareDocumentCommand{\DeclareTOCEntryStyle}{m o m}{}
6 \DeclareDocumentCommand{\DefineTOCEntryOption}{m o m}{}
7 \DeclareDocumentCommand{\DefineTOCEntryBooleanOption}{m o m m m}{}
8 \DeclareDocumentCommand{\DefineTOCEntryCommandOption}{m o m m m}{}
9 \DeclareDocumentCommand{\DefineTOCEntryIfOption}{m o m m m}{}
10 \DeclareDocumentCommand{\DefineTOCEntryLengthOption}{m o m m m}{}
11 \DeclareDocumentCommand{\DefineTOCEntryNumberOption}{m o m m m}{}
12 \DeclareDocumentCommand{\CloneTOCEntryStyle}{m m}{}
13 \DeclareDocumentCommand{\TOCEntryStyleInitCode}{m m}{}
14 \DeclareDocumentCommand{\TOCEntryStyleStartInitCode}{m m}{}

```

---

File 412 **l warp-tocbibind.sty**

§ 512 Package **tocbibind**

*(Emulates or patches code by PETER WILSON.)*

Pkg **tocbibind** **tocbibind** is patched for use by **l warp**.

**placement and toc options** An index may be placed inline with other HTML text, or on its own HTML page:

Pkg **makeidx** **Inline, with a manual toc entry:**

A commonly-used method to introduce an index in a L<sup>A</sup>T<sub>E</sub>X document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname} or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The **tocbibind** package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex **numbered index section** Use the **tocbibind numindex** option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as **imakeidx**, may also have options for including the index in the Table of Contents.

**for HTML output:**

```

1 \let\simplechapterdelim\relax
2
3 \LWR@ProvidesPackagePass{tocbibind}[2010/10/13]

4 \renewenvironment{theindex}%
5 {%
6     \if@bibchapter
7         \if@donumindex
8             \chapter{\indexname}
9         \else
10            \if@dotocind
11                \chapter*{\indexname}
12                \addcontentsline{toc}{chapter}{\LWR@isolate{\indexname}}
13            \else
14                \chapter*{\indexname}
```

```

15      \fi
16      \fi
17  \else
18      \if@donumindex
19          \section{\indexname}
20      \else
21          \if@dotocind
22              \section*{\indexname}
23              \addcontentsline{toc}{\@tocextra}{\LWR@isolate{\indexname}}
24          \else
25              \section*{\indexname}
26          \fi
27      \fi
28  \fi
29 \let\item\LWR@indexitem%
30 \let\subitem\LWR@indexsubitem%
31 \let\subsubitem\LWR@indexsubsubitem%
32 }{}
```

The following code is shared by `anonchap`.

```

33 \DeclareDocumentCommand{\simplechapter}{O{\emptyset}}{%
34     \def\@chapcntformat##1{%
35         #1\cscname \the##1\endcscname\simplechapterdelim\quad%
36     }%
37 }%
38
39 \DeclareDocumentCommand{\restorechapter}{%
40 \let\@chapcntformat\@secntformat%
41 }
```

### File 413 **lwarp-tocdata.sty**

#### § 513 Package **tocdata**

*(Emulates or patches code by BRIAN DUNN.)*

Pkg **tocdata** **tocdata** is patched for use by **lwarp**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{tocdata}[2019/07/06]

```

2 \renewcommand*\LWR@maybetocdata{%
3     \ifdef\empty{\TD@thistocdata}{}{%
4         \quad \InLineClass{authorartist}{\tocdataformat{\TD@thistocdata}}%
5         \def\TD@thistocdata{}%
6     }%
7 }

8 \renewrobustcmd{\tocdatapartprint}[4]
9 {%
10     \InLineClass{authorartist}{%
```

```
11      \qquad --- %
12      \TOptionalnameprint{\#1}\TOptionalnameprint{\#2}\#3\#4%
13  }%
14 }
15
16 \@ifundefined{chapter}{}{
17     \let\tocdatachapterprint\tocdatapartprint
18 }
19 \let\tocdatasectionprint\tocdatapartprint
20 \let\tocdatasubsectionprint\tocdatapartprint
21
22 \newcommand*{\LWR@TD@settextalign}[1]{%
23     \def\LWR@TD@textalign{justify}%
24     \ifcsstring{TD@#1align}{\centering}%
25         {\def\LWR@TD@textalign{center}}%
26     {}%
27     \ifcsstring{TD@#1align}{\raggedleft}%
28         {\def\LWR@TD@textalign{right}}%
29     {}%
30     \ifcsstring{TD@#1align}{\raggedright}%
31         {\def\LWR@TD@textalign{left}}%
32     {}%
33 }
34
35 \renewcommand{\TDArtistauthorprint}[5]{%
36     \LWR@TD@settextalign{\#1}%
37     \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
38     \InlineClass{authorartist}{\TOptionalnameprint{\#2}\TOptionalnameprint{\#3}\#4\#5}%
39     \end{BlockClass}%
40 }
41
42 \newcommand*{\LWR@TD@setnamealign}[1]{%
43     \def\LWR@TD@textalign{justify}%
44     \ifcsstring{TD@#1textalign}{\centering}%
45         {\def\LWR@TD@textalign{center}}%
46     {}%
47     \ifcsstring{TD@#1textalign}{\raggedleft}%
48         {\def\LWR@TD@textalign{right}}%
49     {}%
50     \ifcsstring{TD@#1textalign}{\raggedright}%
51         {\def\LWR@TD@textalign{left}}%
52     {}%
53 }
54
55 \renewcommand{\TDArtistauthortextprint}[2]{%
56     \LWR@TD@setnamealign{\#1}%
57     \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
58     #2%
59     \end{BlockClass}%
60 }
```

---

**File 414 l warp-tocenter.sty****§ 514 Package tocenter**

Pkg tocenter tocenter is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tocenter}[2004/12/09]

2 \NewDocumentCommand{\ToCenter}{s o m m}{}  
3 \NewDocumentCommand{\FromMargins}{s o m m m m}{}

---

**File 415 l warp-tocloft.sty****§ 515 Package tocloft**

(Emulates or patches code by PETER WILSON.)

Pkg tocloft tocloft is emulated. Most user options and macros are ignored and disabled. \newlistof and \cftchapterprecis are supported.

Pkg tocloft If using tocloft with tocbbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its titles option, which tells tocloft to use standard LATEX commands to create the titles, allowing other packages to work with it.

⚠ tocloft & other packages Discard all options for l warp-tocloft:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tocloft}[2017/08/31]

\tocloftpagestyle {\langle style \rangle}  
2 \newcommand{\tocloftpagestyle}[1]{}

---

\cftmarktoc  
3 \newcommand\*{\cftmarktoc}{}

---

\cfttoctitlefont  
4 \newcommand\*{\cfttoctitlefont}{}

---

\cftaftertoctitle  
5 \newcommand\*{\cftaftertoctitle}{}  
6 \newlength{\cftbeforetoctitleskip}  
7 \newlength{\cftaftertoctitleskip}

```
\cftmarklof
 8 \newcommand*\{\cftmarklof\}{}  
  
\cftloftitlefont
 9 \newcommand*\{\cftloftitlefont\}{}  
  
\cftafterloftitle
10 \newcommand*\{\cftafterloftitle\}{}  
  
11 \newlength{\cftbeforeloftitleskip}
12 \newlength{\cftafterloftitleskip}  
  
\cftmarklot
13 \newcommand*\{\cftmarklot\}{}  
  
\cftlottitlefont
14 \newcommand*\{\cftlottitlefont\}{}  
  
\cftafterlottitle
15 \newcommand*\{\cftafterlottitle\}{}  
  
16 \newlength{\cftbeforelottitleskip}
17 \newlength{\cftafterlottitleskip}  
  
\cftdot
18 \providecommand*\{\cftdot\}{.}  
  
\cftdotsep
19 \providecommand*\{\cftdotsep\}{1}  
  
\cftnodots
20 \providecommand*\{\cftnodots\}{5000}  
  
\cftdotfill  {\langle sep\rangle}
21 \providecommand{\cftdotfill}[1]{}  
  
\cftsetpnumwidth {\langle length\rangle}
22 \DeclareDocumentCommand{\cftsetpnumwidth}{m}{}  

```

---

```
\cftsetrmarg {<length>}
23 \DeclareDocumentCommand{\cftsetrmarg}{m}{}}

\cftpnumalign {<alignment>}
24 \DeclareDocumentCommand{\cftpnumalign}{m}{}}

25 \LWR@providelength{\cftparskip}
```

The part-related items are also provided by memoir:

```
26 \LWR@providelength{\cftbeforepartskip}
27 \LWR@providelength{\cftpartindent}
28 \LWR@providelength{\cftpartnumwidth}
29 \providecommand*{\cftpartfont} {}
30 \providecommand*{\cftpartpresnum} {}
31 \providecommand*{\cftpartaftersnum} {}
32 \providecommand*{\cftpartaftersnumb} {}
33 \providecommand*{\cftpartleader} {}
34 \providecommand*{\cftpartdotsep}{1}
35 \providecommand*{\cftpartpagefont} {}
36 \providecommand*{\cftpartafterpnum} {}
```

**memoir** uses the full name “chapter” instead of “chap”:

```
37 \LWR@providelength{\cftbeforechapskip}
38 \LWR@providelength{\cftchapindent}
39 \LWR@providelength{\cftchapnumwidth}
40 \newcommand*{\cftchapfont} {}
41 \newcommand*{\cftchappresnum} {}
42 \newcommand*{\cftchapaaftersnum} {}
43 \newcommand*{\cftchapaaftersnumb} {}
44 \newcommand*{\cftchapleader} {}
45 \newcommand*{\cftchapdotsep}{1}
46 \newcommand*{\cftchappagefont} {}
47 \newcommand*{\cftchapaafterpnum} {}
```

The following do not appear in **memoir**:

```
48 \LWR@providelength{\cftbeforesecskip}
49 \LWR@providelength{\cftsecindent}
50 \LWR@providelength{\cftsecnumwidth}
51 \newcommand*{\cftsecfont} {}
52 \newcommand*{\cftsecpresnum} {}
53 \newcommand*{\cftsecaftersnum} {}
54 \newcommand*{\cftsecaftersnumb} {}
55 \newcommand*{\cftsecleader} {}
56 \newcommand*{\cftsecdotsep}{1}
57 \newcommand*{\cftsecpagefont} {}
58 \newcommand*{\cftsecafterpnum} {}

59 \LWR@providelength{\cftbeforesubsecskip}
```

```
60 \LWR@providelength{\cftsubsecindent}
61 \LWR@providelength{\cftsubsecnumwidth}
62 \newcommand*{\cftsubsecfont}{}
63 \newcommand*{\cftsubsecpresnum}{}
64 \newcommand*{\cftsubsecaftersnum}{}
65 \newcommand*{\cftsubsecaftersnumb}{}
66 \newcommand*{\cftsubsecleader}{}
67 \newcommand*{\cftsubsecdotsep}{1}
68 \newcommand*{\cftsubsecpagefont}{}
69 \newcommand*{\cftsubsecafterpnum}{}

70 \LWR@providelength{\cftbeforesubsubsecskip}
71 \LWR@providelength{\cftsubsubsecindent}
72 \LWR@providelength{\cftsubsubsecnumwidth}
73 \newcommand*{\cftsubsubsecfont}{}
74 \newcommand*{\cftsubsubsecpresnum}{}
75 \newcommand*{\cftsubsubsecaftersnum}{}
76 \newcommand*{\cftsubsubsecaftersnumb}{}
77 \newcommand*{\cftsubsubsecleader}{}
78 \newcommand*{\cftsubsubsecdotsep}{1}
79 \newcommand*{\cftsubsubsecpagefont}{}
80 \newcommand*{\cftsubsubsecafterpnum}{}

81 \LWR@providelength{\cftbeforeparaskip}
82 \LWR@providelength{\cftparraindent}
83 \LWR@providelength{\cftparranumwidth}
84 \newcommand*{\cftparrafont}{}
85 \newcommand*{\cftparrapresnum}{}
86 \newcommand*{\cftparraaftersnum}{}
87 \newcommand*{\cftparraaftersnumb}{}
88 \newcommand*{\cftparraleader}{}
89 \newcommand*{\cftparradotsep}{1}
90 \newcommand*{\cftparrapagefont}{}
91 \newcommand*{\cftparraafterpnum}{}

92 \LWR@providelength{\cftbeforesubparaskip}
93 \LWR@providelength{\cftsubparaindent}
94 \LWR@providelength{\cftsubparanumwidth}
95 \newcommand*{\cftsubparafont}{}
96 \newcommand*{\cftsubparapresnum}{}
97 \newcommand*{\cftsubparaafersnum}{}
98 \newcommand*{\cftsubparaafersnumb}{}
99 \newcommand*{\cftsubparaleader}{}
100 \newcommand*{\cftsubparadotsep}{1}
101 \newcommand*{\cftsubparapagefont}{}
102 \newcommand*{\cftsubparaafterpnum}{}

103 \LWR@providelength{\cftbeforefigskip}
104 \LWR@providelength{\cftfigindent}
105 \LWR@providelength{\cftfignumwidth}
106 \newcommand*{\cftfigfont}{}
107 \newcommand*{\cftfigpresnum}{}
108 \newcommand*{\cftfigaftersnum}{}
109 \newcommand*{\cftfigaftersnumb}{}
110 \newcommand*{\cftfigleader}{}
```

```
111 \newcommand*{\cftfigdotsep}{1}
112 \newcommand*{\cftfigpagefont}{}
113 \newcommand*{\cftfigafterpnum}{}

114 \LWR@providelength{\cftbeforesubfigskip}
115 \LWR@providelength{\cftsubfigindent}
116 \LWR@providelength{\cftsubfignumwidth}
117 \newcommand*{\cftsubfigfont}{}
118 \newcommand*{\cftsubfigpresnum}{}
119 \newcommand*{\cftsubfigaftersnum}{}
120 \newcommand*{\cftsubfigaftersnumb}{}
121 \newcommand*{\cftsubfigleader}{}
122 \newcommand*{\cftsubfigdotsep}{1}
123 \newcommand*{\cftsubfigpagefont}{}
124 \newcommand*{\cftsubfigafterpnum}{}

125 \LWR@providelength{\cftbeforetabskip}
126 \LWR@providelength{\cfttabindent}
127 \LWR@providelength{\cfttabnumwidth}
128 \newcommand*{\cfttabfont}{}
129 \newcommand*{\cfttabpresnum}{}
130 \newcommand*{\cfttabaftersnum}{}
131 \newcommand*{\cfttabaftersnumb}{}
132 \newcommand*{\cfttableader}{}
133 \newcommand*{\cfttabdotsep}{1}
134 \newcommand*{\cfttabpagefont}{}
135 \newcommand*{\cfttabafterpnum}{}

136 \LWR@providelength{\cftbeforesubtabskip}
137 \LWR@providelength{\cftsubtabindent}
138 \LWR@providelength{\cftsubtabnumwidth}
139 \newcommand*{\cftsubtabfont}{}
140 \newcommand*{\cftsubtabpresnum}{}
141 \newcommand*{\cftsubtabaftersnum}{}
142 \newcommand*{\cftsubtabaftersnumb}{}
143 \newcommand*{\cftsubtableader}{}
144 \newcommand*{\cftsubtabdotsep}{1}
145 \newcommand*{\cftsubtabpagefont}{}
146 \newcommand*{\cftsubtabafterpnum}{}

147 \DeclareDocumentCommand{\cftsetindents}{m m m}{}

148 \newcommand{\pagenumbersoff}[1]{}
149 \newcommand{\pagenumberson}[1]{}

\newlistentry [⟨within⟩] {⟨counter⟩} {⟨ext⟩} {⟨level-1⟩}
150 \DeclareDocumentCommand{\newlistentry}{o m m m}
151 {%
152 \LWR@traceinfo{newlistentry #2 #3 #4}%
153 \IfValueTF{#1}%
154 {%
155     @ifundefined{c@#2}{%
156         \newcounter{#2}[#1]%
```

```

157      \expandafter\edef\csname the#2\endcsname{%
158          \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}%
159      }%
160  }{%
161 }%
162 {%
163     \@ifundefined{c@#2}{%
164         \newcounter{#2}%
165     }{%
166 }%
167 \namedef{l@#2}##1##2{%
168     \hypertocfloat{1}{#2}{#3}{##1}{##2}%
169     \def\cftwhatismyname{#2} from memoir
170 }%
171 \expandafter\newlength\csname cftbefore#2skip\endcsname%
172 \expandafter\newlength\csname cft#2indent\endcsname%
173 \expandafter\newlength\csname cft#2numwidth\endcsname%
174 \namedef{cft#2font}{}%
175 \namedef{cft#2presnum}{}%
176 \namedef{cft#2aftersnum}{}%
177 \namedef{cft#2aftersnumb}{}%
178 \namedef{cft#2leader}{}%
179 \namedef{cft#2dotsep}{1}%
180 \namedef{cft#2pagefont}{}%
181 \namedef{cft#2afterpnum}{}%
182 \namedef{toclevel@#2}{#4}%
183 \namedef{cft#2fillnum}{#1}%
184 \LWR@traceinfo{newlistentry done}%
185 }

```

\newlistof [⟨within⟩] {⟨type⟩} {⟨ext⟩} {⟨listofname⟩}

Emulated through the \newfloat mechanism.

```

186 \DeclareDocumentCommand{\newlistof}{o m m}
187 {%
188 \IfValueTF{#1}
189 {\newlistentry[#1]{#2}{#3}{0}}
190 {\newlistentry[#2]{#3}{0}}
191 \namedef{ext@#2}{#3}
192 \@ifundefined{c@#3depth}{\newcounter{#3depth}}{%
193 \setcounter{#3depth}{1}
194 \namedef{cftmark#3}{}
195 \namedef{listof#2}{\listof{#2}{#4}}
196 \namedef{@cftmake#3title}{}
197 \expandafter\newlength\csname cftbefore#3titleskip\endcsname
198 \expandafter\newlength\csname cftafter#3titleskip\endcsname
199 \namedef{cft#3titlefont}{}
200 \namedef{cftafter#3title}{}
201 \namedef{cft#3prehook}{}
202 \namedef{cft#3posthook}{}
203 }

```

\cftchapterprecis {⟨text⟩}

```

204 \newcommand{\cftchapterprecis}[1]{%

```

---

```

205 \cftchapterprecishere{#1}
206 \cftchapterprecistoc{#1}
207 \newcommand{\cftchapterprecishere}[1]{%
208   \begin{quote}\textit{#1}\end{quote}}
209 \newcommand{\cftchapterprecistoc}[1]{%
210   \addtocontents{toc}{%
211   {%
212     \protect\begin{quote}#1\protect\end{quote}}%
213   }%
214 }
```

---

File 416 **l warp-tocstyle.sty**

§ 516 Package **tocstyle**

Pkg tocstyle tocstyle is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output: 1 \LWR@ProvidesPackageDrop{tocstyle}[2017/02/23]

```

2 \newcommand*{\usetocstyle}[2][]{}
3 \newcommand*{\deactivatetocstyle}[1][]{}
4 \newcommand*{\reactivatetocstyle}[1][]{}
5 \NewDocumentCommand{\settocfeature}{o o m m}{}
6 \NewDocumentCommand{\settocstylefeature}{o m m}{}
7 \NewDocumentCommand{\newtocstyle}{o o m m}{}
8 \newcommand*{\aliastoc}[2]({})
9 \newcommand*{\showtoc}[2]({})
10 \newcommand{\iftochasdepth}[4]{}  

```

---

File 417 **l warp-todo.sty**

§ 517 Package **todo**

(Emulates or patches code by FEDERICO GARCIA.)

Pkg todo todo is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{todo}[2010/03/31]

```

2 \renewcommand\todoitem[2]{%
3   \refstepcounter{todo}%
4   \item[%
5     \HTMLUnicode{2610} \quad
6     \ref{todopage}:\thetodo%
7   ] : {\todoformat\ifx#1\todomark\else\textbf{#1}\fi}#2%
8   \label{todolbl}:\thetodo%
9 }%
10  

```

---

```

11 \renewcommand\doneitem[2]{%
12   \stepcounter{todo}%
13   \item[%
14     \HTMLUnicode{2611} \quad
15     \ref{todopage:\thetodo}%
16   ] \nameuse{@done}{\c@todo}:%
17   {\todoformat{\ifx#1\todomark\else\textbf{#1}\fi}#2}%
18 }
19
20 \xpatchcmd{\@displaytodo}%
21   {\todoformat{#1}{\todoformat{\textbf{#1}}{}}}
22   {\PackageWarning{lwarf-todo}{Unable to patch \@displaytodo.}}%
23
24 \xpatchcmd{\@displayfulltodo}%
25   {\todoformat{#1}{\todoformat{\textbf{#1}}{}}}
26   {\PackageWarning{lwarf-todo}{Unable to patch \@displayfulltodo.}}%
27
28 \patchcmd{\todoenv}{\itshape see text.}{\textit{see text.}}{}%
29   {\PackageWarning{lwarf-todo}{Unable to patch todoenv.}}%
30
31 \patchcmd{\astodos}{\todoformat{#1}{\todoformat{\textbf{#1}}{}}}
32   {\PackageWarning{lwarf-todo}{Unable to patch astodos.}}%
33
34 \AtBeginDocument{%
35   \crefname{todo}{todo}{todos}%
36   \Crefname{todo}{Todo}{Todos}%
37 }

```

---

#### File 418 **lwarf-todonotes.sty**

### § 518 Package **todonotes**

*(Emulates or patches code by HENRIK SKOV MIDTIBY.)*

Pkg **todonotes** **todonotes** is emulated.

The documentation for **todonotes** and **luatodonotes** have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

**for HTML output:** 1 \LWR@ProvidesPackagePass{todonotes}[2012/07/25]

```

2 \if@todonotes@disabled
3 \else
4
5 \newcommand{\ext@todo}{\tdo}
6
7 \renewcommand{\l@todo}[2]{\hypertocfloat{1}{\tdo}{\ldo}{#2}}
8 \let\LWRTODONOTES@orig@todototoc\ Todototoc
9
10 \renewcommand*\{\todototoc}{%

```

```
11 \phantomsection%
12 \LWRTODONOTES@orig@todototoc%
13 }
14
15 \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
16 \fcolorbox%
17   {\@todonotes@currentbordercolor}%
18   {\@todonotes@currentbackgroundcolor}%
19   {\arabic{@todonotes@numberoftodonotes}}%
20 \marginpar{\@todonotes@drawMarginNote}%
21 }
22
23 \renewcommand{\@todonotes@drawInlineNote}{%
24 \fcolorboxBlock%
25   {\@todonotes@currentbordercolor}%
26   {\@todonotes@currentbackgroundcolor}%
27   {%
28     \if@todonotes@authorgiven%
29       {\@todonotes@author:\,}%
30     \fi%
31     \@todonotes@text%
32   }%
33 }
34
35 \renewcommand{\@todonotes@drawMarginNote}{%
36   \if@todonotes@authorgiven%
37     \@todonotes@author\par%
38   \fi%
39   \arabic{@todonotes@numberoftodonotes}: %
40   \fcolorbox%
41   {\@todonotes@currentbordercolor}%
42   {\@todonotes@currentbackgroundcolor}%
43   {%
44     \@todonotes@sizecommand%
45     \@todonotes@text %
46   }%
47 }%
48
49 \renewcommand{\@todonotes@drawLineToRightMargin}{}%
50
51 \renewcommand{\@todonotes@drawLineToLeftMargin}{}%
52
53 \renewcommand{\missingfigure}[2][]{%
54 \setkeys{todonotes}{#1}%
55 \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
56 \fcolorboxBlock%
57   {\@todonotes@currentbordercolor}%
58   {\@todonotes@currentfigcolor}%
59   {%
60     \setlength{\fboxrule}{4pt}%
61     \fcolorbox{red}{white}{Missing figure} \quad #2%
62   }%
63 }
64
65 \LetLtxMacro{\LWRTODONOTES@orig@todo}{\todo}
```

---

```

66
67 \RenewDocumentCommand{\@todo}{o m}{%
68 \begingroup%
69 \renewcommand*{\phantomsection}{ }%
70 \IfValueTF{#1}{%
71     \LWRTODONOTES@orig@todo[#1]{#2}%
72 }{%
73     \LWRTODONOTES@orig@todo{#2}%
74 }
75 \endgroup%
76 }
77
78 \fi% \if@todonotes@disabled

```

---

File 419 **l warp-topcapt.sty**

§ 519 Package **topcapt**

Pkg topcapt topcapt is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{topcapt}[2004/12/11]

2 \LetLtxMacro\topcaption\caption

---

File 420 **l warp-tram.sty**

§ 520 Package **tram**

Pkg tram tram is emulated.

⚠ **block only** The HTML emulation uses a <div>, which must not appear inside an HTML <span> or an HTML paragraph. For this reason, the `tram` environment should only be used to contain paragraphs inside a `\parbox` or `minipage`. `tram` should not be used to mark up inline text.

To disable `tram`, allowing source compatibility with inline uses:

```

\begin{warpHTML}
\renewenvironment{tram}[1][]{\{}{\}}
\end{warpHTML}

```

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tram}[2013/04/04]

```

2 \newenvironment{tram}[1][]{%
3     {\BlockClass[background:lightgray]{tram}}%
4     {\endBlockClass}%

```

---

**File 421 l warp-transparent.sty****§ 521 Package transparent**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg transparent transparent is emulated. \texttransparent works for inline objects. \transparent only works for \includegraphics.

⚠ Not X<sub>E</sub>T<sub>E</sub>X! Note that transparent does not work with X<sub>E</sub>T<sub>E</sub>X.

for HTML output: Discard all options for l warp-transparent:

```
1 \LWR@ProvidesPackagePass{transparent}[2019/11/29]

2 \newcommand*{\LWR@HTML@transparent}[1]{\edef\LWR@opacity{#1}}
3
4 \LWR@formatted{transparent}
5
6
7 \newcommand*{\LWR@HTML@texttransparent}[2]{%
8 \begingroup%
9 \transparent{#1}%
10 \InlineClass[opacity: #1]{transparent}{#2}%
11 \endgroup%
12 }
13
14 \LWR@formatted{texttransparent}
```

---

**File 422 l warp-trimclip.sty****§ 522 Package trimclip**

Pkg trimclip trimclip is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{trimclip}[2018/04/08]

The third argument, the text, is not touched. This allows \bgroup / \egroup, and verbatim content.

```
2 \csdef{trimbox}{\@ifstar@gobble@gobble}
3 \csletcs{trimbox*}{trimbox}
4 \def\endtrimbox{}
5 \csletcs{endtrimbox*}{endtrimbox}
6
7 \csletcs{clipbox}{trimbox}
8 \csletcs{clipbox*}{trimbox}
9 \csletcs{endclipbox}{endtrimbox}
```

---

```

10 \csletcs{endclipbox*}{endtrimbox}
11
12 \csletcs{marginbox}{trimbox}
13 \csletcs{marginbox*}{trimbox}
14 \csletcs{endmarginbox}{endtrimbox}
15 \csletcs{endmarginbox*}{endtrimbox}
```

---

File 423 **l warp-trivfloat.sty**

§ 523 Package **trivfloat**

*(Emulates or patches code by JOSEPH WRIGHT.)*

Pkg trivfloat trivfloat is forced to use the built-in l warp emulation for floats.

To create a new float type and change its name:

---

```
\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}
```

---

Discard all options for l warp-trivfloat. This tells trivfloat not to use floatrow or memoir.

```

1 \LWR@ProvidesPackageDrop{trivfloat}[2009/04/23]
2 \LWR@origRequirePackage{trivfloat}
```

\tfl@chapter@fix Nullified at the beginning of the document. Is used by trivfloat to correct float chapter numbers, but is not needed for l warp.

for HTML output:

```

3 \begin{warpHTML}
4 \AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{}}
5 \end{warpHTML}
```

§ 523.1 **Combining \newfloat, \trivfloat, and algorithmicx**

for HTML & PRINT: 6 \begin{warpall}

For both print and HTML output:

⚠ When using float, trivfloat, or algorithmicx at the same time, be aware of conflicting file usage. algorithmicx uses .loa. trivfloat by default starts with .loa and goes up for additional floats, skipping .lof and .lot.

⚠ When using \newfloat, be sure to manually assign higher letters to the \newfloat files to avoid .loa used by algorithmicx, and any files used by trivfloat. Also avoid using .lof and .lot.

- ⚠ When using `\trivfloat`, you may force it to avoid conflicting with `algorithmicx` by starting `trivfloat`'s file extensions with `.lob`:

---

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
7 \end{warpall}
```

---

File 424 **l warp-truncate.sty**

§ 524 Package **truncate**

Pkg `truncate` `truncate` is ignored.

for HTML output: 1 `\LWR@ProvidesPackageDrop{truncate}[2001/08/20]`

```
2 \providecommand{\TruncateMarker}{}%
3 \newcommand{\truncate}[3][\TruncateMarker]{#3}
```

---

File 425 **l warp-turnthepage.sty**

§ 525 Package **turnthepage**

Pkg `turnthepage` `turnthepage` is ignored.

for HTML output: 1 `\LWR@ProvidesPackageDrop{turnthepage}[2011/03/24]`

```
2 \newcommand{\turnthepage}{}%
```

---

File 426 **l warp-twoup.sty**

§ 526 Package **twoup**

Pkg `twoup` `twoup` is ignored.

for HTML output: 1 `\LWR@ProvidesPackageDrop{twoup}[2007/02/26]`

```
2 \newcommand{\cleartolastpage}{}%
```

---

**File 427 l warp-typearea.sty****§ 527 Package typarea**

(Emulates or patches code by MARKUS KOHM.)

Pkg typarea typarea is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{typarea}[2018/03/30]

```
2 \DeclareDocumentCommand{\typearea}{o m}{}
3 \DeclareDocumentCommand{\recalctypearea}{}{}
4 \@ifundefined{fooheight}{\newlength\fooheight}{}
5 \DeclareDocumentCommand{\areaset}{o m m}{}
6 \DeclareDocumentCommand{\activateareas}{}{}
7 \DeclareDocumentCommand{\storeareas}{m}{}
8 \DeclareDocumentCommand{\BeforeRestoreareas}{s m}{}
9 \DeclareDocumentCommand{\AfterRestoreareas}{s m}{}
10 \DeclareDocumentCommand{\AfterCalculatingTypearea}{s m}{}
11 \DeclareDocumentCommand{\AfterSettingArea}{s m}{}
```

---

**File 428 l warp-typicons.sty****§ 528 Package typicons**

(Emulates or patches code by ARTHUR VIGIL, XAVIER DANAUX.)

Pkg typicons typicons is patched for use by l warp.

If \ticon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

**for HTML output:** 1 \LWR@ProvidesPackagePass{typicons}[2015/05/20]

```
2 \LetLtxMacro{\LWR@orig@symbol}{\symbol}
3
4 \let\LWR@orig@typicon@TI\TI
5
6 \newcommand*{\LWR@typicon@symbol}[1]{%
7   \begin{lateximage}*[typicon][typicon#1]%
8   \begingroup%
9   \LWR@orig@typicon@TI%
10  \LWR@orig@symbol{#1}%
11  \endgroup%
```

```
12     \end{lateximage}%
13 }
14
15 \renewcommand*\TI{%
16     \LetLtxMacro\symbol\LWR@typicon@symbol%
17 }
18
19 \renewcommand*\ticon[1]%
20 {%
21     \begin{lateximage}*[#1 icon][typicon#1]%
22     \TI\csname ticon@\#1\endcsname%
23     \end{lateximage}%
24 }
```

---

**File 429 l warp-ulem.sty**

§ 529      Package **ulem**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg ulem Patched for use by l warp.

for HTML output: Use the original package:

```
1 \LWR@ProvidesPackagePass{ulem}[2012/05/18]
```

Basic markup commands, using css:

```
2 \NewDocumentCommand{\LWR@HTML@uline}{+m}{%
3     \InlineClass%
4         (text-decoration:underline; text-decoration-skip: auto)%
5         {uline}{\LWR@isolate{#1}}%
6 }
7 \LWR@formatted{uline}
8
9 \NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
10     \InlineClass%
11         (%
12             text-decoration:underline; text-decoration-skip: auto;%
13             text-decoration-style:double%
14         )%
15         {uuline}{\LWR@isolate{#1}}%
16 }
17 \LWR@formatted{uuline}
18
19 \NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
20     \InlineClass%
21         (%
22             text-decoration:underline; text-decoration-skip: auto;%
23             text-decoration-style:wavy%
24         )%
25         {uwave}{\LWR@isolate{#1}}%
26 }
```

```

27 \LWR@formatted{uwave}
28
29 \NewDocumentCommand{\LWR@HTML@sout}{+m}{%
30     \InlineClass{%
31         (text-decoration:line-through)%
32         {sout}{\LWR@isolate{#1}}%
33     }
34 \LWR@formatted{sout}
35
36 \NewDocumentCommand{\LWR@HTML@xout}{+m}{%
37     \InlineClass{%
38         (text-decoration:line-through)%
39         {xout}{\LWR@isolate{#1}}%
40     }
41
42 \NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
43     \InlineClass{%
44         (%
45             text-decoration:underline;%
46             text-decoration-skip: auto;%
47             text-decoration-style:dashed%
48         )%
49         {dashuline}{\LWR@isolate{#1}}%
50     }
51 \LWR@formatted{xout}
52
53 \NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
54     \InlineClass{%
55         (%
56             text-decoration:underline;%
57             text-decoration-skip: auto;%
58             text-decoration-style: dotted%
59         )%
60         {dotuline}{\LWR@isolate{#1}}%
61     }
62 \LWR@formatted{dotuline}

```

Nullified/emulated macros:

```

63 \NewDocumentCommand{\LWR@HTML@markoverwith}{m}{}
64 \LWR@formatted{markoverwith}
65
66 \NewDocumentCommand{\LWR@HTML@ULon}{+m}{\uline{#1}\egroup}
67 \LWR@formatted{ULon}

```

### File 430 **lwarp-umoline.sty**

#### § 530 Package **umoline**

*(Emulates or patches code by HIROSHI NAKASHIMA.)*

Pkg umoline umoline is patched for use by lwarp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{umoline}[2000/07/11]

2 \newcommand*{\LWR@HTML@Underline}[1]{%
3     \InlineClass{uline}{#1}%
4 }
5 \LWR@formatted{Underline}
6
7 \newcommand*{\LWR@HTML@Midline}[1]{%
8     \InlineClass{sout}{#1}%
9 }
10 \LWR@formatted{Midline}
11
12 \newcommand*{\LWR@HTML@Overline}[1]{%
13     \InlineClass{oline}{#1}%
14 }
15 \LWR@formatted{Overline}
16
17 \newcommand*{\LWR@HTML@UMOline}[2]{%
18     \InlineClass{uline}{#2}%
19 }
20 \LWR@formatted{UMOline}
21
22 \NewDocumentCommand{\LWR@HTML@UMOspace}{s m o}{\hspace*{#2}}
23 \LWR@formatted{UMOspace}
24
25 \NewDocumentCommand{\LWR@HTML@UMOneline}{s}{\newline}
26 \LWR@formatted{UMOneline}
```

---

File 431 **l warp-underscore.sty**

§ 531      Package **underscore**

Pkg    underscore    underscore is ignored.

**for HTML output:**    1 \LWR@ProvidesPackageDrop{underscore}[2006/09/13]

---

File 432 **l warp-unicode-math.sty**

§ 532      Package **unicode-math**

(Emulates or patches code by WILL ROBERTSON.)

Pkg    unicode-math    **unicode-math** is supported as-is for HTML with `svgmath`. For `MATHJAX`, many characters do not seem to be encoded correctly, and so are not read correctly by `pdftotext` for HTML. Symbol font commands are emulated, but not all combinations are supported by `MathJax`.

**for HTML output:**    1 \LWR@ProvidesPackagePass{unicode-math}[2019/09/26]

```
2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{unicode-math}
4
5 % Not all are possible in MathJax.
6 \CustomizeMathJax{\let\symnormal\mathit}
7 \CustomizeMathJax{\let\symliteral\mathrm}
8 \CustomizeMathJax{\let\symbb\mathbb}
9 \CustomizeMathJax{\let\sympbit\mathbb}% not italic
10 \CustomizeMathJax{\let\symcal\mathcal}
11 \CustomizeMathJax{\let\symscr\mathscr}
12 \CustomizeMathJax{\let\symfrak\mathfrak}
13 \CustomizeMathJax{\let\symsfup\mathsf}
14
15 % \CustomizeMathJax{\let\symsfit\mathit}% not sans
16 \CustomizeMathJax{\newcommand{\symsfit}[1]{%
17     \mmlToken{mi}[mathvariant="sans-serif-italic"]{#1}}%
18 }
19
20 % \CustomizeMathJax{\let\symbfsf\mathbf}% not sans
21 \CustomizeMathJax{\newcommand{\symbfsf}[1]{%
22     \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}}%
23 }
24
25 \CustomizeMathJax{\let\symbfup\mathbf}
26 \CustomizeMathJax{\newcommand{\symbfit}[1]{\boldsymbol{#1}}}
27 \CustomizeMathJax{\let\symbfcal\mathcal}% not bold
28
29 \CustomizeMathJax{\let\symbfscr\mathscr}% not bold
30 % \CustomizeMathJax{\newcommand{\symbfscr}[1]{%
31 %     \mmlToken{mi}[mathvariant="math-bold-script"]{#1}}%
32 % }
33
34 \CustomizeMathJax{\let\symbffrak\mathfrak}% not bold
35 % \CustomizeMathJax{\newcommand{\symbffrak}[1]{%
36 %     \mmlToken{mi}[mathvariant="math-bold-fraktur"]{#1}}%
37 % }
38
39 % \CustomizeMathJax{\let\symsfsup\mathbf}% not sans
40 \CustomizeMathJax{\newcommand{\symsfsup}[1]{%
41     \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}}%
42 }
43
44 % \CustomizeMathJax{\let\symsfit\mathit}% not bold nor sans
45 \CustomizeMathJax{\newcommand{\symsfit}[1]{%
46     \mmlToken{mi}[mathvariant="sans-serif-bold-italic"]{#1}}%
47 }
48
49 % Duplicates below are commented out.
50 \CustomizeMathJax{\let\sympup\mathrm}
51 \CustomizeMathJax{\let\symbf\mathbf}% \symbfup defined above
52 \CustomizeMathJax{\let\symit\mathit}
53 % \CustomizeMathJax{\let\sympfit\mathit}% not bold
54 \CustomizeMathJax{\let\symsf\mathsf}
55 % \CustomizeMathJax{\let\symsfsup\mathbf}% not sans
56 % \CustomizeMathJax{\let\symsfit\mathit}% not sans
```

---

```

57 % \CustomizeMathJax{\let\symbolfsfit\mathit}{not bold nor sans}
58 \CustomizeMathJax{\let\symboltt\mathtt}
59 % \CustomizeMathJax{\let\symbolbb\mathbb}
60 % \CustomizeMathJax{\let\symbolbit\mathbb}{not italic}
61 % \CustomizeMathJax{\let\symbolscr\mathscr}
62 % \CustomizeMathJax{\let\symbolfscr\mathscr}{not bold}
63 % \CustomizeMathJax{\let\symbolfrak\mathfrak}
64 \CustomizeMathJax{\let\symbolffrac\mathbf{frac}}
65 \end{warpMathJax}
```

---

File 433 **l warp-units.sty**

§ 533 Package **units**

*(Emulates or patches code by AXEL REICHERT.)*

Pkg **units** **units** is patched for use by **l warp**.

Values are not styled by css, and take the style of the surrounding HTML text.

Units are styled according to the print version, so they will be forced to upright roman in **HTML** if the print version does so. It may be necessary to adjust the document's body css to match the print version.

for **HTML output**:

```

1 \LWR@ProvidesPackagePass{units}[1998/08/04]

2 \DeclareRobustCommand*{\LWR@HTML@unit}[2][]{%
3 \ifblank{#1}{%
4   {\LWR@textcurrentfont{#2}}{%
5   {%
6     #1{%
7       \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,,}%
8       \LWR@textcurrentfont{#2}}{%
9     }{%
10   }{%
11 \LWR@formatted{unit}

12 \DeclareRobustCommand*{\LWR@HTML@unitfrac}[3][]{%
13 \ifblank{#1}{%
14   {%
15     \nicefrac{#2}{#3}}{%
16   }{%
17   {%
18     #1{%
19       \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,,}%
20       \nicefrac{#2}{#3}}{%
21     }{%
22   }{%
23 \LWR@formatted{unitfrac}}
```

For Mathjax:

```
25 \begin{warpMathJax}
26 \CustomizeMathJax{\newcommand{\unit}[2][]{\#1 \#2}}
27 \CustomizeMathJax{\newcommand{\unitfrac}[3][]{\#1 \#2/\#3}}
28 \end{warpMathJax}
```

---

**File 434 l warp-unitsdef.sty****§ 534 Package unitsdef**

(Emulates or patches code by PATRICK HAPPEL.)

Pkg unitsdef unitsdef is patched for use by l warp.

for HTML output: 1 \LWR@ProvidesPackagePass{unitsdef}[2005/01/04]

```
2 \renewcommand{\unitvaluesep}{\,}
3
4 \renewcommand{\unittimes}{\@setunitsepfalse\HTMLUnicode{22c5}\cdot
5
6 \renewunit{\arcmin}{%
7   \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}{%
8     \ensuremath{{}^{\prime}}%
9     \HTMLUnicode{2032}\prime
10 }%
11
12 \renewunit{\arcsec}{%
13   \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}{%
14     \ensuremath{{}^{\prime\prime}}%
15     \HTMLUnicode{2033}\prime\prime
16 }%
17
18 \renewrobustcmd{\SI}[2]{%
19   \begingroup%
20     \let\unit@xspace\relax%
21     \unitSId\selectfont%
22     \LWR@textcurrentfont{\#1\#2}\l warp
23   \endgroup%
24 }
```

---

**File 435 l warp-upref.sty****§ 535 Package upref**

Pkg upref upref is ignored.

for HTML output: Discard all options for l warp-upref:

```
1 \LWR@ProvidesPackageDrop{upref}[2007/03/14]
```

---

**File 436 lwarp-url.sty**

§ 536 Package **url**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg url url is patched for use by lwarp.

**for HTML output:**

```
1 \LetLtxMacro{\LWR@url@orig}{\url}
2
3 \LWR@ProvidesPackagePass{url}[2013/09/16]

4 \renewcommand*{\Url@FormatString}{%
5   \expandafter\LWR@url@orig\url\expandafter{\Url@String}%
6 }
```

---

**File 437 lwarp-uspace.sty**

§ 537 Package **uspace**

Pkg uspace uspace is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{uspace}[2016/11/06]
```

---

**File 438 lwarp-verse.sty**

§ 538 Package **verse**

*(Emulates or patches code by PETER WILSON.)*

Pkg verse verse is supported and patched by lwarp.

**for HTML output:** Pass all options for lwarp-verse:

```
1 \LWR@ProvidesPackagePass{verse}[2009/09/04]
```

When using **verse** or **memoir**, always place a **\** after each line.

**\attrib** The documentation for the **verse** and **memoir** packages suggest defining an **\attrib** command, which may already exist in current documents, but it will only work for print output. **lwarp** provides **\attribution**, which works for both print and **HTML** output. To combine the two so that **\attrib** is used for print and **\attribution** is used for **HTML**:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

---

```
Len  \vleftskip These lengths are used by verse and memoir to control the left margin, and they
Len  \vleftmargini may already be set by the user for print output. New lengths \HTMLvleftskip and
Len  \HTMLvleftskip \HTMLleftmargini are provided to control the margins in HTML output. These new
Len  \HTMLleftmargini lengths may be set by the user before any verse environment, and persist until they
are manually changed again. One reason to change \HTMLleftmargini is if there is
a wide \flagverse in use, such as the word “Chorus”, in which case the value of
\HTMLleftmargini should be set to a wide enough length to contain “Chorus”. The
default is wide enough for a stanza number.
```

**⚠ spacing**

Horizontal spacing relies on **pdftotext**’s ability to discern the layout (-layout option) of the text in the **HTML**-tagged PDF output. For some settings of **\HTMLleftmargini** or **\HTMLvleftskip** the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

**Env verse** The **verse** environment will be placed inside a **HTML <pre>**.

```
2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching verse.}
```

At the beginning of the **verse** environment:

```
4 \AtBeginEnvironment{verse}
5 {%
```

Use the original **list** environment inside a **<pre>** to attempt to preserve formatting.

```
6 \LWR@restoreoriglists%
```

```
Pkg  verse The verse or memoir packages can place stanza numbers to the left with their
Cls  memoir \flagverse command. Do not allow them to go into the left margin, which would
\flagverse cause pdfcrop to crop the entire page further to the left:
Len  \vleftskip
    7 \ifdef{\vleftskip}{%
        8 \setlength{\vleftskip}{\HTMLvleftskip}
        9 \setlength{\leftmargini}{\HTMLleftmargini}
    10 }{%
        11 \LWR@forcenewpage
        12 \LWR@atbeginverbatim{3}{verse}%
    13 }
```

After the end of the **verse** environment, which places the **<pre>** tag at the regular left margin:

```
14 \AtEndEnvironment{verse}{%
15 \leavevmode%
16 \LWR@afterendverbatim{1}%
17 }
```

Patch to place **poemtitle** inside an **HTML <span>** of class **poemtitle**:

```
18 \ifdef{\poemtitle}{
```

```
19 \DeclareDocumentCommand{\@vstypepoemtitle}{m}{%
20   \vspace{\beforepoemtitleskip}%
21   {\InlineClass{poemtitle}{\poemtitlefont #1}\par}%
22   \vspace{\afterpoemtitleskip}%
23 }
24 }{}%
25
26 \LWR@traceinfo{Finished patching verse.}%
27 }% AfterEndPreamble
```

---

File 439 **l warp-*versonotes*.sty**

§ 539 Package **versonotes**

(Emulates or patches code by NORMAN GRAY.)

Pkg *versonotes* **versonotes** is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{versonotes}[2019/07/06]

```
2 \newcommand{\versonote}[1]{\marginpar{#1}}%
3 \newdimen\versotextwidth
4 \newdimen\versoleftmargin
5 \newcommand*{\versolayout}{}%
```

In case the user changed the page number before loading **versonotes**:

```
6 \setcounter{page}{1}
```

---

File 440 **l warp-*vertbars*.sty**

§ 540 Package **vertbars**

(Emulates or patches code by PETER WILSON.)

Pkg *vertbars* **vertbars** is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{vertbars}[2010/11/27]

```
2 \newlength{\barwidth}
3 \setlength{\barwidth}{0.4pt}
4 \newlength{\barspace}
5 \setlength{\barspace}{1em}
6
7 \newenvironment{vertbar}%
8   \LWR@forcenewpage
9   \LWR@forceminwidth{\barwidth}
10  \begin{BlockClass}[%
11    border-left: \LWR@printlength{\LWR@atleastonept} solid black ; %
```

---

```

12     padding-left: \LWR@printlength{\barspace}%
13     ]{vertbar}
14 }{
15     \end{BlockClass}
16 }

```

---

File 441 **l warp-vmargin.sty**

§ 541 Package **vmargin**

Pkg vmargin vmargin is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{vmargin}[2004/07/15]

```

2 \newcommand*{\LWRVM@customsize}[2]{}
3 \newcommand*{\setpapersize}[2][]{{\ifstrequal{#2}{custom}{\LWRVM@customsize}{}}
4 \newcommand*{\setmargins}[8]{}
5 \newcommand*{\setmarginsrb}[8]{}
6 \newcommand*{\setmargnohf}[4]{}
7 \newcommand*{\setmargnofrb}[4]{}
8 \newcommand*{\setmarg}[4]{}
9 \newcommand*{\setmargrb}[4]{}
10 \newlength{\PaperWidth}
11 \setlength{\PaperWidth}{8.5in}
12 \newlength{\PaperHeight}
13 \setlength{\PaperHeight}{11in}
14 \newif\ifLandscape

```

---

File 442 **l warp-vowel.sty**

§ 542 Package **vowel**

(Emulates or patches code by FUKUI REI.)

Pkg vowel vowel is patched for use by l warp.

This package has been tested with *pdflatex* and the Type 1 TIPA fonts using the following package load sequence:

```

\usepackage[T3,T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[noenc]{tipa}
\usepackage{vowel}

```

**for HTML output:** 1 \LWR@ProvidesPackagePass{vowel}[2002/08/08]

```

2 \renewenvironment{vowel}[1][]{%
3     \begin{ lateximage }[-vowel-\sim\PackageDiagramAltText]%

```

```
5      \@vowel[#1]%
6  }
7 {%
8      \@@vowel%
9      \end{lateximage}%
10 }
```

---

**File 443 l warp-vpe.sty****§ 543 Package vpe**

Pkg vpe vpe is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{vpe}[2012/04/18]

---

**File 444 l warp-vwcol.sty****§ 544 Package VWCOL**

(Emulates or patches code by WILL ROBERTSON.)

Pkg vwcol vwcol is patched for use with l warp.

The width option is ignored. All vwcol environments adjust to 1–3 equal-width columns, depending on the width of the browser window.

The remaining options are supported, except for lines and maxrecursion.

for HTML output: 1 \LWR@ProvidesPackagePass{vwcol}[2015/02/10]

Factored from \vwcol. Each is given a style tag to append to the final style.

```
\LWR@vwcol@addrule {<style tag>}
2 \newcommand*{\LWR@vwcol@addrule}[1]{%
3     \appto{\LWR@vwcolstyle}{%
4         #1: %
5         \LWR@printlength{\vwcol@rule} solid \LWR@origpound\LWR@vwcol@rulecolor ; %
6     }%
7 }
```

```
\LWR@vwcol@addrule {<style tag>}
8 \newcommand*{\LWR@vwcol@addgap}[1]{%
9     \appto{\LWR@vwcolstyle}{%
10        #1: %
11        \LWR@printlength{\vwcol@sep} ; %
12    }%
13 }
```

---

Env vwcol {*key/values*}

Redefine the environment to add a HTML style. The style is built depending on the required options.

14 \renewenvironment\*{vwcol}[1][]{%

New paragraph, and process the options:

15 \LWR@stoppars%

16 \vwcolsetup{\#1}%

Begin with no style:

17 \newcommand\*{\LWR@vwcolstyle}{}{}

presep and postsep are created with HTML margins:

18 \if@vwcol@presep

19 \appto{\LWR@vwcolstyle}{margin-left: 1em ; padding-left: .5em ; }

20 \fi

21 \if@vwcol@postsep

22 \appto{\LWR@vwcolstyle}{margin-right: 1em ; padding-right: .5em ; }

23 \fi

sep becomes column-gap:

24 \ifdimgreater{\vwcol@sep}{1sp}{

25 \LWR@vwcol@addgap{column-gap}

26 \LWR@vwcol@addgap{-moz-column-gap}

27 \LWR@vwcol@addgap{-webkit-column-gap}

28 }{}}

rule become column-rule, while prerule and postrule become HTML borders:

29 \convertcolorspec[named]{\vwcol@rulecol}{HTML}\LWR@vwcol@rulecolor%

30 \ifdimgreater{\vwcol@rule}{0pt}{

31 \ifdimless{\vwcol@rule}{1pt}{

32 \setlength{\vwcol@rule}{1pt}

33 }{}

34 \LWR@vwcol@addrule{column-rule}

35 \LWR@vwcol@addrule{-moz-column-rule}

36 \LWR@vwcol@addrule{-webkit-column-rule}

37 \if@vwcol@prerule\LWR@vwcol@addrule{border-left}\fi

38 \if@vwcol@postrule\LWR@vwcol@addrule{border-right}\fi

39 }{}}

Each of the justify options becomes a text-align. Indentation is added where appropriate.

40 \ifdefequal{\vwcol@justify}{\RaggedRight}{

41 \appto{\LWR@vwcolstyle}{text-align: left ; }

42 \ifdimgreater{\vwcol@parindent}{0pt}{

43 \appto{\LWR@vwcolstyle}{%

44 text-indent: \LWR@printlength{\vwcol@parindent} ; %

45 }

46 }{}

47 }{}}

48 \ifdefequal{\vwcol@justify}{\RaggedLeft}{

```

49      \appto{\LWR@vwcolstyle}{text-align: right ; }
50 }{ }

51 \ifdefequal{\vwcol@justify}{\Centering}{%
52     \appto{\LWR@vwcolstyle}{text-align: center ; }
53 }{ }

54 \ifdefequal{\vwcol@justify}{\justifying}{%
55     \appto{\LWR@vwcolstyle}{text-align: justify ; }
56     \ifdimgreater{\vwcol@parindent}{0pt}{%
57         \appto{\LWR@vwcolstyle}{%
58             text-indent: \LWR@printlength{\vwcol@parindent} ; %
59         }
60     }{%
61 }{ }
61 }{ }

```

Create the <div> with the assembled style:

```

62 \BlockClass[\LWR@vwcolstyle]{multicols}
63 }

```

When the environment ends:

```

64 {
65 \endBlockClass
66 \LWR@startpars
67 }

```

#### File 445 **lwarf-wallpaper.sty**

§ 545 Package **wallpaper**

*(Emulates or patches code by MICHAEL H.F. WILKINSON.)*

Pkg wallpaper **wallpaper** is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{wallpaper}[2005/01/18]

```

2 \newcommand*\{CenterWallPaper}[2]{}
3 \newcommand*\{ThisCenterWallPaper}[2]{}
4 \newcommand*\{TileWallPaper}[3]{}
5 \newcommand*\{ThisTileWallPaper}[3]{}
6 \newcommand*\{TileSquareWallPaper}[2]{}
7 \newcommand*\{ThisTileSquareWallPaper}[2]{}
8 \newcommand*\{ULCornerWallPaper}[2]{}
9 \newcommand*\{ThisULCornerWallPaper}[2]{}
10 \newcommand*\{LLCornerWallPaper}[2]{}
11 \newcommand*\{ThisLLCornerWallPaper}[2]{}
12 \newcommand*\{URCornerWallPaper}[2]{}
13 \newcommand*\{ThisURCornerWallPaper}[2]{}
14 \newcommand*\{LRCornerWallPaper}[2]{}
15 \newcommand*\{ThisLRCornerWallPaper}[2]{}
16 \newcommand*\{ClearWallPaper}{}{}
17 \newlength{\wpXoffset}
18 \newlength{\wpYoffset}

```

---

**File 446 l warp-watermark.sty****§ 546 Package watermark**

*(Emulates or patches code by ALEXANDER I. ROZHENKO.)*

Pkg watermark watermark is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{watermark}[2004/12/09]

```
2 \newcommand{\watermark}[1]{}
3 \newcommand{\leftwatermark}[1]{}
4 \newcommand{\rightwatermark}[1]{}
5 \newcommand{\thiswatermark}[1]{}
6 \newcommand{\thispageheading}[1]{}
```

---

**File 447 l warp-widetable.sty****§ 547 Package widetable**

*(Emulates or patches code by CLAUDIO BECCARI.)*

Pkg widetable widetable is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{widetable}[2019-06-25]

```
2 \newenvironment{widetable}{\begin{tabular*}}{\end{tabular*}}
```

---

**File 448 l warp-widows-and-orphans.sty****§ 548 Package widows-and-orphans**

Pkg widows-and-orphans widows-and-orphans is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{widows-and-orphans}[2018/09/01]

```
2 \NewDocumentCommand{\Wa0setup}{m}{}
3 \NewDocumentCommand{\Wa0parameters}{}
4 \NewDocumentCommand{\Wa0ignorenext}{}{}
```

---

**File 449 l warp-witharrows.sty****§ 549 Package witharrows**

*(Emulates or patches code by F. PANTIGNY.)*

Pkg witharrows witharrows is patched for use by l warp. Emulation is provided for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{witharrows}[2019/12/27]

```
2 \begin{warpHTML}
3 \makeatletter
4 \ifbool{mathjax}{
5     % For the hidden print version in the HTML:
6     \newcommand{\Arrow}[2][]{}
7     \newcommand{\unicode}[1]{}
8     \NewDocumentEnvironment { DispWithArrows } { ! d < > ! O { } +b }
9     {
10         \IfValueTF{#1}{
11             \begin{displaymath}
12                 #1 \left\lVert
13                 \begin{aligned}
14                     #3
15                     \end{aligned}
16                     \right.
17                     \end{displaymath}
18     }{
19         \begin{displaymath}
20             \begin{aligned}
21                 #3
22                 \end{aligned}
23             \end{displaymath}
24     }
25 }
26 {}
27 \NewDocumentEnvironment { DispWithArrows* } { ! d < > ! O { } +b }
28 {
29     \IfValueTF{#1}{
30         \begin{displaymath}
31             #1 \left\lVert
32             \begin{aligned}
33                 #3
34                 \end{aligned}
35             \right.
36             \end{displaymath}
37     }{
38         \begin{displaymath}
39             \begin{aligned}
40                 #3
41                 \end{aligned}
42             \end{displaymath}
43     }
44 }
45 {}
46 }{
47     % If not MathJax, use SVG images.
48     \BeforeBeginEnvironment{WithArrows}{\global\booltrue{\LWR@unknownmathsize}}
49     \BeforeBeginEnvironment{DispWithArrows}{%
50         \begin{BlockClass}{displaymathnumbered}%
51         \begin{ lateximage }%
52     }
```

```
53     \AfterEndEnvironment{DispWithArrows}{\end{lateximage}\end{BlockClass}}
54     \BeforeBeginEnvironment{DispWithArrows*}{%
55         \begin{BlockClass}{displaymath}%
56         \begin{lateximage}%
57     }%
58     \AfterEndEnvironment{DispWithArrows*}{\end{lateximage}\end{BlockClass}}%
59 }
60 \makeatother
61 \end{warpHTML}
62
63 \begin{warpMathJax}
64 \CustomizeMathJax{\newenvironment{WithArrows}[1][]{\begin{aligned}}{\end{aligned}}}
65 % Unable to make a sized box.
66 \CustomizeMathJax{\newcommand{\Arrow}[2][]{\&{\Large\unicode{x2938}}\textit{#2}}}
67 \end{warpMathJax}
```

---

**File 450 l warp-wrapfig.sty****§ 550 Package wrapfig**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg wrapfig wrapfig is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{wrapfig}[2003/01/31]

2 \newcommand*{\LWR@wrapposition}{}%
3
4 \newcommand*{\LWR@subwrapfigure}[2]{%
5 \renewcommand*{\LWR@wrapposition}{}%
6 \ifthenelse{%
7     \equal{#1}{r}\OR\equal{#1}{R}\OR%
8     \equal{#1}{o}\OR\equal{#1}{O}%
9 }{%
10     {\renewcommand*{\LWR@wrapposition}{float:right}}%
11     {\renewcommand*{\LWR@wrapposition}{float:left}}%
12 \setlength{\LWR@templengthone}{#2}%
13 \LWR@BlockClassWP{%
14     width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
15     margin:10pt%
16 }%
17 {%
18     width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
19 }%
20 {marginblock}%

21 \setlength{\ linewidth}{\LWR@templengthone}%
22 }
23
24
25 \NewDocumentEnvironment{wrapfigure}{o m o m}%
26 {%
```

```
27 \begin{LWR@setvirtualpage} *%
28 \LWR@subwrapfigure{#2}{#4}%
29 \captionsetup{type=figure}%
30 }
31 {%
32 \endLWR@BlockClassWP%
33 \end{LWR@setvirtualpage}%
34 }
35
36
37 \NewDocumentEnvironment{wraptable}{o m o m}
38 {%
39 \begin{LWR@setvirtualpage} *%
40 \LWR@subwrapfigure{#2}{#4}%
41 \captionsetup{type=table}%
42 }
43 {%
44 \endLWR@BlockClassWP%
45 \end{LWR@setvirtualpage}%
46 }
47
48
49 \NewDocumentEnvironment{wrapfloat}{m o m o m}
50 {%
51 \begin{LWR@setvirtualpage} *%
52 \LWR@subwrapfigure{#3}{#5}%
53 \captionsetup{type=#1}%
54 }
55 {%
56 \endLWR@BlockClassWP%
57 \end{LWR@setvirtualpage}%
58 }
59
60 \newlength{\wrapoverhang}
```

---

File 451 **l warp-xbmks.sty**

§ 551      Package **xbmks**

Pkg    xbmks    xbmks is ignored.

for HTML output:    1 \LWR@ProvidesPackageDrop{xbmks}[2018/07/04]

```
2 \newcommand{\xbmksetup}[1]{}
3 \NewDocumentCommand{\pdfbookmarkx}{o m o m}{}
4 \NewDocumentCommand{\currentpdfbookmarkx}{m o m}{}
5 \NewDocumentCommand{\subpdfbookmarkx}{m o m}{}
6 \NewDocumentCommand{\belowpdfbookmarkx}{m o m}{}
```

---

**File 452 l warp-xcolor.sty****§ 552 Package xcolor**

(Emulates or patches code by DR. UWE KERN.)

Pkg xcolor xcolor is supported by l warp.

**§ 552.1 Limitations**

**\colorboxBlock and \fcolorboxBlock** \colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a <div> instead of a <span>. These <div>s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by l warp's core if xcolor is loaded.

**background: none** \fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

**color support** Color definitions, models, and mixing are fully supported without any changes required.

**colored tables** \rowcolors is supported, except that the optional argument is ignored so far.

**colored text and boxes** \textcolor, \colorbox, and \fcolorbox are supported.

**\color and \pagecolor** \color and \pagecolor are ignored. Use css or \textcolor where possible.

**§ 552.2 xcolor definitions: location and timing**

The l warp core and its l warp-xcolor package are tightly integrated to allow comparable results for print, HTML, and print inside an HTML lateximage. This requires a number of definitions and redefinitions depending on whether each of xcolor and lateximage is being used, and whether print or HTML is being generated. Some of these actions are one-time when xcolor is loaded, and others are temporary as lateximage is used.

**When xcolor is loaded in print mode:** No special actions are taken at the time that xcolor is loaded in print mode, but see \AtBeginDocument below.

**When l warp-xcolor is loaded in HTML mode:** xcolor's original definitions are saved for later restoration. \LWR@restoreorigformatting is appended to restore these definitions for use inside a lateximage. New HTML-mode definitions are created for \textcolor, \pagecolor, \nopagecolor, \colorbox, \colorboxBlock, \fcolorbox, \fcolorboxBlock, and fcolorminipage.

**\AtBeginDocument in print or HTML mode:** See Section 85. If xcolor has been loaded, the print-mode \fcolorbox is modified to accept a background color of none,

and additional definitions are created for lwarp's new macros print-mode macros \colorboxBlock, \fcolorboxBlock, and \fcolorminipage. The HTML versions of these macros will already have been created by lwarp-xcolor if it has been loaded.

For use inside an HTML \textrm{ lateximage}, \LWR@restoreorigformatting is appended to temporarily set these functions to their print-mode versions.

**In a \textrm{ lateximage} in HTML mode:** \LWR@restoreorigformatting temporarily restores the print-mode definitions of xcolor's functions. See \LWR@restoreorigformatting on page 508.

#### \color:

**Print:** Used as-is.

**HTML:** Ignored by *pdftotext*, and will not appear.

**HTML \textrm{ lateximage}: Colors will appear in a \textrm{ lateximage}.**

#### \textcolor:

**Print:** Used as-is.

**HTML:** Redefined by lwarp-xcolor, page 1057.

**HTML \textrm{ lateximage}: Remembers and reuses the print version.**

#### \pagecolor:

**Print:** Used as-is.

**HTML:** Ignored.

**HTML \textrm{ lateximage}: Colors will be picked up in a \textrm{ lateximage}.**

#### \nopagecolor:

**Print:** Used as-is.

**HTML:** Ignored.

**HTML \textrm{ lateximage}: Colors will be picked up in a \textrm{ lateximage}.**

#### \colorbox:

**Print:** Used as-is.

**HTML:** Redefined by lwarp-xcolor, page 1058.

**HTML \textrm{ lateximage}: Remembers and reuses the print version.**

#### \colorboxBlock:

**Print:** Becomes \colorbox.

**HTML:** Newly defined by lwarp-xcolor to use a <div>, page 1058.

**HTML \textrm{ lateximage}: Remembers and reuses the print version \colorbox.**

#### \fcolorbox:

**Print:** Modified to allow a background of none.

\LWR@print@fcolorbox at section 85

**HTML:** Redefined by lwarp-xcolor, page 1059.

**HTML `\textrimage`:** Remembers and reuses the print version.

**\fcolorboxBlock:**

**Print:** Becomes \fcolorbox. Section 85

**HTML:** Newly defined by l warp-xcolor to use a <div>, page 1059.

**HTML `\textrimage`:** Remembers and reuses the print version \fcolorbox.

**fcolorminipage:**

**Print:** Newly defined in the l warp core.

LWR@print@fcolorminipage at section 85

**HTML:** Newly defined by l warp-xcolor, page 1060.

**HTML `\textrimage`:** Uses the print version.

**\boxframe:**

**Print:** Used as-is.

**HTML:** Redefined by l warp-xcolor, page 1061.

**HTML `\textrimage`:** Remembers and reuses the print version.

### § 552.3 Package loading

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{xcolor}[2016/05/11]
2 \begin{warpHTML}
```

### § 552.4 Remembering and restoring original definitions

Remember the following print-mode actions to be restored when inside a `\textrimage` environment:

```
3 \LetLtxMacro{\LWR@print@pagecolor}{\pagecolor}
4 \LetLtxMacro{\LWR@print@nopagecolor}{\nopagecolor}
```

**\LWR@restoreorigformatting** Inside a `\textrimage` the following gets restored to their print-mode actions:

```
5 \appto{\LWR@restoreorigformatting}{%
6 \LetLtxMacro{\pagecolor}{\LWR@print@pagecolor}%
7 \LetLtxMacro{\nopagecolor}{\LWR@print@nopagecolor}%
8 }
```

## § 552.5 \normalcolor

```
\normalcolor
9 \DeclareRobustCommand{\LWR@HTML@normalcolor}{\color{black}}%
10
11 \LWR@formatted{normalcolor}
```

## § 552.6 HTML color style

\LWR@findcurrenttextcolor Sets \LWR@tempcolor to the current color.

```
12 \renewcommand*\LWR@findcurrenttextcolor{%
13 \protect\colorlet{\LWR@current@color}{.}%
14 \protect\convertcolorspec[named]{\LWR@current@color}{HTML}\LWR@tempcolor%
15 }
```

\LWR@currenttextcolorstyle Prints a color style for the current color.

```
16 \newcommand*\LWR@currenttextcolorstyle{%
17 \LWR@findcurrenttextcolor%
18 \ifdefstring{\LWR@tempcolor}{000000}%
19 {}%
20 {color: \LWR@origpound\LWR@tempcolor ; }%
21 }
```

\LWR@textcurrentcolor {\langle text\rangle} Like \textcolor but uses the current \color instead.

```
22 \DeclareDocumentCommand{\LWR@textcurrentcolor}{m}{%
23 \begingroup%
24 \LWR@FBcancel%
25 \LWR@findcurrenttextcolor%
26 \InlineClass[color:\LWR@origpound\LWR@tempcolor]{textcolor}{%
27     \renewcommand*\LWR@currenttextcolor{\LWR@origpound\LWR@tempcolor}%
28     #1%
29 }%
30 \endgroup%
31 }
```

\LWR@colorstyle {\langle 2: model\rangle} {\langle 3: color\rangle}

For a color style, prints the color converted to HTML colors.

```
32 \NewDocumentCommand{\LWR@colorstyle}{m m}{%
33 \begingroup%
34 \LWR@FBcancel%
```

Use the xcolor package to convert to an HTML color space:

```
35 \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```
36 \LWR@origpound\LWR@tempcolor%
37 \endgroup%
38 }
```

---

\LWR@backgroundcolor [*model*] {[*color*] {[*text*]}}

Similar to \textcolor, but prints black text against a color background.

Converted into an HTML hex color span.

```

39 \NewDocumentCommand{\LWR@backgroundcolor}{o m m}{%
40 \begingroup%
41 \LWR@FBcancel%
42 \InlineClass[background:\LWR@colorstyle{#1}{#2}]{backgroundcolor}{%
43 #3%
44 }%
45 \endgroup%
46 }
```

### § 552.7 HTML border

\LWR@borderpadding {[*colorstyle*] {[*color*]}} Prints the HTML attributes for a black border and padding.  
 \LWR@forceminwidth must be used first in order to set the border width.

```

47 \newcommand*{\LWR@borderpadding}[2]{%
48 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
49 padding:\LWR@printlength{\fboxsep}%
50 }
```

### § 552.8 High-level macros

\color [*model*] {[*color*]}

⚠ The current \color is used by HTML rules and frames, but does not affect the current HTML text output, due to the lack of HTML states and scoping limitations. Use \textcolor if possible.

```

51 \NewDocumentCommand{\LWR@HTML@color}{o m}{%
52 \IfValueTF{#1}{%
53   \LWR@print@color[#1]{#2}%
54   \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
55 }{%
56   \LWR@print@color{#2}%
57   \convertcolorspec{named}{#2}{HTML}\LWR@tempcolor%
58 }%
59 \edef\LWR@currenttextcolor{\LWR@origpound\LWR@tempcolor}%
60 }%
61
62 \LWR@formatted{color}
```

\textcolor [*model*] {[*color*] {[*text*]}}

Converted into an HTML hex color span.

```

63 \NewDocumentCommand{\LWR@HTML@textcolor}{o m m}{%
64 \begingroup%
65 \IfValueTF{#1}{%
```

```
66     \color[#1]{#2}%
67 }%
68     \color{#2}%
69 }
70 \InlineClass[color:\LWR@currenttextcolor]{textcolor}{#3}%
71 \endgroup%
72 }%
73
74 \LWR@formatted{textcolor}
```

\pagecolor [*model*] {*color*}

Ignored. Use css instead.

```
75 \renewcommand*\pagecolor[2][named]{}%
```

\nopagecolor Ignored.

```
76 \renewcommand*\nopagecolor{}%
```

\colorbox [*model*] {*color*} {*text*}

Converted into an HTML hex background color <span>.

```
77 \NewDocumentCommand{\LWR@HTML@colorbox}{O{named} m +m}{%
78 \begingroup%
79 \LWR@FBcancel%
80 \InlineClass[%
81 background:\LWR@colorstyle{#1}{#2} ; %
82 padding:\LWR@printlength{\fboxsep}%
83 ]{colorbox}{#3}%
84 \endgroup%
85 }
86
87 \AtBeginDocument{
88 \LWR@formatted{colorbox}
89 }
```

\colorboxBlock [*model*] {*color*} {*text*}

Converted into an HTML hex background color <div>.

```
90 \NewDocumentCommand{\LWR@HTML@colorboxBlock}{O{named} m +m}{%
91 \begingroup%
92 \LWR@FBcancel%
93 \LWR@stopars%
94 \begin{BlockClass}[%
95 background:\LWR@colorstyle{#1}{#2} ; %
```

```

96 padding:\LWR@printlength{\fboxsep}%
97 ]{colorboxBlock}
98 #3
99 \end{BlockClass}%
100 \endgroup%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

101 \global\booltrue{\LWR@minipagethispar}%
102 }
103
104 \AtBeginDocument{
105 \LWR@formatted{colorboxBlock}
106 }

```

\fcolorbox [⟨framemodel⟩] {⟨framecolor⟩} [⟨boxmodel⟩] {⟨boxcolor⟩} {⟨text⟩}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

107 \NewDocumentCommand{\LWR@HTML\fcolorbox}{O{named} m O{named} m +m}{%
108 \LWR@traceinfo{HTML fcolorbox #2 #4}%
109 \begingroup%
110 \LWR@FBcancel%
111 \LWR@forceminwidth{\fboxrule}%
112 \ifthenelse{\equal{#4}{none}}{%
113   {%
114     \InlineClass[%
115       \LWR@borderpadding{#1}{#2}%
116     ]{fcolorbox}{#5}%
117   }%
118   {%
119     \InlineClass[%
120       \LWR@borderpadding{#1}{#2} ; %
121       background:\LWR@colorstyle{#3}{#4}%
122     ]{fcolorbox}{#5}%
123   }%
124 \endgroup%
125 }%
126
127 \AtBeginDocument{%
128 \LWR@formatted{fcolorbox}%
129 }

```

\fcolorboxBlock [⟨framemodel⟩] {⟨framecolor⟩} [⟨boxmodel⟩] {⟨boxcolor⟩} {⟨text⟩}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

130 \NewDocumentCommand{\LWR@HTML@fcolorboxBlock}{O{named} m O{named} m +m}{%
131 \LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
132 \begingroup%
133 \LWR@FBcancel%
134 \LWR@forceminwidth{\fboxrule}%

135 \LWR@stopars%

136 \ifthenelse{\equal{#4}{none}}{%
137     {%
138         \begin{BlockClass}[%%
139             \LWR@borderpadding{#1}{#2}%
140             ]{fcolorboxBlock}%
141             #5%
142         \end{BlockClass}%
143     }%
144     {%
145         \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
146         \begin{BlockClass}[%%
147             background:\LWR@origpound\LWR@tempcolortwo\ ; %
148             \LWR@borderpadding{#1}{#2}%
149             ]{fcolorboxBlock}%
150             #5%
151         \end{BlockClass}%
152     }%
153 \endgroup%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

154 \global\booltrue{\LWR@minipagethispar}%
155 \LWR@traceinfo{HTML fcolorboxBlock done}%
156 }%
157
158 \AtBeginDocument{%
159 \LWR@formatted{fcolorboxBlock}%
160 }

```

Creates a framed HTML <div> around its contents.

A print-output version is defined in the **lwarp** core: section 85

```

\LWR@subfcolorminipage {⟨framemode⟩} {⟨framecolor⟩} {⟨background tag⟩} {⟨height⟩}%
161 \NewDocumentCommand{\LWR@subfcolorminipage}{m m m m}{%
162 \LWR@stopars%
163 \begin{BlockClass}[%%
164 #3%
165 \LWR@borderpadding{#1}{#2} ; %
166 \IfValueT{#4}{height:\LWR@printlength{\LWR@tempheight} ; }%
167 width:\LWR@printlength{\LWR@tempwidth}%
168 ]{fcolorminipage}%

```

---

169 }

```
Env  fcolorminipage  [<1:framemodel>]{<2:framecolor>} [<3:boxmodel>]{<4:boxcolor>} [<5:align>] [<6:height>]
     [<7:inner-align>] [<8:width>]

170 \NewDocumentEnvironment{LWR@HTML@fcolorminipage}{O{named} m O{named} m O{c} o o m}
171 {%
172 \LWR@FBcancel%
173 \setlength{\LWR@tempwidth}{#8}%
174 \IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
175 \LWR@forceminwidth{\fboxrule}%
176 \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
177 \ifthenelse{\equal{#4}{none}}{%
178   {\LWR@subfcolorminipage{#1}{#2}{}}{#6}}{%
179   {%
180     \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
181     \LWR@subfcolorminipage{#1}{#2}{%
182       {background:\LWR@origpound\LWR@tempcolortwo\ ; }%
183       {#6}}%
184   }%
185 }%
186 {%
187   \end{BlockClass}%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
188   \global\booltrue{LWR@minipagethispar}%
189 }
190
191 \AtBeginDocument{%
192 \LWR@formattedenv{fcolorminipage}%
193 }
```

\boxframe {<width>} {<height>} {<depth>}

The depth is added to the height, but the box is not descended below by the depth.  
\textcolor is honored.

```
194 \newcommand*{\LWR@HTML@boxframe}[3]{%
195 {%
196 \setlength{\LWR@tempwidth}{#1}%
197 \setlength{\LWR@tempheight}{#2}%
198 \addtolength{\LWR@tempheight}{#3}%
199 \LWR@forceminwidth{\fboxrule}%
200 \LWR@findcurrenttextcolor%
201 \InlineClass{%
202 display:inline-block ; %
203 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@currenttextcolor{} ; %
204 width:\LWR@printlength{\LWR@tempwidth} ; %
205 height:\LWR@printlength{\LWR@tempheight}%
206 }{boxframe}{}}
```

```
207 }%
208 }
209
210 \LWR@formatted{boxframe}
```

## § 552.9 Row colors

```
\rowc@l@rs  [\langle cmds\rangle] {\langle startrow\rangle} {\langle odd color\rangle} {\langle even color\rangle}
211 \newcommand*{\LWR@xcolortempcolor}{}
212
213 \def\rowc@l@rs[#1]#2#3#4%
214 {
215 \rownum=1%
216 \rowcolorstrue%
217 \ifxempty{#3}%
218 {\def\@oddrowcolor{\norowcolor}}%
219 {%
220 \convertcolorspec{named}{#3}{HTML}\LWR@xcolortempcolor%
221 \edef\@oddrowcolor{%
222 \csdef{\LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
223 }%
224 }%
225 \ifxempty{#4}%
226 {\def\@evenrowcolor{\norowcolor}}%
227 {%
228 \convertcolorspec{named}{#4}{HTML}\LWR@xcolortempcolor%
229 \edef\@evenrowcolor{%
230 \csdef{\LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
231 }%
232 }%
233 \if@rowcmd
234 \def\@rowcolors
235 {%
236 %      #1%
237 \if@rowcolors
238 %      \noalign{%
239 %          \relax\ifnum\rownum<#2\@norowcolor\else
240 %              \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi\fi%
241 %      }%
242 \fi%
243 }%
244 \else
245 \def\@rowcolors
246 {%
247 \if@rowcolors
248 \ifnum\rownum<#2%
249 %      \noalign{%
250 %          \norowcolor
251 %      }
252 \else
253 %      #1%
254 %      \noalign{%
255 %          \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi%
256 %      }%
257 \fi
```

```

258      \fi%
259    }%
260    \fi
261    \ignorespaces%
262 }

\@norowcolor    Turns off color for this row.

263 \def\@norowcolor{%
264 \renewcommand{\LWR@xcolorrowHTMLcolor}{}%
265 }

```

\@rowc@lors Executed at the end of each row.

```

266 \def\@rowc@lors{%
267 %   \noalign{%
268 %     \advance\rownum\@ne%
269 %   }%
270   \@rowcolors%
271 }

272 \end{warpHTML}

```

#### File 453 **lwarf-xexchangebar.sty**

§ 553 Package **xexchangebar**

Pkg xexchangebar xexchangebar is ignored

**for HTML output:** 1 \LWR@ProvidesPackageDrop{xexchangebar}[2017/08/03]  
2 \LWR@origRequirePackage{lwarf-changebar}

#### File 454 **lwarf-xellipsis.sty**

§ 554 Package **xellipsis**

(Emulates or patches code by DONALD P. GOODMAN III.)

Pkg xellipsis xellipsis is patched for use by lwarf.

When non-zero, each of the spaces is converted to an HTML thin unbreakable space.

**for HTML output:** 1 \LWR@ProvidesPackagePass{xellipsis}[2015/11/01]

```

2 \newcommand*{\LWR@xellipsespace}[1]{%
3 \ifdim#1=0pt\else%
4   \ifdim#1<\fontdimen2\font%
5     ,%
6   \else%

```

---

```

7      ~%
8      \fi%
9 \fi%
10 }
11
12 \def\xelip{%
13 \mbox{%
14   \LWR@xellipsespace{\xeliprebef}%
15   \xeliprechar%
16   \LWR@xellipsespace{\xelippref}%
17   \LWR@xellipsespace{\xelipbef}%
18   \xelipchar%
19   \xel@loopi = 1%
20   \loop\ifnum\xelipnum>\xel@loopi%
21     \advance\xel@loopi by1%
22     \LWR@xellipsespace{\xelipgap}%
23     \xelipchar%
24   \repeat%
25   \LWR@xellipsespace{\xelipaft}%
26   \LWR@xellipsespace{\xelippostbef}%
27   \xelippostchar%
28   \LWR@xellipsespace{\xelippostaf}%
29 }%
30 }%

```

---

#### File 455 **l warp-xetexko-vertical.sty**

##### § 555 Package **xetexko-vertical**

*(Emulates or patches code by DOHYUN KIM.)*

Pkg xetexko-vertical xetexko-vertical is patched for use by l warp.

```

for HTML output: 1 \LWR@loadbefore{xetexko-vertical}
2
3 \LWR@ProvidesPackagePass{xetexko-vertical}[2018/04/06]

4 \renewcommand{\verticalltypesetting}{}
5 \renewenvironment{vertical}[1]{\BlockClass{verticalrl}}{\endBlockClass}
6 \renewenvironment{horizontal}[1]{\BlockClass{horizontaltb}}{\endBlockClass}
7 \renewcommand{\vertlatin}[1]{#1}

```

---

#### File 456 **l warp-xfakebold.sty**

##### § 556 Package **xfakebold**

*(Emulates or patches code by HERBERT VOSS.)*

Pkg xfakebold xfakebold is patched for use by l warp, and additional underlying support is found in the l warp core.

⚠ **page breaks** Note that the print version resets to unbold at each page break, whereas the HTML version maintains the bold state until it is undone.

**for HTML output:** 1 \LWR@ProvidesPackagePass{xfakebold}[2018/07/25]

```

2 \let\LWR@orig@setBold\setBold
3 \let\LWR@orig@unsetBold\unsetBold
4 \renewcommand*{\setBold}{\booltrue{LWR@xfakebold}}
5 \renewcommand*{\unsetBold}{\boolfalse{LWR@xfakebold}}
6
7 \renewcommand*{\LWR@applyxfakebold}%
8   \ifbool{LWR@xfakebold}{\LWR@orig@setBold}{\LWR@orig@unsetBold}%
9 }
```

For MATHJAX, `xfakebold` is ignored.

```

10 \begin{warpMathJax}
11 \CustomizeMathJax{\newcommand{\setBold}[1][]{}}
12 \CustomizeMathJax{\newcommand{\unsetBold}{}}
13 \end{warpMathJax}
```

---

File 457 **l warp-xfrac.sty**

§ 557 Package **xfrac**

(Emulates or patches code by THE LATEX3 PROJECT.)

Pkg `xfrac` Supported by adding `xfrac` instances, and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{xfrac}[2018-08-23]

⚠ **font size** In the user's document preamble, `l warp` should be loaded after font-related setup. During HTML conversion, this font is used by `l warp` to generate its initial PDF output containing HTML tags, later to be converted by `pdftotext` to a plain text file. While the text may be in any font which `pdftotext` can read, the math is directly converted into SVG images using this same user-selected font. `xfrac` below is set for the Latin Modern (lmr) font. If another font is used, it may be desirable to redefine `\xfracHTMLfontsize` with a different em size.

`\sfrac` [`<instance>`] [`<num>`] [`<sep>`] [`<denom>`]

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in HTML tags. `\scalebox` is made null inside the numerator and denominator, since the HTML tags should not be scaled, and we do not want to introduce additional HTML tags for scaling.

In math mode, which will appear inside a `lateximage`, no adjustments are necessary.

**for HTML & PRINT:** 2 \begin{warpall}

`\xfracHTMLfontsize` User-redefinable macro which controls the font size of the fraction.

```

3 \newcommand{\xfracHTML}{\normalsize}
4 \end{warpall}

for HTML output: 5 \begin{warpHTML}
```

**instances** Instances of `xfrac` for various font choices:

Produce css for a small raised numerator and a small denominator.

Scaling is turned off so that `pdftotext` correctly reads the result.

```

6 \DeclareInstance{xfrac}{default}{text}{
7   numerator-format = {%
8     \begingroup%
9     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
10    \InlineClass{numerator}{#1},%
11    \endgroup%
12  },
13  denominator-format = {%
14    \begingroup%
15    \RenewDocumentCommand{\scalebox}{m o m}{##3}%
16    \InlineClass{denominator}{#1}%
17    \endgroup%
18  },
```

For `pdftotext`, do not scale the text:

```

19   scaling = false
20 }
21
22 \DeclareInstance{xfrac}{lmr}{text}{
23   numerator-format = {%
24     \begingroup%
25     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
26     \InlineClass{numerator}{#1},%
27     \endgroup%
28  },
29  denominator-format = {%
30    \begingroup%
31    \RenewDocumentCommand{\scalebox}{m o m}{##3}%
32    \InlineClass{denominator}{#1}%
33    \endgroup%
34  },
```

For `pdftotext`, do not scale the text:

```

35   scaling = false
36 }
37
38 \DeclareInstance{xfrac}{lmss}{text}{
39   numerator-format = {%
40     \begingroup%
41     \RenewDocumentCommand{\scalebox}{m o m}{##3}%
42   },
```

```

42      \InlineClass{numerator}{#1}\,%
43      \endgroup%
44 },
45 denominator-format = {%
46   \begingroup%
47   \RenewDocumentCommand{\scalebox}{m o m}##3{%
48     \InlineClass{denominator}{#1}%
49   \endgroup%
50 },

```

For *pdftotext*, do not scale the text:

```

51   scaling = false
52 }
53
54 \DeclareInstance{xfrac}{lmtt}{text}{
55   numerator-format = {%
56     \begingroup%
57     \RenewDocumentCommand{\scalebox}{m o m}##3{%
58       \InlineClass{numerator}{#1}\,%
59     \endgroup%
60 },
61   denominator-format = {%
62     \begingroup%
63     \RenewDocumentCommand{\scalebox}{m o m}##3{%
64       \InlineClass{denominator}{#1}%
65     \endgroup%
66 },

```

For *pdftotext*, do not scale the text:

```

67   scaling = false
68 }

```

For MATHJAX:

```

69 \begin{warpMathJax}
70 \CustomizeMathJax{\newcommand{\LWRsfrac}[2][]{\{}^{\LWRsfrac numerator\!#1\}_{\#2}}}
71 \CustomizeMathJax{\newcommand{\sfrac}[2][]{\def\LWRsfrac numerator{\#2}\LWRsfrac}}
72 \end{warpMathJax}

73 \end{warpHTML}

```

File 458 **lwarp-xltabular.sty**

## § 558 Package **xltabular**

(Emulates or patches code by ROLF NIEPRASCHK, HERBERT VOSS.)

Pkg xltabular xltabular is emulated by lwarp.

for HTML output Relies on tabularx.

**⚠ table numbering**

At present, an `xltabular` without a caption or with only a `\caption*` may be misnumbered in HTML, so it may be necessary to place at the end of the table:

```
\warpHTMLonly{\addtocounter{table}{-1}}
```

```
1 \RequirePackage{tabularx}
2 \RequirePackage{ltablex}
3
4 \LWR@ProvidesPackageDrop{xltabular}[2018/05/23]
5
6 \DeclareDocumentEnvironment{xltabular}{o m m}
7 {\longtable[#3]}
8 {\endlongtable}
```

---

**File 459 l warp-xltxttra.sty****§ 559 Package `xltxttra`**

(Emulates or patches code by WILL ROBERTSON, JONATHAN KEW.)

Pkg `xltxttra` `xltxttra` is emulated.

**for HTML output:** 1 `\LWR@ProvidesPackageDrop{xltxttra}[2016/01/21]`

```
2 \RequirePackage{realscripts}
3 \RequirePackage{metalogo}
4 \newcommand*\TeX@logo@spacing[6] {}
5
6 \newcommand*{\vfrac}[2]{%
7 \textsuperscript{#1}/\textsubscript{#2}%
8 }
9
10 \newcommand\namedglyph[1]{%
11   \tempcnta=\XeTeXglyphindex "#1"\relax
12   \ifnum\tempcnta>0
13     \XeTeXglyph\tempcnta
14   \else
15     \xxt@namedglyph@fallback{#1}%
16   \fi}
17
18 \newcommand\xxt@namedglyph@fallback[1]{[#1]}
19
20 \DeclareDocumentCommand{\showhyphens}{m}{}
```

---

**File 460 l warp-xmpincl.sty****§ 560 Package `xmpincl`**

(Emulates or patches code by MAARTEN SNEEP.)

Pkg xmpincl xmpincl is ignored.

**for HTML output:** Discard all options for l warp-xmpincl:

```
1 \LWR@ProvidesPackageDrop{xmpincl}[2008/05/10]
2 \newcommand*\includexmp[1]{}
```

---

### File 461 l warp-xpiano.sty

#### § 561 Package xpiano

(Emulates or patches code by ENRICO GREGORIO.)

Pkg xpiano xpiano is patched for use by l warp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{xpiano}
2 \ExplSyntaxOn
3 \NewDocumentCommand{\LWR@print@keyboard}{ O{}m }
4 {
5 \xpiano_keyboard:nn { #1 } { #2 }
6 }
7
8 \NewDocumentCommand{\LWR@HTML@keyboard}{ O{}m }
9 {
10 \begin{lateximage}*
11   [% -xpiano-\~\PackageDiagramAltText{}: \detokenize\expandafter{\#2}%
12   ]
13   [\detokenize\expandafter{\#1}]
14 \xpiano_keyboard:nn { #1 } { #2 }
15 \end{lateximage}
16 \ExplSyntaxOff
17 }
18 \LWR@formatted{keyboard}
```

---

### File 462 l warp-xpinyin.sty

#### § 562 Package xpinyin

(Emulates or patches code by SOBEN LEE.)

Pkg xpinyin xpinyin is partly supported. \xpinyin and pinyininscope are nullified, but \pinyin works.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{xpinyin}[2018/01/28]
```

```
2 \RenewDocumentEnvironment{pinyin}{O{}{}{}}
3
4 \RenewDocumentCommand{\xpinyin}{s O{} m}{%
5   \IfBooleanTF{#1}{#3}{\@firstoftwo#3}%
6 }
7
8 \RenewDocumentCommand{\enablepinyin}{}
```

---

**File 463 l warp-xr.sty****§ 563 Package *Xr***

(Emulates or patches code by JEAN-PIERRE DRUCBERT, DAVID CARLISLE.)

Pkg *xr* *xr* is patched for use by *l warp*. The *\*\_html.aux* file is used. *\externaldocument* is modified to also accept the optional arguments for *xr-hyper*, which currently uses *xr* for HTML output.

See section 5.17.

**for HTML output:** 1 \LWR@ProvidesPackagePass{xr}[2019/07/22)%

```
2 \LetLtxMacro{\LWR@orig@\externaldocument}{\externaldocument}
3
4 \RenewDocumentCommand{\externaldocument}{O{} O{} m O{} }{%
5   \ifblank{#1}{%
6     \LWR@orig@\externaldocument[#3_html]{%
7       \LWR@orig@\externaldocument[#1]{#3_html}%
8     }%
9   }%
10 }
```

---

**File 464 l warp-xr-hyper.sty****§ 564 Package *xr-hyper***

(Emulates or patches code by DAVID CARLISLE.)

Pkg *xr-hyper* *xr-hyper* is replaced by *xr*, which is modified to accept the optional arguments for *\externaldocument*. So far, no hyperlinks are provided for citations.

See section 5.17.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{xr-hyper}[2019/10/03]%
2
3 \LWR@origRequirePackage{l warp-xr}

---

**File 465 l warp-xtab.sty****§ 565 Package xtab***(Emulates or patches code by PETER WILSON.)*

Pkg xtab xtab is emulated.

for HTML output: 1 \LWR@ProvidesPackageDrop{xtab}[2011/07/31]

**⚠ Misplaced alignment  
tab character &**

For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars
```

See section 8.10.1.

**⚠ lateximage** supertabular and xtab are not supported inside a lateximage.

```
2 \newcommand{\LWRXT@firsthead}{}%
3
4 \newcommand{\tablefirsthead}[1]{%
5   \long\gdef\LWRXT@firsthead{\#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}%
9
10 \newcommand{\tablelasthead}[1]{}%
11
12 \newcommand{\notablelasthead}{}%
13
14 \newcommand{\tabletail}[1]{}%
15
16 \newcommand{\LWRXT@lasttail}{}%
17
18 \newcommand{\tablelasttail}[1]{%
19   \long\gdef\LWRXT@lasttail{\#1}%
20 }

21 \newcommand{\tablecaption}[2][]{}%
22   \long\gdef\LWRXT@caption{%
23     \ifblank{\#1}{%
24       {\caption{\#2}}%
25       {\caption[\#1]{\#2}}%
26     }%
27   }%
28
29 \let\topcaption\tablecaption
30 \let\bottomcaption\tablecaption
```

```

31 \newcommand*{\LWRXT@caption}{}%
32
33 \newcommand*{\shrinkheight}[1]{}%
34
35 \newcommand*{\xentrystretch}[1]{}%
36
37 \NewDocumentEnvironment{xtabular}{s o m}
38 {%
39 \LWR@traceinfo{xtabular}%
40 \table%
41 \LWRXT@caption%
42 \begin{tabular}{#3}%
43 \TabularMacro\ifdefvoid{\LWRXT@firsthead}%
44 {\LWR@getmynexttoken}%
45 {\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
46 }%
47 {%
48 \ifdefvoid{\LWRXT@lasttail}%
49 {}%
50 {%
51 \TabularMacro\ResumeTabular%
52 \LWRXT@lasttail%
53 }%
54 \end{tabular}%
55 \endtable%
56 \gdef\LWRXT@caption{}%
57 \LWR@traceinfo{xtabular done}%
58 }%
59
60 \NewDocumentEnvironment{mpxtabular}{s o m}
61 {\minipage{\linewidth}\xtabular{#3}%
62 {\endxtabular\endminipage}

```

File 466 **lwarf-xunicode.sty**

§ 566 Package **xunicode**

Pkg xunicode Error if xunicode is loaded after lwarf.

Patch lwarf-xunicode, but also verify that it was loaded before lwarf:

**for HTML output:**

```

1 \LWR@LoadBefore{xunicode}%
2
3 \LWR@ProvidesPackagePass{xunicode}[2011/09/09]

```

\textcircled becomes a span with a rounded border. \providecommand is used to avoid conflict with textcomp.

```

4 \providecommand*{\LWR@HTML@textcircled}[1]{%
5   \InlineClass[border: 1px solid \LWR@currentTextColor]{textcircled}{#1}%

```

```

6 }
7
8 \LWR@formatted{textcircled}

```

Nullify xunicode macros when generating filenames:

```

9 \FilenameNullify{%
10   \renewcommand*\{\textdegree}{\%}
11   \renewcommand*\{\textcelsius}{\%}
12   \renewcommand*\{\textohm}{\%}
13   \renewcommand*\{\textmu}{\%}
14   \renewcommand*\{\textlquill}{\%}
15   \renewcommand*\{\textrquill}{\%}
16   \renewcommand*\{\textcircledP}{\%}
17   \renewcommand*\{\texttwelveudash}{\%}
18   \renewcommand*\{\textthreequartersemdash}{\%}
19   \renewcommand*\{\textmho}{\%}
20   \renewcommand*\{\textnaira}{\%}
21   \renewcommand*\{\textpeso}{\%}
22   \renewcommand*\{\textrecipe}{\%}
23   \renewcommand*\{\textinterrobang}{\%}
24   \renewcommand*\{\textinterrobangdown}{\%}
25   \renewcommand*\{\textperthousand}{\%}
26   \renewcommand*\{\textpertenthousand}{\%}
27   \renewcommand*\{\textbaht}{\%}
28   \renewcommand*\{\textdiscount}{\%}
29   \renewcommand*\{\textservicemark}{\%}
30   \renewcommand*\{\textcircled}[1]{\#1}%
31   \renewcommand*\{\capitalcedilla}[1]{\#1}%
32   \renewcommand*\{\capitalogonek}[1]{\#1}%
33   \renewcommand*\{\capitalgrave}[1]{\#1}%
34   \renewcommand*\{\capitalacute}[1]{\#1}%
35   \renewcommand*\{\capitalcircumflex}[1]{\#1}%
36   \renewcommand*\{\capitaltilde}[1]{\#1}%
37   \renewcommand*\{\capitaldieresis}[1]{\#1}%
38   \renewcommand*\{\capitalhungarumlaut}[1]{\#1}%
39   \renewcommand*\{\capitalring}[1]{\#1}%
40   \renewcommand*\{\capitalcaron}[1]{\#1}%
41   \renewcommand*\{\capitalbreve}[1]{\#1}%
42   \renewcommand*\{\capitalmacron}[1]{\#1}%
43   \renewcommand*\{\capitaldotaccent}[1]{\#1}%
44 }% \FilenameNullify

```

### File 467 **lwarf-xurl.sty**

§ 567      Package **Xurl**

Pkg xurl xurl is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{xurl}[2020/01/14]
2
3 \def\useOriginalUrlSetting{}

```

---

**File 468 l warp-xy.sty**

§ 568      Package **XY**

(Emulates or patches code by KRISTOFFER H. ROSE, ROSS MOORE.)

Pkg xy xy is patched for use by l warp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{xy}[2013/10/06]

After xy modules have been loaded:

2 \AtBeginDocument{

The original definitions without a lateximage:

3 \LetLtxMacro{\LWR@orig@xy}{\xy}  
4 \LetLtxMacro{\LWR@orig@endxy}{\endxy}

The outer-most xy environment is placed in a lateximage, but not more than one level deep, which would conflict with xy:

5 \renewcommand\*{\xy}{%  
6     \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}{%  
7         \addtocounter{\LWR@lateximagedepth}{1}{%  
8             \begin{lateximage}[-xy--\PackageDiagramAltText]{}}%  
9         \LWR@orig@xy%  
10 }  
11  
12 \renewcommand\*{\endxy}{%  
13     \LWR@orig@endxy%  
14     \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{1}{%  
15         \addtocounter{\LWR@lateximagedepth}{-1}{%  
16             \end{lateximage}}%  
17 }

The \xybox must use the original definitions of \xy, \endxy:

18 \def\xybox#1{  
19     \LWR@orig@xy#1\LWR@orig@endxy%  
20     \Edge@c={\rectangleEdge}\computeLeftUpness@%  
21 }

If \xygraph is used, it is placed inside a lateximage:

22 \@ifundefined{xygraph}{}{  
23  
24 \LetLtxMacro{\LWR@origxygraph}{\xygraph}  
25  
26 \renewcommand{\xygraph}[1]{%

```
27   \begin{lateximage}[-xy- xygraph \PackageDiagramAltText]
28   \LWR@origxygraph{\#1}
29   \end{lateximage}
30 }
31
32 }% xygraph defined
33
34 }% AtBeginDocument
```

---

**File 469 l warp-zhlineskip.sty****§ 569 Package zhlineskip**

Pkg zhlineskip zhlineskip is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{zhlineskip}[2019/05/15]

```
2 \newcommand*\SetTextEnvironmentSinglespace[1]{}
3 \newcommand*\RestoreTextEnvironmentLeading[1]{}
4 \newcommand*\SetMathEnvironmentSinglespace[1]{}
5 \newcommand*\RestoreMathEnvironmentLeading[1]{}
```

---

**File 470 l warp-zwpagelayout.sty****§ 570 Package zwpagelayout**

(Emulates or patches code by ZDENĚK WAGNER.)

Pkg zwpagelayout zwpagelayout is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{zwpagelayout}[2013/01/13]

```
2 \def\noBboxes{}
3 \@onlypreamble\noBboxes
4
5 \expandafter\ifx\csname definecolor\endcsname\relax \else
6   \definecolor{cmykblack}{cmyk}{0,0,0,1}
7   \definecolor{grblack}{gray}{0}
8 %   \ifzwpl@redefineblack
9 %     \definecolor{black}{cmyk}{0,0,0,1}\color{black}
10 %   \fi
11  \definecolor{cmykred}{cmyk}{0,1,1,0}
12  \definecolor{cmykgreen}{cmyk}{1,0,1,0}
13  \definecolor{cmykblue}{cmyk}{1,1,0,0}
14  \definecolor{rbred}{rgb}{1,0,0}
15  \definecolor{rbgreen}{rgb}{0,1,0}
16  \definecolor{rbblue}{rgb}{0,0,1}
17 %  \ifzwpl@redefinecmyk
18 %    \definecolor{red}{cmyk}{0,1,1,0}
```

```
19 %      \definecolor{green}{cmyk}{1,0,1,0}
20 %      \definecolor{blue}{cmyk}{1,1,0,0}
21 %      \fi
22 \fi
23
24 \let\OverprintXeTeXExtGState\relax
25
26 \DeclareRobustCommand\SetOverprint{\ignorespaces}
27 \DeclareRobustCommand\SetKnockout{\ignorespaces}
28 \DeclareRobustCommand\textoverprint[1]{{\SetOverprint#1}}
29 \DeclareRobustCommand\textknockout[1]{{\SetKnockout#1}}
30
31 \def\SetPDFminorversion#1{}
32 @onlypreamble\SetPDFminorversion
33
34 \newcommand*\Vcorr(){}
35
36 \DeclareRobustCommand\vb[1][]{}
37 \NewDocumentCommand{\NewOddPage}{* o}{}
38 \NewDocumentCommand{\NewEvenPage}{* o}{}
39 \def\SetOddPageMessage#{\gdef\ZW@oddwarning}
40 \def\SetEvenPageMessage#{\gdef\Z@evenwarning}
41 \def\ZW@oddwarning{Empty page inserted}\let\ZW@evenwarning\ZW@oddwarning
42
43 \def\clap#1{\hbox{#1}}
44
45 \def\CropFlap{2in}
46 \def\CropSpine{1in}
47 \def\CropXSpine{1in}
48 \def\CropXtrim{.25in}
49 \def\CropYtrim{.25in}
50 \def\UserWidth{5in}
51 \def\UserLeftMargin{1in}
52 \def\UserRightMargin{1in}
53 \def\UserTopMargin{1in}
54 \def\UserBotMargin{1in}
55 \def\thePageNumber{\LWR@origpound\,,\arabic{page}}
56 \ifXeTeX
57 \def\ifcaseZWdriver{\ifcase2}
58 \else
59 \def\ifcaseZWdriver{\ifcase1}
60 \fi
61 \DeclareRobustCommand\ZWifdriver[2]{}
```

---

**File 471 lwarp-patch-komascript.sty**

§ 571      Package    **patch-komascript**

Pkg    **lwarp-patch-komascript**    Patches for komascript classes.

lwarp loads this package when **scrbook**, **scrartcl**, or **scrreprt** classes are detected.

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

\titlehead, \subject, \captionformat, \figureformat, and \tableformat are not yet emulated.

 **Not fully tested!** [Please send bug reports!](#)

Some features have not yet been tested. Please contact the author with any bug reports.

**for HTML output:** 1 \ProvidesPackage{lwarf-patch-komascript}

typearea is emulated.

2 \RequirePackage{lwarf-typearea}

tocbasic is emulated.

3 \RequirePackage{lwarf-tocbasic}

scrextend patches most of the new macros.

4 \RequirePackage{lwarf-scrextend}

Indexing macros, simplified for lwarf:

```
5 \AtBeginDocument{  
6  
7 \renewcommand*\idx@heading{  
8   \idx@heading{\indexname}  
9 }  
10  
11 \renewenvironment{theindex}{  
12   \idx@heading%  
13   \index@preamble\par\nobreak  
14   \let\item\LWR@indexitem%  
15   \let\subitem\LWR@indexsubitem%  
16   \let\subsubitem\LWR@indexsubsubitem%  
17 }  
18 {}  
19  
20 \renewcommand*\indexspace{}  
21  
22 }% AtBeginDocument
```

The \minisec is placed inside a <div> of class minisec.

```
23 \renewcommand*\minisec[1]{  
24   \begin{BlockClass}{minisec}  
25     #1  
26   \end{BlockClass}  
27 }
```

The part and chapter preambles are placed as plain text just after each heading.

```

28 \@ifundefined{setpartpreamble}{}{
29   \RenewDocumentCommand{\setpartpreamble}{o o +m}{%
30     \renewcommand{\part@preamble}{#3}%
31   }%
32 }%
33
34 \@ifundefined{setchapterpreamble}{}{
35   \RenewDocumentCommand{\setchapterpreamble}{o o +m}{%
36     \renewcommand{\chapter@preamble}{#3}%
37   }%
38 }

```

Simple captions are used in all cases.

```

39 \AtBeginDocument{
40   \LetLtxMacro\captionbelow\caption
41   \LetLtxMacro\captionabove\caption
42
43   \LetLtxMacro\captionofbelow\captionof
44   \LetLtxMacro\captionofabove\captionof
45 }%
46
47 \RenewDocumentEnvironment{captionbeside}{o m o o o s}
48 {}
49 {%
50   \IfValueTF{#1}{%
51     {\caption[#1]{#2}}%
52     {\caption{#2}}%
53   }%
54
55 \RenewDocumentEnvironment{captionofbeside}{m o m o o o s}
56 {}
57 {%
58   \IfValueTF{#2}{%
59     {\captionof{#1}[#2]{#3}}%
60     {\captionof{#1}{#3}}%
61   }%
62
63 \RenewDocumentCommand{\setcapindent}{s m}{}%
64 \renewcommand*\setcaphanging{}%
65 \renewcommand*\setcapwidth}[2][]{%
66 \renewcommand*\setcapdynwidth}[2][]{%
67 \RenewDocumentCommand{\setcapmargin}{s o m}{}%

```

File 472 **lwarp-patch-memoir.sty**

§ 572 Package **patch-memoir**

*(Emulates or patches code by PETER WILSON.)*

Pkg lwarp-patch-memoir Patches for memoir class.

 Not fully tested! Please send bug reports!

`l warp` loads this package when the `memoir` class is detected.

**⚠️ options clash** While emulating `memoir`, `l warp` pre-loads a number of packages (section 572.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading `l warp`:

```
\documentclass{memoir}
...
\PassOptionsToPackage{options_list}{package_name}
...
\usepackage{l warp}
...
\usepackage{package_name}
```

**⚠️ version numbers** `memoir` emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since `l warp` is intended to support the freestanding packages, which are often newer than the date declared by `memoir`, it is hoped that `memoir` will update and change its emulated version numbers to match.

`\verbfootnote` is not supported.

`\newfootnoteseries`, etc. are not supported.

`l warp` loads `pagenote` to perform `memoir`'s `pagenote` functions, but there are minor differences in `\pagenotesubhead` and related macros.

Poem numbering is not supported.

The `verbatim` environment does not yet support the `memoir` enhancements. It is currently recommended to load and use `fancyvrb` instead.

The `memoir` glossary system is not yet supported by `l warpmk`. The `glossaries` package may be used instead, but does require the glossary entries be changed from the `memoir` syntax to the `glossaries` syntax.

**for HTML output:** 1 `\ProvidesPackage{l warp-patch-memoir}`

## § 572.1 Packages

These are pre-loaded to provide emulation for many of `memoir`'s functions. `memoir` pretends that `abstract`, etc. are already loaded, via its “emulated” package mechanism, but `l warp` is directly loading the “`l warp-`” version of each, which happens to avoid `memoir`'s emulation system.

```
2 \RequirePackage{l warp-abstract}% req'd
3 \RequirePackage{l warp-array}% req'd
4 \RequirePackage{l warp-booktabs}% req'd
5 % \RequirePackage{l warp-ccaption}% emulated below
6 \RequirePackage{l warp-changepage}% req'd
7 \RequirePackage{l warp-crop}
8 \RequirePackage{l warp-dcolumn}% req'd
9 \RequirePackage{l warp-enumerate}% req'd
10 \RequirePackage{l warp-epigraph}% req'd
11 \RequirePackage{l warp-fancyvrb}% req'd
```

---

```

12 \RequirePackage{l warp-footmisc}%
13 \RequirePackage{l warp-framed}%
14 \RequirePackage{l warp-hanging}%
15 \RequirePackage{l warp-makeidx}%
16 \DisemulatePackage{moreverb}
17 \RequirePackage{l warp-moreverb}
18 \RequirePackage{l warp-mparhack}
19 \RequirePackage{l warp-needspace}%
20 \RequirePackage{l warp-nextpage}%
21 \RequirePackage{l warp-pagenote}%
22 \RequirePackage{l warp-parskip}
23 \RequirePackage{l warp-setspace}%
24 \RequirePackage{l warp-showidx}
```

Avoids a conflict with `memoir`:

```

25 \AtBeginDocument{%
26   \@ifpackageloaded{subcaption}{}{%
27     \RequirePackage{l warp-subfigure}
28     \let\subfigure\subbottom
29     \let\subtable\subtop
30   }%
31 }%
32 \makeindex
```

`subfigure` is emulated via `subfig`, which pre-defines `subfigure` and `subtable`, but `memoir` does not, so they must be tested for here:

```

33 \LetLtxMacro{\LWR@memorignewsubfloat}{\newsubfloat}
34 \RenewDocumentCommand{\newsubfloat}{O{} m}{%
35   \@ifundefined{c@sub#2}{%
36     \LWR@memorignewsubfloat[#1]{#2}%
37   }%
38 }
39
40 \RequirePackage{l warp-tabularx}%
41 \RequirePackage{l warp-titling}%
42 % \RequirePackage{l warp-tocbibind}%
43 \RequirePackage{l warp-tocloft}%
44 \RequirePackage{l warp-verse}%
```

## § 572.2 Preliminary setup

Bypass the `memoir` package mechanism:

```
45 \LetLtxMacro{\LWR@orig@label}{\mem@old@label}
```

`memoir` already set the page size to a default, so it must be forced large for `l warp`'s use, to avoid tag overflows off the page.

```

46 \setstocksize{190in}{20in}
47 \setlrmarginsandblock{2in}{2in}{*}
48 \setulmarginsandblock{1in}{1in}{*}
```

§ 572.3 Page layout

```
103 \renewcommand*\{\stockimperialvo}{}
104 \renewcommand*\{\pagepottvo}{}
105 \renewcommand*\{\pagefoolscapvo}{}
106 \renewcommand*\{\pagecrownvo}{}
107 \renewcommand*\{\pagepostvo}{}
108 \renewcommand*\{\pagelargecrownvo}{}
109 \renewcommand*\{\pagelargepostvo}{}
110 \renewcommand*\{\pagesmalldemyvo}{}
111 \renewcommand*\{\pagedemyvo}{}
112 \renewcommand*\{\pagemediumvo}{}
113 \renewcommand*\{\pagesmallroyalvo}{}
114 \renewcommand*\{\pageroyalvo}{}
115 \renewcommand*\{\pagesuperroyalvo}{}
116 \renewcommand*\{\pageimperialvo}{}
117
118 \renewcommand*\{\memfontfamily}{}
119 \renewcommand*\{\memfontenc}{}
120 \renewcommand*\{\memfontpack}{}
121
122 \renewcommand*\{\anyptfilebase}{}
123 \renewcommand*\{\anyptsizes}{10}
124
125 \renewcommand*\{\setstocksize}[2]{}
126 \renewcommand*\{\settrimmedsize}[3]{}
127 \renewcommand*\{\settrims}[2]{}
128
129 % \newlength{\lxvchars}
130 % \setlength{\lxvchars}{305pt}
131 % \newlength{\xlvchars}
132 % \setlength{\xlvchars}{190pt}
133 \renewcommand*\{\setlxvchars}[1]{}
134 \renewcommand*\{\setlxvchars}[1]{}
135
136 \renewcommand*\{\settypeblocksize}[3]{}
137 \renewcommand*\{\setlrmargins}[3]{}
138 \renewcommand*\{\setlrmarginsandblock}[3]{}
139 \renewcommand*\{\setbinding}[1]{}
140 \renewcommand*\{\setulmargins}[3]{}
141 \renewcommand*\{\setulmarginsandblock}[3]{}
142 \renewcommand*\{\setcolsepandruler}[2]{}
143
144 \renewcommand*\{\setheadfoot}[2]{}
145 \renewcommand*\{\setheaderspaces}[3]{}
146 \renewcommand*\{\setmarginnotes}[3]{}
147 \renewcommand*\{\setfootins}[2]{}
148 \renewcommand*\{\checkandfixthelayout}[1][]{}
149 \renewcommand*\{\checkthelayout}[1]{}
150 \renewcommand*\{\fixthelayout}{}  

151 %
152 % \newlength{\stockheight}
153 % \newlength{\trimtop}
154 % \newlength{\trimedge}
155 % \newlength{\stockwidth}
156 % \newlength{\spinemargin}
157 % \newlength{\foremargin}
```

```

158 % \newlength{\uppermargin}
159 % \newlength{\headmargin}
160 %
161 \renewcommand*{\typeoutlayout}{}
162 \renewcommand*{\typeoutstandardlayout}{}
163 \renewcommand*{\settypeoutlayoutunit}[1]{}
164 \renewcommand*{\fixpdflayout}{}
165 \renewcommand*{\fixdvipslayout}{}
166
167 \renewcommand*{\medievalpage}[1][]{}
168 \renewcommand*{\isopage}[1][]{}
169 \renewcommand*{\semiisopage}[1][]{}
170
171 \renewcommand{\setpagebl}[3]{}
172 \renewcommand{\setpageml}[3]{}
173 \renewcommand{\setpagetl}[3]{}
174 \renewcommand{\setpagetm}[3]{}
175 \renewcommand{\setpagetr}[3]{}
176 \renewcommand{\setpagemr}[3]{}
177 \renewcommand{\setpagebr}[3]{}
178 \renewcommand{\setpagebm}[3]{}
179 \renewcommand{\setpagecc}[3]{}

```

#### § 572.4 Text and fonts

```

180 \let\miniscule\tiny
181 \let\HUGE\Huge
182
183 \renewcommand*{\abnormalparskip}[1]{}
184 \renewcommand*{\nonzeroparskip}={}
185 \renewcommand*{\traditionalparskip}={}
186
187 \let\onelineskip\baselineskip
188
189 \let\OnehalfSpacing\onehalfspacing
190 \let\DoubleSpacing\doublespacing
191 \renewcommand*{\setPagenoteSpacing}[1]{}
192 \renewcommand*{\setFloatSpacing}[1]{}
193 \let\SingleSpacing\singlespacing
194 \let\setSingleSpace\SetSingleSpace
195 \let\SingleSpace\singlespace
196 \let\endSingleSpace\endsingleSpace
197 \let\Spacing\space
198 \let\endSpacing\endspace
199 \let\OnehalfSpace\onehalfspace
200 \let\endOnehalfSpace\endonehalfspace
201 \csletcs{OnehalfSpace*}{onehalfspace}
202 \csletcs{endOnehalfSpace*}{endonehalfspace}
203 \let\DoubleSpace\doublespace
204 \let\endDoubleSpace\enddoublespace
205 \csletcs{DoubleSpace*}{doublespace}
206 \csletcs{endDoubleSpace*}{enddoublespace}
207 \renewcommand*{\setDisplayskipStretch}[1]{}
208 \renewcommand*{\memskipstretch}={}
209 \renewcommand*{\noDisplayskipStretch}={}
210 \renewcommand*{\memskips}={}

```

---

```

211
212 \renewcommand*\{midsloppy}{}
213 \renewenvironment*midsloppypar{}{}{}
214
215 \renewcommand*\{sloppybottom}{}

```

### § 572.5 Titles

```

216 \csletcs{titlingpage*}{titlingpage}
217 \csletcs{endtitlingpage*}{endtitlingpage}
218 \let\titlingpageend\relax
219 \newcommand{\titlingpageend}[2]{}
220 \let\andnext\and
221 \renewcommand{\thanksmarkstyle}[1]{}
222
223 \renewcommand{\thanksfootmark}{%
224   \thanksscript{\tmark}%
225 }
226
227 % \newlength{\thanksmarkssep} already provided by memoir

```

### § 572.6 Abstracts

```

228 \renewcommand*\{abstractcol}{}
229 \renewcommand*\{abstractintoc}{}
230 \renewcommand*\{abstractnum}{}
231 \renewcommand*\{abstractrunin}{}

```

### § 572.7 Document divisions

```

\book * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {<6:name>}
232 \DeclareDocumentCommand{\book}{s d() o o d() m}{%
233   \LWR@section{#1}{#3}{#6}{book}%
234 }

235 \def\@apppage{%
236   \part*\{appendixpagename\}
237 }
238 \renewcommand\mempreaddapppagetotohook{}
239 \renewcommand\mempostaddapppagetotohook{}
240
241 \def\@sapppage{%
242   \part*\{appendixpagename\}
243 }

244 \DeclareDocumentCommand{\mainmatter}{s}{%
245   \booltrue{LWR@mainmatter}%
246 }
247
248 \DeclareDocumentCommand{\frontmatter}{s}{%
249   \boolfalse{LWR@mainmatter}%
250 }

```

```
251 \renewcommand*{\raggedbottomsection}{}  
252 \renewcommand*{\normalbottomsection}{}  
253 \renewcommand*{\bottomsectionskip}{}  
254 \renewcommand*{\bottomsectionpenalty}{}  
255 \csletcs{appendixpage}{appendixpage}  
256 \renewcommand*{\namedsubappendices}{}  
257 \renewcommand*{\unnamedsubappendices}{}  
258 \renewcommand*{\setsecnumdepth}[1]{}% todo tocvsec2  
259 \renewcommand*{\maxsecnumdepth}[1]{}% todo tocvsec2  
260 \renewcommand*{\beforebookskip}{}  
261 \renewcommand*{\afterbookskip}{}  
262 \renewcommand*{\beforepartskip}{}  
263 \renewcommand*{\afterpartskip}{}  
264 \renewcommand*{\midbookskip}{}  
265 \renewcommand*{\midpartskip}{}  
266 \renewcommand*{\printbookname}{}  
267 \renewcommand*{\booknamefont}{}  
268 \renewcommand*{\booknamenum}{}  
269 \renewcommand*{\printbooknum}{}  
270 \renewcommand*{\booknumfont}{}  
271 \renewcommand*{\printpartname}{}  
272 \renewcommand*{\partnamefont}{}  
273 \renewcommand*{\partnamenum}{}  
274 \renewcommand*{\printpartnum}{}  
275 \renewcommand*{\partnumfont}{}  
276 \renewcommand*{\printbooktitle}[1]{}  
277 \renewcommand*{\booktitlefont}{}  
278 \renewcommand*{\printparttitle}[1]{}  
279 \renewcommand*{\parttitlefont}{}  
280 \renewcommand*{\bookpageend}{}  
281 \renewcommand*{\bookblankpage}{}  
282 \renewcommand*{\nobookblankpage}{}  
283 \renewcommand*{\partpageend}{}  
284 \renewcommand*{\partblankpage}{}  
285 \renewcommand*{\nopartblankpage}{}  
286 \RenewDocumentCommand{\newleadpage}{s o m m}{}% todo  
287 \RenewDocumentCommand{\renewleadpage}{s o m m}{}% todo  
288 \renewcommand*{\leadpagetoclevel}{chapter}  
289  
290 \renewcommand*{\openright}{}  
291 \renewcommand*{\openleft}{}  
292 \renewcommand*{\openany}{}  
293 \renewcommand*{\clearforchapter}{}  
294 \renewcommand*{\memendofchapterhook}{}  
295 \renewcommand*{\chapterheadstart}{}  
296 % \newlength{\beforechapskip}  
297 \renewcommand*{\afterchaptnum}{}  
298 % \newlength{\midchapskip}  
299 \renewcommand*{\afterchapttitle}{}  
300 % \newlength{\afterchapskip}  
301 \renewcommand*{\printchaptername}{}  
302 \renewcommand*{\chapnamefont}{}  
303 \renewcommand*{\chapnamenum}{}  
304 \renewcommand*{\printchaptnum}{}  
305 \renewcommand*{\chapnumfont}{}  
306
```

```
306 \renewcommand{\printchapertitle}[1]{}
307 \renewcommand*{\chaptilefont}={}
308 \renewcommand*{\printchapternum}{}
309 \renewcommand*{\indentafterchapter}{}
310 \renewcommand*{\noindentafterchapter}{}
311 \renewcommand*{\insertchapterspace}{}
312
313 \renewcommand*{\chapterstyle}[1]{}
314 \renewcommand{\makechapterstyle}[2]{}
315 \renewcommand*{\chapindent}{}
316 \let\chapterprecis\cftchapterprecis
317 \let\chapterprecishere\cftchapterprecishere
318 \let\chapterprecistoc\cftchapterprecistoc
319 \renewcommand*{\precisfont}{}
320 \renewcommand*{\prechapterprecis}{}
321 \renewcommand*{\postchapterprecis}{}
322 \renewcommand{\precistotext}[1]{}
323 \renewcommand*{\precistocfont}{}
324 \renewcommand*{\precistocformat}{}
325 % \newlength{\prechapterprecisshift}
326
327 \renewcommand*{\setbeforesecskip}[1]{}
328 \renewcommand*{\setaftersecskip}[1]{}
329 \renewcommand*{\setsecindent}[1]{}
330 \renewcommand*{\setsecheadstyle}[1]{}
331 \renewcommand*{\setbeforesubsecskip}[1]{}
332 \renewcommand*{\setaftersubsecskip}[1]{}
333 \renewcommand*{\setsubsecindent}[1]{}
334 \renewcommand*{\setsubsecheadstyle}[1]{}
335 \renewcommand*{\setbeforesubsubsecskip}[1]{}
336 \renewcommand*{\setaftersubsubsecskip}[1]{}
337 \renewcommand*{\setsubsubsecindent}[1]{}
338 \renewcommand*{\setsubsubsecheadstyle}[1]{}
339 \renewcommand*{\setbeforeparaskip}[1]{}
340 \renewcommand*{\setafterparaskip}[1]{}
341 \renewcommand*{\setparaindent}[1]{}
342 \renewcommand*{\setparaheadstyle}[1]{}
343 \renewcommand*{\setbeforesubparaskip}[1]{}
344 \renewcommand*{\setaftersubparaskip}[1]{}
345 \renewcommand*{\setsupparaindent}[1]{}
346 \renewcommand*{\setsupparaheadstyle}[1]{}
347 \renewcommand{@hangfrom}[1]{#1}
348 \renewcommand{\sethangfrom}[1]{}
349 \renewcommand{\setsecnumformat}[1]{}
350
351 \renewcommand*{\hangsecnum}{}
352 \renewcommand*{\defaultsecnum}{}
353
354 \renewcommand*{\sechook}{}
355 \renewcommand{\setsechook}[1]{}
356 \renewcommand*{\subsechook}{}
357 \renewcommand{\setsupsechook}[1]{}
358 \renewcommand*{\subsubsechook}{}
359 \renewcommand{\setsupsubsechook}[1]{}
360 \renewcommand*{\parahook}{}
```

---

```

361 \renewcommand{\setparahook}[1]{}
362 \renewcommand*{\subparahook}{}%
363 \renewcommand{\setsubparahook}[1]{}
364
365 \RenewDocumentCommand{\plainbreak}{s m}{\begin{center}\end{center}}
366
367 \RenewDocumentCommand{\fancybreak}{s +m}{%
368     \begin{center}#2\end{center}%
369 }
370
371 \RenewDocumentCommand{\plainfancybreak}{s m m +m}{%
372     \begin{center}#4\end{center}%
373 }
374
375 \RenewDocumentCommand{\pfbreak}{s}{%
376     \begin{center}%
377         \pfbreakdisplay
378     \end{center}%
379 }
380
381 % \newlength{\pfbreakskip}
382 \renewcommand{\pfbreakdisplay}{*\quad*\quad*}
383
384 \renewcommand{\makeheadstyles}[2]{}
385 \renewcommand*{\headstyles}[1]{}

```

## § 572.8 Pagination and headers

```

386 \renewcommand*{\savepagenumber}{}%
387 \renewcommand*{\restorepagenumber}{}%
388 \renewcommand*{\uppercaseheads}{}%
389 \renewcommand*{\nouppercaseheads}{}%
390
391 \renewcommand*{\bookpagemark}[1]{}
392 \renewcommand*{\partmark}[1]{}
393 \renewcommand*{\bibmark}{}%
394 \renewcommand*{\indexmark}{}%
395 \renewcommand*{\glossarymark}{}%
396
397 \LWR@origpagestyle{empty}
398 \renewcommand*{\ps@empty}{}%
399 \renewcommand*{\makepagestyle}[1]{}
400 \renewcommand*{\emptypshook}{}%
401 % \renewcommand*{\empty@oddhead}{}%
402 % \renewcommand*{\empty@oddfoot}{}%
403 % \renewcommand*{\empty@evenhead}{}%
404 % \renewcommand*{\empty@evenfoot}{}%
405 \renewcommand*{@oddhead}{}%
406 \renewcommand*{@oddfoot}{}%
407 \renewcommand*{@evenhead}{}%
408 \renewcommand*{@evenfoot}{}%
409 \renewcommand*{\aliaspagestyle}[2]{}
410 \renewcommand*{\copypagestyle}[2]{}
411
412 \renewcommand*{\makeevenhead}[4]{}
413 \renewcommand*{\makeoddhead}[4]{}

```

```

414 \renewcommand*\{\makeevenfoot}[4]{}
415 \renewcommand*\{\makeoddfoot}[4]{}
416 \renewcommand*\{\makerunningwidth}[3]{}
417 % \newlength{\headwidth}
418 \renewcommand*\{\makeheadrule}[3]{}
419 \renewcommand*\{\makefootrule}[3]{}
420 \renewcommand*\{\makeheadfootruleprefix}[3]{}
421 % \newlength{\normalrulethickness}
422 % \setlength{\normalrulethickness}{.4pt}
423 % \newlength{\footruleheight}
424 % \newlength{\footruleskip}
425 \renewcommand*\{\makeheadposition}[5]{}
426 \renewcommand{\makepsmarks}[2]{}
427 \renewcommand*\{\makeheadfootstrut}[3]{}
428
429 \renewcommand{\createplainmark}[3]{}
430 \renewcommand{\memUhead}[1]{}
431 \renewcommand{\createmark}[5]{}
432 \renewcommand*\{\clearplainmark}[1]{}
433 \renewcommand*\{\clearmark}[1]{}
434 \renewcommand{\addtopsmarks}[3]{}
435 \renewcommand{\ifonlyfloats}[2]{#2}
436 \renewcommand*\{\mergepagefloatstyle}[3]{}
437
438 \renewcommand*\{\framepichead}{}
439 \renewcommand*\{\framepictextfoot}{}
440 \renewcommand*\{\framepichook}{}
441 \renewcommand*\{\showheadfootlocoff}{}
442 \renewcommand*\{\showtextblocklocoff}{}

```

### § 572.9 Paragraphs and lists

```

443 \renewcommand{\hangfrom}[1]{#1}
444 \let\centerfloat\centering
445 \renewcommand*\{\raggedyright}[1][]{}
446 % \newlength{\ragrparindent}
447 \renewcommand*\{\sourceatright}[2][]{\attribution{#2}}
448 \let\memorigdbs\LWR@endofline
449 \let\memorigpar\par
450 \let\atcentercr\LWR@endofline
451
452 \renewcommand*\{\linenottooshort}[1][]{}
453 \renewcommand*\{\russianpar}){}
454 \renewcommand*\{\lastlinerulefill}{}
455 \renewcommand*\{\lastlineparrule}{}
456 \renewcommand*\{\justlastraggedleft}{}
457 \renewcommand*\{\raggedrightthenleft}{}
458 \renewcommand*\{\leftcenterright}{}
459
460 \renewcommand{\leftspringright}[4]{%
461   \begin{minipage}{#1\linewidth}#3\end{minipage}\quad%
462   \begin{minipage}{#2\linewidth}\begin{flushright}#4\end{flushright}\end{minipage}%
463 }
464
465 \renewenvironment*\{\blockdescription}%
466 {\LWR@descriptionstart\LWR@origdescription}

```

```
467 {\end{description}}
468
469 \renewcommand*{\blockdescriptionlabel}[1]{\textbf{\#1}}
470 \renewenvironment*{\labelled}[1]{\begin{description}}{\end{description}}
471 \renewenvironment*{\flexlabelled}[6]{\begin{description}}{\end{description}}
472 \renewcommand*{\tightlists}{}}
473 \renewcommand*{\defaultlists}{}}
474 \RenewDocumentCommand{\firmlists}{s}{}}
475 \renewcommand*{\firmlist}{}}
476 \renewcommand*{\tightlist}{}}
477 \renewcommand*{\zerotrivseps}{}}
478 \renewcommand*{\savetrvseps}{}}
479 \renewcommand*{\restoretrvseps}{}}
```

## § 572.10 Contents lists

```
480 \csletcs{tableofcontents*}{tableofcontents}
481 \csletcs{listoffigures*}{listoffigures}
482 \csletcs{listoftables*}{listoftables}
483 \renewenvironment{KeepFromToc}{}{}
484 \renewcommand*{\onecoltocetc}{}}
485 \renewcommand*{\twocoltocetc}{}}
486 \renewcommand*{\ensureonecol}{}}
487 \renewcommand*{\restorefromonecol}{}}
488 \renewcommand*{\doccoltocetc}{}}
489 \renewcommand*{\maxtocdepth}[1]{% tocsec2
490 \renewcommand*{\settocdepth}[1]{% tocsec2
491
492 \renewcommand{\tocheadstart}{}}
493 \renewcommand{\printtoctitle}[1]{}}
494 \renewcommand{\tocmark}{}}
495 \renewcommand{\aftertoctitle}{}}
496 \renewcommand{\lofheadstart}{}}
497 \renewcommand{\printloftitle}[1]{}}
498 \renewcommand{\lofmark}{}}
499 \renewcommand{\afterloftitle}{}}
500 \renewcommand{\lotheadstart}{}}
501 \renewcommand{\printlottitle}[1]{}}
502 \renewcommand{\lotmark}{}}
503 \renewcommand{\afterlottitle}{}}
504
505 \renewcommand*{\setpnumwidth}[1]{}}
506 \renewcommand*{\setrmarg}[1]{}}
507 \renewcommand*{\cftbookbreak}{}}
508 \renewcommand*{\cftpabtbreak}{}}
509 \renewcommand*{\cftchapterbreak}{}}

510 % \newlength{\cftbeforebookskip}
511 % \newlength{\cftbookindent}
512 % \newlength{\cftbooknumwidth}
513 \renewcommand*{\cftbookfont}{}}
514 \renewcommand*{\cftbookname}{}}
515 \renewcommand*{\cftbookpresnum}{}}
516 \renewcommand*{\cftbookaftersnum}{}}
517 \renewcommand*{\cftbookaftersnumb}{}}
518 \renewcommand*{\cftbookleader}{}}
```

```
519 \renewcommand*\{cftbookdotsep}{1}
520 \renewcommand*\{cftbookpagefont}{}
521 \renewcommand*\{cftbookafterpnum}{}
522 \renewcommand*\{cftbookformatpnum}[1]{}
523 \renewcommand*\{cftbookformatpnumhook}[1]{}
```

Part is already defined by tocloft.

```
524 % \newlength{\cftbeforechapterskip}
525 % \newlength{\cftchapterindent}
526 % \newlength{\cftchapternumwidth}
527 \renewcommand*\{cftchapterfont}{}
528 \renewcommand*\{cftchaptername}{}
529 \renewcommand*\{cftchapterpresnum}{}
530 \renewcommand*\{cftchapteraftersnum}{}
531 \renewcommand*\{cftchapteraftersnumb}{}
532 \renewcommand*\{cftchapterleader}{}
533 \renewcommand*\{cftchapterdotsep}{1}
534 \renewcommand*\{cftchapterpagefont}{}
535 \renewcommand*\{cftchapterafterpnum}{}
536 \renewcommand*\{cftchapterformatpnum}[1]{}
537 \renewcommand*\{cftchapterformatpnumhook}[1]{}

538 % \newlength{\cftbeforesections skip}
539 % \newlength{\cftsectionindent}
540 % \newlength{\cftsectionnumwidth}
541 \renewcommand*\{cftsectionfont}{}
542 \renewcommand*\{cftsectionname}{}
543 \renewcommand*\{cftsectionpresnum}{}
544 \renewcommand*\{cftsectionaftersnum}{}
545 \renewcommand*\{cftsectionaftersnumb}{}
546 \renewcommand*\{cftsectionleader}{}
547 \renewcommand*\{cftsectiondotsep}{1}
548 \renewcommand*\{cftsectionpagefont}{}
549 \renewcommand*\{cftsectionafterpnum}{}
550 \renewcommand*\{cftsectionformatpnum}[1]{}
551 \renewcommand*\{cftsectionformatpnumhook}[1]{}

552 % \newlength{\cftbeforesubsections skip}
553 % \newlength{\cftsubsectionindent}
554 % \newlength{\cftsubsectionnumwidth}
555 \renewcommand*\{cftsubsectionfont}{}
556 \renewcommand*\{cftsubsectionname}{}
557 \renewcommand*\{cftsubsectionpresnum}{}
558 \renewcommand*\{cftsubsectionaftersnum}{}
559 \renewcommand*\{cftsubsectionaftersnumb}{}
560 \renewcommand*\{cftsubsectionleader}{}
561 \renewcommand*\{cftsubsectiondotsep}{1}
562 \renewcommand*\{cftsubsectionpagefont}{}
563 \renewcommand*\{cftsubsectionafterpnum}{}
564 \renewcommand*\{cftsubsectionformatpnum}[1]{}
565 \renewcommand*\{cftsubsectionformatpnumhook}[1]{}

566 % \newlength{\cftbeforesubsubsections skip}
567 % \newlength{\cftsubsubsectionindent}
568 % \newlength{\cftsubsubsectionnumwidth}
```

```
569 \renewcommand*\cftsubsubsectionfont{}  
570 \renewcommand*\cftsubsubsectionname{}  
571 \renewcommand*\cftsubsubsektionpresnum{}  
572 \renewcommand*\cftsubsubsektionaftersnum{}  
573 \renewcommand*\cftsubsubsektionaftersnumb{}  
574 \renewcommand*\cftsubsubsektionleader{}  
575 \renewcommand*\cftsubsubsektiondotsep{1}  
576 \renewcommand*\cftsubsubsektionpagefont{}  
577 \renewcommand*\cftsubsubsektionafterpnum{}  
578 \renewcommand*\cftsubsubsektionformatpnum}[1]{  
579 \renewcommand*\cftsubsubsektionformatpnumhook}[1]{  
  
580 % \newlength{\cftbeforeparagraphskip}  
581 % \newlength{\cftpaginindent}  
582 % \newlength{\cftpaginwidth}  
583 \renewcommand*\cftpaginfont{}  
584 \renewcommand*\cftpaginname{}  
585 \renewcommand*\cftpaginpresnum{}  
586 \renewcommand*\cftpaginhaftersnum{}  
587 \renewcommand*\cftpaginhaftersnumb{}  
588 \renewcommand*\cftpaginleader{}  
589 \renewcommand*\cftpagindotsep{1}  
590 \renewcommand*\cftpaginpagefont{}  
591 \renewcommand*\cftpaginahaftersnum{}  
592 \renewcommand*\cftpaginformatpnum}[1]{  
593 \renewcommand*\cftpaginformatpnumhook}[1]{  
  
594 % \newlength{\cftbeforesubparagraphskip}  
595 % \newlength{\cftsubparagraphindent}  
596 % \newlength{\cftsubparagraphwidth}  
597 \renewcommand*\cftsubparagraphfont{}  
598 \renewcommand*\cftsubparagraphname{}  
599 \renewcommand*\cftsubparagraphpresnum{}  
600 \renewcommand*\cftsubparagraphaftersnum{}  
601 \renewcommand*\cftsubparagraphaftersnumb{}  
602 \renewcommand*\cftsubparagraphleader{}  
603 \renewcommand*\cftsubparagraphdotsep{1}  
604 \renewcommand*\cftsubparagraphpagefont{}  
605 \renewcommand*\cftsubparagraphahaftersnum{}  
606 \renewcommand*\cftsubparagraphformatpnum}[1]{  
607 \renewcommand*\cftsubparagraphformatpnumhook}[1]{  
  
608 % \newlength{\cftbeforefigureskip}  
609 % \newlength{\cftfigureindent}  
610 % \newlength{\cftfigurewidth}  
611 \renewcommand*\cftfigurefont{}  
612 \renewcommand*\cftfigurename{}  
613 \renewcommand*\cftfigurepresnum{}  
614 \renewcommand*\cftfigureaftersnum{}  
615 \renewcommand*\cftfigureaftersnumb{}  
616 \renewcommand*\cftfigureleader{}  
617 \renewcommand*\cftfiguredotsep{1}  
618 \renewcommand*\cftfigurepagefont{}  
619 \renewcommand*\cftfigureahaftersnum{}  
620 \renewcommand*\cftfigureformatpnum}[1]{  
621 \renewcommand*\cftfigureformatpnumhook}[1]{
```

```
622 % \newlength{\cftbeforesubfigureskip}
623 % \newlength{\cftsubfigureindent}
624 % \newlength{\cftsubfigurenumwidth}
625 \newcommand*{\cftsubfigurefont}){}
626 \newcommand*{\cftsubfigurename}){}
627 \newcommand*{\cftsubfigurepresnum}){}
628 \newcommand*{\cftsubfigureaftersnum}){}
629 \newcommand*{\cftsubfigureaftersnumb}){}
630 \newcommand*{\cftsubfigureleader}){}
631 \newcommand*{\cftsubfiguredotsep}{1}
632 \newcommand*{\cftsubfigurepagefont}){}
633 \newcommand*{\cftsubfigureafterpnum}){}
634 \newcommand*{\cftsubfigureformatpnum}[1]{}
635 \newcommand*{\cftsubfigureformatpnumhook}[1]{}

636 % \newlength{\cftbeforetablesip}
637 % \newlength{\cfttableindent}
638 % \newlength{\cfttablenumwidth}
639 \renewcommand*{\cfttablefont}){}
640 \renewcommand*{\cfttablename}){}
641 \renewcommand*{\cfttablepresnum}){}
642 \renewcommand*{\cfttableaftersnum}){}
643 \renewcommand*{\cfttableaftersnumb}){}
644 \renewcommand*{\cfttableleader}){}
645 \renewcommand*{\cfttabledotsep}{1}
646 \renewcommand*{\cfttablepagefont}){}
647 \renewcommand*{\cfttableafterpnum}){}
648 \renewcommand*{\cfttableformatpnum}[1]{}
649 \renewcommand*{\cfttableformatpnumhook}[1]{}

650 % \newlength{\cftbeforesubtableskip}
651 % \newlength{\cftsubtableindent}
652 % \newlength{\cftsubtablenumwidth}
653 \newcommand*{\cftsubtablefont}){}
654 \newcommand*{\cftsubtablename}){}
655 \newcommand*{\cftsubtablepresnum}){}
656 \newcommand*{\cftsubtableaftersnum}){}
657 \newcommand*{\cftsubtableaftersnumb}){}
658 \newcommand*{\cftsubtableleader}){}
659 \newcommand*{\cftsubtabledotsep}{1}
660 \newcommand*{\cftsubtablepagefont}){}
661 \newcommand*{\cftsubtableafterpnum}){}
662 \newcommand*{\cftsubtableformatpnum}[1]{}
663 \newcommand*{\cftsubtableformatpnumhook}[1]{}

664 \renewcommand*{\booknumberline}[1]{}
665 \renewcommand*{\partnumberline}[1]{}
666 \renewcommand*{\chapternumberline}[1]{}
667 \renewcommand*{\numberlinehook}[1]{}
668 % \renewcommand*{\cftwhatismyname}{}%
669 \renewcommand*{\booknumberlinehook}[1]{}
670 \renewcommand*{\partnumberlinehook}[1]{}
671 \renewcommand*{\chapternumberlinehook}[1]{}
672 \renewcommand{\numberlinebox}[2]{}
673 \renewcommand{\booknumberlinebox}[2]{}
674 \renewcommand{\partnumberlinebox}[2]{}
```

---

```

675 \renewcommand{\chaptnumberlinebox}[2]{}
676 %
677 % \newlength{\cftparskip}
678 \renewcommand*{\cftpagenumbersoff}[1]{}
679 \renewcommand*{\cftpagenumberson}[1]{}
680 \renewcommand*{\cftlocalchange}[3]{}
681 \renewcommand*{\cftaddtitleline}[4]{}
682 \renewcommand*{\cftaddnumtitleline}[4]{}
683 \renewcommand{\cftinsertcode}[2]{}
684 \renewcommand{\cftinserthook}[2]{}
685 \renewcommand{\settocpreprocessor}[2]{}
686 \DeclareRobustCommand{\cftpagenumbersoff}[1]{}
687 \DeclareRobustCommand{\cftpagenumberson}[1]{}

```

### § 572.11 Floats and captions

```

\newfloat  [<1: within] {<2: type} {<3: ext} {<4: capname}
688 \RenewDocumentCommand{\newfloat}{o m m m}{%
689     \IfValueTF{#1}{%
690         {\DeclareFloatingEnvironment[fileext=#3,within=#1,name={#4}]{#2}}{%
691             {\DeclareFloatingEnvironment[fileext=#3,name={#4}]{#2}}{%

```

`newfloat` package automatically creates the `\listof` command for new floats, but `float` does not, so remove `\listof` here in case it is manually created later.

```

692     \cslet{\listof#2s}\relax%
693     \cslet{\listof#2es}\relax%
694 }

```

```
\newlistof  [<within>] {<type>} {<ext>} {<listofname>}
```

Emulated through the `\newfloat` mechanism. Note that `memoir` uses a different syntax than `tocloft` for the name.

```

695 \RenewDocumentCommand{\newlistof}{o m m m}{%
696 {%
697     \IfValueTF{#1}{%
698         {\newlistentry[#1]{#2}{#3}{0}}{%
699             {\newlistentry[#2]{#3}{0}}{%
700                 \namedef{ext@#2}{#3}{%
701                     \ifundefined{c@#3depth}{\newcounter{#3depth}}{%
702                         \setcounter{#3depth}{1}{%
703                             \namedef{#3mark}{}}{%
704                             \namedef{#2}{\listof[#2]{#4}}{%
705                                 \namedef{@cftmake#3title}{}}{%
706                                 \ifundefined{cftbefore#3titleskip}{%
707                                     \expandafter\newlength\csname cftbefore#3titleskip\endcsname{%
708                                         \expandafter\newlength\csname cftafter#3titleskip\endcsname{%
709                                         }{}}{%
710                                         \namedef{cft#3titlefont}{}}{%
711                                         \namedef{cftafter#3title}{}}{%
712                                         \namedef{cft#3prehook}{}}{%
713                                         \namedef{cft#3posthook}{}}{%
714 }

```

```
715 \renewcommand{\setfloatadjustment}[2]{}}
```

Borrowed from the `lwarp` version of `keyfloat`:

```
716 \NewDocumentEnvironment{KFLTmemoir@marginfloat}{O{-1.2ex} m}
717 {%
718   \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}
719   \captionsetup{type=#2}%
720 }
721 {%
722   \endLWR@BlockClassWP%
723 }
724
725 \DeclareDocumentEnvironment{marginfigure}{o}
726   {\begin{KFLTmemoir@marginfloat}{figure}}
727   {\end{KFLTmemoir@marginfloat}}
728
729 \DeclareDocumentEnvironment{margintable}{o}
730   {\begin{KFLTmemoir@marginfloat}{table}}
731   {\end{KFLTmemoir@marginfloat}}
732
733 \renewcommand{\setmarginfloatcaptionadjustment}[2]{}
734 \renewcommand{\setmpjustification}[2]{}
735 \renewcommand*{\mpjustification}{}%
736 \renewcommand*{\setfloatlocations}[2]{}
737 \DeclareDocumentCommand{\suppressfloats}{o}{}%
738 \renewcommand*{\FloatBlock}{}%
739 \renewcommand*{\FloatBlockAllowAbove}{}%
740 \renewcommand*{\FloatBlockAllowBelow}{}%
741 \renewcommand*{\setFloatBlockFor}{}%
742
743 \renewcommand{\captiontitlefinal}[1]{}
744 \renewcommand{\fleitable}{\tablename}%
745 \renewcommand{\flegfigure}{\figurename}%
746 \renewcommand{\flegtocable}{}%
747 \renewcommand{\flegtocfigure}{}%
748
749 \renewcommand{\subcaption}[2][]%
750   \ifblank{#1}{\subfloat[#2]{}{\subfloat[#1][#2]}}%
751
752 }%
753
754 \renewcommand{\contsubcaption}{\ContinuedFloat\subcaption}%
755
756 \LetLtxMacro{\subcaptionref}{\subref}%
757
758 \renewcommand*{\tightsubcaptions}{}%
759 \renewcommand*{\loosesubcaptions}{}%
760
761 \renewcommand*{\subcaptionsize}[1]{}%
762 \renewcommand*{\subcaptionlabelfont}[1]{}%
763 \renewcommand*{\subcaptionfont}[1]{}%
764 \renewcommand*{\subcaptionstyle}[1]{}%
765
766 \renewcommand*{\hangsubcaption}{}%
767 \renewcommand*{\shortsubcaption}{}%
```

```

768 \renewcommand*\normalsubcaption(){}
769
770 \RenewDocumentEnvironment{sidecaption}{o m o}
771 {}
772 {%
773     \IfValueTF{#1}{\caption[#1]{#2}}{\caption{#2}}%
774     \IfValueT{#3}{\label{#3}}%
775 }
776
777 % \newlength{\sidecapwidth}
778 % \newlength{\sidecapsep}
779 \renewcommand*\setsidecaps[2]{}%
780 \renewcommand*\sidecapmargin[1]{}%
781 % \newif\ifscapmangleft
782 \scapmangleftfalse
783 \renewcommand*\setsidecappos[1]{}%
784
785 \RenewDocumentEnvironment{sidecontcaption}{m o}
786 {}
787 {%
788     \ContinuedFloat%
789     \caption{#1}%

```

Without `\@capttype`, the section is referred to instead.

```

790     \IfValueT{#2}{\label[\@capttype]{#2}}%
791 }

```

`\sidenamedlegend` does not appear to use the `toc` argument.

```

792 \renewenvironment{sidenamedlegend}[2][]{
793     \begin{center}
794         \@nameuse{@capttype name}\CaptionSeparator#2
795     \end{center}
796 }
797 {}
798
799 \renewenvironment{sidelegend}[1]
800 {\begin{center}
801     #1
802
803 }
804 {\end{center}}
805
806 \renewcommand*\sidecapstyle{}
807 \renewcommand*\overridescapmargin[1]{}%
808 % \newlength{\sidecappraise}
809 \renewcommand*\sidecapfloatwidth{\linewidth}
810
811 \LetLtxMacro\ctabular\tabular
812 \LetLtxMacro\endctabular\endtabular
813
814 \renewcommand{\autorows}[5][]%
815     #5%
816 }

```

```
817
818 \renewcommand{\autocols}[5][]{%
819     #5%
820 }

821 \renewcommand*{\feetabovefloat}{}%
822 \renewcommand*{\feetbelowfloat}{}%
823 \renewcommand*{\feetatbottom}{}%
824
825 \renewcommand*{\verbfootnote}[2][]{%
826     \PackageError{l warp,memoir}%
827     {Verbatim footnotes are not yet supported by l warp.}%
828     {This may be improved some day.}%
829 }
830
831 \renewcommand*{\plainfootnotes}{}%
832 \renewcommand*{\twocolumnfootnotes}{}%
833 \renewcommand*{\threecolumnfootnotes}{}%
834 \renewcommand*{\paragraphfootnotes}{}%
835 \renewcommand*{\footfudgefiddle}{}%
836
837 \renewcommand*{\newfootnoteseries}[1]{%
838     \PackageError{l warp,memoir}%
839     {Memoir footnote series are not yet supported by l warp.}%
840     {This may be improved some day.}%
841 }
842
843 \renewcommand*{\plainfootstyle}[1]{}%
844 \renewcommand*{\twocolumnfootstyle}[1]{}%
845 \renewcommand*{\threecolumnfootstyle}[1]{}%
846 \renewcommand*{\paragraphfootstyle}[1]{}%
847
848 \renewcommand*{\footfootmark}{}%
849 \renewcommand*{\footmarkstyle}[1]{}%
850
851 % \newlength{\footmarkwidth}
852 % \newlength{\footmarksep}
853 % \newlength{\footparindent}
854
855 \renewcommand*{\foottextfont}{}%
856
857 \renewcommand*{\marginparmargin}[1]{}%
858 \renewcommand*{\sideparmargin}[1]{}%
859
860 \LetLtxMacro{\sidepar}{\marginpar}
861 \renewcommand*{\sideparfont}{}%
862 \renewcommand*{\sideparform}{}%
863 \LWR@providelength{\sideparvshift}%
864
865 \renewcommand*{\parnopar}{}%
866
867 \renewcommand{\sidebar}[1]{\begin{quote}#1\end{quote}}%
868 \renewcommand*{\sidebarmargin}[1]{}%
```

## § 572.12 Page notes

```

869 \renewcommand*\{\sidebarfont\}{}%
870 \renewcommand*\{\sidebarform\}{}%
871 % \newlength{\sidebarhsep}%
872 % \newlength{\sidebarvsep}%
873 % \newlength{\sidebarwidth}%
874 % \newlength{\sidebartopsep}%
875 \renewcommand{\setsidebarheight}[1]{}%
876 \renewcommand*\{\setsidebars}[6]{}%
877 \renewcommand*\{\footnotesatfoot}{}%
878 \renewcommand*\{\footnotesinmargin}{}%
879
880 \LetLtxMacro{\sidefootnote}{\footnote}
881 \LetLtxMacro{\sidefootnotemark}{\footnotemark}
882 \LetLtxMacro{\sidefootnotetext}{\footnotetext}
883
884 \renewcommand*\{\sidefootmargin}[1]{}%
885 % \newlength{\sidefoothsep}%
886 % \newlength{\sidefootvsep}%
887 % \newlength{\sidefootwidth}%
888 % \newlength{\sidefootadjust}%
889 % \newlength{\sidefootheight}%
890 \renewcommand*\{\setsidefootheight}[1]{}%
891 % \renewcommand*\{\sidefootfont\}{}% in docs but not in the package
892 \renewcommand*\{\setsidefeet}[6]{}%
893 \renewcommand*\{\sidefootmarkstyle}[1]{}%
894 \renewcommand*\{\sidefoottextfont\}{}%
895 \renewcommand*\{\sidefootform\}{}%
896
897 \renewcommand*\{\continuousnotenums\}{\pncontopttrue}% from pagenote
898 \renewcommand*\{\notepageref\}{}%
899 \renewcommand*\{\prenotetext\}{}%
900 \renewcommand*\{\postnotetext\}{}%
901 \renewcommand*\{\idtextinnotes}[1]{}%
902 \renewcommand*\{\printpageinnotes}[1]{}%
903 \renewcommand*\{\printpageinnoteshyperref}[1]{}%
904 \renewcommand*\{\foottopagenote\}{}%
905 \renewcommand*\{\pagetofootnote\}{}%

```

### § 572.13 Decorative text

```

906 \renewcommand*\{\epigraphposition\}[1]{}%
907 \renewcommand*\{\epigraphtextposition\}[1]{}%
908 \renewcommand*\{\epigraphsourceposition\}[1]{}%
909 \renewcommand*\{\epigraphfontsize\}[1]{}%
910 \renewcommand*\{\epigraphforheader\}[2]{}%
911 \renewcommand*\{\epigraphpicture\}{}%

```

### § 572.14 Poetry

```

912 \renewcommand*\{\vinphantom\}{}%
913 \renewcommand*\{\vleftofline\}[1]{\#1}%
914 % \let\linenumberfrequency\poemlines
915 % \renewcommand*\{\linenumberfont\}[1]{}%
916
917 \DeclareDocumentCommand{\PoemTitle}{s o o m}{%

```

```

918     \IfValueTF{#2}%
919         {\poemtitle[#2]{#4}}%
920         {\poemtitle{#4}}%
921     }
922
923 \renewcommand*\{\NumberPoemTitle}{}%
924 \renewcommand*\{\PlainPoemTitle}{}%
925 \renewcommand*\{\poemtitlepstyle}{}%
926 \renewcommand*\{\poemtitlestarmark}[1]{}%
927 \renewcommand*\{\poemtitlestarpstyle}{}%
928 \renewcommand*\{\PoemTitleheadstart}{}%
929 \renewcommand*\{\printPoemTitlenum}{}
930 \renewcommand*\{\printPoemTitlenum}{}
931 \renewcommand*\{\afterPoemTitlenum}{}
932 \renewcommand*\{\printPoemTitletitle}[1]{}%
933 \renewcommand*\{\afterPoemTitle}{}%
934 \newlength{\midpoemtitleskip}%
935 \renewcommand*\{\PoemTitlenumfont}{}%
936 \renewcommand*\{\PoemTitlefont}{}%

```

### § 572.15 Boxes, verbatims and files

```

937 \renewenvironment{qframe}{\framed}{\endframed}%
938 \renewenvironment{qshade}{\shaded}{\endshaded}%

```

Use the `comment` package:

```

939 \renewcommand*\{\commentsoff}[1]{\includecomment{#1}}%
940 \renewcommand*\{\commentson}[1]{\excludecomment{#1}}%
941 \LetLtxMacro\renewcomment\commentson
942
943 \renewcommand*\{\setverbatimfont}[1]{}%
944 \renewcommand*\{\tabson}[1]{}%
945 \renewcommand*\{\tabsoff}{}%
946 \renewcommand*\{\wrappingon}{}%
947 \renewcommand*\{\wrappingoff}{}%
948 \renewcommand*\{\verbatimindent}{}%
949 \renewcommand*\{\verbatimbreakchar}[1]{}%
950 \DefineVerbatimEnvironment{fboxverbatim}{Verbatim}{frame=single}%

```

`boxedverbatim` is already defined by `moreverb`. `boxedverbatim*` does not appear to work at all, even in a minimal print `memoir` document.

```

951 \renewcommand*\{\bvbox}{}%
952 \renewcommand*\{\bvtopandtail}{}%
953 \renewcommand*\{\bvsides}{}%
954 \renewcommand*\{\nobvbox}{}%
955 % \newlength\bvboxsep
956 \renewcommand*\{\bvtoprulehook}{}%
957 \renewcommand*\{\bvtopmidhook}{}%
958 \renewcommand*\{\bvendrulehook}{}%
959 \renewcommand*\{\byleftsidehook}{}%
960 \renewcommand*\{\bvrightrightsidehook}{}%
961 \renewcommand*\{\bypagetrue}{}%

```

---

```

962 \renewcommand*\{bvperpagefalse}{}%
963 \renewcommand{\bvtopofpage}[1]{}%
964 \renewcommand{\bvendofpage}[1]{}%
965 \renewcommand*\{linenumberfrequency}[1]{}%
966 \renewcommand*\{resetbvlinenumber}{}%
967 \renewcommand*\{setbvlinenums}[2]{}%
968 \renewcommand*\{linenumberfont}[1]{}%
969 \renewcommand*\{bvnumbersinside}{}%
970 \renewcommand*\{bvnumbersoutside}{}%

```

## § 572.16 Cross referencing

```

971 \renewcommand*\{\\ref}[1]{\\cref{#1}}%
972 \renewcommand*\{\\tref}[1]{\\cref{#1}}%
973 \renewcommand*\{\\pref}[1]{\\cpageref{#1}}%
974 \renewcommand*\{\\Aref}[1]{\\cref{#1}}%
975 \renewcommand*\{\\Bref}[1]{\\cref{#1}}%
976 \renewcommand*\{\\Pref}[1]{\\cref{#1}}%
977 \renewcommand*\{\\Sref}[1]{\\cref{#1}}%
978 \renewcommand*\{\\figurerefname}{Figure}%
979 \renewcommand*\{\\tablerefname}{Table}%
980 \renewcommand*\{\\pagerefname}{page}%
981 \renewcommand*\{\\bookrefname}{Book~}%
982 \renewcommand*\{\\partrefname}{Part~}%
983 \renewcommand*\{\\chapterrefname}{Chapter~}%
984 \renewcommand*\{\\sectionrefname}{\\S}%
985 \renewcommand*\{\\appendixrefname}{Appendix~}%
986 \LetLtxMacro\\titleref\\nameref%
987 \renewcommand*\{\\headnameref}{}%
988 \renewcommand*\{\\tocnameref}{}%
989 %
990 \providecounter{LWR@currenttitle}%
991 %
992 \renewcommand*\{\\currenttitle}{%
993     \\addtocounter{LWR@currenttitle}{1}%
994     \\label{currenttitle\\arabic{LWR@currenttitle}}%
995     \\nameref{currenttitle\\arabic{LWR@currenttitle}}%
996 }%
997 %
998 \renewcommand*\{\\theTitleReference}[2]{}%
999 \renewcommand*\{\\namerefon}{}%
1000 \renewcommand*\{\\namerefoff}{}%

```

## § 572.17 Back matter

Redefined to write the LWR@autoindex counter instead of page. Note that memoir has two versions, depending on the use of hyperref.

```

1001 \\AtBeginDocument{%
1002 %
1003 \\def\\@wrindexhyp#1||\\{%
1004     \\addtocounter{LWR@autoindex}{1}%
1005     \\LWR@new@label{LWRindex-\\arabic{LWR@autoindex}}%
1006 %     \\ifshowindexmark\\@showidx{#1}\\fi%
1007     \\protected@write\\@auxout{}%

```

```

1008      {\string\@@wrindexm{\@idxfile}{#1}{\arabic{LWR@autoindex}}}}%
1009      \endgroup
1010      \@esphack}%

```

\specialindex behaves like a regular \index, pointing to where \specialindex is used. If \specialindex is used inside a figure or table after the \caption, then the hyperlink will be given the name of that particular figure or table.

```

1011 \def\@wrspindexhyp#1|||\{%
1012     \addtocounter{LWR@autoindex}{1}%
1013     \LWR@new@label{\LWRindex-\arabic{LWR@autoindex}}%
1014 %     \ifshowindexmark\@showidx{#1}\fi
1015     \protected@write\@auxout{}{%
1016     {%
1017 %         \string\@@wrindexm{\@idxfile}{#1}{\@nameuse{the\@sptheidx}}}}%
1018         \string\@@wrindexm{\@idxfile}{#1}{\arabic{LWR@autoindex}}}}%
1019     }%
1020     \endgroup
1021     \@esphack}%
1022
1023 }% \AtBeginDocument

```

Patched to use \_html filename and \BaseJobname:

```

1024 \catcode`\_=12%
1025 \renewcommand*{\makeindex}[1][\BaseJobname]{%
1026     \if@filesw
1027         \def\gindex{\@bsphack%
1028             \@ifnextchar [{\@index}{\@index[\BaseJobname]}}%
1029         \def\specialindex{\@bsphack\@spindex}%
1030         \makememindexhook
1031         \expandafter\newwrite\csname #1@idxfile\endcsname
1032         \expandafter\immediate\openout \csname #1@idxfile\endcsname #1_html.idx\relax
1033         \typeout{Writing index file #1_html.idx }%
1034     \fi}
1035 \catcode`\_=8%

```

Patched to use \_html filename and \BaseJobname. This will later be patched by the lwarp core.

```

1036 \catcode`\_=12%
1037 \renewcommand{\printindex}[1][\BaseJobname]{\@input{\#1_html.ind}}
1038 \catcode`\_=8%
1039 \DeclareDocumentCommand{\newblock}{}{%
1040 %
1041 \renewcommand*{\showindexmarks}{}%
1042 \renewcommand*{\hideindexmarks}{}%
1043 %
1044 \renewcommand*{\xindyindex}{}%

```

## § 572.18 Miscellaneous

```

1045 \renewcommand*\{changemarks}{}  

1046 \renewcommand*\{nochangemarks}{}  

1047 \renewcommand*\{added}[1]{}  

1048 \renewcommand*\{deleted}[1]{}  

1049 \renewcommand*\{changed}[1]{}  

1050  

1051 \renewcommand*\{showtrimsoff}{}  

1052 \renewcommand*\{showtrimson}{}  

1053 \renewcommand*\{trimXmarks}{}  

1054 \renewcommand*\{trimLmarks}{}  

1055 \renewcommand*\{trimFrame}{}  

1056 \renewcommand*\{trimNone}{}  

1057 \renewcommand*\{trimmarkscolor}{}  

1058 \renewcommand*\{trimmarks}{}  

1059 \renewcommand*\{tmarktl}{}  

1060 \renewcommand*\{tmarktr}{}  

1061 \renewcommand*\{tmarkbr}{}  

1062 \renewcommand*\{tmarkbl}{}  

1063 \renewcommand*\{tmarktm}{}  

1064 \renewcommand*\{tmarkmr}{}  

1065 \renewcommand*\{tmarkbm}{}  

1066 \renewcommand*\{tmarkml}{}  

1067 \renewcommand*\{trimmark}{}  

1068 \renewcommand*\{quarkmarks}{}  

1069 \renewcommand*\{registrationColour}[1]{}  

1070  

1071 \renewcommand*\{leavespergathering}[1]{}  

1072  

1073 \renewcommand*\{noprelistbreak}{}  

1074  

1075 \renewcommand*\{cleartorecto}{}  

1076 \renewcommand*\{cleartoverso}{}  

1077  

1078 \renewenvironment{vplace}[1][]{}{}  


```

## § 572.19 ccaption emulation

```

1079 \renewcommand*\{captiondelim}[1]{\renewcommand*\{CaptionSeparator}{#1}}  

1080 \renewcommand*\{captionnamefont}[1]{}  

1081 \renewcommand*\{captiontitlefont}[1]{}  

1082 \renewcommand*\{flushleftright}{}  

1083 \renewcommand*\{centerlastline}{}  

1084 \renewcommand*\{captionstyle}[2][][]  

1085 \DeclareDocumentCommand{\captionwidth}{m}{}  

1086 \renewcommand*\{changecaptionwidth}{}  

1087 \renewcommand*\{normalcaptionwidth}{}  

1088 \renewcommand*\{hangcaption}{}  

1089 \renewcommand*\{indentcaption}[1]{}  

1090 \renewcommand*\{normalcaption}{}  

1091 \renewcommand{\precaption}[1]{}  

1092 \renewcommand{\postcaption}[1]{}  

1093 \renewcommand{\midbicaption}[1]{}  

1094 \renewcommand{\contcaption}[1]{%  

1095 % \ContinuedFloat%

```

```
1096 % \caption{#1}%
1097 \begin{LWR@figcaption}% later becomes \caption*
1098 \LWR@isolate{@nameuse{@capttype name}}~%
1099 \thechapter.\the\value{@capttype}\CaptionSeparator\LWR@isolate{#1}%
1100 \end{LWR@figcaption}%
1101 }

1102 \newlength{\abovelegendskip}
1103 \setlength{\abovelegendskip}{0.5\baselineskip}
1104 \newlength{\belowlegendskip}
1105 \setlength{\belowlegendskip}{\abovelegendskip}
```

The extra \\ here forces a <br> in HTML when \legend is used in a \marginpar.

```
1106 \renewcommand{\legend}[1]{\begin{center}#1\\\end{center}}
1107
1108 \renewcommand{\namedlegend}[2][]{%
1109   \begin{center}
1110     @nameuse{fleg@\capttype}\CaptionSeparator#2\\
1111   \end{center}
1112   @nameuse{flegtoc@\capttype}{#1}
1113 }
1114
1115 \renewcommand{\newfixedcaption}[3][\caption]{%
1116   \renewcommand{#2}{\def@\capttype{#3}{#1}}
1117 \renewcommand{\renewfixedcaption}[3][\caption]{%
1118   \renewcommand{#2}{\def@\capttype{#3}{#1}}
1119 \renewcommand{\providefixedcaption}[3][\caption]{%
1120   \providecommand{#2}{\def@\capttype{#3}{#1}}
1121
1122 \renewcommand{\bitwounumcaption}[6][]{%
1123   \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
1124   \addtocounter{@capttype}{-1}%
1125   \begingroup%
1126   \csdef{@capttype name}{#4}%
1127   \ifblank{#5}{\caption{#6}}{\caption[#5]{#6}}%
1128   \endgroup%
1129   \ifblank{#1}{}{\label{#1}}%
1130 }
1131
1132 \LetLtxMacro\bionenumcaption\bitwounumcaption% todo
1133
1134 \renewcommand{\bicaption}[5][]{%
1135   \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
1136   \begin{LWR@figcaption}% later becomes \caption*
1137   \LWR@isolate{#4} % space
1138   \thechapter.\the\value{@capttype}\CaptionSeparator\LWR@isolate{#5}%
1139   \end{LWR@figcaption}%
1140   \ifblank{#1}{}{\label{#1}}%
1141 }
1142
1143 \renewcommand{\bicontcaption}[3]{%
1144   \contcaption{#1}%
1145   \begingroup%
1146   \csdef{@capttype name}{#2}%
1147   \contcaption{#3}%
1148 }
```

```

1148     \endgroup%
1149 }

1150 % only in ccaption, not in memoir:
1151 % \LetLtxMacro\longbitwonumcaption\bitwonumcaption%
1152 % \LetLtxMacro\longbionenumcaption\bitwonumcaption%
1153 % \LetLtxMacro\longbicaption\bicaption%
1154
1155 \RenewDocumentCommand{\subtop}{O{} O{} m}{%
1156     \subfloat[#1][#2]{#3}%
1157 }
1158
1159 \RenewDocumentCommand{\subbottom}{O{} O{} m}{%
1160     \subfloat[#1][#2]{#3}%
1161 }
1162
1163 \renewcommand{\contsubtop}{%
1164     \ContinuedFloat\addtocounter{@cattyp}{1}%
1165     \subtop%
1166 }
1167
1168 \renewcommand{\contsubbottom}{%
1169     \ContinuedFloat\addtocounter{@cattyp}{1}%
1170     \subbottom%
1171 }
1172
1173 \renewcommand{\subconcluded}{}
1174
1175 \let\contsubtable\contsubtop
1176 \let\contsubfigure\contsubbottom

1177 \newcommand{\newfloatentry}[4][\empty]{TODO: newfloatentry}
1178 \newcommand{\newfloatlist}[5][\empty]{TODO: newfloatlist}
1179 \newcommand{\newfloatenv}[4][\empty]{TODO: newfloatenv}
1180 \DeclareRobustCommand{\newfloatpagesoff}[1]{}
1181 \DeclareRobustCommand{\newfloatpageson}[1]{}
1182 \newcommand{\setnewfloatindents}[3]{}

```

### § 572.20 Final patchwork

```

1183 \newlistof{tableofcontents}{toc}{\contentsname}
1184 \newlistof{listoffigures}{lof}{\listfigurename}
1185 \newlistof{listoftables}{lot}{\listtablename}

```

File 473 **lwarp-common-multimedia.sty**

### § 573 Package **common-multimedia**

Pkg lwarp-common-multimedia Common code for multimedia, movie15, and media9.

The packages **multimedia**, **movie15**, and **media9** are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediopath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an “embedded” URL with .../embed/... instead of .../v/...

**for HTML output:**

```
1 \ProvidesPackage{lwarp-common-multimedia}[2019/04/22]

2 \RequirePackage{xkeyval}
3
4 \define@key{LWR@multimedia}{width}{\setlength{\LWR@multimedia@width}{#1}}
5 \define@key{LWR@multimedia}{height}{\setlength{\LWR@multimedia@height}{#1}}
6 \define@key{LWR@multimedia}{totalheight}{\setlength{\LWR@multimedia@height}{#1}}

7 \newlength{\LWR@multimedia@width}
8 \newlength{\LWR@multimedia@height}
9 \newlength{\LWR@multimedia@maxdimension}
```

\LWR@multimedia@printsize      Proportional to \linewidth and the viewport's smaller dimension. This scales each object such that it will always fit on the screen, even if a tall or wide object inside a tall or wide viewport.

```
10 \newcommand*\LWR@multimedia@printsize{%
11     \setlength{\LWR@multimedia@maxdimension}{%
12         \maxof%
13             {\linewidth}}%
```

```

14           {\maxof{\LWR@multimedia@width}{\LWR@multimedia@height}}%
15       }%
16   \setlength{\LWR@multimedia@maxdimension}{1.1\LWR@multimedia@maxdimension}%
17   \ifdimgreater{\LWR@multimedia@width}{0pt}{%
18       width:%
19       \LWR@printpercentlength%
20       {\LWR@multimedia@width}%
21       {\LWR@multimedia@maxdimension}vmin ; % space
22   }{%
23   \ifdimgreater{\LWR@multimedia@height}{0pt}{%
24       height:%
25       \LWR@printpercentlength%
26       {\LWR@multimedia@height}%
27       {\LWR@multimedia@maxdimension}vmin ; % space
28   }{%
29 }

```

\LWR@multimedia@fileAV {⟨poster text⟩} {⟨filename⟩} {⟨audio/video⟩} {⟨mimetype⟩}

Creates a video or audio from a file. The 2019/10 update of the L<sup>A</sup>T<sub>E</sub>X kernel may cause extra quotes to be added in the filenames. They are removed here.

```

30 \newcommand*{\LWR@multimedia@fileAV}[4]{%
31 \IfFileExists{#2}{% also sets \@filef@und
32 \StrSubstitute[100]{\@filef@und}{""}[\LWR@parsedfilename]%

```

The container <div> is sized as desired.

```

33 \ifstreq{\#3}{audio}{%
34     \begin{BlockClass}{\Vviewport}
35 }{%
36     \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{\Vviewport}
37 }

```

Paragraph tags are unnecessary for the A/v tags.

```
38 \LWR@stopars
```

The A/v element is 100% of the container.

```

39 \LWR@htmltag{%
40     #3\ % space
41     \ifstreq{\#3}{audio}{%
42         width=\textquotedbl{}100\%\textquotedbl\ % space
43         height=\textquotedbl{}100\%\textquotedbl\ % space
44     }%
45     controls%
46 }\LWR@orignewline

```

The file source and type:

```

47 \LWR@htmltag{%
48     source % space
49     src=\textquotedbl%
50     \LWR@parsedfilename\unskip\textquotedbl\ % space
51     type=\textquotedbl{}#4\textquotedbl}

```

The poster text inside paragraph tags, along with a reference to the file.

```
52 \LWR@startpars
```

```
53      \href{\LWR@parsedfilename}{#1}
54      \LWR@stopars
Finish.
55      \LWR@htmltag{/#3}\LWR@orignewline
56      \end{BlockClass}
57 }{%
58      \PackageError{lwarp-common-multimedia}
59      {File '#2' not found}
60      {Perhaps an incorrect path?}
61 }%
62 }
```

\LWR@multimedia@httpAV {⟨poster text⟩} {⟨filename⟩} {⟨audio/video⟩} {⟨mimetype⟩}

Creates a video or audio from a URL link.

```
63 \newcommand*{\LWR@multimedia@httpAV}[4]{%
```

The container <div> is sized as desired.

```
64      \ifstreq{\#3}{audio}{%
65          \begin{BlockClass}{AVviewport}
66      }{%
67          \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{AVviewport}
68      }
```

Paragraph tags are unnecessary for the A/v tags.

```
69      \LWR@stopars
```

The A/v element is 100% of the container.

```
70      \LWR@htmltag{%
71          #3\ % space
72          \ifstreq{\#3}{audio}{%
73              width=\textquotedbl{}100\%\textquotedbl\ % space
74              height=\textquotedbl{}100\%\textquotedbl\ controls%
75          }%
76      }\LWR@orignewline
```

The file source and type:

```
77      \LWR@htmltag{%
78          source % space
79          src=\textquotedbl{}\textquotedbl\ % space
80          type=\textquotedbl{}\textquotedbl{}}
```

The poster text inside paragraph tags, along with a reference to the URL.

```
81      \LWR@startpars
82      \href{#2}{#1}
83      \LWR@stopars
```

Finish.

```
84      \LWR@htmltag{/#3}\LWR@orignewline
85      \end{BlockClass}
86 }
```

---

\LWR@multimedia@AV {⟨poster text⟩} {⟨filename⟩} {⟨audio/video⟩} {⟨mimetype⟩}

Creates an audio or video from a file or a URL.

```

87 \newcommand*{\LWR@multimedia@AV}[4]{%
88     \IfBeginWith{#2}{http}%
89         {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
90     {%
91         \IfBeginWith{#2}{HTTP}%
92             {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
93             {\LWR@multimedia@fileAV{#1}{#2}{#3}{#4}}%
94     }%
95 }
```

\LWR@multimedia@embed {⟨poster text⟩} {⟨URL or filename⟩} {⟨mime type⟩}

Embeds multimedia of an arbitrary type. The poster text is not used, as it would appear along with the video if the <embed> element is supported.

```

96 \newcommand*{\LWR@multimedia@embed}[3]{%
97     \begin{BlockClass}[width:100\%]{AVviewport}%
98     \LWR@stoppars
99         \LWR@htmltag{%
100             embed % space
101             \ifblank{#3}{\type=\textquotedbl#3\textquotedbl\ }%
102             style=\textquotedbl\LWR@multimedia@printsize\ margin:auto\textquotedbl\ % space
103             src=\textquotedbl#2\textquotedbl\ % space
104         }%
105     \LWR@startpars
106     \end{BlockClass}
107 }
```

Error message if the comment character is used among the arguments of \LWR@multimediac.

\LWR@multimedia@percenterror

```

108 \newcommand*{\LWR@multimedia@percenterror}{{%
109     \PackageError{lwarp-media9}{%
110         \%
111         Do not use a percent comment
112         between\MessageBreak
113         \protect\includemedia\space arguments%
114     }%
115     {Percent is changed to a regular character to allow its use inside a URL.}%
116 }}
```

\LWR@multimediac [⟨options⟩] {⟨poster text⟩} {⟨filename⟩}

Creates multimedia. Examines the file extension to determine the type. If not a supported type, creates an embedded object if it has a URL. If neither, create a link to the unsupported object.

```
117 \newcommand*{\LWR@multimediac}[3][]{%
```

Error if the percent character appears among the arguments. This could happen since the comment character has been temporarily disabled, for use in a URL.

```

118     \if#1@\percentchar\LWR@multimedia@percenterror\fi%
119     \if#2@\percentchar\LWR@multimedia@percenterror\fi%
```

```
120 \if#3@percentchar\LWR@multimedia@percenterror\fi%
```

Paragraph handling:

```
121 \LWR@stoppars%
```

Record the desired size.

```
122 \setlength{\LWR@multimedia@width}{0pt}%
123 \setlength{\LWR@multimedia@height}{0pt}%
124 \setkeys*{\LWR@multimedia}{#1}%
```

If a known A/v type, create an HTML5 <video> or <audio>.

```
125 \IfEndWith{#3}{.mp4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
126 \IfEndWith{#3}{.MP4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
127 \IfEndWith{#3}{.mp3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
128 \IfEndWith{#3}{.MP3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
```

If an arbitrary URL, embed it.

```
129 \IfBeginWith{#3}{http}{\LWR@multimedia@embed{#2}{#3}{}}{%
130 \IfBeginWith{#3}{HTTP}{\LWR@multimedia@embed{#2}{#3}{}}{%
131 \IfBeginWith{#3}{ftp}{\LWR@multimedia@embed{#2}{#3}{}}{%
132 \IfBeginWith{#3}{FTP}{\LWR@multimedia@embed{#2}{#3}{}}{%
```

If unknown, create a link to it.

```
133 \href{#3}{#2}%
134 }}}}}}
```

Paragraph handling:

```
135 \LWR@startpars%
136 \endgroup%
137 }
```

Catcodes which may appear in a URL.

```
138 \newrobustcmd*{\LWR@multimedia}{%
139 \begingroup%
140 \LWR@linkmediacatcodes%
141 \LWR@multimediacatcodes%
142 }
```

# Change History

§ 574 Chg Hist

---

For the most recent changes, see page 1139.

v0.10	General: 2016/03/08 Initial version . . . 1	Test Suite: Assigned cleveref name for Test Float. . . . . 1	
v0.11	General: 2016/03/11 . . . . . 1	Test Suite: Floatrow . . . . . 1	
	Added section: Operating-System portability. . . . . 217		
	Added section: Selecting the operating system. . . . . 117		
	Test Suite: MS-WINDOWS in README.txt . . . . . 1		
	Test Suite: Images and index in README.txt . . . . . 1		
v0.12	\LWR@newhtmlfile: Bugfix: toc with numbered files. . . . . 369	General: 2016/04/06 . . . . . 1	
	General: 2016/03/14 . . . . . 1	Added. . . . . 746	
	Global: Uses \p@{type} in float captions. . . . . 1	Ampersand (&): Fixed handling when passed as an argument. . . . . 422	
	Test Suite: Sub-figures . . . . . 1	Docs: Added warning icons for items needing special attention. . . . . 198	
v0.13	\CaptionSeparator: Fix for newer babel package. . . . . 492	Docs: Clarify print/HTML output. . . . . 117	
	\LWR@LwarpStart: \up and \fup . . . . . 387	Docs: Moved the supported features table to the introduction. . . . . 68	
	General: 2016/03/24 . . . . . 1	Files: lwarp_formal.css added. . . . . 1	
	Fix dollar-redefined bug for newer package. . . . . 1006	Fix: steps counter . . . . . 746	
	Removed package: subfig . . . . . 1	Fixed & handling. . . . . 744	
	Test Suite: Ordinals, Subcaption . . . . . 1	Test Suite: test_suite_formal.css file added. . . . . 1	
v0.14	\LWR@htmlsectionfilename: Fix: Links to home page. . . . . 328	v0.16	General: 2016/04/11 . . . . . 1
	General: 2016/03/31 . . . . . 1	\titlingpage: Improved print-output spacing. . . . . 395	
	floatrow: Added. . . . . 742	xfrac: Adjusted for the use of any font. . . . . 1066	
	Docs: Commands for a successful HTML conversion. . . . . 121	Added XeLaTeX, LuaLaTeX support. . . . . 199	
	Docs: Commands into a warpprint environment. . . . . 118	Docs: Font and UTF-8 support. . . . . 101	
	Docs: Newclude limitations. . . . . 169	Docs: Moved location of \usepackage{lwarp}. . . . . 104	
	Docs: Table: Cross-referencing data structures. . . . . 476	Docs: Text not converting. . . . . 190	
	Docs: Table: Float data structures. . . . . 488	Lwarp no longer selects fonts. . . . . 101, 227	
	Docs: Trademarks section. . . . . 195	Removed package: suffix . . . . . 1	
	Docs: Troubleshooting cross-references. . . . . 190	Test Suite: Improved titlingpage. . . . . 395	
		Test Suite: Lwarp no longer selects fonts. . . . . 1	
		Test Suite: Supports XeLaTeX, LuaLaTeX. . . . . 1	
v0.17	\LWR@htmlsectionfilename: Fix: Links when entire doc is one HTML page. . . . . 328	v0.18	\LWR@htmlsectionfilename: Fix: Links when entire doc is one HTML page. . . . . 328
	General: 2016/04/14 . . . . . 1	General: 2016/04/14 . . . . . 1	
	mdframed: Added. . . . . 839	mdframed: Added. . . . . 839	

Test Suite: Fix: Print-version front-matter page numbers. . . . .	1	\LWR@filestart: l warp_mathjax.txt loaded. . . . .	383
Test Suite: Mdframed . . . . .	1	\LWR@minipagestartpars: Suppresses paragraph tags between minipages. . . . .	583
<b>v0.18</b>		\LWR@subsingleDollar: MATHJAX support. . . . .	519
\LWR@myshorttoc: Reorganize \HomeHTMLFilename logic. . . . .	496	\LateximageFontSizeName: Add: User-adjustable math/latexitimage font size. . . . .	536
\LWR@newhtmlfile: sideroc after title, improving responsive design. . . . .	368	\hspace: Fix: \hspace length computations. . . . .	584
\LWR@requesttoc: Reorganize \HomeHTMLFilename logic. . . . .	389	\minipagefullwidth: Added: No width tag for the next minipage in HTML. . . . .	560
\LWR@subhyperref: Improved HTML output linebreaks. . . . .	484	\warpHTMLonly: Added. . . . .	226
\LWR@subhyperrefclass: Improved HTML output linebreaks. . . . .	485	\warpprintonly: Replaces \rowprintedonly. . . . .	226
\LWR@subinlineimage: Suppress extra space. . . . .	486	\xfracHTMLfontsize: Added. . . . .	1065
\hspace: \hspace supported. . . . .	584	<b>General: 2016/05/19</b> . . . . .	1
graphics: Add: svgz file extension. . . . .	773	css for table note item. . . . .	1003
graphics: Fix: \linewidth, \textwidth, \textheight inside a minipage. . . . .	773	MATHJAX support added. . . . .	524, 530, 531
graphics: Improved HTML output linebreaks. . . . .	773	multirow: Added optional args. . . . .	868
graphics: em, ex, %, px dimensions preserved. . . . .	773	Adapts to tikz version. . . . .	1006
File: l warp.css: Improved toc outline display. . . . .	1	Avoids MATHJAX. . . . .	512
Files: l warp.css and l warp_formal.css: Improved responsive design. . . . .	1	cleveref: Loaded \AtEndPreamble. . . . .	555
Microtype disabled during HTML generation . . . . .	227	Docs: Math options. . . . .	104
PDF Unicode input characters. . . . .	213	Docs: Table: Cross-referencing data structures, updated. . . . .	476
Test Suite: Verse package . . . . .	1	File: l warp.css: \noteitemheader added. . . . .	1
lateximage: pdfcrop: --hires added. . . . .	539	Introduction: MATHJAX support mentioned. . . . .	65
Reorganize \HomeHTMLFilename logic. . . . .	539	Options: mathsvg and mathjax . . . . .	221
Suppress extra space. . . . .	539	Supports colored \rule. . . . .	1056
verse: Supports verse, memoir packages. . . . .	1043	titles: null \pagestyle and \thispagestyle for HTML . . . . .	1007
minipage: Fix: \linewidth, \textwidth, \textheight inside a minipage. . . . .	560	<b>v0.20</b>	
<b>v0.19</b>		\BlockClassSingle: Renamed from "LWR@htmldivclassline". . . . .	341
\HTMLFilename: Docs: Escape filename underscores. . . . .	327	\HTMLDescription: Added \NewHTMLdescription. (Renamed in v0.30.) . . . . .	352
\HomeHTMLFilename: Docs: Escape filename underscores. . . . .	328	\HTMLfilename: No longer escape underscores. . . . .	327
\LWR@LwarpStart: Enabled \\ equal to \newline. . . . .	386	\HomeHTMLfilename: No longer escape underscores. . . . .	328
\LWR@doequation: MATHJAX support. . . . .	526	\InlineClass: Renamed from "inlineclass". . . . .	341
\LWR@doubledollar: MATHJAX support. . . . .	520	\LWR@LwarpStart: Fix: math cross references. . . . .	387
		\LWR@closeparagraph: \unskip extra spaces. . . . .	345

No break tags in the start/end of a tabular. . . . .	345
\LWR@endofline: Fix: \\ . . . . .	583
\LWR@filestart: Adds meta description. . . . .	383
\LWR@htmldivclass: Added optional style. . . . .	339
\LWR@htmlelementclass: Added optional style. . . . .	339
\LWR@htmlsectionfilename: HTMLfilename: removed additional trailing ' ', and may be empty. . . . .	328
Sections called "Index" or "index" have an underscore prepended to their filenames if no prefix. . . . .	328
\LWR@longtabledatacaptiontag: Fix: Pars in captions. . . . .	459
\LWR@section: Combined higher-level sections together into files. . . . .	375
\LWR@setOSWindows: Auto-detects operating system. . . . .	219
\LWR@subhtmlelementclass: Factored code. . . . .	339
\SetHTMLFileName: Add: Control file numbers. . . . .	328
\cpagerefFor: User-redefinable word for page references. . . . .	556
\dotfill: Inserts an ellipsis. . . . .	583
\hfill: Inserts a \quad. . . . .	582
\hrulefill: Inserts a short rule. . . . .	583
\hspace: Add: Supports HTML thin breakable space. . . . .	584
\hyperindexref: Print mode provided in case hyperref not used. . . . .	506
\pageref: Added. . . . .	483
\tracingl warp: Added. . . . .	242
General: 2017/02/09 . . . . .	1
afterpage: Added. . . . .	604, 610
alltt: Added. . . . .	615
bookmark: Added. . . . .	649
caption and subcaption supported. . . . .	1
cleveref and referencing patches:	
Applied \AfterEndPreamble. . . . .	555
draftwatermark: Added. . . . .	706
eso-pic: Added. . . . .	719
everypage: Added. . . . .	720
extramarks: Added. . . . .	721
fancyhdr: Added. . . . .	726
float: Improved float caption type handling. . . . .	739
graphics: Fix: Expands filename. . . . .	773
graphics: Fix: \linewidth in a floatrow. . . . .	773
hyperref: Additional user macros. . . . .	783
keyfloat: Added. . . . .	800
letterspace: User-interface emulated. . . . .	809
listings: Added. . . . .	813
ltcaption: Added. . . . .	822
l warp-newproject: Added. . . . .	253
microtype: User-interface emulated. . . . .	855
needspace: Added. . . . .	878
nowidow: Added. . . . .	891
placeins: Added. . . . .	928
ragged2e: Added. . . . .	936
setspace: Improved support. . . . .	955
textpos: Added. . . . .	998
titlesp: Added. . . . .	1007
titlesec: Added. . . . .	1010
titletoc: Added. . . . .	1012
titling: Improved compatibility. . . . .	1014
tocloft: Added. . . . .	1022
wallpaper: Added. . . . .	1048
wrapfig: Added. . . . .	1051
xetexko-vertical: Added. . . . .	1064
Added @, <, > columns. . . . .	415
Added single-expansion data arrays. . . . .	324
Code factored into independent l warp_html files. . . . .	599
Docs: Examples for generating HTML file names. . . . .	115
Docs: Improved index. . . . .	1
Enhanced titling support. . . . .	394
File: l warp.css: Minor fixes for validation. . . . .	1
File: l warpmk used to compile print, HTML, indexes, and lateximages. . . . .	1
Fix: \linewidth in a floatrow. . . . .	744
Moved sidebar and example code to test suite. . . . .	1
Page geometry set to 6in wide with large margins. . . . .	228
Parallel versions of aux files for print/HTML. . . . .	1
Removed reliance on make, grep, gawk. . . . .	1
Tabular: \unskip extra spaces. . . . .	415
Test Suite: HTML meta descriptions. . . . .	1
verbatim: Added. . . . .	404
BlockClass: Added optional style. . . . .	341
Renamed from "blockclass". . . . .	341
LWR@nestspan: Fix: Minipages inside a span. . . . .	336

v0.21

\LWR@LwarpStart: Changed lateximages to a .txt file. . . . .	386
--	-----

\LWR@filestart: Skip title if not given. . . . .	383	v0.24	\LWR@htmlfileref: Fix: Index links while \tracingl warp. . . . .	478
\LWR@newhtmlfile: Skip title if not given. . . . .	368	\hspace: Add: \hspace \fill converts to 2em . . . . .	584	
\marginpar: Fixed source listing. . . . .	358	\hypertocfloat: List of floats responds to lofdepth, lotdepth. . . . .	502	
\marginparBlock: Fixed source listing. . . . .	359	General: 2017/03/15 . . . . .	1	
General: 2017/02/23 . . . . .	1	fontenc: Added. . . . .	752	
fontenc: Added. . . . .	752	l warp mk: Fix: l warp mk again for WINDOWS. . . . .	303	
l warp mk: Fix: l warp mk l images for WINDOWS. . . . .	303	l warp mk: Fix: l warp mk uses lateximages text file instead of shell script. . . . .	303	
Add: Errors for misplaced packages. . . . .	199	l warp mk: Fix: l warp mk uses lateximages text file instead of shell script. . . . .	303	
Docs: Added internet class. . . . .	74	Add: Errors for misplaced packages. . . . .	199	
Docs: Added TeX2page, GladTeX. . . . .	74	Docs: Added internet class. . . . .	74	
Docs: Installing on WINDOWS. . . . .	80	Docs: Added TeX2page, GladTeX. . . . .	74	
File: l warp _tutorial.txt added. . . . .	84	Docs: Installing on WINDOWS. . . . .	80	
v0.22		File: l warp _tutorial.txt added. . . . .	84	
\l WR@parseDcolumn: Added tabular D column. . . . .	431	v0.25	\l WR@loadnever: Added the ability to prevent conflicting packages. . . . .	201
\l WR@parsebangcolumn: Added tabular ! column. . . . .	426	\addcontentsline: Handles theorems. . . . .	494	
\l WR@parseablecols: Unknown table column types become l. Added tabular D, !, X columns. . . . .	433	General: 2016/03/22 . . . . .	1	
\l WR@printmccoldata: Added tabular D, !, and X columns. . . . .	454	amsthm: Added. . . . .	619	
General: 2017/03/02 . . . . .	1	ellipsis: Added. . . . .	709	
abstract: Added. . . . .	601	emptypage: Added. . . . .	710	
changepage: Added. . . . .	662	framed: Added. . . . .	756	
dcolumn: Added. . . . .	702	lips: Added. . . . .	813	
ftnright: Added. . . . .	759	mdframed: Help avoid hyphenation. . . . .	841	
geometry: Nullified commands. . . . .	761	ntheorem: Added. . . . .	892	
layout: Added. . . . .	805	showidx: Added. . . . .	957	
l scape: Added. . . . .	821	theorem: Added. . . . .	998	
mcaption: Added. . . . .	839	Basic LATEX theorems: improved css. . . . .	405	
nameref: Added. . . . .	875	Docs: Adds credits for patched code. . . . .	1	
nextpage: Added. . . . .	878	Docs: Testing l warp. . . . .	186	
parskip: Added. . . . .	911	Fix: Allows XELATEX and LuaLATEX to preload graphics and graphicx. . . . .	203	
showkeys: Added. . . . .	957	v0.26	General: 2017/03/31 . . . . .	1
sidecap: Added. . . . .	957	l warp.css: Improved responsive marginpar and marginblock. . . . .	260	
tabularx: Added. . . . .	991	cutwin: Added. . . . .	701	
variorref: Supported. . . . .	129	endnotes: Added. . . . .	712	
verse: Added. . . . .	1042	floatflt: Added. . . . .	740	
v0.23		footmisc: Added. . . . .	752	
\l WR@parseablecols: Fix for vert bar column type. . . . .	433	footnotehyper: Added. . . . .	755	
\l WR@printmccoldata: Fix for vert bar column type. . . . .	454	footnote: Added. . . . .	753	
General: 2017/03/02 . . . . .	1	marginfix: Added. . . . .	832	

sidenotes: Added. . . . .	958
Docs: Improved MiKTEX install instructions. . . . .	79, 81
Dollar span avoided in a lateximage. . . . .	512
Footnotes now are LATEX boxes instead of pagenotes. . . . .	353
lateximage: Labels track page numbers of lateximages. . . . .	539
Print mode now uses a minipage of \linewidth. . . . .	539
picture: Fix for \makebox in picture. .	558
<b>v0.27</b>	
\LWR@footnotetext: Fix for table footnote par tags. . . . .	354
General: 2017/04/04 . . . . .	1
letrine: Added. . . . .	809
microtype: Fix with XeLATEX, LuaLATEX. . . . .	855
soul: Added. . . . .	972
ulem: Added. . . . .	1036
Docs: Installing utilities for MACOS. .	82
Docs: Limitations of saveboxes. .	124
Page geometry modified to reduce line overflow. . . . .	228
<b>v0.28</b>	
\@wrindex: Improved indexing. . . . .	505
\HTMLAuthor: Added \HTMLauthor. (Renamed in v0.30.) . . . . .	352
\LWR@LwarpEnd: If FormatEPUB or FormatWP, no bottom nav. . . . .	389
\LWR@LwarpStart: FormatWordProcessor forces single-file output. . . . .	386
\LWR@filestart: Adds HTML meta author. . . . .	383
\LWR@forcenewpage: Forces new PDF page before major environments. .	332
\LWR@htmlcomment: Breaks ligatures in HTML comments. . . . .	338
\LWR@newhtmlfile: If FormatEPUB or FormatWP: skips headers, footers, nav. . . . .	368
\LWR@parsetablecols: Added L, C, R, J column types. . . . .	433
\LWR@startref: Removed space. . .	481
\chapter: If EPUB, prints footnotes before each section. . . . .	381
\hyperindexref: Improved indexing. .	506
\textup: Fixed span class. . . . .	571
General: 2017/04/14 . . . . .	1
glossaries: Added. . . . .	764
graphics: Adapts to graphics syntax. . . . .	773
graphics: Added. . . . .	765
tabularx: Fix for optional pos. . . . .	991
tabulary: Added. . . . .	991
<i>lwarpmk</i> : Add: <b>printglossary</b> and <b>htmlglossary</b> commands. . . . .	303
Added boolean FormatEPUB. . . . .	247
Added boolean FormatWP. . . . .	247
Added boolean HTMLDebugComments. . . . .	242
Added boolean HTMLMarkFloats, changed to WPMarkFloats as of v0.42. . . . .	247
Docs: Modfyng lwarpmk and index processing. . . . .	186
File: lwarpmathjax.txt: Updated CDN repository. . . . .	301
Forced oneside to maintain large right margin. . . . .	228
<b>v0.29</b>	
General: 2017/04/15 . . . . .	1
*.lwarpmkconf: Add: language option for config files. . . . .	260
lwarpmk.conf: Add: language option for config files. . . . .	260
graphics: Fix: Error when no optional arguments. . . . .	773
<i>lwarpmk</i> : Add: language option for config files. . . . .	303
Add: lwarpmklang option for lwarp. . . . .	222
Docs: Using a glossary . . . . .	95
<b>v0.30</b>	
\CSSFilename: Renamed from \NewCSS. . . . .	350
\HTMLAuthor: Renamed from \HTMLauthor. . . . .	352
\HTMLDescription: Renamed from \NewHTMLdescription. . . . .	352
\HTMLFirstPageTop: Renamed from \SetFirstPageTop. . . . .	350
\HTMLLanguage: Renamed from \MetaLanguage. . . . .	382
\HTMLPageBottom: Renamed from \SetPageBottom. . . . .	350
\HTMLPageTop: Renamed from \SetPageTop. . . . .	350
General: 2017/04/29 . . . . .	1
<i>lwarp-newproject</i> removed, and combined with <i>lwarp</i> . . . . .	253
<i>lwarpmk</i> : Add: xdyfile configuration option. . . . .	303
<i>lwarpmk</i> : Fix: <i>xindy</i> and <i>texindy</i> adjusted for <i>pdflatex</i> , <i>xelatex</i> and <i>lualatex</i> . . . . .	303

<i>lwarpmk</i> : Fix: <i>xindy</i> now used for print index generation with <i>latexmk</i> . . . . .	303	Add: Tabular at and bang columns now have their own HTML columns. . . . .	415
<i>lwarpmk</i> : language now used for both index and glossary generation. . . . .	303	cleveref: Fix: Loaded \AtEndPreamble. . . . .	555
File: <i>l warp_html.xdy</i> renamed to <i>l warp.xdy</i> . . . . .	300	Fix: Incorrectly-inline math environments. . . . .	531
Fix: *.css files only written in print mode. . . . .	260	New handling of & to localize catcode changes. . . . .	415
Fix: <i>l warp.xdy</i> only written in print mode. . . . .	300	v0.34	
Fix: <i>l warp_mathjax.txt</i> : Only written in print mode. . . . .	301	\@fnsymbol: Text symbols instead of math. . . . .	396
Option <i>lwarpmklang</i> changed to <i>IndexLanguage</i> . . . . .	222	\InlineClass: Moved optional argument in front of mandatory. . . . .	341
Option <i>OSWindows</i> replaces macro <i>\warpOSwindows</i> . . . . .	222	\LWR@htmldivclass: Moved optional argument in front of mandatory. . . . .	339
Option <i>xdyFilename</i> added. . . . .	222	\LWR@htmlelementclass: Moved optional argument in front of mandatory. . . . .	339
Option <i>latexmk</i> replaces macro <i>\UseLatexmk</i> . . . . .	223	\LWR@htmlelementclassline: Moved optional argument in front of mandatory. . . . .	340
Options <i>HomeHTMLFilename</i> and <i>HTMLFilename</i> replace macros <i>\HomeHTMLFilename</i> and <i>\HTMLFilename</i> . . . . .	222	\LWR@htmlspanclass: Moved optional argument in front of mandatory. . . . .	337
v0.31		\LWR@nullfonts: Improved font control. . . . .	573
General: 2017/05/15 . . . . .	1	\LWR@restoreorigformatting: booktabs: Works inside <i>lateximage</i> . . . . .	508
<i>keyfloat</i> : Improved compatibility. . . . .	800	Improved font control. . . . .	508
v0.32		\LWR@subhtmlelementclass: Moved optional argument in front of mandatory. . . . .	339
\RequirePackage: Fix: Ignores blanks in package list. . . . .	236	\LWR@tabledatatablecolumntag: booktabs: Works inside <i>lateximage</i> . . . . .	466
General: 2016/06/09 . . . . .	1	\fboxBlock: Added. . . . .	566
<i>glossaries</i> : Prevent error with <i>\glo@name</i> not defined. . . . .	507	\makebox: Fix: Handles paren arg. . . . .	564
<i>lwarpmk</i> : Fix: <i>io.lines()</i> changed to <i>file:lines()</i> due to <i>luatex</i> changes. . . . .	303	General: 2017/08/08 . . . . .	1
v0.33		<b>babel-french</b> : Adds fixed-width HTML spaces to punctuation. . . . .	334
\HTMLAuthor: Fix: Provides empty default author if none given. . . . .	352	<b>balance</b> : Added. . . . .	638
\LWR@loadbefore: Fix: No <i>\PackageError</i> if already loaded. . . . .	201	booktabs: Works inside <i>lateximage</i> . . . . .	469, 649
\LWR@parseatcolumn: Fix: Column alignment with leftmost @. . . . .	426	boxedminipage2e: Added. . . . .	652
\LWR@tabledatatablesinglecolumntag: Fix: Macros in tabular could cause extra data cell. . . . .	441	crop: Added. . . . .	698
\LWR@vspace: Add: <i>\vspace</i> nullified. . . . .	586	enumerate: Added. . . . .	712
\StartDefiningTabulars: Add: Avoids error: Misplaced alignment tab character &. . . . .	325	enumitem: Added, no longer required. . . . .	712
General: 2017/07/10 . . . . .	1	everyshi: Added. . . . .	720
<i>amsmath</i> : Removed <i>fleqn</i> option. . . . .	615	fancybox: Added. . . . .	723
<i>fancyhdr</i> : Fix: Optional args for <i>\thead</i> , etc. . . . .	726	fancyverb: Added, no longer required. . . . .	729
		figcaps: Added. . . . .	735
		filecontents: Required. Patched for morewrites. . . . .	231

floatpag: Added. . . . .	741	\LWR@closeparagraph: Extra HTML source space after paragraphs. . . . .	345
flushend: Added. . . . .	747	\LWR@currenttextcolor: Fix for \rule when xcolor not loaded. . . . .	580
fullpage: Added. . . . .	759	\LWR@nullfonts: Fix: Filenames while using MATHJAX. . . . .	573
hyperxmp: Added. . . . .	788	\LWR@restoreorigformatting: siunitx: Improved super/subscripts in a lateximage. . . . .	508
idxlayout: Added. . . . .	789	\LWR@section: Improved spacing. . . . .	375
marginfit: Added. . . . .	831	\LWR@stoppars: Extra HTML source space after paragraphs. . . . .	348
mdframed: Improved mdtheorem patch. . . . .	846	\LWR@subHTMLsanitize: Fix for babel-french. . . . .	364
moreverb: Added. . . . .	861	\fbox: Fix: Uses \fboxrule and \fboxsep. . . . .	566
paralist: Added. . . . .	906	\framebox: Fix: Handles width and horiz position. . . . .	565
pdfescape: Added. . . . .	914	\makebox: Fix: Handles width and horiz position. . . . .	564
pdfsync: Added. . . . .	918	General: 2017/08/17 . . . . .	1
prelim2e: Added. . . . .	930	babel-french: Adjustements for French variants, load order, footnotes, ellipses. . . . .	334
rotfloat: Added. . . . .	943	footnote: Extra HTML source space after paragraphs. . . . .	753
savetrees: Added. . . . .	944	siunitx: Fix for babel-french. . . . .	548
shadow: Added. . . . .	956	siunitx: Improved symbol support. 961	
syntonly: Added. . . . .	990	transparent: Added. . . . .	1032
titlesp: No longer required. . . . .	1007	upref: Added. . . . .	1041
titleref: Prevented. . . . .	1010	xcolor: Added \fcolorboxBlock, \colorboxBlock. . . . .	1053
xmpincl: Added. . . . .	1069	xcolor: Fix: Background none in print mode. . . . .	1053
Added. . . . .	1060	xcolor: Refactored \LWR@colorstyle. . . . .	1056
Docs: Horizontal space limitations. . . . .	1	xcolor: Uses \fboxrule and \fboxsep. . . . .	1053
Docs: Misplaced alignment character. . . . .	190	xcolor: \fcolorbox etc. now work inside lateximage. . . . .	1053
File: l warp_mathjax.txt: Version change. . . . .	301	Docs: Reorganized: Special cases and limitations. . . . .	121
File: README.txt: updated. . . . .	1	Source: Improved formatting. . . . .	1
Fix: Added the eqnarray environments. . . . .	531	tabular: Fix for babel-french. . . . .	470
Improved font control. . . . .	569	lateximage: Footnotes appear in regular text instead of the lateximage minipage. . . . .	539
Lists refactored to remove enumitem requirement. . . . .	406	v0.37	
Verbatim refactored to remove fancyvrb requirement. . . . .	402	\@include: Maintains independent aux files for HTML. . . . .	240
tabular: booktabs: Works inside lateximage. . . . .	470	General: 2017/08/19 . . . . .	1
lateximage: Fix: lateximage with minipage, \parbox, \makebox, \fbox, \framebox, \raisebox, \scalebox, \reflectbox. . . . .	539	IATEX accents: Added. . . . .	252
BlockClass: Moved optional argument in front of mandatory. . . . .	341	babel-french: Adjustment for load order. . . . .	334
fminipage: Added. . . . .	567		
\LWR@nestspan: Fix: Minipages, BlocksClass, and lists inside a span. . . . .	336		
v0.35			
General: 2017/08/08 . . . . .	1		
Fix: \textbf and related. . . . .	569		
v0.36			
\LWR@footnotetext: Extra HTML source space after paragraphs. . . . .	354		
Force HTML superscripts. . . . .	354		
\LWR@HTMLsanitizeexpand: Fix for babel-french. . . . .	365		

color: Prevented. . . . .	695	\AddSubtitlePublished: Added. . . . .	399
comment: Maintains independent cutfiles for print, HTML. . . . .	226	\LWR@domulticolumn: Add: Optional vpos and # rows. . . . .	456
siunitx: Improved symbol support. . . . .	961	\LWR@restoreorigformatting: Appended with \appto instead of calling various macros. . . . .	508
textcomp: Improved support. . . . .	994	\LWR@tabledatacolumntag: Don't start a data cell if see \TabularMacro. . . . .	466
<i>lwarpmk</i> : Removes additional HTML aux files. . . . .	303	\ResumeTabular: Added. . . . .	465
File handles reorganized. . . . .	239	\TabularMacro: Added. . . . .	465
v0.38		\multicolumnrow: Added. . . . .	463, 869
\@secCntformat: Added for appendix. . . . .	374	\printauthor: Removed minipages. . . . .	394
\ForceHTMLPage: Added. . . . .	372	Supports authblk with <div>s of class oneauthor instead of tabular. . . . .	394
\ForceHTMLTOC: Added. . . . .	372	\thanksmarkseries: Removed minipage footnotes. . . . .	1017
\LWR@section: \part* starts a new HTML page, for appendix. . . . .	375	General: 2017/08/27 . . . . .	1
Modified spacing, uses \numberline. . . . .	375	a4wide: Added. . . . .	601
\numberline: Added trailing \quad. . . . .	501	a4: Added. . . . .	600
\part: Fix with article class. . . . .	381	a5comb: Added. . . . .	601
General: 2017/08/27 . . . . .	1	addlines: Added. . . . .	609
appendix: Added. . . . .	623	anySize: Added. . . . .	623
arabicfront: Added. . . . .	625	authblk: Added. . . . .	633
chappg: Added. . . . .	665	bigdelim: Added. . . . .	645
color: Forces xcolor as well. . . . .	695	bigstrut: Added. . . . .	647
fix2col: Added. . . . .	736	ebook: Added. . . . .	708
fncychap: Added. . . . .	748	fullwidth: Added. . . . .	760
grffile: Added. . . . .	778	midpage: Added. . . . .	856
metalogo: Added. . . . .	851	multirow: Add: New optional vpos argument. . . . .	868
nonumonpart: Added. . . . .	890	multirow: Add: Supports left/right border for bigdelim. . . . .	868
nopageno: Added. . . . .	890	multirow: Fix: Long text argument. . . . .	868
pagenote: Option page disabled. . . . .	905	supertabular: Added. . . . .	987
realscripts: Added. . . . .	936	textarea: Added. . . . .	993
relsize: Added. . . . .	939	titling: Improved compatibility. . . . .	1014
romanbarpagenumber: Added. . . . .	942	titling: Removed extraneous center environments. . . . .	1014
romanbar: Added. . . . .	942	typearea: Added. . . . .	1035
scalefnt: Added. . . . .	944	xtabular: Added. . . . .	1071
siunitx: Removed from lwarpm core. . . . .	961	zwpagelayout: Added. . . . .	1075
textcomp: Removed from lwarpm core. . . . .	994	Docs: Reorganized tabular discussion. . . . .	160
tocbibind: Added. . . . .	1019	Titlepage \published and \subtitle removed. \AddSubtitlePublished restores. . . . .	398
xltextra: Added. . . . .	1068	titlepage: Clear pending footnotes. . . . .	393
<i>lwarpmk</i> : Added <code>print1</code> and <code>html1</code> actions. . . . .	303	Removed minipages. . . . .	393
Added \markboth, \sloppy, etc. . . . .	332	titlingpage: Clear pending footnotes. . . . .	1014
Docs: Enhanced <i>Supported Features</i> table. . . . .	68		
Docs: Index, tocbibind. . . . .	136		
Docs: Starred sections. . . . .	132		
v0.39		v0.40	
\@maketitle: titling version. . . . .	1016	\@chapCntformat: Added for tocbibind, anonchap. . . . .	374
Native L <sup>A</sup> T <sub>E</sub> X version. . . . .	397		
Removed minipages. . . . .	397, 1016		
Supports authblk with <div>s of class oneauthor instead of tabular. . . . .	397, 1016		

\LWR@HTMLhline: Added	469	v0.41
\LWR@nullfonts: Fix: Long arguments for expandable command	573	
\LWR@restoreorigformatting: Improved L <sup>A</sup> T <sub>E</sub> X logos inside a lateximage	508	
Improved symbols inside a lateximage	508	
Nullified \InlineClass, etc. inside a lateximage	508	
\LWR@tabledatacolumntag: Fix for bigdelim: \ldelim, \rdelim	466	
\chapter: Added support for quotchap	381	
\multicolumnrow: Fix: Adapts to older multirow and xparse	463	
\simplechapterdelim: Added for tocbibind, anonchap	374	
\underline: Added	580	
General: 2017/09/25	1	
adjmulticol: Added	608	
anonchap: Added	623	
bigdelim: Improved documentation	645	
cuted: Added	701	
dblfnote: Added	702	
fnpos: Added	749	
graphics: Add: Full \graphicspath support	773	
graphics: Moved out of the lwrap core	765	
graphics: Restores \includegraphics and \DeclareGraphicsExtensions in a lateximage	765	
graphicx: Moved out of the lwrap core	778	
grffile: Directly supported	778	
midfloat: Added	856	
multirow: Improved bigdelim borders	868	
pfnote: Added	920	
quotchap: Added	934	
sectsty: Added	953	
stabular: Added	977	
tbls: Added	990	
textcomp: Additional symbols, improved XeLaTeX and LuaLaTeX support	994	
tocbibind: Improved for \simplechapter	1019	
xfrac: No longer preloaded	232	
xltextra: Fix for \showhyphens with XeLaTeX	1068	
\LWR@addcmidruletrim: Add: \cmidrule trims	446	
\LWR@clearmidrules: Add: \cmidrule trims	444	
\LWR@closetabledatacell: Add: Mute > for \bottomrule	420	
Fix: At/bang column with \multirow	420	
Fix: Cancel < for \multicolumn	421	
\LWR@domulticolumn: Add: \cmidrule trims	456	
Added vertical rules	458	
\LWR@nullifyNoAutoSpacing: babel-french: Fix: \NoAutoSpacing in a tabular	470	
\LWR@parsebarcolumn: Added vertical rules	428	
\LWR@printatbang: Add: \cmidrule trims	440	
Add: Mute at and bang columns for \bottomrule	440	
\LWR@printbartag: Added vertical rules	439	
\LWR@subaddcmidruletrim: Added	446	
\LWR@subcmidrule: Add: \cmidrule trims	444	
\LWR@tabledatasinglecolumntag: Add: \cmidrule trims	441	
Add: Mute < for \bottomrule	441	
\LWR@tabularfinishrow: Unfinished tabular rows automatically filled	423	
\mcollrowcell: Added for \multicolumn cells	469	
General: 2017/10/07	1	
booktabs: Improved rules	650	
multirow: Add: \cmidrule trims	868	
Added vertical rules	869	
Fix: < spec	869	
tabular: Fix: \NoAutoSpacing in a tabular with babel-french	471	
v0.42		
\@ensuredmath: Improved \ensuremath	522	
\@textsubscript: Added	580	
\@textsuperscript: Added	580	
\LWR@HTMLhline: If FormatWP force explicit border	469	
\LWR@addformatwpalignment: If FormatWP add explicit style for cell alignment	448	
\LWR@addrulewidth: If FormatWP force explicit border	447	

\LWR@amsmathbody: Fix: Numbering and naming AMS math environments. . . . .	537
\LWR@amsmathbodynumbered: Fix: Numbering and naming AMS math environments. . . . .	538
\LWR@doequation: If FormatWP print LaTeX expression. . . . .	526
\LWR@domulticolumn: If FormatWP add cell alignment. . . . .	458
\LWR@doubledollar: If FormatWP print LaTeX expression. . . . .	520
Improved \ensuremath. . . . .	520
Improved line spacing with mathjax. . . . .	520
\LWR@floatbegin: If FormatWP add a text frame. . . . .	489
\LWR@floatend: If FormatWP add a text frame. . . . .	490
\LWR@htmleqlabel: If FormatWP print LaTeX expression. . . . .	530
\LWR@remembertag: Fix: Numbering and naming AMS math environments. . . . .	537
\LWR@restoreorigformatting: Improved \ensuremath. . . . .	509
\LWR@subaddcmidruletrm: Opt if no rule given. . . . .	446
\LWR@subsingleddollar: If FormatWP print LaTeX expression. . . . .	519
\LWR@tabledata singlecolumn tag: If FormatWP add cell alignment. . . . .	442
\LaTeX: If FormatWP use explicit style. . . . .	591
\TeX: If FormatWP use explicit style. . . . .	590
\hspace: If FormatWP add \quads. . . . .	585
\listoffigures: Added boolean WPMARKLOFT. . . . .	498
\listoftables: Added boolean WPMARKLOFT. . . . .	498
\marginpar: If FormatWP emulate a wrapfig. . . . .	358
\marginparblock: If FormatWP emulate a wrapfig. . . . .	359
\rule: If FormatWP add \quads. . . . .	588
\tableofcontents: Added boolean WPMARKTOC. . . . .	497
\underline: If FormatWP, use explicit styles for \underline, etc. . . . .	580
General: 2017/10/30 . . . . .	1
\textbf and related: If FormatWP, use explicit styles for \textsc, etc. . . . .	569
algorithmicx: If FormatWP add \quads. . . . .	614
booktabs: If FormatWP force explicit border. . . . .	650
epigraph: If FormatWP add HTML styles. . . . .	713
fancybox: If FormatWP add HTML styles. . . . .	723
floatfl: Added width. . . . .	740
graphics: Fix: Class key. . . . .	770
graphics: Fix: Filename expansion. . . . .	773
graphics: If FormatWP, use explicit size. . . . .	770
keyfloat: If FormatWP add explicit HTML style. . . . .	804
moreverb: Simplified formatting of listings. . . . .	861
multirow: If FormatWP add cell alignment. . . . .	869
overpic: Added. . . . .	904
realscripts: Fix for subscripts in a lateximage. . . . .	936
sidenotes: If FormatWP add explicit HTML style. . . . .	959
sunits: Improved \ensuremath. . . . .	961
soul: If FormatWP, add explicit styles. . . . .	972
textcomp: Improved \interrobangdown. . . . .	994
wrapfig: If FormatWP add explicit HTML style. . . . .	1051
Added boolean WPMARKLOFT. . . . .	248
Added boolean WPMARKMATH. . . . .	248
Added boolean WPMARKMINIPAGES. . . . .	247
Added boolean WPMARKTOC. . . . .	248
Added boolean WPTITLEHEADING. . . . .	248
Docs: Added support page. . . . .	2
Docs: Improper \prevdepth. . . . .	190
Docs: Reorganized math limitations . . . . .	148
File: lwarpmathjax.txt: Updated sunits script. . . . .	301
Fix: Numbering and naming AMS math environments. . . . .	536
If FormatWP, shift section headings. . . . .	249
tabbing: Added. . . . .	405
lateximage: Fix: Numbering and naming AMS math environments. . . . .	540
center: If FormatWP use explicit text-align. . . . .	544
minipage: Added boolean WPMARKMINIPAGES. . . . .	562, 563
If FormatWP add a text frame. . . . .	561
eqnarray: Fix: Numbering and naming AMS math environments. . . . .	533
If FormatWP print LaTeX expression. . . . .	532

\LWR@BlockClassWP: Added to factor code.	342
\LWR@figcaption: If FormatWP forces italic captions.	493
<b>v0.43</b>	
\LWR@domulticolumn: Fix for vertical rules.	458
Fix: Multicolumn trim.	457
\LWR@maybeprintpendingfootnotes:	
Added FootnoteDepth.	357
\LWR@nullfonts: Fix: Nullify dollar inside filenames.	573
\LWR@parsetablecols: Ignore spaces in col spec.	433
\LWR@printmccoltype: Added vertical rules.	452
\LWR@section: Fix: Expansion in comparison.	376
Fix: Math in section name.	377, 379
Fix: Nullify fonts inside HTML comment.	377
\TabularMacro: \newcommand instead of \relax to fix supertabular and xtab.	465
\href: Made robust.	485
\nameref: Made robust.	483
\nolinkurl: Made robust.	486
\url: Made robust.	486
General: 2017/11/08	1
\LWR@currentautosec: Added.	375
breakurl: Added.	653
hyperref: Made robust.	784, 785, 787
hyperref: \Gauge added.	787
luatodonotes: Added.	824
todonotes: Added.	1029
Added FootnoteDepth.	353
Docs: HTML settings table.	109
Docs: Reorganized HTML customization.	109
<b>v0.44</b>	
@\currentlabelname: Adjustment for koma-script.	476
\HTMLTitle: Added.	351
\LWR@addformatwpalignment: Fix for multicolumn alignment if FormatWP.	448
\LWR@backgroundcolor: Added.	1057
\LWR@filestart: Add \HTMLTitle.	385
Fix \HTMLAuthor.	384
\LWR@listitem: Added list and trivlist.	409
\LWR@patchlists: Added list and trivlist.	412
\LWR@strresult: Fix: \providecommand.	418
\textcolor{black}{\LWR@textcurrentcolor: xcolor: Added \LWR@textcurrentcolor.}	1056
\addcontentsline: Automatic \LWR@newfloatanchor.	494
\chapter: Add preamble for koma-script.	381
\marginparBlock: Added.	359
\nopagecolor: xcolor: Fix for \nopagecolor.	1058
\part: Add preamble for koma-script.	381
\title: Added \thetitle.	351
General: 2017/11/22	1
algorithmicx: Improved comment symbol.	614
atbegshi: Added.	629
cancel: Added.	656
changepage: Additional options.	663
easy-todo: Added.	707
fancyref: Added.	727
fixmetodonotes: Added.	738
fixme: Added.	737
fontenc: Allowed after \warp.	752
hang: Added.	779
ifoddpage: Added.	790
ltxtable: Added.	823
luatodonotes: Improved.	824
\warp-patch-komascript: Added.	1077
overpic: Fix: Groups for lateximages.	904
pdfsync: Fixes.	918
preview: Added.	930
scrextend: Added.	945
scrhack: Added.	948
scrlayer-notecolumn: Added.	950
scrlayer-scrpage: Added.	950
scrlayer: Added.	948
section: Added.	952
soulpos: Added.	974
soulutf8: Added.	974
supertabular: Fix for caption.	988
tikz: Fix: Groups for lateximages.	1006
tocbasic: Added.	1018
tocloft: Added \newlistentry.	1026
tocloft: Improved \newlistof.	1027
tocstyle: Added.	1028
todonotes: Improved.	1029
todo: Added.	1028
typearea: Added expert commands.	1035
watermark: Added.	1049
xcolor: Added \LWR@currenttextcolorstyle.	1056
xcolor: Added \LWR@findcurrenttextcolor.	1056
xtab: Fix for caption.	1072

Adjustment for koma-script.	211
AMS environments: Fix: Groups for <code>lateximages</code> .	616
If pdfLaTeX, require T1 and UTF-8 encoding.	213
<code>picture:overpic</code> : Fix: Groups for <code>lateximages</code> .	558
<code>list</code> : Added <code>list</code> and <code>trivlist</code> .	409
<code>LWR@nestspan</code> : Added <code>list</code> and <code>trivlist</code> .	336
<b>v0.45</b>	
<code>\@currentHref</code> : Added.	484
<code>\@donoparitem</code> : Modified for HTML.	407
<code>\@item</code> : Modified for HTML.	407
<code>\@mklab</code> : Modified for HTML.	407
<code>\CSSFilename</code> : Improved filenames with underscores.	350
<code>\LWR@LwarpStart</code> : Fix: Lateximages on incorrect pages with Mathjax.	388
<code>\LWR@newautoidanchor</code> : Fix: No anchor if frozen autoid.	491
<code>\LWR@notmemoirloadafter</code> : Added.	200
<code>\LWR@printpendingmpfootnotes</code> : Added.	358
<code>\LWR@startref</code> : Fix: Labels with underscores.	482
<code>\LWR@subhyperref</code> : Improved URLs with underscores.	484
<code>\LWR@subhyperrefclass</code> : Improved URLs with underscores.	485
<code>\LWR@sublabel</code> : Fix: Labels with underscores.	479
<code>\LWR@tabledatacolumntag</code> : Fix: Empty line between rows.	468
<code>\chapter</code> : Add optional heading title for memoir.	381
<code>\newpage</code> : Added.	583
<code>\nolinkurl</code> : Fix: Underscore in URL.	486
<code>\normalmarginpar</code> : Added.	359
<code>\reversemarginpar</code> : Added.	359
<code>\section</code> : Add optional heading title for memoir.	382
<code>\tableofcontents</code> : Fix: Empty <code>sitetoc</code> .	497
Fix: Patch <code>\AtBeginDocument</code> .	497
<code>\url</code> : Improved URLs with underscores.	486
General: 2018/01/14	1
<code>array</code> : Added.	626
<code>babel-french</code> : Robust commands.	334
<code>backref</code> : Added.	637
<code>breakurl</code> : Fix: Underscore in URL.	653
<code>changebar</code> : Added.	661
<code>cite</code> : Added.	693
<code>continue</code> : Added.	697
endfloat: Added.	710
epigraph: Support for memoir.	714
fancyverb: Improvements.	729, 730
flafter: Added.	738
fltrace: Added.	747
footnpag: Added.	755
fwlw: Added.	760
graphics: Improved URLs with underscores.	773
hanging: Added.	781
hyperref: Fix: Underscore in URL.	784
l warp-patch-memoir: Added.	1079
memhfixc: Added.	851
memoir: Added.	593
natbib: Added.	876
pagesel: Added.	905
prettyref: Added.	930
subfigure: Added.	986
subfig: Fix for subcaption end tag.	984
subfig: Fix: Math in subcaptions.	982
textfit: Added.	997
titleref: Added.	1010
turnthepage: Added.	1034
Allows memoir's preloaded packages.	203
Docs: <code>xparse</code> warnings.	170
Docs: Fix for double hyphens.	82
Docs: Improved install instructions.	83
Docs: Improved MiKTEX install instructions.	79
Docs: Moved table so doesn't interfere with install docs.	78
File: <code>l warp_mathjax.txt</code> : Allow MATHJAX inside tabbing.	301
File: <code>l warp_mathjax.txt</code> : Allow MATHJAX inside verse.	301
Fix: Empty sidetoc.	497
Improved: Robust \,, \ , and \textellipsis commands.	581
Separate <code>LWR@thisautoidWP</code> for word processor <div>s.	491
thebibliography: Patched to emphasize titles.	508
minipage: Fix: Improper <code>\prevdepth</code> .	563
<b>v0.46</b>	
<code>\LWR@closeparagraph</code> : Fix: Tabular empty lines.	346
<code>\LWR@closeprevious</code> : Fix: Stack unnesting.	332
<code>\LWR@forcenewpage</code> : Fix: Improper <code>\prevdepth</code> .	332
<code>\LWR@lookforpackagename</code> : Fix: Spaces in <code>\usepackage</code> .	236
<code>\LWR@popclose</code> : Fix: Stack unnesting.	323
<code>\LWR@providelength</code> : Added.	215

\LWR@pushclose: Fix: Stack unnesting	323
\LWRPrintStack: Name changed from \PrintStack	331
General: 2018/01/23	1
LWR@tabularpardepth added	418
amsthm: Adapted to trivlist changes	621
mdframed: Fixes for SVG math or lateximage in title	843
mdframed: Fixes for footnotes	844
ntheorem: Adapted to trivlist changes	892
theorem: Adapt to trivlist changes	1000, 1002
tabular: Fix: Tabular empty lines	474
list: Fix: Stack unnesting	410
v0.47	
\LWR@HTML@caption@begin: Fix: Argument passed to \LWR@origcaption@begin	493
\LWR@LwarpStart: Fix for SVG math in \nameref	388
\LWR@WPcell: Fix: Line wrap at HTML hyphen	448
\LWR@createautosec: Fix: Line wrap at HTML hyphen	373
\LWR@domulticolumn: Fix: Line wrap at HTML hyphen	457
\LWR@floatbegin: Fix: Line wrap at HTML hyphen	489
\LWR@htmclosecomment: Add \mbox to prevent line breaks	338
\LWR@newautoidanchor: Fix: Line wrap at HTML hyphen	491
\LWR@printopenlist: Fix: Line wrap at HTML hyphen	407
\LWR@startref: Fix: Line wrap at HTML hyphen	481
\LWR@sublabel: Fix: Line wrap at HTML hyphen	479
\LWR@subsingledollar: Added SVG math image baseline adjust and em sizing	519
\LWR@subsingledollarsvg: Fix: Line wrap at HTML hyphen	516
\captionlistentry: Fix: Line wrap at HTML hyphen	494
\hypertoc: Fix: Line wrap at HTML hyphen	501
\hypertocfloat: Fix: Line wrap at HTML hyphen	502
General: 2018/01/30	1
adjmulticol: Fix: Line wrap at HTML hyphen	609
blowup: Added	648
caption: Added	657
caption: Also loads l warp-caption	239
changepage: Fix for pagecheck macros	663
endheads: Added	711
epigraph: Fix: Line wrap at HTML hyphen	713
hanging: Fix: Line wrap at HTML hyphen	781
hang: Fix: Line wrap at HTML hyphen	779
keyfloat: Fix for SVG math in captions	801
midpage: Fix: Line wrap at HTML hyphen	856
multirow: Fix: Line wrap at HTML hyphen	868
multitoc: Added	870
ntheorem: Fix: Line wrap at HTML hyphen	896
realscripts: Fix: Line wrap at HTML hyphen	936
scrextend: Fix: Line wrap at HTML hyphen	945
sectionbreak: Added	953
sidenotes: Fix for SVG math in captions	958
subfig: Fix for SVG math in captions	982
subfig: Fix: Support \nameref	981
xurl: Added	1073
<i>l warp mk: pdfcrop</i> : Removed hires option for improved crop accuracy	303
lateximage: Added CSS style option	539
Fix: Line wrap at HTML hyphen	543
center: Fix: Line wrap at HTML hyphen	544
minipage: Fix: Line wrap at HTML hyphen	561
flushleft: Fix: Line wrap at HTML hyphen	545
flushright: Fix: Line wrap at HTML hyphen	545
enumerate: Fix: Line wrap at HTML hyphen	410
itemize: Fix: Line wrap at HTML hyphen	410
LWR@BlockClassWP: Fix: Line wrap at HTML hyphen	342
v0.48	
@@@setpageref: Fix for new v0.21 of cleveref	556

\@@@setcref: Fix for new v0.21 of	
cleveref. . . . .	555
\@@@setcrefrange: Fix for new v0.21	
of cleveref. . . . .	556
\@biblabel: Improved bibliography	
label. . . . .	507
\@item: Honors \makelabel. . . . .	407
\@maketitle: Fix: Errors with	
IEEEtran class. . . . .	397
\LWR@LwarpStart: Adjusted space	
around captions. . . . .	387
\LWR@ProvidesPackageDropB: Fix:	
Options with braces. . . . .	238
\LWR@addtabularhrulecolor:	
colortbl: Added. . . . .	449
\LWR@addtabularrulecolors:	
colortbl: Added. . . . .	450
\LWR@closetabledatacell: colortbl:	
Added. . . . .	421
\LWR@lookforpackagename: Fix:	
Parsing similar package names. .	235
\LWR@newautopagelabel: Fix: toc,	
LOF, LOT links. . . . .	364
\LWR@newhtmlfile: Fix: TOC, LOF, LOT	
links. . . . .	370
\LWR@nullfonts: Fix: \newline in	
title. . . . .	573
\LWR@parsedrequirepackagenames:	
Fix: Parsing similar package	
names. . . . .	233
\LWR@parsetablecols: Fix: Ignore	
optional tabular column	
arguments. . . . .	436
\LWR@restoreorigformatting: Fix:	
Spacing in SVG math, lateximage,	
Tikz. . . . .	509
\LWR@section: Fix: toc, LOF, LOT	
links. . . . .	379
\LWR@tabledatausingsinglecolumntag:	
colortbl: Added. . . . .	442
\LWR@textcurrentfont: Added.	
Improves font control. . . . .	577
\bibliography: Fix: \BaseJobname for	
bibliography. . . . .	507
\centerline: Added. . . . .	546
\l@part: Adapts to classes without	
\part. . . . .	503
\leftline: Added. . . . .	546
\mbox: Nullified for HTML. . . . .	564
\rightline: Added. . . . .	546
\thempfootnote: Removed \itshape. .	357
General: 2018/02/14 . . . . .	1
acronym: Added. . . . .	607
acro: Added. . . . .	605
chapterbib: Added. . . . .	666
colortbl: Added. . . . .	437, 448, 695
fancyref: Now directly supported. .	727
graphics: Fix: Virtual page size	
limited to a group. . . . .	773, 774
hypcap: Added. . . . .	782
hypernat: Added. . . . .	783
hyperref: \texorpdfstring now	
uses the TeX string. . . . .	786
luatodonotes: Improved	
\todototoc. . . . .	825
siunitx: Changes fraction to	
symbol. . . . .	964
siunitx: Improved SVG math. .	961, 963
siunitx: Improved color output. .	962
stfloats: Added. . . . .	979
todonotes: Improved	
\todototoc. . . . .	1029
vmargin: Added. . . . .	1045
xfrac: Fix: Added groups around	
super/subscripts to localize	
\LWR@nestspan changes. . . . .	1066
Docs: Converting an existing	
document. . . . .	99
Improved font control. . . . .	577, 578
tabular: colortbl: Added. . . . .	472
lateximage: Print mode boxed to	
natural width. . . . .	544
abstract: Allow optional name. .	400
v0.49	
\LWR@addtabularcellcolor: xcolor:	
Added tabular row colors. . . . .	451
\LWR@domulticolumn: xcolor: Added	
tabular row colors. . . . .	458
\LWR@printlength: Fix: Group	
printlen changes. . . . .	233
\affiliation: Fix: Adapts to classes	
which already provide. . . . .	393
\href: Fix: Adapt to classes. . . . .	485
\noalign: Fix: \noalign inside	
tabular. . . . .	469
\url: Fix: Adapt to classes. . . . .	486
General: 2018/02/19 . . . . .	1
amsmath: Fix: Patches for \eqref. .	615
eso-pic: Fix for	
\AddToShipoutPicture. . . . .	719
figsize: Added. . . . .	735
fnlineno: Added. . . . .	748
hypdestopt: Added. . . . .	783
hyphenat: Added. . . . .	788
lineno: Added. . . . .	810
luacolor: Added. . . . .	824
pagegrid: Added. . . . .	905
pdfrender: Added. . . . .	918
resizegather: Added. . . . .	941
verbbars: Added. . . . .	1044

vwcol: Added.	1046	siunitx: Improved svg math alt tags.	963
xcolor: Added tabular row colors.	437, 1062	siunitx: Improved units.	548, 961, 965
Fix: Adapt to classes.	582	xy: Added.	1074
<b>v0.50</b>		<i>lwarpmk</i> : Error if <i>lateximage</i> does not exist.	303
\@ensuredmath: Fix: Use <i>lateximage</i> even if MathJax.	522	<i>lwarpmk</i> : Error if <i>lwarpmk.conf</i> points to <i>lwarf</i> .	303
Improved SVG math alt tags.	522	<i>lwarpmk</i> : Improved error messages.	303
\LWR@footnotetext: Robustify macros.	355	<i>lwarpmk</i> : MD5 hash avoids duplicate SVG math.	303
\LWR@atbeginverbatim: Improved column alignment.	403	<i>lwarpmk</i> : Multiprocess support making <i>lateximages</i> .	303
\LWR@dequation: Improved SVG math display.	527	AMS environments: Improved SVG math display.	616
\LWR@doubledollar: Improved SVG math alt tags.	521	Fix: Load <i>fontspec</i> if necessary.	227
Improved SVG math display.	521	Robustify macros.	578
\LWR@htmrefsectionfilename: Fix: SVG math in a section name.	329	<i>lateximage</i> : Fix: SVG math in a section name.	542
\LWR@newhtmlfile: Fix: SVG math in a section name.	370	MD5 hash avoids duplicate SVG math.	540, 543
\LWR@nullfonts: Fix: \underline in sectioning file name.	576	<i>eqnarray</i> : Improved SVG math display.	533
\LWR@overline: Added.	580	<b>v0.51</b>	
\LWR@singledollar: Fix: Use <i>lateximage</i> even if MathJax.	519	\@ensuredmath: Hashes	
Improved SVG math alt tags.	519	\ensuremath.	522
\LWR@singledollarsvg: MD5 hash avoids duplicate SVG math.	517	\@item: Restored list label space.	408
\LWR@vspace: Robustify macros.	586	\LWR@HTMLsanitizeexpand: Fix: Escapes double quotes.	365
\nnewline: Robustify macros.	583	\LWR@LwarpStart: MathJax: Nullifies	388
\textsubscript: Robustify macros.	580	\ensuremath.	388
\textsuperscript: Robustify macros.	579	\LWR@addbaselinemarker: Improved	
General: 2018/03/03	1	SVG math baseline.	512
\lwarf.css: Improved SVG display math centering.	260	\LWR@atbeginverbatim: Adds vertical offset.	403
\lwarf_one_limage.txt: Added.	300	\LWR@dequation: Fix:	
amsmath: Fix: Upright tags for svgmath.	615	\addcontentsline inside SVG math. Provides an autoid anchor.	527
axodraw2: Added.	637	\lwarf:doubledollar: Fix:	
bytefield: Added.	655	\addcontentsline inside SVG math. Provides an autoid anchor.	521
dblfloatfix: Added.	702	\lwarf@findcurrenttextcolor: Added	
diagbox: Added.	703	\lwarf@findcurrenttextcolor when no <i>xcolor</i> .	581
epstopdf: Added.	715	\lwarf@newautoidanchor: Fix: No autoid is inside a <i>lateximage</i> .	491
listings: Force flexible columns.	813	\lwarf@singledollarmeasure: Fix: lateximage inside <i>AMS \text</i> .	514
morefloats: Added.	861	Fix: Honors text font around SVG math.	514
nonfloat: Added.	890	Improved SVG math baseline.	515
ntheorem: Fix: Not standard nor amsthm selected.	898	Typeset SVG math only once during measurement.	514
pbox: Added.	911		
phfqt: Added.	921		
schemata: Added.	944		
siunitx: Fix: Loads <i>xcolor</i> .	961		

\LWR@subHTMLsanitize: Fix: Escapes double quotes.	364
\LWR@subsingleddollar: Fix: \ensuredmath inside SVG image.	519
\LWR@subsingleddollarsvg: Fix: SVG math with enclosed lateximage.	516
SVG math baseline improved with invisible rule at corner.	518
\LWR@textcurrentcolor: xcolor: \LWR@textcurrentcolor if xcolor not loaded.	581
\addcontentsline: Add missing support for float mechanism if necessary.	495
No anchor ID if inside svg image.	495
\displaymathnormal: Processing for complicated display math.	529
\displaymathother: Processing for complicated display math.	529
General: 2018/03/24	1
l warp_one_limage.txt: pdftocairo -noshrink added.	300
afterpackage: No longer required.	230
chemfig: Added.	666
chemformula: Added.	668
chemgreek: Added.	673
chemmacros: Added.	674
chemnum: Added.	692
epstopdf-base: Added.	715
fancybox: Fix: Optional tag for \item in a span.	725
grid: Added.	778
listings: Forces cleared options.	814
ltxgrid: Added.	823
mhchem: Added.	853
tikz: Fix for \tikz macro.	1006
tikz: Fix for tikz with optional argument.	1006
titling: Fix for \thanks mark.	1015
l warpmk: pdfcrop: Restored hires option.	303
l warpmk: pdftocairo -noshrink added.	303
AMS environments: Fix: \addcontentsline inside svg math. Provides an autoid anchor.	616
Docs: tikz limitations.	156
Docs: Multiple authors and affiliations.	132
Docs: Things to avoid.	121
Docs: Updated Converting an existing document.	99
Fix: Remember original \# in case is redefined.	250
MathJax: Nullifies \ensuremath.	367
Named HTML entity used for text dollar.	512
lateximage: Added additional hashing option.	539
Fix: lateximage inside <i>AMS</i>	539
\textrm.	539
Processing for complicated display math.	542
alignat: Fix: Added.	618
eqnarray: Fix: \addcontentsline inside svg math. Provides an autoid anchor.	533
\LWR@displaymathother: Processing for complicated display math.	523
\LWR@equationother: Processing for complicated display math.	524
v0.52	
\@ensuredmath: Improved hashing expansion.	522
\mpfootnotetext: Fix: Paragraph handling.	357
\CustomizeMathJax: Added.	366
\LWR@footnotetext: Fix: Paragraph handling.	355
\LWR@addbaselinemarker: Warnings if l warp_baseline_marker.png is not present or if graphicx/s not loaded.	512
\LWR@customizedMathJax: Added.	366
\LWR@doequation: Fix: equation* now based on equation instead of displaymath.	527
Fix: equation* with split.	526
\LWR@filenamenoblocks: Fix: \FileDepth with non-utf8 encoding.	363
\LWR@nullfonts: Fix: \texorpdfstring in section names.	576
\LWR@section: Fix: Footnote numbering: Limited HTML comment if starred.	377
Fix: Footnote numbering: Use short toc entry for HTMLDebug comments.	377
\LWR@singledollarmeasure: Added user-adjustable SVG math font scaling.	515
\LateximageFontSizeScale: Added user-adjustable SVG math font scaling.	536
\href: Fix: #, %, &, ~, _ in URL.	485
\nolinkurl: Fix: #, %, &, ~, _ in URL.	486

\theHTMLTitleSeparator: Fix:	
\FileDepth with non-utf8	
encoding. . . . .	382
\url: Fix: #, %, &, ~, _ in URL. . . . .	486
General: 2018/04/01 . . . . .	1
breakurl: Fix: #, %, &, ~, _ in URL. . . . .	653
endfloat: Updated for v2.6. . . . .	710
fancyvrb: Initial support for	
\VerbatimFootnotes. . . . .	723, 729
graphics: Added defaults. . . . .	768
graphics: Updated for v1.1a. . . . .	769
graphics: Updated for v1.1b. . . . .	769
hyperref: Fix: #, %, &, ~, _ in	
URL. . . . .	784–786
nicefrac: Added. . . . .	887
url: Added. . . . .	1042
\lwarpmk: Fix: Memory overflow	
when spawning tasks. . . . .	303
\lwarpmk: Fix: Skip image	
generation if from page 0. . . . .	303
Changed FootnoteDepth default to	
\subsubsection. . . . .	353
Docs: Improved install instructions. 80	
Fix: MathJax script line wraps.	
Reduced right margin. . . . .	228
If pdfLaTeX, allow other input	
encoding. . . . .	213
Restore \kill in a lateximage. . . . .	821
tabbing: Fix to allow inside	
lateximage. . . . .	405
lateximage: Fix for hash expansion. 541	
v0.53	
General: 2018/04/01 . . . . .	1
\lwarpmk: Added	
\lwarpmk cleanimages. . . . .	303
\lwarpmk: Added warning for	
corrupted images. . . . .	303
Docs: \lwarpmk cleanimages. . . . .	96
Docs: \lwarpmk pdftohtml. . . . .	96
v0.54	
\LWR@afterendverbatim: Added	
vspace argument. . . . .	404
\LWR@atbeginverbatim: Improved	
column alignment. . . . .	403
\LWR@earlyloadnever: Added. . . . .	202
\LWR@endfloatalignment: Honor	
\centering, etc. in floats. . . . .	492
\LWR@floatalignment: Honor	
\centering, etc. in floats. . . . .	491
\LWR@floatbegin: Honor \centering,	
etc. in floats. . . . .	489
\LWR@floatend: Honor \centering,	
etc. in floats. . . . .	490
\LateximageFontSizeName: Defaults	
to normalsize. . . . .	536
\centering: Added debug comment. 545	
\raggedleft: Added debug	
comment. . . . .	545
\raggedright: Added debug	
comment. . . . .	545
General: 2018/04/22 . . . . .	1
*.lwarpmkconf: Option	
IndexLanguage changed to	
xindyLanguage. . . . .	260
*.lwarpmkconf: Option	
pdftotextEnc added. . . . .	260
*.lwarpmkconf: Option	
xdyFilename changed to	
xindyStyle. . . . .	260
*.lwarpmkconf: Option	
xindyCodepage added. . . . .	260
\lwarpc.css: Fix:	
Text-decoration-skip: auto. . . . .	260
\lwarpmk.conf: Option	
IndexLanguage changed to	
xindyLanguage. . . . .	260
\lwarpmk.conf: Option	
pdftotextEnc added. . . . .	260
\lwarpmk.conf: Option	
xdyFilename changed to	
xindyStyle. . . . .	260
\lwarpmk.conf: Option	
xindyCodepage added. . . . .	260
bibunits: Added. . . . .	644
chngpage: Added. . . . .	693
forest: Added. . . . .	756
glossaries: Fix when not using	
babel or polyglossia. . . . .	765
gridset: Added. . . . .	779
hyperref: Fix: \hyperref and	
\hyperlink with special chars in	
text. . . . .	785, 786
hyperref: Fix: \ref in \hyperref	
and \hyperlink caused nested	
link. . . . .	785, 786
\lwarpatch-memoir: Update for	
v3.7g. . . . .	1084
magaz: Added. . . . .	828
ragged2e: Fix: \centering, etc. . . . .	936
textcomp: Fix for	
\textrthousand. . . . .	994
tikz: Fixes for \pgfpicture,	
minipages, fit, align, font. . . . .	1006
\lwarpmk: Added pdftotextenc. . . . .	303
\lwarpmk: Added xindycodepage. . . . .	303
\lwarpmk: Changed language to	
xindylanguage. . . . .	303
\lwarpmk: Changed xdyfile to	
xindystyle. . . . .	303

<i>lwarpmk</i> : Improved error if configuration file does not exist.	303
<i>lwarpmk</i> : Increased prominence for error for an unknown command.	303
<i>lwarpmk</i> : Verifies HTML version exists before <i>lwarpmk</i> images.	303
<i>lwarpmk</i> : Verifies image references before <i>lwarpmk</i> images.	303
Add: <i>pdftotextEnc</i> .	222
Add: <i>xindyCodepage</i> .	222
Added early check for disallowed packages.	202
Docs: BibTeX.	134
Docs: Macros in sectioning names.	121
Never load <i>aecompl</i> .	202
Option <i>IndexLanguage</i> changed to <i>xindyLanguage</i> .	222
Option <i>xdyFilename</i> changed to <i>xindyStyle</i> .	222
verse: Fix: Line spacing.	402
v0.55	
\LWR@LwarpStart: Fix: Overfull boxes in <i>lateximages</i> .	387
\LWR@floatbegin: Fix: Float optional args.	489
\LWR@nullfonts: Removed extraneous space which appeared in file links.	576
\phantomsection: Fix:	
\ForceHTMLTOC with <i>phantomsection</i> .	589
General: 2018/04/26	1
<clrdblpg>: Added.</clrdblpg>	694
Fix: \centering, etc. for <i>koma-script</i> .	489
Fix: QED symbols in <i>lateximage</i> .	622, 902
v0.56	
\LWR@addcdashline: <i>arydshln</i> :	
Added.	448
\LWR@addmulticolvertrulecolor:	
Adds support for dashed vertical rules.	455
Adds support for double vertical rules.	455
\LWR@addtabularhrulecolor: Adds support for <i>arydshln</i> dashed rules.	449
Adds support for double \hlines and \midrules.	449
\LWR@addtabularrulecolors: Adds support for dashed vertical rules.	450
Adds support for double vertical rules.	450
\lwarpmk: Added	
\lwarpmk <i>pdftosvg</i> .	303
<i>lwarpmk</i> : Supports --shell-escape.	303
Added \thinspace.	581
\LWR@closeparagraph: Added support for <i>parnotes</i> .	346
\LWR@domulticolumn: Adds support for dashed vertical rules.	458
Adds support for double vertical rules.	458
\LWR@floatbegin: Adds a <class> per float package style.	489
\LWR@multicolparttext: Fix: \multicolumn parameters.	453
\LWR@openparagraph: Added support for <i>parnotes</i> .	344
\LWR@parsebarcolumn: Adds support for double vertical rules.	428
\LWR@parsecoloncolumn: <i>arydshln</i> :	
Added.	429
\LWR@parsingsemicoloncolumn: <i>arydshln</i> :	
Added.	429
\LWR@parseablecols: Added array W column.	436
\LWR@printmccoldata: Added array W column.	454
Fix: \multicolumn parameters.	454
\LWR@printmcctype: Added array W column.	452
Adds support for dashed vertical rules.	452
Adds support for double vertical rules.	452
\LWR@tabledatacolumntag: Fix: \morecmidrules	467
\LWR@textcurrentfont: Added span. <i>textbf</i> , etc.	577
General: 2018/05/12	1
*.lwarpmkconf: Records --shell-escape.	260
lwarpm.css: Added div. <i>textbf</i> , etc.	260
lwarpm.css: Added span. <i>textbf</i> , etc.	260
lwarpm.conf: Records --shell-escape.	260
arydshln: Added.	415, 626
lua-check-hyphen: Added.	823
paralist: Fixes for compactenum, compactitem, compactdesc.	906
parnotes: Added.	910
quoting: Added.	935
tocenter: Added.	1022
underscore: Added.	1038

Docs: <i>lwarpmk pdftosvg</i>	96
<i>LWR@blocktextcurrentfont</i> : Added div.textbf, etc.	577
v0.57	
\BlockClassSingle: Improved print/HTML output selection	341
\InlineClass: Improved print/HTML output selection	341
\LWR@ref@ignorestar: subcaption: Fix: \subref	483
\LWR@singledollarmeasure: Fix: Dynamic inline math expressions	514
\LWR@subhyperref: Fix: Text catcodes	484
\LWR@subhyperreftext: Fix: Text catcodes	485
\LWR@subsingledollar: Fix: Dynamic inline math expressions	519
\LWR@subsingledollarsvg: Fix: Dynamic inline math expressions	517
\LWR@vspace: Improved print/HTML output selection	586
\MathImageAltText: Added	510
\PackageDiagramAltText: Added	511
\StartDefiningMath: Added	325
\boxframe: xcolor: Colored \boxframe	1061
\colorbox: xcolor: New system for switching print and HTML outputs	1058
\colorboxBlock: xcolor: New system for switching print and HTML outputs	1058
\fboxBlock: Improved print/HTML output selection	566
\fcolorbox: xcolor: New system for switching print and HTML outputs	1059
\framebox: Improved print/HTML output selection	565
\href: Fix: Text catcodes	485
\inlinemathother: Added	326
\listof: Fix: Provide \lename if not defined	499
\makebox: Improved print/HTML output selection	564
\mbox: Improved print/HTML output selection	564
\multicolumnrow: multirow: Improved print/HTML output selection	869
Improved print/HTML output selection	463
\newfloat: rotfloat: Added float styles	943
rotfloat: Fix for listof sideways floats	943
\parbox: Improved print/HTML output selection	563
\raisebox: Improved print/HTML output selection	569
\reflectbox: Improved print/HTML output selection	777
\resizebox: Improved print/HTML output selection	777
\rotatebox: Improved print/HTML output selection	775
\rule: Fix: Colored rules	588
\scalebox: Improved print/HTML output selection	776
\textcolor: xcolor: New system for switching print and HTML outputs	1057
General: 2018/06/06	1
\larp.css: Added ruled, boxed, boxruled floats	260
\larp.css: Increased float vertical margins	260
algorithm2e: Added	610
bigdelim: Improved print/HTML output selection	645
breakurl: Fix: Text catcodes	653
colortbl: New system for switching print and HTML outputs	695, 696
ellipsis: Added \midwordellipsis	709
errata: Added	717
float: Added float styles	739
float: Fix: Do not pre-define \lename	739
\tablex: Added	822
marginnote: Fix: Long optional argument	832
multirow: Improved print/HTML output selection	868
register: Added	938
subcaption: Fix: \subref	784
trimclip: Added	1032
vowel: Added	1045
xellipsis: Added	1063
\xfrac: Improved print/HTML \scalebox control	1066
\xtabular: Added	1067
\xpiano: Added	1069
\lwarpmk: Improved code factoring	303
\lwarpmk: Improved error handling	303
Docs: Recompiling <i>lwarpmk</i> or css files	186
Docs: Recreating the index for <i>lwarpmk</i> source	183

MathJax: Supports \footnote,	
\footnotemark. . . . .	367
New system for switching print and	
HTML outputs. . . . .	245
minipage: Improved print/HTML	
output selection. . . . .	560
BlockClass: Improved print/HTML	
output selection. . . . .	341
fminipage: Improved print/HTML	
output selection. . . . .	567
LWR@BlockClassWP: Improved	
print/HTML output selection. . .	342
v0.58	
\LWR@HTML@caption@begin: Improved	
print/HTML output selection. . .	493
\LWR@HTML@caption@end: Improved	
print/HTML output selection. . .	494
\LWR@HTML@ref: Improved print/HTML	
output selection. . . . .	482
\LWR@doindexentry: Adds support for	
\see, \seealso, \emph, \textbf,	
etc. . . . .	506
\LWR@hyperindexrefnullified: Adds	
support for \see, \seealso,	
\emph, \textbf, etc. . . . .	506
\LWR@indexitem: Accepts optional arg	
for repeatindex. . . . .	505
\dotfill: Improved print/HTML	
output selection. . . . .	583
\hfill: Improved print/HTML output	
selection. . . . .	582
\hrulefill: Improved print/HTML	
output selection. . . . .	583
\hyperindexref: Adds support for	
\see, \seealso, \emph, \textbf,	
etc. . . . .	506
\printindex: Fix: Extra \newpage to	
flush pending \index writes. . .	829
General: 2018/07/07 . . . . .	1
*.lwarpmkconf: Added option	
makeindexstyle. . . . .	260
*.lwarpmkconf: Added options	
makeindex and xindy. . . . .	260
*.lwarpmkconf: Generated	
\AtBeginDocument. . . . .	260
lwarpm.xdy: Requires	
makeindex.xdy. . . . .	300
lwarpm.xdy: Supports bold, italic. .	300
lwarpm_html.list: Added. . . . .	299
lwarpmk.conf: Added option	
makeindexstyle. . . . .	260
lwarpmk.conf: Added options	
makeindex and xindy. . . . .	260
lwarpmk.conf: Generated	
\AtBeginDocument. . . . .	260
v0.59	
\LWR@addbaselinemarker: Uses .eps	
if DVI <i>latex</i> . . . . .	512
\LWR@texmkcmd: Fix:	
--shell-escape with <i>texmk</i> . . .	255

\LWR@writeconf: Compilation commands now reassigned by <i>lwarf</i> instead of being computed by <i>lwarpmk</i> . . . . .	259
\[: Fix with \displaymathnormal. . .	522
General: 2018/09/07 . . . . .	1
Slunits: Added. . . . .	960
accsupp: Added. . . . .	605
amsmath: Moved from the <i>lwarf</i> core. . . . .	615
asymptote: Added. . . . .	629
axessibility: Added. . . . .	636
breqn: Added. . . . .	653
bxpapersize: Added. . . . .	655
canoniclayout: Added. . . . .	657
chemformula: Fix for \NMR. . . . .	689
draftcopy: Added. . . . .	705
epstopdf-base: Improved. . . . .	715
epstopdf: Improved. . . . .	715
fnbreak: Added. . . . .	747
graphics: Fix: Expand filename. . .	774
graphics: Now works with .pdf and .eps filename extensions. . . . .	773
nccfancyhdr: Added. . . . .	876
pdfricks: Added. . . . .	918
pst-eps: Added. . . . .	932
pstricks: Added. . . . .	933
units: Added support for MathJax. .	1040
xunicode: Added. . . . .	1072
<i>lwarpmk</i> : Added	
<i>lwarpmk epstopdf</i> . . . . .	303
<i>lwarpmk</i> : Consolidated compiling options into printlatexcmd and HTMLLatexcmd. . . . .	303
<i>lwarpmk</i> : Double instead of single-dashed --shell-escape option. . . . .	303
<i>lwarpmk</i> : Error if <i>lwarpmk.conf</i> format changed. . . . .	303
<i>lwarpmk</i> : Warning if operating system changed. . . . .	303
Added option dvipdfmx. . . . .	224
Added option dvipdfm. . . . .	224
Added option dvips. . . . .	224
Docs: <i>lwarpmk epstopdf</i> . . . . .	96
File: <i>lwarf_mathjax.txt</i> : Fix: Removed chapter number from tagged non-numeric MathJax equations. . . . .	301
File: <i>lwarf_mathjax.txt</i> : Updated to MathJax v2.7.4. . . . .	301
picture: Added an alt tag. . . . .	558
v0.60	
\lWR@clearmidrules: tabular: Fix for midrules. . . . .	444
\lWR@parsenormalcolumn: tabular: Improved memory management: Not using <i>xstring</i> . . . . .	430
\lWR@tabulatedatasinglecolumntag: tabular: Improved memory management: Not using <i>xstring</i> . . . . .	441, 442
\lWR@tabularendofline: Fix: Slowdown for long tables. . . . .	425
General: 2018/09/19 . . . . .	1
tabular: Improved memory management: Global boolean. .	416
tabular: Improved memory management: Not using <i>xstring</i> . . . . .	418, 868
2up: Added. . . . .	600
booklet: Added. . . . .	648
bophook: Added. . . . .	651
diagbox: Fix for par tags. . . . .	704
draftfigure: Added. . . . .	706
fancytabs: Added. . . . .	728
fullminipage: Added. . . . .	759
grid-system: Added. . . . .	779
layaureo: Added. . . . .	805
leading: Added. . . . .	808
listings: Fix for HTML entities. . .	814
listings: Fix if inside a list. . .	814, 817
thumbs: Added. . . . .	1005
thumb: Added. . . . .	1005
widows-and-orphans: Added. .	1049
v0.61	
\DeclareGraphicsExtensions: Fix: EPS for DVI LATEX. . . . .	766
\lWR@HTMLLatexCmd: Added	
HTMLLatexCmd option. . . . .	259
Added PrintLatexCmd option. .	259
\lWR@addcompilecmd: Removed spaces. . . . .	255
\lWR@closetabledatacell: Fix: Par tags in tabular. . . . .	420
\lWR@hyperindexrefnullified: Made robust, . . . . .	506
\lWRopseq: Added spaces. . . . .	219
\RequirePackage: Support up to 20 packages. . . . .	236
\inlinemathnormal: Changed name from \StopDynamicMath to \inlinemathnormal. . . . .	326
\inlinemathother: Changed name from \StartDynamicMath to \inlinemathother. . . . .	326
\listof: Fix: newfloat lists. . . . .	499
\lwarfsetup: Added. . . . .	220
General: 2018/10/13 . . . . .	1

\l warp.css: Footnotes text align left.	260
\l warp.css: Minipage table and footnotes: tighter margin.	260
chkfloat: Added.	693
cmdtrack: Added.	694
copyrightbox: Added.	697
dprogress: Added.	705
epsfig: Added.	714
graphics: Fix: EPS for DVI L <sup>A</sup> T <sub>E</sub> X.	770
graphics: Set keys before using filename, for epsfig.	774
lua-visual-debug: Added.	824
pdfprivacy: Added.	917
psfrgx: Added.	931
psfrag: Added.	931
pstool: Added.	932
refcheck: Added.	937
srcltx: Added.	976
srcTeX: Added.	976
supertabular: Fix for caption w/o opt arg.	988
thinsp: Added.	1002
threadcol: Added.	1002
uspace: Added.	1042
vpe: Added.	1046
xbmks: Added.	1052
xtab: Fix for caption w/o opt arg.	1071
Added HTMLLatexCmd option.	223
Added PrintLatexCmd option.	223
Docs: \tracingl warp	241
Docs: HTML entities.	122
Docs: Compiling using custom shell commands.	172
Docs: Fonts.	101
Docs: HTMLDebugComments	109, 241
Docs: Multiple indexes.	195
Don't write configuration files if processing pstool image.	253
Spaces redefined	
\AtBeginDocument.	581
<b>v0.62</b>	
\@partcntformat: Added for ctex.	375
\@partnameformat: Added for ctex.	375
\InlineClass: Added optional word-processing style. Replaces \LWR@HTMLtextstyle.	341
\l WR@PreloadedPackage: Added.	546
\l WR@ProvidesPackagePass: Fix: Unknown option error.	238
\l WR@endofline: Extra space if optional arg.	583
\l WR@filestart: Refactored.	385
\l WR@isolate: Added.	216
\l WR@textcurrentfont: Added print version.	581
Tracks depth to avoid nesting repeated font changes.	577
\colorboxBlock: Fix: Horiz white space.	1058, 1059
\fcolorbox: Fix: No longer requires xifthen.	552
\fcolorboxBlock: Fix: Horiz white space.	1060
\l @chapter: Don't define if no \chapter. Fix for algorithm2e.	503
\slshape: Added.	579
\textup: Fixed WP span class.	571
\theHTMLSection: Added.	383
\theHTMLTitleSection: Added.	383
\theHTMLTitleSeparator: Refactored.	382
General: 2018/11/19	1
\textbf and related: Improved font detection.	569
\l warp.css: Added css for xfrac, nicefrac.	260
\l warp.css: Fixed css for \textup.	260
\l warp.css: Reduced margins in titlepage.	260
\l warp_formal.css: Fix: Font for verse.	295
2in1: Added.	600
CJKutf8: Prevented unless xeCJK.	694
CJK: Prevented unless xeCJK.	694
asymptote: Improved alt tags.	629
bitpattern: Added.	647
calc: Fix: Required for print version.	230
chngpage: Fix: Loads \l warp-chngpage.	693
ctexpatch: Added patch.	595
flippdf: Added.	738
graphics: Fix: Filename expansion.	772
graphics: Fix: FormatWP.	770
musicography: Added.	871
nicefrac: Improved font control and css, honors nice, ugly.	887
notespages: Added.	891
octave: Added.	903
pdfcomment: Added.	913
pdfmarginpar: Added.	915
register: Updated to v1.8.	938
rviewport: Added.	944
semantic-markup: Added.	954
textcomp: Fix conflict with xunicode.	996
tram: Added.	1031
twoup: Added.	1034

ullem: Improved compatibility with CJKulem. . . . .	1036	\LWR@notltjloadafter: Added more classes. . . . .	200																																						
ullem: Now works in a lateximage. . . . .	1036	Added. . . . .	200																																						
unitsdef: Added. . . . .	1041	\LWR@subhtmlelementclass: Fix for xeCJK. . . . .	339																																						
units: Improved font control and css, honors loose, tight. . . . .	1040	\LinkHome: Fix: Print version. . . . .	330																																						
xchangebar: Added. . . . .	1063	\linkhomename: Added. . . . .	330																																						
xfrac: Improved css. . . . .	1066	General: 2018/12/03 . . . . .	1																																						
xunicode: Fix conflict with textcomp. . . . .	1072	\l warp.css: Added css for vertical writing. . . . .	260																																						
Added early checks for CJK, CJKutf8. . . . .	202	\l warp.css: Improved css for mdframed. . . . .	260																																						
Docs: asymptote. . . . .	159	amsthm, mdframed: Fix for enforced load order. . . . .	619																																						
Docs: miktex-poppler-bin-* . . . . .	83	emumitem: v3.6: Nullify \DrawEnumitemLabel. . . . .	712																																						
Docs: MiKTEX Console . . . . .	79	everyhook: Fix for bxjs* classes. . . . .	231																																						
Docs: Improved MiKTEX install instructions. . . . .	79	geometry: Fix for bxjs* classes. . . . .	229																																						
Docs: UTF-8 locale. . . . .	175	mdframed: Avoid thin rules. . . . .	841																																						
File: l warp_mathjax.txt: Removed inoperable siunitx extension. . . . .	301	mdframed: Improved font control. . . . .	844–846																																						
Fix for \em. . . . .	573	stfloats: Adapted to ltj* classes. . . . .	979																																						
Fix: Horiz white space. . . . .	1060	xpinyin: Added. . . . .	1069																																						
Logos: CSS instead of <sup>, <sub>. . . . .	590	zhlineskip: Added. . . . .	1075																																						
Logos: Fix for X E T E X logo if graphics is not loaded. . . . .	590	Added pTeXsupport. . . . .	199																																						
Logos: Improved CSS. . . . .	590	Docs: \linkhomename. . . . .	109																																						
Logos: Made robust. . . . .	590	Docs: \sidetocname. . . . .	111																																						
fcolorminipage: Fix: Horiz white space. . . . .	1061	Fix: Default \LWR@mdfive. . . . .	212																																						
Fix: No longer requires xifthen. . . . .	553	Improved titles. . . . .	844, 845																																						
fminipage: Fix: Horiz white space. . . . .	568	pTEX: Encoding. . . . .	213																																						
\LWR@blocktextcurrentfont: Added print version. . . . .	581	pTEX: Load upquote. . . . .	214																																						
v0.63		pTEX: No newunicodechar. . . . .	213																																						
\LWR@HTMLLatexCmd: ujarticle and related: Compile options. . . . .	259	\LWR@BlockClassWP: Fix for xeCJK. . . . .	342																																						
\LWR@LwarpStart: Fixes for xeCJK. . . . .	386	v0.64																																							
\LWR@atbeginverbatim: Fix for xeCJK. . . . .	403	\LWR@checkloadbefore: Added. . . . .	201	\LWR@HTMLLatexCmd: utarticle and related: Added. . . . .	259	\LWR@checkloadfilename: Added to reduce number of l warp-* files. . . . .	234	\LWR@checkloadfilename: Prevented bitfield, doublespace, newthm, rplain, si. . . . .	234	\LWR@checkloadnever: Added. . . . .	201	\LWR@section: Support for ujarticle and related. . . . .	378	\LWR@compileuplatex: Added. . . . .	256	\enskip: Made robust. . . . .	584	\LWR@createautosec: Fix for xeCJK. . . . .	373	\qqquad: Made robust. . . . .	584	\LWR@earlyclassloadnever: Added. . . . .	202	\quad: Made robust. . . . .	584	\LWR@filestart: Fix: Break ligature for luatexko. . . . .	385	\theHTMLTitleSeparator: Added utarticle and related. . . . .	382	\LWR@firstoffour: Added. . . . .	216	General: 2018/12/08 . . . . .	1	\LWR@htmlclosecomment: Fix: Break ligature for luatexko. . . . .	338	addlines: Updated to v0.3. . . . .	609	\LWR@isolate: Fix for xeCJK. . . . .	216	biblatex: Added patch for C T E X . . . . .	643
\LWR@checkloadbefore: Added. . . . .	201	\LWR@HTMLLatexCmd: utarticle and related: Added. . . . .	259																																						
\LWR@checkloadfilename: Added to reduce number of l warp-* files. . . . .	234	\LWR@checkloadfilename: Prevented bitfield, doublespace, newthm, rplain, si. . . . .	234																																						
\LWR@checkloadnever: Added. . . . .	201	\LWR@section: Support for ujarticle and related. . . . .	378																																						
\LWR@compileuplatex: Added. . . . .	256	\enskip: Made robust. . . . .	584																																						
\LWR@createautosec: Fix for xeCJK. . . . .	373	\qqquad: Made robust. . . . .	584																																						
\LWR@earlyclassloadnever: Added. . . . .	202	\quad: Made robust. . . . .	584																																						
\LWR@filestart: Fix: Break ligature for luatexko. . . . .	385	\theHTMLTitleSeparator: Added utarticle and related. . . . .	382																																						
\LWR@firstoffour: Added. . . . .	216	General: 2018/12/08 . . . . .	1																																						
\LWR@htmlclosecomment: Fix: Break ligature for luatexko. . . . .	338	addlines: Updated to v0.3. . . . .	609																																						
\LWR@isolate: Fix for xeCJK. . . . .	216	biblatex: Added patch for C T E X . . . . .	643																																						

scrpage2: Added. . . . .	951	pxeveryshi: Added. . . . .	933
ujarticle and related: Improved		pxftnright: Added. . . . .	934
\today. . . . .	594	pxjahyper: Added. . . . .	934
Added utarticle and related. . . . .	594	tascmac: Added. . . . .	992
v0.65		versonotes: Added. . . . .	1044
\LWR@LwarpEnd: Improved css for		Added early checks for jarticle,	
page layout. . . . .	389	tarticle, and related. . . . .	202
\LWR@LwarpStart: Improved css for		Fix for \rensaji. . . . .	594
page layout. . . . .	388	Fix space between class and id. . . . .	342
\LWR@PreloadedPackage:		tabular: Added support for plect. . . . .	470
\AtBeginDocument to avoid		Fix: tabular*. . . . .	470
option clashes. . . . .	546	Fix: Rule color. . . . .	472
\LWR@hyperindexrefnullified:		minipage: Refactored to later allow	
Added \textsi. . . . .	506	Japanese <t/y> argument. . . . .	560
\LWR@newhtmlfile: Error if duplicate		\LWR@figcaption: Uses	
file name. . . . .	369	<figurecaption> instead of	
Improved css for page layout. . . . .	368, 371	<figcaption>. . . . .	493
\LWR@nullfonts: Added \sishape. . . . .	574	v0.66	
Added \textsi. . . . .	573	\@mpfootnotetext: Improved HTML	
\LWR@restoreorigformatting: Fix:		formatting. . . . .	356
tabular*. . . . .	509	\IgnoreMinipageWidths: Added, . . . . .	560
\enskip: Changed to Unicode EN		\LWR@footnotetext: Improved HTML	
SPACE. . . . .	584	formatting. . . . .	355
\quad: Changed to Unicode EM		\LWR@LwarpStart: Fix: TOC, LOF, LOT	
SPACE. . . . .	584	links. . . . .	388
\sishape: Added \sishape. . . . .	579	\LWR@checkloadfilename: Prevented	
\textsi: Added. . . . .	572	colortab, epsf, hyper, picinpar,	
General: 2018/12/22 . . . . .	1	picins, sistyle, ucs. . . . .	234
lwrap.css: Added \sishape,		\LWR@closeparagraph: Fix: Combined	
\textsi. . . . .	260	span, tabular, and lateximage. . . . .	346
lwrap.css: Improved css for page		Improved HTML formatting. . . . .	346
layout. . . . .	260	\LWR@closeparagraph@br: Factored. . . . .	345
lwrap.css: Improved css for		\LWR@fboxstyle: Use current text	
quotations. . . . .	260	color. . . . .	566
lwrap.css: Siderocto left for		\LWR@filenamenoblocks: Fix: Section	
improved \marginpars. . . . .	260	names detokenized. . . . .	361
lwrap_formal.css: Siderocto left		Fix: Section names with macros. . . . .	362
for improved \marginpars. . . . .	295	Fix: Section names with percent. . . . .	362
lwrap_sagebrush.css: Siderocto		Improved file name generation. . . . .	361
left for improved \marginpars. . . . .	290	Limits filename length. . . . .	363
boundddvi: Added. . . . .	652	\LWR@findcurrenttextcolor: Fix:	
embrac: Added. . . . .	709	Color if xcolor not loaded. . . . .	581
footnoterange: Added. . . . .	755	\LWR@htmlfileref: No longer use	
gentombow: Added. . . . .	761	zref. . . . .	478
geometry: Fix for bxjs* classes. . . . .	229	\LWR@htmlsectionfilename: Sanitize	
graphics: Added \includegraphics		underscores. . . . .	328
alt key. . . . .	550, 766, 768, 770, 773	\LWR@indentHTML: Added. . . . .	335
lltjext: Added. . . . .	818	\LWR@lateximagedepthref: No longer	
multicolrule: Added. . . . .	865	use zref. . . . .	478
multicol: Added \docolaction. . . . .	865	\LWR@lateximagenumberref: No	
plarydshln: Added. . . . .	928	longer use zref. . . . .	479
plextrydshln: Added. . . . .	929	\LWR@lwarplabel: No longer use zref. . . . .	479
plextcolortbl: Added. . . . .	929	\LWR@nameref: No longer use zref. . . . .	478
plexit: Added. . . . .	928	\LWR@nullfonts: Logos. . . . .	576
pxatbegshi: Added. . . . .	933		

\LWR@openparagraph: Improved HTML	
formatting. . . . .	345
\LWR@section: Fix: TOC, LOF, LOT	
links. . . . .	379
Improved HTML formatting. . . . .	379
\LWR@setexpparray: Fix with \par. .	324
\LWR@setref: No longer use zref. .	478
\LWR@simplifyname: Added. . . . .	360
\LWR@startref: No longer use zref. .	481
\LWR@stoppars: Improved HTML	
formatting. . . . .	348
\LWR@subhtmllementclass:	
Improved HTML formatting. . . . .	339
\LWR@subhyperrefclass: Improved	
HTML formatting. . . . .	485
\LWR@subinlineimage: Improved	
HTML formatting. . . . .	486
\LWR@writeconf: Added	
ImagesDirectory and	
ImagesName. . . . .	259
\LinkHome: Fix: Document	
cross-references. . . . .	330
\UseMinipageWidths: Added, . . . . .	560
\fbox: Fix: Removed extra space. .	566
\hyperindexref: Fix: Long index	
entries. . . . .	506
\minipagefullwidth: Made \global. .	560
\rotatebox: Improved HTML	
formatting. . . . .	776
\rule: Improved HTML formatting. .	588
\scalebox: Improved HTML	
formatting. . . . .	777
\textgreater: Made robust. . . . .	327
\textless: Made robust. . . . .	327
General: 2019/02/08 . . . . .	1
\LWR@currentautosec: Fix for LOF,	
LOFfloat in home page. . . . .	375
\l warp.css: Added niceframe. . . .	260
\l warp.css: Improved css for	
definition lists. . . . .	260
\l warp_formal.css: Improved css	
for table notes. . . . .	295
\l warp_one_limage.txt: Image	
directory and prefix. . . . .	300
\acronym: Fix for acronym in	
caption. . . . .	608
\acronym: No longer uses zref. .	608
\ar: Added. . . . .	624
\caption: Fix for options clash. .	239
\ed: Added. . . . .	708
\extramarks: Updated to v3.10. .	721
\fancyhdr: Updated to v3.10. .	726
\fancyvrb: Improved HTML	
formatting. . . . .	723
graphics: Improved HTML	
formatting. . . . .	773
\kotexutf: Patch for references. .	596
\memoir: Docs re: version	
numbers. . . . .	167
\multicولrule: Updated for v1.2. .	865
\nameauth: Added. . . . .	874
\register: Verified for v1.9. . . . .	938
\subcaption: Added. . . . .	980
\tocbasic: Updated to v3.26a. .	1018
\truncate: Added. . . . .	1034
\zref: No longer used. . . . .	232
\l warpmk: Added ImagesDirectory	
and ImagesName. . . . .	303
\l warpmk: Fix for \cleanimages. .	303
Added early checks for colortab,	
\epsf, \hyper, \picinpar, \picins,	
\sistyle, \ucs. . . . .	202
Added option ImagesDirectory. .	221
Added option ImagesName. . . . .	221
Added support for indentfirst. .	349
\Docs: Updated Converting an	
existing document. . . . .	99
\Fix: Minipages inside multicols. .	865
\Improved HTML formatting. . . . .	730
\Package dates added where	
possible. . . . .	600
\Sanitize filenames. . . . .	225
\tabular: Fix: Minipages inside	
\tabular. . . . .	474
\latextimage: Added \BaseJobname for	
multiple projects. . . . .	539
\Improved HTML formatting. . . . .	540
\minipage: Honor	
\LWR@forceminipagefullwidth. .	561
v0.67	
\FilenameNullify: Added. . . . .	577, 581
\FilenameSimplify: Added. . . . .	361, 368
\LWR@doequation: \x fakebold: Added	
support. . . . .	527
\LWR@doubledollar: \x fakebold:	
Added support. . . . .	521
\LWR@filenamenoblocks: Improved	
file name generation. . . . .	361
\LWR@lookforpackagename:	
\easyReview: Supported. . . . .	235
\LWR@nullfonts: Add'l symbols. .	574
\LWR@simplifycustom: Added. . . . .	361
\LWR@subsingle dollar: \x fakebold:	
Added support. . . . .	519
\LWR@subsingle dollar: \x fakebold:	
Added support. . . . .	517, 518
General: 2019/02/23 . . . . .	1
\academicons: Added. . . . .	603
\bbding: Added. . . . .	638

changes:	Added.	663
color:	Fix for version number.	695
dingbat:	Added.	704
eurosym:	Added.	719
fitbox:	Added.	736
fontawesome5:	Added.	751
fontawesome:	Added.	749
foreign:	Added.	755
gloss:	Added.	763
karnaugh-map:	Added.	797
marvosym:	Added.	833
multicap:	Added.	864
nomencl:	Added.	889
notes:	Added.	890
pifont:	Added.	927
struktex:	Added.	980
textcomp:	Nullify in filenames.	996
typicons:	Added.	1035
umoline:	Added.	1037
xfakebold:	Added support.	511
xfakebold:	Added.	1065
xunicode:	Nullify in filenames.	1073
AMS environments:	Added xfakebold support.	616
eqnarray:	xfakebold: Added support.	533
v0.68		
\LWR@footnotetext:	Factored for multiple foot boxes.	354
\LWR@checkLoadfilename:	Prevented alg, algorithmic, fncylab, pdfcprot.	234
\LWR@printpendingfootnotes:	Factored for multiple footnote boxes.	357
\LWR@tabular@warpprintonly:	Added.	470
General: 2019/03/05		1
bigfoot:	Added.	646
fnpara:	Added.	749
footnotebackref:	Added.	754
hyperref:	Fix for options with braces.	783
layouts:	Added.	806
listings:	Fix for listings v1.7.	817
longtable:	Improved error handling.	820
manyfoot:	Added.	829
niceframe:	Added.	888
perpage:	Added.	920
showtags:	Added.	957
tablefootnote:	Added.	990
threeparttable:	Added.	1004
threeparttable:	Fix for caption type.	1003
\warpmk:	Improved error handling if incomplete compile.	303
Prevented alg, algorithmic, fncylab, pdfcprot.		202
tabular:	Fix: \warpprintonly inside tabular.	472
v0.69		
\LWR@maybetocdata:	Added support for tocdata.	501
\framebox:	Fix: Handle paren arg.	565
\hypertoc:	Added support for tocdata.	501
\hypertocfloat:	Added support for tocdata.	503
\makebox:	Fix: Handle paren arg.	564
\multicolumnrow:	multirow: Error if \multirow without \mrowcell.	869
General: 2019/03/21		1
array:	Fix for \tabularnewline.	626, 821
ctable:	Added.	698
eqlist:	Added.	716
eqparbox:	Added.	716
ftcap:	Added.	759
graphics:	Warning if using scale option.	768
keyfloat:	Updated for v2.00.	800
listliketab:	Added.	817
minitoc:	Added.	857
multirow:	Error if \multirow without \mrowcell.	868
rotfloat:	Requires graphicx.	942
supertabular:	Fix: Clear caption after use.	989
tabularx:	Require array.	991
tabulary:	Require array.	991
tocdata:	Added.	1020
topcapt:	Added.	1031
xtab:	Fix: Clear caption after use.	1072
tabular:	Error if \multirow without \mrowcell.	471, 473, 475
lateximage:	Fix for pdftotext errors from font size change.	543
fminipage:	Honors \minipagefullwidth.	568
v0.70		
\LWR@closeparagraph:	Reduced underfull \hbox warnings.	346
\LWR@lookforpackagename:	changes: Updated to v3.1.2.	235
\LWR@mathjaxfilename:	Added.	351
\LWR@restoreorigformatting:	Fix: \& in a lateximage.	509
\MathJaxFilename:	Added.	351

\enddocument: If labels changed, require recompile before making images. . . . .	390
\framebox: Fix: Accept long arg. . .	565
\makebox: Fix: Accept long arg. . . .	564
Fix: Ignore width of opt. . . . .	564
Fix: No width given. . . . .	564
General: 2019/04/03 . . . . .	1
autonum: Added. . . . .	634
caption: Fix: Extra par tags. . . . .	659
changelayout: Added. . . . .	662
changes: Updated to v3.1.2. . . . .	663
inputrc: Added. . . . .	796
mathtools: Added. . . . .	835
metalogo: Added. . . . .	851
metalogo: Used in print mode. . .	851
textcomp: Fix for \textinterrobang. . . . .	994
textpos: Added optional arg to textblock. . . . .	998
xunicode: Fix for \textinterrobang. . . . .	1073
AMS environments: Refactored. .	616
Ensure vector font. . . . .	214
File: lwarpmathjax.txt: Loads autoload-all.js extension. . .	301
File: lwarpmathjax.txt: Updated to MathJax v2.7.5. . . . .	301
Logos: Improved for metalogo, lateximages. . . . .	590
LWR@nestspan: Improved minipage, \parbox inside a span. . . . .	336
<b>v0.71</b>	
\@mpfootnotetext: Improved HTML formatting. . . . .	356
Reduced underfull \hbox warnings. .	356
\LWR@closeparagraph: Flush left captions. . . . .	346
\LWR@closetabledatacell: Fix: Tabular par tags. . . . .	420, 421
\LWR@stoppars: Reduced underfull \hbox warnings. . . . .	348
\expandcolspe: Added support for tabular '*' column. . . . .	432
General: 2019/04/29 . . . . .	1
chemfig: Updated for v1.4. . . . .	666
endfloat: Updated for v2.7. . . .	710
lwarpm-common-multimedia: Added. . . . .	1104
media9: Added. . . . .	849
movie15: Added. . . . .	863
multimedia: Added. . . . .	866
textpos: Updated for v1.9.1. . . .	998
<b>v0.72</b>	
\lwarpmk: If wrong lwarpmk.conf version, or wrong OS, displays the print command to recompile. . .	303
Docs: Error testing. . . . .	188
Fix: blockquotation tag. . . . .	401
Reduced underfull \hbox warnings. .	660
\lWR@newautopagelabel: Fix: References for xr, xr-hyper. . .	364
\lWR@printmccoldata: Fix: \multicolumn parameters. . . . .	454
\lWR@restoreorigformatting: Use \lWR@formatted for \bfseries, etc. . . . .	509
\chapter: Added support for hypbmsec. . . . .	381
\ebweight: nfssext-cfr: Added. . .	578
\hypertoc: Fix: References for xr, xr-hyper. . . . .	501
\hypertocfloat: Fix: References for xr, xr-hyper. . . . .	502
\lgweight: nfssext-cfr: Added. . .	578
\paragraph: Added support for hypbmsec. . . . .	382
\part: Added support for hypbmsec. .	381
\section: Added support for hypbmsec. . . . .	382
\subparagraph: Added support for hypbmsec. . . . .	382
\subsection: Added support for hypbmsec. . . . .	382
\subsubsection: Added support for hypbmsec. . . . .	382
\texteb: nfssext-cfr: Added. . . . .	570
\textlg: nfssext-cfr: Added. . . . .	570
\textulc: fontaxes: Added. . . . .	572
\ulcshape: fontaxes: Added. . . . .	579
General: 2019/06/08 . . . . .	1
lwarpc.css: Added backnaur. . . .	260
lwarpc.css: Removed unneeded support for \sisshape, \textsi. .	260
backnaur: Added. . . . .	637
boxedminipage2e: Added support for lateximages. . . . .	652
changes: Fix references for xr, xr-hyper. . . . .	663
fontaxes: Added. . . . .	577, 751
gloss: Fix references for xr, xr-hyper. . . . .	763
hypbmsec: Added. . . . .	782
minibox: Added. . . . .	856
nfssext-cfr: Added. . . . .	879
nomenc: Fix references for xr, xr-hyper. . . . .	889
pdfcrypt: Added. . . . .	914

shapepar: Added.	956	General: 2019/07/11	1
slantsc: Added.	971	l warp.css: Added \book for	
soulutf8: Fix: Loads soul.	974	memoir.	260
tabfigures: Added.	990	l warp.css: Improved pkgtodata	
xr-hyper: Added.	1070	formatting.	260
xr: Added.	1070	l warp_formal.css: Added \book	
zhlineskip: Updated to v1.0e.	1075	for memoir.	290, 295
Use \LWR@formatted for		boxedminipage2e: Fix: Paragraph	
\bfseries, etc.	250, 578	tags.	652
v0.73		caption: Fix for starred captions.	658
\@include: Fix: \newpage instead of		epigraph: Fix: Paragraph tags.	713
\clearpage.	240	fancyvrb: Fix: Nested	
\HTMLTitle: Added default title if		<div>/<pre>.	731, 733
none specified.	351	fancyvrb: Btrivlist: Fixed	
\LWR@LwarpEnd: Fix: Empty		paragraph tags.	725
header/footer.	389	intopdf: Updated to v0.2.1.	796
\LWR@LwarpStart: Fix: Empty		listings: Fix: Paragraph tags.	816
header/footer.	388	l warp-common-multimedia: Fix:	
\LWR@addbaselinemarker: Improved		No size for audio file.	1105, 1106
warning messages.	512	l warp-common-multimedia: Fix:	
\LWR@descitem: Fix: HTML tags.	411	Paragraph tags.	1107
\LWR@forceemptyline: Added.	216	l warp-patch-komascript: Fix for	
\LWR@gsavebox: Added global save		captions.	1078
boxes.	217	l warp-patch-memoir: Added	
\LWR@htmlelementclass: Vertical		\book.	1084
space.	339	l warp-patch-memoir: Fix for	
\LWR@htmlelementclassline: Vertical		\frontmatter* and	
space.	340	\mainmatter*.	1084
\LWR@indentHTMLtwo: Added.	335	lyluatex: Added.	827
\LWR@indexitem: Fix: Avoid empty		musicography: Updated to	
<span>.</span>	505	2019/05/28. Now supports	
\LWR@indexsubitem: Fix: Avoid empty		lateximages.	871
<span>.</span>	505	quotchap: Fix: Paragraph tags.	935
\LWR@indexsubsubitem: Fix: Avoid		quotchap: Updated to v1.2.	934
empty <span>.</span>	505	quoting: Fix: Paragraph tags.	935
\LWR@newhtmlfile: Fix: Empty		scrextend: Fix: Paragraph tags.	946, 947
header/footer.	368, 371	stackengine: Added.	977
\LWR@nullfonts: Fix: \hspace in		threepartable: Added	
sectioning file name.	576	measuredfigure.	1003
\LWR@titlingmaketitle: titling: Fix:		tocdata: Honors \tocdataformat.	1020
Paragraph tags.	398, 1017	tocdata: Improved formatting.	1020
Fix: Paragraph tags.	398	tocdata: Updated to v2.03.	1020
\attribution: Fix: Paragraph tags.	400	versionotes: Updated to v0.4.	1044
\color: Added HTML support.	1057	vwcol: Fix: Paragraph tags.	1047
\fboxBlock: Fix: Paragraph tags.	566	xy: Fix for \xybox.	1074
\hspace: Fix: Avoid empty <span>.</span>	585	xy: Improved xy, reverted	
\l@book: Added \book for memoir.	503	\ymatrix, for qcircuit.	1074
\maketitle: titling: Fix: Paragraph		Added \book for memoir.	321, 334
tags.	1016	AMS environments: Fix: alt tags.	616
Fix: Paragraph tags.	397	AMS environments: Fix: Paragraph	
\marginparBlock: Fix: Paragraph		tags.	616, 617
tags.	359	Fix: Paragraph tags.	393
\postbookname: Added \book for		Numbered HTML entity used for	
memoir.	380	text dollar.	512
\rule: Fix: Avoid empty <span>.</span>	589		

tabular: Fix and warning for tabular inside a <span>. . . . .	470	mhchem: Modified for new lateximage. . . . .	853
LWR@blocktextcurrentfont: Fix:		pdfpages: Adjust to user's paper	
Paragraph tags. . . . .	577	size. . . . .	917
LWR@nestspan: Fix: quote, quotation inside a span. . . . .	336	stackengine: alt tags. . . . .	977
v0.74		struktex: alt text. . . . .	980
\@ensuredmath: Add \ThisAltText. .	523	tikz: Added alt text. . . . .	1006
\AltTextClose: Added. . . . .	510	<i>lwarpmk</i> : <b>lwarpmk clean</b> removes add'l files. . . . .	303
\AltTextOpen: Added. . . . .	510	<i>lwarpmk</i> : <b>lwarpmk epstopdf</b> and <b>pdftosvg</b> honor directories. . . . .	303
\ImageAltText: Added. . . . .	510	Add \ThisAltText. . . . .	617
\LWR@ThisAltText: Add		Remembers user's geometry. . . . .	228
\ThisAltText. . . . .	511	lateximage: Add \ThisAltText. . . . .	544
\LWR@addlinktitle: Added. . . . .	481	Added second starred argument. . . . .	539, 544
\LWR@doequation: Add		Improved alt text. . . . .	541
\ThisAltText. . . . .	528	New syntax for	
\LWR@doubledollar: Add		\LWR@subinlineimage. . . . .	543
\ThisAltText. . . . .	521	eqnarray: Add \ThisAltText. . . . .	534
\LWR@lateximage@oneimage: Factored from lateximage. . . . .	538	LWR@displaymathother: Uses	
\LWR@lateximage@oneimageb: Factored from lateximage. . . . .	538	\MathImageAltText. . . . .	523
\LWR@setcurrentfont: Factored. . . . .	512	LWR@equationother: Uses	
\LWR@singledollar: Add		\MathImageAltText. . . . .	524
\ThisAltText. . . . .	521	v0.75	
\LWR@singledollarmeasure: Fix: Font control. . . . .	514	\normalcolor: Added for HTML. . . . .	1056
\LWR@subinlineimage: Add		General: 2019/09/23 . . . . .	1
\ThisAltText. . . . .	486	<i>l warp.css</i> : Improved marginblock. . . . .	260
\LWR@subsingledollar: Add		keyfloat: Fix: \normalcolor. . . . .	800
\ThisAltText. . . . .	520	wrapfig: Fix for \linewidth. . . . .	1051
\LWR@subsingledollarsvg: Adds star argument for lateximage. . . . .	517	wrapfig: Fix for width. . . . .	1051
\LateximageFontScale: Adjusted svg math font scaling default to 1. . . . .	536	minipage: Fix: \linewidth. . . . .	562
\MathImageAltText: Renamed from		v0.76	
\mathimage. . . . .	510	General: 2019/10/08 . . . . .	1
\PackageDiagramAltText: Renamed from \packagediagramname. . . . .	511	<i>l warp.css</i> : Fix for small caps. . . . .	260
\ThisAltText: Add \ThisAltText. . . . .	511	acro: Updated for v2.10. . . . .	605
\hspace: Ignore negative space. . . . .	584	xr-hyper: Updated for v6.1. . . . .	1070
General: 2019/09/02 . . . . .	1	xr: Updated for v5.05 and xr-hyper v6.1. . . . .	1070
<i>l warp.css</i> : Added <i>lyluatex</i> . . . . .	260	Docs expanded: Multiple projects. . . . .	96
forest: alt text. . . . .	756	File: <i>lwarpmathjax.txt</i> : Updated to MathJax v2.7.6. . . . .	301
geometry: Remembers user's		v0.77	
geometry. . . . .	761	General: 2019/10/15 . . . . .	1
graphics: Add		booktabs: Updated to v1.6180339. . . . .	650
\ThisAltText. . . . .	768, 773, 774	chemformula: Updated to v4.15. . . . .	669
<code>lyluatex</code> : Adapts to user's geometry. . . . .	827	v0.78	
<code>lyluatex</code> : Preserves left margin. . . . .	827	\LWR@linkcatcodes: <b>babel-french</b> :	
<code>lyluatex</code> : Renamef		Fix: Hyperlinks. . . . .	484
\lyluateximangename. . . . .	827	Factored. . . . .	484
<code>lyluatex</code> : Split system images, assign class. . . . .	827	\LWR@linkmediacatcodes:	
		<b>babel-french</b> : Fix: Hyperlinks. . . . .	484
		Factored. . . . .	484

\LWR@nullifyNoAutoSpacing:	
babel-french: Fix: Hyperlinks.	470
\LWR@subhyperrefclass:	Remove extra space.
485	
\normalfont:	Uses \LWR@formatted.
579	
General:	2019/11/07
1	
accessibility:	Added.
604	
babel-french:	Fix: Hyperlinks.
334	
caption:	Added warning regarding passing options.
657	
filecontents:	Fix to overwrite existing files using new filecontents environment.
231	
geometry:	Cleaner option handling.
761	
graphics:	Fix: alt tag expansion.
773	
lwrap-common-multimedia:	Fix links with new LaTeX kernel.
1105	
titlesec:	Fix for \titleclass.
1012	
v0.79	
\CustomizeMathJax:	Fix: Sanitize for HTML.
366	
\LWR@HTMLsanitizeexpand:	Fix: \&.
365	
\LWR@ProvidesPackagePass:	Fix: catoptions.
237	
\LWR@checkloadfilename:	Prevented bxcjkjatype, hangul.
234	
\LWR@closetabledatacell:	Fix: Nested tabulars.
421	
\LWR@customizeMathJax:	MathJax: Hide definitions.
367	
\LWR@earlyloadnever:	Factored.
202	
\LWR@forcenewautoidanchor:	Factored.
491	
\LWR@mathjaxwarn:	Warn if using packages not supported by MATHJAX.
597	
\LWR@parseaftercolumn:	Remove outermost braces.
428	
\LWR@parseatcolumn:	Remove outermost braces.
426	
\LWR@parsebangcolumn:	Remove outermost braces.
427	
\LWR@parsebeforecolumn:	Remove outermost braces.
427	
\LWR@setexparray:	Fix: Nested tabulars.
324	
\LWR@singledollarmeasure:	Factored.
514	
\LWR@subHTMLsanitize:	Fix: \&. Factored.
364	
\LWR@subsingledollarsvg:	Adjust for unknown size.
517	
Factored.	516
\LWR@tabularendofline:	Fix: Nested tabulars.
425	
\captionlistentry:	Fix: Duplicate auto-id.
494	
\macrotocname:	Added.
217	
\makebox:	Fix: Adjust for virtual page size.
564	
\multicolumnrow:	multirow: Fix: Nested tabulars.
870	
\noalign:	Fix: Nested tabulars.
469	
General:	2020/02/01
1	
MATHJAX:	Additional macros.
367	
lwrap.css:	Fix: Nested tabulars.
260	
amsmath:	Added MATHJAX emulation.
618	
arydshln:	Added MATHJAX emulation.
628	
ar:	Added MATHJAX emulation.
625	
awesomebox:	Added.
635	
babel and polyglossia:	Added info messages.
596	
bigdelim:	Added MATHJAX emulation.
646	
bigstrut:	Added MATHJAX emulation.
647	
bm:	Added.
648	
booktabs:	Added MATHJAX emulation.
651	
booktabs:	Fix for memoir with lateximage.
469, 650	
braket:	Added.
652	
epigraph:	Updated to v1.5e.
714	
floatflt:	Improved width control.
740	
fontawesome5:	Supports font size, color.
751	
fontawesome:	Refactored with fix for FAthree.
749	
fontawesome:	Supports font size, color.
749	
geometry:	Also save \textwidth, \textheight.
229	
graphics:	Factored from \LWR@includegraphicsb.
770, 772	
graphics:	Fix for negative angles.
769	
ifpdf, ifptex:	Provided by iftex.
199	
ltablex:	Fix: Require longtable.
822	
ltxtable:	Fix: Required packages.
823	
luatex85:	Removed.
199	
mathtools:	Added MATHJAX emulation.
836	
multirow:	Add: MATHJAX emulation.
870	
multirow:	Fix: Centered vertical alignment.
868	

niceframe: Fix: Adjust for virtual	
page size. . . . .	888
parallel: Added. . . . .	906
parcolumns: Added. . . . .	908
pdfcolfoot: Added. . . . .	912
pdfcolmk: Added. . . . .	912
pdfcolparallel: Added. . . . .	912
pdfcolparcolumns: Added. . . . .	913
pdfcol: Added. . . . .	911
physics: Added. . . . .	922
siunitx: Fix: \square, \cubed. . .	965
siunitx: Improved MATHJAX. .	963, 964
slashed: Added. . . . .	971
steinmetz: Added. . . . .	979
subcaption: Fix with memoir. . .	1080
svg: Added. . . . .	989
transparent: Supports	
lateximages. . . . .	1032
unicode-math: Added. . . . .	1038
widetable: Added. . . . .	1049
witharrows: Added. . . . .	1050
xcolor: Fix: Nested	
tabulars. . . . .	1062, 1063
xltabular: Fix: Require ltablex. .	1067
xurl: Updated to v0.08. . . . .	1073
AMS environments: Fix:	
Nested. . . . .	616, 617
Factored to	
\LWR@setvirtualpage. . . . .	744, 773, 805
Fix: Use newfloat instead of float. .	745
Fix: Use full \linewidth. . . . .	744
Remember HTML font size. . . . .	582
tabular: colortbl: Fix: Nested	
tabulars. . . . .	472
Fix: Nested tabulars. . . . .	475
warpMathJax: Added. . . . .	227
lateximage: Improved \linewidth. .	541
minipage: Fix: \linewidth frame	
padding. . . . .	562
Fix: Adjust for virtual page size. .	561
fminipage: Fix: Adjust for virtual page	
size. . . . .	568
\LWR@setvirtualpage: Factored. . .	559
v0.80	
\CustomizeMathJax: Fix: Made	
\@onlypreamble. . . . .	366
Warn of slow compile. . . . .	366
\LWR@checkloadfilename: Prevented	
formula, shadethm, slashbox. . .	234
\LWR@infoprocessingmathjax: Add:	
Info message. . . . .	367
\LWR@restoreorigformatting:	
Improved math, displaymath. . .	510
\fcolorbox: Made robust. . . . .	552
\fcolorboxBlock: Made robust. . .	552
\includegraphics: Made robust. . .	774
General: 2020/02/19 . . . . .	1
\textrbf and related: Use HTML	
series, etc. . . . .	569
accessibility: Added MATHJAX	
emulation. . . . .	604
autobreak: Added. . . . .	634
biblatex: Creates hyperlinks. . .	643
centernot: Added. . . . .	661
chemmacros: Updated to	
v5.10. . . . .	680, 687
extarrows: Added. . . . .	720
fewerfloatpages: Added. . . . .	735
fouridx: Added. . . . .	756
gensymb: Added. . . . .	760
ghsystem: Added. . . . .	762
gmeometric: Requires geometry. .	765
hhline: Added. . . . .	782
leftidx: Added. . . . .	809
mathcomp: Added. . . . .	833
mathdots: Added. . . . .	834
mathfixs: Added. . . . .	834
mismath: Added. . . . .	858
nccmath: Added. . . . .	877
noitcrl: Added. . . . .	889
pdfcomment: Added MATHJAX	
emulation. . . . .	914
relsize: Added MATHJAX emulation.	940
rmathbr: Added. . . . .	941
subsubscripts: Added. . . . .	986
unicode-math: Improved	
MATHJAX. . . . .	1038
url: Creates hyperlinks. . . . .	1042
xfrac: Added MATHJAX emulation. .	1067
AMS environments: Fix: Centering	
starred envs. . . . .	616, 617
Improved math, displaymath. . .	523
Prevented formula, shadethm,	
slashbox. . . . .	202
lateximage: Fix: Rule color in	
lateximage. . . . .	542
fcolorminipage: Made robust. . . .	553
eqnarray: Fix: eqnarray*. . . . .	533

# Index of Objects

This is an index of macros, environments, booleans, counters, lengths, packages, classes, options, keys, files, and various other programming objects. Each is listed by itself, and also by category. In some cases, they are further subdivided by [class].

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

Symbols	
\\$ . . . . .	<i>512</i>
\& . . . . .	<u>327</u> , <u>7593</u>
\( . . . . .	<u>10211</u>
*-images.txt (file) . . . . .	<i>539</i>
*_html.aux (file) . . . . .	<u>364</u> , <u>476</u> , <u>478</u> , <u>539</u>
*_html.lof (file) . . . . .	<i>492</i>
*_html.lot (file) . . . . .	<i>492</i>
*_html.tex (file) . . . . .	<i>254</i>
\, . . . . .	<i>122</i>
--shell-escape (option) . . . . .	<i>101</i>
\@setcpageref . . . . .	<u>11005</u>
\@setcref . . . . .	<u>10968</u>
\@setcrefrange . . . . .	<u>10982</u>
\author . . . . .	<i>391</i>
\begin{theorem} . . . . .	<u>7226</u>
\biblabel . . . . .	<u>9833</u>
\captiontype . . . . .	<u>9420</u>
\chapcntformat . . . . .	<u>6441</u>
\currentHref . . . . .	<u>9244</u>
\currentlabelname . . . . .	<u>9079</u>
\date . . . . .	<i>391</i>
\dblfloat . . . . .	<u>9387</u>
\donoparitem . . . . .	<u>7252</u>
\endtheorem . . . . .	<u>7238</u>
\ensuredmath . . . . .	<u>10221</u>
\float . . . . .	<u>9387</u>
\fnsymbol . . . . .	<u>7012</u>
\footnotetext . . . . .	<u>5927</u>
\include . . . . .	<u>1295</u>
\item . . . . .	<u>7265</u>
\makecaption . . . . .	<u>9443</u>
\makefnmark . . . . .	<u>5894</u>
\makefntext . . . . .	<u>5893</u>
\maketitle . . . . .	<u>56</u> , <u>7035</u>
\mklab . . . . .	<u>7246</u>
\mpfootnotetext . . . . .	<u>5929</u>
\nitem . . . . .	<u>7332</u>
\opargbegintheorem . . . . .	<u>7232</u>
\partcntformat . . . . .	<u>6442</u>
\partnameformat . . . . .	<u>6443</u>
\rowcolor{color}{color} . . . . .	<i>7964</i>
\rowcolors{color}{color}{color} . . . . .	<i>7963</i>
\secntformat . . . . .	<u>6439</u>
\starttoc . . . . .	<u>9559</u>
\textsubscript . . . . .	<u>11776</u>
\textsuperscript . . . . .	<u>11772</u>
\title . . . . .	<i>391</i>
\wrglossary . . . . .	<u>9773</u>
\wrindex . . . . .	<u>9761</u>
\[ . . . . .	<u>10211</u>
\\" . . . . .	<i>583</i>
\\$ . . . . .	<i>520</i>
\\$\$. . . . .	<i>520</i>
2in1 (package) . . . . .	<u>600</u>
2up (package) . . . . .	<u>600</u>

## A

a4 (package) . . . . .	<u>600</u>
a4wide (package) . . . . .	<u>601</u>
a5comb (package) . . . . .	<u>601</u>
abstract (environment) . . . . .	<u>7100</u>
abstract (package) . . . . .	<u>133</u> , <u>601</u>
\abstractname . . . . .	<u>112</u> , <u>7099</u>
academicons (package) . . . . .	<u>603</u>
accessibility (package) . . . . .	<u>604</u>
accsupp (package) . . . . .	<u>605</u>
acro (package) . . . . .	<u>605</u>
acronym (package) . . . . .	<u>607</u>
\addcontentsline . . . . .	<u>9508</u>
addlines (package) . . . . .	<u>609</u>
\AddSubtitlePublished . . . . .	<u>7065</u>
adjmulticol (package) . . . . .	<u>608</u>
Adobe (program) . . . . .	<u>75</u>
\affiliation . . . . .	<u>6915</u>
afterpage (package) . . . . .	<u>604</u> , <u>610</u>
algorithm2e (package) . . . . .	<u>610</u>
algorithmicx (package) . . . . .	<u>165</u> , <u>614</u>
align (environment) . . . . .	<u>83</u>
align* (environment) . . . . .	<u>86</u>
alignat (environment) . . . . .	<u>95</u>
alignat* (environment) . . . . .	<u>98</u>
\altt (package) . . . . .	<u>615</u>

\AltTextClose	114, 9909	bookmark (package)	649
\AltTextOpen	114, 9908	booktabs (package)	649
\AmS	12107	boolean:	
amsmath (package)	615	CombineHigherDepths	111, 360
amsthm (package)	619	FileSectionNames	112, 328
\and	391	FormatEPUB	176, 247
anonchap (package)	623	FormatWP	178, 247
any size (package)	623	HTMLDebugComments	112, 242
appendix (package)	133, 623	LWR@allowanothergeometry	229
ar (package)	624	LWR@amsmultiline	530
arabicfront (package)	625	LWR@copiedsidetoc	497
array (package)	626	LWR@doingapar	344
\arrayrulecolor	7971	LWR@doingcmidrule	416
\arrayrulecolor\nexttoken	7971	LWR@doingstartpars	343
arydshln (package)	626	LWR@doingtbrule	416
AsciiDoc (program)	75	LWR@dynamicmath	326
AsciiDoctor (program)	75	LWR@emptyatbang	417
Asciidoctor-LaTeX (program)	75	LWR@exittingtabular	417
asymptote (package)	159, 628	LWR@forceminipagefullwidth	560
atbegshi (package)	629	LWR@foundmrowcell	417
attachfile (package)	630	LWR@freezethisauto	491
attachfile2 (package)	631	LWR@indisplaymathimage	511
\attrib	168, 401, 1042	LWR@intabularmetadata	417
\attribution	7110	LWR@isstartingequation	537
authblk (package)	133, 633	LWR@mathmacro	325
\author	119, 391	LWR@minipagefullwidth	560
autobreak (package)	634	LWR@minipagethispar	560
autonum (package)	634	LWR@opttablecol	417
autosec	373	LWR@origmathjax	220
awesomebox (package)	635	LWR@skipatbang	417
axessibility (package)	636	LWR@skippingmcolrowcell	416
axodraw2 (package)	637	LWR@skippingmrowcell	416
LWR@starredlongtable	419		
LWR@startedrow	416		
LWR@tableparcell	416		
LWR@tabularcelladded	416		
LWR@tabularmutemods	417		
LWR@tracingl warp	241		
LWR@unknownmathsize	513		
LWR@usedmultirow	417		
LWR@validtablecol	417		
LWR@verbtags	403		
LWR@warnedcustomizemathjax	366		
LWR@xfakebold	511		
mathjax	220		
usingOSWindows	219		
warpingHTML	220		
warpingprint	220		
WPMarkFloats	179, 247		
WPMarkLOFT	180, 248		
WPMarkMath	180, 248		
WPMarkMinipages	180, 247		
WPMarkTOC	180, 248		
WPTitleHeading	181, 248		
bophook (package)	651		

## B

babel (package)	169
\backmatter	6417
backnaur (package)	637
backref (package)	637
balance (package)	638
\BaseJobname	5204
BaseJobname (option)	108, 221
bding (package)	638
\bfseries	11734
bilatex (package)	643
\bibliography	9824
\BibTeX	12100
bibunits (package)	644
bigdelim (package)	165, 645
bigfoot (package)	646
bigstrut (package)	647
bitpattern (package)	647
BlockClass (environment)	5592
\BlockClassSingle	5605
blowup (package)	648
bm (package)	648
booklet (package)	648

bounddvi (package) . . . . .	652	\color . . . . .	51	
boxedminipage2e (package) . . . . .	652	color (package) . . . . .	157, 695	
\boxframe . . . . .	194	\colorbox . . . . .	77	
braket (package) . . . . .	652	\colorboxBlock . . . . .	90, 10867	
breakurl (package) . . . . .	653	colortbl (package) . . . . .	164, 695	
breqn (package) . . . . .	653	CombineHigherDepths (boolean) . . . . .	111, 360	
bsheaders (package) . . . . .	655	comment (package) . . . . .	226	
BVerbatim (environment) . . . . .	247	\ConTeXt . . . . .	12095	
bxpapersize (package) . . . . .	655	continue (package) . . . . .	697	
bytefield (package) . . . . .	655	copyrightbox (package) . . . . .	697	
counter:				
<b>C</b>				
calc (package) . . . . .	230	FileDepth . . . . .	111, 360	
cancel (package) . . . . .	656	FootnoteDepth . . . . .	112, 353	
canoniclayout (package) . . . . .	657	footnoteReset . . . . .	354	
capt-of (package) . . . . .	495	lofdepth . . . . .	502	
caption (package) . . . . .	165, 239, 495, 657	lotdepth . . . . .	502	
\caption@begin . . . . .	9487	LWR@cellcolordepth . . . . .	419	
\caption@end . . . . .	9487	LWR@currentautosec . . . . .	375	
\captionlistentry . . . . .	9491	LWR@externalfilecnt . . . . .	511	
\captionof . . . . .	9524	LWR@hdashedlines . . . . .	416	
\CaptionSeparator . . . . .	9442	LWR@hlines . . . . .	416	
cases (package) . . . . .	660	LWR@htmldocumentnumber . . . . .	328	
center (environment) . . . . .	10759	LWR@latestautopage . . . . .	493	
\centering . . . . .	10783	LWR@lateximagedepth . . . . .	535	
\centerline . . . . .	10802	LWR@lateximagenum . . . . .	535	
centernot (package) . . . . .	661	LWR@LIPage . . . . .	536	
changebar (package) . . . . .	661	LWR@midrulecounter . . . . .	420	
changelayout (package) . . . . .	662	LWR@nextautoid . . . . .	492	
changepage (package) . . . . .	662	LWR@nextautopage . . . . .	492	
changes (package) . . . . .	663	LWR@nextequation . . . . .	524	
chappg (package) . . . . .	665	LWR@prevFileDepth . . . . .	374	
\chapter . . . . .	6644	LWR@previousautopagelabel . . . . .	364	
chapterbib (package) . . . . .	666	LWR@spandepth . . . . .	343	
chemfig (package) . . . . .	666	LWR@splitstarcopies . . . . .	431	
chemformula (package) . . . . .	668	LWR@splitstarindex . . . . .	431	
chemgreek (package) . . . . .	673	LWR@starcount . . . . .	431	
chemmacros (package) . . . . .	674	LWR@startingequation . . . . .	536	
chemnum (package) . . . . .	692	LWR@tablecolsindex . . . . .	418	
chkfloat (package) . . . . .	693	LWR@tablecolswidth . . . . .	418	
chngpage (package) . . . . .	693	LWR@tableLaTeXcolindex . . . . .	418	
cite (package) . . . . .	693	LWR@tabletotalLaTeXcols . . . . .	419	
CJK (package) . . . . .	694	LWR@tabletotalLaTeXcolsnext . . . . .	419	
CJKutf8 (package) . . . . .	694	LWR@tabularDepth . . . . .	417	
class (key) [Gin] . . . . .	770	LWR@tabularpardepth . . . . .	418	
class:				
internet . . . . .	74	LWR@thisautoid . . . . .	490	
komascript . . . . .	167	LWR@thisautoidWP . . . . .	491	
memoir . . . . .	167, 168, 1043	LWR@virtualpagedepth . . . . .	559	
\cleardoublepage . . . . .	11939	SideTOCDepth . . . . .	111, 499	
\clearpage . . . . .	11939	tocdepth . . . . .	111	
cleveref (package) . . . . .	129, 554	\cpagerefFor . . . . .	11004	
clrdblpg (package) . . . . .	694	crop (package) . . . . .	698	
cm-super (package) . . . . .	102	\CSSfilename . . . . .	112, 115, 5836	
cmap (package) . . . . .	103	ctable (package) . . . . .	698	
cmdtrack (package) . . . . .	694	\CustomizeMathJax . . . . .	6221, 6282	
		cuted (package) . . . . .	701	

cutwin (package) . . . . .	<a href="#">701</a>	warpMathJax . . . . .	<a href="#">118</a>
<b>D</b>			
\date . . . . .	<a href="#">119</a>	warpprint . . . . .	<a href="#">114, 117</a>
dblfloatfix (package) . . . . .	<a href="#">702</a>	environments:	
dblfnote (package) . . . . .	<a href="#">702</a>	abstract . . . . .	<a href="#">7100</a>
dcolumn (package) . . . . .	<a href="#">702</a>	align . . . . .	<a href="#">83</a>
\DeclareGraphicsExtensions . . . . .	<a href="#">2</a>	align* . . . . .	<a href="#">86</a>
\defaddtocounter . . . . .	<a href="#">704</a>	alignat . . . . .	<a href="#">95</a>
dejavu (package) . . . . .	<a href="#">102</a>	alignat* . . . . .	<a href="#">98</a>
description (environment) . . . . .	<a href="#">7413</a>	BlockClass . . . . .	<a href="#">5592</a>
diagbox (package) . . . . .	<a href="#">703</a>	BVerbatim . . . . .	<a href="#">247</a>
dingbat (package) . . . . .	<a href="#">704</a>	center . . . . .	<a href="#">10759</a>
\displaymathnormal . . . . .	<a href="#">152, 529, 10414</a>	description . . . . .	<a href="#">7413</a>
\displaymathother . . . . .	<a href="#">152, 529, 10425</a>	enumerate . . . . .	<a href="#">7388</a>
ditaa (package) . . . . .	<a href="#">175</a>	eqnarray . . . . .	<a href="#">10474</a>
\dotfill . . . . .	<a href="#">11857</a>	equation . . . . .	<a href="#">10388</a>
\doublerulesepcolor . . . . .	<a href="#">7973</a>	equation* . . . . .	<a href="#">10398</a>
\doublerulesepcolornexttoken . . . . .	<a href="#">7973</a>	fcolorminipage . . . . .	<a href="#">170, 10907</a>
dprogress (package) . . . . .	<a href="#">705</a>	flalign . . . . .	<a href="#">89</a>
draftcopy (package) . . . . .	<a href="#">705</a>	flalign* . . . . .	<a href="#">92</a>
draftfigure (package) . . . . .	<a href="#">706</a>	flushleft . . . . .	<a href="#">10775</a>
draftwatermark (package) . . . . .	<a href="#">706</a>	flushright . . . . .	<a href="#">10767</a>
dvipdfm (option) . . . . .	<a href="#">104, 224</a>	fminipage . . . . .	<a href="#">11313</a>
dvipdfmx (option) . . . . .	<a href="#">104, 224</a>	gather . . . . .	<a href="#">77</a>
dvips (option) . . . . .	<a href="#">104, 224</a>	gather* . . . . .	<a href="#">80</a>
<b>E</b>			
easy-todo (package) . . . . .	<a href="#">707</a>	itemize . . . . .	<a href="#">7382</a>
ebook (package) . . . . .	<a href="#">708</a>	lateximage . . . . .	<a href="#">10617, 10754</a>
\ebweight . . . . .	<a href="#">11736</a>	list . . . . .	<a href="#">7352</a>
ed (package) . . . . .	<a href="#">708</a>	longtable . . . . .	<a href="#">4</a>
ellipsis (package) . . . . .	<a href="#">709</a>	LWR@BlockClassWP . . . . .	<a href="#">5631</a>
embrac (package) . . . . .	<a href="#">709</a>	LWR@blocktextcurrentfont . . . . .	<a href="#">11723, 11804</a>
\emph . . . . .	<a href="#">11383</a>	LWR@creatinglwarpmk . . . . .	<a href="#">955</a>
emptypage (package) . . . . .	<a href="#">710</a>	LWR@displaymathnormal . . . . .	<a href="#">10256</a>
\end@dblfloat . . . . .	<a href="#">9404</a>	LWR@displaymathother . . . . .	<a href="#">10261</a>
\end@float . . . . .	<a href="#">9404</a>	LWR@equationother . . . . .	<a href="#">10275</a>
\enddocument . . . . .	<a href="#">6880</a>	LWR@figcaption . . . . .	<a href="#">9457</a>
endfloat (package) . . . . .	<a href="#">710</a>	LWR@glrbox . . . . .	<a href="#">743</a>
endheads (package) . . . . .	<a href="#">711</a>	LWR@nestspan . . . . .	<a href="#">5439</a>
endnotes (package) . . . . .	<a href="#">133, 711</a>	LWR@setvirtualpage . . . . .	<a href="#">11073</a>
\enlargethispage . . . . .	<a href="#">11938</a>	math . . . . .	<a href="#">10255</a>
\enskip . . . . .	<a href="#">583, 11883</a>	minipage . . . . .	<a href="#">11099</a>
enumerate (environment) . . . . .	<a href="#">7388</a>	multiline . . . . .	<a href="#">70</a>
enumerate (package) . . . . .	<a href="#">712</a>	multiline* . . . . .	<a href="#">73</a>
enumitem (package) . . . . .	<a href="#">712</a>	picture . . . . .	<a href="#">11064</a>
environ (package) . . . . .	<a href="#">232</a>	quotation . . . . .	<a href="#">7134</a>
environment:		quote . . . . .	<a href="#">7128</a>
fminipage . . . . .	<a href="#">125</a>	tabbing . . . . .	<a href="#">7211</a>
lateximage . . . . .	<a href="#">534</a>	tabular . . . . .	<a href="#">8914</a>
picture . . . . .	<a href="#">557</a>	thebibliography . . . . .	<a href="#">9834</a>
titlepage . . . . .	<a href="#">119</a>	theindex . . . . .	<a href="#">9734</a>
titlingpage . . . . .	<a href="#">119</a>	titlepage . . . . .	<a href="#">6932</a>
warpall . . . . .	<a href="#">118</a>	titlingpage . . . . .	<a href="#">14</a>
warpHTML . . . . .	<a href="#">115, 117</a>	verbatim . . . . .	<a href="#">7201</a>
		verse . . . . .	<a href="#">2, 7142</a>
		warpall . . . . .	<a href="#">939</a>
		warpHTML . . . . .	<a href="#">940</a>

warpMathJax	946	lwarpmk.conf	260
warpprint	943	lwarpmk.lua	186
epigraph (package)	713	project.css	116
epsfig (package)	714	project.lwarpmkconf	260
epstopdf (package)	157, 715	sample_project.css	116, 298
epstopdf (program)	155, 549	tutorial.tex	84
epstopdf-base (package)	715	filecontents (package)	231
eqlist (package)	716	FileDepth (counter)	111, 360
eqnarray (environment)	10474	\FilenameLimit	112, 6039
eqparbox (package)	716	\FilenameNullify	128, 11694, 11805
equation (environment)	10388	\FilenameSimplify	128, 6060, 6283
equation* (environment)	10398	FileSectionNames (boolean)	112, 328
errata (package)	717	fitbox (package)	736
eso-pic (package)	719	fix2col (package)	736
\etalchar	134	fixme (package)	170, 737
etoolbox (package)	199	fixmetodonotes (package)	738
eurosym (package)	719	flafter (package)	738
everyhook (package)	231	\flagverse	1043
everypage (package)	720	flalign (environment)	89
everyshi (package)	720	flalign* (environment)	92
\expandcolspec	7849	Flare (program)	75
expl3 (package)	230	flippdf (package)	738
extarrows (package)	720	float (package)	165, 739
extramarks (package)	721	floatflt (package)	740
		floatpag (package)	741
		floatrow (package)	166, 742
		fltrace (package)	747
		\flushbottom	5345
		flushend (package)	747
		flushleft (environment)	10775
		flushright (environment)	10767
		fminipage (environment)	125, 11313
		fnbreak (package)	747
		fncychap (package)	748
		fnlineno (package)	748
		fnpara (package)	749
		fnpos (package)	749
		fontawesome (package)	749
		fontawesome5 (package)	751
		fontaxes (package)	751
		fontenc (package)	102, 752
		fontspec (package)	102
		footmisc (package)	752
		footnote (package)	753
		footnotebackref (package)	754
		FootnoteDepth (counter)	112, 353
		footnotehyper (package)	754
		footnoterange (package)	755
		footnoteReset (counter)	354
		footnpag (package)	755
		\ForceHTMLPage	132, 6392
		\ForceHTMLTOC	132, 6398
		foreign (package)	755
		forest (package)	756
		FormatEPUB (boolean)	176, 247

FormatWP (boolean) . . . . .	178, 247	\HTMLFilename . . . . .	5205		
fouridx (package) . . . . .	756	\HTMLFilename (option) . . . . .	104, 109, 223		
\framebox . . . . .	11262	\HTMLFirstPageTop . . . . .	113, 5824		
framed (package) . . . . .	756	htmlglossary (option) [lwarpmk] .	134, 763		
FrameMaker (program) . . . . .	75	\HTMLIndexCmd (option) . . . . .	106, 223		
\frontmatter . . . . .	6414	\HTMLLanguage . . . . .	112, 6677		
ftcap (package) . . . . .	759	\HTMLLatexCmd (option) . . . . .	104, 172, 223		
ftnright (package) . . . . .	759	\HTMLLeftmargini (length) .	168, 401, 402, 1043		
fullminipage (package) . . . . .	759	\HTMLPageBottom . . . . .	113, 392, 5830		
fullpage (package) . . . . .	759	\HTMLPageTop . . . . .	113, 5827		
fullwidth (package) . . . . .	760	\HTMLTitle . . . . .	112, 120, 5868		
\fup . . . . .	11780	\HTMLTitleAfterSection . . . . .	113, 6700		
\fussy . . . . .	5347	\HTMLTitleBeforeSection . . . . .	113, 6695		
fwlw (package) . . . . .	760	\HTMLUnicode . . . . .	5196		
<b>G</b>					
gather (environment) . . . . .	77	\HTMLvleftskip (length) .	168, 401, 402, 1043		
gather* (environment) . . . . .	80	hypbmsec (package) . . . . .	782		
GELLMU (program) . . . . .	74	hypcap (package) . . . . .	782		
gensymb (package) . . . . .	760	hypdestopt (package) . . . . .	783		
gentombow (package) . . . . .	761	\hyperindexref . . . . .	9802		
geometry (package) . . . . .	228, 761	hypernat (package) . . . . .	783		
getttitlestring (package) . . . . .	230	hyperref (package) . . . . .	130, 483, 783		
ghsystem (package) . . . . .	762	\hypertoc . . . . .	9668		
[Gin]:		\hypertocfloat . . . . .	9691		
class (key) . . . . .	770	hyperxmp (package) . . . . .	788		
GladTeX (program) . . . . .	74	hyphenat (package) . . . . .	788		
gloss (package) . . . . .	134, 762	<b>I</b>			
glossaries (package) . . . . .	134, 763	idxlayout (package) . . . . .	789		
GlossaryCmd (option) . . . . .	107, 134, 223, 763	\if@titlepage . . . . .	6910		
glyptounicode.tex (file) . . . . .	102	ifoddpage (package) . . . . .	790		
gmeometric (package) . . . . .	765	ifplatform (package) . . . . .	199		
graphics (package) . . . . .	155, 765	\IgnoreMinipageWidths . . . . .	125, 558, 11089		
graphicx (package) . . . . .	155, 778	\ImageAltText . . . . .	113, 9910		
grffile (package) . . . . .	157, 778	ImagesDirectory (option) . . . . .	104, 221		
grid (package) . . . . .	778	ImagesName (option) . . . . .	104, 221		
grid-system (package) . . . . .	779	imakeidx (package) . . . . .	790		
gridset (package) . . . . .	779	\includegraphics . . . . .	316		
<b>H</b>					
hang (package) . . . . .	779	indentfirst (package) . . . . .	349		
hanging (package) . . . . .	781	InDesign (program) . . . . .	75		
Hevea (program) . . . . .	74	index (package) . . . . .	794		
\hfill . . . . .	11853	\InlineClass . . . . .	5615		
hhline (package) . . . . .	782	\inlinemathnormal . . . . .	152, 5181		
\HomeHTMLFilename . . . . .	5206	\inlinemathother . . . . .	152, 5177		
HomeHTMLFilename (option) . . . . .	104, 109, 222	inputenc (package) . . . . .	102		
\href . . . . .	9292	inputenx (package) . . . . .	102		
\hrulefill . . . . .	11855	inputrc (package) . . . . .	796		
\hskip . . . . .	122	internet (class) . . . . .	74		
\hspace . . . . .	122, 583, 11891, 11922, 11928	intopdf (package) . . . . .	796		
htlatex (program) . . . . .	74	itemize (environment) . . . . .	7382		
\HTMLAuthor . . . . .	113, 120, 5873	\itshape . . . . .	11748		
HTMLDebugComments (boolean) . . . . .	112, 242	<b>K</b>			
\HTMLDescription . . . . .	113, 119, 5878	karnaugh-map (package) . . . . .	797		
\HTMLEntity . . . . .	5188	\kern . . . . .	122		

key:	lineno (package) . . . . .	810	
[Gin]:	\LinkHome . . . . .	5264, 5269	
class . . . . .	770		
keyfloat (package) . . . . .	167, 800	109, 5261	
komascript (class) . . . . .	167	Linux (program) . . . . .	117, 217
kotex (package) . . . . .	171	lips (package) . . . . .	813
kvoptions (package) . . . . .	220	list (environment) . . . . .	7352
		listings (package) . . . . .	813
		listlikeatab (package) . . . . .	817
		\listof . . . . .	9615
L		\listoffigures . . . . .	9589
\l@book . . . . .	9712	\listoftables . . . . .	9602
\l@chapter . . . . .	9714	lltjext (package) . . . . .	818
\l@figure . . . . .	9725	lmodern (package) . . . . .	102
\l@paragraph . . . . .	9723	lofdepth (counter) . . . . .	502
\l@part . . . . .	9713	longtable (environment) . . . . .	4
\l@section . . . . .	9720	longtable (package) . . . . .	163, 818
\l@subparagraph . . . . .	9724	lotdepth (counter) . . . . .	502
\l@subsection . . . . .	9721	lscape (package) . . . . .	821
\l@subsubsection . . . . .	9722	ltablex (package) . . . . .	822
\l@table . . . . .	9726	ltcaption (package) . . . . .	822
\LaTeX . . . . .	12049	ltgrid (package) . . . . .	823
\LaTeX2HTML (program) . . . . .	74	ltxtable (package) . . . . .	823
\LaTeXe . . . . .	12049	lua-check-hyphen (package) . . . . .	823
lateimage (environment) . . . . .	534, 10617, 10754	lua-visual-debug (package) . . . . .	824
\LateximageFontSizeScale . . . . .	10547	luacolor (package) . . . . .	824
\LateximageFontSizeName . . . . .	10546	\LuaTeX . . . . .	12078
latemk (option) . . . . .	104, 109, 223	LuaTeX (program) [requirement] . . . . .	78
latemk (program) . . . . .	173	\LuaTeX . . . . .	12078
LatexmkIndexCmd (option) . . . . .	107, 223	luatodonotes (package) . . . . .	169, 824
LaTeXL (program) . . . . .	74	lwarp (package) . . . . .	104
layaureo (package) . . . . .	805	lwarp-common-multimedia (package) . . . . .	1103
layout (package) . . . . .	805	lwarp-patch-komascript (package) . . . . .	1076
layouts (package) . . . . .	806	lwarp-patch-memoir (package) . . . . .	1078
leading (package) . . . . .	808	lwarp.css (file) . . . . .	116, 260
leftidx (package) . . . . .	809	lwarp.ist (file) . . . . .	145, 299
\leftline . . . . .	10801	lwarp.xdy (file) . . . . .	146, 299
length:		lwarp_baseline_marker.eps (file) . . . . .	512
\HTMLleftmargini . . . . .	168, 401, 402, 1043	lwarp_baseline_marker.png (file) . . . . .	512
\HTMLvleftskip . . . . .	168, 401, 402, 1043	lwarp_formal.css (file) . . . . .	294
\LWR@cmidrulewidth . . . . .	443	lwarp_mathjax.txt (file) . . . . .	301
\LWR@heavyrulewidth . . . . .	443	lwarp_one_limage.cmd (file) . . . . .	300
\LWR@lightrulewidth . . . . .	443	lwarp_sagebrush.css (file) . . . . .	290
\LWR@minipageheight . . . . .	559	lwarp_tutorial.txt (file) . . . . .	84
\LWR@minipagewidth . . . . .	559	[lwarpmk]:	
\LWR@tempheight . . . . .	584	htmlglossary (option) . . . . .	134, 763
\LWR@tempraise . . . . .	584	printglossary (option) . . . . .	134, 763
\LWR@tempwidth . . . . .	584	lwarpmk (option) . . . . .	107, 222, 303
\LWR@thiscmidrulewidth . . . . .	443	lwarpmk (program) . . . . .	186, 303
\VerbatimHTMLWidth . . . . .	402	lwarpmk epstopdf (program) . . . . .	155, 549
\vleftmargini . . . . .	168, 401, 1043	lwarpmk pdftosvg (program) . . . . .	155, 549
\vleftskip . . . . .	168, 401, 1043	lwarpmk.conf (file) . . . . .	260
letltxmacro (package) . . . . .	199	lwarpmk.lua (file) . . . . .	186
letterspace (package) . . . . .	809	\lwarpsetup . . . . .	803
lettrine (package) . . . . .	809	\LWR@footnotetext . . . . .	5897
\lgweight . . . . .	11738	\LWR@makebox@align . . . . .	11218
LibreOffice (program) . . . . .	75		
\linebreak . . . . .	11932		

\LWR@makebox@paren .....	<u>11203</u>	\LWR@creatinglwarpmk (environment) .	<u>955</u>
\LWR@printpendingfootnotes .....	<u>5963</u>	\LWR@currentautosec (counter) .....	<u>375</u>
\LWR@addbaselinemarker .....	<u>9943</u>	\LWR@currentcss .....	<u>5835</u>
\LWR@addcdashline .....	<u>8243</u>	\LWR@currenttextcolor .....	<u>11791</u>
\LWR@addcmidruletrim .....	<u>8209</u>	\LWR@customizedMathJax .....	<u>6204</u>
\LWR@addcmidrulewidth .....	<u>8240</u>	\LWR@customizeMathJax .....	<u>6261</u>
\LWR@addcompilecmd .....	<u>1671</u>	\LWR@descitem .....	<u>7394</u>
\LWR@addformatwpalignment .....	<u>8259</u>	\LWR@displaymathnormal (environment)	
\LWR@addleftmostbartag .....	<u>8043</u>	.....	<u>10256</u>
\LWR@addlinktitle .....	<u>9172</u>	\LWR@displaymathother (environment)	<u>10261</u>
\LWR@addmathjax .....	<u>10323</u>	\LWR@docdashline .....	<u>8173</u>
\LWR@addmulticolverrulecolor ...	<u>8511</u>	\LWR@docmidrule .....	<u>8157</u>
\LWR@addrulewidth .....	<u>8214</u>	\LWR@doequation .....	<u>10336</u>
\LWR@addtabularcellcolor .....	<u>8386</u>	\LWR@doindexentry .....	<u>9782</u>
\LWR@addtabularhrulecolor .....	<u>8287</u>	\LWR@doingapar (boolean) .....	<u>344</u>
\LWR@addtabulararrowcolor .....	<u>8272</u>	\LWR@doingcmidrule (boolean) .....	<u>416</u>
\LWR@addtabularrulecolors .....	<u>8333</u>	\LWR@doingstartpars (boolean) .....	<u>343</u>
\LWR@afterendverbatim .....	<u>7184</u>	\LWR@doingtbrule (boolean) .....	<u>416</u>
\LWR@allowanothergeometry (boolean) .	<u>229</u>	\LWR@domulticolumn .....	<u>8549</u>
\LWR@amsmathbody .....	<u>10580</u>	\LWR@doubledollar .....	<u>10162</u>
\LWR@amsmathbodynumbered .....	<u>10586</u>	\LWR@dynamicmath (boolean) .....	<u>326</u>
\LWR@amsmultiline (boolean) .....	<u>530</u>	\LWR@earlyclassloadnever .....	<u>89</u>
\LWR@applyxfakebold .....	<u>9925</u>	\LWR@earlyloadnever .....	<u>84</u>
\LWR@atbeginverbatim .....	<u>7165</u>	\LWR@emptyatbang (boolean) .....	<u>417</u>
\LWR@backgroundcolor .....	<u>39</u>	\LWR@endfloatalignment .....	<u>9436</u>
\LWR@beginhideamsmath .....	<u>10459</u>	\LWR@endhideamsmath .....	<u>10467</u>
\LWR@BlockClassWP (environment) .	<u>5631</u>	\LWR@endofline .....	<u>11864</u>
\LWR@blocktextcurrentfont (environment) .....	<u>11723, 11804</u>	\LWR@ensuredoingapar .....	<u>5697</u>
\LWR@botnavigation .....	<u>5287</u>	\LWR@equationother (environment) .	<u>10275</u>
\LWR@cdashlines .....	<u>443</u>	\LWR@equationtag .....	<u>10566</u>
\LWR@cellcolordepth (counter) .....	<u>419</u>	\LWR@existingtabular (boolean) .....	<u>417</u>
\LWR@cellHTMLcolor .....	<u>7968</u>	\LWR@expandableformatted .....	<u>1392</u>
\LWR@checkloadbefore .....	<u>59</u>	\LWR@expandableformattedenv .....	<u>1421</u>
\LWR@checkloadfilename .....	<u>1112</u>	\LWR@expcolspect .....	<u>7845</u>
\LWR@checkloadnever .....	<u>78</u>	\LWR@externalfilecnt (counter) .....	<u>511</u>
\LWR@clearmidrules .....	<u>8124</u>	\LWR@fboxstyle .....	<u>11278</u>
\LWR@closeparagraph .....	<u>5731</u>	\LWR@figcaption (environment) .....	<u>9457</u>
\LWR@closeparagraph@br .....	<u>5721</u>	\LWR@filenamenoblocks .....	<u>6071</u>
\LWR@closeprevious .....	<u>5314</u>	\LWR@filestart .....	<u>6709</u>
\LWR@closetabledatacell .....	<u>7546</u>	\LWR@findcurrenttextcolor .....	<u>11794</u>
\LWR@cmidrulewidth (length) .....	<u>443</u>	\LWR@findword .....	<u>1109</u>
\LWR@colalterspec .....	<u>419</u>	\LWR@firstoffour .....	<u>725</u>
\LWR@colbeforespec .....	<u>419</u>	\LWR@floatalignment .....	<u>9422</u>
\LWR@colatspec .....	<u>419</u>	\LWR@floatalignmentname .....	<u>9421</u>
\LWR@colbangspec .....	<u>419</u>	\LWR@floatbegin .....	<u>9351</u>
\LWR@colbarspec .....	<u>419</u>	\LWR@floatend .....	<u>9389</u>
\LWR@colbeforespec .....	<u>419</u>	\LWR@floatstyle .....	<u>2</u>
\LWR@columnHTMLcolor .....	<u>7966</u>	\LWR@footnotebox .....	<u>5892</u>
\LWR@columnspeclookahead .....	<u>7677</u>	\LWR@footnotetext .....	<u>5926</u>
\LWR@compilecmd .....	<u>1668</u>	\LWR@forceemptyline .....	<u>721</u>
\LWR@compileuplatex .....	<u>1700</u>	\LWR@forceminipagefullwidth (boolean)	<u>560</u>
\LWR@convertto .....	<u>699</u>	\LWR@forceminwidth .....	<u>11267</u>
\LWR@copiedsidetoc (boolean) .....	<u>497</u>	\LWR@forcenewautoidanchor .....	<u>9410</u>
\LWR@copyfile .....	<u>1330</u>	\LWR@forcenewpage .....	<u>5334</u>
\LWR@createautosec .....	<u>6423</u>	\LWR@formatted .....	<u>1377</u>

\LWR@formattedeenv .....	<u>1407</u>	\LWR@intabularmetadata (boolean) ....	<u>417</u>
\LWR@formatting .....	<u>1376</u>	\LWR@isolate .....	<u>712</u>
\LWR@foundmrowcell (boolean) .....	<u>417</u>	\LWR@isstartingequation (boolean) ....	<u>537</u>
\LWR@fourthoffour .....	<u>725</u>	\LWR@itemizeitem .....	<u>7375</u>
\LWR@freezethisautoid (boolean) .....	<u>491</u>	\LWR@latestautopage (counter) ....	<u>493</u>
\LWR@futurenonspacelet .....	<u>7472</u>	\LWR@lateximage@oneimage .....	<u>10602</u>
\LWR@FVstyle .....	<u>56</u>	\LWR@lateximage@oneimageb .....	<u>10593</u>
\LWR@getexpparray .....	<u>5150</u>	\LWR@lateximagedepth (counter) ....	<u>535</u>
\LWR@getmynexttoken .....	<u>7482</u>	\LWR@lateximagedepthref .....	<u>9101</u>
\LWR@glrbox (environment) .....	<u>743</u>	\LWR@lateximagenumber (counter) ....	<u>535</u>
\LWR@gsavebox .....	<u>729</u>	\LWR@lateximagenumberref .....	<u>9104</u>
\LWR@hdashedlines (counter) .....	<u>416</u>	\LWR@lateximagesfile .....	<u>1292</u>
\LWR@heavyrulewidth (length) .....	<u>443</u>	\LWR@latexmkcmd .....	<u>1686</u>
\LWR@hidelatexequation .....	<u>10309</u>	\LWR@latexmkdvipdfm .....	<u>1691</u>
\LWR@hlines (counter) .....	<u>416</u>	\LWR@latexmkvar .....	<u>1680</u>
\LWR@HTML@caption@begin .....	<u>9467</u>	\LWR@lightrulewidth (length) ....	<u>443</u>
\LWR@HTML@caption@end .....	<u>9478</u>	\LWR@linkcatcodes .....	<u>9251</u>
\LWR@HTML@ref .....	<u>9215</u>	\LWR@linkmediacatcodes .....	<u>9259</u>
\LWR@htmlblockcomment .....	<u>5529</u>	\LWR@LIPage (counter) ....	<u>536</u>
\LWR@htmlblocktag .....	<u>5531</u>	\LWR@listitem .....	<u>7337</u>
\LWR@HTMLcline .....	<u>8895</u>	\LWR@loadafter .....	<u>18</u>
\LWR@htmclosecomment .....	<u>5501</u>	\LWR@loadbefore .....	<u>50</u>
\LWR@htmlcomment .....	<u>5522</u>	\LWR@loadnever .....	<u>65</u>
\LWR@htmldivclass .....	<u>5568</u>	\LWR@longtabledatacaptiontag ....	<u>8618</u>
\LWR@htmldivclassend .....	<u>5571</u>	\LWR@lookforpackagename .....	<u>1162</u>
\LWR@htmlelement .....	<u>5582</u>	\LWR@l warpconfversion .....	<u>1662</u>
\LWR@htmlelementclass .....	<u>5554</u>	\LWR@L warpEnd .....	<u>6855, 12126</u>
\LWR@htmlelementclassend .....	<u>5560</u>	\LWR@l warplabel .....	<u>9107</u>
\LWR@htmlelementclassline .....	<u>5574</u>	\LWR@L warpStart .....	<u>6789, 12126</u>
\LWR@htmlelementend .....	<u>5585</u>	\LWR@maketitlesetup .....	<u>33, 7004</u>
\LWR@htmlfilenumber (counter) .....	<u>328</u>	\LWR@mathjaxfilename .....	<u>5846</u>
\LWR@htmlfilerref .....	<u>9098</u>	\LWR@mathjaxwarn .....	<u>12264</u>
\LWR@HTMLhline .....	<u>8876</u>	\LWR@mathmacro (boolean) ....	<u>325</u>
\LWR@HTMLLatexCmd .....	<u>1710</u>	\LWR@maybenewtablerow .....	<u>7975</u>
\LWR@htmlmathlabel .....	<u>10444</u>	\LWR@maybeprintpendingfootnotes ..	<u>5982</u>
\LWR@htmlmulticolumn .....	<u>8609</u>	\LWR@maybetodata .....	<u>9667</u>
\LWR@htmlopencomment .....	<u>5501</u>	\LWR@midrulecounter (counter) ....	<u>420</u>
\LWR@htmlrefsectionfilename .....	<u>5251</u>	\LWR@midrules .....	<u>443</u>
\LWR@HTMLsanitize .....	<u>6184</u>	\LWR@minipagefullwidth (boolean) ....	<u>560</u>
\LWR@HTMLsanitizeexpand .....	<u>6194</u>	\LWR@minipageheight (length) ....	<u>559</u>
\LWR@htmlsectionfilename .....	<u>5216</u>	\LWR@minipagestartpars .....	<u>11871</u>
\LWR@htmlspan .....	<u>5478</u>	\LWR@minipagestoppars .....	<u>11874</u>
\LWR@htmlspanclass .....	<u>5486</u>	\LWR@minipagethispar (boolean) ....	<u>560</u>
\LWR@htmltag .....	<u>5496</u>	\LWR@minipagewidth (length) ....	<u>559</u>
\LWR@htmltagc .....	<u>5429</u>	\LWR@multicolother .....	<u>8451</u>
\LWR@hyperindexrefnullified .....	<u>9787</u>	\LWR@multicolpartext .....	<u>8445</u>
\LWR@indentHTML .....	<u>5423</u>	\LWR@multicolskip .....	<u>8457</u>
\LWR@indentHTMLtwo .....	<u>5426</u>	\LWR@multirowborder .....	<u>3</u>
\LWR@indexitem .....	<u>9749</u>	\LWR@mynexttoken .....	<u>7471</u>
\LWR@indexnameref .....	<u>9781</u>	\LWR@myshorttoc .....	<u>9536</u>
\LWR@indexsubitem .....	<u>9753</u>	\LWR@nameref .....	<u>9095</u>
\LWR@indexsubsubitem .....	<u>9757</u>	\LWR@nestspan (environment) ....	<u>5439</u>
\LWR@indisplaymathimage (boolean) ..	<u>511</u>	\LWR@new@label .....	<u>9152</u>
\LWR@infoprocessingmathjax .....	<u>6241</u>	\LWR@newautoidanchor .....	<u>9415</u>
\LWR@instertatbangcols .....	<u>7538</u>	\LWR@newautopagelabel .....	<u>6164</u>

\LWR@newhtmlfile .....	<u>6286</u>	\LWR@pushclose .....	<u>5087</u>
\LWR@nextautoid (counter) .....	<u>492</u>	\LWR@pushoneclose .....	<u>6429</u>
\LWR@nextautopage (counter) .....	<u>492</u>	\LWR@quickfile .....	<u>1289</u>
\LWR@nextequation (counter) .....	<u>524</u>	\LWR@ref@ignorestar .....	<u>9223</u>
\LWR@notltjloadafter .....	<u>37</u>	\LWR@remembertag .....	<u>10570</u>
\LWR@notmemoirloadafter .....	<u>34</u>	\LWR@requeststoc .....	<u>6848</u>
\LWR@nullfonts .....	<u>11550</u>	\LWR@requirepackagenames .....	<u>1101</u>
\LWR@nullifycomment .....	<u>1103</u>	\LWR@restoreorigaccents .....	<u>1617</u>
\LWR@nullifyNoAutoSpacing .....	<u>8901</u>	\LWR@restoreorigformatting .....	<u>9857</u>
\LWR@nulllistfills .....	<u>7344</u>	\LWR@restoreoriglists .....	<u>7447</u>
\LWR@openparagraph .....	<u>5703</u>	\LWR@rowHTMLcolor .....	<u>7967</u>
\LWR@opttablecol (boolean) .....	<u>417</u>	\LWR@ruleHTMLcolor .....	<u>7969</u>
\LWR@orig@setBold .....	<u>9923</u>	\LWR@sanitize .....	<u>874</u>
\LWR@orig@unsetBold .....	<u>9924</u>	\LWR@sanitized .....	<u>873</u>
\LWR@origcolspec .....	<u>7521</u>	\LWR@secondoffour .....	<u>725</u>
\LWR@origmathjax (boolean) .....	<u>220</u>	\LWR@section .....	<u>6446</u>
\LWR@overline .....	<u>11786</u>	\LWR@sectionnumber .....	<u>6420</u>
\LWR@parseaftercolumn .....	<u>7754</u>	\LWR@select@html@hspase .....	<u>11891</u>
\LWR@parseatcolumn .....	<u>7687</u>	\LWR@select@html@nohspase .....	<u>11922</u>
\LWR@parsebangcolumn .....	<u>7716</u>	\LWR@select@print@hspase .....	<u>11925</u>
\LWR@parsebarcolumn .....	<u>7766</u>	\LWR@setcurrentfont .....	<u>9926</u>
\LWR@parsebeforecolumn .....	<u>7742</u>	\LWR@setexpparray .....	<u>5141</u>
\LWR@parsecoloncolumn .....	<u>7791</u>	\LWR@setlatestname .....	<u>9081</u>
\LWR@parseDcolumn .....	<u>7840</u>	\LWR@setOSWindows .....	<u>791</u>
\LWR@parsedrequirepackagenames ..	<u>1102</u>	\LWR@setref .....	<u>9089</u>
\LWR@parsenormalcolumn .....	<u>7816</u>	\LWR@setvirtualpage (environment)	<u>11073</u>
\LWR@parsepcolumn .....	<u>7828</u>	\LWR@shellescapecmd .....	<u>1663</u>
\LWR@parsesemicoloncolumn .....	<u>7812</u>	\LWR@sidetoc .....	<u>9641</u>
\LWR@parsestarcolumn .....	<u>7837</u>	\LWR@simplifycustom .....	<u>6059</u>
\LWR@parsetablecols .....	<u>7877</u>	\LWR@simplifyname .....	<u>6048</u>
\LWR@parsewcolumn .....	<u>7832</u>	\LWR@singledollar .....	<u>10189</u>
\LWR@patcherror .....	<u>707</u>	\LWR@singledollarmmeasure .....	<u>9984</u>
\LWR@patchlists .....	<u>7419</u>	\LWR@skipatbang (boolean) .....	<u>417</u>
\LWR@pdfencoding .....	<u>630</u>	\LWR@skippingmcolrowcell (boolean) ..	<u>416</u>
\LWR@popclose .....	<u>5114</u>	\LWR@skippingmrowcell (boolean) ..	<u>416</u>
\LWR@PreloadedPackage .....	<u>10806</u>	\LWR@spandepth (counter) .....	<u>343</u>
\LWR@prevFileDepth (counter) .....	<u>374</u>	\LWR@splitstarcontents .....	<u>7848</u>
\LWR@previousautopagelabel (counter) .....	<u>364</u>	\LWR@splitstarcopies (counter) .....	<u>431</u>
\LWR@printatbang .....	<u>8018</u>	\LWR@splitstarindex (counter) .....	<u>431</u>
\LWR@printbartag .....	<u>8008</u>	\LWR@starcount (counter) .....	<u>431</u>
\LWR@printcloselist .....	<u>7244</u>	\LWR@starredlongtable (boolean) ..	<u>419</u>
\LWR@PrintLatexCmd .....	<u>1710</u>	\LWR@startedrow (boolean) .....	<u>416</u>
\LWR@printlength .....	<u>1083</u>	\LWR@startingequation (counter) ..	<u>536</u>
\LWR@printmccoldata .....	<u>8460</u>	\LWR@startingequationtag .....	<u>10565</u>
\LWR@printmccoltype .....	<u>8403</u>	\LWR@startnewdepth .....	<u>6433</u>
\LWR@printopenlist .....	<u>7245</u>	\LWR@startpars .....	<u>5773</u>
\LWR@printpendingfootnotes .....	<u>5979</u>	\LWR@startref .....	<u>9178</u>
\LWR@printpendingmpfootnotes .....	<u>5991</u>	\LWR@stoppars .....	<u>5791</u>
\LWR@printpercentlength .....	<u>700</u>	\LWR@stripperiod .....	<u>9080</u>
\LWR@printthetitle .....	<u>6956</u>	\LWR@strrresult .....	<u>7519</u>
\LWR@providelength .....	<u>696</u>	\LWR@subaddcmidruletrim .....	<u>8196</u>
\LWR@ProvidesPackageDrop .....	<u>1278</u>	\LWR@subaddtabularcellcolor .....	<u>8380</u>
\LWR@ProvidesPackageDropA .....	<u>1263</u>	\LWR@subcdashline .....	<u>8160</u>
\LWR@ProvidesPackageDropB .....	<u>1272</u>	\LWR@subcmidrule .....	<u>8142</u>
\LWR@ProvidesPackagePass .....	<u>1233</u>	\LWR@subcustomizedmathjax .....	<u>6207</u>

\LWR@subhtmllementclass .....	<u>5536</u>	\LWR@unknownengine .....	<u>1675</u>
\LWR@subHTMLsanitize .....	<u>6172</u>	\LWR@unknowmathsize (boolean) .....	<u>513</u>
\LWR@subhyperref .....	<u>9267</u>	\LWR@usedmultirow (boolean) .....	<u>417</u>
\LWR@subhyperrefclass .....	<u>9281</u>	\LWR@validtablecol (boolean) .....	<u>417</u>
\LWR@subhyperreftext .....	<u>9276</u>	\LWR@verbtags (boolean) .....	<u>403</u>
\LWR@subinlinimage .....	<u>9330</u>	\LWR@virtualpagedepth (counter) .....	<u>559</u>
\LWR@sublabel .....	<u>9126</u>	\LWR@vspace .....	<u>11929</u>
\LWR@subnewref .....	<u>9209</u>	\LWR@warnedcustomizemathjax (boolean) .....	<u>366</u>
\LWR@subsingledollar .....	<u>10109</u>	\LWR@WPcell .....	<u>8255</u>
\LWR@subsingledollarsvg .....	<u>10030</u>	\LWR@writeconf .....	<u>1812</u>
\LWR@subtableofcontents .....	<u>9549</u>	\LWR@xcolorrowHTMLcolor .....	<u>7965</u>
\LWR@subtabularhtmlcolumns .....	<u>8689</u>	\LWR@xfakebold (boolean) .....	<u>511</u>
\LWR@syncmathjax .....	<u>10289</u>	\LWRopquote .....	<u>786</u>
LWR@tablecolsing .....	<u>418</u>	\LWRopseq .....	<u>787</u>
LWR@tablecolsingindex (counter) .....	<u>418</u>	\LWRPrintStack .....	<u>5292</u>
LWR@tablecolsingwidth (counter) .....	<u>418</u>	\LWRsetnextfloat .....	<u>9451</u>
\LWR@tabledatacolumnntag .....	<u>8778</u>	lyluatex (package) .....	<u>826</u>
\LWR@tabledatasinglecolumnntag .....	<u>8057</u>	\LyX .....	<u>12122</u>
LWR@tableLaTeXcolindex (counter) .....	<u>418</u>		
LWR@tableparcell (boolean) .....	<u>416</u>		
LWR@tabletotalLaTeXcols (counter) .....	<u>419</u>	<b>M</b>	
LWR@tabletotalLaTeXcolsnext (counter) .....	<u>419</u>	Mac OS (program) .....	<u>117, 217</u>
\LWR@tabular@warpprintonly .....	<u>8897</u>	\macrotocname .....	<u>755</u>
LWR@tabularcelladded (boolean) .....	<u>416</u>	Madcap (program) .....	<u>75</u>
LWR@tabularDepth (counter) .....	<u>417</u>	magaz (package) .....	<u>828</u>
\LWR@tabularendofline .....	<u>7656</u>	\mainmatter .....	<u>6410</u>
\LWR@tabularfinishrow .....	<u>7607</u>	make (program) .....	<u>175</u>
\LWR@tabularhtmlcolumns .....	<u>8699</u>	\makebox .....	<u>11227</u>
\LWR@tabularleftedge .....	<u>8048</u>	makeidx (package) .....	<u>147, 829, 1018, 1019</u>
LWR@tabularmutemods (boolean) .....	<u>417</u>	\MakeIndex .....	<u>12100</u>
LWR@tabularpardepth (counter) .....	<u>418</u>	makeindex (option) .....	<u>104, 109, 223</u>
\LWR@tdaddstyle .....	<u>8183</u>	makeindex (program) .....	<u>145</u>
\LWR@tdendstyles .....	<u>8189</u>	makeindexStyle (option) .....	<u>106, 145, 221</u>
\LWR@tdstartstyles .....	<u>8182</u>	\makelabel .....	<u>406</u>
\LWR@tempcolor .....	<u>11792</u>	\maketitle .....	<u>47, 119, 7016</u>
\LWR@tempcolortwo .....	<u>11792</u>	manyfoot (package) .....	<u>829</u>
\LWR@tempheight (length) .....	<u>584</u>	marginal (package) .....	<u>831</u>
\LWR@tempraise (length) .....	<u>584</u>	marginfit (package) .....	<u>831</u>
\LWR@tempwidth (length) .....	<u>584</u>	marginfix (package) .....	<u>832</u>
\LWR@textcurrentcolor .....	<u>22, 11797</u>	marginnote (package) .....	<u>832</u>
\LWR@textcurrentfont .....	<u>11701, 11803</u>	\marginpar .....	<u>124, 358, 6003</u>
\LWR@thirdoffour .....	<u>725</u>	\marginparBlock .....	<u>124, 358, 6014, 6032</u>
\LWR@ThisAltText .....	<u>9912</u>	\markboth .....	<u>5342</u>
LWR@thisautoid (counter) .....	<u>490</u>	\markright .....	<u>5343</u>
LWR@thisautoidWP (counter) .....	<u>491</u>	marvosym (package) .....	<u>833</u>
\LWR@thiscmidrulewidth (length) .....	<u>443</u>	math (environment) .....	<u>10255</u>
\LWR@thiscolsing .....	<u>8056</u>	mathcomp (package) .....	<u>833</u>
\LWR@thisfilename .....	<u>6042</u>	mathdots (package) .....	<u>834</u>
\LWR@thisnewfilename .....	<u>6047</u>	mathfixs (package) .....	<u>834</u>
\LWR@titlingmaketitle .....	<u>83, 7057</u>	\MathImageAltText .....	<u>114, 9911</u>
\LWR@topnavigation .....	<u>5284</u>	MathJax (program) .....	<u>149, 151</u>
\LWR@traceinfo .....	<u>1358</u>	MathJax (program) [requirement] .....	<u>78</u>
LWR@tracinglarp (boolean) .....	<u>241</u>	mathjax (boolean) .....	<u>220</u>
LWR@trimlrules .....	<u>443</u>	mathjax (option) .....	<u>104, 109, 221</u>
LWR@trimrrrules .....	<u>443</u>	\MathJaxFilename .....	<u>112, 5847</u>
		mathsgv (option) .....	<u>104, 109, 221</u>
		mathtools (package) .....	<u>152, 834</u>

\mbox	11200	nfssext-cfr (package)	879
mcaption (package)	839	nicefrac (package)	154, 887
\mcolrowcell	8855	niceframe (package)	888
mdframed (package)	127, 839	\noalign	8865
\mdseries	11732	noitcrl (package)	889
media9 (package)	159, 848	\nolinebreak	11933
memhfixc (package)	851	\nolinkurl	9304
memoir (class)	167, 168, 1043	nomencl (package)	135, 889
metalogo (package)	851	nonfloat (package)	890
metalogox (package)	851	nonumonpart (package)	890
mhchem (package)	852	\nopagebreak	11937
microtype (package)	227, 855	\nopagecolor	76
midfloat (package)	856	nopageno (package)	890
midpage (package)	856	\normalcolor	9
\MiKTeX	12120	\normalfont	11767
minibox (package)	856	\normalmarginpar	6029
minipage (environment)	11099	notes (package)	890
\minipagefullwidth	11087	notespaces (package)	891
minitoc (package)	857	nowidow (package)	891
mismath (package)	857	ntheorem (package)	152, 892
morefloats (package)	861	\numberline	9662
moreverb (package)	861	numindex (option) [tocbibind]	148, 1019
movie15 (package)	159, 862	<b>O</b>	
mparhack (package)	864	octave (package)	903
\mrowcell	8852	OpenOffice (program)	75
MS-Windows (program)	117, 218	option:	
multicap (package)	864	--shell-escape	101
multicol (package)	864	[lwarpmk]:	
multicolrule (package)	865	htmlglossary	134, 763
\multicolumnrow	39, 8722	printglossary	134, 763
multimedia (package)	159, 866	[tocbibind]:	
\multirow	868	numindex	148, 1019
multirow (package)	867	[tocloft]:	
multitoc (package)	870	titles	133
multiline (environment)	70	BaseJobname	108, 221
multiline* (environment)	73	dvipdfm	104, 224
musicography (package)	871	dvipdfmx	104, 224
<b>N</b>		dvips	104, 224
nameauth (package)	874	GlossaryCmd	107, 134, 223, 763
\Nameref	9241	HomeHTMLFilename	104, 109, 222
\nameref	9232	HTMLFilename	104, 109, 223
nameref (package)	875	HTMLIndexCmd	106, 223
natbib (package)	876	HTMLLatexCmd	104, 172, 223
nccfancyhdr (package)	876	ImagesDirectory	104, 221
nccmath (package)	877	ImagesName	104, 221
needspace (package)	878	latexmk	104, 109, 223
newclude (package)	169	LatexmkIndexCmd	107, 223
\newfloat	4	lwarpmk	107, 222, 303
newfloat (package)	232	makeindex	104, 109, 223
\newline	11862	makeindexStyle	106, 145, 221
\newpage	11859	mathjax	104, 109, 221
\newtheorem	405	mathsvg	104, 109, 221
newtxmath (package)	155	OSWindows	107, 117, 218, 222
newunicodechar (package)	102	pdftotextEnc	107, 222
nextpage (package)	878	PrintIndexCmd	106, 223

PrintLatexCmd	.....	104, 172, 223	bigdelim	.....	165, 645
warpHTML	.....	107, 221	bigfoot	.....	646
warpprint	.....	107, 220	bigstrut	.....	647
xindy	.....	106, 109, 223	bitpattern	.....	647
xindyCodepage	.....	106, 222	blowup	.....	648
xindyLanguage	.....	106, 222	bm	.....	648
xindyStyle	.....	106, 146, 222	booklet	.....	648
\OSPathSymbol	.....	790	bookmark	.....	649
OSWindows (option)	.....	107, 117, 218, 222	booktabs	.....	649
overpic (package)	.....	159, 904	bophook	.....	651
<b>P</b>					
package:			bounddvi	.....	652
2in1	.....	600	boxedminipage2e	.....	652
2up	.....	600	braket	.....	652
a4	.....	600	breakurl	.....	653
a4wide	.....	601	breqn	.....	653
a5comb	.....	601	bsheaders	.....	655
abstract	.....	133, 601	bxpapersize	.....	655
academicons	.....	603	bytefield	.....	655
accessibility	.....	604	calc	.....	230
accsupp	.....	605	cancel	.....	656
acro	.....	605	canoniclayout	.....	657
acronym	.....	607	capt-of	.....	495
addlines	.....	609	caption	.....	165, 239, 495, 657
adjmulticol	.....	608	cases	.....	660
afterpage	.....	604, 610	centernot	.....	661
algorithm2e	.....	610	changebar	.....	661
algorithmicx	.....	165, 614	changelayout	.....	662
alltt	.....	615	changepage	.....	662
amsmath	.....	615	changes	.....	663
amsthm	.....	619	chappg	.....	665
anonchap	.....	623	chapterbib	.....	666
any size	.....	623	chemfig	.....	666
appendix	.....	133, 623	chemformula	.....	668
ar	.....	624	chemgreek	.....	673
arabicfront	.....	625	chemmacros	.....	674
array	.....	626	chemnum	.....	692
arydshln	.....	626	chkfloat	.....	693
asymptote	.....	159, 628	chngpage	.....	693
atbegshi	.....	629	cite	.....	693
attachfile	.....	630	CJK	.....	694
attachfile2	.....	631	CJKutf8	.....	694
authblk	.....	133, 633	cleveref	.....	129, 554
autobreak	.....	634	clrdtblp	.....	694
autonum	.....	634	cm-super	.....	102
awesomebox	.....	635	cmap	.....	103
axessibility	.....	636	cmdtrack	.....	694
axodraw2	.....	637	color	.....	157, 695
babel	.....	169	colortbl	.....	164, 695
backnaur	.....	637	comment	.....	226
backref	.....	637	continue	.....	697
balance	.....	638	copyrightbox	.....	697
bbding	.....	638	crop	.....	698
biblatex	.....	643	ctable	.....	698
bibunits	.....	644	cuted	.....	701
			cutwin	.....	701

dblfloatfix	702	floatflt	740
dblfnote	702	floatpag	741
dcolumn	702	floatrow	166, 742
dejavu	102	fltrace	747
diagbox	703	flushend	747
dingbat	704	fnbreak	747
ditaa	175	fncychap	748
dprogress	705	fnlineno	748
draftcopy	705	fnpara	749
draftfigure	706	fnpos	749
draftwatermark	706	fontawesome	749
easy-todo	707	fontawesome5	751
ebook	708	fontaxes	751
ed	708	fontenc	102, 752
ellipsis	709	fontspec	102
embrac	709	footmisc	752
emptypage	710	footnote	753
endfloat	710	footnotebackref	754
endheads	711	footnotehyper	754
endnotes	133, 711	footnoterange	755
enumerate	712	footnpag	755
enumitem	712	foreign	755
environ	232	forest	756
epigraph	713	fouridx	756
epsfig	714	framed	756
epstopdf	157, 715	ftcap	759
epstopdf-base	715	ftnright	759
eqlist	716	fullminipage	759
eqparbox	716	fullpage	759
errata	717	fullwidth	760
eso-pic	719	fwlw	760
etoolbox	199	gensymb	760
eurosym	719	gentombow	761
everyhook	231	geometry	228, 761
everypage	720	gettitlestring	230
everyshi	720	ghsystem	762
expl3	230	gloss	134, 762
extarrows	720	glossaries	134, 763
extramarks	721	gmeometric	765
fancybox	126, 721	graphics	155, 765
fancyhdr	726	graphicx	155, 778
fancyref	727	grffile	157, 778
fancytabs	728	grid	778
fancyvrb	729	grid-system	779
fewerfloatpages	735	gridset	779
figcaps	735	hang	779
figsize	735	hanging	781
filecontents	231	hhline	782
fitbox	736	hypbmsec	782
fix2col	736	hypcap	782
fixme	170, 737	hypdestopt	783
fixmetodonotes	738	hypernat	783
flafter	738	hyperref	130, 483, 783
flippdf	738	hyperxmp	788
float	165, 739	hyphenat	788

idxlayout	789	mcaption	839
ifoddpage	790	mdframed	127, 839
ifplatform	199	media9	159, 848
imakeidx	790	memhfixc	851
indentfirst	349	metalogo	851
index	794	metalogox	851
inputenc	102	mhchem	852
inputenx	102	microtype	227, 855
inputtrc	796	midfloat	856
intopdf	796	midpage	856
karnaugh-map	797	minibox	856
keyfloat	167, 800	minitoc	857
kotex	171	mismath	857
kvoptions	220	morefloats	861
layaureo	805	moreverb	861
layout	805	movie15	159, 862
layouts	806	mparhack	864
leading	808	multicap	864
leftidx	809	multicol	864
letltxmacro	199	multicolrule	865
letterspace	809	multimedia	159, 866
lettrine	809	multirow	867
lineno	810	multitoc	870
lips	813	musicography	871
listings	813	nameauth	874
listliketab	817	nameref	875
lltjext	818	natbib	876
lmodern	102	nccfancyhdr	876
longtable	163, 818	nccmath	877
lscape	821	needspace	878
ltablex	822	newclude	169
ltcaption	822	newfloat	232
ltxgrid	823	newtxmath	155
ltxtable	823	newunicodechar	102
lua-check-hyphen	823	nextpage	878
lua-visual-debug	824	nfssext-cfr	879
luacolor	824	nicefrac	154, 887
luatodonotes	169, 824	niceframe	888
lwarp	104	noitcrl	889
lwarp-common-multimedia	1103	nomencl	135, 889
lwarp-patch-komascript	1076	nonfloat	890
lwarp-patch-memoir	1078	nonumonpart	890
lyluatex	826	nopageno	890
magaz	828	notes	890
makeidx	147, 829, 1018, 1019	notespages	891
manyfoot	829	nowidow	891
marginal	831	ntheorem	152, 892
marginfit	831	octave	903
marginfix	832	overpic	159, 904
marginnote	832	pagegrid	905
marvosym	833	pagenote	133, 905
mathcomp	833	pagesel	905
mathdots	834	paralist	906
mathfixs	834	parallel	906
mathtools	152, 834	parcolumns	908

parnotes	910	rmpage	941
parskip	911	romanbar	942
pbox	911	romanbarpage number	942
pdfcol	911	rotating	942
pdfcolfoot	912	rotfloat	943
pdfcolmk	912	rterface	174
pdfcolparallel	912	rviewport	944
pdfcolparcolumns	913	sagetex	174
pdfcomment	913	savetrees	944
pdfcrypt	914	scalefnt	944
pdfescape	914	schemata	944
pdfmarginpar	915	scrextend	945
pdfpages	915	scrhack	948
pdfprivacy	917	scrlayer	948
pdfrender	918	scrlayer-notecolumn	949
pdfsync	918	scrlayer-scrpage	950
pdftricks	158, 918	scrpage2	951
pdfx	919	section	952
perltex	174	sectionbreak	953
perpage	919	sectsty	953
pfnote	920	semantic-markup	954
phfqt	921	setspace	955
physics	154, 921	shadow	956
pifont	927	shapepar	956
placeins	928	showidx	957
plrarydshln	928	showkeys	957
plexit	928	showtags	957
plexitarydshln	929	sidecap	957
plexitcolortbl	929	sidenotes	958
polyglossia	169	SIunits	960
prelim2e	930	siunitx	153, 547, 960
prettyref	930	slantsc	971
preview	930	slashed	971
printlen	232	soul	972
psfrag	158, 931	soulpos	974
psfragx	931	soulutf8	974
pst-eps	932	splitidx	974
pstool	158, 932	srcltx	976
pstricks	157, 933	srctex	976
pxatbegshi	933	stabular	977
pxeveryshi	933	stackengine	977
pxftnright	934	steinmetz	979
pxjahyper	934	stffloats	979
pythontex	174	struktex	980
quotchap	934	subcaption	165, 980
quoting	935	subfig	166, 981
ragged2e	936	subfigure	986
realscripts	936	subsubscripts	986
refcheck	937	supertabular	164, 987
refcount	232	svg	989
register	938	sympytex	174
relsize	123, 939	syntonly	990
repeatindex	940	tabfigures	990
resizegather	941	tablefootnote	990
rmathbr	941	tabs	990

tabularx	991	vpe	1046
tabulary	991	vwcol	1046
tascmac	992	wallpaper	1048
textarea	993	watermark	1049
textcomp	103, 123, 994	widetable	1049
textfit	997	widows-and-orphans	1049
textpos	998	witharrows	1050
theorem	998	wrapfig	1051
thinsp	1002	xbmks	1052
threadcol	1002	xcolor	157, 551, 1053
threeparttable	1003	xexchangebar	1063
threeparttablex	163, 1004	xellipsis	1063
thumb	1005	xetexko-vertical	1064
thumbs	1005	xfakebold	1064
tikz	156, 1005	xfrac	1065
titleps	1007	xifthen	232
titleref	1010	xltablear	1067
titlesec	1010	xltxtra	1068
titletoc	1012	xmpincl	1069
titling	133, 1013	xparse	170, 230
tocbasic	1018	xpatch	199
tocbibind	147, 148, 1018, 1019	xpiano	1069
tocdata	1020	xpinyin	1069
toccenter	1022	xr	1070
tocloft	133, 148, 623, 1022	xr-hyper	1070
tocstyle	1028	xstring	232
todo	1028	xtab	164, 1071
todonotes	169, 1029	xunicode	1072
topcapt	1031	xurl	1073
tram	1031	xy	1074
transparent	1032	zhlineskip	1075
trimclip	1032	zwpagelayout	1075
trivfloat	165, 1033	\PackageDiagramAltText	114, 9916
truncate	1034	\pagebreak	11934
turnthepage	1034	\pagecolor	75
twoup	1034	\pagegrid (package)	905
typearea	1035	\pagenote (package)	133, 905
typicons	1035	\pagenumbering	5348
ulem	1036	\pageref	9227
umoline	1037	\pagerefPageFor	9226
underscore	1038	\pagesel (package)	905
unicode-math	1038	\pagestyle	5340
units	154, 1040	Pandoc (program)	75
unitsdef	1041	\paragraph	6669
upref	1041	\paralist (package)	906
url	130, 1042	\parallel (package)	906
uspace	1042	\parbox	11191
variorref	129	\parcolumns (package)	908
varwidth	233	\parnotes (package)	910
verbatim	232	\parsemulticolumnalignment	8496
verse	168, 1042, 1043	\parskip (package)	911
versionotes	1044	\part	6636
verbbars	1044	\pbox (package)	911
vmargin	1045	\pdfcol (package)	911
vowel	1045	\pdfcolfoot (package)	912

pdfcolmk (package) . . . . .	912	\printthanks . . . . .	391, 393
pdfcolparallel (package) . . . . .	912	\printtitle . . . . .	392, 6948, 6982
pdfcolparcolumns (package) . . . . .	913	program:	
pdfcomment (package) . . . . .	913	[requirement]:	
pdfcrop (program) [requirement] . . . . .	78	LuaLaTeX . . . . .	78
pdfcrypt (package) . . . . .	914	MathJax . . . . .	78
pdfLaTeX (program) [requirement] . . . . .	78	pdfcrop . . . . .	78
pdflscape (package) . . . . .	914	pdfLaTeX . . . . .	78
pdfmarginpar (package) . . . . .	915	pdfseparate . . . . .	78, 83
pdfpages (package) . . . . .	915	pdftocairo . . . . .	78, 83
pdfprivacy (package) . . . . .	917	pdftotext . . . . .	78, 83
pdfrender (package) . . . . .	918	perl . . . . .	83
pdfseparate (program) [requirement]	78, 83	XeLaTeX . . . . .	78
pdfsync (package) . . . . .	918	Adobe . . . . .	75
pdftocairo (program) . . . . .	155, 549	AsciiDoc . . . . .	75
pdftocairo (program) [requirement]	78, 83	AsciiDoctor . . . . .	75
pdftotext (program) [requirement]	78, 83	Asciidoctor-LaTeX . . . . .	75
pdftotextEnc (option) . . . . .	107, 222	epstopdf . . . . .	155, 549
pdftricks (package) . . . . .	158, 918	Flare . . . . .	75
pdfx (package) . . . . .	919	FrameMaker . . . . .	75
perl (program) [requirement] . . . . .	83	GELLMU . . . . .	74
perltex (package) . . . . .	174	GladTeX . . . . .	74
perpage (package) . . . . .	919	Hevea . . . . .	74
pfnote (package) . . . . .	920	htlatex . . . . .	74
\phantomsection . . . . .	11998	InDesign . . . . .	75
phfqt (package) . . . . .	921	LaTeX2HTML . . . . .	74
physics (package) . . . . .	154, 921	latexmk . . . . .	173
picture (environment) . . . . .	557, 11064	LaTeXML . . . . .	74
pifont (package) . . . . .	927	LibreOffice . . . . .	75
placeins (package) . . . . .	928	Linux . . . . .	117, 217
plarydshln (package) . . . . .	928	lwarpmk . . . . .	186, 303
Plastex (program) . . . . .	74	lwarpmk epstopdf . . . . .	155, 549
plexit (package) . . . . .	928	lwarpmk pdftosvg . . . . .	155, 549
plexitarydshln (package) . . . . .	929	Mac OS . . . . .	117, 217
plextblcolortbl (package) . . . . .	929	Madcap . . . . .	75
\PN@parnotes@auto . . . . .	5702	make . . . . .	175
Polyglossia (package) . . . . .	169	makeindex . . . . .	145
\postbookname . . . . .	6616	MathJax . . . . .	149, 151
\postchaptername . . . . .	6620	MS-Windows . . . . .	117, 218
\postpartname . . . . .	6618	OpenOffice . . . . .	75
\postsectionname . . . . .	6622	Pandoc . . . . .	75
\prebookname . . . . .	6616	pdftocairo . . . . .	155, 549
\prechaptername . . . . .	6620	Plastex . . . . .	74
\prelim2e (package) . . . . .	930	TeX2page . . . . .	74
\prepartname . . . . .	6618	TeX4ht . . . . .	74
\preselectionname . . . . .	6622	TeXMaths . . . . .	180
\prettyref (package) . . . . .	930	TtH . . . . .	74
\preview (package) . . . . .	930	Unix . . . . .	117, 217
\printauthor . . . . .	392, 6964, 6983	Windows . . . . .	117, 218
\printdate . . . . .	392, 6975, 6985	Word . . . . .	75
\printglossary (option) [lwarpmk]	134, 763	xindy . . . . .	146
\printindex . . . . .	2	project.css (file) . . . . .	116
\PrintIndexCmd (option) . . . . .	106, 223	project.lwarpmkconf (file) . . . . .	260
\PrintLatexCmd (option) . . . . .	104, 172, 223	psfrag (package) . . . . .	158, 931
\printlen (package) . . . . .	232	psfrags (package) . . . . .	931

pst-eps (package) . . . . .	932	\rownum . . . . .	7962
pstool (package) . . . . .	158, 932	rterface (package) . . . . .	174
pstricks (package) . . . . .	157, 933	\rule . . . . .	11941
pxatbegshi (package) . . . . .	933	rviewport (package) . . . . .	944
pxeveryshi (package) . . . . .	933		
pxftnright (package) . . . . .	934	<b>S</b>	
pxjahyper (package) . . . . .	934	sagetex (package) . . . . .	174
pythontex (package) . . . . .	174	sample_project.css (file) . . . . .	116, 298
		savetrees (package) . . . . .	944
		\sb . . . . .	11770
<b>Q</b>		\scalebox . . . . .	371
\qqquad . . . . .	583, 11882	scalefont (package) . . . . .	944
\quad . . . . .	583, 11877	schemata (package) . . . . .	944
quotation (environment) . . . . .	7134	scrextend (package) . . . . .	945
quotchap (package) . . . . .	934	scrhack (package) . . . . .	948
quote (environment) . . . . .	7128	scrlayer (package) . . . . .	948
quoting (package) . . . . .	935	scrlayer-notecolumn (package) . . . . .	949
		scrlayer-scrpage (package) . . . . .	950
<b>R</b>		scrpage2 (package) . . . . .	951
ragged2e (package) . . . . .	936	\scshape . . . . .	11750
\raggedbottom . . . . .	5344	\section . . . . .	6660
\raggedleft . . . . .	10789	section (package) . . . . .	952
\raggedright . . . . .	10795	sectionbreak (package) . . . . .	953
\raisebox . . . . .	11376	sectsty (package) . . . . .	953
realscripts (package) . . . . .	936	semantic-markup (package) . . . . .	954
\ref . . . . .	9215	\SetHTMLFileNumber . . . . .	5207
refcheck (package) . . . . .	937	setspace (package) . . . . .	955
refcount (package) . . . . .	232	\sffamily . . . . .	11742
\reflectbox . . . . .	390	\sfrac . . . . .	1065
register (package) . . . . .	938	shadow (package) . . . . .	956
relsize (package) . . . . .	123, 939	shapepar (package) . . . . .	956
repeatindex (package) . . . . .	940	showidx (package) . . . . .	957
[requirement]:		showkeys (package) . . . . .	957
LuaLaTeX (program) . . . . .	78	showtags (package) . . . . .	957
MathJax (program) . . . . .	78	sidecap (package) . . . . .	957
pdfcrop (program) . . . . .	78	sidenotes (package) . . . . .	958
pdfLaTeX (program) . . . . .	78	SideTOCDepth (counter) . . . . .	111, 499
pdfseparate (program) . . . . .	78, 83	\sidetocname . . . . .	111, 9638
pdftocairo (program) . . . . .	78, 83	\simplechapterdelim . . . . .	6440
pdftotext (program) . . . . .	78, 83	\sishape . . . . .	11757
perl (program) . . . . .	83	SIunits (package) . . . . .	960
XeLaTeX (program) . . . . .	78	siunitx (package) . . . . .	153, 547, 960
\RequirePackage . . . . .	1195	slantsc (package) . . . . .	971
\resizebox . . . . .	399	slashed (package) . . . . .	971
resizegather (package) . . . . .	941	\sloppy . . . . .	5346
\ResumeTabular . . . . .	8767	\slshape . . . . .	11765
\reversemarginpar . . . . .	6028	soul (package) . . . . .	972
\rightline . . . . .	10803	soulpos (package) . . . . .	974
rmathbr (package) . . . . .	941	soulutf8 (package) . . . . .	974
\rmfamily . . . . .	11740	\sp . . . . .	11769
rmpage (package) . . . . .	941	splitidx (package) . . . . .	974
romanbar (package) . . . . .	942	srcltx (package) . . . . .	976
romanbarpagenumber (package) . . . . .	942	srctex (package) . . . . .	976
\rotatebox . . . . .	348	stabular (package) . . . . .	977
rotating (package) . . . . .	942	stackengine (package) . . . . .	977
rotfloat (package) . . . . .	943	\StartDefiningMath . . . . .	5165
\rowcolor . . . . .	7970		

\StartDefiningTabulars . . . . .	5155	\tfl@chapter@fix . . . . .	1033
steinmetz (package) . . . . .	979	\thanks . . . . .	119
stffloats (package) . . . . .	979	\thanksmarkseries . . . . .	91
\StopDefiningMath . . . . .	5169	\theauthor . . . . .	392
\StopDefiningTabulars . . . . .	5159	thebibliography (environment) . . . . .	9834
struktex (package) . . . . .	980	\thedate . . . . .	392
subcaption (package) . . . . .	165, 980	\theHTMLSection . . . . .	6706
subfig (package) . . . . .	166, 981	\theHTMLTitleSection . . . . .	6705
subfigure (package) . . . . .	986	\theHTMLTitleSeparator . . . . .	6682
\subparagraph . . . . .	6672	theindex (environment) . . . . .	9734
\subsection . . . . .	6663	\thempfootnote . . . . .	5960
\subsubsection . . . . .	6666	theorem (package) . . . . .	998
subsubscripts (package) . . . . .	986	\thetitle . . . . .	392
supertabular (package) . . . . .	164, 987	thinsp (package) . . . . .	1002
svg (package) . . . . .	989	\ThisAltText . . . . .	114, 9913
sympytex (package) . . . . .	174	\thispagestyle . . . . .	5341
syntonly (package) . . . . .	990	threadcol (package) . . . . .	1002
<b>T</b>			
tabbing (environment) . . . . .	7211	threepartable (package) . . . . .	1003
tabfigures (package) . . . . .	990	threepartablex (package) . . . . .	163, 1004
tablefootnote (package) . . . . .	990	thumb (package) . . . . .	1005
\tableofcontents . . . . .	113, 9568	thumbs (package) . . . . .	1005
tabls (package) . . . . .	990	tikz (package) . . . . .	156, 1005
tabular (environment) . . . . .	8914	\title . . . . .	119, 5857
\TabularMacro . . . . .	8765	titlepage (environment) . . . . .	119, 6932
tabularx (package) . . . . .	991	titles (option) [tocloft] . . . . .	133
tabulary (package) . . . . .	991	titlesec (package) . . . . .	1010
tascmac (package) . . . . .	992	titletoc (package) . . . . .	1012
\TeX . . . . .	12036	titling (package) . . . . .	133, 1013
\TeX2page (program) . . . . .	74	titlingpage (environment) . . . . .	14, 119
\TeX4ht (program) . . . . .	74	tocbasic (package) . . . . .	1018
\TeXMaths (program) . . . . .	180	[tocbibind]:	
textarea (package) . . . . .	993	numindex (option) . . . . .	148, 1019
\textbf . . . . .	11403	tocbibind (package) . . . . .	147, 148, 1018, 1019
\textcolor . . . . .	63	tocdata (package) . . . . .	1020
textcomp (package) . . . . .	103, 123, 994	tocdepth (counter) . . . . .	111
\texteb . . . . .	11413	tocenter (package) . . . . .	1022
textfit (package) . . . . .	997	[tocloft]:	
\textgreater . . . . .	5200	titles (option) . . . . .	133
\textit . . . . .	11473	tocloft (package) . . . . .	133, 148, 623, 1022
\textless . . . . .	5198	tocstyle (package) . . . . .	1028
\textlg . . . . .	11423	todo (package) . . . . .	1028
\textmd . . . . .	11393	todonotes (package) . . . . .	169, 1029
\textnormal . . . . .	11532	topcapt (package) . . . . .	1031
textpos (package) . . . . .	998	\tracingl warp . . . . .	194, 1357
\textrm . . . . .	11433	tram (package) . . . . .	1031
\textsc . . . . .	11483	transparent (package) . . . . .	1032
\textsf . . . . .	11443	trimclip (package) . . . . .	1032
\textsi . . . . .	11503	trivfloat (package) . . . . .	165, 1033
\textsl . . . . .	11522	truncate (package) . . . . .	1034
\textsubscript . . . . .	11773	\ttfamily . . . . .	11744
\textsuperscript . . . . .	11771	\TTh (program) . . . . .	74
\textttt . . . . .	11453	turnthepage (package) . . . . .	1034
\textulc . . . . .	11493	tutorial.tex (file) . . . . .	84
\textup . . . . .	11463		

twoup (package) . . . . .	1034	\warpprintonly . . . . .	115, 118, 929			
typearea (package) . . . . .	1035	watermark (package) . . . . .	1049			
typicons (package) . . . . .	1035	widetable (package) . . . . .	1049			
<b>U</b>						
\ulcshape . . . . .	11752	widows-and-orphans (package) . . . . .	1049			
ulem (package) . . . . .	1036	Windows (program) . . . . .	117, 218			
umoline (package) . . . . .	1037	witharrows (package) . . . . .	1050			
\underline . . . . .	11781	Word (program) . . . . .	75			
underscore (package) . . . . .	1038	WPMarkFloats (boolean) . . . . .	179, 247			
unicode-math (package) . . . . .	1038	WPMarkLOFT (boolean) . . . . .	180, 248			
units (package) . . . . .	154, 1040	WPMarkMath (boolean) . . . . .	180, 248			
unitsdef (package) . . . . .	1041	WPMarkMinipages (boolean) . . . . .	180, 247			
Unix (program) . . . . .	117, 217	WPMarkTOC (boolean) . . . . .	180, 248			
\up . . . . .	11779	WPTitleHeading (boolean) . . . . .	181, 248			
upref (package) . . . . .	1041	wrapfig (package) . . . . .	1051			
\upshape . . . . .	11746	<b>X</b>				
\url . . . . .	9317	xbmks (package) . . . . .	1052			
url (package) . . . . .	130, 1042	xcolor (package) . . . . .	157, 551, 1053			
\UseMinipageWidths . . . . .	125, 558, 11088	xchangebar (package) . . . . .	1063			
usingOSWindows (boolean) . . . . .	219	\XeLaTeX . . . . .	12083			
uspace (package) . . . . .	1042	XeLaTeX (program) [requirement] . . . . .	78			
<b>V</b>						
variorref (package) . . . . .	129	xellipsis (package) . . . . .	1063			
varwidth (package) . . . . .	233	\xetex . . . . .	12083			
verbatim (environment) . . . . .	7201	xetexko-vertical (package) . . . . .	1064			
verbatim (package) . . . . .	232	xfakebold (package) . . . . .	1064			
\VerbatimHTMLWidth (length) . . . . .	402	xfrac (package) . . . . .	1065			
\verbatiminput . . . . .	7193	\xfrachHTMLfontsize . . . . .	3			
verse (environment) . . . . .	2, 7142	xifthen (package) . . . . .	232			
verse (package) . . . . .	168, 1042, 1043	xindy (option) . . . . .	106, 109, 223			
versonotes (package) . . . . .	1044	xindy (program) . . . . .	146			
vertbars (package) . . . . .	1044	xindyCodepage (option) . . . . .	106, 222			
\vleftmargini (length) . . . . .	168, 401, 1043	xindyLanguage (option) . . . . .	106, 222			
\vleftskip (length) . . . . .	168, 401, 1043	xindyStyle (option) . . . . .	106, 146, 222			
vmargin (package) . . . . .	1045	xltabular (package) . . . . .	1067			
vowel (package) . . . . .	1045	xltextra (package) . . . . .	1068			
vpe (package) . . . . .	1046	xmpincl (package) . . . . .	1069			
vwcol (package) . . . . .	1046	xparse (package) . . . . .	170, 230			
<b>W</b>						
wallpaper (package) . . . . .	1048	xpatch (package) . . . . .	199			
warpall (environment) . . . . .	118, 939	xpiano (package) . . . . .	1069			
warpHTML (environment) . . . . .	115, 117, 940	xpinyin (package) . . . . .	1069			
warpHTML (option) . . . . .	107, 221	xr (package) . . . . .	1070			
\warpHTMLonly . . . . .	115, 118, 930	xr-hyper (package) . . . . .	1070			
warpingHTML (boolean) . . . . .	220	xstring (package) . . . . .	232			
warpingprint (boolean) . . . . .	220	xtab (package) . . . . .	164, 1071			
warpMathJax (environment) . . . . .	118, 946	xunicode (package) . . . . .	1072			
warpprint (environment) . . . . .	114, 117, 943	xurl (package) . . . . .	1073			
warpprint (option) . . . . .	107, 220	xy (package) . . . . .	1074			
<b>Z</b>						
zhlineskip (package) . . . . .	1075					
zpagelayout (package) . . . . .	1075					

## General Index

This is an index of instructions and concepts. Look here when wondering how to do something, and check the Troubleshooting Index when something goes wrong.

Symbols	CSS	
\, . . . . .	file selection . . . . .	
~ . . . . .	l warp.css . . . . .	
<b>A</b>		
accents	per HTML page . . . . .	
in section & file names . . . . .	project-specific changes . . . . .	
accessibility . . . . .	c table . . . . .	
adapting		
class . . . . .		
document . . . . .		
package . . . . .		
affiliation		
multiple authors . . . . .		
algorithmicx		
with newfloat, trivfloat . . . . .		
alt text . . . . .		
array		
mhchem . . . . .		
audio . . . . .		
author		
HTML meta tag . . . . .	danger icon . . . . .	
multiple . . . . .	debugging . . . . .	
<b>B</b>		
baseline	HTML debug comments . . . . .	
tabular . . . . .	tracing log . . . . .	
bibliography		
HTML page and toc . . . . .	Deja Vu . . . . .	
bitmapped fonts . . . . .	description . . . . .	
bugs . . . . .	HTML meta tag . . . . .	
<b>C</b>		display math . . . . .
<i>Calibre</i> . . . . .	complicated objects . . . . .	
chemistry	document . . . . .	
Greek symbols . . . . .	convert existing . . . . .	
class	DVI LATEX . . . . .	
modifying for l warp . . . . .	dynamic math . . . . .	
code listings . . . . .	dynamic math expressions . . . . .	
compiling		
custom . . . . .		
Computer Modern . . . . .		
converting		
class . . . . .	E	
document . . . . .	endnotes . . . . .	
package . . . . .	HTML page and toc . . . . .	
<b>D</b>		EPS image . . . . .
HTML meta tag . . . . .	converting . . . . .	
multiple . . . . .	using . . . . .	
<b>E</b>		EPUB . . . . .
HTML page and toc . . . . .	conversion software . . . . .	
multiple . . . . .	HTML conversion settings . . . . .	
error messages . . . . .	error messages . . . . .	
export		
	to word processor . . . . .	
<b>F</b>		
FAQ . . . . .	FAQ . . . . .	
filename		
accent in . . . . .	filename . . . . .	
hashed . . . . .	accent in . . . . .	
international languages . . . . .	hashed . . . . .	
length . . . . .	international languages . . . . .	
simplify . . . . .	length . . . . .	
underscore in . . . . .	simplify . . . . .	
unique . . . . .	underscore in . . . . .	

font	
Computer Modern	102
Deja Vu	102
ligatures	102
packages	102
selection	101
size	
<code>lateximage</code>	149, 535
<code>math, SVG</code>	149, 535
<code>xfrac</code>	1065
type 1 vector	101
type 3 bitmapped	101
footnotes	352
numbering	130
foreign	
section names	168
framed objects	125
Frequently Asked Questions	188
<b>G</b>	
generator	
HTML meta tag	384
GIF images	156, 550
gloss	134
glossaries	
HTML page and toc	132
language	134
options	134
processing	95
graphics	
file formats	155, 549
Greek	
chemistry symbols	673
<b>H</b>	
hash	
SVG image filename	518, 539
heading, word processor	181
horizontal space	122
between minipages	583
HTML	
alt text	100
conversion settings	109
debug comments	241
EPUB	176, 247
word processor	178, 247
conversion suggestions	121
entities, conversion	122
filename generation	115
headings	197
meta tag	
author	120, 352
description	119, 352
generator	384
title	112, 113, 120, 351
viewport	385
selecting print/HTML definitions	242
tabular column conversion	434
verbatim, in	122
hyperref	
and <code>xindy</code>	136
title text	100
<b>I</b>	
icon	
warning	198
image	
alt text	100
file formats	155, 549
GIF	156, 550
graphicx package	549
hashed filename	518, 539
PDF or EPS	
converting	96, 155, 549
using	155, 549
PNG and JPG	156, 550
processing	303
\includegraphics	
using	155, 549
index	
custom <code>makeindex</code> style file	145
custom <code>xindy</code> style file	146
custom display styles	147
formatting	506
HTML page and toc	132
letter headings	790
placement and toc options	147, 1018
processing	88, 89, 136
see, seealso, ranges	136
source code	136
table of contents	147, 1018
UTF-8	103
<code>xindy</code> and <code>hyperref</code>	136
inline math	
complicated objects	152
international	
section names	168
item	
empty	406
<b>J</b>	
JAVASCRIPT	
<code>MATHJAX</code>	148
JPG images	156, 550
<b>L</b>	
label	
in HTML	387
math environment	530
language	
glossaries	134
localization	100
language HTML metadata	382

lateximage	
font size	149, 535
processing	303
Latin Modern font	101
LIBREOFFICE	
conversion recommendations	181
import into	178
section headings	181
ligatures	102, 227
line numbers	198
link	
title text	100
list	
empty item	406
filename	123
listings, program code	122
locale	175
localization	100
LuaLaTeX	
detection	199
file & section names	372
lwarf	
loading	104
options	104
lwarf.ist	
customizing	145
lwarf.xdy	
customizing	146
lwarpmk	
customizing	186
M	
make utility	175
makeindex	
customizing	145
margin	
numbers	198
tags	198
markup languages	75
math	
alt text	100
display with complicated objects	152
dynamic	152, 325
font size—SVG	149, 535
inline with complicated objects	152
MATHJAX custom functions	150
MATHJAX summary	149
mathjax option	221
mathsvg option	221
mhchem	852
SVG summary	149
word processor conversion	180
MATHJAX	
accessibility	100
custom functions	150
custom script	301
mathjax option	221
summary	149
\mcolrowcell	162
MD5 hash	
SVG image filename	518, 539
memoir	
verse	1043
meta tag, HTML	
author	120, 352
description	119, 352
generator	384
title	120, 351
viewport	385
minipage	
framed	125
horizontal space between	583
modifying	
class	185
document	99
package	184
\mrowcell	162
\multicolumn	
with \multirow	162
\multimedia	159
multiple projects in a directory	96
\multirow	
with \multicolumn	162
\mrowcell and \mcolrowcell	162
N	
newfloat	
with trivfloat, algorithmicx	1033
nomenc	135
numbers	
left margin	198
P	
package	
modifying for lwarf	184
required	227
\par	
hooks	347
PDF image	
converting	96
using	155, 549
PERL	83
PNG images	156, 550
POPPLER	78, 83
print	
selecting print/HTML definitions	242
problems	188
program listings	122
programs	
utility	77
projects	96

\published	398	tracing log	241
		with newfloat, algorithmicx	1033
		troubleshooting	188
		HTML debug comments	241
		tracing log	241
		type 1 vector fonts	101
		type 3 bitmapped fonts	101
		<b>U</b>	
		underscore	
		filename	109, 123
		Unicode	
		enhanced coverage	102
		file & section names	372
		input characters	213
		selection	101
		UTF-8	
		enhanced coverage	102
		file & section names	372
		index	103
		locale	175
		selection	101
		utility	
		programs	77
		<b>V</b>	
		vector fonts	101
		verbatim	
		code and HTML tags	122
		video	159
		viewport	
		HTML meta tag	385
		<b>W</b>	
		warning icon	198
		word processor	
		conversion recommendations	181
		HTML conversion settings	178, 247
		section headings	181
		<b>X</b>	
		xcite	96
		Xe <sup>L</sup> ATEX	
		detection	199
		file & section names	372
		xindy	
		and hyperref	136
		customizing	146
		xparse	
		warnings	170
		xr	96
		xr-hyper	96

# Troubleshooting Index

This index is a sorted reference of problems and solutions. In order to make it easier to locate a solution, the same issue may be addressed by more than one entry.

Entries with higher page numbers are often duplicates of entries with lower page numbers, as the same warning may occur within the user manual and again within the source code for a given package.

A	C
abstract	<i>Calibre</i>
missing toc .....	EPUB conversion .....
acronym	caption
multiply-defined labels .....	numbering .....
\AddSubtitlePublished .....	options .....
affiliation .....	chemfig .....
alt tags .....	chemformula
AMSmath	MATHJAX .....
ntheorem	chemgreek
numbering .....	fontspec mapping .....
appendix	text-mode symbols .....
incorrect toc link .....	chemmacros
array	\makepolymerdelims .....
chemformula .....	redox reactions .....
MATHJAX .....	colortbl .....
arydshln .....	compiling
audio .....	slow MATHJAX .....
authblk	cross reference
\theauthor .....	incorrect link .....
titling .....	MATHJAX .....
author	missing .....
affiliation .....	CSS .....
formatting .....	ctable .....
autonum .....	
	D
	dita .....
babel	duplicate filename .....
French .....	
backref .....	E
backref .....	\endhead, etc. .....
bibliography	endnotes
HTML page and toc .....	HTML page and toc .....
bibtex	\ensuremath .....
\etalchar .....	epstopdf .....
Improper \prevdepth .....	EPUB .....
bigdelim .....	encoding .....
bigfoot .....	page order .....
booktabs .....	search order .....
boxes .....	section breaks .....
breqn	error messages .....
darray .....	\etalchar .....

F	G
<b>fancybox</b>	<b>gloss</b> . . . . . 134
\VerbatimFootnotes . . . . . 131, 722, 729	
<b>fancyvrb</b>	HTML page and toc . . . . . 132
\VerbatimFootnotes . . . . . 131, 722, 729	makeglossaries not found . . . . . 134, 763
<b>figure</b>	page numbers . . . . . 135, 764
macro in name . . . . . 191	style . . . . . 135, 764
<b>file</b>	<b>graphics</b>
inaccessible . . . . . 111	\rotatebox, \scalebox, \reflectbox . . . . . 156, 550
multiple projects in directory . . . . . 96	image format priorities . . . . . 156, 550
<b>filename</b>	images out of order . . . . . 90, 193
accents . . . . . 372	multimedia . . . . . 159
corrupted . . . . . 128, 168	optional arguments . . . . . 156, 550
duplicate . . . . . 129	scale option . . . . . 99, 155, 549
international, UTF-8 . . . . . 168	scaled . . . . . 766
Korean . . . . . 171	viewport . . . . . 156, 550
macro in name . . . . . 128	Greek packages . . . . . 673
math in . . . . . 99, 129, 148	grffile . . . . . 157, 778
Missing \$ inserted . . . . . 191	
<b>fixme</b> . . . . . 170, 737	
<b>float</b>	<b>H</b>
alignment . . . . . 122, 165	horizontal spacing . . . . . 166, 981
numbering . . . . . 166	<b>HTML</b>
out of sequence . . . . . 192	&, <, > . . . . . 122, 569
<b>floatrow</b>	alt tags . . . . . 152
\FBwidth and \FBheight . . . . . 166, 742	author . . . . . 352
with subfig . . . . . 166, 742	corrupted . . . . . 119, 124, 190, 193
<b>floatrow</b>	entities . . . . . 122, 569
\ttabbox . . . . . 160, 413	image appear as HTML code . . . . . 90, 193
<b>font</b>	inaccessible pages . . . . . 111, 113
ligatures . . . . . 102, 103	starred section . . . . . 132
missing symbols . . . . . 123, 994	invalid . . . . . 122
monospace . . . . . 103	missing pages
package conflicts . . . . . 102	filename not unique . . . . . 112
selection . . . . . 101	recompile . . . . . 193
UTF-8 . . . . . 101	SideTOCDepth and FileDepth . . . . . 111
<b>fontspec</b> . . . . . 102	SideTOCDepth and tocdepth . . . . . 111
<b>footmisc</b> . . . . . 130, 352	page did not update . . . . . 111, 193
<b>footnote</b>	settings
displaymath . . . . . 131, 722, 729	changed . . . . . 109
in math . . . . . 131	undefined . . . . . 190
in sectioning command . . . . . 130	validation . . . . . 122
memoir . . . . . 131, 353	\HTMLAuthor . . . . . 352
numbering . . . . . 130	<b>HTMLIndexCmd</b>
paragraph tags . . . . . 131, 722, 729	filenames . . . . . 106
sectioning, footmisc . . . . . 130, 352	
sectioning, verbatim . . . . . 131, 722, 729	<b>hyperref</b>
title . . . . . 391	backref . . . . . 130
verbatim . . . . . 131	comments between arguments . . . . . 130
\VerbatimFootnotes . . . . . 131, 722, 729	incorrect link . . . . . 192
<b>forest</b> . . . . . 756	
<b>formatting</b>	<b>I</b>
\bfseries etc. . . . . 122, 569	
<b>frames</b> . . . . . 125	<b>image</b>
	appears as HTML code . . . . . 90, 193
	format priorities . . . . . 156, 550
	incorrect . . . . . 90, 192, 193
	viewport . . . . . 156, 550

Improper \prevdepth	
<b>bibtex</b>	134
<b>boxes</b>	191
\includegraphics	
optional arguments	156, 550
scale	99, 155, 549
index	
empty	146
empty link	129, 192
formatting	506
HTML page and toc	132
missing entries	136
numbers, not links	232
reference ranges	146
see and seealso	146
styling references	146
xindy and hyperref	146
xstring bug	232
<b>K</b>	
keyfloat	167, 800
<b>L</b>	
label	
\nameref empty	129, 192
characters	129, 192
Label(s) may have changed	191
\LateximageFontSizeName	536
Leaders not followed by proper glue	191
<i>LibreOffice</i>	
import	178
ligatures	103
LINUX	117, 217
list	
empty item	123, 406
listings	192
lists	
label formatting	406
locale	175
longtable	
\endhead, etc.	163
lrbox	124
ltxtable	
numbering	823
lua <sup>A</sup> T <sub>E</sub> X	102
\LWRbackslash	172
\LWRdollar	172
\LWRhash	172
\LWRopquote	172
\LWRopseq	172
\LWRpercent	172
<b>M</b>	
MAC OS	117, 217
<i>makeglossaries</i>	
not found	134, 763
\b makelabel	406
manyfoot	131, 829
\marginpar	124, 358
math	
alt tags	191
appears as HTML code	90, 193
chemformula	170
custom macros	191
dynamic	325
equation numbering	
ntheorem	152, 892
file name	99, 129, 148
footnote	131
in T <sub>E</sub> X boxes	149
incorrect	90, 193, 325
non-math contents	191
section name	99, 129, 148
slow or failed compile	191
MATHJAX	151
subequations	151
tabbing	160, 405
Tikz	152
MATHJAX	
chemformula	170, 668
custom script	301
errors	152, 192, 325
mathtools	152, 835
mhchem	852
\multicolumn	151
\multirow	151, 163, 867
physics	154
references	151
siunitx	153, 548, 961
slow compilation	150
starred macros	151
subequations	151
unsupported packages	151, 192
MATHJAX	
arydshln	626
booktabs	649
mathtools	152, 834
\mcrlowcell	162
media9	159
memoir	
footmisc	131, 353
options clash	167, 1079
version clash	167, 1079
mhchem	
MATHJAX	852
nested dollar signs	852
minipage	
alignment	125, 559
horizontal space between	583
in a span	124, 558
inline	124, 558

multicols, width in . . . . .	125, 558	version numbers with memoir . . . . .	167, 1079
size . . . . .	124, 558	page inaccessible . . . . .	111
tabular, width in . . . . .	125, 558	page counter references . . . . .	129
Misplaced \noalign . . . . .	163, 819	SVG images . . . . .	90, 193
tabular rules . . . . .	161, 414	page numbers . . . . .	129, 192, 554
Misplaced \omit . . . . .	245	pdftricks . . . . .	158, 918
Misplaced alignment tab character & . . . . .	126	perltex . . . . .	174
ctable . . . . .	164, 698	pfnote numbering . . . . .	131, 920
floatrow . . . . .	166, 742	physics MATHJAX . . . . .	154
frames . . . . .	126	polyglossia Undefined control sequence . . . . .	169, 596
supertabular . . . . .	164, 987, 1071	poppler Syntax Warning (ligature) . . . . .	749
tabular macros . . . . .	160, 325, 413	PrintIndexCmd . . . . .	106
Missing \$ inserted . . . . .	191	projects multiple . . . . .	96
filename or URL . . . . .	191	psfrag . . . . .	158
Missing \begin{document} . . . . .	121	pstool . . . . .	158, 932
package options . . . . .	121	pstricks . . . . .	157, 933
morewrites . . . . .	146, 190	pythontex . . . . .	174
movie15 . . . . .	159		
\mrowcell . . . . .	162		
MS-WINDOWS . . . . .	117, 218		
multicol \linewidth . . . . .	125, 559		
\multicolumn MATHJAX . . . . .	151		
multimedia . . . . .	159		
multiple projects in a directory . . . . .	96		
multiply-defined labels acronym . . . . .	607		
\multirow and \multicolumn . . . . .	162, 867		
multirow MATHJAX . . . . .	151, 163, 867		
\mrowcell and \mcolrowcell . . . . .	162		
		R	
		reference % character between arguments . . . . .	192
		empty link . . . . .	129, 192
		incorrect link . . . . .	192
		label characters . . . . .	129, 192
		MATHJAX . . . . .	151
		missing or incorrect . . . . .	192
		page number . . . . .	129, 192, 554
		repeating index . . . . .	940
		rface . . . . .	175
		S	
		sample_projects.css overwritten . . . . .	116
		\savebox . . . . .	124
		\sbox . . . . .	124
		scale (\includegraphics option) . . . . .	99, 155, 549
		sectioning accents . . . . .	372
		duplicate name . . . . .	129
		international language . . . . .	168
		macro in name . . . . .	128, 191
		math in name . . . . .	99, 129, 148
		missing . . . . .	111
		starred section . . . . .	132
		word processor import . . . . .	181
		sunitx . . . . .	153, 547, 960
		MATHJAX . . . . .	153, 548, 961
		S column . . . . .	162, 414
		tabular S and s columns . . . . .	153, 547, 960

with <i>TeXMaths</i>	180	\theauthor and authblk	391, 392
splitidx		threeparttable	163
\thepage and \AtWriteToIndex	137, 974	tikz	
starred macros		in math	152
MATHJAX	151	matrices, &	156, 1005
subcaption		title	
numbering	166	affiliation	392
subfig		newlines	119
options	166, 981	\thanks	391
with floatrow	166, 742	titling	
SVG image		authblk	133, 391, 633, 1013
appears as HTML code	90, 193	hooks	398
incorrect	90, 192, 193	tocloft	
math incorrect	325	chapter titles	133, 148, 623, 1022
out of order	90, 193	todonotes	169, 824, 1029
sympytex	175	tracing l warp	194
Syntax Warning (ligature)	749	tram	1031
<b>T</b>			
tabbing		transparent	1032
math	160, 405	<b>U</b>	
table		Undefined control sequence	
macro in name	191	polyglossia	169, 596
numbering	823	Unicode	
Table of Contents		fonts	101
missing	113	UTF-8 locale	175
tabular		units	154
baselines	433	UNIX	117, 217
corrupt rows	160, 413, 465	URL	
\endhead, \endfoot, \endlastfoot	163, 819	Missing \$ inserted	191
inside an environment	160, 413, 465	\usebox	124
\kill	163, 819	UTF-8	
macro inside	161, 413	locale	175
Misplaced \noalign	161, 414	<b>V</b>	
Misplaced alignment tab character &		verbatim	
macros	160, 413	footnote	131
rules	325	framed	127, 722
\multicolumn with \multirow	162	VerbatimFootnotes	131, 722, 729
\multirow \mrowcell and \mcolrowcell	162	verse	
\newcolumntype	161, 414	spacing	168, 401, 1043
numbering	1068	version numbers	
row corruption	161, 413	with memoir	167, 1079
rules	161, 414	video	159
S column	162, 414	viewport	156, 550
TeX capacity exceeded		<b>W</b>	
Text input levels equals 15	191	warning messages	188
TeXMaths	180	warpall	190
text		warpHTML	117, 190
&, <, >	122, 569	warpprint	118, 190
\bfseries etc.	122, 569	WINDOWS	117, 218
corrupted	101	word processor	
Text input levels equals 15	191	import	178
textcomp		sectioning headings	181
missing symbols	123, 994		

<b>X</b>	
xcite . . . . .	96
xeLATEX . . . . .	102
xfakebold . . . . .	1065
xfrac . . . . .	1065
xindy	
hyperref . . . . .	146
options	
HTMLIndexCmd . . . . .	107
xltabular	
numbering . . . . .	1068
xparse . . . . .	170
xr . . . . .	96
xr-hyper . . . . .	96
xstring . . . . .	232
LatexmkIndexCmd . . . . .	107
PrintIndexCmd . . . . .	106

## **Index of Indexes**

<b>C</b>		<b>I</b>	
Change History .....	1109	Index of Objects .....	1140
<b>G</b>		<b>T</b>	
General Index .....	1161	Troubleshooting Index .....	1165