

L^AT_EX Class for the *Association for Computing Machinery**

Boris Veytsman[†]

2020/02/08, v1.69

Abstract

This package provides a class for typesetting publications of the Association for Computing Machinery.

Contents

1	Introduction	3
2	User's guide	3
2.1	Installation	3
2.2	Invocation and options	6
2.3	Top matter	7
2.4	Algorithms	20
2.5	Figures and tables	20
2.6	Descriptions of images	22
2.7	Theorems	22
2.8	Online-only and offline-only material	22
2.9	Note about anonymous mode	23
2.10	Acknowledgments	23
2.11	Bibliography	24
2.12	Colors	27
2.13	Other notable packages and typographic remarks	28
2.14	Disabled or forbidden commands	28
2.15	A note for wizards: <code>acmart-preload-hook.tex</code>	29
2.16	Currently supported publications	29

*©2016–2019, Association for Computing Machinery

[†]borisv@lk.net, boris@varphi.com

3	Implementation	32
3.1	Identification	32
3.2	Preload hook	32
3.3	Options	32
3.4	Setting switches	36
3.5	Loading the base class and package	37
3.6	Citations	38
3.7	Paper size and paragraphing	45
3.8	Fonts	48
3.9	Image descriptions	49
3.10	Floats	50
3.11	Lists	52
3.12	Top-matter data	54
3.13	Concepts system	68
3.14	Copyright system	69
3.15	Typesetting top matter	74
3.16	Headers and Footers	89
3.17	Sectioning	96
3.18	TOC lists	98
3.19	Theorems	98
3.20	Balancing columns	102
3.21	Acknowledgments	102
3.22	Conditional typesetting	103
3.23	Additional bibliography commands	103
3.24	End of Class	103

1 Introduction

The Association for Computing Machinery¹ is the world's largest educational and scientific computing society, which delivers resources that advance computing as a science and a profession. It was one of the early adopters of \TeX for its typesetting.

It provided several different classes for a number of journals and conference proceedings. Unfortunately during the years since these classes were written, the code was patched many times, and supporting different versions of the classes became difficult.

This package provides the uniform interface for all ACM publications. It is intended to replace all the different classes and packages and provide an up-to-date \LaTeX package.

This package uses only free \TeX packages and fonts included in \TeX Live, Mik \TeX and other popular \TeX distributions. It is intended to be published in these distributions itself, which minimizes users' efforts in the installation and support of this package.

I am grateful to Michael D. Adams, Leif Andersen, Lawrence Christopher Angrave, Dirk Beyer, Joachim Breitner, Benjamin Byholm, Nils Anders Danielsson, Michael Ekstrand, Matthew Fluet, Paolo G. Giarrusso, Ben Greenman, Enrico Gregorio, Jamie Davis, Peter Kemp, Luis Leiva, Ben Liblit, Rholaïs Lii, LianTze Lim, Kai Mindermann, Frank Mittelbach, Serguei Mokhov, Ross Moore, John Owens, Joel Nider, Tobias Pape, Philip Quinn, Mathias Rav, Andreas Reichinger, Matteo Riondato, Craig Rodkin, Bernard Rous, Feras Saad, Kerry A. Seitz, Jr., David Shamma, Gabriel Scherer, Kartik Singhal, Stephen Spencer, Shin Hwei Tan, Daniel Thomas, Zack Weinberg, John Wickerson and many others for their invaluable help.

The development version of the package is available at <https://github.com/borisveytsman/acmart>.

2 User's guide

This class uses many commands and customizatón options, so it might appear intimidating for a casual user. Do not panic! Many of these commands and options can be safely left with their default values or the values recommended by your conference or journal editors. If you have problems or questions, do not hesitate to ask me directly or the community at <https://github.com/borisveytsman/acmart>, <https://tex.stackexchange.com> or the closest \TeX Users Group. The world-wide \TeX Users Group is at <https://tug.org/>; please consider joining us if you use \TeX regularly.

2.1 Installation

Most probably, you already have this package installed in your favorite \TeX distribution; if not, you may want to upgrade. You may need to upgrade it anyway since this package uses a number of relatively recent packages, especially the ones related to fonts.

The latest released version of this package can be found on CTAN: <https://www.ctan.org/pkg/acmart>. The development version can be found on GitHub: <https://github.com/borisveytsman/acmart>. At this address you can file a bug report—or even contribute your own enhancement by making a pull request.

¹<http://www.acm.org/>

Please note that the version on Github is a development (or experimental) version: please download it for testing new features. The production version is the one on CTAN and ACM sites.

Most users should not attempt to install this package themselves but should rather rely on their \TeX distributions to provide it. If you decide to install the package yourself, follow the standard rules:

1. Run `latex acmart.ins`. This will produce the file `acmart.cls`
2. Put the files `acmart.cls` and `ACM-Reference-Format.bst` in places where \TeX can find them (see [1] or the documentation for your \TeX system).
3. Update the database of file names. Again, see [1] or the documentation for your \TeX system for the system-specific details.
4. The file `acmart.pdf` provides the documentation for the package. (This is probably the file you are reading now.)

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

This class uses a number of other packages. They are included in all major \TeX distributions (\TeX Live, Mac \TeX , Mik \TeX) of 2015 and later, so you probably have them installed. Just in case here is the list of these packages:

- *amscs*, <http://www.ctan.org/pkg/amscs>
- *amsfonts*, <http://www.ctan.org/pkg/amsfonts>
- *amsmath*, <http://www.ctan.org/pkg/amsmath>
- *binhex*, <http://www.ctan.org/pkg/binhex>
- *balance*, <http://www.ctan.org/pkg/balance>
- *booktabs*, <http://www.ctan.org/pkg/booktabs>
- *caption*, <http://www.ctan.org/pkg/caption>
- *comment*, <http://www.ctan.org/pkg/comment>
- *cm-super*, <http://www.ctan.org/pkg/cm-super>
- *cmap*, <http://www.ctan.org/pkg/cmap>
- *draftwatermark*, <http://www.ctan.org/pkg/draftwatermark>
- *environ*, <http://www.ctan.org/pkg/environ>
- *etoolbox*, <http://www.ctan.org/pkg/etoolbox>
- *fancyhdr*, <http://www.ctan.org/pkg/fancyhdr>
- *float*, <http://www.ctan.org/pkg/float>

- *fontaxes*, <http://www.ctan.org/pkg/fontaxes>
- *geometry*, <http://www.ctan.org/pkg/geometry>
- *graphics*, <http://www.ctan.org/pkg/graphics>
- *hyperref*, <http://www.ctan.org/pkg/hyperref>
- *ifluatex*, <http://www.ctan.org/pkg/ifluatex>
- *ifxetex*, <http://www.ctan.org/pkg/ifxetex>
- *inconsolata*, <http://www.ctan.org/pkg/inconsolata>
- *libertine*, <http://www.ctan.org/pkg/libertine>
- *manyfoot*, <http://www.ctan.org/pkg/manyfoot>
- *microtype*, <http://www.ctan.org/pkg/microtype>
- *mmap*, <http://www.ctan.org/pkg/mmap>
- *ms*, <http://www.ctan.org/pkg/ms>
- *mweights*, <http://www.ctan.org/pkg/mweights>
- *natbib*, <http://www.ctan.org/pkg/natbib>
- *nccfoots*, <http://www.ctan.org/pkg/nccfoots>
- *newtx*, <http://www.ctan.org/pkg/newtx>
- *oberdiek*, <http://www.ctan.org/pkg/oberdiek>
- *pdftex-def*, <http://www.ctan.org/pkg/pdftex-def>
- *refcount*, <http://www.ctan.org/pkg/refcount>
- *setspace*, <http://www.ctan.org/pkg/setspace>
- *textcase*, <http://www.ctan.org/pkg/textcase>
- *totpages*, <http://www.ctan.org/pkg/totpages>
- *trimspaces*, <http://www.ctan.org/pkg/trimspaces>
- *upquote*, <http://www.ctan.org/pkg/upquote>
- *url*, <http://www.ctan.org/pkg/url>
- *xcolor*, <http://www.ctan.org/pkg/xcolor>
- *xkeyval*, <http://www.ctan.org/pkg/xkeyval>
- *xstring*, <http://www.ctan.org/pkg/xstring>

2.2 Invocation and options

To use this class, put in the preamble of your document

```
\documentclass[<options>]{acmart}
```

There are several options corresponding to the type of the document and its general appearance. They are described below. Generally speaking, the options have key=value forms, for example,

```
\documentclass[format=acmsmall, screen=true, review=false]{acmart}
```

The option `format` describes the format of the output. There are several possible values for this option, for example,

```
\documentclass[format=acmtog]{acmart}
```

Actually the words `format=` can be omitted, e.g.,

```
\documentclass[acmtog, review=false]{acmart}
```

The possible formats are listed in Table 1. Note that formats starting with `acm` are intended for journals and transactions, while formats starting with `sig` are intended for proceedings published as books.

Note that sometimes conference proceedings are published as a special issue (or issues) of an ACM journal. In this case, you should use the journal format for a conference paper. Please contact your conference committee if in doubt.

There are several Boolean options that can take `true` or `false` values. They are listed in Table 2. The words `=true` can be omitted when setting a Boolean option, so instead of `screen=true` one can write just `screen`, for example,

```
\documentclass[acmsmall, screen, review]{acmart}
```

The option `review` is useful when combined with the `manuscript` format option. It provides a version suitable for reviewers and copy editors.

The default for the option `screen` depends on the publication. At present it is `false` for all publications *but* PACM, since PACM is now electronic-only. Thus PACM titles (see Table 5) set this option to `true`. In the future this option may involve additional features suitable for on-screen versions of articles.

The option `natbib` is used when the corresponding BibTeX style is based on `natbib`. In most cases you do not need to set it. See Section 2.11.

The option `anonymous` is used for anonymous review processes and causes all author information to be obscured.

The option `timestamp` is used to include a time stamp in the footer of each page. When preparing a document, this can help avoid confusing different revisions. The footer also includes the page range of the document. This helps detect missing pages in hard copies.

Table 1: The possible values for the format option

Value	Meaning
<code>manuscript</code>	A manuscript. This is the default.
<code>acmsmall</code>	Small single-column format. Used for CIE, CSUR, JACM, JDIQ, JEA, JERIC, JETC, PACMCGIT, PACMHCI, PACMPL, TAAS, TACCESS, TACO, TALG, TALLIP (formerly TALIP), TCPS, TDS, TEAC, TECS, TELO, THRI, TIIS, TIOT, TISSEC, TIST, TKDD, TMIS, TOCE, TOCHI, TOCL, TOCS, TOCT, TODAES, TODS, TOIS, TOIT, TOMACS, TOMM (formerly TOMCCAP), TOMPECS, TOMS, TOPC, TOPLAS, TOPS, TOS, TOSEM, TOSN, TQC, TRETS, TSAS, TSC, TSLP and TWEB, including special issues.
<code>acmlarge</code>	Large single-column format. Used for DTRAP, HEALTH, IMWUT, JOCCH, POMACS and TAP, including special issues.
<code>acmtog</code>	Large double-column format. Used for TOG, including annual conference Technical Papers.
<code>sigconf</code>	Proceedings format for most ACM conferences (with the exceptions listed below) and all ICPS volumes.
<code>sigplan</code>	Proceedings format for SIGPLAN conferences.
<code>sigchi</code>	Proceedings format for SIGCHI conferences.
<code>sigchi-a</code>	Format for SIGCHI extended abstracts.

The option `authordraft` is intended for author’s drafts that are not intended for distribution. It typesets a copyright block to give the author an idea of its size and the overall size of the paper but overprints it with the phrase “Unpublished working draft. Not for distribution.”, which is also used as a watermark. This option sets `timestamp` and `review` to true, but these can be overridden by setting these options to false *after* setting `authordraft` to true.

The option `balance` determines whether the last page in the two column mode has balanced columns. By default it is true; however, it may lead to problems for some documents. Set it to false if you encounter compilation errors. Note that for one page documents `\balance` command might cause problems.

The option `urlbreakonhyphens` determines whether URLs can be split between lines after hyphens. By default it is true. Set it to false to disallow these breaks.

2.3 Top matter

A number of commands set up *top matter* or (in computer science jargon) *metadata* for an article. They establish the publication name, article title, authors, DOI and other data. Some of these commands, like `\title` and `\author`, should be put by the authors. Others, like `\acmVolume` and `\acmDOI`—by the editors. Below we describe these commands and mention who should issue them. These macros should be used *before* the `\maketitle` command. Note that in previous versions of ACM classes some of these commands should be used before `\maketitle`, and some after it. Now they all must be

Table 2: Boolean options

Option	Default	Meaning
review	false	A review version: lines are numbered and hyperlinks are colored
screen	see text	A screen version: hyperlinks are colored
natbib	true	Whether to use the natbib package (see Section 2.11)
anonymous	false	Whether to make author(s) anonymous
authorversion	false	Whether to generate a special version for the authors' personal use or posting (see Section 2.3)
nonacm	false	Use the class typesetting options for a non-ACM document, which will not include the conference/journal header and footers or permission statements
timestamp	false	Whether to put a time stamp in the footer of each page
authordraft	false	Whether author's-draft mode is enabled
acmthm	true	Whether to define theorem-like environments, see Section 2.7
balance	true	Whether to balance the last page in two column mode
urlbreakonhyphens	true	Whether to break urls on hyphens

used before `\maketitle`.

This class internally loads the `amsart` class, so many top-matter commands are inherited from `amsart` [2].

`\acmJournal` The macro `\acmJournal{<shortName>}` sets the name of the journal or transaction for journals and transactions. The argument is the short name of the publication *in uppercase*, for example,

```
\acmJournal{TOMS}
```

The currently recognized journals are listed in Table 5. Note that conference proceedings published in *book* form do not set this macro.

`\acmConference` The macro `\acmConference[<short name>]{<name>}{<date>}{<venue>}` is used for conference proceedings published in the book form. The arguments are the following:

short name: the abbreviated name of the conference (optional).

name: the name of the conference.

date: the date(s) of the conference.

venue: the place of the conference.

Examples:

```
\acmConference[TD'15]{Technical Data Conference}{November
12--16}{Dallas, TX, USA}
\acmConference{SA'15 Art Papers}{November 02--06, 2015}{Kobe, Japan}
```

`\acmBooktitle` By default we assume that conference proceedings are published in the book named *Proceedings of CONFERENCE*, where *CONFERENCE* is the name of the conference inferred from the command `\acmConference` above. However, sometimes the book title is different. The command `\acmBooktitle` can be used to set this title, for example,

```
\acmBooktitle{Companion to the first International Conference on the
Art, Science and Engineering of Programming (Programming '17)}
```

An ACM paper should have either `\acmJournal` or `\acmConference` command. If it has both (or more) commands, the last one takes precedence. Note that if you have the command `\acmConference` in a journal format like `acmsmall`, the class will use conference format for bibstrip and reference citation formatting. In the samples directory there is a file `sample-acmsmall-conf.tex` with the example of this usage.

`\editor` In most cases, conference proceedings are edited. You can use the command `\editor{<editor>}` to set the editor of the volume. This command can be repeated, for example,

```
\editor{Jennifer B. Sartor}
\editor{Theo D'Hondt}
\editor{Wolfgang De Meuter}
```

`\title` The command `\title`, as in the `amsart` class, has two arguments: one optional, and one mandatory:

```
\title[\langle ShortTitle \rangle]{\langle FullTitle \rangle}
```

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

It is expected that this command is inserted by the author of the manuscript.

`\subtitle` Besides title, ACM classes allow a subtitle, set with the `\subtitle{\langle subtitle \rangle}` macro.

The commands for specifying authors are highly structured. The reason is they serve double duty: the authors' information is typeset in the manuscript *and* is used by the metadata extraction tools for indexing and cataloguing. Therefore it is very important to follow the guidelines exactly.

`\author` The basic commands are `\author`, `\orcid` (for the researchers registered with OR-

`\orcid` CID, <http://www.orcid.org/>), `\affiliation` and `\email`. In the simplest case, you

`\affiliation` enter them in this order:

```
\email
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
```

Do *not* use the \LaTeX `\and` macro or commas, or `\\` between the authors! Each author deserves his or her own `\author` command. An attempt to list several authors or their e-mails in one command leads to a warning or an error. This is not a bug, but the expected behavior.

Note that some formats do not typeset e-mails or ORCID identifiers. Do not worry: the metadata tools will get them.

Sometimes an author has several affiliations. In this case, the `\affiliation` command should be repeated:

```
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}
```

Similarly you can repeat the `\email` command.

You may have several authors with the same affiliation, different affiliations, or overlapping affiliations (author A_1 is affiliated with institutions I_1 and I_2 , while author A_2 is affiliated with I_2 only, author A_3 is affiliated with I_1 and I_3 , etc.). The recommended solution is to put the `\affiliation` commands after each author, possibly repeating them:

```
\author{...}
\orcid{...}
```

```

\affiliation{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\email{...}
\author{...}
\orcid{...}
\affiliation{...}
\affiliation{...}
\email{...}

```

In some cases, when several authors share the same affiliation, you can try to save space using the format

```

\author{...}
\email{...}
\author{...}
\email{...}
\affiliation{...}

```

However, this format is not generally recommended.

`\additionalaffiliation` In some cases, too many affiliations can take too much space. The command `\additionalaffiliation{<affiliation>}` creates a footnote after an author's name with the words "Also with {<affiliation>}". You should use this command only as a last resort. An example of usage is:

```

\author{G. Tobin}
\author{Ben Trovato}
\additionalaffiliation{%
  \institution{The Th{\o}rv{\a}ld Group}
  \streetaddress{1 Th{\o}rv{\a}ld Circle}
  \city{Hekla}
  \country{Iceland}}
\affiliation{%
  \institution{Institute for Clarity in Documentation}
  \streetaddress{P.O. Box 1212}
  \city{Dublin}
  \state{Ohio}
  \postcode{43017-6221}}

```

Here Trovato and Tobin share their affiliation with the Institute for Clarity in Documentation, but only Ben Trovato is affiliated with The Thørväld Group.

The `\affiliation` and `\additionalaffiliation` commands are further structured to interact with the metadata extraction tools. Inside these commands you should use the `\position`, `\institution`, `\department`, `\city`, `\streetaddress`, `\state`, `\postcode`, and `\country` commands.

and `\country` macros to indicate the corresponding parts of the affiliation. Note that in some cases (for example, journals) these parts are not printed in the resulting copy, but they *are* necessary since they are used by the XML metadata extraction programs. Do *not* put commas or `\\` between the elements of `\affiliation`. They will be provided automatically.

An example of the author block:

```
\author{A. U. Thor}
\orcid{1234-4564-1234-4565}
\affiliation{%
  \institution{University of New South Wales}
  \department{School of Biomedical Engineering}
  \streetaddress{Samuels Building (F25), Kensington Campus}
  \city{Sidney}
  \state{NSW}
  \postcode{2052}
  \country{Australia}}
\email{author@nsw.au.edu}
\author{A. N. Other}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}
\author{C. O. Respondent}
\orcid{1234-4565-4564-1234}
\affiliation{%
  \institution{University of Pennsylvania}
  \city{Philadelphia}
  \state{PA}
  \country{USA}}
\affiliation{%
  \institution{University of New South Wales}
  \city{Sidney}
  \state{NSW}
  \country{Australia}}
```

Note that the old ACM conference formats did not allow more than six authors and required some effort from authors to achieve alignment. The new format is much better in this.

Sometimes an author works in several departments within the same insitution. There could be two situations: the departments are independent, or one department is within another. In the first case, just repeat the command `\department` several times. To handle the second case the command has an optional numerical parameter. The departments with higher numbers are higher in the organizational chart. Compare

```
\affiliation{%
  \department[0]{Department of Lunar Studies} % 0 is the default
  \department[1]{John Doe Institute} % higher than 0
```

```
\institution{University of San Serriffe}
\country{San Serriffe}}
```

and

```
\affiliation{%
  \department{Department of Lunar Studies} % Not in the John Doe Institute!
  \department{John Doe Institute}
  \institution{University of San Serriffe}
  \country{San Serriffe}}
```

The command `\affiliation` formats its output according to American conventions. This might be wrong for some cases. Consider, for example, a German address. In Germany, the postcode is put before the city and is not separated by a comma. We can handle this order using

```
\affiliation{%
  \institution{Fluginstitut}
  \streetaddress{Sonnenallee 17}
  \postcode{123456}
  \city{Helm}
  \country{Germany}}
```

However, the comma after the postcode is unfortunate: the address will be typeset (in some formats) as

```
Fluginstitut
Sonnenallee 17
123456, Helm, Germany
```

To overcome this problem, the command `\affiliation` has an optional parameter `obeypunctuation`, which can be `false` (the default) or `true`. If this parameter is `true`, `\affiliation` obeys the author's command. Thus

```
\affiliation[obeypunctuation=true]{%
  \institution{Fluginstitut}\\
  \streetaddress{Sonnenallee 17}\\
  \postcode{123456}
  \city{Helm},
  \country{Germany}}
```

will be typeset as

```
Fluginstitut
Sonnenallee 17
123456 Helm, Germany
```

Note that you should *not* use this option for journals.

It is expected that these commands are inserted by the author of the manuscript.

`\thanks` Like `amsart` (and unlike standard \LaTeX), we allow `\thanks` only *outside* of the commands `\title` and `\author`. This command is obsolete and should *not* be used in most cases. Do not list your acknowledgments or grant sponsors here. Put this information in the `acks` environment (see Section 2.10).

`\authorsaddresses` In some formats, addresses are printed as a footnote on the first page. By default \LaTeX typesets them itself using the information you give it. However, you can override its choice using the command `\authorsaddresses{<contact addresses>}`, for example,

```
\authorsaddresses{%
  Authors' addresses: G.~Zhou, Computer Science Department, College of
  William and Mary, 104 Jameson Rd, Williamsburg, PA 23185, US;
  V.~B\eranger, Inria Paris-Rocquencourt, Rocquencourt, France;
  A.~Patel, Rajiv Gandhi University, Rono-Hills, Doimukh, Arunachal
  Pradesh, India; H.~Chan, Tsinghua University, 30 Shuangqing Rd,
  Haidian Qu, Beijing Shi, China; T.~Yan, Eaton Innovation Center,
  Prague, Czech Republic; T.~He, C.~Huang, J.~A.~Stankovic University
  of Virginia, School of Engineering Charlottesville, VA 22903, USA;
  T. F. Abdelzaher, (Current address) NASA Ames Research Center,
  Moffett Field, California 94035.}
```

You can *suppress* printing authors' addresses by setting them to an empty string: `\authorsaddresses{}`. Please note that authors' addresses are mandatory for journal articles.

`\titlenote` While the command `\thanks` generates a note without a footnote mark, sometimes
`\subtitlenote` the authors might need notes more tightly connected to the title, subtitle or author. The
`\authornote` commands `\titlenote`, `\subtitlenote` and `\authornote` that follow the corresponding commands (`\title`, `\subtitle` and `\author`) generate such notes. For example,

```
\title{This is a title}
\titlenote{This is a titlenote}
\author{A. U. Thor}
\authornote{This is an authornote}
```

Please never use a `\footnote` inside an `\author` or `\title` command since this confuses the metadata extraction software. (Actually these commands now produce errors.)

`\authornotemark` Sometimes one may need to have the same footnote connected to several authors. The command `\authornotemark[<number>]` adds just the footnote mark, for example,

```
\author{A. U. Thor}
\authornote{Both authors contributed equally to the paper}
...
\author{A. N. Other}
\authornotemark[1]
```

The correct numbering of these marks is the responsibility of the user.

`\acmVolume` The macros `\acmVolume`, `\acmNumber`, `\acmArticle`, `\acmYear` and `\acmMonth` are
`\acmNumber` inserted by the editor and set the journal volume, issue, article number, year and month
`\acmArticle` correspondingly. The arguments of all these commands, including `\acmMonth`, is numer-
`\acmYear` ical. For example,
`\acmMonth`

```

\acmVolume{9}
\acmNumber{4}
\acmArticle{39}
\acmYear{2010}
\acmMonth{3}

```

Note that `\acmArticle` is used not only for journals but also for some conference proceedings.

`\acmArticleSeq` The articles in the same issue of a journal have a *sequence number*. It is used to
 vertically position the black blob on the first page of some formats. By default it is the
 same as the article number, but the command `\acmArticleSeq{<n>}` can be used to
 change it:

```

\acmArticle{39}    % The sequence number will be 39 by default
\acmArticleSeq{5} % We redefine it to 5

```

Setting this number to zero suppresses the blob.

`\acmSubmissionID` If your paper got a Submission ID from the Conference Management System, put it
 here:

```
\acmSubmissionID{123-A56-BU3}
```

`\acmPrice` The macro `\acmPrice{<price>}` sets the price for the article, for example,

```
\acmPrice{25.00}
```

Note that you do not need to put the dollar sign here, just the amount. By default the price is \$15.00, unless the copyright is set to `usgov`, `rightsretained`, `iw3c2w3`, or `iw3c2w3g`, when it is suppressed. Note that to override the defaults you need to set the price *after* the `\setcopyright` command. Also, the command `\acmPrice{}` suppresses the printing of the price.

`\acmISBN` Book-like volumes have ISBN numbers attached to them. The macro `\acmISBN{<ISBN>}`
 sets it. Normally it is set by the typesetter, for example,

```
\acmISBN{978-1-4503-3916-2}
```

Setting it to the empty string, as `\acmISBN{}`, suppresses printing the ISBN.

`\acmDOI` The macro `\acmDOI{<DOI>}` sets the DOI of the article, for example,

```
\acmDOI{10.1145/9999997.9999999}
```

It is normally set by the typesetter. Setting it to the empty string, as `\acmDOI{}`, suppresses the DOI.

`\acmBadgeR` Some conference articles get special distinctions, for example, the artifact evaluation
`\acmBadgeL` for PPOPP 2016 (see <http://ctuning.org/ae/ppopp2016.html>). These articles display special badges supplied by the conference organizers. This class provides commands to add these badges: `\acmBadgeR[<url>]{<graphics>}` and `\acmBadgeL[<url>]{<graphics>}`. The first command puts the badge to the right of the title, and the second one—to the left. The exception is the `sigchi-a` mode for SIGCHI extended abstracts, which puts the badges on the left margin. The arguments have the following meaning: [*<url>*], if provided, sets the link to the badge authority in the screen version, while {*<graphics>*} sets the graphics file with the badge image. The file must be a cropped square, which is scaled to a standard size in the output. For example, if the badge image is `ae-logo.pdf`, the command is

```
\acmBadgeR[http://ctuning.org/ae/ppopp2016.html]{ae-logo}
```

`\startPage` The macro `\startPage{<page>}` sets the first page of the article in a journal or book. It is used by the typesetter.

`\terms` The command `\keywords{<keyword, keyword,...>}` sets keywords for the article.
`\keywords` They must be separated by commas, for example,

```
\keywords{wireless sensor networks, media access control,  
multi-channel, radio interference, time synchronization}
```

`CCSXML` ACM publications are classified according to the ACM Computing Classification
`\ccsdesc` Scheme (CCS). CCS codes are used both in the typeset version of the publications *and* in the metadata in various databases. Therefore you need to provide both \TeX commands and XML metadata with the paper.

The tool at <http://dl.acm.org/ccs.cfm> can be used to generate CCS codes. After you select the topics, click on “Generate CCS codes” to get results like the following:

```
\begin{CCSXML}
<ccs2012>
<concept>
<concept_id>10010520.10010553.10010562</concept_id>
<concept_desc>Computer systems organization~Embedded systems</concept_desc>
<concept_significance>500</concept_significance>
</concept>
<concept>
<concept_id>10010520.10010575.10010755</concept_id>
<concept_desc>Computer systems organization~Redundancy</concept_desc>
<concept_significance>300</concept_significance>
</concept>
<concept>
<concept_id>10010520.10010553.10010554</concept_id>
<concept_desc>Computer systems organization~Robotics</concept_desc>
<concept_significance>100</concept_significance>
</concept>
```



```

</concept>
<concept>
  <concept_id>10003033.10003083.10003095</concept_id>
  <concept_desc>Networks~Network reliability</concept_desc>
  <concept_significance>100</concept_significance>
</concept>
</ccs2012>
\end{CCSXML}

\ccsdesc[500]{Computer systems organization~Embedded systems}
\ccsdesc[300]{Computer systems organization~Redundancy}
\ccsdesc{Computer systems organization~Robotics}
\ccsdesc[100]{Networks~Network reliability}

```

You just need to copy this code and paste it in your paper anywhere before `\maketitle`.

CCS Concepts and user-defined keywords are required for all articles over two pages in length, and are optional for one- and two-page articles (or abstracts).

`\setcopyright` There are several possibilities for the copyright of the papers published by the ACM: the authors may transfer the rights to the ACM, license them to the ACM, some or all authors might be employees of the US or Canadian governments, etc. Accordingly the command `\setcopyright{...}` is introduced. Its argument is the copyright status of the paper, for example, `\setcopyright{acmcopyright}`. The possible values for this command are listed in Table 3. This command must be placed in the preamble, before `\begin{document}`.

The ACM submission software should generate the right command for you to paste into your file.

`\copyrightyear` Each copyright statement must have the year of copyright. By default it is the same as `\acmYear`, but you can override this using the macro `\copyrightyear`, e.g.,

```

\acmYear{2016}
\copyrightyear{2015}

```

There is a special case for a personal copy that the authors may be allowed to generate for their use or a posting on a personal site (check the instructions for the specific journal or conference for the details). The document option `authorversion=true` produces a special form of the copyright statement for this case. Note that you still need the `\setcopyright` command and (optionally) `\copyrightyear` command to tell \TeX about the copyright owner and year. Also, you should be aware that due to the different sizes of the permission blocks for the printed version and authors' version, the page breaks might be different between them.

`abstract` The environment `abstract` must *precede* the `\maketitle` command. Again, this is different from the standard \LaTeX . Putting `abstract` after `\maketitle` will trigger an error.

`teaserfigure` A special kind of figure is used for many two-column conference proceedings.

Table 3: Parameters for the `\setcopyright` command

Parameter	Meaning
<code>none</code>	The copyright and permission information is not typeset. (This is the option for some ACM conferences.)
<code>acmcopyright</code>	The authors transfer the copyright to the ACM (the “traditional” choice).
<code>acmlicensed</code>	The authors retain the copyright but license the publication rights to ACM.
<code>rightsretained</code>	The authors retain the copyright and publication rights to themselves or somebody else.
<code>usgov</code>	All the authors are employees of the US government.
<code>usgovmixed</code>	Some authors are employees of the US government.
<code>cagov</code>	All the authors are employees of the Canadian government.
<code>cagovmixed</code>	Some authors are employees of the Canadian government.
<code>licensedusgovmixed</code>	Some authors are employees of the US government, and the publication rights are licensed to ACM.
<code>licensedcagov</code>	All the authors are employees of the Canadian government, and the publication rights are licensed to ACM.
<code>licensedcagovmixed</code>	Some authors are employees of the Canadian government, and the publication rights are licensed to ACM.
<code>othergov</code>	Authors are employees of a government other than the US or Canada.
<code>licensedothergov</code>	Authors are employees of a government other than the US or Canada, and the publication rights are licensed to ACM.
<code>iw3c2w3</code>	Special statement for conferences organized by IW3C2.
<code>iw3c2w3g</code>	Special statement for conferences organized by IW3C2, when some authors are approved Google employees.

Table 4: Settings for the `\settopmatter` command

Parameter	Values	Meaning
<code>printccs</code>	true/false	Whether to print CCS categories
<code>printacmref</code>	true/false	Whether to print the ACM bibliographic entry
<code>printfolios</code>	true/false	Whether to print page numbers (folios)
<code>authorsperrow</code>	numeric	Number of authors per row for the title page in conference proceedings formats

This figure is placed just after the authors but before the main text. The environment `teaserfigure` is used for these figures. This environment must be used *before* `\maketitle`, for example,

```
\begin{teaserfigure}
  \includegraphics[width=\textwidth]{sampleteaser}
  \caption{This is a teaser}
  \label{fig:teaser}
\end{teaserfigure}
```

`\settopmatter` Some information in the top matter is printed for certain journals or proceedings and suppressed for others. You can override these defaults using the command `\settopmatter{<settings>}`. The settings and their meanings are listed in Table 4. For example,

```
\settopmatter{printacmref=false, printccs=true, printfolios=true}
```

The parameter `authorsperrow` requires some explanation. In conference proceedings authors' information is typeset in boxes, several boxes per row (see `sample-sigconf.pdf`, `sample-sigplan.pdf`, etc.). The number of boxes per row is determined automatically. If you want to override this, you can do it using this parameter, for example,

```
\settopmatter{authorsperrow=4}
```

However, in most cases you should *not* do this and should use the default settings. Setting `authorsperrow` to 0 will revert it to the default settings.

The parameter `printacmref` specifies whether to print the ACM bibliographic entry (default), or not. Note that this entry is required for all articles over one page in length, and is optional for one-page articles (abstracts).

`\received` The command `\received[<stage>]{<date>}` sets the history of the publication. The `[<stage>]` argument is optional; the default is Received for the first date and revised for the subsequent ones. For example,

```
\received{February 2007}
\received[revised]{March 2009}
\received[accepted]{June 2009}
```

`\maketitle` The macro `\maketitle` must be the last command in the top-matter group. That is it must follow the commands defined in this section.

`\shortauthors` *After* the command `\maketitle`, the macro `\shortauthors` stores the names of the authors for the running head. You can redefine it if the list of author's name is too long, e.g.,

```

\maketitle
\renewcommand{\shortauthors}{Zhou et al.}

```

2.4 Algorithms

There are now several good packages for typesetting algorithms [3, 4, 5], and the authors are free to choose their favorite one.

2.5 Figures and tables

The new ACM styles use the standard \LaTeX interface for figures and tables. There are some important items to be aware of, however.

1. The captions for figures must be entered *after* the figure bodies and for tables *before* the table bodies.
2. The ACM uses the standard types for figures and tables and adds several new ones. In total there are the following types:

figure, table: a standard figure or table taking a full text width in one-column formats and one column width in two-column formats.

figure*, table* in two-column formats, a special figure or table taking a full text width.

teaserfigure: a special figure before `\maketitle`.

sidebar, marginfigure, margintable: in the sigchi-a format, special sidebars, tables and figures in the margin.

3. Accordingly, when scaling images, one should use the following sizes:
 - (a) For `teaserfigure`, `figure` in one-column mode or `figure*` in two-column mode, use `\textwidth`. In one-column mode, you can also use `\columnwidth`, which coincides with `\textwidth` in this case.
 - (b) For `figure` in two-column mode, use `\columnwidth`.
 - (c) For `marginfigure`, use `\marginparwidth`.
 - (d) For `figure*` in SIGCHI extended abstracts, use `\fulltextwidth`.

It is strongly recommended to use the package `booktabs` [6] and follow its main principles of typography with respect to tables:

1. Never, ever use vertical rules.

2. Never use double rules.

It is also a good idea not to overuse horizontal rules.

For table *footnotes* you have several options described in the TeX FAQ [1]. The simplest one is to use a `\minipage` environment:

```
\begin{table}
\caption{Simulation Configuration}
\label{tab:conf}
\begin{minipage}{\columnwidth}
\begin{center}
\begin{tabular}{ll}
\toprule
TERRAIN\footnote{This is a table footnote. This is a
    table footnote. This is a table footnote.} &
(200\,m$\times$200\,m) Square\\
Node Number & 289\\
Node Placement & Uniform\\
Application & Many-to-Many/Gossip CBR Streams\\
Payload Size & 32 bytes\\
Routing Layer & GF\\
MAC Layer & CSMA/MMSN\\
Radio Layer & RADIO-ACCNOISE\\
Radio Bandwidth & 250Kbps\\
Radio Range & 20m--45m\\
\bottomrule
\end{tabular}
\end{center}
\bigskip
\footnotesize\emph{Source:} This is a table
sourcenote. This is a table sourcenote. This is a table
sourcenote.

\emph{Note:} This is a table footnote.
\end{minipage}
\end{table}
```

sidebar
marginfigure
margintable

SIGCHI extended abstracts use margin space extensively. This package provides three environments for this with optional captions:

sidebar: textual information in the margin

marginfigure: a figure in the margin

margintable: a table in the margin

Tables and figures (including margin tables and margin figures) are by default centered. However, in some cases (for example, when you use several subimages per figure) you may need to override this. A good way to do so is to put the contents into a `\minipage` of the width `\columnwidth`.

2.6 Descriptions of images

`\Description` Some readers of ACM publications might be visually challenged. These readers might use a voice-over software to read aloud the papers. It is important to provide them a description of each image used in the paper.

The command `\Description[<short description>]{<long description>}` should be placed inside every figure, `teaserfigure` or `marginfigure` environment to provide a description of the image(s) used in the figure. Unlike `\caption`, which is used alongside the image, `\Description` is intended to be used instead of the image, for example,

```
\begin{figure}
  \centering
  \includegraphics{voltage}
  \Description{A bell-like histogram centered at $0.5\text{~V}$ with most
    measurements between $0.2\text{~V}$ and $0.8\text{~V}$}
  \caption{Histogram of the measurements of voltage}
  \label{fig:voltage}
\end{figure}
```

At present the lack of descriptions generates a warning at compilation.

2.7 Theorems

The ACM classes define two theorem styles and several pre-defined theorem environments:

acmplain: this is the style used for theorem, conjecture, proposition, lemma and corollary, and

acmdefinition: this is the style used for example and definition.

These environments are defined by default. In the unusual circumstance that a user does not wish to have these environments defined, the option `acmthm=false` in the preamble will suppress them.

2.8 Online-only and offline-only material

`printonly` Some supplementary material in ACM publications is put online but not in the printed version. The text inside the environment `screenonly` will be typeset only when the option `screen` (see Section 2.2) is set to true. Conversely, the text inside the environment `printonly` is typeset only when this option is set to false. For example,

```
\section{Supplementary materials}

\begin{printonly}
  Supplementary materials are available in the online version of this paper.
\end{printonly}

\begin{screenonly}
```

```
(The actual supplementary materials.)
\end{screenonly}
```

We use the `comment` package for typesetting this code, so `\begin` and `\end` should start on a line of their own with no leading or trailing spaces.

2.9 Note about anonymous mode

`anonsuppress` When the option `anonymous` is selected, \TeX suppresses author information (including the number of authors) for a blind review. However, sometimes the information identifying the authors may be present in the body of the paper. For example,

```
\begin{anonsuppress}
  This is the continuation of the previous work by the author
  \cite{prev1, prev2}.
\end{anonsuppress}
```

As for the `printonly` and `screenonly` environments, `\begin{anonsuppress}` and `\end{anonsuppress}` should start on a line of their own with no leading or trailing spaces.

2.10 Acknowledgments

The traditional “Acknowledgments” section is conventionally used to thank persons and granting agencies for their help and support. However, there are several important considerations about this section.

First, in anonymous mode this section must be omitted: it gives too much information to reviewers. Second, data about grants is extracted and stored separately by the postprocessing software. ACM classes provide facilities for both these tasks.

`acks` The environment `acks` starts an unnumbered section “Acknowledgments” unless the anonymous mode is chosen. Put all thanks inside this environment.

As for the `printonly` and `screenonly` environments, `\begin{acks}` and `\end{acks}` should start on a line of their own with no leading or trailing spaces.

`\grantsponsor` All financial support *must* be listed using the commands `\grantsponsor` and
`\grantnum` `\grantnum`. These commands tell the postprocessing software about the granting organization and grant. The format of these commands is the following:

```
\grantsponsor{\sponsorID}{\name}{\url}
\grantnum[\url]{\sponsorID}{\number}.
```

Here `{\sponsorID}` is the unique ID used to match grants to sponsors, `{\name}` is the name of the sponsor, `{\url}` is its URL, and `{\number}` is the grant number. The `{\sponsorID}` of the `\grantnum` command must correspond to the `{\sponsorID}` of a `\grantsponsor` command. Some awards have their own web pages, which you can include using the optional argument of the `\grantnum` command.

At present $\{\langle sponsorID \rangle\}$ is chosen by the authors and can be an arbitrary key in the same way the label of a `\cite` is arbitrarily chosen. There might be a change to this policy if the ACM decides to create a global database of sponsoring organizations.

Example:

```
\begin{acks}
  The authors would like to thank Dr. Yuhua Li for providing the
  matlab code of the \textit{BEPS} method.

  The authors would also like to thank the anonymous referees for
  their valuable comments and helpful suggestions. This work is
  supported by the \grantsponsor{GS501100001809}{National Natural
  Science Foundation of
  China}{https://doi.org/10.13039/501100001809} under Grant
  No.:~\grantnum{GS501100001809}{61273304}
  and~\grantnum[http://www.nnsf.cn/youngscientists]{GS501100001809}{Young
  Scientists' Support Program}.
\end{acks}
```

2.11 Bibliography

The ACM uses the `natbib` package for formatting references and the `BibTeX` style file `ACM-Reference-Format.bst` for `BibTeX` processing. You can disable loading of `natbib` using the option `natbib=false` in `\documentclass`. However, it is not recommended, as well as the use of `BibTeX` styles other than `ACM-Reference-Format.bst`, and may delay the processing of the manuscript.

`\citestyle` If you use `natbib`, you can select one of two predefined citation styles using the command `\citestyle`: the author-year format `acmauthoryear` or the numeric format `acmnumeric`. For example,

```
\citestyle{acmauthoryear}
```

Note that numeric citations are the default mode for most formats.

`\setcitestyle` You can further customize `natbib` using the `\setcitestyle` command, for example,

```
\setcitestyle{numbers,sort&compress}
```

One of the more common versions is

```
\setcitestyle{nosort}
```

It is useful if you do not like the way `natbib` sorts citation lists.

If you use `natbib`, then commands like `\citep` and `\citeauthor` are automatically supported. The command `\shortcite` is the same as `\cite` in numerical mode and cites the year in author-date mode.

Note that before version 1.48 the command `\citeyear` put the year in parentheses. In version 1.48 and later it produces just the year; the command `\citeyearpar` can be used to emulate its old behavior.

There are several customized BibTeX entry types and fields in the ACM style file `ACM-Reference-Format.bst` that you may want to be aware of.

The style supports the fields `doi` and `url`, for example,

```
doi = "10.1145/1188913.1188915",
url = "http://ccrma.stanford.edu/~jos/bayes/bayes.pdf",
```

The style supports the arXiv-recommended fields `eprint` and (optionally) `primaryclass`, for example,

```
eprint = "960935712",
primaryclass = "cs",
```

See the examples at <http://arxiv.org/hypertex/bibstyles/>.

There are several special entry types. Types `online` and `game` are used for Web pages and games, for example,

```
@online{Thornburg01,
  author = "Harry Thornburg",
  year = "2001",
  title = "Introduction to Bayesian Statistics",
  url = "http://ccrma.stanford.edu/~jos/bayes/bayes.html",
  month = mar,
  lastaccessed = "March 2, 2005",
}
```

Entry types `artifactsoftware`, `artifactdataset` (with synonyms `software` and `dataset`) can be used to cite software artifacts and datasets, for example,

```
@ArtifactSoftware{R,
  title = {R: A Language and Environment for Statistical Computing},
  author = {{R Core Team}},
  organization = {R Foundation for Statistical Computing},
  address = {Vienna, Austria},
  year = {2019},
  url = {https://www.R-project.org/},
}
@ArtifactDataset{UMassCitations,
  author = {Sam Anzaroot and Andrew McCallum},
  title = {{UMass} Citation Field Extraction Dataset},
  year = 2013,
  url =
    {http://www.iesl.cs.umass.edu/data/data-umasscitationfield},
  lastaccessed = {May 27, 2019}
}
```

For these entry types you can use the `lastaccessed` field to add the access date for the URL.

There are two ways to enter video or audio sources in the bibliography corresponding to two different possibilities. For standalone sources available online, you can use an online entry and set its `howpublished` field. For example,

```
@online{Obama08,
  author =      "Barack Obama",
  year   =      "2008",
  title   =      "A more perfect union",
  howpublished = "Video",
  day    =      "5",
  url     =      "http://video.google.com/videoplay?docid=6528042696351994555",
  month   =      mar,
  lastaccessed = "March 21, 2008",
}
```

For sources available as attachments to conference proceedings and similar documents, you can use the usual `inproceedings` entry type and set its `howpublished` field:

```
@Inproceedings{Novak03,
  author =      "Dave Novak",
  title   =      "Solder man",
  booktitle =   "ACM SIGGRAPH 2003 Video Review on Animation theater Program",
  year    =      "2003",
  publisher =    "ACM Press",
  address  =      "New York, NY",
  pages    =      "4",
  month    =      "March 21, 2008",
  doi      =      "10.9999/woot07-S422",
  howpublished = "Video",
}
```

Sometimes you need to cite a complete issue of a journal. The periodical entry type is intended for this:

```
@periodical{JCohen96,
  key =      "Cohen",
  editor =    "Jacques Cohen",
  title =     "Special issue: Digital Libraries",
  journal =   "Communications of the {ACM}",
  volume =    "39",
  number =    "11",
  month =     nov,
  year =      "1996",
}
```

If you do not know the year of publication, the style will add “[n. d.]” (for “no date”) to the entry.

If you do not know the author (this is often the case for online entries), use the key field to add a key for sorting and citations, for example,

```
@online{TUGInstmem,
  key =      {TUG},
  year =      2017,
  title =     "Institutional members of the {\TeX} Users Group",
  url =       "http://wwtug.org/instmem.html",
  lastaccessed = "May 27, 2017",
}
```

A note about sorting. The current ACM bibliography styles always sort the entries according to authors names and publication year. There is a controversy about sorting names with “von” or “van” part: should Ludwig van Beethoven be sorted under “V” or under “B”? The American practice is to use “van” in sorting, i.e. to file van Beethoven under “V”. However, some authorities recommend to sort Dutch persons according to their last names (see e.g. https://www.ifla.org/files/assets/cataloguing/pubs/names-of-persons_1996.pdf). While I do not want to take a part in this dispute, I would like to point to the old “noopsort” trick by Oren Patashnik. Add to the .bib file the line

```
@PREAMBLE{"\providecommand{\noopsort}[1]{}"}
```

and then encode the author as

```
author = {Ludwig {\noopsort{Beethoven}}van Beethoven},
```

This will make the author to be sorted as “Beethoven” rather than “van Beethoven”.

2.12 Colors

While printed ACM publications are usually black and white, screen mode allows the use of colors. The ACM classes pre-define several colors according to [7]: ACMBBlue, ACMYellow, ACMOrange, ACMRed, ACMLightBlue, ACMGreen, ACMPurple and ACMDarkBlue. You can use them in color assignments.

The ACM provides the following recommendation on color use.

The most accessible approach would be to ensure that your article is still readable when printed in greyscale. The most notable reasons for this are:

1. The most common type of inherited Color Vision Deficiency (CVD) is red-green (in which similar-brightness colors that differ only in their amounts of red or green are often confused), and it affects up to 8% of males and 0.5% of females of Northern European descent.
2. The most common type of acquired Color Vision Deficiency (CVD) is blue-yellow (including mild cases for many older adults).

3. Most printing is in black and white.
4. Situational impairments (e.g., bright sunlight shining on a mobile screen) tend to reduce the entire color gamut, reducing color discriminability.

Note: It is *not* safe to encode information using only variations in color (i.e., only differences in hue and/or saturation) as there is bound to be someone affected!

To ensure that you are using the most accessible colors, the ACM recommends that you choose sets of colors to help ensure suitable variations in when printed in greyscale by using either of the following tools:

1. ColourBrewer: <http://colorbrewer2.org/>
2. ACE: The Accessible Colour Evaluator: <http://daprlab.com/ace/> for designing WCAG 2.0 compliant palettes.

2.13 Other notable packages and typographic remarks

Several other packages are recommended for specialized tasks.

The package `subcaption` [8] is recommended for complex figures with several subplots or subfigures that require separate subcaptioning. The packages `nomencl` [9] and `glossaries` [10] can be used for the automatic creation of the lists of symbols and concepts used.

By default `acmart` prevents all widows and orphans (i.e., lonely lines at the beginning or end of the page) and hyphenation at the end of the page. This is done by the rather strict settings

```
\widowpenalty=10000
\clubpenalty=10000
\brokenpenalty=10000
```

However, this may lead to frustrating results when the authors must obey a page limit. Setting these penalties to smaller values may help if you absolutely need to.

Another problem might be the too strict line breaking rules. Again, a strategically placed `\sloppy` command or putting the problematic paragraph inside `sloppypar` environment might help—but beware, the results might be, well, sloppy.

Note that the uppercasing in section titles is done using the `textcase` package [11], so the command `\NoCaseChange` inside the title may help to prevent extraneous uppercasing.

2.14 Disabled or forbidden commands

The goal of `acmart` package is to provide a uniform look and feel for ACM publications. Accordingly, a number of commands is forbidden or disabled in `acmart`.

You may *not* put several authors or several e-mails into a `\author` or `\email` command. This may lead to errors or warning.

You cannot change `\baselinestretch` in your document: this produces an error.

You should not abuse the command `\vspace`: this command may disturb the type-setting of ACM papers.

2.15 A note for wizards: `acmart-preload-hook.tex`

Sometimes you need to change the behavior of `acmart`. The usual way to do this is to redefine commands in the preamble. However, these definitions are executed *after* `acmart` is loaded and certain decisions are made. This presents a number of problems.

For example, one may want to use the `titletoc` package with `acmart`. This package should be loaded before `hyperref`. However, since `acmart` loads `hyperref` itself, the line `\usepackage{titletoc}` in the preamble will lead to grief (see <http://tex.stackexchange.com/questions/357265/using-titletoc-with-acm-acmart-style>).

Another example is passing options to a package. Suppose you want to use the `dvipsnames` option of the `xcolor` package. Normally you cannot do this because `acmart` loads this package itself without options.

The file `acmart-preload-hook.tex` can be used to solve these problems. If this file exists, it will be processed before any other package. You can use this file to load packages or pass options to them. For example, if you put in this file

```
\let\LoadClassOrig\LoadClass
\renewcommand\LoadClass[2][\LoadClassOrig[#1]{#2}%
\usepackage{titletoc}}
```

then `titletoc` will be loaded before `hyperref`. If you put in this file

```
\PassOptionsToPackage{dvipsnames}{xcolor}
```

you will pass `dvipsnames` to `xcolor`.

Important note. This hook makes it too easy to create a manuscript that is not acceptable by the ACM. It is even easier to create a file that cannot be compiled. So please do not use it *unless you know what you are doing*. And if you use it, *do not ask for support*. If you decide to use this hook, you are on your own.

2.16 Currently supported publications

Table 5: ACM publications and arguments of the `\acmJournal` command

Abbreviation	Publication
CIE	ACM Computers in Entertainment
CSUR	ACM Computing Surveys
DGOV	Digital Government: Research and Practice
DTRAP	Digital Threats: Research and Practice
HEALTH	ACM Transactions on Computing for Healthcare
IMWUT	PACM on Interactive, Mobile, Wearable and Ubiquitous Technologies
JACM	Journal of the ACM
JDIQ	ACM Journal of Data and Information Quality
JEA	ACM Journal of Experimental Algorithmics
JERIC	ACM Journal of Educational Resources in Computing

Table 5: ACM publications and arguments of the \acmJournal command (continued)

Abbreviation	Publication
JETC	ACM Journal on Emerging Technologies in Computing Systems
JOCCH	ACM Journal on Computing and Cultural Heritage
PACMCGIT	Proceedings of the ACM on Computer Graphics and Interactive Techniques
PACMHCI	PACM on Human-Computer Interaction
PACMPL	PACM on Programming Languages
POMACS	PACM on Measurement and Analysis of Computing Systems
TAAS	ACM Transactions on Autonomous and Adaptive Systems
TACCESS	ACM Transactions on Accessible Computing
TACO	ACM Transactions on Architecture and Code Optimization
TALG	ACM Transactions on Algorithms
TALLIP	ACM Transactions on Asian and Low-Resource Language Information Processing
TAP	ACM Transactions on Applied Perception
TCPS	ACM Transactions on Cyber-Physical Systems
TDS	ACM Transactions on Data Science
TEAC	ACM Transactions on Economics and Computation
TECS	ACM Transactions on Embedded Computing Systems
TELO	ACM Transactions on Evolutionary Learning
THRI	ACM Transactions on Human-Robot Interaction
TIIS	ACM Transactions on Interactive Intelligent Systems
TIOT	ACM Transactions on Internet of Things
TISSEC	ACM Transactions on Information and System Security
TIST	ACM Transactions on Intelligent Systems and Technology
TKDD	ACM Transactions on Knowledge Discovery from Data
TMIS	ACM Transactions on Management Information Systems
TOCE	ACM Transactions on Computing Education
TOCHI	ACM Transactions on Computer-Human Interaction
TOCL	ACM Transactions on Computational Logic
TOCS	ACM Transactions on Computer Systems
TOCT	ACM Transactions on Computation Theory
TODAES	ACM Transactions on Design Automation of Electronic Systems
TODS	ACM Transactions on Database Systems
TOG	ACM Transactions on Graphics
TOIS	ACM Transactions on Information Systems
TOIT	ACM Transactions on Internet Technology
TOMACS	ACM Transactions on Modeling and Computer Simulation
TOMM	ACM Transactions on Multimedia Computing, Communications and Applications
TOMPECS	ACM Transactions on Modeling and Performance Evaluation of Computing Systems
TOMS	ACM Transactions on Mathematical Software

Table 5: ACM publications and arguments of the \acmJournal command (continued)

Abbreviation	Publication
TOPC	ACM Transactions on Parallel Computing
TOPLAS	ACM Transactions on Programming Languages and Systems
TOPS	ACM Transactions on Privacy and Security
TOS	ACM Transactions on Storage
TOSEM	ACM Transactions on Software Engineering and Methodology
TOSN	ACM Transactions on Sensor Networks
TQC	ACM Transactions on Quantum Computing
TRETS	ACM Transactions on Reconfigurable Technology and Systems
TSAS	ACM Transactions on Spatial Algorithms and Systems
TSC	ACM Transactions on Social Computing
TSLP	ACM Transactions on Speech and Language Processing
TWEB	ACM Transactions on the Web

Besides the publications listed in Table 5, there is a special “publication” type FACMP, a forthcoming ACM publication, reserved for new journals which are not assigned an ISSN yet.

3 Implementation

3.1 Identification

We start with a declaration of who we are. Most .dtx files put driver code in a separate .drv driver file. We roll this code into the main file and use the pseudo-guard <gobble> for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 <*gobble>
3 \ProvidesFile{acmart.dtx}
4 </gobble>
5 <class>\ProvidesClass{acmart}
6 [2020/02/08 v1.69 Typesetting articles for the Association for Computing Machinery]
```

And the driver code:

```
7 <*gobble>
8 \documentclass{ltxdoc}
9 \usepackage{array,booktabs,amsmath,graphicx,fancyvrb,tabularx, longtable}
10 \usepackage[tt=false, type1=true]{libertine}
11 \usepackage[varqu]{zi4}
12 \usepackage[libertine]{newtxmath}
13 \usepackage[tableposition=top]{caption}
14 \usepackage{hypdoc}
15 \PageIndex
16 \CodelineIndex
17 \RecordChanges
18 \EnableCrossrefs
19 \begin{document}
20   \DocInput{acmart.dtx}
21 \end{document}
22 </gobble>
23 <*class>
24 \def\@classname{acmart}
```

3.2 Preload hook

We preload acmart-preload-hook:

```
25 \InputIfFileExists{acmart-preload-hook.tex}{%
26   \ClassWarning{\@classname}{%
27     I am loading acmart-preload-hook.tex. You are fully responsible
28     for any problems from now on.}}{}
```

3.3 Options

We need xkeyval since some of our options may have values:

```
29 \RequirePackage{xkeyval}
```

We use xstring to check whether user input is valid

```
30 \RequirePackage{xstring}
```


format The possible formats

```
31 \define@choicekey*+{acmart.cls}{format}[\ACM@format\ACM@format@nr]{%
32 manuscript, acmsmall, acmlarge, acmtog, sigconf, siggraph,
33 sigplan, sigchi, sigchi-a}[manuscript]{}{%
34 \ClassError{\@classname}{The option format must be manuscript,
35 acmsmall, acmlarge, acmtog, sigconf, siggraph,
36 sigplan, sigchi or sigchi-a}}
37 \def\@DeclareACMFormat#1{\DeclareOptionX{#1}{\setkeys{acmart.cls}{format=#1}}}
38 \@DeclareACMFormat{manuscript}
39 \@DeclareACMFormat{acmsmall}
40 \@DeclareACMFormat{acmlarge}
41 \@DeclareACMFormat{acmtog}
42 \@DeclareACMFormat{sigconf}
43 \@DeclareACMFormat{siggraph}
44 \@DeclareACMFormat{sigplan}
45 \@DeclareACMFormat{sigchi}
46 \@DeclareACMFormat{sigchi-a}
47 \ExecuteOptionsX{format}
```

\if@ACM@screen Whether we use screen mode

```
48 \define@boolkey+{acmart.cls}[@ACM@]{screen}[true]{%
49 \if@ACM@screen
50 \PackageInfo{\@classname}{Using screen mode}%
51 \else
52 \PackageInfo{\@classname}{Not using screen mode}%
53 \fi}{\PackageError{\@classname}{The option screen can be either true or
54 false}}
55 \ExecuteOptionsX{screen=false}
```

\if@ACM@urlbreakonhyphens

```
56 \define@boolkey+{acmart.cls}[@ACM@]{urlbreakonhyphens}[true]{%
57 \if@ACM@urlbreakonhyphens
58 \PackageInfo{\@classname}{Using breaking urls on hyphens}%
59 \else
60 \PackageInfo{\@classname}{Not breaking urls on hyphens}%
61 \fi}{\PackageError{\@classname}{The option urlbreakonhyphens can be either true or
62 false}}
63 \ExecuteOptionsX{urlbreakonhyphens=true}
```

\if@ACM@acmthm Whether we define theorem-like environments.

```
64 \define@boolkey+{acmart.cls}[@ACM@]{acmthm}[true]{%
65 \if@ACM@acmthm
66 \PackageInfo{\@classname}{Requiring acmthm}%
67 \else
68 \PackageInfo{\@classname}{Suppressing acmthm}%
69 \fi}{\PackageError{\@classname}{The option acmthm can be either true or
70 false}}
71 \ExecuteOptionsX{acmthm=true}
```

`\if@ACM@review` Whether we use review mode

```

72 \define@boolkey+{acmart.cls}[@ACM@]{review}[true]{%
73   \if@ACM@review
74     \PackageInfo{\@classname}{Using review mode}%
75     \AtBeginDocument{\@ACM@printfoliostrue}%
76   \else
77     \PackageInfo{\@classname}{Not using review mode}%
78   \fi}{\PackageError{\@classname}{The option review can be either true or
79     false}}
80 \ExecuteOptionsX{review=false}

```

`\if@ACM@authorversion` Whether we use author's-version mode

```

81 \define@boolkey+{acmart.cls}[@ACM@]{authorversion}[true]{%
82   \if@ACM@authorversion
83     \PackageInfo{\@classname}{Using authorversion mode}%
84   \else
85     \PackageInfo{\@classname}{Not using authorversion mode}%
86   \fi}{\PackageError{\@classname}{The option authorversion can be either true or
87     false}}
88 \ExecuteOptionsX{authorversion=false}

```

`\if@ACM@nonacm` Special option for non-ACM publications using the ACM typesetting options.

```

89 \define@boolkey+{acmart.cls}[@ACM@]{nonacm}[true]{%
90   \if@ACM@nonacm
91     \PackageInfo{\@classname}{Using nonacm mode}%
92     \AtBeginDocument{\@ACM@printacmreffalse}%
93     % in 'nonacm' mode we disable the "ACM Reference Format"
94     % printing by default, but this can be re-enabled by the
95     % user using \settopmatter{printacmref=true}
96   \else
97     \PackageInfo{\@classname}{Not using nonacm mode}%
98   \fi}{\PackageError{\@classname}{The option nonacm can be either true or
99     false}}
100 \ExecuteOptionsX{nonacm=false}

```

`\if@ACM@balance` Whether to balance the last page

```

101 \define@boolkey+{acmart.cls}[@ACM@]{balance}[true]{}%
102 \PackageError{\@classname}{The option balance can be either true or
103   false}}
104 \ExecuteOptionsX{balance}

```

`\if@ACM@natbib@override` This macro is no longer used.

`\if@ACM@natbib` Whether we use natbib mode

```

105 \define@boolkey+{acmart.cls}[@ACM@]{natbib}[true]{%
106   \if@ACM@natbib
107     \PackageInfo{\@classname}{Explicitly selecting natbib mode}%
108   \else
109     \PackageInfo{\@classname}{Explicitly deselecting natbib mode}%

```

```

110 \fi}{\PackageError{\@classname}{The option natbib can be either true or
111     false}}
112 \ExecuteOptionsX{natbib=true}

\if@ACM@anonymous Whether we use anonymous mode
113 \define@boolkey+{acmart.cls}{@ACM@}{anonymous}[true]{%
114     \if@ACM@anonymous
115         \PackageInfo{\@classname}{Using anonymous mode}%
116     \else
117         \PackageInfo{\@classname}{Not using anonymous mode}%
118     \fi}{\PackageError{\@classname}{The option anonymous can be either true or
119         false}}
120 \ExecuteOptionsX{anonymous=false}

\if@ACM@timestamp Whether we use timestamp mode
121 \define@boolkey+{acmart.cls}{@ACM@}{timestamp}[true]{%
122     \if@ACM@timestamp
123         \PackageInfo{\@classname}{Using timestamp mode}%
124     \else
125         \PackageInfo{\@classname}{Not using timestamp mode}%
126     \fi}{\PackageError{\@classname}{The option timestamp can be either true or
127         false}}
128 \ExecuteOptionsX{timestamp=false}

\if@ACM@authordraft Whether we use author-draft mode
129 \define@boolkey+{acmart.cls}{@ACM@}{authordraft}[true]{%
130     \if@ACM@authordraft
131         \PackageInfo{\@classname}{Using authordraft mode}%
132         \@ACM@timestamptrue
133         \@ACM@reviewtrue
134     \else
135         \PackageInfo{\@classname}{Not using authordraft mode}%
136     \fi}{\PackageError{\@classname}{The option authordraft can be either true or
137         false}}
138 \ExecuteOptionsX{authordraft=false}

\ACM@fontsize The font size to pass to the base class
139 \def\ACM@fontsize{}
140 \DeclareOptionX{9pt}{\edef\ACM@fontsize{\CurrentOption}}
141 \DeclareOptionX{10pt}{\edef\ACM@fontsize{\CurrentOption}}
142 \DeclareOptionX{11pt}{\edef\ACM@fontsize{\CurrentOption}}
143 \DeclareOptionX{12pt}{\edef\ACM@fontsize{\CurrentOption}}

144 \DeclareOptionX{draft}{\PassOptionsToClass{\CurrentOption}{amsart}}
145 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
146 \ProcessOptionsX
147 \ClassInfo{\@classname}{Using format \ACM@format, number \ACM@format@nr}

```

3.4 Setting switches

<code>\if@ACM@manuscript</code>	Whether we use manuscript mode 148 <code>\newif\if@ACM@manuscript</code>
<code>\if@ACM@journal</code>	There are two kinds of publications: journals and books 149 <code>\newif\if@ACM@journal</code>
<code>\if@ACM@journal@bibstrip</code>	Sometimes ACM wants a journal-like publication to have conference information in the bibstrip and vice versa, so we have an additional switch. 150 <code>\newif\if@ACM@journal@bibstrip</code>
<code>\if@ACM@sigchiamode</code>	The formatting of SIGCHI extended abstracts is quite unusual. We have a special switch for them. 151 <code>\newif\if@ACM@sigchiamode</code>

Setting up switches

```

152 \ifnum\ACM@format@nr=5\relax % siggraph
153   \ClassWarning{\@classname}{The format siggraph is now obsolete.
154     I am switching to sigconf.}
155   \setkeys{acmart.cls}{format=sigconf}
156 \fi
157 \ifnum\ACM@format@nr=0\relax
158   \@ACM@manuscripttrue
159 \else
160   \@ACM@manuscriptfalse
161 \fi
162 \@ACM@sigchiamodefalse
163 \ifcase\ACM@format@nr
164 \relax % manuscript
165   \@ACM@journaltrue
166 \or % acmsmall
167   \@ACM@journaltrue
168 \or % acmlarge
169   \@ACM@journaltrue
170 \or % acmtog
171   \@ACM@journaltrue
172 \or % sigconf
173   \@ACM@journalfalse
174 \or % siggraph
175   \@ACM@journalfalse
176 \or % sigplan
177   \@ACM@journalfalse
178 \or % sigchi
179   \@ACM@journalfalse
180 \or % sigchi-a
181   \@ACM@journalfalse
182   \@ACM@sigchiamodetrue
183 \fi

```

```

184 \if@ACM@journal
185 \@ACM@journal@bibstriptrue
186 \else
187 \@ACM@journal@bibstripfalse
188 \fi

```

3.5 Loading the base class and package

At this point we either have \ACM@fontsize or use defaults

```

189 \ifx\ACM@fontsize\@empty
190 \ifcase\ACM@format@nr
191 \relax % manuscript
192 \def\ACM@fontsize{9pt}%
193 \or % acmsmall
194 \def\ACM@fontsize{10pt}%
195 \or % acmlarge
196 \def\ACM@fontsize{10pt}%
197 \or % acmtog
198 \def\ACM@fontsize{9pt}%
199 \or % sigconf
200 \def\ACM@fontsize{9pt}%
201 \or % siggraph
202 \def\ACM@fontsize{9pt}%
203 \or % sigplan
204 \def\ACM@fontsize{10pt}%
205 \or % sigchi
206 \def\ACM@fontsize{10pt}%
207 \or % sigchi-a
208 \def\ACM@fontsize{10pt}%
209 \fi
210 \fi
211 \ClassInfo{\@classname}{Using fontsize \ACM@fontsize}
212 \LoadClass[\ACM@fontsize, reqno]{amsart}
213 \RequirePackage{microtype}

```

We need etoolbox for delayed code

```
214 \RequirePackage{etoolbox}
```

Booktabs is now the default

```
215 \RequirePackage{booktabs}
```

We need totpages to calculate the number of pages and refcount to use that number

```
216 \RequirePackage{refcount}
217 \RequirePackage{totpages}
```

The \collect@body macro in amsmath is defined using \def. We load environ to access the \long version of this command

```
218 \RequirePackage{environ}
```

We use setspace for double spacing

```
219 \if@ACM@manuscript
220 \RequirePackage{setspace}
221 \onehalfspacing
222 \fi
```

We need textcase for better upcasing

```
223 \RequirePackage{textcase}
```

3.6 Citations

We patch `\setcitestyle` to allow, for example, `\setcitestyle{sort}` and `\setcitestyle{nosort}`. We patch `\citestyle` to warn about undefined citation styles.

```
224 \if@ACM@natbib
225   \RequirePackage{natbib}
226   \renewcommand{\bibsection}{%
227     \section*{\refname}%
228     \phantomsection\addcontentsline{toc}{section}{\refname}%
229   }
230   \renewcommand{\bibfont}{\bibliofont}
231   \renewcommand{\setcitestyle}[1]{
232     \@for\@tempa:=#1\do
233     {\def\@tempb{round}\ifx\@tempa\@tempb
234       \renewcommand\NAT@open{(\}\renewcommand\NAT@close{)}\fi
235     \def\@tempb{square}\ifx\@tempa\@tempb
236       \renewcommand\NAT@open{[\}\renewcommand\NAT@close{]}\fi
237     \def\@tempb{angle}\ifx\@tempa\@tempb
238       \renewcommand\NAT@open{$<$}\renewcommand\NAT@close{$>$}\fi
239     \def\@tempb{curly}\ifx\@tempa\@tempb
240       \renewcommand\NAT@open{\{\}\renewcommand\NAT@close{\}}\fi
241     \def\@tempb{semicolon}\ifx\@tempa\@tempb
242       \renewcommand\NAT@sep{;}\fi
243     \def\@tempb{colon}\ifx\@tempa\@tempb
244       \renewcommand\NAT@sep{;}\fi
245     \def\@tempb{comma}\ifx\@tempa\@tempb
246       \renewcommand\NAT@sep{,}\fi
247     \def\@tempb{authoryear}\ifx\@tempa\@tempb
248       \NAT@numbersfalse\fi
249     \def\@tempb{numbers}\ifx\@tempa\@tempb
250       \NAT@numberstrue\NAT@superfalse\fi
251     \def\@tempb{super}\ifx\@tempa\@tempb
252       \NAT@numberstrue\NAT@supertrue\fi
253     \def\@tempb{nobibstyle}\ifx\@tempa\@tempb
254       \let\bibstyle=\@gobble\fi
255     \def\@tempb{bibstyle}\ifx\@tempa\@tempb
256       \let\bibstyle=\@citestyle\fi
257     \def\@tempb{sort}\ifx\@tempa\@tempb
258       \def\NAT@sort{\@ne}\fi
259     \def\@tempb{nosort}\ifx\@tempa\@tempb
```

```

260 \def\NAT@sort{\z@}\fi
261 \def\@tempb{compress}\ifx\@tempa\@tempb
262 \def\NAT@cmprs{\@ne}\fi
263 \def\@tempb{nocompress}\ifx\@tempa\@tempb
264 \def\NAT@cmprs{\z@}\fi
265 \def\@tempb{sort&compress}\ifx\@tempa\@tempb
266 \def\NAT@sort{\@ne}\def\NAT@cmprs{\@ne}\fi
267 \def\@tempb{mcite}\ifx\@tempa\@tempb
268 \let\NAT@merge\@ne\fi
269 \def\@tempb{merge}\ifx\@tempa\@tempb
270 \ifnum{\NAT@merge<\tw@}{\let\NAT@merge\tw@}\fi
271 \def\@tempb{elide}\ifx\@tempa\@tempb
272 \ifnum{\NAT@merge<\thr@@}{\let\NAT@merge\thr@@}\fi
273 \def\@tempb{longnamesfirst}\ifx\@tempa\@tempb
274 \NAT@longnamestrue\fi
275 \def\@tempb{nonamebreak}\ifx\@tempa\@tempb
276 \def\NAT@nmfmt#1{\mbox{\NAT@up#1}}\fi
277 \expandafter\NAT@find@eq\@tempa=\relax\@nil
278 \if\@tempc\relax\else
279 \expandafter\NAT@rem@eq\@tempc
280 \def\@tempb{open}\ifx\@tempa\@tempb
281 \xdef\NAT@open{\@tempc}\fi
282 \def\@tempb{close}\ifx\@tempa\@tempb
283 \xdef\NAT@close{\@tempc}\fi
284 \def\@tempb{aysep}\ifx\@tempa\@tempb
285 \xdef\NAT@aysep{\@tempc}\fi
286 \def\@tempb{yysep}\ifx\@tempa\@tempb
287 \xdef\NAT@yrsep{\@tempc}\fi
288 \def\@tempb{notesep}\ifx\@tempa\@tempb
289 \xdef\NAT@cmt{\@tempc}\fi
290 \def\@tempb{citesep}\ifx\@tempa\@tempb
291 \xdef\NAT@sep{\@tempc}\fi
292 \fi
293 }%
294 \NAT@@setcites
295 }
296 \renewcommand\citestyle[1]{%
297 \ifcsname bibstyle@#1\endcsname%
298 \csname bibstyle@#1\endcsname\let\bibstyle\@gobble%
299 \else%
300 \@latex@error{Undefined ‘#1’ citestyle}%
301 \fi
302 }%
303 \fi

```

\bibstyle@acmauthoryear The default author-year format:

```

304 \newcommand{\bibstyle@acmauthoryear}{%
305 \setcitestyle{%
306   authoryear,%
307   open={},close={},citesep={;},%

```

```

308     aysep={},yysep={,},%
309     notesep={, }}

```

`\bibstyle@acmnumeric` The default numeric format:

```

310 \newcommand{\bibstyle@acmnumeric}{%
311   \setcitestyle{%
312     numbers,sort&compress,%
313     open={},close={},citesep={,},%
314     notesep={, }}

```

The default is numeric:

```

315 \if@ACM@natbib
316 \citestyle{acmnumeric}
317 \fi

```

`\@startsection` Before we call `hyperref`, we redefine `\startsection` commands to their \LaTeX defaults since the `amsart` ones are too AMS-specific. We need to do this early since we want `hyperref` to have a chance to redefine them again:

```

318 \def\@startsection#1#2#3#4#5#6{%
319   \if@noskipsec \leavevmode \fi
320   \par
321   \@tempskipa #4\relax
322   \@afterindenttrue
323   \ifdim \@tempskipa <\z@
324     \@tempskipa -\@tempskipa \@afterindentfalse
325   \fi
326   \if@nobreak
327     \everypar{}%
328   \else
329     \addpenalty\@secpenalty\addvspace\@tempskipa
330   \fi
331   \ifstar
332     {\@ssect{#3}{#4}{#5}{#6}}%
333     {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}
334 \def\@sect#1#2#3#4#5#6[#7]#8{%
335   \edef\@toclevel{\ifnum#2=\@m 0\else\number#2\fi}%
336   \ifnum #2>\c@secnumdepth
337     \let\@svsec\@empty
338   \else
339     \refstepcounter{#1}%
340     \protected@edef\@svsec{\@secntformat{#1}\relax}%
341   \fi
342   \@tempskipa #5\relax
343   \ifdim \@tempskipa>\z@
344     \begingroup
345       #6{%
346         \@hangfrom{\hskip #3\relax\@svsec}%
347         \interlinepenalty \@M #8\@par}%
348     \endgroup

```



```

349 \csname #1mark\endcsname{#7}%
350 \ifnum #2>\c@secnumdepth \else
351   \@tochangmeasure{\csname the#1\endcsname}%
352 \fi
353 \addcontentsline{toc}{#1}{%
354   \ifnum #2>\c@secnumdepth \else
355     \protect\numberline{\csname the#1\endcsname}%
356   \fi
357   #7}%
358 \else
359   \def\@svsechd{%
360     #6{\hspace #3\relax
361       \@svsec #8}%
362     \csname #1mark\endcsname{#7}%
363     \ifnum #2>\c@secnumdepth \else
364       \@tochangmeasure{\csname the#1\endcsname\space}%
365     \fi
366     \addcontentsline{toc}{#1}{%
367       \ifnum #2>\c@secnumdepth \else
368         \protect\numberline{\csname the#1\endcsname}%
369       \fi
370       #7}}%
371 \fi
372 \@xsect{#5}}
373 \def\@xsect#1{%
374   \@tempskipa #1\relax
375   \ifdim \@tempskipa>\z@
376     \par \nobreak
377     \vskip \@tempskipa
378     \afterheading
379   \else
380     \@nobreakfalse
381     \global\@noskipsectrue
382     \everypar{%
383       \if@noskipsec
384         \global\@noskipsecfalse
385         {\setbox\z@\lastbox}%
386         \clubpenalty\@M
387         \begingroup \@svsechd \endgroup
388         \unskip
389         \@tempskipa #1\relax
390         \hspace -\@tempskipa
391       \else
392         \clubpenalty \@clubpenalty
393       \everypar{}}%
394     \fi}%
395 \fi
396 \ignorespaces}
397 \def\@secntformat#1{\csname the#1\endcsname\quad}
398 \def\@ssect#1#2#3#4#5{%

```

```

399 \@tempskipa #3\relax
400 \ifdim \@tempskipa>\z@
401   \begingroup
402     #4{%
403       \@hangfrom{\hskip #1}%
404       \interlinepenalty \@M #5\@par}%
405   \endgroup
406 \else
407   \def\@svsechd{#4{\hskip #1\relax #5}}%
408 \fi
409 \xsect{#3}}

```

\@startsection The amsart package redefines \@startsection. Here we redefine it again to make the table of contents work.

```

410 \def\@starttoc#1#2{\begingroup\makeatletter
411   \setTrue{#1}%
412   \par\removelastskip\vskip\z@skip
413   \@startsection{section}\@M\z@{\linespacing\@plus\linespacing}%
414     {.5\linespacing}{\centering\contentsnamefont}{#2}%
415   \@input{\jobname.#1}%
416   \if@filesw
417     \xp\newwrite\csname tf@#1\endcsname
418     \immediate\xp\openout\csname tf@#1\endcsname \jobname.#1\relax
419   \fi
420   \global\@nobreakfalse \endgroup
421   \addvspace{32\p@\@plus14\p@}%
422 }

```

\l@section Section spacing is more generous than for amsart

```

423 \def\l@section{\@tocline{1}{0pt}{1pc}{2pc}{}}

```

\l@subsection The spacing in amsart is too large

```

424 \def\l@subsection{\@tocline{2}{0pt}{1pc}{3pc}{}}

```

\l@subsubsection The spacing in amsart is too large

```

425 \def\l@subsubsection{\@tocline{2}{0pt}{1pc}{5pc}{}}

```

We need to define footnote-related stuff before the call to hyperref (Ross Moore)

\@makefnmark We do not use indentation for footnotes

```

426 \def\@makefnmark{\noindent\@makefnmark}

```

\@footnotetext In sigchi-a mode our footnotes are in the margin!

```

427 \if@ACM@sigchiamode
428 \long\def\@footnotetext#1{\marginpar{%
429   \reset@font\small
430   \interlinepenalty\interfootnotelinepenalty
431   \protected@edef\@currentlabel{%
432     \csname p@footnote\endcsname\@thefnmark

```

```

433 }%
434 \color@begingroup
435 \makefnmark{\rule{z}{\footnotesep\ignorespaces#1}\finalstrut\strutbox}%
436 \color@endgroup}}%
437 \fi

```

`\mpfootnotetext` We want the footnotes in minipages centered:

```

439 \long\def\mpfootnotetext#1{%
440 \global\setbox\mpfootins\vbox{%
441 \unvbox\mpfootins
442 \reset@font\footnotesize
443 \hsize\columnwidth
444 \@parboxrestore
445 \protected@edef\currentlabel
446 {\csname p\mpfootnote\endcsname\@thefnmark}%
447 \color@begingroup\centering
448 \makefnmark{\rule{z}{\footnotesep\ignorespaces#1}\finalstrut\strutbox}%
449 \color@endgroup}}
450

```

`\makefnmark` AMS classes use a buggy definition of `\makefnmark`. We revert to the standard one.

```

451 \def\makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}

```

And now, `hyperref`

```

452 \let\@footnotemark@nolink\@footnotemark
453 \let\@footnotetext@nolink\@footnotetext
454 \RequirePackage[bookmarksnumbered,unicode]{hyperref}
455 \pdfstringdefDisableCommands{%
456 \def\addtocounter#1#2{}%
457 \def\unskip{}%
458 \def\textbullet{- }%
459 \def\textrightarrow{-> }%
460 \def\footnotemark{}%
461 }
462 \urlstyle{rm}
463 \ifcase\ACM@format@nr
464 \relax % manuscript
465 \or % acmsmall
466 \or % acmlarge
467 \or % acmtog
468 \or % sigconf
469 \or % siggraph
470 \or % sigplan
471 \urlstyle{sf}
472 \or % sigchi
473 \or % sigchi-a
474 \urlstyle{sf}
475 \fi

```

```

476 \AtEndPreamble{%
477   \if@ACM@urlbreakonhyphens
478     \def\do@url@hyp{\do\~}%
479   \fi
480   \if@ACM@screen
481     \hypersetup{colorlinks,
482       linkcolor=ACMPurple,
483       citecolor=ACMPurple,
484       urlcolor=ACMDarkBlue,
485       filecolor=ACMDarkBlue}
486   \else
487     \hypersetup{hidelinks}
488   \fi
489   \hypersetup{pdflang={en},
490     pdfdisplaydoctitle}}

```

Bibliography mangling.

```

491 \if@ACM@natbib
492   \let\citeN\cite
493   \let\cite\citep
494   \let\citeANP\citeauthor
495   \let\citeNN\citeyearpar
496   \let\citeyearNP\citeyear
497   \let\citeNP\citealt
498   \DeclareRobustCommand\citeA
499     {\begingroup\NAT@swafalse
500       \let\NAT@ctype\@ne\NAT@partrue\NAT@fullfalse\NAT@open\NAT@citetp}%
501   \providecommand\newblock{}%
502 \else
503   \AtBeginDocument{%
504     \let\shortcite\cite%
505     \providecommand\citename[1]{#1}}
506 \fi
507 \newcommand\shortcite[2][]{%
508   \ifNAT@numbers\cite[#1]{#2}\else\citeyearpar[#1]{#2}\fi}

```

`\bibliographystyle` The `amsart` package redefines `\bibliographystyle` since it prefers the AMS bibliography style. We turn it back to the \LaTeX definition:

```

509 \def\bibliographystyle#1{%
510   \ifx\@begindocumenthook\@undefined\else
511     \expandafter\AtBeginDocument
512   \fi
513   {\if@filesw
514     \immediate\write\@auxout{\string\bibstyle{#1}}%
515   \fi}}

```

Graphics and color.

```

516 \RequirePackage{graphicx}
517 \RequirePackage[prologue]{xcolor}

```

We define ACM colors according to [7]:

```
518 \definecolor[named]{ACMBlue}{cmyk}{1,0.1,0,0.1}
519 \definecolor[named]{ACMYellow}{cmyk}{0,0.16,1,0}
520 \definecolor[named]{ACMOrange}{cmyk}{0,0.42,1,0.01}
521 \definecolor[named]{ACMRed}{cmyk}{0,0.90,0.86,0}
522 \definecolor[named]{ACMLightBlue}{cmyk}{0.49,0.01,0,0}
523 \definecolor[named]{ACMGreen}{cmyk}{0.20,0,1,0.19}
524 \definecolor[named]{ACMPurple}{cmyk}{0.55,1,0,0.15}
525 \definecolor[named]{ACMDarkBlue}{cmyk}{1,0.58,0,0.21}
```

Author-draft mode

```
526 \if@ACM@authordraft
527   \RequirePackage{draftwatermark}
528   \SetWatermarkFontSize{0.5in}
529   \SetWatermarkColor[gray]{.9}
530   \SetWatermarkText{\parbox{12em}{\centering
531     Unpublished working draft.\}
532     Not for distribution.}}
533 \fi
```

3.7 Paper size and paragraphing

We use geometry for dimensions. Note that the present margins do not depend on the font size option—we might need to change this. See <https://github.com/borisveytsman/acmart/issues/5#issuecomment-272881329>.

```
534 \RequirePackage{geometry}
535 \ifcase\ACM@format@nr
536 \relax % manuscript
537   \geometry{letterpaper,head=13pt,
538     marginparwidth=6pc,heightrounded}%
539 \or % acmsmall
540   \geometry{twoside=true,
541     includeheadfoot, head=13pt, foot=2pc,
542     paperwidth=6.75in, paperheight=10in,
543     top=58pt, bottom=44pt, inner=46pt, outer=46pt,
544     marginparwidth=2pc,heightrounded
545   }%
546 \or % acmlarge
547   \geometry{twoside=true, head=13pt, foot=2pc,
548     paperwidth=8.5in, paperheight=11in,
549     includeheadfoot,
550     top=78pt, bottom=114pt, inner=81pt, outer=81pt,
551     marginparwidth=4pc,heightrounded
552   }%
553 \or % acmtog
554   \geometry{twoside=true, head=13pt, foot=2pc,
555     paperwidth=8.5in, paperheight=11in,
556     includeheadfoot, columnsep=24pt,
557     top=52pt, bottom=75pt, inner=52pt, outer=52pt,
```

```

558     marginparwidth=2pc,heightrounded
559 }%
560 \or % sigconf
561 \geometry{twoside=true, head=13pt,
562     paperwidth=8.5in, paperheight=11in,
563     includeheadfoot, columnsep=2pc,
564     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
565     marginparwidth=2pc,heightrounded
566 }%
567 \or % siggraph
568 \geometry{twoside=true, head=13pt,
569     paperwidth=8.5in, paperheight=11in,
570     includeheadfoot, columnsep=2pc,
571     top=57pt, bottom=73pt, inner=54pt, outer=54pt,
572     marginparwidth=2pc,heightrounded
573 }%
574 \or % sigplan
575 \geometry{twoside=true, head=13pt,
576     paperwidth=8.5in, paperheight=11in,
577     includeheadfoot=false, columnsep=2pc,
578     top=1in, bottom=1in, inner=0.75in, outer=0.75in,
579     marginparwidth=2pc,heightrounded
580 }%
581 \or % sigchi
582 \geometry{twoside=true, head=13pt,
583     paperwidth=8.5in, paperheight=11in,
584     includeheadfoot, columnsep=2pc,
585     top=66pt, bottom=73pt, inner=54pt, outer=54pt,
586     marginparwidth=2pc,heightrounded
587 }%
588 \or % sigchi-a
589 \geometry{twoside=false, head=13pt,
590     paperwidth=11in, paperheight=8.5in,
591     includeheadfoot, marginparsep=72pt,
592     marginparwidth=170pt, columnsep=20pt,
593     top=72pt, bottom=72pt, left=314pt, right=72pt
594 }%
595 \@mparswitchfalse
596 \reversemarginpar
597 \fi

\parindent Paragraphing
\parskip 598 \setlength\parindent{10\p@}
599 \setlength\parskip{\z@}
600 \ifcase\ACM@format@nr
601 \relax % manuscript
602 \or % acmsmall
603 \or % acmlarge
604 \or % acmtog
605 \setlength\parindent{9\p@}%

```

```

606 \or % sigconf
607 \or % siggraph
608 \or % sigplan
609 \or % sigchi
610 \or % sigchi-a
611 \fi

```

`\normalparindent` The `amsart` package defines the `\normalparindent` length and initializes it to 12pt (the value of `\parindent` in `amsart`). It is later used to set the `\listparindent` length in the quotation environment and the `\parindent` length in the `\@footnotetext` command. We set `\normalparindent` to the value of `\parindent` as selected by `acmart` for consistent paragraph indents.

```

612 \setlength\normalparindent{\parindent}

```

Footnotes require some consideration. We have several layers of footnotes: front-matter footnotes, “regular” footnotes and the special insert for the bibstrip. In the old ACM classes, the bibstrip was a `\@float`. The problem with floats is that they tend to, well, float—and we want the guarantee they stay.

We use `manyfoot` for layered footnotes instead.

`\copyrightpermissionfootnoterule` This is the footnote rule that separates the bibstrip from the rest of the paper. It is a full width rule.

```

613 \def\copyrightpermissionfootnoterule{\kern-3\p@
614   \hrule \@width \columnwidth \kern 2.6\p@}

615 \RequirePackage{manyfoot}
616 \SelectFootnoteRule[2]{copyrightpermission}
617 \DeclareNewFootnote{authorsaddresses}
618 \SelectFootnoteRule[2]{copyrightpermission}
619 \DeclareNewFootnote{copyrightpermission}

```

`\footnoterule` Tschichold’s rules:

```

620 \def\footnoterule{\kern-3\p@
621   \hrule \@width 4pc \kern 2.6\p@}

```

`\endminipage` We do not use footnote rules in minipages

```

622 \def\endminipage{%
623   \par
624   \unskip
625   \ifvoid\@mpfootins\else
626     \vskip\skip\@mpfootins
627     \normalcolor
628     \unvbox\@mpfootins
629   \fi
630   \@minipagefalse
631   \color@endgroup
632   \egroup
633   \expandafter\@iiparbox\@mpargs{\unvbox\@tempboxa}}

```

\@textbottom Add some stretch according to David Carlisle's advice at <http://tex.stackexchange.com/a/62318/5522>

```
634 \def\@textbottom{\vskip \z@ \@plus 1pt}
635 \let\@texttop\relax
```

In two-column layouts, force both columns to be the same height by inserting extra internal vertical space to fill out the page.

```
636 \ifcase\ACM@format@nr
637 \relax % manuscript
638 \or % acmsmall
639 \or % acmlarge
640 \or % acmtog
641 \flushbottom
642 \or % sigconf
643 \flushbottom
644 \or % siggraph
645 \flushbottom
646 \or % sigplan
647 \flushbottom
648 \or % sigchi
649 \flushbottom
650 \or % sigchi-a
651 \fi
```

3.8 Fonts

Somehow PDFTeX and XeTeX require different incantations to make a PDF compliant with the current Acrobat bugs. Xpdf is much better.

The code below is by Ross Moore.

```
652 \RequirePackage{iftex}
653 \ifPDFTeX
654 \input{glyphtounicode}
655 \pdfglyphtounicode{f_f}{FB00}
656 \pdfglyphtounicode{f_f_i}{FB03}
657 \pdfglyphtounicode{f_f_l}{FB04}
658 \pdfglyphtounicode{f_i}{FB01}
659 \pdfglyphtounicode{t_t}{0074 0074}
660 \pdfglyphtounicode{f_t}{0066 0074}
661 \pdfglyphtounicode{T_h}{0054 0068}
662 \pdfgentounicode=1
663 \fi
664 \RequirePackage{cmap}
```

\if@ACM@newfonts Whether we load the new fonts

```
665 \newif\if@ACM@newfonts
666 \@ACM@newfontstrue
667 \IfFileExists{libertine.sty}{\ClassWarning{\@classname}{You do not
668 have the libertine package installed. Please upgrade your
```



```

669 TeX}\@ACM@newfontsfalse}
670 \IfFileExists{zi4.sty}{\ClassWarning{\@classname}{You do not
671   have the zi4 package installed. Please upgrade your
672   TeX}\@ACM@newfontsfalse}
673 \IfFileExists{newtxmath.sty}{\ClassWarning{\@classname}{You do not
674   have the newtxmath package installed. Please upgrade your
675   TeX}\@ACM@newfontsfalse}

```

We use Libertine throughout.

```

676 \if@ACM@newfonts
677   \RequirePackage[T1]{fontenc}
678 \ifxetex
679   \RequirePackage[tt=false]{libertine}
680   \setmonofont{inconsolata}
681 \else
682   \RequirePackage[tt=false, type1=true]{libertine}
683 \fi
684 \RequirePackage[varqu]{zi4}
685 \RequirePackage[libertine]{newtxmath}
686 \fi

```

`\liningnums` Libertine defines `\liningnums`, which makes `fontspec` unhappy. While we do not use `fontspec`, some users do.

```

687 \let\liningnums\@undefined
688 \AtEndPreamble{%
689   \DeclareTextFontCommand{\liningnums}{\libertineLF}}

```

The SIGCHI extended abstracts are sans serif:

```

690 \if@ACM@sigchiamode
691   \renewcommand{\familydefault}{\sfdefault}
692 \fi

```

3.9 Image descriptions

`\if@Description@present` A local switch: whether there is a description in the given figure

```

693 \newif\if@Description@present
694 \@Description@presenttrue

```

`\if@undescrbed@images` A global switch whether some images were *not* described

```

695 \newif\if@undescrbed@images
696 \@undescrbed@imagesfalse

```

`\Description` The `Description` macro right now just sets switches

```

697 \newcommand\Description[2][\global\@Description@presenttrue\ignorespaces}

```

The global warning

```

698 \AtEndDocument{\if@undescrbed@images
699   \ClassWarningNoLine{\@classname}{Some images may lack descriptions}\fi}

```

Hooks for figures and tables. We also patch algorithm and algorithm* in case somebody uses them.

```

700 \AtBeginEnvironment{figure}{\@Description@presentfalse
701   \let\@vspace\@vspace@orig
702   \let\@vspacer\@vspacer@orig}
703 \AtBeginEnvironment{figure*}{\@Description@presentfalse
704   \let\@vspace\@vspace@orig
705   \let\@vspacer\@vspacer@orig}
706 \AtEndEnvironment{figure}{\if@Description@present\else
707   \global\@undescrbed@imagestrue
708   \ClassWarning{\@classname}{A possible image without description}\fi}
709 \AtEndEnvironment{figure*}{\if@Description@present\else
710   \global\@undescrbed@imagestrue
711   \ClassWarning{\@classname}{A possible image without description}\fi}
712 \AtBeginEnvironment{table}{\let\@vspace\@vspace@orig
713   \let\@vspacer\@vspacer@orig}
714 \AtBeginEnvironment{table*}{\let\@vspace\@vspace@orig
715   \let\@vspacer\@vspacer@orig}
716 \AtBeginEnvironment{algorithm}{\let\@vspace\@vspace@orig
717   \let\@vspacer\@vspacer@orig}
718 \AtBeginEnvironment{algorithm*}{\let\@vspace\@vspace@orig
719   \let\@vspacer\@vspacer@orig}
720 \AtBeginEnvironment{lstlisting}{\let\@vspace\@vspace@orig
721   \let\@vspacer\@vspacer@orig}
722 \AtBeginEnvironment{lstlisting*}{\let\@vspace\@vspace@orig
723   \let\@vspacer\@vspacer@orig}
724

```

3.10 Floats

We use the caption package

```

725 \RequirePackage{caption, float}
726 \captionsetup[table]{position=top}
727 \if@ACM@journal
728   \captionsetup{labelfont={sf, small},
729     textfont={sf, small}, margin=\z@}
730   \captionsetup[figure]{name={Fig.}}
731 \else
732   \captionsetup{labelfont={bf},
733     textfont={bf}, labelsep=colon, margin=\z@}
734   \ifcase\ACM@format@nr
735     \relax % manuscript
736     \or % acmsmall
737     \or % acmlarge
738     \or % acmtog
739     \or % sigconf
740     \or % siggraph
741     \captionsetup{textfont={it}}
742     \or % sigplan

```

```

743 \captionsetup[labelfont={bf},
744   textfont={normalfont}, labelsep=period, margin=\z@]
745 \or % sigchi
746 \captionsetup[figure]{labelfont={bf, small},
747   textfont={bf, small}}
748 \captionsetup[table]{labelfont={bf, small},
749   textfont={bf, small}}
750 \or % sigchi-a
751 \captionsetup[figure]{labelfont={bf, small},
752   textfont={bf, small}}
753 \captionsetup[table]{labelfont={bf, small},
754   textfont={bf, small}}
755 \fi
756 \fi

```

sidebar The sidebar environment:

```

757 \newfloat{sidebar}{}{sbar}
758 \floatname{sidebar}{Sidebar}
759 \renewenvironment{sidebar}{\Collect@Body\@sidebar}{}

```

\@sidebar The processing of the saved text

```

760 \long\def\@sidebar#1{\bgroup\let\@vspace\@vspace@orig
761 \let\@vspacer\@vspacer@orig\captionsetup{type=sidebar}%
762 \marginpar{\small#1}\egroup}

```

marginfigure The marginfigure environment:

```

763 \newenvironment{marginfigure}{\Collect@Body\@marginfigure}{}

```

\@marginfigure The processing of the saved text

```

764 \long\def\@marginfigure#1{\bgroup
765 \let\@vspace\@vspace@orig
766 \let\@vspacer\@vspacer@orig
767 \captionsetup{type=figure}%
768 \marginpar{\@Description@presentfalse\centering
769 \small#1\if@Description@present\else
770 \global\@undescribed@imagestrue
771 \ClassWarning{\@classname}{A possible image without description}
772 \fi}%
773 \egroup}

```

marginable The marginable environment:

```

774 \newenvironment{marginable}{\Collect@Body\@marginable}{}

```

\@marginable The processing of the saved text

```

775 \long\def\@marginable#1{\bgroup\let\@vspace\@vspace@orig
776 \let\@vspacer\@vspacer@orig\captionsetup{type=table}%
777 \marginpar{\centering\small#1}\egroup}

```

SIGCHI extended abstracts provide an interesting possibility to push into the margin. Here we use figure* and table* for this.

`\fulltextwidth` We define the width of the boxes as

```

778 \newdimen\fulltextwidth
779 \fulltextwidth=\dimexpr(\textwidth+\marginparwidth+\marginparsep)

```

`\dblfloat` We redefine the double-float command. First, we make the size bigger. Second, our default position is going to be tp (to give marginalia a chance)

```

780 \if@ACM@sigchiamode
781 \def\@dblfloat{\bgroup\let\@vspace\@vspace@orig
782 \let\@vspacer\@vspacer@orig\columnwidth=\fulltextwidth
783 \let\@endfloatbox\@endwidefloatbox
784 \def\@fpsaddddefault{\def\@fps{tp}}%
785 \@float}
786 \fi

```

`\enddblfloat` And the end. Just adding a `\bgroup`.

```

787 \if@ACM@sigchiamode
788 \def\enddblfloat{%
789 \end@float\egroup}
790 \fi

```

`\@endwidefloatbox` This is the end of a wide box—we basically move everything to the left

```

791 \def\@endwidefloatbox{%
792 \par\vskip\z@skip
793 \@minipagefalse
794 \outer@nobreak
795 \egroup
796 \color@endbox
797 \global\setbox\@currbox=\vbox{\moveleft
798 \dimexpr(\fulltextwidth-\textwidth)\box\@currbox}%
799 \wd\@currbox=\textwidth
800 }

```

3.11 Lists

```

801 \ifcase\ACM@format@nr
802 \relax % manuscript
803 \or % acmsmall
804 \or % acmlarge
805 \or % acmtog
806 \or % sigconf
807 \or % siggraph
808 \or % sigplan
809 \def\labelenumi{\theenumi.}
810 \def\labelenumii{\theenumii.}
811 \def\labelenumiii{\theenumiii.}
812 \def\labelenumiv{\theenumiv.}
813 \or % sigchi
814 \or % sigchi-a
815 \fi

```

The AMS uses generous margins for lists. Note that `amsart` defines `\leftmargin` values for list levels at the beginning of the document, so we must redefine them in the same manner. Also, note that `amsart` redefines the `enumerate` and `itemize` environments with a `\makelabel` command that uses `\llap`, so the `\labelwidth` value is (effectively) irrelevant; nonetheless, we follow `amsart` and set `\labelwidth` to `\leftmargin` minus `\labelsep`.

```

816 \newdimen\@ACM@labelwidth
817 \AtBeginDocument{%
818   \setlength\labelsep{4pt}
819   \setlength{\@ACM@labelwidth}{6.5pt}
820
821   %% First-level list: when beginning after the first line of an
822   %% indented paragraph or ending before an indented paragraph, labels
823   %% should not hang to the left of the preceding/following text.
824   \setlength\leftmargin{\z@}
825   \addtolength\leftmargin{\parindent}
826   \addtolength\leftmargin{2\labelsep}
827   \addtolength\leftmargin{\@ACM@labelwidth}
828
829   %% Second-level and higher lists.
830   \setlength\leftmarginii{\z@}
831   \addtolength\leftmarginii{0.5\labelsep}
832   \addtolength\leftmarginii{\@ACM@labelwidth}
833   \setlength\leftmarginiii{\leftmarginii}
834   \setlength\leftmarginiv{\leftmarginiii}
835   \setlength\leftmarginv{\leftmarginiv}
836   \setlength\leftmarginvi{\leftmarginv}
837   \@listi}
838 \newskip\listisep
839 \listisep\smallskipamount
840 \def\@listI{\leftmargin\leftmargini
841   \labelwidth\leftmargini \advance\labelwidth-\labelsep
842   \listparindent\z@
843   \topsep\listisep}
844 \let\@listi\@listI
845 \def\@listii{\leftmargin\leftmarginii
846   \labelwidth\leftmarginii \advance\labelwidth-\labelsep
847   \topsep\z@skip}
848 \def\@listiii{\leftmargin\leftmarginiii
849   \labelwidth\leftmarginiii \advance\labelwidth-\labelsep}
850 \def\@listiv{\leftmargin\leftmarginiv
851   \labelwidth\leftmarginiv \advance\labelwidth-\labelsep}
852 \def\@listv{\leftmargin\leftmarginv
853   \labelwidth\leftmarginv \advance\labelwidth-\labelsep}
854 \def\@listvi{\leftmargin\leftmarginvi
855   \labelwidth\leftmarginvi \advance\labelwidth-\labelsep}
\descriptionlabel We do not use a colon by default like amsart does:
856 \renewcommand{\descriptionlabel}[1]{\upshape\bfseries #1}

```

`\description` Make the description environment indentation consistent with that of the `itemize` and `enumerate` environments.

```

857 \renewenvironment{description}{\list{}{
858     \labelwidth\@ACM@labelwidth
859     \let\makelabel\descriptionlabel}%
860 }{
861     \endlist
862 }
863 \let\enddescription=\endlist % for efficiency

```

3.12 Top-matter data

`\if@ACM@maketitle@typeset` The switch to check whether `\maketitle` is already typeset. It is initially false, and setting top matter when it is true is wrong.

```

864 \newif\if@ACM@maketitle@typeset
865 \@ACM@maketitle@typesetfalse

```

We use the `xkeyval` interface to define journal titles and the relevant information

```

866 \define@choicekey*+{ACM}{acmJournal}[\@journalCode\@journalCode@nr]{%
867     CIE,%
868     CSUR,%
869     DGOV,%
870     DTRAP,%
871     HEALTH,%
872     IMWUT,%
873     JACM,%
874     JDIQ,%
875     JEA,%
876     JERIC,%
877     JETC,%
878     JOCCH,%
879     PACMCGIT,%
880     PACMHCI,%
881     PACMPL,%
882     POMACS,%
883     TAAS,%
884     TACCESS,%
885     TACO,%
886     TALG,%
887     TALLIP,%
888     TAP,%
889     TCPS,%
890     TDS,%
891     TEAC,%
892     TECS,%
893     TELO,%
894     THRI,%
895     TIIS,%
896     TIOT,%

```

```

897 TISSEC,%
898 TIST,%
899 TKDD,%
900 TMIS,%
901 TOCE,%
902 TOCHI,%
903 TOCL,%
904 TOCS,%
905 TOCT,%
906 TODAES,%
907 TODS,%
908 TOG,%
909 TOIS,%
910 TOIT,%
911 TOMACS,%
912 TOMM,%
913 TOMPECS,%
914 TOMS,%
915 TOPC,%
916 TOPS,%
917 TOPLAS,%
918 TOS,%
919 TOSEM,%
920 TOSN,%
921 TQC,%
922 TRETs,%
923 TSAS,%
924 TSC,%
925 TSLP,%
926 TWEB,%
927 FACMP%
928 }{%
929 \ifcase\@journalCode@nr
930 \relax % CIE
931 \def\@journalName{ACM Computers in Entertainment}%
932 \def\@journalNameShort{ACM Comput. Entertain.}%
933 \def\@permissionCodeOne{1544-3574}%
934 \or % CSUR
935 \def\@journalName{ACM Computing Surveys}%
936 \def\@journalNameShort{ACM Comput. Surv.}%
937 \def\@permissionCodeOne{0360-0300}%
938 \or % DGOV
939 \def\@journalName{Digital Government: Research and Practice}%
940 \def\@journalNameShort{Digit. Gov. Res. Pract.}%
941 \def\@permissionCodeOne{2639-0175}%
942 \or % DTRAP
943 \def\@journalName{Digital Threats: Research and Practice}%
944 \def\@journalNameShort{Digit. Threat. Res. Pract.}%
945 \def\@permissionCodeOne{2576-5337}%
946 \or % HEALTH

```

```

947 \def\@journalName{ACM Transactions on Computing for Healthcare}%
948 \def\@journalNameShort{ACM Trans. Comput. Healthcare}%
949 \def\@permissionCodeOne{2637-8051}%
950 \or % IMWUT
951 \def\@journalName{Proceedings of the ACM on Interactive, Mobile,
952   Wearable and Ubiquitous Technologies}%
953 \def\@journalNameShort{Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.}%
954 \def\@permissionCodeOne{2474-9567}%
955 \@ACM@screentru
956 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
957 \or % JACM
958 \def\@journalName{Journal of the ACM}%
959 \def\@journalNameShort{J. ACM}%
960 \def\@permissionCodeOne{0004-5411}%
961 \or % JDIQ
962 \def\@journalName{ACM Journal of Data and Information Quality}%
963 \def\@journalNameShort{ACM J. Data Inform. Quality}%
964 \def\@permissionCodeOne{1936-1955}%
965 \or % JEA
966 \def\@journalName{ACM Journal of Experimental Algorithmics}%
967 \def\@journalNameShort{ACM J. Exp. Algor.}%
968 \def\@permissionCodeOne{1084-6654}%
969 \or % JERIC
970 \def\@journalName{ACM Journal of Educational Resources in Computing}%
971 \def\@journalNameShort{ACM J. Edu. Resources in Comput.}%
972 \def\@permissionCodeOne{1073-0516}%
973 \or % JETC
974 \def\@journalName{ACM Journal on Emerging Technologies in Computing Systems}%
975 \def\@journalNameShort{ACM J. Emerg. Technol. Comput. Syst.}%
976 \def\@permissionCodeOne{1550-4832}%
977 \or % JOCCH
978 \def\@journalName{ACM Journal on Computing and Cultural Heritage}%
979 \def\@journalNameShort{ACM J. Comput. Cult. Herit.}%
980 \or % PACMCGIT
981 \def\@journalName{Proceedings of the ACM on Computer Graphics and Interactive Techniques}%
982 \def\@journalNameShort{Proc. ACM Comput. Graph. Interact. Tech.}%
983 \def\@permissionCodeOne{2577-6193}%
984 \@ACM@screentru
985 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
986 \or % PACMHCI
987 \def\@journalName{Proceedings of the ACM on Human-Computer Interaction}%
988 \def\@journalNameShort{Proc. ACM Hum.-Comput. Interact.}%
989 \def\@permissionCodeOne{2573-0142}%
990 \@ACM@screentru
991 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
992 \or % PACMPL
993 \def\@journalName{Proceedings of the ACM on Programming Languages}%
994 \def\@journalNameShort{Proc. ACM Program. Lang.}%
995 \def\@permissionCodeOne{2475-1421}%
996 \@ACM@screentru

```



```

997 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
998 \or % POMACS
999 \def\@journalName{Proceedings of the ACM on Measurement and Analysis of Computing Systems}%
1000 \def\@journalNameShort{Proc. ACM Meas. Anal. Comput. Syst.}%
1001 \def\@permissionCodeOne{2476-1249}%
1002 \@ACM@screentruer
1003 \PackageInfo{\@classname}{Using screen mode due to \@journalCode}%
1004 \or % TAAS
1005 \def\@journalName{ACM Transactions on Autonomous and Adaptive Systems}%
1006 \def\@journalNameShort{ACM Trans. Autonom. Adapt. Syst.}%
1007 \def\@permissionCodeOne{1556-4665}%
1008 \or % TACCESS
1009 \def\@journalName{ACM Transactions on Accessible Computing}%
1010 \def\@journalNameShort{ACM Trans. Access. Comput.}%
1011 \def\@permissionCodeOne{1936-7228}%
1012 \or % TACO
1013 \def\@journalName{ACM Transactions on Architecture and Code Optimization}%
1014 \def\@journalNameShort{ACM Trans. Arch. Code Optim.}%
1015 \or % TALG
1016 \def\@journalName{ACM Transactions on Algorithms}%
1017 \def\@journalNameShort{ACM Trans. Algor.}%
1018 \def\@permissionCodeOne{1549-6325}%
1019 \or % TALLIP
1020 \def\@journalName{ACM Transactions on Asian and Low-Resource Language Information Processing}%
1021 \def\@journalNameShort{ACM Trans. Asian Low-Resour. Lang. Inf. Process.}%
1022 \def\@permissionCodeOne{2375-4699}%
1023 \or % TAP
1024 \def\@journalName{ACM Transactions on Applied Perception}%
1025 \or % TCPS
1026 \def\@journalName{ACM Transactions on Cyber-Physical Systems}%
1027 \or % TDS
1028 \def\@journalName{ACM Transactions on Data Science}%
1029 \def\@journalNameShort{ACM Trans. Data Sci.}%
1030 \def\@permissionCodeOne{2577-3224}%
1031 \or % TEAC
1032 \def\@journalName{ACM Transactions on Economics and Computation}%
1033 \or % TECS
1034 \def\@journalName{ACM Transactions on Embedded Computing Systems}%
1035 \def\@journalNameShort{ACM Trans. Embedd. Comput. Syst.}%
1036 \def\@permissionCodeOne{1539-9087}%
1037 \or % TELO
1038 \def\@journalName{ACM Transactions on Evolutionary Learning}%
1039 \def\@journalNameShort{ACM Trans. Evol. Learn.}%
1040 \def\@permissionCodeOne{2688-3007}%
1041 \or % THRI
1042 \def\@journalName{ACM Transactions on Human-Robot Interaction}%
1043 \def\@journalNameShort{ACM Trans. Hum.-Robot Interact.}%
1044 \def\@permissionCodeOne{2573-9522}%
1045 \or % TIIS
1046 \def\@journalName{ACM Transactions on Interactive Intelligent Systems}%

```

```

1047 \def\@journalNameShort{ACM Trans. Interact. Intell. Syst.}%
1048 \def\@permissionCodeOne{2160-6455}%
1049 \or % TIOT
1050 \def\@journalName{ACM Transactions on Internet of Things}%
1051 \def\@journalNameShort{ACM Trans. Internet Things}%
1052 \def\@permissionCodeOne{2577-6207}%
1053 \or % TISSEC
1054 \def\@journalName{ACM Transactions on Information and System Security}%
1055 \def\@journalNameShort{ACM Trans. Info. Syst. Sec.}%
1056 \def\@permissionCodeOne{1094-9224}%
1057 \or % TIST
1058 \def\@journalName{ACM Transactions on Intelligent Systems and Technology}%
1059 \def\@journalNameShort{ACM Trans. Intell. Syst. Technol.}%
1060 \def\@permissionCodeOne{2157-6904}%
1061 \or % TKDD
1062 \def\@journalName{ACM Transactions on Knowledge Discovery from Data}%
1063 \def\@journalNameShort{ACM Trans. Knowl. Discov. Data.}%
1064 \def\@permissionCodeOne{1556-4681}%
1065 \or % TMIS
1066 \def\@journalName{ACM Transactions on Management Information Systems}%
1067 \def\@journalNameShort{ACM Trans. Manag. Inform. Syst.}%
1068 \def\@permissionCodeOne{2158-656X}%
1069 \or % TOCE
1070 \def\@journalName{ACM Transactions on Computing Education}%
1071 \def\@journalNameShort{ACM Trans. Comput. Educ.}%
1072 \def\@permissionCodeOne{1946-6226}%
1073 \or % TOCHI
1074 \def\@journalName{ACM Transactions on Computer-Human Interaction}%
1075 \def\@journalNameShort{ACM Trans. Comput.-Hum. Interact.}%
1076 \def\@permissionCodeOne{1073-0516}%
1077 \or % TOCL
1078 \def\@journalName{ACM Transactions on Computational Logic}%
1079 \def\@journalNameShort{ACM Trans. Comput. Logic}%
1080 \def\@permissionCodeOne{1529-3785}%
1081 \or % TOCS
1082 \def\@journalName{ACM Transactions on Computer Systems}%
1083 \def\@journalNameShort{ACM Trans. Comput. Syst.}%
1084 \def\@permissionCodeOne{0734-2071}%
1085 \or % TOCT
1086 \def\@journalName{ACM Transactions on Computation Theory}%
1087 \def\@journalNameShort{ACM Trans. Comput. Theory}%
1088 \def\@permissionCodeOne{1942-3454}%
1089 \or % TODAES
1090 \def\@journalName{ACM Transactions on Design Automation of Electronic Systems}%
1091 \def\@journalNameShort{ACM Trans. Des. Autom. Electron. Syst.}%
1092 \def\@permissionCodeOne{1084-4309}%
1093 \or % TODS
1094 \def\@journalName{ACM Transactions on Database Systems}%
1095 \def\@journalNameShort{ACM Trans. Datab. Syst.}%
1096 \def\@permissionCodeOne{0362-5915}%

```

```

1097 \or % TOG
1098   \def\@journalName{ACM Transactions on Graphics}%
1099   \def\@journalNameShort{ACM Trans. Graph.}%
1100   \def\@permissionCodeOne{0730-0301}
1101 \or % TOIS
1102   \def\@journalName{ACM Transactions on Information Systems}%
1103   \def\@permissionCodeOne{1046-8188}%
1104 \or % TOIT
1105   \def\@journalName{ACM Transactions on Internet Technology}%
1106   \def\@journalNameShort{ACM Trans. Internet Technol.}%
1107   \def\@permissionCodeOne{1533-5399}%
1108 \or % TOMACS
1109   \def\@journalName{ACM Transactions on Modeling and Computer Simulation}%
1110   \def\@journalNameShort{ACM Trans. Model. Comput. Simul.}%
1111 \or % TOMM
1112   \def\@journalName{ACM Transactions on Multimedia Computing, Communications and Applications}%
1113   \def\@journalNameShort{ACM Trans. Multimedia Comput. Commun. Appl.}%
1114   \def\@permissionCodeOne{1551-6857}%
1115   \def\@permissionCodeTwo{0100}%
1116 \or % TOMPECS
1117   \def\@journalName{ACM Transactions on Modeling and Performance Evaluation of Computing Systems}%
1118   \def\@journalNameShort{ACM Trans. Model. Perform. Eval. Comput. Syst.}%
1119   \def\@permissionCodeOne{2376-3639}%
1120 \or % TOMS
1121   \def\@journalName{ACM Transactions on Mathematical Software}%
1122   \def\@journalNameShort{ACM Trans. Math. Softw.}%
1123   \def\@permissionCodeOne{0098-3500}%
1124 \or % TOPC
1125   \def\@journalName{ACM Transactions on Parallel Computing}%
1126   \def\@journalNameShort{ACM Trans. Parallel Comput.}%
1127   \def\@permissionCodeOne{1539-9087}%
1128 \or % TOPS
1129   \def\@journalName{ACM Transactions on Privacy and Security}%
1130   \def\@journalNameShort{ACM Trans. Priv. Sec.}%
1131   \def\@permissionCodeOne{2471-2566}%
1132 \or % TOPLAS
1133   \def\@journalName{ACM Transactions on Programming Languages and Systems}%
1134   \def\@journalNameShort{ACM Trans. Program. Lang. Syst.}%
1135   \def\@permissionCodeOne{0164-0925}%
1136 \or % TOS
1137   \def\@journalName{ACM Transactions on Storage}%
1138   \def\@journalNameShort{ACM Trans. Storage}%
1139   \def\@permissionCodeOne{1553-3077}%
1140 \or % TOSEM
1141   \def\@journalName{ACM Transactions on Software Engineering and Methodology}%
1142   \def\@journalNameShort{ACM Trans. Softw. Eng. Methodol.}%
1143   \def\@permissionCodeOne{1049-331X}%
1144 \or % TOSN
1145   \def\@journalName{ACM Transactions on Sensor Networks}%
1146   \def\@journalNameShort{ACM Trans. Sensor Netw.}%

```

```

1147 \def\@permissionCodeOne{1550-4859}%
1148 \or % TQC
1149 \def\@journalName{ACM Transactions on Quantum Computing}%
1150 \def\@journalNameShort{ACM Trans. Quantum Comput.}%
1151 \def\@permissionCodeOne{2643-6817}%
1152 \or % TRET
1153 \def\@journalName{ACM Transactions on Reconfigurable Technology and Systems}%
1154 \def\@journalNameShort{ACM Trans. Reconfig. Technol. Syst.}%
1155 \def\@permissionCodeOne{1936-7406}%
1156 \or % TSAS
1157 \def\@journalName{ACM Transactions on Spatial Algorithms and Systems}%
1158 \def\@journalNameShort{ACM Trans. Spatial Algorithms Syst.}%
1159 \def\@permissionCodeOne{2374-0353}%
1160 \or % TSC
1161 \def\@journalName{ACM Transactions on Social Computing}%
1162 \def\@journalNameShort{ACM Trans. Soc. Comput.}%
1163 \def\@permissionCodeOne{2469-7818}%
1164 \or % TSLP
1165 \def\@journalName{ACM Transactions on Speech and Language Processing}%
1166 \def\@journalNameShort{ACM Trans. Speech Lang. Process.}%
1167 \def\@permissionCodeOne{1550-4875}%
1168 \or % TWEB
1169 \def\@journalName{ACM Transactions on the Web}%
1170 \def\@journalNameShort{ACM Trans. Web}%
1171 \def\@permissionCodeOne{1559-1131}%
1172 \else % FACMP, a dummy journal
1173 \def\@journalName{Forthcoming ACM Publication}%
1174 \def\@journalNameShort{ACM Forthcoming}%
1175 \def\@permissionCodeOne{XXXX-XXXX}%
1176 \fi
1177 \ClassInfo{\@classname}{Using journal code \@journalCode}%
1178 }{%
1179 \ClassError{\@classname}{Incorrect journal #1}%
1180 }%

```

\acmJournal And the syntactic sugar around it

```

1181 \def\acmJournal#1{\setkeys{ACM}{acmJournal=#1}%
1182 \global\@ACM@journal@bibstriptrue}

```

The defaults:

```

1183 \def\@journalCode@nr{0}
1184 \def\@journalName{}%
1185 \def\@journalNameShort{\@journalName}%
1186 \def\@permissionCodeOne{XXXX-XXXX}%
1187 \def\@permissionCodeTwo{}%

```

\acmConference This is the conference command

```

1188 \newcommand\acmConference[4][{}]{%
1189 \gdef\acmConference@shortname{#1}%

```

```

1190 \gdef\acmConference@name{#2}%
1191 \gdef\acmConference@date{#3}%
1192 \gdef\acmConference@venue{#4}%
1193 \ifx\acmConference@shortname\@empty
1194 \gdef\acmConference@shortname{#2}%
1195 \fi
1196 \global\@ACM@journal@bibstripfalse
1197 }
1198 \if@ACM@journal\else
1199 \acmConference[Conference'17]{ACM Conference}{July 2017}{Washington,
1200 DC, USA}%
1201 \fi

\acmBooktitle The book title of the conference:
\@acmBooktitle 1202 \def\acmBooktitle#1{\gdef\@acmBooktitle{#1}}
1203 \acmBooktitle{Proceedings of \acmConference@name
1204 \ifx\acmConference@name\acmConference@shortname\else
1205 \ (\acmConference@shortname)\fi}

\@editorsAbbrev How to abbreviate editors
1206 \def\@editorsAbbrev{(Ed.)}

\@acmEditors The list of editors
1207 \def\@acmEditors{}

\editor Add a new editor to the list
1208 \def\editor#1{\ifx\@acmEditors\@empty
1209 \gdef\@acmEditors{#1}%
1210 \else
1211 \gdef\@editorsAbbrev{(Eds.)}%
1212 \g@addto@macro\@acmEditors{\and#1}%
1213 \fi}

\subtitle The subtitle macro
1214 \def\subtitle#1{\def\@subtitle{#1}}
1215 \subtitle{}

\num@authorgroups The total number of “groups”. Each group is several authors with the same affiliations(s)
1216 \newcount\num@authorgroups
1217 \num@authorgroups=0\relax

\num@authors The total number of authors
1218 \newcount\num@authors
1219 \num@authors=0\relax

\if@insideauthorgroup Whether we are continuing an author group
1220 \newif\if@insideauthorgroup
1221 \@insideauthorgroupfalse

```

`\author` Adding an author to the list of authors and addresses

```

1222 \renewcommand\author[2][{}%
1223   \IfSubStr{#2}{,}{\ClassWarning{\@classname}{Do not put several
1224     authors in the same \string\author\space macro!}}{}%
1225   \global\advance\num@authors by 1\relax
1226   \if@insideauthorgroup\else
1227     \global\advance\num@authorgroups by 1\relax
1228     \global\@insideauthorgroupttrue
1229   \fi
1230   \ifx\addresses\@empty
1231     \if@ACM@anonymous
1232       \gdef\addresses{\@author{Anonymous Author(s)}%
1233         \ifx\@acmSubmissionID\@empty\else\Submission Id:
1234           \@acmSubmissionID\fi}}%
1235       \gdef\authors{Anonymous Author(s)}%
1236     \else
1237       \gdef\addresses{\@author{#2}}%
1238       \gdef\authors{#2}%
1239     \fi
1240   \else
1241     \if@ACM@anonymous\else
1242       \g@addto@macro\addresses{\and\@author{#2}}%
1243       \g@addto@macro\authors{\and#2}%
1244     \fi
1245   \fi
1246   \if@ACM@anonymous
1247     \ifx\shortauthors\@empty
1248       \gdef\shortauthors{Anon.
1249         \ifx\@acmSubmissionID\@empty\else Submission Id:
1250           \@acmSubmissionID\fi}%
1251     \fi
1252   \else
1253     \def\@tempa{#1}%
1254     \ifx\@tempa\@empty
1255       \ifx\shortauthors\@empty
1256         \gdef\shortauthors{#2}%
1257       \else
1258         \g@addto@macro\shortauthors{\and#2}%
1259       \fi
1260     \else
1261       \ifx\shortauthors\@empty
1262         \gdef\shortauthors{#1}%
1263       \else
1264         \g@addto@macro\shortauthors{\and#1}%
1265       \fi
1266     \fi
1267   \fi}

```

`\affiliation` The macro `\affiliation` mimics `\address` from `amsart`. Note that it has an optional

argument, which we use differently from `amsart`.

```

1268 \newcommand{\affiliation}[2][{}]{%
1269   \global\@insideauthorgroupfalse
1270   \if@ACM@anonymous\else
1271     \g@addto@macro\addresses{\affiliation{#1}{#2}}%
1272   \fi}

```

`@ACM@affiliation@obeypunctuation` Whether to use the author's punctuation (false by default, which adds American-style address punctuation)

```

1273 \define@boolkey+{@ACM@affiliation@}{@ACM@affiliation@}{obeypunctuation}%
1274 [true]{\ClassError{\@classname}{The option obeypunctuation can be either true or false}}

```

`\additionalaffiliation` Additional affiliations go to footnotes

```

1275 \def\additionalaffiliation#1{\authornote{\@additionalaffiliation{#1}}}

```

`@additionalaffiliation` Process `\additionalaffiliation` inside `\authornote`

```

1276 \def@additionalaffiliation#1{\bgroup
1277   \def\position##1{\ignorespaces}%
1278   \def\institution##1{##1\ignorespaces}%
1279   \def\department{\@ifnextchar[\@department]{\@department[]}}%
1280   \def@department[##1]##2{\unskip, ##2\ignorespaces}%
1281   \let\streetaddress\position
1282   \let\city\position
1283   \let\state\position
1284   \let\postcode\position
1285   \let\country\position
1286   Also with #1\unskip.\egroup}

```

`\email` The macro `\email` mimics `\email` from `amsart`. Again, it has an optional argument that we do not currently need but keep for possible future use.

```

1287 \renewcommand{\email}[2][{}]{%
1288   \IfSubStr{#2}{,}{\ClassWarning{\@classname}{Do not put several
1289     addresses in the same \string\email\space macro!}}{}%
1290   \if@ACM@anonymous\else
1291     \g@addto@macro\addresses{\email{#1}{#2}}%
1292   \fi}

```

`\orcid` Right now we do not typeset ORCIDs

```

1293 \def\orcid#1{\unskip\ignorespaces}

```

`\authorsaddresses` Setting up authors' addresses

```

1294 \def\authorsaddresses#1{\def@authorsaddresses{#1}}
1295 \authorsaddresses{\mkauthorsaddresses}

```

`@titlenotes` The title notes

```

1296 \def@titlenotes{}

```

```

\titlenote Adding a note to the title
1297 \def\titlenote#1{%
1298   \g@addto@macro\@title{\footnotemark}%
1299   \if@ACM@anonymous
1300     \g@addto@macro\@titlenotes{%
1301       \stepcounter{footnote}\footnotetext{Title note}}%
1302   \else
1303     \g@addto@macro\@titlenotes{\stepcounter{footnote}\footnotetext{#1}}%
1304   \fi}

\@subtitlenotes The subtitle notes
1305 \def\@subtitlenotes{}

\subtitlenote Adding a note to the subtitle
1306 \def\subtitlenote#1{%
1307   \g@addto@macro\@subtitle{\footnotemark}%
1308   \if@ACM@anonymous
1309     \g@addto@macro\@subtitlenotes{%
1310       \stepcounter{footnote}\footnotetext{Subtitle note}}%
1311   \else
1312     \g@addto@macro\@subtitlenotes{%
1313       \stepcounter{footnote}\footnotetext{#1}}%
1314   \fi}

\@authornotes The author notes
1315 \def\@authornotes{}

\authornote Adding a note to the author
1316 \def\authornote#1{%
1317   \if@ACM@anonymous\else
1318     \g@addto@macro\addresses{\@authornotemark}%
1319     \g@addto@macro\@authornotes{%
1320       \stepcounter{footnote}\footnotetext{#1}}%
1321   \fi}

\authornotemark Adding a footnote mark to the authors
1322 \newcommand\authornotemark[1][\relax]{%
1323   \ifx#1\relax\relax\relax
1324     \g@addto@macro\addresses{\@authornotemark}%
1325   \else
1326     \g@addto@macro\addresses{\@authornotemark{#1}}%
1327   \fi}

\acmVolume The current volume
1328 \def\acmVolume#1{\def\@acmVolume{#1}}
1329 \acmVolume{1}

\acmNumber The current number
1330 \def\acmNumber#1{\def\@acmNumber{#1}}
1331 \acmNumber{1}

```


<code>\acmArticle</code>	<p>The current article</p> <pre>1332 \def\acmArticle#1{\def\@acmArticle{#1}} 1333 \acmArticle{}</pre>
<code>\acmArticleSeq</code>	<p>The sequence number</p> <pre>1334 \def\acmArticleSeq#1{\def\@acmArticleSeq{#1}} 1335 \acmArticleSeq{\@acmArticle}</pre>
<code>\acmYear</code>	<p>The current year</p> <pre>1336 \def\acmYear#1{\def\@acmYear{#1}} 1337 \acmYear{\the\year}</pre>
<code>\acmMonth</code>	<p>The current month</p> <pre>1338 \def\acmMonth#1{\def\@acmMonth{#1}} 1339 \acmMonth{\the\month}</pre>
<code>\@acmPubDate</code>	<p>The publication date</p> <pre>1340 \def\@acmPubDate{\ifcase\@acmMonth\or 1341 January\or February\or March\or April\or May\or June\or 1342 July\or August\or September\or October\or November\or 1343 December\fi~\@acmYear}</pre>
<code>\acmPrice</code>	<p>The price</p> <pre>1344 \def\acmPrice#1{\def\@acmPrice{#1}} 1345 \acmPrice{15.00}</pre>
<code>\acmSubmissionID</code>	<p>The submission ID</p> <pre>1346 \def\acmSubmissionID#1{\def\@acmSubmissionID{#1}} 1347 \acmSubmissionID{}</pre>
<code>\acmISBN</code>	<p>The book ISBN</p> <pre>1348 \def\acmISBN#1{\def\@acmISBN{#1}} 1349 \acmISBN{978-x-xxxx-xxxx-x/YY/MM}</pre>
<code>\acmDOI</code>	<p>The paper DOI</p> <pre>1350 \def\acmDOI#1{\def\@acmDOI{#1}} 1351 \acmDOI{10.1145/nnnnnnn.nnnnnnn}</pre>
<code>\if@ACM@badge</code>	<p>Whether to print a badge. Note that either a left or right badge triggers it:</p> <pre>1352 \newif\if@ACM@badge 1353 \@ACM@badgefalse</pre>
<code>\@ACM@badge@width</code>	<p>The width of the badge</p> <pre>1354 \newlength\@ACM@badge@width 1355 \setlength\@ACM@badge@width{5pc}</pre>
<code>\@ACM@title@width</code>	<p>The width of the badge</p> <pre>1356 \newlength\@ACM@title@width</pre>

`\@ACM@badge@skip` The space between the badge and the title

```

1357 \newlength\@ACM@badge@skip
1358 \setlength\@ACM@badge@skip{1pc}

```

`\acmBadgeR` Setting the right badge

```

1359 \newcommand\acmBadgeR[2][\@ACM@badgetrue
1360   \def\@acmBadgeR@url{#1}%
1361   \def\@acmBadgeR@image{#2}}
1362 \def\@acmBadgeR@url{}
1363 \def\@acmBadgeR@image{}

```

`\acmBadgeL` Setting the left badge

```

1364 \newcommand\acmBadgeL[2][\@ACM@badgetrue
1365   \def\@acmBadgeL@url{#1}%
1366   \def\@acmBadgeL@image{#2}}
1367 \def\@acmBadgeL@url{}
1368 \def\@acmBadgeL@image{}

```

`\startPage` The start page of the paper

```

1369 \def\startPage#1{\def\@startPage{#1}}
1370 \startPage{}

```

`\terms` Terms are obsolete. We use CCS now.

```

1371 \def\terms#1{\ClassWarning{\@classname}{The command \string\terms{} is
1372   obsolete. I am going to ignore it}}

```

`\keywords` Keywords are mostly obsolete. We use CCS now. Still it makes sense to keep them for compatibility.

```

1373 \def\keywords#1{\def\@keywords{#1}}
1374 \let\@keywords\empty

1375 \AtEndDocument{\if@ACM@nonacm\else\ifx\@keywords\empty
1376   \ifnum\getrefnumber{TotPages}>2\relax
1377   \ClassWarningNoLine{\@classname}{ACM keywords are mandatory
1378     for papers over two pages}%
1379   \fi\fi\fi}

```

`abstract` The amsart package puts abstract in a box. Since we do not know whether we will use two-column mode, we prefer to save the text

```

1380 \renewenvironment{abstract}{\Collect@Body\@saveabstract}{\}

```

`\@saveabstract` And saving the abstract

```

1381 \long\def\@saveabstract#1{\if@ACM@maketitle@typeset
1382   \ClassError{\@classname}{Abstract must be defined before maketitle
1383     command. Please move it!}\fi
1384   \long\gdef\@abstract{#1}}
1385 \@saveabstract{}

```

`\@empty` The long version of `\@empty` (to compare with `\@abstract`)

```
1386 \long\def\@empty{}
```

`\if@ACM@printccs` Whether to print CCS

```
1387 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printccs}[true]{%
1388   \if@ACM@printccs
1389     \ClassInfo{\@classname}{Printing CCS}%
1390   \else
1391     \ClassInfo{\@classname}{Suppressing CCS}%
1392   \fi}{\ClassError{\@classname}{The option printccs can be either true or false}}
```

`\if@ACM@printacmref` Whether to print the ACM bibstrip

```
1393 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printacmref}[true]{%
1394   \if@ACM@printacmref
1395     \ClassInfo{\@classname}{Printing bibformat}%
1396   \else
1397     \ClassInfo{\@classname}{Suppressing bibformat}%
1398   \fi}{\ClassError{\@classname}{The option printacmref can be either true or false}}

1399 \AtEndDocument{\if@ACM@nonacm\else\if@ACM@printacmref\else
1400   \ifnum\getrefnumber{TotPages}>1\relax
1401   \ClassWarningNoLine{\@classname}{ACM reference format is mandatory
1402     for papers over one page}%
1403   \fi\fi\fi}
```

`\if@ACM@printfolios` Whether to print folios

```
1404 \define@boolkey+{@ACM@topmatter@}[@ACM@]{printfolios}[true]{%
1405   \if@ACM@printfolios
1406     \ClassInfo{\@classname}{Printing folios}%
1407   \else
1408     \ClassInfo{\@classname}{Suppressing folios}%
1409   \fi}{\ClassError{\@classname}{The option printfolios can be either true or false}}
```

`\@ACM@authorsperrrow` The number of authors per row. 0 means use the default algorithm.

```
1410 \define@cmdkey{@ACM@topmatter@}[@ACM@]{authorsperrrow}[0]{%
1411   \IfInteger{#1}{\ClassInfo{\@classname}{Setting authorsperrrow to
1412     #1}}{\ClassWarning{\@classname}{The parameter authorsperrrow must be
1413     numerical. Ignoring the input #1}\gdef\@ACM@authorsperrrow{0}}}
```

`\settopmatter` The usual syntactic sugar

```
1414 \def\settopmatter#1{\setkeys{@ACM@topmatter@}{#1}}
```

Now the settings

```
1415 \settopmatter{printccs=true, printacmref=true}
1416 \if@ACM@manuscript
1417   \settopmatter{printfolios=true}
1418 \else
1419   \if@ACM@journal
1420     \settopmatter{printfolios=true}
```

```

1421 \else
1422 \settopmatter{printfolios=false}
1423 \fi
1424 \fi
1425 \settopmatter{authorsperrow=0}

\@received The container for the paper history
1426 \def\@received{}

\received The \received command
1427 \newcommand\received[2][\def\@tempa{#1}%
1428 \ifx\@tempa\@empty
1429 \ifx\@received\@empty
1430 \gdef\@received{Received #2}%
1431 \else
1432 \g@addto@macro{\@received}{; revised #2}%
1433 \fi
1434 \else
1435 \ifx\@received\@empty
1436 \gdef\@received{#1 #2}%
1437 \else
1438 \g@addto@macro{\@received}{; #1 #2}%
1439 \fi
1440 \fi}
1441 \AtEndDocument{%
1442 \ifx\@received\@empty\else
1443 \par\bigskip\noindent\small\normalfont\@received\par
1444 \fi}

```

3.13 Concepts system

We exclude CCSXML stuff generated by the ACM system:

```

1445 \RequirePackage{comment}
1446 \excludecomment{CCSXML}

\@concepts This is the storage macro and counter for concepts
1447 \let\@concepts\@empty
1448 \newcounter{concepts}

\ccsdesc The first argument is the significance, the second is the concept(s)
1449 \newcommand\ccsdesc[2][100]{%
1450 \ccsdesc@parse#1~#2~~\ccsdesc@parse@end}

\ccsdesc@parse The parser of the expression Significance~General~Specific (we need textcomp for
\textrightarrow). Note that Specific can be empty!
1451 \def\textrightarrow{$\rightarrow$}
1452 \def\ccsdesc@parse#1~#2~#3~{%
1453 \stepcounter{concepts}%

```

```

1454 \expandafter\ifx\csname CCS@General@#2\endcsname\relax
1455 \expandafter\gdef\csname CCS@General@#2\endcsname{\textbullet\
1456 \textbf{#2}}}%
1457 \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{;}%
1458 \expandafter\gdef\csname CCS@Specific@#2\endcsname{}%
1459 \g@addto@macro{\@concepts}{\csname CCS@General@#2\endcsname
1460 \csname CCS@Punctuation@#2\endcsname
1461 \csname CCS@Specific@#2\endcsname}%
1462 \fi
1463 \ifx#3\relax\relax\else
1464 \expandafter\gdef\csname CCS@Punctuation@#2\endcsname{
1465 \textrightarrow}%
1466 \expandafter\g@addto@macro\expandafter{\csname CCS@Specific@#2\endcsname}{%
1467 \addtocounter{@concepts}{-1}}%
1468 \ifnum#1>499\textbf{#3}\else
1469 \ifnum#1>299\textit{#3}\else
1470 #3\fi\fi\ifnum\value{@concepts}=0.\else; \fi}%
1471 \fi
1472 \ccsdesc@parse@finish}

1473 \AtEndDocument{\if@ACM@nonacm\else\ifx\@concepts\empty\relax
1474 \ifnum\getrefnumber{TotPages}>2\relax
1475 \ClassWarningNoLine{\@classname}{CCS concepts are mandatory
1476 for papers over two pages}%
1477 \fi\fi\fi}

```

```

\ccdesc@parse@finish Gobble everything to \ccsdesc@parse@end
1478 \def\ccsdesc@parse@finish#1\ccsdesc@parse@end{}

```

3.14 Copyright system

This is from acmcopyright.sty

```

\if@printcopyright Whether to print a copyright symbol
1479 \newif\if@printcopyright
1480 \@printcopyrighttrue

\if@printpermission Whether to print the permission block
1481 \newif\if@printpermission
1482 \@printpermissiontrue

\if@acmowned Whether the ACM owns the rights to the paper
1483 \newif\if@acmowned
1484 \@acmownedtrue

```

Keys:

```

1485 \define@choicekey*{ACM@}{acmcopyrightmode}[%
1486 \acm@copyrightinput\acm@copyrightmode]{none,%
1487 acmcopyright,acmlicensed,rightsretained,%

```

```

1488     usgov,usgovmixed,cagov,cagovmixed,licensedusgovmixed,%
1489     licensedcagov,licensedcagovmixed,othergov,licensedothergov,%
1490     iw3c2w3,iw3c2w3g}{%
1491 \@printpermissiontrue
1492 \@printcopyrighttrue
1493 \@acmownedtrue
1494 \ifnum\acm@copyrightmode=0\relax % none
1495     \@printpermissionfalse
1496     \@printcopyrightfalse
1497     \@acmownedfalse
1498 \fi
1499 \ifnum\acm@copyrightmode=2\relax % acmlicensed
1500     \@acmownedfalse
1501 \fi
1502 \ifnum\acm@copyrightmode=3\relax % rightsretained
1503     \@acmownedfalse
1504     \AtBeginDocument{\acmPrice{}}%
1505 \fi
1506 \ifnum\acm@copyrightmode=4\relax % usgov
1507     \@printpermissiontrue
1508     \@printcopyrightfalse
1509     \@acmownedfalse
1510     \AtBeginDocument{\acmPrice{}}%
1511 \fi
1512 \ifnum\acm@copyrightmode=6\relax % cagov
1513     \@acmownedfalse
1514 \fi
1515 \ifnum\acm@copyrightmode=8\relax % licensedusgovmixed
1516     \@acmownedfalse
1517 \fi
1518 \ifnum\acm@copyrightmode=9\relax % licensedcagov
1519     \@acmownedfalse
1520 \fi
1521 \ifnum\acm@copyrightmode=10\relax % licensedcagovmixed
1522     \@acmownedfalse
1523 \fi
1524 \ifnum\acm@copyrightmode=11\relax % othergov
1525     \@acmownedtrue
1526 \fi
1527 \ifnum\acm@copyrightmode=12\relax % licensedothergov
1528     \@acmownedfalse
1529 \fi
1530 \ifnum\acm@copyrightmode=13\relax % iw3c2w3
1531     \@acmownedfalse
1532     \AtBeginDocument{\acmPrice{}}%
1533 \fi
1534 \ifnum\acm@copyrightmode=14\relax % iw3c2w3g
1535     \@acmownedfalse
1536     \AtBeginDocument{\acmPrice{}}%
1537 \fi}

```

`\setcopyright` This is the syntactic sugar around setting keys.

```
1538 \def\setcopyright#1{\setkeys{ACM@}{acmcopyrightmode=#1}}
1539 \setcopyright{acmcopyright}
```

`\@copyrightowner` Here is the owner of the copyright

```
1540 \def\@copyrightowner{%
1541   \ifcase\acm@copyrightmode\relax % none
1542   \or % acmcopyright
1543     Association for Computing Machinery.
1544   \or % acmlicensed
1545     Copyright held by the owner/author(s). Publication rights licensed to
1546     ACM\@.
1547   \or % rightsretained
1548     Copyright held by the owner/author(s).
1549   \or % usgov
1550   \or % usgovmixed
1551     Association for Computing Machinery.
1552   \or % cagov
1553     Crown in Right of Canada.
1554   \or %cagovmixed
1555     Association for Computing Machinery.
1556   \or %licensedusgovmixed
1557     Copyright held by the owner/author(s). Publication rights licensed to
1558     ACM\@.
1559   \or % licensedcagov
1560     Crown in Right of Canada. Publication rights licensed to
1561     ACM\@.
1562   \or %licensedcagovmixed
1563     Copyright held by the owner/author(s). Publication rights licensed to
1564     ACM\@.
1565   \or % othergov
1566     Association for Computing Machinery.
1567   \or % licensedothergov
1568     Copyright held by the owner/author(s). Publication rights licensed to
1569     ACM\@.
1570   \or % ic2w3www
1571     IW3C2 (International World Wide Web Conference Committee), published
1572     under Creative Commons CC-BY~4.0 License.
1573   \or % ic2w3wwwgoogle
1574     IW3C2 (International World Wide Web Conference Committee), published
1575     under Creative Commons CC-BY-NC-ND~4.0 License.
1576   \fi}
```

`\@formatdoi` Print a clickable DOI

```
1577 \def\@formatdoi#1{\url{https://doi.org/#1}}
```

`\@copyrightpermission` The canned permission block.

```
1578 \def\@copyrightpermission{%
1579   \ifcase\acm@copyrightmode\relax % none
```

1580 \or % acmcopyright
1581 Permission to make digital or hard copies of all or part of this
1582 work for personal or classroom use is granted without fee provided
1583 that copies are not made or distributed for profit or commercial
1584 advantage and that copies bear this notice and the full citation on
1585 the first page. Copyrights for components of this work owned by
1586 others than ACM must be honored. Abstracting with credit is
1587 permitted. To copy otherwise, or republish, to post on servers or to
1588 redistribute to lists, requires prior specific permission
1589 and\hspace*{.5pt}/or a fee. Request permissions from
1590 permissions@acm.org.

1591 \or % acmlicensed
1592 Permission to make digital or hard copies of all or part of this
1593 work for personal or classroom use is granted without fee provided
1594 that copies are not made or distributed for profit or commercial
1595 advantage and that copies bear this notice and the full citation on
1596 the first page. Copyrights for components of this work owned by
1597 others than the author(s) must be honored. Abstracting with credit
1598 is permitted. To copy otherwise, or republish, to post on servers
1599 or to redistribute to lists, requires prior specific permission
1600 and\hspace*{.5pt}/or a fee. Request permissions from
1601 permissions@acm.org.

1602 \or % rightsretained
1603 Permission to make digital or hard copies of part or all of this work
1604 for personal or classroom use is granted without fee provided that
1605 copies are not made or distributed for profit or commercial advantage
1606 and that copies bear this notice and the full citation on the first
1607 page. Copyrights for third-party components of this work must be
1608 honored. For all other uses, contact the
1609 owner\hspace*{.5pt}/author(s).

1610 \or % usgov
1611 This paper is authored by an employee(s) of the United States
1612 Government and is in the public domain. Non-exclusive copying or
1613 redistribution is allowed, provided that the article citation is
1614 given and the authors and agency are clearly identified as its
1615 source.

1616 \or % usgovmixed
1617 ACM acknowledges that this contribution was authored or co-authored
1618 by an employee, contractor, or affiliate of the United States
1619 government. As such, the United States government retains a
1620 nonexclusive, royalty-free right to publish or reproduce this
1621 article, or to allow others to do so, for government purposes only.

1622 \or % cagov
1623 This article was authored by employees of the Government of Canada.
1624 As such, the Canadian government retains all interest in the
1625 copyright to this work and grants to ACM a nonexclusive,
1626 royalty-free right to publish or reproduce this article, or to allow
1627 others to do so, provided that clear attribution is given both to
1628 the authors and the Canadian government agency employing them.
1629 Permission to make digital or hard copies for personal or classroom

1630 use is granted. Copies must bear this notice and the full citation
 1631 on the first page. Copyrights for components of this work owned by
 1632 others than the Canadian Government must be honored. To copy
 1633 otherwise, distribute, republish, or post, requires prior specific
 1634 permission and\hspace*{.5pt}/or a fee. Request permissions from
 1635 permissions@acm.org.
 1636 \or % cagovmixed
 1637 ACM acknowledges that this contribution was co-authored by an
 1638 affiliate of the national government of Canada. As such, the Crown
 1639 in Right of Canada retains an equal interest in the copyright.
 1640 Reprints must include clear attribution to ACM and the author's
 1641 government agency affiliation. Permission to make digital or hard
 1642 copies for personal or classroom use is granted. Copies must bear
 1643 this notice and the full citation on the first page. Copyrights for
 1644 components of this work owned by others than ACM must be honored.
 1645 To copy otherwise, distribute, republish, or post, requires prior
 1646 specific permission and\hspace*{.5pt}/or a fee. Request permissions
 1647 from permissions@acm.org.
 1648 \or % licensedusgovmixed
 1649 Publication rights licensed to ACM\@. ACM acknowledges that this
 1650 contribution was authored or co-authored by an employee, contractor
 1651 or affiliate of the United States government. As such, the
 1652 Government retains a nonexclusive, royalty-free right to publish or
 1653 reproduce this article, or to allow others to do so, for Government
 1654 purposes only.
 1655 \or % licensedcagov
 1656 This article was authored by employees of the Government of Canada.
 1657 As such, the Canadian government retains all interest in the
 1658 copyright to this work and grants to ACM a nonexclusive,
 1659 royalty-free right to publish or reproduce this article, or to allow
 1660 others to do so, provided that clear attribution is given both to
 1661 the authors and the Canadian government agency employing them.
 1662 Permission to make digital or hard copies for personal or classroom
 1663 use is granted. Copies must bear this notice and the full citation
 1664 on the first page. Copyrights for components of this work owned by
 1665 others than the Canadian Government must be honored. To copy
 1666 otherwise, distribute, republish, or post, requires prior specific
 1667 permission and\hspace*{.5pt}/or a fee. Request permissions from
 1668 permissions@acm.org.
 1669 \or % licensedcagovmixed
 1670 Publication rights licensed to ACM\@. ACM acknowledges that this
 1671 contribution was authored or co-authored by an employee, contractor
 1672 or affiliate of the national government of Canada. As such, the
 1673 Government retains a nonexclusive, royalty-free right to publish or
 1674 reproduce this article, or to allow others to do so, for Government
 1675 purposes only.
 1676 \or % othergov
 1677 ACM acknowledges that this contribution was authored or co-authored
 1678 by an employee, contractor or affiliate of a national government. As
 1679 such, the Government retains a nonexclusive, royalty-free right to

```

1680 publish or reproduce this article, or to allow others to do so, for
1681 Government purposes only.
1682 \or % licensedothergov
1683 Publication rights licensed to ACM\@. ACM acknowledges that this
1684 contribution was authored or co-authored by an employee, contractor
1685 or affiliate of a national government. As such, the Government
1686 retains a nonexclusive, royalty-free right to publish or reproduce
1687 this article, or to allow others to do so, for Government purposes
1688 only.
1689 \or % iw3c2w3
1690 This paper is published under the Creative Commons Attribution~4.0
1691 International (CC-BY~4.0) license. Authors reserve their rights to
1692 disseminate the work on their personal and corporate Web sites with
1693 the appropriate attribution.
1694 \or % iw3c2w3g
1695 This paper is published under the Creative Commons
1696 Attribution-NonCommercial-NoDerivs~4.0 International
1697 (CC-BY-NC-ND~4.0) license. Authors reserve their rights to
1698 disseminate the work on their personal and corporate Web sites with
1699 the appropriate attribution.
1700 \fi}

\copyrightyear By default, the copyright year is the same as \acmYear, but one can override this:
1701 \def\copyrightyear#1{\def\@copyrightyear{#1}}
1702 \copyrightyear{\@acmYear}

\@teaserfigures The teaser figures container
1703 \def\@teaserfigures{}

teaserfigure The teaser figure
1704 \newenvironment{teaserfigure}{\Collect@Body\@saveteaser}{}

\@saveteaser Saving the teaser
1705 \long\def\@saveteaser#1{\g@addto@macro\@teaserfigures{\@teaser{#1}}}}

\thanks We redefine amsart \thanks so the anonymous key works
1706 \renewcommand{\thanks}[1]{%
1707   \@ifnotempty{#1}{%
1708     \if@ACM@anonymous
1709       \g@addto@macro\thankses{\thanks{A note}}}%
1710   \else
1711     \g@addto@macro\thankses{\thanks{#1}}}%
1712   \fi}}

```

3.15 Typesetting top matter

```

\mktitle@bx Some of our formats use a two-column design. Some use a one-column design. In all
cases we use a wide title. Thus we typeset the top matter in a special box to be used in
the construction \@twocolumn[<box>].
1713 \newbox\mktitle@bx

```

`\maketitle` The (in)famous `\maketitle`. Note that in `sigchi-a` mode, authors are *not* in the title box.

Another note: there is a subtle difference between author notes, title notes and thanks. The latter two refer to the paper itself and therefore belong to the copyright/permission block. By the way, this was the default behavior of the old ACM classes.

```

1714 \def\maketitle{%
1715   \ACM@maketitle@typesettrue
1716   \if@ACM@anonymous
1717     % Anonymize omission of \author-s
1718     \ifnum\num@authorgroups=0\author{}\fi
1719   \fi
1720   \begingroup
1721   \let\@vspace\@vspace@orig
1722   \let\@vspacer\@vspacer@orig
1723   \let\@footnotemark\@footnotemark@nolink
1724   \let\@footnotetext\@footnotetext@nolink
1725   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1726   \hsize=\textwidth
1727   \def\@makefnmark{\hbox{\@textsuperscript{\@thefnmark}}}%
1728   \mktitle\if@ACM@sigchiamode\else\mkauthors\fi\mkteasers
1729   \@printtopmatter
1730   \if@ACM@sigchiamode\mkauthors\fi
1731   \setcounter{footnote}{0}%
1732   \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}%
1733   \@titlenotes
1734   \@subtitlenotes
1735   \@authornotes
1736   \let\@makefnmark\relax
1737   \let\@thefnmark\relax
1738   \let\@makefntext\noindent
1739   \ifx\@empty\thankses\else
1740     \footnotetextauthorsaddresses{%
1741       \def\par{\let\par\@par}\parindent\z@\@setthanks}%
1742   \fi
1743   \ifx\@empty\authorsaddresses\else
1744     \if@ACM@anonymous\else
1745       \if@ACM@journal@bibstrip
1746         \footnotetextauthorsaddresses{%
1747           \def\par{\let\par\@par}\parindent\z@\@setauthorsaddresses}%
1748       \fi
1749     \fi
1750   \fi
1751   \if@ACM@nonacm\else\footnotetextcopyrightpermission{%
1752     \if@ACM@authordraft
1753       \raisebox{-2ex}{\z@}{\makebox[0pt][l]{\large\bfseries
1754         Unpublished working draft. Not for distribution.}}%
1755       \color[gray]{0.9}%
1756     \fi
1757     \parindent\z@\parskip0.1\baselineskip

```

```

1758 \if@ACM@authorversion\else
1759   \if@printpermission\@copyrightpermission\par\fi
1760 \fi
1761 \if@ACM@manuscript\else
1762   \if@ACM@journal@bibstrip\else % Print the conference information
1763     {\itshape \acmConference@shortname, \acmConference@date, \acmConference@venue}\par
1764   \fi
1765 \fi
1766 \if@printcopyright
1767   \copyright\ \@copyrightyear\ \@copyrightowner\
1768 \else
1769   \@copyrightyear.\
1770 \fi
1771 \if@ACM@manuscript
1772   Manuscript submitted to ACM\
1773 \else
1774   \if@ACM@authorversion
1775     This is the author's version of the work. It is posted here for
1776     your personal use. Not for redistribution. The definitive Version
1777     of Record was published in
1778     \if@ACM@journal@bibstrip
1779       \emph{\@journalName}%
1780     \else
1781       \emph{\@acmBooktitle}%
1782     \fi
1783     \ifx\@acmDOI\@empty
1784       .
1785     \else
1786       , \@formatdoi{\@acmDOI}.
1787     \fi\
1788   \else
1789     \if@ACM@nonacm\else
1790       \if@ACM@journal@bibstrip
1791         \@permissionCodeOne/\@acmYear/\@acmMonth-ART\@acmArticle
1792         \ifx\@acmPrice\@empty\else\ $\@acmPrice\fi\
1793         \@formatdoi{\@acmDOI}%
1794       \else % Conference
1795         \ifx\@acmISBN\@empty\else ACM~ISBN~\@acmISBN
1796         \ifx\@acmPrice\@empty.\else\dots\$\@acmPrice\fi\\\fi
1797         \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi%
1798       \fi
1799     \fi
1800   \fi
1801 \fi}
1802 \fi
1803 \endgroup
1804 \setcounter{footnote}{0}%
1805 \mkabstract
1806 \if@ACM@printccs
1807 \ifx\@concepts\@empty\else\bgroup

```

```

1808     {\@specialsection{CCS Concepts}%
1809       \noindent\@concepts\par}\egroup
1810   \fi
1811 \fi
1812 \ifx\@keywords\@empty\else\bgroup
1813   {\if@ACM@journal
1814     \@specialsection{Additional Key Words and Phrases}%
1815     \else
1816       \@specialsection{Keywords}%
1817     \fi
1818     \noindent\@keywords}\par\egroup
1819 \fi
1820 \andify\authors
1821 \andify\shortauthors
1822 \global\let\authors=\authors
1823 \global\let\shortauthors=\shortauthors
1824 \if@ACM@printacmref
1825   \@mkbibcitation
1826 \fi
1827 \hypersetup{%
1828   pdfauthor={\authors},
1829   pdftitle={\@title},
1830   pdfsubject={\@concepts},
1831   pdfkeywords={\@keywords},
1832   pdfcreator={LaTeX with acmart
1833     \csname ver@acmart.cls\endcsname\space
1834     and hyperref
1835     \csname ver@hyperref.sty\endcsname}}%
1836 \global\@topnum\z@ % this prevents floats from falling
1837                   % at the top of page 1
1838 \global\@botnum\z@ % we do not want them to be on the bottom either
1839 \@printendtopmatter
1840 \@afterindentfalse
1841 \@afterheading
1842 }

```

`\@specialsection` This macro starts sections for proceedings and uses `\small` for journals

```

1843 \def\@specialsection#1{%
1844   \ifcase\ACM@format@nr
1845     \relax % manuscript
1846     \par\medskip\small\noindent#1: %
1847   \or % acmsmall
1848     \par\medskip\small\noindent#1: %
1849   \or % acmlarge
1850     \par\medskip\small\noindent#1: %
1851   \or % acmtog
1852     \par\medskip\small\noindent#1: %
1853   \or % sigconf
1854     \section*{#1}%
1855   \or % siggraph

```

```

1856 \section*{#1}%
1857 \or % sigplan
1858 \noindentparagraph*{#1:~}%
1859 \or % sigchi
1860 \section*{#1}%
1861 \or % sigchi-a
1862 \section*{#1}%
1863 \fi
1864 }

```

\@printtopmatter The printing of top matter starts a new page and uses the given title box. Note that for sigchi-a we print badges here rather than in \mktitle since we want them in the margins.

```

1865 \def\@printtopmatter{%
1866 \ifx\@startPage\@empty
1867 \gdef\@startPage{1}%
1868 \else
1869 \setcounter{page}{\@startPage}%
1870 \fi
1871 \thispagestyle{firstpagestyle}%
1872 \noindent
1873 \ifcase\ACM@format@nr
1874 \relax % manuscript
1875 \box\mktitle@bx\par
1876 \or % acmsmall
1877 \box\mktitle@bx\par
1878 \or % acmlarge
1879 \box\mktitle@bx\par
1880 \or % acmtog
1881 \twocolumn[\box\mktitle@bx]%
1882 \or % sigconf
1883 \twocolumn[\box\mktitle@bx]%
1884 \or % siggraph
1885 \twocolumn[\box\mktitle@bx]%
1886 \or % sigplan
1887 \twocolumn[\box\mktitle@bx]%
1888 \or % sigchi
1889 \twocolumn[\box\mktitle@bx]%
1890 \or % sigchi-a
1891 \par\box\mktitle@bx\par\bigskip
1892 \if@ACM@badge
1893 \marginpar{\noindent
1894 \ifx\@acmBadgeL@image\@empty\else
1895 \href{\@acmBadgeL@url}{%
1896 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}%
1897 \hskip\@ACM@badge@skip
1898 \fi
1899 \ifx\@acmBadgeR@image\@empty\else
1900 \href{\@acmBadgeR@url}{%
1901 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}%

```

```

1902         \fi}%
1903     \fi
1904 \fi
1905 }

\@mktitle The title of the article
1906 \def\@mktitle{%
1907     \ifcase\ACM@format@nr
1908     \relax % manuscript
1909     \@mktitle@i
1910     \or % acmsmall
1911     \@mktitle@i
1912     \or % acmlarge
1913     \@mktitle@i
1914     \or % acmtog
1915     \@mktitle@i
1916     \or % sigconf
1917     \@mktitle@iii
1918     \or % siggraph
1919     \@mktitle@iii
1920     \or % sigplan
1921     \@mktitle@iii
1922     \or % sigchi
1923     \@mktitle@iii
1924     \or % sigchi-a
1925     \@mktitle@iv
1926     \fi
1927 }

\@titlefont The font to typeset the title
1928 \def\@titlefont{%
1929     \ifcase\ACM@format@nr
1930     \relax % manuscript
1931     \LARGE\sffamily\bfseries
1932     \or % acmsmall
1933     \LARGE\sffamily\bfseries
1934     \or % acmlarge
1935     \LARGE\sffamily\bfseries
1936     \or % acmtog
1937     \Huge\sffamily
1938     \or % sigconf
1939     \Huge\sffamily\bfseries
1940     \or % siggraph
1941     \Huge\sffamily\bfseries
1942     \or % sigplan
1943     \Huge\bfseries
1944     \or % sigchi
1945     \Huge\sffamily\bfseries
1946     \or % sigchi-a
1947     \Huge\bfseries

```

```

1948 \fi}

\@subtitlefont The font to typeset the subtitle
1949 \def\@subtitlefont{\normalsize
1950 \ifcase\ACM@format@nr
1951 \relax % manuscript
1952 \mdseries
1953 \or % acmsmall
1954 \mdseries
1955 \or % acmlarge
1956 \mdseries
1957 \or % acmtog
1958 \LARGE
1959 \or % sigconf
1960 \LARGE\mdseries
1961 \or % siggraph
1962 \LARGE\mdseries
1963 \or % sigplan
1964 \LARGE\mdseries
1965 \or % sigchi
1966 \LARGE\mdseries
1967 \or % sigchi-a
1968 \mdseries
1969 \fi}

\@mktitle@i The version of \mktitle for most journals
1970 \def\@mktitle@i{\hsize=\textwidth
1971 \@ACM@title@width=\hsize
1972 \ifx\@acmBadgeL@image\@empty\else
1973 \advance\@ACM@title@width by -\@ACM@badge@width
1974 \advance\@ACM@title@width by -\@ACM@badge@skip
1975 \fi
1976 \ifx\@acmBadgeR@image\@empty\else
1977 \advance\@ACM@title@width by -\@ACM@badge@width
1978 \advance\@ACM@title@width by -\@ACM@badge@skip
1979 \fi
1980 \setbox\mktitle@bx=\vbox{\noindent\@titlefont
1981 \ifx\@acmBadgeL@image\@empty\else
1982 \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeL@url}{%
1983 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}}%
1984 \hskip\@ACM@badge@skip
1985 \fi
1986 \parbox[t]{\@ACM@title@width}{\raggedright
1987 \@titlefont\noindent
1988 \@title
1989 \ifx\@subtitle\@empty\else
1990 \par\noindent{\@subtitlefont\@subtitle}
1991 \fi}%
1992 \ifx\@acmBadgeR@image\@empty\else
1993 \hskip\@ACM@badge@skip

```



```

1994 \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeR@url}{%
1995 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}%
1996 \fi
1997 \par\bigskip}}%

```

`\@mktitle@ii` The version of `\mktitle` for TOG. Since v1.06, this is subsumed by the `\mktitle@i` macro

`\@mktitle@iii` The version of `\mktitle` for SIG proceedings. Note that since the title is centered, we leave space for the left badge even if only the right badge is defined.

```

1998 \def\@mktitle@iii{\hsize=\textwidth
1999 \setbox\mktitle@bx=\vbox{\@titlefont\centering
2000 \@ACM@title@width=\hsize
2001 \if@ACM@badge
2002 \advance\@ACM@title@width by -2\@ACM@badge@width
2003 \advance\@ACM@title@width by -2\@ACM@badge@skip
2004 \parbox[b]{\@ACM@badge@width}{\strut
2005 \ifx\@acmBadgeL@image\@empty\else
2006 \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeL@url}{%
2007 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeL@image}}}%
2008 \fi}%
2009 \hskip\@ACM@badge@skip
2010 \fi
2011 \parbox[t]{\@ACM@title@width}{\centering\@titlefont
2012 \@title
2013 \ifx\@subtitle\@empty\else
2014 \par\noindent{\@subtitlefont\@subtitle}
2015 \fi
2016 }%
2017 \if@ACM@badge
2018 \hskip\@ACM@badge@skip
2019 \parbox[b]{\@ACM@badge@width}{\strut
2020 \ifx\@acmBadgeR@image\@empty\else
2021 \raisebox{-.5\baselineskip}[\z@][\z@]{\href{\@acmBadgeR@url}{%
2022 \includegraphics[width=\@ACM@badge@width]{\@acmBadgeR@image}}}%
2023 \fi}%
2024 \fi
2025 \par\bigskip}}%

```

`\@mktitle@iv` The version of `\mktitle` for sigchi-a

```

2026 \def\@mktitle@iv{\hsize=\textwidth
2027 \setbox\mktitle@bx=\vbox{\raggedright\leftskip5pc\@titlefont
2028 \noindent\leavevmode\leaders\hrule height 2pt\hfill\kern0pt\par
2029 \noindent\@title
2030 \ifx\@subtitle\@empty\else
2031 \par\noindent\@subtitlefont\@subtitle
2032 \fi
2033 \par\bigskip}}%

```

`\@ACM@addtoaddress` This macro adds an item to the address using the following rules:

1. If we start a paragraph, add the item
2. Otherwise, add a comma and the item
3. However, the comma is deleted if it is at the end of a line. We use the magic `\cleaders` trick for this.

```

2034 \newbox\@ACM@commabox
2035 \def\@ACM@addtoaddress#1{%
2036   \ifvmode\else
2037     \if@ACM@affiliation@obexpunctuation\else
2038     \setbox\@ACM@commabox=\hbox{, }%
2039     \unskip\cleaders\copy\@ACM@commabox\hskip\wd\@ACM@commabox
2040   \fi\fi
2041   #1}

```

```

\institution Theoretically we can define the macros for \affiliation inside the \@mkauthors-style
\position commands. However, this would lead to a strange error if an author uses them outside
\department \affiliation. Of course we can make them produce an error message, but...
\streetaddress 2042 \def\streetaddress#1{\unskip\ignorespaces}
\city 2043 \def\postcode#1{\unskip\ignorespaces}
\state 2044 \if@ACM@journal
\postcode 2045 \def\position#1{\unskip\ignorespaces}
\country 2046 \def\institution#1{\unskip~#1\ignorespaces}
2047 \def\city#1{\unskip\ignorespaces}
2048 \def\state#1{\unskip\ignorespaces}
2049 \newcommand\department[2][0]{\unskip\ignorespaces}
2050 \def\country#1{\if@ACM@affiliation@obexpunctuation\else, \fi#1\ignorespaces}
2051 \else
2052 \def\position#1{\if@ACM@affiliation@obexpunctuation#1\else#1\par\fi}%
2053 \def\institution#1{\if@ACM@affiliation@obexpunctuation#1\else#1\par\fi}%
2054 \newcommand\department[2][0]{\if@ACM@affiliation@obexpunctuation
2055   #2\else#2\par\fi}%
2056 % \def\streetaddress#1{\if@ACM@affiliation@obexpunctuation#1\else#1\par\fi}%
2057 \let\city\@ACM@addtoaddress
2058 \let\state\@ACM@addtoaddress
2059 % \def\postcode#1{\if@ACM@affiliation@obexpunctuation#1\else\unskip\space#1\fi}%
2060 \let\country\@ACM@addtoaddress
2061 \fi

```

```

\@mkauthors Typesetting the authors
2062 \def\@mkauthors{\begingroup
2063   \hsize=\textwidth
2064   \ifcase\ACM@format@nr
2065     \relax % manuscript
2066     \@mkauthors@i
2067   \or % acmsmall
2068     \@mkauthors@i
2069   \or % acmlarge
2070     \@mkauthors@i

```

```

2071 \or % acmtog
2072     \@mkauthors@i
2073 \or % sigconf
2074     \@mkauthors@iii
2075 \or % siggraph
2076     \@mkauthors@iii
2077 \or % sigplan
2078     \@mkauthors@iii
2079 \or % sigchi
2080     \@mkauthors@iii
2081 \or % sigchi-a
2082     \@mkauthors@iv
2083 \fi
2084 \endgroup
2085 }

```

\@authorfont Somehow different conferences use different fonts for author names. Why?

```

2086 \def\@authorfont{\Large\sffamily}

```

\@affiliationfont Font for affiliations

```

2087 \def\@affiliationfont{\normalsize\normalfont}

```

Adjusting fonts for different formats

```

2088 \ifcase\ACM@format@nr
2089 \relax % manuscript
2090 \or % acmsmall
2091     \def\@authorfont{\large\sffamily}
2092     \def\@affiliationfont{\small\normalfont}
2093 \or % acmlarge
2094 \or % acmtog
2095     \def\@authorfont{\LARGE\sffamily}
2096     \def\@affiliationfont{\large}
2097 \or % sigconf
2098     \def\@authorfont{\LARGE}
2099     \def\@affiliationfont{\large}
2100 \or % siggraph
2101     \def\@authorfont{\normalsize\normalfont}
2102     \def\@affiliationfont{\normalsize\normalfont}
2103 \or % sigplan
2104     \def\@authorfont{\Large\normalfont}
2105     \def\@affiliationfont{\normalsize\normalfont}
2106 \or % sigchi
2107     \def\@authorfont{\bfseries}
2108     \def\@affiliationfont{\mdseries}
2109 \or % sigchi-a
2110     \def\@authorfont{\bfseries}
2111     \def\@affiliationfont{\mdseries}
2112 \fi

```

`\typeset@author@line` At this point we have `\@currentauthors` and `\@currentaffiliations`. We typeset them in the journal style

```
2113 \def\@typeset@author@line{%
2114   \andify\@currentauthors\par\noindent
2115   \@currentauthors\def\@currentauthors{%
2116     \ifx\@currentaffiliations\@empty\else
2117       \andify\@currentaffiliations
2118       \unskip, {\@currentaffiliations}\par
2119     \fi
2120   \def\@currentaffiliations{}}
```

`\@mkauthors@i` This version is used in most journal formats. Note that `\and` between authors with the same affiliation becomes `_and_`:

```
2121 \def\@mkauthors@i{%
2122   \def\@currentauthors{%
2123     \def\@currentaffiliations{%
2124       \global\let\and\@typeset@author@line
2125     \def\@author##1{%
2126       \ifx\@currentauthors\@empty
2127         \gdef\@currentauthors{\@authorfont\MakeTextUppercase{##1}}%
2128       \else
2129         \g@addto@macro{\@currentauthors}{\and\MakeTextUppercase{##1}}%
2130       \fi
2131       \gdef\and{}}%
2132     \def\email##1##2{%
2133       \def\affiliation##1##2{%
2134         \def\@tempa{##2}\ifx\@tempa\@empty\else
2135           \ifx\@currentaffiliations\@empty
2136             \gdef\@currentaffiliations{%
2137               \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2138               \setkeys{@ACM@affiliation@}{##1}%
2139               \@affiliationfont##2}%
2140           \else
2141             \g@addto@macro{\@currentaffiliations}{\and
2142               \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2143               \setkeys{@ACM@affiliation@}{##1}##2}%
2144           \fi
2145         \fi
2146         \global\let\and\@typeset@author@line}%
2147       \global\setbox\mktitle@bx=\vbox{\noindent\box\mktitle@bx\par\medskip
2148         \noindent\addresses\@typeset@author@line
2149         \par\medskip}%
2150     }
```

`\@mkauthors@ii` The `\@mkauthors@ii` command was the version used in `acmtog`. It is no longer necessary.

`\author@bx` The box to put an individual author in

```
2151 \newbox\author@bx
```

`\author@bx@wd` The width of the author box
2152 `\newdimen\author@bx@wd`

`\author@bx@sep` The separation between author boxes
2153 `\newskip\author@bx@sep`
2154 `\author@bx@sep=1pc\relax`

`\@typeset@author@bx` Typesetting the box with authors. Note that in sigchi-a the box is not centered.
2155 `\def\@typeset@author@bx{\bgroup\hsize=\author@bx@wd`
2156 `\def\and{\par}\normalbaselines`
2157 `\global\setbox\author@bx=\vtop{\if@ACM@sigchiamode\else\centering\fi`
2158 `\@authorfont\@currentauthors\par\@affiliationfont`
2159 `\@currentaffiliation}\egroup`
2160 `\box\author@bx\hspace{\author@bx@sep}%`
2161 `\gdef\@currentauthors{}`
2162 `\gdef\@currentaffiliation{}}`

`\@mkauthors@iii` The sigconf version. Here we use a centered design with each author in a separate box.
2163 `\def\@mkauthors@iii{%`
First, we need to determine the design of the author strip. The boxes are separated by `\author@bx@sep` plus two `\author@bx@sep` margins. This means that each box must be of width $(\texttt{\textbackslash textwidth} - \texttt{\textbackslash author@bx@sep})/N - \texttt{\textbackslash author@bx@sep}$, where N is the number of boxes per row.
2164 `\author@bx@wd=\textwidth\relax`
2165 `\advance\author@bx@wd by -\author@bx@sep\relax`
2166 `\ifnum\@ACM@authorsprow>0\relax`
2167 `\divide\author@bx@wd by \@ACM@authorsprow\relax`
2168 `\else`
2169 `\ifcase\@num@authorgroups`
2170 `\relax % 0?`
2171 `\or % 1=one author per row`
2172 `\or % 2=two authors per row`
2173 `\divide\author@bx@wd by \@num@authorgroups\relax`
2174 `\or % 3=three authors per row`
2175 `\divide\author@bx@wd by \@num@authorgroups\relax`
2176 `\or % 4=two authors per row (!)`
2177 `\divide\author@bx@wd by 2\relax`
2178 `\else % three authors per row`
2179 `\divide\author@bx@wd by 3\relax`
2180 `\fi`
2181 `\fi`
2182 `\advance\author@bx@wd by -\author@bx@sep\relax`
Now, parsing of `\addresses`:
2183 `\gdef\@currentauthors{}`
2184 `\gdef\@currentaffiliation{}`
2185 `\def\@author##1{\ifx\@currentauthors\@empty`
2186 `\gdef\@currentauthors{\par##1}%`
2187 `\else`

```

2188 \g@addto@macro\@currentauthors{\par##1}%
2189 \fi
2190 \gdef\and{}}%
2191 \def\email##1##2{\ifx\@currentaffiliation\@empty
2192 \gdef\@currentaffiliation{\bgroup
2193 \mathchardef\UrlBreakPenalty=10000\nolinkurl{##2}\egroup}%
2194 \else
2195 \g@addto@macro\@currentaffiliation{\par\bgroup
2196 \mathchardef\UrlBreakPenalty=10000\nolinkurl{##2}\egroup}%
2197 \fi}%
2198 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
2199 \gdef\@currentaffiliation{%
2200 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2201 \setkeys{@ACM@affiliation@}{##1}##2}%
2202 \else
2203 \g@addto@macro\@currentaffiliation{\par
2204 \setkeys{@ACM@affiliation@}{obeypunctuation=false}%
2205 \setkeys{@ACM@affiliation@}{##1}##2}%
2206 \fi
2207 \global\let\and\@typeset@author@bx
2208 }%

```

Actual typesetting is done by the \and macro:

```

2209 \hsize=\textwidth
2210 \global\setbox\mktitle@bx=\vbox{\noindent
2211 \box\mktitle@bx\par\medskip\leavevmode
2212 \lineskip=1pc\relax\centering\hspace*{-1em}%
2213 \addresses\let\and\@typeset@author@bx\and\par\bigskip}}

```

\@mkauthors@iv The sigchi-a version. We put authors in the main text with no more than 2 authors per line, unless overridden.

```

2214 \def\@mkauthors@iv{%

```

First, we need to determine the design of the author strip. The boxes are separated by \author@bx@sep plus two \author@bx@sep margins. This means that each box must be of width $(\text{\textwidth} - \text{\author@bx@sep})/N - \text{\author@bx@sep}$, where N is the number of boxes per row.

```

2215 \author@bx@wd=\columnwidth\relax
2216 \advance\author@bx@wd by -\author@bx@sep\relax
2217 \ifnum\@ACM@authorsperrow>0\relax
2218 \divide\author@bx@wd by \@ACM@authorsperrow\relax
2219 \else
2220 \ifcase\@num@authorgroups
2221 \relax % 0?
2222 \or % 1=one author per row
2223 \else % 2=two authors per row
2224 \divide\author@bx@wd by 2\relax
2225 \fi
2226 \fi
2227 \advance\author@bx@wd by -\author@bx@sep\relax

```

Now, parsing of \addresses:

```

2228 \gdef\@currentauthors{}%
2229 \gdef\@currentaffiliation{}%
2230 \def\@author##1{\ifx\@currentauthors\@empty
2231 \gdef\@currentauthors{\par##1}%
2232 \else
2233 \g@addto@macro\@currentauthors{\par##1}%
2234 \fi
2235 \gdef\and{}}%
2236 \def\email##1##2{\ifx\@currentaffiliation\@empty
2237 \gdef\@currentaffiliation{\nolinkurl{##2}}%
2238 \else
2239 \g@addto@macro\@currentaffiliation{\par\nolinkurl{##2}}%
2240 \fi}%
2241 \def\affiliation##1##2{\ifx\@currentaffiliation\@empty
2242 \gdef\@currentaffiliation{%
2243 \setkeys{@ACM@affiliation@}{obexpunctuation=false}%
2244 \setkeys{@ACM@affiliation@}{##1}##2}%
2245 \else
2246 \g@addto@macro\@currentaffiliation{\par
2247 \setkeys{@ACM@affiliation@}{obexpunctuation=false}%
2248 \setkeys{@ACM@affiliation@}{##1}##2}%
2249 \fi
2250 \global\let\and\@typeset@author@bx}%
2251 %

```

Actual typesetting is done by the \and macro

```

2252 \bgroup\hsize=\columnwidth
2253 \par\raggedright\leftskip=\z@
2254 \lineskip=1pc\noindent
2255 \addresses\let\and\@typeset@author@bx\and\par\bigskip\egroup}

```

\@mkauthorsaddresses Typesetting authors' addresses in the footnote style

```

2256 \def\@mkauthorsaddresses{%
2257 \ifnum\num@authors>1\relax
2258 Authors' \else Author's \fi
2259 \ifnum\num@authorgroups>1\relax
2260 addresses: \else address: \fi
2261 \bgroup
2262 \def\streetaddress##1{\unskip, ##1}%
2263 \def\postcode##1{\unskip, ##1}%
2264 \def\position##1{\unskip\ignorespaces}%
2265 \def\institution##1{\unskip, ##1}%
2266 \def\city##1{\unskip, ##1}%
2267 \def\state##1{\unskip, ##1}%
2268 \renewcommand\department[2][0]{\unskip\@addpunct, ##2}%
2269 \def\country##1{\unskip, ##1}%
2270 \def\and{\unskip; }%
2271 \def\@author##1{##1}%
2272 \def\email##1##2{\unskip, \nolinkurl{##2}}%

```

```

2273 \addresses
2274 \egroup}

2275 \AtEndDocument{\if@ACM@nonacm\else\if@ACM@journal
2276 \ifx\@authorsaddresses\@empty
2277 \ClassWarningNoLine{\@classname}{Authors'
2278 addresses are mandatory for ACM journals}%
2279 \fi\fi\fi}

\@setaddresses This is an amsart macro that we do not need.
2280 \def\@setaddresses{}

\@authornotemark Adding a footnote mark to authors. This version adds a “normal” footnote mark.
2281 \def\@authornotemark{\g@addto@macro\@currentauthors{\footnotemark\relax}}

\@@authornotemark Adding a footnote mark to authors with a given number
2282 \def\@@authornotemark#1{\g@addto@macro\@currentauthors{\footnotemark[#1]}}

\@mkteasers Typesetting the teasers
2283 \def\@mkteasers{%
2284 \ifx\@teaserfigures\@empty\else
2285 \def\@teaser##1{\par\bigskip\bgroup
2286 \captionsetup{type=figure}##1\egroup\par}
2287 \global\setbox\mktitle@bx=\vbox{\noindent\box\mktitle@bx\par
2288 \noindent\@Description@presentfalse
2289 \@teaserfigures\par\if@Description@present\else
2290 \global\@undescrbed@imagestrue
2291 \ClassWarning{\@classname}{A possible image without
2292 description}\fi
2293 \medskip}%
2294 \fi}

\@mkabstract Typesetting the abstract
2295 \def\@mkabstract{\bgroup
2296 \ifx\@abstract\@empty\else
2297 {\phantomsection\addcontentsline{toc}{section}{Abstract}%
2298 \if@ACM@journal
2299 \everypar{\setbox\z@\lastbox\everypar{}}\small
2300 \else
2301 \section*{\abstractname}%
2302 \fi
2303 \ignorespaces\@abstract\par}%
2304 \fi\egroup}

\@mkbibcitation Print the bibcitation format
2305 \def\@mkbibcitation{\bgroup
2306 \let\@vspace\@vspace@orig
2307 \let\@vspacer\@vspacer@orig
2308 \def\@pages@word{\ifnum\getrefnumber{TotPages}=1\relax page\else pages\fi}%

```



```

2309 \def\footnotemark{}%
2310 \def\{\unskip{} \ignorespaces}%
2311 \def\footnote{\ClassError{\@classname}{Please do not use footnotes
2312     inside a \string\title{} or \string\author{} command! Use
2313     \string\titlenote{} or \string\authornote{} instead!}}%
2314 \def\@article@string{\ifx\@acmArticle\@empty{\ } \else,
2315     Article~\@acmArticle\ }%
2316 \par\medskip\small\noindent{\bfseries ACM Reference Format:}\par\nobreak
2317 \noindent\bgroup
2318     \def\{\unskip{}, \ignorespaces}\authors\egroup. \@acmYear. \@title
2319     \ifx\@subtitle\@empty. \else: \@subtitle. \fi
2320     \if@ACM@nonacm\else
2321         % The 'nonacm' option disables 'printacmref' by default,
2322         % and the present \mkbibcitation definition is never used
2323         % in this case. The conditional remains useful if the user
2324         % explicitly sets \settopmatter{printacmref=true}.
2325         \if@ACM@journal@bibstrip
2326             \textit{\@journalNameShort}
2327             \@acmVolume, \@acmNumber \@article@string (\@acmPubDate),
2328             \ref{TotPages}~\@pages@word.
2329         \else
2330             In \textit{\@acmBooktitle}%
2331             \ifx\@acmEditors\@empty\textit{.}\else
2332                 \andify\@acmEditors\textit{, }\@acmEditors~\@editorsAbbrev.%
2333             \fi\
2334             ACM, New York, NY, USA%
2335             \@article@string\unskip, \ref{TotPages}~\@pages@word.
2336         \fi
2337     \fi
2338     \ifx\@acmDOI\@empty\else\@formatdoi{\@acmDOI}\fi
2339 \par\egroup}

```

\@printendtopmatter End the top matter

```

2340 \def\@printendtopmatter{%
2341     \let\@vspace\@vspace@orig
2342     \let\@vspacer\@vspacer@orig
2343     \par\bigskip
2344     \let\@vspace\@vspace@acm
2345     \let\@vspacer\@vspacer@acm
2346 }

```

\@setthanks We redefine \setthanks using \long

```

2347 \def\@setthanks{\long\def\thanks##1{\par##1\@addpunct.}\thankses}

```

\@setauthorsaddresses

```

2348 \def\@setauthorsaddresses{\@authorsaddresses\unskip\@addpunct.}

```

3.16 Headers and Footers

We use fancyhdr for our headers and footers:

```
2349 \RequirePackage{fancyhdr}
```

`\ACM@restore@pagestyle` The following code by Ross Moore protects against changes by the `totpages` package:

```
2350 \let\ACM@ps@plain\ps@plain
2351 \let\ACM@ps@myheadings\ps@myheadings
2352 \let\ACM@ps@headings\ps@headings
2353 \def\ACM@restore@pagestyle{%
2354   \let\ps@plain\ACM@ps@plain
2355   \let\ps@myheadings\ACM@ps@myheadings
2356   \let\ps@headings\ACM@ps@headings}
2357 \AtBeginDocument{\ACM@restore@pagestyle}
```

`\ACM@linecount@bx` This is the box displayed in review mode

```
2358 \if@ACM@review
2359   \newsavebox{\ACM@linecount@bx}
2360   \newlength\ACM@linecount@bxht
2361   \newcount\ACM@linecount
2362   \ACM@linecount\@ne\relax
2363   \def\ACM@mk@linecount{%
2364     \savebox{\ACM@linecount@bx}[4em][t]{\parbox[t]{4em}{\normalfont
2365       \normalsize
2366       \setlength{\ACM@linecount@bxht}{0pt}%
2367       \loop{\color{red}\scriptsize\the\ACM@linecount}\\
2368         \global\advance\ACM@linecount by \@ne
2369         \addtolength{\ACM@linecount@bxht}{\baselineskip}%
2370         \ifdim\ACM@linecount@bxht<\textheight\repeat
2371         {\color{red}\scriptsize\the\ACM@linecount}\hfill
2372         \global\advance\ACM@linecount by \@ne}}}%
2373   \fi
```

`\ACM@linecountL` How to display the box on the left

```
2374 \def\ACM@linecountL{%
2375   \if@ACM@review
2376     \ACM@mk@linecount
2377     \begin{picture}(0,0)%
2378       \put(-26,-22){\usebox{\ACM@linecount@bx}}%
2379     \end{picture}%
2380   \fi}
```

`\ACM@linecountR` How to display the box on the right. In one column formats we do not step the numbers.

```
2381 \def\ACM@linecountR{%
2382   \if@ACM@review
2383     \ifcase\ACM@format@nr
2384       \relax % manuscript
2385       \relax
2386     \or % acmsmall
2387       \relax
2388     \or % acmlarge
2389       \relax
```

```

2390 \or % acmtog
2391 \ACM@mk@linecount
2392 \or % sigconf
2393 \ACM@mk@linecount
2394 \or % siggraph
2395 \ACM@mk@linecount
2396 \or % sigplan
2397 \ACM@mk@linecount
2398 \or % sigchi
2399 \ACM@mk@linecount
2400 \or % sigchi-a
2401 \ACM@mk@linecount
2402 \fi
2403 \begin{picture}(0,0)%
2404 \put(20,-22){\usebox{\ACM@linecount@bx}}%
2405 \end{picture}%
2406 \fi}

```

\ACM@timestamp The timestamp system

```

2407 \if@ACM@timestamp
2408 % Subtracting 30 from \time gives us the effect of rounding down despite
2409 % \numexpr rounding to nearest
2410 \newcounter{ACM@time@hours}
2411 \setcounter{ACM@time@hours}{\numexpr (\time - 30) / 60 \relax}
2412 \newcounter{ACM@time@minutes}
2413 \setcounter{ACM@time@minutes}{\numexpr \time - \theACM@time@hours * 60 \relax}
2414 \newcommand\ACM@timestamp{%
2415 \footnotesize%
2416 \ifx\@acmSubmissionID\@empty\relax\else
2417 Submission ID: \@acmSubmissionID.{ }%
2418 \fi
2419 \the\year-\two@digits{\the\month}-\two@digits{\the\day}{ }%
2420 \two@digits{\theACM@time@hours}:\two@digits{\theACM@time@minutes}{. }%
2421 Page \thepage\ of \@startPage--\pageref*{TotPages}.%
2422 }
2423 \fi

```

\@shortauthors Even if the author redefined \shortauthors, we do not print it in the headers when in anonymous mode:

```

2424 \def\@shortauthors{%
2425 \if@ACM@anonymous
2426 Anon.
2427 \ifx\@acmSubmissionID\@empty\else Submission Id: \@acmSubmissionID\fi
2428 \else\shortauthors\fi}

```

\@headfootfont The font to typeset header and footer text.

```

2429 \def\@headfootfont{\sfamily\footnotesize}

```

standardpagestyle The page style for all pages but the first one The page style for all pages but the first one

```

2430 \AtBeginDocument{%
2431 \fancypagestyle{standardpagestyle}{%
2432 \fancyhf{}%
2433 \renewcommand{\headrulewidth}{\z@}%
2434 \renewcommand{\footrulewidth}{\z@}%
2435 \def\@acmArticlePage{%
2436 \ifx\@acmArticle\empty%
2437 \if@ACM@printfolios\thepage\fi%
2438 \else%
2439 \@acmArticle\if@ACM@printfolios:\thepage\fi%
2440 \fi%
2441 }%
2442 \if@ACM@journal@bibstrip
2443 \ifcase\ACM@format@nr
2444 \relax % manuscript
2445 \fancyhead[LE]{\ACM@linecountL\if@ACM@printfolios\thepage\fi}%
2446 \fancyhead[RO]{\if@ACM@printfolios\thepage\fi}%
2447 \fancyhead[RE]{\@shortauthors}%
2448 \fancyhead[LO]{\ACM@linecountL\shorttitle}%
2449 \if@ACM@nonacm\else%
2450 \fancyfoot[RO,LE]{\footnotesize Manuscript submitted to ACM}
2451 \fi%
2452 \or % acmsmall
2453 \fancyhead[LE]{\ACM@linecountL\@headfootfont\@acmArticlePage}%
2454 \fancyhead[RO]{\@headfootfont\@acmArticlePage}%
2455 \fancyhead[RE]{\@headfootfont\@shortauthors}%
2456 \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2457 \if@ACM@nonacm\else%
2458 \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2459 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2460 \fi
2461 \or % acmlarge
2462 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2463 \@acmArticlePage\quad\textbullet\quad\@shortauthors}%
2464 \fancyhead[LO]{\ACM@linecountL}%
2465 \fancyhead[RO]{\@headfootfont
2466 \shorttitle\quad\textbullet\quad\@acmArticlePage}%
2467 \if@ACM@nonacm\else%
2468 \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2469 \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2470 \fi
2471 \or % acmtog
2472 \fancyhead[LE]{\ACM@linecountL\@headfootfont
2473 \@acmArticlePage\quad\textbullet\quad\@shortauthors}%
2474 \fancyhead[LO]{\ACM@linecountL}%
2475 \fancyhead[RE]{\ACM@linecountR}%
2476 \fancyhead[RO]{\@headfootfont
2477 \shorttitle\quad\textbullet\quad\@acmArticlePage\ACM@linecountR}%
2478 \if@ACM@nonacm\else%
2479 \fancyfoot[RO,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.

```

```

2480      \@acmNumber, Article \@acmArticle. Publication date: \@acmPubDate.}%
2481      \fi
2482  \else % Proceedings
2483      \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2484      \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2485      \fancyhead[RE]{\@headfootfont\@shortauthors\ACM@linecountR}%
2486      \if@ACM@nonacm\else%
2487          \fancyhead[LE]{\ACM@linecountL\@headfootfont\footnotesize
2488              \acmConference@shortname,
2489              \acmConference@date, \acmConference@venue}%
2490          \fancyhead[RO]{\@headfootfont
2491              \acmConference@shortname,
2492              \acmConference@date, \acmConference@venue\ACM@linecountR}%
2493      \fi
2494  \fi
2495  \else % Proceedings
2496      \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2497      \fancyhead[LO]{\ACM@linecountL\@headfootfont\shorttitle}%
2498      \fancyhead[RE]{\@headfootfont\@shortauthors\ACM@linecountR}%
2499      \if@ACM@nonacm\else%
2500          \fancyhead[LE]{\ACM@linecountL\@headfootfont
2501              \acmConference@shortname,
2502              \acmConference@date, \acmConference@venue}%
2503          \fancyhead[RO]{\@headfootfont
2504              \acmConference@shortname,
2505              \acmConference@date, \acmConference@venue\ACM@linecountR}%
2506      \fi
2507  \fi
2508  \if@ACM@sigchiamode
2509      \fancyheadoffset[L]{\dimexpr(\marginparsep+\marginparwidth)}%
2510  \fi
2511  \if@ACM@timestamp
2512      \fancyfoot[LO,RE]{\ACM@timestamp}
2513  \fi
2514 }%
2515 \pagestyle{standardpagestyle}
2516 }

\@folio@wd Folio blob width, height, offsets and max number
\@folio@ht
\@folio@voffset
\@folio@max
2517 \newdimen\@folio@wd
2518 \@folio@wd=\z@
2519 \newdimen\@folio@ht
2520 \@folio@ht=\z@
2521 \newdimen\@folio@voffset
2522 \@folio@voffset=\z@
2523 \def\@folio@max{1}
2524 \ifcase\ACM@format@nr
2525 \relax % manuscript
2526 \or % acmsmall
2527 \@folio@wd=45.75pt\relax

```

```

2528 \@folio@ht=1.25in\relax
2529 \@folio@voffset=.2in\relax
2530 \def\@folio@max{8}
2531 \or % acmlarge
2532 \@folio@wd=43.25pt\relax
2533 \@folio@ht=79pt\relax
2534 \@folio@voffset=.55in\relax
2535 \def\@folio@max{10}
2536 \fi

```

`\@folioblob` The macro to typeset the folio blob.

```

2537 \def\@folioblob{\@tempcnta=0\@acmArticleSeq\relax
2538 \ifnum\@tempcnta=0\relax\else
First, we calculate \@acmArticleSeq modulo \@folio@max
2539 \loop
2540 \ifnum\@tempcnta>\@folio@max\relax
2541 \advance\@tempcnta by - \@folio@max
2542 \repeat
2543 \advance\@tempcnta by -1\relax
2544 \@tempdima=\@folio@ht\relax
2545 \multiply\@tempdima by \the\@tempcnta\relax
2546 \advance\@tempdima by -\@folio@voffset\relax
2547 \begin{picture}(0,0)
2548 \makebox[\z@]{\raisebox{-\@tempdima}{%
2549 \rlap{%
2550 \raisebox{-0.45\@folio@ht}{\z@}\z@}{%
2551 \rule{\@folio@wd}{\@folio@ht}}}%
2552 \parbox{\@folio@wd}{%
2553 \centering
2554 \textcolor{white}{\LARGE\sffamily\bfseries\@acmArticle}}}}
2555 \end{picture}\fi}
2556

```

`firstpagestyle` The page style for the first page only.

```

2557 \AtBeginDocument{%
2558 \fancypagestyle{firstpagestyle}{%
2559 \fancyhf{}%
2560 \renewcommand{\headrulewidth}{\z@}%
2561 \renewcommand{\footrulewidth}{\z@}%
2562 \if@ACM@journal@bibstrip
2563 \ifcase\ACM@format@nr
2564 \relax % manuscript
2565 \fancyhead[L]{\ACM@linecountL}%
2566 \fancyfoot[RO,LE]{\if@ACM@printfolios\small\thepage\fi}%
2567 \if@ACM@nonacm\else%
2568 \fancyfoot[RE,LO]{\footnotesize Manuscript submitted to ACM}%
2569 \fi%
2570 \or % acmsmall
2571 \if@ACM@nonacm\else%

```

```

2572 \fancyfoot[R0,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2573 \acmNumber, Article \@acmArticle. Publication date:
2574 \@acmPubDate.}%
2575 \fi%
2576 \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2577 \fancyhead[LO]{\ACM@linecountL}%
2578 \fancyhead[R0]{\@folioblob}%
2579 \fancyheadoffset[R0,LE]{0.6\@folio@wd}%
2580 \or % acmlarge
2581 \if@ACM@nonacm\else%
2582 \fancyfoot[R0,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2583 \acmNumber, Article \@acmArticle. Publication date:
2584 \@acmPubDate.}%
2585 \fi%
2586 \fancyhead[R0]{\@folioblob}%
2587 \fancyhead[LE]{\ACM@linecountL\@folioblob}%
2588 \fancyhead[LO]{\ACM@linecountL}%
2589 \fancyheadoffset[R0,LE]{1.4\@folio@wd}%
2590 \or % acmtog
2591 \if@ACM@nonacm\else%
2592 \fancyfoot[R0,LE]{\footnotesize \@journalNameShort, Vol. \@acmVolume, No.
2593 \acmNumber, Article \@acmArticle. Publication date:
2594 \@acmPubDate.}%
2595 \fi%
2596 \fancyhead[L]{\ACM@linecountL}%
2597 \fancyhead[R]{\ACM@linecountR}%
2598 \else % Conference proceedings
2599 \fancyhead[L]{\ACM@linecountL}%
2600 \fancyhead[R]{\ACM@linecountR}%
2601 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2602 \fi
2603 \else
2604 \fancyhead[L]{\ACM@linecountL}%
2605 \fancyhead[R]{\ACM@linecountR}%
2606 \fancyfoot[C]{\if@ACM@printfolios\footnotesize\thepage\fi}%
2607 \fi
2608 \if@ACM@timestamp
2609 \ifnum\ACM@format@nr=0\relax % Manuscript
2610 \fancyfoot[LO,RE]{\ACM@timestamp\quad
2611 \if@ACM@nonacm\else
2612 \footnotesize Manuscript submitted to ACM
2613 \fi}
2614 \else
2615 \fancyfoot[LO,RE]{\ACM@timestamp}
2616 \fi
2617 \fi
2618 }}

```

3.17 Sectioning

`\ACM@NRadjust` Ross Moore's macro.

Initially `\ACM@sect@format@` just passes through its #1 argument unchanged. When a sectioning macro such as `\section` occurs, the `\ACM@NRadjust` redefines `\ACM@sect@format@` to expand into the styling commands; e.g., `\@secfont`. Then `\Sectionformat` is temporarily redefined to produce `\realSectionformat{\ACM@sect@format{#1}}{#2}`, which ultimately becomes `\Sectionformat{\@secfont{#1}}{#2}`. This is done to allow `\Sectionformat` to be variable, as may be needed in particular circumstances. Its current expansion is saved as `\realSectionformat` which is used with the modified 1st argument, then `\Sectionformat` is reverted to its former expansion.

To style the section-number, the line `#1{}` is used at the end of `\ACM@NRadjust`. This imposes style-changing commands for fonts and sizes, but any `\MakeUppercase` acts on just the `{}`. It's a bit hacky, by essentially assuming that only numbers occur here, not letters to be case-changed. (This should be acceptable in a class-file, as it ought to be possible to change the case elsewhere, if that was ever desired.) Also, it can result in `\@adddotafter` being called too soon, so a slight adjustment is made, via `\ACM@adddotafter`, which now tests whether its argument is empty. But the coding has to allow for other packages to have also patched `\@adddotafter`.

```

2619 \def\ACM@NRadjust#1{%
2620   \begingroup
2621   \expandafter\ifx\csname Sectionformat\endcsname\relax
2622   % do nothing when \Sectionformat is unknown
2623   \def\next{\endgroup #1}%
2624   \else
2625   \def\next{\endgroup
2626     \let\realSectionformat\Sectionformat
2627     \def\ACM@sect@format@{#1}%
2628     \let\Sectionformat\ACM@NR@adjustedSectionformat
2629   %% next lines added 2018-06-17 to ensure section number is styled
2630     \let\real@adddotafter\@adddotafter
2631     \let\@adddotafter\ACM@adddotafter
2632     #1{}% imposes the styles, but nullifies \MakeUppercase
2633     \let\@adddotafter\real@adddotafter
2634   }%
2635   \fi \next
2636 }
```

`\ACM@NR@adjustedSectionformat`

```

2637 \def\ACM@NR@adjustedSectionformat#1#2{%
2638   \realSectionformat{\ACM@sect@format{#1}}{#2}%
2639   \let\Sectionformat\realSectionformat}
2640 \DeclareRobustCommand{\ACM@sect@format}{\ACM@sect@format@}
2641 \def\ACM@sect@format@null#1{#1}
2642 \let\ACM@sect@format@\ACM@sect@format@null
```



```

2643 \AtBeginDocument{%
2644   \expandafter\ifx\csname LTX@adddotafter\endcsname\relax
2645   \let\LTX@adddotafter\@adddotafter
2646   \fi
2647 }

```

\ACM@adddotafter

```

2648 \def\ACM@adddotafter#1{\ifx\relax#1\relax\else\LTX@adddotafter{#1}\fi}

```

Sectioning is different for different levels

```

2649 \renewcommand\section{\@startsection{section}{1}{\z@}%
2650   {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2651   {.25\baselineskip}%
2652   {\ACM@NRadjust\@secfont}}
2653 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
2654   {- .75\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2655   {.25\baselineskip}%
2656   {\ACM@NRadjust\@subsecfont}}
2657 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
2658   {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2659   {-3.5\p@}%
2660   {\ACM@NRadjust{\@subsubsecfont\@adddotafter}}}
2661 \renewcommand\paragraph{\@startsection{paragraph}{4}{\parindent}%
2662   {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2663   {-3.5\p@}%
2664   {\ACM@NRadjust{\@parfont\@adddotafter}}}
2665 \newcommand\noindentparagraph{\@startsection{paragraph}{4}{\z@}%
2666   {- .5\baselineskip \@plus -2\p@ \@minus -.2\p@}%
2667   {-3.5\p@}%
2668   {\ACM@NRadjust{\@parfont}}}
2669
2670 \renewcommand\part{\@startsection{part}{9}{\z@}%
2671   {-10\p@ \@plus -4\p@ \@minus -2\p@}%
2672   {4\p@}%
2673   {\ACM@NRadjust{\@parfont}}}

```

\section@raggedright Special version of \raggedright compatible with \MakeUppercase

```

2674 \def\section@raggedright{\@rightskip\@flushglue
2675   \rightskip\@rightskip
2676   \leftskip\z@skip
2677   \parindent\z@}

```

\@secfont Fonts for sections etc. are different for different formats.

```

\@subsecfont 2678 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
\@subsubsecfont 2679 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
\@parfont 2680 \def\@subsubsecfont{\sffamily\itshape}
2681 \def\@parfont{\itshape}
2682 \setcounter{secnumdepth}{3}
2683 \ifcase\ACM@format@nr

```

```

2684 \relax % manuscript
2685 \or % acmsmall
2686 \or % acmlarge
2687 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2688 \def\@subsecfont{\sffamily\large\section@raggedright}
2689 \or % acmtog
2690 \def\@secfont{\sffamily\large\section@raggedright\MakeTextUppercase}
2691 \def\@subsecfont{\sffamily\large\section@raggedright}
2692 \or % sigconf
2693 \def\@secfont{\bfseries\Large\section@raggedright\MakeTextUppercase}
2694 \def\@subsecfont{\bfseries\Large\section@raggedright}
2695 \or % siggraph
2696 \def\@secfont{\sffamily\bfseries\Large\section@raggedright\MakeTextUppercase}
2697 \def\@subsecfont{\sffamily\bfseries\Large\section@raggedright}
2698 \or % sigplan
2699 \def\@secfont{\bfseries\Large\section@raggedright}
2700 \def\@subsecfont{\bfseries\section@raggedright}
2701 \def\@subsubsecfont{\bfseries\section@raggedright}
2702 \def\@parfont{\bfseries\itshape}
2703 \def\@subparfont{\itshape}
2704 \or % sigchi
2705 \setcounter{secnumdepth}{1}
2706 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
2707 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2708 \or % sigchi-a
2709 \setcounter{secnumdepth}{0}
2710 \def\@secfont{\sffamily\bfseries\section@raggedright\MakeTextUppercase}
2711 \def\@subsecfont{\sffamily\bfseries\section@raggedright}
2712 \fi

```

\@adddotafter Add punctuation after a sectioning command

```
2713 \def\@adddotafter#1{#1\@addpunct{.}}
```

\@addspaceafter Add space after a sectioning command

```
2714 \def\@addspaceafter#1{#1\@addpunct{\enspace}}
```

3.18 TOC lists

\@dotsep Related to the \tableofcontents are all the horizontal fillers. Base \TeX defines \@dottedtocline, which we should not disable. Yet, this command expects \@dotsep to be defined but leaves this to the class implementation. Since amsart does not provide this, we copy the standard variant from article here.

```
2715 \providecommand*\@dotsep{4.5}
```

3.19 Theorems

\@acmplainbodyfont The font to typeset the body of the acmplain theorem style.

```
2716 \def\@acmplainbodyfont{\itshape}
```

`\acmplainindent` The amount to indent the acmplain theorem style.

```
2717 \def\acmplainindent{\parindent}
```

`\acmplainheadfont` The font to typeset the head of the acmplain theorem style.

```
2718 \def\acmplainheadfont{\scshape}
```

`\acmplainnotefont` The font to typeset the note of the acmplain theorem style.

```
2719 \def\acmplainnotefont{\@empty}
```

Customization of the acmplain theorem style:

```
2720 \ifcase\ACM@format@nr
```

```
2721 \relax % manuscript
```

```
2722 \or % acmsmall
```

```
2723 \or % acmlarge
```

```
2724 \or % acmtog
```

```
2725 \or % sigconf
```

```
2726 \or % siggraph
```

```
2727 \or % sigplan
```

```
2728 \def\acmplainbodyfont{\itshape}
```

```
2729 \def\acmplainindent{\z@}
```

```
2730 \def\acmplainheadfont{\bfseries}
```

```
2731 \def\acmplainnotefont{\normalfont}
```

```
2732 \or % sigchi
```

```
2733 \or % sigchi-a
```

```
2734 \fi
```

`acmplain` The acmplain theorem style

```
2735 \newtheoremstyle{acmplain}%
```

```
2736 { .5\baselineskip\@plus.2\baselineskip
```

```
2737 \@minus.2\baselineskip}% space above
```

```
2738 { .5\baselineskip\@plus.2\baselineskip
```

```
2739 \@minus.2\baselineskip}% space below
```

```
2740 {\acmplainbodyfont}% body font
```

```
2741 {\acmplainindent}% indent amount
```

```
2742 {\acmplainheadfont}% head font
```

```
2743 { .}% punctuation after head
```

```
2744 { .5em}% spacing after head
```

```
2745 {\thmname{#1}\thmnumber{ #2}\thmnote{ {\acmplainnotefont{#3}}}% head spec
```

`\acmdefinitionbodyfont` The font to typeset the body of the acmdefinition theorem style.

```
2746 \def\acmdefinitionbodyfont{\normalfont}
```

`\acmdefinitionindent` The amount to indent the acmdefinition theorem style.

```
2747 \def\acmdefinitionindent{\parindent}
```

`\acmdefinitionheadfont` The font to typeset the head of the acmdefinition theorem style.

```
2748 \def\acmdefinitionheadfont{\itshape}
```

`\@acmdefinitionnotefont` The font to typeset the note of the acmdefinition theorem style.

```
2749 \def\@acmdefinitionnotefont{\@empty}
```

Customization of the acmdefinition theorem style:

```
2750 \ifcase\ACM@format@nr
2751 \relax % manuscript
2752 \or % acmsmall
2753 \or % acmlarge
2754 \or % acmtog
2755 \or % sigconf
2756 \or % siggraph
2757 \or % sigplan
2758 \def\@acmdefinitionbodyfont{\normalfont}
2759 \def\@acmdefinitionindent{\z@}
2760 \def\@acmdefinitionheadfont{\bfseries}
2761 \def\@acmdefinitionnotefont{\normalfont}
2762 \or % sigchi
2763 \or % sigchi-a
2764 \fi
```

`acmdefinition` The acmdefinition theorem style

```
2765 \newtheoremstyle{acmdefinition}%
2766 { .5\baselineskip\@plus.2\baselineskip
2767   \@minus.2\baselineskip}% space above
2768 { .5\baselineskip\@plus.2\baselineskip
2769   \@minus.2\baselineskip}% space below
2770 {\@acmdefinitionbodyfont}% body font
2771 {\@acmdefinitionindent}% indent amount
2772 {\@acmdefinitionheadfont}% head font
2773 { .}% punctuation after head
2774 { .5em}% spacing after head
2775 {\thmname{#1}\thmnumber{ #2}\thmnote{ \@acmdefinitionnotefont{#3}}}% head spec
```

Make acmplain the default theorem style.

```
2776 \theoremstyle{acmplain}
```

Delay defining the theorem environments until after other packages have been loaded. In particular, the `cleveref` package must be loaded before the theorem environments are defined in order to show the correct environment name (see <https://github.com/borisveytsman/acmart/issues/138>). The `acmthm` option is used to suppress the definition of any theorem environments. Also, to avoid obscure errors arising from these environment definitions conflicting with environments defined by the user or by user-loaded packages, we only define environments that have not yet been defined.

```
2777 \AtEndPreamble{%
2778   \if@ACM@acmthm
2779   \theoremstyle{acmplain}
2780   \@ifundefined{theorem}{%
2781     \newtheorem{theorem}{Theorem}[section]}
```

```

2782 }{}
2783 \@ifundefined{conjecture}{%
2784 \newtheorem{conjecture}[theorem]{Conjecture}
2785 }{}
2786 \@ifundefined{proposition}{%
2787 \newtheorem{proposition}[theorem]{Proposition}
2788 }{}
2789 \@ifundefined{lemma}{%
2790 \newtheorem{lemma}[theorem]{Lemma}
2791 }{}
2792 \@ifundefined{corollary}{%
2793 \newtheorem{corollary}[theorem]{Corollary}
2794 }{}
2795 \theoremstyle{acmdefinition}
2796 \@ifundefined{example}{%
2797 \newtheorem{example}[theorem]{Example}
2798 }{}
2799 \@ifundefined{definition}{%
2800 \newtheorem{definition}[theorem]{Definition}
2801 }{}
2802 \fi
2803 \theoremstyle{acmplain}
2804 }

\@proofnamefont The font to typeset the proof name.
2805 \def\@proofnamefont{\scshape}

\@proofindent Whether or not to indent proofs.
2806 \def\@proofindent{\indent}

Customization of the proof environment.
2807 \ifcase\ACM@format@nr
2808 \relax % manuscript
2809 \or % acmsmall
2810 \or % acmlarge
2811 \or % acmtog
2812 \or % sigconf
2813 \or % siggraph
2814 \or % sigplan
2815 \def\@proofnamefont{\itshape}
2816 \def\@proofindent{\noindent}
2817 \or % sigchi
2818 \or % sigchi-a
2819 \fi

proof We want some customization of the proof environment.
2820 \renewenvironment{proof}[1][\proofname]{\par
2821 \pushQED{\qed}%
2822 \normalfont \topsep6\p@\@plus6\p@\relax

```

```

2823 \trivlist
2824 \item[@proofindent\hskip\labelsep
2825       {\@proofnamefont #1\@addpunct{.}}]\ignorespaces
2826 }{%
2827 \popQED\endtrivlist\endpfalse
2828 }

```

3.20 Balancing columns

We need balancing only if the user did not disable it, and we use a two column format

```

2829 \AtEndPreamble{%
2830 \if@ACM@balance
2831 \ifcase\ACM@format@nr
2832 \relax % manuscript
2833 \global\@ACM@balancefalse
2834 \or % acmsmall
2835 \global\@ACM@balancefalse
2836 \or % acmlarge
2837 \global\@ACM@balancefalse
2838 \or % acmtog
2839 \RequirePackage{balance}%
2840 \or % sigconf
2841 \RequirePackage{balance}%
2842 \or % siggraph
2843 \RequirePackage{balance}%
2844 \or % sigplan
2845 \RequirePackage{balance}%
2846 \or % sigchi
2847 \RequirePackage{balance}%
2848 \or % sigchi-a
2849 \global\@ACM@balancefalse
2850 \fi
2851 \fi
2852 }
2853 \AtEndDocument{%
2854 \if@ACM@balance
2855 \if@twocolumn
2856 \balance
2857 \fi\fi}

```

3.21 Acknowledgments

```

\acksname
2858 \newcommand\acksname{Acknowledgments}

\acks This is a comment-like structure
2859 \specialcomment{acks}{%
2860 \begin{group}
2861 \section*{\acksname}

```

```

2862 \phantomsection\addcontentsline{toc}{section}{\acksname}
2863 }{%
2864 \endgroup
2865 }

```

`\grantsponsor` We just typeset the name of the sponsor

```
2866 \def\grantsponsor#1#2#3{#2}
```

`\grantnum`

```

2867 \newcommand\grantnum[3][[]]{#3%
2868 \def\@tempa{#1}\ifx\@tempa\empty\else\space(\url{#1})\fi}

```

3.22 Conditional typesetting

We use the comment package for conditional typesetting:

```

2869 \AtEndPreamble{%
2870 \if@ACM@screen
2871 \includecomment{screenonly}
2872 \excludecomment{printonly}
2873 \else
2874 \excludecomment{screenonly}
2875 \includecomment{printonly}
2876 \fi
2877 \if@ACM@anonymous
2878 \excludecomment{anonsuppress}
2879 \excludecomment{acks}
2880 \else
2881 \includecomment{anonsuppress}
2882 \fi}

```

3.23 Additional bibliography commands

`\showeprint` The command `\showeprint` has two arguments: the (optional) prefix and the eprint number. Right now the only prefix we understand is the (lowercase) word ‘arxiv’ (see <http://arxiv.org/hypertex/bibstyles/>).

```

2883 \newcommand\showeprint[2][arxiv]{%
2884 \def\@tempa{#1}%
2885 \ifx\@tempa\empty\def\@tempa{arxiv}\fi
2886 \def\@tempb{arxiv}%
2887 \ifx\@tempa\@tempb
2888 arXiv:\href{http://arxiv.org/abs/#2}{#2}\else arXiv:#2%
2889 \fi}

```

3.24 End of Class

`\vspace` We do not disable `\vspace`, but add warning to it

```

2890 \let\vspace@orig=\vspace
2891 \let\vspacer@orig=\vspacer

```

```

2892 \apptocmd{\@vspace}{\ClassWarning{\@classname}{\string\vspace\space should
2893     only be used to provide space above/below surrounding
2894     objects}}{}{}
2895 \apptocmd{\@vspacer}{\ClassWarning{\@classname}{\string\vspace\space should
2896     only be used to provide space above/below surrounding
2897     objects}}{}{}
2898 \let\@vspace@acm=\@vspace
2899 \let\@vspacer@acm=\@vspacer

```

```

\ACM@origbaselinestretch We produce an error if the user tries to change \baselinestretch
2900 \let\ACM@origbaselinestretch\baselinestretch
2901 \AtEndDocument{\ifx\baselinestretch\ACM@origbaselinestretch\else
2902     \ClassError{\@classname}{An attempt to redefine
2903         \string\baselinestretch\space detected. Please do not do this for
2904         ACM submissions!}\fi}

2905 \normalsize\normalfont\frenchspacing
2906 \end{class}

```


References

- [1] UK T_EX Users Group. UK list of T_EX frequently asked questions. <https://texfaq.org>, 2019.
- [2] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://www.ctan.org/pkg/amslatex>.
- [3] Cristophe Fiorio. *algorithm2e.sty—package for algorithms*, October 2015. <http://www.ctan.org/pkg/algorithm2e>.
- [4] Rogério Brito. *The algorithms bundle*, August 2009. <http://www.ctan.org/pkg/algorithms>.
- [5] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*, June 2015. <http://www.ctan.org/pkg/listings>.
- [6] Simon Fear. *Publication quality tables in L^AT_EX*, April 2005. <http://www.ctan.org/pkg/booktabs>.
- [7] Association for Computing Machinery. *ACM Visual Identity Standards*, 2007. <http://identitystandards.acm.org>.
- [8] Axel Sommerfeldt. *The subcaption package*, April 2013. <http://www.ctan.org/pkg/subcaption>.
- [9] Boris Veytsman, Bern Schandl, Lee Netherton, and C. V. Radhakrishnan. *A package to create a nomenclature*, September 2005. <http://www.ctan.org/pkg/nomencl>.
- [10] Nicola L. C. Talbot. *User Manual for glossaries.sty v4.44*, December 2019. <http://www.ctan.org/pkg/glossaries>.
- [11] David Carlisle. *The textcase package*, October 2004. <http://www.ctan.org/pkg/textcase>.

Change History

1.48	General: Added prologue option to xcolor	44	\if@ACM@printacmref: Added warning for longer papers	67
	Bib code cleanup (Zack Weinberg)	32	\keywords: Added warning for missing keywords	66
	Documentation update (siggraph) .	32	General: ACM reference format is now mandatory for papers over one page; CCS concepts and keywords are now mandatory for papers over two pages	32
1.49	General: New journal: DTRAP	32	Authors' addresses are mandatory for journal articles	32
1.53	General: New journals: PACMCGIT, TIOT, TDSCI	32		
	Rearranged docs	32	1.69	
1.54	General: Moved footnote stuff before hyperref call (Ross Moore)	32	\vspace: Added the changed command to avoid grouping	103
1.56	General: Documented \Description	32	v1.00	
1.57	General: Booktabs package is now the default	32	General: First released version	32
1.58	General: Changes in samples (Enrico Gregorio)	32	v1.01	
	New journal: HEALTH. TDS is renamed to TDSCI	32	General: Changed hyperref colors in screen mode (closes https://github.com/borisveytsman/acmart/issues/1)	32
1.60	\if@ACM@urlbreakonhyphens: introduced macro	33	Defined ACM colors	32
	General: New option: urlbreakonhyphens	32	Explicitly put draft option (closes https://github.com/borisveytsman/acmart/issues/4)	35
1.62	General: New journal: TELO	32	Set headheight to 1pc for all formats (closes https://github.com/borisveytsman/acmart/issues/5)	32
1.63	General: New journal: FACMP	32	v1.02	
	New journal: TQUANT	32	General: Added TOPS and TSC (closes https://github.com/borisveytsman/acmart/issues/12)	32
1.63a	General: Move: TQUANT to TQC	32	Documentation changes (closes https://github.com/borisveytsman/acmart/issues/13)	32
1.64	General: Putting abstract after \maketitle now causes an error .	32	v1.03	
1.65	General: New journal: DGOV	32	\@formatdoi: Added macro	71
1.66	\@mkauthorsaddresses: Added warning for missing addresses . .	88	\if@ACM@authorversion: Added macro	34
	\ccsdesc@parse: Added warning for missing concepts	69	\maketitle: Added special case of authorversion	75

General: Added anonsuppress environment	32	v1.08	General: SIGPLAN reformatting by Matthew Fluet	32
Added authorversion option (closes https://github.com/borisveytsman/acmart/issues/9)	32	v1.09	Typos corrected (Tobias Pape) . . .	32
v1.04		General: Revert SIGPLAN caption rules	32	
\acmArticleSeq: Name change by Matthew Fluet	65	v1.10	\maketitle: Corrected a bug with doi in manuscript and author version, https://github.com/borisveytsman/acmart/issues/36	75
\acmDOI: Name change by Matthew Fluet	65	General: Changes of 'licensedothergov' wording	69	
\acmISBN: Name change by Matthew Fluet	65	standardpagestyle: Reversed folios location	91	
General: Updated bibliography for siggraph	32	v1.11	General: Customization of ACM theorem styles and proof environment by Matthew Fluet . .	32
v1.05		v1.12	\@marginfigure: Now centering by default	51
General: Added processing doi numbers for acmsiggraph and doi numbers for sigproc.bib	32	\@margintable: Now centering by default	51	
Patched \setcitestyle command; closes https://github.com/borisveytsman/acmart/issues/19	32	\@parfont: Moved to \section@raggedright	97	
v1.06		\copyrightpermissionfootnoterule: Added macro	47	
\@ACM@badge@skip: Added macro . .	66	\descriptionlabel: Redefined	53	
\@ACM@badge@width: Added macro .	65	\footnoterule: Made shorter	47	
\@ACM@title@width: Added macro .	65	\if@ACM@natbib@override: Added macro	34	
\@mktitle@i: Added processing badges	80	\if@ACM@newfonts: Added macro . .	48	
Made generic	80	\maketitle: Moved thankses to copyrightpermission box	75	
\@mktitle@ii: Now this macro is obsolete	81	\section@raggedright: Introduced macro	97	
\@mktitle@iii: Added processing badges	81	General: Added graceful behavior when libertine fonts are absent . .	48	
Made more generic	81	Documentation updates	32	
\@mktitle@iv: Made more generic .	81	v1.13	\@mpfootnotetext: Made minipage footnotes centered	43
\@printtopmatter: Added processing badges	78	\bibliographystyle: Redefined macro	44	
\@subtitelfont: Added macro	80	\bibstyle@acmauthoryear: Added macro	39	
\@titlefont: Added macro	79			
\acmBadgeL: Added macro	66			
\acmBadgeR: Added macro	66			
\if@ACM@badge: Added macro	65			
v1.07				
\maketitle: Corrected a bug with abstract footnotes	75			
Corrected a bug with permission and footnotes order	75			

\bibstyle@acmnumeric: Added macro	40	v1.16	\@headfootfont: Added macro	91
\if@ACM@printfolios: Added macro	67		General: Formatting header/footer (Matthew Fluet)	32
General: Font adjustments for acmsmall	83		standardpagestyle: Customize header/footer text font	91
Increased font size for ACM Large Print bibliographic information by default for the proceedings	67	v1.17	\@makefnmark: Redefined	43
standardpagestyle: Added headers for sigs	91		\@mkauthors: TOG now uses the same authors block as other journals	82
Expanded headers for sigchi-a	91		\@mkauthors@ii: Deleted	84
Suppressed folios if sig	91		\@mkbibcitation: Added \nobreak	88
v1.14			Changed format for sigs	88
\bibstyle@acmauthoryear: Moved def of \bibstyle@acmauthoryear before use	39		\acmArticle: The default is now numerical	65
\bibstyle@acmnumeric: Moved def of \bibstyle@numeric before use	40		\acmMonth: The default must be numerical. Closes #50.	65
General: \citestyle updates (Matthew Fluet)	32		\acmNumber: The default is now numerical	64
Patched \citestyle	38		\acmVolume: The default is now numerical	64
v1.15			\acmYear: The default is now numerical	65
\@ACM@addtoaddress: Added macro	81		\description: Decreased indent	53
\@mkauthors@iii: New authors system	85		\grantnum: Added url	103
\@shortauthors: Introduced macro	91		\grantsponsor: Renamed	103
\@typeset@author@bx: Moved to separate macro	85		\if@ACM@printacmref: Renamed from \if@ACM@printbib	67
\acks: Added macro	102		General: Slightly decreased margins for sigs	45
\affiliation: Added code for author groups	62		standardpagestyle: Added paper title to sigs	91
\author: Added code for author groups	62	v1.18		
\city: Added macro	82		\@mkauthors@i: Now we andify affiliations	84
\country: Added macro	82		\@typeset@author@line: Added macro	83
\department: Added macro	82		General: Natbib is now the default for all formats	32
\grantnum: Added macro	103	v1.19		
\grantsponsor: Added macro	103		\@mkabstract: Include 'Abstract' in PDF bookmarks (Matthew Fluet)	88
\if@insideauthorgroup: Introduced macro	61		\acks: Include 'Acknowledgements' in PDF bookmarks (Matthew Fluet)	102
\institution: Added macro	82		General: Include 'Abstract', 'Acknowledgements', and 'References' in PDF bookmarks (Matthew Fluet)	32
\num@authorgroups: Renamed	61		Include 'References' in PDF bookmarks (Matthew Fluet)	38
\orcid: Introduced macro	63			
\position: Added macro	82			
\postcode: Added macro	82			
\state: Added macro	82			
\streetaddress: Added macro	82			
standardpagestyle: Better handling of anonymous mode	91			

v1.20	\mkabstract: Deleted spurious space	88	\@startsection: Added	
	General: Bug fixes for bst	32	\tochangmeasure	40
v1.21			Redefined macro	42
	\showeprint: Added macro	103	\@textbottom: Redefined	48
v1.22			\acmMonth: The default now is the	
	General: More bibliography changes		current month (Matteo Riondato)	65
	for Aptara	32	\acmYear: The default now is the	
v1.23			current year (Matteo Riondato)	65
	General: Add PACMPL journal option	32	\additionalaffiliation: Added	
v1.24			macro	63
	General: Add IMWUT journal option	54	\l@section: Redefined macro	42
v1.25			\l@subsection: Redefined macro	42
	General: Updated PACMPL	54	General: Documentation changes	32
v1.26			v1.32	
	General: Corrected \shortcite bug	32	\@formatdoi: New doi format	71
	Documentation typos fixed (thanks		General: Added POMACS journal	
	to Stephen Spencer)	32	option	32
v1.27			Format siggraph is now obsolete	32
	\if@ACM@printccs: Typo corrected	67	v1.33	
v1.28			\@ACM@addtoaddress: Added	
	\ccsdesc@parse: Change from \to to		obeypunctuation code	81
	\textrightarrow (Matteo		\mkauthors@i: Added	
	Riondato)	68	obeypunctuation code	84
	General: Corrected option natbib		\mkauthors@iii: Added	
	behavior	40	obeypunctuation code	85
	Got rid of warnings in pdf keywords	43	\mkauthors@iv: Added	
v1.29			obeypunctuation code	86
	\mkabstract: Removed spurious		\@subtitlefont: Added	
	indentation (John Wickerson)	88	\normalsize	80
	\ccsdesc@parse: Add spacing after		\ACM@linecountL: Renamed macro	90
	bullet and around rightarrow;		\ACM@linecountR: Added macro	90
	semicolon separators no longer in		\ACM@timestamp: Added current page	
	bold/italic (John Wickerson)	68	number	91
	General: Increased head to 13pt	45	Added macro (Michael D. Adams)	91
	standardpagestyle: Corrected		Added submission id	91
	printfolios (Matthew Fluet)	91	\acmSubmissionID: Added macro	65
v1.30			\city: Added obeypunctuation code	82
	\department: Added optional		\country: Added obeypunctuation	
	parameter	82	code	82
	General: Added \frenchspacing	104	\department: Added obeypunctuation	
	Bibtex style now recognizes https://		code	82
	in doi	32	\if@ACM@affiliation@obeypunctuation:	
	Switched to T1: looks like libertine		Added macro	63
	has problems with \l in OT1	49	\if@ACM@authordraft: Added macro	35
	Updated IMWUT and PACMPL	54	\if@ACM@natbib@override: Deleted	
v1.31			macro	34
	\@additionalaffiliation: Added		\if@ACM@timestamp: Added macro	
	macro	63	(Michael D. Adams)	35
	\mkbibcitation: Disabled linebreak	88	\institution: Added	
			obeypunctuation code	82

\maketitle: Fixed the bug with figures on top and bottom of the title page, thanks to David Epstein	75	v1.35	\bibstyle@acmauthoryear: Square brackets for author-year style . . .	39
\position: Added obeypunctuation code	82		General: BibTeX bug fixed: et al. . . .	32
\postcode: Added obeypunctuation code	82		If the copyright is set to usgov or rigtsretained, the price is suppressed	69
\state: Added obeypunctuation code	82	v1.36		
\streetaddress: Added obeypunctuation code	82		\@ACM@authorsperrrow: Added macro	67
General: Added acmart-preload-hook	32		\@mkauthors@iii: Added authorsperrrow override	85
Added cmap and glyphtounicode .	48		\@mkauthors@iv: Added authorsperrrow override	86
BibTeX comma before articleno bug corrected	32		\if@ACM@authordraft: Corrected typo, thanks to bargteil	35
BibTeX crossref bug corrected . . .	32		General: Added PACMHCI journal options	54
BibTeX numpages bug corrected . .	32		Added the possibility to adjust number of author boxes per row in conference formats	32
Documentation updates	32			
Moved \citename definition for non-natbib bibliography, so a package may redefine it	44	v1.37		
Switched to Type 1 fonts for libertine even if OTF-capable engine is used (Kai Mindermann) .	49		\description: Reduce list indentation (Matthew Fluet)	53
firstpagestyle: Added right linecount for two-column formats	94		\descriptionlabel: Reduce list indentation (Matthew Fluet)	53
Added timestamp (Michael D. Adams)	94		\normalparindent: Set \normalparindent (Matthew Fluet)	47
standardpagestyle: Added right linecount for two-column formats	91		General: Reduce list indentation (Matthew Fluet)	53
Added timestamp (Michael D. Adams)	91		Set \normalparindent; Reduce list indentation (Matthew Fluet)	32
v1.34		v1.38		
\@mkbibcitation: Deleted DOI from doi numbers	88		General: Increase default font size for SIGPLAN	32, 37
\ACM@linecount@bx: Rulers now are continuous	90	v1.39		
\ACM@linecountL: Rulers now are continuous	90		\@authornotemark: Added macro . .	88
\ACM@linecountR: Rulers now are continuous	90		\authornotemark: Added macro . . .	64
\maketitle: Added date to the bibstrip in conf proceedings	75	v1.40		
Deleted 'DOI' from doi numbers .	75		\@copyrightowner: Added new copyright version: licensedcagov .	71
Rearranged bibstrip	75		\@copyrightpermission: Added new copyright version: licensedcagov .	71
The \terms command is now obsolete	75		\@mkauthors@i: Switched to MakeTextUppercase	84
\terms: The \terms command now just produces a warning	66		\@parfont: Switched to MakeTextUppercase	97
			\ACM@linecount@bx: Work around a bug in xcolor: looks like cmyk colors in boxes do not work	90

\ccdesc@parse@finish: Added macro	69	General: Added package refcount . . .	32
\city: We now do not print this even in SIG	82	Deleted package cleveref	32
\country: Fixed bugs with extra spaces	82	Put theorem defs in a separate style	32
\l@subsection: Redefined macro . .	42		
\postcode: We now do not print this even in SIG	82	v1.45	
\state: We now do not print this even in SIG	82	\@folioblob: Switched \bfeseries\sffamily to \sffamily\bfseries	94
\streetaddress: We now do not print this even in SIG	82	\@parfont: Switched \bfeseries\sffamily to \sffamily\bfseries	97
General: Added 'textcase' package . .	38	\@titlefont: Switched \bfeseries\sffamily to \sffamily\bfseries	79
Added heightrounded to geometry	45	v1.46	
Added new copyright version: licensedcagov	32	\@mkauthorsaddresses: Introduced macro	87
Added package cleveref	32	\@mkbibcitation: Added subtitle . .	88
Added Ross Moore code for glyphtounicode	48	\@printendtopmatter: Made it \par\bigskip uniformly	89
Bibliography changes	32	\@printtopmatter: Deleted rule . . .	78
v1.41		\@setauthorsaddresses: Introduced macro	89
General: Added new badges	32	\ACM@linecount@bx: Rearranged the code to get rid of spurious underfull messages (Benjamin Byholm)	90
v1.42		\author: Started counting authors . .	62
General: Deleted ACM badges	32	\authorsaddresses: Introduced macro	63
v1.43		\country: Corrected spacing for institution	82
\@startsection: Added \makeatletter	42	\if@ACM@acmthm: Modified description	33
\country: Added comma before country for journals	82	\liningnums: Workaround for compatibility with fontspec	49
v1.44		\maketitle: Added authors' addresses Thankses go before authors' addresses	75
\@acmBooktitle: Added macro	61	\num@authors: Introduced macro . .	61
\@acmEditors: Added macro	61	General: Added etoolbox	32
\@editorsAbbrev: Added macro . . .	61	Bst file bug fixes: label width is calculated correctly	32
\@folioblob: Suppress the blob if acmArticleSeq is empty	94	Delayed hypersetup since journal options may change screen mode	43
\@mkbibcitation: If the paper has just one page, use 'page' instead of 'pages'	88	PACM now set screen to true	54
\ACM@restore@pagestyle: Added macro	90	Restore theorem defs to class file .	32
\acmArticle: The default is now empty	65	v1.47	
\acmArticleSeq: Now acmArticle might be empty	65	General: New journal: THRI	32
\acmBooktitle: Added macro	61		
\editor: Added macro	61		
\if@ACM@acmthm: Added macro . . .	33		
\maketitle: Empty DOI or ISBN are not printed (by Michael Ekstrand)	75		

v1.48		v1.54	
\@headfootfont: Deleted		\@mkbibcitation: Bug corrected	
unnecessary switch (Michael		(Ross Moore)	88
D. Adams)	91	\@shortauthors: Added submission	
\@mkabstract: Removed spurious		id in anonymous mode	91
indentation if abstract is followed		\ACM@NR@adjustedSectionformat:	
by an empty line	88	Added macro	96
\ACM@timestamp: Fromatting change		\ACM@NRadjust: Added macro	96
(Michael D. Adams)	91	\ACM@adddotafter: Added macro	97
\if@ACM@review: Review mode now		\author: Added submission id in	
switches on folios	34	anonymous mode	62
\maketitle: Added acmart and		\if@ACM@nonacm: Added macro	34
version info to pdfcreator tag	75	General: Added Ross's patch for	
Added language and doctitle		sectioning	97
attributes to PDF (Andreas		Deleted indent for subsubsection	97
Reichinger)	75	XeTeX now uses T1 encoding	49
Suppressed empty DOI (Serguei			
Mokhov)	75	v1.55	
General: \citeyear no longer		\@mkbibcitation: Bug corrected	88
behaves like \citeyearpar	44	\maketitle: Fixes topnum	75
Code prettying (Michael D. Adams)	32	General: Now we use purple color for	
Initial support for Biblalex (Daniel		links	43
Thomas)	32	Table captions for SIGCHI now use	
Misc entries in the bibliography no		the same font size as figure	
longer produce a separate date	32	captions (Luis Leiva)	50
Typos fixed (Jamie Davis)	32	Typo corrected (Zack Weinberg)	38
v1.50		v1.56	
\@copyrightpermission: New		\@marginfigure: Added checking for	
copyright statements for		description	51
iw3c2w3[g]	71	\@mkteasers: Added check for	
v1.51		description	88
General: Corrected the bug with price		\Description: Added macro	49
suppression	69	\acksname: Added macro (Philip	
Suppress price if the copyright is		Quinn)	102
set to iw3c2w3 or iw3c2w3g	69	\ccsdesc@parse: End the concepts	
XeTeX now uses OTF fonts		list with a period (Philip Quinn)	68
(Joachim Breitner)	49	\if@Description@present: Added	
firstpagestyle: We now use journal		macro	49
abbreviation for footers	94	\if@undescribed@images: Added	
standardpagestyle: We now use		macro	49
journal abbreviation for footers	91	General: Looks like XeTeX requires	
v1.52		explicit monotype font delcaration	49
\@copyrightowner: Rewording of		Make two-column layouts flush	
licenses	71	(Philip Quinn)	45
\@copyrightpermission: Another		v1.57	
rewording of copyright statements		\ACM@origbaselinestretch: Added	
for iw3c2w3[g]	71	check whether the user changed	
v1.53		\baselinestretch	104
General: Added PACMCGIT, TIOT,		\author: Added warning if \author	
TDSCI	54	has comma	62

\email: Added warning if \author		v1.61	
has comma	63	\@typeset@author@bx: Added	
\if@ACM@balance: Added macro . . .	34	\normalbaselines	85
\vspace: Added warning	103	v1.64	
v1.58		\ACM@linecount@bx: Bug fix: made	
\@dblfloat: Deleted spurious		the spacing on the left and the	
\vspace warning	52	right size equal	90
\@marginfigure: Deleted spurious		\if@ACM@maketitle@typeset:	
\vspace warning	51	Introduced macro	54
\@margintable: Deleted spurious		\maketitle: Added a switch setting to	
\vspace warning	51	show that \maketitle is typeset .	75
\@mkbibcitation: Deleted spurious		v1.65	
\vspace warning	88	\@mkauthorsaddresses: Deleted	
\@printendtopmatter: Deleted		cs@addpunct	87
spurious \vspace warning	89	v1.66	
\@sidebar: Deleted spurious \vspace		\@specialsection: Suppress	
warning	51	warnings about \vspace	77
\maketitle: Original \vspace inside		General: Patching algorithm and	
\maketitle	75	algorithm* to prevent spurious	
\vspace: Preserved old versions as		space warnings	50
\@vspace@orig and		v1.67	
\@vspace@orig	103	\@parfont: Deleted redefinitions of	
General: Added HEALTH. TDSCI is		sections	97
renamed to TDS	54	\@specialsection: Paragraph inside	
Suppressed \addtocounter in pdf		group does not print its argument.	
subject	43	Added a bugfix	77
v1.59		General: Patching lstlisting and	
\acmConference: Setting		lstlisting* to prevent spurious	
\@ACM@journal@bibstrip	60	space warnings	50
\acmJournal: Setting		v1.68	
\@ACM@journal@bibstrip	60	\@specialsection: Deleted grouping	
\if@ACM@journal@bibstrip:		altogether	77
Introduced macro	36	General: New command for unindent	
firstpagestyle: Added logic for		paras	97
conference papers using journal		v1.69	
format	94	\@printendtopmatter: Deleted	
Moved page styles to		grouping	89
\AtBeginDocument	94	\@specialsection: Changed dot to	
standardpagestyle: Added logic for		colon for sigplan	77
conference papers using journal		\ACM@linecountR: Do not increase	
format	91	numbers in one column format . .	90
Moved page styles to		\ccsdesc@parse: Use math right	
\AtBeginDocument	91	arrow in text	68
v1.60		General: No dots for unindented	
\@headfootfont: Moved to		paragraphs	97
footnotesize	91		

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols		
\\$	1792, 1796	\@ACM@manuscripttrue 158
\-	478	\@ACM@newfontsfalse 1361, 1363, 1899, 1901, 1976, 1992, 1995, 2020, 2022
\@ 1546, 1558, 1561, 1564, 1569, 1649, 1670, 1683		\@ACM@newfontstrue . 666
\@authornotemark 1326, 2282		\@ACM@printacmreffalse 92
\@par 347, 404		\@ACM@printfoliostrue 75
\@ACM@addtoaddress 2034, 2057, 2058, 2060		\@ACM@reviewtrue . . . 133
\@ACM@authorsperrrow 1410, 2166, 2167, 2217, 2218		\@ACM@screentrue 955, 984, 990, 996, 1002
\@ACM@badge@skip 1357, 1897, 1974, 1978, 1984, 1993, 2003, 2009, 2018		\@ACM@sigchiamodefalses 162
\@ACM@badge@width 1354, 1896, 1901, 1973, 1977, 1983, 1995, 2002, 2004, 2007, 2019, 2022		\@ACM@sigchiamodetrue 182
\@ACM@badgefalse . . . 1353		\@ACM@timestamptrue 132
\@ACM@badgetrue 1359, 1364		\@ACM@title@width 1356, 1971, 1973, 1974, 1977, 1978, 1986, 2000, 2002, 2003, 2011
\@ACM@balancefalse 2833, 2835, 2837, 2849		\@DeclareACMFormat 37, 38, 39, 40, 41, 42, 43, 44, 45, 46
\@ACM@commabox 2034, 2038, 2039		\@Description@presentfalse 700, 703, 768, 2288
\@ACM@journal@bibstripfalse 187, 1196		\@Description@presenttrue 694, 697
\@ACM@journal@bibstriptrue 185, 1182		\@M 347, 386, 404, 413
\@ACM@journalfalse 173, 175, 177, 179, 181		\@abstract 1384, 2296, 2303
\@ACM@journaltrue 165, 167, 169, 171		\@acmArticle . . . 1332, 1335, 1791, 2314, 2315, 2436, 2439, 2459, 2469, 2480, 2554, 2573, 2583, 2593
\@ACM@labelwidth 816, 819, 827, 832, 858		\@acmArticlePage 2435, 2453, 2454, 2463, 2466, 2473, 2477
\@ACM@maketitle@typesetfalse 865		\@acmArticleSeq 1334, 2537
\@ACM@maketitle@typesettrue 1715		\@acmBadgeL@image 1366, 1368, 1894, 1896, 1972, 1981, 1983, 2005, 2007
\@ACM@manuscriptfalse 160		\@acmBadgeL@url . 1365, 1367, 1895, 1982, 2006
		\@acmBadgeR@image 1361, 1363, 1899, 1901, 1976, 1992, 1995, 2020, 2022
		\@acmBadgeR@url . 1360, 1362, 1900, 1994, 2021
		\@acmBooktitle 1202, 1781, 2330
		\@acmDOI . . 1350, 1783, 1786, 1793, 1797, 2338
		\@acmEditors 1207, 1208, 1209, 1212, 2331, 2332
		\@acmISBN 1348, 1795
		\@acmMonth 1338, 1340, 1791
		\@acmNumber 1330, 2327, 2459, 2469, 2480, 2573, 2583, 2593
		\@acmPrice 1344, 1792, 1796
		\@acmPubDate . . . 1340, 2327, 2459, 2469, 2480, 2574, 2584, 2594
		\@acmSubmissionID 1233, 1234, 1249, 1250, 1346, 2416, 2417, 2427
		\@acmVolume 1328, 2327, 2458, 2468, 2479, 2572, 2582, 2592
		\@acmYear 1336, 1343, 1702, 1791, 2318
		\@acmdefinitionbodyfont 2746, 2758, 2770
		\@acmdefinitionheadfont 2748, 2760, 2772
		\@acmdefinitionindent 2747, 2759, 2771
		\@acmdefinitionnotefont 2749, 2761, 2775
		\@acmownedfalse . 1497, 1500, 1503, 1509, 1513, 1516, 1519, 1522, 1528, 1531, 1535

\@acmownedtrue	98, 102, 107, 109,	\@empty 189,
. . . 1484, 1493, 1525	110, 115, 117, 118,	337, 1193, 1208,
\@acmplainbodyfont .	123, 125, 126, 131,	1230, 1233, 1247,
. . . 2716, 2728, 2740	135, 136, 147, 153,	1249, 1254, 1255,
\@acmplainheadfont .	211, 667, 670, 673,	1261, 1374, 1375,
. . . 2718, 2730, 2742	699, 708, 711, 771,	1428, 1429, 1435,
\@acmplainindent . . .	956, 985, 991, 997,	1442, 1447, 1473,
. . . 2717, 2729, 2741	1003, 1177, 1179,	1739, 1743, 1783,
\@acmplainnotefont .	1223, 1274, 1288,	1792, 1795, 1796,
. . . 2719, 2731, 2745	1371, 1377, 1382,	1797, 1807, 1812,
\@adddotafter	1389, 1391, 1392,	1866, 1894, 1899,
2630, 2631, 2633,	1395, 1397, 1398,	1972, 1976, 1981,
2645, 2660, 2664, 2713	1401, 1406, 1408,	1989, 1992, 2005,
\@additionalaffiliation	1409, 1411, 1412,	2013, 2020, 2030,
. 1275, 1276	1475, 2277, 2291,	2116, 2126, 2134,
\@addpunct . 2268, 2347,	2311, 2892, 2895, 2902	2135, 2185, 2191,
2348, 2713, 2714, 2825	\@clubpenalty 392	2198, 2230, 2236,
\@addspaceafter 2714	\@concepts . 1447, 1459,	2241, 2276, 2284,
\@affiliationfont . .	1473, 1807, 1809, 1830	2314, 2319, 2331,
2087, 2092, 2096,	\@copyrightowner . . .	2338, 2416, 2427,
2099, 2102, 2105, 1540, 1767	2719, 2749, 2868, 2885
2108, 2111, 2139, 2158	\@copyrightpermission	\@endfloatbox 783
\@afterheading . 378, 1841 1578, 1759	\@endpefalse 2827
\@afterindentfalse .	\@copyrightyear	\@endwdefloatbox 783, 791
. 324, 1840	. . . 1701, 1767, 1769	\@finalstrut . . . 436, 449
\@afterindenttrue . . 322	\@currbox . . . 797, 798, 799	\@float 785
\@article@string . . .	\@currentaffiliation	\@flushglue 2674
. . . 2314, 2327, 2335	2159, 2162, 2184,	\@fnsymbol 1725
\@author	2191, 2192, 2195,	\@folio@ht
1232, 1237, 1242,	2198, 2199, 2203,	2517, 2544, 2550, 2551
2125, 2185, 2230, 2271	2229, 2236, 2237,	\@folio@max 2517, 2540, 2541
\@authorfont	2239, 2241, 2242, 2246	\@folio@voffset 2517, 2546
2086, 2091, 2095,	\@currentaffiliations	\@folio@wd 2517,
2098, 2101, 2104, 2116,	2551, 2552, 2579, 2589
2107, 2110, 2127, 2158	2117, 2118, 2120,	\@folioblob 2537,
\@authornotemark . . .	2123, 2135, 2136, 2141	2576, 2578, 2586, 2587
. . . 1318, 1324, 2281	\@currentauthors . . .	\@footnotemark . 452, 1723
\@authornotes 2114, 2115,	\@footnotemark@nolink
. . . 1315, 1319, 1735	2122, 2126, 2127, 452, 1723
\@authorsaddresses .	2129, 2158, 2161,	\@footnotetext
1294, 1743, 2276, 2348	2183, 2185, 2186, 427, 453, 1724
\@auxout 514	2188, 2228, 2230,	\@footnotetext@nolink
\@begindocumenthook 510	2231, 2233, 2281, 2282 453, 1724
\@botnum 1838	\@currentlabel . 431, 445	\@for 232
\@citestyle 256	\@dblarg 333	\@formatdoi . . . 1577,
\@classname	\@dblfloat 780	1786, 1793, 1797, 2338
24, 26, 34, 50, 52,	\@department . . 1279, 1280	\@fps 784
53, 58, 60, 61, 66,	\@dotsep 2715	\@fpsadddefault . . . 784
68, 69, 74, 77, 78,	\@editorsAbbrev	\@gobble 254, 298
83, 85, 86, 91, 97,	. . . 1206, 1211, 2332	\@hangfrom 346, 403

<code>\@headfootfont</code> . 2429 , 2453, 2454, 2455, 2456, 2462, 2465, 2472, 2476, 2484, 2485, 2487, 2490, 2497, 2498, 2500, 2503	988, 994, 1000, 1006, 1010, 1014, 1017, 1021, 1029, 1035, 1039, 1043, 1047, 1051, 1055, 1059, 1063, 1067, 1071, 1075, 1079, 1083, 1087, 1091, 1095, 1099, 1106, 1110, 1113, 1118, 1122, 1126, 1130, 1134, 1138, 1142, 1146, 1150, 1154, 1158, 1162, 1166, 1170, 1174, 1185, 2326, 2458, 2468, 2479, 2572, 2582, 2592	<code>\@mkteasers</code> . . . 1728 , 2283 <code>\@mkttitle</code> 1728 , 1906 <code>\@mkttitle@i</code> 1909, 1911, 1913, 1915, 1970 <code>\@mkttitle@ii</code> 1998 <code>\@mkttitle@iii</code> . . . 1917, 1919, 1921, 1923, 1998 <code>\@mkttitle@iv</code> . . 1925 , 2026 <code>\@mpargs</code> 633 <code>\@mparswitchfalse</code> . . 595 <code>\@mpfootins</code> 440, 441, 625, 626, 628 <code>\@mpfootnotetext</code> . . . 439 <code>\@ene</code> . 258, 262, 266, 268, 500, 2362, 2368, 2372 <code>\@enil</code> 277 <code>\@enobreakfalse</code> . 380, 420 <code>\@enoskipsecfalse</code> . . . 384 <code>\@enoskipsectrue</code> . . . 381 <code>\@pages@word</code> 2308, 2328, 2335 <code>\@par</code> 1741, 1747 <code>\@parboxrestore</code> . . . 444 <code>\@parfont</code> 2664, 2668, 2673, 2678 <code>\@permissionCodeOne</code> 933, 937, 941, 945, 949, 954, 960, 964, 968, 972, 976, 983, 989, 995, 1001, 1007, 1011, 1018, 1022, 1030, 1036, 1040, 1044, 1048, 1052, 1056, 1060, 1064, 1068, 1072, 1076, 1080, 1084, 1088, 1092, 1096, 1100, 1103, 1107, 1114, 1119, 1123, 1127, 1131, 1135, 1139, 1143, 1147, 1151, 1155, 1159, 1163, 1167, 1171, 1175, 1186, 1791 <code>\@permissionCodeTwo</code> 1115, 1187 <code>\@plus</code> 413, 421, 634, 2650, 2654, 2658, 2662,
<code>\@ifnextchar</code> 1279 <code>\@ifnotempty</code> 1707 <code>\@ifnum</code> 270, 272 <code>\@ifstar</code> 331 <code>\@ifundefined</code> 2780, 2783, 2786, 2789, 2792, 2796, 2799 <code>\@iiiparbox</code> 633 <code>\@input</code> 415 <code>\@insideauthorgroupfalse</code> 1221, 1269 <code>\@insideauthorgroupttrue</code> 1228 <code>\@journalCode</code> 866, 956, 985, 991, 997, 1003, 1177 <code>\@journalCode@nr</code> 866, 929, 1183 <code>\@journalName</code> 931, 935, 939, 943, 947, 951, 958, 962, 966, 970, 974, 978, 981, 987, 993, 999, 1005, 1009, 1013, 1016, 1020, 1024, 1026, 1028, 1032, 1034, 1038, 1042, 1046, 1050, 1054, 1058, 1062, 1066, 1070, 1074, 1078, 1082, 1086, 1090, 1094, 1098, 1102, 1105, 1109, 1112, 1117, 1121, 1125, 1129, 1133, 1137, 1141, 1145, 1149, 1153, 1157, 1161, 1165, 1169, 1173, 1184, 1185, 1779 <code>\@journalNameShort</code> 932, 936, 940, 944, 948, 953, 959, 963, 967, 971, 975, 979, 982,	<code>\@keywords</code> . 1373, 1374, 1375, 1812, 1818, 1831 <code>\@latex@error</code> 300 <code>\@l@empty</code> 1386 , 2296 <code>\@listI</code> 840, 844 <code>\@listi</code> 837, 844 <code>\@listii</code> 845 <code>\@listiii</code> 848 <code>\@listiv</code> 850 <code>\@listv</code> 852 <code>\@listvi</code> 854 <code>\@m</code> 335 <code>\@makefnmark</code> . . . 426, 451 , 1727, 1732, 1736 <code>\@makefntext</code> 426, 435, 448, 1738 <code>\@marginfigure</code> . 763, 764 <code>\@margintable</code> . . 774, 775 <code>\@minipagefalse</code> . 630, 793 <code>\@minus</code> 2650, 2654, 2658, 2662, 2666, 2671, 2737, 2739, 2767, 2769 <code>\@mkabstract</code> . . 1805, 2295 <code>\@mkauthors</code> 1728, 1730, 2062 <code>\@mkauthors@i</code> . . 2066, 2068, 2070, 2072, 2121 <code>\@mkauthors@ii</code> 2151 <code>\@mkauthors@iii</code> . 2074, 2076, 2078, 2080, 2163 <code>\@mkauthors@iv</code> 2082, 2214 <code>\@mkauthorsaddresses</code> 1295, 2256 <code>\@mkbibcitation</code> 1825, 2305	

2666, 2671, 2736, 2738, 2766, 2768, 2822	\@subtitle . 1214, 1307, 1989, 1990, 2013, 2014, 2030, 2031, 2319	\@titlefont 1928, 1980, 1987, 1999, 2011, 2027
\@printcopyrightfalse 1496, 1508	\@subtitlefont 1949, 1990, 2014, 2031	\@titlenotes 1296, 1300, 1303, 1733
\@printcopyrighttrue 1480, 1492	\@subtitlenotes 1305, 1309, 1312, 1734	\@tochangmeasure 351, 364
\@printendtopmatter 1839, 2340	\@svsec . 337, 340, 346, 361	\@toclevel 335
\@printpermissionfalse 1495	\@svsechd ... 359, 387, 407	\@tocline ... 423, 424, 425
\@printpermissiontrue ... 1482, 1491, 1507	\@teaser 1705, 2285	\@topnum 1836
\@printtopmatter 1729, 1865	\@teaserfigures 1703, 1705, 2284, 2289	\@typeset@author@bx 2155, 2207, 2213, 2250, 2255
\@proofindent 2806, 2816, 2824	\@tempa 232, 233, 235, 237, 239, 241, 243, 245, 247, 249, 251, 253, 255, 257, 259, 261, 263, 265, 267, 269, 271, 273, 275, 277, 280, 282, 284, 286, 288, 290, 1253, 1254, 1427, 1428, 2134, 2868, 2884, 2885, 2887	\@typeset@author@line 2113, 2124, 2146, 2148
\@proofnamefont 2805, 2815, 2825	\@tempb 233, 235, 237, 239, 241, 243, 245, 247, 249, 251, 253, 255, 257, 259, 261, 263, 265, 267, 269, 271, 273, 275, 280, 282, 284, 286, 288, 290, 2886, 2887	\@undefined 510, 687
\@received . 1426, 1429, 1430, 1432, 1435, 1436, 1438, 1442, 1443	\@tempc . 278, 279, 281, 283, 285, 287, 289, 291	\@undescribed@imagesfalse 696
\@rightskip ... 2674, 2675	\@tempcnta . 2537, 2538, 2540, 2541, 2543, 2545	\@undescribed@imagetrue ... 707, 710, 770, 2290
\@saveabstract 1380, 1381	\@tempdima 2544, 2545, 2546, 2548	\@vspace 701, 704, 712, 714, 716, 718, 720, 722, 760, 765, 775, 781, 1721, 2306, 2341, 2344, 2890, 2892, 2898
\@save teaser .. 1704, 1705	\@tempboxa 633	\@vspace@acm .. 2344, 2898
\@seccntformat . 340, 397	\@temppc . 278, 279, 281, 283, 285, 287, 289, 291	\@vspace@orig 701, 704, 712, 714, 716, 718, 720, 722, 760, 765, 775, 781, 1721, 2306, 2341, 2890
\@secfont 2652, 2678	\@tempcnta . 2537, 2538, 2540, 2541, 2543, 2545	\@vspacer 702, 705, 713, 715, 717, 719, 721, 723, 761, 766, 776, 782, 1722, 2307, 2342, 2345, 2891, 2895, 2899
\@secpenalty 329	\@tempdima 2544, 2545, 2546, 2548	\@vspacer@acm . 2345, 2899
\@sect 333, 334	\@tempkipa 321, 323, 324, 329, 342, 343, 374, 375, 377, 389, 390, 399, 400	\@vspacer@orig 702, 705, 713, 715, 717, 719, 721, 723, 761, 766, 776, 782, 1722, 2307, 2342, 2891
\@setaddresses 2280	\@textbottom 634	\@width 614, 621
\@setauthorsaddresses 1747, 2348	\@textsuperscript 451, 1727, 1732	\@xp 417, 418
\@setthanks ... 1741, 2347	\@texttop 635	\@xsect 372, 373, 409
\@shortauthors 2424, 2447, 2455, 2463, 2473, 2485, 2498	\@thefnmark . 432, 446, 451, 1727, 1732, 1737	\\ 531, 1233, 1767, 1772, 1787, 1792, 1796, 2310, 2318, 2367
\@sidebar 759, 760	\@title ... 1298, 1829, 1988, 2012, 2029, 2318	\{ 240
\@specialsection ... 1808, 1814, 1816, 1843		\} 240
\@ssect 332, 398		
\@startPage 1369, 1866, 1867, 1869, 2421		
\@startsection . 318, 410, 2649, 2653, 2657, 2661, 2665, 2670		
\@starttoc 410		
\@subparfont 2703		
\@subsecfont .. 2656, 2678		
\@subsubsecfont 2660, 2678		

<code>_</code> . . . 1205, 1455, 1465, 1767, 1769, 1792, 2314, 2315, 2333, 2421	<code>\ACM@linecountR</code> 2381, 2475, 2477, 2485, 2492, 2498, 2505, 2597, 2600, 2605	<code>\acmISBN</code> 15, 1348 <code>\acmJournal</code> 9, 1181 <code>\acmMonth</code> 15, 1338 <code>\acmNumber</code> 15, 1330 <code>\acmplain</code> 2735 <code>\acmPrice</code> . . . 15, 1344, 1504, 1510, 1532, 1536 <code>\acmSubmissionID</code> 15, 1346 <code>\acmVolume</code> 15, 1328 <code>\acmYear</code> 15, 1336 <code>\addcontentsline</code> 228, 353, 366, 2297, 2862 <code>\additionalaffiliation</code> 11, 1275 <code>\addpenalty</code> 329 <code>\addresses</code> 1230, 1232, 1237, 1242, 1271, 1291, 1318, 1324, 1326, 2148, 2213, 2255, 2273 <code>\addtocounter</code> . . 456, 1467 <code>\addtolength</code> . . . 825, 826, 827, 831, 832, 2369 <code>\addvspace</code> 329, 421 <code>\advance</code> 841, 846, 849, 851, 853, 855, 1225, 1227, 1973, 1974, 1977, 1978, 2002, 2003, 2165, 2182, 2216, 2227, 2368, 2372, 2541, 2543, 2546 <code>\affiliation</code> 10, 1268, 2133, 2198, 2241 <code>\and</code> 1212, 1242, 1243, 1258, 1264, 2124, 2129, 2131, 2141, 2146, 2156, 2190, 2207, 2213, 2235, 2250, 2255, 2270 <code>\andify</code> 1820, 1821, 2114, 2117, 2332 <code>\anonsuppress</code> (environ- ment) 23 <code>\apptocmd</code> 2892, 2895 <code>\AtBeginDocument</code> 75, 92, 503, 511, 817, 1504, 1510, 1532, 1536, 2357, 2430, 2557, 2643
A	<code>\ACM@mk@linecount</code> 2363, 2376, 2391, 2393, 2395, 2397, 2399, 2401	<code>\ACM@NR@adjustedSectionformat</code> 2628, 2637 <code>\ACM@NRadjust</code> 2619, 2652, 2656, 2660, 2664, 2668, 2673 <code>\ACM@origbaselinestretch</code> 2900 <code>\ACM@ps@headings</code> 2352, 2356 <code>\ACM@ps@myheadings</code> 2351, 2355 <code>\ACM@ps@plain</code> . 2350, 2354 <code>\ACM@restore@pagestyle</code> 2350 <code>\ACM@sect@format</code> 2638, 2640 <code>\ACM@sect@format@</code> 2627, 2640, 2642 <code>\ACM@sect@format@null</code> 2641, 2642 <code>\ACM@timestamp</code> 2407, 2512, 2610, 2615 <code>\acmArticle</code> 15, 1332 <code>\acmArticleSeq</code> . . 15, 1334 <code>\acmBadgeL</code> 16, 1364 <code>\acmBadgeR</code> 16, 1359 <code>\acmBooktitle</code> . . . 9, 1202 <code>\acmConference</code> . . 9, 1188 <code>\acmConference@date</code> 1191, 1763, 2489, 2492, 2502, 2505 <code>\acmConference@name</code> . . . 1190, 1203, 1204 <code>\acmConference@shortname</code> . . . 1189, 1193, 1194, 1204, 1205, 1763, 2488, 2491, 2501, 2504 <code>\acmConference@venue</code> 1192, 1763, 2489, 2492, 2502, 2505 <code>\acmdefinition</code> 2765 <code>\acmDOI</code> 15, 1350
<code>\abstract</code> 1380 <code>abstract</code> (environment) 17 <code>\abstractname</code> 2301 <code>\acks</code> 2859 <code>acks</code> (environment) 23 <code>\acksname</code> . 2858, 2861, 2862 <code>\ACM@adddotafter</code> 2631, 2648 <code>\acm@copyrightinput</code> 1486 <code>\acm@copyrightmode</code> 1486, 1494, 1499, 1502, 1506, 1512, 1515, 1518, 1521, 1524, 1527, 1530, 1534, 1541, 1579 <code>\ACM@fontsize</code> 139, 189, 192, 194, 196, 198, 200, 202, 204, 206, 208, 211, 212 <code>\ACM@format</code> 31, 147 <code>\ACM@format@nr</code> 31, 147, 152, 157, 163, 190, 463, 535, 600, 636, 734, 801, 1844, 1873, 1907, 1929, 1950, 2064, 2088, 2383, 2443, 2524, 2563, 2609, 2683, 2720, 2750, 2807, 2831 <code>\ACM@linecount</code> 2361, 2362, 2367, 2368, 2371, 2372 <code>\ACM@linecount@bx</code> 2358, 2378, 2404 <code>\ACM@linecount@bxht</code> . . . 2360, 2366, 2369, 2370 <code>\ACM@linecountL</code> 2374, 2445, 2448, 2453, 2456, 2462, 2464, 2472, 2474, 2484, 2487, 2497, 2500, 2565, 2576, 2577, 2587, 2588, 2596, 2599, 2604		

\AtBeginEnvironment	2678, 2679, 2693,	\citeN	492
... 700, 703, 712,	2694, 2696, 2697,	\citename	505
714, 716, 718, 720, 722	2699, 2700, 2701,	\citeNN	495
\AtEndDocument . 698,	2702, 2706, 2707,	\citeNP	497
1375, 1399, 1441,	2710, 2711, 2730, 2760	\citep	493
1473, 2275, 2853, 2901	\bgroup . 760, 764, 775,	\citestyle ... 24, 296, 316	
\AtEndEnvironment 706, 709	781, 1276, 1807,	\citeyear	496
\AtEndPreamble . 476,	1812, 2155, 2192,	\citeyearNP	496
688, 2777, 2829, 2869	2195, 2252, 2261,	\citeyearpar ... 495, 508	
\author	2285, 2295, 2305, 2317	\city .. 11, 1282, 2042, 2266	
1222, 1717, 1718, 2312	\bibfont	\ClassError . 34, 1179,	
\author@bx 2151, 2157, 2160	230	1274, 1382, 1392,	
\author@bx@sep	\bibiofont	1398, 1409, 2311, 2902	
.... 2153, 2160,	230	\ClassInfo	
2165, 2182, 2216, 2227	\bibliographystyle . 509	.. 147, 211, 1177,	
\author@bx@wd	\bibsection	1389, 1391, 1395,	
.... 2152, 2155,	226	1397, 1406, 1408, 1411	
2164, 2165, 2167,	\bibstyle 254, 256, 298, 514	\ClassWarning	
2173, 2175, 2177,	\bibstyle@acmauthoryear	26, 153, 667, 670,	
2179, 2182, 2215,	304	673, 708, 711, 771,	
2216, 2218, 2224, 2227	\bibstyle@acmnumeric 310	1223, 1288, 1371,	
\authornote	\bigskip .. 1443, 1891,	1412, 2291, 2892, 2895	
. 14, 1275, 1316, 2313	1997, 2025, 2033,	\ClassWarningNoLine	
\authornotemark . 14, 1322	2213, 2255, 2285, 2343	699,	
\authors	\box 798, 1875, 1877, 1879,	1377, 1401, 1475, 2277	
1235, 1238, 1243,	1881, 1883, 1885,	\cleaders	2039
1820, 1822, 1828, 2318	1887, 1889, 1891,	\clubpenalty ... 386, 392	
\authorsaddresses 14, 1294	2147, 2160, 2211, 2287	\CodelineIndex	16
		\Collect@Body .. 759,	
B	C	763, 774, 1380, 1704	
\balance	\c@footnote	\color ... 1755, 2367, 2371	
2856	1725	\color@begingroup 434, 447	
\baselineskip	\c@secnumdepth	\color@endbox	796
.... 1757, 1982,	336, 350, 354, 363, 367	\color@endgroup	
1994, 2006, 2021,	\captionsetup .. 726,	437, 450, 631	
2369, 2650, 2651,	728, 730, 732, 741,	\columnwidth ... 443,	
2654, 2655, 2658,	743, 746, 748, 751,	614, 782, 2215, 2252	
2662, 2666, 2736,	753, 761, 767, 776, 2286	\contentsnamefont .. 414	
2737, 2738, 2739,	\ccdesc@parse@finish 1478	\copy	2039
2766, 2767, 2768, 2769	\ccsdesc	\copyright	1767
\baselinestretch	1450, 1451	\copyrightpermissionfootnoterule	
... 2900, 2901, 2903	\ccsdesc@parse@end .	613	
\begin . 19, 2377, 2403, 2547	1450, 1478	\copyrightyear . 17, 1701	
\begingroup	\ccsdesc@parse@finish	\country 11, 1285, 2042, 2269	
344,	1472, 1478	\csname	
387, 401, 410, 499,	CCSXML (environment) .. 16	298, 349, 351, 355,	
1720, 2062, 2620, 2860	\centering 414, 447, 530,	362, 364, 368, 397,	
\bfseries .. 856, 1753,	768, 777, 1999,	417, 418, 432, 446,	
1931, 1933, 1935,	2011, 2157, 2212, 2553	1454, 1455, 1457,	
1939, 1941, 1943,	\cite ... 492, 493, 504, 508	1458, 1459, 1460,	
1945, 1947, 2107,	\citeA		
2110, 2316, 2554,	498		
	\citealt		
	497		
	\citeANP		
	494		
	\citeauthor		
	494		

1461, 1464, 1466, 1833, 1835, 2621, 2644	1005, 1006, 1007, 1009, 1010, 1011, 1013, 1014, 1016, 1017, 1018, 1020, 1021, 1022, 1024, 1026, 1028, 1029, 1030, 1032, 1034, 1035, 1036, 1038, 1039, 1040, 1042, 1043, 1044, 1046, 1047, 1048, 1050, 1051, 1052, 1054, 1055, 1056, 1058, 1059, 1060, 1062, 1063, 1064, 1066, 1067, 1068, 1070, 1071, 1072, 1074, 1075, 1076, 1078, 1079, 1080, 1082, 1083, 1084, 1086, 1087, 1088, 1090, 1091, 1092, 1094, 1095, 1096, 1098, 1099, 1100, 1102, 1103, 1105, 1106, 1107, 1109, 1110, 1112, 1113, 1114, 1115, 1117, 1118, 1119, 1121, 1122, 1123, 1125, 1126, 1127, 1129, 1130, 1131, 1133, 1134, 1135, 1137, 1138, 1139, 1141, 1142, 1143, 1145, 1146, 1147, 1149, 1150, 1151, 1153, 1154, 1155, 1157, 1158, 1159, 1161, 1162, 1163, 1165, 1166, 1167, 1169, 1170, 1171, 1173, 1174, 1175, 1181, 1183, 1184, 1185, 1186, 1187, 1202, 1206, 1207, 1208, 1214, 1253, 1275, 1276, 1277, 1278, 1279, 1280, 1293, 1294, 1296, 1297, 1305,	1306, 1315, 1316, 1328, 1330, 1332, 1334, 1336, 1338, 1340, 1344, 1346, 1348, 1350, 1360, 1361, 1362, 1363, 1365, 1366, 1367, 1368, 1369, 1371, 1373, 1381, 1386, 1414, 1426, 1427, 1451, 1452, 1478, 1538, 1540, 1577, 1578, 1701, 1703, 1705, 1714, 1727, 1732, 1741, 1747, 1843, 1865, 1906, 1928, 1949, 1970, 1998, 2026, 2035, 2042, 2043, 2045, 2046, 2047, 2048, 2050, 2052, 2053, 2056, 2059, 2062, 2086, 2087, 2091, 2092, 2095, 2096, 2098, 2099, 2101, 2102, 2104, 2105, 2107, 2108, 2110, 2111, 2113, 2115, 2120, 2121, 2122, 2123, 2125, 2132, 2133, 2134, 2155, 2156, 2163, 2185, 2191, 2198, 2214, 2230, 2236, 2241, 2256, 2262, 2263, 2264, 2265, 2266, 2267, 2269, 2270, 2271, 2272, 2280, 2281, 2282, 2283, 2285, 2295, 2305, 2308, 2309, 2310, 2311, 2314, 2318, 2340, 2347, 2348, 2353, 2363, 2374, 2381, 2424, 2429, 2435, 2523, 2530, 2535, 2537, 2619, 2623, 2625, 2627, 2637, 2641, 2648, 2674, 2678, 2679,
D		
\day 2419		
\DeclareNewFootnote 617, 619		
\DeclareOptionX 37, 140, 141, 142, 143, 144, 145		
\DeclareRobustCommand 498, 2640		
\DeclareTextFontCommand 689		
\def 24, 37, 139, 192, 194, 196, 198, 200, 202, 204, 206, 208, 233, 235, 237, 239, 241, 243, 245, 247, 249, 251, 253, 255, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266, 267, 269, 271, 273, 275, 276, 280, 282, 284, 286, 288, 290, 318, 334, 359, 373, 397, 398, 407, 410, 423, 424, 425, 426, 428, 439, 451, 456, 457, 458, 459, 460, 478, 509, 613, 620, 622, 634, 760, 764, 775, 781, 784, 788, 791, 809, 810, 811, 812, 840, 845, 848, 850, 852, 854, 931, 932, 933, 935, 936, 937, 939, 940, 941, 943, 944, 945, 947, 948, 949, 951, 953, 954, 958, 959, 960, 962, 963, 964, 966, 967, 968, 970, 971, 972, 974, 975, 976, 978, 979, 981, 982, 983, 987, 988, 989, 993, 994, 995, 999, 1000, 1001,		

2680, 2681, 2687, 2688, 2690, 2691, 2693, 2694, 2696, 2697, 2699, 2700, 2701, 2702, 2703, 2706, 2707, 2710, 2711, 2713, 2714, 2716, 2717, 2718, 2719, 2728, 2729, 2730, 2731, 2746, 2747, 2748, 2749, 2758, 2759, 2760, 2761, 2805, 2806, 2815, 2816, 2866, 2868, 2884, 2885, 2886	134, 159, 186, 278, 299, 328, 335, 338, 350, 354, 358, 363, 367, 379, 391, 406, 486, 502, 508, 510, 625, 681, 706, 709, 731, 769, 1172, 1198, 1204, 1210, 1226, 1233, 1236, 1240, 1241, 1249, 1252, 1257, 1260, 1263, 1270, 1290, 1302, 1311, 1317, 1325, 1375, 1390, 1396, 1399, 1407, 1418, 1421, 1431, 1434, 1437, 1442, 1463, 1468, 1469, 1470, 1473, 1710, 1728, 1739, 1743, 1744, 1751, 1758, 1761, 1762, 1768, 1773, 1780, 1785, 1788, 1789, 1792, 1794, 1795, 1796, 1797, 1807, 1812, 1815, 1868, 1894, 1899, 1972, 1976, 1981, 1989, 1992, 2005, 2013, 2020, 2030, 2036, 2037, 2050, 2051, 2052, 2053, 2055, 2056, 2059, 2116, 2128, 2134, 2140, 2157, 2168, 2178, 2187, 2194, 2202, 2219, 2223, 2232, 2238, 2245, 2258, 2260, 2275, 2284, 2289, 2296, 2300, 2308, 2314, 2319, 2320, 2329, 2331, 2338, 2416, 2427, 2428, 2438, 2449, 2457, 2467, 2478, 2482, 2486, 2495, 2499, 2538, 2567, 2571, 2581, 2591, 2598, 2603, 2611, 2614,	2624, 2648, 2868, 2873, 2880, 2888, 2901 <u>\email</u> 10, <u>1287</u> , 2132, 2191, 2236, 2272 <u>\emph</u> 1779, 1781 <u>\empty</u> 2436 <u>\EnableCrossrefs</u> 18 <u>\end</u> . . . 21, 2379, 2405, 2555 <u>\end@dblfloat</u> <u>787</u> <u>\end@float</u> <u>789</u> <u>\endcsname</u> 297, 298, 349, 351, 355, 362, 364, 368, 397, 417, 418, 432, 446, 1454, 1455, 1457, 1458, 1459, 1460, 1461, 1464, 1466, 1833, 1835, 2621, 2644 <u>\enddescription</u> 863 <u>\endgroup</u> . . . 348, 387, 405, 420, 1803, 2084, 2623, 2625, 2864 <u>\endlist</u> 861, 863 <u>\endminipage</u> <u>622</u> <u>\endtrivlist</u> 2827 <u>\enspace</u> 2714 environments: abstract 17 acks 23 anonsuppress 23 CCSXML 16 marginfigure 21 margintable 21 printonly 22 screenonly 22 sidebar 21 teaserfigure 17 <u>\everypar</u> 327, 382, 393, 2299 <u>\excludecomment</u> . 1446, 2872, 2874, 2878, 2879 <u>\ExecuteOptionsX</u> 47, 55, 63, 71, 80, 88, 100, 104, 112, 120, 128, 138 <u>\expandafter</u> 277, 279, 511, 633, 1454, 1455, 1457, 1458, 1464, 1466, 2621, 2644
<u>\define@boolkey</u> 48, 56, 64, 72, 81, 89, 101, 105, 113, 121, 129, 1273, 1387, 1393, 1404 <u>\define@choicekey</u> 31, 866, 1485 <u>\define@cmdkey</u> 1410 <u>\definecolor</u> 518, 519, 520, 521, 522, 523, 524, 525 <u>\department</u> 11, 1279, <u>2042</u> , 2268 <u>\Description</u> 22, <u>697</u> <u>\description</u> <u>857</u> <u>\descriptionlabel</u> <u>856</u> , 859 <u>\dimexpr</u> . . 779, 798, 2509 <u>\divide</u> 2167, 2173, 2175, 2177, 2179, 2218, 2224 <u>\do</u> 232, 478 <u>\do@url@hyp</u> 478 <u>\DocInput</u> 20 <u>\documentclass</u> 8 <u>\dots</u> 1796		
E <u>\edef</u> 140, 141, 142, 143, 335 <u>\editor</u> 9, <u>1208</u> <u>\egroup</u> 632, 762, 773, 777, 789, 795, 1286, 1809, 1818, 2159, 2193, 2196, 2255, 2274, 2286, 2304, 2318, 2339 <u>\else</u> . 51, 59, 67, 76, 84, 96, 108, 116, 124,		

F		
<code>\familydefault</code>	691	
<code>\fancyfoot</code>		
2450, 2458, 2468,		
2479, 2483, 2496,		
2512, 2566, 2568,		
2572, 2582, 2592,		
2601, 2606, 2610, 2615		
<code>\fancyhead</code> . 2445, 2446,		
2447, 2448, 2453,		
2454, 2455, 2456,		
2462, 2464, 2465,		
2472, 2474, 2475,		
2476, 2484, 2485,		
2487, 2490, 2497,		
2498, 2500, 2503,		
2565, 2576, 2577,		
2578, 2586, 2587,		
2588, 2596, 2597,		
2599, 2600, 2604, 2605		
<code>\fancyheadoffset</code> . . .		
. . . 2509, 2579, 2589		
<code>\fancyhf</code>	2432, 2559	
<code>\fancypagestyle</code> 2431, 2558		
<code>\fi</code>	53, 61, 69, 78,	
86, 98, 110, 118,		
126, 136, 156, 161,		
183, 188, 209, 210,		
222, 234, 236, 238,		
240, 242, 244, 246,		
248, 250, 252, 254,		
256, 258, 260, 262,		
264, 266, 268, 270,		
272, 274, 276, 281,		
283, 285, 287, 289,		
291, 292, 301, 303,		
317, 319, 325, 330,		
335, 341, 352, 356,		
365, 369, 371, 394,		
395, 408, 419, 438,		
475, 479, 488, 506,		
508, 512, 515, 533,		
597, 611, 629, 651,		
663, 683, 686, 692,		
699, 708, 711, 755,		
756, 772, 786, 790,		
815, 1176, 1195,		
1201, 1205, 1213,		
1229, 1234, 1239,		
1244, 1245, 1250,		
1251, 1259, 1265,		
1266, 1267, 1272,		
1292, 1304, 1314,		
1321, 1327, 1343,		
1379, 1383, 1392,		
1398, 1403, 1409,		
1423, 1424, 1433,		
1439, 1440, 1444,		
1462, 1470, 1471,		
1477, 1498, 1501,		
1505, 1511, 1514,		
1517, 1520, 1523,		
1526, 1529, 1533,		
1537, 1576, 1700,		
1712, 1718, 1719,		
1728, 1730, 1742,		
1748, 1749, 1750,		
1756, 1759, 1760,		
1764, 1765, 1770,		
1782, 1787, 1792,		
1796, 1797, 1798,		
1799, 1800, 1801,		
1802, 1810, 1811,		
1817, 1819, 1826,		
1863, 1870, 1898,		
1902, 1903, 1904,		
1926, 1948, 1969,		
1975, 1979, 1985,		
1991, 1996, 2008,		
2010, 2015, 2023,		
2024, 2032, 2040,		
2050, 2052, 2053,		
2055, 2056, 2059,		
2061, 2083, 2112,		
2119, 2130, 2144,		
2145, 2157, 2180,		
2181, 2189, 2197,		
2206, 2225, 2226,		
2234, 2240, 2249,		
2258, 2260, 2279,		
2292, 2294, 2302,		
2304, 2308, 2315,		
2319, 2333, 2336,		
2337, 2338, 2373,		
2380, 2402, 2406,		
2418, 2423, 2427,		
2428, 2437, 2439,		
2440, 2445, 2446,		
2451, 2460, 2470,		
2481, 2483, 2493,		
2494, 2496, 2506,		
2507, 2510, 2513,		
2536, 2555, 2566,		
2569, 2575, 2585,		
2595, 2601, 2602,		
2606, 2607, 2613,		
2616, 2617, 2635,		
2646, 2648, 2712,		
2734, 2764, 2802,		
2819, 2850, 2851,		
2857, 2868, 2876,		
2882, 2885, 2889, 2904		
<code>\firstpagestyle</code>	2557	
<code>\floatname</code>	758	
<code>\flushbottom</code>		
641, 643, 645, 647, 649		
<code>\footnote</code>	2311	
<code>\footnotemark</code> 460, 1298,		
1307, 2281, 2282, 2309		
<code>\footnoterule</code>	620	
<code>\footnotesep</code>	436, 449	
<code>\footnotesize</code>	442,	
2415, 2429, 2450,		
2458, 2468, 2479,		
2483, 2487, 2496,		
2568, 2572, 2582,		
2592, 2601, 2606, 2612		
<code>\footnotetext</code>	1301,	
1303, 1310, 1313, 1320		
<code>\footnotetextauthorsaddresses</code>		
.	1740, 1746	
<code>\footnotetextcopyrightpermission</code>		
.	1751	
<code>\footrulewidth</code>	2434, 2561	
<code>\format</code>	31	
<code>\frenchspacing</code>	2905	
<code>\fulltextwidth</code>		
.	778, 782, 798	
G		
<code>\g@addto@macro</code>		
1212, 1242, 1243,		
1258, 1264, 1271,		
1291, 1298, 1300,		
1303, 1307, 1309,		
1312, 1318, 1319,		
1324, 1326, 1432,		
1438, 1459, 1466,		
1705, 1709, 1711,		
2129, 2141, 2188,		

2195, 2203, 2233, 2239, 2246, 2281, 2282	\hspace 1589, 1600, 1609, 1634, 1646, 1667, 2160, 2212	2457, 2467, 2478, 2486, 2499, 2567, 2571, 2581, 2591, 2611
\gdef 1189, 1190, 1191, 1192, 1194, 1202, 1209, 1211, 1232, 1235, 1237, 1238, 1248, 1256, 1262, 1384, 1413, 1430, 1436, 1455, 1457, 1458, 1464, 1867, 2127, 2131, 2136, 2161, 2162, 2183, 2184, 2186, 2190, 2192, 2199, 2228, 2229, 2231, 2235, 2237, 2242	\Huge 1937, 1939, 1941, 1943, 1945, 1947 \hypersetup 481, 487, 489, 1827	\if@ACM@printacmref 1393, 1824 \if@ACM@printccs 1387, 1806 \if@ACM@printfolios 1404, 2437, 2439, 2445, 2446, 2483, 2496, 2566, 2601, 2606
	I	
	\if 278	
	\if@ACM@acmthm . 64, 2778	2496, 2566, 2601, 2606
	\if@ACM@affiliation@obey 1273, 2037, 2050, 2052, 2053, 2054, 2056, 2059	\if@ACM@review 72, 2358, 2375, 2382 \if@ACM@screen 48, 480, 2870 \if@ACM@sigchi mode 151, 427, 690, 780, 787, 1728, 1730, 2157, 2508
\geometry 537, 540, 547, 554, 561, 568, 575, 582, 589	\if@ACM@anonymous 113, 1231, 1241, 1246, 1270, 1290, 1299, 1308, 1317, 1708, 1716, 1744, 2425, 2877	\if@ACM@timestamp . . 121, 2407, 2511, 2608
\getrefnumber 1376, 1400, 1474, 2308	\if@ACM@authordraft 129, 526, 1752	\if@ACM@urlbreakonhyphens 56, 477
\global 381, 384, 420, 440, 697, 707, 710, 770, 797, 1182, 1196, 1225, 1227, 1228, 1269, 1822, 1823, 1836, 1838, 2124, 2146, 2147, 2157, 2207, 2210, 2250, 2287, 2290, 2368, 2372, 2833, 2835, 2837, 2849	\if@ACM@authorversion 81, 1758, 1774 \if@ACM@badge 1352, 1892, 2001, 2017 \if@ACM@balance 101, 2830, 2854 \if@ACM@journal 149, 184, 727, 1198, 1419, 1813, 2044, 2275, 2298	\if@acmowned 1483 \if@Description@present 693, 706, 709, 769, 2289 \if@files 416, 513 \if@insideauthorgroup 1220, 1226 \if@nobreak 326 \if@noskipsec 319, 383 \if@printcopyright 1479, 1766 \if@printpermission 1481, 1759 \if@twocolumn 2855
\grantnum 23, 2867	\if@ACM@journal@bibstrip 150, 1745, 1762, 1778, 1790, 2325, 2442, 2562	\if@undescrbed@images 695, 698
\grantsponsor 23, 2866		
	H	
\hbox . 451, 1727, 1732, 2038	\if@ACM@maketitle@typeset 864, 1381	
\headrulewidth 2433, 2560	\if@ACM@manuscript 148, 219, 1416, 1761, 1771	
\hfill 2028, 2371		
\href . 1895, 1900, 1982, 1994, 2006, 2021, 2888	\if@ACM@natbib 105, 224, 315, 491	\ifcase 163, 190, 463, 535, 600, 636, 734, 801, 929, 1340, 1541, 1579, 1844, 1873, 1907, 1929, 1950, 2064, 2088, 2169, 2220, 2383, 2443, 2524, 2563, 2683, 2720, 2750, 2807, 2831
\hrule 614, 621, 2028	\if@ACM@natbib@override 105	\ifcsname 297
\hsize 443, 1726, 1970, 1971, 1998, 2000, 2026, 2063, 2155, 2209, 2252	\if@ACM@newfonts 665, 676	\ifdim 323, 343, 375, 400, 2370
\hskip 346, 360, 390, 403, 407, 1897, 1984, 1993, 2009, 2018, 2039, 2824	\if@ACM@nonacm 89, 1375, 1399, 1473, 1751, 1789, 2275, 2320, 2449,	

<code>\IfFileExists</code>	667, 670, 673	449, 697, 1277,	<code>\Large</code>	2086, 2104, 2693,	
<code>\IfInteger</code>	1411	1278, 1280, 1293,		2694, 2696, 2697, 2699	
<code>\ifNAT@numbers</code>	508	2042, 2043, 2045,	<code>\large</code>	1753,	
<code>\ifnum</code>	152, 157, 335,	2046, 2047, 2048,		2091, 2096, 2099,	
	336, 350, 354, 363,	2049, 2050, 2264,		2687, 2688, 2690, 2691	
	367, 1376, 1400,	2303, 2310, 2318, 2825	<code>\lastbox</code>	385, 2299	
	1468, 1469, 1470,	<code>\immediate</code>	418, 514	<code>\leaders</code>	2028
	1474, 1494, 1499,	<code>\includecomment</code>	2871, 2875, 2881	<code>\leavevmode</code>	319, 2028, 2211
	1502, 1506, 1512,			<code>\leftmargin</code>	840,
	1515, 1518, 1521,	<code>\includegraphics</code>	1896, 1901,		845, 848, 850, 852, 854
	1524, 1527, 1530,		1983, 1995, 2007, 2022	<code>\leftmargini</code>	824,
	1534, 1718, 2166,	<code>\indent</code>	2806		825, 826, 827, 840, 841
	2217, 2257, 2259,	<code>\input</code>	654	<code>\leftmarginii</code>	830,
	2308, 2538, 2540, 2609	<code>\InputIfFileExists</code>	25		831, 832, 833, 845, 846
<code>\ifPDFTeX</code>	653	<code>\institution</code>	11, 1278, 2042, 2265	<code>\leftmarginiii</code>	833, 834, 848, 849
<code>\IfSubStr</code>	1223, 1288	<code>\interfootnotelinepenalty</code>	430	<code>\leftmarginiv</code>	834, 835, 850, 851
<code>\ifvmode</code>	2036	<code>\interlinepenalty</code>	347, 404, 430	<code>\leftmarginv</code>	835, 836, 852, 853
<code>\ifvoid</code>	625	<code>\item</code>	2824	<code>\leftmarginvi</code>	836, 854, 855
<code>\ifx</code>	189, 233,	<code>\itshape</code>	1763, 2680,	<code>\leftskip</code>	2027, 2253, 2676
	235, 237, 239, 241,		2681, 2702, 2703,	<code>\let</code>	254, 256, 268,
	243, 245, 247, 249,		2716, 2728, 2748, 2815		270, 272, 298, 337,
	251, 253, 255, 257,				452, 453, 492, 493,
	259, 261, 263, 265,				494, 495, 496, 497,
	267, 269, 271, 273,				500, 504, 635, 687,
	275, 280, 282, 284,				701, 702, 704, 705,
	286, 288, 290, 510,				712, 713, 714, 715,
	1193, 1204, 1208,				716, 717, 718, 719,
	1230, 1233, 1247,				720, 721, 722, 723,
	1249, 1254, 1255,				760, 761, 765, 766,
	1261, 1323, 1375,				775, 776, 781, 782,
	1428, 1429, 1435,				783, 844, 859, 863,
	1442, 1454, 1463,				1281, 1282, 1283,
	1473, 1739, 1743,				1284, 1285, 1374,
	1783, 1792, 1795,				1447, 1721, 1722,
	1796, 1797, 1807,				1723, 1724, 1736,
	1812, 1866, 1894,				1737, 1738, 1741,
	1899, 1972, 1976,				1747, 1822, 1823,
	1981, 1989, 1992,				2057, 2058, 2060,
	2005, 2013, 2020,				2124, 2146, 2207,
	2030, 2116, 2126,				2213, 2250, 2255,
	2134, 2135, 2185,				2306, 2307, 2341,
	2191, 2198, 2230,				2342, 2344, 2345,
	2236, 2241, 2276,				2350, 2351, 2352,
	2284, 2296, 2314,				2354, 2355, 2356,
	2319, 2331, 2338,				2626, 2628, 2630,
	2416, 2427, 2436,				2631, 2633, 2639,
	2621, 2644, 2648,				
	2868, 2885, 2887, 2901				
<code>\ifxetex</code>	678				
<code>\ignorespaces</code>	396, 436,				

2642, 2645, 2890,	1980, 1999, 2027,	\newif 148, 149,
2891, 2898, 2899, 2900	2147, 2210, 2211, 2287	150, 151, 665, 693,
\libertineLF 689	\month 1339, 2419	695, 864, 1220,
\lineskip 2212, 2254	\moveleft 797	1352, 1479, 1481, 1483
\linespacing . . . 413, 414	\multiply 2545	\newlength
\liningnums 687		1354, 1356, 1357, 2360
\list 857	N	\newsavebox 2359
\listisep . . . 838, 839, 843	\NAT@setcites 294	\newskip 838, 2153
\listparindent 842	\NAT@aysep 285	\newtheorem
\LoadClass 212	\NAT@citetp 500	2781, 2784, 2787,
\long . . . 428, 439, 760,	\NAT@close	2790, 2793, 2797, 2800
764, 775, 1381,	234, 236, 238, 240, 283	\newtheoremstyle
1384, 1386, 1705, 2347	\NAT@cmprs . . 262, 264, 266 2735, 2765
\loop 2367, 2539	\NAT@cmt 289	\newwrite 417
\LTX@adddotafter . . .	\NAT@ctype 500	\next 2623, 2625, 2635
. 2645, 2648	\NAT@find@eq 277	\nobreak 376, 2316
	\NAT@fullfalse 500	\noindent
M	\NAT@longnamestrue . 274	. 426, 1443, 1738,
\makeatletter 410	\NAT@merge . . 268, 270, 272	1809, 1818, 1846,
\makebox 1753, 2548	\NAT@nmfmt 276	1848, 1850, 1852,
\makelabel 859	\NAT@numbersfalse . . 248	1872, 1893, 1980,
\MakeTextUppercase .	\NAT@numberstrue 250, 252	1987, 1990, 2014,
. . . . 2127, 2129,	\NAT@open 234,	2028, 2029, 2031,
2678, 2687, 2690,	236, 238, 240, 281, 500	2114, 2147, 2148,
2693, 2696, 2706, 2710	\NAT@partrue 500	2210, 2254, 2287,
\maketitle 20, 1714	\NAT@rem@eq 279	2288, 2316, 2317, 2816
\MakeUppercase 2632	\NAT@sep 242, 244, 246, 291	\noindentparagraph .
\marginfigure 763	\NAT@sort . . . 258, 260, 266 1858, 2665
marginfigure (environ-	\NAT@superfalse 250	\nolinkurl 2193,
ment) 21	\NAT@supertrue 252	2196, 2237, 2239, 2272
\marginpar 428,	\NAT@swafalse 499	\normalbaselines . . . 2156
762, 768, 777, 1893	\NAT@up 276	\normalcolor 627
\marginparsep . . 779, 2509	\NAT@yrsep 287	\normalfont
\marginparwidth . 779, 2509	\NeedsTeXFormat 1	. 451, 1443, 1732,
\margintable 774	\newblock 501	2087, 2092, 2101,
margintable (environ-	\newbox . . 1713, 2034, 2151	2102, 2104, 2105,
ment) 21	\newcommand . 304, 310,	2364, 2731, 2746,
\mathchardef . . 2193, 2196	507, 697, 1188,	2758, 2761, 2822, 2905
\mbox 276	1268, 1322, 1359,	\normalparindent . . . 612
\mdseries	1364, 1427, 1449,	\normalsize
1952, 1954, 1956,	2049, 2054, 2414,	1949, 2087, 2101,
1960, 1962, 1964,	2665, 2858, 2867, 2883	2102, 2105, 2365, 2905
1966, 1968, 2108, 2111	\newcount . 1216, 1218, 2361	\num@authorgroups . .
\medskip . . 1846, 1848,	\newcounter 1448, 2410, 2412 1216,
1850, 1852, 2147,	\newdimen . . . 778, 816,	1227, 1718, 2169,
2149, 2211, 2293, 2316	2152, 2517, 2519, 2521	2173, 2175, 2220, 2259
\mktitle@bx 1713,	\newenvironment	\num@authors
1875, 1877, 1879, 763, 774, 1704	. . . 1218, 1225, 2257
1881, 1883, 1885,	\newfloat 757	\number 335
1887, 1889, 1891,		\numberline 355, 368

<code>\numexpr</code> .	2409, 2411, 2413	1694, 1847, 1849, 1851, 1853, 1855, 1857, 1859, 1861, 1876, 1878, 1880, 1882, 1884, 1886, 1888, 1890, 1910, 1912, 1914, 1916, 1918, 1920, 1922, 1924, 1932, 1934, 1936, 1938, 1940, 1942, 1944, 1946, 1953, 1955, 1957, 1959, 1961, 1963, 1965, 1967, 2067, 2069, 2071, 2073, 2075, 2077, 2079, 2081, 2090, 2093, 2094, 2097, 2100, 2103, 2106, 2109, 2171, 2172, 2174, 2176, 2222, 2386, 2388, 2390, 2392, 2394, 2396, 2398, 2400, 2452, 2461, 2471, 2526, 2531, 2570, 2580, 2590, 2685, 2686, 2689, 2692, 2695, 2698, 2704, 2708, 2722, 2723, 2724, 2725, 2726, 2727, 2732, 2733, 2752, 2753, 2754, 2755, 2756, 2757, 2762, 2763, 2809, 2810, 2811, 2812, 2813, 2814, 2817, 2818, 2834, 2836, 2838, 2840, 2842, 2844, 2846, 2848	61, 69, 78, 86, 98, 102, 110, 118, 126, 136
O			
<code>\onehalfspacing</code>	221		<code>\PackageInfo</code> . . 50, 52, 58, 60, 66, 68, 74, 77, 83, 85, 91, 97, 107, 109, 115, 117, 123, 125, 131, 135, 956, 985, 991, 997, 1003
<code>\openout</code>	418		
<code>\or</code>	166, 168, 170, 172, 174, 176, 178, 180, 193, 195, 197, 199, 201, 203, 205, 207, 465, 466, 467, 468, 469, 470, 472, 473, 539, 546, 553, 560, 567, 574, 581, 588, 602, 603, 604, 606, 607, 608, 609, 610, 638, 639, 640, 642, 644, 646, 648, 650, 736, 737, 738, 739, 740, 742, 745, 750, 803, 804, 805, 806, 807, 808, 813, 814, 934, 938, 942, 946, 950, 957, 961, 965, 969, 973, 977, 980, 986, 992, 998, 1004, 1008, 1012, 1015, 1019, 1023, 1025, 1027, 1031, 1033, 1037, 1041, 1045, 1049, 1053, 1057, 1061, 1065, 1069, 1073, 1077, 1081, 1085, 1089, 1093, 1097, 1101, 1104, 1108, 1111, 1116, 1120, 1124, 1128, 1132, 1136, 1140, 1144, 1148, 1152, 1156, 1160, 1164, 1168, 1340, 1341, 1342, 1542, 1544, 1547, 1549, 1550, 1552, 1554, 1556, 1559, 1562, 1565, 1567, 1570, 1573, 1580, 1591, 1602, 1610, 1616, 1622, 1636, 1648, 1655, 1669, 1676, 1682, 1689,		<code>\PageIndex</code> 15 <code>\pageref</code> 2421 <code>\pagestyle</code> 2515 <code>\par</code> . 320, 376, 412, 623, 792, 1443, 1741, 1747, 1759, 1763, 1809, 1818, 1846, 1848, 1850, 1852, 1875, 1877, 1879, 1891, 1990, 1997, 2014, 2025, 2028, 2031, 2033, 2052, 2053, 2055, 2056, 2114, 2118, 2147, 2149, 2156, 2158, 2186, 2188, 2195, 2203, 2211, 2213, 2231, 2233, 2239, 2246, 2253, 2255, 2285, 2286, 2287, 2289, 2303, 2316, 2339, 2343, 2347, 2820 <code>\paragraph</code> 2661 <code>\parbox</code> 530, 1986, 2004, 2011, 2019, 2364, 2552 <code>\parindent</code> 598, 612, 825, 1741, 1747, 1757, 2661, 2677, 2717, 2747 <code>\parskip</code> 598, 1757 <code>\part</code> 2670 <code>\PassOptionsToClass</code> 144, 145 <code>\pdfgentounicode</code> . . . 662 <code>\pdfglyphtounicode</code> 655, 656, 657, 658, 659, 660, 661 <code>\pdfstringdefDisableCommands</code> 455 <code>\phantomsection</code> 228, 2297, 2862 <code>\popQED</code> 2827
		<code>\orcid</code> 10, 1293	
		<code>\outer@nobreak</code> 794	
P			
<code>\p@</code>	421, 598, 605, 613, 614, 620, 621, 2650, 2654, 2658, 2659, 2662, 2663, 2666, 2667, 2671, 2672, 2822		
		<code>\PackageError</code> . . . 53,	

<code>\position</code> . . . 11, 1277, 1281, 1282, 1283, 1284, 1285, 2042, 2264	1322, 1323, 1376, 1400, 1454, 1463, 1473, 1474, 1494, 1499, 1502, 1506, 1512, 1515, 1518, 1521, 1524, 1527, 1530, 1534, 1541, 1579, 1736, 1737, 1845, 1874, 1908, 1930, 1951, 2065, 2089, 2154, 2164, 2165, 2166, 2167, 2170, 2173, 2175, 2177, 2179, 2182, 2212, 2215, 2216, 2217, 2218, 2221, 2224, 2227, 2257, 2259, 2281, 2308, 2362, 2384, 2385, 2387, 2389, 2411, 2413, 2416, 2444, 2525, 2527, 2528, 2529, 2532, 2533, 2534, 2537, 2538, 2540, 2543, 2544, 2545, 2546, 2564, 2609, 2621, 2644, 2648, 2684, 2721, 2751, 2808, 2822, 2832	2841, 2843, 2845, 2847
<code>\postcode</code>		<code>\reset@font</code> 429, 442
. 11, 1284, 2042, 2263		<code>\reversemarginpar</code> . . 596
<code>printonly</code> (environment) 22		<code>\rightarrow</code> 1451
<code>\ProcessOptionsX</code> . . . 146		<code>\rightskip</code> 2675
<code>\proof</code> 2820		<code>\rlap</code> 2549
<code>\proofname</code> 2820		<code>\rule</code> 436, 449, 2551
<code>\protect</code> 355, 368		
<code>\protected@edef</code>		S
. 340, 431, 445		<code>\savebox</code> 2364
<code>\providecommand</code>		<code>screenonly</code> (environ- ment) 22
. 501, 505, 2715		<code>\scriptsize</code> . . . 2367, 2371
<code>\ProvidesClass</code> 5		<code>\scshape</code> 2718, 2805
<code>\ProvidesFile</code> 3		<code>\section</code> 227, 1854, 1856, 1860, 1862, 2301, 2649, 2861
<code>\ps@headings</code> . . 2352, 2356		<code>\section@raggedright</code> 2674, 2678, 2679, 2687, 2688, 2690, 2691, 2693, 2694, 2696, 2697, 2699, 2700, 2701, 2706, 2707, 2710, 2711
<code>\ps@myheadings</code> 2351, 2355		<code>\Sectionformat</code> 2622, 2626, 2628, 2639
<code>\ps@plain</code> 2350, 2354		<code>\SelectFootnoteRule</code> 616, 618
<code>\pushQED</code> 2821		<code>\setbox</code> 385, 440, 797, 1980, 1999, 2027, 2038, 2147, 2157, 2210, 2287, 2299
<code>\put</code> 2378, 2404		<code>\setcitestyle</code> 24, 231, 305, 311
Q		<code>\setcopyright</code> . . . 17, 1538
<code>\qed</code> 2821		<code>\setcounter</code> 1731, 1804, 1869, 2411, 2413, 2682, 2705, 2709
<code>\quad</code> 397, 2463, 2466, 2473, 2477, 2610		<code>\setkeys</code> 37, 155, 1181, 1414, 1538, 2137, 2138, 2142, 2143, 2200, 2201, 2204, 2205, 2243, 2244, 2247, 2248
R		<code>\setlength</code> 598, 599, 605, 612, 818, 819, 824, 830, 833, 834, 835, 836, 1355, 1358, 2366
<code>\raggedright</code>		<code>\setmonofont</code> 680
. . . 1986, 2027, 2253	<code>\removelastskip</code> 412	
<code>\raisebox</code>	<code>\renewcommand</code> . . 226, 230, 231, 234, 236, 238, 240, 242, 244, 246, 296, 691, 856, 1222, 1287, 1706, 1725, 2268, 2433, 2434, 2560, 2561, 2649, 2653, 2657, 2661, 2670	
. 1753, 1982, 1994, 2006, 2021, 2548, 2550	<code>\renewenvironment</code> . . . 759, 857, 1380, 2820	
<code>\real@adddotafter</code> . .	<code>\repeat</code> 2370, 2542	
. 2630, 2633	<code>\RequirePackage</code> . . 29, 30, 213, 214, 215, 216, 217, 218, 220, 223, 225, 454, 516, 517, 527, 534, 615, 652, 664, 677, 679, 682, 684, 685, 725, 1445, 2349, 2839,	
<code>\realSectionformat</code> .		
. . . 2626, 2638, 2639		
<code>\received</code> 19, 1427		
<code>\RecordChanges</code> 17		
<code>\ref</code> 2328, 2335		
<code>\refname</code> 227, 228		
<code>\refstepcounter</code> 339		
<code>\relax</code> 152, 157, 164, 191, 277, 278, 321, 340, 342, 346, 360, 374, 389, 399, 407, 418, 464, 536, 601, 635, 637, 735, 802, 930, 1217, 1219, 1225, 1227,		

<code>\settopmatter</code> . 19, 95, 1414, 1415, 1417, 1420, 1422, 1425, 2324	<code>\subsubsection</code> 2657	<code>\tw@</code> 270
<code>\setTrue</code> 411	<code>\subtitle</code> 10, 1214	<code>\two@digits</code> . . . 2419, 2420
<code>\SetWatermarkColor</code> . 529	<code>\subtitlenote</code> . . 14, 1306	<code>\twocolumn</code> 1881, 1883, 1885, 1887, 1889
<code>\SetWatermarkFontSize</code> 528	T	U
<code>\SetWatermarkText</code> . . 530	<code>\teaserfigure</code> 1704	<code>\unskip</code> 388, 457, 624, 1280, 1286, 1293, 2039, 2042, 2043, 2045, 2046, 2047, 2048, 2049, 2059, 2118, 2262, 2263, 2264, 2265, 2266, 2267, 2268, 2269, 2270, 2272, 2310, 2318, 2335, 2348
<code>\sfdefault</code> 691	<code>teaserfigure</code> (environ- ment) 17	
<code>\sffamily</code> 1931, 1933, 1935, 1937, 1939, 1941, 1945, 2086, 2091, 2095, 2429, 2554, 2678, 2679, 2680, 2687, 2688, 2690, 2691, 2696, 2697, 2706, 2707, 2710, 2711	<code>\terms</code> 16, 1371	
	<code>\textbf</code> 1456, 1468	
	<code>\textbullet</code> 458, 1455, 2463, 2466, 2473, 2477	
	<code>\textcolor</code> 2554	
	<code>\textheight</code> 2370	
	<code>\textit</code> 1469, 2326, 2330, 2331, 2332	
	<code>\textrightarrow</code> 459, 1451, 1465	<code>\unvbox</code> 441, 628, 633
<code>\shortauthors</code> 20, 1247, 1248, 1255, 1256, 1258, 1261, 1262, 1264, 1821, 1823, 2428	<code>\textwidth</code> 779, 798, 799, 1726, 1970, 1998, 2026, 2063, 2164, 2209	<code>\upshape</code> 856
<code>\shortcite</code> 504, 507	<code>\thanks</code> 14, 1706, 2347	<code>\url</code> 1577, 2868
<code>\shorttitle</code> 2448, 2456, 2466, 2477, 2484, 2497	<code>\thankses</code> 1709, 1711, 1739, 2347	<code>\UrlBreakPenalty</code> 2193, 2196
<code>\showeprint</code> 2883	<code>\the</code> 1337, 1339, 2367, 2371, 2419, 2545	<code>\urlstyle</code> . . . 462, 471, 474
<code>\sidebar</code> 757	<code>\theACM@time@hours</code> 2413, 2420	<code>\usebox</code> 2378, 2404
<code>sidebar</code> (environment) . 21		<code>\usepackage</code> 9, 10, 11, 12, 13, 14
<code>\skip</code> 626		V
<code>\small</code> . . 429, 762, 769, 777, 1443, 1846, 1848, 1850, 1852, 2092, 2299, 2316, 2566	<code>\theACM@time@minutes</code> 2420	<code>\value</code> 1470
<code>\smallskipamount</code> . . . 839	<code>\theenumi</code> 809	<code>\vbox</code> 440, 797, 1980, 1999, 2027, 2147, 2210, 2287
<code>\space</code> 364, 1224, 1289, 1833, 2059, 2868, 2892, 2895, 2903	<code>\theenumii</code> 810	<code>\vskip</code> 377, 412, 626, 634, 792
<code>\specialcomment</code> 2859	<code>\theenumiii</code> 811	<code>\vspace</code> 2890
<code>\standardpagestyle</code> . 2430	<code>\theenumiv</code> 812	<code>\vtop</code> 2157
<code>\startPage</code> 16, 1369	<code>\thefootnote</code> 1725	W
<code>\state</code> . 11, 1283, 2042, 2267	<code>\theoremstyle</code> 2776, 2779, 2795, 2803	<code>\wd</code> 799, 2039
<code>\stepcounter</code> 1301, 1303, 1310, 1313, 1320, 1453	<code>\thepage</code> 2421, 2437, 2439, 2445, 2446, 2483, 2496, 2566, 2601, 2606	<code>\write</code> 514
<code>\streetaddress</code> 11, 1281, 2042, 2262	<code>\thispagestyle</code> 1871	X
<code>\string</code> . . . 514, 1224, 1289, 1371, 2312, 2313, 2892, 2895, 2903	<code>\thmname</code> 2745, 2775	<code>\xdef</code> 281, 283, 285, 287, 289, 291
<code>\strut</code> 2004, 2019	<code>\thmnote</code> 2745, 2775	Y
<code>\strutbox</code> 436, 449	<code>\thmnumber</code> 2745, 2775	<code>\year</code> 1337, 2419
<code>\subsection</code> 2653	<code>\thr@@</code> 272	Z
	<code>\time</code> 2408, 2411, 2413	<code>\z@</code> . . 260, 264, 323, 343, 375, 385, 400, 413, 436, 449, 599, 634, 729, 733, 744, 824,
	<code>\title</code> 10, 2312	
	<code>\titlenote</code> . . 14, 1297, 2313	
	<code>\topsep</code> . . . 843, 847, 2822	
	<code>\trivlist</code> 2823	

830, 842, 1741,	2253, 2299, 2433,	2653, 2657, 2665,
1747, 1753, 1757,	2434, 2518, 2520,	2670, 2677, 2729, 2759
1836, 1838, 1982,	2522, 2548, 2550,	
1994, 2006, 2021,	2560, 2561, 2649,	\z@skip 412, 792, 847, 2676