

NAME

updmap – manage TeX font maps, per-user
updmap-sys – manage TeX font maps, system-wide

SYNOPSIS

updmap [*OPTION*] ... [*COMMAND*]
updmap-sys [*OPTION*] ... [*COMMAND*]

DESCRIPTION

updmap version svn33988 (2014-05-12 15:39:32 +0900)

Update the default font map files used by pdftex, dvips, and dvipdfm(x), and optionally pxdvi, as determined by all configuration files updmap.cfg (the ones returned by running "kpsewhich **--all** updmap.cfg", but see below).

Among other things, these map files are used to determine which fonts should be used as bitmaps and which as outlines, and to determine which font files are included in the PDF or PostScript output.

updmap-sys is intended to affect the system-wide configuration, while updmap affects personal configuration files only, overriding the system files. As a consequence, once updmap has been run, even a single time, running updmap-sys no longer has any effect. (updmap-sys issues a warning in this situation.)

By default, the TeX filename database (ls-R) is also updated.

OPTIONS

--cnffile FILE
read FILE for the updmap configuration (can be given multiple times, in which case all the files are used)

--dvipdfmxoutputdir DIR
specify output directory (dvipdfm(x) syntax)

--dvipsoutputdir DIR
specify output directory (dvips syntax)

--pdftexoutputdir DIR
specify output directory (pdftex syntax)

--pxdvioutputdir DIR
specify output directory (pxdvi syntax)

--outputdir DIR
specify output directory (for all files)

--copy
cp generic files rather than using symlinks

--force
recreate files even if config hasn't changed

--nomkmap
do not recreate map files

--nohash
do not run texhash

--sys affect system-wide files (equivalent to updmap--sys)

-n, --dry-run
only show the configuration, no output

--quiet, --silent
reduce verbosity

Commands:

--help show this message and exit

--version
show version information and exit

--showoption OPTION
show the current setting of OPTION

--showoptions OPTION
show possible settings for OPTION

--setoption OPTION VALUE
set OPTION to value; option names below

--setoption OPTION=VALUE
as above, just different syntax

--enable MAPTYPE MAPFILE
add "MAPTYPE MAPFILE" to updmap.cfg, where MAPTYPE is Map, MixedMap, or KanjiMap

--enable Map=MAPFILE
add "Map MAPFILE" to updmap.cfg

--enable MixedMap=MAPFILE add "MixedMap MAPFILE" to updmap.cfg

--enable KanjiMap=MAPFILE add "KanjiMap MAPFILE" to updmap.cfg

--disable MAPFILE
disable MAPFILE, of whatever type

--listmaps
list all active and inactive maps

--listavailablemaps
same as **--listmaps**, but without unavailable map files

--syncwithtrees
disable unavailable map files in updmap.cfg

Explanation of the map types: the (only) difference between Map and MixedMap is that MixedMap entries are not added to psfonts_pk.map. The purpose is to help users with devices that render Type 1 outline fonts worse than mode-tuned Type 1 bitmap fonts. So, MixedMap is used for fonts that are available as both Type 1 and Metafont. KanjiMap entries are added to psfonts_t1.map and kanjix.map.

Explanation of the OPTION names for **--showoptions**, **--showoption**, **--setoption**:

dvipsPreferOutline
true,false (default true)

Whether dvips uses bitmaps or outlines, when both are available.

`dvipsDownloadBase35`

true,false (default true)

Whether dvips includes the standard 35 PostScript fonts in its output.

`pdftexDownloadBase14`

true,false (default true)

Whether pdftex includes the standard 14 PDF fonts in its output.

`pxdviUse`

true,false (default false)

Whether maps for pxdvi (Japanese-patched xdvi) are under updmap's control.

`kanjiEmbed`

(any string)

`kanjiVariant`

(any string)

See below.

LW35 `URWkb,URW,ADOBEkb,ADOBE` (default `URWkb`)

Adapt the font and file names of the standard 35 PostScript fonts.

URWkb

URW fonts with "berry" filenames (e.g. `uhvbo8ac.pfb`)

URW URW fonts with "vendor" filenames (e.g. `n019064l.pfb`)

ADOBEkb

Adobe fonts with "berry" filenames (e.g. `phvbo8an.pfb`)

ADOBE

Adobe fonts with "vendor" filenames (e.g. `hvnbo____.pfb`)

These options are only read and acted on by updmap; dvips, pdftex, etc., do not know anything about them. They work by changing the default map file which the programs read, so they can be overridden by specifying command-line options or configuration files to the programs, as explained at the beginning of updmap.cfg.

The options `kanjiEmbed` and `kanjiVariant` specify special replacements in the map lines. If a map contains the string `@kanjiEmbed@`, then this will be replaced by the value of that option; similarly for `kanjiVariant`. In this way, users of Japanese TeX can select different fonts to be included in the final output.

ENVIRONMENT

Explanation of trees and files normally used:

If `--cnffile` is specified on the command line (possibly multiple times), its value(s) are used. Otherwise, updmap reads all the updmap.cfg files found by running `'kpsewhich -all updmap.cfg'`, in the order returned by `kpsewhich`.

In any case, if multiple updmap.cfg files are found, all the maps mentioned in all the updmap.cfg files are merged.

Thus, if updmap.cfg files are present in all trees, and the default layout is used as shipped with TeX Live, the following files are read, in the given order.

For updmap-sys:

```
TEXMFCONFIG $TEXLIVE/YYYY/texmf-config/web2c/updmap.cfg
TEXMFSYSVAR $TEXLIVE/YYYY/texmf-var/web2c/updmap.cfg
TEXMFLOCAL  $TEXLIVE/texmf-local/web2c/updmap.cfg
TEXMFDIST   $TEXLIVE/YYYY/texmf-dist/web2c/updmap.cfg
```

For updmap:

```
TEXMFCONFIG $HOME/.texlive/YYYY/texmf-config/web2c/updmap.cfg
TEXMFVAR     $HOME/.texlive/YYYY/texmf-var/web2c/updmap.cfg
TEXMFHOME    $HOME/texmf/web2c/updmap.cfg
TEXMFCONFIG $TEXLIVE/YYYY/texmf-config/web2c/updmap.cfg
TEXMFSYSVAR  $TEXLIVE/YYYY/texmf-var/web2c/updmap.cfg
TEXMFLOCAL   $TEXLIVE/texmf-local/web2c/updmap.cfg
TEXMFDIST    $TEXLIVE/YYYY/texmf-dist/web2c/updmap.cfg
```

(where YYYY is the TeX Live release version).

According to the actions, updmap might write to one of the given files or create a new updmap.cfg, described further below.

Where changes are saved:

If config files are given on the command line, then the first one given will be used to save any changes from **--setoption**, **--enable** or **--disable**. If the config files are taken from kpsewhich output, then the algorithm is more complex:

- 1) If *\$TEXMFCONFIG/web2c/updmap.cfg* or *\$TEXMFHOME/web2c/updmap.cfg* appears in the list of used files, then the one listed first by kpsewhich **--all** (equivalently, the one returned by kpsewhich updmap.cfg), is used.
- 2) If neither of the above two are present and changes are made, a new config file is created in *\$TEXMFCONFIG/web2c/updmap.cfg*.

In general, the idea is that if a given config file is not writable, a higher-level one can be used. That way, the distribution's settings can be overridden for system-wide using TEXMFLOCAL, and then system settings can be overridden again for a particular using TEXMFHOME.

Resolving multiple definitions of a font:

If a font is defined in more than one map file, then the definition coming from the first-listed updmap.cfg is used. If a font is defined multiple times within the same map file, one is chosen arbitrarily. In both cases a warning is issued.

Disabling maps:

updmap.cfg files with higher priority (listed earlier) can disable maps mentioned in lower priority (listed later) updmap.cfg files by writing, e.g.,

```
#! Map mapname.map
```

or

```
#! MixedMap mapname.map
```

in the higher-priority `updmap.cfg` file.

As an example, suppose you have a copy of MathTime Pro fonts and want to disable the Belleek version of the fonts; that is, disable the map `belleek.map`. You can create the file `$TEXMFCONFIG/web2c/updmap.cfg` with the content

```
#! Map belleek.map Map mt-plus.map Map mt-yy.map
```

and call `updmap`.

`updmap` writes the map files for `dvips` (`psfonts.map`) and `pdftex` (`pdftex.map`) to the `TEXMFVAR/fonts/map/updmap/{dvips,pdftex}/` directories.

The log file is written to `TEXMFVAR/web2c/updmap.log`.

When `updmap-sys` is run, `TEXMFSYSCONFIG` and `TEXMFSYSVAR` are used instead of `TEXMFCONFIG` and `TEXMFVAR`, respectively. This is the only difference between `updmap-sys` and `updmap`.

Other locations may be used if you give them on the command line, or these trees don't exist, or you are not using the original TeX Live.

To see the precise locations of the various files that will be read and written, give the `-n` option (or read the source).

EXAMPLES

For step-by-step instructions on making new fonts known to TeX, read <http://tug.org/fonts/fontinstall.html>. For even more terse instructions, read the beginning of the main `updmap.cfg`.

FILES

Configuration and input files:

updmap.cfg

Main configuration file. In *texmf-dist/web2c* by default, but may be located elsewhere depending on your distribution. Each *texmf* tree read should have its own *updmap.cfg*.

dvips35.map

Map file for standard 35 PostScript fonts for use with **dvips**(1).

pdftex35.map

Map file for standard 35 PostScript fonts for use with **pdftex**(1).

ps2pk35.map

Map file for standard 35 PostScript fonts for use with **ps2pk**(1).

Output files:

psfonts.map

For **dvips**(1). Same as *psfonts_t1.map* if option **dvipsPreferOutline** active, else as *psfonts_pk.map*.

psfonts_pk.map

For **dvips**(1). Without information from MixedMap files. (Setting of **dvipsPreferOutline** ignored.)

psfonts_t1.map

For **dvips**(1). With information from MixedMap files. (Setting of **dvipsPreferOutline** ignored.)

download35.map

For **dvips**(1). Always downloads the standard 35 fonts. (Setting of **dvipsDownloadBase35** ignored.)

builtin35.map

For **dvips**(1). Never downloads the standard 35 fonts. (Setting of **dvipsDownloadBase35** ignored.)

pdftex.map

For **pdftex**(1). Same as *pdftex_dl14.map* if option **pdftexDownloadBase14** active, else as *pdftex_ndl14.map*.

pdftex_dl14.map

For **pdftex**(1). Always downloads the standard 14 fonts.

pdftex_ndl14.map

For **pdftex**(1). Never downloads the standard 14 fonts.

ps2pk.map

Similar to *psfonts.map* file, but forces all fonts to be downloaded, so this map file can be used with **xdvi**(1) and **ps2pk**(1).

Configuration files for **dvips**(1):

config.builtin35

Loads *builtin35.map* instead of *psfonts.map*.

config.download35

Loads *download35.map* instead of *psfonts.map*.

config.outline

Loads *psfonts_t1.map* instead of *psfonts.map*.

config.pdf

Loads *psfonts_t1.map* instead of *psfonts.map* and has additional optimizations for PDF generation.

config.pk

Loads *psfonts_pk.map* instead of *psfonts.map*.

config.www

Loads *psfonts_t1.map* instead of *psfonts.map*. (For compatibility with old versions.)

config.gstopk

Loads *psfonts_t1.map* instead of *psfonts.map*.

REPORTING BUGS

Report bugs to: tex-k@tug.org

TeX Live home page: <http://tug.org/texlive/>