

The `hep-paper` package^{*}

Jan Hajer[†]

Centre for Cosmology, Particle Physics and Phenomenology,
Université catholique de Louvain, Louvain-la-Neuve B-1348, Belgium

2020/03/01

Abstract

The `hep-paper` package aims to provide a single style file containing most configurations and macros necessary to write appealing publications in High Energy Physics. Instead of reinventing the wheel by introducing newly created macros `hep-paper` preferably loads third party packages as long as they are lightweight enough.

^{*}This document corresponds to `hep-paper` v1.2.

[†]`jan.hajer@uclouvain.be`

Contents

1	Introduction	3
1.1	Options	3
2	Macros and environments	4
2.1	Title page	4
2.2	Text	4
2.2.1	References and footnotes	5
2.2.2	Acronyms	5
2.3	Math	5
2.3.1	Physics	6
2.4	Floats	7
2.5	Bibliography	7
3	Conclusion	8
A	Options	8
A.1	Process options	9
B	Engine	10
C	Text	10
C.1	Font size	11
C.2	Text macros	11
C.3	Lists	12
C.4	Footnotes	13
D	Geometry	13
E	Math	13
E.1	Math fonts	14
E.2	Physics notation	15
F	Floats	15
F.1	Sub-floats	16
F.2	Tables	17
F.3	Figures	17
G	Title page	18
G.1	Authors	18
G.2	Preprint	19
G.3	Abstract	19
H	Bibliography	19
I	Hyperlinks and References	22
I.1	Citation macros	24
J	Acronyms	25

1 Introduction

For usual publications it is enough to load additionally to the `article` class without optional arguments only the `hep-paper` package [1].

```
\documentclass{article}
\usepackage{hep-paper}
```

The most notable changes after loading the `hep-paper` package is the change of some L^AT_EX defaults. The paper and font sizes are set to A4 and 11 pt, respectively. Additionally, the paper geometry is set to the values known from the (deprecated) `a4wide` package [2] using the `geometry` package [3]. Finally, the font is changed to `lmodern` [4] with `microtype` [5] optimizations. Portable document format (PDF) hyperlinks are implemented with the `hyperref` package [6].

1.1 Options

- | | |
|-----------------|---|
| paper | The <code>paper=<i>format</i></code> option loads the specified paper format. The possible <i>formats</i> are: <code>a0</code> , <code>a1</code> , <code>a2</code> , <code>a3</code> , <code>a4</code> , <code>a5</code> , <code>a6</code> , <code>b0</code> , <code>b1</code> , <code>b2</code> , <code>b3</code> , <code>b4</code> , <code>b5</code> , <code>b6</code> , <code>c0</code> , <code>c1</code> , <code>c2</code> , <code>c3</code> , <code>c4</code> , <code>c5</code> , <code>c6</code> , <code>ansia</code> , <code>ansib</code> , <code>ansic</code> , <code>ansid</code> , <code>ansie</code> , <code>letter</code> , <code>executive</code> , <code>legal</code> . |
| font | The <code>font=<i>size</i></code> option loads the specified font size. The possible <i>sizes</i> are: <code>8pt</code> , <code>9pt</code> , <code>10pt</code> , <code>11pt</code> , <code>12pt</code> , <code>14pt</code> , <code>17pt</code> , <code>20pt</code> . |
| defaults | The <code>defaults</code> option prevents the adjustment of the page geometry and the font size set by the document class. |
| lang | The <code>lang=<i>name</i></code> option switches the document language to the chosen value. The possible values are given by the <code>babel</code> package [7]. The default is <code>british</code> . |
| parskip | The <code>parskip</code> option makes use of the <code>parskip</code> package [8] and changes how two paragraphs are separated from each other. The L ^A T _E X default is separation via indentation the <code>parskip</code> option switches to separation via vertical space. ¹ |
| sansserif | The <code>sansserif</code> option switches the document including math to sans serif font shape. |
| title | The <code>title=false</code> option deactivates the titlepage adjustments. |
| manualplacement | The <code>manualplacement</code> option reactivates manual float placement. |
| bibliography | The <code>bibliography=<i>key</i></code> option prevents the automatic loading of the <code>biblatex</code> package [9] for <i>key</i> = <code>false</code> or passes the <i>key</i> as <code>style</code> string to the <code>biblatex</code> package. |
| glossaries | The <code>glossaries=false</code> option deactivates the use of the <code>glossaries</code> package [10, 11]. |
| revtex | The <code>revtex</code> option switches the <code>hep-paper</code> package into a <code>revtex</code> [12] compatibility mode. |
| eqnarray | The <code>eqnarray</code> option reactivates the deprecated <code>eqnarray</code> environment. |

¹The `parskip` option is used for this document.

2 Macros and environments

2.1 Title page

The PDF meta information is set according to the `\title{text}` and `\author{text}` information. In order to facilitate multiple authors with different affiliations the `authblk` package [13] is loaded. The following lines add *e.g.* two authors with different affiliations

```
\author
\affiliation
\email
\author[1]{Author one \email{Email one}}
\affiliation[1]{Affiliation one}
\author[2]{Author two \email{Email two}}
\affiliation[1,2]{Affiliation two}
```

`\preprint` The `\preprint{numer}` macro places a pre-print number in the upper right corner of the first page.

`abstract` The `abstract` environment has been adjusted to not start with an indentation.

2.2 Text

`\enquote` Hyphenation is provided by the `babel` package [7] and quotation commands are provided by the `csquotes` package [14] recommended by the `babel` package. The latter package provides the convenient macro `\MakeOuterQuote{"}` allowing to simply use " instead of the pair ‘ ‘ and ’ ’.

`\eg` The `foreign` package [15] defines macros such as `\eg`, `\ie`, `\cf`, and `\vs` which are typeset as *e.g.*, *i.e.*, *cf.*, and *vs.*

`\no` The `\no{number}` macro is typeset as № 123.

`\software` The `\software[version]{name}` macro is typeset as HEP-PAPER v1.2.

`\online` The `\online{url}{text}` macro combines the features of the `\href{url}{text}` and the `\url{text}` macros, resulting in *e.g.* `ctan.org/pkg/hep-paper`.

`inlinelist` Using the `enumitem` package [16] the `inlinelist`

```
The three main points are
\begin{inlinelist}
\item one
\item two
\item three
\end{inlinelist}
```

The three main points are i) one, ii) two, and iii) three.

`enumdescript` and the `enumdescript` environments are defined

```
\begin{enumdescript}[label=\Roman*])
\item{First} one
\item{Second} two
\item{Third} three
\end{enumdescript}
```

I) **First** one
II) **Second** two
III) **Third** three

<code>\textsc</code>	A sans serif version of SMALL CAPS is provided.
<code>\useparskip</code>	If the <code>\parskip</code> option is activated the <code>\useparindent</code> macro switches back the usual
<code>\useparindent</code>	parindent mode, while the <code>\useparskip</code> macro switches to the <code>\parskip</code> mode.

2.2.1 References and footnotes

<code>\cref</code>	References are extended with the <code>cleveref</code> package [17], which allows to <i>e.g.</i> just type <code>\cref{<key>}</code> in order to write 'Figure 1'. Furthermore, the <code>cleveref</code> package allows to reference multiple objects within one <code>\cref{<key>}</code> (similar to the <code>\cite{<key>}</code> macro).
<code>\cite</code>	Citations are adjusted to not start on a new line in order to avoid the repeated use of <code>\cite{<key>}</code> .
<code>\ref</code>	References are also adjusted to not start on a new line and are redefined in order to
<code>\eqref</code>	handle multiple references at once.
<code>\subref</code>	Footnotes are adjusted to swallow white space before the footnote mark and at the
<code>\footnote</code>	beginning of the footnote text.

2.2.2 Acronyms

<code>\acronym</code>	The <code>\acronym{<*>[<typeset abbreviation>]{<abbreviation>}{<definition>}[<plural</code>
<code>\shortacronym</code>	<code>definition>]</code> macro generates the singular <code>\<abbreviation></code> and plural <code>\<abbreviation>s</code>
<code>\longacronym</code>	macros. The starred version does not add an 's' to the abbreviation plural. The long
	form is only shown at the first appearance of these macros, later appearances generate
	the abbreviation with a hyperlink to the long form. Capitalization at the beginning
	of paragraphs and sentences is ensured. The <code>\shortacronym</code> and <code>\longacronym</code>
<code>\resetacronym</code>	macros only show the short or long form of their acronym. The first use form of the
<code>\dummyacronym</code>	acronym can be enforced by resetting the acronym counter. If the acronym counter
	equals one at the end of the document the short form of the acronym is not intro-
	duced. Placing a <code>\dummyacronym{<key>}</code> at the end of the document ensures that
	the short form is introduced.

2.3 Math

	The <code>mathtools</code> [18] and <code>amssymb</code> [19] packages are loaded. They in turn load the
<code>\mathbf</code>	<code>amsmath</code> [20] and <code>amsfonts</code> [19] packages. Bold math, including <code>\mathbf</code> is provided
	by the <code>bm</code> package [21], <i>i.e.</i> ($Ab\Gamma\delta\mathbf{A}b\mathbf{\Gamma}\delta$). Macros switching to <code>\bfseries</code> such as
	<code>\section{<text>}</code> are ensured to also typeset math in bold. This may cause trouble
<code>\text</code>	if bold symbols carry an additional non-implicit meaning. The <code>\text{<text>}</code> macro
	makes it possible to write text within math mode, <i>i.e.</i> ($Ab\Gamma\delta\mathbf{A}b\mathbf{\Gamma}\delta$). The often used
	<code>\mathrm{<text>}</code> and <code>\rm{<text>}</code> macros are <i>not</i> the correct tool for this purpose, as
	they switch to roman font shape. This behaviour conflicts <i>e.g.</i> with the <code>sansserif</code>
<code>\mathsf</code>	package option. The math sans serif alphabet is redefined to be italic sans serif if
	the main text is serif and italic serif if the main text is sans serif, <i>i.e.</i> ($Ab\Gamma\delta\mathbf{A}b\mathbf{\Gamma}\delta$).
<code>\mathscr</code>	Details about the font handling in $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ can be found in [22]. The <code>\mathcal</code> font <i>i.e.</i>

(\mathcal{ABCD}) is accompanied by the `\mathscr` font *i.e.* (\mathcal{ABCD}).

`\nicefrac` The `\frac{⟨number⟩}{⟨number⟩}` macro is accompanied by `\nicefrac{⟨number⟩}{⟨number⟩}` and `\flatfrac{⟨number⟩}{⟨number⟩}`

$$\frac{1}{2} , \qquad 1/2 , \qquad 1/2 . \qquad (1)$$

`\diag` A diagonal matrix operator is defined `\diag`.

`\mathdef` The `\mathdef{⟨name⟩}[⟨arguments⟩]{⟨code⟩}` macro (re-)defines macros only within math mode without changing the text mode definition. The imaginary unit `i` is defined using this functionality.

`\numberwithin` For longer paper it can be useful to re-number the equation in accordance with the section numbering `\numberwithin{equation}{section}`. In order to further reduce the size the of equation counter it can be useful to wrap `align` environments with multiple rows in a `subequations` environment.

`eqnarray` The depreciated `eqnarray` environment is undefined as long this behaviour is not prevented by the `eqnarray` package option. The `align` environment should be used instead.

2.3.1 Physics

Greek letters are adjusted to always be italic and upright in math and text mode, respectively, using the `fixmath` [23] and `alphabetalpha` [24] packages. This allows differentiations like

$$\sigma = 5 \text{ fb} , \qquad \text{at } 5 \sigma \text{ C.L.} , \qquad \mu = 5 \text{ cm} , \qquad l = 5 \mu\text{m} , \qquad (2)$$

and *e.g.* to distinguish gauge ν and mass \mathfrak{v} eigenstates in models with massive light neutrinos. Additionally, Greek letters can also be directly typed using Unicode.

`\ev` The `physics` package [25] provides additional macros such as

$$\langle \phi \rangle , \qquad \frac{\partial^n f}{\partial x^n} , \qquad [A, B] , \qquad \mathcal{O}(x^2) , \qquad x \Big|_0^\infty , \qquad \det(M) . \qquad (3)$$

`\order` The `\slashed{⟨character⟩}` macro from the `slashed` [26] package allows to use the Dirac slash notation.

`\overlefttrightarrow` A better looking over left right arrow is defined $\overleftrightarrow{\partial}$. The correct spacing for units, *cf.* Equation (2), is provided by the macro `\unit[⟨value⟩]{⟨unit⟩}` from the `units` package [27] which can also be used in text mode. The macro `\inv[⟨power⟩]{⟨text⟩}` allows to avoid math mode also for inverse units such as 5 fb^{-1} typeset via `\unit[5]{\inv{fb}}`.


```

\begin{panels}{.6}
code
\panel{.4}
\begin{tabular}...\end{tabular}
\end{panels}

```

(a) Code for this panel environment.

one		two	
	b	c	d
a	b	c	d

(b) The `booktabs` and `multirow` features.

Table 1: Example use of the `panels` environment in Panel (a) and the features from the `booktabs` and `multirow` packages in Panel (b).

2.4 Floats

<code>figure</code>	Automatic float placement is adjusted to place a single float at the top of pages
<code>table</code>	and to reduce the number of float pages. The most useful float placement is usually archived by placing the float <i>in front</i> of the paragraph it is referenced in first. Additionally, manual float placement is deactivated but can be reactivated using the
<code>\raggedright</code>	<code>manualplacement</code> package option. The float environments have been adjusted to center their content. The usual behaviour can be reactivated using <code>\raggedright</code> .
<code>panels</code>	The <code>panels</code> environment makes use of the <code>subcaption</code> package [28]. It provides
<code>\panel</code>	sub-floats and takes as mandatory argument either the number of sub-floats (default 2) or the width of the first sub-float as fraction of the <code>\linewidth</code> . Within the <code>\begin{panels}[\langle vert \rangle]{\langle width \rangle}</code> environment the <code>\panel</code> macro initiates a new sub-float. In the case that the width of the first sub-float has been given as an optional argument to the <code>panels</code> environment the <code>\panel{\langle width \rangle}</code> macro takes the width of the next sub-float as mandatory argument. The example code is presented in Table 1a.
<code>tabular</code>	The <code>booktabs</code> [29] and <code>multirow</code> [30] packages are loaded enabling publication quality tabulars such as in Table 1b.
<code>\graphic</code>	The <code>graphicx</code> package [31] is loaded and the <code>\graphic[\langle width \rangle]{\langle figure \rangle}</code> macro is defined, which is a wrapper for the <code>\includegraphics{\langle figure \rangle}</code> macro and
<code>\graphics</code>	takes the figure width as fraction of the <code>\linewidth</code> as optional argument (default 1). If the graphics are located in a sub-folder its path can be indicated by <code>\graphics{\langle subfolder \rangle}</code> .

2.5 Bibliography

<code>\bibliography</code>	The <code>biblatex</code> package [9] is loaded for bibliography management. The user has
<code>\printbibliography</code>	to add the line <code>\bibliography{\langle my.bib \rangle}</code> to the preamble of the document and <code>\printbibliography</code> at the end of the document. The bibliography is generated by <code>biber</code> [32]. <code>biblatex</code> is extended to be able to cope with the <code>collaboration</code> and <code>reportNumber</code> fields provided by <code>inspirehep.net</code> and a bug in the volume number is fixed. Additionally, <code>ctan.org</code> , <code>github.com</code> , <code>gitlab.com</code> , <code>sourceforge.net</code> , and
<code>erratum</code>	<code>hepforge.org</code> are recognized as <code>eprinttypes</code> . Errata can be included using the related feature.


```

\article{⟨key1⟩,
  ...,
  relatedtype="erratum",
  related="⟨key2⟩",
}
\article{⟨key2⟩,
  ...,
}

```

3 Conclusion

The `hep-paper` package provides a matching selection of preloaded packages and additional macros enabling the user to focus on the content instead of the layout by reducing the amount of manual tasks. The majority of the loaded packages are fairly lightweight, the others can be deactivated with package options.

`arxiv-collector` ArXiv requires the setup dependent `bb1` files instead of the original `bib` files, which causes trouble if the local `LATEX` version differs from the one used by arXiv. The `arxiv-collector` python script [33] alleviates this problem by collecting all files necessary for publication on arXiv (including figures).

A Options

Load the `kvoptions` package and define a `hep` namespace.

```

1 \RequirePackage{kvoptions}
2 \SetupKeyvalOptions{
3   family=hep,
4   prefix=hep@
5 }

```

`paper` Define a `paper=⟨size⟩` option. Make A4 paper the default.

```

6 \DeclareStringOption[a4]{paper}

```

`font` Define a `font=⟨size⟩` option. Make 11 pt the default font size.

```

7 \DeclareStringOption[11pt]{font}

```

`defaults` Define the `defaults` option which deactivates the `paper` and `font` options and prevents the change of the class defaults by this package.

```

8 \DeclareBoolOption[false]{defaults}

```

`lang` Define the `lang` option, which takes the values provided by the `babel` package [7]. Make `british` the default language.

```

9 \DeclareStringOption[british]{lang}

```


<code>parskip</code>	Define the option pair <code>parindent</code> and <code>parskip</code> controlling the separation of paragraphs.
	<pre> 10 \DeclareBoolOption[true]{parindent} 11 \DeclareComplementaryOption{parskip}{parindent} </pre>
<code>sansserif</code>	Define the option pair <code>serif</code> and <code>sansserif</code> controlling the font shape of the whole document.
	<pre> 12 \DeclareBoolOption[true]{serif} 13 \DeclareComplementaryOption{sansserif}{serif} </pre>
<code>eqnarray</code>	Provide the option <code>eqnarray</code> for reactivating the <code>eqnarray</code> environment.
	<pre> 14 \DeclareBoolOption[false]{eqnarray} </pre>
<code>bibliography</code>	Provide the option <code>bibliography</code> for passing a style string to the <code>biblatex</code> package [9] or disabling the automatic loading of <code>biblatex</code> .
	<pre> 15 \DeclareStringOption[numeric-comp]{bibliography} </pre>
<code>glossaries</code>	Provide the option <code>glossaries</code> able to turn off the use of the <code>glossaries-extra</code> package [11].
	<pre> 16 \DeclareBoolOption[true]{glossaries} </pre>
<code>manualplacement</code>	Provide the <code>manualplacement</code> option for reactivating the manual placement of floats.
	<pre> 17 \DeclareBoolOption[false]{manualplacement} </pre>
<code>title</code>	Provide the option <code>title</code> for deactivating redefinition of title macros.
	<pre> 18 \DeclareBoolOption[true]{title} </pre>
<code>revtex</code>	Provide the option <code>revtex</code> for <code>revtex</code> [12] compatibility mode.
	<pre> 19 \DeclareBoolOption[false]{revtex} </pre>

A.1 Process options

```

20 \ProcessKeyvalOptions*

```

Set the `revtex` compatibility options.

```

21 \ifhep@revtex
22   \setkeys{hep}{defaults, title=false, lang=american, bibliography=false}
23 \fi

```


B Engine

`\ifxetexorluatex` Load the `ifluatex` [34] and `ifxetex` [35] packages. Define the `\ifxetexorluatex` conditional.

```
24 \RequirePackage{ifluatex}
25 \RequirePackage{ifxetex}
26 \newif\ifxetexorluatex
27 \ifxetex\xetexorluatextrue\else
28   \ifluatex\xetexorluatextrue
29   \else\xetexorluatexfalse
30 \fi
31 \fi
```

C Text

Load `alphabeta` package [24] first in order to archive the correct behaviour. The `alphabeta` package provides upright Greek letters in text mode.

```
32 \RequirePackage{alphabeta}
```

Pick the correct font encoding depending on the engine used and load the `fontenc` package [36] with this encoding. For details of the font encoding see [37].

```
33 \ifxetexorluatex
34   \def\@encoding{TU}
35 \else
36   \def\@encoding{T1}
37 \fi
38 \RequirePackage[\@encoding]{fontenc}
```

Load the `lmodern` font [4], the `textcomp` extension [38], and the `microtype` font optimization [5].

```
39 \RequirePackage{lmodern}
40 \RequirePackage{textcomp}
41 \RequirePackage{microtype}
```

Define sans serif small caps font shapes.

```
42 \ifxetexorluatex
43   \DeclareFontShape{\@encoding}{lmss}{bx}{sc}{<->cmssbxcsc10}{}
44   \DeclareFontShape{\@encoding}{lmss}{m}{sc}{%
45     <-9>cmsscsc8<9-10>cmsscsc9<10->cmsscsc10%
46   }{}
47 \else
48   \sffamily
49   \DeclareFontShape{\@encoding}{lmss}{bx}{sc}{<->ssub*xcms/bx/sc}{}
50   \DeclareFontShape{\@encoding}{lmss}{m}{sc}{<->ssub*xcms/m/sc}{}
51 \fi
```


Load the `inputenc` [39] package.

```
52 \ifxetexorluatex\else
53   \RequirePackage[utf8]{inputenc}
54 \fi
```

Load the `babel` [7] package for hyphenation and the recommended `csquotes` package [14].

```
55 \RequirePackage[\hep@lang]{babel}
56 \RequirePackage{csquotes}
```

Set the whole text to sans serif if requested.

```
57 \ifhep@serif\else
58   \renewcommand\familydefault{\sfdefault}
59 \fi
```

`\underline` Load the `soul` package [40] for hyphenable underlined text.

```
60 \RequirePackage{soul}
61 \let\underline\ul
```

C.1 Font size

Undefine previously defined font sizes and load the \LaTeX font size file corresponding to the font size option.

```
62 \ifhep@defaults\else
63   \def\remove@pt#1pt{#1}
64   \edef\@ptsize{\expandafter\remove@pt\hep@font}
65   \let\small\relax
66   \let\footnotesize\relax
67   \let\scriptsize\relax
68   \let\tiny\relax
69   \let\large\relax
70   \let\Large\relax
71   \let\LARGE\relax
72   \let\huge\relax
73   \let\Huge\relax
74   \input{size\@ptsize.clo}
75 \fi
```

C.2 Text macros

`\vs` Load the `foreign` package [15] in order to highlight abbreviations and vocabularies from foreign languages. Add the missing `\vs` command.

```
76 \RequirePackage{pdftexcmds}
77 \newcommand{\hep@lang@foreign}{british}
78 \ifnum\pdf@strcmp{\hep@lang}{american}=0%
```



```

79 \renewcommand{\hep@lang@foreign}{USenglish}%
80 \fi
81 \ifnum\pdf@strcmp{\hep@lang}{USenglish}=0%
82 \renewcommand{\hep@lang@foreign}{USenglish}%
83 \fi
84 \RequirePackage[all, \hep@lang@foreign]{foreign}
85 \DeclareRobustCommand\vs{\xperiodafter{\foreignabbrfont{vs}}}}

```

`\no` Define the macro `\no{⟨number⟩}` for the use of \aleph with appropriate spacing.

```

86 \newcommand{\no}[1]{\textnumero~#1}

```

`\software` Define a macro for software with optional version information `\software[⟨version⟩]{⟨name⟩}`, using the `relsize` package [41].

```

87 \RequirePackage{relsize}
88 \newcommand{\software}[2][\hspace{-\fontdimen2\font}]{%
89 {\smaller\textsc{#2}~#1}%
90 }

```

`\online` The `\online{⟨text⟩}{⟨url⟩}` macro combines the features of the `\href` and the `\url` macros.

```

91 \newcommand{\online}[2]{\href{#1}{\url{#2}}}

```

C.3 Lists

Load the `enumitem` package [16].

```

92 \RequirePackage[inline]{enumitem}

```

`inlinelist` Define an inline list environment.

```

93 \newlist{inlinelist}{enumerate*}{1}
94 \setlist*{inlinelist,1}{%
95 label=\roman*), itemjoin={, \ }, itemjoin*={, and \ }, after=.%
96 }

```

`enumdescript` Define an `enumdescript` list environment.

```

97 \newlist{enum@descript}{enumerate}{2}
98 \setlist{enum@descript}{label=\arabic*.}
99 \newenvironment{enumdescript}[1][]{
100 \begin{enum@descript}[#1]
101 \let\old@item\item
102 \renewcommand{\item}[2][]{
103 \ifx##1&\old@item\else\old@item[##1]\fi
104 \textbf{##2}\ifx##2\empty\else~\fi@ifnextchar\par\@gobble\relax
105 }
106 }\end{enum@descript}}

```


C.4 Footnotes

`\footnote` Ensure that no spaces appear before the footmark or at the beginning of the footnote.

```
107 \let\@foot@note\footnote
108 \renewcommand{\footnote}[1]{\unskip\@foot@note{\ignorespaces#1}}
```

D Geometry

Load the `geometry` package [3] and adjust the text width and height to the values of the `a4wide` package [2].

```
109 \ifhep@defaults\else
110   \RequirePackage[\hep@paper paper]{geometry}
111   \geometry{hscale=.75, vscale=.8, vmarginratio=3:4, includeheadfoot}
112 \fi
```

`\useparskip` Load the `parskip` package [8] and provide two commands switching between the
`\useparindent` two paragraph modes.

```
113 \ifhep@parindent\else
114 \RequirePackage{parskip}
115 \newcommand{\useparskip}{%
116   \setlength{\parskip}{.5\baselineskip plus 2pt}%
117   \setlength{\parindent}{0pt}%
118 }
119 \newcommand{\useparindent}{%
120   \setlength{\parskip}{0pt}%
121   \setlength{\parindent}{15pt}%
122   \if@twocolumn\setlength\parindent{1em}
123   \else\setlength\parindent{1.5em}
124   \fi
125 }
126 \fi
```

E Math

Load the `mathtools` package [18] which loads the `amsmath` package [20]. Additionally, load the `amssymb` package [19] which provides further math symbols and also loads the `amsfont` package [19]. Allow page breaks within equations if necessary.

```
127 \RequirePackage{mathtools}
128 \RequirePackage{amssymb}
129 \allowdisplaybreaks[1]
```

`\diag` Provide a `diag` operator

```
130 \DeclareMathOperator{\diag}{diag}
```


`\mathdef` Define the `\mathdef{⟨name⟩}[⟨arguments⟩]{⟨macro⟩}` macro which (re-)defines macros in math mode only. This macro is implemented using the `xparse` package [42].

```

131 \RequirePackage{xparse}
132 \DeclareDocumentCommand{\mathdef}{mO{0}m}{%
133   \expandafter\let\csname old\string#1\endcsname=#1
134   \expandafter\newcommand\csname new\string#1\endcsname[#2]{#3}
135   \DeclareRobustCommand#1{%
136     \ifmmode
137       \expandafter\let\expandafter\next\csname new\string#1\endcsname
138     \else
139       \expandafter\let\expandafter\next\csname old\string#1\endcsname
140     \fi
141     \next
142   }%
143 }
```

`\i` Provide an upright imaginary unit in math mode.

```

144 \AtBeginDocument{\mathdef{\i}{\operatorname{i}}}
```

`eqnarray` Undefine the `eqnarray` environment.

```

145 \ifhep@eqnarray\else%
146   \let\eqnarray\@undefined
147   \let\endeqnarray\@undefined
148 \fi
```

E.1 Math fonts

`\mathbf` Load the `bm` package [21] for superior boldmath. Make math symbols bold whenever they appear in bold macros such as `\section{⟨text⟩}`.

```

149 \RequirePackage{bm}
150 \let\mathbf\bm
151 \g@addto@macro\bfseries{\boldmath}
```

`\mathsf` Load the `fixmath` package [23] which ensures that upper Greek letters in math mode are italic. Ensure that also math mode is sans serif using the `sfnath` package [43] if the option `sans serif` is passed to the package. Ensure that `\mathsf` is italic as well as sans serif and sans for sans and sans serif documents, respectively.

```

152 \ifhep@serif
153   \RequirePackage{fixmath}
154   \DeclareMathAlphabet{\mathsf}{OML}{cmbr}{m}{it}
155   \SetMathAlphabet{\mathsf}{bold}{OML}{cmbr}{bx}{it}
156 \else
157   \RequirePackage[slantedGreek]{sfnath}
158   \DeclareMathAlphabet{\mathsf}{OML}{cmm}{m}{it}
```



```

159 \SetMathAlphabet{\mathsf}{bold}{OML}{cmm}{bx}{it}
160 \fi

```

`\mathscr` Load the `mathrsfs` package for the `\mathscr` math script font.

```

161 \RequirePackage{mathrsfs}

```

E.2 Physics notation

`\slashed` Load the `physics` package [25] which provides macros useful for publications in physics. Additionally, load the `slashed` package [26] which provides the `slashed` macro for Dirac notation. Finally, load the `units` package [27] which provides the `\units` and `\nicefrac` macros.

```

162 \RequirePackage{physics}
163 \RequirePackage{slashed}
164 \RequirePackage{units}

```

`\inv` Provide a macro for the inverse, useful in combination with the unit macro in text mode.

```

165 \newcommand{\inv}[2][1]{#2\ensuremath{\sim\!^{-}\!#1}}

```

`\oset` Define a new overset macro `\oset[⟨offset⟩]{⟨over⟩}{⟨base⟩}`

```

166 \newcommand{\oset}[3][-1pt]{%
167   \raisebox{1pt}{\ensuremath{\mathop{#3}\limits\sim\!^{\!#1}}}
168   \vbox to#1{\kern-2\ex@{\hbox{$\scriptscriptstyle#2$}\vss}}%
169 }%
170 }

```

`\overleftrighth` Define a over left right arrow `\overleftrighth{⟨base⟩}`.

```

171 \newcommand{\overleftrighth}[1]{\oset{\leftrightharrow}{#1}}

```

F Floats

Adjust the \LaTeX float placement defaults

```

172 \renewcommand{\textfraction}{0.01}
173 \setcounter{topnumber}{1}
174 \renewcommand{\topfraction}{.9}
175 \setcounter{bottomnumber}{0}
176 \renewcommand{\floatpagefraction}{.8}

```

`figure` Center the content of `figure` and `table` environments. Ignore the manual placement if the `manualplacement` option is set to false.

```

177 \let\@figure@\figure%

```



```

178 \let\@end@figure@\endfigure%
179 \let\@table@\table%
180 \let\@end@table@\endtable%
181 \ifhep@manualplacement%
182   \renewenvironment{figure}[1][tbp]{%
183     \@figure@[#1]\centering%
184     }\@end@figure@}%
185   \renewenvironment{table}[1][tbp]{%
186     \@table@[#1]\centering%
187     }\@end@table@}%
188 \else%
189   \renewenvironment{figure}[1][]{%
190     \@figure@\centering%
191     }\@end@figure@}%
192   \renewenvironment{table}[1][]{%
193     \@table@\centering%
194     }\@end@table@}%
195 \fi%

```

F.1 Sub-floats

Prevent the `caption` package [44] from complaining about the `revtex` class.

```

196 \ifhep@revtex
197   \setlength\abovecaptionskip{\f@size\p@}
198   \setlength\belowcaptionskip{0\p@}
199   \long\def\@makecaption#1#2{%
200     \vskip\abovecaptionskip
201     \sbox\@tempboxa{#1: #2}%
202     \ifdim \wd\@tempboxa >\hsize
203       #1: #2\par
204     \else
205       \global \@minipagefalse
206       \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
207     \fi
208     \vskip\belowcaptionskip%
209   }
210 \fi

```

Load the `subcaption` package [28].

```

211 \RequirePackage[subrefformat = parens]{subcaption}
212 \captionsetup{font=small}
213 \captionsetup[sub]{font=small}

```

`panels` Load the `subcaption` package [28] and define the `panels` environment as well as the `\panel` macro.

```

214 \newenvironment{panels}[2][b]{%

```


Define an internal macro for global behaviour.

```
215 \newcommand{\begin@subcaption@minipage}[2][b]{%
216   \caption@withoptargs\subcaption@minipage[##1]{##2}%
217   \centering\vskip 0pt%
218 }
```

Define the `\panel` macro for the case that the number of panels is given.

```
219 \ifdim#2pt>1pt%
220   \newcommand{\panel}[1][b]{%
221     \endminipage\hfill\begin@subcaption@minipage[#1]{\linewidth/#2}%
222   }%
223   \begin@subcaption@minipage[#1]{\linewidth/#2}%
```

Define the `\panel` macro for the case that the width of the panel is given.

```
224 \else%
225   \newcommand{\panel}[2][b]{%
226     \endminipage\hfill\begin@subcaption@minipage[#1]{##2\linewidth}%
227   }%
228   \begin@subcaption@minipage[#1]{#2\linewidth}%
229 \fi%
230 }\endminipage}
```

Readjust the captions to the revtex class.

```
231 \ifhep@revtex
232   \renewcommand{\figurename}{Figure}
233   \renewcommand{\tablename}{Table}
234   \RequirePackage{ragged2e}
235   \DeclareCaptionFormat{revtex}{#1#2\justifying{#3}}
236   \captionsetup{font = small, format = revtex}
237   \captionsetup[sub]{font = footnotesize, format = plain}
238 \fi
```

F.2 Tables

`tabular` Enhance tabulars with the `booktabs` and `multirow` packages [29, 30].

```
239 \RequirePackage{booktabs}
240 \RequirePackage{multirow}
```

F.3 Figures

`\graphic` Provide the `\graphic` macro for the inclusion of figures using the `graphicx` package [31].

```
241 \RequirePackage{graphicx}
242 \providecommand{\tikzsetnextfilename}[1]{}
243 \newcommand{\graphic}[2][1]{\tikzsetnextfilename{#2}{%
```



```

244 \centering\includegraphics[width=#1\linewidth]{#2}%
245 }}

```

`\graphics` Provide the `\graphics` macro for the inclusion of figures located in a subfolder.

```

246 \newcommand{\graphics}[1]{\graphicspath{{.#1/}}}

```

G Title page

`\date` Allow empty date field.

```

247 \ifhep@title
248 \date{}

```

G.1 Authors

`\author` Allow empty author field.

```

249 \author{}

```

`\email` Provide macro for the email of authors used as `\author{<name> \email{<email>}}`.

```

250 \AtEndOfClass{\newcommand{\email}[1]{%
251 \unskip\thanks{\online{mailto:#1}{#1}}
252 }}

```

Enable the handling of multiple authors with different affiliations using the `authblk` package [13].

```

253 \RequirePackage{authblk}
254 \renewcommand\Affilfont{\footnotesize}

```

`\affiliation` Define the `\affiliation` macro, ensure that linebreaks happen after a comma.

```

255 \newcommand\active@comma{\penalty-5\relax}
256 \newcommand\cat@comma@active{\catcode'\,\active}
257 {\cat@comma@active\gdef,\active@comma}
258 \newcommand\@affil[1]{%
259 \endgroup\@flushglue=0pt plus .5\linewidth\affil{#1}%
260 }
261 \def\@affil@opt[#1]#2{%
262 \endgroup\@flushglue=0pt plus .5\linewidth\affil[#1]{#2}%
263 }
264 \DeclareRobustCommand\@affiliation{\@ifnextchar[{\@affil@opt}{\@affil}}
265 \newcommand{\affiliation}{\begingroup\cat@comma@active\@affiliation}

```


G.2 Preprint

`\preprint` Places a preprint number in the top right corner of the first page. This code uses the `varwidth` [45], `atbegshi` [46], and `picture` [47] packages.

```
266 \let\@preprint\relax
267 \newcommand\preprint[1]{\long\gdef\@preprint{#1}}
268 \RequirePackage{varwidth}
269 \newcommand{\@preprint@box}{%
270   \begin{varwidth}{\textwidth}%
271     \textsc{\small\@preprint}%
272   \end{varwidth}%
273 }
274 \RequirePackage{atbegshi}
275 \RequirePackage{picture}
276 \AtBeginShipoutFirst{%
277   \put(
278     \textwidth+\oddsidemargin-\widthof{\@preprint@box},
279     -2pt-\topmargin-\heightof{\@preprint@box}
280   ){\normalfont\@preprint@box}
281 }
```

G.3 Abstract

`abstract` Adjust the abstract environment to not start with indentation.

```
282 \let\old@abstract\abstract
283 \renewcommand\abstract{\old@abstract\noindent\ignorespaces}
```

End of check for `title` option.

```
284 \fi
```

H Bibliography

Check if bibliography management is requested using the `pdftexcmds` package [48].

```
285 \ifnum\pdf@strcmp{\hep@bibliography}{false}=0\else
```

`\bibliography` Load the `biblatex` package [9] with a JHEP like bibliography style.

```
286 \RequirePackage[style=\hep@bibliography]{biblatex}
287 \ExecuteBibliographyOptions{
288   sorting=none,
289   giveninits=true
290 }
```

Read the collaboration and pre-print information if present. Move letters from the volume field to the journal field.


```

291 \newcommand{\@reg@exp}{\regex{\A(\p{L}+)?\d+(\p{L}+)?\Z}}
292 \newcommand{\@reg@exp@}{\regex{\A(\p{L}+)?(\d+)(\p{L}+)?\Z}}
293 \DeclareSourcemap{%
294   \maps[datatype=bibtex,overwrite=true]{%
295     \map{%
296       \step[fieldsource=Collaboration,final=true]%
297       \step[fieldset=userre,origfieldval,final=true]
298     }%
299     \map{%
300       \step[fieldsource=reportNumber,final=true]%
301       \step[fieldset=userf,origfieldval,final=true]
302     }%
303     \map[overwrite]{
304       \step[fieldsource=volume, match=\@reg@exp, final]
305       \step[fieldsource=volume, match=\@reg@exp@, replace={\$2}]
306       \step[fieldsource=journal, fieldtarget=journaltitle]
307       \step[fieldset=journaltitle, fieldvalue={\space$1$2}, append=true]
308     }
309   }%
310 }

```

Override the author information with collaboration information if present.

```

311 \renewbibmacro*{author}{%
312   \iffieldundef{usere}{\printnames{author}}{\textbf{\printfield{usere}}}%
313 }

```

Remove spurious ‘In:’ if no journal is present.

```

314 \renewbibmacro*{in:}{%
315   \iffieldundef{journal}{\printtext{\bibstring{in}\intitlepunct}}%
316 }

```

Provide the \letbibmacro macro for old biblatex installations.

```

317 \providecommand{\letbibmacro}[2]{\csletcs{abx@macro@#1}{abx@macro@#2}}

```

Add the pre-print information if present.

```

318 \letbibmacro{doi+eprint+url-old}{doi+eprint+url}
319 \renewbibmacro*{doi+eprint+url}{%
320   \usebibmacro{doi+eprint+url-old}
321   \iffieldundef{userf}{\textls[0]{%
322     \newunitpunct\textnumero\intitlepunct%
323     \textsc{\small\printfield{userf}}}%
324   }}%
325 }

```

Add CTAN as a pre-print option

```

326 \DeclareFieldFormat{eprint:ctan}{%
327   CTAN\addcolon\space\ifhyperref{%

```



```

328     \href{https://ctan.org/pkg/#1}{\nolinkurl{#1}}%
329   }{\nolinkurl{#1}}%
330 }
331 \DeclareFieldAlias{eprint:CTAN}{eprint:ctan}

```

Add GitHub as a pre-print option

```

332 \DeclareFieldFormat{eprint:github}{%
333   GitHub\addcolon\space\ifhyperref{\href{%
334     https://github.com/\thefield{eprintclass}/#1%
335   }{\nolinkurl{\thefield{eprintclass}/#1}}}%
336   }{\nolinkurl{\thefield{eprintclass}/#1}}%
337 }
338 \DeclareFieldAlias{eprint:GitHub}{eprint:github}

```

Add GitLab as a pre-print option

```

339 \DeclareFieldFormat{eprint:gitlab}{%
340   GitLab\addcolon\space\ifhyperref{\href{%
341     https://gitlab.com/\thefield{eprintclass}/#1%
342   }{\nolinkurl{\thefield{eprintclass}/#1}}}%
343   }{\nolinkurl{\thefield{eprintclass}/#1}}%
344 }
345 \DeclareFieldAlias{eprint:GitLab}{eprint:gitlab}

```

Add SourceForge as a pre-print option

```

346 \DeclareFieldFormat{eprint:sourceforge}{%
347   SourceForge\addcolon\space\ifhyperref{%
348     \href{https://sourceforge.net/projects/#1}{\nolinkurl{#1}}%
349   }{\nolinkurl{#1}}%
350 }
351 \DeclareFieldAlias{eprint:SourceForge}{eprint:sourceforge}

```

Add HEPForge as a pre-print option

```

352 \DeclareFieldFormat{eprint:hepforge}{%
353   HEPForge\addcolon\space\ifhyperref{%
354     \href{https://#1/hepforge.org/}{\nolinkurl{#1}}%
355   }{\nolinkurl{#1}}%
356 }
357 \DeclareFieldAlias{eprint:HEPForge}{eprint:hepforge}

```

Add new bibliography string ‘Erratum’ for the use in the `relatedtype` field.

```

358 \NewBibliographyString{erratum}
359 \DefineBibliographyStrings{english}{erratum={Erratum:}}

```

`\printbibliography` Allow the bibliography to be printed sloppy

```

360 \let\old@printbibliography\printbibliography
361 \renewcommand{\printbibliography}{\sloppy\old@printbibliography}

```


End check for bibliography option.

```
362 \fi
```

I Hyperlinks and References

Load the `hyperref` package [6] enable Unicode encoding and hide links.

```
363 \RequirePackage{hyperref}
364 \hypersetup{
365   pdfencoding=auto,
366   psdextra,
367   hidelinks,
368   linktoc=all,
369   breaklinks=true,
370   pdfcreator={},
371   pdfproducer={}
372 }
```

Set the PDF meta data according to the paper information and ensure that unnecessary information is suppressed.

```
373 \pdfstringdefDisableCommands{\def\varepsilon{\textepsilon}}
374 \AtBeginDocument{
375   \pdfstringdefDisableCommands{\let\ensuremath@gobble}
376   \pdfstringdefDisableCommands{\let\mathsurround@gobble}
377   \pdfstringdefDisableCommands{\let\unskip@gobble}
378   \pdfstringdefDisableCommands{\let\thanks@gobble}
379   \pdfstringdefDisableCommands{\let\footnote@gobble}
380   \pdfstringdefDisableCommands{\let\\\@gobble}
381 }
382 \AtBeginShipout{\hypersetup{pdftitle={\@title}}}
383 \ifhep@title
384   \AtBeginDocument{\hypersetup{pdfauthor=AB@authlist}}
385 \else
386   \AtBeginDocument{\hypersetup{pdfauthor={\@author}}}
387 \fi
```

`\cref` Improve reference using the `cleveref` package [17].

```
388 \RequirePackage[noabbrev, capitalize, nameinlink]{cleveref}
389 \crefname{enumi}{point}{points}
390 \Crefname{enumi}{Point}{Points}
```

`\refstepcounter@...` Adjust the `cleveref \refstepcounter@noarg` and `\refstepcounter@optarg` to use the `\@currentlabel` in order to fix problems with `\subref`.

```
391 \def\refstepcounter@noarg#1{%
392   \cref@old@refstepcounter{#1}%
393   \cref@constructprefix{#1}{\cref@result}%
```



```

394 \ifundefined{cref@#1@alias}%
395   {\def\@tempa{#1}}%
396   {\def\@tempa{\csname cref@#1@alias\endcsname}}%
397 \protected@edef\cref@currentlabel{%
398   [\@tempa] [\arabic{#1}] [\cref@result]}%
399   \noexpand\@currentlabel%
400 }% changed
401 }
402
403 \def\refstepcounter@optarg[#1]#2{%
404   \cref@old@refstepcounter{#2}%
405   \cref@constructprefix{#2}{\cref@result}%
406   \ifundefined{cref@#1@alias}%
407     {\def\@tempa{#1}}%
408     {\def\@tempa{\csname cref@#1@alias\endcsname}}%
409   \protected@edef\cref@currentlabel{%
410     [\@tempa] [\arabic{#2}] [\cref@result]}%
411     \noexpand\@currentlabel% changed
412   }%
413 }

```

`\no@break@before` Provide macro able to prevent line breaks.

```

414 \newcommand\no@break@before{%
415   \relax\ifvmode\else%
416     \ifhmode%
417       \ifdim\lastskip > 0pt%
418         \relax\unskip\nobreakspace%
419       \fi%
420     \fi%
421   \fi%
422 }

```

`\ref` Adjust `\ref{<key>}` in order to prevent preceding line breaks and to enable the possibility to reference multiple references at once.

```

423 \let\old@ref\ref
424 \AtBeginDocument{\renewcommand\ref{\no@break@before\labelcref}}

```

`\eqref` Adjust `\eqref{<key>}` in order to prevent preceding line breaks and to enable the possibility to reference multiple equations at once.

```

425 \renewcommand\eqref{\no@break@before\labelcref}

```

`\subref` Adjust `\subref{<key>}` in order to prevent preceding line breaks.

```

426 \let\old@subref\subref
427 \renewcommand\subref{\no@break@before\old@subref}
428 \renewcommand*\subcaption@ref[2]{\begingroup%
429   \caption@setoptions{sub}%

```



```

430 \subcaption@reffmt\p@subref{\old@ref#1{sub@#2}}}%
431 \endgroup}

```

`\subcref` Provide the `\subcref` macro.

```

432 \newcommand{\subcref}[1]{\cref{sub@#1}}

```

`\eqcrefname` Define the `\eqcrefname` macro for named equation types.

```

433 \DeclareDocumentCommand{\eqcrefname}{mmo}{
434   \crefname{#1}{#2}{\IfValueTF{#3}{#3}{#2s}}
435   \creflabelformat{#1}{(##2##1##3)}
436 }

```

`\labelcrefrange` Define the missing `\labelcrefrange{<key1>}{<key2>}` macro.

```

437 \DeclareRobustCommand{\labelcrefrange}[2]{%
438   \@crefrangenostar{labelcref}{#1}{#2}%
439 }

```

I.1 Citation macros

`\cite` Adjust `\cite{<key>}` in order to prevent preceding line breaks.

```

440 \let\old@cite\cite
441 \renewcommand\cite{\no@break@before\old@cite}

```

Begin of bibliography if.

```

442 \ifnum\pdf@strcmp{\hep@bibliography}{false}=0\else

```

Define bibstrings for reference names.

```

443 \NewBibliographyString{refname}
444 \NewBibliographyString{refsnname}
445 \DefineBibliographyStrings{english}{%
446   refname = {Reference},
447   refsnname = {References}
448 }

```

`\ccite` Define *clever* citation macros.

`\Ccite`

```

449 \DeclareCiteCommand{\ccite}{%
450   \ifnum\thecitetotal=1%
451     \bibstring{refname}%
452   \else%
453     \bibstring{refsnname}%
454   \fi%
455   \addnbspace\bibopenbracket%
456   \usebibmacro{cite:init}\usebibmacro{prenote}%

```



```

457 }\usebibmacro{citeindex}\usebibmacro{cite:comp}}}{\%
458 \usebibmacro{cite:dump}\usebibmacro{postnote}%
459 \bibclosebracket%
460 }
461
462 \newrobustcmd*{\Ccite}{\bibsentence\ccite}

```

End of biblatex if.

```

463 \fi

```

J Acronyms

Acronyms are implemented with the `glossaries-extra` package [11] which is an extension of the `glossaries` package [10].

```

464 \ifhepglossaries
465 \RequirePackage[nostyles]{glossaries-extra}

```

The entry count feature is used.

```

466 \glsenableentrycount
467 \glssetcategoryattribute{abbreviation}{entrycount}{1}

```

Provide macros for older `glossaries-extra` installations.

```

468 \providecommand{\glxtrusefield}[2]{\@gls@entry@field{#1}{#2}}
469 \providecommand{\glxtrsetfieldifexists}[3]{\glsdoifexists{#1}{#3}}
470 \providecommand{\gGlsXtrSetField}[3]{%
471   \glxtrsetfieldifexists{#1}{#2}{%
472     \csgdef{glo@glsdetoklabel{#1}@#2}{#3}%
473   }%
474 }

```

Hyperlinks from the abbreviation to their definition in the text are set.

```

475 \glssetcategoryattribute{abbreviation}{nohyperfirst}{true}
476 \renewcommand*{\glsdonohyperlink}[2]{\%
477   \glxtrprotectlinks\edef\fieldvalue{%
478     \glxtrusefield{\glslabel}{hastarget}%
479   }%
480   \ifdefstring\fieldvalue{true}{#2}{%
481     \gGlsXtrSetField{\glslabel}{hastarget}{true}%
482     \glsdohypertarget{#1}{#2}%
483   }%
484 }}

```

`\if@begin@of@sentence` Mark the beginning of a paragraph as if it would follow a full stop using the `everyhook` package [49]. Provide a macro checking for the beginning of a sentence

by examining the length of the preceeding space. (This breaks if `\frenchspacing` is activated)

```

485 \usepackage[excludeor]{everyhook}
486 \PushPostHook{par}{\spacefactor=3000}}
487 \newcommand{\if@begin@of@sentence}[2]{\leavevmode\protecting{%
488   \ifboolexpr{ test {\ifnumcomp{\spacefactor}{=}{3000}} or%
489     test {\ifnumcomp{\spacefactor}{=}{2000}}}%
490   }{#1}{#2}}%
491 }}

```

`\acronym` The `\acronym{<*>[<typeset abbreviation>]{<abbreviation>}{<definition>}[<plural definition>]}` macro is defined.

#1 star for omitting the ‘s’ in the short plural
 #2 optional typeset abbreviation
 #3 mandatory abbreviation
 #4 mandatory long form
 #5 optional plural long form

```

492 \DeclareDocumentCommand{\acronym}{sommo}{%
493   \newabbreviation[
494     longplural=\IfNoValueTF{#5}{#4s}{#5},
495     \glsshortpluralkey=\IfBooleanTF{#1}{#3}{\IfNoValueTF{#2}{#3s}{#2s}}
496   ]{#3}{\IfNoValueTF{#2}{#3}{#2}}{#4}

```

Provide the singular acronym macro.

```

497 \expandafter\newcommand\csname#3\endcsname{%
498   \if@begin@of@sentence{\cGls{#3}}{\cgl{s}{#3}}\@xspace%
499 }

```

Expand the singular acronym macro in PDF labels.

```

500 \pdfstringdefDisableCommands{\expandafter\def\csname#3\endcsname{%
501   \IfNoValueTF{#2}{#3}{#2} }%
502 }

```

Provide the singular acronym macro in math mode.

```

503 \expandafter\mathdef\csname#3\endcsname{%
504   \text{\glstrshort{#3}}\glssunset{#3}%
505 }

```

Provide the plural acronym macro.

```

506 \expandafter\newcommand\csname#3s\endcsname{%
507   \if@begin@of@sentence{\cGlspl{#3}}{\cgl{spl}{#3}}\@xspace%
508 }

```


Expand the plural acronym macro in PDF labels.

```
509 \pdfstringdefDisableCommands{\expandafter\def\csname#3s\endcsname{%
510   \IfBooleanTF{#1}{#3}{\IfNoValueTF{#2}{#3s}{#2s}} }%
511 }
```

Provide the plural acronym macro in math mode.

```
512 \expandafter\mathdef\csname#3s\endcsname{%
513   \text{\glxstrshortpl{#3}}\glunset{#3}%
514 }
515 }
```

`\shortacronym` The `\shortacronym` never expands into the long form.

```
516 \DeclareDocumentCommand{\shortacronym}{somm}{
517   \newabbreviation[
518     \glsshortpluralkey=\IfBooleanTF{#1}{#3}{\IfNoValueTF{#2}{#3s}{#2s}}
519   ]{#3}{\IfNoValueTF{#2}{#3}{#2}}{#4}
```

Provide the singular acronym macro.

```
520 \expandafter\newcommand\csname#3\endcsname{\cgl{*}{#3}\@xspace}
```

Expand the singular acronym macro in PDF labels.

```
521 \pdfstringdefDisableCommands{\expandafter\def\csname#3\endcsname{%
522   \IfNoValueTF{#2}{#3}{#2} }%
523 }
```

Provide the singular acronym macro in math mode.

```
524 \expandafter\mathdef\csname#3\endcsname{\text{\glxstrshort*{#3}}}
```

Provide the plural acronym macro.

```
525 \expandafter\newcommand\csname#3s\endcsname{\cgl{spl*}{#3}\@xspace}
```

Expand the plural acronym macro in PDF labels.

```
526 \pdfstringdefDisableCommands{\expandafter\def\csname#3s\endcsname{%
527   \IfBooleanTF{#1}{#3}{\IfNoValueTF{#2}{#3s}{#2s}} }%
528 }
```

Provide the plural acronym macro in math mode.

```
529 \expandafter\mathdef\csname#3s\endcsname{\text{\glxstrshortpl*{#3}}}%
530 \glunset{#3}
531 }
```

`\longacronym` The `\longacronym` never shows the abbreviated form.

```
532 \DeclareDocumentCommand{\longacronym}{sommo}{
```


Provide the singular acronym macro.

```
533 \expandafter\newcommand\csname#3\endcsname{%
534   \if@begin@of@sentence{\MakeUppercase#4}{#4}\@xspace%
535 }
```

Expand the singular acronym macro in PDF labels.

```
536 \pdfstringdefDisableCommands{\expandafter\def\csname#3\endcsname{#4 }}
```

Provide the plural acronym macro.

```
537 \expandafter\newcommand\csname#3s\endcsname{%
538   \if@begin@of@sentence{%
539     \IfNoValueTF{#5}{\MakeUppercase#4s}{\MakeUppercase#5}%
540   }{%
541     \IfNoValueTF{#5}{#4s}{#5}}\@xspace%
542 }
```

Expand the plural acronym macro in PDF labels.

```
543 \pdfstringdefDisableCommands{\expandafter\def\csname#3s\endcsname{%
544   \IfNoValueTF{#5}{#4s}{#5} }}%
545 }
546 }
```

Silence warning if no acronyms are defined.

```
547 \renewcommand*{\@gls@write@entrycounts}{%
548   \immediate\write\@auxout{%
549     \string\providecommand*\@string\@gls@entry@count}[2]{%
550   }%
551   \count@=0\relax
552   \forallglsentries{\@glsentry}{%
553     \glshasattribute{\@glsentry}{entrycount}{%
554       \ifglssused{\@glsentry}{%
555         \immediate\write\@auxout{%
556           \string\@gls@entry@count{\@glsentry}{%
557             \glssentrycurrcount{\@glsentry}%
558         }
559       }%
560     }{\advance\count@ by \@ne
561   }{}%
562 }%
563 }
```

`\resetacronym` Add two macros for acronym management.

`\dummyacronym`

```
564 \newcommand{\resetacronym}[1]{\protect\glreset{#1}}
565 \newcommand{\dummyacronym}[1]{\protect\glunset{#1}}
```


End of glossaries if.

566 \fi

References

- [1] J. Hajer. *The `hep-paper` package. Publications in High Energy Physics*. 2019. CTAN: `hep-paper`. DOI: 10.5281/zenodo.3606436. GitHub: `janhajer/hep-paper`.
- [2] A. Holt and J.-F. Lamy. *The `a4wide` package. ‘Wide’ a4 layout*. depreciated and not used. 1986. CTAN: `a4wide`.
- [3] D. Carlisle and H. Umeki. *The `geometry` package. Flexible and complete interface to document dimensions*. 1996. CTAN: `geometry`. GitHub: `davidcarlisle/geometry`.
- [4] B. Jackowski and J. Nowacki. *Latin Modern Family of Fonts. Latin modern fonts in outline formats*. 2003. CTAN: `lm`. URL: <http://www.gust.org.pl/projects/e-foundry/latin-modern>.
- [5] R. Schlicht. *The `microtype` package. Subliminal refinements towards typographical perfection*. 2004. CTAN: `microtype`.
- [6] **L^AT_EX3 Project**. *Hypertext marks in L^AT_EX: a manual for `hyperref`. Extensive support for hypertext in L^AT_EX*. 1995. CTAN: `hyperref`. GitHub: `latex3/hyperref`.
- [7] J. Braams, J. Bezos and et al. *Babel Localization and internationalization. Multilingual support for Plain T_EX or L^AT_EX*. 1989. CTAN: `babel`. GitHub: `latex3/babel`.
- [8] R. Fairbairns, F. Mittelbach and H. Partl. *The `parskip` package. Layout with zero `\parindent`, non-zero `\parskip`*. 1989. CTAN: `parskip`. GitHub: `FrankMittelbach/fmitex`.
- [9] P. Lehman et al. *The `biblatex` Package. Sophisticated Bibliographies in L^AT_EX*. 2006. CTAN: `biblatex`. GitHub: `plk/biblatex`.
- [10] N. Talbot. *The `glossaries` package. Create glossaries and lists of acronyms*. 2007. CTAN: `glossaries`.
- [11] N. T. Dickimaw Books. *The `glossaries-extra` package. An extension to the `glossaries` package*. 2015. CTAN: `glossaries-extra`.
- [12] **American Physical Society**. *The `revtex` package. Styles for various Physics Journals*. 1999. CTAN: `revtex`. URL: <https://journals.aps.org/revtex>.
- [13] P. W. Daly. *A L^AT_EX Package to Prepare Author and Affiliation Blocks. Support for footnote style author/affiliation*. 2001. CTAN: `authblk`.
- [14] P. Lehman and J. Wright. *The `csquotes` Package. Context sensitive quotation facilities*. 2003. CTAN: `csquotes`.
- [15] P. G. Ratcliffe. *The `foreign` package for L^AT_EX2_ε. Systematic treatment of ‘foreign’ words in documents*. 2012. CTAN: `foreign`.
- [16] J. Bezos. *Customizing lists with the `enumitem` package. Control layout of itemize, enumerate, description*. 2003. CTAN: `enumitem`. URL: <http://www.texnia.com/enumitem.html>. GitHub: `jbezos/enumitem`.

- [17] T. Cubitt. *The cleveref package. Intelligent cross-referencing.* 2006. CTAN: cleveref. URL: <http://www.dr-qubit.org/cleveref.html>.
- [18] L. Madsen et al. *The mathtools package. Mathematical tools to use with amsmath.* 2004. CTAN: mathtools.
- [19] **American Mathematical Society.** *The amsfonts package. T_EX fonts from the American Mathematical Society.* 1995. CTAN: amsfonts. URL: <http://www.ams.org/tex/amsfonts.html>.
- [20] **L^AT_EX Team.** *The amsmath package. AMS mathematical facilities for L^AT_EX.* 1994. CTAN: amsmath. URL: <http://www.ams.org/tex/amslatex.html>.
- [21] **L^AT_EX Team.** *The bm package. Access bold symbols in maths mode.* 1993. CTAN: bm.
- [22] **L^AT_EX Team.** *L^AT_EX₂ ϵ font selection. Documentation of L^AT_EX font commands.* 1995. CTAN: fntguide.
- [23] W. Schmidt. *The fixmath package for L^AT_EX₂ ϵ . Make maths comply with ISO 31-0:1992 to ISO 31-13:1992.* 2000. CTAN: fixmath.
- [24] G. Milde. *The alphabeta package. LICR macros and encoding definition files for Greek.* 2013. CTAN: greek-fontenc.
- [25] S. C. de la Barrera. *The physics package. Macros supporting the Mathematics of Physics.* 2012. CTAN: physics.
- [26] D. Carlisle. *The slashed package. Put a slash through characters.* 1987. CTAN: slashed.
- [27] A. Reichert. *The units and nicefrac packages. Typeset units.* 1998. CTAN: units.
- [28] A. Sommerfeldt. *The subcaption package. Support for sub-captions.* 2007. CTAN: subcaption.
- [29] D. Els and S. Fear. *The booktabs package. Publication quality tables in L^AT_EX.* 1995. CTAN: booktabs.
- [30] P. van Oostrum and J. Leichter. *The multirow, bigstrut and bigdelim packages. Create tabular cells spanning multiple rows.* 1994. CTAN: multirow.
- [31] D. Carlisle and S. Rahtz. *Packages in the ‘graphics’ bundle. Enhanced support for graphics.* 1994. CTAN: graphicx.
- [32] F. Charette and P. Kime. *biber.* GitHub: plk/biber. SourceForge: biblatex-biber.
- [33] D. Sutherland. *arxiv-collector.* GitHub: dougalsutherland / arxiv - collector.
- [34] **L^AT_EX Team.** *The ifluatex package. Provides the \ifluatex switch.* 2007. CTAN: ifluatex.
- [35] **L^AT_EX Team.** *The iftex package. Am I running under XeTeX?* 2006. CTAN: ifxetex. GitHub: latex3/iftex.
- [36] **L^AT_EX Team.** *The fontenc package. Standard package for selecting font encodings.* CTAN: fontenc.
- [37] **L^AT_EX3 Project Team.** *L^AT_EX font encodings. Documentation of L^AT_EX font encodings.* 1995. CTAN: encguide.

- [38] **L^AT_EX Team**. *The `textcomp` package. L^AT_EX support for the Text Companion fonts*. 1995. CTAN: `textcomp`.
- [39] **L^AT_EX Team**. *The `inputenc` package. Accept different input encodings*. CTAN: `inputenc`.
- [40] M. Franz. *The `soul` package. Hyphenation for letterspacing, underlining, and more*. 1998. CTAN: `soul`.
- [41] D. Arseneau and M. Swift. *The `relsize` package. Set the font size relative to the current font size*. 2011. CTAN: `relsize`.
- [42] **L^AT_EX3 Project**. *The `xparse` package. A generic document command parser*. 1999. CTAN: `xparse`.
- [43] O. Dietrich. *The `sfmath` package. Sans-serif mathematics*. 2005. CTAN: `sfmath`. URL: <http://dtrx.de/od/tex/sfmath.html>.
- [44] A. Sommerfeldt. *The `caption` package. Customising captions in floating environments*. 1994. CTAN: `caption`. GitLab: `axelsommerfeldt/caption`.
- [45] D. Arseneau. *The `varwidth` package. A variable-width minipage*. 2003. CTAN: `varwidth`.
- [46] H. Oberdiek. *The `atbegshi` package. Execute stuff at `shipout` time*. 2007. CTAN: `atbegshi`. GitHub: `ho-tex/atbegshi`.
- [47] H. Oberdiek. *The `picture` package. Dimens for picture macros*. 2006. CTAN: `picture`. GitHub: `ho-tex/picture`.
- [48] H. Oberdiek. *The `pdftexcmds` package. LuaTeX support for pdfTeX utility functions*. 2007. CTAN: `pdftexcmds`.
- [49] S. Checkoway. *The `everyhook` package. Hooks for standard T_EX token lists*. 2010. CTAN: `everyhook`.

Change History

v1.0		L ^A T _E X source file	1
	General: Initial version of the style file	v1.2	
v1.1			
	General: Transition to documented	General: Inclusion of package options	1