

The `lthooks` package*

Frank Mittelbach†

August 31, 2020

Contents

1	Introduction	2
2	Package writer interface	2
2.1	L ^A T _E X 2 _ε interfaces	2
2.1.1	Declaring hooks and using them in code	2
2.1.2	Updating code for hooks	4
2.1.3	Hook names and default labels	5
2.1.4	Defining relations between hook code	6
2.1.5	Querying hooks	7
2.1.6	Displaying hook code	8
2.1.7	Debugging hook code	9
2.2	L3 programming layer (<code>expl3</code>) interfaces	9
2.3	On the order of hook code execution	11
2.4	The use of “reversed” hooks	12
2.5	Difference between “normal” and “one-time” hooks	13
2.6	Private L ^A T _E X kernel hooks	14
2.7	Legacy L ^A T _E X 2 _ε interfaces	14
2.8	L ^A T _E X 2 _ε commands and environments augmented by hooks	15
2.8.1	Generic hooks for all environments	15
2.8.2	Hooks provided by <code>\begin{document}</code>	16
2.8.3	Hooks provided by <code>\end{document}</code>	17
2.8.4	Hooks provided <code>\shipout</code> operations	18
2.8.5	Hooks provided by file loading operations	18
2.8.6	Hooks provided in NFSS commands	18

*This package has version v1.0a dated 2020/08/31, © L^AT_EX Project.

†Code improvements for speed and other goodies by Phelype Oleinik

3	The Implementation	19
3.1	Loading further extensions	19
3.2	Debugging	19
3.3	Borrowing from internals of other kernel modules	20
3.4	Declarations	20
3.5	Providing new hooks	21
3.6	Parsing a label	23
3.7	Setting rules for hooks code	31
3.8	Specifying code for next invocation	44
3.9	Using the hook	44
3.10	Querying a hook	46
3.11	Messages	47
3.12	L ^A T _E X 2 _ε package interface commands	48
3.13	Internal commands needed elsewhere	51

Index	52
--------------	-----------

1 Introduction

Hooks are points in the code of commands or environments where it is possible to add processing code into existing commands. This can be done by different packages that do not know about each other and to allow for hopefully safe processing it is necessary to sort different chunks of code added by different packages into a suitable processing order.

This is done by the packages adding chunks of code (via `\AddToHook`) and labeling their code with some label by default using the package name as a label.

At `\begin{document}` all code for a hook is then sorted according to some rules (given by `\DeclareHookRule`) for fast execution without processing overhead. If the hook code is modified afterwards (or the rules are changed), a new version for fast processing is generated.

Some hooks are used already in the preamble of the document. If that happens then the hook is prepared for execution (and sorted) already at that point.

2 Package writer interface

The hook management system is offered as a set of CamelCase commands for traditional L^AT_EX 2_ε packages (and for use in the document preamble if needed) as well as `expl3` commands for modern packages, that use the L3 programming layer of L^AT_EX. Behind the scenes, a single set of data structures is accessed so that packages from both worlds can coexist and access hooks in other packages.

2.1 L^AT_EX 2_ε interfaces

2.1.1 Declaring hooks and using them in code

With two exceptions, hooks have to be declared before they can be used. The exceptions are hooks in environments (i.e., executed at `\begin` and `\end`) and hooks run when loading files, e.g. before and after a package is loaded, etc. Their hook names depend on the environment or the file name and so declaring them beforehand is difficult.

`\NewHook`

`\NewHook {<hook>}`

Creates a new *<hook>*. If this is a hook provided as part of a package it is suggested that the *<hook>* name is always structured as follows: *<package-name>/<hook-name>*. If necessary you can further subdivide the name by adding more / parts. If a hook name is already taken, an error is raised and the hook is not created.

The *<hook>* can be specified using the dot-syntax to denote the current package name. See section 2.1.3.

`\NewReversedHook`

`\NewReversedHook {<hook>}`

Like `\NewHook` declares a new *<hook>*. the difference is that the code chunks for this hook are in reverse order by default (those added last are executed first). Any rules for the hook are applied after the default ordering. See sections 2.3 and 2.4 for further details.

The *<hook>* can be specified using the dot-syntax to denote the current package name. See section 2.1.3.

`\NewMirroredHookPair`

`\NewMirroredHookPair {<hook-1>} {<hook-2>}`

A shorthand for `\NewHook{<hook-1>}\NewReversedHook{<hook-2>}`.

The *<hooks>* can be specified using the dot-syntax to denote the current package name. See section 2.1.3.

`\UseHook`

`\UseHook {<hook>}`

Execute the hook code inside a command or environment.

Before `\begin{document}` the fast execution code for a hook is not set up, so in order to use a hook there it is explicitly initialized first. As that involves assignments using a hook at those times is not 100% the same as using it after `\begin{document}`.

The *<hook>* *cannot* be specified using the dot-syntax. A leading . is treated literally.

`\UseOneTimeHook`

`\UseOneTimeHook {<hook>}`

Some hooks are only used (and can be only used) in one place, for example, those in `\begin{document}` or `\end{document}`. Once we have passed that point adding to the hook through a defined `\<addto-cmd>` command (e.g., `\AddToHook` or `\AtBeginDocument`, etc.) would have no effect (as would the use of such a command inside the hook code itself). It is therefore customary to redefine `\<addto-cmd>` to simply process its argument, i.e., essentially make it behave like `\@firstofone`.

`\UseOneTimeHook` does that: it records that the hook has been consumed and any further attempt to add to it will result in executing the code to be added immediately.

FMi: Maybe add an error version as well?

The *<hook>* *cannot* be specified using the dot-syntax. A leading . is treated literally.

2.1.2 Updating code for hooks

\AddToHook	\AddToHook {<hook>}[<label>]{<code>}
-------------------	---

Adds <code> to the <hook> labeled by <label>. If the optional argument <label> is not provided, if `\AddToHook` is used in a package/class, then the current package/class name is used, otherwise `top-level` is used (see section 2.1.3).

If there already exists code under the <label> then the new <code> is appended to the existing one (even if this is a reversed hook). If you want to replace existing code under the <label>, first apply `\RemoveFromHook`.

The hook doesn't have to exist for code to be added to it. However, if it is not declared later then obviously the added <code> will never be executed. This allows for hooks to work regardless of package loading order and enables packages to add to hook of other packages without worrying whether they are actually used in the current document. See section 2.1.5.

The <hook> and <label> can be specified using the dot-syntax to denote the current package name. See section 2.1.3.

\RemoveFromHook	\RemoveFromHook {<hook>}[<label>]
------------------------	--

Removes any code labeled by <label> from the <hook>. If the optional argument <label> is not provided, if `\AddToHook` is used in a package/class, then the current package/class name is used, otherwise `top-level` is used.

If the optional argument is `*`, then all code chunks are removed. This is rather dangerous as it drops code from other packages one may not know about!

The <hook> and <label> can be specified using the dot-syntax to denote the current package name. See section 2.1.3.

In contrast to the `voids` relationship between two labels in a `\DeclareHookrule` this is a destructive operation as the labeled code is removed from the hook data structure, whereas the relationship setting can be undone by providing a different relationship later.

A useful application for this declaration inside the document body is when one wants to temporarily add code to hooks and later remove it again, e.g.,

```
\AddToHook{env/quote/before}{\small}
\begin{quote}
  A quote set in a smaller typeface
\end{quote}
...
\RemoveFromHook{env/quote/before}
... now back to normal for further quotes
```

Note that you can't cancel the setting with

```
\AddToHook{env/quote/before}{}
```

because that only "adds" a further empty chunk of code to the hook. Adding `\normalsize` would work but that means the hook then contained `\small\normalsize` which means to font size changes for no good reason.

The above is only needed if one wants to typeset several quotes in a smaller typeface. If the hook is only needed once then `\AddToHookNext` is simpler, because it resets itself after one use.

`\AddToHookNext`

`\AddToHookNext {<hook>}{<code>}`

Adds `<code>` to the next invocation of the `<hook>`. The code is executed after the normal hook code has finished and it is executed only once, i.e. it is deleted after it was used.

Using the declaration is a global operation, i.e., the code is not lost, even if the declaration is used inside a group and the next invocation happens after the group. If the declaration is used several times before the hook is executed then all code is executed in the order in which it was declared.¹

It is possible to nest declarations using the same hook (or different hooks), e.g.,

```
\AddToHookNext{<hook>}{<code-1>\AddToHookNext{<hook>}{<code-2>}}
```

will execute `<code-1>` next time the `<hook>` is used and at that point puts `<code-2>` into the `<hook>` so that it gets executed on following time the hook is run.

A hook doesn't have to exist for code to be added to it. This allows for hooks to work regardless of package loading order. See section 2.1.5.

The `<hook>` can be specified using the dot-syntax to denote the current package name. See section 2.1.3.

2.1.3 Hook names and default labels

It is best practice to use `\AddToHook` in packages or classes *without specifying a <label>* because then the package or class name is automatically used, which is helpful if rules are needed, and avoids mistyping the `<label>`.

Using an explicit `<label>` is only necessary in very specific situations, e.g., if you want to add several chunks of code into a single hook and have them placed in different parts of the hook (by providing some rules).

The other case is when you develop a larger package with several sub-packages. In that case you may want to use the same `<label>` throughout the sub-packages in order to avoid that the labels change if you internally reorganize your code.

It is not enforced, but highly recommended that the hooks defined by a package, and the `<labels>` used to add code to other hooks contain the package name to easily identify the source of the code chunk and to prevent clashes. This should be the standard practice, so this hook management code provides a shortcut to refer to the current package in the name of a `<hook>` and in a `<label>`. If `<hook>` name or `<label>` consist just of a single dot (`.`), or starts with a dot followed by a slash (`./`) then the dot denotes the `<default label>` (usually the current package or class name—see `\DeclareDefaultHookLabel`). A `“.”` or `“./”` anywhere else in a `<hook>` or in `<label>` is treated literally and is not replaced.

For example, inside the package `mypackage.sty`, the default label is `mypackage`, so the instructions:

```
\NewHook    {./hook}
\AddToHook  {./hook}[.]{code}      % Same as \AddToHook{./hook}{code}
\AddToHook  {./hook}[./sub]{code}
\DeclareHookRule{begindocument}{.}{before}{babel}
\AddToHook  {file/after/foo.tex}{code}
```

are equivalent to:

```
\NewHook    {mypackage/hook}
\AddToHook  {mypackage/hook}[mypackage]{code}
```

¹There is no mechanism to reorder such code chunks (or delete them).

```

\AddToHook {mypackage/hook}[mypackage/sub]{code}
\DeclareHookRule{begindocument}{mypackage}{before}{babel}
\AddToHook {file/after/foo.tex}{code} % unchanged

```

The $\langle default label \rangle$ is automatically set to the name of the current package or class (using $\@currname$). If $\@currname$ is not set (because the hook command is used outside of a package, or the current file wasn't loaded with \usepackage or \documentclass), then the `top-level` is used as the $\langle default label \rangle$.

This syntax is available in all $\langle label \rangle$ arguments and most $\langle hook \rangle$, both in the L^AT_EX 2_ε interface, and the L^AT_EX 3 interface described in section 2.2.

Note, however, that the replacement of \cdot by the $\langle default label \rangle$ takes place when the hook command is executed, so actions that are somehow executed after the package ends will have the wrong $\langle default label \rangle$ if the dot-syntax is used. For that reason, this syntax is not available in \UseHook (and $\hook_use:n$) because the hook is most of the time used outside of the package file in which it was defined. This syntax is also not available in the hook conditionals \IfHookEmptyTF (and $\hook_if_empty:nTF$) and \IfHookExistsTF (and $\hook_if_exist:nTF$) because these conditionals are used in some performance-critical parts of the hook management code, and because they are usually used to refer to other package's hooks, so the dot-syntax doesn't make much sense.

In some cases, for example in large packages, one may want to separate it in logical parts, but still use the main package name as $\langle label \rangle$, then the $\langle default label \rangle$ can be set using \DeclareDefaultHookLabel :

\DeclareDefaultHookLabel	$\DeclareDefaultHookLabel \{\langle default label \rangle\}$
----------------------------	--

Sets the $\langle default label \rangle$ to be used in $\langle label \rangle$ arguments. If \DeclareDefaultHookLabel is not used in the current package, $\@currname$ is used instead. If $\@currname$ is not set, the code is assumed to be in the main document, in which case `top-level` is used.

The effect of \DeclareDefaultHookLabel holds for the current file, and is reset to the previous value when the file is closed.

2.1.4 Defining relations between hook code

The default assumption is that code added to hooks by different packages is independent and the order in which it is executed is irrelevant. While this is true in many case it is obviously false in many others.

Before the hook management system was introduced packages had to take elaborate precaution to determine of some other package got loaded as well (before or after) and find some ways to alter its behavior accordingly. In addition it was often the user's responsibility to load packages in the right order so that code added to hooks got added in the right order and some cases even altering the loading order wouldn't resolve the conflicts.

With the new hook management system it is now possible to define rules (i.e., relationships) between code chunks added by different packages and explicitly describe in which order they should be processed.

<hr/> \DeclareHookRule <hr/>	$\backslash\text{DeclareHookRule}\{\langle\text{hook}\rangle\}\{\langle\text{label1}\rangle\}\{\langle\text{relation}\rangle\}\{\langle\text{label2}\rangle\}$ Defines a relation between $\langle\text{label1}\rangle$ and $\langle\text{label2}\rangle$ for a given $\langle\text{hook}\rangle$. If $\langle\text{hook}\rangle$ is ?? this defines a default relation for all hooks that use the two labels, i.e., that have chunks of code labeled with $\langle\text{label1}\rangle$ and $\langle\text{label2}\rangle$. Rules specific to a given hook take precedence over default rules that use ?? as the $\langle\text{hook}\rangle$. Currently, the supported relations are the following: <p>before or < Code for $\langle\text{label1}\rangle$ comes before code for $\langle\text{label2}\rangle$.</p> <p>after or > Code for $\langle\text{label1}\rangle$ comes after code for $\langle\text{label2}\rangle$.</p> <p>incompatible-warning Only code for either $\langle\text{label1}\rangle$ or $\langle\text{label2}\rangle$ can appear for that hook (a way to say that two packages—or parts of them—are incompatible). A warning is raised if both labels appear in the same hook.</p> <p>incompatible-error Like incompatible-error but instead of a warning a L^AT_EX error is raised, and the code for both labels are dropped from that hook until the conflict is resolved.</p> <p>voids Code for $\langle\text{label1}\rangle$ overwrites code for $\langle\text{label2}\rangle$. More precisely, code for $\langle\text{label2}\rangle$ is dropped for that hook. This can be used, for example if one package is a superset in functionality of another one and therefore wants to undo code in some hook and replace it with its own version.</p> <p>unrelated The order of code for $\langle\text{label1}\rangle$ and $\langle\text{label2}\rangle$ is irrelevant. This rule is there to undo an incorrect rule specified earlier.</p>
-------------------------------------	---

There can only be a single relation between two labels for a given hook, i.e., a later `\DeclareHookrule` overwrites any previous delcaration.

The $\langle\text{hook}\rangle$ and $\langle\text{label}\rangle$ can be specified using the dot-syntax to denote the current package name. See section 2.1.3.

<hr/> \ClearHookRule <hr/>	$\backslash\text{ClearHookRule}\{\langle\text{hook}\rangle\}\{\langle\text{label1}\rangle\}\{\langle\text{label2}\rangle\}$ Syntactic sugar for saying that $\langle\text{label1}\rangle$ and $\langle\text{label2}\rangle$ are unrelated for the given $\langle\text{hook}\rangle$.
-----------------------------------	--

<hr/> \DeclareDefaultHookRule <hr/>	$\backslash\text{DeclareDefaultHookRule}\{\langle\text{label1}\rangle\}\{\langle\text{relation}\rangle\}\{\langle\text{label2}\rangle\}$ This sets up a relation between $\langle\text{label1}\rangle$ and $\langle\text{label2}\rangle$ for all hooks unless overwritten by a specific rule for a hook. Useful for cases where one package has a specific relation to some other package, e.g., is incompatible or always needs a special ordering before or after . (Technically it is just a shorthand for using <code>\DeclareHookRule</code> with ?? as the hook name.) Declaring default rules is only supported in the document preamble. ² The $\langle\text{label}\rangle$ can be specified using the dot-syntax to denote the current package name. See section 2.1.3.
--	---

2.1.5 Querying hooks

Simpler data types, like token lists, have three possible states; they can:

- exist and be empty;

²Trying to do so, e.g., via `\DeclareHookRule` with ?? has bad side-effects and is not supported (though not explicitly caught for performance reasons).

- exist and be non-empty; and
- not exist (in which case emptiness doesn't apply);

Hooks are a bit more complicated: they have four possible states. A hook may exist or not, and either way it may or may not be empty. This means that even a hook that doesn't exist may be non-empty.

This seemingly strange state may happen when, for example, package *A* defines hook *A/foo*, and package *B* adds some code to that hook. However, a document may load package *B* before package *A*, or may not load package *A* at all. In both cases some code is added to hook *A/foo* without that hook being defined yet, thus that hook is said to be non-empty, whereas it doesn't exist. Therefore, querying the existence of a hook doesn't imply its emptiness, neither does the other way around.

A hook is said to be empty when no code was added to it, either to its permanent code pool, or to its “next” token list. The hook doesn't need to be declared to have code added to its code pool. A hook is said to exist when it was declared with `\NewHook` or some variant thereof.

<code>\IfHookEmptyTF</code> ★	<code>\IfHookEmptyTF {<hook>} {<true code>} {<false code>}</code>
-------------------------------	---

Tests if the *<hook>* is empty (*i.e.*, no code was added to it using either `\AddToHook` or `\AddToHookNext`), and branches to either *<true code>* or *<false code>* depending on the result.

The *<hook>* *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

<code>\IfHookExistsTF</code> ★	<code>\IfHookExistsTF {<hook>} {<true code>} {<false code>}</code>
--------------------------------	--

Tests if the *<hook>* exists (if it was created with either `\NewHook`, `\NewReversedHook`, or `\NewMirroredHookPair`), and branches to either *<true code>* or *<false code>* depending on the result.

The existence of a hook usually doesn't mean much from the viewpoint of code that tries to add/remove code from that hook, since package loading order may vary, thus the creation of hooks is asynchronous to adding and removing code from it, so this test should be used sparingly.

The *<hook>* *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

FMi: Would be helpful if we provide some use cases

2.1.6 Displaying hook code

If one has to adjust the code execution in a hook using a hook rule it is helpful to get some information about the code associated with a hook, its current order and the existing rules.

<code>\ShowHook</code>	<code>\ShowHook {⟨hook⟩}</code>
------------------------	---------------------------------

Displays information about the $\langle hook \rangle$ such as

- the code chunks (and their labels) added to it,
- any rules set up to order them,
- the computed order in which the chunks are executed,
- any code executed on the next invocation only.

The $\langle hook \rangle$ can be specified using the dot-syntax to denote the current package name. See section 2.1.3.

2.1.7 Debugging hook code

<code>\DebugHooksOn</code>	<code>\DebugHooksOn</code>
----------------------------	----------------------------

<code>\DebugHooksOff</code>

Turn the debugging of hook code on or off. This displays changes made to the hook data structures. The output is rather coarse and not really intended for normal use.

2.2 L3 programming layer (expl3) interfaces

This is a quick summary of the L^AT_EX3 programming interfaces for use with packages written in `expl3`. In contrast to the L^AT_EX_{2 ϵ} interfaces they always use mandatory arguments only, e.g., you always have to specify the $\langle label \rangle$ for a code chunk. We therefore suggest to use the declarations discussed in the previous section even in `expl3` packages, but the choice is yours.

<code>\hook_new:n</code>	<code>\hook_new:n{⟨hook⟩}</code>
<code>\hook_new_reversed:n</code>	<code>\hook_new_pair:nn{⟨hook-1⟩}{⟨hook-2⟩}</code>
<code>\hook_new_pair:nn</code>	

Creates a new $\langle hook \rangle$ with normal or reverse ordering of code chunks. `\hook_new_pair:nn` creates a pair of such hooks with $\{ \langle hook-2 \rangle \}$ being a reversed hook. If a hook name is already taken, an error is raised and the hook is not created.

The $\langle hook \rangle$ can be specified using the dot-syntax to denote the current package name. See section 2.1.3.

<code>\hook_use:n</code>	<code>\hook_use:n {⟨hook⟩}</code>
--------------------------	-----------------------------------

Executes the $\{ \langle hook \rangle \}$ code followed (if set up) by the code for next invocation only, then empties that next invocation code.

The $\langle hook \rangle$ *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

<code>\hook_use_once:n</code>	<code>\hook_use_once:n {⟨hook⟩}</code>
-------------------------------	--

Changes the $\{ \langle hook \rangle \}$ status so that from now on any addition to the hook code is executed immediately. Then execute any $\{ \langle hook \rangle \}$ code already set up.

FMi: better L3 name?

The $\langle hook \rangle$ *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

<hr/> <hr/> <code>\hook_gput_code:nnn</code>	<code>\hook_gput_code:nnn {<hook>} {<label>} {<code>}</code> <p>Adds a chunk of <code><code></code> to the <code><hook></code> labeled <code><label></code>. If the label already exists the <code><code></code> is appended to the already existing code.</p> <p>If code is added to an external <code><hook></code> (of the kernel or another package) then the convention is to use the package name as the <code><label></code> not some internal module name or some other arbitrary string.</p> <p>The <code><hook></code> and <code><label></code> can be specified using the dot-syntax to denote the current package name. See section 2.1.3.</p>
<hr/> <hr/> <code>\hook_gput_next_code:nn</code>	<code>\hook_gput_next_code:nn {<hook>} {<code>}</code> <p>Adds a chunk of <code><code></code> for use only in the next invocation of the <code><hook></code>. Once used it is gone.</p> <p>This is simpler than <code>\hook_gput_code:nnn</code>, the code is simply appended to the hook in the order of declaration at the very end, i.e., after all standard code for the hook got executed.</p> <p>Thus if one needs to undo what the standard does one has to do that as part of <code><code></code>.</p> <p>The <code><hook></code> can be specified using the dot-syntax to denote the current package name. See section 2.1.3.</p>
<hr/> <hr/> <code>\hook_gremove_code:nn</code>	<code>\hook_gremove_code:nn {<hook>} {<label>}</code> <p>Removes any code for <code><hook></code> labeled <code><label></code>.</p> <p>If the code for that <code><label></code> wasn't yet added to the <code><hook></code>, an order is set so that when some code attempts to add that label, the removal order takes action and the code is not added.</p> <p>If the second argument is <code>*</code>, then all code chunks are removed. This is rather dangerous as it drops code from other packages one may not know about, so think twice before using that!</p> <p>The <code><hook></code> and <code><label></code> can be specified using the dot-syntax to denote the current package name. See section 2.1.3.</p>
<hr/> <hr/> <code>\hook_gset_rule:nnnn</code>	<code>\hook_gset_rule:nnnn {<hook>} {<label1>} {<relation>} {<label2>}</code> <p>Relate <code><label1></code> with <code><label2></code> when used in <code><hook></code>. See <code>\DeclareHookRule</code> for the allowed <code><relation></code>s. If <code><hook></code> is <code>??</code> a default rule is specified.</p> <p>The <code><hook></code> and <code><label></code> can be specified using the dot-syntax to denote the current package name. See section 2.1.3. The dot-syntax is parsed in both <code><label></code> arguments, but it usually makes sense to be used in only one of them.</p>
<hr/> <hr/> <code>\hook_if_empty_p:n *</code> <hr/> <hr/> <code>\hook_if_empty:nTF *</code>	<code>\hook_if_empty:nTF {<hook>} {<true code>} {<false code>}</code> <p>Tests if the <code><hook></code> is empty (<i>i.e.</i>, no code was added to it using either <code>\AddToHook</code> or <code>\AddToHookNext</code>), and branches to either <code><true code></code> or <code><false code></code> depending on the result.</p> <p>The <code><hook></code> <i>cannot</i> be specified using the dot-syntax. A leading <code>.</code> is treated literally.</p>

<code>\hook_if_exist_p:n *</code> <code>\hook_if_exist:nTF *</code>	<code>\hook_if_exist:nTF {<hook>} {<true code>} {<false code>}</code> Tests if the <i><hook></i> exists (if it was created with either <code>\NewHook</code> , <code>\NewReversedHook</code> , or <code>\NewMirroredHookPair</code>), and branches to either <i><true code></i> or <i><false code></i> depending on the result.
--	---

FMi: what are the results for generic hooks that do not need to be declared?

The existence of a hook usually doesn't mean much from the viewpoint of code that tries to add/remove code from that hook, since package loading order may vary, thus the creation of hooks is asynchronous to adding and removing code from it, so this test should be used sparingly.

The *<hook>* *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

<code>\hook_debug_on:</code> <code>\hook_debug_off:</code>	<code>\hook_debug_on:</code> Turns the debugging of hook code on or off. This displays changes to the hook data.
---	---

2.3 On the order of hook code execution

Chunks of code for a *<hook>* under different labels are supposed to be independent if there are no special rules set up that define a relation between the chunks. This means that you can't make assumptions about the order of execution!

Suppose you have the following declarations:

```
\NewHook{myhook}
\AddToHook{myhook}[packageA]{\typeout{A}}
\AddToHook{myhook}[packageB]{\typeout{B}}
\AddToHook{myhook}[packageC]{\typeout{C}}
```

then executing the hook with `\UseHook` will produce the typeout A B C in that order. In other words, the execution order is computed to be `packageA`, `packageB`, `packageC` which you can verify with `\ShowHook{myhook}`:

```
The hook 'myhook':
Code chunks:
  packageA -> \typeout {A}
  packageB -> \typeout {B}
  packageC -> \typeout {C}
Extra code next invocation:
  ---
Rules:
  ---
Execution order:
  packageA, packageB, packageC
```

The reason is that the code chunks are internally saved in a property list and the initial order of such a property list is the order in which key-value pairs got added. However, that is only true if nothing other than adding happens!

Suppose, for example, you want to replace the code chunk for `packageA`, e.g.,

```
\RemoveFromHook{myhook}[packageA]
\AddToHook{myhook}[packageA]{\typeout{A alt}}
```

then your order becomes `packageB`, `packageC`, `packageA` because the label got removed from the property list and then re-added (at its end).

While that may not be too surprising, the execution order is also sometimes altered if you add a redundant rule, e.g. if you specify

```
\DeclareHookRule{myhook}{packageA}{before}{packageB}
```

instead of the previous lines we get

```
The hook 'myhook':
Code chunks:
  packageA -> \typeout {A}
  packageB -> \typeout {B}
  packageC -> \typeout {C}
Extra code next invocation:
---
Rules:
  packageA|packageB with relation before
Execution order (after applying rules):
  packageA, packageC, packageB
```

As you can see the code chunks are still in the same order, but in the execution order for the labels `packageB` and `packageC` have swapped places. The reason is that, with the rule there are two orders that satisfy it, and the algorithm for sorting happened to pick a different one compared to the case without rules (where it doesn't run at all as there is nothing to resolve). Incidentally, if we had instead specified the redundant rule

```
\DeclareHookRule{myhook}{packageB}{before}{label-3}
```

the execution order would not have changed.

In summary: it is not possible to rely on the order of execution unless there are rules that partially or fully define the order (in which you can rely on them being fulfilled).

2.4 The use of “reversed” hooks

You may have wondered why you can declare a “reversed” hook with `\NewReversedHook` and what that does exactly.

In short: the execution order of a reversed hook (without any rules!) is exactly reversed to the order you would have gotten for a hook declared with `\NewHook`.

This is helpful if you have a pair of hooks where you expect to see code added that involves grouping, e.g., starting an environment in the first and closing that environment in the second hook. To give a somewhat contrived example³, suppose there is a package adding the following:

```
\AddToHook{env/quote/before}[package-1]{\begin{itshape}}
\AddToHook{env/quote/after} [package-1]{\end{itshape}}
```

As a result, all quotes will be in italics. Now suppose further that the user wants the quotes also in blue and therefore adds:

³there are simpler ways to achieve the same effect.

```

\usepackage{color}
\AddToHook{env/quote/before}{\begin{color}{blue}}
\AddToHook{env/quote/after}{\end{color}}

```

Now if the `env/quote/after` hook would be a normal hook we would get the same execution order in both hooks, namely:

```
package-1, top-level
```

(or vice versa) and as a result, would get:

```

\begin{itshape}\begin{color}{blue} ...
\end{itshape}\end{color}

```

and an error message that `\begin{color}` ended by `\end{itshape}`. With `env/quote/after` declared as a reversed hook the execution order is reversed and so all environments are closed in the correct sequence and `\ShowHook` would give us the following output:

```

The hook 'env/quote/after':
Code chunks:
  package-1 -> \end {itshape}
  top-level -> \end {color}
Extra code next invocation:
---
Rules:
---
Execution order (after reversal):
  top-level, package-1

```

The reversal of the execution order happens before applying any rules, so if you alter the order you will probably have to alter it in both hooks, not just in one, but that depends on the use case.

2.5 Difference between “normal” and “one-time” hooks

When executing a hook a developer has the choice of using either `\UseHook` or `\UseOneTimeHook` (or their `expl3` equivalents `\hook_use:n` and `\hook_use_once:n`). This choice affects how `\AddToHook` is handled after the hook has been executed for the first time.

With normal hooks adding code via `\AddToHook` means that the code chunk is added to the hook data structure and then used each time `\UseHook` is called.

With one-time hooks it this is handled slightly differently: After `\UseOneTimeHook` has been called, any further attempts to add code to the hook via `\AddToHook` will simply execute the `<code>` immediately.

This has some consequences one needs to be aware of:

- If `<code>` is added to a normal hook after the hook was executed and it is never executed again for one or the other reason, then this new `<code>` will never be executed.
- In contrast if that happens with a one-time hook the `<code>` is executed immediately.

In particular this means that construct such as

```

\AddToHook{myhook}
{ \code-1 \AddToHook{myhook}{\code-2} \code-3 }

```

works for one-time hooks⁴ (all three code chunks are executed one after another), but it makes little sense with a normal hook, because with a normal hook the first time `\UseHook{myhook}` is executed it would

- execute `\code-1`,
- then execute `\AddToHook{myhook}{\code-2}` which adds the code chunk `\code-2` to the hook for use on the next invocation,
- and finally execute `\code-3`.

The second time `\UseHook` is called it would execute the above and in addition `\code-2` as that was added as a code chunk to the hook in the meantime. So each time the hook is used another copy of `\code-2` is added and so that code chunk is executed $\langle \# \text{ of invocations} \rangle - 1$ times.

2.6 Private L^AT_EX kernel hooks

There are a few places where it is absolutely essential for L^AT_EX to function correctly that code is executed in a precisely defined order. Even that could have been implemented with the hook management (by adding various rules to ensure the appropriate ordering with respect to other code added by packages). However, this makes every document unnecessary slow, because there has to be sorting even though the result is predetermined. Furthermore it forces package writers to unnecessarily add such rules if they add further code to the hook (or break L^AT_EX).

For that reason such code is not using the hook management, but instead private kernel commands directly before or after a public hook with the following naming convention: `\@kernel@before@hookname` or `\@kernel@after@hookname`. For example, in `\enddocument` you find

```

\UseHook{enddocument}%
\@kernel@after@enddocument

```

which means first the user/package-accessible `enddocument` hook is executed and then the internal kernel hook. As their name indicates these kernel commands should not be altered by third-party packages, so please refrain from that in the interest of stability and instead use the public hook next to it.⁵

2.7 Legacy L^AT_EX 2_ε interfaces

L^AT_EX 2_ε offered a small number of hooks together with commands to add to them. They are listed here and are retained for backwards compatibility.

With the new hook management several additional hooks have been added to L^AT_EX and more will follow. See the next section for what is already available.

⁴This is sometimes used with `\AtBeginDocument` which is why it is supported.

⁵As with everything in T_EX there is not enforcement of this rule, and by looking at the code it is easy to find out how the kernel adds to them. The main reason of this section is therefore to say “please don’t do that, this is unconfigurable code!”

<code>\AtBeginDocument</code>	<code>\AtBeginDocument [<i>label</i>] {<i>code</i>}</code>
-------------------------------	--

If used without the optional argument *label*, it works essentially like before, i.e., it is adding *code* to the hook `begindocument` (which is executed inside `\begin{document}`). However, all code added this way is labeled with the label `top-level` if done outside of a package or class or with the package/class name if called inside such a file.

This way one can add further code to the hook using `\AddToHook` or `\AtBeginDocument` using a different label and explicitly order the code chunks as necessary, e.g., run some code before or after the `top-level` code. When using the optional argument the call is equivalent to running `\AddToHook {begindocument} [label] {code}`.

For important packages with known order requirement we may over time add rules to the kernel (or to those packages) so that they work regardless of the loading-order in the document.

<code>\AtEndDocument</code>	<code>\AtEndDocument [<i>label</i>] {<i>code</i>}</code>
-----------------------------	--

Like `\AtBeginDocument` but for the `enddocument` hook.

<code>\AtBeginDvi</code>	<code>\AtBeginDvi [<i>label</i>] {<i>code</i>}</code>
--------------------------	---

This hook is discussed in conjunction with the shipout hooks.

The few hooks that existed previously in $\text{\LaTeX 2}_{\epsilon}$ used internally commands such as `\@begindocumenthook` and packages sometimes augmented them directly rather than working through `\AtBeginDocument`. For that reason there is currently support for this, that is, if the system detects that such an internal legacy hook command contains code it adds it to the new hook system under the label `legacy` so that it doesn't get lost.

However, over time the remaining cases of direct usage need updating because in one of the future release of \LaTeX we will turn this legacy support off, as it does unnecessary slow down the processing.

2.8 $\text{\LaTeX 2}_{\epsilon}$ commands and environments augmented by hooks

intro to be written

2.8.1 Generic hooks for all environments

Every environment *env* has now four associated hooks coming with it:

env/*env***/before** This hook is executed as part of `\begin` as the very first action, in particular prior to starting the environment group. Its scope is therefore not restricted by the environment.

env/*env***/begin** This hook is executed as part of `\begin` directly in front of the code specific to the environment start (e.g., the second argument of `\newenvironment`). Its scope is the environment body.

env/*env***/end** This hook is executed as part of `\end` directly in front of the code specific to the end of the environment (e.g., the third argument of `\newenvironment`).

env/⟨env⟩/after This hook is executed as part of `\end` after the code specific to the environment end and after the environment group has ended. Its scope is therefore not restricted by the environment.

The hook is implemented as a reversed hook so if two packages add code to `env/⟨env⟩/before` and to `env/⟨env⟩/after` they can add surrounding environments and the order of closing them happens in the right sequence.

Generic environment hooks are never one-time hooks even with environments that are supposed to appear only once in a document.⁶ In contrast to other hooks there is also no need to declare them using `\NewHook`.

The hooks are only executed if `\begin{⟨env⟩}` and `\end{⟨env⟩}` is used. If the environment code is executed via low-level calls to `\⟨env⟩` and `\end⟨env⟩` (e.g., to avoid the environment grouping) they are not available. If you want them available in code using this method, you would need to add them yourself, i.e., write something like

```
\UseHook{env/quote/before}\quote
...
\endquote\UseHook{env/quote/after}
```

to add the outer hooks, etc.

<hr/> <hr/> <code>\BeforeBeginEnvironment</code>	<code>\BeforeBeginEnvironment [⟨label⟩] {⟨code⟩}</code>	This declaration adds to the <code>env/⟨env⟩/before</code> hook using by default the current package or class name as a label or <code>top-level</code> if used in the document directly.
<hr/> <code>\AtBeginEnvironment</code> <hr/>	<code>\AtBeginEnvironment [⟨label⟩] {⟨code⟩}</code>	Like <code>\BeforeBeginEnvironment</code> but adds to the <code>env/⟨env⟩/begin</code> hook.
<hr/> <code>\AtEndEnvironment</code> <hr/>	<code>\AtEndEnvironment [⟨label⟩] {⟨code⟩}</code>	Like <code>\BeforeBeginEnvironment</code> but adds to the <code>env/⟨env⟩/end</code> hook.
<hr/> <code>\AfterEndEnvironment</code> <hr/>	<code>\AfterEndEnvironment [⟨label⟩] {⟨code⟩}</code>	Like <code>\BeforeBeginEnvironment</code> but adds to the <code>env/⟨env⟩/after</code> hook.

2.8.2 Hooks provided by `\begin{document}`

Until 2020 `\begin{document}` offered exactly one hook that one could add to using `\AtBeginDocument`. Experiences over the years have shown that this single hook in one place was not enough and as part of adding the general hook management system a number of additional hooks have been added at this point. The places for these hooks have been chosen to provide the same support as offered by external packages, such as `etoolbox` and others that augmented `\document` to gain better control.

Supported are now the following hooks (all of them one-time hooks):

begindocument/before This hook is executed at the very start of `\document`, one can think of it as a hook for code at the end of the preamble section and this is how it is used by `etoolbox`'s `\AtEndPreamble`.

⁶Thus if one adds code to such hooks after the environment has been processed, it will only be executed if the environment appears again and if that doesn't happen the code will never get executed.

begindocument This hook is added to when using `\AtBeginDocument` and it is executed after the `.aux` file as be read in and most initialization are done, so they can be altered and inspected by the hook code. It is followed by a small number of further initializations that shouldn't be altered and are therefore coming later.

The hook should not be used to add material for typesetting as we are still in L^AT_EX's initialization phase and not in the document body. If such material needs to be added to the document body use the next hook instead.

begindocument/end This hook is executed at the end of the `\document` code in other words at the beginning of the document body. The only command that follows it is `\ignorespaces`.

The generic hooks executed by `\begin` also exist, i.e., `env/document/before` and `env/document/begin`, but with this special environment it is better use the dedicated one-time hooks above.

2.8.3 Hooks provided by `\end{document}`

L^AT_EX 2_ε always provided `\AtEndDocument` to add code to the execution of `\end{document}` just in front of the code that is normally executed there. While this was a big improvement over the situation in L^AT_EX 2.09 it was not flexible enough for a number of use cases and so packages, such as `etoolbox`, `atveryend` and others patched `\enddocument` to add additional points where code could be hooked into.

Patching using packages is always problematical as leads to conflicts (code availability, ordering of patches, incompatible patches, etc.). For this reason a number of additional hooks have been added to the `\enddocument` code to allow packages to add code in various places in a controlled way without the need for overwriting or patching the core code.

Supported are now the following hooks (all of them one-time hooks):

enddocument The hook associated with `\AtEndDocument`. It is immediately called at the beginning of `\enddocument`.

When this hook is executed there may be still unprocessed material (e.g., floats on the deferlist) and the hook may add further material to be typeset. After it, `\clearpage` is called to ensure that all such material gets typeset. If there is nothing waiting the `\clearpage` has no effect.

enddocument/afterlastpage As the name indicates this hook should not receive code that generates material for further pages. It is the right place to do some final housekeeping and possibly write out some information to the `.aux` file (which is still open at this point to receive data). It is also the correct place to set up any testing code to be run when the `.aux` file is re-read in the next step.

After this hook has been executed the `.aux` file is closed for writing and then read back in to do some tests (e.g., looking for missing references or duplicated labels, etc.).

enddocument/afteraux At this point, the `.aux` file has been reprocessed and so this is a possible place for final checks and display of information to the user. However, for the latter you might prefer the next hook, so that your information is displayed after the (possibly longish) list of files if that got requested via `\listfiles`.

enddocument/info This hook is meant to receive code that write final information messages to the terminal. It follows immediately after the previous hook (so both could have been combined, but then packages adding further code would always need to also supply an explicit rule to specify where it should go.

This hook already contains some code added by the kernel (under the labels **kernel/filelist** and **kernel/warnings**), namely the list of files when `\listfiles` has been used and the warnings for duplicate labels, missing references, font substitutions etc.

enddocument/end Finally, this hook is executed just in front of the final call to `\@@end`.

There is also the hook **shipout/lastpage**. This hook is executed as part of the last `\shipout` in the document to allow package to add final `\special`'s to that page. Where this hook is executed in relation to those from the above list can vary from document to document. Furthermore to determine correctly which of the `\shipouts` is the last one, \LaTeX needs to be run several times, so initially it might get executed on the wrong page. See section 2.8.4 for where to find the details.

It is in also possible to use the generic **env/document/end** hook which is executed by `\end`, i.e., just in front of the first hook above. Note however that the other generic `\end` environment hook, i.e., **env/document/after** will never get executed, because by that time \LaTeX has finished the document processing.

2.8.4 Hooks provided `\shipout` operations

There are several hooks and mechanisms added to \LaTeX 's process of generating pages. These are documented in `ltshipout-doc.pdf` or with code in `ltshipout-code.pdf`.

2.8.5 Hooks provided by file loading operations

There are several hooks added to \LaTeX 's process of loading file via its high-level interfaces such as `\input`, `\include`, `\usepackage`, etc. These are documented in `ltfilehook-doc.pdf` or with code in `ltfilehook-code.pdf`.

2.8.6 Hooks provided in NFSS commands

In languages that need to support for more than one script in parallel (and thus several sets of fonts), e.g., Latin and Japanese fonts, NFSS font commands, such as `\sffamily`, need to switch both the Latin family to “Sans Serif” and in addition alter a second set of fonts.

To support this several NFSS have hooks in which such support can be added.

rmfamily After `\rmfamily` has done its initial checks and prepared a any font series update this hook is executed and only afterwards `\selectfont`.

sffamily Like the `rmfamily` hook but for the `\sffamily` command.

ttfamily Like the `rmfamily` hook but for the `\ttfamily` command.

normalfont The `\normalfont` command resets font encoding family series and shape to their document defaults. It then executes this hook and finally calls `\selectfont`.

expand@font@defaults The internal `\expand@font@defaults` command expands and saves the current defaults for the meta families (rm/sf/tt) and the meta series (bf/md). If the NFSS machinery has been augmented, e.g., for Chinese or Japanese fonts, then further defaults may need to be set at this point. This can be done in this hook which is executed at the end of this macro.

bfseries/defaults, bfseries If the `\bfdefault` was explicitly changed by the user its new value is used to set the bf series defaults for the meta families (rm/sf/tt) when `\bfseries` is called. In the `bfseries/defaults` hook further adjustments can be made in this case. This hook is only executed if such a change is detected. In contrast the `bfseries` hook is always executed just before `\selectfont` is called to change to the new series.

mdseries/defaults, mdseries These two hooks are like the previous ones but used in `\mdseries` command.

3 The Implementation

3.1 Loading further extensions

```
1 <@@=hook>
```

At the moment the whole module rolls back in one go, but if we make any modifications in later releases this will then need splitting.

```
2 <*2ekernel | latexrelease>
3 <latexrelease>\IncludeInRelease{2020/10/01}%
4 <latexrelease>                                {\NewHook}{The hook management}%
5 \ExplSyntaxOn
```

3.2 Debugging

```
\g__hook_debug_bool Holds the current debugging state.
6 \bool_new:N \g__hook_debug_bool
(End definition for \g__hook_debug_bool.)

\hook_debug_on: Turns debugging on and off by redefining \__hook_debug:n.
\hook_debug_off:
\__hook_debug:n
\__hook_debug_gset:
7 \cs_new_eq:NN \__hook_debug:n \use_none:n
8 \cs_new_protected:Npn \hook_debug_on:
9 {
10   \bool_gset_true:N \g__hook_debug_bool
11   \__hook_debug_gset:
12 }
13 \cs_new_protected:Npn \hook_debug_off:
14 {
15   \bool_gset_false:N \g__hook_debug_bool
16   \__hook_debug_gset:
17 }
18 \cs_new_protected:Npn \__hook_debug_gset:
19 {
20   \cs_gset_protected:Npx \__hook_debug:n ##1
21   { \bool_if:NT \g__hook_debug_bool {##1} }
22 }
```

(End definition for `\hook_debug_on:` and others. These functions are documented on page 11.)

3.3 Borrowing from internals of other kernel modules

`__hook_str_compare:nn` Private copy of `__str_if_eq:nn`
`23 \cs_new_eq:NN __hook_str_compare:nn __str_if_eq:nn`
(End definition for __hook_str_compare:nn.)

3.4 Declarations

`\l__hook_tmpa_bool` Scratch boolean used throughout the package.
`24 \bool_new:N \l__hook_tmpa_bool`
(End definition for \l__hook_tmpa_bool.)

`\l__hook_return_tl` Scratch variables used throughout the package.
`\l__hook_tmpa_tl` `25 \tl_new:N \l__hook_return_tl`
`\l__hook_tmpb_tl` `26 \tl_new:N \l__hook_tmpa_tl`
`27 \tl_new:N \l__hook_tmpb_tl`
(End definition for \l__hook_return_tl, \l__hook_tmpa_tl, and \l__hook_tmpb_tl.)

`\g__hook_all_seq` In a few places we need a list of all hook names ever defined so we keep track if them in this sequence.
`28 \seq_new:N \g__hook_all_seq`
(End definition for \g__hook_all_seq.)

`\g__hook_removal_list_prop` A token list to hold delayed removals.
`29 \tl_new:N \g__hook_removal_list_tl`
(End definition for \g__hook_removal_list_prop.)

`\l__hook_cur_hook_tl` Stores the name of the hook currently being sorted.
`30 \tl_new:N \l__hook_cur_hook_tl`
(End definition for \l__hook_cur_hook_tl.)

`\l__hook_work_prop` A property list holding a copy of the `\g__hook_⟨hook⟩_code_prop` of the hook being sorted to work on, so that changes don't act destructively on the hook data structure.
`31 \prop_new:N \l__hook_work_prop`
(End definition for \l__hook_work_prop.)

`\g__hook_hook_curr_name_tl` Default label used for hook commands, and a stack to keep track of packages within packages.
`\g__hook_name_stack_seq` `32 \tl_new:N \g__hook_hook_curr_name_tl`
`33 \seq_new:N \g__hook_name_stack_seq`
(End definition for \g__hook_hook_curr_name_tl and \g__hook_name_stack_seq.)

`__hook_tmp:w` Temporary macro for generic usage.
`34 \cs_new_eq:NN __hook_tmp:w ?`
(End definition for __hook_tmp:w.)

`\tl_gremove_once:Nx` Some variants of `expl3` functions.

FMi: should be moved to expl3

```
35 \cs_generate_variant:Nn \tl_gremove_once:Nn { Nx }
```

(End definition for `\tl_gremove_once:Nx`. This function is documented on page ??.)

`\s__hook_mark` Scan mark used for delimited arguments.

```
36 \scan_new:N \s__hook_mark
```

(End definition for `\s__hook_mark`.)

3.5 Providing new hooks

Hooks have a $\langle name \rangle$ and for each hook we have to provide a number of data structures. These are

`\g__hook_⟨name⟩_code_prop` A property list holding the code for the hook in separate chunks. The keys are by default the package names that add code to the hook, but it is possible for packages to define other keys.

`\g__hook_⟨name⟩_rule_⟨label1⟩|⟨label2⟩_tl` A token list holding the relation between $\langle label1 \rangle$ and $\langle label2 \rangle$ in the $\langle name \rangle$. The $\langle labels \rangle$ are lexically (reverse) sorted to ensure that two labels always point to the same token list. For global rules, the $\langle name \rangle$ is ??.

`\g__hook_⟨name⟩_code_tl` The code that is actually executed when the hook is called in the document is stored in this token list. It is constructed from the code chunks applying the information.

`\g__hook_⟨name⟩_reversed_tl` Some hooks are “reversed”. This token list stores a `-` for such hook so that it can be identified. The `-` character is used because $\langle reversed \rangle 1$ is $+1$ for normal hooks and -1 for reversed ones.

`\g__hook_⟨name⟩_code_next_tl` Finally there is extra code (normally empty) that is used on the next invocation of the hook (and then deleted). This can be used to define some special behavior for a single occasion from within the document. This token list is called `code_next` rather than `next_code` because otherwise a hook called $\langle name \rangle_next$ would have its code-token list named `\g__hook_⟨name⟩_code_next_tl`, which would clash with the next code-token list of a hook called $\langle name \rangle$.

(End definition for `\g__hook_..._code_prop`, `\g__hook_..._code_tl`, and `\g__hook_..._code_next_tl`.)

`\hook_new:n` The `\hook_new:n` declaration declare a new hook and expects the hook $\langle name \rangle$ as its argument, e.g., `begindocument`.

```
37 \cs_new_protected:Npn \hook_new:n #1
38 {
39   \exp_args:Nx \__hook_new:n
40   { \__hook_parse_label_default:nn {#1} { top-level } }
41 }
42 \cs_new_protected:Npn \__hook_new:n #1 {
```

We check for one of the internal data structures and if it already exists we complain.

```
43   \hook_if_exist:nTF {#1}
44   { \msg_error:nnn { hooks } { exists } {#1} }
```

Otherwise we add the hook name to the list of all hooks and allocate the necessary data structures for the new hook.

```
45 { \seq_gput_right:Nn \g__hook_all_seq {#1}
```

This is only used by the actual code of the current hook, so declare it normally:

```
46 \tl_new:c { g__hook_#1_code_tl }
```

Now ensure that the base data structure for the hook exists:

```
47 \__hook_declare:n {#1}
```

The `\g__hook_⟨hook⟩_labels_clist` holds the sorted list of labels (once it got sorted). This is used only for debugging.

```
48 \clist_new:c {g__hook_#1_labels_clist}
```

Some hooks should reverse the default order of code chunks. To signal this we have a token list which is empty for normal hooks and contains a `-` for reversed hooks.

```
49 \tl_new:c { g__hook_#1_reversed_tl }
```

The above is all in L3 convention, but we also provide an interface to legacy L^AT_EX 2_ε hooks of the form `\@...hook`, e.g., `\@begindocumenthook`. There have been a few of them and they have been added to using `\g@addto@macro`. If there exists such a macro matching the name of the new hook, i.e., `\@⟨hook-name⟩hook` and it is not empty then we add its contents as a code chunk under the label `legacy`.

Warning: this support will vanish in future releases!

```
50 \__hook_include_legacy_code_chunk:n {#1}
51 }
52 }
```

(End definition for `\hook_new:n`. This function is documented on page 9.)

`__hook_declare:n` This function declares the basic data structures for a hook without actually declaring the hook itself. This is needed to allow adding to undeclared hooks. Here it is unnecessary to check whether both variables exist, since both are declared at the same time (either both exist, or neither).

```
53 \cs_new_protected:Npn \__hook_declare:n #1
54 {
55   \__hook_if_exist:nF {#1}
56   {
57     \prop_new:c { g__hook_#1_code_prop }
58     \tl_new:c { g__hook_#1_code_next_tl }
59   }
60 }
```

(End definition for `__hook_declare:n`.)

`\hook_new_reversed:n` Declare a new hook. The default ordering of code chunks is reversed, signaled by setting the token list to a minus sign.

```
61 \cs_new_protected:Npn \hook_new_reversed:n #1 {
62   \hook_new:n {#1}
```

If the hook already exists the above will generate an error message, so the next line should be executed (but it is — too bad).

```
63 \tl_gset:cn { g__hook_#1_reversed_tl } { - }
64 }
```

(End definition for `\hook_new_reversed:n`. This function is documented on page 9.)

`\hook_new_pair:nn` A shorthand for declaring a normal and a (matching) reversed hook in one go.

```

65 \cs_new_protected:Npn \hook_new_pair:nn #1#2 {
66   \hook_new:n {#1} \hook_new_reversed:n {#2}
67 }

```

(End definition for `\hook_new_pair:nn`. This function is documented on page 9.)

`__hook_include_legacy_code_chunk:n` The L^AT_EX legacy concept for hooks uses with hooks the following naming scheme in the code: `\@...hook`.

If this macro is not empty we add it under the label `legacy` to the current hook and then empty it globally. This way packages or classes directly manipulating commands such as `\@begindocumenthook` still get their hook data added.

Warning: this support will vanish in future releases!

```

68 \cs_new_protected:Npn \__hook_include_legacy_code_chunk:n #1
69   {

```

If the `expl3` code is run with checking on then assigning or using non L3 names such as `\@enddocumenthook` with `expl3` functions will trigger warnings so we run this code with debugging explicitly suspended.

```

70   \debug_suspend:

```

If the macro doesn't exist (which is the usual case) then nothing needs to be done.

```

71   \tl_if_exist:cT { @#1hook }

```

Of course if the legacy hook exists but is empty, there is no need to add anything under `legacy` the legacy label.

```

72   {
73     \tl_if_empty:cF { @#1hook }
74     {
75       \exp_args:Nnnv \__hook_hook_gput_code_do:nnn {#1}
76       { legacy } { @#1hook }

```

Once added to the hook, we need to clear it otherwise it might get added again later if the hook data gets updated.

```

77       \tl_gclear:c { @#1hook }
78     }
79   }
80   \debug_resume:
81 }

```

(End definition for `__hook_include_legacy_code_chunk:n`.)

3.6 Parsing a label

`__hook_parse_label_default:nn` This macro checks if a label was given (not `\c_novalue_tl`), and if so, tries to parse the label looking for a leading `.` to replace for `\@currname`. Otherwise `__hook_currname_or_default:n` is used to pick `\@currname` or the fallback value.

`__hook_parse_label_default:Vn`

```

82 \cs_new:Npn \__hook_parse_label_default:nn #1 #2
83   {
84     \tl_if_novalue:nTF {#1}
85     { \__hook_currname_or_default:n {#2} }

```

```

86     { \tl_trim_spaces_apply:nN {#1} \__hook_parse_dot_label:nn {#2} }
87   }
88   \cs_generate_variant:Nn \__hook_parse_label_default:nn { V }

```

(End definition for __hook_parse_label_default:nn.)

__hook_parse_dot_label:nn Start by checking if the label is empty, which raises an error, and uses the fallback value.
 __hook_parse_dot_label:nw If not, split the label at a ./, if any, and check if no tokens are before the ./, or if the
 __hook_parse_dot_label_cleanup:w only character is a .. If these requirements are fulfilled, the leading . is replaced with
 __hook_parse_dot_label_aux:nw __hook_currname_or_default:n. Otherwise the label is returned unchanged.

```

89   \cs_new:Npn \__hook_parse_dot_label:nn #1 #2
90   {
91     \tl_if_empty:nTF {#1}
92     {
93       \msg_expandable_error:nnn { hooks } { empty-label } {#2}
94       #2
95     }
96     {
97       \str_if_eq:nnTF {#1} { . }
98       { \__hook_currname_or_default:n {#1} }
99       { \__hook_parse_dot_label:nw {#2} #1 ./ \s__hook_mark }
100    }
101  }
102  \cs_new:Npn \__hook_parse_dot_label:nw #1 #2 ./ #3 \s__hook_mark
103  {
104    \tl_if_empty:nTF {#2}
105    { \__hook_parse_dot_label_aux:nw {#1} #3 \s__hook_mark }
106    {
107      \tl_if_empty:nTF {#3}
108      {#2}
109      { \__hook_parse_dot_label_cleanup:w #2 ./ #3 \s__hook_mark }
110    }
111  }
112  \cs_new:Npn \__hook_parse_dot_label_cleanup:w #1 ./ \s__hook_mark {#1}
113  \cs_new:Npn \__hook_parse_dot_label_aux:nw #1 #2 ./ \s__hook_mark
114  { \__hook_currname_or_default:n {#1} / #2 }

```

(End definition for __hook_parse_dot_label:nn and others.)

__hook_currname_or_default:n Uses \g__hook_hook_curr_name_tl if it is set, otherwise tries \@currname. If neither is set, uses the fallback value #1 (usually top-level).

```

115  \cs_new:Npn \__hook_currname_or_default:n #1
116  {
117    \tl_if_empty:nTF \g__hook_hook_curr_name_tl
118    {
119      \tl_if_empty:nTF \@currname
120      {#1}
121      { \@currname }
122    }
123    { \g__hook_hook_curr_name_tl }
124  }

```

(End definition for __hook_currname_or_default:n.)

`\hook_gput_code:nnn` With `\hook_gput_code:nnn{<hook>}{<label>}{<code>}` a chunk of `<code>` is added to an existing `<hook>` labeled with `<label>`.

```

\__hook_gput_code:nnn
\__hook_gput_code:nxv
\__hook_hook_gput_code_do:nnn
125 \cs_new_protected:Npn \hook_gput_code:nnn #1 #2
126 {
127   \exp_args:Nxx \__hook_gput_code:nnn
128     { \__hook_parse_label_default:nn {#1} { top-level } }
129     { \__hook_parse_label_default:nn {#2} { top-level } }
130 }
131 \cs_new_protected:Npn \__hook_gput_code:nnn #1 #2 #3
132 {

```

First check if the current `<hook>/<label>` pair was marked for removal, in which case `__hook_unmark_removal:nn` is used to remove that mark (once). This may happen when a package removes code from another package which was not yet loaded: the removal order is stored, and at this stage it is executed by not adding to the hook.

```

133   \__hook_if_marked_removal:nnTF {#1} {#2}
134   { \__hook_unmark_removal:nn {#1} {#2} }
135   {

```

If no removal is queued, we are free to add. Start by checking if the hook exists.

```

136     \hook_if_exist:nTF {#1}

```

If so we simply add (or append) the new code to the property list holding different chunks for the hook. At `\begin{document}` this is then sorted into a token list for fast execution.

```

137     {
138       \__hook_hook_gput_code_do:nnn {#1} {#2} {#3}

```

However, if there is an update within the document we need to alter this execution code which is done by `__hook_update_hook_code:n`. In the preamble this does nothing.

```

139       \__hook_update_hook_code:n {#1}
140     }

```

If the hook does not exist, however, before giving up try to declare it as a generic hook, if its name matches one of the valid patterns.

```

141       { \__hook_try_declaring_generic_hook:nnn {#1} {#2} {#3} }
142     }
143   }
144 \cs_generate_variant:Nn \__hook_gput_code:nnn { nxv }

```

This macro will unconditionally add a chunk of code to the given hook.

```

145 \cs_new_protected:Npn \__hook_hook_gput_code_do:nnn #1 #2 #3
146 {

```

However, first some debugging info if debugging is enabled:

```

147   \__hook_debug:n{\iow_term:x{****~ Add~ to~
148     \hook_if_exist:nF {#1} { undeclared~ }
149     hook~ #1~ (#2)
150     \on@line\space <-- \tl_to_str:n{#3}} }

```

Then try to get the code chunk labeled #2 from the hook. If there's code already there, then append #3 to that, otherwise just put #3.

```

151   \prop_get:cnNTF { g__hook_#1_code_prop } {#2} \l__hook_return_tl
152   {
153     \prop_gput:cno { g__hook_#1_code_prop } {#2}
154     { \l__hook_return_tl #3 }
155   }

```

```

156     { \prop_gput:cnn { g__hook_#1_code_prop } {#2} {#3} }
157   }

```

(End definition for `\hook_gput_code:nnn`, `__hook_gput_code:nnn`, and `__hook_hook_gput_code_do:nnn`. This function is documented on page 10.)

`__hook_gput_undeclared_hook:nnn`

Often it may happen that a package *A* defines a hook `foo`, but package *B*, that adds code to that hook, is loaded before *A*. In such case we need to add code to the hook before its declared.

```

158 \cs_new_protected:Npn \__hook_gput_undeclared_hook:nnn #1 #2 #3
159 {
160   \__hook_declare:n {#1}
161   \__hook_hook_gput_code_do:nnn {#1} {#2} {#3}
162 }

```

(End definition for `__hook_gput_undeclared_hook:nnn`.)

`__hook_try_declaring_generic_hook:nnn`

These entry-level macros just pass the arguments along to the common `__hook_try_declaring_generic_hook:nNNnn` with the right functions to execute when some action is to be taken.

The wrapper `__hook_try_declaring_generic_hook:nnn` then defers `\hook_gput_code:nnn` if the generic hook was declared, or to `__hook_gput_undeclared_hook:nnn` otherwise (the hook was tested for existence before, so at this point if it isn't generic, it doesn't exist).

The wrapper `__hook_try_declaring_generic_next_hook:nn` for next-execution hooks does the same: it defers the code to `\hook_gput_next_code:nn` if the generic hook was declared, or to `__hook_gput_next_do:nn` otherwise.

```

163 \cs_new_protected:Npn \__hook_try_declaring_generic_hook:nnn #1
164 {
165   \__hook_try_declaring_generic_hook:nNNnn {#1}
166   \hook_gput_code:nnn \__hook_gput_undeclared_hook:nnn
167 }
168 \cs_new_protected:Npn \__hook_try_declaring_generic_next_hook:nn #1
169 {
170   \__hook_try_declaring_generic_hook:nNNnn {#1}
171   \hook_gput_next_code:nn \__hook_gput_next_do:nn
172 }

```

`__hook_try_declaring_generic_hook:nNNnn` now splits the hook name at the first / (if any) and first checks if it is a file-specific hook (they require some normalization) using `__hook_if_file_hook:wTF`. If not then check it is one of a predefined set for generic names. We also split off the second component to see if we have to make a reversed hook. In either case the function returns *⟨true⟩* for a generic hook and *⟨false⟩* in other cases.

```

173 \cs_new_protected:Npn \__hook_try_declaring_generic_hook:nNNnn #1
174 {
175   \__hook_if_file_hook:wTF #1 / / \s__hook_mark
176   {
177     \exp_args:Ne \__hook_try_declaring_generic_hook_split:nNNnn
178     { \exp_args:Ne \__hook_file_hook_normalize:n {#1} }
179   }
180   { \__hook_try_declaring_generic_hook_split:nNNnn {#1} }
181 }
182 \cs_new_protected:Npn \__hook_try_declaring_generic_hook_split:nNNnn #1 #2 #3

```

```

183 {
184   \__hook_try_declaring_generic_hook:wnTF #1 / / / \scan_stop: {#1}
185   { #2 }
186   { #3 } {#1}
187 }
188 \prg_new_protected_conditional:Npnn \__hook_try_declaring_generic_hook:wn
189   #1 / #2 / #3 / #4 \scan_stop: #5 { TF }
190 {
191   \tl_if_empty:nTF {#2}
192   { \prg_return_false: }
193   {
194     \prop_if_in:NnTF \c__hook_generics_prop {#1}
195     {
196       \hook_if_exist:nF {#5} { \hook_new:n {#5} }

```

After having declared the hook we check the second component (for file hooks) or the third component for environment hooks) and if it is on the list of components for which we should have declared a reversed hook we alter the hook data structure accordingly.

```

197       \prop_if_in:NnTF \c__hook_generics_reversed_ii_prop {#2}
198       { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
199       {
200         \prop_if_in:NnTF \c__hook_generics_reversed_iii_prop {#3}
201         { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
202       }

```

Now that we know that the hook is declared we can add the code to it.

```

203       \prg_return_true:
204     }
205     { \prg_return_false: }
206   }
207 }

```

(End definition for __hook_try_declaring_generic_hook:nnn and others.)

__hook_if_file_hook_p:w __hook_if_file_hook:wTF checks if the argument is a valid file-specific hook (not, for example, file/before, but file/before/foo.tex). If it is a file-specific hook, then it executes the *⟨true⟩* branch, otherwise *⟨false⟩*.

A file-specific hook is file/⟨position⟩/⟨name⟩. If any of these parts don't exist, it is a general file hook or not a file hook at all, so the conditional evaluates to *⟨false⟩*. Otherwise, it checks that the first part is file and that the *⟨position⟩* is in the \c__hook_generics_file_prop.

A property list is used here to avoid having to worry with catcodes, because expl3's file name parsing turns all characters into catcode-12 tokens, which might differ from hand-input letters.

```

208 \prg_new_conditional:Npnn \__hook_if_file_hook:w
209   #1 / #2 / #3 \s__hook_mark { TF }
210 {
211   \str_if_eq:nnTF {#1} { file }
212   {
213     \bool_lazy_or:nnTF
214       { \tl_if_empty_p:n {#3} }
215       { \str_if_eq_p:nn {#3} { / } }
216     { \prg_return_false: }
217   {

```

```

218         \prop_if_in:NnTF \c__hook_generics_file_prop {#2}
219         { \prg_return_true: }
220         { \prg_return_false: }
221     }
222 }
223 { \prg_return_false: }
224 }

```

(End definition for __hook_if_file_hook:wTF.)

__hook_file_hook_normalize:n When a file-specific hook is found, before being declared it is lightly normalized by __hook_file_hook_normalize:n. The current implementation just replaces two consecutive slashes (//) by a single one, to cope with simple cases where the user did something like \def\input@path{./mypath/}, in which case a hook would have to be \AddToHook{file/after/./mypath//file.tex}.

```

225 \cs_new:Npn \__hook_file_hook_normalize:n #1
226 { \__hook_strip_double_slash:n {#1} }
227 \cs_new:Npn \__hook_strip_double_slash:n #1
228 { \__hook_strip_double_slash:w #1 // \s__hook_mark }
229 \cs_new:Npn \__hook_strip_double_slash:w #1 // #2 \s__hook_mark
230 {
231     \tl_if_empty:NTF {#2}
232     {#1}
233     { \__hook_strip_double_slash:w #1 / #2 \s__hook_mark }
234 }

```

(End definition for __hook_file_hook_normalize:n, __hook_strip_double_slash:n, and __hook_strip_double_slash:w.)

\c__hook_generics_prop Property list holding the generic names. We don't provide any user interface to this as this is meant to be static.

env The generic hooks used in \begin and \end.

file The generic hooks used when loading a file

```

235 \prop_const_from_keyval:Nn \c__hook_generics_prop
236 {env=,file=,package=,class=,include=}

```

(End definition for \c__hook_generics_prop.)

\c__hook_generics_reversed_ii_prop Some of the generic hooks are supposed to use reverse ordering, these are the following (only the second or third sub-component is checked):

```

\c__hook_generics_reversed_iii_prop
\c__hook_generics_file_prop
237 \prop_const_from_keyval:Nn \c__hook_generics_reversed_ii_prop {after=,end=}
238 \prop_const_from_keyval:Nn \c__hook_generics_reversed_iii_prop {after=}
239 \prop_const_from_keyval:Nn \c__hook_generics_file_prop {before=,after=}

```

(End definition for \c__hook_generics_reversed_ii_prop, \c__hook_generics_reversed_iii_prop, and \c__hook_generics_file_prop.)

\hook_gremove_code:nn With \hook_gremove_code:nn{<hook>}{<label>} any code for <hook> stored under <label> is removed.

```

240 \cs_new_protected:Npn \hook_gremove_code:nn #1 #2
241 {
242     \exp_args:Nxx \__hook_gremove_code:nn
243     { \__hook_parse_label_default:nn {#1} { top-level } }

```

```

244     { \__hook_parse_label_default:nn {#2} { top-level } }
245   }
246 \cs_new_protected:Npn \__hook_gremove_code:nn #1 #2
247   {

```

First check that the hook code pool exists. `\hook_if_exist:nTF` isn't used here because it should be possible to remove code from a hook before its defined (see section 2.1.5).

```

248     \__hook_if_exist:nTF {#1}

```

Then remove the chunk and run `__hook_update_hook_code:n` so that the execution token list reflects the change if we are after `\begin{document}`.

```

249     {
250       \str_if_eq:nnTF {#2} {*}
251       { \prop_gclear:c { g__hook_#1_code_prop } }
252       {

```

Check if the label being removed exists in the code pool. If it does, just call `__hook_gremove_code_do:nn` to do the removal, otherwise mark it to be removed.

```

253         \prop_get:cnNTF { g__hook_#1_code_prop } {#2} \l__hook_return_tl
254         { \__hook_gremove_code_do:nn }
255         { \__hook_mark_removal:nn
256           {#1} {#2}
257       }

```

Finally update the code, if the hook exists.

```

258     \hook_if_exist:nT {#1}
259     { \__hook_update_hook_code:n {#1} }
260   }

```

If the code pool for this hook doesn't exist it means that nothing tried to add to it before, so we just queue this removal order for later.

```

261     { \__hook_mark_removal:nn {#1} {#2} }
262   }

```

```

263 \cs_new_protected:Npn \__hook_gremove_code_do:nn #1 #2
264   { \prop_gremove:cn { g__hook_#1_code_prop } {#2} }

```

(End definition for `\hook_gremove_code:nn`, `__hook_gremove_code:nn`, and `__hook_gremove_code_do:nn`. This function is documented on page 10.)

`__hook_mark_removal:nn` Marks $\langle label \rangle$ ($\#2$) to be removed from $\langle hook \rangle$ ($\#1$). The number of removals should be fairly small, and `\tl_gremove_once:Nx` is fairly efficient even for longer token lists, so we use a single global token list, rather than one for each hook.

```

265 \cs_new_protected:Npn \__hook_mark_removal:nn #1 #2
266   {
267     \tl_gput_right:Nx \g__hook_removal_list_tl
268     { \__hook_removal_tl:nn {#1} {#2} }
269   }

```

(End definition for `__hook_mark_removal:nn`.)

`__hook_unmark_removal:nn` Unmarks $\langle label \rangle$ ($\#2$) to be removed from $\langle hook \rangle$ ($\#1$). `\tl_gremove_once:Nx` is used rather than `\tl_gremove_all:Nx` so that two additions are needed to cancel two marked removals, rather than only one.

```

270 \cs_new_protected:Npn \__hook_unmark_removal:nn #1 #2
271 {
272   \tl_gremove_once:Nx \g__hook_removal_list_tl
273   { \__hook_removal_tl:nn {#1} {#2} }
274 }

```

(End definition for `__hook_unmark_removal:nn`.)

`__hook_if_marked_removal:nnTF` Checks if the `\g__hook_removal_list_tl` contains the current $\langle label \rangle$ ($\#2$) and $\langle hook \rangle$ ($\#1$).

```

275 \prg_new_protected_conditional:Npnn \__hook_if_marked_removal:nn #1 #2 { TF }
276 {
277   \exp_args:NNx \tl_if_in:NnTF \g__hook_removal_list_tl
278   { \__hook_removal_tl:nn {#1} {#2} }
279   { \prg_return_true: } { \prg_return_false: }
280 }

```

(End definition for `__hook_if_marked_removal:nnTF`.)

`__hook_removal_tl:nn` Builds a token list with $\#1$ and $\#2$ which can only be matched by $\#1$ and $\#2$. The $\&_4$ anchors a removal, so that $\#1$ can't be mistaken by $\#2$ and vice versa, and the two $\$3$ delimit the two arguments

```

281 \cs_new:Npn \__hook_removal_tl:nn #1 #2
282 { & \tl_to_str:n {#2} $ \tl_to_str:n {#1} $ }

```

(End definition for `__hook_removal_tl:nn`.)

`\g__hook_??_code_prop` Initially these variables simply used an empty “label” name (not two question marks).
`\g__hook_??_code_tl` This was a bit unfortunate, because then `l3doc` complains about `__` in the middle of a command name when trying to typeset the documentation. However using a “normal” name such as `default` has the disadvantage of that being not really distinguishable from a real hook name. I now have settled for `??` which needs some gymnastics to get it into the csname, but since this is used a lot things should be fast, so this is not done with `c` expansion in the code later on.

`\g__hook_??_code_tl` isn't used, but it has to be defined to trick the code into thinking that `??` is actually a hook.

```

283 \prop_new:c {g__hook_??_code_prop}
284 \prop_new:c {g__hook_??_code_tl}

```

Default rules are always given in normal ordering (never in reversed ordering). If such a rule is applied to a reversed hook it behaves as if the rule is reversed (e.g., `after` becomes `before`) because those rules are applied first and then the order is reversed.

```

285 \tl_new:c {g__hook_??_reversed_tl}

```

(End definition for `\g__hook_??_code_prop`, `\g__hook_??_code_tl`, and `\g__hook_??_reversed_tl`.)

3.7 Setting rules for hooks code

`\hook_gset_rule:nnnn`
`__hook_gset_rule:nnnn`

FMi: needs docu correction given new implementation

With `\hook_gset_rule:nnnn{<hook>}{<label1>}{<relation>}{<label2>}` a relation is defined between the two code labels for the given `<hook>`. The special hook `??` stands for any hook describing a default rule.

```

286 \cs_new_protected:Npn \hook_gset_rule:nnnn #1#2#3#4
287 {
288   \use:x
289   {
290     \__hook_gset_rule:nnnn
291     { \__hook_parse_label_default:nn {#1} { top-level } }
292     { \__hook_parse_label_default:nn {#2} { top-level } }
293     {#3}
294     { \__hook_parse_label_default:nn {#4} { top-level } }
295   }
296 }
297 \cs_new_protected:Npn \__hook_gset_rule:nnnn #1#2#3#4
298 {

```

First we ensure the basic data structure of the hook exists:

```

299   \__hook_declare:n {#1}

```

Then we clear any previous relationship between both labels.

```

300   \__hook_rule_gclear:nnn {#1} {#2} {#4}

```

Then we call the function to handle the given rule. Throw an error if the rule is invalid.

```

301   \debug_suspend:
302   \cs_if_exist_use:cTF { \__hook_rule_#3_gset:nnn }
303   {
304     {#1} {#2} {#4}
305     \__hook_update_hook_code:n {#1}
306   }
307   { \msg_error:nnnnnn { hooks } { unknown-rule }
308     {#1} {#2} {#3} {#4} }
309   \debug_resume:
310 }

```

(End definition for `\hook_gset_rule:nnnn` and `__hook_gset_rule:nnnn`. This function is documented on page 10.)

`__hook_rule_before_gset:nnn`
`__hook_rule_after_gset:nnn`
`__hook_rule_<_gset:nnn`
`__hook_rule_>_gset:nnn`

Then we add the new rule. We need to normalize the rules here to allow for faster processing later. Given a pair of labels l_A and l_B , the rule $l_A > l_B$ is the same as $l_B < l_A$ only presented differently. But by normalizing the forms of the rule to a single representation, say, $l_B < l_A$, reduces the time spent looking for the rules later considerably.

Here we do that normalization by using `\(pdf)strcmp` to lexically sort labels l_A and l_B to a fixed order. This order is then enforced every time these two labels are used together.

Here we use `__hook_label_pair:nn {<hook>}{<label1>}{<label2>}` to build a string $l_B|l_A$ with a fixed order, and use `__hook_label_ordered:nnTF` to apply the correct rule to the pair of labels, depending if it was sorted or not.

```

311 \cs_new_protected:Npn \__hook_rule_before_gset:nnn #1#2#3
312 {
313   \tl_gset:cx { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _t1 }

```

```

314     { \_hook_label_ordered:nnTF {#2} {#3} { < } { > } }
315   }
316 \cs_new_eq:cN { \_hook_rule_<_gset:nnn } \_hook_rule_before_gset:nnn
317 \cs_new_protected:Npn \_hook_rule_after_gset:nnn #1#2#3
318 {
319   \tl_gset:cx { g\_hook\_#1\_rule\_ \_hook_label_pair:nn {#3} {#2} \_tl }
320   { \_hook_label_ordered:nnTF {#3} {#2} { < } { > } }
321 }
322 \cs_new_eq:cN { \_hook_rule_>_gset:nnn } \_hook_rule_after_gset:nnn

```

(End definition for _hook_rule_before_gset:nnn and others.)

_hook_rule_voids_gset:nnn This rule removes (clears, actually) the code from label #3 if label #2 is in the hook #1.

```

323 \cs_new_protected:Npn \_hook_rule_voids_gset:nnn #1#2#3
324 {
325   \tl_gset:cx { g\_hook\_#1\_rule\_ \_hook_label_pair:nn {#2} {#3} \_tl }
326   { \_hook_label_ordered:nnTF {#2} {#3} { -> } { <- } }
327 }

```

(End definition for _hook_rule_voids_gset:nnn.)

_hook_rule_incompatible-error_gset:nnn These relations make an error/warning if labels #2 and #3 appear together in hook #1.

```

328 \cs_new_protected:cpn { \_hook_rule_incompatible-error_gset:nnn } #1#2#3
329 { \tl_gset:cn { g\_hook\_#1\_rule\_ \_hook_label_pair:nn {#2} {#3} \_tl } { xE } }
330 \cs_new_protected:cpn { \_hook_rule_incompatible-warning_gset:nnn } #1#2#3
331 { \tl_gset:cn { g\_hook\_#1\_rule\_ \_hook_label_pair:nn {#2} {#3} \_tl } { xW } }

```

(End definition for _hook_rule_incompatible-error_gset:nnn and _hook_rule_incompatible-warning_gset:nnn.)

_hook_rule_unrelated_gset:nnn Undo a setting. _hook_rule_unrelated_gset:nnn doesn't need to do anything, since
_hook_rule_gclear:nnn we use _hook_rule_gclear:nnn before setting any rule.

```

332 \cs_new_protected:Npn \_hook_rule_unrelated_gset:nnn #1#2#3 { }
333 \cs_new_protected:Npn \_hook_rule_gclear:nnn #1#2#3
334 { \cs_undefine:c { g\_hook\_#1\_rule\_ \_hook_label_pair:nn {#2} {#3} \_tl } }

```

(End definition for _hook_rule_unrelated_gset:nnn and _hook_rule_gclear:nnn.)

_hook_label_pair:nn Ensure that the lexically greater label comes first.

```

335 \cs_new:Npn \_hook_label_pair:nn #1#2
336 {
337   \if_case:w \_hook_str_compare:nn {#1} {#2} \exp_stop_f:
338     #1 | #1 % 0
339   \or:   #1 | #2 % +1
340   \else: #2 | #1 % -1
341   \fi:
342 }

```

(End definition for _hook_label_pair:nn.)

`__hook_label_ordered_p:nn` Check that labels #1 and #2 are in the correct order (as returned by `__hook_label_-pair:nn`) and if so return true, else return false.

```

343 \prg_new_conditional:Npnn \__hook_label_ordered:nn #1#2 { TF }
344 {
345   \if_int_compare:w \__hook_str_compare:nn {#1} {#2} > 0 \exp_stop_f:
346   \prg_return_true:
347   \else
348   \prg_return_false:
349   \fi:
350 }

```

(End definition for `__hook_label_ordered:nnTF`.)

`__hook_if_label_case:nnnnn` To avoid doing the string comparison twice in `__hook_initialize_single:NNNn` (once with `\str_if_eq:nn` and again with `__hook_label_ordered:nn`), we use a three-way branching macro that will compare #1 and #2 and expand to `\use_i:nnn` if they are equal, `\use_ii:nn` if #1 is lexically greater, and `\use_iii:nn` otherwise.

```

351 \cs_new:Npn \__hook_if_label_case:nnnnn #1#2
352 {
353   \cs:w use_
354   \if_case:w \__hook_str_compare:nn {#1} {#2}
355   i \or: ii \else: iii \fi: :nnn
356   \cs_end:
357 }

```

(End definition for `__hook_if_label_case:nnnnn`.)

`__hook_update_hook_code:n` Before `\begin{document}` this does nothing, in the body it reinitializes the hook code using the altered data.

```

358 \cs_new_eq:NN \__hook_update_hook_code:n \use_none:n

```

(End definition for `__hook_update_hook_code:n`.)

`__hook_initialize_all:` Initialize all known hooks (at `\begin{document}`), i.e., update the fast execution token lists to hold the necessary code in the right order.

```

359 \cs_new_protected:Npn \__hook_initialize_all: {

```

First we change `__hook_update_hook_code:n` which so far was a no-op to now initialize one hook. This way any later updates to the hook will run that code and also update the execution token list.

```

360   \cs_gset_eq:NN \__hook_update_hook_code:n \__hook_initialize_hook_code:n

```

Now we loop over all hooks that have been defined and update each of them.

```

361   \__hook_debug:n { \prop_gc_clear:N \g__hook_used_prop }
362   \seq_map_inline:Nn \g__hook_all_seq
363   {
364     \__hook_update_hook_code:n {##1}
365   }

```

If we are debugging we show results hook by hook for all hooks that have data.

```

366   \__hook_debug:n
367   { \iow_term:x{^^JAll~ initialized~ (non-empty)~ hooks:}
368     \prop_map_inline:Nn \g__hook_used_prop
369     { \iow_term:x{^^J~ ##1~ ->~
370       \exp_not:v {g__hook_##1_code_tl}~ }
371     }
372 }

```

After all hooks are initialized we change the “use” to just call the hook code and not initialize it (as it was done in the preamble.

```

373 \cs_gset_eq:NN \hook_use:n \__hook_use_initialized:n
374 \cs_gset_eq:NN \__hook_preamble_hook:n \use_none:n
375 }

```

(End definition for __hook_initialize_all:.)

__hook_initialize_hook_code:n Initializing or reinitializing the fast execution hook code. In the preamble this is selectively done in case a hook gets used and at \begin{document} this is done for all hooks and afterwards only if the hook code changes.

```

376 \cs_new_protected:Npn \__hook_initialize_hook_code:n #1 {
377   \__hook_debug:n{ \iow_term:x{^^JUpdate~ code~ for~ hook~
378                   ' #1' \on@line :^^J} }

```

This does the sorting and the updates. First thing we do is to check if a legacy hook macro exists and if so we add it to the hook under the label `legacy`. This might make the hook non-empty so we have to do this before the then following test.

```

379 \__hook_include_legacy_code_chunk:n {#1}

```

If there aren't any code chunks for the current hook, there is no point in even starting the sorting routine so we make a quick test for that and in that case just update `\g__hook_<hook>_code_tl` to hold the next code. If there are code chunks we call `__hook_initialize_single:NNNn` and pass to it ready made csnames as they are needed several times inside. This way we save a bit on processing time if we do that up front.

```

380 \hook_if_exist:nT {#1}
381 {
382   \prop_if_empty:cTF {g__hook_#1_code_prop}
383   { \tl_gset:co {g__hook_#1_code_tl}
384     {\cs:w g__hook_#1_code_next_tl \cs_end: } }
385   {

```

By default the algorithm sorts the code chunks and then saves the result in a token list for fast execution by adding the code one after another using `\tl_gput_right:NV`. When we sort code for a reversed hook, all we have to do is to add the code chunks in the opposite order into the token list. So all we have to do in preparation is to change two definitions used later on.

```

386 \__hook_if_reversed:nTF {#1}
387 { \cs_set_eq:NN \__hook_tl_gput:NV \tl_gput_left:NV
388   \cs_set_eq:NN \__hook_clist_gput:NV \clist_gput_left:NV }
389 { \cs_set_eq:NN \__hook_tl_gput:NV \tl_gput_right:NV
390   \cs_set_eq:NN \__hook_clist_gput:NV \clist_gput_right:NV }

```

When sorting, some relations (namely voids) need to act destructively on the code property lists to remove code that shouldn't appear in the sorted hook token list, so we temporarily save the old code property list so that it can be restored later.

```

391 \prop_set_eq:Nc \l__hook_work_prop { g__hook_#1_code_prop }
392 \__hook_initialize_single:cccn
393 { g__hook_#1_code_tl } { g__hook_#1_code_next_tl }
394 { g__hook_#1_labels_clist } {#1}

```

For debug display we want to keep track of those hooks that actually got code added to them, so we record that in plist. We use a plist to ensure that we record each hook name only once, i.e., we are only interested in storing the keys and the value is arbitrary.

```

395         \__hook_debug:n{ \exp_args:NNx \prop_gput:Nnn
396                               \g__hook_used_prop {#1}{ } }
397     }
398 }
399 }

(End definition for \__hook_initialize_hook_code:n.)

\g__hook_used_prop All hooks that receive code (for use in debugging display).
400 \prop_new:N\g__hook_used_prop

(End definition for \g__hook_used_prop.)

\__hook_tl_csname:n It is faster to pass a single token and expand it when necessary than to pass a bunch of
\__hook_seq_csname:n character tokens around.

FMi: note to myself: verify

401 \cs_new:Npn \__hook_tl_csname:n #1 { l__hook_label_#1_tl }
402 \cs_new:Npn \__hook_seq_csname:n #1 { l__hook_label_#1_seq }

(End definition for \__hook_tl_csname:n and \__hook_seq_csname:n.)

\l__hook_labels_seq For the sorting I am basically implementing Knuth's algorithm for topological sorting as
\l__hook_labels_int given in TAOCP volume 1 pages 263–266. For this algorithm we need a number of local
\l__hook_front_tl variables:
\l__hook_rear_tl
\l__hook_label_0_tl


- List of labels used in the current hook to label code chunks:


403 \seq_new:N \l__hook_labels_seq



- Number of labels used in the current hook. In Knuth's algorithm this is called  $N$ :


404 \int_new:N \l__hook_labels_int



- The sorted code list to be build is managed using two pointers one to the front of the queue and one to the rear. We model this using token list pointers. Knuth calls them  $F$  and  $R$ :


405 \tl_new:N \l__hook_front_tl
406 \tl_new:N \l__hook_rear_tl



- The data for the start of the queue is kept in this token list, it corresponds to what Don calls QLINK[0] but since we aren't manipulating individual words in memory it is slightly differently done:


407 \tl_new:c { \__hook_tl_csname:n { 0 } }

(End definition for \l__hook_labels_seq and others.)

```

_hook_initialize_single:NNNn
_hook_initialize_single:cccn

_hook_initialize_single:NNNn implements the sorting of the code chunks for a hook and saves the result in the token list for fast execution (#3). The arguments are $\langle hook-code-plist \rangle$, $\langle hook-code-tl \rangle$, $\langle hook-next-code-tl \rangle$, $\langle hook-ordered-labels-clist \rangle$ and $\langle hook-name \rangle$ (the latter is only used for debugging—the $\langle hook-rule-plist \rangle$ is accessed using the $\langle hook-name \rangle$).

The additional complexity compared to Don’s algorithm is that we do not use simple positive integers but have arbitrary alphanumeric labels. As usual Don’s data structures are chosen in a way that one can omit a lot of tests and I have mimicked that as far as possible. The result is a restriction I do not test for at the moment: a label can’t be equal to the number 0!

FMi: Needs checking for, just in case

```
408 \cs_new_protected:Npn \_hook_initialize_single:NNNn #1#2#3#4 {
409   \debug_suspend:
```

Step T1: Initialize the data structure ...

```
410   \seq_clear:N \l__hook_labels_seq
411   \int_zero:N \l__hook_labels_int
```

Store the name of the hook:

```
412   \tl_set:Nn \l__hook_cur_hook_tl {#4}
```

We loop over the property list holding the code and record all labels listed there. Only rules for those labels are of interest to us. While we are at it we count them (which gives us the N in Knuth’s algorithm. The prefix `label_` is added to the variables to ensure that labels named `front`, `rear`, `labels`, or `return` don’t interact with our code.

```
413   \prop_map_inline:Nn \l__hook_work_prop
414   {
415     \int_incr:N \l__hook_labels_int
416     \seq_put_right:Nn \l__hook_labels_seq {##1}
417     \tl_set:cn { \_hook_tl_csname:n {##1} }{0}
418     \seq_clear_new:c { \_hook_seq_csname:n {##1} }
419   }
```

Steps T2 and T3: Sort the relevant rules into the data structure...

This loop constitutes a square matrix of the labels in `\l__hook_work_prop` in the vertical and the horizontal directions. However since the rule $l_A \langle rel \rangle l_B$ is the same as $l_B \langle rel \rangle^{-1} l_A$ we can cut the loop short at the diagonal of the matrix (*i.e.*, when both labels are equal), saving a good amount of time. The way the rules were set up (see the implementation of `_hook_rule_before_gset:nnn` above) ensures that we have no rule in the ignored side of the matrix, and all rules are seen. The rules are applied in `_hook_apply_label_pair:nnn`, which takes the properly-ordered pair of labels as argument.

```
420   \prop_map_inline:Nn \l__hook_work_prop
421   {
422     \prop_map_inline:Nn \l__hook_work_prop
423     {
424       \_hook_if_label_case:nnnnn {##1} {####1}
425       { \prop_map_break: }
426       { \_hook_apply_label_pair:nnn {##1} {####1} }
427       { \_hook_apply_label_pair:nnn {####1} {##1} }
428       {#4}
429     }
430   }
```

Take a breath and take a look at the data structures that have been set up:

```

431  \__hook_debug:n { \__hook_debug_label_data:N \l__hook_work_prop }
Step T4:
432  \tl_set:Nn \l__hook_rear_tl { 0 }
433  \tl_set:cn { \__hook_tl_csname:n { 0 } } { 0 }
434  \seq_map_inline:Nn \l__hook_labels_seq
435  {
436    \int_compare:nNnT { \cs:w \__hook_tl_csname:n {##1} \cs_end: } = 0
437    {
438      \tl_set:cn { \__hook_tl_csname:n { \l__hook_rear_tl } } {##1}
439      \tl_set:Nn \l__hook_rear_tl {##1}
440    }
441  }
442  \tl_set_eq:Nc \l__hook_front_tl { \__hook_tl_csname:n { 0 } }
443  \tl_gclear:N #1
444  \clist_gclear:N #3

```

The whole loop combines steps T5–T7:

```

445  \bool_while_do:nn { ! \str_if_eq_p:Vn \l__hook_front_tl { 0 } }
446  {

```

This part is step T5:

```

447    \int_decr:N \l__hook_labels_int
448    \prop_get:NVN \l__hook_work_prop \l__hook_front_tl \l__hook_return_tl
449    \__hook_tl_gput:NV #1 \l__hook_return_tl
450    \__hook_clist_gput:NV #3 \l__hook_front_tl
451    \__hook_debug:n{ \iow_term:x{Handled~ code~ for~ \l__hook_front_tl} }

```

This is step T6 except that we don't use a pointer *P* to move through the successors, but instead use ##1 of the mapping function.

```

452    \seq_map_inline:cn { \__hook_seq_csname:n { \l__hook_front_tl } }
453    {
454      \tl_set:cx { \__hook_tl_csname:n {##1} }
455      { \int_eval:n
456        { \cs:w \__hook_tl_csname:n {##1} \cs_end: - 1 }
457      }
458      \int_compare:nNnT
459      { \cs:w \__hook_tl_csname:n {##1} \cs_end: } = 0
460      {
461        \tl_set:cn { \__hook_tl_csname:n { \l__hook_rear_tl } } {##1}
462        \tl_set:Nn \l__hook_rear_tl {##1}
463      }
464    }

```

and step T7:

```

465    \tl_set_eq:Nc \l__hook_front_tl
466    { \__hook_tl_csname:n { \l__hook_front_tl } }

```

This is step T8: If we haven't moved the code for all labels (i.e., if `\l__hook_labels_int` is still greater than zero) we have a loop and our partial order can't be flattened out.

```

467  }
468  \int_compare:nNnF \l__hook_labels_int = 0
469  {

```

```

470 \iow_term:x{=====}
471 \iow_term:x{Error:~ label~ rules~ are~ incompatible:}

```

This is not really the information one needs in the error case but will do for now ...

FMi: fix

```

472 \__hook_debug_label_data:N \l__hook_work_prop
473 \iow_term:x{=====}
474 }

```

After we have added all hook code to #1 we finish it off with adding extra code for a one time execution. That is stored in #2 but is normally empty.

```

475 \tl_gput_right:Nn #1 {#2}
476 \debug_resume:
477 }
478 \cs_generate_variant:Nn \__hook_initialize_single:NNNn {ccc}

```

(End definition for __hook_initialize_single:NNNn.)

```

\__hook_tl_gput:NV
\__hook_clist_gput:NV

```

These append either on the right (normal hook) or on the left (reversed hook). This is setup up in __hook_initialize_hook_code:n, elsewhere their behavior is undefined.

```

479 \cs_new:Npn \__hook_tl_gput:NV {\ERROR}
480 \cs_new:Npn \__hook_clist_gput:NV {\ERROR}

```

(End definition for __hook_tl_gput:NV and __hook_clist_gput:NV.)

```

\__hook_apply_label_pair:nnn
\__hook_label_if_exist_apply:nnnF

```

This is the payload of steps T2 and T3 executed in the loop described above. This macro assumes #1 and #2 are ordered, which means that any rule pertaining the pair #1 and #2 is `\g__hook_⟨hook⟩_rule_#1|#2_tl`, and not `\g__hook_⟨hook⟩_rule_#2|#1_tl`. This also saves a great deal of time since we only need to check the order of the labels once.

The arguments here are $\langle label1 \rangle$, $\langle label2 \rangle$, $\langle hook \rangle$, and $\langle hook-code-plist \rangle$. We are about to apply the next rule and enter it into the data structure. `__hook_apply_label_pair:nnn` will just call `__hook_label_if_exist_apply:nnnF` for the $\langle hook \rangle$, and if no rule is found, also try the $\langle hook \rangle$ name ?? denoting a default hook rule.

`__hook_label_if_exist_apply:nnnF` will check if the rule exists for the given hook, and if so call `__hook_apply_rule:nnn`.

```

481 \cs_new_protected:Npn \__hook_apply_label_pair:nnn #1#2#3
482 {

```

Extra complication: as we use default rules and local hook specific rules we first have to check if there is a local rule and if that exist use it. Otherwise check if there is a default rule and use that.

```

483 \__hook_label_if_exist_apply:nnnF {#1} {#2} {#3}
484 {

```

If there is no hook-specific rule we check for a default one and use that if it exists.

```

485 \__hook_label_if_exist_apply:nnnF {#1} {#2} { ?? } { }
486 }
487 }
488 \cs_new_protected:Npn \__hook_label_if_exist_apply:nnnF #1#2#3
489 {
490 \if_cs_exist:w g__hook_ #3 _rule_ #1 | #2 _tl \cs_end:

```

What to do precisely depends on the type of rule we have encountered. If it is a **before** rule it will be handled by the algorithm but other types need to be managed differently. All this is done in `__hook_apply_rule:nnnN`.

```

491     \__hook_apply_rule:nnn {#1} {#2} {#3}
492     \exp_after:wN \use_none:n
493     \else:
494     \use:nn
495     \fi:
496 }

```

(End definition for `__hook_apply_label_pair:nnn` and `__hook_label_if_exist_apply:nnnF`.)

`__hook_apply_rule:nnn` This is the code executed in steps T2 and T3 while looping through the matrix This is part of step T3. We are about to apply the next rule and enter it into the data structure. The arguments are $\langle label1 \rangle$, $\langle label2 \rangle$, $\langle hook-name \rangle$, and $\langle hook-code-plist \rangle$.

```

497 \cs_new_protected:Npn \__hook_apply_rule:nnn #1#2#3
498 {
499     \cs:w __hook_apply_
500     \cs:w g__hook_#3_reversed_tl \cs_end: rule_
501     \cs:w g__hook_ #3 _rule_ #1 | #2 _tl \cs_end: :nnn \cs_end:
502     {#1} {#2} {#3}
503 }

```

(End definition for `__hook_apply_rule:nnn`.)

`__hook_apply_rule_<:nnn` The most common cases are $<$ and $>$ so we handle that first. They are relations \prec and \succ in TAOCP, and they dictate sorting.

```

\__hook_apply_rule_>:nnn
504 \cs_new_protected:cpn { __hook_apply_rule_<:nnn } #1#2#3
505 {
506     \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
507     \tl_set:cx { \__hook_tl_csname:n {#2} }
508     { \int_eval:n{ \cs:w \__hook_tl_csname:n {#2} \cs_end: + 1 } }
509     \seq_put_right:cn{ \__hook_seq_csname:n {#1} }{#2}
510 }
511 \cs_new_protected:cpn { __hook_apply_rule_>:nnn } #1#2#3
512 {
513     \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
514     \tl_set:cx { \__hook_tl_csname:n {#1} }
515     { \int_eval:n{ \cs:w \__hook_tl_csname:n {#1} \cs_end: + 1 } }
516     \seq_put_right:cn{ \__hook_seq_csname:n {#2} }{#1}
517 }

```

(End definition for `__hook_apply_rule_<:nnn` and `__hook_apply_rule_>:nnn`.)

`__hook_apply_rule_xE:nnn` These relations make two labels incompatible within a hook. `xE` makes raises an error if the labels are found in the same hook, and `xW` makes it a warning.

```

\__hook_apply_rule_xW:nnn
518 \cs_new_protected:cpn { __hook_apply_rule_xE:nnn } #1#2#3
519 {
520     \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
521     \msg_error:nnnnnn { hooks } { labels-incompatible }
522     {#1} {#2} {#3} { 1 }
523     \use:c { __hook_apply_rule_>:nnn } {#1} {#2} {#3}
524     \use:c { __hook_apply_rule_<:nnn } {#1} {#2} {#3}
525 }

```

```

526 \cs_new_protected:cpn { __hook_apply_rule_xW:nnn } #1#2#3
527 {
528   \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
529   \msg_warning:nnnnnn { hooks } { labels-incompatible }
530   {#1} {#2} {#3} { 0 }
531 }

```

(End definition for __hook_apply_rule_xE:nnn and __hook_apply_rule_xW:nnn.)

```

\__hook_apply_rule_>:nnn
\__hook_apply_rule_<:nnn

```

If we see `>` we have to drop code for label #3 and carry on. We could do a little better and drop everything for that label since it doesn't matter where we sort in the empty code. However that would complicate the algorithm a lot with little gain.⁷ So we still unnecessarily try to sort it in and depending on the rules that might result in a loop that is otherwise resolved. If that turns out to be a real issue, we can improve the code.

Here the code is removed from `\l__hook_cur_hook_tl` rather than #3 because the latter may be `??`, and the default hook doesn't store any code. Removing from `\l__hook_cur_hook_tl` makes default rules `>` and `<` work properly.

```

532 \cs_new_protected:cpn { __hook_apply_rule_>:nnn } #1#2#3
533 {
534   \__hook_debug:n
535   {
536     \__hook_msg_pair_found:nnn {#1} {#2} {#3}
537     \iow_term:x{--->~ Drop~ '#2'~ code~ from~
538       \iow_char:N \ g__hook_ \l__hook_cur_hook_tl _code_prop ~
539       because~ of~ '#1' }
540   }
541   \prop_put:Nnn \l__hook_work_prop {#2} { }
542 }
543 \cs_new_protected:cpn { __hook_apply_rule_<:nnn } #1#2#3
544 {
545   \__hook_debug:n
546   {
547     \__hook_msg_pair_found:nnn {#1} {#2} {#3}
548     \iow_term:x{--->~ Drop~ '#1'~ code~ from~
549       \iow_char:N \ g__hook_ \l__hook_cur_hook_tl _code_prop ~
550       because~ of~ '#2' }
551   }
552   \prop_put:Nnn \l__hook_work_prop {#1} { }
553 }

```

(End definition for __hook_apply_rule_>:nnn and __hook_apply_rule_<:nnn.)

```

\__hook_apply_rule_<:nnn
\__hook_apply_rule_>:nnn
\__hook_apply_rule_<:nnn
\__hook_apply_rule_>:nnn
\__hook_apply_rule_x:nnn

```

Reversed rules.

```

554 \cs_new_eq:cc { __hook_apply_rule_<:nnn } { __hook_apply_rule_>:nnn }
555 \cs_new_eq:cc { __hook_apply_rule_>:nnn } { __hook_apply_rule_<:nnn }
556 \cs_new_eq:cc { __hook_apply_rule_<:nnn } { __hook_apply_rule_<:nnn }
557 \cs_new_eq:cc { __hook_apply_rule_>:nnn } { __hook_apply_rule_>:nnn }
558 \cs_new_eq:cc { __hook_apply_rule_xE:nnn } { __hook_apply_rule_xE:nnn }
559 \cs_new_eq:cc { __hook_apply_rule_xW:nnn } { __hook_apply_rule_xW:nnn }

```

(End definition for __hook_apply_rule_<:nnn and others.)

⁷This also has the advantage that the result of the sorting doesn't change which might otherwise (for unrelated chunks) if we aren't careful.


```

\__hook_msg_pair_found:nnn A macro to avoid moving this many tokens around.
560 \cs_new_protected:Npn \__hook_msg_pair_found:nnn #1#2#3
561 {
562   \iow_term:x{~ \str_if_eq:nnTF {#3} {??} {default} {~normal} ~
563     rule~ \__hook_label_pair:nn {#1} {#2}:~
564     \use:c { g__hook_#3_rule_ \__hook_label_pair:nn {#1} {#2} _tl } ~
565     found}
566 }

```

(End definition for __hook_msg_pair_found:nnn.)

```

\__hook_debug_label_data:N
567 \cs_new_protected:Npn \__hook_debug_label_data:N #1 {
568   \iow_term:x{Code~ labels~ for~ sorting:}
569   \iow_term:x{~ \seq_use:Nnnn\l__hook_labels_seq {~and~}{,~}{~and~} }
570   \iow_term:x{^^J Data~ structure~ for~ label~ rules:}
571   \prop_map_inline:Nn #1
572   {
573     \iow_term:x{~ ##1~ =~ \tl_use:c{ \__hook_tl_csname:n {##1} }~ ->~
574       \seq_use:cnnn{ \__hook_seq_csname:n {##1} }{-->~}{-->~}{-->~}
575   }
576 }
577 \iow_term:x{}
578 }

```

(End definition for __hook_debug_label_data:N.)

\hook_log:n This writes out information about the hook given in its argument onto the terminal and the .log file.

```

579 \cs_new_protected:Npn \hook_log:n #1
580 {
581   \exp_args:Nx \__hook_log:n
582   { \__hook_parse_label_default:nn {#1} { top-level } }
583 }
584 \cs_new_protected:Npn \__hook_log:n #1
585 {
586   \__hook_preamble_hook:n {#1}
587   \iow_term:x{^^JThe~ hook~ '#1':}
588   \hook_if_exist:nF {#1}
589   { \iow_term:x {~Hook~ is~ not~ declared!} }
590   \__hook_if_exist:nTF {#1}
591   {
592     \iow_term:x{~Code~ chunks:}
593     \prop_if_empty:cTF {g__hook_#1_code_prop}
594     { \iow_term:x{\@spaces ---} }
595     {
596       \prop_map_inline:cn {g__hook_#1_code_prop}
597       { \iow_term:x{\@spaces ##1~ ->~ \tl_to_str:n{##2} } }
598     }
599     \iow_term:x{~Extra~ code~ next~ invocation:}
600     \iow_term:x{\@spaces
601       \tl_if_empty:cTF { g__hook_#1_code_next_tl }
602       {---}}

```

If the token list is not empty we want to display it but without the first tokens (the code to clear itself) so we call a helper command to get rid of them.

```

603         {->~ \exp_args:Nv
604         \__hook_log_next_code:n {g__hook_#1_code_next_tl} } }

```

Loop through the rules in a hook and for every rule found, print it. If no rule is there, print ---. The boolean \l__hook_tmpa_bool here indicates if the hook has no rules.

```

605     \iow_term:x { ~Rules: }
606     \bool_set_true:N \l__hook_tmpa_bool
607     \__hook_list_rules:nn {#1}
608     {
609         \bool_set_false:N \l__hook_tmpa_bool
610         \iow_term:x
611         {
612             \@spaces ##2~ with~
613             \str_if_eq:nnT {##3} {??} { default~ }
614             relation~ ##1 }
615         }
616     \bool_if:NT \l__hook_tmpa_bool
617     { \iow_term:x { \@spaces --- } }
618     \bool_lazy_and:nnT
619     { \hook_if_exist_p:n {#1} }
620     { ! \hook_if_empty_p:n {#1} }
621     { \iow_term:x { ~Execution~ order
622         \bool_if:NTF \l__hook_tmpa_bool
623         { \__hook_if_reversed:nT {#1}
624             { ~ (after~ reversal) }
625         }
626         { ~ (after~
627             \__hook_if_reversed:nT {#1} {reversal~ and~}
628             applying~ rules)
629         }
630         :
631     }
632     \iow_term:x
633     { \@spaces \clist_use:cn {g__hook_#1_labels_clist} { ,~ } }
634 }
635 }
636 { \iow_term:n { ~The~hook~is~empty. } }
637 \iow_term:n { }
638 }

```

To display the code for next invocation only (i.e., from \AddToHookNext we have to remove the first two tokens at the front which are \tl_gclear:N and the token list to clear.

```

639 \cs_new:Npn \__hook_log_next_code:n #1 {
640     \exp_args:No \tl_to_str:n {\use_none:nn #1}
641 }

```

(End definition for \hook_log:n. This function is documented on page ??.)

__hook_list_rules:nn This macro takes a *<hook>* and an *<inline function>* and loops through each pair of *<labels>* in the *<hook>*, and if there is a relation between this pair of *<labels>*, the *<inline function>*

__hook_list_one_rule:nnn

__hook_list_if_rule_exists:nnnF

is executed with $\#1 = \langle relation \rangle$, $\#2 = \langle label_1 \rangle | \langle label_2 \rangle$, and $\#3 = \langle hook \rangle$ (the latter may be the argument $\#1$ to `_hook_list_rules:nn`, or `??` if it is a default rule).

```

642 \cs_new_protected:Npn \_hook_list_rules:nn #1 #2
643 {
644   \cs_set_protected:Npn \_hook_tmp:w ##1 ##2 ##3 {#2}
645   \prop_map_inline:cn { g\_hook\_#1\_code\_prop }
646   {
647     \prop_map_inline:cn { g\_hook\_#1\_code\_prop }
648     {
649       \_hook_if_label_case:nnnnn {##1} {####1}
650       { \prop_map_break: }
651       { \_hook_list_one_rule:nnn {##1} {####1} }
652       { \_hook_list_one_rule:nnn {####1} {##1} }
653       {#1}
654     }
655   }
656 }

```

These two are quite similar to `_hook_apply_label_pair:nnn` and `_hook_label_if_exist_apply:nnnF`, respectively, but rather than applying the rule, they pass it to the *inline function*.

```

657 \cs_new_protected:Npn \_hook_list_one_rule:nnn #1#2#3
658 {
659   \_hook_list_if_rule_exists:nnnF {#1} {#2} {#3} { }
660   { \_hook_list_if_rule_exists:nnnF {#1} {#2} { ?? } { } }
661 }
662 \cs_new_protected:Npn \_hook_list_if_rule_exists:nnnF #1#2#3
663 {
664   \if_cs_exist:w g\_hook\_ #3\_rule\_ #1 | #2\_tl \cs_end:
665   \exp_args:Nv \_hook_tmp:w
666   { g\_hook\_ #3\_rule\_ #1 | #2\_tl } { #1 | #2 } {#3}
667   \fi:
668 }

```

(End definition for `_hook_list_rules:nn`, `_hook_list_one_rule:nnn`, and `_hook_list_if_rule_exists:nnnF`.)

`_hook_debug_print_rules:n` A shorthand for debugging that prints similar to `\prop_show:N`.

```

669 \cs_new_protected:Npn \_hook_debug_print_rules:n #1
670 {
671   \iow_term:n { The~hook~#1~contains~the~rules: }
672   \cs_set_protected:Npn \_hook_tmp:w ##1
673   {
674     \_hook_list_rules:nn {#1}
675     {
676       \iow_term:x
677       {
678         > ##1 {####2} ##1 => ##1 {####1}
679         \str_if_eq:nnT {####3} {??} { ~(default) }
680       }
681     }
682   }
683   \exp_args:No \_hook_tmp:w { \use:nn { ~ } { ~ } }
684 }

```

(End definition for `_hook_debug_print_rules:n`.)

3.8 Specifying code for next invocation

`\hook_gput_next_code:nn`

```

685 \cs_new_protected:Npn \hook_gput_next_code:nn #1
686 {
687   \exp_args:Nx \__hook_gput_next_code:nn
688     { \__hook_parse_label_default:nn {#1} { top-level } }
689 }
690 \cs_new_protected:Npn \__hook_gput_next_code:nn #1 #2
691 {
692   \__hook_declare:n {#1}
693   \hook_if_exist:nTF {#1}
694     { \__hook_gput_next_do:nn {#1} {#2} }
695     { \__hook_try_declaring_generic_next_hook:nn {#1} {#2} }
696 }
697 \cs_new_protected:Npn \__hook_gput_next_do:nn #1
698 {
699   \exp_args:Nc \__hook_gput_next_do:Nnn
700     { g__hook_#1_code_next_tl } {#1}
701 }

```

First check if the “next code” token list is empty: if so we need to add a `\tl_gclear:c` to clear it, so the code lasts for one usage only. The token list is cleared early so that nested usages don’t get lost. `\tl_gclear:c` is used instead of `\tl_gclear:N` in case the hook is used in an expansion-only context, so the token list doesn’t expand before `\tl_gclear:N`: that would make an infinite loop. Also in case the main code token list is empty, the hook code has to be updated to add the next execution token list.

```

702 \cs_new_protected:Npn \__hook_gput_next_do:Nnn #1 #2
703 {
704   \tl_if_empty:cT { g__hook_#2_code_tl }
705     { \__hook_update_hook_code:n {#2} }
706   \tl_if_empty:NT #1
707     { \tl_gset:Nn #1 { \tl_gclear:c { g__hook_#2_code_next_tl } } }
708   \tl_gput_right:Nn #1
709 }

```

(End definition for `\hook_gput_next_code:nn`. This function is documented on page 10.)

3.9 Using the hook

`\hook_use:n`
`__hook_use_initialized:n`
`__hook_preamble_hook:n`

`\hook_use:n` as defined here is used in the preamble, where hooks aren’t initialized by default. `__hook_use_initialized:n` is also defined, which is the non-`\protected` version for use within the document. Their definition is identical, except for the `__hook_preamble_hook:n` (which wouldn’t hurt in the expandable version, but it would be an unnecessary extra expansion).

`__hook_use_initialized:n` holds the expandable definition while in the preamble. `__hook_preamble_hook:n` initializes the hook in the preamble, and is redefined to `\use_none:n` at `\begin{document}`.

Both versions do the same internally: check if the hook exist as given, and if so use it as quickly as possible. If it doesn’t exist, the a call to `__hook_use:wn` checks for file hooks.

At `\begin{document}`, all hooks are initialized, and any change in them causes an update, so `\hook_use:n` can be made expandable. This one is better not protected

so that it can expand into nothing if containing no code. Also important in case of generic hooks that we do not generate a `\relax` as a side effect of checking for a `cname`. In contrast to the \TeX low-level `\cname ... \endcname` construct `\tl_if_exist:c` is careful to avoid this.

```

710 \cs_new_protected:Npn \hook_use:n #1
711 {
712   \tl_if_exist:cTF { g__hook_#1_code_tl }
713   {
714     \__hook_preamble_hook:n {#1}
715     \cs:w g__hook_#1_code_tl \cs_end:
716   }
717   { \__hook_use:wn #1 / \s__hook_mark {#1} }
718 }
719 \cs_new:Npn \__hook_use_initialized:n #1
720 {
721   \tl_if_exist:cTF { g__hook_#1_code_tl }
722   { \cs:w g__hook_#1_code_tl \cs_end: }
723   { \__hook_use:wn #1 / \s__hook_mark {#1} }
724 }
725 \cs_new_protected:Npn \__hook_preamble_hook:n #1
726 { \__hook_initialize_hook_code:n {#1} }

```

(End definition for `\hook_use:n`, `__hook_use_initialized:n`, and `__hook_preamble_hook:n`. This function is documented on page 9.)

`__hook_use:wn` `__hook_use:wn` does a quick check to test if the current hook is a file hook: those need a special treatment. If it is not, the hook does not exist. If it is, then `__hook_try_file_hook:n` is called, and checks that the current hook is a file-specific hook using `__hook_if_file_hook:wTF`. If it's not, then it's a generic file/ hook and is used if it exist.

If it is a file-specific hook, it passes through the same normalization as during declaration, and then it is used if defined. `__hook_if_exist_use:n` checks if the hook exist, and calls `__hook_preamble_hook:n` if so, then uses the hook.

```

727 \cs_new:Npn \__hook_use:wn #1 / #2 \s__hook_mark #3
728 {
729   \str_if_eq:nnTF {#1} { file }
730   { \__hook_try_file_hook:n {#3} }
731   { } % Hook doesn't exist
732 }
733 \cs_new_protected:Npn \__hook_try_file_hook:n #1
734 {
735   \__hook_if_file_hook:wTF #1 / / \s__hook_mark
736   {
737     \exp_args:Ne \__hook_if_exist_use:n
738     { \exp_args:Ne \__hook_file_hook_normalize:n {#1} }
739   }
740   { \__hook_if_exist_use:n {#1} } % file/ generic hook (e.g. file/before)
741 }
742 \cs_new_protected:Npn \__hook_if_exist_use:n #1
743 {
744   \tl_if_exist:cT { g__hook_#1_code_tl }
745   {
746     \__hook_preamble_hook:n {#1}

```

```

747         \cs:w g__hook_#1_code_tl \cs_end:
748     }
749 }

```

(End definition for `_hook_use:wn`, `_hook_try_file_hook:n`, and `_hook_if_exist_use:n`.)

`\hook_use_once:n` For hooks that can and should be used only once we have a special use command that remembers the hook name in `\g__hook_execute_immediately_clist`. This has the effect that any further code added to the hook is executed immediately rather than stored in the hook.

```

750 \cs_new_protected:Npn \hook_use_once:n #1
751 {
752     \tl_if_exist:cT { g__hook_#1_code_tl }
753     {
754         \clist_gput_left:Nn \g__hook_execute_immediately_clist {#1}
755         \hook_use:n {#1}
756     }
757 }

```

(End definition for `\hook_use_once:n`. This function is documented on page 9.)

3.10 Querying a hook

Simpler data types, like token lists, have three possible states; they can exist and be empty, exist and be non-empty, and they may not exist, in which case emptiness doesn't apply (though `\tl_if_empty:N` returns false in this case).

Hooks are a bit more complicated: they have four possible states. A hook may exist or not, and either way it may or may not be empty (even a hook that doesn't exist may be non-empty).

A hook is said to be empty when no code was added to it, either to its permanent code pool, or to its “next” token list. The hook doesn't need to be declared to have code added to its code pool (it may happen that a package *A* defines a hook `foo`, but it's loaded after package *B*, which adds some code to that hook. In this case it is important that the code added by package *B* is remembered until package *A* is loaded).

A hook is said to exist when it was declared with `\hook_new:n` or some variant thereof.

`\hook_if_empty_p:n` Test if a hook is empty (that is, no code was added to that hook). A hook being empty means that *both* its `\g__hook_⟨hook⟩_code_prop` and its `\g__hook_⟨hook⟩_code_next_tl` are empty.

`\hook_if_empty:nTF`

```

758 \prg_new_conditional:Npnn \hook_if_empty:n #1 { p , T , F , TF }
759 {
760     \_hook_if_exist:nTF {#1}
761     {
762         \bool_lazy_and:nnTF
763         { \prop_if_empty_p:c { g__hook_#1_code_prop } }
764         { \tl_if_empty_p:c { g__hook_#1_code_next_tl } }
765         { \prg_return_true: }
766         { \prg_return_false: }
767     }
768     { \prg_return_true: }
769 }

```

(End definition for `\hook_if_empty:nTF`. This function is documented on page 10.)

`\hook_if_exist_p:n` A canonical way to test if a hook exists. A hook exists if the token list that stores the sorted code for that hook, `\g__hook_⟨hook⟩_code_tl`, exists. The property list `\g__hook_⟨hook⟩_code_prop` cannot be used here because often it is necessary to add code to a hook without knowing if such hook was already declared, or even if it will ever be (for example, in case the package that defines it isn't loaded).

`\hook_if_exist:nTF`

```

770 \prg_new_conditional:Npnn \hook_if_exist:n #1 { p , T , F , TF }
771 {
772   \tl_if_exist:cTF { g__hook_#1_code_tl }
773   { \prg_return_true: }
774   { \prg_return_false: }
775 }

```

(End definition for `\hook_if_exist:nTF`. This function is documented on page 11.)

`__hook_if_exist_p:n` An internal check if the hook has already been declared with `__hook_declare:n`. This means that the hook was already used somehow (a code chunk or rule was added to it), but it still wasn't declared with `\hook_new:n`.

`__hook_if_exist:nTF`

```

776 \prg_new_conditional:Npnn \__hook_if_exist:n #1 { p , T , F , TF }
777 {
778   \prop_if_exist:cTF { g__hook_#1_code_prop }
779   { \prg_return_true: }
780   { \prg_return_false: }
781 }

```

(End definition for `__hook_if_exist:nTF`.)

`__hook_if_reversed_p:n` An internal conditional that checks if a hook is reversed.

`__hook_if_reversed:nTF`

```

782 \prg_new_conditional:Npnn \__hook_if_reversed:n #1 { p , T , F , TF }
783 {
784   \if_int_compare:w \cs:w g__hook_#1_reversed_tl \cs_end: 1 < 0 \exp_stop_f:
785   \prg_return_true:
786   \else:
787   \prg_return_false:
788   \fi:
789 }

```

(End definition for `__hook_if_reversed:nTF`.)

`\g__hook_execute_immediately_clist` List of hooks that from now on should not longer receive code.

```

790 \clist_new:N \g__hook_execute_immediately_clist

```

(End definition for `\g__hook_execute_immediately_clist`.)

3.11 Messages

```

791 \msg_new:nnnn { hooks } { labels-incompatible }
792 {
793   Labels~'#1'~and~'#2'~are~incompatible
794   \str_if_eq:nnF {#3} {??} { ~in~hook~'~#3' } .~
795   \int_compare:nNnTF {#4} = { 1 }
796   { The~ code~ for~ both~ labels~ will~ be~ dropped. }
797   { You~ may~ see~ errors~ later. }

```

```

798 }
799 { LaTeX-found-two-incompatible-labels-in-the-same-hook.~
800   This~indicates~an~incompatibility~between~packages. }

801 \msg_new:nnnn { hooks } { exists }
802   { Hook~‘#1’~ has~ already~ been~ declared. }
803   { There~ already~ exists~ a~ hook~ declaration~ with~ this~
804     name.\\
805     Please~ use~ a~ different~ name~ for~ your~ hook.}

806 \msg_new:nnn { hooks } { empty-label }
807   { Empty~code~label~\msg_line_context:..Using~‘#1’~instead. }

808 \msg_new:nnnn { hooks } { unknown-rule }
809   { Unknown~ relationship~ ‘#3’~
810     between~ labels~ ‘#2’~ and~ ‘#4’~
811     \str_if_eq:nnF {#1} {??} { ~in~hook~‘#1’ }. ~
812     Perhaps~ a~ misspelling?
813   }
814   {
815     The~ relation~ used~ not~ known~ to~ the~ system.~ Allowed~ values~ are~
816     ‘before’~ or~ ‘<’,~
817     ‘after’~ or~ ‘>’,~
818     ‘incompatible-warning’,~
819     ‘incompatible-error’,~
820     ‘voids’~ or~
821     ‘unrelated’.
822   }

823 \msg_new:nnn { hooks } { should-not-happen }
824   {
825     ERROR!~This~should~not~happen.~#1 \\
826     Please~report~at~https://github.com/latex3/latex2e.
827   }

```

3.12 L^AT_EX 2_ε package interface commands

\NewHook Declaring new hooks ...

```

\NewReversedHook 828 \NewDocumentCommand \NewHook          { m }{ \hook_new:n {#1} }
\NewMirroredHookPair 829 \NewDocumentCommand \NewReversedHook      { m }{ \hook_new_reversed:n {#1} }
830 \NewDocumentCommand \NewMirroredHookPair { mm }{ \hook_new_pair:nn {#1}{#2} }

```

(End definition for `\NewHook`, `\NewReversedHook`, and `\NewMirroredHookPair`. These functions are documented on page 3.)

\AddToHook

```

831 \NewDocumentCommand \AddToHook { m o +m }
832   {
833     \clist_if_in:NnTF \g__hook_execute_immediately_clist {#1}
834       {#3}
835     { \hook_gput_code:nnn {#1} {#2} {#3} }
836   }

```

(End definition for `\AddToHook`. This function is documented on page 4.)

\AddToHookNext

```

837 \NewDocumentCommand \AddToHookNext { m +m }
838   { \hook_gput_next_code:nn {#1} {#2} }

```


(End definition for `\AddToHookNext`. This function is documented on page 5.)

`\RemoveFromHook`

```
839 \NewDocumentCommand \RemoveFromHook { m o }
840 { \hook_gremove_code:nn {#1} {#2} }
```

(End definition for `\RemoveFromHook`. This function is documented on page 4.)

`\DeclareDefaultHookLabel`

```
\__hook_curr_name_push:n
  \__hook_curr_name_pop:
```

The token list `\g__hook_hook_curr_name_tl` stores the name of the current package/file to be used as label for hooks. Providing a consistent interface is tricky, because packages can be loaded within packages, and some packages may not use `\DeclareDefaultHookLabel` to change the default label (in which case `@currname` is used, if set).

To pull that off, we keep a stack that contains the default label for each level of input. The bottom of the stack contains the default label for the top-level. Since the string `top-level` is hardcoded, here this item of the stack is empty. Also, since we're in an input level, add `lthooks` to the stack as well. This stack should never go empty. An empty entry is added to the stack to account for the `top-level`. The item is empty so that the hard-coded default is used, but a call to `\DeclareDefaultHookLabel` will change it if needed.

```
841 \seq_gpush:Nn \g__hook_name_stack_seq { }
```

Two commands keep track of the stack: when a file is input, `__hook_curr_name_push:n` pushes an (empty by default) label to the stack:

```
842 \cs_new_protected:Npn \__hook_curr_name_push:n #1
843 {
844   \seq_gpush:Nn \g__hook_name_stack_seq {#1}
845   \tl_gset:Nn \g__hook_hook_curr_name_tl {#1}
846 }
847 %
```

and when an input is over, the topmost item of the stack is popped, since the label will not be used again, and `\g__hook_hook_curr_name_tl` is updated to the now topmost item of the stack:

```
848 \cs_new_protected:Npn \__hook_curr_name_pop:
849 {
850   \seq_gpop:NN \g__hook_name_stack_seq \l__hook_return_tl
851   \seq_get:NNTF \g__hook_name_stack_seq \l__hook_return_tl
852   { \tl_gset_eq:NN \g__hook_hook_curr_name_tl \l__hook_return_tl }
853   {
854     \msg_error:nnn { hooks } { should-not-happen }
855     { Tried-to-pop-from-an-empty-default-label-stack. }
856   }
857 }
```

The token list `\g__hook_hook_curr_name_tl` is but a mirror of the top of the stack.

Now define a wrapper that replaces the top of the stack with the argument, and updates `\g__hook_hook_curr_name_tl` accordingly.

```
858 \NewDocumentCommand \DeclareDefaultHookLabel { m }
859 {
860   \seq_gpop:NN \g__hook_name_stack_seq \l__hook_return_tl
861   \__hook_curr_name_push:n {#1}
862 }
```

(End definition for `\DeclareDefaultHookLabel`, `_hook_curr_name_push:n`, and `_hook_curr_name_pop:`. This function is documented on page 6.)

`\UseHook` Avoid the overhead of `xparse` and its protection that we don't want here (since the hook should vanish without trace if empty)!

`\UseOneTimeHook`

```
863 \newcommand \UseHook      { \hook_use:n }
864 \newcommand \UseOneTimeHook { \hook_use_once:n }
```

(End definition for `\UseHook` and `\UseOneTimeHook`. These functions are documented on page 3.)

`\ShowHook`

```
865 \cs_new_protected:Npn \ShowHook { \hook_log:n }
```

(End definition for `\ShowHook`. This function is documented on page 9.)

`\DebugHooksOn`

`\DebugHooksOff`

```
866 \cs_new_protected:Npn \DebugHooksOn { \hook_debug_on: }
867 \cs_new_protected:Npn \DebugHooksOff { \hook_debug_off: }
```

(End definition for `\DebugHooksOn` and `\DebugHooksOff`. These functions are documented on page 9.)

`\DeclareHookRule`

```
868 \NewDocumentCommand \DeclareHookRule { m m m m }
869 { \hook_gset_rule:nnnn {#1}{#2}{#3}{#4} }
```

(End definition for `\DeclareHookRule`. This function is documented on page 7.)

`\DeclareDefaultHookRule`

This declaration is only supported before `\begin{document}`.

```
870 \NewDocumentCommand \DeclareDefaultHookRule { m m m }
871 { \hook_gset_rule:nnnn {??}{#1}{#2}{#3} }
872 \@onlypreamble\DeclareDefaultHookRule
```

(End definition for `\DeclareDefaultHookRule`. This function is documented on page 7.)

`\ClearHookRule`

A special setup rule that removes an existing relation. Basically `@@_rule_gclear:nnn` plus fixing the property list for debugging.

FMi: Need an L3 interface, or maybe it should get dropped?

```
873 \NewDocumentCommand \ClearHookRule { m m m }
874 { \hook_gset_rule:nnnn {#1}{#2}{unrelated}{#3} }
```

(End definition for `\ClearHookRule`. This function is documented on page 7.)

`\IfHookExistsTF`

`\IfHookEmptyTF`

```
875 \NewExpandableDocumentCommand \IfHookExistsTF { m }
876 { \hook_if_exist:nTF {#1} }
877 \NewExpandableDocumentCommand \IfHookEmptyTF { m }
878 { \hook_if_empty:nTF {#1} }
```

(End definition for `\IfHookExistsTF` and `\IfHookEmptyTF`. These functions are documented on page 8.)

3.13 Internal commands needed elsewhere

Here we set up a few horrible (but consistent) L^AT_EX_{2 ϵ} names to allow for internal commands to be used outside this module. We have to unset the @@ since we want double “at” sign in place of double underscores.

```

879 <@@=)

\@expl@@@initialize@all@@
\@expl@@@hook@curr@name@push@@n
\@expl@@@hook@curr@name@pop@@
880 \cs_new_eq:NN \@expl@@@initialize@all@@
881      \__hook_initialize_all:
882 \cs_new_eq:NN \@expl@@@hook@curr@name@push@@n
883      \__hook_curr_name_push:n
884 \cs_new_eq:NN \@expl@@@hook@curr@name@pop@@
885      \__hook_curr_name_pop:

```

(End definition for \@expl@@@initialize@all@@, \@expl@@@hook@curr@name@push@@n, and \@expl@@@hook@curr@name@pop@@. These functions are documented on page ??.)

```

886 \ExplSyntaxOff

```

Rolling back here doesn’t undefine the interface commands as they may be used in packages without rollback functionality. So we just make them do nothing which may or may not work depending on the code usage.

```

887 </2kernel | latexrelease>
888 <latexrelease>\EndIncludeInRelease
889 <latexrelease>\IncludeInRelease{0000/00/00}%
890 <latexrelease>      {\NewHook}{The hook management}%
891 <latexrelease>
892 <latexrelease>\def \NewHook#1{}
893 <latexrelease>\def \NewReversedHook#1{}
894 <latexrelease>\def \NewMirroredHookPair#1#2{}
895 <latexrelease>
896 <latexrelease>\long\def \AddToHook#1#2{}
897 <latexrelease>
898 <latexrelease>\def \AddToHookNext#1{\@gobble@AddToHook@args}
899 <latexrelease>\providecommand\@gobble@AddToHook@args[2] [] {}
900 <latexrelease>
901 <latexrelease>\def \RemoveFromHook#1{\@gobble@RemoveFromHook@arg}
902 <latexrelease>\providecommand\@gobble@RemoveFromHook@arg[1] [] {}
903 <latexrelease>
904 <latexrelease>\def \UseHook      #1{}
905 <latexrelease>\def \UseOneTimeHook #1{}
906 <latexrelease>\def \ShowHook #1{}
907 <latexrelease>\let \DebugHooksOn \@empty
908 <latexrelease>\let \DebugHooksOff \@empty
909 <latexrelease>
910 <latexrelease>\def \DeclareHookRul#1#2#3#4{}
911 <latexrelease>\def \DeclareDefaultHookRule #1#2#3{}
912 <latexrelease>\def \ClearHookRule#1#2#3{}

```

If the hook management is not provided we make the test for existence false and the test for empty true in the hope that this is most of the time reasonable. If not a package would need to guard against running in an old kernel.

```

913 <latexrelease>\def \IfHookExistTF #1#2#3{#3}

```

```

914 \<latexrelease>\def \IfHookEmptyTF #1#2#3{#2}
915 \<latexrelease>
916 \<latexrelease>\EndIncludeInRelease

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
<code>\</code>	538, 549, 804, 825
<code>\<addto-cmd></code>	2
<code>\<env></code>	15
A	
<code>\AddToHook</code>	1,
	2, 3, 3, 4, 7, 9, 12, 13, 14, 831, 896
<code>\AddToHookNext</code>	3, 4, 7, 9, 41, 837, 898
<code>\AfterEndEnvironment</code>	15
<code>\AtBeginDocument</code>	14
<code>\AtBeginDocument</code> ...	2, 13, 14, 14, 15, 16
<code>\AtBeginDvi</code>	14
<code>\AtBeginEnvironment</code>	15
<code>\AtEndDocument</code>	14, 16
<code>\AtEndEnvironment</code>	15
<code>\AtEndPreamble</code>	15
B	
<code>\BeforeBeginEnvironment</code> ..	15, 15, 15, 15
<code>\begin</code>	1, 14, 15, 15, 16, 27
<code>\bfdefault</code>	18
<code>\bfseries</code>	18
bool commands:	
<code>\bool_gset_false:N</code>	15
<code>\bool_gset_true:N</code>	10
<code>\bool_if:NTF</code>	21, 616, 622
<code>\bool_lazy_and:nnTF</code>	618, 762
<code>\bool_lazy_or:nnTF</code>	213
<code>\bool_new:N</code>	6, 24
<code>\bool_set_false:N</code>	609
<code>\bool_set_true:N</code>	606
<code>\bool_while_do:nn</code>	445
C	
<code>\ClearHookRule</code>	6, 873, 912
<code>\clearpage</code>	16
clist commands:	
<code>\clist_gclear:N</code>	444
<code>\clist_gput_left:Nn</code>	388, 754
<code>\clist_gput_right:Nn</code>	390
<code>\clist_if_in:NnTF</code>	833
<code>\clist_new:N</code>	48, 790
<code>\clist_use:Nn</code>	633
cs commands:	
<code>\cs:w</code> .	353, 384, 436, 456, 459, 499,
	500, 501, 508, 515, 715, 722, 747, 784
<code>\cs_end:</code>	
	356, 384, 436, 456, 459, 490, 500,
	501, 508, 515, 664, 715, 722, 747, 784
<code>\cs_generate_variant:Nn</code>	
	35, 88, 144, 478
<code>\cs_gset_eq:NN</code>	360, 373, 374
<code>\cs_gset_protected:Npx</code>	20
<code>\cs_if_exist_use:NTF</code>	302
<code>\cs_new:Npn</code>	82, 89, 102, 112,
	113, 115, 225, 227, 229, 281, 335,
	351, 401, 402, 479, 480, 639, 719, 727
<code>\cs_new_eq:NN</code>	
	7, 23, 34, 316, 322, 358, 554,
	555, 556, 557, 558, 559, 880, 882, 884
<code>\cs_new_protected:Npn</code>	
	8, 13, 18, 37, 42, 53, 61,
	65, 68, 125, 131, 145, 158, 163, 168,
	173, 182, 240, 246, 263, 265, 270,
	286, 297, 311, 317, 323, 328, 330,
	332, 333, 359, 376, 408, 481, 488,
	497, 504, 511, 518, 526, 532, 543,
	560, 567, 579, 584, 642, 657, 662,
	669, 685, 690, 697, 702, 710, 725,
	733, 742, 750, 842, 848, 865, 866, 867
<code>\cs_set_eq:NN</code>	387, 388, 389, 390
<code>\cs_set_protected:Npn</code>	644, 672
<code>\cs_undefine:N</code>	334
D	
debug commands:	
<code>\debug_resume:</code>	80, 309, 476
<code>\debug_suspend:</code>	70, 301, 409
<code>\DebugHooksOff</code>	8, 866, 908
<code>\DebugHooksOn</code>	8, 866, 907
<code>\DeclareDefaultHookLabel</code> .	4, 5, 5, 48, 841
<code>\DeclareDefaultHookRule</code>	6, 870, 911
<code>\DeclareHookRul</code>	910
<code>\DeclareHookRule</code>	1, 6, 6, 9, 868
<code>\DeclareHookrule</code>	3, 6

<code>\def</code>	892, 893, 894, 896, 898, 901, 904, 905, 906, 910, 911, 912, 913, 914
<code>\document</code>	15, 16
<code>\documentclass</code>	5
E	
<code>\else</code>	347
else commands:	
<code>\else:</code>	340, 355, 493, 786
<code>\end</code>	1, 14, 15, 16, 17, 27
<code>\end(env)</code>	15
<code>\enddocument</code>	13, 16
<code>\EndIncludeInRelease</code>	888, 916
<code>\ERROR</code>	479, 480
exp commands:	
<code>\exp_after:wN</code>	492
<code>\exp_args:Nc</code>	699
<code>\exp_args:Ne</code>	177, 178, 737, 738
<code>\exp_args:Nnnv</code>	75
<code>\exp_args:NNx</code>	277, 395
<code>\exp_args:No</code>	640, 683
<code>\exp_args:Nv</code>	603, 665
<code>\exp_args:Nx</code>	39, 581, 687
<code>\exp_args:Nxx</code>	127, 242
<code>\exp_not:n</code>	370
<code>\exp_stop_f:</code>	337, 345, 784
<code>\ExplSyntaxOff</code>	886
<code>\ExplSyntaxOn</code>	5
F	
fi commands:	
<code>\fi:</code>	341, 349, 355, 495, 667, 788
H	
hook commands:	
<code>\hook_debug_off:</code>	7, 10, 867
<code>\hook_debug_on:</code>	7, 10, 866
<code>\hook_gput_code:nnn</code>	9, 9, 24, 25, 125, 166, 835
<code>\hook_gput_next_code:nn</code>	9, 25, 171, 685, 838
<code>\hook_gremove_code:nn</code>	9, 27, 240, 840
<code>\hook_gset_rule:nnnn</code>	9, 30, 286, 869, 871, 874
<code>\hook_if_empty:nTF</code>	5, 9, 758, 878
<code>\hook_if_empty_p:n</code>	9, 620, 758
<code>\hook_if_exist:nTF</code>	5, 10, 28, 43, 136, 148, 196, 258, 380, 588, 693, 770, 876
<code>\hook_if_exist_p:n</code>	10, 619, 770
<code>\hook_log:n</code>	579, 865
<code>\hook_new:n</code>	8, 20, 37, 45, 46, 62, 66, 196, 828
<code>\hook_new_pair:nn</code>	8, 65, 830
<code>\hook_new_reversed:n</code>	8, 61, 66, 829
<code>\hook_use:n</code>	5, 8, 12, 43, 373, 710, 755, 863
<code>\hook_use_once:n</code>	8, 12, 750, 864
hook internal commands:	
<code>\g__hook_..._code_next_tl</code>	37
<code>\g__hook_..._code_prop</code>	37
<code>\g__hook_..._code_tl</code>	37
<code>\g__hook_??_code_prop</code>	283
<code>\g__hook_??_code_tl</code>	29, 283
<code>\g__hook_??_reversed_tl</code>	283
<code>\g__hook_{hook}_code_tl</code>	33
<code>\g__hook_{hook}_labels_clist</code>	21
<code>\g__hook_{name}_code_next_tl</code>	20
<code>\g__hook_{name}_code_prop</code>	20
<code>\g__hook_{name}_code_tl</code>	20
<code>\g__hook_{name}_reversed_tl</code>	20
<code>\g__hook_all_seq</code>	28, 45, 362
<code>__hook_apply_rule_>:nnn</code>	554
<code>__hook_apply_rule_<:nnn</code>	554
<code>__hook_apply_rule_<:nnn</code>	554
<code>__hook_apply_rule_>:nnn</code>	554
<code>__hook_apply_rule_x:nnn</code>	554
<code>__hook_apply_label_pair:nnn</code>	35, 37, 42, 426, 427, 481
<code>__hook_apply_rule:nnn</code>	37, 491, 497
<code>__hook_apply_rule:nnnN</code>	38
<code>__hook_apply_rule_>:nnn</code>	532
<code>__hook_apply_rule_<:nnn</code>	532
<code>__hook_apply_rule_<:nnn</code>	504
<code>__hook_apply_rule_>:nnn</code>	504
<code>__hook_apply_rule_xE:nnn</code>	518
<code>__hook_apply_rule_xW:nnn</code>	518
<code>__hook_clist_gput:Nn</code>	388, 390, 450, 479
<code>\l__hook_cur_hook_tl</code>	30, 39, 412, 538, 549
<code>__hook_curr_name_pop:</code>	841, 885
<code>__hook_curr_name_push:n</code>	48, 841, 883
<code>__hook_currname_or_default:n</code>	22, 23, 85, 98, 114, 115
<code>__hook_debug:n</code>	7, 18, 147, 361, 366, 377, 395, 431, 451, 506, 513, 520, 528, 534, 545
<code>\g__hook_debug_bool</code>	6, 10, 15, 21
<code>__hook_debug_gset:</code>	7
<code>__hook_debug_label_data:N</code>	431, 472, 567
<code>__hook_debug_print_rules:n</code>	669
<code>__hook_declare:n</code>	46, 47, 53, 160, 299, 692
<code>\g__hook_execute_immediately_</code> <code>clist</code>	45, 754, 790, 833

__hook_file_hook_normalize:n ...	__hook_label_pair:nn 30, 32, 313,
..... 27, 178, 225, 738	319, 325, 329, 331, 334, 335, 563, 564
\l_hook_front_tl 403,	\l_hook_labels_int
442, 445, 448, 450, 451, 452, 465, 466 36, 403, 411, 415, 447, 468
\c_hook_generics_file_prop	\l_hook_labels_seq
..... 26, 218, 237 403, 410, 416, 434, 569
\c_hook_generics_prop 194, 235	__hook_list_if_rule_exists:nnnTF
\c_hook_generics_reversed_ii_- 642
prop 197, 237	__hook_list_one_rule:nnn 642
\c_hook_generics_reversed_iii_-	__hook_list_rules:nn 42, 607, 642, 674
prop 200, 237	__hook_log:n 581, 584
__hook_gput_code:nnn 125	__hook_log_next_code:n 604, 639
__hook_gput_next_code:nn .. 687, 690	__hook_mark_removal:nn 255, 261, 265
__hook_gput_next_do:nn	__hook_msg_pair_found:nnn
..... 25, 171, 694, 697 506, 513, 520, 528, 536, 547, 560
__hook_gput_next_do:Nnn ... 699, 702	\g_hook_name_stack_seq
__hook_gput_undeclared_hook:nnn 32, 841, 844, 850, 851, 860
..... 25, 158, 166	__hook_new:n 39, 42
__hook_gremove_code:nn 240	__hook_parse_dot_label:nn .. 86, 89
__hook_gremove_code_do:nn	__hook_parse_dot_label:nw 89
..... 28, 254, 263	__hook_parse_dot_label_aux:nw .. 89
__hook_gset_rule:nnnn 286	__hook_parse_dot_label_cleanup:w
\g_hook_hook_curr_name_tl 89
. 23, 32, 48, 48, 48, 117, 123, 845, 852	__hook_parse_label_default:nn ..
__hook_hook_gput_code_do:nnn 40, 82, 128,
..... 75, 125, 161	129, 243, 244, 291, 292, 294, 582, 688
__hook_if_exist:nTF	__hook_preamble_hook:n
..... 55, 248, 590, 760, 776 43, 44, 374, 586, 710, 746
__hook_if_exist_p:n 776	\l_hook_rear_tl
__hook_if_exist_use:n 44, 727 403, 432, 438, 439, 461, 462
__hook_if_file_hook:wTF	\g_hook_removal_list_prop 29
..... 25, 26, 44, 175, 208, 735	\g_hook_removal_list_tl
__hook_if_file_hook_p:w 208 29, 29, 267, 272, 277
__hook_if_label_case:nnnn 351, 424, 649	__hook_removal_tl:nn
__hook_if_marked_removal:nnTF 268, 273, 278, 281
..... 133, 275	\l_hook_return_tl 25, 151,
__hook_if_reversed:nTF	154, 253, 448, 449, 850, 851, 852, 860
..... 386, 623, 627, 782	__hook_rule_<_gset:nnn 311
__hook_if_reversed_p:n 782	__hook_rule_>_gset:nnn 311
__hook_include_legacy_code_-	__hook_rule_after_gset:nnn ... 311
chunk:n 50, 68, 379	__hook_rule_before_gset:nnn 35, 311
__hook_initialize_all: 359, 881	__hook_rule_gclear:nnn . 31, 300, 332
__hook_initialize_hook_code:n ..	__hook_rule_incompatible-error_-
..... 37, 360, 376, 726	gset:nnn 328
__hook_initialize_single:NNNn ..	__hook_rule_incompatible-warning_-
..... 32, 33, 35, 392, 408	gset:nnn 328
\l_hook_label_0_tl 403	__hook_rule_unrelated_gset:nnn .
__hook_label_if_exist_apply:nnnTF 31, 332
..... 37, 42, 481	__hook_rule_voids_gset:nnn ... 323
__hook_label_ordered:nn 32	__hook_seq_csname:n
__hook_label_ordered:nnTF 401, 418, 452, 509, 516, 574
..... 30, 314, 320, 326, 343	__hook_str_compare:nn
__hook_label_ordered_p:nn 343 23, 337, 345, 354
	__hook_strip_double_slash:n .. 225

_hook_strip_double_slash:w ..	<u>225</u>	589, 592, 594, 597, 599, 600, 605,
_hook_tl_csname:n	<u>401, 407,</u>	610, 617, 621, 632, 636, 637, 671, 676
417, 433, 436, 438, 442, 454, 456,		
459, 461, 466, 507, 508, 514, 515, 573		
_hook_tl_gput:Nn .	<u>387, 389, 449, 479</u>	
_hook_tmp:w ..	<u>34, 644, 665, 672, 683</u>	
\\l_hook_tmpa_bool		
.....	<u>24, 41, 606, 609, 616, 622</u>	
\\l_hook_tmpa_tl	<u>25</u>	
\\l_hook_tmpb_tl	<u>25</u>	
_hook_try_declaring_generic_-		
hook:nnn	<u>25, 141, 163</u>	
_hook_try_declaring_generic_-		
hook:nNNnn ..	<u>25, 25, 165, 170, 173</u>	
_hook_try_declaring_generic_-		
hook:wnTF	<u>173</u>	
_hook_try_declaring_generic_-		
hook_split:nNNnn	<u>173</u>	
_hook_try_declaring_generic_-		
next_hook:nn	<u>25, 163, 695</u>	
_hook_try_file_hook:n	<u>44, 727</u>	
_hook_unmark_removal:nn	<u>24, 134, 270</u>	
_hook_update_hook_code:n ..	<u>24,</u>	
28, 32, 139, 259, 305, 358, 360, 364, 705		
_hook_use:wn ..	<u>43, 44, 717, 723, 727</u>	
_hook_use_initialized:n	<u>43, 373, 710</u>	
\\g_hook_used_prop .	<u>361, 368, 396, 400</u>	
\\l_hook_work_prop ...	<u>31, 35, 391,</u>	
413, 420, 422, 431, 448, 472, 541, 552		
I		
if commands:		
\\if_case:w	<u>337, 354</u>	
\\if_cs_exist:w	<u>490, 664</u>	
\\if_int_compare:w	<u>345, 784</u>	
\\IfHookEmptyTF	<u>5, 7, 875, 914</u>	
\\IfHookExistsTF	<u>5, 7, 875</u>	
\\IfHookExistTF	<u>913</u>	
\\ignorespaces	<u>16</u>	
\\include	<u>17</u>	
\\IncludeInRelease	<u>3, 889</u>	
\\input	<u>17</u>	
int commands:		
\\int_compare:nNnTF .	<u>436, 458, 468, 795</u>	
\\int_decr:N	<u>447</u>	
\\int_eval:n	<u>455, 508, 515</u>	
\\int_incr:N	<u>415</u>	
\\int_new:N	<u>404</u>	
\\int_zero:N	<u>411</u>	
iow commands:		
\\iow_char:N	<u>538, 549</u>	
\\iow_term:n	<u>147, 367, 369,</u>	
377, 451, 470, 471, 473, 537, 548,		
562, 568, 569, 570, 573, 577, 587,		
L		
\\let	<u>907, 908</u>	
\\listfiles	<u>16, 17</u>	
\\long	<u>896</u>	
M		
\\mdseries	<u>18</u>	
msg commands:		
\\msg_error:nnn	<u>44, 854</u>	
\\msg_error:nnnnnn	<u>307, 521</u>	
\\msg_expandable_error:nnn	<u>93</u>	
\\msg_line_context:	<u>807</u>	
\\msg_new:nnn	<u>806, 823</u>	
\\msg_new:nnnn	<u>791, 801, 808</u>	
\\msg_warning:nnnnnn	<u>529</u>	
N		
\\newcommand	<u>863, 864</u>	
\\NewDocumentCommand	<u>828, 829,</u>	
830, 831, 837, 839, 858, 868, 870, 873		
\\newenvironment	<u>14</u>	
\\NewExpandableDocumentCommand .	<u>875, 877</u>	
\\NewHook	<u>2,</u>	
2, 2, 4, 7, 7, 10, 11, 15, 828, 890, 892		
\\NewMirroredHookPair ..	<u>2, 7, 10, 828, 894</u>	
\\NewReversedHook .	<u>2, 2, 7, 10, 11, 828, 893</u>	
\\normalfont	<u>17</u>	
\\normalsize	<u>3</u>	
O		
or commands:		
\\or:	<u>339, 355</u>	
P		
prg commands:		
\\prg_new_conditional:Npnn	<u>208, 343, 758, 770, 776, 782</u>	
\\prg_new_protected_conditional:Npnn	<u>188, 275</u>	
\\prg_return_false: .	<u>192, 205, 216,</u>	
220, 223, 279, 348, 766, 774, 780, 787		
\\prg_return_true:	<u>203,</u>	
219, 279, 346, 765, 768, 773, 779, 785		
prop commands:		

`\prop_if_empty_p:N` 763
`\prop_if_exist:NTF` 778
`\prop_if_in:NnTF` ... 194, 197, 200, 218
`\prop_map_break:` 425, 650
`\prop_map_inline:Nn`
368, 413, 420, 422, 571, 596, 645, 647
`\prop_new:N` 31, 57, 283, 284, 400
`\prop_put:Nnn` 541, 552
`\prop_set_eq:NN` 391
`\prop_show:N` 42
`\providecommand` 899, 902

Q

quark internal commands:

`\s_hook_mark` 36,
99, 102, 105, 109, 112, 113, 175,
209, 228, 229, 233, 717, 723, 727, 735

R

`\relax` 44
`\RemoveFromHook` 3, 3, 839, 901
`\rmfamily` 17

S

scan commands:

`\scan_new:N` 36
`\scan_stop:` 184, 189
`\selectfont` 17, 18

seq commands:

`\seq_clear:N` 410
`\seq_clear_new:N` 418
`\seq_get:NNTF` 851
`\seq_gpop:NN` 850, 860
`\seq_gpush:Nn` 841, 844
`\seq_gput_right:Nn` 45
`\seq_map_inline:Nn` ... 362, 434, 452
`\seq_new:N` 28, 33, 403
`\seq_put_right:Nn` 416, 509, 516
`\seq_use:Nnnn` 569, 574
`\sffamily` 17
`\shipout` 17
`\ShowHook` 8, 10, 12, 865, 906
`\small` 3
`\space` 150
`\special` 17

str commands:

`\str_if_eq:nn` 32
`\str_if_eq:nnTF` 97,
211, 250, 562, 613, 679, 729, 794, 811
`\str_if_eq_p:nn` 215, 445

str internal commands:

`__str_if_eq:nn` 19, 23

T

TeX and L^AT_EX 2_ε commands:

`\@...hook` 21, 22
`\@begindocumenthook` 14, 21, 22
`\@currname` ... 5, 5, 22, 23, 48, 119, 121
`\@empty` 907, 908
`\@enddocumenthook` 22
`\@expl@@hook@curr@name@pop@@` ... 880
`\@expl@@hook@curr@name@push@@n` 880
`\@expl@@initialize@all@@` 880
`\@firstofone` 2
`\@gobble@AddToHook@args` ... 898, 899
`\@gobble@RemoveFromHook@arg` 901, 902
`\@kernel@after@{hookname}` 13
`\@kernel@before@{hookname}` 13
`\@onlypreamble` 872
`\@spaces` ... 594, 597, 600, 612, 617, 633
`\@end` 17
`\expand@font@defaults` 18
`\g@addto@macro` 21
`\on@line` 150, 378
`\protected` 43

tl commands:

`\c_novalue_tl` 22
`\tl_gclear:N` 41, 43, 77, 443, 707
`\tl_gput_left:Nn` 387
`\tl_gput_right:Nn` 33, 267, 389, 475, 708
`\tl_gremove_all:Nn` 29
`\tl_gremove_once:Nn` 28, 29, 35, 35, 272
`\tl_gset:Nn` 63, 198, 201,
313, 319, 325, 329, 331, 383, 707, 845
`\tl_gset_eq:NN` 852
`\tl_if_empty:N` 45
`\tl_if_empty:NNTF`
..... 73, 117, 119, 601, 704, 706
`\tl_if_empty:nTF` 91, 104, 107, 191, 231
`\tl_if_empty_p:N` 764
`\tl_if_empty_p:n` 214
`\tl_if_exist:N` 44
`\tl_if_exist:NNTF`
..... 71, 712, 721, 744, 752, 772
`\tl_if_in:NnTF` 277
`\tl_if_novalue:NNTF` 84
`\tl_new:N` 25, 26, 27,
29, 30, 32, 46, 49, 58, 285, 405, 406, 407
`\tl_set:Nn` 412, 417, 432,
433, 438, 439, 454, 461, 462, 507, 514
`\tl_set_eq:NN` 442, 465
`\tl_to_str:n` 150, 282, 597, 640
`\tl_trim_spaces_apply:nN` 86
`\tl_use:N` 573
`\ttfamily` 17

U	
use commands:	
\use:N	523, 524, 564
\use:n	288
\use:nn	494, 683
\use_i:nnn	32
\use_ii:nn	32
\use_iii:nn	32
\use_none:n	7, 43, 358, 374, 492
\use_none:nn	640
\UseHook	2, 5, 10, 12, 13, 863, 904
\UseOneTimeHook	2, 12, 863, 905
\usepackage	5, 17