tcolorbox

Manual for version 4.32 (2020/09/17)

Thomas F. Sturm

Cover code

```
% \usepackage{incgraph}
\begin{inctext}
\begin{tikzpicture}
\definecolorseries{boxcol}{rgb}{last}{blue}{red}
\resetcolorseries[28]{boxcol}
\coordinate (A) at (0,0); \coordinate (B) at (21,29.7);
\path[use as bounding box] (A) rectangle coordinate (C) (B);
\node[transform shape,xslant=0.7,rotate=-10,xshift=0cm] at (C) {%
  \begin{tcbraster}[raster columns=4,title=tcolorbox \version,
    fonttitle=\small\bfseries,raster width=50cm]
  \foreach \b in {1,...,28} {\begin{tcolorbox}[enhanced,
    watermark text=\thetcbrasternum,
    colframe=boxcol!30!white,
    colback=boxcol!25!white!30!white,
    colbacktitle=boxcol!!+!50!black!30!white,
    colupper=black!30!white]\lipsum[2]\end{tcolorbox}}
  \end{tcbraster}%
};
\node at (C) {%
  \begin{tcbitemize}[title=tcolorbox \version,fonttitle=\small\bfseries,
    enhanced jigsaw,opacityback=0.5,opacitybacktitle=0.75,
    halign=center,valign=center,arc=5mm,
    raster width=16cm,raster column skip=8mm,raster halign=center,
    raster force size=false,
    raster row 1/.style={height=6cm},
    raster row 2/.style={width=6cm,height=4cm},
    raster column 1/.style={flushright title,
      frame style={left color=yellow!50!black,right color=green!50!black},
      title style={left color=yellow!50!blue,right color=blue!50!green!50!black},
      interior style={left color=yellow!70,right color=green!70},
      underlay={\draw[line width=6mm,line cap=round,black!60]
        ([shift={(0.4,-0.15)}]frame.north east)
        --([shift={(0.4,0.15)}]frame.south east); }},
    raster column 2/.style={
      frame style={left color=green!50!black,right color=yellow!50!black},
      title style={left color=blue!50!green!50!black,right color=yellow!50!blue},
      interior style={left color=green!70,right color=yellow!70}}]
  \tcbitem[fontupper=\Huge\bfseries,sharp corners=east,
    underlay={\draw[line width=6mm,line cap=round,black!60]
      ([shift={(0.4,0.30)}]frame.north east)-- coordinate(A) +(0,0.2);
      \draw[line width=1mm,line cap=round,black!60](A) -- +(30:1.5cm);
      \draw[line width=1mm,line cap=round,black!60](A) -- +(150:1.5cm);}]
    tcolorbox
  \tcbitem[fontupper=\large\bfseries,sharp corners=west]
    Manual for\\ version\\ \version\\(\datum)
  \tcbitem[sharp corners=northeast]
  \tcbitem[sharp corners=northwest] Thomas F.~Sturm
  \end{tcbitemize}%
};
\end{tikzpicture}
\end{inctext}
```

The tcolorbox package

Manual for version 4.32 (2020/09/17)

Thomas F. Sturm[1]

https://www.ctan.org/pkg/tcolorbox

https://github.com/T-F-S/tcolorbox

Abstract

tcolorbox provides an environment for colored and framed text boxes with a heading line. Optionally, such a box can be split in an upper and a lower part. The package tcolorbox can be used for the setting of LaTeX examples where one part of the box displays the source code and the other part shows the output. Another common use case is the setting of theorems. The package supports saving and reuse of source code and text parts.

Contents

1 Introduction **8**
- 1.1 Installation . . . 8
- 1.2 Loading the Package . . . 8
- 1.3 Libraries . . . 9

2 Quick Reference **11**

3 Macros for Box Creation **12**

4 Option Keys **18**
- 4.1 Title . . . 18
- 4.2 Subtitle . . . 21
- 4.3 Upper Part . . . 22
- 4.4 Lower Part . . . 24
- 4.5 Colors and Fonts . . . 27
- 4.6 Text Alignment . . . 30
- 4.7 Geometry . . . 34
  - 4.7.1 Width . . . 34
  - 4.7.2 Rules . . . 35
  - 4.7.3 Arcs . . . 36
  - 4.7.4 Spacing . . . 39
  - 4.7.5 Size Shortcuts . . . 44
  - 4.7.6 Toggle Left and Right . . . 46
- 4.8 Corners . . . 48
- 4.9 Transparency . . . 51
- 4.10 Height Control . . . 53
- 4.11 Box Content Additions . . . 64
- 4.12 Overlays . . . 74

[1]Prof. Dr. Dr. Thomas F. Sturm, Institut für Mathematik und Informatik, Universität der Bundeswehr München, D-85577 Neubiberg, Germany; email: thomas.sturm@unibw.de

4.13 Floating Objects . . . 79
4.14 Embedding into the Surroundings . . . 81
4.15 Bounding Box . . . 85
4.15.1 Shifting Bounding Box Borders . . . 85
4.15.2 Box Alignment . . . 88
4.15.3 Toggle Enlargements . . . 89
4.15.4 Spread Box to Page Borders . . . 90
4.15.5 Box Extrusion . . . 92
4.16 Layered Boxes and Every Box Settings . . . 94
4.17 Capture Mode . . . 97
4.18 Text Characteristics . . . 98
4.19 Files . . . 99
4.20 `\tcbox` Specials . . . 99
4.21 Counters, Labels, and References . . . 101
4.22 Even and Odd Pages . . . 104
4.23 Externalization . . . 108
4.24 Miscellaneous . . . 109

5 Initialization Option Keys 111
5.1 Numbered Boxes . . . 111
5.2 Lists of `tcolorboxes` . . . 118

6 Side by Side 119
6.1 Basic Settings . . . 119
6.2 Advanced Settings from the LIB xparse Library . . . 125

7 Saving and Loading of Verbatim Texts 129

8 Recording 131
8.1 Macros . . . 131
8.2 Options . . . 131
8.3 Example: Exercises . . . 132
8.4 Example: Solutions . . . 135

9 Technical Overview and Customization 137
9.1 Skins and Drawing Engines . . . 137
9.2 Code Option Keys . . . 141
9.3 Subskins . . . 144
9.4 Drawing Scheme . . . 145
9.5 Color Names . . . 149
9.6 Useful Properties . . . 150

10 Library LIB skins 152
10.1 Style Option Keys . . . 152
10.2 Boxed Title Option Keys . . . 159
10.2.1 Boxed Title Placement . . . 159
10.2.2 Options for the Boxed Title Placement . . . 161
10.2.3 Options for the Boxed Title Box . . . 162
10.3 Watermark Option Keys . . . 169
10.4 Clip Environments . . . 176
10.5 Border Line Option Keys . . . 181
10.6 Shadow Option Keys . . . 186
10.6.1 Common Shadows and Halos . . . 186

10.6.2 Lifted Shadows . . . 191
10.6.3 Generic Shadows . . . 192
10.6.4 TikZ Shadows . . . 195
10.7 TikZ Picture Option Keys . . . 196
10.8 Underlay Option Keys . . . 199
10.9 Finish Option Keys . . . 201
10.10 Hyper Option Keys . . . 203
10.11 Jigsaw Skin Variants . . . 205
10.12 Draft Mode . . . 207
10.13 Skin Family "standard" . . . 209
10.14 Skin Family "enhanced" . . . 211
10.15 Skin Family "bicolor" . . . 224
10.16 Skin Family "tile" . . . 229
10.17 Skin Family "beamer" . . . 233
10.18 Skin Family "widget" . . . 238
10.19 Skin Family "empty" . . . 242
10.20 Skin "spartan" . . . 252
10.21 Skin "draft" . . . 253
10.22 Skin Family "freelance" . . . 255

11 Inclusion of Boxed Image Files **256**
11.1 Macros . . . 256
11.2 Option Keys . . . 259

12 TikZ Image and Picture Fill Extensions; Auxiliary Macros **261**
12.1 Fill Plain . . . 261
12.2 Fill Stretch . . . 262
12.3 Fill Overzoom . . . 263
12.4 Fill Zoom . . . 264
12.5 Fill Shrink . . . 265
12.6 Fill Tile . . . 266
12.7 Filling Options . . . 267
12.8 Straightening of the Arcs . . . 268
12.9 Extracting Node Dimensions . . . 269
12.10 Hyper Nodes . . . 269

13 Beamer Support **270**

14 Library LIB vignette **276**
14.1 Vignette Drawing . . . 276
14.2 Generic Geometry Settings . . . 277
14.3 Generic Color and Style Settings . . . 279
14.4 Generic Fading Settings . . . 281
14.5 Vignette as Underlay . . . 283
14.6 Vignette as Finish . . . 285

15 Library LIB raster **288**
15.1 Concept of Rasters . . . 288
15.2 Macros of the Library . . . 290
15.3 Option Keys of the Library . . . 294
15.4 Adding Styles for Specific Boxes . . . 300
15.5 Combining Columns or Rows . . . 302

15.6 Rasters inside Rasters . . . 305
15.6.1 Raster Setup . . . 305
15.6.2 Placing Spaces . . . 306

16 Libraries LIB listings, LIB listingsutf8, and LIB minted . . . 310
16.1 Loading the Libraries . . . 310
16.1.1 Loading LIB listings . . . 310
16.1.2 Loading LIB listingsutf8 . . . 310
16.1.3 Loading LIB minted . . . 311
16.2 Common Macros of the Libraries . . . 311
16.3 Option Keys of the LIB listings Library . . . 317
16.4 Option Keys of the LIB listingsutf8 Library . . . 319
16.5 Option Keys of the LIB minted Library . . . 320
16.6 Common Option Keys of all Libraries . . . 322
16.7 Option Keys for Processing and Full Document Examples . . . 332
16.8 Creation of LaTeX Tutorials . . . 339
16.9 Creation of LaTeX Exercises . . . 346
16.10 List of Exercises . . . 349
16.11 Solutions for the given LaTeX Exercises . . . 350

17 Library LIB theorems . . . 352
17.1 Macros of the Library . . . 352
17.2 Option Keys of the Library . . . 356
17.3 Examples for Definitions and Theorems . . . 371
17.4 Using other theorem environments with `tcolorbox` . . . 376

18 Library LIB breakable . . . 377
18.1 Technical Overview . . . 377
18.2 Limitations and Known Bugs . . . 378
18.3 Main Option Keys . . . 379
18.4 Option Keys for the Break Appearance . . . 383
18.5 Extra Options for Partial Boxes . . . 385
18.6 Breakable boxes and the `multicol` package . . . 388
18.7 Break Point Insertion . . . 391
18.8 Break Sequence for the Skins . . . 392
18.9 Break by Hand (Faked Break) . . . 401

19 Library LIB magazine . . . 402
19.1 Creation and Resetting of Box Arrays . . . 402
19.2 Storing Content . . . 403
19.3 Retrieving Content . . . 405
19.4 Box Dimensions . . . 408
19.5 Leaflet Example . . . 410

20 Library LIB poster . . . 412
20.1 Overview . . . 412
20.2 Main Poster Environment . . . 413
20.3 Poster Settings . . . 415
20.4 Coverage . . . 416
20.5 Common Box Settings . . . 417
20.6 Font Scaling . . . 417
20.7 Box Placement . . . 418

21 Library fitting **426**
21.1 Macros of the Library . . . 426
21.2 Option Keys of the Library . . . 429

22 Library hooks **438**
22.1 Concept of Hooks . . . 438
22.2 Box Content Additions . . . 439
22.3 Embedding into the Surroundings . . . 440
22.4 Overlays . . . 441
22.5 Watermarks . . . 443
22.6 Underlays . . . 445
22.7 Finishes . . . 446
22.8 Skin Code . . . 446
22.9 Extras . . . 448
22.10 Listings . . . 448

23 Library xparse **449**
23.1 Option Keys . . . 449
23.2 Producing `tcolorbox` Environments and Commands . . . 451
23.3 Producing `tcbox` Commands . . . 454
23.4 Producing `tcblisting` Environments . . . 457
23.5 Producing `tcbinputlisting` Commands . . . 459
23.6 Producing `tboxfit` Commands . . . 460

24 Library external **462**
24.1 Preparation of a Document for Externalization . . . 463
24.2 Marking Externalization Snippets . . . 464
24.3 Customization . . . 469
24.4 Troubleshooting and FAQ . . . 473

25 Library documentation **474**
25.1 Macros of the Library . . . 474
25.2 Entry Content Option Keys . . . 488
25.3 Entry Customization Option Keys . . . 491
25.4 General Customization Option Keys . . . 496
25.5 Language Option Keys . . . 499
25.6 Predefined Colors of the Library . . . 500

A Picture Credits **501**

References **502**

Index **504**

Contents

1 Introduction

The package originates from the first edition of my book «*LaTeX– Einführung in das Textsatzsystem*» [18] in about 2006. For the LaTeX examples and tutorials given there, I wanted to have accentuated and colored boxes to display source code and compiled text in combination. Since, in my opinion, this type of boxes is also quite useful to highlight definitions and theorems, I applied them for my lecture notes in mathematics [19–21] as well. With this package, you are invited to apply these boxes for similar projects.

The breaking news for version 2.00 was the support for breakable boxes. This feature allows new applications of the package without affecting the core package too much if you do not need boxes to break automatically. With version 2.20, the often requested "side by side" mode for listings has been added. With version 3.00, boxed titles are introduced together with improved customization options for overlays, underlays, finishes, and own code extensions.

Since the first public release in 2011, I received a lot of feedback from all over the world. I want to thank all who wrote me for supporting this package by sending bug reports and ideas for new or better features.

1.1 Installation

Typically, `tcolorbox` will be installed as part of a major LaTeX distribution and there is nothing special to do for a user.

If you intend to make a local installation *by hand*, see the `README` file of the `tcolorbox` package for some hints. The short story is: you have to install not only `tcolorbox.sty`, but also all `*.code.tex` files in the local `texmf` tree.

1.2 Loading the Package

The base package `tcolorbox` loads the packages `pgf` [22], `verbatim` [17], `etoolbox` [7], and `environ` [16]. `tcolorbox` itself is loaded in the usual manner in the preamble:

```
\usepackage{tcolorbox}
```

The package takes option keys in the key-value syntax. Alternatively, you may use these keys later in the preamble with `\tcbuselibrary` → P. 9 (see there). For example, the key to typeset listings is:

```
\usepackage[listings]{tcolorbox}
```

1.3 Libraries

The base package `tcolorbox` is extendable by program libraries. This is done by using option keys while loading the package or inside the preamble by applying the following macro with the same set of keys.

`\tcbuselibrary{`⟨*key list*⟩`}`

Loads the libraries given by the ⟨*key list*⟩.

```
\tcbuselibrary{listings,theorems}
```

The following keys are used inside `\tcbuselibrary` respectively `\usepackage` without the key tree path `/tcb/library/`.

`/tcb/library/skins` (LIB skins)

Loads the package `tikz` [22] and provides additional styles (skins) for the appearance of the colored boxes; see Section 10 from page 152.

`/tcb/library/vignette` (LIB vignette)

Provides code for more ornamental; see Section 14 from page 276.

`/tcb/library/raster` (LIB raster)

Provides additional macros and options for typesetting multiple boxes arranged in a kind of raster; see Section 15 from page 288.

`/tcb/library/listings` (LIB listings)

Loads the package `listings` [6] and provides additional macros for typesetting listings which are described in Section 16 from page 310.

`/tcb/library/listingsutf8` (LIB listingsutf8)

Loads the packages `listings` [6] and `listingsutf8` [11] for UTF-8 support. This is a variant of the library LIB listings and is described in Section 16 from page 310.

`/tcb/library/minted` (LIB minted)

Loads the package `minted` [12] to typeset listings with the `Pygments` [14] tool, also see Section 16 on page 310.

`/tcb/library/theorems` (LIB theorems)

Provides additional macros for typesetting theorems which are described in Section 17 from page 352.

`/tcb/library/breakable` (LIB breakable)

Provides support for automatic box breaking from one page to another; see Section 18 on page 377.

`/tcb/library/magazine` (LIB magazine)

Provides support for storing broken box parts to be used later or in interchanged order, Section 19 on page 402.

`/tcb/library/poster` (LIB poster)

Provides support for creating posters, Section 20 on page 412.

`/tcb/library/fitting` (LIB fitting)

Provides support for font size adaption of the box content to the box dimensions; see Section 21 from page 426.

`/tcb/library/hooks` (LIB hooks)

Extends several option keys to “hookable” keys; see Section 22 from page 438.

/tcb/library/xparse (LIB xparse)

Provides document command production with `xparse` for `tcolorbox`; see Section 23 from page 449.

/tcb/library/external (LIB external)

Provides externalization support for stand-alone document snippets, see Section 24 on page 462.

/tcb/library/documentation (LIB documentation)

Provides additional macros for typesetting LaTeX documentations which are described in Section 25 from page 474.

/tcb/library/many (style, no value)

Loads the libraries LIB skins, LIB breakable, LIB raster, LIB hooks, LIB theorems, LIB fitting, and LIB xparse. Use this shortcut, if you want to use all features of `tcolorbox` with exception of typesetting listings and using the specialized LIB documentation library.

/tcb/library/most (style, no value)

Loads all libraries except LIB minted and LIB documentation. Use this shortcut, if you want to use all features of `tcolorbox` with exception of using the `minted` package and using the specialized LIB documentation library.

/tcb/library/all (style, no value)

Loads all libraries. Use this shortcut only, if you intend to use the LIB documentation library.




/tcb/before → P. 81, /tcb/before skip → P. 83
tcolorbox
/tcb/width → P. 34
/tcb/height → P. 53
/tcb/left skip → P. 84
/tcb/grow to left by → P. 87
/tcb/right skip → P. 84
/tcb/grow to right by → P. 87
/tcb/after → P. 81, /tcb/after skip → P. 83


/tcb/toprule → P. 35
/tcb/toptitle → P. 42
/tcb/bottomtitle → P. 43
/tcb/titlerule → P. 36
/tcb/top → P. 42
/tcb/boxsep → P. 39
/tcb/boxsep → P. 39
/tcb/boxsep → P. 39
tcolorbox
/tcb/boxsep → P. 39
/tcb/left → P. 39
/tcb/right → P. 40
/tcb/boxsep → P. 39
/tcb/leftrule → P. 35
/tcb/rightrule → P. 35
/tcb/middle → P. 43
/tcb/middle → P. 43
/tcb/boxsep → P. 39
/tcb/boxsep → P. 39
/tcb/bottom → P. 43
/tcb/bottomrule → P. 35
/tcb/boxsep → P. 39

3 Macros for Box Creation

```
\begin{tcolorbox}[⟨options⟩]
  ⟨environment content⟩
\end{tcolorbox}
```

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts. The appearance of this box is controlled by numerous options. In the most simple case the source code

```
\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

creates the following compiled text box:

This is a **tcolorbox**.

The text content of the box can be divided in an upper and a lower part by the command `\tcblower`. Visually, both parts are separated by a line. For example:

```
\begin{tcolorbox}
This is another \textbf{tcolorbox}.
\tcblower
Here, you see the lower part of the box.
\end{tcolorbox}
```

This code gives the following box:

This is another **tcolorbox**.

Here, you see the lower part of the box.

The ⟨*options*⟩ control the appearance and several functions of the boxes, see Section 4 on page 18 for the complete list. A quick example is given here:

```
\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black,title=My nice heading]
This is another \textbf{tcolorbox}.
\tcblower
Here, you see the lower part of the box.
\end{tcolorbox}
```

My nice heading

This is another **tcolorbox**.

Here, you see the lower part of the box.

`\tcblower`

Used inside `tcolorbox` to separate the upper box part from the optional lower box part. The upper and the lower part are treated as separate functional units. If you only want to draw a line, see `\tcbline` → P. 214.

\tcbset{⟨*options*⟩}

Sets options for every following tcolorbox→ P. 12 inside the current TEX group. By default, this does not apply to nested boxes, see Section 4.16 on page 94.
For example, the colors of the boxes may be defined for the whole document by this:

```
\tcbset{colback=red!5!white,colframe=red!75!black}
```

\tcbsetforeverylayer{⟨*options*⟩}

Sets options for every following tcolorbox→ P. 12 inside the current TEX group. In contrast to \tcbset, this does also apply to nested boxes, see Section 4.16 on page 94. Technically, the ⟨*options*⟩ are appended to the default values for every tcolorbox which are applied by /tcb/reset→ P. 109.
You should not use this macro, if you are not completely sure that you want to have the ⟨*options*⟩ also for boxes in boxes (in boxes in boxes . . .).

```
\tcbset{colback=green!10!white}
\tcbsetforeverylayer{colframe=red!75!black}

\begin{tcolorbox}[title=All options for this box]
  This is a tcolorbox.\par\medskip
  \begin{tcolorbox}[title=Nested box]
    Note that this nested box has a red frame but no green background.
  \end{tcolorbox}
\end{tcolorbox}
\bigskip

\begin{tcolorbox}[reset]
  Options given with |\tcbsetforeverylayer| survive a |reset|.
\end{tcolorbox}
```

All options for this box

This is a tcolorbox.

Nested box

Note that this nested box has a red frame but no green background.

Options given with \tcbsetforeverylayer survive a reset.

`\tcbox[⟨options⟩]{⟨box content⟩}`

Creates a colored box which is fitted to the width of the given ⟨*box content*⟩. In principle, most ⟨*options*⟩ for a `tcolorbox` → P. 12 can be used for `\tcbox` with some restrictions. A `\tcbox` cannot have a lower part and cannot be broken.

```
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
        fonttitle=\bfseries,nobeforeafter,center title}

Text \tcbox[tcbox raise base]{Hello World}\hfill
%
\tcbox[left=0mm,right=0mm,top=0mm,bottom=0mm,boxsep=0mm,
  toptitle=0.5mm,bottomtitle=0.5mm,title=My table]{%
  \arrayrulecolor{blue!50!black}\renewcommand{\arraystretch}{1.2}%
  \begin{tabular}{r|c|l}
  One    & Two     & Three \\\hline\hline
  Men    & Mice    & Lions \\\hline
  Upper & Middle & Lower
  \end{tabular}}\hfill
%
\tcbox[colback=blue!85!black,
  left=0mm,right=0mm,top=0mm,bottom=0mm,boxsep=1mm,arc=0mm,boxrule=0.5pt,
  title=My picture]{%
  \includegraphics[width=5cm]{Basilica_5.png}}
```

Text Hello World

My table

One	Two	Three
Men	Mice	Lions
Upper	Middle	Lower

My picture



```
% \usepackage{tikz}
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
        fonttitle=\bfseries,center title}

% Fixed width box
\begin{tcolorbox}Hello\\World!\end{tcolorbox}

% Fitted width box (like hbox or makebox)
\tcbox{Hello\\World!}

% Fitted width box (using a \tikzname\  node)
\tcbox[tikznode]{Hello\\World!}
```

Hello
World!

HelloWorld!

Hello
World!

See Section 23.2 on page 451 and Section 23.3 on page 454 for more elaborate methods to create new environments and commands.

\newtcolorbox[⟨*init options*⟩]{⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Creates a new environment ⟨*name*⟩ based on `tcolorbox`→ P. 12. Basically, `\newtcolorbox` operates like `\newenvironment`. This means, the new environment ⟨*name*⟩ optionally takes ⟨*number*⟩ arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying `tcolorbox`. Note that `/tcb/savedelimiter`→ P. 26 is set to the given ⟨*name*⟩ automatically. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.

```
\newtcolorbox{mybox}{colback=red!5!white,
  colframe=red!75!black}

\begin{mybox}
This is my own box.
\end{mybox}
```

This is my own box.

```
\newtcolorbox{mybox}[1]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  title=#1}

\begin{mybox}{Hello there}
This is my own box with a mandatory title.
\end{mybox}
```

Hello there

This is my own box with a mandatory title.

```
\newtcolorbox{mybox}[2][]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  colbacktitle=red!85!black,enhanced,
attach boxed title to top center={yshift=-2mm},
  title=#2,#1}

\begin{mybox}[colback=yellow]{Hello there}
This is my own box with a mandatory title
and options.
\end{mybox}
```

Hello there

This is my own box with a mandatory title and options.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Examp.~\thetcbcounter: #2,#1}
```

```
\begin{pabox}[colback=yellow]{Hello there}
This is my own box with a mandatory
numbered title and options.
\end{pabox}
```

Examp. 3.1: Hello there

This is my own box with a mandatory numbered title and options.

\renewtcolorbox[⟨*init options*⟩]{⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Operates like `\newtcolorbox`, but based on `\renewenvironment` instead of `\newenvironment`. An existing environment is redefined.

`\newtcbox[⟨init options⟩]{\⟨name⟩}[⟨number⟩][⟨default⟩]{⟨options⟩}`

Creates a new macro \⟨*name*⟩ based on `\tcbox` → P. 14. Basically, `\newtcbox` operates like `\newcommand`. The new macro \⟨*name*⟩ optionally takes ⟨*number*⟩+1 arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying `tcbox`. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.

```
\newtcbox{\mybox}{colback=red!5!white,
  colframe=red!75!black}

\mybox{This is my own box.}
```

This is my own box.

```
\newtcbox{\mybox}[1]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  title=#1}

\mybox{Hello there}{This is my own box.}
```

Hello there

This is my own box.

```
\newtcbox{\mybox}[2][]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  title=#2,#1}

\mybox[colback=yellow]{Hello there}%
  {This is my own box.}
```

Hello there

This is my own box.

Definition in the preamble:

```
% counter from previous example
\newtcbox[use counter from=pabox]{\pbbox}[2][]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=(\thetcbcounter) #2,#1}
```

```
\pbbox[colback=yellow]{Hello there}%
  {This is my own box.}
```

(3.2) Hello there

This is my own box.

```
\newtcbox{\mybox}[1][red]{on line,
  arc=0pt,outer arc=0pt,colback=#1!10!white,colframe=#1!50!black,
  boxsep=0pt,left=1pt,right=1pt,top=2pt,bottom=2pt,
  boxrule=0pt,bottomrule=1pt,toprule=1pt}
\newtcbox{\xmybox}[1][red]{on line,
  arc=7pt,colback=#1!10!white,colframe=#1!50!black,
  before upper={\rule[-3pt]{0pt}{10pt}},boxrule=1pt,
  boxsep=0pt,left=6pt,right=6pt,top=2pt,bottom=2pt}

The \mybox[green]{quick} brown \mybox{fox} \mybox[blue]{jumps} over the
\mybox[green]{lazy} \mybox{dog}.\par
The \xmybox[green]{quick} brown \xmybox{fox} \xmybox[blue]{jumps} over the
\xmybox[green]{lazy} \xmybox{dog}.
```

The quick brown fox jumps over the lazy dog.
The quick brown fox jumps over the lazy dog.

`\renewtcbox[⟨init options⟩]{\⟨name⟩}[⟨number⟩][⟨default⟩]{⟨options⟩}`

Operates like `\newtcbox`, but based on `\renewcommand` instead of `\newcommand`. An existing macro is redefined.

N 2014-10-20 **\tcolorboxenvironment{⟨*name*⟩}{⟨*options*⟩}**

An existing environment ⟨*name*⟩ is redefined to be boxed inside a `tcolorbox` with the given ⟨*options*⟩.

```
% tcbuselibrary{skins}
\newenvironment{myitemize}{%
  \begin{itemize}}{\end{itemize}}

\tcolorboxenvironment{myitemize}{blanker,
  before skip=6pt,after skip=6pt,
  borderline west={3mm}{0pt}{red}}

Some text.
\begin{myitemize}
\item Alpha
\item Beta
\item Gamma
\end{myitemize}
More text.
```

Some text.

- Alpha
- Beta
- Gamma

More text.

See further examples in Section 17.4 on page 376.

4 Option Keys

For the ⟨*options*⟩ in `tcolorbox`→ P. 12 respectively `\tcbset`→ P. 13 the following `pgf` keys can be applied. The key tree path `/tcb/` is not to be used inside these macros. It is easy to add your own style keys using the syntax for `pgf` keys, see [18, 22] or the examples starting from page 339.

4.1 Title

`/tcb/title=`⟨*text*⟩ (no default, initially empty)

Creates a heading line with ⟨*text*⟩ as content.

```
\begin{tcolorbox}[title=My heading line]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My heading line

This is a **tcolorbox**.

`/tcb/notitle` (no value, initially set)

Removes the title line if set before.

`/tcb/adjusted title=`⟨*text*⟩ (style, no default, initially unset)

Creates a heading line with ⟨*text*⟩ as content. The minimal height of this line is adjusted to fit the text given by `/tcb/adjust text`. This option makes sense for single line headings if boxes are set side by side with equal height. Note that it is very easy to trick this adjustment.

```
\tcbset{colback=White,arc=0mm,width=(\linewidth-4pt)/4,
equal height group=AT,before=,after=\hfill,fonttitle=\bfseries}

The following titles are not adjusted:\\
\foreach \n in {xxx,ggg,AAA,\"Agypten}
{\begin{tcolorbox}[title=\n,colframe=red!75!black]
  Some content.\end{tcolorbox}}
Now, we try again with adjusted titles:\\
\foreach \n in {xxx,ggg,AAA,\"Agypten}
{\begin{tcolorbox}[adjusted title=\n,colframe=blue!75!black]
  Some content.\end{tcolorbox}}
```

The following titles are not adjusted:

xxx	ggg	AAA	Ägypten
Some content.	Some content.	Some content.	Some content.

Now, we try again with adjusted titles:

xxx	ggg	AAA	Ägypten
Some content.	Some content.	Some content.	Some content.

`/tcb/adjust text=`⟨*text*⟩ (no default, initially `Äpgjy`)

This sets the reference text for `/tcb/adjusted title`. If your texts never exceed "Äpgjy" in depth and height you don't need to care about this option.

N 2014-11-24 **/tcb/squeezed title=**⟨*text*⟩ (style, no default, initially unset)

Creates a single heading line with ⟨*text*⟩ as content. If the ⟨*text*⟩ is longer than the available space, the text is squeezed to fit into the available space.

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster columns=3,raster equal height,
  colframe=red!75!black,colback=red!5!white,fonttitle=\bfseries]
\tcbitem[squeezed title={Short title}]
  First box
\tcbitem[squeezed title={This is a very very long title}]
  Second box
\tcbitem[squeezed title={This title is clearly to long for this application}]
  Third box
\end{tcbitemize}
```

Short title
First box

This is a very very long title
Second box

This title is clearly to long for this application
Third box

N 2014-11-24 **/tcb/squeezed title*=**⟨*text*⟩ (style, no default, initially unset)

This is a combination of **/tcb/adjusted title** →P. 18 and **/tcb/squeezed title**.

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster columns=3,raster equal height,
  colframe=red!75!black,colback=red!5!white,fonttitle=\bfseries]
\tcbitem[squeezed title*={Short title}]
  First box
\tcbitem[squeezed title*={This is a very very long title}]
  Second box
\tcbitem[squeezed title*={This title is clearly to long for this application}]
  Third box
\end{tcbitemize}
```

Short title
First box

This is a very very long title
Second box

This title is clearly to long for this application
Third box

N 2019-03-01 **/tcb/titlebox=**⟨*mode*⟩ (no default, initially `visible`)

Controls the treatment of the title part of the box. Feasible values for ⟨*mode*⟩ are:

- `visible`: usual type setting of the title box,
- `invisible`: empty space instead of the title contents.

```
\begin{tcolorbox}[title=My invisible title,
  titlebox=invisible]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/detach title (no value)

Detaches the title from its normal position. The text of the title is stored into **\tcbtitletext** and the formatted title is available by **\tcbtitle**. The main application is to move the title from its usual place to another one.

```
\newtcolorbox{mybox}[2][]{colbacktitle=red!10!white,
  colback=blue!10!white,coltitle=red!70!black,
  title={#2},fonttitle=\bfseries,#1}

\begin{mybox}{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
\begin{mybox}[detach title,before upper={\tcbtitle\quad}]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
\begin{mybox}[detach title,after upper={\par\hfill\tcbtitle}]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

My title

This is a **tcolorbox**.

My title This is a **tcolorbox**.

This is a **tcolorbox**.

My title

/tcb/attach title (no value)

Attaches the title to its normal position. This option is used to reverse **/tcb/detach title**.

U 2015-07-08 **/tcb/attach title to upper=**⟨*text*⟩ (style, default empty, initially unset)

Attaches the title to the begin of the upper part of the box content. The optional ⟨*text*⟩ is set between the formatted title and the box content.

```
\newtcolorbox{mybox}[2][]{colbacktitle=red!10!white,
  colback=blue!10!white,coltitle=red!70!black,
  title={#2},fonttitle=\bfseries,#1}

\begin{mybox}[attach title to upper={\ ---\ }]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
\begin{mybox}[attach title to upper,after title={:\ }]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

My title — This is a **tcolorbox**.

My title: This is a **tcolorbox**.

! More title options are documented in Section 4.11 on page 64 and Section 10.2 on page 159.

4.2 Subtitle

Inside the box content, one or more subtitles can be added. In general, a subtitle is a further tcolorbox→ P. 12 which inherits some color and geometry options from the enclosing box. It may be customized just like any other tcolorbox→ P. 12.

N 2014-10-10 **\tcbsubtitle**[⟨*options*⟩]{⟨*text*⟩}

Used inside a tcolorbox→ P. 12 to add a subtitle box with the given ⟨*text*⟩. This is an independent tcolorbox→ P. 12 which is formatted by several inherited properties of the enclosing box, by further settings from /tcb/subtitle style, and by the given ⟨*options*⟩.

```
\begin{tcolorbox}[title=My title,
    colback=red!5!white,
    colframe=red!75!black,
    fonttitle=\bfseries]
  This is a \textbf{tcolorbox}.
\tcbsubtitle[before skip=\baselineskip]%
  {My subtitle}
  Further text.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My subtitle

Further text.

```
\begin{tcolorbox}[title=My title,
    colback=red!5!white,
    colframe=red!75!black,
    colbacktitle=yellow!50!red,
    coltitle=red!25!black,
    fonttitle=\bfseries]
  This is a \textbf{tcolorbox}.
\tcbsubtitle[before skip=\baselineskip]%
  {My subtitle}
  Further text.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My subtitle

Further text.

N 2014-10-10 **/tcb/subtitle style**=⟨*options*⟩ (no default, initially empty)

Adds tcolorbox ⟨*options*⟩ to the settings for \tcbsubtitle.

```
\begin{tcolorbox}[title=My title,
  colback=red!5!white,
  colframe=red!75!black,
  colbacktitle=yellow!50!red,
  coltitle=red!25!black,
  fonttitle=\bfseries,
  subtitle style={boxrule=0.4pt,
    colback=yellow!50!red!25!white} ]
  This is a \textbf{tcolorbox}.
\tcbsubtitle{My subtitle}
  Further text.
\tcbsubtitle{Second subtitle}
  Further text.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My subtitle

Further text.

Second subtitle

Further text.

4.3 Upper Part

The text content of a tcolorbox→ P. 12 may be parted into a mandatory *upper part* and an optional *lower part*. These parts are separated by \tcblower→ P. 12. If there is no \tcblower→ P. 12 present, there is no *lower part* and the *upper part* forms the complete text content.

N 2015-01-06 **/tcb/upperbox=**⟨*mode*⟩ (no default, initially visible)

Controls the treatment of the upper part of the box. If there is no lower part, this is the complete text content. Feasible values for ⟨*mode*⟩ are:

- **visible**: usual type setting of the upper part,
- **invisible**: empty space instead of the upper part contents.

```
\begin{tcolorbox}[upperbox=invisible,colback=white]
This is a \textbf{tcolorbox} (but invisible).
\end{tcolorbox}

\bigskip

\begin{tcolorbox}[upperbox=invisible,colback=white]
This is a \textbf{tcolorbox} (but invisible).
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is the lower part.

N 2015-01-06 U 2019-03-01 **/tcb/visible** (style, no value)

Shortcut for setting /tcb/upperbox, /tcb/lowerbox→ P. 24, and /tcb/titlebox→ P. 19 to be **visible**.

N 2015-01-06 U 2019-03-01 **/tcb/invisible** (style, no value)

Shortcut for setting /tcb/upperbox, /tcb/lowerbox→ P. 24, and /tcb/titlebox→ P. 19 to be **invisible**.

```
\begin{tcolorbox}[invisible]
This is a \textbf{tcolorbox} (but invisible).
\end{tcolorbox}
```

N 2015-05-04 **/tcb/saveto=**⟨*file name*⟩ (no default, initially empty)

Saves the content of the box into a file for an optional later usage. This is the counterpart of /tcb/savelowerto → P. 24, but is saves not only the upper part but the whole content. If a lower part is present, it is also saved including \tcblower → P. 12.

> ! This option cannot be combined with /tcb/savelowerto → P. 24.

```
\begin{tcolorbox}[invisible,saveto=\jobname_mysave1.tex,colback=white]
This is a \textbf{tcolorbox} which seems to be empty.
The content is saved for later usage.
\end{tcolorbox}

Now, we load the saved text:\\
\input{\jobname_mysave1.tex}
```

Now, we load the saved text:
This is a **tcolorbox** which seems to be empty. The content is saved for later usage.

```
\begin{tcolorbox}[saveto=\jobname_mysave2.tex]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}

Now, we load the saved text:
\begin{tcolorbox}[colframe=red,colback=red!10,
  coltitle=black,colbacktitle=red!20,sidebyside,
  title=Here we see the saved content including the lower part]
\input{\jobname_mysave2.tex}
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

Now, we load the saved text:

Here we see the saved content including the lower part

This is a **tcolorbox**. | This is the lower part.

4.4 Lower Part

/tcb/lowerbox=⟨*mode*⟩ (no default, initially `visible`)

Controls the treatment of the lower part of the box. Feasible values for ⟨*mode*⟩ are:

- `visible`: usual type setting of the lower part,
- `invisible`: empty space instead of the lower part contents,
- `ignored`: the lower part is not used (here).

The last two values are usually applied in connection with `savelowerto`.

```
\begin{tcolorbox}[lowerbox=invisible,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part (but invisible).
\end{tcolorbox}

\begin{tcolorbox}[lowerbox=ignored,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part (but ignored).
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

U 2014-11-28 **/tcb/savelowerto=**⟨*file name*⟩ (no default, initially empty)

Saves the content of the lower part into a file for an optional later usage.

```
\begin{tcolorbox}[lowerbox=invisible,savelowerto=\jobname_bspsave.tex,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part which may be quite complex:
$\displaystyle f(x)=\frac{1+x^2}{1-x^2}$.
\end{tcolorbox}

Now, we load the saved text:\\
\input{\jobname_bspsave.tex}
```

This is a **tcolorbox**.

Now, we load the saved text:

This is the lower part which may be quite complex: $f(x)=\dfrac{1+x^2}{1-x^2}$.

/tcb/lower separated=true|false (default `true`, initially `true`)

If set to `true`, the lower part is visually separated from the upper part. It depends on the chosen skin how the visualization of the separation is done.

```
% \tcbuselibrary{skins,raster}
\begin{tcbraster}[colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,fontlower=\itshape]
%
\begin{tcolorbox}[title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[sidebyside,title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[sidebyside,title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[beamer,title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[beamer,title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\end{tcbraster}
```

Lower separated

This is the upper part.

This is the lower part.

Lower not separated

This is the upper part.

This is the lower part.

Lower separated

This is the upper part.

This is the lower part.

Lower not separated

This is the upper part.

This is the lower part.

Lower separated

This is the upper part.

This is the lower part.

Lower not separated

This is the upper part.

This is the lower part.

/tcb/savedelimiter=⟨*name*⟩ (no default, initially `tcolorbox`)

Used in connection with new environment definitions which extend `tcolorbox` and use or allow the option `savelowerto`. To catch the end of the new box environment ⟨*name*⟩ has to be the name of this environment. Additionally, the environment definition has to use `\tcolorbox` instead of `\begin{tcolorbox}` and `\endtcolorbox` instead of `\end{tcolorbox}`.

```
\newenvironment{mybox}[1]{%
  \tcolorbox[savedelimiter=mybox,
             savelowerto=\jobname_bspsave2.tex,lowerbox=ignored,
             colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
             title=#1]}%
  {\endtcolorbox}

\begin{mybox}{My Example}
Upper part.
\tcblower
Saved lower part!
\end{mybox}

Now, the saved part is used:
\begin{tcolorbox}[colback=green!5]
\input{\jobname_bspsave2.tex}
\end{tcolorbox}
```

My Example

Upper part.

Now, the saved part is used:

Saved lower part!

The `savedelimiter` is used implicitely with `\newtcolorbox` → P. 15 which allows a more convenient usage:

```
\newtcolorbox{mybox}[1]{%
             savelowerto=\jobname_bspsave2.tex,lowerbox=ignored,
             colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
             title=#1}%

\begin{mybox}{My Example}
Upper part.
\tcblower
Saved lower part!
\end{mybox}

Now, the saved part is used:
\begin{tcolorbox}[colback=green!5]
\input{\jobname_bspsave2.tex}
\end{tcolorbox}
```

My Example

Upper part.

Now, the saved part is used:

Saved lower part!

4.5 Colors and Fonts

/tcb/colframe=⟨*color*⟩ (no default, initially `black!75!white`)

Sets the frame ⟨*color*⟩ of the box.

```
\begin{tcolorbox}[colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/colback=⟨*color*⟩ (no default, initially `black!5!white`)

Sets the background ⟨*color*⟩ of the box.

```
\begin{tcolorbox}[colback=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/title filled=true|false (default `true`, initially `false`)

Switches the drawing of the title background according to the given value. This option is set to `true` automatically by `/tcb/colbacktitle`, `/tcb/opacitybacktitle`→ P. 51, and `/tcb/title style`→ P. 155, and `/tcb/title code`→ P. 143.

```
\begin{tcolorbox}[title=My title,title filled]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[title=My title,
  title filled=false]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My title

This is a **tcolorbox**.

/tcb/colbacktitle=⟨*color*⟩ (no default, initially `black!50!white`)

Sets the background ⟨*color*⟩ of the title area of the box.

```
\begin{tcolorbox}[colbacktitle=red!50!white,
  title=My title,coltitle=black,
  fonttitle=\bfseries]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/colupper=⟨*color*⟩ (no default, initially `black`)

Sets the text ⟨*color*⟩ of the upper part.

```
\begin{tcolorbox}[colupper=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/collower=⟨*color*⟩ (no default, initially `black`)

Sets the text ⟨*color*⟩ of the lower part.

```
\begin{tcolorbox}[collower=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/coltext=⟨*color*⟩ (style, no default, initially `black`)

Sets the text ⟨*color*⟩ of the box. This is an abbreviation for setting `colupper` and `collower` to the same value.

```
\begin{tcolorbox}[coltext=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/coltitle=⟨*color*⟩ (no default, initially `white`)

Sets the title text ⟨*color*⟩ of the box.

```
\begin{tcolorbox}[coltitle=red!75!black,
  colbacktitle=black!10!white,title=Test]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Test

This is a **tcolorbox**.

/tcb/fontupper=⟨*text*⟩ (no default, initially empty)

Sets ⟨*text*⟩ before the content of the upper part (e. g. font settings).

```
\begin{tcolorbox}[fontupper=Hello!~\sffamily]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Hello! This is a **tcolorbox**.

/tcb/fontlower=⟨*text*⟩ (no default, initially empty)

Sets ⟨*text*⟩ before the content of the lower part (e. g. font settings).

```
\begin{tcolorbox}[fontlower=\sffamily\bfseries]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/fonttitle=⟨*text*⟩ (no default, initially empty)

Sets ⟨*text*⟩ before the content of the title text (e. g. font settings).

```
\begin{tcolorbox}[fonttitle=\sffamily\bfseries\large,title=Hello]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Hello

This is a **tcolorbox**.

! More color options are provided by using skins documented in Section 10 from page 152.

4.6 Text Alignment

N 2015-05-07 **/tcb/halign=**⟨*alignment*⟩ (no default, initially `justify`)

If there is no lower part, `halign` determines the horizontal ⟨*alignment*⟩ of the text content. Otherwise, `halign` determines the horizontal ⟨*alignment*⟩ of the upper part of the box only. The feasible values for ⟨*alignment*⟩ are more or less identical to the corresponding `/tikz/align` settings, even if the implementation differs.

- `justify`: usual left and right justified type setting.
- `left`: left border justification in analogy to plain TEX.
- `flush left`: left border justification with `\raggedright` of LATEX.
- `right`: right border justification in analogy to plain TEX.
- `flush right`: right border justification with `\raggedleft` of LATEX.
- `center`: centering in analogy to plain TEX.
- `flush center`: centering with `\centering` of LATEX.

The differences between the flush and non-flush version are explained in detail in the TikZ manual [22]. The short story is that the non-flush versions will often look more balanced but with more hyphenations.

```
\tcbset{colback=red!5!white,colframe=red!75!black,size=small,
  fonttitle=\bfseries,width=3.5cm,box align=top,
  nobeforeafter}

\begin{tcolorbox}[adjusted title=flush center,halign=flush center]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=flush left,halign=flush left]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=flush right,halign=flush right]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}

\begin{tcolorbox}[adjusted title=center,halign=center]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=left,halign=left]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=right,halign upper=right]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
```

flush center
This is a demonstration text for showing how line breaking works.

flush left
This is a demonstration text for showing how line breaking works.

flush right
This is a demonstration text for showing how line breaking works.

center
This is a demonstration text for showing how line breaking works.

left
This is a demonstration text for showing how line breaking works.

right
This is a demonstration text for showing how line breaking works.

N 2015-05-07 **/tcb/halign upper=**⟨*alignment*⟩ (no default, initially `justify`)

Alias for `/tcb/halign`.

N 2015-05-07 **/tcb/halign lower=**⟨*alignment*⟩ (no default, initially `justify`)

`halign lower` determines the horizontal ⟨*alignment*⟩ of the lower part of the box. The feasible values for ⟨*alignment*⟩ are the same as for `/tcb/halign` → P. 30.

```
\begin{tcbraster}[raster columns=3,fonttitle=\bfseries,
  colback=red!5!white,colframe=red!75!black]

  \begin{tcolorbox}[adjusted title=flush center,halign lower=flush center]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=flush left,halign lower=flush left]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=flush right,halign lower=flush right]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=center,halign lower=center]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=left,halign lower=left]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=right,halign lower=right]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}

\end{tcbraster}
```

flush center
Upper part.
Lower part.

flush left
Upper part.
Lower part.

flush right
Upper part.
Lower part.

center
Upper part.
Lower part.

left
Upper part.
Lower part.

right
Upper part.
Lower part.

N 2015-05-07 **/tcb/halign title=⟨*alignment*⟩** (no default, initially `justify`)

`halign lower` determines the horizontal ⟨*alignment*⟩ of the title of the box. The feasible values for ⟨*alignment*⟩ are the same as for `/tcb/halign` → P. 30.

```
\begin{tcbraster}[raster columns=3,fonttitle=\bfseries,
  colback=red!5!white,colframe=red!75!black]

  \begin{tcolorbox}[adjusted title=flush center,halign title=flush center]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=flush left,halign title=flush left]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=flush right,halign title=flush right]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=center,halign title=center]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=left,halign title=left]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=right,halign title=right]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}

\end{tcbraster}
```



U 2015-05-07 **/tcb/flushleft upper** (style, no value)

Shortcut for setting `/tcb/halign` → P. 30 to `flush left`.

U 2015-05-07 **/tcb/center upper** (style, no value)

Shortcut for setting `/tcb/halign` → P. 30 to `flush center`.

U 2015-05-07 **/tcb/flushright upper** (style, no value)

Shortcut for setting `/tcb/halign` → P. 30 to `flush right`.

U 2015-05-07 **/tcb/flushleft lower** (style, no value)

Shortcut for setting `/tcb/halign lower` → P. 31 to `flush left`.

U 2015-05-07 **/tcb/center lower** (style, no value)

Shortcut for setting `/tcb/halign lower` → P. 31 to `flush center`.

U 2015-05-07 **/tcb/flushright lower** (style, no value)

Shortcut for setting `/tcb/halign lower` → P. 31 to `flush right`.

U 2015-05-07 **/tcb/flushleft title** (style, no value)

Shortcut for setting /tcb/halign title→P. 32 to **flush left**.

U 2015-05-07 **/tcb/center title** (style, no value)

Shortcut for setting /tcb/halign title→P. 32 to **flush center**.

U 2015-05-07 **/tcb/flushright title** (style, no value)

Shortcut for setting /tcb/halign title→P. 32 to **flush right**.

> ! The vertical alignment settings are only relevant for boxes which are larger than their natural height, see Section 4.10 on page 53.

U 2015-07-16 **/tcb/valign**=⟨*alignment*⟩ (no default, initially `top`)

If the height of a `tcolorbox` is not the natural height, `valign` determines the vertical ⟨*alignment*⟩ of the upper part. Feasible values are

- **top**: Anchor text at top.
- **center**: Anchor text at center.
- **bottom**: Anchor text at bottom.
- **scale**: Scale text vertically to fit into the available space. This is brutal and may not look very good. Consider Section 21 on page 426 alternatively.
- **scale***: Like **scale**, but scaling is bounded by /tcb/valign scale limit.

For a box with natural height, these settings are meaningless.

```
\tcbset{width=(\linewidth-2mm)/4,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=2cm}

\foreach \myalign in {top,center,bottom,scale}
{\begin{tcolorbox}[valign=\myalign]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}}
```



N 2015-05-07 **/tcb/valign upper**=⟨*alignment*⟩ (no default, initially `top`)

Alias for /tcb/valign.

/tcb/valign lower=⟨*alignment*⟩ (no default, initially `top`)

This key has the same meaning for the lower part as `valign` for the upper part, i. e., it determines the vertical ⟨*alignment*⟩ of the lower part with feasible values `top`, `center`, `bottom`, `scale`, and `scale*`.

N 2015-07-16 **/tcb/valign scale limit**=⟨*real number*⟩ (no default, initially `1.1`)

Sets an upper scale limit for the **scale*** setting in /tcb/valign and /tcb/valign lower. Note that this value is not reset by /tcb/reset→P. 109. So, changes also apply to embedded boxes.

Also see /tcb/sidebyside align→P. 120 for alignment settings when upper part and lower part are set side-by-side.

4.7 Geometry

4.7.1 Width

`/tcb/width=`⟨*length*⟩ (no default, initially `\linewidth`)

Sets the total width of the colored box to ⟨*length*⟩. See also `/tcb/height` → P. 53.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=\linewidth/2]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-31 `/tcb/text width=`⟨*length*⟩ (style, no default)

Sets the text width of the upper part to ⟨*length*⟩. See also `/tcb/text height` → P. 54.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[text width=4cm]
This is a \textbf{tcolorbox} where the text has a width of 4cm.
\end{tcolorbox}
```

This is a **tcolorbox** where the text has a width of 4cm.

N 2014-11-07 `/tcb/add to width=`⟨*length*⟩ (style, no default)

Adds ⟨*length*⟩ to the current total width of the colored box.

```
\tcbset{width=4cm,colback=red!5!white,
  colframe=red!75!black}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\begin{tcolorbox}[add to width=1cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

See Section 4.10 on page 53 for setting fixed height values.

4.7.2 Rules

/tcb/toprule=⟨*length*⟩ (no default, initially `0.5mm`)

Sets the line width of the top rule to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[toprule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/bottomrule=⟨*length*⟩ (no default, initially `0.5mm`)

Sets the line width of the bottom rule to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottomrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/leftrule=⟨*length*⟩ (no default, initially `0.5mm`)

Sets the line width of the left rule to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/rightrule=⟨*length*⟩ (no default, initially `0.5mm`)

Sets the line width of the right rule to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[rightrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/titlerule=⟨*length*⟩ (no default, initially `0.5mm`)

Sets the line width of the rule below the title to ⟨*length*⟩.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,
  colbacktitle=red!90!black}

\begin{tcolorbox}[titlerule=3mm,title=This is the title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is the title

This is a **tcolorbox**.

/tcb/boxrule=⟨*length*⟩ (style, no default, initially `0.5mm`)

Sets all rules of the frame to ⟨*length*⟩, i. e. /tcb/toprule→ P. 35, /tcb/bottomrule→ P. 35, /tcb/leftrule→ P. 35, /tcb/rightrule→ P. 35, and /tcb/titlerule.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[boxrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

! More options for drawing a /tcb/borderline→ P. 181 are provided by using skins documented in Section 10 from page 152.

4.7.3 Arcs

/tcb/arc=⟨*length*⟩ (no default, initially `1mm`)

Sets the inner radius of the four frame arcs to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[arc=0mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[arc=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

N 2015-05-05 **/tcb/circular arc** (style, no value)

Sets /tcb/arc → P. 36 to match the half of the inner width of the colored box. If width and height of the box are identical, this gives a circle.

> **!** If the height of the box is smaller than the width, the result will look quite ugly.

```
\begin{tcolorbox}[width=3cm,
  colback=red!5!white,
  colframe=red!75!black,
  halign=center,valign=center,
  square,circular arc]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

N 2015-05-05 **/tcb/bean arc** (style, no value)

Sets /tcb/arc → P. 36 to match the smaller value of the half of the inner width and of the inner height of the colored box.

> **!** This only works for a fixed /tcb/height → P. 53. Also, /tcb/bean arc must be used *after* width and height are set by option keys.

```
\tcbset{size=fbox,boxrule=0.5mm,
  colback=red!5!white,
  colframe=red!75!black,
  halign=center,valign=center}

\begin{tcolorbox}[width=3cm,height=2cm,
  bean arc]
Box A
\end{tcolorbox}

\begin{tcolorbox}[width=2cm,height=3cm,
  bean arc]
Box B
\end{tcolorbox}
```



N 2015-05-05 **/tcb/octogon arc** (style, no value)

Sets /tcb/arc → P. 36 to match $\frac{1}{2+\sqrt{2}}$ of the inner width of the colored box. If width and height of the box are identical, the interior is a regular octogon.

```
\begin{tcolorbox}[enhanced,
  size=minimal,auto outer arc,
  width=2.1cm,octogon arc,
  colback=red,colframe=white,colupper=white,
  fontupper=\fontsize{7mm}{7mm}\selectfont\bfseries\sffamily,
  halign=center,valign=center,
  square,arc is angular,
  borderline={0.2mm}{-1mm}{red}  ]
STOP
\end{tcolorbox}
```

N 2015-05-05 **/tcb/arc is angular** (no value, initially unset)

Using this options applies a patch which straightens the corners arcs of the boxes. The little arcs are replaced by little straight lines.

> **!** This patch is considered as an experimental feature. It changes some of the original TikZ code. This change may break with future updates of TikZ.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  arc=3mm}

\begin{tcolorbox}[arc is angular]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[arc is curved]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

N 2015-05-05 **/tcb/arc is curved** (no value, initially set)

This option resets the patch from /tcb/arc is angular. The original TikZ code is activated.

/tcb/outer arc=⟨*length*⟩ (no default, initially unset)

Sets the outer radius of the four frame arcs to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[arc=4mm,outer arc=1mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/auto outer arc (no value, initially set)

Sets the outer radius of the four frame arcs automatically in dependency of the inner radius given by /tcb/arc → P. 36.

4.7.4 Spacing

/tcb/boxsep=⟨*length*⟩ (no default, initially `1mm`)

Sets a common padding of ⟨*length*⟩ between the text content and the frame of the box. This value is added to the key values of `left`, `right`, `top`, `bottom`, and `middle` at the appropriate places.

```
\tcbset{colback=red!5!white,colframe=red!75!black,width=(\linewidth-4mm)/2,
  before=,after=\hfill}

\begin{tcolorbox}[boxsep=5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[boxsep=5mm,draft]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

frame: w=195.33255pt, h=48.97505pt

upper: w=141.2724pt, h=6.296pt

interior: w=192.4873pt, h=46.1298pt

/tcb/left=⟨*length*⟩ (style, no default, initially `4mm`)

Sets the left space between all text parts and frame (additional to `boxsep`). This is an abbreviation for setting `lefttitle`, `leftupper`, and `leftlower` to the same value.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[left=0mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2017-02-16 **/tcb/left*=**⟨*length*⟩ (style, no default)

Sets `/tcb/left` such that ⟨*length*⟩ is the distance between the left bounding box and the text parts.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

This is some text.
\begin{tcolorbox}[grow to left by=5mm,left*=0mm,
  enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is some text.

This is a **tcolorbox**.

/tcb/lefttitle=⟨*length*⟩ (no default, initially 4mm)

Sets the left space between title text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[lefttitle=3cm,title=My Title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My Title

This is a **tcolorbox**.

/tcb/leftupper=⟨*length*⟩ (no default, initially 4mm)

Sets the left space between upper text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftupper=3cm,title=My Title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My Title

This is a **tcolorbox**.

/tcb/leftlower=⟨*length*⟩ (no default, initially 4mm)

Sets the left space between lower text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftlower=3cm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/right=⟨*length*⟩ (style, no default, initially 4mm)

Sets the right space between all text parts and frame (additional to boxsep). This is an abbreviation for setting rightitle, rightupper, and rightlower to the same value.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,right=2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcol-**
orbox.

N 2017-02-16 **/tcb/right*=**⟨*length*⟩ (style, no default)

Sets /tcb/right → P. 40 such that ⟨*length*⟩ is the distance between the right bounding box and the text parts.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\flushright This is some text.
\begin{tcolorbox}[grow to right by=5mm,right*=0mm,
  halign=right,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is some text.

This is a **tcolorbox**.

/tcb/righttitle=⟨*length*⟩ (no default, initially 4mm)

Sets the right space between title text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,righttitle=2cm,title=My very long title text]
This is a \textbf{tcolorbox} with standard upper box dimensions.
\end{tcolorbox}
```

My very long ti-
tle text

This is a **tcolorbox** with standard upper box dimensions.

/tcb/rightupper=⟨*length*⟩ (no default, initially 4mm)

Sets the right space between upper text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,rightupper=2cm,title=My very long title text]
This is a \textbf{tcolorbox} with compressed upper box dimensions.
\end{tcolorbox}
```

My very long title text

This is a **tcol-
orbox** with compressed upper box dimensions.

/tcb/rightlower=⟨*length*⟩ (no default, initially `4mm`)

Sets the right space between lower text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,rightlower=2cm]
This is a \textbf{tcolorbox} with standard upper box dimensions.
\tcblower
This is the lower part with large space at right.
\end{tcolorbox}
```

This is a **tcolorbox** with standard upper box dimensions.

This is the lower part with large space at right.

/tcb/top=⟨*length*⟩ (no default, initially `2mm`)

Sets the top space between text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[top=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/toptitle=⟨*length*⟩ (no default, initially `0mm`)

Sets the top space between title and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[toptitle=3mm,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/bottom=⟨*length*⟩ (no default, initially 2mm)

Sets the bottom space between text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottom=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/bottomtitle=⟨*length*⟩ (no default, initially 0mm)

Sets the bottom space between title and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottomtitle=3mm,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/middle=⟨*length*⟩ (no default, initially 2mm)

Sets the space between upper and lower text to the separation line (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[middle=0mm,boxsep=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.
This is the lower part.

4.7.5 Size Shortcuts

`/tcb/size=`⟨*name*⟩ (no default, initially `normal`)

Sets all geometry keys with exception of `/tcb/width` → P. 34 to predefined length values. For ⟨*name*⟩, the following values are feasible:

- `normal`: normal sized boxes e.g. of width `\linewidth`.
- `title`: title line sized boxes.
- `small`: small boxes e.g. for keyword highlighting.
- `fbox`: identical to the standard `\fbox`.
- `tight`: no padding space at all.
- `minimal`: no padding space, no box rules.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\foreach \s in {normal,title,small,fbox,tight,minimal} {
  \tcbox[size=\s,on line]{\s} }

\foreach \s in {normal,title,small,fbox,tight,minimal} {
  \tcbox[size=\s,on line,title=Test]{\s} }

\foreach \s in {normal,title,small,fbox,tight,minimal} {
  \begin{tcolorbox}[size=\s,on line,title=Test,width=2.2cm]
    \s \tcblower lower\end{tcolorbox} }
```



Predefined values						
	`normal`	`title`	`small`	`fbox`	`tight`	`minimal`
`boxrule`	0.5mm	0.4mm	0.3mm	0.4pt	0.4pt	0.0pt
`boxsep`	1.0mm	1.0mm	1.0mm	3.0pt	0.0pt	0.0pt
`left`	4.0mm	2.0mm	1.0mm	0.0pt	0.0pt	0.0pt
`right`	4.0mm	2.0mm	1.0mm	0.0pt	0.0pt	0.0pt
`top`	2.0mm	0.25mm	0.0mm	0.0pt	0.0pt	0.0pt
`bottom`	2.0mm	0.25mm	0.0mm	0.0pt	0.0pt	0.0pt
`toptitle`	0.0mm	0.0mm	0.0mm	0.0pt	0.0pt	0.0pt
`bottomtitle`	0.0mm	0.0mm	0.0mm	0.0pt	0.0pt	0.0pt
`middle`	2.0mm	0.75mm	0.5mm	1.0pt	0.2pt	0.0pt
`arc`	1.0mm	0.75mm	0.5mm	1.0pt	0.0pt	0.0pt
`outer arc`	`auto`	`auto`	`auto`	`auto`	0.0pt	0.0pt

/tcb/oversize=⟨*length*⟩ (style, default `0pt`)

Sets the text width of the upper part to the current line width plus an optional ⟨*length*⟩. This is achieved by changing the keys `/tcb/width` → P. 34 `/tcb/enlarge left by` → P. 86, and `/tcb/enlarge right by` → P. 86 appropriately. The resulting box is overlapping into the left and right margin of the page. Note that this style option has to be given *after* all other geometry keys! Also see `/tcb/grow sidewards by` → P. 88 and `/tcb/spread sidewards` → P. 91.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\textit{Normal text for comparison:}\\
\lipsum[2]

\begin{tcolorbox}[oversize,title=Oversized box]
\lipsum[2]
\end{tcolorbox}

\begin{tcolorbox}[title=Normal box]
\lipsum[2]
\end{tcolorbox}
```

Normal text for comparison:
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Oversized box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Normal box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

4.7.6 Toggle Left and Right

U 2017-02-16 **/tcb/toggle left and right=**⟨*toggle preset*⟩ (default `evenpage`, initially `none`)

According to the ⟨*toggle preset*⟩, the left and the right settings of the `tcolorbox` are switched or not. Feasible values are:

- `none`: no switching.
- `forced`: the values of the left and right rules, spaces, and corners are switched.
- `evenpage`: if the page is an even page, the values of the left and right rules, spaces, and corners are switched. This value also sets `/tcb/check odd page` → P. 104 to `true`.

> **!** Horizontal bounding box enlargements are not toggled by this option. They can be toggled independently by `/tcb/toggle enlargement` → P. 89. For example, `/tcb/oversize` → P. 45 changes the bounding box.

```
% \usepackage{lipsum}
% \usetikzlibrary{patterns}
% \tcbuselibrary{skins,breakable}
\begin{tcolorbox}[enhanced,breakable,
  toggle left and right,sharp corners,
  boxrule=0mm,top=0mm,bottom=0mm,left=1mm,right=1mm,
  rightrule=1cm,colupper=blue!25!black,
  interior style={fill overzoom image=lichtspiel.jpg,fill image opacity=0.25},
  frame style={pattern=crosshatch dots light steel blue},
  overlay={%
    \begin{tcbclipframe}
    \tcbifoddpage{\coordinate (X) at ([xshift=-5mm]frame.east);}
                 {\coordinate (X) at ([xshift=5mm]frame.west);}
    \fill[shading=ball,ball color=blue!50!white,opacity=0.5] (X) circle (4mm);
    \end{tcbclipframe}}]
\lipsum[1-6]
\end{tcolorbox}
```

This example switches a `1cm` thick rule from the left to the right side depending on the page number. Thereby, the rule is always on the outer side of the double-sided paper. Additionally, a ball is drawn on the outer side with help of an overlay.


Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tin-

cidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

4.8 Corners

The four corners of any `tcolorbox` can be set individually as `/tcb/sharp corners` or as `/tcb/rounded corners`→ P. 49. These settings are also reflected in the behavior of `/tcb/borderline`→ P. 181 and `/tcb/shadow`→ P. 192 as one would expect.

By default, all four corners are *rounded*. So, only the `/tcb/sharp corners` option will be necessary for most use cases. The `/tcb/rounded corners`→ P. 49 option can be used to revert a `/tcb/sharp corners` setting.

`/tcb/sharp corners`=⟨*position*⟩ (default `all`, initially unset)

The ⟨*position*⟩ denotes one or more of the four box corners to be set as *sharp* corners. The not assigned corners will retain their mode. Feasible values for ⟨*position*⟩ are:

- `northwest`
- `northeast`
- `southwest`
- `southeast`
- `north`
- `south`
- `east`
- `west`
- `downhill`
- `uphill`
- `all`

```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,
  sharp corners=northwest ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,
  sharp corners ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/rounded corners=⟨*position*⟩ (default `all`, initially `all`)

The `/tcb/rounded corners` can be used to revert a `/tcb/sharp corners` → P. 48 setting. The ⟨*position*⟩ denotes one or more of the four box corners to be set as *rounded* corners. The not assigned corners will retain their mode. Feasible values for ⟨*position*⟩ are[2]:

- `northwest`
- `northeast`
- `southwest`
- `southeast`
- `north`
- `south`
- `east`
- `west`
- `downhill`
- `uphill`
- `all`

```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,sharp corners,
  rounded corners=northwest ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/sharpish corners (style, no value)

Shortcut for setting `/tcb/arc` → P. 36 and `/tcb/outer arc` → P. 38 to `0pt`. With this setting, rounded corners will appear as quasi-sharp, but e. g. the shadow will be somewhat rounder than the shadow of really sharp corners.

> **!** Corners are still of type *rounded* with this option, but appear *sharp*. To switch back to rounded corners, one has to adapt `/tcb/arc` → P. 36 and `/tcb/outer arc` → P. 38.

```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,
  sharpish corners ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

[2] The graphical examples assume that the boxes where set to have sharp corners before.

The following examples will show the differences between `/tcb/rounded corners` → P. 49, `/tcb/sharpish corners` → P. 49, and `/tcb/sharp corners` → P. 48. The later two give the same core box, but `/tcb/borderline` → P. 181 and `/tcb/shadow` → P. 192 settings are slightly different. The following examples use `/tcb/drop fuzzy shadow` → P. 186.

My title

This is a **tcolorbox**.

rounded corners



My title

This is a **tcolorbox**.

sharpish corners



My title

This is a **tcolorbox**.

sharp corners



4.9 Transparency

> **!** Transparency effects are likely to be used in conjunction with *jigsaw* skin variants, see Section 10.11 on page 205.

/tcb/opacityframe=⟨*fraction*⟩ (no default, initially `1.0`)

Sets the frame opacity of the box to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[opacityframe=0.25,
  colframe=red]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/opacityback=⟨*fraction*⟩ (no default, initially `1.0`)

Sets the background opacity of the box to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[standard jigsaw,colframe=red,
  opacityframe=0.5, opacityback=0.5]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/opacitybacktitle=⟨*fraction*⟩ (no default, initially `1.0`)

Sets the title background opacity of the box to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[standard jigsaw,colframe=red,
  opacityframe=0.5, opacitybacktitle=0.5,
  title filled, title=This is a title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

/tcb/opacityfill=⟨*fraction*⟩ (style, no default, initially `1.0`)

Sets the fill opacity for frame, interior and optionally the title background to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[standard jigsaw,colframe=red,
  opacityfill=0.7, title=This is a title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

/tcb/opacityupper=⟨*fraction*⟩ (no default, initially 1.0)

Sets the text opacity of the upper box part to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[enhanced,opacityupper=0.5,
  interior ⤸
      ⤹style={preaction={fill=white},pattern=checkerbo
      ⤹color=gray!40}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/opacitylower=⟨*fraction*⟩ (no default, initially 1.0)

Sets the text opacity of the lower box part to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[enhanced,opacitylower=0.5,
  interior ⤸
      ⤹style={preaction={fill=white},pattern=checkerbo
      ⤹color=gray!40}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/opacitytext=⟨*fraction*⟩ (no default, initially 1.0)

Sets the text opacity of the upper and the lower box part to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[enhanced,opacitytext=0.5,
  interior ⤸
      ⤹style={preaction={fill=white},pattern=checkerbo
      ⤹color=gray!40}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/opacitytitle=⟨*fraction*⟩ (no default, initially 1.0)

Sets the text opacity of the box title to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[enhanced,opacitytitle=0.7,
  coltitle=black,
  fonttitle=\bfseries,title=This is a title,
  title ⤸
      ⤹style={preaction={fill=white},pattern=checkerbo
      ⤹color=gray!40}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced jigsaw,fonttitle=\bfseries,title=This is a title,
  opacityframe=0.5,opacityback=0.25,opacitybacktitle=0.25,opacitytext=0.8,
  colback=red!5!white,colframe=red!75!black,colbacktitle=yellow!20!red]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

4.10 Height Control

In a typical usage scenario, the height of a `tcolorbox` is computed automatically to fit the content. Nevertheless, the height can be set to a fixed value or to fit commonly for several boxes, e. g. if boxes are set side by side.

> **!** The height control keys are only applicable to unbreakable boxes. If a box is set to be `/tcb/breakable` →P. 379, the height is always computed according to the *natural height*.

`/tcb/natural height` (no value, initially set)

Sets the total height of the colored box to its natural height depending on the box content.

`/tcb/height`=⟨*length*⟩ (no default)

Sets the total height of the colored box to ⟨*length*⟩ independent of the box content. ⟨*length*⟩ is the minimum height of the box, if `/tcb/height plus` is larger than zero.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white}

\begin{tcolorbox}[height=1cm,valign=center]
  This box has a height of 1cm.
\end{tcolorbox}
\begin{tcolorbox}[height=2cm,valign=center]
  This box has a height of 2cm.
\end{tcolorbox}
\begin{tcolorbox}[height=3cm,split=0.5,valign=center,valign lower=center]
  This box has a height of 3cm.
  \tcblower
  Lower part.
\end{tcolorbox}
```

This box has a height of 1cm.

This box has a height of 2cm.

This box has a height of 3cm.

Lower part.

`/tcb/height plus`=⟨*length*⟩ (no default, initially `0pt`)

The box may extend a given fixed `/tcb/height` up to the given ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
  right=1mm,boxsep=0mm,width=3cm,nobeforeafter}

\begin{tcolorbox}[height=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[height=1cm,height plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[height=1cm,height plus=1cm]
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.

/tcb/height from=⟨*min*⟩ **to** ⟨*max*⟩ (style, no default)

Sets the box height to a dimension between ⟨*min*⟩ and ⟨*max*⟩.

```
% \usepackage{lipsum}
\newtcolorbox{mybox}{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  bottom=1mm,right=1mm,boxsep=0mm,width=4.5cm,nobeforeafter,
  height from=2cm to 8cm}

\begin{mybox}
This is a tcolorbox.
\end{mybox}
\begin{mybox}
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{mybox}
\begin{mybox}
\lipsum[2]
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

N 2014-10-31 **/tcb/text height=**⟨*length*⟩ (style, no default)

Sets the text height to ⟨*length*⟩. This is the length from the top of the upper part to the bottom of the optional lower part. See also **/tcb/text width** → P. 34.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[text height=2cm]
This is a \textbf{tcolorbox} where the text area has a height of 2cm.
\end{tcolorbox}
```

This is a **tcolorbox** where the text area has a height of 2cm.

N 2014-11-07 **/tcb/add to height=⟨*length*⟩** (style, no default)

Adds ⟨*length*⟩ to the current height of the colored box. /tcb/height → P. 53 has to be set before this key is used! If this option is used several times, then the /tcb/height → P. 53 is also increased several times.

```
\tcbset{height=2cm,
  valign=center,width=(\linewidth-2mm)/2,
  before=,after=\hfill,colframe=blue!75!black,colback=white}

\begin{tcolorbox}
  This box has a height of 2cm.
\end{tcolorbox}
\begin{tcolorbox}[add to height=1cm]
  This box has a height of 3cm.
\end{tcolorbox}
```

This box has a height of 2cm.

This box has a height of 3cm.

N 2016-02-16 **/tcb/add to natural height=⟨*length*⟩** (style, no default)

The application of this option generates a box with natural height plus the given ⟨*length*⟩. If this option is used several times, then the last setting of ⟨*length*⟩ wins. The resulting box is not considered a fixed height box and the implementation is quite different to /tcb/add to height.

```
\tcbset{valign=center,width=(\linewidth-2mm)/2,
  before=,after=\hfill,colframe=blue!75!black,colback=white}

\begin{tcolorbox}
  This box has natural height.
\end{tcolorbox}
\begin{tcolorbox}[add to natural height=1cm]
  This box has natural height plus 1 cm.
\end{tcolorbox}
```

This box has natural height.

This box has natural height plus 1 cm.

N 2014-09-22
U 2016-02-17

`/tcb/height fill=true|false|maximum` (default `true`, initially `false`)

If set to `true`, the height of the `tcolorbox` is set to the rest of the available vertical space of the current page. If set to `maximum`, the page is compressed as much as possible. Note that the `tcolorbox` is always set as its own paragraph using this option. Also see `/tcb/text fill` → P. 69.

> ! Note that the library LIB breakable has to be loaded to use this key!

This height control key is only applicable to unbreakable boxes, but it uses code from the library LIB breakable. The counterpart for breakable boxes is `/tcb/height fixed for` → P. 384.

This option can and should not be used for boxes in boxes, but it can be used for boxes inside a `tcbraster` → P. 290.

```
% \usepackage{lipsum}
% \tcbuselibrary{breakable}
\begin{tcolorbox}[height fill,
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Box which fills the rest of the page]
\lipsum[1]
\end{tcolorbox}
```

Box which fills the rest of the page

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

N 2017-06-28 **/tcb/inherit height=⟨*fraction*⟩** (default 1, initially unset)

If this option is used for a tcolorbox which is embedded inside another (outer) tcolorbox *and* if this outer tcolorbox has a fixed height, then the given ⟨*fraction*⟩ of the available text height of the outer tcolorbox is used as /tcb/height → P. 53 for the current tcolorbox. Otherwise, /tcb/natural height → P. 53 is applied for the current tcolorbox.

```
\tcbset{colframe=blue!75!black,colback=white,fonttitle=\bfseries}

\begin{tcolorbox}[title=Outer box with fixed height 4cm,height=4cm]
  \begin{tcolorbox}[title=Inner box,nobeforeafter,inherit height]
    This inner box matches the available space.
  \end{tcolorbox}
\end{tcolorbox}

\begin{tcolorbox}[title=Outer box with natural height]
  \begin{tcolorbox}[title=Inner box,nobeforeafter,inherit height]
    This inner box has its natural height.
  \end{tcolorbox}
\end{tcolorbox}

\begin{tcolorbox}[title=Outer box with fixed height 5cm,height=5cm]
  \begin{tcolorbox}[title=Inner box,nobeforeafter,inherit height]
    \begin{tcolorbox}[colframe=red,beforeafter skip=0pt,inherit height=0.6]
      Deeply nested box using 60 percent of the available space.
    \end{tcolorbox}
    \begin{tcolorbox}[colframe=red,beforeafter skip=0pt,inherit height=0.4]
      Deeply nested box using 40 percent of the available space.
    \end{tcolorbox}
  \end{tcolorbox}
\end{tcolorbox}
```

Outer box with fixed height 4cm

Inner box

This inner box matches the available space.

Outer box with natural height

Inner box

This inner box has its natural height.

Outer box with fixed height 5cm

Inner box

Deeply nested box using 60 percent of the available space.

Deeply nested box using 40 percent of the available space.

N 2015-05-05 **/tcb/square** (style, no value)

Sets /tcb/height → P. 53 to match the width of the colored box.

```
\begin{tcolorbox}[width=3cm,
  colback=red!5!white,
  colframe=red!75!black,
  halign=center,valign=center,
  square]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/space=⟨*fraction*⟩ (no default, initially 0)

If the height of a `tcolorbox` is not the natural height, the space difference between the forced and the natural size is distributed between the upper and the lower part of the box. This space could also be negative. ⟨*fraction*⟩ with a value between 0 and 1 is the amount of space which is added to the upper part, the rest is added to the lower part. If there is no lower part, then all of the space is added to the upper part always.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=3cm}

\foreach \f in {0.2,0.4,0.7}
{\begin{tcolorbox}[space=\f]
    This is the upper part.
    \tcblower
    This is the lower part.
\end{tcolorbox}}
```

This is the upper part.
This is the lower part.

This is the upper part.
This is the lower part.

This is the upper part.
This is the lower part.

/tcb/space to upper (style)

This is an abbreviation for `space=1`, i. e. all extra space is added to the upper part.

/tcb/space to lower (style, initially set)

This is an abbreviation for `space=0`, i. e. all extra space is added to the lower part (if there is any).

/tcb/space to both (style)

This is an abbreviation for `space=0.5`, i. e. the extra space equally distributed between the upper and the lower part.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=3cm}

\foreach \myspace in {space to upper,space to both,space to lower}
{\begin{tcolorbox}[\myspace]
    This is the upper part.
    \tcblower
    This is the lower part.
\end{tcolorbox}}
```



N 2015-02-15
U 2020-07-30

/tcb/space to=⟨*macro*⟩ (no default, initially unset)

If the height of a `tcolorbox` is not the natural height, the space difference between the forced and the natural size is saved into the given local ⟨*macro*⟩. This ⟨*macro*⟩ can and should be used inside the box content to add content which is vertically sized to match ⟨*macro*⟩.

!

- The actual length saved into ⟨*macro*⟩ is adapted dynamically during several compilations – at least two, but maybe more.
- Due to the adaption algorithm, objects can be sized with ⟨*macro*⟩ plus any offset length.
- Never ever use ⟨*macro*⟩ multiplied with a factor. The only exception to this rule is that the space can be split into parts which sum to ⟨*macro*⟩.
- Never use this in combination with `/tcb/fit` → P. 429.

```
\begin{tcolorbox}[colframe=blue!75!black,colback=white,height=3cm,
    space to=\myspace]
  This is my box of height 3cm. The space is filled with a picture:\\[2mm]
  \includegraphics[width=\linewidth,height=\myspace]{goldshade.png}\\[1mm]
  This is some other text.
\end{tcolorbox}
```



```
\begin{tcolorbox}[colframe=blue!75!black,colback=white,height=3cm,
    space to=\myspace]
  \includegraphics[width=\linewidth,
    height=0.33\dimexpr\myspace]{blueshade.png}\\[1mm]
  This is my box of height 3cm.\\[2mm]
  \includegraphics[width=\linewidth,
    height=0.67\dimexpr\myspace]{goldshade.png}
\end{tcolorbox}
```



/tcb/split=⟨*fraction*⟩ (no default)

If the height of a `tcolorbox` is not the natural height, the ⟨*fraction*⟩ with a value between 0 and 1 determines the positioning of the segmentation between the upper and the lower part. Here, 0 stands for top and 1 for bottom. Note that the box is split regardless of the actual dimensions of the text parts!

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,height=3cm,
colback=white,colframe=blue!75!black,valign=center,valign lower=center}

\foreach \f in {0.1,0.5,0.8}
{\begin{tcolorbox}[split=\f]
This is the upper part.
\tcblower
This is the lower part with a lot of text in several lines.
\end{tcolorbox}}
```



U 2014-11-07 **/tcb/equal height group=**⟨*id*⟩ (no default)

Boxes which are members of an **equal height group** will all get the same height, i. e. the maximum of all their natural heights. The ⟨*id*⟩ serves to distinguish between different height groups. Note that you have to compile twice to see changes and that height groups are global definitions.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,arc=0mm,
colframe=blue!75!black,colback=white,fonttitle=\bfseries}

\begin{tcolorbox}[equal height group=A,adjusted title={One}]
  My smallest box.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=A,adjusted title={Two}]
  This box is also small.
  \tcblower
  But with a lower part.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=A,adjusted title={Three}]
  This box contains a lot of text just to fill the space
  with word flowing and flowing and flowing until the box
  is filled with all of it.
\end{tcolorbox}\linebreak
%
\tcbset{width=(\linewidth-1mm)/2,before=,after=\hfill,arc=0mm,
colframe=red!75!black,colback=white}
%
\begin{tcolorbox}[equal height group=B]
  Now, we use another equal height group.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=B,after=]
  \begin{equation*}
    \int\limits_{0}^{1} x^2 = \frac13.
  \end{equation*}
\end{tcolorbox}
```

One

My smallest box.

Two

This box is also small.

But with a lower part.

Three

This box contains a lot of text just to fill the space with word flowing and flowing and flowing until the box is filled with all of it.

Now, we use another equal height group.

$$\int\limits_{0}^{1} x^2 = \frac{1}{3}.$$

! See Section 15 on page 288 for more equal height options.

/tcb/minimum for equal height group=⟨*id*⟩:⟨*length*⟩ (no default, initially unset)

Plants a ⟨*length*⟩ into the equal height group with the given ⟨*id*⟩. This ensures that the height will not drop below ⟨*length*⟩. Note that you cannot reduce a computed height value by using this key with a small value. The difference to applying /tcb/height → P. 53 directly is that the boxes are never too small for their content.

```
\tcbset{colframe=blue!75!black,colback=white,arc=0mm,
  before=,after=\hfill,fonttitle=\bfseries,left=2mm,right=2mm,
  width=3.5cm,
  equal height group=C,
  minimum for equal height group=C:3.5cm}

\begin{tcolorbox}
  My first box. All boxes will get 3.5cm times 3.5cm
  if the content height is not too large.
\end{tcolorbox}%
\begin{tcolorbox}
  My second box.
  \tcblower
  This is the lower part.
\end{tcolorbox}%
\begin{tcblisting}{}
\textbf{Mixed}
with a listing.
\end{tcblisting}
\begin{tcolorbox}[title={Fourth box}]
  My final box.
\end{tcolorbox}%
```

My first box. All boxes will get 3.5cm times 3.5cm if the content height is not too large.

My second box.

This is the lower part.

Mixed with a listing.

Fourth box

My final box.

N 2016-03-24 **/tcb/minimum for current equal height group=⟨*length*⟩** (no default, initially unset)

Sets /tcb/minimum for equal height group for the current equal height group. Apparently, this only works for an already known equal height group, i.e. /tcb/equal height group → P. 61 has to be set *before* this option is used. This option is likely to be used in combination with /tcb/raster equal height → P. 299

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster equal height,colframe=blue!75!black,colback=white,
  raster every box/.style={minimum for current equal height group=2cm}]
  \tcbitem A
  \tcbitem B
\end{tcbitemize}
```

A

B

N 2015-11-27
U 2016-02-22

/tcb/use height from group=⟨*id*⟩ (style, default current group)

Sets the current box to a fixed /tcb/height → P. 53 which is copied from an equal height group with the given ⟨*id*⟩. If this height is not available during the current compilation, no fixed height setting is used. If ⟨*id*⟩ is omitted, the current equal height group is used which has to be set before by /tcb/equal height group → P. 61.
Note that the natural height of the current box is not considered for computation of the group height. The main application for /tcb/use height from group is that the height can be adapted further by /tcb/add to height → P. 55.

```
\begin{tcolorbox}[use height from group=C,add to height=-2cm,
  colframe=blue!75!black,colback=white]
Height from group \enquote{C} of the previous example, but reduced by 2cm.
\end{tcolorbox}%
```

Height from group "C" of the previous example, but reduced by 2cm.

```
% \tcbuselibrary{raster}
Every line is inside an equal height group:
\begin{tcbraster}[raster equal height=rows,
    title=Box \thetcbrasternum,
    enhanced,size=small,colframe=red!50!black,colback=red!10!white]
  \begin{tcolorbox}First line\\second line\\
    The height of this box rules.\end{tcolorbox}
  \begin{tcolorbox}[use height from group]Test\end{tcolorbox}
  \begin{tcolorbox}[use height from group]
    First line\\second line\end{tcolorbox}
  \begin{tcolorbox}The height of this box rules.\end{tcolorbox}
\end{tcbraster}
```

Every line is inside an equal height group:

Box 1
First line
second line
The height of this box rules.

Box 2
Test

Box 3
First line
second line

Box 4
The height of this box rules.

N 2015-11-27

\tcbheightfromgroup{⟨*macro*⟩}{⟨*id*⟩}

Saves the height from an equal height group with the given ⟨*id*⟩ to a ⟨*macro*⟩. If this height is not available during the current compilation, ⟨*macro*⟩ is set to `0pt`.

4.11 Box Content Additions

The following options introduce some arbitrary ⟨*code*⟩ to the content of a `tcolorbox`. These additions can be given at the beginning or at the ending of the title, the upper part, or the lower part.

/tcb/before title=⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the color and font settings and *before* the content of the title.

```
\tcbset{before title={\textcolor{yellow}{\large Important:}~},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Important: **My title**

This is a **tcolorbox**.

/tcb/after title=⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the content of the title.

```
\tcbset{after title={\hfill\colorbox{Navy}{approved}},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title **approved**

This is a **tcolorbox**.

/tcb/before upper=⟨*code*⟩ (no default, initially empty)

The given ⟨*code*⟩ is placed *after* the color and font settings and *before* the content of the upper part. The ⟨*code*⟩ is appended by a final `\ignorespaces`.

```
\tcbset{before upper={\textit{The story:}\par},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

The story:
This is a **tcolorbox**.

N 2019-02-26 **/tcb/before upper*=**⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the color and font settings and *before* the content of the upper part. In contrast to `/tcb/before upper`, no `\ignorespaces` is appended. Use this for situations where `\ignorespaces` is not needed or causes harm.

```
\begin{tcolorbox}[size=small,tile,
  colback=yellow!20,colbacktitle=yellow!70!black,
  title=My table,hbox,center,center title,
  before upper*=\begin{tabular}{cc},
  after upper*=\end{tabular},
]
  \multicolumn{2}{c}{Title}\\
  one & two \\
  three & four\\
\end{tcolorbox}
```

My table

Title	
one	two
three	four

U 2016-10-21 **/tcb/after upper=**⟨*code*⟩ (no default, initially empty)

The given ⟨*code*⟩ is placed *after* the content of the upper part. The ⟨*code*⟩ is prepended by a leading `\unskip`.

```
\tcbset{after upper={\par\hfill\textit{Read more next week}},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

Read more next week

```
\begin{tcolorbox}[before upper=\flqq,after upper=\frqq,
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

«This is a **tcolorbox**.»

N 2016-10-21
U 2019-02-28 **/tcb/after upper*=**⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the content of the upper part. In contrast to `/tcb/after upper`, no `\unskip` is prepended. Use this for situations where `\unskip` is not needed or causes harm. See `/tcb/before upper*` → P. 65 for an example.

> **!** From version 3.80 to 3.94, this option prepended an `\unskip` to the given ⟨*code*⟩.
> From version 3.95 to 4.15, this option was deprecated.
> From version 4.20, this option is re-established with changed semantic (no `\unskip`!)

/tcb/before lower=⟨*code*⟩ (no default, initially empty)

The given ⟨*code*⟩ is placed *after* the color and font settings and *before* the content of the lower part. The ⟨*code*⟩ is appended by a final `\ignorespaces`.

```
\tcbset{before lower=\textit{Behold:~},colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

Behold: This is the lower part.

N 2019-02-26 **/tcb/before lower*=**⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the color and font settings and *before* the content of the lower part. In contrast to `/tcb/before lower`, no `\ignorespaces` is appended. Use this for situations where `\ignorespaces` is not needed or causes harm.

```
\begin{tcolorbox}[size=small,bicolor,sidebyside,center lower,
  colback=yellow!30,colbacklower=yellow!20,colframe=yellow!80!black,
  before lower*=\begin{tabular}{cc},
  after lower*=\end{tabular},
]
My table
\tcblower
  \multicolumn{2}{c}{Title}\\
  one & two \\
  three & four\\
\end{tcolorbox}
```

My table

Title	
one	two
three	four

U 2016-10-21 **/tcb/after lower=**⟨*code*⟩ (no default, initially empty)

The given ⟨*code*⟩ is placed *after* the content of the lower part. The ⟨*code*⟩ is prepended by a leading `\unskip`.

```
\begin{tcolorbox}[after lower=\ \textit{This is the end.},
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part. *This is the end.*

N 2016-10-21
U 2019-02-28 **/tcb/after lower*=**⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the content of the lower part. In contrast to `/tcb/after upper` → P. 66, no `\unskip` is prepended. Use this for situations where `\unskip` is not needed or causes harm.

```
\begin{tcolorbox}[before lower*=$,after lower*=$,
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
\sin^2(x)+\cos^2(x)=1.
\end{tcolorbox}
```

This is a **tcolorbox**.

$\sin^2(x) + \cos^2(x) = 1.$

! From version 3.80 to 3.94, this option prepended an `\unskip` to the given ⟨*code*⟩.
From version 3.95 to 4.15, this option was deprecated.
From version 4.20, this option is re-established with changed semantic (no `\unskip`!)

If /tcb/text fill is used, one cannot have a lower part and the box is unbreakable.

N 2015-07-15 **/tcb/text fill** (style, no value)

This style sets /tcb/before upper→P. 65 and /tcb/after upper→P. 66 to embed the upper part with a minipage. If a fixed height was applied e.g. by /tcb/height→P. 53 or /tcb/height fill→P. 56, this minipage gets a matching height. This allows to use vertical glue macros like \vfill to act like expected. If the box has no fixed height, setting /tcb/text fill has no other effect as making the box unbreakable.

```
\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  height=8cm,text fill,
  title=My filled box]
This is a \textbf{tcolorbox}.
\par\vfill
\begin{center}
  My middle text.
\end{center}
\par\vfill
This is the end of my box.
\end{tcolorbox}
```

My filled box

This is a **tcolorbox**.

My middle text.

This is the end of my box.

N 2019-09-19 **/tcb/tabulars=**⟨*preamble*⟩ (style)

This style sets /tcb/before upper → P. 65 and /tcb/after upper → P. 66 and several geometry keys to support a `tabular*` with the given ⟨*preamble*⟩. The packages `array` and `colortbl` have to be loaded separately.

```
% \usepackage{array}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title}

\begin{tcolorbox}[tabulars={@{\extracolsep{\fill}\hspace{5mm}}lrrrrr@{\hspace{5mm}}},
  boxrule=0.5pt,title=My table]
Group & One     & Two     & Three    & Four     & Sum\\\hline\hline
Red   & 1000.00 & 2000.00 &  3000.00 &  4000.00 & 10000.00\\\hline
Green & 2000.00 & 3000.00 &  4000.00 &  5000.00 & 14000.00\\\hline
Blue  & 3000.00 & 4000.00 &  5000.00 &  6000.00 & 18000.00\\\hline\hline
Sum   & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00
\end{tcolorbox}
```

My table

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

N 2019-09-19 **/tcb/tabulars*=**{⟨*code*⟩}{⟨*preamble*⟩} (style)

This is a variant of /tcb/tabulars which adds some ⟨*code*⟩ before the table starts.

```
% \usepackage{array}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title}

\begin{tcolorbox}[tabulars*={\arrayrulewidth0.5mm\renewcommand\arraystretch{1.4}}%
    {@{\extracolsep{\fill}\hspace{20mm}}lll@{\hspace{20mm}}},
  title=My table]
One     & Two     & Three \\\hline\hline
1000.00 & 2000.00 &  3000.00\\\hline
2000.00 & 3000.00 &  4000.00
\end{tcolorbox}
```

My table

One	Two	Three
1000.00	2000.00	3000.00
2000.00	3000.00	4000.00

If /tcb/tabularx or /tcb/tabularx* are used, one cannot have a lower part.

/tcb/tabularx=⟨*preamble*⟩ (style)

This style sets /tcb/before upper→ P. 65 and /tcb/after upper→ P. 66 and several geometry keys to support a tabularx with the given ⟨*preamble*⟩. The packages tabularx [4], array, and colortbl have to be loaded separately.

```
% \usepackage{array,tabularx}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\newcolumntype{Y}{>{\raggedleft\arraybackslash}X}% see tabularx
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title}

\begin{tcolorbox}[tabularx={X||Y|Y|Y|Y||Y},title=My table]
Group & One     & Two     & Three    & Four     & Sum\\\hline\hline
Red   & 1000.00 & 2000.00 &  3000.00 &  4000.00 & 10000.00\\\hline
Green & 2000.00 & 3000.00 &  4000.00 &  5000.00 & 14000.00\\\hline
Blue  & 3000.00 & 4000.00 &  5000.00 &  6000.00 & 18000.00\\\hline\hline
Sum   & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00
\end{tcolorbox}
```

My table

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

/tcb/tabularx*={⟨*code*⟩}{⟨*preamble*⟩} (style)

This is a variant of /tcb/tabularx which adds some ⟨*code*⟩ before the table starts.

```
% \usepackage{array,tabularx}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title}

\begin{tcolorbox}[tabularx*={\arrayrulewidth0.5mm}{X|X|X},title=My table]
One     & Two     & Three \\\hline\hline
1000.00 & 2000.00 &  3000.00\\\hline
2000.00 & 3000.00 &  4000.00
\end{tcolorbox}
```

My table

One	Two	Three
1000.00	2000.00	3000.00
2000.00	3000.00	4000.00

/tcb/tikz upper=⟨*options*⟩ (style)

This style adds a centered `tikzpicture` environment to the start and end of the upper part. The ⟨*options*⟩ may be given as Ti*k*Z picture options.

```
% \usepackage{tikz}

\begin{tcolorbox}[tikz upper,fonttitle=\bfseries,colback=white,colframe=black,
                  title=\tikzname\ drawing]
  \path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
  \fill[red] (45:5mm) circle (1mm);
  \fill[red] (135:5mm) circle (1mm);
  \draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tcolorbox}
```

Ti*k*Z drawing

/tcb/tikz lower=⟨*options*⟩ (style)

This style adds a centered `tikzpicture` environment to the start and end of the lower part. The ⟨*options*⟩ may be given as Ti*k*Z picture options.

```
% \usepackage{tikz}
% \tcbuselibrary{skins,listings}

\begin{tcblisting}{tikz lower,listing side text,fonttitle=\bfseries,
  bicolor,colback=LightBlue!50!white,colbacklower=white,colframe=black,
  righthand width=3cm,title=\tikzname\ drawing}
\path[fill=yellow,draw=yellow!75!red]
    (0,0) circle (1cm);
\fill[red] (45:5mm) circle (1mm);
\fill[red] (135:5mm) circle (1mm);
\draw[line width=1mm,red]
    (215:5mm) arc (215:325:5mm);
\end{tcblisting}
```

Ti*k*Z drawing

```
\path[fill=yellow,draw=yellow!75!red]
    (0,0) circle (1cm);
\fill[red] (45:5mm) circle (1mm);
\fill[red] (135:5mm) circle (1mm);
\draw[line width=1mm,red]
    (215:5mm) arc (215:325:5mm);
```

/tcb/tikznode upper=⟨*options*⟩ (style)

This style places the upper part content into a centered TikZ node. The ⟨*options*⟩ may be given as TikZ node options. This style is especially useful for boxes with multiline texts which are fitted to the text width.

```
% \usepackage{tikz}
\newtcbox{\headline}[1][]{enhanced,center,
  ignore nobreak,fontupper=\Large\bfseries,
  colframe=red!50!black,colback=red!10!white,
  drop fuzzy shadow=yellow,tikznode upper,#1}

\headline{Important\\Headline}
```

Important Headline

/tcb/tikznode lower=⟨*options*⟩ (style)

This style places the lower part content into a centered TikZ node. The ⟨*options*⟩ may be given as TikZ node options.

```
% \usepackage{tikz}
\begin{tcolorbox}[bicolor,colback=LightBlue!50!white,colbacklower=white,
  colframe=black,tikznode lower={inner sep=2pt,draw=red,fill=yellow}]
Upper part.
\tcblower
Lower part.
\end{tcolorbox}
```

Upper part.

Lower part.

/tcb/tikznode=⟨*options*⟩ (style)

Shortcut for setting `/tcb/tikznode upper` and `/tcb/tikznode lower` the same time.

/tcb/varwidth upper=⟨*length*⟩ (style, default `/tcb/width` → P. 34)

This style places the upper part content into a `varwidth` environment. This style needs the `varwidth` package [1] to be loaded manually. The resulting box has a maximal width of ⟨*length*⟩. This option is only senseful for a `\tcbox` → P. 14.

```
% \usepackage{varwidth}
\newtcbox{\varbox}{colframe=red!50!black,
  colback=red!10!white,varwidth upper}

\varbox{Short text.}
\varbox{This box contains is a longer text
  which is broken.}
```

Short text.

This box contains is a longer text which is broken.

4.12 Overlays

With an overlay, arbitrary ⟨*graphical code*⟩ can be added to a `tcolorbox`. This code is executed *after* the frame and interior are drawn and *before* the text content is drawn. Therefore, you can decorate the `tcolorbox` with your own extensions. Common special cases are *watermarks* which are implemented using overlays. See Subsection 10.3 from page 169 if you want to add *watermarks*.

> **!** If you use the core package only, the ⟨*graphical code*⟩ has to be `pgf` code and there is not much assistance for positioning. Therefore, the usage of the `/tcb/enhanced` → P. 211 mode from the library skins is recommended which allows `tikz` code and gives access to `/tcb/geometry nodes` → P. 140 for positioning.

`/tcb/overlay=`⟨*graphical code*⟩ (no default, initially unset)

Adds ⟨*graphical code*⟩ to the box drawing process. This ⟨*graphical code*⟩ is drawn *after* the frame and interior and *before* the text content.

```
% \tcbuselibrary{skins} % preamble
\tcbset{frogbox/.style={enhanced,colback=green!10,colframe=green!65!black,
  enlarge top by=5.5mm,
  overlay={\foreach \x in {2cm,3.5cm} {
    \begin{scope}[shift={([xshift=\x]frame.north west)}]
      \path[draw=green!65!black,fill=green!10,line width=1mm] (0,0) arc (0:180:5mm);
      \path[fill=black] (-0.2,0) arc (0:180:1mm);
    \end{scope}}}}}

\begin{tcolorbox}[frogbox,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

```
% \usetikzlibrary{patterns} % preamble
% \tcbuselibrary{skins}     % preamble
\tcbset{ribbonbox/.style={enhanced,colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,
  overlay={\path[fill=blue!75!white,draw=blue,double=white!85!blue,
    preaction={opacity=0.6,fill=blue!75!white},
    line width=0.1mm,double distance=0.2mm,
    pattern=fivepointed stars,pattern color=white!75!blue]
    ([xshift=-0.2mm,yshift=-1.02cm]frame.north east)
    -- ++(-1,1) -- ++(-0.5,0) -- ++(1.5,-1.5) -- cycle;}}}

\begin{tcolorbox}[ribbonbox,title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

/tcb/no overlay (style, no default, initially set)

Removes the overlay if set before.

/tcb/overlay broken=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process. /tcb/overlay→P. 74 overwrites this key.

/tcb/overlay unbroken=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 but *is not* broken actually or if the box is set to be /tcb/unbreakable→P. 380, then the ⟨*graphical code*⟩ is added to the box drawing process. /tcb/overlay→P. 74 overwrites this key.

/tcb/overlay first=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *first* part of the break sequence. /tcb/overlay→P. 74 overwrites this key.

/tcb/overlay middle=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *middle* parts (if any) of the break sequence. /tcb/overlay→P. 74 overwrites this key.

/tcb/overlay last=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *last* part of the break sequence. /tcb/overlay→P. 74 overwrites this key.

/tcb/overlay unbroken and first=⟨*graphical code*⟩ (no default, initially unset)

This is an optimized abbreviation for setting /tcb/overlay unbroken and /tcb/overlay first together. /tcb/overlay→P. 74 overwrites this key.

/tcb/overlay middle and last=⟨*graphical code*⟩ (no default, initially unset)

This is an optimized abbreviation for setting /tcb/overlay middle and /tcb/overlay last together. /tcb/overlay→P. 74 overwrites this key.

/tcb/overlay unbroken and last=⟨*graphical code*⟩ (no default, initially unset)

This is an optimized abbreviation for setting /tcb/overlay unbroken and /tcb/overlay last together. /tcb/overlay→P. 74 overwrites this key.

N 2014-09-19 **/tcb/overlay first and middle=**⟨*graphical code*⟩ (no default, initially unset)

This is an optimized abbreviation for setting /tcb/overlay first and /tcb/overlay middle together. /tcb/overlay→P. 74 overwrites this key.

This example demonstrates the application of break sequence specific overlay options. Here, we define an environment `myexample` based on `tcolorbox` where the visible drawing is done totally by overlay keys.
Here, the first application of `myexample` produces an unbroken `tcolorbox`. The frame is drawn by the code given with /tcb/overlay unbroken.
The second application of `myexample` is broken into several parts which are drawn by the codes given with /tcb/overlay first, /tcb/overlay middle, and /tcb/overlay last.

```
% Preamble:
%\usepackage{tikz,lipsum}
%\tcbuselibrary{skins,breakable}
%\newcounter{example}
```

```
\colorlet{colexam}{red!75!black}
\newtcolorbox[use counter=example]{myexample}{%
  empty,title={Example \thetcbcounter},attach boxed title to top left,
  boxed title style={empty,size=minimal,toprule=2pt,top=4pt,
    overlay={\draw[colexam,line width=2pt]
      ([yshift=-1pt]frame.north west)--([yshift=-1pt]frame.north east);}},
  coltitle=colexam,fonttitle=\Large\bfseries,
  before=\par\medskip\noindent,parbox=false,boxsep=0pt,left=0pt,right=3mm,top=4pt,
  breakable,pad at break*=0mm,vfill before first,
  overlay unbroken={\draw[colexam,line width=1pt]
    ([yshift=-1pt]title.north east)--([xshift=-0.5pt,yshift=-1pt]title.north-|frame.east)
    --([xshift=-0.5pt]frame.south east)--(frame.south west); },
  overlay first={\draw[colexam,line width=1pt]
    ([yshift=-1pt]title.north east)--([xshift=-0.5pt,yshift=-1pt]title.north-|frame.east)
    --([xshift=-0.5pt]frame.south east); },
  overlay middle={\draw[colexam,line width=1pt] ([xshift=-0.5pt]frame.north east)
    --([xshift=-0.5pt]frame.south east); },
  overlay last={\draw[colexam,line width=1pt] ([xshift=-0.5pt]frame.north east)
    --([xshift=-0.5pt]frame.south east)--(frame.south west);},%
}

\begin{myexample}
\lipsum[1]
\end{myexample}

\begin{myexample}
\lipsum[2-11]
\end{myexample}

\lipsum[12]% following text
```

Example 1

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Example 2

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed

lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetuer a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetuer. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero.

Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetuer odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetuer eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetuer tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

Floating box from `floatplacement`

This floating box is placed at the top of a page.

4.13 Floating Objects

/tcb/floatplacement=⟨*values*⟩ (no default, initially `htb`)

Sets ⟨*values*⟩ as default values for the usage of `/tcb/float` and `/tcb/float*`. Feasible are the usual parameters for floating objects.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,
   watermark color=red!15!white}

\begin{tcolorbox}[floatplacement=t,float,
                  title=Floating box from |floatplacement|,
                  watermark text={I am floating}]
  This floating box is placed at the top of a page.
\end{tcolorbox}
```

/tcb/float=⟨*values*⟩ (default from `floatplacement`)

Turns the box to a floating object where ⟨*values*⟩ are the usual parameters for such floating objects. If they are not used, the placement uses the default values given by `floatplacement`.

```
\begin{tcolorbox}[float, title=Floating box from |float|,
    enhanced,watermark text={I'm also floating}]
  This box floats to a feasible place automatically. You do not have to
  use a numbering for this floating object.
\end{tcolorbox}
```

Floating box from `float`

This box floats to a feasible place automatically. You do not have to use a numbering for this floating object.

/tcb/float*=⟨*values*⟩ (default from `floatplacement`)

Identical to `/tcb/float`, but for wide boxes spanning the whole page width of two column documents or in conjunction with the packages `multicol` or `paracol`. Note that you have to set `width=\textwidth` additionally, if the box should span the whole page width in these cases!

```
\begin{tcolorbox}[float*=b, title=Floating box from |float*|,width=\textwidth,
    enhanced,watermark text={I'm also floating}]
  In this single column document, you will see no difference to |float|.
\end{tcolorbox}
```

/tcb/nofloat (style, initially set)

Turns the floating behavior off.

Floating box from `float*`

In this single column document, you will see no difference to `float`.

N 2014-09-19 **/tcb/every float=**⟨*code*⟩ (no default, initially empty)

For floating objects, the /tcb/before → P. 81 and /tcb/after → P. 81 settings are ignored. Instead, the given ⟨*code*⟩ is inserted before a floating box. If the box is /tcb/breakable → P. 379, the given ⟨*code*⟩ is inserted before every part of the break sequence. The most common use case is every float=\centering.

```
\tcbox[float=htb,title={Floating box},every float=\centering,
  colback=blue!50!black,colframe=blue!50!white,colbacktitle=blue!10!white,
  coltitle=black,center title]
  {\includegraphics[height=6cm]{lichtspiel.jpg}}
```

Floating box

4.14 Embedding into the Surroundings

Typically, but not necessarily, a `tcolorbox` is put inside a separate paragraph and has some vertical space before and after it. This behavior is controlled by the keys `before` and `after`.

/tcb/before=⟨*code*⟩ (no default, initially see /tcb/autoparskip)

Sets the ⟨*code*⟩ which is executed before the colored box. It is not used for floating boxes. Also, it is not used, if the box follows a heading immediately and /tcb/ignore nobreak → P. 84 is set to `false`.

/tcb/after=⟨*code*⟩ (no default, initially see /tcb/autoparskip)

Sets the ⟨*code*⟩ which is executed after the colored box. It is not used for floating boxes.

U 2017-02-01 **/tcb/parskip** (style, no value)

Sets the keys `before` and `after` to values which are recommended, if the package `parskip` *is* used and there is no better idea for `before` and `after`. This is similar to:

```
\tcbset{parskip/.style={before={\par\pagebreak[0]\parindent=0pt},
                        after={\par}}}
```

U 2017-02-01 **/tcb/noparskip** (style, no value)

Sets the keys `before` and `after` to values which are recommended, if the package `parskip` is *not* used and there is no better idea for `before` and `after`. This is similar to:

```
\tcbset{noparskip/.style={before={\par\pagebreak[0]\smallskip\parindent=0pt},
                          after={\par\smallskip}}}
```

/tcb/autoparskip (style, no value, initially set)

Tries to detect the usage of the package `parskip` and sets the keys `before` and `after` accordingly. Actually, the following is done:

- If the length of `\parskip` is greater than `0pt` at the beginning of the document, /tcb/parskip is executed. Here, the usage of package `parskip` is *assumed*.
- Otherwise, if the length of `\parskip` is not greater than `0pt` at the beginning of the document, /tcb/noparskip is executed. Here, the absence of package `parskip` is *assumed*.

`autoparskip` is the default for the package `tcolorbox`, if `before` or `after` are not changed otherwise.

/tcb/nobeforeafter (style, no value)

Abbreviation for clearing the keys `before` and `after`. The colored box is not put into a paragraph and there is no space before or after the box.

```
\tcbset{myone/.style={colback=LightGreen,colframe=DarkGreen,
  equal height group=nobefaf,width=\linewidth/4,nobeforeafter}}
\begin{tcolorbox}[myone,title=Box 1]Box 1\end{tcolorbox}%
\begin{tcolorbox}[myone,title=Box 2]Box 2\end{tcolorbox}%
\begin{tcolorbox}[myone,title=Box 3]Box 3\end{tcolorbox}%
\begin{tcolorbox}[myone,title=Box 4]Box 4\end{tcolorbox}
```



/tcb/force nobeforeafter (style, no value)

Forces the setting of /tcb/nobeforeafter even if /tcb/before and /tcb/after are set to other values later. Do not use this option globally unless you *really* know what you do. Note that embedded boxes do not inherit this forced clearance.

/tcb/baseline=⟨*length*⟩ (no default, initially `0pt`)

Used to set the `\pgfsetbaseline` value of the resulting `tcolorbox`.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[baseline=3mm]
One line.
\end{tcolorbox}
\begin{tcolorbox}[baseline=3mm]
First line.\\Second line.
\end{tcolorbox}
```

Some text . . . . . One line. First line. Second line.

N 2014-10-10 **/tcb/box align=**⟨*alignment*⟩ (style, no default, initially `bottom`)

Used to set the `/tcb/baseline` value of the resulting `tcolorbox`. Feasible values for ⟨*alignment*⟩ are:

- `bottom`: alignment with the box bottom,
- `top`: alignment with the box top,
- `center`: alignment with the box center,
- `base`: alignment with the box content base. This option is not applicable for a `tcolorbox`→P. 12 but for a `\tcbox`→P. 14 only. It is an alias for `/tcb/tcbox raise base`→P. 99.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=bottom]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=bottom]
First line.\\Second line.
\end{tcolorbox}
```

Some text . . . . . One line. First line. Second line.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=top]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=top]
First line.\\Second line.
\end{tcolorbox}
```

Some text . . . . . One line. First line. Second line.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=center]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=center]
First line.\\Second line.
\end{tcolorbox}
```

Some text . . . . . One line. First line. Second line.

```
\tcbset{colframe=red!50!white,nobeforeafter}
Some text\dotfill
\tcbox[nobeforeafter,box align=base]{One line}
\tcbox[nobeforeafter,box align=base,size=fbox]{Another line}
```

Some text . . . . . One line Another line

N 2014-10-10
U 2015-03-16

/tcb/before skip=⟨*glue*⟩ (style, no default)

Inserts some vertical space of the given ⟨*glue*⟩ before the colored box. This style sets /tcb/before→ P. 81.

```
Some text.
\begin{tcolorbox}[before skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Some text.

This is a **tcolorbox**.

N 2014-10-10
U 2017-02-01

/tcb/after skip=⟨*glue*⟩ (style, no default)

Inserts some vertical space of the given ⟨*glue*⟩ after the colored box. This style sets /tcb/after→ P. 81.

```
\begin{tcolorbox}[after skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
Some text.
```

This is a **tcolorbox**.

Some text.

N 2014-10-10

/tcb/beforeafter skip=⟨*glue*⟩ (style, no default)

Inserts some vertical space of the given ⟨*glue*⟩ before *and* after the colored box. This style sets /tcb/before→ P. 81 and /tcb/after→ P. 81.

```
\tcbset{beforeafter skip=0pt,
  colframe=red!50!white}
\begin{tcolorbox}
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}
  Second box.
\end{tcolorbox}
```

This is a **tcolorbox**.

Second box.

N 2014-11-07 **/tcb/left skip=⟨*length*⟩** (style, no default, initially 0mm)

Inserts some horizontal space of the given ⟨*length*⟩ before the colored box. This style sets /tcb/grow to left by→P. 87 with the negated ⟨*length*⟩, i.e. the bounding box and box width are changed.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[left skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-11-07 **/tcb/right skip=⟨*length*⟩** (style, no default, initially 0mm)

Inserts some horizontal space of the given ⟨*length*⟩ after the colored box. This style sets /tcb/grow to right by→P. 87 with the negated ⟨*length*⟩, i.e. the bounding box and box width are changed.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[right skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-10 **/tcb/leftright skip=⟨*length*⟩** (style, no default)

Inserts some horizontal space of the given ⟨*length*⟩ before *and* after the colored box. This style changes the bounding box and the box width.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[leftright skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-12-11 **/tcb/ignore nobreak=true|false** (default true, initially false)

After a heading, LaTeX tries to avoid a break by setting a nobreak boolean value. Starting from version 3.33, the /tcb/before→P. 81 respectively /tcb/before skip→P. 83 settings are not used after a heading if /tcb/ignore nobreak is set to **false**. For an unbreakable box, /tcb/before nobreak is used instead. Further, a /tcb/breakable→P. 379 box will also try to avoid a break between a heading and a directly following first part of a break sequence. Set /tcb/ignore nobreak to **true**, if nobreak should be ignored as prior to version 3.33. Also, such a setting may be used locally to enforce the /tcb/before→P. 81 setting.

N 2014-12-16 **/tcb/before nobreak=⟨*code*⟩** (no default, initially \noindent)

Sets the ⟨*code*⟩ which is executed before the colored box if it is unbreakable, if /tcb/ignore nobreak is not set, and if the box follows a heading.

N 2017-02-23 **/tcb/parfillskip restore=true|false** (default true, initially true)

If this option is set to be true, the minimum value of \parfillskip is tested at specific spots, if it is greater than 0pt. If so, \parfillskip is restored to \@flushglue which happens to be the default value.

These tests are executed for /tcb/parskip→P. 81, /tcb/noparskip→P. 81, /tcb/after skip→P. 83, /tcb/breakable→P. 379, and tcbraster→P. 290.

This option was created to automatically avoid overfull box warnings with \parfillskip changing packages.

4.15 Bounding Box

Normally, every `tcolorbox` has a bounding box which fits exactly to the dimensions of the outer frame. Therefore, LaTeX reserves exactly the space needed for the box. This behavior can be changed by enlarging (or shrinking) the bounding box. If the bounding box is enlarged, the `tcolorbox` will get some clearance around it. If the bounding box is shrunk, i. e. enlarged with negative values, the `tcolorbox` will overlap to other parts of the page. For example, the `tcolorbox` could be stretched into the page margin.

> **!** The following examples use `/tcb/show bounding box` → P. 183 to display the actual bounding box. For this, the library LIB skins has to be included and `/tcb/enhanced` → P. 211 has to be set.

4.15.1 Shifting Bounding Box Borders

`/tcb/enlarge top initially by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the top of the box by ⟨*length*⟩. If the box is *breakable*, only the first box of the break sequence gets enlarged. `/tcb/enlarge top by` → P. 86 overwrites this key.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge top initially by=-5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge top initially by=5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

`/tcb/enlarge bottom finally by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the bottom of the box by ⟨*length*⟩. If the box is *breakable*, only the last box of the break sequence gets enlarged. `/tcb/enlarge bottom by` → P. 86 overwrites this key.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge bottom finally by=5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge bottom finally by=-5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

/tcb/enlarge top at break by=⟨*length*⟩ (no default, initially 0mm)

Enlarges the bounding box distance to the top of the box by ⟨*length*⟩, *if* the box is /tcb/breakable→P. 379. In this case, it is applied to *middle* and *last* parts in a break sequence. /tcb/enlarge top by overwrites this key.

/tcb/enlarge bottom at break by=⟨*length*⟩ (no default, initially 0mm)

Enlarges the bounding box distance to the bottom of the box by ⟨*length*⟩, *if* the box is /tcb/breakable→P. 379. In this case, it is applied to *first* and *middle* parts in a break sequence. /tcb/enlarge bottom by overwrites this key.

/tcb/enlarge top by=⟨*length*⟩ (no default, initially 0mm)

Enlarges the bounding box distance to the top of the box by ⟨*length*⟩. /tcb/enlarge top initially by→P. 85 and /tcb/enlarge top at break by are set to ⟨*length*⟩.

/tcb/enlarge bottom by=⟨*length*⟩ (no default, initially 0mm)

Enlarges the bounding box distance to the bottom of the box by ⟨*length*⟩. /tcb/enlarge bottom finally by→P. 85 and /tcb/enlarge bottom at break by are set to ⟨*length*⟩.

/tcb/enlarge left by=⟨*length*⟩ (no default, initially 0mm)

Enlarges the bounding box distance to the left side of the box by ⟨*length*⟩.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge left by=2cm,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge left by=-2cm,width=\linewidth+2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



/tcb/enlarge right by=⟨*length*⟩ (no default, initially 0mm)

Enlarges the bounding box distance to the right side of the box by ⟨*length*⟩.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge right by=-2cm,width=\linewidth+2cm,
  enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge right by=2cm,width=\linewidth-2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



/tcb/enlarge by=⟨*length*⟩ (no default, initially 0mm)

Enlarges the bounding box distance to all sides of the box by ⟨*length*⟩.

```
\tcbset{colframe=blue!75!black,colback=white,width=5cm,nobeforeafter}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge by=5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

/tcb/grow to left by=⟨*length*⟩ (no default, initially 0mm)

Enlarges the current box width by ⟨*length*⟩ and enlarges (shrinks) the bounding box distance to the left side of the box by −⟨*length*⟩. Also see /tcb/left skip → P. 84.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[width=5cm,grow to left by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox} with a width of 7cm.
\end{tcolorbox}
```

This is a **tcolorbox** with a width of 7cm.

/tcb/grow to right by=⟨*length*⟩ (no default, initially 0mm)

Enlarges the current box width by ⟨*length*⟩ and enlarges (shrinks) the bounding box distance to the right side of the box by −⟨*length*⟩. Also see /tcb/right skip → P. 84.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[grow to right by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\bigskip

\begin{tcolorbox}[grow to right by=2cm,grow to left by=1cm,
  enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

N 2018-03-22 **/tcb/grow sidewards by=⟨*length*⟩** (no default, initially 0mm)

Shortcut for setting /tcb/grow to left by→ P. 87 and /tcb/grow to right by→ P. 87 to ⟨*length*⟩. Also see /tcb/oversize→ P. 45 and /tcb/spread sidewards→ P. 91.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[grow sidewards by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

4.15.2 Box Alignment

N 2015-11-20 **/tcb/flush left** (style, no value)

Enlarges the bounding box to the right side to fill the line completely.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[flush left,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2015-11-20 **/tcb/flush right** (style, no value)

Enlarges the bounding box to the left side to fill the line completely.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[flush right,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2015-11-20 **/tcb/center** (style, no value)

Enlarges the bounding box equally to both sides to fill the line completely.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[center,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

Floating box from toggle enlargement

This page is an odd page. Therefore, the left and right enlargements are not toggled. This box stretches to the right margin on odd pages and to the left margin on even pages. The current document is one-sided – this feature makes sense for two-sided documents only.

4.15.3 Toggle Enlargements

U 2015-11-13 `/tcb/toggle enlargement=`⟨*toggle preset*⟩ (default `evenpage`, initially `none`)

According to the ⟨*toggle preset*⟩, the left and the right enlargements of the bounding box are switched or not. Feasible values are:

- `none`: no switching.
- `forced`: the values of the left and right enlargement are switched.
- `evenpage`: if the page is an even page, the values of the left and right enlargement are switched. This value also sets `/tcb/check odd page` → P. 104 to `true`.

! See `/tcb/toggle left and right` → P. 46 to toggle geometry settings.

```
\tcbset{colframe=blue!75!black,colback=white,
  grow to left by=20mm,grow to right by=-5mm}

\begin{tcolorbox}[toggle enlargement=none,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[toggle enlargement=forced]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[toggle enlargement=evenpage]
  This page is an \tcbifoddpage{odd}{even} page.
  Therefore, the left and right enlargements
  \tcbifoddpage{are not}{are} toggled.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

This page is an odd page. Therefore, the left and right enlargements are not toggled.

```
\begin{tcolorbox}[colframe=red!60!black,colback=red!15!white,
  fonttitle=\bfseries,title=Floating box from \texttt{toggle enlargement},
  width=\textwidth,grow to right by=2cm,toggle enlargement,float=t]
  This page is an \tcbifoddpage{odd}{even} page.
  Therefore, the left and right enlargements \tcbifoddpage{are not}{are} toggled.
  This box stretches to the right margin on odd pages and to the left
  margin on even pages. The current document is one-sided -- this feature makes
  sense for two-sided documents only.
\end{tcolorbox}
```

4.15.4 Spread Box to Page Borders

> **!** The following border options are *not* applicable to nested boxes, boxes insides tables, etc. For boxes inside lists, the options *may* work, but not necessarily. Also, boxes should be set with `\noindent` and full width.

N 2017-02-13 **/tcb/spread inwards=**⟨*length*⟩ (default `0pt`, initially unset)

Enlarges the current box width to match the inner page border (left-handed side for one-sided documents). If the optional ⟨*length*⟩ is greater than `0pt`, the box grows over the border, if ⟨*length*⟩ is lower than `0pt`, there is a margin between box and page border. `/tcb/toggle enlargement` → P. 89 is set automatically.

```
\begin{tcolorbox}[enhanced,spread inwards,
  colframe=blue!75!black,colback=white,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2017-02-13 **/tcb/spread outwards=**⟨*length*⟩ (default `0pt`, initially unset)

Enlarges the current box width to match the outer page border (right-handed side for one-sided documents). If the optional ⟨*length*⟩ is greater than `0pt`, the box grows over the border, if ⟨*length*⟩ is lower than `0pt`, there is a margin between box and page border. `/tcb/toggle enlargement` → P. 89 is set automatically.

```
\begin{tcolorbox}[enhanced,spread outwards,
  colframe=blue!75!black,colback=white,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2017-02-13 **/tcb/move upwards=**⟨*length*⟩ (default `0pt`, initially unset)

Starts a new page with the box at the very top page border. If the optional ⟨*length*⟩ is greater than `0pt`, the box moves over the border, if ⟨*length*⟩ is lower than `0pt`, there is a margin between box and page border.

N 2017-02-13 **/tcb/move upwards*=**⟨*length*⟩ (default `0pt`, initially unset)

Identical to `/tcb/move upwards`, but without starting a new page.

N 2017-02-13 **/tcb/fill downwards=**⟨*length*⟩ (default `0pt`, initially unset)

Enlarges the height of the box until the very bottom page border. The library LIB breakable has to be loaded, and `/tcb/height fill` → P. 56 is set automatically. If the optional ⟨*length*⟩ is greater than `0pt`, the box moves over the border, if ⟨*length*⟩ is lower than `0pt`, there is a margin between box and page border.

```
\begin{tcolorbox}[enhanced,fill downwards,
  colframe=blue!75!black,colback=white,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is an example for “spread upwards”.

N 2017-02-13 **/tcb/spread upwards=**⟨*length*⟩ (default Opt, initially unset)

Combination of /tcb/move upwards→P. 90, /tcb/spread inwards→P. 90, and /tcb/spread outwards→P. 90. The optional ⟨*length*⟩ is used for all these keys.

```
\begin{tcolorbox}[enhanced,spread upwards,sharp corners=north,height=3cm,
  colframe=blue!75!black,interior style={top color=blue!50,bottom color=white}]
This is an example for \enquote{spread upwards}.
\end{tcolorbox}
```

N 2017-02-13 **/tcb/spread upwards*=**⟨*length*⟩ (default Opt, initially unset)

Identical to /tcb/move upwards→P. 90, but without starting a new page.

N 2017-02-13 **/tcb/spread sidewards=**⟨*length*⟩ (default Opt, initially unset)

Combination of /tcb/spread inwards→P. 90 and /tcb/spread outwards→P. 90. The optional ⟨*length*⟩ is used for all these keys. Also see /tcb/oversize→P. 45 and /tcb/grow sidewards by→P. 88.

```
\begin{tcolorbox}[enhanced,spread sidewards,
  colframe=blue!75!black,colback=white,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2017-02-13 **/tcb/spread=**⟨*length*⟩ (default Opt, initially unset)

Combination of /tcb/move upwards→P. 90, /tcb/fill downwards→P. 90, /tcb/spread inwards→P. 90, and /tcb/spread outwards→P. 90. Such, the box fills the whole page. The optional ⟨*length*⟩ is used for all these keys.

N 2017-02-13 **/tcb/spread downwards=**⟨*length*⟩ (default Opt, initially unset)

Combination of /tcb/fill downwards→P. 90, /tcb/spread inwards→P. 90, and /tcb/spread outwards→P. 90. The optional ⟨*length*⟩ is used for all these keys.

```
\begin{tcolorbox}[enhanced,spread downwards,sharp corners=south,
  colframe=red!75!black,interior style={top color=white,bottom color=red!50}]
This is an example for \enquote{spread downwards}.
\end{tcolorbox}
```

This is an example for “spread downwards”.

4.15.5 Box Extrusion

! The following keys should not be used with breakable boxes or boxes with a lower part.

/tcb/shrink tight (style, no value, initially unset)

The total colored box is shrunk to the dimensions of the upper part. There should be no lower part and no title. This style sets the /tcb/boxsep → P. 39 to 0pt and other geometry keys to fitting values. This option is likely to be used with the following extrusion keys.

```
\tcbset{colframe=blue!75!black,colback=white,arc=0mm,boxrule=0.4pt,
        nobeforeafter,tcbox raise base,shrink tight}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}

Lorem \tcbox{ipsum} dolor sit amet, consectetuer adipiscing elit.
```

This is a **tcolorbox**.
Lorem ipsum dolor sit amet, consectetuer adipiscing elit.

U 2014-09-19 **/tcb/extrude left by=**⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to the left side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbox[extrude left by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.

U 2014-09-19 **/tcb/extrude right by=**⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to the right side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbox[extrude right by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.

/tcb/extrude top by=⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to the top side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbox[extrude top by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.

/tcb/extrude bottom by=⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to the bottom side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbox[extrude bottom by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.

/tcb/extrude by=⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to all sides. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis. \tcbox{Curabitur} dictum
gravida mauris. \tcbox[colframe=Green,interior style={opacity=0.0}]{Nam}
arcu libero, nonummy eget, consectetuer id, \tcbox{vulputate} a, magna. Donec
vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus
et malesuada fames ac turpis egestas. \tcbox{Mauris ut leo.}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo.

4.16 Layered Boxes and Every Box Settings

A `tcolorbox` may contain another `tcolorbox` and so on. The package takes track of the nesting level using a counter `tcblayer`. Counter values may be used for doing some fancy things, but you should never change the counter value yourself.

The package takes special care for the first four layers or nesting levels, called managed layers. Here, footnote texts are administrated to find their intended place and specific layer dependent options may be set by changing `/tcb/every box on layer n`→P. 95. If needed, the number of managed layers can be increased by setting `\tcbsetmanagedlayers`→P. 95 to a higher value than 4.

The following styles have a considerable influence on how layered boxes are processed. Note especially that nested boxes are getting a `/tcb/reset`→P. 109 by default. You can change this, but be prepared for surprises if you do.

If the defaults are *not changed*, a `tcolorbox` gets its options in the following order. Following options overwrite preceding options.

1. On package load, all options are set to default values.
2. Every `\tcbset`→P. 13 command adds or changes options for the following boxes inside the current TEX group.
3. While entering a `tcolorbox`, a `/tcb/every box on layer n`→P. 95 or `/tcb/every box on higher layers`→P. 95 option list is applied. With default settings this means:
   - For layer 1 (lowest layer), the `/tcb/every box` option list is applied. Not overwritten options given by a preceding `\tcbset`→P. 13 survive.
   - For layer 2 and above (nested boxes), a `/tcb/reset`→P. 109 followed by `/tcb/every box` option list is applied. Every resettable options given by a preceding `\tcbset`→P. 13 and by the sourrounding box(es) are reset.
4. The ⟨*options*⟩ given to the `tcolorbox` are applied. Or, if the box was generated by `\newtcolorbox`→P. 15 or friends, the ⟨*options*⟩ given there are applied.
5. If the box was generated by `\newtcolorbox`→P. 15 or friends, some automated options are applied.

`/tcb/every box` (style)

By default, this style is empty.

```
% default setting:
\tcbset{every box/.style={}}
```

It may be changed by redefining this style.

```
% setting all boxes to be enhanced:
\tcbset{every box/.style={enhanced}}
```

> **!** The alternative for setting something for every box (on every layer) is `\tcbsetforeverylayer`→P. 13:
>
> ```
> % setting all boxes to be enhanced:
> \tcbsetforeverylayer{enhanced}
> ```

/tcb/every box on layer n (style)

Here, n has to be replaced by a number ranging from 1 to the highest managed layer number (4 by default).

```
% default settings:
\tcbset{
  every box on layer 1/.style={every box},
  every box on layer 2/.style={reset,every box},
  every box on layer 3/.style={reset,every box},
  every box on layer 4/.style={reset,every box},
  }
```

/tcb/every box on higher layers (style)

Higher layers are layers above the highest managed layer number (4 by default).

```
\tcbset{every box on higher layers/.style={reset,every box}}
```

\tcbsetmanagedlayers{⟨*number*⟩}

Replaces the highest managed layer number by ⟨*number*⟩ where 4 is the default. This macro can only be used inside the preamble. Using a ⟨*number*⟩ lower than 4 typically makes no sense, but is not forbidden.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins,breakable}
\tcbset{colframe=red!75!black,fonttitle=\bfseries,
  colback=red!5!white,
  every box/.style={enhanced,watermark text=\thetcblayer,
    before=\par\smallskip,after=\par\smallskip},
  every box on layer 2/.style={reset,every box,colback=yellow!10!white,
    drop fuzzy shadow}}
\begin{tcolorbox}[enhanced jigsaw,breakable,title=Layer 1 Box]
Here comes a footnote\footnote{Footnote from layer 1 box}.
\lipsum[2]
  \begin{tcolorbox}[title=Layer 2 Box]
  abc\footnote{The footnote of abc}
  \end{tcolorbox}
  \begin{tcolorbox}[title=Another Box,ams equation]
    \tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} = \infty.
  \end{tcolorbox}
Some text\footnote{Footnote from some text}.
  \begin{tcolorbox}[title=Yet Another Box]
    \tcboxfit[height=2cm]{\lipsum[1]}
    My text.
    \begin{tcolorbox}
      Another lipsum text\footnote{A lipsum text}. \lipsum[3]
      \begin{tcolorbox}[title=Layer 4,colframe=blue,colback=white]
        Layer 4\footnote{Layer 4 footnote}
      \end{tcolorbox}
      The End\footnote{Last footnote}.
    \end{tcolorbox}
  \end{tcolorbox}
\end{tcolorbox}
```

Layer 1 Box

Here comes a footnote[a]. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae

ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Layer 2 Box

abc[a]

[a] The footnote of abc

Another Box

$$\boxed{\sum_{n=1}^{\infty} \frac{1}{n}} = \infty. \tag{1}$$

Some text[b].

Yet Another Box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My text.

Another lipsum text[a]. Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Layer 4

Layer 4[a]

[a] Layer 4 footnote

The End[b].

[a] A lipsum text
[b] Last footnote

[a] Footnote from layer 1 box
[b] Footnote from some text

4.17 Capture Mode

/tcb/capture=⟨*mode*⟩ (no default, initially `minipage`)

The capture ⟨*mode*⟩ defines how the box content is processed.
Feasible values for ⟨*mode*⟩ are:

- **minipage**:
  This is the default ⟨*mode*⟩ for `tcolorbox` → P. 12. The content may have an upper and a lower part. Optionally, the box can be `/tcb/breakable` → P. 379. The box content is put into a minipage or into something similar to a minipage.
- **hbox**:
  This is the default ⟨*mode*⟩ for `\tcbox` → P. 14. The content cannot have a lower part and cannot be broken. The colored box is sized according to the dimensions of the content. A shortcut to set this mode is `/tcb/hbox`.
- **fitbox**: (needs the LIB fitting library)
  This is the default ⟨*mode*⟩ for `\tcboxfit` → P. 426. The content cannot have a lower part and cannot be broken. The content is sized according to the dimensions of the colored box. A shortcut to set this mode is `/tcb/fit` → P. 429.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[capture=minipage]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[capture=hbox]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[capture=fitbox,height=9mm]% needs the `fitting' library
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

This is a tcolorbox.

/tcb/hbox (style, no default)

Shortcut for `capture=hbox`.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[hbox]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/minipage (style, no default)

Shortcut for `capture=minipage`.

4.18 Text Characteristics

U 2015-10-14 **/tcb/parbox=true|false** (default `true`, initially `true`)

The text inside a `tcolorbox` is formatted using a LaTeX `minipage` if the box is unbreakable. If breakable, the box tries a mimicry of a `minipage`. In a `minipage` or `parbox`, paragraphs are formatted slightly different as the main text. If the key value is set to `false`, the normal main text behavior is restored. In some situations, this has some unwanted side effects. It is recommended that you use this experimental setting only where you really want to have this feature.

```
% \usepackage{lipsum}  % preamble
\tcbset{width=(\linewidth-2mm)/2,nobeforeafter,arc=1mm,
  colframe=blue!75!black,colback=white,fonttitle=\bfseries,fontupper=\small,
  left=2mm,right=2mm,top=1mm,bottom=1mm,equal height group=parbox}

\begin{tcolorbox}[parbox,adjusted title={parbox=true (normal)}]
  \lipsum[1-2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[parbox=false,adjusted title={parbox=false}]
  \lipsum[1-2]
\end{tcolorbox}%
```

parbox=true (normal)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

parbox=false

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/hyphenationfix=true|false (default `true`, initially `false`)

Long words at the beginning of paragraphs in very narrow boxes will not be hyphenated using `pdflatex`. This problem is circumvented by applying the `hyphenationfix` option.

```
\tcbset{colframe=blue!75!black,
  fontupper=\normalsize,
  colback=blue!5!white,width=4cm}

\begin{tcolorbox}
Rechnungsadjunktentochter.\par
Statthaltereikonzipist.
\end{tcolorbox}

\begin{tcolorbox}[hyphenationfix]
Rechnungsadjunktentochter.\par
Statthaltereikonzipist.
\end{tcolorbox}
```

Rechnungsadjunktentochter.
Statthaltereikonzipist.

Rechnungsad-
junktentochter.
Statthal-
tereikonzipist.

> **!** `parbox=false` and `hyphenationfix` should not be used together. They are targeting different box types and they do not blend very well.

4.19 Files

/tcb/tempfile=⟨*file name*⟩ (no default, initially `\jobname.tcbtemp`)

Sets ⟨*file name*⟩ as name for the temporary file which is used inside `tcbwritetemp`→ P. 129 and `\tcbusetemp`→ P. 129 implicitely.

4.20 `\tcbox` Specials

The following options are applicable for `\tcbox`→ P. 14 and `\tcboxmath`→ P. 354 only.

/tcb/tcbox raise=⟨*length*⟩ (no default, initially `0pt`)

Raises the `\tcbox`→ P. 14 by the given ⟨*length*⟩.

```
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
        fonttitle=\bfseries,nobeforeafter,center title}

Test\dotfill
\tcbox[tcbox raise base]{Hello World 1}\dotfill
\tcbox{Hello World 2}\dotfill
\tcbox[tcbox raise=5mm]{Hello World 3}
```

Test . . . . . Hello World 1 . . . . . Hello World 2 . . . . . Hello World 3

/tcb/tcbox raise base (style, no value, initially unset)

Raises the `\tcbox`→ P. 14 such that the base of its content matches the base of the environmental line; see example above.

/tcb/on line (style, no value, initially unset)

Combines `/tcb/tcbox raise base` with `/tcb/nobeforeafter`→ P. 81. The resulting box behaves analogue to `\fbox`.

N 2015-03-23 **/tcb/tcbox width=**⟨*mode*⟩ (no default, initially `auto`)

Controls how `\tcbox` → P. 14 respects a `/tcb/width` → P. 34 setting. Feasible values for ⟨*mode*⟩ are:

- **`auto`** (initial setting): ignore `/tcb/width` → P. 34 and set box width according to its content.
- **`auto limited`**: Set box width according to its content, if it is smaller than `/tcb/width` → P. 34. Otherwise, the content is set like in a `tcolorbox` → P. 12 with line breaks.
- **`forced center`**: Set box width according to `/tcb/width` → P. 34. The content is centered and may overlap the box borders.
- **`forced left`**: Set box width according to `/tcb/width` → P. 34. The content is left aligned and may overlap the box borders.
- **`forced right`**: Set box width according to `/tcb/width` → P. 34. The content is right aligned and may overlap the box borders.
- **`minimum center`**: Set box width according to `/tcb/width` → P. 34, if the content fits into. The content is centered and the box width may grow beyond `/tcb/width` → P. 34.
- **`minimum left`**: Set box width according to `/tcb/width` → P. 34, if the content fits into. The content is left aligned and the box width may grow beyond `/tcb/width` → P. 34.
- **`minimum right`**: Set box width according to `/tcb/width` → P. 34, if the content fits into. The content is right aligned and the box width may grow beyond `/tcb/width` → P. 34.

```
\tcbset{size=small,on line,before upper=\strut,
  colframe=blue!75!black,colback=blue!5!white,
  fontupper=\normalsize,width=4cm}

\tcbox[tcbox width=auto]{auto}\qquad
\tcbox[tcbox width=auto limited]{auto limited}\qquad
\tcbox[tcbox width=auto limited]{auto limited with long text}\\
\tcbox[tcbox width=forced center]{forced center}\qquad
\tcbox[tcbox width=forced center]{forced center with long text}\\
\tcbox[tcbox width=forced left]{forced left}\qquad
\tcbox[tcbox width=forced left]{forced left with long text}\\
\tcbox[tcbox width=forced right]{forced right}\qquad
\tcbox[tcbox width=forced right]{forced right with long text}\\
\tcbox[tcbox width=minimum center]{minimum center}\qquad
\tcbox[tcbox width=minimum center]{minimum center with long text}\\
\tcbox[tcbox width=minimum left]{minimum left}\qquad
\tcbox[tcbox width=minimum left]{minimum left with long text}\\
\tcbox[tcbox width=minimum right]{minimum right}\qquad
\tcbox[tcbox width=minimum right]{minimum right with long text}
```



4.21 Counters, Labels, and References

/tcb/phantom=⟨*code*⟩ (no default, initially unset)

The ⟨*code*⟩ is put in a box at the upper left corner of the `tcolorbox`. If the `tcolorbox` is breakable, the ⟨*code*⟩ is executed for the first box of the break sequence only. If there already was some phantom code given, the new ⟨*code*⟩ is appended.

The ⟨*code*⟩ is intended to be used for counter stepping, labelling, and related operations which do not produce visible text.

- The ⟨*code*⟩ is executed before the title and box content, i. e. counter values are ensured to be increased before usage.
- Labels are ensured to reference the correct page number.
- The ⟨*code*⟩ is executed only once even during fitting operations for title and box content.
- In combination with the `hyperref` package, the hyper anchor is set to the upper left corner of the `tcolorbox`, i. e. links inside the pdf document will jump to the box pleasantly.
- Since the ⟨*code*⟩ is executed inside a TEX group, only global operations can survive this group.

Examples for the `phantom` usage are given in Section 16.9 from page 346, e. g. Example 16.1 on page 347.

/tcb/nophantom (no value, initially set)

Removes the phantom code if set before.

/tcb/label=⟨*marker*⟩ (no default, initially unset)

The ⟨*marker*⟩ is set as label text for a reference with the `\ref` macro. Typically, this option is used for numbered boxes, see Subsection 5.1 from page 111, e. g. `/tcb/new/auto counter` → P. 111.

N 2014-11-28 **/tcb/phantomlabel**=⟨*marker*⟩ (no default, initially unset)

Equivalent to `/tcb/label` for an *unnumbered* box. A `\phantomsection` from the package `hyperref` [15] is used to set a correct hyperlink target. This is not needed for a numbered box.

/tcb/label type=⟨*type*⟩ (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. ⟨*type*⟩ has to be a cross-reference type *known* to `cleveref` like `theorem`, `algorithm`, `result`, etc. References made with `cleveref` will use this type. Note that using `label type` will result in compilation errors, if `cleveref` is not loaded. For an example, see Theorem 17.3.5 on page 373.

/tcb/no label type (no value, initially set)

Removes a `/tcb/label type`, if set before.

/tcb/step=⟨*counter*⟩ (no default, initially unset)

Shortcut for `phantom={\refstepcounter{#1}}`. The given ⟨*counter*⟩ is increased and ready for labelling. This option is not needed when using the convenient automated numbering introduced with version 2.40, see Subsection 5.1 from page 111.

/tcb/step and label={⟨*counter*⟩}{⟨*marker*⟩} (no default, initially unset)

Shortcut for using `/tcb/step` and `/tcb/label`. This option is not needed when using the convenient automated numbering introduced with version 2.40, see Subsection 5.1 from page 111.

/tcb/list entry=⟨*text*⟩ (no default, initially unset)

If the «list of tcolorbox(es)» feature described in Subsection 5.2 from page 118 is used, this key describes the ⟨*text*⟩ for an entry into the generated list, e. g.

```
list entry={\protect\numberline{\thetcbcounter}My beautiful Example}
```

See Section 16.9 from page 346 for a complete example.

N 2014-09-19 **/tcb/list text=⟨*text*⟩** (style, no default)

This is a shortcut for setting /tcb/list entry to \protect\numberline{\thetcbcounter}⟨*text*⟩. So, the following settings are identical:

```
list text={My beautiful Example},
list entry={\protect\numberline{\thetcbcounter}My beautiful Example}
```

See Section 16.9 from page 346 for a complete example.

/tcb/add to list={⟨*list*⟩}{⟨*type*⟩} (no default, initially unset)

If the «list of tcolorbox(es)» feature described in Subsection 5.2 from page 118 is used, list entries are generated automatically. With this key, you can enforce an entry to the given ⟨*list*⟩ with the given ⟨*type*⟩. This issues:
\addcontentsline{⟨*list*⟩}{⟨*type*⟩}{⟨*entry text*⟩}

N 2016-06-22
U 2016-11-18 **/tcb/nameref=⟨*text*⟩** (no default, initially unset)

If the nameref package is loaded, the given ⟨*text*⟩ is used for corresponding \nameref macros. Typically, the ⟨*text*⟩ will be chosen to be identical or nearly identical to the one for /tcb/title → P. 18.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Examp.~\thetcbcounter: #2,#1}
```

```
\begin{pabox}[label={mynamelabel},nameref={Title or anything else}]{Title text}
This is a tcolorbox.
\end{pabox}
This box is automatically numbered with \ref{mynamelabel} on page
\pageref{mynamelabel}.

The box is titled \enquote{\nameref{mynamelabel}}.
```

Examp. 4.1: Title text

This is a tcolorbox.

This box is automatically numbered with 4.1 on page 102.
The box is titled "Title or anything else".

! /tcb/nameref is used automatically inside \newtcbtheorem → P. 352.

N 2017-02-03 **/tcb/hypertarget=⟨*marker*⟩** (no default, initially unset)

A \hypertarget from the package hyperref [15] is used to create an internal link of an anchor ⟨*marker*⟩. This ⟨*marker*⟩ can be referenced by \hyperlink or /tcb/hyperlink → P. 203.

```
% \usepackage{hyperref}%
\begin{tcolorbox}[enhanced,
  colback=red!10,colframe=red!50!black,
  hypertarget=hypertwinA,
  hyperlink=hypertwinB,
  title=Box A]
Click me to jump to Box B.
\end{tcolorbox}
```

Box A

Click me to jump to Box B.

N 2017-02-10 **/tcb/bookmark=⟨*text*⟩** (no default, initially unset)

Sets a PDF bookmark with the given ⟨*text*⟩, if the package bookmark [10] is loaded. This bookmark is set with an automated destination (the current box) and is set one level below the current bookmark level.

```
% \usepackage{bookmark}%
\begin{tcolorbox}[colback=blue!10,colframe=blue!50!black,
  bookmark=Example for using a bookmark,
  title=Example for using a bookmark]
Open the bookmark view of the previewer
to see the bookmark.
\end{tcolorbox}
```

Example for using a bookmark

Open the bookmark view of the previewer to see the bookmark.

N 2017-02-10 **/tcb/bookmark*={⟨*options*⟩}{⟨*text*⟩}** (no default, initially unset)

Identical to /tcb/bookmark, but additional ⟨*options*⟩ from the package bookmark [10] can be given.

```
% \usepackage{bookmark}%
\begin{tcolorbox}[colback=red!10,colframe=red!50!black,
  bookmark*={color=red,italic,bold}%
            {Another bookmark example},
  title=Red and bold bookmark]
Open the bookmark view of the previewer
to see the bookmark.
\end{tcolorbox}
```

Red and bold bookmark

Open the bookmark view of the previewer to see the bookmark.

N 2018-07-26 **/tcb/index=⟨*entry*⟩** (no default, initially unset)

Adds an index ⟨*entry*⟩ for the box. This is a shortcut for setting \index{⟨*entry*⟩} to /tcb/phantom → P. 101.

N 2018-07-26 **/tcb/index*={⟨*name*⟩}{⟨*entry*⟩}** (no default, initially unset)

Adds an ⟨*entry*⟩ to an index with a specific ⟨*name*⟩. This is a shortcut for setting \index[⟨*name*⟩]{⟨*entry*⟩} to /tcb/phantom → P. 101. An index extension package like imakeidx has to be loaded to use this option key.

4.22 Even and Odd Pages

> **!** Also see `/tcb/toggle left and right` → P. 46 and `/tcb/toggle enlargement` → P. 89 for further even/odd options.

U 2015-11-13 `/tcb/check odd page=true|false` (default `true`, initially `false`)

If set to `true`, a precise even/odd page testing for the current box is applied. This is done by using labels. If a box moves to another page, the document has to be compiled twice for the correct settings. If set to `false`, even/odd page tests may give wrong results for the first box of a page.
`/tcb/toggle left and right` → P. 46, `/tcb/toggle enlargement` → P. 89, and `/tcb/if odd page` automatically set `check odd page`, but for `\tcbifoddpage` → P. 106 this option has to be set explicitely.

N 2015-11-13 `/tcb/if odd page={`⟨*odd options*⟩`}{`⟨*even options*⟩`}` (style, no default)

If the current box is on an odd page, the ⟨*odd options*⟩ are applied. On an even page, the ⟨*even options*⟩ are applied. `/tcb/check odd page` is automatically set for precise even/odd page testing.

```
\begin{tcolorbox}[if odd page={colback=yellow!50}{colback=red!50}]
  This box is colored in yellow on an odd page
  and is colored in red on an even page.
\end{tcolorbox}
```

This box is colored in yellow on an odd page and is colored in red on an even page.

> **!** If a box is `/tcb/breakable` → P. 379, using `/tcb/if odd page` only acts upon the *first* box. If the setting should be repeated for every partial box of the break sequence, the option should be packed into `/tcb/extras` → P. 385. In this case, `/tcb/check odd page` has to be set explicitely! Also see `/tcb/if odd page*` → P. 105.

N 2016-11-18 `/tcb/if odd page or oneside={`⟨*odd options*⟩`}{`⟨*even options*⟩`}` (style, no default)

For onesided documents, the ⟨*odd options*⟩ are applied always. For twosided documents, this style is identical to `/tcb/if odd page`.

N 2015-11-13 **/tcb/if odd page*={⟨*odd options*⟩}{⟨*even options*⟩}** (style, no default)

> ! This option needs the breakable library, see Section 18 on page 377.

For breakable boxes, if the current partial box is on an odd page, the ⟨*odd options*⟩ are applied. On an even page, the ⟨*even options*⟩ are applied. /tcb/check odd page→P. 104 is automatically set for precise even/odd page testing.
In contrast to /tcb/if odd page→P. 104, /tcb/if odd page* is used on *every* partial box of a break sequences and not only on the *first* box. Another difference is that /tcb/if odd page* is applied quite *late* during option processing, while /tcb/if odd page→P. 104 is applied immediately.
/tcb/if odd page* is implemented as /tcb/if odd page→P. 104 packed into /tcb/extras→P. 385.

```
% \tcbuselibrary{breakable}
\begin{tcolorbox}[breakable,if odd page*={colback=yellow!50}{colback=red!50}]
  This breakable box is colored in yellow on an odd page
  and is colored in red on an even page. For every partial box, the
  test is repeated, i.e. this would give a yellow, red, yellow, red, \ldots\
  sequence for a long content.
\end{tcolorbox}
```

> This breakable box is colored in yellow on an odd page and is colored in red on an even page. For every partial box, the test is repeated, i.e. this would give a yellow, red, yellow, red, ... sequence for a long content.

N 2016-11-18 **/tcb/if odd page or oneside*={⟨*odd options*⟩}{⟨*even options*⟩}** (style, no default)

For onesided documents, the ⟨*odd options*⟩ are applied always. For twosided documents, this style is identical to /tcb/if odd page*.

N 2015-11-13 **\tcbifoddpage**{⟨*odd code*⟩}{⟨*even code*⟩}

If the current box is on an odd page, the ⟨*odd code*⟩ is executed. On an even page, the ⟨*even code*⟩ is executed. For precise even/odd page testing, the `/tcb/check odd page` → P. 104 has to be set manually inside the box options.

The macro `\tcbifoddpage` can be used inside underlay, overlay, or watermark code to test if the box is on an odd page. This will work also for boxes in a break sequence.

The macro can also be used inside the box **content text**. For unbreakable boxes, the correct page test is applied. But for `/tcb/breakable` → P. 379 boxes, `\tcbifoddpage` will always give the result for the page of the *first* box inside the box **content text**. If needed, the methods from the packages `changepage` or `ifoddpage` could be used here.

```
\tcbset{colframe=blue!75!black,colback=white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,check odd page,
  title={Example for a box on an \tcbifoddpage{odd}{even} page},
  watermark text={\tcbifoddpage{Odd}{Even} page!}]
\lipsum[1]
\end{tcolorbox}
```

Example for a box on an even page

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Even page!

N 2016-11-18 **\tcbifoddpageoroneside**{⟨*odd code*⟩}{⟨*even code*⟩}

For onesided documents, the ⟨*odd code*⟩ is executed always. For twosided documents, this macro is identical to `\tcbifoddpage`.

N 2015-11-13 **\thetcolorboxnumber**

This is a unique identifier (arabic number) for a tcolorbox. It is locally defined inside boxes and has no meaning outside. It is used for precise even/odd page testing, but may also be valuable for elaborate user code.

```
\begin{tcolorbox}[colback=yellow!5,title=Box \thetcolorboxnumber]
  This box is \thetcolorboxnumber.
  \tcbox[on line,size=fbox]{This box is \thetcolorboxnumber} and
  \tcbox[on line,size=fbox]{this box is \thetcolorboxnumber}.
  This box is \thetcolorboxnumber.
\end{tcolorbox}
```

Box 1143

This box is 1143. This box is 1144 and this box is 1145. This box is 1143.

N 2015-11-13 **\thetcolorboxpage**

This macro contains the expanded arabic page number of the current tcolorbox. It is locally defined inside boxes and has no meaning outside. It is precise only, if `/tcb/check odd page` → P. 104 was set.

```
\begin{tcolorbox}[colback=yellow!5,check odd page,
    title=Box on page~\thetcolorboxpage]
  This box is located on page~\thetcolorboxpage.
\end{tcolorbox}
```

Box on page 107

This box is located on page 107.

4.23 Externalization

! See Section 24 on page 462 for the LIB external library of `tcolorbox`.

If the *externalization* library of the `tikz` package is used and `/tcb/graphical environment` → P. 138 is set to `tikzpicture`, a `tcolorbox` could trigger the externalization process which will arise a compilation error.

To avoid this, there are two possible strategies:

- Ensure, that `\tikzexternaldisable` is set before a `tcolorbox` is used. If you typically use the pattern `\tikzexternalenable` *some picture* `\tikzexternaldisable`, there is nothing to care about.
- If *externalization* is enabled globally, use `/tcb/shield externalize` to shield any `tcolorbox`. The preamble code could look like this:

```
\usetikzlibrary{external}
\tikzexternalize
\tcbset{shield externalize}
```

`/tcb/shield externalize=true|false` (default `true`, initially `false`)

If set to `true`, the drawing part of the `tcolorbox` is not being externalized which is a good thing at the current state of art. Nevertheless, if the `tcolorbox` contains a `tikzpicture`, this picture is still externalized. Pictures drawn with help of `/tcb/tikz upper` → P. 72 or alike are *not* externalized.

! If a `tcolorbox` is used inside a node of an encircling `tikzpicture` which is externalized, do *not* use `\tikzexternaldisable` in front of the `tcolorbox`. `/tcb/shield externalize` is deactivated automatically inside a `tikzpicture`.

! `/tcb/shield externalize` is applied for every following `tcolorbox` inside the current TEX group and is not affected by `/tcb/reset` → P. 109.

`/tcb/external=`⟨*file name*⟩ (no default, initially unset)

Convenience option which calls `\tikzsetnextfilename{`⟨*file name*⟩`}`. Typically, it may be used inside the option list of a `tcolorbox` to set the externalization ⟨*file name*⟩ for the first `tikzpicture` which is discovered *inside* the box content. The package `tikz` [22] or the library LIB skins has to be loaded to use this option. Additionally, `\usetikzlibrary{external}` has to be used.

`/tcb/remake=true|false` (default `true`, initially `false`)

Convenience option which calls `/tikz/external/remake next`. Typically, it may be used inside the option list of a `tcolorbox` to force the remake of the first `tikzpicture` which is discovered *inside* the box content. The package `tikz` [22] or the library LIB skins has to be loaded to use this option. Additionally, `\usetikzlibrary{external}` has to be used.

4.24 Miscellaneous

/tcb/reset (no value, initially set)

Sets (nearly) all `tcolorbox` settings (including loaded libraries) back to their default values *plus* any settings given by `\tcbsetforeverylayer`[→ P. 13]. `/tcb/savedelimiter`[→ P. 26], `/tcb/capture`[→ P. 97], and `/tcb/shield externalize`[→ P. 108] keep their values. Also, all raster values (see Section 15 on page 288) are not resetted.

This option is useful for boxes in boxes where the inner box should not inherit the settings of the outer box. Note that for boxes inside boxes the `reset` is done automatically, if the standard settings of the package are used (v2.40 and above), see Section 4.16 from page 94.

/tcb/code=⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is executed immediately. This option is useful to place some arbitrary code into an option list.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  code={Useless at this spot but functional.},
  fonttitle=\bfseries}

\begin{tcolorbox}[code={\newcommand{\mycommand}{\textit{working}}},
  title=My \mycommand\ title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Useless at this spot but functional.

My *working* title

This is a **tcolorbox**.

N 2016-10-21 **/tcb/void** (no value, initially unset)

Annihilates the current tcolorbox as far as possible. Basically, this comments out the whole tcolorbox by using a key. If the option list of the current tcolorbox contains arbitrary code with global impact (like counter settings), these actions are not undone automatically. Nevertheless, the effects of /tcb/phantom → P. 101, /tcb/step → P. 101, /tcb/new/auto counter → P. 111, etc., are removed by /tcb/void.

```
A%
  \begin{tcolorbox}[
      title=This box is completely removed by the following key,
      void
    ]
  This is a \textbf{tcolorbox}.
  \end{tcolorbox}
B
```

AB

> ! This option key cannot be applied for every situation. For example, if several box environments with the same environment name are nested, for the outer environment /tcb/void cannot be used, since the end of the inner environment will be misinterpreted as end of the outer environment.

N 2019-03-01 **/tcb/nirvana** (no value, initially unset)

The contents of the current tcolorbox are processed including counter settings, but the box is just not drawn. Therefore, /tcb/nirvana is less radical than /tcb/void and several box environments can be nested without problems.

```
A%
  \begin{tcolorbox}[
      title=This box is completely removed by the following key,
      nirvana
    ]
  This is a \textbf{tcolorbox}.
    \begin{tcolorbox}
    Nested Box
    \end{tcolorbox}
  \end{tcolorbox}%
B
```

AB

5 Initialization Option Keys

The *initialization* options are only applicable for the generation of new environments and commands based on `tcolorbox` and friends. Particularly, they can be used for

- `\newtcolorbox` → P. 15,
- `\newtcbox` → P. 16,
- `\newtcblisting` → P. 314,
- `\newtcbinputlisting` → P. 316,
- `\newtcbtheorem` → P. 352, and
- `\newtcboxfit` → P. 427.

> **!** Typically, these options may generate counters and alike. It is **strongly** recommended that you use initialization options inside the preamble only. Otherwise, you may get trouble when using LaTeX's `\include` features.

5.1 Numbered Boxes

Counters assigned using the initialization options are administrated automatically. Especially, they are increased for each new box. Independent from the real counter name, the counter value can be referenced by `\thetcbcounter`, e. g. inside the title of the box. The real counter name is stored inside `\tcbcounter`.

`/tcb/new/auto counter` (no value, initially unset)

Creates a new counter automatically. With `/tcb/new/number format` → P. 113 and `/tcb/new/number within` → P. 113, the appearance and behavior of the counter can be changed. The counter value is referenced by `\thetcbcounter`.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Examp.~\thetcbcounter: #2,#1}
```

```
\begin{pabox}[label={myautocounter}]{Title with number}
This box is automatically numbered with \ref{myautocounter} on page
\pageref{myautocounter}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{pabox}
```

Examp. 5.1: Title with number

This box is automatically numbered with 5.1 on page 111. Inside the box, the 5.1 can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@pabox`.

/tcb/new/use counter from=⟨*tcolorbox*⟩ (no default, initially unset)

Here, a counter from another ⟨*tcolorbox*⟩ is reused. Note that the settings for /tcb/new/number format→P. 113 and /tcb/new/number within→P. 113 are inherited and cannot be changed. The counter value is referenced by **\thetcbcounter**.

```
\newtcolorbox[use counter from=pabox]{mybox}[2][]{%
colback=blue!5!white,colframe=blue!75!black,fonttitle=\bfseries,
title=Some Box \thetcbcounter: #2,#1}

\begin{mybox}[label={myusecounterfrom}]{Title with continued number}
This box is automatically numbered with \ref{myusecounterfrom} on page
\pageref{myusecounterfrom}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{mybox}
```

Some Box 5.2: Title with continued number

This box is automatically numbered with 5.2 on page 112. Inside the box, the 5.2 can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@pabox`.

/tcb/new/use counter=⟨*counter*⟩ (no default, initially unset)

Here, an ordinary existing LaTeX ⟨*counter*⟩ is used for numbering. With /tcb/new/number format→P. 113 and /tcb/new/number within→P. 113, the appearance and behavior of the counter can be changed. The counter value is referenced by **\thetcbcounter**.

```
% \newcounter{myexample}%  preamble
\newtcolorbox[use counter=myexample,number format=\Alph]{mybox}[2][]{%
colback=green!5!white,colframe=green!55!black,fonttitle=\bfseries,
title=Some Box \thetcbcounter: #2,#1}

\begin{mybox}[label={myusecounter}]{Title with \LaTeX\ number}
This box is automatically numbered with \ref{myusecounter} on page
\pageref{myusecounter}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{mybox}
```

Some Box A: Title with LaTeX number

This box is automatically numbered with A on page 112. Inside the box, the A can also be referenced by `\thetcbcounter`. The real counter name is `myexample`.

N 2014-09-19 **/tcb/new/use counter*=⟨*counter*⟩** (no default, initially unset)

An existing LaTeX ⟨*counter*⟩ is used for numbering. In contrast to /tcb/new/use counter, the options /tcb/new/number format→P. 113 and /tcb/new/number within→P. 113 are ignored. Use this for counters which are already configured outside the `tcolorbox` package, e. g. the standard `figure` counter.

/tcb/new/no counter (no value, initially set)

The created boxes are not numbered. This is the default. The option may be used to overrule a previous option.

N 2019-10-18 **/tcb/new/reset counter on overlays=true|false** (default `true`, initially `false`)

For `beamer` slides, this invokes the `\resetcounteronoverlays` command for the box counter. The counter is automatically reset on subsequent overlay slides of a frame. Thereby, the counter will be the same on all slides of every frame.

/tcb/new/number within=⟨*counter*⟩ (no default, initially unset)

The automatic counter is set to zero, if ⟨*counter*⟩ is increased. Additionally, during output, the value of ⟨*counter*⟩ is prepended to the value of the automatic counter.
To prepend the automatic counter with the chapter number and to reset it with every new chapter, use:

```
number within=chapter
```

See /tcb/new/use counter → P. 112 for a complete example.

/tcb/new/number format=⟨*format macro*⟩ (no default, initially \arabic)

Declares the format of the automatic counter. The ⟨*format macro*⟩ can be any valid LaTeX number formatting macro like \arabic, \roman, etc.
To display the counter value in large roman numbers, use:

```
number format=\Roman
```

See /tcb/new/auto counter → P. 111 for a complete example.

/tcb/new/number freestyle=⟨*code*⟩ (no default, initially unset)

Allows advanced control over the complete number format. This option overrules the format given by /tcb/new/number within and /tcb/new/number format. Nevertheless, you can combine it with /tcb/new/number within to get the desired reset property.
The ⟨*code*⟩ is some formatting code which should contain \tcbcounter to reference the automated counter. Since this ⟨*code*⟩ is expanded, you have to secure each macro with \noexpand with *exception* of \tcbcounter.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section,
  number freestyle={(Q/\noexpand\thesection/\noexpand\Alph{\tcbcounter})},
  ]{phbox}[2][]{%
  colback=yellow!15!white,colframe=blue!75!black,fonttitle=\bfseries,
  title=Question~\thetcbcounter: #2,#1}
```

```
\begin{phbox}[label={myfreestyle}]{Title with freestyle number}
This box is automatically numbered with \ref{myfreestyle} on page
\pageref{myfreestyle}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{phbox}
```

Question (Q/5/A): Title with freestyle number

This box is automatically numbered with (Q/5/A) on page 113. Inside the box, the (Q/5/A) can also be referenced by \thetcbcounter. The real counter name is tcb@cnt@phbox.

> **!** The following options `/tcb/new/crefname` and `/tcb/new/Crefname` need to be set inside the preamble.

U 2014-12-01 `/tcb/new/crefname={⟨singular⟩}{⟨plural⟩}` (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. It creates a cross-reference type for the new `tcolorbox`'es, where the lowercase ⟨*singular*⟩ and ⟨*plural*⟩ forms of the cross-reference are given. This type is the environment or macro name and `/tcb/label type` → P. 101 is set automatically. See `/tcb/label type` → P. 101 and [5] for more information.

U 2014-12-01 `/tcb/new/Crefname={⟨singular⟩}{⟨plural⟩}` (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. It creates a cross-reference type for the new `tcolorbox`'es, where the uppercase ⟨*singular*⟩ and ⟨*plural*⟩ forms of the cross-reference are given. This type is the environment or macro name and `/tcb/label type` → P. 101 is set automatically. See `/tcb/label type` → P. 101 and [5] for more information.

Definition in the preamble:

```
% \usepackage{cleveref}
\newtcolorbox[auto counter,number within=section,
  crefname={bluebox}{blueboxes}]%
  {mybluebox}[2][]{colback=blue!5!white,colframe=blue!75!black,fonttitle=\bfseries,
     title=Bluebox \thetcbcounter: #2,#1}
```

```
% \usepackage{varioref}
% \usepackage{cleveref}
\begin{mybluebox}[label={myreference}]{My title}
This is an example.
\end{mybluebox}

\Cref{myreference}, \cref{myreference}.\\
\Cpageref{myreference}, \cpageref{myreference}.\\
\nameCref{myreference}, \namecref{myreference}.\\
\labelcref{myreference}, \labelcpageref{myreference}.\\
With \texttt{varioref}:\\
\Vref{myreference}, \vref{myreference}.\\
\Vref*{myreference}, \vref*{myreference}.
```

Bluebox 5.1: My title

This is an example.

Bluebox 5.1, bluebox 5.1.
Page 114, page 114.
Bluebox, bluebox.
5.1, 114.
With `varioref`:
Bluebox 5.1, bluebox 5.1.
Bluebox 5.1, bluebox 5.1.

N 2014-09-19 **/tcb/new/blend into=⟨*name*⟩** (style, no default, initially unset)

Used to comfortably blend into an existing schema of naming and numbering for some selected cases. For example, a `tcolorbox` can be used to display and entitle an image pretending to be a standard `figure` environment. Here, `/tcb/title` → P. 18 is used instead of the standard `\caption` and `/tcb/list text` → P. 102 can be used instead of the optional parameter of the standard `\caption`.

Feasible values for ⟨*name*⟩ are:

- `figures`: blend into the standard `figure` environment.
- `tables`: blend into the standard `table` environment.
- `listings`: blend into the standard `lstlisting` environment of the package `listings` [6].

> **!** Note that `blend into=listings` can only be used in the document content or, preferably, inside a `\AtBeginDocument` clause! Using it without `\AtBeginDocument` inside the preamble does not work since the `listings` packages initializes its counter also inside `\AtBeginDocument`.

```
\begin{figure}[htb]
  \centering\includegraphics[height=4cm]{lichtspiel.jpg}
  \caption{A standard figure}
\end{figure}

\newtcolorbox[blend into=figures]{myfigure}[2][]{float=htb,capture=hbox,
  title={#2},every float=\centering,#1}

\begin{myfigure}{A tcolorbox figure}
  \includegraphics[height=4cm]{lichtspiel.jpg}
\end{myfigure}
```

Figure 1: A standard figure

Figure 2: A tcolorbox figure

N 2015-03-13 **/tcb/blend before title=**⟨*value*⟩ (no default, initially **colon**)

This option formats the title output of /tcb/new/blend into → P. 115. Note that this is a common tcolorbox option which should be set globally or in the normal option part of \newtcolorbox → P. 15.

Feasible values for ⟨*value*⟩ are:

- **colon**: use name/number plus colon.
- **dash**: use name/number plus dash.
- **colon hang**: use name/number plus colon with hanging indent.
- **dash hang**: use name/number plus dash with hanging indent.

```
\newtcolorbox[blend into=figures]{myfigure}[2][]{float=htb,capture=hbox,
  blend before title=dash hang,title={#2},every float=\centering,#1}

\begin{myfigure}{A tcolorbox figure with quite a long title}
  \includegraphics[height=5cm]{lichtspiel.jpg}
\end{myfigure}
```

Figure 3 – A tcolorbox figure with quite a long title

N 2015-03-13 **/tcb/blend before title code=⟨*code*⟩** (no default)

This option formats the title output of /tcb/new/blend into → P. 115. The ⟨*code*⟩ takes one parameter, the name/number. Use this, if /tcb/blend before title → P. 116 is not flexible enough.

```
\newtcolorbox[blend into=figures]{myfigure}[2][]{float=htb,capture=hbox,
  blend before title code={\fbox{##1}\ },title={#2},every float=\centering,#1}

\begin{myfigure}{A tcolorbox figure}
  \includegraphics[height=6cm]{lichtspiel.jpg}
\end{myfigure}
```

Figure 4 A tcolorbox figure

5.2 Lists of tcolorboxes

For figures and tables, LaTeX provides the `\listoffigures` and `\listoftables` commands to create lists of these numbered entities. Also, a `tcolorbox` can be part of such a kind of list.

1. Assign a list ⟨*name*⟩ by the *initialization* option `/tcb/new/list inside`.
2. Optionally, a new ⟨*type*⟩ for list entries may be assigned by the *initialization* option `/tcb/new/list type`.
3. List entries a generated automatically within each new `tcolorbox` using the above initialization.
   - If `/tcb/list entry` → P. 102 is set, the entry is generated with it.
   - Otherwise, if `/tcb/title` → P. 18 is set, the entry is generated with it.
   - Otherwise, the entry is generated with the current number and the environment name.
4. The generated list is displayed by `\tcblistof`.

`/tcb/new/list inside=`⟨*name*⟩ (no default, initially unset)

Assigns a list or contents file to the generated `tcolorbox`es. Entries to this list are saved to a file which gets the ⟨*name*⟩ as file name extension. The list is referenced by this name in `\tcblistof`. For example:

```
list inside=exam
```

See Section 16.9 from page 346 for a complete example.

`/tcb/new/list type=`⟨*type*⟩ (no default, initially `tcolorbox`)

Optionally, some ⟨*type*⟩ can be assigned to the list entries. For a new ⟨*type*⟩, a macro `\l@`⟨*type*⟩ has to exist which controls the format of the list entry. The default type is defined by

```
\newcommand*\l@tcolorbox{\@dottedtocline{1}{1.5em}{2.3em}}
```

This is identical to the `\l@section` setting of LaTeX. `\l@tcolorbox` can be redefined or a new ⟨*type*⟩ can be assigned.

`\tcblistof`[⟨*macro*⟩]{⟨*name*⟩}{⟨*title text*⟩}

Displays the generated list of `tcolorbox`es with the given ⟨*name*⟩. The heading is generated by ⟨*macro*⟩{⟨*title text*⟩} where `\section` is the default setting for ⟨*macro*⟩.
To display the list inside a subsection, use for example:

```
\tcblistof[\subsection]{exam}{List of Exercises}
```

The result of the example is found as Subsection 16.10 on page 349.

> **!** The core of the list is generated by `\@starttoc{`⟨*name*⟩`}` which can be wrapped into an own macro.

6 Side by Side

A *side by side* box is a special tcolorbox→ P. 12 where the upper and lower part of the box are set side by side. All boxes of this kind are unbreakable.

> **!** Further side by side options for code examples are /tcb/listing side text→ P. 327, /tcb/text side listing→ P. 327, /tcb/listing outside text→ P. 327, and /tcb/text outside listing→ P. 328.

6.1 Basic Settings

/tcb/sidebyside=true|false (default `true`, initially `false`)

Normally, the upper part and the lower part of the box have their positions as their names suggest. If `sidebyside` is set to `true`, the upper part is drawn *left-handed* and the lower part is drawn *right-handed*. Both parts are drawn together with the geometry settings of the upper part but the space is divided horizontally according to the following options. Colors, fonts, and box content additions are used individually. The resulting box is unbreakable.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside]
  This is the upper (\textit{left-handed}) part.
\tcblower
  This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part. | This is the lower (*right-handed*) part.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins}
\begin{tcolorbox}[bicolor,sidebyside,righthand width=3cm,
    sharp corners,boxrule=.4pt,colback=green!5,colbacklower=green!50!black!50]
  \lipsum[2]
\tcblower
  \includegraphics[width=\linewidth]{goldshade}%
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

U 2015-02-06 **/tcb/sidebyside align=**⟨*alignment*⟩ (no default, initially `center`)

Sets the vertical ⟨*alignment*⟩ for the left-handed and right-handed part.
Feasible values for ⟨*alignment*⟩ are:

- `center`: identical to `minipage` option `c`.
- `top`: identical to `minipage` option `t` (aligns the top lines of the left-handed and right-handed side according to their baselines).
- `bottom`: identical to `minipage` option `b` (aligns the bottom lines of the left-handed and right-handed side according to their baselines).
- `center seam`: aligns the center of the left-handed and right-handed side.
- `top seam`: aligns the very top seam of the left-handed and right-handed side.
- `bottom seam`: aligns the very bottom seam of the left-handed and right-handed side.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,nobeforeafter,
  left=2mm,right=2mm,sidebyside,sidebyside gap=6mm,width=(\linewidth-2mm)/3}

\begin{tcolorbox}[adjusted title=center,sidebyside align=center]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=top,sidebyside align=top]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=bottom,sidebyside align=bottom]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}
```

center

This is a text which is too long for one line.

This is a short text.

top

This is a text which is too long for one line.

This is a short text.

bottom

This is a text which is too long for one line.

This is a short text.

`center`, `top`, and `bottom` are identical to the known corresponding `minipage` options. While this is the preferred approach for text content, the result for boxed content like tables or images may not be as expected.
For such content, one may use `center seam`, `top seam`, and `bottom seam`. For example, `top seam` aligns the very top seam of the left-handed and right-handed side.

```latex
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  size=small,righthand width=4cm,sidebyside,sidebyside gap=6mm,lower separated=false}

\begin{tcolorbox}[adjusted title=center seam,sidebyside align=center seam]
  This is my description text for the pictures displayed on the right-handed side.
  \tcblower
  \includegraphics[width=\linewidth/2]{goldshade}%
  \includegraphics[width=\linewidth/2]{blueshade}
\end{tcolorbox}

\begin{tcolorbox}[adjusted title=top seam,sidebyside align=top seam]
  This is my description text for the pictures displayed on the right-handed side.
  \tcblower
  \includegraphics[width=\linewidth/2]{goldshade}%
  \includegraphics[width=\linewidth/2]{blueshade}
\end{tcolorbox}

\begin{tcolorbox}[adjusted title=bottom seam,sidebyside align=bottom seam]
  This is my description text for the pictures displayed on the right-handed side.
  \tcblower
  \includegraphics[width=\linewidth/2]{goldshade}%
  \includegraphics[width=\linewidth/2]{blueshade}
\end{tcolorbox}
```

center seam

This is my description text for the pictures displayed on the right-handed side.



top seam

This is my description text for the pictures displayed on the right-handed side.



bottom seam

This is my description text for the pictures displayed on the right-handed side.



/tcb/sidebyside gap=⟨*length*⟩ (no default, initially 10mm)

Sets the horizontal distance between the left-handed and right-handed part to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,nobeforeafter,
  sidebyside,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[adjusted title=Wide gap,sidebyside gap=30mm]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=Narrow gap,sidebyside gap=1mm]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}
```

Wide gap

This is a text which is too long for one line.

This is a short text.

Narrow gap

This is a text which is too long for one line.

This is a short text.

/tcb/lefthand width=⟨*length*⟩ (no default, initially unset)

Sets the width of the left-handed part to the given ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,lefthand width=3cm]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

/tcb/righthand width=⟨*length*⟩ (no default, initially unset)

Sets the width of the right-handed part to the given ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,righthand width=3cm]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

/tcb/lefthand ratio=⟨*fraction*⟩ (no default, initially 0.5)

Sets the width of the left-handed part to the given ⟨*fraction*⟩ of the available space. ⟨*fraction*⟩ is a value between 0 and 1.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,lefthand ratio=0.25]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

/tcb/righthand ratio=⟨*fraction*⟩ (no default, initially 0.5)

Sets the width of the right-handed part to the given ⟨*fraction*⟩ of the available space. ⟨*fraction*⟩ is a value between 0 and 1.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,righthand ratio=0.25]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

If one side of a side-by-side box should be adapted to the width of its content, this width has to be computed beforehand. The following example uses a savebox `\mysavebox` to store the picture to determine its width. A more convenient way to handle this task is to use the methods from Section 6.2 on page 125.

```
% \tcbuselibrary{skins,xparse}
% \usepackage{lipsum}
% \newsavebox\mysavebox  % preamble
\DeclareTotalTColorBox{\mysidebox}{ O{} +m +m }{
  bicolor,colback=white,colbacklower=yellow!10,
  fonttitle=\bfseries,center title,
  sidebyside,
  code={\sbox{\mysavebox}{#2}},
  lefthand width=\wd\mysavebox,
  drop lifted shadow,
  #1
}
{\usebox{\mysavebox}\tcblower#3}

\mysidebox[title=The Triangle]{%
  \begin{tikzpicture}
    \path[fill=red!20,draw=red!50!black]
      (0,0) node[below]{A} -- (3,1) node[right]{B}
      -- (1,4) node[above]{C} -- cycle;
  \end{tikzpicture}%
}{%
  \lipsum[1]
}
```

The Triangle



Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

6.2 Advanced Settings from the xparse Library

> **!** All following macros and options need the xparse library to be loaded, see Section 23 on page 449.

N 2015-11-20 `\tcbsidebyside[⟨options⟩]{⟨left-handed content⟩}{⟨right-handed content⟩}`

Creates a colored box using more or less arbitrary ⟨*options*⟩ for a `tcolorbox` →P. 12. The `/tcb/sidebyside` →P. 119 option is set to `true` and the ⟨*left-handed content*⟩ and ⟨*right-handed content*⟩ is filled into the box appropriately. The resulting box is unbreakable. `\tcbsidebyside` is not only a shortcut for using a normal `tcolorbox` →P. 12 with `/tcb/sidebyside` →P. 119, but allows setting further options like `/tcb/sidebyside adapt` →P. 126 and `/tcb/sidebyside switch` →P. 128.

```
% \tcbuselibrary{skins,xparse}
% \usepackage{lipsum}
\tcbsidebyside[title=The Triangle,
  sidebyside adapt=left,
  bicolor,colback=white,colbacklower=yellow!10,
  fonttitle=\bfseries,center title,drop lifted shadow,
]{%
  \begin{tikzpicture}
    \path[fill=red!20,draw=red!50!black]
      (0,0) node[below]{A} -- (3,1) node[right]{B}
      -- (1,4) node[above]{C} -- cycle;
  \end{tikzpicture}%
}{%
  \lipsum[1]
}
```

The Triangle



Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

N 2015-11-20 **/tcb/sidebyside adapt=⟨*side(s)*⟩** (no default, initially none)

The option allows the left-handed and/or right-handed side to determine the dimensions of the box. This option is only valid inside \tcbsidebyside→ P. 125.

Feasible values for ⟨*side(s)*⟩ are:

- none: no measurement of left-handed and right-handed side.
- left: the actual width of the left-handed content is used to set /tcb/lefthand width→ P. 122.
- right: the actual width of the right-handed content is used to set /tcb/righthand width→ P. 122.
- both: the actual width of the left-handed and right-handed content is used to set /tcb/lefthand width→ P. 122, /tcb/righthand width→ P. 122, and the overall /tcb/width→ P. 34.

```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside[sidebyside adapt=left,
  title=Very important table,
  beamer,colframe=blue!50!black,colback=blue!10,
  lower separated=false,sidebyside gap=5mm
]{%
  \begin{tabular}{|l|c|r|}\hline
    left & center & right\\\hline
    A & B & C\\\hline
    D & E & F\\\hline
  \end{tabular}
}{%
  This table contains the most important figures for
  all future actions. You may notice that B follows A,
  C follows B, and so on.
}
```

Very important table

left	center	right
A	B	C
D	E	F

This table contains the most important figures for all future actions. You may notice that B follows A, C follows B, and so on.

```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside[sidebyside adapt=right,
  blanker,sidebyside gap=5mm
]{%
  \lipsum[2]
}{%
\begin{tikzpicture}
  \path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
  \fill[red] (45:5mm) circle (1mm);
  \fill[red] (135:5mm) circle (1mm);
  \draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tikzpicture}
}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside[sidebyside adapt=both,
  enhanced,center,
  title=Both sides adapted,
  attach boxed title to top center={yshift=-2mm},
  coltitle=black,boxed title style={colback=red!25},
  segmentation style=solid,colback=red!5,colframe=red!50
]{%
  \begin{tabular}{|l|c|r|}\hline
    left & center & right\\\hline
    A & B & C\\\hline
    D & E & F\\\hline
  \end{tabular}
}{%
\begin{tikzpicture}
  \path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
  \fill[red] (45:5mm) circle (1mm);
  \fill[red] (135:5mm) circle (1mm);
  \draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tikzpicture}
}
```

Both sides adapted

left	center	right
A	B	C
D	E	F

N 2015-11-20 **/tcb/sidebyside switch=true|false** (default `true`, initially `false`)

If set to `true`, the ⟨*left-handed content*⟩ and ⟨*right-handed content*⟩ of `\tcbsidebyside` → P. 125 are switched. Obviously, this option is only valid inside `\tcbsidebyside` → P. 125.

The side switching can be made even/odd page sensitive, if used inside `/tcb/if odd page` → P. 104.

```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside{Left}{Right}

\tcbsidebyside[sidebyside switch]{Left}{Right}

\tcbsidebyside[title=Very important table,
  if odd page={sidebyside switch,sidebyside adapt=right,flushright title}%
               {sidebyside adapt=left},
  beamer,colframe=blue!50!black,colback=blue!10,
  lower separated=false,sidebyside gap=5mm
]{%
  \begin{tabular}{|l|c|r|}\hline
    left & center & right\\\hline
    A & B & C\\\hline
    D & E & F\\\hline
  \end{tabular}
}{%
  This table contains the most important figures for
  all future actions. You may notice that B follows A,
  C follows B, and so on.
}
```

Left | Right

Right | Left

Very important table

left	center	right
A	B	C
D	E	F

This table contains the most important figures for all future actions. You may notice that B follows A, C follows B, and so on.

7 Saving and Loading of Verbatim Texts

The following macros are slightly modified versions of the original macros from the known packages `moreverb` and `verbatim`. They are used implicitly inside of a `tcolorbox` environment, but they can be used outside also.

`\begin{tcbverbatimwrite}{`⟨*file name*⟩`}`
  ⟨*environment content*⟩
`\end{tcbverbatimwrite}`

Saves the ⟨*environment content*⟩ to a file named by ⟨*file name*⟩. TEX macros inside the environment are not expanded.

```
\begin{tcbverbatimwrite}{\jobname_verbexp.tex}
  This text is saved \textit{as is}.
\end{tcbverbatimwrite}

Now, we are using the file:\par
\input{\jobname_verbexp.tex}
```

Now, we are using the file:
This text is saved *as is*.

This environment may be used inside an own environment. Note, that inside the environment definition `\tcbverbatimwrite` has to be used instead of `\begin{tcbverbatimwrite}` and `\endtcbverbatimwrite` instead of `\end{tcbverbatimwrite}`.

```
\newenvironment{myverbatim}{%
  \begingroup\tcbverbatimwrite{\jobname_myverb.tex}}%
  {\endtcbverbatimwrite\endgroup}

\begin{myverbatim}
  This is the text which is saved by my own environment.
\end{myverbatim}

Now, we are using the file:\par
\input{\jobname_myverb.tex}
```

Now, we are using the file:
This is the text which is saved by my own environment.

`\begin{tcbwritetemp}`
  ⟨*environment content*⟩
`\end{tcbwritetemp}`

Has the same function as `tcbverbatimwrite`, but uses the key value of `tempfile` for the file name.

```
\begin{tcbwritetemp}
  This text is saved \textit{as is}.
\end{tcbwritetemp}

Now, we are using the file:\par
\tcbusetemp
```

Now, we are using the file:
This text is saved *as is*.

`\tcbusetemp`

Loads the current temporary file which was saved by `tcbwritetemp`.

N 2017-07-05 **/tcb/verbatim ignore percent=true|false** (default `true`, initially `false`)

If this option is set to be `true`, the percent sign % is silently ignored for `tcbverbatimwrite`→ P. 129 and all macros and environments which are built using `tcbverbatimwrite`→ P. 129, e.g. `tcbwritetemp`→ P. 129, `tcblisting`→ P. 311, or `dispExample`→ P. 482.

This option may be useful for creating some special effects, but mainly it is intended to be applied for documentation with DocStrip. The creation of this option was motivated by Yudai Nakata. Note that this option is not getting reset by `/tcb/reset`→ P. 109.

```
Normal usage:
\begin{tcbwritetemp}
%\begin{center}\bfseries
This is my text.
%\end{center}
\end{tcbwritetemp}

\tcbusetemp

\tcbset{verbatim ignore percent}
\bigskip Option applied:
\begin{tcbwritetemp}
%\begin{center}\bfseries
This is my text.
%\end{center}
\end{tcbwritetemp}

\tcbusetemp
```

Normal usage:
This is my text.

Option applied:
This is my text.

> **!** Note that *every* percent sign is removed, also escaped ones.

```
% \tcbuselibrary{listings}
\def\percent{\%}

\begin{tcblisting}{title=Normal}
%\begin{center}\bfseries
This is my 5\percent\ text
and this is my 10\% text.
%\end{center}
\end{tcblisting}

\begin{tcblisting}{
  title=Option applied,
  verbatim ignore percent}
%\begin{center}\bfseries
This is my 5\percent\ text
and this is my 10\% text.
%\end{center}
\end{tcblisting}
```

Normal

```
%\begin{center}\bfseries
This is my 5\percent\ text
and this is my 10\% text.
%\end{center}
```

This is my 5% text and this is my 10% text.

Option applied

```
\begin{center}\bfseries
This is my 5\percent\ text
and this is my 10\ text.
\end{center}
```

This is my 5% text and this is my 10 text.

8 Recording

The package provides some macros and options to take *records* during compilation. This is done by LaTeX file operations to save some data to a file for later usage. The main application scenario is depicted in Section 8.3 on the next page where information about example solutions is recorded and read again in Section 8.4 on page 135.

8.1 Macros

N 2014-11-28 `\tcbstartrecording[⟨file name⟩]`

Opens a file denoted by ⟨*file name*⟩ for writing the records. The default file name is `\jobname.records`. See Section 8.3 on the next page for an example application.

> **!** In some situations, a not existing optional parameter may cause parsing problems. If this happens (or just for precaution), use
>
> ```
> \tcbstartrecording\relax
> ```
>
> or
>
> ```
> \tcbstartrecording[\jobname.records]
> ```

N 2014-11-28 `\tcbrecord{⟨content⟩}`

Records any ⟨*content*⟩ to the record file. `\tcbrecord` is implemented as `\immediate\write`. `\tcbstartrecording` has to be called before; otherwise, `\tcbrecord` is silently ignored.

```
\tcbrecord{\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}}
```

N 2014-11-28 `\tcbstoprecording`

Closes the current record file which was opened by `\tcbstartrecording` before.

N 2014-11-28 `\tcbinputrecords[⟨file name⟩]`

Opens a file denoted by ⟨*file name*⟩ for reading the records via `\input`. The default file name is the name of the last used record file for saving. `\tcbstoprecording` has to be called before.

8.2 Options

N 2014-11-28 `/tcb/record=⟨content⟩` (style, no default)

Records any ⟨*content*⟩ to the record file, see `\tcbrecord`. This key can be used several times to write several lines.

```
record={\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}}
```

N 2014-11-28 `/tcb/no recording`

Disables `\tcbrecord` and `/tcb/record` inside the current group.

8.3 Example: Exercises

The following application example creates exercises and their corresponding solutions. Each pair is generated inside a single `tcolorbox` where the solution is given below `\tcblower`→ P. 12. For every example, the solution part is saved by `/tcb/savelowerto`→ P. 24 to a file. The saving is recorded using `/tcb/record`→ P. 131. To enlighten the possibilities, the second exercise has no solution. Finally, the solutions are input in Section 8.4 on page 135.

Definition in the preamble:

```
% \tcbuselibrary{skins,xparse}

\NewTColorBox[auto counter,number within=section]{exercise}{+!O{}}{%
  enhanced,colframe=green!20!black,colback=yellow!10!white,coltitle=green!40!black,
  fonttitle=\bfseries,
  underlay={\begin{tcbclipinterior}
    \shade[inner color=green!80!yellow,outer color=yellow!10!white]
      (interior.north west) circle (2cm);
    \draw[help lines,step=5mm,yellow!80!black,shift={(interior.north west)}]
      (interior.south west) grid (interior.north east);
    \end{tcbclipinterior}},
  title={Exercise~\thetcbcounter:},
  label={exercise@\thetcbcounter},
  attach title to upper=\quad,
  after upper={\par\hfill\textcolor{green!40!black}%
    {\itshape Solution on page~\pageref{solution@\thetcbcounter}}},
  lowerbox=ignored,
  savelowerto=solutions/exercise-\thetcbcounter.tex,
  record={\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}},
  #1
}

\NewTotalTColorBox{\solution}{mm}{%
  enhanced,colframe=red!20!black,colback=yellow!10!white,coltitle=red!40!black,
  fonttitle=\bfseries,
  underlay={\begin{tcbclipinterior}
    \shade[inner color=red!50!yellow,outer color=yellow!10!white]
      (interior.north west) circle (2cm);
    \draw[help lines,step=5mm,yellow!80!black,shift={(interior.north west)}]
      (interior.south west) grid (interior.north east);
    \end{tcbclipinterior}},
  title={Solution of Exercise~\ref{exercise@#1} on page~\pageref{exercise@#1}:},
  phantomlabel={solution@#1},
  attach title to upper=\par,
}{\input{#2}}

\tcbset{no solution/.style={no recording,after upper=}}
```

```
\tcbstartrecording\relax

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\sin((\sin x)^2)
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \sin((\sin x)^2) \right)'
    =\cos((\sin x)^2) 2\sin x \cos x.
  \end{align*}
\end{exercise}
```

```
\begin{exercise}[no solution]
  It holds:
  \begin{equation*}
    \frac{d}{dx}\left(\ln|x|\right) = \frac{1}{x}.
  \end{equation*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=(\sin(\sin x))^2
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( (\sin(\sin x))^2 \right)'
    =2\sin(\sin x)\cos(\sin x)\cos x.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\sqrt{x^3-6x^2+2x}
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \sqrt{x^3-6x^2+2x} \right)'
    = \frac{3x^2-12x+2}{2\sqrt{x^3-6x^2+2x}}.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\left(\frac{2+3x}{1-2x}\right)^3
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \left(\frac{2+3x}{1-2x}\right)^3 \right)'
    = 3 \left(\frac{2+3x}{1-2x}\right)^2 \frac{(1-2x)3-(2+3x)(-2)}{(1-2x)^2}
    = \frac{21(2+3x)^2}{(1-2x)^4}.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\frac{\cos x}{(\tan 2x)^2}
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \frac{\cos x}{(\tan 2x)^2} \right)'
    = \left( \frac{\cos x (\cos 2x)^2}{(\sin 2x)^2} \right)'\\
    &= \frac{(\sin 2x)^2 [(-\sin x)(\cos 2x)^2+(\cos x)4\cos 2x (-\sin 2x)]
       - \cos x (\cos 2x)^2 4\sin 2x \cos 2x}{(\sin 2x)^4}\\
    &= -\frac{\cos(2x) [\sin x \sin 2x \cos 2x+ 4\cos x(\sin 2x)^2
       + 4 \cos x (\cos 2x)^2]}{(\sin 2x)^3}\\
    &= -\frac{\cos(2x) [\sin x \sin 2x \cos 2x+ 4\cos x]}{(\sin 2x)^3}.
```

```
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\cos((2x^2+3)^3)
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \cos((2x^2+3)^3) \right)'
    =-\sin((2x^2+3)^3) 3(2x^2+3)^2 2\cdot 2x\\
    &=-12x(2x^2+3)^2\sin((2x^2+3)^3).
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=(x^2+1)\sqrt{x^4+1}
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( (x^2+1)\sqrt{x^4+1} \right)'
    = 2x\sqrt{x^4+1} + \frac{2x^3(x^2+1)}{\sqrt{x^4+1}}.
  \end{align*}
\end{exercise}

\tcbstoprecording
```

Exercise 8.1: Compute the derivative of the following function:

$$f(x) = \sin((\sin x)^2)$$

Solution on page 135

Exercise 8.2: It holds:

$$\frac{d}{dx}(\ln \mathtt{x}) = \frac{1}{x}.$$

Exercise 8.3: Compute the derivative of the following function:

$$f(x) = (\sin(\sin x))^2$$

Solution on page 135

Exercise 8.4: Compute the derivative of the following function:

$$f(x) = \sqrt{x^3 - 6x^2 + 2x}$$

Solution on page 135

Exercise 8.5: Compute the derivative of the following function:

$$f(x) = \left(\frac{2+3x}{1-2x}\right)^3$$

Solution on page 136

Exercise 8.6: Compute the derivative of the following function:

$$f(x) = \frac{\cos x}{(\tan 2x)^2}$$

Solution on page 136

Exercise 8.7: Compute the derivative of the following function:

$$f(x) = \cos((2x^2+3)^3)$$

Solution on page 136

Exercise 8.8: Compute the derivative of the following function:

$$f(x) = (x^2+1)\sqrt{x^4+1}$$

Solution on page 136

8.4 Example: Solutions

This concludes the example given in Section 8.3 on page 132. Now, the saved and recorded solutions are included.

```
\tcbinputrecords
```

Solution of Exercise 8.1 on page 134:
The derivative is:

$$f'(x) = \Big(\sin((\sin x)^2)\Big)' = \cos((\sin x)^2)2\sin x\cos x.$$

Solution of Exercise 8.3 on page 134:
The derivative is:

$$f'(x) = \Big((\sin(\sin x))^2\Big)' = 2\sin(\sin x)\cos(\sin x)\cos x.$$

Solution of Exercise 8.4 on page 134:
The derivative is:

$$f'(x) = \Big(\sqrt{x^3-6x^2+2x}\Big)' = \frac{3x^2-12x+2}{2\sqrt{x^3-6x^2+2x}}.$$

Solution of Exercise 8.5 on page 135:
The derivative is:

$$f'(x) = \left(\left(\frac{2+3x}{1-2x}\right)^3\right)' = 3\left(\frac{2+3x}{1-2x}\right)^2 \frac{(1-2x)3-(2+3x)(-2)}{(1-2x)^2} = \frac{21(2+3x)^2}{(1-2x)^4}.$$

Solution of Exercise 8.6 on page 135:
The derivative is:

$$\begin{aligned} f'(x) &= \left(\frac{\cos x}{(\tan 2x)^2}\right)' = \left(\frac{\cos x(\cos 2x)^2}{(\sin 2x)^2}\right)' \\ &= \frac{(\sin 2x)^2[(-\sin x)(\cos 2x)^2 + (\cos x)4\cos 2x(-\sin 2x)] - \cos x(\cos 2x)^2 4\sin 2x\cos 2x}{(\sin 2x)^4} \\ &= -\frac{\cos(2x)[\sin x\sin 2x\cos 2x + 4\cos x(\sin 2x)^2 + 4\cos x(\cos 2x)^2]}{(\sin 2x)^3} \\ &= -\frac{\cos(2x)[\sin x\sin 2x\cos 2x + 4\cos x]}{(\sin 2x)^3}. \end{aligned}$$

Solution of Exercise 8.7 on page 135:
The derivative is:

$$\begin{aligned} f'(x) &= \left(\cos((2x^2+3)^3)\right)' = -\sin((2x^2+3)^3)3(2x^2+3)^2 2\cdot 2x \\ &= -12x(2x^2+3)^2\sin((2x^2+3)^3). \end{aligned}$$

Solution of Exercise 8.8 on page 135:
The derivative is:

$$f'(x) = \left((x^2+1)\sqrt{x^4+1}\right)' = 2x\sqrt{x^4+1} + \frac{2x^3(x^2+1)}{\sqrt{x^4+1}}.$$

9 Technical Overview and Customization

This section provides a technical overview of the skin concept of `tcolorbox`. For most applications of `tcolorbox`, one will not need to know the bells and whistles described herein. You may proceed to Section 10 on page 152 where the customization options for most users are documented.

The following explanations also cover options and settings from the LIB skins library, see Section 10 on page 152.

9.1 Skins and Drawing Engines

From a technical point of view, a *skin* is a style definition for the appearance of a `tcolorbox`. The core package provides some additional option keys for skins but only two skins called `standard`→P. 209 and `standard jigsaw`→P. 210. The LIB skins library adds several more skins. To change to a skin, only one option from the core package has to be set.

/tcb/skin=⟨*name*⟩ (style, no default, initially `standard`)

Sets the current skin to ⟨*name*⟩. This is a style definition which sets all the following keys, i. e. for many use cases there is nothing more to do.

```
\tcbset{colback=Salmon!50!white,colframe=FireBrick!75!black,
  width=(\linewidth-8mm)/2,before=,after=\hfill,equal height group=ske}

\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[skin=beamer,beamer,adjusted title=My title]
  This is my content.
\end{tcolorbox}
```



/tcb/skin first=⟨*name*⟩ (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable`→P. 379 and *is* broken actually, then the skin for the *first* part of the break sequence is set to ⟨*name*⟩, see Subsection 18.8 on page 392. Typically, this key is set by a `/tcb/skin`.

/tcb/skin middle=⟨*name*⟩ (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable`→P. 379 and *is* broken actually, then the skin for the *middle* parts (if any) of the break sequence is set to ⟨*name*⟩, see Subsection 18.8 on page 392. Typically, this key is set by a `/tcb/skin`.

/tcb/skin last=⟨*name*⟩ (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable`→P. 379 and *is* broken actually, then the skin for the *last* part of the break sequence is set to ⟨*name*⟩, see Subsection 18.8 on page 392. Typically, this key is set by a `/tcb/skin`.

`/tcb/graphical environment=`⟨*name*⟩ (no default, initially `pgfpicture`)

Sets the graphical environment for the `tcolorbox` to ⟨*name*⟩. Feasible values are `pgfpicture` and `tikzpicture` or environments which inherit from one of these two. This key is set by a `/tcb/skin`→P. 137 and may seldom be used directly.

The skin of a `tcolorbox` is drawn by up to four *engines*. Afterwards, the text content is drawn which is not part of a skin. The four steps are:

1. The *frame* of the box, drawn by `/tcb/frame engine`.
2. The *interior* of the box. The interior of a box with title is drawn differently from a box without title. `/tcb/interior titled engine` or `/tcb/interior engine`→P. 139 is used to draw the interior.
3. The *segmentation* (line) of the box, if there is a lower part; drawn by `/tcb/segmentation engine`→P. 139.
4. The *title area* of the box, if there is a title and `/tcb/title filled`→P. 27 is set to `true`; drawn by `/tcb/title engine`→P. 139.

`/tcb/frame engine=`⟨*name*⟩ (no default, initially `standard`)

Sets the *frame* drawing engine for a box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin`→P. 137. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/frame style`→P. 152,
- `pathjigsaw`: a `tikz` path which is controlled by `/tcb/frame style`→P. 152,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/frame style`→P. 152,
- `pathfirstjigsaw`: a `tikz` path which is controlled by `/tcb/frame style`→P. 152,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/frame style`→P. 152,
- `pathmiddlejigsaw`: a `tikz` path which is controlled by `/tcb/frame style`→P. 152,
- `pathlast`: a `tikz` path which is controlled by `/tcb/frame style`→P. 152,
- `pathlastjigsaw`: a `tikz` path which is controlled by `/tcb/frame style`→P. 152,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/interior titled engine=`⟨*name*⟩ (no default, initially `standard`)

Sets the *interior* drawing engine for a titled box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin`→P. 137. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/interior style`→P. 153,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/interior style`→P. 153,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/interior style`→P. 153,
- `pathlast`: a `tikz` path which is controlled by `/tcb/interior style`→P. 153,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/interior engine=`⟨*name*⟩ (no default, initially `standard`)

Sets the *interior* drawing engine for an untitled box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin`→P. 137. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/interior style`→P. 153,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/interior style`→P. 153,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/interior style`→P. 153,
- `pathlast`: a `tikz` path which is controlled by `/tcb/interior style`→P. 153,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/segmentation engine=`⟨*name*⟩ (no default, initially `standard`)

Sets the *segmentation* (line) drawing engine for a box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin`→P. 137. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/segmentation style`→P. 155,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/title engine=`⟨*name*⟩ (no default, initially `standard`)

Sets the *title area* drawing engine for a titled box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin`→P. 137. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/title style`→P. 155,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/title style`→P. 155,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/title style`→P. 155,
- `pathlast`: a `tikz` path which is controlled by `/tcb/title style`→P. 155,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

! After an engine is set to an initializing value, the resulting graphical code can be changed using code option keys, see Section 9.2 on page 141.

`/tcb/geometry nodes=true|false` (default `true`, initially `false`)

If set to `true`, up to four `tikz` nodes are defined for a `tcolorbox` which are named `frame`, `interior`, `segmentation`, and `title`. These nodes describe the boundaries of the equally named parts of a `tcolorbox`. They are used by most engines based on Ti*k*Z. Typically, this key is set automatically by a `/tcb/skin` → P. 137.

```
\tcbset{colback=Salmon!50!white,colframe=FireBrick!75!black,
  width=(\linewidth-8mm)/2,before=,after=\hfill,equal height group=geon}

\begin{tcolorbox}[adjusted title=The title]
  The upper part.\tcblower The lower part.
\end{tcolorbox}
\begin{tcolorbox}[enhanced,adjusted title=The title,
  frame code={\path[draw=red,fill=red!25]
      (frame.south west) rectangle (frame.north east);},
  interior titled code={\path[draw=blue,fill=blue!25]
      (interior.south west) rectangle (interior.north east);},
  segmentation code={\path[draw=green,fill=green!25]
      (segmentation.south west) rectangle (segmentation.north east);},
  title code={\path[draw=black,fill=brown!75!black]
      (title.south west) rectangle (title.north east);}]
  The upper part.\tcblower The lower part.
\end{tcolorbox}
```



9.2 Code Option Keys

The following code options are applicable for all skins. The used ⟨*graphical code*⟩ can be any `pgf` code. For all skins with exception of `standard` → P. 209 and `standard jigsaw` → P. 210, the ⟨*graphical code*⟩ can also be any Ti*k*Z code.

`/tcb/frame code=`⟨*graphical code*⟩ (code, default from `standard`)

The given ⟨*graphical code*⟩ is used for drawing the *frame* of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[enhanced,frame code={
  \foreach \n in {north east,north west,south east,south west}
  {\path [fill=red!75!black] (interior.\n) circle (3mm); }; }]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

`/tcb/frame empty` (style, no value)

This is a shortcut for setting `/tcb/frame code` to empty. This option removes the drawing of the frame. Alternatively, use `/tcb/frame hidden` → P. 153.

`/tcb/interior titled code=`⟨*graphical code*⟩ (code, default from `standard`)

The given ⟨*graphical code*⟩ is used for drawing the *interior* of the box, if the box comes with a title.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,interior titled code={
  \path[draw=red!5!white,line width=5mm,line cap=round]
    ([xshift=3mm,yshift=-3mm]interior.north west)
    --([xshift=-3mm,yshift=3mm]interior.south east)
    ([xshift=3mm,yshift=3mm]interior.south west)
    --([xshift=-3mm,yshift=-3mm]interior.north east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

`/tcb/interior titled empty` (style, no value)

This is a shortcut for setting `/tcb/interior titled code` to empty. This option removes the drawing of the untitled interior. Alternatively, use `/tcb/interior hidden` → P. 154.

/tcb/interior code=⟨*graphical code*⟩ (code, default from **standard**)

The given ⟨*graphical code*⟩ is used for drawing the *interior* of the box, if the box is without a title.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[enhanced,interior code={
  \path[draw=red!5!white,line width=5mm,line cap=round]
    ([xshift=3mm,yshift=-3mm]interior.north west)
    --([xshift=-3mm,yshift=3mm]interior.south east)
    ([xshift=3mm,yshift=3mm]interior.south west)
    --([xshift=-3mm,yshift=-3mm]interior.north east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/interior empty (style, no value)

This is a shortcut for setting **/tcb/interior code** to empty. This option removes the drawing of the interior. Alternatively, use **/tcb/interior hidden** → P. 154.

/tcb/segmentation code=⟨*graphical code*⟩ (code, default from **standard**)

The given ⟨*graphical code*⟩ is used for drawing the *segmentation* area of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,segmentation code={
  \path[top color=red!5!white,bottom color=red!5!white,middle color=blue]
  (segmentation.south west) rectangle (segmentation.north east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/segmentation empty (style, no value)

This is a shortcut for setting **/tcb/segmentation code** to empty. This option removes the drawing of the segmentation line. Alternatively, use **/tcb/segmentation hidden** → P. 155.

/tcb/title code=⟨*graphical code*⟩ (code, default from **standard**)

The given ⟨*graphical code*⟩ is used for drawing the *title* area of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,title code={
  \path[draw=yellow,solid,decorate,line width=2mm,
    decoration={coil,aspect=0,segment length=10.1mm}]
    ([xshift=1mm]title.west) -- ([xshift=-1mm]title.east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/title empty (style, no value)

This is a shortcut for setting **/tcb/title code** to empty. This option removes the drawing of the title area. Alternatively, use **/tcb/title hidden** → P. 156.

9.3 Subskins

A subskin is a new /tcb/skin→ P. 137 based on an existing skin which is extended or changed.

> **!** Never use geometry settings or bounding box options inside a subskin definition! If one skin is replaced by another skin, the overall bounding box should stay constant. Especially, if a skin is used for a breakable box, unpredictable and unpleasant results could arise otherwise. If you want to change the geometry also, use an additional style. See the skin beamer→ P. 233 and the style /tcb/beamer→ P. 233 as pattern.

\tcbsubskin{⟨*name*⟩}{⟨*base skin*⟩}{⟨*options*⟩}

Creates a new skin ⟨*name*⟩ which inherits all properties of an existing ⟨*base skin*⟩ plus the given ⟨*options*⟩. The new skin ⟨*name*⟩ can be used as value for the keys /tcb/skin→ P. 137, /tcb/skin first→ P. 137, /tcb/skin middle→ P. 137, and /tcb/skin last→ P. 137. As ⟨*base skin*⟩, one can take standard→ P. 209, empty→ P. 242, enhanced→ P. 211, or any skin from the LIB skins library, see Section 10 on page 152.

```
% \tcbuselibrary{skins}
\tcbsubskin{mycross}{empty}{frame code={%
  \draw[red,line width=5pt] (frame.south west)--(frame.north east);
  \draw[red,line width=5pt] (frame.north west)--(frame.south east);},
  skin first=mycross,skin middle=mycross,skin last=mycross }

\begin{tcolorbox}[skin=mycross]
  This is my content.
\end{tcolorbox}
```

This is my content.

/tcb/skin first is subskin of={⟨*base skin*⟩}{⟨*options*⟩} (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing ⟨*base skin*⟩ plus the given ⟨*options*⟩. This skin is set as /tcb/skin first→ P. 137.
See a detailed example on page 248.

/tcb/skin middle is subskin of={⟨*base skin*⟩}{⟨*options*⟩} (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing ⟨*base skin*⟩ plus the given ⟨*options*⟩. This skin is set as /tcb/skin middle→ P. 137.
See a detailed example on page 248.

/tcb/skin last is subskin of={⟨*base skin*⟩}{⟨*options*⟩} (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing ⟨*base skin*⟩ plus the given ⟨*options*⟩. This skin is set as /tcb/skin last→ P. 137.
See a detailed example on page 248.

9.4 Drawing Scheme

Depending on the complexity of a `tcolorbox` definition, the resulting box is drawn in a more or less complex series of steps.

To document and demonstrate these drawing steps, we consider the following box definition:

```
\newtcolorbox{testbox}[1][]{enhanced,title=Test Box,
  boxrule=1mm,titlerule=0.5mm,colframe=blue!50!black,
  interior style={top color=blue!20!green!50!white,bottom color=blue!20!yellow!50!white},
  colbacktitle=blue!50!green!90!white,segmentation style={solid},
  fonttitle=\bfseries,drop fuzzy shadow,borderline={0.3mm}{0.35mm}{yellow!50!white},
  underlay={\path[fill image opacity=0.15,fill image scale=0.9,
    fill stretch picture={\draw[blue,line width=2mm] circle (1);}]
    (interior.south west) rectangle (interior.north east);},
  watermark text={Watermark},watermark color={green!20!white},
  finish={\begin{tcbclipframe}
    \path[bottom color=black,top color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.south east) -- (frame.north east) -- cycle;
    \path[top color=white,bottom color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.north east) -- (frame.north west) -- cycle;
    \end{tcbclipframe}},#1}
```

For this definition, we get the maximal number of drawing steps:

1. shadow

- Section 10.6 on page 186.

2. frame

- `/tcb/colframe` → P. 27, `/tcb/opacityframe` → P. 51
- `/tcb/frame code` → P. 141
- `/tcb/frame style` → P. 152



- /tcb/colback → P. 27, /tcb/opacityback → P. 51
- /tcb/interior code → P. 142, /tcb/interior titled code → P. 141
- /tcb/interior style → P. 153



- /tcb/colbacktitle → P. 27, /tcb/opacitybacktitle → P. 51
- /tcb/title code → P. 143
- /tcb/title style → P. 155



- /tcb/lower separated → P. 25
- /tcb/segmentation code → P. 142
- /tcb/segmentation style → P. 155



- Section 10.5 on page 181



- Section 10.2 on page 159
- Section 10.8 on page 199



- Section 4.12 on page 74
- Section 10.3 on page 169

Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

9. text content

Lower part

- `/tcb/colupper` → P. 28, `/tcb/collower` → P. 28, `/tcb/coltitle` → P. 28
- `/tcb/fontupper` → P. 29, `/tcb/fontlower` → P. 29, `/tcb/fonttitle` → P. 29
- `/tcb/opacityupper` → P. 52, `/tcb/opacitylower` → P. 52, `/tcb/opacitytitle` → P. 52

Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

10. finish

Lower part

- Section 10.9 on page 201

All together, the box is drawn:

```
% \usepackage{lipsum}
\begin{testbox}
\lipsum[2]
\tcblower
Lower part
\end{testbox}
```

Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Lower part

9.5 Color Names

N 2019-01-18

Color settings for a `tcolorbox` are saved into named colors which may be used inside a box, e.g. for an overlay. These color names are

- **tcbcolframe** set by /tcb/colframe → P. 27 (frame color)
- **tcbcolback** set by /tcb/colback → P. 27 (background color)
- **tcbcolbacktitle** set by /tcb/colbacktitle → P. 27 (background color of the title)
- **tcbcolbacklower** set by /tcb/colbacklower → P. 225 (skin dependend background color of the lower part; needs LIB skins to be loaded)
- **tcbcolupper** set by /tcb/colupper → P. 28 (text color upper part)
- **tcbcollower** set by /tcb/collower → P. 28 (text color lower part)
- **tcbcoltitle** set by /tcb/coltitle → P. 28 (text color title)

```
% \tcbuselibrary{skins}
\begin{tcolorbox}[title=Color names,
    colframe=blue!50!black,colback=blue!5,
    colbacktitle=blue!50,colupper=red!35!black]
  \foreach \name in {tcbcolframe,tcbcolback,tcbcolbacktitle,tcbcolbacklower,
    tcbcolupper,tcbcollower,tcbcoltitle}
  {\tikz\path[draw,fill=\name]
    (0,0) rectangle node[right=4mm,font=\ttfamily]{\name} (0.8,0.8);\par}
\end{tcolorbox}
```

Color names

tcbcolframe

tcbcolback

tcbcolbacktitle

tcbcolbacklower

tcbcolupper

tcbcollower

tcbcoltitle

9.6 Useful Properties

The following macros describe certain *properties* which may be used for the drawing scheme, see Section 9.4 on page 145. Sometimes, they are even available inside the box content. All of them are considered to be *read-only* and should never be redefined by the user.

N 2016-02-16 **\tcbheightspace**

If the height of a `tcolorbox` is not the natural height, the space difference between the forced and the natural size is hold by `\tcbheightspace`. This macro is not usable inside the box content, but for skins or inside `/tcb/underlay` → P. 199, `/tcb/overlay` → P. 74, etc.
If such a space information is needed inside the box content, see `/tcb/space to` → P. 59 instead.

```
% \tcbuselibrary{skins}
\newtcolorbox{testbox}[2][]{enhanced,size=fbox,
  colframe=blue!75!black,colback=white,height=#2,
  underlay={\node[above,inner sep=3pt] at (interior.south){%
    \includegraphics[width=\tcbtextwidth,height=\tcbheightspace-3pt]{goldshade.png}};
    },
  #1}
\begin{testbox}{3cm}
  This is my box. The space is filled with a picture.
\end{testbox}
\begin{testbox}{2cm}
  This is my box. The space is filled with a picture.
\end{testbox}
```

This is my box. The space is filled with a picture.

This is my box. The space is filled with a picture.

N 2016-02-16 **\tcbtextwidth**

This property describes the box content width.

- If there also is a lower part, it describes the width of the upper part.
- For `/tcb/sidebyside` → P. 119 boxes, it describes the combined text width plus segmentation.
- This property can be used inside the box content text with exception of `/tcb/fit` → P. 429 boxes.
- `\tcbtextwidth` can be used for all box types for skins or inside `/tcb/underlay` → P. 199, `/tcb/overlay` → P. 74, etc.

```
\begin{tcolorbox}[colframe=blue!75!black]
  Inside a box: \tcbtextwidth\ (=\the\linewidth).
\end{tcolorbox}
```

Inside a box: 370.74823pt (=370.74823pt).

N 2016-02-16 **\tcbtextheight**

This property describes the designated box content height. If the box is larger than the natural height, the actual content will be smaller than \tcbtextheight.

- For boxes with a fixed /tcb/height → P. 53, this property can be used inside the box content text. For other boxes, it denotes 0pt inside the box content.
- \tcbtextheight can be used for all box types for skins or inside /tcb/underlay → P. 199, /tcb/overlay → P. 74, etc.

```
% \tcbuselibrary{skins}
\begin{tcolorbox}[enhanced,colframe=blue!75!black,
    underlay={\node[left,red] at (frame.east) {Here: \tcbtextheight};}]
  Inside a box with natural height: \tcbtextheight.
\end{tcolorbox}
\begin{tcolorbox}[enhanced,colframe=blue!75!black,height=1cm,
    underlay={\node[left,red] at (frame.east) {Here: \tcbtextheight};}]
  Inside a box with fixed height: \tcbtextheight.
\end{tcolorbox}
```

Inside a box with natural height: 0pt. Here: 7.95pt

Inside a box with fixed height: 8.5359pt. Here: 8.5359pt

N 2017-04-25 **\tcbsegmentstate**

This macro contains 0, 1, or 2. Itis set for every unbroken box and every broken partial box with the following meaning:

- 0: The current (partial) box contains only an upper part.
- 1: The current (partial) box contains an upper and a lower part. The segmentation node can be used for positioning.
- 2: The current (partial) box contains only a lower part. This can only be true for parts of breakable boxes.

Skins like bicolor → P. 224 use this property to paint the (partial) boxes.

```
% \tcbuselibrary{skins,raster}
\begin{tcbraster}[raster equal height,enhanced,
    watermark text=\tcbsegmentstate]
  \begin{tcolorbox}Upper part\end{tcolorbox}
  \begin{tcolorbox}Upper part\tcblower Lower part\end{tcolorbox}
\end{tcbraster}
```

Upper part 0

Upper part 1

Lower part

10 Library skins

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

This also loads the package `tikz` [22]. Typically but not necessarily, the following skins use `tikz` instead of `pgf`.

10.1 Style Option Keys

The following style options are applicable for all skins which use engines of type `path`, `pathfirst`, `pathmiddle`, or `pathlast`. Especially, the skin `enhanced` → P. 211 supports *all* of them and `standard` → P. 209 *none*.

`/tcb/frame style`=⟨`tikz` *keys*⟩ (style, no default)

The ⟨`tikz` *keys*⟩ are used inside the `tikz` path command for drawing the *frame* of the box. This option is available if the `/tcb/frame engine` → P. 138 is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style={left color=red!75!black,
               right color=blue!75!black}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

`/tcb/frame style image`=⟨*file name*⟩ (no default, initially unset)

Fills the frame with an external image referenced by ⟨*file name*⟩. For advanced features like blending of a picture with the background, use `/tcb/frame style` together with `/tikz/fill stretch image` → P. 262.

```
\tcbset{colback=red!5!white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style image=blueshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/frame style tile={⟨*graphics options*⟩}{⟨*file name*⟩} (no default, initially unset)

Fills the frame with a tile pattern based on an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command. For advanced features like blending of a picture with the background, use /tcb/frame style → P. 152 together with /tikz/fill tile image → P. 266.

```
\tcbset{colback=red!5!white,coltitle=red!30!black,
  opacityback=0.75,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style tile={width=1cm}{pink_marble.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/frame hidden (style, no value)

This is a shortcut for `frame style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the frame. Alternatively, use /tcb/frame empty → P. 141.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,
  frame hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/interior style=⟨tikz *keys*⟩ (style, no default)

The ⟨tikz *keys*⟩ are used inside the `tikz` path command for drawing the *interior* of the box. They are used for the titled and for the untitled version as well.
This option is available if the /tcb/interior titled engine → P. 138 or /tcb/interior engine → P. 139 is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  interior style={left color=red!20!white,
                  right color=yellow!50!white}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/interior style image=⟨*file name*⟩ (no default, initially unset)

Fills the interior with an external image referenced by ⟨*file name*⟩. For advanced features like blending of a picture with the background, use /tcb/interior style→P. 153 together with /tikz/fill stretch image→P. 262.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  interior style image=goldshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/interior style tile={⟨*graphics options*⟩**}{**⟨*file name*⟩**}** (no default, initially unset)

Fills the interior with a tile pattern based on an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying \includegraphics command. For advanced features like blending of a picture with the background, use /tcb/interior style→P. 153 together with /tikz/fill tile image→P. 266.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  interior style tile={width=2cm}{crinklepaper.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/interior hidden (style, no value)

This is a shortcut for interior style={draw=none,fill=none}. Depending on the skin, this option switches off the drawing of the interior. Alternatively, use /tcb/interior empty→P. 142 and/or /tcb/interior titled empty→P. 141.

```
\tcbset{frame style={top color=red!20!white,
  bottom color=red!20!white!75!black},
  fonttitle=\bfseries,coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,
  interior hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/segmentation style=⟨tikz *keys*⟩ (style, no default)

The ⟨tikz *keys*⟩ are used inside the tikz path command for drawing the *segmentation* line of the box.

This option is available if the /tcb/segmentation engine → P. 139 is set to path. It is *not* available for standard.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  segmentation style={double=white,draw=blue,
                double distance=1pt,solid}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/segmentation hidden (style, no value)

This is a shortcut for segmentation style={draw=none,fill=none}. Depending on the skin, this option switches off the drawing of the segmentation line. See also /tcb/lower separated → P. 25 which has the same effect for most skins. Alternatively, use /tcb/segmentation empty → P. 142.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,
  enhanced,segmentation hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/title style=⟨tikz *keys*⟩ (style, no default)

The ⟨tikz *keys*⟩ are used inside the tikz path command for drawing the *title area* of the box.

This option is available if the /tcb/title engine → P. 139 is set to path, pathfirst, pathmiddle, or pathlast. It is *not* available for standard.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  coltitle=blue!50!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  title style={left color=blue!15!yellow,
               right color=red!85!black}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

/tcb/title style image=⟨*file name*⟩ (no default, initially unset)

Fills the title area with an external image referenced by ⟨*file name*⟩. For advanced features like blending of a picture with the background, use /tcb/title style → P. 155 together with /tikz/fill stretch image → P. 262.

```
\tcbset{colback=blue!5!white,colframe=blue!75!black,
  fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  title style image=blueshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/title style tile={⟨*graphics options*⟩**}{**⟨*file name*⟩**}** (no default, initially unset)

Fills the title area with a tile pattern based on an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command. For advanced features like blending of a picture with the background, use /tcb/title style → P. 155 together with /tikz/fill tile image → P. 266.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  coltitle=blue!50!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  title style tile={width=1cm}{pink_marble.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/title hidden (style, no value)

This is a shortcut for `title style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the title background. See also /tcb/title filled → P. 27 for a similar effect. Alternatively, use /tcb/title empty → P. 143.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,
  enhanced,title hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



N 2015-01-14 **/tcb/titlerule style=⟨tikz *keys*⟩** (style, no default)

The ⟨tikz *keys*⟩ are used to draw a title rule, i.e. a rule below the optional title. The width of the rule is controlled by /tcb/titlerule→ P. 36. It may be set directly to a smaller width to create mixed effects with the standard rule. This option is implemented as an /tcb/underlay→ P. 199. Thus, it is not available for standard→ P. 209 and standard jigsaw→ P. 210, but for all other skins, e.g. enhanced→ P. 211. As an underlay, this option can be used multiple times and is removed by /tcb/no underlay→ P. 199.

```
\begin{tcolorbox}[enhanced,
  colback=red!5!white,colframe=red!75!black,
  colbacktitle=red!50!yellow,fonttitle=\bfseries,
  title=My title,
  titlerule=1mm,
  titlerule style=yellow  ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced,
  colback=red!5!white,colframe=red!75!black,
  colbacktitle=red!50!yellow,fonttitle=\bfseries,
  title=My title,
  titlerule=1mm,
  titlerule style={yellow,line width=0.5mm}  ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced,
  colback=red!10!white,colframe=red!75!black,
  colbacktitle=red!50!yellow,fonttitle=\bfseries,
  frame hidden,
  title=My title,
  boxrule=0pt,titlerule=1mm,
  titlerule style=red!50!black  ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
%\usetikzlibrary{arrows.meta}
\begin{tcolorbox}[empty,
  coltitle=red!75!black,fonttitle=\bfseries,
  borderline horizontal={0.5mm}{0pt}{red!50!white},
  title=My title,
  titlerule style={red,
    arrows = {Hooks[arc=270]-Hooks[arc=270]}} ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

The combined TikZ style applied to frame, interior, and title background can used by authors in customizing code.

/tikz/tcb fill frame (style, no value)

This is a TikZ style which is finally applied to the *frame* of the box.

```
% \tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  frame code app={\path[tcb fill frame]
    ([yshift=-2mm]frame.north)
        circle (8mm); }  }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tikz/tcb fill interior (style, no value)

This is a TikZ style which is finally applied to the *interior* of the box.

```
% \tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  interior titled code app={\path[tcb fill interior]
      ([yshift=-0.1pt]interior.north east)
    --([yshift=3pt]interior.north)
    --([yshift=-0.1pt]interior.north west)
    --cycle;}  }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tikz/tcb fill title (style, no value)

This is a TikZ style which is finally applied to the *title area* of the box.

```
% \tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  colbacktitle=blue!75!black,
  title code app={\path[tcb fill title]
    (title) circle (5mm); }  }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



10.2 Boxed Title Option Keys

10.2.1 Boxed Title Placement

The following options place the title text into an own `\tcbox`→P. 14. This boxed title can be customized independently from the main box using `/tcb/boxed title style`→P. 163. The placement can be influenced by ⟨*boxtitle options*⟩.

/tcb/attach boxed title to top left={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a `\tcbox`→P. 14 and attached to the top left corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/attach boxed title to top center={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a `\tcbox`→P. 14 and attached to the top of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/attach boxed title to top right={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a `\tcbox`→P. 14 and attached to the top right corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top right]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/attach boxed title to bottom left={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a `\tcbox`→P. 14 and attached to the bottom left corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom left]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

/tcb/attach boxed title to bottom center={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a `\tcbox`→P. 14 and attached to the bottom of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom center]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

/tcb/attach boxed title to bottom right={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a `\tcbox`→P. 14 and attached to the bottom right corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom right]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

N 2016-02-26 **/tcb/attach boxed title to top={⟨*boxtitle options*⟩}** (style, default empty)

This is a convenient style to mimic a standard title. It uses /tcb/attach boxed title to top center → P. 159, /tcb/minipage boxed title → P. 167, and sizes the boxed title to match the base box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top,
  boxed title style={colframe=red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

N 2016-02-26 **/tcb/attach boxed title to top*={⟨*boxtitle options*⟩}** (style, default empty)

In contrast to /tcb/attach boxed title to top, this style uses smaller left and right rules to avoid previewer glitches. Typically, one would not use different colors for the frame as in the example below.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top*,
  boxed title style={colframe=red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

N 2016-02-26 **/tcb/attach boxed title to bottom={⟨*boxtitle options*⟩}** (style, default empty)

This is a convenient style to produce a standard-like title at the bottom of the box. It uses /tcb/attach boxed title to bottom center → P. 159, /tcb/minipage boxed title → P. 167, and sizes the boxed title to match the base box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom,
  boxed title style={colframe=red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

N 2016-02-26 **/tcb/attach boxed title to bottom*={⟨*boxtitle options*⟩}** (style, default empty)

In contrast to /tcb/attach boxed title to top, this style uses smaller left and right rules to avoid previewer glitches.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom*]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

N 2016-02-26 **/tcb/flip title={⟨*options*⟩}** (style, default empty)

This style combines /tcb/attach boxed title to bottom* with /tcb/boxed title style → P. 163. The ⟨*options*⟩ are given to /tcb/boxed title style → P. 163.

```
\begin{tcolorbox}[tile,flip title={sharp corners},
  title=My title,colback=red!10,
  colbacktitle=red!75!black]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

10.2.2 Options for the Boxed Title Placement

The ⟨*boxtitle options*⟩ of the keys described above are shift values. The dimensions of the boxed title are stored into two macros **\tcboxedtitleheight** and **\tcboxedtitlewidth**. These macros can be used inside the following ⟨*boxtitle options*⟩:

/tcb/boxtitle/xshift=⟨*length*⟩ (no default, initially `0pt`)

The boxed title is shifted by ⟨*length*⟩ in the horizontal direction.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left={xshift=-2mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/boxtitle/yshift=⟨*length*⟩ (no default, initially `0pt`)

The boxed title is shifted by ⟨*length*⟩ in the vertical direction.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center=
    {yshift=-\tcboxedtitleheight/2},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/boxtitle/yshifttext=⟨*length*⟩ (no default, initially `0pt`)

The text inside the main box is shifted by ⟨*length*⟩ to give room for e. g. a sunken title.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/boxtitle/yshift*=⟨*length*⟩ (no default, initially `0pt`)

Sets `/tcb/boxtitle/yshift` and `/tcb/boxtitle/yshifttext` the same time. `/tcb/boxtitle/yshifttext` is only set if necessary.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center={yshift*=-3mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

! The bounding box of the resulting total `tcolorbox` is adapted automatically to the *vertical* dimensions of the boxed title. Possible horizontal enlargements are *not* automatically computed.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left=
    {xshift=-2mm,yshift=-2mm},
  boxed title style={size=small,colback=blue},
  show bounding box]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

10.2.3 Options for the Boxed Title Box

> **!** The boxed title options are implemented as an underlay, see Section 10.8 on page 199. Therefore, a boxed title is not drawn, if a skin does not support underlays like `standard`→P. 209. Still, the room for the boxed titles gets reserved in these cases.

> **!** A TikZ node `title` is produced by a boxed title which can be used inside `/tcb/frame code`→P. 141, `/tcb/interior code`→P. 142, underlays, overlays, and finishes.

> **!** A boxed title is almost always the first underlay. The only exceptions are underlays defined by `/tcb/underlay boxed title`→P. 200 which are drawn before. Additionally, underlays defined by `/tcb/underlay boxed title`→P. 200 are only drawn, if a boxed title is actually set. They are ignored, if there is no boxed title.

N 2016-02-26 **`/tcb/boxed title size=`⟨*size*⟩** (no default, initially `title`)

This setting defines the basic size for the title box. Further settings can be applied using `/tcb/boxed title style`→P. 163. Feasible values for ⟨*size*⟩ are:

- `title`: Sets the size according to `/tcb/size`→P. 44`=title`.
- `standard`: No size setting. Typically, this is identical to `/tcb/size`→P. 44`=normal`.
- `copy`: The size values for a title of the base box are copied for the title box.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,enhanced,boxrule=0.4pt,
    title=My title,attach boxed title to top center]
  \begin{tcolorbox}[boxed title size=title]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[boxed title size=standard]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[boxed title size=copy]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
\end{tcbraster}
```



U 2016-02-26 **/tcb/boxed title style=⟨*options*⟩** (style, initially empty)

By default, a boxed title is dimensioned with /tcb/size→P. 44=title and inherits the /tcb/skin→P. 137 and /tcb/colframe→P. 27 of the main box. Also, the /tcb/colback→P. 27 is inherited from the main /tcb/colbacktitle→P. 27. Font and color of the title text are set as usual. All other ⟨*options*⟩ are set by the /tcb/boxed title style key. Since a boxed title is set by \tcbox→P. 14, all tcolorbox options are applicable here. If /tcb/boxed title style is used several times, the ⟨*options*⟩ are is appended.

```
\begin{tcolorbox}[enhanced,title=My title,
  fonttitle=\bfseries,coltitle=green!25!black,
  attach boxed title to top center=
    {yshift=-2mm,yshifttext=-1mm},
  boxed title style={colframe=green!75!black,
    colback=yellow!50!green}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced,title=My title,
  colframe=red!50!black,colback=red!10!white,
  arc=1mm,colbacktitle=red!10!white,
  fonttitle=\bfseries,coltitle=red!50!black,
  attach boxed title to top left=
    {xshift=3.2mm,yshift=-0.50mm},
  boxed title style={skin=enhancedfirst jigsaw,
    size=small,arc=1mm,bottom=-1mm,
    interior style={fill=none,
      top color=red!30!white,
      bottom color=red!20!white}}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced,title=My title,
  colframe=blue!50!black,colback=blue!10!white,colbacktitle=blue!5!yellow!10!white,
  fonttitle=\bfseries,coltitle=black,attach boxed title to top center=
    {yshift=-0.25mm-\tcboxedtitleheight/2,yshifttext=2mm-\tcboxedtitleheight/2},
  boxed title style={boxrule=0.5mm,
    frame code={ \path[tcb fill frame] ([xshift=-4mm]frame.west)
    -- (frame.north west) -- (frame.north east) -- ([xshift=4mm]frame.east)
    -- (frame.south east) -- (frame.south west) -- cycle; },
    interior code={ \path[tcb fill interior] ([xshift=-2mm]interior.west)
    -- (interior.north west) -- (interior.north east)
    -- ([xshift=2mm]interior.east) -- (interior.south east) -- (interior.south west)
    -- cycle;}  }]
  \lipsum[2]
\end{tcolorbox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][]{enhanced,skin=enhancedlast jigsaw,
  attach boxed title to top left={xshift=-4mm,yshift=-0.5mm},
  fonttitle=\bfseries\sffamily,varwidth boxed title=0.7\linewidth,
  colbacktitle=blue!45!white,colframe=red!50!black,
  interior style={top color=blue!10!white,bottom color=red!10!white},
  boxed title style={empty,arc=0pt,outer arc=0pt,boxrule=0pt},
  underlay boxed title={
    \fill[blue!45!white] (title.north west) -- (title.north east)
      -- +(\tcboxedtitleheight-1mm,-\tcboxedtitleheight+1mm)
      -- ([xshift=4mm,yshift=0.5mm]frame.north east) -- +(0mm,-1mm)
      -- (title.south west) -- cycle;
    \fill[blue!45!white!50!black] ([yshift=-0.5mm]frame.north west)
      -- +(-0.4,0) -- +(0,-0.3) -- cycle;
    \fill[blue!45!white!50!black] ([yshift=-0.5mm]frame.north east)
      -- +(0,-0.3) -- +(0.4,0) -- cycle;  },
  title={#2},#1}

\begin{mybox}{My title}
  \lipsum[2]
\end{mybox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][]{enhanced,
  attach boxed title to top left={xshift=1cm,yshift=-2mm},
  fonttitle=\bfseries,varwidth boxed title=0.7\linewidth,
  colbacktitle=green!45!white,coltitle=green!10!black,colframe=green!50!black,
  interior style={top color=yellow!10!white,bottom color=green!10!white},
  boxed title style={boxrule=0.75mm,colframe=white,
    borderline={0.1mm}{0mm}{green!50!black},
    borderline={0.1mm}{0.75mm}{green!50!black},
    interior style={top color=green!10!white,bottom color=green!10!white,
      middle color=green!50!white},
    drop fuzzy shadow},
  title={#2},#1}

\begin{mybox}{My title}
  \lipsum[2]
\end{mybox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\newtcolorbox{flipbox}[2][]{
  enhanced,colframe=blue!50!black,colback=yellow!5,fonttitle=\bfseries,
  flip title={interior hidden},title={#2},#1}

\begin{flipbox}{My title}
\lipsum[2]
\end{flipbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My title

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][]{skin=enhancedlast jigsaw,interior hidden,
  boxsep=0pt,top=0pt,colframe=red,coltitle=red!50!black,
  fonttitle=\bfseries\sffamily,
  attach boxed title to bottom center,
  boxed title style={empty,boxrule=0.5mm},
  varwidth boxed title=0.5\linewidth,
  underlay boxed title={
    \draw[white,line width=0.5mm]
      ([xshift=0.3mm-\tcboxedtitleheight*2,yshift=0.3mm]title.north west)
      --([xshift=-0.3mm+\tcboxedtitleheight*2,yshift=0.3mm]title.north east);
    \path[draw=red,top color=white,bottom color=red!50!white,line width=0.5mm]
    ([xshift=0.25mm-\tcboxedtitleheight*2,yshift=0.25mm]title.north west)
    cos +(\tcboxedtitleheight,-\tcboxedtitleheight/2)
    sin +(\tcboxedtitleheight,-\tcboxedtitleheight/2)
    -- ([xshift=0.25mm,yshift=0.25mm]title.south west)
    -- ([yshift=0.25mm]title.south east)
    cos +(\tcboxedtitleheight,\tcboxedtitleheight/2)
    sin +(\tcboxedtitleheight,\tcboxedtitleheight/2); },
  title={#2},#1}

\begin{mybox}{My title}
  \lipsum[2]
\end{mybox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My title

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][]{enhanced,
  before skip=2mm,after skip=2mm,
  colback=black!5,colframe=black!50,boxrule=0.2mm,
  attach boxed title to top left={xshift=1cm,yshift*=1mm-\tcboxedtitleheight},
  varwidth boxed title*=-3cm,
  boxed title style={frame code={
    \path[fill=tcbcolback!30!black]
      ([yshift=-1mm,xshift=-1mm]frame.north west)
        arc[start angle=0,end angle=180,radius=1mm]
      ([yshift=-1mm,xshift=1mm]frame.north east)
        arc[start angle=180,end angle=0,radius=1mm];
    \path[left color=tcbcolback!60!black,right color=tcbcolback!60!black,
      middle color=tcbcolback!80!black]
      ([xshift=-2mm]frame.north west) -- ([xshift=2mm]frame.north east)
      [rounded corners=1mm]-- ([xshift=1mm,yshift=-1mm]frame.north east)
      -- (frame.south east) -- (frame.south west)
      -- ([xshift=-1mm,yshift=-1mm]frame.north west)
      [sharp corners]-- cycle;
    },interior engine=empty,
  },
  fonttitle=\bfseries,
  title={#2},#1}

\begin{mybox}[colbacktitle=green]{My title}
\lipsum[2]
\end{mybox}
\begin{mybox}[colbacktitle=red]{My title}
\lipsum[3]
\end{mybox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My title

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

N 2016-02-26 **/tcb/no boxed title style** (style, initially set)

Removes all options which were set by `/tcb/boxed title style` → P. 163.

/tcb/hbox boxed title (no value, initially set)

The title text content is captured with a horizontal box. Especially, there are no linebreak possible.

```
\newtcolorbox{mybox}[1]{hbox boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

Short title
This is a **tcolorbox**.

This title is not really very short
This is a **tcolorbox**.

/tcb/minipage boxed title=⟨*length*⟩ (initially unset)

The title text content is captured with a minipage with a width of ⟨*length*⟩. By default, the resulting boxed title is somewhat smaller than the main box.

```
\newtcolorbox{mybox}[1]{minipage boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

Short title
This is a **tcolorbox**.

This title is not really very short
This is a **tcolorbox**.

/tcb/minipage boxed title*=⟨*length*⟩ (initially unset)

The title text content is captured with a minipage with a width of main box width plus ⟨*length*⟩. By default, the resulting boxed title is somewhat smaller than the main box.

```
\newtcolorbox{mybox}[1]{minipage boxed title*=-2cm,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

Short title
This is a **tcolorbox**.

This title is not really very short
This is a **tcolorbox**.

/tcb/tikznode boxed title=⟨*options*⟩ (initially unset)

The title text content is captured with a TikZ node with given TikZ ⟨*options*⟩. The text is centered by default

```
\newtcolorbox{mybox}[1]{tikznode boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title\\is not really\\very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

Short title
This is a **tcolorbox**.

This title
is not really
very short
This is a **tcolorbox**.

/tcb/varwidth boxed title=⟨*length*⟩ (initially unset)

The title text content is captured with a `varwidth` environment with a width of ⟨*length*⟩. This style needs the `varwidth` package [1] to be loaded manually. By default, the resulting boxed title is somewhat smaller than the main box.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[1]{varwidth boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

Short title
This is a **tcolorbox**.

This title is not really
very short
This is a **tcolorbox**.

/tcb/varwidth boxed title*=⟨*length*⟩ (initially unset)

The title text content is captured with a `varwidth` environment with a width of main box width plus ⟨*length*⟩. This style needs the `varwidth` package [1] to be loaded manually. By default, the resulting boxed title is somewhat smaller than the main box.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[1]{varwidth boxed title*=-2cm,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

Short title
This is a **tcolorbox**.

This title is not
really very short
This is a **tcolorbox**.

10.3 Watermark Option Keys

The following watermark options are applicable for all skins which use `tikzpicture` as `/tcb/graphical environment`→ P. 138. Therefore, the skin `standard`→ P. 209 does not support these watermarks, but all other skins, e. g. `enhanced`→ P. 211.

> **!** The watermark options rely on the more general overlay options described in Section 4.12 from page 74. Therefore, *watermarks* and *overlays* cannot be used mixed. But a mixture is possible with the LIB hooks library, see Section 22.

`/tcb/watermark text=`⟨*text*⟩ (no default, initially unset)

Writes some ⟨*text*⟩ in the center of the interior region of a `tcolorbox`. This ⟨*text*⟩ is written *after* the frame and interior are drawn and *before* the text content is drawn. It is zoomed or stretched according the values of `/tcb/watermark zoom`→ P. 172 or `/tcb/watermark stretch`→ P. 174.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark text=My Watermark]
\lipsum[1]
\tcblower
\lipsum[2]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My Watermark

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark text on=`⟨*part*⟩ `is` ⟨*text*⟩ (no default, initially unset)

This option writes some ⟨*text*⟩ in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark text`. But this is done only for boxes named ⟨*part*⟩ of a break sequence, see `/tcb/breakable`→ P. 379.

Feasible values for ⟨*part*⟩ are:

- `broken`: all broken box parts,
- `unbroken`: unbroken boxes only,
- `first`: first parts of a break sequence,
- `middle`: middle parts of a break sequence,
- `last`: last parts of a break sequence,
- `unbroken and first`: unbroken boxes and first parts of a break sequence,
- `middle and last`: middle and last parts of a break sequence.
- `first and middle`: first and middle parts of a break sequence.

/tcb/watermark graphics=⟨*file name*⟩ (no default, initially unset)

Draws an external picture referenced by ⟨*file name*⟩ in the center of the interior region of a `tcolorbox`. The picture is drawn *after* the frame and interior are drawn and *before* the text content is drawn. It is zoomed or stretched according the values of `/tcb/watermark zoom` → P. 172 or `/tcb/watermark stretch` → P. 174.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark graphics=Basilica_5.png,
  watermark opacity=0.15]
\lipsum[1-2]
\tcblower
This example uses a public domain picture from\\
\url{http://commons.wikimedia.org/wiki/File:Basilica_5.png}
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This example uses a public domain picture from
http://commons.wikimedia.org/wiki/File:Basilica_5.png

/tcb/watermark graphics on=⟨*part*⟩ `is` ⟨*file name*⟩ (no default, initially unset)

This option draws a picture referenced by ⟨*file name*⟩ in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark graphics`. But this is done only for boxes named ⟨*part*⟩ of a break sequence, see `/tcb/breakable` → P. 379.

Feasible values for ⟨*part*⟩ are:

- `broken`: all broken box parts,
- `unbroken`: unbroken boxes only,
- `first`: first parts of a break sequence,
- `middle`: middle parts of a break sequence,
- `last`: last parts of a break sequence,
- `unbroken and first`: unbroken boxes and first parts of a break sequence,
- `middle and last`: middle and last parts of a break sequence.

/tcb/watermark tikz=⟨*graphical code*⟩ (no default, initially unset)

Draws the given `tikz` ⟨*graphical code*⟩ in the center of the interior region of a `tcolorbox`. The code is executed *after* the frame and interior are drawn and *before* the text content is drawn. The result is zoomed or stretched according the values of `/tcb/watermark zoom` → P. 172 or `/tcb/watermark stretch` → P. 174.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  watermark tikz={\draw[line width=2mm] circle (1cm)
    node{\fontfamily{ptm}\fontseries{b}\fontsize{20mm}{20mm}\selectfont ?};}]
\lipsum[1]
\tcblower
\lipsum[2]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/watermark tikz on=⟨*part*⟩ `is` ⟨*graphical code*⟩ (no default, initially unset)

This option draws the given `tikz` ⟨*graphical code*⟩ in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark tikz`. But this is done only for boxes named ⟨*part*⟩ of a break sequence, see `/tcb/breakable` → P. 379.

Feasible values for ⟨*part*⟩ are:

- `broken`: all broken box parts,
- `unbroken`: unbroken boxes only,
- `first`: first parts of a break sequence,
- `middle`: middle parts of a break sequence,
- `last`: last parts of a break sequence,
- `unbroken and first`: unbroken boxes and first parts of a break sequence,
- `middle and last`: middle and last parts of a break sequence.

/tcb/no watermark (style, no default, initially set)

Removes the watermark if set before. This is an alias for `/tcb/no overlay` → P. 75.

/tcb/watermark opacity=⟨*fraction*⟩ (no default, initially `1.00`)

Sets the opacity value $\in [0, 1]$ for a watermark.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  watermark text=Watermark,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Opacity 1.00,watermark opacity=1.00]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Opacity 0.50,watermark opacity=0.50]
\lipsum[2]
\end{tcolorbox}%
```

Opacity 1.00

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Opacity 0.50

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/watermark zoom=⟨*fraction*⟩ (no default, initially `0.75`)

Sets the zoom value for a watermark. The zoom respects the aspect ratio. The value 1.0 means to fill the whole box until the watermark touches the frame.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  watermark text=Watermark,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Zoom 1.0,watermark zoom=1.0]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Zoom 0.5,watermark zoom=0.5]
\lipsum[2]
\end{tcolorbox}%
```

Zoom 1.0

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Zoom 0.5

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/watermark shrink=⟨*fraction*⟩ (no default, initially unset)

Identically to /tcb/watermark zoom→P. 172, but the watermark never gets enlarged. Thus, the watermark keeps its original size or is shrunk.

/tcb/watermark overzoom=⟨*fraction*⟩ (no default, initially unset)

Sets the overzoom value for a watermark. The overzoom respects the aspect ratio. The value 1.0 means to fill the whole box until the watermark touches all four sides of the frame.

```
\tcbset{enhanced,colback=white,colframe=blue!50!black,fonttitle=\bfseries,
  watermark opacity=0.5,
  watermark graphics=lichtspiel.jpg,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Zoom 1.0,watermark zoom=1.0]
\lipsum[1]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Overzoom 1.0,watermark overzoom=1.0]
\lipsum[1]
\end{tcolorbox}%
```

Zoom 1.0

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Overzoom 1.0

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

! If a /tcb/watermark overzoom value of 1.0 is used in connection with invisible top and bottom rules which still have a thickness greater than 0pt, the space of these invisible rules may not be covered by the watermark. For example, this situation may occur during the breaking of /tcb/enhanced→P. 211 boxes. To avoid this optical glitch, just set /tcb/pad at break→P. 383 to any desired value.

/tcb/watermark stretch=⟨*fraction*⟩ (no default, initially unset)

Sets the stretch value for a watermark. The stretch value is applied to width and height in relation to the box dimensions. It does not respect the aspect ratio. The value 1.0 means to fill the whole box.

```
\tcbset{enhanced,colback=white,colframe=blue!50!black,fonttitle=\bfseries,
  watermark graphics=lichtspiel.jpg,watermark opacity=0.5,
  nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Stretch 1.00,watermark stretch=1.00]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Stretch 0.50,watermark stretch=0.50]
\lipsum[2]
\end{tcolorbox}%
```

Stretch 1.00

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Stretch 0.50

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/watermark color=⟨*color*⟩ (no default, initially mixed background and frame color)

Sets the color for the watermark.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark text=My Watermark,
  watermark color=yellow!50!red]
\lipsum[1]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My Watermark

`/tcb/clip watermark=true|false` (default `true`, initially `true`)

Sets the watermark to be clipped to the interior area.

```
\tcbset{enhanced,colback=white,colframe=blue!50!white,fonttitle=\bfseries,
  watermark opacity=0.5,watermark stretch=1.00,arc=3mm,
  watermark graphics=lichtspiel.jpg}

\begin{tcolorbox}[title=Clip (default),clip watermark]
\lipsum[1]
\end{tcolorbox}

\begin{tcolorbox}[title=No clip,clip watermark=false]
\lipsum[1]
\end{tcolorbox}%
```

Clip (default)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

No clip

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

10.4 Clip Environments

The following clip environments are applicable for all skins which use engines of type `path`, `pathfirst`, `pathmiddle`, or `pathlast`. Especially, the skin `enhanced`→ P. 211 supports *all* of them and `standard`→ P. 209 *none*. The typical area of application is inside overlay code, see Section 4.12 from page 74.

```
\begin{tcbclipframe}
  ⟨environment content⟩
\end{tcbclipframe}
```

Defines a `Tikz` scope which clips to the frame area path.

```
\makeatletter
\newtcolorbox{picturebox}[2][]{%
  enhanced,frame hidden,interior hidden,fonttitle=\bfseries,
  overlay={\begin{tcbclipframe}\node at (frame)
    {\includegraphics[width=\tcb@width,height=\tcb@height]{#2}};\end{tcbclipframe}%
    \begin{tcbclipinterior}\fill[white,opacity=0.75]
    (frame.south west) rectangle (frame.north east);\end{tcbclipinterior}},#1}
\makeatother

\begin{picturebox}[title=My Picture Box]{lichtspiel.jpg}
\lipsum[1]
\end{picturebox}
```

My Picture Box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
\begin{tcbinvclipframe}
  ⟨environment content⟩
\end{tcbinvclipframe}
```

Defines a `Tikz` scope which clips to the *outside* of the frame area path.

```
\tcbset{enhanced jigsaw,fonttitle=\bfseries,opacityback=0.35,colback=blue!5!white,
  frame style={left color=red!75!black,right color=red!10!yellow}}

\begin{tikzpicture}% draw two balls
  \path[use as bounding box] (0,0.8) rectangle +(0.1,0.1);
  \shadedraw [shading=ball] (0,0) circle (1cm);
  \shadedraw [ball color=red] (3,-2.2) circle (1cm);
\end{tikzpicture}

\begin{tcolorbox}[title=A translucent box,
  overlay={\begin{tcbinvclipframe}
    \draw[red,line width=1cm] ([xshift=-2mm,yshift=2mm]frame.north west)
      --([xshift=2mm,yshift=-2mm]frame.south east);
    \draw[red,line width=1cm] ([xshift=-2mm,yshift=-2mm]frame.south west)
      --([xshift=2mm,yshift=2mm]frame.north east);
  \end{tcbinvclipframe}}]
  \lipsum[2]
\end{tcolorbox}
```



```
\begin{tcbclipinterior}
  ⟨environment content⟩
\end{tcbclipinterior}
```

Defines a `Tikz` scope which clips to the interior area path.

```
\begin{tcolorbox}[enhanced,title=My Title,
  overlay={\begin{tcbclipinterior}
    \draw[red,line width=1cm] (interior.north west)--(interior.south east);
    \draw[red,line width=1cm] (interior.south west)--(interior.north east);
  \end{tcbclipinterior}}]
\lipsum[1]
\end{tcolorbox}
```

My Title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
\begin{tcbcliptitle}
  ⟨environment content⟩
\end{tcbcliptitle}
```

Defines a `Tikz` scope which clips to the title area path.

```
\begin{tcolorbox}[enhanced,title=My Title,colframe=blue,colback=yellow!10!white,
  overlay={\begin{tcbcliptitle}\node at (title)
  {\includegraphics[width=\linewidth]{lichtspiel.jpg}};\end{tcbcliptitle}}]
\lipsum[1]
\end{tcolorbox}
```

My Title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

/tcb/clip title=true|false (default `true`, initially `false`)

Sets the title to be clipped to the title area.

```
\tcbset{enhanced,width=5cm,colframe=red!50!white,coltitle=black,
  colbacktitle=yellow!50!white}

\begin{tcolorbox}[title=\mbox{This is a title which is unbreakable and far too long}]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[title=\mbox{This is a title which is unbreakable and far too long},
  clip title]
This is a tcolorbox.
\end{tcolorbox}
```

This is a title which is unbreakable and far too long

This is a tcolorbox.

This is a title which is unbreak

This is a tcolorbox.

/tcb/clip upper=true|false (default `true`, initially `false`)

Sets the upper part to be clipped to the interior area.

```
\newcommand{\mygraphics}[2][]{%
  \tcbox[enhanced,boxsep=0pt,top=0pt,bottom=0pt,left=0pt,
    right=0pt,boxrule=0.4pt,drop fuzzy shadow,clip upper,
    colback=black!75!white,toptitle=2pt,bottomtitle=2pt,nobeforeafter,
    center title,fonttitle=\small\sffamily,title=\detokenize{#2}]
  {\includegraphics[width=\the\dimexpr(\linewidth-4mm)/2\relax]{#2}}}

\mygraphics{lichtspiel.jpg}\hfill
\mygraphics{Basilica_5.png}
```

lichtspiel.jpg



Basilica_5.png



The example for /tcb/clip upper → P. 179 sizes the box according to the dimensions of the picture. To do it the other way around, the watermark options provide an easy solution.

```
\newcommand{\mygraphics}[2][]{%
  \tcbox[enhanced,capture=minipage,boxsep=0pt,top=0pt,bottom=0pt,left=0pt,
    right=0pt,boxrule=0.4pt,drop fuzzy shadow,nobeforeafter,
    colback=black!75!white,toptitle=2pt,bottomtitle=2pt,
    center title,fonttitle=\small\sffamily,title=\detokenize{#2},
    width=(\linewidth-4mm)/2,height=6cm,colbacktitle={black},
    watermark zoom=1.0,watermark graphics={#2}]{}}

\mygraphics{lichtspiel.jpg}\hfill
\mygraphics{Basilica_5.png}
```



/tcb/clip lower=true|false (default true, initially false)

Sets the lower part to be clipped to the interior area.

```
\tcbset{enhanced,width=5cm,colframe=red!50!black,text and listing}

\begin{tcblisting}{}
Donau\-dampf\-schiff\-fahrts\-ka\-pi\-t\"ans\-m\"ut\-zen\-fran\-sen
\end{tcblisting}

\begin{tcblisting}{clip lower}
Donau\-dampf\-schiff\-fahrts\-ka\-pi\-t\"ans\-m\"ut\-zen\-fran\-sen
\end{tcblisting}
```

Donaudampfschifffahrtskapitänsmützenfransen

```
Donau\-dampf\-schiff\-fahrts\-ka\-pi\-t\"ans\-m\"ut\-zen\-fran\-sen
```

Donaudampfschifffahrtskapitänsmützenfransen

```
Donau\-dampf\-schiff\-fa
```

10.5 Border Line Option Keys

The following borderline options are applicable for most skins which use `tikzpicture` as `/tcb/graphical environment`→ P. 138. Therefore, the skin `standard`→ P. 209 does not support these border lines, but most other skins, e. g. `enhanced`→ P. 211.

The borderlines are independent from the normal `tcolorbox` rules. They may be used with or without the `/tcb/segmentation engine`→ P. 139.

The borderlines are stackable, i. e. several different border lines can be used on the same `tcolorbox`. They are drawn *after* the box frame and box interior and *before* overlays or watermarks.

> **!** Technically, the normal `tcolorbox` rules result from a TikZ *filling* process. The border lines are created by a TikZ *drawing* process. This can be used to apply different effects.

`/tcb/borderline={`⟨*width*⟩`}{`⟨*offset*⟩`}{`⟨*options*⟩`}` (no default, initially unset)

Adds a new borderline to the stack of border lines. This border line is drawn with the given ⟨*width*⟩ and gets an ⟨*offset*⟩ computed from the frame outline. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.
The border line is drawn along a TikZ path with the given TikZ ⟨*options*⟩. Note that the TikZ `line width` option should not be used here.
The border lines adapt to the rounded corners of the `tcolorbox`. An inside borderline will switch to sharp corners if necessary, an outside borderline will always be rounded except for `/tcb/sharp corners`→ P. 48.

```
\begin{tcolorbox}[enhanced,title=Rounded corners,fonttitle=\bfseries,boxsep=5pt,
  arc=8pt,
  borderline={0.5pt}{0pt}{red},
  borderline={0.5pt}{5pt}{blue,dotted},
  borderline={0.5pt}{-5pt}{green} ]
This is a tcolorbox.
\end{tcolorbox}
\bigskip
\begin{tcolorbox}[enhanced,title=Sharp corners,fonttitle=\bfseries,boxsep=5pt,
  arc=8pt,sharp corners=downhill,
  borderline={0.5pt}{0pt}{red},
  borderline={0.5pt}{5pt}{blue,dotted},
  borderline={0.5pt}{-5pt}{green} ]
This is a tcolorbox.
\end{tcolorbox}
```

Rounded corners

This is a tcolorbox.

Sharp corners

This is a tcolorbox.

```latex
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,arc=3mm,boxrule=1.5mm,boxsep=1.5mm,
  colback=yellow!20!white,
  colframe=blue,
  borderline={1mm}{1mm}{white},
  borderline={1mm}{2mm}{red} ]
  \lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```latex
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,arc=3mm,boxrule=1.5mm,
  frame hidden,colback=blue!10!white,
  borderline={1mm}{0mm}{blue,dotted} ]
  \lipsum[2]
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```latex
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,skin=enhancedmiddle,
  frame hidden,interior hidden,top=0mm,bottom=0mm,boxsep=0mm,
  borderline={0.75mm}{0mm}{red},
  borderline={0.75mm}{0.75mm}{red!50!yellow},
  borderline={0.75mm}{1.5mm}{yellow}, ]
  \lipsum[3]
\end{tcolorbox}
```

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

```
% \usepackage{lipsum}
\newtcolorbox{mygreenbox}[2][]{%
  enhanced,width=\linewidth-6pt,
  enlarge top by=3pt,enlarge bottom by=3pt,
  enlarge left by=3pt,enlarge right by=3pt,
  title={#2},frame hidden,boxrule=0pt,top=1mm,bottom=1mm,
  colframe=green!30!black, colbacktitle=green!50!yellow,
  coltitle=black, colback=green!25!white,
  borderline={0.5pt}{-0.5pt}{green!75!blue},
  borderline={1pt}{-3pt}{green!50!blue},#1}

\begin{mygreenbox}{My title}
  \lipsum[4]
\end{mygreenbox}
```

My title

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

/tcb/no borderline (no default, initially set)

Removes all borderlines if set before.

/tcb/show bounding box=⟨*color*⟩ (default `red`, initially unset)

Displays the bounding box borderline of a `tcolorbox`. Its intended use is debugging and fine tuning. It should not be part of a final document. The optional ⟨*color*⟩ is the base color for the bounding box borderline.

```
\tcbset{enhanced,nobeforeafter,width=4cm,fonttitle=\bfseries}

\begin{tcolorbox}[show bounding box,title=Normal]
This is a tcolorbox.
\end{tcolorbox}%
\begin{tcolorbox}[show bounding box=blue,title=Shadow,drop fuzzy shadow]
This is a tcolorbox.
\end{tcolorbox}%
\begin{tcolorbox}[show bounding box=green,title=Enlarged,drop fuzzy shadow,
  enlarge by=2mm]
This is a tcolorbox.
\end{tcolorbox}
```

Normal
This is a tcolorbox.

Shadow
This is a tcolorbox.

Enlarged
This is a tcolorbox.

> **!** The following *partial* borderlines act slightly different from the complete borderlines described before. They ignore rounded corner settings, their length is not modified by their ⟨*offset*⟩, they ignore skin settings but adapt to breakable boxes.

N 2014-10-20 **/tcb/borderline north**={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩} (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the north of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline north={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline south**={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩} (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the south of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline south={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline east**={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩} (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the east of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline east={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline west**={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩} (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the west of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline west={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline horizontal={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩}** (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the north and south of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderlines inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves them outside without changing the bounding box.

```
\begin{tcolorbox}[blanker,top=3mm,bottom=3mm,
   borderline horizontal={2pt}{0pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline vertical={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩}** (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the east and west of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderlines inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves them outside without changing the bounding box.

```
\begin{tcolorbox}[blanker,left=3mm,right=3mm,
   borderline vertical={2pt}{0pt}{red}]
  This is a \textbf{tcolorbox}.\\
  My second line.
\end{tcolorbox}
```

This is a **tcolorbox**.
My second line.

```
\begin{tcolorbox}[enhanced,colback=yellow!10!white,boxrule=0pt,frame hidden,
  borderline north={1mm}{-2mm}{red},
  borderline south={1mm}{-2mm}{blue},
  borderline west={1mm}{-2mm}{green},
  borderline east={1mm}{-2mm}{yellow}]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

10.6 Shadow Option Keys

The following shadow options are applicable for most skins which use `tikzpicture` as `/tcb/graphical environment`→ P. 138. Therefore, the skin `standard`→ P. 209 does not support these shadows, but most other skins, e. g. `enhanced`→ P. 211.

The shadows are stackable, i. e. several different shadows can be used on the same `tcolorbox`. They are drawn *before* the box frame is drawn.

`/tcb/no shadow` (no default)

Removes all shadows if set before.

10.6.1 Common Shadows and Halos

`/tcb/drop shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

`/tcb/drop fuzzy shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop fuzzy shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop fuzzy shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

`/tcb/drop midday shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop midday shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop midday shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

/tcb/drop fuzzy midday shadow=⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop fuzzy midday shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop fuzzy midday shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

/tcb/halo=⟨*size*⟩ with ⟨*color*⟩ (style, default `0.9mm with yellow`)

Adds a new halo shadow with the given ⟨*color*⟩ which overlaps the colorbox an all sides by ⟨*size*⟩.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own halo,halo]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Another halo,
  halo=2mm with green]
This is a tcolorbox.
\end{tcolorbox}
```

My own halo

This is a tcolorbox.

Another halo

This is a tcolorbox.

/tcb/fuzzy halo=⟨*size*⟩ with ⟨*color*⟩ (style, default `0.9mm with yellow`)

Adds a new fuzzy halo shadow with the given ⟨*color*⟩ which overlaps the colorbox an all sides by ⟨*size*⟩ plus `0.48mm`.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own halo,fuzzy halo]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Another halo,
  fuzzy halo=2mm with green]
This is a tcolorbox.
\end{tcolorbox}
```

My own halo

This is a tcolorbox.

Another halo

This is a tcolorbox.

```
\begin{tcolorbox}[blank,enhanced jigsaw,boxsep=2pt,arc=2pt,
  fuzzy halo=2mm with red!50!white,
  fuzzy halo=1mm with white]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

For all following shadows, the optionally given ⟨*color*⟩ for the shadow can be changed equivalent to the preceding examples.

/tcb/drop shadow southeast=⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop shadow` → P. 186.

```
\begin{tcolorbox}[drop shadow southeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop shadow south=⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop midday shadow` → P. 186.

```
\begin{tcolorbox}[drop shadow south,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop shadow southwest=⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow southwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop shadow west=⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow west,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop shadow northwest=⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow northwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop shadow north=⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow north,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop shadow northeast=⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow northeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop shadow east=⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow east,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow southeast=⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop fuzzy shadow` → P. 186.

```
\begin{tcolorbox}[drop fuzzy shadow southeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow south=⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop fuzzy midday shadow` → P. 187.

```
\begin{tcolorbox}[drop fuzzy shadow south,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow southwest=⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow southwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow west=⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow west,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow northwest=⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow northwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow north=⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow north,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow northeast=⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow northeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

/tcb/drop fuzzy shadow east=⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow east,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

10.6.2 Lifted Shadows

/tcb/drop lifted shadow=⟨*color*⟩ (style, default `black!50!white`)

Adds a new lifted shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  boxrule=0.4pt,sharp corners,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop lifted shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop lifted shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

/tcb/drop small lifted shadow=⟨*color*⟩ (style, default `black!50!white`)

Adds a new small lifted shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  boxrule=0.4pt,sharp corners,
  colframe=red!75!black,fonttitle=\bfseries}

\tcbox[drop small lifted shadow,size=fbox]
  {This is a tcolorbox.}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop small lifted shadow=black]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

/tcb/drop large lifted shadow=⟨*color*⟩ (style, default `black!50!white`)

Adds a new large lifted shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop large lifted shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop large lifted shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

10.6.3 Generic Shadows

`/tcb/shadow={⟨xshift⟩}{⟨yshift⟩}{⟨offset⟩}{⟨options⟩}` (no default)

Adds a new shadow to the stack of shadows. This shadow follows the outline of the `tcolorbox` but is shifted by ⟨*xshift*⟩ and ⟨*yshift*⟩. The ⟨*offset*⟩ value is a distance value from the frame outline. A positive ⟨*offset*⟩ value shrinks the shadow and a negative ⟨*offset*⟩ value enlarges the shadow. The shadow is filled along a TikZ path with the given TikZ ⟨*options*⟩.

The shadows adapt to the rounded corners of the `tcolorbox`. An shrinked shadow will switch to sharp corners if necessary, an enlarged shadow may become more rounded depending on several factors. But `/tcb/sharp corners` → P. 48 have sharp shadows.

> **!** Shadows are not considered for the bounding box computation by default. Large shadows may be overlaped by the following content. But, the bounding box can be adapted if necessary.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
  shadow={2mm}{-1mm}{0mm}{black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  shadow={-1mm}{-2mm}{0mm}{fill=blue,
    opacity=0.5}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Double shadow,
  shadow={-1.5mm}{-1.5mm}{0mm}{fill=blue,
    opacity=0.25},
  shadow={1.5mm}{-1.5mm}{0mm}{fill=red,
    opacity=0.25}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Far shadow,
  shadow={5.5mm}{-3.5mm}{2mm}{fill=black,
    opacity=0.25}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Halo shadow,
  shadow={0mm}{0mm}{-1.5mm}%
     {fill=yellow!75!red,opacity=0.5}]
This is a tcolorbox.
\end{tcolorbox}
```

My own shadow
This is a tcolorbox.

Another shadow
This is a tcolorbox.

Double shadow
This is a tcolorbox.

Far shadow
This is a tcolorbox.

Halo shadow
This is a tcolorbox.

/tcb/fuzzy shadow={⟨*xshift*⟩}{⟨*yshift*⟩}{⟨*offset*⟩}{⟨*step*⟩}{⟨*options*⟩} (no default)

Adds a new fuzzy shadow to the stack of shadows. Actually, this option adds several shadows which appear like a shadow with a fuzzy border. This fuzzy shadow follows the outline of the `tcolorbox` but is shifted by ⟨*xshift*⟩ and ⟨*yshift*⟩. The ⟨*offset*⟩ value is a distance value from the frame outline. A positive ⟨*offset*⟩ value shrinks the shadow and a negative ⟨*offset*⟩ value enlarges the shadow. The {⟨*step*⟩} value describes a shrink offset used for the combination of the partial shadows. The shadow is filled along a Ti*k*Z path with the given Ti*k*Z ⟨*options*⟩ but any `opacity` value will be ignored.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
  fuzzy shadow={2mm}{-1mm}{0mm}{0.1mm}%
               {black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  fuzzy shadow={-1mm}{-2mm}{0mm}{0.2mm}%
               {fill=blue}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Double shadow,
  fuzzy shadow={-1.5mm}{-1.5mm}{0mm}{0.1mm}%
               {blue},
  fuzzy shadow={1.5mm}{-1.5mm}{0mm}{0.1mm}%
               {red}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Far shadow,
  fuzzy shadow={5.5mm}{-3.5mm}{0mm}{0.3mm}%
               {black}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Glow shadow,
  fuzzy shadow={0mm}{0mm}{-1.5mm}{0.15mm}%
               {yellow!75!red}]
This is a tcolorbox.
\end{tcolorbox}
```

My own shadow

This is a tcolorbox.

Another shadow

This is a tcolorbox.

Double shadow

This is a tcolorbox.

Far shadow

This is a tcolorbox.

Glow shadow

This is a tcolorbox.

```
\newtcolorbox{mybox}[1][]{enhanced,
  fuzzy shadow={1.0mm}{-1.0mm}{0.12mm}{0mm}{blue!50!white},
  fuzzy shadow={-1.0mm}{-1.0mm}{0.12mm}{0mm}{red!50!white},
  fuzzy shadow={-1.0mm}{1.0mm}{0.12mm}{0mm}{green!50!white},
  fuzzy shadow={1.0mm}{1.0mm}{0.12mm}{0mm}{yellow!50!white},#1
}

\begin{mybox}[title=A multi shadow box]
This is a tcolorbox.
\end{mybox}
```

A multi shadow box

This is a tcolorbox.

N 2015-05-05 **/tcb/smart shadow arc=true|false** (default `true`, initially `true`)

If set to `true`, the shadow drawing algorithm tries to do a somewhat smart calculation of the arc for the shadow. The result is pleasing for typical boxes with rounded corners, but gives strange results for circular boxes.

```
\tcbset{enhanced,nobeforeafter,colback=red!5!white,
  colframe=red!75!black,width=3cm,square,halign=center,valign=center
  }

\begin{tcolorbox}[drop shadow]
Smart shadow arc (arguably better than normal)
\end{tcolorbox}
\hfill
\begin{tcolorbox}[smart shadow arc=false, drop shadow]
Normal shadow arc
\end{tcolorbox}
\hfill
\begin{tcolorbox}[circular arc, drop shadow]
Smart shadow arc (worse than normal)
\end{tcolorbox}
\hfill
\begin{tcolorbox}[circular arc, smart shadow arc=false, drop shadow]
Normal shadow arc
\end{tcolorbox}
```



/tcb/lifted shadow={⟨*xshift*⟩}{⟨*yshift*⟩}{⟨*bend*⟩}{⟨*step*⟩}{⟨*options*⟩} (no default)

Adds a new lifted shadow to the stack of shadows. Actually, this option adds several shadows which appear like a shadow with a fuzzy border. This lifted shadow follows the outline of the `tcolorbox` but is shifted by ⟨*xshift*⟩ and ⟨*yshift*⟩ on the lower left corner and by −⟨*xshift*⟩ and ⟨*yshift*⟩ on the lower right corner. Additionally, there is a ⟨*bend*⟩ in the middle. The `{`⟨*step*⟩`}` value describes a shrink offset used for the combination of the partial shadows. The shadow is filled along a Ti*k*Z path with the given Ti*k*Z ⟨*options*⟩ but any `opacity` value will be ignored.

```
\tcbset{enhanced,colback=red!5!white,
  boxrule=0.1pt,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
  lifted shadow={1mm}{-2mm}{3mm}{0.1mm}%
              {black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
```



10.6.4 TikZ Shadows

Alternativ to the package shadow options described before, shadows from the «Shadows Library» of TikZ can be used. Such shadows can be added directly to the frame path using `/tcb/frame style` → P. 152.

```
% \usetikzlibrary{shadows}
\begin{tcolorbox}[enhanced,
  colback=red!5!white,colframe=red!75!black,
  frame style={drop shadow} ]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
% \usetikzlibrary{shadows}
\begin{tcolorbox}[enhanced,height=3cm,
  colback=red!5!white,colframe=red!75!black,
  halign=center,valign=center,
  frame style={circular drop shadow} ]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
% \usetikzlibrary{shadows}
\begin{tcolorbox}[enhanced,width=2.5cm,
  square,circular arc,
  halign=center,valign=center,
  colback=red!5!white,colframe=red!75!black,
  frame style={circular glow={fill=red}} ]
  tcolorbox
\end{tcolorbox}
```

tcolorbox

10.7 TikZ Picture Option Keys

The following general options are applicable for skins which use `tikzpicture` as `/tcb/graphical environment`→ P. 138. Therefore, the skin `standard`→ P. 209 does not support these options, but most other skins, e. g. `enhanced`→ P. 211.

`/tcb/tikz`=⟨*tikz option list*⟩ (no default, initially empty)

Adds the given ⟨*tikz option list*⟩ to the main `tikzpicture` environment used to draw the color box, see [22]. If this option is applied a second time, the new ⟨*tikz option list*⟩ is appended to the current option list.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=Transparent box,
  tikz={opacity=0.5,transparency group}]
This is a tcolorbox.
\end{tcolorbox}
```




```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  fontupper=\bfseries\Huge,
  halign title=center,halign=center}

\begin{tcolorbox}[title=Rotated box,
  tikz={rotate=30}]
Sold!
\end{tcolorbox}
```

`/tcb/tikz reset` (initially set)

Removes all options given by `/tcb/tikz`.

`/tcb/at begin tikz`=⟨*tikz code*⟩ (no default, initially empty)

The given ⟨*tikz code*⟩ is executed at the beginning of the `tikzpicture` environment after the TikZ option `execute at begin picture` was applied. If this option is applied a second time, the new ⟨*tikz code*⟩ is appended to the current code.

`/tcb/at begin tikz reset` (initially set)

Removes all code given by `/tcb/at begin tikz`.

`/tcb/at end tikz`=⟨*tikz code*⟩ (no default, initially empty)

The given ⟨*tikz code*⟩ is executed at the ending of the `tikzpicture` environment before the TikZ option `execute at end picture` was applied. If this option is applied a second time, the new ⟨*tikz code*⟩ is appended to the current code.

`/tcb/at end tikz reset` (initially set)

Removes all code given by `/tcb/at end tikz`.

/tcb/rotate=⟨*angle*⟩ (no default, initially unset)

Rotates the `tcolorbox` by the given ⟨*angle*⟩. Note that this is a Ti*k*Z coordinate transformation i.e. not all graphical elements like shadings will really be rotated.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=Rotated box,rotate=30]
This is a tcolorbox.
\end{tcolorbox}
```



/tcb/scale=⟨*fraction*⟩ (no default, initially unset)

Scales the `tcolorbox` by the given ⟨*fraction*⟩. Note that this is a Ti*k*Z coordinate transformation i.e. not all graphical elements like line widths will really be scaled.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=Scaled box,scale=0.5]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[title=Scaled box,scale=1.25]
This is a tcolorbox.
\end{tcolorbox}
```



/tcb/remember (style, initially unset)

Shortcut for `tikz={remember picture}`. This allows one to reference nodes in other Ti*k*Z pictures.

```
\begin{tcolorbox}[enhanced,remember,colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,title=The four corners of a paper,
  overlay={\draw[red!50!white,line width=1mm,opacity=0.5,shorten >=3mm]
    (frame.north west) edge[->] (current page.north west)
    (frame.north east) edge[->] (current page.north east)
    (frame.south west) edge[->] (current page.south west)
    (frame.south east) edge[->] (current page.south east);}]
This is a tcolorbox.
\end{tcolorbox}
```

The four corners of a paper

This is a tcolorbox.

/tcb/remember as=⟨*name*⟩ (style, no default, initially unset)

The **frame** node will be remembered by the given ⟨*name*⟩ to be referenced in other TikZ pictures.

```
% \usepackage{lipsum}
\newtcolorbox{mybox}[1][]{enhanced,colframe=blue!75!black,colback=blue!10!white,
  fonttitle=\bfseries,#1}

\begin{mybox}[title=First Box,nobeforeafter,width=\linewidth/4,remember as=one]
This is a test.
\end{mybox}
\hfill
\begin{mybox}[title=Second Box,nobeforeafter,width=\linewidth/4,remember as=two]
This is a test.
\end{mybox}
\hfill
\begin{mybox}[title=Third Box,nobeforeafter,width=\linewidth/4,remember as=three]
This is a test.
\end{mybox}

\lipsum[2]

\begin{mybox}[title=Fourth Box,remember as=four]
This is a test.
\end{mybox}

\begin{tikzpicture}[overlay,remember picture,line width=1mm,draw=red!75!black]
  \draw[->] (one.east) to[bend right] node[above] {A} (two.west);
  \draw[->] (two.east) to[bend left] node[above] {B} (three.west);
  \draw[->] (three.east) to[bend left=90] node[right] {C} (four.east);
  \draw[->] (four.west) to[bend left=90] node[left] {D} (one.west);
\end{tikzpicture}
```



Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

10.8 Underlay Option Keys

Underlays are quite similar to overlays described in Section 4.12 on page 74. Underlays are drawn *after* the frame and interior are drawn and *before* overlays and the text content is drawn; see Section 9.4 on page 145 for the general drawing scheme.

The differences between underlays and overlays are:

- Underlays are not applicable for the skins `standard`^{→ P. 209} and `standard jigsaw`^{→ P. 210}, whereas overlays are applicable also for these skins. The skin `spartan`^{→ P. 252} supports underlays but no overlays.

  > **!** If an underlay is used with the `standard`^{→ P. 209} skin, it is silently ignored.

- Underlays are stackable, i. e. several different underlays can be used on the same `tcolorbox`. Overlays are not stackable by default (but with some help of the library LIB hooks).
- Boxed titles are implemented with underlays (Section 10.2 on page 159), watermarks are implemented with overlays (Section 10.3 on page 169).

`/tcb/underlay=`⟨*graphical code*⟩ (no default, initially unset)

Adds ⟨*graphical code*⟩ to the box drawing process. This ⟨*graphical code*⟩ is drawn *after* the frame and interior and *before* the text content.

```
\newtcolorbox{mybox}[1][]{enhanced,colback=red!5!white,
  colbacktitle=red!85!black!50!white,
  colframe=red!75!black,fonttitle=\bfseries,watermark color=yellow!50!white,
  underlay={\begin{tcbclipinterior}
    \draw[red!40!white,line width=1cm] (interior.south west)--(interior.north east);
    \end{tcbclipinterior}},
  attach boxed title to top center={yshift=-2mm},#1}

\begin{mybox}[title=My box,watermark text=My Watermark]
\lipsum[2]
\end{mybox}
```



`/tcb/no underlay` (style, no default, initially set)

Removes the underlay if set before.

/tcb/underlay broken=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process. /tcb/underlay→P. 199 overwrites this key.

/tcb/underlay unbroken=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 but *is not* broken actually or if the box is set to be /tcb/unbreakable→P. 380, then the ⟨*graphical code*⟩ is added to the box drawing process. /tcb/underlay→P. 199 overwrites this key.

/tcb/no underlay unbroken (style, no default, initially set)

Removes the unbroken underlay if set before.

/tcb/underlay first=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *first* part of the break sequence. /tcb/underlay→P. 199 overwrites this key.

/tcb/no underlay first (style, no default, initially set)

Removes the first underlay if set before.

/tcb/underlay middle=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *middle* parts (if any) of the break sequence. /tcb/underlay→P. 199 overwrites this key.

/tcb/no underlay middle (style, no default, initially set)

Removes the middle underlay if set before.

/tcb/underlay last=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *last* part of the break sequence. /tcb/underlay→P. 199 overwrites this key.

/tcb/no underlay last (style, no default, initially set)

Removes the last underlay if set before.

/tcb/underlay boxed title=⟨*graphical code*⟩ (no default, initially unset)

If the box has a *boxed title*, see Section 10.2 on page 159, then the ⟨*graphical code*⟩ is added to the box drawing process *before* the boxed title is drawn.

/tcb/no underlay boxed title (style, no default, initially set)

Removes the boxed title underlay if set before.

/tcb/underlay unbroken and first=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting /tcb/underlay unbroken and /tcb/underlay first together. /tcb/underlay→P. 199 overwrites this key.

/tcb/underlay middle and last=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting /tcb/underlay middle and /tcb/underlay last together. /tcb/underlay→P. 199 overwrites this key.

/tcb/underlay unbroken and last=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting /tcb/underlay unbroken and /tcb/underlay last together. /tcb/underlay→P. 199 overwrites this key.

N 2014-09-19 **/tcb/underlay first and middle=**⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting /tcb/underlay first and /tcb/underlay middle together. /tcb/underlay→P. 199 overwrites this key.

10.9 Finish Option Keys

Finishes are quite similar to underlays described in Section 10.8 on page 199 and overlays described in Section 4.12 on page 74. Finishes are drawn *after* the text content is drawn; see Section 9.4 on page 145 for the general drawing scheme. Therefore, a finish will reduce the readability of the text content.

Finishes are intended for special effects like highlights or glosses or text over text.

- Finishes are only applicable for the skins `enhanced`→P. 211, `empty`→P. 242, `freelance`→P. 255, `bicolor`→P. 224, `beamer`→P. 233, and `widget`→P. 238.

  ! If a finish is used with the `standard`→P. 209 skin, it is silently ignored.

- Finishes are stackable, i. e. several different finishes can be used on the same `tcolorbox`.

`/tcb/finish=`⟨*graphical code*⟩ (no default, initially unset)

Adds ⟨*graphical code*⟩ to the box drawing process. This ⟨*graphical code*⟩ is drawn *after* the text content.

```
\newtcolorbox{mybox}[1][]{enhanced,colback=red!5!white,
  colbacktitle=red!85!black!50!white,colframe=red!75!black,fonttitle=\bfseries,
  finish={\begin{tcbclipframe}
    \path[bottom color=black,top color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.south east) -- (frame.north east) -- cycle;
    \path[top color=white,bottom color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.north east) -- (frame.north west) -- cycle;
    \end{tcbclipframe}},#1}

\begin{mybox}[title=My box]
\lipsum[2]
\end{mybox}
```

My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\newtcolorbox{mybox}[1][]{enhanced,colback=red!5!white,
  colbacktitle=red!85!black!50!white,colframe=red!75!black,fonttitle=\bfseries,
  finish={\node[draw,fill=white,fill opacity=0.85,inner sep=5mm,
    rounded corners] at (frame.center) {\Huge\bfseries Finish!};},#1}

\begin{mybox}[title=My box]
\lipsum[2]
\end{mybox}
```

My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Finish!

/tcb/no finish (style, no default, initially set)

Removes the finish if set before.

/tcb/finish broken=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process. /tcb/finish→P. 201 overwrites this key.

/tcb/finish unbroken=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 but *is not* broken actually or if the box is set to be /tcb/unbreakable→P. 380, then the ⟨*graphical code*⟩ is added to the box drawing process. /tcb/finish→P. 201 overwrites this key.

/tcb/no finish unbroken (style, no default, initially set)

Removes the unbroken finish if set before.

/tcb/finish first=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *first* part of the break sequence. /tcb/finish→P. 201 overwrites this key.

/tcb/no finish first (style, no default, initially set)

Removes the first finish if set before.

/tcb/finish middle=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *middle* parts (if any) of the break sequence. /tcb/finish→P. 201 overwrites this key.

/tcb/no finish middle (style, no default, initially set)

Removes the middle finish if set before.

/tcb/finish last=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→P. 379 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *last* part of the break sequence. /tcb/finish→P. 201 overwrites this key.

/tcb/no finish last (style, no default, initially set)

Removes the last finish if set before.

/tcb/finish unbroken and first=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting /tcb/finish unbroken and /tcb/finish first together. /tcb/finish→P. 201 overwrites this key.

/tcb/finish middle and last=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting /tcb/finish middle and /tcb/finish last together. /tcb/finish→P. 201 overwrites this key.

/tcb/finish unbroken and last=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting /tcb/finish unbroken and /tcb/finish last together. /tcb/finish→P. 201 overwrites this key.

N 2014-09-19 **/tcb/finish first and middle=**⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting /tcb/finish first and /tcb/finish middle together. /tcb/finish→P. 201 overwrites this key.

10.10 Hyper Option Keys

All options of this section need the package **hyperref** [15] to be loaded separately. All these options are implemented as /tcb/finish→ P. 201 and can be disabled by /tcb/no finish→ P. 202.

> **!** If the package **hyperref** [15] is not loaded or if the standard→ P. 209 skin is used, all hyper option are silently ignored.

N 2017-02-03 **/tcb/hyperref=**⟨*marker*⟩ (no default, initially unset)

The whole *frame* of a **tcolorbox** is make an active hyperlink for a ⟨*marker*⟩ which was given by **\label** or /tcb/label→ P. 101 or /tcb/phantomlabel→ P. 101. Such, the **tcolorbox** is made a clickable button (depending on the previewer).

```
% \section{Library skins}\label{sec:skins}%
\begin{tcolorbox}[beamer,colback=red!50,
  hyperref=sec:skins]
Jump to the heading of Section~\ref*{sec:skins}.
\end{tcolorbox}
```

Jump to the heading of Section 10.

N 2017-02-03 **/tcb/hyperref interior=**⟨*marker*⟩ (no default, initially unset)

Identical to /tcb/hyperref, but only the *interior* of a **tcolorbox** is made a hyperlink (without frame and title).

N 2017-02-03 **/tcb/hyperref title=**⟨*marker*⟩ (no default, initially unset)

Identical to /tcb/hyperref, but only the *title* of a **tcolorbox** is made a hyperlink.

N 2017-02-03 **/tcb/hyperref node={**⟨*marker*⟩**}{**⟨*node*⟩**}** (no default, initially unset)

Identical to /tcb/hyperref, but only the given Ti*k*Z ⟨*node*⟩ is made a hyperlink. This ⟨*node*⟩ may be **frame**, **interior**, **title**, or any other named node used for drawing the **tcolorbox**. The ⟨*node*⟩ may be defined inside /tcb/underlay→ P. 199, /tcb/overlay→ P. 74 or /tcb/finish→ P. 201. If the later is used, define the node *before* /tcb/hyperref node is applied.

```
% \section{Library skins}\label{sec:skins}%
\begin{tcolorbox}[enhanced,colback=yellow!10,
  underlay={\node[red,fill=red!30,inner sep=3mm]
   (click) at (frame.center) {X};},
  hyperref node={sec:skins}{click}]
Jump to the heading of Section~\ref*{sec:skins}
(X marks the click point).
\end{tcolorbox}
```

Jump to the heading of Section 10 (X marks the click point).

N 2017-02-03 **/tcb/hyperlink=**⟨*marker*⟩ (no default, initially unset)

The whole *frame* of a **tcolorbox** is make an active hyperlink for a ⟨*marker*⟩ which was given by **\hypertarget** or /tcb/hypertarget→ P. 103. Such, the **tcolorbox** is made a clickable button (depending on the previewer).

```
% \usepackage{hyperref}%
\begin{tcolorbox}[enhanced,
  colback=blue!10,colframe=blue!50!black,
  hypertarget=hypertwinB,
  hyperlink=hypertwinA,
  title=Box B]
Click me to jump to Box A.
\end{tcolorbox}
```

Box B

Click me to jump to Box A.

N 2017-02-03 **/tcb/hyperlink interior=⟨*marker*⟩** (no default, initially unset)

Identical to /tcb/hyperlink→ P. 203, but only the *interior* of a tcolorbox is made a hyperlink (without frame and title).

N 2017-02-03 **/tcb/hyperlink title=⟨*marker*⟩** (no default, initially unset)

Identical to /tcb/hyperlink→ P. 203, but only the *title* of a tcolorbox is made a hyperlink.

N 2017-02-03 **/tcb/hyperlink node={⟨*marker*⟩}{⟨*node*⟩}** (no default, initially unset)

Identical to /tcb/hyperlink→ P. 203, but only the given TikZ ⟨*node*⟩ is made a hyperlink. This ⟨*node*⟩ may be frame, interior, title, or any other named node used for drawing the tcolorbox. The ⟨*node*⟩ may be defined inside /tcb/underlay→ P. 199, /tcb/overlay→ P. 74 or /tcb/finish→ P. 201. If the later is used, define the node *before* /tcb/hyperlink node is applied.

N 2017-02-03 **/tcb/hyperurl=⟨*url*⟩** (no default, initially unset)

The whole *frame* of a tcolorbox is make an active hyperlink for an ⟨*url*⟩ in the same manner as using \href or \url. Such, the tcolorbox is made a clickable button (depending on the previewer).

```
\begin{tcolorbox}[enhanced,colback=red!50,
  hyperurl=https://www.ctan.org/pkg/tcolorbox]
View CTAN with a browser.
\end{tcolorbox}
```

View CTAN with a browser.

N 2017-02-03 **/tcb/hyperurl interior=⟨*url*⟩** (no default, initially unset)

Identical to /tcb/hyperurl, but only the *interior* of a tcolorbox is made a hyperlink (without frame and title).

N 2017-02-03 **/tcb/hyperurl title=⟨*url*⟩** (no default, initially unset)

Identical to /tcb/hyperurl, but only the *title* of a tcolorbox is made a hyperlink.

N 2017-02-03 **/tcb/hyperurl node={⟨*url*⟩}{⟨*node*⟩}** (no default, initially unset)

Identical to /tcb/hyperurl, but only the given TikZ ⟨*node*⟩ is made a hyperlink. This ⟨*node*⟩ may be frame, interior, title, or any other named node used for drawing the tcolorbox. The ⟨*node*⟩ may be defined inside /tcb/underlay→ P. 199, /tcb/overlay→ P. 74 or /tcb/finish→ P. 201. If the later is used, define the node *before* /tcb/hyperurl node is applied.

N 2017-02-03 **/tcb/hyperurl*={⟨*options*⟩}{⟨*url*⟩}** (no default, initially unset)

Identical to /tcb/hyperurl, but additional hyperref [15] ⟨*options*⟩ are applied.

```
\begin{tcolorbox}[enhanced,colback=green!50,
  hyperurl*={page=3,pdfnewwindow=true}%
            {tcolorbox-example.pdf}]
Open example file on Page~3.
\end{tcolorbox}
```

Open example file on Page 3.

N 2017-02-03 **/tcb/hyperurl* interior={⟨*options*⟩}{⟨*url*⟩}** (no default, initially unset)

Identical to /tcb/hyperurl interior, but additional hyperref [15] ⟨*options*⟩ are applied.

N 2017-02-03 **/tcb/hyperurl* title={⟨*options*⟩}{⟨*url*⟩}** (no default, initially unset)

Identical to /tcb/hyperurl title, but additional hyperref [15] ⟨*options*⟩ are applied.

N 2017-02-03 **/tcb/hyperurl* node={⟨*options*⟩}{⟨*url*⟩}{⟨*node*⟩}** (no default, initially unset)

Identical to /tcb/hyperurl node, but additional hyperref [15] ⟨*options*⟩ are applied.

10.11 Jigsaw Skin Variants

As described in Section 9.1 on page 137, a `tcolorbox` is drawn by up to four *engines*. Typically, the *frame* engine fills the complete box area with color and the other engines fill certain areas with other colors. Finally, only the area which you see as *frame* of the box will display the frame color. For most applications, this is a good approach.

For certain boxes, a more delicate procedure is needed. E.g., if the box should be translucent, an already painted area cannot be made unpainted. Therefore, more elaborate frame engines saw holes into the frame where the interior area and optionally the title area will be painted. The resulting skins are called *jigsaw* skins. For `standard`→ P. 209 and `enhanced`→ P. 211, there are variants called `standard jigsaw`→ P. 210 and `enhanced jigsaw`→ P. 218.

```
\newcommand{\ballexample}{\begin{tikzpicture}
  \path[use as bounding box] (0,0.8) rectangle +(0.1,0.1);
  \shadedraw [shading=ball] (0,0) circle (1cm);
  \shadedraw [ball color=red] (3,-2.2) circle (1cm);
\end{tikzpicture}}

\tcbset{enhanced,colback=blue!5!white,
  frame style={left color=red!75!black,right color=red!10!yellow},
  fonttitle=\bfseries }

\ballexample

\begin{tcolorbox}[title=A normal box]
  \lipsum[2]
\end{tcolorbox}

\ballexample

\begin{tcolorbox}[title=A translucent jigsaw box,
  enhanced jigsaw,opacityback=0.35]
  \lipsum[2]
\end{tcolorbox}
```



```
\tcbset{enhanced,colback=red!10!white,coltitle=black,
  frame style={left color=red!75!black,right color=red!10!yellow},
  fonttitle=\bfseries,interior hidden,title hidden}

\begin{tcolorbox}[title=A normal box with hidden interior and title]
  This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[enhanced jigsaw,
  title=A jigsaw box with hidden interior and title]
  This is a tcolorbox.
\end{tcolorbox}
```

A normal box with hidden interior and title

This is a tcolorbox.

A jigsaw box with hidden interior and title

This is a tcolorbox.

```
\newtcolorbox{mybox}{skin=enhancedmiddle jigsaw,leftrule=5mm,rightrule=5mm,
  boxsep=0mm,top=0mm,bottom=0mm,
  frame style={top color=blue,bottom color=red},interior hidden}

\begin{mybox}
  \lipsum[2]
\end{mybox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

10.12 Draft Mode

To reduce the compiliation time while drafting a document, the *draft mode* can be applied. Basically, it changes all skins to `spartan`→P. 252 and sets the `/tcb/fit algorithm`→P. 435 to `squeeze`. Especially, when fuzzy shadows are used, the speedup will be considerable high.

> **!** It is strongly recommended that the draft mode is *not* used for the final document. Use `spartan`→P. 252 directly, if you want to stay with it. The draft mode implementation may change in future.

> **!** Normally, switching to the draft mode should not alter the geometry of your document. Since overlays are deactivated, any code placed there (e.g. counter changes) is not executed anymore! Also, `/tcb/remember as`→P. 198 will not have any effect. You may exclude critical code with `\tcbinterruptdraftmode` / `\tcbcontinuedraftmode` from converting to draft mode.

`\tcbstartdraftmode`

Any following `tcolorbox` code is put into *draft mode*. All skin settings are overruled with `spartan`→P. 252. Overlays, watermarks, shadows, borderlines, and rounded corners are deactivated for all `tcolorbox` layers.

`\tcbstopdraftmode`

The *draft mode* is deactivated for the following code.

`\tcbinterruptdraftmode`

If the compilation is in *draft mode*, the *draft mode* is deactivated until a following `\tcbcontinuedraftmode` is detected.
If the compilation is not in *draft mode*, nothing happens and a following `\tcbcontinuedraftmode` will not start the *draft mode*.

> **!** The pair `\tcbinterruptdraftmode` and `\tcbcontinuedraftmode` cannot be used nested.

`\tcbcontinuedraftmode`

Continues the *draft mode* which was suspended by a preceding `\tcbinterruptdraftmode`. Nothing happens, if there was no draft mode before `\tcbinterruptdraftmode`.

> **!** Code, which is place between `\tcbinterruptdraftmode` and `\tcbcontinuedraftmode` is shielded from *draft mode*.

`/tcb/draftmode=true|false` (default `true`, initially `false`)

If set to `true`, the *draft mode* is started. If set to `false`, the *draft mode* is stopped.

```
\newtcolorbox{mybeamer}[2][]{beamer,colback=Salmon!50!white,
  colframe=FireBrick!75!black,adjusted title={#2},#1}

\begin{mybeamer}{Beamer box}
This box looks like a box provided by the \texttt{beamer} class.
\end{mybeamer}\par\medskip
\begin{mybeamer}[draftmode]{Beamer box}
This box looks like a box provided by the \texttt{beamer} class.
\end{mybeamer}
```

Beamer box

This box looks like a box provided by the `beamer` class.

Beamer box

This box looks like a box provided by the `beamer` class.

10.13 Skin Family "standard"

> **!** Note that the option keys `/tcb/frame style`[→P. 152], `/tcb/interior style`[→P. 153], `/tcb/segmentation style`[→P. 155], and `/tcb/title style`[→P. 155] are not be applicable to the standard skin. Also, watermarks (see Subsection 10.3) are not usable with the standard skin.

`/tcb/skin=standard` (skin)

This is the standard skin from the core package. All drawing engines are set to type `standard`. The drawing is based on `pgf` commands and does not need the `tikz` package.

Environment and engines for the skin "standard"

`/tcb/graphical environment`[→P. 138]:	`pgfpicture`
`/tcb/frame engine`[→P. 138]:	`standard`
`/tcb/interior titled engine`[→P. 138]:	`standard`
`/tcb/interior engine`[→P. 139]:	`standard`
`/tcb/segmentation engine`[→P. 139]:	`standard`
`/tcb/title engine`[→P. 139]:	`standard`

`/tcb/standard` (style, no value)

This is an abbreviation for setting `skin=standard`.

```
\begin{tcbraster}[standard,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=standard jigsaw (skin)

This is the standard jigsaw skin from the core package. It differs from the skin `standard` → P. 209 by its frame engine, see Section 10.11 on page 205.

Environment and engines for the skin "standard jigsaw"

/tcb/graphical environment → P. 138:	pgfpicture
/tcb/frame engine → P. 138:	standardjigsaw
/tcb/interior titled engine → P. 138:	standard
/tcb/interior engine → P. 139:	standard
/tcb/segmentation engine → P. 139:	standard
/tcb/title engine → P. 139:	standard

/tcb/standard jigsaw (style, no value)

This is an abbreviation for setting `skin=standard jigsaw`.

```
\begin{tcbraster}[standard jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



10.14 Skin Family "enhanced"

> **!** If you like the standard appearance of a `tcolorbox` but you want to have some "enhanced" features, the `enhanced` skin is what you are looking for.

/tcb/skin=enhanced (skin)

This skin translates the drawing commands of the core package into `tikz` path commands. Therefore, it allows all `tikz` high level options for these paths and has more flexibility compared to the `standard` → P. 209 skin. You pay for this with some prolonged compilation time. The `tikz` path options can be given with the option keys `/tcb/frame style` → P. 152, `/tcb/interior style` → P. 153, `/tcb/segmentation style` → P. 155, and `/tcb/title style` → P. 155.

Environment and engines for the skin "enhanced"

`/tcb/graphical environment` → P. 138:	`tikzpicture`
`/tcb/frame engine` → P. 138:	`path`
`/tcb/interior titled engine` → P. 138:	`path`
`/tcb/interior engine` → P. 139:	`path`
`/tcb/segmentation engine` → P. 139:	`path`
`/tcb/title engine` → P. 139:	`path`

/tcb/enhanced (style, no value)

This is an abbreviation for setting `skin=enhanced`.

```
\begin{tcbraster}[enhanced,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



```
% \usetikzlibrary{shadings}          % preamble
\tcbset{skin=enhanced,fonttitle=\bfseries,
  frame style={upper left=blue,upper right=red,lower left=yellow,lower right=green},
  interior style={white,opacity=0.5},
  segmentation style={black,solid,opacity=0.2,line width=1pt}}

\begin{tcolorbox}[title=Nice box in rainbow colors]
  With the \enquote{enhanced} skin, it is quite easy to produce fancy looking effects.
  \tcblower
  Note that this is still a \texttt{tcolorbox}.
\end{tcolorbox}
```

Nice box in rainbow colors

With the "enhanced" skin, it is quite easy to produce fancy looking effects.

Note that this is still a `tcolorbox`.

```
% \usetikzlibrary{decorations.pathmorphing} % preamble
\tcbset{skin=enhanced,fonttitle=\bfseries,boxrule=1mm,
  frame style={draw=FireBrick,fill=Salmon},drop fuzzy shadow,
  interior style={draw=FireBrick,top color=Salmon!10,bottom color=Salmon!20},
  segmentation style={draw=FireBrick,solid,decorate,
        decoration={coil,aspect=0,segment length=10.1mm}}}

\begin{tcblisting}{title=A listing box with shadow and some specials}
Of course, skins can be used for listings also.
\begin{equation}
  \int\limits_1^2 \frac{1}{x}~dx = \ln(2).
\end{equation}
\end{tcblisting}
```

A listing box with shadow and some specials

```
Of course, skins can be used for listings also.
\begin{equation}
  \int\limits_1^2 \frac{1}{x}~dx = \ln(2).
\end{equation}
```

Of course, skins can be used for listings also.

$$\int\limits_1^2 \frac{1}{x}~dx = \ln(2). \tag{2}$$

/tcb/enhanced standard (style, no value)

For unbreakable boxes, this is identical to using /tcb/enhanced→ P. 211. But, for breakable boxes, the *break sequence* is identical to the standard→ P. 209 skin, see Section 18.8 from page 392.

/tcb/blank (style, initially unset)

This style relies on the skin enhanced→ P. 211. All drawing operations are hidden and all margins are set to 0pt. See /tcb/blanker→ P. 243 for switching off the drawing engines.

```
\begin{tcolorbox}[blank,watermark text=A blank box]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

A blank box

\tcbline

Sometimes, a line is only a line. With \tcblower → P. 12 you separate the box content into two functional units. \tcbline draws only a line which looks like the segmentation line between upper and lower part. Furthermore, you can use \tcbline more than just once. \tcbline always uses the path drawing engine. Therefore, the /tcb/segmentation style → P. 155 can be applied.

```
\tcbset{enhanced,colframe=blue!50!black,colback=white}

\begin{tcolorbox}[colupper=red!50!black,collower=green!50!black]
\lipsum[1]
\tcbline
\lipsum[2]
\tcblower
\lipsum[3]
\tcbline
\lipsum[4]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

\tcbline*

Equivalent to \tcbline, but in a breakable box, \tcbline* is removed if at a page/box break. Also, it is removed at the end of a box.

/tcb/skin=enhancedfirst (skin)

This is a flavor of enhanced→ P. 211 which is used as a *first* part in a break sequence for enhanced→ P. 211. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "enhancedfirst"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	pathfirst
/tcb/interior titled engine→ P. 138:	pathfirst
/tcb/interior engine→ P. 139:	pathfirst
/tcb/segmentation engine→ P. 139:	path
/tcb/title engine→ P. 139:	pathfirst

```
\begin{tcbraster}[skin=enhancedfirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhancedmiddle (skin)

This is a flavor of enhanced→ P. 211 which is used as a *middle* part in a break sequence for enhanced→ P. 211. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "enhancedmiddle"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	pathmiddle
/tcb/interior titled engine→ P. 138:	pathmiddle
/tcb/interior engine→ P. 139:	pathmiddle
/tcb/segmentation engine→ P. 139:	path
/tcb/title engine→ P. 139:	pathmiddle

```
\begin{tcbraster}[skin=enhancedmiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhancedlast (skin)

This is a flavor of enhanced→ P. 211 which is used as a *last* part in a break sequence for enhanced→ P. 211. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "enhancedlast"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	pathlast
/tcb/interior titled engine→ P. 138:	pathlast
/tcb/interior engine→ P. 139:	pathlast
/tcb/segmentation engine→ P. 139:	path
/tcb/title engine→ P. 139:	pathlast

```
\begin{tcbraster}[skin=enhancedlast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhanced jigsaw (skin)

This is the jigsaw variant of skin enhanced[→P. 211]. It differs by its frame engine, see Section 10.11 on page 205.

Environment and engines for the skin "enhanced jigsaw"

/tcb/graphical environment[→P. 138]:	tikzpicture
/tcb/frame engine[→P. 138]:	pathjigsaw
/tcb/interior titled engine[→P. 138]:	path
/tcb/interior engine[→P. 139]:	path
/tcb/segmentation engine[→P. 139]:	path
/tcb/title engine[→P. 139]:	path

/tcb/enhanced jigsaw (style, no value)

This is an abbreviation for setting skin=enhanced jigsaw.

```
\begin{tcbraster}[enhanced jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



N 2017-07-01 **/tcb/enhanced standard jigsaw** (style, no value)

For unbreakable boxes, this is identical to using /tcb/enhanced jigsaw. But, for breakable boxes, the *break sequence* is identical to the standard jigsaw[→P. 210] skin, see Section 18.8 from page 392.

/tcb/skin=enhancedfirst jigsaw (skin)

This is the jigsaw variant of skin enhancedfirst→P. 215. It differs by its frame engine, see Section 10.11 on page 205.

Environment and engines for the skin "enhancedfirst jigsaw"

/tcb/graphical environment→P. 138:	tikzpicture
/tcb/frame engine→P. 138:	pathfirstjigsaw
/tcb/interior titled engine→P. 138:	pathfirst
/tcb/interior engine→P. 139:	pathfirst
/tcb/segmentation engine→P. 139:	path
/tcb/title engine→P. 139:	pathfirst

```
\begin{tcbraster}[skin=enhancedfirst jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



/tcb/skin=enhancedmiddle jigsaw (skin)

This is the jigsaw variant of skin enhancedmiddle→ P. 216. It differs by its frame engine, see Section 10.11 on page 205.

Environment and engines for the skin "enhancedmiddle jigsaw"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	pathmiddlejigsaw
/tcb/interior titled engine→ P. 138:	pathmiddle
/tcb/interior engine→ P. 139:	pathmiddle
/tcb/segmentation engine→ P. 139:	path
/tcb/title engine→ P. 139:	pathmiddle

```
\begin{tcbraster}[skin=enhancedmiddle jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



/tcb/marker (style, no value)

This styles relies on the skin enhancedmiddle jigsaw. It is intended to be used as an optical marker like a highlighter pen.

```
\begin{tcolorbox}[marker]
\lipsum[2]
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This examples demonstrates the creation of several *text marker* environments based on enhancedmiddle → P. 216.

```
\tcbset{textmarker/.style={%
    skin=enhancedmiddle jigsaw,breakable,parbox=false,
    boxrule=0mm,leftrule=5mm,rightrule=5mm,boxsep=0mm,arc=0mm,outer arc=0mm,
    left=3mm,right=3mm,top=1mm,bottom=1mm,toptitle=1mm,bottomtitle=1mm,oversize}}

\newtcolorbox{yellow}{textmarker,colback=yellow!5!white,colframe=yellow}
\newtcolorbox{orange}{textmarker,colback=DarkOrange!5!white,
                      colframe=DarkOrange!75!yellow}
\newtcolorbox{red}{textmarker,colback=red!5!white,colframe=red}
\newtcolorbox{blue}{textmarker,colback=DeepSkyBlue!5!white,colframe=DeepSkyBlue}
\newtcolorbox{green}{textmarker,colback=Chartreuse!5!white,colframe=Chartreuse}
\newtcolorbox{rainbow}{textmarker,interior hidden,
  frame style={top color=blue,bottom color=red,middle color=green}}

\begin{yellow}
  \lipsum[1-3]
\end{yellow}

\begin{orange}
  \lipsum[4]
\end{orange}

\begin{red}
  \lipsum[5]
\end{red}

\begin{green}
  \lipsum[6]
\end{green}

\begin{blue}
  \lipsum[7]
\end{blue}

\begin{rainbow}
  \lipsum[8]
\end{rainbow}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique,

libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

/tcb/skin=enhancedlast jigsaw (skin)

This is the jigsaw variant of skin enhancedlast→P. 217. It differs by its frame engine, see Section 10.11 on page 205.

Environment and engines for the skin "enhancedlast"

/tcb/graphical environment→P. 138:	tikzpicture
/tcb/frame engine→P. 138:	pathlastjigsaw
/tcb/interior titled engine→P. 138:	pathlast
/tcb/interior engine→P. 139:	pathlast
/tcb/segmentation engine→P. 139:	path
/tcb/title engine→P. 139:	pathlast

```
\begin{tcbraster}[skin=enhancedlast jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



10.15 Skin Family "bicolor"

/tcb/skin=bicolor (skin)

This skin is quite similar to the standard[→P. 209] and enhanced[→P. 211] skin. But instead of a segmentation line, the optional lower part of the box is filled with a different color or drawn with a different style.

Environment and engines for the skin "bicolor"

/tcb/graphical environment[→P. 138]:	tikzpicture
/tcb/frame engine[→P. 138]:	path
/tcb/interior titled engine[→P. 138]:	*special*
/tcb/interior engine[→P. 139]:	*special*
/tcb/segmentation engine[→P. 139]:	*special*
/tcb/title engine[→P. 139]:	path

- The most basic usage of this skin is to set the background color of the lower part by /tcb/colbacklower[→P. 225] and all other options like for the standard[→P. 209] skin.

```
\begin{tcolorbox}[skin=bicolor,title=The title,
    colframe=FireBrick!75!black,colback=Salmon!50!white,colbacklower=Salmon]
  The upper part.
  \tcblower
  The lower part.
\end{tcolorbox}
```

- The more advanced usage of this skin is to apply the /tcb/frame style[→P. 152] and the /tcb/interior style[→P. 153] like for the enhanced[→P. 211] skin. Also, the /tcb/segmentation style[→P. 155] can be used, but it is applied to the whole lower part.

```
\begin{tcolorbox}[skin=bicolor,title=The title,
    frame style={top color=FireBrick,
                 bottom color=FireBrick!15!white,draw=black},
    interior style={left color=Salmon,right color=Salmon!50!white},
    segmentation style={right color=Salmon,left color=Salmon!50!white}]
  The upper part.
  \tcblower
  The lower part.
\end{tcolorbox}
```

/tcb/bicolor (style, no value)

This is an abbreviation for setting `skin=bicolor`.

```
\begin{tcbraster}[bicolor,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/colbacklower=⟨*color*⟩ (no default, initially `black!15!white`)

Sets the background ⟨*color*⟩ of the lower part. It depends on the skin, if this value is used.

```
\tcbset{gitexample/.style={listing and comment,comment={#1},
  skin=bicolor,boxrule=1mm,fonttitle=\bfseries,coltitle=black,
  frame style={draw=black,left color=Gold,right color=Goldenrod!50!Gold},
  colback=black,colbacklower=Goldenrod!75!Gold,
  colupper=white,collower=black,
  listing options={language={bash},aboveskip=0pt,belowskip=0pt,nolol,
  basicstyle=\ttfamily\bfseries,extendedchars=true}}}

\begin{tcblisting}{title={Snapshot of the staging area},
  gitexample={The option `-a' automatically stages all tracked and modified
              files before the commit.\par
              This can be combined with the message option `-m'
              as seen in the third line.}}
git commit
git commit -a
git commit -am `changes to my example'
\end{tcblisting}
```

Snapshot of the staging area

```
git commit
git commit -a
git commit -am `changes to my example'
```

The option '-a' automatically stages all tracked and modified files before the commit.
This can be combined with the message option '-m' as seen in the third line.

/tcb/skin=bicolorfirst (skin)

This is a flavor of bicolor→ P. 224 which is used as a *first* part in a break sequence for bicolor→ P. 224. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "bicolorfirst"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	pathfirst
/tcb/interior titled engine→ P. 138:	*special*
/tcb/interior engine→ P. 139:	*special*
/tcb/segmentation engine→ P. 139:	*special*
/tcb/title engine→ P. 139:	pathfirst

```
\begin{tcbraster}[skin=bicolorfirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=bicolormiddle (skin)

This is a flavor of bicolor→ P. 224 which is used as a *middle* part in a break sequence for bicolor→ P. 224. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "bicolormiddle"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	pathmiddle
/tcb/interior titled engine→ P. 138:	*special*
/tcb/interior engine→ P. 139:	*special*
/tcb/segmentation engine→ P. 139:	*special*
/tcb/title engine→ P. 139:	pathmiddle

```
\begin{tcbraster}[skin=bicolormiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



/tcb/skin=bicolorlast (skin)

This is a flavor of bicolor→ P. 224 which is used as a *last* part in a break sequence for bicolor→ P. 224. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "bicolorlast"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	pathlast
/tcb/interior titled engine→ P. 138:	*special*
/tcb/interior engine→ P. 139:	*special*
/tcb/segmentation engine→ P. 139:	*special*
/tcb/title engine→ P. 139:	pathlast

```
\begin{tcbraster}[skin=bicolorlast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



10.16 Skin Family "tile"

N 2016-02-25 **/tcb/skin=tile** (skin)

This skin is a variant of skin bicolor→P. 224. Especially, the optional lower part of the box is colored by /tcb/colbacklower→P. 225. The main difference to bicolor→P. 224 is that tile has no frame.

Environment and engines for the skin "tile"

/tcb/graphical environment→P. 138:	tikzpicture
/tcb/frame engine→P. 138:	empty
/tcb/interior titled engine→P. 138:	*special*
/tcb/interior engine→P. 139:	*special*
/tcb/segmentation engine→P. 139:	*special*
/tcb/title engine→P. 139:	path

N 2016-02-25 **/tcb/tile** (style, no value)

This is an abbreviation for setting skin=tile.

! It also changes the geometry and some style options.

```
\begin{tcbraster}[tile,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

N 2016-02-25 **/tcb/skin=tilefirst** (skin)

This is a flavor of tile [→ P. 229] which is used as a *first* part in a break sequence for tile [→ P. 229]. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "tilefirst"

/tcb/graphical environment [→ P. 138]:	tikzpicture
/tcb/frame engine [→ P. 138]:	empty
/tcb/interior titled engine [→ P. 138]:	*special*
/tcb/interior engine [→ P. 139]:	*special*
/tcb/segmentation engine [→ P. 139]:	*special*
/tcb/title engine [→ P. 139]:	pathfirst

```
\begin{tcbraster}[skin=tilefirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm,boxrule=0pt]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

N 2016-02-25 **/tcb/skin=tilemiddle** (skin)

This is a flavor of tile[→P. 229] which is used as a *middle* part in a break sequence for tile[→P. 229]. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "tilemiddle"

/tcb/graphical environment[→P. 138]:	tikzpicture
/tcb/frame engine[→P. 138]:	empty
/tcb/interior titled engine[→P. 138]:	*special*
/tcb/interior engine[→P. 139]:	*special*
/tcb/segmentation engine[→P. 139]:	*special*
/tcb/title engine[→P. 139]:	pathmiddle

```
\begin{tcbraster}[skin=tilemiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm,boxrule=0pt]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

N 2016-02-25 **/tcb/skin=tilelast** (skin)

This is a flavor of tile→ P. 229 which is used as a *last* part in a break sequence for tile→ P. 229. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "tilelast"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	empty
/tcb/interior titled engine→ P. 138:	*special*
/tcb/interior engine→ P. 139:	*special*
/tcb/segmentation engine→ P. 139:	*special*
/tcb/title engine→ P. 139:	pathlast

```
\begin{tcbraster}[skin=tilelast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm,boxrule=0pt]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.17 Skin Family "beamer"

/tcb/skin=beamer (skin)

This skin resembles boxes known from the `beamer` class and therefore is called "beamer". It uses the normal colors from the core package but shades them a little bit. To use this skin, the `tikz` library `shadings` has to be included in the preamble by:

```
\usetikzlibrary{shadings}
```

Environment and engines for the skin "beamer"

/tcb/graphical environment → P. 138:	`tikzpicture`
/tcb/frame engine → P. 138:	`path`
/tcb/interior titled engine → P. 138:	*special*
/tcb/interior engine → P. 139:	*special*
/tcb/segmentation engine → P. 139:	*special*
/tcb/title engine → P. 139:	`path`

/tcb/beamer (style, no value)

This is an abbreviation for setting `skin=beamer`.

> ! It also changes the geometry and some style options.

```
\begin{tcbraster}[beamer,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



```
\begin{tcolorbox}[beamer,colback=Salmon!50!white,colframe=FireBrick!75!black,
  adjusted title=A colored box with the \enquote{beamer} skin]
This box looks like a box provided by the \texttt{beamer} class.
\end{tcolorbox}
```

A colored box with the "beamer" skin

This box looks like a box provided by the `beamer` class.

```
\begin{tcolorbox}[beamer,colframe=blue,colback=black,
  watermark graphics=lichtspiel.jpg,
  coltext=white,watermark opacity=0.75,watermark stretch=1.0,
  title=Beamer Box with background picture]
\lipsum[1]
\end{tcolorbox}
```

Beamer Box with background picture

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
\newtcolorbox{myblock}[2][]{%
  beamer,breakable,colback=LightBlue,colframe=DarkBlue,#1,title=#2}%

\begin{myblock}{Beamerish \texttt{block}: \texttt{myblock}}
\lipsum[1]
\end{myblock}
```

Beamerish `block`: `myblock`

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

/tcb/skin=beamerfirst (skin)

This is a flavor of beamer[→ P. 233] which is used as a *first* part in a break sequence for beamer[→ P. 233]. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "beamerfirst"

/tcb/graphical environment[→ P. 138]:	tikzpicture
/tcb/frame engine[→ P. 138]:	pathfirst
/tcb/interior titled engine[→ P. 138]:	*special*
/tcb/interior engine[→ P. 139]:	*special*
/tcb/segmentation engine[→ P. 139]:	*special*
/tcb/title engine[→ P. 139]:	pathfirst

```
\begin{tcbraster}[beamer,skin=beamerfirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=beamermiddle (skin)

This is a flavor of beamer→ P. 233 which is used as a *middle* part in a break sequence for beamer→ P. 233. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "beamermiddle"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	pathmiddle
/tcb/interior titled engine→ P. 138:	*special*
/tcb/interior engine→ P. 139:	*special*
/tcb/segmentation engine→ P. 139:	*special*
/tcb/title engine→ P. 139:	pathmiddle

```
\begin{tcbraster}[beamer,skin=beamermiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=beamerlast (skin)

This is a flavor of beamer→ P. 233 which is used as a *last* part in a break sequence for beamer→ P. 233. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "beamerlast"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	pathlast
/tcb/interior titled engine→ P. 138:	*special*
/tcb/interior engine→ P. 139:	*special*
/tcb/segmentation engine→ P. 139:	*special*
/tcb/title engine→ P. 139:	pathlast

```
\begin{tcbraster}[beamer,skin=beamerlast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



10.18 Skin Family "widget"

/tcb/skin=widget (skin)

This skin uses the normal colors from the core package but shades them a little bit. To use this skin, the `tikz` library `shadings` has to be included in the preamble by:

```
\usetikzlibrary{shadings}
```

The appearance of the skin can be controlled by /tcb/frame style→P. 152, /tcb/interior style→P. 153, and /tcb/segmentation style→P. 155, if needed.

Environment and engines for the skin "widget"

/tcb/graphical environment→P. 138:	tikzpicture
/tcb/frame engine→P. 138:	path
/tcb/interior titled engine→P. 138:	path
/tcb/interior engine→P. 139:	path
/tcb/segmentation engine→P. 139:	*special*
/tcb/title engine→P. 139:	*special*

/tcb/widget (style, no value)

This is an abbreviation for setting `skin=widget`.

> **!** It also changes the geometry and some style options.

```
\begin{tcbraster}[widget,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

```
\begin{tcolorbox}[widget,colback=Salmon!50!white,colframe=FireBrick!75!black,
  adjusted title=A colored box with the \enquote{widget} skin]
This is my content.
\end{tcolorbox}
```

A colored box with the "widget" skin

This is my content.

/tcb/skin=widgetfirst (skin)

This is a flavor of widget→P. 238 which is used as a *first* part in a break sequence for widget→P. 238. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "widgetfirst"

/tcb/graphical environment→P. 138:	tikzpicture
/tcb/frame engine→P. 138:	pathfirst
/tcb/interior titled engine→P. 138:	pathfirst
/tcb/interior engine→P. 139:	pathfirst
/tcb/segmentation engine→P. 139:	*special*
/tcb/title engine→P. 139:	*special*

```
\begin{tcbraster}[widget,skin=widgetfirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=widgetmiddle (skin)

This is a flavor of widget→P. 238 which is used as a *middle* part in a break sequence for widget→P. 238. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "widgetmiddle"

/tcb/graphical environment→P. 138:	tikzpicture
/tcb/frame engine→P. 138:	pathmiddle
/tcb/interior titled engine→P. 138:	pathmiddle
/tcb/interior engine→P. 139:	pathmiddle
/tcb/segmentation engine→P. 139:	*special*
/tcb/title engine→P. 139:	*special*

```
\begin{tcbraster}[widget,skin=widgetmiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=widgetlast (skin)

This is a flavor of widget→P. 238 which is used as a *last* part in a break sequence for widget→P. 238. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "widgetlast"

/tcb/graphical environment→P. 138:	tikzpicture
/tcb/frame engine→P. 138:	pathlast
/tcb/interior titled engine→P. 138:	pathlast
/tcb/interior engine→P. 139:	pathlast
/tcb/segmentation engine→P. 139:	*special*
/tcb/title engine→P. 139:	*special*

```
\begin{tcbraster}[widget,skin=widgetlast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.19 Skin Family "empty"

/tcb/skin=empty (skin)

This skin sets all engines to `empty`, i. e. nothing is drawn at all. Therefore, this skin is a good starting point to create a complete new style by yourself.

Environment and engines for the skin "empty"

/tcb/graphical environment^{→ P. 138}:	tikzpicture
/tcb/frame engine^{→ P. 138}:	empty
/tcb/interior titled engine^{→ P. 138}:	empty
/tcb/interior engine^{→ P. 139}:	empty
/tcb/segmentation engine^{→ P. 139}:	empty
/tcb/title engine^{→ P. 139}:	empty

/tcb/empty (style, no value)

This is an abbreviation for setting `skin=empty`.

```
\begin{tcbraster}[empty,raster equal height,raster columns=4,
    coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/blanker (style, initially unset)

This style relies on the skin empty → P. 242. All engines are set to empty and all margins are set to 0pt. In contrast to /tcb/blank → P. 213, the graphical paths are not constructed with exception of the geometry nodes.

```
\begin{tcolorbox}[blanker,watermark text=A blank box]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

A blank box

```
% \tcbuselibrary{fitting}
\newtcboxfit{\mybox}[1]{blanker,width=4cm,height=7cm,top=4pt,
  watermark text=#1}

\begin{tabular}{|c|c|c|}\hline
A & B & C\\\hline
\mybox{A}{\lipsum[1]} & \mybox{B}{\lipsum[2]} & \mybox{C}{\lipsum[3]}\\\hline
\end{tabular}
```

A	B	C
Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.	Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.	Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

A blank box

/tcb/blankest (style, initially unset)

This style extends /tcb/blanker → P. 243. All engines are set to empty and all margins are set to 0pt. In contrast to /tcb/blanker → P. 243, also title, shadow, underlay, overlay, finish and borderline are removed.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,raster equal height,
    title=Box \thetcbrasternum,
    enhanced,size=small,colframe=red!50!black,colback=red!10!white,
    coltitle=yellow!85!black,
    drop fuzzy shadow,watermark text={Box \thetcbrasternum},
    borderline={.25mm}{-0.5mm}{green!40!black},
    finish={\begin{tcbclipframe}\draw[blue,opacity=0.1,line width=1cm]
      (frame.south west) -- (frame.north east);\end{tcbclipframe}},
    ]
  \begin{tcolorbox}\lipsum[4]\end{tcolorbox}
  \begin{tcolorbox}[blanker]\lipsum[4]\end{tcolorbox}
  \begin{tcolorbox}[blankest]\lipsum[4]\end{tcolorbox}
\end{tcbraster}
```

Box 1

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Box 2

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

/tcb/skin=emptyfirst (skin)

This is a flavor of empty→ P. 242 which is used as a *first* part in a break sequence for empty→ P. 242. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "emptyfirst"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	empty
/tcb/interior titled engine→ P. 138:	empty
/tcb/interior engine→ P. 139:	empty
/tcb/segmentation engine→ P. 139:	empty
/tcb/title engine→ P. 139:	empty

```
\begin{tcbraster}[empty,skin=emptyfirst,raster equal height,raster columns=4,
    coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=emptymiddle (skin)

This is a flavor of empty→ P. 242 which is used as a *middle* part in a break sequence for empty→ P. 242. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "emptymiddle"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	empty
/tcb/interior titled engine→ P. 138:	empty
/tcb/interior engine→ P. 139:	empty
/tcb/segmentation engine→ P. 139:	empty
/tcb/title engine→ P. 139:	empty

```
\begin{tcbraster}[empty,skin=emptymiddle,raster equal height,raster columns=4,
    coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=emptylast (skin)

This is a flavor of empty→ P. 242 which is used as a *last* part in a break sequence for empty→ P. 242. Nevertheless, this skin can be applied independently.

Environment and engines for the skin "emptylast"

/tcb/graphical environment→ P. 138:	tikzpicture
/tcb/frame engine→ P. 138:	empty
/tcb/interior titled engine→ P. 138:	empty
/tcb/interior engine→ P. 139:	empty
/tcb/segmentation engine→ P. 139:	empty
/tcb/title engine→ P. 139:	empty

```
\begin{tcbraster}[empty,skin=emptylast,raster equal height,raster columns=4,
    coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

This example demonstrates a breakable customized box. Here, we define an environment `freebox`. The first application of `freebox` produces an unbroken `tcolorbox`. The box is drawn by the code given by `/tcb/frame code` →P. 141 and `/tcb/interior code` →P. 142. The second application of `freebox` is broken into several parts which are drawn by the codes given by `/tcb/skin first is subskin of` →P. 144, `/tcb/skin middle is subskin of` →P. 144, and `/tcb/skin last is subskin of` →P. 144.

```
% Preamble:
%\usepackage{tikz,lipsum}
%\tcbuselibrary{skins,breakable}
\tikzset{coltria/.style={fill=red!15!white}}

\newtcolorbox{freebox}[1][]{empty,
  breakable,height fixed for=first and middle,
  leftrule=5mm,left=2mm,
  frame style={fill,top color=red!75!black,bottom color=red!75!black,middle color=red},
  colback=yellow!50!white,
  watermark color=red!50!yellow!75!white,
  watermark text on=unbroken is unbroken box,
  watermark text on=first is first part,
  watermark text on=middle is middle part,
  watermark text on=last is last part,
  % code for unbroken boxes:
  frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
    --([xshift=-5mm]frame.north east)--([yshift=-5mm]frame.north east)
    --([yshift=5mm]frame.south east)--([xshift=-5mm]frame.south east)--cycle; },
  interior code={\path[tcb fill interior] (interior.south west)--(interior.north west)
    --([xshift=-4.8mm]interior.north east)--([yshift=-4.8mm]interior.north east)
    --([yshift=4.8mm]interior.south east)--([xshift=-4.8mm]interior.south east)
    --cycle; },
  % code for the first part of a break sequence:
  skin first is subskin of={emptyfirst}{%
    frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
      --([xshift=-5mm]frame.north east)--([yshift=-5mm]frame.north east)
      --(frame.south east)--cycle;
      \path[coltria] ([xshift=2.5mm,yshift=1mm]frame.south west) -- +(120:2mm)
      -- +(60:2mm)-- cycle; },
    interior code={\path[tcb fill interior] (interior.south west|-frame.south)
      --(interior.north west)--([xshift=-4.8mm]interior.north east)
      --([yshift=-4.8mm]interior.north east)--(interior.south east|-frame.south)
      --cycle; },
  },%
  % code for the middle part of a break sequence:
  skin middle is subskin of={emptymiddle}{%
    frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
      --(frame.north east)--(frame.south east)--cycle;
      \path[coltria] ([xshift=2.5mm,yshift=-1mm]frame.north west) -- +(240:2mm)
        -- +(300:2mm) -- cycle;
      \path[coltria] ([xshift=2.5mm,yshift=1mm]frame.south west) -- +(120:2mm)
        -- +(60:2mm) -- cycle;
      },
    interior code={\path[tcb fill interior] (interior.south west|-frame.south)
      --(interior.north west|-frame.north)--(interior.north east|-frame.north)
      --(interior.south east|-frame.south)--cycle; },
    },
  % code for the last part of a break sequence:
  skin last is subskin of={emptylast}{%
    frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
      --(frame.north east)--([yshift=5mm]frame.south east)
      --([xshift=-5mm]frame.south east)--cycle;
      \path[coltria] ([xshift=2.5mm,yshift=-1mm]frame.north west) -- +(240:2mm)
      -- +(300:2mm) -- cycle;
```

```
      },
    interior code={\path[tcb fill interior] (interior.south west)
      --(interior.north west|-frame.north)--(interior.north east|-frame.north)
      --([yshift=4.8mm]interior.south east)--([xshift=-4.8mm]interior.south east)
      --cycle; },
    },
  #1}

\begin{freebox}
\lipsum[1]
\end{freebox}

\begin{freebox}
\lipsum[1-12]
\end{freebox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

unbroken box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel

first part

magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

middle part

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetuer a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetuer. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetuer odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetuer eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetuer tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

last part

10.20 Skin "spartan"

/tcb/skin=spartan (skin)

This skin is quite ... spartan. It supports no rounded corners, no overlays, no shadows, no borderlines, and no finishes. The only exception are underlays. One cannot do very fancy things with this skin, but it compiles very fast. Therefore, the `spartan` skin is used for the draft mode, see Section 10.12 on page 207. Nevertheless, it can be used as a normal skin.

Environment and engines for the skin "spartan"

/tcb/graphical environment → P. 138:	tikzpicture
/tcb/frame engine → P. 138:	spartan
/tcb/interior titled engine → P. 138:	spartan
/tcb/interior engine → P. 139:	spartan
/tcb/segmentation engine → P. 139:	spartan
/tcb/title engine → P. 139:	spartan

/tcb/spartan (style, no value)

This is an abbreviation for setting `skin=spartan`.

```
\begin{tcbraster}[spartan,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.21 Skin “draft”

/tcb/skin=draft (skin)

This skin is intended to be used while drafting new geometric settings for a `tcolorbox`.

Environment and engines for the skin “draft”

/tcb/graphical environment^{→ P. 138}:	`tikzpicture`
/tcb/frame engine^{→ P. 138}:	*special*
/tcb/interior titled engine^{→ P. 138}:	*special*
/tcb/interior engine^{→ P. 139}:	*special*
/tcb/segmentation engine^{→ P. 139}:	`path`
/tcb/title engine^{→ P. 139}:	`path`

/tcb/draft (style, no value)

This is an abbreviation for setting `skin=draft`.

```
\begin{tcbraster}[draft,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



```
\vspace*{3mm}
\begin{tcolorbox}[draft,title=A colored box with the \enquote{draft} skin]
\lipsum[1-3]
\tcblower
\lipsum[4-6]
\end{tcolorbox}
```

frame: w=423.94617pt, h=506.20157pt

A colored box with the "draft" skin title: w=392.64822pt, h=6.2pt

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare metus odio a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

upper: w=392.64822pt, h=249.95pt

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

lower: w=392.64822pt, h=205.95pt

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

interior: w=421.10092pt, h=490.04318pt

10.22 Skin Family "freelance"

> **!** This skin family "freelance" is deprecated with `tcolorbox` 3.00. It is not longer needed, because `/tcb/frame code`[→P. 141], `/tcb/interior code`[→P. 142], `/tcb/interior titled code`[→P. 141], and `/tcb/title code`[→P. 143] can be applied to every skin now. In this sense, everything has become *freelance* now.
> For users of `/tcb/freelance`: Old code should continue to work. There may be exceptions for breakable freelance boxes under certain circumstances. For new code, use `/tcb/empty`[→P. 242] or `/tcb/enhanced`[→P. 211] where you would have used `/tcb/freelance` before.

`/tcb/skin=freelance` (skin)

This skin gives full freedom for the appearance of the `tcolorbox`. All drawing engines are set to type `freelance`; they use the `tikz` package and compute the `/tcb/geometry nodes`[→P. 140].

Environment and engines for the skin "`freelance`"

`/tcb/graphical environment`[→P. 138]:	`tikzpicture`
`/tcb/frame engine`[→P. 138]:	`freelance`
`/tcb/interior titled engine`[→P. 138]:	`freelance`
`/tcb/interior engine`[→P. 139]:	`freelance`
`/tcb/segmentation engine`[→P. 139]:	`freelance`
`/tcb/title engine`[→P. 139]:	`freelance`

`/tcb/freelance` (style, no value)

This is an abbreviation for setting `skin=freelance`.

`/tcb/skin=freelancefirst` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 18.8 on page 392.

`/tcb/skin=freelancemiddle` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 18.8 on page 392.

`/tcb/skin=freelancelast` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 18.8 on page 392.

`/tcb/extend freelance=`⟨*options*⟩ (no default, initially empty)

The ⟨*options*⟩ are added to the skin definition of `freelance`.

`/tcb/extend freelancefirst=`⟨*options*⟩ (no default, initially empty)

The ⟨*options*⟩ are added to the skin definition of `freelancefirst` which is used as first part of the break sequence of `freelance`. See `/tcb/skin first is subskin of`[→P. 144] for a substitute of this key.

`/tcb/extend freelancemiddle=`⟨*options*⟩ (no default, initially empty)

The ⟨*options*⟩ are added to the skin definition of `freelancemiddle` which is used as middle part of the break sequence of `freelance`. See `/tcb/skin middle is subskin of`[→P. 144] for a substitute of this key.

`/tcb/extend freelancelast=`⟨*options*⟩ (no default, initially empty)

The ⟨*options*⟩ are added to the skin definition of `freelancelast` which is used as last part of the break sequence of `freelance`. See `/tcb/skin last is subskin of`[→P. 144] for a substitute of this key.

11 Inclusion of Boxed Image Files

The LIB skins library adds some commands to conveniently include boxed image files. For the following macros and options, the LIB skins library has to be loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

See Section 10 on page 152 for the documentation of all other options of the LIB skins library.

11.1 Macros

N 2014-11-14
U 2016-07-13

\tcbincludegraphics[⟨*options*⟩]{⟨*file name*⟩}

In principle, this macro includes an image file denoted by ⟨*file name*⟩ using the standard `\includegraphics` and puts it into a `tcolorbox`[→ P. 12]. The ⟨*options*⟩ are `tcolorbox` keys to set up the colored box. Use `/tcb/graphics options`[→ P. 259] to specify options for the underlying `\includegraphics`. Some `tcolorbox` option keys are automatically set, namely `/tcb/enhanced`[→ P. 211] and options to center the image inside the box.

The sizing of the included image is done depending on the following:

- If a `/tcb/width`[→ P. 34] is specified, but no fixed `/tcb/height`[→ P. 53], the image is sized to fill the inner width of the box. The height of the box adapts to the image.
- If a fixed `/tcb/height`[→ P. 53] is specified, the image is sized to fill the fixed inner area of the box.
- If the `/tcb/capture`[→ P. 97] mode `/tcb/hbox`[→ P. 97] is specified, the image is sized according to given `\includegraphics` options only. The box adapts to the image.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,raster force size=false,size=fbox,
    colframe=red!50!black,colback=red!20!black,
    fonttitle=\bfseries,center title,drop fuzzy shadow]
  \tcbincludegraphics[title=Normal]{goldshade.png}
  \tcbincludegraphics[title=Fixed height,height=3cm]{goldshade.png}
  \tcbincludegraphics[title=hbox mode,hbox,graphics options={width=3cm}]
    {goldshade.png}
\end{tcbraster}
```



The auxiliary macro **\imagename** may be used inside \tcbincludegraphics → P. 256 to display the name of the file. **\imagename** is already partially detokenized and is allowed to contain special characters like the underscore. Note that an appropriate font is required to display such characters.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[size=fbox,
    colframe=red!50!black,colback=red!20!black,
    fonttitle=\bfseries\ttfamily,center title,drop fuzzy shadow]
  \tcbincludegraphics[title=\imagename]{goldshade.png}
  \tcbincludegraphics[finish={
    \node[fill=white,fill opacity=0.5,text opacity=1]
    at (frame.center) {\bfseries\ttfamily\imagename};}]{blueshade.png}
\end{tcbraster}
```

N 2014-11-14 **\tcbincludepdf**[⟨*options*⟩]{⟨*file name*⟩}

This is a generalized version of \tcbincludegraphics → P. 256 which allows to include a complete PDF file denoted by ⟨*file name*⟩. Every page is boxed into an own tcolorbox → P. 12 customized by the given ⟨*options*⟩. It is reasonable to put such a series of boxes inside a tcbraster → P. 290 for alignment.

Use /tcb/graphics pages → P. 259 to use a selection of pages instead of using the whole file. The auxiliary macro **\imagepage** may be used inside \tcbincludepdf to display the current page number.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,colframe=blue,colback=white,
  colbacktitle=blue!50!white,fonttitle=\small\bfseries\ttfamily,
  left=0pt,right=0pt,top=0pt,bottom=0pt,boxsep=0pt,boxrule=0.6pt,
  toptitle=1mm,bottomtitle=1mm,drop lifted shadow,center title,
  graphics pages={1,...,6},title={\imagename\ [\imagepage]}]
\tcbincludepdf{tcolorbox-example.pdf}
\end{tcbraster}
```

tcolorbox-example.pdf [1]



tcolorbox-example.pdf [2]



tcolorbox-example.pdf [3]



tcolorbox-example.pdf [4]



tcolorbox-example.pdf [5]



tcolorbox-example.pdf [6]



11.2 Option Keys

N 2014-11-14
U 2018-03-18

/tcb/graphics options=⟨*options*⟩ (no default, initially empty)

Used for \tcbincludegraphics → P. 256 and \tcbincludepdf → P. 258 to specify \includegraphics ⟨*options*⟩.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,size=fbox,raster equal height,
    colframe=red!50!black,colback=red!20!black,drop fuzzy shadow]
  \tcbincludegraphics{goldshade.png}
  \newcommand{\myangle}{angle=20}%
  \tcbincludegraphics[graphics options=\myangle]{goldshade.png}
  \tcbincludegraphics[graphics options={viewport=0cm 0cm 8cm 4cm,clip}]
    {goldshade.png}
\end{tcbraster}
```



N 2014-11-14

/tcb/graphics directory=⟨*directory*⟩ (no default, initially empty)

Used for \tcbincludegraphics → P. 256 and \tcbincludepdf → P. 258 to specify a file system ⟨*directory*⟩ where the image files are located.

```
\tcbset{
  graphics directory={.},
  graphics directory={examples},
  graphics directory={../../pictures},
}
```

> **!** The \graphicspath macro from the graphics package is superior to this option. /tcb/graphics directory may be used especially for \tcbincludepdf → P. 258.

N 2014-11-14

/tcb/graphics pages=⟨*selection*⟩ (no default, initially 1,...,\pdfpages)

Used for \tcbincludepdf → P. 258 to specify a ⟨*selection*⟩ of pages to be included. The largest page number is accessible by \pdfpages. The ⟨*selection*⟩ has to be given using the \foreach syntax of Ti*k*Z.

```
\tcbset{
  graphics pages={1,3,7},
  graphics pages={1,...,10},
  graphics pages={1,3,...,18},
  graphics pages={100,...,\pdfpages},
}
```

N 2018-03-21 **/tcb/graphics orientation=**⟨*orientation*⟩ (no default, initially `as-is`)

Used for `\tcbincludegraphics` → P. 256 and `\tcbincludepdf` → P. 258 to guarantee a certain ⟨*orientation*⟩ of the included image. After all other options for the image are processed, the result is possibly rotated to be in landscape or portrait mode.
Feasible values for ⟨*orientation*⟩ are:

- `as-is`: no rotation of the processed image.
- `landscape`: the processed image is possibly rotated by 90 degrees to ensure that the final width is not smaller than the final height.
- `landscape*`: the processed image is possibly rotated by -90 degrees to ensure that the final width is not smaller than the final height.
- `portrait`: the processed image is possibly rotated by 90 degrees to ensure that the final height is not smaller than the final width.
- `portrait*`: the processed image is possibly rotated by -90 degrees to ensure that the final height is not smaller than the final width.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=6,size=fbox,raster equal height,
    colframe=red!50!black,colback=red!20!black,drop fuzzy shadow]
  \tcbincludegraphics{Basilica_5.png}
  \tcbincludegraphics[graphics orientation=landscape]{Basilica_5.png}
  \tcbincludegraphics[graphics orientation=portrait]{Basilica_5.png}
  \tcbincludegraphics[graphics orientation=portrait*]{Basilica_5.png}
  \tcbincludegraphics[graphics options={viewport=0cm 0cm 2cm 3cm,clip}]
    {goldshade.png}
  \tcbincludegraphics[graphics options={viewport=0cm 0cm 2cm 3cm,clip},
    graphics orientation=landscape]{goldshade.png}
\end{tcbraster}
```



12 TikZ Image and Picture Fill Extensions; Auxiliary Macros

The LIB skins library adds some image and picture fill options to the vast option set of TikZ [22]. These options can be used in any `tikzpicture`. For the following options, the LIB skins library has to be loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

See Section 10 on page 152 for the documentation of all other options of the LIB skins library.

12.1 Fill Plain

/tikz/fill plain image=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is put in the center of the path, but it is not resized to fit into the path area.

```
\begin{tikzpicture}
\path[draw,fill plain image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill plain image*=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is put in the center of the path, but it is not resized to fit into the path area. The ⟨*graphics options*⟩ are given to the underlying `\includegraphics` command.

```
\begin{tikzpicture}
\path[draw,
    fill plain image*={width=2.5cm}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill plain picture=⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is put in the center of the path, but it is not resized to fit into the path area. Note that this is almost identical to the standard `path picture` option.

```
\begin{tikzpicture}
\path[draw,fill plain picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.2 Fill Stretch

/tikz/fill stretch image=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is stretched to fill the path area.

```
\begin{tikzpicture}
\path[fill stretch image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill stretch image*={⟨*graphics options*⟩}{⟨*file name*⟩} (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command. The image is stretched to fill the path area.

```
\begin{tikzpicture}
\path[fill stretch image*=
  {angle=90,origin=c}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill stretch picture=⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is stretched to fill the path area.

```
\begin{tikzpicture}
\path[draw,fill stretch picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.3 Fill Overzoom

/tikz/fill overzoom image=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is zoomed such that the path area fills the image.

```
\begin{tikzpicture}
\path[fill overzoom image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill overzoom image*={⟨*graphics options*⟩}{⟨*file name*⟩} (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command. The image is zoomed such that the path area fills the image.

```
\begin{tikzpicture}
\path[fill overzoom image*=
  {angle=90,origin=c}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill overzoom picture=⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is zoomed such that the path area fills the image.

```
\begin{tikzpicture}
\path[draw,fill overzoom picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.4 Fill Zoom

/tikz/fill zoom image=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill zoom image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill zoom image*={⟨*graphics options*⟩}{⟨*file name*⟩} (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command. The image is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill zoom image*=
  {angle=90,origin=c}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill zoom picture=⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill zoom picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.5 Fill Shrink

/tikz/fill shrink image=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill shrink image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill shrink image*=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command. The image is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,
    fill shrink image*={width=1.5cm}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill shrink picture=⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill shrink picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.6 Fill Tile

/tikz/fill tile image=⟨*file name*⟩ (no default, initially unset)

Fills the current path with a tile pattern using an external image referenced by ⟨*file name*⟩.

```
\begin{tikzpicture}
\path[fill tile image=pink_marble.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```

/tikz/fill tile image*={⟨*graphics options*⟩}{⟨*file name*⟩} (no default, initially unset)

Fills the current path with a tile pattern using an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command.

```
\begin{tikzpicture}
\path[fill tile image*={width=1cm}{pink_marble.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill tile picture=⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with a tile pattern using the given ⟨*graphical code*⟩.

```
\begin{tikzpicture}
\path[draw,fill tile picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill tile picture*={⟨*fraction*⟩}{⟨*graphical code*⟩} (no default, initially unset)

Fills the current path with a tile pattern using the given ⟨*graphical code*⟩. The graphic is resized by ⟨*fraction*⟩.

```
\begin{tikzpicture}
\path[draw,fill tile picture*={0.25}{%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.7 Filling Options

/tikz/fill image opacity=⟨*fraction*⟩ (no default, initially 1.0)

Sets the fill opacity for the image or picture fill options to the given ⟨*fraction*⟩.

```
\begin{tikzpicture}
\path[fill stretch image=goldshade.png] (0,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.75]
  (2,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.5]
  (4,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.25]
  (6,0) circle (1cm);
\path[fill=red] (8,0) circle (1cm);
\end{tikzpicture}
```



/tikz/fill image scale=⟨*fraction*⟩ (no default, initially 1.0)

Stretches, zooms, overzooms or shrinks the image or picture to the given ⟨*fraction*⟩ of the width and height of the current path.

```
\begin{tikzpicture}
\path[draw,fill zoom image=goldshade.png]
  (0,0) rectangle +(2,2);

\path[draw,fill zoom image=goldshade.png,fill image scale=0.75]
  (3,0) rectangle +(2,2);

\path[draw,fill zoom image=goldshade.png,fill image scale=1.5]
  (6,0) rectangle +(2,2);
\end{tikzpicture}
```

U 2018-03-18 **/tikz/fill image options=**⟨*graphics options*⟩ (no default, initially empty)

The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command for the image fill options. This can be just together with /tikz/fill stretch image → P. 262, /tikz/fill overzoom image → P. 263, /tikz/fill zoom image → P. 264, and /tikz/fill tile image → P. 266.

```
\begin{tikzpicture}
\path[fill image options={width=1cm},
  fill tile image=pink_marble.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



Image blending example

```
\begin{tikzpicture}[every node/.style=
  {circle,minimum width=2cm}]
\node[fill stretch image=blueshade.png]
  (A) at (120:3cm) {A};
\node[fill stretch image=goldshade.png]
  (B) at (60:3cm) {B};
\node[
  preaction={fill stretch image=blueshade.png},
  fill stretch image=goldshade.png,
  fill image opacity=0.5] (C) {C};
\path (A) -- node{$+$} (B);
\draw[->,very thick] (A)--(C);
\draw[->,very thick] (B)--(C);
\end{tikzpicture}
```



12.8 Straightening of the Arcs

> **!** This patch is considered as an experimental feature. It changes some of the original Ti*k*Z code. This change may break with future updates of Ti*k*Z.

N 2014-05-05 **\tcbpatcharcangular**

The Ti*k*Z package provides a nice `rounded corners` option to replace all corners by little arcs. `\tcbpatcharcangular` is a patch which straightens the arcs. To say it more prosaic, the little arcs are replaced by little straight lines.

```
\begin{tikzpicture}
  \draw[thick,rounded corners=8pt]
    (0,0) -- (0,2) -- (1,3.25) -- (2,2) -- (2,0)
     -- (0,2) -- (2,2) -- (0,0) -- (2,0);
  \tcbpatcharcangular
  \draw[thick,rounded corners=8pt,xshift=2.5cm]
    (0,0) -- (0,2) -- (1,3.25) -- (2,2) -- (2,0)
     -- (0,2) -- (2,2) -- (0,0) -- (2,0);
\end{tikzpicture}
```



N 2014-05-05 **\tcbpatcharcround**

This macro reverts `\tcbpatcharcangular`, i.e., the patch from `\tcbpatcharcangular` is replaced by the original code.

12.9 Extracting Node Dimensions

The following auxiliary macros are defined by the LIB skins library. They allow to determine the width and height of an arbitrary TikZ node. To be more specific, they determine the east-to-west and the north-to-south dimensions which may be not the maximal dimensions for a non-rectangular node. Note that the following dimensions are measured exactly including the line width of the border line. If a new rectangle or node with the same dimensions and a border is to be drawn, this border width has to be substracted.

N 2014-09-19 **\tcbsettowidthofnode**{⟨*register*⟩}{⟨*node*⟩}

Sets the east-to-west dimension of the given ⟨*node*⟩ to the TEX ⟨*register*⟩.

N 2014-09-19 **\tcbsetmacrotowidthofnode**{⟨*macro*⟩}{⟨*node*⟩}

Defines ⟨*macro*⟩ as the east-to-west dimension of the given ⟨*node*⟩.

N 2014-09-19 **\tcbsettoheightofnode**{⟨*register*⟩}{⟨*node*⟩}

Sets the north-to-south dimension of the given ⟨*node*⟩ to the TEX ⟨*register*⟩.

N 2014-09-19 **\tcbsetmacrotoheightofnode**{⟨*macro*⟩}{⟨*node*⟩}

Defines ⟨*macro*⟩ as the north-to-south dimension of the given ⟨*node*⟩.

```
\begin{tikzpicture}
  \node[align=center,draw=red,fill=yellow] (A) {This is my\\example node};
  \tcbsetmacrotowidthofnode\mywidth{A}
  \tcbsetmacrotoheightofnode\myheight{A}
  \path[fill=blue!25!white]            %  rectangle widthout border
    ([xshift=2mm]A.south east)
    rectangle node{Copy} +(\mywidth,\myheight);
  \node[draw=blue,fill=blue!25!white, % standard border width 0.4pt
    minimum width=\mywidth-0.4pt,      % minus width of border
    minimum height=\myheight-0.4pt     % minus height of border
    ]
    at ([xshift=5cm]A) {Copy 2};
\end{tikzpicture}
```

This is my example node | Copy | Copy 2

12.10 Hyper Nodes

The following auxiliary macro is defined by the LIB skins library.

N 2016-02-03 **\tcbhypernode**{⟨*macro*⟩}{⟨*node*⟩}

Applies a hyperlink creating ⟨*macro*⟩ from the package `hyperref` [15] to an existing `tikz` ⟨*node*⟩. `\tcbhypernode` can only be used inside a `tikzpicture` environment. The last argument of the ⟨*macro*⟩ is to be omitted and should stand for an object (text) which is to be made a hyperlink. For example, use `\hyperref[name]` instead of `\hyperref[name]{text}`.

```
% \usepackage{hyperref}
\begin{tikzpicture}
  \node[align=center,draw=red,fill=red!5] (mybutton)
    {Click me to jump to Section~\ref*{sec:tikzimagefilling}};
  \tcbhypernode{\hyperref[sec:tikzimagefilling]}{mybutton}
\end{tikzpicture}
```

Click me to jump to Section 12

13 Beamer Support

The LIB skins library adds some supporting options for the `beamer` package [23]. For the following options, the LIB skins library has to be loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

See Section 10 on page 152 for the documentation of all other options of the LIB skins library.

N 2015-01-09
U 2019-03-01

`/tcb/only=<`*overlay specification*`>{`*options*`}` (style, no default, initially unset)

Sets the given `tcolorbox` ⟨*options*⟩ in dependency of a `beamer` ⟨*overlay specification*⟩. Note that this needs the `beamer` class [23]. The ⟨*options*⟩ will only be used on the specified `beamer` frames.

```
\documentclass{beamer}
\usepackage[many]{tcolorbox}
\begin{document}

\begin{frame}
  \begin{tcolorbox}[title=My title,fonttitle=\bfseries,
      enhanced,colframe=red!50!black,colback=red!10,colbacktitle=red,
      sidebyside,righthand width=3cm,
      lowerbox=invisible,lower separated=false,
      drop lifted shadow,
      only=<1>{colbacktitle=yellow,coltitle=red!50!black,colframe=red},
      only=<3>{colback=yellow!50,watermark text={Attention!}},
      only=<3->{lowerbox=visible}  ]
    This is a test.
    \begin{itemize}[<+->]
      \item One
      \item Two
      \item \alert<3>{Three}
      \item Four
    \end{itemize}
  \tcblower
    \begin{equation*}
    \int\limits_{1}^{x} \frac{1}{t}~dt = \ln(x).
    \end{equation*}
  \end{tcolorbox}
\end{frame}
\end{document}
```








```
\documentclass{beamer}
\usepackage[most]{tcolorbox}
\begin{document}

\begin{frame}[fragile]
  \begin{tcblisting}{beamer,colback=blue!5,colframe=blue!20!gray,coltitle=yellow,
    title=Example,
    only=<1>{lowerbox=invisible},only=<2>{}
  }
This is an \textbf{example listing}
  \end{tcblisting}
\end{frame}
\end{document}
```



! The option `/tcb/only` → P. 270 belonged to the base package before version 4.20.

N 2019-03-01 **`/tcb/hide=<`**⟨*overlay specification*⟩**`>`** (style, no default, initially unset)

Sets the `/tcb/beamer hidden` style in dependency of a `beamer` ⟨*overlay specification*⟩. `/tcb/beamer hidden` can be redefined for customization.

N 2019-03-01 **`/tcb/beamer hidden`** (style, no options, initially `nirvana`)

This style is not intended to be used directly, but in concealed way by applying `/tcb/hide`. The style can be redefined.

```
\tcbset{
  beamer hidden/.style={invisible,interior hidden,colframe=blue!20!gray!15},
}
```

N 2019-03-01 **/tcb/alert=<⟨*overlay specification*⟩>** (style, no default, initially unset)

Sets the /tcb/beamer alerted style in dependency of a beamer ⟨*overlay specification*⟩. /tcb/beamer alerted can be redefined for customization.

N 2019-03-01 **/tcb/beamer alerted** (style, no options, initially fuzzy halo)

This style is not intended to be used directly, but in concealed way by applying /tcb/alert. The style can be redefined.

```
\tcbset{
  beamer alerted/.style={colframe=red!50!gray},
}
```

The following examples use tcbitemize → P. 291 from LIB raster for convenient use of a list of boxes which are uncovered one by one.

```
\documentclass{beamer}
\usepackage[most]{tcolorbox}
\begin{document}

\begin{frame}
  \begin{tcbitemize}[raster equal height=rows,
    enhanced,colback=blue!5,colframe=blue!20!gray,coltitle=yellow,
    ]
  \tcbitem[title=One,alert=<1>]
    First Statement
  \tcbitem[title=Two,hide=<-1>,alert=<2>]
    Second Statement
  \tcbitem[title=Three,hide=<-2>,alert=<3>]
    Test
  \tcbitem[title=Four,hide=<-3>,alert=<4>]
    \begin{equation*}
    \int\limits_{1}^{x} \frac{1}{t}~dt = \ln(x).
    \end{equation*}
  \tcbitem[title=Five,hide=<-4>,alert=<5>]
    \includegraphics[width=1cm]{goldshade.png}
  \tcbitem[title=Six,hide=<-5>,alert=<6>]
    Test
  \end{tcbitemize}
\end{frame}
\end{document}
```








```latex
\documentclass{beamer}
\usepackage[most]{tcolorbox}
\begin{document}

\begin{frame}
  \begin{tcbitemize}[raster equal height=rows,
    enhanced,colback=blue!5,colframe=blue!20!gray,coltitle=yellow,
    beamer hidden/.style={invisible,interior hidden,colframe=blue!20!gray!15},
    beamer alerted/.style={colframe=red!50!gray},
    ]
  \tcbitem[title=One,alert=<1>]
    First Statement
  \tcbitem[title=Two,hide=<-1>,alert=<2>]
    Second Statement
  \tcbitem[title=Three,hide=<-2>,alert=<3>]
    Test
  \tcbitem[title=Four,hide=<-3>,alert=<4>]
    \begin{equation*}
    \int\limits_{1}^{x} \frac{1}{t}~dt = \ln(x).
    \end{equation*}
  \tcbitem[title=Five,hide=<-4>,alert=<5>]
    \includegraphics[width=1cm]{goldshade.png}
  \tcbitem[title=Six,hide=<-5>,alert=<6>]
    Test
  \end{tcbitemize}
\end{frame}
\end{document}
```

```
\documentclass{beamer}
\usepackage[most]{tcolorbox}
\begin{document}

\begin{frame}
  \begin{tcbitemize}[raster equal height=rows,
    beamer,colback=blue!5,colframe=blue!20!gray,coltitle=yellow,
    beamer ↩
      ↳hidden/.style={colback=white,colframe=gray!50,opacityupper=0.2,opacitytitle=0.2},
    beamer alerted/.style={colframe=red!50!gray,fuzzy halo},
    ]
  \tcbitem[title=One,alert=<1>]
    First Statement
  \tcbitem[title=Two,hide=<-1>,alert=<2>]
    Second Statement
  \tcbitem[title=Three,hide=<-2>,alert=<3>]
```

```
    Test
  \tcbitem[title=Four,hide=<-3>,alert=<4>]
    \begin{equation*}
    \int\limits_{1}^{x} \frac{1}{t}~dt = \ln(x).
    \end{equation*}
  \tcbitem[title=Five,hide=<-4>,alert=<5>]
    \includegraphics[width=1cm]{goldshade.png}
  \tcbitem[title=Six,hide=<-5>,alert=<6>]
    Test
  \end{tcbitemize}
\end{frame}
\end{document}
```

14 Library LIB vignette

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{vignette}
```

This also loads the LIB skins library, see Section 10 on page 152, and the `fadings` library of `tikz` [22].

14.1 Vignette Drawing

N 2016-04-22 **\tcbvignette{⟨*options*⟩}**

In this context, a *vignette* is a four part rectangular frame. It is constructed as several TikZ paths and, therefore, can only be used inside a `tikzpicture` environment or inside `tcolorbox` → P. 12 options.

The ⟨*options*⟩ control position, size and style settings of the vignette. Theses options have the common key path `/tcb/vig/` and are described in the following.

The next examples show direct `\tcbvignette` usage without a `tcolorbox` → P. 12.

```
\begin{tikzpicture}
  \tcbvignette{}
\end{tikzpicture}
```

```
\begin{tikzpicture}
  \node[draw,fill=blue!15!white] (A) {Test};
  \tcbvignette{outside node=A,raised color=blue}
\end{tikzpicture}
```

```
\begin{tikzpicture}
  \node[draw,fill=blue!15!white] (A) {Another Test};
  \tcbvignette{size=3mm,outside node=A,
    north style=red,east style=yellow,
    south style=blue,west style=green}
\end{tikzpicture}
```

```
\begin{tikzpicture}
  \node[inner sep=3mm,fill=red!75] (A) {Test};
  \tcbvignette{over node=A,fade in}
\end{tikzpicture}
```

`\tcbvignette` can be used directly inside appropriate options keys for `tcolorbox` → P. 12. Note that options like `/tcb/underlay` → P. 199 need `/tcb/enhanced` → P. 211 or similar settings.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colback=green!10,colframe=green!50!black,
  boxrule=1mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay={\tcbvignette{size=1mm,inside node=frame,
      raised color=green!50!black}}]
    This is a tcolorbox.
\end{tcolorbox}
```



Mostly, convenient short cuts like /tcb/underlay vignette → P. 283 can be used to add a *vignette* to a tcolorbox → P. 12. Here, \tcbvignette is used internally.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colback=green!10,colframe=green!50!black,
  boxrule=1mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay vignette]
    This is a tcolorbox.
\end{tcolorbox}
```

My title
This is a tcolorbox.

14.2 Generic Geometry Settings

N 2016-04-22 **/tcb/vig/xmin=⟨*length*⟩** (no default, initially 0pt)

Sets the lower horizontal limit of a \tcbvignette → P. 276.

N 2016-04-22 **/tcb/vig/xmax=⟨*length*⟩** (no default, initially 1cm)

Sets the upper horizontal limit of a \tcbvignette → P. 276.

N 2016-04-22 **/tcb/vig/ymin=⟨*length*⟩** (no default, initially 0pt)

Sets the lower vertical limit of a \tcbvignette → P. 276.

N 2016-04-22 **/tcb/vig/ymax=⟨*length*⟩** (no default, initially 1cm)

Sets the upper vertical limit of a \tcbvignette → P. 276.

```
\begin{tikzpicture}
  \fill [black!20] (0,0) rectangle (3,2);
  \path [pattern=checkerboard,pattern color=black!30]
    (0,0) rectangle (3,2);
  \tcbvignette{xmin=1cm,xmax=2.5cm,ymin=0.5cm,ymax=1.75cm}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/lower left corner=⟨*coordinates*⟩** (style, initially 0,0)

Sets the lower left corner of a \tcbvignette → P. 276. This style sets /tcb/vig/xmin and /tcb/vig/ymin.

N 2016-04-22 **/tcb/vig/upper right corner=⟨*coordinates*⟩** (style, initially 1,1)

Sets the upper right corner of a \tcbvignette → P. 276. This style sets /tcb/vig/xmax and /tcb/vig/ymax.

```
\begin{tikzpicture}
  \fill [black!20] (0,0) rectangle (3,2);
  \path [pattern=checkerboard,pattern color=black!30]
    (0,0) rectangle (3,2);
  \tcbvignette{lower left corner={1,0.5},
               upper right corner={2.5,1.75}}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/inside node=⟨*name*⟩** (style, initally unset)

Places the \tcbvignette → P. 276 inside the node with the given ⟨*name*⟩. The outer limits of the *vignette* are adapted to the node geometry.

```
\begin{tikzpicture}
  \node[minimum width=2cm,minimum height=1cm] (A) {Node A};
  \tcbvignette{inside node=A}
  \draw[very thick] (A.south west) rectangle (A.north east);
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/outside node=**⟨*name*⟩ (style, initally unset)

Places the \tcbvignette → P. 276 outside the node with the given ⟨*name*⟩. The inner limits of the *vignette* are adapted to the node geometry.

```
\begin{tikzpicture}
  \node[minimum width=2cm,minimum height=1cm] (A) {Node A};
  \tcbvignette{outside node=A}
  \draw[very thick] (A.south west) rectangle (A.north east);
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/over node=**⟨*name*⟩ (style, initally unset)

Places the \tcbvignette → P. 276 over the node with the given ⟨*name*⟩. The outer limits of the *vignette* are adapted to the node geometry, but are shifted to the outside by /tcb/vig/over node offset.

```
\begin{tikzpicture}
  \node[minimum width=2cm,minimum height=1cm] (A) {Node A};
  \tcbvignette{over node offset=1mm,over node=A}
  \draw[very thick] (A.south west) rectangle (A.north east);
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/over node offset=**⟨*length*⟩ (no default, initially 0.1mm)

Determines the shift value for /tcb/vig/over node. Note that /tcb/vig/over node offset has to be set *before* /tcb/vig/over node is used.

N 2016-04-22 **/tcb/vig/north size=**⟨*length*⟩ (no default, initially 2mm)

Sets the thickness of the north *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{north size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/south size=**⟨*length*⟩ (no default, initially 2mm)

Sets the thickness of the south *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{south size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/east size=**⟨*length*⟩ (no default, initially 2mm)

Sets the thickness of the east *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{east size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/west size=**⟨*length*⟩ (no default, initially 2mm)

Sets the thickness of the west *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{west size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/vertical size=**⟨*length*⟩ (style, initially 2mm)

Sets /tcb/vig/north size→P. 278 and /tcb/vig/south size→P. 278, to the given ⟨*length*⟩.

```
\begin{tikzpicture}
  \tcbvignette{vertical size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/horizontal size=**⟨*length*⟩ (style, initially 2mm)

Sets /tcb/vig/east size→P. 278 and /tcb/vig/west size→P. 278, to the given ⟨*length*⟩.

```
\begin{tikzpicture}
  \tcbvignette{horizontal size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/size=**⟨*length*⟩ (style, initially 2mm)

Sets /tcb/vig/north size→P. 278, /tcb/vig/south size→P. 278, /tcb/vig/east size→P. 278, and /tcb/vig/west size→P. 278 to the given ⟨*length*⟩.

```
\begin{tikzpicture}
  \tcbvignette{size=4mm}
\end{tikzpicture}
```

! /tcb/vig/north size→P. 278, /tcb/vig/south size→P. 278, etc. have to be set *before* /tcb/vig/outside node→P. 278 is used.

14.3 Generic Color and Style Settings

N 2016-04-22 **/tcb/vig/north style={**⟨*style*⟩**}** (no default, initially red!50!white)

Sets TikZ ⟨*style*⟩ options for the north *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{north style=blue}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/south style={**⟨*style*⟩**}** (no default, initially red!50!black)

Sets TikZ ⟨*style*⟩ options for the south *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{south style={draw=blue,fill=yellow}}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/east style={**⟨*style*⟩**}** (no default, initially red!75!black)

Sets TikZ ⟨*style*⟩ options for the east *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{east style={left color=yellow!75!black,
    right color=blue!75!black}}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/west style={⟨*style*⟩}** (no default, initially `red!75!white`)

Sets TikZ ⟨*style*⟩ options for the west *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{west style={preaction={fill=black!20},
    pattern=checkerboard,
    pattern color=black!30}}
\end{tikzpicture}
```

N 2016-05-24 **/tcb/vig/scope={⟨*style*⟩}** (no default, initially empty)

The four *vignette* parts are drawn inside a TikZ `scope` environment which takes the given ⟨*style*⟩ as option.

```
\begin{tikzpicture}
  \tcbvignette{scope={transparency group,opacity=0.25}}
\end{tikzpicture}
```


N 2016-04-22 **/tcb/vig/raised color=⟨*color*⟩** (no default)

Creates a raised frame impression by setting the four style options `/tcb/vig/north style`→ P. 279, `/tcb/vig/south style`→ P. 279, `/tcb/vig/east style`→ P. 279, and `/tcb/vig/west style` to darkened and lightened variations of the given ⟨*color*⟩.

```
\begin{tikzpicture}
  \tcbvignette{raised color=blue}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/lowered color=⟨*color*⟩** (no default)

Creates a lowered frame impression by setting the four style options `/tcb/vig/north style`→ P. 279, `/tcb/vig/south style`→ P. 279, `/tcb/vig/east style`→ P. 279, and `/tcb/vig/west style` to darkened and lightened variations of the given ⟨*color*⟩.

```
\begin{tikzpicture}
  \tcbvignette{lowered color=green!75!black}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/color from=⟨*inner*⟩ to ⟨*outer*⟩** (no default)

Sets the four style options `/tcb/vig/north style`→ P. 279, `/tcb/vig/south style`→ P. 279, `/tcb/vig/east style`→ P. 279, and `/tcb/vig/west style` such that the color shades from the ⟨*inner*⟩ color to the ⟨*outer*⟩ color.

```
\begin{tikzpicture}
  \tcbvignette{color from=red to blue!50}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/base color=⟨*color*⟩** (no default)

Sets the base color for `/tcb/vig/raised color`, `/tcb/vig/lowered color`, `/tcb/finish fading vignette`→ P. 286. Typically, this value has not to be set directly.

N 2016-04-22 `/tcb/vig/draw method=direct|clipped` (no default, initially `direct`)

Especially, if shadings or fadings are used, the drawn *vignette* graphs are displayed sometimes not as perfect as expected. Glitches and imperfections are very dependent on the previewer software. The `/tcb/vig/draw method` intends to give a choice of alternative drawing methods.

- `direct`: The *vignette* parts are drawn/filled by using a single TikZ graph. This is the preferred (and default) method for solid color graphs.
- `clipped`: The *vignette* parts are drawn somewhat oversized and are clipped to the intended region. In combination with shadings and fadings this seems to give a better/different optical result (depends on the previewer).

```
\begin{tikzpicture}
  \tcbvignette{color from=red to yellow}
\end{tikzpicture}
```

```
\begin{tikzpicture}
  \tcbvignette{color from=red to yellow,draw method=clipped}
\end{tikzpicture}
```

This option is a stopgap and may be changed or preferably removed in future.

14.4 Generic Fading Settings

The `fadings` library of `tikz` [22] is loaded automatically by the LIB vignette library. Amongst others, the fadings `west`, `east`, `north`, and `south` are defined inside the `fadings` library.

The LIB vignette library adds some more fadings called `semi west`, `semi east`, `semi north`, and `semi south`. These fadings are much *weaker* than the normal fadings.

```
\begin{tikzpicture}
  \fill [black!20] (0,0) rectangle (1,1);
  \path [pattern=checkerboard,pattern color=black!30]
    (0,0) rectangle (1,1);
  \fill [path fading=semi west,blue] (0,0) rectangle (1,1);
\end{tikzpicture}
```

Comparison of the Fadings

`west`		`east`	
`north`		`south`	
`semi west`		`semi east`	
`semi north`		`semi south`	

N 2016-04-22 **/tcb/vig/fade in={⟨*style*⟩}** (style, default **white**)

Sets the four style options /tcb/vig/north style→P. 279, /tcb/vig/south style→P. 279, /tcb/vig/east style→P. 279, and /tcb/vig/west style→P. 280 such that the paths fade from outside to inside.

```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{fade in=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/fade out={⟨*style*⟩}** (style, default **white**)

Sets the four style options /tcb/vig/north style→P. 279, /tcb/vig/south style→P. 279, /tcb/vig/east style→P. 279, and /tcb/vig/west style→P. 280 such that the paths fade from inside to outside.

```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{fade out=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/semi fade in={⟨*style*⟩}** (style, default **white**)

Sets the four style options /tcb/vig/north style→P. 279, /tcb/vig/south style→P. 279, /tcb/vig/east style→P. 279, and /tcb/vig/west style→P. 280 such that the paths fade weak from outside to inside.

```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{semi fade in=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/semi fade out={⟨*style*⟩}** (style, default **white**)

Sets the four style options /tcb/vig/north style→P. 279, /tcb/vig/south style→P. 279, /tcb/vig/east style→P. 279, and /tcb/vig/west style→P. 280 such that the paths fade weak from inside to outside.

```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{semi fade out=blue}
\end{tikzpicture}
```



14.5 Vignette as Underlay

N 2016-04-22 **/tcb/underlay vignette={⟨*options*⟩}** (style, no default)

This puts a \tcbvignette[→P. 276] with the given ⟨*options*⟩ as /tcb/underlay[→P. 199] to a tcolorbox[→P. 12]. The dimensions of the *vignette* are matched to the dimensions of the tcolorbox[→P. 12]. For example, /tcb/leftrule[→P. 35] is used as /tcb/vig/west size[→P. 278]. Also, /tcb/colframe[→P. 27] is used as /tcb/vig/raised color[→P. 280].
For a /tcb/breakable[→P. 379] tcolorbox, the *vignette* is also been broken. Alternatively, \tcbvignette[→P. 276] could be used directly inside an /tcb/underlay[→P. 199] with appropriate settings.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colback=green!10,colframe=green!50!black,
  boxrule=2mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay vignette]
    This is a tcolorbox.
\end{tcolorbox}
```




```
\begin{tcolorbox}[enhanced,size=small,arc=0pt,
  colback=blue!10,colframe=blue,boxrule=2mm,
  underlay vignette={size=1.5mm}]
    This is a tcolorbox.
\end{tcolorbox}
```




```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colframe=red,interior hidden,boxrule=2mm,
  colupper=white,center upper,fontupper=\bfseries,
  underlay vignette]
    This is a tcolorbox.
\end{tcolorbox}
```

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colback=red!50!yellow,frame hidden,boxrule=2mm,
  underlay vignette={color from=red!50!yellow to white,
     draw method=clipped,size=2.1mm}]
    This is a tcolorbox.
\end{tcolorbox}
```

```
\tcbox[enhanced,sharp corners,colback=red!10,colframe=red]
  {Test}

\tcbox[enhanced,sharp corners,colback=red!10,colframe=red,
  underlay vignette]{Test}
```



N 2016-04-22 **/tcb/underlay raised shading vignette={⟨*options*⟩}** (style, no default)

This is a special style derived from /tcb/underlay vignette → P. 283, where the frame color is shaded to create a soft raised frame impression.

```
\begin{tcolorbox}[enhanced,sharp corners,
  colback=green!10,
  colframe=green!50!black,
  size=small,boxrule=2mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay raised shading vignette]
    This is a tcolorbox.
\end{tcolorbox}
```



N 2016-04-22 **/tcb/underlay raised fading vignette={⟨*options*⟩}** (style, no default)

This style gives a similar effect as /tcb/underlay raised shading vignette, but a path fading is used here. Different optical impression are very previewer-dependent.

```
\begin{tcolorbox}[enhanced,sharp corners,
  colback=green!10,
  colframe=green!50!black,
  size=small,boxrule=2mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay raised fading vignette]
    This is a tcolorbox.
\end{tcolorbox}
```



N 2016-04-22 **/tcb/underlay shade in vignette={⟨*options*⟩}** (style, no default)

This is a special style derived from /tcb/underlay vignette → P. 283, where the frame color is shaded into the interior color.

```
\begin{tcolorbox}[enhanced,sharp corners,frame hidden,
  colback=green!10,
  colframe=green!50!black,
  size=small,boxrule=2mm,titlerule=0mm,
  underlay shade in vignette]
    This is a tcolorbox.
\end{tcolorbox}
```



14.6 Vignette as Finish

N 2016-04-22 **/tcb/finish vignette={⟨*options*⟩}** (style, no default)

This puts a \tcbvignette → P. 276 with the given ⟨*options*⟩ as /tcb/finish → P. 201 to a tcolorbox → P. 12. The default style settings create a raised frame impression by drawing black and white color parts with reduced opacity.

```
\begin{tcolorbox}[enhanced,size=small,
  colback=green!10,colframe=green!50!black,
  boxrule=0.5mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  finish vignette={size=1mm}]
    This is a tcolorbox.
\end{tcolorbox}
```

My title
This is a tcolorbox.

```
\tcbincludegraphics[blankest,width=3cm,
  finish vignette={size=3mm}]{pink_marble.png}
```



N 2016-04-22 **/tcb/finish raised fading vignette={⟨*options*⟩}** (style, no default)

This puts a \tcbvignette → P. 276 with the given ⟨*options*⟩ as /tcb/finish → P. 201 to a tcolorbox → P. 12. The default style settings create a soft raised frame impression by drawing fading black and white color parts.

```
\begin{tcolorbox}[enhanced,size=small,
  colback=green!10,colframe=green!50!black,
  boxrule=0.5mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  finish raised fading vignette={size=1mm}]
    This is a tcolorbox.
\end{tcolorbox}
```

My title
This is a tcolorbox.

```
\tcbincludegraphics[blankest,width=3cm,
  finish raised fading vignette={size=3mm}]{pink_marble.png}
```

N 2016-04-22 **/tcb/finish fading vignette={⟨*options*⟩}** (style, no default)

This puts a \tcbvignette → P. 276 with the given ⟨*options*⟩ as /tcb/finish → P. 201 to a tcolorbox → P. 12. The default style settings fade the box into white from inside to outside. Note that /tcb/vig/over node → P. 278 is used here. /tcb/vig/over node offset → P. 278 can be adapted to overlap the box more or less. The fade color can be set using /tcb/vig/base color → P. 280.

```
\begin{tcolorbox}[enhanced,size=small,
  colback=green!10,colframe=green!50!black,
  boxrule=0.5mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  finish fading vignette={size=2mm}]
    This is a tcolorbox.
\end{tcolorbox}
```

My title
This is a tcolorbox.

```
\tcbincludegraphics[blankest,width=3cm,
  finish fading vignette={size=3mm}]{pink_marble.png}
```

```
\begin{tcolorbox}[colback=blue!50!black,size=small,
  title=Example]
\tcbincludegraphics[blankest,
  finish fading vignette={base color=blue!50!black,size=3mm,
    over node offset=0.2mm}]{pink_marble.png}
\end{tcolorbox}
```

Example



```
\begin{tcbitemize}[raster columns=3,bicolor,
  raster equal height,sharp corners,boxrule=2mm,
  colframe=red,colback=yellow!5,colbacklower=yellow!25!red!20]
\tcbitem A
\tcbitem[underlay vignette] B
\tcbitem[underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}}] C
\tcbitem[underlay vignette,
  underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}}] D
\tcbitem[boxrule=3mm,underlay vignette={size=2mm},
  underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}}] E
\tcbitem[underlay raised shading vignette] F
\tcbitem[underlay raised shading vignette,
  underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}}] G
\tcbitem[title=H1,underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}},finish vignette] H2
\tcbitem[boxrule=0.25mm,colback=red!30,finish vignette] I1 \tcblower I2
\tcbitem[tile,colback=red!30,finish raised fading vignette] J1 \tcblower J2
\tcbitem[boxrule=1mm,underlay={\tcbvignette{inside node=interior,
  raised color=red,size=1mm}}] K
\tcbitem[boxrule=1mm,title=L1,underlay={\tcbvignette{inside node=title,
  lowered color=red,size=0.5mm}}] L2
\end{tcbitemize}
```



15 Library raster

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{raster}
```

15.1 Concept of Rasters

A *raster* is used to align several colored boxes in a regular way. It can be seen as a far related counterpart to the `matrix` construct of Ti*k*Z, but it differs in many aspects.

In principle, `tcolorbox`es are arranged in rows and columns when put inside a `tcbraster` → P. 290 environment. The boxes are fluently added to the raster like adding text to a paragraph. Especially, line/row breaks are done automatically and one cannot end a line/row ahead of schedule. Further, a *raster* is not restricted to a single page but may break into an arbitrary series of pages.



```
\begin{tcbraster}[raster columns=3,raster rows=3,raster height=\linewidth,
  enhanced,size=small,sharp corners,arc=8mm,colframe=red!50!black,
  colback=yellow!10!white,watermark overzoom=1.0,fit algorithm=hybrid* ]
  \begin{tcolorbox}[rounded corners=northwest,boxrule=0pt,
    watermark graphics=lichtspiel.jpg]\end{tcolorbox}
  \tcboxfit{\lipsum[1]}
  \begin{tcolorbox}[rounded corners=northeast,boxrule=0pt,
    watermark graphics=goldshade.png]\end{tcolorbox}
  \tcboxfit{\lipsum[2]}
  \begin{tcolorbox}[valign=center,halign=center]Nine Boxes.\end{tcolorbox}
  \tcboxfit{\lipsum[3]}
  \begin{tcolorbox}[rounded corners=southwest,boxrule=0pt,
    watermark graphics=goldshade.png]\end{tcolorbox}
  \tcboxfit{\lipsum[4]}
  \begin{tcolorbox}[rounded corners=southeast,boxrule=0pt,
    watermark graphics=lichtspiel.jpg]\end{tcolorbox}
\end{tcbraster}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nine Boxes.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

15.2 Macros of the Library

N 2014-11-10
U 2017-02-01

```
\begin{tcbraster}[⟨options⟩]
  ⟨environment content⟩
\end{tcbraster}
```

A raster arranges enclosed boxes in a regular way, mainly into rows and columns. The ⟨*options*⟩ are used to control the raster parameters and to set the properties for the enclosed boxes.

- The *raster* is only allowed to contain a series of `tcolorbox`→ P. 12 environments or derived constructs. With some small restrictions, boxes created with `\tcboxfit`→ P. 426 can also be added. Boxes created with `\tcbox`→ P. 14 are not reasonable here, but may be used to a certain degree.
- Do not add anything else between the boxes inside the raster with exception of white-space. Especially, do not use `\\` or `\par` to end a row; row breaks are done automatically.
- The boxes inside a raster are numbered automatically. `\thetcbrasternum` may be used inside a box to access this number.

```
\begin{tcbraster}[raster columns=3, raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  \begin{tcolorbox}First box\end{tcolorbox}
  \begin{tcolorbox}Second box\end{tcolorbox}
  \begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
  \begin{tcolorbox}Another box\end{tcolorbox}
  \begin{tcolorbox}A box again\end{tcolorbox}
\end{tcbraster}
```

Box # 1
First box

Box # 2
Second box

Box # 3
This is a box
with a second line

Box # 4
Another box

Box # 5
A box again

```
\begin{tcbraster}[raster columns=2, raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  \begin{tcolorbox}First box\end{tcolorbox}
  \begin{tcolorbox}Second box\end{tcolorbox}
  \begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
  \begin{tcolorbox}Another box\end{tcolorbox}
  \begin{tcolorbox}A box again\end{tcolorbox}
\end{tcbraster}
```

Box # 1
First box

Box # 2
Second box

Box # 3
This is a box
with a second line

Box # 4
Another box

Box # 5
A box again

N 2014-11-10 `\begin{tcbitemize}[⟨options⟩]`
`⟨environment content⟩`
`\end{tcbitemize}`

This is a special case of a `tcbraster`→ P. 290 with the given ⟨*options*⟩.

- Here, the enclosed boxes are created using `\tcbitem`.
- There has to be at least one `\tcbitem`.
- One cannot use anything else than `\tcbitem` to add something to the *raster*.

This leads to a very compact syntax.

```
\begin{tcbitemize}[raster columns=2, raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  \tcbitem First box
  \tcbitem Second box
  \tcbitem This is a box\\with a second line
  \tcbitem[colback=yellow,colbacktitle=yellow!50!black] Another box
  \tcbitem A box again
\end{tcbitemize}
```

Box # 1
First box

Box # 2
Second box

Box # 3
This is a box
with a second line

Box # 4
Another box

Box # 5
A box again

! `tcbitemize` has more restrictions than `tcbraster`→ P. 290. Especially, the `/tcb/capture`→ P. 97 mode has to be `minipage`. For example, `/tcb/fit`→ P. 429 cannot be used safely. If `/tcb/fit`→ P. 429 should be used, turn over to `tcbraster`→ P. 290.

N 2014-11-10 `\tcbitem[⟨options⟩]`

Used inside `tcbitemize` to create a new `tcolorbox`→ P. 12 with the given ⟨*options*⟩.

N 2016-02-19

```
\begin{tcboxedraster}[⟨raster options⟩]{⟨box options⟩}
  ⟨environment content⟩
\end{tcboxedraster}
```

This is a convenience environment which combines a `tcolorbox`→ P. 12 with an embedded `tcbraster`→ P. 290. The ⟨*box options*⟩ are given to the outer `tcolorbox`→ P. 12, while the ⟨*raster options*⟩ are given to the embedded `tcbraster`→ P. 290. This environment is especially useful for rasters inside rasters.

```
\begin{tcboxedraster}[raster columns=3, raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  {colback=yellow!10,fonttitle=\bfseries,title=Boxed Raster}
  \begin{tcolorbox}First box\end{tcolorbox}
  \begin{tcolorbox}Second box\end{tcolorbox}
  \begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
  \begin{tcolorbox}Another box\end{tcolorbox}
  \begin{tcolorbox}A box again\end{tcolorbox}
\end{tcboxedraster}
```




```
% \tcbuselibrary{skins}
\begin{tcbraster}[raster columns=2, raster equal height,
  raster every box/.style={size=small,colframe=red!50!black,colback=red!10!white,
    valign=center,halign=center}]
  \begin{tcolorbox}One\end{tcolorbox}
  \begin{tcolorbox}Two\end{tcolorbox}
    \begin{tcboxedraster}{blankest}
      \begin{tcolorbox}Three\end{tcolorbox}
      \begin{tcolorbox}Four\end{tcolorbox}
      \begin{tcolorbox}Five\end{tcolorbox}
      \begin{tcolorbox}Six\end{tcolorbox}
    \end{tcboxedraster}
    \begin{tcolorbox}Seven\end{tcolorbox}
\end{tcbraster}
```



N 2016-04-27

```
\begin{tcboxeditemize}[⟨raster options⟩]{⟨box options⟩}
  ⟨environment content⟩
\end{tcboxeditemize}
```

This is a convenience environment which combines a `tcolorbox` → P. 12 with an embedded `tcbitemize` → P. 291. The ⟨*box options*⟩ are given to the outer `tcolorbox` → P. 12, while the ⟨*raster options*⟩ are given to the embedded `tcbitemize` → P. 291. This environment is especially useful for rasters inside rasters.

```
\begin{tcboxeditemize}[raster columns=3, raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  {colback=yellow!10,fonttitle=\bfseries,title=Boxed Itemize}
  \tcbitem First box
  \tcbitem Second box
  \tcbitem This is a box\\with a second line
  \tcbitem Another box
  \tcbitem A box again
\end{tcboxeditemize}
```

Boxed Itemize

Box # 1
First box

Box # 2
Second box

Box # 3
This is a box
with a second line

Box # 4
Another box

Box # 5
A box again

15.3 Option Keys of the Library

N 2014-11-10 **/tcb/raster columns=**⟨*number*⟩ (no default, initially 2)

Sets the ⟨*number*⟩ of columns for a *raster*.

```
\begin{tcbitemize}[raster columns=3,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
\begin{tcbitemize}[raster columns=4,
  size=small,colframe=blue!50!black,colback=blue!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two | Three
Four

One | Two | Three | Four

N 2014-11-10 **/tcb/raster rows=**⟨*number*⟩ (no default, initially 2)

Sets the ⟨*number*⟩ of rows for a *raster*. Note that this is only relevant in connection with setting /tcb/raster height → P. 296 to a value greater than 0pt. Then, it defines the number of rows *per* given height.

N 2014-11-10 **/tcb/raster width=**⟨*length*⟩ (no default, initially \linewidth)

Sets the total raster width to the given ⟨*length*⟩. /tcb/raster left skip → P. 297 and /tcb/raster right skip → P. 297 are part of the total width. Note that both skip values are not changed by this option.

```
\begin{tcbitemize}[raster width=\linewidth/2,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

N 2018-11-30 **/tcb/raster width flush left=⟨*length*⟩** (style, no default)

Sets the total /tcb/raster width→P. 294 to \linewidth and adapts /tcb/raster left skip→P. 297 and /tcb/raster right skip→P. 297 to place the raster on the left hand side with a visual width of the given ⟨*length*⟩.

```
\begin{tcbitemize}[raster width flush left=\linewidth/2,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

Note that the results of /tcb/raster width→P. 294 and /tcb/raster width flush left look identical, but differ on technical side since the later always fills the available \linewidth.

N 2018-11-30 **/tcb/raster width center=⟨*length*⟩** (style, no default)

Sets the total /tcb/raster width→P. 294 to \linewidth and adapts /tcb/raster left skip→P. 297 and /tcb/raster right skip→P. 297 to center the raster with a visual width of the given ⟨*length*⟩.

```
\begin{tcbitemize}[raster width center=\linewidth/2,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

N 2018-11-30 **/tcb/raster width flush right=⟨*length*⟩** (style, no default)

Sets the total /tcb/raster width→P. 294 to \linewidth and adapts /tcb/raster left skip→P. 297 and /tcb/raster right skip→P. 297 to place the raster on the right hand side with a visual width of the given ⟨*length*⟩.

```
\begin{tcbitemize}[raster width flush right=\linewidth/2,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

N 2014-11-10 **/tcb/raster height=⟨*length*⟩** (no default, initially `0pt`)

Sets the raster height *per* `/tcb/raster rows` → P. 294 to the given ⟨*length*⟩. This forces an appropriate height for the enclosed boxes. `/tcb/raster before skip` and `/tcb/raster after skip` are not part of this calculation. If the ⟨*length*⟩ is set to `0pt`, this feature is deactivated.

```
\begin{tcbitemize}[raster height=4cm, raster rows=2,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem[enhanced,
    finish={\draw[blue,very thick,<->] (frame.south)
      -- node[right,pos=.75]{4cm} +(0,4); }]
    Three
  \tcbitem Four
  \tcbitem Five
\end{tcbitemize}
```



N 2014-11-10
U 2014-12-16 **/tcb/raster before skip=⟨*glue*⟩** (no default, initially `2mm`)

Space of the given ⟨*glue*⟩ is inserted vertically before the *raster*. This space is discardable.

N 2014-11-10
U 2014-12-16 **/tcb/raster after skip=⟨*glue*⟩** (no default, initially `2mm`)

Space of the given ⟨*glue*⟩ is inserted vertically after the *raster*. This space is discardable.

N 2015-01-08 **/tcb/raster equal skip=⟨*length*⟩** (style, no default)

Shortcut to set `/tcb/raster before skip`, `/tcb/raster after skip`, `/tcb/raster column skip` → P. 297, and `/tcb/raster row skip` → P. 297 to the same ⟨*length*⟩ value.

```
\begin{tcbitemize}[raster equal skip=4mm,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```



N 2014-11-10 **/tcb/raster left skip=⟨*length*⟩** (no default, initially 0pt)

Space of the given ⟨*length*⟩ is inserted horizontally left of the *raster*.

```
\begin{tcbitemize}[raster left skip=2cm,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

N 2014-11-10 **/tcb/raster right skip=⟨*length*⟩** (no default, initially 0pt)

Space of the given ⟨*length*⟩ is inserted horizontally right of the *raster*.

```
\begin{tcbitemize}[raster right skip=2cm,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

N 2014-11-10 **/tcb/raster column skip=⟨*length*⟩** (no default, initially 2mm)

Space of the given ⟨*length*⟩ is inserted horizontally between the columns.

```
\begin{tcbitemize}[raster column skip=2cm,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

N 2014-11-10 **/tcb/raster row skip=⟨*length*⟩** (no default, initially 2mm)

Space of the given ⟨*length*⟩ is inserted vertically between the rows.

```
\begin{tcbitemize}[raster row skip=0pt,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

N 2014-11-10 **/tcb/raster halign=**⟨*alignment*⟩ (no default, initially **left**)

Defines the horizontal alignment for the boxes of the rows of a *raster*, if these rows are not completely filled (mainly: the last one).
Feasible values for ⟨*alignment*⟩ are:

- **left**: align to the left side,
- **center**: align to the center,
- **right**: align to the right side.

```
\begin{tcbitemize}[raster halign=center,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
\end{tcbitemize}
```

One | Two | Three

N 2014-11-10 **/tcb/raster valign=**⟨*alignment*⟩ (no default, initially **center**)

Defines the vertical alignment for the boxes of a row, if the boxes do not have equal height. This sets the **/tcb/box align** →P. 82 option.
Feasible values for ⟨*alignment*⟩ are:

- **top**: align to the top side,
- **center**: align to the center,
- **bottom**: align to the bottom side.

```
\begin{tcbitemize}[raster valign=top, raster columns=3,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem \Huge One
  \tcbitem \Large Two
  \tcbitem Three
\end{tcbitemize}
\begin{tcbitemize}[raster valign=center, raster columns=3,
  size=small,colframe=blue!50!black,colback=blue!10!white]
  \tcbitem \Huge One
  \tcbitem \Large Two
  \tcbitem Three
\end{tcbitemize}
\begin{tcbitemize}[raster valign=bottom, raster columns=3,
  size=small,colframe=green!50!black,colback=green!10!white]
  \tcbitem \Huge One
  \tcbitem \Large Two
  \tcbitem Three
\end{tcbitemize}
```

One | Two | Three

One | Two | Three

One | Two | Three

N 2014-11-10
U 2017-02-28

/tcb/raster equal height=⟨*type*⟩ (default **all**, initially **none**)

Puts the enclosed boxes into a common /tcb/equal height group → P. 61. The ⟨*id*⟩ of the equal height group is chosen automatically, but it may be set manually by /tcb/raster equal height group. Also see /tcb/minimum for current equal height group → P. 62. Feasible values for ⟨*type*⟩ are:

- **none**: no equal height setting,
- **rows**: all boxes in a row are set to equal height,
- **all**: all boxes in the raster are set to equal height.

Note that you have to compile twice to see changes.

```
\begin{tcbitemize}[raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem \Huge Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One

Two

Three

Four

```
\begin{tcbitemize}[raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem \Huge Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One

Two

Three

Four

N 2014-11-10

/tcb/raster equal height group=⟨*id*⟩ (no default)

Overwrites the automatically chosen id with the given ⟨*id*⟩. If this is used to share a common height between the *raster* and another raster or box, the /tcb/raster equal height option should be set to **all**.

```
\tcbset{size=small,colframe=red!50!black,colback=red!10!white}
\begin{tcolorbox}[equal height group=raster-manual-id]
  A single box
\end{tcolorbox}
\begin{tcbitemize}[raster equal height,raster equal height group=raster-manual-id]
  \tcbitem One
  \tcbitem \Huge Two
\end{tcbitemize}
```

A single box

One

Two

N 2014-11-10 **/tcb/raster force size=true|false** (default true, initially true)

Enforces the raster size computations onto the enclosed boxes. If set to **false**, individual settings can be used (for the better or worse).

```
\begin{tcbitemize}[raster force size=false, raster halign=center,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem[add to width=-3cm] Three
  \tcbitem[add to width=-3cm] Four
  \tcbitem[add to width=-3cm] Five
  \tcbitem[add to width=3cm] Six
\end{tcbitemize}
```

One | Two | Three | Four | Five | Six

N 2014-11-10 **/tcb/raster reset** (no value)

Sets all raster settings back to their default values. Note that /tcb/reset → P. 109 does not execute this option. Style settings like /tcb/raster odd column etc. are not touched by /tcb/raster reset.

15.4 Adding Styles for Specific Boxes

The following styles can be defined to address certain boxes inside a *raster*. Note that such style definitions are not removed by /tcb/reset → P. 109 or /tcb/raster reset. The style definitions are used in the order given below.

N 2014-11-24 **/tcb/raster every box** (style)

This style is used for every box.

N 2014-11-10 **/tcb/raster odd column** (style)

This style is used for every box in an odd column.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
  raster odd column/.style={colframe=blue!50!black,colback=blue!10!white}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two | Three | Four

N 2014-11-10 **/tcb/raster even column** (style)

This style is used for every box in an even column.

N 2014-11-10 **/tcb/raster column n** (style)

This style is used for every box in the n-th column. n has to be replaced by a number.

N 2014-11-10 **/tcb/raster odd row** (style)

This style is used for every box in an odd row.

N 2014-11-10 **/tcb/raster even row** (style)

This style is used for every box in an even row.

N 2014-11-10 **/tcb/raster row m** (style)

This style is used for every box in the m-th row. m has to be replaced by a number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
  raster row 2/.style={colframe=blue!50!black,colback=blue!10!white}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

N 2014-11-10 **/tcb/raster odd number** (style)

This style is used for every box with an odd number.

N 2014-11-10 **/tcb/raster even number** (style)

This style is used for every box with an even number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
  raster columns=3,
  raster even number/.style={colframe=blue!50!black,colback=blue!10!white}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
  \tcbitem Five
  \tcbitem Six
\end{tcbitemize}
```

One | Two | Three
Four | Five | Six

N 2014-11-10 **/tcb/raster row m column n** (style)

This style is used for the box in the m-th row and n-th column. m and n have to be replaced by numbers.

N 2014-11-10 **/tcb/raster number n** (style)

This style is used for the box with number n. n has to be replaced by a number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
  raster number 4/.style={colframe=blue!50!black,colback=blue!10!white}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two
Three | Four

15.5 Combining Columns or Rows

N 2016-02-19 **/tcb/raster multicolumn=**⟨*number*⟩ (no default, initially unset)

This option has to be set inside the option list of a `tcolorbox` → P. 12 inside a `tcbraster` → P. 290 or inside `\tcbitem` → P. 291 inside `tcbitemize` → P. 291. It merges the given ⟨*number*⟩ of boxes into one single box on the same line. The resulting box gets the **\thetcbrasternum** of the first box. If there are not enough boxes available on the current line, this option is ignored and a warning is given.

```
\begin{tcbitemize}[raster equal height=rows,raster columns=3,
  title=\thetcbrasternum,colframe=red!50!black,colback=red!10!white]
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=1]
  multicolumn=1
\tcbitem
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=2]
  multicolumn=2
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=3]
  multicolumn=3
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=2]
  multicolumn=2
\end{tcbitemize}
```



N 2016-02-19 **/tcb/raster multirow=**⟨*number*⟩ (no default, initially unset)

This option has to be set inside the option list of a tcolorbox → P. 12 inside a tcbraster → P. 290 or inside \tcbitem → P. 291 inside tcbitemize → P. 291. This option not really merges boxes, but simply sizes the current box to fit the space of ⟨*number*⟩ rows.

> **!** /tcb/raster multirow needs /tcb/raster height → P. 296 to be set. How to achieve a similar result for boxes without fixed /tcb/raster height → P. 296 is shown afterwards.

```
\begin{tcbitemize}[raster rows=3,raster columns=3,raster height=6cm,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
\tcbitem
\tcbitem
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multirow=2]
  multirow=2
\tcbitem[raster multicolumn=2,raster multirow=2,blankest]
  \begin{tcbitemize}[raster rows=2,raster columns=2,raster height=\tcbtextheight]
  \tcbitem
  \tcbitem
  \tcbitem
  \tcbitem
  \end{tcbitemize}
\end{tcbitemize}
```



For rasters without fixed /tcb/raster height→ P. 296, /tcb/raster multirow→ P. 303 cannot be used. Note that \tcbtextheight→ P. 151 also cannot be used like in the previous example.
But, with combination of /tcb/raster equal height→ P. 299 and /tcb/space to→ P. 59, a similar effect can be created:

```
\begin{tcbitemize}[raster columns=3,raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
\tcbitem
\tcbitem
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white]
 \lipsum[2]
\tcbitem[raster multicolumn=2,blankest,space to=\myspace]
  \begin{tcbitemize}[raster columns=2]
  \tcbitem This is a box of the inner raster.
  \tcbitem
  \tcbitem[height=\myspace]
  \tcbitem[height=\myspace]
  \end{tcbitemize}
\end{tcbitemize}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This is a box of the inner raster.

15.6 Rasters inside Rasters

A *raster* inside a *raster* cannot be used directly, because a *raster* can only contain a *tcolorbox* or something derived from a *tcolorbox*. So, a *raster* can be put inside a *tcolorbox* inside a *raster*.

Some examples for such constructions can be found at `tcboxedraster` → P. 292, `/tcb/raster multicolumn` → P. 302, `/tcb/raster multirow` → P. 303.

15.6.1 Raster Setup

The intermediating `tcolorbox` → P. 12 can be made invisible by using `/tcb/blankest` → P. 244.

```
\begin{tcbraster}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \begin{tcolorbox}[blankest]
    \begin{tcbraster}[raster columns=1]
      \begin{tcolorbox}One\end{tcolorbox}
      \begin{tcolorbox}Two\end{tcolorbox}
    \end{tcbraster}
  \end{tcolorbox}
  \begin{tcolorbox}raster+tcolorbox+raster\end{tcolorbox}
\end{tcbraster}
```

One

Two

raster+tcolorbox+raster

```
\begin{tcbraster}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \begin{tcboxedraster}[raster columns=1]{blankest}
    \begin{tcolorbox}One\end{tcolorbox}
    \begin{tcolorbox}Two\end{tcolorbox}
  \end{tcboxedraster}
  \begin{tcolorbox}raster+tcboxedraster\end{tcolorbox}
\end{tcbraster}
```

One

Two

raster+tcboxedraster

```
\begin{tcbitemize}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \tcbitem[blankest]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem One
      \tcbitem Two
    \end{tcbitemize}
  \tcbitem tcbitemize+tcbitem+tcbitemize
\end{tcbitemize}
```

One

Two

tcbitemize+tcbitem+tcbitemize

15.6.2 Placing Spaces

If the heights of boxes inside staggered rasters should be matched, the space has to be distributed accordingly.

- For fixed height boxes/rasters using `/tcb/raster height` → P. 296, the height of boxes is available by `\tcbtextheight` → P. 151. This can be used to size deeper layered boxes/rasters.
- For boxes/rasters layed out using `/tcb/raster equal height` → P. 299, space can be distributed by `/tcb/space to` → P. 59. It can take several compilations until all spaces are distributed correctly.

```
\begin{tcbitemize}[raster rows=2,raster height=6cm,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \tcbitem[blankest]
    \begin{tcbitemize}[raster columns=1,raster rows=2,raster height=\tcbtextheight]
      \tcbitem One
      \tcbitem Two
    \end{tcbitemize}
  \tcbitem This is a fixed height box.
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One

Two

This is a fixed height box.

Three

Four

```
\begin{tcbitemize}[raster columns=4,raster rows=4,raster height=0.8\linewidth,
  raster every box/.style={size=small,beamer,
    colframe=blue!75!yellow,colback=red!75!yellow!20,
    center title,title=Box}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
  \tcbitem[raster multirow=2,blankest]
    \begin{tcbitemize}[raster columns=1,raster rows=2,raster height=\tcbtextheight]
      \tcbitem Twelve
      \tcbitem Eleven
    \end{tcbitemize}
  \tcbitem[raster multirow=2,raster multicolumn=2,
      colframe=red!75!yellow,colback=blue!75!yellow!20]
    This is an example with fixed height boxes.
  \tcbitem[raster multirow=2,blankest]
    \begin{tcbitemize}[raster columns=1,raster rows=2,raster height=\tcbtextheight]
      \tcbitem Five
      \tcbitem Six
    \end{tcbitemize}
  \tcbitem Ten
  \tcbitem Nine
  \tcbitem Eight
  \tcbitem Seven
\end{tcbitemize}
```



```
\begin{tcbitemize}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \tcbitem[blankest,space to=\myspace]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem One
      \tcbitem[add to natural height=\myspace]
        This box will adapt its height.
    \end{tcbitemize}
  \tcbitem This is a flexible height box.
  \tcbitem \lipsum[4]
  \tcbitem[blankest,space to=\myspace]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem One
      \tcbitem[add to natural height=\myspace]
        This box will adapt its height.
    \end{tcbitemize}
\end{tcbitemize}
```

One

This box will adapt its height.

This is a flexible height box.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

One

This box will adapt its height.

```
\begin{tcbitemize}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \tcbitem[blankest,space to=\myspace]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem One
      \tcbitem[add to natural height=\myspace]
        This box will adapt its height.
      \tcbitem \lipsum[4]
    \end{tcbitemize}
  \tcbitem[blankest,space to=\myspace]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem[blankest]\includegraphics[width=\linewidth]{goldshade.png}
      \tcbitem[add to natural height=\myspace]
        This box will adapt its height.
    \end{tcbitemize}
\end{tcbitemize}
```

One

This box will adapt its height.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

This box will adapt its height.

16 Libraries LIB listings, LIB listingsutf8, and LIB minted

16.1 Loading the Libraries

In contrast to other `tcolorbox` libraries, the libraries LIB listings, LIB listingsutf8, and LIB minted are concurrent in the sense that they all do the same thing, i. e. displaying listings with or without typesetting the listing in LaTeX parallel. The difference is the underlying LaTeX package which does the core job for displaying a listing. So, typically, you need just *one* of these libraries. If you do not have a clue which one of them you should use and you are using `pdflatex`, you should take LIB listingsutf8. If you are using `xelatex` or `lualatex`, you should take LIB listings as `xelatex` and `lualatex` are not compatible with LIB listingsutf8.

> **!** The order in which the libraries are included influences the default settings and the `/tcb/reset` → P. 109 behavior. The settings of a later loaded library overwrite the settings of a previous loaded library. A library is never loaded twice.

16.1.1 Loading LIB listings

This library uses the package `listings` [6] to typeset listings. It is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{listings}
```

This also loads the package `listings` [6].

The `/tcb/listing engine` → P. 322 is set to `listings` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=listings}
```

16.1.2 Loading LIB listingsutf8

> **!** This library is not needed (and troublesome) when using XeLaTeX or LuaLaTeX. Therefore, loading this library is automatically replaced by loading LIB listings only, if pdfLaTeX is *not* used.

To extend `listings` for UTF-8 encoded sources, you can use the support from the package `listingsutf8` [11] by loading the library variant LIB listingsutf8.

```
\tcbuselibrary{listingsutf8}
\tcbset{listing utf8=latin1}% optional; `latin1' is the default.
```

This also loads the library LIB listings and the packages `listings` [6] and `listingsutf8` [11].

The `/tcb/listing engine` → P. 322 is set to `listings` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=listings}
```

16.1.3 Loading LIB minted

This library uses the package `minted` [12] to typeset listings. It is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{minted}
```

This also loads the package `minted` [12].

> **!** The `minted` package uses the external tool `Pygments` [14] to apply syntax highlighting. It has to be installed and set up, before the library can be used, see [12] and [14]. The `tcolorbox` library LIB minted does not work, if the package `minted` [12] does not work.

The `/tcb/listing engine` → P. 322 is set to `minted` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=minted}
```

16.2 Common Macros of the Libraries

`\begin{tcblisting}{`⟨*options*⟩`}`
  ⟨*environment content*⟩
`\end{tcblisting}`

Creates a colored box based on a `tcolorbox` → P. 12. Controlled by the given ⟨*options*⟩, the environment content is typeset normally and/or as a listing. Furthermore, the ⟨*options*⟩ control appearance and functions of the `tcolorbox`. By default, the listing is interpreted as a LaTeX listing.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{tcblisting}
```

```
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
```

This is a LaTeX example which displays the text as source code and in compiled form.

```
% \tcbuselibrary{listings} /or/ \tcbuselibrary{listingsutf8}
\begin{tcblisting}{colback=yellow!5,colframe=yellow!50!black,listing only,
    title=This is source code in another language (XML), fonttitle=\bfseries,
  listing options={language=XML,columns=fullflexible,keywordstyle=\color{red}}}
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
\end{tcblisting}
```

This is source code in another language (XML)

```
<?xml version="1.0"?>
<project name="Package␣tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
```

```
% \tcbuselibrary{minted}
\begin{tcblisting}{colback=yellow!5,colframe=yellow!50!black,listing only,
    title=This is source code in another language (XML), fonttitle=\bfseries,
  listing engine=minted,minted language=xml}
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
\end{tcblisting}
```

This is source code in another language (XML)

```
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
```

```
% This box is as wide as needed (listing only !!)
% \tcbuselibrary{skins}
\begin{tcblisting}{colback=green!5!white,colframe=green!50!black,listing only,
  hbox,enhanced,drop fuzzy shadow,before=\begin{center},after=\end{center}}
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
\end{tcblisting}
```

```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

```
\begin{tcboutputlisting}
  ⟨environment content⟩
\end{tcboutputlisting}
```

Saves the environment content to a file which is named by the key value of `listing file`. Later, this file can be loaded by `\tcbinputlisting` or `\tcbuselistingtext` or `\tcbuselistinglisting`.

```
\begin{tcboutputlisting}
This \textbf{text} is written to a standardized file for later usage.
\end{tcboutputlisting}
```

`\tcbinputlisting{⟨options⟩}`

Creates a colored boxed based on a `tcolorbox`. The text content is read from a file named by the key value of `listing file`. Apart from that, the function is equal to that of `tcblisting` → P. 311.

```
\tcbinputlisting{colback=red!5!white,colframe=red!75!black,text only}
\tcbinputlisting{colback=green!5,colframe=green!75!black,listing only}
```

```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

`\tcbuselistingtext`

Loads text from a file named by the key value of `listing file`.

```
\tcbuselistingtext
```

`\tcbuselistinglisting`

Typesets text as listing from a file named by the key value of `listing file`.

```
\tcbuselistinglisting
```

```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

`\tcbusetemplisting`

Typesets text as listing from a temporary file which was written by `tcbwritetemp` → P. 129.

! See Section 23.4 on page 457 and Section 23.5 on page 459 for more elaborate methods to create new environments and commands.

! If a new sort of **tcblisting** environments should be created with one optional argument only, one is highly recommended to use `\DeclareTCBListing` → P. 457 or `\NewTCBListing` → P. 457 instead of `\newtcblisting` to avoid content scanning problems.

`\newtcblisting`[⟨*init options*⟩]{⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Creates a new environment ⟨*name*⟩ based on `tcblisting` → P. 311. Basically, `\newtcblisting` operates like `\newenvironment`. This means, the new environment ⟨*name*⟩ optionally takes ⟨*number*⟩ arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying **tcblisting**. Note that `/tcb/savedelimiter` → P. 26 is set to the given ⟨*name*⟩ automatically. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.

```
\newtcblisting{mybox}{%
  colback=red!5!white,
  colframe=red!75!black}

\begin{mybox}
This is my \LaTeX\ box.
\end{mybox}
```

This is my \LaTeX\ box.

This is my LaTeX box.

```
\newtcblisting{mybox}[1]{%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=#1}

\begin{mybox}{Listing Box}
This is my \LaTeX\ box.
\end{mybox}
```

Listing Box

This is my \LaTeX\ box.

This is my LaTeX box.

```
\newtcblisting{mybox}[2][]{%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=#2,#1}

\begin{mybox}[listing only]
  {Listing Box}
This is my \LaTeX\ box.
\end{mybox}
\bigskip

\begin{mybox}[listing side text]
  {Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
```

Listing Box

This is my \LaTeX\ box.

Listing Box

This is my \LaTeX\ box.

This is my LaTeX box.

Definition in the preamble:

```
\newtcblisting[auto counter]{mycbox}[1]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Listing \thetcbcounter: #1}
```

```
\begin{mycbox}{Listing Box}
This is my \LaTeX\ box.
\end{mycbox}
```

Listing 1: Listing Box

This is my \LaTeX\ box.

This is my LaTeX box.

\renewtcblisting[⟨*init options*⟩]{⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Operates like \newtcblisting → P. 314, but based on \renewenvironment instead of \newenvironment. An existing environment is redefined.

`\newtcbinputlisting[⟨init options⟩]{\⟨name⟩}[⟨number⟩][⟨default⟩]{⟨options⟩}`

Creates a new macro \⟨*name*⟩ based on `\tcbinputlisting` → P. 313. Basically, `\newtcbinputlisting` operates like `\newcommand`. The new macro \⟨*name*⟩ optionally takes ⟨*number*⟩ arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying `tcbinputlisting`. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
          {\jobname.tcbtemp}
```

Listing (2) of `tcolorbox.tcbtemp`

This is the included file content:

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
          {\jobname.tcbtemp}
```

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing engine=minted,minted language=latex,minted style=colorful,
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
          {\jobname.tcbtemp}
```

Listing (3) of `tcolorbox.tcbtemp`

This is the included file content:

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing engine=minted,minted language=latex,minted style=colorful,
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
          {\jobname.tcbtemp}
```

`\renewtcbinputlisting[⟨init options⟩]{\⟨name⟩}[⟨number⟩][⟨default⟩]{⟨options⟩}`

Operates like `\newtcbinputlisting`, but based on `\renewcommand` instead of `\newcommand`. An existing macro is redefined.

16.3 Option Keys of the listings Library

/tcb/listing options=⟨*key list*⟩ (no default, initially `style=tcblatex`)

Sets the options from the package `listings` [6] which are used during typesetting of the listing. For LaTeX listings, there is a predefined `listings` style named `tcblatex` which can be used.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!25,left=6mm,
listing options={style=tcblatex,numbers=left,numberstyle=\tiny\color{red!75!black}}}
This is a \LaTeX\ example which displays the text as source code
and in compiled form. Additionally, we use line numbers here.
\end{tcblisting}
```

```
1 This is a \LaTeX\ example which displays the text as source code
2 and in compiled form. Additionally, we use line numbers here.
```

This is a LaTeX example which displays the text as source code and in compiled form. Additionally, we use line numbers here.

/tcb/no listing options (no value, initially unset)

Abbreviation for `listing options={}`. This removes all options for the `listings` package. This includes the `tcblisting` standard style `tcblatex` and the encoding presets. Use this option, if you want to set the `listings` options outside of `tcblisting`, e. g. globally in the preamble.

```
\begin{tcblisting}{no listing options}
All \textit{listings} options removed.
\end{tcblisting}
```

```
All \textit{listings} options removed.
```

All *listings* options removed.

/tcb/listing style=⟨*style*⟩ (no default, initially `tcblatex`)

Abbreviation for `listing options={style=...}`. This key sets a ⟨*style*⟩ for the `listings` package, see [6]. For LaTeX, there is a predefined style named `tcblatex`.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,
listing style=tcblatex}
Here, we use the predefined style.
\end{tcblisting}
```

```
Here, we use the predefined style.
```

Here, we use the predefined style.

/tcb/listing inputencoding=⟨*encoding*⟩ (no default, initially `\inputencodingname`)

Sets the input encoding value for the predefined listing style `tcblatex` and `tcbdocumentation` from the library LIB documentation. The initial value is derived from the package `inputenc` if used.

/tcb/listing remove caption=true|false (default `true`, initially `true`)

If set to `true`, some part of the caption building code of the `listings` package is silenced to prevent some unwanted interaction with the `hyperref` package resulting in additional vertical space. If set to `false`, the `listings` package code is kept unchanged. Note that listings outside `tcblisting`→ P. 311 and `\tcbinputlisting`→ P. 313 are always processed normally. Typically, a user is not expected to use this key at all.

/tcb/every listing line=⟨*text*⟩ (no default, initially unset/empty)

Inserts some ⟨*text*⟩ to the begin of every line of a listing. Note that this a hack of the `listings` package code. This may become unusable or superfluous in the future.

```
\newtcblisting{commandshell}{colback=black,colupper=white,colframe=yellow!75!black,
  listing only,listing options={style=tcblatex,language=sh},
  every listing line={\textcolor{red}{\small\ttfamily\bfseries root \$> }}}

\begin{commandshell}
ls -al
cd /usr/lib
\end{commandshell}
```

```
root $> ls -al
root $> cd /usr/lib
```

/tcb/every listing line*=⟨*text*⟩ (no default, initially unset/empty)

Identical to `/tcb/every listing line` plus additional enlargement of `/tcb/rightupper`→ P. 41 by the width of ⟨*text*⟩. Therefore, this option has to be used after the geometry settings are done. This option is intended to be used in conjunction with `/tcb/hbox`→ P. 97.

```
\newtcblisting{commandshell}{colback=black,colupper=white,colframe=yellow!75!black,
  listing only,listing options={style=tcblatex,language=sh},hbox,
  every listing line*={\textcolor{red}{\small\ttfamily\bfseries root \$> }}}

\begin{commandshell}
ls -al
cd /usr/lib
\end{commandshell}
```

```
root $> ls -al
root $> cd /usr/lib
```

See further options in Section 16.6 on page 322.

! For an combined example of using `\lstinline` inside a `tcolorbox`, see `\DeclareTotalTCBox`→ P. 455.

16.4 Option Keys of the LIB listingsutf8 Library

> **!** The LIB listingsutf8 library is not needed (and troublesome) when using XeLaTeX or LuaLaTeX. Therefore, loading this library is automatically replaced by loading LIB listings only, if pdfLaTeX is *not* used.

The LIB listingsutf8 library is an extension of the LIB listings library, so all options from Section 16.3 on page 317 are applicable.

`/tcb/listing utf8`=⟨*one-byte-encoding*⟩ (style, no default, initially `latin1`)

Abbreviation for using `/tcb/listing inputencoding`→P. 318 together with UTF-8 support from the package `listingsutf8` [11]. This option is available only for the library variant LIB listingsutf8. The ⟨*one-byte-encoding*⟩ is one of the applicable encodings from [11], e. g. `latin1` which is the default.

Be aware that this means restriction to this specific ⟨*one-byte-encoding*⟩: e. g. `latin1` comprises umlauts and other accented characters, but not the Euro sign. If you want to use the `listings` package *and* «real» UTF-8 source code, then do *not* use LIB listingsutf8 but LIB listings with `/tcb/listing inputencoding`→P. 318`=utf8` *and* with specific manual hacks for specific UTF-8-encoded characters.

See further options in Section 16.6 on page 322.

16.5 Option Keys of the minted Library

/tcb/minted language=⟨*programming language*⟩ (no default, initially `latex`)

Sets a ⟨*programming language*⟩ known to `Pygments` [14].

```
\begin{tcblisting}{listing engine=minted,minted style=trac,
  minted language=java,
  colback=red!5!white,colframe=red!75!black,listing only}
    public class HelloWorld {
      // A `Hello World' in Java
      public static void main(String[] args) {
        System.out.println("Hello World!");
      }
    }
\end{tcblisting}
```

```
public class HelloWorld {
  // A `Hello World' in Java
  public static void main(String[] args) {
    System.out.println("Hello World!");
  }
}
```

U 2017-07-05 **/tcb/minted options=**⟨*key list*⟩ (no default, initially `tabsize=2,fontsize=\small,breaklines,autogobble`)

Sets the options from the package `minted` [12] which are used during typesetting of the listing.

```
% \tcbuselibrary{skins}
\newtcblisting{myjava}{listing engine=minted,
  minted style=colorful,
  minted language=java,
  minted options={fontsize=\small,breaklines,autogobble,linenos,numbersep=3mm},
  colback=blue!5!white,colframe=blue!75!black,listing only,
  left=5mm,enhanced,
  overlay={\begin{tcbclipinterior}\fill[red!20!blue!20!white] (frame.south west)
    rectangle ([xshift=5mm]frame.north west);\end{tcbclipinterior}}}

\begin{myjava}
  public class HelloWorld {
    // A `Hello World' in Java
    public static void main(String[] args) {
      System.out.println("Hello World!");
    }
  }
\end{myjava}
```

```
1 public class HelloWorld {
2   // A `Hello World' in Java
3   public static void main(String[] args) {
4     System.out.println("Hello World!");
5   }
6 }
```

/tcb/minted style=⟨*style*⟩ (no default, initially unset)

Sets a ⟨*style*⟩ known to `Pygments` [14]. This is independent from `/tcb/minted options`→ P. 320. Note that styles are always applied globally; all following examples will be set in the given ⟨*style*⟩ until a new style is set. Also note that setting `\usemintedstyle{`⟨*style*⟩`}` only once per document is more economic, if all styles in a document are the same. For examples of different styles, see `/tcb/minted language`→ P. 320 and `/tcb/minted options`→ P. 320.

See further options in Section 16.6 on the next page.

16.6 Common Option Keys of all Libraries

For the ⟨*options*⟩ in `tcblisting` → P. 311 respectively `\tcbinputlisting` → P. 313 the following `pgf` keys can be applied. The key tree path `/tcb/` is not to be used inside these macros.

`/tcb/listing engine=`⟨*engine*⟩ (no default)

Sets the ⟨*engine*⟩ which typesets the listings. Feasible values are

- `listings`, if library LIB listings or LIB listingsutf8 is loaded.
- `minted`, if library LIB minted is loaded.

`/tcb/listing file=`⟨*file name*⟩ (no default, initially `\jobname.listing`)

Sets the ⟨*file name*⟩ of the file which is used to save listings.

`/tcb/listing and text` (no value, initially set)

Typesets the environment content as listing in the upper part and as compiled text in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and text}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```

This is a LaTeX example.

`/tcb/text and listing` (no value)

Typesets the environment content as compiled text in the upper part and as listing in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text and listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

```
This is a \LaTeX\ example.
```

`/tcb/listing only` (no value)

Typesets the environment content as listing.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing only}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```

/tcb/text only (no value)

Typesets the environment content as compiled text.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text only}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

/tcb/comment=⟨*text*⟩ (no default, initially empty)

Records a comment with ⟨*text*⟩ as content. The comment is displayed e. g. in conjunction with **/tcb/listing and comment** → P. 326 and **/tcb/comment and listing** → P. 326.

```
\begin{tcblisting}{comment={This comment is really only a comment},
  colback=red!5!white,colframe=red!75!black}
This is a \textbf{tcolorbox}.
\end{tcblisting}
```

This is a **\textbf{tcolorbox}**.

This is a **tcolorbox**.

N 2014-11-17 **/tcb/comment only** (no value)

Typesets the environment content with the comment text.

```
\begin{tcblisting}{comment only,
  comment={This is a comment.},
  colback=red!5!white,colframe=red!75!black}
This is a \textbf{tcolorbox}.
\end{tcblisting}
```

This is a comment.

/tcb/image comment={⟨*options*⟩**}{**⟨*filename*⟩**}** (style, no default, initially unset)

Uses an image denoted by ⟨*filename*⟩ as *comment* for the listing. The image is included by the standard **\includegraphics** macro with given ⟨*options*⟩.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side comment,
  image comment={width=2.5cm}{example-image-a.pdf},center lower}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a **\LaTeX** example.



N 2014-11-14 **/tcb/tcbimage comment=**⟨*filename*⟩ (style, no default, initially unset)

Uses an image denoted by ⟨*filename*⟩ as *comment* for the listing. The image is included by the `\tcbincludegraphics` → P. 256 macro. The inclusion can be customized by `/tcb/comment style` → P. 326.

> **!** The library LIB skins is needed to apply this option.

```
% \tcbuselibrary{skins}
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side comment,
  righthand width=3cm,lower separated=false,
  tcbimage comment={example-image-a.pdf},
  comment style={size=fbox,colframe=blue,colback=blue!50,sharp corners,
    drop fuzzy shadow}}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```



N 2014-11-14 **/tcb/pdf comment=⟨*filename*⟩** (style, default listing file, initially unset)

Uses a PDF file denoted by ⟨*filename*⟩ as *comment* for the listing. The image is included by `\tcbincludepdf` → P. 258 inside a `tcbraster` → P. 290. The inclusion can be customized by `/tcb/comment style` → P. 326.

> **!** The libraries LIB skins and LIB raster are needed to apply this option.

```
% \tcbuselibrary{skins,raster}
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and comment,
  righthand width=3cm,lower separated=false,middle=1mm,
  pdf comment={tcolorbox-example.pdf},
  comment style={raster columns=3,graphics pages={1,2,3},
    colframe=blue,drop fuzzy shadow}}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```



N 2014-11-14 **/tcb/pdf extension=**⟨*extension*⟩ (no default, initially pdf)

Sets the PDF file name extension for /tcb/pdf comment→ P. 325 to ⟨*extension*⟩. Note that ⟨*extension*⟩ always overwrites any actual extension given inside /tcb/pdf comment→ P. 325.

N 2014-11-14 **/tcb/comment style=**⟨*options*⟩ (no default, initially empty)

Sets the ⟨*options*⟩ for /tcb/tcbimage comment→ P. 324 and /tcb/pdf comment→ P. 325. These are tcolorbox options to customize the colored box drawn around the image(s), also image options encapsulated by /tcb/graphics options→ P. 259, and tcbraster→ P. 290 options for /tcb/pdf comment→ P. 325.

/tcb/listing and comment (no value)

Typesets the environment content as listing in the upper part and a given comment in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and comment,
  comment={This is my comment. It may contain line breaks.\par
    It can even use the environment content
    \flqq\ignorespaces\tcbuselistingtext\unskip\frqq}}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```

This is my comment. It may contain line breaks.
It can even use the environment content «This is a LaTeX example.»

/tcb/comment and listing (no value)

Typesets a given comment in the upper part and the environment content as listing in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment and listing,
comment={This is my comment.}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is my comment.

```
This is a \LaTeX\ example.
```

/tcb/listing side text (style, no value)

Typesets the environment content side by side as listing in the left (upper) part and as compiled text in the right (lower) part. This is a shortcut for setting /tcb/listing and text → P. 322 and /tcb/sidebyside → P. 119.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a LaTeX example.

Note that sidebyside=false has to be added, if the setting of /tcb/listing side text is to be annihilated.

/tcb/text side listing (style, no value)

Typesets the environment content side by side as compiled text in the left (upper) part and as listing in the right (lower) part. This is a shortcut for setting /tcb/text and listing → P. 322 and /tcb/sidebyside → P. 119.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text side listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

This is a \LaTeX\ example.

/tcb/listing outside text (no value)

Typesets the environment content side by side as listing in a tcolorbox and as compiled text outside the box in the right part of the page. Nevertheless, the outside text is treated as *lower* part of the tcolorbox and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 119.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing outside text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a LaTeX example.

/tcb/text outside listing (no value)

Typesets the environment content side by side as listing in a `tcolorbox` and as compiled text outside the box in the left part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 119.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text outside listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

```
This is a \LaTeX\ example.
```

/tcb/listing side comment (style, no value)

Typesets the environment content side by side as listing in the left (upper) part and a given comment in the right (lower) part. This is a shortcut for setting `/tcb/listing and comment` → P. 326 and `/tcb/sidebyside` → P. 119.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side comment,
  righthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```

/tcb/comment side listing (style, no value)

Typesets the environment content side by side with a given comment in the left (upper) part and as listing in the right (lower) part. This is a shortcut for setting `/tcb/comment and listing` → P. 326 and `/tcb/sidebyside` → P. 119.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment side listing,
  lefthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```

/tcb/listing outside comment (no value)

Typesets the environment content side by side as listing in a `tcolorbox` and a given comment outside the box in the right part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 119.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing outside comment,
  righthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

/tcb/comment outside listing (no value)

Typesets the environment content side by side as listing in a `tcolorbox` and a given comment outside the box in the left part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 119.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment outside listing,
  lefthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

/tcb/listing above text (no value)

Typesets the environment content as listing in a `tcolorbox` and as compiled text outside and below the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and text is controlled by `/tcb/middle` → P. 43.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing above text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a LaTeX example.

N 2014-11-07 **/tcb/listing above* text** (no value)

Widely equal to `/tcb/listing above text`, but the outside text is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and text is controlled by `/tcb/after` → P. 81.

/tcb/text above listing (no value)

Typesets the environment content as listing in a `tcolorbox` and as compiled text outside and above the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and text is controlled by `/tcb/middle` → P. 43.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text above listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

```
This is a \LaTeX\ example.
```

N 2014-11-07 **/tcb/text above* listing** (no value)

Widely equal to `/tcb/text above listing`, but the outside text is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and text is controlled by `/tcb/before` → P. 81.

/tcb/listing above comment (no value)

Typesets the environment content as listing in a `tcolorbox` and a given comment outside and below the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and comment is controlled by `/tcb/middle` → P. 43.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing above comment,
  center lower,image comment={width=3cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```



N 2014-11-07 **/tcb/listing above* comment** (no value)

Widely equal to `/tcb/listing above comment`, but the outside comment is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and comment is controlled by `/tcb/after` → P. 81.

/tcb/comment above listing (no value)

Typesets the environment content as listing in a `tcolorbox` and a given comment outside and above the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and comment is controlled by `/tcb/middle` → P. 43.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment above listing,
  center lower,image comment={width=3cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```




```
This is a \LaTeX\ example.
```

N 2014-11-07 **/tcb/comment above* listing** (no value)

Widely equal to `/tcb/comment above listing`, but the outside comment is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and comment is controlled by `/tcb/before` → P. 81.

16.7 Option Keys for Processing and Full Document Examples

A complete LaTeX document including `\documentclass`, `\begin{document}` and `\end{document}` cannot be processed directly by `tcolorbox`. It always has to be compiled separately. There are two methods supported by the package to process and display such a full document example:

- Prepare and compile the example document independent from your main document. The source file and the resulting PDF file can be included into the main document afterwards. This is the most economic way since the example document can be left untouched after the example is complete.
- The other possibility is to compile the example on the fly while the main document is compiled. This way has some charm, because the example can be edited inside the main document. But be aware that the compilation of the example is issued on every run of the main document. Also, there are fewer degrees of freedom how the example is compiled.

For both methods, the resulting example PDF file can be included as a `/tcb/pdf comment` → P. 325.

The following example shows how to apply the first method. There already is a file `tcolorbox-example.tex` and a PDF file `tcolorbox-example.pdf`. Both of them are input partly by the following:

```
% \tcbuselibrary{breakable,skins,raster}
\tcbinputlisting{
  enhanced jigsaw,breakable,pad at break*=2mm,height fixed for=first and middle,
  lower separated=false,
  leftlower=0pt,rightlower=0pt,middle=0pt,
  colframe=red!50!black,colback=yellow!10!white,
  listing and comment,
  listing file={tcolorbox-example},
  listing options=
    {style=tcblatex,texcsstyle=*\color{red!70!black},firstline=20,lastline=85},
  after upper={\par\bigskip\texttt{\ldots}\par},
  pdf comment,
  comment style={drop lifted shadow,graphics pages={1,...,4}},
}
```

```
% arara: pdflatex: {  }
% arara: pdflatex: { synctex: yes }
%
\documentclass{article}
\usepackage{tikz,lipsum,lmodern}
\usepackage[most]{tcolorbox}

\begin{document}

%-----------------------------------------------------------
\section{Colored boxes}

\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black]
  My box.
\end{tcolorbox}

\begin{tcolorbox}[colback=blue!5!white,colframe=blue!75!black,title=My title]
  My box with my title.
\end{tcolorbox}

\begin{tcolorbox}[colback=green!5!white,colframe=green!75!black]
```

```
  Upper part of my box.
  \tcblower
  Lower part of my box.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!5!white,colframe=yellow!50!black,
  colbacktitle=yellow!75!black,title=My title]
  I can do this also with a title.
  \tcblower
  Lower part of my box.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!10!white,colframe=red!75!black,lowerbox=invisible,
  savelowerto=\jobname_ex.tex]
  Now, we play hide and seek. Where is the lower part?
  \tcblower
  I'm invisible until you find me.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!10!white,colframe=red!75!black,title=Here I am]
  \input{\jobname_ex.tex}
\end{tcolorbox}


\begin{tcolorbox}[enhanced,sharp corners=uphill,
    colback=blue!50!white,colframe=blue!25!black,coltext=yellow,
    fontupper=\Large\bfseries,arc=6mm,boxrule=2mm,boxsep=5mm,
    borderline={0.3mm}{0.3mm}{white}]
  Funny settings.
\end{tcolorbox}


\begin{tcolorbox}[enhanced,frame style image=blueshade.png,
  opacityback=0.75,opacitybacktitle=0.25,
  colback=blue!5!white,colframe=blue!75!black,
  title=My title]
  This box is filled with an external image.\par
  Title and interior are made partly transparent to show the image.
\end{tcolorbox}


\begin{tcolorbox}[enhanced,attach boxed title to top
    center={yshift=-3mm,yshifttext=-1mm},
  colback=blue!5!white,colframe=blue!75!black,colbacktitle=red!80!black,
  title=My title,fonttitle=\bfseries,
  boxed title style={size=small,colframe=red!50!black} ]

...
```

1 Colored boxes

My box.

My title

My box with my title.

Upper part of my box.

Lower part of my box.

My title

I can do this also with a title.

Lower part of my box.

Now, we play hide and seek. Where is the lower part?

Here I am

I'm invisible until you find me.

Funny settings.

My title

This box is filled with an external image.
Title and interior are made partly transparent to show the image.

My title

This box uses a *boxed title*. The box of the title can be formatted independently from the main box.

1

2 LaTeX-Examples

```
This is a \LaTeX\ example:
\begin{equation}
\sum\limits_{i=1}^n i = \frac{n(n+1)}{2}.
\end{equation}
```

This is a LaTeX example:

$$\sum_{i=1}^{n} i = \frac{n(n+1)}{2}. \tag{1}$$

Side by side

```
This is a \LaTeX\ example:
\begin{equation}
\sum\limits_{i=1}^n i =
    \frac{n(n+1)}{2}.
\end{equation}
```

This is a LaTeX example:

$$\sum_{i=1}^{n} i = \frac{n(n+1)}{2}. \tag{2}$$

3 Theorems

Theorem 3.1: Summation of Numbers

For all natural number n it holds:

$$\sum_{i=1}^{n} i = \frac{n(n+1)}{2}. \tag{3}$$

We have given Theorem 3.1 on page 2.

3.2 Theorem (Summation of Numbers): *For all natural number n it holds:*

$$\sum_{i=1}^{n} i = \frac{n(n+1)}{2}. \tag{4}$$

2

4 Watermarks

Box with a watermark picture

Here, you see my nice box with a picture as a watermark. This picture is automatically resized to fit the dimensions of my box. Instead of a picure, some text could be used or arbitrary graphical code. See the documentation for more options.

5 Boxes in boxes

Box

Box inside box

Box inside box inside box

And now for something completely different: Boxes!

This | is | another | box...

6 Breakable Boxes

Breakable box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae,

3

ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.
Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.
Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.
Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.
Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.
Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit.

4

N 2014-11-14 **/tcb/no process** (no default)

Removes all processing commands if set before.

N 2014-11-14 **/tcb/process code=⟨*code*⟩** (no default, initially empty)

Adds ⟨*code*⟩ which is executed during `\tcbinputlisting`→P. 313 and `tcblisting`→P. 311. At the time of executing the given ⟨*code*⟩, the listing is already written to `/tcb/listing file`→P. 322, but the colored box is not constructed yet. Its intended use is to process the listing somehow before displaying. The processing result can be used inside a `/tcb/comment`→P. 323. Several `/tcb/process code` options can be given which are processed in the given order. Typically, ⟨*code*⟩ is added by using the following styles `/tcb/run system command`, `/tcb/run pdflatex`, etc.

> **!** To use the further options, the compiler has to be called with the `-shell-escape` permission to authorize potentially dangerous system calls. Be warned that this is a security risk. Anyway, it's more economic to compile examples independent from the main document and to include them as shown in the previous pages.

N 2014-11-14 **/tcb/run system command=⟨*system command*⟩** (style, no default, initially unset)

Runs a ⟨*system command*⟩, if the document is compiled with the `-shell-escape` permission. The current listing file can be accessed as `\filename@area\filename@base\filename@ext`. This ⟨*system command*⟩ is added to `/tcb/process code`.

N 2014-11-14
U 2016-05-27 **/tcb/compilable listing** (style, no default)

Sets `/tcb/listing file`→P. 322 to `\jobname-listing-`⟨*counter*⟩.

> **!** The default `/tcb/listing file`→P. 322 setting cannot be used to compile a listing, since the base name equals the `\jobname` and the included PDF files should be unique. Therefore, to use `/tcb/run pdflatex` etc., the `/tcb/listing file`→P. 322 has to be set to a unique value. One may use `/tcb/compilable listing` for this purpose.

N 2014-11-14 **/tcb/run pdflatex=⟨*arguments*⟩** (style, no default, initially unset)

Issues a `pdflatex` compilation of the listing with the given ⟨*arguments*⟩.

- The main document has to be compiled with the `-shell-escape` permission.
- The `/tcb/listing file`→P. 322 has to be unique for the listing.
- If the listing has to be compiled twice, add `run pdflatex` two times to the option list.

```
\begin{tcblisting}{enhanced jigsaw,lower separated=false,
  leftlower=0pt,rightlower=0pt,
  colframe=red!50!black,colback=yellow!10!white,
  listing options={style=tcblatex,texcsstyle=*\color{red!70!black}},
  listing and comment,
  pdf comment,freeze pdf,
  compilable listing,
  run pdflatex
}
\documentclass{beamer}
\usetheme{Warsaw}
\begin{document}
\begin{frame}{Beamer example}
  \begin{block}{Hello World}
    \begin{itemize}[<+->]
      \item One
      \item Two
    \end{itemize}
  \end{block}

  \begin{alertblock}{Integral}
```

```
    \begin{equation}
      \visible<3->{\int\limits_1^x \frac{1}{t}~dt}
      \visible<4->{ = \ln(x).}
    \end{equation}
  \end{alertblock}
\end{frame}
\end{document}
\end{tcblisting}
```

```
\documentclass{beamer}
\usetheme{Warsaw}
\begin{document}
\begin{frame}{Beamer example}
  \begin{block}{Hello World}
    \begin{itemize}[<+->]
      \item One
      \item Two
    \end{itemize}
  \end{block}

  \begin{alertblock}{Integral}
    \begin{equation}
      \visible<3->{\int\limits_1^x \frac{1}{t}~dt}
      \visible<4->{ = \ln(x).}
    \end{equation}
  \end{alertblock}
\end{frame}
\end{document}
```



N 2014-11-14 **/tcb/run xelatex=**⟨*arguments*⟩ (style, no default, initially unset)

Issues a `xelatex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run lualatex=**⟨*arguments*⟩ (style, no default, initially unset)

Issues a `lualatex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run makeindex=**⟨*arguments*⟩ (style, no default, initially unset)

Issues a `makeindex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run bibtex=**⟨*arguments*⟩ (style, no default, initially unset)

Issues a `bibtex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run biber=**⟨*arguments*⟩ (style, no default, initially unset)

Issues a `biber` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run arara=**⟨*arguments*⟩ (style, no default, initially unset)

Issues an `arara` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run latex=**⟨*arguments*⟩ (style, no default, initially unset)

Issues a `latex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run dvips=**⟨*arguments*⟩ (style, no default, initially unset)

Issues a `dvips` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run ps2pdf=**⟨*arguments*⟩ (style, no default, initially unset)

Issues a `ps2pdf` compilation of the listing with the given ⟨*arguments*⟩.

```
\begin{tcblisting}{enhanced jigsaw,
  title={PSTricks with pdflatex},fonttitle=\bfseries,
  colframe=red!50!black,colback=yellow!10!white,
  listing options={style=tcblatex,texcsstyle=*\color{red!70!black}},
  lower separated=false,middle=0pt,
  listing side comment,righthand width=4cm,
  compilable listing,
  run latex,run dvips,run ps2pdf,
  pdf comment,freeze pdf,
  comment style={raster columns=1,
    graphics options={viewport=0.5in 7.7in 3.5in 10.5in,clip}},
}
\documentclass{article}
\usepackage{pstricks,multido}
\begin{document}
\psset{unit=3}%
\multido{\nHue=0.01+0.01}{100}{%
\definecolor{MyColor}{hsb}{\nHue,1,1}%
\pscircle[linewidth=0.01,linecolor=MyColor]{\nHue}}
\end{document}
\end{tcblisting}
```

PSTricks with pdflatex

```
\documentclass{article}
\usepackage{pstricks,multido}
\begin{document}
\psset{unit=3}%
\multido{\nHue=0.01+0.01}{100}{%
\definecolor{MyColor}{hsb}{\nHue,1,1}%
\pscircle[linewidth=0.01,linecolor=MyColor]{\nHue}}
\end{document}
```



For most applications, you will like to add /tcb/freeze pdf as option, since the included pdf file is only refreshed, if the source for this file has changed.

N 2016-07-14 **/tcb/freeze file=⟨*file*⟩** (no default, initially unset)

Observes some ⟨*file*⟩, usually the final file produced by /tcb/process code→P. 335, /tcb/run system command→P. 335, /tcb/run pdflatex→P. 335, etc. If the MD5 checksum of the current /tcb/listing file→P. 322 is unchanged and ⟨*file*⟩ exists, the processing is skipped and the ⟨*file*⟩ is kept (frozen). Typically, the style /tcb/freeze pdf can be used for convenience.

N 2016-07-14 **/tcb/freeze none** (no default, initially set)

Freeze no file and always execute the given process commands.

N 2016-07-14 **/tcb/freeze extension=⟨*text*⟩** (style, no default)

Calls /tcb/freeze file with the current /tcb/listing file→P. 322 stripped with its extension plus ⟨*text*⟩ as new extension.

```
...
listing file=myfile.tex,
freeze extension=-modified.pdf,    % ->   myfile-modified.pdf   is observed
...
```

N 2016-07-14 **/tcb/freeze pdf** (no value)

Calls /tcb/freeze file with the current /tcb/listing file→P. 322 stripped with its extension plus .pdf as new extension.

N 2016-07-14 **/tcb/freeze png** (no value)

Calls /tcb/freeze file with the current /tcb/listing file→P. 322 stripped with its extension plus .png as new extension. See the examples for /tcb/run pdflatex→P. 335 and /tcb/run ps2pdf→P. 337.

N 2016-07-14 **/tcb/freeze jpg** (no value)

Calls /tcb/freeze file with the current /tcb/listing file→P. 322 stripped with its extension plus .jpg as new extension.

16.8 Creation of LaTeX Tutorials

The following source code gives a guideline for the creation of LaTeX tutorials. In the next section, a framework for LaTeX exercises is described. All examples shall be numbered optionally.

Firstly, some additional `tcb` keys are defined for the appearance. For the examples, three environments `texexp`, `texexptitled`, and `texexptitledspec` are defined with automatic numbering.

- `texexp` is used for untitled examples,
- `texexptitled` is used for titled examples,
- `texexptitledspec` is used for titled examples with special treatment.

Definition in the preamble:

```
\tcbset{
  texexp/.style={colframe=red!50!yellow!50!black, colback=red!50!yellow!5!white,
      coltitle=red!50!yellow!3!white,
      fonttitle=\small\sffamily\bfseries, fontupper=\small, fontlower=\small},
  example/.style 2 args={texexp,
      title={Example \thetcbcounter: #1},label={#2}},
}


\newtcblisting{texexp}[1]{texexp,#1}
\newtcblisting[auto counter,number within=section]{texexptitled}[3][]{%
  example={#2}{#3},#1}
\newtcolorbox[use counter from=texexptitled]{texexptitledspec}[3][]{%
  example={#2}{#3},#1}
```

```
\begin{tcblisting}{texexp}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{tcblisting}
```

```
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
```

This is a LaTeX example which displays the text as source code and in compiled form.

```
\begin{texexptitled}{First example with a title line}{firstExample}
Here, we use Example \ref{firstExample} with a title line.
\end{texexptitled}
```

Example 16.1: First example with a title line

```
Here, we use Example \ref{firstExample} with a title line.
```

Here, we use Example 16.1 with a title line.

```
\begin{texexp}{}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{texexp}
```

```
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
```

This is a LaTeX example which displays the text as source code and in compiled form.

```
\begin{texexp}{text and listing}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{texexp}
```

This is a LaTeX example which displays the text as source code and in compiled form.

```
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
```

```
\begin{texexp}{listing only}
This is a \LaTeX\ example which displays the text as source code only.
\end{texexp}
```

```
This is a \LaTeX\ example which displays the text as source code only.
```

```
\begin{texexp}{text only}
This is a \LaTeX\ example which displays the text in compiled form only.
\end{texexp}
```

This is a LaTeX example which displays the text in compiled form only.

```
\begin{texexptitled}{An Example with a Heading}{heading1}
This is a \LaTeX\ example with a numbered heading line
which can be referred to.
\end{texexptitled}
Here, we see Example \ref{heading1}.
```

Example 16.2: An Example with a Heading

```
This is a \LaTeX\ example with a numbered heading line
which can be referred to.
```

This is a LaTeX example with a numbered heading line which can be referred to.

Here, we see Example 16.2.

```
\begin{texexptitled}[listing only]{Another Example with a Heading}{heading2}
The keys can be used in combination. Here, an example with a heading line
and source code only is given.
\end{texexptitled}
Here, we see Example \ref{heading2}.
```

Example 16.3: Another Example with a Heading

The keys can be used in combination. Here, an example with a heading line and source code only is given.

Here, we see Example 16.3.

```
\begin{texexptitled}[float]{A floating Example with a Heading}{heading3}
This is another \LaTeX\ example with numbered heading line.
But now, the box is a floating object.
\end{texexptitled}
```

Example 16.4: A floating Example with a Heading

This is another \LaTeX\ example with numbered heading line.
But now, the box is a floating object.

This is another LaTeX example with numbered heading line. But now, the box is a floating object.

```
The floating box of the last example is seen as Example \ref{heading3}
on page \pageref{heading3}.
```

The floating box of the last example is seen as Example 16.4 on page 341.

```
\begin{texexptitledspec}{Special application}{texexpbox1}
\begin{lstlisting}[style=tcblatex]
Some \LaTeX\ source code.
\end{lstlisting}
\tcblower
For special cases, the environment |texexptitledspec| with style
|example| can be used directly. As one can see, the upper and the lower
part of the box can be used uncoupled also.
\end{texexptitledspec}
```

Example 16.5: Special application

Some \LaTeX\ source code.

For special cases, the environment `texexptitledspec` with style `example` can be used directly. As one can see, the upper and the lower part of the box can be used uncoupled also.

The following series of examples demonstrate the application of `tcolorbox`→ P. 12 options for diversification.

```
\begin{texexptitled}{How to use options (1):\par The basic example}{options1}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 16.6: How to use options (1): The basic example

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{texexptitled}[center lower,enhanced,segmentation hidden,middle=0mm]
  {How to use options (2):\par The text output is centered and the
    segmentation line has vanished.}{options2}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 16.7: How to use options (2): The text output is centered and the segmentation line has vanished.

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{texexptitled}[tikz lower,bicolor,colbacklower=white]
  {How to use options (3):\par Here, the |tikzpicture| is totally hidden.
    The |bicolor| skin highlights the output.}{options3}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{texexptitled}
```

Example 16.8: How to use options (3):
Here, the `tikzpicture` is totally hidden. The `bicolor` skin highlights the output.

```
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
```



```
\begin{texexptitled}[center lower,listing side text,righthand width=3.5cm,
  bicolor,colbacklower=white]
  {How to use options (4):\par The |bicolor| skin also works with side
   by side mode}{options4}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 16.9: How to use options (4):
The `bicolor` skin also works with side by side mode

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{texexptitled}[center lower,listing outside text,righthand width=3.5cm]
  {How to use options (5):\par Putting our picture outside is just
    a matter of one word.}{options5}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 16.10: How to use options (5): Putting our picture outside is just a matter of one word.

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{texexptitled}[center lower,text above listing]
  {How to use options (6):\par The picture may also be put above
    the listing box.}{options6}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```



Example 16.11: How to use options (6): The picture may also be put above the listing box.

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
```

```
\begin{texexptitled}[beamer,center lower,text outside listing,lefthand width=3.5cm]
  {How to use options (7):\par Our style is easily transformed into
    a beamerish one.}{options7}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```



Example 16.12: How to use options (7):
Our style is easily transformed into a beamerish one.

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
```

16.9 Creation of LaTeX Exercises

In the following, a guideline is given for the creation of LaTeX exercises with solutions. These solutions are saved to disk for application at a place of choice. Therefore, all used exercises are logged to a file `\jobname.records` for automatic processing. The solution contents themselves are saved to a subdirectory named `solutions`. Also see Section 8 on page 131.

- Before the first exercise is given, `\tcbstartrecording`→P. 131 has to be called to start recording.
- The solution is given as content of a `tcboutputlisting`→P. 313 environment. Note, that you can use this content also inside the exercise with `\tcbuselistingtext`→P. 313 in compiled form.
- After the last exercise is given (and before using the solutions), `\tcbstoprecording`→P. 131 has to be called to stop recording.
- The solutions are loaded by `\tcbinputrecords`→P. 131.

Inside the exercise text, there may be text parts which are needed as LaTeX source code and as compiled text as well. These parts can be saved by `tcbwritetemp`→P. 129 and used in compiled form by `\tcbusetemp`→P. 129 or as source code by `\tcbusetemplisting`→P. 313.

At first, we generate some a common style for the exercises and the solutions. Further, since exercises and solutions should be numbered, we force to use a label ⟨*marker*⟩. Automatically, the label `exe:`⟨*marker*⟩ is used to mark the exercise and the label `sol:`⟨*marker*⟩ is used to mark the solution.

```
\tcbset{texercisestyle/.style={arc=0.5mm, colframe=blue!25!yellow!90!white,
  colback=blue!25!yellow!5!white, coltitle=blue!25!yellow!40!black,
  fonttitle=\small\sffamily\bfseries, fontupper=\small, fontlower=\small,
  listing options={style=tcblatex,texcsstyle=*\color{red!40!black}},
}}
```

With these preparations, the kernel environment `texercise` for our exercises is created quickly:

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section,list inside=exam]{texercise}[2][]{%
  texercisestyle,
  listing file={solutions/texercise\thetcbcounter.tex},
  label={exe:#2},
  record={\string\processsol{solutions/texercise\thetcbcounter.tex}{#2}},
  title={Exercise \thetcbcounter\hfill\mdseries Solution on page \pageref{sol:#2}},
  list text={Exercise with solution on page \pageref{sol:#2}},#1}
```

The following examples demonstrate the application.

```
\tcbstartrecording
```

```
\begin{texercise}{tabular_example}
\textit{Create the following table:}\par\smallskip%
\begin{tcboutputlisting}
\begin{tabular}{|p{3cm}|p{3cm}|p{3cm}|p{3cm}|}\hline
\multicolumn{4}{|c|}{\bfseries\itshape Das alte Italien}\\\hline
\multicolumn{2}{|c|}{\bfseries Antike} &
\multicolumn{2}{c|}{\bfseries Mittelalter}\\\hline
\multicolumn{1}{|c|}{\itshape Republik}&
\multicolumn{1}{c|}{\itshape Kaiserreich}&
\multicolumn{1}{c|}{\itshape Franken}&
\multicolumn{1}{c|}{\itshape Teilstaaten}\\\hline
In den Zeiten der r\"{o}mischen Republik standen dem Staat jeweils zwei
Konsuln vor, deren Machtbefugnisse identisch waren. &
Das r\"{o}mische Kaiserreich wurde von einem Alleinherrscher, dem Kaiser,
regiert.
& In der V\"{o}lkerwanderungszeit \"{u}bernahmen die Goten und sp\"{a}ter die
Franken die Vorherrschaft.
& Im sp\"{a}teren Mittelalter regierten F\"{u}rsten einen Fleckenteppich
von Einzelstaaten.\\\hline
\end{tabular}
\end{tcboutputlisting}
\tcbuselistingtext%
\end{texercise}
```

Exercise 16.1 Solution on page 350

Create the following table:

Das alte Italien			
Antike		**Mittelalter**	
Republik	*Kaiserreich*	*Franken*	*Teilstaaten*
In den Zeiten der römischen Republik standen dem Staat jeweils zwei Konsuln vor, deren Machtbefugnisse identisch waren.	Das römische Kaiserreich wurde von einem Alleinherrscher, dem Kaiser, regiert.	In der Völkerwanderungszeit übernahmen die Goten und später die Franken die Vorherrschaft.	Im späteren Mittelalter regierten Fürsten einen Fleckenteppich von Einzelstaaten.

```
\begin{texercise}{macro_oneparam}
\begin{tcboutputlisting}
\newcommand{\headingline}[1]{%
  \begin{center}\Large\bfseries #1\end{center}}
\end{tcboutputlisting}
\tcbuselistingtext%

Create a new macro \verb+\headingline+ which produces the
following output:\par\smallskip
\begin{tcbwritetemp}
\headingline{Very important heading}
\end{tcbwritetemp}
\tcbusetemplisting\tcbusetemp%
\end{texercise}
```

Exercise 16.2 Solution on page 350

Create a new macro `\headingline` which produces the following output:

```
\headingline{Very important heading}
```

Very important heading

```
\begin{texercise}{macro_twoparam}
\begin{tcboutputlisting}
\newcommand{\minitable}[2]{%
  \begin{center}\begin{tabular}{p{10cm}}\hline%
  \multicolumn{1}{c}{\bfseries#1}\\\hline%
  #2\\\hline%
  \end{tabular}\end{center}}
\end{tcboutputlisting}
\tcbuselistingtext%
Create a new macro \verb+\minitable+ which produces the
following output:\par\smallskip
\begin{tcbwritetemp}
\minitable{My heading}{In this tiny tabular, there is only a heading
  and some text below which has a width of ten centimeters.}
\end{tcbwritetemp}
\tcbusetemplisting\par\smallskip\tcbusetemp%
\end{texercise}
```

Exercise 16.3 Solution on page 350

Create a new macro `\minitable` which produces the following output:

```
\minitable{My heading}{In this tiny tabular, there is only a heading
  and some text below which has a width of ten centimeters.}
```

My heading
In this tiny tabular, there is only a heading and some text below which has a width of ten centimeters.

```
\begin{texercise}{macro_threeparam}
\begin{tcboutputlisting}
\newcommand{\synop}[3]{%
  \begin{tabular}{@{}p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}|%
    p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}@{}}\hline
  \multicolumn{2}{c}{\bfseries #1}\\\hline
  \multicolumn{1}{c|}{\itshape English}&
  \multicolumn{1}{c}{\itshape German}\\\hline
  #2 & #3
  \end{tabular}}
\end{tcboutputlisting}
\tcbuselistingtext%
Create a new macro \verb+\synop+ which typesets a synoptic text according
to the following example. Base your macro on a tabular which takes the
total line width.\par\smallskip
\begin{tcbwritetemp}
\synop{Neil Armstrong}%
{That's one small step for a man, one giant leap for mankind.}%
{Das ist ein kleiner Schritt f\"{u}r einen Mann,
   ein riesiger Sprung f\"{u}r die Menschheit.}
\end{tcbwritetemp}
\tcbusetemplisting\par\smallskip\tcbusetemp%
\end{texercise}
```

Exercise 16.4 Solution on page 351

Create a new macro `\synop` which typesets a synoptic text according to the following example. Base your macro on a tabular which takes the total line width.

```
\synop{Neil Armstrong}%
{That's one small step for a man, one giant leap for mankind.}%
{Das ist ein kleiner Schritt f\"{u}r einen Mann,
   ein riesiger Sprung f\"{u}r die Menschheit.}
```

Neil Armstrong	
English	*German*
That's one small step for a man, one giant leap for mankind.	Das ist ein kleiner Schritt für einen Mann, ein riesiger Sprung für die Menschheit.

```
\tcbstoprecording
```

Now, we give a list of all exercises with:

```
\tcblistof[\subsection]{exam}{List of Exercises%
  \label{listofexercises}}
```

16.10 List of Exercises

16.1 Exercise with solution on page 350 347
16.2 Exercise with solution on page 350 348
16.3 Exercise with solution on page 350 348
16.4 Exercise with solution on page 351 349

16.11 Solutions for the given LaTeX Exercises

For all solutions, a macro `\processsol` was written to the file `\jobname.records`. Now, we need a definition for this macro to use the solutions.

```
% \usepackage{hyperref} % for phantomlabel
\newtcbinputlisting{\processsol}[2]{%
  texercisestyle,
  listing only,
  listing file={#1},
  phantomlabel={sol:#2},%
  title={Solution for Exercise \ref{exe:#2} on page \pageref{exe:#2}},
}
```

The loading of all solutions is done by:

```
\tcbinputrecords
```

With this, we get:

Solution for Exercise 16.1 on page 347

```
\begin{tabular}{|p{3cm}|p{3cm}|p{3cm}|p{3cm}|}\hline
\multicolumn{4}{|c|}{\bfseries\itshape Das alte Italien}\\\hline
\multicolumn{2}{|c|}{\bfseries Antike} &
\multicolumn{2}{c|}{\bfseries Mittelalter}\\\hline
\multicolumn{1}{|c|}{\itshape Republik}&
\multicolumn{1}{c|}{\itshape Kaiserreich}&
\multicolumn{1}{c|}{\itshape Franken}&
\multicolumn{1}{c|}{\itshape Teilstaaten}\\\hline
In den Zeiten der r\"{o}mischen Republik standen dem Staat jeweils zwei
Konsuln vor, deren Machtbefugnisse identisch waren. &
Das r\"{o}mische Kaiserreich wurde von einem Alleinherrscher, dem Kaiser,
regiert.
& In der V\"{o}lkerwanderungszeit \"{u}bernahmen die Goten und sp\"{a}ter die
Franken die Vorherrschaft.
& Im sp\"{a}teren Mittelalter regierten F\"{u}rsten einen Fleckenteppich
von Einzelstaaten.\\\hline
\end{tabular}
```

Solution for Exercise 16.2 on page 348

```
\newcommand{\headingline}[1]{%
  \begin{center}\Large\bfseries #1\end{center}}
```

Solution for Exercise 16.3 on page 348

```
\newcommand{\minitable}[2]{%
  \begin{center}\begin{tabular}{p{10cm}}\hline%
  \multicolumn{1}{c}{\bfseries#1}\\\hline%
  #2\\\hline%
  \end{tabular}\end{center}}
```

Solution for Exercise 16.4 on page 349

```
\newcommand{\synop}[3]{%
  \begin{tabular}{@{}p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}|%
    p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}@{}}\hline
  \multicolumn{2}{c}{\bfseries #1}\\\hline
  \multicolumn{1}{c|}{\itshape English}&
  \multicolumn{1}{c}{\itshape German}\\\hline
  #2 & #3
  \end{tabular}}
```

17 Library theorems

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{theorems}
```

This also loads the package amsmath.

17.1 Macros of the Library

U 2016-06-22 **\newtcbtheorem**[⟨*init options*⟩]{⟨*name*⟩}{⟨*display name*⟩}{⟨*options*⟩}{⟨*prefix*⟩}

Creates new environments ⟨*name*⟩ and ⟨*name*⟩* based on tcolorbox to frame a (mathematical) theorem. The ⟨*display name*⟩ is used in the title line with a number, e. g. «Theorem 5.1». The ⟨*options*⟩ are given to the underlying tcolorbox to control the appearance. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 on page 111. The new environment ⟨*name*⟩ takes one optional and two mandatory parameters. The optional parameter supplements the options and should be used only in rare cases. The first mandatory parameter is the title text for the theorem and is also set as /tcb/nameref → P. 102 identifier. The second mandatory parameter is a ⟨*marker*⟩. The theorem is automatically labeled with ⟨*prefix*⟩⟨*separator*⟩⟨*marker*⟩ where ⟨*separator*⟩ is predefined as ":", see /tcb/label separator → P. 359.
The new environment ⟨*name*⟩* takes one optional and one mandatory parameter and represents an unnumbered variant of the environment ⟨*name*⟩. This variant is not labeled and not listed in lists of theorems.

Definition in the preamble:

```
\newtcbtheorem[number within=section]{mytheo}{My Theorem}%
  {colback=green!5,colframe=green!35!black,fonttitle=\bfseries}{th}
```

```
% usage of `\nameref' needs `nameref' or `hyperref' to be loaded
\begin{mytheo}{This is my title}{theoexample}
  This is the text of the theorem. The counter is automatically assigned and,
  in this example, prefixed with the section number. This theorem is numbered with
  \ref{th:theoexample}, it is given on page~\pageref{th:theoexample},
  and it is titled \flqq\nameref{th:theoexample}\frqq.
\end{mytheo}
```

My Theorem 17.1: This is my title

This is the text of the theorem. The counter is automatically assigned and, in this example, prefixed with the section number. This theorem is numbered with 17.1, it is given on page 352, and it is titled «This is my title».

```
\begin{mytheo}[label=myownlabel]{This is my title}{}
  The label parameter can be left empty without \LaTeX\ error.
  Or you may use an own label to reference Theorem \ref{myownlabel}.
\end{mytheo}
```

My Theorem 17.2: This is my title

The label parameter can be left empty without LaTeX error. Or you may use an own label to reference Theorem 17.2.

```
\begin{mytheo}{}{}
  The title can also be left empty without problem. Note that the \enquote{:}
  vanished magically.
\end{mytheo}
```

My Theorem 17.3

The title can also be left empty without problem. Note that the “:” vanished magically.

```
\begin{mytheo*}{Unnumbered Theorem}
  This theorem is not numbered.
\end{mytheo*}
```

My Theorem: Unnumbered Theorem

This theorem is not numbered.

```
\begin{mytheo*}{}
  This theorem has no number and no title.
\end{mytheo*}
```

My Theorem

This theorem has no number and no title.

> ! To switch off the `nameref` feature permanently, add `nameref/.style={}` inside the ⟨*options*⟩ list.

`\renewtcbtheorem`[⟨*init options*⟩]{⟨*name*⟩}{⟨*display name*⟩}{⟨*options*⟩}{⟨*prefix*⟩}

Operates like `\newtcbtheorem` → P. 352, but based on `\renewenvironment` instead of `\newenvironment`. An existing environment is redefined.

`\tcbmaketheorem`{⟨*name*⟩}{⟨*display name*⟩}{⟨*options*⟩}{⟨*counter*⟩}{⟨*prefix*⟩}

> ! `\newtcbtheorem` → P. 352 supersedes this macro.

Creates a new environment ⟨*name*⟩ based on `tcolorbox` to frame a (mathematical) theorem. The ⟨*display name*⟩ is used in the title line with a number, e. g. «Theorem 5.1». The ⟨*options*⟩ are given to the underlying `tcolorbox` to control the appearance. The ⟨*counter*⟩ is used for automatic numbering. The new environment ⟨*name*⟩ takes one optional and two mandatory parameters. The optional parameter supplements the options and should be used only in rare cases. The first mandatory parameter is the title text for the theorem and the second mandatory parameter is a ⟨*marker*⟩. The theorem is automatically labeled with ⟨*prefix*⟩⟨*separator*⟩⟨*marker*⟩ where ⟨*separator*⟩ is predefined as “`:`”, see `/tcb/label separator` → P. 359.

deprecated

`\tcboxmath[⟨options⟩]{⟨mathematical box content⟩}`

Creates a `tcolorbox` → P. 12 which is fitted to the width of the given ⟨*mathematical box content*⟩. This box is intended to be applied as part of a larger formula and may be used as replacement for the `\boxed` macro of `amsmath`.

```
\begin{equation}
\tcbset{fonttitle=\scriptsize}
\tcboxmath[colback=LightBlue!25!white,colframe=blue]{ a^2 = 16 }
\quad \Rightarrow \quad
\tcboxmath[colback=Salmon!25!white,colframe=red,title=Implication]%
  { a = 4 ~\vee~ a=-4. }
\end{equation}
```

$$\boxed{a^2 = 16} \quad \Rightarrow \quad \boxed{\begin{array}{l}\text{Implication}\\ a = 4 \ \vee \ a = -4.\end{array}} \tag{3}$$

`\tcbhighmath[⟨options⟩]{⟨mathematical box content⟩}`

This is a special case of the `\tcboxmath` macro which uses the style `/tcb/highlight math` → P. 363. It is intended to provide context sensitive highlighting of formula parts. The color settings via `/tcb/highlight math style` → P. 363 may be different inside theorems or other colored areas and outside.

```
\tcbset{myformula/.style={colback=yellow!10!white,colframe=red!50!black,
  every box/.style={highlight math style={colback=LightBlue!50!white,colframe=Navy}}
  }}

\begin{align}
  \tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} &= \infty.\\
  \int x^2 ~\text{d}x                                  &= \frac13 x^3 + c.
\end{align}

\begin{tcolorbox}[ams align,myformula]
  \tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} &= \infty.\\
  \int x^2 ~\text{d}x                                  &= \frac13 x^3 + c.
\end{tcolorbox}
```

$$\boxed{\sum_{n=1}^{\infty} \frac{1}{n}} = \infty. \tag{4}$$

$$\int x^2 \ \mathrm{d}x = \frac{1}{3}x^3 + c. \tag{5}$$

$$\boxed{\sum_{n=1}^{\infty} \frac{1}{n}} = \infty. \tag{6}$$

$$\int x^2 \ \mathrm{d}x = \frac{1}{3}x^3 + c. \tag{7}$$

\tcbhighmath→ P. 354 can be used in symbiosis with the **empheq** package which allows to specify own boxing commands to mark multiline formulas.

```
% \usepackage{empheq}
\begin{empheq}[box=\tcbhighmath]{align}
a&=\sin(z)\\
E&=mc^2 + \int_a^b x\, dx
\end{empheq}

\tcbset{highlight math style={enhanced,
  colframe=red!60!black,colback=yellow!50!white,arc=4pt,boxrule=1pt,
  drop fuzzy shadow}}

\begin{empheq}[box=\tcbhighmath]{align}
a&=\sin(z)\\
E&=mc^2 + \int_a^b x\, dx
\end{empheq}
```

$$a = \sin(z) \tag{8}$$
$$E = mc^2 + \int_a^b x\, dx \tag{9}$$

$$a = \sin(z) \tag{10}$$
$$E = mc^2 + \int_a^b x\, dx \tag{11}$$

Besides \tcbhighmath→ P. 354, one can easily define an independent new box based on \tcbox→ P. 14 which acts like \tcbhighmath→ P. 354:

```
% \usepackage{empheq}
\newtcbox{\otherbox}[1][]{nobeforeafter,math upper,tcbox raise base,
  enhanced,frame hidden,boxrule=0pt,interior style={top color=green!10!white,
  bottom color=green!10!white,middle color=green!50!yellow},
  fuzzy halo=1pt with green,#1}

\begin{empheq}[box=\otherbox]{align}
a&=\sin(z)\\
E&=mc^2 + \int_a^b x\, dx
\end{empheq}

\begin{equation}
\tcbhighmath{E} = \otherbox{mc^2}
\end{equation}
```

$$a = \sin(z) \tag{12}$$
$$E = mc^2 + \int_a^b x\, dx \tag{13}$$

$$\boxed{E} = \boxed{mc^2} \tag{14}$$

17.2 Option Keys of the Library

/tcb/separator sign=⟨*sign*⟩ (no default, initially :)

The given ⟨*sign*⟩ is used inside the title text of a theorem as separater between display name combined with number and the specific title text. It is omitted, if there is no specific title text.

```
% \usepackage{amssymb}
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   separator sign={\ $\blacktriangleright$}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.4 ▶ My example

My theorem text.

/tcb/separator sign colon (style, no value, initially set)

Sets /tcb/separator sign to the default colon : sign.

/tcb/separator sign dash (style, no value)

Sets /tcb/separator sign to an en-dash sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   separator sign dash}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.5 – My example

My theorem text.

/tcb/separator sign none (style, no value)

Sets /tcb/separator sign to empty.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   separator sign none}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.6 My example

My theorem text.

/tcb/description delimiters={⟨*left*⟩}{⟨*right*⟩} (no default, initially empty)

The given ⟨*left*⟩ and ⟨*right*⟩ delimiter signs are used to frame the descriptive title text of a theorem.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description delimiters={\flqq}{\frqq}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.7: «My example»

My theorem text.

/tcb/description delimiters parenthesis (style, no value)

Sets `/tcb/description delimiters` to (and).

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description delimiters parenthesis}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.8: (My example)

My theorem text.

/tcb/description delimiters none (style, no value, initially set)

Sets `/tcb/description delimiters` to the default empty texts.

/tcb/description color=⟨*color*⟩ (default empty, initially empty)

Sets the ⟨*color*⟩ of the descriptive title text deviating from `/tcb/coltitle` → P. 28. The color is reset to `/tcb/coltitle` → P. 28, if `description color` is used without value.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description color=red!25!yellow}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.9: My example

My theorem text.

/tcb/description font=⟨*text*⟩ (default empty, initially empty)

Sets ⟨*text*⟩ (e. g. font settings) before the descriptive title text deviating from /tcb/fonttitle → P. 29. The ⟨*text*⟩ is removed, if description font is used without value.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description delimiters={\glqq}{\grqq},
   description font=\mdseries\itshape}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.10: *„My example“*

My theorem text.

/tcb/description formatter=⟨*macro*⟩ (default empty, initially empty)

Sets ⟨*macro*⟩ as formatter for the descriptive title text. The ⟨*macro*⟩ has to take one mandatory argument (the description text).

Note that /tcb/description delimiters → P. 357, /tcb/description color → P. 357, and /tcb/description font are ignored, if this option is used.

If description formatter is used without value, the formatter is reset to its standard behavior.

```
\newtcbox{\formbox}{enhanced,frame empty,size=minimal,boxsep=2pt,arc=1pt,
  on line,interior style image=goldshade.png}

\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description formatter=\formbox}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.11: **My example**

My theorem text.

/tcb/terminator sign=⟨*sign*⟩ (no default, initially empty)

The given ⟨*sign*⟩ is used as terminator at the end of the title text of a theorem.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   terminator sign={.}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.12: My example.

My theorem text.

/tcb/terminator sign colon (style, no value, initially set)

Sets /tcb/terminator sign → P. 358 to the colon : sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   separator sign dash,terminator sign colon}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.13 – My example:

My theorem text.

/tcb/terminator sign dash (style, no value)

Sets /tcb/terminator sign → P. 358 to an en-dash sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   terminator sign dash}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.14: My example –

My theorem text.

/tcb/terminator sign none (style, no value)

Sets /tcb/terminator sign → P. 358 to the default empty text.

N 2016-04-19 **/tcb/label separator=**⟨*separator*⟩ (no default, initially :)

The given ⟨*separator*⟩ is used for labels created with environments which are defined themselves by \newtcbtheorem → P. 352. This ⟨*separator*⟩ is put between ⟨*prefix*⟩ (defined by \newtcbtheorem → P. 352) and ⟨*marker*⟩ (defined by an actual theorem environment).

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   label separator=*}{theo}
\begin{sometheorem}{My example}{myex}
My theorem text.
\end{sometheorem}
See Example~\ref{theo*myex}.
```

Theorem 17.15: My example

My theorem text.

See Example 17.15.

N 2018-01-12 **/tcb/theorem full label supplement={⟨*style*⟩}** (no default, initially empty)

The given ⟨*style*⟩ is used in connection with labels created with environments which are defined themselves by \newtcbtheorem → P. 352. This ⟨*style*⟩ uses one argument which is automatically set to the full label marker of the environment, i.e. a text consisting of ⟨*prefix*⟩ (defined by \newtcbtheorem → P. 352), /tcb/label separator → P. 359, and ⟨*marker*⟩ (defined by an actual theorem environment).

```
% The following adds a hyper target to all environments
% created with \newtcbtheorem
\tcbset{theorem full label supplement={hypertarget={#1}}}

\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
   {colback=white,colframe=red!50!black,fonttitle=\bfseries}{theo}
\begin{sometheorem}{My example}{myex2}
My theorem text.
\end{sometheorem}
This automated \hyperlink{theo:myex2}{hyper target can be linked to with a
 hyper link}.
```

Theorem 17.16: My example

My theorem text.

This automated hyper target can be linked to with a hyper link.

A second usage of /tcb/theorem full label supplement overwrites the first setting.

N 2018-01-12 **/tcb/theorem label supplement={⟨*style*⟩}** (no default, initially empty)

The given ⟨*style*⟩ is used in connection with labels created with environments which are defined themselves by \newtcbtheorem → P. 352. This ⟨*style*⟩ uses one argument which is automatically set to the label ⟨*marker*⟩ defined by an actual theorem environment.
A second usage of /tcb/theorem label supplement overwrites the first setting, but /tcb/theorem full label supplement and /tcb/theorem label supplement can be used independently.

```
% `marginnote' has to be loaded
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
   {colback=white,colframe=red!50!black,fonttitle=\bfseries,
    theorem label supplement={hypertarget={XYZ-##1}},
    theorem full label supplement={code={\marginnote{##1}}}
   }{theo}
\begin{sometheorem}{My example}{myex3}
My theorem text.
\end{sometheorem}
This automated \hyperlink{XYZ-myex3}{hyper target can be linked to with a
 hyper link}.
```

theo:myex3

Theorem 17.17: My example

My theorem text.

This automated hyper target can be linked to with a hyper link.

/tcb/theorem name and number (style, no value, initially set)

Prints theorem name followed by theorem number inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   theorem name and number}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 17.18: My example

My theorem text.

/tcb/theorem number and name (style, no value)

Prints theorem number followed by theorem name inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   theorem number and name}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

17.19 Theorem: My example

My theorem text.

/tcb/theorem name (style, no value)

Prints theorem name without number inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   theorem name,enhanced,watermark text={\thetcbcounter}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem: My example

My theorem text. 17.20

`/tcb/theorem={⟨display name⟩}{⟨counter⟩}{⟨title⟩}{⟨marker⟩}` (no default)

This key is internally used by `\tcbmaketheorem` → P. 353, but can be used directly in a `tcolorbox` for a more flexible approach. The ⟨*display name*⟩ is used together with the increased ⟨*counter*⟩ value and the ⟨*title*⟩ for the title line of the box. Additionally, a `\label` with the given ⟨*marker*⟩ is created.

```
% \newcounter{texercise}%  preamble
\begin{tcolorbox}[colback=green!10,colframe=green!50!black,arc=4mm,
                  theorem={Test}{texercise}{Direct usage}{myMarker}]
Here, we see the test \ref{myMarker}.
\end{tcolorbox}
```

Test 1: Direct usage

Here, we see the test 1.

For a common appearance inside the document, the key `theorem` should not be used directly as in the example above, but as part of a new environment created by hand or using `\tcbmaketheorem` → P. 353 or using its successor `\newtcbtheorem` → P. 352.

/tcb/highlight math (style, no value)

A style which is used for \tcbhighmath → P. 354 and which is predefined as `notitle,nophantom,colframe=red,colback=yellow!25!white`.
It can be changed with the usual `pgf` techniques or with /tcb/highlight math style.

```
\begin{align*}
  \tcbhighmath{1} + 1 &= 2,\\
  \tcbset{highlight math/.append style={left=0mm,right=0mm,top=0mm,bottom=0mm}}
  \tcbhighmath{1} + 1 &= 2.
\end{align*}
```

$$\boxed{1} + 1 = 2,$$
$$\boxed{1} + 1 = 2.$$

/tcb/highlight math style=⟨*style definition*⟩ (style, no default)

Changes the definition for /tcb/highlight math to `notitle,nophantom` plus the given ⟨*style definition*⟩. See \tcbhighmath → P. 354 for another example.

```
% \tcbuselibrary{skins}
\tcbset{highlight math style={enhanced,%<-- needed for the `remember' options
  colframe=red,colback=red!10!white,boxsep=0pt}}
\begin{align*}
\tcbhighmath[remember as=fx]{f(x)}
     &= \int\limits_{1}^{x} \frac{1}{t^2}~dt
      = \left[ -\frac{1}{t} \right]_{1}^{x}\\
     &= -\frac{1}{x} + \frac{1}{1}\\
     &=
\tcbhighmath[remember,overlay={%
    \draw[blue,very thick,->] (fx.south) to[bend right] ([yshift=2mm]frame.west);}]
  {1-\frac{1}{x}.}
\end{align*}
```

$$\boxed{f(x)} = \int_1^x \frac{1}{t^2}\,dt = \left[-\frac{1}{t}\right]_1^x$$
$$= -\frac{1}{x} + \frac{1}{1}$$
$$= \boxed{1 - \frac{1}{x}.}$$

/tcb/math upper (style, no value)

Sets the upper part to mathematical mode with font `\displaystyle`.

/tcb/math lower (style, no value)

Sets the lower part to mathematical mode with font `\displaystyle`.

/tcb/math (style, no value)

Sets the upper part *and* lower part to mathematical mode with font `\displaystyle`.

```
\begin{tcolorbox}[math,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

> **!** The following styles are only tested to work with the original `amsmath` environments. If e.g. the `equation` environment is redefined as `gather`, then `/tcb/ams equation` should / could not be used. Obviously, you are encouraged to use `/tcb/ams gather` → P. 366 in this case.

U 2014-10-30 **/tcb/ams equation upper** (style, no value)

Adds an `amsmath` `equation` environment to the start and end of the upper part.

U 2014-10-30 **/tcb/ams equation lower** (style, no value)

Adds an `amsmath` `equation` environment to the start and end of the lower part.

U 2014-10-30 **/tcb/ams equation** (style, no value)

Adds an `amsmath` `equation` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams equation,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{15}$$

U 2014-10-30 **/tcb/ams equation* upper** (style, no value)

Adds an `amsmath` `equation*` environment to the start and end of the upper part.

U 2014-10-30 **/tcb/ams equation* lower** (style, no value)

Adds an `amsmath` `equation*` environment to the start and end of the lower part.

U 2014-10-30 **/tcb/ams equation*** (style, no value)

Adds an `amsmath` `equation*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams equation*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

/tcb/ams align upper (style, no value)

Adds an `amsmath` `align` environment to the start and end of the upper part.

/tcb/ams align lower (style, no value)

Adds an `amsmath` `align` environment to the start and end of the lower part.

/tcb/ams align (style, no value)

Adds an `amsmath` `align` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams align,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty.\\
  \int x^2 ~\text{d}x                    &= \frac13 x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{16}$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c. \tag{17}$$

/tcb/ams align* upper (style, no value)

Adds an `amsmath` `align*` environment to the start and end of the upper part.

/tcb/ams align* lower (style, no value)

Adds an `amsmath` `align*` environment to the start and end of the lower part.

/tcb/ams align* (style, no value)

Adds an `amsmath` `align*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams align*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty.\\
  \int x^2 ~\text{d}x                    &= \frac13 x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c.$$

/tcb/ams gather upper (style, no value)

Adds an `amsmath` `gather` environment to the start and end of the upper part.

/tcb/ams gather lower (style, no value)

Adds an `amsmath` `gather` environment to the start and end of the lower part.

/tcb/ams gather (style, no value)

Adds an `amsmath` `gather` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams gather,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 ~\text{d}x = \frac13 x^3 + c.
\end{tcolorbox}
```

$$\sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{18}$$

$$\int x^2 ~\text{d}x = \frac13 x^3 + c. \tag{19}$$

/tcb/ams gather* upper (style, no value)

Adds an `amsmath` `gather*` environment to the start and end of the upper part.

/tcb/ams gather* lower (style, no value)

Adds an `amsmath` `gather*` environment to the start and end of the lower part.

/tcb/ams gather* (style, no value)

Adds an `amsmath` `gather*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams gather*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 ~\text{d}x = \frac13 x^3 + c.
\end{tcolorbox}
```

$$\sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 ~\text{d}x = \frac13 x^3 + c.$$

/tcb/ams nodisplayskip upper (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the upper part. Note that the text content has to start with such a formula.

/tcb/ams nodisplayskip lower (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the lower part. Note that the text content has to start with such a formula.

/tcb/ams nodisplayskip (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the upper part *and* lower part. Note that the text content has to start with such a formula.

```
\begin{tcolorbox}[ams nodisplayskip,colback=yellow!10!white,colframe=red!50!black]
  \begin{gather}
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 ~\text{d}x = \frac13 x^3 + c.
  \end{gather}
  And now for something completely different.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{20}$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c. \tag{21}$$

And now for something completely different.

New colored mathematical environments are easily created using `\newtcolorbox`→ P. 15:

```
\newtcolorbox{mymath}{ams gather*,colback=yellow!10!white,colframe=red!50!black}

\begin{mymath}
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 ~\text{d}x = \frac13 x^3 + c.
\end{mymath}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c.$$

! All described options like `/tcb/ams gather upper`→ P. 366, `/tcb/ams gather lower`→ P. 366, `/tcb/ams gather`→ P. 366 are (partially) setting (overwritting) the keys `/tcb/before upper`→ P. 65, `/tcb/after upper`→ P. 66, `/tcb/before lower`→ P. 67, `/tcb/after lower`→ P. 68.
Therefore, e. g. `\tcbset{ams gather,before upper={\text{Pythagoras:}}}` produces an invalid result. For this case, you are invited to use
`\tcbset{ams gather,before upper app={\text{Pythagoras:}}}`,
see `/tcb/before upper app`→ P. 439.

`/tcb/theorem style=`⟨*name*⟩ (no default, initially `standard`)

Applies a predefined style ⟨*name*⟩ to the theorem environment. Some of the feasible ⟨*name*⟩ values resemble style names from the packages `theorem` and `ntheorem` to give convenient access to known patterns.

> **!** The styles alter `/tcb/separator sign` → P. 356, `/tcb/description delimiters` → P. 357, `/tcb/terminator sign` → P. 358, and more. Therefore, one should apply such keys *after* a theorem style.

For the following examples, we use:

Definition in the preamble:

```
\newtcbtheorem[use counter from=mytheo]{theorem}{Theorem}{%
  fonttitle=\bfseries\upshape,fontupper=\itshape,
  colframe=green!50!black,colback=green!10!white,
  colbacktitle=green!20!white,coltitle=blue!75!black}{theo}
```

The predefined styles are:

- `standard`: This is the initial value.

```
\begin{theorem}[theorem style=standard]{standard}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

Theorem 17.21: standard

This is my theorem.

$$a^2 + b^2 = c^2.$$

- `change standard`

```
\begin{theorem}[theorem style=change standard]{change standard}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

17.22 Theorem: change standard

This is my theorem.

$$a^2 + b^2 = c^2.$$

- `plain`

```
\begin{theorem}[theorem style=plain]{plain}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

Theorem 17.23 (plain): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **break**

```
\begin{theorem}[theorem style=break]{break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

Theorem 17.24 (break):
This is my theorem.

$$a^2 + b^2 = c^2.$$

- **plain apart**

```
\begin{theorem}[theorem style=plain apart]{plain apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

Theorem 17.25 (plain apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

- **change**

```
\begin{theorem}[theorem style=change]{change}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

17.26 Theorem (change): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **change break**

```
\begin{theorem}[theorem style=change break]{change break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

17.27 Theorem (change break):
This is my theorem.

$$a^2 + b^2 = c^2.$$

- **change apart**

```
\begin{theorem}[theorem style=change apart]{change apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

17.28 Theorem (change apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

- **margin**

```
\begin{theorem}[theorem style=margin,left=10mm]{margin}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
\begin{theorem}[theorem style=margin,left=10mm,oversize]{margin}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

17.29 Theorem (margin): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

17.30 Theorem (margin): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **margin break**

```
\begin{theorem}[theorem style=margin break,left=10mm]{margin break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
\begin{theorem}[theorem style=margin break,left=10mm,oversize]{margin break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

17.31 Theorem (margin break):
This is my theorem.

$$a^2 + b^2 = c^2.$$

17.32 Theorem (margin break):
This is my theorem.

$$a^2 + b^2 = c^2.$$

- **margin apart**

```
\begin{theorem}[theorem style=margin apart,left=10mm]{margin apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
\begin{theorem}[theorem style=margin apart,left=10mm,oversize]{margin apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

17.33 Theorem (margin apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

17.34 Theorem (margin apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

17.3 Examples for Definitions and Theorems

In the following, the application of \tcbmaketheorem→ P. 353 to highlight mathematical definitions, theorems, or the like is demonstrated.

At first, additional tcb keys are created for the appearance of the colored boxes. It is assumed that theorems and corollaries should be identically colored. All following environments are numbered with a common counter, but this can be changed easily. Here, the counter output is supplemented by the subsection number. Further, the cleveref package [5] is used for clever references.

Definition in the preamble:

```
% \usepackage{cleveref}
\tcbset{
  defstyle/.style={fonttitle=\bfseries\upshape, fontupper=\slshape,
              arc=0mm, colback=blue!5!white,colframe=blue!75!black},
  theostyle/.style={fonttitle=\bfseries\upshape, fontupper=\slshape,
               colback=red!10!white,colframe=red!75!black},
}
\newtcbtheorem[number within=subsection,crefname={definition}{definitions}]%
  {Definition}{Definition}{defstyle}{def}
\newtcbtheorem[use counter from=Definition,crefname={theorem}{theorems}]%
  {Theorem}{Theorem}{theostyle}{theo}
\newtcbtheorem[use counter from=Definition,crefname={corollary}{corollaries}]%
  {Corollary}{Corollary}{theostyle}{cor}
```

By \newtcbtheorem→ P. 352, commonly numbered theorem environments are created now. defstyle and theostyle are used for the appearance.

Now, everything is prepared for the following examples.

```
The following theorem is numbered as \Cref{theo:diffbarstetig} and
referenced with the marker \texttt{theo:diffbarstetig}.\bigskip

\begin{Theorem}{Differenzierbarkeit bedingt Stetigkeit, wobei diese Benennung
  zu Testzwecken ungew\"{o}hnlich lang ist}{diffbarstetig}%
  Eine Funktion $f:I\to\mathbb{R}$ ist in $x_0\in I$ stetig, wenn $f$ in
  $x_0$ differenzierbar ist.
\end{Theorem}
```

The following theorem is numbered as Theorem 17.3.1 and referenced with the marker theo:diffbarstetig.

Theorem 17.3.1: Differenzierbarkeit bedingt Stetigkeit, wobei diese Benennung zu Testzwecken ungewöhnlich lang ist

Eine Funktion $f : I \to \mathbb{R}$ ist in $x_0 \in I$ stetig, wenn f in x_0 differenzierbar ist.

```
The following definition is numbered as \Cref{def:diffbarkeit} and
referenced with the marker \texttt{def:diffbarkeit}.\bigskip

\begin{Definition}{Differenzierbarkeit}{diffbarkeit}
  Eine Funktion $f:~I\to\mathbb{R}$ auf einem Intervall $I$ hei\ss{}t in
  $x_0\in I$ differenzierbar oder linear approximierbar,
  wenn der Grenzwert
  \begin{equation*}
  \lim\limits_{x\to x_0}\frac{f(x)-f(x_0)}{x-x_0}=
  \lim\limits_{h\to 0}\frac{f(x_0+h)-f(x_0)}{h}
  \end{equation*}
  existiert. Bei Existenz hei\ss{}t dieser Grenzwert Ableitung
  oder Differentialquotient von $f$ in $x_0$ und man
  schreibt f\"{u}r ihn
  \begin{equation*}
  f'(x_0)\quad\text{oder}\quad\frac{df}{dx}(x_0).
  \end{equation*}
\end{Definition}
```

The following definition is numbered as Definition 17.3.2 and referenced with the marker `def:diffbarkeit`.

Definition 17.3.2: Differenzierbarkeit

Eine Funktion $f: I \to \mathbb{R}$ auf einem Intervall I heißt in $x_0 \in I$ differenzierbar oder linear approximierbar, wenn der Grenzwert

$$\lim_{x\to x_0}\frac{f(x)-f(x_0)}{x-x_0}=\lim_{h\to 0}\frac{f(x_0+h)-f(x_0)}{h}$$

existiert. Bei Existenz heißt dieser Grenzwert Ableitung oder Differentialquotient von f in x_0 und man schreibt für ihn

$$f'(x_0)\quad\text{oder}\quad\frac{df}{dx}(x_0).$$

```
The following corollary is numbered as \Cref{cor:nullstellen} and
referenced with the marker \texttt{cor:nullstellen}.\bigskip

\begin{Corollary}{Nullstellenexistenz}{nullstellen}
  Ist $f:[a,b]\to\mathbb{R}$ stetig und haben $f(a)$ und $f(b)$ entgegengesetzte
  Vorzeichen, also $f(a)f(b)<0$, so besitzt $f$ eine Nullstelle $x_0\in]a,b[$,
  also $f(x_0)=0$.
\end{Corollary}
```

The following corollary is numbered as Corollary 17.3.3 and referenced with the marker `cor:nullstellen`.

Corollary 17.3.3: Nullstellenexistenz

Ist $f:[a,b]\to\mathbb{R}$ stetig und haben $f(a)$ und $f(b)$ entgegengesetzte Vorzeichen, also $f(a)f(b)<0$, so besitzt f eine Nullstelle $x_0\in]a,b[$, also $f(x_0)=0$.

```
\begin{Theorem}[boxrule=2mm,toptitle=-1.5mm,bottomtitle=-1.5mm]{%
    Hinreichende Bedingung f\"{u}r Wendepunkte}{wendehinreichend}%
  $f$ sei eine auf einem Intervall $]a,b[$ dreimal stetig differenzierbare Funktion.
  Ist $f''(x_0)=0$ in $x_0\in]a,b[$ und $f'''(x_0)\ne 0$, so ist
  $(x_0,f(x_0))$ ein Wendepunkt von $f$.
\end{Theorem}
```

Theorem 17.3.4: Hinreichende Bedingung für Wendepunkte

f sei eine auf einem Intervall $]a,b[$ dreimal stetig differenzierbare Funktion. Ist $f''(x_0) = 0$ in $x_0 \in]a,b[$ und $f'''(x_0) \neq 0$, so ist $(x_0, f(x_0))$ ein Wendepunkt von f.

```
% \usepackage{varioref}
% \usepackage{cleveref}
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
  {theorem style=plain apart,label type=theorem,enhanced,frame hidden,
  boxrule=2mm,titlerule=0mm,toptitle=1mm,bottomtitle=1mm,
  fonttitle=\bfseries\large,fontupper=\normalsize,
  coltitle=green!35!black,colbacktitle=green!15!white,
  colback=green!50!yellow!15!white,borderline={1pt}{0pt}{green!25!blue},
  }{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"{u}r $n$ Variable}{meanvaluetheorem}%
  Es sei $n\in\mathbb{N}$, $D\subseteq\mathbb{R}^n$ eine offene Menge und
  $f\in C^{1}(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
  $[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
  \begin{equation*}
  f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
  \end{equation*}
\end{YetAnotherTheorem}

\medskip
Here, |cleveref| support is used to reference \Cref{theo:meanvaluetheorem}
on \Cpageref{theo:meanvaluetheorem}. This \namecref{theo:meanvaluetheorem}
can also be referenced by |\Vref| resulting in \Vref{theo:meanvaluetheorem}.
```

Theorem 17.3.5 (Mittelwertsatz für n Variable)

Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^{\top}(x - x_0)$$

Here, `cleveref` support is used to reference Theorem 17.3.5 on Page 373. This theorem can also be referenced by `\Vref` resulting in Theorem 17.3.5.

! Note that `/tcb/label type` → P. 101 was used in the example above to feed `cleveref` [5] with the needed name information.

```
Here, using |\Vref| resulting in \Vref{theo:meanvaluetheorem} is more interesting\ldots
```

Here, using \Vref resulting in Theorem 17.3.5 on the previous page is more interesting...

```
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
  {theorem style=change apart,enhanced,arc=0mm,outer arc=0mm,
  boxrule=0mm,toprule=1mm,bottomrule=1mm,left=1mm,right=1mm,
  titlerule=0mm,toptitle=0mm,bottomtitle=1mm,top=0mm,
  colframe=red!50!black,colback=red!5!white,coltitle=red!50!black,
  title style={top color=yellow!50!white,bottom color=red!5!white,
    middle color=yellow!50!white},
  fonttitle=\bfseries\sffamily\normalsize,fontupper=\normalsize\itshape,
  }{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"{u}r $n$ Variable}{mittelwertsatz_n2}%
  Es sei $n\in\mathbb{N}$, $D\subseteq\mathbb{R}^n$ eine offene Menge und
  $f\in C^{1}(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
  $[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
  \begin{equation*}
  f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
  \end{equation*}
\end{YetAnotherTheorem}
```

17.3.6 Theorem (Mittelwertsatz für n Variable)

Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^\top (x - x_0)$$

```
% \usepackage{varwidth}   \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
{enhanced,frame empty,interior empty,colframe=ForestGreen!50!white,
  coltitle=ForestGreen!50!black,fonttitle=\bfseries,colbacktitle=ForestGreen!15!white,
  borderline={0.5mm}{0mm}{ForestGreen!15!white},
  borderline={0.5mm}{0mm}{ForestGreen!50!white,dashed},
  attach boxed title to top center={yshift=-2mm},
  boxed title style={boxrule=0.4pt},varwidth boxed title}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"{u}r $n$ Variable}{mittelwertsatz_n3}%
  Es sei $n\in\mathbb{N}$, $D\subseteq\mathbb{R}^n$ eine offene Menge und
  $f\in C^{1}(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
  $[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
  \begin{equation*}
  f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
  \end{equation*}
\end{YetAnotherTheorem}
```

Theorem 17.3.7: Mittelwertsatz für n Variable

Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^\top (x - x_0)$$

You need more attention for your theorems? Here, you are ...

```
% tcbuselibrary{skins}  % preamble
\begin{Theorem}[enhanced,
    fuzzy halo=3mm with yellow,
    fuzzy halo=2mm with red,
    fuzzy halo=1mm with yellow,
    watermark color=red!35!white,
    watermark text={Overacting\\Fundamental Theorem}]%
  {Fundamental Theorem of Theorems}{fundamental}%
  \lipsum[1-2]
\end{Theorem}
```

Theorem 17.3.8: Fundamental Theorem of Theorems

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Overacting
Fundamental Theorem

Let's try a more conservative approach:

```
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
  {theorem style=plain,enhanced,colframe=blue!50!black,colback=yellow!20!white,
   coltitle=red!50!black,fonttitle=\upshape\bfseries,fontupper=\itshape,
   drop fuzzy shadow=blue!50!black!50!white,boxrule=0.4pt}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"{u}r $n$ Variable}{mittelwertsatz_n4}%
  Es sei $n\in\mathbb{N}$, $D\subseteq\mathbb{R}^n$ eine offene Menge und
  $f\in C^{1}(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
  $[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
  \begin{equation*}
  f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
  \end{equation*}
\end{YetAnotherTheorem}
```

Theorem 17.3.9 (Mittelwertsatz für n Variable): *Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt*

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^{\top}(x - x_0)$$

17.4 Using other theorem environments with `tcolorbox`

Instead of creating theorem environments with the methods described before, environments from other packages can be boxed with a `tcolorbox`.

Environments may be created e.g. by methods from the `theorem` package or the `amsthm` package. `\tcolorboxenvironment` → P. 17 can be used to put a box around these environments.

Definition in the preamble:

```
\usepackage{amsthm}

\theoremstyle{plain}%    from `amsthm'
\newtheorem{lem}{Lemma}% from `amsthm'

\tcolorboxenvironment{lem}{
  enhanced jigsaw,colframe=cyan,interior hidden,
  breakable,before skip=10pt,after skip=10pt }

\tcolorboxenvironment{proof}{% `proof' from `amsthm'
  blanker,breakable,left=5mm,
  before skip=10pt,after skip=10pt,
  borderline west={1mm}{0pt}{red}}
```

```
\begin{lem}
  \lipsum[2]
\end{lem}

\lipsum[3]

\begin{proof}
  \lipsum*[4]
\end{proof}
```

Lemma 1. *Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.*

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Proof. Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. □

18 Library breakable

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{breakable}
```

This also loads the package `pdfcol`.

18.1 Technical Overview

The library breakable supports the automatic breaking of a `tcolorbox`. This feature is enabled by `/tcb/breakable` → P. 379 and disabled by `/tcb/unbreakable` → P. 380.

If a `tcolorbox` is set to be `/tcb/breakable` → P. 379, then the following algorithm is executed:

1. The box content is read to a box register similar but not identical to the unbreakable case.
2. If the total box fits into the current page, it is shipped out visibly unbroken and the algorithm stops.

   Unbroken Box

   The box. unbroken

3. Otherwise, it is checked if at least `/tcb/lines before break` → P. 380 of the upper box can be placed on the current page. If not, a page break is inserted and the algorithm goes back to Step 2.
4. Now, the *break sequence* starts. The upper box part or the lower box part is split such that it fits into the current page. The fitting part is named *first part* of the *break sequence* and shipped out.

   Broken Box

   The box. first

5. If the remaining content of the total box fits into the current page, the algorithm continues with Step 7, else with Step 6.
6. The upper box part or the lower box part is split such that it fits into the current page. The fitting part is named *middle part* of the *break sequence* and shipped out. Then, the algorithm goes back to Step 5.

   The box. middle

7. The remaining part is named *last part* of the *break sequence* and shipped out. The algorithm stops.

   The box. last

The algorithm takes care that the optional segmentation line never appears at the end of a box. The optional lower box part is also checked to have at least `/tcb/lines before break` → P. 380.

In principle, all boxes of the *break sequence* share the same geometric parameters. The differences are:

- The given /tcb/before→P. 81 and /tcb/after→P. 81 values are used only before the *first* and after the *last* part of the *break sequence*.
- A special behavior between the parts of the *break sequence* can be given by /tcb/toprule at break→P. 383, /tcb/bottomrule at break→P. 383, /tcb/enlarge top at break by→P. 86, and /tcb/enlarge bottom at break by→P. 86.
- The /tcb/skin→P. 137 decides *how* the *first*, *middle*, and *last* part look like. Actually, every part type has its own skin given by the options /tcb/skin first→P. 137, /tcb/skin middle→P. 137, and /tcb/skin last→P. 137. Typically, these options are set automatically by the main skin, see Subsection 18.8 from page 392.

18.2 Limitations and Known Bugs

- The maximal total height of the upper and of the lower part of normal breakable tcolorboxes is about 65536pt (ca. 2300cm) apiece. If such a part gets longer, the output will get buggy without warning. For very oversized boxes which are longer than 65536pt, use the **unlimited** value for /tcb/breakable→P. 379. With the **unlimited** setting, the applied algorithm has (virtually) no height limit for boxes, but very likely the compiler memory will have to be increased for boxes longer than 300 pages (depending on compiler settings and box content). But it is recommended to use **unlimited** for critical large boxes only.
- You can nest an unbreakable tcolorbox inside another tcolorbox, even inside a breakable one. But you cannot not nest a breakable box inside a breakable box. The /tcb/breakable→P. 379 key for a nested box is ignored automatically[3], i. e. inner boxes are always unbreakable.

  After all, in the unlikely case you really want to have the nested box to be breakable, use /tcb/enforce breakable→P. 380 for the nested box[4]. **But, a breakable box inside a breakable box will usually give a mess.**

N 2020-09-17
- Depending on the LaTeX compiler, if your text content contains some text color changing commands, your color may not survive the break to the next box. Since tcolorbox 4.32, pdflatex and lualatex should not have that problem. For xelatex, with the fontspec package, you can use \addfontfeatures{Color=mycolor} to add a font color which survives the break.

N 2014-10-30
- The perpage option of the footmisc package is deliberately deactivated inside a breakable box since all footnotes are placed at the end of the box (possibly far away from the reference point).

N 2016-02-15
- Making a box /tcb/breakable→P. 379 which actually is not broken creates a box which acts *almost* like an unbreakable box. Visual differences are kept as indiscernible as possible, but can appear with certain /tcb/before→P. 81 and /tcb/after→P. 81 settings, especially, if there is an automatic page break before the box.

N 2016-05-25
- LuaTeX version 0.95 changes the behaviour of the basic \vsplit (a bug?!) resulting in badly broken boxes. Thanks to Jeremy Engel, the LIB breakable library contains a patch for this which also loads the the ifluatex package.

[3] Until tcolorbox 3.04, the /tcb/breakable→P. 379 key was not ignored for nested boxes.
[4] /tcb/enforce breakable→P. 380 acts like /tcb/breakable→P. 379 until tcolorbox 3.04.

18.3 Main Option Keys

U 2017-02-01 **/tcb/breakable=true|false|unlimited** (default `true`, initially `false`)

Allows the `tcolorbox` to be breakable. If the box is larger than the available space at the current page, the box is automatically broken and continued to the next page. All sorts of `tcolorbox` can be made breakable. It depends on the skin how the breaking looks like. If you do not know better, use `/tcb/enhanced` → P. 211 for breaking a box. The parts of the *break sequence* are numbered by the counter `tcbbreakpart`.

- `false`: Sets the `tcolorbox` to be unbreakable.
- `true`: Breaks the `tcolorbox` from one page to another. The maximal total height of the upper and of the lower part is about 65536pt (ca. 2300cm or ca. 90 pages) apiece.
- `unlimited`: Experimental code for unlimited total height of breakable boxes. For boxes longer than 300 pages (or even shorter ones) the compiler memory will have to be increased.

```
% \usepackage{lipsum}  % preamble
\tcbset{enhanced jigsaw,colback=red!5!white,colframe=red!75!black,
  watermark color=yellow!25!white,watermark text=\arabic{tcbbreakpart},
  fonttitle=\bfseries}

\begin{tcolorbox}[breakable,title=My breakable box]
\lipsum[1-6]
\end{tcolorbox}
```

My breakable box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt

ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.
Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.
Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

/tcb/unbreakable (no value, initially set)

Sets the `tcolorbox` to be unbreakable.

/tcb/enforce breakable (no value)

A `tcolorbox` inside a `tcolorbox` is automatically set to be unbreakable. Using `/tcb/breakable` → P. 379 on such an inner box has no effect. If one *really* wants the inner box to be breakable, use `/tcb/enforce breakable`. **This will usually give a mess of shattered boxes. You are advised to not use this option.**
Note that `/tcb/enforce breakable` has the functionality that `/tcb/breakable` → P. 379 had until package version 3.04 and exists for backward compatibility.

U 2018-07-26 **/tcb/title after break=**⟨*text*⟩ (no default, initially empty)

The `/tcb/title` → P. 18 is used only for the *first* part of a *break sequence*. Use `title after break` to create a heading line with ⟨*text*⟩ as content for all following parts. Also see `/tcb/extras title after break` → P. 386 for formatting the title text.

/tcb/notitle after break (no value, initially set)

Removes the title line or following parts in a *break sequence* if set before.

/tcb/adjusted title after break=⟨*text*⟩ (style, no default, initially unset)

Works like `/tcb/adjusted title` → P. 18 but applied to `/tcb/title after break`.

/tcb/lines before break=⟨*number*⟩ (no default, initially 2)

Assures that the given ⟨*number*⟩ of lines of the upper box part or the lower box part are placed before a break happens.

U 2017-07-05 **/tcb/break at=⟨*length*⟩/⟨*length*⟩/.../⟨*length*⟩** (no default, initially `0pt`)

Defines break points at the given ⟨*length*⟩ values. The first ⟨*length*⟩ defines the (maximal) height of the first partial box, the second ⟨*length*⟩ defines the (maximal) height of the second partial box, and so on. The last ⟨*length*⟩ value is applied to all following partial boxes if any.

- Setting a ⟨*length*⟩ to `0pt` means that the naturally available space is used for breaking.
- Setting a ⟨*length*⟩ to a negative value means that the sum of this negative value and the naturally available space is used for breaking (boxes will shrink in height). That that before version 4.10 negative values were treated like `0pt`.

```
% \usepackage{multicol,lipsum}
\begin{multicols}{3}\footnotesize
Breakable boxes inside a |multicols| environment need special attendance.
They are broken by default at |\textheight|.
The |break at| option can be used to insert better break points by hand.
\begin{tcolorbox}[enhanced jigsaw,size=small,vfill before first,
  colframe=red,colback=yellow!10!white,before title=\raggedright,
  title={Broken box inside a |multicols| environment},fonttitle=\bfseries,
  enforce breakable,% use only breakable in the real world!
  pad at break=1mm,break at=3cm/6.3cm ]
\lipsum[1]
\end{tcolorbox}
\refKey{/tcb/height fixed for} may also be considered for |multicols| environments.
\end{multicols}
```

Breakable boxes inside a `multicols` environment need special attendance. They are broken by default at `\textheight`. The `break at` option can be used to insert better break points by hand.

Broken box inside a multicols environment

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

`/tcb/height fixed for` → P. 384 may also be considered for `multicols` environments.

/tcb/enlargepage=⟨*length*⟩/⟨*length*⟩/.../⟨*length*⟩ (no default, initially `0pt`)

Inserts a `\enlargethispage{`⟨*length*⟩`}` to the pages of the break sequence, i. e. allows one to enlarge (or shrink) partial boxes. The first ⟨*length*⟩ is applied to the first partial box, the second ⟨*length*⟩ is applied to the second partial box, and so on. The last ⟨*length*⟩ value is applied to all following partial boxes if any. Note that floating boxes will not be enlarged.

```
\begin{tcolorbox}[breakable,enlargepage=0mm/\baselineskip/2\baselineskip/0mm,...
```

The example code enlarged the second partial box by one line, the third partial box by two lines, and all following parts are not enlarged.

> **!** If an automated page break occures before the first partial box, the page enlargement is applied to the page before the first partial box *and* again to the page of the first partial box. Insert a manual break to prevent this.
> In general, `enlargepage` should be used at the final stage of a document for fine-tuning only.

/tcb/enlargepage flexible=⟨*length*⟩ (no default, initially `0pt`)

This allows an automated page enlargement for up to ⟨*length*⟩. The algorithm can use this to avoid breaking a box, if there is anough room after enlargement. Also, the *last* partial box of a break sequence may be enlarged to avoid further breaking.
Note that this potential enlargement is *additive* to settings of `/tcb/enlargepage` → P. 381. But `/tcb/enlargepage flexible` overwrites settings of `/tcb/pad before break*` → P. 383 or `/tcb/pad at break*` → P. 383.

```
% The following setting hinders orphan lines for the last partial box
\tcbset{enlargepage flexible=\baselineskip}
```

N 2014-12-15 **/tcb/compress page=⟨*option*⟩** (default `all`, initially `baselineskip`)

This option controls the space management on the page which contains the unbroken box or the first part of a *break sequence*. Feasible ⟨*option*⟩ values are:

- `all` (default value): All shrinkable glue on the page is potentially used for the unbroken box or the first part of a *break sequence*. Thus, all vertical spaces on the page will potentially be reduced to their minimal values.
- `baselineskip` (initial value): Shrinkable glue up to one `\baselineskip` on the page is potentially used for the unbroken box or the first part of a *break sequence*.
- `none`: The break algorithm respects the target size of the given glue values on the page. This was the inital value before version `3.34`.

> **!** Note that the box *content* is not influenced by this option.

/tcb/shrink break goal=⟨*length*⟩ (no default, initially `0pt`)

This is an emergency parameter if the break algorithm produces unpleasant breaks. It shrinks the goal height of the current box part by ⟨*length*⟩ which may result in smaller boxes. Never use negative values. *Usually, this option will never be needed at all.*

18.4 Option Keys for the Break Appearance

/tcb/toprule at break=⟨*length*⟩ (no default, initially 0.5mm)

Sets the line width of the top rule to ⟨*length*⟩ *if* the box is /tcb/breakable → P. 379. In this case, it is applied to *middle* and *last* parts in a break sequence. Note that /tcb/toprule → P. 35 overwrites this value if used afterwards.

/tcb/bottomrule at break=⟨*length*⟩ (no default, initially 0.5mm)

Sets the line width of the bottom rule to ⟨*length*⟩ *if* the box is /tcb/breakable → P. 379. In this case, it is applied to *first* and *middle* parts in a break sequence. Note that /tcb/bottomrule → P. 35 overwrites this value if used afterwards.

/tcb/topsep at break=⟨*length*⟩ (no default, initially 0mm)

Additional vertical space of ⟨*length*⟩ which is added at the top of *middle* and *last* parts in a break sequence. In general, it is not advisable to change this value if these parts start with a rule or a title.

/tcb/bottomsep at break=⟨*length*⟩ (no default, initially 0mm)

Additional vertical space of ⟨*length*⟩ which is added at the bottom of *first* and *middle* parts in a break sequence. In general, it is not advisable to change this value if these parts end with a rule.

/tcb/pad before break=⟨*length*⟩ (style, no default, initially 3.5mm)

Sets the total amount of vertical space after the text content and before the break point to ⟨*length*⟩. This style sets /tcb/toprule at break to 0pt and changes /tcb/topsep at break as required. In general, it is not advisable to change this value if the *middle* and *last* parts in a break sequence start with a rule or a title.

/tcb/pad before break*=⟨*length*⟩ (style, no default)

Sets /tcb/pad before break to ⟨*length*⟩ and /tcb/enlargepage flexible → P. 382 to an appropriate value such that empty closing frames are avoided.

/tcb/pad after break=⟨*length*⟩ (style, no default, initially 3.5mm)

Sets the total amount of vertical space after the break point and before the text content to ⟨*length*⟩. This style sets /tcb/bottomrule at break to 0pt and changes /tcb/bottomsep at break as required. In general, it is not advisable to change this value if the *first* and *middle* parts in a break sequence end with a rule.

/tcb/pad at break=⟨*length*⟩ (style, no default, initially 3.5mm)

Abbreviation for setting ⟨*length*⟩ to /tcb/pad before break and /tcb/pad after break.

/tcb/pad at break*=⟨*length*⟩ (style, no default)

Sets /tcb/pad at break to ⟨*length*⟩ and /tcb/enlargepage flexible → P. 382 to an appropriate value such that empty closing frames are avoided.

```
% \usepackage{lipsum}  % preamble
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced jigsaw,breakable,pad at break*=0mm,
  title={For this box, the pad space at the break point is set to 0mm}]
  \lipsum[1-2]
\end{tcolorbox}
```

For this box, the pad space at the break point is set to 0mm

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

! `/tcb/pad at break`→P. 383 or `/tcb/pad at break*`→P. 383 should be used as very last option in an option list, because they adapt other settings.

! Also see `/tcb/enlarge top at break by`→P. 86 and `/tcb/enlarge bottom at break by`→P. 86.

`/tcb/height fixed for=`⟨*part*⟩ (no default, initially `none`)

When certain amount of space is available for a partial box of a break sequence, the partial box typically is smaller than this space (depending on the box content). For given ⟨*part*⟩(s), the height can be set to all available space.

- `none`: Every partial `tcolorbox` is set with its natural height.
- `first`: The *first* partial box is set to a height which matches the available space.
- `middle`: All *middle* partial boxes are set to a height which matches the available space.
- `last`: The *last* partial box is set to a height which matches the available space.
- `first and middle`: The *first* and all *middle* partial boxes are set to a height which matches the available space.
- `middle and last`: All *middle* partial boxes and the *last* partial box are set to a height which matches the available space.
- `all`: All partial boxes are set to a height which matches the available space.

! If the box keeps unbroken, this option is not applied. See `/tcb/height`→P. 53 for setting a fixed height for unbroken boxes. See `/tcb/height fill`→P. 56 for giving unbroken boxes maximum height.

`/tcb/vfill before first=true|false` (default `true`, initially `false`)

Inserts a `\vfill` at the begin of the *first* partial box to move this partial box to the end of the current page. This may be used as an alternative to `/tcb/height fixed for=first` to get justified columns or pages. The `\vfill` is not inserted, if the box gets not actually broken.

N 2017-03-20 **`/tcb/segmentation at break=true|false`** (default `true`, initially `true`)

If a breakable box contains an *upper part* and a *lower part* and the break happens at the *segmentation* between both parts, then

- the segmenation line (or similar) is drawn as first element of the partial box containing the *lower part*, if `/tcb/segmentation at break` is set to be `true`.
- the segmenation line (or similar) is not drawn at all, if `/tcb/segmentation at break` is set to be `false`. This may be preferable for skins like `bicolor`→P. 224, `tile`→P. 229, or `beamer`→P. 233.

18.5 Extra Options for Partial Boxes

N 2015-07-16 **/tcb/extras**={⟨*options*⟩} (no default, initially unset)

Adds `tcolorbox` ⟨*options*⟩ to every box of a *break sequence* after skin settings are done. This is quite late in box processing. Geometry and break settings should *not be used* here, because they will either be ignored or have unexpected negative results. But it is possible to change most colors, skin effects, shadows, borders, frame code, etc. Note that using `/tcb/extras` for every box is very seldom an advantage over setting the options directly. Usually, `/tcb/extras first`, `/tcb/extras middle`, etc. are sensible to apply.

N 2015-07-16 **/tcb/no extras** (style, no default, initially set)

Removes all extras if set before.

N 2015-07-16 **/tcb/extras broken**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 379 and *is* broken actually, then the ⟨*options*⟩ are added to every box of the *break sequence*. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/extras unbroken**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 379 but *is not* broken actually or if the box is set to be `/tcb/unbreakable` → P. 380, then the ⟨*options*⟩ are added to the box. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/no extras unbroken** (style, no default, initially set)

Removes the unbroken extras if set before.

N 2015-07-16 **/tcb/extras first**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 379 and *is* broken actually, then the ⟨*options*⟩ are added to the *first* box of the break sequence. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/no extras first** (style, no default, initially set)

Removes the first extras if set before.

N 2015-07-16 **/tcb/extras middle**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 379 and *is* broken actually, then the ⟨*options*⟩ are added to every *middle* box (if any) of the break sequence. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/no extras middle** (style, no default, initially set)

Removes the middle extras if set before.

N 2015-07-16 **/tcb/extras last**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 379 and *is* broken actually, then the ⟨*options*⟩ are added to the *last* box of the break sequence. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/no extras last** (style, no default, initially set)

Removes the last extras if set before.

N 2015-07-16 **/tcb/extras unbroken and first**={⟨*options*⟩} (no default, initially unset)

This is an abbreviation for setting `/tcb/extras unbroken` and `/tcb/extras first` together. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/extras middle and last**={⟨*options*⟩} (no default, initially unset)

This is an abbreviation for setting `/tcb/extras middle` and `/tcb/extras last` together. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/extras unbroken and last**={⟨*options*⟩} (no default, initially unset)

This is an abbreviation for setting `/tcb/extras unbroken` and `/tcb/extras last` together. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/extras first and middle**={⟨*options*⟩} (no default, initially unset)

This is an abbreviation for setting /tcb/extras first→ P. 385 and /tcb/extras middle→ P. 385 together. /tcb/extras→ P. 385 overwrites this key.

N 2018-07-26 **/tcb/extras title after break**={⟨*options*⟩} (no default, initially unset)

If the box has a /tcb/title after break→ P. 380, then the ⟨*options*⟩ are added for all titles after the first break, i.e. all middle and last. The color, font, and alignment of titles after break can be adapted choosing ⟨*options*⟩, e.g. by /tcb/coltitle→ P. 28, /tcb/fonttitle→ P. 29, /tcb/halign title→ P. 32. Note that /tcb/colbacktitle→ P. 27 has to be placed into /tcb/extras middle and last→ P. 385.

N 2018-07-26 **/tcb/no extras title after break** (style, no default, initially set)

Removes the title after break extras if set before.

```latex
% \usepackage{lipsum,multicol}
% \usetikzlibrary{decorations.pathmorphing}
% \tcbuselibrary{skins}
\newtcolorbox{mybox}[1][]{
  tile,
  colback=green!7,coltitle=blue!50!black,colbacktitle=blue!5,
  center title,
  toprule=1.25mm,bottomrule=1.25mm,
  extras unbroken and first={
    borderline north={0.25mm}{0.5mm}{blue,decoration={zigzag,amplitude=0.5mm},decorate}},
  extras unbroken and last={
    borderline south={0.25mm}{0.5mm}{blue,decoration={zigzag,amplitude=0.5mm},decorate}},
  #1
}

\begin{mybox}[title=My unbroken box]
\lipsum[1]
\end{mybox}

\begin{multicols}{3}
  \begin{mybox}[title=My broken box,
    enforce breakable,% use only breakable in the real world!
    break at=4.2cm,pad at break=2mm,
    height fixed for=first and middle,  ]
  \lipsum[2]
  \end{mybox}
\end{multicols}
```

My unbroken box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My broken box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

18.6 Breakable boxes and the `multicol` package

> **!** With version 4.10, the algorithm for detecting the available height for a `tcolorbox` inside a `multicol` environment was improved with help of Frank Mittelbach. This change *may* impact existing user code which *may* have to be adapted.

Unbreakable `tcolorbox`es can be used without special care inside a `multicols` environment from the `multicol` package [9].
Since version 3.10, a breakable `tcolorbox` detects, if it is used inside a `multicols` environment. But choosing break points for a breakable box cannot be done by the balancing routine of `multicols`. By default, boxes will break at maximum column height. To get pleasant results, use the `/tcb/break at` → P. 381 and `/tcb/height fixed for` → P. 384 options.

```
% \usepackage{lipsum,multicol}  % preamble
\footnotesize
\begin{multicols}{2}
  \lipsum[1]
  \begin{tcolorbox}[enhanced jigsaw,breakable,size=title,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=My breakable box,pad at break=1mm, break at=-\baselineskip/0pt ]
  \lipsum[2-4]
  \end{tcolorbox}
  \lipsum[4]
\end{multicols}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My breakable box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.
Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.
Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

This example is already set inside a `multicols` environment. This time, a *middle* part has full column height (here `\textheight`). `/tcb/height fixed for` → P. 384 is used to spread this box part over the full height to align with neighboring columns.

```
% \usepackage{lipsum,multicol}
\lipsum[1]
\begin{tcolorbox}[enhanced jigsaw,
  breakable,
  size=title,
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=My breakable box,
  pad at break=2mm,
  break at=-\baselineskip/0pt,
  height fixed for=middle ]
\lipsum[2-7]
\end{tcolorbox}
\lipsum[8]
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My breakable box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi

quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

The following example has a `\tcolorbox` which fills the `\multicols` environment completely. Here, `/tcb/height fixed for` → P. 384 is used to give all three columns the full height. Note that the appropriate `/tcb/break at` → P. 381 value is not computed automatically but set manually.

```
% \usepackage{lipsum,multicol}  % preamble
\small
\begin{multicols}{3}
  \begin{tcolorbox}[enhanced jigsaw,breakable,size=small,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=My breakable box,pad at break=2mm,drop fuzzy shadow,
    height fixed for=all, break at=11.4cm ]
  \lipsum[1-3]
  \end{tcolorbox}
\end{multicols}
```

My breakable box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

18.7 Break Point Insertion

N 2017-07-05 **\tcbbreak**

A *breakable* box is not broken, if there is enough space on the current page or column. Therefore, typical penalty insertion with \break, \pagebreak, \columnbreak, ... *may* only work as expected, if the box is broken at least into two parts *without* inserting the penalties.

To *force* a page or column break, \tcbbreak starts a new paragraph and inserts an insane tall rule which causes a break and which is immediately discarded. You may ignore this technical information and just use it as you would use \pagebreak.

For an *unbreakable box*, \tcbbreak is identical to insert \par, i.e. it just starts a new paragraph.

Also see /tcb/break at → P. 381 for defining height dependend breaks.

```
% \usepackage{lipsum,multicol}  % preamble
\begin{multicols}{3}
  \begin{tcolorbox}[breakable,enhanced jigsaw,size=small,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=Break into parts
  ]
  First part\tcbbreak
  Second part\tcbbreak
  Third part
  \end{tcolorbox}
\end{multicols}

\begin{multicols}{3}
  \begin{tcolorbox}[enhanced jigsaw,size=small,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=You shall not break
  ]
  First part\tcbbreak
  Second part\tcbbreak
  Third part
  \end{tcolorbox}
\end{multicols}
```

Break into parts
First part

Second part

Third part

You shall not break
First part
Second part
Third part

18.8 Break Sequence for the Skins

The following diagrams document the *break sequence* for different skins. Depending on the main skin of a `tcolorbox`, the actual skins of the *break sequence* parts are displayed.




Unbroken Box
skin=enhanced
unbroken
Broken Boxes
skin=enhancedfirst
first
skin=enhancedmiddle
middle
skin=enhancedlast
last
Unbroken Box
skin=enhancedfirst
unbroken
Broken Boxes
skin=enhancedfirst
first
skin=enhancedmiddle
middle
skin=enhancedmiddle
last
Unbroken Box
skin=enhancedmiddle
unbroken
Broken Boxes
skin=enhancedmiddle
first
skin=enhancedmiddle
middle
skin=enhancedmiddle
last
Unbroken Box
skin=enhancedlast
unbroken
Broken Boxes
skin=enhancedmiddle
first
skin=enhancedmiddle
middle
skin=enhancedlast
last


Unbroken Box
skin=enhanced jigsaw
unbroken
Broken Boxes
skin=enhancedfirst jigsaw
first
skin=enhancedmiddle jigsaw
middle
skin=enhancedlast jigsaw
last
Unbroken Box
skin=enhancedfirst jigsaw
unbroken
Broken Boxes
skin=enhancedfirst jigsaw
first
skin=enhancedmiddle jigsaw
middle
skin=enhancedmiddle jigsaw
last
Unbroken Box
skin=enhancedmiddle jigsaw
unbroken
Broken Boxes
skin=enhancedmiddle jigsaw
first
skin=enhancedmiddle jigsaw
middle
skin=enhancedmiddle jigsaw
last
Unbroken Box
skin=enhancedlast jigsaw
unbroken
Broken Boxes
skin=enhancedmiddle jigsaw
first
skin=enhancedmiddle jigsaw
middle
skin=enhancedlast jigsaw
last

skin=empty

unbroken

skin=emptyfirst

first

skin=emptymiddle

middle

skin=emptylast

last

skin=emptyfirst

unbroken

skin=emptyfirst

first

skin=emptymiddle

middle

skin=emptymiddle

last

skin=emptymiddle

unbroken

skin=emptymiddle

first

skin=emptymiddle

middle

skin=emptymiddle

last

skin=emptylast

unbroken

skin=emptymiddle

first

skin=emptymiddle

middle

skin=emptylast

last


Unbroken Box
skin=bicolor
unbroken
Broken Boxes
skin=bicolorfirst
first
skin=bicolormiddle
middle
skin=bicolorlast
last
Unbroken Box
skin=bicolorfirst
unbroken
Broken Boxes
skin=bicolorfirst
first
skin=bicolormiddle
middle
skin=bicolormiddle
last
Unbroken Box
skin=bicolormiddle
unbroken
Broken Boxes
skin=bicolormiddle
first
skin=bicolormiddle
middle
skin=bicolormiddle
last
Unbroken Box
skin=bicolorlast
unbroken
Broken Boxes
skin=bicolormiddle
first
skin=bicolormiddle
middle
skin=bicolorlast
last

Unbroken Box

`skin=tile`

unbroken

Broken Boxes

`skin=tilefirst` first

`skin=tilemiddle` middle

`skin=tilelast` last

Unbroken Box

`skin=tilefirst`

unbroken

Broken Boxes

`skin=tilefirst` first

`skin=tilemiddle` middle

`skin=tilemiddle` last

Unbroken Box

`skin=tilemiddle`

unbroken

Broken Boxes

`skin=tilemiddle` first

`skin=tilemiddle` middle

`skin=tilemiddle` last

Unbroken Box

`skin=tilelast`

unbroken

Broken Boxes

`skin=tilemiddle` first

`skin=tilemiddle` middle

`skin=tilelast` last

Unbroken Box

skin=beamer

unbroken

Broken Boxes

skin=beamerfirst

skin=beamermiddle

skin=beamerlast

Unbroken Box

skin=beamerfirst

unbroken

Broken Boxes

skin=beamerfirst

skin=beamermiddle

skin=beamermiddle

Unbroken Box

skin=beamermiddle

unbroken

Broken Boxes

skin=beamermiddle

skin=beamermiddle

skin=beamermiddle

Unbroken Box

skin=beamerlast

unbroken

Broken Boxes

skin=beamermiddle

skin=beamermiddle

skin=beamerlast


Unbroken Box
skin=widget
unbroken
Broken Boxes
skin=widgetfirst
first
skin=widgetmiddle
middle
skin=widgetlast
last
Unbroken Box
skin=widgetfirst
unbroken
Broken Boxes
skin=widgetfirst
first
skin=widgetmiddle
middle
skin=widgetmiddle
last
Unbroken Box
skin=widgetmiddle
unbroken
Broken Boxes
skin=widgetmiddle
first
skin=widgetmiddle
middle
skin=widgetmiddle
last
Unbroken Box
skin=widgetlast
unbroken
Broken Boxes
skin=widgetmiddle
first
skin=widgetmiddle
middle
skin=widgetlast
last
frame: w=199.16928pt, h=108.12054pt
title: w=167.87134pt, h=7.65457pt
Unbroken Box
skin=draft
upper: w=167.87134pt, h=73.43599pt
interior: w=196.32404pt, h=90.50758pt
frame: w=199.16928pt, h=39.83368pt
title: w=167.87134pt, h=7.65457pt
Broken Boxes
upper: w=167.87134pt, h=5.14912pt
skin=draft
interior: w=196.32404pt, h=22.22072pt
frame: w=199.16928pt, h=28.45274pt
upper: w=167.87134pt, h=8.5359pt
skin=draft
interior: w=196.32404pt, h=25.6075pt
frame: w=199.16928pt, h=28.45274pt
upper: w=167.87134pt, h=8.5359pt
skin=draft
interior: w=196.32404pt, h=25.6075pt


Unbroken Box
skin=freelance
unbroken
Broken Boxes
skin=freelancefirst
first
skin=freelancemiddle
middle
skin=freelancelast
last
Unbroken Box
skin=freelancefirst
unbroken
Broken Boxes
skin=freelancefirst
first
skin=freelancemiddle
middle
skin=freelancemiddle
last
Unbroken Box
skin=freelancemiddle
unbroken
Broken Boxes
skin=freelancemiddle
first
skin=freelancemiddle
middle
skin=freelancemiddle
last
Unbroken Box
skin=freelancelast
unbroken
Broken Boxes
skin=freelancemiddle
first
skin=freelancemiddle
middle
skin=freelancelast
last

18.9 Break by Hand (Faked Break)

See Section 18.6 on page 388 for *real* column breaks.

Since the appearance of broken boxes is done by skins, it is quite easy to 'fake a break'. For this, you actually don't need the breakable library at all.

```
\tcbset{enhanced,equal height group=fakedbreak,
  colback=LightGreen,colframe=DarkGreen,
  width=(\linewidth-6mm)/3,nobeforeafter,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm}
%
\begin{tcolorbox}[title=My broken box,skin=enhancedfirst]
This is a box which breaks from one column to another
\end{tcolorbox}\hfill
\begin{tcolorbox}[skin=enhancedmiddle]
column. I am sorry to say that this is a trick.
Nevertheless, you may use this trick for your
\end{tcolorbox}\hfill
\begin{tcolorbox}[skin=enhancedlast]
own purposes.
\end{tcolorbox}
```



19 Library magazine

The main purpose of this library is to store a `tcolorbox` into an array of box registers for later usage.

If the `tcolorbox` is not breakable, there is not much add-on compared to usual TEX/LATEX box storage and usage (and you do not really need this library for that use case). For a breakable `tcolorbox`, this library allows to capture all partial boxes into a sequence of registers. The partial boxes can be used anywhere in arbitrary order.

Example Article

This is an example for an article which starts right here and is continued to the following pages. The body text for the article is written inside a single `tcolorbox`. This box is split into parts using the tools from this section,

— *continued on page 405* —

The name of this library indicates *magazine* in the sense of storage, but also in the sense of a journal where an article often is *continued on page x*. An example for this kind of application is given throughout this section starting on the right hand side. The creation of this library was motivated by Ulrike Fischer and Steven B. Segletes.

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{magazine}
```

This also loads the library breakable, see Section 18 on page 377.

> **!** The box register operations of this library are global. TEX grouping will not clear the registers when leaving the current group. Also be aware that extensive use of large box arrays may eat up TEX's available memory and registers.

19.1 Creation and Resetting of Box Arrays

N 2015-07-13 `\newboxarray{⟨name⟩}`

This creates a new box array called ⟨*name*⟩. There already is a box array available with name `default` which can be used directly. Note that the creation is a global operation.

```
\newboxarray{myarray}
```

N 2015-07-13 `\boxarrayreset[⟨name⟩]`

Resets the size counter of a box array ⟨*name*⟩ to zero. If ⟨*name*⟩ is not provided, `default` is used as name. Use this or `/tcb/reset box array` before you apply `/tcb/store to box array` → P. 403. Otherwise, all boxes would be appended to the already existing boxes. This command does not clear box registers.

```
\boxarrayreset            % resets `default'
\boxarrayreset{myarray}   % resets `myarray'
```

N 2015-07-13 `/tcb/reset box array=⟨name⟩` (default `default`, initially unset)

Resets the size counter of a box array ⟨*name*⟩ to zero. Use this or `\boxarrayreset` (which does the same) before you apply `/tcb/store to box array` → P. 403.

```
\tcbset{
  reset box array,          % resets `default'
  reset box array=myarray,  % resets `myarray'
}
```

N 2015-07-13 `\boxarrayclear[⟨name⟩]`

Works like `\boxarrayreset` → P. 402 to reset the size counter of a box array ⟨*name*⟩ to zero. Additionally, all allocated box registers of the box array are cleared of their content. Note that the allocated box registers stay allocated. So, this may be useful to clear memory, but not to free registers for other applications. If `\consumeboxarray` → P. 406 or `\consumetcboxarray` → P. 406 was used to apply the stored boxes, there is no advantage in using `\boxarrayclear`.

```
\boxarrayclear              % clears `default'
\boxarrayclear{myarray}     % clears `myarray'
```

19.2 Storing Content

N 2015-07-13 `/tcb/store to box array=`⟨*name*⟩ (default `default`, initially unset)

Stores a `tcolorbox` or all parts of a break sequence of a `tcolorbox` into a box array ⟨*name*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. Otherwise, the box array has to be created beforehand with `\newboxarray` → P. 402. Note that the box has to be `/tcb/breakable` → P. 379, if the box shall break into several parts. Typically, manual break points are additionally defined by `/tcb/break at` → P. 381. Otherwise, the box parts will have a length of about `\textheight`. For most use cases, a `/tcb/reset box array` → P. 402 should be applied to reset the box array counter.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced jigsaw,size=fbox,width=4cm,
  colback=yellow!10,colframe=yellow!10!black,
  enforce breakable,% use only breakable in the real world!
  break at=7cm/4cm,
  height fixed for=all,
  watermark text=\arabic{tcbbreakpart},
  reset box array,
  store to box array
  ]
\lipsum[1]
\end{tcolorbox}

\useboxarray{1}\hfill
\begin{tabular}[b]{cc}
\multicolumn{2}{c}{\includegraphics[width=7cm]{Basilica_5.png}}\\
\useboxarray{2} & \useboxarray{3}
\end{tabular}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhon-



cus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

If the first box part should fill the rest of the available space of the current page, you can use `\pagegoal-\pagetotal` minus some distance for the first element of `/tcb/break at`→ P. 381. You may want to have some additional distance to the preceeding text.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,breakable,
  reset box array,
  store to box array,
  break at=\pagegoal-\pagetotal-5mm/0pt,
  height fixed for=first and middle]
\lipsum[1-15]
\end{tcolorbox}%
%
\consumetcboxarray{1}{blanker,before=\par\vfill\noindent}
```

```
\begin{tcolorbox}[blanker,width=4cm,
  fontupper=\footnotesize,
  enforce breakable,% use only breakable in the real world!
  break at=4cm,
  height fixed for=all,
  watermark text=\arabic{tcbbreakpart},
  reset box array,
  store to box array
  ]
\includegraphics[width=\linewidth]{Basilica_5.png}\par
\lipsum[1-2]
\end{tcolorbox}

\begin{tcbitemize}[raster columns=3,raster equal height,
  size=small,halign=center,sharp corners,colback=blue!5]
\tcbitem\consumeboxarray{5}
\tcbitem\consumeboxarray{6}
\tcbitem\consumeboxarray{1}
\tcbitem\consumeboxarray{2}
\tcbitem\consumeboxarray{3}
\tcbitem\consumeboxarray{4}
\end{tcbitemize}
```

lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec

ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam

arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus

vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at,

mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor

N 2015-07-13 **/tcb/reset and store to box array=⟨*name*⟩** (style, default `default`, initially unset)

Combination of `/tcb/reset box array` → P. 402 and `/tcb/store to box array` → P. 403.

N 2015-07-13 **/tcb/do not store to box array** (style, no default, initially set)

Disables the `/tcb/store to box array` → P. 403 option, if set before.

N 2015-07-13
```
\begin{boxarraystore}{⟨name⟩}
  ⟨environment content⟩
\end{boxarraystore}
```

Stores the environment content into a box array ⟨*name*⟩. This corresponds to the standard LaTeX environment `lrbox`, but the storage operation is global. As long as `\boxarrayreset` → P. 402 is not used, every new `boxarraystore` adds a further box to the array.

```
\boxarrayreset
\begin{boxarraystore}{default}\fbox{Mary}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{Had}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{a}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{Little}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{Lamb}\end{boxarraystore}
\useboxarray{5}\useboxarray{4}\useboxarray{3}\useboxarray{2}\useboxarray{1}\hfill
\useboxarray{1}\useboxarray{5}
```

Lamb | Little | a | Had | Mary Mary | Lamb

19.3 Retrieving Content

N 2015-07-13 **\boxarraygetsize[⟨*name*⟩]{⟨*macro*⟩}**

Stores the current size of a box array ⟨*name*⟩ into a given ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used.

```
\boxarraygetsize{\mysize}
Current size of the default box array:
\mysize.
```

Current size of the default box array: 5.

— *continued from page 402* —
namely `/tcb/reset and store to box array` → P. 405 with a new box array `myarticle` which was created by `\newboxarray{myarticle}`.
The resulting parts are distributed throughout this Section 19 on page 402 using `\consumetcboxarray` → P. 406 at
— *continued on page 406* —

N 2015-07-13 **\useboxarray[⟨*name*⟩]{⟨*index*⟩}**

Typesets the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. It is silently ignored, if the ⟨*index*⟩ is out of range. Note that `\useboxarray` corresponds to the standard `\usebox` macro, respectively, `\copy`.

```
\boxarraygetsize{\mysize}
\foreach \n in  {1,...,\mysize} { \useboxarray{\n} }
```

Mary | Had | a | Little | Lamb

N 2015-07-13 `\usetcboxarray[⟨name⟩]{⟨index⟩}{⟨options⟩}`

Typesets the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ using `\useboxarray` → P. 405 as content of a `\tcbox` → P. 14. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. It is silently ignored, if the ⟨*index*⟩ is out of range. The `\tcbox` → P. 14 can be customized by `tcolorbox` ⟨*options*⟩.

```
\boxarraygetsize{\mysize}
\foreach \n in  {1,...,\mysize} { \usetcboxarray{\n}{on line,colframe=yellow,
  colback=yellow!10} }
```

Mary Had a Little Lamb

N 2015-07-13 `\consumeboxarray[⟨name⟩]{⟨index⟩}`

Typesets the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. It is silently ignored, if the ⟨*index*⟩ is out of range. In contrast to `\useboxarray` → P. 405, `\consumeboxarray` corresponds to the standard `\box` macro, i.e. after typesetting the box register is cleared and cannot be used again.

```
\boxarraygetsize{\mysize}
First run: \foreach \n in  {1,...,\mysize} { \consumeboxarray{\n} }
\par
Second run: \foreach \n in  {1,...,\mysize} { \consumeboxarray{\n} }
```

First run: Mary Had a Little Lamb
Second run:

N 2015-07-13 `\consumetcboxarray[⟨name⟩]{⟨index⟩}{⟨options⟩}`

Typesets the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ using `\consumeboxarray` as content of a `\tcbox` → P. 14. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. It is silently ignored, if the ⟨*index*⟩ is out of range. The `\tcbox` → P. 14 can be customized by `tcolorbox` ⟨*options*⟩. After typesetting the box register is cleared and cannot be used again.

— *continued from page 405* —

the appropriate places you see. The linking texts like *continued on page x* are created by `/tcb/finish` → P. 201 commands for the embedding `\tcbox` → P. 14. To label the box parts, `/tcb/phantomlabel` → P. 101 is used.

These quite small partial boxes are

— *continued on page 409* —

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced jigsaw,size=fbox,width=6cm,
  colback=yellow!10,colframe=yellow!10!black,
  enforce breakable,% use only breakable in the real world!
  break at=5cm,
  watermark text=\arabic{tcbbreakpart},
  reset and store to box array
  ]
\lipsum[1]
\end{tcolorbox}

\consumeboxarray{2} \hfill \consumeboxarray{1} \hfill \consumeboxarray{1}
```

lus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tel-

N 2015-07-13 **\boxarraygetbox**[⟨*name*⟩]{⟨*macro*⟩}{⟨*index*⟩}

Assigns the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be undefined.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\boxarraygetsize{\mysize} Array size: \mysize

\boxarraygetbox{\mybox}{1}
Box width: \the\wd\mybox
\quad\usebox{\mybox}
```

Array size: 1
Box width: 30.35799pt Test

N 2017-06-27 **\ifboxarrayempty**[⟨*name*⟩]{⟨*index*⟩}{⟨*true*⟩}{⟨*false*⟩}

Tests the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ for emptiness be empty and executes ⟨*true*⟩ if it is empty, and ⟨*false*⟩ otherwise. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\ifboxarrayempty{1}{no Box~1}{Box~1: \useboxarray{1}},
\ifboxarrayempty{2}{no Box~2}{Box~2: \useboxarray{2}}
```

Box 1: Test, no Box 2

19.4 Box Dimensions

N 2015-07-13 **\boxarraygetwidth**[⟨*name*⟩]{⟨*macro*⟩}{⟨*index*⟩}

Assigns the width of the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be set to `0pt`.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\begin{tabular}{ll}
\useboxarray{1} & width of box 1: \boxarraygetwidth{\mylen}{1} \mylen\\
\useboxarray{2} & width of box 2: \boxarraygetwidth{\mylen}{2} \mylen
\end{tabular}
```

Test width of box 1: 30.35799pt
width of box 2: 0pt

N 2015-07-13 **\boxarraygetheight**[⟨*name*⟩]{⟨*macro*⟩}{⟨*index*⟩}

Assigns the height of the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be set to `0pt`.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\begin{tabular}{ll}
\useboxarray{1} & height of box 1: \boxarraygetheight{\mylen}{1} \mylen\\
\useboxarray{2} & height of box 2: \boxarraygetheight{\mylen}{2} \mylen
\end{tabular}
```

Test height of box 1: 9.89883pt
height of box 2: 0pt

N 2015-07-13 **\boxarraygetdepth**[⟨*name*⟩]{⟨*macro*⟩}{⟨*index*⟩}

Assigns the depth of the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be set to `0pt`.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\begin{tabular}{ll}
\useboxarray{1} & depth of box 1: \boxarraygetdepth{\mylen}{1} \mylen\\
\useboxarray{2} & depth of box 2: \boxarraygetdepth{\mylen}{2} \mylen
\end{tabular}
```

Test depth of box 1: 3.69884pt
depth of box 2: 0pt

N 2015-07-13 `\boxarraygettotalheight[⟨name⟩]{⟨macro⟩}{⟨index⟩}`

Assigns the total height of the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be set to `0pt`.

— continued from page 406 —
for demonstration purposes. With the tools of this section, a magazine type document could be created, but this still needs a lot of manual control.

```
\boxarrayreset
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  store to box array]{Test}

\begin{tabular}{ll}
\useboxarray{1} & total height of box 1: \boxarraygettotalheight{\mylen}{1} \mylen\\
\useboxarray{2} & total height of box 2: \boxarraygettotalheight{\mylen}{2} \mylen
\end{tabular}
```

Test

total height of box 1:	13.59767pt
total height of box 2:	0pt

19.5 Leaflet Example

The following full application example can be used to create leaflets. Obviously, the code can be adapted and customized in many ways.

```
\documentclass[a4paper,landscape]{article}
\usepackage[noheadfoot,margin=0pt]{geometry}
\usepackage[skins,raster,magazine]{tcolorbox}
\usepackage{lipsum}

\newenvironment{leaflet}[1][]{%
  \begin{tcolorbox}[nobeforeafter,empty,colback=white,
    sharp corners,size=minimal,left=10mm,right=10mm,top=10mm,bottom=10mm,
    width=\textwidth/3,
    breakable,
    break at=\textheight,
    height fixed for=all,
    reset box array,
    store to box array,#1]}
  {\end{tcolorbox}%
    \begin{tcbitemize}[raster columns=3,raster equal skip=0pt,blankest]
      \tcbitem\consumeboxarray{5}
      \tcbitem\consumeboxarray{6}
      \tcbitem\consumeboxarray{1}
      \tcbitem\consumeboxarray{2}
      \tcbitem\consumeboxarray{3}
      \tcbitem\consumeboxarray{4}
    \end{tcbitemize}%
  }

\pagestyle{empty}
\begin{document}

\begin{leaflet}[underlay={\node[above=5mm,font=\footnotesize]
    at (frame.south) {- \arabic{tcbbreakpart} -};}]
  \includegraphics[width=\linewidth]{Basilica_5.png}
  \begin{center}
  \bfseries\LARGE Example
  \end{center}

  \section{Introduction}
  \lipsum[1]

  \section{Main Part A}
  \lipsum[2-8]

  \section{Main Part B}
  \lipsum[9-15]

  \section{Conclusion}
  \lipsum[16-18]
\end{leaflet}

\end{document}
```

cursus sodales, augue est scelerisque sapien, venenatis congue nulla arcu et pede. Ut suscipit enim vel sapien. Donec congue. Maecenas urna mi, suscipit in, placerat ut, vestibulum ut, massa. Fusce ultrices nulla et nisl.
Etiam ac leo a risus tristique nonummy. Donec dignissim tincidunt nulla. Vestibulum rhoncus molestie odio. Sed lobortis, justo et pretium lobortis, mauris turpis condimentum augue, nec ultricies nibh arcu pretium enim. Nunc purus neque, placerat id, imperdiet sed, pellentesque nec, nisl. Vestibulum imperdiet neque non sem accumsan laoreet. In hac habitasse platea dictumst. Etiam condimentum facilisis libero. Suspendisse in elit quis nisl aliquam dapibus. Pellentesque auctor sapien. Sed egestas sapien nec lectus. Pellentesque vel dui vel neque bibendum viverra. Aliquam porttitor nisl nec pede. Proin mattis libero vel turpis. Donec rutrum mauris et libero. Proin euismod porta felis. Nam lobortis, metus quis elementum commodo, nunc lectus elementum mauris, eget vulputate ligula tellus eu neque. Vivamus eu dolor.
Nulla in ipsum. Praesent eros nulla, congue vitae, euismod ut, commodo a, wisi. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Aenean nonummy magna non leo. Sed felis erat, ullamcorper in, dictum non, ultricies ut, lectus. Proin vel arcu a odio lobortis euismod. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Proin ut est. Aliquam odio. Pellentesque massa turpis, cursus eu, euismod nec, tempor congue, nulla. Duis viverra gravida mauris. Cras tincidunt. Curabitur eros ligula, varius ut, pulvinar in, cursus faucibus, augue.

4 Conclusion

Nulla mattis luctus nulla. Duis commodo velit at leo. Aliquam vulputate magna et leo. Nam vestibulum ullamcorper leo. Vestibulum condimentum rutrum mauris. Donec id mauris. Morbi molestie justo et pede. Vivamus eget turpis sed nisl cursus tempor. Curabitur mollis sapien condimentum nunc. In wisi nisl, malesuada at, dignissim sit amet, lobortis in, odio. Aenean consequat arcu a ante. Pellentesque porta elit sit amet orci. Etiam at turpis nec elit ultricies imperdiet. Nulla facilisi. In hac habitasse platea dictumst. Suspendisse viverra aliquam risus. Nullam pede justo, molestie nonummy, scelerisque eu, facilisis vel, arcu.
Curabitur tellus magna, porttitor a, commodo a, commodo in, tortor. Donec interdum. Praesent scelerisque. Maecenas posuere sodales odio. Vivamus metus lacus, varius quis, imperdiet quis, rhoncus a, turpis. Etiam ligula arcu, elementum a, venenatis quis, sollicitudin sed, metus. Donec nunc pede, tincidunt in, venenatis vitae, faucibus vel, nibh. Pellentesque wisi. Nullam malesuada. Morbi ut tellus ut pede tincidunt porta. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam congue neque id dolor.
Donec et nisl at wisi luctus bibendum. Nam interdum tellus ac libero. Sed sem justo, laoreet vitae, fringilla at, adipiscing ut, nibh. Maecenas non sem quis tortor eleifend fermentum. Etiam id tortor ac mauris porta vulputate. Integer porta neque vitae massa. Maecenas tempus libero a libero posuere dictum. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Aenean quis mauris sed elit commodo placerat. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Vivamus rhoncus tincidunt libero. Etiam elementum pretium justo. Vivamus est. Morbi a tellus eget pede tristique commodo. Nulla nisl. Vestibulum sed nisl eu sapien cursus rutrum.



Example

1 Introduction

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

2 Main Part A

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ali-

quam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.
Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.
Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.
Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.
Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio. Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.
Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

3 Main Part B

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetuer a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetuer. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.
Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetuer odio sem sed wisi.
Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetuer eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor. Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetuer tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.
Aliquam lectus. Vivamus leo. Quisque ornare tellus ullamcorper nulla. Mauris porttitor pharetra tortor. Sed fringilla justo sed mauris. Mauris tellus. Sed non leo. Nullam elementum, magna in

20 Library poster

The main purpose of this library is to support creation of single page posters with `tcolorbox`es.

A `tcbposter`→ P. 413 is a `tikzpicture` where `tcolorbox`es can be placed in a column oriented manner using `\posterbox`→ P. 418 commands. This base concept is more or less copied from the great `baposter` package.

The raster library, see Section 15 on page 288, can produce similar looking results and may be more appropriate depending on the actual project.

- The raster library has a flow oriented concept, just like a convential text flow. The text flow (box flow) is a merely endless ribbon which gets broken into lines (and paragraphs) and the lines are broken into pages. raster shapes the boxes to convenient sizes to fill lines and pages in a pleasant way.
- The tcbposter library supports a quite free placement of boxes inside a page. Basically, boxes are placed like `node`s are placed inside a `tikzpicture`. In contrast to raster, this is a *single* page and not a flow of pages. The poster is divided into columns and rows. There is a more or less gentle force to use the columns (or spans of columns) for positioning and sizing while the row placement is completely optional.

The creation of this library was motivated by Ignasi.

> **!** Inside a `tikzpicture` there should be no embedded `tikzpicture`s. This rule is violated by the poster library. Be aware that there may be some unwanted interactions between the main `tikzpicture` and the embedded ones inside the `tcolorbox`es.

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{poster}
```

This also loads the libraries skins, see Section 10 on page 152, breakable, see Section 18 on page 377, magazine, see Section 19 on page 402, and fitting, see Section 21 on page 426.

20.1 Overview

Click me to see the tutorial

You get the best overview of the poster library and its facilities, if you look at the **Poster Tutorial** which is part of the `tcolorbox` documentation:
`tcolorbox-tutorial-poster.pdf`

20.2 Main Poster Environment

N 2017-07-03

```
\begin{tcbposter}[⟨options⟩]
  ⟨environment content⟩
\end{tcbposter}
```

This creates a `tikzpicture` environment with suitable additional settings defined by the given ⟨*options*⟩. Basically, `\posterbox` → P. 418 and `posterboxenv` → P. 418 are used to place `tcolorboxes` as nodes into the environment, but additional TikZ code can also be used. As ⟨*options*⟩ all `/tcb/posterset/` keys may be applied, namely:

- `/tcb/posterset/poster` → P. 415: poster settings like columns, rows, sizes...
- `/tcb/posterset/coverage` → P. 416 and `/tcb/posterset/no coverage` → P. 416: settings for a surrounding `tcolorbox` for background and margins.
- `/tcb/posterset/boxes` → P. 417: style of the `tcolorboxes` used for the poster.
- `/tcb/posterset/fontsize` → P. 417: scaling of used fonts.

```
\begin{tcbposter}[
  poster = {showframe,height=10cm,spacing=2mm},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=3,row=2}{My first box}
\posterbox[adjusted title=Second box]
          {name=B,column=2,span=2,below=A}{My second box}
\posterbox[adjusted title=Third box]
          {name=C,column=2,between=B and bottom}{My third box}
\end{tcbposter}
```



Inside tcbposter[→P. 413], there are several predefined TikZ nodes. These nodes share a common /tcb/poster/prefix[→P. 415] which is TCBPOSTER@ by default. This prefix is used to discriminate the poster nodes from local nodes of any embedded tikzpicture environment. You will never need this prefix using \posterbox[→P. 418] and its placement options, but if you want to refer to a predefined node using pure TikZ code. The predefined nodes (shown without prefix) are:

- poster: defines the bounding box of the poster (without the coverage).
- top: top position plus row spacing
- bottom: bottom position minus row spacing
- middle: vertical middle position
- col1, col2, ...: bounding box of column 1, column 2, ...
- row1, row2, ...: bounding box of row 1, row 2, ...

Further nodes are defined using the /tcb/posterloc/name[→P. 419] option.

> **!** Never use a tcbposter[→P. 413] inside a tcbposter[→P. 413]. But, if you do anyway, use a different /tcb/poster/prefix[→P. 415] for the embedded poster or you surely get a total mess.

There are several properties inside a tcbposter[→P. 413] which may be useful for advanced code (skip the following on first reading):

- \tcbposterwidth: Width of the poster (without margins).
- \tcbposterheight: Height of the poster (without margins).
- \tcbpostercolspacing: Column distance.
- \tcbposterrowspacing: Row distance.
- \tcbpostercolumns: Column quantity.
- \tcbposterrows: Row quantity.
- \tcbpostercolwidth: Width of a column.
- \tcbposterrowheight: Height of a row.

N 2017-07-03 **\tcbposterset**{⟨*options*⟩}

Sets options for every following tcbposter[→P. 413] inside the current TEX group. For example, the numbers for rows and columns may be defined for the whole document by this:

```
\tcbposterset{poster={columns=2,rows=3}}
```

See tcbposter[→P. 413] for all feasible options.

20.3 Poster Settings

N 2017-07-03 **/tcb/posterset/poster={⟨*option list*⟩}** (style, no default)

This option can be applied inside `tcbposter`→ P. 413 and `\tcbposterset`→ P. 414 to set the given poster ⟨*option list*⟩, e.g.

```
\tcbposterset{poster={width=20cm,height=15cm}}
```

For the ⟨*option list*⟩, see the following keys.

N 2017-07-03 **/tcb/poster/columns=⟨*number*⟩** (no default, initially `3`)

Sets the ⟨*number*⟩ of columns for a `tcbposter`.

```
\begin{tcbposter}[
  poster = {showframe,columns=5,rows=2,spacing=1mm,height=4cm},
]
\end{tcbposter}
```



N 2017-07-03 **/tcb/poster/rows=⟨*number*⟩** (no default, initially `4`)

Sets the ⟨*number*⟩ of rows for a `tcbposter`.

N 2017-07-03 **/tcb/poster/colspacing=⟨*length*⟩** (no default, initially `4mm`)

Sets ⟨*length*⟩ as distance between columns.

N 2017-07-03 **/tcb/poster/rowspacing=⟨*length*⟩** (no default, initially `4mm`)

Sets ⟨*length*⟩ as distance between rows.

N 2017-07-03 **/tcb/poster/spacing=⟨*length*⟩** (style, no default, initially `4mm`)

Sets ⟨*length*⟩ as distance between columns and rows.

N 2017-07-03 **/tcb/poster/showframe=true|false** (default `true`, initially `false`)

Displays a red auxiliary mesh as optical support during poster creation. Also, every `/tcb/posterloc/name`→ P. 419 is displayed.

N 2017-07-03 **/tcb/poster/width=⟨*length*⟩** (no default, initially `\linewidth`)

Sets ⟨*length*⟩ as width of the poster. For a typical poster, this has not to be set manually. Especially, if `/tcb/posterset/coverage`→ P. 416 is present, use `coverage={width=`⟨*length*⟩`}` instead to change the overall width.

N 2017-07-03 **/tcb/poster/height=⟨*length*⟩** (no default, initially unset)

Sets ⟨*length*⟩ as height of the poster. For a typical poster, this has not to be set manually, but is set automatically to an appropriate value. If `/tcb/posterset/coverage`→ P. 416 is present, use only one if any option `coverage={height=`⟨*length*⟩`}` or `poster={height=`⟨*length*⟩`}`.

N 2017-07-03 **/tcb/poster/prefix=⟨*name*⟩** (no default, initially `TCBPOSTER@`)

⟨*name*⟩ is set as prefix for any Ti*k*Z node which is generated automatically by the LIB poster library. This encompasses predefined nodes like `top`, `bottom`, ..., and nodes defined by using `/tcb/posterloc/name`→ P. 419. Also, see Section 20.2 on page 413. For a typical poster, this value can stay as it is.

20.4 Coverage

N 2017-07-03 **/tcb/posterset/coverage={⟨*option list*⟩}** (style, no default)

This option can be applied inside `tcbposter` → P. 413 and `\tcbposterset` → P. 414 and it adds an optional coverage for the poster which is a surrounding `tcolorbox` with the given ⟨*option list*⟩. Here, margins and background settings for the poster can be given. The *coverage* has several default `tcolorbox` settings suitable for the purpose:

```
enhanced, frame hidden, sharp corners, boxsep=0pt, boxrule=0pt,
top=4mm, bottom=4mm, left=4mm, right=4mm,
toptitle=2mm, bottomtitle=2mm, colback=white
```

The ⟨*option list*⟩ can contain any `tcolorbox` option.

```
\begin{tcbposter}[
  poster   = {showframe,spacing=1mm},
  coverage = {height=5cm,
              interior style={top color=yellow,bottom color=yellow!50!red},
              watermark text={My Poster},watermark color=white,
             },
]
\end{tcbposter}
```



- For a typical poster, the option `/tcb/spread` → P. 91 will use the whole page for the poster coverage.
- Poster margins can be adapted by `/tcb/left` → P. 39, `/tcb/right` → P. 40, `/tcb/top` → P. 42, `/tcb/bottom` → P. 43.
- Poster background can be changed by `/tcb/colback` → P. 27, `/tcb/interior style` → P. 153, `/tcb/interior style image` → P. 154, etc.
- Do not use `/tcb/poster/width` → P. 415 and `/tcb/poster/height` → P. 415 in combination with a *coverage*. Note that you may use `/tcb/width` → P. 34 and `/tcb/height` → P. 53 inside the *coverage* ⟨*option list*⟩. Note that this also is not necessary when `/tcb/spread` → P. 91 is applied.

N 2017-07-03 **/tcb/posterset/no coverage** (style, no value, initially set)

Removes the surrounding `tcolorbox` completely.

20.5 Common Box Settings

N 2017-07-03 **/tcb/posterset/boxes**={⟨*option list*⟩} (style, no default)

This option can be applied inside tcbposter→ P. 413 and \tcbposterset→ P. 414 and it is used to set up the style of the tcolorboxes inside the poster. The ⟨*option list*⟩ can contain any tcolorbox option, but box size options are not assumed to be useful here, because the size will be determined by the placement options.

```
\begin{tcbposter}[
  poster   = {spacing=2mm,columns=3,rows=2},
  coverage = {height=5cm,
              interior style={top color=yellow,bottom color=yellow!50!red},
             },
  boxes    = {sharp corners=downhill,arc=3mm,boxrule=1mm,
              colback=white,colframe=cyan,
              title style={left color=black,right color=cyan},
              fonttitle=\bfseries}
]
  \posterbox[adjusted title=First]{column=1,row=1,span=2}{First box}
  \posterbox[adjusted title=Second]{column=1,row=2,span=2}{Second box}
  \posterbox[adjusted title=Third]{column=3,row=1,rowspan=2}{Third box}
\end{tcbposter}
```



20.6 Font Scaling

N 2017-07-03 **/tcb/posterset/fontsize**=⟨*length*⟩ (style, no default, initially unset)

This option can be applied inside tcbposter→ P. 413 and \tcbposterset→ P. 414. It uses /tcb/fit basedim→ P. 430 and /tcb/fit fontsize macros→ P. 431 to redefine \normalsize to ⟨*length*⟩ and all other standard font size macros like \small and \large accordingly. This needs a freely scalable font family like lmodern to work. If /tcb/posterset/fontsize is not applied, there standard font size macros are not changed in any way.

```
\begin{tcbposter}[
  poster   = {spacing=2mm,columns=3,rows=2},
  coverage = {height=5cm,
              interior style={top color=yellow,bottom color=yellow!50!red},
             },
  fontsize = 15pt,   % <--- \normalsize is now 15pt
]
...
```

20.7 Box Placement

N 2017-07-03 **\posterbox**[⟨*options*⟩]{⟨*placement*⟩}{⟨*box content*⟩}

Inside a tcbposter→ P. 413 environment, this places a tcolorbox with additional tcolorbox ⟨*options*⟩ and the given ⟨*box content*⟩ at a place determined by ⟨*placement*⟩. All ⟨*placement*⟩ options are described in the following. Note that ⟨*box content*⟩ cannot contain *verbatim* material, see posterboxenv.

```
\begin{tcbposter}[
  poster = {showframe,height=4cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox[title=My title]{name=A,column=2,row=2}{My first box}
\end{tcbposter}
```



N 2017-07-03 \begin{**posterboxenv**}[⟨*options*⟩]{⟨*placement*⟩}
⟨*environment content*⟩
\end{**posterboxenv**}

This is the environment version of \posterbox, i.e. inside a tcbposter→ P. 413 environment, this places a tcolorbox with additional tcolorbox ⟨*options*⟩ and the given ⟨*environment content*⟩ at a place determined by ⟨*placement*⟩. In contrast to \posterbox, the ⟨*environment content*⟩ is allowed to contain *verbatim* material. Note that the implementation of \posterbox is more efficient than the implementation of posterboxenv.

```
\begin{tcbposter}[
  poster = {showframe,height=4cm,spacing=2mm,rows=2},
  boxes  = {size=small,beamer,
            colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\begin{posterboxenv}[title=My title]{name=A,column=2,between=top and bottom}
  My first box.
  \begin{tcblisting}{size=small,colback=yellow!10}
My \textbf{first}
poster listing.
  \end{tcblisting}
\end{posterboxenv}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/name=⟨*name*⟩** (no default, initially @)

Sets ⟨*name*⟩ as reference for the current \posterbox → P. 418 or posterboxenv → P. 418. A TikZ shape name is constructed automatically as combination of /tcb/poster/prefix → P. 415 and ⟨*name*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=2,row=2}{My first box}
\node[below right=4mm,fill=yellow] (X) at (TCBPOSTER@poster.north west) {Example A};
\draw[blue,very thick,->] (X) |- (TCBPOSTER@A);
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/column=⟨*number*⟩** (no default, initially 1)

Places the box at the column denoted by ⟨*number*⟩. If /tcb/posterloc/span → P. 420 is not 1, the box is aligned to the left side of column ⟨*number*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{row=1,column=2,span=2}{First box}
\posterbox{row=2,column=2,span=0.8}{Second box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/column*=⟨*number*⟩** (no default, initially unset)

Places the box at the column denoted by ⟨*number*⟩. If /tcb/posterloc/span → P. 420 is not 1, the box is aligned to the right side of column ⟨*number*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{row=1,column*=2,span=2}{First box}
\posterbox{row=2,column*=2,span=0.8}{Second box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/span=**⟨*number*⟩ (no default, initially 1)

Sets the width of the current box to span ⟨*number*⟩ columns. ⟨*number*⟩ is also allowed to be a real number like 0.5 or 1.7. See /tcb/posterloc/column → P. 419 and /tcb/posterloc/column* → P. 419 for examples.

N 2017-07-03 **/tcb/posterloc/row=**⟨*number*⟩ (no default, initially unset)

If this option is applied, the box is placed at the row denoted by ⟨*number*⟩. Also, the height is set as fixed according to /tcb/posterloc/rowspan.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{row=1,column=1}{First box}
\posterbox{row=1,column=2,rowspan=2}{Second box}
\posterbox[natural height]{row=1,column=3}{Third box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/rowspan=**⟨*number*⟩ (no default, initially 1)

Sets the height of the current box to span ⟨*number*⟩ rows. ⟨*number*⟩ is also allowed to be a real number like 0.5 or 1.7.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{row=1,column=1,rowspan=0.9}{First box}
\posterbox{row=1,column=2,rowspan=1.5}{Second box}
\posterbox{row=1,column=3,rowspan=2}{Third box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/fixed height** (no value, initially 0pt)

Sets the height of the current box span rows as denoted by /tcb/posterloc/rowspan. This can be used, if not /tcb/posterloc/row, but another height placement option is applied.

N 2017-07-03 **/tcb/posterloc/below=**⟨*name*⟩ (no default, initially `top`)

The box is placed below another box with the given ⟨*name*⟩. Also, ⟨*name*⟩ can be a predefined node, see Section 20.2 on page 413.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,below=top}{First box}
\posterbox{name=B,column=1,below=A}{Second box}
\posterbox{name=C,column=2,below=B}{Third box}
\posterbox{name=D,column=3,below=row1}{Fourth box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/above=**⟨*name*⟩ (no default, initially unset)

The box is placed above another box with the given ⟨*name*⟩. Also, ⟨*name*⟩ can be a predefined node, see Section 20.2 on page 413.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,above=bottom}{First box}
\posterbox{name=B,column=1,above=A}{Second box}
\posterbox{name=C,column=2,above=B}{Third box}
\posterbox{name=D,column=3,above=row2}{Fourth box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/at=**⟨*name*⟩ (no default, initially unset)

The box is placed at the position with the given ⟨*name*⟩. This is quite likely a predefined node, see Section 20.2 on page 413.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,at=middle}{First box}
\posterbox{name=B,column=2,at=row1}{Second box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/between=**⟨*name1*⟩ **and** ⟨*name2*⟩ (no default, initially unset)

The box is placed below a box ⟨*name1*⟩ and above another box ⟨*name2*⟩. Also, ⟨*name1*⟩ and ⟨*name2*⟩ can be predefined nodes, see Section 20.2 on page 413.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,below=top}{First box}
\posterbox{name=B,column=1,between=A and bottom}{Second box}
\posterbox{name=C,column=2,above=bottom}{Third box}
\posterbox{name=D,column=2,between=top and C,span=2}{Fourth box}
\posterbox{name=E,column=3,between=D and bottom}{Fifth box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/sequence=**⟨*sequence*⟩ (no default, initially unset)

The box is broken into partial boxes. These partial boxes are placed following the given ⟨*sequence*⟩ of placements. The feasible syntax for the ⟨*sequence*⟩ is:

⟨*column a*⟩ `between` ⟨*name a1*⟩ `and` ⟨*name a2*⟩ `then`
⟨*column b*⟩ `between` ⟨*name b1*⟩ `and` ⟨*name b2*⟩ `then`
⟨*column c*⟩ `between` ⟨*name c1*⟩ `and` ⟨*name c2*⟩ `then`...

Obviously, this places the first part box at ⟨*column a*⟩ between ⟨*name a2*⟩ and ⟨*name a2*⟩. The second box part is placed at ⟨*column b*⟩ between ⟨*name b2*⟩ and ⟨*name b2*⟩, and so on.

```
\begin{tcbposter}[
  poster = {showframe,height=6cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox[adjusted title=A]{name=A,column=1,below=top,span=2}{First box}
\posterbox{name=B,column=2,above=bottom,span=2}{Second box}
\posterbox[adjusted title=C,colframe=red!50!black,colback=red!50]{
  name=C, sequence=1 between A and bottom then
                  2 between A and B then
                  3 between top and B
  }{\lipsum[2]}
\end{tcbposter}
```



N 2017-07-03 **/tcb/placeholder** (style, no value)

If the box content of a /tcb/posterloc/sequence → P. 423 is too short to fill all reserved box parts, the empty boxes are drawn with the /tcb/placeholder style. This style can be redefined, e.g. to /tcb/blankest → P. 244, if nothing should be drawn for empty boxes.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,below=top,span=2}{First box}
\posterbox[colframe=red!50!black,colback=red!50]{
  name=B, sequence=1 between A and bottom then
                  2 between A and bottom then
                  3 between top and bottom
  }{Second box followed by placeholder boxes}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/xshift=**⟨*length*⟩ (no default, initially 0pt)

Horizontal shift of a box by ⟨*length*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,row=1,xshift=6mm}{First box}
\posterbox{name=B,column=2,row=2,xshift=-6mm}{Second box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/yshift=**⟨*length*⟩ (no default, initially `0pt`)

Vertical shift of a box by ⟨*length*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,row=1,yshift=-4mm}{First box}
\posterbox{name=B,column=2,row=2,yshift=4mm}{Second box}
\end{tcbposter}
```



21 Library fitting

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{fitting}
```

21.1 Macros of the Library

\tcboxfit[⟨*options*⟩]{⟨*box content*⟩}

Creates a colored box where the given ⟨*box content*⟩ is fitted to the width and height of the box. A `tcboxfit` has to have a fixed height. If no fixed height is given, a square box is constructed. In principle, most ⟨*options*⟩ for a `tcolorbox` → P. 12 can be used for `\tcboxfit` with some restrictions. A `\tcboxfit` cannot have a lower part and cannot be broken.

```
% \usepackage{lipsum} \tcbuselibrary{raster}
\tcbset{colframe=blue!50!black,colback=red!10!white,
    boxsep=0pt,top=1mm,bottom=1mm,left=1mm,right=1mm,
    fit algorithm=hybrid*,raster equal skip=1mm}
\begin{tcbraster}[raster columns=3,raster valign=bottom]
  \tcboxfit[height=8cm]{\lipsum[1]}
  \tcboxfit[height=4cm]{\lipsum[1]}
  \tcboxfit[height=2cm]{\lipsum[1]}
\end{tcbraster}
\begin{tcbraster}[colback=green!10!white,boxsep=1mm]
  \tcboxfit[height=4cm]{\lipsum[2]}
  \tcboxfit[height=4cm,title=With a title]{\lipsum[2]}
\end{tcbraster}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

With a title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

See Section 23.6 on page 460 for more elaborate methods to create new commands.

\newtcboxfit[⟨*init options*⟩]{\⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Creates a new macro \⟨*name*⟩ based on \tcboxfit→ P. 426. Basically, \newtcboxfit operates like \newcommand. The new macro \⟨*name*⟩ optionally takes ⟨*number*⟩+1 arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying tcboxfit. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.

```
\newtcboxfit{\mybox}{colback=red!5!white,
  colframe=red!75!black,width=4cm,
  height=1.5cm,halign=center}

\mybox{This is my own box.}\par
\mybox{This is my own box with more text
       to be written.}
```

This is my own box.

This is my own box with more text to be written.

```
% \usepackage{lipsum}
\newtcboxfit{\mybox}[2]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  boxsep=1mm,left=0mm,right=0mm,top=0mm,
  bottom=0mm,halign=center,valign=center,
  nobeforeafter,width=#1,height=#2}

\mybox{2.5cm}{1cm}{First box}%
\mybox{2.5cm}{1cm}{Second box with more text}\\
\mybox{5cm}{2cm}{Third box with text}\\
\mybox{5cm}{3cm}{\lipsum[1]}
```

First box

Second box with more text

Third box with text

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
% \usepackage{lipsum}
\newtcboxfit{\mybox}[2][]{colback=red!5!white,
  colframe=red!75!black,
  width=#2,height=#2/3*2,#1}

\mybox[colback=yellow]{5cm}%
  {\lipsum[2]}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

\renewtcboxfit[⟨*init options*⟩]{\⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Operates like \newtcboxfit, but based on \renewcommand instead of \newcommand. An existing macro is redefined.

U 2020-04-24 **\tcbfitdim** (read-only LaTeX length)

This is a LaTeX length adapted automatically by most variants of /tcb/fit algorithm → P. 435. Therefore, it never is to be changed by the user, but may be applied read-only. The \tcbfitdim corresponds to the font size and may also be used to calculate box margins or other distances in dependency. The initial and maximum value for \tcbfitdim is set by /tcb/fit basedim → P. 430.

\tcbfontsize{⟨*factor*⟩}

Selects a font size inside a tcolorbox which is scaled with the given ⟨*factor*⟩ relative to \tcbfitdim. Also see /tcb/fit fontsize macros → P. 431

```
\tcbset{colback=red!5!white,size=small,
  colframe=red!75!black}
\begin{tcolorbox}[fit basedim=10pt]
  {\tcbfontsize{0.25} Very tiny,}\\
  {\tcbfontsize{0.5} Small,}\\
  {\tcbfontsize{1} Normal,}\\
  {\tcbfontsize{2} Large,}\\
  {\tcbfontsize{4} Huge.}
\end{tcolorbox}
```

```
\tcbset{colback=red!5!white,size=small,
  colframe=red!75!black}
\begin{tcolorbox}[fit basedim=10pt,
    fit to height=2cm]
  {\tcbfontsize{0.25} Very tiny,}\\
  {\tcbfontsize{0.5} Small,}\\
  {\tcbfontsize{1} Normal,}\\
  {\tcbfontsize{2} Large,}\\
  {\tcbfontsize{4} Huge.}
\end{tcolorbox}
```

21.2 Option Keys of the Library

The font size for the content of a box with fixed width and fixed height can be adjusted automatically. This is called the *fitbox capture mode*. Note that the fit control algorithm constructs a series of versions for the box and selects the "best". Therefore, the compilation time is quite longer than for a normal box. The algorithm will fail, if a different selected font size does not change the overall size of the box content. The `\tcboxfit` → P. 426 macro uses this algorithm by default.

> **!** The fit control keys are only applicable to unbreakable boxes without a lower part. The box content should not change counters.

`/tcb/fit` (style, initially unset)

Sets the `/tcb/capture` → P. 97 mode to `fitbox`, i. e. enables the font size adjustment algorithm. Thereby, a `tcolorbox` → P. 12 acts like `\tcboxfit` → P. 426 where the given ⟨*box content*⟩ is fitted to the width and height of the box. Therefore, the box has to have a fixed height. If no fixed height is given, a square box is constructed. The font dimension `\tcbfitdim` → P. 428 can also be used to adjust the margins of the box since a box with a tiny font may not need large margins. The number of constructed boxes is saved to the macro `\tcbfitsteps` for analysis.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins}
\newtcolorbox{fitting}[2][]{fit,height=#2,boxsep=1pt,valign=center,opacityupper=0.5,
  top=0.4\tcbfitdim,bottom=0.4\tcbfitdim,left=0.75\tcbfitdim,right=0.75\tcbfitdim,
  enhanced,watermark text={\tcbfitsteps},colframe=blue!75!black,colback=white,#1}

\begin{fitting}{4cm}
\lipsum[1]
\end{fitting}

\begin{fitting}{2cm}
\lipsum[2]
\end{fitting}

\begin{fitting}{1cm}
\lipsum[3]
\end{fitting}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

/tcb/fit to=⟨*width*⟩ and ⟨*height*⟩ (style, initially unset)

Shortcut for using /tcb/fit → P. 429 and setting the ⟨*width*⟩ and ⟨*height*⟩ values separately.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to=3cm and 2cm]
  This box content is fitted to the given
  dimensions.
\end{tcolorbox}
```

This box content is fitted to the given dimensions.

/tcb/fit to height=⟨*height*⟩ (style, initially unset)

Shortcut for using /tcb/fit → P. 429 and setting the ⟨*height*⟩ value separately.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to height=2cm]
  This box content is fitted to the given
  height.
\end{tcolorbox}
```

This box content is fitted to the given height.

/tcb/fit basedim=⟨*length*⟩ (no default, initially 10pt)

Sets the starting font dimension for the font size adjustment algorithm to ⟨*length*⟩. The algorithm never enlarges this dimension. Therefore, the final \tcbfitdim → P. 428 is identical to or small than ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to=4cm and 2cm]
  Too few words for the box.
\end{tcolorbox}

\begin{tcolorbox}[fit to=4cm and 2cm,
  fit basedim=50pt]
  Enough words for the box.
\end{tcolorbox}
```

Too few words for the box.

Enough words for the box.

/tcb/fit skip=⟨*real value*⟩ (no default, initially 1.2)

Sets the skip value of the selected font to ⟨*real value*⟩ times \tcbfitdim → P. 428.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,
  colframe=red!75!black,left=1mm,
  right=1mm,boxsep=0mm}

\begin{tcolorbox}[fit to=5cm and 4cm,
  fit skip=1.0  ]
  \lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

/tcb/fit fontsize macros (style, initially unset)

Redefines the standard LaTeX font size macros \tiny, \scriptsize, \footnotesize, \small, \normalsize, \large, \Large, \LARGE, \huge, and \Huge, to set font sizes relative to the current \tcbfitdim → P. 428. Note that the display skip values for mathematical formulas are respected by the redefined macros. Also see \tcbfontsize → P. 428.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,
  colframe=red!75!black,left=1mm,
  right=1mm,boxsep=0mm}

\begin{tcolorbox}[fit to height=4cm]
  {\Large\bfseries This text is
              not adapted:\par}
  \lipsum[2]
\end{tcolorbox}

\begin{tcolorbox}[fit to height=4cm,
  fit fontsize macros ]
  {\Large\bfseries This text is adapted:\par}
  \lipsum[2]
\end{tcolorbox}
```

This text is not adapted:
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This text is adapted:
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\tcbset{colback=red!5!white,
  colframe=red!75!black,left=1mm,
  right=1mm,boxsep=0mm}

\let\realHuge=\Huge

\begin{tcolorbox}[fit basedim=7pt,
  fontupper=\normalsize,
  fit fontsize macros]
The relative relative font size macros
are also usable without the
\textit{fit} algorithm.\par
{\Huge Adapted Huge} ---
{\realHuge Original Huge}
\end{tcolorbox}
```

The relative relative font size macros are also usable without the *fit* algorithm.
Adapted Huge — Original Huge

```
\tcbset{size=fbox,colback=red!5!white,
  colframe=red!75!black}

\tcboxfit[height=5cm,
  fit fontsize macros,
  fonttitle=\normalsize\bfseries,
  title=Adapted title]
{\lipsum[2]}
```

Adapted title
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/fit height plus=⟨*dimension*⟩ (no default, initially `0pt`)

The box is allowed to enlarge the fixed height up to the given ⟨*dimension*⟩, before a font size fit is applied. An optional `/tcb/fit width plus` is tried after the height adaption.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
  right=1mm,boxsep=0mm,width=3cm,height=3cm,nobeforeafter}

\begin{tcolorbox}[fit]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit,fit height plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit]
\lipsum[2]
\end{tcolorbox}
\begin{tcolorbox}[fit,fit height plus=1cm]
\lipsum[2]
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/fit width plus=⟨*dimension*⟩ (no default, initially `0pt`)

The box is allowed to enlarge the fixed width up to the given ⟨*dimension*⟩, before a font size fit is applied. An optional `/tcb/fit height plus` is tried before the width adaption.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
  right=1mm,boxsep=0mm,width=3cm,height=3cm,nobeforeafter}

\begin{tcolorbox}[fit]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit,fit width plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit]
\lipsum[2]
\end{tcolorbox}
\begin{tcolorbox}[fit,fit width plus=1cm]
\lipsum[2]
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Typically but not necessarily, the optional title of a `tcolorbox` is not part of the fit operation. If a `/tcb/fit width plus` is applied, the title is also adapted to the new width. If counters are increased inside the title text, they may be increased more than one time. To avoid this, you are encouraged to use `/tcb/phantom` → P. 101 or `/tcb/step and label` → P. 101 to set counters or use automatic numbering, see Subsection 5.1 from page 111.

`/tcb/fit width from=`⟨*min*⟩ `to` ⟨*max*⟩ (style, no default)

Sets the box width to ⟨*min*⟩ and allows the width to grow up to ⟨*max*⟩.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
  right=1mm,boxsep=0mm,height=4cm}

\begin{tcolorbox}[fit,width=\linewidth/2]
\lipsum[2]
\end{tcolorbox}\par
\begin{tcolorbox}[fit width from=\linewidth/2 to \linewidth]
\lipsum[2]
\end{tcolorbox}\par
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

/tcb/fit height from=⟨*min*⟩ **to** ⟨*max*⟩ (style, no default)

Sets the box height to ⟨*min*⟩ and allows the height to grow up to ⟨*max*⟩.

```
% \usepackage{lipsum}
\newtcolorbox{mybox}{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  bottom=1mm,right=1mm,boxsep=0mm,width=4cm,nobeforeafter,
  fit height from=1cm to 8cm}

\begin{mybox}
This is a tcolorbox.
\end{mybox}
\begin{mybox}
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{mybox}
\begin{mybox}
\lipsum[2]
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit algorithm=`⟨*name*⟩ (no default, initially `fontsize`)

Sets the algorithm for the fitting process *after* optionally width and height are adapted. In the following, adapting the font size means adapting `\tcbfitdim` → P. 428. Feasible values for ⟨*name*⟩ are:

- `fontsize` (initial): The algorithm is a bisection method that adapts the font size until certain stop conditions are fulfilled. This is the most time-consuming method but it is robust and gives pleasant results.

  > ! The used font has to be freely scalable for this method! Other content than text is not scaled down. The aspect ratio is fully garanteed.

N 2014-10-29

- `fontsize*`: First, the `fontsize` algorithm is applied. If the font was scaled down and the resulting height is too small, the box is squeezed to fit the area.

  > ! The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully garanteed.

- `areasize`: The algorithm calculates the area size for the text without scaling the font. The text box is shaped for the needed aspect ratio in one or two steps. Finally, it is scaled down with a standard `\resizebox` macro.

  > ! The used font has not to be scalable. Every box content is scaled down. The aspect ratio cannot be fully garanteed.

N 2014-10-29

- `areasize*`: The `areasize` algorithm is applied, but if the content was scaled down and the resulting height is too small, the box is squeezed to fit the area.

  > ! The used font has not to be scalable. Every box content is scaled down. The aspect ratio cannot be fully garanteed.

- `hybrid`: First, this algorithm estimates the needed font size in one or two steps. Then an `areasize` fitting as above is a applied.

  > ! The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully garanteed.

N 2014-10-29

- `hybrid*`: First, this algorithm estimates the needed font size in one or two steps. Then an `areasize*` fitting as above is a applied.

  > ! The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully garanteed.

- `squeeze`: The text box is brutally scaled down to fit.

  > ! The aspect ratio is very likely to be horrible. You should not use this method for final documents.

```
% \usepackage{lipsum}
\newtcboxfit{mybox}[1]{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  bottom=1mm,right=1mm,boxsep=0mm,width=3.5cm,height=7cm,nobeforeafter,
  before upper=\textcolor{blue}{\rule{5mm}{5mm}}\ ,
  enhanced,watermark text={\tcbfitsteps},
  fonttitle=\bfseries,adjusted title=#1,fit algorithm=#1}

\mybox{fontsize}{\lipsum[2]}\hfill
\mybox{hybrid}{\lipsum[2]}\hfill
\mybox{areasize}{\lipsum[2]}\hfill
\mybox{squeeze}{\lipsum[2]}

Quality \dotfill versus \dotfill Speed
```

fontsize

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

hybrid

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

areasize

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

squeeze

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Quality . . . . . versus . . . . . Speed

```
% \usepackage{lipsum}
\newtcboxfit{mybox}[2]{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  size=tight,width=7.2cm,height=5cm,nobeforeafter,
  before upper=\textcolor{blue}{\rule{5mm}{5mm}}\ ,
  enhanced,fonttitle=\bfseries,adjusted title=#2,fit algorithm=#1}

\mybox{hybrid}{hybrid (possible gap at end)}{\lipsum[1]}\hfill
\mybox{hybrid*}{hybrid* (no gap but possibly squeezed)}{\lipsum[1]}
```

hybrid (possible gap at end)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

hybrid* (no gap but possibly squeezed)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

> **!** The following options set control parameters for the fit algorithm. Mainly, they apply to the `fontsize` variant, see `/tcb/fit algorithm` → P. 435. The options should be seen as experimental and are likely to change in future versions, if necessary.

`/tcb/fit maxstep=`⟨*number*⟩ (no default, initially `20`)

Sets the maximal step size for the font size adjustment algorithm. In normal situations, the algorithm stops before reaching the intial value of 20 steps. If the box content does not shrink, this value prevents an endless loop.

`/tcb/fit maxfontdiff=`⟨*dimension*⟩ (no default, initially `0.1pt`)

The algorithm stops, if the font size is determined within a deviation of ⟨*dimension*⟩.

`/tcb/fit maxfontdiffgap=`⟨*dimension*⟩ (no default, initially `1pt`)

The algorithm stops, if the number of lines is determined and the font size is determined within a deviation of ⟨*dimension*⟩.

`/tcb/fit maxwidthdiff=`⟨*dimension*⟩ (no default, initially `1pt`)

The algorithm stops, if the (optionally) flexible box width is determined within a deviation of ⟨*dimension*⟩.

`/tcb/fit maxwidthdiffgap=`⟨*dimension*⟩ (no default, initially `10pt`)

The algorithm stops, if the number of lines is determined and the (optionally) flexible box width is determined within a deviation of ⟨*dimension*⟩.

`/tcb/fit warning=`⟨*value*⟩ (no default, initially `off`)

Typically, the fit control algorithm constructs several auxiliary boxes to determine the optimal one. If not switched off, the construction of the auxiliary boxes may produce many `hbox` warnings. This option key changes the `\hbadness` value.

- `off`: Most of `'Underfull \hbox'` and `'Overfull \hbox'` warnings are switched off (including the ones for the finally used box).
- `on`: All warnings for all auxiliary boxes are displayed.
- `final`: Only warnings for the finally used box are displayed. Note that an additional box has to be contructed for theses messages.

22 Library LIB hooks

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{hooks}
```

For the skin related options, the library LIB skins has to be loaded separately.

22.1 Concept of Hooks

A hook is a placeholder in some LaTeX code where additional code can be added. For example, the LaTeX macro `\AtBeginDocument` adds code to a hook which is placed at the beginning of every document.

Several option keys of `tcolorbox` allow providing some code which is added to specific places of a colored box. For example, `/tcb/before upper` → P. 65 places code before the content of the upper part. A following usage of this key overwrites any prior settings.

The library LIB hooks extends `/tcb/before upper` → P. 65 and several more existing keys to "hookable" versions, e. g. `/tcb/before upper app` → P. 439 and `/tcb/before upper pre` → P. 439. The "hookable" keys don't overwrite prior settings but either *app*end or *pre*pend the newly given code to the existing code.

The general naming convention (with some small exceptions) is:

- ⟨*option key*⟩ `app`: works like ⟨*option key*⟩ but *app*ends its code to the existing code.
- ⟨*option key*⟩ `pre`: works like ⟨*option key*⟩ but *pre*pends its code to the existing code.

If the original ⟨*option key*⟩ is used (again), all code will be overwritten. Therefore, the order of the option key usage is crucial.

```
% \usepackage{array,tabularx}
\newcolumntype{Y}{>{\raggedleft\arraybackslash}X}% see tabularx
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title,
  tabularx={X||Y|Y|Y|Y||Y},% this sets `before upper' and `after upper'
  before upper app={Group & One & Two & Three & Four & Sum\\\hline\hline}  }

\begin{tcolorbox}[title=My table]
Red   & 1000.00 & 2000.00 &  3000.00 &  4000.00 & 10000.00\\\hline
Green & 2000.00 & 3000.00 &  4000.00 &  5000.00 & 14000.00\\\hline
Blue  & 3000.00 & 4000.00 &  5000.00 &  6000.00 & 18000.00\\\hline\hline
Sum   & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00
\end{tcolorbox}
```

My table

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

22.2 Box Content Additions

The following option keys extend the options given in Subsection 4.11 from page 64.

/tcb/before title app=⟨*code*⟩ (no default)

Appends the given ⟨*code*⟩ to /tcb/before title →P. 64 *after* the color and font settings and *before* the content of the title.

/tcb/before title pre=⟨*code*⟩ (no default)

Prepends the given ⟨*code*⟩ to /tcb/before title →P. 64 *after* the color and font settings and *before* the content of the title.

/tcb/after title app=⟨*code*⟩ (no default)

Appends the given ⟨*code*⟩ to /tcb/after title →P. 64 *after* the content of the title.

/tcb/after title pre=⟨*code*⟩ (no default)

Prepends the given ⟨*code*⟩ to /tcb/after title →P. 64 *after* the content of the title.

/tcb/before upper app=⟨*code*⟩ (no default)

Appends the given ⟨*code*⟩ to /tcb/before upper →P. 65 or /tcb/before upper* →P. 65 *after* the color and font settings and *before* the content of the upper part.

/tcb/before upper pre=⟨*code*⟩ (no default)

Prepends the given ⟨*code*⟩ to /tcb/before upper →P. 65 or /tcb/before upper* →P. 65 *after* the color and font settings and *before* the content of the upper part.

/tcb/after upper app=⟨*code*⟩ (no default)

Appends the given ⟨*code*⟩ to /tcb/after upper →P. 66 or /tcb/after upper* →P. 66 *after* the content of the upper part.

/tcb/after upper pre=⟨*code*⟩ (no default)

Prepends the given ⟨*code*⟩ to /tcb/after upper →P. 66 or /tcb/after upper* →P. 66 *after* the content of the upper part.

```
% \tcbuselibrary{theorems}

\begin{tcolorbox}[
  ams align,%  this sets `before upper*' and `after upper*'
  colback=yellow!10!white,colframe=red!50!black,
  before upper app={\frac{2}{\sqrt{2}}&=\sqrt{2}.\\},
  after upper pre={\\\sin\left(\frac{\pi}{2}\right)&=1.},
]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty.\\
  \int x^2 ~\text{d}x &= \frac13 x^3 + c.
\end{tcolorbox}
```

$$\frac{2}{\sqrt{2}} = \sqrt{2}. \tag{22}$$

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{23}$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c. \tag{24}$$

$$\sin\left(\frac{\pi}{2}\right) = 1. \tag{25}$$

/tcb/before lower app=⟨*code*⟩ (no default)

Appends the given ⟨*code*⟩ to /tcb/before lower→P. 67 or /tcb/before lower*→P. 67 *after* the color and font settings and *before* the content of the lower part.

/tcb/before lower pre=⟨*code*⟩ (no default)

Prepends the given ⟨*code*⟩ to /tcb/before lower→P. 67 or /tcb/before lower*→P. 67 *after* the color and font settings and *before* the content of the lower part.

/tcb/after lower app=⟨*code*⟩ (no default)

Appends the given ⟨*code*⟩ to /tcb/after lower→P. 68 or /tcb/after lower*→P. 68 *after* the content of the lower part.

/tcb/after lower pre=⟨*code*⟩ (no default)

Prepends the given ⟨*code*⟩ to /tcb/after lower→P. 68 or /tcb/after lower*→P. 68 *after* the content of the lower part.

22.3 Embedding into the Surroundings

The following option keys extend the options given in Subsection 4.14 from page 81.

> **!** The "hookable" versions are usable inside the document. In the preamble, they can only be used after explicit setting of /tcb/before→P. 81 and /tcb/after→P. 81 or by e. g. /tcb/parskip→P. 81.

/tcb/before app=⟨*code*⟩ (no default)

Appends the given ⟨*code*⟩ to /tcb/before→P. 81 before the colored box.

/tcb/before pre=⟨*code*⟩ (no default)

Prepends the given ⟨*code*⟩ to /tcb/before→P. 81 before the colored box.

/tcb/after app=⟨*code*⟩ (no default)

Appends the given ⟨*code*⟩ to /tcb/after→P. 81 after the colored box.

/tcb/after pre=⟨*code*⟩ (no default)

Prepends the given ⟨*code*⟩ to /tcb/after→P. 81 after the colored box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,before app={The box follows:\\[4pt]},
  after app={This is the end.}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

The box follows:

My title

This is a **tcolorbox**.

This is the end.

22.4 Overlays

The following option keys extend the options given in Subsection 4.12 from page 74.

/tcb/overlay app=⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to /tcb/overlay→ P. 74.

```
% \usetikzlibrary{patterns} % preamble
% \tcbuselibrary{skins} % preamble
\tcbset{frogbox/.style={enhanced,colback=green!10,colframe=green!65!black,
  enlarge top by=5.5mm,
  overlay={\foreach \x in {2cm,3.5cm} {
    \begin{scope}[shift={([xshift=\x]frame.north west)}]
      \path[draw=green!65!black,fill=green!10,line width=1mm] (0,0) arc (0:180:5mm);
      \path[fill=black] (-0.2,0) arc (0:180:1mm);
    \end{scope}}}]}}
\tcbset{ribbon/.style={overlay app={%
  \path[fill=blue!75!white,draw=blue,double=white!85!blue,
    preaction={opacity=0.6,fill=blue!75!white},
    line width=0.1mm,double distance=0.2mm,
    pattern=fivepointed stars,pattern color=white!75!blue]
    ([xshift=-0.2mm,yshift=-1.02cm]frame.north east)
    -- ++(-1,1) -- ++(-0.5,0) -- ++(1.5,-1.5) -- cycle;}}}

\begin{tcolorbox}[frogbox,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\begin{tcolorbox}[frogbox,ribbon,title=My title]
This is a \textbf{tcolorbox}.\par
Here, we apply a second overlay.
\end{tcolorbox}
```



/tcb/overlay pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to /tcb/overlay→ P. 74.

/tcb/overlay unbroken app=⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to /tcb/overlay unbroken→ P. 75.

/tcb/overlay unbroken pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to /tcb/overlay unbroken→ P. 75.

/tcb/overlay first app=⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to /tcb/overlay first→ P. 75.

/tcb/overlay first pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to /tcb/overlay first→ P. 75.

`/tcb/overlay middle app=`⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to `/tcb/overlay middle`→P. 75.

`/tcb/overlay middle pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay middle`→P. 75.

`/tcb/overlay last app=`⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to `/tcb/overlay last`→P. 75.

`/tcb/overlay last pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay last`→P. 75.

`/tcb/overlay broken app=`⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to `/tcb/overlay broken`→P. 75.

`/tcb/overlay broken pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay broken`→P. 75.

`/tcb/overlay unbroken and first app=`⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to `/tcb/overlay unbroken and first`→P. 75.

`/tcb/overlay unbroken and first pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay unbroken and first`→P. 75.

`/tcb/overlay middle and last app=`⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to `/tcb/overlay middle and last`→P. 75.

`/tcb/overlay middle and last pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay middle and last`→P. 75.

`/tcb/overlay unbroken and last app=`⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to `/tcb/overlay unbroken and last`→P. 75.

`/tcb/overlay unbroken and last pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay unbroken and last`→P. 75.

N 2014-09-19 `/tcb/overlay first and middle app=`⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to `/tcb/overlay first and middle`→P. 75.

N 2014-09-19 `/tcb/overlay first and middle pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay first and middle`→P. 75.

22.5 Watermarks

The following option keys extend the options given in Subsection 10.3 from page 169.

> **!** Watermarks are special overlays. The LIB hooks library allows the combination of several watermarks and overlays.

/tcb/watermark text app=⟨*text*⟩ (no default)

Appends a /tcb/watermark text → P. 169 to the colored box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark graphics=Basilica_5.png,
  watermark opacity=0.25,
  watermark text app=Basilica,watermark color=Navy
  ]
\lipsum[1-2]
\tcblower
This example uses a public domain picture from\\
\url{http://commons.wikimedia.org/wiki/File:Basilica_5.png}
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This example uses a public domain picture from
http://commons.wikimedia.org/wiki/File:Basilica_5.png

/tcb/watermark text pre=⟨*text*⟩ (no default)

Prepends a /tcb/watermark text → P. 169 to the colored box.

/tcb/watermark text app on=⟨*part*⟩ **is** ⟨*text*⟩ (no default)

Appends a /tcb/watermark text on → P. 169 the named ⟨*part*⟩ of a break sequence.

/tcb/watermark text pre on=⟨*part*⟩ **is** ⟨*text*⟩ (no default)

Prepends a /tcb/watermark text on → P. 169 the named ⟨*part*⟩ of a break sequence.

/tcb/watermark graphics app=⟨*file name*⟩ (no default)

Appends a /tcb/watermark graphics →P. 170 referenced by ⟨*file name*⟩ to the colored box.

/tcb/watermark graphics pre=⟨*file name*⟩ (no default)

Prepends a /tcb/watermark graphics →P. 170 referenced by ⟨*file name*⟩ to the colored box.

/tcb/watermark graphics app on=⟨*part*⟩ **is** ⟨*file name*⟩ (no default)

Appends a /tcb/watermark graphics on →P. 170 the named ⟨*part*⟩ of a break sequence. The picture is referenced by ⟨*file name*⟩.

/tcb/watermark graphics pre on=⟨*part*⟩ **is** ⟨*file name*⟩ (no default)

Prepends a /tcb/watermark graphics on →P. 170 the named ⟨*part*⟩ of a break sequence. The picture is referenced by ⟨*file name*⟩.

/tcb/watermark tikz app=⟨*graphical code*⟩ (no default)

Appends a /tcb/watermark tikz →P. 171 with the given **tikz** ⟨*graphical code*⟩ to the colored box.

/tcb/watermark tikz pre=⟨*graphical code*⟩ (no default)

Prepends a /tcb/watermark tikz →P. 171 with the given **tikz** ⟨*graphical code*⟩ to the colored box.

```
% \usepackage{tikz}
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  watermark color=Navy,watermark opacity=0.25,
  smiley/.style={watermark tikz pre={%
    \path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
    \fill[red] (45:5mm) circle (1mm);
    \fill[red] (135:5mm) circle (1mm);
    \draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);}}}

\begin{tcolorbox}[enhanced,title=My title, watermark text=Watermark,
  smiley]
\lipsum[1-2]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Watermark

/tcb/watermark tikz app on=⟨*part*⟩ **is** ⟨*graphical code*⟩ (no default)

Appends a /tcb/watermark tikz on →P. 171 the named ⟨*part*⟩ of a break sequence.

/tcb/watermark tikz pre on=⟨*part*⟩ **is** ⟨*graphical code*⟩ (no default)

Prepends a /tcb/watermark tikz on →P. 171 the named ⟨*part*⟩ of a break sequence.

22.6 Underlays

The following option keys extend the options given in Section 10.8 on page 199. There are no `app` type keys since underlays are stackable by default.

`/tcb/underlay pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay`→P. 199.

`/tcb/underlay unbroken pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay unbroken`→P. 200.

`/tcb/underlay first pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay first`→P. 200.

`/tcb/underlay middle pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay middle`→P. 200.

`/tcb/underlay last pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay last`→P. 200.

`/tcb/underlay boxed title pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay boxed title`→P. 200.

`/tcb/underlay broken pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay broken`→P. 200.

`/tcb/underlay unbroken and first pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay unbroken and first`→P. 200.

`/tcb/underlay middle and last pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay middle and last`→P. 200.

`/tcb/underlay unbroken and last pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay unbroken and last`→P. 200.

N 2014-09-19 `/tcb/underlay first and middle pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay first and middle`→P. 200.

22.7 Finishes

The following option keys extend the options given in Section 10.9 on page 201. There are no `app` type keys since finishes are stackable by default.

`/tcb/finish pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish`→P. 201.

`/tcb/finish unbroken pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish unbroken`→P. 202.

`/tcb/finish first pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish first`→P. 202.

`/tcb/finish middle pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish middle`→P. 202.

`/tcb/finish last pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish last`→P. 202.

`/tcb/finish broken pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish broken`→P. 202.

`/tcb/finish unbroken and first pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish unbroken and first`→P. 202.

`/tcb/finish middle and last pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish middle and last`→P. 202.

`/tcb/finish unbroken and last pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish unbroken and last`→P. 202.

N 2014-09-19 `/tcb/finish first and middle pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/finish first and middle`→P. 202.

22.8 Skin Code

The following option keys extend the options given in Subsection 9.2 from page 141.

`/tcb/frame code app=`⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to `/tcb/frame code`→P. 141.

`/tcb/frame code pre=`⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to `/tcb/frame code`→P. 141.

`/tcb/interior titled code app=`⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to `/tcb/interior titled code`→P. 141.

```
\begin{tcolorbox}[title=My title,enhanced,colframe=Navy,
  frame code app={\draw[yellow,line width=1cm] (
    frame.south west)--(frame.north east);},
  interior titled code app={\draw[red,line width=1cm]
    (frame.north west)--(frame.south east);},
  ]
\lipsum[1]
\end{tcolorbox}
```



/tcb/interior titled code pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to **/tcb/interior titled code** → P. 141.

/tcb/interior code app=⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to **/tcb/interior code** → P. 142.

/tcb/interior code pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to **/tcb/interior code** → P. 142.

/tcb/segmentation code app=⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to **/tcb/segmentation code** → P. 142.

/tcb/segmentation code pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to **/tcb/segmentation code** → P. 142.

/tcb/title code app=⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to **/tcb/title code** → P. 143.

/tcb/title code pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to **/tcb/title code** → P. 143.

22.9 Extras

The following option keys extend the options given in Section 18.5 on page 385. There are no app type keys since extras are stackable by default.

N 2015-07-16 **/tcb/extras pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras→P. 385.

N 2015-07-16 **/tcb/extras unbroken pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras unbroken→P. 385.

N 2015-07-16 **/tcb/extras first pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras first→P. 385.

N 2015-07-16 **/tcb/extras middle pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras middle→P. 385.

N 2015-07-16 **/tcb/extras last pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras last→P. 385.

N 2015-07-16 **/tcb/extras broken pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras broken→P. 385.

N 2015-07-16 **/tcb/extras unbroken and first pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras unbroken and first→P. 385.

N 2015-07-16 **/tcb/extras middle and last pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras middle and last→P. 385.

N 2015-07-16 **/tcb/extras unbroken and last pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras unbroken and last→P. 385.

N 2015-07-16 **/tcb/extras first and middle pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/extras first and middle→P. 386.

22.10 Listings

The following option keys extend the options given in Section 16 from page 310.

N 2019-07-11 **/tcb/listing options app={⟨*options*⟩}** (no default)

Appends the given ⟨*options*⟩ to /tcb/listing options→P. 317.

N 2019-07-11 **/tcb/listing options pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/listing options→P. 317.

N 2019-07-11 **/tcb/minted options app={⟨*options*⟩}** (no default)

Appends the given ⟨*options*⟩ to /tcb/minted options→P. 320.

N 2019-07-11 **/tcb/minted options pre={⟨*options*⟩}** (no default)

Prepends the given ⟨*options*⟩ to /tcb/minted options→P. 320.

23 Library xparse

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{xparse}
```

This also loads the package `xparse` [13].

The purpose of this library is to give comfortable access to the powerful document command production with `xparse` for `tcolorbox`. See the `xparse` package documentation [13] for details about the argument ⟨*specification*⟩ used in this section.

23.1 Option Keys

/tcb/verbatim (style, no value)

Sets options for a *verbatim* style `\tcbox` → P. 14. Since the indented boxes may contain only very few words, the dimensions are made smaller and `/tcb/nobeforeafter` → P. 81 and `/tcb/tcbox raise base` → P. 99 are set.

```
\DeclareTotalTCBox{\myverb}{ v }{verbatim,
  colframe=red!75!black,colupper=blue}{#1}

\myverb{\textbf} is a \myverb{\LaTeX} command.
```

`\textbf` is a `\LaTeX` command.

/tcb/IfNoValueTF={⟨*argument*⟩}{⟨*true options*⟩}{⟨*false options*⟩} (no default)

N 2020-09-16 **/tcb/IfNoValueT**={⟨*argument*⟩}{⟨*true options*⟩} (no default)

N 2020-09-16 **/tcb/IfNoValueF**={⟨*argument*⟩}{⟨*false options*⟩} (no default)

Wraps the `\IfNoValue(TF)` command(s) of `xparse` for option setting. If the ⟨*argument*⟩ has no value, the ⟨*true options*⟩ are set. Otherwise, the ⟨*false options*⟩ are set.

```
\DeclareTColorBox{mybox}{ o }{colframe=red!75!black,
  IfNoValueTF={#1}{colback=red!5!white}{enhanced,interior style image=#1}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[goldshade.png]
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox.

/tcb/IfValueTF={⟨*argument*⟩}{⟨*true options*⟩}{⟨*false options*⟩} (no default)
N 2020-09-16 /tcb/IfValueT={⟨*argument*⟩}{⟨*true options*⟩} (no default)
N 2020-09-16 /tcb/IfValueF={⟨*argument*⟩}{⟨*false options*⟩} (no default)

Wraps the `\IfValue(TF)` command(s) of `xparse` for option setting. If the ⟨*argument*⟩ has a value, the ⟨*true options*⟩ are set. Otherwise, the ⟨*false options*⟩ are set.

```
\DeclareTColorBox{mybox}{ o }{colframe=red!75!black,colback=red!5!white,
  IfValueT={#1}{title={\flqq #1\frqq},fonttitle=\bfseries}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[My title]
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

«My title»

This is a tcolorbox.

/tcb/IfBooleanTF={⟨*argument*⟩}{⟨*true options*⟩}{⟨*false options*⟩} (no default)
N 2020-09-16 /tcb/IfBooleanT={⟨*argument*⟩}{⟨*true options*⟩} (no default)
N 2020-09-16 /tcb/IfBooleanF={⟨*argument*⟩}{⟨*false options*⟩} (no default)

Wraps the `\IfBoolean(TF)` command(s) of `xparse` for option setting. If the ⟨*argument*⟩ is `\BooleanTue`, the ⟨*true options*⟩ are set. If the ⟨*argument*⟩ is `\BooleanFalse`, the ⟨*false options*⟩ are set.

```
\DeclareTColorBox{mybox}{ s }{colframe=red!75!black,
  IfBooleanTF={#1}{colback=yellow!50!red}{colback=red!5!white}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}*
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox.

23.2 Producing tcolorbox Environments and Commands

\DeclareTColorBox[⟨*init options*⟩]{⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Creates a new environment ⟨*name*⟩ based on tcolorbox^{→ P. 12}.
Basically, \DeclareTColorBox operates like \DeclareDocumentEnvironment. This means, the new environment ⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying tcolorbox^{→ P. 12}.
Note that /tcb/savedelimiter^{→ P. 26} is set to the given ⟨*name*⟩ automatically.
The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.
The new environment is always created, irrespective of an already existing environment with the same name.

```
% counter from previous example
\DeclareTColorBox[use counter from=pabox]{mybox}{ O{red} m d"" !O{} }
  {enhanced,colframe=#1!75!black,colback=#1!5!white,
   fonttitle=\bfseries,title={\thetcbcounter~#2},
   IfValueTF={#3}{watermark text={#3}}{},#4}

\begin{mybox}{My title}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[blue]{My title}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[green]{My title}"My Watermark"
This is a tcolorbox.
\end{mybox}

\begin{mybox}[yellow]{My title}[colbacktitle=yellow!50!white,coltitle=black]
This is a tcolorbox.
\end{mybox}

\begin{mybox}[purple]{My title}"All together"[coltitle=yellow]
This is a tcolorbox.
\end{mybox}
```

23.1 My title

This is a tcolorbox.

23.2 My title

This is a tcolorbox.

23.3 My title

This is a tcolorbox. My Watermark

23.4 My title

This is a tcolorbox.

23.5 My title

This is a tcolorbox. All together

`\NewTColorBox[⟨init options⟩]{⟨name⟩}{⟨specification⟩}{⟨options⟩}`

Operates like `\DeclareTColorBox` → P. 451, but based on `\NewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An error is issued if ⟨*name*⟩ has already been defined.

`\RenewTColorBox[⟨init options⟩]{⟨name⟩}{⟨specification⟩}{⟨options⟩}`

Operates like `\DeclareTColorBox` → P. 451, but based on `\RenewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An existing environment is redefined.

`\ProvideTColorBox[⟨init options⟩]{⟨name⟩}{⟨specification⟩}{⟨options⟩}`

Operates like `\DeclareTColorBox` → P. 451, but based on `\ProvideDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. The environment ⟨*name*⟩ is only created if it is not already defined.

\DeclareTotalTColorBox[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Creates a new command \⟨*name*⟩ based on tcolorbox→ P. 12. In contrast to \DeclareTColorBox→ P. 451, also the ⟨*content*⟩ of the tcolorbox is specified.
Basically, \DeclareTotalTColorBox operates like \DeclareDocumentCommand. This means, the new command \⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying tcolorbox→ P. 12 which is filled with the specified ⟨*content*⟩.
Note that /tcb/savedelimiter→ P. 26 is set to the given ⟨*name*⟩ automatically.
The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.
The new command is always created, irrespective of an already existing command with the same name.

```
\DeclareTotalTColorBox{\diabox}{ O{} v  m }
  { bicolor,nobeforeafter,equal height group=diabox,width=5.7cm,
    fonttitle=\bfseries\ttfamily,adjusted title={#2},center title,
    colframe=blue!20!black,leftupper=0mm,rightupper=0mm,colback=black!75!white,#1}
  { \tikz\path[fill zoom image={#2}] (0,0) rectangle (\linewidth,4cm);%
    \tcblower#3}

\diabox{blueshade.png}{Created with |GIMP|.\\\url{http://www.gimp.org}}
\diabox{goldshade.png}{Created with |GIMP|.\\\url{http://www.gimp.org}}
```

\NewTotalTColorBox[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like \DeclareTotalTColorBox, but based on \NewDocumentCommand instead of \DeclareDocumentCommand. An error is issued if \⟨*name*⟩ has already been defined.

\RenewTotalTColorBox[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like \DeclareTotalTColorBox, but based on \RenewDocumentCommand instead of \DeclareDocumentCommand. An existing command is redefined.

\ProvideTotalTColorBox[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like \DeclareTotalTColorBox, but based on \ProvideDocumentCommand instead of \DeclareDocumentCommand. The command \⟨*name*⟩ is only created if it is not already defined.

23.3 Producing tcbox Commands

\DeclareTCBox[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Creates a new command \⟨*name*⟩ based on \tcbox→ P. 14. Basically, \DeclareTCBox operates like \DeclareDocumentCommand. This means, the new command \⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying \tcbox→ P. 14.
Note that /tcb/savedelimiter→ P. 26 is set to the given ⟨*name*⟩ automatically.
The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.
The new command is always created, irrespective of an already existing command with the same name.

```
% counter from previous example
\DeclareTCBox[use counter from=pabox]{\mybox}{ s m s }
{ nobeforeafter,colback=red!5!white,colframe=red!75!black,
  title={#2 (Box \thetcbcounter)},fonttitle=\bfseries,
  IfBooleanTF={#1}{enhanced,drop shadow}{},
  IfBooleanTF={#3}{colbacktitle=red!50!white}{}  }

\mybox{Bird}{This is my first box.}
  \hfill
\mybox*{Tree}{This is my second box.}
  \par\bigskip
\mybox{Bike}*{This is my third box.}
  \hfill
\mybox*{City}*{This is my fourth box.}
```

Bird (Box 23.6)
This is my first box.

Tree (Box 23.7)
This is my second box.

Bike (Box 23.8)
This is my third box.

City (Box 23.9)
This is my fourth box.

\NewTCBox[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBox, but based on \NewDocumentCommand instead of \DeclareDocumentCommand. An error is issued if \⟨*name*⟩ has already been defined.

\RenewTCBox[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBox, but based on \RenewDocumentCommand instead of \DeclareDocumentCommand. An existing command is redefined.

\ProvideTCBox[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBox, but based on \ProvideDocumentCommand instead of \DeclareDocumentCommand. The command \⟨*name*⟩ is only created if it is not already defined.

`\DeclareTotalTCBox[⟨init options⟩]{\⟨name⟩}{⟨specification⟩}{⟨options⟩}{⟨content⟩}`

Creates a new command \⟨*name*⟩ based on `\tcbox` → P. 14. In contrast to `\DeclareTCBox` → P. 454, also the ⟨*content*⟩ of the `tcbox` is specified.
Basically, `\DeclareTotalTCBox` operates like `\DeclareDocumentCommand`. This means, the new command \⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying `\tcbox` → P. 14 which is filled with the specified ⟨*content*⟩.
Note that `/tcb/savedelimiter` → P. 26 is set to the given ⟨*name*⟩ automatically.
The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.
The new command is always created, irrespective of an already existing command with the same name.

```
\DeclareTotalTCBox{\myverb}{ O{red} v !O{} }
{ fontupper=\ttfamily,nobeforeafter,tcbox raise base,arc=0pt,outer arc=0pt,
  top=0pt,bottom=0pt,left=0mm,right=0mm,
  leftrule=0pt,rightrule=0pt,toprule=0.3mm,bottomrule=0.3mm,boxsep=0.5mm,
  colback=#1!10!white,colframe=#1!50!black,#3}{#2}

To set a word \textbf{bold} in \myverb{\LaTeX}, use
\myverb[green]{\textbf{bold}}. Alternatively, write
\myverb[yellow]{{\bfseries bold}}.
In \myverb[blue]{\LaTeX}[enhanced,fuzzy halo], other font settings are
done in the same way, e.\,g. \myverb{\textit}, \myverb{\itshape}\\
or \myverb[brown]{\texttt}, \myverb[brown]{\ttfamily}.
```

To set a word **bold** in `\LaTeX`, use `\textbf{bold}`. Alternatively, write `{\bfseries bold}`. In `\LaTeX`, other font settings are done in the same way, e. g. `\textit`, `\itshape` or `\texttt`, `\ttfamily`.

The next example uses `\lstinline` from the `listings` package to typeset the verbatim content.

```
% \usepackage{listings} or \tcbuselibrary{listings}
\DeclareTotalTCBox{\commandbox}{ s v }
{verbatim,colupper=white,colback=black!75!white,colframe=black}
{\IfBooleanTF{#1}{\textcolor{red}{\ttfamily\bfseries > }}{}%
  \lstinline[language=command.com,keywordstyle=\color{blue!35!white}\bfseries]^#2^}

\commandbox*{cd "My Documents"} changes to directory \commandbox{My Documents}.

\commandbox*{dir /A} lists the directory content.

\commandbox*{copy example.txt d:\target} copies \commandbox{example.txt} to
  \commandbox{d:\target}.
```

`> cd "My␣Documents"` changes to directory `My Documents`.
`> dir /A` lists the directory content.
`> copy example.txt d:\target` copies `example.txt` to `d:\target`.

`\NewTotalTCBox[⟨init options⟩]{\⟨name⟩}{⟨specification⟩}{⟨options⟩}{⟨content⟩}`

Operates like `\DeclareTotalTCBox` → P. 455, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\⟨name⟩` has already been defined.

`\RenewTotalTCBox[⟨init options⟩]{\⟨name⟩}{⟨specification⟩}{⟨options⟩}{⟨content⟩}`

Operates like `\DeclareTotalTCBox` → P. 455, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

`\ProvideTotalTCBox[⟨init options⟩]{\⟨name⟩}{⟨specification⟩}{⟨options⟩}{⟨content⟩}`

Operates like `\DeclareTotalTCBox` → P. 455, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\⟨name⟩` is only created if it is not already defined.

`\tcboxverb[⟨options⟩]{⟨verbatim box content⟩}`

Creates a colored box based on `\tcbox` → P. 14 which is fitted to the width of the given ⟨*verbatim box content*⟩. The underlying `\tcbox` → P. 14 is styled with `/tcb/verbatim` → P. 449 plus the given ⟨*options*⟩. The difference to `\tcbox` → P. 14 is that the ⟨*verbatim box content*⟩ is interpreted *verbatim*. Therefore, `\tcboxverb` acts similar to `\verb`.

```
\tcboxverb{\LaTeX}, \tcboxverb[colback=blue!10!white,colupper=blue]{\LaTeX},
\tcboxverb[blank,fuzzy halo]{\LaTeX}, \tcboxverb[beamer]{\LaTeX},
\tcboxverb[enhanced,skin=enhancedmiddle jigsaw,colframe=red]{\LaTeX}.
```

`\LaTeX`, `\LaTeX`, `\LaTeX`, `\LaTeX`, `\LaTeX`.

23.4 Producing tcblisting Environments

Besides LIB xparse, the following commands also need the LIB listings library to be included.

\DeclareTCBListing[⟨*init options*⟩]{⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Creates a new environment ⟨*name*⟩ based on tcblisting→ P. 311.
Basically, \DeclareTCBListing operates like \DeclareDocumentEnvironment. This means, the new environment ⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying tcblisting→ P. 311.
Note that /tcb/savedelimiter→ P. 26 is set to the given ⟨*name*⟩ automatically.
The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.
The new environment is always created, irrespective of an already existing environment with the same name.

```
\DeclareTCBListing{mybox}{ s O{} m }{%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  IfBooleanTF={#1}
    {listing side text}
    {text side listing},
  title=#3,#2}

\begin{mybox}{Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
\bigskip

\begin{mybox}*{Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
\bigskip

\begin{mybox}[colback=yellow]
  {Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
```

Listing Box

This is my LaTeX box. | This is my \LaTeX\ box.

Listing Box

This is my \LaTeX\ box. | This is my LaTeX box.

Listing Box

This is my LaTeX box. | This is my \LaTeX\ box.

\NewTCBListing[⟨*init options*⟩]{⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBListing, but based on \NewDocumentEnvironment instead of \DeclareDocumentEnvironment. An error is issued if ⟨*name*⟩ has already been defined.

\RenewTCBListing[⟨*init options*⟩]{⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBListing, but based on \RenewDocumentEnvironment instead of \DeclareDocumentEnvironment. An existing environment is redefined.

\ProvideTCBListing[⟨*init options*⟩]{⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBListing, but based on \ProvideDocumentEnvironment instead of \DeclareDocumentEnvironment. The environment ⟨*name*⟩ is only created if it is not already defined.

With date of 2018-05-12, the `xparse` [13] package changed the argument collection process. Now, spaces are ignored which leads to a serious change for listing environments ending with an optional argument like `O{}`. The former behaviour of respecting spaces can be preserved by adding a «`!`». Note that the following code uses `!O{}` now.

- For older `xparse` versions, the following code is correct when using `O{}`.
- For `xparse` of 2018-05-12, only the first two examples of the following code using `O{}` are really «good» – all others do not work.
- For `xparse` of 2018-05-12 and later, the following code is correct when using `!O{}`.

Caveats of using an environment ending with an optional argument

```
\DeclareTCBListing{mybox}{ !O{} }{listing only,#1}

\begin{mybox}[colframe=red]
\good
\end{mybox}

\begin{mybox}[colframe=red]\good\end{mybox}

\begin{mybox}
\good
\end{mybox}

\begin{mybox} \good\end{mybox}

\begin{mybox}\bad!\end{mybox}

\begin{mybox}
[\good]
\end{mybox}

\begin{mybox} [\good]\end{mybox}

\begin{mybox}[\bad!]\end{mybox}
```

23.5 Producing tcbinputlisting Commands

! The following commands need the LIB listings library to be included.

\DeclareTCBInputListing[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Creates a new command \⟨*name*⟩ based on \tcbinputlisting → P. 313. Basically, \DeclareTCBInputListing operates like \DeclareDocumentCommand. This means, the new command \⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying \tcbinputlisting → P. 313.
The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.
The new command is always created, irrespective of an already existing command with the same name.

```
% counter from previous example
\DeclareTCBInputListing[use counter from=pabox]{\mylisting}{ O{} O{red} m }{%
  listing file={#3},title=Listing~\thetcbcounter,
  colback=#2!5!white,colframe=#2!50!black,colbacktitle=#2!75!black,
  fonttitle=\bfseries,listing only,#1}

\mylisting[before upper=\textit{This is the included file content:}]
  [blue]{\jobname.tcbtemp}
```

Listing 23.10

This is the included file content:

```
% counter from previous example
\DeclareTCBInputListing[use counter from=pabox]{\mylisting}{ O{}
    O{red} m }{%
  listing file={#3},title=Listing~\thetcbcounter,
  colback=#2!5!white,colframe=#2!50!black,colbacktitle=#2!75!black,
  fonttitle=\bfseries,listing only,#1}

\mylisting[before upper=\textit{This is the included file content:}]
  [blue]{\jobname.tcbtemp}
```

\NewTCBInputListing[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBInputListing, but based on \NewDocumentCommand instead of \DeclareDocumentCommand. An error is issued if \⟨*name*⟩ has already been defined.

\RenewTCBInputListing[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBInputListing, but based on \RenewDocumentCommand instead of \DeclareDocumentCommand. An existing command is redefined.

\ProvideTCBInputListing[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBInputListing, but based on \ProvideDocumentCommand instead of \DeclareDocumentCommand. The command \⟨*name*⟩ is only created if it is not already defined.

23.6 Producing tboxfit Commands

The following commands need the LIB fitting library to be included.

\DeclareTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Creates a new command \⟨*name*⟩ based on \tcboxfit→ P. 426. Basically, \DeclareTCBoxFit operates like \DeclareDocumentCommand. This means, the new command \⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying \tcboxfit→ P. 426.
Note that /tcb/savedelimiter→ P. 26 is set to the given ⟨*name*⟩ automatically.
The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.
The new command is always created, irrespective of an already existing command with the same name.

```
% \usepackage{lipsum}

\DeclareTCBoxFit{\mybox}{ O{} m !o }
 {colback=red!5!white,
  colframe=red!75!black,
  width=#2,height=#2/3*2,
  IfValueTF={#3}{height=#3}{},
  #1}

\mybox[colback=yellow]{5cm}%
  {\lipsum[2]}

\mybox[colback=yellow]{5cm}[4cm]{\lipsum[2]}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

\NewTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBoxFit, but based on \NewDocumentCommand instead of \DeclareDocumentCommand. An error is issued if \⟨*name*⟩ has already been defined.

\RenewTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBoxFit, but based on \RenewDocumentCommand instead of \DeclareDocumentCommand. An existing command is redefined.

\ProvideTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like \DeclareTCBoxFit, but based on \ProvideDocumentCommand instead of \DeclareDocumentCommand. The command \⟨*name*⟩ is only created if it is not already defined.

\DeclareTotalTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Creates a new command \⟨*name*⟩ based on \tcboxfit→ P. 426. In contrast to \DeclareTCBoxFit→ P. 460, also the ⟨*content*⟩ of the tcboxfit is specified.
Basically, \DeclareTotalTCBoxFit operates like \DeclareDocumentCommand. This means, the new command \⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying \tcboxfit→ P. 426 which is filled with the specified ⟨*content*⟩.
Note that /tcb/savedelimiter→ P. 26 is set to the given ⟨*name*⟩ automatically.
The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 111.
The new command is always created, irrespective of an already existing command with the same name.

```
% \usepackage{lipsum}

\DeclareTotalTCBoxFit{\multibox}{ O{} m O{10} m }
 {nobeforeafter,colback=red!5!white,colframe=red!75!black,width=#2,height=#2/3*2,
  valign=center,#1}
 { \foreach \n in {1,...,#3} { #4} }

\multibox{5cm}{I shall not repeat.}
\multibox[colframe=blue!75!white]{5cm}[20]{I shall not repeat.}\\
\multibox[colback=yellow,height=5cm]{14cm}[100]{I shall not repeat.}
```

I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat.

I shall not repeat. I shall not repeat.
I shall not repeat. I shall not repeat.
I shall not repeat. I shall not repeat.
I shall not repeat. I shall not repeat.
I shall not repeat. I shall not repeat.
I shall not repeat. I shall not repeat.
I shall not repeat. I shall not repeat.
I shall not repeat. I shall not repeat.
I shall not repeat. I shall not repeat.
I shall not repeat. I shall not repeat.

I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I
shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat.

\NewTotalTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like \DeclareTotalTCBoxFit, but based on \NewDocumentCommand instead of \DeclareDocumentCommand. An error is issued if \⟨*name*⟩ has already been defined.

\RenewTotalTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like \DeclareTotalTCBoxFit, but based on \RenewDocumentCommand instead of \DeclareDocumentCommand. An existing command is redefined.

\ProvideTotalTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like \DeclareTotalTCBoxFit, but based on \ProvideDocumentCommand instead of \DeclareDocumentCommand. The command \⟨*name*⟩ is only created if it is not already defined.

24 Library LIB external

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{external}
```

The purpose of this library is to support externalization of document snippets like graphics or boxes which can be compiled stand-alone. These snippets are written to external files, compiled and the resulting pdf files are included to the main document as images. The whole procedure saves compilation time, if such a snippet is costly to compile but needs to compile just once or very seldom.

There are very good alternatives to this library. One should consider the `standalone` package or the Ti*k*Z externalization library instead. The LIB external library is something in between and can be seen as poor man variant of the Ti*k*Z externalization library.

The main differences between Ti*k*Z externalization and LIB external are:

- Ti*k*Z `external` compiles the whole original document in a sophisticated way while LIB external uses only the preamble or a part of the preamble of the original document.
- Ti*k*Z `external` can automatically externalize all `tikzpicture` environments while LIB external externalizes marked snippets only.
- Code snippets to be externalized by LIB external are not restricted to `tikzpicture` environments. But these snippets have to be stand-alone without dependencies to the rest of the document.

Why should somebody use LIB external instead of the more powerful Ti*k*Z `external`? One reason could be compilation speed, but the main reason for creating the library at all was that Ti*k*Z `external` tends to choke on complicated documents where the sophisticated mechanism stumbles. Since LIB external does not use the original document body for compilation, this cannot happen.

> **!** Source snippets are compiled, if their `md5` checksum has changed. They are not compiled automatically, if option settings are changed or anything outside the snippet is changed. Use `/tcb/external/force remake` → P. 463 to force compilation in this case or simply delete the externalized pdf oder md5 files.

> **!** To use the externalization options, the compiler has to be called with the `-shell-escape` permission to authorize potentially dangerous system calls. Be warned that this is a security risk.

24.1 Preparation of a Document for Externalization

The preamble of the main document has to contain the \tcbEXTERNALIZE command. Without this command, no externalization operation will be executed.

N 2015-03-11 **\tcbEXTERNALIZE**

It is mandatory for externalization that this command is used once in the preamble of the main document. Every setting *before* \tcbEXTERNALIZE will also be used for compiling an external snippet. Every setting *after* \tcbEXTERNALIZE will be ignored for compiling an external snippet. Place this command right before \begin{document}, if you are not absolutely sure about another place.
The main document has to look like the following:

```
\documentclass[a4paper]{book}%   for example
\usepackage{...}%                 anything
% ...
% Tpyically, all or the very most settings for the document.

\tcbEXTERNALIZE% Typically, just before \begin{document}

% Additional settings which are ABSOLUTELY irrelevant for the
% stand-alone snippets.
%
\begin{document}
  % The document.
  % This also contains the marked snippets for externalization.
\end{document}
```

During compilation, a /tcb/external/runner file is dynamically created (several times). This is the actual main file for compiling an externalized snippet.

N 2015-03-11 **/tcb/external/runner=⟨*file name*⟩** (no default, initially \jobname_run.tex)

Sets the ⟨*file name*⟩ for dynamically created runner file. This is the actual main file for a document snippet. Typically, the initial setting is not needed to be changed.

```
\tcbset{external/runner=myrunner.tex}
```

N 2015-03-11 **/tcb/external/prefix=⟨*text*⟩** (no default, initially external/)

The ⟨*text*⟩ is prefixed to any /tcb/external/name → P. 465 for an externalization snippet. The initial setting implies saving all snippets into an external/ subdirectory. Depending on the operation system, the subdirectory may have to be created manually once.

```
% Use a 'real' prefix instead of writing into a subdirectory:
\tcbset{external/prefix=ext_}
```

N 2015-03-11 **/tcb/external/externalize=true|false** (default true, initially true)

If set to true, the marked snippets are compiled if necessary. If set to false, the marked snippets are not compiled but included as text. /tcb/external/externalize can only be used after \tcbEXTERNALIZE.

N 2015-03-11 **/tcb/external/force remake=true|false** (default true, initially false)

If set to true, the marked snippets are always compiled. If set to true, the marked snippets are compiled only if necessary. The necessity is given, if a compiled pdf file is missing or the md5 checksum of the source snippet has changed.

N 2015-03-11 U 2017-02-24 **/tcb/external/!** (style)

Shortcut for setting /tcb/external/force remake to true.

N 2015-06-12 U 2017-02-24 **/tcb/external/-** (style)

Shortcut for setting /tcb/external/externalize to false.

24.2 Marking Externalization Snippets

N 2015-03-11

```
\begin{tcbexternal}[⟨options⟩]{⟨name⟩}
  ⟨environment content⟩
\end{tcbexternal}
```

Marks the environment content as a snippet for externalization. Typically, the content is a `tikzpicture` or something similar. It is important to note that the snippet should not have any dependencies with the rotation of the document, e.g. referencing counters or setting counters is not possible. The ⟨*name*⟩ is automatically prefixed with `/tcb/external/prefix` → P. 463. In combination, this has to be a unique file name. It is advised to not use spaces or umlauts for the name. The ⟨*options*⟩ are keys from the `/tcb/external/` key tree.

```
\begin{tcbexternal}{example_tikzpicture}
  \begin{tikzpicture}
    \path[fill=yellow!50!white] (0,0) circle (11mm);
    \path[fill=white] (0,0) circle (9mm);
    \foreach \w/\c in {90/red,210/green,330/blue}
      {\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
  \end{tikzpicture}
\end{tcbexternal}
```



If a `tcolorbox` → P. 12 is externalized, one should use `/tcb/nobeforeafter` → P. 81 for the box. Indention and distances to the text before and after have to be given separately outside the `tcbexternal` environment.

```
\noindent%
\begin{tcbexternal}[minipage]{example_tcolorbox}
  \begin{tcolorbox}[nobeforeafter,enhanced,
      fonttitle=\bfseries,title=Externalized Box,
      colframe=red!50!black,drop fuzzy shadow,
      interior style={fill overzoom image=goldshade.png}]
    This complete tcolorbox is externalized. One cannot use numbered
    boxes here. Note the \texttt{minipage} option which tells the
    current line width to the external snippet.
  \end{tcolorbox}
\end{tcbexternal}
```

Externalized Box

This complete tcolorbox is externalized. One cannot use numbered boxes here. Note the `minipage` option which tells the current line width to the external snippet.

```
\begin{tcolorbox}[nobeforeafter,enhanced,
      fonttitle=\bfseries,title=Externalized Box,
      colframe=blue!50!black,
      interior style={fill overzoom image=blueshade.png}]
  \begin{tcbexternal}[minipage]{example_tcolorbox2}
    \color{white}%
    The interior of the tcolorbox is externalized.
    One can use numbered boxes without problems.
    Note that the text color has to be set for the text manually
    since it is converted into an image.
  \end{tcbexternal}
\end{tcolorbox}
```

Externalized Box

The interior of the tcolorbox is externalized. One can use numbered boxes without problems. Note that the text color has to be set for the text manually since it is converted into an image.

```
\begin{tcbexternal}[minipage]{example_tabularx}
  \newcolumntype{Y}{>{\raggedleft\arraybackslash}X}%
  \begin{tabularx}{\linewidth}{|l||Y|Y|Y|Y||Y|}\hline
    Group & One & Two & Three & Four & Sum\\\hline\hline
    Red & 1000.00 & 2000.00 & 3000.00 & 4000.00 & 10000.00\\\hline
    Green & 2000.00 & 3000.00 & 4000.00 & 5000.00 & 14000.00\\\hline
    Blue & 3000.00 & 4000.00 & 5000.00 & 6000.00 & 18000.00\\\hline\hline
    Sum & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00\\\hline
  \end{tabularx}
\end{tcbexternal}
```

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

N 2015-03-11 **/tcb/external/name=**⟨*name*⟩ (no default, initially `unnamed`)

The ⟨*name*⟩ is automatically prefixed with `/tcb/external/prefix` → P. 463. In combination, this has to be a unique file name for externalization. Typically, this key is not used directly but is set indirectly as mandatory parameter, see `tcbexternal` → P. 464.

N 2015-03-11

```
\begin{extcolorbox}[⟨options⟩]{⟨name⟩}[⟨tcolorbox options⟩]
  ⟨environment content⟩
\end{extcolorbox}
```

This is an externalized version of `tcolorbox` → P. 12 created using `\newtcbexternalizetcolorbox` → P. 471:

```
\newtcbexternalizetcolorbox{extcolorbox}{tcolorbox}{}{}
```

⟨*options*⟩ and ⟨*name*⟩ are given to the underlying `tcbexternal` → P. 464 environment, while ⟨*tcolorbox options*⟩ are given to `tcolorbox` → P. 12.

! Note that you should not redefine `/tcb/before` → P. 81 and `/tcb/after` → P. 81 inside the ⟨*tcolorbox options*⟩, since the externalized version would not be identical to the non-externalized otherwise.

```
\begin{extcolorbox}[minipage]{example_extcolorbox}
  [ enhanced,colframe=red!50!black,colback=yellow!10,
    fonttitle=\bfseries,drop fuzzy shadow,
    title=My external box ]

  This box is completely externalized.

  \begin{tcolorbox}[colframe=blue,colback=blue!5,before skip=6pt]
  Inner box.
  \end{tcolorbox}
\end{extcolorbox}
```

My external box

This box is completely externalized.

Inner box.

!
- **Never** externalize numbered boxes.
- **Never** externalize boxes which contain references to other things, e.g. using `\ref` or `\cite`.
- **Never** externalize breakable boxes.

N 2015-03-11

```
\begin{extikzpicture}[⟨options⟩]{⟨name⟩}[⟨tikz options⟩]
  ⟨environment content⟩
\end{extikzpicture}
```

This is an externalized version of `tikzpicture` created using `\newtcbexternalizeenvironment` → P. 471:

```
\newtcbexternalizeenvironment{extikzpicture}{tikzpicture}{}{}{}
```

⟨*options*⟩ and ⟨*name*⟩ are given to the underlying `tcbexternal` → P. 464 environment, while ⟨*tikz options*⟩ are given to `tikzpicture`.

```
\begin{center}
\begin{extikzpicture}[
  preamble={\usepackage{pgfplots}},  % add package for external graph
  input source on error=false,       % do not load source on error
]{example_pgfplots}
  \pgfplotsset{width=12cm}
  \begin{axis}[3d box=background,grid=major,
    xlabel=$x$, ylabel=$y$, zlabel=$z$, view/h=40,
    mesh/interior colormap name=hot,
    colormap/blackwhite,
    z buffer=sort,domain=0:90,y domain=0:60,
    zmin=0,zmax=2,z post scale=1.2,
    ]
  \addplot3[surf,mesh/interior colormap name=blackwhite,
    colormap/hot,] ( {cos(x)},{sin(x)}, {2*sin(y)} );
  \addplot3[surf] ( {2*cos(x)*cos(y)},{2*sin(x)*cos(y)}, {2*sin(y)} );
  \end{axis}
\end{extikzpicture}
\end{center}
```



N 2015-03-11 **/tcb/externalize listing=⟨*name*⟩** (style, no default)

The text content of a tcblisting → P. 311 is externalized with the given ⟨*name*⟩. Note that the listing part is not externalized.

```
\begin{tcblisting}{externalize listing=example_listing,
  bicolor,colback=yellow!10,colframe=yellow!50!black,
  colbacklower=white,center lower}
\begin{tikzpicture}
  \path[fill=yellow!50!white] (0,0) circle (11mm);
  \path[fill=white] (0,0) circle (9mm);
  \foreach \w/\c in {90/red,210/green,330/blue}
    {\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{tcblisting}
```

```
\begin{tikzpicture}
  \path[fill=yellow!50!white] (0,0) circle (11mm);
  \path[fill=white] (0,0) circle (9mm);
  \foreach \w/\c in {90/red,210/green,330/blue}
    {\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



N 2015-03-11 **/tcb/externalize listing!=⟨*name*⟩** (style, no default)

Combination of /tcb/externalize listing and /tcb/external/force remake → P. 463.

N 2015-03-11 **/tcb/externalize example=⟨*name*⟩** (style, no default)

The text content of a dispExample* → P. 482 is externalized with the given ⟨*name*⟩. Note that the listing part is not externalized.

```
\begin{dispExample*}{sidebyside,externalize example=example_example}
\tikz\path[shading=ball,
  ball color=red] circle (7mm);
\end{dispExample*}
```

```
\tikz\path[shading=ball,
  ball color=red] circle (7mm);
```

N 2015-03-11 **/tcb/externalize example!=⟨*name*⟩** (style, no default)

Combination of /tcb/externalize example and /tcb/external/force remake → P. 463.

24.3 Customization

N 2015-03-11 **/tcb/external/safety=⟨*length*⟩** (no default, initially `2mm`)

The snippet box is surrounded with a safety border with a thickness of ⟨*length*⟩. This border is automatically trimmed during picture inclusion. The reason for this mechanism is to catch box content which extrudes over the bounding box. For example, shadows of a `tcolorbox` are painted outside the bounding box and would be lost otherwise.

N 2015-03-11 **/tcb/external/environment=⟨*env*⟩** (no default, initially unset)

Surrounds the exported snippet text with an environment ⟨*env*⟩ without parameters. Note that this option is ignored for `/tcb/externalize listing`→ P. 468.

N 2015-05-05 **/tcb/external/environment with percent=true|false** (default `true`, initially `true`)

If set to `true`, the `\begin` and `\end` code of `/tcb/external/environment` is appended with a percent sign. For verbatim environments, this option typically has to be se to `false`.

N 2015-03-11 **/tcb/external/minipage=⟨*length*⟩** (default `\linewidth`, initially unset)

Surrounds the exported snippet text with a minipage. The optional ⟨*length*⟩ parameter sets the width of the minipage. Note that the default width is the current line width of the main document. See `tcbexternal`→ P. 464 for examples. Note that this option is ignored for `/tcb/externalize listing`→ P. 468.

N 2015-03-11 **/tcb/external/plain** (no value, initially set)

Removes any text which was set to surround the snippet. This removes the setting of `/tcb/external/minipage`, but is independent of `/tcb/external/safety`.

N 2015-03-11 **/tcb/external/compiler=⟨*text*⟩** (no default, initially `pdflatex`)

Sets the name of the compiler for the snippets. Note that this compiler has to support the `\pdfmdfivesum` primitive e.g. using the `pdftexcmds` package. This should work for `xelatex` and `lualatex`.

N 2015-03-11 **/tcb/external/runs=⟨*number*⟩** (no default, initially `1`)

Sets the number of compiler runs for the snippet.

```
\begin{tcbexternal}[minipage,runs=2]{example_raster}
  \begin{tcbitemize}[raster equal height,
      size=small,colframe=red!50!black,colback=red!10!white]
    \tcbitem One
    \tcbitem \Huge Two
    \tcbitem Three
    \tcbitem Four
  \end{tcbitemize}
\end{tcbexternal}
```



N 2015-03-11 **/tcb/external/input source on error=true|false** (default `true`, initially `true`)

If set to `true`, the source code of the snippet is loaded instead of the failed pdf picture. Typically, this will lead to an error stop at the faulty place of the source and such helps detecting the cause. If the source input compiles without error, the document setup may be incorrect, see Section 24.1 on page 463. Maybe, the `external/` subdirectory has to be created manually in this case, see `/tcb/external/prefix`→ P. 463.

If the option is set to `false`, the compilation stops immediately on an error. The log file of the external snippet has to be consulted for error messages in this case.

N 2015-05-05 **/tcb/external/preclass=⟨*code*⟩** (no default, initially unset)

The given ⟨*code*⟩ is added before the snippet document. Typically, this means before `\documentclass`. This is not used for compilation of the main document.

N 2015-05-05 **/tcb/external/PassOptionsToPackage={⟨*options*⟩}{⟨*package*⟩}** (no default, initially unset)

The given ⟨*options*⟩ are passed to the given ⟨*package*⟩ for the snippet document. This is a shortcut for using `/tcb/external/preclass` with `\PassOptionsToPackage`. This not used for compilation of the main document.

N 2015-05-05 **/tcb/external/PassOptionsToClass={⟨*options*⟩}{⟨*class*⟩}** (no default, initially unset)

The given ⟨*options*⟩ are passed to the given ⟨*class*⟩ for the snippet document. This is a shortcut for using `/tcb/external/preclass` with `\PassOptionsToClass`. This not used for compilation of the main document.

N 2015-05-05 **/tcb/external/clear preclass** (no value)

Removes all additional `/tcb/external/preclass` settings.

N 2015-03-11 **/tcb/external/preamble=⟨*code*⟩** (no default, initially unset)

The given ⟨*code*⟩ is added to the preamble of the snippet document. This is not used for compilation of the main document.

N 2015-05-05 **/tcb/external/preamble tcbset=⟨*options*⟩** (no default, initially unset)

The given ⟨*options*⟩ are added as parameter for `\tcbset` → P. 13 to the preamble of the snippet document. This are not used for compilation of the main document.

N 2015-03-16 **/tcb/external/clear preamble** (no value)

Removes all additional `/tcb/external/preamble` settings.

N 2015-03-11 **\tcbifexternal{⟨*true*⟩}{⟨*false*⟩}**

Expands to ⟨*true*⟩, if executed during snippet compilation, and to ⟨*false*⟩, if executed during main document compilation. This can be used *before* `\tcbEXTERNALIZE` → P. 463 to give different setting to snippet and main document.

```
\tcbifexternal{
  \usepackage{onlyforexternal}
}{
  \usepackage{onlyformain}
}
```

N 2015-03-11 **\newtcbexternalizeenvironment**{⟨*newenv*⟩}{⟨*env*⟩}{⟨*options*⟩}{⟨*begin*⟩}{⟨*end*⟩}

Creates a new environment ⟨*newenv*⟩ which is based on tcbexternal→ P. 464. This enviroment takes *at least* one optional parameter and one mandatory parameter. These two parameters are passed to tcbexternal→ P. 464. Further, the given ⟨*options*⟩ are always added to the option list of tcbexternal→ P. 464.
The environment content is externalized and the external snippet is surrounded by an environment ⟨*env*⟩. All further parameters of ⟨*newenv*⟩ are given to ⟨*env*⟩ as parameters. The included image is prepended by ⟨*begin*⟩ and appended by ⟨*end*⟩.
extikzpicture→ P. 467 is an example application for \newtcbexternalizeenvironment.

```
\newtcbexternalizeenvironment{extabular}{tabular}{}{\par\centering}{\par}

\begin{extabular}{example_tabular}{|l|p{6cm}|r|}\hline
A & B & C\\\hline
a & This table is externalized as snippet. Obviously,
  this only makes sense for highly complex tables.
& b\\\hline
\end{extabular}
```

A	B	C
a	This table is externalized as snippet. Obviously, this only makes sense for highly complex tables.	b

N 2015-03-11 **\renewtcbexternalizeenvironment**{⟨*newenv*⟩}{⟨*env*⟩}{⟨*options*⟩}{⟨*begin*⟩}{⟨*end*⟩}

Identical to \newtcbexternalizeenvironment, but the environment ⟨*newenv*⟩ is created by \renewenvironment instead of \newenvironment.

N 2015-03-11 **\newtcbexternalizetcolorbox**{⟨*newenv*⟩}{⟨*env*⟩}{⟨*options*⟩}{⟨*begin end options*⟩}

Creates a new environment ⟨*newenv*⟩ which is based on tcbexternal→ P. 464. This enviroment takes *at least* one optional parameter and one mandatory parameter. These two parameters are passed to tcbexternal→ P. 464. Further, the given ⟨*options*⟩ are always added to the option list of tcbexternal→ P. 464.
The environment content is externalized and the external snippet is surrounded by an environment ⟨*env*⟩. All further parameters of ⟨*newenv*⟩ are given to ⟨*env*⟩ as parameters. **In contrast to \newtcbexternalizeenvironment, the environment ⟨*env*⟩ is intended to be based on tcolorbox→ P. 12 or tcblisting→ P. 311.**
The ⟨*begin end options*⟩ are options for settings the space before and after the included image using /tcb/before→ P. 81, /tcb/before skip→ P. 83, /tcb/after→ P. 81, or /tcb/after skip→ P. 83.

> **!** Use the exact identical values for /tcb/before→ P. 81 and /tcb/after→ P. 81 inside ⟨*begin end options*⟩ as they where used for definition of ⟨*env*⟩! Otherwise, externalized and non-externalized version will have different spacings.

extcolorbox→ P. 466 is an example application for \newtcbexternalizetcolorbox.

Definition in the preamble:

```
\newtcblisting{myownlisting}[2][]{
  enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  colbacktitle=red!50!yellow,before skip=6pt,after skip=6pt,
  title={#2},#1}

\newtcbexternalizetcolorbox{exmyownlisting}{myownlisting}%
  {minipage,environment with percent=false}%
  {before skip=6pt,after skip=6pt}% same values as for mylisting
```

```
\begin{exmyownlisting}{example_mylisting}% <- name for the external file
  {My externalized example box}
This is my \LaTeX\ box.
\end{exmyownlisting}
```

My externalized example box

```
This is my \LaTeX\ box.
```

This is my LaTeX box.

N 2015-03-11 **\renewtcbexternalizetcolorbox**{⟨*newenv*⟩}{⟨*env*⟩}{⟨*options*⟩}{⟨*begin end options*⟩}

Identical to \newtcbexternalizetcolorbox → P. 471, but the environment ⟨*newenv*⟩ is created by \renewenvironment instead of \newenvironment.

N 2016-07-14 **\tcbiffileprocess**{⟨*condition*⟩}{⟨*source*⟩}{⟨*md5-file*⟩}{⟨*target*⟩}{⟨*true*⟩}{⟨*false*⟩}

This is a low-level macro which is internally used. The MD5 digest of a ⟨*source*⟩ file is compared with a stored MD5 digest from an auxiliary ⟨*md5-file*⟩. If they are not equal, the auxiliary ⟨*md5-file*⟩ is updated to store the current MD5 digest. Further,

- if ⟨*condition*⟩ equals 0, ⟨*true*⟩ is executed.
- if ⟨*condition*⟩ equals 1:
  If the current and stored MD5 digests were different, ⟨*true*⟩ is executed.
  Otherwise, if the ⟨*target*⟩ file is not existing, ⟨*true*⟩ is executed.
  Otherwise, if the ⟨*target*⟩ file is older than the ⟨*md5-file*⟩, ⟨*true*⟩ is executed.
  Otherwise, ⟨*false*⟩ is executed.
- if ⟨*condition*⟩ equals 2, ⟨*false*⟩ is executed.

The intended processing purpose of the ⟨*true*⟩ code is to produce a ⟨*target*⟩ file from the given ⟨*source*⟩ file.

24.4 Troubleshooting and FAQ

- **I use the default settings, but the `external` subdirectory is not created.**
  Depending on operating system and compiler, an `external` subdirectory is automatically created or not. If not, create such a directory manually or add the following to your document[5]:

  ```
  \ShellEscape{mkdir external}
  ```

  or

  ```
  \ShellEscape{mkdir -p external}
  ```

  If the combination of `/tcb/external/prefix` → P. 463 and chosen snippet name points to another subdirectory than `external`, this has to be adapted.

- **I use the `minted` package and I get a cache directory for every externalized snippet.**
  To avoid this problem, there are several ways.

  – If you do not need `minted` inside the snippet code, you may use `\usepackage{minted}` *after* `\tcbEXTERNALIZE` → P. 463 or use `\tcbifexternal` → P. 470 to switch `minted` off for the external code. If `minted` is already included by another package, add the following to your preamble:

  ```
  \tcbset{external/PassOptionsToPackage={draft}{minted}}
  ```

  – If `minted` is needed for the snippet code, caching can be switched off by adding the following to your preamble:

  ```
  \tcbset{external/PassOptionsToPackage={cache=false}{minted}}
  ```

  Alternatively, the `cachedir` option of `minted` may be used to redirect the cache.

[5] The `shellesc` package is loaded automatically by the library.

25 Library documentation

This library has the single purpose to support LaTeX package documentations like this one. Actually, the visual nature follows the approach from Till Tantau's `pgf` [22] documentation. Typically, this library is assumed to be used in conjunction with the class `ltxdoc` or alike. Denis Bitouzé, Muzimuzhi, and many others provided very valuable input for this library.

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{documentation}
```

This also loads the library skins, see Section 10 on page 152, the library raster, see Section 15 on page 288, the library listings, see Section 16 on page 310, the library xparse, see Section 23 on page 449, and a bunch of packages, namely `pifont`, `marvosym`, `makeidx`, `marginnote`, `refcount`, and `hyperref`.

> **!** The package `makeidx` is loaded only, if `\printindex` is *not* already defined. Therefore, one can include an alternative to `makeidx` like `imakeidx` *before* the library `documentation` is used.

> **!** The package `marginnote` is loaded only, if `\marginnote` is *not* already defined.

> **!** In contrast to other `tcolorbox` options, the option settings for documentation are typically not getting reset by `/tcb/reset` → P. 109, i.e. they keep their values for embedded boxes.

> **!** In combination with DocStrip, `/tcb/verbatim ignore percent` → P. 130 may be helpful.

For UTF-8 support load (ignore this when using XeLaTeX):

```
\tcbuselibrary{listingsutf8,documentation}
```

For `minted` [12] support, load:

```
\tcbuselibrary{documentation,minted}
\tcbset{listing engine=minted}
```

25.1 Macros of the Library

U 2020-04-22

`\begin{docCommand}[⟨options⟩]{⟨name⟩}{⟨parameters⟩}`
  ⟨*command description*⟩
`\end{docCommand}`

Documents a LaTeX macro with given ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. This macro takes mandatory or optional ⟨*parameters*⟩. It is automatically indexed and can be referenced with `\refCom` → P. 485`{⟨name⟩}`.

```
\begin{docCommand}{foomakedocSubKey}{\marg{name}\marg{key path}}
  Creates a new environment \meta{name} based on \refEnv{docKey} for the
  documentation of keys with the given \meta{key path}.
\end{docCommand}
```

\foomakedocSubKey{⟨*name*⟩}{⟨*key path*⟩}

Creates a new environment ⟨*name*⟩ based on docKey → P. 478 for the documentation of keys with the given ⟨*key path*⟩.

```
\begin{docCommand}[color definition=blue]{foomakedocSubKey*}%
    {\marg{name}\marg{key path}}
  Creates a new environment \meta{name} based on \refEnv{docKey} for the
  documentation of keys with the given \meta{key path}.
\end{docCommand}
```

\foomakedocSubKey*{⟨*name*⟩}{⟨*key path*⟩}

Creates a new environment ⟨*name*⟩ based on docKey → P. 478 for the documentation of keys with the given ⟨*key path*⟩.

U 2020-04-22

\begin{docCommand*}[⟨*options*⟩]{⟨*name*⟩}{⟨*parameters*⟩}
  ⟨*command description*⟩
\end{docCommand*}

Identical to docCommand → P. 474, but without index entry.

N 2020-04-22

\begin{docCommands}[⟨*options*⟩]{{⟨*variant1*⟩},{⟨*variant2*⟩},...}
  ⟨*command description*⟩
\end{docCommands}

Documents several (similar) LaTeX macro variants simultaneously. The given ⟨*options*⟩ are set with \tcbset → P. 13 and are valid for all variants and the documentation text. Every variant is described by an option set ⟨*variant1*⟩, ⟨*variant2*⟩, and so on. The most crucial options are /tcb/doc name → P. 488 and /tcb/doc parameter → P. 488.

```
\begin{docCommands}[
    doc no index,  %  no index entries for this example
    doc name      = newtheorem,
    doc parameter = \marg{envname},
  ]
  {
    {  },
    { doc parameter = \marg{envname}\oarg{numbered within} },
    { doc parameter = \oarg{numbered like}\marg{envname} },
    { doc name      = newtheorem* },
  }
  example
\end{docCommands}
```

\newtheorem{⟨*envname*⟩}
\newtheorem{⟨*envname*⟩}[⟨*numbered within*⟩]
\newtheorem[⟨*numbered like*⟩]{⟨*envname*⟩}
\newtheorem*{⟨*envname*⟩}

example

U 2020-04-22 `\begin{docEnvironment}[⟨options⟩]{⟨name⟩}{⟨parameters⟩}`
`⟨environment description⟩`
`\end{docEnvironment}`

Documents a LaTeX environment with given ⟨*name*⟩. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. This environment takes mandatory or optional ⟨*parameters*⟩. It is automatically indexed and can be referenced with `\refEnv` → P. 485`{`⟨*name*⟩`}`.

```
\begin{docEnvironment}{foocolorbox}{\oarg{options}}
  This is the main environment to create an accentuated colored text box with
  rounded corners and, optionally, two parts.
\end{docEnvironment}
```

`\begin{foocolorbox}[⟨options⟩]`
`⟨environment description⟩`
`\end{foocolorbox}`

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts.

```
\begin{docEnvironment}%
    [doclang/environment content=My content text]%
    {foocolorbox*}{\oarg{options}}
  This is the main environment to create an accentuated colored text box with
  rounded corners and, optionally, two parts.
\end{docEnvironment}
```

`\begin{foocolorbox*}[⟨options⟩]`
`⟨My content text⟩`
`\end{foocolorbox*}`

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts.

U 2020-04-22 `\begin{docEnvironment*}[⟨options⟩]{⟨name⟩}{⟨parameters⟩}`
`⟨environment description⟩`
`\end{docEnvironment*}`

Identical to `docEnvironment`, but without index entry.

N 2020-04-22

```
\begin{docEnvironments}[⟨options⟩]{{⟨variant1⟩},{⟨variant2⟩},...}
  ⟨environment description⟩
\end{docEnvironments}
```

Documents several (similar) LaTeX environment variants simultaneously. The given ⟨*options*⟩ are set with `\tcbset` → P. 13 and are valid for all variants and the documentation text. Every variant is described by an option set ⟨*variant1*⟩, ⟨*variant2*⟩, and so on. The most crucial options are `/tcb/doc name` → P. 488 and `/tcb/doc parameter` → P. 488.

```
\begin{docEnvironments}[
    doc no index,   % no index entries for this example
    doc parameter = \oarg{options}\marg{title},
    doclang/environment content = box content,
  ]
  {
    {
      doc name        = redbox,
      doc description = a red colored box,
    },
    {
      doc name        = greenbox,
      doc description = a green colored box,
    },
    {
      doc name        = bluebox,
      doc description = a blue colored box,
    },
    {
      doc name        = custombox,
      doc parameter   = \oarg{options}\marg{color}\marg{title},
      doc description = a colored box,
    },
  }
  example
\end{docEnvironments}
```

```
\begin{redbox}[⟨options⟩]{⟨title⟩}                          (a red colored box)
  ⟨box content⟩
\end{redbox}
\begin{greenbox}[⟨options⟩]{⟨title⟩}                        (a green colored box)
  ⟨box content⟩
\end{greenbox}
\begin{bluebox}[⟨options⟩]{⟨title⟩}                         (a blue colored box)
  ⟨box content⟩
\end{bluebox}
\begin{custombox}[⟨options⟩]{⟨color⟩}{⟨title⟩}              (a colored box)
  ⟨box content⟩
\end{custombox}
```

example

U 2020-04-22 `\begin{docKey}[⟨key path⟩][⟨options⟩]{⟨name⟩}{⟨parameters⟩}{⟨description⟩}`
`⟨key description⟩`
`\end{docKey}`

Documents a key with given ⟨*name*⟩ and an optional ⟨*key path*⟩. The given ⟨*options*⟩ are set with `\tcbset`→P. 13. This key takes mandatory or optional ⟨*parameters*⟩ as value with a short ⟨*description*⟩. It is automatically indexed and can be referenced with `\refKey`→P. 485`{⟨name⟩}`.

```
\begin{docKey}[foo]{footitle}{=\meta{text}}{no default, initially empty}
  Creates a heading line with \meta{text} as content.
\end{docKey}
```

`/foo/footitle=`⟨*text*⟩ (no default, initially empty)

Creates a heading line with ⟨*text*⟩ as content.

U 2020-04-22 `\begin{docKey*}[⟨key path⟩][⟨options⟩]{⟨name⟩}{⟨parameters⟩}{⟨description⟩}`
`⟨key description⟩`
`\end{docKey*}`

Identical to `docKey`, but without index entry.

N 2020-04-22 `\begin{docKeys}[⟨options⟩]{{⟨variant1⟩},{⟨variant2⟩},...}`
`⟨key description⟩`
`\end{docKeys}`

Documents several (similar) key variants simultaneously. The given ⟨*options*⟩ are set with `\tcbset`→P. 13 and are valid for all variants and the documentation text. Every variant is described by an option set ⟨*variant1*⟩, ⟨*variant2*⟩, and so on. The most crucial options are `/tcb/doc keypath`→P. 488, `/tcb/doc name`→P. 488, `/tcb/doc parameter`→P. 488, and `/tcb/doc description`→P. 489.

```
\begin{docKeys}[
    doc no index,   % no index entries for this example
    doc keypath   = mykeyroot,
    doc parameter = {=\meta{length}},
  ]
  {
    {
      doc name        = width,
      doc description = initially \texttt{10cm},
    },
    {
      doc name        = height,
      doc description = initially \texttt{7cm},
    },
  }
  example
\end{docKeys}
```

`/mykeyroot/width=`⟨*length*⟩ (initially `10cm`)
`/mykeyroot/height=`⟨*length*⟩ (initially `7cm`)

example

N 2019-09-18
U 2020-04-22

```
\begin{docPathOperation}[⟨options⟩]{⟨name⟩}{⟨parameters⟩}
  ⟨operation description⟩
\end{docPathOperation}
```

Documents a TikZ path operation with given ⟨*name*⟩. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. This TikZ path operation takes mandatory or optional ⟨*parameters*⟩. It is automatically indexed and can be referenced with `\refPathOperation` → P. 486`{`⟨*name*⟩`}`.

```
\begin{docPathOperation}{fooop}{\oarg{opt}(\meta{name})\colOpt{at(\meta{coord})}}
  Imaginary path operation for illustration.
\end{docPathOperation}
```

```
\path ... fooop[⟨opt⟩](⟨name⟩)at(⟨coord⟩) ...;
```

Imaginary path operation for illustration.

N 2019-09-18
U 2020-04-22

```
\begin{docPathOperation*}[⟨options⟩]{⟨name⟩}{⟨parameters⟩}
  ⟨command description⟩
\end{docPathOperation*}
```

Identical to `docPathOperation`, but without index entry.

N 2020-04-22

```
\begin{docPathOperations}[⟨options⟩]{{⟨variant1⟩},{⟨variant2⟩},...}
  ⟨command description⟩
\end{docPathOperations}
```

Documents several (similar) TikZ path operation variants simultaneously. The given ⟨*options*⟩ are set with `\tcbset` → P. 13 and are valid for all variants and the documentation text. Every variant is described by an option set ⟨*variant1*⟩, ⟨*variant2*⟩, and so on. The most crucial options are `/tcb/doc name` → P. 488 and `/tcb/doc parameter` → P. 488.

```
\begin{docPathOperations}[
    doc no index,   %  no index entries for this example
  ]
  {
    {
      doc name      = rectangle,
      doc parameter = \meta{corner or cycle},
    },
    {
      doc name      = circle,
      doc parameter = \oarg{options},
    },
    {
      doc name      = ellipse,
      doc parameter = \oarg{options},
    },
  }
  example
\end{docPathOperations}
```

```
\path ... rectangle⟨corner or cycle⟩ ...;
\path ... circle[⟨options⟩] ...;
\path ... ellipse[⟨options⟩] ...;
```

example

U 2020-04-23 `\docValue[⟨options⟩]{⟨name⟩}`
`\docValue*[⟨options⟩]{⟨name⟩}`

Documents a value with given ⟨*name*⟩. Typically, this is a value for a key. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. This value is automatically indexed for `\docValue` and has no index entry for `\docValue*`.

```
A feasible value for \refKey{/foo/footitle} is \docValue*{foovalue}.
```

A feasible value for `/foo/footitle` → P. 478 is `foovalue`.

U 2020-04-23 `\docAuxCommand[⟨options⟩]{⟨name⟩}`
`\docAuxCommand*[⟨options⟩]{⟨name⟩}`

Documents an auxiliary or minor LaTeX macro with given ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. This macro is automatically indexed for `\docAuxCommand` and has no index entry for `\docAuxCommand*`.

```
The macro \docAuxCommand{fooaux} holds some interesting data.
```

The macro `\fooaux` holds some interesting data.

U 2020-04-23 `\docAuxEnvironment[⟨options⟩]{⟨name⟩}`
`\docAuxEnvironment*[⟨options⟩]{⟨name⟩}`

Documents an auxiliary or minor LaTeX environment with given ⟨*name*⟩. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. This macro is automatically indexed indexed for `\docAuxEnvironment` and has no index entry for `\docAuxEnvironment*`.

```
The environment \docAuxEnvironment{fooauxenv} holds some interesting data.
```

The environment `fooauxenv` holds some interesting data.

U 2020-04-23 `\docAuxKey[⟨key path⟩][⟨options⟩]{⟨name⟩}`
`\docAuxKey*[⟨key path⟩][⟨options⟩]{⟨name⟩}`

Documents an auxiliary key with given ⟨*name*⟩ and an optional ⟨*key path*⟩. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. It is automatically indexed for `\docAuxKey` and has no index entry for `\docAuxKey*`.

```
The key \docAuxKey[foo]{fooaux} holds some interesting data.
```

The key `/foo/fooaux` holds some interesting data.

U 2020-04-23 `\docCounter[⟨options⟩]{⟨name⟩}`
`\docCounter*[⟨options⟩]{⟨name⟩}`

Documents a counter with given ⟨*name*⟩. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. The counter is automatically indexed for `\docCounter` and has no index entry for `\docCounter*`.

```
The counter \docCounter{foocounter} can be used for computation.
```

The counter `foocounter` can be used for computation.

U 2020-04-23 `\docLength[⟨options⟩]{⟨name⟩}`
`\docLength*[⟨options⟩]{⟨name⟩}`

Documents a length with given ⟨*name*⟩. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. The length is automatically indexed for `\docLength` and has no index entry for `\docLength*`.

```
The length \docLength{foolength} can be used for computation.
```

The length `\foolength` can be used for computation.

U 2020-04-23 `\docColor[⟨options⟩]{⟨name⟩}`
`\docColor*[⟨options⟩]{⟨name⟩}`

Documents a color with given ⟨*name*⟩. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. The color is automatically indexed for `\docColor` and has no index entry for `\docColor*`.

```
The color \docColor{foocolor} is available.
```

The color `foocolor` is available.

`\cs{⟨name⟩}`

Macro from `ltxdoc` [3] to typeset a command word ⟨*name*⟩ where the backslash is prefixed. The library overwrites the original macro.

```
This is a \cs{foocommand}.
```

This is a `\foocommand`.

`\meta{⟨text⟩}`

Macro from `doc` [8] to typeset a meta ⟨*text*⟩. The library overwrites the original macro.

```
This is a \meta{text}.
```

This is a ⟨*text*⟩.

`\marg{⟨text⟩}`

Macro from `ltxdoc` [3] to typeset a ⟨*text*⟩ with curly brackets as a mandatory argument. The library overwrites the original macro.

```
This is a mandatory \marg{argument}.
```

This is a mandatory `{`⟨*argument*⟩`}`.

`\oarg{⟨text⟩}`

Macro from `ltxdoc` [3] to typeset a ⟨*text*⟩ with square brackets as an optional argument. The library overwrites the original macro.

```
This is an optional \oarg{argument}.
```

This is an optional `[`⟨*argument*⟩`]`.

`\brackets{⟨text⟩}`

Sets the given ⟨*text*⟩ with curly brackets.

```
Here we use \brackets{some text}.
```

Here we use {some text}.

U 2014-10-10

```
\begin{dispExample}
  ⟨environment content⟩
\end{dispExample}
```

Creates a colored box based on a `tcolorbox`→ P. 12. It displays the environment content as source code in the upper part and as compiled text in the lower part of the box. The appearance is controlled by `/tcb/documentation listing style`→ P. 496 and the style `/tcb/docexample`→ P. 496. It may be changed by redefining this style.

```
\begin{dispExample}
This is a \LaTeX\ example.
\end{dispExample}
```

```
This is a \LaTeX\ example.
```

This is a LaTeX example.

U 2014-10-10

```
\begin{dispExample*}{⟨options⟩}
  ⟨environment content⟩
\end{dispExample*}
```

The starred version of `dispExample` takes `tcolorbox`→ P. 12 ⟨*options*⟩ as parameter. These ⟨*options*⟩ are executed after `/tcb/docexample`→ P. 496.

```
\begin{dispExample*}{sidebyside}
This is a \LaTeX\ example.
\end{dispExample*}
```

```
This is a \LaTeX\ example.
```

This is a LaTeX example.

```
\begin{dispListing}
  ⟨environment content⟩
\end{dispListing}
```

Creates a colored box based on a `tcolorbox` → P. 12. It displays the environment content as source code. The appearance is controlled by `/tcb/documentation listing style` → P. 496 and the style `/tcb/docexample` → P. 496. It may be changed by redefining this style.

```
\begin{dispListing}
This is a \LaTeX\ example.
\end{dispListing}
```

```
This is a \LaTeX\ example.
```

```
\begin{dispListing*}{⟨options⟩}
  ⟨environment content⟩
\end{dispListing*}
```

The starred version of `dispListing` takes `tcolorbox` → P. 12 ⟨*options*⟩ as parameter. These ⟨*options*⟩ are executed after `/tcb/docexample` → P. 496.

```
\begin{dispListing*}{title=My listing}
This is a \LaTeX\ example.
\end{dispListing*}
```

My listing

```
This is a \LaTeX\ example.
```

```
\begin{absquote}
  ⟨environment content⟩
\end{absquote}
```

Used to typeset an abstract as quoted and small text.

```
\begin{absquote}
|tcolorbox| provides an environment for colored and framed text boxes with a
heading line. Optionally, such a box can be split in an upper and a lower part.
\end{absquote}
```

> `tcolorbox` provides an environment for colored and framed text boxes with a heading line. Optionally, such a box can be split in an upper and a lower part.

U 2020-04-22 **\tcbmakedocSubKey{⟨name⟩}{⟨key path⟩}**

Creates a new environment ⟨*name*⟩ based on docKey → P. 478 for the documentation of keys with the given ⟨*key path*⟩ as root. The new environment ⟨*name*⟩ takes the same parameters as docKey → P. 478 itself. A second starred environment ⟨*name*⟩ is also created, which is identical to ⟨*name*⟩ but without index entry.

```
\tcbmakedocSubKey{docFooKey}{foo}

\begin{docFooKey}{foodummy}{=\meta{nothing}}{no default, initially empty}
Some key.
\end{docFooKey}

\begin{docFooKey*}{foo another dummy}{=\meta{nothing}}{no default, initially empty}
Some key (not indexed).
\end{docFooKey*}
```

/foo/foodummy=⟨*nothing*⟩ (no default, initially empty)

Some key.

/foo/foo another dummy=⟨*nothing*⟩ (no default, initially empty)

Some key (not indexed).

N 2020-04-22 **\tcbmakedocSubKeys{⟨name⟩}{⟨key path⟩}**

Creates a new environment ⟨*name*⟩ based on docKeys → P. 478 for the documentation of keys with the given ⟨*key path*⟩ as root. The new environment ⟨*name*⟩ takes the same parameters as docKeys → P. 478 itself.

```
\tcbmakedocSubKeys{docFooKeys}{foo}

\begin{docFooKeys}[
    doc parameter   = {=\meta{nothing}},
    doc description = {no default, initially empty},
  ]
  {
    {
      doc name = foodummy 2,
    },
    {
      doc name = foo another dummy 2,
      doc no index,
    }
  }
Some description.
\end{docFooKeys}
```

/foo/foodummy 2=⟨*nothing*⟩ (no default, initially empty)
/foo/foo another dummy 2=⟨*nothing*⟩ (no default, initially empty)

Some description.

\refCom{⟨name⟩}

References a documented LaTeX macro with given ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. The page reference is suppressed if it links to the same page.

```
We have created \refCom{foomakedocSubKey} as an example.
```

We have created `\foomakedocSubKey` → P. 475 as an example.

\refCom*{⟨name⟩}

References a documented LaTeX macro with given ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. There is no page reference.

```
We have created \refCom*{foomakedocSubKey} as an example.
```

We have created `\foomakedocSubKey` as an example.

\refEnv{⟨name⟩}

References a documented LaTeX environment with given ⟨*name*⟩. The page reference is suppressed if it links to the same page.

```
We have created \refEnv{foocolorbox} as an example.
```

We have created `foocolorbox` → P. 476 as an example.

\refEnv*{⟨name⟩}

References a documented LaTeX environment with given ⟨*name*⟩. There is no page reference.

```
We have created \refEnv*{foocolorbox} as an example.
```

We have created `foocolorbox` as an example.

\refKey{⟨name⟩}

References a documented key with given ⟨*name*⟩ where ⟨*name*⟩ is the full path name of the key. The page reference is suppressed if it links to the same page.

```
We have created \refKey{/foo/footitle} as an example.
```

We have created `/foo/footitle` → P. 478 as an example.

\refKey*{⟨name⟩}

References a documented key with given ⟨*name*⟩ where ⟨*name*⟩ is the full path name of the key. There is no page reference.

```
We have created \refKey*{/foo/footitle} as an example.
```

We have created `/foo/footitle` as an example.

N 2019-09-17 **\refPathOperation**{⟨*name*⟩}

References a documented TikZ path operation with given ⟨*name*⟩. The page reference is suppressed if it links to the same page.

```
We have created \refPathOperation{fooop} as an example.
```

We have created fooop → P. 479 as an example.

N 2019-09-17 **\refPathOperation***{⟨*name*⟩}

References a documented TikZ path operation with given ⟨*name*⟩. There is no page reference.

```
We have created \refPathOperation*{fooop} as an example.
```

We have created fooop as an example.

U 2020-02-11 **\refAux**{⟨*name*⟩}

References some auxiliary environment, key, value, or color. The ⟨*name*⟩ is colored according to /tcb/color hyperlink → P. 498, if hyperref colorlinks are set, but there is no real link.

```
Some pages back, one can see \refAux{/foo/footitle} as an example.
```

Some pages back, one can see /foo/footitle as an example.

U 2020-02-11 **\refAuxcs**{⟨*name*⟩}

References some auxiliary macro ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. The ⟨*name*⟩ is colored according to /tcb/color hyperlink → P. 498, if hyperref colorlinks are set, but there is no real link.

```
Some pages back, one can see \refAuxcs{fooaux} as an example.
```

Some pages back, one can see \fooaux as an example.

\colDef{⟨*text*⟩}

Sets ⟨*text*⟩ with the command color, see /tcb/color command → P. 498.

```
This is my \colDef{text}.
```

This is my text.

\colOpt{⟨*text*⟩}

Sets ⟨*text*⟩ with the option color, see /tcb/color option → P. 498.

```
This is my \colOpt{text}.
```

This is my text.

N 2019-09-18 **\colFade{⟨*text*⟩}**

Sets ⟨*text*⟩ with the fade color, see /tcb/color fade → P. 498.

```
This is my \colFade{text}.
```

This is my text.

N 2014-09-19 **\tcbdocmarginnote[⟨*options*⟩]{⟨*text*⟩}**

Creates a tcolorbox note with the given ⟨*text*⟩ inside the margin using the marginnote package. The style of the tcolorbox is predefined and can be altered by /tcb/doc marginnote → P. 490 and the given ⟨*options*⟩.

```
Some text\tcbdocmarginnote{Note A}
which is commented by a note inside the margin.
Alternatively to |\tcbdocmarginnote|, you can always use
|\marginnote| with a |tcolorbox| directly.\par
This is further text%
\tcbdocmarginnote[colframe=blue!50!white,colback=blue!5!white]{Note B}
with another note.
```

Note A

Note B

Some text which is commented by a note inside the margin. Alternatively to \tcbdocmarginnote, you can always use \marginnote with a tcolorbox directly.
This is further text with another note.

N 2014-09-19 **\tcbdocnew{⟨*date*⟩}**

Auxiliary macro which typesets the /tcb/doclang/new → P. 499 text with the given ⟨*date*⟩. It may be redefined for customization.

New: 1978-02-09

```
\tcbdocnew{1981-10-29}.
% Next one is displayed in the margin:
\tcbdocmarginnote{\tcbdocnew{1978-02-09}}
```

New: 1981-10-29.

N 2014-09-19 **\tcbdocupdated{⟨*date*⟩}**

Auxiliary macro which typesets the /tcb/doclang/updated → P. 499 text with the given ⟨*date*⟩. It may be redefined for customization.

```
\tcbdocupdated{2014-09-19}.
```

Updated: 2014-09-19.

25.2 Entry Content Option Keys

N 2020-04-22 **/tcb/doc name=⟨*name*⟩** (no default, initially empty)

Sets the ⟨*name*⟩ of the entry to document, i.e. the ⟨*name*⟩ of the command, environment, key, etc. For docCommand^{→ P. 474}, docEnvironment^{→ P. 476}, etc. the ⟨*name*⟩ is set by a mandatory parameter, but can also be set by /tcb/doc name. /tcb/doc name also sets ⟨*name*⟩ to /tcb/doc label^{→ P. 489}, /tcb/doc index^{→ P. 489}, and /tcb/doc sort index^{→ P. 489}.

```
\begin{docCommands}[
    doc no index,  %  no index entries for this example
    doc name      = bfseries,
  ] {}
  Font setting to bold face.
\end{docCommands}
```

\bfseries

Font setting to bold face.

N 2020-04-22 **/tcb/doc parameter=⟨*parameters*⟩** (no default, initially empty)

Sets the ⟨*parameters*⟩ of the entry to document, i.e. the ⟨*parameters*⟩ of the command, environment, key, etc. For docCommand^{→ P. 474}, docEnvironment^{→ P. 476}, etc. the ⟨*parameters*⟩ is set by a mandatory option, but can also be set by /tcb/doc parameter.

```
\begin{docCommands}[
    doc no index,  %  no index entries for this example
    doc name      = textbf,
    doc parameter = \marg{text},
  ] {}
  Sets \meta{text} in bold face.
\end{docCommands}
```

\textbf{⟨*text*⟩}

Sets ⟨*text*⟩ in bold face.

N 2020-04-22 **/tcb/doc keypath=⟨*key path*⟩** (no default, initially empty)

Sets the ⟨*key path*⟩ of the key to document. For docKey^{→ P. 478} and docKey*^{→ P. 478} the ⟨*key path*⟩ is set by a specialized option, but can also be set by /tcb/doc keypath.

```
\begin{docKeys}[
    doc no index,  %  no index entries for this example
    doc keypath     = tikz,
    doc name        = fill,
    doc parameter   = \colOpt{=\meta{color}},
    doc description = default is scope's color setting,
  ] {}
  This option causes the path to be filled.
\end{docKeys}
```

/tikz/fill=⟨*color*⟩ (default is scope's color setting)

This option causes the path to be filled.

/tcb/doc description=⟨*description*⟩ (no default, initially empty)

Sets a (short!) additional ⟨*description*⟩ for docCommand→ P. 474, docEnvironment→ P. 476, or docPathOperation→ P. 479. Such a description is mandatory for docKey→ P. 478.

```
\begin{docCommand*}[doc description=my description]{myCommandF}{\marg{argument}}
  This is the documentation of \refCom{myCommandF} which takes one \meta{argument}.
  \refCom{myCommandF} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandF{⟨*argument*⟩} (my description)

This is the documentation of \myCommandF which takes one ⟨*argument*⟩. \myCommandF does some funny things with its ⟨*argument*⟩.

> **!** Note that the description ⟨*text*⟩ may overlap with the text on the left hand side if too long. Linebreaks can be used inside the ⟨*text*⟩.

N 2019-09-18 **/tcb/doc label=**⟨*text*⟩ (no default, initially unset)

If used inside the option list of docCommand→ P. 474, docEnvironment→ P. 476, docKey→ P. 478, etc, then ⟨*text*⟩ is used for labeling instead of the name of the definition.

```
\begin{docPathOperation*}[doc label=pathline]{-{}-}{\meta{coordinate or cycle}}
  This is the documentation of \refPathOperation{pathline}.
\end{docPathOperation*}
```

\path ... --⟨*coordinate or cycle*⟩ ...;

This is the documentation of --.

N 2020-01-07 **/tcb/doc index=**⟨*text*⟩ (no default, initially unset)

If used inside the option list of docCommand→ P. 474, docEnvironment→ P. 476, docKey→ P. 478, etc, then ⟨*text*⟩ is used for the index instead of the name of the definition.

```
\begin{docPathOperation}[doc index=foo path (horizontal then vertical),
    doc label=pathline2]{-\textbar}{\meta{coordinate or cycle}}
  This is the documentation of \refPathOperation{pathline2}.
\end{docPathOperation}
```

\path ... -|⟨*coordinate or cycle*⟩ ...;

This is the documentation of -|.

N 2020-04-23 **/tcb/doc sort index=**⟨*text*⟩ (no default, initially unset)

If used inside the option list of docCommand→ P. 474, docEnvironment→ P. 476, docKey→ P. 478, etc, then ⟨*text*⟩ is used for as sort key for the index instead of the name of the definition.

```
\begin{docCommands}[
    doc name        = l_tcobox_example_tl,
    doc sort index  = example_tl,  % sorted unter e like example
  ]{}
\end{docCommands}
```

/tcb/doc into index=true|false (default `true`, initially `true`)

If set to `false`, no index entries are written for the main documentation environments. The same effect is achieved by using e. g. `docCommand*` → P. 475 instead of `docCommand` → P. 474.

N 2020-04-22 **/tcb/doc no index** (style, initially unset)

If set, no index entries are written for the main documentation environments. This is a shortcut for using `/tcb/doc into index=false`.

N 2014-09-19 **/tcb/doc marginnote=⟨*options*⟩** (no default, initially empty)

Sets style ⟨*options*⟩ for the displayed box of the `\tcbdocmarginnote` → P. 487 command.

```
\tcbset{doc marginnote={colframe=blue!50!white,colback=blue!5!white}}%
This is some text\tcbdocmarginnote{Note A}
which is commented by a note inside the margin.
```

Note A

This is some text which is commented by a note inside the margin.

N 2014-09-19 **/tcb/doc new=⟨*date*⟩** (style, no default)

Adds a a marginnote with a "New: ⟨*date*⟩" message at the beginning of the upper box part. The intended use is inside the option list of `docCommand` → P. 474, `docEnvironment` → P. 476, etc.

```
\begin{docCommand}[doc new=2000-01-01]{foosomething}{\marg{text}}
Some command for something.
\end{docCommand}
```

New: 2000-01-01

\foosomething{⟨*text*⟩}

Some command for something.

N 2014-09-19 **/tcb/doc updated=⟨*date*⟩** (style, no default)

Adds a marginnote with a "Updated: ⟨*date*⟩" message at the beginning of the upper box part. See `/tcb/doc new`.

N 2014-09-19 **/tcb/doc new and updated={⟨*new date*⟩}{⟨*update date*⟩}** (style, no default)

Adds a marginnote with "New: ⟨*new date*⟩" and "Updated: ⟨*update date*⟩" messages at the beginning of the upper box part. See `/tcb/doc new`.

25.3 Entry Customization Option Keys

/tcb/doc left=⟨*length*⟩ (no default, initially 2em)

Sets the left hand offset of the documentation texts from docCommand → P. 474, docEnvironment → P. 476, docKey → P. 478, etc, to ⟨*length*⟩.

```
\begin{docCommand*}[doc left=2cm,doc left indent=-2cm]{myCommandA}{\marg{argument}}
  This is the documentation of \refCom{myCommandA} which takes one \meta{argument}.
  \refCom{myCommandA} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandA{⟨*argument*⟩}

This is the documentation of \myCommandA which takes one ⟨*argument*⟩. \myCommandA does some funny things with its ⟨*argument*⟩.

/tcb/doc right=⟨*length*⟩ (no default, initially 0em)

Sets the right hand offset of the documentation texts from docCommand → P. 474, docEnvironment → P. 476, docKey → P. 478, etc, to ⟨*length*⟩.

```
\begin{docCommand*}[doc right=2cm]{myCommandB}{\marg{argument}}
  This is the documentation of \refCom{myCommandB} which takes one \meta{argument}.
  \refCom{myCommandB} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandB{⟨*argument*⟩}

This is the documentation of \myCommandB which takes one ⟨*argument*⟩. \myCommandB does some funny things with its ⟨*argument*⟩.

/tcb/doc left indent=⟨*length*⟩ (no default, initially -2em)

Sets the left hand indent of documentation heads from docCommand → P. 474, docEnvironment → P. 476, docKey → P. 478, etc, to ⟨*length*⟩.

```
\begin{docCommand*}[doc left indent=2cm]{myCommandC}{\marg{argument}}
  This is the documentation of \refCom{myCommandC} which takes one \meta{argument}.
  \refCom{myCommandC} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandC{⟨*argument*⟩}

This is the documentation of \myCommandC which takes one ⟨*argument*⟩. \myCommandC does some funny things with its ⟨*argument*⟩.

/tcb/doc right indent=⟨*length*⟩ (no default, initially 0pt)

Sets the right hand indent of documentation heads from docCommand → P. 474, docEnvironment → P. 476, docKey → P. 478, etc, to ⟨*length*⟩.

```
\begin{docCommand*}[doc right indent=-10mm,doc right=10mm,
    doc description=test value]{myCommandD}{\marg{argument}}
  This is the documentation of \refCom{myCommandD} which takes one \meta{argument}.
  \refCom{myCommandD} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandD{⟨*argument*⟩} (test value)

This is the documentation of \myCommandD which takes one ⟨*argument*⟩. \myCommandD does some funny things with its ⟨*argument*⟩.

The head lines of the main documentation environments docCommand[→ P. 474], docEnvironment[→ P. 476], docKey[→ P. 478], etc, are tcolorboxes inside a tcbraster[→ P. 290]. Options to the surrounding tcbrasters and the embedded tcolorboxes can be given using the following keys.

N 2020-04-24 **/tcb/doc raster command=⟨*options*⟩** (no default, initially empty)

Sets ⟨*options*⟩ for the surrounding tcbraster[→ P. 290] of docCommand[→ P. 474], docCommand*[→ P. 475], and docCommands[→ P. 475].

```
\tcbset{doc raster command={raster before skip=7mm,raster after skip=0mm}}

The is an example text.

\begin{docCommand*}{myCommandI}{\marg{argument}}
  This is the documentation of \refCom{myCommandI} which takes one \meta{argument}.
  \refCom{myCommandI} does some funny things with its \meta{argument}.
\end{docCommand*}
```

The is an example text.

\myCommandI{⟨*argument*⟩}

This is the documentation of \myCommandI which takes one ⟨*argument*⟩. \myCommandI does some funny things with its ⟨*argument*⟩.

N 2020-04-24 **/tcb/doc raster environment=⟨*options*⟩** (no default, initially empty)

Sets ⟨*options*⟩ for the surrounding tcbraster[→ P. 290] of docEnvironment[→ P. 476], docEnvironment*[→ P. 476], and docEnvironments[→ P. 477].

N 2020-04-24 **/tcb/doc raster key=⟨*options*⟩** (no default, initially empty)

Sets ⟨*options*⟩ for the surrounding tcbraster[→ P. 290] of docKey[→ P. 478], docKey*[→ P. 478], and docKeys[→ P. 478].

N 2020-04-24 **/tcb/doc raster path=⟨*options*⟩** (no default, initially empty)

Sets ⟨*options*⟩ for the surrounding tcbraster[→ P. 290] of docPathOperation[→ P. 479], docPathOperation*[→ P. 479], and docPathOperations[→ P. 479].

N 2020-04-24 **/tcb/doc raster=⟨*options*⟩** (no default, initially empty)

Shortcut for setting the same ⟨*options*⟩ for /tcb/doc raster command, /tcb/doc raster environment, /tcb/doc raster key, and /tcb/doc raster path.

/tcb/doc head command=⟨*options*⟩ (no default, initially empty)

Sets ⟨*options*⟩ for the head line of docCommand[→ P. 474], docCommand*[→ P. 475], and docCommands[→ P. 475].

```
\tcbset{doc head command={interior style={fill,left color=red!20!white,
  right color=blue!20!white}}}

\begin{docCommand*}{myCommandE}{\marg{argument}}
  This is the documentation of \refCom{myCommandE} which takes one \meta{argument}.
  \refCom{myCommandE} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandE{⟨*argument*⟩}

This is the documentation of \myCommandE which takes one ⟨*argument*⟩. \myCommandE does some funny things with its ⟨*argument*⟩.

/tcb/doc head environment=⟨*options*⟩ (no default, initially empty)

Sets ⟨*options*⟩ for the head line of docEnvironment→P. 476, docEnvironment*→P. 476, and docEnvironments→P. 477.

```
\tcbset{doc head environment={beamer,boxsep=2pt,arc=2pt,colback=green!20!white}}

\begin{docEnvironment*}{myEnvironment}{\marg{argument}}
  This is the documentation of \refEnv{myEnvironment} which
  takes one \meta{argument}.
\end{docEnvironment*}
```

```
\begin{myEnvironment}{⟨argument⟩}
  ⟨environment content⟩
\end{myEnvironment}
```

This is the documentation of myEnvironment which takes one ⟨*argument*⟩.

/tcb/doc head key=⟨*options*⟩ (no default, initially empty)

Sets ⟨*options*⟩ for the head line of docKey→P. 478, docKey*→P. 478, and docKeys→P. 478.

```
\tcbset{doc head key={boxsep=4pt,arc=4pt,boxrule=0.6pt,
  frame style=fill,interior style=fill,colframe=green!50!black}}

\begin{docKey}{/foo/myKey}{}{no value}
  This is the documentation of \refKey{/foo/myKey}.
\end{docKey}
```

/foo/myKey (no value)

This is the documentation of /foo/myKey.

N 2019-09-18 **/tcb/doc head path=⟨*options*⟩** (no default, initially empty)

Sets ⟨*options*⟩ for the head line of docPathOperation→P. 479, docPathOperation*→P. 479, and docPathOperations→P. 479.

```
\tcbset{doc head command={interior style={fill,left color=red!7!white,
  right color=blue!7!white}}}

\begin{docPathOperation*}{-{}-}{\meta{coordinate or cycle}}
  This is the documentation of \refPathOperation{-{}-}.
\end{docPathOperation*}
```

```
\path ... --⟨coordinate or cycle⟩ ...;
```

This is the documentation of --.

U 2019-09-18 **/tcb/doc head=⟨*options*⟩** (no default, initially empty)

Shortcut for setting the same ⟨*options*⟩ for /tcb/doc head command→P. 492, /tcb/doc head environment, /tcb/doc head key, and /tcb/doc head path.

The description texts of the main documentation environments docCommand→P. 474, docEnvironment→P. 476, docKey→P. 478, etc, are set in a compact form without indention and parskip=0pt. This settings can overruled by using the following keys to insert code before (or after) the description texts.

N 2015-10-09 **/tcb/before doc body command=⟨*code*⟩** (no default, initially empty)

Executes ⟨*code*⟩ before the description texts of docCommand→P. 474 and docCommand*→P. 475.

```
\tcbset{before doc body command={%
    \setlength{\parindent}{2.5em}%
    \setlength{\parskip}{1ex plus 0.75ex minus 0.25ex}%
}}

\begin{docCommand*}{myCommandG}{\marg{argument}}
  This is the documentation of \refCom{myCommandG} which takes one \meta{argument}.
  \refCom{myCommandG} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandG{⟨*argument*⟩}

This is the documentation of \myCommandG which takes one ⟨*argument*⟩. \myCommandG does some funny things with its ⟨*argument*⟩.

N 2015-10-09 **/tcb/after doc body command=⟨*code*⟩** (no default, initially empty)

Executes ⟨*code*⟩ after the description texts of docCommand→P. 474 and docCommand*→P. 475.

```
\tcbset{after doc body command={%
    \hfill\nolinebreak[1]\hspace*{\fill}\textcolor{red}{$\diamondsuit$}%
}}

\begin{docCommand*}{myCommandH}{\marg{argument}}
  This is the documentation of \refCom{myCommandH} which takes one \meta{argument}.
  \refCom{myCommandH} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandH{⟨*argument*⟩}

This is the documentation of \myCommandH which takes one ⟨*argument*⟩. \myCommandH does some funny things with its ⟨*argument*⟩. ♢

N 2015-10-09 **/tcb/before doc body environment=⟨*code*⟩** (no default, initially empty)

Executes ⟨*code*⟩ before the description texts of docEnvironment→P. 476 and docEnvironment*→P. 476.

N 2015-10-09 **/tcb/after doc body environment=⟨*code*⟩** (no default, initially empty)

Executes ⟨*code*⟩ after the description texts of docEnvironment→P. 476 and docEnvironment*→P. 476.

N 2015-10-09 **/tcb/before doc body key=⟨*code*⟩** (no default, initially empty)

Executes ⟨*code*⟩ before the description texts of docKey→P. 478 and docKey*→P. 478.

N 2015-10-09 **/tcb/after doc body key=⟨*code*⟩** (no default, initially empty)

Executes ⟨*code*⟩ after the description texts of docKey→P. 478 and docKey*→P. 478.

N 2019-09-18 **/tcb/before doc body path**=⟨*code*⟩ (no default, initially empty)

Executes ⟨*code*⟩ before the description texts of docPathOperation→ P. 479 and docPathOperation*→ P. 479.

N 2019-09-18 **/tcb/after doc body path**=⟨*code*⟩ (no default, initially empty)

Executes ⟨*code*⟩ after the description texts of docPathOperation→ P. 479 and docPathOperation*→ P. 479.

N 2015-10-09
U 2019-09-18 **/tcb/before doc body**=⟨*options*⟩ (no default, initially empty)

Shortcut for setting the same ⟨*options*⟩ for /tcb/before doc body command→ P. 494, /tcb/before doc body environment→ P. 494, /tcb/before doc body key→ P. 494, and /tcb/before doc body path.

N 2015-10-09
U 2019-09-18 **/tcb/after doc body**=⟨*options*⟩ (no default, initially empty)

Shortcut for setting the same ⟨*options*⟩ for /tcb/after doc body command→ P. 494, /tcb/after doc body environment→ P. 494, /tcb/after doc body key→ P. 494, and /tcb/after doc body path.

25.4 General Customization Option Keys

U 2015-03-16 **/tcb/docexample** (style, no value)

Sets the style for dispExample[→P. 482] and dispListing[→P. 483] with the colors ExampleBack and ExampleFrame. To change the appearance of the examples, this style can be redefined.

```
% Predefined style:
\tcbset{
  docexample/.style={colframe=ExampleFrame,colback=ExampleBack,
    before skip=\medskipamount,after skip=\medskipamount,
    fontlower=\footnotesize}
}
```

/tcb/documentation listing options=⟨*key list*⟩ (no default, initially style=tcbdocumentation)

Sets the options from the package listings [6]. They are used inside dispExample[→P. 482] and dispListing[→P. 483] to typeset the listings. Note that this is not identical to the key /tcb/listing options[→P. 317] which is used for "normal" listings.
Used for /tcb/listing engine[→P. 322]=listings only.

/tcb/documentation listing style=⟨*listing style*⟩ (no default, initially tcbdocumentation)

Abbreviation for documentation listing options={style=...}. This key sets a ⟨*style*⟩ for the listings package, see [6]. Note that this is not identical to the key /tcb/listing style[→P. 317] which is used for "normal" listings.
Used for /tcb/listing engine[→P. 322]=listings only.

/tcb/documentation minted options=⟨*minted style*⟩ (no default, initially tabsize=2,fontsize=\small)

Sets the options from the package minted [12] which are used during typesetting of the listing, if used. Note that this is not identical to the key /tcb/minted options[→P. 320] which is used for "normal" listings.
Used for /tcb/listing engine[→P. 322]=minted only.

/tcb/documentation minted style=⟨*key list*⟩ (no default, initially unset)

Sets a ⟨*style*⟩ known to Pygments [14] for the package minted [12], if used. Note that this is not identical to the key /tcb/minted style[→P. 321] which is used for "normal" listings.
Used for /tcb/listing engine[→P. 322]=minted only.

N 2017-04-24 **/tcb/documentation minted language=**⟨*programming language*⟩ (no default, initially latex)

Sets a ⟨*programming language*⟩ known to Pygments [14] for the package minted [12], if used. Note that this is not identical to the key /tcb/minted language[→P. 320] which is used for "normal" listings.
Used for /tcb/listing engine[→P. 322]=minted only.

> ! The following two keys are deprecated and without function (v3.50 and above). Use /tcb/before[→P. 81] and /tcb/after[→P. 81] with appropriate values instead. Also see /tcb/docexample.

U 2015-03-16 **/tcb/before example=**⟨*macros*⟩ (no default, initially empty)

Sets the ⟨*macros*⟩ which are executed before dispExample[→P. 482] and dispListing[→P. 483] additional to /tcb/before[→P. 81]. deprecated

/tcb/after example=⟨*macros*⟩ (no default, initially empty)

Sets the ⟨*macros*⟩ which are executed after dispExample[→P. 482] and dispListing[→P. 483] additional to /tcb/after[→P. 81]. deprecated

N 2017-04-25 **/tcb/keywords bold=true|false** (default `true`, initially `true`)

Keyword used in `docEnvironment`[→ P. 476], `docCommand`[→ P. 474], etc. are printed boldface (or not). Since the typewriter font is used, the effect may be invisible with Computer Modern fonts or similar which do not have a bold variant. Note that references to keywords are not printed boldface at all.

```
\LARGE
\docAuxCommand{fooaux}, \refCom{tcbset}

\tcbset{keywords bold=false}
\docAuxCommand{fooaux}, \refCom{tcbset}
```

\fooaux, \tcbset[→ P. 13]
\fooaux, \tcbset[→ P. 13]

N 2015-01-09 **/tcb/index command=**⟨*macro*⟩ (no default, initially `\index`)

Replaces the internally used `\index` macro by the given ⟨*macro*⟩. The ⟨*macro*⟩ has to take one mandatory argument like `\index`. This option is mutually exclusive with `/tcb/index command name`.

```
\tcbset{index command=\myindexcommand}
```

N 2015-01-09 **/tcb/index command name=**⟨*name*⟩ (no default, initially unset)

Replaces the internally used `\index` macro by `\index[`⟨*name*⟩`]`, i.e. `\index{...}` is replaced by `\index[`⟨*name*⟩`]{...}`. This option is intended to be used with `imakeidx` and is mutually exclusive with `/tcb/index command`.

```
\tcbset{index command name=mydoc}
```

/tcb/index format=⟨*format*⟩ (no default, initially `pgf`)

Determines the basic ⟨*format*⟩ of the generated index. Feasible values are:

- `pgfsection`: The index is formatted like in the `pgf` documentation (as a section).
- `pgfchapter`: The index is formatted like in the `pgf` documentation (as a chapter).
- `pgf`: Alias for `pgfsection`.
- `doc`: The index is assumed to be formatted by `doc` or `ltxdoc`. The usage of `makeindex` with `-s gind.ist` is assumed. The package `hypdoc` has to be loaded *before* `tcolorbox`. Only a limited set of customizations will work! This option cannot be unset when used!
- `off`: The index is not formatted by `tcolorbox`. Use this, if the index is formatted by other package like `imakeidx`.

/tcb/index actual=⟨*character*⟩ (no default, initially `@`)

Sets the character for "actual" in automatic indexing.

/tcb/index quote=⟨*character*⟩ (no default, initially `"`)

Sets the character for "quote" in automatic indexing.

/tcb/index level=⟨*character*⟩ (no default, initially `!`)

Sets the character for "level" in automatic indexing.

/tcb/index default settings (style, no value)

Sets the `makeindex` default values for `/tcb/index actual`, `/tcb/index quote`, and `/tcb/index level`.

/tcb/index german settings (style, no value)

Sets the `makeindex` values recommended for German language texts. This is identical to setting the following:

```
\tcbset{index actual={=},index quote={!},index level={>}}
```

`/tcb/index annotate=true|false` (default `true`, initially `true`)

If set to `true`, the index entries are annotated with short descriptions given by `/tcb/doclang/environment` → P. 499, `/tcb/doclang/key` → P. 499, and others.

`/tcb/index colorize=true|false` (default `true`, initially `false`)

If set to `true`, the index entries colorized according to the color settings given by `/tcb/color environment`, `/tcb/color key`, and others.

`/tcb/color command=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by macro definitions.

`/tcb/color environment=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by environment definitions.

`/tcb/color key=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by key definitions.

N 2019-09-18 `/tcb/color path=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by T*i*kZ path operation definitions.

`/tcb/color value=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by value definitions.

N 2015-01-08 `/tcb/color counter=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by counter definitions.

N 2015-01-08 `/tcb/color length=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by length definitions.

`/tcb/color color=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by color definitions.

U 2019-09-18 `/tcb/color definition=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color for `/tcb/color command`, `/tcb/color environment`, `/tcb/color key`, `/tcb/color path`, `/tcb/color value`, `/tcb/color counter`, `/tcb/color length`, and `/tcb/color color`.

`/tcb/color option=`⟨*color*⟩ (no default, initially `Option`)

Sets the color used for optional arguments.

`/tcb/color fade=`⟨*color*⟩ (no default, initially `Fade`)

Sets the color used for faded text like \path in `docPathOperation` → P. 479.

`/tcb/color hyperlink=`⟨*color*⟩ (no default, initially `Hyperlink`)

Sets the color for all hyper-links, i. e. all internal and external links.

25.5 Language Option Keys

The following keys are provided for language specific settings. The English language is predefined.

`/tcb/english language` (style, no value)

Sets all language specific settings to English.

`/tcb/doclang/color=`⟨*text*⟩ (no default, initially `color`)

Text used in the index for colors.

`/tcb/doclang/colors=`⟨*text*⟩ (no default, initially `Colors`)

Heading text in the index for colors.

N 2015-01-08 `/tcb/doclang/counter=`⟨*text*⟩ (no default, initially `counter`)

Text used in the index for counters.

N 2015-01-08 `/tcb/doclang/counters=`⟨*text*⟩ (no default, initially `Counters`)

Heading text in the index for counters.

`/tcb/doclang/environment=`⟨*text*⟩ (no default, initially `environment`)

Text used in the index for environments.

`/tcb/doclang/environments=`⟨*text*⟩ (no default, initially `Environments`)

Heading text in the index for environments.

`/tcb/doclang/environment content=`⟨*text*⟩ (no default, initially `environment content`)

Text used in `docEnvironment` → P. 476.

`/tcb/doclang/index=`⟨*text*⟩ (no default, initially `Index`)

Heading text for the index.

`/tcb/doclang/key=`⟨*text*⟩ (no default, initially `key`)

Text used in the index for keys.

`/tcb/doclang/keys=`⟨*text*⟩ (no default, initially `Keys`)

Heading text used in the index for keys.

N 2015-01-08 `/tcb/doclang/length=`⟨*text*⟩ (no default, initially `length`)

Text used in the index for lengths.

N 2015-01-08 `/tcb/doclang/lengths=`⟨*text*⟩ (no default, initially `Lengths`)

Heading text in the index for lengths.

N 2014-09-19 `/tcb/doclang/new=`⟨*text*⟩ (no default, initially `New`)

Announcement text for new content.

N 2019-09-18 `/tcb/doclang/path=`⟨*text*⟩ (no default, initially `path operation`)

Text used in the index for path operations.

N 2019-09-18 `/tcb/doclang/paths=`⟨*text*⟩ (no default, initially `Path operations`)

Heading text in the index for path operations.

`/tcb/doclang/pageshort=`⟨*text*⟩ (no default, initially `P.`)

Short text for page references.

N 2014-09-19 `/tcb/doclang/updated=`⟨*text*⟩ (no default, initially `Updated`)

Announcement text for updated content.

`/tcb/doclang/value=`⟨*text*⟩ (no default, initially `value`)

Text used in the index for values.

`/tcb/doclang/values=`⟨*text*⟩ (no default, initially `Values`)

Heading text in the index for values.

25.6 Predefined Colors of the Library

U 2019-09-18

The following colors are predefined. They are used as default colors in some library commands.

`Option` , `Definition` , `ExampleFrame` , `ExampleBack` , `Hyperlink` , `Fade` .

A Picture Credits

The following pictures were used inside this documentation.

Basilica_5.png



http://commons.wikimedia.org/wiki/File:Basilica_5.png

lichtspiel.jpg



Photograph taken by Thomas F. Sturm.

crinklepaper.png



Created with GIMP.
http://www.gimp.org

pink_marble.png



Created with GIMP.
http://www.gimp.org

blueshade.png



Created with GIMP.
http://www.gimp.org

goldshade.png



Created with GIMP.
http://www.gimp.org

References

[1] Donald Arseneau. *The varwidth package*. Sept. 26, 2011.
https://mirrors.ctan.org/macros/latex/contrib/varwidth/varwidth-doc.pdf.

[2] Peter Breitenlohner. *The ε-TEX manual*. Version 2. Feb. 1998.
https://mirrors.ctan.org/systems/doc/etex/etex_man.pdf.

[3] David Carlisle. *The file ltxdoc.dtx for use with LaTeX 2ε*. Sept. 16, 2019.
https://mirror.ctan.org/macros/latex/base/ltxdoc.pdf.

[4] David Carlisle. *The tabularx package*. Jan. 15, 2020.
https://mirror.ctan.org/macros/latex/required/tools/tabularx.pdf.

[5] Toby Cubitt. *The cleveref Package*. Mar. 27, 2018.
https://mirror.ctan.org/macros/latex/contrib/cleveref/cleveref.pdf.

[6] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*. Version 1.8d. Mar. 24, 2020.
https://mirror.ctan.org/macros/latex/contrib/listings/listings.pdf.

[7] Philipp Lehman and Joseph Wright. *The etoolbox Package*. Sept. 21, 2019.
https://mirror.ctan.org/macros/latex/contrib/etoolbox/etoolbox.pdf.

[8] Frank Mittelbach. *The doc and shortvrb Packages*. June 30, 2011.
https://mirror.ctan.org/macros/latex/base/doc.dtx.

[9] Frank Mittelbach. *An environment for multicolumn output*. Feb. 2, 2020.
https://mirror.ctan.org/macros/latex/required/tools/multicol.pdf.

[10] Heiko Oberdiek. *The bookmark package*. Dec. 3, 2019.
https://mirrors.ctan.org/macros/latex/contrib/bookmark/bookmark.pdf.

[11] Heiko Oberdiek. *The listingsutf8 package*. Dec. 10, 2019.
http://mirrors.ctan.org/macros/latex/contrib/listingsutf8/listingsutf8.pdf.

[12] Geoffrey M. Poore. *The minted package. Highlighted source code in LaTeX*. July 19, 2017.
https://mirror.ctan.org/macros/latex/contrib/minted/minted.pdf.

[13] The LaTeX3 Project. *The xparse Package*. Mar. 6, 2020.
https://mirror.ctan.org/macros/latex/contrib/l3packages/xparse.pdf.

[14] *Pygments. Python syntax highlighter*. 2019.
https://pygments.org/.

[15] Sebastian Rahtz and Heiko Oberdiek. *Hypertext marks in LaTeX: a manual for hyperref*. Jan. 2020.
https://mirrors.ctan.org/macros/latex/contrib/hyperref/doc/manual.pdf.

[16] Will Robertson. *A couple of things involving environments*. May 4, 2014.
https://mirror.ctan.org/macros/latex/contrib/environ/environ.pdf.

[17] Rainer Schöpf, Bernd Raichle, and Chris Rowley. *A New Implementation of LaTeX's verbatim and verbatim* Environments*. Mar. 12, 2001.
https://mirror.ctan.org/macros/latex/required/tools/verbatim.pdf.

[18] Thomas F. Sturm. *LaTeX– Einführung in das Textsatzsystem*. 12th edition. IT-Handbücher. Hannover: Leibnitz Universität Hannover IT Services (LUIS), July 2019.
https://www.luis.uni-hannover.de/buch.html?&titel=latex.

[19] Thomas F. Sturm. *Höhere Mathematik: Fortgeschrittene mathematische Methoden (M.Eng.)* Vorlesungs-Skriptum. Neubiberg: Universität der Bundeswehr München, 2019.
https://www.unibw.de/bw/professuren/thomas-sturm.

[20] Thomas F. Sturm. *Mathematik 1 (B.Eng.)* Vorlesungs-Skriptum. Neubiberg: Universität der Bundeswehr München, 2019.
https://www.unibw.de/bw/professuren/thomas-sturm.

[21] Thomas F. Sturm. *Mathematik 2 (B.Eng.)* Vorlesungs-Skriptum. Neubiberg: Universität der Bundeswehr München, 2019.
https://www.unibw.de/bw/professuren/thomas-sturm.

[22] Till Tantau. *The TikZ and PGF Packages. Manual for version 3.1.5b.* Jan. 8, 2020.
https://mirrors.ctan.org/graphics/pgf/base/doc/pgfmanual.pdf.

[23] Till Tantau, Joseph Wright, and Vedran Miletić. *The Beamer Class. User Guide for version 3.57.* Sept. 30, 2019.
https://mirrors.ctan.org/macros/latex/contrib/beamer/doc/beameruserguide.pdf.

Index

- key, 463
foo path (horizontal then vertical) path operation, 489
/foo/myKey key, 493
! key, 463

0 value, 151
1 value, 151
2 value, 151

above key, 421
absquote environment, 483
add to height key, 55
add to list key, 102
add to natural height key, 55
add to width key, 34
adjust text key, 18
adjusted title key, 18
adjusted title after break key, 380
after key, 81
after app key, 440
after doc body key, 495
after doc body command key, 494
after doc body environment key, 494
after doc body key key, 494
after doc body path key, 495
after example key, 496
after lower key, 68
after lower app key, 440
after lower pre key, 440
after lower* key, 68
after pre key, 440
after skip key, 83
after title key, 64
after title app key, 439
after title pre key, 439
after upper key, 66
after upper app key, 439
after upper pre key, 439
after upper* key, 66
alert key, 272
all key, 10
all value, 48, 49, 299, 382, 384
ams align key, 365
ams align lower key, 365
ams align upper key, 365
ams align* key, 365
ams align* lower key, 365
ams align* upper key, 365
ams equation key, 364
ams equation lower key, 364
ams equation upper key, 364
ams equation* key, 364
ams equation* lower key, 364
ams equation* upper key, 364
ams gather key, 366
ams gather lower key, 366
ams gather upper key, 366
ams gather* key, 366
ams gather* lower key, 366
ams gather* upper key, 366
ams nodisplayskip key, 367
ams nodisplayskip lower key, 367
ams nodisplayskip upper key, 367
arc key, 36
arc is angular key, 38
arc is curved key, 38
areasize value, 435
areasize* value, 435
as-is value, 260
at key, 422
at begin tikz key, 196
at begin tikz reset key, 196
at end tikz key, 196
at end tikz reset key, 196
attach boxed title to bottom key, 160
attach boxed title to bottom center key, 159
attach boxed title to bottom left key, 159
attach boxed title to bottom right key, 159
attach boxed title to bottom* key, 160
attach boxed title to top key, 160
attach boxed title to top center key, 159
attach boxed title to top left key, 159
attach boxed title to top right key, 159
attach boxed title to top* key, 160
attach title key, 20
attach title to upper key, 20
auto value, 100
auto counter key, 111
auto limited value, 100
auto outer arc key, 38
autoparskip key, 81

base value, 82
base color key, 280
baseline key, 82
baselineskip value, 382
beamer key, 233
beamer Skin, 233
beamer alerted key, 272
beamer hidden key, 271
beamerfirst Skin, 235
beamerlast Skin, 237
beamermiddle Skin, 236
bean arc key, 37
before key, 81
before app key, 440
before doc body key, 495
before doc body command key, 494
before doc body environment key, 494

before doc body key key, 494
before doc body path key, 495
before example key, 496
before lower key, 67
before lower app key, 440
before lower pre key, 440
before lower* key, 67
before nobreak key, 84
before pre key, 440
before skip key, 83
before title key, 64
before title app key, 439
before title pre key, 439
before upper key, 65
before upper app key, 439
before upper pre key, 439
before upper* key, 65
beforeafter skip key, 83
below key, 421
between key, 422
bicolor key, 225
bicolor Skin, 224
bicolorfirst Skin, 226
bicolorlast Skin, 228
bicolormiddle Skin, 227
blank key, 213
blanker key, 243
blankest key, 244
blend before title key, 116
blend before title code key, 117
blend into key, 115
bookmark key, 103
bookmark* key, 103
borderline key, 181
borderline east key, 184
borderline horizontal key, 185
borderline north key, 184
borderline south key, 184
borderline vertical key, 185
borderline west key, 184
both value, 126
bottom key, 43
bottom value, 33, 82, 120, 298
bottom seam value, 120
bottomrule key, 35
bottomrule at break key, 383
bottomsep at break key, 383
bottomtitle key, 43
box align key, 82
\boxarrayclear, 403
\boxarraygetbox, 407
\boxarraygetdepth, 408
\boxarraygetheight, 408
\boxarraygetsize, 405
\boxarraygettotalheight, 409
\boxarraygetwidth, 408
\boxarrayreset, 402
boxarraystore environment, 405
boxed title size key, 162
boxed title style key, 163
boxes key, 417
boxrule key, 36
boxsep key, 39
\brackets, 482
break value, 369
break at key, 381
breakable key, 9, 379
broken value, 169–171

capture key, 97
center key, 88
center value, 30, 33, 82, 120, 298
center lower key, 32
center seam value, 120
center title key, 33
center upper key, 32
change value, 369
change apart value, 369
change break value, 369
change standard value, 368
check odd page key, 104
circular arc key, 37
clear preamble key, 470
clear preclass key, 470
clip lower key, 180
clip title key, 179
clip upper key, 179
clip watermark key, 175
clipped value, 281
code key, 109
colback key, 27
colbacklower key, 225
colbacktitle key, 27
\colDef, 486
\colFade, 487
colframe key, 27
collower key, 28
colon value, 116
colon hang value, 116
\colOpt, 486
color key, 499
color color key, 498
color command key, 498
color counter key, 498
color definition key, 498
color environment key, 498
color fade key, 498
color from key, 280
color hyperlink key, 498
color key key, 498
color length key, 498
color option key, 498
color path key, 498
color value key, 498
Colors
    Definition, 500
    ExampleBack, 500
    ExampleFrame, 500
    Fade, 500

foocolor, 481
Hyperlink, 500
Option, 500
tcbcolback, 149
tcbcolbacklower, 149
tcbcolbacktitle, 149
tcbcolframe, 149
tcbcollower, 149
tcbcoltitle, 149
tcbcolupper, 149
colors key, 499
colspacing key, 415
coltext key, 28
coltitle key, 28
column key, 419
column* key, 419
columns key, 415
colupper key, 28
comment key, 323
comment above listing key, 331
comment above* listing key, 331
comment and listing key, 326
comment only key, 323
comment outside listing key, 329
comment side listing key, 328
comment style key, 326
compilable listing key, 335
compiler key, 469
compress page key, 382
\consumeboxarray, 406
\consumetcboxarray, 406
copy value, 162
counter key, 499
Counters
foocounter, 480
counters key, 499
coverage key, 416
Crefname key, 114
crefname key, 114
\cs, 481

dash value, 116
dash hang value, 116
\DeclareTCBInputListing, 459
\DeclareTCBListing, 457
\DeclareTCBox, 454
\DeclareTCBoxFit, 460
\DeclareTColorBox, 451
\DeclareTotalTCBox, 455
\DeclareTotalTCBoxFit, 461
\DeclareTotalTColorBox, 453
Definition color, 500
description color key, 357
description delimiters key, 357
description delimiters none key, 357
description delimiters parenthesis key, 357
description font key, 358
description formatter key, 358
detach title key, 20
direct value, 281
dispExample environment, 482
dispExample* environment, 482
dispListing environment, 483
dispListing* environment, 483
do not store to box array key, 405
doc value, 497
doc description key, 489
doc head key, 493
doc head command key, 492
doc head environment key, 493
doc head key key, 493
doc head path key, 493
doc index key, 489
doc into index key, 490
doc keypath key, 488
doc label key, 489
doc left key, 491
doc left indent key, 491
doc marginnote key, 490
doc name key, 488
doc new key, 490
doc new and updated key, 490
doc no index key, 490
doc parameter key, 488
doc raster key, 492
doc raster command key, 492
doc raster environment key, 492
doc raster key key, 492
doc raster path key, 492
doc right key, 491
doc right indent key, 491
doc sort index key, 489
doc updated key, 490
\docAuxCommand, 480
\docAuxCommand*, 480
\docAuxEnvironment, 480
\docAuxEnvironment*, 480
\docAuxKey, 480
\docAuxKey*, 480
\docColor, 481
\docColor*, 481
docCommand environment, 474
docCommand* environment, 475
docCommands environment, 475
\docCounter, 480
\docCounter*, 480
docEnvironment environment, 476
docEnvironment* environment, 476
docEnvironments environment, 477
docexample key, 496
docKey environment, 478
docKey* environment, 478
docKeys environment, 478
\docLength, 481
\docLength*, 481
docPathOperation environment, 479
docPathOperation* environment, 479
docPathOperations environment, 479

documentation key, 10
documentation listing options key, 496
documentation listing style key, 496
documentation minted language key, 496
documentation minted options key, 496
documentation minted style key, 496
\docValue, 480
\docValue*, 480
downhill value, 48, 49
draft key, 253
draft Skin, 253
draftmode key, 208
draw method key, 281
drop fuzzy midday shadow key, 187
drop fuzzy shadow key, 186
drop fuzzy shadow east key, 190
drop fuzzy shadow north key, 190
drop fuzzy shadow northeast key, 190
drop fuzzy shadow northwest key, 190
drop fuzzy shadow south key, 189
drop fuzzy shadow southeast key, 189
drop fuzzy shadow southwest key, 189
drop fuzzy shadow west key, 189
drop large lifted shadow key, 191
drop lifted shadow key, 191
drop midday shadow key, 186
drop shadow key, 186
drop shadow east key, 189
drop shadow north key, 188
drop shadow northeast key, 189
drop shadow northwest key, 188
drop shadow south key, 188
drop shadow southeast key, 188
drop shadow southwest key, 188
drop shadow west key, 188
drop small lifted shadow key, 191

east fading, 281
east value, 48, 49
east size key, 278
east style key, 279
empty key, 242
empty Skin, 242
empty value, 138, 139
emptyfirst Skin, 245
emptylast Skin, 247
emptymiddle Skin, 246
enforce breakable key, 380
english language key, 499
enhanced key, 211
enhanced Skin, 211
enhanced jigsaw key, 218
enhanced jigsaw Skin, 218
enhanced standard key, 213
enhanced standard jigsaw key, 218
enhancedfirst Skin, 215
enhancedfirst jigsaw Skin, 219
enhancedlast Skin, 217
enhancedlast jigsaw Skin, 223
enhancedmiddle Skin, 216
enhancedmiddle jigsaw Skin, 220
enlarge bottom at break by key, 86
enlarge bottom by key, 86
enlarge bottom finally by key, 85
enlarge by key, 87
enlarge left by key, 86
enlarge right by key, 86
enlarge top at break by key, 86
enlarge top by key, 86
enlarge top initially by key, 85
enlargepage key, 381
enlargepage flexible key, 382
environment key, 469, 499
environment content key, 499
environment with percent key, 469
Environments
    absquote, 483
    boxarraystore, 405
    dispExample, 482
    dispExample*, 482
    dispListing, 483
    dispListing*, 483
    docCommand, 474
    docCommand*, 475
    docCommands, 475
    docEnvironment, 476
    docEnvironment*, 476
    docEnvironments, 477
    docKey, 478
    docKey*, 478
    docKeys, 478
    docPathOperation, 479
    docPathOperation*, 479
    docPathOperations, 479
    extcolorbox, 466
    extikzpicture, 467
    fooauxenv, 480
    foocolorbox, 476
    foocolorbox*, 476
    posterboxenv, 418
    tcbclipframe, 176
    tcbclipinterior, 178
    tcbcliptitle, 178
    tcbexternal, 464
    tcbinvclipframe, 177
    tcbitemize, 291
    tcblisting, 311
    tcboutputlisting, 313
    tcboxeditemize, 293
    tcboxedraster, 292
    tcbposter, 413
    tcbraster, 290
    tcbverbatimwrite, 129
    tcbwritetemp, 129
    tcolorbox, 12
environments key, 499
equal height group key, 61
evenpage value, 46, 89
every box key, 94

every box on higher layers key, 95
every box on layer n key, 95
every float key, 80
every listing line key, 318
every listing line* key, 318
ExampleBack color, 500
ExampleFrame color, 500
extcolorbox environment, 466
extend freelance key, 255
extend freelancefirst key, 255
extend freelancelast key, 255
extend freelancemiddle key, 255
external key, 10, 108
externalize key, 463
externalize example key, 468
externalize example! key, 468
externalize listing key, 468
externalize listing! key, 468
extikzpicture environment, 467
extras key, 385
extras broken key, 385
extras broken pre key, 448
extras first key, 385
extras first and middle key, 386
extras first and middle pre key, 448
extras first pre key, 448
extras last key, 385
extras last pre key, 448
extras middle key, 385
extras middle and last key, 385
extras middle and last pre key, 448
extras middle pre key, 448
extras pre key, 448
extras title after break key, 386
extras unbroken key, 385
extras unbroken and first key, 385
extras unbroken and first pre key, 448
extras unbroken and last key, 385
extras unbroken and last pre key, 448
extras unbroken pre key, 448
extrude bottom by key, 93
extrude by key, 93
extrude left by key, 92
extrude right by key, 92
extrude top by key, 93

Fade color, 500
fade in key, 282
fade out key, 282
Fadings
    east, 281
    north, 281
    semi east, 281
    semi north, 281
    semi south, 281
    semi west, 281
    south, 281
    west, 281
false value, 81, 84, 300, 379
fbox value, 44
figures value, 115
fill downwards key, 90
fill image opacity key, 267
fill image options key, 267
fill image scale key, 267
fill overzoom image key, 263
fill overzoom image* key, 263
fill overzoom picture key, 263
fill plain image key, 261
fill plain image* key, 261
fill plain picture key, 261
fill shrink image key, 265
fill shrink image* key, 265
fill shrink picture key, 265
fill stretch image key, 262
fill stretch image* key, 262
fill stretch picture key, 262
fill tile image key, 266
fill tile image* key, 266
fill tile picture key, 266
fill tile picture* key, 266
fill zoom image key, 264
fill zoom image* key, 264
fill zoom picture key, 264
final value, 437
finish key, 201
finish broken key, 202
finish broken pre key, 446
finish fading vignette key, 286
finish first key, 202
finish first and middle key, 202
finish first and middle pre key, 446
finish first pre key, 446
finish last key, 202
finish last pre key, 446
finish middle key, 202
finish middle and last key, 202
finish middle and last pre key, 446
finish middle pre key, 446
finish pre key, 446
finish raised fading vignette key, 285
finish unbroken key, 202
finish unbroken and first key, 202
finish unbroken and first pre key, 446
finish unbroken and last key, 202
finish unbroken and last pre key, 446
finish unbroken pre key, 446
finish vignette key, 285
first value, 169–171, 384
first and middle value, 169, 384
fit key, 429
fit algorithm key, 435
fit basedim key, 430
fit fontsize macros key, 431
fit height from key, 434
fit height plus key, 432
fit maxfontdiff key, 437
fit maxfontdiffgap key, 437
fit maxstep key, 437

fit maxwidthdiff key, 437
fit maxwidthdiffgap key, 437
fit skip key, 430
fit to key, 430
fit to height key, 430
fit warning key, 437
fit width from key, 433
fit width plus key, 432
fitbox value, 97
fitting key, 9
fixed height key, 420
flip title key, 160
float key, 79
float* key, 79
floatplacement key, 79
flush center value, 30, 32, 33
flush left key, 88
flush left value, 30, 32, 33
flush right key, 88
flush right value, 30, 32, 33
flushleft lower key, 32
flushleft title key, 33
flushleft upper key, 32
flushright lower key, 32
flushright title key, 33
flushright upper key, 32
fontlower key, 29
fontsize key, 417
fontsize value, 435
fontsize* value, 435
fonttitle key, 29
fontupper key, 29
\fooaux, 480, 497
fooaux key, 480
fooauxenv environment, 480
foocolor color, 481
foocolorbox environment, 476
foocolorbox* environment, 476
foocounter counter, 480
foodummy key, 484
foodummy 2 key, 484
\foolength length, 481
\foomakedocSubKey, 475
\foomakedocSubKey*, 475
fooop path operation, 479
\foosomething, 490
footitle key, 478
force nobeforeafter key, 81
force remake key, 463
forced value, 46, 89
forced center value, 100
forced left value, 100
forced right value, 100
frame code key, 141
frame code app key, 446
frame code pre key, 446
frame empty key, 141
frame engine key, 138
frame hidden key, 153
frame style key, 152
frame style image key, 152
frame style tile key, 153
freelance key, 255
freelance Skin, 255
freelance value, 138, 139
freelancefirst Skin, 255
freelancelast Skin, 255
freelancemiddle Skin, 255
freeze extension key, 338
freeze file key, 338
freeze jpg key, 338
freeze none key, 338
freeze pdf key, 338
freeze png key, 338
fuzzy halo key, 187
fuzzy shadow key, 193

geometry nodes key, 140
graphical environment key, 138
graphics directory key, 259
graphics options key, 259
graphics orientation key, 260
graphics pages key, 259
grow sidewards by key, 88
grow to left by key, 87
grow to right by key, 87

halign key, 30
halign lower key, 31
halign title key, 32
halign upper key, 30
halo key, 187
hbox key, 97
hbox value, 97
hbox boxed title key, 167
height key, 53, 415
height fill key, 56
height fixed for key, 384
height from key, 54
height plus key, 53
hide key, 271
highlight math key, 363
highlight math style key, 363
hooks key, 9
horizontal size key, 279
hybrid value, 435
hybrid* value, 435
Hyperlink color, 500
hyperlink key, 203
hyperlink interior key, 204
hyperlink node key, 204
hyperlink title key, 204
hyperref key, 203
hyperref interior key, 203
hyperref node key, 203
hyperref title key, 203
hypertarget key, 103
hyperurl key, 204
hyperurl interior key, 204

hyperurl node key, 204
hyperurl title key, 204
hyperurl* key, 204
hyperurl* interior key, 204
hyperurl* node key, 204
hyperurl* title key, 204
hyphenationfix key, 99

if odd page key, 104
if odd page or oneside key, 104
if odd page or oneside* key, 105
if odd page* key, 105
IfBooleanF key, 450
IfBooleanT key, 450
IfBooleanTF key, 450
\ifboxarrayempty, 407
IfNoValueF key, 449
IfNoValueT key, 449
IfNoValueTF key, 449
IfValueF key, 450
IfValueT key, 450
IfValueTF key, 450
ignore nobreak key, 84
ignored value, 24
image comment key, 323
\imagename, 257
\imagepage, 258
index key, 103, 499
index actual key, 497
index annotate key, 498
index colorize key, 498
index command key, 497
index command name key, 497
index default settings key, 497
index format key, 497
index german settings key, 497
index level key, 497
index quote key, 497
index* key, 103
inherit height key, 57
input source on error key, 469
inside node key, 277
interior code key, 142
interior code app key, 447
interior code pre key, 447
interior empty key, 142
interior engine key, 139
interior hidden key, 154
interior style key, 153
interior style image key, 154
interior style tile key, 154
interior titled code key, 141
interior titled code app key, 446
interior titled code pre key, 447
interior titled empty key, 141
interior titled engine key, 138
invisible key, 22
invisible value, 19, 22, 24

justify value, 30

key key, 499
Keys
/foo/myKey, 493
/foo/
fooaux, 480
foodummy, 484
foodummy 2, 484
footitle, 478
/tcb/
add to height, 55
add to list, 102
add to natural height, 55
add to width, 34
adjust text, 18
adjusted title, 18
adjusted title after break, 380
after, 81
after app, 440
after doc body, 495
after doc body command, 494
after doc body environment, 494
after doc body key, 494
after doc body path, 495
after example, 496
after lower, 68
after lower app, 440
after lower pre, 440
after lower*, 68
after pre, 440
after skip, 83
after title, 64
after title app, 439
after title pre, 439
after upper, 66
after upper app, 439
after upper pre, 439
after upper*, 66
alert, 272
ams align, 365
ams align lower, 365
ams align upper, 365
ams align*, 365
ams align* lower, 365
ams align* upper, 365
ams equation, 364
ams equation lower, 364
ams equation upper, 364
ams equation*, 364
ams equation* lower, 364
ams equation* upper, 364
ams gather, 366
ams gather lower, 366
ams gather upper, 366
ams gather*, 366
ams gather* lower, 366
ams gather* upper, 366
ams nodisplayskip, 367
ams nodisplayskip lower, 367
ams nodisplayskip upper, 367

arc, 36
arc is angular, 38
arc is curved, 38
at begin tikz, 196
at begin tikz reset, 196
at end tikz, 196
at end tikz reset, 196
attach boxed title to bottom, 160
attach boxed title to bottom center, 159
attach boxed title to bottom left, 159
attach boxed title to bottom right, 159
attach boxed title to bottom*, 160
attach boxed title to top, 160
attach boxed title to top center, 159
attach boxed title to top left, 159
attach boxed title to top right, 159
attach boxed title to top*, 160
attach title, 20
attach title to upper, 20
auto outer arc, 38
autoparskip, 81
baseline, 82
beamer, 233
beamer alerted, 272
beamer hidden, 271
bean arc, 37
before, 81
before app, 440
before doc body, 495
before doc body command, 494
before doc body environment, 494
before doc body key, 494
before doc body path, 495
before example, 496
before lower, 67
before lower app, 440
before lower pre, 440
before lower*, 67
before nobreak, 84
before pre, 440
before skip, 83
before title, 64
before title app, 439
before title pre, 439
before upper, 65
before upper app, 439
before upper pre, 439
before upper*, 65
beforeafter skip, 83
bicolor, 225
blank, 213
blanker, 243
blankest, 244
blend before title, 116
blend before title code, 117
bookmark, 103
bookmark*, 103
borderline, 181
borderline east, 184
borderline horizontal, 185
borderline north, 184
borderline south, 184
borderline vertical, 185
borderline west, 184
bottom, 43
bottomrule, 35
bottomrule at break, 383
bottomsep at break, 383
bottomtitle, 43
box align, 82
boxed title size, 162
boxed title style, 163
boxrule, 36
boxsep, 39
break at, 381
breakable, 379
capture, 97
center, 88
center lower, 32
center title, 33
center upper, 32
check odd page, 104
circular arc, 37
clip lower, 180
clip title, 179
clip upper, 179
clip watermark, 175
code, 109
colback, 27
colbacklower, 225
colbacktitle, 27
colframe, 27
collower, 28
color color, 498
color command, 498
color counter, 498
color definition, 498
color environment, 498
color fade, 498
color hyperlink, 498
color key, 498
color length, 498
color option, 498
color path, 498
color value, 498
coltext, 28
coltitle, 28
colupper, 28
comment, 323
comment above listing, 331
comment above* listing, 331
comment and listing, 326
comment only, 323

comment outside listing, 329
comment side listing, 328
comment style, 326
compilable listing, 335
compress page, 382
description color, 357
description delimiters, 357
description delimiters none, 357
description delimiters parenthesis, 357
description font, 358
description formatter, 358
detach title, 20
do not store to box array, 405
doc description, 489
doc head, 493
doc head command, 492
doc head environment, 493
doc head key, 493
doc head path, 493
doc index, 489
doc into index, 490
doc keypath, 488
doc label, 489
doc left, 491
doc left indent, 491
doc marginnote, 490
doc name, 488
doc new, 490
doc new and updated, 490
doc no index, 490
doc parameter, 488
doc raster, 492
doc raster command, 492
doc raster environment, 492
doc raster key, 492
doc raster path, 492
doc right, 491
doc right indent, 491
doc sort index, 489
doc updated, 490
docexample, 496
documentation listing options, 496
documentation listing style, 496
documentation minted language, 496
documentation minted options, 496
documentation minted style, 496
draft, 253
draftmode, 208
drop fuzzy midday shadow, 187
drop fuzzy shadow, 186
drop fuzzy shadow east, 190
drop fuzzy shadow north, 190
drop fuzzy shadow northeast, 190
drop fuzzy shadow northwest, 190
drop fuzzy shadow south, 189
drop fuzzy shadow southeast, 189
drop fuzzy shadow southwest, 189
drop fuzzy shadow west, 189
drop large lifted shadow, 191
drop lifted shadow, 191
drop midday shadow, 186
drop shadow, 186
drop shadow east, 189
drop shadow north, 188
drop shadow northeast, 189
drop shadow northwest, 188
drop shadow south, 188
drop shadow southeast, 188
drop shadow southwest, 188
drop shadow west, 188
drop small lifted shadow, 191
empty, 242
enforce breakable, 380
english language, 499
enhanced, 211
enhanced jigsaw, 218
enhanced standard, 213
enhanced standard jigsaw, 218
enlarge bottom at break by, 86
enlarge bottom by, 86
enlarge bottom finally by, 85
enlarge by, 87
enlarge left by, 86
enlarge right by, 86
enlarge top at break by, 86
enlarge top by, 86
enlarge top initially by, 85
enlargepage, 381
enlargepage flexible, 382
equal height group, 61
every box, 94
every box on higher layers, 95
every box on layer n, 95
every float, 80
every listing line, 318
every listing line*, 318
extend freelance, 255
extend freelancefirst, 255
extend freelancelast, 255
extend freelancemiddle, 255
external, 108
externalize example, 468
externalize example!, 468
externalize listing, 468
externalize listing!, 468
extras, 385
extras broken, 385
extras broken pre, 448
extras first, 385
extras first and middle, 386
extras first and middle pre, 448
extras first pre, 448
extras last, 385
extras last pre, 448
extras middle, 385
extras middle and last, 385
extras middle and last pre, 448

extras middle pre, 448
extras pre, 448
extras title after break, 386
extras unbroken, 385
extras unbroken and first, 385
extras unbroken and first pre, 448
extras unbroken and last, 385
extras unbroken and last pre, 448
extras unbroken pre, 448
extrude bottom by, 93
extrude by, 93
extrude left by, 92
extrude right by, 92
extrude top by, 93
fill downwards, 90
finish, 201
finish broken, 202
finish broken pre, 446
finish fading vignette, 286
finish first, 202
finish first and middle, 202
finish first and middle pre, 446
finish first pre, 446
finish last, 202
finish last pre, 446
finish middle, 202
finish middle and last, 202
finish middle and last pre, 446
finish middle pre, 446
finish pre, 446
finish raised fading vignette, 285
finish unbroken, 202
finish unbroken and first, 202
finish unbroken and first pre, 446
finish unbroken and last, 202
finish unbroken and last pre, 446
finish unbroken pre, 446
finish vignette, 285
fit, 429
fit algorithm, 435
fit basedim, 430
fit fontsize macros, 431
fit height from, 434
fit height plus, 432
fit maxfontdiff, 437
fit maxfontdiffgap, 437
fit maxstep, 437
fit maxwidthdiff, 437
fit maxwidthdiffgap, 437
fit skip, 430
fit to, 430
fit to height, 430
fit warning, 437
fit width from, 433
fit width plus, 432
flip title, 160
float, 79
float*, 79
floatplacement, 79
flush left, 88
flush right, 88
flushleft lower, 32
flushleft title, 33
flushleft upper, 32
flushright lower, 32
flushright title, 33
flushright upper, 32
fontlower, 29
fonttitle, 29
fontupper, 29
force nobeforeafter, 81
frame code, 141
frame code app, 446
frame code pre, 446
frame empty, 141
frame engine, 138
frame hidden, 153
frame style, 152
frame style image, 152
frame style tile, 153
freelance, 255
freeze extension, 338
freeze file, 338
freeze jpg, 338
freeze none, 338
freeze pdf, 338
freeze png, 338
fuzzy halo, 187
fuzzy shadow, 193
geometry nodes, 140
graphical environment, 138
graphics directory, 259
graphics options, 259
graphics orientation, 260
graphics pages, 259
grow sidewards by, 88
grow to left by, 87
grow to right by, 87
halign, 30
halign lower, 31
halign title, 32
halign upper, 30
halo, 187
hbox, 97
hbox boxed title, 167
height, 53
height fill, 56
height fixed for, 384
height from, 54
height plus, 53
hide, 271
highlight math, 363
highlight math style, 363
hyperlink, 203
hyperlink interior, 204
hyperlink node, 204
hyperlink title, 204
hyperref, 203

hyperref interior, 203
hyperref node, 203
hyperref title, 203
hypertarget, 103
hyperurl, 204
hyperurl interior, 204
hyperurl node, 204
hyperurl title, 204
hyperurl*, 204
hyperurl* interior, 204
hyperurl* node, 204
hyperurl* title, 204
hyphenationfix, 99
if odd page, 104
if odd page or oneside, 104
if odd page or oneside*, 105
if odd page*, 105
IfBooleanF, 450
IfBooleanT, 450
IfBooleanTF, 450
IfNoValueF, 449
IfNoValueT, 449
IfNoValueTF, 449
IfValueF, 450
IfValueT, 450
IfValueTF, 450
ignore nobreak, 84
image comment, 323
index, 103
index actual, 497
index annotate, 498
index colorize, 498
index command, 497
index command name, 497
index default settings, 497
index format, 497
index german settings, 497
index level, 497
index quote, 497
index*, 103
inherit height, 57
interior code, 142
interior code app, 447
interior code pre, 447
interior empty, 142
interior engine, 139
interior hidden, 154
interior style, 153
interior style image, 154
interior style tile, 154
interior titled code, 141
interior titled code app, 446
interior titled code pre, 447
interior titled empty, 141
interior titled engine, 138
invisible, 22
keywords bold, 497
label, 101
label separator, 359
label type, 101
left, 39
left skip, 84
left*, 39
lefthand ratio, 123
lefthand width, 122
leftlower, 40
leftright skip, 84
leftrule, 35
lefttitle, 40
leftupper, 40
lifted shadow, 194
lines before break, 380
list entry, 102
list text, 102
listing above comment, 330
listing above text, 329
listing above* comment, 330
listing above* text, 329
listing and comment, 326
listing and text, 322
listing engine, 322
listing file, 322
listing inputencoding, 318
listing only, 322
listing options, 317
listing options app, 448
listing options pre, 448
listing outside comment, 329
listing outside text, 327
listing remove caption, 318
listing side comment, 328
listing side text, 327
listing style, 317
listing utf8, 319
lower separated, 25
lowerbox, 24
marker, 220
math, 364
math lower, 364
math upper, 364
middle, 43
minimum for current equal height group, 62
minimum for equal height group, 62
minipage, 97
minipage boxed title, 167
minipage boxed title*, 167
minted language, 320
minted options, 320
minted options app, 448
minted options pre, 448
minted style, 321
move upwards, 90
move upwards*, 90
nameref, 102
natural height, 53
nirvana, 110
no borderline, 183

no boxed title style, 166
no extras, 385
no extras first, 385
no extras last, 385
no extras middle, 385
no extras title after break, 386
no extras unbroken, 385
no finish, 202
no finish first, 202
no finish last, 202
no finish middle, 202
no finish unbroken, 202
no label type, 101
no listing options, 317
no overlay, 75
no process, 335
no recording, 131
no shadow, 186
no underlay, 199
no underlay boxed title, 200
no underlay first, 200
no underlay last, 200
no underlay middle, 200
no underlay unbroken, 200
no watermark, 171
nobeforeafter, 81
nofloat, 79
noparskip, 81
nophantom, 101
notitle, 18
notitle after break, 380
octogon arc, 37
on line, 99
only, 270
opacityback, 51
opacitybacktitle, 51
opacityfill, 51
opacityframe, 51
opacitylower, 52
opacitytext, 52
opacitytitle, 52
opacityupper, 52
outer arc, 38
overlay, 74
overlay app, 441
overlay broken, 75
overlay broken app, 442
overlay broken pre, 442
overlay first, 75
overlay first and middle, 75
overlay first and middle app, 442
overlay first and middle pre, 442
overlay first app, 441
overlay first pre, 441
overlay last, 75
overlay last app, 442
overlay last pre, 442
overlay middle, 75
overlay middle and last, 75
overlay middle and last app, 442
overlay middle and last pre, 442
overlay middle app, 442
overlay middle pre, 442
overlay pre, 441
overlay unbroken, 75
overlay unbroken and first, 75
overlay unbroken and first app, 442
overlay unbroken and first pre, 442
overlay unbroken and last, 75
overlay unbroken and last app, 442
overlay unbroken and last pre, 442
overlay unbroken app, 441
overlay unbroken pre, 441
oversize, 45
pad after break, 383
pad at break, 383
pad at break*, 383
pad before break, 383
pad before break*, 383
parbox, 98
parfillskip restore, 84
parskip, 81
pdf comment, 325
pdf extension, 326
phantom, 101
phantomlabel, 101
placeholder, 424
process code, 335
raster after skip, 296
raster before skip, 296
raster column n, 300
raster column skip, 297
raster columns, 294
raster equal height, 299
raster equal height group, 299
raster equal skip, 296
raster even column, 300
raster even number, 301
raster even row, 301
raster every box, 300
raster force size, 300
raster halign, 298
raster height, 296
raster left skip, 297
raster multicolumn, 302
raster multirow, 303
raster number n, 301
raster odd column, 300
raster odd number, 301
raster odd row, 300
raster reset, 300
raster right skip, 297
raster row m, 301
raster row m column n, 301
raster row skip, 297
raster rows, 294
raster valign, 298
raster width, 294

raster width center, 295
raster width flush left, 295
raster width flush right, 295
record, 131
remake, 108
remember, 197
remember as, 198
reset, 109
reset and store to box array, 405
reset box array, 402
right, 40
right skip, 84
right*, 41
righthand ratio, 123
righthand width, 122
rightlower, 42
rightrule, 35
righttitle, 41
rightupper, 41
rotate, 197
rounded corners, 49
run arara, 337
run biber, 337
run bibtex, 337
run dvips, 337
run latex, 337
run lualatex, 337
run makeindex, 337
run pdflatex, 335
run ps2pdf, 337
run system command, 335
run xelatex, 337
savedelimiter, 26
savelowerto, 24
saveto, 23
scale, 197
segmentation at break, 384
segmentation code, 142
segmentation code app, 447
segmentation code pre, 447
segmentation empty, 142
segmentation engine, 139
segmentation hidden, 155
segmentation style, 155
separator sign, 356
separator sign colon, 356
separator sign dash, 356
separator sign none, 356
shadow, 192
sharp corners, 48
sharpish corners, 49
shield externalize, 108
show bounding box, 183
shrink break goal, 382
shrink tight, 92
sidebyside, 119
sidebyside adapt, 126
sidebyside align, 120
sidebyside gap, 122
sidebyside switch, 128
size, 44
skin, 137
skin first, 137
skin first is subskin of, 144
skin last, 137
skin last is subskin of, 144
skin middle, 137
skin middle is subskin of, 144
smart shadow arc, 194
space, 58
space to, 59
space to both, 59
space to lower, 58
space to upper, 58
spartan, 252
split, 60
spread, 91
spread downwards, 91
spread inwards, 90
spread outwards, 90
spread sidewards, 91
spread upwards, 91
spread upwards*, 91
square, 58
squeezed title, 19
squeezed title*, 19
standard, 209
standard jigsaw, 210
step, 101
step and label, 101
store to box array, 403
subtitle style, 21
tabulars, 70
tabulars*, 70
tabularx, 71
tabularx*, 71
tcbimage comment, 324
tcbox raise, 99
tcbox raise base, 99
tcbox width, 100
tempfile, 99
terminator sign, 358
terminator sign colon, 359
terminator sign dash, 359
terminator sign none, 359
text above listing, 330
text above* listing, 330
text and listing, 322
text fill, 69
text height, 54
text only, 323
text outside listing, 328
text side listing, 327
text width, 34
theorem, 362
theorem full label supplement, 360
theorem label supplement, 360
theorem name, 361

theorem name and number, 361
theorem number and name, 361
theorem style, 368
tikz, 196
tikz lower, 72
tikz reset, 196
tikz upper, 72
tikznode, 73
tikznode boxed title, 168
tikznode lower, 73
tikznode upper, 73
tile, 229
title, 18
title after break, 380
title code, 143
title code app, 447
title code pre, 447
title empty, 143
title engine, 139
title filled, 27
title hidden, 156
title style, 155
title style image, 156
title style tile, 156
titlebox, 19
titlerule, 36
titlerule style, 157
toggle enlargement, 89
toggle left and right, 46
top, 42
toprule, 35
toprule at break, 383
topsep at break, 383
toptitle, 42
unbreakable, 380
underlay, 199
underlay boxed title, 200
underlay boxed title pre, 445
underlay broken, 200
underlay broken pre, 445
underlay first, 200
underlay first and middle, 200
underlay first and middle pre, 445
underlay first pre, 445
underlay last, 200
underlay last pre, 445
underlay middle, 200
underlay middle and last, 200
underlay middle and last pre, 445
underlay middle pre, 445
underlay pre, 445
underlay raised fading vignette, 284
underlay raised shading vignette, 284
underlay shade in vignette, 284
underlay unbroken, 200
underlay unbroken and first, 200
underlay unbroken and first pre, 445
underlay unbroken and last, 200
underlay unbroken and last pre, 445
underlay unbroken pre, 445
underlay vignette, 283
upperbox, 22
use height from group, 63
valign, 33
valign lower, 33
valign scale limit, 33
valign upper, 33
varwidth boxed title, 168
varwidth boxed title*, 168
varwidth upper, 73
verbatim, 449
verbatim ignore percent, 130
vfill before first, 384
visible, 22
void, 110
watermark color, 174
watermark graphics, 170
watermark graphics app, 444
watermark graphics app on, 444
watermark graphics on, 170
watermark graphics pre, 444
watermark graphics pre on, 444
watermark opacity, 172
watermark overzoom, 173
watermark shrink, 173
watermark stretch, 174
watermark text, 169
watermark text app, 443
watermark text app on, 443
watermark text on, 169
watermark text pre, 443
watermark text pre on, 443
watermark tikz, 171
watermark tikz app, 444
watermark tikz app on, 444
watermark tikz on, 171
watermark tikz pre, 444
watermark tikz pre on, 444
watermark zoom, 172
widget, 238
width, 34
/tcb/boxtitle/
xshift, 161
yshift, 161
yshift*, 161
yshifttext, 161
/tcb/doclang/
color, 499
colors, 499
counter, 499
counters, 499
environment, 499
environment content, 499
environments, 499

index, 499
key, 499
keys, 499
length, 499
lengths, 499
new, 499
pageshort, 499
path, 499
paths, 499
updated, 499
value, 499
values, 499
/tcb/external/
-, 463
!, 463
clear preamble, 470
clear preclass, 470
compiler, 469
environment, 469
environment with percent, 469
externalize, 463
force remake, 463
input source on error, 469
minipage, 469
name, 465
PassOptionsToClass, 470
PassOptionsToPackage, 470
plain, 469
preamble, 470
preamble tcbset, 470
preclass, 470
prefix, 463
runner, 463
runs, 469
safety, 469
/tcb/library/
all, 10
breakable, 9
documentation, 10
external, 10
fitting, 9
hooks, 9
listings, 9
listingsutf8, 9
magazine, 9
many, 10
minted, 9
most, 10
poster, 9
raster, 9
skins, 9
theorems, 9
vignette, 9
xparse, 10
/tcb/new/
auto counter, 111
blend into, 115
Crefname, 114
crefname, 114
list inside, 118
list type, 118
no counter, 112
number format, 113
number freestyle, 113
number within, 113
reset counter on overlays, 112
use counter, 112
use counter from, 112
use counter*, 112
/tcb/poster/
colspacing, 415
columns, 415
height, 415
prefix, 415
rows, 415
rowspacing, 415
showframe, 415
spacing, 415
width, 415
/tcb/posterloc/
above, 421
at, 422
below, 421
between, 422
column, 419
column*, 419
fixed height, 420
name, 419
row, 420
rowspan, 420
sequence, 423
span, 420
xshift, 424
yshift, 425
/tcb/posterset/
boxes, 417
coverage, 416
fontsize, 417
no coverage, 416
poster, 415
/tcb/vig/
base color, 280
color from, 280
draw method, 281
east size, 278
east style, 279
fade in, 282
fade out, 282
horizontal size, 279
inside node, 277
lower left corner, 277
lowered color, 280
north size, 278
north style, 279
outside node, 278
over node, 278
over node offset, 278
raised color, 280

scope, 280
semi fade in, 282
semi fade out, 282
size, 279
south size, 278
south style, 279
upper right corner, 277
vertical size, 279
west size, 278
west style, 280
xmax, 277
xmin, 277
ymax, 277
ymin, 277
/tikz/
fill image opacity, 267
fill image options, 267
fill image scale, 267
fill overzoom image, 263
fill overzoom image*, 263
fill overzoom picture, 263
fill plain image, 261
fill plain image*, 261
fill plain picture, 261
fill shrink image, 265
fill shrink image*, 265
fill shrink picture, 265
fill stretch image, 262
fill stretch image*, 262
fill stretch picture, 262
fill tile image, 266
fill tile image*, 266
fill tile picture, 266
fill tile picture*, 266
fill zoom image, 264
fill zoom image*, 264
fill zoom picture, 264
tcb fill frame, 158
tcb fill interior, 158
tcb fill title, 158
keys key, 499
keywords bold key, 497

label key, 101
label separator key, 359
label type key, 101
landscape value, 260
landscape* value, 260
last value, 169–171, 384
left key, 39
left value, 30, 126, 298
left skip key, 84
left* key, 39
lefthand ratio key, 123
lefthand width key, 122
leftlower key, 40
leftright skip key, 84
leftrule key, 35
lefttitle key, 40
leftupper key, 40
length key, 499
Lengths
\foolength, 481
lengths key, 499
lifted shadow key, 194
lines before break key, 380
list entry key, 102
list inside key, 118
list text key, 102
list type key, 118
listing above comment key, 330
listing above text key, 329
listing above* comment key, 330
listing above* text key, 329
listing and comment key, 326
listing and text key, 322
listing engine key, 322
listing file key, 322
listing inputencoding key, 318
listing only key, 322
listing options key, 317
listing options app key, 448
listing options pre key, 448
listing outside comment key, 329
listing outside text key, 327
listing remove caption key, 318
listing side comment key, 328
listing side text key, 327
listing style key, 317
listing utf8 key, 319
listings key, 9
listings value, 115, 322
listingsutf8 key, 9
lower left corner key, 277
lower separated key, 25
lowerbox key, 24
lowered color key, 280

magazine key, 9
many key, 10
\marg, 481
margin value, 370
margin apart value, 370
margin break value, 370
marker key, 220
math key, 364
math lower key, 364
math upper key, 364
maximum value, 56
\meta, 481
middle key, 43
middle value, 169–171, 384
middle and last value, 169–171, 384
minimal value, 44
minimum center value, 100
minimum for current equal height group key, 62
minimum for equal height group key, 62
minimum left value, 100
minimum right value, 100

minipage key, 97, 469
minipage value, 97, 291
minipage boxed title key, 167
minipage boxed title* key, 167
minted key, 9
minted value, 322
minted language key, 320
minted options key, 320
minted options app key, 448
minted options pre key, 448
minted style key, 321
most key, 10
move upwards key, 90
move upwards* key, 90

name key, 419, 465
nameref key, 102
natural height key, 53
new key, 499
\newboxarray, 402
\newtcbexternalizeenvironment, 471
\newtcbexternalizetcolorbox, 471
\NewTCBInputListing, 459
\newtcbinputlisting, 316
\NewTCBListing, 457
\newtcblisting, 314
\NewTCBox, 454
\newtcbox, 16
\NewTCBoxFit, 460
\newtcboxfit, 427
\newtcbtheorem, 352
\NewTColorBox, 452
\newtcolorbox, 15
\NewTotalTCBox, 456
\NewTotalTCBoxFit, 461
\NewTotalTColorBox, 453
nirvana key, 110
no borderline key, 183
no boxed title style key, 166
no counter key, 112
no coverage key, 416
no extras key, 385
no extras first key, 385
no extras last key, 385
no extras middle key, 385
no extras title after break key, 386
no extras unbroken key, 385
no finish key, 202
no finish first key, 202
no finish last key, 202
no finish middle key, 202
no finish unbroken key, 202
no label type key, 101
no listing options key, 317
no overlay key, 75
no process key, 335
no recording key, 131
no shadow key, 186
no underlay key, 199
no underlay boxed title key, 200
no underlay first key, 200
no underlay last key, 200
no underlay middle key, 200
no underlay unbroken key, 200
no watermark key, 171
nobeforeafter key, 81
nofloat key, 79
none value, 46, 89, 126, 299, 382, 384
noparskip key, 81
nophantom key, 101
normal value, 44, 162
north fading, 281
north value, 48, 49
north size key, 278
north style key, 279
northeast value, 48, 49
northwest value, 48, 49
notitle key, 18
notitle after break key, 380
number format key, 113
number freestyle key, 113
number within key, 113

\oarg, 481
octogon arc key, 37
off value, 437, 497
on value, 437
on line key, 99
only key, 270
opacityback key, 51
opacitybacktitle key, 51
opacityfill key, 51
opacityframe key, 51
opacitylower key, 52
opacitytext key, 52
opacitytitle key, 52
opacityupper key, 52
Option color, 500
outer arc key, 38
outside node key, 278
over node key, 278
over node offset key, 278
overlay key, 74
overlay app key, 441
overlay broken key, 75
overlay broken app key, 442
overlay broken pre key, 442
overlay first key, 75
overlay first and middle key, 75
overlay first and middle app key, 442
overlay first and middle pre key, 442
overlay first app key, 441
overlay first pre key, 441
overlay last key, 75
overlay last app key, 442
overlay last pre key, 442
overlay middle key, 75
overlay middle and last key, 75
overlay middle and last app key, 442
overlay middle and last pre key, 442

overlay middle app key, 442
overlay middle pre key, 442
overlay pre key, 441
overlay unbroken key, 75
overlay unbroken and first key, 75
overlay unbroken and first app key, 442
overlay unbroken and first pre key, 442
overlay unbroken and last key, 75
overlay unbroken and last app key, 442
overlay unbroken and last pre key, 442
overlay unbroken app key, 441
overlay unbroken pre key, 441
oversize key, 45

pad after break key, 383
pad at break key, 383
pad at break* key, 383
pad before break key, 383
pad before break* key, 383
pageshort key, 499
parbox key, 98
parfillskip restore key, 84
parskip key, 81
PassOptionsToClass key, 470
PassOptionsToPackage key, 470
path key, 499
path value, 138, 139
Path operations
    foo path (horizontal then vertical), 489
    fooop, 479
pathfirst value, 138, 139
pathfirstjigsaw value, 138
pathjigsaw value, 138
pathlast value, 138, 139
pathlastjigsaw value, 138
pathmiddle value, 138, 139
pathmiddlejigsaw value, 138
paths key, 499
pdf comment key, 325
pdf extension key, 326
\pdfpages, 259
pgf value, 497
pgfchapter value, 497
pgfsection value, 497
phantom key, 101
phantomlabel key, 101
placeholder key, 424
plain key, 469
plain value, 368
plain apart value, 369
portrait value, 260
portrait* value, 260
poster key, 9, 415
\posterbox, 418
posterboxenv environment, 418
preamble key, 470
preamble tcbset key, 470
preclass key, 470
prefix key, 415, 463
process code key, 335
\ProvideTCBInputListing, 459
\ProvideTCBListing, 457
\ProvideTCBox, 454
\ProvideTCBoxFit, 460
\ProvideTColorBox, 452
\ProvideTotalTCBox, 456
\ProvideTotalTCBoxFit, 461
\ProvideTotalTColorBox, 453

raised color key, 280
raster key, 9
raster after skip key, 296
raster before skip key, 296
raster column n key, 300
raster column skip key, 297
raster columns key, 294
raster equal height key, 299
raster equal height group key, 299
raster equal skip key, 296
raster even column key, 300
raster even number key, 301
raster even row key, 301
raster every box key, 300
raster force size key, 300
raster halign key, 298
raster height key, 296
raster left skip key, 297
raster multicolumn key, 302
raster multirow key, 303
raster number n key, 301
raster odd column key, 300
raster odd number key, 301
raster odd row key, 300
raster reset key, 300
raster right skip key, 297
raster row m key, 301
raster row m column n key, 301
raster row skip key, 297
raster rows key, 294
raster valign key, 298
raster width key, 294
raster width center key, 295
raster width flush left key, 295
raster width flush right key, 295
record key, 131
\refAux, 486
\refAuxcs, 486
\refCom, 485
\refCom*, 485
\refEnv, 485
\refEnv*, 485
\refKey, 485
\refKey*, 485
\refPathOperation, 486
\refPathOperation*, 486
remake key, 108
remember key, 197
remember as key, 198
\renewtcbexternalizeenvironment, 471

\renewtcbexternalizetcolorbox, 472
\RenewTCBInputListing, 459
\renewtcbinputlisting, 316
\RenewTCBListing, 457
\renewtcblisting, 315
\RenewTCBox, 454
\renewtcbox, 16
\RenewTCBoxFit, 460
\renewtcboxfit, 427
\renewtcbtheorem, 353
\RenewTColorBox, 452
\renewtcolorbox, 15
\RenewTotalTCBox, 456
\RenewTotalTCBoxFit, 461
\RenewTotalTColorBox, 453
reset key, 109
reset and store to box array key, 405
reset box array key, 402
reset counter on overlays key, 112
right key, 40
right value, 30, 126, 298
right skip key, 84
right* key, 41
righthand ratio key, 123
righthand width key, 122
rightlower key, 42
rightrule key, 35
righttitle key, 41
rightupper key, 41
rotate key, 197
rounded corners key, 49
row key, 420
rows key, 415
rows value, 299
rowspacing key, 415
rowspan key, 420
run arara key, 337
run biber key, 337
run bibtex key, 337
run dvips key, 337
run latex key, 337
run lualatex key, 337
run makeindex key, 337
run pdflatex key, 335
run ps2pdf key, 337
run system command key, 335
run xelatex key, 337
runner key, 463
runs key, 469

safety key, 469
savedelimiter key, 26
savelowerto key, 24
saveto key, 23
scale key, 197
scale value, 33
scale* value, 33
scope key, 280
segmentation at break key, 384
segmentation code key, 142
segmentation code app key, 447
segmentation code pre key, 447
segmentation empty key, 142
segmentation engine key, 139
segmentation hidden key, 155
segmentation style key, 155
semi east fading, 281
semi fade in key, 282
semi fade out key, 282
semi north fading, 281
semi south fading, 281
semi west fading, 281
separator sign key, 356
separator sign colon key, 356
separator sign dash key, 356
separator sign none key, 356
sequence key, 423
shadow key, 192
sharp corners key, 48
sharpish corners key, 49
shield externalize key, 108
show bounding box key, 183
showframe key, 415
shrink break goal key, 382
shrink tight key, 92
sidebyside key, 119
sidebyside adapt key, 126
sidebyside align key, 120
sidebyside gap key, 122
sidebyside switch key, 128
size key, 44, 279
skin key, 137
skin first key, 137
skin first is subskin of key, 144
skin last key, 137
skin last is subskin of key, 144
skin middle key, 137
skin middle is subskin of key, 144
Skins
    beamer, 233
    beamerfirst, 235
    beamerlast, 237
    beamermiddle, 236
    bicolor, 224
    bicolorfirst, 226
    bicolorlast, 228
    bicolormiddle, 227
    draft, 253
    empty, 242
    emptyfirst, 245
    emptylast, 247
    emptymiddle, 246
    enhanced, 211
    enhanced jigsaw, 218
    enhancedfirst, 215
    enhancedfirst jigsaw, 219
    enhancedlast, 217
    enhancedlast jigsaw, 223
    enhancedmiddle, 216

enhancedmiddle jigsaw, 220
freelance, 255
freelancefirst, 255
freelancelast, 255
freelancemiddle, 255
spartan, 252
standard, 209
standard jigsaw, 210
tile, 229
tilefirst, 230
tilelast, 232
tilemiddle, 231
widget, 238
widgetfirst, 239
widgetlast, 241
widgetmiddle, 240
skins key, 9
small value, 44
smart shadow arc key, 194
south fading, 281
south value, 48, 49
south size key, 278
south style key, 279
southeast value, 48, 49
southwest value, 48, 49
space key, 58
space to key, 59
space to both key, 59
space to lower key, 58
space to upper key, 58
spacing key, 415
span key, 420
spartan key, 252
spartan Skin, 252
spartan value, 138, 139
split key, 60
spread key, 91
spread downwards key, 91
spread inwards key, 90
spread outwards key, 90
spread sidewards key, 91
spread upwards key, 91
spread upwards* key, 91
square key, 58
squeeze value, 435
squeezed title key, 19
squeezed title* key, 19
standard key, 209
standard Skin, 209
standard value, 138, 139, 162, 368
standard jigsaw key, 210
standard jigsaw Skin, 210
step key, 101
step and label key, 101
store to box array key, 403
subtitle style key, 21

tables value, 115
tabulars key, 70
tabulars* key, 70
tabularx key, 71
tabularx* key, 71
tcb fill frame key, 158
tcb fill interior key, 158
tcb fill title key, 158
\tcbbreak, 391
tcbclipframe environment, 176
tcbclipinterior environment, 178
tcbcliptitle environment, 178
tcbcolback color, 149
tcbcolbacklower color, 149
tcbcolbacktitle color, 149
tcbcolframe color, 149
tcbcollower color, 149
tcbcoltitle color, 149
tcbcolupper color, 149
\tcbcontinuedraftmode, 207
\tcbcounter, 111
\tcbdocmarginnote, 487
\tcbdocnew, 487
\tcbdocupdated, 487
tcbexternal environment, 464
\tcbEXTERNALIZE, 463
\tcbfitdim, 428
\tcbfitsteps, 429
\tcbfontsize, 428
\tcbheightfromgroup, 63
\tcbheightspace, 150
\tcbhighmath, 354
\tcbhypernode, 269
\tcbifexternal, 470
\tcbiffileprocess, 472
\tcbifoddpage, 106
\tcbifoddpageoroneside, 106
tcbimage comment key, 324
\tcbincludegraphics, 256
\tcbincludepdf, 258
\tcbinputlisting, 313
\tcbinputrecords, 131
\tcbinterruptdraftmode, 207
tcbinvclipframe environment, 177
\tcbitem, 291
tcbitemize environment, 291
\tcbline, 214
\tcbline*, 214
tcblisting environment, 311
\tcblistof, 118
\tcblower, 12
\tcbmakedocSubKey, 484
\tcbmakedocSubKeys, 484
\tcbmaketheorem, 353
tcboutputlisting environment, 313
\tcbox, 14
tcbox raise key, 99
tcbox raise base key, 99
tcbox width key, 100
tcboxeditemize environment, 293
tcboxedraster environment, 292
\tcboxedtitleheight, 161

\tcboxedtitlewidth, 161
\tcboxfit, 426
\tcboxmath, 354
\tcboxverb, 456
\tcbpatcharcangular, 268
\tcbpatcharcround, 268
tcbposter environment, 413
\tcbpostercolspacing, 414
\tcbpostercolumns, 414
\tcbpostercolwidth, 414
\tcbposterheight, 414
\tcbposterrowheight, 414
\tcbposterrows, 414
\tcbposterrowspacing, 414
\tcbposterset, 414
\tcbposterwidth, 414
tcbraster environment, 290
\tcbrecord, 131
\tcbsegmentstate, 151
\tcbset, 13
\tcbsetforeverylayer, 13
\tcbsetmacrotoheightofnode, 269
\tcbsetmacrotowidthofnode, 269
\tcbsetmanagedlayers, 95
\tcbsettoheightofnode, 269
\tcbsettowidthofnode, 269
\tcbsidebyside, 125
\tcbstartdraftmode, 207
\tcbstartrecording, 131
\tcbstopdraftmode, 207
\tcbstoprecording, 131
\tcbsubskin, 144
\tcbsubtitle, 21
\tcbtextheight, 151
\tcbtextwidth, 150
\tcbtitle, 20
\tcbtitletext, 20
\tcbuselibrary, 9
\tcbuselistinglisting, 313
\tcbuselistingtext, 313
\tcbusetemp, 129
\tcbusetemplisting, 313
tcbverbatimwrite environment, 129
\tcbvignette, 276
tcbwritetemp environment, 129
tcolorbox environment, 12
\tcolorboxenvironment, 17
tempfile key, 99
terminator sign key, 358
terminator sign colon key, 359
terminator sign dash key, 359
terminator sign none key, 359
text above listing key, 330
text above* listing key, 330
text and listing key, 322
text fill key, 69
text height key, 54
text only key, 323
text outside listing key, 328
text side listing key, 327
text width key, 34
theorem key, 362
theorem full label supplement key, 360
theorem label supplement key, 360
theorem name key, 361
theorem name and number key, 361
theorem number and name key, 361
theorem style key, 368
theorems key, 9
\thetcbcounter, 111, 112
\thetcbrasternum, 290, 302
\thetcolorboxnumber, 107
\thetcolorboxpage, 107
tight value, 44
tikz key, 196
tikz lower key, 72
tikz reset key, 196
tikz upper key, 72
tikznode key, 73
tikznode boxed title key, 168
tikznode lower key, 73
tikznode upper key, 73
tile key, 229
tile Skin, 229
tilefirst Skin, 230
tilelast Skin, 232
tilemiddle Skin, 231
title key, 18
title value, 44, 162
title after break key, 380
title code key, 143
title code app key, 447
title code pre key, 447
title empty key, 143
title engine key, 139
title filled key, 27
title hidden key, 156
title style key, 155
title style image key, 156
title style tile key, 156
titlebox key, 19
titlerule key, 36
titlerule style key, 157
toggle enlargement key, 89
toggle left and right key, 46
top key, 42
top value, 33, 82, 120, 298
top seam value, 120
toprule key, 35
toprule at break key, 383
topsep at break key, 383
toptitle key, 42
true value, 84, 379

unbreakable key, 380
unbroken value, 169–171
unbroken and first value, 169–171
underlay key, 199
underlay boxed title key, 200

underlay boxed title pre key, 445
underlay broken key, 200
underlay broken pre key, 445
underlay first key, 200
underlay first and middle key, 200
underlay first and middle pre key, 445
underlay first pre key, 445
underlay last key, 200
underlay last pre key, 445
underlay middle key, 200
underlay middle and last key, 200
underlay middle and last pre key, 445
underlay middle pre key, 445
underlay pre key, 445
underlay raised fading vignette key, 284
underlay raised shading vignette key, 284
underlay shade in vignette key, 284
underlay unbroken key, 200
underlay unbroken and first key, 200
underlay unbroken and first pre key, 445
underlay unbroken and last key, 200
underlay unbroken and last pre key, 445
underlay unbroken pre key, 445
underlay vignette key, 283
unlimited value, 378, 379
updated key, 499
uphill value, 48, 49
upper right corner key, 277
upperbox key, 22
use counter key, 112
use counter from key, 112
use counter* key, 112
use height from group key, 63
\useboxarray, 405
\usetcboxarray, 406

valign key, 33
valign lower key, 33
valign scale limit key, 33
valign upper key, 33
value key, 499
Values
0, 151
1, 151
2, 151
all, 48, 49, 299, 382, 384
areasize, 435
areasize*, 435
as-is, 260
auto, 100
auto limited, 100
base, 82
baselineskip, 382
both, 126
bottom, 33, 82, 120, 298
bottom seam, 120
break, 369
broken, 169–171
center, 30, 33, 82, 120, 298
center seam, 120
change, 369
change apart, 369
change break, 369
change standard, 368
clipped, 281
colon, 116
colon hang, 116
copy, 162
dash, 116
dash hang, 116
direct, 281
doc, 497
downhill, 48, 49
east, 48, 49
empty, 138, 139
evenpage, 46, 89
false, 81, 84, 300, 379
fbox, 44
figures, 115
final, 437
first, 169–171, 384
first and middle, 169, 384
fitbox, 97
flush center, 30, 32, 33
flush left, 30, 32, 33
flush right, 30, 32, 33
fontsize, 435
fontsize*, 435
forced, 46, 89
forced center, 100
forced left, 100
forced right, 100
freelance, 138, 139
hbox, 97
hybrid, 435
hybrid*, 435
ignored, 24
invisible, 19, 22, 24
justify, 30
landscape, 260
landscape*, 260
last, 169–171, 384
left, 30, 126, 298
listings, 115, 322
margin, 370
margin apart, 370
margin break, 370
maximum, 56
middle, 169–171, 384
middle and last, 169–171, 384
minimal, 44
minimum center, 100
minimum left, 100
minimum right, 100
minipage, 97, 291
minted, 322
none, 46, 89, 126, 299, 382, 384
normal, 44, 162
north, 48, 49

northeast, 48, 49
northwest, 48, 49
off, 437, 497
on, 437
path, 138, 139
pathfirst, 138, 139
pathfirstjigsaw, 138
pathjigsaw, 138
pathlast, 138, 139
pathlastjigsaw, 138
pathmiddle, 138, 139
pathmiddlejigsaw, 138
pgf, 497
pgfchapter, 497
pgfsection, 497
plain, 368
plain apart, 369
portrait, 260
portrait*, 260
right, 30, 126, 298
rows, 299
scale, 33
scale*, 33
small, 44
south, 48, 49
southeast, 48, 49
southwest, 48, 49
spartan, 138, 139
squeeze, 435
standard, 138, 139, 162, 368
tables, 115
tight, 44
title, 44, 162
top, 33, 82, 120, 298
top seam, 120
true, 84, 379
unbroken, 169–171
unbroken and first, 169–171
unlimited, 378, 379
uphill, 48, 49
visible, 19, 22, 24
west, 48, 49
values key, 499
varwidth boxed title key, 168
varwidth boxed title* key, 168
varwidth upper key, 73
verbatim key, 449
verbatim ignore percent key, 130
vertical size key, 279
vfill before first key, 384
vignette key, 9
visible key, 22
visible value, 19, 22, 24
void key, 110

watermark color key, 174
watermark graphics key, 170
watermark graphics app key, 444
watermark graphics app on key, 444
watermark graphics on key, 170
watermark graphics pre key, 444
watermark graphics pre on key, 444
watermark opacity key, 172
watermark overzoom key, 173
watermark shrink key, 173
watermark stretch key, 174
watermark text key, 169
watermark text app key, 443
watermark text app on key, 443
watermark text on key, 169
watermark text pre key, 443
watermark text pre on key, 443
watermark tikz key, 171
watermark tikz app key, 444
watermark tikz app on key, 444
watermark tikz on key, 171
watermark tikz pre key, 444
watermark tikz pre on key, 444
watermark zoom key, 172
west fading, 281
west value, 48, 49
west size key, 278
west style key, 280
widget key, 238
widget Skin, 238
widgetfirst Skin, 239
widgetlast Skin, 241
widgetmiddle Skin, 240
width key, 34, 415

xmax key, 277
xmin key, 277
xparse key, 10
xshift key, 161, 424

ymax key, 277
ymin key, 277
yshift key, 161, 425
yshift* key, 161
yshifttext key, 161