

Lwarp

L^AT_EX HTML5

The lwarp package

L^AT_EX to HTML

v0.893 — 2020/11/26

© 2016–2020 Brian Dunn
bd@BDTechConcepts.com

Abstract

The `lwarp` package converts L^AT_EX to HTML by using L^AT_EX to process the user's document and directly generate HTML tags. External utility programs are only used for the final conversion of text and images. Math may be represented by SVG images or MATHJAX. More than 500 L^AT_EX packages and classes are supported, of which more than 90 also support MATHJAX.

Documents may be produced by DVI or PDF L^AT_EX, LuaL^AT_EX, XeL^AT_EX; by several CJK engines, classes, and packages; or by customized systems such as `perltext` and `pythontex`. A `texlua` script automates compilation, index, glossary, and batch image processing, and also supports `latexmk`. Configuration is semi-automatic at the first manual compile. Support files are self-generated. Print and HTML versions of each document may coexist.

Assistance is provided for HTML import into EPUB conversion software and word processors.

Requirements include the commonly-available POPPLER utilities (included with M^IK_TE_X) and PERL. Detailed installation instructions are included for each of the major operating systems and T_EX distributions.

A quick-start tutorial is provided, as well as extensive documentation for special cases, a general index, and a troubleshooting index. Automatic error testing is provided for configuration files, package load order, and image generation.

SVG math and many other generated images include L^AT_EX expressions in the `alt` tags. MATHJAX may be used with advanced equation numbering under the direct control of `lwarp`.

Complicated tables are supported, which copy/paste well into LIBREOffice WRITER.

Supported classes and packages include `memoir` and `koma-script`, `cleveref`, `caption`, `mdframed`, `siunitx`, and many popular packages for tabulars, floats, graphics, theorems, the title page, bibliography, indexing, footnotes, and editorial work, as well as a number of CJK-related classes and packages.

T_EX is a self-modifying tokenized macro-expansion language. Since `lwarp` is written directly in L^AT_EX, it is able to interpret the document's meaning at a deeper level than external conversions which merely approximate T_EX. HTML5 and CSS3 are leveraged to provide advanced features such as `booktabs trim`, `multicolumns`, `side-by-side minipages`, and JAVASCRIPT-free navigation.

For a list of supported features, see [table 2: Supported packages and features](#).

To update existing projects, see [section 1: Updates](#).

Lwarp is still in development. Changes are likely.

License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in <http://www.latex-project.org/lppl.txt> and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

Support T_EX development

T_EX and related projects:

- are mostly open-sourced and a volunteer effort;
- benefit students, academics, scientists, engineers, and businesses;
- help drive education, public and private research, and commercial activity;
- are used in the fields of mathematics, science, engineering, and humanities;
- are international in reach;
- span decades of development;
- are enduring — many older packages are still actively used and maintained;
- are largely backwards compatible;
- are portable across all the major computing platforms;
- are usable even on older computers and away from internet access;
- are continuing to maintain relevance with modern improvements;
- require no yearly subscription fees;
- and are supported by an active community of knowledgeable volunteers.

Please consider helping by joining and/or contributing to the T_EX Users Group, a United States 501(c)(3) tax-exempt charitable organization. Contributions are accepted by credit card, check, or Pay Pal, via the United Way, or by USA or European bank transfer. Membership in TUG supports the development of T_EXLive, the major T_EX distribution.

Donations may be directed towards individual projects:

TUG Bursary Fund: Assistance for attending annual TUG meetings.

CTAN: The Comprehensive T_EX Archive Network — Central storage for T_EX.

TeX Development Fund: Support for specific projects.

EduTeX: Teaching and using T_EX in schools and universities.

GUST e-foundry fonts: Enhanced for math and additional language groups.

LaTeX Project: Modernizing the L^AT_EX core.

Libre Font Fund: Fonts, tools (FontForge), and distribution (the Open Font Library).

LuaTeX: Combining the pdfT_EX engine and the Lua language.

MetaPost: Postscript graphics.

MacTeX: T_EX for Mac.

PDF Accessibility: Modern PDF standards.

Other: Additional projects may be specified.

To make a contribution: <https://www.tug.org/donate.html>

For country-specific T_EX users groups: <http://tug.org/usergroups.html>

For users of MiK_TE_X: <https://miktex.org/donations.html>

Contents

Support T_EX development	2
List of Figures	43
List of Tables	43
1 Updates	44
2 Introduction	63
2.1 Typesetting conventions	65
2.2 Supported packages and features	66
3 Alternatives	73
3.1 internet class	73
3.2 T _E X4HT	73
3.3 Translators	73
3.4 ASCIIDOC and ASCIIDOCTOR	74
3.4.1 ASCIIDOCTOR- \LaTeX	74
3.5 PANDOC	74
3.6 Word processors	74
3.7 Commercial systems	74
3.8 Comparisons	74
4 Installation	76
4.1 Installing the lwarp package	78
4.2 Installing the <i>lwarpmk</i> utility	79
4.2.1 Using a local copy of <i>lwarpmk</i>	81
4.3 Installing additional utilities	81
5 Tutorial	83
5.1 Starting a new project	83
5.2 Compiling the print version with <i>lwarpmk</i>	87
5.3 Compiling the HTML version with <i>lwarpmk</i>	88
5.4 Generating the SVG images	89

5.5	Using <code>MATHJAX</code> for math	90
5.6	Changing the <code>CSS</code> style	91
5.7	Customizing the <code>HTML</code> output	91
5.8	Using <code>latexmk</code>	92
5.9	Using <code>X_YL^AT_EX</code> or <code>Lua^AT_EX</code>	93
5.10	Using <code>DVI L^AT_EX</code>	93
5.11	Using a glossary	94
5.11.1	gloss package	94
5.11.2	glossaries package	94
5.12	Cleaning auxiliary files	95
5.13	Cleaning auxiliary and output files.	95
5.14	Cleaning the images from the <code><project>-images</code> directory	95
5.15	Converting <code>PDF</code> or <code>EPS</code> images to <code>SVG</code>	95
5.16	Creating <code>HTML</code> from an incomplete compile	95
5.17	Processing multiple projects in the same directory	95
5.18	Using the <i>make</i> utility	96
5.19	What next?	97
6	Converting an existing document	98
7	Additional details	99
7.1	Localization.	99
7.2	Accessibility.	99
7.3	Shell escape.	101
7.4	Font and <code>UTF-8</code> support	101
7.4.1	Indexes, glossaries, and encoding	103
7.5	lwarp package loading and options.	104
7.6	Customizing the <code>HTML</code> output	110
7.6.1	Example <code>HTML</code> file naming	116
7.7	Customizing the <code>CSS</code>	117
7.8	Assigning <code>CSS</code> classes and styles	118

7.9	Selecting the operating system	118
7.10	Selecting actions for print, HTML, or MATHJAX output	119
7.11	Commands to be placed into the warpprint environment	120
7.12	Title page	120
7.13	HTML page meta descriptions	121
7.14	HTML homepage meta title	122
7.15	HTML page meta author	122
8	Special cases and limitations	123
8.1	Things to avoid	123
8.1.1	Invalid HTML	124
8.2	Formatting	124
8.2.1	Text formatting	124
8.2.2	Small caps	124
8.2.3	Horizontal and vertical space and rules	124
8.2.4	Text alignment	125
8.2.5	Accents.	125
8.2.6	textcomp package	125
8.2.7	Superscripts and other non-math uses of math mode	125
8.2.8	Empty \item followed by a new line of text or a nested list:	125
8.2.9	Filenames and URLs in lists or footnotes	126
8.2.10	resize package	126
8.3	Boxes and minipages	126
8.3.1	Marginpars	126
8.3.2	Save Boxes	126
8.3.3	Minipages.	126
8.3.4	Side-by-side minipages	127
8.3.5	Framed minipages and other environments	127
8.3.6	fancybox package	129
8.3.7	mdframed package	130

8.3.8	tcolorbox package	130
8.4	Section names	131
8.5	Cross-references	132
8.5.1	Page references	132
8.5.2	cleveref and varioref packages	132
8.5.3	Hyperlinks, hyperref, and url	133
8.5.4	Footnotes, endnotes, and page notes	133
8.5.5	xr, xr-hyper, and xcite packages	135
8.6	Front and back matter	135
8.6.1	Custom classes with multiple authors and affiliations	135
8.6.2	Starred chapters and sections	135
8.6.3	abstract package	136
8.6.4	titling and authblk	136
8.6.5	tocloft package	136
8.6.6	appendix package	136
8.6.7	pagenote package	136
8.6.8	endnotes package	137
8.6.9	<i>BibTeX</i>	137
8.6.10	xcite package	137
8.6.11	gloss package	137
8.6.12	glossaries package	138
8.6.13	nomencl package	139
8.6.14	Indexing overview	139
8.6.15	Indexing with <i>makeidx</i>, <i>makeindex</i>, <i>xindy</i>, <i>xindex</i>, <i>gindex</i>	139
8.6.16	Indexing with <i>index</i>	141
8.6.17	Indexing with <i>splitidx</i>	142
8.6.18	Indexing with <i>imakeidx</i>	144
8.6.19	Indexes with <i>memoir</i>	147
8.6.20	Using a custom <i>makeindex</i> style file	150

8.6.21	Using a custom <i>xindy</i> style file.	151
8.6.22	Using a custom <i>xindex</i> style file	152
8.6.23	Additional indexing limitations	152
8.6.24	Index positions, toc, tocbind	153
8.7	Math	154
8.7.1	Math in section names	154
8.7.2	Rendering tradeoffs	154
8.7.3	svg option	155
8.7.4	MATHJAX option	155
8.7.5	Customizing MATHJAX	156
8.7.6	MATHJAX limitations	157
8.7.7	Catcode changes	158
8.7.8	Complicated inline math objects.	158
8.7.9	Complicated display math objects	159
8.7.10	ntheorem package.	159
8.7.11	mathtools package.	160
8.7.12	siunitx package	160
8.7.13	units and nicefrac packages.	161
8.7.14	physics package.	161
8.8	Graphics	161
8.8.1	tikz package	163
8.8.2	grffile package	163
8.8.3	color package	163
8.8.4	xcolor package	163
8.8.5	epstopdf package	164
8.8.6	pstricks package.	164
8.8.7	pdftricks package	164
8.8.8	psfrag package	164
8.8.9	pstool package	164

8.8.10	asymptote package	165
8.8.11	overpic package	165
8.8.12	Multimedia packages	165
8.9	Tabbing	166
8.10	Tabular	166
8.10.1	tabular environment.	166
8.10.2	multirow package	169
8.10.3	longtable package	169
8.10.4	threeparttablex package	170
8.10.5	supertabular and xtab packages	171
8.10.6	colortbl package	171
8.10.7	ctable package	171
8.10.8	bigdelim package	171
8.11	Floats	172
8.11.1	Float contents alignment	172
8.11.2	float, trivfloat, and/or algorithmicx together	172
8.11.3	caption and subcaption packages.	172
8.11.4	subfig package	173
8.11.5	floatrow package	173
8.11.6	keyfloat package	173
8.12	KOMA-SCRIPT classes.	173
8.13	MEMOIR class	174
8.14	International languages.	175
8.15	Miscellaneous packages	176
8.15.1	verse and memoir	176
8.15.2	newclude package	176
8.15.3	babel package	176
8.15.4	polyglossia package	177
8.15.5	todonotes and luatodonotes packages	177

8.15.6	fixme	177
8.15.7	acro package	178
8.15.8	chemfig package	178
8.15.9	chemformula package	178
8.15.10	mhchem package	178
8.15.11	xparse package	178
8.15.12	kotex package	178
9	Compiling using custom shell commands	179
9.1	Command options	179
9.2	Literal character macros	179
9.3	latexmk	180
9.4	perltex package	181
9.5	pythontex package	181
9.6	Other packages	181
9.7	make program	182
9.8	UTF-8 locale	182
10	EPUB conversion	183
11	Word-processor conversion	185
11.1	Activating word-processor conversion	185
11.2	Additional modifications	186
11.3	Recommendations	188
11.4	Limitations	189
12	Modifying lwarp	190
12.1	Creating a development system	190
12.2	Modifying a package for lwarp	192
12.2.1	Adding a package to the lwarp.dtx file	193
12.3	Modifying a class for lwarp	193
12.4	Testing lwarp	193
12.5	Modifying lwarpmk	194

13	Troubleshooting	195
13.1	lwarp package error conditions and warnings	195
13.1.1	Configuration file <code>lwarpmk.conf</code>	195
13.1.2	Image generation with <code>lwarpmk limages</code>	195
13.1.3	Default bitmapped font	196
13.1.4	Packages	196
13.1.5	Compiling	196
13.2	Using the lwarp package	197
13.2.1	Debug tracing output	201
13.3	Compiling the <code>lwarp.dtx</code> file	201
14	Trademarks	202
1	lwarp.sty	203
15	Implementation	203
16	Section depths and HTML headings	204
17	Source code	205
18	Detecting the T_EX engine — <i>pdf_latex, lualatex, xelatex</i>	206
19	Early package requirements	206
20	Package load order	206
20.1	Tests of package load order	207
20.2	Error for disallowed packages and classes loaded before <code>lwarp</code>	209
20.3	Enforcing package loading after <code>lwarp</code>	210
21	MD5 hashing	220
22	pdf_lAT_EX T₁ and UTF-8 encoding	221
23	Unicode input characters	222
24	Avoid a bitmapped font	222
25	Upright quotes	223
26	Miscellaneous tools	223
26.1	Variables	223
26.2	Lengths and units	223

26.3	Counters	224
26.4	Patching	224
26.5	Chinese text isolation	224
26.6	Inserting vertical space	225
26.7	Argument selection	225
26.8	Inside boxes.	225
26.9	Global boxes	226
26.10	Converting a macro name to a cs name	226
26.11	Title case.	227
26.12	LetLtxMacros	227
26.13	Absorbing a star	227
27	Operating-System portability.	228
27.1	Literal characters	228
27.2	Common portability code	229
27.3	UNIX, LINUX, and MAC OS	229
27.4	MS-WINDOWS	229
28	Package options.	230
28.1	Additional options support	234
28.2	Conditional compilation	237
29	Required packages.	239
30	Loading packages	245
31	File handles	251
32	Include a file	251
33	Copying a file.	252
34	Debugging messages	253
35	Defining print and HTML versions of macros and environments	254
36	HTML-conversion output modifications	259
36.1	User-level controls	259
36.2	Heading adjustments	261

37	Remembering original formatting macros	262
38	Accents	264
39	Configuration files	266
39.1	Decide whether to generate configuration files	266
39.2	<code><project>_html.tex</code>	266
39.3	<i>lwarpmk</i> configuration files	266
39.3.1	Helper macros	267
39.3.2	<code>lwarpmk.conf</code>	273
39.3.3	<code><project>.lwarpmkconf.</code>	273
39.4	<code>lwarp.css</code>	273
39.5	<code>lwarp_sagebrush.css</code>	305
39.6	<code>lwarp_formal.css</code>	309
39.7	<code>sample_project.css</code>	313
39.8	<code>lwarp.ist</code>	314
39.9	<code>lwarp.xdy</code>	314
39.10	<code>lwarp_one_limage.cmd.</code>	315
39.11	<code>lwarp_mathjax.txt</code>	316
39.12	<code>lwarpmk.lua</code> — <i>lwarpmk</i> option.	319
40	Stacks	337
40.1	Assigning depths	338
40.2	Closing actions.	338
40.3	Closing depths.	339
40.4	Pushing and popping the stack	339
41	Data arrays	341
42	Localizing catcodes	341
43	Localizing dynamic math	342
44	HTML entities.	343
45	HTML filename generation	344
46	Homepage link	347

47	Previous/next navigation links	348
48	\LWRPrintStack diagnostic tool	350
49	Closing stack levels	350
50	PDF pages and styles	351
51	HTML tags, spans, divs, elements.	352
51.1	Mapping L ^A T _E X sections to HTML sections	352
51.2	Babel-French tag modifications	353
51.3	HTML output formatting	354
51.4	HTML tags	354
51.5	Block tags and comments	357
51.6	Div class and element class	358
51.7	Single-line elements	359
51.8	HTML5 semantic elements	360
51.9	High-level block and inline classes	360
51.10	Closing HTML tags	362
52	Paragraph handling	363
53	Paragraph start/stop handling	366
54	Indentfirst.	369
55	Page headers and footers	369
56	css	370
57	MathJax script	370
58	Title, HTML meta author, HTML meta description.	371
59	Footnotes	372
59.1	Regular page footnotes	373
59.2	Minipage footnotes	373
59.3	Titlepage thanks	373
59.4	Regular page footnote implementation	373
59.5	Minipage footnote implementation	376
59.6	Printing pending footnotes	377

60	Marginpars	378
61	Splitting HTML files	380
61.1	Sanitizing expressions for HTML	385
61.2	Customizing MATHJAX	388
62	Sectioning	395
62.1	User-level starred section commands	395
62.2	Book class commands	396
62.3	Sectioning support macros	397
62.4	Pre- and post- sectioning names	404
62.5	\section and friends	405
63	Starting a new file	406
64	Starting HTML output	410
65	Ending HTML output	413
66	Nullifying foreground/background hooks	416
67	Title page	416
67.1	Setting the title, etc.	417
67.2	\if@titlepage.	418
67.3	Changes for \affiliation	418
67.4	Printing the thanks	419
67.5	Printing the title, etc. in HTML	419
67.6	Printing the title, etc. in print form.	420
67.7	\maketitle for HTML output	421
67.8	\published and \subtitle	424
68	Abstract	425
69	Quote and verse	426
69.1	Attributions	426
69.2	Quotes, quotations	426
69.3	Verse	427
69.3.1	L ^A T _E X core verse environment.	427

	69.3.2	verse and memoir	428
70		Verbatim and tabbing	428
71		Theorems	432
72		Lists	432
	72.1	List environment	433
	72.2	Itemize	437
	72.3	Enumerate	437
	72.4	Description	437
	72.5	Patching the lists	438
73		Tabular	439
	73.1	Limitations	439
	73.2	Temporary package-related macros	442
	73.2.1	arydshn	442
	73.3	Token lookahead	442
	73.4	Tabular variables	443
	73.4.1	Multicolumn variables	446
	73.4.2	Longtable variables	446
	73.4.3	Midrule variables	447
	73.5	Handling &, @, !, and bar	447
	73.5.1	Handling &	449
	73.5.2	Filling an unfinished row	449
	73.6	Handling \	451
	73.7	Looking ahead in the column specifications	452
	73.8	Parsing @, >, <, !, bar columns	453
	73.9	Parsing 'l', 'c', or 'r' columns	456
	73.10	Parsing 'p', 'm', or 'b' columns	457
	73.11	Parsing 'w' columns	457
	73.12	Parsing '*' columns	458
	73.13	Parsing 'D' columns	458

73.14	Expanding the star column specifications	458
73.15	Parsing the column specifications	460
73.16	colortbl and xcolor tabular color support.	464
73.17	Starting a new row	466
73.18	Printing vertical bar tags	466
73.19	Printing @ or ! tags	467
73.20	Data opening tag	468
73.21	Midrules	470
73.22	Cell colors	475
73.23	Multicolumns	479
73.23.1	Parsing multicolumns	479
73.23.2	Multicolumn factored code.	482
73.23.3	Multicolumn	485
73.23.4	Longtable captions	486
73.23.5	Counting HTML tabular columns	488
73.24	Multirow if not loaded	489
73.25	Multicolumnrow	490
73.26	Utility macros inside a table	491
73.27	Special-case tabular markers	491
73.28	Checking for a new table cell.	492
73.29	\mrowcell	495
73.30	\mcolrowcell	495
73.31	HTML tabular environment	496
74	Cross-references	502
74.1	Setup	503
74.2	New lwarp labels.	503
74.3	Labels	506
74.4	References	508
74.5	Hyper-references	511

75	Floats	515
75.1	Float environment	515
75.2	Float tracking	518
75.3	Caption inside a float environment	519
75.4	Caption and LOF linking and tracking	520
76	Table of Contents, LOF, LOT	523
76.1	Reading and printing the toc	524
76.2	High-level toc commands	527
76.3	Side toc	527
76.4	Low-level toc line formatting	529
77	Index and glossary	532
78	Bibliography presentation	540
79	Restoring original formatting	541
80	Nullifying filename formatting	543
81	Math	546
81.1	Limitations	546
81.2	HTML alt tag names	547
81.3	Inline and display math	548
81.4	MATHJAX support	561
81.5	Equation environment	564
81.6	<code>\displaymathnormal</code> and <code>\displaymathother</code>	567
81.7	AMS Math environments	569
81.7.1	Support macros	569
81.7.2	Environment patches	569
82	Lateximages	572
82.1	Description	572
82.2	Support counters and macros	573
82.3	Font size	574
82.4	Equation numbers	574

82.5	HTML alt tags	575
82.6	lateximage environment	576
83	center, flushleft, flushright	582
84	Preloaded packages	584
85	siunitx	586
86	Graphics print-mode modifications	587
86.1	General limitations	587
86.2	Print-mode modifications	589
87	xcolor boxes	589
88	chemmacros environments.	592
89	cleveref	593
90	Preexisting label and reference definitions	593
91	picture environment.	594
92	Minipages and Boxes	594
92.1	Computed lengths	595
92.2	Virtual page size	595
92.3	Footnote handling	596
92.4	Minipage handling	596
92.5	\parbox, \mbox, \makebox, \framebox, \fbox, \raisebox	600
93	Direct formatting	605
94	Skips, spaces, font sizes	615
95	\phantomsection	624
96	\LaTeX and other logos	624
97	Starting and stopping lwarp	628
98	Loading everyshi patches	628
99	Loading textcomp patches	628
100	Loading amsmath, amsthm patches, centernot.	628
101	Loading KOMA-SCRIPT class patches	629
102	Loading MEMOIR class patches	629

103	ut* class patches	629
104	CTEX patches	631
105	kotexutf patches	631
106	babel and polyglossia warnings	632
107	MATHJAX warnings	633
2	lwarp-2in1.sty	636
3	lwarp-2up.sty	636
4	lwarp-a4.sty	636
5	lwarp-a4wide.sty	637
6	lwarp-a5comb.sty	637
7	lwarp-abstract.sty	637
8	lwarp-academicons.sty	639
9	lwarp-accents.sty	640
10	lwarp-accessibility.sty	641
11	lwarp-accsupp.sty	642
12	lwarp-acro.sty	642
13	lwarp-acronym.sty	645
14	lwarp-adjmulticol.sty	646
15	lwarp-addlines.sty	647
16	lwarp-afterpage.sty	647
17	lwarp-algorithm2e.sty	647
18	lwarp-algorithmicx.sty	651
19	lwarp-alltt.sty	652
20	lwarp-amsmath.sty	653
21	lwarp-amsthm.sty	656
22	lwarp-anonchap.sty	661
23	lwarp-anysize.sty	661

24	lwarp-appendix.sty	661
25	lwarp-ar.sty	662
26	lwarp-arabicfront.sty	664
27	lwarp-array.sty	664
28	lwarp-arydshln.sty	664
29	lwarp-asymptote.sty	666
30	lwarp-atbegshi.sty	667
31	lwarp-attachfile.sty	668
32	lwarp-attachfile2.sty	669
33	lwarp-authblk.sty	671
34	lwarp-autobreak.sty	672
35	lwarp-autonum.sty	673
36	lwarp-awesomebox.sty	674
37	lwarp-axessibility.sty	675
38	lwarp-axodraw2.sty	676
39	lwarp-backnaur.sty	676
40	lwarp-backref.sty	676
41	lwarp-balance.sty	677
42	lwarp-bbding.sty	677
43	lwarp-biblatex.sty	682
44	lwarp-bibunits.sty	686
45	lwarp-bigdelim.sty	686
46	lwarp-bigfoot.sty	687
47	lwarp-bigstrut.sty	688
48	lwarp-bitpattern.sty	688
49	lwarp-blowup.sty	689
50	lwarp-bm.sty	689

51	lwarp-booklet.sty	689
52	lwarp-bookmark.sty	690
53	lwarp-booktabs.sty	690
54	lwarp-bophook.sty	692
55	lwarp-bounddvi.sty	693
56	lwarp-boxedminipage.sty	693
57	lwarp-boxedminipage2e.sty	693
58	lwarp-braket.sty	694
59	lwarp-breakurl.sty	694
60	lwarp-breqn.sty	694
61	lwarp-bsheaders.sty	696
62	lwarp-bussproofs.sty	696
63	lwarp-bxpapersize.sty	697
64	lwarp-bytefield.sty	697
65	lwarp-cancel.sty	697
66	lwarp-caniclayout.sty	698
67	lwarp-caption.sty	699
68	lwarp-caption3.sty	701
69	lwarp-cases.sty	703
70	lwarp-centernot.sty	704
71	lwarp-changebar.sty	704
72	lwarp-changelayout.sty	705
73	lwarp-changepage.sty	705
74	lwarp-changes.sty	706
75	lwarp-chappg.sty	708
76	lwarp-chapterbib.sty	709
77	lwarp-chemfig.sty	709

78	lwarp-chemformula.sty	711
79	lwarp-chemgreek.sty	716
80	lwarp-chemmacros.sty	717
186	chemmacros	717
186.1	Changes to the user's document.	717
186.2	Code	717
186.3	Loading modules	717
186.4	New environments	718
186.5	Acid-base	718
186.6	Charges	720
186.7	Nomenclature	720
186.8	Particles	722
186.9	Phases.	723
186.10	Mechanisms	724
186.11	Newman	726
186.12	Orbital	726
186.13	Reactions	727
186.14	Redox	728
186.15	Scheme	728
186.16	Spectroscopy	729
186.17	Thermodynamics	733
81	lwarp-chemnum.sty	735
82	lwarp-chkfloat.sty	736
83	lwarp-chngpage.sty	736
84	lwarp-cite.sty	736
85	lwarp-citeref.sty	737
86	lwarp-CJK.sty	737
87	lwarp-CJKutf8.sty	737

88	lwarp-cleveref.sty	738
89	lwarp-clrdblpg.sty	741
90	lwarp-cmbright.sty	741
91	lwarp-cmdtrack.sty	742
92	lwarp-colonequals.sty	742
93	lwarp-color.sty	743
94	lwarp-colortbl.sty	743
95	lwarp-continue.sty	745
96	lwarp-copyrightbox.sty	745
97	lwarp-crop.sty	746
98	lwarp-ctable.sty	746
99	lwarp-cuted.sty	749
100	lwarp-cutwin.sty	749
101	lwarp-dblfloatfix.sty	750
102	lwarp-dblfnote.sty	750
103	lwarp-dcolumn.sty	750
104	lwarp-decimal.sty	751
105	lwarp-diagbox.sty	751
106	lwarp-dingbat.sty	753
107	lwarp-DotArrow.sty	754
108	lwarp-dotlessi.sty	754
109	lwarp-dprogress.sty	754
110	lwarp-draftcopy.sty	755
111	lwarp-draftfigure.sty	755
112	lwarp-draftwatermark.sty	755
113	lwarp-drftcite.sty	756
114	lwarp-easy-todo.sty	756

115	lwarp-ebook.sty	757
116	lwarp-econometrics.sty	758
117	lwarp-ed.sty	760
118	lwarp-ellipsis.sty	761
119	lwarp-embrac.sty	761
120	lwarp-emptypage.sty	762
121	lwarp-endfloat.sty	762
122	lwarp-endheads.sty	763
123	lwarp-endnotes.sty	764
124	lwarp-engtlc.sty	765
125	lwarp-enumerate.sty	769
126	lwarp-enumitem.sty	769
127	lwarp-epigraph.sty	770
128	lwarp-epsfig.sty	771
129	lwarp-epstopdf.sty	771
130	lwarp-epstopdf-base.sty	772
131	lwarp-eqlist.sty	773
132	lwarp-eqparbox.sty	773
133	lwarp-errata.sty	774
134	lwarp-eso-pic.sty	775
135	lwarp-esvect.sty	776
136	lwarp-etoc.sty	776
137	lwarp-eurosym.sty	779
138	lwarp-everypage.sty	779
139	lwarp-everyshi.sty	779
140	lwarp-extarrows.sty	780
141	lwarp-extramarks.sty	780

142	lwarp-fancybox.sty	781
143	lwarp-fancyhdr.sty	786
144	lwarp-fancyref.sty	787
145	lwarp-fancytabs.sty	787
146	lwarp-fancyvrb.sty	788
147	lwarp-fbox.sty	794
148	lwarp-fewerfloatpages.sty	797
149	lwarp-figcaps.sty	797
150	lwarp-figsize.sty	797
151	lwarp-fitbox.sty	798
152	lwarp-fix2col.sty	798
153	lwarp-fixmath.sty	799
154	lwarp-fixme.sty	799
155	lwarp-fixmetodonotes.sty	800
156	lwarp-flafter.sty	801
157	lwarp-flippdf.sty	801
158	lwarp-float.sty	801
159	lwarp-floatflt.sty	803
160	lwarp-floatpag.sty	804
161	lwarp-floatrow.sty	804
162	lwarp-fltrace.sty	809
163	lwarp-flushend.sty	810
164	lwarp-fnbreak.sty	810
165	lwarp-fncychap.sty	810
166	lwarp-fnlineno.sty	811
167	lwarp-fnpara.sty	811
168	lwarp-fnpos.sty	811

169	lwarp-fontawesome.sty	812
170	lwarp-fontawesome5.sty	813
171	lwarp-fontaxes.sty	814
172	lwarp-fontenc.sty	814
173	lwarp-footmisc.sty	815
174	lwarp-footnote.sty	816
175	lwarp-footnotebackref.sty	817
176	lwarp-footnotehyper.sty	817
177	lwarp-footnoterange.sty	817
178	lwarp-footnpag.sty	817
179	lwarp-foreign.sty	818
180	lwarp-forest.sty	818
181	lwarp-fouridx.sty	819
182	lwarp-fourier.sty	819
183	lwarp-framed.sty	821
184	lwarp-ftcap.sty	823
185	lwarp-ftnright.sty	823
186	lwarp-fullminipage.sty	823
187	lwarp-fullpage.sty	824
188	lwarp-fullwidth.sty	824
189	lwarp-fvextra.sty	824
190	lwarp-fwlw.sty	827
191	lwarp-gensymb.sty	828
192	lwarp-gentombow.sty	828
193	lwarp-geometry.sty	828
194	lwarp-ghsystem.sty	829
195	lwarp-gindex.sty	830

196	lwarp-gloss.sty	831
197	lwarp-glossaries.sty	831
198	lwarp-gmeometric.sty	833
199	lwarp-graphics.sty	834
305	graphics	834
305.1	Graphics extensions	834
305.2	Length conversions and graphics options	835
305.3	Printing HTML styles	837
305.4	\includegraphics	838
305.5	Boxes	843
200	lwarp-graphicx.sty	846
201	lwarp-grffile.sty	846
202	lwarp-grid.sty	847
203	lwarp-grid-system.sty	847
204	lwarp-gridset.sty	847
205	lwarp-hang.sty	848
206	lwarp-hanging.sty	849
207	lwarp-hepunits.sty	850
208	lwarp-hhline.sty	852
209	lwarp-hhtensor.sty	852
210	lwarp-hypbmsec.sty	853
211	lwarp-hypcap.sty	853
212	lwarp-hypdestopt.sty	853
213	lwarp-hypernat.sty	854
214	lwarp-hyperref.sty	854
215	lwarp-hyperxmp.sty	863
216	lwarp-hyphenat.sty	864

217	lwarp-idxlayout.sty	864
218	lwarp-ifoddpag.sty	865
219	lwarp-imateidx.sty	866
220	lwarp-index.sty	870
221	lwarp-inputtrc.sty	871
222	lwarp-intopdf.sty	872
223	lwarp-jurabib.sty	872
224	lwarp-karnaugh-map.sty	873
225	lwarp-keyfloat.sty	876
226	lwarp-keystroke.sty	882
227	lwarp-kpfonts.sty	883
228	lwarp-kpfonts-otf.sty	885
229	lwarp-layaureo.sty	886
230	lwarp-layout.sty	886
231	lwarp-layouts.sty	887
232	lwarp-leading.sty	889
233	lwarp-leftidx.sty	890
234	lwarp-letterspace.sty	890
235	lwarp-lettrine.sty	890
236	lwarp-libertinustlmath.sty	891
237	lwarp-lineno.sty	897
238	lwarp-lips.sty	900
239	lwarp-listings.sty	900
240	lwarp-listliketab.sty	905
241	lwarp-lltjext.sty	905
242	lwarp-longtable.sty	906
243	lwarp-lscape.sty	909

244	lwarp-ltablex.sty	909
245	lwarp-ltcaption.sty	910
246	lwarp-ltxgrid.sty	910
247	lwarp-ltxtable.sty	910
248	lwarp-lua-check-hyphen.sty	911
249	lwarp-lua-visual-debug.sty	911
250	lwarp-luacolor.sty	911
251	lwarp-luamplib.sty	911
252	lwarp-luatexko.sty	912
253	lwarp-luatodonotes.sty	914
254	lwarp-lyluatex.sty	916
255	lwarp-magaz.sty	918
256	lwarp-makeidx.sty	918
257	lwarp-manyfoot.sty	919
258	lwarp-marginal.sty	921
259	lwarp-marginfit.sty	921
260	lwarp-marginfix.sty	921
261	lwarp-marginnote.sty	922
262	lwarp-marvosym.sty	922
263	lwarp-mathalpha.sty	923
264	lwarp-mathastext.sty	923
265	lwarp-mathcomp.sty	924
266	lwarp-mathdesign.sty	925
267	lwarp-mathdots.sty	926
268	lwarp-mathfixs.sty	927
269	lwarp-mathpazo.sty	927
270	lwarp-mathptmx.sty	928

271	lwarp-mathspec.sty	928
272	lwarp-mathtools.sty	930
273	lwarp-mcaption.sty	936
274	lwarp-mdframed.sty	937
380	mdframed	937
380.1	Limitations	937
380.2	Package loading	938
380.3	Patches	938
380.4	Initial setup	938
380.5	Color and length HTML conversion	939
380.6	Environment encapsulation	939
380.7	Mdframed environment	940
380.8	Titles and subtitles	941
380.9	New environments	943
275	lwarp-media9.sty	946
276	lwarp-memhfixc.sty	948
277	lwarp-menukeys.sty	948
278	lwarp-metalogo.sty	949
279	lwarp-metalogox.sty	950
280	lwarp-mhchem.sty	950
281	lwarp-microtype.sty	953
282	lwarp-midfloat.sty	954
283	lwarp-midpage.sty	954
284	lwarp-minibox.sty	954
285	lwarp-minitoc.sty	955
286	lwarp-minted.sty	955
287	lwarp-mismath.sty	956

288	lwarp-mleftright.sty	960
289	lwarp-morefloats.sty	960
290	lwarp-moreverb.sty	961
291	lwarp-movie15.sty	962
292	lwarp-mparhack.sty	963
293	lwarp-multibib.sty	964
294	lwarp-multicap.sty	964
295	lwarp-multicol.sty	964
296	lwarp-multicolrule.sty	966
297	lwarp-multimedia.sty	966
298	lwarp-multiobjective.sty	967
299	lwarp-multirow.sty	968
300	lwarp-multitoc.sty	971
301	lwarp-musicography.sty	972
302	lwarp-nameauth.sty	975
303	lwarp-nameref.sty	976
304	lwarp-natbib.sty	976
305	lwarp-nccfancyhdr.sty	977
306	lwarp-nccfoots.sty	978
307	lwarp-nccmath.sty	978
308	lwarp-needspace.sty	980
309	lwarp-newpxmath.sty	980
310	lwarp-newtxmath.sty	981
311	lwarp-newtxsf.sty	982
312	lwarp-nextpage.sty	983
313	lwarp-nfssect-cfr.sty	983
314	lwarp-nicefrac.sty	990

315	lwarp-niceframe.sty	990
316	lwarp-noitcrul.sty	991
317	lwarp-nolbreaks.sty	991
318	lwarp-nomencl.sty	991
319	lwarp-nonfloat.sty	992
320	lwarp-nonumonpart.sty	992
321	lwarp-nopageno.sty	992
322	lwarp-notes.sty	993
323	lwarp-notespages.sty	993
324	lwarp-nowidow.sty	994
325	lwarp-ntheorem.sty	994
431	ntheorem	994
431.1	Limitations	995
431.2	Options	995
431.3	Remembering the theorem style	996
431.4	HTML cross-referencing.	999
431.5	\newtheoremstyle	999
431.6	Standard styles.	1000
431.7	Additional objects	1001
431.8	Renewed standard configuration	1001
431.9	amsthm option	1002
431.10	Ending a theorem.	1005
431.11	\NoEndMark	1005
431.12	List-of.	1005
431.13	Symbols	1006
431.14	Cross-referencing.	1006
326	lwarp-octave.sty	1006
327	lwarp-overpic.sty	1007

328	lwarp-pagegrid.sty	1008
329	lwarp-pagenote.sty	1008
330	lwarp-pagesel.sty	1009
331	lwarp-paralist.sty	1009
332	lwarp-parallel.sty	1010
333	lwarp-parcolumns.sty	1011
334	lwarp-parnotes.sty	1013
335	lwarp-parskip.sty	1015
336	lwarp-pbox.sty	1015
337	lwarp-pdfcol.sty	1015
338	lwarp-pdfcolfoot.sty	1016
339	lwarp-pdfcolmk.sty	1016
340	lwarp-pdfcolparallel.sty	1016
341	lwarp-pdfcolparcolumns.sty	1017
342	lwarp-pdfcomment.sty	1017
343	lwarp-pdfcrypt.sty	1018
344	lwarp-pdflandscape.sty	1018
345	lwarp-pdfmarginpar.sty	1019
346	lwarp-pdfpages.sty	1019
347	lwarp-pdfprivacy.sty	1021
348	lwarp-pdfrender.sty	1022
349	lwarp-pdfsync.sty	1022
350	lwarp-pdftricks.sty	1022
351	lwarp-pdfx.sty	1023
352	lwarp-perpage.sty	1023
353	lwarp-pfnote.sty	1024
354	lwarp-phfqit.sty	1025

355	lwarp-physics.sty	1025
356	lwarp-physunits.sty	1026
357	lwarp-picinpar.sty	1027
358	lwarp-pifont.sty	1029
359	lwarp-placeins.sty	1030
360	lwarp-plarydshln.sty	1030
361	lwarp-plext.sty	1030
362	lwarp-plextarydshln.sty	1031
363	lwarp-plextcolortbl.sty	1031
364	lwarp-plimsoll.sty	1032
365	lwarp-prelim2e.sty	1032
366	lwarp-prettyref.sty	1032
367	lwarp-preview.sty	1033
368	lwarp-psfrag.sty	1033
369	lwarp-psfragx.sty	1034
370	lwarp-pst-eps.sty	1034
371	lwarp-pstool.sty	1034
372	lwarp-pstricks.sty	1035
373	lwarp-pxatbegshi.sty	1036
374	lwarp-pxeveryshi.sty	1036
375	lwarp-pxfonts.sty	1036
376	lwarp-pxftnright.sty	1037
377	lwarp-pxjahyper.sty	1037
378	lwarp-quotchap.sty	1037
379	lwarp-quoting.sty	1038
380	lwarp-ragged2e.sty	1039
381	lwarp-realscripts.sty	1039

382	lwarp-refcheck.sty	1043
383	lwarp-register.sty	1043
384	lwarp-reysize.sty	1044
385	lwarp-repeatindex.sty	1045
386	lwarp-repltext.sty	1046
387	lwarp-resizegather.sty	1046
388	lwarp-returntogrid.sty	1047
389	lwarp-rmathbr.sty	1047
390	lwarp-rmpage.sty	1047
391	lwarp-romanbar.sty	1047
392	lwarp-romanbarpagenumber.sty	1048
393	lwarp-rotating.sty	1048
394	lwarp-rotfloat.sty	1049
395	lwarp-rviewport.sty	1050
396	lwarp-savetrees.sty	1050
397	lwarp-scalefnt.sty	1050
398	lwarp-scalerel.sty	1050
399	lwarp-schemata.sty	1051
400	lwarp-scrextend.sty	1052
401	lwarp-scrhack.sty	1056
402	lwarp-scrlayer.sty	1056
403	lwarp-scrlayer-notecolumn.sty	1057
404	lwarp-scrlayer-scrpage.sty	1058
405	lwarp-scrpage2.sty	1059
406	lwarp-section.sty	1060
407	lwarp-sectionbreak.sty	1061
408	lwarp-sectsty.sty	1061

409	lwarp-selectp.sty	1062
410	lwarp-semantic-markup.sty	1062
411	lwarp-seqsplit.sty	1063
412	lwarp-setspace.sty	1064
413	lwarp-shadethm.sty	1065
414	lwarp-shadow.sty	1065
415	lwarp-shapepar.sty	1066
416	lwarp-showidx.sty	1066
417	lwarp-showkeys.sty	1066
418	lwarp-showtags.sty	1067
419	lwarp-shuffle.sty	1067
420	lwarp-sidecap.sty	1068
421	lwarp-sidenotes.sty	1069
422	lwarp-simplebnf.sty	1070
423	lwarp-SIunits.sty	1072
424	lwarp-siunitx.sty	1079
425	lwarp-slantsc.sty	1090
426	lwarp-slashed.sty	1090
427	lwarp-soul.sty	1090
428	lwarp-soulpos.sty	1092
429	lwarp-soulutf8.sty	1093
430	lwarp-splitbib.sty	1093
431	lwarp-splitidx.sty	1094
432	lwarp-srcltx.sty	1096
433	lwarp-srctex.sty	1096
434	lwarp-stabular.sty	1096
435	lwarp-stackengine.sty	1097

436	lwarp-stackrel.sty	1099
437	lwarp-statex2.sty	1099
438	lwarp-statistics.sty	1103
439	lwarp-statmath.sty	1109
440	lwarp-steinmetz.sty	1110
441	lwarp-stfloats.sty	1111
442	lwarp-struktex.sty	1111
443	lwarp-subcaption.sty	1112
444	lwarp-subfig.sty	1112
445	lwarp-subfigure.sty	1117
446	lwarp-subsupscripts.sty	1118
447	lwarp-supertabular.sty	1119
448	lwarp-svg.sty	1120
449	lwarp-swfigure.sty	1121
450	lwarp-syntonly.sty	1121
451	lwarp-tabfigures.sty	1122
452	lwarp-tablefootnote.sty	1122
453	lwarp-tables.sty	1122
454	lwarp-tabularx.sty	1123
455	lwarp-tabulary.sty	1123
456	lwarp-tagpdf.sty	1124
457	lwarp-tascmac.sty	1126
458	lwarp-tcolorbox.sty	1127
459	lwarp-termcal.sty	1133
460	lwarp-textarea.sty	1134
461	lwarp-textcomp.sty	1134
462	lwarp-textfit.sty	1138

463	lwarp-textpos.sty	1138
464	lwarp-theorem.sty	1139
465	lwarp-thinsp.sty	1143
466	lwarp-thm-listof.sty	1143
467	lwarp-thm-restate.sty	1144
468	lwarp-thmbox.sty	1144
469	lwarp-thmtools.sty	1145
470	lwarp-threadcol.sty	1146
471	lwarp-threeparttable.sty	1146
472	lwarp-threeparttablex.sty	1147
473	lwarp-thumb.sty	1148
474	lwarp-thumbs.sty	1148
475	lwarp-tikz.sty	1148
476	lwarp-titleps.sty	1150
477	lwarp-titleref.sty	1153
478	lwarp-titlesec.sty	1153
479	lwarp-titletoc.sty	1155
480	lwarp-titling.sty	1157
481	lwarp-tocbasic.sty	1161
482	lwarp-tocbibind.sty	1162
483	lwarp-tocdata.sty	1164
484	lwarp-tocenter.sty	1165
485	lwarp-tocloft.sty	1165
486	lwarp-tocstyle.sty	1171
487	lwarp-todo.sty	1172
488	lwarp-todonotes.sty	1173
489	lwarp-topcapt.sty	1174

490	lwarp-tram.sty	1175
491	lwarp-transparent.sty	1175
492	lwarp-trimclip.sty	1176
493	lwarp-trivfloat.sty	1176
494	lwarp-truncate.sty	1177
495	lwarp-turnthepage.sty	1177
496	lwarp-twoup.sty	1178
497	lwarp-txfonts.sty	1178
498	lwarp-txgreeks.sty	1178
499	lwarp-typearea.sty	1179
500	lwarp-typicons.sty	1180
501	lwarp-ulem.sty	1180
502	lwarp-umoline.sty	1182
503	lwarp-underscore.sty	1183
504	lwarp-unicode-math.sty	1183
505	lwarp-units.sty	1187
506	lwarp-unitsdef.sty	1188
507	lwarp-upgreek.sty	1189
508	lwarp-upref.sty	1189
509	lwarp-url.sty	1189
510	lwarp-ushort.sty	1190
511	lwarp-ospace.sty	1190
512	lwarp-varioref.sty	1190
513	lwarp-verse.sty	1191
514	lwarp-ersonotes.sty	1192
515	lwarp-vertbars.sty	1193
516	lwarp-vmargin.sty	1193

517	lwarp-vowel.sty	1194
518	lwarp-vpe.sty	1194
519	lwarp-vwcol.sty	1195
520	lwarp-wallpaper.sty	1197
521	lwarp-watermark.sty	1197
522	lwarp-widetable.sty	1198
523	lwarp-widows-and-orphans.sty	1198
524	lwarp-witharrows.sty	1198
525	lwarp-wrapfig.sty	1200
526	lwarp-xbmks.sty	1201
527	lwarp-xcolor.sty	1201
633	xcolor	1201
633.1	Limitations	1202
633.2	xcolor definitions: location and timing	1202
633.3	Package loading	1204
633.4	Remembering and restoring original definitions	1204
633.5	\normalcolor	1204
633.6	HTML color style	1204
633.7	HTML border	1206
633.8	High-level macros	1206
633.9	Row colors	1210
528	lwarp-xexchangebar.sty	1212
529	lwarp-xellipsis.sty	1212
530	lwarp-xetexko-vertical.sty	1213
531	lwarp-xfakebold.sty	1213
532	lwarp-xfrac.sty	1214
533	lwarp-xltabular.sty	1216

534	lwarp-xtxttra.sty	1216
535	lwarp-xmpincl.sty	1217
536	lwarp-xpiano.sty	1217
537	lwarp-xpinyin.sty	1218
538	lwarp-xr.sty	1219
539	lwarp-xr-hyper.sty	1220
540	lwarp-xtab.sty	1220
541	lwarp-xunicode.sty	1222
542	lwarp-xurl.sty	1223
543	lwarp-xy.sty	1223
544	lwarp-zhlineskip.sty	1224
545	lwarp-zwpagelayout.sty	1225
546	lwarp-patch-komascript.sty	1226
547	lwarp-patch-memoir.sty	1228
653	patch-memoir	1228
653.1	Packages	1229
653.2	Label handling	1230
653.3	Page layout	1231
653.4	Text and fonts	1234
653.5	Titles	1234
653.6	Abstracts	1235
653.7	Document divisions	1235
653.8	Pagination and headers	1238
653.9	Paragraphs and lists	1239
653.10	Contents lists	1239
653.11	Floats and captions	1243
653.12	Footnotes and page notes	1247
653.13	Decorative text	1249

653.14	Poetry	1249
653.15	Boxes, verbatims and files	1250
653.16	Cross referencing	1250
653.17	Back matter	1251
653.18	Miscellaneous	1253
653.19	ccaption emulation	1253
653.20	Final patchwork	1256
548	lwarp-common-multimedia.sty	1257
549	lwarp-common-mathjax-letters.sty	1262
550	lwarp-common-mathjax-newpctxmath.sty	1269
551	lwarp-common-mathjax-nonunicode.sty	1274
552	lwarp-common-mathjax-overlaysymbols.sty	1277
	Change History	1279
659	Chg Hist	1279
	Index of Objects	1317
	General Index	1341
	Troubleshooting Index.	1346
	Index of Indexes	1352

List of Figures

1	tutorial.tex listing	84
---	--------------------------------	----

List of Tables

1	Typesetting conventions	65
2	L ^A T _E X lwarp package — Supported features	66
3	Required software programs	77
4	Configuration files created by print version	86
5	Localization settings	99
6	Accessibilitiy settings	100
7	Lwarp package options	105
8	HTML settings	111
9	Literal character macros	180
10	Section HTML headings for word-processor conversion	188
11	Section depths and HTML headings	204
12	Tabular baseline	460
13	Tabular HTML column conversions	461
14	Cross-referencing data structures	504
15	Float data structures	515
16	CSS related to the sideroc	527
17	amsthm package — css styling of theorems and proofs	657
18	Ntheorem package — css styling of theorems and proofs	994
19	Theorem package — css styling of theorems and proofs	1139

1 Updates

The following is a summary of updates to `lwarp`, highlighting new features and any special changes which must be made due to improvements or modifications in `lwarp` itself.

For a detailed list of the most recent changes, see the end of the Change History on page 1316.

v0.893: Minor fixes, more packages.

`MATHJAX`
packages

- Added `MATHJAX` emulation for `\mathnormal`.
- Fixed `pstricks` `pspicture*`.
- Fixed `tikz` font macros.
- `braket`: Now uses the `MATHJAX` extension.
- Added `esvect`, `fixmath`, `keystroke`, `mathastext`, `menukeys`, `picipar`, `plimsoll`, `repltext`, `selectp`, `seqsplit`, `simplebnf`, `statistics`, `swfigure`.
- Added `MATHJAX` emulation for `mathspec`.
- Verified to work as-is for `apxproof`, `syntaxdi`, `venndiagram`.

v0.892: `minted`, `fvextra`, `MATHJAX \left/\right`.

`MATHJAX`
packages

- `fourier`, `libertinustlmath`, `newpxmath`, `newtxmath`, `newtxsf`, `unicode-math`: Added `MATHJAX \left/\right` support for additional delimiters.
- `textpos`: Updated to v1.10.
- `xcolor`: Fixed optional args for `\fcolorbox` and related.
- Added `fvextra`, `minted`.

v0.891: `MATHJAX` additions and improvements.

`core`

- Now displays inline `\verb` text as `\texttt`.
- Fixed `alltt` and `verbatim` with \LaTeX lists.
- Now generates an error if nested each of `warpHTML`, `warpprint`, `warpMathJax` inside itself.

`MATHJAX`
packages

- Added `MATHJAX` `textmacros` extension, allowing formatting inside `\text`.
- `biblatex`, `hyperref`: Added back page references.
- `fancyvrb`: Fixed `BVerbatim` with a label.
- `listings`: Fixed `MATHJAX` with captions, improved HTML sanitation.
- `babel-french`: Fixed `\texorpdfstring` conflict.
- Now honors Greek package options for `mathdesign`, `mathpazo`, `mathptmx`, `newpxmath`, `newtxmath`.
- Improved `MATHJAX` for `colonequals`, `mathdesign`, `mathdots`, `mathfixs`, `mathtools`, `multiobjective`, `nicefrac`, `shuffle`, `units`.
- `unicode-math`: Added Greek macros, as well as macros for the first several categories listed in `texdoc unimath-symbols`. Improved symbol shape macros with Greek. Improved documentation.

- Added bussproofs, cmbright, fourier, kpfonts, kpfonts-otf, libertinust1math, scalerel, txgreek.

v0.89: Additional MATHJAX support.

core

- Adapted to upcoming L^AT_EX kernel changes.
- Allows load of amsmath before lwarp.

lwarpmk

- Also removes *.bbl when cleaning aux files.

MATHJAX

- MATHJAX: Neutralized \protect, \mathcode and related, ligatures. Fixed nested environments.

packages

- caption: Updated for v3.5, fix for label sep.
- thmtools: Updated for v0.72. Fixed swapnumber, margin.
- Improved MATHJAX for centernot, mathtools, mismath, Slunits, siunitx, statmath.
- Added MATHJAX emulation for accents, hepunits, hhtensor, mathalpha, mathdesign, mathpazo, mathptmx, mleftright, newpxmath, newtxmath, newtxsf, pxfonts, shuffle, txfonts, upgreek, ushort.
- Verified to work as-is: authoraftertitle.

v0.88: Indexing, boxing, theorems.

- **Now has programmed support for more than 500 packages and classes, of which more than 60 also support MATHJAX.**

core

- Fixed: \ref*, and also added MATHJAX emulation.
- If starting a new paragraph, \hrulefill creates a <div> with a thin horizontal line across the page. Use instead of \hrule.
- Fixed: Use \chaptername where appropriate.
- Fixed: Inline links causing extraneous paragraphs.

lwarpmk

- Added **lwarpmk -v** to print the version number.

indexing

- Added the IndexRef option to control the display of index entries. See section 7.5.
- Added \IndexPageSeparator and \IndexRangeSeparator for custom index styles.
- Added support for gindex, xindex.
- Verified to work as-is with varindex.

packages

- cleveref, varioref: Fix for starred macros.
- varioref: Removed page-related text from HTML output.
- xfakebold: Updated to v0.08, using pdfrender.
- caption, scrextend: Fixed \caption*.
- Added fbox, shadethm, tcolorbox, termcal, thmbox, thmtools.

v0.87: MATHJAX, bibliography packages.

core

- Added boolean `FixSmallCaps` for fonts which render small caps as all caps.
- Fixed `\bibliography` to use the HTML version's `.bbl` file. Previously the HTML bibliography relied on the print version's `.bbl`, thus would fail if the print document had not yet been created.
- Added `\ifstar` and `\ifnextchar` to MATHJAX, and removed `\DeclareIfstar`. See section 8.7.5.
- `physics`: Now supports the MATHJAX v3 extension.
- `mathtools`: Improved `\underbracket`, `\overbracket` for MATHJAX.
- `nccmath`: Improved `\underrel` for MATHJAX.
- `mhchem`: Now supports the MATHJAX v3 extension for `\ce` inside math.
- `cancel`: Now supports the MATHJAX v3 extension.
- `embrac`: Neutralized kerning for improved HTML conversion.
- Added `citeref`, `drftcite`, `jurabib`, `multibib`, `splitbib`.
- Verified to work as-is with `bibtopic`, `collref`, `mciteplus`.

MATHJAX

⚠ Removed
`\DeclareIfstar`
 packages

v0.86: MATHJAX major updates.

core

- Fixed: Filename if named files with `*`, parens, period in section name.
- Fixed: Labels in `eqnarray`, `lateximage`.

MATHJAX

- Updated to MATHJAX v3. New repository.
- Fixed forward references for MATHJAX.
- Improved MATHJAX equation number formatting, now compatible with `amsmath \numberwithin` for chapters, sections, subsections, as well as `amsmath subequations`. See section 8.7.5.
- Added `\DeclareIfstar` to define starred TEX macros in MATHJAX. See section 8.7.5.
- Generates an error if `\MathJaxFilename` file does not exist.

packages

- `mathtools`, `nccmath`, `physics`: Added starred macros for MATHJAX.
- `nccmath`: Fixed `\nr`, `\displaybreak` for MATHJAX.
- `xcolor`: Fixed `\textcolor` with `babel-french`.

v0.85: fontspec

packages

⚠ `acro formats`

- `fontspec`: Fixed core font change macros for world languages.
- `acro`: Due to v3 changes, when defining acronym formats, use `\textbf` instead of `\bfseries`, etc.
- Fixed `idxlayout`, `mathtools`, `titlesec`, `url`.

v0.84: Previous/next page links, numerous fixes.

docs

- Added documentation of `BlockClass` and `\InlineClass` for CSS `<div>s` and `s`. See section 7.8.
- Added `\LinkPrevious`, `\LinkNext` page links. See section 7.6.
- Added `\FirstPageBottom`. Home page no longer shares `\PageBottom`. See section 7.6.

⚠ home page footer changed

core

- Improved coexistence with `comment`, support for nested environments.
- No longer requires but still supports the `caption` package.
- Improved filenames and HTML titles when using special characters.

⚠

- Change: Append `-0` to section named `Index` previously `_index` to distinguish from `index.html`
- Fixed style tags for `\multicolumn`, `\multirow`.
- Fixed spacing in `tabbing`.
- Fixed `lateximage` for: `quote`, `quotation`, `verse`, `center`, `flushleft`, `flushright`, `<par>` tags, packages `verbatim`, `alltt`, `epigraph`.
- Fixed `textcomp` due to integration into \LaTeX kernel.
- Fixed `\itshape`, etc. Adapted to \LaTeX fontaxes integration.
- Fixed `\@fnsymbol`.
- Warns about section names with dollar-delimited math.
- Warns about a `` containing a float, caption, section, `mdframed`, or other `<div>` object.
- Only warn about \XeTeX logo and `graphics` if actually used `\Xe`.
- **lwarpmk clean** also removes `comment_*.cut`.
- `scrextend`, `scrartcl`, `scrbook`: Added `\titlehead`, `\subject`, `\subtitle`, `\publishers`.
- `titling`: Fixed `\printthanks`.
- `memoir`, `abstract`: Fixed for updated `memoir`.
- `memoir`: Fixed `\newcomment`, `pagenotes`, `crossreferences`. Fixed setting a recursive name.
- Fixed or improved: `amsthm`, `backref`, `biblatex`, `fixme`, `nfssect-cfr`, `ntheorem`, `parcolumns`, `realscripts`, `rotfloat`, `titling`.
- Added `boxedminipage`, renamed from `boxedminipage2e` per author.
- Verified to work as-is with `mcite`.

lwarpmk packages

v0.83: memoir fixes.

packages

- `memoir`: Various fixes and updates.
- `physunits`: Updated to v1.0.4.

v0.82: MATHJAX notes, xpinyin improvements, various updates.

- MATHJAX
 - Improved footnotes with MATHJAX.
 - Added MATHJAX emulation for endnotes, marginnote, nccfoots, pagenote, parnotes, sidenotes.
- packages
 - xpinyin: Added pinyin with modern HTML.
 - luatexko: Added `\dotemph`, `\ruby`, `\uline`, etc.
 - soul: Fixed `\<`.
 - chemfig: Updated to v1.5.
 - draftwatermark: Updated to v2.0.
 - ulem: Fixed: `\dashuline`.
 - amsmath: Fixed: `\intertext` with MATHJAX.
 - endnotes: Fixed: Marks in print mode.
 - tocvsec2, tableof: Verified to work as-is.
 - Added etoc (nullified).

v0.81: MATHJAX speedup and additional emulations.

- core
 - Improved warning regarding SVG math sizing/baselines and graphics/graphics. See section 8.7.
- MATHJAX
 - Improved MATHJAX emulation processing speed.
 - Added MATHJAX emulation for accsupp, axessibility, colonequals, decimal, dotlessi, econometrics, engtlc, multiobjective, physunits, Slunits, stackrel, statmath.
- packages
 - axessibility: Updated to 2020/01/08 version.
 - gridset: Updated to v0.3.
 - Slunits: Fixed for math mode.
 - Added DotArrow, nolbreaks, luamplib, returntograd, statex2, tagpdf.
 - Verified to work as-is with icomma, mathpunctspace, textualicomma.

v0.80: MATHJAX, biblatex.

- MATHJAX
 - Added docs and warning/info messages re: avoiding slow MATHJAX compilation. See section 8.7.5, [Customizing MATHJAX](#).
 - Added MATHJAX emulation for accessibility, autobreak, centernot, extarrows, fouridx, gensymb, leftidx, mathcomp, mathdots, mathfixs, mismath, nccmath, noitcrul, pdfcomment, relsize, rmathbr, subsubscripts, xfrac.
 - Improved MATHJAX emulation for unicode-math.
- packages
 - biblatex, url: Now create hyperlinks.
 - amsmath: Fix to center starred environments.
 - xcolor, graphics: Made more macros robust.
 - colortbl: Fix: Rule color in a lateximage.
 - chemmacros: Updated to v5.10.
 - Added fewerfloatpages, ghsystem, hline, mismath, nccmath.

v0.79: MATHJAX, nested tabular.

- MATHJAX**
 - Added or improved MATHJAX emulation for amsmath, ar, arydshln, bm, bigdelim, bigstrut, booktabs, braket, mathtools, multirow, physics, siunitx, slashed, unicode-math, xfakebold.
 - Warn if using certain packages not supported by MATHJAX.
- core**
 - tabular: Now may be nested.
 - minipage, \parbox, fminipage, \makebox, \framebox: Fix: Adjust for virtual page size.
 - Uses new iftex.
- packages**
 - graphicx: Fix: Negative angles.
 - caption: Fix: \captionlistentry with longtable.
 - multirow: Fix: Centered vertical alignment.
 - siunitx: Fix: \square, \cubed.
 - booktabs: Fix: memoir with lateximage.
 - babel and polyglossia: Added troubleshooting warnings.
 - fontawesome, fontawesome5: Supports text color and size.
 - transparent: Fix: lateximages.
 - epigraph: Updated to v1.5e.
 - xurl: Updated to v0.08.
 - subcaption: Fixed with memoir.
 - floatrow: Fix: \linewidth. No longer require float, graphics.
 - floatflt, wrapfig, niceframe: Fix: Adjust for virtual page size.
 - Added widetable, witharrows, steinmetz.
 - Added awesomebox, catoptions.
 - Added svg, supports svg-extract.
 - Added parcolumns, pdfcolparcolumns,
 - Added parallel, pdfcolparallel.
 - Added pdfcol, pdfcolfoot, pdfcolmk.

v0.78: Fixes for support files, alt tags, hyperlinks, and the 2019/10 L^AT_EX release.

- docs**
 - Docs: Improved documentation regarding package options. See section 8.1.
 - Fix to overwrite existing support files using new filecontents environment.
- packages**
 - breqn: Previously broken by the 2019/10 L^AT_EX update, but now working again.
 - graphics: Fix for \includegraphics alt tags.
 - babel-french: Fix for hyperlinks.
 - media9, movie15, multimedia: Fix for the 2019/10 L^AT_EX update.
 - accessibility: Added.

v0.77: Updates to fix recently-broken packages.

- booktabs: Updated to v1.6180339.
- chemformula: Updated to v4.15.

v0.76: MATHJAX, updates for L^AT_EX 2019/10 release.

docs

- Docs: Expanded documentation regarding the use of multiple projects in the same directory. See section 5.17.

MATHJAX

- MATHJAX: Updated to v2.7.6.

packages

- xr: Updated to v5.05.
- xr-hyper: Updated to v6.1.
- Verified works as-is with xcite.
- acro: Updated to v2.10.

⚠ broken

- Currently broken in print mode by the 2019/10 L^AT_EX update, and waiting for fixes: breqn, grffile, multimedia, movie15.

v0.75: keyfloat, wrapfig

packages

- \minipage: Fix for \linewidth.
- keyfloat: Improved color control.
- wrapfig: Fix for \linewidth.

v0.74: Docs, svg math, *lwarpmk*, HTML alt and title text, lyluatex

docs

- Added to the tutorial the section **What next?**. See section 5.19.
- Added documentation about localization options. See section 7.1.
- Added documentation about accessibility options. See section 7.2.
- Renamed and updated HTML alt text macros:

⚠ HTML alt text
changed names

Old	New
(hard coded as “image”)	\ImageAltText
\mathimagename	\MathImageAltText
\packagediagramname	\PackageDiagramAltText

- Added \ImageAltText for the default HTML alt text for an image. See section 7.6.
- Added \ThisAltText, which may be used to assign a one-time HTML alt tag to the very next image generated by lwarp, such as a lateximage, picture, tikzpicture, an image generated by various chemistry or engineering packages, or an svg math image. This macro also adds a title tag to a reference or hyperlink. See section 7.6.

svg math

- Adjusted \LateximageFontSize default from .75 to 1.
- Fix: Font control for svg math.

misc

- Fix: Ignores negative \hspace.
- Warning if SideTOCDepth < FileDepth.

lwarpmk

- *lwarpmk*: **lwarpmk clean** removes additional files.

- *lwarpmk*: **lwarpmk epstopdf** and **lwarpmk pdftosvg** now honor directories.
- *lyluatex*: Split images by system or per fullpage, improved margins and scaling.
- Tested to work as-is with *mathspec*, *unicode-math*.

packages

v0.73: `\include`, *memoir*, *koma-script*, *caption*, *xy*, *datatool*, music scores.

packages

- Fix for `\include`.
- Warning for a *tabular* inside a ``.
- `\color`: Added HTML support for rules and frames, but not inline text. Use `\textcolor` if possible.
- Improved many HTML tags, reducing *tidy* warnings. See Change History.
- *memoir*: Fixes for `\frontmatter*` and `\mainmatter*`. Added `\book`.
- *koma-script*: Fix for starred captions in the toc.
- *caption*: Fix for starred captions.
- *datatool*: Added pie, bar, and plot charts.
- *threeparttable*: Added `measuredfigure`.
- *intopdf*: Updated to v0.2.1.
- *tocdata*: Updated to v2.03.
- *quotchap*: Updated to v1.2.
- *versonotes*: Updated to v0.4.
- *backnaur*: Now uses SVG images. Updated to v3.1.
- *xy*: Fix for `\xybox`, improved *xy*, also now compatible with *qccircuit*.
- *fancyvrb*: Fix for label HTML tags.
- Added *stackengine*.
- Added *lyluatex*. (Music scores.)
- *musicography*: Updated to 2019/05/28. Added support for *lateximages*.

music

v0.72: Font control, `\multicolumn`, *xr* and *xr-hyper*.

⚠ images

- Due to internal changes, images for inline SVG math and *lateximages* will have new hash values, and will have to be regenerated using

Enter ⇒ **lwarpmk cleanlimages**

and

Enter ⇒ **lwarpmk limages**

- Docs: Color-codes package names in the table of supported packages and features, table 2, according to each package's level of support by *lwarp*.
- `\multicolumn`: Fix for paragraph columns.
- *xr*, *xr-hyper*: Fixes for references, `\externaldocument`.
- *soulutf8*: Fix: Loads *soul* for emulation.
- *boxedminipage2e*: Added support for *lateximages*.
- *zhlineskip*: Updated to v1.0e.
- Added *fontaxes*, *slantsc*, *tabfigures*.
- Added *nfssect-cfr*, thus supporting *cfr-lm* and several other font packages.
- Added *backnaur*, *hybpmsec*, *minibox*, *pdfcrypt*, *shapepar*.

packages

v0.71: Error handling, multimedia, tabular.

- tabular: Added support for ‘*’ columns. Fix for paragraph tags.
- quotation: Fix for HTML tag.
- Docs: Added a section about error conditions tested by lwarp. See section 13.1.
- *lwarpmk*: If file `lwarpmk.conf` is an older version, or the incorrect operating system, displays the print command to use to recompile.
- packages
- chemfig: Updated for v1.4.
- endfloat: Updated for v2.7.
- textpos: Updated for v1.9.1.
- multimedia
- Added `media9`, `movie15`, `multimedia`.

v0.70: Error handling, MATHJAX, mathtools.

- Error handling for “Label(s) changed.” Refuses to `lwarpmk` `limages` until recompile first.
- Fix: If Computer Modern font is used, ensures `cm-super` or `lmodern` is used.
- Fixes for `\makebox`.
- Fixes for `\parbox` inside a ``.
- MATHJAX: Updated to v2.7.5. Loads the `autoload-all.js` extension. Added `\MathJaxFilename` to select custom scripts.
- packages
- `textcomp`, `xunicode`: Fix for `\textinterrobang`.
- `mhchem`: Works with MATHJAX. See section 386.
- `changes`: Updated to v3.1.2.
- Added `autonum`, `changelayout`, `inputtrc`, `mathtools`, `metalogo`.

v0.69: Error handling, many fixes, improved `keyfloat` / `tocdata`.

- Fix for HTML corruption of `lateximage` displays.
- `\makebox`, `\framebox`: Fix for `(\langle width,height \rangle)` arguments.
- `fminipage`: Honors `\minipagefullwidth`.
- packages
- `array`, `longtable`: Fix for `\tabularnewline`.
- `tabularx`, `tabulary`: Fix to require the `array` package.
- `supertabular`, `xtab`: Fix to clear caption after use.
- `graphics`: Added a warning if used the `\includegraphics` `scale` option.
- `multirow`: Added an error if didn’t use `\mrowcell` or `\mcolrowcell` when using `\multirow` or `\multicolumnrow`.
- `keyfloat`: Updated for v2.00, additional improvements.
- Added `ctable`, `eqlist`, `eqparbox`, `ftcap`, `listliketab`, `minitoc`, `tocdata`, `topcapt`.

v0.68: Error handling, tabulars, footnotes.

- lwarpmk*
 - *lwarpmk*: Improved error handling for image generation if compile was incomplete.
 - *tabular*: Fix for `\warpprintonly`.
- packages
 - *longtable*: Improved flexibility for `\endhead`, etc. Improved error reporting if `\endhead`, etc. incorrect for *lwarp*.
 - *threeparttable*: Fix for caption type.
 - *hyperref*: Fix for options with braces.
 - *morefloats*: Fix to be loaded early for print output.
 - *listings*: Updated for v1.7.
 - Added *bigfoot*, *fnpara*, *footnotebackref*, *manyfoot*, *tablefootnote*, *threeparttablex*.
 - Added *layouts*, *niceframe*, *perpage*, *showtags*.
 - Prevented *alg*, *algorithmic*, *pdfcprot*, *fncylab*.

v0.67: Filename generation, symbol fonts.

- docs
 - Documentation fix for `<project>-images`, `<project>-images.txt`.
 - Added discussion regarding section names. See section 8.4.
- filenames
 - Added `\FilenameNullify` and `\FilenameSimplify` for filename generation. See section 8.4.
 - *Core*, *textcomp*, *xunicode*: Nullified additional symbols during filename generation.
- packages
 - *color*: Fix for version number warnings.
 - Added *academicons*, *bbding*, *dingbat*, *eurosym*, *fontawesome*, *fontawesome5*, *marvosym*, *pifont*, *typicons*.
 - Added *changes*, *easyReview*, *fitbox*, *foreign*, *gloss*, *karnaugh-map*, *multicap*, *nomencl*, *notes*, *struktex*, *umoline*, *xfakebold*.
 - Tested to work as-is with *askmaps*, *curves*, *euro*, *karnaughmap*, *tikz-karnaugh*.

v0.66: *xr*, multiple projects, image names/directory, HTML formatting

- ⚠ Reset the configuration
 - Due to changes in *lwarpmk*, **recompile any existing project a single time** using **pdfLatex filename.tex** or similar, after which *lwarpmk* may then be used with the new configuration files.
- lateximage
 - Adds options `ImagesDirectory` and `ImagesName` to assign directory and name prefixes for *lateximage* images. The new defaults include the job-name, allowing the image directories for multiple projects to coexist.
- ⚠ existing projects
 - To reuse existing *lateximage* directories, add *lwarp* options


```
\usepackage[
  ImagesDirectory={lateximages},
  ImagesName={lateximage-}
]{lwarp}
```

If not reused, the existing *lateximages* directory and *lateximages.txt* file may be removed.

- filenames
 - Added `\FilenameLimit` to control the maximum length of the filenames generated by `lwarp`.
- △ Possible filename changes
 - Improved filename generation when special characters or macros are used in section names.
- WINDOWS
 - Fix for `lwarpmk cleanimages` with `WINDOWS`.
- floats
 - Fixes for floats in the home page.
- lists, table notes
 - Improved css for definition lists, table notes.
- tabular
 - `tabular`: Fixes for `\par` in column specifier, `minipage` inside `tabular`.
- indexing
 - Indexing: Fix for a long line of multiple entries.
- minipage
 - `\minipagefullwidth`: Fix for global changes.
 - Added `\UseMinipageWidths` and `\IgnoreMinipageWidths`. See section 8.3.3.
- colors
 - Improved `\fbox`, `\fboxBlock`, `\fminipage` to use current text color.
- HTML
 - Improved HTML output formatting.
- docs
 - Added discussion regarding invalid HTML. See section 8.1.1.
 - Added discussion regarding math in section names, `\imagegraphics scale` option. See section 6.
 - Added discussion regarding international languages in section names. See section 8.14.
- packages
 - `caption`: Fix for options clash.
 - `xr`, `xr-hyper`: Now compatible.
 - `subcaption`: Improved horizontal spacing.
 - `multicol`: Fix for `minipage` inside `multicols`.
 - `multicolrule`: Updated for v1.2.
 - `tocbasic`: Minor update.
 - `acronym`: Fix for acronym in float caption.
 - `kotexutf`: Patch with `pdflatex` and new `lwarp` labels.
 - `extramarks`, `fancyhdr`: Updated for v3.10.
 - `memoir`: Added docs regarding version numbers. See section 8.13.
 - `zref`: No longer required.
 - Added `ar`, `ed`, `indentfirst`, `nameauth`, `truncate`.
 - Verified to work as-is with `changelog`.
 - Prevented `colortab`, `epsf`, `hyper`, `picinpar`, `picins`, `sistyle`, `ucs`.
- v0.65: css layout, alt tags, Japanese.
 - Moved the `sideroc` to the left side, allowing improved css for margin notes.
 - Improved page layout css.
- page layout
 - Moved the `sideroc` to the left side, allowing improved css for margin notes.
 - Improved page layout css.
- image alt tags
 - `graphicx \includegraphics`: Added the `alt` key to assign an alt tag to an image. Default is “image”, assigned to pass validation.
- duplicate HTML files
 - Detects and causes an error if duplicate HTML file names are generated, caused by identical or similar sectioning names.
- fixes
 - Fix for `tabular*`.

- Fix for tabular border colors.
 - Fixes `\quad`, `\enskip`, and figure captions to pass validation.
- Japanese
- Added `ltj*` classes, `bounddvi`, `gentombow`, `ltxtext`, `plarydshln`, `plext`, `plextarydshln`, `plextcolortbl`, `pxatbegshi`, `pxeveryshi`, `pxftnright`, `pxjahyper`, `tascmac`.
 - Verified to work with `plarray`, `plautopatch`, `plextarray`, `plextdelarray`, `pxgentombow`, `plsiunitx`, `pxpdfpages`, `pxpgfrcs`, `pxpgfmark`.
- packages
- Added support for `fontspec \textsi` and `\sishape`.
 - Added `multicol's \docolaction`.
 - Added `embrace`, `footnoterange`, `multicolrule`, `versionotes`.
- v0.64:** Koma-Script, Japanese, Chinese.
- Japanese
- Added `utarticle` and related classes.
 - Improved `ujarticle` and related classes.
- Chinese
- Fix for `biblatex` with `CTEX` and other classes.
- Koma-Script packages
- Fixes for `sclayer`, `sclayer-scrpage`.
 - `addlines`: Updated to v0.3.
 - Added `bsheaders`, `gmeometric`, `marginal`, `rmpage`, `scrpage2`.
- v0.63:** `mdframed`, Chinese, Japanese, Korean
- localization
- Added `\Linkhomename`: A user-definable name for the **Home** link.
 - Documented `\sidetocname`: A user-definable name for the `sideroc`.
- fixes
- Fix: `\LinkHome` for print output.
- optimizations
- Moved package load checks to the `lwarp` core to reduce the number of `lwarp-*` files.
- packages
- `mdframed`: Fix with `amsthm`, improved titles and font control. Improved rule widths.
- Chinese
- Fixes for `xeCJK`.
 - Added `xpinyin`, `zhlineskip`.
 - Verified to work with `ckjpunct`, `upzhkinsoku`, `zhspacing`.
- Japanese
- Verified to work with `zxjatype`, `luatexja`, `luatexja-fontspec`.
 - Added `bxjsarticle` and related classes.
 - Added `ltjsarticle` and related classes.
 - Added `pLATEX`, `upLATEX`, `ujarticle` and related classes.
 - Prevented `utarticle` and related classes.
 - Prevented `bxckatype`.
- Korean
- Verified to work with `kotex`, `xetexko`, `luatexko`.

v0.62: MiKTeX docs, HTML title, CTeX, xeCJK, bitpattern.

- docs
 - Docs: Setting a UTF-8 locale. See section 9.8.
- MiKTeX
 - MiKTeX: Docs for *MiKTeX Console* and miktex-poppler-bin.
- HTML <title>
 - HTML subpage titles: Added \HTMLTitleBeforeSection and \HTMLTitleAfterSection to select whether the HTML <title> displays the website name before or after the section name. See section 7.6.
- fixes
 - Fix for package options handling.
 - Fixes for horizontal white space between fminipage, fcolorminipage, colorboxBlock, fcolorboxBlock.
 - Logos: Fix for XeTeX logo, improved css, made robust, improved search-engine optimization.
 - \[\$1]: Additional HTML
 if \$1 > 0 pt.
 - Fixes for \includgraphics filename, and with FormatWP.
 - Fix: css for \textup.
 - Fix: Added \slshape.
- Chinese
 - Added ctex package and related classes, xeCJK.
 - Prevented CJK, CJKutf8 unless xeCJK, ctex are used.
- packages
 - chemfig: Docs for new macro \polymerdelim.
 - asymptote: Docs for compilation.
 - chngpage: Fix to load lwarp-change page.
 - algorithm2e: Fix with non-book classes.
 - register: Updated to v1.8.
 - nicefrac: Improved font control and css, honors nice and ugly.
 - units: Improved font control and css, honors tight and loose.
 - xfrac: Improved css.
 - textcomp and xunicode: Fix conflicts with \textcircled.
 - ulem: Improved compatibility with CJKulem, lateximage.
 - MathJax and siunitx: Removed inoperable extension.
 - Added bitpattern, pdfcomment, pdfmarginpar, tram, unitsdef, xexchangebar.
 - Added musicography, octave, semantic-markup.
 - Added 2in1, flippdf, notespages, rviewport, twoup.

v0.61: Custom compilation, EPS-related packages, documentation, indexes.

- docs
 - Split index into multiple indexes.
 - Improved documentation regarding font selection. See section 7.4.
 - Added documentation regarding debugging options. See section 34.
 - Added documentation regarding HTML entities inside program listings. See section 8.2.1.
- custom compiling
 - Added options to specify the shell commands to execute for **lwarpmk print** and **lwarpmk html**, allowing the use of lwarp with perltex, pythontex, etc. If not specified, these are set automatically depending on the L^AT_EX engine, --shell-escape, and lwarp options. See section 9.

⚠ changed names

- Changed macro names to match `\displaymathother`, `\displaymathnormal`:

Old	New
<code>\StartDynamicMath</code>	<code>\inlinemathother</code>
<code>\StopDynamicMath</code>	<code>\inlinemathnormal</code>

fixes

- Fix: Paragraph tags in a tabular.
- Fix: supertabular and xtab captions.
- Fix: DVI L^AT_EX `\includegraphics` EPS images.
- Fix: newfloat lists.
- Fix: css footnotes text align, minipage tabular and footnote margins.

packages

- Added epsfig, psfrag, psfragx, pstool.
- Added copyrightbox, pdfprivacy, thinsp, threadcol, uspace.
- Added chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.

v0.60: Fixes for longtable, listings.

fixes

- longtable, etc.: Fixes for slowdown and memory management for very long tables.
- listings: Fix for HTML entities, and also when used inside a list.
- diagbox: Fix for incorrect HTML par tags.

packages

- Added 2up, booklet.
- Added bophook, drafffigure, fullminipage, grid-system, layareo.
- Added leading, widows-and-orphans.
- Added fancytabs, thumb, thumbs.

v0.59: DVI *latex*, MATHJAX, asymptote, pdftricks and pstricks, epstopdf, brqen.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, **recompile any existing project a single time** using `pdfLatex filename.tex` or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- Added an error if `lwarpmk.conf`'s format has changed and the document must be recompiled.
- Added a warning if the `lwarpmk.conf` configuration file appears to be for the wrong operating system, in case files are transferred between systems.
- Added

```
lwarpmk epstopdf <list-of-EPS-files>
```

to quickly convert a document's EPS images to PDF or SVG. See section 8.8.

DVI *latex*

latexmk

math

- Added support for DVI *latex*. See section 7.5.
- Fix for `--shell-escape` with *latexmk*.
- Updated MathJax script to v2.7.4.
- Fix: Mathjax chapter number removed from non-numeric tagged equations.
- Added MathJax support for nicefrac, units.
- Fix for `\[` and `\]` with `\displaymathnormal`.

- images
 - Fix for `\includegraphics` filename expansion.
 - `\includegraphics` now works with `.pdf` and `.eps` filename extensions.
- packages
 - Moved `amsmath` out of the `lwarp` core.
 - Fix for `chemformula \NMR`.
 - Added `asymptote`, `pdftricks`, `pstricks`, `pst-eps`.
 - Added `breqn`, `Slunits`.
 - Added `bxpapersize`, `canoniclayout`, `draftcopy`, `fnbreak`, `nccfancyhdr`.
 - Added `accsupp`, `axessibility`.
 - Added `xunicode`.
 - Improved and now supports `epstopdf`.
 - Tested to work as-is: `eepic`, `sepfootnotes`.
- docs
 - Added information about setting up a development version of `lwarp`.

v0.58: Extensive improvements in indexing, glossaries. Adds PDF-inclusion packages.



Reset the configuration

- Due to changes in `lwarpmk`, **recompile any existing project a single time** using `pdf latex filename.tex` or similar, after which `lwarpmk` may then be used with the new configuration files.

`lwarpmk`

glossaries

- `lwarpmk`: Added the `-p` option to specify the project name.
- `lwarpmk`: Now uses `makeglossaries` for glossary generation, allowing the processing of multiple glossaries at once.
- Added `lwarp` option `GlossaryCmd` to specify the shell command used by `lwarpmk printglossary` and `lwarpmk htmlglossary`. Defaults to `makeglossaries`.

index and glossary

- Docs: Extra indexing options. See section 8.6.14.
- Added support for `makeindex`. (Previously supported only `xindy`.) Also added indexing packages listed below.
- Added `lwarp` options `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to specify shell commands used by `lwarpmk printindex`, `lwarpmk htmlindex`, and `latexmk`. May be preset with the `makeindex` or `xindy` `lwarp` options. See section 7.5.
- Added `lwarp` options `makeindex` and `xindy` to set `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to sensible values for a typical single index. See section 7.5.
- Added `lwarp` option `makeindexStyle` to tell `lwarpmk` to use a custom style instead of `lwarp.ist`. See section 8.6.20.

misc. fixes

- Fix for index entries with `\see`, `\seealso`, `\emph`, `\textbf`, etc.
- Replaced each `\csuse` with `\@nameuse` for improved error detection.
- Additional internal print/HTML macro selection improvements.

packages

- Fix: `\printindex` finishes pending `\index` writes first.
- Fixes for `memoir`: `makeidx`, `ccaption`, multiple indexes, `\specialindex`.
- Fixes for `komascript`: Indexing improvements.
- Added `imakeidx`, `index`, `repeatindex`, `splitidx`.
- Added `attachfile`, `attachfile2`, `intopdf`, `pdfpages`, `pdfx`.
- Added `cases`.
- Tested to work as-is: `notes2bib`, `hvinde`.

v0.57: algorithm2e, float styles, tabular packages, internal improvements.

MathJax

math macros

dynamic math

 new name

lateximage alt tags

- Added support for MathJax equations with `\footnote`, `\footnotemark`.
- Added `\StartDefiningMath` and `\StopDefiningMath` for use when defining macros in the preamble which contain `$`. See section 8.7.7.
- Added `\inlinemathother` and `\inlinemathnormal` to delimit math expressions which depend on a variable condition such as a counter. Such expressions will not be hashed for reuse, and will be converted to SVG math images even when MathJax is enabled. See section 8.7.8.
- Renamed `\EndDefiningTabulars` to `\StopDefiningTabulars`.
- Improved localization for `lateximage` HTML alt tags. For SVG math images, the alt tag under some conditions will be set to `\MathImageAltText`, which defaults to `math image`. For packages, the alt tag is set using the package name followed by `\PackageDiagramAltText`, which defaults to `diagram`. Ex:

`(-xy- diagram)`

See section 7.6.

misc. fixes

packages

- Fix: Improved print/HTML macro selection.
- Fix: `\href` text catcodes.
- Fix: `\subref` text.
- Fixes: Colored `\rule` and `\boxframe`.
- `float`, `rotfloat`: Adds support for float styles `ruled` and `boxed`.
- `float`: Fix: Do not create `\l@<type>` until `\listof` is used.
- `marginnote`: Fix: Long optional argument.
- `ellipsis`: Adds `\midwordellipsis`.
- `breakurl`: Fix for text catcodes.
- Added `algorithm2e`, `register`, `ltablex`, `xltabular`, `xellipsis`, `trimclip`, `errata`, `vowel`, `xpiano`.
- Prevents `glossary`.
- Tested to work as-is with `gauss`, `phonrule`, `piano`, `Slunits`, `tikzcodeblocks`.

v0.56: Shell escape, tabular packages.

lwarpmk

tabular

misc. fixes

- Added `lwarpmk pdftosvg <list-of-PDF-files>` to quickly convert a document's PDF images to SVG, for use with HTML. See section 8.8.
- Added support for `--shell-escape`. See section 7.3.
- Added support for `array w` and `W` columns.
- Fix: `\multicolumn` parameter handling.
- Added support for double `\hlines`, `\midrules`, and vertical rules.
- Added support for `arydshln` dashed lines with HTML `tabular`, but reverts to plain rules for `lateximage` and `SVG math array`.
- Fix: `\thinspace`.

- Fix: paralist compact environments.
- Added parnotes, quoting, lua-check-hyphen, tocenter, underscore.
- Added bibunits.
- Tested to work as-is with babelbib, bodegraph, fast-diagram, nicematrix, structmech.

v0.55: Various fixes.

- misc fixes**
 - Fix: Extraneous space in file links, which also prevented *Calibre* EPUB conversions.
 - Fix: Float optional argument regression.
 - Fix: \ForceHTMLTOC with \phantomsection.
 - Fix: Overfull boxes in lateximages.
 - Fix: QED symbols in lateximage.
- packages**
 - koma-script: Fix: Figure with \centering, etc.
 - Added clrdblpg.

v0.54: Float \centering, improved image checks.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, **recompile any existing project a single time** using `pdfLatex filename.tex` or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- *lwarpmk* `limages` checks for the presence of the HTML version of the document and valid image references before attempting to create the `lateximages`.
- *lwarpmk*: Improved error message if configuration file does not exist.

BibTeX

- Added documentation for avoiding error with BibTeX and `\eta\lchar`. See section 8.6.9.

polyglossia

- Added documentation regarding polyglossia. See section 8.15.4.

macros in section names

- Added documentation regarding the use of macros in section names. See section 8.1.

document encoding

⚠ New and revised encoding options

- Renamed and added package options:

Old Package Option	New Package Option
<code>xdyFilename</code>	<code>xindyStyle</code>
<code>IndexLanguage</code>	<code>xindyLanguage</code>
–	<code>xindyCodepage</code>
–	<code>pdftotextEnc</code>

Use these options along with `inputenc` or `inputenx` to process documents in an encoding other than UTF-8. See section 7.4.

floats with \centering, etc.

- Floats now honor `\centering`, `\raggedright`, `\raggedleft`, and their `ragged2e` equivalents, when placed directly after:

```
\begin{floattype}
\centering
```

misc. fixes

- `tikz`: `\pgfpicture`, `fit`, `align`, `font`.

- `ragged2e`: `\centering` etc.
 - `hyperref`: `\hypertarget` was creating duplicate of `\label`.
 - `hyperref`: Active chars inside `\hyperref`, `\hyperlink`.
 - `hyperref`: `\ref` inside `\hyperlink` caused a nested HTML link.
 - `glossaries`: Fix when not using `babel` or `polyglossia`.
 - `textcomp`: `\textperthousand`.
 - L^AT_EX core `verse` environment: line spacing.
 - Removed `\citetitle`, adjusted `\attribution`.
 - `memoir`: Minor update for v3.7g.
 - Added `inputenx`, `bibunits`, `chngpage`, `forest`, `magaz`, `gridset`.
 - Prevents loading `ae`, `aecc`, `t1enc`, and `wasysym`.
- v0.53:** Improved image checks.
- `lwarpmk`: Added a warning about corrupted images due to the need to recompile the document one more time.
 - `lwarpmk`: Added the `lwarpmk cleanimages` command.
 - Added documentation for `lwarpmk cleanimages` and `lwarpmk pdftohtml`.
- v0.52:** Improved footnotes, SVG math.
- Improved install instructions regarding `lwarp_baseline_marker.png`.
 - Added documentation regarding footnotes in section headings, and footnotes with `\VerbatimFootnotes` from `fancybox`, `fancyvrb`. See section 8.5.4.
 - Added documentation regarding font selection when using X_YL^AT_EX or LuaL^AT_EX with `fontspec` and traditional font packages. See section 7.4.
 - Fix: Limit the number of background tasks when generating `lateximages`.
 - Added user-adjustable SVG math font scaling. See section 82.3.
 - Added warnings if `lwarp_baseline_marker.png` is not present, or if `graphicx` or `graphics` is not loaded.
 - Improved `\ensuremath` hashing expansion.
 - Fix: `equation*` with `split`.
 - `tabbing` now works inside a `lateximage`. Use for math in `tabbing`.
 - Fix: MathJax script was not executing in some conditions.
 - Added `\CustomizeMathJax` to add custom functions. See section 8.7.
 - Fix: Footnote numbering when using `HTMLDebugComments`.
 - Fix: Footnote paragraph tags.
 - Fix: `FootnoteDepth` defaults to `\subsubsection`.
 - Fix: `\kill` in a `lateximage`.
 - Fix: `\FileDepth`, misc. others, when input encoding is not `utf8`.
 - Fix: `\texorpdfstring` in a section name.
 - `hyperref` emulation: Fix for `#`, `%`, `&`, `~`, `_` characters in URLs.
 - `fancybox`, `fancyvrb`: Initial support for `\VerbatimFootnotes`.

- nicefrac: Added with fix for `\ensuremath`.
- graphicx: Fix for option defaults. Added v1.1a/b options.
- endfloat: Updated for v2.6.
- url: Fixes for active characters.

v0.51: Improved svg math, added numerous chemistry packages.

documentation

- Docs: Added **Things to avoid**.
- Docs: Added to **Converting an existing document**.
- Docs: Multiple authors and affiliations with custom classes. See section **8.6.1**.
- Docs: tikz with matrices. See section **8.8.1**.

SVG math

- Improved svg math baseline.
- Improved svg math font and color.
- Faster svg math rendering.
- Improved support for display math containing complicated math objects, such as tikz-cd. See section **8.7.9**.
- Fix: `\addcontentsline` inside svg math.
- Fix: SVG math containing an embedded `lateximage`.

MathJax

misc. fixes

- MathJax now handles `\ensuremath` in expressions.
- Fix: Added `alignat` environment.
- Fix: `afterpackage` no longer required, which conflicted with `scrfile`.
- Fix: `titling` `\thanks` mark.
- Fix: `fancybox` improvements.
- Fix: `tikz` `\tikz` macro. (Previously only the `tikzpicture` environment worked.)
- Fix: `tikz` with optional argument.

packages

- Added `mhchem`, `chemfig`, `chemformula`, `chemmacros`, `chemnum`, `chemgreek`, `epstopdf-base`, `grid`, `ltxgrid`.

2 Introduction

The `lwarp` project aims to allow a rich \LaTeX document to be converted to a reasonable `HTML5` interpretation, with only minor intervention on the user's part. No attempt has been made to force \LaTeX to provide for every `HTML`-related possibility, and `HTML` cannot exactly render every possible \LaTeX concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the `HTML` conversion.

Several “modern” features of `HTML5`, `CSS3`, and `SVG` are employed to allow a fairly feature-rich document without relying on the use of `JAVASCRIPT`. Limited testing on older browsers shows that these new features degrade gracefully.

`lwarp` is a native \LaTeX package, and operates by either patching or emulating various functions. Source-level compatibility is a major goal, but occasional user intervention is required in certain cases.

As a package running directly in \LaTeX , `lwarp` has some advantages over other methods of `HTML` conversion. `TEX` itself is still used, allowing a wider range of `TEX` trickery to be understood. Lua expressions are still available with `LuaTeX`. Entire categories of \LaTeX packages work as-is when used with `lwarp`: definitions, file handling, utilities, internal data structures and calculations, specialized math-mode typesetting for various fields of science and engineering, and anything generating plain-text output. Blocks of `PDF` output may be automatically converted to `SVG` images while using the same font and spacing as the original print document, directly supporting `Tikz` and `picture`. Numerous packages are easily adapted for `HTML` versions, either by loading and patching the originals, or by creating nullified or emulated replacements, and all without resorting to external programming. As a result, several hundred packages have already been adapted (table 2), and an uncounted number more work as-is.

Packages have been selected according to several criteria: perceived importance, popularity lists, recent CTAN updates, CTAN topics, mention in other packages, support by other `HTML` conversion methods, and from sample documents taken from public archives. These include some “obsolete” packages as well.¹

Assistance is also provided for modifying the `HTML` output to suit the creation of `EPUB` documents, and for modifying the `HTML` output to ease import into a word processor.

`pdflatex`, `xelatex`, or `lualatex` may be used, allowing `lwarp` to process the usual image formats. While generating `HTML` output, `SVG` files are used in place of `PDF`. Other formats such as `PNG` and `JPG` are used as-is.

¹An amazing number of decades-old packages are still in use today.

SVG images may be used for math, and are also used for `picture`, `Tikz`, and similar environments. The `svg` format has better browser and e-book support than `MathML` (as of this writing), while still allowing for high-quality display and printing of images (again, subject to potentially bug-ridden² browser support).

Furthermore, `svg` images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by `<alt>` tags holding the `LATEX` source for the expression, allowing it to be copy/pasted into other documents.³ Custom `LATEX` macros may be used as-is in math expressions, since the math is evaluated entirely inside `LATEX`. An MD5 hash is used to combine multiple instances of the same inline math expression into a single image file, which then needs to be converted to `svg` only a single time.

The `MATHJAX` JavaScript display engine may be selected for math display instead of using `svg` images. Subject to browser support and Internet access, `MATHJAX` allows an `HTML` page to display math without relying on a large number of external image files.⁴ `lwarp` maintains `LATEX` control for cross-referencing and equation numbering, and attempts to force `MATHJAX` to tag equations accordingly.

A `texlua` program called `lwarpmk` is used to process either the print or `HTML` version of the document. A few external utility programs are used to finish the conversion from a `LATEX`-generated `PDF` file which happens to have `HTML5` tags, to a number of `HTML5` plain-text files and accompanying images.

`lwarp` automatically generates the extra files necessary for the `HTML` conversion, such as `css` and `.xdy` files, and configuration files for the utility `lwarpmk`. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects `HTML` output and then inputs the user's own source. This process allows both the printed and `HTML` versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during `HTML` conversion, `lwarp` first looks to see if it has its own modified version to use instead of the standard `LATEX` version. These `lwarp-packagename.sty` files contain code used to emulate or replace functions for `HTML` output.

²`FIREFOX` has had an on-again/off-again bug for quite some time regarding printing `svgs` at high resolution.

³There seems to be some debate as to whether `MathML` is actually an improvement over `LATEX` for sharing math. The author has no particular opinion on the matter, except to say that in this case `LATEX` is much easier to implement!

⁴One `svg` image file per math expression, except that duplicate inline math expressions are combined into a single file according to the MD5 hash function of its contents. A common scientific paper can easily include several thousand files, and in one case the MD5 hash cut the number of files in half and the rendering time by 30%.

2.1 Typesetting conventions

Font weight, family, and style are used to indicate various objects:

Table 1: Typesetting conventions

package	L ^A T _E X package.
<i>program</i>	Program's executable name.
option	Program or package option.
filename	File name in the operating system.
BRAND NAME	Proper name for a program, operating system, etc.
commands	Commands to be entered by the user.
code	Program code.
\macroname	L ^A T _E X macro.
environment	L ^A T _E X environment.
counter	L ^A T _E X counter.
boolean	L ^A T _E X boolean.
<element>	HTML element.
attribute	HTML attribute.
User Interface	A user-interface item.
ACRO	Acronym.

2.2 Supported packages and features

Table 2 lists some of the various L^AT_EX features and packages which may be used.

Package names are colored according to their support level:

name: Supported as-is.

name: Modified to work with HTML output, and perhaps also as print output in `svg` `math` or `lateximage` environments.

name: Emulated for HTML output.

name: Ignored for HTML output, but provides source-level compatibility.

MJ: Supported as-is for MATHJAX, subject to limitations.

MJ: Emulated for MATHJAX using custom macros, subject to limitations.

MJ: Ignored by MATHJAX, but may be used in the document source.

Table 2: L^AT_EX lwarp package — Supported features

Category	Status and supported features.
Engines:	DVI L ^A T _E X, pdfL ^A T _E X, X _Y L ^A T _E X, LuaL ^A T _E X, upL ^A T _E X
Compiling:	<i>latexmk</i> , <i>perltex</i> , <i>pythontex</i> , <i>make</i> , etc.
Classes:	article, book, report, scrartcl, scrbook, screprt, memoir, CJK-related as listed below.
Koma-script:	scxextend , scrhack , scrlayer . Others as listed below.
Memoir:	memhfixc
Languages:	babel , polyglossia . ckjpunct , xeCJK .
Chinese:	CTEX, ctex , upzhkinsoku , xpinyin , zhlineskip , zhspacing .
Japanese:	upL ^A T _E X, LuaT _E X-ja, gentombow , lltjext , plarray , plarydshln , plautopatch , plext , plextarray , plextarydshln , plextcolortbl , plextdelarray , pxatbegshi , pxeveryshi , pxftnright , pxgentombow , pxjahyper , pxpdfpages , pxpgfrcs , pxpgfmark , tascmac , zxjatype . bxjsarticle and related, ltjsarticle and related, luatexja , luatexja-fontspec , ujarticle and related, utarticle and related.
Korean:	kotex , luatexko , xetexko .

lwarp Supported Functions — continued

Category	Status
Page layout:	2in1, 2up, a4, a4wide, a5comb, addlines, anysize, atbegshi , blowup, booklet, bophook, bounddvi, bxpapersize, canoniclayout, changelayout , changepage , chngpage, clrdblpg, continue, draftcopy, drafftfigure, draftwatermark, ebook, everyshi, fancyhdr , fancytabs, flippdf, fullminipage, fullpage, fwlw, geometry, gmeometric, grid, grid-system , gridset, layaureo, layout, layouts, leading, ltxgrid, nccfancyhdr, notespages, nowidow, pagegrid, pagesel, parallel , parcolumns , pdfcolparallel, pdfcolparcolumns, pdfcrypt, pdfprivacy, preview, ragged2e , returntogrid, rmpage, scrlayer-scrpage , scrpage2 , setspace , selectp, textarea, threadcol, thumb, thumbs, titles, tocenter, turnthepage, twoup, typearea, underlin, vmargin, watermark, widows-and-orphans, zwpagelayout.
Sectioning:	Adds FileDepth for splitting the HTML output. Files may be numbered sequentially or named according to section name. Common short words and punctuation are removed from the file names. anonchap , bsheaders, fncychap, hypbmsc , indentfirst , quotchap , section, sectionbreak , secdot , sectsty, titlesec, tocvsec2 .
Table of contents, figures, tables:	Supported, with hyperlinks. etoc, minitoc, multitoc, shorttoc , tableof , titletoc, tocbasic, tocbibind , tocdata , tocloft, tocstyle, tocvsec2 .
Title page:	<code>\maketitle</code> , titlepage, authblk , authaftertitle , titling .
Front & back matter:	abstract , appendix .
Indexing:	makeindex , xindy , and xindex are supported, with hyperlinks. gindex , hvindex , idxlayout , imakeidx , index , makeidx , repeatindex , splitidx , varindex , xindex .
Glossary:	gloss , glossaries and xindy , nomencl .
Bibliography:	babelbib , bibtopic , backref , biblatex , bibunits , chapterbib , cite , citeref , collref , drftcite , hypernat , jurabib , mcite , mciteplus , multibib , natbib , notes2bib , splitbib , showtags .

lwarp Supported Functions — continued

Category	Status
Cross-references:	bookmark, breakurl , cleveref , fancyref , hypdestopt , hyperref , perpage , prettyref , titleref , url , varioref , xcite , xr , xr-hyper , xurl , zref .
Margin notes:	marginal , marginfit , marginfix , sclayer-notecolumn , versonotes .
Footnotes:	Adds FootnoteDepth to print footnotes at section breaks. MATHJAX emulation for <code>\footnote</code> , and also as marked in the following: bigfoot , dblfnote , endheads , endnotes^{MJ} , fixfoot , fnbreak , fnpara , fnpos , footmisc , footnote , footnotebackref , footnoterange , footnpag , manyfoot , marginnote^{MJ} , nccfoots^{MJ} , pagenote^{MJ} , parnotes^{MJ} , pdfcolfoot , pfnote , sepfootnotes , sidenotes^{MJ} , tablefootnote .
Math:	Converted to SVG images with HTML <code><alt></code> tags containing the L ^A T _E X source for the math expression. MATHJAX supported as an alternative. amsmath^{MJ} : $\mathcal{A}\mathcal{M}\mathcal{S}$ environments are supported. User-defined macros are available during conversion, due to native L ^A T _E X processing.
Theorems:	Native L ^A T _E X theorems, amsthm , apxproof , nththeorem , shadethm , theorem , thmbox , thmtools .
Additional math:	Math fonts via SVG images, accents^{MJ} , amscd , autobreak^{MJ} , autonum , backnaur , bm^{MJ} , braket^{MJ} , breqn , bussproofs^{MJ} , cases , centernot^{MJ} , cmbright^{MJ} , colonequals^{MJ} , decimal^{MJ} , delarray , DotArrow^{MJ} , dotlessi^{MJ} , dotlessj^{MJ} , esvect^{MJ} , extrarrows^{MJ} , fixmath^{MJ} , fouridx^{MJ} , fourier^{MJ} , guass , hhtensor^{MJ} , icomma^{MJ} , jkmath , kpfonts^{MJ} , kpfonts-otf^{MJ} , leftidx^{MJ} , libertinust1math^{MJ} , mathalpha^{MJ} , mathastext^{MJ} , mathcomp^{MJ} , mathdesign^{MJ} , mathdots^{MJ} , mathfixs^{MJ} , mathpazo^{MJ} , mathptmx^{MJ} , mathpunctspace^{MJ} , mathspec^{MJ} , mathtools^{MJ} , mismath^{MJ} , mleftright^{MJ} , multiobjective^{MJ} , nccmath^{MJ} , nicematrix , noitcrul^{MJ} , newpxmath^{MJ} , newtxmath^{MJ} , newtxsf^{MJ} , pb-diagram , pxfonts^{MJ} , resizegather , rmathbr^{MJ} , scalarel^{MJ} , shuffle^{MJ} , stackrel^{MJ} , statex2^{MJ} , statistics , statmath^{MJ} , subsupscripts^{MJ} , textualicomma^{MJ} , txfonts^{MJ} , txgreeks^{MJ} , unicode-math^{MJ} , upgreek^{MJ} , ushort^{MJ} , witharrows^{MJ} , xfakebold^{MJ} , xy . Many others work as-is.
Display math with <code>\displaymath</code> or <code>\displaymathother</code> :	Complicated math objects in display math, such as tikz-cd , etc.

lwarp Supported Functions — continued

Category	Status
Units and fractions:	<code>nicefrac^{MJ}</code> , <code>Slunits^{MJ}</code> , <code>siunitx^{MJ}</code> , <code>units^{MJ}</code> , <code>unitsdef</code> , <code>xfrac^{MJ}</code> .
Floats:	Appear where declared. <code>capt-of</code> , <code>caption</code> , <code>cutwin</code> , <code>dblfloatfix</code> , <code>endfloat</code> , <code>fewerfloatpages</code> , <code>fix2col</code> , <code>flafter</code> , <code>float</code> , <code>floatflt</code> , <code>floatrow</code> , <code>fltrace</code> , <code>ftcap</code> , <code>hycap</code> , <code>keyfloat</code> , <code>morefloats</code> , <code>multicap</code> , <code>newfloat</code> , <code>nonfloat</code> , <code>picinpar</code> , <code>placeins</code> , <code>rotfloat</code> , <code>stfloats</code> , <code>subcaption</code> , <code>subfig</code> , <code>subfigure</code> , <code>subfloat</code> , <code>swfigure</code> , <code>topcapt</code> , <code>trivfloat</code> , <code>wrapfig</code> .
Tabular:	<code>tabular</code> environment, <code>array^{MJ}</code> , <code>arydshln^{MJ}</code> , <code>bigdelim^{MJ}</code> , <code>bigstrut^{MJ}</code> , <code>booktabs^{MJ}</code> , <code>colortbl</code> , <code>ctable</code> , <code>diagbox</code> , <code>hhline^{MJ}</code> , <code>longtable</code> , <code>ltablex</code> , <code>ltxtable</code> , <code>multirow^{MJ}</code> , <code>supertabular</code> , <code>tabularx</code> , <code>tabulary</code> , <code>threeparttable</code> , <code>threeparttablex</code> , <code>widetable</code> , <code>xltabular</code> , <code>xtab</code> .
Graphics:	<code>graphics</code> and <code>graphicx</code> . <code>\includegraphics</code> supports width, height, origin, angle, and scale tags, and adds class. References to PDF files are changed to SVG, other image types are accepted as well. <code>\rotatebox</code> and <code>\scalebox</code> are supported as well as HTML can handle. <code>rotating</code> is emulated but all objects are unrotated. <code>picture</code> , <code>tikz</code> , and <code>xy</code> are converted to an SVG image. <code>asymptote</code> , <code>curves</code> , <code>datatool</code> , <code>eepic</code> , <code>epsfig</code> , <code>epstopdf</code> , <code>figsize</code> , <code>fitbox</code> , <code>grffile</code> , <code>luamplib</code> , <code>media9</code> , <code>movie15</code> , <code>multimedia</code> , <code>overpic</code> , <code>pict2e</code> , <code>psfrag</code> , <code>psfragx</code> , <code>pst-eps</code> , <code>pstool</code> , <code>pstricks</code> , <code>rviewport</code> , <code>svg</code> , <code>svg-extract</code> , <code>tikz-3dplot</code> .
<code>xcolor</code> :	Full package color names, any color models, and mixing. <code>\textcolor</code> , <code>\colorbox</code> , <code>\fcolorbox</code> . Enhanced for HTML compatibility.
Lists:	Standard L ^A T _E X environments, <code>enumerate</code> , <code>enumitem</code> , <code>eqlist</code> , <code>hang</code> , <code>listliketab</code> , <code>paralist</code> .
Environments:	Standard L ^A T _E X environments.
<code>minipage</code> , <code>\parbox</code> :	Some HTML5-imposed limitations. Nested minipages are supported. <code>eqparbox</code> , <code>minibox</code> , <code>pbox</code> , <code>shapepar</code> .
Quotations:	<code>copyrightbox</code> , <code>csquotes</code> , <code>epigraph</code> , <code>quoting</code> , <code>verse</code> .
Verbatim:	<code>fancyvrb</code> , <code>fvextra</code> , <code>moreverb</code> , <code>shortvrb</code> , <code>verbatim</code> .

lwarp Supported Functions — continued

Category	Status
Frames:	<code>boxedminipage</code> , <code>boxedminipage2e</code> , <code>fancybox</code> , <code>fbox^{MJ}</code> , <code>framed</code> , <code>mdframed</code> , <code>niceframe</code> , <code>shadow</code> , <code>tcolorbox^{MJ}</code> , <code>vertbars</code> .
Multi-columns:	<code>adjmulticol</code> , <code>multicol</code> , <code>multicolrule</code> , <code>vwcol</code> .
Margins:	<code>fullwidth</code> , <code>hanging</code> , <code>midpage</code> .
Line numbering:	<code>fnlineno</code> , <code>lineno</code> .
Direct formatting:	<code>\emph</code> , <code>\textsuperscript</code> , <code>\textbf</code> , etc are supported. <code>\bfseries</code> , etc. are only supported in some cases. <code>cancel^{MJ}</code> , <code>ellipsis</code> , <code>embrace</code> , <code>enparen</code> , <code>hyphenat</code> , <code>lettrine</code> , <code>lips</code> , <code>lua-check-hyphen</code> , <code>luacolor</code> , <code>magaz</code> , <code>moresize</code> , <code>nolbreaks</code> , <code>normalcolor</code> , <code>pdfcol</code> , <code>pdfcolmk</code> , <code>pdfrender</code> , <code>realscripts</code> , <code>resize^{MJ}</code> , <code>scalegnt</code> , <code>seqsplit^{MJ}</code> , <code>soul</code> , <code>soulpos</code> , <code>soulutf8</code> , <code>stackengine</code> , <code>textfit</code> , <code>thinsp</code> , <code>trimclip</code> , <code>truncate</code> , <code>ulem</code> , <code>umoline</code> , <code>underscore</code> , <code>uspace</code> , <code>xellipsis</code> .
Acronyms:	<code>acro</code> , <code>acronym</code> .
Ordinals:	<code>engord</code> , <code>fntcount</code> , <code>nth</code> .
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for <code>thin-unbreakable</code> , <code>unbreakable</code> , <code>\enskip</code> , <code>\quad</code> , <code>\qqquad</code> , <code>\hspace</code> .
Rules:	<code>\rule</code> with <code>width</code> , <code>height</code> , <code>raise</code> , <code>text color</code> .
HTML reserved characters:	<code>\&</code> , <code>\textless</code> , and <code>\textgreater</code> are converted to HTML entities.
Fonts:	Used as-is. Appear in SVG math expressions or embedded image environments. <code>fontaxes</code> , <code>nfssect-cfr</code> , <code>slantsc</code> , <code>tabfigures</code> . Tested to work as-is: Special font macros in <code>cfr-lm</code> and others which use <code>nfssect-cfr</code> . Also see the math section for math and MATHJAX support for math font packages.

lwarp Supported Functions — continued

Category	Status
Symbols:	Native L ^A T _E X diacriticals, <code>academicons</code> , <code>amssymb</code> ^{MJ} , <code>bbding</code> , <code>chemgreek</code> , <code>dingbat</code> , <code>euro</code> , <code>eurosym</code> , <code>fontawesome</code> , <code>fontawesome5</code> , <code>gensymb</code> ^{MJ} , <code>latexsym</code> ^{MJ} , <code>marvosym</code> , <code>metalogo</code> , <code>metalogox</code> , <code>pifont</code> , <code>textalpha</code> , <code>textcomp</code> , <code>textgreek</code> , <code>typicons</code> , <code>xunicode</code> .
Files:	<code>attachfile</code> , <code>attachfile2</code> , <code>hyperxmp</code> , <code>inputtrc</code> , <code>intopdf</code> , <code>pdfpages</code> , <code>pdfx</code> , <code>xmpincl</code> .
Science and engineering:	<code>algorithm2e</code> , <code>algorithmicx</code> , <code>ar</code> ^{MJ} , <code>askmaps</code> , <code>axodraw2</code> , <code>bitpattern</code> , <code>blochsphere</code> , <code>bodegraph</code> , <code>bohr</code> , <code>bytefield</code> , <code>chemfig</code> , <code>chemformula</code> , <code>chemgreek</code> , <code>chemmacros</code> , <code>chemnum</code> , <code>circuitikz</code> , <code>econometrics</code> ^{MJ} , <code>elements</code> , <code>engtlc</code> ^{MJ} , <code>fast-diagram</code> , <code>ghsystem</code> , <code>hepnicenames</code> , <code>heppennames</code> , <code>hepunits</code> ^{MJ} , <code>karnaughmap</code> , <code>karnaugh-map</code> , <code>keystroke</code> , <code>listings</code> , <code>listingsutf8</code> , <code>linop</code> , <code>menukeys</code> , <code>mhchem</code> ^{MJ} , <code>minted</code> , <code>pgfgantt</code> , <code>phfqit</code> , <code>physics</code> ^{MJ} , <code>physunits</code> ^{MJ} , <code>plimsoll</code> ^{MJ} , <code>qccircuit</code> , <code>register</code> , <code>simplebnf</code> , <code>simpler-wick</code> , <code>slashed</code> ^{MJ} , <code>steinmetz</code> ^{MJ} , <code>structmech</code> , <code>struktex</code> , <code>syntaxdi</code> , <code>tikz-karnaugh</code> , <code>tikzcodeblocks</code> , <code>venndiagram</code>
Arts and humanities:	<code>foreign</code> , <code>forest</code> , <code>lyluatex</code> , <code>musicography</code> , <code>nameauth</code> , <code>octave</code> , <code>phonrule</code> , <code>piano</code> , <code>schemata</code> , <code>semantic-markup</code> , <code>tikz-dependency</code> , <code>vowel</code> , <code>xpiano</code>
Calendars:	<code>termcal</code>
Admonitions:	<code>awesomebox</code> , <code>notes</code> .
Editorial:	<code>changebar</code> , <code>changelog</code> , <code>changes</code> , <code>easy-todo</code> , <code>easyReview</code> , <code>ed</code> , <code>errata</code> , <code>fixme</code> , <code>fixmetodonotes</code> , <code>pdfcomment</code> ^{MJ} , <code>pdfmarginpar</code> , <code>todo</code> , <code>todonotes</code> , <code>tram</code> , <code>xchangebar</code> .
Accessibility:	<code>accessibility</code> ^{MJ} , <code>accsupp</code> ^{MJ} , <code>axessibility</code> ^{MJ} , <code>pdfcomment</code> ^{MJ} , <code>repltext</code> ^{MJ} , <code>tagpdf</code> .
Package handling:	<code>catoptions</code> .
Debug:	<code>chkfloat</code> , <code>cmdtrack</code> , <code>dprogress</code> , <code>lua-visual-debug</code> , <code>refcheck</code> , <code>srcltx</code> , <code>srtex</code> , <code>vpe</code> , <code>xbmks</code> .

lwarp Supported Functions — continued

Category	Status
Working as-is:	Various utility, calculation, file, and text-only packages, such as <code>calc</code> , <code>fileerr</code> , <code>somedefs</code> , <code>trace</code> , <code>xspace</code> . Also, most math-only packages, including specialized typesetting for various fields of science and engineering.

3 Alternatives

Summarized below are several other ways to convert a \LaTeX or other document to HTML. Where an existing \LaTeX document is to be converted to HTML, `lwarp` may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

3.1 internet class

Cls `internet` The closest to `lwarp` in design principle is the `internet` class by Andrew Stacey—an interesting project which directly produces several versions of markdown, and also HTML and EPUB. <https://github.com/loopspace/latex-to-internet>

3.2 TeX4HT

Prog `TeX4ht` <http://tug.org/tex4ht/>
 Prog `htlatex`

This system uses native \LaTeX processing to produce a DVI file containing special commands, and then uses additional post-processing for the HTML conversion by way of numerous configuration files. In some cases `lwarp` provides a better HTML conversion, and it supports a different set of packages. `TeX4ht` produces several other forms of output beyond HTML, including ODT and a direct path to EPUB, and is still being developed.

3.3 Translators

These systems use external programs to translate a subset of \LaTeX syntax into HTML. Search for each on CTAN (<http://ctan.org>).

Prog `Hevea` **H^Ev^Ea**: <http://hevea.inria.fr/> (not on CTAN)
 Prog `TtH` **T_TH**: <http://hutchinson.belmont.ma.us/tth/>
 Prog `GELLMU` **GELLMU**: <http://www.albany.edu/~hammond/gellmu/>
 Prog `LaTeXML` **LaTeXML**: <http://dlmf.nist.gov/LaTeXML/>
 Prog `Plastex` **PlasTeX**: <https://github.com/tiarno/plastex>
 Prog `LaTeX2HTML` **LaTeX2HTML**: <http://www.latex2html.org/>
 and <http://ctan.org/pkg/latex2html>.
 Prog `TeX2page` **TeX2page**: <http://ds26gte.github.io/tex2page/index.html>

Finally, `GladTeX` may used to directly insert \LaTeX math into HTML:

Prog `GLadTeX` **GLadTeX**: <http://humenda.github.io/GLadTeX/>

3.4 ASCII DOC and ASCIIDOCTOR

AsciiDoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes L^AT_EX and HTML.

Prog AsciiDoc **Asciidoctor:** <http://asciidoctor.org/> (More active.)

Prog AsciiDoctor **AsciiDoc:** <http://asciidoc.org/> (The original project.)

3.4.1 ASCIIDOCTOR-L^AT_EX

The Asciidoctor-LaTeX project is developing additional L^AT_EX-related features.

Asciidoctor-Lat_EX:

<http://www.noteshare.io/book/asciidoctor-latex-manual>

Prog AsciiDoctor-LaTeX <https://github.com/asciidoctor/asciidoctor-latex>

3.5 PANDOC

Prog Pandoc A markup system which also reads and writes L^AT_EX and HTML.

Pandoc: <http://pandoc.org/>

(Watch for improvements in cross-references to figures and tables.)

3.6 Word processors

Prog Word It should be noted that the popular word processors have advanced through the years
 Prog LibreOffice in their abilities to represent math with a L^AT_EX-ish input syntax, unicode math fonts,
 Prog OpenOffice and high-quality output, and also generate HTML with varying success. See recent
 developments in MICROSOFT[®] *Word*[®] and LIBREOFFICE[™] *Writer*.

3.7 Commercial systems

Prog Adobe Likewise, several professional systems exist whose abilities have been advancing
 Prog FrameMaker in the areas of typesetting, cross-referencing, and HTML generation. See ADOBE[®]
 Prog InDesign *FrameMaker*[®], ADOBE *InDesign*[®], and MADCAP *Flare*[™].

Prog Flare

Prog Madcap

3.8 Comparisons

AsciiDoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to

require many combinations of special characters, resulting in a complicated mess of syntax. By contrast, \LaTeX spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that \LaTeX is comparably easy to learn, while \LaTeX provides many more advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of \LaTeX vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a \LaTeX back end, yielding high-quality results especially when the \LaTeX template is adjusted, but they lose the ability to use \LaTeX macros and other \LaTeX source-document features.

The effort required to customize the output of each markup system varies. For print output, \LaTeX configuration files are usually used. For HTML output, a CSS file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of `lwarp`, CSS is used, and much HTML output is adjusted through the usual \LaTeX optional macro parameters, but further customization may require patching \LaTeX code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

4 Installation

Table 3 shows the tools which are used for the L^AT_EX to HTML conversion. In most cases, these will be available via the standard package-installation tools.

Detailed installation instructions follow.

Table 3: Required software programs

Provided by your L^AT_EX distribution:

From T_EXLive: <http://tug.org/texlive/>.

L^AT_EX: *pdflatex*, *xelatex*, or *lua_latex*.

The lwarp package: This package.

The *lwarpmk* utility: Provided along with this package. This should be an operating-system executable in the same way that *pdflatex* or *latexmk* is. It is possible to have the *lwarp* package generate a local copy of *lwarpmk* called *lwarpmk.lua*. See table 4.

***lua_ltex*:** Used by the *lwarpmk* program to simplify and automate document generation.

***xindy*:** The *xindy* program is used by *lwarp* to create indexes. On a MiK_TE_X system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

***latexmk*:** Optionally used by *lwarpmk* to compile L^AT_EX code. On a MiK_TE_X system, *Perl* may need to be installed first.

***pdfcrop*:** Used to pull images out of the L^AT_EX PDF.

POPPLER PDF utilities:

***pdftotext*:** Used to convert PDF to text.

***pdfseparate*:** Used to pull images out of the L^AT_EX PDF.

***pdftocairo*:** Used to convert images to SVG.

These might be provided by your operating-system package manager, and MiK_TE_X provides *miktex-poppler-bin-** packages.

From POPPLER: poppler.freedesktop.org.

For MACOS[®], see <https://brew.sh/>, install *Homebrew*, then

```
Enter ⇒ brew install poppler
```

For WINDOWS, see MiK_TE_X *miktex-poppler-bin-**, or:

<https://sourceforge.net/projects/poppler-win32/> and:

<http://blog.alivate.com.au/poppler-windows/>

Perl:

This may be provided by your operating-system package manager, and may be required for some of the POPPLER PDF utilities.

strawberryperl.com (recommended), perl.org

Automatically downloaded from the internet as required:

MATHJAX: Optionally used to display math. From: mathjax.org

4.1 Installing the lwarp package

There are several ways to install lwarp. These are listed here with the preferred methods listed first:

Pre-installed: Try entering into a command line:

```
Enter ⇒ kpsewhich lwarp.sty
```

If a path to lwarp.sty is shown, then lwarp is already installed and you may skip to the next section.

TEX Live: If using a TEX Live distribution, try installing via *tlmgr*:

```
Enter ⇒ tlmgr install lwarp
```

MiKTeX:

1. For newer versions of MiKTeX, install or update lwarp using the *MiKTeX Console* program.
2. For older versions of MiKTeX, to install lwarp the first time, use the *MiKTeX Package Manager (Admin)*. To update lwarp, use *MiKTeX Update (Admin)*.
3. Either way, also update the package miktex-misc, which will install and update the *lwarpmk* executable.

Operating-system package: The operating-system package manager may already have lwarp, perhaps as part of a set of TEX-related packages.

CTAN TDS archive: lwarp may be downloaded from the Comprehensive TEX Archive:

1. See <http://ctan.org/pkg/lwarp> for the lwarp package.
2. Download the TDS archive: lwarp.tds.zip
3. Find the TEX local directory:

TEX Live:

```
Enter ⇒ kpsewhich -var-value TEXMFLOCAL
```

MiKTeX:

In the **Settings** window, **Roots** tab, look for a local TDS root.

This should be something like:

```
/usr/local/texlive/texmf-local/
```

4. Unpack the archive in the TDS local directory.
5. Renew the cache:

```
Enter ⇒ mktexlsr
```

— or —

```
Enter ⇒ texhash
```

Or, for WINDOWS MiKTeX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.

CTAN .dtx and .ins files: Another form of TEX package is .dtx and .ins source files. These files are used to create the documentation and .sty files.

1. See <http://ctan.org/pkg/lwarp> for the lwarp package.
2. Download the zip archive `lwarp.zip` into your own lwarp directory.
3. Unpack `lwarp.zip`.
4. Locate the contents `lwarp.dtx` and `lwarp.ins`
5. Create the `.sty` files:
 Enter ⇒ **pdflatex lwarp.ins**
6. Create the documentation:

```
pdflatex lwarp.dtx (several times)
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
makeindex -s gind.ist lwarp.idx
pdflatex lwarp.dtx (several times)
```

7. Copy the `.sty` files somewhere such as the T_EX Live local tree found in the previous CTAN TDS section, under the subdirectory:
 `<texlocal>/tex/latex/local/lwarp`
8. Copy `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` to the same place as the `.sty` files.
9. Copy the documentation `lwarp.pdf` to a source directory in the local tree, such as:
 `<texlocal>/doc/local/lwarp`
10. Renew the cache:
 Enter ⇒ **mktxlsr**
 — or —
 Enter ⇒ **texhash**
 Or, for WINDOWS MiKTeX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.
11. See section 4.2.1 to generate your local copy of *lwarpmk*.
12. Once the local version of `lwarpmk.lua` is installed, it may be made available system-wide as per section 4.2.

Project-local CTAN .dtx and .ins files: The `.dtx` and `.ins` files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant `*.sty` and `lwarpmk.lua` files may be used as-is, so long as they are in the same directory as the document source. The files `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` must also be copied as well. This approach is especially useful if you would like to temporarily test lwarp before deciding whether to permanently install it.

Just testing!

4.2 Installing the *lwarpmk* utility

(Note: If *lwarpmk* is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 4.2.1.)

After the lwarp package is installed, you may need to setup the *lwarpmk* utility:

1. At a command line, try executing `lwarpmk`. If the *lwarpmk* help message appears, then *lwarpmk* is already set up. If not, it is easiest to generate and use a local copy. See section 4.2.1.
2. For MiKTeX, try updating the miktex-misc package. This may install the *lwarpmk* executable for you.

Otherwise, continue with the following:

3. Locate the file `lwarpmk.lua`, which should be in the `scripts` directory of the TDS tree. On a T_EX Live or MiKTeX system you may use

```
Enter ⇒ kpsewhich lwarpmk.lua
```

(If the file is not found, you may also generate a local copy and use it instead. See section 4.2.1.)

4. Create *lwarpmk*:

Unix: Create a symbolic link and make it executable:

- (a) Locate the T_EX Live binaries:

```
Enter ⇒ kpsewhich -var-value TEXMFROOT
```

This will be something like:

```
/usr/local/texlive/<year>
```

The binaries are then located in the `bin/<arch>` directory under the root:

```
/usr/local/texlive/<year>/bin/<architecture>/
```

In this directory you will find programs such as *pdflatex* and *makeindex*.

- (b) In the binaries directory, create a new symbolic link from the binaries directory to `lwarpmk.lua`:

```
Enter ⇒ ln -s <pathto>lwarpmk.lua lwarpmk
```

- (c) Make the link executable:

```
Enter ⇒ chmod 0755 lwarpmk
```

WINDOWS T_EX Live: Create a new `lwarpmk.exe` file:

- (a) Locate the T_EX Live binaries as shown above for UNIX.
- (b) In the binaries directory, make a *copy* of `runscript.exe` and call it `lwarpmk.exe`. This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

WINDOWS MiKTeX: Create a new `lwarpmk.bat` file:

- (a) Locate the MiKTeX binaries. These will be in a directory such as:

```
C:\Program Files\MiKTeX 2.9\miktex\bin\x64
```

In this directory you will find programs such as `pdflatex.exe` and `makeindex.exe`.

- (b) Create a new file named `lwarpmk.bat` containing:

```
texlua "C:\Program Files\MiKTeX 2.9\scripts\lwarp\lwarp.texlua" %*
```

This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

4.2.1 Using a local copy of *lwarpmk*

It is also possible to use a local version of *lwarpmk*:

1. When compiling the tutorial in section 5, use the `lwarpmk` option for the `lwarp` package:

```
\usepackage[lwarpmk]{lwarp}
```

2. When the tutorial is compiled with *pdf_latex*, the file `lwarpmk.lua` will be generated along with the other configuration files.
3. `lwarpmk.lua` may be used for this project:

Unix:

- (a) Make `lwarpmk.lua` executable:

```
Enter ⇒ chmod 0755 lwarpmk.lua
```

- (b) Compile documents with

```
Enter ⇒ ./lwarpmk.lua html
```

```
Enter ⇒ ./lwarpmk.lua print
```

etc.

- (c) It may be useful to rename or link to a version without the `.lua` suffix.

WINDOWS:

Compile documents with either of the following, depending on which command shell is being used:

```
Enter ⇒ texlua lwarpmk.lua html
```

```
Enter ⇒ texlua lwarpmk.lua print
```

etc.

Or:

```
Enter ⇒ lwarpmk html
```

```
Enter ⇒ lwarpmk print
```

etc.

4.3 Installing additional utilities

To test for the existence of the additional utilities:

Enter the following in a command line. If each program's version is displayed, then that utility is already installed. See table 3 on page 77.

```
Enter ⇒ luatex --version
```

```
Enter ⇒ xindy --version
```

```
Enter ⇒ latexmk --version
```

```
Enter ⇒ perl --version
```

```
Enter ⇒ pdftocrop --version
```

```
Enter ⇒ pdftotext -v
```

```
Enter ⇒ pdfseparate --version
```

```
Enter ⇒ pdftocairo -v
```

To install *xindy*, *latexmk*, and *pdfcrop*:

The TEX utilities *xindy*, *latexmk*, and *pdfcrop* may be installed in *TeXLive* with *tlmgr*, installed by *MiKTeX*, provided by your operating system's package manager, or downloaded from the *CTAN* archive:

<http://ctan.org/pkg/xindy>

<http://ctan.org/pkg/latexmk>

<http://ctan.org/pkg/pdfcrop>

To install the POPPLER utilities to a UNIX/LINUX system:

The tools from the POPPLER project should be provided by your operating system's package manager.

To install the POPPLER utilities to a MACOS machine:

1. Install *Homebrew* from <https://brew.sh/>:

```
/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"
```

2. Install the POPPLER utilities:

```
Enter ⇒ brew install poppler
```

To install the POPPLER utilities to a WINDOWS machine:

If using MikTeX, install a miktex-poppler-bin-* package. Otherwise:

1. See table 3 on page 77.
2. Download and extract the POPPLER utilities *pdftotext*, *pdfseparate*, and *pdfseparate* to a directory, such as Poppler.
3. In the **Start** window, type "Path" to search for results related to Path. Or, open the control panel and search for "Path".
4. Choose **Edit the system environment variables** in the control panel.
5. Choose the **Environment Variables** button.
6. Choose the **Path** variable, then the **Edit** button.
7. Choose the **New** button to make an additional entry.
8. Enter the bin directory of the POPPLER utilities, such as:

```
C:\Users\\Desktop\Poppler\poppler-0.5_x86\poppler-0.5\bin
```

Be sure to include \bin.

9. Click **Ok** when done.

To install PERL to a WINDOWS machine:

1. Download and install a version of PERL, such as STRAWBERRY PERL, to a directory without a space in its name, such as C:\Strawberry.
2. Edit the **Path** as seen above for the POPPLER utilities.
3. Enter the bin directory of the *perl* utility, such as:

```
C:\Strawberry\perl\bin
```

Be sure to include \bin.

4. Click **Ok** when done.

Any utilities installed by hand must be added to the PATH.

5 Tutorial

This section shows an example of how to create an lwarp document.

Need help?

See the [General Index](#) for “how-to”, and the [Troubleshooting Index](#) if something doesn’t work. A [Troubleshooting](#) section is also available. The [Index of Objects](#) contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

5.1 Starting a new project

1. Create a new project directory called `tutorial`.

File `tutorial.tex`

2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

Copy from the documentation PDF:

A listing is in [fig. 1](#), which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

Copy from the lwarp documentation directory:

Another copy may be found by entering into a command line:

```
Enter ⇒ texdoc -l lwarp_tutorial.tex
```

This should be in the `doc/latex/lwarp/` directory along with this PDF documentation. Copy `lwarp_tutorial.tex` directly into your `tutorial` directory, renamed as `tutorial.tex`.

File `lwarp_tutorial.txt`

 **Note: .txt suffix!**

 **Bad formatting!**

When using WINDOWS, use an editor other than NOTEPAD, since NOTEPAD does not accept the end-of-line from a UNIX text file.

3. Compile the project:

```
Enter ⇒ pdflatex tutorial.tex
```

(several times)

(*xelatex* or *lualatex* may be used as well. lwarp also supports DVI *latex* for use with `.eps` images.)

4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in [table 4](#). These files are created by the lwarp package.

(Two of the new files are configuration files for the helper program *lwarpmk*. Whenever a print version of the document is created, the configuration files for *lwarpmk* are updated to record the operating system, L^AT_EX engine (*latex*, *pdflatex*, *xelatex*, or *lualatex*), the filenames of the source code and HTML output, and whether the additional helper program *latexmk* will be used to compile the document.)

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarp package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern}           % pdflatex or dvi latex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec}         % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
% HomeHTMLFilename=index,     % Filename of the homepage.
% HTMLFilename={node-},       % Filename prefix of other pages.
% IndexLanguage=english,     % Language for xindy index, glossary.
% latexmk,                    % Use latexmk to compile.
% OSWindows,                  % Force Windows. (Usually automatic.)
% mathjax,                    % Use MathJax to display math.
]{lwarp}
% \boolfalse{FileSectionNames} % If false, numbers the files.

% --- LOAD PDFLATEX MATH FONTS HERE ---

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor}   % (Demonstration purposes only.)
\usepackage{hyperref,cleveref} % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarp Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2} % Include subsections in the \TOC.
\setcounter{secnumdepth}{2} % Number down to subsections.
\setcounter{FileDepth}{1} % Split \HTML\ files at sections
\booltrue{CombineHigherDepths} % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1} % Include subsections in the side\TOC
\HTMLTitle{Webpage Title} % Overrides \title for the web page.
\HTMLAuthor{Some Author} % Sets the HTML meta author tag.
\HTMLLanguage{en-US} % Sets the HTML meta language.
\HTMLDescription{A description.} % Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSFilename{lwarp_sagebrush.css}
```

```

\begin{document}

\maketitle           % Or titlepage/titlingpage environment.

% An article abstract would go here.

\tableofcontents    % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math:  $r = r_0 + vt - \frac{1}{2}at^2$ 
followed by display math:
\begin{equation}
a^2 + b^2 = c^2
\end{equation}

\begin{warpprint} % For print output ...
\cleardoublepage % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage    % HTML index will be on its own page.
\ForceHTMLTOC     % HTML index will have its own toc entry.
\printindex

\end{document}

```

Table 4: Configuration files created by print version

- tutorial.pdf:** The PDF output from L^AT_EX. The print version of the document.
- tutorial_html.tex:** A small .tex file used to create a parallel HTML version of the document, which co-exists with usual the PDF version, and which will have its own auxiliary files. In this way, both PDF and HTML documents may co-exist side-by-side.
- Auxiliary files:** The usual L^AT_EX files .aux, .log, .out, .toc, .lof, .idx. When an HTML version of the document is created, _html versions of the auxiliary files will also be generated.
- lwarpmk.conf:** A configuration file for *lwarpmk*, which is used to automate the compilation of PDF or HTML versions of the document.
- tutorial.lwarpmkconf:** Another configuration file used by *lwarpmk*, which is only useful if you wish to have several projects residing in the same directory.
- .css files:** *lwarp.css*, *lwarp_formal.css*, *lwarp_sagebrush.css* These files are standard for *lwarp*, and are not meant to be modified by the user.
- sample_project.css:** An example of a user-customized css file, which may be used for project-specific changes to the *lwarp* defaults.
- lwarp.ist:** Used by *lwarp* while creating an index using *makeindex*. This file should not be modified by the user. A custom file may be used instead, if necessary.
- lwarp.xdy:** Used by *lwarp* while creating an index using *xindy*. This file should not be modified by the user. A custom file may be used instead, if necessary.
- lwarp_one_limage.txt:** For WINDOWS only. Used to process svg images in the background. Copied to *lwarp_one_limage.cmd* when images are generated.
- lwarp_mathjax.txt:** Inserted into the HTML files when MATHJAX is used to display math. Do not modify, see `\MathJaxFilename` instead.
- comment_*.cut:** Temporary files used by *lwarp* to conditionally process blocks of text. These files may be ignored.

When the *lwarpmk* option is given to the *lwarp* package:

lwarpmk.lua: A local copy of the *lwarpmk* utility.

On UNIX-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

5.2 Compiling the print version with *lwarpmk*

The *lwarpmk* utility program is used to compile either the printed or the HTML version of the document.

`lwarpmk print` is used to recompile a printed version of the document.

1. Re-compile the print version:

Enter ⇒ **lwarpmk print**

lwarpmk prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then *lwarpmk* informs you of that fact and then exits.

2. Make a small change in the original document, such as adding a space character.

3. Recompile again.

Enter ⇒ **lwarpmk print**

The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

4. Force a recompile to occur.

Enter ⇒ **lwarpmk again**

Enter ⇒ **lwarpmk print**

`lwarpmk again` updates the date code for the file, triggering a recompile the next time the document is made.⁵

5. Process the index.^{6 7}

Enter ⇒ **lwarpmk printindex**

6. Recompile again to include the index.

Enter ⇒ **lwarpmk print**

7. To force a single recompile when needed, even if no changes were detected:

Enter ⇒ **lwarpmk print1**

Note that the HTML customization commands are ignored while making the print version.

⁵Although, when using the utility *latexmk* (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

⁶The command `lwarpmk printglossary` is also available to process a glossary produced with the `glossaries` package. See section 8.6.12.

⁷Also see section 8.6.15 for index options.

5.3 Compiling the HTML version with *lwarpmk*

`lwarpmk html` is used to recompile an HTML version of the document.

1. Compile the HTML version:

Enter ⇒ **lwarpmk html**

- (a) *lwarpmk* uses L^AT_EX to process `tutorial_html.tex` to create `tutorial_html.pdf`.
- (b) *pdftotext* is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.
- (c) *lwarpmk* manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`⁸, `Some-math.html`, and the document's index in `_Index.html`.⁹

2. View the HTML page in a web browser.

Open the file `tutorial.html` in a web browser.

math

Note that math is still displayed as its alt tag, which is the plain-text L^AT_EX source, until the images of the math expressions have been generated. Math may be displayed as SVG images or by a MATHJAX script, as seen in sections 5.4 and 5.5.

3. Force a recompile:

Enter ⇒ **lwarpmk again**

Enter ⇒ **lwarpmk html**

Enter ⇒ **lwarpmk print**

4. Process the HTML index and recompile:¹⁰¹¹

Enter ⇒ **lwarpmk htmlindex**

Enter ⇒ **lwarpmk html**

`_Index.html` is updated for the new L^AT_EX index.

5. Reload the web page to see the added index.

6. To force a single recompile when needed, even if no changes were detected:

Enter ⇒ **lwarpmk html1**

⁸`First-chapter.html` also contains the first section, even though the second section is its own HTML page. This behavior is controlled by the boolean `CombineHigherDepths`.

⁹`index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

¹⁰The command **lwarpmk htmlglossary** is also available to process a glossary produced with the `glossaries` package. See section 8.6.12.

¹¹Also see section 8.6.15 for index options.

5.4 Generating the svg images

math as svg images By default `lwarp` represents math as svg images, with the \LaTeX source included in `alt` attributes. In this way, the math is displayed as it was drawn by \LaTeX , and the \LaTeX source may be copied and pasted into other documents.

picture and Tikz `lwarp` uses the same mechanism for `picture` and `Tikz` environments.

1. Create the svg images:

Enter \Rightarrow `lwarpmk limages`

Enter \Rightarrow `lwarpmk html`

2. Move to the tutorial's HTML math page and reload the document in the browser.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the \LaTeX source.

adding/removing When a math expression, `picture`, or `Tikz` environment is added or removed, the svg images must be re-created by entering `lwarpmk limages` to maintain the proper image-file associations. Inline svg math may be hashed and thus not need to be recreated, but display math and objects such as `Tikz` may move to new image numbers when the document is changed.

recompile first Before attempting to create the svg image files, `lwarpmk` verifies that the HTML version of the document exists and has correct internal image references.¹² If it is necessary to recompile the document's HTML version one more time, `lwarpmk` usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the \LaTeX recompile warnings.

HTML instead of images If HTML appears where an svg image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

page counter Incorrect svg images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

Lots of files! Expressing math as svg images has the advantage of representing the math exactly as \LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, `lwarp` uses an MD5 hash on its \LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and `Tikz` require one image file each. For a document with a large amount of math, see section 5.5 to use `MATHJAX` instead.

¹²This becomes important when dealing with a document containing thousands of images.

5.5 Using MATHJAX for math

math with MATHJAX Math may also be represented using the MATHJAX JAVASCRIPT project.

1. In the tutorial's source code, uncomment the `mathjax` package option for `lwarp`:

```
mathjax, % Use MathJax to display math.
```

2. Recompile

```
Enter ⇒ lwarpmk html
```

3. Reload the math page.

 **MATHJAX requirements** MATHJAX requires web access unless a local copy of MATHJAX is available, and it also requires that JAVASCRIPT is enabled for the web page. The math is rendered by MATHJAX. Right-click on math to see several options for rendering, and for copying the L^AT_EX source.

While using MATHJAX has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as L^AT_EX, and it may not support some math-related packages.

5.6 Changing the css style

For a formal css style, add to the preamble:

```
\usepackage{lwarp}  
...  
\CSSFilename{lwarp_formal.css}  
...  
\begin{document}
```

For a modern css style, `lwarp_sagebrush.css` is also provided:

```
\CSSFilename{lwarp_sagebrush.css}
```

See section [7.7](#) for more information about modifying the css styling of the document.

5.7 Customizing the HTML output

A number of settings may be made to control the HTML output, including filename generation, automatic compilation, math output, document splitting, meta data, and page headers and footers.

See section [7.6](#) for more information.

5.8 Using *latexmk*

latexmk is a L^AT_EX utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the *latexmk* option for the *lwarp* package:

```
latexmk, % Use latexmk to compile.
```

2. Recompile the printed version of the document.

```
Enter ⇒ lwarpmk print
```

lwarp updates its own configuration files (*lwarpmk.conf* and *tutorial.lwarpmkconf*) whenever the printed version of the document is compiled. These configuration files remember that *lwarpmk* should use *latexmk* to compile the document.

3. Recompile the document.

```
Enter ⇒ lwarpmk print
```

and/or

```
Enter ⇒ lwarpmk html
```

Changes are detected by comparing checksums rather than modification times, so *lwarpmk* again will not trigger a recompile, but *latexmk* has a much better awareness of changes than the *lwarpmk* utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source, and a single recompile may be forced with:

```
Enter ⇒ lwarpmk print1
```

and/or

```
Enter ⇒ lwarpmk html1
```

[forced single-pass recompile](#)

5.9 Using Xe_{La}TeX or Lua_{La}TeX

Xe_{La}TeX or Lua_{La}TeX may be used instead of \LaTeX .

1. Remove the auxiliary files for the project:

```
Enter ⇒ lwarpmk cleanall
```

2. Use *xelatex* or *lualatex* to compile the printed version a single time.

```
Enter ⇒ xelatex tutorial.tex
```

— *or* —

```
Enter ⇒ lualatex tutorial.tex
```

When the compile occurs, the configuration files for *lwarpmk* are modified to remember which TeX engine was used. Xe_{La}TeX or Lua_{La}TeX will be used for future runs of *lwarpmk*.

3. To recompile the document:

```
Enter ⇒ lwarpmk print
```

-and-

```
Enter ⇒ lwarpmk html
```

4. Also remember to update the indexes and recompile again:

```
Enter ⇒ lwarpmk htmlindex
```

```
Enter ⇒ lwarpmk html
```

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk print
```

5.10 Using DVI \LaTeX

Traditional DVI LaTeX may also be used along with .eps image files. An svg version of each image must also be provided. *lwarpmk* may be used to convert image formats.

To convert EPS files to PDF:

```
Enter ⇒ lwarpmk epstopdf *.eps (or a list of files)
```

To convert PDF files to SVG:

```
Enter ⇒ lwarpmk pdftosvg *.pdf (or a list of files)
```

 **bitmapped fonts** See section 7.4 regarding font selection to avoid the use of bitmapped fonts.

5.11 Using a glossary

lwarp supports the `gloss` and `glossaries` packages, although this tutorial does not supply an example.

5.11.1 `gloss` package

See section [8.6.11](#).

5.11.2 `glossaries` package

To process the glossary for the print version:

```
Enter ⇒ lwarpmk printglossary
```



(If `makeglossaries` is not found, see section [8.6.12](#).)

To process the glossary for the HTML version:

```
Enter ⇒ lwarpmk htmlglossary
```

In each case, the document will have to be recompiled afterwards:

```
Enter ⇒ lwarpmk html1
```

```
Enter ⇒ lwarpmk html
```

```
Enter ⇒ lwarpmk print1
```

```
Enter ⇒ lwarpmk print
```

See section [8.6.12](#) to set options for processing glossaries.

5.12 Cleaning auxiliary files

To remove the auxiliary files `.aux`, `.toc`, `.lof`, `.lot`, `.idx`, `.ind`, `.log`, and `.gl*`, and a few others:

```
Enter ⇒ lwarpmk clean
```

5.13 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the `.pdf` and `.html` files:

```
Enter ⇒ lwarpmk cleanall
```

5.14 Cleaning the images from the `<project>-images` directory

The `<project>-images` directory contains SVG images automatically generated for inline and display math, tikz, etc. To remove all the images from the `<project>-images` directory:

```
Enter ⇒ lwarpmk cleanimages
```

5.15 Converting PDF or EPS images to SVG

HTML cannot display PDF or EPS images, so any external PDF graphics images must be converted to SVG format. *pdftocairo* and *epstopdf* may be used one image at a time, but *lwarpmk* also provides a way to convert PDF or EPS images in bulk:

```
Enter ⇒ lwarpmk epstopdf *.eps (or a list of files)
```

```
Enter ⇒ lwarpmk pdftosvg *.pdf (or a list of files)
```

Be sure to always provide SVG files for HTML output.

5.16 Creating HTML from an incomplete compile

During testing it may be useful to finish the HTML conversion even when the document had errors and did not compile successfully. To attempt an HTML conversion of an incomplete document:

```
Enter ⇒ lwarpmk pdftohtml [-p project]
```

5.17 Processing multiple projects in the same directory

 `xr`, `xr-hyper`, `xcite`

It is possible to have several projects in the same directory. *lwarpmk* has an optional parameter which is the document to compile.

To create each project:

```
Enter ⇒ pdflatex project_a
```

```
Enter ⇒ pdflatex project_b
```

Each project is given its own configuration file:

```
project_a.lwarpmkconf, project_b.lwarpmkconf
```

To compile each project with `lwarkmk`:

```
Enter ⇒ lwarpmk print -p project_a
```

```
Enter ⇒ lwarpmk print -p project_b
```

```
Enter ⇒ lwarpmk html -p project_a
```

```
Enter ⇒ lwarpmk html -p project_b
```

To generate each project's images:

```
Enter ⇒ lwarpmk limages -p project_a
```

```
Enter ⇒ lwarpmk limages -p project_b
```

To clean each project's images:

```
Enter ⇒ lwarpmk cleanlimages -p project_a
```

```
Enter ⇒ lwarpmk cleanlimages -p project_b
```

To clean each project's auxiliary files:

```
Enter ⇒ lwarpmk cleanall -p project_a
```

```
Enter ⇒ lwarpmk cleanall -p project_b
```

If using *bibtex*, for example, the HTML version must also be processed:

```
Enter ⇒ bibtex project_a_html
```

5.18 Using the *make* utility

lwarpmk has an action which may be useful for integration with the common *make* utility:

```
lwarpmk pdftohtml [-p project]
```

make may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then *lwarpmk* may be used to convert each target to HTML files.

5.19 What next?

How do I do something? See the [General Index](#).

Something do not work! See the [Troubleshooting Index](#) or section 13: [Troubleshooting](#).

Package options: See section 28, [Package options](#).

HTML and filename settings: See section 7.6, [Customizing the HTML output](#).

Footnote placement: See section 7.6, [Customizing the HTML output](#).

Title page, indexing, glossaries: See section 8.6, [Front and back matter](#).

Shell escape: See section 7.3, [Shell escape](#).

css customization: See section 7.7, [Customizing the css](#).

MATHJAX customization: See section 8.7.5, [Customizing MATHJAX](#).

Localization: (languages) — See section 7.1, [Localization](#).

Accessibility: (alt and title tags) — See section 7.2, [Accessibility](#).

Converting an existing document: See section 6, [Converting an existing document](#).

EPUB conversion: See section 10, [EPUB conversion](#).

Word processor conversion: See section 11, [Word-processor conversion](#).

6 Converting an existing document

To convert an existing document for use with lwarp:

1. Arrange the document in the following order:

- (a) Declare the `\documentclass`.
- (b) Load text fonts.
- (c) Load `inputenc` or `inputenx`, `fontenc`, or `fontspec`.
- (d) Load `lwarp`.
- (e) Load remaining packages.

2. Modify the document:

- (a) If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring` from the `hyperref` package:

```
\section{Some math \texorpdfstring{$1+2=3$}{three}}
```

- (b) Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

- (c) Possible changes to `tabular` environments include: `* columns`, `multirow`, `longtable`, `supertabular`, `xtable`, `bigdelim`. See section 8.10.1.

- (d) If using braces in package options, such as with `caption`, see section 8.1.

- (e) Possible option clashes with `memoir`. See section 8.13.

- (f) If using indexes, see section 8.6.15.

- (g) If using many indexes, glossaries, `.aux` files, etc., see section 8.6.15 regarding `morewrites`. If `morewrites` is already used, be sure to add the setup with `allocate=10`.

- (h) Other changes as per [Special cases and limitations](#), section 8.

3. Convert any PDF images to SVG. See section 8.8.

4. Manually compile the print version with `latex`, `pdflatex`, `lualatex`, or `xelatex`.

5. `lwarpmk print` to finish the print version.

6. `lwarpmk html` to create the HTML version.

7. `lwarpmk limages` to create the SVG images of any SVG math, `lateximage`, `Tikz`, etc.

[Need help?](#)

See the [General Index](#) for “how-to”, and the [Troubleshooting Index](#) if something doesn’t work. A [Troubleshooting](#) section is also available. The [Index of Objects](#) contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

 [math in section names](#)

 [scale](#)

 [tabular](#)

 [package options](#)

 [indexes](#)

Table 5: Localization settings

Object names: L^AT_EX provides redefinable names for various objects, and lwarp adds a few more. Use `\renewcommand` to change these.

\abstractname: This macro is honored by lwarp.

\linkhomename: Displayed by the link to the homepage.

\linkpreviousname: Displayed by the link to the previous page

\linknextname: Displayed by the link to the next page.

\sitetocname: Displayed at the head of the sideroc.

HTML settings: See table 8 and section 7.6 for details.

\HTMLLanguage: The language to declare for each web page.

\ImageAltText, \MathImageAltText, \PackageDiagramAltText, \AltTextOpen, \AltTextClose: The defaults used for HTML alt text for images. See section 7.2.

\CSSFilename: The name of the css file to use.

\MathJaxFilename: The name of the MATHJAX script to use.

Package options:

ImagesName and ImagesDirectory: These options control the filenames used by lwarp when it automatically generates images. See table 7 and section 7.5.

xindyStyle, xindyLanguage, xindyCodepage: When using *xindy*, these options may be set according to local use. See section 8.6.21.

pdftotextEnc: To adjust the encoding of *pdftotext*.

7 Additional details

7.1 Localization

Regional localization is supported by lwarp via the package options and macros shown in table 5.

7.2 Accessibility

lwarp provides several methods for improving access to the document using tools such as text-only browsers, copy/paste, text-to-speech readers, or Braille readers. HTML provides the `alt` text attribute for images, which is used by lwarp as describe below. HTML also provides the `title` attribute, which usually generates a pop-up text. lwarp can add this to a reference or hyperlink. MATHJAX also has provisions for improved accessibility as well. See table 6.

Table 6: Accessibility settings

\ImageAltText: The default HTML alt text for `\includegraphics` and `lateximages`. Set with `\renewcommand`.

\includegraphics alt key: For `\includegraphics`, `lwarp` adds the alt key/value. For example:

```
\includegraphics[alt={Some text.}]{filename}
```

svg math: For simple svg math, `lwarp` places the L^AT_EX math expression in the alt text, so that the L^AT_EX expression may be copied and pasted to another document as plain text.

\MathImageAltText: For complicated svg math, such as enclosed in `\InlineMathOther/\InlineMathNormal`, or `\DisplayMathOther/\DisplayMathNormal`, the HTML alt text will be set to `\MathImageAltText`. Set with `\renewcommand`.

MATHJAX: For MATHJAX, the accessibility tools provided by MATHJAX are enabled by default by `lwarp`'s MATHJAX scripts.

\PackageDiagramAltText: Various packages create diagrams which `lwarp` converts into svg images. These are given alt text set to `\PackageDiagramAltText`. Set with `\renewcommand`.

\ThisAltText: The HTML alt text of the next image may be set with:

```
\ThisAltText{Custom text about the image.}
<SVG math, Tikz, picture, etc.>
```

The next single image will be generated with the given text, and the following images will revert to back to their defaults.

`\ThisAltText` may also be used to assign an HTML title to the next reference or hyperlink.

```
\ThisAltText{Custom text about the link.}
Text ... \ref{label_name} ... text.
```

See section 7.6.

\AltTextOpen and \AltTextClose: By default, HTML alt text is enclosed by parentheses. This may be changed by redefining `\AltTextOpen` and `\AltTextClose`. Set with `\renewcommand`.

7.3 Shell escape

Opt `--shell-escape` Some documents require the use of an external program, which is allowed when using the `--shell-escape` command-line option. When the document is first compiled manually, and also whenever the print version is recompiled, `lwarp` detects and remembers whether shell escape is enabled. If so, it will also be enabled when the document is recompiled with `lwarpmk`.

7.4 Font and UTF-8 support

 **type 3 bitmapped fonts** `lwarp` uses `pdftotext` to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which may prevent the use of older “type 3” bit-mapped fonts, and of older packages such as `ae`. The `lwarp` option `pdftotextEnc` may be useful in some situations. See section 7.5.

vector fonts While using DVI `latex` or PDF `pdflatex`, if no font-related package is specified then the default COMPUTER MODERN font is used, which may be a “type 3” bit-mapped font which may not convert well to plain text. A “type 1” vector font is required.

 **pdflatex**

 **DVI latex**

Pkg `cm-super`

To use the updated `cm-super`'s type 1 fonts instead of Computer Modern, install the `cm-super` font package.

Pkg `lmodern` To use Latin Modern instead, add

```
usepackage{lmodern}
```

to the preamble.

Pkg `dejavu` Another useful option is the Deja Vu series of fonts, which have an increased coverage of language and glyphs:

```
\usepackage{dejavu}
```

latex, pdflatex, T1, UTF8 While using DVI `latex` or PDF `pdflatex`, `lwarp` automatically loads `fontenc` with T1 encoding. `fontenc` may be loaded with an additional encoding after `lwarp`. `inputenc` is automatically loaded with UTF8 encoding if it has not yet been loaded, but may also be specified with another encoding such as `latin1`. See the next section regarding index encoding.

 **xelatex, luatex, fontspec** X_ƎLaTeX and LuaLaTeX users must use the `fontspec` package. Do NOT use `fontenc`!

Place `fontspec` or `fontenc`, `xunicode`, and other font and UTF-8 related commands after the `\documentclass` command and before `\usepackage{lwarp}`.

 **package conflicts** In some cases, a package conflict may require that a font package be loaded after `lwarp`, which should work as well:

1. `documentclass{article/book/report}` comes first, followed by any of:
2. Font and UTF-8 related commands:
 - For X_ƎLaTeX or LuaLaTeX:

Pkg fontspec

ligatures

– fontspec and font choices

lwarp sets the following to turn off T_EX ligatures during the generation of HTML tags, and turn off common ligatures in regular text, since older browsers may not display them correctly and newer browsers can automatically re-create them.

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
```

• For *pdflatex*:

Pkg lmodern

Pkg fontenc

Pkg inputenc

Pkg inputenx

Pkg newunicodechar

File glyphtounicode.tex

(a) `\usepackage{lmodern}`, or other font-related packages(b) `\usepackage[T1]{fontenc}`(c) `\usepackage[utf8]{inputenc}`, or `latin1`, etc. Or use `inputenx`.(d) `\usepackage{newunicodechar}` along with related definitions.

(e) To assist with the PDF-HTML conversion:

i. `\input glyphtounicode.tex`ii. `\input glyphtounicode-cmr.tex`% from the pdfx packageiii. `\pdfgentounicode=1`(f) Another option to assist with the PDF-HTML conversion, such as the `dotless j` (`\j`):– `\usepackage{cmap}` — *or* —– `\usepackage{mmap}` — *or* —– `\usepackage[noTeX]{mmap}`(g) `\usepackage{textcomp}` **dotless j**

Pkg cmap

Pkg mmap

Pkg textcomp

3. `\usepackage{newtxmath}` or other math-related font packages. Many of these load `amsmath`, which may now be loaded before `lwarp`.4. `\usepackage{lwarp}` (section 7.5) is placed after any of the above, followed by:5. `\setmonofont{TeX Gyre Cursor}` or similar may be required if using X_EL_AT_EX or Lua_AT_EX and `fontspec` along with traditional font packages such as `txfonts`, `newtxtext`, etc. This is required to turn off the monospaced font's ligatures with `fontspec` after loading the traditional font packages. Monospaced output ligatures must be turned off to produce the correct HTML characters.

Any monospace font with built-in ligatures may require these ligatures to be disabled for HTML. In one example, JETBRAIN MONO, it is required to use

```
\setmonofont{JetBrains Mono}[%
...
Contextuals=AlternateOff,
]
```

After `lwarp` is loaded, the ligature may be re-enabled for print mode by using `\setmonofont` again inside a `warpprint` environment.

6. ... the rest of the preamble and the main document.

 **fontspec with monospaced fonts** **JETBRAIN MONO** **HTML corrupted** **UTF-8 locale** In some cases, an external program may require a UTF-8 “locale”. See section 9.8.

7.4.1 Indexes, glossaries, and encoding

lwarp supports *makeindex*, *xindy*, *xindex*, and glossaries, gloss, and nomencl.

See section [8.6.14](#) for indexing, and section [8.6.12](#) for the glossaries package.

7.5 lwarp package loading and options

lwarp supports book, report, and article classes, as well as the equivalent Koma-script classes and memoir, and various CJK-related classes and packages.

Load the lwarp package immediately after the font and UTF-8 setup commands.

Package options may be set while loading lwarp, or later with

```
\lwarpsetup{<key=value, . . . >}
```

Pkg lwarp lwarp package options are as follows:

Opt mathsvg **mathsvg** and **mathjax**: Selects SVG images or MATHJAX for math display. See section 8.7.

Opt mathjax

Default: mathsvg

Opt latexmk **latexmk**: Tells *lwarpmk* to use *latexmk* to recompile the document several times if necessary. Otherwise, *lwarpmk* attempts to determine for itself whether to recompile. See section 7.6.

Default: false

Opt dvips **dvips**: Tells *lwarpmk* to use *dvips* and *ps2pdf* to convert DVI output to PDF.

Default: false

Opt dvipdfm **dvipdfm**: Tells *lwarpmk* to use *dvipdfm* to convert DVI output to PDF.

Default: false

Opt dvipdfmx **dvipdfmx**: Tells *lwarpmk* to use *dvipdfmx* to convert DVI output to PDF.

Default: false

Opt HomeHTMLFilename **HomeHTMLFilename**:

Default: \BaseJobname

Filename of the homepage, without the “.html” suffix. Defaults to the \BaseJobname. A common setting is:

```
HomeHTMLFilename=index
```

causing the homepage to be the file index.html. Underscores are allowed in HomeHTMLFilename and HTMLFilename options, but may need to be escaped elsewhere, such as when appearing in a list:

filename underscores

```
\item [\href{file\_name.pdf}{text}] \
```

See section 7.6.1 for examples of naming and numbering HTML files.

Opt HTMLFilename **HTMLFilename**: A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty. See section 7.6.1 for examples of naming and numbering HTML files.

Default: <empty>

Opt ImagesName **ImagesName**: The prefix for the images automatically generated by lwarp for objects such as svg math and lateximages.

Default: image-

Opt ImagesDirectory **ImagesDirectory**: The directory for the images automatically generated by lwarp for

Default: \jobname-images

Table 7: Lwarp package options

Option	Description
mathsvg	Show math using SVG images.
mathjax	Show math using MATHJAX.
latexmk	Use <i>latexmk</i> for compiling documents.
dvips	Use <i>dvips</i> and <i>ps2pdf</i> to convert DVI documents.
dvipdfm	Use <i>dvipdfm</i> to convert DVI documents.
dvipdfmx	Use <i>dvipdfmx</i> to convert DVI documents.
HomeHTMLFilename	The filename of the home page.
HTMLFilename	A prefix for the filenames of the remaining web pages.
ImagesName	A prefix for the filenames of generated images.
ImagesDirectory	The directory used to hold generated images.
PrintLatexCmd	The shell commands for lwarpmk print .
HTMLLatexCmd	The shell commands for lwarpmk html .
For indexing (section 8.6.15) and glossaries (section 8.6.12):	
makeindex	Use <i>makeindex</i> to generate indices.
makeindexStyle	Set a custom style for <i>makeindex</i> .
xindy	Use <i>xindy</i> to generate indices.
xindyStyle	Set a custom style for <i>xindy</i> .
xindyLanguage	The <i>xindy</i> language option used for index generation.
xindyCodepage	The <i>xindy</i> codepage option used for index generation.
xindex	Use <i>xindex</i> to generate indices.
xindexConfig	Set a custom configuration file for <i>xindex</i> .
PrintIndexCmd	Shell commands executed by lwarpmk printindex .
HTMLIndexCmd	Shell commands executed by lwarpmk htmlindex .
LatexmkIndexCmd	Shell commands executed by <i>latexmk</i> .
IndexRef	How to format index links.
GlossaryCmd	Shell command executed by lwarpmk printglossary and lwarpmk htmlglossary .
Seldom necessary:	
OSWindows	Force compatibility with MS-WINDOWS.
pdftotextEnc	Set the encoding for <i>pdftotext</i> .
Lwarpmk	Generate a local copy of <code>lwarpmk.lua</code> .
Used internally by lwarp:	
warpprint	Generate print output, and also generate configuration files.
warpHTML	Generate HTML output.
BaseJobname	The <code>\jobname</code> to use. Set to the <code>\jobname</code> of the printed version even while generating HTML.

objects such as `svg math` and `lateximages`. By default, these images will appear in a directory named `<jobname>-images`, and the images will be named and numbered `image-<nn>`.

- Opt `PrintLatexCmd` **PrintLatexCmd:** Sets the shell commands executed by `lwarpmk print`. If not specified, will automatically be set according to the detected `LATEX` engine and the use of `--shell-escape`.
Default: `<automatic>`
- Opt `HTMLLatexCmd` **HTMLLatexCmd:** Sets the shell commands executed by `lwarpmk html`. If not specified, will automatically be set according to the detected `LATEX` engine and the use of `--shell-escape`.
Default: `<automatic>`
- Opt `makeindex` **makeindex:** Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use `makeindex` when generating indexes with `lwarpmk printindex`, `lwarpmk htmlindex`, or `latexmk`. If neither `makeindex` nor `xindy` is used, `makeindex` is assumed.
Default: `makeindex`
- Opt `makeindexStyle` **makeindexStyle:** If you wish to use a custom `.ist` file for index generation, see section 8.6.20.
Default: `lwarp.ist`
- Opt `xindy` **xindy:** Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use `xindy` when generating indexes with `lwarpmk printindex`, `lwarpmk htmlindex`, or `latexmk`.
Default: `makeindex`
- Opt `xindyStyle` **xindyStyle:** If you wish to use a custom `.xdy` file for index generation, see section 8.6.21.
Default: `lwarp.xdy`
- Opt `xindyLanguage` **xindyLanguage:** If using an index or glossary, see section 28.
Default: `english`
- Opt `xindyCodepage` **xindyCodepage:** If using an index, see section 28.
Default: `utf8`
- Opt `xindex` **xindex:** Sets `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkImageCmd` to use `xindex` when generating indexes with `lwarpmk printindex`, `lwarpmk htmlindex`, or `latexmk`.
Default: `makeindex`
- Opt `xindexConfig` **xindexConfig:** If you wish to use a custom `xindex-*.lua` file for index generation, see section 8.6.22.
Default: `<empty>`
- Opt `PrintIndexCmd` **PrintIndexCmd:** Sets the shell commands executed by `lwarpmk printindex`. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 8.6.15.
Default: `<automatic>`

Examples:

```
makeindex -s lwarp.ist projectname.idx (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname.idx (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `PrintIndexCmd` to sensible values for each of those programs while compiling a single index. `lwarp`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified.

⚠ **xindy**

If specifying `PrintIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C xindy` options, as the `lwarp xindyLanguage` and `xindyCodepage` options are not used for the `PrintIndexCmd` option when it is set manually.

This option is stored in the configuration files `lwarpmk.conf` and `*.lwarpmkconf`, and is then passed by the `lwarpmk printindex` command to the operating system to compile the print indexes. Since the command string is parsed by `TEX`, written to a file, read from the file by `LuaTEX`, and finally passed to the operating system, any attempt at quoting will be problematic. For complicated commands, it would be best to create a shell script, and simply refer to the script with the `lwarp PrintIndexCmd` option.

Opt HTMLIndexCmd

Default: <automatic>

HTMLIndexCmd: Sets the shell commands executed by `lwarpmk htmlindex`. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 8.6.15.

⚠ **filenames**

Example settings are similar to `PrintIndexCmd`, but append `_html` to the filenames:

```
makeindex -s lwarp.ist projectname_html.idx (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname_html.idx (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `HTMLIndexCmd` to sensible values for each of those programs while compiling a single index. `lwarp`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified.

⚠ **xindy**

If specifying `HTMLIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C xindy` options, as the `lwarp xindyLanguage` and `xindyCodepage` options are not used for the `HTMLIndexCmd` option when it is set manually.

As with `PrintIndexCmd`, to generate complicated indexes it may be worthwhile to use a shell script, then refer to that script with `HTMLIndexCmd`.

Opt LatexmkIndexCmd

Default: <automatic>

LatexmkIndexCmd: Sets the shell commands executed by `latexmk`. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `LatexmkIndexCmd` does not include any filenames, which will be provided instead by `latexmk`. See section 8.6.15.

Example settings are similar to `PrintIndexCmd`, but without a filename:

```
makeindex -s lwarp.ist (makeindex)
xindy -M lwarp.xdy -L english -C utf8 (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `LatexmkIndexCmd` to either of the two settings show above. `lwarp`'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options will be used if specified. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, *latexmk* uses either of the single-line settings of `LatexmkIndexCmd` shown above to compile each of multiple indexes if necessary.

⚠ xindy

If specifying `LatexmkIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C xindy` options, as the `lwarp xindyLanguage` and `xindyCodepage` options are not used for the `LatexmkIndexCmd` option when it is set manually.

Opt IndexRef Default: cref

IndexRef: Describes how to display the index entries for HTML output. Possible values are `ref`, `nameref`, `refnameref`, `cref`, `crefnameref`, `autoref`, or a text string such as `(link)` or `(*)` for each index entry reference. (Adding parentheses around a single character makes the link larger and easier to click on.) The default is `cref`, which is available even if the print document does not use `cleveref`, as the `lwarp` package relies on `cleveref` during HTML output. Option `autoref` gives the same results as `cref`.

`\ref` and `\cref` to starred or otherwise unknown links will display as `(*)` instead of `??`.

⚠ ??

If using `cref` (the default), and if a reference appears as `??` with a non-functional link, use `cleveref`'s `\crefname` to give a name to that type of label.

In general, `crefnameref` gives the most information, but the index can become quite verbose. Using `(*)` or similar yields a very compact index.

Opt GlossaryCmd Default: makeglossaries

GlossaryCmd: Sets the shell command executed by `lwarpmk printglossary` and `lwarpmk htmlglossary`. The print or HTML glossary filename is appended to this command. See section 8.6.12.

Opt OSWindows

OSWindows: `lwarp` attempts to automatically sense WINDOWS, but it may be forced with this option. See section 7.9.

Opt pdftotextEnc Default: UTF-8

pdftotextEnc: Used to specify the encoding used by `pdftotext` during the PDF-HTML conversion. In most situations, the default is the correct choice.

Opt lwarpmk

lwarpmk: If you wish to have `lwarp` generate a local copy of `lwarpmk.lua` for archival or local-installation purposes, compile the print version with the `lwarpmk` option set. See section 28.

The following options are used internally by `lwarp`, and usually are not used in the user's document:

Opt warpprint Opt warpHTML

warpprint and **warpHTML:** Usually controlled by `lwarpmk`, and not set in the docu-

ment. Select the `warpprint` option to generate print output (default), or the `warpHTML` option to generate HTML5 output. The default is print output, so the print version may be compiled with the usual *pdflatex*, etc. When `lwarp` is loaded in print mode, it creates `<project>_html.tex`, which sets the `warpHTML` option before calling the user's source code `<project>.tex`. In this way, `<project>.tex` can `\usepackage{lwarp}` without any options to create a printed version, while `<project>_html.tex` will create an HTML version.

Opt BaseJobname **BaseJobname:** Not intended for the user. Used internally by `lwarp` when creating the
Default: `\jobname` `*_html.tex` file used to compile the HTML version. See section 28.

7.6 Customizing the HTML output

⚠ Placement!

Table 8 shows several settings may be used to customize the HTML output. Watch for the correct placement of each!

⚠ Changes!

Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:

Enter ⇒ `lwarpmk clearall`

2. Recompile the print version in order to recreate the configuration files for *lwarpmk*:

Enter ⇒ `lwarpmk print`

3. Finally, recompile the HTML version with the new settings:

Enter ⇒ `lwarpmk html`

Placed in the preamble before `\begin{document}`:

<code>\HTMLFirstPageTop</code> Default: <code><empty></code>	<code>\HTMLFirstPageTop: {<contents>}</code> A user-definable custom action applied to the top of the home page. Useful for logos, etc. <code>\LinkNext</code> may be used to link to the next web page. Defaults empty. Ignored in print output.
<code>\HTMLFirstPageBottom</code> Default: <code><empty></code>	<code>\HTMLFirstPageBottom: {<contents>}</code> A user-definable custom action applied to the bottom of the home page. Useful for logos, etc. <code>\LinkNext</code> may be used to link to the next web page. Defaults empty. Ignored in print output.
<code>\linkhomename</code> Default: <code>Home</code>	<code>\linkhomename</code> : Name of the link to the home page. Paragraphs are allowed. Redefine with <code>\renewcommand</code> .
<code>\linkpreviousname</code> Default: <code>Previous</code>	<code>\linkpreviousname</code> : Name of the link to the previous page. Paragraphs are allowed. Redefine with <code>\renewcommand</code> .
<code>\linknextname</code> Default: <code>Next</code>	<code>\linknextname</code> : Name of the link to the next page. Paragraphs are allowed. Redefine with <code>\renewcommand</code> .
Ctrl <code>tocdepth</code>	<code>tocdepth</code> : Sectioning depth of the table of contents. See section 16 for a list of L ^A T _E X stack depths.
Ctrl <code>SideTOCDepth</code> Default: <code>1</code> <code>sideroc</code>	<code>SideTOCDepth</code> : Sectioning depth of the sideroc. Defaults to 1, causing the sideroc to show sections but not subsections. Each subpage of the website has its own small table of contents on the side (the “sideroc”). Its depth is set by <code>SideTOCDepth</code> . This sideroc is only shown if the browser display is wide enough. When using a narrow web browser window, “responsive web design” is used to show the sideroc at the top of the page, as well as a link back to Home at the top and bottom.

It is recommended to set:

```
SideTOCDepth = FileDepth
```

Table 8: HTML settings

Macro/Cntr/Bool	Loc*	Description
<code>\linkhomename</code>	P	Name of the link to the homepage.
<code>\linkpreviousname</code>	P	Name of the link to the previous page.
<code>\linknextname</code>	P	Name of the link to the next page.
<code>SideTOCDepth</code>	P	Sectioning depth of the sideroc.
<code>\sidetocname</code>	P	Name of the sideroc.
<code>FileDepth</code>	P	Sectioning depth of the file splits.
<code>CombineHigherDepths</code>	P	Combine higher section levels.
<code>FileSectionNames</code>	P	Use section names for file names, else use numbers.
<code>\FilenameLimit</code>	P	Maximum length of the generated filenames.
<code>FootnoteDepth</code>	P	Sectioning depth of footnotes.
<code>\abstractname</code>	P	The name of the abstract.
<code>\ImageAltText</code>	PD	<code>\includegraphics</code> and other images' alt tag.
<code>\ThisAltText {{text}}</code>	PD	Assigns an alt/title tag for the next image or link.
<code>\MathImageAltText</code>	PD	The SVG math image <code>lateximage</code> alt tag.
<code>\PackageDiagramAltText</code>	PD	The suffix for a package's <code>lateximage</code> alt tags.
<code>\AltTextOpen</code>	PD	Start an HTML alt tag.
<code>\AltTextClose</code>	PD	End an HTML alt tag.
<code>\CSSFilename</code>	PS	The CSS for the following files.
<code>\MathJaxFilename</code>	PS	The MathJax script for the following files.
<code>\HTMLLanguage</code>	PS	The HTML lang tag.
<code>\HTMLTitle</code>	PS	The homepage's <title>, overriding <code>\title</code> .
<code>\HTMLTitleBeforeSection</code>	PS	Set subpage <title>s to <code>\HTMLTitle - sectionname</code>
<code>\HTMLTitleAfterSection</code>	PS	Set subpage <title>s to <code>sectionname - \HTMLTitle</code>
<code>\HTMLAuthor</code>	PS	The HTML author meta tag, overriding <code>\author</code> .
<code>\HTMLDescription</code>	PS	The HTML description meta tag.
<code>\HTMLFirstPageTop</code>	P	Heading for the home page.
<code>\HTMLFirstPageBottom</code>	P	Footer for the home page.
<code>\HTMLPageTop</code>	PS	Heading for the other pages.
<code>\HTMLPageBottom</code>	PS	Footer for the other pages.
<code>\IndexPageSeparator</code>	P	Index page list separator.
<code>\IndexRangeSeparator</code>	P	Index page range separator.
<code>FixSmallCaps</code>	P	Set true if small caps rendered as all caps.
<code>HTMLDebugComments</code>	P	Boolean to generate HTML comments.

* **P**: Preamble, **D**: Anywhere in the document. **S**: Before a section.

or

$$\text{SideTOCDepth} = \text{FileDepth} + 1$$

If $\text{SideTOCDepth} < \text{FileDepth}$, web pages will be inaccessible via the sideroc.

⚠ inaccessible pages

\sidedotocname
Default: Contents

\sidedotocname: Name of the sideroc. Paragraphs are allowed. Redefine with \renewcommand.

Ctrl FileDepth
Default: -5

FileDepth: Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.

- To place the entire file into one HTML page, use:
`\setcounter{FileDepth}{-5}`
- To split the HTML file at \section depth, use:
`\setcounter{FileDepth}{1}`
- To ensure that the HTML pages/files are accessible:
Place a \tableofcontents somewhere before the first section break (therefore in the “home page”), and set
`tocdepth >= FileDepth`

⚠

Bool CombineHigherDepths
Default: true

CombineHigherDepths: Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

⚠ Inaccessible pages!

⚠ Lost in an old page!

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (`lwarpmk cleanall`), change FileDepth and/or CombineHigherDepths, then finally recompile and navigate to the desired page using the new file structure.

Bool FileSectionNames
Default: true

FileSectionNames: If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the HTMLFilename option is used as a prefix. See section 7.6.1 for examples of naming and numbering HTML files. The user must ensure that filenames are unique after begin sanitized. For example, math in the section name is removed before creating the filename, so the rest of the filename must be sufficiently unique to avoid name collisions.

⚠ Unique filename!

\FilenameLimit
Default: 80

\FilenameLimit: The maximum length of the filenames generated by lwarp. “.html” is added to this length. Redefine with \renewcommand.

Ctrl FootnoteDepth
Default: 3

FootnoteDepth: Determines where to place pending footnotes. 3 places foot-

notes before each break down to the `\subsubsection` level. 1 places footnotes before each `\section` break. Any pending footnotes are also placed at the bottom of each page before each file break.

Bool	<code>FixSmallCaps</code> Default: <code>false</code>	FixSmallCaps: Set true if SMALL CAPS are rendering in all caps (“SMALL CAPS”). May be required for some fonts (erewhon, utopia, fbb, et al.), and packages such as embrac.
Bool	<code>HTMLDebugComments</code> Default: <code>false</code>	HTMLDebugComments: Set true to generate HTML comments, such as which section or <code><div></code> is being opened or closed.
	<code>\abstractname</code> Default: <code>Abstract</code>	\abstractname: The name of the abstract. This may also be over-written by the babel package. Defaults to “Abstract”. Redefine with <code>\renewcommand</code> .
	<code>\IndexPageSeparator</code> Default: <code>“ , ”</code>	\IndexPageSeparator: Index page list separator. Adjust to match index style file. If using <code>gindex</code> , this is set automatically to <code>gindex’s \indexpagesep</code> .
	<code>\IndexRangeSeparator</code> Default: <code>“--”</code>	\IndexRangeSeparator: Index page range separator. Adjust to match index style file. If using <code>gindex</code> , this is set automatically to <code>gindex’s \indexrangesep</code> .

Placed before `\begin{document}`, or before any sectioning command which causes a file break:

`\CSSFilename`
Default: `lwarp.css`

\CSSFilename: `{\filename.css}` Sets the css file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The css styles of the web pages are set by the `\CSSFilename` command. If `\CSSFilename` is not used, a default plain style is used to mimic printed L^AT_EX output. `lwarp_sagebrush.css` is a semi-fancy colored style as shown in this tutorial. Change it to `lwarp_formal.css` for a more formal look, or comment out the `\CSSFilename` command to see the default. `\CSSFilename` may be used before each file break to set the css for individual pages of the website.

`\MathJaxFilename`
Default: `lwarp_mathjax.txt`

\MathJaxFilename: `{\filename}` Sets the MathJax script file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The MathJax script file is copied into the head of each HTML file. This may be used to point to a local repository, add extensions, or change the script somewhere in the middle of the document. `\MathJaxFilename` may be used before each file break to set the script file for individual pages of the website.

`\HTMLLanguage`
Default: `en-US`

\HTMLLanguage: `{\langauge}` The HTML file’s HTML lang meta tag. Defaults to en-US.

`\HTMLTitle`
Default: `\thetitle`

\HTMLTitle: `{\title}` Overrides `\title` for the HTML header’s meta title. Defaults to `\thetitle`, which is set by `\title`, or empty otherwise. Unlike the author, `\thetitle` is set by `\title` even if not using the titling package.

`\HTMLTitleBeforeSection`
Default: `\HTMLTitleBeforeSection`

\HTMLTitleBeforeSection: Sets subpage `<title>` tags to show the website title followed by the section name.

<code>\HTMLTitleAfterSection</code>	\HTMLTitleAfterSection: Sets subpage <code><title></code> tags to show the section name followed by the website title.
<code>custom <title></code>	To customize subpage <code><title></code> s, redefine <code>\theHTMLTitleSection</code> , which defaults to: <pre> \def\theHTMLTitleSection{% \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection% } </pre>
<code>\HTMLAuthor</code> Default: <code>\theauthor</code>	\HTMLAuthor: <code>{\langle author \rangle}</code> The HTML header's meta author. Defaults to <code>\theauthor</code> , which is set by <code>\author</code> if using the <code>titling</code> package, but is empty otherwise. There are several ways to represent the author and affiliations, especially if using the <code>authblk</code> package, most of which do not result in a sensible <code>\theauthor</code> , so <code>\HTMLAuthor</code> is useful to create a list of authors without their affiliations.
<code>\HTMLDescription</code> Default: <code><empty></code>	\HTMLDescription: <code>{\langle description \rangle}</code> Sets the HTML description tag for the following files. May be changed before each each sectioning command which would cause a file split.
<code>\HTMLPageTop</code> Default: <code><empty></code>	\HTMLPageTop: <code>{\langle contents \rangle}</code> A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. <code>\LinkHome</code> may be used to place a link back to the homepage, as well as <code>\LinkPrevious</code> and <code>\LinkNext</code> . Ignored in print output.
<code>\HTMLPageBottom</code> Default: <code><empty></code>	\HTMLPageBottom: <code>{\langle contents \rangle}</code> A user-definable custom action applied to the bottom of pages other than the home page. Useful for authors, copyright notices, contact information, etc. Defaults empty. <code>\LinkHome</code> may be used to place a link back to the homepage, as well as <code>\LinkPrevious</code> and <code>\LinkNext</code> . Ignored in print output.
<code>\LinkHome</code>	\LinkHome: Creates a link to the home page. Usually used in <code>\HTMLPageTop</code> and related.
<code>\LinkPrevious</code>	\LinkPrevious: Creates a link to the previous HTML page, unless already at the home page. Usually used in <code>\HTMLPageTop</code> and related.
<code>\LinkNext</code>	\LinkNext: Creates a link to the next HTML page, unless already at the end. Usually used in <code>\HTMLPageTop</code> and related.

Placed in the home page before the first sectioning command which causes a file break:

<code>\tableofcontents</code> △ TOC on the homepage!	\tableofcontents: Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage. Links to each chapter/section are provided, as selected by <code>tocdepth</code> .
---	--

Placed in the document wherever necessary:

<code>\ImageAltText</code> Default: <code>image</code>	\ImageAltText: Redefine with <code>\renewcommand</code> . <code>\includegraphics</code> and other images are assigned an HTML alt tag according to <code>\ImageAltText</code> along
---	--

with `\AltTextOpen` and `\AltTextClose`. This text is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `\includegraphics` and other images.

`\ThisAltText`

\ThisAltText: `{\text}` `\ThisAltText` can be used to assign an HTML alt text attribute to the next image generated by a `lateximage`, `picture`, `tikzpicture`, or any other similar environment which generates an image, or the next SVG math expression. This tag is cleared after use. The tag is also cleared after each MATHJAX expression, in case the user changes between SVG math and MATHJAX.

`\ThisAltText` also may be used to add an HTML title to a reference or hyperlink, such as a `\ref`, `\cref`, `\href`, `\url`, `\hyperref`, or `\hyperlink`. In each case, the alternative text is cleared after use.

`\MathImageAltText`

Default: math image

\MathImageAltText: Redefine with `\renewcommand`. When creating an SVG math image, its HTML alt tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the alt tag is set to `\MathImageAltText`, along with `\AltTextOpen` and `\AltTextClose`, and the image is not reused.

This alt expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “math image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

`\PackageDiagramAltText`

Default: diagram

\PackageDiagramAltText: Redefine with `\renewcommand`. For many packages, the output is placed inside a `lateximage` with an HTML alt tag set to the package name followed by `\PackageDiagramAltText`. For example:

(-xy- diagram)

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “diagram”, and may it be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

`\AltTextOpen`

Default: (

`\AltTextClose`

Default:)

\AltTextOpen: Redefine with `\renewcommand`.

\AltTextClose: Redefine with `\renewcommand`. HTML alt text is enclosed by the macros `\AltTextOpen` and `\AltTextClose`, which default to an opening and closing parenthesis.

Env `warpprint`

warpprint: An environment which is only used while generating print output. Place inside anything which does not apply to HTML and which may cause problems with `lwarp`. If `lwarp` knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won’t have to be placed inside a `warpprint` environment, but unknown packages may cause problems which may be isolated from `lwarp` using this environment.

		<i>Do not place anything else on the same line as <code>\end{warpprint}</code>. Also do not nest <code>warpprint</code> inside itself.</i>
Env	<code>warpHTML</code>	warpHTML: An environment which is only included while generating HTML output. This is useful for website logos and other items which have no purpose in printed output.
		<i>Do not place anything else on the same line as <code>\end{warpHTML}</code>. Also do not nest <code>warpHTML</code> inside itself.</i>
	<code>\warpprintonly</code>	\warpprintonly: <code>{\langle contents \rangle}</code> A macro version of the <code>warpprint</code> environment.
	<code>\warpHTMLonly</code>	\warpHTMLonly: <code>{\langle contents \rangle}</code> A macro version of the <code>warpHTML</code> environment.

7.6.1 Example HTML file naming

Examples of ways to name or number HTML files:

Numbered HTML nodes:

Example: Homepage `index.html`, and `node-1`, `node-2`.¹³

```
\usepackage[
  HomeHTMLFilename=index,
  HTMLFilename={node-}
]{lwarp}
\boolfalse{FileSectionNames}
```

Named HTML sections, no prefix:

Example: `index.html`, and `About.html`, `Products.html`

```
\usepackage[
  HomeHTMLFilename=index,
  HTMLFilename={}
]{lwarp}
\booltrue{FileSectionNames}
```

Named HTML sections, with prefix:

Example: Homepage `mywebsite.html`, and additional pages such as `mywebsite-About.html`, `mywebsite-Products`, etc.

```
\usepackage[
  HomeHTMLFilename=mywebsite,
  HTMLFilename={mywebsite-}
]{lwarp}
\booltrue{FileSectionNames}
```

¹³See `\SetHTMLFileNumber` to number in groups by chapter, for example.

7.7 Customizing the css

`\CSSFilename` $\{ \langle filename \rangle \}$
 Default: `lwarp.css`

`\CSSFilename` may be used to choose which `.css` file is used to display each page of the web site. Use `\CSSFilename` before `\begin{document}` to assign the style of the home page. If different parts of the website should have different styles, call `\CSSFilename` again before each section heading which creates a new file. This may be changed numerous times throughout the file, resulting in different HTML pages having different css files assigned:

```
...
\CSSFilename{myCSS.css}
\chapter{Another Chapter}
...
```

The styles provided by `lwarp` include:

lwarp.css: A default style if `\CSSFilename` is not used. This style is comparable to a plain L^AT_EX document. To set this style, you may use `\CSSFilename{lwarp.css}`, or no `\CSSFilename` call at all.

lwarp_formal.css: A formal style with a serif fonts and a traditional look.

lwarp_sagebrush.css: A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the `\CSSFilename` entry in the tutorial, `lwarpmk.html` again, and then reload the tutorial webpage.

Custom css A customized style may also be created. For each new project a file called `sample_project.css` is generated. This may be renamed to `<project>.css` then used by assigning `\CSSFilename{<project>.css}`.

 **Rename it!** Note that `sample_project.css` is overwritten whenever `lwarp` is loaded in print mode. It is therefore important to rename the file to something like `<project>.css` before using it, so that your own changes are not overwritten.

`<project>.css` has an entry which loads `lwarp.css`, and this entry may be changed to load `lwarp_formal.css` or `lwarp_sagebrush.css` if desired. Additional changes to the css may be made by making entries later in the `<project>.css` file.

File `lwarp.css`
 File `project.css`
 File `sample_project.css`

It is best to make a local project-specific css file such as `project.css`, containing only things which are different from `lwarp.css`. The file `project.css` should refer to `lwarp.css` as follows:

```
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
```

```

/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */

```

Finally use `\CSSFilename{<project>.css}` in the document to activate the custom CSS.

7.8 Assigning css classes and styles

HTML CSS classes and styles may be assigned to fragments of the document.

Env BlockClass [*<style>*] {*<class>*}

An entire block of text, including paragraphs, may be assigned a CSS class and optional CSS style using the BlockClass environment. The result is placed inside a `<div>`. A BlockClass may nest other BlockClasses or \InlineClasses.

\InlineClass ((*wp CSS style*) [*web CSS style*]) {*<css class>*} {*<text>*}

A section of text without paragraphs may be assigned a CSS class and optional CSS style using the \InlineClass macro. The result is placed inside a ``. \InlineClass may be nested, but per the HTML standard it must not contain BlockClass, nor may it contain a paragraph, nor several other objects such as HTML figures. \InlineClass also accepts a second optional parameter, enclosed inside parentheses, which assigns the style while generating output for a word processor, while ignoring the web style.

Nullified versions of BlockClass and \InlineClass are provided for the print version, so they may be used in the document without placing them inside `warpHTML` or `\warpHTMLonly`.

7.9 Selecting the operating system

Prog Unix	lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.
Prog Mac OS	
Prog Linux	
Prog MS-Windows	If MS-WINDOWS is not correctly detected, use the lwarp option OSWindows.
Prog Windows	When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean usingOSWindows is set true. This boolean may be tested by the user for later use.
Opt OSWindows	

7.10 Selecting actions for print, HTML, or MATHJAX output

The following environments and macros are used to select actions which only apply to either traditional L^AT_EX print-formatted PDF generation, or to HTML generation, or to HTML with MATHJAX.

For most of built-in L^AT_EX and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which lwarp does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

Env `warpHTML` Anything which is to be done only for HTML5 output is surrounded by a `warpHTML` environment:

```
\begin{warpHTML}
... something to be done only during \HTML\ generation
\end{warpHTML}
```

 `\end{warpHTML}` Do *not* place anything else on the same line as `\end{warpHTML}`. The exact phrase is used to mark the end of the environment. Do not nest `warpHTML` inside itself.

 **nesting** `warpMathJax` may be used inside `warpHTML`.

Env `warpprint` Anything which is to be done only for print output is surrounded by a `warpprint` environment:

```
\begin{warpprint}
... something to be done only during traditional \PDF\ generation
\end{warpprint}
```

 `\end{warpprint}` As above, do not place anything else on the line with `\end{warpprint}`. Do not nest `warpprint` inside itself.

 **nesting**

Env `warpall` Anything which is to be done for any output may be surrounded by a `warpall` environment. Doing so is optional.

```
\begin{warpall}
... something to be done during print \PDF\ or \HTML\ output
\end{warpall}
```

 `\end{warpall}` As above, do not place anything else on the line with `\end{warpall}`. Do not nest `warpall` inside itself.

 **nesting**

Macros are also provided for print-only or HTML-only code:

`\warpprintonly` $\{\langle actions \rangle\}$

Performs the given actions only when print output is being generated.

`\warpHTMLonly` $\{\langle actions \rangle\}$

Performs the given actions only when HTML output is being generated.

Env `warpMathJax` Anything which is to be done only while using HTML output with MATHJAX is surrounded by a `warpMathJax` environment. Usually, this is `\CustomizeMathJax`, used to add emulation macros. `\end{warpMathJax}` must appear on its own line. Do not nest `warpMathJax` inside itself. `warpMathJax` may be used inside `warpHTML`.

⚠ `\end{warpMathJax}`
 ⚠ nesting

7.11 Commands to be placed into the warpprint environment

Certain print-related commands should always be placed inside a `warpprint` environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: `\parindent` `\parskip`
- Manual page positions such as the `textpos` package, which is emulated but only in a limited way.
- Anything changing the page counter. `lwarp` requires that the page counter not be adjusted during HTML output.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 13: [Troubleshooting](#).

7.12 Title page

In the preamble, place an additional block of code to set the following:

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
  Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

The title is used in the meta tags in the HTML files, unless overridden by `\HTMLTitle`, and the rest are used in `\maketitle`. To use a `\subtitle` or `\published` field, see section 67.8.

`\maketitle` Use `\maketitle` just after the `\begin{document}`, as this will establish the title of the homepage. Optionally, use a `titlepage` environment instead.

- Env `titlepage` The `titlepage` environment may be used to hold a custom title page. The `titlepage` will be set in a `<div>` class `titlepage`, and `\printtitle`, etc. may be used inside this environment.
- Env `titlingpage` Another form of custom title page, where `\maketitle` is allowed, and additional information may be included as well.
- `\title` `{\langle title \rangle}`
- ⚠ **HTML corrupted** Avoid newlines in the `\title`; these will interfere with the file break and css detection.
- ⚠ **newlines** Use a `\subtitle` command instead (section 67.8). The title will appear in the document `\maketitle` as a heading `<h1>`. The HTML meta title tag will also have this title, unless `\HTMLtitle` is used to set the meta title to something else instead.
- `\author` `{\langle author \rangle}`
- In `\author`, `\protect` may be needed before some formatting commands. In HTML, the author will appear in a `<div>` of class `author` in the `\maketitle`. If the `titling` package is used, the author will also appear in a HTML meta tag, but `\HTMLAuthor` may be necessary to create a plain list of names if `\author` had affiliations added. `\affiliation` is a new addition to `lwarp`.
- `\date` `{\langle date \rangle}`
- `\date` works as expected. In HTML, this will appear in a `<div>` class `titledate`.
- `\thanks` `{\langle text \rangle}`
- `\thanks` are allowed in the `titlepage` fields, and will be rendered as HTML notes at the bottom of the title page.

7.13 HTML page meta descriptions

- `\HTMLDescription` `{\langle A description of the web page. \rangle}`
 Default: (none)
- limitations** Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character (`"`).
- placement** Use `\HTMLDescription` just before `\begin{document}` to set the description of the home page, and also just before each sectioning command such as `\chapter` or `\section` where a new file will be generated, depending on `FileDepth`. For example, if `FileDepth` is 1, use `\HTMLDescription` just before each `\section` command, and that description will be placed inside the HTML page for that `\section`. The same description will be used for all following HTML files as well, until reset by a new `\HTMLDescription`. It is best to use a unique description for each HTML file.
- disabling** To disable the generation of HTML description meta tags, use:

```
\HTMLDescription{}
```

7.14 HTML homepage meta title

`\HTMLTitle` $\{\langle title \rangle\}$

Default: `\HTMLtitle{\thetitle}`

Sets the contents of the web page `<meta name="title">` element. May be set empty to cancel the meta title tag.

See section 7.6 for `\HTMLTitleBeforeSection` and `\HTMLTitleAfterSection`, used to set the title for HTML subpages.

7.15 HTML page meta author

`\HTMLAuthor` $\{\langle author \rangle\}$

Default: `\HTMLAuthor{\theauthor}`

Sets the contents of the web page `<meta name="author">` element. May be set empty to cancel the meta author tag.

`\author` may be used to create a list of authors and their affiliations, in several formats if using `authblk`, and these may not successfully parse properly into a sensible list for `\theauthor`. `\HTMLAuthor` may be used to set the meta tag to a simple list of names.

8 Special cases and limitations

Some commonly-used L^AT_EX expressions should be modified as follows to allow for a smooth conversion to both HTML and print-formatted outputs.

Need help?

See the [General Index](#) for “how-to”, and the [Troubleshooting Index](#) if something doesn’t work. A [Troubleshooting](#) section is also available. The [Index of Objects](#) contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category.

8.1 Things to avoid

In the document, avoid the following:

 **options with braces** **Package options:** Package options may cause problems with `lwarp`, especially if they include curly braces.

If selecting options with braces in `\usepackage` does not work:

```
\usepackage[font={it,small}]{caption}% does not work
```

... try instead selecting the package options before loading `lwarp`:

```
\PassOptionsToPackage{font={it,small}}{caption}
```

```
...
```

```
\usepackage{lwarp}
```

```
...
```

```
\usepackage{caption}
```

... or try setting package options after the package has been loaded:

```
\usepackage{caption}
```

```
\captionsetup{font={it,small}}
```

page counter: Do not adjust the page counter. If doing so is required for the print version, place the adjustment inside a `warpprint` environment.

Custom math environment macros: Do not use expressions such as `\beq` as a replacement for `\begin{equation}`.

Custom macros in section, figure, table names: Custom macros which appear in sectioning commands or float captions then appear in the `.toc`, `.lof`, and `.lot` lists, and should be made robust using `\newrobustcmd` or `\robustify` from `etoolbox`, `xparse`, etc.

When setting `FileSectionNames` to `true` to name the HTML files from the section names, the file names are created from sanitized versions of the chapter or section names, but the section names must be plain text or something which expands into plain text. Robust macros will not work at the sectioning level which is used for file names, but a robust macro or other complicated name may be used for the mandatory argument of `\chapter`, `\section`, etc., if a plain-text version is also included in the optional argument:

```
\chapter[Plain Name]{\ARobustMacro{Fancy Name}}
```

8.1.1 Invalid HTML

Additionally, some objects are valid \LaTeX , but invalid HTML. An example is a tabular inside `\textbf`, since HTML does not allow a table inside a span. `lwarp` will create the table, and the browser may support it, but the result is technically invalid.

8.2 Formatting

8.2.1 Text formatting

- △ `\bfseries`, etc. `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.
- △ **HTML special chars** `&`, `<`, and `>` have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.
 - program listings For program listings, the `listings` package is supported, and its `literate` option is used to convert `&`, `<`, and `>` to proper HTML entities.
 - verbatim The various `verbatim`-related environments do not convert `&`, `<`, and `>`, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

8.2.2 Small caps

- `Bool` `FixSmallCaps` Some fonts, such as `erewhon`, `utopia`, or `fbf`, and some packages such as `embrac`, copy/paste “SMALL CAPS” as all caps (“SMALL CAPS”), which `lwarp` then reads as all caps, so the text is printed in all caps. If small caps are being rendered as all caps, set:

```
\booltrue{FixSmallCaps}
```

- △ **CJK fonts** Some CJK fonts may not work if `FixSmallCaps` is set true.

8.2.3 Horizontal and vertical space and rules

- `\hspace` `\hspace` is converted to an inline HTML span of the given width, except that `0` width is ignored, a width of `.16667em` is converted to an HTML thin breakable space (`U+2009`), and a `\fill` is converted to a `\quad`.
- `\vspace` `\vspace` is ignored for HTML.
 - `\,` `~` and `\,` are converted to HTML entities.
- `\kern` `\kern` and `\hskip` are entered into the HTML PDF output as-is, then interpreted by `\hskip` `pdftotext`, and thus usually appear as a single space.
- `\rule` `\rule` is converted to an HTML rule of the same dimensions, of the currently selected

text color.

`\hrule` Both `\hrule` and `\vrule` are ignored for HTML. To create a horizontal dividing rule across the page, use `\hrulefill` in its own paragraph.

`\hrulefill` `\hrulefill` usually creates a one-inch rule, similar to a “fill in the blank”. If it is used at the start of a new paragraph, it creates a `<div>` with a thin horizontal border across the page, as would often be done with `\hrule`.

8.2.4 Text alignment

Use the environments `center`, `flushright`, `flushleft` instead of the macros `\centering`, `\raggedright`, `\raggedleft`.

 **figure & table alignment** `\centering`, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
...
```

8.2.5 Accents

Native \LaTeX accents such as `\`` will work, but many more kinds of accents are available when using Unicode-aware $X_{\text{e}}\LaTeX$ and $\text{Lua}\LaTeX$. If using accents in section names which will become file names, it is recommended to use the \LaTeX accents such as `\`` and `\v` instead of Unicode accents. The \LaTeX accents will have the accents stripped when creating the filenames, whereas the Unicode accents will appear in the file names, which may cause issues with some operating systems.

8.2.6 textcomp package

Pkg `textcomp` Some `textcomp` symbols do not have Unicode equivalents, and thus are not supported.

 **missing symbols** Many `textcomp` symbols are not supported by many system / browser fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

8.2.7 Superscripts and other non-math uses of math mode

Use `x` instead of $\text{\$}^{\text{\$}}\text{\$}$

8.2.8 Empty `\item` followed by a new line of text or a nested list:

[lists](#) Use a trailing backslash: `\item[label] \`

8.2.9 Filenames and URLs in lists or footnotes

filename underscore Escape underscores in the filenames:

```
\item[\href{file\_name.pdf}{text}]
```

8.2.10 relsize package

Pkg relsize For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified font-size.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarily restored, and so should work as expected.

 **not small** The HTML browser's setting for minimum font size may limit how small the output will be displayed.

8.3 Boxes and minipages

8.3.1 Marginpars

`\marginpar` [*left*] [*right*] `\marginpar` may contain paragraphs, but in order to remain inline with the surrounding text `lwarp` nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `
` tags.

`\marginparBlock` [*left*] [*right*] To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a ``. A line break will occur in the text where the `\marginBlock` occurs.

8.3.2 Save Boxes

 **HTML corrupted**

 **boxes** TeX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. `lwarp` uses methods which help avoid this problem.

 **minipage, \parbox** `\savebox` and related do not (yet) support `minipage` or `\parbox`.

8.3.3 Minipages

 **inline** A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made inline-block.

placement `minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a

`\newline` between them.

side-by-side Side-by-side minipages may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.

 **minipage in a span** There is limited support for minipages inside an HTML ``. An HTML `<div>` cannot appear inside a ``. While in a ``, minipages, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an “inline” format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

 **minipage size** When using `minipage`, `\parbox`, and `fminipage`, a virtual 6 × 9 inch text area is used for `\linewidth`, `\textwidth`, and `\textheight`, both for sizing the minipage, and also for its contents.

if width is `\linewidth` If a minipage or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML A new macro `\minipagefullwidth` requests that, during HTML output, the next single minipage or `\parbox` be generated without an HTML width attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version’s width makes no sense in HTML.

 **tabular, multicols** Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every minipage or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell `lwarp` to honor the specified widths of all following minipages and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell `lwarp` to ignore the specified widths.

 **multicol** Inside a `multicols`, `\linewidth` is divided by the specified number of columns.

 **text alignment** Nested minipages adopt their parent’s text alignment in HTML, whereas in regular L^AT_EX PDF output they do not. Use a `flushleft` or similar environment in the child minipage to force a text alignment.

8.3.4 Side-by-side minipages

Place side-by-side minipages inside a `center` environment, with horizontal space between them, such as `\quad`, `\qquad`, `\hspace`, or `\hfill`. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

8.3.5 Framed minipages and other environments

`\fbox` can only be used around inline `` items during HTML output, but HTML cannot place a block element such as a `<div>` for a minipage or a list inside of a ``. Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

`\fbox`
`\fboxBlock`
 Env `fminipage`

For a framed object, options include:

To remove the frame in HTML output: Place the `\fbox` command and its closing brace inside `warpprint` environments. This will nullify the frame for HTML output.

For inline text:

To frame the contents inline with some formatting losses in HTML: This is the default action of `\fbox` when enclosing a `minipage`. During HTML output, `\fbox` nullifies the HTML tags for `minipage`, `\parbox`, and lists. The contents are included as inline text inside the `\fbox`'s `` of class `framebox`. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.

For inline `minipage` and lists:

To frame the contents on their own line with improved formatting in HTML: A new command `\fboxBlock` is included, intended to be a direct replacement for `\fbox` for cases where the `\fbox` surrounds a `minipage`, table, or list. For print output, this behaves as `\fbox`. For HTML output, the contents are placed inside an HTML `<div>` with the class `framed`, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and `minipages` look nicer, and valid HTML is created for a `tabular`. While an `\fbox` containing a `tabular` is valid \LaTeX code, the result in HTML is problematic since a table is a `<div>` not a ``, so use `\fboxBlock` around a `tabular`, or else place the `tabular` inside a `minipage`, or use `fminipage`, described next. Also see below regarding the “Misplaced alignment tab character &.” error.

For display `tabular`, `minipages`, and lists:

To create a framed `minipage` in both print and HTML: A new environment `fminipage` is included. For print output, this is identical to `minipage`, except that it is also framed. For HTML output, this forms a `<div>` of class `framed`, the contents preserve their HTML formatting, and valid HTML is created for a `tabular`. Also see section 87 for a new environment `fcloorminipage`. Also see below regarding the “Misplaced alignment tab character &.” error.

colored boxes and frames:

To create colored frames and boxes: See section 633 for `xcolor`'s `\colorbox` and `\fcolorbox`, and `lwarp`'s additional `\colorboxBlock` and `\fcolorboxBlock`.

⚠ Misplaced alignment tab character &

To frame tables or verbatim environments: Place the contents inside a `fminipage`, or perhaps a `\fboxBlock` for a `tabular`. Also, if using `\fboxblock` with `tabular`, you will have to use `\StartDefiningTabulars` before the start of the macro which uses `\fboxBlock` and the `tabular`, and `\StopDefiningTabulars` afterwards. Also see the `lwarp` documentation for the `fancybox` package.

To frame equations: See section 248 for the `fancybox` package.

For fancy framed `minipages`: See packages `boxedminipage`, `shadow`, `fancybox`, `framed`, `mdframed`.

Custom environments: Use a custom environment to create a sidebar, containing a `BlockClass` environment with custom CSS formatting, and `\warpprintonly{\hrule}` command:

```
\begin{BlockClass}{frameminipage}% ignored in print output
% use \CSS\ to format div class framedminipage
```

```

\warpprintonly{\hrule} % only appears in print output
Contents
\warpprintonly{\hrule} % only appears in print output
\end{BlockClass}

```

8.3.6 fancybox package

Pkg fancybox
framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```

\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
... }{...
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}

```

framing alternatives

\fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example

The fancybox documentation's example of a framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method does lose some HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```

\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
...
\end{tabular}
\end{fminipage}
\end{table}

```

⚠ framed verbatim

lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```

\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \beginVerbatim
}{
  \endVerbatim
  \endfminipage
}

```

framed `\VerbBox` fancybox's `\VerbBox` may be used inside `\fbox`.

indented alignment `LVerbatim`, `\LVerbatimInput`, and `\LUseVerbatim` indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

8.3.7 mdframed package

Pkg `mdframed` Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for `mdframed` environments and frame titles.

△ loading When used, `lwarp` loads `mdframed` in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the `mdframed` source). Since `lwarp` does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont `theoremtitlefont` is not supported, since the following text is not in braces in the `mdframed` source.

ignored options `userdefinedwidth` and `align` are currently ignored.

css classes Environments created or encapsulated by `mdframed` are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class `[mdframedtitle]`. Subtitles are in a `<div>` of class `[mdframedsubtitle]`, and likewise for subsubtitles.

8.3.8 tcolorbox package

Pkg `tcolorbox` `tcolorbox` is emulated for HTML and MATHJAX, and supported as-is inside a `lateximage`

or `svg math`.

What has been tested to work (at least partly) includes:

- `tcolorbox`, `\tcbbox`.
- Title, subtitle.
- Upper, lower parts.
- Colors and title fonts.
- Floating objects.
- Some layered box features.
- Counters, labels, references.
- `listings`, `listingsutf8`.
- theorems: Theorems are supported. `math`, `ams equation`, etc. are not supported. Use a `tcolorbox` with regular math inside it. `\tcbboxmath` and `\tcbhighmath` are supported in `svg math`, and emulated in `MATHJAX`.
- Fitting features: `\tcbboxfit` becomes `\tcbbox` in `HTML`.
- Footnote numbering does not match the printed output.
- MathJax emulation is provided for common macros.

⚠ **math**

⚠ **footnotes**

⚠ **undefined references** If using `cleveref`, it may be necessary to name theorems such as:

```
\crefname{tcb@cnt@mytheo}{my theorem}{my theorems}
```

8.4 Section names

If using named `HTML` files, by selecting `\booltrue{FileSectionNames}`, the generated filenames may be simplified by using `\FilenameSimplify` and `\FilenameNullify`:

```
\FilenameSimplify {<text>}
```

To remove common short words from the automatically-generated filenames, replacing each with a single hyphen “-”, use `\FilenameSimplify`:

```
\FilenameSimplify*{-in-}
\FilenameSimplify*{A-}
```

The first example removes the word “in” in the middle of a filename, and the second example removes “A” at the start of the filename. The star forces the arguments to be detokenized, which is required for a plain-text comparison. (The unstarred form is used for a token-sensitive comparison, which is seldom required by the user.) After simplification, repeated hyphen characters will be further simplified to a single hyphen “-”. Finally, single hyphens at the start or end of the filename are removed.

```
\FilenameNullify {<macros>}
```

⚠ **macros in section names** Macro names may appear in the automatically-generated file names. To remove these, create *non-robust* nullified versions of the macros, ensuring that each line ends with a percent character % as shown below. These are placed inside `\FilenameNullify`, which adds them to the list of macros which are nullfied during filename generation. Low-level macros such as `\begingroup` will cause problems when nullfied. Many macros such as `\textbf` are already nullfied. `lwarp` also already nullifies built-in symbol and

`textcomp` macros, including if defined by `xunicode`, but not all `xunicode` macros. See the definition of `\LWR@nullfonts` for a complete list.

```
\FilenameNullify{%
  \renewcommand*{\macroname}[1]{#1}%
  \renewcommand*{\anothermacro}{}%
}
```

⚠ **duplicate filename** Avoid duplicate file names. Section names at levels which result in HTML file splits must be unique. `lwarp` will generate an error if a duplicate HTML filename is generated. Use the optional TOC caption entry parameter for formatting. Remember to `\protect` L^AT_EX commands which appear in section names and TOC captions.

⚠ **math in section names** If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring` from the `hyperref` package:

```
\section{Some math \texorpdfstring{$1+2=3$}{three}}
```

8.5 Cross-references

labels Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).

⚠ **label characters**

\nameref `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

⚠ **empty link**

8.5.1 Page references

⚠ **L^AT_EX page numbers** The printed page does not translate to the HTML page, so `\pageref` references are converted to parentheses containing `\pagerefPageFor`, which defaults to “see”, followed by a hyperlink to the appropriate object.

Ex:

```
\ref{sec:name} on page \pageref{sec:name}
```

in HTML becomes:

```
“Sec. 1.23 on page (see sec. 1.23)”.
```

`\pagerefPageFor` may be redefined to “page for”, empty, etc. See page 510.

8.5.2 `cleveref` and `varioref` packages

Pkg `cleveref` `cleveref` and `varioref` are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\pageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

Pkg `varioref`

⚠ **cleveref page numbers**

Ex:

```
\cpageref{tab:first,tab:second}
in html becomes:
“pages for table 4.1 and for table 4.2”
```

See `\cpagerefFor` at page 739 to redefine the message which is printed for page number references.

- ⚠ **varioref types** `cleveref` changes the behavior of `varioref` in that the reference type is automatically printed if `cleveref` is loaded. `Lwarp` requires `cleveref`, so the HTML version will always automatically print the reference types even if the print mode does not. The simplest way to make them match is to require the `cleveref` package for the document.

8.5.3 Hyperlinks, `hyperref`, and `url`

`Pkg hyperref` `lwarp` emulates `hyperref`, including the creation of active hyperlinks, but does not require that `hyperref` be loaded by the document.

`Pkg url`

- ⚠ **comments between arguments** Do not place a comment with a `%` character between arguments for `\hyperref`, etc., as it is neutralized for inclusion in HTML URLs.

`lwarp` can also load `url`, but `url` should not be used at the same time as `hyperref`, since they both define the `\url` command. `lwarp` does not (yet) attempt to convert `url` links into hyperlinks during HTML output, nor does the print version of `url` create hyperlinks.

- ⚠ **backref** When generating HTML, `lwarp`'s emulation of `hyperref` does not automatically load `backref`, so `backref` must be loaded explicitly.

8.5.4 Footnotes, endnotes, and page notes

`lwarp` uses native `LATEX` footnote code, although with its own `\box` to avoid the `LATEX` output routine. The usual functions mostly work as-is.

footnote numbering To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For `bigfoot`, `manyfoot`, or `perpage`:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

- ⚠ **MathJax, \footnotemark** If using `MATHJAX`, after each math expression with a `\footnotemark`, adjust the footnote counter by the number of `\footnotemarks`:

```
\[ (math expression with two instances of \footnotemark) \]
\warphTMLOnly{\addtocounter{footnote}{2}}
```

Similarly for endnotes, but *not* sidenotes.

Also for MATHJAX, \footnotename is used for a \footnotemark if the actual footnote number is not known. To redefine it, provide it before loading lwarp:

```
\providecommand{\footnotename}{something}
\usepackage{lwarp}
```

Similar for sidenotes. For endnotes:

```
\def\endnotename{something}% \def allows name to start with "end"
```

For the pagenote package, there is no \pagenotename to define, since there is no \pagenotemark command.

footmisc The footmisc stable option is emulated by lwarp.

 **sectioning commands** When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the stable option, provide a short toc entry, and \protect the \footnote:

```
\usepackage[stable]{footmisc}
...
\subsection[Subsection Name]
{Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc If using memoir class, with which lwarp preloads footmisc, the stable option must be declared before lwarp is loaded:



memoir

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
...
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust \secnumdepth instead.

fancybox, fancyvrb

 **\VerbatimFootnotes** If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

 **sectioning or displaymath**

```
\subsection[Subsection Name]
{Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

pfnote

 **pfnote numbers** While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

bigfoot, manyfoot

Verbatim footnotes are not yet supported.

 **verbatim**

If using the `bigfoot` package, and possibly also `manyfoot`, problems may occur with counter allocation because `lwarp` uses many counters, and there is a difference in how counters numbered 256 and up are handled in `pdfLATEX`. With `bigfoot` this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as an input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining `bigfoot` or `manyfoot` footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use `XYLATEX` or `LuaLATEX` instead of `pdfLATEX`.

8.5.5 `xr`, `xr-hyper`, and `xcite` packages

See section 5.17.

8.6 Front and back matter

8.6.1 Custom classes with multiple authors and affiliations

Some classes allow multiple authors and affiliations. Often it is possible to emulate these using a standard class along with `authblk`:

```
%\documentclass{customclass} % for print document
\documentclass{article} % for html document

\usepackage{lwarp}
\begin{warpHTML}
\usepackage{authblk}
\let\affiliation\affil % maybe required
\end{warpHTML}
```

8.6.2 Starred chapters and sections

HTML page and TOC

The following describes `\ForceHTMLPage` and `\ForceHTMLTOC`, which may be used for endnotes, glossaries, `tocbibind`, bibliographies, and the index. See the following sections where applicable. Continue here if interested in the reason for adding these commands to `lwarp`.

Some packages use `\chapter*` or `\section*` to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own HTML pages, and they are not given TOC entries.

`lwarp` provides a method to cause a starred section to be on its own HTML page, subject to `FileDepth`, and also a method to cause the starred section to have its own TOC entry during HTML output.

`\ForceHTMLPage` To place a starred section on its own HTML page, use `\ForceHTMLPage` just before the

`\chapter*` or `\section*`. `lwarp` will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using `\phantomsection` and `\addcontentsline` works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created, or when creating an EPUB where the TOC entry will point to the page before the starred section. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is created.

`\ForceHTMLTOC` To automatically force the HTML version of the document to have a TOC entry for a starred section, use `\ForceHTMLTOC` just before the `\chapter*` or `\section*`, and place `\phantomsection` and `\addcontentsline` inside a `warpprint` environment.

For print output, `\ForceHTMLTOC` and `\ForceHTMLPage` have no effect.

8.6.3 abstract package

Pkg abstract If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

⚠ inaccessible HTML page
⚠ missing TOC

8.6.4 titling and authblk

Pkg titling `lwarp` supports the native L^AT_EX titling commands, and also supports the packages `authblk` and `titling`. If both are used, `authblk` should be loaded before `titling`.

Pkg authblk

package support

If using the `titling` package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 67.8.

⚠ load order

`\published` and `\subtitle`

8.6.5 tocloft package

Opt [tocloft] titles If using `tocloft` with `tocbibind`, `anonchp`, `fncychap`, or other packages which change chapter title formatting, load `tocloft` with its `titles` option, which tells `tocloft` to use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

Pkg tocloft

Pkg tocloft

⚠ tocloft & other packages

8.6.6 appendix package

Pkg appendix During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and `also page` at the same time.

⚠ incorrect TOC link

8.6.7 pagenote package

Pkg pagenote `pagenote` works as-is, but the `page` option is disabled.

 **labels** Note that labels in page notes do not appear as expected, even in the print version.

8.6.8 endnotes package

Pkg endnotes To place the endnotes in the TOC, use:
 table of contents

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

HTML page To additionally have the endnotes on their own HTML page, if FileDepth allows:

```
\ForceHTMLPage
\theendnotes
```

 **\endnotemark numbering** If using MATHJAX, see section 8.5.4 regarding the use of \endnotemark and \endnotetext.

8.6.9 BibTeX

\etalchar Displays a superscript “+” to indicate “and others”.

 **Modify *.bib** When enough authors are cited for a source, BibTeX may use the \etalchar command to display a math superscript with a + character to indicate “and others”. Without modification, this will result in an “Improper \prevdepth” error. At present, lwarp requires that \etalchar be replaced by a text superscript. To do so, add to the start of the .bib file the following:

```
@PREAMBLE{"\let\etalchar\relax \newcommand{\etalchar}[1]{\textsuperscript{#1}}"}

```

8.6.10 xcite package

See section 5.17.

8.6.11 gloss package

Pkg gloss To process the HTML glossary:

 **compiling** `bibtex <projectname>_html.gls`

8.6.12 glossaries package

Pkg `glossaries`
[processing glossaries](#)

Opt `GlossaryCmd`

Default: `makeglossaries`

Opt [`lwarp`] `printglossary`

Opt [`lwarp`] `htmlglossary`

`lwarp` has the commands `lwarp` `printglossary` and `lwarp` `htmlglossary`, which process the glossaries created by the `glossaries` package using that package's `makeglossaries` program.

The shell command to execute is set by the `lwarp` option `GlossaryCmd`, which defaults to `makeglossaries`. The print or HTML glossary filename is appended to this command.

⚠ [makeglossaries not found](#)

In some situations it may be required to modify the default command, such as to add the `perl` command in front:

```
\usepackage[
  GlossaryCmd={perl makeglossaries},
] {lwarp}
```

[xindy language](#)

To set the language to use for processing glossaries with `xindy`:

```
\usepackage[
  GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for `makeglossaries` may be set as well.

[placement and toc options](#)

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
...
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
...
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries
```

⚠ [glossary style](#)

The default `style=item` option for `glossaries` conflicts with `lwarp`, so the style is forced to `index` instead.

⚠ [number list](#)

The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

[print/HTML versions](#)

The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

8.6.13 nomencl package

Pkg nomencl To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

8.6.14 Indexing overview

There are many ways to process indexes for a L^AT_EX document, including native L^AT_EX capabilities, a number of packages and classes, the possible availability of shell escape and *latexmk*, and the need to process print and HTML versions. *lwarp* attempts to provide easy recompilation of indexes along with the rest of the document, but the various indexing options must be set correctly. Numerous examples are given below. Some differ in minor details, so the important parts are highlighted in red, and options are in green.

Once set up properly, the entire document may be recompiled with **lwarpmk print** and **lwarpmk html**. In some cases, it will also be necessary to compile the indexes with **lwarpmk printindex** and **lwarpmk htmlindex**. A recompile may then be forced with **lwarpmk print1** and **lwarpmk html1**.

[manual processing](#) The user may continue to process indexes manually or by shell script without the use of *lwarpmk*, but adjustments will be required to process HTML indexes as well. In general, *.idx and *.ind files will be accompanied by *_html.idx and *_html.ind files.

[custom index style](#) If using a custom indexing style file, see sections [8.6.20](#) to [8.6.22](#).

[link appearance](#) To control how the index links appear in the HTML output, see the IndexRef option in section [7.5](#), page [108](#).

[source code](#) See section [77](#) for *lwarp*'s core index and glossary code, section [326](#) for index, section [537](#) for splitidx, section [325](#) for imakeidx, section [588](#) for tocbibind, and section [653.17](#) for memoir's indexing patches.

8.6.15 Indexing with makeidx, makeindex, xindy, xindex, gindex

[lwarpmk processing](#) The following allow the user to process indexes automatically, or using *lwarpmk*'s commands:

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

Prog makeindex **For a single index using *makeindex*:**

```
\usepackage[makeindex,latexmk] {lwarp}
```

The usual .idx and .ind files will be used, along with the new lwarp.ist style file. When creating the HTML index, "_html" is automatically appended to each of the names.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

To use a custom configuration file, see section [8.6.20](#).

Prog xindy **For a single index using *xindy*:**

```
\usepackage[
  xindy,
  xindyLanguage=english,           <optional>
  xindyCodepage=utf8,             <optional>
  latexmk                           <optional>
]{lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

To use a custom configuration file, see section [8.6.21](#).

Prog xindex **For a single index using *xindex*:**

```
\usepackage[
  xindex,
  latexmk                           <optional>
]{lwarp}
```

The usual `.idx` and `.ind` files will be used.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

To use a custom configuration file, see section [8.6.22](#).

Pkg gindex **For a single index using gindex:**

```
\usepackage[
  makeindex,
  makeindexStyle=gindex.ist,
  . . . or . . .
  makeindexStyle=gindexh.ist,
  latexmk
]{lwarp} <optional>
```

The usual .idx and .ind files will be used.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

To use a custom configuration file, copy `gindex.ist` to a new file, modify, then specify it with `MakeindexStyle` as above. *lwarp* will automatically adapt to *gindex*'s `\indexpagessep` and `\indexrangesep` settings.

8.6.16 Indexing with index

Prog index

lwarp is told how to use *makeindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

For multiple indexes using *makeindex* and *index*:

(Assuming that the second index has file extensions .sist and .sind)

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist
      -o <projectname>.sind <projectname>.sidx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist
      -o <projectname>_html.sind <projectname>_html.sidx
  }
]{lwarp}
\usepackage{index}
. . .
\makeindex
\newindex{secondname}{sidx}{sind}{Second Index}
```

⚠ WINDOWS

For WINDOWS, replace the two “;” characters with “&”.

When creating the HTML index, “_html” is automatically appended to the index filenames.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

If the `latexmk` option is selected for `lwarp`, `latexmk` will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

8.6.17 Indexing with `splitidx`

Prog `splitidx`

`lwarp` is told how to use *splitindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

If the `latexmk` option is selected for `lwarp`, `latexmk` will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

 **\thepage** When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to `\thepage` during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the `\index`-like action occurs, and then refer to `\arabic{LWR@autoindex}` instead of `\thepage` where the reference should occur.

See section 653.17 in the `lwarp-patch-memoir` package for the `\@@wrsindexhyp` macro as an example.

For multiple indexes using *makeindex* and *splitidx*:

```

\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    splitindex <projectname> -- -s lwarp.ist
  },
  HTMLIndexCmd={
    splitindex <projectname>_html -- -s lwarp.ist
  }
]{lwarp}
\usepackage{splitidx}
...
\makeindex
\newindex[Second Index]{secondname}

```

When creating the HTML index, “_html” is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

For multiple indexes using *xindy* and *splitidx*:

```

\usepackage[
  xindy, latexmk,
  PrintIndexCmd={
    splitindex -m xindy <projectname> -- -M lwarp.xdy
    -L english -C utf8 <optional>
  },
  HTMLIndexCmd={
    splitindex -m xindy <projectname>_html -- -M lwarp.xdy
    -L english -C utf8 <optional>
  }
]{lwarp}
\usepackage{splitidx}
...
\makeindex
\newindex[Second Index]{secondname}

```

When creating the HTML index, “_html” is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

8.6.18 Indexing with imakeidx

Prog imakeidx

Due to the number of methods which may be used to process multiple indexes, the options for style file and *xindy* language and codepage must be specified in one of several different ways. These are described in detail later in this section, but are summarized here.

If shell escape is used, *imakeidx* will automatically compile the indexes by itself. Options specifying a custom style file and *xindy* language and codepage must be specified for each `\makeindex` command using its `options=` option, which must include *lwarp*'s special `lwarp.ist` or `lwarp.xdy` file, or a file based on them. If using a custom indexing style file, see sections 8.6.20 to 8.6.22.

The `splitindex` option is also available if shell escape is used, in which case the `splitidx` package and *splitindex* program will also be used.

If shell escape is not possible, *latexmk* may be used to automatically compile the indexes. The style, language, and codepage options are specified with *lwarp*'s `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options. These are passed to *latexmk* by *lwarpmk*'s `lwarpmk printindex` and `lwarpmk htmlindex` commands.

Where shell escape and *latexmk* are not possible, *lwarpmk* may be used to manually compile the indexes. *lwarp*'s `PrintIndexCmd` and `HTMLIndexCmd` options are used.

For a single or multiple indexes using *makeindex* and *imakeidx*:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex]{imakeidx}
...
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

imakeidx will automatically compile the indexes. Shell escape is not required while using *makeindex*. *latexmk* may be specified, and if so it will be used for `lwarpmk print` and `lwarpmk html`, but *imakeidx* will actually create the indexes.

For a single or multiple indexes using *makeindex* and *splitindex* with *imakeidx*:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```

\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]

```

⚠ enable shell escape

Shell escape is required while using *splitindex*. For the first compile, use

```
Enter ⇒ pdflatex --shell-escape projectname.tex
```

```
Enter ⇒ pdflatex --enable-write18 projectname.tex (MiKTeX)
```

or similar with *xelatex* or *lualatex*. *lwarp* will remember that shell escape was used.

imakeidx will automatically execute *splitindex*, and will also use *makeindex* to compile the indexes.

latexmk may be specified, and if so it will be used for *lwarpmk print* and *lwarpmk html*, but *imakeidx* will actually create the indexes.

For multiple indexes using *xindy* and *imakeidx*, using shell escape:

Options may be given to *imakeidx*'s *\makeindex* command. The style file *lwarp.xdy* is automatically used for HTML output, and is not necessary for print output since the output will be similar. If language or codepage must be set, they should be specified as options for *\makeindex*, since *imakeidx* will process the indexes.

```

\usepackage[xindy,latexmk] {lwarp}
\usepackage[xindy,splitindex]{imakeidx}
. . .
\makeindex[
  options={ -M lwarp.xdy -L english -c utf8 }
]
\makeindex[
  name=secondname,
  options={ -M lwarp.xdy -L english -c utf8 }
]

```

⚠ enable shell escape

For the first compile, use

```
Enter ⇒ pdflatex --shell-escape projectname.tex
```

```
Enter ⇒ pdflatex --enable-write18 projectname.tex (MiKTeX)
```

or similar with *xelatex* or *lualatex*. *lwarp* will remember that shell escape was used.

imakeidx will automatically execute *splitindex* if selected, and will also use *xindy* to compile the indexes.

If selected, *latexmk* will automatically recompile the entire document as necessary.

For indexes using *xindy* and *imakeidx*, without shell escape, but *with latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```

\usepackage[
  xindy,
  xindyLanguage=english,           <optional>
  xindyCodepage=utf8,             <optional>
  latexmk,
]{lwarp}
\usepackage[xindy]{imakeidx}
...
\makeindex
\makeindex[name=secondname]

```

latexmk will create the indexes automatically when `lwarpmk print` and `lwarpmk html` are executed.

For indexes using *xindy* and *imakeidx*, without shell escape, and *without latexmk*:

lwarpmk must be told how to create the indexes:

```

\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
    <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
    secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
    <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
    secondname_html.idx
  }
]{lwarp}
\usepackage[xindy]{imakeidx}
...
\makeindex
\makeindex[name=secondname]

```

⚠ WINDOWS

For WINDOWS, replace the two “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name_html.idx.

Use

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

For multiple indexes using *xindex* and *imakeidx*, using shell escape:

xindex, *makeindex*, *imakeidx*, and *splitindex* can all work together:

```
\usepackage[%
  xindex,
  xindexConfig=-imakeidx,
  latexmk
]{lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
...
\makeindex[%
  options={ -s lwarp.ist} }
]
\makeindex[
  name=secondname,
  options={ -s lwarp.ist} }
]
```

⚠ enable shell escape

For the first compile, use:

Enter ⇒ **pdflatex --shell-escape projectname.tex**

Enter ⇒ **pdflatex --enable-write18 projectname.tex (MiKTeX)**

or similar with *xelatex* or *lualatex*. *lwarp* will remember if shell escape was used.

xindex will use *imakeidx*, and *imakeidx* will automatically execute *splitindex* if selected.

If selected, *latexmk* will automatically recompile the entire document as necessary.

8.6.19 Indexes with memoir**For a single index with memoir and *makeindex*:**

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
...
\makeindex
```

The usual *.idx* and *.ind* files will be used, along with the *lwarp.ist* style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

For multiple indexes with memoir and makeindex, using latexmk:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
...
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically when the user executes `lwarpmk print` and `lwarpmk html`.

For multiple indexes with memoir and makeindex, without latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  makeindex,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist secondname.idx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist secondname_html.idx
  }
]{lwarp}
...
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS

For WINDOWS, replace the two “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name_html.idx.

Use

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

For a single index with memoir and xindy:

```

\documentclass{memoir}
\usepackage[
  xindy,
  xindyLanguage=english,           <optional>
  xindyCodepage=utf8,             <optional>
  latexmk                           <optional>
]{lwarp}
...
\xindyindex
\makeindex

```

The usual .idx and .ind files will be used, along with the lwarp.xdy style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

```
Enter ⇒ lwarpmk printindex
```

```
Enter ⇒ lwarpmk htmlindex
```

to compile the indexes.

For multiple indexes with memoir and xindy, using latexmk:

lwarp's options are used, and are passed to *latexmk*.

```

\documentclass{memoir}
\usepackage[
  xindy,
  xindyLanguage=english,           <optional>
  xindyCodepage=utf8,             <optional>
  latexmk
]{lwarp}
...
\xindyindex
\makeindex
\makeindex[secondname]

```

lwarpmk will use *latexmk* to create the indexes automatically.

For multiple indexes with memoir and *xindy*, without latexmk:

lwarpmk must be told how to create the indexes:

```

\documentclass{memoir}
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
    <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
    secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
    <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
    secondname_html.idx
  }
]{lwarp}
...
\xindyindex
\makeindex
\makeindex[secondname]

```

⚠ WINDOWS

For *WINDOWS*, replace the four “;” characters with “&”.

<projectname> is the \jobname: if compiling “name.tex”, use the filenames name.idx and name_html.idx.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

8.6.20 Using a custom *makeindex* style file

Prog	makeindex	When using <i>makeindex</i> , <i>lwarpmk</i> uses the file <code>lwarp.ist</code> to process the index. This file
File	<code>lwarp.ist</code>	is over-written by <i>lwarp</i> whenever a print version of the document is processed.

To use a custom *makeindex* style file:

1. Copy `lwarp.ist` to a new filename such as `projectname.ist`
2. Make changes to `projectname.ist`. Keep the lines which refer to `\hyperindexref`. These lines creates the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.
3. If changing

```
delim_n -and- delim_r
```

in `projectname.ist`, then in the document preamble redefine

```
\IndexPageSeparator -and- \IndexRangeSeparator
```

to match.

Opt makeindexStyle

4. In the document source use the `makeindexStyle` option for `lwarp`:

```
\usepackage[
  . . . other options . . .
  makeindex,
  makeindexStyle=projectname.ist,
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

5. Recompile the print version, which causes `lwarp` to rewrite the `lwarpmk.conf` configuration file. This tells `lwarpmk` to use the custom `projectname.ist` file instead of `lwarp.ist`.

8.6.21 Using a custom *xindy* style file

Prog xindy
File lwarp.xdy

When using *xindy*, `lwarpmk` uses the file `lwarp.xdy` to process the index. This file is over-written by `lwarp` whenever a print version of the document is processed.

To use a custom *xindy* style file:

1. Copy `lwarp.xdy` to a new filename such as `projectname.xdy`
2. Make changes to `projectname.xdy`.

Keep the lines which refer to `\hyperindexref`:

```
(define-attributes (("hyperindexref"))
(markup-locref :open "\hyperindexref{" :close "}")
. . .
(markup-locref :open "\textit{\hyperindexref{" :close "}" :attr "textit")
```

These lines create the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

To create custom styles, refer to the lines for `\textbf` and `\textit`.

3. If changing any of

```
markup-locref-list :sep
markup-locclass-list :open
markup-locclass-list :sep
markup-crossref-layer-list :sep
markup-range :sep
```

in `projectname.xdy`, then in the document preamble redefine

```
\IndexPageSeparator -and- \IndexRangeSeparator
```

to match.

- Opt xindyStyle 4. In the document source use the xindyStyle option for lwarp:
- ```
\usepackage[
 ... other options ...
 xindy,
 xindyStyle=projectname.xdy,
]{lwarp}
```
- Likewise, refer to the custom style file if using \PrintIndexCmd, \HTMLIndexCmd, or \LatexmkIndexCmd.
5. Recompile the print version, which causes lwarp to rewrite the lwarpmk.conf configuration file. This tells *lwarpmk* to use the custom projectname.xdy file instead of lwarp.xdy.

### 8.6.22 Using a custom *xindex* style file

Prog xindex To use a custom *xindex* style file:

#### filename

1. Copy xindex-cfg.lua to a new filename such as xindex-projectname.lua. The filename must start with xindex- and end with .lua.
2. Make changes to xindex-projectname.lua.

3. If changing

```
itemPageDelimiter -and- rangeSymbol
```

in xindex-projectname.lua, then in the document preamble redefine

```
\IndexPageSeparator -and- \IndexRangeSeparator
```

to match.

- Opt xindexConfig 4. In the document source use the xindexConfig option for lwarp:
- ```
\usepackage[
  ... other options ...
  xindex,
  xindexConfig=projectname, % (without xindex- or .lua)
]{lwarp}
```
- Likewise, refer to the custom style file if using \PrintIndexCmd, \HTMLIndexCmd, or \LatexmkIndexCmd.
5. Recompile the print version, which causes lwarp to rewrite the lwarpmk.conf configuration file. This tells *lwarpmk* to use the custom xindex-projectname.lua file instead of the default xindex-cfg.lua.

8.6.23 Additional indexing limitations

 *xindy* with *hyperref* *xindy* and *hyperref* may not work well together for print output with “see”, “see also”, reference ranges, or stylized index references. It may be necessary to turn off hyper-referencing for indexes:

```
\usepackage[hyperindex=false]{hyperref}
```

 **empty index** If an HTML index is empty, it may be necessary to add the following before `lwarp` is loaded:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
. . .
\usepackage{lwarp}
```

makeindex custom display styles When using *makeindex*, custom display styles are possible:

```
\begin{warpprint}
\newcommand{\notesstyle}[1]{#1nn}
\end{warpprint}

\begin{warpHTML}
\makeatletter
\newcommand{\notesstyle}[1]{\LWR@doindexentry{#1} notes }
\makeatother
\end{warpHTML}
. . .
A sentence.\index{key|notesstyle}
```

xindy custom display styles For custom styles with *xindy*, see `lwarp.xdy` for `\textbf` and `\textit` as examples.

8.6.24 Index positions, `roc`, `tocbibind`

placement and `roc` options An index may be placed inline with other HTML text, or on its own HTML page:

Pkg `makeidx` **Inline, with a manual `roc` entry:**

A commonly-used method to introduce an index in a \LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg `makeidx` **On its own HTML page, with a manual `roc` entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg `tocbibind` **Inline, with an automatic `roc` entry:**

The `tocbibind` package may be used to automatically place an entry in the `roc`.

```

\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex

```

Pkg `tocbibind` **On its own HTML page, with an automatic toc entry:**

```

\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex

```

Opt [`tocbibind`] `numindex` Use the `tocbibind numindex` option to generate a numbered index. Without this option, the index heading has no number.

[numbered index section](#)

Other packages, such as `imakeidx`, may also have options for including the index in the Table of Contents.

Pkg `tocloft`

If using `tocloft` with `tocbibind`, `anonchp`, `fncychap`, or other packages which change chapter title formatting, load `tocloft` with its `titles` option, which tells `tocloft` to use standard L^AT_EX commands to create the titles, allowing other packages to work with it.

 [tocloft & other packages](#)

8.7 Math

8.7.1 Math in section names

 [math in section names](#) If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the toc entry without the math, or use `\texorpdfstring` from the `hyperref` package:

```

\section{Some math \texorpdfstring{$1+2=3$}{three}}

```

8.7.2 Rendering tradeoffs

[Math rendering](#) Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.

[svg files](#) Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

[svg inline](#) The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

- PNG files** Others L^AT_EX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.
- MathML** Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 10 regarding EPUB output with MATHJAX.

8.7.3 SVG option

- SVG math option** For SVG math, math is rendered as usual by L^AT_EX into the initial PDF file using the current font¹⁴, then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by L^AT_EX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML alt attribute carries the L^AT_EX code which generated the math, allowing copy/paste of the L^AT_EX math expression into other documents.

- SVG image font size** For the lateximage environment, the size of the math and text used in the SVG image may be adjusted by setting \LateximageFontSizeName to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by \LateximageFontScale, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

- SVG math copy/paste** For SVG math, text copy/paste from the HTML <alt> tags lists the equation number or tag for single equations, along with the L^AT_EX code for the math expression. For \mathcal{AMS} environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred \mathcal{AMS} environment, although the \tag macro will still appear inside the L^AT_EX math expression.

- ⚠ **SVG math size, baseline** SVG math sizing and baselines are improved if the graphics or graphicx package is loaded. An almost-invisible marker is placed at either end of the image to assist in cropping and computing the baseline. A warning is issued at the end of the compile if graphics or graphicx are not used.

- ⚠ **SVG math in T_EX boxes** SVG math does not work inside T_EX boxes, since a \newpage is required before and after each image.

8.7.4 MATHJAX option

- MATHJAX math option** The MATHJAX (mathjax.org) L^AT_EX-math to HTML converter may be used to display math.

Prog MathJax

¹⁴See section 638 regarding fonts and fractions.

When MATHJAX is enabled, math is rendered twice:

1. As regular L^AT_EX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of L^AT_EX, and
2. As detokenized printed L^AT_EX commands placed directly into the HTML output for interpretation by the MATHJAX display scripts. An additional script is used to pre-set the equation number format and value according to the current L^AT_EX values, and the MATHJAX equation numbering system is ignored in favor of the L^AT_EX internal system, seamlessly integrating with the rest of the HTML output, including any math appearing in non-MATHJAX SVG output.

8.7.5 Customizing MATHJAX

equation numbering lwarp detects and adjusts MATHJAX equation numbering format for article and book style equations as well as `amsmath \numberwithin` for chapters, sections, and subsections. Custom equation number formats may be set as follows, for example:

```
\renewcommand*{\theequation}{\Alph{section}.\arabic{equation}}
\AtBeginDocument{
  \renewcommand*{\theMathJaxsection}{\Alph{section}.}
}
```

△ subequation The `amsmath` `subequations` environment is supported, but only with `\alpha` subequation numbering.

global customizations MATHJAX does not have preexisting support every possible math function. Additional MATHJAX function definitions may be defined in the preamble. These will be declared at the start of each HTML page, and thus will have a global effect across all HTML pages.

Examples:

```
\begin{warpMathJax}
\CustomizeMathJax{
  \newcommand{\expval}[1]{\langle#1\rangle}
  \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arcsinh}{\text{arcsinh}}}
\CustomizeMathJax{\newcommand{\arccosh}{\text{arccosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
\end{warpMathJax}
```

△ slow compilation To avoid a slowdown in compile speed, use the `warpMathJax` environment to prevent its contents from being processed in print or SVG math output. Also, place each new definition inside its own `\CustomizeMathJax`. A warning to this effect is issued if an overly-long definition is attempted.

lwarp already provides MATHJAX customizations for some packages.

siunitx When using `siunitx`, a similar process may be used to add custom units:

```

\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\myunit}{\mathrm{WXYZ}}}
\CustomizeMathJax{\newcommand{\myunit}{\mathrm{\micro\myunit}}}
\end{warpMathJax}

```

advanced control For more advanced control over dynamically creating custom definitions, see as an example the `lwarp` definition for `\DeclarePairedDelimiterX`, in section 378, [mathtools](#).

local customizations For customizations local to the current HTML page only, macros may be defined as follows:

```

\begin{warpMathJax}
\(\ \newcommand{\macroname}{. . . } \)
\(\ \newcommand{\anothername}{. . . } \)
\end{warpMathJax}

```

To maintain compile speed, use the `warpMathJax` environment, and use a separate math environment for each definition.

`\ifstar` For MATHJAX, use `\ifstar` instead of `\@ifstar`:

```

\CustomizeMathJax{
  \def\myname{
    \ifstar\starredaction\unstarredaction
    % (Do not place anything after!)
  } }

```

`\ifnextchar` For MATHJAX, use `\ifnextchar` instead of `\@ifnextchar`:

```

\CustomizeMathJax{\def\myname{\ifnextchar X \found\notfound}}

```

“X” may be a single ASCII character, or a hex number inside braces, ex:

```

\CustomizeMathJax{\def\myname{\ifnextchar{0x7B}\found\notfound}}

```

Use “(” or “{0x28}” for a left parenthesis, “{0x7B}” for a left brace, “{0x7D}” for a right brace, or “{0x5C}” for a backslash.

8.7.6 MATHJAX limitations

MATHJAX limitations Limitations when using MATHJAX include:

Prog MathJax



`\multicolumn`, `multirow`

- MATHJAX does not support `\multicolumn` or `multirow`. These may be used in text tabulars or SVG math, but in MATHJAX math arrays they are emulated. `\multicolumn` only fills a single cell, resulting in a short row. `\multirow` simply prints its text on the first line.



footnotes

- Footnotes are emulated when used inside a MATHJAX expression. For an equation with a single footnote, the correct footnote number is used. For non-equations, `\footnotename` is used instead, since the actual number cannot be tracked. See section 8.5.4 regarding the use of footnotes with MATHJAX.



references

- Inside a MATHJAX expression, references to equations work within the same HTML web page, but do not work when referring to an equation in a different

HTML web page. Outside of a MATHJAX expression, in the text body, references work as expected.

- [lateximage](#)
 - Math appearing inside a lateximage, and therefore also inside a Tikz or picture environment, is rendered as SVG math even if MATHJAX is used in the rest of the document.
- [siunitx](#)
 - For siunitx, see [siunitx package](#), section 8.7.12.
- [physics](#)
 - For physics, see [physics package](#), section 8.7.14.
- [tabbing](#)
 - A tabbing environment is emulated using an HTML <pre>. While MATHJAX is enabled inside tabbing, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.
- [\text](#)
 - MATHJAX includes the *textmacros* extension, which supports various macros which are commonly used inside \text, such as \textbf and text accents. Lwarp supports this extension.
-  [other macros and packages](#)
 - Many other math-related macros and packages are not directly supported by MATHJAX, including \ensuremath and occasionally-used macros such as \relax. While using MATHJAX, lwarp provides emulation for many of these macros, as well as for footnotes and emulation for dozens of packages (see table 2). In many cases these emulations simply ignore the package in a source-compatible way. Others produce a result which represents the meaning, even if they don't look exact. Look up each package in this document for a description of the limitations of each.

8.7.7 Catcode changes

- [preamble macros with math](#) The math shift character \$ is not set for HTML output until after the preamble. Macros defined in the preamble which contain \$ must be enclosed between \StartDefiningMath and \StopDefiningMath to temporarily change to the HTML meaning of \$:

```
\StartDefiningMath
\newcommand{. . .}
\StopDefiningMath
```

As an alternative, use \ (and \) instead of \$, in which case \StartDefiningMath and \StopDefiningMath are not necessary.

If a package defines macros using \$, it may be necessary to use \StartDefiningMath and \StopDefiningMath before and after loading the package.

8.7.8 Complicated inline math objects

- [\inlinemathnormal](#)
 - An inline math expression is usually converted to a reusable hashed svg math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as $x+1$, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses.
- [\inlinemathother](#)
 - Another problem is complicated contents which do not expand well in an alt tag.
- [changing contents](#)
- [complicated alt tag](#)

The macro `\inlinemathother` may be used before a dynamic math expression, and `\inlinemathnormal` after. Doing so tells `lwarp` to use an unhashed SVG math image, even if `MathJax` is in use. See section 43.

8.7.9 Complicated display math objects

`\displaymathnormal` By default, or when selecting `\displaymathnormal`, `MATHJAX` math display environments print their contents as text into `HTML`, and `SVG` display math environments render their contents as `SVG` images and use their contents as the `alt` tag of `HTML` output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated `Tikz` pictures, compilation will fail.

`\displaymathother` When selecting `\displaymathother`, it is assumed that the contents are more complicated than “pure” math. An example is an elaborate `Tikz` picture, which will not render in `MATHJAX` and will not make sense as an `HTML alt` tag. In this mode, `MATHJAX` is turned off, math display environments become `SVG` images, even if `MATHJAX` is selected, and the `HTML alt` tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as `Tikz` pictures are more likely to compile successfully.

8.7.10 ntheorem package

Pkg `ntheorem`

⚠ Font control

This conversion is not total. Font control is via `CSS`, and the custom `LATEX` font settings are ignored.

⚠ `cref` reference format undefined

If the print version does not use `cleveref`, place all `\theoremstyle` and `\newtheorem` declarations in the preamble inside `\AtBeginDocument`.¹⁵ For some theorems, it may also be required to add inside `\AtBeginDocument` something such as:

```
\AtBeginDocument{ % if not using cleveref package
  \theoremstyle{definition}
  \newtheorem{dtheorem}{Definition}
  . . .
  \usepackage{etoolbox} % for \ifdef
  \ifdef{\cref}{
    \crefname{Proof}{Proof}{Proofs}
  }{}
}
```

⚠ Equation numbering

`ntheorem` has a bug with equation numbering in \mathcal{AMS} environments when the option `thref` is used. `lwarp` does not share this bug, so equations with `\split`, etc, are numbered correctly with `lwarp`'s `HTML` output, but not with the print output. It is recommended to use `cleveref` instead of `ntheorem`'s `thref` option.

¹⁵`lwarp` uses `cleveref` for the `HTML` conversion, and loads `cleveref` `\AtEndPreamble`, just before `\AtBeginDocument`.

8.7.11 mathtools package

- Pkg `mathtools` `showonlyrefs` is disabled, as it conflicts with `cleveref`, which is used by `lwarp`. Equation numbers may not match the print version.
- ⚠ **equation numbering**
- ⚠ **italic correction** `mathic` is not emulated for HTML.
- ⚠ **MATHJAX** If using `MATHJAX`:

- `mathtools disallowspaces` does not work for `MATHJAX`. Protect brackets which are not optional arguments, such as:


```
\begin{gathered}{}
[p]=1 . . .
\end{gathered}
```
- `showonlyrefs` does not work in `MATHJAX`, and will result in a difference in equation numbering compared to the print version.
- Due to `MATHJAX` limitations, the following do not render well: `\overbracket`, `\underbracket`, `\overbrace`, `\underbrace`, `rcases`, `drcases`, `\Aboxed`, and `\ArrowBetweenLines`.
- For the new cases-like environments, `\text` must be used to set the normal roman font if desired.
- `alignat` in `MATHJAX` requires math mode, but in `LATEX` it doesn't. It may be required to use `warpHTML` and `warpprint` to isolate a version for each mode.
- `\DeclarePairedDelimiter` and related must be in the preamble before `\begin{document}`.

8.7.12 siunitx package

- Pkg `siunitx` `fractions` Due to `pdftotext` limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.
- ⚠ **math mode required** Some units will require that the expression be placed inside math mode.
- ⚠ **tabular** Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.
- ⚠ **MathJax** For math mode with `svg` display, the original `siunitx` code is used while generating the `svg` image. For text mode, `lwarp` uses an emulation which provides a very effective HTML interpretation of `siunitx`. For math expressions while using `MATHJAX`, a limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. `siunitx` macros with more than one optional value cannot absorb the second optional value, and complicated parsing such as for `\ang` is not supported. The result usually looks fine, and otherwise is enough to get the meaning across.

`lwarp`'s `MATHJAX` emulation for `siunitx` is meant to be a stop-gap measure until an extension is included in `MATHJAX`. As of this writing, the third-party `siunitx` extension for

MATHJAX is not currently hosted at any public CDN, thus siunitx is not usable with this extension unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJax script, but lwarp's emulation would have to be disabled as well.

Document modifications required for MATHJAX:

`custom units` • Custom units may be added with `\CustomizeMathJax`. See the `lwarp-siunitx` code for examples.

 `unit spacing` • Units work better using `~` between units instead of using periods.

 `\square, \cubic` • To square or cube compound units, enclose the following compound units in braces:

```
\cubic{\centi\meter}
```

Single units do not require braces.

Also see [MATHJAX option](#), section 8.7.4.

8.7.13 units and nicefrac packages

`Pkg units` `units` and `nicefrac` work with lwarp, but MATHJAX does not have an extension for `units` or `nicefrac`. These packages do work with lwarp's option `svgmath`.

`Pkg nicefrac`

8.7.14 physics package

`Pkg physics` `physics` works as-is for HTML with SVG math.

For MATHJAX, the MATHJAX v3 `physics` extension is used.

8.8 Graphics

`Pkg graphics` Avoid using the `\includegraphics scale` option. Change:

`Pkg graphicx` `\includegraphics[scale=<xx>]{ . . . }`

 `scale`

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

`\includegraphics file formats` For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps` image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf or .eps image is referred to with its file extension, the extension will be changed to .svg for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo To convert a PDF image to SVG, use the utility *pdftocairo*:

PDF to SVG

Enter ⇒ **pdftocairo -svg filename.pdf**

Prog lwarpmk pdftosvg For a large number of images, use *lwarpmk*:

Enter ⇒ **lwarpmk pdftosvg *.pdf (or a list of filenames)**

Prog lwarpmk epstopdf For EPS images converted to PDF using the package *epstopdf*, use

Prog epstopdf
epstopdf package

Enter ⇒ **lwarpmk pdftosvg *.PDF**

to convert to SVG images.

DVI latex When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **lwarpmk epstopdf *.eps (or a list of filenames)**

Enter ⇒ **lwarpmk pdftosvg *.pdf (or a list of filenames)**

PNG and JPG For PNG or JPG while using *pdf_latex*, *lua_latex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

△ graphics vs. graphicx If using the older *graphics* syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer *graphicx* syntax. Note that viewports are not supported by *lwarp*—the entire image will be shown.

△ viewport

△ viewport
units

For `\includegraphics`, avoid px and % units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use ex or em. For fixed-sized images, use cm, mm, in, pt, or pc. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options `\includegraphics` accepts width and height, origin, rotate and scale, plus new class and alt keys.

HTML class With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML alt tags Likewise, the `\includegraphics` alt key adds an HTML alt tag to an image, and is

ignored for print output. If not assigned, each image is given an alt tag according to `\ImageAltText`.

`\rotatebox` `\rotatebox` accepts the optional origin key.

 **browser support** `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike L^AT_EX, so expect some ugly results for scaling and rotating.

8.8.1 tikz package

 **displaymath and matrices** Pkg `tikz` If using display math with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the `tikz` expression must be replaced with `\&`.

8.8.2 grffile package

 **matching PDF and SVG** Pkg `grffile` `grffile` is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

8.8.3 color package

Pkg `color` `color` is superseded by `xcolor`, and `lwarp` requires several of the features of `xcolor`. When `color` is requested, `xcolor` is loaded as well.

8.8.4 xcolor package

Pkg `xcolor` `\colorboxBlock` and `\fcolorboxBlock` are provided for increased HTML compatibility, and they are identical to `\colorbox` and `\fcolorbox` in print mode. In HTML mode they place their contents into a `<div>` instead of a ``. These `<div>`s are set to `display: inline-block` so adjacent `\colorboxBlock`s appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for `\colorboxBlock` and `\fcolorboxBlock` are created by `lwarp`'s core if `xcolor` is loaded.

background: none `\colorbox` and `\fcolorboxBlock` allow a background color of `none`, in which case only the frame is drawn, which can be useful for HTML.

color support Color definitions, models, and mixing are fully supported without any changes required.

- [colored tables](#) `\rowcolors` is supported, except that the optional argument is ignored so far.
- [colored text and boxes](#) `\textcolor`, `\colorbox`, and `\fcolorbox` are supported.
- [\color and \pagecolor](#) `\color` and `\pagecolor` are ignored. Use `css` or `\textcolor` where possible.

8.8.5 epstopdf package

- `Pkg epstopdf` Images with an `.eps` extension will be converted to `.pdf`. The HTML output uses the `.svg` version, so use

 [convert to .svg](#)

Enter ⇒ `lwarpmk pdftosvg <listofPDFfiles>`

to generate `.svg` versions.

8.8.6 pstricks package

- `Pkg pstricks` All `pstricks` content should be contained inside a `pspicture` environment.

 [use pspicture](#)

8.8.7 pdftricks package

- `Pkg pdftricks` The `pdftricks` image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

 [convert image files](#)

Enter ⇒ `lwarpmk pdftosvg <jobname>-fig*.pdf`

8.8.8 psfrag package

- `Pkg psfrag` The `psfrags` environment is modified to use `lateximage` to encapsulate the image. Always use a `psfrags` environment to contain any local `\psfrag` macros and the associated `\includegraphics` or `\epsfig` calls. Outside of a `psfrags` environment, `psfrags` adjustments will not be seen by `lwarp`.

 [use psfrags](#)

 Tip: Use a mono-spaced font for the tags in the EPS file.

8.8.9 pstool package

- `Pkg pstool` `\graphicspath` is ignored, and the file directory must be stated.

 [path and filename](#) The filename must not have a file extension.

Use

Enter ⇒ `lwarpmk html`

followed by

Enter ⇒ **lwarpmk limages**

8.8.10 asymptote package

Pkg asymptote To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

8.8.11 overpic package

Pkg overpic The macros `\overpicfontsize` and `\overpicfontskip` are used during HTML generation. These are sent to `\fontsize` to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the `overpic` and `Overpic` environments.

 **scaling**

8.8.12 Multimedia packages

Pkg multimedia The packages `multimedia`, `movie15`, and `media9` are supported.

Pkg movie15 HTML5 `<audio>` and `<video>` objects are created for `.mp3` and `.mp4` files.

Pkg media9 HTML5 `<embed>` objects are created for `http` and `ftp` links.

`\href` links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For `media9`, a multimedia object is inserted for each `addressource=`, as well as each `flashvars source=` and `src=`. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside `\warpprintonly` or the `warpprint` environment.

Each HTML multimedia object includes the poster text, except for `<embed>` objects. For `movie15`, the `text` option is supported to specify the poster text.

The `width`, `height`, and `totalheight` options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

`media9 \addmediapath` is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each `<audio>` and `<video>` object.

`media9` slideshows are not supported.

`\hyperlinkmovie`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YOUTUBE™ video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

8.9 Tabbing

The tabbing environment works, except that `svg math` and `lateximages` do not yet work inside the environment.

 **math in tabbing** If math is used inside tabbing, place tabbing inside a `lateximage` environment, which will render the entire environment as a single `svg` image.

8.10 Tabular

8.10.1 tabular environment

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, `siunitx S` columns, or the packages `multirow`, `longtable`, `supertabular`, or `xtab`.

Defining macros and environments:

- When defining environments or macros which include `tabular` and instances of the `&` character, it may be necessary to make `&` active before the environment or macro is defined, then restore `&` to its default catcode after, using the following commands. These are ignored in print mode.

```
\StartDefiningTabulars
```

```
<define macros or environments using tabular and & here>
```

```
\StopDefiningTabulars
```

This includes before and after defining any macro which used `\ttabbox` from `floatrow`.

 **Misplaced alignment tab character &**

 **floatrow**

⚠ tabular inside another environment

- When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```

\StartDefiningTabulars % (& is used in a definition)
\newenvironment{outerenvironment}
{
  \tabular{cc}
  left & right \\
}
{
  \TabularMacro\ResumeTabular
  left & right \\
  \endtabular
}
\StopDefiningTabulars

```

For developers:

- To automate the use of `\StartDefiningTabulars` and `\EndDefiningTabulars`, these macros may be embedded inside an HTML environment definition to automatically change the catcode of `&` before absorbing the arguments. Another environment may be embedded as well.

```

% Does the work after the catcode has been changed:
\newcommand*\LWR@HTML@subsomename}[2]{%
  . . .
  \otherenvironmentname [<args>] {<args>} % for example
}
% Change catcode before absorbing arguments:
\newcommand*\LWR@HTML@somename{%
  \StartDefiningTabulars
  \LWR@HTML@subsomename
}
% Change catcode again at the end:
\newcommand*\LWR@HTML@endsomename}{%
  . . .
  \endotherenvironmentname % for example
  \StopDefiningTabulars
}
% Combine with the existing print definition:
\LWR@formattedenv{somename}

```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use `\TabularMacro` just before the macro. This is ignored in print mode.

```

\TabularMacro\somemacro & more row contents \\

```

Column specifiers:

@ and !

- Only one each of `@` and `!` is used at each column, and they are used in that order.

\multirow

- In `\multirow` cells, the print version may have extra instances of `<`, `>`, `@`,

and ! cells on the second and later rows in the `\multirow` which do not appear in the HTML version.

⚠ `\newcolumntype`

- `\newcolumntype` is ignored; unknown column types are set to l.

Rules:

vertical rules

width and trim

combined rules

- Doubled `\hlines`, `\midrules`, and vertical rules are supported.
- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.
- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.
- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:


```
\cmidrule{2-3} \[-2ex]
\bottomrule
```

 The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

⚠ `\warpprintonly`

⚠ Misplaced `\noalign`

- For `\toprule` and `\bottomrule`, when combined with a `warpprint` or `warpHTML` environment, if a “Misplaced `\noalign`” error occurs, change


```
This & That \endhead
```

 to


```
\warpprintonly{This & That \endhead}
```

 and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevant to HTML output.

Other:

longtable headings

⚠ S columns

- `tabularx` ignores the width, but X columns do produce paragraph columns or multicolumns.
- For `longtable`, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.
- For S columns (from the `siunitx` package), while producing print output, anything non-numeric must be placed inside `{ }` braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by `lwarp`'s tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:


```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\\}
```

⚠ `tabular` inside a ``

- In `LATEX`, a `tabular` may be placed inside a `minipage`, but in HTML a `<table>` may not be inside a ``. If this situation is detected, a warning is printed instructing the user to isolate the `` using `\warpprintonly` or the `warpprint` environment.

8.10.2 multirow package

vposn

- Note that recent versions of `multirow` include a new optional `vposn` argument.

multirow cells

- For `multirow`, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
... & \multirow{2}{.5in}{text} & ...
... & \mrowcell & ...
```

colored cells

- The `multirow` documentation regarding colored cells recommends using a negative number of rows. This will not work with `lwarp`, so `\warpprintonly` and `\warpHTMLonly` must be used to make versions for print and HTML.

with `\multicolumn`

- See section 405.2 for `\multicolumnrow`.

⚠ `\multicolumn & \multirow`

`lwarp` does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

⚠ skipped cells

As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines, `\mcolrowcell` must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

⚠ empty cells

```
... & \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text} & ...
... & \mcolrowcell & \mcolrowcell & ...
... & \mcolrowcell & \mcolrowcell & ...
```

⚠ `MathJax`

- `MATHJAX` does not support `multirow`, so it is emulated to only print its text on the first row. `\multirow` works as expected in text tabulars or `svg math`.

8.10.3 longtable package

Pkg `longtable`

Use one of either `\endhead` or `\endfirsthead` for both print and HTML, and use a `\warpprintonly` macro to disable the other head phrase, and also the `\endfoot` and `\endfirstfoot` phrases. (See section 8.10.4 if using `threeparttablex`.)

```

\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[ . . . ] \endhead % or \endfirsthead
[ . . . ] \endfoot
[ <lastfoot macros> ] \endlastfoot
}
. . . table contents . . .
\warppHTMLonly{
[ <lastfoot macros> ] % HTML last footer, without \endfoot
% or \endlastfoot.
}
\end{longtable}

```

⚠ **Misplaced \noalign** Use the `\warpprintonly` macro instead of the `\warpprint` environment. Doing so helps avoid “Misplaced `\noalign`.” when using `\begin{\warpprint}`.

⚠ **\kill** `\kill` is ignored, place a `\kill` line inside

```
\begin{\warpprint} . . . \end{\warpprint}
```

or place it inside `\warpprintonly`.

⚠ **lateximage** `longtable` is not supported inside a `lateximage`.

8.10.4 threeparttablex package

Pkg `threeparttablex` `threeparttablex` is used with `longtable` and `booktabs` as follows:

```

\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[ . . . ] \endhead % or \endfirsthead
[ . . . ] \endfoot
\bottomrule \insertTableNotes \endlastfoot
}
. . . table contents . . .
\warppHTMLonly{ % HTML last footer
\bottomrule
\UseMinipageWidths % optional
\insertTableNotes
\endlastfoot
}
\end{longtable}

```

table width The table notes are created using a `\multicolumn`. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, `lwarp` guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use `\UseMinipageWidths` before `\insertTableNotes`. The width is then specified, and in many cases the result is an improvement in overall table layout.

8.10.5 supertabular and xtab packages

Pkg supertabular For `\tablefirsthead`, etc., enclose them as follows:

⚠ Misplaced alignment
tab character &

```
Pkg xtab
\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a lateximage.

8.10.6 colortbl package

Pkg colortbl Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.

⚠ row/cell color colortbl ignores the overhang arguments.

8.10.7 ctable package

⚠ Misplaced alignment
tab character & Use `\StartDefiningTabulars` before one or more `\ctables`, and `\StopDefiningTabulars` after. These change the meaning of the ampersand `&` character.

8.10.8 bigdelim package

⚠ use \mrowcell Pkg bigdelim `\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

```
<-> a b
left { c d
      e f
      g h
<-> i j
```

For MATHJAX, limited emulation is provided which merely prints the delimiter and optional text in the first row.

8.11 Floats

8.11.1 Float contents alignment

 **figure & table alignment** `\centering`, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
...
```

8.11.2 float, trivfloat, and/or algorithmicx together

Pkg float If using `\newfloat`, `trivfloat`, and/or `algorithmicx` together, see section 599.1.

Pkg trivfloat

Pkg algorithmicx

 **package conflicts**

Pkg caption

Pkg subcaption

8.11.3 caption and subcaption packages

Package options may cause problems with `lwarp`, especially if they include curly braces.

If selecting options with braces in `\usepackage` does not work:

```
\usepackage[font={it,small}]{caption}% does not work
```

... try instead selecting the package options before loading `lwarp`:

```
\PassOptionsToPackage{font={it,small}}{caption}
...
\usepackage{lwarp}
...
\usepackage{caption}
```

... or try setting package options after the package has been loaded:

```
\usepackage{caption}
\captionsetup{font={it,small}}
```

 **numbering** To ensure proper float numbering, set caption positions such as:

```
\captionsetup[figure]{position=bottom}
\captionsetup[subfigure]{position=bottom}
\captionsetup[table]{position=top}
\captionsetup[subtable]{position=top}
```

Similarly for `longtable`. These positions depend on where the user places the `\caption` command inside each float.

8.11.4 subfig package

Pkg subfig

⚠ **table numbering** To have correct sub table numbers:

```
\usepackage{caption}
\captionsetup[table]{position=top}
```

⚠ **lof/lotdepth** At present, the package options for lofdepth and lotdepth are not working. These counters must be set separately after the package has been loaded.

⚠ **horizontal spacing** In the document source, use `\hfill` and `\hspace*` between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

8.11.5 floatrow package

Pkg floatrow

⚠ **Misplaced alignment
tab character &
subfig package**

Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 8.10.1.

When combined with the subfig package, while inside a subfloatrow `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ **\FBwidth, \FBheight**

The emulation of floatrow does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

8.11.6 keyfloat package

Pkg keyfloat

⚠ **keywrap**

If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the `lw` option.)

8.12 KOMA-SCRIPT classes

Cls komascript

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

`\captionformat`, `\figureformat`, and `\tableformat` are not yet emulated.

⚠ **Not fully tested!** [Please send bug reports!](#)

Some features have not yet been tested. Please contact the author with any bug reports.

8.13 MEMOIR class

`\cls memoir` **captions** `lwarp` uses `caption`, which causes a warning from `memoir`. This is normal. Adjust captions via `caption`, instead of `memoir`.

⚠ **options clash** While emulating `memoir`, `lwarp` pre-loads a number of packages (section 653.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading `lwarp`:

```
\documentclass{memoir}
...
\PassOptionsToPackage{options_list}{package_name}
...
\usepackage{lwarp}
...
\usepackage{package_name}
```

⚠ **version numbers** `memoir` emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since `lwarp` is intended to support the freestanding packages, which are often newer than the date declared by `memoir`, it is hoped that `memoir` will update and change its emulated version numbers to match.

`\label{bookmark}{tag}` `\label` accepts an optional (bookmark) argument, but this is ignored in HTML.

⚠ **comment** The `comment` environment is from the `comment` package, and thus requires that the `\begin` and `\end` each be on its own line:

```
\begin{comment}
This is a comment.
\end{comment}
```

`\newcomment` Comments defined with `\newcomment` use `memoir`'s definitions, and behave as expected, where the `\begin` and `\end` do have to each be on its own line.

⚠ **verbatim footnotes** `\verbfootnote` is not supported.

⚠ **\newfootnoteseries** `\newfootnoteseries`, etc. are not supported.

⚠ **page notes** `lwarp` loads `pagenote` to perform `memoir`'s `pagenote` functions, but there are minor differences in `\pagenotesubhead` and related macros.

page notes with cleveref To add support for pagenotes with `cleveref`, add:

```
\crefname{pagenote}{page note}{page notes}
\Crefname{pagenote}{Page note}{Page notes}
```

page note \nameref Note that for print mode, `\nameref` print the section name where the page notes are

declared in the text, but for HTML it prints the name where the page notes are printed.

- ⚠ **poems** Poem numbering is not supported.
- ⚠ **verbatim** The verbatim environment does not yet support the memoir enhancements. It is currently recommended to load and use `fancyvrb` instead.
- ⚠ **glossaries** The memoir glossary system is not yet supported by *lwarpmk*. The `glossaries` package may be used instead, but does require the glossary entries be changed from the memoir syntax to the `glossaries` syntax.
- ⚠ **framewithtitle, titledframe** The custom frame commands in the memoir manual may be emulated by placing the original definitions in the preamble inside `warpprint` environments, and then providing an HTML equivalent:

```

\begin{warpHTML}
\newcommand{\FrameTitle}[2]{%
  \textbf{#2}
}

\newenvironment{framewithtitle}[2][\FrameFirst@Lab\ (cont.)]{%
  \begin{fminipage}{\linewidth}
  \textbf{#2}
  \begin{minipage}{\linewidth}
  }
{\end{minipage}\end{fminipage}}

\newcommand{\TitleFrame}[2]{%
  \par
  \textbf{#1}\par
  \fboxBlock{#2}
}

\newenvironment{titledframe}[2][\FrameFirst@Lab\ (cont.)]{%
  \par
  \textbf{#2}
  \begin{fminipage}{\linewidth}
  }
{\end{fminipage}}
\end{warpHTML}

```

8.14 International languages

- ⚠ **section and file names** If using *pdf_latex* with the setting `\booltrue{FileSectionNames}`, non-ASCII text in section names can result in corrupted HTML file names. *pdf_latex* may be used if setting `\boolfalse{FileSectionNames}`, in which case HTML file numbers will be generated.

For correct HTML file names, use *xel_latex*, *lual_latex*, or dedicated document classes / engines.

(As of this writing, this warning is only relevant to the `kotex` package.)

8.15 Miscellaneous packages

8.15.1 verse and memoir

Pkg `verse` When using `verse` or `memoir`, always place a `\\` after each line.

Cls `memoir`
`\attrib` The documentation for the `verse` and `memoir` packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. `lwarp` provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len `\vleftskip` These lengths are used by `verse` and `memoir` to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

Len `\vleftmargini`

Len `\HTMLvleftskip`

Len `\HTMLleftmargini`

⚠ **spacing** Horizontal spacing relies on *pdftotext*'s ability to discern the layout (`-layout` option) of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLvleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space. During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused *pdftotext* to shift everything over.

⚠ **verse margin**

8.15.2 newclude package

Pkg `newclude` `newclude` modifies `\label` in a non-adaptive way, so `newclude` must be loaded before `lwarp` is loaded:

⚠ **loading**

```
\documentclass{article}
... <font setup>
\usepackage{newclude}
\usepackage[warpHTML]{lwarp}
...
```

8.15.3 babel package

Pkg `babel` When French is used, the caption separator is changed to a dash. To restore it to a colon, the following may be placed before `lwarp` is loaded:

⚠ **\CaptionSeparator**

```
\renewcommand*{\CaptionSeparator}{:~}
```

punctuation spaces Also when French is used, `lwarp` creates fixed-width space around punctuation by patching `\FBcolonspace`, `\FBthinspace`, `\FBguillspace`, `\FBmedkern`, `\FBthickkern`, `\FBtextellipsis`, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a `warpprint` environment so that the user's changes do not affect the HTML output.

⚠ **customized spacing**

8.15.4 polyglossia package

Pkg `polyglossia` `lwarp` uses `cleveref`, which has some limitations when using `polyglossia`, possibly resulting in the error

```
! Undefined control sequence. . . . \@begindocumenthook
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by `cleveref`, then select other languages using `\setotherlanguages`.

Once the print version works with `cleveref` and `polyglossia`, the HTML version should work as well using `lwarp`.

8.15.5 todonotes and luatodonotes packages

Pkg `todonotes` The documentation for `todonotes` and `luatodonotes` have an example with a `todo` inside a caption. If this example does not work it will be necessary to move the `todo` outside of the caption.
Pkg `luatodonotes`

8.15.6 fixme

Pkg `fixme` External layouts (`\fxloadlayouts`) are not supported.

⚠ **external layouts**

User control is provided for setting the HTML styling of the “faces”. The defaults are as follows, and may be changed in the preamble after `fixme` is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

8.15.7 acro package

 **formats** Define acronymn formats using `\textbf` instead of `\bfseries` etc.

8.15.8 chemfig package

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```
\begin{lateximage}[-chemfig-~\PackageDiagramAltText]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

8.15.9 chemformula package

 **chemformula with MATHJAX** `chemformula` works best without `MATHJAX`. If `MATHJAX` is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The `chemformula` package adapts to `array`, but does not know about `MATHJAX`, and `MATHJAX` does not know about `chemformula`.)

While using `MATHJAX`, `\displaymathother` may also be used for other forms of display and inline math which contain `chemformula` expressions.

8.15.10 mhchem package

See section 386.

8.15.11 xparse package

Pkg `xparse` To remove from the log any warnings about redeclaring objects, place the following before `lwarp` is loaded:

```
\usepackage[log-declarations=false]{xparse}
```

8.15.12 kotex package

Pkg `kotex` See section 8.14 regarding `pdflatex` and Korean section names.

 **Korean section names**

9 Compiling using custom shell commands

`lwarp` and `lwarpmk` try to make it easy to process print and HTML compilation tasks in most situations. Depending on the operating system, command-line options, T_EX engine, and `lwarp` options, the commands `lwarpmk print` and `lwarpmk html` are automatically set up to correctly recompile the project. These actions may be overridden using `lwarp` options, thus allowing the use of packages such as `perltex` and `pythontex`.

9.1 Command options

Opt `PrintLatexCmd` The `lwarp` options `PrintLatexCmd` and `HTMLLatexCmd` are used to set customized commands to be executed by `lwarpmk print` and `lwarpmk html`.
 Opt `HTMLLatexCmd`

PrintLatexCmd should be set to shell commands which take `project.tex` and generate `project.pdf`.

HTMLLatexCmd should be set to take `project_html.tex` and generate `project_html.pdf`. `lwarpmk` will then take `project_html.pdf` and automatically convert it and generate `project.html`.

9.2 Literal character macros

The `lwarp` package options are parsed by T_EX, and so some characters require the use of a special macro to represent them. See table 9. `\LWRopquote` and `\LWRopseq` may be used to increase operating-system portability. `\jobname` must have `_html` appended for processing HTML. `\space` may be necessary between other macros.

 **macro not found** To use these macros, either `kvoptions-patch` must be loaded before `lwarp`:

```
\usepackage{kvoptions-patch}
\usepackage[
  PrintLatexCmd={ ... } ,
  HTMLLatexCmd={ ... }
]{lwarp}
```

Table 9: Literal character macros

Character	Macro	Comment
%	\LWRpercent	
\$	\LWRdollar	
&	\LWRamp	
%	\LWRhash	
\	\LWRbackslash	
' or "	\LWRopquote	Depends on the operating system.
& or &&	\LWRopseq	Depends on the operating system.
(space)	\space	Forces an extra space.
(jobname)	\jobname	Without file extension.

or `\lwarpsetup` must be used to set `PrintLatexCmd` and `HTMLLatexCmd`:

```

\usepackage[...]{lwarp}
\lwarpsetup{
  PrintLatexCmd=
  {
    latex tm \LWRopseq
    dvips -o tm-pics.ps tm.dvi \LWRopseq
    ps2pdf tm-pics.ps \LWRopseq
    pdflatex tm.tex
  } ,
  HTMLLatexCmd=
  {
    latex tm_html \LWRopseq
    dvips -o tm_html-pics.ps tm_html.dvi \LWRopseq
    ps2pdf tm_html-pics.ps \LWRopseq
    pdflatex tm_html.tex
  }
}

```

9.3 *latexmk*

Prog `latexmk` If *latexmk* is used for a project, it may be easiest to continue using it.

`latexmk project.tex` would create `project.pdf` as normal.

`latexmk project_html.tex` would create `project_html.pdf`, then

`lwarpmk pdftohtml project_html.pdf` would take `project_html.pdf` and convert it to `project.html`.

Pkg `sagetex` *latexmk* may simplify the use of packages such as `sagetex`.

9.4 `perltex` package

Pkg `perltex` The `lwarp` package option settings to use `perltex` would be similar to:

```
\usepackage[
  . . .
  PrintLatexCmd={perltex -latex=pdflatex project.tex} ,
  HTMLLatexCmd={perltex -latex=pdflatex project_html.tex} ,
  . . .
]{lwarp}
```

⚠ “impure” math Place `perltex` math expressions between `\displaymathother` and `\displaymathnormal`, or `\inlinemathother` and `\inlinemathnormal`. See section 8.7.9.

9.5 `pythontex` package

Pkg `pythontex` An example using `pythontex`:

```
\usepackage[
  . . .
  PrintLatexCmd={
    pdflatex project.tex \LWRopseq
    pythontex project \LWRopseq
    pdflatex project.tex
  } ,
  HTMLLatexCmd={
    pdflatex project_html.tex \LWRopseq
    pythontex project_html \LWRopseq
    pdflatex project_html.tex
  } ,
  . . .
]{lwarp}
```

Another possibility is to use *latexmk*, placing the `latexmk . . .` commands in the `PrintLatexCmd` and `HTMLLatexCmd` options. While using these options, the `lwarp` option `latexmk` would not be used.

⚠ “impure” math No attempt has yet been made to make `pythontex` robust with HTML output. Some math objects must be surrounded by `\displaymathother ... \displaymathnormal`, or

⚠ HTML look-alike `\inlinemathother ... \inlinemathnormal`. Displays of code may have to be enclosed inside a `lateximage` environment to prevent `<`, `>` and similar from being interpreted by the browser as HTML entities.

9.6 Other packages

Pkg `sympytex` Other packages such as `sympytex` and `rterface` would be set up similar to `pythontex`,

Pkg `rterface`

and the same warnings would apply.

9.7 *make* program

Prog **make** To use `lwarp` with the *make* program, have the makefile take `project.tex` and generate the print version `project.pdf`, as normal. `\usepackage{lwarp}` must be used, and it generates `lwarpmk.conf` when the print version is created.

To generate HTML, first have `project_html.tex` be compiled to generate `project_html.pdf`. This must be in PDF format. Finally, have `project_html.pdf` be converted to HTML using `lwarpmk pdftohtml project_html.pdf`, and convert SVG math with `lwarpmk limages`.

9.8 UTF-8 locale

 **UTF-8 locale** *lwarpmk* uses the *texlua* program, which sets the “locale” to “C”, including for external operating-system calls such as when executing `lwarpmk html`. In some cases, an external program called from the user’s document may require the use of a UTF-8 “locale”. For UNIX-related operating systems, it may be required to use `lwarp`’s custom compilation options to add a locale change:

```
\usepackage{lwarp}[
  PrintLatexCmd={
    env LC_CTYPE=en_US.UTF-8
    xelatex -shell-escape project.tex
  }
  HTMLLatexCmd={
    env LC_CTYPE=en_US.UTF-8
    xelatex -shell-escape project_html.tex
  }
]
```

Pkg **ditaa** The only example seen so far where this is required is the *ditaa* package, where the locale change allows the use of UTF-8 with Xe^LA^TE^X and *ditaa*. To use Lua^AT^EX instead, the locale change would have to be made inside the *ditaa* package where it calls the *ditaa* program.

10 EPUB conversion

lwarp does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

<meta> author To assign the author's name for regular lwarp HTML files, and also for the EPUB, use `\HTMLAuthor {<name>}`. This assigns the name to the `<meta>` author element. It may be set empty, and it defaults to `\theauthor`.

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

FormatEPUB	
Bool	FormatEPUB
	Default: <code>false</code>
	FormatEPUB changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

To help convert lwarp HTML output to EPUB, add

```
\booltrue{FormatEPUB}
```

to the project's source preamble after `\usepackage{lwarp}`. The EPUB version of the document cannot co-exist with the regular HTML version, so

```
Enter ⇒ lwarpmk cleanall
```

```
Enter ⇒ lwarpmk html
```

```
Enter ⇒ lwarpmk limages
```

to recompile with the FormatEPUB boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.

The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program *Calibre* (<https://calibre-ebook.com/>).

 **search order**

The EPUB conversion program must know what order the files are included. For lwarp projects, set the EPUB conversion software to do a breadth-first search of the files. For *Calibre*, this option is found in

Preferences → Plugins → File type plugins → HTML to Zip

 **encoding**

Check the box **Add linked files in breadth first order**. Set the document encoding as `utf-8`, which is what lwarp generates for HTML, even if the original printed document uses some other encoding.

⚠ section breaks

The EPUB-conversion program must also know where the section breaks are located. For a list of `lwarp`'s section headings, see table 11. For example, an `article` class document would break at `\section`, which is mapped to HTML heading level `<h4>`, whereas a `book` class document would break at `\chapter`, which is HTML heading level `<h3>`. For *Calibre*, this option is found in

Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)

Select the “magic wand” to the right of this entry box, and set the first entry

Match HTML tags with tag name:

to “h4”. (Or “h3” for document classes with `\chapters`.) The Detect chapters at field should then show

`//h:h4` — or — `//h:h3`

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the `lwarp`-generated HTML files may be loaded by *Calibre*, and then converted to an EPUB.

MATHJAX support

MATHJAX may be used in EPUB documents. Some e-readers include MATHJAX, but any given reader may or may not have a recent version, and may or may not include extensions such as support for `siunitx`.

`lwarp` adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader's version of MATHJAX, so `lwarp` requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn't work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MATHJAX, especially for equations numbered by chapter, or where `siunitx` support is important.

11 Word-processor conversion

lwarp may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LIBREOffice works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. lwarp provides some assistance in locating these frame boundaries, as shown below.

11.1 Activating word-processor conversion

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

	FormatWP
Bool	FormatWP
Default: false	
	Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Additionally, honors the booleans WPMarkFloats, WPMarkMinipages, WPMarkTOC, and WPMarkLOFT.

To help modify lwarp HTML output for easier import to a word processor, add

```
\booltrue{FormatWP}
```

formatting adjustments

to the project's source preamble after lwarp is loaded. The following changes are then made to the HTML output:

- If using a class without chapters, \section and lower are shifted up in level for the HTML heading tags. The CSS has not been changed, so the section heading formats will not match the normal HTML output, but when imported to *LibreOffice Writer* the higher section headings will import as **Heading 1** for the title, **Heading 2** for \section, etc.
- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and <div>s, but they are no longer useful when the document has been imported into a word processor.
- An additional <div> with an id encapsulates each float and minipage, which on import into *LibreOffice Writer* causes a thin frame to appear around the text block for each.
- Float captions are given an explicit italic formatting.

- Tabular rule borders are made explicit for *LibreOffice Writer*. LIBREOffice displays a light border around each cell while editing, even those which have no border when printed, and lwarp also uses a light border for thin rules, so it will be best to judge the results using the print preview instead of while editing in LIBREOffice.
- `\includegraphics` and `svg` math width and height are made explicit for LIBREOffice.
- `\hspace` is approximated by a number of `\quads`, and rules are approximated by a number of underscores.
- Explicit HTML styles are given to:
 - `\textsc`, etc.
 - `\underline`, `soul` and `ulem` markup.
 - `center`, `flushleft`, `flushright`.
 - `\marginpar`, `keyfloat`, `sidenotes`, `floatflt`, and `wrapfig`.
 - `fancybox` `\shadowbox`, etc.
 - The L^AT_EX and T_EX logos.

- Honors several booleans:

WPMarkFloats: Marks the begin and end of floats.

WPMarkMinipages: Marks the begin and end of minipages.

WPMarkTOC: Marks the location of the Table of Contents.

WPMarkLOFT: Marks the locations of the List of Figures/Tables.

WPMarkMath: Prints L^AT_EX math instead of using images.

WPTitleHeading: Adjusts title and section headings.

Several of these may be used to add markers to the HTML text which help determine where to adjust the word processor document after import.

11.2 Additional modifications

WPMarkFloats

Bool WPMarkFloats
Default: false

Adds

```
=== begin table ===
...
=== end ===
```

or

```
=== begin figure ===
...
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.

WPMarkMinipages

Bool WPMarkMinipages
 Default: false

Adds

```
=== begin minipage ===
...
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

WPMarkTOC

Bool WPMarkTOC
 Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set false, the actual TOC is printed instead.

WPMarkLOFT

Bool WPMarkLOFT
 Default: false

While formatting for word processors, adds

```
=== list of figures === and/or
=== list of tables ===
```

where each of these lists would have been. This helps identify where to insert the actual lists.

If set false, the actual lists are printed instead.

WPMarkMath

[siunitx](#)
 Bool WPMarkMath
 Default: false
 Prog TeXMaths

While formatting for word processors, prints math as \LaTeX code instead of creating SVG images or MATHJAX. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

When using the `siunitx` package, enter

```
\usepackage{siunitx}
```

in the *TeXMaths* preamble. Equation numbering is problematic for \mathcal{AMS} math environments.

Table 10: Section HTML headings for word-processor conversion

Section	HTML headings*			
	With \chapter		Without \chapter	
	WPTitleHeading true	WPTitleHeading false	WPTitleHeading true	WPTitleHeading false
Title	<h1>	plain	<h1>	plain
\book	<div>	<div>	<div>	<div>
\part	<h2>	<h1>	<h2>	<h1>
\chapter	<h3>	<h2>	—	—
\section	<h4>	<h3>	<h3>	<h2>
\subsection	<h5>	<h4>	<h4>	<h3>
\paragraph	<h6>	<h5>	<h5>	<h4>
\subparagraph		<h6>	<h6>	<h5>

* For default depths when not FormatWP, see table 11 on page 204.

WPTitleHeading

Bool WPTitleHeading
Default: false
section headings

While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LIBREOffice. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 10 on page 188.

11.3 Recommendations

TOC, LOE, LOT For use with *LibreOffice Writer*, it is recommended to:

1. Set `\booltrue{FormatWP}`
2. Set `\booltrue{WPMarkTOC}` and `\boolfalse{WPMarkLOFT}`
3. Use `lwarp` to generate the HTML document.
4. Copy/paste from the HTML document into an empty *LibreOffice Writer* document.
5. Manually insert a LIBREOffice TOC in the LIBREOffice document.
6. Manually add frames around each float, adding a caption which is cut/pasted from each float's simulated caption.
7. Manually create cross references.

This process yields a document with an actual LIBREOffice Table of Contents, but a simulated List of Figures and List of Tables.

siunitx For siunitx, remember to adjust the preamble as mentioned above.

LO view border options LIBREOffice has options in the **View** menu to turn on/off the display of thin borders around table cells and text objects.

11.4 Limitations

Floats and captions are not explicitly converted to LIBREOffice floats with their own captions. Floats are surrounded by a thin frame in the LIBREOffice editor, and may be marked with `WPMarkFloats`, but are not given a proper LIBREOffice object frame. Captions are given an explicit italic formatting, but not a proper LIBREOffice paragraph style.

Cross references are not actual LIBREOffice linked cross references.

The List of Figures and List of Tables are not linked. The pasted pseudo LOF and LOT match the numbering of the L^AT_EX and HTML versions.

Equation numbering is not automatic, but the equation numbers in SVG math will match the L^AT_EX and HTML output. SVG math is recommended when using the \mathcal{AMS} environments, which may have multiple numbered equations per object.

As of when last checked, LIBREOffice ignores the following:

- Minipage alignment.
- Tabular cell vertical alignment.
- Image rotation and scaling.
- Rounded border corners, which are also used by:
 - `\textcircled`
 - `booktabs trim`
- `\hspace` and `rules`, also used by `algorithmic`.
- Coloring of text decorations, used by `soul` and `ulem`.
- Overline text decoration, used by `romanbar`.

LIBREOffice also has limitations with frames and backgrounds:

- Multiple lines in an object are framed individually instead of as a whole.
- Nested frames are not handled correctly.
- Images inside boxes are not framed correctly.
- Spans with background colors and frames are not displayed correctly.

12 Modifying lwarp

- locating something** To quickly find the source for a package in `lwarp.dtx`, search for `*packagename`, such as `*siunitx`.
- Likewise, to quickly find the source for a file in `lwarp.dtx`, search for `*filename`, such as `*lwarp.css`.
- Purely text-based packages probably will work as-is when generating HTML.
- Look to existing code for ideas on how to expand into new code.
- image of TeX output** An environment may be converted to a `lateximage` then displayed with an image of the resulting L^AT_EX output. See section 91 for an example of the `picture` environment.
- css classes** To create a custom HTML block or inline CSS class, see section 51.9.
- print/HTML macros** To create print and HTML versions of the same macro or environment, see section 35.
-  **TeX boxes** Any TeX boxes must be undone, as SVG math or `lateximages` require `\newpage`, which will not work in a TeX box.

12.1 Creating a development system

The following creates a local development system for `lwarp` on a TeXLive system in a UNIX-like environment. Doing so allows anything requesting `lwarp` to use the development version instead of whichever version is installed in TeXLive.

Create a development directory:

Place into this directory `lwarp.dtx` and `lwarp.ins`.

To create `lwarp.sty`, execute

```
Enter ⇒ pdflatex lwarp.ins
```

which creates `lwarp.sty` and several hundred additional `lwarp-*.sty` files for the various packages which are supported.

To create the initial documentation `lwarp.pdf`, execute

```
Enter ⇒ pdflatex lwarp.dtx
```

To make the development files visible to other projects:

Create the directory

```
/usr/local/texlive/texmf-local/tex/latex/local/lwarp
```

Inside this directory, create the file `update`, containing:

```
rm lwarp-*.sty
ln -s /path_to_dev_directory/lwarp*.sty .
ln -s /path_to_dev_directory/lwarp_baseline_marker.png .
ln -s /path_to_dev_directory/lwarp_baseline_marker.eps .
mktexlsr
```

Run `./update` now, and whenever a new `lwarp-*` package is added.

To make the development version of *lwarpmk* visible to other projects:

```
cd /opt
ln -s /usr/local/texlive/texmf-local/bin/x86_64-linux texbin_local
cd texbin_local
ln -s ../../scripts/lwarp/lwarpmk.lua lwarpmk
cd /usr/local/texlive/texmf-local/scripts/
mkdir lwarp
cd lwarp
ln -s /path_to_dev_directory/lwarpmk.lua lwarpmk
```

Verify that the correct version is found with

Enter \Rightarrow **which lwarpmk**

To make the local versions visible to the shell:

Paths must be set by the shell startup, such as in `.bashrc` and `.cshrc`:

In `.bashrc`:

```
PATH=/opt/texbin_local:/opt/texbin:$PATH
```

In `.cshrc`:

```
setenv PATH ${HOME}/bin:/opt/texbin_local:/opt/texbin:${PATH}
```

To fully compile the lwarp documentation and indexes:

```
pdflatex lwarp.ins
pdflatex lwarp.dtx
pdflatex lwarp.dtx <if necessary>
makeindex -s gglo.ist -o lwarp.gls lwarp.glo <indexes>
splitindex lwarp.idx - -s gind.ist
pdflatex lwarp.dtx
pdflatex lwarp.dtx <if necessary>
makeindex -s gglo.ist -o lwarp.gls lwarp.glo <indexes>
splitindex lwarp.idx - -s gind.ist <again>
pdflatex lwarp.dtx
pdflatex lwarp.dtx <if necessary>
```

(The second round of index processing is required to fully resolve the final Index of Indexes.)

To make it easier to update the documentation after a minor change, it is useful to create a command script called `make_index`, containing:

```
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
splitindex lwarp.idx -- -s gind.ist
```

 **references**

Note that Index of Indexes and the cross-references to the indexes may not be correct until the above has been accomplished.

12.2 Modifying a package for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic L^AT_EX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

When creating HTML, lwarp redefines the `\usepackage` and `\RequirePackage` macros such that it first looks to see if a `lwarp-⟨packagename⟩.sty` version exists. If so, the lwarp version is used instead. This modular system allows users to create their own versions of packages for lwarp to use for HTML, simply by creating a new package with a `lwarp-` prefix. If placed in the local directory along with the source code, it will be seen by that project alone. If placed alongside the other `lwarp-` packages where T_EX can see it, then the user's new package will be seen by any documents using lwarp. (Remember `mktexlsr` or `texhash`.)

An `lwarp-⟨packagename⟩.sty` package is only used during HTML generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful HTML conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing `lwarp-` packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new `lwarp-` package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a “local” prefix according to the package name, and `@` characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for HTML output. Only the “user-facing” macros need to be nullified or emulated.

Each `lwarp-*` package should first call either of:

```
\LWR@ProvidesPackageDrop
```

— *or* —

```
\LWR@ProvidesPackagePass
```

If “Drop”ped, the original print-version package is ignored, and only the `lwarp-` version is used. Use this where the original print version is useless for HTML. If “Pass”ed, the original package is loaded first, with the user-supplied options, then the `lwarp-` version continues loading as well. See section 431 ([ntheorem](#)) for an example of selectively disabling user options for a package. Use this when HTML output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a `lwarp-` version.

12.2.1 Adding a package to the lwarp.dtx file

When adding a package to `lwarp.dtx` for permanent including in `lwarp`, provide the `lwarp-<packagename>` code in `lwarp.dtx`, add its entry into `lwarp.ins`, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to `lwarp.dtx` in section 20.1. This causes `lwarp` to stop with an error if `packagename` is loaded before `lwarp`. Finally, add an entry in table 2, **Supported packages and features**, and also the Updates section.

12.3 Modifying a class for lwarp

If a class loads additional packages, it will be required to modify the class for `lwarp`, since `lwarp` must be loaded before most other packages.

To work with `lwarp`, a class must first set up anything which replicates the functions of the basic \LaTeX classes, load any required fonts, then load `lwarp`, then finally load and adjust any other required packages.

12.4 Testing lwarp

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

Remember that the configuration files are only rewritten when compiling the printed version of the document.

When changing the source to *lwarpmk* or a css file in `lwarp.dtx`:

1. Change the source in `lwarp.dtx`.
2. `pdflatex lwarp.ins`
3. `pdflatex lwarp.dtx`
4. If modifying *lwarpmk* the new version should now be active.
5. If modifying css files:
 - (a) For the document, `lwarpmk print` to update the css files in the project.
 - (b) Reload the HTML document to see the effect of the new css files.

Sometimes it is worth checking the `<project>_html.pdf` file, which is the PDF containing HTML tags. Also, `<project>_html.html` has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and css code.

12.5 Modifying *lwarpmk*

Prog `lwarpmk` In most installations, `lwarpmk.lua` is an executable file located somewhere the operating system knows about, and it is called by typing **lwarpmk** into a terminal.
File `lwarpmk.lua`

A project-local copy of `lwarpmk.lua` may be generated, modified, and then used to compile documents:

1. Add the `lwarpmk` option to the `lwarp` package.
2. Recompile the printed version of the document. The `lwarpmk` option causes `lwarp` to create a local copy of `lwarpmk.lua`
3. The `lwarpmk` option may now be removed from the `lwarp` package.
4. Copy and rename `lwarpmk.lua` to a new file such as `mymake.lua`.
5. Modify `mymake.lua` as desired.
6. If necessary, make `mymake.lua` executable.
7. Use `mymake.lua` instead of `lwarpmk.lua`.

13 Troubleshooting

13.1 lwarp package error conditions and warnings

lwarp tests for a number of error conditions and prints appropriate warnings. The following is a summary of these conditions.

13.1.1 Configuration file `lwarpmk.conf`

File does not exist: The configuration file must exist for `lwarpmk`.

Incorrect Unix /Windows selection: The operating system which was detected by `lwarp`. So far only Unix and Windows are supported.

Incorrect delimiter characters. Older versions of `lwarpmk` used a different delimiter.

Source name is set to lwarp: `lwarp` has recently been recompiled in this directory, which overwrote the project's configuration files. This also occurs if `lwarpmk` is executed in `lwarp`'s source directory.

Incorrect operating system: The configuration file was set for a different operating system, perhaps due to sharing in a collaborative project.

Outdated configuration files: `lwarp` has been updated since this project was last compiled. If there appears to be a valid print command in the file, `lwarpmk` displays this to instruct the user how to recompile the print version, which then updates the configuration files.

The designated source file does not exist: For whatever reason...

Unknown engine: `lwarp` cannot determine which engine is being used. Supported are DVI \LaTeX , PDF \LaTeX , Xe \LaTeX , Lua \LaTeX , and up \LaTeX .

13.1.2 Image generation with `lwarpmk limages`

“Wait a moment for the images to complete before reloading page.”:

Images are generated by background tasks. If the document is reloaded before these tasks are complete, some images may not yet be generated. `lwarpmk` tries to wait for background tasks to complete before exiting.

HTML version does not exist: Images are extracted from the HTML version, which must be compiled before images are generated.

***-images.txt does not exist:** This file tells which images to extract from the HTML file. If the file does not exist, it may be that no `svg math` or `lateximages` were used. If so, `lwarpmk limages` is not necessary.

Cross references are not correct: The document must have up-to-date cross references to locate the images to extract. A number of conditions may cause incorrect cross references.

“WARNING: Images will be incorrect.”: An image reference was not found. Recompile.

lwarpmk epstopdf * or lwarpmk pdftosvg *: Errors if filenames are not found.

13.1.3 Default bitmapped font

lwarp requires the use of a vector font. If lwarp detects that the document uses the default COMPUTER MODERN font, and the cm-super package is not installed, it is assumed that the font is bitmapped. An error is generated, along with the recommendation to install cm-super or use lmodern.

13.1.4 Packages

Loaded before lwarp: Some packages and classes must be loaded before lwarp. These include input and font encoding, morewrites and newclude, and a number of CJK-related packages and classes.

Loaded after lwarp: Most packages which are modified by lwarp must be loaded after lwarp.

Loaded never: Some packages do not work with lwarp. An error is generated, along with a list of alternatives to consider.

Specific packages: Some packages enforce a specific load order vs. certain other packages.

Patching error: lwarp tries to patch some packages using xpatch. If the original package has been updated more recently than lwarp, a patch may not work. It may be necessary to use an older version of the package until lwarp is updated.

longtable: lwarp's longtable package issues detailed error messages regarding the use of the table headers and footers.

polyglossia: If used, an informative message is printed to instruct the user to be sure to set a language, without which an error will occur.

babel or polyglossia: An informative message is printed to note that not all languages are supported by cleveref.

13.1.5 Compiling

SideTOCDepth < FileDepth: A warning is displayed if these counters are set such that the sideroc will not be able to access all pages of the website.

Filenames: lwarp may generate file names from section names. While doing so, the filenames are simplified, and special characters and math are removed. If this process generates a duplicate filename, an error is generated, describing the filename and which section name generated it. A warning is issued if dollar-delimited math is used. Parenthesis-delimited math is recommended instead.

-  **HTML corrupted** **Multirow:** When `\multirow` or `\multicolrow` are used, `\mrowcell` or `\mcolrowcell` must be placed in the appropriate cells to avoid corrupted HTML output.
- (width,height) missing a comma:** `\makebox` and `\framebox` can accept a parenthesis-delimited width and height, which must be separated by a comma.
- “Load graphicx or graphics for improved SVG math baselines.”:** SVG math sizing and baselines are improved if either of these packages are used.
- “Load graphicx or graphics for improved XeTeX logo.”:** If these packages are loaded, the Xe_{La}TeX logo can use the reversed “E”.
- “It is recommended to use [width=xx\linewidth] instead of [scale=yy]”:** Browser support of `scale` does not have the same effect as in L^AT_EX.

13.2 Using the lwarp package

The following address problems which may occur, and possible solutions to each.

Also see:

Section 7.11: [Commands to be placed into the warpprint environment](#)

Section 8: [Special cases and limitations](#)

-  **HTML corrupted** **Text is not converting correctly / corrupted HTML tags:**
- Font-related UTF-8 information must be embedded in the PDF file. See section 7.4 regarding bitmapped vs. vector fonts.
 - See section 8.2.1 regarding HTML entities and the characters `&`, `<`, and `>`.

-  **dotlessj** **Dotless j (`\j`):** See section 7.4 regarding `cmap`, `mmap`.

Undefined HTML settings:

- See the warning regarding the placement of the HTML settings at section 7.6.

Tabular problems: See section 8.10.1.

Obscure error messages:

Print first: Be sure that a print version of the document compiles and that your document’s L^AT_EX code is correct, before attempting to generate an HTML version.

`\end{warpHTML}`, `\end{warpprint}`, `\end{warpall}`, `\end{warpMathJax}`:
Each of these must be without any other characters on the same line.

“Runaway argument? File ended while scanning use of `\next`:

Don’t use `warpHTML`, `warpprint`, `warpall`, or `warpMathJax` inside itself.

Options clash: If using `memoir`, see section 8.13.

“Missing `\begin{document}`.”: Some packages require that their options be specified before `lwarp` is loaded, or via the package’s setup macro, especially if these options include the use of braces. See section 8.1.

 `warpHTML`, `warpprint`,
`warpMathJax`, `warpall`

“No room for a new \write.”: Before `\usepackage{lwarp}`, add:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
```

“! TeX capacity exceeded, sorry [text input levels=15].”: Packages were nested too many levels deep. Locate the file `texmf.cnf` for your distribution, and add the line

```
max_in_open = 30
```

“Missing \$ inserted.”: If using a filename or URL in a footnote or `\item`, escape underscores with `_.`

“Label(s) may have changed. Rerun to get cross-references right.”:

This warning may repeat endlessly if a math expression is used in a caption. Simple math expressions such as $X=1$ may be replaced with

```
\textit{X}\,=\,1
```

“Temporary page! LaTeX was unable to guess the total number of pages ...”: Harmless. Recompile the document one more time.

“Leaders not followed by proper glue”:

This can be caused by a missing `l@<floatype>` or `l@<sectiontype>` definition. See `lwarp`’s definitions for examples.

“Improper \prevdepth”: `lateximages` and `svg` math require `\newpage`, which cannot work inside `TeX` boxes or `\ensuremath`. Anything using `\newsavebox`, `\newbox`, `lrbox`, `\savebox`, `\hbox`, `\vbox`, `\usebox`, `\sbox`, etc., must be modified to work without box commands.

If you find something using `\ensuremath`, have it temporarily set:

```
\LetLtxMacro\@ensuredmath\LWR@origensuredmath
```

inside a group first.

`LWR@texboxdepth`

As a stop-gap measure, you may wish to try incrementing the counter `LWR@texboxdepth` before the problematic macro, and then decrementing it after. Doing so tells `lwarp` to avoid using a `\newpage` inside the macro, which may avoid this error.

Also, custom macros which appear inside a section, figure, or table name should be made robust since they appear inside the `.toc`, `.lof`, or `.lot` files. Use `\newrobustcmd` or `\robustify` from `etoolbox`, `xparse`, etc.

If using BibTeX, see section 8.6.9.

“! Undefined control sequence. . . . \@begindocumenthook”: See section 8.15.4 if using `polyglossia`.

“\begin{equation} ended by \end{document}”: Do not use custom macros such as `\beq` and `\eeq` to replace

```
\begin{equation}
. . .
\end{equation}
```

“Misplaced \omit”: If using `\LWR@formatted` to define new macros for print and HTML modes, see section 35 regarding `\LWR@expandableformatted`.

⚠ macros in section, table,
figure names

⚠ BibTeX

⚠ polyglossia

⚠ custom macros for
environments

⚠ `\LWR@formatted`

“Token not allowed in a PDF string”: This `hyperref` warning appears while creating the print-mode document, not HTML. A low-level macro is being used in a section name which appears in the PDF bookmarks. `hyperref` removes this macro from the bookmark, and warns of doing so. To avoid this warning, use `\pdfstringdefDisableCommands` in the preamble to define simplified replacement macros for each, or use `\texorpdfstring` in the `\section` or related macro to declare what to use for the T_EX text, v.s. the PDF bookmark. See the `hyperref` manual.

⚠ quote character

“Command `\textquoteright` invalid in math mode”: This can occur when the document source has math containing the slanted quote `'` character, instead of using the upright quote `'` character.

⚠ “impure” math objects

Complicated objects inside math: Some objects, such as `Tikz`, may not compile in `lwarp`’s normal math emulation. Insert

```
\displaymathother — or — \inlinemathother
```

before the math, and then

```
\displaymathnormal — or — \inlinemathnormal
```

when displaying “normal” math. See section 8.7.9.

Slow compilation of math objects: Complicated math objects can also cause problems with `alt` tags, resulting in very slow compilation, large `alt` tags, and possible crashes. Use `\inlinemathother ... \inlinemathnormal` or `\displaymathother ... \displaymathnormal` around the math expression.

⚠ MATHJAX

Incorrect MATHJAX: Some objects do not convert to MATHJAX. Use `\displaymathother` before these objects, then `\displaymathnormal` to return to “normal” display math. See section 8.7.9.

Missing sections: See section 7.6 regarding the `FileDepth` and `SideTOCDepth` counters, and the use of `\tableofcontents` in the home page.

Misnumbered footnotes from section headings: See section 8.5.4.

Missing HTML files:

- See the warning regarding changes to the HTML settings at section 7.6.
- Ensure that the filenames are unique after math and short words are removed. See `FileSectionNames` at section 7.6.

Missing / incorrect cross-references:

- Use `lwarpmk` again followed by `lwarpmk html` or `lwarpmk print` to compile the document one more time.
- Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French). `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.
- `cleveref` and `varioref` are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

labels

⚠ label characters

`\nameref`

⚠ empty link

⚠ cleveref page numbers

Ex:

```
\cpageref{tab:first,tab:second}
```

in html becomes:

“pages **for table 4.1** and **for table 4.2**”

See `\cpagerefFor` at page 739 to redefine the message which is printed for page number references.

BibTeX errors with `\etalchar`: See section 8.6.9.

Malformed URLs: Do not use the % character between arguments of `\hyperref`, etc., as this character is among those which is neutralized for inclusion in HTML URLs.

Em-dashes or En-dashes in listing captions and titles:

Use Xe_{La}TeX or Lua_{La}TeX.

Floats out of sequence:

Mixed “Here” and floating: Floats [H]ere and regular floats may become out of order. `\clearpage` if necessary.

Caption setup: With `\captionsetup` set the positions for the captions above or below to match their use in the source code.

Images are appearing in strange places:

- Enter `lwarpmk limages` to refresh the `lateximage` images.

SVG images:

△ adding/removing

When a math expression, picture, or Tikz environment is added or removed, the svg images must be re-created by entering `lwarpmk limages` to maintain the proper image-file associations. Inline svg math may be hashed and thus not need to be recreated, but display math and objects such as Tikz may move to new image numbers when the document is changed.

recompile first

Before attempting to create the svg image files, `lwarpmk` verifies that the HTML version of the document exists and has correct internal image references.¹⁶ If it is necessary to recompile the document’s HTML version one more time, `lwarpmk` usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the `LaTeX` recompile warnings.

△ HTML instead of images

If HTML appears where an svg image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

△ page counter

Incorrect svg images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

△ Lots of files!

Expressing math as svg images has the advantage of representing the math exactly as `LaTeX` would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, `lwarp` uses an MD5 hash on its `LaTeX` source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and `Tikz` require one image file each. For a document with a large amount of math, see section 5.5 to use `MATHJAX` instead.

¹⁶This becomes important when dealing with a document containing thousands of images.

Plain-looking document:

- The document's CSS stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFile` statements point to a valid CSS file.

△ HTML corrupted**Broken fragments of HTML:**

- Check the PDF file used to create HTML to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

Changes do not seem to be taking effect:

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the HTML settings at section 7.6.
- Verify that the proper CSS is actually being used.
- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

Un-matched conditional compiles:

- Verify the proper `begin/end` of `warpprint`, `warpHTML`, and `warpall` environments.

13.2.1 Debug tracing output

`\tracinglwarp` When `\tracinglwarp` is used, `lwarp` will add extra tracing messages to the `.log` file. The last several messages may help track down errors.

Place `\tracinglwarp` just after `\usepackage{lwarp}` to activate tracing.

13.3 Compiling the `lwarp.dtx` file

`lwarp_tutorial.tex`: Copy or link `lwarp_tutorial.txt` from the TDS doc directory to the source directory, or wherever you wish to compile the documentation. This file is included verbatim in the documentation, but is in the doc directory so that it may be found by `texdoc` and copied by the user.

Illogical error messages caused by an out-of-sync `lwarp.sty` file:

1. Delete the `lwarp.sty` file.
2. Enter `pdflatex lwarp.ins` to generate a new `lwarp.sty` file.
3. Enter `pdflatex lwarp.dtx` to recompile the `lwarp.pdf` documentation.

Un-nested environments:

Be sure to properly nest:

- `\begin{macrocode}` and `\end{macrocode}`
- `\begin{macro}` and `\end{macro}`
- `\begin{environment}` and `\end{environment}`

14 Trademarks

- TEX is a trademark of American Mathematical Society.
- ADOBE® and ADOBE *Framemaker*® are either registered trademarks or trademarks of ADOBE SYSTEMS INCORPORATED in the United States and/or other countries.
- LINUX® is the registered trademark of Linus Torvalds in the U.S. and other countries.
- MAC OS® is a trademark of APPLE INC.
- MADCAP FLARE™ is the property of MADCAP SOFTWARE, INC.
- MATHJAX is copyright 2009 and later. The MATHJAX CONSORTIUM is a joint venture of the AMERICAN MATHEMATICAL SOCIETY (AMS) and the SOCIETY FOR INDUSTRIAL AND APPLIED MATHEMATICS (SIAM) to advance mathematical and scientific content on the web.
- MICROSOFT®, ENCARTA, MSN, and WINDOWS® are either registered trademarks or trademarks of MICROSOFT CORPORATION in the United States and/or other countries.
- UNIX® is a registered trademark of THE OPEN GROUP.
- YOUTUBE™ is trademark of GOOGLE LLC.

File 1 **lwarp.sty**

15 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of ~~erude-hacks~~ clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include `xcolor` with its color models and conversion to HTML color output, and `siunitx` which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by *pdftotext*.

Packages were emulated where their primary purpose was visual formatting which is not relevant to HTML output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in HTML output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a `lateximage` environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

Table 11: Section depths and HTML headings

Section	\LaTeX depth	HTML headings *
Title of the entire website		<code><h1></code>
(none)	-5	new for this package
book	-2	<code><div class = "book"></code>
part	-1	<code><h2></code>
chapter	0	<code><h3></code>
section	1	<code><h4></code>
subsection	2	<code><h5></code>
subsubsection	3	<code><h6></code>
paragraph	4	<code></code>
subparagraph	5	<code></code>
listitem	7	new for this package, used for list items

* If `FormatWP` is true, section headings may be adjusted, depending on `WPTitleHeading`. See table 10 on page 188.

16 Section depths and HTML headings

Stacks are created to track depth inside the \LaTeX document structure. This depth is translated to HTML headings as shown in table 11. “Depth” here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the \LaTeX document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Support for the memoir package will require the addition of a book level, which may push the HTML headings down a step, and also cause subsubsection to become a `<div>` due to a limit of six HTML headings.

It is possible to use HTML5 `<section>` and `<h1>` for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the CSS to remain fixed as well.

17 Source code

This is where the documented source code for `lwarp` begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the `lwarp` package.

line numbers The small numbers at the left end of a line refer to line numbers in the `lwarp.sty` file.

subjects Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph.

objects Black-colored tags in the left margin are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are

index entries command macros. Each of these also appears in the index as individual entries, and are also listed together under “files”, “packages”, “environments”, “booleans”, and “counters”.

 **warnings** Special warnings are marked with a warning icon.

for HTML output: Green-colored tags in the left margin show which sections of source code apply to the generation of HTML, print, or both forms of output.
for PRINT output:
for HTML & PRINT:

18 Detecting the T_EX engine — *pdf_latex*, *lua_latex*, *xel_latex*

See: <http://tex.stackexchange.com/a/47579>.

Detects X_lT_EX and Lua_LT_EX:

```

1 \RequirePackage{iftex}[2019/11/07]
2 \RequirePackage{ifpdf}
3 \RequirePackage{ifptex}
4
5 \newif\ifxetexorluatex
6
7 \ifXeTeX
8   \xetexorluatextrue
9 \else
10  \ifLuaTeX
11    \xetexorluatextrue
12  \else
13    \xetexorluatexfalse
14  \fi
15 \fi

```

19 Early package requirements

Pkg etoolbox Provides \ifbool and other functions.

Pkg xpatch Patches macros with optional arguments.

```

16 \RequirePackage{etoolbox}[2011/01/03]% v2.6 for \BeforeBeginEnvironment, etc.
17 \RequirePackage{xpatch}

```

Pkg ifplatform Provides \ifwindows to try to automatically detect WINDOWS OS.

```

18 \RequirePackage{ifplatform}% sense op-system platform

```

Pkg letltxmacro

```

19 \RequirePackage{letltxmacro}

```

20 Package load order

Several packages must never be used with `lwarp`, others should only be loaded before `lwarp`, and others should only be loaded after. The `lwarp` core checks most of these cases. In some `lwarp-*` packages, `\LWR@loadbefore` is used to trigger an error if they are loaded after `lwarp`, while additional code provides necessary patches for when they are loaded before.

Packages which must be loaded after `lwarp` are enforced by a large number of `\LWR@loadafter` statements, below. Some packages are emulated by `memoir`, and so these are tested by `\LWR@notmemoirloadafter`, which does not cause an error if `memoir` is used.

`\LWR@checkloadfilename` is used to check each filename to see if it must never be loaded, or must always be loaded before `lwarp`.

20.1 Tests of package load order

`\LWR@loadafter` $\langle\textit{packagename}\rangle$ Error if this package was loaded before `lwarp`.

```

20 \newcommand*\LWR@loadafter}[1]{%
21 \@ifpackageloaded{#1}
22 {
23   \PackageError{lwarp}
24     {%
25       Package #1,\MessageBreak
26       or one which uses #1,\MessageBreak
27       must be loaded after Lwarp.\MessageBreak
28       Enter 'H' for possible solutions%
29     }
30     {%
31       Move “\protect\usepackage{#1}” after
32       “\protect\usepackage{lwarp}”.\MessageBreak
33       Package #1 may also be loaded by something else,\MessageBreak
34       which must also be moved after Lwarp.%
35     }
36 }
37 {\relax}
38 }

```

`\LWR@notmemoirloadafter` $\langle\textit{packagename}\rangle$ Error if not `memoir` class and this package was loaded before `lwarp`.

`memoir` emulates many packages, and pretends that they have already been loaded.

```

39 \@ifclassloaded{memoir}
40 {\newcommand*\LWR@notmemoirloadafter}[1]{}
41 {\LetLtxMacro\LWR@notmemoirloadafter\LWR@loadafter}

```

`\LWR@notltjloadafter` $\langle\textit{packagename}\rangle$ Error if not a `ltjs*` class and this package was loaded before `lwarp`.

```

42 \LetLtxMacro\LWR@notltjloadafter\LWR@loadafter
43
44 \@ifclassloaded{ltjarticle}{\renewcommand*\LWR@notltjloadafter}[1]{}{ }
45 \@ifclassloaded{ltjbook}{\renewcommand*\LWR@notltjloadafter}[1]{}{ }
46 \@ifclassloaded{ltjreport}{\renewcommand*\LWR@notltjloadafter}[1]{}{ }
47 \@ifclassloaded{ltjsarticle}{\renewcommand*\LWR@notltjloadafter}[1]{}{ }
48 \@ifclassloaded{ltjsbook}{\renewcommand*\LWR@notltjloadafter}[1]{}{ }
49 \@ifclassloaded{ltjsreport}{\renewcommand*\LWR@notltjloadafter}[1]{}{ }

```

```

50 \@ifclassloaded{ltjspf}{\renewcommand*\LWR@notltjloadafter}[1]{}{}
51 \@ifclassloaded{ltjskiyou}{\renewcommand*\LWR@notltjloadafter}[1]{}{}
52 \@ifclassloaded{ltjtarticle}{\renewcommand*\LWR@notltjloadafter}[1]{}{}
53 \@ifclassloaded{ltjtbook}{\renewcommand*\LWR@notltjloadafter}[1]{}{}
54 \@ifclassloaded{ltjtreport}{\renewcommand*\LWR@notltjloadafter}[1]{}{}

```

`\LWR@loadbefore` $\langle\textit{packagename}\rangle$ Error if this package is loaded after lwarp.

```

55 \newcommand*\LWR@loadbefore}[1]{%
56 \@ifpackageloaded{#1}
57 {\relax}
58 {
59   \PackageError{lwarp}
60   {%
61     Package #1 must be loaded before lwarp.\MessageBreak
62     Enter 'H' for possible solutions%
63   }
64   {Move “\protect\usepackage{#1}” before “\protect\usepackage{lwarp}”’.}
65 }
66 }

```

`\LWR@checkloadbefore` $\langle\textit{thispackagename}\rangle$ $\langle\textit{packagename}\rangle$

If package names match, error if it is loaded after lwarp.

```

67 \newcommand*\LWR@checkloadbefore}[2]{%
68   \edef\LWR@tempone{#1}%
69   \ifdefstring{\LWR@tempone}{#2}{%
70     \LWR@loadbefore{#1}%
71   }{}%
72 }

```

`\LWR@loadnever` $\langle\textit{badpackagename}\rangle$ $\langle\textit{replacementpkgnames}\rangle$

The first packages is not supported, so tell the user to use the second instead.

```

73 \newcommand*\LWR@loadnever}[2]{%
74 \PackageError{lwarp}
75 {%
76   Package #1 is not supported\MessageBreak
77   by lwarp's HTML conversion.\MessageBreak
78   Package(s)\MessageBreak
79   \space\space#2\MessageBreak
80   may be useful instead%
81 }
82 {%
83   Package #1 might conflict with lwarp in some way,\MessageBreak
84   or is superceded by another package.\MessageBreak
85   For a possible alternative, see package(s) #2.
86 }
87 }

```

`\LWR@checkloadnever` $\langle\textit{thispackagename}\rangle$ $\langle\textit{badpackagename}\rangle$ $\langle\textit{replacementpkgnames}\rangle$

If this package name is the bad packagename, suggest the replacements instead.

```
88 \newcommand*\LWR@checkloadnever}[3]{%
89   \edef\LWR@tempone{#1}%
90   \ifdefstring{\LWR@tempone}{#2}{%
91     \LWR@loadnever{#2}{#3}%
92   }{}%
93 }
```

`\LWR@earlyloadnever` {*<badpackagename>*} {*<replacementpkgname>*}

The first package is not supported, so tell the user to use the second instead. This version checks immediately for packages which may have been loaded before lwarp.

```
94 \newcommand*\LWR@earlyloadnever}[2]{%
95   \@ifpackageloaded{#1}{%
96     \LWR@loadnever{#1}{#2}%
97   }{}%
98 }
```

`\LWR@earlyclassloadnever` {*<badclassname>*} {*<replacementclassname>*}

The first class is not supported, so tell the user to use the second instead. This version checks immediately for classes which may have been loaded before lwarp.

```
99 \newcommand*\LWR@earlyclassloadnever}[2]{%
100 \@ifclassloaded{#1}{%
101   \PackageError{lwarp}
102   {%
103     Class #1 is not supported\MessageBreak
104     by lwarp's HTML conversion.\MessageBreak
105     Class(es) #2 may be useful instead
106   }
107   {%
108     Class #1 might conflict with lwarp in some way,\MessageBreak
109     or is superceded by another class.\MessageBreak
110     For a possible alternative, see class(es) #2.
111   }
112 }{\relax}%
113 }
```

20.2 Error for disallowed packages and classes loaded before lwarp

```
114 \LWR@earlyclassloadnever{jarticle}{ujarticle}
115 \LWR@earlyclassloadnever{jbook}{ujbook}
116 \LWR@earlyclassloadnever{jreport}{ujreport}
117 \LWR@earlyclassloadnever{tarticle}{utarticle}
118 \LWR@earlyclassloadnever{tbook}{utbook}
119 \LWR@earlyclassloadnever{treport}{utreport}
120 \LWR@earlyloadnever{ae}{cm-super, lmodern}
121 \LWR@earlyloadnever{aecompl}{cm-super, lmodern}
122 \LWR@earlyloadnever{aecc}{cm-super, lmodern}
```

```

123 \LWR@earlyloadnever{alg}{algorithm2e, algorithmicx}
124 \LWR@earlyloadnever{algorithmic}{algorithm2e, algorithmicx}
125 \LWR@earlyloadnever{bitfield}{bytefield}
126 \LWR@earlyloadnever{caption2}{caption}
127 % \LWR@earlyloadnever{ccaption}{caption}% might be preloaded by memoir
128 \LWR@earlyloadnever{colortab}{colortbl}
129 \LWR@earlyloadnever{csvtools}{datatool}
130 \LWR@earlyloadnever{doublespace}{setspace}
131 \LWR@earlyloadnever{epsf}{graphicx}
132 \LWR@earlyloadnever{fancyheadings}{fancyhdr}
133 \LWR@earlyloadnever{fncylab}{cleveref}
134 \LWR@earlyloadnever{formula}{siunitx}
135 \LWR@earlyloadnever{glossary}{glossaries}
136 \LWR@earlyloadnever{hyper}{hyperref}
137 \LWR@earlyloadnever{libgreek}{libertinust1math, newtx}
138 \LWR@earlyloadnever{newthm}{ntheorem}
139 \LWR@earlyloadnever{pdfcprot}{microtype}
140 \LWR@earlyloadnever{picins}{floatflt, wrapfig}
141 \LWR@earlyloadnever{rplain}{fancyhdr}
142 \LWR@earlyloadnever{si}{siunitx}
143 \LWR@earlyloadnever{sistyle}{siunitx}
144 \LWR@earlyloadnever{slashbox}{diagbox}
145 \LWR@earlyloadnever{statex}{statex2}
146 \LWR@earlyloadnever{t1enc}{fontenc, inputenc, inputenx}
147 \LWR@earlyloadnever{ucs}{inputenc, inputencx}
148 \LWR@earlyloadnever{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}

```

The older CJK and CJKutf8 only work with xeCJK:

```

149 \@ifpackageloaded{xeCJK}{}{
150   \LWR@earlyloadnever{CJK}{ctex, xeCJK}
151   \LWR@earlyloadnever{CJKutf8}{ctex, xeCJK}
152 }

```

bxckjatype is based on CJK:

```

153 \LWR@earlyloadnever{bxckjatype}{upLaTeX, bxjsarticle, uarticle, utarticle}

```

hangul is not in TeXLive, and is not tested:

```

154 \LWR@earlyloadnever{hangul}{kotex, xetexko, luatexko}

```

20.3 Enforcing package loading after lwarp

Packages which should only be loaded after lwarp are tested here to trip an error of they have already been loaded.

The following packages must be loaded after lwarp:

```

155 \LWR@loadafter{2in1}
156 \LWR@loadafter{2up}
157 \LWR@loadafter{a4}
158 \LWR@loadafter{a4wide}
159 \LWR@loadafter{a5comb}

```

```
160 \LWR@notmemoirloadafter{abstract}
161 \LWR@loadafter{academicons}
162 \LWR@loadafter{accents}
163 \LWR@loadafter{accessibility}
164 \LWR@loadafter{accsupp}
165 \LWR@loadafter{acro}
166 \LWR@loadafter{acronym}
167 \LWR@loadafter{adjmulticol}
168 \LWR@loadafter{addlines}
169 \LWR@loadafter{afterpage}
170 \LWR@loadafter{algorithm2e}
171 \LWR@loadafter{algorithmicx}
172 \LWR@loadafter{alltt}
173 % \LWR@loadafter{amsmath}% may be preloaded
174 % \LWR@loadafter{amsthm}% may be preloaded
175 \LWR@loadafter{anonchp}
176 \LWR@loadafter{anysize}
177 \LWR@notmemoirloadafter{appendix}
178 \LWR@loadafter{ar}
179 \LWR@loadafter{arabicfront}
180 \LWR@notmemoirloadafter{array}
181 \LWR@loadafter{arydshln}
182 \LWR@loadafter{asymptote}
183 % \LWR@loadafter{atbegshi}% now in LaTeX core, also used by morewrites
184 \LWR@loadafter{attachfile}
185 \LWR@loadafter{attachfile2}
186 \LWR@loadafter{authblk}
187 \LWR@loadafter{authoraftertitle}% Supported as-is, but must be loaded after.
188 \LWR@loadafter{autobreak}
189 \LWR@loadafter{autonum}
190 \LWR@loadafter{awesomebox}
191 \LWR@loadafter{axessibility}
192 \LWR@loadafter{axodraw2}
193 \LWR@loadafter{backnaur}
194 \LWR@loadafter{backref}
195 \LWR@loadafter{balance}
196 \LWR@loadafter{bbding}
197 \LWR@loadafter{bigdelim}
198 \LWR@loadafter{bigfoot}
199 \LWR@loadafter{bigstrut}
200 \LWR@loadafter{bitpattern}
201 \LWR@loadafter{blowup}
202 \LWR@loadafter{bm}
203 \LWR@loadafter{booklet}
204 \LWR@loadafter{bookmark}
205 \LWR@notmemoirloadafter{booktabs}
206 \LWR@loadafter{bophook}
207 \LWR@loadafter{bounddvi}
208 \LWR@loadafter{boxedminipage}
209 \LWR@loadafter{boxedminipage2e}
210 \LWR@loadafter{braket}
211 \LWR@loadafter{breakurl}
212 \LWR@loadafter{breqn}
213 \LWR@loadafter{bsheaders}
214 \LWR@loadafter{bussproofs}
```

215 \LWR@loadafter{bypapersize}
216 \LWR@loadafter{bytefield}
217 \LWR@loadafter{cancel}
218 \LWR@loadafter{canoniclayout}
219 \LWR@loadafter{caption}
220 \LWR@loadafter{caption2}
221 \LWR@loadafter{caption3}
222 \LWR@loadafter{cases}
223 % catoptions is supported by the lwarp core
224 % \LWR@loadafter{ccaption}% may be preloaded by memoir
225 % \LWR@loadafter{centernot}% may be preloaded by newtx
226 \LWR@loadafter{changebar}
227 \LWR@loadafter{changelayout}
228 \LWR@notmemoirloadafter{changepage}
229 \LWR@loadafter{changes}
230 \LWR@loadafter{chappg}
231 \LWR@loadafter{chapterbib}
232 \LWR@loadafter{chemfig}
233 \LWR@loadafter{chemformula}
234 \LWR@loadafter{chemgreek}
235 \LWR@loadafter{chemmacros}
236 \LWR@loadafter{chemnum}
237 \LWR@loadafter{chkfloat}
238 \LWR@notmemoirloadafter{chnpage}
239 \LWR@loadafter{cite}
240 \LWR@loadafter{citeref}
241 \LWR@loadafter{cleveref}
242 % cmbright may be preloaded
243 \LWR@loadafter{cmdtrack}
244 \LWR@loadafter{colonequals}
245 \LWR@loadafter{color}
246 \LWR@loadafter{colortbl}
247 \LWR@loadafter{continue}
248 \LWR@loadafter{copyrightbox}
249 \LWR@notmemoirloadafter{crop}
250 % ctex must be loaded before lwarp
251 \LWR@loadafter{ctable}
252 \LWR@loadafter{cuted}
253 \LWR@loadafter{cutwin}
254 \LWR@loadafter{dblfloatfix}
255 \LWR@loadafter{dblfnote}
256 \LWR@notmemoirloadafter{dcolumn}
257 \LWR@loadafter{decimal}
258 \LWR@loadafter{diagbox}
259 \LWR@loadafter{dingbat}
260 \LWR@loadafter{DotArrow}
261 \LWR@loadafter{dotlessi}
262 \LWR@loadafter{dprogress}
263 \LWR@loadafter{draftcopy}
264 \LWR@loadafter{draftfigure}
265 \LWR@loadafter{draftwatermark}
266 \LWR@loadafter{drftcite}
267 \LWR@loadafter{easy-todo}
268 \LWR@loadafter{ebook}
269 \LWR@loadafter{econometrics}

```
270 \LWR@loadafter{ed}
271 \LWR@loadafter{ellipsis}
272 \LWR@loadafter{embrac}
273 \LWR@loadafter{emptypage}
274 \LWR@loadafter{endfloat}
275 \LWR@loadafter{endheads}
276 \LWR@loadafter{endnotes}
277 \LWR@loadafter{engtlc}
278 \LWR@notmemoirloadafter{enumerate}
279 \LWR@loadafter{enumitem}
280 \LWR@notmemoirloadafter{epigraph}
281 \LWR@loadafter{epsfig}
282 \LWR@loadafter{epstopdf}
283 \LWR@loadafter{epstopdf-base}
284 \LWR@loadafter{eqlist}
285 \LWR@loadafter{eqparbox}
286 \LWR@loadafter{errata}
287 \LWR@loadafter{eso-pic}
288 \LWR@loadafter{esvect}
289 \LWR@loadafter{etoc}
290 \LWR@loadafter{eurosym}
291 \LWR@loadafter{everypage}
292 % \LWR@loadafter{everyshi}% now in LaTeX core
293 \LWR@loadafter{extrarrows}
294 \LWR@loadafter{extramarks}
295 \LWR@loadafter{fancybox}
296 \LWR@loadafter{fancyhdr}
297 \LWR@loadafter{fancyref}
298 \LWR@loadafter{fancytabs}
299 \LWR@loadafter{fancyvrb}
300 \LWR@loadafter{fbox}
301 \LWR@loadafter{fewerfloatpages}
302 \LWR@loadafter{figcaps}
303 \LWR@loadafter{figsize}
304 \LWR@loadafter{fitbox}
305 \LWR@loadafter{fix2col}
306 \LWR@loadafter{fixmath}
307 \LWR@loadafter{fixme}
308 \LWR@loadafter{fixmetodonotes}
309 \LWR@loadafter{flafter}
310 \LWR@loadafter{flippdf}
311 \LWR@loadafter{float}
312 \LWR@loadafter{floatflt}
313 \LWR@loadafter{floatpag}
314 \LWR@loadafter{floatrow}
315 \LWR@loadafter{fltrace}
316 \LWR@loadafter{flushend}
317 \LWR@loadafter{fnbreak}
318 \LWR@loadafter{fncychap}
319 \LWR@loadafter{fnlineno}
320 \LWR@loadafter{fnpara}
321 \LWR@loadafter{fnpos}
322 \LWR@loadafter{fontawesome}
323 \LWR@loadafter{fontawesome5}
324 % fontenc must be loaded before lwarp
```

```
325 % fontspec must be loaded before lwarp
326 \LWR@loadafter{footmisc}
327 \LWR@loadafter{footnote}
328 \LWR@loadafter{footnotebackref}
329 \LWR@loadafter{footnotehyper}
330 \LWR@loadafter{footnoterange}
331 \LWR@loadafter{footnpag}
332 \LWR@loadafter{foreign}
333 \LWR@loadafter{forest}
334 \LWR@loadafter{fouridx}
335 % fourier may be loaded before lwarp
336 \LWR@loadafter{framed}
337 \LWR@loadafter{ftcap}
338 \LWR@loadafter{ftnright}
339 \LWR@loadafter{fullminipage}
340 \LWR@loadafter{fullpage}
341 \LWR@loadafter{fullwidth}
342 \LWR@loadafter{fvextra}
343 \LWR@loadafter{fwlw}
344 \LWR@loadafter{gensymb}
345 \LWR@loadafter{gentombow}
346 % geometry is always loaded by lwarp, and lwarp-geometry is AtBeginDocument
347 \LWR@loadafter{ghsystem}
348 \LWR@loadafter{gindex}
349 \LWR@loadafter{glossaries}
350 \LWR@loadafter{gmeometric}
351 % \LWR@loadafter{graphics}% pre-loaded by xunicode
352 % \LWR@loadafter{graphicx}% pre-loaded by xunicode
353 \LWR@loadafter{gloss}
354 \LWR@loadafter{glossary}
355 \LWR@loadafter{grffile}
356 \LWR@loadafter{grid}
357 \LWR@loadafter{grid-system}
358 \LWR@loadafter{gridset}
359 \LWR@loadafter{hang}
360 \LWR@loadafter{hanging}
361 \LWR@loadafter{hepunits}
362 \LWR@loadafter{hhline}
363 \LWR@loadafter{hhtensor}
364 \LWR@loadafter{hypbmsec}
365 \LWR@loadafter{hypcap}
366 \LWR@loadafter{hypdestopt}
367 \LWR@loadafter{hypernat}
368 \LWR@loadafter{hyperref}
369 \LWR@loadafter{hyperxmp}
370 \LWR@loadafter{hyphenat}
371 \LWR@loadafter{idxlayout}
372 \LWR@loadafter{ifoddpag}
373 \LWR@loadafter{imakeidx}
374 \LWR@notmemoirloadafter{index}
375 % inputenc must be loaded before lwarp
376 % inputenx must be loaded before lwarp
377 % inputtrc may be loaded before lwarp
378 \LWR@loadafter{intopdf}
379 \LWR@loadafter{jurabib}
```

```
380 \LWR@loadafter{karnaugh-map}
381 \LWR@loadafter{keyfloat}
382 \LWR@loadafter{keystroke}
383 % kpfonts may be loaded before lwarp
384 % kpfonts-otf may be loaded before lwarp
385 \LWR@loadafter{layaureo}
386 \LWR@loadafter{layout}
387 \LWR@loadafter{layouts}
388 \LWR@loadafter{leading}
389 \LWR@loadafter{leftidx}
390 \LWR@loadafter{letterspace}
391 \LWR@loadafter{lettrine}
392 % libertinustlmath may be loaded before lwarp
393 \LWR@loadafter{lineno}
394 \LWR@loadafter{lips}
395 \LWR@loadafter{listings}
396 \LWR@loadafter{listliketab}
397 \LWR@loadafter{longtable}
398 \LWR@loadafter{lscap}
399 \LWR@loadafter{ltablex}
400 \LWR@loadafter{ltcaption}
401 \LWR@loadafter{ltxgrid}
402 \LWR@loadafter{ltxtable}
403 \LWR@loadafter{lua-check-hyphen}
404 \LWR@loadafter{lua-visual-debug}
405 \LWR@loadafter{luacolor}
406 \LWR@loadafter{luamplib}
407 \LWR@loadafter{luatodonotes}
408 \LWR@loadafter{lyluatex}
409 \LWR@loadafter{magaz}
410 \LWR@notmemoirloadafter{makeidx}
411 \LWR@loadafter{manyfoot}
412 \LWR@loadafter{marginfit}
413 \LWR@loadafter{marginfix}
414 \LWR@loadafter{marginnote}
415 \LWR@loadafter{marvosym}
416 % mathalpha may be loaded before lwarp
417 \LWR@loadafter{mathastext}
418 \LWR@loadafter{mathcomp}
419 \LWR@loadafter{mathdesign}
420 \LWR@loadafter{mathdots}
421 \LWR@loadafter{mathfixs}
422 \LWR@loadafter{mathpazo}
423 \LWR@loadafter{mathptmx}
424 \LWR@loadafter{mathspec}
425 \LWR@loadafter{mathtools}
426 \LWR@loadafter{mcaption}
427 \LWR@loadafter{mdframed}
428 \LWR@loadafter{media9}
429 \LWR@loadafter{memhfixc}
430 \LWR@loadafter{menukeys}
431 \LWR@loadafter{metalogo}
432 \LWR@loadafter{metalogoX}
433 \LWR@loadafter{mhchem}
434 \LWR@loadafter{microtype}
```

```
435 \LWR@loadafter{midfloat}
436 \LWR@loadafter{midpage}
437 \LWR@loadafter{minibox}
438 \LWR@loadafter{minitoc}
439 \LWR@loadafter{minted}
440 \LWR@loadafter{mismath}
441 \LWR@loadafter{mletright}
442 % morefloats must be allowed early for print mode
443 \LWR@notmemoirloadafter{moreverb}
444 % morewrites must be loaded before lwarp
445 \LWR@notmemoirloadafter{movie15}
446 \LWR@notmemoirloadafter{mparhack}
447 \LWR@loadafter{multibib}
448 \LWR@loadafter{multicap}
449 %\LWR@loadafter{multicol}% loaded by ltxdoc
450 \LWR@loadafter{multicolrule}
451 \LWR@loadafter{multimedia}
452 \LWR@loadafter{multiobjective}
453 \LWR@loadafter{multirow}
454 \LWR@loadafter{multitoc}
455 \LWR@loadafter{musicography}
456 \LWR@loadafter{nameauth}
457 \LWR@loadafter{nameref}
458 \LWR@loadafter{natbib}
459 \LWR@notmemoirloadafter{nccfancyhdr}
460 \LWR@loadafter{nccfoots}
461 \LWR@loadafter{nccmath}
462 \LWR@notmemoirloadafter{needspace}
463 % newclude must be loaded before lwarp
464 % newpxmath may be preloaded
465 % newtxmath may be loaded before lwarp
466 % newtxsf may be loaded before lwarp
467 % newunicodechar must be loaded before lwarp
468 \LWR@notmemoirloadafter{nextpage}
469 \LWR@loadafter{nicefrac}
470 \LWR@loadafter{niceframe}
471 \LWR@loadafter{noitcrl}
472 \LWR@loadafter{nolbreaks}
473 \LWR@loadafter{nomencL}
474 \LWR@loadafter{nonfloat}
475 \LWR@loadafter{nonumonpart}
476 \LWR@loadafter{nopageno}
477 \LWR@loadafter{notes}
478 \LWR@loadafter{notespages}
479 \LWR@loadafter{nowidow}
480 \LWR@loadafter{ntheorem}
481 \LWR@loadafter{octave}
482 \LWR@loadafter{overpic}
483 \LWR@loadafter{pagegrid}
484 \LWR@notmemoirloadafter{pagenote}
485 \LWR@loadafter{pagesel}
486 \LWR@loadafter{paralist}
487 \LWR@loadafter{parallel}
488 \LWR@loadafter{parcolumns}
489 \LWR@loadafter{parnotes}
```

```
490 \LWR@notmemoirloadafter{parskip}
491 \LWR@loadafter{pbox}
492 \LWR@loadafter{pdfcol}
493 \LWR@loadafter{pdfcolfoot}
494 \LWR@loadafter{pdfcolmk}
495 \LWR@loadafter{pdfcolparallel}
496 \LWR@loadafter{pdfcolparcolumns}
497 \LWR@loadafter{pdfcomment}
498 \LWR@loadafter{pdfcrypt}
499 \LWR@loadafter{pdfscape}
500 \LWR@loadafter{pdfmarginpar}
501 \LWR@loadafter{pdfpages}
502 \LWR@loadafter{pdfprivacy}
503 \LWR@loadafter{pdfrender}
504 \LWR@loadafter{pdfsync}
505 \LWR@loadafter{pdftricks}
506 \LWR@loadafter{pdfx}
507 \LWR@loadafter{perpage}
508 \LWR@loadafter{pfnote}
509 \LWR@loadafter{phfqit}
510 \LWR@loadafter{physics}
511 \LWR@loadafter{physunits}
512 \LWR@loadafter{picinpar}
513 \LWR@loadafter{pifont}
514 \LWR@loadafter{placeins}
515 \LWR@loadafter{plarray}
516 \LWR@loadafter{plarydshln}
517 \LWR@loadafter{plextarray}
518 \LWR@loadafter{plextarydshln}
519 \LWR@loadafter{plcolortbl}
520 \LWR@loadafter{plextdelarray}
521 \LWR@loadafter{plimsoll}
522 \LWR@loadafter{prelim2e}
523 \LWR@loadafter{prettyref}
524 \LWR@loadafter{preview}
525 \LWR@loadafter{psfrag}
526 \LWR@loadafter{psfragx}
527 \LWR@loadafter{pst-eps}
528 \LWR@loadafter{pstool}
529 \LWR@loadafter{pstricks}
530 % \LWR@loadafter{pxatbegshi}% may be used by morewrites
531 \LWR@loadafter{pxeveryshi}
532 % \LWR@loadafter{pxfonts}% may be loaded before lwarp
533 \LWR@loadafter{pxftnright}
534 \LWR@loadafter{pxjahyper}
535 \LWR@loadafter{quotchap}
536 \LWR@loadafter{quoting}
537 \LWR@loadafter{ragged2e}
538 \LWR@loadafter{realscripts}
539 \LWR@loadafter{refcheck}
540 \LWR@loadafter{register}
541 \LWR@loadafter{relnsize}
542 \LWR@loadafter{repeatindex}
543 \LWR@loadafter{resizgather}
544 \LWR@loadafter{returntograd}
```

```
545 \LWR@loadafter{rmathbr}
546 \LWR@loadafter{rmpage}
547 \LWR@loadafter{romanbar}
548 \LWR@loadafter{romanbarpagenumber}
549 \LWR@loadafter{rotating}
550 \LWR@loadafter{rotfloat}
551 \LWR@loadafter{rviewport}
552 \LWR@loadafter{savetrees}
553 % scalefnt is loaded by babel-french
554 \LWR@loadafter{scalereel}
555 \LWR@loadafter{schemata}
556 \LWR@loadafter{scrextend}
557 \LWR@loadafter{scrhack}
558 \LWR@loadafter{scrlayer}
559 \LWR@loadafter{scrlayer-notecolumn}
560 \LWR@loadafter{scrlayer-scrpage}
561 \LWR@loadafter{scrpage2}
562 \LWR@loadafter{section}
563 \LWR@loadafter{sectionbreak}
564 \LWR@loadafter{sectsty}
565 \LWR@loadafter{selectp}
566 \LWR@loadafter{semantic-markup}
567 \LWR@notmemoirloadafter{setspace}
568 \LWR@loadafter{shadow}
569 \LWR@loadafter{shapepar}
570 \LWR@notmemoirloadafter{showidx}
571 \LWR@loadafter{showkeys}
572 \LWR@loadafter{showtags}
573 \LWR@loadafter{shuffle}
574 \LWR@loadafter{sidecap}
575 \LWR@loadafter{sidenotes}
576 \LWR@loadafter{simplebnf}
577 \LWR@loadafter{SIunits}
578 \LWR@loadafter{siunitx}
579 \LWR@loadafter{slantsc}
580 \LWR@loadafter{slashed}
581 \LWR@loadafter{soul}
582 \LWR@loadafter{soulpos}
583 \LWR@loadafter{soulutf8}
584 \LWR@loadafter{splitbib}
585 \LWR@loadafter{splitidx}
586 \LWR@loadafter{srcltx}
587 \LWR@loadafter{srctex}
588 \LWR@loadafter{stabular}
589 \LWR@loadafter{stackengine}
590 \LWR@loadafter{stackrel}
591 \LWR@loadafter{statex2}
592 \LWR@loadafter{statistics}
593 \LWR@loadafter{statmath}
594 \LWR@loadafter{steinmetz}
595 \LWR@notltjloadafter{stfloats}
596 \LWR@loadafter{struktex}
597 \LWR@loadafter{subcaption}
598 \LWR@loadafter{subfig}
599 \LWR@loadafter{subfigure}
```

```
600 \LWR@loadafter{subsupscripts}
601 \LWR@loadafter{supertabular}
602 \LWR@loadafter{svg}
603 \LWR@loadafter{swfigure}
604 \LWR@loadafter{syntonly}
605 \LWR@loadafter{t1inc}
606 \LWR@loadafter{tabfigures}
607 \LWR@loadafter{tabls}
608 \LWR@loadafter{tablefootnote}
609 \LWR@notmemoirloadafter{tabularx}
610 \LWR@loadafter{tabulary}
611 \LWR@loadafter{tagpdf}
612 \LWR@loadafter{tascmac}
613 \LWR@loadafter{tcolorbox}
614 \LWR@loadafter{termcal}
615 \LWR@loadafter{textarea}
616 % \LWR@loadafter{textcomp}% maybe before lwarp with font packages
617 \LWR@loadafter{textfit}
618 \LWR@loadafter{textpos}
619 \LWR@loadafter{theorem}
620 \LWR@loadafter{thinsp}
621 \LWR@loadafter{thm-listof}
622 \LWR@loadafter{thm-restate}
623 \LWR@loadafter{thmbox}
624 \LWR@loadafter{thmtools}
625 \LWR@loadafter{threadcol}
626 \LWR@loadafter{threeparttable}
627 \LWR@loadafter{threeparttablex}
628 \LWR@loadafter{thumb}
629 \LWR@loadafter{thumbs}
630 \LWR@loadafter{tikz}
631 \LWR@loadafter{titlesps}
632 \LWR@loadafter{titlesec}
633 \LWR@loadafter{titletoc}
634 \LWR@notmemoirloadafter{titling}
635 % \LWR@loadafter{tocbasic}% preloaded by koma-script classes
636 \LWR@notmemoirloadafter{tocbibind}
637 \LWR@loadafter{tocdata}
638 \LWR@loadafter{tocenter}
639 \LWR@notmemoirloadafter{tocloft}
640 \LWR@loadafter{tocstyle}
641 \LWR@loadafter{todo}
642 \LWR@loadafter{todonotes}
643 \LWR@loadafter{topcapt}
644 \LWR@loadafter{tram}
645 \LWR@loadafter{transparent}
646 \LWR@loadafter{trimclip}
647 \LWR@loadafter{trivfloat}
648 \LWR@loadafter{truncate}
649 \LWR@loadafter{turnthepage}
650 \LWR@loadafter{twoup}
651 % \LWR@loadafter{txfonts}% may be loaded before lwarp
652 % txgreek may be loaded before lwarp

653 % \LWR@loadafter{typearea}% preloaded by koma-script classes
```

```

654 \LWR@loadafter{typicons}
655 % \LWR@loadafter{ulem}% preloaded by ctextart and related classes
656 \LWR@loadafter{umoline}
657 \LWR@loadafter{underscore}
658 % unicode-math may be loaded before lwarp
659 \LWR@loadafter{units}
660 \LWR@loadafter{unitsdef}
661 \LWR@loadafter{upgreek}
662 \LWR@loadafter{upref}
663 \LWR@loadafter{url}
664 \LWR@loadafter{ushort}
665 \LWR@loadafter{uspace}
666 \LWR@loadafter{varioref}
667 \LWR@notmemoirloadafter{verse}
668 \LWR@loadafter{versonotes}
669 \LWR@loadafter{vertbars}
670 \LWR@loadafter{vmargin}
671 \LWR@loadafter{vowel}
672 \LWR@loadafter{vpe}
673 \LWR@loadafter{vwcol}
674 \LWR@loadafter{wallpaper}
675 \LWR@loadafter{watermark}
676 \LWR@loadafter{widetable}
677 \LWR@loadafter{widows-and-orphans}
678 \LWR@loadafter{witharrows}
679 \LWR@loadafter{wrapfig}
680 \LWR@loadafter{xbmks}
681 \LWR@loadafter{xcolor}
682 \LWR@loadafter{xexchangebar}
683 \LWR@loadafter{xellipsis}
684 % xetexko-vertical must be loaded before lwarp
685 \LWR@loadafter{xfakebold}
686 \LWR@loadafter{xfrac}
687 \LWR@loadafter{xltabular}
688 \LWR@loadafter{xltextra}
689 \LWR@loadafter{xmpincl}
690 \LWR@loadafter{xpiano}
691 \LWR@loadafter{xpinyin}
692 \LWR@loadafter{xr}
693 \LWR@loadafter{xr-hyper}
694 \LWR@loadafter{xtab}
695 % xunicode must be loaded before lwarp
696 \LWR@loadafter{xurl}
697 \LWR@loadafter{xy}
698 \LWR@loadafter{zwpageLayout}

```

21 MD5 hashing

The MD5 hash is used for lateximage filenames for svg math.

```

699 \newcommand{\LWR@mdfive}[1]{%
700   \PackageError{lwarp}
701     {No MD5 macro was found}

```

```

702     {%
703         Lwarp must find the macros \protect\pdfmdfivesum\space
704         or \protect\mdfivesum.%
705     }
706 }

```

The default for pdf \LaTeX , dvi \LaTeX , up \LaTeX , etc:

```
707 \let\LWR@mdfive\pdfmdfivesum
```

For Lua \LaTeX :

```

708 \ifLuaTeX
709 \RequirePackage{pdftexcmds}
710 \let\LWR@mdfive\pdf@mdfivesum
711 \fi

```

For Xe \LaTeX :

```

712 \ifXeTeX
713 \@ifundefined{pdfmfivesum}{}
714     {\let\LWR@mdfive\pdfmdfivesum}
715 \@ifundefined{mdfivesum}{}
716     {\let\LWR@mdfive\mdfivesum}
717 \fi

```

22 pdf \LaTeX T1 and UTF-8 encoding

When using pdf \LaTeX , lwarp requires T1 font encoding, and recommends UTF-8 input encoding.

If some other input encoding is already defined, lwarp will try to use it instead, and hope for the best.

Xe \LaTeX and Lua \LaTeX are both UTF-8 by nature.

`\LWR@pdfencoding` Sets T1, and also utf8 if not already set.

```

718 \newcommand*{\LWR@pdfencoding}{%
719     \RequirePackage[T1]{fontenc}
720
721     \@ifpackageloaded{inputenc}{}{
722         \@ifpackageloaded{inputenx}{}{
723             \RequirePackage[utf8]{inputenc}
724         }
725     }
726 }

727 \ifPDFTeX% pdflatex or dvi latex
728     \LWR@pdfencoding
729 \fi

```

```

730
731 \ifpTeX
732   \LWR@pdfencoding
733 \fi

```

23 Unicode input characters

for HTML & PRINT: If using *pdf_latex*, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be `\texttimes`.

The first arguments of `\newunicodechar` below are text ligatures in the source code, even though they are not printed in the following listing.

```

734 \ifpTeX
735 \else
736 \RequirePackage{newunicodechar}
737
738 \newunicodechar{x}{\texttimes}
739
740 \ifPDFTeX% pdflatex or dvi latex
741 \newunicodechar{ff}{ff}% Here, the first arguments are ligatures.
742 \newunicodechar{fi}{fi}
743 \newunicodechar{fl}{fl}
744 \newunicodechar{ffi}{ffi}
745 \newunicodechar{ffl}{ffl}
746 \newunicodechar{-}{---}
747 \newunicodechar{-}{--}
748 \fi
749
750 \fi

```

24 Avoid a bitmapped font

If DVI or PDF \LaTeX , and if the default Computer Modern is the selected font family, ensure that `cm-super` or `lmodern` is used to provide a vector font.

```

751 \ifxetexorluatex
752 \else
753   \ifdefstring{\f@family}{cmr}{
754     \IfFileExists{type1ec.sty}% found in cm-super
755     {}
756     {% cm-super not installed
757       \IfFileExists{lmodern.sty}{
758         \PackageInfo{lwarp}{cm-super not installed, loading lmodern}
759         \RequirePackage{lmodern}
760       }{
761         \PackageError{lwarp}
762         {%

```

```

763             Lwarp requires a vector font.\MessageBreak
764             Install and load cm-super, lmodern, or another\MessageBreak
765             Type-1 vector font before loading lwarp.\MessageBreak
766             Enter 'H' for possible solutions%
767         }
768     {%
769         Install cm-super or lmodern.\MessageBreak
770         If lmodern, load it before lwarp:\MessageBreak
771         \space\space\protect\usepackage{lmodern}\MessageBreak
772         \space\space\protect\usepackage{lwarp}%
773     }
774 }
775 }% cm-super not installed
776 }{}% f@family
777 \fi

```

25 Upright quotes

In PDFTEX, preserve upright quotes in verbatim text. upquote also loads textcomp.

```

778 \ifPDFTeX
779 \RequirePackage{upquote}
780 \fi
781
782 \ifpTeX
783 \RequirePackage{upquote}
784 \fi

```

26 Miscellaneous tools

26.1 Variables

```

785 \newlength{\LWR@templengthone}
786 \newlength{\LWR@templengthtwo}
787 \newlength{\LWR@templengththree}
788 \newcounter{LWR@tempcountone}

```

26.2 Lengths and units

`\LWR@providelength` `{\lengthname}` Provides the length if it isn't defined yet.

Used to provide source compatibility for lengths which will be ignored, but might or might not be already provided by other packages.

```

789 \newcommand*\LWR@providelength[1]{%
790   \ifdeflength{#1}{\newlength{#1}}%
791 }

```

`\LWR@convertto` $\langle dest\ unit\rangle$ $\langle length\rangle$

Prints a length in the given units, without printing the unit itself.

```
792 \newcommand*\LWR@convertto[2]{\strip@pt\dimexpr #2*65536/\number\dimexpr 1#1}
```

`\LWR@printpercentlength` $\langle smaller\rangle$ $\langle larger\rangle$

Prints a percent ratio of the two lengths.

```
793 \newcommand*\LWR@printpercentlength[2]{%
794   \setcounter{LWR@tempcountone}{100*\ratio{#1}{#2}}%
795   \arabic{LWR@tempcountone}%
796 }
```

26.3 Counters

`\defaddtocounter` $\langle name\rangle$ $\langle value\rangle$

Locally add to a counter.

```
797 \providecommand*\defaddtocounter[2]{%
798   \defcounter{#1}{\value{#1}+#2}%
799 }
```

26.4 Patching

`\LWR@patcherror` $\langle packagename\rangle$ $\langle macroname\rangle$

Prints an error if could not patch a macro.

```
800 \newcommand*\LWR@patcherror[2]{%
801   \PackageError{lwarp}%
802     {%
803       Unable to patch package #1,\MessageBreak
804       macro \LWRbackslash #2.\MessageBreak
805       Lwarp may need to be updated%
806     }%
807   {Please contact the maintainer of the Lwarp package.}%
808 }
```

26.5 Chinese text isolation

`\LWR@isolate` $\langle text\rangle$ Isolates Chinese characters from the surrounding text. This is required to avoid extra spaces on either side of the Chinese characters, especially when written to a file.

```
809 \newcommand{\LWR@isolate}[1]{#1}%
```

```

810
811 \@ifpackageloaded{ctexpatch}{
812   \renewcommand{\LWR@isolate}[1]{\null#1\null}%
813 }{}
814
815 \@ifpackageloaded{xeCJK}{
816   \renewcommand{\LWR@isolate}[1]{\null#1\null}%
817 }{}

```

`\LWR@disablepinyin` Disable `xpinyin` during file, sideroc, and footnote generation. Set by `xpinyin`.

```
818 \newcommand*{\LWR@disablepinyin}{}

```

26.6 Inserting vertical space

`\LWR@forceemptyline` Extra vertical space in the HTML output. Use after `\LWR@stoppars`.

```

819 \newcommand*{\LWR@forceemptyline}{%
820   \LWR@origrule{0pt}{1\baselineskip}%
821   \LWR@originewline%
822 }

```

26.7 Argument selection

`\LWR@firstoffour` $\{\langle first \rangle\} \{\langle second \rangle\} \{\langle third \rangle\} \{\langle fourth \rangle\}$

`\LWR@secondoffour` $\{\langle first \rangle\} \{\langle second \rangle\} \{\langle third \rangle\} \{\langle fourth \rangle\}$

`\LWR@thirdoffour` $\{\langle first \rangle\} \{\langle second \rangle\} \{\langle third \rangle\} \{\langle fourth \rangle\}$

`\LWR@fourthoffour` $\{\langle first \rangle\} \{\langle second \rangle\} \{\langle third \rangle\} \{\langle fourth \rangle\}$

Expands to the *n*th of the four arguments. Used for extra cross referencing.

```

823 \long\def\LWR@firstoffour#1#2#3#4{#1}
824 \long\def\LWR@secondoffour#1#2#3#4{#2}
825 \long\def\LWR@thirdoffour#1#2#3#4{#3}
826 \long\def\LWR@fourthoffour#1#2#3#4{#4}

```

26.8 Inside boxes

Greater than zero if currently inside a T_EX box, thus should not use `\LWR@originewpage`. See section [13.2](#).

```

827 \newcounter{LWR@texboxdepth}
828 \setcounter{LWR@texboxdepth}{0}

```

`\LWR@maybe@orignewpage` Only do `\LWR@orignewpage` if not inside a T_EX box.

```
829 \newcommand*{\LWR@maybe@orignewpage}{%
830   \LWR@traceinfo{\LWR@maybe@orignewpage}%
831   \ifnumgreater{\value{\LWR@textboxdepth}}{0}
832     {}%
833     {\LWR@orignewpage}%
834   \LWR@traceinfo{\LWR@maybe@orignewpage done}%
835 }
```

26.9 Global boxes

`\LWR@gsavebox` $\{\langle\textit{macroname}\rangle\} \{\langle\textit{contents}\rangle\}$

From <https://tex.stackexchange.com/questions/288702/savebox-forgets-its-content-across-columns-inside-align>

```
836 \DeclareRobustCommand\LWR@gsavebox[1]{%
837   \@ifnextchar(%
838     {\LWR@@gsavepicbox#1}{\@ifnextchar[{\LWR@@gsavebox#1}{\LWR@gsbox#1}}}%
839   \long\def\LWR@gsbox#1#2{\global\setbox#1\hbox{%
840     \color@setgroup#2\color@endgroup}}
841   \def\LWR@@gsavebox#1[#2]{%
842     \@ifnextchar [{{\LWR@@igsavebox#1[#2]}{\LWR@@igsavebox#1[#2][c]}}
843     \long\def\LWR@@igsavebox#1[#2][#3]#4{%
844       \LWR@gsbox#1{\@imakebox[#2][#3]{#4}}
845     \def\LWR@@gsavepicbox#1(#2,#3){%
846       \@ifnextchar[%
847         {\LWR@@igsavepicbox#1(#2,#3)}{\LWR@@igsavepicbox#1(#2,#3)[]}}
848     \long\def\LWR@@igsavepicbox#1(#2,#3)[#4]#5{%
849       \LWR@gsbox#1{\@imakepicbox(#2,#3)[#4]{#5}}}
```

Env `LWR@glrbox` $\{\langle\textit{macroname}\rangle\}$

```
850 \def\LWR@glrbox#1{%
851   \edef\reserved@a{%
852     \endgroup
853     \global\setbox#1\hbox{%
854       \begingroup\aftergroup}%
855     \def\noexpand\@currentenv{\@currentenv}%
856     \def\noexpand\@currentline{\on@line}}%
857   \reserved@a
858   \@endpfalse
859   \color@setgroup
860   \ignorespaces}
861 \let\LWR@endglrbox\LWR@endlrbox
```

26.10 Converting a macro name to a cs name

`\macrotoaname` $\{\langle\textit{macro name with backslash}\rangle\}$

Results in the macro name without the leading backslash.

Ref: <https://tex.stackexchange.com/questions/42318/removing-a-backslash-from-a-character-sequence>

```
862 \newcommand*{\macroctocname}[1]{%
863   \ifcat\relax\noexpand#1%
864     \expandafter\expandafter\expandafter\@gobble\expandafter\string
865   \fi
866   #1%
867 }
```

26.11 Title case

`\LWRtexttitlecase`

```
868 \ExplSyntaxOn
869 \newcommand*{\LWRtexttitlecase}[1]{%
870   \text_titlecase:n{#1}%
871 }
872 \ExplSyntaxOff
```

26.12 LetLtxMacros

`\LWR@LetLtxMacros` $\{\langle newcsname \rangle\} \{\langle oldcsname \rangle\}$

`\LetLtxMacro` with cs names.

```
873 \newcommand*{\LWR@LetLtxMacros}[2]{%
874   \expandafter\LetLtxMacro\csname #1\expandafter\endcsname%
875   \csname#2\endcsname%
876 }
```

26.13 Absorbing a star

`\LWR@absorbstar` $\{\langle csname \rangle\}$

Modifies a macro to absorb a star. Used for `cleveref`, since `hyperref` is emulated, so the starred macros are not created by `cleveref`.

```
877 \newcommand*{\LWR@absorbstar}[1]{%
878   \LWR@LetLtxMacros{\LWR@origins@#1}{#1}%
879   \csdef{#1}{\@ifstar{\csuse{\LWR@origins@#1}}{\csuse{\LWR@origins@#1}}}
880   \expandafter\robustify\csname #1\endcsname
881 }
```

27 Operating-System portability

Prog	Unix	lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as “UNIX” in the configuration files), and MS-WINDOWS is supported as well.
Prog	Mac OS	
	Linux	
Prog	MS-Windows	If MS-WINDOWS is not correctly detected, use the lwarp option OSWindows.
Prog	Windows	When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean usingOSWindows is set true. This boolean may be tested by the user for later use.
Opt	OSWindows	

27.1 Literal characters

Literal characters to be used in `PrintLatexCmd` and `HTMLLatexCmd`. These are defined without @ to easily allow their inclusion in the user’s document.

The literal % character:

```
882 \let\LWRpercent\@percentchar
```

The literal \$ character:

```
883 \catcode'\$=12
884 \def\LWRdollar{\$}
885 \catcode'\$=3
```

The literal & character:

```
886 \catcode'\&=12
887 \def\LWRamp{&}
888 \catcode'\&=4
```

The literal \ character. The ampersand is temporarily set to the escape character during the definition of the backslash macro.

```
889 \catcode'\&=0
890 &catcode'\=12
891 \def&LWRbackslash{\}
892 &catcode'\=0
893 \catcode'\&=4
```

The literal { character. The ampersand is temporarily set to the begin group character during the definition of the leftbrace macro.

```
894 \catcode'\&=1
895 \catcode'\{=12
896 \def\LWRleftbrace&{\}
897 \catcode'\{=1
898 \catcode'\&=4
```

The literal } character. The ampersand is temporarily set to the end group character during the definition of the leftbrace macro.

```
899 \catcode'\&=2
900 \catcode'\}=12
901 \def\LWRrightbrace{ }&
902 \catcode'\}=2
903 \catcode'\&=4
```

The literal # character:

```
904 \catcode'\#=12
905 \def\LWRhash{#}
906 \catcode'\#=6
```

`\LWRopquote` The operating system's quote mark, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
907 \def\LWRopquote{' }
```

`\LWRopseq` The operating system's sequential execution command, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
908 \def\LWRopseq{\space\LWRamp\LWRamp\space\space}
```

27.2 Common portability code

`Bool usingOSWindows` Set if the `OSWindows` option is used, or if `WINDOWS` is automatically detected.

```
909 \newbool{usingOSWindows}
910 \boolfalse{usingOSWindows}
```

27.3 UNIX, LINUX, and MAC OS

`\OSPathSymbol` Symbol used to separate directories in a path.

```
911 \newcommand*{\OSPathSymbol}{/}
```

27.4 MS-WINDOWS

For MS-WINDOWS:

`\LWR@setOSWindows` Set defaults for the MS-WINDOWS operating system. `lwarp` attempts to auto-detect the operating system, and the `OSWindows` option may also be used to force MS-WINDOWS compatibility.

```

912 \newcommand*{\LWR@setOSWindows}
913 {
914 \booltrue{usingOSWindows}
915 \renewcommand*{\OSPathSymbol}{\@backslashchar}
916 \def\LWRopquote{"}
917 \def\LWRopseq{\space\LWRamp\space\space}
918 }

```

Test for windows during compile. The user may also specify OSWindows package option in case this test fails.

```

919 \ifwindows
920 \LWR@setOSWindows
921 \fi

```

28 Package options

Pkg `kvoptions` Allows key/value package options.

```

922 \RequirePackage{kvoptions}
923 \SetupKeyvalOptions{family=LWR,prefix=LWR@}

```

`\lwarppsetup` A user interface to set the keys:

```

924 \newcommand{\lwarppsetup}[1]{\setkeys{LWR}{#1}}

```

Bool `warpingprint`

Bool `warpingHTML`

Bool `mathjax`

Bool `LWR@origmathjax`

Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax.

`LWR@origmathjax` remembers the original setting to be restored by `\displaymathnormal`.

```

925 \newbool{warpingprint}
926 \newbool{warpingHTML}
927 \newbool{mathjax}
928 \newbool{LWR@origmathjax}

```

defaults The default is print output, and svg math if the user chose HTML output.

```

929 \booltrue{warpingprint}%
930 \boolfalse{warpingHTML}%
931 \boolfalse{mathjax}%

```

Opt `warpprint` If the `warpprint` option is given, boolean `warpingprint` is true and boolean `warpingHTML` is false, and may be used for `\ifbool` tests.

```

932 \DeclareVoidOption{warpprint}{%
933   \PackageInfo{lwarp}{Using option 'warpprint'}

```

```

934 \booltrue{warpingprint}%
935 \boolfalse{warpingHTML}%
936 }

```

Opt warpHTML Anything in the warpHTML environment will be generated for HTML output only.

Opt warpHTML If the warpHTML option is given, boolean warpingHTML is true and boolean warpingprint is false, and may be used for \ifbool tests.

```

937 \DeclareVoidOption{warpHTML}{%
938 \PackageInfo{lwarp}{Using option 'warpHTML'}%
939 \booltrue{warpingHTML}%
940 \boolfalse{warpingprint}%
941 }

```

Opt mathsvg Option mathsvg selects SVG math display: If the mathsvg option is given, boolean mathjax is false, and may be used for \ifbool tests.

```

942 \DeclareVoidOption{mathsvg}{%
943 \PackageInfo{lwarp}{Using option 'mathsvg'}
944 \boolfalse{mathjax}%
945 \boolfalse{LWR@origmathjax}%
946 }

```

Opt mathjax Option mathjax selects MATHJAX math display: If the mathjax option is given, boolean mathjax is true, may be used for \ifbool tests.

```

947 \DeclareVoidOption{mathjax}{%
948 \PackageInfo{lwarp}{Using option 'mathjax'}
949 \booltrue{mathjax}%
950 \booltrue{LWR@origmathjax}%
951 }

```

Opt BaseJobname Option BaseJobname sets the \BaseJobname for this document.

Default: \jobname

This is the \jobname of the printed version, even if currently compiling the HTML version. I.e. this is the \jobname without _html appended. This is used to set \HomeHTMLFilename if the user did not provide one.

```

952 \DeclareStringOption[\jobname]{BaseJobname}

```

Opt ImagesDirectory Option ImagesDirectory sets the name of the directory to use for the lateximage images.

Default: \jobname-images

```

953 \DeclareStringOption[\BaseJobname-images]{ImagesDirectory}

```

Opt ImagesName Option ImagesName sets the prefix to use for the lateximage images.

Default: image-

```

954 \DeclareStringOption[image-]{ImagesName}

```

- Opt `makeindexStyle` Selects a custom `.ist` file. A customized file should be based on `lwarp.ist`. See section 8.6.20.
 Default: `lwarp.ist`
- ```
955 \DeclareStringOption[lwarp.ist]{makeindexStyle}
```
- Opt `xindyStyle` Selects a custom `.xdy` file. A customized file should be based on `lwarp.xdy`. See section 8.6.21.  
 Default: `lwarp.xdy`
- ```
956 \DeclareStringOption[lwarp.xdy]{xindyStyle}
```
- Opt `xindyLanguage` Sets the *xindy* language to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index and glossary.
 Default: `english`
- ```
957 \DeclareStringOption[english]{xindyLanguage}
```
- Opt `xindyCodepage` Sets the *xindy* codepage to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index.  
 Default: `utf8`
- ```
958 \DeclareStringOption[utf8]{xindyCodepage}
```
- Opt `xindexConfig` Selects a custom `xindex-*.lua` file. A customized file should be based on `xindex-cfg.lua`. See section 8.6.22.
 Default: `<empty>`
- ```
959 \DeclareStringOption[]{xindexConfig}
```
- Opt `pdftotextEnc` The option `pdftotextEnc` sets the encoding used by *pdftotext*. This is passed to *pdftotext* using its `-enc` option, and is used when converting L<sup>A</sup>T<sub>E</sub>X PDF output with HTML tags into a plain-text file with HTML tags.  
 Default: `UTF-8`
- ```
960 \DeclareStringOption[UTF-8]{pdftotextEnc}
```
- Opt `lwarpmk` Tells *lwarp* to generate a local copy of *lwarpmk* called `lwarpmk.lua`. Useful for archiving for future use. This file may be made executable and acts just like *lwarpmk*.
- If `lwarpmk` option, creates a local copy of `lwarpmk.lua`:
- ```
961 \newbool{LWR@creatinglwarpmk}
962 \boolfalse{LWR@creatinglwarpmk}
963
964 \DeclareVoidOption{lwarpmk}{
965 \PackageInfo{lwarp}{Using option 'lwarpmk'}
966 \booltrue{LWR@creatinglwarpmk}
967 }
```
- Opt `OSWindows` Tells *lwarp* to use MS-WINDOWS compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated `lwarpmk.conf` file to find out whether the operating system was detected correctly.
- ```
968 \DeclareVoidOption{OSWindows}{
```

```

969 \PackageInfo{lwarp}{Using option 'OSWindows'}
970 \LWR@setOSWindows
971 }

```

Opt HomeHTMLFilename The filename of the homepage. The default is the jobname. This option is stored into `\LWR@HomeHTMLFilename`, and later transferred into `\HomeHTMLFilename` for internal use.

```
972 \DeclareStringOption[]{HomeHTMLFilename}
```

Opt HTMLFilename The filename prefix of web pages after the homepage. The default is empty, no prefix. This option is stored into `\LWR@HTMLFilename`, and later transferred into `\HTMLFilename` for internal use.

```
973 \DeclareStringOption[]{HTMLFilename}
```

Opt PrintLatexCmd The shell commands to use to compile the print document.
Default: `<automatic>`

```
974 \DeclareStringOption[]{PrintLatexCmd}
```

Opt HTMLLatexCmd The shell commands to use to compile the HTML document.
Default: `<automatic>`

```
975 \DeclareStringOption[]{HTMLLatexCmd}
```

Opt PrintIndexCmd The shell commands to use to compile the print indexes.
Default: `<empty>`

```
976 \DeclareStringOption[]{PrintIndexCmd}
```

Opt HTMLIndexCmd The shell commands to use to compile the HTML indexes.
Default: `<empty>`

```
977 \DeclareStringOption[]{HTMLIndexCmd}
```

Opt LatexmkIndexCmd The shell commands to be used by *latexmk* to compile the print indexes. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `LatexmkIndexCmd` does not include the filename, which will be provided by *latexmk*.

```
978 \DeclareStringOption[]{LatexmkIndexCmd}
```

Opt makeindex Tells *lwarp* to use *makeindex* for index generation. When `lwarpmk.conf` and `*.lwarpmkconf` are generated, `PrintIndexCmd` and `HTMLIndexCmd` will be set for *makeindex* with a single index file.

```
979 \DeclareBoolOption[false]{makeindex}
```

Opt xindy Tells *lwarp* to use *xindy* for index generation. When `lwarpmk.conf` and `*.lwarpmkconf` are generated, `PrintIndexCmd` and `HTMLIndexCmd` will be set for *xindy* with a single index file.

```
980 \DeclareBoolOption[false]{xindy}
```

Opt `xindex` Tells `lwarp` to use *xindex* for index generation. When `lwarpmk.conf` and `*.lwarpmkconf` are generated, `PrintIndexCmd` and `HTMLIndexCmd` will be set for *xindex* with a single index file.

```
981 \DeclareBoolOption[false]{xindex}
```

Opt `IndexRef` Tells `lwarp` how to display the index entries in HTML output. See section 7.5.
Default: `cref`

```
982 \DeclareStringOption[cref]{IndexRef}
```

Opt `GlossaryCmd` The shell command to use to compile the glossary. The print or HTML version of the glossary filename will be appended to this command.
Default: `makeglossaries`

```
983 \DeclareStringOption[makeglossaries]{GlossaryCmd}
```

Opt `latexmk` Option `latexmk` tells `lwarpmk` to use *latexmk* when compiling documents.

```
984 \DeclareBoolOption[false]{latexmk}
```

Opt `dvips` Option `dvips` tells `lwarpmk` to use *dvips* when compiling DVI *latex* documents.

```
985 \DeclareBoolOption[false]{dvips}
```

Opt `dvipdfm` Option `dvipdfm` tells `lwarpmk` to use *dvipdfm* when compiling DVI *latex* documents.

```
986 \DeclareBoolOption[false]{dvipdfm}
```

Opt `dvipdfmx` Option `dvipdfmx` tells `lwarpmk` to use *dvipdfmx* when compiling DVI *latex* documents.

```
987 \DeclareBoolOption[false]{dvipdfmx}
```

Execute options Execute the package options, with the defaults which have been set just above:

```
988 \ProcessKeyvalOptions*\relax
```

28.1 Additional options support

Assign the `\BaseJobname` if the user hasn't provided one:

```
989 \providecommand*\BaseJobname{\LWR@BaseJobname}
```

Defaults unless already over-ridden by the user:

```
990 \ifcseempty{LWR@HomeHTMLFilename}{
991   \newcommand*\HomeHTMLFilename{\BaseJobname}
992 }{
993   \csedef{HomeHTMLFilename}{\LWR@HomeHTMLFilename}
994 }
995
996 \csedef{HTMLFilename}{\LWR@HTMLFilename}
```

Special handling for underscores in labels and filenames.

`\LWR@sanitized` The sanitized version of what was given to `\LWR@sanitize`. Characters are set to their detokenized versions. Required for underscores in labels and filenames.

```
997 \newcommand*{\LWR@sanitized}{}
```

`\LWR@sanitize` `{\text}`

Sanitizes the text and returns the result in `\LWR@sanitized`.

```
998 \newcommand*{\LWR@sanitize}[1]{%
999 \edef\LWR@sanitized{#1}%
1000 \edef\LWR@sanitized{\detokenize\expandafter{\LWR@sanitized}}%
1001 }
```

Sanitize some string options to neutralize underscores.

```
1002 \LWR@sanitize{\LWR@BaseJobname}
1003 \edef\LWR@BaseJobname{\LWR@sanitized}
1004
1005 \LWR@sanitize{\LWR@ImagesDirectory}
1006 \edef\LWR@ImagesDirectory{\LWR@sanitized}
1007
1008 \LWR@sanitize{\LWR@ImagesName}
1009 \edef\LWR@ImagesName{\LWR@sanitized}
```

`\LWR@PrintIndexCmd` and `\LWR@HTMLIndexCmd` are tested to see if they are empty. If so, they are set to a reasonable defaults for a single index using *makeindex*, then possibly set to defaults for *xindy* if the `lwarp xindy` option was selected, then likewise for *xindex* if the `xindex` option was selected.

```
1010 \ifdefempty{\LWR@PrintIndexCmd}{
1011   \renewcommand{\LWR@PrintIndexCmd}{%
1012     makeindex -s \LWR@makeindexStyle \space \jobname.idx%
1013   }
1014   \ifbool{\LWR@xindy}{
1015     \renewcommand{\LWR@PrintIndexCmd}{%
1016       xindy
1017       -M \LWR@xindyStyle \space
1018       -L \LWR@xindyLanguage \space
1019       -C \LWR@xindyCodepage \space
1020       \jobname.idx%
1021     }
1022   }{}
1023   \ifbool{\LWR@xindex}{
1024     \ifdefvoid{\LWR@xindexConfig}{
1025       \renewcommand{\LWR@PrintIndexCmd}{%
1026         xindex
1027         \jobname.idx%
1028       }
1029     }{
1030       \renewcommand{\LWR@PrintIndexCmd}{%
```

```

1031         xindex
1032         -c \LWR@indexConfig \space
1033         \jobname.idx%
1034     }
1035 }
1036 {}
1037 {}
1038
1039 \ifdefempty{\LWR@HTMLIndexCmd}{
1040     \renewcommand{\LWR@HTMLIndexCmd}{%
1041         makeindex -s \LWR@makeindexStyle \space \jobname_html.idx%
1042     }
1043     \ifbool{LWR@xindy}{
1044         \renewcommand{\LWR@HTMLIndexCmd}{%
1045             xindy
1046             -M \LWR@xindyStyle \space
1047             -L \LWR@xindyLanguage \space
1048             -C \LWR@xindyCodepage \space
1049             \jobname_html.idx%
1050         }
1051     }{}
1052     \ifbool{LWR@index}{
1053         \ifdefvoid{\LWR@indexConfig}{
1054             \renewcommand{\LWR@HTMLIndexCmd}{%
1055                 xindex
1056                 \jobname_html.idx%
1057             }
1058         }{
1059             \renewcommand{\LWR@HTMLIndexCmd}{%
1060                 xindex
1061                 -c \LWR@indexConfig \space
1062                 \jobname_html.idx%
1063             }
1064         }
1065     }{}
1066 }{}
1067
1068 \ifdefempty{\LWR@LatexmkIndexCmd}{
1069     \renewcommand{\LWR@LatexmkIndexCmd}{%
1070         makeindex -s \LWR@makeindexStyle%
1071     }
1072     \ifbool{LWR@xindy}{
1073         \renewcommand{\LWR@LatexmkIndexCmd}{%
1074             xindy
1075             -M \LWR@xindyStyle \space
1076             -L \LWR@xindyLanguage \space
1077             -C \LWR@xindyCodepage%
1078         }
1079     }{}
1080     \ifbool{LWR@index}{
1081         \ifdefvoid{\LWR@indexConfig}{
1082             \renewcommand{\LWR@LatexmkIndexCmd}{%
1083                 xindex
1084             }
1085         }{

```

```

1086         \renewcommand{\LWR@LatexmkIndexCmd}{%
1087             xindex
1088             -c \LWR@xindexConfig
1089         }
1090     }
1091 }{}
1092 }{}

```

28.2 Conditional compilation

`\warpprintonly` {<*contents*>}

Only process the contents if producing printed output.

```
1093 \newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{} }
```

`\warpHTMLonly` {<*contents*>}

Only process the contents if producing HTML output.

```
1094 \newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{} }
```

`\pkg comment` Provides conditional code blocks.

Attempts to use `versions` or `verbatim` fail in some cases, and do not provide much of a speed benefit even when they do work.

```
1095 \RequirePackage{comment}
```

`\LWR@includecomment` {<*env name*>} {<*partial filename*>}

`\LWR@excludecomment` {<*env name*>} {<*partial filename*>}

Use many `comment` cut files to avoid collision in case the user uses the `comment` package. Each filename is “comment_#2.cut”. Based on the `comment` package.

```

1096 \def\LWR@includecomment
1097 #1#2{\message{Lwarp: Including comment '#1'}%
1098     \csarg\def{After#1Comment}{%
1099         \CloseAndInputCutFile%
1100         \csundef{LWR@#1commentused}%
1101     }
1102     \csarg\def{#1}{%
1103         \endgroup
1104         \ifcsdef{LWR@#1commentused}{
1105             \PackageError{lwarp}%
1106                 {Nested #1 environment}%
1107             {%
1108                 Environment #1 cannot be nested.\MessageBreak
1109                 This can happen when a package is loaded

```

```

1110             from inside a\MessageBreak
1111             #1 environment.%
1112         }%
1113     }{\relax}
1114     \csdef{LWR@#1commentused}{}
1115     \message{Including '#1' comment.}%
1116     \def\CommentCutFile{comment_#2.cut}
1117     \SetUpCutFile
1118     \ProcessComment{#1}
1119 }%
1120 \CommentEndDef{#1}
1121 }
1122
1123 \def\LWR@excludecomment
1124 #1#2{\message{Lwarp: Excluding comment '#1'}%
1125     \csarg\def{#1}{
1126         \endgroup
1127         \message{Excluding '#1' comment.}%
1128         \begingroup
1129             \def\CommentCutFile{comment_#2.cut}
1130             \def\ProcessCutFile{}%
1131             \def\ThisComment####1{}%
1132             \ProcessComment{#1}
1133         }%
1134     \csarg\def{After#1Comment}{\CloseAndInputCutFile \endgroup}
1135     \CommentEndDef{#1}}

```

Env `warpall` Anything in the `warpall` environment will be generated for print or HTML outputs.

```
1136 \LWR@includecomment{warpall}{all}
```

Env `warpHTML` For HTML output:

```

1137 \ifbool{warpingHTML}
1138   {\LWR@includecomment{warpHTML}{html}}
1139   {\LWR@excludecomment{warpHTML}{html}}

```

Env `warpprint` Anything in the `warpprint` environment will be generated for print output only.

```

1140 \ifbool{warpingprint}
1141   {\LWR@includecomment{warpprint}{print}}
1142   {\LWR@excludecomment{warpprint}{print}}

```

Env `warpMathJax` Only if `MATHJAX` is being used along with HTML.

```

1143 \begin{warpprint}
1144 \LWR@excludecomment{warpMathJax}{mathjax}
1145 \end{warpprint}
1146
1147 \begin{warpHTML}
1148 \ifbool{mathjax}
1149   {\LWR@includecomment{warpMathJax}{mathjax}}

```

```
1150   {\LWR@excludecomment{warpMathJax}{mathjax}}
1151 \end{warpHTML}
```

Env LWRcreatelwarpmk Optionally generate a local copy of *lwarpmk*. Default to no.

```
1152 \ifbool{LWR@creatinglwarpmk}
1153   {\LWR@includecomment{LWRcreatelwarpmk}{lwarpmk}}
1154   {\LWR@excludecomment{LWRcreatelwarpmk}{lwarpmk}}
```

29 Required packages

These packages are automatically loaded by *lwarp* when generating HTML output. Some of them are also automatically loaded when generating print output, but some are not.

for HTML output: 1155 \begin{warpHTML}

Pkg fontspec Load fontspec if necessary:

```
1156 \ifxetexorluatex
1157 \@ifpackageloaded{fontspec}{\{
1158   \usepackage[no-math]{fontspec}
1159 \}
```

The monospaced font is used for HTML tags, so turn off its TeX ligatures and common ligatures:

```
1160 \defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
1161 \defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
1162 \defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
1163 \else
```

pdf_latex only: Only pre-loaded if *pdf_latex* is being used.

Pkg microtype

ligatures Older browsers don't display ligatures. Turn off letter ligatures, keeping \LaTeX dash and quote ligatures, which may fail on older browsers but at least won't corrupt written words.

```
1164 \RequirePackage {microtype}
1165
1166 \microtypesetup{
1167   protrusion=false,
1168   expansion=false,
1169   tracking=false,
1170   kerning=false,
1171   spacing=false}
1172 % \begin{macrocode}
1173 %
1174 % Disable ligatures for typewriter fonts.
```

```

1175 % The comma was causing issues with \brand{MathJax} and \cs{,} followed by a comma.
1176 % Ligatures for f, q, t, etc used to be disabled for non-typewriter fonts, but
1177 % are now allowed.
1178 % \changes{v0.89}{2020/08/01}{Disable typewriter ligatures.}
1179 % ^^A \DisableLigatures[,{,},f,q,t,T,Q]{encoding = *,family = *}% previous
1180 % \begin{macrocode}
1181 \DisableLigatures{encoding = *,family = tt*}

1182 \fi

1183 \end{warpHTML}

```

Pkg geometry Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

for HTML output: 1184 \begin{warpHTML}

If geometry has not yet been loaded, use the preexisting page and text sizes to be preserved for later reuse. These will be replaced by lwarp \AtBeginDocument with a very large page size to reduce HTML tag overflow off the page.

```

1185 \@ifpackageloaded{geometry}
1186 {}{
1187   \RequirePackage[
1188     reset,
1189     paperwidth=\paperwidth,
1190     paperheight=\paperheight,
1191     textwidth=\textwidth,
1192     textheight=\textheight,
1193     left=\oddsidemargin,
1194     top=\topmargin,
1195     marginparsep=\marginparsep,
1196     marginparwidth=\marginparwidth,
1197   ]{geometry}
1198 }

```

Remember the original definitions for later reuse. If the geometry package is loaded by the user, lwarp-geometry will nullify the user-level originals.

```

1199 \LetLtxMacro\LWR@origgeometry\geometry
1200 \LetLtxMacro\LWR@orignewgeometry\newgeometry
1201 \LetLtxMacro\LWR@origrestoregeometry\restoregeometry
1202 \LetLtxMacro\LWR@origsavegeometry\savegeometry
1203 \LetLtxMacro\LWR@origloadgeometry\loadgeometry

```

Bool
LWR@allowanothergeometry
geometry may be loaded by the user before `lwarp`, after `lwarp`, or not at all. If before `lwarp`, it will have already been loaded by now and its page layout has already been saved. If **geometry** is loaded after `lwarp`, its layout will be set at that time and the user macros nullified. `\AtEndPreamble` this layout will be saved. If the user never loads **geometry**, `lwarp-geometry` will be loaded `\AtBeginDocument`, but it should not change the page layout set here. This is controlled by the boolean `LWR@allowanothergeometry`. Geometry may be adjusted throughout the preamble until `\AtEndPreamble`, when this boolean is set false.

```
1204 \newbool{LWR@allowanothergeometry}
1205 \booltrue{LWR@allowanothergeometry}
```

Use `\AtEndPreamble` to avoid class and option conflict by changing settings after other packages load, instead of using `geometry` package options:

```
1206 \AtEndPreamble{
```

Whatever geometry choices the user has made in the preamble, either before or after `lwarp` was loaded, are now saved for possible temporary reuse, such as by `lyluatex`.

See the `lwarp-geometry` section for what happens if `geometry` is loaded after `lwarp`.

```
1207 \LWR@origsavegeometry{LWR@usergeometry}
```

The user's paper size is saved for later reuse, such as by the `pdfpages` or `parallel` packages.

```
1208 \newlength{\LWR@userspaperwidth}
1209 \setlength{\LWR@userspaperwidth}{\paperwidth}
1210
1211 \newlength{\LWR@userspaperheight}
1212 \setlength{\LWR@userspaperheight}{\paperheight}
1213
1214 \newlength{\LWR@usersmarginparwidth}
1215 \setlength{\LWR@usersmarginparwidth}{\marginparwidth}
1216
1217 \newlength{\LWR@userstextwidth}
1218 \setlength{\LWR@userstextwidth}{\textwidth}
1219
1220 \newlength{\LWR@userstextheight}
1221 \setlength{\LWR@userstextwidth}{\textheight}
```

For `lwarp`, use a very large page and margins to help avoid letting HTML tags run off the edge:

```
1222 \LWR@origgeometry{
1223   reset,
1224   paperheight=190in,
1225   paperwidth=20in,
1226   left=2in,
1227   right=6in,
1228   top=1in,
1229   bottom=1in,
1230   heightrounded,%
```

1231 }

The `lwarp` page geometry is saved for future restore:

```
1232 \LWR@origsavegeometry{LWR@lwarpgeometry}
```

No longer adjust the page layout when `lwarp-geometry` is loaded `\AtBeginDocument`:

```
1233 \boolfalse{LWR@allowanothergeometry}%
```

`ltsjbook` and other classes can print vertically, and require these to be reset by `lwarp`:

```
1234 \setlength{\textheight}{0.8\paperheight}
```

```
1235 \setlength{\textwidth}{0.7\paperwidth}
```

```
1236
```

```
1237 \@twosidefalse
```

```
1238 \@mparswitchfalse
```

```
1239 ]% \AtEndPreamble
```

```
1240
```

```
1241 \end{warpHTML}
```

for HTML & PRINT: 1242 `\begin{warpall}`

Pkg `xparse`

`LATEX3` command argument parsing

```
1243 \RequirePackage{xparse}
```

Pkg `calc`

```
1244 \RequirePackage{calc}
```

```
1245 \end{warpall}
```

for HTML output: 1246 `\begin{warpHTML}`

Pkg `expl3`

`LATEX3` programming

```
1247 \RequirePackage{expl3}
```

Pkg `getttitlestring`

Used to emulate `\nameref`.

```
1248 \RequirePackage{getttitlestring}
```

Pkg `everyhook`

`everyhook` is used to patch paragraph handling.

```

1249 \@ifundefined{bxjs@everypar}{\let\everypar\bxjs@everypar}
1250
1251 \RequirePackage{everyhook}
1252 \end{warpHTML}

```

for HTML & PRINT: 1253 \begin{warpall}

Pkg filecontents

Used to write helper files while creating the print version.

Recent versions of L^AT_EX (as of Fall 2019) now include the functionality of the `filecontents` package, but with a new optional argument used to specify whether to force the overwriting of an existing file. If an older L^AT_EX kernel is used, the original `filecontents` package is used, but it is patched to throw away the new optional argument.

```

1254 \@ifundefined{filec@ntents@opt}{% older kernel, discard optional args
1255
1256     \RequirePackage{filecontents}
1257
1258     \LetLtxMacro\LWR@orig@filec@ntents\filec@ntents
1259
1260     \@ifpackagelater{filecontents}{2011/10/08}
1261     {

```

For a newer version of the `filecontents` package, simply discard the optional argument.

```

1262         \renewcommand*{\filec@ntents}[1][\LWR@orig@filec@ntents]
1263     }
1264     {% patch older package for morewrites

```

For an older version of `filecontents`, discard the optional argument, and also patch to work with `morewrites`, per <https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910>

```

1265         \newwrite\fcwrite
1266         \renewcommand*{\filec@ntents}[1][\LWR@orig@filec@ntents]{%
1267             \def\chardef##1\write{\let\reserved@c\fcwrite}%
1268             \LWR@orig@filec@ntents%
1269         }
1270     }
1271
1272 }% older kernel
1273 {% newer kernel

```

For a newer kernel with a `filecontents` environment which accepts the optional `overwrite` argument, use the environment as-is.

```

1274 }% newer kernel, filecontents env accepts optional args, do not load package
1275 \end{warpall}

```

for HTML output: 1276 \begin{warpHTML}

Pkg xifthen

1277 \RequirePackage{xifthen}

Pkg verbatim

1278 \RequirePackage{verbatim}

Pkg refcount

Provides \setcounterref, \setcounterpageref, etc.

1279 \RequirePackage{refcount}

Pkg newfloat

1280 \RequirePackage{newfloat}

1281 \end{warpHTML}

for HTML & PRINT: 1282 \begin{warpall}

Pkg xstring There was a short-term bug in xstring regarding \IfInteger which affected lwarp's index generation. The updated version is requested here.



index

1283 \RequirePackage{xstring}[2019/02/01]

Pkg environ Used to encapsulate math environments for re-use in HTML <alt> text.

1284 \RequirePackage{environ}

1285 \end{warpall}

for HTML output: 1286 \begin{warpHTML}

Pkg printlen Used to convert lengths for image width/height options.

1287 \RequirePackage{printlen}

\LWR@printlength $\{\langle length \rangle\}$

Prints a length using a locally-controlled unit and space. Rounding is used unless the length is small.

1288 \newrobustcmd*\LWR@printlength[1]{%

1289 \begingroup%

1290 \uselengthunit{PT}%

1291 \renewcommand*\unitspace}{}%

1292 \ifdimless{#1}{10pt}{%

```

1293     \printlength{#1}%
1294   }{%
1295     \rndprintlength{#1}%
1296   }%
1297   \endgroup%
1298 }

1299 \end{warpHTML}

```

for PRINT output: 1300 \begin{warpprint}

Pkg varwidth Used for print-mode lateximage.

```

1301 \RequirePackage{varwidth}

1302 \end{warpprint}

```

30 Loading packages

for HTML & PRINT: 1303 \begin{warppall}

Remember the original \RequirePackage:

```

1304 \LetLtxMacro\LWR@origRequirePackage\RequirePackage
1305 \LetLtxMacro\LWR@origRequirePackageWithOptions\RequirePackageWithOptions

```

\LWR@requirepackagenames Stores the list of required package names.

```
1306 \newcommand*\LWR@requirepackagenames{}
```

\LWR@parsedrequirepackagenames Stores the parsed list of required package names after spaces are removed and lwarp- is prepended.

```
1307 \newcommand*\LWR@parsedrequirepackagenames{}
```

\LWR@nullifycomment Remove the preexisting comment environment. Certain packages define it for their own use.

```

1308 \newcommand*\LWR@nullifycomment{%
1309   \PackageInfo{lwarp}%
1310     {Nullifying the comment environment before loading \LWR@strresulttwo,}%
1311   \let\comment\relax%
1312   \let\endcomment\relax%
1313 }

```

\LWR@findword [*1: separator*] [*2: list*] [*3: index*] [*4: destination*]

Note that argument 4 is passed directly to \StrBetween.

```

1314 \newcommand*\LWR@findword[3][,]{%
1315   \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}{#1}%
1316 }

```

`\LWR@checkloadfilename` $\{ \langle filename \rangle \}$ Checks if this filename should be loaded after `lwarp`, or never at all.

The following should never be loaded:

```

1317 \newcommand*\LWR@checkloadfilename[1]{%
1318 \LWR@checkloadnever{#1}{ae}{cm-super, lmodern}
1319 \LWR@checkloadnever{#1}{aecc}{cm-super, lmodern}
1320 \LWR@checkloadnever{#1}{aecompl}{cm-super, lmodern}
1321 \LWR@checkloadnever{#1}{alg}{algorithm2e, algorithmicx}
1322 \LWR@checkloadnever{#1}{algorithmic}{algorithm2e, algorithmicx}
1323 \LWR@checkloadnever{#1}{bitfield}{bytefield}
1324 \LWR@checkloadnever{#1}{caption2}{caption}
1325 \LWR@checkloadnever{#1}{ccaption}{caption}% might be preloaded by memoir
1326 \LWR@checkloadnever{#1}{colortab}{colortbl}
1327 \LWR@checkloadnever{#1}{csvtools}{datatool}
1328 \LWR@checkloadnever{#1}{doublespace}{setspace}
1329 \LWR@checkloadnever{#1}{epsf}{graphicx}
1330 \LWR@checkloadnever{#1}{fancyheadings}{fancyhdr}
1331 \LWR@checkloadnever{#1}{fncylab}{cleveref}
1332 \LWR@checkloadnever{#1}{formula}{siunitx}
1333 \LWR@checkloadnever{#1}{glossary}{glossaries}
1334 \LWR@checkloadnever{#1}{hyper}{hyperref}
1335 \LWR@checkloadnever{#1}{libgreek}{libertinust1math, newtx}
1336 \LWR@checkloadnever{#1}{newthm}{ntheorem}
1337 \LWR@checkloadnever{#1}{pdfcprot}{microtype}
1338 \LWR@checkloadnever{#1}{picins}{floatflt, wrapfig}
1339 \LWR@checkloadnever{#1}{rplain}{fancyhdr}
1340 \LWR@checkloadnever{#1}{si}{siunitx}
1341 \LWR@checkloadnever{#1}{sistyle}{siunitx}
1342 \LWR@checkloadnever{#1}{slashbox}{diagbox}
1343 \LWR@checkloadnever{#1}{statex}{statex2}
1344 \LWR@checkloadnever{#1}{tlenc}{fontenc, inputenc, inputenx}
1345 \LWR@checkloadnever{#1}{ucs}{inputenc, inputencx}
1346 \LWR@checkloadnever{#1}{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
1347 \LWR@checkloadnever{#1}{bxcjkjatyp}{upLaTeX, bxjarticle, uarticle, utarticle}
1348 \LWR@checkloadnever{#1}{hangul}{kotex, xetexko, luatexko}

```

The following should only be loaded before `lwarp`:

```

1349 \LWR@checkloadbefore{#1}{ctex}
1350 \LWR@checkloadbefore{#1}{fontspec}
1351 \LWR@checkloadbefore{#1}{inputenc}
1352 \LWR@checkloadbefore{#1}{inputenx}
1353 \LWR@checkloadbefore{#1}{nfssect-cfr}
1354 \LWR@checkloadbefore{#1}{fontaxes}
1355 \LWR@checkloadbefore{#1}{kotex}
1356 \LWR@checkloadbefore{#1}{luatexja}
1357 \LWR@checkloadbefore{#1}{luatexja-fontspec}
1358 \LWR@checkloadbefore{#1}{luatexko}
1359 \LWR@checkloadbefore{#1}{morewrites}

```

```

1360 \LWR@checkloadbefore{#1}{newclude}
1361 \LWR@checkloadbefore{#1}{newunicodechar}
1362 \LWR@checkloadbefore{#1}{plex}
1363 \LWR@checkloadbefore{#1}{xeCJK}
1364 \LWR@checkloadbefore{#1}{xetexko}
1365 \LWR@checkloadbefore{#1}{zsjatype}
1366 }

```

`\LWR@lookforpackagename` {<*index*>}

If HTML, and if this is an lwarp-supported package name, re-direct it to the lwarp version by renaming it lwarp- followed by the original name.

Looks index deep into the list of package names, `\LWR@requirepackagenames`, and builds `\LWR@parsedrequirepackagenames` which is the modified list of names.

```
1367 \newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the index'th package name from the list:

```
1368 \LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in `LWR@strresult` and the final name with no blanks goes into `LWR@strresulttwo`.

```
1369 \StrSubstitute[100]{\LWR@strresult}{ }{ }\LWR@strresulttwo}%
```

See if the package name was found:

```

1370 \IfStrEq{\LWR@strresulttwo}{}%
1371 {}% no filename
1372 {% yes filename was found

```

Possible adjustments before loading the package. Maybe nullify the comment environment if the new package will be redefining it for a new purpose.

```

1373 \ifdefstring{\LWR@strresulttwo}{easyReview}{\LWR@nullifycomment}{}%
1374 \ifdefstring{\LWR@strresulttwo}{changes}{\LWR@nullifycomment}{}%

```

If HTML, check if the package should be loaded before lwarp, or never at all:

```
1375 \ifbool{warpingHTML}{\LWR@checkloadfilename{\LWR@strresulttwo}}{%
```

If HTML, and if found, and if an lwarp-equivalent name exists, use lwarp-* instead.

```

1376 \ifbool{expr}{
1377   bool{warpingHTML} and
1378   test{\IfFileExists{lwarp-\LWR@strresulttwo.sty}}
1379 }%
1380 {% lwarp-* file found
1381   \ifdefvoid{\LWR@parsedrequirepackagenames}{%
1382     \edef\LWR@parsedrequirepackagenames{lwarp-\LWR@strresulttwo}%
1383   }%

```

```

1384         \edef\LWR@parsedrequirepackagenames{%
1385             \LWR@parsedrequirepackagenames,lwarp-\LWR@strresulttwo%
1386         }%
1387     }%
1388 }%
1389 {%

```

Otherwise, use the current package name.

```

1390     \ifdefvoid{\LWR@parsedrequirepackagenames}{%
1391         \edef\LWR@parsedrequirepackagenames{\LWR@strresulttwo}%
1392     }{%
1393         \edef\LWR@parsedrequirepackagenames{%
1394             \LWR@parsedrequirepackagenames,\LWR@strresulttwo%
1395         }%
1396     }%
1397 }% no lwarp-* file
1398 }% yes filename
1399 }

```

`\RequirePackage` [*<1: options>*] [*<2: package names>*] [*<3: version>*]

For each of many package names in a comma-separated list, if an lwarp version of a package exists, select it instead of the L^AT_EX version.

```
1400 \RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to twenty names:¹⁷

```

1401 \renewcommand*{\LWR@requirepackagenames}{#2}%
1402 \renewcommand*{\LWR@parsedrequirepackagenames}{}%
1403 \LWR@lookforpackagename{1}%
1404 \LWR@lookforpackagename{2}%
1405 \LWR@lookforpackagename{3}%
1406 \LWR@lookforpackagename{4}%
1407 \LWR@lookforpackagename{5}%
1408 \LWR@lookforpackagename{6}%
1409 \LWR@lookforpackagename{7}%
1410 \LWR@lookforpackagename{8}%
1411 \LWR@lookforpackagename{9}%
1412 \LWR@lookforpackagename{10}%
1413 \LWR@lookforpackagename{11}%
1414 \LWR@lookforpackagename{12}%
1415 \LWR@lookforpackagename{13}%
1416 \LWR@lookforpackagename{14}%
1417 \LWR@lookforpackagename{15}%
1418 \LWR@lookforpackagename{16}%
1419 \LWR@lookforpackagename{17}%
1420 \LWR@lookforpackagename{18}%
1421 \LWR@lookforpackagename{19}%
1422 \LWR@lookforpackagename{20}%

```

¹⁷This was originally nine names, but then I came across a package which used twelve...

\RequirePackage depending on the options and version:

```

1423 \IfValueTF{#1}%
1424 {% options given
1425     \IfValueTF{#3}% version given?
1426         {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}[#3]}%
1427         {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}}%
1428 }%
1429 {% no options given
1430     \IfValueTF{#3}% version given?
1431         {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}[#3]}%
1432         {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}}%
1433 }%
1434 }
1435 \LetLtxMacro\usepackage\RequirePackage
1436 \@onlypreamble\RequirePackage
1437 \@onlypreamble\usepackage

1438 \end{warpall}

```

for HTML output: 1439 \begin{warpHTML}

\LWR@ProvidesPackagePass {*{pkgname}*} [*{version}*]

Uses the original package, including options.

```

1440 \NewDocumentCommand{\LWR@ProvidesPackagePass}{m o}{
1441     \PackageInfo{lwarp}{%
1442         Using package ‘#1’,\MessageBreak
1443         and adding lwarp modifications, including options,\MessageBreak%
1444     }%
1445     \IfValueTF{#2}%
1446         {\ProvidesPackage{lwarp-#1}[#2]}%
1447         {\ProvidesPackage{lwarp-#1}}%
1448     \DeclareOption*{%
1449         \PassOptionsToPackage{\CurrentOption}{#1}%
1450     }%
1451     \ProcessOptions\relax%

```

If using `catoptions`, an error occurs if a package is loaded with an option then loaded again with no options. `lwarp` does this if a package is preloaded then later patched. To avoid an error while using `catoptions`, if a package has already been loaded, it is loaded again with its original options.

```

1452     \@ifpackageloaded{#1}{%
1453         \edef\LWR@tempone{\csuse{opt@#1.sty}}%
1454         \IfValueTF{#2}%
1455             {%
1456                 \expandafter\LWR@origRequirePackage%
1457                 \expandafter[\LWR@tempone]{#1}[#2]%
1458             }%
1459             {%
1460                 \expandafter\LWR@origRequirePackage%
1461                 \expandafter[\LWR@tempone]{#1}%

```

```

1462         }%
1463     }{%
1464         \IfValueTF{#2}%
1465         {\LWR@origRequirePackage{#1}[#2]}%
1466         {\LWR@origRequirePackage{#1}}%
1467     }%

```

In some cases, the following seems to be required to avoid an “unknown option” error, such as when loading xcolor with options.

```

1468     \DeclareOption*{%
1469     \ProcessOptions\relax%
1470 }

```

`\LWR@ProvidesPackageDropA` `{<name>} {<date or -NoValue->}`

Declares the package. Factored for reuse.

```

1471 \newcommand*\LWR@ProvidesPackageDropA[2]{%
1472     \PackageInfo{lwarp}{%
1473         Replacing package ‘#1’ with the lwarp version,\MessageBreak
1474         and discarding options,%
1475     }%
1476     \IfValueTF{#2}
1477     {\ProvidesPackage{lwarp-#1}[#2]}
1478     {\ProvidesPackage{lwarp-#1}}
1479 }

```

`\LWR@ProvidesPackageDropB` Nullifies then processes the options.

Seems to be required when options contain curly braces, which were causing “Missing \begin{document}”.

```

1480 \newcommand*\LWR@ProvidesPackageDropB{%
1481 % \ProcessOptions\relax% original LaTeX code
1482 \let\ds@\empty%         from the original \ProcessOptions
1483 \edef\@curroptions{}%   lwarp modification to \ProcessOptions
1484 \@processoptions\relax% from the original \ProcessOptions
1485 }

```

`\LWR@ProvidesPackageDrop` `{<pkgname>} [<version>]`

Ignores the original package and uses lwarp’s version instead. Drops/discards all options.

```

1486 \NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o}{

```

Declare the package:

```

1487 \LWR@ProvidesPackageDropA{#1}{#2}

```

Ignore all options:

```
1488 \DeclareOption*{}
```

Process the options:

```
1489 \LWR@ProvidesPackageDropB
1490 }
```

```
1491 \end{warpHTML}
```

31 File handles

Defines file handles for writes.

for HTML & PRINT: 1492 \begin{warpall}

\LWR@quickfile For quick temporary use only. This is reused in several places.

```
1493 \newwrite\LWR@quickfile%
```

```
1494 \end{warpall}
```

for HTML output: 1495 \begin{warpHTML}

\LWR@lateximagesfile For <project>-images.txt:

```
1496 \newwrite\LWR@lateximagesfile
```

```
1497 \end{warpHTML}
```

32 Include a file

During HTML output, `\include{<filename>}` causes the following to occur:

1. lwarp creates `<filename>_html_inc.tex` whose contents are:


```
\input <filename>.tex
```
2. `<filename>_html_inc.tex` is then `\included` instead of `<filename>.tex`.
3. `<filename>_html_inc.aux` is automatically generated and used by L^AT_EX.

for HTML output: 1498 \begin{warpHTML}

`\@include` `{\filename}` Modified to load `_html_inc` files.

(Below, `\clearpage` caused missing text, and was changed to `\newpage`.)

```

1499 \def\@include#1 {%
1500 \immediate\openout\LWR@quickfile #1_html_inc.tex% lwarp
1501 \immediate\write\LWR@quickfile{\string\input{#1.tex}}% lwarp
1502 \immediate\closeout\LWR@quickfile% lwarp
1503 \LWR@maybe@orignewpage% changed from clearpage
1504 \if@filesw
1505   \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
1506 \fi
1507 \@tempswatruw
1508 \if@partsw
1509   \@tempswafalse
1510   \edef\reserved@b{#1}%
1511   \@for\reserved@a:=\@partlist\do
1512     {\ifx\reserved@a\reserved@b\@tempswatruw\fi}%
1513 \fi
1514 \if@tempswa
1515   \let\@auxout\@partaux
1516   \if@filesw
1517     \immediate\openout\@partaux #1_html_inc.aux % changed
1518     \immediate\write\@partaux{\relax}%
1519   \fi
1520   \@input{#1_html_inc.tex}% changed
1521   \LWR@maybe@orignewpage% changed from clearpage
1522   \writeckpt{#1}%
1523   \if@filesw
1524     \immediate\closeout\@partaux
1525   \fi
1526 \else
1527   \deadcycles\z@
1528   \@nameuse{cp@#1}%
1529 \fi
1530 \let\@auxout\@mainaux%
1531 }

1532 \end{warpHTML}

```

33 Copying a file

for HTML output: `1533 \begin{warpHTML}`

`\LWR@copyfile` `{\source filename}` `{\destination filename}`

Used to copy the `.toc` file to `.sidetoc` to re-print the TOC in the sideroc navigation pane.

```

1534 \newwrite\LWR@copyoutfile % open the file to write to
1535 \newread\LWR@copyinfile % open the file to read from
1536

```

```

1537 \newcommand*{\LWR@copyfile}[2]{%
1538   \LWR@traceinfo{\LWR@copyfile: copying #1 to #2}
1539
1540   \immediate\openout\LWR@copyoutfile=#2
1541   \openin\LWR@copyinfile=#1
1542   \begingroup\endlinechar=-1
1543   \makeatletter
1544
1545   \LWR@traceinfo{\LWR@copyfile: about to loop}
1546
1547   \loop\unless\ifeof\LWR@copyinfile
1548     \LWR@traceinfo{\LWR@copyfile: one line}
1549     \read\LWR@copyinfile to\LWR@fileline % Read one line and store it into \LWR@fileline
1550 %   \LWR@fileline\par % print the content into the pdf
1551 % print the content:
1552     \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
1553     \repeat
1554   \immediate\closeout\LWR@copyoutfile
1555   \LWR@traceinfo{\LWR@copyfile: done}
1556   \endgroup
1557 }

1558 \end{warpHTML}

```

34 Debugging messages

HTML comments To have the HTML output include additional HTML comments, such as which `<div>` is closing, use

```
\booltrue{HTMLDebugComments}
```

debugging information To have debug information written to the log, use

```
\tracinglwarp
```

for HTML & PRINT: 1559 \begin{warpall}

Bool `LWR@tracinglwarp` True if tracing is turned on.

```
1560 \newbool{LWR@tracinglwarp}
```

`\tracinglwarp` Turns on the debug tracing messages.

```
1561 \newcommand{\tracinglwarp}{\booltrue{LWR@tracinglwarp}}
```

`\LWR@traceinfo` `{\langle text \rangle}` If tracing is turned on, writes the text to the `.log` file.

```

1562 \newcommand{\LWR@traceinfo}[1]{%
1563   \ifbool{LWR@tracinglwarp}%
1564   {%
1565     \typeout{*** lwarp: #1}%

```

```
1566 }%
1567 {}%
1568 }
```

Bool HTMLDebugComments Add comments in HTML about closing <div>s, sections, etc.
Default: false

```
1569 \newbool{HTMLDebugComments}
1570 \boolfalse{HTMLDebugComments}
```

If `\tracinglwarp`, show where preamble hooks occur:

```
1571 \AfterEndPreamble{
1572 \LWR@traceinfo{AfterEndPreamble}
1573 }
1574
1575 \AtBeginDocument{
1576 \LWR@traceinfo{AtBeginDocument}
1577 }

1578 \end{warpall}
```

35 Defining print and HTML versions of macros and environments

The following refers to defining objects inside `lwarp`, and is not for the user's document.

Many macros and environments must be provided as both print and HTML versions.

While generating the print version of a document, the original macros as defined by `LATEX` and its packages are used as-is.

While generating the HTML version of a document, the original macro or environment is redefined to call a new HTML version or a copy of the original print version. The new HTML versions of macros and environments are used most of the time. Copies of the print versions are used inside a `lateximage` environment, which draws and remembers an image of the printed output, and also several other places.

The general structure for providing print and HTML versions of a macro or environment is as follows:

For a preexisting macro, not defined with `xparse`: An HTML version is provided with a special name, inside a `warpHTML` environment, then `\LWR@formatted` is used to redefine and patch various macros:

```

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may also use xparse

\LWR@formatted{name}
\end{warpHTML}

```

`\LWR@formatted{name}` copies the original print version, then redefines `\name` to use either the print or HTML version depending on which mode `lwarp` is using. `xparse` may be used to define the new HTML version, even if the original did not use `xparse`. `expl3` syntax may be used as well.

For a preexisting environment, not defined with `xparse`: The process is similar. Note the use of `\LWR@formattedenv` instead of `\LWR@formatted`.

```

\begin{warpHTML}
\newenvironment{\LWR@HTML@name}{...}% may also use xparse

\LWR@formattedenv{name}
\end{warpHTML}

```

If the original used `xparse`: A copy must be made using a new name:

```

\begin{warpHTML}
\NewDocumentCommand{\LWR@print@name}{..}{..}% copy the original

\NewDocumentCommand{\LWR@HTML@name}{..}{..}% or use \newcommand

\LWR@formatted{name}
\end{warpHTML}

```

Similar for an environment, using `\LWR@formattedenv`. (`\LWR@formatted` and `\LWR@formattedenv` use `\LetLtxMacro` to copy the original print definition, which may not work with macros and environments created by `xparse`, so the print version must be manually recreated in the `lwarp` source.)

For a new macro or environment, not using `xparse` for the print version:

```

\begin{warpaLL}
\newcommand{\name}{...}% NOT xparse!
\end{warpaLL}

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may use xparse for HTML

\LWR@formatted{name}
\end{warpHTML}

```

Similar for an environment. The plain `\name` or environment name is used for the printed version, and is placed inside `warpaLL`. `xparse` may be used for the `\LWR@HTML@<name>` version. `expl3` syntax may be used for the print and HTML versions.

For a new macro or environment, using `xparse`: It is possible to use `xparse` for an entirely new macro or environment by defining the `\LWR@print@<name>` version with `xparse`, along with `\name` defined without `xparse` to refer directly to the `\LWR@print` version:

```
\begin{warpall}
\NewDocumentCommand{\LWR@print@name}{...} {...}% -or-
\NewDocumentEnvironment{\LWR@print@name}{...} {...} {...}

% Simply a call to \LWR@print@name:
\newcommand{\name}{\LWR@print@name}% -or-
\newenvironment{name}{\LWR@print@name}{\endLWR@print@name}
\end{warpall}

\begin{warpHTML}
\NewDocumentCommand{\LWR@HTML@name}{...} {...}% -or-
\NewDocumentEnvironment{\LWR@HTML@name}{...} {...} {...}

\LWR@formatted{name}% -or-
\LWR@formattedenv{name}
\end{warpHTML}
```

In general, `\LWR@formatted` or `\LWR@formattedenv` are placed inside a `warpHTML` environment, and while producing an HTML document they do the following:

- Macros are modified:
 1. The pre-existing print version `\name` is saved as `\LWR@print@<name>`, unless `\LWR@print@<name>` is already defined.
 2. The original `\name` is redefined to call either the print or HTML version depending on which format is in use at the moment, as set by `\LWR@formatting`, which is defined as either “print” or “HTML”.
- When `lwarp` is producing a print document, the original definitions are used, as well as any new definitions defined in `warpall` above.
- When `lwarp` is generating HTML output, `\LWR@formatting` is set to “HTML”, and `\name` is directed to `\LWR@HTML@<name>`.
- When `lwarp` is generating HTML output but enters a `lateximage` environment, or for some other reason needs to draw images using the original print definitions, `\LWR@formatting` is changed to “print” and `\name` is then redirected to `\LWR@print@<name>`, which was the original `\name`.

Since arguments are not handled by the new `\name`, any star and other arguments are processed by the print or HTML version.

Expandable versions are also provided as well. These usually are necessary for anything which could appear inside a `tabular`, without which a “Misplaced `\omit`” error may occur.

```
\LWR@expandableformatted
\LWR@expandableformattedenv
```



Misplaced `\omit` error

(Older versions of `lwarp` used `\LetLtxMacro` for everything, but this could fail when using macros defined by `xparse`. This older system is still in use for many definitions.)

for HTML output: 1579 `\begin{warpHTML}`

`\LWR@formatting` Remembers if selected print/HTML formatting.

Used while `\LWR@restoreorigformatting`, such as in an `lateximage`. May be set to either “print” or “HTML”.

```
1580 \newcommand*{\LWR@formatting}{HTML}
```

`\LWR@formatted@checkname` $\langle name \rangle$

```
1581 \newcommand*{\LWR@formatted@checkname}[1]{%
1582   \ifcsundef{LWR@HTML@#1}{%
1583     \PackageError{lwarp}
1584     {%
1585       \protect\LWR@HTML@#1 is not defined%
1586     }
1587     {Perhaps it is misspelled.}
1588   }\relax}%
1589 }
```

`\LWR@formatted@checkendname` $\langle name \rangle$

```
1590 \newcommand*{\LWR@formatted@checkendname}[1]{%
1591   \ifcsundef{endLWR@HTML@#1}{%
1592     \PackageError{lwarp}
1593     {%
1594       \protect\endLWR@HTML@#1 is not defined%
1595     }
1596     {Perhaps it is misspelled.}
1597   }\relax}%
1598 }
```

`\LWR@formatted` $\langle macroname \rangle$ No backslash in the macro name.

If not yet defined, defines `\LWR@print@<name>` as the original print-mode `\<name>`. Also redefines `\<name>` to use `\LWR@<format>@<name>`, where `<format>` is set by `\LWR@formatting`, and is print or HTML.

```
1599 \newcommand*{\LWR@formatted}[1]{%
1600   \LWR@formatted@checkname{#1}%
1601   \ifcsundef{LWR@print@#1}{%
1602     \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
1603     \csname#1\endcsname%
1604   }{%
1605     \ifcsundef{#1}{%
1606       \expandafter\newrobustcmd\csname #1\endcsname{%
1607         \@nameuse{LWR@\LWR@formatting @#1}%
1608       }%

```

```

1609   }{%
1610     \expandafter\renewrobustcmd\csname #1\endcsname{%
1611       \@nameuse{LWR@LWR@formatting @#1}%
1612     }%
1613   }%
1614 }

```

`\LWR@expandableformatted` $\{\langle\textit{macroname}\rangle\}$ No backslash in the macro name.

An expandable version of `\LWR@formatted`.

```

1615 \newcommand*{\LWR@expandableformatted}[1]{%
1616   \LWR@formatted@checkname{#1}%
1617   \ifcsundef{LWR@print@#1}{%
1618     \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
1619     \csname#1\endcsname%
1620   }{%
1621   \ifcsundef{#1}{%
1622     \expandafter\newcommand\csname #1\endcsname{%
1623       \@nameuse{LWR@LWR@formatting @#1}%
1624     }%
1625   }{%
1626     \expandafter\renewcommand\csname #1\endcsname{%
1627       \@nameuse{LWR@LWR@formatting @#1}%
1628     }%
1629   }%
1630 }

```

`\LWR@formattedenv` $\{\langle\textit{environmentname}\rangle\}$

If not yet defined, defines the environment `LWR@print@<name>` as the original print-mode `<name>`. Also redefines the environment `<name>` to use environment `LWR@<format>@<name>`, where `<format>` is set by `\LWR@formatting`, and is `print` or `HTML`.

```

1631 \newcommand*{\LWR@formattedenv}[1]{%
1632   \LWR@formatted@checkname{#1}%
1633   \LWR@formatted@checkendname{#1}%
1634   \ifcsundef{LWR@print@#1}{%
1635     \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
1636     \csname#1\endcsname%
1637     \csletcs{endLWR@print@#1}{end#1}%
1638   }{%
1639   \DeclareDocumentEnvironment{#1}{%
1640     {%
1641       \@nameuse{LWR@LWR@formatting @#1}%
1642     }%
1643     {%
1644       \@nameuse{endLWR@LWR@formatting @#1}%
1645     }%
1646 }

```

`\LWR@expandableformattedenv` $\{\langle\textit{environmentname}\rangle\}$

An expandable version of LWR@formattedenv.

```

1647 \newcommand*{\LWR@expandableformattedenv}[1]{%
1648   \LWR@formatted@checkname{#1}%
1649   \LWR@formatted@checkendname{#1}%
1650   \ifcsundef\LWR@print@#1{%
1651     \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
1652     \csname#1\endcsname%
1653     \csletcs{endLWR@print@#1}{end#1}%
1654   }{%
1655   \DeclareExpandableDocumentEnvironment{#1}{%
1656   {%
1657     \@nameuse{LWR@\LWR@formatting @#1}%
1658   }%
1659   {%
1660     \@nameuse{endLWR@\LWR@formatting @#1}%
1661   }%
1662 }

1663 \end{warpHTML}

```

36 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

for HTML & PRINT: 1664 \begin{warpall}

36.1 User-level controls

Bool `FormatEPUB` Changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.
Default: `false`

```

1665 \newbool{FormatEPUB}
1666 \boolfalse{FormatEPUB}

```

Bool `FormatWP` Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.
Default: `false`

```

1667 \newbool{FormatWP}
1668 \boolfalse{FormatWP}

```

Bool `WPMarkFloats` Adds
Default: `false`

```

=== begin table ===
. . .
=== end ===

or

```

```

=== begin figure ===
. . .
=== end ===

```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.¹⁸

```

1669 \newbool{WPMarkFloats}
1670 \boolfalse{WPMarkFloats}

```

Bool WPMarkMinipages

Adds

Default: false

```

=== begin minipage ===
. . .
=== end minipage ===

```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

```

1671 \newbool{WPMarkMinipages}
1672 \boolfalse{WPMarkMinipages}

```

Bool WPMarkTOC

While formatting for word processors, adds

Default: true

```

=== table of contents ===

```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set false, the actual TOC is printed instead.

```

1673 \newbool{WPMarkTOC}
1674 \booltrue{WPMarkTOC}

```

Bool WPMarkLOFT

While formatting for word processors, adds

Default: false

```

=== list of figures === and/or
=== list of tables ===

```

where each of these lists would have been. This helps identify where to insert the actual lists.

If set false, the actual lists are printed instead.

```

1675 \newbool{WPMarkLOFT}
1676 \boolfalse{WPMarkLOFT}

```

Bool WPMarkMath

While formatting for word processors, prints math as \LaTeX code instead of creating SVG images or MATHJAX . This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

Default: false

¹⁸Perhaps some day word processors will have HTML import options for identifying `<figure>` and caption tags for figures and tables.

```
1677 \newbool{WPMarkMath}
1678 \boolfalse{WPMarkMath}
```

Bool WPTitleHeading While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LIBREOffice. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

Default: false

See table 10 on page 188.

```
1679 \newbool{WPTitleHeading}
1680 \boolfalse{WPTitleHeading}
```

```
1681 \end{warpall}
```

36.2 Heading adjustments

If formatting the HTML for a word processor, adjust heading levels.

If WPTitleHeading is true, adjust so that part is **Heading 1**.

If WPTitleHeading is false, use <h1> for the title, and set part to **Heading 2**.

for HTML output: 1682 \begin{warpHTML}

```
1683 \AtBeginDocument{
1684 \ifbool{FormatWP}{
1685 \@ifundefined{chapter}{
1686 \ifbool{WPTitleHeading}{% part and section starting at h2
1687 \renewcommand*\LWR@tagtitle}{h1}
1688 \renewcommand*\LWR@tagtitleend}{/h1}
1689 \renewcommand*\LWR@tagpart}{h2}
1690 \renewcommand*\LWR@tagpartend}{/h2}
1691 \renewcommand*\LWR@tagsection}{h3}
1692 \renewcommand*\LWR@tagsectionend}{/h3}
1693 \renewcommand*\LWR@tagsubsection}{h4}
1694 \renewcommand*\LWR@tagsubsectionend}{/h4}
1695 \renewcommand*\LWR@tagsubsubsection}{h5}
1696 \renewcommand*\LWR@tagsubsubsectionend}{/h5}
1697 \renewcommand*\LWR@tagparagraph}{h6}
1698 \renewcommand*\LWR@tagparagraphend}{/h6}
1699 \renewcommand*\LWR@tagsubparagraph}{span class="subparagraph"}
1700 \renewcommand*\LWR@tagsubparagraphend}{/span}
1701 }% WPTitleHeading
1702 {% not WPTitleHeading, part and section starting at h1
1703 \renewcommand*\LWR@tagtitle}{div class="title"}
1704 \renewcommand*\LWR@tagtitleend}{/div}
1705 \renewcommand*\LWR@tagpart}{h1}
1706 \renewcommand*\LWR@tagpartend}{/h1}
1707 \renewcommand*\LWR@tagsection}{h2}
1708 \renewcommand*\LWR@tagsectionend}{/h2}
1709 \renewcommand*\LWR@tagsubsection}{h3}
1710 \renewcommand*\LWR@tagsubsectionend}{/h3}
```

```

1711 \renewcommand*\LWR@tagssubsubsection}{h4}
1712 \renewcommand*\LWR@tagssubsubsectionend}{/h4}
1713 \renewcommand*\LWR@tagparagraph}{h5}
1714 \renewcommand*\LWR@tagparagraphend}{/h5}
1715 \renewcommand*\LWR@tagsubparagraph}{h6}
1716 \renewcommand*\LWR@tagsubparagraphend}{/h6}
1717 }% not WPTitleHeading
1718 }% chapter undefined
1719 {% chapter defined
1720 \ifbool{WPTitleHeading}{
1721 {% not WPTitleHeading, part and chapter starting at h1
1722 \renewcommand*\LWR@tagtitle}{div class="title"}
1723 \renewcommand*\LWR@tagtitleend}{/div}
1724 \renewcommand*\LWR@tagpart}{h1}
1725 \renewcommand*\LWR@tagpartend}{/h1}
1726 \renewcommand*\LWR@tagchapter}{h2}
1727 \renewcommand*\LWR@tagchapterend}{/h2}
1728 \renewcommand*\LWR@tagsection}{h3}
1729 \renewcommand*\LWR@tagsectionend}{/h3}
1730 \renewcommand*\LWR@tagsubsection}{h4}
1731 \renewcommand*\LWR@tagsubsectionend}{/h4}
1732 \renewcommand*\LWR@tagssubsubsection}{h5}
1733 \renewcommand*\LWR@tagssubsubsectionend}{/h5}
1734 \renewcommand*\LWR@tagparagraph}{h6}
1735 \renewcommand*\LWR@tagparagraphend}{/h6}
1736 \renewcommand*\LWR@tagsubparagraph}{span class="subparagraph"}
1737 \renewcommand*\LWR@tagsubparagraphend}{/span}
1738 }% not WPTitleHeading
1739 }% chapter defined
1740 }{}% FormatWP
1741 }% AtBeginDocument

1742 \end{warpHTML}

```

37 Remembering original formatting macros

for HTML output: 1743 \begin{warpHTML}

Remember original definitions of formatting commands. Will be changed to HTML commands for most uses. Will be temporarily restored to original meaning inside any lateximage environment. Also nullify unused commands.

Some packages redefine \#, which is used to generate HTML, so the original must be remembered here.

```

1744 \chardef\LWR@origpound='\#

1745 \let\LWR@origcomma\,
1746 \let\LWR@origthinspace\thinspace
1747 \let\LWR@orignegthinspace\negthinspace
1748 \let\LWR@origtilde~
1749 \let\LWR@origenskip\enskip

```

```
1750 \let\LWR@origquad\quad
1751 \let\LWR@origqquad\qquad
1752 \let\LWR@origfil\hfil
1753 \let\LWR@orighss\hss
1754 \let\LWR@origllap\llap
1755 \let\LWR@origrlap\rlap
1756 \let\LWR@origfilneg\hfilneg
1757 \let\LWR@origspace\hspace
1758
1759 \let\LWR@origrule\rule
1760
1761 \let\LWR@origmedskip\medskip
1762 \let\LWR@origbigskip\bigskip
1763
1764 \let\LWR@origtextellipsis\textellipsis

1765 \let\LWR@origvdots\vdots

1766 \let\LWR@orig@textquotedbl\textquotedbl
1767
1768 \LetLtxMacro\LWR@origttfamily\ttfamily
1769
1770 \LetLtxMacro\LWR@origem\em
1771
1772 \LetLtxMacro\LWR@orignormalfont\normalfont
1773
1774 \let\LWR@origonecolumn\onecolumn
1775
1776 \let\LWR@origsp\sp
1777 \let\LWR@origsb\sbs
1778
1779 \LetLtxMacro\LWR@origunderline\underline

1780 \let\LWR@orignewpage\newpage
1781
1782 \let\LWR@origpagestyle\pagestyle
1783 \let\LWR@origthispagestyle\thispagestyle
1784 \LetLtxMacro\LWR@origpagenumbering\pagenumbering
1785
1786 \let\LWR@orignewline\newline
1787
1788 \AtBeginDocument{% in case packages change definition
1789 \let\LWR@orig@trivlist@trivlist
1790 \let\LWR@origtrivlist\trivlist
1791 \let\LWR@origendtrivlist\endtrivlist
1792 \LetLtxMacro\LWR@origitem\item
1793 \LetLtxMacro\LWR@origitemize\itemize
1794 \LetLtxMacro\LWR@endorigitemize\enditemize
1795 \LetLtxMacro\LWR@origenumerate\enumerate
1796 \LetLtxMacro\LWR@endorigenumerate\endenumerate
1797 \LetLtxMacro\LWR@origdescription\description
1798 \LetLtxMacro\LWR@endorigdescription\enddescription
1799 \let\LWR@orig@mklab@mklab
1800 \let\LWR@origmake\make
1801 \let\LWR@orig@donoparitem\@donoparitem
```

```

1802 \LetLtxMacro\LWR@orig@item\@item
1803 \let\LWR@orig@nbitem\@nbitem
1804 }
1805
1806 \let\LWR@origpar\par
1807
1808 \LetLtxMacro\LWR@origfootnote\footnote
1809 \let\LWR@orig@mpfootnotetext\@mpfootnotetext
1810
1811
1812 \AtBeginDocument{% in case packages change definition
1813 \LetLtxMacro\LWR@orighline\hline%
1814 \LetLtxMacro\LWR@origcline\cline%
1815 }

1816 \end{warpHTML}

```

38 Accents

Native \LaTeX accents such as `\`` will work, but many more kinds of accents are available when using Unicode-aware $X\LaTeX$ and $\text{Lua}\LaTeX$. If using accents in section names which will become file names, it is recommended to use the \LaTeX accents such as `\`` and `\v` instead of Unicode accents. The \LaTeX accents will have the accents stripped when creating the filenames, whereas the Unicode accents will appear in the file names, which may cause issues with some operating systems.

for HTML output: 1817 \begin{warpHTML}

Without `\AtBeginDocument`, `\t` was being re-defined somewhere.

```
1818 \AtBeginDocument{
```

The following are restored for print when inside a `lateximage`.

For Unicode engines, only `\t` needs to be redefined:

```
1819 \LetLtxMacro\LWR@origtie\t
```

For $\text{pdf}\LaTeX$, additional work is required:

```

1820 \ifPDFTeX% pdflatex or dvi latex
1821 \LetLtxMacro\LWR@origgraveaccent\`
1822 \LetLtxMacro\LWR@origacuteaccent\'
1823 \LetLtxMacro\LWR@origcircumflexaccent\^
1824 \LetLtxMacro\LWR@origtildeaccent\~
1825 \LetLtxMacro\LWR@origmacronaccent\=
1826 \LetLtxMacro\LWR@origbreve\u
1827 \LetLtxMacro\LWR@origdotaccent\.
1828 \LetLtxMacro\LWR@origdiaeresisaccent\"
1829 \LetLtxMacro\LWR@origdoubleacuteaccent\H
1830 \LetLtxMacro\LWR@origcaronaccent\v

```

```

1831 \LetLtxMacro\LWR@origdotbelowaccent\d
1832 \LetLtxMacro\LWR@origcedillaaccent\c
1833 \LetLtxMacro\LWR@origmacronbelowaccent\b

```

The HTML redefinitions follow.

For pdfL^AT_EX, Unicode diacritical marks are used:

```

1834 \renewcommand*{\'}[1]{#1\HTMLUnicode{0300}}
1835 \renewcommand*{\'}[1]{#1\HTMLUnicode{0301}}
1836 \renewcommand*{\^}[1]{#1\HTMLUnicode{0302}}
1837 \renewcommand*{\~}[1]{#1\HTMLUnicode{0303}}
1838 \renewcommand*{\=}[1]{#1\HTMLUnicode{0304}}
1839 \renewcommand*{\u}[1]{#1\HTMLUnicode{0306}}
1840 \renewcommand*{\.}[1]{#1\HTMLUnicode{0307}}
1841 \renewcommand*{\"}[1]{#1\HTMLUnicode{0308}}
1842 \renewcommand*{\H}[1]{#1\HTMLUnicode{030B}}
1843 \renewcommand*{\v}[1]{#1\HTMLUnicode{030C}}
1844 \renewcommand*{\d}[1]{#1\HTMLUnicode{0323}}
1845 \renewcommand*{\c}[1]{#1\HTMLUnicode{0327}}
1846 \renewcommand*{\b}[1]{#1\HTMLUnicode{0331}}
1847 \fi

```

For all engines, a Unicode diacritical tie is used:

```

1848 \def\LWR@t#1#2{#1\HTMLUnicode{0361}#2}
1849 \renewcommand*{\t}[1]{\LWR@t#1}

```

`\LWR@restoreorigaccents` Called from `\restoreoriginalformatting` when a latex image is begun.

```

1850 \ifPDFTeX% pdflatex or dvi latex
1851 \newcommand*{\LWR@restoreorigaccents}{%
1852   \LetLtxMacro\'\LWR@origgraveaccent%
1853   \LetLtxMacro\'\LWR@origacuteaccent%
1854   \LetLtxMacro\^\LWR@origcircumflexaccent%
1855   \LetLtxMacro\~\LWR@origtildeaccent%
1856   \LetLtxMacro\=\LWR@origmacronaccent%
1857   \LetLtxMacro\u\LWR@origbreve%
1858   \LetLtxMacro\.\LWR@origdotaccent%
1859   \LetLtxMacro\\"\LWR@origdiaeresisaccent%
1860   \LetLtxMacro\H\LWR@origdoubleacuteaccent%
1861   \LetLtxMacro\v\LWR@origcaronaccent%
1862   \LetLtxMacro\t\LWR@origtie%
1863   \LetLtxMacro\d\LWR@origdotbelowaccent%
1864   \LetLtxMacro\c\LWR@origcedillaaccent%
1865   \LetLtxMacro\b\LWR@origmacronbelowaccent%
1866 }%
1867 \else% XeLaTeX, LuaLaTeX:
1868 \newcommand*{\LWR@restoreorigaccents}{%
1869   \LetLtxMacro\t\LWR@origtie%
1870 }%
1871 \fi%
1872 }% AtBeginDocument

1873 \end{warpHTML}

```

39 Configuration files

39.1 Decide whether to generate configuration files

Configuration files are only written if processing the print version of the document, and not processing a pstool image. pstool uses an additional compile for each image using the original document's preamble, which includes lwarp, so the lwarp configuration files are turned off if -pstool is part of the \jobname.

Default to no configuration files:

```
1874 \LWR@excludecomment{LWRwriteconf}{writeconf}
```

Generate configuration files if print mode and not -pstool:

```
for PRINT output: 1875 \begin{warpprint}
1876 \fullexpandarg%
1877 \IfSubStr*{\jobname}{-pstool}
1878   {
1879     \PackageInfo{lwarp}{%
1880       Jobname with -pstool is found.\MessageBreak
1881       Not generating lwarp configuration files,%
1882     }
1883   }
1884   {
1885     \PackageInfo{lwarp}{Generating lwarp configuration files,}%
1886     \LWR@includecomment{LWRwriteconf}{writeconf}
1887   }
1888 \end{warpprint}
```

39.2 <project>_html.tex

File *_html.tex Used to allow an HTML version of the document to exist alongside the print version.

```
Config file: 1889 \begin{LWRwriteconf}
1890 \immediate\openout\LWR@quickfile=\jobname_html.tex
1891 \immediate\write\LWR@quickfile{%
1892 \detokenize{\PassOptionsToPackage}%
1893 {warpHTML,BaseJobname=\jobname}{Lwarp}%
1894 }
1895 \immediate\write\LWR@quickfile{%
1896 \detokenize{\input}\string{\jobname.tex}\string }%
1897 }
1898 \immediate\closeout\LWR@quickfile
1899 \end{LWRwriteconf}
```

39.3 lwarpmk configuration files

```
Config file: 1900 \begin{LWRwriteconf}
```

`\LWR@lwarpcnfversion` The version number of the configuration file, allowing *lwarpmk* to detect an obsolete configuration file format. Incremented by one each time the configuration file format changes. (This is NOT the same as the *lwarp* version number.)

```
1901 \newcommand*\LWR@lwarpcnfversion}{2}% also in lwarpmk.lua
```

39.3.1 Helper macros

`\LWR@shellescapecmd` The LaTeX compile option for shell escape, if used.

```
1902 \ifshellescape
1903   \def\LWR@shellescapecmd{--shell-escape }
1904 \else
1905   \def\LWR@shellescapecmd{}
1906 \fi
```

`\LWR@compilecmd` `{<engine>}{<suffix>}`

Used to form the basic compilation command for a document, adding the optional shell escape.

Engine is *pdf \LaTeX* , etc. Suffix is empty or `_html`

```
1907 \newcommand*\LWR@compilecmd}[2]{%
1908   #1 \LWR@shellescapecmd \jobname#2%
1909 }
```

`\LWR@addcompilecmd` `{<cmd>}{<suffix>}`

Adds to the compilation command.

Cmd is *dvipdfmx*, etc. Suffix is empty or `_html`

```
1910 \newcommand*\LWR@addcompilecmd}[2]{%
1911   \LWRopseq
1912   #1 \jobname#2%
1913 }
```

`\LWR@unknownengine` Error message if not sure which \LaTeX engine is being used.

```
1914 \newcommand*\LWR@unknownengine){%
1915   \PackageError{l warp}{%
1916     {Unknown LaTeX engine}%
1917     {%
1918       Lwarp only knows about pdf $\text{\LaTeX}$ , dvi latex,
1919       xelatex, luatex, and upL $\text{\LaTeX}$ .%
1920     }%
1921 }
```

`\LWR@latexmkvar` `{<varname>}{<value>}`

Adds a *latexmk* variable assignment.

```
1922 \newcommand*{\LWR@latexmkvar}[2]{%
1923     -e
1924     \LWRopquote%
1925     \LWRdollar #1=q/#2/%
1926     \LWRopquote
1927 }
```

`\LWR@latexmkcmd` {*⟨latexmk options⟩*}

Sets a call to *latexmk* with the given options, possibly adding `--shell-escape`, and also adding the indexing program.

```
1928 \newcommand*{\LWR@latexmkcmd}[1]{%
1929     latexmk \space \LWR@shellescapecmd \space #1 \space
1930     -recorder \space
1931     \LWR@latexmkvar{makeindex}{\LWR@LatexmkIndexCmd}%
1932 }
```

`\LWR@latexmkdvipdfm` {*⟨dvipdfm or dvipdfmx⟩*}

Adds the options settings for *dvipdfm* or *dvipdfmx*.

```
1933 \newcommand*{\LWR@latexmkdvipdfm}[1]{%
1934     -pdfdvi \space
1935     \LWR@latexmkvar{dvipdf}{%
1936         #1
1937         \@percentchar O
1938         -o \@percentchar D
1939         \@percentchar S%
1940     }
1941 }
```

`\LWR@compileuplatex` Sets compile options for upL^AT_EX with *ujarticle* or related classes.

```
1942 \newcommand*{\LWR@compileuplatex}{
1943     \def\LWR@tempprintlatexcmd{%
1944         \LWR@compilecmd{uplatex}{ }
1945         \LWR@addcompilecmd{dvipdfmx}{ }
1946     }
1947     \def\LWR@tempHTMLlatexcmd{%
1948         \LWR@compilecmd{uplatex}{_html}
1949         \LWR@addcompilecmd{dvipdfmx}{_html}
1950     }
1951 }
```

`\LWR@PrintLatexCmd` If not set by the user, the following sets the command to use to compile the source to PDF form.
`\LWR@HTMLLatexCmd`

If using *latexmk*, a complicated string is created, eventually resulting in something such as:

For *xelatex* with `--shell-escape`:

```
[[latexmk -xelatex --shell-escape -recorder
  -e '$makeindex = q/makeindex -s lwarp.ist/' <jobname>_html]]
```

For *dvipdfmx*:

```
[[latexmk -pdfdvi -e '$dvi-pdf=q/dvipdfmx %O -o %D %S/'
  -recorder
  -e '$makeindex=q/makeindex -s lwarp.ist/' <jobname>_html]]
```

For the following, temporary values are computed, but the permanent values are only set if the originals were not assigned by the user.

```
1952 \ifbool{LWR@latexmk}{
```

For *latexmk* with *pdflatex* or *lualatex*:

```
1953   \ifpdf
```

For *latexmk* with *pdflatex*:

```
1954       \ifPDFTeX
1955         \def\LWR@latexcmd{\LWR@latexmkcmd{-pdf -dvi- -ps-}}
1956       \else
```

For *latexmk* with *lualatex*:

```
1957         \ifLuaTeX
1958           \def\LWR@latexcmd{\LWR@latexmkcmd{-lualatex}}
1959         \else
1960           \LWR@unknownengine
1961         \fi
1962       \fi
1963   \else% \ifpdf
```

For *latexmk* with *xelatex* or DVI *latex*:

```
1964       \ifXeTeX
```

For *latexmk* with *xelatex*:

```
1965         \def\LWR@latexcmd{\LWR@latexmkcmd{-xelatex}}
1966       \else% \ifXeTeX
```

For *latexmk* with DVI *latex*:

```
1967       \ifbool{LWR@dvipdfm}{
```

```

1968         \def\LWR@latexcmd{%
1969             \LWR@latexmkcmd{%
1970                 \LWR@latexmkdvipdfm{dvipdfm}%
1971             }
1972         }
1973     }{
1974         \ifbool{LWR@dvipdfmx}{
1975             \def\LWR@latexcmd{%
1976                 \LWR@latexmkcmd{%
1977                     \LWR@latexmkdvipdfm{dvipdfmx}%
1978                 }
1979             }
1980         }{
1981             \def\LWR@latexcmd{\LWR@latexmkcmd{-pdfps}}
1982         }
1983     }
1984     \fi
1985     \fi% \ifpdf

```

The final assignment if *latexmk*:

```

1986     \def\LWR@tempprintlatexcmd{\LWR@latexcmd \space \jobname}
1987     \def\LWR@tempHTMLlatexcmd{\LWR@latexcmd \space \jobname_html}
1988 }% latexmk

```

Without *latexmk*, the compiling command is simply the compiler name and the optional shell escape:

```

1989 {% not latexmk
1990     \ifpdf

```

For *pdflatex* or *lualatex*:

```

1991     \ifPDFTeX

```

For *pdflatex*:

```

1992         \def\LWR@tempprintlatexcmd{\LWR@compilecmd{pdflatex}{}}
1993         \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{pdflatex}{_html}}
1994     \else
1995         \ifLuaTeX

```

For *lualatex*:

```

1996         \def\LWR@tempprintlatexcmd{\LWR@compilecmd{lualatex}{}}
1997         \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{lualatex}{_html}}
1998     \else
1999         \LWR@unknownengine
2000     \fi
2001     \fi
2002     \else% \ifpdf

```

For DVI *latex* or *xelatex*:

```
2003      \ifXeTeX
```

For *xelatex*:

```
2004      \def\LWR@tempprintlatexcmd{\LWR@compilecmd{xelatex}{}}
2005      \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{xelatex}{_html}}
2006      \else
```

For DVI *latex*. Default to *dvips*, unless told to use *dvipdfm* or *dvipdfmx*:

```
2007      \ifbool{LWR@dvipdfm}{
```

For DVI *latex* with *dvipdfm*:

```
2008      \def\LWR@tempprintlatexcmd{%
2009      \LWR@compilecmd{latex}{}}
2010      \LWR@addcompilecmd{dvipdfm}{}}
2011      }
2012      \def\LWR@tempHTMLlatexcmd{%
2013      \LWR@compilecmd{latex}{_html}
2014      \LWR@addcompilecmd{dvipdfm}{_html}
2015      }
2016      }{
2017      \ifbool{LWR@dvipdfmx}{
```

For DVI *latex* with *dvipdfmx*:

```
2018      \def\LWR@tempprintlatexcmd{%
2019      \LWR@compilecmd{latex}{}}
2020      \LWR@addcompilecmd{dvipdfmx}{}}
2021      }
2022      \def\LWR@tempHTMLlatexcmd{%
2023      \LWR@compilecmd{latex}{_html}
2024      \LWR@addcompilecmd{dvipdfmx}{_html}
2025      }
2026      }{% dvips
```

For DVI *latex* with *dvips* and *ps2pdf*:

```
2027      \def\LWR@tempprintlatexcmd{%
2028      \LWR@compilecmd{latex}{}}
2029      \LWR@addcompilecmd{dvips}{}}
2030      \LWR@addcompilecmd{ps2pdf}{}.ps
2031      }
2032      \def\LWR@tempHTMLlatexcmd{%
2033      \LWR@compilecmd{latex}{_html}
2034      \LWR@addcompilecmd{dvips}{_html}
2035      \LWR@addcompilecmd{ps2pdf}{_html}.ps
2036      }
2037      }
2038      }
2039      \fi% \ifXeTeX
2040      \fi% \ifpdf
2041      }% latexmk
```

For `ujarticle`, `utarticle`, and related, using up^LA^TE^X and *dvipdfmx*:

```
2042 \@ifclassloaded{ujarticle}{\LWR@compileuplatex}{}
2043 \@ifclassloaded{ujbook}{\LWR@compileuplatex}{}
2044 \@ifclassloaded{ujreport}{\LWR@compileuplatex}{}
2045 \@ifclassloaded{utarticle}{\LWR@compileuplatex}{}
2046 \@ifclassloaded{utbook}{\LWR@compileuplatex}{}
2047 \@ifclassloaded{utreport}{\LWR@compileuplatex}{}

```

Only make the setting permanent if the original was empty:

```
2048 \ifdefempty{\LWR@PrintLatexCmd}{
2049     \def\LWR@PrintLatexCmd{\LWR@tempprintlatexcmd}
2050 }{}
2051 \ifdefempty{\LWR@HTMLLatexCmd}{
2052     \def\LWR@HTMLLatexCmd{\LWR@tempHTMLlatexcmd}
2053 }{}

```

`\LWR@writeconf {filename}`

Common code for each of `lwarpmk.conf` and `<project>.lwarpmkconf`. Each entry is a variable name, the equal sign, and a quoted string inside `[[` and `]]`, which are *lua*'s long quote characters, allowing the use of single and double quotes inside.

```
2054 \newcommand{\LWR@writeconf}[1]{
2055 \ifcsdef{LWR@quickfile}{\newwrite{\LWR@quickfile}}
2056 \immediate\openout\LWR@quickfile=#1
2057 \immediate\write\LWR@quickfile{confversion = [[\LWR@lwarpcnfversion]]}
2058 \ifbool{usingOSWindows}{
2059     \immediate\write\LWR@quickfile{opsystem = [[Windows]]}
2060 }{
2061     \immediate\write\LWR@quickfile{opsystem = [[Unix]]}
2062 }
2063 \immediate\write\LWR@quickfile{sourcename = [[\jobname]]}
2064 \immediate\write\LWR@quickfile{homehtmlfilename = [[\HomeHTMLFilename]]}
2065 \immediate\write\LWR@quickfile{htmlfilename = [[\HTMLFilename]]}
2066 \immediate\write\LWR@quickfile{imagesdirectory = [[\LWR@ImagesDirectory]]}
2067 \immediate\write\LWR@quickfile{imagesname = [[\LWR@ImagesName]]}
2068 \immediate\write\LWR@quickfile{latexmk = [[\ifbool{LWR@latexmk}{true}{false}]]}
2069 \immediate\write\LWR@quickfile{printlatexcmd = [[\LWR@PrintLatexCmd]]}
2070 \immediate\write\LWR@quickfile{HTMLlatexcmd = [[\LWR@HTMLLatexCmd]]}
2071 \immediate\write\LWR@quickfile{printindexcmd = [[\LWR@PrintIndexCmd]]}
2072 \immediate\write\LWR@quickfile{HTMLindexcmd = [[\LWR@HTMLIndexCmd]]}
2073 \immediate\write\LWR@quickfile{latexmkindexcmd = [[\LWR@LatexmkIndexCmd]]}
2074 \immediate\write\LWR@quickfile{glossarycmd = [[\LWR@GlossaryCmd]]}
2075 \immediate\write\LWR@quickfile{pdftotextenc = [[\LWR@pdftotextEnc]]}
2076 \immediate\closeout\LWR@quickfile
2077 }
2078
2079 \end{LWRwriteconf}

```

39.3.2 lwarpmk.conf

File `lwarpmk.conf` `lwarpmk.conf` is automatically (re-)created by the `lwarp` package when executing `pdflatex <project.tex>`, or similar for `xelatex` or `lualatex`, in print-document generation mode, which is the default unless the `warpHTML` option is given. `lwarpmk.conf` is then used by the utility `lwarpmk`.

Config file: 2080 `\begin{LWRwriteconf}`
 2081
 2082 `\AtBeginDocument{\LWR@writeconf{lwarpmk.conf}}`
 2083
 2084 `\end{LWRwriteconf}`

39.3.3 <project>.lwarpmkconf

File `project.lwarpmkconf` A project-specific configuration file for `lwarpmk`.

The `makeindex` and `xindy` options have already been handled for `lwarp.conf`.

Config file: 2085 `\begin{LWRwriteconf}`
 2086
 2087 `\AtBeginDocument{\LWR@writeconf{\jobname.lwarpmkconf}}`
 2088
 2089 `\end{LWRwriteconf}`

39.4 lwarp.css

File `lwarp.css` This is the base CSS layer used by `lwarp`.

This must be present both when compiling the project and also when distributing the HTML files.

Config file: 2090 `\begin{LWRwriteconf}`
 2091 `\begin{filecontents*}[overwrite]{lwarp.css}`
 2092 `/*`
 2093 `CSS stylesheet for the LaTeX Lwarp package`
 2094 `Copyright 2016-2020 Brian Dunn – BD Tech Concepts LLC`
 2095 `*/`
 2096
 2097
 2098 `/* a fix for older browsers: */`
 2099 `header, section, footer, aside, nav, main,`
 2100 `article, figure { display: block; }`
 2101
 2102
 2103 `A:link {color:#000080 ; text-decoration: none ; }`
 2104 `A:visited {color:#800000 ; }`
 2105 `A:hover {color:#000080 ; text-decoration: underline ;}`
 2106 `A:active {color:#800000 ; }`
 2107

```
2108 a.tocbook {display: inline-block ; margin-left: 0em ;
2109     font-weight: bold ; margin-top: 1ex ; margin-bottom: 1ex ; }
2110 a.tocpart {display: inline-block ; margin-left: 0em ;
2111     font-weight: bold ;}
2112 a.tocchapter {display: inline-block ; margin-left: 0em ;
2113     font-weight: bold ;}
2114 a.tocsection {display: inline-block ; margin-left: 1em ;
2115     text-indent: -.5em ; font-weight: bold ; }
2116 a.tocsubsection {display: inline-block ; margin-left: 2em ;
2117     text-indent: -.5em ; }
2118 a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
2119     text-indent: -.5em ; }
2120 a.tocparagraph {display: inline-block ; margin-left: 4em ;
2121     text-indent: -.5em ; }
2122 a.tocsubparagraph {display: inline-block ; margin-left: 5em ;
2123     text-indent: -.5em ; }
2124 a.tocfigure {margin-left: 0em}
2125 a.tocsubfigure {margin-left: 2em}
2126 a.toctable {margin-left: 0em}
2127 a.tocsubtable {margin-left: 2em}
2128 a.toctheorem {margin-left: 0em}
2129 a.toclstlisting {margin-left: 0em}
2130
2131 body {
2132     font-family: "DejaVu Serif", "Bitstream Vera Serif",
2133         "Lucida Bright", Georgia, serif;
2134     background: #FAF7F4 ;
2135     color: black ;
2136     margin:0em ;
2137     padding:0em ;
2138     font-size: 100% ;
2139     line-height: 1.2 ;
2140 }
2141
2142 p {margin: 1.5ex 0em 1.5ex 0em ;}
2143 table p {margin: .5ex 0em .5ex 0em ;}
2144
2145 /* Holds a section number */
2146 span.sectionnumber { margin-right: 0em }
2147
2148 /* Inserted in front of index lines */
2149 span.indexitem {margin-left: 0em}
2150 span.indexsubitem {margin-left: 2em}
2151 span.indexsubsubitem {margin-left: 4em}
2152 div.indexheading {margin-top: 2ex ; font-weight: bold}
2153
2154 div.hidden, span.hidden { display: none ; }
2155
2156 kbd, span.texttt, p span.texttt {
2157     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2158         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2159         "Courier New", monospace;
2160     font-size: 100% ;
2161 }
2162
```

```
2163 pre { padding: 3pt ; }
2164
2165 span.strong, span.textbf, div.strong, div.textbf { font-weight: bold; }
2166
2167 span.textit, div.textit { font-style: italic; }
2168
2169 span.textmd, div.textmd { font-weight: normal; }
2170
2171 span.textup, div.textup {
2172     font-style: normal;
2173     font-variant: normal;
2174     font-variant-numeric: normal ;
2175 }
2176
2177 span.textsc, div.textsc {
2178     font-variant: small-caps;
2179     font-variant-numeric: oldstyle-nums ;
2180 }
2181
2182 span.textulc, div.textulc {
2183     font-variant: normal ;
2184     font-variant-numeric: normal ;
2185 }
2186
2187 span.textsl, div.textsl { font-style: oblique; }
2188
2189 span.textrm, div.textrm {
2190     font-family: "DejaVu Serif", "Bitstream Vera Serif",
2191     "Lucida Bright", Georgia, serif;
2192 }
2193
2194 span.textsf, div.textsf {
2195     font-family: "DejaVu Sans", "Bitstream Vera Sans",
2196     Geneva, Verdana, sans-serif ;
2197 }
2198
2199 /* nfssect-cfr lining figures */
2200 span.textln, div.textln {
2201     font-variant-numeric: lining-nums ;
2202 }
2203
2204 /* nfssect-cfr proportional figures */
2205 span.textp, div.textp {
2206     font-variant-numeric: proportional-nums ;
2207 }
2208
2209 /* nfssect-cfr tabular figures */
2210 span.textt, div.textt {
2211     font-variant-numeric: tabular-nums ;
2212 }
2213
2214 /* nfssect-cfr font weights */
2215 span.textdb, div.textdb {
2216     font-weight: 500 ;
2217 }
```

```
2218
2219 span.textsb, div.textsb {
2220     font-weight: 600 ;
2221 }
2222
2223 span.texteb, div.texteb {
2224     font-weight: 800 ;
2225 }
2226
2227 span.textub, div.textub {
2228     font-weight: 900 ;
2229 }
2230
2231 span.textlg, div.textlg {
2232     font-weight: 300 ;
2233 }
2234
2235 span.textel, div.textel {
2236     font-weight: 200 ;
2237 }
2238
2239 span.textul, div.textul {
2240     font-weight: 100 ;
2241 }
2242
2243
2244
2245 span.textcircled { border: 1px solid black ; border-radius: 1ex ; }
2246
2247 span.underline {
2248     text-decoration: underline ;
2249     text-decoration-skip: auto ;
2250 }
2251
2252 span.overline {
2253     text-decoration: overline ;
2254     text-decoration-skip: auto ;
2255 }
2256
2257 div.hrule { border-top: 1px solid silver }
2258
2259
2260 /* for vertical text: */
2261 div.verticalrl { writing-mode: vertical-rl }
2262 div.horizontalrb { writing-mode: horizontal-tb }
2263
2264
2265 /* for diagbox */
2266 div.diagboxtitleN { border-bottom: 1px solid gray }
2267 div.diagboxtitleS { border-top: 1px solid gray }
2268
2269 div.diagboxE {
2270     padding-left: 2em ;
2271     text-align: right ;
2272 }
```

```
2273
2274 div.diagboxW {
2275     padding-right: 2em ;
2276     text-align: left ;
2277 }
2278
2279
2280
2281 /* For realscripts */
2282 .supsubscript {
2283     display: inline-block;
2284     text-align:left ;
2285 }
2286
2287 .supsubscript sup,
2288 .supsubscript sub {
2289     position: relative;
2290     display: block;
2291     font-size: .7em;
2292     line-height: 1;
2293 }
2294
2295 .supsubscript sup {
2296     top: .3em;
2297 }
2298
2299 .supsubscript sub {
2300     top: .3em;
2301 }
2302
2303 div.attribution p {
2304     text-align: right ;
2305     font-size: 80%
2306 }
2307
2308 span.poemtitle {
2309     font-size: 120% ; font-weight: bold;
2310 }
2311
2312 pre.tabbing {
2313     font-family: "Linux Libertine Mono O", "Lucida Console",
2314                 "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
2315                 "Liberation Mono", "FreeMono", "Andale Mono",
2316                 "Nimbus Mono L", "Courier New", monospace;
2317 }
2318
2319 blockquote {
2320     display: block ;
2321     margin-left: 2em ;
2322     margin-right: 2em ;
2323 }
2324
2325 /* quotchap is for the quotchap package */
2326 div.quotchap {
2327     display: block ;
```

```
2328     font-style: oblique ;
2329     overflow-x: auto ;
2330     margin-left: 2em ;
2331     margin-right: 2em ;
2332 }
2333
2334 blockquote p, div.quotchap p {
2335     line-height: 1.5;
2336     text-align: left ;
2337     font-size: .85em ;
2338 }
2339
2340 /* qauthor is for the quotchap package */
2341 div.qauthor {
2342     display: block ;
2343     text-align: right ;
2344     margin-left: auto ;
2345     margin-right: 2em ;
2346     font-size: 80% ;
2347     font-variant: small-caps;
2348 }
2349
2350 div.qauthor p {
2351     text-align: right ;
2352 }
2353
2354 div.epigraph, div.dictum {
2355     line-height: 1.2;
2356     text-align: left ;
2357     padding: 3ex 1em 0ex 1em ;
2358 /*     margin: 3ex auto 3ex auto ; */ /* Epigraph centered */
2359     margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
2360 /*     margin: 3ex 1em 3ex 1em ; */ /* Epigraph to the left */
2361     font-size: .85em ;
2362     max-width: 27em ;
2363 }
2364
2365 div.epigraphsource, div.dictumauthor {
2366     text-align:right ;
2367     margin-left:auto ;
2368 /*     max-width: 50% ; */
2369     border-top: 1px solid #A0A0A0 ;
2370     padding-bottom: 3ex ;
2371     line-height: 1.2;
2372 }
2373
2374 div.epigraph p, div.dictum p { padding: .5ex ; margin: 0ex ;}
2375 div.epigraphsource p, div.dictumauthor p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
2376 div.dictumauthor { font-style:italic }
2377
2378
2379 /* copyrightbox package: */
2380 div.copyrightbox { margin: .5ex .5em }
2381 div.copyrightbox p {margin: 0px .5em ; padding: 0px}
2382 div.copyrightboxnote {text-align: left ; font-size: 60%}
```

```
2383
2384
2385 /* lettrine package: */
2386 span.lettrine { font-size: 4ex ; float: left ; }
2387 span.lettrinetext { font-variant: small-caps ; }
2388
2389 /* ulem, soul, umoline packages: */
2390 span.uline {
2391     text-decoration: underline ;
2392     text-decoration-skip: auto ;
2393 }
2394
2395 span.uuline {
2396     text-decoration: underline ;
2397     text-decoration-skip: auto ;
2398     text-decoration-style: double ;
2399 }
2400
2401 span.uwave {
2402     text-decoration: underline ;
2403     text-decoration-skip: auto ;
2404     text-decoration-style: wavy ;
2405 }
2406
2407 span.sout {
2408     text-decoration: line-through ;
2409 }
2410
2411 span.oline {
2412     text-decoration: overline ;
2413     text-decoration-skip: auto ;
2414 }
2415
2416 span.xout {
2417     text-decoration: line-through ;
2418 }
2419
2420 span.dashuline {
2421     text-decoration: underline ;
2422     text-decoration-skip: auto ;
2423     text-decoration-style: dashed ;
2424 }
2425
2426 span.dotuline {
2427     text-decoration: underline ;
2428     text-decoration-skip: auto ;
2429     text-decoration-style: dotted ;
2430 }
2431
2432 span.letterspacing { letter-spacing: .2ex ; }
2433
2434 span.capsspacing {
2435     font-variant: small-caps ;
2436     letter-spacing: .1ex ;
2437 }
```

```
2438
2439 span.highlight { background: #F8E800 ; }
2440
2441
2442 /* keystroke package: */
2443 span.keystroke {
2444     border-style: outset ;
2445     padding: 0pt .5em 0pt .5em ;
2446 }
2447
2448
2449 html body {
2450     margin: 0 ;
2451     line-height: 1.2;
2452 }
2453
2454
2455 body div {
2456     margin: 0ex;
2457 }
2458
2459
2460 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
2461 {
2462     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
2463     "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
2464     "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
2465     "Times New Roman", serif;
2466     font-style: normal ;
2467     font-weight: bold ;
2468     text-align: left ;
2469 }
2470
2471 h1 { /* title of the entire website, used on each page */
2472     text-align: center ;
2473     font-size: 2.5em ;
2474     padding: .4ex 0em 0ex 0em ;
2475 }
2476
2477 div.book {
2478     text-align: center ;
2479     font-size: 2.325em ;
2480     padding: .4ex 0em 0ex 0em ;
2481 }
2482
2483 h2 { font-size: 2.25em }
2484 h3 { font-size: 2em }
2485 h4 { font-size: 1.75em }
2486 h5 { font-size: 1.5em }
2487 h6 { font-size: 1.25em }
2488 span.paragraph {font-size: 1em ; font-variant: normal ;
2489     margin-right: 1em ; }
2490 span.subparagraph {font-size: 1em ; font-variant: normal ;
2491     margin-right: 1em ; }
2492
```

```
2493 div.minisec {
2494     font-family: "DejaVu Sans", "Bitstream Vera Sans",
2495         Geneva, Verdana, sans-serif ;
2496     font-style: normal ;
2497     font-weight: bold ;
2498     text-align: left ;
2499 }
2500
2501 h1 {
2502     margin: 0ex 0em 0ex 0em ;
2503     line-height: 1.3;
2504     text-align: center ;
2505 }
2506
2507 h2 {
2508     margin: 1ex 0em 1ex 0em ;
2509     line-height: 1.3;
2510     text-align: center ;
2511 }
2512
2513 h3 {
2514     margin: 3ex 0em 1ex 0em ;
2515     line-height: 1.3;
2516 }
2517
2518 h4 {
2519     margin: 3ex 0em 1ex 0em ;
2520     line-height: 1.3;
2521 }
2522
2523 h5 {
2524     margin: 3ex 0em 1ex 0em ;
2525     line-height: 1.3;
2526 }
2527
2528 h6 {
2529     margin: 3ex 0em 1ex 0em ;
2530     line-height: 1.3;
2531 }
2532
2533
2534 div.titlepage {
2535     text-align: center ;
2536 }
2537
2538 .footnotes {
2539     text-align: left ;
2540     font-size: .85em ;
2541     margin: 3ex 2em 0ex 2em ;
2542     border-top: 1px solid silver ;
2543 }
2544
2545 .marginpar, .marginparblock {
2546     max-width: 50%;
2547     float: right ;
```

```
2548     clear: both ;
2549     text-align: left ;
2550     margin: 1ex 0.5em 1ex 1em ;
2551     padding: 1ex 0.5em 1ex 0.5em ;
2552     font-size: 85% ;
2553     border-top: 1px solid silver ;
2554     border-bottom: 1px solid silver ;
2555     overflow-x: auto ;
2556 }
2557
2558 .marginpar br { margin-bottom: 2ex ; }
2559
2560 div.marginblock, div.marginparblock {
2561     max-width:50%;
2562     min-width: 10em; /* room for caption */
2563     float:right;
2564     text-align:left;
2565     margin: 1ex 0.5em 1ex 1em ;
2566     padding: 1ex 0.5em 1ex 0.5em ;
2567     overflow-x: auto;
2568 }
2569
2570 div.marginblock div.minipage,
2571 div.marginparblock div.minipage {
2572     display: inline-block ;
2573     margin: 0pt auto 0pt auto ;
2574 }
2575
2576 div.marginblock div.minipage p ,
2577 div.marginparblock div.minipage p
2578     { font-size: 85%}
2579
2580 div.marginblock br ,
2581 div.marginparblock br
2582     { margin-bottom: 2ex ; }
2583
2584 div.bodycontainer {
2585     float: left ;
2586     width: 80% ;
2587 }
2588
2589 div.bodywithoutsidetoc div.bodycontainer {
2590     float: none ;
2591     width: 100% ;
2592 }
2593
2594 section.textbody div.footnotes{
2595     margin: 3ex 2em .5ex 2em ;
2596     border-bottom: 2px solid silver ;
2597 }
2598
2599 .footnoteheader {
2600     border-top: 2px solid silver ;
2601     margin-top: 3ex ;
2602     padding-top: 1ex ;
```

```
2603     font-weight: bold ;
2604 }
2605
2606 .mpfootnotes {
2607     text-align: left ;
2608     font-size: .85em ;
2609     margin-left: 1em ;
2610     border-top: 1px solid silver ;
2611 }
2612
2613 /* Remove footnote top border in the title page. */
2614 div.titlepage div.mpfootnotes {
2615     border-top: none ;
2616 }
2617
2618
2619
2620 ul, ol {
2621     margin: 1ex 1em 1ex 0em;
2622     line-height: 1.2;
2623 }
2624
2625 body dir, body menu {
2626     margin: 3ex 1em 3ex 0em;
2627     line-height: 1.2;
2628 }
2629
2630 li { margin: 0ex 0em 1ex 0em; }
2631
2632 html {
2633     margin: 0;
2634     padding: 0;
2635 }
2636
2637 .programlisting {
2638     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2639         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2640         "Courier New", monospace;
2641     margin: 1ex 0ex 1ex 0ex ;
2642     padding: .5ex 0pt .5ex 0pt ;
2643     overflow-x: auto;
2644 }
2645
2646 section.textbody>pre.programlisting {
2647 border-top: 1px solid silver ;
2648 border-bottom: 1px solid silver ;
2649 }
2650
2651
2652 div.displaymath {
2653     text-align: center ;
2654 }
2655
2656 div.displaymathnumbered {
2657     text-align: right ;
```

```
2658     margin-left: 5% ;
2659     margin-right: 5% ;
2660     min-width: 2.5in ;
2661 }
2662
2663 @media all and (min-width: 400px) {
2664     div.displaymathnumbered {
2665         margin-left: 10% ;
2666         margin-right: 10% ;
2667     }
2668 }
2669
2670 @media all and (min-width: 800px) {
2671     div.displaymathnumbered {
2672         margin-right: 20% ;
2673     }
2674 }
2675
2676 @media all and (min-width: 1200px) {
2677     div.displaymathnumbered {
2678         margin-right: 30% ;
2679     }
2680 }
2681
2682
2683 .inlineprogramlisting {
2684     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
2685         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
2686         "Courier New", monospace;
2687     overflow-x: auto;
2688 }
2689
2690 span.listinglabel {
2691     display: inline-block ;
2692     font-size: 70% ;
2693     width: 4em ;
2694     text-align: right ;
2695     margin-right: 2em ;
2696 }
2697
2698 div.abstract {
2699     margin: 2em 5% 2em 5% ;
2700     padding: 1ex 1em 1ex 1em ;
2701     /* font-weight: bold ; */
2702     font-size: 90% ;
2703     text-align: left ;
2704 }
2705
2706 div.abstract dl {line-height:1.5;}
2707 div.abstract dt {color:#304070;}
2708
2709 div.abstracttitle{
2710     font-family: "URW Classico", Optima, "Linux Biolinum O",
2711         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2712         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
```

```
2713     font-weight:bold;
2714     font-size:1.25em;
2715     text-align: center ;
2716 }
2717
2718 span.abstractrunintitle{
2719     font-family: "URW Classico", Optima, "Linux Biolinum O",
2720         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2721         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2722     font-weight:bold;
2723 }
2724
2725
2726 .verbatim {
2727     overflow-x: auto ;
2728 }
2729
2730 .alltt {
2731     overflow-x: auto ;
2732 }
2733
2734
2735 .bverbatim {
2736     margin: 1ex 0pt 1ex 0pt ;
2737     padding: .5ex 0pt .5ex 0pt ;
2738     overflow-x: auto ;
2739 }
2740
2741 .lverbatim {
2742     margin: 1ex 0pt 1ex 0pt ;
2743     padding: .5ex 0pt .5ex 0pt ;
2744     overflow-x: auto ;
2745 }
2746
2747 .fancyvrb {
2748     font-size:.85em ;
2749     margin: 3ex 0pt 3ex 0pt
2750 }
2751
2752 .fancyvrblabel {
2753     font-size: .85em ;
2754     text-align: center ;
2755     font-weight: bold ;
2756     margin-top: 1ex ;
2757     margin-bottom: 1ex ;
2758 }
2759
2760
2761 .verse {
2762     font-family: "Linux Libertine Mono O", "Lucida Console",
2763         "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
2764         "Liberation Mono", "FreeMono", "Andale Mono",
2765         "Nimbus Mono L", "Courier New", monospace;
2766     margin-left: 1em ;
2767 }
```

```
2768
2769
2770 div.singlespace { line-height: 1.2 ; }
2771 div.onehalfspace { line-height: 1.5 ; }
2772 div.doublespace { line-height: 2 ; }
2773
2774
2775 /* Word processor format output: */
2776 div.wpfigure { border: 1px solid red ; margin: .5ex ; padding: .5ex ; }
2777 div.wptable { border: 1px solid blue ; margin: .5ex ; padding: .5ex ; }
2778 div.wpminipage { border: 1px solid green ; margin: .5ex ; padding: .5ex ;}
2779
2780
2781
2782
2783 /* Minipage environments, vertically aligned to top, center, bottom: */
2784 .minipage, .fminipage, .fcolorminipage {
2785     /* display: inline-block ; */
2786     /* Mini pages which follow each other will be tiled. */
2787     text-align:left;
2788     margin: .25em .25em .25em .25em;
2789     padding: .25em .25em .25em .25em;
2790     display: inline-flex;
2791     flex-direction: column ;
2792     overflow: auto;
2793 }
2794
2795 .inlineminipage {
2796     display: inline-block ;
2797     text-align: left
2798 }
2799
2800 /* Paragraphs in the flexbox did not collapse their margins. */
2801 /* Have not yet researched this. */
2802 .minipage p {margin: .75ex 0em .75ex 0em ;}
2803
2804 .fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
2805 .fcolorbox .minipage, .fcolorboxBlock .minipage
2806     {border: none ; background: none;}
2807
2808 .fbox, .fboxBlock { border: 1px solid black ; }
2809
2810 .fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
2811 .fminipage, .fcolorminipage
2812     {display: inline-block}
2813
2814 .shadowbox, .shabox {
2815     border: 1px solid black;
2816     box-shadow: 3px 3px 3px #808080 ;
2817     border-radius: 0px ;
2818     padding: .4ex .3em .4ex .3em ;
2819     margin: 0pt .3ex 0pt .3ex ;
2820     display: inline-block ;
2821 }
2822
```

```
2823 .doublebox {
2824     border: 3px double black;
2825     border-radius: 0px ;
2826     padding: .4ex .3em .4ex .3em ;
2827     margin: 0pt .3ex 0pt .3ex ;
2828     display: inline-block ;
2829 }
2830
2831 .ovalbox, .Ovalbox {
2832     border: 1px solid black;
2833     border-radius: 1ex ;
2834     padding: .4ex .3em .4ex .3em ;
2835     margin: 0pt .3ex 0pt .3ex ;
2836     display: inline-block ;
2837 }
2838
2839 .Ovalbox { border-width: 2px ; }
2840
2841 .framebox {
2842     border: 1px solid black;
2843     border-radius: 0px ;
2844     padding: .3ex .2em 0ex .2em ;
2845     margin: 0pt .1ex 0pt .1ex ;
2846     display: inline-block ;
2847 }
2848
2849
2850 /* mdframed, tcolorbox, shadebox packages */
2851 .mdframed, .tcolorbox, .shadebox {
2852     padding: 0ex ;
2853     margin: 2ex 0em 2ex 0em ;
2854     border: 1px solid black ;
2855 }
2856
2857 .tcolorbox {
2858     border-radius: 10pt ;
2859     margin: 2ex 1em 2ex 1em ;
2860 }
2861
2862 .mdframed p, .tcolorbox p { padding: 0ex .5em 0ex .5em ; }
2863
2864 .mdframed dl, .tcolorbox dl { padding: 1ex .5em 0ex .5em ; }
2865
2866 .mdframedtitle, .tcolorboxtitle {
2867     padding: .5ex 0pt 0pt 0pt ;
2868     border-radius: 10pt 10pt 0pt 0pt ;
2869     display: block ;
2870     margin-bottom: 1ex ;
2871     border-bottom: 1px solid silver ;
2872 }
2873
2874 .tcolorboxsubtitle .tcolorbox {
2875     margin: 2ex 0em 2ex 0em ;
2876     border-radius: 0pt ;
2877 }
```

```
2878
2879 .mdframedsubtitle {
2880     display: block ;
2881 }
2882
2883 .mdframedsubsubtitle {
2884     display: block ;
2885 }
2886
2887 .mdtheorem {
2888     padding: 0ex .5em 0ex .5em ;
2889     margin: 3ex 5% 3ex 5% ;
2890 }
2891
2892
2893 /* framed package */
2894 .framed, pre.boxedverbatim, fcolorbox {
2895     margin: 3ex 0em 3ex 0em ;
2896     border: 1px solid black;
2897     border-radius: 0px ;
2898     padding: .3ex 1em 0ex 1em ;
2899     display: block ;
2900 }
2901
2902 .shaded {
2903     margin: 3ex 0em 3ex 0em ;
2904     padding: .3ex 1em .3ex 1em ;
2905     display: block ;
2906 }
2907
2908 .snugframed {
2909     margin: 3ex 0em 3ex 0em ;
2910     border: 1px solid black;
2911     border-radius: 0px ;
2912     display: block ;
2913 }
2914
2915 .framedleftbar {
2916     margin: 3ex 0em 3ex 0em ;
2917     border-left: 3pt solid black;
2918     border-radius: 0px ;
2919     padding: .3ex .2em .3ex 1em ;
2920     display: block ;
2921 }
2922
2923 .framedtitle {
2924     margin: 0em ;
2925     padding: 0em ;
2926     font-size: 130%
2927 }
2928
2929 .framedtitle p { padding: .3em }
2930
2931
2932 /* For the niceframe package: */
```

```
2933
2934 div.niceframe, div.curlyframe, div.artdecoframe, div.generalframe {
2935     padding: 1ex ;
2936     margin: 2ex auto ;
2937     border-radius: 2ex ;
2938 }
2939
2940 div.niceframe {
2941     border: 6px groove black ;
2942 }
2943
2944 div.curlyframe {
2945     border-left: 3px dotted black ;
2946     border-right: 3px dotted black ;
2947     border-radius: 6ex ;
2948 }
2949
2950 div.artdecoframe {
2951     border-left: 10px double black ;
2952     border-right: 10px double black ;
2953     border-radius: 6ex ;
2954 }
2955
2956 div.generalframe {
2957     border: 6px groove black ;
2958 }
2959
2960
2961
2962 dl {
2963     margin: 1ex 2em 1ex 0em;
2964     line-height: 1.3;
2965 }
2966
2967 dl dt {
2968     display: block ;
2969     float:left ;
2970     font-weight: bold;
2971     padding-right: 1em ;
2972 }
2973
2974 dl dd { display: block ; }
2975
2976 dl dd:after { content: "" ; display: block ; clear: both }
2977
2978 dl dd p { margin-top: 0em; }
2979
2980 dd ul, dd ol, dd dl { clear: both ; padding-top: 1ex }
2981
2982
2983 nav {
2984     font-family: "URW Classico", Optima, "Linux Biolinum O",
2985                 "DejaVu Sans", "Bitstream Vera Sans",
2986                 Geneva, Verdana, sans-serif ;
2987     margin-bottom: 4ex ;
```

```
2988 }
2989
2990 nav p {
2991     line-height: 1.2 ;
2992     margin-top:.5ex ;
2993     margin-bottom:.5ex;
2994     font-size: .9em ;
2995 }
2996
2997
2998
2999 img, img.hyperimage, img.borderimage {
3000     max-width: 600px;
3001     border: 1px solid silver;
3002     box-shadow: 3px 3px 3px #808080 ;
3003     padding: .5% ;
3004     margin: .5% ;
3005     background: none ;
3006 }
3007
3008 img.inlineimage{
3009     padding: 0px ;
3010     box-shadow: none ;
3011     border: none ;
3012     background: none ;
3013     margin: 0px ;
3014     display: inline-block ;
3015     border-radius: 0px ;
3016 }
3017
3018 img.logoimage{
3019     max-width: 300px ;
3020     box-shadow: 3px 3px 3px #808080 ;
3021     border: 1px solid black ;
3022     background:none ;
3023     padding:0 ;
3024     margin:.5ex ;
3025     border-radius: 10px ;
3026 }
3027
3028
3029 .section {
3030 /*
3031     To have each section float relative to each other:
3032 */
3033 /*
3034     display: block ;
3035     float: left ;
3036     position: relative ;
3037     background: white ;
3038     border: 1px solid silver ;
3039     padding: .5em ;
3040 */
3041     margin: 0ex .5em 0ex .5em ;
3042     padding: 0 ;
```

```
3043 }
3044
3045
3046 figure {
3047     margin: 5ex auto 5ex auto ;
3048     padding: 1ex 1em 1ex 1em ;
3049     overflow-x: auto ;
3050 }
3051
3052
3053 /* To automatically center images in figures: */
3054 /*
3055 figure img.inlineimage {
3056     margin: 0ex auto 0ex auto ;
3057     display: block ;
3058 }
3059 */
3060
3061 /* To automatically center minipages in figures: */
3062 /*
3063 figure div.minipage, figure div.minipage div.minipage {
3064     margin: 1ex auto 1ex auto ;
3065     display: block ;
3066 }
3067 */
3068
3069 figure figure { margin: 0pt }
3070
3071 figure div.minipage p { font-size: 85% ; }
3072
3073 figure.subfigure, figure.subtable {
3074     display: inline-block ; margin: 3ex 1em 3ex 1em ;
3075 }
3076
3077 div.figurecaption .minipage { margin:0 ; padding: 0 }
3078
3079 div.minipage figure { border: none ; box-shadow: none ; }
3080 div.minipage figure.table { margin: 0ex }
3081 div.minipage div.footnotes { margin: 1ex 2em 0ex 2em }
3082
3083 div.floatrow { text-align: center; }
3084
3085 div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }
3086
3087 div.floatfoot { font-size: .85em ;
3088     border-top: 1px solid silver ; line-height: 1.2 ; }
3089
3090 div.figurecaption , .lstlistingtitle {
3091     font-size: .85em ;
3092     text-align: center ;
3093     font-weight: bold ;
3094     margin-top: 1ex ;
3095     margin-bottom: 1ex ;
3096 }
3097
```

```
3098 figure.subfigure div.figurecaption, figure.subtable div.figurecaption {
3099     border-bottom: none ; background: none ;
3100 }
3101
3102 div.nonfloatcaption {
3103     margin: 1ex auto 1ex auto ;
3104     font-size: .85em ;
3105     text-align: center ;
3106     font-weight: bold ;
3107 }
3108
3109 /* For a \RawCaption inside a minipage inside a figure's floatrow: */
3110 figure div.floatrow div.minipage div.figurecaption {
3111     border: none ;
3112     background: none ;
3113 }
3114
3115
3116 /* For packages such as float, rotfloat, and algorithm2e: */
3117
3118 figure.boxed, figure.boxruled {
3119     border: 1px solid black ;
3120 }
3121
3122 figure.ruled {
3123     border-top: 1px solid black ;
3124     border-bottom: 1px solid black ;
3125     border-left: 0px ;
3126     border-right: 0px ;
3127     border-radius: 0px ;
3128     background: none ;
3129     box-shadow: none ;
3130 }
3131
3132 figure.ruled div.figurecaption, figure.boxruled div.figurecaption {
3133     border-top: 1px solid silver ;
3134     border-bottom: 1px solid silver ;
3135 }
3136
3137
3138 table {
3139     margin: 1ex auto 1ex auto ;
3140     border-collapse: separate ;
3141     border-spacing: 0px ;
3142     line-height: 1.3 ;
3143 }
3144
3145 table > tbody > tr.hline > td {border-top: 1px solid #808080 ; margin-top: 0ex ;
3146     margin-bottom: 0ex ; } /* for \hline */
3147
3148 tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;
3149     margin-bottom: 0ex ; } /* for \toprule, \bottomrule */
3150
3151 td {padding: .5ex .5em .5ex .5em ;}
3152
```

```
3153 table td.tdl { text-align: left ; vertical-align: middle ; }
3154 table td.tdc { text-align: center ; vertical-align: middle ; }
3155 table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }
3156 table td.tdbang { text-align: center ; vertical-align: middle ; }
3157 table td.tdr { text-align: right ; vertical-align: middle ; }
3158 table td.tdp { text-align: left ; vertical-align: bottom ; }
3159 table td.tdm { text-align: left ; vertical-align: middle ; }
3160 table td.tdb { text-align: left ; vertical-align: top ; }
3161 table td.tdP { text-align: center ; vertical-align: bottom ; }
3162 table td.tdM { text-align: center ; vertical-align: middle ; }
3163 table td.tdB { text-align: center ; vertical-align: top ; }
3164
3165 table td.tvertbarl { border-left: 1px solid black }
3166 table td.tvertbardouble { border-left: 4px double black }
3167 table td.tvertbarr { border-right: 1px solid black }
3168 table td.tvertbarrdouble { border-right: 4px double black }
3169
3170 table td.tvertbarldash { border-left: 1px dashed black }
3171 table td.tvertbarldoubledash { border-left: 2px dashed black }
3172 table td.tvertbarrdash { border-right: 1px dashed black }
3173 table td.tvertbarrdoubledash { border-right: 2px dashed black }
3174
3175
3176 /* for cmidrules: */
3177 table td.tdrule {
3178     border-top: 1px solid #A0A0A0 ;
3179 }
3180
3181 table td.tdrulel {
3182     border-top-left-radius:.5em ;
3183     border-top: 1px solid #A0A0A0 ;
3184 }
3185
3186 table td.tdruler {
3187     border-top-right-radius:.5em ;
3188     border-top: 1px solid #A0A0A0 ;
3189 }
3190
3191 table td.tdrulelr {
3192     border-top-left-radius:.5em ;
3193     border-top-right-radius:.5em ;
3194     border-top: 1px solid #A0A0A0 ;
3195 }
3196
3197
3198 /* Margins of paragraphs inside table cells: */
3199 td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
3200     padding-bottom: 1ex ; margin: 0ex ; }
3201 td.tdm p , td.tdmrule p , td.tdM p , td.tdMrule p { padding-top: 1ex ;
3202     padding-bottom: 1ex ; margin: 0ex ; }
3203 td.tdb p , td.tdbrule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
3204     padding-bottom: 1ex ; margin: 0ex ; }
3205
3206 td.tdp , td.tdprule , td.tdP , td.tdPrule
3207     { padding: 0ex .5em 0ex .5em ; }
```

```
3208 td.tdm , td.tdmrule , td.tdM , td.tdMrule
3209     { padding: 0ex .5em 0ex .5em ; }
3210 td.tdb , td.tdbrule , td.tdB , td.tdBrule
3211     { padding: 0ex .5em 0ex .5em ; }
3212
3213
3214 /* table notes: */
3215 .tnotes {
3216     margin: 0ex 5% 1ex 5% ;
3217     padding: 0.5ex 1em 0.5ex 1em;
3218     font-size:.80em;
3219     text-align: left ;
3220 }
3221
3222 .minipage .tnotes {
3223     margin: 0pt ;
3224     padding: 0pt ;
3225 }
3226
3227 .tnotes dl dt p {margin-bottom:0px;}
3228
3229 .tnoteitemheader {margin-right: 1em;}
3230
3231
3232 /* for colortbl and cell color */
3233 div.cellcolor {
3234     width: 100% ;
3235     padding: .5ex .5em .5ex .5em ;
3236     margin: -.5ex -.5em -.5ex -.5em ;
3237 }
3238
3239
3240 /* for lyluatex */
3241 span.lyluatex {
3242     display: inline-block ;
3243 }
3244
3245 div.lyluatex p span.lateximagesource img {
3246     display: block ;
3247     margin-top: 3ex ;
3248     margin-bottom: 3ex ;
3249 }
3250
3251
3252 /* for bigdelim */
3253 .ldelim, .rdelim { font-size: 200% }
3254
3255
3256 /* center, flushleft, flushright environments */
3257 div.center{text-align:center;}
3258 div.center table {margin-left:auto;margin-right:auto;}
3259 div.flushleft{text-align:left;}
3260 div.flushleft table {margin-left:0em ; margin-right:auto;}
3261 div.flushright{text-align:right;}
3262 div.flushright table {margin-left:auto ; margin-right: 0em ;}
```

```
3263
3264
3265 /* Fancybox */
3266 div.Btrivlist table tr td {
3267     padding: .2ex 0em ;
3268 }
3269
3270
3271 /* program listing callouts: */
3272 span.callout {
3273     font-family: "DejaVu Sans", "Bitstream Vera Sans",
3274         Geneva, Verdana, sans-serif ;
3275     border-radius: .5em;
3276     background-color:black;
3277     color:white;
3278     padding:0px .25em 0px .25em;
3279     margin: 0 ;
3280     font-weight: bold;
3281     font-size:.72em ;
3282 }
3283
3284 div.programlisting pre.verbatim span.callout{
3285     font-size: .85em ;
3286 }
3287
3288 span.verbatim {
3289     font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
3290         "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
3291         "Courier New", monospace;
3292 }
3293
3294
3295
3296 div.titlehead
3297 {
3298     text-align: left ;
3299     font-style: normal ;
3300     font-weight: normal ;
3301     font-style: normal ;
3302     font-size: .8em ;
3303     margin: 1ex 0em 1ex 0em ;
3304 }
3305
3306 div.subject
3307 {
3308     text-align: center ;
3309     font-style: normal ;
3310     font-weight: bold ;
3311     font-style: normal ;
3312     font-size: .8em ;
3313     margin: 1ex 0em 1ex 0em ;
3314 }
3315
3316 div.published
3317 {
```

```
3318     text-align: center ;
3319     font-variant: normal ;
3320     font-style: italic ;
3321     font-size: 1em ;
3322     margin: 1ex 0em 1ex 0em ;
3323 }
3324
3325 div.subtitle
3326 {
3327     text-align: center ;
3328     font-variant: normal ;
3329     font-style: italic ;
3330     font-size: 1.25em ;
3331     margin: 1ex 0em 1ex 0em ;
3332 }
3333
3334 div.subtitle p { margin: 1ex ; }
3335
3336 div.author
3337 {
3338     font-variant: normal ;
3339     font-style: normal ;
3340     font-size: 1em ;
3341     margin: 1ex 0em 1ex 0em ;
3342 }
3343
3344 div.oneauthor {
3345     display: inline-block ;
3346     margin: 0ex 1em 0ex 1em ;
3347 }
3348
3349 /*
3350 div.author table {
3351     margin: 1ex auto 0ex auto ;
3352     background: none ;
3353 }
3354
3355 div.author table tbody tr td { padding: .25ex ; }
3356 */
3357
3358 span.affiliation {font-size: .85em ; font-variant: small-caps; }
3359
3360 div.titledate {
3361     text-align: center ;
3362     font-size: .85em ;
3363     font-style: italic;
3364     margin: 1ex 0em 1ex 0em ;
3365 }
3366
3367
3368 nav.topnavigation{
3369     text-align: left ;
3370     padding: 0.5ex 1em 0.5ex 1em ;
3371 /*     margin: 2ex 0em 3ex 0em ; */
3372     margin: 0 ;
```

```
3373     border-bottom: 1px solid silver ;
3374     border-top: 1px solid silver ;
3375     clear:both ;
3376 }
3377
3378 nav.botnavigation{
3379     text-align: left ;
3380     padding: 0.5ex 1em 0.5ex 1em ;
3381 /*     margin: 3ex 0em 2ex 0em ; */
3382     margin: 0 ;
3383     border-top: 1px solid silver ;
3384     border-bottom: 1px solid silver ;
3385     clear:both ;
3386 }
3387
3388
3389 header {
3390     line-height: 1.2 ;
3391     font-size: 1em ;
3392     border-bottom: 1px solid silver ;
3393     margin: 0px ;
3394     padding: 2ex 1em 2ex 1em ;
3395     text-align:left ;
3396 }
3397
3398
3399 footer {
3400     font-size: .85em ;
3401     line-height: 1.2 ;
3402     margin-top: 1ex ;
3403     border-top: 1px solid silver ;
3404     padding: 2ex 1em 2ex 1em ;
3405     clear:both ;
3406     text-align:left ;
3407 }
3408
3409
3410 /* for \LinkHome, \LinkPrevious, and \LinkNext: */
3411 a.linkhome { font-weight:bold ; font-size: 1em ;}
3412
3413
3414 div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }
3415
3416 img.lateximage{
3417     padding: 0pt ;
3418     margin: 0pt ;
3419     box-shadow: none ;
3420     border: none ;
3421     background: none ;
3422     max-width: 100% ;
3423     border-radius: 0ex ;
3424     border: none ;
3425 }
3426
3427
```

```
3428 /* The -1px right margin compensates for the 1px right border. */
3429 /* Without this -1px margin, the body container appears below instead */
3430 /* of floating to the side. */
3431 div.sidetoccontainer {
3432     font-family: "DejaVu Serif", "Bitstream Vera Serif",
3433         "Lucida Bright", Georgia, serif;
3434     float: left ;
3435     width: 20%;
3436     margin: 0pt -1px 3ex 0pt ;
3437     border-right: 1px solid silver;
3438     border-bottom: 1px solid silver;
3439     background: #FAF7F4 ;
3440     font-size:.9em ;
3441     border-radius: 0px 0px 20px 0px ;
3442 }
3443
3444 div.sidetoccontents {
3445     overflow-y: auto ;
3446     width: 100% ;
3447     text-align: left ;
3448 }
3449
3450
3451 nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;
3452     text-indent: 0 ; }
3453
3454 nav.sidetoc p a {color:black ; font-size: .7em ;}
3455
3456 div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;
3457     border-bottom: 1px solid silver ;    }
3458
3459 nav.sidetoc a:hover {text-decoration: underline ; }
3460
3461
3462
3463 section.textbody { margin: 0ex 1em 0ex 1em ;}
3464
3465
3466 div.multicolshheading { -webkit-column-span: all;
3467     -moz-column-span: all; column-span: all; }
3468 div.multicols { -webkit-columns: 3 380px ;
3469     -moz-columns: 3 380px ; columns: 3 380px ; }
3470 div.multicols p {margin-top: 0ex}
3471
3472
3473 /* Used for xfrac and nicefrac: */
3474 span.numerator {
3475     font-size: 60% ;
3476     vertical-align: .4em ;
3477 }
3478
3479 span.denominator {
3480     font-size: 60%
3481 }
3482
```

```
3483
3484 /* Used for algorithm2e: */
3485 div.alg2evline{
3486     margin-left: 1em ;
3487     padding-left: 1em ;
3488     border-left: 1px solid black ;
3489     border-radius: 0px 0px 0px 1ex ;
3490 }
3491
3492 div.alg2evsline{
3493     margin-left: 1em ;
3494     padding-left: 1em ;
3495     border-left: 1px solid black ;
3496 }
3497
3498 div.alg2enoline{
3499     margin-left: 1em ;
3500     padding-left: 1em ;
3501 }
3502
3503 span.alg2elinenumber{
3504     margin-right: .5em ;
3505     font-size: 50% ;
3506     color: red ;
3507 }
3508
3509
3510 /* Used for algorithmicx: */
3511 span.floatright { float: right ; }
3512
3513
3514 /* keyfloat and tocdata: */
3515 .floatnotes {
3516     margin: 0ex 5% 0ex 5% ;
3517     padding: 0ex 1em 0ex 1em ;
3518     font-size:.80em ;
3519     text-align: left ;
3520 }
3521
3522 .authorartist{
3523     display:block ;
3524     font-size:.70em ;
3525     font-style: italic;
3526 }
3527
3528 nav .authorartist{ display:inline; }
3529
3530
3531
3532 /* Native LaTeX theorems: */
3533
3534 .theoremcontents {
3535     font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ;
3536 }
3537
```

```
3538 .theoremlabel {
3539     font-style: normal; font-weight: bold ; margin-right: .5em ;
3540 }
3541
3542
3543
3544 /* theorem, amsthm, and ntheorem packages */
3545
3546 span.theoremheader,
3547 span.theoremheaderplain,
3548 span.theoremheaderdefinition,
3549 span.theoremheaderbreak,
3550 span.theoremheadermarginbreak,
3551 span.theoremheaderchangebreak,
3552 span.theoremheaderchange,
3553 span.theoremheadermargin
3554 {
3555     font-style:normal ; font-weight: bold ; margin-right: 1em ;
3556 }
3557
3558 span.amsthmnameplain,
3559 span.amsthmnamedefinition,
3560 span.amsthmnumberplain,
3561 span.amsthmnumberdefinition
3562 {
3563     font-style:normal ; font-weight: bold ;
3564 }
3565
3566
3567 span.amsthmnameremark,
3568 span.amsthmnumberremark
3569 {font-style:italic ; font-weight: normal ; }
3570
3571
3572 span.amsthmnoteplain,
3573 span.amsthmnotedefinition
3574 {font-style:normal ;}
3575
3576
3577 span.theoremheaderremark,
3578 span.theoremheaderproof,
3579 span.amsthmproofname
3580 {font-style:italic ; font-weight: normal ; margin-right: 1em ; }
3581
3582 span.theoremheadersc
3583 {
3584     font-style:normal ;
3585     font-variant: small-caps ;
3586     font-weight: normal ;
3587     margin-right: 1em ;
3588 }
3589
3590 .theoremdemark {float:right}
3591
3592 div.amsthmbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
```

```
3593 div.theorembodybreak, div.theorembodynonumberbreak,
3594 div.theorembodymarginbreak,
3595 div.theorembodychangebreak,
3596 div.theorembodychange,
3597 div.theorembodymargin
3598 {
3599     font-style:italic;
3600     margin-top: 3ex ; margin-bottom: 3ex ;
3601 }
3602
3603 div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
3604 div.theorembodyplainupright, nonumberplainuprightsc,
3605 div.amsthmbodydefinition, div.amsthmbodyremark,
3606 div.amsthmproof
3607 {
3608     font-style: normal ;
3609     margin-top: 3ex ; margin-bottom: 3ex ;
3610 }
3611
3612 span.amsthmnoteremark {}
3613
3614
3615 /* thmbox */
3616
3617 .thmbox {
3618     font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ;
3619     border: 1px solid gray ;
3620     padding: 1ex ;
3621 }
3622
3623 .thmboxtitle {
3624     font-style: normal; font-weight: bold ; margin-right: .5em ;
3625     border-bottom: 1px solid gray ;
3626 }
3627
3628 span.thmboxproofname, span.thmboxexemplename {
3629     font-weight: bold ;
3630 }
3631
3632 div.thmboxproof, div.thmboxexample {
3633     font-size: 0.85em ;
3634     margin: 2ex ;
3635 }
3636
3637 div.thmboxleftbar {
3638     border-left: 2px solid black ;
3639     padding-left: 1em ;
3640 }
3641
3642
3643
3644 /* For the backnaur package: */
3645 div.backnaur {
3646     display: block ;
3647     margin: 2ex 2em 2ex 2em ;
```

```
3648 }
3649
3650 div.backnaur p {
3651     margin: .25ex 0ex .25ex 0ex ;
3652 }
3653
3654 div.backnaurprod {
3655     display: inline-block ;
3656     min-width: 8em ;
3657     text-align:right ;
3658 }
3659
3660 div.backnaurdsc {
3661     display: inline-block ;
3662 }
3663
3664
3665 /* For the notes package: */
3666 div.notesimportantnote, div.noteswarningnote, div.notesinformationnote {
3667     clear: both ;
3668     margin: 2ex 2em 2ex 2em ;
3669     border: 1px solid silver ;
3670 }
3671
3672 div.notesicon {
3673     float:left ;
3674     display: inline-block ;
3675     background: gold ;
3676     padding: 0ex 1em 0ex 1em ;
3677     margin-right: 1em ;
3678     font-weight: bold ;
3679 }
3680
3681 div.notescontents { font-style: italic }
3682
3683
3684 /* nolbreaks package: */
3685 span.nolbreaks { white-space: nowrap ; }
3686
3687
3688 /*
3689 For CSS LaTeX and related logos:
3690 Based on spacing demonstrated by the metafont package.
3691 */
3692
3693 .latexlogofont {
3694     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3695         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3696     font-variant: normal ;
3697 }
3698
3699 .latexlogo {
3700     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3701         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3702     font-size: 1.1em;
```

```
3703 }
3704
3705 .latexlogosup {
3706   text-transform: uppercase;
3707   letter-spacing: .03em ;
3708   font-size: 0.7em;
3709   vertical-align: 0.25em;
3710   margin-left: -0.4em;
3711   margin-right: -0.15em;
3712 }
3713
3714 .latexlogosub {
3715   text-transform: uppercase;
3716   vertical-align: -0.27ex;
3717   margin-left: -0.08em;
3718   margin-right: -0.07em;
3719   font-size: 1em;
3720 }
3721
3722 .latexlogotwoe {
3723   text-transform: none ;
3724   font-variant-numeric: oldstyle-nums ;
3725 }
3726
3727 .latexlogotwoesub {
3728   font-style:italic ;
3729   vertical-align: -0.27ex;
3730   margin-left: -0.11em;
3731   margin-right: -0.1em;
3732   font-size: 1em;
3733 }
3734
3735 .xelatexlogo {
3736   font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3737     "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3738   letter-spacing: .03em ;
3739   font-size: 1.1em;
3740 }
3741
3742 .xelatexlogosub {
3743   vertical-align: -0.27ex;
3744   margin-left: -0.0667em;
3745   margin-right: -.05em;
3746   font-size: 1em;
3747   letter-spacing: .03em ;
3748 }
3749
3750 .amslogo {
3751   font-family: "TeXGyreChorus","URW Chancery L",
3752     "Apple Chancery","ITC Zapf Chancery","Monotype Corsiva",
3753     "Linux Libertine O", "Nimbus Roman No 9 L", "FreeSerif",
3754     "Hoefler Text", Times, "Times New Roman", serif ;
3755   font-style: italic ;
3756 }
3757
```

```
3758 .lyxlogo {
3759     font-family: "URW Classico", Optima, "Linux Biolinum O",
3760         "DejaVu Sans", "Bitstream Vera Sans", Geneva,
3761         Verdana, sans-serif ;
3762 }
3763
3764
3765 /* Only display top and bottom navigation if a small screen: */
3766 /* Hide the sidetoc if a small screen: */
3767 nav.topnavigation { display:none; }
3768 nav.botnavigation { display:none; }
3769
3770 /* Only display the sidetoc's webpage title if a small screen */
3771 span.sidetocthetitle { display: none }
3772
3773 @media screen and (max-width: 50em) {
3774     div.sidetoccontainer {
3775         float: none ;
3776         width: 100% ;
3777         padding: 0 ;
3778         border-radius: 0 ;
3779         border-bottom: 1px solid black ;
3780         border-top: 1px solid black ;
3781         box-shadow: none ;
3782     }
3783     span.sidetocthetitle { display: inline }
3784     nav.topnavigation { display:block }
3785     nav.botnavigation { display:block }
3786     div.bodycontainer { width: 100% }
3787     .marginpar {
3788         max-width: 100%;
3789         float: none;
3790         display:block ;
3791         margin: 1ex 1em 1ex 1em ;
3792     }
3793 }
3794
3795 @media print {
3796     body {
3797         font-family: "Linux Libertine O",
3798             "DejaVu Serif", "Bitstream Vera Serif",
3799             "Liberation Serif", "Nimbus Roman No 9 L",
3800             "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3801     }
3802     div.sidetoccontainer { display:none; }
3803     nav.topnavigation { display: none; }
3804     nav.botnavigation { display: none; }
3805     div.bodycontainer { width: 100% }
3806 }
3807
3808 @media handheld {
3809     div.sidetoccontainer { display:none; }
3810     nav.topnavigation { display:block }
3811     nav.botnavigation { display:block }
3812     div.bodycontainer { width: 100% }
```

```

3813 }
3814
3815 @media projection {
3816     div.sidetoccontainer { display:none; }
3817     nav.topnavigation { display:block }
3818     nav.botnavigation { display:block }
3819     div.bodycontainer { width: 100% }
3820 }
3821 \end{filecontents*}
3822 % \end{Verbatim}% for syntax highlighting
3823 \end{LWRwriteconf}

```

39.5 lwarp_sagebrush.css

File `lwarp_sagebrush.css` An optional css which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

```

Config file: 3824 \begin{LWRwriteconf}
3825 \begin{filecontents*}[overwrite]{lwarp_sagebrush.css}
3826 @import url("lwarp.css") ;
3827
3828
3829 A:link {color:#105030 ; text-decoration: none ; }
3830 A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}
3831 A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}
3832 A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}
3833
3834
3835
3836 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
3837 {
3838     font-family: "URW Classico", Optima, "Linux Biolinum 0",
3839     "Linux Libertine 0", "Liberation Serif",
3840     "Nimbus Roman No 9 L", "FreeSerif",
3841     "Hoefler Text", Times, "Times New Roman", serif;
3842     font-variant: small-caps ;
3843     font-weight: normal ;
3844     color: #304070 ;
3845     text-shadow: 2px 2px 3px #808080;
3846 }
3847
3848 h1 { /* title of the entire website, used on each page */
3849     font-variant: small-caps ;
3850     color: #304070 ;
3851     text-shadow: 2px 2px 3px #808080;
3852     background-color: #F7F7F0 ;
3853     background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);
3854 }
3855
3856 h1 {
3857     border-bottom: 1px solid #304070;
3858 /* border-top: 2px solid #304070; */

```

```
3859 }
3860
3861 h2 {
3862   border-bottom: 1px solid #304070;
3863 /*   border-top: 2px solid #304070; */
3864   background-color: #F7F7F0 ;
3865   background-image: linear-gradient(to bottom, #F7F7F0, #DAD0C0);
3866 }
3867
3868
3869
3870 div.abstract {
3871   background: #f5f5eb ;
3872   background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3873
3874   border: 1px solid silver;
3875   border-radius: 1em ;
3876 }
3877
3878 div.abstract dl {line-height:1.5;}
3879 div.abstract dt {color:#304070;}
3880
3881 div.abstracttitle{
3882   font-family: "URW Classico", Optima, "Linux Biolinum O",
3883     "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3884     "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3885   font-weight:bold;
3886   font-variant: small-caps ;
3887   font-size:1.5em;
3888   border-bottom: 1px solid silver ;
3889   color: #304070 ;
3890   text-align: center ;
3891   text-shadow: 1px 1px 2px #808080;
3892 }
3893
3894 span.abstracrunintitle{
3895   font-family: "URW Classico", Optima, "Linux Biolinum O",
3896     "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3897     "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3898   font-weight:bold;
3899 }
3900
3901
3902 div.epigraph, div.dictum {
3903   background: #f5f5eb ;
3904   background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3905
3906   border: 1px solid silver ;
3907   border-radius: 1ex ;
3908   box-shadow: 3px 3px 3px #808080 ;
3909 }
3910
3911
3912 .example {
3913   background-color: #f5f5eb ;
```

```
3914     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3915
3916 }
3917
3918 div.exampletitle{
3919     font-family: "URW Classico", Optima, "Linux Biolinum O",
3920         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3921         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3922     font-weight:bold;
3923     font-variant: small-caps ;
3924     border-bottom: 1px solid silver ;
3925     color: #304070 ;
3926     text-align: center ;
3927     text-shadow: 1px 1px 2px #808080;
3928 }
3929
3930
3931 .sidebar {
3932     background-color: #f5f5eb ;
3933     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3934
3935 }
3936
3937 div.sidebartitle{
3938     font-family: "URW Classico", Optima, "Linux Biolinum O",
3939         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3940         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3941     font-weight:bold;
3942     font-variant: small-caps ;
3943     border-bottom: 1px solid silver ;
3944     color: #304070 ;
3945     text-align: center ;
3946     text-shadow: 1px 1px 2px #808080;
3947 }
3948
3949
3950 .fancyvrblabel {
3951     font-family: "URW Classico", Optima, "Linux Biolinum O",
3952         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3953         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3954     font-weight:bold;
3955     font-variant: small-caps ;
3956     font-size: 1.5em ;
3957     color: #304070 ;
3958     text-align: center ;
3959     text-shadow: 1px 1px 2px #808080;
3960 }
3961
3962 div.minipage {
3963     background-color: #eeeeee7 ;
3964     border: 1px solid silver ;
3965     border-radius: 1ex ;
3966 }
3967
3968 table div.minipage { background: none ; border: none ; }
```

```
3969
3970 div.framebox div.minipage {border:none ; background:none}
3971
3972 section.textbody > div.minipage {
3973     box-shadow: 3px 3px 3px #808080 ;
3974 }
3975
3976 div.fboxBlock div.minipage { box-shadow: none ; }
3977
3978 .framed .minipage , .framedleftbar .minipage {
3979     border: none ;
3980     background: none ;
3981     padding: 0ex ;
3982     margin: 0ex ;
3983 }
3984
3985 figure.figure .minipage, div.figurecaption .minipage { border: none; }
3986
3987 div.marginblock div.minipage ,
3988 div.marginparblock div.minipage
3989     { border: none; }
3990
3991 figure , div.marginblock {
3992     background-color: #eeeeee7 ;
3993     border: 1px solid silver ;
3994     border-radius: 1ex ;
3995     box-shadow: 3px 3px 3px #808080 ;
3996 }
3997
3998 figure figure {
3999     border: 1px solid silver ;
4000     margin: 0em ;
4001     box-shadow: none ;
4002 }
4003
4004 /*
4005 div.figurecaption {
4006     border-top: 1px solid silver ;
4007     border-bottom: 1px solid silver ;
4008     background-color: #e8e8e8 ;
4009 }
4010 */
4011
4012
4013 div.table {
4014     box-shadow: 3px 3px 3px #808080 ;
4015 }
4016
4017 /*
4018 .tnotes {
4019     background: #e8e8e8;
4020     border: 1px solid silver;
4021 }
4022 */
4023
```

```
4024
4025 nav.topnavigation{
4026     background-color: #b0b8b0 ;
4027     background-image: linear-gradient(to bottom,#e0e0e0,#b0b8b0) ;
4028 }
4029
4030 nav.botnavigation{
4031     background-color: #b0b8b0 ;
4032     background-image: linear-gradient(to top,#e0e0e0,#b0b8b0) ;
4033 }
4034
4035
4036
4037 header{
4038     background-color: #F7F7F0 ;
4039     background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
4040 }
4041
4042 footer{
4043     background-color: #F7F7F0 ;
4044     background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
4045 }
4046
4047
4048
4049 div.sidetoccontainer {
4050     background-color: #F7F7F0 ;
4051     background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
4052     box-shadow: 3px 3px 3px #808080 ;
4053     }
4054
4055 div.sidetocitle {color: #304070 ; }
4056
4057 nav.sidetoc a:hover {
4058     color:#006000 ;
4059     text-decoration: none ;
4060     text-shadow:0px 0px 2px #a0a0a0;
4061 }
4062
4063
4064 @media screen and (max-width: 45em) {
4065     div.sidetoccontainer { border-radius: 0 ; }
4066 }
4067
4068
4069 \end{filecontents*}
4070 % \end{Verbatim}% for syntax highlighting
4071 \end{LWRwriteconf}
```

39.6 lwarp_formal.css

File lwarp_formal.css An optional css which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

```
Config file: 4072 \begin{LWRwriteconf}
4073 \begin{filecontents*}[overwrite]{lwarp_formal.css}
4074 @import url("lwarp.css") ;
4075
4076
4077
4078 A:link {color:#802020 ; text-decoration:none; }
4079 A:visited {color:#802020 ; text-shadow:none ;}
4080 A:hover {color:#400000 ; text-shadow:none ;}
4081 A:active {color:#C00000 ; text-shadow:none ;}
4082
4083
4084 body {
4085     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4086         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4087         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4088         "Times New Roman", serif;
4089     background: #fffcf5;
4090 }
4091
4092 span.textrm {
4093     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4094         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4095         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4096         "Times New Roman", serif;
4097 }
4098
4099 span.textsf {
4100     font-family: "DejaVu Sans", "Bitstream Vera Sans",
4101         Geneva, Verdana, sans-serif ;
4102 }
4103
4104
4105
4106 div.book, h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
4107 {
4108     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4109         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4110         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4111         "Times New Roman", serif;
4112     color: #800000 ;
4113     text-shadow: none ;
4114 }
4115
4116 h1, h2 {
4117     background-color: #fffcf5 ;
4118     background-image: none ;
4119     border-bottom: 1px solid #808080;
4120 /*     border-top: 2px solid #808080; */
4121 }
4122
4123 div.abstracttitle {
4124     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
```

```
4125     "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4126     "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4127     "Times New Roman", serif;
4128     color: black ;
4129     text-shadow: none ;
4130 }
4131
4132 span.abstractrunintitle {
4133     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4134     "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4135     "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4136     "Times New Roman", serif;
4137     color: black ;
4138     text-shadow: none ;
4139 }
4140
4141 div.abstract { font-size: 100% }
4142
4143 .sidebar {
4144     background: #fffcf5;
4145     background-image: none ;
4146     margin: 2em 5% 2em 5%;
4147     padding: 0.5em 1em;
4148     border: none ;
4149     border-top : 1px solid silver;
4150     border-bottom : 1px solid silver;
4151     font-size: 90% ;
4152 }
4153
4154 div.sidebartitle{
4155     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4156     "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4157     "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4158     "Times New Roman", serif;
4159     color: #800000 ;
4160     text-shadow: none ;
4161     border: none ;
4162 }
4163
4164 .example {
4165     background: #fffcf5;
4166     background-image: none ;
4167     margin: 2em 5% 2em 5%;
4168     padding: 0.5em 1em;
4169     border: none ;
4170     border-top : 1px solid silver;
4171     border-bottom : 1px solid silver;
4172 }
4173
4174 div.exampletitle{
4175     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4176     "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4177     "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4178     "Times New Roman", serif;
4179     color: #800000 ;
```

```
4180     text-shadow: none ;
4181     border: none ;
4182 }
4183
4184 div.fancyvrblabel{
4185     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4186         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4187         "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4188         "Times New Roman", serif;
4189     color: #800000 ;
4190     text-shadow: none ;
4191     border: none ;
4192 }
4193
4194
4195
4196 figure {
4197     margin: 5ex 5% 5ex 5% ;
4198     padding: 1ex 1em 1ex 1em ;
4199     background-color: #fffcf5 ;
4200     overflow-x: auto ;
4201     border: none ;
4202 /*     border-top: 1px solid silver; */
4203 /*     border-bottom: 1px solid silver; */
4204 }
4205
4206
4207 div.figurecaption , .lstlisting {
4208     border: none ;
4209 /*     border-top: 1px solid silver ; */
4210 /*     border-bottom: 1px solid silver ; */
4211     background-color: #fffcf5 ;
4212 }
4213
4214 .tnotes {
4215     background: #fffcf5 ;
4216     border-top: 1px solid silver ;
4217     border-bottom: 1px solid silver ;
4218 }
4219
4220 .theorem {
4221     background: none ;
4222 }
4223
4224 .minipage {
4225     background-color: #fffcf5 ;
4226     border: none ;
4227 }
4228
4229 div.floatrow figure { border: none ; }
4230
4231 figure figure { border: none ; }
4232
4233
4234 nav.toc, nav.lof, nav.lot, nav.lol {
```

```

4235 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4236 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4237 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4238 "Times New Roman", serif;
4239 }
4240
4241 div.sidetoccontainer {
4242 font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
4243 "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
4244 "Liberation Serif", "Nimbus Roman No 9 L", "FreeSerif", Times,
4245 "Times New Roman", serif;
4246 background-image: linear-gradient(to bottom, #fffcf5, #C0C0C0);
4247 }
4248
4249 div.sidetocitle{
4250 color: #800000 ;
4251 }
4252
4253 header{
4254 background-color: #e0e0e0 ;
4255 background-image: linear-gradient(to top, #fffcf5, #b0b0b0);
4256 text-align:center ;
4257 }
4258
4259 footer{
4260 background-color: #e0e0e0 ;
4261 background-image: linear-gradient(to bottom, #fffcf5, #b0b0b0);
4262 padding: 2ex 1em 2ex 1em ;
4263 text-align:left ;
4264 }
4265
4266 nav.botnavigation {
4267 background: #dedcd5 ;
4268 border-top: 1px solid black ;
4269 }
4270 \end{filecontents*}
4271 % \end{Verbatim}% for syntax highlighting
4272 \end{LWRwriteconf}

```

39.7 sample_project.css

File `sample_project.css` The project-specific css file. Use with `\CSSFilename`.

If used, this must be present both when compiling the project and also when distributing the HTML files.

```

Config file: 4273 \begin{LWRwriteconf}
4274 \begin{filecontents*}[overwrite]{sample_project.css}
4275 /* ( --- Start of project.css --- ) */
4276 /* ( --- A sample project-specific CSS file for lwarp --- ) */
4277
4278 /* Uncomment one of the following: */
4279 @import url("lwarp.css") ;
4280 /* @import url("lwarp_formal.css") ; */

```

```

4281 /* @import url("lwarp_sagebrush.css") ; */
4282
4283 /* Project-specific CSS setting follow here. */
4284 /* . . . */
4285
4286 /* ( --- End of project.css --- ) */
4287 \end{filecontents*}
4288 % \end{Verbatim}% for syntax highlighting
4289 \end{LWRwriteconf}

```

39.8 lwarp.ist

File lwarp.ist Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The page compositor line is for memoir's `\specialindex`.

```

Config file: 4290 \begin{LWRwriteconf}
4291 \begin{filecontents*}[overwrite]{lwarp.ist}
4292 preamble
4293 "\begin{theindex}
4294   \providecommand*\lettergroupDefault[1]{}
4295   \providecommand*\lettergroup[1]{%
4296     \par\textbf{#1}\par
4297     \nopagebreak
4298   }
4299 "
4300 headings_flag 1
4301 heading_prefix "
4302   \lettergroup{"
4303 heading_suffix "}"
4304 delim_0 ", \hyperindexref{"
4305 delim_1 ", \hyperindexref{"
4306 delim_2 ", \hyperindexref{"
4307 delim_n "}, \hyperindexref{"
4308 delim_r "} -- \hyperindexref{"
4309 delim_t "}"
4310 page_compositor "."
4311 \end{filecontents*}
4312 % \end{Verbatim}% for syntax highlighting
4313 \end{LWRwriteconf}

```

39.9 lwarp.xdy

File lwarp.xdy Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

See:

<https://tex.stackexchange.com/questions/80300/how-can-i-convince-hyperref-and-xindy-to-play-together-nicely>

Config file:

```

4314 \begin{LWRwriteconf}
4315 \begin{filecontents*}[overwrite]{lwarp.xdy}
4316 (require "tex/inputenc/latin.xdy")
4317 (merge-rule "\\PS *" "Postscript")
4318 (require "texindy.xdy")
4319 (require "page-ranges.xdy")
4320 (require "book-order.xdy")
4321 (define-location-class "arabic-page-numbers"
4322   ("arabic-numbers") :min-range-length 1)
4323 (require "makeindex.xdy")
4324 (define-attributes (("hyperindexref")))
4325 (markup-locref :open "\hyperindexref{" :close "}")
4326 (markup-locref :open "\hyperindexref{" :close "}" :attr "hyperpage")
4327 (markup-locref :open "\textbf{\hyperindexref{" :close "}}" :attr "textbf")
4328 (markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
4329 (define-location-class-order ("roman-page-numbers"
4330   "arabic-page-numbers"
4331   "alpha-page-numbers"
4332   "Roman-page-numbers"
4333   "Alpha-page-numbers"
4334   "see"
4335   "seealso"))
4336 \end{filecontents*}
4337 % \end{Verbatim}% for syntax highlighting
4338 \end{LWRwriteconf}

```

39.10 lwarp_one_limage.cmd

File `lwarp_one_limage.cmd` Used by `lwarp` to help make lateximages when using WINDOWS.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The arguments are each of the three fields from `<project>-images.txt`, and also the base name of the source file.

MiKTeX does not allow file `lwarp_one_limage.cmd` to be created directly by *lwarpmk*, so `lwarp_one_limage.txt` is created instead, then copied to `lwarp_one_limage.cmd` by *lwarpmk*. This occurs each time *lwarpmk* used to create lateximages.

Config file:

```

4339 \begin{LWRwriteconf}
4340 \immediate\openout\LWR@quickfile=lwarp_one_limage.txt
4341 \immediate\write\LWR@quickfile{%
4342   pdfseparate -f \LWRpercent 1 -l \LWRpercent 1 \LWRpercent 4_html.pdf %
4343   \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent\LWRpercent d.pdf%
4344 }
4345 \immediate\write\LWR@quickfile{%
4346   pdfcrop --hires \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf %
4347   \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
4348 }

```

```

4349 \immediate\write\LWR@quickfile{%
4350   pdftocairo -svg -noshrink \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf %
4351   \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.svg%
4352 }
4353 \immediate\write\LWR@quickfile{%
4354   del \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
4355 }
4356 \immediate\write\LWR@quickfile{%
4357   del \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf%
4358 }
4359 \immediate\write\LWR@quickfile{exit}
4360 \immediate\closeout\LWR@quickfile
4361 \end{LWRwriteconf}

```

39.11 lwarp_mathjax.txt

(Emulates or patches code by DAVIDE P. CERVONE.)

File `lwarp_mathjax.txt` The default MathJax script used by `lwarp` when using `MATHJAX`. A recent version of MathJax is used, as served by the recommended repository. Adjustments are made to allow \LaTeX to control the equation tags and provide for starred macros.

`\MathJaxFilename` determines which script file is copied into the HTML pages, and defaults to `lwarp_mathjax.txt`. The script files must be present when compiling the project, but do not need to be present when distributing the resulting HTML files.

custom script To generate a custom script, such as to use a local repository, copy `lwarp_mathjax.txt` to a new file, make changes while keeping `lwarp`'s adjustments for equation numbering and starred macros, and use `\MathJaxFilename` to select the new filename.

Config file:

```

4362 \begin{LWRwriteconf}
4363 \begin{filecontents*}[overwrite]{lwarp_mathjax.txt}
4364 <script>
4365 // Lwarp MathJax emulation code
4366 //
4367 // Based on code by Davide P. Cervone.
4368 // Equation numbering: https://github.com/mathjax/MathJax/issues/2427
4369 // Starred and ifnextchar macros: https://github.com/mathjax/MathJax/issues/2428
4370 // \left, \right delimiters: https://github.com/mathjax/MathJax/issues/2535
4371 //
4372 // Modified by Brian Dunn to adjust equation numbering and add subequations.
4373 //
4374 // LaTeX can use \seteqnumber{subequations?}{section}{number} before each equation.
4375 // subequations? is 0 usually, 1 if inside subequations.
4376 // section is a string printed as-is, or empty.
4377 // number is auto-incremented by MathJax between equations.
4378 //
4379 MathJax = {
4380   subequations: "0",
4381   section: "",
4382   loader: {
4383     load: ['[tex]/tagformat', '[tex]/textmacros'],
4384   },
4385   startup: {

```

```

4386 ready() {
4387     // These would be replaced by import commands if you wanted to make
4388     // a proper extension.
4389     const Configuration = MathJax._.input.tex.Configuration.Configuration;
4390     const CommandMap = MathJax._.input.tex.SymbolMap.CommandMap;
4391     const Macro = MathJax._.input.tex.Symbol.Macro;
4392     const TexError = MathJax._.input.tex.TexError.default;
4393     const ParseUtil = MathJax._.input.tex.ParseUtil.default;
4394     const expandable = MathJax._.util.Options.expandable;
4395
4396     // Insert the replacement string into the TeX string, and check
4397     // that there haven't been too many macro substitutions (prevents
4398     // infinite loops).
4399     const useArgument = (parser, text) => {
4400     parser.string = ParseUtil.addArgs(parser, text, parser.string.slice(parser.i));
4401     parser.i = 0;
4402     if (++parser.macroCount > parser.configuration.options.maxMacros) {
4403         throw new TexError('MaxMacroSub1',
4404             'MathJax maximum macro substitution count exceeded; ' +
4405             'is there a recursive macro call?');
4406     }
4407     }
4408
4409     // Create the command map for \ifstar, \ifnextchar, \seteqnumber
4410     new CommandMap('ifstar-ifnextchar-seteqnumber', {
4411         ifstar: 'IfstarFunction',
4412         ifnextchar: 'IfnextcharFunction',
4413         seteqnumber: 'SeteqnumberFunction'
4414     }, {
4415         // This function implements an ifstar macro.
4416         IfstarFunction(parser, name) {
4417             const resultstar = parser.GetArgument(name);
4418             const resultnostar = parser.GetArgument(name);
4419             const star = parser.GetStar(); // true if there is a *
4420             useArgument(parser, star ? resultstar : resultnostar);
4421         },
4422
4423         // This function implements an ifnextchar macro.
4424         IfnextcharFunction(parser, name) {
4425             let whichchar = parser.GetArgument(name);
4426             if (whichchar.match(/^(?:0x[0-9A-F]+|[0-9]+)$/i)) {
4427                 // $ syntax highlighting
4428                 whichchar = String.fromCharCode(parseInt(whichchar));
4429             }
4430             const resultnextchar = parser.GetArgument(name);
4431             const resultnotnextchar = parser.GetArgument(name);
4432             const gotchar = (parser.GetNext() === whichchar);
4433             useArgument(parser, gotchar ? resultnextchar : resultnotnextchar);
4434         },
4435
4436         // This function modifies the equation numbers.
4437         SeteqnumberFunction(parser, name) {
4438             // Get the macro parameters
4439             const star = parser.GetStar(); // true if there is a *
4440             const optBrackets = parser.GetBrackets(name); // contents of optional brackets

```

```

4441     const newsubequations = parser.GetArgument(name); // the subequations argument
4442     const neweqsection = parser.GetArgument(name); // the eq section argument
4443     const neweqnumber = parser.GetArgument(name); // the eq number argument
4444     MathJax.config.subequations=newsubequations; // a string with boolean meaning
4445     MathJax.config.section=neweqsection; // a string with numeric meaning
4446     parser.tags.counter = parser.tags.allCounter = neweqnumber;
4447   }
4448
4449 });
4450
4451 // Create the ifstar-ifnextchar-seteqnumber package
4452 Configuration.create('ifstar-ifnextchar-seteqnumber', {
4453   handler: {macro: ['ifstar-ifnextchar-seteqnumber']}
4454 });
4455
4456 MathJax.startup.defaultReady();
4457
4458 // For forward references:
4459 MathJax.startup.input[0].preFilters.add(({math}) => {
4460   if (math.inputData.recompile){
4461     MathJax.config.subequations = math.inputData.recompile.subequations;
4462     MathJax.config.section = math.inputData.recompile.section;
4463   }
4464 });
4465 MathJax.startup.input[0].postFilters.add(({math}) => {
4466   if (math.inputData.recompile){
4467     math.inputData.recompile.subequations = MathJax.config.subequations;
4468     math.inputData.recompile.section = MathJax.config.section;
4469   }
4470 });
4471
4472 // For \left, \right with unicode-math:
4473 const {DelimiterMap} = MathJax._.input.tex.SymbolMap;
4474 const {Symbol} = MathJax._.input.tex.Symbol;
4475 const {MapHandler} = MathJax._.input.tex.MapHandler;
4476 const delimiter = MapHandler.getMap('delimiter');
4477 delimiter.add('\lBrack', new Symbol('\lBrack', '\u27E6'));
4478 delimiter.add('\rBrack', new Symbol('\rBrack', '\u27E7'));
4479 delimiter.add('\lAngle', new Symbol('\lAngle', '\u27EA'));
4480 delimiter.add('\rAngle', new Symbol('\rAngle', '\u27EB'));
4481 delimiter.add('\lbrbrak', new Symbol('\lbrbrak', '\u2772'));
4482 delimiter.add('\rbrbrak', new Symbol('\rbrbrak', '\u2773'));
4483 delimiter.add('\lbag', new Symbol('\lbag', '\u27C5'));
4484 delimiter.add('\rbag', new Symbol('\rbag', '\u27C6'));
4485 delimiter.add('\lllparenthesis', new Symbol('\lllparenthesis', '\u2987'));
4486 delimiter.add('\rrrparenthesis', new Symbol('\rrrparenthesis', '\u2988'));
4487 delimiter.add('\lllangle', new Symbol('\lllangle', '\u2989'));
4488 delimiter.add('\rrrangle', new Symbol('\rrrangle', '\u298A'));
4489 delimiter.add('\lLbrbrak', new Symbol('\lLbrbrak', '\u27EC'));
4490 delimiter.add('\rRbrbrak', new Symbol('\rRbrbrak', '\u27ED'));
4491 delimiter.add('\lBrace', new Symbol('\lBrace', '\u2983'));
4492 delimiter.add('\rBrace', new Symbol('\rBrace', '\u2984'));
4493 delimiter.add('\lParen', new Symbol('\lParen', '\u2985'));
4494 delimiter.add('\rParen', new Symbol('\rParen', '\u2986'));
4495 delimiter.add('\lbrackubar', new Symbol('\lbrackubar', '\u298B'));

```

```

4496     delimiter.add('\rbrackubar', new Symbol('\rbrackubar', '\u298C'));
4497     delimiter.add('\lbrackultick', new Symbol('\lbrackultick', '\u298D'));
4498     delimiter.add('\rbracklrtick', new Symbol('\rbracklrtick', '\u298E'));
4499     delimiter.add('\lbracklltick', new Symbol('\lbracklltick', '\u298F'));
4500     delimiter.add('\rbrackurtick', new Symbol('\rbrackurtick', '\u2990'));
4501     delimiter.add('\langedot', new Symbol('\langedot', '\u2991'));
4502     delimiter.add('\rangedot', new Symbol('\rangedot', '\u2992'));
4503     delimiter.add('\lparenless', new Symbol('\lparenless', '\u2993'));
4504     delimiter.add('\rparengtr', new Symbol('\rparengtr', '\u2994'));
4505     delimiter.add('\lparengtr', new Symbol('\lparengtr', '\u2995'));
4506     delimiter.add('\Rparenless', new Symbol('\Rparenless', '\u2996'));
4507     delimiter.add('\lblkbrbrak', new Symbol('\lblkbrbrak', '\u2997'));
4508     delimiter.add('\rblkbrbrak', new Symbol('\rblkbrbrak', '\u2998'));
4509     delimiter.add('\lvzigzag', new Symbol('\lvzigzag', '\u29D8'));
4510     delimiter.add('\rvzigzag', new Symbol('\rvzigzag', '\u29D9'));
4511     delimiter.add('\Lvzigzag', new Symbol('\Lvzigzag', '\u29DA'));
4512     delimiter.add('\Rvzigzag', new Symbol('\Rvzigzag', '\u29DB'));
4513     delimiter.add('\lcurvyangle', new Symbol('\lcurvyangle', '\u29FC'));
4514     delimiter.add('\rcurvyangle', new Symbol('\rcurvyangle', '\u29FD'));
4515     delimiter.add('\Vvert', new Symbol('\Vvert', '\u2980'));
4516   } // ready
4517 }, // startup
4518
4519 tex: {
4520   packages: {'[+]': ['tagformat', 'ifstar-ifnextchar-setequnumber', 'textmacros']},
4521   tags: "ams",
4522   tagformat: {
4523     number: function (n) {
4524       if(MathJax.config.subequations==0)
4525         return(MathJax.config.section + n);
4526       else
4527         return(MathJax.config.section + String.fromCharCode(96+n));
4528     },
4529   },
4530 }
4531 }
4532 </script>
4533
4534 <script
4535   id="MathJax-script"
4536   src="https://cdn.jsdelivr.net/npm/mathjax@3/es5/tex-ctml.js"
4537 ></script>
4538 \end{filecontents*}
4539 % \end{Verbatim}% for syntax highlighting
4540 \end{LWRwriteconf}

```

39.12 lwarpmk.lua — lwarpmk option

Opt lwarpmk Creates a local copy of *lwarpmk*.

Prog lwarpmk Command-line utility to process lwarp files and images.

[parallel processing](#) lateximages and svg math images are generated using multiple processes in parallel. For UNIX and LINUX, every 32 images the wait command is issued to wait for the pre-

vious batch of images to finish processing before starting a new batch. For WINDOWS, every 32 images one task is dispatched with

```
START /B /WAIT /BELOWNORMAL
```

which causes the operating system to wait until this lesser-priority tasks finishes, hopefully also waiting for the normal priority tasks which were already in progress to also complete. Afterwards, the next batch of images is started.

The following is only generated if the `lwarpmk` option was given to `lwarp`.

```
4541 \begin{LWRcreate{lwarpmk}

4542 \begin{filecontents*}[overwrite]{lwarpmk.lua}
4543 #!/usr/bin/env texlua
4544
4545 -- Copyright 2016-2020 Brian Dunn
4546
4547
4548 printversion = "v0.893"
4549 requiredconfversion = "2" -- also at *lwarpmk.conf
4550
4551 function printhelp ()
4552 print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help.");
4553 end
4554
4555
4556 function printusage ()
4557 --
4558 -- Print the usage of the lwarpmk command:
4559 --
4560 print ( [[
4561
4562 lwarpmk print [-p project]: Compile the print version if necessary.
4563 lwarpmk print1 [-p project]: Forced single compile of the print version.
4564 lwarpmk printindex [-p project]: Process print indexes.
4565 lwarpmk printglossary [-p project]: Process the glossary for the print version.
4566 lwarpmk html [-p project]: Compile the HTML version if necessary.
4567 lwarpmk html1 [-p project]: Forced single compile of the HTML version.
4568 lwarpmk htmlindex [-p project]: Process HTML indexes.
4569 lwarpmk htmlglossary [-p project]: Process the glossary for the html version.
4570 lwarpmk again [-p project]: Touch the source code to trigger recompiles.
4571 lwarpmk limages [-p project]: Process the "lateximages" created by lwarp.sty.
4572 lwarpmk pdftohtml [-p project]:
4573     For use with latexmk or a Makefile:
4574     Converts project_html.pdf to project_html.html and individual HTML files.
4575     Finishes the HTML conversion even if there was a compile error.
4576 lwarpmk pdftosvg <list of file names>: Converts each PDF file to SVG.
4577 lwarpmk epstopdf <list of file names>: Converts each EPS file to PDF.
4578 lwarpmk clean [-p project]: Remove *.aux, *.toc, *.lof/t,
4579     *.idx, *.ind, *.bbl, *.log, *_html_inc.*, .gl*,
4580     *_html.pdf, *_html.html, *_html.sidetoc
4581 lwarpmk cleanall [-p project]: Remove auxiliary files, project.pdf, *.html
4582 lwarpmk cleanlimages: Removes all images from the "lateximages" directory.
4583 lwarpmk -v: Print the version number.
```

```
4584 lwarpmk -h: Print this help message.
4585 lwarpmk --help: Print this help message.
4586
4587 ]] )
4588 -- printconf ()
4589 end
4590
4591
4592 function splitfilename ( pathandfilename )
4593 --
4594 -- Separates out the path and extension from a filename.
4595 -- Returns path, filename with extension, and extension.
4596 -- Ex: thispath, thisfilename, thisextension = splitfilename ("path/to/filename.ext")
4597 --
4598 -- https://www.fhug.org.uk/wiki/wiki/doku.php?id=plugins:code\_snippets:
4599 --     split_filename_in_to_path_filename_and_extension
4600 --
4601     if lfs.attributes(pathandfilename,"mode") == "directory" then
4602         local strPath = pathandfilename:gsub("[\\/]$", "") -- $(syntax highlighting)
4603         return strPath.."\\", "", ""
4604     end
4605     pathandfilename = pathandfilename.."."
4606     return pathandfilename:match("^(-)([^\\"/]-)%.(^[^\\"/%.]-)?.$")
4607 end
4608
4609
4610 function splitfile (destfile,sourcefile)
4611 --
4612 -- Split one large sourcefile into a number of files,
4613 -- starting with destfile.
4614 -- The file is split at each occurrence of <!--|Start file|newfilename|*
4615 --
4616 print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
4617 local sfile = io.open(sourcefile)
4618 io.output(destfile)
4619 for line in sfile:lines() do
4620 i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*|)" ) ;
4621 if ( (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then
4622     -- split the file
4623     io.output(newfilename) ;
4624 else
4625     -- not a splitpoint
4626     io.write (line .. "\n") ;
4627 end
4628 end -- do
4629 io.close(sfile)
4630 end -- function
4631
4632
4633 function cvalueerror ( line, linenum , cvalue )
4634 --
4635 -- Incorrect value, so print an error and exit.
4636 --
4637     print ("lwarpmk: ===")
4638     print ("lwarpmk: " .. linenum .. " : " .. line ) ;
```

```
4639     print (
4640         "lwarpmk: incorrect variable value \"" .. cvalue ..
4641         "\" in lwarpmk.conf.\n"
4642     ) ;
4643     print ("lwarpmk: ===")
4644 --     printconf () ;
4645     os.exit(1) ;
4646 end
4647
4648
4649 function printhowtorecompile ()
4650 -- Tells the user how to recompile to regenerate the configuration files.
4651     print ("lwarpmk: The configuration files lwarpmk.conf and "..sourcename.."lwarpmkconf" )
4652     print ("lwarpmk:  must be updated. To do so, recompile" )
4653     print ("lwarpmk:  ", sourcename.."tex" )
4654     if ( printlatexcmd == "" ) then
4655         print ("lwarpmk:  using xe/luatex/pdflatex," )
4656     else
4657         print ("lwarpmk:  using the command:")
4658         print ("lwarpmk:  ", printlatexcmd )
4659     end
4660     print ("lwarpmk:  then use lwarpmk again.")
4661 end -- printhowtorecompile
4662
4663
4664 function ignoreconf ()
4665 -- Global argument index
4666 argindex = 2
4667 end
4668
4669 function loadconf ()
4670 --
4671 -- Load settings from the project's "lwarpmk.conf" file:
4672 --
4673 -- Default configuration filename:
4674 local conffile = "lwarpmk.conf"
4675 local confroot = "lwarpmk"
4676 -- Global argument index
4677 argindex = 2
4678 -- Optional configuration filename:
4679 if ( arg[argindex] == "-p" ) then
4680     argindex = argindex + 1
4681     confroot = arg[argindex]
4682     conffile = confroot.."lwarpmkconf"
4683     argindex = argindex + 1
4684 end
4685 -- Additional defaults:
4686 confversion = "0"
4687 opsystem = "Unix"
4688 imagesdirectory = "lateximages"
4689 imagesname = "image-"
4690 latexmk = "false"
4691 printlatexcmd = ""
4692 HTMLlatexcmd = ""
4693 printindexcmd = ""
```

```
4694 HTMLindexcmd = ""
4695 latexmkindexcmd = ""
4696 -- to be removed:
4697 -- indexprog = "makeindex"
4698 -- makeindexstyle = "lwarp.ist"
4699 -- xindylanguage = "english"
4700 -- xindycodepage = "utf8"
4701 -- xindystyle = "lwarp.xdy"
4702 -- pdftotextenc = "UTF-8"
4703 glossarycmd = "makeglossaries"
4704 -- Verify the file exists:
4705 if (lfs.attributes(conffile,"mode")==nil) then
4706     -- file not exists
4707     print ("lwarpmk: ===")
4708     print ("lwarpmk: File \"\" .. conffile ..\"\" does not exist.")
4709     print ("lwarpmk: Move to the project's source directory,")
4710     print ("lwarpmk: recompile using pdflatex, xelatex, or luatex,")
4711     print ("lwarpmk: then try using lwarpmk again.")
4712     if ( arg[argindex] ~= nil ) then
4713         print (
4714             "lwarpmk: (\"\" .. confroot ..
4715             "\"\" does not appear to be a project name.)"
4716         )
4717     end
4718     print ("lwarpmk: ===")
4719     printhelp () ;
4720     os.exit(1) -- exit the entire lwarpmk script
4721 else -- file exists
4722 -- Read the file:
4723 print ("lwarpmk: Reading " .. conffile ..".")
4724 local cfile = io.open(conffile)
4725 -- Scan each line, parsing each line as: name = [[string]]
4726 local linenum = 0
4727 for line in cfile:lines() do -- scan lines
4728 linenum = linenum + 1
4729 i,j,cvarname,cvalue = string.find (line,"([%w-]*)%s*=%s*%[[^%]]*)%]") ;
4730 -- Error if incorrect enclosing characters:
4731 if ( i == nil ) then
4732     print ("lwarpmk: ===")
4733     print ("lwarpmk: " .. linenum .. " : " .. line ) ;
4734     print ("lwarpmk: Incorrect entry in " .. conffile ..".\n" ) ;
4735     print ("lwarpmk: ===")
4736 --     printconf () ;
4737     os.exit(1) ;
4738 end -- nil
4739 if ( cvarname == "confversion" ) then
4740     confversion = cvalue
4741 elseif ( cvarname == "opssystem" ) then
4742     -- Verify choice of opssystem:
4743     if ( (cvalue == "Unix") or (cvalue == "Windows") ) then
4744         opssystem = cvalue
4745     else
4746         cvalueerror ( line, linenum , cvalue )
4747     end
4748 elseif ( cvarname == "sourcename" ) then sourcename = cvalue
```

```
4749 elseif ( cvarname == "homehtmlfilename" ) then homehtmlfilename = cvalue
4750 elseif ( cvarname == "htmlfilename" ) then htmlfilename = cvalue
4751 elseif ( cvarname == "imagesdirectory" ) then imagesdirectory = cvalue
4752 elseif ( cvarname == "imagesname" ) then imagesname = cvalue
4753 elseif ( cvarname == "latexmk" ) then latexmk = cvalue
4754 elseif ( cvarname == "printlatexcmd" ) then printlatexcmd = cvalue
4755 elseif ( cvarname == "HTMLlatexcmd" ) then HTMLlatexcmd = cvalue
4756 elseif ( cvarname == "printindexcmd" ) then printindexcmd = cvalue
4757 elseif ( cvarname == "HTMLindexcmd" ) then HTMLindexcmd = cvalue
4758 elseif ( cvarname == "latexmkindexcmd" ) then latexmkindexcmd = cvalue
4759 elseif ( cvarname == "glossarycmd" ) then glossarycmd = cvalue
4760 elseif ( cvarname == "pdftotextenc" ) then pdftotextenc = cvalue
4761 else
4762     print ("lwarpmk: ===")
4763     print ("lwarpmk: " .. linenum .. " : " .. line ) ;
4764     print (
4765         "lwarpmk: Incorrect variable name \"\" .. cvarname .. "\" in " ..
4766         conffile .. ".\n"
4767     ) ;
4768     print ("lwarpmk: ===")
4769 --     printconf () ;
4770 os.exit(1) ;
4771 end -- cvarname
4772 end -- do scan lines
4773 io.close(cfile)
4774 end -- file exists
4775 -- Error if sourcename is "lwarp".
4776 -- This could happen if a local copy of lwarp has recently been recompiled.
4777 if sourcename=="lwarp" then
4778     print ("lwarpmk: ===")
4779     print ("lwarpmk: lwarp.sty has recently been recompiled in this directory,")
4780     print ("lwarpmk: and \"lwarpmk.conf\" is no longer set for your own project.")
4781     print ("lwarpmk: (Perhaps you are not in your project's directory?)")
4782     print ("lwarpmk: In your project directory, recompile your project")
4783     print ("lwarpmk: using pdf/lua/xelatex <projectname>.")
4784     print ("lwarpmk: After a recompile, \"lwarpmk.conf\" will be set for your project,")
4785     print ("lwarpmk: and you may again use lwarpmk.")
4786     print ("lwarpmk: ===")
4787     os.exit(1)
4788 end -- sourcename of "lwarp"
4789 -- Select some operating-system commands:
4790 if opsystem=="Unix" then -- For Unix / Linux / Mac OS:
4791     rmname = "rm"
4792     mvname = "mv"
4793     cpname = "cp"
4794     touchnamepre = "touch"
4795     touchnamepost = ""
4796     newtouchname = "touch"
4797     dirslash = "/"
4798     opquote= "\""
4799     cmdgroupopenname = " ( "
4800     cmdgroupclosename = " ) "
4801     seqname = " && "
4802     bgname = " &"
4803 elseif opsystem=="Windows" then -- For Windows
```

```
4804     rmname = "DEL"
4805     mvname = "MOVE"
4806     cpname = "COPY"
4807     touchnamepre = "COPY /b"
4808     touchnamepost = "+,,"
4809     newtouchname = "echo empty >"
4810     dirslash = "\\\"
4811     opquote= "\""
4812     cmdgroupopenname = ""
4813     cmdgroupclosename = ""
4814     seqname = " & "
4815     bgname = ""
4816 else
4817     print ("lwarpmk: ===")
4818     print ("lwarpmk: Select Unix or Windows for opsystem." )
4819     print ("lwarpmk: ===")
4820     os.exit(1)
4821 end --- for Windows
4822 -- Warning if the operating system does not appear to be correct,
4823 -- in case files were transferred to another system.
4824 if ( (package.config:sub(1,1)) ~= dirslash ) then
4825     print ("lwarpmk: ===")
4826     print ("lwarpmk: It appears that lwarpmk.conf is for a different operating system." )
4827     printhowtorecompile ()
4828     print ("lwarpmk: ===")
4829     os.exit(1)
4830 end
4831 -- Error if the configuration file's version is not current:
4832 if ( confversion ~= requiredconfversion ) then
4833     print ("lwarpmk: ===")
4834     printhowtorecompile ()
4835     print ("lwarpmk: ===")
4836     os.exit(1)
4837 end
4838 end -- loadconf
4839
4840
4841 function executecheckerror ( executecommands , errormessage )
4842 --
4843 -- Execute an operating system call,
4844 -- and maybe exit with an error message.
4845 --
4846 local err
4847 err = os.execute ( executecommands )
4848 if ( err ~= 0 ) then
4849     print ("lwarpmk: ===")
4850     print ("lwarpmk: " .. errormessage )
4851     print ("lwarpmk: ===")
4852     os.exit(1)
4853 end
4854 end -- executecheckerror
4855
4856
4857 function refreshdate ()
4858 os.execute(touchnamepre .. " " .. sourcename .. ".tex " .. touchnamepost)
```

```
4859 end
4860
4861
4862
4863 function reruntoget (filesource)
4864 --
4865 -- Scan the LaTeX log file for the phrase "Rerun to get",
4866 -- indicating that the file should be compiled again.
4867 -- Return true if found.
4868 --
4869 local fsource = io.open(filesource)
4870 for line in fsource:lines() do
4871 if ( string.find(line,"Rerun to get") ~= nil ) then
4872     io.close(fsource)
4873     return true
4874 end -- if
4875 end -- do
4876 io.close(fsource)
4877 return false
4878 end
4879
4880
4881
4882 function onetime (latexcmd, fsuffix)
4883 --
4884 -- Compile one time, return true if should compile again.
4885 -- fsuffix is "" for print, "_html" for HTML output.
4886 --
4887 print("lwarpmk: Compiling with: " .. latexcmd)
4888 executecheckerror (
4889     latexcmd ,
4890     "Compile error."
4891 )
4892 return (reruntoget(sourcename .. fsuffix .. ".log") ) ;
4893 end
4894
4895
4896 function manytimes (latexcmd, fsuffix)
4897 --
4898 -- Compile up to five times.
4899 -- fsuffix is "" for print, "_html" for HTML output
4900 --
4901 if onetime(latexcmd, fsuffix) == true then
4902 if onetime(latexcmd, fsuffix) == true then
4903 if onetime(latexcmd, fsuffix) == true then
4904 if onetime(latexcmd, fsuffix) == true then
4905 if onetime(latexcmd, fsuffix) == true then
4906 end end end end end
4907 end
4908
4909
4910 function verifyfileexists (filename)
4911 --
4912 -- Exit if the given file does not exist.
4913 --
```

```
4914 if (lfs.attributes ( filename , "modification" ) == nil ) then
4915     print ("lwarpmk: ===")
4916     print ("lwarpmk: " .. filename .. " not found." ) ;
4917     print ("lwarpmk: ===")
4918     os.exit (1) ;
4919 end
4920 end
4921
4922
4923
4924 function pdftohtml ()
4925 --
4926 -- Convert <project>_html.pdf into HTML files:
4927 --
4928 -- Convert to text:
4929 print ("lwarpmk: Converting " .. sourcename
4930     .. "_html.pdf to " .. sourcename .. "_html.html")
4931 os.execute("pdftotext -enc " .. pdftotextenc .. " -nopgbrk -layout "
4932     .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
4933 -- Split the result into individual HTML files:
4934 splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
4935 end
4936
4937
4938 function removeaux ()
4939 --
4940 -- Remove auxiliary files:
4941 -- All .aux files are removed since there may be many bbl*.aux files.
4942 -- Also removes sourcename_html.pdf, sourcename_html.html,
4943 -- and sourcename_html.sidetoc, plus comment_*.cut.
4944 --
4945 os.execute ( rmname .. " *.aux " ..
4946     sourcename .. ".toc " .. sourcename .. "_html.toc " ..
4947     sourcename .. ".lof " .. sourcename .. "_html.lof " ..
4948     sourcename .. ".lot " .. sourcename .. "_html.lot " ..
4949     sourcename .. ".bbl " .. sourcename .. "_html.bbl " ..
4950     " *.idx " ..
4951     " *.ind " ..
4952     sourcename .. ".ps " .. sourcename .. "_html.ps " ..
4953     sourcename .. ".log " .. sourcename .. "_html.log " ..
4954     sourcename .. ".gl*" .. sourcename .. "_html.gl*" ..
4955     sourcename .. "_html.pdf " ..
4956     sourcename .. "_html.html " ..
4957     sourcename .. "_html.sidetoc " ..
4958     " *_html_inc.* " ..
4959     " comment_*.cut"
4960 )
4961 end
4962
4963 function checkhtmlpdfexists ()
4964 --
4965 -- Error if the HTML document does not exist.
4966 -- The lateximages are drawn from the HTML PDF version of the document,
4967 -- so "lwarpmk html" must be done before "lwarpmk limages".
4968 --
```

```
4969 local htmlpdffile = io.open(sourcename .. "_html.pdf", "r")
4970 if ( htmlpdffile == nil ) then
4971     print ("")
4972     print ("lwarpmk: ===")
4973     print ("lwarpmk: The HTML version of the document does not exist.")
4974     print ("lwarpmk: Enter \"lwarpmk html\" to compile the HTML version.")
4975     print ("lwarpmk: ===")
4976     os.exit(1)
4977 end
4978 io.close (htmlpdffile)
4979 end -- checkhtmlpdfexists
4980
4981
4982 function warnlimages ()
4983 --
4984 -- Warning of a missing <sourcename>-images.txt file:
4985     print ("lwarpmk: ===")
4986     print ("lwarpmk: \"\" .. sourcename .. "-images.txt\" does not exist.")
4987     print ("lwarpmk: Your project does not use SVG math or other lateximages,")
4988     print ("lwarpmk: or the file has been deleted somehow.")
4989     print ("lwarpmk: Use \"lwarpmk html1\" to recompile your project")
4990     print ("lwarpmk: and recreate \"\" .. sourcename .. "-images.txt\".")
4991     print ("lwarpmk: If your project does not use SVG math or other lateximages,")
4992     print ("lwarpmk: then \"\" .. sourcename .. "-images.txt\" will never exist, and")
4993     print ("lwarpmk: \"lwarpmk limages\" will not be necessary.")
4994     print ("lwarpmk: ===")
4995 end -- warnlimages
4996
4997
4998 function warnlimagesrecompile ()
4999 -- Warning if must recompile before creating limages:
5000     print ("")
5001     print ("lwarpmk: ===")
5002     print ("lwarpmk: Cross-references are not yet correct.")
5003     print ("lwarpmk: The document must be recompiled before creating the lateximages.")
5004     print ("lwarpmk: Enter \"lwarpmk html1\" again, then try \"lwarpmk limages\" again.")
5005     print ("lwarpmk: ===")
5006 end --warnlimagesrecompile
5007
5008
5009 function checklimages ()
5010 --
5011 -- Check <sourcename>.txt to see if need to recompile first.
5012 -- If any entry has a page number of zero, then there were incorrect images.
5013 --
5014 print ("lwarpmk: Checking for a valid \" .. sourcename .. "-images.txt file.")
5015 local limagesfile = io.open(sourcename .. "-images.txt", "r")
5016 if ( limagesfile == nil ) then
5017     warnlimages ()
5018     os.exit(1)
5019 end
5020 -- Track warning to recompile if find a page 0
5021 local pagezerowarning = false
5022 -- Scan <sourcename>.txt
5023 for line in limagesfile:lines() do
```

```

5024 -- lwimpage is the page number in the PDF which has the image
5025 -- lwimghash is true if this filename is a hash
5026 -- lwimname is the lateximage filename root to assign for the image
5027 i,j,lwimpage,lwimghash,lwimname = string.find (line,"|(.*)|(.*)|(.*)|")
5028 -- For each entry:
5029 if ( (i~=nil) ) then
5030     -- If the page number is 0, image references are incorrect
5031     -- and must recompile the source document:
5032     if ( lwimpage == "0" ) then
5033         pagezerowarning = true
5034     end
5035 end -- if i~=nil
5036 end -- do
5037 -- The last line should be |end|end|end|.
5038 -- If not, the compile must have aborted, and the images are incomplete.
5039 if ( lwimpage ~= "end" ) then
5040     warnlimagesrecompile()
5041     os.exit(1) ;
5042 end
5043 if ( pagezerowarning ) then
5044     warnlimagesrecompile()
5045     os.exit(1) ;
5046 end -- pagezerowarning
5047 end -- checklimages
5048
5049
5050 function createuniximage ( lwimgfullname )
5051 --
5052 -- Create one lateximage for Unix / Linux / Mac OS.
5053 --
5054 executecheckerror (
5055     cmdgroupopenname ..
5056     "pdfseparate -f " .. lwimpage .. " -l " .. lwimpage .. " " ..
5057     sourcename .. "_html.pdf" " ..
5058     imagesdirectory .. dirslash .. "lateximagetemp-%d" .. ".pdf" ..
5059     seqname ..
5060     -- Crop the image:
5061     "pdfcrop --hires " .. imagesdirectory .. dirslash .. "lateximagetemp-" ..
5062     lwimpage .. ".pdf" " ..
5063     imagesdirectory .. dirslash .. lwimname .. ".pdf" ..
5064     seqname ..
5065     -- Convert the image to svg:
5066     "pdftocairo -svg -noshrink " .. imagesdirectory .. dirslash .. lwimname .. ".pdf" " ..
5067     imagesdirectory .. dirslash .. lwimname .. ".svg" ..
5068     seqname ..
5069     -- Remove the temporary files:
5070     rmname .. " " .. imagesdirectory .. dirslash .. lwimname .. ".pdf" .. seqname ..
5071     rmname .. " " .. imagesdirectory .. dirslash .. "lateximagetemp-" .. lwimpage .. ".pdf" ..
5072     cmdgroupclosename .. " >/dev/null " .. bgnam
5073     ,
5074     "File error trying to convert " .. lwimgfullname
5075 )
5076 -- Every 32 images, wait for completion at below normal priority,
5077 -- allowing other image tasks to catch up.
5078 numimageprocesses = numimageprocesses + 1

```

```

5079 if ( numimageprocesses > 32 ) then
5080     numimageprocesses = 0
5081     print ( "lwarpmk: waiting" )
5082     executecheckerror ( "wait" , "File error trying to wait.")
5083 end
5084 end -- createuniximage
5085
5086
5087 function createwindowsimage ( lwimgfullname )
5088 --
5089 -- Create one lateximage for Windows.
5090 --
5091 -- Every 32 images, wait for completion at below normal priority,
5092 -- allowing other image tasks to catch up.
5093 numimageprocesses = numimageprocesses + 1
5094 if ( numimageprocesses > 32 ) then
5095     numimageprocesses = 0
5096     thiswaitcommand = "/WAIT /BELOWNORMAL"
5097     print ( "lwarpmk: waiting" )
5098 else
5099     thiswaitcommand = ""
5100 end
5101 -- Execute the image generation command
5102 executecheckerror (
5103     "start /B " .. thiswaitcommand .. " \"\" lwarp_one_limage " ..
5104     lwimgpage .. " " ..
5105     lwimgghash .. " " ..
5106     lwimgname .. " " ..
5107     sourcename .. " <nul >nul"
5108     ,
5109     "File error trying to create image."
5110 )
5111 end -- createwindowsimage
5112
5113
5114 function createonelateximage ( line )
5115 --
5116 -- Given the next line of <sourcename>.txt, convert a single image.
5117 --
5118 -- lwimgpage is the page number in the PDF which has the image
5119 -- lwimgghash is true if this filename is a hash
5120 -- lwimgname is the lateximage filename root to assign for the image
5121 i,j,lwimgpage,lwimgghash,lwimgname = string.find (line,"|(.*)|(.*)(.*)|")
5122 -- For each entry:
5123 if ( (i~=nil) ) then
5124     -- Skip if the page number is 0:
5125     if ( lwimgpage == "0" ) then
5126         pagezerowarning = true
5127     -- Skip if the page number is "end":
5128     else if ( lwimgpage == "end" ) then
5129     else
5130         -- Skip is this image is hashed and already exists:
5131         local lwimgfullname = imagesdirectory .. dirslash .. lwimgname .. ".svg"
5132         if (
5133             (lwimgghash ~= "true") or

```

```
5134         (lfs.attributes(lwimgfullname,"mode")==nil) -- file not exists
5135     )
5136     then -- not hashed or not exists:
5137         -- Print the name of the file being generated:
5138         print ( "lwarpmk: " .. lwimgname )
5139         -- Touch/create the dest so that only once instance tries to build it:
5140         executecheckerror (
5141             newtouchname .. " " .. lwimgfullname ,
5142             "File error trying to touch " .. lwimgfullname
5143         )
5144         -- Separate out the image into its own single-page pdf:
5145         if opsystem=="Unix" then
5146             createuniximage (lwimgfullname)
5147         elseif opsystem=="Windows" then
5148             createwindowsimage (lwimgfullname)
5149         end
5150     end -- not hashed or not exists
5151 end -- not page "end"
5152 end -- not page 0
5153 end -- not nil
5154 end -- createonelateximage
5155
5156
5157 function createlateximages ()
5158 --
5159 -- Create lateximages based on <sourcename>-images.txt:
5160 --
5161 -- See if the document must be recompiled first:
5162 checklimages ()
5163 -- See if the HTML version exists:
5164 checkhtmlpdfexists ()
5165 -- Attempt to create the lateximages:
5166 print ("lwarpmk: Creating lateximages.")
5167 local limagesfile = io.open(sourcename .. "-images.txt", "r")
5168 if ( limagesfile == nil ) then
5169     warnlimages ()
5170     os.exit(1)
5171 end
5172 -- Create the lateximages directory, ignore error if already exists
5173 err = os.execute("mkdir " .. imagesdirectory)
5174 -- For Windows, create lwarp_one_limage.cmd from lwarp_one_limage.txt:
5175 if opsystem=="Windows" then
5176     executecheckerror (
5177         cpname .. " lwarp_one_limage.txt lwarp_one_limage.cmd" ,
5178         "File error trying to copy lwarp_one_limage.txt to lwarp_one_limage.cmd"
5179     )
5180 end -- create lwarp_one_limage.cmd
5181 -- Track the number of parallel processes
5182 numimageprocesses = 0
5183 -- Track warning to recompile if find a page 0
5184 pagezerowarning = false
5185 -- Scan <sourcename>.txt
5186 for line in limagesfile:lines() do
5187     createonelateximage ( line )
5188 end -- do
```

```
5189 io.close(limagesfile)
5190 print ( "lwarpmk limages: ===")
5191 print ( "lwarpmk limages: Wait a moment for the images to complete" )
5192 print ( "lwarpmk limages:  before reloading the page." )
5193 print ( "lwarpmk limages: ===")
5194 print ( "lwarpmk limages: Done." )
5195 if ( pagezerowarning == true ) then
5196     print ( "lwarpmk limages: WARNING: Images will be incorrect." )
5197     print ( "lwarpmk limages:  Enter \"lwarpmk cleanlimages\", then" )
5198     print ( "lwarpmk limages:  recompile the document one more time, then" )
5199     print ( "lwarpmk limages:  repeat \"lwarpmk images\" again." )
5200 end -- pagezerowarning
5201 end -- function
5202
5203
5204 function convertepstopdf ()
5205 --
5206 -- Converts EPS files to PDF files.
5207 -- The filenames are arg[argindex] and up.
5208 -- arg[1] is the command "epstopdf".
5209 --
5210 ignoreconf ()
5211 for i = argindex , #arg do
5212     if (lfs.attributes(arg[i],"mode")==nil) then
5213         print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
5214     else
5215         print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
5216         thispath, thisfilename, thisextension = splitfilename(arg[i])
5217         if ( thispath == nil ) then
5218             os.execute ( "epstopdf " .. arg[i] )
5219         else
5220             os.execute (
5221                 "epstopdf " ..
5222                 thispath .. thisfilename .. "." .. thisextension .. " " ..
5223                 thispath .. thisfilename .. ".pdf"
5224             )
5225         end
5226     end -- if
5227 end -- do
5228 end --function
5229
5230
5231 function convertpdf2svg ()
5232 --
5233 -- Converts PDF files to SVG files.
5234 -- The filenames are arg[argindex] and up.
5235 -- arg[1] is the command "pdf2svg".
5236 --
5237 ignoreconf ()
5238 for i = argindex , #arg do
5239     if (lfs.attributes(arg[i],"mode")==nil) then
5240         print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
5241     else
5242         print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
5243         thispath, thisfilename, thisextension = splitfilename(arg[i])
```

```
5244     if ( thispath == nil ) then
5245         os.execute ( "pdftocairo -svg " .. arg[i] )
5246     else
5247         os.execute (
5248             "pdftocairo -svg " ..
5249             thispath .. thisfilename .. "." .. thisextension .. " " ..
5250             thispath .. thisfilename .. ".svg"
5251         )
5252     end
5253 end -- if
5254 end -- do
5255 end --function
5256
5257
5258 -- Force an update and conclude processing:
5259 function updateanddone ()
5260 print ("lwarpmk: Forcing an update of " .. sourcename .. ".tex.")
5261 refreshdate ()
5262 print ("lwarpmk: " .. sourcename .. ".tex is ready to be recompiled.")
5263 print ("lwarpmk: Done.")
5264 end -- function
5265
5266
5267 -- Start of the main code: --
5268
5269
5270 -- lwarpmk --version :
5271
5272 if (arg[1] == "--version") then
5273 print ( "lwarpmk: " .. printversion )
5274
5275 else -- not --version
5276
5277
5278 -- print intro:
5279
5280 print ("lwarpmk: " .. printversion .. " Automated make for the LaTeX Lwarp package.")
5281
5282
5283 -- lwarpmk print:
5284
5285 if arg[1] == "print" then
5286 loadconf ()
5287 if ( latexmk == "true" ) then
5288     print ("lwarpmk: Compiling with: " .. printlatexcmd)
5289     executecheckerror (
5290         printlatexcmd ,
5291         "Compile error."
5292     )
5293     print ("lwarpmk: Done.")
5294 else -- not latexmk
5295     verifyfileexists (sourcename .. ".tex") ;
5296     -- See if up to date:
5297     if (
5298         ( lfs.attributes ( sourcename .. ".pdf" , "modification" ) == nil ) or
```

```
5299     (
5300         lfs.attributes ( sourcename .. ".tex" , "modification" ) >
5301         lfs.attributes ( sourcename .. ".pdf" , "modification" )
5302     )
5303 ) then
5304     -- Recompile if not yet up to date:
5305     manytimes(printlatexcmd, "")
5306     print ("lwarpmk: Done.");
5307 else
5308     print ("lwarpmk: " .. sourcename .. ".pdf is up to date.");
5309 end
5310 end -- not latexmk
5311
5312
5313 -- lwarpmk print1:
5314
5315 elseif arg[1] == "print1" then
5316     loadconf ()
5317     verifyfileexists (sourcename .. ".tex");
5318     onetime(printlatexcmd, "")
5319     print ("lwarpmk: Done.");
5320
5321
5322 -- lwarpmk printindex:
5323 -- Compile the index then touch the source
5324 -- to trigger a recompile of the document:
5325
5326 elseif arg[1] == "printindex" then
5327 loadconf ()
5328 os.execute ( printindexcmd )
5329 print ("lwarpmk: -----")
5330 updateanddone ()
5331
5332
5333 -- lwarpmk printglossary:
5334 -- Compile the glossary then touch the source
5335 -- to trigger a recompile of the document:
5336
5337 elseif arg[1] == "printglossary" then
5338 loadconf ()
5339 print ("lwarpmk: Processing the glossary.")
5340
5341 os.execute(glossarycmd .. " " .. sourcename)
5342 updateanddone ()
5343
5344
5345 -- lwarpmk html:
5346
5347 elseif arg[1] == "html" then
5348 loadconf ()
5349 if ( latexmk == "true" ) then
5350     print ("lwarpmk: Compiling with: " .. HTMLlatexcmd)
5351     executecheckerror (
5352         HTMLlatexcmd ,
5353         "Compile error."
```

```
5354 )
5355 pdftohtml ()
5356 print ("lwarpmk: Done.")
5357 else -- not latexmk
5358   verifyfileexists ( sourcename .. ".tex" ) ;
5359   -- See if exists and is up to date:
5360   if (
5361     ( lfs.attributes ( homehtmlfilename .. ".html" , "modification" ) == nil ) or
5362     (
5363       lfs.attributes ( sourcename .. ".tex" , "modification" ) >
5364       lfs.attributes ( homehtmlfilename .. ".html" , "modification" )
5365     )
5366   ) then
5367     -- Recompile if not yet up to date:
5368     manytimes(HTMLlatexcmd, "_html")
5369     pdftohtml ()
5370     print ("lwarpmk: Done.")
5371   else
5372     print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
5373   end
5374 end -- not latexmk
5375
5376
5377 -- lwarpmk html1:
5378
5379 elseif arg[1] == "html1" then
5380   loadconf ()
5381   verifyfileexists ( sourcename .. ".tex" ) ;
5382   onetime(HTMLlatexcmd, "_html")
5383   pdftohtml ()
5384   print ("lwarpmk: Done.")
5385
5386
5387 -- lwarpmk pdftohtml:
5388 elseif arg[1] == "pdftohtml" then
5389   loadconf ()
5390   pdftohtml ()
5391
5392
5393 -- lwarpmk htmlindex:
5394 -- Compile the index then touch the source
5395 -- to trigger a recompile of the document:
5396
5397 elseif arg[1] == "htmlindex" then
5398   loadconf ()
5399   os.execute ( HTMLindexcmd )
5400   print ("lwarpmk: -----")
5401   updateanddone ()
5402
5403
5404 -- lwarpmk htmlglossary:
5405 -- Compile the glossary then touch the source
5406 -- to trigger a recompile of the document.
5407 -- The <sourcename>.xdy file is created by the glossaries package.
5408
```

```
5409 elseif arg[1] == "htmlglossary" then
5410 loadconf ()
5411 print ("lwarpmk: Processing the glossary.")
5412 os.execute(glossarycmd .. " " .. sourcename .. "_html")
5413 updateanddone ()
5414
5415
5416 -- lwarpmk limages:
5417 -- Scan the <sourcename>.txt file to create lateximages.
5418
5419 elseif arg[1] == "limages" then
5420 loadconf ()
5421 print ("lwarpmk: Processing images.")
5422 createlateximages ()
5423 print ("lwarpmk: Done.")
5424
5425
5426 -- lwarpmk again:
5427 -- Touch the source to trigger a recompile.
5428
5429 elseif arg[1] == "again" then
5430 loadconf ()
5431 updateanddone ()
5432
5433
5434 -- lwarpmk clean:
5435 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
5436
5437 elseif arg[1] == "clean" then
5438 loadconf ()
5439 removeaux ()
5440 print ("lwarpmk: Done.")
5441
5442
5443 -- lwarpmk cleanall
5444 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
5445 -- and also project.pdf, project.dvi, *.html
5446
5447 elseif arg[1] == "cleanall" then
5448 loadconf ()
5449 removeaux ()
5450 os.execute ( rmname .. " " ..
5451     sourcename .. ".pdf " .. sourcename .. "_html.pdf " ..
5452     sourcename .. ".dvi " .. sourcename .. "_html.dvi " ..
5453     "*.html"
5454 )
5455 print ("lwarpmk: Done.")
5456
5457
5458 -- lwarpmk cleanlimages
5459 -- Remove images from the imagesdirectory.
5460
5461 elseif arg[1] == "cleanlimages" then
5462 loadconf ()
5463 os.execute ( rmname .. " " .. imagesdirectory .. dirsslash .. "*" )
```

```

5464 print ("lwarpmk: Done.")
5465
5466 -- lwarpmk epstopdf <list of file names>
5467 -- Convert EPS files to PDF using epstopdf
5468 elseif arg[1] == "epstopdf" then
5469 convertepstopdf ()
5470 print ("lwarpmk: Done.")
5471
5472
5473 -- lwarpmk pdftosvg <list of file names>
5474 -- Convert PDF files to SVG using pdftocairo
5475 elseif arg[1] == "pdftosvg" then
5476 convertpdftosvg ()
5477 print ("lwarpmk: Done.")
5478
5479
5480 -- lwarpmk with no argument :
5481
5482 elseif (arg[1] == nil) then
5483 printhelp ()
5484
5485
5486 -- lwarpmk -v:
5487
5488 elseif (arg[1] == "-v" ) then
5489 -- The version number has already been printed
5490 -- by the lwarpmk intro.
5491
5492 -- lwarpmk -h or lwarpmk --help :
5493
5494 elseif (arg[1] == "-h" ) or (arg[1] == "--help") then
5495 printusage ()
5496
5497
5498 -- Unknown command:
5499
5500 else
5501 printhelp ()
5502 print ("\nlwarpmk: ***** Unknown command \"\"..arg[1]..\"\". *****\n")
5503 end
5504
5505 end -- not --version
5506 \end{filecontents*}
5507 % \end{Verbatim}% for syntax highlighting

5508 \end{LWRcreatelwarpmk}

```

40 Stacks

for HTML output: 5509 \begin{warpHTML}

Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (un-nested) in



proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new `\section` would close any currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an enumerate, for example. Depths to be recorded in `\LWR@closedepthone`, etc.

40.1 Assigning depths

initial depths for empty stack entries:

```
5510 \newcommand*\LWR@depthnone}{-5}
```

All sectioning depths are deeper than `LWR@depthfinished`:

```
5511 \newcommand*\LWR@depthfinished}{-4}
5512 \newcommand*\LWR@depthbook}{-2}
5513 \newcommand*\LWR@depthpart}{-1}
5514 \newcommand*\LWR@depthchapter}{0}
5515 \newcommand*\LWR@depthsection}{1}
5516 \newcommand*\LWR@depthsubsection}{2}
5517 \newcommand*\LWR@depthsubsubsection}{3}
5518 \newcommand*\LWR@depthparagraph}{4}
5519 \newcommand*\LWR@depthsubparagraph}{5}
```

Used by `\itemize`, `\enumerate`, `\description`:

```
5520 \newcommand*\LWR@depthlist}{6}
```

Used by `\item`:

```
5521 \newcommand*\LWR@depthlistitem}{7}
5522 \let\LWR@depthdescitem\LWR@depthlistitem
```

40.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to `\pushclose` and `\popclose` as well.

```
5523 \newcommand*\LWR@closeone}{% top of the stack
5524 \newcommand*\LWR@closetwo}{
5525 \newcommand*\LWR@closethree}{
5526 \newcommand*\LWR@closefour}{
5527 \newcommand*\LWR@closefive}{
5528 \newcommand*\LWR@closesix}{
5529 \newcommand*\LWR@closeseven}{
```

```

5530 \newcommand*\LWR@closeeight{}
5531 \newcommand*\LWR@closenine{}
5532 \newcommand*\LWR@closeten{}
5533 \newcommand*\LWR@closeeeleven{}
5534 \newcommand*\LWR@closetwelve{}

```

40.3 Closing depths

A stack to record the depth of each level:



Note that nested L^AT_EX structures may push depths which are non-sequential.

Ex:

```

\begin{itemize}
  \item{A}
  \begin{description}
    \item{B}
  \end{description}
\end{itemize}

```

```

5535 \newcommand*\LWR@closedepthone{\LWR@depthnone}% top of the stack
5536 \newcommand*\LWR@closedepthtwo{\LWR@depthnone}
5537 \newcommand*\LWR@closedepththree{\LWR@depthnone}
5538 \newcommand*\LWR@closedepthfour{\LWR@depthnone}
5539 \newcommand*\LWR@closedepthfive{\LWR@depthnone}
5540 \newcommand*\LWR@closedepthsix{\LWR@depthnone}
5541 \newcommand*\LWR@closedepthseven{\LWR@depthnone}
5542 \newcommand*\LWR@closedeptheight{\LWR@depthnone}
5543 \newcommand*\LWR@closedepthnine{\LWR@depthnone}
5544 \newcommand*\LWR@closedephten{\LWR@depthnone}
5545 \newcommand*\LWR@closedeptheleven{\LWR@depthnone}
5546 \newcommand*\LWR@closedephtwelve{\LWR@depthnone}

```

40.4 Pushing and popping the stack

`\LWR@pushclose` $\{ \langle sectiontype \rangle \}$

Pushes one return action and its L^AT_EX depth onto the stacks.

```

5547 \NewDocumentCommand{\LWR@pushclose}{m}
5548 {%
5549 \global\let\LWR@closetwelve\LWR@closeeeleven%
5550 \global\let\LWR@closeeeleven\LWR@closeten%
5551 \global\let\LWR@closeten\LWR@closenine%
5552 \global\let\LWR@closenine\LWR@closeeight%
5553 \global\let\LWR@closeeight\LWR@closeseven%
5554 \global\let\LWR@closeseven\LWR@closesix%
5555 \global\let\LWR@closesix\LWR@closefive%

```

```

5556 \global\let\LWR@closefive\LWR@closefour%
5557 \global\let\LWR@closefour\LWR@closethree%
5558 \global\let\LWR@closethree\LWR@closetwo%
5559 \global\let\LWR@closetwo\LWR@closeone%
5560 \global\csletcs{LWR@closeone}{LWR@printclose#1}%
5561 \global\let\LWR@closedepthtwelve\LWR@closedeptheleven%
5562 \global\let\LWR@closedeptheleven\LWR@closedepthten%
5563 \global\let\LWR@closedepthten\LWR@closedepthnine%
5564 \global\let\LWR@closedepthnine\LWR@closedeptheight%
5565 \global\let\LWR@closedeptheight\LWR@closedepthseven%
5566 \global\let\LWR@closedepthseven\LWR@closedepthsix%
5567 \global\let\LWR@closedepthsix\LWR@closedepthfive%
5568 \global\let\LWR@closedepthfive\LWR@closedepthfour%
5569 \global\let\LWR@closedepthfour\LWR@closedepththree%
5570 \global\let\LWR@closedepththree\LWR@closedepthtwo%
5571 \global\let\LWR@closedepthtwo\LWR@closedepthone%
5572 \global\csletcs{LWR@closedepthone}{LWR@depth#1}%
5573 }

```

\LWR@popclose Pops one action and its depth off the stacks.

```

5574 \newcommand*{\LWR@popclose}
5575 {%
5576 \global\let\LWR@closeone\LWR@closetwo%
5577 \global\let\LWR@closetwo\LWR@closethree%
5578 \global\let\LWR@closethree\LWR@closefour%
5579 \global\let\LWR@closefour\LWR@closefive%
5580 \global\let\LWR@closefive\LWR@closesix%
5581 \global\let\LWR@closesix\LWR@closeseven%
5582 \global\let\LWR@closeseven\LWR@closeeight%
5583 \global\let\LWR@closeeight\LWR@closenine%
5584 \global\let\LWR@closenine\LWR@closeten%
5585 \global\let\LWR@closeten\LWR@closeeleven%
5586 \global\let\LWR@closeeleven\LWR@closetwelve%
5587 \global\let\LWR@closedepthone\LWR@closedepthtwo%
5588 \global\let\LWR@closedepthtwo\LWR@closedepththree%
5589 \global\let\LWR@closedepththree\LWR@closedepthfour%
5590 \global\let\LWR@closedepthfour\LWR@closedepthfive%
5591 \global\let\LWR@closedepthfive\LWR@closedepthsix%
5592 \global\let\LWR@closedepthsix\LWR@closedepthseven%
5593 \global\let\LWR@closedepthseven\LWR@closedeptheight%
5594 \global\let\LWR@closedeptheight\LWR@closedepthnine%
5595 \global\let\LWR@closedepthnine\LWR@closedepthten%
5596 \global\let\LWR@closedepthten\LWR@closedeptheleven%
5597 \global\let\LWR@closedeptheleven\LWR@closedepthtwelve%
5598 }

5599 \end{warpHTML}

```

41 Data arrays

These macros are similar to the `arrayjobx` package, except that `\LWR@setexparray's` argument is expanded only once when assigned.

`name` has no backslash, `index` can be a number or a text name, and an empty value must be `\relax` instead of empty.

To assign an empty value:

```
\LWR@setexparray{name}{index}{}
```

for HTML output: 5600 `\begin{warpHTML}`

```
\LWR@setexparray {<name>} {<index>} {<contents>}
```

```
5601 \NewDocumentCommand{\LWR@setexparray}{m m m}{%
5602   \let\LWR@temp@par\par%
5603   \let\par\relax%
5604   \edef\LWR@thisexparrayname{#1#2}%
5605   \ifstrempy{#3}%
5606     {\csdef{\LWR@thisexparrayname}{}}%
5607     {\csdef{\LWR@thisexparrayname}{#3}}%
5608   \let\par\LWR@temp@par%
5609 }
```

```
\LWR@getexparray {<name>} {<index>}
```

```
5610 \newcommand*{\LWR@getexparray}[2]{%
5611   \@nameuse{#1#2}%
5612 }
```

```
5613 \end{warpHTML}
```

42 Localizing catcodes

for HTML & PRINT: 5614 `\begin{warpall}`

 **Misplaced alignment tab character &** Place `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error

```
Misplaced alignment tab character &.
```

`\StartDefiningTabulars` Place before defining something with & in it.

```
5615 \newcommand{\StartDefiningTabulars}{%
5616   \LWR@traceinfo{StartDefiningTabulars}%
```

```
5617 \warpHTMLonly{\catcode'\&=\active}%
5618 }
```

`\StopDefiningTabulars` Place after defining something with `&` in it.

```
5619 \newcommand{\StopDefiningTabulars}{%
5620 \LWR@traceinfo{StopDefiningTabulars}%
5621 \warpHTMLonly{\catcode'\&=4}%
5622 }
```

Bool `LWR@mathmacro` True if currently defining math macros. Used to disable svg math hashing and MathJax math contents while defining a macro using inline math. Begin a macro, it is not guaranteed that the contents are static, and so the image must be unique. The contents also almost certainly will not be parsed correctly by MathJax.

```
5623 \newbool{LWR@mathmacro}
5624 \boolfalse{LWR@mathmacro}
```

`\StartDefiningMath` Place before defining something with `$` in it.

```
5625 \newcommand{\StartDefiningMath}{%
5626 \LWR@traceinfo{StartDefiningMath}%
5627 \warpHTMLonly{\catcode'\$=\active}%
5628 }
```

`\StopDefiningMath` Place after defining something with `$` in it.

```
5629 \newcommand{\StopDefiningMath}{%
5630 \LWR@traceinfo{StopDefiningMath}%
5631 \warpHTMLonly{\catcode'\$=3}% math shift
5632 }
```

```
5633 \end{warpall}
```

43 Localizing dynamic math

Inline svg math usually uses a hash of its contents to generate `lateximages` which are reusable for multiple instances with the same contents. If the contents may change for each use, such as depending on the current value of a counter, then `\inlinemathother` must be used before the inline math expression, and `\inlinemathnormal` must be used after.

For MathJax, the inline math expression is usually printed for MathJax to interpret. When marked as dynamic math, the following inline math expression will be displayed as an unhashed inline svg image instead.

For existing code and packages, it may be possible to patch macros after they have been defined, using the `xpatch` package, which is pre-loaded by `lwarp`:

```

\patchcmd{\macroname}
  {$math expression$}
  {\inlinemathother$math expression$\inlinemathnormal}
  {}
  {\typeout{Error patching macroname.}}

```

for HTML & PRINT: 5634 \begin{warpall}

Bool LWR@dynamicmath True to mark inline math which is dynamic in nature, thus should not be hashed for reuse.
 Default: false

```

5635 \newbool{LWR@dynamicmath}
5636 \boolfalse{LWR@dynamicmath}

```

\inlinemathother Place before using \$... \$ or \ (... \) if the contents of the math are not static, depending on counters or dynamic macros.

```

5637 \newcommand{\inlinemathother}{%
5638 \LWR@traceinfo{inlinemathother}%
5639 \booltrue{LWR@dynamicmath}%
5640 }

```

\inlinemathnormal Place after using \$... \$ or \ (... \) with dynamic contents.

```

5641 \newcommand{\inlinemathnormal}{%
5642 \LWR@traceinfo{inlinemathnormal}%
5643 \boolfalse{LWR@dynamicmath}%
5644 }

```

```

5645 \end{warpall}

```

44 HTML entities

for HTML output: 5646 \begin{warpHTML}

HTML Unicode entities:

```

5647 \let\LWR@origampersand&

```

\HTMLentity {<entitytag>}

```

5648 \newcommand*{\HTMLentity}[1]{%
5649 % \LWR@traceinfo{HTMLentity \detokenize{#1}}%
5650 \begingroup%
5651 \LWR@FBcancel%
5652 \LWR@origampersand#1;%
5653 \endgroup%
5654 % \LWR@traceinfo{HTMLentity done}%
5655 }

```

`\HTMLUnicode` {*<hex_unicode>*}

5656 \newcommand*{\HTMLUnicode}[1]{\HTMLentity{\LWR@origpound{ }x#1}}

`\&`

5657 \renewrobustcmd*{\&}{\HTMLentity{amp}}

`\textless`

5658 \let\LWR@origtextless\textless

5659 \renewrobustcmd*{\textless}{\HTMLentity{lt}}

`\textgreater`

5660 \let\LWR@origtextgreater\textgreater

5661 \renewrobustcmd*{\textgreater}{\HTMLentity{gt}}

5662 \end{warpHTML}

45 HTML filename generation

The filename of the homepage is set to `\HomeHTMLFilename.html`. The filenames of additional sections start with `\HTMLFilename`, to which is appended a section number or a simplified section name, depending on `FileSectionNames`.

for HTML & PRINT: 5663 \begin{warpall}

`\BaseJobname` The `\jobname` of the printed version, even if currently compiling the HTML version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLFilename` if the user did not provide one.

5664 \providecommand*{\BaseJobname}{\jobname}

`\HTMLFilename` The prefix for all generated HTML files other than the home page, defaulting to empty. See section [7.6.1](#).

5665 \providecommand*{\HTMLFilename}{}

`\HomeHTMLFilename` The filename of the home page, defaulting to the `\BaseJobname`. See section [7.6.1](#).

5666 \providecommand*{\HomeHTMLFilename}{\BaseJobname}

`\SetHTMLFileNumber` {*<number>*}

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number

of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
5667 \newcommand*{\SetHTMLFileNumber}[1]{%
5668   \setcounter{LWR@htmlfilenumber}{#1}%
5669 }
```

Bool FileSectionNames Selects how to create HTML file names.

Defaults to use section names in the filenames.

```
5670 \newbool{FileSectionNames}
5671 \booltrue{FileSectionNames}

5672 \end{warpall}
```

for HTML output: 5673 \begin{warpHTML}

Updated each time a new HTML file is begun. Used to provide HTML previous/next web page links.

```
5674 \newcounter{LWR@HTMLpagenum}
5675 \setcounter{LWR@HTMLpagenum}{0}
```

Ctr LWR@htmlseqfilenumber A sequential count of the number of each HTML file as it is being created. Number 0 is the home page. Unlike \LWR@htmlfilenumber, this one is known to increment by one for each file. This is used to generate previous /next links for each web page, via labels called \BaseJobname-autofile-*, and the last page is also labelled \BaseJobname-autofile-last.

```
5676 \newcounter{LWR@htmlseqfilenumber}
5677 \setcounter{LWR@htmlseqfilenumber}{0}
```

Bool LWR@setseqfilelabel At each new HTML file, this is false until a sectional unit is used, at which point this is set true and a label is placed. In this way, the previous/next labels will point to a named section.

```
5678 \newbool{LWR@setseqfilelabel}
5679 \setbool{LWR@setseqfilelabel}{false}
```

Ctr LWR@htmlfilenumber Records the number of each HTML file as it is being created. Number 0 is the home page. This might not be sequential, as the user may use \SetHTMLFileNumber to create groups of numbered nodes.

```
5680 \newcounter{LWR@htmlfilenumber}
5681 \setcounter{LWR@htmlfilenumber}{0}
```

\LWR@htmlsectionfilename *{(htmlfilenumber or name)}*

Prints the filename for a given section: \HTMLFilename{}filenumber/name.html

```

5682 \newcommand*{\LWR@htmlsectionfilename}[1]{%
5683 \LWR@traceinfo{\LWR@htmlsectionfilename A !\detokenize{#1}!}%
5684 \begingroup%

```

Disable CJK xpinyin while generating file names.

```
5685 \LWR@disablepinyin%
```

Section 0 or empty is given the home filename. The filename must be detokenized for underscores.

```

5686 % \LWR@traceinfo{about to assign temp}%
5687 \LWR@sanitize{#1}%
5688 \LWR@traceinfo{about to compare with ??}%
5689 \ifdefstring{\LWR@sanitized}{??}
5690   {\LWR@traceinfo{found ??}}%
5691   {\LWR@traceinfo{not found ??}}%
5692 \LWR@traceinfo{about to compare with zero or empty}%
5693 \ifboolexpr{
5694   test {\ifdefstring{\LWR@sanitized}{0}} or
5695   test {\ifdefstring{\LWR@sanitized}} or
5696   test {\ifdefstring{\LWR@sanitized}{??}}
5697 }
5698 {%
5699   \LWR@traceinfo{\LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
5700   \HomeHTMLFilename.html%
5701 }%

```

For a L^AT_EX section named “Index” or “index” without a prefix, create a filename with a trailing -0 to avoid colliding with the HTML filename index.html:

```

5702 {%
5703   \LWR@traceinfo{\LWR@htmlsectionfilename C \LWR@sanitized}%
5704   \ifboolexpr{
5705     test{\ifdefvoid{\HTMLFilename}} and
5706     (
5707       test{\ifdefstring{\LWR@sanitized}{Index}} or
5708       test{\ifdefstring{\LWR@sanitized}{index}}
5709     )
5710   }%
5711   {%
5712     \LWR@traceinfo{Adding a zero to the index filename.}%
5713     \LWR@sanitized-0.html%
5714   }%

```

Otherwise, create a filename with the chosen prefix:

```

5715   {%
5716     \HTMLFilename\LWR@isolate{\LWR@sanitized}.html%
5717   }%
5718 }%
5719 \LWR@traceinfo{\LWR@htmlsectionfilename Z}%
5720 \endgroup%
5721 }

```

`\LWR@htmlrefsectionfilename` {<label>}

Prints the filename for the given label

```
5722 \newcommand*\LWR@htmlrefsectionfilename[1]{%
5723   \LWR@traceinfo{\LWR@htmlrefsectionfilename: !\detokenize{#1}!}%
```

`\LWR@nullfonts` to allow math in a section name.

```
5724   \begingroup%
5725   \LWR@nullfonts%
5726   \LWR@htmlsectionfilename{\LWR@htmlfileref{#1}}%
5727   \endgroup%
5728   \LWR@traceinfo{\LWR@htmlrefsectionfilename: done}%
5729 }
```

```
5730 \end{warpHTML}
```

46 Homepage link

for HTML & PRINT: 5731 `\begin{warpall}`

`\linkhomename` Holds the default name for the home link.

```
5732 \newcommand{\linkhomename}{Home}
```

```
5733 \end{warpall}
```

for HTML output: 5734 `\begin{warpHTML}`

`\LinkHome` May be used wherever you wish to place a link back to the homepage. The filename must be detokenized for underscores.

```
5735 \newcommand*\LinkHome{%
5736   \LWR@subhyperrefclass{\HomeHTMLFilename.html}{\linkhomename}{linkhome}%
5737 }
```

```
5738 \end{warpHTML}
```

for PRINT output: 5739 `\begin{warpprint}`

`\LinkHome` May be used wherever you wish to place a link back to the homepage. For print output, if `hyperref` is available a hyperlink to the first page is used, named by `\linkhomename`. If `hyperref` is not available, a `pageref` is used instead.

`\BaseJobname` is included in the link label in case multiple documents are cross-referenced.

```

5740 \AtBeginDocument{
5741 \ifundefined{hyperref}{
5742   \newcommand*\LinkHome{%
5743     \linkhomename\ --- page \pageref{\BaseJobname-page-LWRfirstpage}%
5744   }
5745 }{
5746   \newcommand*\LinkHome{%
5747     \hyperref[\BaseJobname-page-LWRfirstpage]{\linkhomename}%
5748   }
5749 }
5750 }
5751
5752 \AfterEndPreamble{\label{\BaseJobname-page-LWRfirstpage}}

5753 \end{warpprint}

```

for HTML output: 5754 \begin{warpHTML}

`\LWR@topnavigation` Creates a link to the homepage at the top of the page for use when the window is too narrow for the sideroc.

```

5755 \newcommand*\LWR@topnavigation{%
5756   \LWRhtmllementclassline{nav}{topnavigation}{\LinkHome}
5757 }

```

`\LWR@botnavigation` Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sideroc.

```

5758 \newcommand*\LWR@botnavigation{%
5759   \LWRhtmllementclassline{nav}{botnavigation}{\LinkHome}
5760 }

```

```
5761 \end{warpHTML}
```

47 Previous/next navigation links

for HTML & PRINT: 5762 \begin{warpall}

`\linkpreviousname` What to call the link to the previous web page.

```
5763 \newcommand*\linkpreviousname{Previous}
```

`\linknextname` What to call the link to the next web page.

```
5764 \newcommand*\linknextname{Next}
```

```
5765 \end{warpall}
```

for PRINT output: 5766 \begin{warpprint}

`\LinkPrevious` Creates a link to the previous web page if there is one.

```
5767 \newcommand*{\LinkPrevious}{}
```

`\LinkNext` Creates a link to the next web page if there is one.

```
5768 \newcommand*{\LinkNext}{}

5769 \end{warpprint}
```

for HTML output: 5770 `\begin{warpHTML}`

`\LinkPrevious` Creates a link to the previous web page if there is one.

The links refer to the L^AT_EX labels `\Basejobname-autofile-*`

```
5771 \newcommand*{\LinkPrevious}{%
5772   \ifnumless{\value{LWR@htmlseqfilenumber}}{1}}{}{%
5773     \setcounter{LWR@tempcountone}{\value{LWR@htmlseqfilenumber}-1}%
5774     \LWR@subhyperrefclass{%
5775       \LWR@htmlrefsectionfilename{%
5776         \BaseJobname-autofile-\arabic{LWR@tempcountone}%
5777       }%
5778     }{\linkpreviousname}{linkhome}%
5779   }%
5780 }
```

`\LinkNext` Creates a link to the next web page if there is one.

The links refer to the L^AT_EX labels `\Basejobname-autofile-*`
and the last is the label `\Basejobname-autofile-last`

```
5781 \newcommand*{\LinkNext}{%
5782   \ifcsdef{r@\BaseJobname-autofile-last@lwarp}{%
5783     \edef\LWR@tempone{%
5784       \LWR@htmlfileref{\BaseJobname-autofile-\arabic{LWR@htmlseqfilenumber}}%
5785     }%
5786     \edef\LWR@temptwo{%
5787       \LWR@htmlfileref{\BaseJobname-autofile-last}%
5788     }%
5789     \ifdefequal{\LWR@tempone}{\LWR@temptwo}}{}{%
5790       \setcounter{LWR@tempcountone}{\value{LWR@htmlseqfilenumber}+1}%
5791       \LWR@subhyperrefclass{%
5792         \LWR@htmlrefsectionfilename{%
5793           \BaseJobname-autofile-\arabic{LWR@tempcountone}%
5794         }%
5795       }{\linknextname}{linkhome}%
5796     }%
5797   }{}%
5798 }

5799 \end{warpHTML}
```

48 \LWRPrintStack diagnostic tool



Diagnostics tool: Prints the L^AT_EX nesting depth values for the stack levels. \LWR@startpars is used before printing the stack, so that \LWRPrintStack may be called from anywhere in the normal text flow.

for HTML output: 5800 \begin{warpHTML}

\LWRPrintStack Prints the closedepth stack.

```
5801 \newcommand*{\LWR@subprintstack}{
5802 \LWR@closedepthone\ \LWR@closedepthtwo\ \LWR@closedepththree\
5803 \LWR@closedepthfour\ \LWR@closedepthfive\ \LWR@closedepthsix\
5804 \LWR@closedepthseven\ \LWR@closedeptheight\ \LWR@closedepthnine\
5805 \LWR@closedephten\ \LWR@closedeptheleven\ \LWR@closedephtwelve\
5806 }
5807
5808 \newcommand*{\LWRPrintStack}{
5809 \LWR@startpars
5810 \LWR@subprintstack
5811 }

5812 \end{warpHTML}
```

for PRINT output: 5813 \begin{warpprint}

```
5814 \newcommand*{\LWRPrintStack}{}

5815 \end{warpprint}
```

49 Closing stack levels

for HTML output: 5816 \begin{warpHTML}

Close one nested level:

```
5817 \newcommand*{\LWR@closeoneprevious}{%
5818
5819 \LWR@closeone
5820
5821 \LWR@popclose
5822 }
```

\LWR@closeprevious *{(sectintype)}* Close everything up to the given depth:

```
5823 \newcommand*{\LWR@closeprevious}[1]{
5824 \LWR@traceinfo{%
5825     \LWR@closeprevious to depth \csuse{\LWR@depth#1}, %
5826     depths are \LWR@subprintstack%
5827 }%
```

Close any pending paragraph:

```
5828 \LWR@stoppars%
```

Close anything nested deeper than the desired depth. First close anything deeper, then at most one of the same level.

```
5829 \whileboolexpr{test{\ifnumcomp{\LWR@closedepthone}{>}{\csuse{\LWR@depth#1}}}}%
5830 {%
5831   \LWR@traceinfo{\LWR@closeprevious: closing out depth \LWR@closedepthone}%
5832   \LWR@closeoneprevious%
5833 }%
5834 \ifboolexpr{test{\ifnumcomp{\LWR@closedepthone}{=}{\csuse{\LWR@depth#1}}}}%
5835 {%
5836   \LWR@traceinfo{\LWR@closeprevious: closing out depth \LWR@closedepthone}%
5837   \LWR@closeoneprevious%
5838 }{}%
5839 \LWR@traceinfo{\LWR@closeprevious: done, depths are \LWR@subprintstack}%
5840 }

5841 \end{warpHTML}
```

50 PDF pages and styles

for HTML output: 5842 \begin{warpHTML}

\LWR@forcenewpage New PDF page a before major environment.

This is used just before major environments, such as verse. Reduces the chance of an environment overflowing the HTML PDF output page.

```
5843 \newcommand{\LWR@forcenewpage}{%
5844 \LWR@traceinfo{\LWR@forcenewpage}%
5845 \ifinner\else%
5846   \LWR@traceinfo{\LWR@forcenewpage A}%
5847   \LWR@stoppars%
5848   \LWR@traceinfo{\LWR@forcenewpage B}%
5849   \LWR@maybe@orignewpage%
5850   \LWR@traceinfo{\LWR@forcenewpage C}%
5851   \LWR@startpars%
5852 \fi%
5853 \LWR@traceinfo{\LWR@forcenewpage done}%
5854 }
```

\pagestyle, etc. are nullified for HTML output.

\pagestyle {*style*}

```
5855 \renewcommand*{\pagestyle}[1]{}
```

```

\thispagestyle  {\langle style \rangle}

5856 \renewcommand*{\thispagestyle}[1]{}

\markboth  {\langle left \rangle} {\langle right \rangle}

5857 \renewcommand*{\markboth}[2]{}

\markright  {\langle right \rangle}

5858 \renewcommand*{\markright}[1]{}

\raggedbottom

5859 \renewcommand*{\raggedbottom}{}

\flushbottom

5860 \renewcommand*{\flushbottom}{}

\sloppy

5861 \renewcommand*{\sloppy}{}

\fussy

5862 \renewcommand*{\fussy}{}

\pagenumbering  * {\langle commands \rangle}

5863 \RenewDocumentCommand{\pagenumbering}{s m}{}

5864 \end{warpHTML}

```

51 HTML tags, spans, divs, elements

for HTML output: 5865 \begin{warpHTML}

51.1 Mapping L^AT_EX sections to HTML sections

```

5866 \newcommand*{\LWR@tagtitle}{h1}
5867 \newcommand*{\LWR@tagtitleend}{/h1}
5868 \newcommand*{\LWR@tagbook}{div class="book"}
5869 \newcommand*{\LWR@tagbookend}{/div}
5870 \newcommand*{\LWR@tagpart}{h2}

```

```

5871 \newcommand*\LWR@tagpartend{/h2}
5872 \newcommand*\LWR@tagchapter{h3}
5873 \newcommand*\LWR@tagchapterend{/h3}
5874 \newcommand*\LWR@tagsection{h4}
5875 \newcommand*\LWR@tagsectionend{/h4}
5876 \newcommand*\LWR@tagsubsection{h5}
5877 \newcommand*\LWR@tagsubsectionend{/h5}
5878 \newcommand*\LWR@tagsubsubsection{h6}
5879 \newcommand*\LWR@tagsubsubsectionend{/h6}
5880 \newcommand*\LWR@tagparagraph[span class="paragraph"]
5881 \newcommand*\LWR@tagparagraphend{/span}
5882 \newcommand*\LWR@tagsubparagraph[span class="subparagraph"]
5883 \newcommand*\LWR@tagsubparagraphend{/span}
5884
5885 \newcommand*\LWR@tagregularparagraph{p}

```

51.2 Babel-French tag modifications

Adjust babel-french for HTML spaces. So far, this only works for *pdf_latex* and *xelatex*.

(Emulates or patches code by DANIEL FLIPO.)

```

5886 \providecommand*\LWR@FBcancel{}
5887
5888 \AtBeginDocument{%

```

In some circumstances, `\NoAutoSpacing` may be defined when `\frenchbsetup` is not.

```

5889 \@ifundefined{NoAutoSpacing}%
5890   {}%
5891   {%
5892     \LetLtxMacro\LWR@FBcancel\NoAutoSpacing%
5893   }%
5894
5895 \@ifundefined{frenchbsetup}%
5896   {}%
5897   {%
5898     \frenchbsetup{FrenchFootnotes=false}%
5899 %
5900   \renewrobustcmd*\FBcolonspace{%
5901     \begingroup%
5902     \LWR@FBcancel%
5903     \LWR@origampersand{}nbsp;%
5904     \endgroup%
5905   }%
5906   \renewrobustcmd*\FBthinspace{%
5907     \begingroup%
5908     \LWR@FBcancel%
5909     \LWR@origampersand\LWR@origpound{x202f;% \,
5910     \endgroup%
5911   }%
5912   \renewrobustcmd*\FBguillspace{%

```

```

5913     \begingroup%
5914     \LWR@FBcancel%
5915     \LWR@origampersand{}nbsp;% ~, for \og xyz \fg{}
5916     \endgroup%
5917 }%
5918 \DeclareDocumentCommand{\FBmedkern}{}{%
5919     \begingroup%
5920     \LWR@FBcancel%
5921     \LWR@origampersand\LWR@origpound{}x202f;% \,
5922     \endgroup%
5923 }%
5924 \DeclareDocumentCommand{\FBthickkern}{}{%
5925     \begingroup%
5926     \LWR@FBcancel%
5927     \LWR@origampersand{}nbsp;% ~
5928     \endgroup%
5929 }%
5930 \renewrobustcmd*{~}{\HTMLentity{nbsp}}% was overwritten by babel-french
5931 \ifFBunicode%
5932 \else%
5933     \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
5934     \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
5935 \fi%
5936 }%
5937 }

```

51.3 HTML output formatting

Helps format the output HTML code for human readability.

`\LWR@indentHTML` Newline and indent the output HTML code.

```

5938 \newcommand*{\LWR@indentHTML}{}%
5939     \LWR@orignewline\LWR@origrule{2em}{0pt}%
5940 }

```

`\LWR@indentHTMLtwo` Newline and indent the output HTML code.

```

5941 \newcommand*{\LWR@indentHTMLtwo}{}%
5942     \LWR@orignewline\LWR@origrule{4em}{0pt}%
5943 }

```

51.4 HTML tags

`\LWR@htmltagc` `{\tag}` Break ligatures and use upright apostrophes in HTML tags.

`\protect` is in case the tag appears in TOC, LOF, LOT.

```

5944 \newcommand*{\LWR@htmltagc}[1]{}%
5945 \LWR@traceinfo{\LWR@htmltagc !\detokenize{#1}!}%

```

```

5946 \begingroup%
5947 \LWR@FBcancel%
5948 \ifmmode\else\protect\LWR@print@normalfont\protect\LWR@origttfamily\fi%
5949 \protect\LWR@origtextless%
5950 \LWR@isolate{#1}%
5951 \protect\LWR@origtextgreater%
5952 \endgroup%
5953 }

```

`\LWR@spanwarnformat` {*object*}

Warns if the given object is used inside a span.

```

5954 \newcommand*\LWR@spanwarnformat}[1]{%
5955   \ifnumcomp{\value{LWR@spandepth}}{>}{0}{%
5956     \PackageWarning{lwarp}{%
5957       A #1 is being used inside a span.\MessageBreak
5958       Formatting may be lost,%
5959     }%
5960   }{}%
5961 }

```

`\LWR@spanwarninvalid` {*object*}

Warns if the given object is used inside a span.

```

5962 \newcommand*\LWR@spanwarninvalid}[1]{%
5963   \ifnumcomp{\value{LWR@spandepth}}{>}{0}{%
5964     \PackageWarning{lwarp}{%
5965       A #1 is being used inside a span.\MessageBreak
5966       This generates invalid HTML,%
5967     }%
5968   }{}%
5969 }

```

Env `LWR@nestspan` Disable minipage, `\parbox`, and HTML `<div>`s inside a ``.

-  `\begin{LWR@nestspan}` must follow the opening `` tag to allow a paragraph to start if the span is at the beginning of a new paragraph.
-  `\end{LWR@nestspan}` must follow the `` or a `<p>` may appear inside the span.

```

5970 \newcommand*\LWR@nestspanitem}{%
5971 \if@newlist\else{\LWR@htmltagc{br /}}\fi%
5972 \LWR@origitem%
5973 }
5974
5975 \newenvironment*{LWR@nestspan}
5976 {%
5977 \LWR@traceinfo{LWR@nestspan starting}%
5978 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
5979 {%
5980   \LWR@traceinfo{LWR@nestspan: inside a lateximage}%

```

```

5981 }%
5982 {% not in a lateximage
5983   \LWR@traceinfo{LWR@nestspan: NOT inside a lateximage}%
5984   \addtocounter{LWR@spandepth}{1}%

```

Nullify several objects inside the span:

```

5985   \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}%
5986     {\LWR@spanwarnformat{minipage or \protect\parbox}}%
5987     {}%
5988   \RenewDocumentEnvironment{BlockClass}{o m}%
5989     {\LWR@spanwarnformat{multi-paragraph object}}%
5990     {}%
5991   \renewcommand{\BlockClassSingle}[2]{%
5992     {\LWR@spanwarnformat{multi-paragraph object}}%
5993     ##2%
5994   }%
5995   \renewcommand{\LWR@forcenewpage}{}%
5996   \renewcommand{\LWR@liststart}{%
5997     \let\item\LWR@nestspanitem%
5998   }%
5999   \renewcommand{\LWR@listend}{\LWR@htmltagc{br /}\LWR@htmltagc{br /}}%
6000   \renewenvironment{quote}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
6001   \renewenvironment{quotation}{\LWR@htmltagc{br /}}{\LWR@htmltagc{br /}}%
6002 }% not in a lateximage
6003 \LWR@traceinfo{LWR@nestspan starting: done}%
6004 }% starting env
6005 {% ending env
6006 \LWR@traceinfo{LWR@nestspan ending}%
6007 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
6008 {}%
6009 {\addtocounter{LWR@spandepth}{-1}}%
6010 \LWR@traceinfo{LWR@nestspan ending: done}%
6011 }
6012
6013 \AfterEndEnvironment{LWR@nestspan}{\global\let\par\LWR@closeparagraph}

```

`\LWR@htmlspan` $\{\langle tag \rangle\} \{\langle text \rangle\}$



`\LWR@spandepth` is used to ensure that paragraph tags are not generated inside a span. The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```

6014 \NewDocumentCommand{\LWR@htmlspan}{m +m}{%
6015 \LWR@ensuredoingapar%
6016 \LWR@htmltagc{#1}%
6017 \begin{LWR@nestspan}%
6018 #2%
6019 \LWR@htmltagc{/#1}%
6020 \end{LWR@nestspan}%
6021 }

```

`\LWR@htmlspanclass` $[\langle style \rangle] \{\langle class \rangle\} \{\langle text \rangle\}$

```

6022 \NewDocumentCommand{\LWR@htmlspanclass}{o m +m}{%
6023 \LWR@traceinfo{\LWR@htmlspanclass |#1|#2|}%
6024 \LWR@ensuredoingapar%
6025 \LWR@subhtml elementclass{span}[#1][#2]%
6026 \begin{\LWR@nestspan}%
6027 #3%
6028 \LWR@htmltagc{/span}%
6029 \LWR@traceinfo{\LWR@htmlspanclass done}%
6030 \end{\LWR@nestspan}%
6031 }

```

`\LWR@htmltag` {*<tag>*}

Print an HTML tag: `<tag>`

```

6032 \newcommand*\LWR@htmltag[1]{%
6033 % \LWR@traceinfo{\LWR@htmltagb !\detokenize{#1}!}%
6034 \LWR@htmltagc{#1}%
6035 % \LWR@traceinfo{\LWR@htmltagb: done}%
6036 }

```

51.5 Block tags and comments

In the following, `\origttfamily` breaks ligatures, which may not be used for HTML codes:

`\LWR@htmlopencomment`
`\LWR@htmlclosecomment`

```

6037 \newcommand*\LWR@htmlopencomment}{%
6038 {%
6039 % \LWR@traceinfo{\LWR@htmlopencomment}%
6040 \begingroup%
6041 \LWR@FBcancel%
6042 \ifmmode\else\protect\LWR@print@normalfont\protect\LWR@origttfamily\fi%
6043 \LWR@print@mbox{\LWR@origtextless{}}!-/-}%
6044 \endgroup%
6045 }%
6046 }
6047
6048 \newcommand*\LWR@htmlclosecomment}{%
6049 {%
6050 % \LWR@traceinfo{\LWR@htmlclosecomment}%
6051 \begingroup%
6052 \LWR@FBcancel%
6053 \ifmmode\else\protect\LWR@print@normalfont\protect\LWR@origttfamily\fi%
6054 \LWR@print@mbox{-/-\LWR@origtextgreater}%
6055 \endgroup%
6056 }%
6057 }

```

`\LWR@htmlcomment` {*<comment>*}

```

6058 \newcommand{\LWR@htmlcomment}[1]{%
6059 \ifmmode%
6060 \else%
6061   \LWR@htmlopencomment{%
6062     {%
6063       \LWR@print@normalfont%
6064       \LWR@origttfamily% break ligatures
6065       #1%
6066     }%
6067   \LWR@htmlclosecomment{%
6068 \fi%
6069 }

```

`\LWR@htmlblockcomment` {*comment*}

```

6070 \newcommand{\LWR@htmlblockcomment}[1]
6071 {\LWR@stoppars\LWR@htmlcomment{#1}\LWR@startpars}

```

`\LWR@htmlblocktag` {*tag*} print a stand-alone HTML tag

```

6072 \newcommand*{\LWR@htmlblocktag}[1]{%
6073 \LWR@stoppars%
6074 \LWR@htmltag{#1}%
6075 \LWR@startpars%
6076 }

```

51.6 Div class and element class

`\LWR@subhtmlElementclass` {*element*} [*style*] {*class*}

Factored and reused in several places.

The trailing spaces allow more places for a line break.

The use of `\textquotedbl` instead of " provides improved compatibility with xeCJK.

```

6077 \NewDocumentCommand{\LWR@subhtmlElementclass}{m O{} m}{%
6078 \LWR@traceinfo{\LWR@subhtmlElementclass !#1!#2!#3!}%
6079 \ifblank{#2}%
6080 {% empty style
6081   \LWR@htmltag{%
6082     #1%
6083     \ifblank{#3}{\class=\textquotedbl#3\textquotedbl\ }% spaces
6084   }%
6085 }%
6086 {% non-empty style
6087   \LWR@htmltag{%
6088     #1\LWR@indentHTML%
6089     \ifblank{#3}{\class=\textquotedbl#3\textquotedbl\LWR@indentHTML}%
6090     style=\textquotedbl#2\textquotedbl\LWR@orignewline%
6091   }%
6092 }%

```

```
6093 \LWR@traceinfo{\LWR@subhtmlElementclass done}%
6094 }
```

`\LWR@htmlElementclass` {*element*} {*class*} [*style*]

```
6095 \NewDocumentCommand{\LWR@htmlElementclass}{m o m}{%
6096 \LWR@stoppars%
6097 \LWR@forceemptyline%
6098 \LWR@subhtmlElementclass{#1}[#2]{#3}%
6099 \LWR@startpars%
6100 }
```

`\LWR@htmlElementclassend` {*element*} {*class*}

```
6101 \newcommand*{\LWR@htmlElementclassend}[2]{%
6102 \LWR@stoppars%
6103 \LWR@htmltag{/#1}%
6104 \ifbool{HTMLDebugComments}{%
6105   \LWR@htmlcomment{End of #1 ‘#2’}%
6106 }{}%
6107 \LWR@startpars%
6108 }
```

`\LWR@htmldivclass` [*style*] {*class*}

```
6109 \NewDocumentCommand{\LWR@htmldivclass}{o m}{%
6110 \LWR@htmlElementclass{div}[#1]{#2}%
6111 }
```

`\LWR@htmldivclassend` {*class*}

```
6112 \newcommand*{\LWR@htmldivclassend}[1]{%
6113 \LWR@htmlElementclassend{div}{#1}%
6114 }
```

51.7 Single-line elements

A single-line element, without a paragraph tag for the line of text:

`\LWR@htmlElementclassline` {*element*} [*style*] {*class*} {*text*}

```
6115 \NewDocumentCommand{\LWR@htmlElementclassline}{m o m +m}{%
6116 \LWR@stoppars
6117 \LWR@forceemptyline%
6118 \LWR@subhtmlElementclass{#1}[#2]{#3}%
6119 #4%
6120 \LWR@htmltag{/#1}
6121 \LWR@startpars
6122 }
```

51.8 HTML5 semantic elements

`\LWR@htmlElement` $\{\langle element \rangle\}$

```
6123 \newcommand*\LWR@htmlElement}[1]{%
6124 \LWR@htmlblocktag{#1}
6125 }
```

`\LWR@htmlElementend` $\{\langle element \rangle\}$

```
6126 \newcommand*\LWR@htmlElementend}[1]{%
6127 \LWR@stoppars
6128 \LWR@htmltag{/#1}
6129 \LWR@startpars
6130 }
6131
6132 \end{warpHTML}
```

51.9 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with css.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section [93](#).

`Env` `BlockClass` $[\langle style \rangle] \{\langle class \rangle\}$ High-level interface for `<div>` classes.

Ex: `\begin{BlockClass}{class} text \end{BlockClass}`

for PRINT output:

```
6133 \begin{warpprint}
6134 \NewDocumentEnvironment{BlockClass}{o m}{\}{}%
6135 \end{warpprint}
```

for HTML output:

```
6136 \begin{warpHTML}
6137
6138 \NewDocumentEnvironment{LWR@print@BlockClass}{o m}{\}{}%
6139
6140 \NewDocumentEnvironment{LWR@HTML@BlockClass}{o m}%
6141   {\LWR@htmldivclass{#1}{#2}}
6142   {\LWR@htmldivclassend{#2}}
6143
6144 \LWR@formattedenv{BlockClass}
6145 \end{warpHTML}
```

`\BlockClassSingle` $\{\langle class \rangle\} \{\langle text \rangle\}$ A single-line `<div>`, without a paragraph tag for the line of text.

for HTML & PRINT:

```
6146 \begin{warpall}
6147 \newcommand{\BlockClassSingle}[2]{#2}
6148 \end{warpall}
```

for HTML output: 6149 \begin{warpHTML}
6150 \newcommand{\LWR@HTML@BlockClassSingle}[2]{%
6151 \LWR@html@element@classline{div}{#1}{#2}%
6152 }
6153
6154 \LWR@formatted{BlockClassSingle}
6155 \end{warpHTML}

\InlineClass (<WP style>) [<style>] {<class>} {<text>}

High-level interface for inline span classes.

(<WP style>) is CSS styling to add when formatting for a word processor import.

[<style>] is the CSS styling to add when not formatting for a word processor.

for PRINT output: 6156 \begin{warpprint}
6157 \NewDocumentCommand{\InlineClass}{D{()}{}}{ o m +m}{#4}%
6158 \end{warpprint}

for HTML output: 6159 \begin{warpHTML}
6160 \NewDocumentCommand{\LWR@print@InlineClass}{D{()}{}}{ o m +m}{#4}%
6161
6162 \NewDocumentCommand{\LWR@HTML@InlineClass}{D{()}{}}{ o m +m}{%
6163 \ifbool{FormatWP}{%
6164 \LWR@htmlspanclass[#1]{#3}{#4}%
6165 }{%
6166 \LWR@htmlspanclass[#2]{#3}{#4}%
6167 }%
6168 }
6169
6170 \LWR@formatted{InlineClass}
6171 \end{warpHTML}

Env LWR@BlockClassWP {<WPstyle>} {<HTMLstyle>} {<class>} Low-level interface for <div> classes with an automatic float ID. These are often used when \ifbool{FormatWP}.

The use of \textquotedbl instead of " provides improved compatibility with xeCJK.

for PRINT output: 6172 \begin{warpprint}
6173 \NewDocumentEnvironment{LWR@BlockClassWP}{m m m}{ }{%
6174 \end{warpprint}

for HTML output: 6175 \begin{warpHTML}
6176 \NewDocumentEnvironment{LWR@print@LWR@BlockClassWP}{m m m}{ }{%
6177 \NewDocumentEnvironment{LWR@HTML@LWR@BlockClassWP}{m m m}{%
6178 {%
6179 \LWR@stoppars%
6180 \ifbool{FormatWP}%
6181 {%
6182 \addtocounter{LWR@thisautoidWP}{1}%

6183 \LWR@htmltag{%

```

6184     div class=\textquotedbl#3\textquotedbl\ % space
6185     id=\textquotedbl%
6186     \LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}%
6187     \textquotedbl%
6188     \ifblank{#1}{\style=\textquotedbl#1\textquotedbl}%
6189     }%
6190 }% FormatWP
6191 {% not FormatWP
6192     \LWR@htmltag{%
6193     div class=\textquotedbl#3\textquotedbl%
6194     \ifblank{#2}{\style=\textquotedbl#2\textquotedbl}%
6195     }%
6196 }% not FormatWP
6197 \LWR@startpars%
6198 }
6199 {\LWR@htmldivclassend{#3}}
6200
6201 \LWR@formattedenv{LWR@BlockClassWP}
6202 \end{warpHTML}

```

51.10 Closing HTML tags

for HTML output: 6203 \begin{warpHTML}

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```

6204 \newcommand*{\LWR@printclosebook}
6205   {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing book}}{}}
6206 \newcommand*{\LWR@printclosepart}
6207   {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
6208 \newcommand*{\LWR@printclosechapter}
6209   {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
6210 \newcommand*{\LWR@printclosesection}
6211   {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
6212 \newcommand*{\LWR@printclosesubsection}
6213   {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
6214 \newcommand*{\LWR@printclosesubsection}
6215   {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
6216 \newcommand*{\LWR@printcloseparagraph}
6217   {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
6218 \newcommand*{\LWR@printclose subparagraph}
6219   {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}

```

Lists require closing HTML tags:

```

6220 \newcommand*{\LWR@printcloselistitem}
6221   {\LWR@htmltag{/li}}
6222 \newcommand*{\LWR@printclosedescitem}
6223   {\LWR@htmltag{/dd}}
6224 \newcommand*{\LWR@printcloseitemize}
6225   {\LWR@htmltag{/ul}}
6226 \newcommand*{\LWR@printcloseenumerate}

```

```

6227     {\LWR@htmltag{/ol}}
6228 \newcommand*{\LWR@printclosedescription}
6229     {\LWR@htmltag{/dl}}

6230 \end{warpHTML}

```

52 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 53 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (`\LWR@doingstartpars`), tags are not generated until a \LaTeX paragraph is being used (`\LWR@doingapar`). `LWR@lateximagedepth` is used to prevent nesting tags inside a `lateximage`. `LWR@spandepth` is used to prevent nesting paragraph tags inside a paragraph, which became important inside `\fbox` commands and other spans.

for HTML output: 6231 `\begin{warpHTML}`

Ctrl `LWR@spandepth` Do not create paragraph tags inside of an HTML span.

```

6232 \newcounter{LWR@spandepth}
6233 \setcounter{LWR@spandepth}{0}

```

Bool `LWR@doingstartpars` Tells whether paragraphs may be generated.

```

6234 \newbool{LWR@doingstartpars}
6235 \boolfalse{LWR@doingstartpars}

```

Bool `LWR@doingapar` Tells whether have actually generated and are currently processing paragraph text.

```

6236 \newbool{LWR@doingapar}
6237 \global\boolfalse{LWR@doingapar}

```

`\LWR@ensuredoingapar` If are about to print something visible, and if allowed to start a new paragraph, ensure that are `LWR@doingapar`, so that paragraph tags are placed:

```

6238 \newcommand*{\LWR@ensuredoingapar}{%
6239 \ifbool{LWR@doingstartpars}%
6240 {\global\booltrue{LWR@doingapar}}%
6241 {}}%
6242 }

```

`\PN@parnotes@auto` Redefined by `parnotes` to print paragraph notes at the end of each paragraph.

```

6243 \def\PN@parnotes@auto{}%

```

`\LWR@openparagraph`

```
6244 \newcommand*{\LWR@openparagraph}
6245 {%
```

See if paragraph handling is enabled:

```
6246 \ifbool{\LWR@doingstartpars}%
6247 {% handling pars
```

See if have already started a `lateximage` or a ``. If so, do not generate nested paragraph tags.

```
6248   \ifboolexpr{
6249     test {\ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}} or
6250     test {\ifnumcomp{\value{\LWR@spandepth}}{>}{0}}
6251   }{% nested par tags?
```

If so: Do nothing if already started a `lateximage` page. Cannot nest a `lateximage`. Also do nothing if already inside a ``. Do not nest paragraph tags inside a ``.

```
6252   }{% no nested par tags
```

Else: No `lateximage` or `` has been started yet, so it's OK to generate paragraph tags.

```
6253   {% yes nest par tags
```

If `parnotes` is used, paragraph notes are inserted before starting the next paragraph:

```
6254     \PN@parnotes@auto%
```

The opening paragraph tag:

```
6255     \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@originewline%
```

Now have started a paragraph.

```
6256     \global\booltrue{\LWR@doingapar}%
```

At the end of each paragraph, generate closing tag and do regular `/par` stuff. (Attempting to use the `everyhook` or `hook` for `\LWR@closeparagraph` does not work well.)

```
6257     \let\par\LWR@closeparagraph%
6258   }% end of yes nest par tags
6259 }% end of handling pars
6260 }% not handling pars
6261 }
```

`\LWR@closeparagraph@br` Add an HTML break if in a `span`, and not in a `lateximage`, and not in tabular metadata. Factored from `\LWR@closeparagraph`.

```
6262 \newcommand*{\LWR@closeparagraph@br}
6263 {%
```

```

6264 \ifboolexpr{
6265     test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}} and
6266     test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}} and
6267     not bool {LWR@intabularmetadata}
6268 }%
6269     {\unskip\LWR@htmltagc{br /}}%
6270     {}%
6271 }

```

\LWR@closeparagraph

```

6272 \newcommand*{\LWR@closeparagraph}
6273 {%
6274 % \LWR@traceinfo{LWR@closeparagraph}%

```

See if paragraph handling is enabled:

```
6275 \ifbool{LWR@doingapar}%
```

If currently in paragraph mode:

```
6276 {% handling pars
```

See if already started a lateximage or a :

```

6277 \ifboolexpr{
6278     test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
6279     test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
6280 }%

```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```

6281 {% no nested par tags
6282     \LWR@closeparagraph@br%
6283 }% no nested par tags

```

If have not already started a lateximage or a :

```
6284 {% yes nest par tags
```

Print a closing tag and some extra vertical space.

(The fill seems to be required to force the caption package to create flush left caption text in the HTML.)

```

6285     \@hspacer{\fill}% \hspace*{\fill}
6286     \leavevmode\LWR@orignewline%
6287     \LWR@htmltagc{/\LWR@tagregularparagraph}%

```

No longer doing a paragraph:

```
6288     \global\boolfalse{LWR@doingapar}%
```

Disable the special minipage & \hspace interaction until a new minipage is found:

```
6289     \global\boolfalse{LWR@minipagethispar}%
```

If parnotes is used, paragraph notes are inserted after ending the previous paragraph:

```
6290     \PN@parnotes@auto%
6291   }% end of yes nest par tags
6292 }% end of handling pars
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
6293 {% not handling pars
6294   \LWR@closeparagraph@br%
6295 }% not handling pars
```

In most cases, finish with a \LaTeX `\par`, but in the case of paragraphs between lines in a tabular fetch the next token instead:

```
6296 \ifboolexpr{%
6297   not bool {LWR@doingapar} and
6298   test {\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}} and
6299   test {
6300     \ifnumcomp{\value{LWR@tabulardepth}}{=}{\value{LWR@tabularpardepth}}
6301   } and
6302   bool {LWR@intabularmetadata} and
6303   not bool {LWR@tableparcell} and
6304   test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
6305 }%
6306 {%
6307   \LWR@getmynexttoken%
6308 }{%
6309   \LWR@origpar%
6310 }%
6311 }

6312 \end{warpHTML}
```

53 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 52 has the commands which actually generate the tags.

The everyhook package is used to generate the opening paragraph tags. The closing tags are generated by `\par`.

for HTML output: 6313 `\begin{warpHTML}`

`\LWR@startpars` Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```
6314 \newcommand*{\LWR@startpars}%
6315 {%
6316 % \LWR@traceinfo{\LWR@startpars}%
```

Ignore if inside a lateximage or :

```
6317 \ifboolexpr{
6318   test {\ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}} or
6319   test {\ifnumcomp{\value{\LWR@spandepth}}{>}{0}}
6320 }%
6321 }%
6322 {%
```

See if currently handling HTML paragraphs:

```
6323   \ifbool{\LWR@doingstartpars}%
```

If already in paragraph mode, do nothing.

```
6324   }%
```

If not currently in paragraph mode:

```
6325   {%
```

At the start of each paragraph, generate an opening tag:

```
6326       \PushPreHook{par}{\LWR@openparagraph}%
```

At the end of each paragraph, generate closing tag then do regular /par actions:

```
6327       \let\par\LWR@closeparagraph
6328
6329   }% an intentionally blank line
```

Are now handling paragraphs, but have not yet actually started one:

```
6330   \global\setbool{\LWR@doingstartpars}{true}%
```

No <par> tag yet to undo:

```
6331   \global\boolfalse{\LWR@doingapar}%
6332 }% nestspan
6333 % \LWR@traceinfo{\LWR@startpars: done}%
6334 }
```

`\LWR@stoppars` Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```
6335 \newcommand*{\LWR@stoppars}%
6336 {%
```

Ignore if inside a lateximage or :

```
6337 \ifboolexpr{
6338   test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
6339   test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
6340 }%
6341 {}%
6342 {%
```

See if currently handling HTML paragraphs:

```
6343   \ifbool{LWR@doingapar}%
```

if currently in an HTML paragraph:

```
6344   {%
```

Print a closing tag:

```
6345       \leavevmode\LWR@orignewline%
6346       \LWR@htmltagc{\LWR@tagregularparagraph}%
6347       \LWR@orignewline%
```

No longer have an open HTML paragraph:

```
6348       \global\boolfalse{LWR@doingapar}%
```

Disable the special minipage & \hspace interaction until a new minipage is found:

```
6349       \global\boolfalse{LWR@minipagethispar}
6350   }%
```

If was not in an HTML paragraph:

```
6351   {}%
```

See if currently allowing HTML paragraphs:

```
6352   \ifbool{LWR@doingstartpars}%
```

If so: clear the par hook to no longer catch paragraphs:

```
6353       {\ClearPreHook{par}}%
```

Else: Do nothing:

```
6354       {}%
```

No longer in paragraph mode:

```
6355   \global\setbool{LWR@doingstartpars}{false}%
```

No <p> tag to undo:

```
6356   \global\boolfalse{LWR@doingapar}%
6357 }% nestspan
6358 }

6359 \end{warpHTML}
```

54 Indentfirst

Pkg indentfirst indentfirst redefines \@afterindentfalse to be \@afterindenttrue. This is reversed \@AtBeginDocument here.

for HTML output: 6360 \begin{warpHTML}

```
6361 \AtBeginDocument{
6362   \def\@afterindentfalse{\let\if@afterindent\iffalse}
6363   \@afterindentfalse
6364 }
6365 \let\LWR@afterindent@syntaxhighlight\fi% syntax highlighting

6366 \end{warpHTML}
```

55 Page headers and footers

for HTML & PRINT: 6367 \begin{warpall}

In the following, catcode is manually changed back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
6368 \newcommand{\LWR@firstpagetop}{} % for the home page alone
6369 \newcommand{\LWR@firstpagebottom}{} % for the home page alone
6370 \newcommand{\LWR@pagetop}{} % for all other pages
6371 \newcommand{\LWR@pagebottom}{}
```

\HTMLFirstPageTop {<*text and logos*>}

```
6372 \newcommand{\HTMLFirstPageTop}[1]{%
6373   \renewcommand{\LWR@firstpagetop}{#1}%
6374 }
```

\HTMLFirstPageBottom {<*text and logos*>}

```
6375 \newcommand{\HTMLFirstPageBottom}[1]{%
6376   \renewcommand{\LWR@firstpagebottom}{#1}%
6377 }
```

`\HTMLPageTop` {*⟨text and logos⟩*}

```
6378 \newcommand{\HTMLPageTop}[1]{%
6379     \renewcommand{\LWR@pagetop}{#1}%
6380 }
```

`\HTMLPageBottom` {*⟨text and logos⟩*}

```
6381 \newcommand{\HTMLPageBottom}[1]{%
6382     \renewcommand{\LWR@pagebottom}{#1}%
6383 }
```

```
6384 \end{warpall}
```

56 CSS

for HTML output: 6385 `\begin{warpHTML}`

`\LWR@currentcss` The css filename to use. This may be changed mid-document using `\CSSFilename`, allowing different css files to be used for different sections of the document.

```
6386 \newcommand*\LWR@currentcss{lwrap.css}
```

`\CSSFilename` {*⟨new-css-filename.css⟩*} Assigns the css file to be used by the following HTML pages.

```
6387 \newcommand*\CSSFilename[1]{%
6388     \renewcommand*\LWR@currentcss{#1}%
6389     \@onelevel@sanitize\LWR@currentcss%
6390 }
6391
6392 \end{warpHTML}
```

for PRINT output: 6393 `\begin{warpprint}`
 6394 `\newcommand*\CSSFilename[1]{}`
 6395 `\end{warpprint}`

57 MathJax script

for HTML output: 6396 `\begin{warpHTML}`
 Default: `lwrap_mathjax.txt`

`\LWR@mathjaxfilename` The MathJax script filename to use. This file is copied into the head of each HTML page. This may be changed mid-document using `\MathJaxFilename`, allowing the use of a custom MathJax script, such as for a local repository, or different MathJax script files to be used for different sections of the document.

```
6397 \newcommand*\LWR@mathjaxfilename{lwrap_mathjax.txt}
```

`\MathJaxFilename` $\langle filename \rangle$ Assigns the MathJax script file to be used by the following HTML pages.

```
6398 \newcommand*\MathJaxFilename[1]{%
6399   \renewcommand*\LWR@mathjaxfilename{#1}%
6400   \@onelevel@sanitize\LWR@mathjaxfilename%
6401 }
6402
6403 \end{warpHTML}
```

for PRINT output:

```
6404 \begin{warpprint}
6405 \newcommand*\MathJaxFilename[1]{%
6406 \end{warpprint}
```

58 Title, HTML meta author, HTML meta description

for HTML output:

```
6407 \begin{warpHTML}
```

`\title` $\langle title \rangle$ Modified to remember `\thetitle`, which is used to set the HTML page titles.

```
6408 \let\LWR@origtitle\title
6409
6410 \renewcommand*\title[1]{%
6411   \LWR@origtitle{#1}%
6412   \begingroup%
6413     \renewcommand{\thanks}[1]{%
6414       \protected@xdef\thetitle{#1}%
6415     \endgroup%
6416 }
```

```
6417 \end{warpHTML}
```

for HTML & PRINT:

```
6418 \begin{warpall}
```

`\HTMLTitle` $\langle Titlename \rangle$ The Title to place into an HTML meta tag. The default is to use the document `\title`'s setting.

```
6419 \providecommand{\thetitle}{\BaseJobname}
6420
6421 \newcommand{\theHTMLTitle}{\thetitle}
6422
6423 \newcommand{\HTMLTitle}[1]{\renewcommand{\theHTMLTitle}{#1}}
```

`\HTMLAuthor` $\langle authorname \rangle$ The author to place into an HTML meta tag. If none given, the default is `\theauthor`, which is empty unless the titling package is used.

```
6424 \providecommand{\theauthor}{}
6425
6426 \newcommand{\theHTMLAuthor}{\theauthor}
6427
6428 \newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}
```

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using `\HTMLDescription`, allowing different HTML descriptions to be used for different sections of the document.

 **HTML author** Do not use double quotes, and do not exceed 150 characters.

`\HTMLDescription` `{\langle New HTML meta description.\rangle}` Assigns the HTML file's description meta tag.

```
6429 \newcommand{\LWR@currentHTMLDescription}{}
6430
6431 \newcommand{\HTMLDescription}[1]{%
6432 \renewcommand{\LWR@currentHTMLDescription}{#1}
6433 }
6434
6435 \end{warpall}
```

59 Footnotes

lwarp uses native L^AT_EX footnote code, although with its own `\box` to avoid the L^AT_EX output routine. The usual functions mostly work as-is.

footnote numbering To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For `bigfoot`, `manyfoot`, or `perpage`:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

 **MathJax, \footnotemark** If using MATHJAX, after each math expression with a `\footnotemark`, adjust the footnote counter by the number of `\footnotemarks`:

```
\[ (math expression with two instances of \footnotemark) \]
\warpHTMLonly{\addtocounter{footnote}{2}}
```

Similarly for endnotes, but *not* sidenotes.

Also for MATHJAX, `\footnotename` is used for a `\footnotemark` if the actual footnote number is not known. To redefine it, provide it before loading lwarp:

```
\providecommand{\footnotename}{something}
\usepackage{lwarp}
```

Similar for sidenotes. For endnotes:

```
\def\endnotename{something}% \def allows name to start with "end"
```

For the `pagenote` package, there is no `\pagenotename` to define, since there is no `\pagenotemark` command.

`footmisc` The `footmisc stable` option is emulated by `lwarp`.

 **sectioning commands** When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the `footmisc` package with the `stable` option, provide a short TOC entry, and `\protect` the `\footnote`:

```
\usepackage[stable]{footmisc}
...
\subsection[Subsection Name]
{Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc If using `memoir` class, with which `lwarp` preloads `footmisc`, the `stable` option must be declared before `lwarp` is loaded:

 **memoir**

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
...
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handle differently.

59.1 Regular page footnotes

In HTML documents, footnotes are placed at the bottom of the web page or the section, depending on `FootnoteDepth`, using the L^AT_EX box `\LWR@footnotebox`. Using this instead of the original `\footins` box avoids having footnotes be printed by the output routine, since footnotes should be printed per HTML page instead of per PDF page.

See section 59.4 for the implementation.

59.2 Minipage footnotes

See section 59.5 for how minipage footnotes are gathered. See section 92.4 for how minipage footnotes are placed into the document.

59.3 Titlepage thanks

See section 67.7 for titlepage footnotes.

59.4 Regular page footnote implementation

for HTML & PRINT: `6436 \begin{warpall}`

Ctr FootnoteDepth Determines how deeply to place footnotes in the HTML files, similar to tocdepth. The default of 3 places footnotes before each `\subsubsection` or higher. See table 11 for a table of L^AT_EX section headings.

Default: 3

```
6437 \newcounter{FootnoteDepth}
6438 \setcounter{FootnoteDepth}{3}
```

Ctr footnoteReset If non-zero, the footnote counter is reset to this value each time the footnotes are printed, as controlled by FootnoteDepth. For the manyfoot and bigfoot packages, additional counters such as footnote<suffix>Reset will be defined as well. These counters may be set non-zero by the user, and are also set if the perpage's `\MakePerPage` or `\MakeSortedPerPage` macros are used for the footnote or footnote<suffix> counters.

Default: 0

(The name is not capitalized because it is made from the counter's name with "Reset" appended.)

```
6439 \newcounter{footnoteReset}
6440 \setcounter{footnoteReset}{0}
```

```
6441 \end{warpall}
```

for HTML output: 6442 `\begin{warpHTML}`

`\LWR@footnotebox` Patch L^AT_EX footnotes to use a new `\box` instead of an insert for lwarp footnotes. This avoids having the original `\footins` appear at the bottom of a `lateximage`, which is on its own new page.

```
6443 \newbox\LWR@footnotebox
```

Much of the following has unneeded print-mode formatting removed.

`\@makefntext` `{\langle text \rangle}`

```
6444 \long\def\@makefntext#1{\textsuperscript{\@thefnmark}~#1}
```

`\@makefnmark`

```
6445 \def\@makefnmark{%
6446   \textsuperscript{\@thefnmark}%
6447 }
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or `lateximage`, in which case paragraph tags must be added manually.

In a `lateximage` during HTML output, the `lateximage` is placed inside a print-mode `minipage`, but the footnotes are broken out by:

```
\def\@mpfn{footnote}
\def\@thempfn{\thefootnote}
\let\@footnotetext\LWR@footnotetext
```

```
\LWR@@footnotetext {<text>} {<footnote box name>}
```

Factored to allow multiple footnote boxes for manyfoot.

```
6448 \long\def\LWR@@footnotetext#1#2{%
6449 \LWR@traceinfo{LWR@footnotetext}%
6450 \global\setbox\csname #2\endcsname=\vbox{%
```

Add to any current footnotes:

```
6451 \unvbox\csname #2\endcsname%
```

Remember the footnote number for \ref:

```
6452 \protected@edef\@currentlabel{%
6453 \csname p@footnote\endcsname\@thefnmark%
6454 }% @currentlabel
```

Open a group:

```
6455 \color@begingroup%
```

Disable CJK xpinyin while generating footnotes.

```
6456 \LWR@disablepinyin%
```

Use HTML superscripts in the footnote even when the main text is inside a lateximage, because the footnote will be in HTML:

```
6457 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
6458 \ifthenelse{%
6459 \boolean{LWR@doingstartpars} \AND%
6460 \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
6461 }%
6462 {}%
6463 {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@originewline}%
```

Append the footnote to the list:

```
6464 \@makefntext{#1}%
```

Closing paragraph tag:

```
6465 \ifthenelse{%
6466 \boolean{LWR@doingstartpars} \AND%
6467 \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
6468 }%
6469 {\par}%
6470 {%
6471 \LWR@htmltagc{/\LWR@tagregularparagraph}%
```

```
6472         \LWR@orignewline%
6473     }%
```

Close the group:

```
6474     \color@endgroup%
6475 }% vbox
```

Paragraph handling:

```
6476 \LWR@ensuredoingapar%
6477 }%
```

```
\LWR@footnotetext {<text>}
```

```
6478 \long\def\LWR@footnotetext#1{\LWR@@footnotetext{#1}{LWR@footnotebox}}
```

```
\@footnotetext {<text>}
```

```
6479 \LetLtxMacro\@footnotetext\LWR@footnotetext
```

59.5 Minipage footnote implementation

Patch \LaTeX minipage footnotes to use a new `\box` instead of an insert for `lwarp` minipage footnotes. This avoids having the original `\@mpfootins` appear at the bottom of a `lateximage`, which is on its own new page.

```
6480 \newbox\LWR@mpfootnotes
```

```
\@mpfootnotetext {<text>}
```

```
6481 \long\def\@mpfootnotetext#1{%
6482 \LWR@traceinfo{@mpfootnotetext}%
6483 \global\setbox\LWR@mpfootnotes\vbox{%
6484     \unvbox\LWR@mpfootnotes%
6485     \reset@font\footnotesize%
6486     \hsize\columnwidth%
6487     \@parboxrestore%
6488     \protected@edef\@currentlabel%
6489         {\csname p@mpfootnote\endcsname\@thefnmark}%
6490     \color@begingroup%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
6491     \ifthenelse{%
6492         \boolean{LWR@doingstartpars} \AND%
6493         \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
6494     }%
6495     {}%
6496     {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%

```

```

6497 \@makefntext{%
6498 \ignorespaces#1%
6499 }%

```

Don't add the closing paragraph tag if are inside a lateximage:

```

6500 \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}{>}{0}}%
6501 {}%
6502 {%
6503 \leavevmode\LWR@orignewline%
6504 \LWR@htmltagc{/LWR@tagregularparagraph}%
6505 \LWR@origpar%
6506 }%
6507 \color@endgroup%
6508 }% vbox

```

Paragraph handling:

```

6509 \LWR@ensuredoingapar%
6510 \LWR@traceinfo{@mpfootnotetext: done}%
6511 }

```

`\thempfootnote` Redefined to remove the `\itshape`, which caused an obscure compiling error in some situations.

```

6512 \AtBeginDocument{
6513 \def\thempfootnote{\@alph\c@mpfootnote}
6514 }

```

59.6 Printing pending footnotes

`\LWR@printpendingfootnotes` $\{ \langle footnote\ counter\ name \rangle \}$

```

6515 \newcommand*{\LWR@printpendingfootnotes}[1]{%
6516 \expandafter\ifvoid\c@name LWR@#1box\endcsname\else
6517 \LWR@forcenewpage
6518 \begin{BlockClass}{footnotes}
6519 \null
6520 \unvbox\csuse{LWR@#1box}
6521 \setbox\csuse{LWR@#1box}=\vbox{}
6522 \end{BlockClass}
6523 \ifltxcounter{#1Reset}{%
6524 \ifnumgreater{\value{#1Reset}}{0}{%
6525 \setcounter{#1}{\value{#1Reset}}%
6526 \addtocounter{#1}{-1}%
6527 }{}%
6528 }{}%
6529 \fi
6530 }

```

`\LWR@printpendingfootnotes` Enclose the footnotes in a class, print, then clear. For `manynotes`, new footnotes may be added via `\appto`.

```
6531 \newcommand*\LWR@printpendingfootnotes}{%
6532   \LWR@printpendingfootnotes{footnote}%
6533 }
```

`\LWR@maybeprintpendingfootnotes` `{<depth>}` Used to print footnotes before sections only if formatting for an EPUB or word processor:

```
6534 \newcommand*\LWR@maybeprintpendingfootnotes}[1]{%
6535   \ifboolexpr{
6536     not test{\ifnumcomp{#1}{>}{\value{FootnoteDepth}}} or
6537     bool{FormatEPUB} or
6538     bool{FormatWP}
6539   }%
6540   {\LWR@printpendingfootnotes}%
6541   }%
6542 }
```

`\LWR@printpendingmpfootnotes` Enclose the minipage footnotes in a class, print, then clear.

```
6543 \newcommand*\LWR@printpendingmpfootnotes}{%
6544   \ifvoid\LWR@mpfootnotes\else
6545     \LWR@forcenewpage
6546     \begin{BlockClass}{footnotes}
6547     \null
6548     \unvbox\LWR@mpfootnotes
6549     \setbox\LWR@mpfootnotes=\vbox{}
6550     \end{BlockClass}
6551   \fi
6552 }

6553 \end{warpHTML}
```

60 Marginpars

`\marginpar` [`<left>`] [`<right>`] `\marginpar` may contain paragraphs, but in order to remain inline with the surrounding text `lwarp` nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `
` tags.

`\marginparBlock` [`<left>`] [`<right>`] To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a ``. A line break will occur in the text where the `\marginparBlock` occurs.

for HTML output: `6554 \begin{warpHTML}`

`\marginpar` [`<left>`] [`<right>`]

```

6555 \renewcommand{\marginpar}[2][]{%
6556 \ifbool{FormatWP}%
6557 {%
6558 \begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{\marginblock}
6559 #2
6560 \end{LWR@BlockClassWP}
6561 }%
6562 {%
6563 \LWR@htmlspanclass{\marginpar}{#2}%
6564 }%
6565 }

```

`\marginparBlock` [*left*] [*right*]

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

HTML version.

```

6566 \newcommand{\marginparBlock}[2][]{%
6567 \LWR@stoppars%
6568 \ifbool{FormatWP}%
6569 {%
6570 \begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{\marginblock}
6571 #2
6572 \end{LWR@BlockClassWP}
6573 }%
6574 \begin{BlockClass}[width:2in; float:right; margin:10pt]{marginparblock}
6575 #2
6576 \end{BlockClass}
6577 }%
6578 \LWR@startpars%
6579 }

```

`\reversemarginpar`

```
6580 \renewcommand*{\reversemarginpar}{}

```

`\normalmarginpar`

```
6581 \renewcommand*{\normalmarginpar}{}

```

```
6582 \end{warpHTML}

```

for PRINT output: 6583 \begin{warpprint}

`\marginparBlock` [*left*] [*right*]

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

Print version.

```
6584 \LetLtxMacro\marginparBlock\marginpar
```

```
6585 \end{warpprint}
```

61 Splitting HTML files

- Files are split according to FileDepth and CombineHigherDepths.
- Filenames are sanitized by \LWR@filenameno blanks.
- \LWR@newhtmlfile finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

for HTML & PRINT: 6586 \begin{warpall}

Ctrl FileDepth *{<section depth>}* determines how deeply to break into new HTML files, similar to tocdepth. The default of -5 produces one large HTML file.

```
6587 \newcounter{FileDepth}
6588 \setcounter{FileDepth}{-5}
```

Bool CombineHigherDepths Combile higher-level sections together into one file?

```
6589 \newbool{CombineHigherDepths}
6590 \booltrue{CombineHigherDepths}
```

\FilenameLimit Maximum length of the generated filenames.

```
6591 \newcommand*{\FilenameLimit}{80}

6592 \end{warpall}
```

for HTML output: 6593 \begin{warpHTML}

\LWR@thisfilename The currently-active filename or number. At first, this is the homepage.

```
6594 \AtBeginDocument{
6595 \ifbool{FileSectionNames}%
6596   {\newcommand*\LWR@thisfilename{\HomeHTMLFilename}}
6597   {\newcommand*\LWR@thisfilename{0}}
6598 }
```

\LWR@thisnewfilename The filename being sanitized.

```
6599 \newcommand*\LWR@thisnewfilename{}
```

`\LWR@simplifiname` * $\langle expression \rangle$ Simplify `\LWR@thisnewfilename`.

If starred, detokenizes the input expression. If found, changes the expression to a single detokenized dash.

```
6600 \NewDocumentCommand{\LWR@simplifiname}{s m}{%
6601 \IfBooleanTF{#1}{%
6602   \StrSubstitute{\LWR@thisnewfilename}%
6603     {\detokenize{#2}}%
6604     {\detokenize{-}}[\LWR@thisnewfilename]%
6605 }{%
6606   \StrSubstitute{\LWR@thisnewfilename}%
6607     {#2}%
6608     {\detokenize{-}}[\LWR@thisnewfilename]%
6609 }
6610 }
```

`\LWR@simplifycustom` User-defined filename simplifications. Redefine with `\newcommand`.

```
6611 \newcommand*{\LWR@simplifycustom}{}%
```

`\FilenameSimplify` * $\langle phrase \rangle$ Assign a user-defined filename simplification. Appends to `\LWR@simplifycustom`.

```
6612 \NewDocumentCommand{\FilenameSimplify}{s m}{%
6613 \IfBooleanTF{#1}{%
6614   \appto{\LWR@simplifycustom}{%
6615     \LWR@simplifiname*{#2}%
6616   }%
6617 }{%
6618   \appto{\LWR@simplifycustom}{%
6619     \LWR@simplifiname{#2}%
6620   }%
6621 }%
6622 }
```

`\LWR@avoiddupfilenames` Instructions for how to avoid duplicate filenames. This is used in a warning in `\LWR@filenamenoblanks`, and in an error in `\LWR@newhtmlfile`.

```
6623 \newcommand*{\LWR@avoiddupfilenames}{%
6624   To avoid duplicate filenames, use the optional\MessageBreak
6625   short Table of Contents entry:\MessageBreak
6626   \space\space\protect\section[Unique name, no math]{Name with math}%
6627   \MessageBreak
6628   or use \protect\texorpdfstring, from the hyperref package:\MessageBreak
6629   \space\space%
6630   \protect\section{\MessageBreak
6631     \space\space\space\space\protect\texorpdfstring\MessageBreak
6632     \space\space\space\space\space\space%
6633     {Name with math}{Unique name, no math}\MessageBreak
6634   \space\space}
6635 }
```

`\LWR@filenamoblanks` $\{ \langle filename \rangle \}$

Convert blanks into dashes, removes short words, store result in `\LWR@thisfilename`.

Also see `\LWR@nullfonts` for nullified macros.

```
6636 \newcommand*{\LWR@filenamoblanks}[1]{%
6637 \begingroup
```

Locally temporarily disable direct-formatting commands, not used in filenames:

```
6638 \LWR@nullfonts%
6639 \renewcommand*{\LWR@htmltagc}[1]{%
```

```
6640 \edef\LWR@thisnewfilename{#1}%
```

Replaces common macros with hyphens. (`\&` is done by `\LWR@nullfonts`.)

```
6641 \RenewDocumentCommand{\LWR@subsingledollar}{s m m}{}%
6642 \LWR@simplifiname{\_}
6643 \LWR@simplifiname{\#}
6644 \LWR@simplifiname{\textbackslash}
6645 \LWR@simplifiname{\protect}
6646 \LWR@simplifiname{\ }
6647 \LWR@simplifiname{\textless}
6648 \LWR@simplifiname{\textgreater}
```

```
6649 \edef\LWR@thisnewfilename{\detokenize\expandafter{\LWR@thisnewfilename}}%
```

Warn if there is dollar math in the section name:

```
6650 \ifbool{FileSectionNames}{%
6651   \IfSubStr{\LWR@thisnewfilename}{\LWRdollar}{%
6652     \PackageWarning{lwarp}
6653     {%
6654       This section name:\MessageBreak
6655       \space\space‘\detokenize\expandafter{#1}’\MessageBreak
6656       at the line number listed below,\MessageBreak
6657       is using $dollar-delimited math$,
6658       which generates\MessageBreak
6659       complicated file names. It is better to use\MessageBreak
6660       \space\space%
6661       \protect\section{Name with \protect\(\parenthesis math\protect\)}%
6662       \MessageBreak
6663       The math then will be removed from the file name.\MessageBreak
6664       \MessageBreak
6665       \LWR@avoiddupfilenames%
6666       \MessageBreak
6667       This section is found before or%
6668     }
6669   }{}%
6670 }
```

```
6671 \LWR@traceinfo{LWR@filenamoblanks edef: !\LWR@thisnewfilename!}%
6672 \fullexpandarg%
```

Convert spaces into hyphens:

```
6673 \LWR@simplifiname*{ }
```

Convert punctutation into hyphens:

```
6674 \LWR@simplifiname*{*}
6675 \LWR@simplifiname*{(}
6676 \LWR@simplifiname*{)}
6677 \LWR@simplifiname*{.}
6678 \LWR@simplifiname*{!}
6679 \LWR@simplifiname*{,}
6680 \LWR@simplifiname*{'}
6681 \LWR@simplifiname*{+}
6682 \LWR@simplifiname*{/}
6683 \LWR@simplifiname*{:}
6684 \LWR@simplifiname*{;}
6685 \LWR@simplifiname*{=}
6686 \LWR@simplifiname*{?}
6687 \LWR@simplifiname*{@}
6688 \LWR@simplifiname*{^}
6689 \LWR@simplifiname*{&}
6690 \LWR@simplifiname*{"}
6691 \LWR@simplifiname*{<}
6692 \LWR@simplifiname*{>}
```

```
6693 \LWR@simplifiname{\LWRbackslash}
```

Braces are removed entirely to avoid extra dashes in the result.

```
6694 \StrSubstitute{\LWR@thisnewfilename}%
6695   {\LWRleftbrace}{[\LWR@thisnewfilename]}%
6696 \StrSubstitute{\LWR@thisnewfilename}%
6697   {\LWRrightbrace}{[\LWR@thisnewfilename]}%
```

```
6698 \LWR@simplifiname{\LWRpercent}
6699 \LWR@simplifiname{\LWRdollar}
```

```
6700 \LWR@simplifiname*{|}
6701 \LWR@simplifiname*{^}
6702 \LWR@simplifiname*{~}
6703 \LWR@simplifiname*{[}
6704 \LWR@simplifiname*{]}
6705 \LWR@simplifiname*{'}
```

Convert short words:

```
6706 \LWR@simplifiname*{-s-}
6707 \LWR@simplifiname*{-S-}
6708 \LWR@simplifiname*{-a-}
```

```

6709 \LWR@simplifynam*{-A-}
6710 \LWR@simplifynam*{-an-}
6711 \LWR@simplifynam*{-AN-}
6712 \LWR@simplifynam*{-to-}
6713 \LWR@simplifynam*{-TO-}
6714 \LWR@simplifynam*{-by-}
6715 \LWR@simplifynam*{-BY-}
6716 \LWR@simplifynam*{-of-}
6717 \LWR@simplifynam*{-OF-}
6718 \LWR@simplifynam*{-and-}
6719 \LWR@simplifynam*{-AND-}
6720 \LWR@simplifynam*{-for-}
6721 \LWR@simplifynam*{-FOR-}
6722 \LWR@simplifynam*{-the-}
6723 \LWR@simplifynam*{-THE-}

```

Convert custom words:

```
6724 \LWR@simplifycustom%
```

If pdfL^AT_EX and not utf8 encoding, don't try to convert emdash, endash:

```

6725 \ifPDFTeX% pdflatex or dvi latex
6726 \ifdefstring{\inputencodingname}{utf8}{}%
6727   \LWR@simplifynam*{-}
6728 %   emdash
6729   \LWR@simplifynam*{-}
6730 %   endash
6731 }{}%
6732 \else% not PDFTeX
6733   \LWR@simplifynam*{-}
6734   \LWR@simplifynam*{-}
6735 \fi%

```

Convert multiple hyphens:

```

6736 \LWR@simplifynam*{-----}
6737 \LWR@simplifynam*{----}
6738 \LWR@simplifynam*{---}
6739 \LWR@simplifynam*{--}

```

If starts with a dash, remove the leading dash:

```

6740 \IfBeginWith{\LWR@thisnewfilename}{\detokenize{-}}{%
6741   \StrGobbleLeft{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
6742 }{}%

```

If ends with a dash, remove the trailing dash:

```

6743 \IfEndWith{\LWR@thisnewfilename}{\detokenize{-}}{%
6744   \StrGobbleRight{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
6745 }{}%

```

Limits the length of the filename:

```
6746 \StrLeft{\LWR@thisnewfilename}{\FilenameLimit}[\LWR@thisnewfilename]%
```

Return the global result:

```
6747 \global\let\LWR@thisfilename\LWR@thisnewfilename%
6748 \endgroup%
6749 \LWR@traceinfo{\LWR@filenamenooblanks: result is \LWR@thisfilename}%
6750 }
```

Ctrl Remembers which autopage label was most recently generated. Used to avoid dupli-
LWR@previousautopagelabel cates.

```
6751 \newcounter{\LWR@previousautopagelabel}
6752 \setcounter{\LWR@previousautopagelabel}{-1}
```

File *_html.aux A new entry in the *_html.aux file is used to help cross-references:

```
\newlabel{autopage-<nnn>}{<x>}{<y>}}
```

LWR@newautopagelabel {<pagenumber counter>}

LWR@newautopagelabel \BaseJobname is added to the label in case xr or xr-hyper are used.

```
6753 \newcommand*{\LWR@newautopagelabel}[1]{%
6754 \ifnumequal{\value{\LWR@previousautopagelabel}}{\value{page}}%
6755 {}% no action if this autopage label has already been defined
6756 {%
6757 \label{\BaseJobname-autopage-\arabic{#1}}%
6758 \setcounter{\LWR@previousautopagelabel}{\value{page}}
6759 }%
6760 }
```

61.1 Sanitizing expressions for HTML

Math expressions are converted to lateximages, and some math environments may contain &, <, or >, which should not be allowed inside an HTML <alt> tag, so must convert them to HTML entities.

LWR@replacestrings {<search>} {<replace>}

Replaces strings inside \tmpb.

Modified from the original, by PETR OLSAK, from the opmac package.

```
6761 \bgroup
6762 \catcode'\!=3 \catcode'\?=3
6763
6764 \long\gdef\LWR@replacestrings@addto#1#2{%
```

```

6765 \expandafter\def\expandafter#1\expandafter{#1#2}%
6766 }
6767
6768 \gdef\LWR@replacestrings#1#2{%
6769 \long\def\LWR@replacestringsA##1#1{\def\tmpb{##1}\LWR@replacestringsB}%
6770 \long\def\LWR@replacestringsB##1#1{%
6771 \ifx!##1\relax \else\LWR@replacestrings@addto\tmpb{#2##1}%
6772 \expandafter\LWR@replacestringsB\fi%
6773 }% improved version <May 2016> inspired
6774 \expandafter\LWR@replacestringsA\tmpb?#1!#1% from pysyntax.tex by Petr Krajnik
6775 \long\def\LWR@replacestringsA##1?{%
6776 \def\tmpb{##1}%
6777 }\expandafter\LWR@replacestringsA\tmpb%
6778 }
6779 \egroup

```

`Bool` `LWR@MathJax@silentquotes` If true, double quotes (\ " and ") are removed (used for mathspec). This unfortunately includes double quotes used inside `\text` with `MATHJAX`. If false, double quotes are escaped.

```

6780 \newbool{LWR@MathJax@silentquotes}
6781 \boolfalse{LWR@MathJax@silentquotes}

```

`\LWR@subHTMLsanitize` `\LWR@strresult` must first be set by `\LWR@HTMLsanitize`, `\LWR@HTMLsanitizeexpand`, or `\CustomizeMathJax`.

```

6782 \catcode'\#=12
6783 \catcode'\&=12
6784 \newcommand{\LWR@subHTMLsanitize}{%

```

The `&`, `<`, and `>` may be interpreted by the browser:

```

6785 \edef\tmpb{\detokenize\expandafter{\LWR@strresult}}%
6786 \LWR@replacestrings{&}{&};%
6787 \LWR@replacestrings{<}{&lt;};%
6788 \LWR@replacestrings{>}{&gt;};%

```

The quotes occasionally causes problems. For `mathspec`, also allow neutralization of `\` " and the `"` character.

```

6789 \ifbool{LWR@MathJax@silentquotes}
6790 {%
6791 \expandafter\LWR@replacestrings\expandafter{\LWRbackslash"}{}}%
6792 \LWR@replacestrings{"}{}}%
6793 }%
6794 {\LWR@replacestrings{"}{&quot;}}%
6795 \LWR@replacestrings{'}{&apos;}}%
6796 \LWR@replacestrings{'}{&grave;}}%

```

`MathJax` allows expressions to be defined with `\newcommand`. These expressions would appear with `##` for each argument, and each must be changed to a single `#`. This must

be done after all the above changes. Attempting another conversion after this causes an error upon further expansion.

```
6797 \LWR@replacestrings{##}{#}%
6798 \edef\LWR@strresult{\detokenize\expandafter{\tmpb}}%
6799 }
6800 \catcode'\#=6
6801 \catcode'\&=4
```

`\LWR@HTMLsanitize` $\langle text \rangle$

```
6802 \newrobustcmd{\LWR@HTMLsanitize}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
6803 \begingroup%
6804 \LWR@FBcancel%
6805 \edef\LWR@strresult{\detokenize{#1}}%
6806 \LWR@subHTMLsanitize%
6807 \LWR@strresult%
6808 \endgroup%
6809 }
```

`\LWR@HTMLsanitizeexpand` $\langle text \rangle$

This version expands the argument before sanitizing it. This is only used for adding math to `MATHJAX` expressions or `lateximage alt` tags.

```
6810 \edef\LWR@beginspaceleftbrace{begin \LWRleftbrace}
6811 \edef\LWR@beginspaceleftbrace{\detokenize\expandafter{\LWR@beginspaceleftbrace}}
6812 \edef\LWR@beginleftbrace{begin\LWRleftbrace}
6813 \edef\LWR@beginleftbrace{\detokenize\expandafter{\LWR@beginleftbrace}}
6814
6815 \edef\LWR@endspacerightbrace{end \LWRrightbrace}
6816 \edef\LWR@endspacerightbrace{\detokenize\expandafter{\LWR@endspacerightbrace}}
6817 \edef\LWR@endrightbrace{end\LWRrightbrace}
6818 \edef\LWR@endrightbrace{\detokenize\expandafter{\LWR@endrightbrace}}
6819
6820 \newrobustcmd{\LWR@HTMLsanitizeexpand}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
6821 \begingroup%
6822 \LWR@FBcancel%
```

The difference between this and `\LWR@HTMLsanitize` (without “expand”) is the following `\expandafter`:

```
6823 \edef\LWR@strresult{\detokenize\expandafter{#1}}%
```

The math expression may includes spaces between tokens, but MATHJAX does not want a space between `\begin` or `\end` and the following brace. This space is removed here.

```
6824 \protect\StrSubstitute{\LWR@strresult}%
6825     {\LWR@beginspaceleftbrace}{\LWR@beginleftbrace}[\LWR@strresult]%
6826 \protect\StrSubstitute{\LWR@strresult}%
6827     {\LWR@endspacerightbrace}{\LWR@endrightbrace}[\LWR@strresult]%

6828 \LWR@subHTMLsanitize%
6829 \LWR@strresult%
6830 \endgroup%
6831 }
```

61.2 Customizing MATHJAX

`\LWR@customizedMathJax` Additional MATHJAX definitions to be added to the start of each HTML page.

```
6832 \newcommand*{\LWR@customizedMathJax}{}
```

Bool Used to issue only one warning about using a `\CustomizeMathJax` per macro.

`LWR@warnedcustomizemathjax`

```
6833 \newbool{LWR@warnedcustomizemathjax}
6834 \boolfalse{LWR@warnedcustomizemathjax}
```

`\LWR@subcustomizedmathjax` {*macro definition*}

```
6835 \newcommand*{\LWR@subcustomizedmathjax}[1]{%
6836   \begingroup%
6837   \LWR@FBcancel%
6838   \edef\LWR@strresult{\detokenize{#1}}%
6839   \LWR@subHTMLsanitize%
6840   \xdef\LWR@customizedMathJax{%
6841     \LWR@customizedMathJax%
6842     \LWR@strresult%
6843   }%
6844   \endgroup%
6845 }
6846 \@onlypreamble\LWR@subcustomizedmathjax
```

`\CustomizeMathJax` {*macro definition*}

A warning is issued if a very long argument is given.

```
6847 \newcommand*{\CustomizeMathJax}[1]{%
6848   \ifbool{LWR@warnedcustomizemathjax}{}{%
6849     \StrLen{\detokenize{#1}}[\LWR@tempone]%
6850     \ifnumgreater{\LWR@tempone}{200}{%
6851       \AtEndDocument{%
6852         \PackageWarningNoLine{lwarp}{%
```

```

6853             To ensure faster MathJax compilation, place each\MessageBreak
6854             custom macro in its own \protect\CustomizeMathJax.\MessageBreak
6855             See the Lwarp documentation regarding customizing\MessageBreak
6856             MathJax%
6857             }%
6858         }%
6859         \booltrue{LWR@warnedcustomizemathjax}%
6860     }{}%
6861 }%
6862 \appto\LWR@customizedMathJax{\LWRbackslash{}}%
6863 \LWR@subcustomizedmathjax{#1}%
6864 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
6865 }
6866 \@onlypreamble\CustomizeMathJax

```

`\LWR@infoprocessingmathjax` $\{(\textit{package name})\}$

```

6867 \newcommand*{\LWR@infoprocessingmathjax}[1]{%
6868 \typeout{---}
6869 \typeout{Package lwarp: Processing MathJax customizations for #1.}
6870 \typeout{\space\space This may take a moment.}
6871 \typeout{---}
6872 }

```

defaults Default customizations:

In the MATHJAX code, footnotes are only referenced. For equations, they are also generated in the HTML when the L^AT_EX math is generated inside the HTML comment. For other math environments, the `\footnotemark/\footnotetext` method must be used. See section 8.5.4 regarding `\footnotemark`.

 `\footnotemark`

For footnotes, `\footnotename` is used in most cases, however for equation the footnote is picked up from L^AT_EX in `\LWR@doendequation`.

First, `\footnotename` for MATHJAX is copied from L^AT_EX.

```

6873 \providecommand{\footnotename}{footnote}
6874
6875 % due to warpMathJax:
6876 \end{warpHTML}
6877
6878 \begin{warpMathJax}
6879 \xdef\LWR@customizedMathJax{\LWR@customizedMathJax%
6880     \LWRbackslash(%
6881     \LWRbackslash{}newcommand%
6882     \{\LWRbackslash{}footnotename\}%
6883     \{\footnotename\}%
6884     \LWRbackslash)\par%
6885 }
6886 \end{warpMathJax}

```

`\LWRfootnote` is set per equation if a footnote is detected in the equation's math expression, otherwise it defaults to `\footnotename`.

```

6887 \begin{warpMathJax}
6888 \CustomizeMathJax{\def\LWRfootnote{1}}
6889 \CustomizeMathJax{\newcommand{\footnote}[2][\LWRfootnote]{\mathrm{#1}}}
6890 \CustomizeMathJax{\newcommand{\footnotemark}[1][\LWRfootnote]{\mathrm{#1}}}

```

Various other customizations:

```

6891 \CustomizeMathJax{\newcommand{\mathnormal}[1]{#1}}
6892 \CustomizeMathJax{\newcommand\ensuremath[1]{#1}}
6893 \CustomizeMathJax{% absorb two optional arguments
6894     \newcommand{\LWRframebox}[2][\fbox{#2}}
6895     \newcommand{\framebox}[1][\LWRframebox}
6896 }
6897 \CustomizeMathJax{\newcommand{\setlength}[2]{}}
6898 \CustomizeMathJax{\newcommand{\addtolength}[2]{}}
6899 \CustomizeMathJax{\newcommand{\setcounter}[2]{}}
6900 \CustomizeMathJax{\newcommand{\addtocounter}[2]{}}
6901 \CustomizeMathJax{\newcommand{\cline}[1]{}}
6902 \CustomizeMathJax{\newcommand{\directlua}[1]{\text{(directlua)}}}
6903 \CustomizeMathJax{\newcommand{\luatexdirectlua}[1]{\text{(directlua)}}}

```

`\protect`, `\mathchar`, and `\delimiter` are silently discarded; and `\mathcode` and `\delcode` are ignored.

```

6904 \CustomizeMathJax{\newcommand{\protect}{}}
6905 \CustomizeMathJax{\def\LWRabsorbnumber#1 {}}
6906 \CustomizeMathJax{\def\LWRabsorbquotenumber"#1 {}}
6907 \CustomizeMathJax{\def\mathchar{\ifnextchar\LWRabsorbquotenumber\LWRabsorbnumber}}
6908 \CustomizeMathJax{\def\mathcode#1={\mathchar}}
6909 \CustomizeMathJax{\let\delcode\mathcode}
6910 \CustomizeMathJax{\let\delimiter\mathchar}
6911 \end{warpMathJax}
6912
6913 \begin{warpHTML}% due to warpMathJax

```

`\LWR@customizeMathJax` Prints MathJax commands to the HTML output.

```

6914 \newcommand{\LWR@customizeMathJax}{%
6915 \ifbool{mathjax}{

6916 \LWR@stoppars
6917 \LWR@htmlcomment{MathJax customizations:}
6918
6919 \begin{BlockClass}{hidden}
6920 \LWR@stoppars

```

Avoid ligatures while printing MATHJAX customizations:

```

6921 {
6922     \LWR@print@ttfamily
6923     \LWR@customizedMathJax
6924 }
6925 \LWR@startpars

```

```

6926 \end{BlockClass}
6927
6928 \LWR@startpars
6929 }{}
6930 }

```

```

6931 \end{warpHTML}

```

for PRINT output: 6932 \begin{warpprint}

\CustomizeMathJax The print-mode version:

```

6933 \newcommand*\CustomizeMathJax[1]{}

```

\FilenameSimplify * $\langle expression \rangle$

```

6934 \NewDocumentCommand{\FilenameSimplify}{s m}{}

```

```

6935 \end{warpprint}

```

for HTML output: 6936 \begin{warpHTML}

\LWR@createfooter If specified, create the first or later web page footer.

```

6937 \newcommand*\LWR@createfooter{%
6938   \ifnumless{\value{LWR@htmlseqfilenumber}}{1}{%
6939     \ifdefempty{\LWR@firstpagebottom}{%
6940       \LWR@htmlElement{footer}
6941
6942       \LWR@firstpagebottom
6943
6944       \LWR@htmlElementend{footer}
6945     }%
6946   }{%
6947     \ifdefempty{\LWR@pagebottom}{%
6948       \LWR@htmlElement{footer}
6949
6950       \LWR@pagebottom
6951
6952       \LWR@htmlElementend{footer}
6953     }%
6954   }%
6955 }

```

\LWR@newhtmlfile $\langle section name \rangle$

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and CSS are, then adds navigation, side TOC, header, and starts the text body.

```

6956 \newcommand*\LWR@newhtmlfile[1]{
6957 \LWR@traceinfo{LWR@newhtmlfile}

```

At the bottom of the ending file:

```
6958 \LWR@htmlelementclassend{section}{tbody}
6959 \LWR@htmlelementclassend{div}{bodycontainer}
6960 \LWR@htmlelementclassend{div}{bodyandsidetoc}
6961
6962 \LWR@printpendingfootnotes
6963
```

No footer between files if EPUB:

```
6964 \ifbool{FormatEPUB}{\LWR@createfooter}
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
6965 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
6966   {}
6967   {\ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}}
```

End of this HTML file:

```
6968 \LWR@stoppars
6969 \LWR@htmltag{/body}\LWR@orignewline
6970 \LWR@htmltag{/html}\LWR@orignewline
6971 \LWR@traceinfo{LWR@newhtmlfile: about to LWR@orignewpage}
6972 \LWR@maybe@orignewpage
```

```
6973 \addtocounter{LWR@htmlfilenumber}{1}%
6974 \addtocounter{LWR@htmlseqfilenumber}{1}%
```

If using a filename based on section name, create a version without blanks. The filename without blanks will be placed into \LWR@thisfilename. Duplicates will be detected using MD5 hashes.

If not using a filename, the file number will be used instead.

```
6975 \ifbool{FileSectionNames}%
6976 {%
```

Convert the section name to a filename with blanks and common words removed. The resulting filename is in \LWR@thisfilename.

```
6977   \LWR@filenamenoblanks{#1}%
```

Create a macro name from the MD5 hash of the file name, to detect duplicates:

```
6978   \edef\LWR@hashedname{\LWR@mdfive{\LWR@thisfilename}}%
```

If the macro name is not yet defined, this filename is unique.

```
6979   \ifcsundef{LWR@filename\LWR@hashedname}{%
```

If the filename is unique, create a macro using the hashed name, to be used to test for additional duplicates in the future.

```
6980     \csdef{LWR@filename\LWR@hashedname}{}%
6981     }{%
```

If the filename is not unique, create an error.

```
6982     \PackageError{lwarp}%
6983     {%
6984         The section name:\MessageBreak
6985         ‘‘#1’’,\MessageBreak
6986         at the line number listed below,\MessageBreak
6987         generates the filename\MessageBreak
6988         ‘‘\LWR@thisfilename’’,\MessageBreak
6989         which appears to be a duplicate. There is a\MessageBreak
6990         previous section with an identical or similar name.\MessageBreak
6991         While generating file names, Lwarp sanitizes math,\MessageBreak
6992         most symbols, and a few common short words,\MessageBreak
6993         and this may cause a conflict.\MessageBreak
6994         Enter ‘H’ for possible solutions%
6995     }%
6996     {%
6997         \LWR@avoiddupfilenames%
6998     }%
6999 }%
7000 }%
```

If using file numbers instead of names, the name is set to the next file number.

```
7001 {\renewcommand*{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}
```

Include an HTML comment to instruct lwarpmk where to split the files apart. Uses pipe-separated fields for `split_html.gawk`. Uses monospaced font with ligatures disabled for everything except the title.

```
7002 \LWR@traceinfo{LWR@newhtmlfile: about to print start file}%
```

`\LWR@nullfonts` to allow math in a section name.

```
7003 \begingroup%
7004 \LWR@nullfonts%
7005 \LWR@htmlblockcomment{%
7006 |Start file|%
7007 \LWR@htmlsectionfilename{\LWR@thisfilename}|%
7008 }
7009 \endgroup%
```

At the top of the starting file:

```
7010 \LWR@stoppars
7011
```

Start a new file with the given section name:

```
7012 \LWR@filestart[#1]
7013
```

Track the PDF page numbers of the HTML output:

```
7014 \setcounter{LWR@latestautopage}{\value{page}}%
7015 \LWR@newautopagelabel{LWR@latestautopage}%
```

No navigation between files if formatting for an EPUB or word processor:

```
7016 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
7017   {}
7018   {\LWR@topnavigation}
7019
```

No header if between files if formatting for an EPUB or word processor:

```
7020 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
7021   {}
7022   {
7023       \ifdefempty{\LWR@pagetop}{}{
7024           \LWR@htmlElement{header}
7025       }
7026       \LWR@pagetop
7027       \LWR@htmlElementend{header}
7028   }
7029 }
7030 }
7031
```

The container for the sidetoc and text body:

```
7032 \LWR@htmlElementclass{div}{bodyandsidetoc}
```

No sideroc if formatting for an EPUB or word processor:

```
7033 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
7034   {}
7035   {\LWR@sidetoc}
7036
```

Start of the <textbody>:

```
7037 \LWR@htmlElementclass{div}{bodycontainer}
7038 \LWR@htmlElementclass{section}{textbody}
```

Not yet found a new section in this file. Once one is found, a label will be placed for previous/next links.

```
7039 \boolfalse{LWR@setseqfilelabel}
```

Print title only if there is one. Skip if formatting for an EPUB or word processor:

```

7040 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}%
7041   {}%
7042   {%
7043     \ifcsvoid{thetitle}{}{%
7044       \LWR@printthetitle%
7045     }%
7046   }%

```

Keep paragraph tags disabled for now:

```

7047 \LWR@stoppars
7048

```

If using MATHJAX, print the customizations here.

```

7049 \LWR@customizeMathJax

7050 \LWR@traceinfo{LWR@newhtmlfile: done}
7051 }

7052 \end{warpHTML}

```

62 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing L^AT_EX code and packages. Formatting is handled by css, so the emulated code has much less work to do than the print versions.

Unicode Section names and the resulting filenames with accented characters are partially supported, depending on the ability of *pdf_latex* to generate characters and *pdf_totext* to read them. If extra symbols appear in the text, it may be that *pdf_latex* is actually producing a symbol over or under a character, resulting in *pdf_totext* picking up the accent symbol separately.

⚠ accents in filenames

X_HL^AT_EX and LuaL^AT_EX directly support accented section and file names, but it may be necessary to use L^AT_EX accents instead of native Unicode accents. L^AT_EX accents will have the accents stripped when creating file names, whereas using Unicode accents will create filenames which include accents, which may cause issues with some operating systems.

for HTML output: 7053 \begin{warpHTML}

62.1 User-level starred section commands

`\ForceHTMLPage` For HTML output, forces the next section to be on its own HTML page, if `FileDepth` allows, even if starred. For use with `\printindex` and others which generate a starred section which should be on its own HTML page. Also see `\ForceHTMLTOC`.

For print output, no effect.

```
7054 \newbool{LWR@forcinghtmlpage}
7055 \boolfalse{LWR@forcinghtmlpage}
7056
7057 \newcommand*{\ForceHTMLPage}{%
7058 \global\booltrue{LWR@forcinghtmlpage}%
7059 }
```

`\ForceHTMLTOC` For HTML output, forces the next section to have a TOC entry, even if starred. For use with `\printindex` and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with `tocbibind`. Also see `\ForceHTMLPage`.

For print output, no effect.

```
7060 \newbool{LWR@forcinghtmltoc}
7061 \boolfalse{LWR@forcinghtmltoc}
7062
7063 \newcommand*{\ForceHTMLTOC}{%
7064 \global\booltrue{LWR@forcinghtmltoc}%
7065 }
```

```
7066 \end{warpHTML}
```

for PRINT output:

```
7067 \begin{warpprint}
7068 \newcommand*{\ForceHTMLPage}{}
7069 \newcommand*{\ForceHTMLTOC}{}
7070 \end{warpprint}
```

for HTML output:

```
7071 \begin{warpHTML}
```

62.2 Book class commands

`\mainmatter`  Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```
7072 \newbool{LWR@mainmatter}
7073 \DeclareDocumentCommand{\mainmatter}{}{}%
7074 \booltrue{LWR@mainmatter}%
7075 }
```

`\frontmatter` Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```
7076 \DeclareDocumentCommand{\frontmatter}{}{}%
7077 \boolfalse{LWR@mainmatter}%
7078 }
```

`\backmatter` Declare the back matter section of the document. Does not reset the page number.

```
7079 \DeclareDocumentCommand{\backmatter}{}{%
7080 \boolfalse{LWR@mainmatter}
7081 }
```

62.3 Sectioning support macros

`\LWR@sectionnumber` $\langle section\ type \rangle$

Typeset a section number and its trailing space with css formatting:

```
7082 \newcommand*{\LWR@sectionnumber}[1]{%
7083 \InlineClass{sectionnumber}{#1}%
7084 }
```

`autosec` A tag used by the toc and index.

`\LWR@createautosec` $\langle section\ type \rangle$

Create an autosection tag.

The use of `\textquotedbl` instead of " provides improved compatibility with xeCJK.

```
7085 \newcommand*{\LWR@createautosec}[1]{%
7086 \LWR@htmltag{%
7087   #1 % space
7088   id=\textquotedbl\LWR@print@mbx{autosec-\arabic{page}}\textquotedbl%
7089 }%
7090 }
```

`\LWR@pushoneclose` $\langle sectiontype \rangle$ Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

 `\LWR@stoppars` must be executed first.

```
7091 \NewDocumentCommand{\LWR@pushoneclose}{m}{%
7092 \LWR@traceinfo{LWR@pushoneclose #1}%
7093   \LWR@pushclose{#1}%
7094 }
```

`\LWR@startnewdepth` $\langle sectiontype \rangle$

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

 `\LWR@stoppars` must be executed first.

```
7095 \NewDocumentCommand{\LWR@startnewdepth}{m}{%
```

Close any stacked sections up to this new one.

```
7096 \LWR@closeprevious{#1}%
```

Push a new section depth:

```
7097 \LWR@pushoneclose{#1}%
7098 }
```

Ctrl LWR@prevFileDepth Remembers the previous LWR@FileDepth.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
7099 \newcounter{LWR@prevFileDepth}
7100 \setcounter{LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

`\@secntformat` {<sectiontype>}

```
7101 \def\@secntformat#1{\csname the#1\endcsname\quad}
```

`\simplechapterdelim` Used by `tocbibind` and `anonchap`.

```
7102 \newcommand*\simplechapterdelim{}
```

`\@chaptformat` {<sectiontype>}

\let to `\@secntformat` by default, but may be redefined by `\simplechapter` and `\restorechapter` from `tocbibind` or `anonchap`.

```
7103 \let\@chaptformat\@secntformat
```

`\@partcntformat` {<sectiontype>}

\let to `\@secntformat` by default, but may be redefined by `ctex`.

```
7104 \let\@partcntformat\@secntformat
```

`\@partnameformat` Prints “Part” for part sections.

Nullified by `ctex`.

```
7105 \newcommand*\@partnameformat{\LWR@isolate{\partname}~}%
```

`\LWR@printchaptername` Print `\chaptername` in most cases, but this is nullified for `ctexbook`, `komascript`, `ujt*` classes.

```
7106 \newcommand*\LWR@printchaptername{%
7107   \ifvoid{\chaptername}{\chaptername~}%
7108 }
```

Ctrl LWR@currentautosec Records the page number when the section was created. (If a math expression is included in the section name, and SVG math is used, the corresponding `lateximage` will cause the page number to change by the time the following autosec label is created, thus the initial page number is recorded here.)

```
7109 \newcounter{LWR@currentautosec}
7110 \setcounter{LWR@currentautosec}{1}
```

`\LWR@section` * [*<TOC name>*] {*<name>*} {*<sectiontype>*}

The common actions for the high-level sectioning commands.

```
7111 \DeclareDocumentCommand{\LWR@section}{m m m m}{%
7112 \IfValueTF{#2}%
7113   {\LWR@traceinfo{LWR@section: starting #4 #2}}%
7114   {\LWR@traceinfo{LWR@section: starting #4 #3}}%
```

Warn if starting a section inside a ``:

```
7115   \LWR@spanwarninvalid{section}%

7116 \LWR@maybeprintpendingfootnotes{\csuse{LWR@depth#4}}%
7117 \LWR@stoppars%
7118 \LWR@startnewdepth{#4}%
```

Cancel special minipage horizontal space interaction:

```
7119 \global\boolfalse{LWR@minipagethispar}%
```

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for `\part*`, for appendix.

Generate a new \LaTeX page so that TOC and index page number points to the section:

```
7120 \LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%
7121 \IfBooleanT{#1}{\LWR@traceinfo{LWR@section: starred}}%
7122 \ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}}{}%
7123 \ifthenelse{%
7124   \(%
7125     \(\NOT\equal{#1}{\BooleanTrue})\OR%
7126     \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart})\OR%
7127     \(\boolean{LWR@forcinghtmlpage})\)%
7128   \)%
7129   \AND%
7130   \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{FileDepth}}%
7131   \AND%
7132   \(%
7133     \NOT\boolean{CombineHigherDepths}\OR%
7134     \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}%
7135   \)%
7136   \AND%
```

```

7137 \(% phantomsection
7138 \NOT\isempty{#3}%
7139 \OR%
7140 \(\NOT\equal{#1}{\BooleanTrue}\)%
7141 \)%
7142 }%

```

If so: start a new HTML file:

```

7143 {% new file
7144 \LWR@traceinfo{LWR@section: new HTML file}%

```

See if there was an optional TOC name entry:

```

7145 \IfNoValueTF{#2}%

```

If no optional entry

```

7146 {\LWR@newhtmlfile{#3}}%

```

If yes an optional entry

```

7147 {\LWR@newhtmlfile{#2}}%
7148 }% new file

```

Else: No new HTML file:

```

7149 {% not new file

```

Generate a new L^AT_EX page so that TOC and index page number points to the section:

```

7150 \LWR@traceinfo{LWR@section: not a new HTML file, about to LWR@orignewpage}%
7151 \LWR@maybe@orignewpage%
7152 }% not new file
7153

```

Remember this section's name for \nameref:

```

7154 \IfValueT{#3}{%
7155 \LWR@traceinfo{LWR@section: about to LWR@setlatestname}%
7156 \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
7157 }%

```

Print an opening comment with the level and the name; ex: “section” “Introduction”
Footnotes may be used in section names, which would also appear in the HTML section opening comments, so the short toc entry is used if possible, and a limited opening comment is made if the sectional unit is starred.

```

7158 \ifbool{HTMLDebugComments}{%
7159 \begingroup%
7160 \LWR@nullfonts%
7161 \IfBooleanTF{#1}% starred
7162 {\LWR@htmlcomment{Opening #4*}}%

```

```

7163   {%
7164       \IfNoValueTF{#2}% short TOC
7165           {\LWR@htmlcomment{Opening #4 ‘#3’}}%
7166           {\LWR@htmlcomment{Opening #4 ‘#2’}}%
7167   }\LWR@originewline%
7168   \endgroup%
7169 }{}

```

For inline sections paragraph and subparagraph, start a new paragraph now:

```

7170 \ifthenelse{%
7171     \cnttest{\@nameuse{LWR@depth#4}}{>=}{\LWR@depthparagraph}%
7172 }%
7173     {\LWR@startpars}%
7174     {}%

```

Create the opening tag with an autosec:

```

7175 \LWR@traceinfo{LWR@section: about to LWR@createautosec}%
7176 \LWR@createautosec{\@nameuse{LWR>tag#4}}%

7177 \setcounter{LWR@currentautosec}{\value{page}}%

```

Check if starred:

```

7178 \IfBooleanTF{#1}%
7179 {%
7180     \LWR@traceinfo{LWR@section: starred}%

```

Starred, but also forcing a toc entry, so add unnumbered toc name or regular name:

```

7181     \ifbool{LWR@forcinghtmltoc}%
7182     {%
7183         \addcontentsline{toc}{#4}{%
7184             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
7185         }%
7186     }%
7187     {}%
7188 }% starred

```

Not starred, so step counter and add to toc:

```

7189 {% not starred

```

Only add a numbered toc entry if section number is not too deep:

```

7190     \ifthenelse{%
7191         \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
7192     }%
7193     {% if secnumdepth

```

If in the main matter, step the counter and add the toc entry. For article class, lwarp assumes that all is mainmatter.

```

7194     \LWR@traceinfo{LWR@section: about to test main matter}%
7195     \ifbool{LWR@mainmatter}%
7196     {%
7197         \LWR@traceinfo{LWR@section: yes mainmatter}%
7198         \refstepcounter{#4}%

```

Add main matter numbered toc entry with the toc name or the regular name:

```

7199         \LWR@traceinfo{LWR@section: about to addcontentsline}%
7200         \addcontentsline{toc}{#4}%
7201         {%
7202             \protect\numberline{%
7203                 \@nameuse{pre#4name}%
7204                 \@nameuse{the#4}%
7205                 \@nameuse{post#4name}%
7206             }%
7207             {%
7208                 \ignorespaces%
7209                 \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
7210             }%
7211         }%
7212         \LWR@traceinfo{LWR@section: finished addcontentsline}%
7213     }% end of if main matter

```

If not main matter, add unnumbered toc name or regular name:

```

7214     {% not main matter
7215         \LWR@traceinfo{LWR@section: no main matter}%
7216         \addcontentsline{toc}{#4}{%
7217             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
7218         }%
7219     }% end of not main matter
7220 }% end of secnumdepth

```

Deeper than secnumdepth, so add an unnumbered toc entry:

```

7221     {%
7222         \addcontentsline{toc}{#4}{%
7223             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
7224         }%
7225     }%

```

For part, print "Part":

```

7226     \ifbool{LWR@mainmatter}%
7227     {%
7228         \ifthenelse{%
7229             \(\cntttest{\@nameuse{LWR@depth#4}}{<=}%
7230             {\value{secnumdepth}}\)\ \AND%
7231             \(\cntttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)%
7232         }%
7233         {\@partnameformat}%
7234     }%

```

Print the section number:

```

7235     \LWR@traceinfo{LWR@section: about to print section number}%
7236     \ifthenelse{%
7237         \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
7238     }%
7239         {%
7240             \ifstrequal{#4}{part}%
7241             {\protect\LWR@sectionnumber{\@partcntformat{#4}}}%
7242             {%
7243                 \ifstrequal{#4}{chapter}%
7244                 {%
7245                     \LWR@printchaptername%
7246                     \protect\LWR@sectionnumber{\@chapcntformat{#4}}%
7247                 }%
7248                 {\protect\LWR@sectionnumber{\@secntformat{#4}}}%
7249             }%
7250         }%
7251     }%
7252     \LWR@traceinfo{LWR@section: finished print section number}%
7253 }{%}%
7254 }% not starred

```

Print the section name:

```

7255 \LWR@traceinfo{LWR@section: about to print the section name}%
7256 \LWR@isolate{#3}%

```

Close the heading tag, such as /H2:

```

7257 \LWR@traceinfo{LWR@section: about to close the heading tag}%
7258 \LWR@htmltag{\@nameuse{LWR>tag#4end}}%
7259 \LWR@orignewline%

```

Generate a L^AT_EX label.

Track the PDF page numbers of the HTML output.

```

7260 \LWR@traceinfo{LWR@section: about to create the LaTeX label}%
7261 \setcounter{LWR@latestautopage}{\value{page}}%
7262 \LWR@newautopagelabel{LWR@currentautosec}\LWR@orignewline%

```

If this is the first section found in this file, create a label for previous/next links:

```

7263 \ifbool{LWR@setseqfilelabel}{}%
7264     \label{\BaseJobname-autofile-\arabic{LWR@htmlseqfilenumber}}%
7265     \booltrue{LWR@setseqfilelabel}%
7266 }%

```

Start paragraph handing unless is an inline paragraph or subparagraph:

```

7267 \ifthenelse{%

```

```

7268 \cnttest{\@nameuse{LWR@depth#4}}{<}{LWR@depthparagraph}%
7269 }%
7270 {\LWR@startpars}%
7271 {}%

```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a `\part*` to start a new HTML page. This is used by `appendix`.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a `\listoftables` was tested in the middle of the document. The `\chapter*` for the list was not allowing a new HTML page for the section following it while `CombineHigherDepths` was true.

```

7272 \ifthenelse{%
7273 \NOT\equal{#1}{\BooleanTrue}\OR%
7274 \cnttest{\@nameuse{LWR@depth#4}}{=}{LWR@depthpart}%
7275 }%
7276 {% not starred
7277 \setcounter{LWR@prevFileDepth}{\@nameuse{LWR@depth#4}}%
7278 }% not starred
7279 {}%

```

Reset to defaults if not a phantomsection:

```

7280 \ifstrempy{#3}%
7281 {}%
7282 {%
7283 \global\boolfalse{LWR@forcinghtmlpage}%
7284 \global\boolfalse{LWR@forcinghtmltoc}%
7285 }%
7286 %
7287 \LWR@traceinfo{LWR@section: done}%
7288 }

```

62.4 Pre- and post- sectioning names

`\prebookname` Usually null, but is used by `uj*` and `ut*` Japanese classes.

`\postbookname`

```

7289 \providecommand*\prebookname{}
7290 \providecommand*\postbookname{}

```

`\prepartname` Usually null, but is used by `uj*` and `ut*` Japanese classes.

`\postpartname`

```

7291 \providecommand*\prepartname{}
7292 \providecommand*\postpartname{}

```

`\prechaptername` Usually null, but is used by `uj*` and `ut*` Japanese classes.

`\postchaptername`

```

7293 \providecommand*\prechaptername{}
7294 \providecommand*\postchaptername{}

```

`\presectionname` Always null, but provided here for algorithmic simplicity in `\LWR@section`.
`\postsectionname`

```
7295 \providecommand*\presectionname{}
7296 \let\postsectionname\presectionname
7297
7298 \let\presubsectionname\presectionname
7299 \let\postsubsectionname\postsectionname
7300
7301 \let\presubsubsectionname\presectionname
7302 \let\postsubsubsectionname\postsectionname
7303
7304 \let\preparagraphname\presectionname
7305 \let\postparagraphname\postsectionname
7306
7307 \let\presubparagraphname\presectionname
7308 \let\postsubparagraphname\postsectionname
```

62.5 `\section` and friends

For `memoir`, a second optional argument is allowed.

For `hypbmssec`, a second optional argument or either parenthesis argument is allowed.

Each of these additional arguments are for headers or PDF bookmarks, and are ignored for HTML output.

`\part` * (`\langle 2:PDF name \rangle`) [`\langle 3:TOC name \rangle`] [`\langle 4:PDF name \rangle`] (`\langle 5:PDF name \rangle`) {`\langle 6:name \rangle`}

```
7309 \newcommand{\part@preamble}{}% for koma-script
7310
7311 \DeclareDocumentCommand{\part}{s d() o o d() m}{%
7312   \LWR@section{#1}{#3}{#6}{part}%
7313
7314   \part@preamble% for koma-script
7315   \renewcommand{\part@preamble}{}%
7316 }
```

`\chapter` * (`\langle 2:PDF name \rangle`) [`\langle 3:TOC name \rangle`] [`\langle 4:PDF name \rangle`] (`\langle 5:PDF name \rangle`) {`\langle 6:name \rangle`}

```
7317 \let\@printcites\relax% for quotchap package
7318
7319 \newcommand{\chapter@preamble}{}% for koma-script
7320
7321 \@ifundefined{chapter}
7322 {}
7323 {%
7324   \DeclareDocumentCommand{\chapter}{s d() o o d() m}{%
7325     \LWR@section{#1}{#3}{#6}{chapter}%
7326
7327     \@printcites% for quotchap package
7328
7329     \chapter@preamble% for koma-script
```

```

7330     \renewcommand{\chapter@preamble}{}%
7331   }
7332 }

```

`\section` * (*<2:PDF name>*) [*<3:TOC name>*] [*<4:PDF name>*] (*<5:PDF name>*) {*<6:name>*}

```

7333 \DeclareDocumentCommand{\section}{s d() o o d() m}{%
7334   \LWR@section{#1}{#3}{#6}{section}%
7335 }

```

`\subsection` * (*<2:PDF name>*) [*<3:TOC name>*] [*<4:PDF name>*] (*<5:PDF name>*) {*<6:name>*}

```

7336 \DeclareDocumentCommand{\subsection}{s d() o o d() m}{%
7337   \LWR@section{#1}{#3}{#6}{subsection}%
7338 }

```

`\subsubsection` * (*<2:PDF name>*) [*<3:TOC name>*] [*<4:PDF name>*] (*<5:PDF name>*) {*<6:name>*}

```

7339 \DeclareDocumentCommand{\subsubsection}{s d() o o d() m}{%
7340   \LWR@section{#1}{#3}{#6}{subsubsection}%
7341 }

```

`\paragraph` * (*<2:PDF name>*) [*<3:TOC name>*] [*<4:PDF name>*] (*<5:PDF name>*) {*<6:name>*}

```

7342 \DeclareDocumentCommand{\paragraph}{s d() o o d() m}{%
7343   \LWR@section{#1}{#3}{#6}{paragraph}%
7344 }

```

`\subparagraph` * (*<2:PDF name>*) [*<3:TOC name>*] [*<4:PDF name>*] (*<5:PDF name>*) {*<6:name>*}

```

7345 \DeclareDocumentCommand{\subparagraph}{s d() o o d() m}{%
7346   \LWR@section{#1}{#3}{#6}{subparagraph}%
7347 }

```

```

7348 \end{warpHTML}

```

63 Starting a new file

for HTML & PRINT: 7349 `\begin{warpall}`

`\HTMLLanguage` Default language for the HTML lang tag.

```

7350 \newcommand*{\LWR@currentHTMLLanguage}{en-US}
7351
7352 \newcommand*{\HTMLLanguage}[1]{%
7353   \renewcommand*{\LWR@currentHTMLLanguage}{#1}%
7354 }

```

`\theHTMLTitleSeparator` May be used inside `\theHTMLTitleSection` to separate the website's overall HTML title and the particular page's section name.

```

7355 \ifPDFTeX% pdflatex or dvi latex
7356   \ifdefstring{\inputencodingname}{utf8}{%
7357     \newcommand*\theHTMLTitleSeparator}{ -\ }% EMDash
7358   }{%
7359     \newcommand*\theHTMLTitleSeparator}{ -\ }% hyphen
7360   }%
7361 \else%
7362   \ifpTeX
7363     \newcommand*\theHTMLTitleSeparator}{ -\ }% hyphen
7364   \else
7365     \newcommand*\theHTMLTitleSeparator}{ -\ }% EMDash
7366   \fi%
7367 \fi%
```

`\HTMLTitleBeforeSection` Sets the HTML page's meta title tag to show the website title before the section name.

```

7368 \newcommand*\HTMLTitleBeforeSection}{%
7369   \def\theHTMLTitleSection{%
7370     \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
7371   }%
7372 }
```

`\HTMLTitleAfterSection` Sets the HTML page's meta title tag to show the section name before the website title.

```

7373 \newcommand*\HTMLTitleAfterSection}{%
7374   \def\theHTMLTitleSection{%
7375     \theHTMLSection\theHTMLTitleSeparator\theHTMLTitle%
7376   }%
7377 }
```

`\theHTMLTitleSection` Forms the HTML page's meta title tag. The default is to show the website title before the section name.

```
7378 \HTMLTitleBeforeSection
```

`\theHTMLSection` The section name is passed to `\LWR@filestart`, which then sets `\theHTMLSection` for use inside `\theHTMLTitleSection` to create an HTML meta title tag.

```
7379 \newcommand*\theHTMLSection){}
```

```
7380 \end{warpall}
```

for HTML output: 7381 `\begin{warpHTML}`

`\LWR@filestart` [*section name*] Creates the opening HTML tags.

```

7382 \newcommand*\LWR@filestart}[1][[]]{%
7383 \LWR@traceinfo{\LWR@filestart !#1!}%
```

Locally temporarily disable direct-formatting commands:

```
7384 \begingroup%
7385 \LWR@nullfont%
```

Save the section name for use while creating the HTML meta title tag:

```
7386 \edef\theHTMLSection{#1}%
```

Remove extra material:

```
7387 \StrSubstitute{\theHTMLSection}{\protect}{\detokenize{-}}[\theHTMLSection]
7388 \StrSubstitute{\theHTMLSection}{\detokenize{-----}}{\detokenize{-}}[\theHTMLSection]
7389 \StrSubstitute{\theHTMLSection}{\detokenize{----}}{\detokenize{-}}[\theHTMLSection]
7390 \StrSubstitute{\theHTMLSection}{\detokenize{---}}{\detokenize{-}}[\theHTMLSection]
7391 \StrSubstitute{\theHTMLSection}{\detokenize{--}}{\detokenize{-}}[\theHTMLSection]
```

If starts with a dash, remove the leading dash:

```
7392 \IfBeginWith{\theHTMLSection}{\detokenize{-}}{%
7393   \StrGobbleLeft{\theHTMLSection}{1}[\theHTMLSection]%
7394 }{%}
```

Create the page's HTML header:

```
7395 \LWR@htmltag{!DOCTYPE html}\LWR@orignewline
```

The language is user-adjustable:

```
7396 \LWR@htmltag{%
7397   html lang=\LWR@orig@textquotedbl\LWR@currentHTMLLanguage\LWR@orig@textquotedbl%
7398 }\LWR@orignewline
```

Start of the meta data:

```
7399 \LWR@htmltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
7400 \LWR@htmltag{%
7401   meta charset=\LWR@orig@textquotedbl{}UTF-8\LWR@orig@textquotedbl\ /%
7402 }\LWR@orignewline
```

Author:

```
7403 \ifthenelse{\equal{\theHTMLAuthor}{}}%
7404   {}%
7405   {%
7406     \LWR@htmltag{%
7407       meta name=\LWR@orig@textquotedbl{}author\LWR@orig@textquotedbl\ % space
7408       content=\LWR@orig@textquotedbl\theHTMLAuthor\LWR@orig@textquotedbl\ /%
7409     }\LWR@orignewline%
7410   }%
```

lwarp is the generator:

```
7411 \LWR@htmltag{%
7412     meta % space
7413     name=\LWR@orig@textquotedbl{}generator\LWR@orig@textquotedbl\ % space
7414     content=\LWR@orig@textquotedbl{}LaTeX Lwarp package\LWR@orig@textquotedbl\ /%
7415 }\LWR@orignewLine%
```

If there is a description, add it now:

```
7416 \ifdefempty{\LWR@currentHTMLDescription}{}%
7417     \LWR@htmltag{%
7418         meta name=\LWR@orig@textquotedbl{}description\LWR@orig@textquotedbl\ % space
7419         content=\LWR@orig@textquotedbl\LWR@currentHTMLDescription\LWR@orig@textquotedbl\ /%
7420     }\LWR@orignewLine
7421 }%
```

Mobile-friendly viewport:

```
7422 \LWR@htmltag{%
7423     meta % space
7424     name=\LWR@orig@textquotedbl{}viewport\LWR@orig@textquotedbl\ % space
7425     content=\LWR@orig@textquotedbl{}width=device-width, initial-scale=1.0\LWR@orig@textquotedbl\ /%
7426 }\LWR@orignewLine
```

IE patch:

```
7427 \LWR@htmltag{!-\-[if lt IE 9]}\LWR@orignewline
7428 \LWR@htmltag{%
7429     script % space
7430     src=\LWR@orig@textquotedbl{}%
7431     http://html5shiv.googlecode.com/svn/trunk/html5.js%
7432     \LWR@orig@textquotedbl%
7433 }%
7434 \LWR@htmltag{/script}\LWR@orignewline
7435 \LWR@htmltag{![endif]-\-[}\LWR@orignewline
```

The page's title, if there is one. A section name is also added if given.

```
7436 \ifthenelse{\equal{\theHTMLTitle}{}}%
7437     {}%
7438     {%
7439         \LWR@htmltag{title}%
7440         \ifdefempty{\theHTMLSection}%
7441             {\theHTMLTitle}%
7442             {\theHTMLTitleSection}%
7443         \LWR@htmltag{/title}\LWR@orignewline%
7444     }%
```

The page's stylesheet:

```
7445 \LWR@htmltag{%
7446     link % space
7447     rel=\LWR@orig@textquotedbl{}stylesheet\LWR@orig@textquotedbl\ % space
```

```

7448     type=\LWR@orig@textquotedbl{}text/css\LWR@orig@textquotedbl\ % space
7449     href=\LWR@orig@textquotedbl\LWR@currentcss\LWR@orig@textquotedbl\ /%
7450 }%
7451 \LWR@orignewline

```

Optional MATHJAX support. The HTML tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```

7452 \ifbool{mathjax}%
7453 {%
7454     \begingroup%
7455     \LWR@restoreoriglists%
7456     \boolfalse{LWR@verbtags}%

7457     \IfFileExists{\LWR@mathjaxfilename}%
7458     {\verbatiminput{\LWR@mathjaxfilename}}%
7459     {%
7460         \PackageError{lwarp}%
7461         {%
7462             \protect\MathJaxFilename\space specified the file\MessageBreak
7463             \space\space\LWR@mathjaxfilename\MessageBreak
7464             which does not exist%
7465         }%
7466         {Specify an existing file, or remove \protect\MathJaxFilename.}%
7467     }%

7468     \booltrue{LWR@verbtags}%
7469     \endgroup%
7470     \LWR@stoppars%
7471 }% end of mathjax
7472 {}%

```

End of the header:

```
7473 \LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```

7474 \LWR@htmltag{body}\LWR@orignewline
7475 \endgroup
7476 \LWR@traceinfo{LWR@filestart: done}
7477 }

```

```
7478 \end{warpHTML}
```

64 Starting HTML output

for HTML output: 7479 \begin{warpHTML}

`\LWR@LwarpStart` Executed at the beginning of the entire document.

The use of `\textquotedbl` instead of `"` improves compatibility with `xeCJK`.

```
7480 \catcode'\$=\active
7481 \newcommand*\LWR@LwarpStart{
7482 {%
7483 \LWR@traceinfo{LWR@lwarpStart}
```

If formatting for a word processor, force `filedepth` to single-file only, force `HTML debug comments` off.

```
7484 \ifbool{FormatWP}{%
7485   \setcounter{FileDepth}{-5}%
7486   \boolfalse{HTMLDebugComments}%
7487 }{}
```

Expand and detokenize `\HomeHTMLFilename` and `\HTMLFilename`:

```
7488 \edef\LWR@strresult{\HomeHTMLFilename}
7489 \edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
7490 \edef\LWR@strresult{\HTMLFilename}
7491 \edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}
```

Force `onecolumn` and empty page style:

```
7492 \LWR@origonecolumn%
7493 \LWR@origpagestyle{empty}%
```

No black box for overfull lines:

```
7494 \overfullrule=0pt
```

Reduce chance of line overflow when `HTML` tags are added:

```
7495 \LWR@print@footnotesize%
```

In `PDF` output, don't allow line breaks to interfere with `HTML` tags:

```
7496 \LWR@print@raggedright%
7497 \LetLtxMacro{\}\LWR@endofline%
```

Spread the lines for *pdftotext* to read them well:

```
7498 \linespread{1.3}%
```

For *pdftotext* to reliably identify paragraph splits:

```
7499 \setlength{\parindent}{0pt}
7500 \setlength{\parskip}{2ex}
```

For the `lateximage` record file:

```
7501 \immediate\openout\LWR@lateximagesfile=\BaseJobname-images.txt
```

Removes space around the caption in the HTML:

```
7502 \setlength{\belowcaptionskip}{0ex}
7503 \setlength{\abovecaptionskip}{0ex}
```

Redefine the plain page style to be empty when used by index pages:

```
7504 \renewcommand{\ps@plain}{}
```

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Float captions:

```
7505 \let\LWR@origcaption\caption
```

Not yet started any paragraph handling:

```
7506 \global\boolfalse{LWR@doingapar}
7507 \global\boolfalse{LWR@doingstartpars}
```

Document and page settings:

```
7508 \mainmatter
7509 \LWR@origpagenumbering{arabic}
```

Start a new HTML file and a header:

```
7510 \LWR@traceinfo{LWR@lwarpStart: Starting new file.}
7511 \LWR@filestart
7512 \LWR@traceinfo{LWR@lwarpStart: Generating first header.}

7513 \ifdefempty{\LWR@firstpagetop}{%}
7514   \LWR@htmltag{header}\LWR@orignewline
7515   \LWR@startpars
7516   \LWR@firstpagetop
7517   \LWR@stoppars
7518   \LWR@htmltag{/header}\LWR@orignewline
7519 }%

7520 \LWR@htmlclass{div}{bodywithoutsidetoc}
7521 \LWR@htmlclass{div}{bodycontainer}
7522 \LWR@traceinfo{LWR@lwarpStart: Generating textbody.}
7523 \LWR@htmlclass{section}{textbody}
```

Create a label for previous/next links, and remember it has been done:

```
7524 \booltrue{LWR@setseqfilelabel}%
7525 \label{\BaseJobname-autofile-\arabic{LWR@htmlseqfilenumber}}
```

Patch the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native \LaTeX environments, as well as those provided by `enumitem`, `enumerate`, and `paralist`.

```
7526 \LWR@patchlists
```

Ensure that math mode is active to call `lwarp`'s patches:

```
7527 \catcode'\$=\active
```

Required for `\nameref` to work with SVG math:

```
7528 \immediate\write\@mainaux{\catcode'\string$\active}%
7529 \LetLtxMacro\LWR@syntaxhighlightone$% balance for editor syntax highlighting
```

Allow HTML paragraphs to begin:

```
7530 \LWR@startpars
```

If using `MATHJAX`, disable `\ensuremath` by printing a nullified definition at the start of each file, and add further customizations:

```
7531 \ifbool{mathjax}{
7532   \typeout{---}
7533   \typeout{Package lwarp:}
7534   \typeout{Processing MathJax customizations for the first HTML page.}
7535   \typeout{Later HTML pages will take the same amount of time.}
7536   \typeout{If this takes too long, see the Lwarp manual regarding customizing MathJax.}
7537 }{}
7538
7539 \LWR@customizeMathJax
7540
7541 \ifbool{mathjax}{
7542   \typeout{Done.}
7543   \typeout{---}
7544 }{}
```

First autopage label in case a figure occurs early.

```
7545 \setcounter{LWR@latestautopage}{\value{page}}%
7546 \LWR@newautopagelabel{LWR@currentautosec}%
```

```
7547 \LWR@traceinfo{LWR@lwarpStart: done}
7548 }
7549 \catcode'\$=3% math shift until lwarp starts
```

```
7550 \end{warpHTML}
```

65 Ending HTML output

for HTML output: 7551 \begin{warpHTML}

`\LWR@requesttoc` {<*boolean*>} {<*suffix*>} Requests that a TOC, LOF, or LOT be generated.

```
7552 \newcommand*{\LWR@requesttoc}[2]{%
7553 \ifbool{#1}
7554 {
7555     \expandafter\newwrite\@nameuse{tf@#2}
7556     \immediate\openout \@nameuse{tf@#2} \jobname.#2\relax
7557 }{}}
7558 }
```

`\LWR@LwarpEnd` Final stop of all HTML output:

```
7559 \newcommand*{\LWR@LwarpEnd}
7560 {
7561 \LWR@stoppars
7562 \LWR@closeprevious{finished}}
```

At the bottom of the ending file:

Close the textbody:

```
7563 \label{\BaseJobname-autofile-last}
7564 \LWR@htmlElementclassend{section}{textbody}
7565 \LWR@htmlElementclassend{div}{bodycontainer}
7566 \LWR@htmlElementclassend{div}{bodyandsidetoc}
```

Print any pending footnotes:

```
7567 \LWR@printpendingfootnotes
```

Create the footer if not EPUB

```
7568 \ifbool{FormatEPUB}{\LWR@createfooter}
```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```
7569 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
7570     {}
7571     {
7572         \ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}}
7573     }
```

```
7574 \LWR@stoppars% final stop of all paragraphs
```

Finish the HTML file:

```
7575 \LWR@htmltag{/body}\LWR@orignewline
7576 \LWR@htmltag{/html}\LWR@orignewline
```

Seems to be required sometimes:

```
7577 \LWR@maybe@orignewpage
7578 }
```

\enddocument If labels have not changed, mark successful completion of the lateximages.txt file.
Executed as everything is being shut down.

For the newer kernel hooks, see **texdoc lthooks-doc** and **texdoc ltshipout-doc**.

```
7579 \ifdef{\AddToHook}{% newer kernel
7580   \AddToHook{enddocument/info}{%
7581     \if@filesw
7582       \ifx \@multiplelabels \relax
7583         \if@tempswa
```

This is where warnings of duplicate labels would appear.

```
7584     \else
```

No duplicate labels, so safe to create images.

```
7585         \immediate\write\LWR@lateximagesfile{%
7586           |end|end|end|%
7587         }%
7588       \fi
7589     \fi\fi
7590   }
7591 }% newer kernel
7592 {% older kernel
7593   \xpatchcmd{\enddocument}
7594     {%
7595       \if@tempswa
7596         \@latex@warning@no@line{Label(s) may have changed.
7597         Rerun to get cross-references right}%
7598       \fi
7599     }
7600     {%
7601       \if@tempswa
7602         \@latex@warning@no@line{Label(s) may have changed.
7603         Rerun to get cross-references right}%
7604       \else
```

No duplicate labels, so safe to create images.

```
7605         \immediate\write\LWR@lateximagesfile{%
7606           |end|end|end|%
7607         }%
7608       \fi
7609     }
7610   {}
7611   {
7612     \AtEndDocument{
7613       \PackageWarningNoLine{lwarp}
```

```

7614         {%
7615         Could not patch \protect\enddocument.\MessageBreak
7616         If labels have changed, be sure to recompile before\MessageBreak
7617         creating lateximages with\MessageBreak
7618         \space\space lwarpmk limages,\MessageBreak
7619         or the images may be corrupt%
7620         }
7621     }
7622 }
7623 }% older kernel

```

66 Nullifying foreground/background hooks

See `texdoc lthooks-doc` and `texdoc ltshipout-doc`.

```

7624 \ifdef{\RemoveFromHook}{
7625     \AfterEndPreamble{
7626         \IfHookEmptyTF{shipout/background}{}{
7627             \PackageInfo{lwarp}{Removing background hook}
7628             \RemoveFromHook{shipout/background}[*]
7629         }
7630         \IfHookEmptyTF{shipout/foreground}{}{
7631             \PackageInfo{lwarp}{Removing foreground hook}
7632             \RemoveFromHook{shipout/foreground}[*]
7633         }
7634     }
7635 }{}

7636 \end{warpHTML}

```

67 Title page

package support `lwarp` supports the native L^AT_EX titling commands, and also supports the packages `authblk` and `titling`. If both are used, `authblk` should be loaded before `titling`.

 **load order**

\published and \subtitle If using the `titling` package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 67.8.

affiliation `lwarp` provides for the `\author` macro an additional `\affiliation` macro to provide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using `titlingpage`'s `\theauthor` in the main text.

reusing titlepage information The `titling` package maintains the definitions of `\thetitle`, `\theauthor`, etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the `\thanks` and `\affiliation` removed, and for `\author` the `\and` is replaced to generate a simple inline list of authors separated by commas. Note: `\theauthor` does not work well with `authblk` unless the traditional L^AT_EX syntax is used.

 **\theauthor, authblk**

- custom titlepages** `\printtitle`, `\printauthor`, etc., are provided for use inside a custom titlepage or titlingpage environment, and these retain the `\thanks` and `\affiliation`.
- `\printthanks` `\printthanks` has been added to force the printing of thanks inside a titlingpage environment when `\maketitle` is not used.
-  **\thanks** Inside a `\titlepage` or `\titlingpage` environment, use `\thanks` instead of `\footnote` for acknowledgements, etc.

67.1 Setting the title, etc.

The following provide setting commands for both HTML and print outputs.

`\author` `\and` `{\author}` While using `\maketitle` and print mode, the author is treated as a single-column tabular and the `\and` feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as

```
\author{Name \ Affiliation \and Second Name \ Second Affiliation}
```

For HTML, the entire author block is placed inside a `<div>` of class `author`, and each individual author is inside a `<div>` of class `oneauthor`.

`\@title` `\@author` `\@date` `\@title`, `\@author`, and `\@date` store the values as originally assigned, including any `\thanks`, `\and`, or `\affiliation`. These are low-level macros intended to be used by other macros only inside a titlepage or titlingpage, and are used by `\maketitle`. The author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For HTML, these tabulars become side-by-side `<div>`s of class `oneauthor`, all of which are combined into one `<div>` of class `author`.

`\printtitle` `\printauthor` `\printdate` `\printtitle`, etc. are user-level macros intended to be used in custom titlepage or titlingpage environments in cases where `\maketitle` is not desired. These commands preserve the `\thanks`, etc., and should not be used in the main text.

`\thetitle` `\theauthor` `\thedata` `\thetitle`, `\theauthor`, and `\thedata` are available if `\titling` has been loaded, and are sanitized user-level versions from which have been removed the `\thanks` and `\affiliation`, and `\and` is changed for inline text usage. The author is printed inline without `\affiliation` or `\thanks`, with `\and` placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each HTML page, such as:

```
\HTMLPageBottom{
  \begin{center}\textcopyright~20xx \theauthor\end{center}
}
```

 **\theauthor, authblk** `\theauthor` does not work well if `authblk` is used. If `\theauthor` is important, it is recommended to use the standard L^AT_EX syntax for `\author`, optionally with `lwarp`'s `\affiliation` macro as well.

 **affiliations** After `\maketitle` has completed, `\theauthor` retains the definition of the author, but

`\and` is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

`\affiliation` A solution, provide here, is to define a macro `\affiliation` which, during `\maketitle`, starts a new row and adds the affiliation, but after `\maketitle` is finished `\affiliation` is re-defined to discard its argument, thus printing only the author names when `\author` is later used inline.

67.2 `\if@titlepage`

for HTML & PRINT: 7637 `\begin{warpall}`

`\if@titlepage` Some classes do not provide `\if@titlepage`. In this case, provide it and force it false.

```
7638 \ifcvoid{@titlepagefalse}{
7639   \newif\if@titlepage
7640   \@titlepagefalse
7641 }{}

7642 \end{warpall}
```

67.3 Changes for `\affiliation`

`\affiliation` `{\text}`

Adds the affiliation to the author for use in `\maketitle`.

Inside `titlepage`, this macro prints its argument. Outside, it is null.

for HTML & PRINT: 7643 `\begin{warpall}`
7644 `\providerobustcmd{\affiliation}[1]{}{}`
7645 `\end{warpall}`

for PRINT output: 7646 `\begin{warpprint}`

```
7647 \AtBeginEnvironment{titlepage}{
7648 \renewrobustcmd{\affiliation}[1]{\ \textsc{\small#1}}
7649 }
7650
7651 \AtBeginDocument{
7652 \ifpackageloaded{titling}{
7653 \AtBeginEnvironment{titlingpage}{
7654 \renewrobustcmd{\affiliation}[1]{\ \textsc{\small#1}}
7655 }
7656 }{}% titling loaded
7657 }% AtBeginDocument

7658 \end{warpprint}
```

for HTML output: 7659 `\begin{warppHTML}`

Env titlepage Sets up a <div> of class titlepage. Provided even for memoir class, since it is used by \maketitle.

```

7660 \DeclareDocumentEnvironment{titlepage}{}
7661 {
7662 \renewrobustcmd{\affiliation}[1]{\ \ \InlineClass{affiliation}{##1}}
7663 \LWR@printpendingfootnotes
7664 \LWR@forcenewpage
7665 \BlockClass{titlepage}
7666 }
7667 {
7668 \endBlockClass
7669 \LWR@printpendingfootnotes
7670 }

7671 \end{warpHTML}

```

67.4 Printing the thanks

\printthanks Forces the \thanks to be printed. This is necessary in a titlingpage environment when \maketitle was not used.

for PRINT output: 7672 \begin{warpprint}
7673 \newcommand*{\printthanks}{\@thanks}
7674 \end{warpprint}

for HTML output: 7675 \begin{warpHTML}
7676 \newcommand*{\printthanks}{\LWR@stoppars\@thanks\LWR@startpars}
7677 \end{warpHTML}

67.5 Printing the title, etc. in HTML

The following are for printing the title, etc. in a titlepage or a titlingpage in HTML:

for HTML output: 7678 \begin{warpHTML}

\printtitle

```

7679 \newcommand*{\printtitle}
7680 {%
7681 \LWR@stoppars%
7682 \LWR@htmltag{\LWR@tagtitle}%
7683 \@title%
7684 \LWR@htmltag{\LWR@tagtitleend}%
7685 \LWR@startpars%
7686 }

```

\LWR@printhehtml A private version which prints the title without footnotes, used to title each HTML page.

```

7687 \newcommand*{\LWR@printthetitle}
7688 {%
7689   \LWR@stoppars%
7690   \LWR@htmltag{\LWR@tagtitle}%
7691   \thetitle%
7692   \LWR@htmltag{\LWR@tagtitleend}%
7693   \LWR@startpars%
7694 }

```

`\printauthor` HTML version.

```
7695 \newcommand*{\printauthor}{
```

The entire author block is contained in a <div> named author:

```
7696 \begin{BlockClass}{author}
```

\and finishes one author and starts the next:

```

7697 \renewcommand{\and}{%
7698 \end{BlockClass}
7699 \begin{BlockClass}{oneauthor}
7700 }

```

Individual authors are contained in a <div> named oneauthor:

```

7701 \begin{BlockClass}{oneauthor}
7702 \@author
7703 \end{BlockClass}
7704 \end{BlockClass}
7705 }

```

`\printdate`

```

7706 \newcommand*{\printdate}{%
7707 \begin{BlockClass}{titledate}
7708 \@date
7709 \end{BlockClass}
7710 }

```

```
7711 \end{warpHTML}
```

67.6 Printing the title, etc. in print form

The following are for printing the title, etc. in a titlepage or a titlingpage in print form:

for PRINT output: 7712 \begin{warpprint}

`\printtitle`

```
7713 \newcommand*{\printtitle}{\Huge\@title}}
```

`\printauthor` Print mode.

```
7714 \newcommand*{\printauthor}
7715   {\large\begin{tabular}[t]{c}\@author\end{tabular}}}
```

`\printdate`

```
7716 \newcommand*{\printdate}{\small\textit{\@date}}
```

```
7717 \end{warpprint}
```

67.7 `\maketitle` for HTML output

An HTML `<div>` of class `titlepage` is used.

`\thanks` are a form of footnotes used in the title page. See section 59 for other kinds of footnotes.

See `\thanksmarkseries{series}`, below, to set the style of the footnote marks.

for HTML output: `7718 \begin{warppHTML}`

```
7719 \@ifclassloaded{memoir}
7720 {
7721 \newcommand{\LWR@setfootnoteseries}{%
7722   \renewcommand\thefootnote{\@arabic\c@footnote}%
7723 }
7724 }{% not memoir
7725 \if@titlepage
7726 \newcommand{\LWR@setfootnoteseries}{%
7727   \renewcommand\thefootnote{\@arabic\c@footnote}%
7728 }
7729 \else
7730 \newcommand{\LWR@setfootnoteseries}{%
7731   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
7732 }
7733 \fi
7734 }% not memoir
```

`\LWR@maketitlesetup` Patches `\thanks` macros.

```
7735 \newcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
7736 \LWR@setfootnoteseries%
7737 \def\@makefnmark{\textsuperscript{\thefootnote}}
```

```
\thefootnote ⇒ \nameuse{arabic}{footnote}, or
\thefootnote ⇒ \nameuse{fnsymbol}{footnote}
```

Redefine the footnote text:

```
7738 \long\def\@makefnmark##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
7739 \textsuperscript{\@thefnmark}~%
```

```
\makethanksmark ⇒ \thanksfootmark ⇒ \tamark ⇒
\@thefnmark ⇒ \itshape a (or similar)
```

Print the text:

```
7740 ##1%
7741 }%
7742 }
```

`\@fnsymbol` {*<counter>*}

Re-defined to use an HTML entity for the double vertical bar symbol. The original definition used `\|` which was not being seen by *pdftotext*.

```
7743 \def\LWR@HTML@fnsymbol#1{%
7744   \ifcase#1\or *\or
7745   \HTMLentity{dagger}\or
7746   \HTMLentity{Dagger}\or
7747   \HTMLentity{sect}\or
7748   \HTMLentity{para}\or
7749   \HTMLunicode{2016}\or
7750   **\or
7751   \HTMLentity{dagger}\HTMLentity{dagger} \or
7752   \HTMLentity{Dagger}\HTMLentity{Dagger} \else
7753   \@ctrerr\fi%
7754 }
7755 \LWR@formatted{@fnsymbol}
```

`\maketitle` HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
7756 \renewcommand*{\maketitle}{%
```

An HTML titlepage `<div>` is used for all classes.

```
7757 \begin{titlepage}
```

Set up special patches:

```
7758 \LWR@maketitlesetup
```

Typeset the title, etc:

```
7759 \@maketitle
```

Immediately generate any \thanks footnotes:

```
7760 \LWR@stoppars\@thanks\LWR@startpars
```

Close the HTML titlepage div and cleanup:

```
7761 \end{titlepage}
7762 \setcounter{footnote}{0}%
7763 \global\let\thanks\relax
7764 \global\let\maketitle\relax
7765 \global\let\@maketitle\relax
7766 \global\let\@thanks\@empty
7767 \global\let\@author\@empty
7768 \global\let\@date\@empty
7769 \global\let\@title\@empty
7770 \global\let\title\relax
7771 \global\let\author\relax
7772 \global\let\date\relax
7773 \global\let\and\relax
7774 }
```

\@maketitle HTML mode. Typesets the title, etc.:

```
7775 \DeclareDocumentCommand{\@maketitle}{}{%
7776   \LWR@stoppars%
7777   \LWR@htmltag{\LWR@tagtitle}%
7778   \@title%
7779   \LWR@htmltag{\LWR@tagtitleend}%
7780   \LWR@startpars%
7781   \begin{BlockClass}{author}%
```

For IEEEtran class:

```
7782   \renewcommand*\cr}{}%
7783   \renewcommand*\crrc}{}%
7784   \renewcommand*\noalign}{}%

7785   \renewcommand{\and}{%
7786     \end{BlockClass}%
7787     \begin{BlockClass}{oneauthor}%
7788   }%
7789   \begin{BlockClass}{oneauthor}%
7790     \@author%
7791   \end{BlockClass}%
7792 \end{BlockClass}%
7793 \begin{BlockClass}{titledate}%
7794 \@date%
7795 \end{BlockClass}%
7796 }
```

`\LWR@titlingmaketitle` `\maketitle` for use inside an HTML titlingpage environment.

```
7797 \newcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
7798 \LWR@stoppars\@thanks\LWR@startpars
```

Set up special patches:

```
7799 \LWR@maketitlesetup
```

Typeset the title, etc:

```
7800 \@maketitle
```

Immediately generate any `\thanks` footnotes:

```
7801 \LWR@stoppars\@thanks\LWR@startpars
7802 }
```

```
7803 \end{warpHTML}
```

67.8 `\published` and `\subtitle`

`\subtitle` and `\published` To add `\subtitle` and `\published` to the titlepage, load the titling package and use `\AddSubtitlePublished` in the preamble.

The default `lwarp.css` has definitions for the `published` and `subtitle` classes.

If `titling` is loaded, `\AddSubtitlePublished` creates a number of additional macros, and also assigns some of the titling hooks. If `titling` is not loaded, `\AddSubtitlePublished` creates null macros.

 **titling hooks** Do not use `\AddSubtitlePublished` if the user has patched the titling hooks for some other reason. Portions are marked `\warpprintonly` to reduce extra tags in HTML. Similarly, `BlockClass` has no effect in print mode. Thus, the following may be marked `warpall`.

for HTML & PRINT: `7804 \begin{warpall}`

`\AddSubtitlePublished` Adds `\published` and `\subtitle`, and related.

```
7805 \newcommand*{\AddSubtitlePublished}{%
7806 \@ifpackageloaded{titling}{% yes titling package
7807   \newcommand{\@published}{}%
7808   \newcommand{\published}[1]{\gdef\@published{##1}}%
7809   \renewcommand*{\maketitlehooka}{\printpublished}%
7810   \newcommand*{\printpublished}{%
7811     \warpprintonly{\begin{center}}\unskip}%
7812     \begin{BlockClass}{published}%
```

```

7813     \warpprintonly{\Large\itshape}%
7814     \@published%
7815     \end{BlockClass}%
7816     \warpprintonly{\end{center}}%
7817   }%
7818   \newcommand{\@subtitle}{}%
7819   \newcommand{\subtitle}[1]{\gdef\@subtitle{##1}}%
7820   \renewcommand*\maketitlehookb{\printssubtitle}%
7821   \newcommand*\printssubtitle{%
7822     \warpprintonly{\begin{center}\unskip}%
7823     \begin{BlockClass}{subtitle}%
7824     \warpprintonly{\Large\itshape}%
7825     \@subtitle%
7826     \end{BlockClass}%
7827     \warpprintonly{\end{center}}%
7828   }%
7829 }% yes titling package
7830 {% no titling package

7831   \def\@published{}%
7832   \DeclareDocumentCommand{\published}{m}{\gdef\@published{##1}}%
7833   \DeclareDocumentCommand{\printpublished}{}{}%
7834   \def\@subtitle{}%
7835   \DeclareDocumentCommand{\subtitle}{m}{\gdef\@subtitle{##1}}%
7836   \DeclareDocumentCommand{\printssubtitle}{}{}%
7837 }% no titling package
7838 }% \AddSubtitlePublished

7839 \end{warpall}

```

68 Abstract

The following code replaces the L^AT_EX default, and will itself be replaced later if the abstract package is loaded.

for HTML output: 7840 \begin{warpHTML}

\abstractname User-redefinable title for the abstract.

Also over-written by the babel package.

```
7841 \providecommand*\abstractname}{Abstract}
```

Some classes allow an optional name, so it is allowed here.

Env abstract

```

7842 \DeclareDocumentEnvironment{abstract}{0}{\abstractname}}
7843 {
7844   \LWR@forcenewpage

```

```

7845 \BlockClass{abstract}
7846 \BlockClassSingle{abstracttitle}{#1}
7847 }
7848 {
7849 \endBlockClass
7850 }

7851 \end{warpHTML}

```

69 Quote and verse

69.1 Attributions

`\attribution` {<*name*>}

For use with quote, quotation, verse:

Ex: "A quotation." `\attribution{\textsc{Author Name}}\textsl{Book Title}`

for HTML & PRINT:

```

7852 \begin{warpall}
7853 \newcommand{\attribution}[1]{
7854 \begin{flushright}
7855 \unskip
7856 #1
7857 \end{flushright}}%
7858 }
7859 \end{warpall}

```

for HTML output:

```

7860 \begin{warpHTML}
7861 \newcommand{\LWR@HTML@attribution}[1]{%
7862 \LWR@stoppars%
7863 \begin{BlockClass}{attribution}
7864 #1
7865 \end{BlockClass}
7866 \LWR@startpars%
7867 }
7868 \LWR@formatted{attribution}
7869 \end{warpHTML}

```

69.2 Quotes, quotations

for HTML output: 7870 `\begin{warpHTML}`

Env quote

```

7871 \newenvironment*{\LWR@HTML@quote}
7872 {
7873 \LWR@forcenewpage
7874 \LWR@htmlblocktag{blockquote}

```

```

7875 }
7876 {\LWR@htmlblocktag{/blockquote}}
7877
7878 \LWR@formattedenv{quote}

```

Env quotation

```

7879 \newenvironment*{LWR@HTML@quotation}
7880 {
7881   \LWR@forcenewpage
7882   \LWR@htmlblocktag{blockquote}
7883 }
7884 {\LWR@htmlblocktag{/blockquote}}
7885
7886 \LWR@formattedenv{quotation}

7887 \end{warpHTML}

```

69.3 Verse

When using `verse` or `memoir`, always place a `\\` after each line.

`\attrib` The documentation for the `verse` and `memoir` packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. `lwarp` provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```

\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}

```

Len `\vleftskip` These lengths are used by `verse` and `memoir` to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any `verse` environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

 **spacing** Horizontal spacing relies on *pdftotext*'s ability to discern the layout (`-layout` option) of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLleftskip` the horizontal alignment may not work out exactly, in which case a label may be shifted by one space. During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused *pdftotext* to shift everything over.

 **verse margin**

69.3.1 L^AT_EX core verse environment

for HTML output: `7888 \begin{warpHTML}`

Env verse

```

7889 \newenvironment{LWR@HTML@verse}
7890     {\let\\newline% lwarp
7891     \list{}{\itemsep \z@
7892     \itemindent -1.5em%
7893     \listparindent\itemindent
7894     \rightmargin \leftmargin
7895     \advance\leftmargin 1.5em}%
7896     \item\relax}
7897     {\endlist}
7898
7899 \LWR@formattedenv{verse}

```

```
7900 \end{warpHTML}
```

for HTML & PRINT: 7901 \begin{warpall}

69.3.2 verse and memoir

The following lengths are used by `verse` and `memoir`. They may be set in either print or HTML output, but are only used in HTML. This allows the user to set `\leftskip` and `\leftmargini` for print output, and optionally select different values for HTML.

Len `\HTMLvleftskip` Sets `\vleftskip` inside a verse environment in HTML.

```

7902 \newlength{\HTMLvleftskip}
7903 \setlength{\HTMLvleftskip}{1em}

```

Len `\HTMLleftmargini` Sets `\leftmargini` inside a verse environment in HTML.

```

7904 \newlength{\HTMLleftmargini}
7905 \setlength{\HTMLleftmargini}{4.5em}

```

```
7906 \end{warpall}
```

70 Verbatim and tabbing

for HTML & PRINT: 7907 \begin{warpall}

Len `\VerbatimHTMLWidth` Width to use in HTML Verbatim environment.

This width is used when placing line numbers to the right. Ignored during print output.

```

7908 \newlength{\VerbatimHTMLWidth}
7909 \setlength{\VerbatimHTMLWidth}{4in}
7910 \end{warpall}

```

for HTML output: 7911 \begin{warpHTML}

Bool LWR@verbtags Used to temporarily turn off verbatim tags while doing `\verbatiminput` in the HTML head.

```
7912 \newbool{LWR@verbtags}
7913 \booltrue{LWR@verbtags}
```

`\verb` Patched to encapsulate the verbatim text inside span with a class of `texttt`.

```
7914 \LetLtxMacro\LWR@orig@verb@egroup\verb@egroup
7915
7916 \def\LWR@verb@egroup@endspan{%
7917   \LWR@orig@verb@egroup%
7918   \LWR@htmltag{/span}%
7919   \endgroup%
7920 }
7921
7922 \xpretocmd{\verb}
7923   {%
7924     \begingroup%
7925     \LWR@htmltag{span class="texttt"}%
7926     \let\verb@egroup\LWR@verb@egroup@endspan%
7927   }
7928   {}
7929   {\LWR@patcherror{LaTeX}{verb}}
```

`\LWR@atbeginverbatim` [*1: style*] {*2: class*}

Encloses a verbatim environment with the given CSS class.

The use of `\textquotedbl` instead of `"` improves compatibility with XeCJK.

```
7930 \newcommand*{\LWR@atbeginverbatim}[2]{}
7931 {%
```

Stop generating HTML paragraph tags:

```
7932 \LWR@stoppars%
```

Avoid excessive space between lines:

```
7933 \setlength{\parskip}{0ex}%
7934 \setlength{\topsep}{0pt}%
7935 \setlength{\partopsep}{0pt}%
```

Create a new pre of the given class. The tags may temporarily be turned off for internal use, such as loading the MATHJAX script.

```
7936 \ifbool{LWR@verbtags}{%
7937   \LWR@htmltag{pre class=\textquotedbl#2\textquotedbl%
7938     \ifthenelse{\equal{#1}{}}{ style=\textquotedbl#1\textquotedbl}%
7939   }%
7940   \par%
7941 }{}
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the css for the verse class.

```
7942 \begingroup%
```

```
7943 \LWR@print@normalfont%
```

```
7944 \LWR@origttfamily%
```

```
7945 \LWR@print@scriptsize%
```

Since inside a <pre>, restore the original list processing:

```
7946 \LWR@restoreoriglists%
```

Turn off babel-french extra space before punctuation:

```
7947 \LWR@FBcancel%
```

Do not produce HTML tags for \hspace inside a verse par. Restore plain L^AT_EX \hspace functionality:

```
7948 \LWR@select@print@hspace%
```

```
7949 }
```

`\LWR@afterendverbatim` Finishes enclosing a verbatim environment.

```
7950 \newcommand*{\LWR@afterendverbatim}{%
```

```
7951 \endgroup%
```

```
7952 \par%
```

At the end of the environment, close the pre:

```
7953 \ifbool{LWR@verbtags}{%
```

```
7954   \noindent\LWR@htmltag{/pre}\par% pre
```

```
7955 }{ }%
```

Resume regular paragraph handling:

```
7956 \LWR@startpars%
```

```
7957 }
```

`\verbatiminput` {<filename>}

Patch `\verbatiminput` to add HTML tags:

```
7958 \newcommand{\LWR@HTML@verbatim@input}[2]{%
```

```
7959   \ifbool{LWR@verbtags}{\LWR@forcenewpage}{ }%
```

```
7960   \LWR@atbeginverbatim{Verbatim}%
```

```
7961   \LWR@print@verbatim@input{#1}{#2}%
```

```
7962   \LWR@afterendverbatim%
```

```
7963 }
```

```
7964
```

```
7965 \LWR@formatted{verbatim@input}
```

Env verbatim

```

7966 \AfterEndPreamble{
7967 \LWR@traceinfo{Patching verbatim.}
7968 \AtBeginEnvironment{verbatim}{%
7969   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
7970     {}%
7971     {%
7972       \LWR@forcenewpage%
7973       \LWR@atbeginverbatim{verbatim}%
7974     }%
7975 }
7976 \AfterEndEnvironment{verbatim}{%
7977   \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
7978     {}%
7979     {%
7980       \LWR@afterendverbatim%
7981     }%
7982 }
7983 }

```

Env tabbing The tabbing environment works, except that `svg math` and `lateximages` do not yet work inside the environment.

 **math in tabbing** If math is used inside tabbing, place tabbing inside a `lateximage` environment, which will render the entire environment as a single `svg` image.

```

7984 \newcommand*{\LWR@HTML@tabbing}{%
7985   \LWR@forcenewpage%
7986   \LWR@atbeginverbatim{tabbing}%
7987   \let\enskip\LWR@origenskip%
7988   \let\quad\LWR@origquad%
7989   \let\qqquad\LWR@origqqquad%
7990   \let~\LWR@origtilde%
7991   \let\,\LWR@origcomma%
7992   \let\thinspace\LWR@origthinspace%
7993   \let\negthinspace\LWR@orignegthinspace%
7994   \LWR@print@tabbing%
7995 }
7996
7997 \newcommand*{\LWR@HTML@endtabbing}{%
7998   \LWR@print@endtabbing%
7999   \LWR@afterendverbatim%
8000 }
8001
8002 \LWR@formatted{tabbing}
8003 \LWR@formatted@endtabbing}

8004 \end{warpHTML}

```

71 Theorems

`\newtheorem` $\langle\text{text}\rangle$ [$\langle\text{counter}\rangle$] — or — [$\langle\text{oldname}\rangle$] $\langle\text{text}\rangle$

A few minor changes are made to supply HTML tags.

- The entire theorem is placed into a `<div>` of class `theoremcontents`.
- The label for each theorem is placed inside a `` of class `theoremlabel`.
- The contents are placed inside a `<div>` of class `theoremcontents`.

for HTML output: 8005 `\begin{warpHTML}`

`\@begintheorem` $\langle\text{name}\rangle$ $\langle\text{number}\rangle$

```
8006 \renewcommand{\@begintheorem}[2]{%
8007 \LWR@forcenewpage
8008 \BlockClass{theoremcontents}
8009 \trivlist
8010 \item[\InlineClass{theoremlabel}{#1\ #2\ }]\itshape
8011 }
```

`\@opargbegintheorem` $\langle\text{name}\rangle$ $\langle\text{number}\rangle$ $\langle\text{oparg}\rangle$

L^AT_EX defines this, but `amsthm` `\relaxes` it, so it will not be defined if `amsthm` is loaded before `lwarp`.

```
8012 \ifundef{\@opargbegintheorem}{%
8013   \renewcommand{\@opargbegintheorem}[3]{%
8014     \LWR@forcenewpage
8015     \BlockClass{theoremcontents}
8016     \trivlist
8017     \item[\InlineClass{theoremlabel}{#1\ #2\ (#3)\ }]\itshape
8018   }
8019 }
```

`\@endtheorem`

```
8020 \renewcommand*\@endtheorem{%
8021 \endtrivlist
8022 \endBlockClass% theoremcontents
8023 }
```

```
8024 \end{warpHTML}
```

72 Lists

The environments `itemize`, `enumerate`, and `description` are patched when `lwarp` is started. These patches support the standard L^AT_EX environments, as well as those of

enumerate, enumitem, and paralist, and at least the French version of babel. Additional patches are done on a package-specific basis.

The L^AT_EX source for itemize and enumerate are found in source2e, but the source for description is found in article.cls, etc.

empty item To have an empty item, use `\mbox{}` or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

```
begin{itemize}
item \mbox{}
  \begin{itemize}
...
  \end{itemize}
item \
  \begin{itemize}
...
  \end{itemize}
```

`\makelabel` While inside a list environment, `lwarp` nullifies a number of T_EX horizontal skip and fill commands, allowing the user to define `\makelabel` for print mode while HTML mode ignores those commands.

 **label font** When defining `\makelabel` in a list environment, use `\textbf` etc. instead of `\bfseries`.

72.1 List environment

for HTML output: 8025 `\begin{warpHTML}`

`\LWR@printcloselist` May be locally redefined by enumerate or description.

```
8026 \newcommand*\LWR@printcloselist{\LWR@printcloseitemize}
```

`\LWR@printopenlist` May be locally redefined by enumerate or description.

```
8027 \newcommand*\LWR@printopenlist{\ul style="\LWR@print@mbox{list-style-type:none}"}
```

`\@mklab` Removes PDF spacing.

```
8028 \AtBeginDocument{
8029 \def\@mklab#1{%
8030 %   \hfil %
8031   #1}
8032 \let\makelabel\@mklab
8033 }
```

`\@donoparitem` Modified for HTML output by replacing T_EX boxes with plain text. Also removes PDF spacing.

```

8034 \def\@donoparitem{%
8035   \@noparitemfalse
8036 %   \global\setbox\@labels\hbox{\hskip -\leftmargin
8037 %                               \unhbox\@labels
8038 %                               \hskip \leftmargin}%
8039 %   \if@minipage\else
8040 %     \@tempskipa\lastskip
8041 %     \vskip -\lastskip
8042 %     \advance\@tempskipa\outerparskip
8043 %     \advance\@tempskipa -\parskip
8044 %     \vskip\@tempskipa
8045 %   \fi
8046 }
```

`\@item` Modified for HTML output by replacing T_EX boxes with plain text. Also removes PDF spacing.

```

8047 \def\LWR@HTML@item[#1]{%
8048 \LWR@traceinfo{\@item}
8049 \if@noparitem
8050   \@donoparitem
8051 \else
8052 %   \if@inlabel
8053 %     \indent
8054 %     \par
8055 %   \fi
8056 \ifhmode
8057 %   \unskip\unskip
8058 %   \par
8059 \fi
8060 \if@newlist
8061   \if@nobreak
8062     \@nbitem
8063   \else
8064 %     \addpenalty\@beginparpenalty
8065 %     \addvspace\@topsep
8066 %     \addvspace{-\parskip}%
8067   \fi
8068 \else
8069 %   \addpenalty\@itempenalty
8070 %   \addvspace\itemsep
8071 \fi
8072 \global\@inlabeltrue
8073 \fi
8074 % \everypar{%
8075 % \@minipagefalse
8076 \global\@newlistfalse

8077 %   \if@inlabel
8078 %     \global\@inlabelfalse
```

```

8079 %      {\setbox\z@\lastbox
8080 %      \ifvoid\z@
8081 %      \kern-\itemindent
8082 %      \fi}%

8083 %      \box\@labels
8084 %      \penalty\z@
8085 %      \fi

8086 %      \if@nobreak
8087 %      \@nobreakfalse
8088 %      \clubpenalty \@M
8089 %      \else
8090 %      \clubpenalty \@clubpenalty
8091 %      \everypar{}%
8092 %      \fi}%

8093 \if@noitemarg
8094 \@noitemargfalse
8095 \if@nmbrowse

8096 \refstepcounter\@listctr
8097 \fi
8098 \fi

8099 \makeLabel{#1} % extra space
8100 % \sbox\@tempboxa{\makeLabel{#1}}%
8101 % \global\setbox\@labels\hbox{%
8102 % \unhbox\@labels
8103 % \hskip \itemindent
8104 % \hskip -\labelwidth
8105 % \hskip -\labelsep
8106 % \ifdim \wd\@tempboxa >\labelwidth
8107 % \box\@tempboxa

8108 % \else
8109 % \hbox to\labelwidth {\unhbox\@tempboxa}%
8110 % \fi
8111 % \hskip \labelsep}%
8112 \ignorespaces%
8113 }

\@nbitem

8114 \def\@nbitem{%
8115 % \@tempkipa\@outerparskip
8116 % \advance\@tempkipa -\parskip
8117 % \addvspace\@tempkipa
8118 }

```

\LWR@listitem [*label*]

Handles \item inside a list, itemize, or enumerate.

See `\LWR@openparagraph` where extra `\hspace` is used to leave room for the label while inside a list during paragraph construction.

```
8119 \newcommand*\LWR@listitem}{%
8120 \LWR@stoppars%
8121 \LWR@startnewdepth{listitem}%
8122 \LWR@htmltag{li}%
8123 \LWR@startpars%
8124 \LWR@origitem%
8125 }
```

`\LWR@nulllistfills` Nullifies various TeX fill commands, in case they are used inside `\makeLabel`. Problems are caused when these are nullified all the time.

```
8126 \newcommand*\LWR@nulllistfills}{%
8127 \renewcommand*\hss}{}%
8128 \renewcommand*\llap[1]{##1}%
8129 \renewcommand*\rlap[1]{##1}%
8130 \renewcommand*\hfil}{}%
8131 \renewcommand*\hfilneg}{}%
8132 \renewcommand*\hfill}{}%
8133 }
```

Env `list` `{<label>}{<commands>}`

```
8134 \newcommand*\LWR@liststart}{%
8135 \LWR@traceinfo{LWR@liststart}%
8136 \LWR@stoppars%
8137 \LWR@pushoneclose{list}%
8138 \LWR@htmltag{\LWR@printopenlist}\LWR@orignewline%
8139 \LWR@startpars%
8140 \setlength{\topsep}{0pt}%
8141 \setlength{\partopsep}{0pt}%
8142 \setlength{\itemsep}{0pt}%
8143 \setlength{\parsep}{0pt}%
8144 \setlength{\leftmargin}{0pt}%
8145 \setlength{\rightmargin}{0pt}%
8146 \setlength{\listparindent}{0pt}%
8147 \setlength{\itemindent}{0pt}%
8148 \setlength{\labelsep}{1em}%
8149 \LWR@nulllistfills%
8150 }
```

```
8151 \newcommand*\LWR@listend}{%
8152 \LWR@traceinfo{LWR@listend}%
8153 \LWR@stoppars%
8154 \LWR@closeprevious{list}%
8155 \LWR@startpars%
8156 }
```

72.2 Itemize

`\LWR@itemizeitem` [*<label>*]

Handles `\item` inside an `itemize` or `enumerate`.

See `\LWR@openparagraph` where extra `\hspace` is used to leave room for the label while inside a list during paragraph construction.

```
8157 \newcommand*\LWR@itemizeitem{%
8158 \LWR@stoppars%
8159 \LWR@startnewdepth{listitem}%
8160 \LWR@htmltag{li}%
8161 \LWR@startpars%
8162 \LWR@origitem%
8163 }
```

Env `itemize` [*<options>*]

```
8164 \newcommand*\LWR@itemizestart{%
8165 \renewcommand*\LWR@printcloselist{\LWR@printcloseitemize}
8166 \renewcommand*\LWR@printopenlist{\ul style="\LWR@print@box{list-style-type:none"}}
8167 \let\item\LWR@itemizeitem%
8168 \LWR@nulllistfills%
8169 }
```

72.3 Enumerate

An HTML unordered list is used with customized L^AT_EX-generated labels.

Env `enumerate` [*<options>*]

```
8170 \newcommand*\LWR@enumeratestart{%
8171 \renewcommand*\LWR@printcloselist{\LWR@printcloseitemize}
8172 \renewcommand*\LWR@printopenlist{\ul style="\LWR@print@box{list-style-type:none"}}
8173 \let\item\LWR@itemizeitem%
8174 \LWR@nulllistfills%
8175 }
```

72.4 Description

`\LWR@descitem` [*<label>*] Handles an `\item` inside a description.

```
8176 \newcommand*\LWR@descitem[1][[]]{%
8177 {%
8178 \LWR@stoppars%
8179 \LWR@setlatestname{#1}%
8180 \LWR@startnewdepth{descitem}%
```

While creating the label, encase it inside tags and disable `\hspace`, which is used by the standard classes to add space to the labels.

```

8181 \begingroup%
8182 \let\LWR@orig@desc@makeLabel\makeLabel
8183 \renewcommand*\makeLabel}[1]{%
8184   \LWR@htmltag{dt}%
8185   \LWR@orig@desc@makeLabel{#1}%
8186   \LWR@htmltag{/dt}%
8187 }
8188 \LWR@select@html@nohspace%
8189 \LWR@origitem[#1]%
8190 \endgroup%
8191 \LWR@orignewline%
8192 \LWR@htmltag{dd}%
8193 \LWR@startpars%
8194 }

```

Env description [*(options)*]

```

8195 \newcommand*\LWR@descriptionstart{%
8196 \renewcommand*\LWR@printcloseList{\LWR@printclosedescription}
8197 \renewcommand*\LWR@printopenList}{dl}
8198 \let\item\LWR@descitem%
8199 \LWR@nulllistfills%
8200 }

```

72.5 Patching the lists

`\LWR@patchlists` Patches list environments.

`\LWR@patchlists` remembers `\item` as defined by whatever packages have been loaded, then patches the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native L^AT_EX environments, as well as those provided by `enumitem`, `enumerate`, and `paralist`.

```

8201 \newcommand*\LWR@patchlists{%
8202   \LetLtxMacro\item\LWR@listitem%
8203   \LetLtxMacro\@item\LWR@HTML@item%
8204   \renewcommand*\@trivlist{%
8205     \LWR@traceinfo{@trivlist start}%
8206     \LWR@liststart%
8207     \LWR@orig@trivlist%
8208     \LWR@traceinfo{@trivlist done}%
8209   }%
8210   \renewcommand*\trivlist{%
8211     \LWR@traceinfo{trivlist}%
8212     \LWR@origtrivlist%
8213   }%
8214   \renewcommand*\endtrivlist{%
8215     \LWR@traceinfo{endtrivlist start}%
8216     \LWR@origendtrivlist\LWR@listend%

```

```

8217     \LWR@traceinfo{endtrivlist done}%
8218   }%
8219   \renewcommand*\itemize{%
8220     \LWR@itemizestart\LWR@origitemize%
8221   }%
8222   \renewcommand*\enumerate{%
8223     \LWR@enumeratestart\LWR@origenumerate%
8224   }%
8225   \renewcommand*\description{%
8226     \LWR@descriptionstart\LWR@origdescription%
8227   }%
8228 }

```

`\LWR@restoreoriglists` Restores the original `trivlist` environment.

```

8229 \newcommand*\LWR@restoreoriglists{%
8230   \LWR@traceinfo{LWR@restoreoriglists}%
8231   \LetLtxMacro\item\LWR@origitem%
8232   \LetLtxMacro\@item\LWR@orig@item%
8233   \let\@trivlist\LWR@orig@trivlist%
8234   \let\trivlist\LWR@origtrivlist%
8235   \let\endtrivlist\LWR@origendtrivlist%
8236   \LetLtxMacro\itemize\LWR@origitemize%
8237   \LetLtxMacro\enditemize\LWR@endorigitemize%
8238   \LetLtxMacro\enumerate\LWR@origenumerate%
8239   \LetLtxMacro\endenumerate\LWR@endorigenumerate%
8240   \LetLtxMacro\description\LWR@origdescription%
8241   \LetLtxMacro\enddescription\LWR@endorigdescription%
8242   \let\@mklab\LWR@orig@mklab%
8243   \let\makeLabel\LWR@origmakeLabel%
8244   \let\@donoparitem\LWR@orig@donoparitem%
8245   \let\@nbitem\LWR@orig@nbitem%
8246 }

8247 \end{warpHTML}

```

73 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax of the \LaTeX core and the various tabular-related packages.

73.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, `siunitx` `S` columns, or the packages `multirow`, `longtable`, `supertabular`, or `xtab`.

Defining macros and environments:

⚠ Misplaced alignment
tab character &

⚠ floatrow

⚠ tabular inside another
environment

- When defining environments or macros which include tabular and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

This includes before and after defining any macro which used \ttabbox from floatrow.

- When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % (& is used in a definition)
\newenvironment{outerenvironment}
{
  \tabular{cc}
  left & right \\
}
{
  \TabularMacro\ResumeTabular
  left & right \\
  \endtabular
}
\StopDefiningTabulars
```

For developers:

- To automate the use of \StartDefiningTabulars and \EndDefiningTabulars, these macros may be embedded inside an HTML environment definition to automatically change the catcode of & before absorbing the arguments. Another environment may be embedded as well.

```
% Does the work after the catcode has been changed:
\newcommand*{\LWR@HTML@subsomename}[2]{%
  . . .
  \otherenvironmentname [<args>] {<args>} % for example
}
% Change catcode before absorbing arguments:
\newcommand*{\LWR@HTML@somename{%
  \StartDefiningTabulars
  \LWR@HTML@subsomename
}
% Change catcode again at the end:
\newcommand*{\LWR@HTML@endsomename}{%
  . . .
  \endotherenvironmentname % for example
  \StopDefiningTabulars
}
% Combine with the existing print definition:
\LWR@formattedenv{somename}
```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML

data cell tag, corrupting the HTML table. To avoid this, use `\TabularMacro` just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

`\multirow`

- In `\multirow` cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the `\multirow` which do not appear in the HTML version.

⚠ `\newcolumnntype`

- `\newcolumnntype` is ignored; unknown column types are set to l.

Rules:

vertical rules

- Doubled `\hlines`, `\midrules`, and vertical rules are supported.
- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:


```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

 The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

⚠ `\warpprintonly`

⚠ Misplaced `\noalign`

- For `\toprule` and `\bottomrule`, when combined with a `warpprint` or `warppHTML` environment, if a “Misplaced `\noalign`” error occurs, change


```
This & That \endhead
```

 to


```
\warpprintonly{This & That \endhead}
```

 and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevant to HTML output.

Other:

longtable headings

- `tabularx` ignores the width, but X columns do produce paragraph columns or multicolumns.
- For `longtable`, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.

⚠ S columns

- For S columns (from the `siunitx` package), while producing print output, anything non-numeric must be placed inside `{ }` braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by `lwarp`'s tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warppHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

⚠ tabular inside a

- In \LaTeX , a tabular may be placed inside a minipage, but in HTML a <table> may not be inside a . If this situation is detected, a warning is printed instructing the user to isolate the using \warpprintonly or the warpprint environment.

for HTML output: 8248 \begin{warppHTML}

73.2 Temporary package-related macros

These macros are temporary placeholders for macros defined by various packages. If the relevant package is not loaded, these placeholders are used instead.

73.2.1 arydshln

Emulated by the original \LaTeX non-dashed versions.

```
8249 \LetLtxMacro\hdashline\hline
8250 \LetLtxMacro\cdashline\cline
8251 \LetLtxMacro\firsthdashline\hline
8252 \LetLtxMacro\lasthdashline\hline
```

73.3 Token lookahead

Used by \LWR@futurenonpacelet to look at the next token.

\LWR@mynexttoken

```
8253 \newcommand\LWR@mynexttoken\relax
```

\futurelet copies the next token then executes a function to analyze it.

\LWR@futurenonpacelet does the same, but ignores intervening white space

Based on the booktabs style:

\LWR@futurenonpacelet

```
8254 \def\LWR@futurenonpacelet#1{\def\LWR@cs{#1}%
8255 \afterassignment\LWR@fnslone\let\nexttoken= }
8256
8257 \def\LWR@fnslone{\expandafter\futurelet\LWR@cs\LWR@fnsltwo}
8258
8259 \def\LWR@fnsltwo{%
8260 \expandafter\ifx\LWR@cs\@sptoken\let\next=\LWR@fnslthree%
8261 \else\let\next=\nexttoken\fi\next}
8262
8263 \def\LWR@fnslthree{\afterassignment\LWR@fnslone\let\next= }
```

`\LWR@getmynexttoken` Looks ahead and copies the next token into `\LWR@mynexttoken`.

```
8264 \newcommand*{\LWR@getmynexttoken}{%
8265   \LWR@traceinfo{\LWR@getmynexttoken}%
8266 % nothing must follow this next line
8267   \LWR@futurenonospacelet\LWR@mynexttoken\LWR@tabledatacolumnstag
8268 }
```

73.4 Tabular variables

In order to support nested tabulars, each of these is used locally. For local counters, `etoolbox's` `\defcounter` and `lwarp's` new `\defaddtocounter` are used.

`Bool` `LWR@startedrow` True if should print a row tag before this column.

```
8269 \newbool{LWR@startedrow}
8270 \boolfalse{LWR@startedrow}
```

`Bool` `LWR@tabularcelladded` True if have added a data cell for this position.

```
8271 \newbool{LWR@tabularcelladded}
8272 \boolfalse{LWR@tabularcelladded}
```

`Ctr` `LWR@hlines` Number of `\hlines` or `\midrules` above the next row.

```
8273 \newcounter{LWR@hlines}
```

`Ctr` `LWR@hdashedlines` Number of `\arydshln` dashed lines above the next row.

```
8274 \newcounter{LWR@hdashedlines}
```

`Bool` `LWR@doingtbrule` True if the next row will have a top/bottom rule above it.

```
8275 \newbool{LWR@doingtbrule}
8276 \boolfalse{LWR@doingtbrule}
```

`Bool` `LWR@doingcmidrule` True if the next row will have a `\cmidrule` above it.

This is used by `\LWR@tabularfinishrow` to force a final empty row to create the border for the `\cmidrule`.

```
8277 \newbool{LWR@doingcmidrule}
8278 \boolfalse{LWR@doingcmidrule}
```

`Bool` `LWR@tableparcell` True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

```
8279 \newbool{LWR@tableparcell}
```

`Bool` `LWR@skippingmrowcell` True if are doing an empty `\multirow` cell, and thus there is no data tag to close.

```
8280 \newbool{LWR@skippingmrowcell}
```

LWR@skippingmcolrowcell	Bool	True if are doing an empty <code>\multicolumnrow</code> cell, and thus there is no data tag to close, and do not print @ and ! columns.
		8281 <code>\newbool{LWR@skippingmcolrowcell}</code>
LWR@usedmultirow	Bool	Used to error if used <code>\multirow</code> or <code>\multicolumnrow</code> without using <code>\mrowcell</code> or <code>\mcolrowcell</code> .
		8282 <code>\newbool{LWR@usedmultirow}</code>
LWR@foundmrowcell	Bool	Used to error if used <code>\multirow</code> or <code>\multicolumnrow</code> without using <code>\mrowcell</code> or <code>\mcolrowcell</code> .
		8283 <code>\newbool{LWR@foundmrowcell}</code>
LWR@skipatbang	Bool	True if just finished a <code>\multicolumn</code> so should not create the trailing @ or ! columns table data cells.
		8284 <code>\newbool{LWR@skipatbang}</code>
LWR@emptyatbang	Bool	True if finishing a row and should print empty @ or ! column table data cells.
		8285 <code>\newbool{LWR@emptyatbang}</code>
LWR@intabularmetadata	Bool	True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.
		8286 <code>\newbool{LWR@intabularmetadata}</code> 8287 <code>\boolfalse{LWR@intabularmetadata}</code>
LWR@exitingtabular	Bool	When <code>\end</code> is found, turns off the next opening data tag.
		8288 <code>\newbool{LWR@exitingtabular}</code>
LWR@tabularmutemods	Bool	Mutes HTML output for @, !, < and >. <p style="margin-left: 20px;">This is used while printing the final row to generate <code>\bottomrules</code>.</p>
		8289 <code>\newbool{LWR@tabularmutemods}</code>
LWR@validtablecol	Bool	True if found a valid table column type.
		8290 <code>\newbool{LWR@validtablecol}</code>
LWR@opttablecol	Bool	True if found a table column optional argument.
		8291 <code>\newbool{LWR@opttablecol}</code>
		Used to add a style to a table data cell:
		8292 <code>\newbool{LWR@tdhavecellstyle}</code>

- Ctrl LWR@tabularDepth Tracks whether & is being used inside a tabular.
- ```
8293 \newcounter{LWR@tabulardepth}
8294 \setcounter{LWR@tabulardepth}{0}
```
- Ctrl LWR@tabularpardepth Tracks whether should look ahead at the next token when encountering a \par while processing tabular contents.
- When LWR@tabularpardepth is deeper than LWR@tabulardepth then lwarp has started looking at the contents of the tabular, and thus any \pars encountered must be followed by another token lookahead.
- ```
8295 \newcounter{LWR@tabularpardepth}
8296 \setcounter{LWR@tabularpardepth}{0}
```
- ```
8297 \newcommand*{\LWR@colsresult}{}%temp storage for column format results
8298 \newcommand*{\LWR@pposition}{}
8299 \newcommand*{\LWR@pleft}{}
8300 \newcommand*{\LWR@pright}{}

```
- LWR@tablecolspec Holds the parsed column specification, of total width LWR@tabletotalLaTeXcols, not counting @ and ! columns.
- Will contain a string such as llrrccpc, exactly one letter per L<sup>A</sup>T<sub>E</sub>X table column, without @, !, >, <, or the vertical bar.
- \LWR@strresult Holds the result of Str functions.
- ```
8301 \providecommand*{\LWR@strresult}{}
8302 \providecommand*{\LWR@strresulttwo}{}

```
- \LWR@origcolspec Holds the original column specs given to tabular.
- ```
8303 \newcommand*{\LWR@origcolspec}{}

```
- Ctrl LWR@tablecolspecwidth Holds the number of tokens in the table columns specification.
- This includes one for each @, !, <, > column, and also one for each of the parameters of p, @, !, <, > columns, and three for each D column.
- (This is not the total # of L<sup>A</sup>T<sub>E</sub>X columns in the table.)
- ```
8304 \newcounter{LWR@tablecolspecwidth}
```
- Ctrl LWR@tablecolspecindex While parsing the L^AT_EX table column specification, starts at 1 and is incremented per token of the specification.
- ```
8305 \newcounter{LWR@tablecolspecindex}
```
- Ctrl LWR@tableLaTeXcolindex While producing the table, resets to 1 at the start of the table and also at each end of line, and is incremented by 1 by each ampersand.

8306 `\newcounter{LWR@tableLaTeXcolindex}`

Ctrl `LWR@tabletotalLaTeXcols` While parsing a table column specification, begins at 0 and increments by 1 per  $\LaTeX$  table column. Eventually holds the final number of  $\LaTeX$  table columns in each row, not counting @ and ! columns. (In HTML, @ and ! cells become their own columns, but are not included in `LWR@tabletotalLaTeXcols`.)

8307 `\newcounter{LWR@tabletotalLaTeXcols}`

Ctrl `LWR@tabletotalLaTeXcolsnext` Holds the next  $\LaTeX$  table column index while parsing, equal to one more than `LWR@tabletotalLaTeXcols`.

8308 `\newcounter{LWR@tabletotalLaTeXcolsnext}`

`LWR@colatspec` A data array of specifications for @ columns. The leftmost's index is `leftedge`, the others are counter values. See section 41.

`LWR@colbangspec` A data array of specifications for ! columns. The leftmost's index is `leftedge`, the others are counter values. See section 41.

`LWR@colbeforespec` A data array of specifications for > columns.

`LWR@colafterspec` A data array of specifications for < columns.

`LWR@colbarspec` A data array of specifications for vertical rules.

Ctrl `LWR@cellcolordepth` Counts how many cell color `<div>`s were added to the current tabular data cell.

8309 `\newcounter{LWR@cellcolordepth}`

### 73.4.1 Multicolumn variables

8310 `\newcounter{LWR@tablemulticolwidth}`

Indexes into the multicolumn specification:

8311 `\newcounter{LWR@tablemulticolspos}`

Remembers multicolumn vertical rules if found in the column spec.

8312 `\newcounter{LWR@mccolvertbarsl}`

8313 `\newcounter{LWR@mccolvertbarsr}`

8314 `\newcounter{LWR@mccolvertbarsldash}`

8315 `\newcounter{LWR@mccolvertbarsrdash}`

8316 `\newbool{LWR@mccolvertbaronleft}`

### 73.4.2 Longtable variables

Bool `LWR@starredlongtable` Per the caption package, step the counter if `longtable*`.

8317 `\newbool{LWR@starredlongtable}`

8318 `\boolfalse{LWR@starredlongtable}`

### 73.4.3 Midrule variables

Ctrl LWR@midrulecounter Indexes across the LWR@midrules and LWR@trim<l/r>rules data arrays.

```
8319 \newcounter{LWR@midrulecounter}
```

## 73.5 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:

<http://tex.stackexchange.com/questions/11638/>

[where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860](http://tex.stackexchange.com/questions/11638/where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860)

\LWR@instertatbangcols

```
8320 \newcommand*{\LWR@insertatbangcols}{%
8321 \ifbool{LWR@skipatbang}%
8322 {}%
8323 {%
8324 \LWR@printatbang{at}{\arabic{LWR@tableLaTeXcolindex}}%
8325 \LWR@printatbang{bang}{\arabic{LWR@tableLaTeXcolindex}}%
8326 }%
8327 }
```

\LWR@closetabledatacell If LWR@skippingmrowcell or LWR@skippingmcolrowcell then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
8328 \newcommand*{\LWR@closetabledatacell}{%
8329 \booltrue{LWR@intabularmetadata}%
8330 \ifbool{LWR@exitingtabular}%
8331 {%
8332 \LWR@stoppars%
8333 }%
8334 {% not exiting tabular
8335 \ifboolexpr{bool{LWR@skippingmrowcell} or bool{LWR@skippingmcolrowcell}}%
8336 {%
8337 \LWR@stoppars%
```

If not skipping a \multicolumnrow cell, insert the @ and ! columns after this non-existent column.

```
8338 \ifbool{LWR@skippingmcolrowcell}%
8339 {}%
8340 {\LWR@insertatbangcols}%
8341 }%
8342 {% not skippingmrowcell
```

Insert any < then any @ and ! column contents, unless muted for the \bottomrule or a \multicolumn:

```

8343 \unskip%
8344 \ifboolexpr{%
8345 bool{LWR@tabularmutemods} or
8346 bool{LWR@skipatbang} or
8347 bool{LWR@emptyatbang}
8348 }%
8349 {%
8350 {%
8351 \LWR@getexparray{LWR@colafterspec}%
8352 {\arabic{LWR@tableLaTeXcolindex}}%
8353 }%

```

Close paragraphs:

```

8354 \LWR@stoppars%
8355 \boolfalse{LWR@tableparcell}%

```

Close the table data cell.

Close any color <div>s.

```

8356 \whileboolexpr{test {\ifnumcomp{\value{LWR@cellcolordepth}}{>}{0}}}{%
8357 \LWR@htmltag{/div}\LWR@orignewline%
8358 \defaddtocounter{LWR@cellcolordepth}{-1}%
8359 }%

```

Skip the @ and ! cells if are closing a multicolumn cell.

```

8360 \leavevmode\unskip\LWR@htmltag{/td}\LWR@orignewline%
8361 \global\booltrue{LWR@tabularcelladded}%
8362 \LWR@insertatbangcols%
8363 }% not skipping mrowcell
8364 }% not exiting tabular
8365 \boolfalse{LWR@skippingmrowcell}%
8366 \boolfalse{LWR@skippingmcolrowcell}%
8367 \boolfalse{LWR@skipatbang}%

```

Color control. Column is set by >{} for each cell, so it must be cleared here.

```

8368 \def\LWR@cellHTMLcolor{}%
8369 \def\LWR@columnHTMLcolor{}%
8370 \defcounter{LWR@cellcolordepth}{0}%
8371 }

```

When not used inside a tabular, & performs its original function as recorded here ( with catcode 4 ).

```

8372 \let\LWR@origampmacro&

```

```

8373 \end{warpHTML}

```

### 73.5.1 Handling &

for HTML output: 8374 `\begin{warpHTML}`

& Will behave depending on whether it is being used inside `tabular`.

& is redefined to test whether it is inside a `tabular` environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```
8375 \newcommand*\LWR@tabularampersand}{%
8376 \LWR@traceinfo{\LWR@tabularampersand}%
8377 \ifnumcomp{\value{\LWR@tabulardepth}}{>}{0}%
8378 {%
```

If not skipping a `multirow` cell, close the current data cell.

```
8379 \unskip%
8380 \LWR@closetabledatacell%
```

Move to the next column.

```
8381 \defaddtocounter{\LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
8382 \global\boolfalse{\LWR@tabularcelladded}%
```

Look at the next token to decide multi or single column data tag.

```
8383 \LWR@getmynexttoken%
8384 }%
```

If not inside a `tabular`, performs the original action:

```
8385 {%
8386 \LWR@origampmacro%
8387 }%
8388 }
```

& is left with its original catcode for now.

`tikz` package seems to require & be left alone until after `tikz` has been loaded. Also, `cleveref` uses the ampersand in one of its options.

& is made active inside a `tabular`.

& is left alone when in math alignments.

### 73.5.2 Filling an unfinished row

`\LWR@tabularfinishrow` Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
8389 \newcommand*{\LWR@tabularfinishrow}{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
8390 \ifboolexpr{%
8391 not bool {LWR@exitingtabular} or%
8392 bool{LWR@doingtbrule} or%
8393 bool{LWR@doingcmidrule} or%
8394 test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
8395 test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
8396 bool{LWR@startedrow}%
8397 }{%
```

To temporarily turn off LWR@exitingtabular so that table data tags will still be generated:

If generating a final row for the \bottomrule borders, turn off the @, !, <, and > column output:

```
8398 \ifbool{LWR@exitingtabular}{%
8399 \booltrue{LWR@tabularmutemods}%
8400 }{%
8401 \boolfalse{LWR@tabularmutemods}%
8402 }%
```

Locally reenable the table data tags until finished with the final row:

```
8403 \boolfalse{LWR@exitingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
8404 \whileboolexpr{%
8405 test {
8406 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
8407 {\value{LWR@tabletotalLaTeXcols}}
8408 } or %
8409 (%
8410 bool{LWR@intabularmetadata} and%
8411 not bool{LWR@tabularcelladded} and%
8412 test {
8413 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}
8414 {\value{LWR@tabletotalLaTeXcols}}
8415 }%
8416)%
8417 }%
8418 {%
8419 \LWR@tabledatasinglecolumnstag%
```

The following is essentially \LWR@tabularampersand with LWR@emptyatbang added to empty the following cells:

```

8420 \LWR@closetabledatacell%
8421 \defaddtocounter{LWR@tableLaTeXcolindex}{1}%
8422 \global\boolfalse{LWR@tabularcelladded}%
8423 \booltrue{LWR@emptyatbang}%

```

Starts the next cell:

```

8424 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
8425 {\value{LWR@tabletotalLaTeXcols}}%
8426 {\LWR@getmynexttoken}%
8427 {}%
8428 }%

```

Reenable the original LWR@exitingtabular to close the entire table:

```

8429 \ifbool{LWR@tabularmutemods}{%
8430 \booltrue{LWR@exitingtabular}%
8431 }{%
8432 \boolfalse{LWR@exitingtabular}%
8433 }%
8434 \boolfalse{LWR@tabularmutemods}%

8435 \boolfalse{LWR@emptyatbang}%
8436 }{}% ifboolexpr
8437 }

```

## 73.6 Handling \\

Inside tabular, \\ is redefined to \LWR@tabularendofline

Throws away options \\[dim] or \\\*

\LWR@tabularendofline

```

8438 \NewDocumentCommand{\LWR@tabularendofline}{s o}{%

```

Finish the row:

```

8439 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}
8440 {\value{LWR@tabletotalLaTeXcols}}%
8441 {\LWR@tabularfinishrow}%
8442 {\LWR@closetabledatacell}%
8443 \LWR@htmltag{/tr}\LWR@orignewline%

```

xcolor row color support:

```

8444 \@row@lors%

```

No longer inside a data cell:

```

8445 \booltrue{LWR@intabularmetadata}%

```

Not yet started a table row:

```
8446 \boolfalse{LWR@startedrow}%
```

Additional setup:

```
8447 \defcounter{LWR@hlines}{0}%
8448 \defcounter{LWR@hdashedlines}{0}%
8449 \boolfalse{LWR@doingtbrule}%
8450 \boolfalse{LWR@doingcmidrule}%
8451 \LWR@clearmidrules%
```

```
8452 \def\LWR@rowHTMLcolor{ }%
```

Start at first column:

```
8453 \defcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
8454 \global\boolfalse{LWR@tabularcelladded}%
```

Allow T<sub>E</sub>X to flush the pending paragraph. Not doing so causes a slowdown for very large tables.

```
8455 \LWR@stoppars%
8456 \LWR@origpar%
```

Look at the next token to decide between single column data tag or a special case:

```
8457 \LWR@getmynexttoken%
8458 }
```

### 73.7 Looking ahead in the column specifications

`\LWR@columnspeclookahead` {*offset*}

Looks *offset* tokens ahead in the column specification, setting `\LWR@strresulttwo`.

The *w* column alignment will be seen as a single unit such as `{c}`.

```
8459 \newcommand*{\LWR@columnspeclookahead}[1]{%
8460 \setcounter{LWR@tempcountone}{\value{LWR@tablecolspecindex}}%
8461 \addtocounter{LWR@tempcountone}{#1}%
8462 \fullexpandarg%
8463 \StrChar{\LWR@origcolspec}{\arabic{LWR@tempcountone}}[\LWR@strresulttwo]%
```

Get the contents of the first group in `\LWR@strresulttwo`:

```
8464 \exploregroups%
8465 \StrChar{\LWR@strresulttwo}{1}[\LWR@strresulttwo]%
8466 \noexploregroups%
8467 }
```

### 73.8 Parsing @, >, <, !, bar columns

Holds the parsed argument for @, >, <, or ! columns:

```
8468 \newcommand*{\LWR@colparameter}{}
```

`\LWR@parseatcolumn` Handles @{text} columns.

```
8469 \newcommand*{\LWR@parseatcolumn}{%
```

Move to the next token after the '@':

```
8470 \LWR@traceinfo{at column}%
```

```
8471 \defaddtocounter{\LWR@tablecolspecindex}{1}%
```

Read the next token into `\LWR@colparameter`, expanding once:

```
8472 \LWR@traceinfo{about to read the next token:}%
```

```
8473 \expandarg%
```

```
8474 \StrChar{\LWR@origcolspec}%
```

```
8475 {\arabic{\LWR@tablecolspecindex}}[\LWR@colparameter]%
```

```
8476 \fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
8477 \LWR@traceinfo{have now read the next token}%
```

```
8478 \ifnumcomp{\value{\LWR@tabletotalLaTeXcols}}{=}{0}%
```

```
8479 {% left edge of the table:
```

```
8480 \LWR@traceinfo{at the left edge}%
```

```
8481 \LWR@setexparray{\LWR@colatspec}%
```

```
8482 {leftedge}%
```

```
8483 {\expandafter\@firstofone\LWR@colparameter}%
```

```
8484 \LWR@traceinfo{at the left edge: %
```

```
8485 \LWR@getexparray{\LWR@colatspec}{leftedge}}%
```

```
8486]%
```

```
8487 {% not at the left edge:
```

```
8488 \LWR@traceinfo{not at the left edge}%
```

```
8489 \LWR@setexparray{\LWR@colatspec}%
```

```
8490 {\arabic{\LWR@tabletotalLaTeXcols}}%
```

```
8491 {\expandafter\@firstofone\LWR@colparameter}%
```

```
8492 \LWR@traceinfo{at \arabic{\LWR@tabletotalLaTeXcols}: %
```

```
8493 \LWR@getexparray{\LWR@colatspec}{\arabic{\LWR@tabletotalLaTeXcols}}}%
```

```
8494]%
```

```
8495 \let\LWR@colparameter\relax%
```

```
8496 \booltrue{\LWR@validtablecol}%
```

```
8497 }
```

`\LWR@parsebangcolumn` Handles !{text} columns.

```
8498 \newcommand*{\LWR@parsebangcolumn}{%
```

Move to the next token after the '!':

```
8499 \LWR@traceinfo{bang column}%
8500 \defaddtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
8501 \LWR@traceinfo{about to read the next token:}%
8502 \expandarg%
8503 \StrChar{\LWR@origcolspec}%
8504 {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
8505 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
8506 \LWR@traceinfo{have now read the next token}%
8507 \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
8508 {% left edge of the table:
8509 \LWR@traceinfo{at the left edge}%
8510 \LWR@setexparray{LWR@colbangspec}%
8511 {leftedge}%
8512 {\expandafter\@firstofone\LWR@colparameter}%
8513 }%
8514 {% not at the left edge:
8515 \LWR@traceinfo{not at the left edge}%
8516 \LWR@setexparray{LWR@colbangspec}%
8517 {\arabic{LWR@tabletotalLaTeXcols}}%
8518 {\expandafter\@firstofone\LWR@colparameter}%
8519 \LWR@traceinfo{bang \arabic{LWR@tabletotalLaTeXcols}: \LWR@colparameter!}%
8520 }%
8521 \let\LWR@colparameter\relax%
8522 \booltrue{LWR@validtablecol}%
8523 }
```

\LWR@parsebeforecolumn Handles >{text} columns.

```
8524 \newcommand*{\LWR@parsebeforecolumn}{%
```

Move to the next token after the '>':

```
8525 \defaddtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```
8526 \expandarg%
8527 \StrChar{\LWR@origcolspec}%
8528 {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
8529 \fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
8530 \LWR@setexparray{LWR@colbeforespec}%
8531 {\arabic{LWR@tabletotalLaTeXcolsnext}}%
8532 {\expandafter\@firstofone\LWR@colparameter}%
8533 \let\LWR@colparameter\relax%
```

```
8534 \booltrue{LWR@validtablecol}%
8535 }
```

`\LWR@parseaftercolumn` Handles <{text} columns.

```
8536 \newcommand*{\LWR@parseaftercolumn}{%
```

Move to the next token after the '<':

```
8537 \defaddtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into `\LWR@colparameter`:

```
8538 \expandarg%
8539 \StrChar{\LWR@origcolspec}%
8540 {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
8541 \fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
8542 \LWR@setexparray{LWR@colafterspec}%
8543 {\arabic{LWR@tabletotalLaTeXcols}}%
8544 {\expandafter\@firstofone\LWR@colparameter}%
8545 \let\LWR@colparameter\relax%
8546 \booltrue{LWR@validtablecol}%
8547 }
```

`\LWR@parsebarcolumn` Handles vertical rules.

```
8548 \newcommand*{\LWR@parsebarcolumn}{%
8549 \LWR@traceinfo{LWR@parsebarcolumn}%
```

Remember the bar at this position:

```
8550 \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
8551 {% left edge of the table:
8552 \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
8553 \ifdefstring{\LWR@tempone}{tvertbarl}%
8554 {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldouble}}%
8555 {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarl}}%
8556 }%
8557 {% not at the left edge:
8558 \edef\LWR@tempone{%
8559 \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
8560 }%
8561 \ifdefstring{\LWR@tempone}{tvertbarr}%
8562 {%
8563 \LWR@setexparray{LWR@colbarspec}%
8564 {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdouble}}%
8565 }%
8566 {%
8567 \LWR@setexparray{LWR@colbarspec}%
```

```

8568 {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarr}%
8569 }%
8570]%
8571 \booltrue{LWR@validtablecol}%
8572 }

```

`\LWR@parsecoloncolumn` Handles vertical rules.

```

8573 \newcommand*{\LWR@parsecoloncolumn}{%
8574 \LWR@traceinfo{LWR@parsecoloncolumn}%

```

Remember the bar at this position:

```

8575 \ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
8576 {% left edge of the table:
8577 \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
8578 \ifdefstring{\LWR@tempone}{tvertbarldash}%
8579 {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldoubledash}}%
8580 {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldash}}%
8581 }%
8582 {% not at the left edge:
8583 \edef\LWR@tempone{%
8584 \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
8585 }%
8586 \ifdefstring{\LWR@tempone}{tvertbarrdash}%
8587 {\LWR@setexparray{LWR@colbarspec}%
8588 {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdoubledash}}%
8589 {\LWR@setexparray{LWR@colbarspec}%
8590 {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdash}}%
8591 }%
8592 \booltrue{LWR@validtablecol}%
8593 }

```

`\LWR@parsesemicoloncolumn` Handles vertical rules.

```

8594 \newcommand*{\LWR@parsesemicoloncolumn}{%

```

Treat ; as a : column:

```

8595 \LWR@parsecoloncolumn%

```

Skip the following width token:

```

8596 \defaddtocounter{LWR@tablecolspecindex}{1}%
8597 }

```

### 73.9 Parsing ‘l’, ‘c’, or ‘r’ columns

`\LWR@parsenormalcolumn` `{\<thiscolumn>}`

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

```

8598 \newcommand*{\LWR@parsenormalcolumn}[1]{%
8599 \defaddtocounter{\LWR@tabletotalLaTeXcols}{1}%
8600 \defaddtocounter{\LWR@tabletotalLaTeXcolsnext}{1}%

8601 \LWR@setexparray{\LWR@tablecolspec}{\arabic{\LWR@tabletotalLaTeXcols}}{#1}%

8602 \LWR@traceinfo{normal column \arabic{\LWR@tabletotalLaTeXcols}: #1}%
8603 \LWR@setexparray{\LWR@colatspec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
8604 \LWR@setexparray{\LWR@colbangspec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
8605 \LWR@setexparray{\LWR@colbeforespec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
8606 \LWR@setexparray{\LWR@colafterspec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
8607 \LWR@setexparray{\LWR@colbarspec}{\arabic{\LWR@tabletotalLaTeXcolsnext}}{}%
8608 \booltrue{\LWR@validtablecol}%
8609 }
```

### 73.10 Parsing ‘p’, ‘m’, or ‘b’ columns

`\LWR@parsepcolumn`  $\langle\textit{thiscolumn}\rangle$  The width will be ignored.

```

8610 \newcommand*{\LWR@parsepcolumn}[1]{%

Converts to the given column type:

8611 \LWR@parsenormalcolumn{#1}%

Skips the following width token:

8612 \defaddtocounter{\LWR@tablecolspecindex}{1}%
8613 }
```

### 73.11 Parsing ‘w’ columns

`\LWR@parsewcolumn` The width will be ignored.

```

8614 \newcommand*{\LWR@parsewcolumn}{%

8615 \LWR@columnspeclookahead{1}%
8616 \expandafter\LWR@parsenormalcolumn\expandafter{\LWR@strresulttwo}%

Skips the following width and alignment tokens:

8617 \defaddtocounter{\LWR@tablecolspecindex}{2}%
8618 }
```

### 73.12 Parsing '\*' columns

`\LWR@parsestarcolumn` Star columns should already have been expanded, so this should never be used.

```
8619 \newcommand*{\LWR@parsestarcolumn}{%
8620 \defaddtocounter{\LWR@tablecolspecindex}{2}%
8621 }
```

### 73.13 Parsing 'D' columns

From the dcolumn package.

`\LWR@parseDcolumn` `{\langle thiscolumn \rangle}` The three parameters will be ignored.

```
8622 \newcommand*{\LWR@parseDcolumn}[1]{%
```

Converts to the given column type.

```
8623 \LWR@parsenormalcolumn{#1}%
```

Skips the following three parameters.

```
8624 \defaddtocounter{\LWR@tablecolspecindex}{3}%
8625 }
```

### 73.14 Expanding the star column specifications

Ctrl `LWR@starcount` Internal count for duplicating star columns.

```
8626 \newcount\LWR@starcount
```

`\LWR@expcolspec` Temporary storage used to build the expanded column specifier.

```
8627 \newcommand*{\LWR@expcolspec}{}
```

Ctrl `LWR@splitstarindex` Indexes into the column specifiers.

```
8628 \newcounter{\LWR@splitstarindex}
```

Ctrl `LWR@splitstarcopies` Number of copies.

```
8629 \newcounter{\LWR@splitstarcopies}
```

`\LWR@splitstarcontents` Contents to duplicate.

```
8630 \newcommand*{\LWR@splitstarcontents}{}
```

`\expandcolspec` Expands `\LWR@origcolspec` for star columns.

```
8631 \newcommand*{\expandcolspec}{%
```

Find the position of any star token.

```
8632 \StrPosition{\LWR@origcolspec}{*}[\LWR@tempone]%
```

Expand until no stars are found:

```
8633 \whileboolexpr{ test {\ifnumgreater{\LWR@tempone}{0}}}%
8634 {%
```

Begin with any characters to the left of the star.

```
8635 \setcounter{\LWR@splitstarindex}{\LWR@tempone}%
8636 \addtocounter{\LWR@splitstarindex}{-1}%
8637 \StrLeft{\LWR@origcolspec}{\value{\LWR@splitstarindex}}[\LWR@expcolspec]%
```

Move past the star to remember its number of copies.

```
8638 \addtocounter{\LWR@splitstarindex}{2}%
8639 \StrChar{\LWR@origcolspec}{\value{\LWR@splitstarindex}}[\LWR@tempone]%
8640 \setcounter{\LWR@splitstarcopies}{\expandafter\@firstofone\LWR@tempone}%
```

Move past the number of copies and remember the contents.

```
8641 \addtocounter{\LWR@splitstarindex}{1}%
8642 \StrChar{\LWR@origcolspec}{\value{\LWR@splitstarindex}}[\LWR@splitstarcontents]%
```

For each copy, append the contents.

```
8643 \ifnumgreater{\value{\LWR@splitstarcopies}}{0}%
8644 {%
8645 \LWR@starcount=\value{\LWR@splitstarcopies}%
8646 \loop
8647 \appto\LWR@expcolspec{%
```

(Remove the enclosing braces.)

```
8648 \expandafter\@firstofone\LWR@splitstarcontents%
8649 }%
8650 \advance \LWR@starcount -1
8651 \ifnum \LWR@starcount>0 \repeat
8652 }{%
```

Remove any token to the left, and append the rightmost remaining tokens.

```
8653 \StrGobbleLeft{\LWR@origcolspec}{\value{\LWR@splitstarindex}}[\colspecremainder]%
8654 \appto{\LWR@expcolspec}{\colspecremainder}%
```

Remember the final result.

```
8655 \edef\LWR@origcolspec{\LWR@expcolspec}%
```

Table 12: Tabular baseline

|   |     |     |     |   |
|---|-----|-----|-----|---|
| l | p   | m   | b   | r |
|   |     |     | bot |   |
|   |     | mid | bot |   |
| l | par | mid | bot | r |
|   | par | mid |     |   |
|   | par |     |     |   |

See if more stars exist.

```
8656 \StrPosition{\LWR@origcolspec}{*}[\LWR@tempone]%
8657 }%
8658 }
```

### 73.15 Parsing the column specifications

 **tabular baselines** HTML CSS cannot exactly match the L<sup>A</sup>T<sub>E</sub>X concept of a baseline for a table row. Table 12 shows the L<sup>A</sup>T<sub>E</sub>X results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the p column specification in table 13 for details.

Table 13 describes how each kind of column is converted to HTML.

```
\LWR@parsetablecols {<colspecs>}
```

Scans the column specification left to right.

Builds `\LWR@tablecolspec` with the final specification, one L<sup>A</sup>T<sub>E</sub>X column per entry. The final number of L<sup>A</sup>T<sub>E</sub>X columns in each row is stored in `\LWR@tabletotalLaTeXcols`, which is the number of `&` and `\\` in each line, but which does not include `@`, `!`, `<`, `>` specifications in the count.

```
8659 \newcommand*\LWR@parsetablecols[1]{%
8660 \LWR@traceinfo{\LWR@parsetablecols}%
```

Remember the original supplied column spec:

```
8661 \renewcommand*\LWR@origcolspec{#1}%
```

Remove spaces:

```
8662 \expandarg%
8663 \StrSubstitute{\LWR@origcolspec}{ }{ }[\LWR@origcolspec]%
```

Expand any star columns:

```
8664 \expandcolspec%
```

Table 13: Tabular HTML column conversions

---

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>l, r, c:</b>          | Converted to table cells without paragraph tags.<br>Uses css <code>vertical-align:middle</code> so that top or bottom-aligned cells may go above or below this cell.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>p:</b>                | Converted to table cells with paragraph tags. Ref: Table 12, $\LaTeX$ places the top line of a parbox aligned with the rest of the text line, so css <code>vertical-align:bottom</code> is used to have the HTML result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the HTML conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the css may be desired, changing <code>td.tdp</code> , <code>td.tdP</code> , <code>td.tdprule</code> , and <code>td.tdPrule</code> to <code>vertical-align: middle</code> . Another possibility is to change L,R,C, and P to <code>vertical-align: top</code> and not worry about the alignment of B and M cells or trying to approximate $\LaTeX$ baselines. |
| <b>m:</b>                | With paragraph tags, css <code>vertical-align:middle</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>b:</b>                | With paragraph tags, css <code>vertical-align:top</code> so that the bottom of the text is closest to the middle of the text line.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>P, M, B:</b>          | Horizontally-centered versions.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>S:</b>                | Converted to 'r'. Ignores optional argument. From the <code>siunitx</code> package.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>D:</b>                | Converted to 'c'. From the <code>dcolumn</code> package.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>@, !, &gt;, &lt;:</b> | One each, in that order.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b> :</b>                | Vertical rule.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Unknown:</b>          | Converted to 'l'.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>\newcolumn:</b>       | Currently treated as unknown.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

---

The parsed column spec data array, `LWR@tablecolspec`, will be overwritten with new values.

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```

8665 \defcounter{LWR@tabletotalLaTeXcols}{0}%
8666 \defcounter{LWR@tabletotalLaTeXcolsnext}{1}%
8667 \LWR@setexparray{LWR@colatspec}{leftedge}{}%
8668 \LWR@setexparray{LWR@colatspec}{1}{}%
8669 \LWR@setexparray{LWR@colatspec}{2}{}%
8670 \LWR@setexparray{LWR@colatspec}{3}{}%
8671 \LWR@setexparray{LWR@colbangspec}{leftedge}{}%
8672 \LWR@setexparray{LWR@colbangspec}{1}{}%
8673 \LWR@setexparray{LWR@colbangspec}{2}{}%
8674 \LWR@setexparray{LWR@colbangspec}{3}{}%
8675 \LWR@setexparray{LWR@colbeforespec}{1}{}%
8676 \LWR@setexparray{LWR@colbeforespec}{2}{}%
8677 \LWR@setexparray{LWR@colbeforespec}{3}{}%
8678 \LWR@setexparray{LWR@colafterspec}{1}{}%
8679 \LWR@setexparray{LWR@colafterspec}{2}{}%
8680 \LWR@setexparray{LWR@colafterspec}{3}{}%
8681 \LWR@setexparray{LWR@colbarspec}{leftedge}{}%
8682 \LWR@setexparray{LWR@colbarspec}{1}{}%
8683 \LWR@setexparray{LWR@colbarspec}{2}{}%
8684 \LWR@setexparray{LWR@colbarspec}{3}{}%

```

Starting at the first column specification:

```

8685 \defcounter{LWR@tablecolspecindex}{1}%

```

Place the colspecs string length into `\LWR@strresult`, and remember the number of characters in the column specification:

```

8686 \expandarg%
8687 \StrLen{\LWR@origcolspec}[\LWR@strresult]%
8688 \fullexpandarg%
8689 \LWR@traceinfo{original column spec length: \LWR@strresult}%
8690 \defcounter{LWR@tablecolspecwidth}{\LWR@strresult}%

```

Haven't seen any optional arguments so far

```

8691 \boolfalse{LWR@opttablecol}%

```

Scan through the column specifications:

```

8692 \whileboolexpr{%
8693 not test{%
8694 \ifnumcomp{\value{LWR@tablecolspecindex}}{>}%
8695 {\value{LWR@tablecolspecwidth}}%
8696 }%
8697 }%
8698 {%

```

Place the next single-character column type into `\LWR@strresult`:

```
8699 \expandarg%
8700 \StrChar{\LWR@origcolspec}{\arabic{\LWR@tablecolspecindex}}[\LWR@strresult]%
8701 \LWR@traceinfo{position \arabic{\LWR@tablecolspecindex}: \LWR@strresult}%
8702 \fullexpandarg%
```

Not yet found a valid column type:

```
8703 \boolfalse{\LWR@validtablecol}%
```

Skip over any optional arguments, such as siunitx S column:

```
8704 \IfStrEq{\LWR@strresult}{[]}{\booltrue{\LWR@opttablecol}}{}}%
```

Throw away anything found inside the optional argument:

```
8705 \ifbool{\LWR@opttablecol}%
8706 {}% inside an optional argument
8707 {}% not an optional tabular argument
```

Not inside an optional argument, so consider the column type:

```
8708 \IfStrEq{\LWR@strresult}{l}{\LWR@parsenormalcolumn{l}}{}}%
8709 \IfStrEq{\LWR@strresult}{c}{\LWR@parsenormalcolumn{c}}{}}%
8710 \IfStrEq{\LWR@strresult}{r}{\LWR@parsenormalcolumn{r}}{}}%
8711 \IfStrEq{\LWR@strresult}{L}{\LWR@parsenormalcolumn{L}}{}}%
8712 \IfStrEq{\LWR@strresult}{C}{\LWR@parsenormalcolumn{C}}{}}%
8713 \IfStrEq{\LWR@strresult}{R}{\LWR@parsenormalcolumn{R}}{}}%
8714 \IfStrEq{\LWR@strresult}{J}{\LWR@parsenormalcolumn{J}}{}}%

8715 \IfStrEq{\LWR@strresult}{S}{\LWR@parsenormalcolumn{S}}{}}%
8716 \IfStrEq{\LWR@strresult}{s}{\LWR@parsenormalcolumn{s}}{}}%

8717 \IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@parseatcolumn}{}}%
8718 \IfStrEq{\LWR@strresult}{!}{\LWR@parsebangcolumn}{}}%
8719 \IfStrEq{\LWR@strresult}{>}{\LWR@parsebeforecolumn}{}}%
8720 \IfStrEq{\LWR@strresult}{<}{\LWR@parseaftercolumn}{}}%
8721 \IfStrEq{\LWR@strresult}{|}{\LWR@parsebarcolumn}{}}%
8722 \IfStrEq{\LWR@strresult}{:}{\LWR@parsecoloncolumn}{}}%
8723 \IfStrEq{\LWR@strresult}{;}{\LWR@parsesemicoloncolumn}{}}%

8724 \IfStrEq{\LWR@strresult}{p}{\LWR@parsepcolumn{p}}{}}%
8725 \IfStrEq{\LWR@strresult}{m}{\LWR@parsepcolumn{m}}{}}%
8726 \IfStrEq{\LWR@strresult}{b}{\LWR@parsepcolumn{b}}{}}%

8727 \IfStrEq{\LWR@strresult}{w}{\LWR@parsewcolumn}{}}%
8728 \IfStrEq{\LWR@strresult}{W}{\LWR@parsewcolumn}{}}%
```

A star column:

```
8729 \IfStrEq{\LWR@strresult}{*}{\LWR@parsestarcolumn}{}}%
```

From the dcolumn package:

```
8730 \IfStrEq{\LWR@strresult}{D}{\LWR@parseDcolumn{c}}{%
```

From the tabularx package. X column has no parameter, but will be given paragraph tags.

```
8731 \IfStrEq{\LWR@strresult}{X}{\LWR@parsenormalcolumn{X}}{%
```

---

Many people define centered versions “P”, “M”, and “B”:

```
\newcolumn{P}[1]{>\centering\arraybackslash}p{#1}}
```

---

```
8732 \IfStrEq{\LWR@strresult}{P}{\LWR@parsepcolumn{P}}{%
```

```
8733 \IfStrEq{\LWR@strresult}{M}{\LWR@parsepcolumn{M}}{%
```

```
8734 \IfStrEq{\LWR@strresult}{B}{\LWR@parsepcolumn{B}}{%
```

If this column was an invalid column type, convert it to an l column:

```
8735 \ifbool{LWR@validtablecol}{%

```

```
8736 \LWR@traceinfo{invalid column type: \LWR@strresult}%

```

```
8737 \LWR@parsenormalcolumn{l}%

```

```
8738 }%

```

```
8739 }% not an optional column argument
```

If read the closing bracket, no longer inside the optional argument:

```
8740 \IfStrEq{\LWR@strresult}{] }{\boolfalse{LWR@opttablecol}}{%
```

Move to the next character:

```
8741 \defaddtocounter{LWR@tablecolspecindex}{1}%

```

```
8742 }% whiledo

```

```
8743 }%
```

## 73.16 colortbl and xcolor tabular color support

These macros provide a minimal emulation of some colortbl macros which might appear between table cells. If colortbl is loaded, these macros will be replaced with functional versions.

For each of the HTML colors below, the text for the HTML color is set if requested, but the macro is empty if none has been set.

`\rownum` Reserve a counter register.

```
8744 \@ifundefined{rownum}{\newcount\rownum}{}
```

`\@rowcolors` Emulated in case `xcolor` is not used.

8745 `\newcommand*\@rowcolors{}`

`\@rowcolours` Emulated in case `xcolor` is not used.

8746 `\newcommand*\@rowcolours{}`

`\LWR@xcolorrowHTMLcolor` Emulated `xcolor` row color.

8747 `\newcommand*\LWR@xcolorrowHTMLcolor{}`

`\LWR@columnHTMLcolor` HTMLstyle code for the column color.

8748 `\def\LWR@columnHTMLcolor{}`

`\LWR@rowHTMLcolor` HTMLstyle code for the row color.

8749 `\def\LWR@rowHTMLcolor{}`

`\LWR@cellHTMLcolor` HTMLstyle code for the cell color.

8750 `\def\LWR@cellHTMLcolor{}`

`\LWR@ruleHTMLcolor` HTMLstyle code for the rule color.

8751 `\newcommand*\LWR@ruleHTMLcolor{}`

`\rowcolor` [*model*] {*color*} [*left overhang*] [*right overhang*] Print version. The HTML version is in `lwarp-colortbl`. Used before starting a tabular data cell, thus `\LWR@getmynexttoken`.

8752 `\newcommand*\rowcolor{\LWR@getmynexttoken}%`

`\arrayrulecolor` [*model*] {*color*}

`\arrayrulecolornexttoken` [*model*] {*color*}

Print versions for use outside and inside a tabular:

8753 `\newcommand{\arrayrulecolor}[2][named]{}`

8754 `\newcommand{\arrayrulecolornexttoken}[2][named]{\LWR@getmynexttoken}`

`\doublerulesepcolor` [*model*] {*color*}

`\doublerulesepcolornexttoken` [*model*] {*color*}

Print versions for use inside and outside a tabular:

8755 `\newcommand{\doublerulesepcolor}[2][named]{}`

8756 `\newcommand{\doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}`

### 73.17 Starting a new row

`\LWR@maybeowntablerow` If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for `hline` or `tbrule` if necessary.

```
8757 \newcommand*{\LWR@maybeowntablerow}
8758 {%
8759 \ifbool{\LWR@startedrow}%
8760 {}% started the row
8761 {% not started the row
```

Remember that now have started the row:

```
8762 \booltrue{\LWR@startedrow}%
```

Create the row tag, with a class if necessary.

```
8763 \booltrue{\LWR@intabularmetadata}%
8764 \ifboolexpr{%
8765 test{\ifnumcomp{\value{\LWR@hlines}}{>}{0}} or%
8766 test{\ifnumcomp{\value{\LWR@hdashedlines}}{>}{0}}}%
8767 }%
8768 {%
8769 \LWR@htmltag{tr class="hline" }%
8770 \LWR@orignewline%
8771 }%
8772 {% not doing hline
8773 \ifbool{\LWR@doingtbrule}%
8774 {%
8775 \ifdefvoid{\LWR@ruleHTMLcolor}{%
8776 \LWR@htmltag{tr class="tbrule"}%
8777 }{%
8778 \LWR@htmltag{%
8779 tr class="tbrule" % space
8780 style="border-top: 1px solid % space
8781 \LWR@origpound\LWR@ruleHTMLcolor "%
8782 }%
8783 }%
8784 \LWR@orignewline%
8785 }%
8786 {\LWR@htmltag{tr}\LWR@orignewline}%
8787 }% end of not doing hline
8788 }% end of not started the row
8789 }
```

### 73.18 Printing vertical bar tags

`\LWR@printbartag`  $\{ \langle index \rangle \}$

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```
8790 \newcommand*{\LWR@printbartag}[1]{%
```

```

8791 \LWR@traceinfo{LWR@printbartag !#1!}%
8792 \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
8793 {}% muting or empty
8794 {% not muting
8795 \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{#1}}%
8796 \ifdefempty{\LWR@tempone}{\LWR@tempone}%
8797 }% not muting
8798 \LWR@traceinfo{LWR@printbartag done}%
8799 }

```

### 73.19 Printing @ or ! tags

`\LWR@printatbang` {<*at* — *or* — *bang*>} {<*index*>}

```
8800 \newcommand*{\LWR@printatbang}[2]{%
```

Fetch the column at or bang spec:

```

8801 \xdef\LWR@atbangspec{\LWR@getexparray{LWR@col#1spec}{#2}}%
8802 \LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}%

```

Only generate if is not empty;

```

8803 \ifdefempty{\LWR@atbangspec}%
8804 {}%
8805 {% not empty
8806 \LWR@htmltag{%
8807 td class="td#1%
8808 \LWR@subaddcmidruletrim{}}}%
8809 \LWR@printbartag{#2}%
8810 "%
8811 \LWR@tdstartstyles%
8812 \LWR@addcmidrulewidth%
8813 \LWR@addcdashline%
8814 \LWR@addtabularrulecolors%
8815 \LWR@tdendstyles%
8816 }%

```

Create an empty cell if muting for the `\bottomrule`:

```

8817 \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
8818 {}%
8819 {\LWR@atbangspec}%
8820 %
8821 \LWR@htmltag{/td}\LWR@orignewline%
8822 \global\booltrue{LWR@tabularcellladded}%
8823 }% not empty
8824 }%

```

`\LWR@addleftmostbartag`

```

8825 \newcommand*\LWR@addleftmostbartag}{%
8826 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=} {1}{%
8827 \LWR@printbartag{leftedge}%
8828 }{}%
8829 }

```

`\LWR@tabularleftedge`

```

8830 \newcommand*\LWR@tabularleftedge}{%
8831 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=} {1}{%
8832 {%
8833 \LWR@printatbang{at}{leftedge}%
8834 \LWR@printatbang{bang}{leftedge}%
8835 }% left edge
8836 }{}% not left edge
8837 }

```

## 73.20 Data opening tag

`\LWR@thiscolspec` Temporary storage.

```

8838 \newcommand*\LWR@thiscolspec{}

```

`\LWR@tabledatasinglecolumn` Print a table data opening tag with style for alignment and color.

```

8839 \newcommand*\LWR@tabledatasinglecolumn}{%
8840 {%
8841 \LWR@traceinfo{LWR@tabledatasinglecolumn}%
8842 \LWR@maybenewtablerow%

```

Don't start a new paragraph tag if have already started one:

```

8843 \ifbool{LWR@intabularmetadata}%
8844 {%

```

If have found the end of tabular command, do not create the next data cell:

```

8845 \ifbool{LWR@exitingtabular}}{}%
8846 {% not exiting tabular

```

Print the @ and ! contents before first column:

```

8847 \LWR@tabularleftedge%

```

Fetch the current column's alignment character into `\LWR@strresult`:

```

8848 \xdef\LWR@strresult{%
8849 \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
8850 }%

```

print the start of a new table data cell:

```
8851 \LWR@traceinfo{LWR@tabledatasinglecolumnntag: about to print td tag}%
8852 \LWR@htmltag{%
8853 td class="td%
```

append this column's spec:

```
8854 \LWR@strresult%
```

If this column has a cmidrule, add “rule” to the end of the HTML class tag. Also add vertical bar tags.

```
8855 \LWR@addcmidruletrim%
8856 \LWR@addleftmostbartag%
8857 \LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
8858 "%
```

Add styles for rules, alignment:

```
8859 \LWR@tdstartstyles%
8860 \LWR@addcmidrulewidth%
8861 \LWR@addcdashline%

8862 \xdef\LWR@thiscolspec{%
8863 \LWR@getexparray{LWR@tablecolspec}%
8864 {\arabic{LWR@tableLaTeXcolindex}}%
8865 }%
8866 \LWR@addformatwpalignment{\LWR@thiscolspec}%
```

Add styles for cell and rule colors:

```
8867 \LWR@addtabulararrowcolor%
8868 \LWR@addtabularrulecolors%

8869 \LWR@tdendstyles%
8870 }% HTML td
8871 \LWR@traceinfo{LWR@tabledatasinglecolumnntag: done printing td tag}%
```

If this is a p, m, b, or X column, allow paragraphs:

```
8872 \ifboolexpr{%
8873 test{ \ifdefstring{\LWR@strresult}{p} } or
8874 test{ \ifdefstring{\LWR@strresult}{m} } or
8875 test{ \ifdefstring{\LWR@strresult}{b} } or
8876 test{ \ifdefstring{\LWR@strresult}{P} } or
8877 test{ \ifdefstring{\LWR@strresult}{M} } or
8878 test{ \ifdefstring{\LWR@strresult}{B} } or
8879 test{ \ifdefstring{\LWR@strresult}{X} }
8880 }%
8881 {% allow pars
8882 \LWR@traceinfo{LWR@tabledatasinglecolumnntag: about to LWR@startpars}%
8883 \booltrue{LWR@tableparcell}%
```

```

8884 \LWR@startpars%
8885 \LWR@traceinfo{LWR@tabledatasinglecolumntag: done with LWR@startpars}%
8886 }% allow pars
8887 {}% no pars

```

Print the > contents unless muted for the \bottomrule:

```

8888 \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
8889 {}%
8890 {%
8891 \LWR@getexparray{LWR@colbefore-spec}{\arabic{LWR@tableLaTeXcolindex}}%
8892 }%
8893 \boolfalse{LWR@intabularmetadata}%
8894 }% not exiting tabular
8895 }{}% in tabular metadata
8896 \LWR@traceinfo{LWR@tabledatasinglecolumntag: done}%
8897 }%

```

### 73.21 Midrules

`LWR@midrules` `LWR@midrules` is a data array (section 41) of columns each containing a non-zero width if a midrule should be created for this column.

`LWR@trimlrules` `LWR@trimlrules` is a data array (section 41) of columns containing `l` if a midrule should be left trimmed for each column.

`LWR@trimrrules` `LWR@trimrrules` is a data array (section 41) of columns containing `r` if a midrule should be right trimmed for each column.

`LWR@cdashlines` `LWR@cdashlines` is a data array (section 41) of columns each containing a `Y` if an `arydashln` package "cdashed line" should be created for this column.

Len `\LWR@heavyrulewidth` The default width of the rule.

```

8898 \newlength{\LWR@heavyrulewidth}
8899 \setlength{\LWR@heavyrulewidth}{.08em}

```

Len `\LWR@lightrulewidth` The default width of the rule.

```

8900 \newlength{\LWR@lightrulewidth}
8901 \setlength{\LWR@lightrulewidth}{.05em}

```

Len `\LWR@cmidrulewidth` The default width of the rule.

```

8902 \newlength{\LWR@cmidrulewidth}
8903 \setlength{\LWR@cmidrulewidth}{.03em}

```

Len `\LWR@thiscmidrulewidth` The width of the next rule, defaulting to `\LWR@cmidrulewidth`.

If not `\LWR@cmidrulewidth`, a style will be used to generate the custom width.

Assigned from the `LWR@midrules` array.

```
8904 \newlength{\LWR@thiscmidrulewidth}
8905 \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}
```

`\LWR@clearmidrules` Start new midrules. Called at beginning of tabular and also at `\`.

Clears all `LWR@midrules` and `LWR@trimrules` markers for this line.

```
8906 \newcommand*\LWR@clearmidrules}
8907 {%
8908 \defcounter{LWR@midrulecounter}{1}%
8909 \whileboolexpr{%
8910 not test{%
8911 \ifnumcomp{\value{LWR@midrulecounter}}{>}%
8912 {\value{LWR@tabletotalLaTeXcols}}%
8913 }%
8914 }%
8915 {%
8916 \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{0pt}%
8917 \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
8918 \LWR@setexparray{LWR@trimlrules}{\arabic{LWR@midrulecounter}}{}%
8919 \LWR@setexparray{LWR@trimrrules}{\arabic{LWR@midrulecounter}}{}%
8920 \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{N}%
8921 \defaddtocounter{LWR@midrulecounter}{1}%
8922 }%
8923 }
```

`\LWR@subcmidrule`  $\langle width \rangle$   $\langle trim \rangle$   $\langle leftcolumn \rangle$   $\langle rightcolumn \rangle$

Marks `LWR@midrules` data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

`LWR@doingcmidrule` is set to force an empty row at the end of the tabular to create the rule.

```
8924 \newcommand*\LWR@subcmidrule}[4]{%
8925 \defcounter{LWR@midrulecounter}{#3}%
8926 \whileboolexpr{%
8927 not test {%
8928 \ifnumcomp{\value{LWR@midrulecounter}}{>}{#4}%
8929 }%
8930 }%
8931 {%
8932 \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{#1}%
8933 \defaddtocounter{LWR@midrulecounter}{1}%
8934 }% whiledo
8935 \IfSubStr{#2}{l}{\LWR@setexparray{LWR@trimlrules}{#3}{l}}{}%
8936 \IfSubStr{#2}{r}{\LWR@setexparray{LWR@trimrrules}{#4}{r}}{}%
8937 \booltrue{LWR@doingcmidrule}%
8938 }
```

`\LWR@docmidrule`  $[\langle width \rangle]$   $(\langle trim \rangle)$   $\langle leftcolumn-rightcolumn \rangle$

Marks LWR@midrules array elements to be a non-zero width from left to right columns. Also marks trimming for the L and/or R columns.

```
8939 \NewDocumentCommand{\LWR@docmidrule}
8940 {0{\LWR@cmidrulewidth} D()} >{\SplitArgument{1}{-}}m}
8941 {\LWR@subcmidrule{#1}{#2}#3}
```

`\LWR@subcdashline`  $\{\langle leftcolumn \rangle\} \{\langle rightcolumn \rangle\}$

Marks LWR@cdashlines data array elements to be Y from left to right columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
8942 \newcommand*{\LWR@subcdashline}[2]{%
8943 \defcounter{LWR@midrulecounter}{#1}%
8944 \whileboolexpr{%
8945 not test {%
8946 \ifnumcomp{\value{LWR@midrulecounter}}{>}{#2}%
8947 }%
8948 }%
8949 {%
8950 \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{Y}%
8951 \defaddtocounter{LWR@midrulecounter}{1}%
8952 }% whiledo
8953 \booltrue{LWR@doingcmidrule}%
8954 }
```

`\LWR@docdashline`  $\{\langle leftcolumn-rightcolumn \rangle\}$

Marks LWR@cdashlines data array elements to be Y from left to right columns.

```
8955 \NewDocumentCommand{\LWR@docdashline}
8956 {>{\SplitArgument{1}{-}}m}%
8957 {%
8958 \LWR@subcdashline#1%
8959 }
```

`\LWR@tdstartstyles` Begins possibly adding a table data cell style.

```
8960 \newcommand*{\LWR@tdstartstyles}{\boolfalse{LWR@tdhavecellstyle}}
```

`\LWR@tdaddstyle` Starts adding a table data cell style.

```
8961 \newcommand*{\LWR@tdaddstyle}{%
8962 \ifbool{LWR@tdhavecellstyle}%
8963 {; }%
8964 { style="}%
8965 \booltrue{LWR@tdhavecellstyle}%
8966 }
```

`\LWR@tdendstyles` Finishes possibly adding a table data cell style. Prints the closing quote.

```

8967 \newcommand*{\LWR@tdendstyles}{%
8968 \ifbool{\LWR@tdhavecellstyle}%
8969 {%
8970 "%
8971 \boolfalse{\LWR@tdhavecellstyle}%
8972 }{}%
8973 }
```

`\LWR@subaddcmidruletrim` `{\lefttrim}` `{\righttrim}` Adds a `\cmidrule` with optional trim.

```

8974 \newcommand*{\LWR@subaddcmidruletrim}[2]{%
8975 \setlength{\LWR@templengthone}{%
8976 \LWR@getexparray{\LWR@midrules}{\arabic{\LWR@tableLaTeXcolindex}}%
8977 }%
8978 \ifdimcomp{\LWR@templengthone}{>}{0pt}%
8979 {%
```

Print the class with left and right trim letters appended:

```
8980 \LWR@origtilde tdrule#1#2%
```

Remember the width of the rule:

```

8981 \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
8982 }%
8983 {%
8984 \setlength{\LWR@thiscmidrulewidth}{0pt}%
8985 }%
8986 }
```

`\LWR@addcmidruletrim` Adds left or right trim to a `\cmidrule`.

```

8987 \newcommand*{\LWR@addcmidruletrim}{%
8988 \LWR@subaddcmidruletrim%
8989 {\LWR@getexparray{\LWR@trimlrules}{\arabic{\LWR@tableLaTeXcolindex}}}%
8990 {\LWR@getexparray{\LWR@trimrrules}{\arabic{\LWR@tableLaTeXcolindex}}}%
8991 }
```

`\LWR@addrulewidth` `{\thiswidth}` `{\defaultwidth}`

If not default width, add a custom style with width and color depending on `thiswidth`.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
8992 \newcommand{\LWR@addrulewidth}[2]{%
```

Only add a custom width if `thiswidth` is different than the `defaultwidth`, or if a color is being used:

```

8993 \ifboolexpr{%
8994 test{\ifdimcomp{#1}{=}{0pt}} or
8995 (
8996 (test{\ifdimcomp{#1}{=}{#2}} and not bool{FormatWP})
8997 and (test {\ifdefvoid{\LWR@ruleHTMLcolor}})
8998)
8999 }%
9000 {}% default width and color
9001 {% custom width and/or color

```

Ensure that the width is wide enough to display in the browser:

```
9002 \LWR@forceminwidth{#1}%
```

Begin adding another style:

```
9003 \LWR@tdaddstyle%
```

The style itself:

```
9004 border-top:\LWR@printlength{\LWR@atleastonept} solid % space
```

If default gray, the darkness of the color depends on the thickness of the rule:

```

9005 \ifdefvoid{\LWR@ruleHTMLcolor}{%
9006 \ifdimcomp{#1}{<}{\LWR@lightrulewidth}%
9007 {\LWR@origpound{ }A0A0A0}%
9008 {% lightrule or heavier
9009 \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}%
9010 {\LWR@origpound{ }808080}%
9011 {black}%
9012 }% lightrule or heavier
9013 }{%
9014 \LWR@origpound\LWR@ruleHTMLcolor%
9015 }%
9016 }% custom width and/or color
9017 }

```

`\LWR@addcmidrulewidth` Adds a style for the rule width.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```

9018 \newcommand{\LWR@addcmidrulewidth}{%
9019 \LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
9020 }

```

`\LWR@addcdashline` Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```

9021 \newcommand{\LWR@addcdashline}{%
9022 \edef\LWR@tempone{%
9023 \LWR@getexparray{\LWR@cdashlines}{\arabic{\LWR@tableLaTeXcolindex}}%
9024 }%
9025 \ifdefstring{\LWR@tempone}{Y}{%

```

```

9026 \LWR@tdaddstyle%
9027 border-top: 1pt dashed %
9028 \ifdefvoid{\LWR@ruleHTMLcolor}%
9029 {black}%
9030 {\LWR@origpound\LWR@ruleHTMLcolor}%
9031 }{}%
9032 }

```

`\LWR@WPcell` {<*text-align*>} {<*vertical-align*>}

```

9033 \newcommand*{\LWR@WPcell}[2]{%
9034 \LWR@tdaddstyle%
9035 \LWR@print@mbbox{text-align:#1}; \LWR@print@mbbox{vertical-align:#2}%
9036 }

```

`\LWR@addformatwpalignment` If `FormatWP`, adds a style for the alignment.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```

9037 \newcommand*{\LWR@addformatwpalignment}[1]{%
9038 \ifbool{FormatWP}{%
9039 \IfSubStr{#1}{l}{\LWR@WPcell{left}{middle}}{}%
9040 \IfSubStr{#1}{c}{\LWR@WPcell{center}{middle}}{}%
9041 \IfSubStr{#1}{r}{\LWR@WPcell{right}{middle}}{}%
9042 \IfSubStr{#1}{p}{\LWR@WPcell{left}{bottom}}{}%
9043 \IfSubStr{#1}{m}{\LWR@WPcell{left}{middle}}{}%
9044 \IfSubStr{#1}{b}{\LWR@WPcell{left}{top}}{}%
9045 \IfSubStr{#1}{P}{\LWR@WPcell{center}{bottom}}{}%
9046 \IfSubStr{#1}{M}{\LWR@WPcell{center}{middle}}{}%
9047 \IfSubStr{#1}{B}{\LWR@WPcell{center}{top}}{}%
9048 }{}%
9049 }

```

## 73.22 Cell colors

`\LWR@addtabulararrowcolor` Adds a cell's row color style, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```

9050 \newcommand*{\LWR@addtabulararrowcolor}{%
9051 \ifbool{LWR@tabularmutemods}{}{}%
9052 \ifdefvoid{\LWR@rowHTMLcolor}{%
9053 \ifdefvoid{\LWR@xcolorrowHTMLcolor}{}{}%
9054 {% xcolor row color
9055 \LWR@tdaddstyle%
9056 background:\LWR@origpound\LWR@xcolorrowHTMLcolor%
9057 }%
9058 }%
9059 {% explicit row color
9060 \LWR@tdaddstyle%
9061 background:\LWR@origpound\LWR@rowHTMLcolor%
9062 }%

```

```
9063 }%
9064 }
```

`\LWR@addtabularhrulecolor` Adds a cell's horizontal rule color style, if needed.

```
9065 \newcommand*{\LWR@addtabularhrulecolor}{%
```

If either form of horizontal rule is requested:

```
9066 \ifboolexpr{%
9067 test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
9068 test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
9069 bool{LWR@doingtbrule}%
9070 }{%
```

If there is a no custom color:

```
9071 \ifdefvoid{\LWR@ruleHTMLcolor}%
9072 {%
9073 \ifnumcomp{\value{LWR@hlines}}{>}{1}%
9074 {%
9075 \LWR@tdaddstyle%
9076 border-top: 4px double%
9077 }{% else
9078 \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
9079 {%
9080 \LWR@tdaddstyle%
9081 border-top: 2px dashed%
9082 }{% else
9083 \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
9084 {%
9085 \LWR@tdaddstyle%
9086 border-top: 1px dashed%
9087 }{}}}%
```

If no color and not doubled or dashed, then add nothing, since a simpler rule is the default.

```
9088 }%
```

If there is a custom color:

```
9089 {%
9090 \ifnumcomp{\value{LWR@hlines}}{>}{1}%
9091 {%
9092 \LWR@tdaddstyle%
9093 border-top: 4px double \LWR@origpound\LWR@ruleHTMLcolor%
9094 }{% else
9095 \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
9096 {%
9097 \LWR@tdaddstyle%
9098 border-top: 2px dashed \LWR@origpound\LWR@ruleHTMLcolor%
9099 }{% else
9100 \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
```

```

9101 {%
9102 \LWR@tdaddstyle%
9103 border-top: 1px dashed \LWR@origpound\LWR@ruleHTMLcolor%
9104 }{% else
9105 \LWR@tdaddstyle%
9106 border-top: 1px solid \LWR@origpound\LWR@ruleHTMLcolor%
9107 }}}%
9108 }%
9109 }{%
9110 }

```

`\LWR@addtabularrulecolors` Adds a cell's rule color styles, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```
9111 \newcommand*{\LWR@addtabularrulecolors}{%
```

Custom horizontal rule color:

```
9112 \LWR@addtabularhrulecolor%
```

No vertical rules if finishing the tabular with a row of empty cells:

```
9113 \ifbool{\LWR@tabularmutemods}{}{%
```

If at the leftmost cell, possibly add a leftmost vertical rule:

```
9114 \ifnumequal{\value{\LWR@tableLaTeXcolindex}}{1}{%
```

Fetch the left edge's vertical bar specification:

```
9115 \edef\LWR@tempone{\LWR@getexparray{\LWR@colbarspec}{Leftedge}}%
```

Add a custom style if a vertical bar was requested:

```

9116 \ifdefstring{\LWR@tempone}{tvertbarl}{%
9117 \LWR@tdaddstyle%
9118 border-left: 1px solid % space
9119 \LWR@vertruleHTMLcolor%
9120 }{%
9121 \ifdefstring{\LWR@tempone}{tvertbarldouble}{%
9122 \LWR@tdaddstyle%
9123 border-left: 4px double % space
9124 \LWR@vertruleHTMLcolor%
9125 }{%
9126 \ifdefstring{\LWR@tempone}{tvertbarldash}{%
9127 \LWR@tdaddstyle%
9128 border-left: 1px dashed % space
9129 \LWR@vertruleHTMLcolor%
9130 }{%
9131 \ifdefstring{\LWR@tempone}{tvertbarldoubledash}{%
9132 \LWR@tdaddstyle%
9133 border-left: 2px dashed % space

```

```

9134 \LWR@vertruleHTMLcolor%
9135 }{}%
9136 }{}%

```

Possibly add a right vertical rule for this cell:

```

9137 \edef\LWR@tempone{%
9138 \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tableLaTeXcolindex}}%
9139 }%
9140 \ifdefstring{\LWR@tempone}{tvertbarr}{%

```

Add a custom style if a vertical bar was requested:

```

9141 \LWR@daddstyle%
9142 border-right: 1px solid \LWR@vertruleHTMLcolor%
9143 }{}%
9144 \ifdefstring{\LWR@tempone}{tvertbarrdouble}{%
9145 \LWR@daddstyle%
9146 border-right: 4px double \LWR@vertruleHTMLcolor%
9147 }{}%
9148 \ifdefstring{\LWR@tempone}{tvertbarrdash}{%
9149 \LWR@daddstyle%
9150 border-right: 1px dashed \LWR@vertruleHTMLcolor%
9151 }{}%
9152 \ifdefstring{\LWR@tempone}{tvertbarrdoubledash}{%
9153 \LWR@daddstyle%
9154 border-right: 2px dashed \LWR@vertruleHTMLcolor%
9155 }{}%
9156 }%
9157 }

```

`\LWR@subaddtabularcellcolor` {*(HTML color)*}

```

9158 \newcommand*{\LWR@subaddtabularcellcolor}[1]{%
9159 \LWR@htmltag{div class="cellcolor" style="
9160 background:\LWR@origpound{}}{#1 %
9161 " }%
9162 \defaddtocounter{LWR@cellcolordepth}{1}%
9163 }

```

`\LWR@addtabularcellcolor` Adds a cell color style, if needed.

```

9164 \newcommand*{\LWR@addtabularcellcolor}{%
9165 \ifdefvoid{\LWR@cellHTMLcolor}%
9166 {%
9167 \ifdefvoid{\LWR@rowHTMLcolor}%
9168 {%
9169 \ifdefvoid{\LWR@xcolorrowHTMLcolor}%
9170 {%
9171 \ifdefvoid{\LWR@columnHTMLcolor}%
9172 {}%
9173 {\LWR@subaddtabularcellcolor{\LWR@columnHTMLcolor}}%
9174 }%
9175 {\LWR@subaddtabularcellcolor{\LWR@xcolorrowHTMLcolor}}%

```

```

9176 }%
9177 {\LWR@subadddtabularcellcolor{\LWR@rowHTMLcolor}}%
9178 }%
9179 {\LWR@subadddtabularcellcolor{\LWR@cellHTMLcolor}}%
9180 }

```

## 73.23 Multicolumns

### 73.23.1 Parsing multicolumns

`\LWR@printmccoltype` `{<colspec>}` Print any valid column type found. Does not print @, !, >, or < columns or their associated tokens.

This is printed as part of the table data tag's class.

```

9181 \newcommand*{\LWR@printmccoltype}[1]{%
9182 \LWR@traceinfo{lw@printmccoltype -#1-}%

```

Get one token of the column spec:

```

9183 \StrChar{#1}{\arabic{\LWR@tablemulticolspos}}[\LWR@strresult]%

```

Add to the HTML tag depending on which column type is found:

```

9184 \IfStrEq{\LWR@strresult}{l}{l}{}%
9185 \IfStrEq{\LWR@strresult}{c}{c}{}%
9186 \IfStrEq{\LWR@strresult}{r}{r}{}%
9187 \IfStrEq{\LWR@strresult}{p}{p}{}%
9188 \IfStrEq{\LWR@strresult}{m}{m}{}%
9189 \IfStrEq{\LWR@strresult}{b}{b}{}%
9190 \IfStrEq{\LWR@strresult}{P}{P}{}%
9191 \IfStrEq{\LWR@strresult}{M}{M}{}%
9192 \IfStrEq{\LWR@strresult}{B}{B}{}%

9193 \IfStrEq{\LWR@strresult}{w}{w}{}%
9194 \IfStrEq{\LWR@strresult}{W}{W}{}%

9195 \IfStrEq{\LWR@strresult}{S}{c}{}%
9196 \IfStrEq{\LWR@strresult}{s}{c}{}%

9197 \IfStrEq{\LWR@strresult}{X}{p}{}%

9198 \IfStrEq{\LWR@strresult}{|}{|}%
9199 {%
9200 \ifbool{\LWR@mcolvertbaronleft}%
9201 {\defaddtocounter{\LWR@mcolvertbarsl}{1}}% left edge
9202 {\defaddtocounter{\LWR@mcolvertbarsr}{1}}% not left edge
9203 }%
9204 {%
9205 \IfStrEq{\LWR@strresult}{:}{:}%
9206 }%

```

```

9207 \ifbool{LWR@mcolvertbaronleft}%
9208 {\defaddtocounter{LWR@mcolvertbarsldash}{1}}% left edge
9209 {\defaddtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
9210 }%
9211 {%
9212 \IfStrEq{\LWR@strresult}{;}%
9213 {%
9214 \ifbool{LWR@mcolvertbaronleft}%
9215 {\defaddtocounter{LWR@mcolvertbarsldash}{1}}% left edge
9216 {\defaddtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
9217 }%
9218 {\boolfalse{LWR@mcolvertbaronleft}}%
9219 }%
9220 }%
9221 \LWR@traceinfo{lwr@printmccoltype done}%
9222 }

```

`\LWR@multicolpartext`  $\langle num\ parameters \rangle$  Print the data with paragraph tags, advance to bypass the given number of parameters.

```

9223 \newcommand*{\LWR@multicolpartext}[1]{%
9224 \LWR@startpars%
9225 \LWR@multicoltext%
9226 \defaddtocounter{LWR@tablemulticolspos}{#1}%
9227 \LWR@stoppars%
9228 }

```

`\LWR@multicolother`  $\langle colspec \rangle$  For @, !, >, <, print the next token without paragraph tags:

```

9229 \newcommand*{\LWR@multicolother}[1]{%
9230 \defaddtocounter{LWR@tablemulticolspos}{1}%
9231 \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
9232 \LWR@strresult%

```

A valid column data type was found:

```

9233 \booltrue{LWR@validtablecol}%
9234 }

```

`\LWR@multicolskip` Nothing to print for this column type.

```

9235 \newcommand*{\LWR@multicolskip}{%

```

A valid column data type was found:

```

9236 \booltrue{LWR@validtablecol}%
9237 }

```

`\LWR@printmccoldata`  $\langle colspec \rangle$  Print the data for any valid column type found.

```

9238 \newcommand*{\LWR@printmccoldata}[1]{%
9239 \LWR@traceinfo{lwr@printmccoldata -#1}%

```

Not yet found a valid column type:

```
9240 \boolfalse{LWR@validtablecol}%
```

Get one token of the column spec, into a local copy in case nested.

```
9241 \StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
9242 \edef\LWR@printmccoldataatoken{\LWR@strresult}%
```

Print the text depending on which column type is found. Also handles @, >, < as it comes to them.

```
9243 \IfStrEq{\LWR@printmccoldataatoken}{l}{\LWR@multicoltext}{}%
9244 \IfStrEq{\LWR@printmccoldataatoken}{c}{\LWR@multicoltext}{}%
9245 \IfStrEq{\LWR@printmccoldataatoken}{r}{\LWR@multicoltext}{}%
9246 \IfStrEq{\LWR@printmccoldataatoken}{D}{}%
9247 \defaddtocounter{LWR@tablemulticolspos}{3}% skip parameters
9248 \LWR@multicoltext%
9249 }{}%

9250 \IfStrEq{\LWR@printmccoldataatoken}{p}{\LWR@multicolpartext{2}}{}%
9251 \IfStrEq{\LWR@printmccoldataatoken}{m}{\LWR@multicolpartext{2}}{}%
9252 \IfStrEq{\LWR@printmccoldataatoken}{b}{\LWR@multicolpartext{2}}{}%
9253 \IfStrEq{\LWR@printmccoldataatoken}{P}{\LWR@multicolpartext{2}}{}%
9254 \IfStrEq{\LWR@printmccoldataatoken}{M}{\LWR@multicolpartext{2}}{}%
9255 \IfStrEq{\LWR@printmccoldataatoken}{B}{\LWR@multicolpartext{2}}{}%

9256 \IfStrEq{\LWR@printmccoldataatoken}{w}{\LWR@multicolpartext{3}}{}%
9257 \IfStrEq{\LWR@printmccoldataatoken}{W}{\LWR@multicolpartext{3}}{}%

9258 \IfStrEq{\LWR@printmccoldataatoken}{S}{\LWR@multicoltext}{}%
9259 \IfStrEq{\LWR@printmccoldataatoken}{s}{\LWR@multicoltext}{}%

9260 \IfStrEq{\LWR@printmccoldataatoken}{X}{\LWR@multicolpartext{1}}{}%
9261 \IfStrEq{\LWR@printmccoldataatoken}{|}{\LWR@multicolskip}{}%
9262 \IfStrEq{\LWR@printmccoldataatoken}{:}{\LWR@multicolskip}{}%
9263 \IfStrEq{\LWR@printmccoldataatoken}{;}{;%
9264 \LWR@multicolskip%
9265 \defaddtocounter{LWR@tablemulticolspos}{1}% skip parameter
9266 }{}%
9267 \IfStrEq{\LWR@printmccoldataatoken}{\detokenize{@}}{\LWR@multicolother{#1}}{}%
9268 \IfStrEq{\LWR@printmccoldataatoken}{\detokenize{!}}{\LWR@multicolother{#1}}{}%
9269 \IfStrEq{\LWR@printmccoldataatoken}{\detokenize{>}}{\LWR@multicolother{#1}}{}%
9270 \IfStrEq{\LWR@printmccoldataatoken}{\detokenize{<}}{\LWR@multicolother{#1}}{}
```

If an invalid column type:

```
9271 \ifbool{LWR@validtablecol}{\LWR@multicoltext}{}
```

Tracing:

```
9272 \LWR@traceinfo{lwarp@printmccoldata done}%
9273 }
```

```
\parsemulticolumnalignment {<1: colspec>} {<2: printresults>}
```

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a p{spec} column, or @, >, <, is a token list which will NOT match l, c, r, or p.

```
9274 \newcommand*{\LWR@parsemulticolumnalignment}[2]{%
9275 \defcounter{\LWR@tablemulticolspos}{1}%
9276 \StrLen{#1}[\LWR@strresult]%
9277 \defcounter{\LWR@tablemulticolwidth}{\LWR@strresult}%
```

Scan across the tokens in the column spec:

```
9278 \whileboolexpr{%
9279 not test {%
9280 \ifnumcomp{\value{\LWR@tablemulticolspos}}{>}%
9281 {\value{\LWR@tablemulticolwidth}}%
9282 }%
9283 }%
9284 {%
```

Execute the assigned print function for each token in the column spec:

```
9285 #2{#1}%
```

Move to the next token in the column spec:

```
9286 \defaddtocounter{\LWR@tablemulticolspos}{1}%
9287 }%
9288 }
```

### 73.23.2 Multicolumn factored code

```
\LWR@addmulticolvertrulecolor
```

```
9289 \newcommand*{\LWR@addmulticolvertrulecolor}{%
```

No vertical rules if finishing the tabular with a row of empty cells:

```
9290 \ifbool{\LWR@tabularmutemods}{}{}%
```

Left side:

```
9291 \ifnumcomp{\value{\LWR@mcolvertbarsl}}{=}{1}{%
9292 \LWR@tdaddstyle%
9293 border-left: 1px solid \LWR@vertruleHTMLcolor%
9294 }{%
9295 \ifnumcomp{\value{\LWR@mcolvertbarsl}}{>}{1}{%
9296 \LWR@tdaddstyle%
9297 border-left: 4px double \LWR@vertruleHTMLcolor%
9298 }{%
```

```

9299 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{%
9300 \LWR@tdaddstyle%
9301 border-left: 1px dashed \LWR@vertruleHTMLcolor%
9302 }{}%
9303 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
9304 \LWR@tdaddstyle%
9305 border-left: 2px dashed \LWR@vertruleHTMLcolor%
9306 }{}%

```

Right side:

```

9307 \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{%
9308 \LWR@tdaddstyle%
9309 border-right: 1px solid \LWR@vertruleHTMLcolor%
9310 }{}%
9311 \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{%
9312 \LWR@tdaddstyle%
9313 border-right: 4px double \LWR@vertruleHTMLcolor%
9314 }{}%
9315 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{%
9316 \LWR@tdaddstyle%
9317 border-right: 1px dashed \LWR@vertruleHTMLcolor%
9318 }{}%
9319 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
9320 \LWR@tdaddstyle%
9321 border-right: 2px dashed \LWR@vertruleHTMLcolor%
9322 }{}%
9323 }%
9324 }

```

```
9325 \newcommand{\LWR@multicoltext}{}

```

To find multicolumn right trim:

```
9326 \newcounter{LWR@lastmulticolumn}

```

```
\LWR@domulticolumn [1: vpos] [2: #rows] [3: numLaTeXcols] [4: numHTMLcols] [5: colspec]
[6: text]

```

```

9327 \NewDocumentCommand{\LWR@domulticolumn}{o o m m +m}{%
9328 \LWR@traceinfo{\LWR@domulticolumn -#1- -#2- -#4- -#5-}%

```

Remember the text to be inserted, and remember that a valid column type was found:

```

9329 \renewcommand{\LWR@multicoltext}{%
9330 #6%
9331 \booltrue{LWR@validtablecol}%
9332 }%

```

Compute the rightmost column to be included. This is used to create the right trim.

```

9333 \defcounter{LWR@lastmulticolumn}{\value{LWR@tableLaTeXcolindex}}%
9334 \defaddtocounter{LWR@lastmulticolumn}{#3}%
9335 \defaddtocounter{LWR@lastmulticolumn}{-1}%

```

Row processing:

```
9336 \LWR@maybenewtablerow%
```

Begin the opening table data tag:

```
9337 \LWR@htmltag{%
9338 td colspan="#4" %

9339 \IfValueT{#2}{ % rows?
9340 rowspan="#2" %
9341 }%

9342 class="td%
```

Print the column type and vertical bars:

```
9343 \defcounter{LWR@mcolvertbarsl}{0}%
9344 \defcounter{LWR@mcolvertbarsr}{0}%
9345 \defcounter{LWR@mcolvertbarsldash}{0}%
9346 \defcounter{LWR@mcolvertbarsrdash}{0}%
9347 \booltrue{LWR@mcolvertbaronleft}%
9348 \LWR@parsemulticolumnalignment{#5}{\LWR@printmcoltype}%
```

If this column has a `cmidrule`, add “rule” to the end of the HTML class tag.

If this position had a “Y” then add “rule” for a horizontal rule:

```
9349 \LWR@subaddcmidruletrim%
9350 {%
9351 \LWR@getexparray{LWR@trimlrules}%
9352 {\arabic{LWR@tableLaTeXcolindex}}%
9353 }%
9354 {%
9355 \LWR@getexparray{LWR@trimrrules}%
9356 {\arabic{LWR@lastmulticolumn}}%
9357 }%
```

Also add vertical bar class.

```
9358 \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{ tvertbarl}{}%
9359 \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{ tvertbarldouble}{}%
9360 \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{ tvertbarr}{}%
9361 \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{ tvertbarrdouble}{}%
9362 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{ tvertbarldash}{}%
9363 \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}%
9364 { tvertbarldoubledash}{}%
9365 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{ tvertbarrdash}{}%
9366 \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}%
9367 { tvertbarrdoubledash}{}%
```

Close the class tag’s opening quote:

```
9368 "%
```

9369           \LRW@tdstartstyles%

Style for vertical position:

```

9370 \IfValueT{#1}{% vpos?
9371 \ifstrequal{#1}{b}%
9372 {%
9373 \LRW@tdaddstyle%
9374 \LRW@print@mbbox{vertical-align:bottom}%
9375 }{}%
9376 \ifstrequal{#1}{t}%
9377 {%
9378 \LRW@tdaddstyle%
9379 \LRW@print@mbbox{vertical-align:top}%
9380 }{}%
9381 }% vpos?

```

Style for row colors:

9382           \LRW@addtabulararrowcolor%

Other styles:

```

9383 \LRW@addcmidrulewidth%
9384 \LRW@addcdashline%
9385 \LRW@addtabularhrulecolor%
9386 \LRW@addmulticolvertrulecolor%
9387 \LRW@addformatwppalignment{#5}%
9388 \LRW@tdendstyles%
9389 }% end of the opening table data tag
9390 \boolfalse{LRW@intabularmetadata}%
9391 \LRW@parsemulticolumnalignment{#5}{\LRW@printmccoldata}%
9392 }

```

### 73.23.3 Multicolumn

`\LRW@htmlmulticolumn` {<numcols>} {<alignment>} {<text>}

```

9393 \NewDocumentCommand{\LRW@htmlmulticolumn}{m m +m}%
9394 {%

```

Figure out how many extra HTML columns to add for @ and ! columns:

```

9395 \LRW@tabularhtmlcolumns{\arabic{LRW@tableLaTeXcolindex}}{#1}%

```

Create the multicolumn tag:

```

9396 \LRW@domulticolumn{#1}{\arabic{LRW@tabhtmlcoltotal}}{#2}{#3}%

```

Move to the next L<sup>A</sup>T<sub>E</sub>X column:

```

9397 \defaddtocounter{LRW@tableLaTeXcolindex}{#1}%
9398 \defaddtocounter{LRW@tableLaTeXcolindex}{-1}%

```

Skip any trailing @ or ! columns for this cell:

```
9399 \booltrue{LWR@skipatbang}%
9400 }
```

### 73.23.4 Longtable captions

longtable captions use \multicolumn.

Per the caption package. User-redefinable float type.

```
9401 \providecommand*{\LTcaptype}{table}
```

```
\LWR@longtabledatacaptiontag * [toc entry] {caption}
```

```
9402 \NewDocumentCommand{\LWR@longtabledatacaptiontag}{s o +m}
9403 {%
```

Remember the latest name for \nameref:

```
9404 \IfValueTF{#2}{% optional given?
9405 \ifblank{#2}% optional empty?
9406 {\LWR@setlatestname{#3}}% empty
9407 {\LWR@setlatestname{#2}}% given and non-empty
9408 }% optional given
9409 {\LWR@setlatestname{#3}}% no optional
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for @ and ! columns found between the first and the last column:

```
9410 \LWR@tabularhtmlcolumns{1}{\arabic{LWR@tabletotalLaTeXcols}}%
```

Create the multicolumn tag:

```
9411 \LWR@domulticolumn{\arabic{LWR@tabletotalLaTeXcols}}%
9412 {\arabic{LWR@tabhtmlcoltotal}}%
9413 {P}%
9414 {% \LWR@domulticolumn
9415 \IfBooleanTF{#1}% star?
```

Star version, show a caption but do not make a LOT entry:

```
9416 {% yes star
9417 \LWR@figcaption%
9418 \LWR@isolate{#3}%
9419 \endLWR@figcaption%
9420 }%
9421 {% No star:
```

Not the star version:

Don't step the counter if `\caption[]`{A caption.}

```

9422 \ifbool{LWR@starredlongtable}%
9423 {%
9424 \ifblank{#2}% TOC entry
9425 {}%
9426 {%
9427 \refstepcounter{\LTcaption}%
9428 \protected@edef\@currentlabel{%
9429 \@nameuse{p@\LTcaption}\@nameuse{the\LTcaption}%
9430 }%
9431 }%
9432 }{}%
```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```

9433 \LWR@figcaption%
9434 \LWR@isolate{\@nameuse{fnum@\LTcaption}}%
9435 \CaptionSeparator%
9436 \LWR@isolate{#3}%
9437 \endLWR@figcaption%
```

See if an optional caption was given:

```

9438 \ifblank{#2}% TOC entry empty
```

if the optional caption was given, but empty, do not form a TOC entry

```

9439 {}%
```

If the optional caption was given, but might only be []:

```

9440 {% TOC entry not empty
9441 \IfNoValueTF{#2}% No TOC entry?
```

The optional caption is []:

```

9442 {% No TOC entry
9443 \addcontentsline%
9444 {\@nameuse{ext@\LTcaption}}%
9445 {\LTcaption}%
9446 {%
9447 \protect\numberline%
9448 {\LWR@isolate{\@nameuse{p@\LTcaption}}\@nameuse{the\LTcaption}}%
9449 {\ignorespaces \LWR@isolate{#3}\protect\relax}%
9450 }%
9451 }% end of No TOC entry
```

The optional caption has text enclosed:

```

9452 {% yes TOC entry
9453 \addcontentsline%
```

```

9454 {\@nameuse{ext\LTcapttype}}%
9455 {\LTcapttype}%
9456 {%
9457 \protect\numberline%
9458 {\LWR@isolate{\@nameuse{p\LTcapttype}}\@nameuse{the\LTcapttype}}%
9459 {\ignorespaces \LWR@isolate{#2}\protect\relax}%
9460 }%
9461 }% end of yes TOC entry
9462 }% end of TOC entry not empty
9463 }% end of no star

```

Skip any trailing @ or ! columns for this cell:

```

9464 \booltrue{LWR@skipatbang}%
9465 }% end of \LWR@domulticolumn
9466 \defaddtocounter{LWR@tableLaTeXcolindex}{\value{LWR@tabletotalLaTeXcols}}%
9467 \defaddtocounter{LWR@tableLaTeXcolindex}{-1}
9468
9469 }

```

### 73.23.5 Counting HTML tabular columns

The L<sup>A</sup>T<sub>E</sub>X specification for a table includes a number of columns separated by the & character. These columns differ in content from line to line. Additional virtual columns may be specified by the special @ and ! columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, @ and ! columns are placed into their own tabular columns. Thus, a L<sup>A</sup>T<sub>E</sub>X \multicolumn command may span several additional @ and ! columns in HTML output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```

9470 \newcounter{LWR@tabhtmlcolindex}
9471 \newcounter{LWR@tabhtmlcolend}
9472 \newcounter{LWR@tabhtmlcoltotal}

```

\LWR@subtabularhtmlcolumns {<*index*>}

Factored from \LWR@tabularhtmlcolumns, which follows.

```

9473 \newcommand*{\LWR@subtabularhtmlcolumns}[1]{%

```

Temporarily define a macro equal to the @ specification for this column:

```

9474 \edef\LWR@atbangspec{\LWR@getexparray{LWR@colatspec}{#1}}%

```

If the @ specification is not empty, add to the count:

```

9475 \ifdefempty{\LWR@atbangspec}%
9476 {}%
9477 {\defaddtocounter{LWR@tabhtmlcoltotal}{1}}%

```

Likewise for the ! columns:

```

9478 \edef\LWR@atbangspec{\LWR@getexparray{\LWR@colbangspec}{#1}}%
9479 \ifdefempty{\LWR@atbangspec}%
9480 {}%
9481 {\defaddtocounter{\LWR@tabhtmlcoltotal}{1}}%
9482 }

```

```
\LWR@tabularhtmlcolumns {<starting LATEX column>} {<number LATEX columns>}
```

Compute the total number of HTML columns being spanned, considering the starting L<sup>A</sup>T<sub>E</sub>X table column and the number of L<sup>A</sup>T<sub>E</sub>X tabular columns being spanned. Any @ and ! columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter LWR@tabhtmlcoltotal.

```
9483 \newcommand*{\LWR@tabularhtmlcolumns}[2]{%
```

Count the starting index, compute ending index, and begin with the count being the L<sup>A</sup>T<sub>E</sub>X span, to which additional @ and ! columns may be added:

```

9484 \defcounter{\LWR@tabhtmlcolindex}{#1}%
9485 \defcounter{\LWR@tabhtmlcoltotal}{#2}%
9486 \defcounter{\LWR@tabhtmlcolend}{#1}%
9487 \defaddtocounter{\LWR@tabhtmlcolend}{#2}%

```

If at the left edge, add the at/bang columns for the left edge:

```

9488 \ifnumcomp{\value{\LWR@tabhtmlcolindex}}{=}{1}{}%
9489 \LWR@subtabularhtmlcolumns{leftedge}%
9490 }{}%

```

Walk across the L<sup>A</sup>T<sub>E</sub>X columns looking for @ and ! columns:

```

9491 \whileboolexpr{%
9492 test {%
9493 \ifnumcomp{\value{\LWR@tabhtmlcolindex}}{<}{\value{\LWR@tabhtmlcolend}}%
9494 }%
9495 }%
9496 {%
9497 \LWR@subtabularhtmlcolumns{\arabic{\LWR@tabhtmlcolindex}}%
9498 \defaddtocounter{\LWR@tabhtmlcolindex}{1}}%
9499 }% whiledo
9500 }

```

```
9501 \end{warpHTML}
```

## 73.24 Multirow if not loaded

A default definition in case multirow is not loaded. This is used during table parsing.

```

9502 \begin{warpHTML}
9503 \newcommand{\multirow}[2][c]{}
9504 \end{warpHTML}

```

### 73.25 Multicolumnrow

A print-mode version is defined here, and is also used during HTML output while inside a lateximage.

See section 405 for the HTML versions.

**for HTML & PRINT:** 9505 \begin{warpall}

```
\multicolumnrow {<1:cols>}{<2:halign>} [<3:vpos>] {<4:numrows>} [<5:bigstruts>] {<6:width>} [<7:fixup>]
{<8:text>}
```

For discussion of the use of \DeclareExpandableDocumentCommand, see:  
<https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex>

\AtBeginDocument to adjust after the user may have loaded multirow, which requires several tests to determine which version is loaded and thus which options are available.

```
9506 \AtBeginDocument{
```

\@ifundefined{@xmultirow} determines if multirow was never loaded.

Null action if not loaded:

```
9507 \@ifundefined{@xmultirow}
9508 {
9509 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
9510 {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
9511 {}%
9512 }% no version of multirow was loaded
9513 {% \@xmultirow defined, so some version of multirow was loaded
```

\@ifpackageloaded{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The print version:

```
9514 \@ifpackageloaded{multirow}{% v2.0 or newer
9515 \@ifpackagelater{multirow}{2016/09/01}% 2016/09/27 for v2.0
9516 {% v2.0+:
9517 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
9518 {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
9519 {\multicolumn{#1}{#2}{\@xmultirow[#3][#4][#5][#6][#7][#8]}}%
9520 }
9521 {% loaded but older, probably not executed:
9522 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
9523 {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
9524 {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5][#6][#7][#8]}}%
9525 }
9526 }% packageloaded{multirow}
```

If not `\ifpackageloaded{multirow}` but `\xmultirow` is defined, then this must be v1.6 or earlier, which did not `\ProvidesPackage{multirow}`, and did not have the `vposn` option.

```

9527 {% v1.6 or older did not \ProvidePackage
9528 \DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
9529 {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
9530 {\multicolumn{#1}{#2}{\xmultirow{#4}[#5][#6][#7][#8]}}%
9531 }
9532
9533 {% \ifundefined{@xmultirow}
9534
9535 \providecommand*{\multicolumnrow}{\LWR@print@multicolumnrow}
9536
9537 }% AtBeginDocument

9538 \end{warpall}

```

### 73.26 Utility macros inside a table

**for HTML output:** 9539 `\begin{warpHTML}`

Used to prevent opening a tabular data cell if the following token is one which does not create tabular data:

```
9540 \newcommand*{\LWR@donothing}{}

```

In case `array` is not loaded:

```

9541 \let\firstline\relax
9542 \let\lastline\relax
9543 \newcommand*{\firstline}{}
9544 \newcommand*{\lastline}{}

```

In case `bigdelim` is not loaded:

```

9545 \newcommand*{\ldelim}{}
9546 \newcommand*{\rdelim}{}

```

```
9547 \end{warpHTML}

```

### 73.27 Special-case tabular markers

**for HTML & PRINT:** 9548 `\begin{warpall}`

`\TabularMacro` Place this just before inserting a custom macro in a table data cell. Doing so tells `lwarp` not to automatically start a new HTML table data cell yet. See section [8.10.1](#).

```
9549 \newcommand*{\TabularMacro}{}

```

```
9550 \end{warpall}
```

`\ResumeTabular` Used to resume tabular entries after resuming an environment.

⚠ **tabular inside another environment** When creating a new environment which contains a tabular environment, `lwarp`'s emulation of the tabular does not automatically resume when the containing environment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars % (& is used in a definition)
\newenvironment{outerenvironment}
{
 \tabular{cc}
 left & right \\
}
{
 \TabularMacro\ResumeTabular
 left & right \\
 \endtabular
}
\StopDefiningTabulars
```

**for HTML output:** 9551 \begin{warpHTML}

```
9552 \newcommand*{\ResumeTabular}{%
9553 \boolfalse{LWR@exitingtabular}%
9554 \boolfalse{LWR@tabularmutemods}%
9555 \LWR@getmynexttoken%
9556 }
```

```
9557 \end{warpHTML}
```

**for PRINT output:** 9558 \begin{warpprint}

```
9559 \newcommand*{\ResumeTabular}{}
9560 \end{warpprint}
```

## 73.28 Checking for a new table cell

**for HTML output:** 9561 \begin{warpHTML}

`\LWR@tabledatacolumnntag` Open a new HTML table cell unless the next token is for a macro which does not create data, such as `\hline`, `\toprule`, etc:

```
9562 \newcommand*{\LWR@tabledatacolumnntag}%
9563 {%
9564 \LWR@traceinfo{\LWR@tabledatacolumnntag}%
```

`\show\LWR@mynexttoken` to see what tokens to look for

If not any of the below, start a new table cell:

```
9565 \global\let\LWR@mynextaction\LWR@tabledatasinglecolumn%tag%
```

If exiting the tabular:

```
9566 \ifdefequal{\LWR@mynexttoken}{\end}%
9567 {\booltrue{LWR@exitingtabular}}{}
```

longtable can have a caption in a cell

```
9568 \ifdefequal{\LWR@mynexttoken}{\caption}%
9569 {\global\let\LWR@mynextaction\LWR@donothing}}{}
```

Look for other things which would not start a table cell:

```
9570 \ifdefequal{\LWR@mynexttoken}{\multicolumn}%
9571 {\global\let\LWR@mynextaction\LWR@donothing}}{}%
9572 \ifdefequal{\LWR@mynexttoken}{\multirow}%
9573 {\global\let\LWR@mynextaction\LWR@donothing}}{}%
9574 \ifdefequal{\LWR@mynexttoken}{\multicolumnrow}%
9575 {\global\let\LWR@mynextaction\LWR@donothing}}{}%
9576 \ifdefequal{\LWR@mynexttoken}{\noalign}%
9577 {\global\let\LWR@mynextaction\LWR@donothing}}{}
```

If an `\mrowcell`, this is a cell to be skipped over:

```
9578 \ifdefequal{\LWR@mynexttoken}{\mrowcell}%
9579 {\global\let\LWR@mynextaction\LWR@donothing}}{}
```

If an `\mcolrowcell`, this is a cell to be skipped over:

```
9580 \ifdefequal{\LWR@mynexttoken}{\mcolrowcell}%
9581 {\global\let\LWR@mynextaction\LWR@donothing}}{}
```

```
9582 \ifdefequal{\LWR@mynexttoken}{\TabularMacro}%
9583 {\global\let\LWR@mynextaction\LWR@donothing}}{}
```

```
9584 \ifdefequal{\LWR@mynexttoken}{\hline}%
9585 {\global\let\LWR@mynextaction\LWR@donothing}}{}
```

```
9586 \ifdefequal{\LWR@mynexttoken}{\firstline}%
9587 {\global\let\LWR@mynextaction\LWR@donothing}}{}
```

```
9588 \ifdefequal{\LWR@mynexttoken}{\lastline}%
9589 {\global\let\LWR@mynextaction\LWR@donothing}}{}
```

```
9590 \ifdefequal{\LWR@mynexttoken}{\toprule}%
9591 {\global\let\LWR@mynextaction\LWR@donothing}}{}
```

```

9592 \ifdefequal{\LWR@mynexttoken}{\midrule}%
9593 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9594 \ifdefequal{\LWR@mynexttoken}{\cmidrule}%
9595 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9596 \ifdefequal{\LWR@mynexttoken}{\morecmidrules}%
9597 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9598 \ifdefequal{\LWR@mynexttoken}{\specialrule}%
9599 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9600 \ifdefequal{\LWR@mynexttoken}{\cline}%
9601 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9602 \ifdefequal{\LWR@mynexttoken}{\bottomrule}%
9603 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9604 \ifdefequal{\LWR@mynexttoken}{\hhline}%
9605 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9606 \ifdefequal{\LWR@mynexttoken}{\rowcolor}%
9607 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9608 \ifdefequal{\LWR@mynexttoken}{\arrayrulecolor}%
9609 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9610 \ifdefequal{\LWR@mynexttoken}{\doublerulesepcolor}%
9611 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9612 \ifdefequal{\LWR@mynexttoken}{\warpprintonly}%
9613 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9614 \ifdefequal{\LWR@mynexttoken}{\warppHTMLonly}%
9615 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9616 \ifdefequal{\LWR@mynexttoken}{\ldelim}%
9617 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9618 \ifdefequal{\LWR@mynexttoken}{\rdelim}%
9619 {\global\let\LWR@mynextaction\LWR@donothing}{}%

```

For arydshln:

```

9620 \ifdefequal{\LWR@mynexttoken}{\hdashline}%
9621 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9622 \ifdefequal{\LWR@mynexttoken}{\cdashline}%
9623 {\global\let\LWR@mynextaction\LWR@donothing}{}%

9624 \ifdefequal{\LWR@mynexttoken}{\firsthdashline}%
9625 {\global\let\LWR@mynextaction\LWR@donothing}{}%

```

```

9626 \ifdefequal{\LWR@mynexttoken}{\lasthdashline}%
9627 {\global\let\LWR@mynextaction\LWR@doanything}{}%

```

Ignore an empty line between rows:

```

9628 \ifdefequal{\LWR@mynexttoken}{\par}%
9629 {\global\let\LWR@mynextaction\LWR@doanything}{}%

```

No action for an `\end` token.

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```

9630 \LWR@traceinfo{\LWR@tabledatacolumnstag: about to do mynext}%
9631 \LWR@mynextaction%
9632 \LWR@traceinfo{\LWR@tabledatacolumnstag: done}%
9633 }

9634 \end{warpHTML}

```

### 73.29 `\mrowcell`

**for HTML & PRINT:** 9635 `\begin{warpall}`

 **multirow cells** `\mrowcell` The user must insert `\mrowcell` into any `\multirow` cells which must be skipped. This command has no action during print output.

```

9636 \newcommand*{\mrowcell}{}

9637 \end{warpall}

```

### 73.30 `\mcolrowcell`

**for HTML & PRINT:** 9638 `\begin{warpall}`

 **multirow cells** `\mcolrowcell` The user must insert `\mcolrowcell` into any `\multicolumnrow` cells which must be skipped. This command has no action during print output.

```

9639 \newcommand*{\mcolrowcell}{}

9640 \end{warpall}

```

### 73.31 HTML tabular environment

for HTML output: 9641 `\begin{warpHTML}`

These are default definitions in case `booktabs` is not loaded, and are not expected to be used, but must exist as placeholders. `memoir` may have already loaded `booktabs`.

```
9642 \providecommand*\toprule[1][\hline]
9643 \providecommand*\midrule[1][\hline]
9644 \providecommand*\cmidrule{\cline}
9645 \providecommand*\bottomrule[1][\hline]
9646 \providecommand*\addlinespace[1][\]
9647 \providecommand*\morecmidrules{}
9648 \providecommand*\specialrule[3][\hline]
```

`\noalign`  $\{<text>\}$  Redefined for use inside `tabular`.

```
9649 \LetLtxMacro\LWR@orignoalign\noalign
9650
9651 \newcommand{\LWR@tabularnoalign}[1]{%
9652 \advance\rownum\m@ne%
9653 \LetLtxMacro\LWR@save@xcolorrowHTMLcolor\LWR@xcolorrowHTMLcolor%
9654 \renewcommand*\LWR@xcolorrowHTMLcolor{}%
9655 \multicolumn{\value\LWR@tabletotalLaTeXcols}{l}{#1} \ \
9656 \LetLtxMacro\LWR@xcolorrowHTMLcolor\LWR@save@xcolorrowHTMLcolor%
9657 % \@rowcol@lors%
9658 \LWR@getmynexttoken%
9659 }
```

`\LWR@HTMLhline` The definition of `\hline` depends on whether `tabs` has been loaded. If so, optional space below the line may be specified, but will be ignored.

```
9660 \AtBeginDocument{
9661
9662 \ifpackageloaded{lwarp-tabs}
9663 {
9664 \newcommand*\LWR@HTMLhline[1][\]{%
9665 \ifbool{FormatWP}%
9666 {\LWR@docmidrule{1-\arabic\LWR@tabletotalLaTeXcols}}%
9667 {\defaddtocounter\LWR@hlines{1}}%
9668 \LWR@getmynexttoken}%
9669 }
9670 {
9671 \newcommand*\LWR@HTMLhline[1]{%
9672 \ifbool{FormatWP}%
9673 {\LWR@docmidrule{1-\arabic\LWR@tabletotalLaTeXcols}}%
9674 {\defaddtocounter\LWR@hlines{1}}%
9675 \LWR@getmynexttoken}%
9676 }
9677
9678 }% AtBeginDocument
```

`\LWR@HTMLcline` {*<columns>*}

```
9679 \NewDocumentCommand{\LWR@HTMLcline}{m}%
9680 {\LWR@docmidrule{#1}\LWR@getmynexttoken}%
```

`\LWR@tabular@warpprintonly` {*<contents>*}

Only process the contents if producing printed output. Modified inside a `tabular` to grab the next token.

```
9681 \newcommand{\LWR@tabular@warpprintonly}[1]{%
9682 \ifbool{warpingprint}{#1}{}%
9683 \LWR@getmynexttoken%
9684 }
```

`\LWR@nullifyNoAutoSpacing` For `babel-french`, turn off auto spacing at the start of the `tabular`, then nullify the autospacing commands inside the `tabular`, since they were not compatible with the `tabular` column parsing code, which uses `xstring`.

```
9685 \AtBeginDocument{
9686 \ifundefined{NoAutoSpacing}%
9687 {% no babel-french
9688 \newcommand*\LWR@nullifyNoAutoSpacing}{%
9689 }% no babel-french
9690 {% yes babel-french
9691 \newcommand*\LWR@nullifyNoAutoSpacing}{%
9692 \NoAutoSpacing%
9693 \renewcommand*\NoAutoSpacing}{}%
9694 \renewcommand*\LWR@FBcancel}{}%
9695 }
9696 }% yes babel-french
9697 }% AtBeginDocument
```

Env `tabular` *<direction>* [*<verticalposition>*] {*<colspecs>*}

The *<direction>* is from `plext` for Japanese documents, and is ignored.

```
9698 \StartDefiningTabulars
9699
9700 \NewDocumentCommand{\LWR@HTML@tabular}{d<> o m}
9701 {%
9702 \LWR@traceinfo{\LWR@HTML@tabular started}%
```

 **`<table>` inside `<span>`** In `LATEX`, a `tabular` may be placed inside a `minipage`, but in `HTML` a `<table>` may not be inside a `<span>`. Since there may be several nested `<span>`s, with an unknown number of other objects between, it is hard to undo all these `<span>`s before the `<table>` then redo them after. The browser probably compensates for this situation, but formatting may be lost inside the `<table>` because several things are neutralized inside a `<span>`. Furthermore, in the `HTML` output, the entire `<table>` is placed on a single line of `HTML` code, since the line breaking commands are neutralized inside a `<span>`. Since this is such a sloppy situation, a warning is issued here instructing the user to please isolate the `<span>` to print-only.

```
9703 \LWR@spanwarnformat{tabular}%
9704 \addtocounter{LWR@tabulardepth}{1}%
```

Not yet started a table row:

```
9705 \boolfalse{LWR@startedrow}%
```

Not yet doing any rules:

```
9706 \defcounter{LWR@hlines}{0}%
9707 \defcounter{LWR@hdashedlines}{0}%
9708 \boolfalse{LWR@doingtbrule}%
9709 \boolfalse{LWR@doingcmidrule}%
```

For babel-french, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the tabular parsing code.

```
9710 \LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of tabular command. Unmute the @ and ! columns.

```
9711 \boolfalse{LWR@exitingtabular}%
9712 \boolfalse{LWR@tabularmutemods}%
```

Error if failed to use \mrowcell or \mcolrowcell when needed.

```
9713 \boolfalse{LWR@usedmultirow}%
9714 \boolfalse{LWR@foundmrowcell}%

9715 \renewcommand*{\LWR@multicoltext}{}%
```

Create the table tag:

```
9716 \booltrue{LWR@intabularmetadata}%
9717 \LWR@traceinfo{LWR@tabular: About to LWR@forecnewpage.}%
9718 \LWR@forcenewpage
9719 \LWR@htmlblocktag{table}%
```

Parse the table columns:

```
9720 \LWR@parsetablecols{#3}%
```

Table col spec is: \LWR@tablecolspec which is a string of llccrr, etc.

Do not place the table inside a paragraph:

```
9721 \LWR@stoppars%
```

Track column #:

```
9722 \defcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
9723 \global\boolfalse{LWR@tabularcelladded}%
```

Start looking for midrules:

```
9724 \LWR@clearmidrules%
```

`\` becomes a macro to end the table row:

```
9725 \LetLtxMacro{\}{LWR@tabularendofline}%
```

`\warpprintonly` inside a tabular must grab the next token.

```
9726 \LetLtxMacro\warpprintonly\LWR@tabular@warpprintonly%
```

The following adjust for `colortbl`.

```
9727 \LetLtxMacro\arrayrulecolor\arrayrulecolornexttoken%
9728 \LetLtxMacro\doublerulesepcolor\doublerulesepcolornexttoken%
9729 \def\LWR@columnHTMLcolor{}%
9730 \def\LWR@rowHTMLcolor{}%
9731 \def\LWR@cellHTMLcolor{}%
9732 \@rowcolors%
```

The vertical rules are set to the color active at the start of the tabular. `\arrayrulecolor` will then affect horizontal rules inside the tabular, but not the vertical rules.

```
9733 \ifdefined\LWR@ruleHTMLcolor}%
9734 {\edef\LWR@vertruleHTMLcolor{black}}%
9735 {\edef\LWR@vertruleHTMLcolor{\LWR@origpound\LWR@ruleHTMLcolor}}%
```

Tracking the depth of cell color `<div>s`:

```
9736 \defcounter{LWR@cellcolordepth}{0}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with `\LWR@getmynexttoken` to see if the next token might create a new data cell:

The optional parameter for `\hline` supports the `tabs` package.

```
9737 \LWR@traceinfo{LWR@@HTML@tabular: redefining macros}%
9738 \LetLtxMacro\noalign\LWR@tabularnoalign%
9739 \LetLtxMacro\hline\LWR@HTMLhline%
9740 \LetLtxMacro\cline\LWR@HTMLcline%

9741 \DeclareDocumentCommand{\hdashline}{o}{%
9742 \ifbool{FormatWP}%
9743 {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
9744 {\defaddtocounter{LWR@hdashedlines}{1}}%
9745 \LWR@getmynexttoken%
9746 }%
```

```

9747 \DeclareDocumentCommand{\cdashline}{m}{%
9748 \LWR@docdashline{##1}\LWR@getmynexttoken%
9749 }%

9750 \DeclareDocumentCommand{\firsthdashline}{o}{%
9751 \ifbool{FormatWP}%
9752 {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
9753 {\defaddtocounter{LWR@hdashedlines}{1}}}%
9754 \LWR@getmynexttoken%
9755 }%

9756 \DeclareDocumentCommand{\lasthdashline}{o}{%
9757 \ifbool{FormatWP}%
9758 {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
9759 {\defaddtocounter{LWR@hdashedlines}{1}}}%
9760 \LWR@getmynexttoken%
9761 }%

```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use `\LWR@getmynexttoken`.

```

9762 \renewcommand{\multicolumn}{\LWR@htmlmulticolumn}%
9763 \renewcommand*{\mrowcell}{%
9764 \LWR@maybenewtablerow%
9765 \LWR@tabularLeftedge%
9766 \booltrue{LWR@skippingmrowcell}%
9767 \booltrue{LWR@foundmrowcell}%
9768 }%
9769 \renewcommand*{\mcolrowcell}{%
9770 \LWR@maybenewtablerow%
9771 \booltrue{LWR@skippingmcolrowcell}%
9772 \booltrue{LWR@foundmrowcell}%
9773 }%
9774 \LetLtxMacro\caption\LWR@longtabledatacaptiontag%

```

Reset for new processing:

```

9775 \boolfalse{LWR@tableparcell}%
9776 \boolfalse{LWR@skippingmrowcell}%
9777 \boolfalse{LWR@skippingmcolrowcell}%
9778 \boolfalse{LWR@skipatbang}%
9779 \boolfalse{LWR@emptyatbang}%

```

Set & for its special meaning inside the tabular:

```

9780 \StartDefiningTabulars%
9781 \protected\gdef&{\LWR@tabularampersand}%

```

Locally force any minipages to be fullwidth, until the end of the tabular:

```

9782 \booltrue{LWR@forceminipagefullwidth}%

```

Nest one level deeper of tabular paragraph handling:

```
9783 \addtocounter{LWR@tabularpardepth}{1}%
```

Look ahead for a possible table data cell:

```
9784 \LWR@traceinfo{LWR@@HTML@tabular: about to LWR@getmynexttoken}%
9785 \LWR@getmynexttoken%
9786 }%
```

Ending the environment:

```
9787 \newcommand*{\LWR@HTML@endtabular}
9788 {%
9789 \LWR@traceinfo{LWR@HTML@endtabular}%
```

Unnest one level of tabular paragraph handling:

```
9790 \addtocounter{LWR@tabularpardepth}{-1}%
9791 \ifboolexpr{%
9792 test {%
9793 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}%
9794 {\value{LWR@tabletotalLaTeXcols}}
9795 } or %
9796 (%
9797 bool{LWR@intabularmetadata} and%
9798 not bool{LWR@tabularcelladded} and%
9799 test {%
9800 \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}%
9801 {\value{LWR@tabletotalLaTeXcols}}%
9802 }%
9803)%
9804 }%
9805 {%
9806 \LWR@tabularfinishrow%
9807 }%
9808 {%
9809 \LWR@closetabledatacell%
9810 }%
9811 \LWR@htmlblocktag{/tr}%
```

xcolor row color support:

```
9812 \@rowc@lors%

9813 \LWR@htmlblocktag{/table}%
9814 \boolfalse{LWR@intabularmetadata}%
```

Unnest one level of tabular:

```
9815 \addtocounter{LWR@tabulardepth}{-1}%
```

Restore & to its usual meaning:

```
9816 \ifnumequal{\value{LWR@tabulardepth}}{0}{%
9817 \protected\gdef&{\LWR@origampmacro}%
```

```
9818 \StopDefiningTabulars%
9819 }{}%
```

Error if used `\multirow` or `\multicolumnrow` without using `\mrowcell` or `\mcolrowcell`.

```
9820 \ifbool{LWR@usedmultirow}{%
9821 \ifbool{LWR@foundmrowcell}%
9822 {\relax}%
9823 {%
9824 \PackageError{lwarp}%
9825 {%
9826 When using \protect\multirow, \protect\multicolumnrow, \MessageBreak
9827 or the bigdelim package, \MessageBreak
9828 place \protect\mrowcell\space or \protect\mcolrowcell\MessageBreak
9829 in empty cells which are to be skipped.\MessageBreak
9830 See the Lwarp package documentation:\MessageBreak
9831 "Special cases and limitations" -> "Tabular"
9832 }%
9833 }%
9834 See the Lwarp package documentation:\MessageBreak
9835 "Special cases and limitations" -> "Tabular".
9836 }%
9837 }%
9838 }{}%
```

```
9839 \LWR@traceinfo{LWR@HTML@endtabular finished}%
9840 }
9841
9842 \csletcs{LWR@HTML@endtabular*}{LWR@HTML@endtabular}
9843
9844 \StopDefiningTabulars
```

`siunitx` may redefine `tabular`, so set the following later:

```
9845 \AtBeginDocument{
9846 \LetLtxMacro\LWR@origendtabular\endtabular
9847 \csletcs{LWR@origendtabular*}{endtabular*}
9848 \LWR@formatted{@tabular}
9849 \LWR@formatted{endtabular}
9850 \LWR@formatted{endtabular*}
9851 }

9852 \end{warpHTML}
```

## 74 Cross-references

Sectioning commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and `lateximage`

depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
 {<imagedepth>}{<imagenumber>}}
```

Table 14 shows the data structures related to cross-referencing.

**for HTML output:** 9853 \begin{warpHTML}

## 74.1 Setup

`\@currentlabelname` To remember the most recently defined section name, description, or caption, for `\nameref`.

```
9854 \def\@currentlabelname{\linkhomename}%
```

`\LWR@stripperperiod` `{<text>} [(<.>)]`

Removes a trailing period.

```
9855 \def\LWR@stripperperiod#1.\ltx@empty#2\@nil{#1}%
```

`\LWR@setlatestname` `{<object name>}`

Removes `\label`, strips any final period, and remembers the result.

```
9856 \newcommand*\LWR@setlatestname}[1]{%
```

Remove `\label` and other commands from the name, the strip any final period. See `getttitlestring`.

```
9857 \GetTitleStringExpand{#1}%
9858 \edef\@currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
9859 \edef\@currentlabelname{%
9860 \expandafter\LWR@stripperperiod\@currentlabelname%
9861 \ltx@empty.\ltx@empty\@nil%
9862 }%
9863 }
```

## 74.2 New lwarp labels.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and `lateximage` depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
 {<imagedepth>}{<imagenumber>}}
```

Table 14: Cross-referencing data structures

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|
| <b>Original L<sup>A</sup>T<sub>E</sub>X:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | (print and HTML) |
| <p><b>\refstepcounter:</b> Steps the counter and sets \@currentlabel.</p> <p><b>\@currentlabel:</b> \p@&lt;ctr&gt;\the&lt;ctr&gt; Updated by \refstepcounter.</p> <p><b>\label:</b> Writes to the .aux file:<br/> <code>\newlabel{&lt;label&gt;}{\@currentlabel}{\thepage}}</code></p> <p><b>\newlabel:</b> When the .aux file is read, sets \r@&lt;label&gt;.</p> <p><b>\r@&lt;label&gt;:</b> Set to: <code>{\@currentlabel}{\thepage}</code></p> <p><b>\ref:</b> Returns the first part of \r@&lt;label&gt;.</p> <p><b>\pageref:</b> Returns the second part of \r@&lt;label&gt;.</p>                                                                                                                                                                                                                                                                                 |                  |
| <b>Added by lwarp:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | (HTML only)      |
| <p><b>\label:</b> Adds HTML tags (section 74.3), and another .aux entry (section 74.2). If memoir is used, its \@mem@old@label points to lwarp's version, and cleveref patches.</p> <p><b>\newlabel:</b> Unchanged. When the .aux file is read, sets \r@&lt;label&gt;@lwarp.</p> <p><b>\r@&lt;label&gt;@lwarp:</b> Set to <code>{{section_name}{file_name}{depth}{number}}</code>:</p> <p><b>\LWR@nameref:</b> The section name for this label.</p> <p><b>\LWR@htmlfileref:</b> The filename or name for this label.</p> <p><b>\LWR@lateximagedepthref:</b> The lateximagedepth for this label.</p> <p><b>\LWR@lateximagenumberref:</b> The lateximagenumber for this label.</p> <p><b>\nameref:</b> Emulated from hyperref for lwarp. See section 74.4.</p> <p><b>\ref and \nameref:</b> Adds HTML tags. See section 74.4.</p>                                         |                  |
| <b>Added by amsmath:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | (print and HTML) |
| <p><b>\label:</b> Execution is delayed until the math environment is completed.</p> <p><b>\ltx@label:</b> L<sup>A</sup>T<sub>E</sub>X \label, (HTML: patched by lwarp,) later patched by cleveref.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                  |
| <b>Added by cleveref:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | (print and HTML) |
| <p><b>\refstepcounter:</b> Added: sets \cref@currentlabel.</p> <p><b>\cref@currentlabel:</b> (&lt;type&gt;=&lt;ctr&gt; unless an alias is used):<br/> <code>[&lt;type&gt;][\arabic{&lt;ctr&gt;}][&lt;parent ctrs&gt;]{\p@&lt;ctr&gt;\the&lt;ctr&gt;}</code> Also see section 59.4 for use with footnotes.</p> <p><b>\label:</b> Writes to the .aux file:<br/> <code>\newlabel{&lt;label&gt;@cref}{\cref@currentlabel}{\thepage}}</code></p> <p><b>\newlabel:</b> Unchanged. When the .aux file is read, sets \r@&lt;label&gt;@cref.</p> <p><b>\r@&lt;label&gt;@cref:</b> Set to: <code>{\cref@currentlabel}{\thepage}</code></p> <p><b>Utility functions:</b> See \cref@getlabel, \cref@gettype, \cref@getcounter, \cref@getprefix.</p> <p><b>Cross-referencing names:</b> \crefname and \Crefname assign human-readable names for references to this counter type.</p> |                  |
| <b>Additionally patched by lwarp:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | (HTML only)      |
| <p><b>\cref, etc.:</b> Modified for lwarp. See section 194.</p> <p><b>\label inside math:</b> See section 81.7.1.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                  |
| <b>Footnotes:</b> See \noteentry in section 59.4.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                  |

See:

[http://tex.stackexchange.com/questions/57194/  
extract-section-number-from-equation-reference](http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference)

`\LWR@setref`  $\langle args\ list\rangle$   $\langle selector\rangle$   $\langle label\rangle$

`\@setref` without the `\null` (`\hbox`), and without the warning messages. Each caused problems with `lwarp` references. The regular reference will cause the warning.

```
9864 \def\LWR@setref#1#2#3{%
9865 \ifx#1\relax%
9866 ??%
9867 \else%
9868 \expandafter#2#1%
9869 \fi}
```

`\LWR@nameref`  $\langle label\rangle$  Returns the section name for this label:

```
9870 \newcommand*\LWR@nameref}[1]{%
9871 \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@firstoffour{#1}%
9872 }
```

`\LWR@htmlfileref`  $\langle label\rangle$  Returns the file number or name for this label:

```
9873 \newcommand*\LWR@htmlfileref}[1]{%
9874 \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@secondoffour{#1}%
9875 }
```

`\LWR@lateximagedepthref`  $\langle label\rangle$  Returns the `lateximagedepth` for this label:

```
9876 \newcommand*\LWR@lateximagedepthref}[1]{%
9877 \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@thirdoffour{#1}%
9878 }
```

`\LWR@lateximagenumberref`  $\langle label\rangle$  Returns the `lateximagenumber` for this label:

```
9879 \newcommand*\LWR@lateximagenumberref}[1]{%
9880 \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@fourthoffour{#1}%
9881 }
```

`\LWR@write@lwarplabel`  $\langle label\rangle$  Sanitize the name and then creates the label:

```
9882 \newcommand*\LWR@write@lwarplabel}[1]{%
9883 \LWR@traceinfo{\LWR@write@lwarplabel !#1!}%
9884 \LWR@setlatestname{\@currentlabelname}%
9885 \@bsphack%
9886 \protected@write\@auxout{%
9887 {%
9888 \string\newlabel{#1@lwarp}{%
9889 {\@currentlabelname}%
```

```

9890 {%
9891 \ifbool{FileSectionNames}%
9892 {\LWR@thisfilename}%
9893 {\arabic{LWR@htmlfilename}}}%
9894 }%
9895 {\arabic{LWR@lateximagedepth}}%
9896 {\arabic{LWR@lateximagenumber}}}%
9897 }%
9898 }%
9899 \@esphack%
9900 }

```

### 74.3 Labels

`\LWR@label@subcreatetag` Creates the tag from `\LWR@sanitized`.

```

9901 \newcommand*\LWR@label@subcreatetag{%
9902 \LWR@htmltag{a \LWR@print@mbx{id="\LWR@sanitized"}}%
9903 \LWR@htmltag{/a}%
9904 }

```

`\LWR@label@inmathcomment`

```

9905 \newcommand*\LWR@label@inmathcomment{%
9906 \ifbool{mathjax} or (bool{FormatWP} and bool{WPMarkMath}) }%
9907 {%

```

The combined  $\LaTeX$  & HTML label is printed in a `\mbox` field:

```

9908 \mbox{%

```

Shift the label over to the right side of the environment to avoid over-printing the math:

```

9909 \ifdef{\totwidth@}{\ifbool{LWR@amsmultline}{\hspace*{\totwidth@}}}{}%

```

Temporarily end the HTML comment, insert the  $\LaTeX$  & HTML label, then resume the HTML comment. `\@firstofone` is required to remove extra braces introduced by the `amsmath` package.)

```

9910 \LWR@htmlclosecomment%
9911 \LWR@label@subcreatetag%
9912 \LWR@htmlopencomment%
9913 }% mbox
9914 }% mathjax
9915 {%
9916 \LWR@label@subcreatetag%
9917 }%
9918 }

```

`\LWR@label@createtag` `{\langle label \rangle}` Creates an HTML id tag.

Used by `\LWR@new@label` and `\hyperdef`.

`\detokenize` is used to allow underscores in the labels.

```
9919 \newcommand*{\LWR@label@createtag}[1]{%
9920 \LWR@traceinfo{\LWR@label@createtag !#1!}%
```

Create an HTML id tag unless are inside a `lateximage`, since it would appear in the image:

```
9921 \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}%
9922 {}%
9923 {% not lateximage
```

If not doing a `lateximage`, create an HTML ID tag.

```
9924 \LWR@sanitize{#1}%
9925 \ifbool{\LWR@insidemathcomment}%
9926 {% inside HTML math comment
9927 \LWR@label@inmathcomment%
9928 }% inside HTML math comment
9929 {% not inside HTML math comment
9930 \ifbool{\LWR@doingstartpars}%
9931 {% pars allowed
9932 \ifbool{\LWR@doingapar}%
9933 {% par started
9934 \LWR@label@subcreatetag%
9935 }% par started
9936 {% par not started
9937 \LWR@stoppars%
9938 \LWR@label@subcreatetag%
9939 \LWR@startpars%
9940 }% par not started
9941 }% pars allowed
9942 {% pars not allowed
9943 \LWR@label@subcreatetag%
9944 }% pars not allowed
9945 }% not inside HTML math comment
9946 }% not lateximage
9947 }
```

`\LWR@new@label`  $\{\langle label \rangle\}$

`\label` during HTML output when not in SVG math mode, removing extra spaces around the label, as done by a regular L<sup>A</sup>T<sub>E</sub>X `\label`.

This is also used during a `lateximage`, including SVG math, since the special label handling is required, but `\LWR@label@createtag` does not generate HTML tags inside a `lateximage`.

If `memoir` is used, its `\@memoold@label` is pointed here.

`cleveref` later encases this to add its own cross-referencing, and also patches `memoir`.

```

9948 \NewDocumentCommand{\LWR@new@label}{m}{%
9949 \LWR@traceinfo{\LWR@new@label: starting}%
9950 \LWR@traceinfo{\LWR@new@label: !#1!}%
9951 % \@bsphack%

```

Create a traditional L<sup>A</sup>T<sub>E</sub>X label, as modified by `cleveref`:

```

9952 \LWR@orig@label{#1}%

```

Create a special label which holds the section number, `LWR@htmlfilenumber`, `LWR@lateximagedepth`, and `LWR@lateximagenumber`:

```

9953 \LWR@traceinfo{%
9954 LWR@new@label: filesectionnames is %
9955 \ifbool{FileSectionNames}{true}{false}%
9956 }%
9957 \LWR@traceinfo{%
9958 LWR@new@label: LWR@thisfilename is !\LWR@thisfilename!%
9959 }%
9960 \LWR@traceinfo{%
9961 LWR@new@label: LWR@htmlfilenumber is \arabic{LWR@htmlfilenumber}%
9962 }%
9963 \LWR@write@lwarplabel{#1}%
9964 \LWR@label@createtag{#1}%
9965 % \@esphack%
9966 \LWR@traceinfo{\LWR@new@label: done}%
9967 }

```

## 74.4 References

`\LWR@addlinktitle`

```

9968 \newcommand*{\LWR@addlinktitle}{%
9969 \ifdefvoid{\LWR@ThisAltText}{}{ % space
9970 title="\LWR@ThisAltText" % space
9971 \gdef\LWR@ThisAltText{}%
9972 }%
9973 }

```

`\LWR@startref`  $\{ \langle label \rangle \}$  (Common code for `\ref` and `\nameref`.)

Open an HTML tag reference to a filename, # character, and a label.

```

9974 \newcommand*{\LWR@startref}[1]
9975 {%
9976 \LWR@sanitize{#1}%
9977 \LWR@traceinfo{\LWR@startref A: !#1!}%

```

Create the filename part of the link:

```

9978 \LWR@htmltag{a href="%

```

```

9979 \LWR@traceinfo{LWR@startref B}%
9980 \LWR@print@mbox{\LWR@htmlrefsectionfilename{#1}}%
9981 \LWR@traceinfo{LWR@startref C}%
9982 \LWR@origpound%

```

Create the destination id:

See if `LWR@lateximagedepth` is unknown:

```

9983 \LWR@traceinfo{LWR@startref D: !#1!}%
9984 \ifcsundef{r@#1@lwarp}%

```

“??” if `LWR@lateximagedepth` is unknown, so create a link with an unknown destination:

```

9985 {%
9986 \LWR@traceinfo{LWR@startref D0: ??}%
9987 ??%
9988 }%

```

If `LWR@lateximagedepth` is known. Use a lateximage if the depth is greater than zero, or a regular link otherwise:

```

9989 {%
9990 \ifthenelse{\cnttest{\LWR@lateximagedepthref{#1}}{>}{0}}%
9991 {%
9992 \lateximage-\BaseJobname-\LWR@lateximagenumberref{#1}%
9993 }%
9994 {%
9995 \LWR@traceinfo{LWR@startref D3}%

```

`\detokenize` is used to allow underscores in the labels:

```

9996 \LWR@print@mbox{\LWR@sanitized}%
9997 }%
9998 }%
9999 \LWR@traceinfo{LWR@startref E}%

```

Closing quote:

```

10000 "%

```

Maybe add a title:

```

10001 \LWR@addlinktitle%
10002 }%
10003 \LWR@traceinfo{LWR@startref F}%
10004 }

```

`\LWR@subnewref`  $\{ \langle label \rangle \} \{ \langle label \text{ or } sub@label \rangle \}$

Factored for the `subfig` package. Uses the original label for the hyper-reference, but prints its own text, such as “1(b)”.

```
10005 \NewDocumentCommand{\LWR@subnewref}{m m}{%
10006 \LWR@traceinfo{\LWR@subnewref #1 #2}%
10007 \LWR@startref{#1}%
10008 \LWR@print@ref{#2}%
10009 \LWR@htmltag{/a}%
10010 }
```

`\ref * {<label>}` `\ref` is redefined to `\LWR@HTML@ref`, except inside the text part of a `\hyperref`, where it is redefined to `\LWR@ref@ignorestar`.

`\LWR@HTML@ref * {<label>}` Create an internal document reference link, or without a link if starred per `hyperref`.

`hyperref` defines a starred version. Since `hyperref` is only emulated, the starred version is defined here for print mode, in case `\ref` is used inside `svg math`:

```
10011 \LWR@absorbstar{ref}%
```

The HTML version:

```
10012 \NewDocumentCommand{\LWR@HTML@ref}{s m}{%
10013 \LWR@traceinfo{\LWR@HTML@ref !#2!}%
10014 \IfBooleanTF{#1}%
10015 {\LWR@print@ref{#2}}%
10016 {\LWR@subnewref{#2}{#2}}%
10017 }
10018
10019 \LWR@formatted{ref}
```

For MATHJAX:

```
10020 \CustomizeMathJax{\let\LWRref\ref}
10021 \CustomizeMathJax{\renewcommand{\ref}{\ifstar\LWRref\LWRref}}
```

`\pagerefPageFor` Text for page references.

```
10022 \newcommand*{\pagerefPageFor}{see }
```

`\pageref * {<label>}` Create an internal document reference, or just the unlinked number if starred, per `hyperref`.

```
10023 \NewDocumentCommand{\LWR@new@pageref}{s m}{%
10024 \IfBooleanTF{#1}%
10025 {(\pagerefPageFor\LWR@print@ref{#2})}%
10026 {(\cpageref{#2})}%
10027 }
```

`\nameref {<label>}`

```
10028 \newrobustcmd*{\nameref}[1]{%
10029 \LWR@traceinfo{nameref}%
10030 \LWR@startref{#1}%
10031 \LWR@traceinfo{nameref B}%
10032 \LWR@nameref{#1}%
10033 \LWR@traceinfo{nameref C}%
10034 \LWR@htmltag{/a}%
10035 \LWR@traceinfo{nameref: done}%
10036 }
```

`\Nameref {<label>}` In print, adds the page number. In HTML, does not.

```
10037 \LetLtxMacro\Nameref\nameref
```

## 74.5 Hyper-references



Note that the code currently only sanitizes the underscore character. Additional characters should be rendered inert as well. See the `hyperref.sty` definition of `\gdef\hyper@normalise` for an example.

Pkg hyperref



Do not tell other packages that `hyperref` is emulated. Some packages patch various commands if `hyperref` is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

```
10038 % DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:
10039 % \EmulatesPackage{hyperref}[2015/08/01]% Disabled. Do not do this.
```

Emulates `hyperref`:

`\@currentHref` Added to support `backref`.

```
10040 \AtBeginDocument{
10041 \def\@currentHref{\BaseJobname-autopage-\theLWR@currentautosec}
10042 }
```

`\LWR@linkcatcodes` Sets catcodes before processing macros which have hyperlinks as arguments.

```
10043 \newcommand*{\LWR@linkcatcodes}{%
10044 \catcode'\#=12%
10045 \catcode'\%=12%
10046 \catcode'\&=12%
10047 \catcode'\~=12%
10048 \catcode'_ =12%
```

For `babel-french`:

```
10049 \LWR@FBcancel%
10050 }
```

`\LWR@linkmediacatcodes` Sets catcodes before processing macros which have hyperlinks as arguments. Modified for multimedia links.

```
10051 \newcommand*\LWR@linkmediacatcodes}{%
10052 \catcode'\#=12%
10053 \catcode'\%=12%
10054 % \catcode'\&=12% left alone for splitting flash variables
10055 \catcode'\~=12%
10056 \catcode'_ =12%
```

For babel-french:

```
10057 \LWR@FBcancel%
10058 }
```

`\LWR@subhyperref` `{\URL}`

Starts a link for `\LWR@hrefb`. A group must have been opened first, with nullified catcodes. The text name is printed afterwards, after the group is closed and catcodes restored.

```
10059 \NewDocumentCommand{\LWR@subhyperref}{m}{%
10060 \LWR@traceinfo{\LWR@subhyperref !#1!}%
10061 \LWR@sanitize{#1}%
10062 \LWR@htmltag{%
10063 a href="\LWR@sanitized" % space
10064 \LWR@addlinktitle % space
10065 target="_{}blank" % space
10066 }%
10067 }
```

`\LWR@subhyperreftext` `{\text}`

Finishes the hyperref for `\LWR@hrefb`. Catcodes must have been restored already. To be used after `\LWR@subhyperref`, and after its group has been closed.

```
10068 \newcommand{\LWR@subhyperreftext}[1]{%
10069 #1%
10070 \LWR@htmltag{/a}%
10071 \LWR@ensuredoingapar%
10072 }
```

`\LWR@subhyperrefclass` `{\URL}` `{\text}` `{\htmlclass}`

```
10073 \NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
10074 \LWR@htmltag{%
10075 a % space
10076 href="\begingroup\@sanitize#1\endgroup" % space
10077 class="#3" % space
```

```

10078 \LWR@addlinktitle % space
10079 }\LWR@orignewline%
10080 #2%
10081 \LWR@htmltag{/a}%
10082 \LWR@ensuredoingapar%
10083 }

```

`\LWR@href` [*options*] {*URL*}

Create a link with accompanying text:

```

10084 \DeclareDocumentCommand{\LWR@hrefb}{O{} m}{%
10085 \LWR@ensuredoingapar%
10086 \LWR@subhyperref{#2}%
10087 \endgroup% restore catcodes
10088 \LWR@subhyperreftext%
10089 }
10090
10091 \newrobustcmd*{\LWR@href}{%
10092 \begingroup%
10093 \LWR@linkcatcodes%
10094 \LWR@hrefb%
10095 }

```

`\LWR@nolinkurl` {*URL*}

Print the name of the link without creating the link:

```

10096 \newcommand*{\LWR@nolinkurlb}[1]{%
10097 \LWR@ensuredoingapar%
10098 \def\LWR@templink{#1}%
10099 \@onelevel@sanitize\LWR@templink%
10100 \LWR@templink%
10101 \endgroup%
10102 }
10103
10104 \newrobustcmd*{\LWR@nolinkurl}{%
10105 \begingroup%
10106 \LWR@linkcatcodes%
10107 \LWR@nolinkurlb%
10108 }

```

`\LWR@url` {*URL*}

Create a link whose text name is the address of the link.

The `url` package may redefine `\url`, so it is `\let` to `\LWR@url` here and also redefined by `lwarp-url`.

```

10109 \DeclareDocumentCommand{\LWR@urlb}{m}{%
10110 \LWR@ensuredoingapar%
10111 \def\LWR@templink{#1}%
10112 \@onelevel@sanitize\LWR@templink%

```

```

10113 \LWR@href{\LWR@templink}{\LWR@templink}%
10114 \endgroup%
10115 }
10116
10117 \newrobustcmd*\LWR@url{%
10118 \begingroup%
10119 \LWR@linkcatcodes%
10120 \LWR@urlb%
10121 }

```

`\LWR@subinlineimage`  $\{\langle alt \rangle tag\} \{\langle class \rangle\} \{\langle filename \rangle\} \{\langle extension \rangle\} \{\langle CSS style \rangle\}$

Factored from `lateximage`.

```

10122 \newcommand*\LWR@subinlineimage}[5]{%
10123 \ifblank{#1}%
10124 {%
10125 \LWR@htmltag{img \LWR@indentHTML
10126 src="#3.#4" \LWR@indentHTML
10127 alt="#3" \LWR@indentHTML
10128 style="#5" \LWR@indentHTML
10129 class="#2" \LWR@orignewline
10130 }%
10131 }%
10132 {%
10133 \LWR@htmltag{img \LWR@indentHTML
10134 src="#3.#4" \LWR@indentHTML
10135 alt="#1" \LWR@indentHTML
10136 style="#5" \LWR@indentHTML
10137 class="#2" \LWR@orignewline
10138 }%
10139 }%
10140 }

10141 \end{warpHTML}

```

Table 15: Float data structures

---

For each <type> of float (figure, table, etc.) there exists the following:

- counter <type>:** A counter called <type>, such as figure, table.
  - \<type>name:** Name. \figurename prints “Figure”, etc.
  - \ext@<type>:** File extension. \ext@figure prints “lof”, etc.
  - \fps@<type>:** Placement.
  - \the<type>:** Number. \thetable prints the number of the table, etc.
  - \p@<type>:** Parent’s number. Prints the number of the [within] figure, etc.
  - \fnum@<type>:** Prints the figure number for the caption.  
     <type>name \the<type>, “Figure 123”.
  - \<type>:** Starts the float environment. \figure or \begin{figure}
  - \end<type>:** Ends the float environment. \endfigure or \end{figure}
  - \tf@<ext>:** The L<sup>A</sup>T<sub>E</sub>X file identifier for the output file.
  - LWR@have<type>:** A boolean remembering whether a \listof was requested for a float of this type.
  - File with extension lo<f, t, a-z>:** An output file containing the commands to build the \listof<type> “table-of-contents” structure.
  - Cross-referencing names:** For cleveref’s \cref and related, \crefname and \Crefname assign human-readable names for references to this float type.
- 

## 75 Floats

Floats are supported, although partially through emulation.

Table 15 shows the data structure associated with each <type> of float.

### 75.1 Float environment

**for HTML output:** 10142 \begin{warpHTML}

\LWR@floatbegin {<type>} [<placement>]      Begins a \newfloat environment.

10143 \NewDocumentCommand{\LWR@floatbegin}{m o}{%

    Warn if starting a float inside a <span>:

10144      \LWR@spanwarninvalid{float}%

```
10145 \ifbool{FormatWP}{\newline}{}%
10146 \LWR@stoppars%
```

There is a new float, so increment the unique float counter:

```
10147 \addtocounter{LWR@thisautoid}{1}%
10148 \booltrue{LWR@freezethisautoid}%

10149 \begingroup%
```

Settings while inside the environment:

```
10150 \LWR@print@raggedright%
```

Open an HTML figure tag. The figure is assigned a class equal to its type, and another class according to the float package style, if used. Note that `\csuse` returns an empty string if `\LWR@floatstyle@<type>` is not defined.

```
10151 \LWR@htmltag{%
10152 figure id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}" % space
10153 class="#1 \@nameuse{LWR@floatstyle@#1}"%
10154 }%
10155 \ifbool{FormatWP}{%
10156 \LWR@orignewLine%
10157 \LWR@BlockClassWP{#1}{wp#1}%
10158 }{ }%
```

Update the caption type:

```
10159 \renewcommand*{\@capttype}{#1}%
```

Mark the float for a word processor conversion:

```
10160 \LWR@startpars%
10161 \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%
10162
10163 === begin #1 ===
10164
10165 }{ }%
```

After each `\LWR@floatbegin`, look for `\centering`, etc next, using `\LWR@floatalignment`.

```
10166 }
```

For koma-script. The following does not work for tables.

```
10167 \AtBeginDocument{
10168
10169 \@ifpackageloaded{tocbasic}{
10170
10171 \appto\figure@atbegin{%
10172 \LWR@futurenonSPACElet\LWR@mynexttoken\LWR@floatalignment%
```

```

10173 }
10174
10175 }{}% tocbasic
10176
10177 }% AtBeginDocument

```

`\@xfloat` Support packages which create floats directly.  
`\@xdblfloat` Look for `\centering`, etc using `\LWR@floatalignment`.

```

10178 \AtBeginDocument{
10179 \def\@xfloat #1[#2]{%
10180 \LWR@floatbegin{#1}[#2]
10181 \LWR@futurenonspacel\@LWR@mynexttoken\LWR@floatalignment%
10182 }
10183 \def\@xdblfloat #1[#2]{%
10184 \LWR@floatbegin{#1}[#2]
10185 \LWR@futurenonspacel\@LWR@mynexttoken\LWR@floatalignment%
10186 }
10187 }

```

`\LWR@floatend` Ends a `\newfloat` environment.

```

10188 \newcommand*{\LWR@floatend}{%

```

If saw a `\centering`, finish the center environment:

```

10189 \LWR@endfloatalignment%

```

Mark the float end for a word processor conversion:

```

10190 \ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%
10191
10192 === end ===
10193
10194 }{}%
10195 \LWR@stoppars%

```

Close an HTML figure tag:

```

10196 \ifbool{FormatWP}{\endLWR@BlockClassWP}{}%
10197 \LWR@html\elementend{figure}%
10198 \endgroup%
10199 \boolfalse{LWR@freezethisautoid}%
10200 \LWR@startpars%
10201 \ifbool{FormatWP}{\newline}{}%
10202 }

```

`\end@float` Support packages which create floats directly.  
`\end@dblfloat`

```

10203 \AtBeginDocument{
10204 \let\end@float\LWR@floatend
10205 \let\end@dblfloat\LWR@floatend
10206 }

```

## 75.2 Float tracking

Ctr LWR@thisautoid A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
10207 \newcounter{LWR@thisautoid}
```

Ctr LWR@thisautoidWP A sequential counter for all word processor conversion <div>s. This is used to convince LIBREOffice to form a frame around this element.

```
10208 \newcounter{LWR@thisautoidWP}
```

Bool LWR@freezethisautoid Prevents multiple increments of \LWR@thisautoid inside a float.

```
10209 \newbool{LWR@freezethisautoid}
10210 \boolfalse{LWR@freezethisautoid}
```

\LWR@forcenewautoidanchor Adds a new <autoid> anchor.

```
10211 \newcommand*{\LWR@forcenewautoidanchor}{%
10212 \addtocounter{LWR@thisautoid}{1}%
10213 \ifbool{LWR@doingapar}%
10214 {%
10215 \LWR@htmltag{a id="\LWR@print@mbx{autoid-\arabic{LWR@thisautoid}}" }%
10216 \LWR@htmltag{/a }%
10217 }%
10218 {%
10219 \LWR@stoppars%
10220 \LWR@htmltag{a id="\LWR@print@mbx{autoid-\arabic{LWR@thisautoid}}" }%
10221 \LWR@htmltag{/a }%
10222 \LWR@startpars%
10223 }%
10224 }
```

\LWR@newautoidanchor Sometimes adds a new <autoid> anchor.

```
10225 \newcommand*{\LWR@newautoidanchor}{%
10226 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
10227 {}%
10228 {\ifbool{LWR@freezethisautoid}}{\LWR@forcenewautoidanchor}}%
10229 }
```

\@capttype Remembers which float type is in use.

```
10230 \newcommand*{\@capttype}{}
```

\LWR@floatalignmentname Set to center, flushleft, or flushright if saw \centering, \raggedright, or \raggedleft.

```
10231 \newcommand*{\LWR@floatalignmentname}{}
```

`\LWR@floatalignment` If sees a `\centering`, `\raggedleft`, or `\raggedright`, creates a center, flushright, or flushleft environment.

```

10232 \newcommand*\LWR@floatalignment{%
10233 \ifdefstrequal{\LWR@mynexttoken}{\centering}{%
10234 \center%
10235 \renewcommand*\LWR@floatalignmentname}{center}%
10236 }{}%
10237 \ifdefstrequal{\LWR@mynexttoken}{\raggedright}{%
10238 \flushleft%
10239 \renewcommand*\LWR@floatalignmentname}{flushleft}%
10240 }{}%
10241 \ifdefstrequal{\LWR@mynexttoken}{\raggedleft}{%
10242 \flushright%
10243 \renewcommand*\LWR@floatalignmentname}{flushright}%
10244 }{}%
10245 }
```

`\LWR@endfloatalignment` Closes an environment from `\LWR@floatalignment`.

```

10246 \newcommand*\LWR@endfloatalignment{%
10247 \ifdefvoid{\LWR@floatalignmentname}%
10248 {}%
10249 {\@nameuse{end\LWR@floatalignmentname}}%
10250 \renewcommand*\LWR@floatalignmentname{}%
10251 }
```

### 7.5.3 Caption inside a float environment

`\CaptionSeparator` How to separate the float number and the caption text, if not defined by the user. In most cases, `caption`'s settings are used instead.

```
10252 \AtBeginDocument{\providecommand*\CaptionSeparator}{:~}}
```

```
\@caption {<posn>} [<name>] {<long name>}
```

```
\@makecaption {<name and num>} {<text>}
```

Prints the float type and number, the caption separator, and the caption text.

`\@caption` is provided here in case `caption` is not loaded, and is based on the `nameref` package.

```

10253 \AtBeginDocument{
10254 \ifpackageloaded{caption}{}{
10255 \let\LWR@orig@caption\@caption%
10256 \long\def\@caption#1[#2]{%
```

Warn if using a caption inside a `<span>`:

```
10257 \LWR@spanwarnformat{caption}%
```

```

10258 \LWR@setlatestname{#2}%
10259 \LWR@orig@caption{#1}[{#2}]% also takes third argument
10260 }%
10261
10262 \renewcommand{\@makecaption}[2]{%
10263 \LWR@traceinfo{\@makecaption}%
10264 \caption@begin{\@capttype}%
10265 \LWR@isolate{#1}%
10266 \edef\LWR@tempone{#1}%
10267 \ifdefvoid{\LWR@tempone}{\CaptionSeparator}%
10268 \LWR@isolate{#2}%
10269 \caption@end%
10270 \LWR@traceinfo{\@makecaption: done}%
10271 }%
10272 }
10273 }

```

## 75.4 Caption and LOF linking and tracking

When a new HTML file is marked in the L<sup>A</sup>T<sub>E</sub>X PDF file, or at the start of a new section, the L<sup>A</sup>T<sub>E</sub>X page number at that point is stored in `LWR@latestautopage`, (and the associated filename is remembered by the special L<sup>A</sup>T<sub>E</sub>X labels). This page number is used to generate an `autopage HTML <id>` in the HTML output at the start of the new HTML file or section. Meanwhile, there is a float counter used to generate an `HTML autoid <id>` at the start of the float itself in the HTML file. The `autopage` and `autoid` values to use for each float are written to the `.lof`, etc. files just before each float's entry. These values are used by `\l@figure`, etc. to create the HTML links in the List of Figures, etc.

Ctrl `LWR@nextautoid` Tracks `autoid` for floats. Tracks `autopage` for floats.  
Ctrl `LWR@nextautopage` These are updated per float as the `.lof`, `.lot` file is read.

```

10274 \newcounter{LWR@nextautoid}
10275 \newcounter{LWR@nextautopage}

```

```
\LWRsetnextfloat {<autopage>} {<float autoid>}
```

File `*_html.lof` This is written to the `*_html.lof` or `*_html.lot` file just before each float's usual entry. The `autopage` and the float's `autoid` are remembered for `\l@figure` to use when creating the HTML links.  
File `*_html.lot`

```

10276 \newcommand*\LWRsetnextfloat}[2]{%
10277 \setcounter{LWR@nextautopage}{#1}%
10278 \setcounter{LWR@nextautoid}{#2}%
10279 }

```

Ctrl `LWR@latestautopage` The HTML output's PDF page number at the start of a new HTML file or section.

`\LWRsetnextfloat` is written with this and the `autoid` by the modified `\addcontentsline` just before each float's entry.

```
10280 \newcounter{LWR@latestautopage}
10281 \setcounter{LWR@latestautopage}{1}
```

Env LWR@figcaption An HTML <figcaption> is not allowed in places where L<sup>A</sup>T<sub>E</sub>X does allow a figure caption, such as inside a longtable where the tabular has already started, or inside a center environment. Therefore, a <div> of class figurecaption is used instead.

```
10282 \newenvironment*{LWR@figcaption}
10283 {%
10284 \ifbool{FormatWP}{%
10285 \BlockClass[font-style:italic]{figurecaption}%
10286 %
10287 \LWR@print@vspace*{\baselineskip}
10288 }{%
10289 \BlockClass{figurecaption}%
10290 }%
10291 {\endBlockClass}
```

```
\LWR@HTML@caption@begin {<type>}
```

Low-level code to create HTML tags for captions.

The print versions are from the caption package, if loaded.

```
10292 \newcommand*{\LWR@HTML@caption@begin}[1]
10293 {%
10294 \LWR@traceinfo{LWR@HTML@caption@begin}%
```

Keep par and minipage changes local:

```
10295 \begingroup%
```

No need for a minipage or \parbox inside the caption:

```
10296 \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{\}{\}%
10297 \RenewDocumentCommand{\parbox}{O{t} O{} O{t} m +m}{##5}%
```

Enclose the original caption code inside an HTML tag:

```
10298 \LWR@figcaption%
10299 \LWR@traceinfo{LWR@HTML@caption@begin: about to LWR@origcaption@begin}%
10300 \LWR@print@caption@begin{#1}%
10301 \LWR@traceinfo{LWR@HTML@caption@begin: done}%
10302 }
```

\LWR@HTML@caption@end Low-level patches to create HTML tags for captions.

```
10303 \newcommand*{\LWR@HTML@caption@end}
10304 {%
10305 \LWR@traceinfo{LWR@HTML@caption@end}%
10306 \LWR@print@caption@end%
```

Closing tag:

```
10307 \endLWR@figcaption%
10308 \endgroup%
10309 % \leavevmode% avoid bad space factor (0) error
10310 \LWR@traceinfo{LWR@HTML@caption@end: done}%
10311 }
```

`\caption@begin` Low-level patches to create HTML tags for captions. These are assigned `\AtBeginDocument` so that other packages which modify captions will have already been loaded before saving the print-mode version.

Print versions are provided here in case `caption` is not loaded.

```
10312 \AtBeginDocument{
10313 \providecommand{\caption@begin}[1]{}
10314 \LWR@formatted{caption@begin}
10315
10316 \providecommand{\caption@end}{}
10317 \LWR@formatted{caption@end}
10318 }
```

`\captionlistentry` Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```
10319 \AtBeginDocument{%
10320 \@ifpackageloaded{caption}{
10321 \let\LWR@origcaptionlistentry\captionlistentry
10322
10323 \renewcommand*{\captionlistentry}{%
10324 \LWR@ensuredoingapar%
10325 \LWR@origcaptionlistentry%
10326 }

10327 \def\LWR@LTcaptionlistentry{%
10328 \LWR@ensuredoingapar%
10329 \LWR@forcenewautoanchor%
10330 \bgroup%
10331 \@ifstar{\egroup\LWR@LT@captionlistentry}% gobble *
10332 {\egroup\LWR@LT@captionlistentry}%
10333 }%
10334
10335 \def\LWR@LT@captionlistentry#1{%
10336 \caption@listentry\@firstoftwo[LTcaption]{#1}%
10337 }%
10338 }% caption loaded
10339 {% caption not loaded
10340 \newcommand{\captionlistentry}[2]{}%
10341 \newcommand{\LWR@LT@captionlistentry}[2]{}%
10342 }
10343 }% AtBeginDocument
```

`\addcontentsline` Patched to write the autopage and autoid before each float's entry. No changes if writing `.toc`. For a theorem, automatically defines `\ext@<type>` as needed, to mimic and reuse the float mechanism.

f

```

10344 \let\LWR@origaddcontentsline\addcontentsline
10345
10346 \renewcommand*{\addcontentsline}[3]{%
10347 \ifstrequal{#1}{toc}{}% not TOC

10348 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
10349 {}%
10350 {\LWR@newautoidanchor}%

10351 \ifcsvoid{ext@#2}{\csdef{ext@#2}{#1}}{%

10352 \addtocontents{\@nameuse{ext@#2}}{%
10353 \protect\LWRsetnextfloat%
10354 {\arabic{LWR@latestautopage}}%
10355 {\arabic{LWR@thisautoid}}%
10356 }%
10357 }% not TOC
10358 \LWR@origaddcontentsline{#1}{#2}{#3}%
10359 }
```

Pkg `capt-of` Either package provides `\captionof`, which is later patched at the beginning of the document.  
Pkg `caption`

`\captionof` Patched to handle paragraph tags.

```

10360 \RequirePackage{capt-of}
10361
10362 \AtBeginDocument{
10363 \let\LWR@origcaptionof\captionof
10364
10365 \renewcommand*{\captionof}{%
10366 \LWR@stoppars%
10367 \LWR@origcaptionof%
10368 }
10369 }% AtBeginDocument

10370 \end{warpHTML}
```

## 76 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The `.toc`, `.lof`, and `.lot` files are named by the source code `\jobname`.

In HTML, the printed tables are placed inside a `<div>` of class `toc`, `lof`, or `lot`.

A “`sidetoc`” is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular L<sup>A</sup>T<sub>E</sub>X infrastructure is used for TOC, along with some patches to generate HTML output.

for HTML output: 10371 `\begin{warpHTML}`

## 76.1 Reading and printing the toc

`\LWR@myshorttoc` `{\toc/lof/lot/sidetoc}`

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the @ character into a normal letter to allow formatting commands in the section names.

Unlike in regular L<sup>A</sup>T<sub>E</sub>X, the file is not reset after being read, since the `sidetoc` may be referred to again in each HTML page.

```
10372 \newcommand*\LWR@myshorttoc[1]{%
10373 \LWR@traceinfo{LWR@myshorttoc: #1}%
10374 \LWR@ensuredoingapar%
```

Only if the file exists:

```
10375 \IfFileExists{\jobname.#1}{%
10376 \LWR@traceinfo{LWR@myshorttoc: loading}%
```



Many of the commands in the file will have @ characters in them, so @ must be made a regular letter.

```
10377 \begingroup%
10378 \makeatletter%
```

Disable CJK xpinyin while generating the `sidetoc`.

```
10379 \LWR@disablepinyin%
```

Read in the toc file:

```
10380 \@input{\jobname.#1}%
10381 \endgroup%
10382 }%
10383 {%
10384 \LWR@traceinfo{LWR@myshorttoc: done}%
10385 }
```

`\LWR@subtableofcontents` `{\toc/lof/lot} {\sectionstarname}`

Places a TOC/LOF/LOT at the current position.

```
10386 \NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
10387 \@ifundefined{chapter}%
10388 {\LWR@closeprevious{section}}%
10389 {\LWR@closeprevious{chapter}}%
```

Prints any pending footnotes so that they appear above the potentially large toc:

```
10390 \LWR@printpendingfootnotes%
```

Place the list into its own chapter (if defined) or section:

```
10391 \@ifundefined{chapter}{\section*{#2}}{\chapter*{#2}}%
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
10392 \LWR@htmlclass{nav}{#1}%
```

Create the actual list:

```
10393 \LWR@myshorttoc{#1}%
```

Close the nav:

```
10394 \LWR@htmlclassend{nav}{#1}%
10395 }
```

```
\@starttoc {<ext>}
```

Patch \@starttoc to encapsulate the toc inside HTML tags:

```
10396 \let\LWR@orig@starttoc\@starttoc
10397
10398 \renewcommand{\@starttoc}[1]{
10399 \LWR@htmlclass{nav}{#1}%
10400 \LWR@orig@starttoc{#1}%
10401 \LWR@htmlclassend{nav}{#1}%
10402 }
```

Bool LWR@copiedsidetoc Used to only copy the toc file to the sidetoc a single time.

(listings and perhaps other packages would re-use \tableofcontents for their own purposes, causing the sidetoc to be copied more than once, and thus end up empty.)

```
10403 \newbool{LWR@copiedsidetoc}
10404 \boolfalse{LWR@copiedsidetoc}
```

\tableofcontents Patch \tableofcontents, etc. to print footnotes first. newfloat uses \listoffigures for all future float types.

```

10405 \AtBeginDocument{
10406
10407 \let\LWR@origtableofcontents\tableofcontents
10408
10409 \renewcommand*{\tableofcontents}{%

```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```

10410 \ifboolexpr{bool{FormatWP} and bool{WPMarkTOC}}{
10411
10412 === table of contents ===
10413
10414 }
10415 {

```

Copy the .toc file to .sideroc for printing the sideroc. The original .toc file is renewed when \tableofcontents is finished.

```

10416 \ifbool{LWR@copiedsideroc}{%
10417 \LWR@copyfile{\jobname.toc}{\jobname.sideroc}%
10418 \booltrue{LWR@copiedsideroc}%
10419 }%
10420 \LWR@printpendingfootnotes
10421 \LWR@origtableofcontents
10422 }
10423 }% \tableofcontents
10424
10425 }% AtBeginDocument

```

#### \listoffigures

```

10426 \let\LWR@origlistoffigures\listoffigures
10427
10428 \renewcommand*{\listoffigures}{
10429 \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{
10430
10431 === list of figures ===
10432
10433 }
10434 {
10435 \LWR@printpendingfootnotes
10436 \LWR@origlistoffigures
10437 }
10438 }

```

#### \listoftables

```

10439 \let\LWR@origlistoftables\listoftables
10440
10441 \renewcommand*{\listoftables}{
10442 \ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{
10443

```

```

10444 === list of tables ===
10445
10446 }
10447 {
10448 \LWR@printpendingfootnotes
10449 \LWR@origlistoftables
10450 }
10451 }

```

## 76.2 High-level toc commands

`\listof`  $\{\langle type \rangle\} \{\langle title \rangle\}$

Emulate the `\listof` command from the `float` package (section 264). Used to create lists of custom float types. Also used to redefine the standard L<sup>A</sup>T<sub>E</sub>X `\listoffigures` and `\listoftables` commands.

```

10452 \NewDocumentCommand{\listof}{m +m}{%
10453 \ifundefined{l@#1}{%
10454 \csdef{l@#1}##1##2{\hypertocfloat{1}{#1}{\@nameuse{ext@#1}}{##1}{##2}}%
10455 }{%
10456 \LWR@subtableofcontents{\@nameuse{ext@#1}}{#2}%
10457 \expandafter\newwrite\csname tf@\csname ext@#1\endcsname\endcsname%
10458 \immediate\openout \csname tf@\csname ext@#1\endcsname\endcsname%
10459 \jobname.\@nameuse{ext@#1}\relax%
10460 }

```

## 76.3 Side toc

The “side toc” is a table-of-contents positioned to the side.

It may be renamed by redefining `\sidetocname`, and may contain paragraphs.

Per table 16, `css` may be used to format the sideroc.

Table 16: CSS related to the sideroc

**div.sidetoccontainer:** The entire sideroc.

**div.sidetoctitle:** The title.

**div.sidetoccontents:** The table of contents.

```

10461 \end{warpHTML}

```

**for HTML & PRINT:** 10462 `\begin{warpall}`

**Ctrl** `SideTOCDepth` Controls how deep the side-TOC gets. Use a standard L<sup>A</sup>T<sub>E</sub>X section level similar to `tocdepth`. Warn if parts of the website may be inaccessible.

```

10463 \newcounter{SideTOCDepth}

```

```

10464 \setcounter{SideTOCDepth}{1}
10465
10466 \AtEndDocument{%
10467 \ifnumcomp{\value{SideTOCDepth}}{<}{\value{FileDepth}}{
10468 \PackageWarningNoLine{lwarp}
10469 {%
10470 SideTOCDepth is less than FileDepth,\MessageBreak
10471 so some website pages may be inaccessible%
10472 }
10473 }{}
10474 }

```

`\sitetocname` Holds the default name for the sideroc.

```

10475 \newcommand{\sitetocname}{Contents}

10476 \end{warpall}

```

**for HTML output:** 10477 `\begin{warpHTML}`

`\LWR@sitetoc` Creates the actual side-TOC.

```

10478 \newcommand*{\LWR@sitetoc}{%
10479 \LWR@forcenewpage
10480 \LWR@stoppars
10481 }

```

The entire sideroc is placed into a nav of class `sitetoc`.

```

10482 \LWR@htmlclass{div}{sitetoccontainer}
10483 \LWR@htmlclass{nav}{sitetoc}
10484
10485 \setcounter{tocdepth}{\value{SideTOCDepth}}
10486

```

The title is placed into a `<div>` of class `sitetoctitle`, and may contain paragraphs.

```

10487 \begin{BlockClass}{sitetoctitle}
10488 \ifcvoid{thetitle}{}{\InlineClass{sitetocthetitle}{\thetitle}\par}
10489 \sitetocname
10490 \end{BlockClass}

```

The table of contents is placed into a `<div>` of class `sitetoccontents`.

```

10491 \begin{BlockClass}{sitetoccontents}
10492 \LinkHome
10493
10494 \LWR@myshorttoc{sitetoc}
10495 \end{BlockClass}
10496 \LWR@htmlclassend{nav}{sitetoc}
10497 \LWR@htmlclassend{div}{sitetoccontainer}
10498 }

```

## 76.4 Low-level toc line formatting

`\numberline`  $\langle number \rangle$

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```
10499 \newcommand*\LWR@numberline[1]{%
10500 \LWR@sectionnumber{#1}\quad%
10501 }
10502
10503 \LetLtxMacro\numberline\LWR@numberline
```

`\LWR@maybetocdata` Replaced by `tocdata`. Adds author name.

```
10504 \newcommand*\LWR@maybetocdata{}
```

`\hypertoc`  $\langle 1: depth \rangle$   $\langle 2: type \rangle$   $\langle 3: name \rangle$   $\langle 4: page \rangle$

Called by `\l@section`, etc. to create a hyperlink to a section.

The autopage label is always created just after the section opens.

**#1** is depth

**#2** is section, subsection, etc.

**#3** the text of the caption

**#4** page number

```
10505 \NewDocumentCommand{\hypertoc}{m m +m m}{%
10506 \LWR@traceinfo{hypertoc !#1!#2!#3!#4!}%
```

Respond to `tocdepth`:

```
10507 \ifnumcomp{#1}{>}{\value{tocdepth}}%
10508 {}%
10509 {%
10510 \LWR@startpars%
```

Create an HTML link to `<filename>#autosec-(page)`, with the name, of the given HTML class.

`\BaseJobname` is added to the label in case `xr` or `xr-hyper` are used.

```
10511 \LWR@subhyperrefclass{%
10512 \LWR@htmlrefsectionfilename{\BaseJobname-autopage-#4}%
10513 \LWR@origpound\LWR@print@box{autosec-#4}%
10514 }{#3}{toc#2}%
```

```

10515 \LWR@maybetocdata%

10516 \LWR@stoppars%
10517 }%
10518 \LWR@traceinfo{hypertoc done}%
10519 }

```

Ctrl lofdepth TOC depth for figures.

```

10520 \@ifclassloaded{memoir}{%
10521 \newcounter{lofdepth}
10522 \setcounter{lofdepth}{1}
10523 }

```

Ctrl lotdepth TOC depth for tables.

```

10524 \@ifclassloaded{memoir}{%
10525 \newcounter{lotdepth}
10526 \setcounter{lotdepth}{1}
10527 }

```

`\hypertocfloat`  $\langle 1: depth \rangle \langle 2: type \rangle \langle 3: ext\ of\ parent \rangle \langle 4: caption \rangle \langle 5: page \rangle$

**#1** is depth

**#2** is figure, table, etc.

**#3** is lof, lot, of the parent.

**#4** the text of the caption

**#5** page number

```

10528 \newcommand{\hypertocfloat}[5]{%

```

If some float-creation package has not yet defined the float type's lofdepth counter, etc, define it here:

```

10529 \@ifundefined{c@#3depth}{%
10530 \newcounter{#3depth}%
10531 \setcounter{#3depth}{1}%
10532 }{}%

```

Respond to lofdepth, etc.:

```

10533 \LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%
10534 \ifthenelse{\cntttest{#1}{<=}}{\arabic{#3depth}}{}%
10535 {%
10536 \LWR@startpars%

```

Create an HTML link to filename#autoid-(float number), with text of the caption, of the given HTML class.

`\BaseJobname` is added to the label in case `xr` or `xr-hyper` are used.

```

10537 \LWR@subhyperrefclass{%
10538 \LWR@htmlrefsectionfilename{%
10539 \BaseJobname-autopage-\arabic{LWR@nextautopage}%
10540 }%
10541 \LWR@origpound\LWR@print@embox{autoid-\arabic{LWR@nextautoid}}}%
10542 {#4}{toc#2}%

10543 \LWR@maybetocdata%

10544 \LWR@stoppars%
10545 }%
10546 {}%
10547 }
```

Automatically called by `\contentsline`:

```
\l@book {<name>} {<page>}
```

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\book`.

```
10548 \DeclareDocumentCommand{\l@book}{m m}{\hypertoc{-2}{book}{#1}{#2}}
```

```
\l@part {<name>} {<page>}
```

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\part`.

```
10549 \DeclareDocumentCommand{\l@part}{m m}{\hypertoc{-1}{part}{#1}{#2}}
```

```
\l@chapter {<name>} {<page>}
```

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\chapter`.

```

10550 \@ifundefined{chapter}
10551 {}
10552 {
10553 \DeclareDocumentCommand{\l@chapter}{m m}
10554 {\hypertoc{0}{chapter}{#1}{#2}}
10555 }
```

```
\l@section {<name>} {<page>}
```

```
10556 \renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
```

```
\l@subsection {<name>} {<page>}
```

```
10557 \renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
```

```

\l@subsubsection {<name>} {<page>}

10558 \renewcommand{\l@subsubsection}[2]{\hypertoc{3}{subsubsection}{#1}{#2}}

\l@paragraph {<name>} {<page>}

10559 \renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}

\l@subparagraph {<name>} {<page>}

10560 \renewcommand{\l@subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}

\l@figure {<name>} {<page>}

10561 \renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}

\l@table {<name>} {<page>}

10562 \renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}

10563 \end{warpHTML}

```

## 77 Index and glossary

See:

<http://tex.stackexchange.com/questions/187038/how-to-mention-section-number-in-index-created-by-imakeidx>

Index links are tracked by the counter `LWR@autoindex`. This counter is used to create a label for each index entry, and a reference to this label for each entry in the index listing. This method allows each index entry to link directly to its exact position in the document.

**for HTML output:** 10564 `\begin{warpHTML}`

```

10565 \newcounter{LWR@autoindex}
10566 \setcounter{LWR@autoindex}{0}
10567
10568 \newcounter{LWR@autoglossary}
10569 \setcounter{LWR@autoglossary}{0}

```

`\IndexPageSeparator` User-adjustable delimiters for page and range separators in the \*.ind files.  
`\IndexRangeSeparator`

```

10570 \newcommand*\IndexPageSeparator}{, }
10571 \newcommand*\IndexRangeSeparator}{--}

```

Env theindex

```

10572 \@ifundefined{chapter}
10573 {\newcommand*\LWR@indexsection}[1]{\section*{#1}}
10574 {\newcommand*\LWR@indexsection}[1]{\chapter*{#1}}
10575
10576
10577 \AtBeginDocument{
10578
10579 \renewenvironment*{theindex}{%
10580 \LWR@indexsection{\indexname}%
10581 \let\item\LWR@indexitem%
10582 \let\subitem\LWR@indexsubitem%
10583 \let\subsubitem\LWR@indexsubsubitem%
10584 }{}
10585
10586 }% AtBeginDocument

```

`\LWR@indexitem` [*(index key)*] The optional argument is added to support `repeatindex`.

```

10587 \newcommand*\LWR@indexitem}[1][\@empty]{
10588
10589 \InlineClass{indexitem}{\LWR@htmlcomment{}}#1%
10590 }

```

`\LWR@indexsubitem`

```

10591 \newcommand*\LWR@indexsubitem){
10592
10593 \InlineClass{indexsubitem}{\LWR@htmlcomment{}}%
10594 }

```

`\LWR@indexsubsubitem`

```

10595 \newcommand*\LWR@indexsubsubitem){
10596
10597 \InlineClass{indexsubsubitem}{\LWR@htmlcomment{}}%
10598 }

```

`\LWR@index@modifyentry` {*(indexing term)*}

If using *xindex*, modifies the pipe character to become `\hyperindexformat`. The indexing term is split into two argument at the pipe, then fed to `\LWR@index@modifyentrysub`.

```

10599 \NewDocumentCommand*\LWR@index@modifyentry}{>{\SplitArgument{1}{|}}m}
10600 {\LWR@index@modifyentrysub#1}

```

Handle left and right parenthesis range argument, or add a `hyperindexformat` clause.

```

10601 \newcommand*\LWR@index@modifyentrysub}[2]{%
10602 \edef\LWR@tempone{#1}%
10603 \edef\LWR@temptwo{#2}%

```

```

10604 \IfValueTF{#2}{%
10605 \ifx#2(%
10606 \appto\LWR@tempone{ | }%
10607 \else%
10608 \ifx#2)%
10609 \appto\LWR@tempone{ |)}%
10610 \else%
10611 \appto\LWR@tempone{%
10612 |hyperindexformat\LWRleftbrace%
10613 \LWRbackslash#2%
10614 \LWRrightbrace%
10615 }%
10616 \fi%
10617 \fi%
10618 }%
10619 {}%
10620 }

```

`\@wrindex {<indexing term>}` Redefined to write the LWR@autoindex counter instead of page.

If using *xindex*, the first line is a comment including a special phrase which tricks *xindex* into thinking that *hyperref* was used.

```

10621 \newbool{LWR@xindex@tricked}
10622 \boolfalse{LWR@xindex@tricked}
10623
10624 \def\LWR@wrindex#1{%
10625 \ifbool{LWR@xindex}{%
10626 \ifbool{LWR@xindex@tricked}{%
10627 \protected@write\@indexfile{%
10628 {%
10629 \LWRpercent\space hyperpage\LWRrightbrace%
10630 \LWRpercent\space trick xindex to assume hyperref%
10631 }%
10632 \global\booltrue{LWR@xindex@tricked}%
10633 }%
10634 \LWR@xindex@modifyentry{#1}%
10635 }{%
10636 \def\LWR@tempone{#1}%
10637 }%
10638 \addtocounter{LWR@autoindex}{1}%
10639 \label{LWRindex-\arabic{LWR@autoindex}}%
10640 \protected@write\@indexfile{%
10641 {\string\indexentry{\LWR@tempone}{\arabic{LWR@autoindex}}}%
10642 \endgroup%
10643 \@esphack%
10644 }
10645
10646 \AtBeginDocument{
10647 \let\@wrindex\LWR@wrindex
10648 }

```

`\@wrglossary {<term>}` Redefined to write the LWR@latestautopage counter instead of page.

```

10649 \def\@wrglossary#1{%
10650 \addtocounter{LWR@autoglossary}{1}%
10651 \LWR@new@label{LWRglossary-\theLWR@autoglossary}%
10652 \protected@write\@glossaryfile{%
10653 {\string\glossaryentry{#1}{\theLWR@autoglossary}}%
10654 \endgroup%
10655 \@esphack%
10656 }

```

`\LWR@indexnameref@anonref`  $\langle LWR@autoindex \rangle$

Displays a reference link where there no `\ref` available.

```

10657 \newcommand*\LWR@indexnameref@anonref}[1]{%
10658 \LWR@startref{LWRindex-#1}%
10659 (*)%
10660 \LWR@htmltag{/a}%
10661 }

```

`\LWR@indexnameref@ref`  $\langle LWR@autoindex \rangle$

Creates `\ref`-style index references. To avoid an unwanted space if there is nothing to reference, the reference is checked first.

```

10662 \newcommand*\LWR@indexnameref@ref}[1]{%
10663 \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
10664 \ifdefvoid{\LWR@thisref}{}%
10665 \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
10666 \ifdefvoid{\LWR@thisref}%
10667 {\LWR@indexnameref@anonref{#1}}%
10668 {\ref{LWRindex-#1}}%
10669 }%
10670 }

```

`\LWR@indexnameref@refnameref`  $\langle LWR@autoindex \rangle$

Creates `\ref`-style index references. To avoid an unwanted space if there is nothing to reference, the reference is checked first. For links to starred or ?? objects, only the name is used.

```

10671 \newcommand*\LWR@indexnameref@refnameref}[1]{%
10672 \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
10673 \ifdefvoid{\LWR@thisref}{}%
10674 \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
10675 \ifdefvoid{\LWR@thisref}{}%
10676 \ifdefstring{\LWR@thisref}{(*)}%
10677 {}%
10678 {\ref{LWRindex-#1} }% space
10679 }%
10680 }%
10681 \nameref{LWRindex-#1}%
10682 }

```

`\LWR@indexnameref@cref`  $\langle LWR@autoindex \rangle$

Creates `\cref`-style index references. If no numbered reference is available, a `\nameref` is used instead. If the reference is `??`, which will be changed by `\LWR@indexnameref` to become `(*)`, then the link is changed to show `(*)`.

```

10683 \newcommand*{\LWR@indexnameref@cref}[1]{%
10684 \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
10685 \ifdefvoid{\LWR@thisref}{%
10686 \nameref{LWRindex-#1}%
10687 }{%
10688 \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
10689 \ifdefvoid{\LWR@thisref}{%
10690 \nameref{LWRindex-#1}%
10691 }{%
10692 \ifdefstring{\LWR@thisref}{(*)}{%
10693 \LWR@indexnameref@anonref{#1}%
10694 }{%
10695 \cref{LWRindex-#1}%
10696 }%
10697 }%
10698 }%
10699 }

```

`\LWR@indexnameref@crefnameref`  $\langle LWR@autoindex \rangle$

Creates `\cref`-style index references. If no numbered reference is available, a `\nameref` is used instead. If the reference is `??`, which will be changed by `\LWR@indexnameref` to become `(*)`, then the link is changed to show only the name.

```

10700 \newcommand*{\LWR@indexnameref@crefnameref}[1]{%
10701 \edef\LWR@thisref{\csuse{r@LWRindex-#1}}%
10702 \ifdefvoid{\LWR@thisref}%
10703 {}%
10704 {%
10705 \edef\LWR@thisref{\expandafter\@firstoftwo\LWR@thisref}%
10706 \ifdefvoid{\LWR@thisref}%
10707 {}%
10708 {%
10709 \ifdefstring{\LWR@thisref}{(*)}%
10710 {}%
10711 {\cref{LWRindex-#1}} % space
10712 }%
10713 }%
10714 \nameref{LWRindex-#1}%
10715 }

```

`\LWR@indexnameref`  $\langle LWR@autoindex \rangle$

Creates a hyperlink based on the given entry's autoindex.

```

10716 \newcommand*{\LWR@indexnameref}[1]{%
10717 {% group

```

Temporarily redefine `\caption@xref` because it was printing ?? in the indexes, and also causing error on expansion:

```

10718 \ifdef{\caption@xref}{%
10719 \renewcommand*\caption@xref}[2]{(*)}%
10720 }{%

10721 \ifdefstring{\LWR@IndexRef}{ref}{%
10722 \LWR@indexnameref@ref{#1}%
10723 }{%
10724 \ifdefstring{\LWR@IndexRef}{nameref}{%
10725 \nameref{LWRindex-#1}%
10726 }{%
10727 \ifdefstring{\LWR@IndexRef}{refnameref}{%
10728 \LWR@indexnameref@refnameref{#1}%
10729 }{%
10730 \ifdefstring{\LWR@IndexRef}{cref}{%
10731 \LWR@indexnameref@cref{#1}%
10732 }{%
10733 \ifdefstring{\LWR@IndexRef}{crefnameref}{%
10734 \LWR@indexnameref@crefnameref{#1}%
10735 }{%
10736 \ifdefstring{\LWR@IndexRef}{autoref}{%
10737 \LWR@indexnameref@cref{#1}%
10738 }{% text string
10739 \LWR@startref{LWRindex-#1}%
10740 \LWR@IndexRef%
10741 \LWR@htmltag{/a}%
10742 }}}}}%
10743 }% group
10744 }

```

`\LWR@doindexentrysubsub` *{(range start: LWR@autoindex, or macros.)}{(range end or blank)}*

Creates a hyperlink, or handles `\see`, `\textbf`, etc.

```

10745 \newrobustcmd{\LWR@doindexentrysubsub}[2]{%
10746 \IfInteger{#1}%
10747 {\LWR@indexnameref{#1}}%
10748 {#1}%
10749 \IfValueT{#2}{%
10750 \IndexRangeSeparator%
10751 \IfInteger{#2}%
10752 {\LWR@indexnameref{#2}}%
10753 {#2}%
10754 }%
10755 }

```

`\LWR@doindexentrysub` *{(range delimiter)}{(LWR@autoindex or macros, possible a range)}*

```

10756 \NewDocumentCommand{\LWR@doindexentrysub}{m >{\SplitArgument{1}{#1}}m}
10757 {\LWR@doindexentrysubsub#2}

```

`\LWR@doindexentry` {*<LWR@autoindex or macros, possible a range>*}

```
10758 \newcommand*{\LWR@doindexentry}[1]{%
10759 \relax% required
10760 \expandafter\LWR@doindexentrysub\expandafter{\IndexRangeSeparator}{#1}%
10761 }
```

`\LWR@hyperindexrefnullified` Handles macros commonly seen inside an `\index` entry. Each macro is redefined to create and format a link to its entry.

 **index formatting** To handle additional macros:

```
\appto\LWR@hyperindexrefnullified{...}
```

```
10762 \newcommand{\LWR@hyperindexrefnullified}{%
10763 \renewrobustcmd{\emph}[1]{\LWR@HTML@emph{\LWR@doindexentry{##1}}}%
10764 \renewrobustcmd{\textbf}[1]{\LWR@HTML@textbf{\LWR@doindexentry{##1}}}%
10765 \renewrobustcmd{\texteb}[1]{\LWR@HTML@texteb{\LWR@doindexentry{##1}}}%
10766 \renewrobustcmd{\textlg}[1]{\LWR@HTML@textlg{\LWR@doindexentry{##1}}}%
10767 \renewrobustcmd{\textrm}[1]{\LWR@HTML@textrm{\LWR@doindexentry{##1}}}%
10768 \renewrobustcmd{\textsf}[1]{\LWR@HTML@textsf{\LWR@doindexentry{##1}}}%
10769 \renewrobustcmd{\texttt}[1]{\LWR@HTML@texttt{\LWR@doindexentry{##1}}}%
10770 \renewrobustcmd{\textup}[1]{\LWR@HTML@textup{\LWR@doindexentry{##1}}}%
10771 \renewrobustcmd{\textsc}[1]{\LWR@HTML@textsc{\LWR@doindexentry{##1}}}%
10772 \renewrobustcmd{\textulc}[1]{\LWR@HTML@textulc{\LWR@doindexentry{##1}}}%
10773 \renewrobustcmd{\textsi}[1]{\LWR@HTML@textsi{\LWR@doindexentry{##1}}}%
10774 \renewrobustcmd{\textit}[1]{\LWR@HTML@textit{\LWR@doindexentry{##1}}}%
10775 \renewrobustcmd{\textsl}[1]{\LWR@HTML@textsl{\LWR@doindexentry{##1}}}%
10776 }
```

`\hyperindexref` {*<list of LWR@autoindex, commas, and ranges>*}

`\hyperindexref{LWR@autoindex}` is inserted into `*.ind` by the *makeindex* style file `lwarp.ist` or the *xindy* style file `lwarp.xdy`. For *xindex*, `\hyperpage` is inserted, which is `\let` to `\hyperindexref`. For *gindex*, `\addindexitem` and related are inserted, which are defined to use `\hyperindexref`.

The argument is split at commas, and also for ranges, then passed to `\LWR@hyperindexrefsub`.

```
10777 \newcommand*{\hyperindexref}[1]{%
10778 \relax% required
10779 \expandafter\LWR@hyperindexref@comma\expandafter{\IndexPageSeparator}{#1}%
10780 }
```

`\LWR@hyperindexref@comma` {*<separator>*} {*<list of args>*}

The list is split at commas, and passed to `\LWR@hyperindexref@comma`.

```
10781 \NewDocumentCommand{\LWR@hyperindexref@comma}
10782 {m >{\SplitList{##1}} m}
10783 {%
```

Used to place the separator between each entry, but not before the first.

```
10784 \def\LWR@hyperindexref@thiscomma{}%
10785 \def\LWR@hyperindexref@nextcomma{#1}%
```

Each comma-delimited entry is now passed individually to \LWR@hyperindexref@@comma.

```
10786 \ProcessList{#2}\LWR@hyperindexref@@comma%
10787 }
```

\LWR@hyperindexref@@comma {*<arg, perhaps with a range>*}

A comma separator is placed if not the first item, then the range is parsed.

```
10788 \newcommand*\LWR@hyperindexref@@comma[1]{%
10789 \LWR@hyperindexref@thiscomma%
10790 \renewcommand{\LWR@hyperindexref@thiscomma}{\LWR@hyperindexref@nextcomma}%
10791 \expandafter\LWR@hyperindexref@range\expandafter{\IndexRangeSeparator}{#1}%
10792 }
```

\LWR@hyperindexref@range {*<range delimiter>*} {*<arg>*}

```
10793 \NewDocumentCommand{\LWR@hyperindexref@range}
10794 {m >{\SplitArgument{1}{#1}} m}
10795 {\LWR@hyperindexrefsub#2}
```

\LWR@hyperindexrefsub {*<range start: LWR@autoindex>*} {*<range end, or -NoValue->*}

Handles the start and end of a range, if applicable.

```
10796 \newcommand*\LWR@hyperindexrefsub[2]{%
10797 \LWR@hyperindexrefsubtwo{#1}%
10798 \IfValueT{#2}{%
10799 \IndexRangeSeparator%
10800 \LWR@hyperindexrefsubtwo{#2}%
10801 }%
10802 }
```

\LWR@hyperindexrefsubtwo {*<LWR@autoindex>*}

```
10803 \newcommand*\LWR@hyperindexrefsubtwo[1]{%
```

In long index lines with numerous entries, *makeindex* can insert a newline before the page number, resulting in an extra space before the first digit. If the first character is a space, remove it first.

```
10804 \edef\LWR@tempone{#1}%
10805 \IfBeginWith{\LWR@tempone}{ }{%
10806 \StrGobbleLeft{\LWR@tempone}{1}[\LWR@tempone]%
10807 }{}}%
```

If a numeric entry, create a link. If not numeric, such as `\see`, use the entry as-is. `\emph`, `\textit`, etc. have been redefined above to create and format the entry.

```

10808 \IfInteger{\LWR@tempone}%
10809 {\LWR@indexnameref{\LWR@tempone}}%
10810 {%
10811 \begingroup%
10812 \LWR@hyperindexrefnullified%
10813 #1%
10814 \endgroup%
10815 }%
10816 }
```

`\hyperpage` Emulate `hyperref`.

```
10817 \LetLtxMacro\hyperpage\hyperindexref
```

`\nohyperpage` Emulate `hyperref`.

```
10818 \def\nohyperpage#1{}
```

`\hyperindexformat` Emulate `hyperref`.

```

10819 \def\hyperindexformat#1#2{%
10820 #1{\hyperpage{#2}}%
10821 }%
```

```
10822 \end{warpHTML}
```

**for PRINT output:** A null command for print mode, in case `hyperref` was not used:

```

10823 \begin{warpprint}
10824 \newcommand{\hyperindexref}[1]{#1}
10825 \end{warpprint}
```

**for HTML & PRINT:** For the `glossaries` package, try to prevent an error where `\glo@name` was not found:

```

10826 \begin{warpall}
10827 \providecommand{\glo@name}{}
10828 \end{warpall}
```

## 78 Bibliography presentation

**for HTML output:** 10829 `\begin{warpHTML}`

`\bibliography` `{\filenames}` At one time this was modified to read `\BaseJobname.bbl`, which meant the HTML version could not resolve until the print version was also present. This also confused `multibib`. It has been reverted to the original to use `\jobname.bbl`.

`\@biblabel` { $\langle text-refnumber \rangle$ }

```
10830 \renewcommand{\@biblabel}[1][[#1]\quad}
```

Env `thebibliography` To emphasize document titles in the bibliography, the following redefines `\em` inside `thebibliography` to gather everything until the next closing brace, then display these tokens with `\textit`.

*Adapted from `embracedef.sty`, which is by TAKAYUKI YATO:*

<https://gist.github.com/zr-tex8r/b72555e3e7ad2f0a37f1>

```
10831 \AtBeginDocument{
10832
10833 \AtBeginEnvironment{thebibliography}{
10834
10835 \providecommand*\LWR@newem}[1]{\textit{#1}}
10836
10837 \renewrobustcmd{\em}{%
10838 \begingroup
10839 \gdef\LWR@em@after{\LWR@em@finish\LWR@newem}%
10840 \afterassignment\LWR@em@after
10841 \toks@\bgroup
10842 }
10843
10844 \def\LWR@em@finish#1{%
10845 \xdef\LWR@em@after{\noexpand#1{\the\toks@}}%
10846 \endgroup
10847 \LWR@em@after\egroup
10848 }
10849
10850 }% \AtBeginEnvironment{thebibliography}
10851
10852 }% \AtBeginDocument

10853 \end{warpHTML}
```

## 79 Restoring original formatting

**for HTML output:** `10854 \begin{warpHTML}`

`\LWR@restoreMathJaxformatting` A few macros (ref: `tcolorbox`) must be treated separately while printing the HTML comment for a MATHJAX expression. These are set here, to which other functions may be appended.

```
10855 \newcommand*\LWR@restoreMathJaxformatting{}
```

`\LWR@restoreorigformatting` Used to temporarily restore the print-mode meaning of a number of formatting, graphics, and symbols-related macros while generating SVG math or a `lateximage`.

Must be used inside a group.

Sets `\LWR@formatting` to print until the end of the group.

A number of packages will `\appto` additional actions to this macro.

Various packages add to this macro using `\appto`.

```
10856 \newcommand*\LWR@restoreorigformatting}{%
10857 \LWR@traceinfo{\LWR@restoreorigformatting}%
```

Numerous macros change their print/HTML meaning depending on `\LWR@formatting`:

```
10858 \renewcommand*\LWR@formatting}{print}%
10859 \linespread{1}%

10860 \let\par\LWR@origpar%

10861 \LWR@select@print@hspace%

10862 \LetLtxMacro\hfil\LWR@origfil%
10863 \let\hss\LWR@orighss%
10864 \let\llap\LWR@origllap%
10865 \let\rlap\LWR@origrlap%
10866 \let\hfilneg\LWR@origfilneg%

10867 \let\,\LWR@origcomma% disable HTML short unbreakable space
10868 \let\thinspace\LWR@origthinspace% disable HTML short unbreakable space
10869 \let\negthinspace\LWR@orignegthinspace% disable HTML negative short unbreakable space
10870 \let\textellipsis\LWR@origtextellipsis%

10871 \let\vdots\LWR@origvdots%

10872 \let\textless\LWR@origtextless%
10873 \let\textgreater\LWR@origtextgreater%

10874 \let\&\LWR@origampersand%

10875 \LetLtxMacro\em\LWR@origem%
10876 \LetLtxMacro\normalfont\LWR@orignormalfont%
10877 \let\sp\LWR@origsp%
10878 \let\sb\LWR@origsb%
10879 \LetLtxMacro\underline\LWR@origunderline%
10880 \let~\LWR@origtilde%
10881 \let\enskip\LWR@origenskip%
10882 \let\quad\LWR@origquad%
10883 \let\qqquad\LWR@origqqquad%
```

`\endtabular` must be restored to its original, instead of relying on `lwarp`'s `\LWR@formatted` mechanism:

```
10884 \LetLtxMacro\endtabular\LWR@origendtabular%
10885 \csletcs{endtabular*}{\LWR@origendtabular*}%
```

```

10886 \LetLtxMacro\noalign\LWR@orignoalign%
10887 \LetLtxMacro\hline\LWR@orighline%

10888 \let\newline\LWR@orignewline%
10889 \LetLtxMacro\includegraphics\LWR@origincludegraphics%

10890 \LetLtxMacro\@ensuredmath\LWR@origensuredmath%

10891 \let\math\LWR@orig@math%
10892 \let\endmath\LWR@orig@endmath%
10893 \let\displaymath\LWR@orig@displaymath%
10894 \let\enddisplaymath\LWR@orig@enddisplaymath%
10895 %
10896 \LWR@restoreorigaccents%
10897 \LWR@restoreoriglists%
10898 %
10899 \LWR@FBcancel%

```

To enable MATHJAX-specific nullification, used for tcolorbox:

```

10900 \ifboolexpr{bool{mathjax} or (bool{FormatWP} and bool{WPMarkMath}) }%
10901 {\LWR@restoreMathJaxformatting}%
10902 {}%
10903 }

10904 \end{warpHTML}

```

## 80 Nullifying filename formatting

The following are used to nullify certain macros and environments while converting section names to file names.

**for HTML output:** 10905 \begin{warpHTML}

Also commonly used are \@empty, \@gobble, and \@firstofone.

```
10906 \newcommand*{\LWR@dash}{-}
```

\LWR@nullfonts Removes formatting during filename operations, file references, and HTML comments.

 **Use only inside a group.**

The following are *not* made robust, since they must be expanded to their nullified versions.

```

10907 \catcode'\$=\active% redefining $ below
10908 \catcode'_ =12% redefining _ below
10909 \newcommand*{\LWR@nullfonts}{%

```

## Various built-in symbols.

```

10910 \renewcommand*{\$}{-}%
10911 \renewcommand*{\%}{-}%
10912 \renewcommand*{_}{-}%
10913 \renewcommand*{\}{-}%
10914 \renewcommand*{\{ }{-}%
10915 \renewcommand*{\&}{-}% used to be 'and'
10916 \renewcommand*{\#}{-}%
10917 \renewcommand*{\,}{-}%
10918 \renewcommand*{\~}{-}%
10919 %
10920 % accents:
10921 \renewcommand*{\`}[1]{##1}%
10922 \renewcommand*{\'}[1]{##1}%
10923 \renewcommand*{\^}[1]{##1}%
10924 \renewcommand*{\~}[1]{##1}%
10925 \renewcommand*{\=}[1]{##1}%
10926 \renewcommand*{\u}[1]{##1}%
10927 \renewcommand*{\.}[1]{##1}%
10928 \renewcommand*{\"}[1]{##1}%
10929 \renewcommand*{\H}[1]{##1}%
10930 \renewcommand*{\v}[1]{##1}%
10931 \renewcommand*{\d}[1]{##1}%
10932 \renewcommand*{\c}[1]{##1}%
10933 \renewcommand*{\b}[1]{##1}%
10934 \renewcommand*{\t}[1]{##1}%
10935 %
10936 \let\newline\LWR@dash%
10937 \let\textasciicircum\LWR@dash%
10938 \let\textasciitilde\LWR@dash%
10939 \let\textasteriskcentered\LWR@dash%
10940 \let\textbackslash\LWR@dash%
10941 \let\textbar\LWR@dash%
10942 \let\textbardbl\LWR@dash%
10943 \let\textbigcircle\LWR@dash%
10944 \let\textbraceleft\LWR@dash%
10945 \let\textbraceright\LWR@dash%
10946 \let\textbullet\LWR@dash%
10947 \let\textcopyright\LWR@dash%
10948 \let\textdagger\LWR@dash%
10949 \let\textdaggerdbl\LWR@dash%
10950 \let\textdollar\LWR@dash%
10951 \let\textellipsis\LWR@dash%
10952 \let\textemdash\LWR@dash%
10953 \let\textendash\LWR@dash%
10954 \let\textexclamdown\LWR@dash%
10955 \let\textgreater\LWR@dash%
10956 \let\textless\LWR@dash%
10957 \let\textordfeminine\LWR@dash%
10958 \let\textordmasculine\LWR@dash%
10959 \let\textparagraph\LWR@dash%
10960 \let\textperiodcentered\LWR@dash%
10961 \let\textpertenthousand\LWR@dash%
10962 \let\textperthousand\LWR@dash%

```

```

10963 \let\textquestiondown\LWR@dash%
10964 \let\textquotedblleft\LWR@dash%
10965 \let\textquotedblright\LWR@dash%
10966 \let\textquoteleft\LWR@dash%
10967 \let\textquoteright\LWR@dash%
10968 \let\textregistered\LWR@dash%
10969 \let\textsection\LWR@dash%
10970 \let\textsterling\LWR@dash%
10971 \let\texttrademark\LWR@dash%
10972 \let\textunderscore\LWR@dash%
10973 \let\textvisiblespace\LWR@dash%
10974 \let\copyright\LWR@dash%
10975 \let\dag\LWR@dash%
10976 \let\ddag\LWR@dash%
10977 \let\dots\LWR@dash%
10978 \let\P\LWR@dash%
10979 \let\pounds\LWR@dash%
10980 \let\S\LWR@dash%
10981 %
10982 \renewcommand*\aa}{a}%
10983 \renewcommand*\AA}{A}%
10984 \renewcommand*\AE}{AE}%
10985 \renewcommand*\ae}{ae}%
10986 \renewcommand*\dh}{d}%
10987 \renewcommand*\DH}{D}%
10988 \renewcommand*\DJ}{D}%
10989 \renewcommand*\dj}{d}%
10990 \renewcommand*\IJ}{IJ}%
10991 \renewcommand*\ij}{ij}%
10992 \renewcommand*\L}{L}%
10993 \renewcommand*\l}{l}%
10994 \renewcommand*\NG}{NG}%
10995 \renewcommand*\ng}{ng}%
10996 \renewcommand*\O}{O}%
10997 \renewcommand*\o}{o}%
10998 \renewcommand*\oe}{oe}%
10999 \renewcommand*\OE}{OE}%
11000 \renewcommand*\ss}{ss}%
11001 \renewcommand*\SS}{SS}%
11002 \renewcommand*\th}{th}%
11003 \renewcommand*\TH}{TH}%
11004 %
11005 \let\guillemotleft\@empty%
11006 \let\guilsinglleft\@empty%
11007 \let\quotedblbase\@empty%
11008 \let\textquotedbl\@empty%
11009 \let\guillemotright\@empty%
11010 \let\guilsinglright\@empty%
11011 \let\quotesinglbase\@empty%

11012 \renewcommand*\HTMLunicode}[1]{}%
11013 \renewcommand*\HTMLentity}[1]{}%

11014 \renewcommand{\textsuperscript}[1]{##1}%
11015 \renewcommand{\textsubscript}[1]{##1}%

```

```

11016 \renewcommand{\underline}[1]{##1}%
11017 \RenewDocumentCommand{\hspace}{s m}{}%
11018 \RenewDocumentCommand{\LWR@htmlspanclass}{o m +m}{##3}%
11019 \DeclareExpandableDocumentCommand{\InlineClass}{D{({})}{ } o m +m}{##4}%

```

Nullify math macros.

```

11020 \def\(&##1\){}%
11021 \def\[&##1\]{}%
11022 \RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%

```

Nullify logos:

```

11023 \renewcommand*\TeX{\TeX}%
11024 \renewcommand*\LaTeX{\LaTeX}%
11025 \renewcommand*\LaTeXe{\LaTeX2e}%
11026 \renewcommand*\LuaTeX{\LuaTeX}%
11027 \renewcommand*\LuaLaTeX{\LuaLaTeX}%
11028 \renewcommand*\XeTeX{\XeTeX}%
11029 \renewcommand*\XeLaTeX{\XeLaTeX}%
11030 \renewcommand*\ConTeXt{\ConTeXt}%
11031 \renewcommand*\BibTeX{\BibTeX}%
11032 \renewcommand*\MakeIndex{\MakeIndex}%
11033 \renewcommand*\AmS{\AmS}%
11034 \renewcommand*\MiKTeX{\MiKTeX}%
11035 \renewcommand*\LyX{\LyX}%

```

Use the simpler form with `\texorpdfstring`:

```

11036 \def\texorpdfstring{\expandafter\@secondoftwo}%
11037 }
11038 \catcode'\$=3%
11039 \catcode'_ =8%

```

`\FilenameNullify` *{(redefinitions)}*

Adds more nullifying definitions for filename generation.

```

11040 \newcommand*\FilenameNullify}[1]{%
11041 \appto{\LWR@nullfonts}{#1}%
11042 }
11043 \end{warpHTML}

```

## 81 Math

### 81.1 Limitations

See [Math](#), section 8.7.

## 81.2 HTML alt tag names

Redefinable names for the HTML alt tags, for translation according to the reader's native language.

**for HTML & PRINT:** 11044 `\begin{warpall}`

`\AltTextOpen` The opening part of HTML alt tag for an image. The default is a left parenthesis.  
 Default: `(`

11045 `\newcommand*\AltTextOpen}{(}`

`\AltTextClose` The closing part of HTML alt tag for an image. The default is a right parenthesis.  
 Default: `)`

11046 `\newcommand*\AltTextClose}{)}`

`\ImageAltText` The HTML alt tag for an image.  
 Default: `image`

11047 `\newcommand*\ImageAltText}{image}`

`\MathImageAltText` The HTML alt tag for an SVG math image.  
 Default: `"math image"`

11048 `\newcommand*\MathImageAltText}{math image}`

`\LWR@ThisAltText` The HTML alt tag for the next image. Cleared after use, and also after each `lateximage`, `\LWR@subsingledollar`, and each use of `MATHJAX`.

11049 `\newcommand*\LWR@ThisAltText}{}`

`\ThisAltText` `{<text>}`

Assigns the HTML alt tag for the next image generated by `lwarp`, such as a `lateximage`, `picture`, or `svg math`.

11050 `\newcommand*\ThisAltText[1]{%`

11051 `\renewcommand{\LWR@ThisAltText}{#1}%`

11052 `}`

`\PackageDiagramAltText` Appended to the `lateximage` HTML alt tag for the images generated by many packages.  
 Default: `"diagram"`

11053 `\newcommand*\PackageDiagramAltText}{diagram}`

11054 `\end{warpall}`

### 81.3 Inline and display math

**for HTML output:** 11055 `\begin{warpHTML}`

**Ctr** `LWR@externalfilecnt` Counter for the external files which are generated and then referenced from the HTML:

11056 `\newcounter{LWR@externalfilecnt}`

**Bool** `LWR@indisplaymathimage` True if processing display math for svg output. Inside a `lateximage`, display math is only set to print-mode output if `LWR@indisplaymathimage` is false. Used to avoid nullifying display math before it has been completed.

11057 `\newbool{LWR@indisplaymathimage}`

**Bool** `LWR@insidemathcomment` True while inside an HTML comment which is displaying a math environment. Used to undo the comment for a moment while creating a `\label`, so that the label's HTML tags will be seen by HTML.

11058 `\newbool{LWR@insidemathcomment}`

11059 `\boolfalse{LWR@insidemathcomment}`

**Bool** `LWR@xfakebold` True if `xfakebold \setBold` is in use.

11060 `\newbool{LWR@xfakebold}`

11061 `\boolfalse{LWR@xfakebold}`

`\LWR@orig@setBold` Redefined by `lwarp-xfakebold`.

11062 `\newcommand*{\LWR@orig@setBold}{}`

`\LWR@orig@unsetBold` Redefined by `lwarp-xfakebold`.

11063 `\newcommand*{\LWR@orig@unsetBold}{}`

`\LWR@applyxfakebold` Redefined by `lwarp-xfakebold`.

11064 `\newcommand*{\LWR@applyxfakebold}{}`

`\LWR@setcurrentfont` Sets the actual L<sup>A</sup>T<sub>E</sub>X font to that which was selected for HTML output. Ex: In HTML mode, `\bfseries` sets `\LWR@f@series` to “bf”. This sets the PDF output here for use inside a `lateximage`.

11065 `\newcommand*{\LWR@setcurrentfont}{%`

11066 `\LWR@traceinfo{Using font family \LWR@f@family}%`

11067 `\@nameuse{LWR@print@\LWR@f@family family}%`

11068 `\LWR@traceinfo{Using font series \LWR@f@series}%`

11069 `\@nameuse{LWR@print@\LWR@f@series series}%`

11070 `\LWR@traceinfo{Using font shape \LWR@f@shape}%`

11071 `\@nameuse{LWR@print@\LWR@f@shape shape}%`

11072 `\LWR@traceinfo{Using font caps shape \LWR@f@shapecaps}%`

11073 `\@nameuse{LWR@print@\LWR@f@shapecaps shape}%`

11074 }

`\$` Plain dollar signs appearing in the HTML output may be interpreted by MATHJAX to be math shifts. For a plain text dollar `\$`, use an HTML entity to avoid it being interpreted by MATHJAX, unless are inside a lateximage, in which case it will not be seen by MATHJAX.

```
11075 \let\LWR@origtextdollar\$
11076
11077 \renewcommand*{\$}{%
11078 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
11079 {\LWR@origtextdollar}%
11080 {\HTMLunicode{00024}}%
11081 }
```

File `lwarp_baseline_marker.png` A marker to be used to help *pdfcrop* identify the inline math baseline and width. If either `graphicx` or `graphics` is loaded, this marker is placed at the lower left and lower right corners of the inline math. *pdfcrop* is then able to identify the width of the image, and also the height of an image such as a horizontal dash which does not otherwise touch the baseline.

File `lwarp_baseline_marker.eps`

A marker with alpha or opacity of 0% is not registered by *pdfcrop*, so the marker is a small square block of 1% alpha, which seems to work while still being effectively invisible in the final SVG image.

If `graphicx` is loaded, this marker is sized as a tiny 1 sp square. If `graphics` is loaded, this marker is used at its default size of around .25 pt. If neither `graphics` package is loaded, the marker is replaced by a 10 sp horizontal space, and there is no assistance for determining baseline or width of the inline math image. The best results are obtained when using `graphicx`.

`\LWR@addbaselinemarker` Places a small marker in an svg inline image. If `graphics` or `graphicx` are loaded, the marker is a mostly transparent image. If neither is loaded, no marker is used.

```
11082 \AtBeginDocument{
11083
11084 \ifpdf
11085 \newcommand*\LWR@baselinename}{lwarp_baseline_marker.png}
11086 \else
11087 \ifXeTeX
11088 \newcommand*\LWR@baselinename}{lwarp_baseline_marker.png}
11089 \else
11090 \newcommand*\LWR@baselinename}{lwarp_baseline_marker.eps}
11091 \fi
11092 \fi
11093
11094 \IfFileExists{\LWR@baselinename}%
11095 {
11096 \@ifpackageloaded{graphicx}{
11097 \newcommand*\LWR@addbaselinemarker}{%
11098 \LWR@originincludegraphics{\LWR@baselinename}%
11099 }
11100 }{
11101 \@ifpackageloaded{graphics}{
11102 \newcommand*\LWR@addbaselinemarker}{%
11103 \LWR@originincludegraphics{\LWR@baselinename}%

```

```

11104 }
11105 }{
11106 \newcommand*\LWR@addbaselinemarker}{%
11107 \global\booltrue{LWR@warnbaselinemarker}%
11108 }
11109 \AtEndDocument{
11110 \ifbool{LWR@warnbaselinemarker}{
11111 \PackageWarningNoLine{lwarp}{%
11112 Load graphicx or graphics for improved\MessageBreak
11113 SVG math sizing and baselines%
11114 }
11115 }{}
11116 }
11117 }
11118 }
11119 }{% lwarp_baseline_marker.png or .eps is not present
11120 \newcommand*\LWR@addbaselinemarker}{%
11121 \global\booltrue{LWR@warnbaselinemarker}%
11122 }
11123 \AtEndDocument{
11124 \ifbool{LWR@warnbaselinemarker}{
11125 \PackageWarningNoLine{lwarp}{%
11126 File \LWR@baselinename\space is not installed\MessageBreak
11127 alongside the lwarp-*.sty files, so\MessageBreak
11128 SVG math sizing and baselines may not be accurate}
11129 }{}
11130 }
11131 }
11132
11133 }% AtBeginDocument

```

**Bool** LWR@warnbaselinemarker True if the math baseline marker was ever called for, but `graphics` or `graphicx` were not loaded.

```

11134 \newbool{LWR@warnbaselinemarker}
11135 \boolfalse{LWR@warnbaselinemarker}

```

**Bool** LWR@unknownmathsize If `Tikz` or other objects are used inside math mode, the resulting image may exceed the `TEX` box, resulting in an incorrect measurement of the size of the resulting image. If this is so, the `HTML` styles for image size and depth will be neutralized.

```

11136 \newbool{LWR@unknownmathsize}

```

**\LWR@singledollarmeasure**  $\langle \textit{math expression} \rangle$

Measures the size of the image of the math expression.

(In some circumstances `SVG math` is used even if `MATHJAX` is preferred.)

**SVG math:** `\LWR@originsuredmath` is part of argument #4.

**SVG math \ensuremath:** `\LWR@originsuredmath` is part of argument #4.

**SVG dynamic math:** `\LWR@originsuredmath` is part of argument #4.

**Mathjax:** Argument #4 is the contents of the math expression without `\LWR@origensuredmath`. This case is handled above.

**Mathjax \ensuremath:** `\LWR@origensuredmath` is part of argument #4.

**Mathjax dynamic math:** Argument #4 is the contents of the math expression without `\LWR@origensuredmath`, so `\LWR@origensuredmath` is added below.

**\ifmmode:** Included “just in case”.

Factored from `\LWR@subsingledollarsvg`.

```
11137 \newcommand*{\LWR@singledollarmeasure}[1]{%
11138 \begingroup%
```

Temporarily disable formatting while measuring the image parameters:

```
11139 \LWR@restoreorigformatting%
11140 \RenewDocumentEnvironment{lateximage}{s o s o}{\}{\}% inside group
11141 \LWR@print@normalsize%
```

Temporarily set font for the HTML PDF output:

```
11142 \LWR@setcurrentfont%
```

`lateximagedepth` must be nested to avoid generating paragraph tags.  $\mathcal{A}\mathcal{M}\mathcal{S}$  math modifies the `\text` macro such that `\addtocounter` does not always occur as expected. Lower-level code is used instead.

```
11143 \global\advance\c@LWR@lateximagedepth 1\relax%
```

Typeset the math in a box. While doing so, some macros or environments may set `LWR@unknownmathsize`, in which case this will be used to cancel the HTML styles being generated here.

```
11144 \boolfalse{LWR@unknownmathsize}%
11145 \ifmmode%
11146 \global\sbox{\LWR@singledollarbox}{#1}%
11147 \else%
11148 \ifbool{LWR@dynamicmath}{%
11149 \ifbool{mathjax}{%
11150 \global\sbox{\LWR@singledollarbox}%
11151 {\LWR@origensuredmath{#1}}%
11152 }{%
11153 \global\sbox{\LWR@singledollarbox}{#1}%
11154 }%
11155 }{%
11156 \global\sbox{\LWR@singledollarbox}{#1}%
11157 }%
11158 \fi%
```

Add a small and almost transparent marker at the depth of the image.

A math minus sign has the same depth as a plus, even though it does not draw anything below the baseline. This means that *pdfcrop* would crop the image without depth. The marker below the baseline is seen by *pdfcrop* and preserves the depth.

```
11159 \global\sbox{\LWR@singledollarbox}{%
11160 \usebox{\LWR@singledollarbox}%
11161 \raisebox{-\dp\LWR@singledollarbox}{%
11162 \LWR@addbaselinemarker%
11163 }%
11164 }%
```

More low-level code to undo the counter change.

```
11165 \global\advance\c@LWR@lateximagedepth -1\relax% Due to AmS \text macro.
```

Measure the depth:

```
11166 \setlength{\LWR@singledollardepth}{%
11167 \LateximageFontScale\dp\LWR@singledollarbox%
11168 }%
```

Make the length a global change:

```
11169 \global\LWR@singledollardepth=\LWR@singledollardepth%
```

Likewise for width:

```
11170 \setlength{\LWR@singledollarwidth}{%
11171 \LateximageFontScale\wd\LWR@singledollarbox%
11172 }%
11173 \global\LWR@singledollarwidth=\LWR@singledollarwidth%
```

Likewise for total height:

```
11174 \setlength{\LWR@singledollarheight}{%
11175 \LateximageFontScale\ht\LWR@singledollarbox%
11176 }%
11177 \addtolength{\LWR@singledollarheight}{%
11178 \LateximageFontScale\dp\LWR@singledollarbox%
11179 }%
11180 \global\LWR@singledollarheight=\LWR@singledollarheight%

11181 \endgroup%
11182 }
```

```
\LWR@subsingledollarsvg * {<2: alt text>} {<3: add'l hashing>} {<4: math expression>}
```

For inline math. Uses SVG math. The image is measured and adjusted to the baseline of the HTML output, and placed inside a `lateximage`.

(In some circumstances SVG math is used even if MATHJAX is preferred.)

Factored from `\LWR@subsingledollar`.

```
11183 \newcommand*\LWR@subsingledollarsvg}[4]{%
```

Measure the depth, width, and height of the math image:

```
11184 \LWR@singledollarmeasure{#4}%
```

Set a style for the the height or width. The em unit is used so that the math scales according to the user's selected font size.

Start with the greater of the width or the height, biased towards the width:

```
11185 \ifdimgreater{\LWR@singledollarwidth}{.7\LWR@singledollarheight}{%
11186 \def\LWR@singledollarstyle{%
11187 width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
11188 }%
11189 }{%
11190 \def\LWR@singledollarstyle{%
11191 height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
11192 }%
11193 }%
```

If a very narrow width, use the height.

```
11194 \ifdimless{\LWR@singledollarwidth}{.2em}%
11195 {%
11196 \def\LWR@singledollarstyle{%
11197 height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
11198 }%
11199 }%
11200 {}%
```

If very wide and short, use the width:

```
11201 \ifdimless{\LWR@singledollarheight}{.2em}%
11202 {%
11203 \def\LWR@singledollarstyle{%
11204 width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
11205 }%
11206 }%
11207 {}%
```

If there is significant text depth, add the depth to the style.

```
11208 \ifdimgreater{\LWR@singledollardepth}{0.05ex}{%
11209 \def\LWR@singledollardepthstyle{%
11210 \ ; % extra space
11211 \LWR@print@mbx{%
11212 vertical-align:-\LWR@convertto{em}{\the\LWR@singledollardepth} em%
11213 } % extra space
11214 }%
11215 }{%
11216 \def\LWR@singledollardepthstyle{%
11217 }%
```

If using certain Tikz actions inside math, the resulting image may exceed the T<sub>E</sub>X boundaries, so the HTML size styles may be incorrect, and must be neutralized.

```

11218 \ifbool{LWR@unknownmathsize}{%
11219 \def\LWR@singledollarstyle{}%
11220 \def\LWR@singledollardepthstyle{}%
11221 }{}%

```

Create the `lateximage` using the alternate tag and the computed size and depth. The star causes `lateximage` to use an MD5 hash as the filename. When hashing, also include the current font and color in the hash.

```

11222 \ifbool{LWR@dynamicmath}{%
11223 \LWR@traceinfo{subsingledollar: dynamic}%
11224 \begin{lateximage}% no hashing
11225 [\MathImageAltText]% alt tag
11226 []% no add'l hashing
11227 [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
11228 }{% not dynamic math
11229 \LWR@traceinfo{subsingledollar: static}%
11230 \IfValueTF{#1}{% #1 True
11231 \LWR@findcurrenttextcolor% sets \LWR@tempcolor

```

Support for `xfakebold`:

```

11232 \ifbool{LWR@xfakebold}%
11233 {\def\LWR@tempone{Y}}%
11234 {\def\LWR@tempone{N}}%

11235 \begin{lateximage}*% use hashing
11236 [#2]% alt
11237 *% do not add open/closing braces
11238 [% addl' hashing
11239 #3%
11240 FM\LWR@f@family%
11241 SR\LWR@f@series%
11242 SH\LWR@f@shape%
11243 SHC\LWR@f@shapecaps%
11244 CL\LWR@tempcolor%
11245 FB\LWR@tempone% xfakebold
11246]%
11247 [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
11248 }{% #1 False
11249 \begin{lateximage}% no hashing
11250 [#2]% alt
11251 []% no add'l hashing
11252 [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
11253 }%
11254 }% not dynamic math

```

Place small and almost transparent markers on the baseline at the left and right edges of the image. These markers are seen by *pdfcrop*, and force vertically-centered objects such as a dash to be raised off the baseline in the cropped image, and also force the total width and left/right margins to be correct. (Except that in some fonts a

character may exceed the bounding box, and thus may appear wider than expected when converted to an image.)

11255     \LR@addbaselinemarker%

Support for xfakebold:

11256     \LR@applyxfakebold%

Typeset the contents:

11257     \usebox{\LR@singledollarbox}%

The closing baseline marker:

11258     \LR@addbaselinemarker%

11259     \end{lateximage}%

11260 %

11261 }

`\LR@subsingledollar * {<2: alt text>} {<3: add'l hashing>} {<4: math expression>}`

For inline math. Uses MathJax, or for SVG math the image is measured and adjusted to the baseline of the HTML output, and placed inside a `lateximage`.

**SVG math:** `\LR@origensuredmath` is part of argument #4.

**SVG math \ensuremath:** `\LR@origensuredmath` is part of argument #4.

**SVG dynamic math:** `\LR@origensuredmath` is part of argument #4.

**Mathjax:** Argument #4 is the contents of the math expression without `\LR@origensuredmath`. This case is handled above.

**Mathjax \ensuremath:** `\LR@origensuredmath` is part of argument #4.

**Mathjax dynamic math:** Argument #4 is the contents of the math expression without `\LR@origensuredmath`, so `\LR@origensuredmath` is added below.

[image filename hashing](#) If starred, a hashed filename is used. If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing

argument in order to make the hash unique according to the set of options, even if the simple alt tag is still the same.

```

11262 \newlength{\LWR@singledollarwidth}
11263 \newlength{\LWR@singledollarheight}
11264 \newlength{\LWR@singledollardepth}
11265
11266 \newsavebox{\LWR@singledollarbox}
11267
11268 \NewDocumentCommand{\LWR@subsingledollar}{s m m}{%
11269 \LWR@traceinfo{\LWR@subsingledollar}%

11270 \ifnumcomp{\value{\LWR@lateximagedepth}}{>}{0}%
11271 {%
11272 \LWR@traceinfo{\LWR@subsingledollar: already in a lateximage}%
11273 #4% contents
11274 }%
11275 {% not in a lateximage
11276 \begingroup%
```

Support for xfakebold:

```

11277 \LWR@applyxfakebold%
```

MathJax cannot parse the often complicated TEX expressions which appear in the various uses of `\ensuredmath`. `\ensuredmath` forces the alt tag to “(math image)”, as translated according to `\MathImageAltText`. If this is the case, force the use of a `lateximage` even if MathJax. Likewise for `siunitx` if `parse-numbers=false`.

If MathJax, or if formatting math for a word processor, and not `\ensuredmath`, and not a dynamic math expression, print the math expression:

```

11278 \ifboolexpr{%
11279 (
11280 bool{mathjax} or
11281 (bool{FormatWP} and bool{WPMarkMath})
11282) and
11283 (not test {
11284 \ifstrequal {#2}% from \ensuredmath
11285 {\AltTextOpen\MathImageAltText\AltTextClose}
11286 }
11287) and
11288 (not bool{\LWR@dynamicmath})
11289 }%
```

For MATHJAX, print the math between `\(` and `\)`:

```

11290 {%
11291 \LWR@traceinfo{\LWR@subsingledollar: Mathjax}%
11292 {%
11293 \textbackslash(
11294 {%
```

`\ifmmode` to avoid error about `\ttfamily` inside math mode in the case of nested math, ex. equation with `tcolorbox` with math.

```

11295 \ifmmode\else\LWR@print@ttfamily\fi%
11296 \LWR@HTMLsanitize{#4}%
11297 }%
11298 \textbackslash)%
11299 }%
11300 }% mathjax

```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the  $\LaTeX$  code, and a `css` style to control the baseline adjustment.

```

11301 {% not mathjax
11302 \LWR@traceinfo{%
11303 LWR@subsingledollar: NOT mathjax, or is ensuremath, or is dynamic%
11304 }%
11305 \LWR@subsingledollarsvg{#1}{#2}{#3}{#4}%
11306 }% not mathjax
11307 \endgroup%
11308 }% not in a lateximage

```

Clear the single-use `alt` text:

```

11309 \gdef\LWR@ThisAltText{}%
11310 \LWR@traceinfo{LWR@subsingledollar: done}%
11311 }

```

```

11312 \LetLtxMacro\LWR@origdollar$
11313 \LetLtxMacro\LWR@secondorigdollar$% balance for editor syntax highlighting

```

```

11314 \LetLtxMacro\LWR@origopenparen\(

11315 \LetLtxMacro\LWR@origcloseparen\

11316 \LetLtxMacro\LWR@origopenbracket\

11317 \LetLtxMacro\LWR@origclosebracket\]

```

**\$** Redefine the dollar sign to place math inside a `lateximage`, or use `MATHJAX`:  
**\$\$**

```

11318 \begingroup
11319 \catcode'\$=\active%
11320 \protected\gdef$\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%

```

Used by `chemformula` to escape single-dollar math:

```

11321 \protected\gdef\LWR@newsingledollar{\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%

```

`\LWR@doubledollar` Redefine the double dollar sign to place math inside a `lateximage`, or use `MATHJAX`:

```

11322 \protected\gdef\LWR@doubledollar$#1$${%

```

If `MATHJAX` or formatting for a word processor, print the  $\LaTeX$  expression:

```

11323 \ifboolexpr{bool{mathjax} or (bool{FormatWP} and bool{WPMarkMath}) }%

```

For MATHJAX, print the math between `\[` and `\]`:

```
11324 {
11325
11326 \textbackslash[%
11327 {\LWR@print@ttfamily\LWR@HTMLsanitize{#1}}%
11328 \textbackslash]
11329
11330 }% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the L<sup>A</sup>T<sub>E</sub>X code:

```
11331 {% not mathjax
11332 \begin{BlockClass}{displaymath}%
11333 \LWR@newautoidanchor%
11334 \booltrue{LWR@indisplaymathimage}%
11335 \begin{lateximage}%
11336 [%
11337 \textbackslash[[] % extra space
11338 \LWR@HTMLsanitize{#1} % extra space
11339 \textbackslash[]}%
11340]%
11341 *% do not add open/closing braces
```

Support for `xfakebold`:

```
11342 \LWR@applyxfakebold%

11343 \LWR@origdollar\LWR@origdollar#1\LWR@origdollar\LWR@origdollar%
11344 \end{lateximage}%
11345 \end{BlockClass}%
11346 }% not mathjax
```

Clear the single-use `alt` text:

```
11347 \gdef\LWR@ThisAltText{}%
11348 }%
```

`\LWR@singledollar` `{<alt text>}{<math expression>}`

```
11349 \protected\gdef\LWR@singledollar#1${%
11350 \ifbool{mathjax}{%
11351 \LWR@subsingledollar*%
11352 {% alt tag
11353 \textbackslash(%
11354 \LWR@HTMLsanitize{#1} % extra space
11355 \textbackslash)%
11356 }%
11357 {singledollar}% add'l hashing
11358 {#1}% contents
11359 }{% not mathjax
11360 \LWR@subsingledollar*%
11361 {% alt tag
11362 \textbackslash(%
```

```

11363 \LWR@HTMLsanitize{#1} % extra space
11364 \textbackslash)%
11365 }%
11366 {singledollar}% add'l hashing
11367 {\LWR@origensuredmath{#1}}% contents
11368 }% not mathjax

```

Clear the single-use alt text:

```

11369 \gdef\LWR@ThisAltText{}%
11370 }

```

\( Redefine to the above dollar macros.

\[

```

11371 \AtBeginDocument{
11372 \protected\gdef\(#1\){$#1$}
11373 \protected\gdef\[#1\]{$$#1$$}
11374 }
11375
11376 \endgroup% active $

```

```

11377 \AtBeginDocument{
11378 \LetLtxMacro\LWR@openbracketnormal\[
11379 \LetLtxMacro\LWR@closebracketnormal\]
11380 }

```

\@ensuredmath {*expression*}

If MathJax, a `lateximage` is used, since `\ensuremath` is often used for complex T<sub>E</sub>X expressions which MathJax may not render. If `svg math`, a hashed file is used with a simple alt tag, but additional hashing provided by the contents.

```

11381 \LetLtxMacro\LWR@origensuredmath\@ensuredmath
11382
11383 \renewcommand{\@ensuredmath}[1]{%
11384 \ifbool{mathjax}{%
11385 \LWR@subsingledollar*{\AltTextOpen\MathImageAltText\AltTextClose}%
11386 {%
11387 \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
11388 }%
11389 {%
11390 \relax%
11391 \LWR@origensuredmath{#1}%
11392 }%
11393 }{% SVG math

```

If already inside a `lateximage` in `math` mode, continue as-is.

```

11394 \ifmmode%
11395 \LWR@origensuredmath{#1}%
11396 \else%

```

Create an inline math `lateximage` with a simple `alt` tag and additional hashing according to the contents.

```

11397 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
11398 {\LWR@origensuredmath{#1}}%
11399 {%
11400 \LWR@subsingledollar*%
11401 {\AltTextOpen\MathImageAltText\AltTextClose}%
11402 {\protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}}%
11403 {\LWR@origensuredmath{#1}}%
11404 }%
11405 \fi%
11406 }%
```

Clear the single-use `alt` text:

```

11407 \gdef\LWR@ThisAltText{%
11408 }
```

Remember then remove the old `math` and `displaymath` environments:

```

11409 \let\LWR@orig@math\math
11410 \let\LWR@orig@endmath\endmath
11411 \let\LWR@orig@displaymath\displaymath
11412 \let\LWR@orig@enddisplaymath\enddisplaymath
11413
11414 \let\math\relax
11415 \let\endmath\relax
11416 \let\displaymath\relax
11417 \let\enddisplaymath\relax
```

Env `math` Set `math` mode then typeset the body of what was between the `begin/end`. See the `environ` package for `\BODY`.

```

11418 \NewEnviron{math}{\expandafter\(\BODY\)}
```

Env `LWR@displaymathnormal` Set `math` mode then typeset the body of what was between the `begin/end`. See the `environ` package for `\BODY`.

```

11419 \NewEnviron{LWR@displaymathnormal}{\expandafter\[\BODY\]\@ignoretrue}
```

Set the default `displaymath` to the normal version:

```

11420 \LetLtxMacro\displaymath\LWR@displaymathnormal%
11421 \LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
```

Env `LWR@displaymathother` A version of `displaymath` which can handle complicated objects, but does not supply `MATHJAX` or `HTML alt` tags.

```

11422 \newenvironment{LWR@displaymathother}
11423 {%
```

```

11424 \begin{BlockClass}{displaymath}%
11425 \LWR@newautoidanchor%
11426 \booltrue{LWR@indisplaymathimage}%
11427 \begin{lateximage}%
11428 [\MathImageAltText]%
11429 \LWR@origdollar\LWR@origdollar%
11430 }
11431 {%
11432 \LWR@origdollar\LWR@origdollar%
11433 \end{lateximage}%
11434 \end{BlockClass}%
11435 }

```

Env LWR@equationother A version of `displaymath` which can handle complicated objects, but does not supply `MATHJAX` or `HTML alt` tags.

```

11436 \newenvironment{LWR@equationother}
11437 {%
11438 \begin{BlockClass}{displaymathnumbered}%
11439 \LWR@newautoidanchor%
11440 \booltrue{LWR@indisplaymathimage}%
11441 \begin{lateximage}[\MathImageAltText]%
11442 \LWR@origequation%
11443 }
11444 {%
11445 \LWR@origendequation%
11446 \end{lateximage}%
11447 \end{BlockClass}%
11448 }

```

## 81.4 MATHJAX support

Ctrl LWR@nextequation Used to add one to compute the next equation number.

```
11449 \newcounter{LWR@nextequation}
```

Determining how to set `MATHJAX` section and equation numbers. Adjusts for various kinds of `\theequation` to determine `\theMathJaxsection` and `\theMathJaxequation`.

```

11450 \newcommand\LWR@article@theequation{\@arabic\c@equation}
11451
11452 \newcommand\LWR@book@theequation
11453 {\ifnum \c@chapter>\z@ \thechapter.\fi \@arabic\c@equation}
11454
11455
11456 \newcommand\LWR@chapter@theequation{\thechapter.\arabic{equation}}
11457 \newcommand\LWR@section@theequation{\thesection.\arabic{equation}}
11458 \newcommand\LWR@subsection@theequation{\thesubsection.\arabic{equation}}
11459
11460 \AtBeginDocument{
11461 % default per article class:
11462 \newcommand*\theMathJaxsubequations{\0}

```

```

11463 \newcommand*\theMathJaxsection{}
11464 \newcommand*\theMathJaxequation{\arabic{equation}}
11465
11466 \ifdefstrequal{\theequation}{\LWR@article@theequation}
11467 {}{
11468 \ifdefstrequal{\theequation}{\LWR@book@theequation}{
11469 \renewcommand*\theMathJaxsection{\ifnum \c@chapter>\z@ \thechapter.\fi}
11470 }{
11471 \ifdefstrequal{\theequation}{\LWR@subsection@theequation}{
11472 \renewcommand*\theMathJaxsection{\thesubsection{.}}
11473 }{
11474 \ifdefstrequal{\theequation}{\LWR@section@theequation}{
11475 \renewcommand*\theMathJaxsection{\thesection{.}}
11476 }{
11477 \ifdefstrequal{\theequation}{\LWR@chapter@theequation}{
11478 \renewcommand*\theMathJaxsection{\thechapter{.}}
11479 }{% unknown format
11480 \PackageWarningNoLine{lwarp}
11481 {%
11482 Unknown equation tag format for \protect\theequation.\MessageBreak
11483 Article-style equation numbering will be used%
11484 }
11485 }}}}
11486 }

```

`\LWR@syncmathjax` Sets the MATHJAX equation format and number for the following equations.

These MATHJAX commands are printed inside “\{” and “\}” characters. They are printed to HTML output, not interpreted by L<sup>A</sup>T<sub>E</sub>X.

```
11487 \newcommand*\LWR@syncmathjax}{%
```

Tell MATHJAX that the next equation number is the current L<sup>A</sup>T<sub>E</sub>X equation number.

Before each equation, lwarp inserts into the HTML code:

```
\seteqnumber{subequations?}{section}{number}
```

**subequations?** is 0 usually, 1 if inside `amsmath` subequations.

**section** is a string printed as-is, or empty.

**number** is auto-incremented by MATHJAX between equations.

Place the MATHJAX command inside “\{” and “\}” characters, to be printed to HTML, not interpreted by L<sup>A</sup>T<sub>E</sub>X.

```

11488 \LWR@stoppars%
11489 \InlineClass{hidden}{
11490 \textbackslash(%
11491 \textbackslash{}seteqnumber%
11492 \{\theMathJaxsubequations\}%
11493 \{\theMathJaxsection\}%

```

```

11494 \{\theMathJaxequation\}%
11495 \textbackslash)%
11496 }
11497 \LWR@startpars%
11498 }

```

`\LWR@hidelatexequation`  $\langle environment \rangle$   $\langle contents \rangle$

Creates the L<sup>A</sup>T<sub>E</sub>X version of the equation inside an HTML comment.

```

11499 \NewDocumentCommand{\LWR@hidelatexequation}{m +m}{%

```

Stop HTML paragraph handling and open an HTML comment:

```

11500 \LWR@stoppars
11501 \LWR@htmlopencomment
11502

```

Start the L<sup>A</sup>T<sub>E</sub>X math environment inside the HTML comment:

```

11503 \begingroup
11504 \@nameuse{\LWR@orig#1}

```

While in the math environment, restore various commands to their L<sup>A</sup>T<sub>E</sub>X meanings.

```

11505 \LWR@restoreorigformatting
11506 \booltrue{\LWR@insidemathcomment}

```

See `\LWR@htmlmathlabel` in section 81.7.1.

Print the contents of the equation:

```

11507 #2

```

End the L<sup>A</sup>T<sub>E</sub>X math environment inside the HTML comment:

```

11508 \@nameuse{\LWR@origend#1}
11509 \endgroup
11510

```

Close the HTML comment and resume HTML paragraph handling:

```

11511 \LWR@htmlclosecomment
11512 \boolfalse{\LWR@insidemathcomment}
11513 \LWR@startpars
11514 }

```

`\LWR@addmathjax`  $\langle environment \rangle$   $\langle contents \rangle$

Given the name of a math environment and its contents, create a MATHJAX instance. The contents are printed to HTML output, not interpreted by L<sup>A</sup>T<sub>E</sub>X.

```

11515 \NewDocumentCommand{\LWR@addmathjax}{m +m}{%

```

Enclose the MATHJAX environment inside printed “\ (“ and “\)” characters.

```
11516 \LWR@origtilde\LWR@orignewline
```

Print the environment name and contents, sanitizing for HTML special characters.

```
11517 {%
11518 \LWR@print@ttfamily%
11519 \textbackslash{}begin\{#1\}
11520 \LWR@orignewline%
11521 \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#2}}%
11522 \LWR@orignewline%
11523 \textbackslash{}end\{#1\}
11524 }%

11525 \LWR@orignewline
11526 }
```

## 81.5 Equation environment

Remember existing equation environment, after redefined by amsmath, if loaded.

```
11527 \AtBeginDocument{
11528 \let\LWR@origequation\equation
11529 \let\LWR@origendequation\endequation
11530 \csletcs{LWR@origequation*}{equation*}
11531 \csletcs{LWR@origendequation*}{endequation*}
11532 }
```

```
\LWR@doequation {<env contents>} {<env name>}
```

For SVG math output, the contents are typeset using the original equation inside a `lateximage`, along with an `<alt>` tag containing a detokenized copy of the  $\LaTeX$  source for the math.

For MATHJAX output, the contents are typeset in an original equation environment placed inside a HTML comment, with special processing for `\labels`. The contents are also printed to the HTML output for processing by the MATHJAX script.

```
11533 \newcommand*{\LWR@doequation}[2]{%
11534
```

If `mathjax` or `FormatWP`, print the  $\LaTeX$  expression:

```
11535 \ifboolexpr{bool{mathjax} or (bool{FormatWP} and bool{WPMarkMath}) }%
```

MATHJAX output:

```
11536 {
```

Print commands to synchronize MATHJAX's equation number and format to the current L<sup>A</sup>T<sub>E</sub>X chapter/section and equation number:

```
11537 \LWR@syncmathjax%
```

Print the L<sup>A</sup>T<sub>E</sub>X math inside an HTML comment:

```
11538 \LWR@hidelatexequation{#2}{#1}
11539 }
```

SVG output: Create the lateximage along with an HTML <alt> tag having an equation number, the L<sup>A</sup>T<sub>E</sub>X equation environment commands, and the contents of the environment's \BODY.

```
11540 {% not mathjax
```

Begin the lateximage with an <alt> tag containing the math source:

```
11541 \ifstrequal{#2}{equation*}{%
11542 \begin{BlockClass}{displaymath}%
11543 }{%
11544 \begin{BlockClass}{displaymathnumbered}%
11545 }%
11546 \LWR@newautoidanchor%
11547 \booltrue{LWR@indisplaymathimage}%
11548 \begin{lateximage}[%
11549 \ifstrequal{#2}{equation*}{%
11550 \ifdefequal{\LWR@equationtag}{\theequation}{%
11551 % no tag was given
11552 }{%
11553 (\LWR@equationtag) % tag was given
11554 }%
11555 }{%
11556 (\LWR@equationtag) % automatic numbering
11557 }%
11558 \textbackslash{begin\{#2\}} % extra space
11559 \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#1}} % extra space
11560 \textbackslash{end\{#2\}}%
11561]*% alt tag
```

Support for xfakebold:

```
11562 \LWR@applyxfakebold%
```

Create the actual L<sup>A</sup>T<sub>E</sub>X-formatted equation inside the lateximage using the contents of the environment.

```
11563 \@nameuse{LWR@orig#2}%
11564 #1 contents collected by \collect@body
11565 \@nameuse{LWR@origend#2}%
11566 \end{lateximage}%
11567 \end{BlockClass}%
11568 }% not mathjax
```

Clear the single-use alt text:

```
11569 \gdef\LWR@ThisAltText{}%
11570 }
```

After the environment, if MATHJAX, print the math to the HTML output for MATHJAX processing. If a footnote is used, sync the footnote counter before, then unsync after for non-equation environments, as defined next.

```
11571 \newcommand*\LWR@doendequation}[1]{%
11572 \ifboolexpr{bool{mathjax} or (bool{FormatWP} and bool{WPMarkMath}) }%
11573 {%
11574 \IfSubStr{\detokenize\expandafter{\BODY}}{\detokenize{note}}{%
11575 \InlineClass{hidden}{\LWR@syncnotenumbers}%
11576 \LWR@addmathjax{#1}{\BODY}%
11577 \InlineClass{hidden}{\LWR@syncnotenames}%
11578 }{%
11579 \LWR@addmathjax{#1}{\BODY}%
11580 }%
11581 }{%
11582 }
```

Clear the single-use alt text:

```
11583 \gdef\LWR@ThisAltText{}%
11584 }
```

The following are used to synchronize footnote marks and related to MATHJAX if *\*note\** is used inside the MATHJAX expression. The counter is read from L<sup>A</sup>T<sub>E</sub>X then defined into MATHJAX for use during the following equation. After the equation, the MATHJAX value is returned to the text from `\footnotename`. Other notes may be added by appending to `\LWR@syncnotenumbers` and `\LWR@syncnotenames`.

```
\LWR@synconenotenummer {<MATHJAX variable>} {<mark>}
```

```
11585 \newcommand*\LWR@synconenotenummer}[2]{%
11586 \textbackslash(
11587 \textbackslash{}def\textbackslash{}#1\{#2\}
11588 \textbackslash)
11589 }
```

`\LWR@syncnotenumbers` Assignments to make.

```
11590 \newcommand*\LWR@syncnotenumbers{\LWR@synconenotenummer{\LWRfootnote}{\thefootnote}}
```

```
\LWR@synconenotename {<MATHJAX variable>} {<text>}
```

```
11591 \newcommand*\LWR@synconenotename}[2]{%
11592 \textbackslash(
11593 \textbackslash{}def\textbackslash{}#1\{#2\}
11594 \textbackslash)
11595 }
```

`\LWR@syncnotenames` Assignments to make.

```
11596 \newcommand*\LWR@syncnotenames{\LWR@synconenotename\LWRfootnote}{\footnotename}}
```

Remove existing equation environment:

```
11597 \AtBeginDocument{
11598 \let\equation\relax
11599 \let\endequation\relax
11600 \csletcs{equation*}{relax}
11601 \csletcs{endequation*}{relax}
11602 }
```

Env `equation` The new equation environment is created with `\NewEnviron` (from the `environ` package), which stores the contents of its environment in a macro called `\BODY`.

```
11603 \AtBeginDocument{
11604 \NewEnviron{equation}%
11605 {\LWR@doequation{\BODY}{equation}}%
11606 [\LWR@doendequation{equation}]
11607
11608 \LetLtxMacro\LWR@equationnormal\equation
11609 \LetLtxMacro\endLWR@equationnormal\endequation
11610 }% AtBeginDocument
```

Env `equation*`

```
11611 \AtBeginDocument{
11612 \NewEnviron{equation*}%
11613 {\LWR@doequation{\BODY}{equation*}}%
11614 [\LWR@doendequation{equation*}]
11615
11616 \csletcs{LWR@equationnormalstar}{equation*}
11617 \csletcs{LWR@endequationnormalstar}{endequation*}
11618 }% AtBeginDocument
```

Remember the “less” version of `equation`, which uses `MATHJAX` and `alt` tags, but does not support complicated contents such as some `Tikz` expressions.

```
11619 \AtBeginDocument{
11620 \LetLtxMacro\LWR@equationless\equation
11621 \LetLtxMacro\endLWR@equationless\endequation
11622 \csletcs{LWR@equationlessstar}{equation*}
11623 \csletcs{LWR@endequationlessstar}{endequation*}
11624 }
```

## 81.6 `\displaymathnormal` and `\displaymathother`

`\displaymathnormal` By default, or when selecting `\displaymathnormal`, `MATHJAX` math display environments print their contents as text into `HTML`, and `SVG` display math environments

render their contents as SVG images and use their contents as the `alt` tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Tikz pictures, compilation will fail.

`\displaymathother` When selecting `\displaymathother`, it is assumed that the contents are more complicated than “pure” math. An example is an elaborate Tikz picture, which will not render in MATHJAX and will not make sense as an HTML `alt` tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML `alt` tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Tikz pictures are more likely to compile successfully.

`\displaymathnormal` Use when display math environments have simple math which is to be sent to MATHJAX or included in HTML `alt` tags.

```
11625 \newcommand*{\displaymathnormal}{%
11626 \ifbool{LWR@origmathjax}{\booltrue{mathjax}}{\boolfalse{mathjax}}%
11627 \LetLtxMacro\[\LWR@openbracketnormal%
11628 \LetLtxMacro\]\LWR@closebracketnormal%
11629 \LetLtxMacro\displaymath\LWR@displaymathnormal%
11630 \LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
11631 \LetLtxMacro\equation\LWR@equationnormal%
11632 \LetLtxMacro\endequation\endLWR@equationnormal%
11633 \csletcs{equation*}{LWR@equationnormalstar}%
11634 \csletcs{endequation*}{LWR@endequationnormalstar}%
11635 }
```

`\displaymathother` Use when display math environments have complicated objects which will not work with MathJax or should not be included in HTML `alt` tags. Complicated contents are more likely to compile correctly.

```
11636 \newcommand*{\displaymathother}{%
11637 \boolfalse{mathjax}%
11638 \LetLtxMacro\displaymath\LWR@displaymathother%
11639 \LetLtxMacro\enddisplaymath\endLWR@displaymathother%
11640 \LetLtxMacro\[\LWR@displaymathother%
11641 \LetLtxMacro\]\endLWR@displaymathother%
11642 \LetLtxMacro\equation\LWR@equationother%
11643 \LetLtxMacro\endequation\endLWR@equationother%
11644 \csletcs{equation*}{displaymath}%
11645 \csletcs{endequation*}{enddisplaymath}%
11646 }
```

```
11647 \end{warpHTML}
```

**for PRINT output:** 11648 `\begin{warpprint}`

Print-mode versions:

```
11649 \newcommand*{\displaymathnormal}{}
11650 \newcommand*{\displaymathother}{}

11651 \end{warpprint}
```

for HTML output: 11652 `\begin{warpHTML}`}

## 81.7 AMS Math environments

### 81.7.1 Support macros

Bool `LWR@amsmultline` True if processing a multiline environment.

To compensate for `multline`-specific code, `LWR@amsmultline` is used to add extra horizontal space in `\LWR@htmlmathlabel` if is used in an `amsmath` environment which is not a `multline` environment and not an equation.

```
11653 \newbool{LWR@amsmultline}
11654 \boolfalse{LWR@amsmultline}
```

`\LWR@beginhideamsmath` Starts hiding  $\LaTeX$  math inside an HTML comment.

```
11655 \newcommand*{\LWR@beginhideamsmath}{
11656 \LWR@stoppars
11657 \LWR@origtilde\LWR@orignewline
11658 \LWR@htmlopencomment
11659
11660 \begingroup
11661 \LWR@restoreorigformatting
11662 \booltrue{LWR@insidemathcomment}
11663 }
```

`\LWR@endhideamsmath` Ends hiding  $\LaTeX$  math inside an HTML comment.

```
11664 \newcommand*{\LWR@endhideamsmath}{
11665 \endgroup
11666
11667 \LWR@htmlclosecomment
11668 \boolfalse{LWR@insidemathcomment}
11669 \LWR@orignewline
11670 \LWR@startpars
11671 }
```

### 81.7.2 Environment patches

The `amsmath` environments already collect their contents in `\@envbody` for further processing. `eqnarray` is not an  $\mathcal{AMS}$  package, and thus requires special handling.

For `svg math`: Each environment is encapsulated inside a `lateximage` environment, along with a special optional argument of `\LWR@amsmathbody` or `\LWR@amsmathbodynumbered` telling `lateximage` to use as the HTML `<alt>` tag the environment's contents which were automatically captured by the  $\mathcal{AMS}$  environment.

For MATHJAX: Each environment is syched with L<sup>A</sup>T<sub>E</sub>X's equation numbers, typeset with L<sup>A</sup>T<sub>E</sub>X inside an HTML comment, then printed to HTML output for MATHJAX to process.

Env eqnarray This environmnet is not an  $\mathcal{A}\mathcal{M}\mathcal{S}$  environment and thus its body is not automatically captured, so the `environ` package is used to capture the environment into `\BODY`.

```
11672 \let\LWR@origeqnarray\eqnarray
11673 \let\LWR@origendeqnarray\endeqnarray
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
11674 \newbool{LWR@numbereqnarray}
11675 \booltrue{LWR@numbereqnarray}
```

Common code used by eqnarray and Beqnarray (from fancybox):

```
11676 \newcommand{\LWR@eqnarrayfactor}{%
```

If mathjax or FormatWP, print the L<sup>A</sup>T<sub>E</sub>X expression:

```
11677 \ifboolexpr{bool{mathjax} or (bool{FormatWP} and bool{WPMarkMath}) }%
11678 {%
```

If MATHJAX, the environment contents (the `\BODY`) are executed in a HTML comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for MATHJAX to interpret:

```
11679 \LWR@syncmathjax%
11680 \boolfalse{LWR@amsmultline}%
11681 \ifbool{LWR@numbereqnarray}%
11682 {%
```

If numbering the equations, execute a copy inside an HTML comment block:

```
11683 \LWR@beginhideamsmath%
11684 \LWR@origeqnarray%
11685 \BODY%
11686 \LWR@origendeqnarray%
11687 \LWR@endhideamsmath%
```

Then print the (sanitized) contents to the output for MATHJAX to interpret:

```
11688 \LWR@addmathjax{eqnarray}{\BODY}%
11689 }%
11690 {% not LWR@numbereqnarray
```

If not numbering equations, just create the contents for MATHJAX:

```
11691 \LWR@addmathjax{eqnarray*}{\BODY}%
11692 }% LWR@numbereqnarray
```

```

11693 }% mathjax
11694 {% not mathjax
11695 \ifbool{LWR@numbreqnarray}%
11696 {%

```

For numbered svg equations, first create a `lateximage` with an `alt` attribute containing sanitized copy of the source code:

```

11697 \begin{BlockClass}{displaymathnumbered}%
11698 \LWR@newautoidanchor%
11699 \booltrue{LWR@indisplaymathimage}%
11700 \begin{lateximage}[(\LWR@startingequationtag\textendash\LWR@equationtag)%
11701 \LWR@addmathjax{eqnarray}{\BODY}]*%

```

Support for `xfakebold`:

```

11702 \LWR@applyxfakebold%

```

Create the image contents using an actual `eqnarray`:

```

11703 \LWR@origeqnarray%
11704 \BODY%
11705 \LWR@origendeqnarray%
11706 \end{lateximage}%
11707 \end{BlockClass}%
11708 }%
11709 {% not LWR@numbreqnarray

```

If not numbered, do the same, but an extra `\nonumber` seems to be required:

```

11710 \begin{BlockClass}{displaymath}%
11711 \LWR@newautoidanchor%
11712 \booltrue{LWR@indisplaymathimage}%
11713 \begin{lateximage}[(\LWR@addmathjax{eqnarray*}{\BODY})*%

```

Support for `xfakebold`:

```

11714 \LWR@applyxfakebold%

11715 \def\@eqnrcr{\nonumber\@seqnrcr}
11716 \csuse{LWR@origeqnarray}%
11717 \BODY%
11718 \nonumber\csuse{LWR@origendeqnarray}%
11719 \end{lateximage}%
11720 \end{BlockClass}%
11721 }% LWR@numbreqnarray
11722 }% not mathjax

```

Default to number equations in the future:

```

11723 \booltrue{LWR@numbreqnarray}%

```

Clear the single-use `alt` text:

```
11724 \gdef\LWR@ThisAltText{%
11725 }
```

eqnarray itself is made with a blank line before and after to force it to be on its own line:

```
11726 \RenewEnviron{eqnarray}
11727 {%
11728
11729 \LWR@eqnarrayfactor
11730
11731 }
```

The starred version is patched to turn off the numbering:

```
11732 \csgpreto{eqnarray*}{\boolfalse{LWR@numbereqnarray}}
11733 \end{warpHTML}
```

## 82 Lateximages

### 82.1 Description

**Env lateximage** A lateximage is a piece of the document which is typeset in L<sup>A</sup>T<sub>E</sub>X then included in the HTML output as an image. This is used for math if `svg math` is chosen, and also for the `picture`, `tikzpicture`, and other environments.

Before typesetting the lateximage a large number of formatting, graphics, and symbols-related macros are temporarily restored to their print-mode meaning by `\LWR@restoreorigformatting`. (See section 79.)

A lateximage is typeset on its own PDF page inside an HTML comment which starts on the preceding page and ends on following page, and instructions are written to `lateximage.txt` for `lwarpmk` to extract the lateximage from the page of the PDF file then generate an accompanying `.svg` file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML `<span>` is created to hold both the HTML comment, which will have the `pdfotext` conversion, and also the link to the final `.svg` image.

A L<sup>A</sup>T<sub>E</sub>X label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

**HTML alt tag** The HTML `alt` tag is set to the L<sup>A</sup>T<sub>E</sub>X source for `svg math`, some chemistry expressions, and perhaps some other expressions which make sense for text copy/paste. In some other cases, the `alt` tag is set according to the package name.

When creating an `svg math` image, its HTML `alt` tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after

`\inlinemathother`, where the contents require a unique image for each instance of the same expression, the `alt` tag is set to `\MathImageAltText`, along with `\AltTextOpen` and `\AltTextClose`, and the image is not reused.

This `alt` expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “math image”, and it may be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `svg` math images.

For many packages, the output is placed inside a `lateximage` with an `HTML alt` tag set to the package name followed by `\PackageDiagramAltText`. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is “diagram”, and may it be changed according to the document’s language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following package diagrams.

**svg image font size** For the `lateximage` environment, the size of the math and text used in the `svg` image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline `svg` math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

## 82.2 Support counters and macros

**for HTML output:** 11734 `\begin{warpHTML}`

Ctrl LWR@`lateximagenumber` Sequence the images.

```
11735 \newcounter{LWR@lateximagenumber}
11736 \setcounter{LWR@lateximagenumber}{0}
```

Ctrl LWR@`lateximagedepth` Do not create `\lateximage` inside of `\lateximage`.

```
11737 \newcounter{LWR@lateximagedepth}
11738 \setcounter{LWR@lateximagedepth}{0}
```

A few utility macros to write special characters:

```
11739 \edef\LWR@hashmark{\string#} % for use in \write
11740 \edef\LWR@percent{\@percentchar} % for use in \write
```

Ctrl LWR@`LIPage` Used to reference the PDF page number of a `lateximage` to be written into `<project>-images.txt`.

```
11741 \newcounter{LWR@LIPage}
```

```
11742 \end{warpHTML}
```

## 82.3 Font size

**for HTML & PRINT:** 11743 \begin{warpall}

`\LateximageFontSizeName` Declares how large to write text in `\lateximages`. The `.svg` file text size should blend well with the surrounding HTML text size.

 **no backslash** *Do not include the leading backslash in the name.*

```
11744 \newcommand*{\LateximageFontSizeName}{normalsize}
```

`\LateximageFontScale` Declares how large to scale inline SVG math images. The `.svg` file text size should blend well with the surrounding HTML text size. The default is 1, but it may be redefined as needed depending on the HTML font.

```
11745 \newcommand*{\LateximageFontScale}{1}
```

```
11746 \end{warpall}
```

## 82.4 Equation numbers

**for HTML output:** 11747 \begin{warpHTML}

`Ctrl LWR@startingequation` For use with `lateximage` and multi-line numbered equations. Remembers the next equation number so that it may be printed in the alt tag.

```
11748 \newcounter{LWR@startingequation}
11749
11750 \ifundefined{chapter}
11751 {
11752 \renewcommand{\theLWR@startingequation}{%
11753 \arabic{LWR@startingequation}%
11754 }
11755 }
11756 {% chapter defined
11757 \renewcommand{\theLWR@startingequation}{%
11758 \ifnumcomp{\value{chapter}}{>}{0}{\arabic{chapter}.}%
11759 \arabic{LWR@startingequation}%
11760 }
11761 }
```

`Bool LWR@isstartingequation` True for the first equation tag, false for later tags in the same environment.

```
11762 \newbool{LWR@isstartingequation}
```

`\LWR@startingequationtag` Prints the starting equation number or tag.

```
11763 \let\LWR@startingequationtag\theLWR@startingequation
```

`\LWR@equationtag` Prints the ending equation number or tag.

This is reset by `lateximage`, may be temporarily overwritten by `\tag` calling `\LWR@remembertag`.

```
11764 \newcommand*\LWR@equationtag{}
```

Only if `svg math`, patch `\tag` after packages have loaded, in case someone else modified `\tag`.

```
11765 \AtBeginDocument{
11766
11767 \ifbool{mathjax}{}{% not mathjax
```

`\LWR@remembertag` `{<tag>}`

For use inside the math environments while using `svg math`. Sets `\theLWR@startingequation` and `\theequation` to the given tag.

```
11768 \NewDocumentCommand{\LWR@remembertag}{m}{%
11769 \ifbool{LWR@isstartingequation}%
11770 {%
11771 \global\boolfalse{LWR@isstartingequation}%
11772 \xdef\LWR@startingequationtag{#1}%
11773 }{%
11774 \xdef\LWR@equationtag{#1}%
11775 }%

11776 }% not mathjax
11777 }% AtBeginDocument
```

## 82.5 HTML alt tags

`\LWR@amsmathbody` `{<envname>}` For use inside the optional argument to a `lateximage` to add the contents of a AMS math environment to the `<alt>` tag.

```
11778 \newcommand*\LWR@amsmathbody[1]
11779 {%
11780 \textbackslash\{begin\}\{#1\} % extra space
11781 \LWR@HTMLSanitizeexpand{\detokenize\expandafter{\the\@envbody}}%
11782 \textbackslash\{end\}\{#1\}%
11783 }
```

`\LWR@amsmathbodynumbered` `{<envname>}` For use inside the optional argument to a `lateximage` to add the contents of a AMS math environment to the `alt` tag, prefixed by the equation numbers.

```

11784 \newcommand*{\LWR@amsmathbodynumbered}[1]
11785 {%
11786 \ifnumcomp{\value{LWR@startingequation}}{=}{\value{equation}}%
11787 {(\LWR@equationtag)}%
11788 {(\LWR@startingequationtag\textendash\LWR@equationtag)} % extra space
11789 \LWR@amsmathbody{#1} % extra space
11790 }

```

## 82.6 lateximage environment

`\LWR@lateximage@oneimageb`  $\langle 1: alt\ text \rangle \langle 2: filename \rangle \langle 3: CSS\ style \rangle$  Creates the image for the lateximage.

```

11791 \newcommand{\LWR@lateximage@oneimageb}[3]{%
11792 \LWR@subinlineimage{#1}{lateximage}%
11793 {%
11794 \LWR@print@mbox{%
11795 \LWR@ImagesDirectory\OSPathSymbol%
11796 #2%
11797 }%
11798 }{svg}{#3}%
11799 }

```

`\LWR@lateximage@oneimage`  $\langle 1: alt\ text \rangle \langle 2: filename \rangle \langle 3: css\ style \rangle \langle 4: delimit? \rangle$

Creates an image for the lateximage, whose alt text depends on the circumstances.

```

11800 \newcommand{\LWR@lateximage@oneimage}[4]{%
11801 \ifdefvoid{\LWR@ThisAltText}{%
11802 \IfBooleanTF{#4}{%
11803 \LWR@lateximage@oneimageb{#1}{#2}{#3}%
11804 }{%
11805 \LWR@lateximage@oneimageb%
11806 {\AltTextOpen#1\AltTextClose}%
11807 {#2}{#3}%
11808 }%
11809 }{%
11810 \LWR@lateximage@oneimageb%
11811 {\AltTextOpen\LWR@ThisAltText\AltTextClose}%
11812 {#2}{#3}%
11813 }%
11814 }

```

Env `lateximage` \*  $\langle 2: <alt>\ tag \rangle$  \*  $\langle 4: add'l\ hashing \rangle$   $\langle 5: css\ style \rangle$

Typesets the contents and then renders the result as an svg file. Star #1 causes the image to be hashed for reuse. Star #3 causes the alt tag to not include `\AltTextOpen` and `\AltTextClose`, for use with math expressions.

The optional `<alt>` tag is included in the HTML code for use with copy/paste.

[image filename hashing](#) If starred, a hashed filename is used. If so, the hash is based on the alt tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated `TEX` expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

File `*_html.aux` A new label is placed into the file `*_html.aux`:

```
\newlabel{LWRlateximage-<BaseJobname>-<number>}{{<x>}{<y>}}
```

This is used to find the image in the `PDF` file, according to its name.

File `*-images.txt` A list of images to generate is created in `<jobname>-images.txt`. Each line has three pipe-delimited fields, containing the `PDF` page number from `<jobname>_html.pdf`, where the image is located, a boolean indicating whether the image is hashed, and the filename of the image. The last line has “end” in each field, and is used to detect an incomplete compile.

```
11815 \catcode'\$=\active%
11816
11817 \NewDocumentEnvironment{lateximage}{s O{\ImageAltText} s O{} O{}}
11818 {%
11819 \LWR@traceinfo{lateximage: starting on \jobname.pdf page \arabic{page}}%
11820 \LWR@traceinfo{lateximage: entering depth is \arabic{LWR@lateximagedepth}}%
```

Nested `lateximages` remain one large `lateximage`:

```
11821 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
```

If nesting inside an already-existing `lateximage`, simply record one more level. `AMS` packages redefine `\addtocounter` to do nothing if inside a `\text`, so lower-level `TEX` macros are used for tracking nested `lateximages`.

```
11822 {%
11823 % \addtocounter{LWR@lateximagedepth}{1}%
11824 \global\advance\c@LWR@lateximagedepth 1\relax% Due to AmS \text macro.
11825 }%
```

Otherwise, this is the outer-most `lateximage`:

```
11826 {% start of outer-most lateximage
```

Remember the next equation number to be allocated, in case it must be printed in a multi-equation environment:

```
11827 \LWR@traceinfo{lateximage: starting outer-most lateximage}%
```

```

11828 \setcounter{LWR@startingequation}{\value{equation}}%
11829 \addtocounter{LWR@startingequation}{1}%
11830 \booltrue{LWR@isstartingequation}%
11831 \let\LWR@startingequationtag\theLWR@startingequation%

```

The default equation tag, unless overwritten by `\tag`:

```

11832 \let\LWR@equationtag\theequation%

```

Starting a new lateximage:

```

11833 \addtocounter{LWR@lateximagenumber}{1}%
11834 \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{LWR@lateximagenumber}}%

```

While inside a lateximage, locally do not use mathjax:

```

11835 \boolfalse{mathjax}%

```

Be sure that are doing a paragraph:

```

11836 \LWR@ensuredoingapar%

```

Next file:

```

11837 \addtocounter{LWR@externalfilecnt}{1}%
11838 \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{LWR@externalfilecnt}}%

```

Figure out what the next page number will be. `\setcounterpageref` assigns `LWR@LIpage` to the page number for the reference `LWR\lateximage-BaseJobname-XXX`:

```

11839 \setcounterpageref{LWR@LIpage}{%
11840 LWR\lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}%
11841 }%
11842 \LWR@traceinfo{lateximage: LWR@LIpage is \arabic{LWR@LIpage}}%

```

Create an HTML span which will hold the comment which contains the *pdftotext* translation of the image's page, and also will hold the link to the .svg file:

```

11843 \LWR@htmltag{span\LWR@indentHTML%
11844 id="lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}"\LWR@indentHTML
11845 class="lateximagesource"\LWR@originewline
11846 }%

```

Write instructions to the `<ImagesDirectory>.txt` file:

```

11847 \LWR@traceinfo{lateximage: about to write to \BaseJobname-images.txt}%
11848 \IfBooleanTF{#1}% starred
11849 {% hash

```

Compute and save the hashed file name for later use:

```

11850 \ifdefvoid{\LWR@ThisAltText}{%
11851 \IfBooleanTF{#3}{%

```

```

11852 \edef\LWR@hashedname{%
11853 \LWR@mdfive{\detokenize\expandafter{#2}-!-#4}%
11854 }%
11855 }{%
11856 \edef\LWR@hashedname{%
11857 \LWR@mdfive{\detokenize\expandafter{\AltTextOpen#2\AltTextClose}-!-#4}%
11858 }%
11859 }%
11860 }{%
11861 \edef\LWR@hashedname{%
11862 \LWR@mdfive{\detokenize\expandafter{\AltTextOpen\LWR@ThisAltText\AltTextClose}-!-#4}%
11863 }%
11864 }%
11865 \LWR@traceinfo{lateximage: hash is \LWR@hashedname}%

```

Write the page, hashing, and hashed name:

```

11866 \immediate\write\LWR@lateximagesfile{%
11867 |\arabic{LWR@LPage}|true|\LWR@hashedname|%
11868 }%
11869 }% hash
11870 {% no hash

```

No hash, so write the page, no hashing, and the image number:

```

11871 \LWR@traceinfo{lateximage: hash false}%
11872 \immediate\write\LWR@lateximagesfile{%
11873 |\arabic{LWR@LPage}|false|\LWR@ImagesName\arabic{LWR@externalfilecnt}|}%
11874 }%
11875 }% no hash

```

Place an open comment tag. This will hide any traces of the lateximage PDF page which were picked up by *pdftotext*.

```

11876 \LWR@traceinfo{lateximage: about to create open comment}%
11877 \LWR@htmlopencomment%

```

One level deeper. At this outer-most lateximage, it is known that this is not being used inside an  $\mathcal{AMS}$  \text, since the outer-most level will never be in math mode.

```

11878 \addtocounter{LWR@lateximagedepth}{1}%

```

Start the new PDF page:

```

11879 \LWR@traceinfo{lateximage: about to create a new page}%
11880 \LWR@maybe@orignewpage%

```

If the current page is larger, typeset the image in a “standard” width page and font size:

```

11881 \LWR@traceinfo{lateximage: about to create minipage}%
11882 \ifdimless{\linewidth}{6in}{%
11883 \LWR@print@minipage{\linewidth}%
11884 }{%

```

```

11885 \LWR@print@minipage{6in}%
11886 }%
11887 \@nameuse{LWR@print@LateximageFontSizeName}%

```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for \hspace, etc. inside a lateximage.

```

11888 \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
11889 \LWR@restoreorigformatting%

```

Use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```

11890 \def\@mpfn{footnote}%
11891 \def\thempfn{\thefootnote}%
11892 \LetLtxMacro\@footnotetext\LWR@footnotetext%

```

Create the LWRlateximage<number> label:

```

11893 \LWR@traceinfo{lateximage: about to create label}%
11894 \LWR@orig@label{LWRlateximage-BaseJobname-\arabic{LWR@lateximagenumber}}%
11895 \LWR@traceinfo{lateximage: finished creating the label}%

```

Adjust the rule color to match HTML:

```

11896 \ifdefvoid{\LWR@ruleHTMLcolor}{}{%
11897 \LWR@print@arrayrulecolor[HTML]{\LWR@ruleHTMLcolor}%
11898 }%

```

Enable print-mode math functions:

```

11899 \LetLtxMacro$\LWR@origdollar%
11900 \catcode'\$=3% math shift
11901 \LetLtxMacro\(\LWR@origopenparen%
11902 \LetLtxMacro\)\LWR@origcloseparen%

```

Only enable print-mode display math if are not already inside display math:

```

11903 \ifbool{LWR@indisplaymathimage}{}{% not in display math
11904 \LetLtxMacro\[\LWR@origopenbracket%
11905 \LetLtxMacro\]\LWR@origclosebracket%
11906 \let\equation\LWR@origequation%
11907 \let\endequation\LWR@origendequation%
11908 \csletcs{equation*}{LWR@origequation*}%
11909 \csletcs{endequation*}{LWR@origendequation*}%
11910 }% not in display math

```

For chemformula:

```

11911 \LetLtxMacro\LWR@newsingledollar$%
11912 \LetLtxMacro\LWR@newsingledollar$% syntax highlighting

```

```

11913 }% end of outer-most lateximage
11914 \LWR@traceinfo{lateximage: finished start of environment}%
11915 }% end of \begin{lateximage}

```

`\endlateximage` When the environment closes:

```
11916 {% start of \end{lateximage}
11917 \LWR@traceinfo{lateximage: starting end of lateximage}%
```

Nested more than one deep?

```
11918 \LWR@traceinfo{lateximage: internal depth was \arabic{LWR@lateximagedepth}}%
11919 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
```

If nesting inside an already existing lateximage, simply record one less level. Uses a lower-level TEX macro due to *AMS* \text change of `\addtocounter`.

```
11920 {%
11921 \LWR@traceinfo{lateximage: unnesting}%
11922 \global\advance\c@LWR@lateximagedepth -1\relax%
11923 }%
```

If this is the outer-most lateximage:

```
11924 {% end of outer-most lateximage
```

Finish the lateximage minipage and start a new PDF page:

```
11925 \LWR@traceinfo{lateximage: ending outer-most lateximage}%
11926 \endLWR@print@minipage%
11927 \LWR@maybe@orignewpage%
```

Close the HTML comment which encapsulated any traces of the lateximage picked up by *pdftotext*:

```
11928 \LWR@print@vspace*{.5\baselineskip}%
11929 \LWR@htmlclosecomment%
11930 \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%
```

Create a link to the lateximage, allowing its natural height:

```
11931 \IfBooleanTF{#1}% starred
11932 {% hash
11933 \LWR@lateximage@oneimage{#2}{\LWR@hashedname}{#5}{#3}%
11934 }% hash
11935 {% no hash
11936 \LWR@lateximage@oneimage{#2}{\LWR@ImagesName\theLWR@externalfilecnt}{#5}{#3}%
11937 }% no hash
```

Be sure that are doing a paragraph:

```
11938 \LWR@ensuredoingapar%
```

Close the HTML span which has the *pdftotext* comment and also the link to the .svg image:

```
11939 \LWR@htmltag{/span}%
```

```

11940 \ifbool{HTMLDebugComments}{%
11941 \LWR@htmlcomment{End of lateximage}%
11942 }{}%

```

Undo one lateximage level. This is not inside an  $\mathcal{AMS}$  \text, so regular \addtocounter may be used here.

```

11943 \addtocounter{LWR@lateximagedepth}{-1}%

```

Clear the single-use alt text:

```

11944 \gdef\LWR@ThisAltText{}%
11945 }% end of outer-most lateximage
11946 \LWR@traceinfo{lateximage: exiting depth is \arabic{LWR@lateximagedepth}}%
11947 \LWR@traceinfo{lateximage: done}%
11948 }%
11949 \catcode'\$=3% math shift
11950 \end{warpHTML}

```

**for PRINT output:** 11951 \begin{warpprint}

Env lateximage \* [ $\langle$ alt tag $\rangle$ ] \* [*add'l hashing*] [*css style*]

varwidth is used to create a box of the natural width of its contents.

```

11952 \NewDocumentEnvironment{lateximage}{s o s o o}
11953 {\begin{varwidth}[b]{\linewidth}}
11954 {\end{varwidth}}

```

```

11955 \end{warpprint}

```

## 83 center, flushleft, flushright

**for HTML output:** 11956 \begin{warpHTML}

Env center Replace center functionality with css tags:

```

11957 \newenvironment*{LWR@HTML@center}
11958 {
11959 \LWR@forcenewpage
11960 \ifbool{FormatWP}
11961 {\BlockClass[LWR@print@mbbox{text-align:center}]{center}}
11962 {\BlockClass{center}}
11963 }
11964 {\endBlockClass}
11965
11966 \LWR@formattedenv{center}

```

Env flushright

```

11967 \newenvironment*{LWR@HTML@flushright}
11968 {
11969 \LWR@forcenewpage
11970 \ifbool{FormatWP}
11971 {\BlockClass[\LWR@print@mbbox{text-align:right}]{flushright}}
11972 {\BlockClass{flushright}}
11973 }
11974 {\endBlockClass}
11975
11976 \LWR@formattedenv{flushright}

```

Env flushleft

```

11977 \newenvironment*{LWR@HTML@flushleft}
11978 {
11979 \LWR@forcenewpage
11980 \ifbool{FormatWP}
11981 {\BlockClass[\LWR@print@mbbox{text-align:left}]{flushleft}}
11982 {\BlockClass{flushleft}}
11983 }
11984 {\endBlockClass}
11985
11986 \LWR@formattedenv{flushleft}

```

`\centering`, `\raggedleft`, and `\raggedright` usually have no effect on the HTML output, but they may be used to compare with the next token to identify their use at the start of a float. See `\LWR@floatalignment`.

`\centering`

```

11987 \newcommand*{\LWR@HTML@centering}{%
11988 \ifbool{HTMLDebugComments}{%
11989 \LWR@htmlcomment{centering}%
11990 }{}%
11991 }
11992 \LWR@formatted{centering}

```

`\raggedleft`

```

11993 \newcommand*{\LWR@HTML@raggedleft}{%
11994 \ifbool{HTMLDebugComments}{%
11995 \LWR@htmlcomment{raggedleft}%
11996 }{}%
11997 }
11998 \LWR@formatted{raggedleft}

```

`\raggedright`

```

11999 \newcommand*{\LWR@HTML@raggedright}{%

```

```

12000 \ifbool{HTMLDebugComments}{%
12001 \LWR@htmlcomment{raggedright}%
12002 }{%
12003 }
12004 \LWR@formatted{raggedright}

```

`\leftline`  $\{\langle text \rangle\}$

```
12005 \renewcommand{\leftline}[1]{\begin{flushleft}#1\end{flushleft}}
```

`\centerline`  $\{\langle text \rangle\}$

```
12006 \renewcommand{\centerline}[1]{\begin{center}#1\end{center}}
```

`\rightline`  $\{\langle text \rangle\}$

```
12007 \renewcommand{\rightline}[1]{\begin{flushright}#1\end{flushright}}
```

```
12008 \end{warpHTML}
```

## 84 Preloaded packages

**for HTML output:** 12009 `\begin{warpHTML}`

If the given package was loaded before or by lwarp, load the lwarp version as well.

`\LWR@PreloadedPackage`  $\{\langle packagename \rangle\}$

```

12010 \newcommand*\LWR@PreloadedPackage[1]{%
12011 \@ifpackageloaded{#1}%
12012 {%
12013 \AtBeginDocument{
12014 \LWR@origRequirePackage{lwarp-#1}%
12015 }
12016 }%
12017 }%
12018 }

```

If `inputtrc` was loaded before lwarp, as is usually done, explicitly load the lwarp patches now:

```
12019 \LWR@PreloadedPackage{inputtrc}
```

If `textcomp` was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
12020 \LWR@PreloadedPackage{textcomp}
```

If `xunicode` was loaded before `lwarp`, perhaps as part of the font-related packages, explicitly load the `lwarp` patches now:

```
12021 \LWR@PreloadedPackage{xunicode}
```

If `graphics` or `graphicx` were loaded before `lwarp`, perhaps by `xunicode`, explicitly load the `lwarp` patches now:

```
12022 \LWR@PreloadedPackage{graphics}
```

```
12023 \LWR@PreloadedPackage{graphicx}
```

`scalegnt` may have been preloaded by `babel`

```
12024 \LWR@PreloadedPackage{scalegnt}
```

`fontaxes` must be preloaded so that `lwarp` may patch it for `HTML`.

```
12025 \LWR@PreloadedPackage{fontaxes}
```

Various font packages which may be loaded before `lwarp`:

```
12026 \LWR@PreloadedPackage{cmbright}
```

```
12027 \LWR@PreloadedPackage{fourier}
```

```
12028 \LWR@PreloadedPackage{kpfonts}
```

```
12029 \LWR@PreloadedPackage{kpfonts-otf}
```

```
12030 \LWR@PreloadedPackage{libertinust1math}
```

```
12031 \LWR@PreloadedPackage{pxfonts}
```

```
12032 \LWR@PreloadedPackage{txfonts}
```

```
12033 \LWR@PreloadedPackage{txgreek}
```

```
12034 \LWR@PreloadedPackage{newpxmath}
```

```
12035 \LWR@PreloadedPackage{newtxmath}
```

```
12036 \LWR@PreloadedPackage{newtxsf}
```

```
12037 \LWR@PreloadedPackage{mathalpha}
```

```
12038 \LWR@PreloadedPackage{unicode-math}
```

`nfssex-cfr` may be preloaded by `cfm-lm` or related font packages.

```
12039 \LWR@PreloadedPackage{nfssex-cfr}
```

`ulem` may be preloaded by `ctex`, `ctexart`, and related classes.

```
12040 \LWR@PreloadedPackage{ulem}
```

`xetexko-vertical` may be preloaded by `xetexko`.

```
12041 \LWR@PreloadedPackage{xetexko-vertical}
```

`geometry` is preloaded by `lwarp`, and perhaps by various classes.

```
12042 \LWR@PreloadedPackage{geometry}
```

`plext` is preloaded by some CJK classes.

```
12043 \LWR@PreloadedPackage{plext}
```

stfloats is preloaded by ltj\* classes.

```
12044 \LWR@PreloadedPackage{stfloats}
```

lltjext is preloaded by ltj\* classes.

```
12045 \LWR@PreloadedPackage{lltjext}
```

luatexko must be loaded before lwarp.

```
12046 \LWR@PreloadedPackage{luatexko}
```

```
12047 \end{warpHTML}
```

## 85 siunitx

Pkg siunitx The lwarp core passes a few options to siunitx.

**fractions** Due to *pdftotext* limitations, fraction output is replaced by symbol output for per-mode and quotient-mode.

 **math mode required** Some units will require that the expression be placed inside math mode.

 **tabular** Tabular S columns are rendered as simple c columns, and tabular s columns are not supported. These may be replaced by c columns with each cell contained in \num or \si.

 **MathJax** For math mode with svg display, the original siunitx code is used while generating the svg image. For text mode, lwarp uses an emulation which provides a very effective HTML interpretation of siunitx. For math expressions while using MATHJAX, a limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. siunitx macros with more than one optional value cannot absorb the second optional value, and complicated parsing such as for \ang is not supported. The result usually looks fine, and otherwise is enough to get the meaning across.

lwarp's MATHJAX emulation for siunitx is meant to be a stop-gap measure until an extension is included in MATHJAX. As of this writing, the third-party siunitx extension for MATHJAX is not currently hosted at any public CDN, thus siunitx is not usable with this extension unless a local copy of this extension is created first. See \MathJaxFilename to select a custom MathJax script, but lwarp's emulation would have to be disabled as well.

Document modifications required for MATHJAX:

**custom units** • Custom units may be added with \CustomizeMathJax. See the lwarp-siunitx code for examples.

 **unit spacing** • Units work better using ~ between units instead of using periods.

 **\square, \cubic** • To square or cube compound units, enclose the following compound units in braces:

```
\cubic{\centi\meter}
```

Single units do not require braces.

Also see **MATHJAX option**, section 8.7.4.

**for HTML output:** 12048 \begin{warpHTML}

Options for siunitx:

```
12049 \newrobustcmd{\LWR@siunitx@textcelsius}{\HTMLentity{deg}C}
12050 \newrobustcmd{\LWR@siunitx@textdegree}{\HTMLentity{deg}}
12051 \newrobustcmd{\LWR@siunitx@textprime}{\HTMLunicode{2032}}
12052 \newrobustcmd{\LWR@siunitx@textdblprime}{\HTMLunicode{2033}}
12053 \newrobustcmd{\LWR@siunitx@textplanckbar}{\text{\textit{\HTMLunicode{210F}}}}
12054
12055 \appto\LWR@restoreorigformatting{%
12056 \renewrobustcmd{\LWR@siunitx@textcelsius}{\text{\ensuremath{^\circ}C}}%
12057 \renewrobustcmd{\LWR@siunitx@textdegree}{\text{\ensuremath{^\circ}}}%
12058 \renewrobustcmd{\LWR@siunitx@textprime}{\text{\ensuremath{^\prime}}}%
12059 \renewrobustcmd{\LWR@siunitx@textdblprime}{\text{\ensuremath{^\prime\prime}}}%
12060 \renewrobustcmd{\LWR@siunitx@textplanckbar}{\text{\ensuremath{\hbar}}}%
12061 }
12062
12063 \PassOptionsToPackage{
12064 detect-mode=true,
12065 per-mode=symbol,% fraction is not seen by pdftotext
12066 text-celsius = {\LWR@siunitx@textcelsius},
12067 text-degree = {\LWR@siunitx@textdegree},
12068 text-arcminute = {\LWR@siunitx@textprime} ,
12069 text-arcsecond = {\LWR@siunitx@textdblprime} ,
12070 }{siunitx}

12071 \end{warpHTML}
```

## 86 Graphics print-mode modifications

### 86.1 General limitations

 **scale** Avoid using the `\includegraphics scale` option. Change:

```
\includegraphics[scale=<xx>]{...}
```

to:

```
\includegraphics[width=<yy>\linewidth]{...}
```

**`\includegraphics` file formats** For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps` image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, `lwarp` will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a `.pdf` or `.eps` image is referred to with its file extension, the extension will be changed to `.svg` for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog `pdftocairo` To convert a PDF image to SVG, use the utility *pdftocairo*:

PDF to SVG

Enter ⇒ **`pdftocairo -svg filename.pdf`**

Prog `lwarpmk pdftosvg` For a large number of images, use *lwarpmk*:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** (or a list of filenames)

Prog `lwarpmk epstopdf` For EPS images converted to PDF using the package `epstopdf`, use

Prog `epstopdf`

`epstopdf` package

Enter ⇒ **`lwarpmk pdftosvg *.PDF`**

to convert to SVG images.

DVI latex When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **`lwarpmk epstopdf *.eps`** (or a list of filenames)

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** (or a list of filenames)

PNG and JPG For PNG or JPG while using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

△ **graphics vs. graphicx** If using the older `graphics` syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer `graphicx` syntax. Note that viewports are not supported by `lwarp`—the entire image will be shown.

△ **viewport**

△ **viewport units**

For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus `new class` and `alt` keys.

HTML class With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combi-

nation, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

**HTML alt tags** Likewise, the `\includegraphics alt` key adds an HTML alt tag to an image, and is ignored for print output. If not assigned, each image is given an alt tag according to `\ImageAltText`.

`\rotatebox` `\rotatebox` accepts the optional origin key.

 **browser support** `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike L<sup>A</sup>T<sub>E</sub>X, so expect some ugly results for scaling and rotating.

## 86.2 Print-mode modifications

**for PRINT output:** For print output, accept and then discard the new class key:

```
12072 \begin{warpprint}
12073 \define@key{Gin}{class}{}
12074 \define@key{Gin}{alt}{}

```

Print-mode additions for the `overpic` package. See section 433 for the HTML version.

```
12075 \AtBeginDocument{
12076 \ifpackageloaded{overpic}{
12077 \newcommand*\overpicfontsize{12}
12078 \newcommand*\overpicfontskip{14}
12079 }{}
12080 }
12081 \end{warpprint}

```

## 87 xcolor boxes

**Pkg** `xcolor` A few new definitions are provided for enhanced HTML colored boxes, and `\fcolorbox` is slightly modified. Print-mode version are also provided.

Print-mode versions of new `xcolor` definitions. These are defined inside `warppall` because they are also used for HTML while inside a `lateximage`. They are defined `\AtBeginDocument` so that the `xcolor` originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of none, in which case only the frame is drawn, allowing the background page color to show.

**for HTML & PRINT:** 12082 `\begin{warppall}`

After `xparse` may have been loaded ...

```
12083 \AtBeginDocument{

```

... and *only* if xcolor was loaded:

```
12084 \@ifpackageloaded{xcolor}{
12085 \LWR@traceinfo{patching xcolor}
```

The print version:

`\colorboxBlock` `\colorboxBlock` is the same as `\colorbox`:

```
12086 \LetLtxMacro\colorboxBlock\colorbox
```

The original definition is reused by the new versions:

```
12087 \LetLtxMacro\LWR@orig@print@fcolorbox\fcolorbox
```

```
\fcolorbox [framemodel] [framecolor] [boxmodel] [boxcolor] [text]
```

In print mode, `\fcolorbox` is modified to accept a background color of none.

(`\fcolorbox` is particular about its optional arguments, thus the elaborate combinations of `\ifthenelse`.)

```
12088 \newsavebox{\LWR@colorminipagebox}
12089
12090 \NewDocumentCommand{\LWR@print@fcolorbox}{o m o m +m}{%
12091 \LWR@traceinfo{LWR@print@fcolorbox #2 #4}%
```

Pre-load the contents into an LR box so that they can be used inside a `\fcolorbox`:

```
12092 \begin{lrbox}{\LWR@colorminipagebox}%
12093 #5%
12094 \end{lrbox}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a `\fcolorbox`.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
12095 \ifstrequal{#4}{none}%
12096 {% #4 none
12097 \LWR@traceinfo{background is none}%
12098 {% scope the \colorlet
12099 \colorlet{LWR@currentcolor}{.}%
12100 \color{#2}%
12101 \fbox{%
12102 \color{LWR@currentcolor}%
12103 \usebox{\LWR@colorminipagebox}%
12104 }% fbox
12105 }% colorlet
12106 }% #4 none
12107 {% #4 not none
12108 \LWR@traceinfo{background not none}%
```

```

12109 \IfValueTF{#1}%
12110 {%
12111 \IfValueTF{#3}%
12112 {\LWR@orig@print@fcolorbox[#1][#2][#3][#4]{\usebox{\LWR@colorminipagebox}}}%
12113 {\LWR@orig@print@fcolorbox[#1][#2][#4]{\usebox{\LWR@colorminipagebox}}}%
12114 }%
12115 {% no value #1
12116 \IfValueTF{#3}%
12117 {\LWR@orig@print@fcolorbox[#2][#3][#4]{\usebox{\LWR@colorminipagebox}}}%
12118 {\LWR@orig@print@fcolorbox[#2][#4]{\usebox{\LWR@colorminipagebox}}}%
12119 }% no value #1
12120 }% #4 not none
12121 \LWR@traceinfo{\LWR@print@fcolorbox done}%
12122 }

```

```
12123 \renewrobustcmd*{\fcolorbox}{\LWR@print@fcolorbox}%
```

`\fcolorboxBlock` [*framemodel*] [*framecolor*] [*boxmodel*] [*boxcolor*] [*text*]

In print mode, `\fcolorboxBlock` is the same as `\fcolorbox`.

```
12124 \newcommand*{\LWR@print@fcolorboxBlock}{\LWR@print@fcolorbox}
```

```
12125 \newrobustcmd*{\fcolorboxBlock}{\LWR@print@fcolorboxBlock}
```

Env `fcolorminipage` [*1:framemodel*] [*2:framecolor*] [*3:boxmodel*] [*4:boxcolor*] [*5:align*] [*6:height*] [*7:inner-align*] [*8:width*]

In print mode, becomes a `\fcolorbox` containing a minipage:

```

12126 \NewDocumentEnvironment{LWR@print@fcolorminipage}{o m o m O{c} O{ } o m}
12127 {%
12128 \LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%

```

Pre-load the contents into an LR box so that they can be used inside a `\fcolorbox`:

```
12129 \begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```

12130 \IfValueTF{#7}%
12131 {\begin{minipage}[#5][#6][#7]{#8}}%
12132 {\begin{minipage}[#5][#6][#5]{#8}}%
12133 }%
12134 {%
12135 \end{minipage}%
12136 \end{lrbox}%
12137 \LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}%

```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a `\fcolorbox`.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```

12138 \ifstrequal{#4}{none}%
12139 {% #4 none
12140 {% scope the \colorlet
12141 \colorlet{LWR@currentcolor}{.}%
12142 \color{#2}%
12143 \fbox{%
12144 \color{LWR@currentcolor}%
12145 \usebox{LWR@colorminipagebox}%
12146 }% fbox
12147 }% colorlet
12148 }% #4 none
12149 {% #4 not none
12150 \IfValueTF{#1}%
12151 {%
12152 \IfValueTF{#3}%
12153 {\LWR@orig@print@fcolorbox[#1][#2][#3][#4]{\usebox{LWR@colorminipagebox}}}%
12154 {\LWR@orig@print@fcolorbox[#1][#2][#4]{\usebox{LWR@colorminipagebox}}}%
12155 }%
12156 {% no value #1
12157 \IfValueTF{#3}%
12158 {\LWR@orig@print@fcolorbox[#2][#3][#4]{\usebox{LWR@colorminipagebox}}}%
12159 {\LWR@orig@print@fcolorbox[#2][#4]{\usebox{LWR@colorminipagebox}}}%
12160 }% no value #1
12161 }% #4 not none
12162 \LWR@traceinfo{*** finished end fcolorminipage}%
12163 }

12164 \NewDocumentEnvironment{fcolorminipage}{}
12165 {\LWR@print@fcolorminipage}
12166 {\endLWR@print@fcolorminipage}

12167 \LWR@traceinfo{xcolor patches done}
12168 }{% xcolor loaded
12169 }% AtBeginDocument

12170 \end{warppall}

```

## 88 chemmacros environments

`\makepolymerdelims` and redox reactions must be enclosed in a `lateximage` during HTML output. These environments are provided here in print mode, and in the `chemmacros` code in HTML mode, as a high-level semantic syntax which automatically embeds the contents in a `lateximage` with an appropriate `alt` tag.

**for PRINT output:** 12171 `\begin{warpprint}`

```

12172 \AtBeginDocument{
12173 \@ifpackageloaded{chemmacros}{

```

Env polymerdelims

```
12174 \DeclareDocumentEnvironment{polymerdelims}{}
12175 {}{}
```

Env redoxreaction  $\{\langle space above \rangle\} \{\langle space below \rangle\}$

For print output, extra space is include above and below the image, and a `lateximage` is not necessary. This extra space must be enforced, even inside a float, so zero-width rules are used.

For the HTML version, see section 186.4.

```
12176 \DeclareDocumentEnvironment{redoxreaction}{m m}
12177 {\rule{0pt}{#1}}{\rule[-#2]{0pt}{#2}}
```

```
12178 }{}% chemmacros
12179 }% AtBeginDocument
```

```
12180 \end{warpprint}
```

## 89 cleveref

**loading order** `cleveref` and `lwarp-cleveref` with its associated macro patches are automatically preloaded at the end of the preamble via `\AtEndPreamble` and `\AfterEndPreamble`. This is done because the HTML conversion requires `cleveref`. The user's document may not require `cleveref`, thus the user may never explicitly load it, so during HTML output `lwarp` loads it last. If the user's document preamble uses `cleveref` options, or functions such as `\crefname`, then `cleveref` may be loaded in the user's preamble near the end, and `lwarp`'s additional loading of `cleveref` will have no effect.

`\AtEndPreamble` forces `cleveref` to be loaded last, if it has not yet been loaded by the user.

```
for HTML output: 12181 \begin{warppHTML}
12182
12183 \AtEndPreamble{
12184 \RequirePackage{cleveref}
12185 }
12186
12187 \end{warppHTML}
```

## 90 Preexisting label and reference definitions

Remember and patch some label-related definitions. These will be further encased and patched by other packages later.

`\label` and `\pageref` do NOT change their behavior according to print or HTML output, and thus do not use the `\LWR@formatted` system.

```

for HTML output: 12188 \begin{warpHTML}
12189
12190 \LetLtxMacro\LWR@orig@label\label% includes memoir, before cleveref
12191 \LetLtxMacro\label\LWR@new@label
12192
12193 \LetLtxMacro\LWR@orig@pageref\pageref
12194 \LetLtxMacro\pageref\LWR@new@pageref
12195
12196 \end{warpHTML}

```

## 91 picture environment

Env `picture` The `picture` environment is enclosed inside a `\lateximage`.

```

for HTML output: 12197 \begin{warpHTML}

```

Env `picture`

```

12198 \BeforeBeginEnvironment{picture}{\begin{lateximage}[picture]}
12199
12200 \AfterEndEnvironment{picture}{\end{lateximage}}

12201 \end{warpHTML}

```

## 92 Minipages and Boxes

A CSS flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

 **inline** A line of text with an inline minipage or `\parbox` will have the minipage or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made inline-block.

**placement** minipages and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

**side-by-side** Side-by-side minipages may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.

 **minipage in a span** There is limited support for minipages inside an HTML `<span>`. An HTML `<div>` cannot appear inside a `<span>`. While in a `<span>`, minipages, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an “inline” format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

 **minipage size** When using `minipage`, `\parbox`, and `fminipage`, a virtual 6 × 9 inch text area is used for `\linewidth`, `\textwidth`, and `\textheight`, both for sizing the minipage, and also for its contents.

- if width is `\linewidth`** If a `minipage` or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.
- full-width if HTML** A new macro `\minipagefullwidth` requests that, during HTML output, the next single `minipage` or `\parbox` be generated without an HTML width attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.
- ⚠ tabular, multicol** Inside a `tabular` or `multicol` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every `minipage` or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell `lwarp` to honor the specified widths of all following `minipages` and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell `lwarp` to ignore the specified widths.
- `\UseMinipageWidths`  
`\IgnoreMinipageWidths`
- ⚠ multicol** Inside a `multicol`, `\linewidth` is divided by the specified number of columns.
- ⚠ text alignment** Nested `minipages` adopt their parent's text alignment in HTML, whereas in regular L<sup>A</sup>T<sub>E</sub>X PDF output they do not. Use a `flushleft` or similar environment in the child `minipage` to force a text alignment.
- for HTML output:** `12202 \begin{warpHTML}`

## 92.1 Computed lengths

Len `\LWR@minipagewidth` Used to convert the width into printable units.

```
12203 \newlength{\LWR@minipagewidth}
```

Len `\LWR@minipageheight` Used to convert the height into printable units.

```
12204 \newlength{\LWR@minipageheight}
```

## 92.2 Virtual page size

Ctr `LWR@virtualpagedepth` Used to only reset the line width at the outermost `minipage`.

```
12205 \newcounter{LWR@virtualpagedepth}
12206 \setcounter{LWR@virtualpagedepth}{0}
```

Env `LWR@setvirtualpage` \* [`<columns>`]

If not nesting a `minipage`, adjust `\linewidth`, `\textwidth`, and `\textheight` for a virtual  $6 \times 9$  page, and start on a new PDF page to help prevent page overflows.

If starred, force a new page in the PDF before generating more HTML. This may be done to reduce the chance of page overflow when starting a new `minipage`.

The optional number of columns defaults to 1.

```

12207 \NewDocumentEnvironment{LWR@setvirtualpage}{s O{1}}{%
12208 \ifnumequal{\value{LWR@virtualpagedepth}}{0}{%
12209 \IfBooleanT{#1}{\LWR@maybe@orignewpage}%
12210 \setlength{\linewidth}{6in/#2}%
12211 \setlength{\textwidth}{6in}%
12212 \setlength{\textheight}{9in}%
12213 }{%
12214 \addtocounter{LWR@virtualpagedepth}{1}%
12215 }
12216 {\addtocounter{LWR@virtualpagedepth}{-1}}

```

### 92.3 Footnote handling

Also see section 59 for other forms of footnotes. Minipage footnotes are gathered in section 59.5, and then placed into the document in section 92.4.

### 92.4 Minipage handling

Bool LWR@minipagefullwidth Should the next minipage have no HTML width?

```

12217 \newbool{LWR@minipagefullwidth}
12218 \boolfalse{LWR@minipagefullwidth}

```

Bool LWR@forceminipagefullwidth Should the next minipage have no HTML width? Used to force full width for all minipages in an environment such as tabular or multicols, where the actual width depends on the browser width. Controlled by \useminipagewidths and \ignoreminipagewidths.

```

12219 \newbool{LWR@forceminipagefullwidth}
12220 \boolfalse{LWR@forceminipagefullwidth}

```

\minipagefullwidth Requests that the next minipage have no width tag in HTML:

**for HTML output:** 12221 \newcommand\*{\minipagefullwidth}{\global\booltrue{LWR@minipagefullwidth}}

\UseMinipageWidths Locally requests that minipage widths be honored.

```

12222 \newcommand*{\UseMinipageWidths}{\boolfalse{LWR@forceminipagefullwidth}}

```

\IgnoreMinipageWidths Locally requests that minipage widths be ignored.

```

12223 \newcommand*{\IgnoreMinipageWidths}{\booltrue{LWR@forceminipagefullwidth}}
12224 \end{warppHTML}

```

**for PRINT output:** 12225 \begin{warpprint}

```

12226 \newcommand*\minipagefullwidth{}
12227 \newcommand*\UseMinipageWidths{}
12228 \newcommand*\IgnoreMinipageWidths{}
12229 \end{warpprint}

```

**for HTML output:** 12230 \begin{warppHTML}

Bool LWR@minipagethispar Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.

```

12231 \newbool{LWR@minipagethispar}
12232 \boolfalse{LWR@minipagethispar}

```

Env minipage [*⟨vert position⟩*] [*⟨height⟩*] [*⟨inner vert position⟩*] {*⟨width⟩*}

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using \linewidth, \textwidth, or \textheight, these are scaled proportionally to a 6×9 inch text area.

```

12233 \NewDocumentEnvironment{LWR@HTML@sub@minipage}{m m m m}
12234 {%
12235 \LWR@traceinfo{minipage}%

```

Start an environment, in which width and height is computed based on a virtual page size instead of the extra-large PDF page used during HTML tag generation.

```
12236 \begin{LWR@setvirtualpage}*
```

Save the requested width now that \linewidth, etc. are adjusted to virtual size.

```

12237 \setlength{\LWR@minipagewidth}{#4}%
12238 \ifnumequal{\value{LWR@virtualpagedepth}}{1}{%
12239 \addtolength{\LWR@minipagewidth}{3em}% room for frames
12240 }{}%
12241 \LWR@traceinfo{computed width is \LWR@printlength{\LWR@minipagewidth}}%

```

Compute height:

```

12242 \setlength{\LWR@minipageheight}{\textheight}% default unless specified
12243 \ifblank{#2}{\setlength{\LWR@minipageheight}{#2}}%

```

L<sup>A</sup>T<sub>E</sub>X wants to start a paragraph for the virtual minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

```

12244 \ifbool{FormatWP}{\newline}{}%
12245 \LWR@stoppars%

```

If FormatWP, add a text frame:

```
12246 \ifbool{FormatWP}{%
```

```

12247
12248 \addtocounter{LWR@thisautoidWP}{1}%
12249 \LWR@htmltag{%
12250 div id="\LWR@print@mbbox{autoidWP-\arabic{LWR@thisautoidWP}}" %
12251 class="wpmnipage"%
12252 }%
12253
12254 }{}%

```

Create the <div> tag with optional alignment style:

```

12255 \LWR@traceinfo{minipage: creating div class}%
12256 \LWR@htmltag{div class="minipage" style="%
12257 \ifthenelse{equal{#1}{t}}{\LWR@print@mbbox{vertical-align:bottom} ; }{}%
12258 \ifthenelse{equal{#1}{c}}{\LWR@print@mbbox{vertical-align:middle} ; }{}%
12259 \ifthenelse{equal{#1}{b}}{\LWR@print@mbbox{vertical-align:top} ; }{}%
12260 \ifthenelse{equal{#3}{t}}{\LWR@print@mbbox{justify-content:flex-start} ; }{}%
12261 \ifthenelse{equal{#3}{c}}{\LWR@print@mbbox{justify-content:center} ; }{}%
12262 \ifthenelse{equal{#3}{b}}{\LWR@print@mbbox{justify-content:flex-end} ; }{}%
12263 \ifthenelse{equal{#3}{s}}{\LWR@print@mbbox{justify-content:space-between} ; }{}%

```

Print the width and optional height styles:

```

12264 \LWR@traceinfo{minipage: about to print the width of \LWR@printlength{\LWR@minipagewidth}}%
12265 \ifbool{LWR@minipagefullwidth}%
12266 {\global\boolfalse{LWR@minipagefullwidth}}%
12267 {%
12268 \ifbool{LWR@forceminipagefullwidth}%
12269 {%
12270 {%
12271 \ifdimequal{#4}{\linewidth}%
12272 {%
12273 {width:\LWR@printlength{\LWR@minipagewidth} ; }%
12274 }%
12275 }%
12276 \LWR@traceinfo{minipage: about to print the height}%
12277 \ifblank{#2}{\height:\LWR@printlength{\LWR@minipageheight} ; }%
12278 "%}

```

Finish with an empty line to start the contents on a new line.

```

12279
12280 % The preceding empty line is required.

```

Set the user-accessible line and text width and height values inside the virtual minipage. These do not affect the actual size of the PDF output, but are used by any reference to `\linewidth`, etc. inside the virtual minipage being created here. `\LWR@minipagewidth` was the original then padded by 3em, which is restored here. This is done instead of settings back to #4, in case #4 was `\linewidth`, which was changed to 6in above.

```

12281 \ifnumequal{\value{LWR@virtualpagedepth}}{1}{%
12282 \addtolength{\LWR@minipagewidth}{-3em}% undo frame padding
12283 }{}%
12284 \setlength{\linewidth}{\LWR@minipagewidth}%

```

`\raggedright` cancels hyphenation, which will be done by HTML instead.

```
12285 \LWR@print@raggedright%
```

Set minipage footnotes:

```
12286 \def\@mpfn{mpfootnote}%
12287 \def\thempfn{\thempfootnote}\c@mpfootnote\z@%
12288 \let\@footnotetext\@mpfootnotetext%
```

Resume paragraph tag handling for the contents of the minipage:

```
12289 \LWR@startpars%
12290 \ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%
12291
12292 === begin minipage ===
12293
12294 }{%
12295 \LWR@traceinfo{minipage: finished starting the minipage}%
12296 }% finished \minipage
12297 {% \endminipage
```

Print pending minipage footnotes:

```
12298 \LWR@printpendingmpfootnotes%
```

End the environment with closing tag:

```
12299 \ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%
12300
12301 === end minipage ===
12302
12303 }{%
12304 \LWR@stoppars%
12305
12306 \ifbool{FormatWP}{%
12307
12308 \LWR@htmlElementend{div}%
12309
12310 }{%
12311 \LWR@htmldivclassend{minipage}%
12312
12313 \end{LWR@setvirtualpage}%
12314 \LWR@startpars%
12315 \ifbool{FormatWP}{\newline}{}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
12316 \global\booltrue{LWR@minipagethispar}%
12317 \LWR@traceinfo{LWR@minipage: done}%
12318 }
12319
12320 \NewDocumentEnvironment{LWR@HTML@minipage}{0{t} 0{} 0{t} m}
```

```

12321 {\LWR@HTML@sub@minipage{#1}{#2}{#3}{#4}}
12322 {\endLWR@HTML@sub@minipage}
12323
12324 \LWR@formattedenv{minipage}

```

## 92.5 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox

for HTML output:

```
\parbox [pos] [height] [inner-pos] {width} {text}
```

A parbox uses the minipage code:

```

12325 \NewDocumentCommand{\LWR@HTML@parbox}{O{t} O{} O{t} m +m}
12326 {
12327 \LWR@traceinfo{parbox of width #4}%
12328 \begin{minipage}[#1][#2][#3]{#4}%
12329 #5
12330 \end{minipage}%
12331 }
12332
12333 \LWR@formatted{parbox}

```

```
\mbox {text} Nullified for HTML.
```

```

12334 \newcommand*{\LWR@HTML@mbox}[1]{#1}
12335
12336 \LWR@formatted{mbox}

```

```
\LWR@makebox@paren {width} , {height}
```

Adds to the style in \LWR@temptwo.

```

12337 \NewDocumentCommand{\LWR@makebox@paren}{m m}{%
12338 \IfValueTF{#2}{%
12339 \setlength{\LWR@tempwidth}{#1\unitlength}%
12340 \setlength{\LWR@tempheight}{#2\unitlength}%
12341 \appto{\LWR@temptwo}{%
12342 \LWR@print@mbox{width:\LWR@printlength{\LWR@tempwidth}} ; % space
12343 \LWR@print@mbox{height:\LWR@printlength{\LWR@tempheight}} ; % space
12344 }%
12345 }{%
12346 \PackageError{lwarp}%
12347 {(width,height) is missing a comma ',' character}%
12348 {\protect\makebox\space and \protect\framebox\space accept
12349 a size in the format (width,height).}%
12350 }%
12351 }

```

```
\LWR@makebox@align {alignment character}
```

Adds to the style in \LWR@temptwo.

```

12352 \newcommand*\LWR@makebox@align[1]{%
12353 \def\LWR@align{center}%
12354 \ifstrequal{#1}{l}{\def\LWR@align{left}}{}%
12355 \ifstrequal{#1}{r}{\def\LWR@align{right}}{}%
12356 \ifstrequal{#1}{s}{\def\LWR@align{justify}}{}%
12357 \appto{\LWR@temptwo}{%
12358 \LWR@print@mbx{text-align:\LWR@align} ; %
12359 }%
12360 }

```

\makebox (*(width,height)*) [*[width]*] [*[pos]*] {*<text>*}

```

12361 \NewDocumentCommand{\LWR@HTML@makebox}>{\SplitArgument{1}{,}}d(o o +m){%

```

Build the style depending on arguments:

```

12362 \begin{LWR@setvirtualpage}%
12363 \def\LWR@temptwo{%
12364 \IfValueTF{#1}%
12365 {% (width,height) ..
12366 \LWR@makebox@paren #1%
12367 \IfValueT{#2}%
12368 {% (width,height) [posn]
12369 \LWR@makebox@align{#2}%
12370 }%
12371 }%
12372 {% [width]
12373 \IfValueT{#2}% [width]
12374 {%
12375 \setlength{\LWR@tempwidth}{#2}%
12376 \ifdimgreater{\LWR@tempwidth}{0pt}{%
12377 \appto{\LWR@temptwo}{%
12378 width:\LWR@printlength{\LWR@tempwidth} ; % space
12379 }%
12380 }{}%
12381 }%
12382 }%
12383 \IfValueT{#3}%
12384 {% [width] [posn]
12385 \LWR@makebox@align{#3}%
12386 }%
12387 \InlineClass[%
12388 \LWR@print@mbx{display:inline-block} ; %
12389 \LWR@temptwo%
12390]%
12391 {makebox}%
12392 {#4}%
12393 \end{LWR@setvirtualpage}%
12394 }
12395 \LWR@formatted{makebox}

```

`\framebox` ( $\langle width, height \rangle$ ) [ $\langle width \rangle$ ] [ $\langle pos \rangle$ ] { $\langle text \rangle$ }

```
12396 \NewDocumentCommand{\LWR@HTML@framebox}{d() o o +m}{%
12397 \fbox{\makebox(#1)[#2][#3]{#4}}%
12398 }
12399
12400 \LWR@formatted{framebox}
```

`\LWR@forceminwidth` { $\langle length \rangle$ }

Sets `\LWR@atleastonept` to be at least 1pt.

```
12401 \newlength{\LWR@atleastonept}
12402
12403 \newcommand*{\LWR@forceminwidth}[1]{%
12404 \setlength{\LWR@atleastonept}{#1}%
12405 \ifthenelse{%
12406 \lengthtest{\LWR@atleastonept>0pt}\AND%
12407 \lengthtest{\LWR@atleastonept<1pt}%
12408 }%
12409 {\setlength{\LWR@atleastonept}{1pt}}%
12410 {}%
12411 }
```

`\LWR@fboxstyle` Prints the HTML attributes for a black border and padding.

`\LWR@forceminwidth` must be used first in order to set the border width.

```
12412 \newcommand*{\LWR@fboxstyle}{%
12413 \LWR@findcurrenttextcolor%
12414 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@origpound\LWR@tempcolor ; %
12415 padding:\LWR@printlength{\fboxsep} ; %
12416 color:\LWR@origpound\LWR@tempcolor%
12417 }
```

`\fbox` { $\langle text \rangle$ }

Creates a framed inline span enclosing the text.

Create a new HTML version, but don't use it until after `xcolor` may have loaded:

```
12418 \newcommand{\LWR@HTML@fbox}[1]{%
12419 \LWR@traceinfo{HTML fbox}%
12420 \LWR@forceminwidth{\fboxrule}%
12421 \InlineClass[%
12422 \LWR@print@ebox{display:inline-block} ; %
12423 \LWR@fboxstyle%
12424]{fbox}{#1}%
12425 }
```

`xcolor` lets things to `\fbox` when it is loaded, and this must remain even for HTML output while in a `lateximage`, so `\fbox` is not modified until `\AtBeginDocument`:

```
12426 \AtBeginDocument{\LWR@formatted{fbox}}
```

`\fboxBlock`  $\{\langle text \rangle\}$  Creates a framed HTML `<div>` of the text.

First, a print-mode version. This is newly defined for print mode, so it is defined inside `warpall`.

**for HTML & PRINT:** 12427 `\end{warpHTML}`  
 12428 `\begin{warpall}`  
 12429 `\let\fboxBlock\fbox`  
 12430 `\end{warpall}`  
 12431  
 12432 `\begin{warpHTML}`

**for HTML output:** Next, an HTML version:

```
12433 \newcommand{\LWR@HTML@fboxBlock}[1]{%
12434 \LWR@forceminwidth{\fboxrule}%
12435 \LWR@stoppars%
12436 \begin{BlockClass}[%
12437 \LWR@fboxstyle%
12438]{fboxBlock}
12439 #1
12440 \end{BlockClass}
12441 \LWR@startpars%
12442 }
12443
12444 \LWR@formatted{fboxBlock}
12445
12446 \end{warpHTML}
```

Env `fminipage`  $[\langle align \rangle] [\langle height \rangle] [\langle align \rangle] \{\langle width \rangle\}$

Creates a framed HTML `<div>` around its contents.

**for HTML & PRINT:** Print version:

```
12447 \begin{warpall}
12448
12449 \newsavebox{\LWR@fminipagebox}
12450
12451 \NewDocumentEnvironment{\LWR@print@fminipage}{0{t} o 0{t} m}
12452 {%
```

An outer `minipage` will be used for vertical alignment. An inner `minipage` will be framed with `\fbox`.

If the optional inner alignment is not given, use the outer instead:

```
12453 \IfValueTF{#3}%
12454 {\def\LWR@thisalign{#3}}
12455 {\def\LWR@thisalign{#1}}%
```

Form the outer `minipage` depending on whether a height was given. Make the outer `minipage` larger to compensate for the frame.

```
12456 \IfValueTF{#2}%
```

```
12457 {\minipage[#1][#2+2\fbboxsep+2\fbboxrule][\LWR@thisalign]{#4+2\fbboxsep+2\fbboxrule}}%
12458 {\minipage[#1]{#4+2\fbboxsep+2\fbboxrule}}%
```

Capture the contents of the environment:

```
12459 \begin{lrbox}{\LWR@fminipagebox}%
```

Nest the contents inside an inner minipage of the desired size:

```
12460 \IfValueTF{#2}%
12461 {\minipage[#1][#2][\LWR@thisalign]{#4}}%
12462 {\minipage[#1]{#4}}%
12463 }
12464 {%
```

Close the inner minipage and the LR box with the contents:

```
12465 \endminipage%
12466 \end{lrbox}%
```

Create a frame around the contents of the environment:

```
12467 \fbox{\usebox{\LWR@fminipagebox}}%
```

The entire thing is placed inside the outer minipage:

```
12468 \endminipage%
12469 }
12470
12471 \LetLtxMacro\fminipage\LWR@print@fminipage
12472 \LetLtxMacro\endfminipage\endLWR@print@fminipage
12473 % \newenvironment{fminipage}{\LWR@print@fminipage}{\endLWR@print@fminipage}
12474
12475 \end{warpall}
```

HTML version:

**for HTML output:**

```
12476 \begin{warpHTML}
12477
12478 \NewDocumentEnvironment{LWR@HTML@fminipage}{0{t} o 0{t} m}
12479 {%
12480 \LWR@traceinfo{fminipage #1 #2 #3 #4}%
```

Locally change to the virtual page size before processing the requested sizes:

```
12481 \begin{LWR@setvirtualpage}*%
12482 \setlength{\LWR@tempwidth}{#4}%
12483 \IfValueTF{#2}{\setlength{\LWR@tempheight}{#2}}%
```

Use a rule of at least one pixel in width:

```
12484 \LWR@forceminwidth{\fbboxrule}%
```

```
12485 \LWR@stoppars%
```

```

12486 \begin{BlockClass}[%
12487 \LWR@fboxstyle ; %
12488 \IfValueT{#2}{height:\LWR@printlength{\LWR@tempheight} ; }%
12489 \ifbool{\LWR@minipagefullwidth}%
12490 {\global\boolfalse{\LWR@minipagefullwidth}}%
12491 {%
12492 \ifbool{\LWR@forceminipagefullwidth}%
12493 {}%
12494 {%
12495 \ifdimequal{\LWR@tempwidth}{\linewidth}%
12496 {}%
12497 {width:\LWR@printlength{\LWR@tempwidth} ; }%
12498 }%
12499 }%
12500]{fminipage}%
12501 }
12502 {%
12503 \end{BlockClass}%
12504 \end{\LWR@setvirtualpage}%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

12505 \global\booltrue{\LWR@minipagethispar}%
12506 \LWR@traceinfo{fminipage done}%
12507 }
12508
12509 \LWR@formattedenv{fminipage}

```

`\raisebox`  $\langle\textit{raiselen}\rangle$  [ $\langle\textit{height}\rangle$ ] [ $\langle\textit{depth}\rangle$ ]  $\langle\textit{text}\rangle$

```

12510 \NewDocumentCommand{\LWR@HTML@raisebox}{m o o m}{%
12511 #4%
12512 }
12513
12514 \LWR@formatted{raisebox}

12515 \end{warpHTML}

```

## 93 Direct formatting

 **\bfseries, etc.** `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

 **HTML special chars** `&`, `<`, and `>` have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

**program listings** For program listings, the `listings` package is supported, and its `literate` option is used to convert `&`, `<`, and `>` to proper HTML entities.

**verbatim** The various `verbatim`-related environments do not convert `&`, `<`, and `>`, so care must

be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

For high-level block and inline custom CSS classes, see section 51.9.

**for HTML & PRINT:** 12516 \begin{warpall}

Bool FixSmallCaps User may set FixSmallCaps to true if small caps are being incorrectly rendered as all caps.

```
12517 \newbool{FixSmallCaps}
12518 \boolfalse{FixSmallCaps}
```

```
12519 \end{warpall}
```

**for HTML output:** 12520 \begin{warpHTML}

\emph {<text>}

```
12521 \DeclareRobustCommand{\LWR@HTML@emph}[1]{%
12522 {%
12523 \LWR@HTML@itshape%
12524 \LWR@htmlspan{em}{#1}%
12525 }%
12526 }
12527
12528 \LWR@formatted{emph}
```

\textmd {<text>}

```
12529 \DeclareRobustCommand{\LWR@HTML@textmd}[1]{%
12530 {%
12531 \LWR@HTML@mdseries%
12532 \InlineClass(font-weight:normal){textmd}{#1}%
12533 }%
12534 }
12535
12536 \LWR@formatted{textmd}
```

\textbf {<text>}

```
12537 \DeclareRobustCommand{\LWR@HTML@textbf}[1]{%
12538 {%
12539 \LWR@HTML@bfseries%
12540 \LWR@htmlspan{b}{#1}%
12541 }%
12542 }
12543
12544 \LWR@formatted{textbf}
```

\texteb {<text>} From nfssect-cfr.

```

12545 \DeclareRobustCommand{\LWR@HTML@texteb}[1]{%
12546 {%
12547 \LWR@HTML@ebweight%
12548 \InlineClass{texteb}{#1}%
12549 }%
12550 }
12551
12552 \LWR@formatted{texteb}

```

`\textlg`  $\{\langle text \rangle\}$  From `nfssect-cfr`.

```

12553 \DeclareRobustCommand{\LWR@HTML@textlg}[1]{%
12554 {%
12555 \LWR@HTML@lgweight%
12556 \InlineClass{textlg}{#1}%
12557 }%
12558 }
12559
12560 \LWR@formatted{textlg}

```

`\textrm`  $\{\langle text \rangle\}$

```

12561 \DeclareRobustCommand{\LWR@HTML@textrm}[1]{%
12562 {%
12563 \LWR@HTML@rmfamily%
12564 \InlineClass(font-family:serif){textrm}{#1}%
12565 }%
12566 }
12567
12568 \LWR@formatted{textrm}

```

`\textsf`  $\{\langle text \rangle\}$

```

12569 \DeclareRobustCommand{\LWR@HTML@textsf}[1]{%
12570 {%
12571 \LWR@HTML@sffamily%
12572 \InlineClass(font-family:sans){textsf}{#1}%
12573 }%
12574 }
12575
12576 \LWR@formatted{textsf}

```

`\texttt`  $\{\langle text \rangle\}$

```

12577 \DeclareRobustCommand{\LWR@HTML@texttt}[1]{%
12578 {%
12579 \LWR@HTML@ttfamily%
12580 \LWR@htmlspan{kbd}{#1}%
12581 }%
12582 }
12583
12584 \LWR@formatted{texttt}

```

`\textup {<text>}`

```

12585 \DeclareRobustCommand{\LWR@HTML@textup}[1]{%
12586 {%
12587 \LWR@HTML@upshape%
12588 \InlineClass(font-style:normal){textup}{#1}%
12589 }%
12590 }
12591
12592 \LWR@formatted{textup}

```

`\textit {<text>}`

```

12593 \DeclareRobustCommand{\LWR@HTML@textit}[1]{%
12594 {%
12595 \LWR@HTML@itshape%
12596 \LWR@htmlspan{i}{#1}%
12597 }%
12598 }
12599
12600 \LWR@formatted{textit}

```

`\textsc {<text>}`

```

12601 \DeclareRobustCommand{\LWR@HTML@textsc}[1]{%
12602 {%
12603 \LWR@HTML@scshape%
12604 \InlineClass{textsc}{#1}%
12605 }%
12606 }
12607
12608 \LWR@formatted{textsc}

```

`\textulc {<text>}`      From fontaxes.

```

12609 \DeclareRobustCommand{\LWR@HTML@textulc}[1]{%
12610 {%
12611 \LWR@HTML@ulcshape%
12612 \InlineClass{textulc}{#1}%
12613 }%
12614 }
12615
12616 \LWR@formatted{textulc}

```

`\textsi {<text>}`

```

12617 \@ifundefined{textsi}{
12618 \LetLtxMacro\LWR@print@textsi\LWR@print@textsc
12619 }{}
12620
12621 \DeclareRobustCommand{\LWR@HTML@textsi}[1]{%
12622 {%

```

```

12623 \LWR@HTML@sishape%
12624 \textsc{\textit{#1}}%
12625 % \InlineClass(
12626 % font-style: italic;
12627 % font-variant: small-caps ;
12628 % font-variant-numeric: oldstyle-nums ;
12629 %){textsi}{#1}%
12630]%
12631 }
12632
12633 \LWR@formatted{textsi}

```

`\textsl {<text>}`

```

12634 \DeclareRobustCommand{\LWR@HTML@textsl}[1]{%
12635 {%
12636 \slshape%
12637 \InlineClass(font-style:oblique){textsl}{#1}%
12638 }%
12639 }
12640
12641 \LWR@formatted{textsl}

```

`\textssc {<text>}`

```

12642 \newrobustcmd{\LWR@HTML@textssc}[1]{\textsc{#1}}
12643 \LWR@formatted{textssc}

```

`\textnormal {<text>}`

```

12644 \DeclareRobustCommand{\LWR@HTML@textnormal}[1]{\textmd{\textrm{\textup{#1}}}}
12645
12646 \LWR@formatted{textnormal}

```

```

12647 \FilenameNullify{%
12648 \LetLtxMacro\emph\@firstofone%
12649 \LetLtxMacro\textmd\@firstofone%
12650 \LetLtxMacro\textbf\@firstofone%
12651 \LetLtxMacro\texteb\@firstofone%
12652 \LetLtxMacro\textlg\@firstofone%
12653 \LetLtxMacro\textrm\@firstofone%
12654 \LetLtxMacro\textsf\@firstofone%
12655 \LetLtxMacro\texttt\@firstofone%
12656 \LetLtxMacro\textup\@firstofone%
12657 \LetLtxMacro\textit\@firstofone%
12658 \LetLtxMacro\textsc\@firstofone%
12659 \LetLtxMacro\textulc\@firstofone%
12660 \LetLtxMacro\textsi\@firstofone%
12661 \LetLtxMacro\textsl\@firstofone%
12662 \LetLtxMacro\textssc\@firstofone%
12663 \LetLtxMacro\textnormal\@firstofone%
12664 }

```

Remembers the current font family, series, and shape. fontaxes support is integrated here.

```
12665 \newcommand*{\LWR@family}{rm}
12666 \newcommand*{\LWR@series}{md}
12667 \newcommand*{\LWR@shape}{up}
12668 \newcommand*{\LWR@shapecaps}{ulc}
```

`\LWR@textcurrentfont` {*<text>*}

Prints the text with the current font choices. Avoids nesting repeated font selections.

```
12669 \newcounter{LWR@textcurrentfontdepth}
12670 \setcounter{LWR@textcurrentfontdepth}{0}
12671
12672 \newcommand*{\LWR@textcurrentfont}[1]{%
12673 \ifnumcomp{\value{LWR@textcurrentfontdepth}}{>}{0}%
12674 {%
12675 \addtocounter{LWR@textcurrentfontdepth}{1}%
12676 #1%
12677 \addtocounter{LWR@textcurrentfontdepth}{-1}%
12678 }%
12679 {%
12680 \addtocounter{LWR@textcurrentfontdepth}{1}%
12681 \InlineClass{%
12682 text\LWR@family\LWR@origtilde{%
12683 text\LWR@series\LWR@origtilde{%
12684 text\LWR@shape\LWR@origtilde{%
12685 text\LWR@shapecaps%
12686 }%
12687 }#1}%
12688 \addtocounter{LWR@textcurrentfontdepth}{-1}%
12689 }%
12690 }
```

Env `LWR@blocktextcurrentfont` Prints the contents with the current font choices.

```
12691 \newenvironment*{LWR@blocktextcurrentfont}{%
12692 \LWR@stoppars%
12693 \BlockClass{%
12694 text\LWR@family\LWR@origtilde{%
12695 text\LWR@series\LWR@origtilde{%
12696 text\LWR@shape\LWR@origtilde{%
12697 text\LWR@shapecaps%
12698 }%
12699 }{\endBlockClass\LWR@startpars}
```

`\mdseries`

```
12700 \newrobustcmd*{\LWR@HTML@mdseries}{%
12701 \LWR@print@mdseries%
12702 \renewcommand*{\LWR@series}{md}%
```

```
12703 }
12704 \LWR@formatted{mdseries}
```

#### \bfseries

```
12705 \newrobustcmd*{\LWR@HTML@bfseries}{%
12706 \LWR@print@bfseries%
12707 \renewcommand*{\LWR@f@series}{bf}%
12708 }
12709 \LWR@formatted{bfseries}
```

#### \ebweight From nfssex-cfr.

```
12710 \newrobustcmd*{\LWR@HTML@ebweight}{%
12711 \LWR@print@ebweight%
12712 \renewcommand*{\LWR@f@series}{eb}%
12713 }
12714 \LWR@formatted{ebweight}
```

#### \lgweight From nfssex-cfr.

```
12715 \newrobustcmd*{\LWR@HTML@lgweight}{%
12716 \LWR@print@lgweight%
12717 \renewcommand*{\LWR@f@series}{lg}%
12718 }
12719 \LWR@formatted{lgweight}
```

#### \rmfamily

```
12720 \newrobustcmd*{\LWR@HTML@rmfamily}{%
12721 \LWR@print@rmfamily%
12722 \renewcommand*{\LWR@f@family}{rm}%
12723 }
12724 \LWR@formatted{rmfamily}
```

#### \sffamily

```
12725 \newrobustcmd*{\LWR@HTML@sffamily}{%
12726 \LWR@print@sffamily%
12727 \renewcommand*{\LWR@f@family}{sf}%
12728 }
12729 \LWR@formatted{sffamily}
```

#### \ttfamily

```
12730 \newrobustcmd*{\LWR@HTML@ttfamily}{%
12731 \LWR@print@ttfamily%
12732 \renewcommand*{\LWR@f@family}{tt}%
12733 }
12734 \LWR@formatted{ttfamily}
```

The following use `\AtBeginDocument` due to the L<sup>A</sup>T<sub>E</sub>X core `\reinstall@nfss@defs`, which redefines these `\AtBeginDocument`. See **texdoc source2e**.

`\upshape`

```
12735 \newrobustcmd*{\LWR@HTML@upshape}{%
12736 \LWR@print@upshape%
12737 \renewcommand*{\LWR@f@shape}{up}%
12738 }
12739 \AtBeginDocument{\LWR@formatted{upshape}}
```

`\itshape`

```
12740 \newrobustcmd*{\LWR@HTML@itshape}{%
12741 \LWR@print@itshape%
12742 \renewcommand*{\LWR@f@shape}{it}%
12743 }
12744 \AtBeginDocument{\LWR@formatted{itshape}}
```

`\scshape` Note: `\LWR@print@scshape` is not used here since some fonts, such as `erewhon`, copy/paste as all-caps.

```
12745 \newrobustcmd*{\LWR@HTML@scshape}{%
12746 \ifbool{FixSmallCaps}{}{%
12747 \LWR@print@scshape%
12748 }%
12749 \renewcommand*{\LWR@f@shapecaps}{sc}%
12750 }
12751 \AtBeginDocument{\LWR@formatted{scshape}}
```

`\ulcshape` From `fontaxes`.

```
12752 \@ifundefined{ulcshape}{
12753 \LetLtxMacro\ulcshape\upshape
12754 }{}
12755 \newrobustcmd*{\LWR@HTML@ulcshape}{%
12756 \LWR@print@ulcshape%
12757 \renewcommand*{\LWR@f@shapecaps}{ulc}%
12758 }
12759 \AtBeginDocument{\LWR@formatted{ulcshape}}
```

`\sishape`

```
12760 \@ifundefined{sishape}{
12761 \LetLtxMacro\sishape\scshape
12762 }{}
12763 \newrobustcmd*{\LWR@HTML@sishape}{%
12764 \ifbool{FixSmallCaps}{}{%
12765 \LWR@print@sishape%
12766 }%
12767 \renewcommand*{\LWR@f@shape}{it}
```

```

12768 \renewcommand*\LWR@f@shapecaps}{sc}%
12769 }
12770 \AtBeginDocument{\LWR@formatted{sishape}}

```

**\slshape**

```

12771 \newrobustcmd*\LWR@HTML@slshape}{%
12772 \LWR@print@slshape%
12773 \renewcommand*\LWR@f@shape}{sl}%
12774 }
12775 \AtBeginDocument{\LWR@formatted{slshape}}

```

**\sscshape**

```

12776 \newrobustcmd{\LWR@HTML@sscshape}{\LWR@HTML@scshape}
12777 \AtBeginDocument{\LWR@formatted{sscshape}}

```

**\normalfont**

```

12778 \newrobustcmd*\LWR@HTML@normalfont}{\rmfamily\mdseries\upshape\ulcshape}
12779 \LWR@formatted{normalfont}

```

```

12780 \FilenameNullify{%
12781 \LetLtxMacro\rmfamily\@empty%
12782 \LetLtxMacro\sffamily\@empty%
12783 \LetLtxMacro\ttfamily\@empty%
12784 \LetLtxMacro\bfseries\@empty%
12785 \LetLtxMacro\ebweight\@empty%
12786 \LetLtxMacro\lgweight\@empty%
12787 \LetLtxMacro\mdseries\@empty%
12788 \LetLtxMacro\upshape\@empty%
12789 \LetLtxMacro\slshape\@empty%
12790 \LetLtxMacro\sishape\@empty%
12791 \LetLtxMacro\sscshape\@empty%
12792 \LetLtxMacro\itshape\@empty%
12793 \LetLtxMacro\ulcshape\@empty%
12794 \LetLtxMacro\sscshape\@empty%
12795 \LetLtxMacro\normalfont\@empty%
12796 }

```

**\sp**  $\{ \langle text \rangle \}$

For siunitx. Must work in math mode.

```
12797 \renewcommand{\sp}[1]{\text{\sup>#1</sup>}}
```

**\sb**  $\{ \langle text \rangle \}$

For siunitx. Must work in math mode.

```
12798 \renewcommand{\sb}[1]{\text{\sub>#1</sub>}}
```

`\textsuperscript`  $\{\langle text \rangle\}$

```
12799 \newrobustcmd{\LWR@HTML@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
12800 \LWR@formatted{textsuperscript}
```

`\@textsuperscript`  $\{\langle text \rangle\}$

```
12801 \newcommand{\LWR@HTML@@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
12802 \LWR@formatted{@textsuperscript}
```

`\textsubscript`  $\{\langle text \rangle\}$

```
12803 \newrobustcmd{\LWR@HTML@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
12804 \LWR@formatted{textsubscript}
```

`\@textsubscript`  $\{\langle text \rangle\}$

```
12805 \newcommand{\LWR@HTML@@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
12806 \LWR@formatted{@textsubscript}
```

`\up`  $\{\langle text \rangle\}$  Prints superscript.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
12807 \AtBeginDocument{\let\up\textsuperscript}
```

`\fup`  $\{\langle text \rangle\}$  Prints superscript.

Supports `fntcount` package.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
12808 \AtBeginDocument{\let\fup\textsuperscript}
```

`\underline`  $\{\langle text \rangle\}$

```
12809 \renewcommand{\underline}[1]{%
12810 \InlineClass%
12811 (text-decoration:underline; text-decoration-skip: auto)%
12812 {underline}{#1}%
12813 }
```

`\LWR@overline`  $\{\langle text \rangle\}$

```
12814 \newcommand{\LWR@overline}[1]{%
12815 \InlineClass%
12816 (text-decoration:overline; text-decoration-skip: auto)%
12817 {overline}{#1}%
12818 }
```

`\LWR@currenttextcolor` The color to use for text and `\rule`, defaulting to black:

```
12819 \newcommand*{\LWR@currenttextcolor}{black}
```

`\LWR@tempcolor` The color converted to HTML colorspace.  
`\LWR@tempcolortwo`

```
12820 \newcommand*{\LWR@tempcolor}{}
12821 \newcommand*{\LWR@tempcolortwo}{}
```

`\LWR@findcurrenttextcolor` Sets `\LWR@tempcolor` to the current color.

```
12822 \newcommand*{\LWR@findcurrenttextcolor}{%
12823 \renewcommand{\LWR@tempcolor}{000000}%
12824 }
```

`\LWR@textcurrentcolor` `{<text>}` Like `\textcolor` but uses the current `\color` instead.

```
12825 \NewDocumentCommand{\LWR@textcurrentcolor}{m}{%
12826 \renewcommand*{\LWR@currenttextcolor}{black}%
12827 #1%
12828 }
```

```
12829 \end{warppHTML}
```

**for PRINT output:** 12830 `\begin{warpprint}`

`\LWR@textcurrentfont` `{<text>}`

Prints the text with the current font choices.

```
12831 \newcommand*{\LWR@textcurrentfont}[1]{#1}
```

Env `LWR@blocktextcurrentfont` Prints the contents with the current font choices.

```
12832 \newenvironment*{LWR@blocktextcurrentfont}{}{}
```

`\FilenameNullify` `{<macros to nullify>}`

```
12833 \newcommand*{\FilenameNullify}[1]{}
12834 \end{warpprint}
```

## 94 Skips, spaces, font sizes

**for HTML output:** 12835 `\begin{warppHTML}`

`\`, and `\thinspace` may be redefined by other packages, so are redefined `\AtBeginDocument` here.

Direct-formatting space commands become HTML entities:

```
12836 \AtBeginDocument{
12837 \renewrobustcmd*\,}{\HTMLUnicode{202f}} % HTML thin non-breakable space
12838 \renewrobustcmd*\thinspace}{\HTMLUnicode{202f}} % HTML thin non-breakable space
12839 \renewrobustcmd*\negthinspace}{\HTMLUnicode{202f}} % HTML thin non-breakable space
12840 \renewrobustcmd*~}{\HTMLentity{nbsp}}
12841 \renewrobustcmd*\textellipsis}{\HTMLUnicode{2026}}
12842 \renewrobustcmd*\vdots}{\HTMLUnicode{22EE}}
12843 }
```

Direct-formatting font sizes are remembered for future use:

```
12844 \newcommand*\LWR@font@size}{normalsize}
12845
12846 \newrobustcmd*\LWR@HTML@normalsize}{\renewcommand*\LWR@font@size}{normalsize}}
12847 \LWR@formatted{normalsize}
12848
12849 \newrobustcmd*\LWR@HTML@small}{\renewcommand*\LWR@font@size}{small}}
12850 \LWR@formatted{small}
12851
12852 \newrobustcmd*\LWR@HTML@footnotesize}{\renewcommand*\LWR@font@size}{footnotesize}}
12853 \LWR@formatted{footnotesize}
12854
12855 \newrobustcmd*\LWR@HTML@scriptsize}{\renewcommand*\LWR@font@size}{scriptsize}}
12856 \LWR@formatted{scriptsize}
12857
12858 \newrobustcmd*\LWR@HTML@tiny}{\renewcommand*\LWR@font@size}{tiny}}
12859 \LWR@formatted{tiny}
12860
12861 \newrobustcmd*\LWR@HTML@large}{\renewcommand*\LWR@font@size}{large}}
12862 \LWR@formatted{large}
12863
12864 \newrobustcmd*\LWR@HTML@Large}{\renewcommand*\LWR@font@size}{Large}}
12865 \LWR@formatted{Large}
12866
12867 \newrobustcmd*\LWR@HTML@LARGE}{\renewcommand*\LWR@font@size}{LARGE}}
12868 \LWR@formatted{LARGE}
12869
12870 \newrobustcmd*\LWR@HTML@huge}{\renewcommand*\LWR@font@size}{huge}}
12871 \LWR@formatted{huge}
12872
12873 \newrobustcmd*\LWR@HTML@Huge}{\renewcommand*\LWR@font@size}{Huge}}
12874 \LWR@formatted{Huge}

12875 \DeclareDocumentCommand{\onecolumn}{}{}
12876
12877 \DeclareDocumentCommand{\twocolumn}{0}{}{
12878
12879 #1
12880
```

12881 }

### \hfill

```
12882 \newcommand*\LWR@HTML@hfill{\quad}
12883 \LWR@formatted{hfill}
```

### \hrulefill

```
12884 \newcommand*\LWR@HTML@hrulefill{%
12885 \ifbool{LWR@doingapar}%
12886 {\rule{1in}{1pt}}%
12887 {%
12888 \LWR@findcurrenttextcolor%
12889 \ifdefstring{LWR@tempcolor}{000000}%
12890 {%
12891 \begin{BlockClass}{hrule}%
12892 \end{BlockClass}%
12893 }%
12894 {%
12895 \begin{BlockClass}[%
12896 border-top: 1px solid \LWR@origpound\LWR@tempcolor % space
12897]{hrule}%
12898 \end{BlockClass}%
12899 }%
12900 }%
12901 }%
12902 \LWR@formatted{hrulefill}
```

### \dotfill

```
12903 \newcommand*\LWR@HTML@dotfill{\dots}
12904 \LWR@formatted{dotfill}
```

### \newpage

```
12905 \renewcommand*\newpage{%
12906
12907 }
```

### \newline

Uses the HTML `<br />` element.

```
12908 \newrobustcmd*\LWR@newlinebr{\unskip\LWR@htmltag{br /}\LWR@orignewline}%
12909 \LetLtxMacro\newline\LWR@newlinebr
```

`\` Redefined to `\LWR@endofline` or `\LWR@tabularendofline`.

`\LWR@endofline` \* [*len*]

`\` is assigned to `\LWR@endofline` at `\LWR@LwarpStart`.

Inside tabular, `\` is temporarily changed to `\LWR@tabularendofline`.

```
12910 \LetLtxMacro\LWR@origendofline\
12911 \NewDocumentCommand{\LWR@endofline}{s O{0pt}}
12912 {%
12913 \newline%

12914 \setlength{\LWR@templengthone}{#2}%
12915 \ifdimgreater{\LWR@templengthone}{0pt}{\newline}{}%
12916 }
```

`\LWR@minipagestartpars` Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a `<div>` to be inside a `p`, paragraphs must be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, `lwarp` correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to be on its own line. Since people often place small horizontal space between minipages, `lwarp` tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around `\hspace`, `\enskip`, `\quad`, and `\qqquad` until the end of the paragraph, when the closing `p` tag is created.

When a minipage is seen, the boolean `LWR@minipagethispar` is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. `LWR@minipagethispar` is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before `\hspace`, `\quad`, or `\qqquad`'s HTML output.

```
12917 \newcommand*{\LWR@minipagestartpars}{%
12918 \ifbool{LWR@minipagethispar}{\LWR@startpars}{}%
12919 }
```

`\LWR@minipagestoppars` Placed just after `\hspace`, `\quad`, or `\qqquad`'s HTML output.

```
12920 \newcommand*{\LWR@minipagestoppars}{%
12921 \ifbool{LWR@minipagethispar}{\LWR@stoppars}{}%
12922 }
```

`\quad` Handles special minipage & horizontal space interactions. Uses `2003 EM SPACE` to pass validation.

```
12923 \renewrobustcmd*{\quad}{%
12924 \LWR@minipagestoppars%
12925 \HTMLunicode{2003}%
12926 \LWR@minipagestartpars%
12927 }
```

`\qqquad` Handles special minipage & horizontal space interactions.

```
12928 \renewrobustcmd*{\qqquad}{\quad\quad}
```

`\enskip` Handles special minipage & horizontal space interactions.

```
12929 \renewrobustcmd*{\enskip}{%
12930 \LWR@minipagestoppars%
12931 \HTMLUnicode{2002}%
12932 \LWR@minipagestartpars%
12933 }
```

Len `\LWR@tempwidth` Used to compute span width, height, raise for `\hspace` and `\rule`:

```
Len \LWR@tempheight
12934 \newlength{\LWR@tempwidth}
Len \LWR@tempraise
12935 \newlength{\LWR@tempheight}
12936 \newlength{\LWR@tempraise}
```

```
\LWR@select@html@hspace * {\langle length \rangle} * {\langle length \rangle}
\hspace
```

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

`\hspace{\fill}` is converted to `\hspace{2em}`, equal to `\qqquad`.

```
12937 \newcommand{\LWR@select@html@hspace}{%
12938 \RenewDocumentCommand{\hspace}{s m}{%
12939 \setlength{\LWR@tempwidth}{##2}%
```

If `\fill`, change to `\qqquad`:

```
12940 \ifnum\gluestretchorder\LWR@tempwidth>0%
12941 \setlength{\LWR@tempwidth}{2em}%
12942 \fi%
```

Only if the width is greater than zero:

```
12943 \ifdimcomp{\LWR@tempwidth}{>}{0pt}{%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
12944 \LWR@minipagestoppars%
```

Support the HTML thin wrappable space:

```
12945 \ifdimcomp{\LWR@tempwidth}{=}{.16667em}%
12946 {%
12947 \HTMLUnicode{2009}% thin breakable space
12948 }%
```

Print the span with the converted width. Not rounded.

```
12949 {%
12950 \LWR@htmltagc{%
12951 span style="width:\LWR@printlength{\LWR@tempwidth}; % extra space
```

```

12952 display:inline-block"%
12953 }%

```

If formatting for a word processor, approximate with a number of \quads, in case a span of a given width is not supported:

```

12954 \ifbool{FormatWP}{%
12955 \setlength{\LWR@templengthone}{\LWR@tempwidth}%
12956 \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
12957 \quad%
12958 \addtolength{\LWR@templengthone}{-1em}%
12959 }%
12960 }%

```

If NOT formatting for a word processor, include an empty comment to avoid an empty span:

```

12961 {\LWR@htmlcomment{}}%

```

Close the span:

```

12962 \LWR@htmltagc{/span}%
12963 }%

```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```

12964 \LWR@minipagestartpars%
12965 }{}% width greater than 0
12966 }%
12967 }

```

```

\LWR@select@html@nohspace *{\length}
\hspace

```

Used to disable \hspace while creating description \items.

```

12968 \newcommand{\LWR@select@html@nohspace}{%
12969 \RenewDocumentCommand{\hspace}{s m}{}%
12970 }

```

```

\LWR@select@print@hspace

```

```

12971 \newcommand*{\LWR@select@print@hspace}{%
12972 \renewrobustcmd\hspace{\@ifstar\@hspace\@hspacer\@hspace}%
12973 }

```

```

\hspace *{\length}

```

Handles special minipage & horizontal space interactions.

```

12974 \LWR@select@html@hspace

```

`\LWR@vspace` \*  $\langle length \rangle$  Nullified `vspace`.

```
12975 \NewDocumentCommand{\LWR@HTML@vspace}{s m}{}
12976
12977 \LWR@formatted{vspace}
```

`\linebreak` [ $\langle num \rangle$ ] Inserts an HTML `br` tag.

```
12978 \renewcommand*\linebreak[1][\newline}
```

`\nolinebreak` [ $\langle num \rangle$ ]

```
12979 \renewcommand*\nolinebreak[1][{}]
```

`\pagebreak` [ $\langle num \rangle$ ] Starts a new paragraph.

```
12980 \renewcommand*\pagebreak[1][{}
12981
12982 }
```

`\nopagebreak` [ $\langle num \rangle$ ]

```
12983 \renewcommand*\nopagebreak[1][{}]
```

`\enlargethispage` \*  $\langle len \rangle$

```
12984 \RenewDocumentCommand{\enlargethispage}{s m}{}

```

`\clearpage`

`\cleardoublepage`

```
12985 \renewcommand*\clearpage{}
12986 \renewcommand*\cleardoublepage{}

```

`\rule` [ $\langle raise \rangle$ ] [ $\langle width \rangle$ ] [ $\langle height \rangle$ ]

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

`\fill` is zero-width, so `\hspace{\fill}` is ignored.

```
12987 \newcommand*\LWR@HTML@rule[3][\%

```

The width is copied into a temporary L<sup>A</sup>T<sub>E</sub>X length, from which comparisons and conversions may be made:

```
12988 \setlength{\LWR@tempwidth}{#2}%

```

If it's zero-width then skip the entire rule:

```
12989 \ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}%
12990 {}% zero- width
12991 {% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
12992 \ifthenelse{%
12993 \lengthtest{\LWR@tempwidth>0pt}\AND%
12994 \lengthtest{\LWR@tempwidth<1pt}}%
12995 }%
12996 {\setlength{\LWR@tempwidth}{1pt}}%
12997 {}%
```

Likewise with height:

```
12998 \setlength{\LWR@tempheight}{#3}%
12999 \ifthenelse{%
13000 \lengthtest{\LWR@tempheight>0pt}\AND%
13001 \lengthtest{\LWR@tempheight<1pt}}%
13002 }%
13003 {\setlength{\LWR@tempheight}{1pt}}%
13004 {}%
```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```
13005 \LWR@minipagestoppars%
```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in L<sup>A</sup>T<sub>E</sub>X code.

```
13006 \LWR@findcurrenttextcolor%
13007 \LWR@htmltagc{%
13008 span\LWR@indentHTML%
13009 style="%
```

The HTML background color is used to draw the filled rule according to the L<sup>A</sup>T<sub>E</sub>X foreground color set by `\textcolor`.

```
13010 \ifbool{FormatWP}{\background:\LWR@currenttextcolor ; }%
```

The width and height are printed, converted to PT:

```
13011 width:\LWR@printlength{\LWR@tempwidth} ; %
13012 height:\LWR@printlength{\LWR@tempheight} ; %
```

The raise height is converted to a CSS transform. The \*2 raise multiplier is to approximately match HTML output's X height. Conversion to a L<sup>A</sup>T<sub>E</sub>X length allows a typical L<sup>A</sup>T<sub>E</sub>X expression to be used as an argument for the raise, whereas printing the raise argument directly to HTML output without conversion to a L<sup>A</sup>T<sub>E</sub>X length limits the

allowable syntax. To do: A superior method would compute a ratio of  $\text{\LaTeX}$  ex height, then print that to HTML with an ex unit.

```

13013 \ifblank{#1}%
13014 {}%
13015 {%
13016 \setlength{\LWR@tempraise}{0pt-#1}%
13017 \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
13018 \LWR@indentHTML%
13019 -ms-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
13020 \LWR@indentHTML%
13021 -webkit-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
13022 \LWR@indentHTML%
13023 transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
13024 \LWR@indentHTML%
13025 }%
```

Display inline-block to place the span inline with the text:

```

13026 display:inline-block;"\LWR@orignewline%
13027 }%
```

If formatting for a word processor, approximate with a number of underscores, in case a span of a given width is not supported:

```

13028 \ifbool{FormatWP}{%
13029 \setlength{\LWR@templengthone}{\LWR@tempwidth}%
13030 \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
13031 _{}%
13032 \addtolength{\LWR@templengthone}{-1em}%
13033 }%
13034 }%
```

If NOT formatting for a word processor, add a comment to avoid an empty `<span>`:

```

13035 {\LWR@htmlcomment{}}%
```

Close the span:

```

13036 \LWR@htmltagc{/span}%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```

13037 \LWR@minipagestartpars%
13038 }% non-zero width
13039 }
13040
13041 \LWR@formatted{rule}

13042 \end{warpHTML}
```

## 95 \phantomsection

**for HTML output:** 13043 \begin{warpHTML}

\LWR@phantomsection Emulate the hyperref \phantomsection command, often used to insert the bibliography into the table of contents. Ignores \ForceHTMLTOC.

```
13044 \newrobustcmd*{\LWR@phantomsection}{%
13045 \begingroup%
13046 \boolfalse{LWR@forcinghtmltoc}%
13047 \section*{}}%
13048 \endgroup%
13049 }
```

```
13050 \end{warpHTML}
```

## 96 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally set by \LWR@formatted.

For CSS conversions, see:

<http://edward.oconnor.cx/2007/08/tex-poshlet>

<http://nitens.org/taraborelli/texlogo>

and the spacing described in the metafont package documentation.

```
for HTML & PRINT: 13051 \begin{warpall}
13052 \newbool{LWR@warnXe}
13053 \boolfalse{LWR@warnXe}
13054
13055 \newrobustcmd*{\Xe}
13056 {%
13057 X\hspace{-.1667em}\raisebox{-.5ex}{E}%
13058 \global\booltrue{LWR@warnXe}%
13059 }
13060
13061 \AtBeginDocument{
13062 \@ifpackageloaded{graphics}{
13063 \@ifpackageloaded{metalogo}{%
13064 \renewrobustcmd*{\Xe}
13065 {X\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}}
13066 }
13067 }{}
13068 }
13069
13070 \AtEndDocument{
13071 \ifbool{LWR@warnXe}{
```

```

13072 \PackageWarningNoLine{lwarp}{Load graphicx or graphics
13073 for improved XeTeX logo}
13074 }{}
13075 }
13076
13077 \providerobustcmd*{\XeTeX}{\mbox{\Xe\hspace{- .125em}\TeX}}
13078 \providerobustcmd*{\XeLaTeX}{\mbox{\Xe\hspace{- .125em}\LaTeX}}
13079 \providerobustcmd*{\AmS}{%
13080 \leavevmode\hbox{$\mathcal A\kern-.2em\lower.376ex%
13081 \hbox{$\mathcal M$}\kern-.2em\mathcal S$}%
13082 }
13083 \newrobustcmd*{\LyX}{\textsf{LyX}}
13084 \providerobustcmd*{\LuaTeX}{\mbox{Lua\TeX}}
13085 \providerobustcmd*{\LuaLaTeX}{\mbox{Lua\LaTeX}}
13086 \providerobustcmd*{\BibTeX}{\mbox{B\textsc{ib}\TeX}}
13087 \providerobustcmd*{\MakeIndex}{\mbox{\textit{MakeIndex}}}
13088 \providerobustcmd*{\ConTeXt}{\mbox{Con\TeX{t}}}
13089 \providerobustcmd*{\MiKTeX}{\mbox{MiK\TeX}}
13090 \end{warpall}

```

**for HTML output:** 13091 \begin{warpHTML}

The print-mode versions of the following may be changed by `metalogo`, so their print formatting is recorded `\AtBeginDocument`.

`\TeX` `TEX`

`latexlogo` is a css class used to properly typeset the E and A in `LATEX` and friends.

`latexlogofont` is a css class used to select the font for the rest of the logo in `LATEX`, `LuaTeX`, `ConTeXt`, etc.

```

13092 \newrobustcmd*{\LWR@HTML@TeX}
13093 {%
13094 \InlineClass{latexlogofont}%
13095 {%
13096 \InlineClass{latexlogo}%
13097 {%
13098 T%
13099 \InlineClass{latexlogosub}{e}%
13100 X%
13101 }%
13102 }%
13103 }
13104 \AtBeginDocument{\LWR@formatted{TeX}}% may have been patched by metalogo

```

`\LaTeX` `LATEX`, `LATEX 2ε`

`\LaTeXe`

```

13105 \newrobustcmd*{\LWR@HTML@LaTeX}
13106 {%
13107 \InlineClass{latexlogofont}%
13108 {%
13109 \InlineClass{latexlogo}%
13110 {%

```

```

13111 L%
13112 \InlineClass{latexlogosup}{a}%
13113 T%
13114 \InlineClass{latexlogosub}{e}%
13115 X%
13116 }%
13117 }%
13118 }
13119
13120 \AtBeginDocument{\LWR@formatted{LaTeX}}% may have been patched by metalogo
13121
13122
13123 \newrobustcmd*{\LWR@HTML@LaTeXe}
13124 {%
13125 \LaTeX%
13126 \InlineClass{latexlogofont}{%
13127 \InlineClass{latexlogotwoe}{%
13128 2%
13129 \InlineClass{latexlogotwoesub}{\HTMLUnicode{03B5}}%
13130 }%
13131 }%
13132 }
13133 \AtBeginDocument{\LWR@formatted{LaTeXe}}% may have been patched by metalogo

```

\LuaTeX LuaTeX, Lua<sup>A</sup>TeX

\LuaLaTeX

```

13134 \newrobustcmd*{\LWR@HTML@LuaTeX}{\InlineClass{latexlogofont}{Lua}\TeX}
13135 \AtBeginDocument{\LWR@formatted{LuaTeX}}% may have been patched by metalogo
13136
13137 \newrobustcmd*{\LWR@HTML@LuaLaTeX}{\InlineClass{latexlogofont}{Lua}\LaTeX}
13138 \AtBeginDocument{\LWR@formatted{LuaLaTeX}}% may have been patched by metalogo

```

\XeTeX XeTeX, Xe<sup>A</sup>TeX

\XeLaTeX

xetexlogo is a css class which aligns the backwards E in XeTeX and spaces TeX appropriately.

xelatexlogo is a css class which aligns the backwards E in Xe<sup>A</sup>TeX and spaces <sup>A</sup>TeX appropriately.

```

13139 \newrobustcmd*{\LWR@HTML@Xe}
13140 {%
13141 X%
13142 \InlineClass{xelatexlogosub}{\HTMLUnicode{18e}}%
13143 }
13144 \AtBeginDocument{\LWR@formatted{Xe}}% may have been patched by metalogo
13145
13146 \newrobustcmd*{\LWR@HTML@XeTeX}{\InlineClass{xelatexlogo}{Xe}\TeX}
13147 \AtBeginDocument{\LWR@formatted{XeTeX}}% may have been patched by metalogo
13148
13149 \newrobustcmd*{\LWR@HTML@XeLaTeX}{\InlineClass{xelatexlogo}{Xe}\LaTeX}
13150 \AtBeginDocument{\LWR@formatted{XeLaTeX}}% may have been patched by metalogo

```

`\ConTeXt` **ConTeXt**

```

13151 \newrobustcmd*{\LWR@HTML@ConTeXt}{%
13152 \InlineClass{latexlogofont}{Con}\TeX{}}%
13153 \InlineClass{latexlogofont}{t}%
13154 }
13155 \LWR@formatted{ConTeXt}

```

`\BibTeX` **BIB<sub>T</sub>X**, *MakeIndex*`\MakeIndex`

```

13156 \newrobustcmd*{\LWR@HTML@BibTeX}
13157 {\InlineClass{latexlogofont}{B\textsc{ib}}\TeX}
13158 \LWR@formatted{BibTeX}
13159
13160 \newrobustcmd*{\LWR@HTML@MakeIndex}
13161 {\InlineClass{latexlogofont}{\textit{MakeIndex}}}
13162 \LWR@formatted{MakeIndex}

```

`\AmS` **AMS**

`amslogo` is a css class used for the **AMS** logo.

```

13163 \AtBeginDocument{%
13164 \newrobustcmd*{\LWR@HTML@AmS}
13165 {%
13166 \InlineClass{amslogo}{%
13167 \textit{%
13168 A%
13169 \InlineClass{latexlogosub}{M}%
13170 S%
13171 }}%
13172 }%
13173 }%
13174 \LWR@formatted{AmS}
13175 }

```

`\MiKTeX` **MiKTeX**

```

13176 \newrobustcmd*{\LWR@HTML@MiKTeX}{\InlineClass{latexlogofont}{MiK}\TeX}
13177 \LWR@formatted{MiKTeX}

```

`\LyX` **LyX**

`lyxlogo` is a css class used for the **LyX** logo.

```

13178 \newrobustcmd*{\LWR@HTML@LyX}{\InlineClass{lyxlogo}{LyX}}
13179 \LWR@formatted{LyX}

```

```

13180 \end{warpHTML}

```

## 97 Starting and stopping lwarp

**for HTML output:** 13181 \begin{warpHTML}

\LWR@LwarpStart Automatically sets up the HTML-related actions for the start and end of the document.

```
\LWR@LwarpEnd
13182 \AfterEndPreamble{\LWR@LwarpStart}
13183 \AtEndDocument{\LWR@LwarpEnd}

13184 \end{warpHTML}
```

## 98 Loading everyshi patches

everyshi is emulated by the L<sup>A</sup>T<sub>E</sub>X core, so its patches are loaded here. \AtBeginDocument is used in case an older version of L<sup>A</sup>T<sub>E</sub>X is used.

**for HTML output:** 13185 \begin{warpHTML}  
13186 \AtBeginDocument{  
13187 \ifpackageloaded{everyshi}{  
13188 \RequirePackage{lwarp-everyshi}  
13189 }{ }  
13190 }  
13191 \end{warpHTML}

## 99 Loading textcomp patches

textcomp has now been integrated into the L<sup>A</sup>T<sub>E</sub>X core, so its patches are loaded now.

**for HTML output:** 13192 \begin{warpHTML}  
13193 \RequirePackage{lwarp-textcomp}  
13194 \end{warpHTML}

## 100 Loading amsmath, amsthm patches, centernot

amsmath, amsthm, and centernot may have been preloaded, such as by newtx, so their patches are loaded now.

**for HTML output:** 13195 \begin{warpHTML}  
13196 \ifpackageloaded{amsthm}{  
13197 \RequirePackage{lwarp-amsthm}  
13198 }{ }  
  
13199 \ifpackageloaded{amsmath}{  
13200 \RequirePackage{lwarp-amsmath}  
13201 }{ }

amsthm may load centernot, so centernot must be checked second.

```
13202 \@ifpackageloaded{centernot}{
13203 \RequirePackage{lwarp-centernot}
13204 }{}
13205 \end{warpHTML}
```

## 101 Loading KOMA-SCRIPT class patches

Load patches to koma-script.

```
for HTML output: 13206 \begin{warpHTML}

13207 \@ifclassloaded{scrbook}{\RequirePackage{lwarp-patch-komascript}}{}
13208 \@ifclassloaded{scrartcl}{\RequirePackage{lwarp-patch-komascript}}{}
13209 \@ifclassloaded{scrreprt}{\RequirePackage{lwarp-patch-komascript}}{}

13210 \end{warpHTML}
```

## 102 Loading MEMOIR class patches

Load patches to memoir.

```
for HTML & PRINT: 13211 \begin{warpprint}
13212 \@ifclassloaded{memoir}{\LWR@origRequirePackage{xcolor}}{}
13213 \end{warpprint}

for HTML output: 13214 \begin{warpHTML}
13215 \@ifclassloaded{memoir}{\RequirePackage{lwarp-patch-memoir}}{}
13216 \end{warpHTML}
```

## 103 ut\* class patches

Load patches to uj\* and ut\* classes, as well as ltj\* classes.

```
for HTML output: 13217 \begin{warpHTML}

13218 \newcommand*{\LWR@patchujtclasses}{

 uj/t does not use \partname

13219 \def\@partnameformat{}

13220 \def\@partcntformat##1{%
13221 \prepartname%
```

```

13222 \csname the##1\endcsname%
13223 \postpartname%
13224 \quad%
13225 }
13226 \@ifundefined{chapter}{}{
13227 \def\@chapcntformat##1{%
13228 \prechaptername%
13229 \csname the##1\endcsname%
13230 \postchaptername%
13231 \quad%
13232 }
13233 }
13234 \renewcommand*\LWR@printchaptername{}

```

Use decimal points instead of centered dots:

```

13235 \renewcommand{\thepart}{\@Roman\c@part}
13236 \@ifundefined{chapter}{
13237 \renewcommand{\thesection}{\@arabic\c@section}
13238 }{
13239 \renewcommand{\thechapter}{\@arabic\c@chapter}
13240 \renewcommand{\thesection}{\thechapter.\@arabic\c@section}
13241 }
13242 \renewcommand{\thesubsection}{\thesection.\@arabic\c@subsection}
13243 \renewcommand{\thesubsubsection}{%
13244 \thesubsection.\@arabic\c@subsubsection}
13245 \renewcommand{\theparagraph}{%
13246 \thesubsubsection.\@arabic\c@paragraph}
13247 \renewcommand{\thesubparagraph}{%
13248 \theparagraph.\@arabic\c@subparagraph}
13249 \@ifundefined{chapter}{
13250 \renewcommand{\thefigure}{\@arabic\c@figure}
13251 \renewcommand{\thetable}{\@arabic\c@table}
13252 }{
13253 \renewcommand{\thefigure}{%
13254 \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@figure}
13255 \renewcommand{\thetable}{%
13256 \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@table}
13257 }
13258 }
13259
13260 \@ifclassloaded{ujarticle}{\LWR@patchujtclasses}{}
13261 \@ifclassloaded{ujbook}{\LWR@patchujtclasses}{}
13262 \@ifclassloaded{ujreport}{\LWR@patchujtclasses}{}
13263 \@ifclassloaded{utarticle}{\LWR@patchujtclasses}{}
13264 \@ifclassloaded{utbook}{\LWR@patchujtclasses}{}
13265 \@ifclassloaded{utreport}{\LWR@patchujtclasses}{}
13266 \@ifclassloaded{ltjarticle}{\LWR@patchujtclasses}{}
13267 \@ifclassloaded{ltjbook}{\LWR@patchujtclasses}{}
13268 \@ifclassloaded{ltjreport}{\LWR@patchujtclasses}{}
13269 \@ifclassloaded{ltjsarticle}{\LWR@patchujtclasses}{}
13270 \@ifclassloaded{ltjsbook}{\LWR@patchujtclasses}{}
13271 \@ifclassloaded{ltjsreport}{\LWR@patchujtclasses}{}
13272 \@ifclassloaded{ltjskiyou}{\LWR@patchujtclasses}{}
13273 \@ifclassloaded{ltjspf}{\LWR@patchujtclasses}{}

```

```

13274 \@ifclassloaded{ltjtarticle}{\LWR@patchujtclasses}{}
13275 \@ifclassloaded{ltjtbook}{\LWR@patchujtclasses}{}
13276 \@ifclassloaded{ltjtreport}{\LWR@patchujtclasses}{}

13277 \end{warpHTML}

```

## 104 CTEX patches

Patches for `ctex` and related classes, which are loaded before `lwarp`.

All CTEX classes and the `ctex` package seem to load `ctexpatch`, so its presence is used to decide whether to have `lwarp` patch CTEX.

**for HTML output:** 13278 \begin{warpHTML}

\AtBeginDocument in case the user set `FileSectionNames` in the preamble.

```

13279 \AtBeginDocument{
13280 \@ifpackageloaded{ctexpatch}{%
13281 \def\@partcntformat#1{%
13282 \LWR@isolate{\CTEX@partname}~%
13283 \CTEX@part@aftername%
13284 }%
13285
13286 \def\@partnameformat{}
13287
13288 \def\@chapcntformat#1{%
13289 \LWR@isolate{\CTEX@chaptername}~%
13290 \CTEX@chapter@aftername%
13291 }%
13292
13293 \renewcommand*\LWR@printchaptername{}
13294 }{}
13295 }

13296 \end{warpHTML}

```

## 105 kotexutf patches

Patch for `kotexutf`, which is loaded before `lwarp`.

`kotexutf`'s `\@setref` was conflicting with `lwarp`'s cross references.

**for HTML output:** 13297 \begin{warpHTML}

If `kotexutf`'s version of `\@setref` is detected, it is reverted to the original.

```

13298 \AtBeginDocument{
13299 \@ifpackageloaded{kotexutf}{%

```

```

13300 \def\LWR@kotexutf@setref#1#2#3{%
13301 \@setref@dhucs@orig{#1}{#2}{#3}%
13302 \ifx#1\relax\else
13303 \bgroup
13304 \dhucs@make@CJKchar@null
13305 \edef\@temp{\expandafter#2#1}\global\josatoks\expandafter{\@temp}%
13306 \egroup
13307 \fi%
13308 }%
13309
13310 \ifdefequal{\@setref}{\LWR@kotexutf@setref}{
13311 \let\@setref\@setref@dhucs@orig
13312 }{}
13313 }{}
13314 }

13315 \end{warpHTML}

```

## 106 babel and polyglossia warnings

lwarp prints a message instructing the user how to avoid the following error.

(These are not `\PackageWarnings` because there may not be a problem.)

lwarp uses `cleveref`, which has some limitations when using `polyglossia`, possibly resulting in the error

```
! Undefined control sequence. . . . \@begindocumenthook
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by `cleveref`, then select other languages using `\setotherlanguages`.

Once the print version works with `cleveref` and `polyglossia`, the HTML version should work as well using `lwarp`.

```

for HTML output: 13316 \begin{warpHTML}
13317 \AtBeginDocument{
13318
13319 \ifpackageloaded{polyglossia}{
13320 \PackageWarningNoLine{lwarp}
13321 {%
13322 Polyglossia has been loaded. Lwarp also uses cleveref.\MessageBreak
13323 See the cleveref documentation regarding\MessageBreak
13324 polyglossia support. Some languages are not supported%

```

```

13325 }
13326 \typeout{---}
13327 \typeout{Package lwarp:}
13328 \typeout{If the error}
13329 \typeout{\space\space‘! Undefined control sequence.
13330 \space ... \space \protect\@begindocumenthook’}
13331 \typeout{occurs here, use the polyglossia macro:}
13332 \typeout{\space\space\protect\setmainlanguage\protect{...\protect}}
13333 \typeout{---}
13334 }{
13335 \@ifpackageloaded{babel}{
13336 \PackageWarningNoLine{lwarp}
13337 {%
13338 Babel has been loaded. Lwarp also uses cleveref.\MessageBreak
13339 See the cleveref documentation regarding\MessageBreak
13340 babel support. Some languages are not supported%
13341 }
13342 }{}
13343 }
13344
13345 }
13346 \end{warpHTML}

```

## 107 MATHJAX warnings

`\LWR@mathjaxwarn`  $\langle packagename \rangle$   $\langle More\ text. \rangle$

To be done `\AtBeginDocument`.

```

13347 \newcommand*\LWR@mathjaxwarn}[2]{%
13348 \@ifpackageloaded{lwarp-#1}{%
13349 \ifblank{#2}{%
13350 \PackageWarningNoLine{lwarp}
13351 {%
13352 Lwarp provides emulation for MathJax when used\MessageBreak
13353 with the #1 package%
13354 }
13355 }{%
13356 \PackageWarningNoLine{lwarp}
13357 {%
13358 Lwarp provides emulation for MathJax when used\MessageBreak
13359 with the #1 package.\MessageBreak
13360 #2%
13361 }
13362 }%
13363 }{}%
13364 }
13365
13366 \AtBeginDocument{
13367 \ifbool{mathjax}{
13368 \LWR@mathjaxwarn{arydshln}
13369 {In a math array, do not use the optional argument\MessageBreak

```

```

13370 for \protect\cdashline.\space\space
13371 Furthermore, \protect\cline\space is not\MessageBreak
13372 supported by MathJax}
13373 \LWR@mathjaxwarn{autonum}
13374 {MathJax does not support equation+.\MessageBreak
13375 You may use the warpprint and warpHTML\MessageBreak
13376 environments to isolate the package load\MessageBreak
13377 and the equation+ environments}
13378 \LWR@mathjaxwarn{backnaur}
13379 {You may enclose its uses inside\MessageBreak
13380 lateximage environments to force SVG output,\MessageBreak
13381 but this also changes the print output}
13382 \LWR@mathjaxwarn{bigdelim}
13383 {Delimiters appear only of the first line}
13384 \LWR@mathjaxwarn{booktabs}
13385 {In a math array, do not use (trim) for \protect\cmidrule}
13386 \LWR@mathjaxwarn{breqn}
13387 {Each environment becomes an SVG image}
13388 \LWR@mathjaxwarn{delarray}
13389 {Enclose its uses inside lateximage\MessageBreak
13390 environments to force SVG output}
13391 \LWR@mathjaxwarn{jkmath}{ }
13392 \LWR@mathjaxwarn{mathtools}
13393 {See the Lwarp manual regarding the disallowspaces\MessageBreak
13394 and showonlyrefs options, the alignat environment,\MessageBreak
13395 and \protect\DeclarePairedDelimiter\space and related%
13396 }
13397 \LWR@mathjaxwarn{mathspec}
13398 {Double quotes are removed, even inside \protect\text}
13399 \LWR@mathjaxwarn{multirow}
13400 {Multirow works as expected in text mode, but\MessageBreak
13401 limited emulation is provided for MathJax math.\MessageBreak
13402 \protect\multirow\space ignores all arguments except\MessageBreak
13403 the text}
13404 \LWR@mathjaxwarn{pb-diagram}
13405 {Enclose its uses inside lateximage environments\MessageBreak
13406 to force SVG output}
13407 % \LWR@mathjaxwarn{physics}
13408 % {The third-party extension is not used.\MessageBreak
13409 % {The MathJax v3 extension is used.\MessageBreak
13410 % See the Lwarp manual for details}
13411 \LWR@mathjaxwarn{unicode-math}
13412 {Do not use embedded Unicode characters.\MessageBreak
13413 Not all characters are encoded correctly.\MessageBreak
13414 \protect\left\space and \protect\right\space may not work.\MessageBreak
13415 Some symbol fonts are not supported by MathJax,\MessageBreak
13416 and are only approximated.\MessageBreak
13417 Latin characters may not be correct}
13418 \LWR@mathjaxwarn{witharrows}
13419 {Arrows can only point to the next line.\MessageBreak
13420 Text is only placed on a single line}
13421 \LWR@mathjaxwarn{xy}
13422 {xy works in text, but in math you must\MessageBreak
13423 enclose its uses inside lateximage\MessageBreak
13424 environments to force SVG output}

```

```
13425 }{}
13426 }
```

---

 File 2 **lwarp-2in1.sty**

§ 108 Package **2in1**

Pkg 2in1 2in1 is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{2in1}

---

 File 3 **lwarp-2up.sty**

§ 109 Package **2up**

Pkg 2up 2up is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{2up}[2010/05/15]

```

2 \def\source#1#2#3{}
3 \def\target#1#2#3{}
4 \def\targetlayout#1{}
5 \newdimen\pageseplength
6 \newdimen\pagesepwidth
7 \newdimen\pagesepoffset
8 \def\twoupeemptypage{}
9 \def\twoupclearpage{}
10 \def\twoupeject{}
11 \def\twouparticle{}
12 \def\twouplain{}
13 \def\twouplegaltarget{}
14 \def\twouplandscape{}
15 \def\twoupwrites{}

```

---

 File 4 **lwarp-a4.sty**

§ 110 Package **a4**

Pkg a4 a4 is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{a4}[2004/04/15]

```

2 \newcommand*{\WideMargins}{}

```

File 5 **lwarp-a4wide.sty**§ 111 Package **a4wide**

Pkg a4wide a4wide is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{a4wide}[1994/08/30]

File 6 **lwarp-a5comb.sty**§ 112 Package **a5comb**

Pkg a5comb a5comb is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{a5comb}

File 7 **lwarp-abstract.sty**§ 113 Package **abstract**

*(Emulates or patches code by PETER WILSON.)*

Pkg abstract abstract is supported and patched by lwarp.

 **missing TOC** If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

**for HTML output:** memoir provides an abstract environment even though it is not an article or report class. Meanwhile, lwarp loads book to emulate memoir, but book does not have an abstract environment, so when the abstract package is loaded for emulation there is no pre-existing abstract to redefine, which would cause an error. Thus, a null abstract is provide here:

```
1 \ProvideDocumentEnvironment{abstract}{}{}{}
```

Accept all options for lwarp-abstract:

```
2 \LWR@ProvidesPackagePass{abstract}[2009/06/08]
```

```
3 \AtBeginDocument{
4 \BeforeBeginEnvironment{abstract}{
5 \LWR@forcenewpage
6 \BlockClass{abstract}
```

```

7 }
8 \AfterEndEnvironment{abstract}{\endBlockClass}
9 }
10
11 \renewcommand{@bsrunintitle}{%
12 \hspace*{\abstitleskip}%
13 {\abstractnamefont%
14 \InlineClass{abstractrunintitle}{\abstractname}%
15 \@bslabeldelim}%
16 }

17 \@ifclassloaded{memoir}
18 {
19 \renewenvironment{abstract}{%
20 % \titlepage
21 % \null\vfil
22 % \@beginparpenalty\@lowpenalty
23 \setupabstract
24 \if@bsrunin
25 \else
26 % \if@bsstyle
27 % \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
28 % \else
29 % \ifnumber@bs
30 % \num@bs
31 % \else
32 % \begin{\absnamepos}%
33 \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
34 % \endparpenalty\@M
35 % \end\absnamepos%
36 % \vspace{\abstitleskip}%
37 % \fi
38 % \fi
39 % \vspace{\abstitleskip}%
40 \fi
41 \put@bsintoc%
42 \begin{@bsrunintitle}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
43 {\par\end{@bsrunintitle}\vfil\null%\endtitlepage
44 }
45 }{% not memoir
46 \if@titlepage
47 \renewenvironment{abstract}{%
48 % \titlepage
49 % \null\vfil
50 % \@beginparpenalty\@lowpenalty
51 % \if@bsrunin
52 % \else
53 % \if@bsstyle
54 % \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
55 % \else
56 % \ifnumber@bs
57 % \num@bs
58 % \else
59 % \begin{\absnamepos}%
60 \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}

```

```

61 \endparpenalty\@M
62 \end\absnamepos%
63 %% \vspace{\abstitlekip}%
64 \fi
65 \fi
66 \vspace{\abstitlekip}%
67 \fi
68 \put@bsintoc%
69 \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
70 {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
71 }
72 \else
73 \renewenvironment{abstract}{%
74 \if@bsrunin
75 \else
76 \if@bsstyle
77 \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
78 \else
79 \ifnumber@bs
80 \num@bs
81 \else
82 \begin{\absnamepos}%
83 \abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
84 \end\absnamepos%
85 %% \vspace{\abstitlekip}%
86 \fi
87 \fi
88 \vspace{\abstitlekip}%
89 \fi
90 \put@bsintoc%
91 \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
92 {\par\end{@bstr@ctlist}}
93 \fi
94 }% not memoir

```

---

## File 8 **lwarp-academics.sty**

### § 114 Package **academics**

*(Emulates or patches code by DIOGO A. B. FERNANDES.)*

Pkg academics **academics** is patched for use by **lwarp**.

If `\aiicon` is used, the name of the icon is used in the `alt` tag. Otherwise, for each of the individual icon macros, a generic `alt` tag is used.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{academics}[2018/06/27]
2 \LetLtxMacro\LWR@orig@symbol\symbol
3
4 \let\LWR@academics@orig@AI\AI
5
6 \newcommand*{\LWR@academics@symbol}[1]{%

```

```

7 \begin{lateximage}*[academicon][academicons#1]%
8 \begingroup%
9 \LWR@academicons@orig@AI%
10 \LWR@orig@symbol{#1}%
11 \endgroup%
12 \end{lateximage}%
13 }
14
15 \renewcommand*{\AI}{%
16 \LetLtxMacro\symbol\LWR@academicons@symbol%
17 }
18
19 \renewcommand*{\aiicon}[1]
20 {%
21 \begin{lateximage}*[#1 icon][academicons#1]%
22 \AI\csname aiicon@#1\endcsname%
23 \end{lateximage}%
24 }

```

---

File 9 **lwarp-accents.sty**

§ 115 Package **accents**

(Emulates or patches code by JAVIER BEZOS.)

Pkg accents accents is used as-is for SVG math, and is emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{accents}[2006/05/12]

For MATHJAX:

```

2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{accents}
4
5 \CustomizeMathJax{\newcommand{\ring}[1]{\mathring{#1}}}
6 \CustomizeMathJax{\newcommand{\accentset}[2]{\overset{#1}{#2}}}

```

As of this writing, MATHJAX v3 does not yet support groups for macros, so for `\underaccent`, the originals are remembered here, then they are temporarily redefined and used inside `\underaccent`, then restored to their originals. `\LARGE` gives a reasonable size, and `\raise` is used to adjust vertically without introducing extra line space.

```

7 \CustomizeMathJax{\let\LWRgrave\grave}
8 \CustomizeMathJax{\let\LWRacute\acute}
9 \CustomizeMathJax{\let\LWRcheck\check}
10 \CustomizeMathJax{\let\LWRbreve\breve}
11 \CustomizeMathJax{\let\LWRbar\bar}
12 \CustomizeMathJax{\let\LWRhat\hat}
13 \CustomizeMathJax{\let\LWRdot\dot}
14 \CustomizeMathJax{\let\LWRtilde\tilde}
15 \CustomizeMathJax{\let\LWRddot\ddot}

```

```

16 \CustomizeMathJax{\let\LWRvec\vec}
17 \CustomizeMathJax{\let\LWRwidetilde\widetilde}
18
19 \CustomizeMathJax{\newcommand{\underaccent}[2]{%
20 {%
21 \renewcommand{\grave}[1]{\LARGE\LWRgrave{##1}}}%
22 \renewcommand{\acute}[1]{\LARGE\LWRacute{##1}}}%
23 \renewcommand{\check}[1]{\LARGE\LWRcheck{##1}}}%
24 \renewcommand{\breve}[1]{\LARGE\LWRbreve{##1}}}%
25 \renewcommand{\bar}[1]{\LARGE\LWRbar{##1}}}%
26 \renewcommand{\hat}[1]{\LARGE\LWRhat{##1}}}%
27 \renewcommand{\dot}[1]{\LARGE\LWRdot{##1}}}%
28 \renewcommand{\tilde}[1]{\LARGE\LWRtilde{##1}}}%
29 \renewcommand{\ddot}[1]{\LARGE\LWRddot{##1}}}%
30 \renewcommand{\vec}[1]{\LARGE\LWRvec{##1}}}%
31 \renewcommand{\widetilde}[1]{\LARGE\LWRwidetilde{\hphantom{#2}}}%
32 \underset{\raise 2pt {#1}}{#2}%
33 \let\grave\LWRgrave%
34 \let\acute\LWRacute%
35 \let\check\LWRcheck%
36 \let\breve\LWRbreve%
37 \let\bar\LWRbar%
38 \let\hat\LWRhat%
39 \let\dot\LWRdot%
40 \let\tilde\LWRtilde%
41 \let\ddot\LWRddot%
42 \let\vec\LWRvec%
43 \let\widetilde\LWRwidetilde%
44 }%
45 }}
46
47 \CustomizeMathJax{\newcommand{\undertilde}[1]{%
48 \underset{\raise 3pt {\widetilde{\hphantom{#1}}}}{#1}%
49 }}
50 \end{warpMathJax}

```

---

File 10 **lwarp-accessibility.sty**

§ 116 Package **accessibility**

Pkg accessibility accessibility is emulated.

**for HTML output:** Discard all options for lwarp-accessibility:

```

1 \LWR@ProvidesPackageDrop{accessibility}[2019/10/14]

2 \newcommand{\alt}[1]{\ThisAltText{#1}}
3 \newcommand{\newhref}[3]{\ThisAltText{#2}\LWR@href{#1}{#3}}%
4 \providecommand{\thead}[1]{\textbf{#1}}

```

For MATHJAX:

---

```

5 \begin{warpMathJax}
6 \CustomizeMathJax{\newcommand{\alt}[1]{} }
7 \CustomizeMathJax{\newcommand{\thead}[1]{\text{\textbf{#1}}}}
8 \end{warpMathJax}

```

---

File 11 **lwarp-accsupp.sty**

§ 117 Package **accsupp**

Pkg accsupp accsupp is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{accsupp}[2018/03/28]

```

2 \newcommand*{\BeginAccSupp}[1]{}
3 \newcommand*{\EndAccSupp}[1]{}

```

For MATHJAX:

```

4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\BeginAccSupp}[1]{} }
6 \CustomizeMathJax{\newcommand{\EndAccSupp}[1]{} }
7 \end{warpMathJax}

```

---

File 12 **lwarp-acro.sty**

§ 118 Package **acro**

*(Emulates or patches code by CLEMENS NIEDERBERGER.)*

Pkg acro acro is patched for use by lwarp.

 **formats** Define acronymn formats using \textbf instead of \bfseries etc.

**for HTML output:** 1 \LWR@ProvidesPackagePass{acro}[2019/10/12]

\DeclareAcronym is used in the preamble, where lwarp has not yet made the dollar active, so temporarily enable lwarp math catcode just for this definition:

```

2 \ExplSyntaxOn
3 \NewDocumentCommand \LWR@DeclareAcronym {mm}
4 {
5 \acro_declare_acronym:nn {#1} {#2}
6 \catcode'\$=3% lwarp
7 }
8 \ExplSyntaxOff
9
10 \RenewDocumentCommand{\DeclareAcronym}{}{
11 \catcode'\$=\active% lwarp
12 \LWR@DeclareAcronym
13 }

```

Modified to activate the current font:

```

14 \ExplSyntaxOn
15 \@ifpackagelater{acro}{2020/04/29}%
16 {}% v3 or later
17 {}% before v3
18 \@ifpackagelater{acro}{2019/09/23}%
19 {}% v2.10 or later
20 \cs_gset_protected:Npn __acro_typeset:nn #1#2
21 {
22 \mode_if_horizontal:F { \leavevmode }
23 \group_begin:
24 \use:x
25 {
26 \bool_if:cTF {l__acro_custom_#1_format_bool}
27 { \exp_not:v {l__acro_custom_#1_format_tl} }
28 { \exp_not:v {l__acro_#1_format_tl} }
29 { \exp_not:N\LWR@textcurrentfont{#2}}% lwarp
30 }
31 \group_end:
32 }
33
34 \cs_gset_protected:Npn __acro_ending_format:nn #1#2
35 {
36 \bool_if:NTF \l__acro_include_endings_format_bool
37 {
38 \str_case:nn {#1}
39 {
40 {long}
41 {
42 \bool_if:NTF \l__acro_custom_long_format_bool
43 { \l__acro_custom_long_format_tl }
44 {
45 \bool_if:NTF \l__acro_first_instance_bool
46 { \l__acro_first_long_format_tl }
47 { \l__acro_long_format_tl }
48 }
49 }
50 } {short}
51 {
52 \bool_if:NTF \l__acro_custom_short_format_bool
53 { \l__acro_custom_short_format_tl }
54 { \l__acro_short_format_tl }
55 }
56 } {alt}
57 {
58 \bool_if:NTF \l__acro_custom_alt_format_bool
59 { \l__acro_custom_alt_format_tl }
60 { \l__acro_alt_format_tl }
61 }
62 }
63 }
64 { \use:n }
65 { \exp_not:N\LWR@textcurrentfont{#2}}% lwarp
66 }

```

```

67 }% v2.10 or later
68 {% before v2.10
69 \cs_gset_protected:Npn \acro_write_short:nn #1#2
70 {
71 \mode_if_horizontal:F { \leavevmode }
72 \group_begin:
73 \bool_if:NTF \l__acro_custom_format_bool
74 { \l__acro_custom_format_tl }
75 { \l__acro_short_format_tl }
76 {\LWR@textcurrentfont{#2}}% lwarp
77 \group_end:
78 }
79
80 \cs_gset_protected:Npn \acro_write_alt:nn #1#2
81 {
82 \mode_if_horizontal:F { \leavevmode }
83 \group_begin:
84 \bool_if:NTF \l__acro_custom_format_bool
85 { \l__acro_custom_format_tl }
86 { \l__acro_alt_format_tl }
87 {\LWR@textcurrentfont{#2}}% lwarp
88 \group_end:
89 }
90
91 \cs_gset_protected:Npn \acro_write_long:nn #1#2
92 {
93 \mode_if_horizontal:F { \leavevmode }
94 \group_begin:
95 \bool_if:NTF \l__acro_custom_long_format_bool
96 { \l__acro_custom_long_format_tl }
97 { \use:n }
98 {
99 \use:x
100 {
101 \exp_not:n {#1}
102 {
103 \bool_if:NTF \l__acro_first_upper_bool
104 { \exp_not:N __acro_first_upper_case:n { \exp_not:n {
105 \LWR@textcurrentfont{#2}}% lwarp
106 } } }
107 { \exp_not:n {\LWR@textcurrentfont{#2}} }% lwarp
108 }
109 }
110 }
111 \group_end:
112 }
113 }% before v2.10
114 }% before v3
115 \ExplSyntaxOff

```

File 13 **lwarp-acronym.sty**§ 119 Package **acronym**

(Emulates or patches code by TOBIAS OETIKER.)

Pkg acronym acronym is patched for use by lwarp.

⚠ multiply-defined labels `\acresetall` does not work with `cleveref`, causing multiply-defined labels. `lwarp` patches `acronym` for HTML, but not for print mode.

for HTML output: 1 `\LWR@ProvidesPackagePass{acronym}[2015/03/21]`

Uses `\textit` instead of `\itshape`:

```
2 \renewcommand{\acfia}[1]{%
3 {\textit{\AC@acl{#1}}} (\ifAC@starred\acs*{#1}\else\acs{#1}\fi)}
```

Removes the `mbox` to allow math inside:

```
4 \renewcommand*\AC@acs[1]{%
5 % \mbox{
6 \expandafter\AC@get\csname fn@#1\endcsname\@firstoftwo{#1}}
7 % }
```

Fix for acronym labels in the captions of floats.

```
8 \renewcommand{\@starttoc}[1]{
9 \LWR@html@elementclass{nav}{#1}
10 \LetLtxMacro\@verridelabel\@gobble
11 \LWR@orig@starttoc{#1}
12 \LWR@html@elementclassend{nav}{#1}
13 }
```

Modified for `cleveref` and `lwarp`:

```
14 \renewcommand*\AC@und@newlabel[3]{%
15 \@ifundefined{#1@#3}%
16 {%
17 \global\expandafter\let\csname#2@#3\endcsname\@nnil
18 \global\expandafter\let\csname#2@#3@lwarp\endcsname\@nnil% lwarp
19 \global\expandafter\let\csname#2@#3@cref\endcsname\@nnil% lwarp
20 }%
21 {%
22 \global\expandafter\let\csname#1@#3\endcsname\relax
23 \global\expandafter\let\csname#1@#3@lwarp\endcsname\relax% lwarp
24 \global\expandafter\let\csname#1@#3@cref\endcsname\relax% lwarp
25 }%
26 }%
```

File 14 **lwarp-adjmulticol.sty**

§ 120 Package **adjmulticol**

(Emulates or patches code by BORIS VEYTSMAN.)

Pkg adjmulticol adjmulticol is emulated.

Emulation similar to multicol is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, lwarp allows a variable number of columns up to three.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{adjmulticol}[2012/01/20]

2 \RequirePackage{multicol}

adjmulticols \* {\numcols} {\left margin} {\right margin}

3 \NewDocumentEnvironment{adjmulticols}{s m m m}

4 {%

Compute the margins, and limit to positive only:

5 \setlength{\LWR@templengthone}{#3}%

6 \ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{%

7 \setlength{\LWR@templengthtwo}{#4}

8 \ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{%

If one column is specified, use a <div> of class singlecolumn, else use multicol:

9 \newcommand\*\LWR@mcolstype{multicol}%

10 \ifnumcomp{#2}{=}{1}{\renewcommand\*\LWR@mcolstype{singlecolumn}}{%

Help avoid page overflow:

11 \LWR@forcenewpage%

Create the <div> with the given margin and class:

12 \BlockClass[%

13 \LWR@print@mbx{margin-left:\LWR@printlength{\LWR@templengthone}} ; %

14 \LWR@print@mbx{margin-right:\LWR@printlength{\LWR@templengthtwo}}%

15 ]{\LWR@mcolstype}%

16 }

17 {\endBlockClass}

File 15 **lwarp-addlines.sty**§ 121 Package **addlines***(Emulates or patches code by WILL ROBERTSON.)*Pkg addlines **addlines** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{addlines}[2018/12/05]

```

2 \newcommand\addlines{\@ifstar\addlines@a\addlines@a}
3 \newcommand\addlines@a[1][1]{}
4 \let\addline\addlines
5 \newcommand\removelines{\@ifstar\removelines@a\removelines@a}
6 \newcommand\removelines@a[1][1]{}
7 \let\removeline\removelines
8 \newcommand\squeezepage[1][0]{}

```

File 16 **lwarp-afterpage.sty**§ 122 Package **afterpage***(Emulates or patches code by DAVID CARLISLE.)*Pkg afterpage **afterpage** is emulated.**for HTML output:** Discard all options for **lwarp-afterpage**:

```

1 \LWR@ProvidesPackageDrop{afterpage}[2014/10/28]
2 \newcommand{\afterpage}[1][#1]{}

```

File 17 **lwarp-algorithm2e.sty**§ 123 Package **algorithm2e***(Emulates or patches code by CHRISTOPHE FIORIO.)*Pkg algorithm2e **algorithm2e** is patched for use by **lwarp**.

For print output, captions are placed according to package options, but for HTML output captions are placed where used. Therefore, to have captions appear at the top of the algorithms for both print and HTML, place each captions at the top of each algorithm.

**for HTML output:** 1 \LWR@ProvidesPackagePass{algorithm2e}[2017/07/18]

For the list-of entries:

```
2 \renewcommand{\l@algocf}[2]{\hypertocfloat{1}{algocf}{loa}{#1}{#2}}
```

Select the lwarp float style according to the algorithm2e style:

```
3 \newcommand*\LWR@floatstyle@algocf{ruled}
4
5 \ifdefstring{\algocf@style}{boxed}{%
6 \renewcommand*\LWR@floatstyle@algocf}{boxed}
7 }{}
8
9 \ifdefstring{\algocf@style}{boxruled}{%
10 \renewcommand*\LWR@floatstyle@algocf}{boxruled}
11 }{}
12
13 \ifdefstring{\algocf@style}{plain}{%
14 \renewcommand*\LWR@floatstyle@algocf}{plain}
15 }{}
```

Paragraph handling to allow line numbers under certain conditions:

```
16 \newbool{LWR@algocf@dopars}
17 \booltrue{LWR@algocf@dopars}
18
19 \renewcommand{\algocf@everypar}{%
20 \ifbool{LWR@algocf@dopars}{%
21 \ifbool{LWR@doingstartpars}{%
22 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}{%
23 }%
24 {%
25 \algocf@everypar\n\algocf@everyparhanging%
26 }%
27 }{}%
28 }{}%
29 }
```

lwarp caption handling:

```
30 \renewcommand{\algocf@makecaption}[2]{%
31 \LWR@HTML@caption@begin{algocf}%
32 \LWR@isolate{\algocf@captiontext{#1}{#2}}%
33 \LWR@HTML@caption@end%
34 }
```

Print any caption where it is declared:

```
35 \renewcommand{\algocf@makecaption@plain}[2]{%
36 \LWR@HTML@caption@begin{algocf}%
37 \LWR@isolate{\algocf@captiontext{#1}{#2}}%
38 \LWR@HTML@caption@end%
39 }
40
41 \renewcommand{\algocf@makecaption@boxed}[2]{%
42 \LWR@HTML@caption@begin{algocf}%
```

```

43 \LWR@isolate{\algocf@captiontext{#1}{#2}}%
44 \LWR@HTML@caption@end%
45 }
46
47 \renewcommand{\algocf@makecaption@ruled}[2]{%
48 \LWR@HTML@caption@begin{\algocf}%
49 \LWR@isolate{\algocf@captiontext{#1}{#2}}%
50 \LWR@HTML@caption@end%
51 }

```

Turn off line numbering while making the caption:

```

52 \long\def\algocf@latexcaption#1[#2]#3{% original definition of caption
53 \boolfalse{LWR@algocf@dopars}% lwarp
54 \par%
55 \addcontentsline{\csname ext@#1\endcsname}{#1}%
56 {\protect\numberline{\csname the#1\endcsname}{\ignorespaces \LWR@isolate{#2}}}%
57 \begingroup%
58 \@parboxrestore%
59 \if@minipage%
60 \setminipage%
61 \fi%
62 \normalsize%
63 \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par%
64 \endgroup%
65 \booltrue{LWR@algocf@dopars}% lwarp
66 }

```

Line numbers are printed in a `<span>` of class `alg2elinenumber`:

```

67 \renewcommand{\algocf@printnl}[1]{%
68 \InlineClass{alg2elinenumber}{\NLSty{#1}}~%
69 }%

```

While initializing an algorithm environment, locally declare the style of a regular figure to be the same as the algorithm style, in case the `figure` option was used.

```

70 \preto{\algocf@init}{%
71 \edef\LWR@floatstyle@figure{\LWR@floatstyle@algocf}%
72 }

```

For `lwarp`, the algorithm is not assembled inside a box, since `lateximages` would not work, so the captions are printed where declared.

```

73 \renewcommand{\algocf@start}{%
74 \let\@mathsemicolon=\; \def\;{\ifmmode\@mathsemicolon\else\@endalgoln\fi}%
75 % \raggedright%
76 \ALFnt{}}%
77 \booltrue{LWR@algocf@dopars}% lwarp
78 }
79
80 \renewcommand{\algocf@finish}{%
81 \boolfalse{LWR@algocf@dopars}% lwarp
82 \lineskip\normallineskip\setlength{\skiptotal}{\@defaultskiptotal}%

```

```

83 \let\;=\@mathsemicolon%
84 \let\]=\@emathdisplay%
85 }

```

Use an HTML break:

```

86 \renewcommand{\BlankLine}{%
87 \LWR@stoppars%
88 \LWR@htmltagc{br /}%
89 \LWR@startpars%
90 }

```

Simplified for HTML. The paragraph handling must be preserved.

```

91 \renewcommand{\SetKwInOut}[2]{%
92 \algocf@newcommand{#1}[1]{%
93 \ifthenelse{\boolean{algocf@hanginginout}}%
94 {\relax}%
95 {\algocf@seteveryparhanging{\relax}}%
96 \ifthenelse{\boolean{algocf@inoutnumbered}}%
97 {\relax}%
98 {\algocf@seteveryparnl{\relax}}%
99 {%
100 \KwSty{#2\algocf@typo:}%
101 ~##1\par%
102 }%
103 \algocf@linesnumbered% reset the numbering of the lines
104 \ifthenelse{\boolean{algocf@hanginginout}}%
105 {\relax}%
106 {\algocf@reseteveryparhanging}%
107 }%
108 }%
109
110 \renewcommand{\ResetInOut}[1]{%

```

Each of the following creates a <div> of a given class, and turns off line numbering while creating the <div> tags:

```

111 \renewcommand{\algocf@Vline}[1]{%
112 \boolfalse{LWR@algocf@dopars}%
113 \begin{BlockClass}{alg2evline}
114 \booltrue{LWR@algocf@dopars}%
115 #1
116 \boolfalse{LWR@algocf@dopars}%
117 \end{BlockClass}
118 \booltrue{LWR@algocf@dopars}%
119 }

```

```

120 \renewcommand{\algocf@Vsline}[1]{%
121 \boolfalse{LWR@algocf@dopars}%
122 \begin{BlockClass}{alg2evsline}
123 \booltrue{LWR@algocf@dopars}%
124 #1
125 \boolfalse{LWR@algocf@dopars}%
126 \end{BlockClass}

```

```

127 \booltrue{LWR@algocf@dopars}%
128 }

129 \renewcommand{\algocf@Noline}[1]{%
130 \boolfalse{LWR@algocf@dopars}%
131 \begin{BlockClass}{alg2enoline}
132 \booltrue{LWR@algocf@dopars}%
133 #1
134 \boolfalse{LWR@algocf@dopars}%
135 \end{BlockClass}
136 \booltrue{LWR@algocf@dopars}%
137 }

```

The [H] environment is converted to a regular float, which in HTML is placed where declared. Reusing the regular float allows the [H] version to reuse the ruled and boxed options.

```

138 \LetLtxMacro\algocf@Here\algocf
139 \LetLtxMacro\endalgocf@Here\endalgocf

```

---

## File 18 **lwarp-algorithmicx.sty**

### § 124 Package **algorithmicx**

*(Emulates or patches code by SZÁSZ JÁNOS.)*

Pkg algorithmicx algorithmicx is supported with minor adjustments.

**for HTML output:** 1 \LWR@ProvidesPackagePass{algorithmicx}[2005/04/27]

Inside the algorithmic environment, level indenting is converted to a <span> of the required length, and comments are placed inside a <span> which is floated right.

 **package conflicts** If using \newfloat, trivfloat, and/or algorithmicx together, see section 599.1.

```

2 \AtBeginEnvironment{algorithmic}{%
3 %
4 \let\origALG@doentity\ALG@doentity%
5 %
6 \renewcommand*\ALG@doentity}{%
7 \origALG@doentity%
8 \LWR@htmltagc{%
9 span style="width:\LWR@printlength{\ALG@thistlm}; display:inline-block;"%
10 }%
11 \ifbool{FormatWP}{%
12 \setlength{\LWR@templengthone}{\the\ALG@thistlm}%
13 \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
14 \quad%
15 \addtolength{\LWR@templengthone}{-1em}%
16 }%
17 }{%
18 \LWR@htmltagc{/span}%

```

```

19 }%
20
21 \let\LWR@origComment\Comment%
22
23 \renewcommand{\Comment}[1]{%
24 \InlineClass{floatright}{\LWR@origComment{#1}}%
25 }%
26 }
27
28 \renewcommand\algorithmiccomment[1]{%
29 \hfill\HTMLUnicode{25B7} #1% white right triangle
30 }%

```

---

File 19 **lwarp-alltt.sty**

§ 125 Package **alltt**

*(Emulates or patches code by JOHANNES BRAAMS.)*

Pkg alltt alltt is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{alltt}[1997/06/16]

```

2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching alltt.}
4
5 \AtBeginEnvironment{alltt}{%
6 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
7 {}%
8 {%
9 \LWR@forcenewpage

```

Vertical spacing changes if inside a list.

```

10 \LWR@atbeginverbatim{alltt}%
11 }%
12 }
13
14 \AfterEndEnvironment{alltt}{%
15 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
16 {}%
17 {%

```

Vertical spacing changes if inside a list.

```

18 \LWR@afterendverbatim%
19 }%
20 }
21
22 }

```

File 20 **lwarp-amsmath.sty**

§ 126 Package **amsmath**

(Emulates or patches code by AMERICAN MATHEMATICAL SOCIETY, L<sup>A</sup>T<sub>E</sub>X3 PROJECT.)

Pkg amsmath amsmath is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{amsmath}[2017/09/02]

\dotso An HTML text-mode version.

```
2 \newcommand*\LWR@HTML@dotso{\textellipsis\ }
3 \LWR@formatted{dotso}
```

Patches to allow \eqref inside a caption:

```
4 \def\maketag@@@#1{\text{#1}}
5 \def\tagform@#1{\maketag@@@{\ignorespaces#1\unskip}}
```

Patches for  $\mathcal{AMS}$  math \tag macro to remember the first tag:

```
6 \ifbool{mathjax}{}{% not mathjax
7
8 \LetLtxMacro\LWR@origmake@df@tag@@\make@df@tag@@
9 \LetLtxMacro\LWR@origmake@df@tag@@@\make@df@tag@@@
10
11 \renewcommand*\make@df@tag@@[1]{%
12 \LWR@remembertag{#1}%
13 \LWR@origmake@df@tag@@{#1}%
14 }
15
16 \renewcommand*\make@df@tag@@@[1]{%
17 \LWR@remembertag{#1}%
18 \LWR@origmake@df@tag@@@{#1}%
19 }
20
21 }% not mathjax
```

For nesting  $\mathcal{AMS}$  environments:

```
22 \newcounter{LWR@amsmathdepth}
23 \setcounter{LWR@amsmathdepth}{0}
```

The following  $\mathcal{AMS}$  environments are patched in-place:

```
\LWR@amsmathenv@@before * {\environment name}
* if the environment was starred.
```

Embeds the environment inside a lateximage.

```

24 \NewDocumentCommand{\LWR@amsmathenv@before}{s m}{%
25 \IfBooleanTF{#1}{
26 \begin{BlockClass}{displaymath}
27 }{
28 \begin{BlockClass}{displaymathnumbered}
29 }
30 \LWR@newautooidanchor%
31 \booltrue{LWR@indisplaymathimage}%
32 \begin{lateximage}[\LWR@amsmathbodynumbered{#2}]*%
33 \LWR@applyxfakebold%
34 }

```

`\LWR@amsmathenv@before` \*  $\langle environment name \rangle$

\* if the environment was starred.

Embeds the environment with MATHJAX or a lateximage.

```

35 \NewDocumentCommand{\LWR@amsmathenv@before}{s m}{%
36 \ifnumequal{\value{LWR@amsmathdepth}}{0}{%
37 \LWR@stoppars%
38 \ifboolexpr{bool{mathjax} or (bool{FormatWP} and bool{WPMarkMath}) }%
39 {
40 \LWR@syncmathjax
41 \boolfalse{LWR@amsmultline}
42 \ifstrequal{#2}{multline}{\booltrue{LWR@amsmultline}}{ }
43 \ifstrequal{#2}{multiline*}{\booltrue{LWR@amsmultline}}{ }

```



autonom's "+" environments are not supported by MATHJAX.

```

44 \LWR@beginhideamsmath
45 }
46 {
47 \IfBooleanTF{#1}{
48 \LWR@amsmathenv@before*{#2}
49 }{
50 \LWR@amsmathenv@before{#2}
51 }
52 }
53 }{}
54 \addtocounter{LWR@amsmathdepth}{1}
55 }

```

`\LWR@amsmathenv@after`

Embeds the environment inside a lateximage.

```

56 \newcommand*{\LWR@amsmathenv@after}{%
57 \end{lateximage}\end{BlockClass}\LWR@startpars%
58 }

```

`\LWR@amsmathenv@after` \*  $\langle environment name \rangle$

\* if the environment was starred. Ignored here, only used for a consistent syntax.

Embeds the environment with MATHJAX or a lateximage.

```

59 \NewDocumentCommand{\LWR@amsmathenv@after}{s m}{%
60 \ifnumequal{\value{LWR@amsmathdepth}}{1}{%
61 \ifboolexpr{bool{mathjax} or (bool{FormatWP} and bool{WPMarkMath}) }%
62 {
63 \LWR@endhideamsmath
64 \boolfalse{LWR@amsmultline}
65 \LWR@addmathjax{#2}{\the\@envbody}
66 }
67 {\LWR@amsmathenv@@after}

```

Clear the single-use alt text:

```

68 \gdef\LWR@ThisAltText{%
69 }{}
70 \addtocounter{LWR@amsmathdepth}{-1}
71 }

```

Env `multline`

```

72 \BeforeBeginEnvironment{multline}{\LWR@amsmathenv@before{multline}}
73
74 \AfterEndEnvironment{multline}{\LWR@amsmathenv@after{multline}}

```

Env `multline*`

```

75 \BeforeBeginEnvironment{multline*}{\LWR@amsmathenv@before*{multline*}}
76
77 \AfterEndEnvironment{multline*}{\LWR@amsmathenv@after*{multline*}}
78

```

Env `gather`

```

79 \BeforeBeginEnvironment{gather}{\LWR@amsmathenv@before{gather}}
80
81 \AfterEndEnvironment{gather}{\LWR@amsmathenv@after{gather}}

```

Env `gather*`

```

82 \BeforeBeginEnvironment{gather*}{\LWR@amsmathenv@before*{gather*}}
83
84 \AfterEndEnvironment{gather*}{\LWR@amsmathenv@after*{gather*}}

```

Env `align`

```

85 \BeforeBeginEnvironment{align}{\LWR@amsmathenv@before{align}}
86
87 \AfterEndEnvironment{align}{\LWR@amsmathenv@after{align}}

```

Env `align*`

```

88 \BeforeBeginEnvironment{align*}{\LWR@amsmathenv@before*{align*}}
89
90 \AfterEndEnvironment{align*}{\LWR@amsmathenv@after*{align*}}

```

Env flalign

```
91 \BeforeBeginEnvironment{flalign}{\LWR@amsmathenv@before{flalign}}
92
93 \AfterEndEnvironment{flalign}{\LWR@amsmathenv@after{flalign}}
```

Env flalign\*

```
94 \BeforeBeginEnvironment{flalign*}{\LWR@amsmathenv@before*{flalign*}}
95
96 \AfterEndEnvironment{flalign*}{\LWR@amsmathenv@after*{flalign*}}
```

Env alignat

```
97 \BeforeBeginEnvironment{alignat}{\LWR@amsmathenv@before{alignat}}
98
99 \AfterEndEnvironment{alignat}{\LWR@amsmathenv@after{alignat}}
```

Env alignat\*

```
100 \BeforeBeginEnvironment{alignat*}{\LWR@amsmathenv@before*{alignat*}}
101
102 \AfterEndEnvironment{alignat*}{\LWR@amsmathenv@after*{alignat*}}

103 \AtBeginEnvironment{subequations}{
104 \renewcommand*\theMathJaxsubequations{1}
105 \renewcommand*\theMathJaxsection{\theparentequation}
106 \renewcommand*\theMathJaxequation{\arabic{equation}}
107 }
```

For MATHJAX:

```
108 \begin{warpMathJax}
109 \CustomizeMathJax{\newcommand{\intertext}[1]{\text{#1}\notag \\\}}
110 \end{warpMathJax}
```

---

File 21 **lwarp-amsthm.sty**

§ 127 Package **amsthm**

(Emulates or patches code by PUBLICATIONS TECHNICAL GROUP — AMERICAN MATHEMATICAL SOCIETY.)

The original source code is located in `amsclass.dtx`, and printed in `amsclass.pdf`.

Pkg amsthm amsthm is patched for use by lwarp.

**for HTML output:** amsthm must be loaded before mdframed:

```
1 \@ifpackageloaded{mdframed}{
```

Table 17: amsthm package — css styling of theorems and proofs

**Theorem:** <div> of class amsthmbody<theoremstyle>

**Theorem Name:** <span> of class amsthmname<theoremstyle>

**Theorem Number:** <span> of class amsthmnumber<theoremstyle>

**Theorem Note:** <span> of class amsthmnote<theoremstyle>

**Proof:** <div> of class amsthmproof

**Proof Name:** <span> of class amsthmproofname

where <theoremstyle> is plain, definition, etc.

```

2 \PackageError{lwarp}
3 {%
4 Package mdframed must be loaded after package amsthm.\MessageBreak
5 Enter 'H' for solutions%
6 }
7 {%
8 Move ‘‘\protect\usepackage{amsthm}’’ before
9 ‘‘\protect\usepackage{mdframed}’’.\MessageBreak
10 Package amsthm may be loaded by something else,\MessageBreak
11 which must also be moved before mdframed.%
12 }
13 }
14 {\relax}

```

Necessary for `\text`, used by `\openbox`, etc., below:

```

15 \RequirePackage{amsmath}

16 \LWR@ProvidesPackagePass{amsthm}[2017/10/31]

```

Storage for the style being used for new theorems:

```

17 \newcommand{\LWR@newtheoremstyle}{plain}

```

Patched to remember the style being used for new theorems:

```

18 \renewcommand{\theoremstyle}[1]{%
19 \ifundefined{th#1}{%
20 \PackageWarning{amsthm}{Unknown theoremstyle ‘#1’}%
21 \thm@style{plain}%
22 \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
23 }{%
24 \thm@style{#1}%
25 \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
26 }%
27 }

```

Patched to remember the style for this theorem type:

```

28 \def\@xnthm#1#2{%
29 \csedef{LWR@thmstyle#2}{\LWR@newtheoremstyle}% lwarp
30 \let\@tempa\relax
31 \@xp\@ifdefinable\csname #2\endcsname{%
32 \global\@xp\let\csname end#2\endcsname\@endtheorem
33 \ifx *#1% unnumbered, need to get one more mandatory arg
34 \edef\@tempa##1{%
35 \gdef\@xp\@nx\csname#2\endcsname{%
36 \@nx\thm{\@xp\@nx\csname th@the\thm@style\endcsname}%
37 {##1}}}%
38 \else % numbered theorem, need to check for optional arg
39 \def\@tempa{\@oparg{\@ynthm{#2}}{}}%
40 \fi
41 \AtBeginEnvironment{#2}{%
42 \edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#2}}%
43 }% lwarp
44 }%
45 \@tempa
46 }

```

Patched to enclose with css:

```

47 \newcommand{\LWR@haveamsthmname}{
48 \renewcommand{\thmname}[1]{%
49 \InlineClass{amsthmname\LWR@thisthmstyle}{##1}%
50 }
51 }
52
53 \newcommand{\LWR@haveamsthmnumber}{
54 \renewcommand{\thmnumber}[1]{%
55 \InlineClass{amsthmnumber\LWR@thisthmstyle}{##1}%
56 }
57 }
58
59 \newcommand{\LWR@haveamsthmnote}{
60 \renewcommand{\thmnote}[1]{%
61 \InlineClass{amsthmnote\LWR@thisthmstyle}{##1}%
62 }
63 }
64
65 \LWR@haveamsthmname
66 \LWR@haveamsthmnumber
67 \LWR@haveamsthmnote

```

Patched for css:

```

68 \def\@begintheorem#1#2[#3]{%
69 \GetTitleString{#3}% lwarp
70 \let\@currentlabelname\GetTitleStringResult% lwarp
71 \item[

```

```

72 % \deferred@thm@head{
73 % \the\thm@headfont \thm@indent
74 \@ifempty{#1}{\let\thmname@gobble}{\LWR@haveamsthmname}% lwarp
75 \@ifempty{#2}{\let\thmnumber@gobble}{\LWR@haveamsthmnumber}% lwarp
76 \@ifempty{#3}{\let\thmnote@gobble}{\LWR@haveamsthmnote}% lwarp
77 \thm@swap\swappedhead\thmhead{#1}{#2}{#3}%
78 \the\thm@headpunct~
79 \thmheadnl % possibly a newline.
80 \hskip\thm@headsep
81 % }%
82]
83 \ignorespaces}

```

Patched for css:

```

84 \def\@thm#1#2#3{%
85 \ifhmode\unskip\unskip\par\fi
86 \normalfont
87 \LWR@forcenewpage% lwarp
88 \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
89 \trivlist
90 \let\thmheadnl\relax
91 \let\thm@swap@gobble
92 \thm@notefont{\fontseries\mddefault\upshape}%
93 \thm@headpunct{.}% add period after heading
94 \thm@headsep 5\p@ plus\p@ minus\p@\relax
95 \thm@space@setup
96 #1% style overrides
97 \@topsep \thm@preskip % used by thm head
98 \@topsepadd \thm@postskip % used by \@endparenv
99 \def\@tempa{#2}\ifx\@empty\@tempa
100 \def\@tempa{\@oparg{\@begintheorem{#3}}{}}{[]}%
101 \else
102 \refstepcounter{#2}%
103 \def\@tempa{\@oparg{\@begintheorem{#3}}{\csname the#2\endcsname}}{[]}%
104 \fi
105 \@tempa
106 }

```

clever patches \@thm to do \cref@thmoptarg if an optional argument is given. lwarp then patches \cref@thmoptarg \AtBeginDocument.

```

107 \AtBeginDocument{%
108 \def\cref@thmoptarg[#1]#2#3#4{%
109 \ifhmode\unskip\unskip\par\fi%
110 \normalfont%
111 \LWR@forcenewpage% lwarp
112 \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
113 \trivlist%
114 \let\thmheadnl\relax%
115 \let\thm@swap@gobble%
116 \thm@notefont{\fontseries\mddefault\upshape}%
117 \thm@headpunct{.}% add period after heading
118 \thm@headsep 5\p@ plus\p@ minus\p@\relax%
119 \thm@space@setup%

```

```

120 #2% style overrides
121 \@topsep \thm@preskip % used by thm head
122 \@topsepadd \thm@postskip % used by \@endparenv
123 \def\@tempa{#3}\ifx\@empty\@tempa%
124 \def\@tempa{\@oparg{\@begintheorem{#4}}{}}[]%
125 \else%
126 \refstepcounter[#1]{#3}% <<< cleveref modification
127 \def\@tempa{\@oparg{\@begintheorem{#4}{\csname the#3\endcsname}}{}}%
128 \fi%
129 \@tempa
130 }%
131 }% AtBeginDocument
132
133 \def\@endtheorem{\endtrivlist\endBlockClass\@endpfalse }

```

### Proof QED symbol:

```

134 \AtBeginDocument{
135 \ifundefined{LWR@orig@openbox}{
136 \LetLtxMacro\LWR@orig@openbox\openbox
137 \LetLtxMacro\LWR@orig@blacksquare\blacksquare
138 \LetLtxMacro\LWR@orig@Box\Box
139
140 \def\openbox{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
141 \def\blacksquare{\text{\HTMLUnicode{220E}}}% UTF-8 end-of-proof
142 \def\Box{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
143
144 \appto\LWR@restoreorigformatting{%
145 \LetLtxMacro\openbox\LWR@orig@openbox%
146 \LetLtxMacro\blacksquare\LWR@orig@blacksquare%
147 \LetLtxMacro\Box\LWR@orig@Box%
148 }% appto
149 }{}% @ifundefined
150 }% AtBeginDocument

```

### Patched for css:

```

151 \renewenvironment{proof}[1][\proofname]{\par
152 \LWR@forcenewpage% lwarp
153 \BlockClass{amsthmproof}% lwarp
154 \pushQED{\qed}%
155 \normalfont \topsep6\p@\@plus6\p@\relax
156 \trivlist
157 \item[
158 \InlineClass{amsthmproofname}{#1\@addpunct{.}}\ignorespaces% changes
159]{}%
160 \InlineClass{theoremdemark}{\popQED}\endtrivlist%
161 \endBlockClass% lwarp
162 \@endpfalse
163 }

```

File 22 **lwarp-anonchap.sty**§ 128 Package **anonchap**

(Emulates or patches code by PETER WILSON.)

Pkg anonchap anonchap is emulated.

Pkg tocloft If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard L<sup>A</sup>T<sub>E</sub>X commands to create the titles, allowing other packages to work with it.

△ tocloft & other packages

The code is shared by tocbibind.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{anonchap}[2009/08/03]

2 \newcommand{\simplechapter}[1][\@empty]{%
3 \def\@chapcntformat##1{%
4 #1~\csname the##1\endcsname\simplechapterdelim\quad%
5 }%
6 }
7
8 \newcommand{\restorechapter}{%
9 \let\@chapcntformat\@secCNTformat%
10 }
```

File 23 **lwarp-anysize.sty**§ 129 Package **anysize**

(Emulates or patches code by MICHAEL SALZENBERG, THOMAS ESSER.)

Pkg anysize anysize is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{anysize}[1994/08/13]

2 \def\papersize#1#2{}
3 \def\marginSize#1#2#3#4{}
```

File 24 **lwarp-appendix.sty**§ 130 Package **appendix**

(Emulates or patches code by PETER WILSON.)

Pkg appendix appendix is patched for use by lwarp.

- ⚠ **incorrect toc link** During HTML conversion, the option `toc` without the option `page` results in a toc link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and `also page` at the same time.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{appendix}[2009/09/02]

2 \renewcommand*{\@chap@pppage}{%
3 \part*{\appendixpagename}
4 \if@dotoc@pp
5 \addappheadtotoc
6 \fi
7 }
8
9 \renewcommand*{\@sec@pppage}{%
10 \part*{\appendixpagename}
11 \if@dotoc@pp
12 \addappheadtotoc
13 \fi
14 }
```

---

File 25 **lwarp-ar.sty**

§ 131 Package **ar**

*(Emulates or patches code by AGOSTINO DE MARCO.)*

Pkg ar ar is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{ar}[2012/01/23]
```

Measure and print the width of the supplied glyph.

```

2 \newlength{\LWR@ar@width}
3
4 \newcommand*{\LWR@ar@printwidth}[1]{%
5 \setlength{\LWR@ar@width}{\widthof{#1}}%
6 width:%
7 \LWR@convertto{em}{\the\LWR@ar@width}em%
8 }
```

The HTML version of `\AR`:

```

9 \newrobustcmd*{\LWR@HTML@AR}{%
```

Start a hashed `lateximage`, additionally hashed by the font series, with a width depending on the given glyph:

```

10 \begin{lateximage}*[AR][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@AR}]%
```

For text mode, set the font series according to the HTML font series:

```

11 \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
```

Print the original glyph using the newly set font series:

```
12 \LWR@print@AR%
```

Done.

```
13 \end{lateximage}%
14 }
```

Combine the print and HTML versions:

```
15 \LWR@formatted{AR}
```

```
16 \newrobustcmd*{\LWR@HTML@ARb}{%
17 \begin{lateximage}*[AR][b][\LWR@ar@printwidth{\LWR@print@ARb}]%
18 \LWR@print@ARb%
19 \end{lateximage}%
20 }
21 \LWR@formatted{ARb}
```

```
22 \newrobustcmd*{\LWR@HTML@ARss}{%
23 \begin{lateximage}*[ARss][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@ARss}]%
24 \ifmmode\else\csuse{\LWR@orig\LWR@f@series series}\fi%
25 \LWR@print@ARss%
26 \end{lateximage}%
27 }
28 \LWR@formatted{ARss}
```

```
29 \newrobustcmd*{\LWR@HTML@ARssb}{%
30 \begin{lateximage}*[AR][ssb][\LWR@ar@printwidth{\LWR@print@ARssb}]%
31 \LWR@print@ARssb%
32 \end{lateximage}%
33 }
34 \LWR@formatted{ARssb}
```

```
35 \newrobustcmd*{\LWR@HTML@ARtt}{%
36 \begin{lateximage}*[AR][tt][\LWR@ar@printwidth{\LWR@print@ARtt}]%
37 \LWR@print@ARtt%
38 \end{lateximage}%
39 }
40 \LWR@formatted{ARtt}
```

For MATHJAX:

```
41 \begin{warpMathJax}
42 \CustomizeMathJax{\newcommand{\AR}{\mathit{A\!\!R}}}
43 \CustomizeMathJax{\newcommand{\ARb}{\boldsymbol{A\!\!R}}}
44 \end{warpMathJax}
```

---

File 26 **lwarp-arabicfront.sty**

§ 132 Package **arabicfront**

Pkg arabicfront arabicfront is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{arabicfront}[2006/09/03]

---

File 27 **lwarp-array.sty**

§ 133 Package **array**

Pkg array array is used as-is for print output, and emulated for HTML.

plarray and plectarray do not affect \firstline or \lasthline, and so are not affected by the following.

**for HTML output:** Remove the default nullfied macros:

```

1 \let\firstline\relax
2 \let\lasthline\relax
3
4 \LWR@ProvidesPackagePass{array}[2018/12/30]

5 \newcommand*\LWR@HTML@firstline{\LWR@HTMLhline}%
6 \LWR@expandableformatted{firstline}
7
8 \newcommand*\LWR@HTML@lasthline{\LWR@HTMLhline}%
9 \LWR@expandableformatted{lasthline}

10 \providecommand*\LWR@HTML@tabularnewline{\LWR@tabularendofline}
11 \LWR@formatted{tabularnewline}

```

For MATHJAX:

```

12 \CustomizeMathJax{
13 \newcommand{\multicolumn}[3]{#3}% only uses one cell
14 }

```

---

File 28 **lwarp-arydshln.sty**

§ 134 Package **arydshln**

(Emulates or patches code by HIROSHI NAKASHIMA.)

Pkg `arydshln` `arydshln` heavily patches `tabular` code, so the actual package is not used. `arydshln` is emulated for HTML `tabular`, and reverts to solid rules for SVG `math array` and `tabular` in a `lateximage`.

`css` is not able to display a double-dashed border, so a single-dashed rule is displayed as a single-dashed border, and a double-dashed rule is displayed as a thicker single-dashed border.

For `MATHJAX`, limited emulation is provided for math mode.

for HTML output: `array` is required to allow `\newcolumn` below.

```
1 \RequirePackage{array}

2 \LWR@ProvidesPackageDrop{arydshln}[2018/09/26]
```

Ignored, but included for source compatibility:

```
3 \newdimen\dashlinedash \dashlinedash4pt %
4 \newdimen\dashlinegap \dashlinegap4pt %
5 \let\hdashlinewidth\dashlinedash
6 \let\hdashlinegap\dashlinegap
7
8 \def\ADLnullwide{}
9 \def\ADLsomewide{}
10 \def\ADLnullwidehline{}
11 \def\ADLsomewidehline{}
12
13 \def\ADLactivate{}
14 \def\ADLinactivate{}
15 \newcommand*\ADLdrawingmode[1]{}
16 \newcommand*\ADLnoshorthanded{}
17 \newcommand*\dashgapcolor[2]{}
18 \newcommand*\nodashgapcolor{}
```

In a `lateximage`, revert to solid vertical rules:

```
19 \appto\LWR@restoreorigformatting{%
20 \newcolumntype{:}{|}%
21 \newcolumntype{;}[1]{|}%
22 \LetLtxMacro\hdashline\hline%
23 }
```

Some of these macros are already defined as temporary placeholders in the `lwarp` core, so they must be redefined here.

The emulated defaults also work for an emulated print mode inside a `lateximage`:

```
24 \def\hdashline{
25 % \adl@hdashline\adl@ihdashline
26 \adl@hdashline\adl@inactivehdl
27 }
28 \def\adl@hdashline#1{\noalign{\ifnum0=#'}\fi
29 % \ifadl@zwhrule \vskip-\arrayrulewidth
```

```

30 % \else
31 % \adl@hline\adl@connect\arrayrulewidth
32 % \hrule \@height \arrayrulewidth% lwarp
33 % \fi
34 \@ifnextchar[%]
35 {#1}%
36 {#1[%
37 % \dashlinedash/\dashlinegap
38 % 1pt/1pt
39 %]}}
40 % \def\adl@ihdashline[#1/#2]{\ifnum0='{ \fi}%
41 % \multispan{\adl@columns}\unskip \adl@hcline\z@[#1/#2]%
42 % \noalign{\ifnum0='}\fi
43 % \futurelet\@tempa\adl@xhline}
44 % \def\adl@inactivehdl[#1/#2]{
45 % \ifadl@zwhrule \vskip-\arrayrulewidth \fi
46 % \hrule\@height\arrayrulewidth
47 % \futurelet\@tempa\adl@xhline}
48 % \def\adl@xhline{\ifx\@tempa\hline \adl@ixhline\fi
49 % \ifx\@tempa\hdashline \adl@ixhline\fi
50 % \ifnum0='{ \fi}}
51 % \def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
52 % \def\adl@hline#1#2{%
53 % \@tempcnta#2
54 % \global\advance\adl@totalheight\@tempcnta
55 % \xdef\adl@rowsL{\adl@rowsL
56 % (#1/\number\@tempcnta);}
57 % \xdef\adl@rowsR{\adl@rowsR
58 % (#1/\number\@tempcnta);}
59 % }
60
61 % \def\cdashline#1{\noalign{\ifnum0='}\fi
62 % \@ifnextchar[%]
63 % {\adl@cdline[#1]}%
64 % {\adl@cdline[#1][\dashlinedash/\dashlinegap]}
65 % {\adl@inactivecdl[#1]}%
66 % {\adl@inactivecdl[#1][\dashlinedash/\dashlinegap]}
67 % }
68
69 % \def\adl@inactivecdl[#1-#2][#3]{\ifnum0='{ \fi}\cline{#1-#2}}

70 \begin{warpMathJax}
71 \CustomizeMathJax{\newcommand{\firsthdashline}[1][\hdashline]}
72 \CustomizeMathJax{\let\lasthdashline\firsthdashline}
73 \CustomizeMathJax{\let\cdashline\cline}
74 \end{warpMathJax}

```

---

File 29 **lwarp-asymptote.sty**

§ 135 Package **asymptote**

(Emulates or patches code by ANDY HAMMERLINDL, JOHN BOWMAN, TOM PRINCE.)

Pkg asymptote asymptote is patched for use by lwarp.

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{asymptote}[2016/11/26]
2 \BeforeBeginEnvironment{asy}{%
3 \begin{lateximage}[-asymptote-~\PackageDiagramAltText]%
4 }
5 \AfterEndEnvironment{asy}{\end{lateximage}}
6
7 \xpatchcmd{\asyinclude}
8 {\begingroup}
9 {\begin{lateximage}[-asymptote-~\PackageDiagramAltText]}
10 {}
11 {\LWR@patcherror{asymptote}{asyinclude-begingroup}}
12
13 \xpatchcmd{\asyinclude}
14 {\endgroup}
15 {\end{lateximage}}
16 {}
17 {\LWR@patcherror{asymptote}{asyinclude-endgroup}}
```

---

File 30 **lwarp-atbegshi.sty**

§ 136 Package **atbegshi**

*(Emulates or patches code by HEIKO OBERDIEK.)*

Pkg atbegshi atbegshi is ignored.

**for HTML output:** Discard all options for lwarp-atbegshi:

```
1 \LWR@ProvidesPackageDrop[atbegshi][2011/10/05]
2 \let\AtBeginShipout\relax
```

```

3 \let\AtBeginShipoutNext\relax
4 \let\AtBeginShipoutFirst\relax
5 \let\AtBeginShipoutDiscard\relax
6 \let\AtBeginShipoutInit\relax
7 \let\AtBeginShipoutAddToBox\relax
8 \let\AtBeginShipoutAddToBoxForeground\relax
9 \let\AtBeginShipoutUpperLeft\relax
10 \let\AtBeginShipoutUpperLeftForeground\relax
11 \let\AtBeginShipoutOriginalShipout\relax
12
13 \newcommand*\AtBeginShipout}[1]{}
14 \newbox\AtBeginShipoutBox
15 \newcommand*\AtBeginShipoutNext}[1]{}
16 \newcommand*\AtBeginShipoutFirst}[1]{}
17 \newcommand*\AtBeginShipoutDiscard{}
18 \newcommand*\AtBeginShipoutInit{}
19 \newcommand*\AtBeginShipoutAddToBox}[1]{}
20 \newcommand*\AtBeginShipoutAddToBoxForeground}[1]{}
21 \newcommand*\AtBeginShipoutUpperLeft}[1]{}
22 \newcommand*\AtBeginShipoutUpperLeftForeground}[1]{}
23 \newcommand*\AtBeginShipoutOriginalShipout}[1]{}
24 \def\AtBeginShipoutBoxWidth{0pt}
25 \def\AtBeginShipoutBoxHeight{0pt}
26 \def\AtBeginShipoutBoxDepth{0pt}

```

---

File 31 **lwarp-attachfile.sty**

§ 137 Package **attachfile**

*(Emulates or patches code by SCOTT PAKIN.)*

Pkg attachfile **attachfile** is patched for use by **lwarp**.

 Metadata is ignored for now.

**for HTML output:** 1 \LWR@ProvidesPackagePass{attachfile}[2016/09/18]

Encloses each icon:

```

2 \newenvironment*LWR@attachfile@icon
3 {
4 \begin{lateximage}*%
5 [-attachfile-%
6 [%
7 \detokenize\expandafter{\atfi@icon@icon}-%
8 \detokenize\expandafter{\atfi@color@rgb}%
9]%
10 }
11 {
12 \end{lateximage}
13 }

```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```

14 \xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
15 \xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}
16
17 \xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
18 \xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}
19
20 \xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
21 \xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}
22
23 \xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
24 \xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}

```

Disable PDF file embedding:

```
25 \DeclareRobustCommand{\atfi@embedfile}[1]{}

```

The displayed output for an `\attachfile` reference:

```

26 \newcommand*{\LWR@attachfile@appearance}{}
27
28 \DeclareRobustCommand{\atfi@set@appearance}[1]{%
29 \def\LWR@attachfile@appearance{#1}%
30 }

```

A file annotation becomes a reference:

```

31 \DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
32 \LWR@href{#1}{\LWR@attachfile@appearance}%
33 }

```

## File 32 **lwarp-attachfile2.sty**

### § 138 Package **attachfile2**

*(Emulates or patches code by HEIKO OBERDIEK.)*

Pkg attachfile2 **attachfile2** is patched for use by **lwarp**.



Metadata is ignored for now.

**for HTML output:** 1 \LWR@ProvidesPackagePass{attachfile2}[2016/05/16]

Adds memory of the selected color:

```

2 \def\LWR@attachfiletwo@color{}%
3
4 \define@key{AtFi}{color}{%
5 \def\LWR@attachfiletwo@color{#1}% lwarp
6 \HyColor@AttachfileColor{#1}%
7 \atfi@color@tex\atfi@color@inline\atfi@color@annot

```

```

8 {attachfile2}{color}%
9 }

```

Encloses each icon:

```

10 \newenvironment*{LWR@attachfile@icon}
11 {
12 \begin{lateximage}*%
13 [-attachfile-]%
14 [%
15 \detokenize\expandafter{\atfi@icon@icon}-%
16 \detokenize\expandafter{\LWR@attachfiletwo@color}%
17]%
18 }
19 {
20 \end{lateximage}
21 }

```

Each icon is enclosed inside a LWR@attachfile@icon environment:

```

22 \xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
23 \xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}
24
25 \xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
26 \xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}
27
28 \xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
29 \xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}
30
31 \xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
32 \xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}

```

Disable PDF file embedding:

```

33 \DeclareRobustCommand{\atfi@embedfile}[1]{}

```

The displayed output for an \attachfile reference:

```

34 \newcommand*{\LWR@attachfile@appearance}{}
35
36 \def\atfi@set@appearance@icon{%
37 \atfi@set@appearance{\csname atfi@acro\atfi@icon@icon\endcsname}%
38 }
39
40 \DeclareRobustCommand{\atfi@set@appearance}[1]{%
41 \def\LWR@attachfile@appearance{#1}%
42 }

```

A file annotation becomes a reference:

```

43 \DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
44 \LWR@href{#1}{\LWR@attachfile@appearance}%
45 }

```

Modified for text color:

```

46 \DeclareRobustCommand{\notextattachfile}[2][]{%
47 \begingroup
48 \atfi@setup{#1}%
49 \ifatfi@print
50 \leavevmode
51 \begingroup
52 \HyColor@UseColor\atfi@color@tex
53 \LWR@textcurrentcolor{#2}% lwarp
54 % \strut
55 \endgroup
56 % \else
57 % \sbox\ltx@zero{#2\strut}%
58 % \makebox[\wd0]{}%
59 \fi
60 \endgroup
61 }

```

Modified to draw the icon:

```

62 \DeclareRobustCommand{\noattachfile}[1][]{%
63 \begingroup
64 \atfi@setup{#1}%
65 \atfi@set@appearance@icon
66 \ifatfi@print
67 \LWR@attachfile@appearance% lwarp
68 % \expandafter
69 % \atfi@refxform\csname atfi@appobj@\atfi@icon@icon\endcsname
70 % \else
71 % \makebox[\atfi@appearancewidth]{}%
72 \fi
73 \endgroup
74 }

```

---

File 33 **lwarp-authblk.sty**

§ 139 Package **authblk**

*(Emulates or patches code by PATRICK W. DALY.)*

Pkg authblk **authblk** is patched for HTML.

[package support](#)

 [load order](#)

**lwarp** supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages **authblk** and **titling**. If both are used, **authblk** should be loaded before **titling**.

[\published and \subtitle](#)

If using the **titling** package, additional titlepage fields for `\published` and `\subtitle` may be added by using `\AddSubtitlePublished` in the preamble. See section 67.8.

*(Emulates or patches code by PATRICK W. DALY.)*

**for HTML output:**

Require that **authblk** be loaded before **titling**:

```

1 \@ifpackageloaded{titling}{
2 \PackageError{lwarp-authblk}
3 {Package authblk must be loaded before titling}
4 {%
5 Titling appends authblk's author macro,
6 so authblk must be loaded first.%
7 }
8 }
9 {\relax}

```

Load authblk:

```
10 \LWR@ProvidesPackagePass{authblk}[2001/02/27]
```

Patch to add a class for the affiliation:

```

11 \LetLtxMacro\LWRAB@affil\affil
12
13 \renewcommand{\affil}[2][{}]{%
14 \LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}
15 }

```

Create an HTML break for an `\authorcr`:

```
16 \renewcommand*{\authorcr}{\protect\LWR@newlinebr}
```

File 34 **lwarp-autobreak.sty**

§ 140 Package **autobreak**

(Emulates or patches code by TAKAHIRO UEDA.)

Pkg autobreak **autobreak** is used as-is for SVG math, and nullified for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{autobreak}[2017/02/23]

For MATHJAX. The modified `align` environment is used for SVG math, but is reverted to its original for MATHJAX. (Extraneous commas were appearing in the result.)

```

2 \begin{warpMathJax}
3 \renewenvironment{autobreak}{\newcommand{\MoveEqLeft}[1]{}{}}
4 \let\start@align\@autobreak@oldstart@align
5 \let\endalign\@autobreak@oldendalign
6 \CustomizeMathJax{\newenvironment{autobreak}{}{}}
7 \CustomizeMathJax{\newcommand{\MoveEqLeft}[1]{}{}}
8 \CustomizeMathJax{\newcommand{\everybeforeautobreak}[1]{}{}}
9 \CustomizeMathJax{\newcommand{\everyafterautobreak}[1]{}{}}
10 \end{warpMathJax}

```

File 35 **lwarp-autonum.sty**§ 141 Package **autonum**

Pkg autonum autonum is ignored.

 **numbering** All equations are numbered in HTML output.

MATHJAX does not support the “+” environments.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{autonum}[2015/01/18]
2 \RequirePackage{amsmath}
3
4
5 \newenvironment{equation+}{\equation}{\endequation}
6
7
8 \newenvironment{gather+}{\gather}{\endgather}
9
10 \BeforeBeginEnvironment{gather+}{\LWR@amsmathenv@@before{gather+}}
11
12 \AfterEndEnvironment{gather+}{\LWR@amsmathenv@@after}
13
14
15 \newenvironment{multline+}{\multline}{\endmultline}
16
17 \BeforeBeginEnvironment{multline+}{\LWR@amsmathenv@@before{multline+}}
18
19 \AfterEndEnvironment{multline+}{\LWR@amsmathenv@@after}
20
21
22 \newenvironment{flalign+}{\flalign}{\endflalign}
23
24 \BeforeBeginEnvironment{flalign+}{\LWR@amsmathenv@@before{flalign+}}
25
26 \AfterEndEnvironment{flalign+}{\LWR@amsmathenv@@after}
27
28
29 \newenvironment{align+}{\align}{\endalign}
30
31 \BeforeBeginEnvironment{align+}{\LWR@amsmathenv@@before{align+}}
32
33 \AfterEndEnvironment{align+}{\LWR@amsmathenv@@after}
34
35
36 \newenvironment{alignat+}{\alignat}{\endalignat}
37
38 \BeforeBeginEnvironment{alignat+}{\LWR@amsmathenv@@before{alignat+}}
39
40 \AfterEndEnvironment{alignat+}{\LWR@amsmathenv@@after}

```

```

41
42
43 \newenvironment{split+}{\split}{\endsplit}

```

---

File 36 **lwarp-awesomebox.sty**

§ 142 Package **awesomebox**

*(Emulates or patches code by ÉTIENNE DEPARIS.)*

Pkg awesomebox awesomebox is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{awesomebox}[2019/07/27]

2 \newcommand*\LWR@awesomebox@boxborders{}{}%
3 \newcommand*\LWR@awesomebox@contentsborders{}{}%
4
5 \newcommand*\LWR@awesomebox@ruleborders{}{%
6 border-top: 1px solid black ;
7 border-bottom: 1px solid black%
8 }
9
10 % \awesomebox[1:vrulecolor][2:hrule][3:title]{4:vrulewidth}{5:icon}{6:iconcolor}{7:content}
11 \RenewDocumentCommand \awesomebox { O{abvrulecolor} O{} o m m m +m }{%
12 \begin{awesomeblock}[#1][#2][#3][#4][#5][#6]
13 #7
14 \end{awesomeblock}
15 }
16
17 % \begin{awesomeblock}[1:vrulecolor][2:hrule][3:title][4:vrulewidth]{5:icon}{6:iconcolor}
18 % <contents>
19 % \end{awesomeblock}
20 \RenewDocumentEnvironment{awesomeblock}{ O{abvrulecolor} O{} o m m m }
21 {%
22 \LWR@forceminwidth{#4}%
23 \convertcolorspec{named}{#1}{HTML}\LWR@tempcolor%
24 \renewcommand*\LWR@awesomebox@boxborders{}{}%
25 \renewcommand*\LWR@awesomebox@contentsborders{}{}%
26 \ifdefstrequal{\abShortLine}{#2}{%
27 \renewcommand*\LWR@awesomebox@contentsborders{\LWR@awesomebox@ruleborders}%
28 }{}%
29 \ifdefstrequal{\abLongLine}{#2}{%
30 \renewcommand*\LWR@awesomebox@boxborders{\LWR@awesomebox@ruleborders}%
31 }{}%
32 \begin{BlockClass}[\LWR@awesomebox@boxborders]{awesomebox}
33 \begin{BlockClass}[%
34 margin-left: 2\% ;
35 vertical-align: top
36]{minipage}
37 \color{#6}\Huge #5
38 \end{BlockClass}
39 \begin{BlockClass}[%
40 width:75\% ;

```

```

41 vertical-align: top ;
42 padding-left: 1em ;
43 \LWR@awesomebox@contentsborders ;
44 border-left: \LWR@printlength{\LWR@atleastonept} %
45 solid \LWR@origpound\LWR@tempcolor%
46]{minipage}
47 \IfValueTF{#3}{#3\newline}{}
48 }
49 {%
50 \end{BlockClass}
51 \end{BlockClass}
52 }

```

---

File 37 **lwarp-axessibility.sty**

§ 143 Package **axessibility**

Pkg axessibility axessibility is ignored.

**for HTML output:**

```

1 \PackageInfo{lwarp}{Using the lwarp version of package 'axessibility'.}%
2 \ProvidesPackage{lwarp-axessibility}% no date is declared by the original
3
4 \newif\iftagpdfopt
5
6 \DeclareOption{accsupp}{
7 \tagpdfoptfalse
8 }
9
10 \DeclareOption{tagpdf}{
11 \tagpdfopttrue
12 }
13
14 \ProcessOptions\relax
15
16 \iftagpdfopt
17 \RequirePackage{tagpdf}
18 \else
19 \RequirePackage{accsupp}
20 \fi

21 \long\def\wrap#1{}
22 \long\def\wrapml#1{}
23 \long\def\wrapmlstar#1{}
24 \long\def\wrapmlalt#1{}

```

For MATHJAX. These usually will not be needed.

```

25 \begin{warpMathJax}
26 \CustomizeMathJax{\newcommand{\wrap}[1]{} }
27 \CustomizeMathJax{\newcommand{\wrapml}[1]{} }
28 \CustomizeMathJax{\newcommand{\wrapmlstar}[1]{} }
29 \CustomizeMathJax{\newcommand{\wrapmlalt}[1]{} }
30 \end{warpMathJax}

```

File 38 **lwarp-axodraw2.sty**§ 144 Package **axodraw2**

(Emulates or patches code by JOHN C. COLLINS, J.A.M. VERMASEREN.)

Pkg axodraw2 axodraw2 is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{axodraw2}[2018/02/15]

2 \BeforeBeginEnvironment{axopicture}{%
3 \begin{lateximage}[-axopicture-~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{axopicture}{\end{lateximage}}
```

File 39 **lwarp-backnaur.sty**§ 145 Package **backnaur**

(Emulates or patches code by ADRIAN P. ROBSON.)

Pkg backnaur backnaur is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{backnaur}[2019/06/18]

2 \renewenvironment{bnf}{\eqnarray}{\endeqnarray}
3 \renewenvironment{bnf*}{\csuse{eqnarray*}}{\csuse{endeqnarray*}}
```

File 40 **lwarp-backref.sty**§ 146 Package **backref**

(Emulates or patches code by DAVID CARLISLE AND SEBASTIAN RAHTZ.)

Pkg backref backref is patched for use by lwarp.

 **loading** Note that backref must be explicitly loaded, and is not automatically loaded by hyperref when generating HTML output.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{backref}[2016/05/21]
```

Force the hyperref option:

```

2 \def\backref{}
```

```

3
4 \long\def\hyper@section@backref#1#2#3{%
5 \ref{#3}%
6 }
7
8 \let\backrefxxx\hyper@section@backref

```

---

File 41 **lwarp-balance.sty**

§ 147 Package **balance**

*(Emulates or patches code by PATRICK W. DALY.)*

Pkg balance balance is ignored.

**for HTML output:** Discard all options for lwarp-balance:

```

1 \LWR@ProvidesPackageDrop{balance}[1999/02/23]

2 \newcommand*\balance{}
3 \newcommand*\nobalance{}

```

---

File 42 **lwarp-bbding.sty**

§ 148 Package **bbding**

*(Emulates or patches code by KAREL HORAK, PETER MØLLER NEERGAARD.)*

Pkg bbding bbding is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{bbding}[1999/04/15]

2 \newcommand*\LWR@bbdingsymbol[2]{\HTMLUnicode{#2}}
3
4 \newcommand{\LWR@HTML@ScissorRightBrokenBottom}{\LWR@bbdingsymbol{000} {2701}}
5 \newcommand{\LWR@HTML@ScissorRight}{\LWR@bbdingsymbol{001} {2702}}
6 \newcommand{\LWR@HTML@ScissorRightBrokenTop}{\LWR@bbdingsymbol{002} {2703}}
7 \newcommand{\LWR@HTML@ScissorLeftBrokenBottom}{\LWR@bbdingsymbol{003} {2701}}
8 \newcommand{\LWR@HTML@ScissorLeft}{\LWR@bbdingsymbol{004} {2702}}
9 \newcommand{\LWR@HTML@ScissorLeftBrokenTop}{\LWR@bbdingsymbol{005} {2703}}
10 \newcommand{\LWR@HTML@ScissorHollowRight}{\LWR@bbdingsymbol{006} {2704}}
11 \newcommand{\LWR@HTML@ScissorHollowLeft}{\LWR@bbdingsymbol{007} {2704}}
12 \newcommand{\LWR@HTML@Phone}{\LWR@bbdingsymbol{010} {260E}}
13 \newcommand{\LWR@HTML@PhoneHandset}{\LWR@bbdingsymbol{011} {2706}}
14 \newcommand{\LWR@HTML@Tape}{\LWR@bbdingsymbol{012} {2707}}
15 \newcommand{\LWR@HTML@Plane}{\LWR@bbdingsymbol{013} {2708}}
16 \newcommand{\LWR@HTML@Envelope}{\LWR@bbdingsymbol{014} {2709}}
17 \newcommand{\LWR@HTML@HandCuffRight}{\LWR@bbdingsymbol{015} {261B}}
18 \newcommand{\LWR@HTML@HandCuffLeft}{\LWR@bbdingsymbol{016} {261A}}
19 \newcommand{\LWR@HTML@HandCuffRightUp}{\LWR@bbdingsymbol{017} {261D}}

```

|    |                                                                       |         |
|----|-----------------------------------------------------------------------|---------|
| 20 | \newcommand{\LWR@HTML@HandCuffLeftUp}{\LWR@bbdingsymbol{020}}         | {261F}} |
| 21 | \newcommand{\LWR@HTML@HandRight}{\LWR@bbdingsymbol{021}}              | {261E}} |
| 22 | \newcommand{\LWR@HTML@HandLeft}{\LWR@bbdingsymbol{022}}               | {261C}} |
| 23 | \newcommand{\LWR@HTML@HandRightUp}{\LWR@bbdingsymbol{023}}            | {261D}} |
| 24 | \newcommand{\LWR@HTML@HandLeftUp}{\LWR@bbdingsymbol{024}}             | {261F}} |
| 25 | \newcommand{\LWR@HTML@Peace}{\LWR@bbdingsymbol{025}}                  | {270C}} |
| 26 | \newcommand{\LWR@HTML@HandPencilLeft}{\LWR@bbdingsymbol{026}}         | {270D}} |
| 27 | \newcommand{\LWR@HTML@PencilRight}{\LWR@bbdingsymbol{027}}            | {270F}} |
| 28 | \newcommand{\LWR@HTML@PencilLeft}{\LWR@bbdingsymbol{030}}             | {270F}} |
| 29 | \newcommand{\LWR@HTML@PencilRightUp}{\LWR@bbdingsymbol{031}}          | {2710}} |
| 30 | \newcommand{\LWR@HTML@PencilLeftUp}{\LWR@bbdingsymbol{032}}           | {2710}} |
| 31 | \newcommand{\LWR@HTML@PencilRightDown}{\LWR@bbdingsymbol{033}}        | {270E}} |
| 32 | \newcommand{\LWR@HTML@PencilLeftDown}{\LWR@bbdingsymbol{034}}         | {270E}} |
| 33 | \newcommand{\LWR@HTML@NibRight}{\LWR@bbdingsymbol{035}}               | {2711}} |
| 34 | \newcommand{\LWR@HTML@NibLeft}{\LWR@bbdingsymbol{036}}                | {2711}} |
| 35 | \newcommand{\LWR@HTML@NibSolidRight}{\LWR@bbdingsymbol{037}}          | {2712}} |
| 36 | \newcommand{\LWR@HTML@NibSolidLeft}{\LWR@bbdingsymbol{040}}           | {2712}} |
| 37 | \newcommand{\LWR@HTML@Checkmark}{\LWR@bbdingsymbol{041}}              | {2713}} |
| 38 | \newcommand{\LWR@HTML@CheckmarkBold}{\LWR@bbdingsymbol{042}}          | {2714}} |
| 39 | \newcommand{\LWR@HTML@XSolid}{\LWR@bbdingsymbol{043}}                 | {2715}} |
| 40 | \newcommand{\LWR@HTML@XSolidBold}{\LWR@bbdingsymbol{044}}             | {2716}} |
| 41 | \newcommand{\LWR@HTML@XSolidBrush}{\LWR@bbdingsymbol{045}}            | {2717}} |
| 42 | \newcommand{\LWR@HTML@PlusOutline}{\LWR@bbdingsymbol{046}}            | {2719}} |
| 43 | \newcommand{\LWR@HTML@Plus}{\LWR@bbdingsymbol{047}}                   | {271A}} |
| 44 | \newcommand{\LWR@HTML@PlusCenterOpen}{\LWR@bbdingsymbol{050}}         | {271C}} |
| 45 | \newcommand{\LWR@HTML@PlusThinCenterOpen}{\LWR@bbdingsymbol{051}}     | {271B}} |
| 46 | \newcommand{\LWR@HTML@Cross}{\LWR@bbdingsymbol{052}}                  | {271D}} |
| 47 | \newcommand{\LWR@HTML@CrossOpenShadow}{\LWR@bbdingsymbol{053}}        | {271E}} |
| 48 | \newcommand{\LWR@HTML@CrossOutline}{\LWR@bbdingsymbol{054}}           | {271F}} |
| 49 | \newcommand{\LWR@HTML@CrossBoldOutline}{\LWR@bbdingsymbol{055}}       | {271F}} |
| 50 | \newcommand{\LWR@HTML@CrossMaltese}{\LWR@bbdingsymbol{056}}           | {2720}} |
| 51 | \newcommand{\LWR@HTML@DavidStarSolid}{\LWR@bbdingsymbol{057}}         | {2721}} |
| 52 | \newcommand{\LWR@HTML@DavidStar}{\LWR@bbdingsymbol{060}}              | {2721}} |
| 53 | \newcommand{\LWR@HTML@FourAsterisk}{\LWR@bbdingsymbol{061}}           | {2722}} |
| 54 | \newcommand{\LWR@HTML@JackStar}{\LWR@bbdingsymbol{062}}               | {2723}} |
| 55 | \newcommand{\LWR@HTML@JackStarBold}{\LWR@bbdingsymbol{063}}           | {2724}} |
| 56 | \newcommand{\LWR@HTML@CrossLowerTips}{\LWR@bbdingsymbol{064}}         | {2725}} |
| 57 | \newcommand{\LWR@HTML@FourStar}{\LWR@bbdingsymbol{065}}               | {2726}} |
| 58 | \newcommand{\LWR@HTML@FourStarOpen}{\LWR@bbdingsymbol{066}}           | {2727}} |
| 59 | \newcommand{\LWR@HTML@FiveStarLines}{\LWR@bbdingsymbol{067}}          | {2729}} |
| 60 | \newcommand{\LWR@HTML@FiveStar}{\LWR@bbdingsymbol{070}}               | {2605}} |
| 61 | \newcommand{\LWR@HTML@FiveStarOpen}{\LWR@bbdingsymbol{071}}           | {2729}} |
| 62 | \newcommand{\LWR@HTML@FiveStarOpenCircled}{\LWR@bbdingsymbol{072}}    | {272A}} |
| 63 | \newcommand{\LWR@HTML@FiveStarCenterOpen}{\LWR@bbdingsymbol{073}}     | {272B}} |
| 64 | \newcommand{\LWR@HTML@FiveStarOpenDotted}{\LWR@bbdingsymbol{074}}     | {272C}} |
| 65 | \newcommand{\LWR@HTML@FiveStarOutline}{\LWR@bbdingsymbol{075}}        | {272D}} |
| 66 | \newcommand{\LWR@HTML@FiveStarOutlineHeavy}{\LWR@bbdingsymbol{076}}   | {272E}} |
| 67 | \newcommand{\LWR@HTML@FiveStarConvex}{\LWR@bbdingsymbol{077}}         | {272F}} |
| 68 | \newcommand{\LWR@HTML@FiveStarShadow}{\LWR@bbdingsymbol{100}}         | {2730}} |
| 69 | \newcommand{\LWR@HTML@AsteriskBold}{\LWR@bbdingsymbol{101}}           | {2731}} |
| 70 | \newcommand{\LWR@HTML@AsteriskCenterOpen}{\LWR@bbdingsymbol{102}}     | {2732}} |
| 71 | \newcommand{\LWR@HTML@AsteriskThin}{\LWR@bbdingsymbol{103}}           | {273B}} |
| 72 | \newcommand{\LWR@HTML@AsteriskThinCenterOpen}{\LWR@bbdingsymbol{104}} | {273C}} |
| 73 | \newcommand{\LWR@HTML@EightStarTaper}{\LWR@bbdingsymbol{105}}         | {2733}} |
| 74 | \newcommand{\LWR@HTML@EightStarConvex}{\LWR@bbdingsymbol{106}}        | {2735}} |

|     |                                                                                         |         |
|-----|-----------------------------------------------------------------------------------------|---------|
| 75  | <code>\newcommand{\LWR@HTML@SixStar}{\LWR@bbdingsymbol{107}}</code>                     | {2736}} |
| 76  | <code>\newcommand{\LWR@HTML@EightStar}{\LWR@bbdingsymbol{110}}</code>                   | {2737}} |
| 77  | <code>\newcommand{\LWR@HTML@EightStarBold}{\LWR@bbdingsymbol{111}}</code>               | {2738}} |
| 78  | <code>\newcommand{\LWR@HTML@TwelveStar}{\LWR@bbdingsymbol{112}}</code>                  | {2739}} |
| 79  | <code>\newcommand{\LWR@HTML@SixteenStarLight}{\LWR@bbdingsymbol{113}}</code>            | {273A}} |
| 80  | <code>\newcommand{\LWR@HTML@SixFlowerPetalRemoved}{\LWR@bbdingsymbol{114}}</code>       | {273B}} |
| 81  | <code>\newcommand{\LWR@HTML@SixFlowerOpenCenter}{\LWR@bbdingsymbol{115}}</code>         | {273C}} |
| 82  | <code>\newcommand{\LWR@HTML@Asterisk}{\LWR@bbdingsymbol{116}}</code>                    | {273D}} |
| 83  | <code>\newcommand{\LWR@HTML@SixFlowerAlternate}{\LWR@bbdingsymbol{117}}</code>          | {273E}} |
| 84  | <code>\newcommand{\LWR@HTML@FiveFlowerPetal}{\LWR@bbdingsymbol{120}}</code>             | {273F}} |
| 85  | <code>\newcommand{\LWR@HTML@SixFlowerPetalDotted}{\LWR@bbdingsymbol{121}}</code>        | {2740}} |
| 86  | <code>\newcommand{\LWR@HTML@FiveFlowerOpen}{\LWR@bbdingsymbol{122}}</code>              | {2740}} |
| 87  | <code>\newcommand{\LWR@HTML@EightFlowerPetal}{\LWR@bbdingsymbol{123}}</code>            | {2741}} |
| 88  | <code>\newcommand{\LWR@HTML@SunshineOpenCircled}{\LWR@bbdingsymbol{124}}</code>         | {2742}} |
| 89  | <code>\newcommand{\LWR@HTML@SixFlowerAltPetal}{\LWR@bbdingsymbol{125}}</code>           | {2743}} |
| 90  | <code>\newcommand{\LWR@HTML@FourClowerOpen}{\LWR@bbdingsymbol{126}}</code>              | {273F}} |
| 91  | <code>\newcommand{\LWR@HTML@FourClowerSolid}{\LWR@bbdingsymbol{127}}</code>             | {273F}} |
| 92  | <code>\newcommand{\LWR@HTML@AsteriskRoundedEnds}{\LWR@bbdingsymbol{130}}</code>         | {2749}} |
| 93  | <code>\newcommand{\LWR@HTML@EightFlowerPetalRemoved}{\LWR@bbdingsymbol{131}}</code>     | {274A}} |
| 94  | <code>\newcommand{\LWR@HTML@EightAsterisk}{\LWR@bbdingsymbol{132}}</code>               | {274B}} |
| 95  | <code>\newcommand{\LWR@HTML@SixFlowerRemovedOpenPetal}{\LWR@bbdingsymbol{133}}</code>   | {2740}} |
| 96  | <code>\newcommand{\LWR@HTML@SparkleBold}{\LWR@bbdingsymbol{134}}</code>                 | {2748}} |
| 97  | <code>\newcommand{\LWR@HTML@Sparkle}{\LWR@bbdingsymbol{135}}</code>                     | {2747}} |
| 98  | <code>\newcommand{\LWR@HTML@SnowflakeChevron}{\LWR@bbdingsymbol{136}}</code>            | {2744}} |
| 99  | <code>\newcommand{\LWR@HTML@SnowflakeChevronBold}{\LWR@bbdingsymbol{137}}</code>        | {2746}} |
| 100 | <code>\newcommand{\LWR@HTML@Snowflake}{\LWR@bbdingsymbol{140}}</code>                   | {2744}} |
| 101 | <code>\newcommand{\LWR@HTML@CircleSolid}{\LWR@bbdingsymbol{141}}</code>                 | {25CF}} |
| 102 | <code>\newcommand{\LWR@HTML@Ellipse}{\LWR@bbdingsymbol{142}}</code>                     | {274D}} |
| 103 | <code>\newcommand{\LWR@HTML@EllipseSolid}{\LWR@bbdingsymbol{143}}</code>                | {25CF}} |
| 104 | <code>\newcommand{\LWR@HTML@CircleShadow}{\LWR@bbdingsymbol{144}}</code>                | {274D}} |
| 105 | <code>\newcommand{\LWR@HTML@EllipseShadow}{\LWR@bbdingsymbol{145}}</code>               | {274D}} |
| 106 | <code>\newcommand{\LWR@HTML@Square}{\LWR@bbdingsymbol{146}}</code>                      | {25A1}} |
| 107 | <code>\newcommand{\LWR@HTML@SquareSolid}{\LWR@bbdingsymbol{147}}</code>                 | {25A0}} |
| 108 | <code>\newcommand{\LWR@HTML@SquareShadowBottomRight}{\LWR@bbdingsymbol{150}}</code>     | {2751}} |
| 109 | <code>\newcommand{\LWR@HTML@SquareShadowTopRight}{\LWR@bbdingsymbol{151}}</code>        | {2752}} |
| 110 | <code>\newcommand{\LWR@HTML@SquareShadowTopLeft}{\LWR@bbdingsymbol{152}}</code>         | {2752}} |
| 111 | <code>\newcommand{\LWR@HTML@SquareCastShadowBottomRight}{\LWR@bbdingsymbol{153}}</code> | {2751}} |
| 112 | <code>\newcommand{\LWR@HTML@SquareCastShadowTopRight}{\LWR@bbdingsymbol{154}}</code>    | {2752}} |
| 113 | <code>\newcommand{\LWR@HTML@SquareCastShadowTopLeft}{\LWR@bbdingsymbol{155}}</code>     | {2752}} |
| 114 | <code>\newcommand{\LWR@HTML@TriangleUp}{\LWR@bbdingsymbol{156}}</code>                  | {25B2}} |
| 115 | <code>\newcommand{\LWR@HTML@TriangleDown}{\LWR@bbdingsymbol{157}}</code>                | {25BC}} |
| 116 | <code>\newcommand{\LWR@HTML@DiamondSolid}{\LWR@bbdingsymbol{160}}</code>                | {25C6}} |
| 117 | <code>\newcommand{\LWR@HTML@OrnamentDiamondSolid}{\LWR@bbdingsymbol{161}}</code>        | {2756}} |
| 118 | <code>\newcommand{\LWR@HTML@HalfCircleRight}{\LWR@bbdingsymbol{162}}</code>             | {25D7}} |
| 119 | <code>\newcommand{\LWR@HTML@HalfCircleLeft}{\LWR@bbdingsymbol{163}}</code>              | {25D6}} |
| 120 | <code>\newcommand{\LWR@HTML@RectangleThin}{\LWR@bbdingsymbol{164}}</code>               | {2758}} |
| 121 | <code>\newcommand{\LWR@HTML@Rectangle}{\LWR@bbdingsymbol{165}}</code>                   | {2759}} |
| 122 | <code>\newcommand{\LWR@HTML@RectangleBold}{\LWR@bbdingsymbol{166}}</code>               | {275A}} |
| 123 | <code>\newcommand{\LWR@HTML@ArrowBoldRightStrobe}{\LWR@bbdingsymbol{167}}</code>        | {27A0}} |
| 124 | <code>\newcommand{\LWR@HTML@ArrowBoldUpRight}{\LWR@bbdingsymbol{170}}</code>            | {27A6}} |
| 125 | <code>\newcommand{\LWR@HTML@ArrowBoldDownRight}{\LWR@bbdingsymbol{171}}</code>          | {27A5}} |
| 126 | <code>\newcommand{\LWR@HTML@ArrowBoldRightShort}{\LWR@bbdingsymbol{172}}</code>         | {27A7}} |
| 127 | <code>\newcommand{\LWR@HTML@ArrowBoldRightCircled}{\LWR@bbdingsymbol{173}}</code>       | {27B2}} |
| 128 |                                                                                         |         |
| 129 |                                                                                         |         |

130 \LWR@formatted{ScissorRightBrokenBottom}  
131 \LWR@formatted{ScissorRight}  
132 \LWR@formatted{ScissorRightBrokenTop}  
133 \LWR@formatted{ScissorLeftBrokenBottom}  
134 \LWR@formatted{ScissorLeft}  
135 \LWR@formatted{ScissorLeftBrokenTop}  
136 \LWR@formatted{ScissorHollowRight}  
137 \LWR@formatted{ScissorHollowLeft}  
138 \LWR@formatted{Phone}  
139 \LWR@formatted{PhoneHandset}  
140 \LWR@formatted{Tape}  
141 \LWR@formatted{Plane}  
142 \LWR@formatted{Envelope}  
143 \LWR@formatted{HandCuffRight}  
144 \LWR@formatted{HandCuffLeft}  
145 \LWR@formatted{HandCuffRightUp}  
146 \LWR@formatted{HandCuffLeftUp}  
147 \LWR@formatted{HandRight}  
148 \LWR@formatted{HandLeft}  
149 \LWR@formatted{HandRightUp}  
150 \LWR@formatted{HandLeftUp}  
151 \LWR@formatted{Peace}  
152 \LWR@formatted{HandPencilLeft}  
153 \LWR@formatted{PencilRight}  
154 \LWR@formatted{PencilLeft}  
155 \LWR@formatted{PencilRightUp}  
156 \LWR@formatted{PencilLeftUp}  
157 \LWR@formatted{PencilRightDown}  
158 \LWR@formatted{PencilLeftDown}  
159 \LWR@formatted{NibRight}  
160 \LWR@formatted{NibLeft}  
161 \LWR@formatted{NibSolidRight}  
162 \LWR@formatted{NibSolidLeft}  
163 \LWR@formatted{Checkmark}  
164 \LWR@formatted{CheckmarkBold}  
165 \LWR@formatted{XSolid}  
166 \LWR@formatted{XSolidBold}  
167 \LWR@formatted{XSolidBrush}  
168 \LWR@formatted{PlusOutline}  
169 \LWR@formatted{Plus}  
170 \LWR@formatted{PlusCenterOpen}  
171 \LWR@formatted{PlusThinCenterOpen}  
172 \LWR@formatted{Cross}  
173 \LWR@formatted{CrossOpenShadow}  
174 \LWR@formatted{CrossOutline}  
175 \LWR@formatted{CrossBoldOutline}  
176 \LWR@formatted{CrossMaltese}  
177 \LWR@formatted{DavidStarSolid}  
178 \LWR@formatted{DavidStar}  
179 \LWR@formatted{FourAsterisk}  
180 \LWR@formatted{JackStar}  
181 \LWR@formatted{JackStarBold}  
182 \LWR@formatted{CrossCLowerTips}  
183 \LWR@formatted{FourStar}  
184 \LWR@formatted{FourStarOpen}

185 \LWR@formatted{FiveStarLines}  
186 \LWR@formatted{FiveStar}  
187 \LWR@formatted{FiveStarOpen}  
188 \LWR@formatted{FiveStarOpenCircled}  
189 \LWR@formatted{FiveStarCenterOpen}  
190 \LWR@formatted{FiveStarOpenDotted}  
191 \LWR@formatted{FiveStarOutline}  
192 \LWR@formatted{FiveStarOutlineHeavy}  
193 \LWR@formatted{FiveStarConvex}  
194 \LWR@formatted{FiveStarShadow}  
195 \LWR@formatted{AsteriskBold}  
196 \LWR@formatted{AsteriskCenterOpen}  
197 \LWR@formatted{AsteriskThin}  
198 \LWR@formatted{AsteriskThinCenterOpen}  
199 \LWR@formatted{EightStarTaper}  
200 \LWR@formatted{EightStarConvex}  
201 \LWR@formatted{SixStar}  
202 \LWR@formatted{EightStar}  
203 \LWR@formatted{EightStarBold}  
204 \LWR@formatted{TwelveStar}  
205 \LWR@formatted{SixteenStarLight}  
206 \LWR@formatted{SixFlowerPetalRemoved}  
207 \LWR@formatted{SixFlowerOpenCenter}  
208 \LWR@formatted{Asterisk}  
209 \LWR@formatted{SixFlowerAlternate}  
210 \LWR@formatted{FiveFlowerPetal}  
211 \LWR@formatted{SixFlowerPetalDotted}  
212 \LWR@formatted{FiveFlowerOpen}  
213 \LWR@formatted{EightFlowerPetal}  
214 \LWR@formatted{SunshineOpenCircled}  
215 \LWR@formatted{SixFlowerAltPetal}  
216 \LWR@formatted{FourCLowerOpen}  
217 \LWR@formatted{FourCLowerSolid}  
218 \LWR@formatted{AsteriskRoundedEnds}  
219 \LWR@formatted{EightFlowerPetalRemoved}  
220 \LWR@formatted{EightAsterisk}  
221 \LWR@formatted{SixFlowerRemovedOpenPetal}  
222 \LWR@formatted{SparkleBold}  
223 \LWR@formatted{Sparkle}  
224 \LWR@formatted{SnowflakeChevron}  
225 \LWR@formatted{SnowflakeChevronBold}  
226 \LWR@formatted{Snowflake}  
227 \LWR@formatted{CircleSolid}  
228 \LWR@formatted{Ellipse}  
229 \LWR@formatted{EllipseSolid}  
230 \LWR@formatted{CircleShadow}  
231 \LWR@formatted{EllipseShadow}  
232 \LWR@formatted{Square}  
233 \LWR@formatted{SquareSolid}  
234 \LWR@formatted{SquareShadowBottomRight}  
235 \LWR@formatted{SquareShadowTopRight}  
236 \LWR@formatted{SquareShadowTopLeft}  
237 \LWR@formatted{SquareCastShadowBottomRight}  
238 \LWR@formatted{SquareCastShadowTopRight}  
239 \LWR@formatted{SquareCastShadowTopLeft}

```

240 \LWR@formatted{TriangleUp}
241 \LWR@formatted{TriangleDown}
242 \LWR@formatted{DiamondSolid}
243 \LWR@formatted{OrnamentDiamondSolid}
244 \LWR@formatted{HalfCircleRight}
245 \LWR@formatted{HalfCircleLeft}
246 \LWR@formatted{RectangleThin}
247 \LWR@formatted{Rectangle}
248 \LWR@formatted{RectangleBold}
249 \LWR@formatted{ArrowBoldRightStrobe}
250 \LWR@formatted{ArrowBoldUpRight}
251 \LWR@formatted{ArrowBoldDownRight}
252 \LWR@formatted{ArrowBoldRightShort}
253 \LWR@formatted{ArrowBoldRightCircled}

```

---

File 43 **lwarp-biblatex.sty**

§ 149 Package **biblatex**

*(Emulates or patches code by PHILIPP LEHMAN.)*

Pkg biblatex When biblatex is used, modifications from newfloat may have to be undone.

**for HTML output:**

1. lwarp uses newfloat.
2. For classes with chapters which newfloat does not know about, such as CTEX-related classes, newfloat may modify \addtocontents.
3. biblatex, though, wants to patch \addtocontents, which causes an error if \addtocontents has been changed.
4. Therefore, \addtocontents is restored to its original here, since biblatex is about to be loaded.
5. This means that the newfloat's chapterlistsgaps option may no longer work.

```

1 \ifdef{\newfloat@addtocontents@ORI}{
2 \let\addtocontents\newfloat@addtocontents@ORI
3 }{}

```

hyperref emulation is loaded \AtBeginDocument to avoid an options clash.

```

4 \AtBeginDocument{\RequirePackage{hyperref}}
5
6 \LWR@ProvidesPackagePass{biblatex}[2018/03/04]

```

The following create hyperlinks to the references. The original code to use hyperref is recreated here, because hyperref is emulated.

```

7 \AfterPreamble{
8
9 \let\blx@anchors\@empty

```

```

10 \protected\def\blx@anchor{%
11 \xifinlist{\the\c@refsection @\abx@field@entrykey}{\blx@anchors}
12 {}
13 {\listxadd\blx@anchors{\the\c@refsection @\abx@field@entrykey}%
14 \hypertarget{cite.\the\c@refsection @\abx@field@entrykey}{}}}
15
16 \protected\def\blx@imc@bibhyperref{%
17 \@ifnextchar[%
18 {\blx@bibhyperref}
19 {\blx@bibhyperref[\abx@field@entrykey]}}%
20
21 \long\def\blx@bibhyperref[#1]#2{%
22 % \blx@sfsave
23 \hyperlink{cite.\the\c@refsection @#1}{%
24 % \blx@sffrest
25 % #2%
26 % \blx@sfsave
27 % }%
28 % \blx@sffrest%
29 }%% \def\blx@nohyperref[#1]#2{#2}%
30
31 \protected\long\def\blx@imc@bibhyperlink#1#2{%
32 % \blx@sfsave
33 \hyperlink{cite.\the\c@refsection:#1}{%
34 % \blx@sffrest
35 % #2%
36 % \blx@sfsave
37 % }%
38 % \blx@sffrest%
39 }%
40
41 \protected\long\def\blx@imc@bibhypertarget#1#2{%
42 % \blx@sfsave%
43 \hypertarget{cite.\the\c@refsection:#1}{%
44 % \blx@sffrest
45 % #2%
46 % \blx@sfsave%
47 % }%
48 % \blx@sffrest%
49 }
50
51 \let\blx@imc@ifhyperref\@firstoftwo

```

The following patches are for back page references.

```

52 \DeclareListFormat{pageref}{%
53 \ifnumless{\abx@pagerefstyle}{0}
54 {\usebibmacro{list:plain}%
55 \ifhyperref
56 {%
57 % \hyperlink{page.#1}{#1}%
58 % \ref{\BaseJobname-autopage-#1}% lwarp
59 }
60 {#1}}
61 {\ifnumequal{\value{listcount}}{1}

```

```

62 {\usebibmacro{pageref:init}}
63 {}%
64 \usebibmacro{pageref:comp}{#1}%
65 \ifnumequal{\value{listcount}}{\value{liststop}}
66 {\usebibmacro{pageref:dump}}
67 {}}
68
69 \renewbibmacro*{pageref:comp}[1]{%
70 \numdef\abx@range@prev{\abx@range@prev+1}%
71 \ifinteger{#1}
72 {\def\abx@range@num{#1}%
73 \def\abx@range@this{1}%
74 \ifnumequal{\abx@range@this}{\abx@range@last}
75 {}
76 {\def\abx@range@prev{-1}}}
77 {\ifrmnum{#1}
78 {\numdef\abx@range@num{\rmntonum{#1}}%
79 \def\abx@range@this{2}%
80 \ifnumequal{\abx@range@this}{\abx@range@last}
81 {}
82 {\def\abx@range@prev{-1}}}
83 {\undef\abx@range@num
84 \def\abx@range@this{0}%
85 \def\abx@range@prev{-1}}}%
86 \ifdef\abx@range@num
87 {\ifnumequal{\abx@range@num}{\abx@range@prev}
88 {\def\abx@range@hold{#1}%
89 \numdef\abx@range@diff{\abx@range@diff+1}}
90 {\usebibmacro{pageref:dump}%
91 \ifnumgreater{\abx@range@last}{-1}
92 {\printdelim{multilistdelim}}
93 {}%
94 \ifhyperref
95 {\hyperlink{page.#1}{#1}}
96 {\ref{\BaseJobname-autopage-#1}}% lwarp
97 {#1}}%
98 \edef\abx@range@prev{\abx@range@num}}
99 {\usebibmacro{pageref:dump}%
100 \ifnumgreater{\abx@range@last}{-1}
101 {\printdelim{multilistdelim}}
102 {}%
103 \ifhyperref
104 {\hyperlink{page.#1}{#1}}
105 {\ref{\BaseJobname-autopage-#1}}% lwarp
106 {#1}}%
107 \def\abx@range@prev{-1}}%
108 \edef\abx@range@last{\abx@range@this}}
109
110 \renewbibmacro*{pageref:dump}{%
111 \ifnumgreater{\abx@range@diff}{0}
112 {\ifcase\abx@pagerefstyle\relax % two
113 \bibrangedash
114 \ifhyperref
115 {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
116 {\ref{\BaseJobname-autopage-\abx@range@hold}}% lwarp

```

```

117 {\abx@range@hold}%
118 \or % three
119 \ifnumless{\abx@range@diff}{2}
120 {\printdelim{multilistdelim}}
121 {\bibrangedash}%
122 \ifhyperref
123 % {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
124 {\ref{\BaseJobname-autopage-\abx@range@hold}}% lwarp
125 {\abx@range@hold}%
126 \or % two+
127 \ifnumless{\abx@range@diff}{2}
128 {\sqspace
129 \ifhyperref
130 % {\hyperlink{page.\abx@range@hold}{\bibstring{sequens}}}
131 {\ref{\BaseJobname-autopage-\abx@range@hold}}% lwarp
132 {\bibstring{sequens}}}
133 {\bibrangedash
134 \ifhyperref
135 % {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
136 {\ref{\BaseJobname-autopage-\abx@range@hold}}% lwarp
137 {\abx@range@hold}}%
138 \or % three+
139 \ifnumless{\abx@range@diff}{2}
140 {\sqspace
141 \ifhyperref
142 % {\hyperlink{page.\abx@range@hold}{\bibstring{sequens}}}
143 {\ref{\BaseJobname-autopage-\abx@range@hold}}% lwarp
144 {\bibstring{sequens}}}
145 {\ifnumless{\abx@range@diff}{3}
146 {\sqspace
147 \ifhyperref
148 % {\hyperlink{page.\abx@range@hold}{\bibstring{sequentes}}}
149 {\ref{\BaseJobname-autopage-\abx@range@hold}}% lwarp
150 {\bibstring{sequentes}}}
151 {\bibrangedash
152 \ifhyperref
153 % {\hyperlink{page.\abx@range@hold}{\abx@range@hold}}
154 {\ref{\BaseJobname-autopage-\abx@range@hold}}% lwarp
155 {\abx@range@hold}}}%
156 \else % all+
157 \ifnumless{\abx@range@diff}{2}
158 {\sqspace
159 \ifhyperref
160 % {\hyperlink{page.\abx@range@hold}{\bibstring{sequens}}}
161 {\ref{\BaseJobname-autopage-\abx@range@hold}}% lwarp
162 {\bibstring{sequens}}}
163 {\sqspace
164 \ifhyperref
165 % {\hyperlink{page.\abx@range@hold}{\bibstring{sequentes}}}
166 {\ref{\BaseJobname-autopage-\abx@range@hold}}% lwarp
167 {\bibstring{sequentes}}}%
168 \fi
169 \def\abx@range@diff{0}}
170 {}
171

```

---

```
172 }% \AfterPreamble
```

---

File 44 **lwarp-bibunits.sty**

§ 150 Package **bibunits**

(Emulates or patches code by THORSTEN HANSEN.)

Pkg bibunits bibunits is patched for use by lwarp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{bibunits}[2004/05/12]
2 \def\bu@bibdata{\BaseJobname}
```

---

File 45 **lwarp-bigdelim.sty**

§ 151 Package **bigdelim**

(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)

Pkg bigdelim bigdelim is used as-is for print or lateximage, and patched for HTML.

The delimiters are displayed in HTML by printing the delimiter, the text, and a thick border across the side of the `\multirow` which indicates the actual height of the delimiter. The delimiter character is given a `<span>` class of `ldelim` or `rdelim`, and the default CSS sets this to `font-size:200%`

 **use `\mrowcell`** `\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

---

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\}{3}{.25in}[left] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

---

```
<-> a b
 {
left { c d
 { e f
 { g h
 {
<-> i j
```

---

For MATHJAX, limited emulation is provided which merely prints the delimiter and optional text in the first row.

**for HTML output:** First, remove the temporary definitions of `\ldelim` and `\rdelim`, which were previously defined for tabular scanning in case `bigdelim` was not loaded:

```
1 \let\ldelim\relax
2 \let\rdelim\relax
```

Next, load the package's new definitions:

```
3 \LWR@ProvidesPackagePass{bigdelim}[2018/08/03]

\ldelim {\langle 1:delimiter \rangle} {\langle 2:#rows \rangle} {\langle 3:width \rangle} [\langle 4:text \rangle]
\rdelim

4 \NewDocumentCommand{\LWR@HTML@ldelim}{m m m O{}}{%
5 \renewcommand{\LWR@multirowborder}{right}%
6 \multirow{#2}{#3}{#4 \InlineClass{ldelim}{#1}}%
7 }
8
9 \LWR@formatted{ldelim}
10
11 \NewDocumentCommand{\LWR@HTML@rdelim}{m m m O{}}{%
12 \renewcommand{\LWR@multirowborder}{left}%
13 \multirow{#2}{#3}{\InlineClass{rdelim}{#1} #4}%
14 }
15
16 \LWR@formatted{rdelim}
```

Limited emulation for MATHJAX. The delimiter is printed on the first row, along with any optional text.

```
17 \begin{warpMathJax}
18 % \ldelim ([n]{width}[text]
19 \CustomizeMathJax{\newcommand{\LWRldelim}[1][]{\text{#1}~\LWRbigdelim}}
20 \CustomizeMathJax{\def\ldelim#1#2#3{\def\LWRbigdelim{#1}\LWRldelim}}
21 % \rdelim) [n]{width}[text]
22 \CustomizeMathJax{\newcommand{\LWRrdelim}[1][]{\LWRbigdelim~\text{#1}}}
23 \CustomizeMathJax{\def\rdelim#1#2#3{\def\LWRbigdelim{#1}\LWRrdelim}}
24 \end{warpMathJax}
```

---

File 46 **lwarp-bigfoot.sty**

§ 152 Package **bigfoot**

Pkg bigfoot bigfoot is emulated.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{bigfoot}[2015/08/30]

2 \RequirePackage{manyfoot}
3 \RequirePackage{perpage}
4
5 \def\RestyleFootnote#1#2{
6 \def\FootnoteSpecific#1{
7 \def\DefineFootnoteStack#1{
```

---

```

8 \def\PushFootnoteMark#1{}
9 \def\PopFootnoteMark#1{}
10 \def\hfootfraction{0.9}
11 \def\vtypefraction{0.7}
12 \def\FootnoteMinimum{1sp}
13 \def\FootnoteMainMinimum{0pt}
14 \newcount\bigfoottolerance
15 \bigfoottolerance=100
16 \providecommand\footnotecarryratio{2}

```

---

File 47 **lwarp-bigstrut.sty**

§ 153 Package **bigstrut**

*(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)*

Pkg bigstrut bigstrut is used as-is for print or lateximage, and patched for HTML.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{bigstrut}[2018/08/03]

2 \LetLtxMacro\LWR@origbigstrut\bigstrut
3
4 \renewcommand\bigstrut[1][x]{}
5
6 \appto\LWR@restoreorigformatting{%
7 \LetLtxMacro\bigstrut\LWR@origbigstrut%
8 }
9

10 \begin{warpMathJax}
11 \CustomizeMathJax{\newcommand{\bigstrut}[1][x]{} }
12 \end{warpMathJax}

```

---

File 48 **lwarp-bitpattern.sty**

§ 154 Package **bitpattern**

*(Emulates or patches code by JEAN-MARC BOURGUET.)*

Pkg bitpattern bitpattern is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{bitpattern}[2015/12/11]

2 \xpatchcmd{\bitpattern}
3 {\begingroup}
4 {\begin{lateximage}[-bitpattern-~\PackageDiagramAltText]}
5 {}
6 {\LWR@patcherror{bitpattern}{bitpattern}}
7

```

---

```

8 \xpatchcmd{\bp@Done}
9 {\endgroup}
10 {\end{lateximage}}
11 {}
12 {\LWR@patcherror{bitpattern}{bp@Done}}

```

---

File 49 **lwarp-blowup.sty**

§ 155 Package **blowup**

Pkg blowup blowup is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{blowup}[2018/01/02]

2 \newcommand\*\blowUp[1]{}

---

File 50 **lwarp-bm.sty**

§ 156 Package **bm**

(Emulates or patches code by DAVID CARLISLE, FRANK MITTELBACH.)

Pkg bm bm is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{bm}[2019/07/24]

\DeclareBoldMathCommand must only be used in the preamble, since it adds to the MATHJAX setup code.

```

2 \begin{warpMathJax}
3 \LetLtxMacro\LWR@orig@DeclareBoldMathCommand\DeclareBoldMathCommand
4
5 \renewcommand\DeclareBoldMathCommand[3][bold]{%
6 \LWR@orig@DeclareBoldMathCommand[#1]{#2}{#3}%
7 \CustomizeMathJax{\newcommand{#2}{\boldsymbol{#3}}}%
8 }
9
10 \onlypreamble\DeclareBoldMathCommand
11
12 \CustomizeMathJax{\newcommand{\bm}[1]{\boldsymbol{#1}}}
13 \end{warpMathJax}

```

---

File 51 **lwarp-booklet.sty**

§ 157 Package **booklet**

(Emulates or patches code by PETER WILSON.)

Pkg booklet **booklet** is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{booklet}[2009/09/02]

2 \newdimen\pageseplength
3 \newdimen\pagesepwidth
4 \newdimen\pagesepoffset
5 \newif\ifsidebyside \sidebysidetrue
6 \newif\ifuselandscape \uselandscapefalse
7 \newif\ifprintoption \printoptionfalse
8 \newcommand*\pagespersignature[1]{}
9 \def\magstepminus#1{}
10 \newcommand*\target[3]{}
11 \newcommand*\source[3]{}
12 \newcommand*\setpdftargetpages{}
13 \newcommand*\setdvipstargetpages{}
14 \newcommand*\targettopbottom{}
15 \newcommand*\twoupemptypage{}
16 \newcommand*\twoupclearpage{}
17 \newcommand*\checkforlandscape{}

```

File 52 **lwarp-bookmark.sty**

§ 158 Package **bookmark**

*(Emulates or patches code by HEIKO OBERDIEK.)*

Pkg bookmark **bookmark** is ignored.

**for HTML output:** Discard all options for **lwarp-bookmark**:

```

1 \LWR@ProvidesPackageDrop{bookmark}[2016/05/17]

2 \newcommand*\bookmarksetup[1]{}
3 \newcommand*\bookmarksetupnext[1]{}
4 \newcommand*\bookmark[2][1]{}
5 \newcommand*\bookmarkdefinestyle[2]{}
6 \newcommand*\bookmarkget[1]{}
7 \newcommand{\BookmarkAtEnd}[1]{}

```

File 53 **lwarp-booktabs.sty**

§ 159 Package **booktabs**

*(Emulates or patches code by SIMON FEAR.)*

Pkg booktabs **booktabs** is emulated during HTML output, and used as-is during print output and inside an HTML `latex` image.

 `\cmidrule` For MATHJAX, emulation is provided in math mode, but `\cmidrule` trim must not be

used.

for HTML output:

If `booktabs` has already been loaded before `lwarp`, such as by `memoir`, use it as-is. If not, the `lwarp` core will have placed some dummy macros which should be removed before loading the actual `booktabs` definitions.

```

1 \@ifpackageloaded{booktabs}{
2 \LetLtxMacro\toprule\relax
3 \LetLtxMacro\midrule\relax
4 \LetLtxMacro\cmidrule\cline
5 \LetLtxMacro\bottomrule\relax
6 \LetLtxMacro\addlinespace\relax
7 \LetLtxMacro\morecmidrules\relax
8 \LetLtxMacro\specialrule\relax
9 }

```

Next, load the `booktabs` package:

```
10 \LWR@ProvidesPackagePass{booktabs}[2019/10/08]
```

Adjust to work even if `xltabular` is loaded:

```

11 % \def\LWR@HTML@BLTrule{\@BTnormal}
12 %
13 % \LWR@formatted{@BLTrule}
14 \LetLtxMacro@BLTrule\@BTnormal

15 \DeclareDocumentCommand{\LWR@HTML@toprule}{o d()}%
16 {%
17 \IfValueTF{#1}%
18 {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
19 {%
20 \ifbool{FormatWP}%
21 {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
22 {\booltrue{LWR@doingtbrule}}}%
23 }%
24 \LWR@getmynexttoken}
25
26 \LWR@expandableformatted{toprule}
27
28 \DeclareDocumentCommand{\LWR@HTML@midrule}{o d()}%
29 {%
30 \IfValueTF{#1}%
31 {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
32 {%
33 \ifbool{FormatWP}%
34 {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
35 {\defaddtocounter{LWR@hlines}{1}}}%
36 }%
37 \LWR@getmynexttoken}
38
39 \LWR@expandableformatted{midrule}
40
41 \DeclareDocumentCommand{\LWR@HTML@cmidrule}{O{\LWR@cmidrulewidth} d() m}{%
42 \LWR@docmidrule[#1](#2){#3}%

```

```

43 \LWR@getmynexttoken%
44 }%
45
46 \LWR@expandableformatted{cmidrule}
47
48 \DeclareDocumentCommand{\LWR@HTML@bottomrule}{o d()}{%
49 \IfValueTF{#1}%
50 {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
51 {%
52 \ifbool{FormatWP}%
53 {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
54 {\booltrue{LWR@doingtbrule}}}%
55 }%
56 \LWR@getmynexttoken%
57 }%
58
59 \LWR@expandableformatted{bottomrule}
60
61 \DeclareDocumentCommand{\LWR@HTML@addlinespace}{o}{}%
62
63 \LWR@expandableformatted{addlinespace}
64
65 \DeclareDocumentCommand{\LWR@HTML@morecmidrules}{o}{}%
66
67 \LWR@expandableformatted{morecmidrules}
68
69 \DeclareDocumentCommand{\LWR@HTML@specialrule}{m m m d()}%
70 {\LWR@docmidrule[#1]}{1-\arabic{LWR@tabletotalLaTeXcols}}\LWR@getmynexttoken}%
71
72 \LWR@expandableformatted{specialrule}

```

For MATHJAX:

```

73 \begin{warpMathJax}
74 \CustomizeMathJax{\newcommand{\toprule}[1][\hline]}
75 \CustomizeMathJax{\let\midrule\toprule}
76 \CustomizeMathJax{\let\bottomrule\toprule}
77 \CustomizeMathJax{\newcommand{\cmidrule}[2][{}]}% avoid (trim)
78 \CustomizeMathJax{\newcommand{\morecmidrules}{}}
79 \CustomizeMathJax{\newcommand{\specialrule}[3]{\hline}}
80 \CustomizeMathJax{\newcommand{\addlinespace}[1][{}]}
81 \end{warpMathJax}

```

---

File 54 **lwarp-bophook.sty**

§ 160 Package **bophook**

Pkg bophook **bophook** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{bophook}[2001/03/29]

2 \newcommand\*\AtBeginPage}[1]{}

3 \newcommand\*\PageLayout}[1]{}

---

File 55 **lwarp-bounddvi.sty**

§ 161 Package **bounddvi**

Pkg bounddvi bounddvi is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{bounddvi}[2016/12/28]

---

File 56 **lwarp-boxedminipage.sty**

§ 162 Package **boxedminipage**

*(Emulates or patches code by SCOTT PAKIN.)*

Pkg boxedminipage boxedminipage is emulated for HTML, and used as-is for lateximages.

**for HTML output:** 1 \LWR@ProvidesPackagePass{boxedminipage}[2020/04/19]

```

2 \newenvironment{LWR@HTML@boxedminipage}{%
3 \LWR@stoppars%
4 \begin{BlockClass}{framebox}%
5 \minipage%
6 }
7 {%
8 \endminipage%
9 \end{BlockClass}%
10 \LWR@startpars%
11 }
12 \LWR@formattedenv{boxedminipage}

```

---

File 57 **lwarp-boxedminipage2e.sty**

§ 163 Package **boxedminipage2e**

*(Emulates or patches code by SCOTT PAKIN.)*

Pkg boxedminipage2e boxedminipage2e has been renamed boxedminipage by the author.

**for HTML output:** Automatically loads boxedminipage:

```

1 \LWR@ProvidesPackagePass{boxedminipage2e}

```

File 58 **lwarp-braket.sty**

§ 164 Package **braket**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg braket **braket** works as-is for HTML with SVG math. For MATHJAX, the MATHJAX extension is used.

**for HTML output:** 1 \LWR@ProvidesPackagePass{braket}% No date is provided by the file.

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\require{braket}}
4 \end{warpMathJax}
```

File 59 **lwarp-breakurl.sty**

§ 165 Package **breakurl**

*(Emulates or patches code by VILAR CAMARA NETO.)*

Pkg breakurl **breakurl** is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{breakurl}[2013/04/10]

```
2 \LetLtxMacro\ Burl\LWR@url
3
4 \NewDocumentCommand{\LWR@BurlalTB}{O{} +m m}{%
5 \LWR@ensureDoingApar%
6 \LWR@subHyperref{#2}%
7 \LWR@subHyperrefText{#3}%
8 \endgroup% restore catcodes
9 }
10
11 \newrobustcmd*\ BurlalT{%
12 \begingroup%
13 \LWR@linkcatcodes%
14 \LWR@BurlalTB%
15 }
16
17 \LetLtxMacro\ urlalT\ BurlalT
```

File 60 **lwarp-breqn.sty**

§ 166 Package **breqn**

*(Emulates or patches code by MICHAEL J. DOWNES, MORTEN HØGHOLM.)*

Pkg breqn breqn is patched for use by lwarp.

 darray darray is not supported, and in fact does not work in the print version either.

While using MATHJAX, breqn objects are converted to SVG images.

```

for HTML output: 1 \LWR@ProvidesPackagePass{breqn}[2017/01/27]

2 \setkeys{breqn}{spread={5pt}}
3
4 \def\eqnumside{R}
5 % \def\eqnumplace{T}
6
7 \BeforeBeginEnvironment{dmath}{
8 \begin{BlockClass}{displaymathnumbered}
9 \LWR@newautoidanchor%
10 \booltrue{LWR@indisplaymathimage}%
11 \begin{lateximage}[-breqn dmath- \MathImageAltText]
12 }
13
14 \AfterEndEnvironment{dmath}{
15 \end{lateximage}\end{BlockClass}
16 }
17
18 \BeforeBeginEnvironment{dmath*}{
19 \begin{BlockClass}{displaymath}
20 \LWR@newautoidanchor%
21 \booltrue{LWR@indisplaymathimage}%
22 \begin{lateximage}[-breqn dmath*- \MathImageAltText]
23 }
24
25 \AfterEndEnvironment{dmath*}{
26 \end{lateximage}\end{BlockClass}
27 }
28
29 \BeforeBeginEnvironment{dseries}{
30 \begin{BlockClass}{displaymathnumbered}
31 \LWR@newautoidanchor%
32 \booltrue{LWR@indisplaymathimage}%
33 \begin{lateximage}[-breqn dseries- \MathImageAltText]
34 }
35
36 \AfterEndEnvironment{dseries}{
37 \end{lateximage}\end{BlockClass}
38 }
39
40 \BeforeBeginEnvironment{dseries*}{
41 \begin{BlockClass}{displaymath}
42 \LWR@newautoidanchor%
43 \booltrue{LWR@indisplaymathimage}%
44 \begin{lateximage}[-breqn dseries*- \MathImageAltText]
45 }
46
47 \AfterEndEnvironment{dseries*}{
48 \end{lateximage}\end{BlockClass}
49 }

```

```

50
51 \BeforeBeginEnvironment{dgroup}{
52 \begin{BlockClass}{displaymath}
53 \LWR@newautoidanchor%
54 \booltrue{LWR@indisplaymathimage}%
55 \begin{lateximage}[-breqn dgroup- \MathImageAltText]
56 }
57
58 \AfterEndEnvironment{dgroup}{
59 \end{lateximage}\end{BlockClass}
60 }
61
62 \BeforeBeginEnvironment{dgroup*}{
63 \begin{BlockClass}{displaymath}
64 \LWR@newautoidanchor%
65 \booltrue{LWR@indisplaymathimage}%
66 \begin{lateximage}[-breqn dgroup* - \MathImageAltText]
67 }
68
69 \AfterEndEnvironment{dgroup*}{
70 \end{lateximage}\end{BlockClass}
71 }

```

---

File 61 **lwarp-bsheaders.sty**

§ 167 Package **bsheaders**

Pkg bsheaders bsheaders is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{bsheaders}[1997/10/06]

---

File 62 **lwarp-bussproofs.sty**

§ 168 Package **bussproofs**

*(Emulates or patches code by SAMUEL R. BUSS.)*

Pkg bussproofs bussproofs is used as-is for HTML, and emulated by MATHJAX's extension.

 **\DisplayProof** If not using MATHJAX, inline proofs with `\DisplayMath` must be placed inside a math expression.

If using MATHJAX, only the prooftree environment may be used, not `\DisplayProof`.

**for HTML output:** 1 \LWR@ProvidesPackagePass{bussproofs}% no date in file

```

2 \ifbool{mathjax}{
3 \CustomizeMathJax{\require{bussproofs}}
4
5 \NewEnviron{LWR@HTML@prooftree}%

```

```

6 {\LWR@doequation{\BODY}{prooftree}}%
7 [\LWR@doendequation{prooftree}]
8 \LWR@formattedenv{prooftree}
9 }{% SVG HTML
10 \BeforeBeginEnvironment{prooftree}{%
11 \begin{lateximage}[-bussproofs-~\PackageDiagramAltText]%
12 }
13 \AfterEndEnvironment{prooftree}{\end{lateximage}}
14 }

```

---

File 63 **lwarp-bxpapersize.sty**

§ 169 Package **bxpapersize**

Pkg `bxpapersize` `bxpapersize` is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{bxpapersize}[2017/10/08]

2 \providecommand*\papersizesetup{\bxpapersizesetup}
3 \newcommand*\bxpapersizesetup[1]{}

```

---

File 64 **lwarp-bytefield.sty**

§ 170 Package **bytefield**

*(Emulates or patches code by SCOTT PAKIN.)*

Pkg `bytefield` `bytefield` is patched for use by `lwarp`.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{bytefield}[2017/09/15]

2 \BeforeBeginEnvironment{bytefield}{%
3 \begin{lateximage}[-bytefield-~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{bytefield}{\end{lateximage}}

```

---

File 65 **lwarp-cancel.sty**

§ 171 Package **cancel**

Pkg `cancel` `cancel` is used as-is for SVG math, and emulated for HTML text output.

**for HTML output:**

```

1 \LWR@origRequirePackage{lwarp-xcolor}% for \convertcolorspec
2 \LWR@ProvidesPackagePass{cancel}[2013/04/12]

```

`\cancelto` is math-only, so is used as-is.

```

3 \LetLtxMacro\LWR@origcancel\cancel
4 \LetLtxMacro\LWR@origbcancel\bcancel
5 \LetLtxMacro\LWR@origxcancel\xcancel
6
7 \appto\LWR@restoreorigformatting{%
8 \LetLtxMacro\cancel\LWR@origcancel%
9 \LetLtxMacro\bcancel\LWR@origbcancel%
10 \LetLtxMacro\xcancel\LWR@origxcancel%
11 }

```

`\LWR@cancelcolor`     $\langle text \rangle$   $\langle color \rangle$   $\langle class \rangle$   $\langle colorstyle \rangle$   $\langle FormatWPstyle \rangle$

Add colors if not empty:

```

12 \newcommand{\LWR@cancelcolor}[5]{%
13 \ifcempty{#2}%
14 {\InlineClass{#5}{#3}{#1}}%
15 {\LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}%
16 }

```

`\cancel`     $\langle text \rangle$

```

17 \DeclareRobustCommand{\cancel}[1]{%
18 \begingroup%
19 \CancelColor%
20 \LWR@findcurrenttextcolor%
21 \color{black}%
22 \LWR@cancelcolor{#1}{\LWR@tempcolor}{sout}{text-decoration-color}%
23 {text-decoration:line-through}%
24 \endgroup%
25 }
26
27 \LetLtxMacro\bcancel\cancel
28 \LetLtxMacro\xcancel\cancel

```

For MATHJAX:

```

29 \begin{warpMathJax}
30 \PackageWarningNoLine[lwarp, cancel]{The MathJax v3 extension will be used}
31 \CustomizeMathJax{\require{cancel}}
32 \end{warpMathJax}

```

File 66    **lwarp-canonicalayout.sty**

§ 172    Package    **canonicalayout**

Pkg    canonicalayout    canonicalayout is ignored.

**for HTML output:**    s1 \LWR@ProvidesPackageDrop{canonicalayout}[2011/11/05]

```
2 \newcommand*{\currentfontletters}{}
3 \newcommand*{\charactersperpage}{}
```

---

File 67 **lwarp-caption.sty**

§ 173 Package **caption**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg caption caption is patched for use by lwarp.

**for HTML output:**

```
1 \typeout{---}
2 \typeout{Packages lwarp and caption:}
3 \typeout{If a ‘Missing \protect\begin\protect{document\protect}’ error occurs here,}
4 \typeout{try using: \space \protect\usepackage\protect{caption\protect}\space%
5 \protect\captionsetup{options}}
6 \typeout{instead of: \protect\usepackage[options]\protect{caption\protect}.}
7 \typeout{---}
8
9 \LWR@ProvidesPackagePass{caption}[2020/10/26]

10 \long\def\caption@iibox@#1#2#3#4{%
11 % \setbox\@tempboxa\hbox{#4}%
12 \caption@iiibox{#1}{#2}{#3}%
13 % [\wd\@tempboxa]%
14 []% lwarp
15 [\captionbox@hj@default]%
16 % {\unhbox\@tempboxa}%
17 {#4}% lwarp
18 }

19 \long\def\caption@iiibox#1#2#3#4#5[#6][#7]#8{%
20 \begingroup
21 #1*% set \caption@position
22 \caption@iftop{%
23 \endgroup

24 \minipagefullwidth% lwarp
25 \parbox[t]{\linewidth}{%
26 #1\relax
27 \caption@setposition t%
28 % #2%
29 {\caption#4{#5}}%
30 % \captionbox@hrule
31 % \csname caption@hj@#7\endcsname
32 #8%
33 }%
34 }{%
35 \endgroup

36 % \parbox[b]{#6}{%
37 \minipagefullwidth% lwarp
```

```

38 \parbox[b]{\linewidth}{% lwarp
39 #1\relax
40 \caption@setposition b%
41 % \csname caption@hj@#7\endcsname
42 #8%
43 % \captionbox@hrule
44 % #3
45 {\caption#4{#5}}%
46 }%
47 }%
48 }

```

\caption@makecaption

```

49 \long\def\caption@makecaption#1#2{%
50 % \caption@make@above
51 % \caption@make{#1}{#2}%
52 % \caption@make@below
53 }
54
55 \AtBeginDocument{
56 \let\@makecaption\caption@makecaption
57 }

```

Appended to look ahead to the next token for \centering, etc:

```

58 \AtBeginDocument{
59 \xapptocmd{\@xfloat}
60 {\LWR@futurenonspacel\@LWR@mynexttoken\LWR@floatalignment}
61 {}
62 {\LWR@patcherror{caption}{@xfloat}}
63
64 \xapptocmd{\@xdblfloat}
65 {\LWR@futurenonspacel\@LWR@mynexttoken\LWR@floatalignment}
66 {}
67 {\LWR@patcherror{caption}{@xdblfloat}}
68 }

```

Updates for late patches for scrextend:

```

69 \caption@AtBeginDocument{
70 \ifpackageloaded{lwarp-scrextend}{
71 \LetLtxMacro\captionbelow\caption
72 \LetLtxMacro\captionabove\caption
73 \LetLtxMacro\captionofbelow\captionof
74 \LetLtxMacro\captionofabove\captionof
75 }{}
76 }

```

File 68 **lwarp-caption3.sty**

§ 174 Package **caption3**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg caption3 **caption3** is patched for use by **lwarp**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{caption3}[2020/10/21]

```

\caption@@@make {\caption label} {\caption text}

2 \ifpackagelater{caption3}{2020/08/23}{
3 \renewcommand\caption@@@make[2]{%
4 \LWR@traceinfo{caption@@@make}%

5 \LWR@stoppars% lwarp

6 % \sbox\@tempboxa{#1}%
7 % \ifdim\wd\@tempboxa=\z@
8 % \caption@set{labelseparator}{none}%
9 % \fi
10 \caption@ifempty{#2}{%
11 \caption@set{labelseparator}{none}%
12 \caption@set{textformat}{simple}%
13 }%
14 \caption@labelseparator % defines \caption@iflabelfont,
15 % \caption@labelsep and \caption@labelsep@name
16 % (the latter is needed by \caption@fmt)
17 %

18 % \setpar{\@@par\caption@@par}\caption@@par
19 \caption@applyfont

\caption@fmt with plain format is defined as {#1#2#3\par}:

20 % \caption@fmt
21 % {\ifcaption@star\else
22 % \begingroup
23 % \captionlabelfont

24 % \LWR@isolate{#1}% lwarp
25 % \endgroup
26 % \fi}%
27 % {\ifcaption@star\else
28 % \begingroup
29 % \caption@iflabelfont\captionlabelfont
30 % \relax\caption@labelsep
31 % \endgroup
32 % \fi}%
33 % {{\captiontextfont

```

```

34 \let\\newline% lwarp
35 %
36 \caption@textstart

37 % \caption@ifstrut
38 % {\vrule\@height\ht\strutbox\@width\z}%
39 % {}%
40 % \nobreak\hskip\z@skip % enable hyphenation

41 \LWR@isolate{\caption@textformat{#2}}% lwarp

42 % \caption@ifstrut
43 % {\ifhmode\@finalstrut\strutbox\fi}%
44 % {}%
45 \caption@textend}}%

46 \LWR@startpars% lwarp
47 \LWR@traceinfo{caption@@@make done}%
48 }
49]% later than 2020/08/23
50 {% earlier than 2020/08/23
51 \renewcommand\caption@@@make[2]{%
52 \LWR@traceinfo{caption@@@make}%
53 \LWR@stoppars% lwarp
54 % \sbox\@tempboxa{#1}%
55 % \ifdim\wd\@tempboxa=\z@
56 % \let\caption@lsep\relax
57 % \fi
58 \caption@ifempty{#2}{%
59 \let\caption@lsep\@empty
60 \let\caption@tfmt\@firstofone
61 }%
62 % \setpar{\@@par\caption@@par}\caption@@par
63 \caption@applyfont

\caption@fmt with plain format is defined as {#1#2#3\par}:

64 % \caption@fmt
65 {\ifcaption@star\else
66 \begingroup
67 \caption@labelfont
68 \LWR@isolate{#1}% lwarp
69 \endgroup
70 \fi}%
71 {\ifcaption@star\else
72 \begingroup
73 \caption@iflf\caption@labelfont
74 \relax
75 \caption@lsep
76 \endgroup
77 \fi}%
78 {%
79 \caption@textfont
80 \let\\newline% lwarp
81 % \caption@ifstrut
82 % {\vrule\@height\ht\strutbox\@width\z}%
83 % {}%
84 % \nobreak\hskip\z@skip % enable hyphenation

```

```

85 \LWR@isolate{\caption@tfmt{#2}}% lwarp
86 % \caption@ifstrut
87 % {\ifhmode\@finalstrut\strutbox\fi}%
88 % {}%
89 }%
90 \LWR@startpars% lwarp
91 \LWR@traceinfo{caption@@@make done}%
92 }
93 }% earlier than 2020/08/23

```

```

\caption@@make@ {<>} {<>}

94 \renewcommand{\caption@@make@[2]}{%
95 \caption@stepthecounter%
96 \caption@beginhook%
97 \caption@@@make{#1}{#2}%
98 \caption@endhook%
99 }

100 \DeclareCaptionBox{none}{#2}
101 \DeclareCaptionBox{parbox}{%
102 #2%
103 }

104 \DeclareCaptionBox{colorbox}{%
105 #2%
106 }

```

---

## File 69 **lwarp-cases.sty**

### § 175 Package **cases**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg cases **cases** is patched for use by **lwarp**.

While using **MATHJAX**, **cases** objects are converted to **svg** math images.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{cases}[2002/05/02]

2 \BeforeBeginEnvironment{numcases}{
3 \begin{BlockClass}{displaymathnumbered}
4 \LWR@newautoidanchor%
5 \booltrue{LWR@indisplaymathimage}%
6 \begin{lateximage}[-cases- \MathImageAltText]
7 }
8
9 \AfterEndEnvironment{numcases}{
10 \end{lateximage}\end{BlockClass}
11 }
12
13 \BeforeBeginEnvironment{subnumcases}{

```

```

14 \begin{BlockClass}{displaymathnumbered}
15 \LWR@newautoidanchor%
16 \booltrue{LWR@indisplaymathimage}%
17 \begin{lateximage}[-cases- \MathImageAltText]
18 }
19
20 \AfterEndEnvironment{subnumcases}{
21 \end{lateximage}\end{BlockClass}
22 }

```

---

File 70 **lwarp-centernot.sty**

§ 176 Package **centernot**

*(Emulates or patches code by HEIKO OBERDIEK.)*

Pkg centernot centernot is used as-is for SVG math, and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{centernot}[2016/05/16]

Based on <https://github.com/mathjax/MathJax/issues/2107> with \textstyle removed to work with sub/super scripts.

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
3
4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\centernot}[1]{%
6 \LWRoverlaysymbols{\unicode{x2215}}{#1}
7 }}
8 \end{warpMathJax}

```

---

File 71 **lwarp-changebar.sty**

§ 177 Package **changebar**

Pkg changebar changebar is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{changebar}[2018/03/09]

```

2 \newcommand*{\cbstart}{}
3 \newcommand*{\cbend}{}
4 \newenvironment*{\changebar}{}{}
5 \newcommand*{\cbdelete}{}
6 \newcommand*{\nochnagebars}{}
7 \newcommand*{\cbcolor}[1]{}
8 \newlength{\changebarwidth}
9 \newlength{\deletebarwidth}
10 \newlength{\changebarsep}
11 \newcounter{changebargrey}

```

File 72 **lwarp-changelayout.sty**§ 178 Package **changelayout***(Emulates or patches code by AHMED MUSA.)*

Pkg changelayout changelayout is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{changelayout}[2009/10/07]
2 \renewrobustcmd\cpl@backtodefautls{}
3
4 \renewrobustcmd\cpl@checkifoddpagelayout{%
5 \cpl@oddpagelayoutfalse%
6 }
7
8 \renewrobustcmd\changepagelayout[1]{%
9 \setkeys[KV]{changelayout}{#1}%
10 }
11
12 \renewrobustcmd{\changetextlayout}[1]{\changepagelayout{#1}}
13
14 \renewrobustcmd\adjustpagelayout[1]{%
15 \setkeys[KV@X]{changelayout}{#1}%
16 }
17
18 \renewrobustcmd{\adjusttextlayout}[1]{\adjustpagelayout{#1}}
19
20 \renewrobustcmd\adjusttextwidth[1]{%
21 \setkeys[KV]{changelayout}{#1}%
22 \begin{BlockClass}[color:\LWR@colorstyle{named}{\cpl@textcolor}]{changelayout}
23 \color{\cpl@textcolor}%
24 \cpl@content
25 \end{BlockClass}
26 }

```

File 73 **lwarp-changepage.sty**§ 179 Package **changepage***(Emulates or patches code by PETER WILSON.)*

Pkg changepage changepage is ignored.

**for HTML output:** Discard all options for lwarp-changepage:

```

1 \LWR@ProvidesPackageDrop{changepage}[2009/10/20]

```

```

2 \newif\ifoddpag
3 \DeclareRobustCommand{\checkoddpag}{\oddpagetrue}
4 \DeclareRobustCommand{\changetext}[5]{}
5 \DeclareRobustCommand{\changepag}[9]{}
6
7 \@ifundefined{adjustwidth}{
8 \newenvironment{adjustwidth}[2]{}{}
9 \newenvironment{adjustwidth*}[2]{}{}
10 }{
11 \renewenvironment{adjustwidth}[2]{}{}
12 \renewenvironment{adjustwidth*}[2]{}{}
13 }

14 \DeclareDocumentCommand{\strictpagecheck}{}{}
15 \DeclareDocumentCommand{\easypagecheck}{}{}

```

---

File 74 **lwarp-changes.sty**

§ 180 Package **changes**

*(Emulates or patches code by EKKART KLEINOD.)*

Pkg changes changes is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{changes}[2019/01/26]

\BaseJobname is added to the label in case xr or xr-hyper are used.

```

2 \renewcommand{\ChangesListline}[4]{%
3 \IfSubStr{\Changes@loc@show}{#1}{%
4 \LWR@startpars%
5 #2: #3 \quad
6 \nameref{\BaseJobname-autopage-#4}%
7 \LWR@stoppars%
8 }{}%
9 }
10
11 \renewcommand{\Changes@summaryline}[4]{%
12 \IfSubStr{\Changes@loc@show}{#1}{%
13 \ifthenelse{\not\equal{\Changes@loc@style}{compactsummary} \or #2 > 0}%
14 {%
15 #3:~#2#4%
16 }{}%
17 }{}%
18 }
19
20 \xpatchcmd{\listofchanges}
21 {{\changesauthorname: \changesanonymousname}}
22 {{\LWR@textcurrentcolor{\changesauthorname: \changesanonymousname}}}
23 {}
24 {\LWR@patcherror{changes}{listofchanges A}}
25

```

```

26 \xpatchcmd{\listofchanges}
27 {\changesauthorname: \Changes@InID}
28 {\LWR@textcurrentcolor{\changesauthorname: \Changes@InID}}
29 {}
30 {\LWR@patcherror{changes}{\listofchanges B}}
31
32 \xpatchcmd{\listofchanges}
33 {(\Changes@InName)}
34 {\LWR@textcurrentcolor{(\Changes@InName)}}
35 {}
36 {\LWR@patcherror{changes}{\listofchanges C}}
37
38 \xpatchcmd{\listofchanges}
39 {\parbox{\Changes@summary@width}}
40 {}
41 {}
42 {\LWR@patcherror{changes}{\listofchanges D}}
43
44 \xpatchcmd{\Changes@Markup@comment}
45 {%
46 \ifthenelse{\isAnonymous{#2}}%
47 {\textbf{[\arabic{Changes@commentCount#2}]:} }%
48 {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
49 #1%
50 }
51 {%
52 \LWR@textcurrentcolor{% lwarp
53 \ifthenelse{\isAnonymous{#2}}%
54 {\textbf{[\arabic{Changes@commentCount#2}]:} }%
55 {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
56 #1%
57 }% lwarp
58 }
59 {}
60 {\LWR@patcherror{changes}{\Changes@Markup@comment A}}
61
62 \xpatchcmd{\Changes@Markup@comment}
63 {%
64 \uwave{%
65 \ifthenelse{\isAnonymous{#2}}%
66 {\textbf{[\arabic{Changes@commentCount#2}]:} }%
67 {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
68 #1%
69 }%
70 }
71 {%
72 \LWR@textcurrentcolor{% lwarp
73 \uwave{%
74 \ifthenelse{\isAnonymous{#2}}%
75 {\textbf{[\arabic{Changes@commentCount#2}]:} }%
76 {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
77 #1%
78 }%
79 }% lwarp
80 }

```

```

81 {}
82 {\LWR@patcherror{changes}{\Changes@Markup@comment B}}
83
84 \xpatchcmd{\Changes@output}
85 {\Changes@Markup@author{\Changes@output@author{#2}{left}}}
86 {\LWR@textcurrentcolor{\Changes@Markup@author{\Changes@output@author{#2}{left}}}}
87 {}
88 {\LWR@patcherror{changes}{Changes@output A}}
89
90 \xpatchcmd{\Changes@output}
91 {%
92 \ifthenelse{\equal{#1}{added}}{\Changes@Markup@added{#3}}{}%
93 \ifthenelse{\equal{#1}{deleted}}{\Changes@Markup@deleted{#4}}{}%
94 \ifthenelse{\equal{#1}{replaced}}{}%
95 {\Changes@Markup@added{#3}}\allowbreak\Changes@Markup@deleted{#4}%
96 }{}%
97 \ifthenelse{\equal{#1}{highlight}}{\Changes@Markup@highlight{#3}}{}%
98 }
99 {%
100 \LWR@textcurrentcolor{%
101 \ifthenelse{\equal{#1}{added}}{\Changes@Markup@added{#3}}{}%
102 \ifthenelse{\equal{#1}{deleted}}{\Changes@Markup@deleted{#4}}{}%
103 \ifthenelse{\equal{#1}{replaced}}{}%
104 {\Changes@Markup@added{#3}}\allowbreak\Changes@Markup@deleted{#4}%
105 }{}%
106 \ifthenelse{\equal{#1}{highlight}}{\Changes@Markup@highlight{#3}}{}%
107 }%
108 }
109 {}
110 {\LWR@patcherror{changes}{Changes@output B}}
111
112 \xpatchcmd{\Changes@output}
113 {\Changes@Markup@author{\Changes@output@author{#2}{right}}}
114 {\LWR@textcurrentcolor{\Changes@Markup@author{\Changes@output@author{#2}{right}}}}
115 {}
116 {\LWR@patcherror{changes}{Changes@output C}}

```

---

File 75 **lwarp-chappg.sty**

§ 181 Package **chappg**

*(Emulates or patches code by ROBIN FAIRBAIRNS.)*

Pkg chappg **chappg** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{chappg}[2006/05/09]

2 \renewcommand{\pagenumbering}[2][{}]

3 \providecommand{\chappgsep}{--}

---

File 76 **lwarp-chapterbib.sty**

§ 182 Package **chapterbib**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg chapterbib chapterbib is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{chapterbib}[2010/09/18]

2 \xdef\@savedjobname{\BaseJobname}
3 \let\@currentipfile\@savedjobname
```

---

File 77 **lwarp-chemfig.sty**

§ 183 Package **chemfig**

*(Emulates or patches code by CHRISTIAN TELLECHEA.)*

Pkg chemfig chemfig is patched for use by lwarp.

If using `\polymerdelim` to add delimiters to a `\chemfig`, wrap both inside a single `lateximage`:

```

\begin{lateximage}[-chemfig-~\PackageDiagramAltText]
\chemfig{. . .}
\polymerdelim[. . .]{. . .}
\end{lateximage}
```

The images are not hashed because they depend on external settings which may be changed at any time, and are unlikely to be reused inline anyhow.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{chemfig}[2020/03/05]

2
3 \catcode'_ =11
4
5 \@ifpackagelater{chemfig}{2020/03/05}
6 {
7 \xpretocmd\charge{\begin{lateximage}[-chemfig-~\PackageDiagramAltText]}
8 {}{\LWR@patcherror{chemfig}{charge}}
9 \xpretocmd\Charge{\begin{lateximage}[-chemfig-~\PackageDiagramAltText]}
10 {}{\LWR@patcherror{chemfig}{Charge}}
11 \xapptocmd\charge_c{\end{lateximage}}
12 {}{\LWR@patcherror{chemfig}{charge_c}}
13 }{}
14
15 \@ifpackagelater{chemfig}{2019/04/18}%
```

```

16 {% 2019/04/18 or newer
17
18
19 \LetLtxMacro\LWR@chemfig@origchemfig\chemfig
20
21 \renewcommand*\chemfig[2][]{%
22 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
23 \LWR@chemfig@origchemfig[#1]{#2}%
24 \end{lateximage}%
25 }
26
27 \GlobalLetLtxMacro\LWR@chemfig@origCF_lewisc\CF_lewisc
28 \gdef\CF_lewisc#1,#2_nil{%
29 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
30 \LWR@chemfig@origCF_lewisc#1,#2_nil
31 \end{lateximage}
32 }
33
34 \gpreto{\schemestart}{%
35 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
36 }
37 \gappto{\CF_schemestop}{\end{lateximage}}
38
39 }% 2019/04/18 or newer
40 {% older than 2019/04/18
41
42 \LetLtxMacro\LWR@chemfig@origchemfig\chemfig
43
44 \DeclareDocumentCommand\chemfig{s O{} O{} m}{%
45 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
46 \IfBooleanTF{#1}{%
47 \LWR@chemfig@origchemfig*[#2][#3]{#4}%
48 }{%
49 \LWR@chemfig@origchemfig[#2][#3]{#4}%
50 }
51 \end{lateximage}%
52 }
53
54 \LetLtxMacro\LWR@chemfig@origCF@Lewis@b\CF@Lewis@b
55
56 \def\CF@Lewis@b#1#2{%
57 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
58 \LWR@chemfig@origCF@Lewis@b{#1}{#2}%
59 \end{lateximage}%
60 }
61
62 \preto{\schemestart}{%
63 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
64 }
65 \appto{\CF@schemestop}{\end{lateximage}}
66
67 }% older than 2019/04/18
68
69 \catcode'_ =8%
70

```

```

71
72
73 \LetLtxMacro\LWR@chemfig@origchemleft\chemleft
74
75 \def\chemLeft#1#2\chemright#3{%
76 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
77 \LWR@chemfig@origchemLeft#1#2\chemright#3%
78 \end{lateximage}%
79 }
80
81 \LetLtxMacro\LWR@chemfig@origchemup\chemup
82
83 \def\chemup#1#2\chemdown#3{%
84 \begin{lateximage}[-chemfig-~\PackageDiagramAltText]%
85 \LWR@chemfig@origchemup#1#2\chemdown#3%
86 \end{lateximage}%
87 }

```

---

File 78 **lwarp-chemformula.sty**

§ 184 Package **chemformula**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemformula chemformula is patched for use by lwarp.

The svg images are hashed according to contents and local options. Global options are assumed to be constant document-wide.

 **chemformula with MATHJAX** chemformula works best without MATHJAX. If MATHJAX is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The chemformula package adapts to array, but does not know about MATHJAX, and MATHJAX does not know about chemformula.)

While using MATHJAX, `\displaymathother` may also be used for other forms of display and inline math which contain chemformula expressions.

**for HTML output:** 1 \LWR@ProvidesPackagePass{chemformula}[2019/10/13]

2 \ExplSyntaxOn

`\ch` Enclose in an inline svg image or MathJax. The alt tag is is the contents of the `\ch` expression. The filename is hashed, and also has additional hashing information based on the local options.

```

3 \RenewDocumentCommand \ch { O{}m }
4 { %

```

To work inside align with `\displaymathother`, a simple version must be used to work with chemformula's adaptation to align.

```

5 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp

```

```

6 {
7 \chemformula_ch:nn {#1} {#2}% original
8 }

```

If used as the outer level, must temporarily ensure MATHJAX is disabled:

```

9 {
10 \begingroup%
11 \boolfalse{mathjax}%

```

An inline image is used, adjusted for the baseline:

```

12 \LWR@subsingledollar*{% lwarp
13 \textbackslash{}ch{\LWR@HTMLsanitize{#2}\}% alt text
14 }{%
15 \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}% add'l hashing
16 }%
17 {%
18 \chemformula_ch:nn {#1} {#2}% original
19 }%
20 \endgroup%
21 }
22 }

```

`\chcpd`    Similar to `\ch`.

```

23 \@ifpackagelater{chemformula}{2019/10/13}{
24 \cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
25 {
26 \begingroup%
27 \boolfalse{mathjax}%
28 \LWR@subsingledollar*{% lwarp
29 \textbackslash{}chcpd{\LWR@HTMLsanitize{#2}\}%
30 }{%
31 \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
32 }{% original
33 \group_begin:
34 \tl_if_blank:nF {#2}
35 {
36 \keys_set:nn {chemformula} {#1}
37 __chemformula_save_catcodes:
38 __chemformula_sanitize:Nn
39 \l__chemformula_chemformula_tmpa_tl
40 {#2}
41 __chemformula_input_compound_no_check:NV
42 \l__chemformula_compound_tl
43 \l__chemformula_chemformula_tmpa_tl
44 __chemformula_prepare_output:NV
45 \l__chemformula_compound_tl
46 \l__chemformula_catcodes_tl
47 \chemformula_write:V \l__chemformula_compound_tl
48 }
49 \group_end:
50 }
51 \endgroup
52 }
53 }% later than 2019/10/13

```

```

54 {% earlier than 2019/10/13
55 \cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
56 {
57 \begingroup%
58 \boolfalse{mathjax}%
59 \LWR@subsingledollar*{% lwarp
60 \textbackslash}chcpd{\LWR@HTMLsanitize{#2}\}%
61 }{%
62 \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
63 }{% original
64 \group_begin:
65 \tl_if_blank:nF {#2}
66 {
67 \keys_set:nn {chemformula} {#1}
68 __chemformula_save_catcodes:
69 __chemformula_sanitize:Nn
70 \l__chemformula_chemformula_tmpa_tl
71 {#2}
72 __chemformula_input_compound_no_check:NV
73 \l__chemformula_compound_tl
74 \l__chemformula_chemformula_tmpa_tl
75 __chemformula_prepare_output:N \l__chemformula_compound_tl
76 \chemformula_write:V \l__chemformula_compound_tl
77 }
78 \group_end:
79 }
80 \endgroup
81 }
82 }% earlier than 2019/10/13

```

`\charrow` If standalone, appears in a regular `lateximage`.

```

83 \RenewDocumentCommand \charrow { mO{}O{} }
84 {
85 \begin{lateximage}[-chemformula- charrow]
86 \group_begin:
87 __chemformula_draw_arrow:nnn {#1} {#2} {#3}
88 \group_end:
89 \end{lateximage}
90 }

```

`\chname` If standalone, appears in a regular `lateximage`, hashed according to contents.

```

91 \RenewDocumentCommand \chname { R(){}R(){} }
92 {
93 \begin{lateximage}*[%
94 \textbackslash}chname(\LWR@HTMLsanitize{#1})(\LWR@HTMLsanitize{#2})
95]*%
96 \chemformula_chwritebelow:nn {#1} {#2}
97 \end{lateximage}
98 }

```

`\chlewis` Placed inline, hashed according to contents and options.

```

99 \RenewDocumentCommand \chlewis { O{}mm }

```

```

100 {
101 \begingroup%
102 \boolfalse{mathjax}%
103 \LWR@subsingledollar*{\textbackslash}chlewis\{#2\}\{#3\}%
104 {
105 \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
106 }{
107 \chemformula_lewis:nnn {#1} {#2} {#3}
108 }
109 \endgroup%
110 }

```

**lwarp** redefines the \$ character, so special handling is required to escape math expressions inside `\ch`.

This boolean tracks a new kind of escaped math:

```
111 \bool_new:N \l__chemformula_first_last_LWRdollar_bool
```

`\chemformula_input_escape_math`

Adds additional escaping for the new dollar definition:

```

112 \cs_gset_protected:Npn \l__chemformula_input_escape_math:n #1
113 {
114 \l__chemformula_first_last_math:n {#1}
115 \bool_if:NT \l__chemformula_first_last_dollar_bool
116 {
117 \bool_set_true:N \l__chemformula_first_last_math_bool
118 __chemformula_read_escape_dollar:w #1 \q_nil
119 }
120 \bool_if:NT \l__chemformula_first_last_mathbraces_bool
121 {
122 \bool_set_true:N \l__chemformula_first_last_math_bool
123 __chemformula_read_escape_mathbraces:w #1 \q_nil
124 }

```

Added by **lwarp**:

```

125 \bool_if:NT \l__chemformula_first_last_LWRdollar_bool% lwarp
126 {
127 \bool_set_true:N \l__chemformula_first_last_math_bool% lwarp
128 __chemformula_read_escape_LWRdollar:w #1 \q_nil% lwarp
129 }
130 }

```

`\chemformula_read_escape_LWRdollar`

The following parses the contents inside the new dollars.

**lwarp** keeps the dollar as its original math shift until the document starts. While **chemmacros** is being patched, the dollar must temporarily be set to its new meaning during the following definition.

```
131 \begingroup
```

```

132 \catcode'\$=\active
133
134 \cs_new_protected:Npn __chemformula_read_escape_LWRdollar:w $#1$ \q_nil
135 {
136 __chemformula_read_escape_math:n {#1}
137 }
138
139 \endgroup

```

#### \chemformula\_bool\_set\_if\_first\_last

The following looks at the first and last tokens for delimiters to escape math inside \ch. The original definition is modified to look for the control sequences which are used by the new meaning of \$.

```

140 \cs_new_protected:Npn __chemformula_bool_cs_set_if_first_last:NnNN #1#2#3#4
141 {
142 \int_zero:N \l__chemformula_tmpa_int
143 \int_zero:N \l__chemformula_tmpb_int
144 \int_set:Nn \l__chemformula_tmpa_int { \tl_count:n {#2} }
145 \tl_map_inline:nn {#2}
146 {
147 \int_incr:N \l__chemformula_tmpb_int
148 \int_compare:nT { \l__chemformula_tmpb_int = 1 }
149 {

```

At the start, the cs\_ version compares control sequences:

```

150 \ifdefstrequal{##1}{#3}% lwarp
151 {
152 \bool_set_true:N #1
153 }% lwarp
154 {}
155 }

```

At the end, compare more control sequences:

```

156 \int_compare:nT { \l__chemformula_tmpb_int = \l__chemformula_tmpa_int }
157 {
158 \ifdefstrequal{##1}{#4}
159 {}
160 {
161 \bool_set_false:N #1
162 }
163 }
164 }
165 }

```

#### \chemformula\_first\_last\_math

Modified to check for the new meaning of \$ at first/last:

```

166 \cs_gset_protected:Npn __chemformula_first_last_math:n #1
167 {
168 \bool_set_false:N \l__chemformula_first_last_math_bool
169 \bool_set_false:N \l__chemformula_first_last_dollar_bool

```

```

170 \bool_set_false:N \l__chemformula_first_last_LWRdollar_bool% lwarp
171 \bool_set_false:N \l__chemformula_first_last_mathbraces_bool
172 __chemformula_bool_set_if_first_last:Nnnn
173 \l__chemformula_first_last_dollar_bool
174 {#1}
175 { $ } { $ }
176 \bool_if:NF \l__chemformula_first_last_dollar_bool
177 {
178 __chemformula_bool_set_if_first_last:Nnnn
179 \l__chemformula_first_last_mathbraces_bool
180 {#1}
181 { \ (} { \) }

```

Added by lwarp:

```

182 \bool_if:NF \l__chemformula_first_last_mathbraces_bool% lwarp
183 {
184 __chemformula_bool_cs_set_if_first_last:NnNN
185 \l__chemformula_first_last_LWRdollar_bool
186 {#1}
187 { \LWR@newsingledollar } { \LWR@newsingledollar }
188]% lwarp
189 }
190 }

```

```
191 \ExplSyntaxOff
```

---

## File 79 **lwarp-chemgreek.sty**

### § 185 Package **chemgreek**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemgreek chemgreek is patched for use by lwarp.

 **Greek symbols package selection** To use text-mode symbols, use packages `textalpha` or `textgreek`. Using the other packages supported by `chemgreek` will result in math-mode greek characters, which will result in SVG images being used. These images will be hashed.

 **X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X, Lua<sup>A</sup>T<sub>E</sub>X** If using X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X or Lua<sup>A</sup>T<sub>E</sub>X, select the fontspec mapping:

```
\selectchemgreekmapping{fontspec}
```

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{chemgreek}[2020/01/16]
2 \ExplSyntaxOn
3
4 \cs_gset_protected:Npn \chemgreek_text:n #1
5 { { \text {#1} } }
6
7 \appto\LWR@restoreorigformatting{%
8 \cs_set_protected:Npn \chemgreek_text:n #1%
9 { \ensuremath { \text {#1} } }%

```

```
10 }
11
12 \ExplSyntaxOff
```

---

File 80 **lwarp-chemmacros.sty**

§ 186 Package **chemmacros**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemmacros chemmacros is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{chemmacros}[2017/08/28]

SVG file hashing assumes that the relevant options are constant for the entire document.

§ 186.1 **Changes to the user's document**

 **\makepolymerdelims** When using `\makepolymerdelims`, enclose the entire expression inside a `polymerdelims` environment, such as (from the `chemmacros` manual):

```
\begin{polymerdelims}
\chemfig{-[@{op,.75}]CH_2-CH(-[6]Cl)-[@{cl,0.25}]}
\makepolymerdelims{5pt}[27pt]{op}{cl}
\end{polymerdelims}
```

 **redox reactions** Redox reactions must be enclosed inside a `redoxreaction` environment. For print output, extra space must be included above and/or below the result, so they are declared as arguments to the environment, instead of being manually entered as per the `chemmacros` manual. For HTML output, the extra space is ignored and a `lateximage` is used instead.

```
\begin{redoxreaction}{7mm}{7mm}
\OX{a,Na} \rightarrow \OX{b,Na}\pch\redox(a,b){oxidation}
\end{redoxreaction}
```

§ 186.2 **Code**

§ 186.3 **Loading modules**

Patching `chemmacros` modules must be done `\AtBeginDocument`, since modules are invoked by the user in the preamble, and each patch is only done if the module is loaded.

```
2 \ExplSyntaxOn
3
4 \newcommand{\ifchemmacrosmoduleloaded}[1]{%
```

```

5 \@ifl@aded{\c__chemmacros_module_extension_tl}{\c__chemmacros_module_prefix_tl.#1}%
6 }
7
8 \ExplSyntaxOff

```

#### § 186.4 New environments

`\makepolymerdelims` and redox reactions must be enclosed in a `lateximage` during HTML output. These environments are provided here in HTML mode, and in the `lwarp` core in print mode, as a high-level semantic syntax which automatically embeds the contents in a `lateximage` with an appropriate `alt` tag.

Env `polymerdelims`

```

9 \DeclareDocumentEnvironment{polymerdelims}{}
10 {\begin{lateximage}[-chemmacros- polymer]}
11 {\end{lateximage}}

```

Env `redoxreaction`     $\langle \textit{space above} \rangle \langle \textit{space below} \rangle$

For HTML output, the above and below space is ignored, and a `lateximage` is used instead. For the print output version, see section 88.

```

12 \DeclareDocumentEnvironment{redoxreaction}{m m}
13 {\begin{lateximage}[-chemmacros- redoxreaction]}
14 {\end{lateximage}}

```

```

15 \ExplSyntaxOn

```

#### § 186.5 Acid-base

```

16 \AtBeginDocument{
17 \@ifchemmacrosmoduleloaded{acid-base}{
18 \PackageInfo{lwarp}{Patching~chemmacros~module~acid-base}
19
20 \cs_gset_protected:Npn \chemmacros_p:n #1
21 {
22 \begingroup
23 \boolfalse{mathjax}
24 \LWR@subsingledollar*{
25 \textbackslash}p{\LWR@HTMLsanitize{#1}\}
26 }{
27 chemmacrosp\protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
28 }{
29 \group_begin:
30 \mbox
31 {
32 \chemmacros_p_style:n {p}
33 \ensuremath {#1}
34 }
35 \group_end:
36 }
37 \endgroup
38 }

```

```

39
40 \RenewDocumentCommand \pH {} {
41 \begingroup
42 \boolfalse{mathjax}
43 \LWR@subsingledollar*{\textbackslash}pH}{chemmacros}{
44 \chemmacros_p:n { \chemmacros_chemformula:n {H} }
45 }
46 \endgroup
47 }
48
49 \RenewDocumentCommand \pOH {} {
50 \begingroup
51 \boolfalse{mathjax}
52 \LWR@subsingledollar*{\textbackslash}pOH}{chemmacros}{
53 \chemmacros_p:n { \chemmacros_chemformula:n {OH} }
54 }
55 \endgroup
56 }
57
58 \RenewDocumentCommand \pKa {0{}}
59 {
60 \begingroup
61 \boolfalse{mathjax}
62 \LWR@subsingledollar*{\textbackslash}pKa{[]#1{}}{chemmacros #1}{
63 \chemmacros_p:n
64 {
65 \Ka \ifblank {#1} {}
66 { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
67 }
68 }
69 \endgroup
70 }
71
72 \RenewDocumentCommand \pKb {0{}}
73 {
74 \begingroup
75 \boolfalse{mathjax}
76 \LWR@subsingledollar*{\textbackslash}pKb{[]#1{}}{chemmacros #1}{
77 \chemmacros_p:n
78 {
79 \Kb \ifblank {#1} {}
80 { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
81 }
82 }
83 \endgroup
84 }
85
86 \LetLtxMacro\LWR@chemmacros@origKa\Ka
87 \renewcommand*{\Ka}{%
88 \begingroup
89 \boolfalse{mathjax}
90 \LWR@subsingledollar*{\textbackslash}Ka}{chemmacros}{%
91 \LWR@chemmacros@origKa%
92 }%
93 \endgroup

```

```

94 }
95
96 \LetLtxMacro\LWR@chemmacros@origKb\Kb
97 \renewcommand*\Kb{%
98 \begingroup
99 \boolfalse{mathjax}
100 \LWR@subsingledollar*\textbackslash{Kb}{chemmacros}{%
101 \LWR@chemmacros@origKb%
102 }%
103 \endgroup
104 }
105
106 \LetLtxMacro\LWR@chemmacros@origKw\Kw
107 \renewcommand*\Kw{%
108 \begingroup
109 \boolfalse{mathjax}
110 \LWR@subsingledollar*\textbackslash{Kw}{chemmacros}{
111 \LWR@chemmacros@origKw
112 }
113 \endgroup
114 }
115
116 }{}% \ifchemmacrosmoduleloaded
117 }% AtBeginDocument

```

## § 186.6 Charges

```

118 \AtBeginDocument{
119 \ifchemmacrosmoduleloaded{charges}{
120 \PackageInfo{lwarp}{Patching~chemmacros~module~charges}
121
122 \cs_gset_protected:Npn \fplus {
123 \begingroup
124 \boolfalse{mathjax}
125 \LWR@subsingledollar*\textbackslash{fplus}{chemmacros}
126 { \LWR@origensuredmath{\chemformula_fplus:} }
127 \endgroup
128 }
129 \cs_gset_protected:Npn \fminus {
130 \begingroup
131 \boolfalse{mathjax}
132 \LWR@subsingledollar*\textbackslash{fminus}{chemmacros}
133 { \LWR@origensuredmath{\chemformula_fminus:} }
134 \endgroup
135 }
136
137 }{}% \ifchemmacrosmoduleloaded
138 }% AtBeginDocument

```

## § 186.7 Nomenclature

```

139 \AtBeginDocument{
140 \ifchemmacrosmoduleloaded{nomenclature}{
141 \PackageInfo{lwarp}{Patching~chemmacros~module~nomenclature}
142

```

```

143 \cs_gset_protected:Npn \chemmacros_charge:n #1
144 {
145 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}
146 {\chemmacros_chemformula:n { }^{#1} }}
147 {
148 \ifmmode
149 {\chemmacros_chemformula:n { }^{#1} }}
150 \else
151 { \textsuperscript{\ensuremath{#1}} }
152 \fi
153 }
154 }
155
156
157 \LetLtxMacro\LWR@chemmacros@origchemprime\chemprime
158
159 \protected\def\chemprime { \HTMLUnicode{2032} }
160
161 \appto\LWR@restoreorigformatting{%
162 \LetLtxMacro\chemprime\LWR@chemmacros@origchemprime%
163 }

164 \ChemCompatibilityFrom{5.8}
165 \cs_gset_protected:Npn __chemmacros_cip:n #1
166 {
167 \tl_set:Nn \l__chemmacros_tmpa_tl {#1}
168 \int_step_inline:nnnn {0} {1} {9}
169 {
170 \tl_replace_all:Nnn \l__chemmacros_tmpa_tl
171 {##1}
172 { { \l__chemmacros_cip_number_tl ##1} }
173 }
174 {
175 \l__chemmacros_cip_inner_tl
176 \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
177 \l__chemmacros_tmpa_tl
178 }}% lwarp
179 }
180 }
181 \EndChemCompatibility

182 \RenewDocumentCommand \Sconf { O{S} } {
183 \begin{lateximage}[\textbackslash{}Sconf{[]#1{}}]*
184 \chemmacros_sconf:n {#1}
185 \end{lateximage}
186 }
187
188 \RenewDocumentCommand \Rconf { O{R} } {
189 \begin{lateximage}[\textbackslash{}Rconf{[]#1{}}]*
190 \chemmacros_rconf:n {#1}
191 \end{lateximage}
192 }

193 \cs_gset_protected:Npn \chemmacros_hapto:n #1
194 {
195 \begingroup

```

```

196 \boolfalse{mathjax}
197 \LWR@subsingledollar*{\textbackslash{}}hpto\{#1\}\}{chemmacros}{
198 \chemmacros_coordination_symbol:nnnn
199 { \l__chemmacros_coord_use_hyphen_bool }
200 {
201 \chemmacros_if_compatibility:nnTF {>} {5.7}
202 { \c_true_bool }
203 { \c_false_bool }
204 }
205 { \chemeta }
206 {#1}
207 }
208 \endgroup
209 }
210
211 \cs_gset_protected:Npn \chemmacros_dento:n #1
212 {
213 \begingroup
214 \boolfalse{mathjax}
215 \LWR@subsingledollar*{\textbackslash{}}dento\{#1\}\}{chemmacros}{
216 \chemmacros_coordination_symbol:nnnn
217 { \l__chemmacros_coord_use_hyphen_bool }
218 {
219 \chemmacros_if_compatibility:nnTF {>} {5.7}
220 { \c_true_bool }
221 { \c_false_bool }
222 }
223 { \chemkappa }
224 {#1}
225 }
226 \endgroup
227 }
228
229 \cs_gset_protected:Npn \chemmacros_bridge:n #1
230 {
231 \begingroup
232 \boolfalse{mathjax}
233 \LWR@subsingledollar*{\textbackslash{}}bridge\{#1\}\}{chemmacros}{
234 \chemmacros_coordination_symbol:nnnn
235 { \l__chemmacros_coord_use_hyphen_bool }
236 { \l__chemmacros_bridge_super_bool }
237 { \chemmu }
238 {#1}
239 }
240 \endgroup
241 }
242 }{}% \@ifchemmacrosmoduleloaded
243 }% AtBeginDocument

```

## § 186.8 Particles

```

244 \AtBeginDocument{
245 \@ifchemmacrosmoduleloaded{particles}{
246 \PackageInfo{lwarp}{Patching~chemmacros~module~particles}
247 }
248 \cs_gset_protected:Npn \chemmacros_declare_nucleophile:Nn #1#2

```

```

249 {
250 \cs_set_protected:cpn {__chemmacros_ \chemmacros_remove_backslash:N #1;}
251 {
252 \bool_if:NTF \l__chemmacros_nucleophile_elpair_bool
253 {
254 \chemmacros_elpair:n { #2 }
255 \chemmacros_if_compatibility:nnT {>=} {5.3}
256 { \skip_horizontal:N \l__chemmacros_nucleophile_dim }
257 \chemmacros_chemformula:n { {}^{ - } }
258 }
259 { \chemmacros_chemformula:n { #2^{ - } } }
260 }
261 \DeclareDocumentCommand #1 {o}
262 {%
263 \begin{lateximage}%
264 \group_begin:%
265 \IfNoValueF {##1}%
266 { \chemmacros_set_keys:nn {particles} {##1} }%
267 \use:c {__chemmacros_ \chemmacros_remove_backslash:N #1;}%
268 \group_end:%
269 \end{lateximage}%
270 }
271 }
272
273 \RenewChemNucleophile \Nuc {Nu}
274 \RenewChemNucleophile \ba {ba}
275
276 }{}% \@ifchemmacrosmoduleloaded
277 }% AtBeginDocument

```

## § 186.9 Phases

```

278 \AtBeginDocument{
279 \@ifchemmacrosmoduleloaded{phases}{
280 \PackageInfo{lwarp}{Patching~chemmacros~module~phases}
281
282 \cs_undefine:N \chemmacros_phase:n
283 \cs_new_protected:Npn \chemmacros_phase:n #1
284 {
285 \mode_leave_vertical:
286
287 \bool_if:NTF \l__chemmacros_phases_sub_bool
288 {
289 \ifnumequal{\value{LWR@lateximagedepth}}{0}
290 {
291 \textsubscript{ (#1) }
292 }
293 {
294 \chemformula_subscript:n { (#1) }
295 }
296 }
297 {
298 \skip_horizontal:N \l__chemmacros_phases_space_dim
299 \chemmacros_text:n { (#1) }

```

```

299 }
300 }
301
302 }{}% \@ifchemmacrosmoduleloaded
303 }% AtBeginDocument

```

## § 186.10 Mechanisms

```

304 \AtBeginDocument{
305 \@ifchemmacrosmoduleloaded{mechanisms}{
306 \PackageInfo{lwarp}{Patching~chemmacros~module~mechanisms}
307
308 \chemmacros_define_keys:nn {textmechanisms}
309 {
310 type .choice: ,
311 type / .code:n =
312 {
313 __chemmacros_set_mechanisms:nnn { S }
314 {
315 \textsubscript{N}
316 }
317 { }
318 } ,
319 type / 1 .code:n =
320 {
321 __chemmacros_set_mechanisms:nnn { S }
322 {
323 \textsubscript{N}
324 1
325 }
326 { }
327 } ,
328 type / 2 .code:n =
329 {
330 __chemmacros_set_mechanisms:nnn { S }
331 {
332 \textsubscript{N}
333 2
334 }
335 { }
336 } ,
337 type / se .code:n =
338 {
339 __chemmacros_set_mechanisms:nnn { S }
340 {
341 \textsubscript{E}
342 }
343 { }
344 } ,
345 type / 1e .code:n =
346 {
347 __chemmacros_set_mechanisms:nnn { S }
348 {
349 \textsubscript{E}
350 1
351 }

```

```

352 { }
353 } ,
354 type / 2e .code:n =
355 {
356 __chemmacros_set_mechanisms:nnn { S }
357 {
358 \textsubscript{E}
359 2
360 }
361 { }
362 } ,
363 type / ar .code:n =
364 {
365 __chemmacros_set_mechanisms:nnn { S }
366 {
367 \textsubscript{E}
368 }
369 { Ar - }
370 } ,
371 type / e .code:n =
372 { __chemmacros_set_mechanisms:nnn { E } { } { } } ,
373 type / e1 .code:n =
374 { __chemmacros_set_mechanisms:nnn { E } { 1 } { } } ,
375 type / e2 .code:n =
376 { __chemmacros_set_mechanisms:nnn { E } { 2 } { } } ,
377 type / cb .code:n =
378 {
379 __chemmacros_set_mechanisms:nnn { E }
380 {
381 1
382 \textsubscript{cb}
383 }
384 { }
385 } ,
386 type .default:n =
387 }
388
389 \cs_gset_protected:Npn \chemmacros_mechanisms:n #1
390 {
391 \tl_if_blank:nTF {#1}
392 { \chemmacros_set_keys:nn {textmechanisms} { type } }
393 { \chemmacros_set_keys:nn {textmechanisms} { type = #1 } }
394 \mbox
395 {
396 \tl_use:N \l__chemmacros_mechanisms_ar_tl
397 \tl_use:N \l__chemmacros_mechanisms_type_tl
398 \tl_use:N \l__chemmacros_mechanisms_mol_tl
399 }
400 }
401
402 \appto\LWR@restoreorigformatting%
403 \cs_set_protected:Npn \chemmacros_mechanisms:n #1%
404 {%
405 \tl_if_blank:nTF {#1}%
406 { \chemmacros_set_keys:nn {mechanisms} { type } }%

```

```

407 { \chemmacros_set_keys:nn {mechanisms} { type = #1 } }%
408 \mbox%
409 {%
410 \tl_use:N \l__chemmacros_mechanisms_ar_tl%
411 \tl_use:N \l__chemmacros_mechanisms_type_tl%
412 \tl_use:N \l__chemmacros_mechanisms_mol_tl%
413 }%
414 }%
415 }
416
417 }{}% \@ifchemmacrosmoduleloaded
418 }% AtBeginDocument

```

### § 186.11 Newman

```

419 \AtBeginDocument{
420 \@ifchemmacrosmoduleloaded{newman}{
421 \PackageInfo{lwarp}{Patching~chemmacros~module~newman}
422
423 \RenewDocumentCommand \newman {od()}m%
424 {
425 \IfValueTF{#2}
426 {\begin{lateximage}[\textbackslash}newman(#2)\{#3\}*}
427 {\begin{lateximage}[\textbackslash}newman\{#3\}*}
428 \group_begin:
429 \IfNoValueF {#1} { \chemmacros_set_keys:nn {newman} {#1} }
430 \IfNoValueTF {#2}
431 { \chemmacros_newman:nn { } {#3} }
432 { \chemmacros_newman:nn {#2} {#3} }
433 \group_end:
434 \end{lateximage}
435 }%
436
437 }{}% \@ifchemmacrosmoduleloaded
438 }% AtBeginDocument

```

### § 186.12 Orbital

```

439 \AtBeginDocument{
440 \@ifchemmacrosmoduleloaded{orbital}{
441 \PackageInfo{lwarp}{Patching~chemmacros~module~orbital}
442
443 \RenewDocumentCommand \orbital {om}
444 {
445 \IfValueTF{#1}
446 {
447 \begin{lateximage}[%
448 \textbackslash}orbital{[]\LWR@HTMLSanitize{#1}[]}\{#2\}%
449]*[[margin-left: 1em ; margin-right: 1em]
450 }
451 {
452 \begin{lateximage}[%
453 \textbackslash}orbital\{#2\}%
454]*[[margin-left: 1em ; margin-right: 1em]
455 }

```

```

456 \group_begin:
457 \chemmacros_set_keys:nn {orbital/type} {#2}
458 \IfNoValueTF {#1}
459 { \chemmacros_orbital:n { } }
460 { \chemmacros_orbital:n {#1} }
461 \group_end:
462 \end{lateximage}
463 }
464
465 }{}% \@ifchemmacrosmoduleloaded
466 }% AtBeginDocument

```

### § 186.13 Reactions

```

\chemmacros_declare_reaction_env <<chem>> <<math>> <<args number>> <<argument list ({#2}{#3...})>>

467 \AtBeginDocument{
468 \@ifchemmacrosmoduleloaded{reactions}{
469 \PackageInfo{lwarp}{Patching~chemmacros~module~reactions}
470 }
471 \cs_gset_protected:Npn \chemmacros_declare_reaction_env:nnnn #1#2#3#4
472 {
473 \exp_args:Nnx \DeclareDocumentEnvironment {#1} { 0{} \prg_replicate:nn {#3+0} {m} }
474 {
475 \boolfalse{mathjax}% lwarp
476 \ifdefvoid{\LWR@ThisAltText}{% lwarp
477 \ThisAltText{-chemmacros~reaction}% lwarp
478 }{}% lwarp
479 \chemmacros_add_reaction_description:n {##1}
480 __chemmacros_begin_reaction:
481 \chemmacros_reaction_read:nnw {#2} {#4}
482 }
483 {
484 __chemmacros_end_reaction:
485 \gdef\LWR@ThisAltText{}% lwarp
486 }
487 }
488 \cs_generate_variant:Nn \chemmacros_declare_reaction_env:nnnn {nnnV}
489
490 \RenewChemReaction {reaction} {equation}
491 \RenewChemReaction {reaction*} {equation*}
492 \RenewChemReaction {reactions} {align}
493 \RenewChemReaction {reactions*} {align*}
494
495 }{}% \@ifchemmacrosmoduleloaded
496 }% AtBeginDocument

```

§ 186.14 **Redox**

```

497 \AtBeginDocument{
498 \@ifchemmacrosmoduleloaded{redox}{
499 \PackageInfo{lwarp}{Patching~chemmacros~module~redox}
500
501 \NewDocumentCommand \LWR@chemmacros@ox { s m >{\SplitArgument{1}{,}}m }
502 {
503 \IfBooleanTF {#1}
504 { \chemmacros_ox:nnnn {#1} {#2} #3 }
505 { \chemmacros_ox:nnnn { } {#2} #3 }
506 }
507
508 \RenewDocumentCommand \ox { s O{ } m }
509 {
510 \begingroup
511 \boolfalse{mathjax}
512 \IfBooleanTF {#1}
513 {
514 \LWR@subsingledollar*{% yes hash
515 \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
516 }{%
517 star \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
518 }{%
519 \LWR@chemmacros@ox* {#2} {#3}% contents
520 }%
521 }
522 {
523 \LWR@subsingledollar*{% yes hash
524 \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
525 }{%
526 \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
527 }{%
528 \LWR@chemmacros@ox {#2} {#3}% contents
529 }%
530 }
531 \endgroup
532 }
533
534 }{}% \@ifchemmacrosmoduleloaded
535 }% AtBeginDocument

```

§ 186.15 **Scheme**

Fix for chemmacros as of v5.8b, when using newfloat and babel:

```

536 \AtBeginDocument{
537 \@ifchemmacrosmoduleloaded{scheme}{
538 \PackageInfo{lwarp}{Patching~chemmacros~module~scheme}
539
540 \ifdefstring{\schemename}{\los}{
541 \SetupFloatingEnvironment{scheme}{
542 name = \chemmacros_translate:n {scheme-name}
543 }
544 }{}

```

```

545
546 }{}% \@ifchemmacrosmoduleloaded
547 }% AtBeginDocument

```

## § 186.16 Spectroscopy

```

548 \AtBeginDocument{
549 \@ifchemmacrosmoduleloaded{spectroscopy}{
550 \PackageInfo{lwarp}{Patching~chemmacros~module~spectroscopy}
551
552 \ChemCompatibilityTo{5.8}
553 \cs_gset_protected:Npn __chemmacros_nmr_base:nn #1#2
554 {
555 \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
556 {
557 \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
558 \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
559 }
560 \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
561 % \chemmacros_chemformula:n { ^{#1} }
562 #1
563 \bool_if:NTF \l__chemmacros_nmr_parse_bool
564 { \chemformula_ch:nV {} } \g__chemmacros_nmr_element_coupled_tl }
565 { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
566 \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
567 \tl_use:N \l__chemmacros_nmr_method_tl
568 }
569 \EndChemCompatibility
570 \ChemCompatibilityFrom{5.8}
571 \cs_gset_protected:Npn __chemmacros_nmr_base:nn #1#2
572 {
573 \group_begin:
574 \tl_use:N \l__chemmacros_nmr_base_format_tl
575 \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
576 {
577 \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
578 \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
579 }
580 \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
581 % \chemmacros_chemformula:n { ^{#1} }
582 #1
583 \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
584 {
585 \bool_if:NTF \l__chemmacros_nmr_parse_bool
586 { \chemformula_ch:nV {} } \g__chemmacros_nmr_element_coupled_tl }
587 { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
588 }
589 \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
590 \tl_use:N \l__chemmacros_nmr_method_tl
591 \group_end:
592 }
593 \EndChemCompatibility
594
595
596 \cs_gset_protected:Npn \chemmacros_nmr_position:n #1

```

```

597 {
598 \chemmacros_chemformula:x
599 {
600 \exp_not:V \g__chemmacros_nmr_element_tl
601 \bool_if:NF \l__chemmacros_nmr_position_side_bool
602 {
603 \tl_if_eq:NnTF \l__chemmacros_nmr_position_tl {^}% lwarp
604 { \textsuperscript{\exp_not:n { {#1} }} }% lwarp
605 { \textsubscript{\exp_not:n { {#1} }} }% lwarp
606 % \exp_not:V \l__chemmacros_nmr_position_tl
607 % \exp_not:n { {#1} }
608 }
609 }
610 \bool_if:NT \l__chemmacros_nmr_position_side_bool
611 {
612 \tl_use:N \l__chemmacros_nmr_position_tl
613 __chemmacros_nmr_position:n {#1}
614 }
615 }
616
617 \cs_gset_protected:Npn __chemmacros_nmr_coupling:w (#1;#2)
618 {
619 \tl_set:Nn \l__chemmacros_nmr_coupling_bonds_tl
620 {
621 \l__chemmacros_nmr_coupling_bonds_pre_tl
622 #1
623 \l__chemmacros_nmr_coupling_bonds_post_tl
624 }
625 \bool_if:NTF \l__chemmacros_nmr_coupling_nuclei_sub_bool
626 {
627 \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
628 {
629 % \c_math_subscript_token
630 \textsubscript% lwarp
631 {
632 \l__chemmacros_nmr_coupling_nuclei_pre_tl
633 \chemmacros_chemformula:n {#2}
634 \l__chemmacros_nmr_coupling_nuclei_post_tl
635 }
636 }
637 }
638 {
639 \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
640 {
641 \l__chemmacros_nmr_coupling_nuclei_pre_tl
642 \chemmacros_chemformula:n {#2}
643 \l__chemmacros_nmr_coupling_nuclei_post_tl
644 }
645 }
646 __chemmacros_nmr_coupling_aux_i:w
647 }
648 \AfterEndPreamble{% After \AtBeginDocument
649 % \NMR{<num>,<elem>}<num>,<unit>}<solvent>] ALL arguments are optional
650 % \NMR* same but without ": δ" at end
651 \cs_gset_protected:Npn \chemmacros_nmr:n nnn #1#2#3#4

```

```

652 {
653 \bool_if:NT \l__chemmacros_nmr_list_bool { \item \scan_stop: }
654 \group_begin:

655 \mode_leave_vertical:

656 \bool_set_false:N \l__chemmacros_nmr_frequency_bool
657 \bool_set_false:N \l__chemmacros_nmr_solvent_bool
658 \tl_if_empty:nF {#3}
659 { \bool_set_true:N \l__chemmacros_nmr_frequency_bool }
660 \tl_if_empty:nF {#4}
661 { \bool_set_true:N \l__chemmacros_nmr_solvent_bool }
662 \bool_if:nT
663 {
664 \l__chemmacros_nmr_frequency_bool
665 ||
666 \l__chemmacros_nmr_solvent_bool
667 }
668 { \bool_set_true:N \l__chemmacros_nmr_delimiters_bool }
669 \bool_if:nT
670 {
671 \l__chemmacros_nmr_frequency_bool
672 &&
673 \l__chemmacros_nmr_solvent_bool
674 }
675 { \bool_set_true:N \l__chemmacros_nmr_comma_bool }
676 \tl_if_empty:nTF {#2}
677 {
678 __chemmacros_nmr_nucleus:VV
679 \l__chemmacros_nmr_isotope_default_tl
680 \l__chemmacros_nmr_element_default_tl
681 }
682 { __chemmacros_nmr_nucleus:w #2 \q_stop }
683 \mode_if_math:TF
684 {
685 \text
686 {
687 \group_begin:
688 \tl_use:N \l__chemmacros_nmr_format_tl
689 \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
690 __chemmacros_nmr_base:VV
691 \g__chemmacros_nmr_isotope_tl
692 \g__chemmacros_nmr_element_tl
693 \bool_if:NT \l__chemmacros_nmr_delimiters_bool
694 { ~ (}
695 \bool_if:NT \l__chemmacros_nmr_frequency_bool
696 { __chemmacros_nmr_frequency:n {#3} }
697 \bool_if:NT \l__chemmacros_nmr_comma_bool
698 { , ~ }
699 \bool_if:NT \l__chemmacros_nmr_solvent_bool
700 { \chemmacros_chemformula:n {#4} }
701 \bool_if:NT \l__chemmacros_nmr_delimiters_bool
702 {) }
703 \tl_if_blank:nT {#1} {::~}
704 }}}% lwarp

```

```

705 \group_end:
706 }
707 \tl_if_blank:nT {#1}
708 {
709 \delta
710 \text { \l__chemmacros_nmr_delta_tl }
711 \bool_if:NT \l__chemmacros_nmr_use_equal_bool {=}
712 }
713 }
714 {
715 \group_begin:
716 \tl_use:N \l__chemmacros_nmr_format_tl
717 \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
718 __chemmacros_nmr_base:VV
719 \g__chemmacros_nmr_isotope_tl
720 \g__chemmacros_nmr_element_tl
721 \bool_if:NT \l__chemmacros_nmr_delimiters_bool
722 {~()}
723 \bool_if:NT \l__chemmacros_nmr_frequency_bool
724 { __chemmacros_nmr_frequency:n {#3} }
725 \bool_if:NT \l__chemmacros_nmr_comma_bool
726 {,~}
727 \bool_if:NT \l__chemmacros_nmr_solvent_bool
728 {
729 \bool_if:NTF \l__chemmacros_nmr_parse_bool

730 % { \chemformula_ch:nn { } {#4} }% original
731 % {\ch{#4}}% lwarp
732 % {#4}
733 % }
734 \bool_if:NT \l__chemmacros_nmr_delimiters_bool
735 {}}
736 }}% lwarp
737 \tl_if_blank:nT {#1} {:}
738 \group_end:
739 \tl_if_blank:nT {#1}
740 {
741 \tl_use:N \c_space_tl
742 \c_math_toggle_token
743 \delta
744 \c_math_toggle_token
745 \l__chemmacros_nmr_delta_tl
746 \bool_if:NT \l__chemmacros_nmr_use_equal_bool {~=}
747 }
748 }
749 \group_end:
750 }
751]% AfterEndPreamble
752
753
754 \RenewDocumentCommand \chemmacros_data:w { smo }
755 {
756 \bool_if:NT \l__chemmacros_nmr_list_bool { \item }
757 {
758 % \tl_use:N \l__chemmacros_nmr_format_tl #2

```

```

759 \tl_use:N \l__chemmacros_nmr_format_tl
760 \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
761 #2
762 \IfNoValueF {#3} { ~ (#3) }
763 \IfBooleanT {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { : } }
764 }% lwarp
765 }
766 \IfBooleanF {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { ~ = } }
767 }
768
769 }{}% \@ifchemmacrosmoduleloaded
770 }% AtBeginDocument

```

### § 186.17 Thermodynamics

```

771 \AtBeginDocument{
772 \@ifchemmacrosmoduleloaded{thermodynamics}{
773 \PackageInfo{lwarp}{Patching~chemmacros~module~thermodynamics}
774
775 \cs_gset_protected:Npn \chemmacros_state:nn #1#2
776 {
777 \group_begin:
778 \boolfalse{mathjax}
779 \chemmacros_set_keys:nn {thermodynamics} {#1}
780 \LWR@subsingledollar*{% yes hashing
781 \textbackslash{}state{\LWR@HTMLsanitize{#2}\}% alt
782 }{%
783 chemmacros_state% add'l hashing
784 #1% options
785 LSP \tl_use:N \l__chemmacros_state_sp_left_tl% super/subscripts
786 LSB \tl_use:N \l__chemmacros_state_sb_left_tl
787 RSP \tl_use:N \l__chemmacros_state_sp_right_tl
788 RSB \tl_use:N \l__chemmacros_state_sb_right_tl
789 }
790 {
791 \LWR@origensuredmath{
792 \chemmacros_text:V \l__chemmacros_state_pre_tl
793 \c_math_superscript_token
794 { \chemmacros_text:V \l__chemmacros_state_sp_left_tl }

```

Only add the subscripts if they are being used. This avoids causing an incorrect depth, as the empty subscript will be measured by TeX but cropped out by *pdfcrop*.

```

795 \tl_if_empty:NTF \l__chemmacros_state_sb_left_tl
796 {}
797 {
798 \c_math_subscript_token
799 { \chemmacros_text:V \l__chemmacros_state_sb_left_tl }
800 }
801 #2
802 \c_math_superscript_token
803 { \chemmacros_text:V \l__chemmacros_state_sp_right_tl }
804 \tl_if_empty:NTF \l__chemmacros_state_sb_right_tl
805 {}
806 {

```

```

807 \c_math_subscript_token
808 { \chemmacros_text:V \l__chemmacros_state_sb_right_tl }
809 }
810 \chemmacros_text:V \l__chemmacros_state_post_tl
811 }
812 }
813 \group_end:
814 }
815 \cs_generate_variant:Nn \chemmacros_state:nn { nV }
816
817 \cs_gset_protected:Npn \chemmacros_declare_state:Nn #1#2
818 {
819 \chemmacros_define_keys:xn
820 {thermodynamics/\chemmacros_remove_backslash:N #1}
821 {
822 pre .meta:nn = {chemmacros/thermodynamics} { pre = ##1 } ,
823 post .meta:nn = {chemmacros/thermodynamics} { post = ##1 } ,
824 superscript-left .meta:nn = {chemmacros/thermodynamics} { superscript-left = ##1 } ,
825 superscript-right .meta:nn = {chemmacros/thermodynamics} { superscript-right = ##1 } ,
826 superscript .meta:n = { superscript-right = ##1 } ,
827 subscript-left .meta:nn = {chemmacros/thermodynamics} { subscript-left = ##1 } ,
828 subscript-right .meta:nn = {chemmacros/thermodynamics} { subscript-right = ##1 } ,
829 subscript .meta:n = { subscript-left = ##1 } ,
830 subscript-pos .choices:nn =
831 { left , right }
832 { \tl_set_eq:NN \l__chemmacros_state_sb_pos_tl \l_keys_choice_tl } ,
833 symbol .tl_set:N = \l__chemmacros_state_symbol_tl ,
834 unit .tl_set:N = \l__chemmacros_state_unit_tl
835 }
836 \DeclareDocumentCommand #1 { sO{}D(){}m }
837 {
838 \group_begin:
839 \chemmacros_set_keys:xn
840 {thermodynamics/\chemmacros_remove_backslash:N #1}
841 {#2}
842 \tl_if_blank:nF {##3}
843 {
844 \chemmacros_set_keys:nx {thermodynamics}
845 { subscript-\l__chemmacros_state_sb_pos_tl = \exp_not:n {##3} }
846 }
847 \chemmacros_state:nV {##2} \l__chemmacros_state_symbol_tl
848 \chemmacros_set_keys_groups:nnn {thermodynamics} {variables} {##2}
849 \IfBooleanF {##1} { = ~ \SI {##4} { \l__chemmacros_state_unit_tl } }
850 \group_end:
851 }
852 }

```

The pre-existing macros are redefined with the new definition:

```

853 \RenewChemState \enthalpy { symbol = H , unit = \kilo\joule\per\mole }
854 \RenewChemState \entropy { symbol = S , unit = \joule\per\kelvin\per\mole , pre = }
855 \RenewChemState \gibbs { symbol = G , unit = \kilo\joule\per\mole }
856
857 }{}% \@ifchemmacrosmoduleloaded
858 }% AtBeginDocument

```

859 \ExplSyntaxOff

File 81 **lwarp-chemnum.sty**

§ 187 Package **chemnum**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg chemnum chemnum is patched for use by lwarp.

for HTML output:

```

1 \LWR@ProvidesPackagePass{chemnum}[2016/04/14]
2 \ExplSyntaxOn
3
4 \cs_gset_protected:Npn \chemnum_compound_write:n #1
5 {
6 \chemnum_get_compound_property:nn {#1} {pre-main-label-code}
7 \group_begin:
8 \bool_if:NTF \l__chemnum_compound_local_bool
9 { \l__chemnum_local_label_format_tl }
10 { \chemnum_get_compound_property:nn {#1} {label-format} }
11 {
12 \LWR@textcurrentfont{
13 \chemnum_get_compound_property:nn {#1} {counter-representation}
14 }
15 }
16 \group_end:
17 \chemnum_get_compound_property:nn {#1} {post-main-label-code}
18 }
19
20 \cs_gset_protected:Npn \chemnum_subcompound_write:nn #1#2
21 {
22 \group_begin:
23 \bool_if:NTF \l__chemnum_compound_local_bool
24 { \l__chemnum_local_label_format_tl }
25 { \chemnum_get_compound_property:nn {#1} {label-format} }
26 {
27 \LWR@textcurrentfont{
28 \chemnum_get_subcompound_property:nnn {#1} {#2}
29 {counter-representation}
30 }
31 }
32 \group_end:
33 }
34
35 \ExplSyntaxOff

```

---

File 82 **lwarp-chkfloat.sty**

§ 188 Package **chkfloat**

Pkg chkfloat chkfloat is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{chkfloat}[2012/08/19]

---

File 83 **lwarp-chngpage.sty**

§ 189 Package **chngpage**

*(Emulates or patches code by PETER WILSON.)*

Pkg chngpage chngpage is ignored.

**for HTML output:** Discard all options for lwarp-chngpage:

```
1 \LWR@ProvidesPackageDrop{chngpage}[2009/10/20]
2 \LWR@origRequirePackage{lwarp-chngpage}
```

---

File 84 **lwarp-cite.sty**

§ 190 Package **cite**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg cite cite is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{cite}[2015/02/27]

For the [super] option, the \kern must be removed:

```
2 \def\LWRCT@biblabel#1{\@citess{#1}\kern-\labelsep\,}
3
4 \ifdefstrequal{\@biblabel}{\LWRCT@biblabel}
5 {
6 \def\@biblabel#1{\@citess{#1}}
7 }{}
```

For the [super] option, \textsuperscript is used instead of math superscript:

```
8 \def\@citess#1{#1}
9
10 \DeclareDocumentCommand\citepunct{}{\, \, \relax}
```

File 85 **lwarp-citeref.sty**§ 191 Package **citeref***(Emulates or patches code by BJÖRN BRIEL.)*

Pkg citeref citeref is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{citeref}[1999/27/05]
2 \def\@cprwrite#1={\write\@auxout{\string\citepageref{#1}\theLWR@currentautosec}}
3
4 \def\citepageref#1#2{%
5 \xdef\cpr@testa{\@nameuse{cpr@last@#1}}%letzte Zitatstelle
6 \xdef\cpr@testb{#2}% Seite dieser Zitatstelle
7 \ifx\cpr@testa\cpr@testb%
8 \relax% Konsekutive identische Seitenangaben weglassen
9 \else%
10 \@namexdef{cpr@last@#1}{#2}%
11 \@ifundefined{cpr@#1}%
12 {\@namexdef{cpr@#1}{\ref{\BaseJobname-autopage-#2}}}% lwarp
13 {\@namexdef{cpr@#1}{\@nameuse{cpr@#1}, \ref{\BaseJobname-autopage-#2}}}% lwarp
14 \fi
15 }
```

File 86 **lwarp-CJK.sty**§ 192 Package **CJK**

Pkg CJK CJK does not work with lwarp unless called from ctex.

**for HTML output:**

```

1 \@ifpackageloaded{xeCJK}{%
2 \LWR@loadnever{CJK}{ctex, xeCJK}
3 }
4
5 \LWR@ProvidesPackagePass{CJK}[2015/04/18]
```

File 87 **lwarp-CJKutf8.sty**§ 193 Package **CJKutf8**

Pkg CJKutf8 CJKutf8 does not work with lwarp unless called from ctex.

**for HTML output:**

```

1 \@ifpackageloaded{xeCJK}{%
2 \LWR@loadnever{CJKutf8}{ctex, xeCJK}
3 }
```

```
4
5 \LWR@ProvidesPackagePass{CJKutf8}[2015/04/18]
```

File 88 **lwarp-cleveref.sty**

§ 194 Package **cleveref**

(Emulates or patches code by TOBY CUBITT.)

Pkg cleveref cleveref is patched for HTML, and limited MATHJAX emulation is added.

⚠ **cleveref page numbers** cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to “for”.

Ex:

```
\cpageref{tab:first,tab:second}
in html becomes:
“pages for table 4.1 and for table 4.2”
```

See `\cpagerefFor` at page 739 to redefine the message which is printed for page number references.

Table 14 on page 504 shows the data structure of the label/reference system as revised by `lwarp` and `cleveref`.

For MATHJAX, each references is printed as an `\eqref`, without `cleveref`'s description text. Page references are also printed as simple `\eqrefs`. Multiple labels in a single `\cref` will print as (???) in MATHJAX.

⚠ **multiple labels**

for HTML output: `1 \LWR@ProvidesPackagePass{cleveref}[2018/03/27]`

The following patches are applied. Print-mode versions are not required since they all come down to `\ref` eventually, and `\ref` has a print-mode version.

```
\@@@setcref {<kindofref>} {<label>}
```

`\@templabel` becomes the section number.

```
2 \def\LWR@orig@@@setcref#1#2{\cref@getlabel{#2}{\@templabel}#1{\@templabel}{}}%
3
4 \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% before v0.21
5 \renewcommand*{\@@@setcref}[2]{#1{\ref{#2}}{}}
6 }{
7 \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% as of v0.21
8 \renewcommand*{\@@@setcref}[2]{%
9 #1{\ref{#2}}{}}
10 }{
11 \PackageWarningNoLine{lwarp-cleveref}{
12 Unknown version of cleveref.
13 \protect\cref\space will fail.
```

```

14 }%
15 }
16 }

```

`\@@@setcrefrange`  $\langle text \rangle$   $\langle label \rangle$   $\langle label \rangle$

```

17 \def\LWR@orig@@@setcrefrange#1#2#3{%
18 \cref@getlabel{#2}{\@labela}%
19 \cref@getlabel{#3}{\@labelb}%
20 #1{\@labela}{\@labelb}{\@labela}{\@labelb}%
21 }
22 \ifdefequal{\@@@setcrefrange}{\LWR@orig@@@setcrefrange}{
23 \renewcommand{\@@@setcrefrange}[3]{%
24 #1{\ref{#2}}{\ref{#3}}{\@labela}{\@labelb}%
25 }
26 }{
27 \ifdefequal{\@@@setcrefrange}{\LWR@orig@@@setcrefrange}{
28 \renewcommand{\@@@setcrefrange}[3]{%
29 #1{\ref{#2}}{\ref{#3}}{\@labela}{\@labelb}%
30 }
31 }{
32 \PackageWarningNoLine{lwarp-cleveref}{
33 Unknown version of cleveref.
34 \protect\crefrange\space will fail.
35 }
36 }
37 }

```

`\cpagerefFor` Redefinable word between “page(s)” and the page numbers.

```

38 \newcommand*{\cpagerefFor}{for}

```

`\@@@setcpageref`  $\langle typeofref \rangle$   $\langle label \rangle$ , where *typeofref* is “page” or “pages”

```

39 \def\LWR@orig@@@setcpageref#1#2{% before v0.21
40 \cref@getpageref{#2}{\@temppage}#1{\@temppage}{\@temppage}%
41 }
42 \def\LWR@orig@@@setcpageref#1#2{% as of v0.21
43 \cpageref@getlabel{#2}{\@temppage}#1{\@temppage}{\@temppage}%
44 }
45 \ifdefequal{\@@@setcpageref}{\LWR@orig@@@setcpageref}{
46 \renewcommand*{\@@@setcpageref}[2]{%
47 #1{\cpagerefFor\ \cref{#2}}{\@temppage}%
48 }
49 }{
50 \ifdefequal{\@@@setcpageref}{\LWR@orig@@@setcpageref}{
51 \renewcommand*{\@@@setcpageref}[2]{%
52 #1{\cpagerefFor\ \cref{#2}}{\@temppage}%
53 }
54 }
55 {
56 \PackageWarningNoLine{lwarp-cleveref}{

```

```

57 Unknown version of cleveref.
58 \protect\cpageref\space will fail.
59 }
60 }
61 }

62 \def\LWR@orig@@setcpagerefrange#1#2#3{% before v0.21
63 \cref@getpageref{#2}{\@pagea}%
64 \cref@getpageref{#3}{\@pageb}%
65 #1{\@pagea}{\@pageb}{\@pagec}{\@paged}%
66 }
67 \def\LWR@orig@@@setcpagerefrange#1#2#3{% as of v0.21
68 \cpageref@getlabel{#2}{\@pagea}%
69 \cpageref@getlabel{#3}{\@pageb}%
70 #1{\@pagea}{\@pageb}{\@pagec}{\@paged}%
71 }
72 \ifdefequal{\@@setcpagerefrange}{\LWR@orig@@setcpagerefrange}{
73 \renewcommand*\@@setcpagerefrange[3]{%
74 #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{\@pagec}{\@paged}%
75 }
76 }{
77 \ifdefequal{\@@@setcpagerefrange}{\LWR@orig@@@setcpagerefrange}{
78 \renewcommand*\@@@setcpagerefrange[3]{%
79 #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{\@pagec}{\@paged}%
80 }
81 }
82 {
83 \PackageWarningNoLine{lwarp-cleveref}{
84 Unknown version of cleveref.
85 \protect\cpagerefrange\space will fail.
86 }
87 }
88 }

```

If `hyperref` is loaded, `cleveref` defines starred versions of the following, but since `hyperref` is only emulated, starred versions are defined here:

```

89 \LWR@absorbstar{cref}
90 \LWR@absorbstar{Cref}
91 \LWR@absorbstar{crefrange}
92 \LWR@absorbstar{Crefrange}
93 \LWR@absorbstar{cpageref}
94 \LWR@absorbstar{Cpageref}
95 \LWR@absorbstar{cpagerefrange}
96 \LWR@absorbstar{Cpagerefrange}
97 \LWR@absorbstar{labelcref}
98 \LWR@absorbstar{labelcpageref}

```

If `hyperref` is loaded, `cleveref` also defines starred versions of `varioref` macros, so they are defined here.

```

99 \@ifpackageloaded{varioref}{
100 \LWR@absorbstar{vref}
101 \LWR@absorbstar{Vref}
102 \LWR@absorbstar{vrefrange}

```

```

103 \LWR@absorbstar{Vrefrange}
104 \LWR@absorbstar{fullref}
105 \LWR@absorbstar{Fullref}
106 }{}% varioref

```

---

File 89 **lwarp-clrdblpg.sty**

§ 195 Package **clrdblpg**

Pkg clrdblpg clrdblpg is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{clrdblpg}[2018/04/21]

---

File 90 **lwarp-cmbright.sty**

§ 196 Package **cmbright**

*(Emulates or patches code by WALTER SCHMIDT.)*

Pkg cmbright cmbright is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except slantedGreek is honored, and \mathbold is available.

The dedicated macros for upright Greek letters do work correctly.

svg math should appear the same as the printed output.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{cmbright}[2005/04/13]
2
3 \LWR@infoprocessingmathjax{cmbright}

4 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
5
6 \begin{warpMathJax}
7
8 \@ifpackagewith{cmbright}{slantedGreek}
9 {
10 \LWR@mathjax@addgreek@u@it*{}{}
11 }
12 {}
13
14 \LWR@mathjax@addgreek@u@up*{up}{}
15
16 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
17
18 \end{warpMathJax}

```

---

File 91 **lwarp-cmdtrack.sty**

§ 197 Package **cmdtrack**

Pkg cmdtrack cmdtrack is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{cmdtrack}[2012/12/18]

2 \newcommand{\untrack}[1]{}

---

File 92 **lwarp-colonequals.sty**

§ 198 Package **colonequals**

*(Emulates or patches code by HEIKO OBERDIEK.)*

Pkg colonequals colonequals is used as-is for SVG math, and is emulated for MATHJAX.

Since UNICODE symbols are not available for each of the following, only two are used for the single and double colons, and the other symbols are derived in a consistent manner. Occasional negative space is added as well. This may need to be undone for some fonts.

**for HTML output:** 1 \LWR@ProvidesPackagePass{colonequals}[2016/05/16]

```

2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{colonequals}
4
5 \CustomizeMathJax{\newcommand{\ratio}{\mathrel{\unicode{x2236}}}}
6 \CustomizeMathJax{\newcommand{\coloncolon}{\mathrel{\unicode{x2237}}}}
7 \CustomizeMathJax{\newcommand{\colonequals}{\mathrel{\unicode{x2236}!\=}}}
8 \CustomizeMathJax{\newcommand{\coloncolonequals}{\mathrel{\unicode{x2237}!\=}}}
9 \CustomizeMathJax{\newcommand{\equalscolon}{\mathrel{=\!\unicode{x2236}}}}
10 \CustomizeMathJax{\newcommand{\equalscoloncolon}{\mathrel{=\!\unicode{x2237}}}}
11 \CustomizeMathJax{\newcommand{\colonminus}{\mathrel{\unicode{x2236}-}}}
12 \CustomizeMathJax{\newcommand{\coloncolonminus}{\mathrel{\unicode{x2237}-}}}
13 \CustomizeMathJax{\newcommand{\minuscolon}{\mathrel{-\unicode{x2236}}}}
14 \CustomizeMathJax{\newcommand{\minuscoloncolon}{\mathrel{-\unicode{x2237}}}}
15 \CustomizeMathJax{\newcommand{\coloncolonapprox}{\mathrel{\unicode{x2236}!\approx}}}
16 \CustomizeMathJax{\newcommand{\coloncolonapprox}{\mathrel{\unicode{x2237}!\approx}}}
17 \CustomizeMathJax{\newcommand{\approxcolon}{\mathrel{\approx!\unicode{x2236}}}}
18 \CustomizeMathJax{\newcommand{\approxcoloncolon}{\mathrel{\approx!\unicode{x2237}}}}
19 \CustomizeMathJax{\newcommand{\colonsim}{\mathrel{\unicode{x2236}!\sim}}}
20 \CustomizeMathJax{\newcommand{\coloncolonsim}{\mathrel{\unicode{x2237}!\sim}}}
21 \CustomizeMathJax{\newcommand{\simcolon}{\mathrel{\sim!\unicode{x2236}}}}
22 \CustomizeMathJax{\newcommand{\simcoloncolon}{\mathrel{\sim!\unicode{x2237}}}}
23 \end{warpMathJax}

```

File 93 **lwarp-color.sty**§ 199 Package **color**

Pkg color Allowed but ignored. xcolor is then required as well.

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{color}[2016/07/10]
2 \RequirePackage{xcolor}
```

File 94 **lwarp-colortbl.sty**§ 200 Package **colortbl**

Pkg colortbl colortbl is used as-is for print output, and emulated for HTML.

 **row/cell color** Only use \rowcolor and \cellcolor at the start of a row, in that order.

colortbl ignores the overhang arguments.

**for HTML output:** A placeholder definition is forgotten first:

```
1 \let\rowcolor\relax
2
3 \LWR@ProvidesPackagePass{colortbl}[2018/12/12]
```

The following \LWR@HTML versions are used inside an HTML tabular.

\columncolor [*model*] [*color*] [*left overhang*] [*right overhang*]

\LWR@getmynexttoken is not used here because \columncolor is not used inside the data area of the tabular.

```
4 \NewDocumentCommand{\LWR@HTML@columncolor}{O{named} m o o}{%
5 \convertcolorspec{#1}{#2}{HTML}\LWR@columnHTMLcolor%
6 \LWR@addtabularcellcolor%
7 }
8
9 \AtBeginDocument{\LWR@formatted{columncolor}}
```

\LWR@getmynexttoken is used for \rowcolor because it is used inside the data area of the tabular.

\rowcolor [*model*] [*color*] [*left overhang*] [*right overhang*]

```
10 \NewDocumentCommand{\LWR@HTML@rowcolor}{O{named} m o o}{%
```

```

11 \convertcolorspec{#1}{#2}{HTML}\LWR@rowHTMLcolor%
12 \LWR@getmynexttoken%
13 }
14
15 \AtBeginDocument{\LWR@expandableformatted{rowcolor}}

```

`\cellcolor` [*⟨model⟩*] {*⟨color⟩*} [*⟨left overhang⟩*] [*⟨right overhang⟩*]

```

16 \NewDocumentCommand{\LWR@HTML@cellcolor}{0{named} m o o}{%
17 \convertcolorspec{#1}{#2}{HTML}\LWR@cellHTMLcolor%
18 \LWR@addtabularcellcolor%
19 }
20
21 \AtBeginDocument{\LWR@formatted{cellcolor}}

```

`\arrayrulecolor` [*⟨model⟩*] {*⟨color⟩*}

The HTML version for use outside a tabular. Inside a tabular, `\LWR@HTML@arrayrulecolornexttoken` is used instead.

```

22 \newcommand{\LWR@HTML@arrayrulecolor}[2][named]{%
23 \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
24 }
25
26 \AtBeginDocument{\LWR@expandableformatted{arrayrulecolor}}

```

[*⟨model⟩*] {*⟨color⟩*}

`\LWR@arrayrulecolornexttoken` The HTML version for use inside a tabular.

```

27 \newcommand{\LWR@HTML@arrayrulecolornexttoken}[2][named]{%
28 \convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
29 \LWR@getmynexttoken%
30 }
31
32 \AtBeginDocument{\LWR@expandableformatted{arrayrulecolornexttoken}}

```

`\doublerulesepcolor` [*⟨model⟩*] {*⟨color⟩*}

The version for use outside a tabular.

```

33 \newcommand{\LWR@HTML@doublerulesepcolor}[2][named]{%
34
35 \AtBeginDocument{\LWR@expandableformatted{doublerulesepcolor}}

```

[*⟨model⟩*] {*⟨color⟩*}

`\LWR@doublerulesepcolornexttoken` The version for use inside a tabular.

```

36 \newcommand{\LWR@HTML@doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}
37
38 \AtBeginDocument{\LWR@expandableformatted{doublerulesepcolornexttoken}}

```

File 95 **lwarp-continue.sty**§ 201 Package **continue**

Pkg continue continue is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{continue}[2018/12/09]

```

2 \newcommand*\flagcont{}
3 \newcommand*\flagend{}
4 \newcommand*\flagword{}
5 \newcommand*\preflagword{}
6 \newcommand*\postflagword{}
7 \newlength\contsep
8 \newlength\contdrop

```

File 96 **lwarp-copyrightbox.sty**§ 202 Package **copyrightbox**

*(Emulates or patches code by THOMAS FISCHER, IVES VAN DER FLAAS.)*

Pkg copyrightbox copyrightbox is emulated for use by lwarp.

The entire copyright box is placed inside a <div> of class copyrightbox.

The contents are placed inside a <div> of class copyrightboxcontents.

The copyright notice is placed inside a <div> of class copyrightboxnote.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{copyrightbox}[2011/11/27]

```

2 \newcommand{\copyrightbox}[3][r]{%
3 \begin{BlockClass}[
4 display: inline-flex;
5 flex-direction: column ;
6]{copyrightbox}
7 \begin{BlockClass}{copyrightboxcontents}
8 #2
9 \end{BlockClass}
10 \begin{BlockClass}{copyrightboxnote}
11 #3
12 \end{BlockClass}
13 \end{BlockClass}
14 }
15
16 \newcommand{\CRB@setcopyrightfont}{}
17 \newcommand{\CRB@setcopyrightparagraphstyle}{}

```

File 97 **lwarp-crop.sty**§ 203 Package **crop**

(Emulates or patches code by MELCHIOR FRANZ.)

Pkg crop **crop** is ignored.

**for HTML output:** Discard all options for lwarp-crop:

```
1 \LWR@ProvidesPackageDrop{crop}[2003/05/20]
2 \newcommand*{\crop}[1][{}]{
3 \newcommand*{\cropdef}[6][{}]
```

File 98 **lwarp-ctable.sty**§ 204 Package **ctable**

(Emulates or patches code by WYBO DEKKER.)

Pkg ctable **ctable** is patched for use by lwarp.

 **Misplaced alignment tab character &** Use `\StartDefiningTabulars` before one or more `\ctables`, and `\StopDefiningTabulars` after. These change the meaning of the ampersand & character.

**for HTML output:** 1 \LWR@ProvidesPackagePass{ctable}[2015/10/17]

The following is in the original:

```
2 \newcommand{\LWR@HTML@ctable}[4][{}]{%
3 \let\@CTtaborfig \@dfLTtaborfig
4 \let\@CTalign \@dfLTalign
5 \let\@CTsideways \@dfLTsideways
6 \let\@CTcontinued \empty
7 \let\@CTpos \@dfLTpos
8 \let\@CTcaption \empty
9 \let\@CTcap \undefined
10 \let\@CTlabel \empty
11 \let\@CTbotcap \@dfLTbotcap
12 \let\@CTstarred \@dfLTstarred
13 \let\@CTsuper \@dfLTsuper
14 \let\@CTnotespar \@dfLTnotespar
15 \let\@CTdoinside \@dfLTdoinside
16 \let\@CTbgopacity \@dfLTbgopacity
17 \@CTframerule \@dfLTframerule
18 \@CTcaptionskip \@dfLTcaptionskip
19 \@CTframesep \@dfLTframesep
```

```

20 \@CTwidth \@dfltCTwidth
21 \@CTmaxwidth \@dfltCTmaxwidth
22 \@CTmincapwidth \@dfltCTmincapwidth
23 \@CTfooterwidth \@dfltCTfooterwidth
24 \def\@CTfgactual {\@dfltCTframefg}%
25 \def\@CTbgactual {\@dfltCTframebg}%
26 \def\@CTbeg {\@begin{\@CTsideways\@CTtaborfig\@CTstarred}}%
27 \def\@CTbegin {\@CTbeg}%
28 \def\@CTend {\@end{\@CTsideways\@CTtaborfig\@CTstarred}}%
29 \setkeys{CT}{#1}%
30 \ifx\@CTcap\undefined\let\@CTcap\@CTcaption\fi
31 \ifx\@CTcap\empty
32 \if@CTcaptionloaded\else
33 \PackageWarningNoLine{lwarp-ctable}{\MessageBreak
34 An empty cap= option prevents lot/loc entry only\MessageBreak
35 if the caption package is loaded!}
36 \fi
37 \fi
38 \if@CTinmemoir\else
39 \ifx\@CTbotcap\undefined
40 \PackageError{lwarp-ctable}{\MessageBreak
41 You can, currently, use the sidecap option only with\MessageBreak
42 memoir documents. Use topcap or botcap only}
43 {}
44 \fi
45 \fi
46 \ifdim\@CTwidth=0pt\else
47 \ifdim\@CTmaxwidth=0pt\else
48 \PackageError{lwarp-ctable}{\MessageBreak
49 You may not use the width and maxwidth options together\MessageBreak
50 Use either width or maxwidth}
51 {}
52 \fi
53 \fi
54 \ifx\@CTpos\empty
55 \ifx\@CTsideways\empty\else
56 \PackageError{lwarp-ctable}{\MessageBreak
57 You may not use the pos and sideways options together\MessageBreak
58 Rotated tables and figures are always typeset on a separate page}
59 {}
60 \fi
61 \fi
62 \ifx\@CTcaption\empty
63 \ifx\@CTlabel\empty\else
64 \PackageError{lwarp-ctable}{\MessageBreak
65 You may not label a captionless table\MessageBreak
66 Such a label can't be referenced}
67 {}
68 \fi
69 \fi

```

Some of the original, regarding computing the width of `\CT@t`, is removed here.

```

70 \@CTbegin
71 \ifx\@CTcontinued\empty\else\addtocounter{\@CTtaborfig}{-1}\fi

```

72 \@CTalign

lwarp's patches begin here:

```
73 \begin{center}
74 \setlength{\fboxrule}{\@CTframerule}
75 \setlength{\fboxsep}{\@CTframesep}
76 \LWR@forceminwidth{\fboxrule}% lwarp
77 \convertcolorspec{named}{\@CTbgactual}{HTML}\LWR@tempcolor% lwarp
78 \begin{BlockClass}[% lwarp
79 border:
80 \LWR@printlength{\LWR@atleastonept}
81 solid
82 \LWR@colorstyle{named}{\@CTfgactual} ; %
83 padding:\LWR@printlength{\fboxsep} ; %
84 \ifdefstring{\LWR@tempcolor}{FFFFFF}{%
85 background: \LWR@colorstyle{named}{\@CTbgactual} ; %
86 }%
87]{fminipage}% lwarp
88 \ifx\@CTbotcap\@CTfalse\@CTcaption\vskip\@CTcaptionskip\fi
89 \ifx\@CTbotcap\undefined%
90 \begin{sidecaption}[\@CTcap]{\@CTcaption}[\@CTlabel]
91 \fi
92 \@CTdoinside
93 \begin{tabularx}{\linewidth}{#2}% lwarp
94 #4%
95 \end{tabularx}% lwarp
96 \def\@CTfootnotes{#3}%
97 \ifx#3\empty\else{% append footnotes, if any
98 \begin{BlockClass}{tnotes}% lwarp
99 #3
100 \end{BlockClass}% lwarp
101 }
102 \fi
103 \ifx\@CTbotcap\undefined\end{sidecaption}\fi
104 \ifx\@CTbotcap\@CTtrue\vskip\@CTcaptionskip\@CTcaption\fi
105 \end{BlockClass}
106 \end{center}
107 \@CTend
108 }
109 \LWR@formatted{ctable}
```

Required to properly detect the toprule:

```
110 \LetLtxMacro\FL\toprule
```

Table notes are redefined for HTML:

```
111 \newcommand{\LWR@HTML@tmark}[1][a]{%
112 \textsuperscript{\textrm{\textit{#1}}}}
113 }
114 \LWR@formatted{tmark}
115
116 \newcommand{\LWR@HTML@tnote}[2][a]{%
117 \tmark[#1]\,#2\par
```

```
118 }
119 \LWR@formatted{tnote}
```

---

File 99 **lwarp-cuted.sty**

§ 205 Package **cuted**

*(Emulates or patches code by SIGITAS TOLUŠIS.)*

Pkg cuted cuted is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{cuted}[2012/10/04]

2 \newenvironment{strip}{}{}
3 \newskip\stripsep
4 \def\oldcolsbreak#1{}
```

---

File 100 **lwarp-cutwin.sty**

§ 206 Package **cutwin**

*(Emulates or patches code by PETER WILSON AND ALAN HOENIG.)*

Pkg cutwin cutwin is emulated.

**for HTML output:** Discard all options for lwarp-cutwin:

```
1 \LWR@ProvidesPackageDrop{cutwin}[2010/09/29]

2 \newcommand*\opencutleft{}
3 \newcommand*\opencutright{}
4 \newcommand*\opencutcenter{}
5 \newcommand*\cutfuzz{}
6
7 \newenvironment{cutout}[4]
8 {\marginpar{\windowpagestuff}}
9 {}
10
11 \newcommand*\windowpagestuff{}
12
13 \newcommand*\pageinwindow}{%
14 % \begin{minipage}{.3\linewidth}
15 \windowpagestuff
16 % \end{minipage}
17 }
18
19 \newenvironment{shapedcutout}[3]
20 {\marginpar{\picinwindow}}
21 {}
22
```

---

```

23 \newcommand*{\putstuffinpic}{}
24
25 \newcommand*{\picinwindow}{%
26 \begin{picture}(0,0)
27 \putstuffinpic
28 \end{picture}}

```

---

File 101 **lwarp-dblfloatfix.sty**

§ 207 Package **dblfloatfix**

Pkg dblfloatfix **dblfloatfix** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{dblfloatfix}[2012/12/31]

---

File 102 **lwarp-dblfnote.sty**

§ 208 Package **dblfnote**

*(Emulates or patches code by HIROSHI NAKASHIMA.)*

Pkg dblfnote **dblfnote** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{dblfnote}[1999/07/14]

---

```

2 \newcounter{DFNsloppiness}
3 \newdimen\DFNcolumnsep
4 \newdimen\DFNcolumnwidth
5 \def\DFNallowcbreak{}
6 \def\DFNinhibitcbreak{}
7 \def\DFNtrysingle{}
8 \def\DFNalwaysdouble{}
9 \def\DFNruleboth{}
10 \def\DFNruleleft{}

```

---

File 103 **lwarp-dcolumn.sty**

§ 209 Package **dcolumn**

Pkg dcolumn **dcolumn** is emulated by the lwarp core.

1 \LWR@ProvidesPackageDrop{dcolumn}[2014/10/28]

---

File 104 **lwarp-decimal.sty**

§ 210 Package **decimal**

*(Emulates or patches code by A. SYROPOULOS AND R. W. D. NICKALLS.)*

Pkg decimal decimal works as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{decimal}[2011/06/03]

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\def\.\{\mbox{.}\}}
4 \end{warpMathJax}
```

---

File 105 **lwarp-diagbox.sty**

§ 211 Package **diagbox**

*(Emulates or patches code by LEO LIU.)*

Pkg diagbox diagbox is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{diagbox}[2016/12/28]

To restore print-mode inside a lateximage:

```
2 \LetLtxMacro\LWR@origdiagbox@double\diagbox@double
3 \LetLtxMacro\LWR@origdiagbox@triple\diagbox@triple
4
5 \appto\LWR@restoreorigformatting{%
6 \LetLtxMacro\diagbox@double\LWR@origdiagbox@double%
7 \LetLtxMacro\diagbox@triple\LWR@origdiagbox@triple%
8 }
```

\LWR@diagbox@AB  $\{\langle E/W \rangle\} \{\langle A \rangle\} \{\langle E/W \rangle\} \{\langle B \rangle\}$

```
9 \newcommand{\LWR@diagbox@AB}[4]{
10 \begingroup%
11 \LetLtxMacro\\\newline%
12 \BlockClassSingle{diagbox#1}{#2}%
13 \BlockClassSingle{diagbox#3}{#4}%
14 \endgroup%
15 \LWR@stoppars%
16 }
```

\LWR@diagboxNW  $\{\langle A \rangle\} \{\langle B \rangle\}$

```

17 \newcommand{\LWR@diagboxNW}[2]{%
18 \LWR@diagbox@AB{E}{#2}{W}{#1}%
19 }

```

Likewise for NE, SW, SE:

```

20 \newcommand{\LWR@diagboxNE}[2]{%
21 \LWR@diagbox@AB{W}{#1}{E}{#2}%
22 }
23
24 \let\LWR@diagboxSW\LWR@diagboxNE
25 \let\LWR@diagboxSE\LWR@diagboxNW

```

`\diagbox@double`     $\langle keys \rangle \langle A \rangle \langle B \rangle$

```

26 \def\diagbox@double#1#2#3{%
27 \setkeys{diagbox}{dir=NW,#1}%
28 \@nameuse{LWR@diagbox\diagbox@dir}{#2}{#3}%
29 }

```

`\LWR@diagboxTNW`     $\langle title \rangle \langle A \rangle \langle B \rangle$

```

30 \newcommand{\LWR@diagboxTNW}[3]{%
31 \BlockClassSingle{diagboxtitleN}{#1}
32 \LWR@diagboxNW{#2}{#3}
33 }

```

Likewise for NE, SW, SE:

```

34 \newcommand{\LWR@diagboxTNE}[3]{%
35 \BlockClassSingle{diagboxtitleN}{#1}
36 \LWR@diagboxNE{#2}{#3}
37 }
38
39 \newcommand{\LWR@diagboxTSW}[3]{%
40 \LWR@diagboxSW{#2}{#3}
41 \BlockClassSingle{diagboxtitleS}{#1}
42 \LWR@stoppars%
43 }
44
45 \newcommand{\LWR@diagboxTSE}[3]{%
46 \LWR@diagboxSE{#2}{#3}
47 \BlockClassSingle{diagboxtitleS}{#1}
48 \LWR@stoppars%
49 }

```

`\diagbox@triple`     $\langle keys \rangle \langle A \rangle \langle T \rangle \langle B \rangle$

```

50 \def\diagbox@triple#1#2#3#4{%
51 \setkeys{diagbox}{dir=NW,#1}%
52 \@nameuse{LWR@diagboxT\diagbox@dir}{#3}{#2}{#4}%
53 }

```

File 106 **lwarp-dingbat.sty**

§ 212 Package **dingbat**

(Emulates or patches code by SCOTT PAKIN.)

Pkg dingbat **dingbat** is patched for use by **lwarp**.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{dingbat}[2001/04/27]

2 \newcommand*{\LWR@dingbatsymbol}[1]{\HTMLUnicode{#1}}
3
4 \newcommand{\LWR@HTML@rightpointright}{\LWR@dingbatsymbol{261E}}
5 \newcommand{\LWR@HTML@leftpointright}{\LWR@dingbatsymbol{261E}}
6 \newcommand{\LWR@HTML@leftthumbsdown}{\LWR@dingbatsymbol{1F44E}}
7 \newcommand{\LWR@HTML@leftthumbsup}{\LWR@dingbatsymbol{1F44D}}
8 \newcommand{\LWR@HTML@rightpointleft}{\LWR@dingbatsymbol{261C}}
9 \newcommand{\LWR@HTML@rightthumbsdown}{\LWR@dingbatsymbol{1F44E}}
10 \newcommand{\LWR@HTML@rightthumbsup}{\LWR@dingbatsymbol{1F44D}}
11 \newcommand{\LWR@HTML@squarewithdots}{\LWR@dingbatsymbol{25C7}}
12 \newcommand{\LWR@HTML@filledsquarewithdots}{\LWR@dingbatsymbol{25C6}}
13 \newcommand{\LWR@HTML@Sborder}{\LWR@dingbatsymbol{271A}}
14 \newcommand{\LWR@HTML@Zborder}{\LWR@dingbatsymbol{274B}}
15 \newcommand{\LWR@HTML@largepencil}{\LWR@dingbatsymbol{270E}}
16 \newcommand{\LWR@HTML@anchor}{\LWR@dingbatsymbol{2693}}
17 \newcommand{\LWR@HTML@carriagereturn}{\LWR@dingbatsymbol{23CE}}
18 \newcommand{\LWR@HTML@checkmark}{\LWR@dingbatsymbol{2713}}
19 \newcommand{\LWR@HTML@eye}{\LWR@dingbatsymbol{1F441}}
20 \newcommand{\LWR@HTML@satellitedish}{\LWR@dingbatsymbol{1F4E1}}
21 \newcommand{\LWR@HTML@smallpencil}{\LWR@dingbatsymbol{270E}}
22
23 \LWR@formatted{rightpointright}
24 \LWR@formatted{leftpointright}
25 \LWR@formatted{leftthumbsdown}
26 \LWR@formatted{leftthumbsup}
27 \LWR@formatted{rightpointleft}
28 \LWR@formatted{rightthumbsdown}
29 \LWR@formatted{rightthumbsup}
30 \LWR@formatted{squarewithdots}
31 \LWR@formatted{filledsquarewithdots}
32 \LWR@formatted{Sborder}
33 \LWR@formatted{Zborder}
34 \LWR@formatted{largepencil}
35 \LWR@formatted{anchor}
36 \LWR@formatted{carriagereturn}
37 \LWR@formatted{checkmark}
38 \LWR@formatted{eye}
39 \LWR@formatted{satellitedish}
40 \LWR@formatted{smallpencil}

```

---

File 107 **lwarp-DotArrow.sty**

§ 213 Package **DotArrow**

*(Emulates or patches code by SVEN SCHNEIDER.)*

Pkg DotArrow **DotArrow** is patched for use by **lwarp**, and emulated for **MATHJAX**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{DotArrow}[2007/02/12]

The width must be recomputed each time, depending on print or HTML output.

```
2 \xpretocmd{\dotarrow}{\settowidth{\oneWidth}{\onePartX}}{}{}
3
4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\dotarrow}[1]{\stackrel{#1}{\unicode{x21E2}}}}
6 \end{warpMathJax}
```

---

File 108 **lwarp-dotlessi.sty**

§ 214 Package **dotlessi**

*(Emulates or patches code by JAVIER BEZOS.)*

Pkg dotlessi **dotlessi** is used as-is for SVG math, and is emulated for **MATHJAX**.

 **HTML \dotlessj** Use `\usepackage{cmap}` if `\dotlessj` does not appear in HTML in text mode. See section 7.4.

 **not bold** For **MATHJAX**, use `\boldsymbol` instead of `\mathbf`.

**for HTML output:** 1 \LWR@ProvidesPackagePass{dotlessi}[1999/10/12]

For **MATHJAX**:

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{\let\dotlessi\imath}
4 \CustomizeMathJax{\let\dotlessj\jmath}
5 \end{warpMathJax}
```

---

File 109 **lwarp-dprogress.sty**

§ 215 Package **dprogress**

Pkg dprogress **dprogress** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{dprogress}[2008/02/21]

---

File 110 **lwarp-draftcopy.sty**

§ 216 Package **draftcopy**

Pkg draftcopy **draftcopy** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{draftcopy}[2002/02/25]

```

2 \newcommand{\draftcopyVersion}[1]{}
3 \newcommand{\draftcopySetGrey}[1]{}
4 \newcommand{\draftcopySetScale}[1]{}
5 \newcommand{\draftcopySetScaleFactor}[1]{}
6 \newcommand{\draftcopyFirstPage}[1]{}
7 \newcommand{\draftcopyLastPage}[1]{}
8 \newcommand{\draftcopyName}[2]{}
9 \newcommand{\draftcopyPageTransform}[1]{}
10 \newcommand{\draftcopyBottomTransform}[1]{}
11 \newcommand{\draftcopyPageX}[1]{}
12 \newcommand{\draftcopyPageY}[1]{}
13 \newcommand{\draftcopyBottomX}[1]{}
14 \newcommand{\draftcopyBottomY}[1]{}

```

---

File 111 **lwarp-draftfigure.sty**

§ 217 Package **draftfigure**

Pkg draftfigure **draftfigure** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{draftfigure}[2017/07/19]  
2 \RequirePackage{xkeyval}

```

3 \define@key{draftfigure}{code}{}
4 \define@key{draftfigure}{noframe}[true]{}
5 \define@key{draftfigure}{filename}[true]{}
6 \define@key{draftfigure}{content}[]{}
7 \define@key{draftfigure}{style}[normal]{}
8 \define@key{draftfigure}{position}[left]{}
9 \define@key{draftfigure}{size}[normal]{}
10 \newcommand\setdf[1]{\setkeys{draftfigure}{#1}}

```

---

File 112 **lwarp-draftwatermark.sty**

§ 218 Package **draftwatermark**

*(Emulates or patches code by SERGIO CALLEGARI.)*

Pkg draftwatermark **draftwatermark** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{draftwatermark}[2020/03/14]

```

2 \newcommand{\DraftwatermarkOptions}[1]{}
3 \newcommand{\DraftwatermarkStdMark}{}
4 \newcommand{\SetWatermarkAngle}[1]{}
5 \newcommand{\SetWatermarkColor}[1]{}
6 \newcommand{\SetWatermarkLightness}[1]{}
7 \newcommand{\SetWatermarkFontSize}[1]{}
8 \newcommand{\SetWatermarkScale}[1]{}
9 \newcommand{\SetWatermarkHorCenter}[1]{}
10 \newcommand{\SetWatermarkVertCenter}[1]{}
11 \newcommand{\SetWatermarkText}[1]{}

```

File 113 **lwarp-drftcite.sty**

§ 219 Package **drftcite**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg drftcite **drftcite** is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{drftcite}[1995/01/23]

```

2 \def\lbbibitem[#1]#2{\global\@HighCite\ze
3 \item[
4 \textsuperscript{\@nameuse{DCN@#2\@extra@b@citeb}}~% lwarp
5 \@biblabel{\@ifundefined{DCN@#2\@extra@b@citeb}{\@warning
6 {Reference ‘#2’ on page \thepage\space was never cited}}}{%
7 % \DC@llap{$^\@nameuse{DCN@#2\@extra@b@citeb}}$\ \ }%o
8 \@citeverb{#2}}\hfil]\if@filesw{\def\protect##1{\string ##1\space}%
9 \immediate\write\@auxout{\string\bibcite{#2}{#1}}}\fi\ignorespaces}

```

File 114 **lwarp-easy-todo.sty**

§ 220 Package **easy-todo**

*(Emulates or patches code by JUAN RADA-VILELA.)*

Pkg easy-todo **easy-todo** is patched for use by lwarp.

To remove the “P” heading for HTML:

```
\warpHTMLonly{\renewcommand{\todoindexpagetitle}{}}
```

**for HTML output:** 1 \LWR@ProvidesPackagePass{easy-todo}[2014/01/01]

`\listoftodos` Modified to correct buggy use of `\flushright`.

```
2 \let\LWR@easytodo@origlistoftodos\listoftodos
3
4 \renewcommand{\listoftodos}{%
5 \beginingroup
6 \renewcommand{\flushright}{%
7 \LWR@easytodo@origlistoftodos
8 \endgroup
9 }
```

`\todoii` Modified to use `\textcolor` instead of `\color`.

```
10 \renewcommand{\todoii}[2]{%
11 \ifthenelse{\equal{\@todoobeyfinal}{true}}{%
12 {%
13 \ifoptionfinal{\todoenable{false}}{\todoenable{true}}%
14 }%
15 }%
16 \ifthenelse{\equal{\@todoenable}{true}}{%
17 {%
18 \refstepcounter{todos}%
19 \noindent{%
20 \todocolor%
21 \LWR@textcurrentcolor{%
22 \normalfont\scriptsize{\bfseries{\thetodos.#1}}%
23 }%
24 }%
25 \addcontentsline{lod}{todos}{\protect{\thetodos. } \LWR@isolate{#2}}%
26 }%
27 }%
28 }
```

---

File 115 **lwarp-ebook.sty**

§ 221 Package **ebook**

*(Emulates or patches code by JØRGEN STEENSGAARD.)*

Pkg ebook **ebook** is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{ebook}
2
3 \setcounter{secnumdepth}{0}
4 \setcounter{tocdepth}{2}
5
6 \providecommand{\pagefilll}[1][0.001mm]{\noindent}
7
8 \providecommand{\ebook}{%
9 \setcounter{secnumdepth}{0}
10 \setcounter{tocdepth}{2}
11 }
```

File 116 **lwarp-econometrics.sty**

§ 222 Package **econometrics**

(Emulates or patches code by ERIK KOLE.)

Pkg econometrics econometrics is used as-is for SVG math, and is emulated for MATHJAX.

```

for HTML output: 1 \LWR@ProvidesPackagePass{econometrics}% no date specified in the original

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{econometrics}
6
7 \CustomizeMathJax{\newcommand{\SC}{\mathbb{C}}}
8 \CustomizeMathJax{\newcommand{\SN}{\mathbb{N}}}
9 \CustomizeMathJax{\newcommand{\SQ}{\mathbb{Q}}}
10 \CustomizeMathJax{\newcommand{\SR}{\mathbb{R}}}
11 \CustomizeMathJax{\newcommand{\SZ}{\mathbb{Z}}}
12
13 \CustomizeMathJax{\newcommand{\calA}{\mathcal{A}}}
14 \CustomizeMathJax{\newcommand{\calB}{\mathcal{B}}}
15 \CustomizeMathJax{\newcommand{\calC}{\mathcal{C}}}
16 \CustomizeMathJax{\newcommand{\calD}{\mathcal{D}}}
17 \CustomizeMathJax{\newcommand{\calE}{\mathcal{E}}}
18 \CustomizeMathJax{\newcommand{\calF}{\mathcal{F}}}
19 \CustomizeMathJax{\newcommand{\calG}{\mathcal{G}}}
20 \CustomizeMathJax{\newcommand{\calH}{\mathcal{H}}}
21 \CustomizeMathJax{\newcommand{\calI}{\mathcal{I}}}
22 \CustomizeMathJax{\newcommand{\calJ}{\mathcal{J}}}
23 \CustomizeMathJax{\newcommand{\calK}{\mathcal{K}}}
24 \CustomizeMathJax{\newcommand{\calL}{\mathcal{L}}}
25 \CustomizeMathJax{\newcommand{\calM}{\mathcal{M}}}
26 \CustomizeMathJax{\newcommand{\calN}{\mathcal{N}}}
27 \CustomizeMathJax{\newcommand{\calO}{\mathcal{O}}}
28 \CustomizeMathJax{\newcommand{\calP}{\mathcal{P}}}
29 \CustomizeMathJax{\newcommand{\calQ}{\mathcal{Q}}}
30 \CustomizeMathJax{\newcommand{\calR}{\mathcal{R}}}
31 \CustomizeMathJax{\newcommand{\calS}{\mathcal{S}}}
32 \CustomizeMathJax{\newcommand{\calT}{\mathcal{T}}}
33 \CustomizeMathJax{\newcommand{\calU}{\mathcal{U}}}
34 \CustomizeMathJax{\newcommand{\calV}{\mathcal{V}}}
35 \CustomizeMathJax{\newcommand{\calW}{\mathcal{W}}}
36 \CustomizeMathJax{\newcommand{\calX}{\mathcal{X}}}
37 \CustomizeMathJax{\newcommand{\calY}{\mathcal{Y}}}
38 \CustomizeMathJax{\newcommand{\calZ}{\mathcal{Z}}}
39
40 \LWR@mathjax@addlatin@u@bfit{m}% uppercase Latin, bold italic
41 \LWR@mathjax@addlatin@l@bfit{v}% lowercase Latin, bold italic
42

```

```

43 \LWR@mathjax@addgreek@l@bfit{v}{}% lowercase Greek bold italic
44 \LWR@mathjax@addgreek@u@bfit*{m}{}% uppercase Greek bold italic, capitalized macro names
45
46 \CustomizeMathJax{\newcommand{\rb}{\mathrm{b}}}
47 \CustomizeMathJax{\newcommand{\rB}{\mathrm{B}}}
48 \CustomizeMathJax{\newcommand{\rC}{\mathrm{C}}}
49 \CustomizeMathJax{\newcommand{\rD}{\mathrm{D}}}
50 \CustomizeMathJax{\newcommand{\rf}{\mathrm{f}}}
51 \CustomizeMathJax{\newcommand{\rF}{\mathrm{F}}}
52 \CustomizeMathJax{\newcommand{\rH}{\mathrm{H}}}
53 \CustomizeMathJax{\newcommand{\rL}{\mathrm{L}}}
54 \CustomizeMathJax{\newcommand{\rN}{\mathrm{N}}}
55 \CustomizeMathJax{\newcommand{\rt}{\mathrm{t}}}
56 \CustomizeMathJax{\newcommand{\rU}{\mathrm{U}}}
57 \CustomizeMathJax{\newcommand{\rGam}{\mathrm{Gam}}}
58 \CustomizeMathJax{\newcommand{\rBeta}{\mathrm{Beta}}}
59
60 \CustomizeMathJax{\newcommand{\Bin}{\mathrm{Bin}}}
61 \CustomizeMathJax{\newcommand{\eu}{\mathrm{e}}}
62 \CustomizeMathJax{\newcommand{\iu}{\mathrm{i}}}
63 \CustomizeMathJax{\newcommand{\LN}{\mathrm{LN}}}
64 \CustomizeMathJax{\newcommand{\IN}{\mathrm{IN}}}
65
66 \CustomizeMathJax{\newcommand{\Poi}{\mathrm{Poi}}}
67
68 \CustomizeMathJax{\newcommand{\ped}[1]{_ \mathrm{#1}}}
69 \CustomizeMathJax{\newcommand{\ap}[1]{^ \mathrm{#1}}}
70 \CustomizeMathJax{\renewcommand{\Re}{\mathrm{Re}}{\nolimits}}
71 \CustomizeMathJax{\renewcommand{\Im}{\mathrm{Im}}{\nolimits}}
72
73 \CustomizeMathJax{\newcommand{\deriv}[3][]{%
74 \frac{\mathrm{d}^{#1}\mathrm{d}^{#2}}{\mathrm{d}\mathrm{d},\mathrm{d}^{#1}}%
75 }}
76 \CustomizeMathJax{\newcommand{\pderiv}[3][]{%
77 \frac{\partial^{#1}\mathrm{d}^{#2}}{\partial \mathrm{d}^{#1}}%
78 }}
79
80 \CustomizeMathJax{\newcommand{\bias}{\operatorname{bias}}}
81 \CustomizeMathJax{\newcommand{\col}{\operatorname{col}}}
82 \CustomizeMathJax{\newcommand{\corr}{\operatorname{corr}}}
83 \CustomizeMathJax{\newcommand{\cov}{\operatorname{cov}}}
84 \CustomizeMathJax{\newcommand{\dg}{\operatorname{dg}}}
85 \CustomizeMathJax{\newcommand{\diag}{\operatorname{diag}}}
86 \CustomizeMathJax{\newcommand{\E}{\operatorname{E}}}
87 \CustomizeMathJax{\newcommand{\etr}{\operatorname{etr}}}
88 \CustomizeMathJax{\newcommand{\ip}{\mathrm{int}}{\nolimits}}
89 \CustomizeMathJax{\newcommand{\kur}{\operatorname{kur}}}
90 \CustomizeMathJax{\newcommand{\MSE}{\operatorname{MSE}}}
91 \CustomizeMathJax{\newcommand{\MSFE}{\operatorname{MSFE}}}
92 \CustomizeMathJax{\newcommand{\OLS}{\operatorname{OLS}}}
93 \CustomizeMathJax{\newcommand{\plim}{\operatorname{plim}}}
94 \CustomizeMathJax{\newcommand{\resid}{\operatorname{resid}}}
95 \CustomizeMathJax{\newcommand{\rk}{\operatorname{rk}}}
96 \CustomizeMathJax{\newcommand{\SE}{\operatorname{SE}}}
97 \CustomizeMathJax{\newcommand{\sgn}{\operatorname{sgn}}}

```

```

98 \CustomizeMathJax{\newcommand{\tr}{\operatorname{tr}}}
99 \CustomizeMathJax{\newcommand{\var}{\operatorname{var}}}
100 \CustomizeMathJax{\renewcommand{\vec}{\operatorname{vec}}}
101 \CustomizeMathJax{\newcommand{\vech}{\operatorname{vech}}}
102
103 \CustomizeMathJax{\newcommand{\distr}{\sim}}
104 \CustomizeMathJax{\newcommand{\adistr}{\stackrel{a}{\distr}}}
105 \CustomizeMathJax{\newcommand{\diff}{\Delta}}
106 \CustomizeMathJax{\newcommand{\fdiff}{\diff_{\rf}}}
107 \CustomizeMathJax{\newcommand{\bdiff}{\diff_{\rb}}}
108
109 \CustomizeMathJax{\newcommand{\eps}{\epsilon}}
110 \CustomizeMathJax{\newcommand{\epsi}{\varepsilon}}
111
112 \CustomizeMathJax{\newcommand{\longto}{\longrightarrow}}
113 \CustomizeMathJax{\newcommand{\pto}{\stackrel{p}{\longrightarrow}}}
114 \CustomizeMathJax{\newcommand{\dto}{\stackrel{d}{\longrightarrow}}}
115 \CustomizeMathJax{\newcommand{\wto}{\stackrel{w}{\longrightarrow}}}
116
117 \CustomizeMathJax{\newcommand{\Infmat}{\bm{calI}}}
118 \CustomizeMathJax{\newcommand{\Hesmat}{\bm{calH}}}
119 \CustomizeMathJax{\newcommand{\bcdot}{\bullet}}
120
121 \CustomizeMathJax{\newcommand{\vones}{\bm{\imath}}}
122 \CustomizeMathJax{\newcommand{\vzeros}{\boldsymbol{0}}}
123 \CustomizeMathJax{\newcommand{\mZeros}{\mathbf{0}}}
124
125 \CustomizeMathJax{\newcommand{\e}{\eu}}
126 \CustomizeMathJax{\newcommand{\mply}{\cdot}}
127 \CustomizeMathJax{\newcommand{\rW}{\ensuremath{\mathrm{W}}}}
128 \end{warpMathJax}

```

---

File 117 **lwarp-ed.sty**

§ 223 Package **ed**

(Emulates or patches code by MICHAEL KOHLHASE.)

Pkg ed ed is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{ed}[2012/01/29]

Bugs:

1. `todoList` fails with the `hide` option, as does `\dedexplanation`.
2. `\edstubURI` is actually `\edstuURI`.

```

2 \RequirePackage{xcolor}
3
4 \renewenvironment{edstub}[2][The following blue text]
5 {%

```

```

6 \def\@test{#1}%
7 \begin{center}%
8 \huge%
9 \textcolor{red}{%
10 #1 is only a provisional stub\\Large
11 the Office document
12 \ifx\ed@stubURI\@empty{#2}\else\LWR@href{\ed@stubURI}{#2}\fi\
13 contains more text\\which will be merged for the final document%
14 }%
15 \end{center}%
16 \BlockClass[color:blue]{edstub}%
17 }
18 {\endBlockClass}

```

---

File 118 **lwarp-ellipsis.sty**

§ 224 Package **ellipsis**

(Emulates or patches code by PETER J. HESLIN.)

Pkg ellipsis ellipsis is emulated.

```

1 \LWR@ProvidesPackageDrop{ellipsis}[2004/09/28]
2
3 \newcommand{\ellipsisgap}{0.1em}
4
5 \newcommand*{\midwordellipsis}{\,\textellipsis\,}

```

---

File 119 **lwarp-embrac.sty**

§ 225 Package **embrac**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg embrac embrac is patched for HTML and used as-is for print.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{embrac}[2017/07/04]
2
3 \ExplSyntaxOn
4 \RenewDocumentCommand{\embrac_kern:n}{m}{ }
5 \ExplSyntaxOff
6
7 \LetLtxMacro\LWR@orig@HTML@emph\LWR@HTML@emph
8 \RenewDocumentCommand{\LWR@HTML@emph}{s m}{\LWR@orig@HTML@emph{#2}}
9
10 \LetLtxMacro\LWR@orig@HTML@textit\LWR@HTML@textit
11 \RenewDocumentCommand{\LWR@HTML@textit}{s m}{\LWR@orig@HTML@textit{#2}}
12
13 \LetLtxMacro\LWR@orig@HTML@textsl\LWR@HTML@textsl
14 \RenewDocumentCommand{\LWR@HTML@textsl}{s m}{\LWR@orig@HTML@textsl{#2}}

```

```

12 \RenewDocumentCommand{\LWR@HTML@textsl}{s m}{\LWR@orig@HTML@textsl{#2}}
13
14 \ifxetexorluatex
15 \LetLtxMacro\LWR@orig@HTML@textsi\LWR@HTML@textsi
16 \RenewDocumentCommand{\LWR@HTML@textsi}{s m}{%
17 \LWR@orig@HTML@textsi{#2}}
18 \fi
19
20 \AtBeginDocument{
21 \LWR@formatted{emph}
22 \LWR@formatted{textit}
23 \LWR@formatted{textsl}
24 \ifxetexorluatex
25 \LWR@formatted{textsi}
26 \fi
27 }
28
29 \newcommand{\LWR@HTML@EmbracOff}{}
30 \LWR@formatted{EmbracOff}
31
32 \newcommand{\LWR@HTML@EmbracOn}{}
33 \LWR@formatted{EmbracOn}

```

---

File 120 **lwarp-emptypage.sty**

§ 226 Package **emptypage**

Pkg emptypage emptypage is ignored.

**for HTML output:** Discard all options for lwarp-emptypage:

```
1 \LWR@ProvidesPackageDrop{emptypage}[2010/05/30]
```

---

File 121 **lwarp-endfloat.sty**

§ 227 Package **endfloat**

Pkg endfloat endfloat is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{endfloat}[2019/04/15]

```

2 \newcommand\figureplace{}
3 \newcommand\tableplace{}
4 \newcommand\floatplace[1]{}
5 \newcounter{posttable}
6 \newcounter{postfigure}
7 \newcommand*\theposttbl{}
8 \newcommand*\thepostfig{}
9 \newcommand{\AtBeginFigures}[1]{}
10 \newcommand{\AtBeginTables}[1]{}

```

```

11 \newcommand{\AtBeginDelayedFloats}[1]{}
12 \newcommand*\processdelayedfloats{}
13 \newcommand*\efloatseparator{}
14 \def\efloattype{}
15 \providecommand\efloatheading[1]{}
16 \providecommand\efloatpreamble{}
17 \providecommand\efloatpostamble{}
18 \NewDocumentCommand{\addtodelayedfloat}{s m m}{}
19 \providecommand{\efloatbegin}{}
20 \providecommand{\efloatend}{}
21 \providecommand{\efloatbeginlist}{}
22 \providecommand{\efloatendlist}{}

```

---

File 122 **lwarp-endheads.sty**

§ 228 Package **endheads**

Pkg endheads endheads is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{endheads}[2017/04/06]

2 \newcommand{\changesinglepageabbrev}[1]{}
3 \newcommand{\changemultiplepageabbrev}[1]{}
4 \newcommand{\changenotesname}[1]{}
5 \newcommand{\changenotesheader}[1]{}
6 \newcommand{\changenotescontentsname}[1]{}
7 \newcommand{\changechapternotesline}[1]{}
8 \newcommand{\checknoteheaders}{}
9 \newif\ifnotesincontentson \notesincontentsonfalse
10 \newcommand{\notesincontents}{\notesincontentsontrue}
11 \newif\ifendnoteheaderson \endnoteheadersonfalse
12 \newcommand{\setupendnoteheaders}{%
13 \endnoteheadersontrue%
14 }
15 \newif\iftitleinnotes \titleinnotestrue
16 \newcommand{\styleforchapternotebegin}{}
17 \newcommand{\styleforchapternoteend}{}
18 \newcommand{\setstyleforchapternotebegin}[1]{%
19 \renewcommand{\styleforchapternotebegin}{#1}%
20 }
21 \newcommand{\setstyleforchapternoteend}[1]{%
22 \renewcommand{\styleforchapternoteend}{#1}%
23 }
24 \newcommand{\resetendnotes}{}
25 \newif\ifnotesbychapteron \notesbychapteronfalse
26 \newcommand{\notesbychapter}{\notesbychapterontrue}

```

File 123 **lwarp-endnotes.sty**

§ 229 Package **endnotes**

*(Emulates or patches code by JOHN LAVAGNINO.)*

Pkg endnotes Patched for HTML.

[table of contents](#) To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\noteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

[HTML page](#) To additionally have the endnotes on their own HTML page, if FileDepth allows:

```
\ForceHTMLPage
\theendnotes
```

 [\endnotemark numbering](#) If using MATHJAX, see section 8.5.4 regarding the use of \endnotemark and \endnotetext.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{endnotes}

2 \def\noteformat{%
3 % \rightskip\z@ \leftskip\z@ \parindent=1.8em
4 \leavevmode
5 % \llap{
6 \makeenmark
7 % }
8 }

9 \def\LWR@HTML@makeenmark{\hbox{\LWR@htmlspan{sup}{\normalfont\theenmark}}}
10 \LWR@formatted{@makeenmark}
11
12 \def\makeenmark{\@makeenmark}
```

For MATHJAX:

```
13 \begin{warpMathJax}
14 \def\endnotename{endnote}
15 \appto\LWR@syncnotenumbers{\LWR@synconenotenummer{\LWRendnote}{\theendnote}}
16 \appto\LWR@syncnotenames{\LWR@synconenotename{\LWRendnote}{\endnotename}}
17 \CustomizeMathJax{\def\LWRendnote{1}}
18 \CustomizeMathJax{\newcommand{\endnote}[2][\LWRendnote]{{}^{\mathrm{#1}}}}
19 \CustomizeMathJax{\newcommand{\endnotemark}[1][\LWRendnote]{{}^{\mathrm{#1}}}}
20 \end{warpMathJax}
```

File 124 **lwarp-engtcl.sty**

§ 230 Package **engtcl**

(Emulates or patches code by CLAUDIO FIANDRINO.)

Pkg engtcl engtcl is patched for use by lwarp. MATHJAX is emulated.



For MATHJAX, `\signf`, `\signn`, and `\signz` do not force letter case as they do in SVG math.

for HTML output:

```

1 \LWR@ProvidesPackagePass{engtcl}[2012/12/18]
2 \newcommand{\LWR@HTML@fines}{%
3 \begin{BlockClass}[text-align:right]{exerend}%
4 \HTMLUnicode{220E}%
5 \end{BlockClass}%
6 }
7 \LWR@formatted{fines}
8
9 \newcommand{\LWR@HTML@exerend}{\fines}
10 \LWR@formatted{exerend}
11
12 \begin{warpMathJax}
13 \LWR@infoprocessingmathjax{engtcl}
14
15 \CustomizeMathJax{\newcommand{\unit}[1]{\,\mathrm{#1}}}
16 \CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
17 %
18 \CustomizeMathJax{\newcommand{\ho}{\unit{h}}}
19 \CustomizeMathJax{\newcommand{\s}{\unit{s}}}
20 \CustomizeMathJax{\newcommand{\ms}{\unit{ms}}}
21 \CustomizeMathJax{\newcommand{\us}{\unit{\micro s}}}
22 \CustomizeMathJax{\newcommand{\ns}{\unit{ns}}}
23 \CustomizeMathJax{\newcommand{\ps}{\unit{ps}}}
24 %
25 \CustomizeMathJax{\newcommand{\um}{\unit{\micro m}}}
26 \CustomizeMathJax{\newcommand{\mm}{\unit{mm}}}
27 \CustomizeMathJax{\newcommand{\cm}{\unit{cm}}}
28 \CustomizeMathJax{\newcommand{\dm}{\unit{dm}}}
29 \CustomizeMathJax{\newcommand{\m}{\unit{m}}}
30 \CustomizeMathJax{\newcommand{\km}{\unit{km}}}
31 %
32 \CustomizeMathJax{\newcommand{\MA}{\unit{MA}}}
33 \CustomizeMathJax{\newcommand{\kA}{\unit{kA}}}
34 \CustomizeMathJax{\newcommand{\A}{\unit{A}}}
35 \CustomizeMathJax{\newcommand{\mA}{\unit{mA}}}
36 \CustomizeMathJax{\newcommand{\uA}{\unit{\micro A}}}
37 \CustomizeMathJax{\newcommand{\nA}{\unit{nA}}}
38 %
39 \CustomizeMathJax{\newcommand{\MV}{\unit{MV}}}

```

```
40 \CustomizeMathJax{\newcommand{\kV}{\unit{kV } }}
41 \CustomizeMathJax{\newcommand{\V}{\unit{V}}}
42 \CustomizeMathJax{\newcommand{\mV}{\unit{mV}}}
43 \CustomizeMathJax{\newcommand{\uV}{\unit{\micro V}}}
44 %
45 \CustomizeMathJax{\newcommand{\mohm}{\unit{m\Omega}}}
46 \CustomizeMathJax{\newcommand{\ohm}{\unit{\Omega}}}
47 \CustomizeMathJax{\newcommand{\kohm}{\unit{k\Omega}}}
48 \CustomizeMathJax{\newcommand{\Mohm}{\unit{M\Omega}}}
49 %
50 \CustomizeMathJax{\newcommand{\pSi}{\unit{pS}}}
51 \CustomizeMathJax{\newcommand{\nSi}{\unit{nS}}}
52 \CustomizeMathJax{\newcommand{\uSi}{\unit{\micro S}}}
53 \CustomizeMathJax{\newcommand{\mSi}{\unit{mS}}}
54 \CustomizeMathJax{\newcommand{\Si}{\unit{S}}}
55 \CustomizeMathJax{\newcommand{\kSi}{\unit{kS}}}
56 \CustomizeMathJax{\newcommand{\MSi}{\unit{MS}}}
57 %
58 \CustomizeMathJax{\newcommand{\fFa}{\unit{fF}}}
59 \CustomizeMathJax{\newcommand{\pFa}{\unit{pF}}}
60 \CustomizeMathJax{\newcommand{\nFa}{\unit{nF}}}
61 \CustomizeMathJax{\newcommand{\uFa}{\unit{\micro F}}}
62 \CustomizeMathJax{\newcommand{\mFa}{\unit{mF}}}
63 \CustomizeMathJax{\newcommand{\Fa}{\unit{F}}}
64 %
65 \CustomizeMathJax{\newcommand{\fHe}{\unit{fH}}}
66 \CustomizeMathJax{\newcommand{\pHe}{\unit{pH}}}
67 \CustomizeMathJax{\newcommand{\nHe}{\unit{nH}}}
68 \CustomizeMathJax{\newcommand{\uHe}{\unit{\micro H}}}
69 \CustomizeMathJax{\newcommand{\mHe}{\unit{mH}}}
70 \CustomizeMathJax{\newcommand{\He}{\unit{H}}}
71 %
72 \CustomizeMathJax{\newcommand{\dB}{\unit{dB}}}
73 \CustomizeMathJax{\newcommand{\dBm}{\unit{dBm}}}
74 %
75 \CustomizeMathJax{\newcommand{\uW}{\unit{\micro W}}}
76 \CustomizeMathJax{\newcommand{\mW}{\unit{mW}}}
77 \CustomizeMathJax{\newcommand{\W}{\unit{W}}}
78 \CustomizeMathJax{\newcommand{\kW}{\unit{kW}}}
79 \CustomizeMathJax{\newcommand{\MW}{\unit{MW}}}
80 %
81 \CustomizeMathJax{\newcommand{\Hz}{\unit{Hz}}}
82 \CustomizeMathJax{\newcommand{\kHz}{\unit{kHz}}}
83 \CustomizeMathJax{\newcommand{\MHz}{\unit{MHz}}}
84 \CustomizeMathJax{\newcommand{\GHz}{\unit{GHz}}}
85 \CustomizeMathJax{\newcommand{\THz}{\unit{THz}}}
86 %
87 \CustomizeMathJax{\newcommand{\bit}{\unit{bit}}}
88 \CustomizeMathJax{\newcommand{\kbit}{\unit{Kib}}}
89 \CustomizeMathJax{\newcommand{\Mbit}{\unit{Mib}}}
90 \CustomizeMathJax{\newcommand{\Byte}{\unit{B}}}
91 \CustomizeMathJax{\newcommand{\kByte}{\unit{KiB}}}
92 \CustomizeMathJax{\newcommand{\MByte}{\unit{Mib}}}
93 \CustomizeMathJax{\newcommand{\GByte}{\unit{GiB}}}
94 \CustomizeMathJax{\newcommand{\TByte}{\unit{TiB}}}
```

```

95 \CustomizeMathJax{\newcommand{\bits}{\unit{bit/s}}}
96 \CustomizeMathJax{\newcommand{\kbits}{\unit{Kib/s}}}
97 \CustomizeMathJax{\newcommand{\Mbits}{\unit{Mib/s}}}
98 \CustomizeMathJax{\newcommand{\Bytes}{\unit{B/s}}}
99 \CustomizeMathJax{\newcommand{\kBytes}{\unit{KiB/s}}}
100 \CustomizeMathJax{\newcommand{\MBytes}{\unit{MiB/s}}}
101 \CustomizeMathJax{\newcommand{\GBytes}{\unit{GiB/s}}}
102 \CustomizeMathJax{\newcommand{\TBytes}{\unit{TiB/s}}}
103 \CustomizeMathJax{\newcommand{\chips}{\unit{chip/s}}}
104 \CustomizeMathJax{\newcommand{\kchips}{\unit{Ki\mkern2mu chip/s}}}
105 \CustomizeMathJax{\newcommand{\Mchips}{\unit{Mi\mkern2mu chip/s}}}
106 \CustomizeMathJax{\newcommand{\chipsubit}{\unit{chip/bit}}}
107 %
108 \CustomizeMathJax{\newcommand{\frecciadex}[1][0.5]{%
109 \hspace{.25cm}\Longrightarrow \hspace{.25cm}}%
110 }
111 \CustomizeMathJax{\newcommand{\varianzarumore}{\frac{N_0}{2}}}
112 %
113 \CustomizeMathJax{\newcommand{\etsymbolbracearg}[2]{%
114 #1\mathopen{\}\left\lbrace#2\right\rbrace\mathclose{}}%
115 }
116 \CustomizeMathJax{\newcommand{\fourier}[1]{\etsymbolbracearg{\mathcal{F}}{#1}}}
117 \CustomizeMathJax{\newcommand{\invfourier}[1]{\etsymbolbracearg{\mathcal{F}^{-1}}{#1}}}
118 \CustomizeMathJax{\newcommand{\partereale}[1]{\etsymbolbracearg{\textbf{Re}}{#1}}}
119 \CustomizeMathJax{\newcommand{\parteimm}[1]{\etsymbolbracearg{\textbf{Im}}{#1}}}
120 \CustomizeMathJax{\newcommand{\Info}[1]{I\left(#1\right)}}
121 \CustomizeMathJax{\newcommand{\versore}[1]{\hat{#1}}}
122 \CustomizeMathJax{\newcommand{\vettore}[1]{\overrightarrow{#1}}}
123 \CustomizeMathJax{\newcommand{\coseno}[1]{\cos\left(2\pi#1t\right)}}
124 \CustomizeMathJax{\newcommand{\seno}[1]{\sin\left(2\pi#1t\right)}}
125 \CustomizeMathJax{\newcommand{\energia}[1]{\mathcal{E}_{#1}}}
126 \CustomizeMathJax{\newcommand{\moduloexp}[2]{\left\vert#1\right\vert^{\#2}}}
127 \CustomizeMathJax{\newcommand{\modulo}[1]{\left\vert#1\right\vert}}
128 \CustomizeMathJax{\newcommand{\indB}[1]{%
129 \mathopen{\}\left.#1\right\vert_{\mathrm{dB}}\mathclose{}}}%
130 \CustomizeMathJax{\newcommand{\for}[2]{\left.#1\right\vert_{\#2}}}
131 \CustomizeMathJax{\newcommand{\massimo}[1]{\etsymbolbracearg{\max}{#1}}}
132 \CustomizeMathJax{\newcommand{\minimo}[1]{\etsymbolbracearg{\min}{#1}}}
133 \CustomizeMathJax{\newcommand{\valc}{3\cdot 10^8}}
134 \CustomizeMathJax{\newcommand{\loga}[2]{\log_{#1}\#2}}
135 \CustomizeMathJax{\newcommand{\analitic}[1]{\mathring{#1}}}
136 \CustomizeMathJax{\newcommand{\diff}{\mathop{\}\mathopen{\mathrm{d}}}}
137 \CustomizeMathJax{\newcommand{\intinf}[1]{\int_{-\infty}^{+\infty}{#1}}}
138 \CustomizeMathJax{\newcommand{\deltain}[1]{\delta\left(#1\right)}}
139 \CustomizeMathJax{\newcommand{\iu}{\mathrm{j}}}
140 \CustomizeMathJax{\newcommand{\ex}[1]{\mathrm{e}^{\#1}}}
141 %
142 \CustomizeMathJax{\newcommand{\gammatens}{\{\}\^{\mathrm{V}}\Gamma}}
143 \CustomizeMathJax{\newcommand{\gammacorr}{\{\}\^{\mathrm{I}}\Gamma}}
144 \CustomizeMathJax{\newcommand{\gammatensin}[1]{\{\}\^{\mathrm{V}}\Gamma_{\mathrm{#1}}}}
145 \CustomizeMathJax{\newcommand{\gammacorrin}[1]{\{\}\^{\mathrm{I}}\Gamma_{\mathrm{#1}}}}
146 \CustomizeMathJax{\newcommand{\gammain}[1]{\Gamma_{\mathrm{#1}}}}
147 \CustomizeMathJax{\newcommand{\gammak}{\{\}\^{\mathrm{k}}\Gamma}}
148 %
149 \CustomizeMathJax{\newcommand{\lbvt}{\lambda_0}}

```

```

150 \CustomizeMathJax{\newcommand{\lbg}{\lambda_g}}
151 \CustomizeMathJax{\newcommand{\lbgvt}{\lambda_{g_0}}}
152 %
153 \CustomizeMathJax{\newcommand{\potin}[1]{P_{\mathrm{#1}}}}
154 \CustomizeMathJax{\newcommand{\potdisp}[1][P_{\mathrm{disp}}^{\#1}}
155 \CustomizeMathJax{\newcommand{\potDC}[1][P_{\mathrm{DC}}^{\#1}}
156 \CustomizeMathJax{\newcommand{\potCC}[1][P_{\mathrm{CC}}^{\#1}}
157 \CustomizeMathJax{\newcommand{\potirr}[1][P_{\mathrm{irr}}^{\#1}}
158 \CustomizeMathJax{\newcommand{\potdiss}[1][P_{\mathrm{diss}}^{\#1}}
159 \CustomizeMathJax{\newcommand{\potinc}[1][P_{\mathrm{inc}}^{\#1}}
160 %
161 \CustomizeMathJax{\newcommand{\z}[1]{Z_{\mathrm{#1}}}}
162 \CustomizeMathJax{\newcommand{\znorm}[1]{z_{\mathrm{#1}}}}
163 \CustomizeMathJax{\newcommand{\y}[1]{Y_{\mathrm{#1}}}}
164 \CustomizeMathJax{\newcommand{\ynorm}[1]{y_{\mathrm{#1}}}}
165 \CustomizeMathJax{\newcommand{\zinf}[1][Z_{\infty\#1}}
166 \CustomizeMathJax{\newcommand{\zinfn}[1]{zinf\#1}}
167 \CustomizeMathJax{\newcommand{\yinf}[1][Y_{\infty\#1}}
168 \CustomizeMathJax{\newcommand{\yinfn}[1]{yinf\#1}}
169 \CustomizeMathJax{\newcommand{\zvt}{Z_0}}
170 \CustomizeMathJax{\newcommand{\yvt}{Y_0}}
171 %
172 \CustomizeMathJax{\newcommand{\campoe}{\underline{\mathcal{E}}(\underline{r},t)}}
173 \CustomizeMathJax{\newcommand{\campoe fas}{\underline{E}(\underline{r})}}
174 \CustomizeMathJax{\newcommand{\campoh}{\underline{\mathcal{H}}(\underline{r},t)}}
175 \CustomizeMathJax{\newcommand{\campoh fas}{\underline{H}(\underline{r})}}
176 %
177 \CustomizeMathJax{\newcommand{\signt}[1]{\#1(t)}}
178 \CustomizeMathJax{\newcommand{\signf}[1]{\#1(f)}}
179 \CustomizeMathJax{\newcommand{\signn}[1]{\#1(n)}}
180 \CustomizeMathJax{\newcommand{\signz}[1]{\#1(z)}}
181 %
182 \CustomizeMathJax{\newcommand{\prob}[1]{\mathcal{P}\left(\#1\right)}}
183 \CustomizeMathJax{\newcommand{\valatt}[1]{\mathbb{E}\left[\#1\right]}}
184 \CustomizeMathJax{\newcommand{\var}[1]{\mathrm{Var}\left[\#1\right]}}
185 \CustomizeMathJax{\newcommand{\comma}{\ , \ , \ ,}}
186 \CustomizeMathJax{\newcommand{\dato}{\ , | \ ,}}
187 %
188 \CustomizeMathJax{\let\bfRe\partereale}
189 \CustomizeMathJax{\let\bfIm\parteimm}
190 \CustomizeMathJax{\let\noisevar\varianzarumore}
191 % \CustomizeMathJax{\let\exerend\finees}
192 \CustomizeMathJax{\let\Spimplies\frecciadex}
193 \CustomizeMathJax{\let\Downimplies\frecciadown}
194 \CustomizeMathJax{\let\unitvec\versore}
195 \CustomizeMathJax{\let\vector\vettore}
196 \CustomizeMathJax{\let\cosine\coseno}
197 \CustomizeMathJax{\let\sine\seno}
198 \CustomizeMathJax{\let\energy\energia}
199 \CustomizeMathJax{\let\Abs\modulo}
200 \CustomizeMathJax{\let\AbsPow\moduloexp}
201 \CustomizeMathJax{\let\Max\massimo}
202 \CustomizeMathJax{\let\Min\minimo}
203 \CustomizeMathJax{\let\c\light\valc}
204 \CustomizeMathJax{\let\Log\loga}

```

---

```

205 \CustomizeMathJax{\let\analytic\analitic}
206 \CustomizeMathJax{\let\infint\intinf}
207 \CustomizeMathJax{\let\deltaimp\deltain}
208 \CustomizeMathJax{\let\Vgamma\gammatens}
209 \CustomizeMathJax{\let\Cgamma\gammacorr}
210 \CustomizeMathJax{\let\Vgammain\gammatensin}
211 \CustomizeMathJax{\let\Cgammain\gammacorrin}
212 \CustomizeMathJax{\let\Kgamma\gammak}
213 \CustomizeMathJax{\let\powerin\potin}
214 \CustomizeMathJax{\let\availpow\potdisp}
215 \CustomizeMathJax{\let\irrpow\potirr}
216 \CustomizeMathJax{\let\disppow\potdiss}
217 \CustomizeMathJax{\let\incpow\potinc}
218 \CustomizeMathJax{\let\potalim\potCC}
219 \CustomizeMathJax{\let\potDC\potCC}
220 \CustomizeMathJax{\let\Efield\campoe}
221 \CustomizeMathJax{\let\Hfield\campoh}
222 \CustomizeMathJax{\let\phasorEfield\campoefas}
223 \CustomizeMathJax{\let\phasorHfield\campohfas}
224 \CustomizeMathJax{\let\given\dato}
225 \CustomizeMathJax{\let\expval\valatt}
226 \CustomizeMathJax{\let\rmexp\lex}
227 \end{warpMathJax}

```

---

File 125 **lwarp-enumerate.sty**

§ 231 Package **enumerate**

Pkg enumerate enumerate is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by lwarp and thus must no longer be dropped.

**for HTML output:** 1 \LWR@ProvidesPackagePass{enumerate}[2015/07/23]

---

File 126 **lwarp-enumitem.sty**

§ 232 Package **enumitem**

*(Emulates or patches code by JAVIER BEZOS.)*

Pkg enumitem enumitem is supported with minor adjustments.

**for HTML output:** 1 \LWR@ProvidesPackagePass{enumitem}[2018/11/30]

```

\newlist {<name>} {<type>} {<maxdepth>}
\renewlist {<name>} {<type>} {<maxdepth>}

```

For `enumitem` lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

```

2 \let\LWR@enumitem@orignewlist\newlist
3
4 \renewcommand*{\newlist}[3]{%
5 \LWR@enumitem@orignewlist{#1}{#2}{#3}%
6 \AtBeginEnvironment{#1}{\@nameuse{LWR@#2start}}%
7 \AtEndEnvironment{#1}{\@nameuse{LWR@#2end}}%
8 }
9
10 \def\DrawEnumitemLabel{}
```

---

File 127 **lwarp-epigraph.sty**

§ 233 Package **epigraph**

*(Emulates or patches code by PETER WILSON.)*

Pkg epigraph epigraph is emulated for HTML, and used as-is for print output.

Use CSS to format epigraphs.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{epigraph}[2020/01/02]

2 \DeclareDocumentCommand{\LWR@HTML@qitem}{m m}
3 {%
4 \begin{BlockClass}{qitem}%
5 #1%
6 \LWR@stoppars%
7 \ifbool{FormatWP}%
8 {\begin{BlockClass}[border-top:1px solid gray]{epigraphsource}}%
9 {\begin{BlockClass}{epigraphsource}}%
10 #2%
11 \end{BlockClass}%
12 \end{BlockClass}%
13 }
14 \LWR@formatted{qitem}

15 \DeclareDocumentCommand{\LWR@HTML@epigraph}{m m}
16 {%
17 \begin{LWR@BlockClassWP}{\LWR@print@mbx{text-align:right}}{epigraph}%
18 \qitem{#1}{#2}%
19 \end{LWR@BlockClassWP}%
20 }
21 \LWR@formatted{epigraph}
22
23 \DeclareDocumentEnvironment{LWR@HTML@epigraphs}{}
24 {\LWR@BlockClassWP{\LWR@print@mbx{text-align:right}}{epigraph}}
25 {\endLWR@BlockClassWP}
26 \LWR@formattedenv{epigraphs}
```

The following cannot be used in print mode while generating HTML:

```
27 \renewcommand{\epigraphhead}[2][0]{#2}
28 \renewcommand{\dropchapter}[1]{}
29 \renewcommand*\undodrop{}
```

File 128 **lwarp-epsfig.sty**

§ 234 Package **epsfig**

Pkg epsfig epsfig is emulated for use by lwarp.

 Only the L<sup>A</sup>T<sub>E</sub>X<sub>2</sub>ε syntax is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{epsfig}[2017/06/25]

A few additional keys to capture the filename:

```
2 \RequirePackage{graphics}
3
4 \define@key{igraph}{file}{%
5 \xdef\LWR@epsfig@filename{#1}%
6 }
7
8 \define@key{igraph}{figure}{%
9 \xdef\LWR@epsfig@filename{#1}%
10 }
11
12 \define@key{igraph}{prolog}{}
13
14 \define@key{igraph}{silent}[]{}

```

The captured filename is used as the argument to `\includegraphics`:

```
15 \newcommand{\epsfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
16
17 \newcommand{\psfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
```

File 129 **lwarp-epstopdf.sty**

§ 235 Package **epstopdf**

Pkg epstopdf Previous versions of lwarp had a nullified version, but now **epstopdf-base** is supported. **lwarp-epstopdf** becomes a placeholder to overwrite previous versions.

See package **epstopdf-base** for details.

**for HTML output:** 1 \LWR@ProvidesPackagePass{epstopdf}[2020-01-24]

File 130 **lwarp-epstopdf-base.sty**

§ 236 Package **epstopdf-base**

Pkg epstopdf-base

⚠ **convert to .svg**

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{epstopdf-base}[2020-01-24]
```

Redefine to remember the image filename, replacing .pdf with .svg. Use the epstopdf print version inside a lateximage.

```
2 \newcommand*{\LWR@HTML@ETE@OrgGin@setfile}[3]{%
3 \edef\LWR@tempone{#3}%
4 \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
5 \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
6 \xdef\LWR@parsedfilename{\LWR@tempone}%
7 }
8
9 \LWR@formatted{ETE@OrgGin@setfile}
```

\includegraphics in HTML mode redefines \Gin@setfile to be \LWR@HTML@Gin@setfile, which is now redirected to epstopdf's version:

```
10 \renewcommand*{\LWR@HTML@Gin@setfile}[3]{%
11 \ETE@Gin@setfile{#1}{#2}{#3}%
12 }
```

Allow .eps images to be found if a suffix is not provided:

```
13 \AtBeginDocument{
14 \DeclareGraphicsExtensions{%
15 .eps,.EPS,.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
16 }
17 \DeclareGraphicsRule{.svg}{svg}{.svg}{}
18 \DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
19 }
```

Likewise when inside a lateximage:

```
20 \appto\LWR@restoreorigformatting{%
21 \DeclareGraphicsExtensions{%
22 .eps,.EPS,.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
23 }%
24 }
```

---

File 131 **lwarp-eqlist.sty**

§ 237 Package **eqlist**

Pkg eqlist eqlist is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{eqlist}[2002/08/15]

```

2 \newenvironment{eqlist}[1][\description]{\enddescription}
3 \newenvironment{eqlist*}[1][\description]{\enddescription}
4 \newenvironment{EqList}[2][\description]{\enddescription}
5 \newenvironment{EqList*}[2][\description]{\enddescription}
6 \newcommand*\longitem[1][\item[#1]}
7 \newcommand*\eqlistinit{}
8 \newcommand*\eqliststarinit{}
9 \newcommand*\eqlistinitpar{}
10 \def\eqlistlabel#1{#1}
11 \newcommand{\eqlistauto}[1]{}
12 \newcommand{\eqlistnoauto}{}

```

---

File 132 **lwarp-eqparbox.sty**

§ 238 Package **eqparbox**

*(Emulates or patches code by SCOTT PAKIN.)*

Pkg eqparbox eqparbox is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{eqparbox}[2017/09/03]

```

2 \NewDocumentCommand{\LWR@HTML@eqparbox}{O{t} O{} O{t} m +m}{%
3 {%
4 \minipagefullwidth%
5 \parbox[#1][#2][#3]{\linewidth}{#5}%
6 }%
7 }
8 \LWR@formatted{eqparbox}
9
10 \NewDocumentCommand{\LWR@HTML@eqmakebox}{o o m}{%
11 \makebox[#2][#3]%
12 }
13 \LWR@formatted{eqmakebox}
14
15 \NewDocumentCommand{\LWR@HTML@eqframebox}{o o m}{%
16 \framebox[#2][#3]%
17 }
18 \LWR@formatted{eqframebox}
19

```

```

20 \NewDocumentEnvironment{LWR@HTML@eqminipage}{0}{t} O{} O{t} m}
21 {%
22 \begingroup%
23 \minipagefullwidth%
24 \minipage[#1][#2][#3]{\linewidth}%
25 }%
26 {%
27 \endminipage%
28 \endgroup%
29 }
30
31 \newcommand*\LWR@HTML@eqboxwidth}[1]{.25\linewidth}
32 \LWR@formatted{eqboxwidth}
33
34 \newcommand*\LWR@HTML@eqsetminwidth}[2]{}
35 \newcommand*\LWR@HTML@eqsetmaxwidth}[2]{}
36
37 \newcommand*\LWR@HTML@eqsetminwidthto}[2]{}
38 \newcommand*\LWR@HTML@eqsetmaxwidthto}[2]{}

```

---

File 133 **lwarp-errata.sty**

§ 239 Package **errata**

(Emulates or patches code by MICHAEL KOHLHASE.)

Pkg errata **errata** is patched for use by **lwarp**.

This is for v0.3 of **errata**. A newer version of **errata** with more features is under development, at which time the **lwarp** version will have to be updated.

**for HTML output:** Macros are being defined with the math dollar, so enable the **HTML** version during package loading:

```
1 \StartDefiningMath
```

Now load the package:

```
2 \LWR@ProvidesPackagePass{errata}[2006/11/12]
```

Patches for dynamic inline math:

```

3 \xpatchcmd{\erratumAdd}
4 {$_a^{\arabic{erratum}}}$}
5 % {\inlinemathother$_a^{\arabic{erratum}}}\inlinemathnormal}
6 {\textsubscript{a}\textsuperscript{\arabic{erratum}}}
7 {}
8 {\LWR@patcherror{erratum}{erratumAdd}}
9
10 \xpatchcmd{\erratumDelete}
11 {$_d^{\arabic{erratum}}}$}
12 % {\inlinemathother$_d^{\arabic{erratum}}}\inlinemathnormal}

```

```

13 {\textsubscript{d}\textsuperscript{\arabic{erratum}}}
14 {}
15 {\LWR@patcherror{erratum}{erratumDelete}}
16
17 \xpatchcmd{\erratumReplace}
18 {$_r^{\arabic{erratum}}$}
19 % {\inlinemathother$_r^{\arabic{erratum}}$\inlinemathnormal}
20 {\textsubscript{r}\textsuperscript{\arabic{erratum}}}
21 {}
22 {\LWR@patcherror{erratum}{erratumReplace}}
23
24 \xpatchcmd{\erratum}
25 {$_a$}
26 % {\inlinemathother$_a$\inlinemathnormal}
27 {\textsubscript{a}}
28 {}
29 {\LWR@patcherror{erratum}{erratumDelete}}
30
31 \xpatchcmd{\erratum}
32 {$_d^{\@thefnmark}$}
33 % {\inlinemathother$_d^{\@thefnmark}$\inlinemathnormal}
34 {\textsubscript{d}\@thefnmark}
35 {}
36 {\LWR@patcherror{erratum}{eDelete}}
37
38 \xpatchcmd{\erratum}
39 {$_r^{\@thefnmark}$}
40 % {\inlinemathother$_r^{\@thefnmark}$\inlinemathnormal}
41 {\textsubscript{r}\@thefnmark}
42 {}
43 {\LWR@patcherror{erratum}{eReplace}}

```

Finish the current page's errata before closing and reloading the list:

```
44 \preto\PrintErrata{\LWR@maybe@orignewpage}
```

No longer defining math macros with the HTML \$:

```
45 \StopDefiningMath
```

File 134 **lwarp-eso-pic.sty**

§ 240 Package **eso-pic**

*(Emulates or patches code by ROLF NIEPRASCHK.)*

Pkg eso-pic **eso-pic** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{eso-pic}[2018/04/12]

```
2 \newcommand*\LenToUnit{}
3 \newcommand{\AtPageUpperLeft}[1]{}

```

```

4 \newcommand{\AtPageLowerLeft}[1]{}
5 \newcommand{\AtPageCenter}[1]{}
6 \newcommand{\AtStockLowerLeft}[1]{}
7 \newcommand{\AtStockUpperLeft}[1]{}
8 \newcommand{\AtStockCenter}[1]{}
9 \newcommand{\AtTextUpperLeft}[1]{}
10 \newcommand{\AtTextLowerLeft}[1]{}
11 \newcommand{\AtTextCenter}[1]{}
12 \NewDocumentCommand{\AddToShipoutPictureBG}{s +m}{}

13 \newcommand{\AddToShipoutPicture}{\AddToShipoutPictureBG}
14 \NewDocumentCommand{\AddToShipoutPictureFG}{s +m}{}
15 \newcommand*\ClearShipoutPictureBG{}
16 \newcommand*\ClearShipoutPicture{}
17 \newcommand*\ClearShipoutPictureFG{}
18 \newcommand{\gridSetup}[6][[]]{}

```

---

File 135 **lwarp-esvect.sty**

§ 241 Package **esvect**

(Emulates or patches code by EDDIE SAUDRAIS.)

Pkg esvect esvect is used as-is for SVG math, and emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{esvect}% no date given

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\LWRresvectv}[1]{\overrightarrow{#1}}}
4 \CustomizeMathJax{\newcommand{\LWRresvectvstar}[2]{\overrightarrow{#1}\!_{#2}}}
5 \CustomizeMathJax{\newcommand{\vv}{\ifstar\LWRresvectvstar\LWRresvectv}}
6 \end{warpMathJax}

```

---

File 136 **lwarp-etoc.sty**

§ 242 Package **etoc**

Pkg etoc etoc is ignored. All commands are nullified.

 **\tableofcontents with \ref** The etoc package uses a non-standard syntax which looks ahead after a \tableofcontents for a following \ref. These \refs appear in the HTML result unless they are removed. Where a \tableofcontents is followed by \ref, and perhaps also \label as well, enclose all of them inside \warpprintonly:

```
\warpprintonly{\tableofcontents \ref{toc:abc} \label{toc:def}}
```

or place all code related to a local \tableofcontents inside a warpprint environment.

 **home page** Be sure to keep the initial \tableofcontents on the home page, perhaps in its own

\warpHTMLonly macro or warpHTML environment.

for HTML output:

```

1 \LWR@ProvidesPackageDrop{etoc}[2019/11/17]

2 \def\etocsetlevel#1#2{}
3 \def\etocskipfirstprefix{}
4 \let\etocthename \empty
5 \let\etocthenumber \empty
6 \let\etocthepage \empty
7 \let\etocthelinkedname \empty
8 \let\etocthelinkednumber \empty
9 \let\etocthelinkedpage \empty
10 \let\etocthelink \etocfirstofone % prior to 1.08j its was \let to \empty
11 \DeclareRobustCommand*\etocname {}
12 \DeclareRobustCommand*\etocnumber {}
13 \DeclareRobustCommand*\etocpage {}
14 \DeclareRobustCommand*\etoclink {\etocfirstofone}
15 \DeclareRobustCommand*\etocifnumbered {\etocfirstoftwo}
16 \DeclareRobustCommand*\etociffirst {\etocfirstoftwo}
17 \DeclareRobustCommand*\etocifwasempty {\etocfirstoftwo}
18 \let\etocaftertitlehook \empty
19 \let\etocaftercontentshook \empty
20 \def\etocstableofcontents{}
21 \newcommand*\localtableofcontents{}
22 \newcommand*\localtableofcontentswithrelativedepth[1]{}
23 \newcommand\etocsettocstyle[2]{}
24 \long\def\etocsetstyle#1#2#3#4#5{}
25 \def\etocfontminustwo {\normalfont \LARGE \bfseries}
26 \def\etocfontminusone {\normalfont \Large \bfseries}
27 \def\etocfontzero {\normalfont \large \bfseries}
28 \def\etocfontone {\normalfont \normalsize \bfseries}
29 \def\etocfonttwo {\normalfont \normalsize}
30 \def\etocfontthree {\normalfont \footnotesize}
31 \def\etocsepminustwo {4ex \@plus .5ex \@minus .5ex}
32 \def\etocsepminusone {4ex \@plus .5ex \@minus .5ex}
33 \def\etocsepzero {2.5ex \@plus .4ex \@minus .4ex}
34 \def\etocseppone {1.5ex \@plus .3ex \@minus .3ex}
35 \def\etocseptwo {.5ex \@plus .1ex \@minus .1ex}
36 \def\etocseptthree {.25ex \@plus .05ex \@minus .05ex}
37 \def\etocbaselinespreadminustwo {1}
38 \def\etocbaselinespreadminusone {1}
39 \def\etocbaselinespreadzero {1}
40 \def\etocbaselinespreadone {1}
41 \def\etocbaselinespreadtwo {1}
42 \def\etocbaselinespreadthree {.9}
43 \def\etocminustwoleftmargin {1.5em plus 0.5fil}
44 \def\etocminustworightmargin {1.5em plus -0.5fil}
45 \def\etocminusoneleftmargin {1em}
46 \def\etocminusonerightmargin {1em}
47 \def\etococlineleaders
48 {\hbox{\normalfont\normalsize\hbext@2ex {\hss.\hss}}}
49 \def\etocabbrevpagenamename {p.~}
50 \def\etocpartname {Part}% modified 1.08b
51 \def\etocbookname {Book}
52 \def\etocdefaultlines{}

```

```

53 \def\etocabovetocskip{3.5ex \@plus 1ex \@minus .2ex}
54 \def\etocbelowtocskip{3.5ex \@plus 1ex \@minus .2ex}
55 \def\etoccolumnsep{2em}
56 \def\etocmulticolsep{0ex}
57 \def\etocmulticolpretolerance{-1}
58 \def\etocmulticoltolerance{200}
59 \def\etocdefaultnbcol{2}
60 \def\etocinnertopsep{2ex}
61 \newcommand\etocmulticolstyle[2][{}]{
62 \def\etocinnerbottomsep{3.5ex}
63 \def\etocinnerleftsep{2em}
64 \def\etocinnerrightsep{2em}
65 \def\etocoprule{\hrule}
66 \def\etocleftrule{\vrule}
67 \def\etocrightrule{\vrule}
68 \def\etocbottomrule{\hrule}
69 \def\etocoprulecolorcmd{\relax}
70 \def\etocbottomrulecolorcmd{\relax}
71 \def\etocleftrulecolorcmd{\relax}
72 \def\etocrightrulecolorcmd{\relax}
73 \newcommand*\etocruledstyle[2][{}]{
74 \def\etocframedmhook{\relax}
75 \long\def\etocbkgcolorcmd{\relax}
76 \newcommand*\etocframedstyle[2][{}]{
77 \def\etocmulticol{}
78 \def\etocruled{}
79 \def\etocframed{}
80 \def\etoclocalmulticol{}
81 \def\etoclocalruled{}
82 \def\etoclocalframed{}
83 \def\etocarticlestyle{}
84 \def\etocarticlestylenomarks{}
85 \def\etocbookstyle{}
86 \def\etocbookstylenomarks{}
87 \let\etocreportstyle\etocbookstyle
88 \let\etocreportstylenomarks\etocbookstylenomarks
89 \def\etocmemoirtocstofmt #1#2{}
90 \def\etocmemoirstyle{}
91 \def\etocscrartclstyle{}
92 \let\etocscrbookstyle\etocscrartclstyle
93 \let\etocscrreprtstyle\etocscrartclstyle
94 \def\etocstandarddisplaystyle{\etocarticlestyle}
95 \newcommand*\etocmarkboth[1]{}
96 \newcommand*\etocmarkbothnouc[1]{}
97 \newcommand\etocstocstyle[3][section]{}
98 \newcommand\etocstocstylewithmarks[4][section]{}
99 \newcommand\etocstocstylewithmarksnouc[4][section]{}
100 \def\etocignoretoctocdepth{}
101 \def\etocsettocdepth[1]{}
102 \def\etocdepthtag #1#{\Etoc@depthtag }
103 \def\Etoc@depthtag #1{}
104 \def\etocignoredepthtags {}
105 \def\etocobeydepthtags {}
106 \def\etocsettagdepth #1#2{}
107 \def\invisibletableofcontents {}

```

---

```

108 \def\invisiblelocaltableofcontents{}
109 \def\etocsetnexttocdepth #1{}
110 \def\etocsetlocaltop #1#\Etoc@set@localtop
111 \def\Etoc@set@localtop #1{}
112 \def\etocstandardlines {}
113 \def\etococlines {}
114 \let\etocaftertohook \@empty
115 \let\etocbeforetitlehook \@empty
116 \appto\tableofcontents{\def\tableofcontents{}}
```

---

File 137 **lwarp-eurosym.sty**

§ 243 Package **eurosym**

*(Emulates or patches code by HENRIK THEILING.)*

Pkg eurosym eurosym is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{eurosym}[1998/08/06]

2 \renewrobustcmd\officialeguro{\HTMLentity{euro}}
3 \let\geneuro\officialeguro
4 \let\geneuronarrow\officialeguro
5 \let\geneurowide\officialeguro
6 \let\euro\officialeguro
7 \renewrobustcmd\eurobars{}
8 \renewrobustcmd\eurobarsnarrow{}
9 \renewrobustcmd\eurobarswide{}

```

---

File 138 **lwarp-everypage.sty**

§ 244 Package **everypage**

*(Emulates or patches code by SERGIO CALLEGARI.)*

Pkg everypage everypage is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{everypage}[2007/06/20]

2 \newcommand*\AddEverypageHook[1]{}
3 \newcommand*\AddThispageHook[1]{}

```

---

File 139 **lwarp-everyshi.sty**

§ 245 Package **everyshi**

*(Emulates or patches code by MARTIN SCHRÖDER.)*

Pkg everyshi ignored.

**for HTML output:** Discard all options for lwarp-everyshi:

```
1 \LWR@ProvidesPackageDrop{everyshi}[2001/05/15]

2 \let\EveryShipout\relax
3 \newcommand*\EveryShipout}[1]{}
4
5 \let\AtNextShipout\relax
6 \newcommand*\AtNextShipout}[1]{}

```

File 140 **lwarp-extarrows.sty**

§ 246 Package **extarrows**

*(Emulates or patches code by HUYNH KY ANH.)*

Pkg extarrows **extarrows** is used as-is for SVG math, and emulated for MATHJAX.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{extarrows}[2008/05/15]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\Newextarrow\xLongleftarrow{10,10}{0x21D0}}
4 \CustomizeMathJax{\Newextarrow\xLongrightarrow{10,10}{0x21D2}}
5 \CustomizeMathJax{\Newextarrow\xLonglefttrightarrow{10,10}{0x21D4}}
6 \CustomizeMathJax{\Newextarrow\xLeftrightarrow{10,10}{0x21D4}}
7 \CustomizeMathJax{\Newextarrow\xlonglefttrightarrow{10,10}{0x2194}}
8 \CustomizeMathJax{\Newextarrow\xleftrightharrow{10,10}{0x2194}}
9 \CustomizeMathJax{\let\xlongleftarrow\xleftarrow}
10 \CustomizeMathJax{\let\xlongrightarrow\xrightarrow}
11 \end{warpMathJax}

```

File 141 **lwarp-extramarks.sty**

§ 247 Package **extramarks**

*(Emulates or patches code by PIET VAN OOSTRUM.)*

Pkg extramarks **extramarks** is ignored.

**for HTML output:** Discard all options for lwarp-extramarks:

```
1 \LWR@ProvidesPackageDrop{extramarks}[2019/01/31]

2 \newcommand*\extramarks}[2]{}
3 \newcommand*\firstleftxmark{}
4 \newcommand*\lastleftxmark{}
5 \newcommand*\firstrightxmark{}
6 \newcommand*\lastrightxmark{}

```

```

7 \newcommand*\firstxmark{}
8 \newcommand*\lastxmark{}
9 \newcommand*\topxmark{}
10 \newcommand*\topleftxmark{}
11 \newcommand*\toprightxmark{}
12 \newcommand*\firstleftmark{}
13 \newcommand*\lastrightmark{}
14 \newcommand*\firstrightmark{}
15 \newcommand*\lastleftmark{}

```

File 142 **lwarp-fancybox.sty**

§ 248 Package **fancybox**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg fancybox fancybox is supported with some patches.

#### framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```

\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
... }{...
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}

```

#### framing alternatives

\fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

#### framed table example

The fancybox documentation's example of a framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method does lose some HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```

\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
...
\end{tabular}
\end{fminipage}
\end{table}

```

 **framed verbatim** lwarp does not support the verbatim environment inside a span, box, or fancybox's

`\Sbox`, but a verbatim may be placed inside a `fminipage`. The `fancybox` documentation's example `FramedVerb` may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
 \VerbatimEnvironment
 \fminipage{#1}
 \beginVerbatim
}{
 \endVerbatim
 \endfminipage
}
```

`framed \VerbBox` `fancybox`'s `\VerbBox` may be used inside `\fbox`.

`indented alignment` `\LVerbatim`, `\LVerbatimInput`, and `\LUseVerbatim` indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

`fancybox, fancyvrb`

If using `fancybox` or `fancyvrb` with `\VerbatimFootnotes`, and using footnotes in a sectioning command or display math, use `\footnotemark` and `\footnotetext`:

⚠ `\VerbatimFootnotes`  
⚠ sectioning or displaymath

```
\subsection[Subsection Name]
 {Subsection Name\protect\footnotemark}
 \footnotetext{A footnote with \verb+verbatim+.
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

```
1 \LWR@ProvidesPackagePass{fancybox}[2010/05/15]
```

After the preamble is loaded, after any patches to `Verbatim`:

```
2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching fancybox.}
```

`\VerbatimFootnotes` Patched to use the new version.

```
4 \def\VerbatimFootnotes{%
5 \let\@footnotetext\@footnotetext%
6 \let\LWR@footnotetext\@footnotetext% lwarp
7 }
```

`\V@footnotetext` Patches in a subset of `lwarp`'s `\LWR@footnotetext` to the `fancyvrb` version of `\V@footnotetext`.

```
8 \def\V@footnotetext{%
9 \LWR@traceinfo{V@footnotetext}%
10 \global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
11 \unvbox\LWR@footnotebox%
```

Remember the footnote number for `\ref`:

```
12 \protected@edef\@currentlabel{%
13 \csname p@footnote\endcsname\@thefnmark%
14 }% @currentlabel
```

Use HTML superscripts in the footnote even inside a `lateximage`:

```
15 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
16 \ifthenelse{%
17 \boolean{LWR@doingstartpars} \AND%
18 \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
19 }%
20 {}%
21 {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%

```

Append the footnote to the list:

```
22 \@makefntext{}%
```

The footnote text will follow after `\V@@@footnotetext` has completed.

```
23 \bgroup%
24 \aftergroup{\V@@@footnotetext}%
25 \ignorespaces%
26 }%
```

```
27 }% AfterEndPreamble
```

```
28 \renewcommand*{\@shadowbox}[1]{%
29 \ifbool{FormatWP}%
30 {\InlineClass[border:1px solid black]{shadowbox}{#1}}%
31 {\InlineClass{shadowbox}{#1}}%
32 }
33
34 \renewcommand*{\@doublebox}[1]{%
35 \ifbool{FormatWP}%
36 {\InlineClass[border:1px double black]{doublebox}{#1}}%
37 {\InlineClass{doublebox}{#1}}%
38 }
39
40 \renewcommand*{\@ovalbox}[2]{%
41 \ifbool{FormatWP}%
42 {\InlineClass[border:1px solid black; border-radius:1ex]{ovalbox}{#2}}%
43 {%
44 \ifthenelse{\isequivalentto{#1}{\thinlines}}%
45 {\InlineClass{ovalbox}{#2}}%
46 {\InlineClass{Ovalbox}{#2}}%
47 }%
48 }
```

Convert minipages, parboxes, and lists into linear text using the `LWR@nestspan` environment:

```
49 \let\LWR@origSbox\Sbox
```

```

50
51 \def\Sbox{\LWR@origSbox\LWR@nestspan}
52
53
54 \let\LWR@origendSbox\endSbox
55
56 \def\endSbox{\endLWR@nestspan\LWR@origendSbox}

```

Beqnarray is adapted for MATHJAX or enclosed inside a lateximage:

```

57 \RenewEnviron{Beqnarray}
58 {\LWR@eqnarrayfactor}
59
60 \csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}

```

\GenericCaption is enclosed in an HTML block:

```

61 \renewcommand{\GenericCaption}[1]{%
62 \LWR@figcaption%
63 \LWR@isolate{#1}%
64 \endLWR@figcaption%
65 }

```

Btrivlist is enclosed in an HTML block. This is a tabular, and does not use \item.

```

\trivlist {\llcr} [\t/c/b]
66 \RenewDocumentEnvironment{Btrivlist}{m o}
67 {%
68 \LWR@stoppars%
69 \begin{BlockClass}{Btrivlist}%
70 \tabular{#1}%
71 }
72 {%
73 \endtabular%
74 \end{BlockClass}%
75 \LWR@startpars%
76 }

```

Btrivlist is also neutralized when used inside a span:

```

77 \AtBeginEnvironment{LWR@nestspan}{%
78 \RenewDocumentEnvironment{Btrivlist}{m o}{\}{\}%
79 }

```

lwarp's handling of \item is patched to accept fancybox's optional arguments:

```

80 \let\LWRFB@origitemizeitem\LWR@itemizeitem
81 \let\LWRFB@origdescitem\LWR@descitem
82
83 \RenewDocumentCommand{\LWR@itemizeitem}{d(o)}{%
84 \IfValueTF{#2}{%
85 \LWRFB@origitemizeitem[#2]%

```

```

86 }{%
87 \LWRFB@origitemizeitem%
88 }%
89 }
90
91 \RenewDocumentCommand{\LWR@descitem}{d()}{%
92 \IfValueTF{#2}{%
93 \LWRFB@origdescitem[#2]~%
94 }{%
95 \LWRFB@origdescitem%
96 }%
97 }

98 \RenewDocumentCommand{\LWR@nestspanitem}{d()}{%
99 \if@newlist\else{\LWR@htmltagc{br /}}\fi%
100 \LWR@origitem%
101 }

```

The various boxed lists become regular lists:

```

102 \renewenvironment{Bitemize}[1][\begin{itemize}]{\end{itemize}}
103 \renewenvironment{Benumerate}[1][\begin{enumerate}]{\end{enumerate}}
104 \renewenvironment{Bdescription}[1][\begin{description}]{\end{description}}

```

`\boxput` simply prints one then the other argument, side-by-side instead of above and behind:

```

105 \RenewDocumentCommand{\boxput}{s d() m m}{%
106 \IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
107 }

```

Neutralized commands:

```

108 \RenewDocumentCommand{\fancyput}{s d() m}{%}
109 \RenewDocumentCommand{\thisfancyput}{s d() m}{%}
110
111 \RenewDocumentCommand{\fancypage}{m m}{%}
112 \RenewDocumentCommand{\thisfancypage}{m m}{%}
113
114 \def\LandScape#1{}
115 \def\endLandScape{}
116 \def\@Landscape#1#2#3{}
117 \def\endLandscape{}

```

Low-level patches for `UseVerbatim` and friends:

```

118 \let\LWRFB@UseVerbatim\UseVerbatim
119 \renewcommand*{\UseVerbatim}[1]{%
120 \LWR@atbeginverbatim{Verbatim}%
121 \LWRFB@UseVerbatim{#1}%
122 \LWR@afterendverbatim%
123 }

```

```

124
125 \let\LWRFB@LUseVerbatim\LUseVerbatim
126
127 \renewcommand*\LUseVerbatim[1]{%
128 \LWR@atbeginverbatim{LVerbatim}%
129 \noindent%
130 \LWRFB@LUseVerbatim{#1}%
131 \LWR@afterendverbatim%
132 }
133
134 \def\@BUseVerbatim[#1]#2{%
135 \LWR@atbeginverbatim{BVerbatim}%
136 \LWRFB@UseVerbatim{#2}%
137 \LWR@afterendverbatim%
138 }

```

---

File 143 **lwarp-fancyhdr.sty**

§ 249 Package **fancyhdr**

*(Emulates or patches code by PIET VAN OOSTRUM.)*

Pkg fancyhdr fancyhdr is ignored.

**for HTML output:** Discard all options for lwarp-fancyhdr:

```

1 \LWR@ProvidesPackageDrop{fancyhdr}[2019/01/31]

2 \newcommand*\fancyhead[2][{}]{
3 \newcommand*\fancyfoot[2][{}]{
4 \newcommand*\fancyhf[2][{}]{
5 \newcommand*\fancypagestyle[2]{
6 \newcommand*\lhead[2][{}]{
7 \newcommand*\chead[2][{}]{
8 \newcommand*\rhead[2][{}]{
9 \newcommand*\lfoot[2][{}]{
10 \newcommand*\cfoot[2][{}]{
11 \newcommand*\rfoot[2][{}]{
12 \newcommand*\headrulewidth{}
13 \newcommand*\footrulewidth{}
14 \newcommand*\headrule{}
15 \newcommand*\footrule{}
16 \newlength\headwidth
17 \newcommand*\fancyheadoffset[2][{}]{
18 \newcommand*\fancyfootoffset[2][{}]{
19 \newcommand*\fancyhfoffset[2][{}]{
20 \newcommand*\iffloatpage[2]{#2}
21 \newcommand*\ifftopfloat[2]{#2}
22 \newcommand*\iffbotfloat[2]{#2}
23 \newcommand*\iffootnote[2]{#2}

```

File 144 **lwarp-fancyref.sty**

§ 250 Package **fancyref**

*(Emulates or patches code by AXEL REICHERT.)*

Pkg fancyref fancyref is modified for HTML output.

**for HTML output:** 1 \LWR@ProvidesPackagePass{fancyref}[1999/02/03]

To remove the margin option, if \fancyrefhook is anything other than the paren option, then force it to the default instead. (Comparing to the margin option was not possible since lwarp has revised the meaning of \mbox so the comparison failed.)

```
2 \newcommand*{\LWRfref@parenfancyrefhook}[1]{(#1)}
3
4 \ifdefstrequal{\fancyrefhook}{\LWRfref@parenfancyrefhook}
5 {}{
6 \renewcommand*{\fancyrefhook}[1]{#1}%
7 }
```

File 145 **lwarp-fancytabs.sty**

§ 251 Package **fancytabs**

Pkg fancytabs fancytabs is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fancytabs}[2016/03/29]

```
2 \newcommand{\fancytab}[3][RIGHT]{ }
3 \newcommand{\fancytabsStyle}[1]{ }
4 \newcommand{\fancytabsHeight}[1]{ }
5 \newcommand{\fancytabsWidth}[1]{ }
6 \newcommand{\fancytabsCount}[1]{ }
7 \newcommand{\fancytabsLeftColor}[1]{ }
8 \newcommand{\fancytabsRightColor}[1]{ }
9 \newcommand{\fancytabsTop}[1]{ }
10 \newcommand{\fancytabsTextVPos}[1]{ }
11 \newcommand{\fancytabsTextHPos}[1]{ }
12 \newcommand{\fancytabsGap}[1]{ }
13 \newcommand{\fancytabsFloor}[1]{ }
14 \newcommand{\fancytabsRotate}[1]{ }
```

File 146 **lwarp-fancyvrb.sty**

§ 252 Package **fancyvrb**

(Emulates or patches code by TIMOTHY VAN ZANDT.)

Pkg fancyvrb **fancyvrb** is supported with some patches.

**HTML classes** The fancy verbatim environment is placed inside a <div> of class fancyvrb. The label is placed inside a <div> of class fancyvrblabel. The verbatim text itself is placed inside a <div> of class verbatim.

**fancybox, fancyvrb**

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

⚠ **\VerbatimFootnotes**  
⚠ **sectioning or displaymath**

```
\subsection[Subsection Name]
 {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
1 \AtBeginDocument{\RequirePackage{xcolor}}% for \convertcolorspec
2
3 \LWR@ProvidesPackagePass{fancyvrb}[2008/02/07]
```

Initial default patch for fancyvrb:

```
4 \fvset{frame=none}%
```

After the preamble is loaded, after any patches to Verbatim:

```
5 \AfterEndPreamble{
6 \LWR@traceinfo{Patching fancyvrb.}
```

\VerbatimFootnotes Patched to use the new version.

```
7 \def\VerbatimFootnotes{%
8 \let\@footnotetext\V@footnotetext%
9 \let\footnote\V@footnote%
10 \let\LWR@footnotetext\V@footnotetext% lwarp
11 }
```

\V@footnotetext Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@footnotetext.

```
12 \def\V@footnotetext{%
13 \LWR@traceinfo{V@footnotetext}%
```

```
14 \global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
15 \unvbox\LWR@footnotebox%
```

Remember the footnote number for \ref:

```
16 \protected@edef\@currentlabel{%
17 \csname p@footnote\endcsname\@thefnmark%
18 }% @currentlabel
```

Use HTML superscripts in the footnote even inside a lateximage:

```
19 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
20 \ifthenelse{%
21 \boolean{LWR@doingstartpars} \AND%
22 \cnttest{\value{LWR@lateximagedepth}}{=} {0}%
23 }%
24 {}%
25 {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@originewline}%
```

Append the footnote mark to the list:

```
26 \@makefnmark{}%
```

The footnote text will follow after \V@@@footnotetext has completed.

```
27 \bgroup%
28 \aftergroup{\V@@@footnotetext}%
29 \ignorespaces%
30 }%
```

```
31 \preto\FVB@Verbatim{\LWR@forcenewpage}
32 \preto\FVB@LVerbatim{\LWR@forcenewpage}
33 % \preto\FVB@BVerbatim{\LWR@forcenewpage}% Fails, so done below.
```

Simplified to remove PDF formatting:

```
34 \def\FV@BeginListFrame@Single{%
35 \FV@SingleFrameLine{\z@}%
36 }
37
38 \def\FV@EndListFrame@Single{%
39 \FV@SingleFrameLine{\@ne}%
40 }
41
42 \def\FV@BeginListFrame@Lines{%
43 \FV@SingleFrameLine{\z@}%
44 }
45
46 \def\FV@EndListFrame@Lines{%
47 \FV@SingleFrameLine{\@ne}%
48 }
49
50 \renewcommand*{\FV@SingleFrameSep}{}
```

Adds HTML formatting:

```
51 \def\FV@BUseVerbatim#1{%
52 \FV@BVerbatimBegin#1\FV@BVerbatimEnd%
53 }
```

`\LWR@FVstyle` Holds the style of the verbatim.

```
54 \newcommand*\LWR@FVstyle{}
```

The following patches to Verbatim are executed at the start and end of the environment, depending on the choice of frame. Original code is from the fancyvrb package.

```
55 \newcommand*\LWR@fvstartnone{%
56 \LWR@traceinfo{fvstartnone}%
57 % \hbox to\z@{
58 \BlockClass[\LWR@FVstyle]{fancyvrb}
59 \LWR@stoppars
60 \ifx\FV@LabelPositionTopLine\relax\else
61 \ifx\FV@LabelBegin\relax\else
62 \FancyVerbRuleColor{\LWR@FVfindbordercolor}
63 \LWR@htmltagc{%
64 div class="fancyvrblabel" % extra space
65 style="color: \LWR@origpound\LWR@tempcolor"%
66 }
67 \LWR@print@textrm{\FV@LabelBegin}% \textrm preserves emdash
68 \LWR@htmltagc{/div}\LWR@orignewline%
69 \fi
70 \fi
71 \LWR@atbeginverbatim{verbatim}%
72 % }%
73 }
74
75 \newcommand*\LWR@fvendnone{%
76 \LWR@traceinfo{fvendnone}%
77 % \hbox to\z@{
78 \LWR@afterendverbatim%
79 \LWR@stoppars%
80 \ifx\FV@LabelPositionBottomLine\relax\else
81 \ifx\FV@LabelEnd\relax\else
82 \FancyVerbRuleColor{\LWR@FVfindbordercolor}
83 \LWR@htmltagc{%
84 div class="fancyvrblabel" % extra space
85 style="color: \LWR@origpound\LWR@tempcolor"%
86 }
87 \LWR@print@textrm{\FV@LabelEnd}
88 \LWR@htmltagc{/div}\LWR@orignewline%
89 \fi
90 \fi
91 \endBlockClass
92 }
93
94 \newcommand*\LWR@fvstartsingel{%
```

```

95 \LWR@traceinfo{fvstartsingle}%
96 \LWR@fvstartnone%
97 \FV@BeginListFrame@Single%
98 }
99
100 \newcommand*\LWR@fvendsingle}{%
101 \LWR@traceinfo{fvendsingle}%
102 \FV@EndListFrame@Single%
103 \LWR@fvendnone%
104 }
105
106 \newcommand*\LWR@fvstartline}{%
107 \LWR@traceinfo{fvstartline}%
108 \LWR@fvstartnone%
109 % \setlength{\LWR@templengthone}{\baselineskip}%
110 \FV@BeginListFrame@Lines%
111 % \setlength{\baselineskip}{\LWR@templengthone}%
112 % \setlength{\baselineskip}{5pt}%
113 }
114
115 \newcommand*\LWR@fvendline}{%
116 \LWR@traceinfo{fvendline}%
117 \FV@EndListFrame@Lines%
118 \LWR@fvendnone%
119 }

```

The following patches select the start/left/right/end behaviors depending on frame. Original code is from the fancyvrb package.

```

120 \newcommand*\LWR@FVfindbordercolor}{%
121 \FancyVerbRuleColor%
122 \LWR@findcurrenttextcolor%
123 \color{black}%
124 }
125
126 % border width of \FV@FrameRule
127 \newcommand*\LWR@FVborderstyle}[1]{%
128 padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ; % space
129 \LWR@FVfindbordercolor\LWR@indentHTMLtwo%
130 border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt % space
131 solid {\FancyVerbRuleColor{\LWR@origpound\LWR@tempcolor}} ; % space
132 }
133
134 \def\FV@Frame@none{%
135 \renewcommand*\LWR@FVstyle}{\LWR@currenttextcolorstyle}%
136 \let\FV@BeginListFrame\LWR@fvstartnone%
137 \let\FV@LeftListFrame\relax%
138 \let\FV@RightListFrame\relax%
139 \let\FV@EndListFrame\LWR@fvendnone}
140
141 \FV@Frame@none% default values
142
143 \def\FV@Frame@single{%
144 \renewcommand*\LWR@FVstyle}{%
145 \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%

```

```

146 \LWR@FVborderstyle{}}%
147 }%
148 \let\FV@BeginListFrame\LWR@fvstartsingle%
149 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
150 \let\FV@RightListFrame\FV@RightListFrame@Single%
151 \let\FV@EndListFrame\LWR@fvendsingle}
152
153 \def\FV@Frame@lines{%
154 \renewcommand*\LWR@FVstyle{%
155 \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
156 \LWR@FVborderstyle{-top}%
157 \LWR@indentHTMLtwo%
158 \LWR@FVborderstyle{-bottom}%
159 }%
160 \let\FV@BeginListFrame\LWR@fvstartline%
161 \let\FV@LeftListFrame\relax%
162 \let\FV@RightListFrame\relax%
163 \let\FV@EndListFrame\LWR@fvendline}
164
165 \def\FV@Frame@topline{%
166 \renewcommand*\LWR@FVstyle{%
167 \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
168 \LWR@FVborderstyle{-top}%
169 }%
170 \let\FV@BeginListFrame\LWR@fvstartline%
171 \let\FV@LeftListFrame\relax%
172 \let\FV@RightListFrame\relax%
173 \let\FV@EndListFrame\LWR@fvendnone}
174
175 \def\FV@Frame@bottomline{%
176 \renewcommand*\LWR@FVstyle{%
177 \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
178 \LWR@FVborderstyle{-bottom}%
179 }%
180 \let\FV@BeginListFrame\LWR@fvstartnone%
181 \let\FV@LeftListFrame\relax%
182 \let\FV@RightListFrame\relax%
183 \let\FV@EndListFrame\LWR@fvendline}

```

Seems to be required in some situations:

```

184 \def\FV@FrameFillLine{}}%

185 \def\FV@Frame@leftline{%
186 \renewcommand*\LWR@FVstyle{%
187 \LWR@currenttextcolorstyle\LWR@indentHTMLtwo%
188 \LWR@FVborderstyle{-left}%
189 }%
190 % To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)
191 \ifx\FancyVerbFillColor\relax%
192 \let\FV@FrameFillLine\relax%
193 \else%
194 \@tempdima\FV@FrameRule\relax%
195 \multiply\@tempdima-\tw@%
196 \edef\FV@FrameFillLine{%

```

```

197 {\noexpand\FancyVerbFillColor{\vrule\@width\number\@tempdima sp}%
198 \kern-\number\@tempdima sp}}%
199 \fi%
200 \let\FV@BeginListFrame\LWR@fvstartnone%
201 \let\FV@LeftListFrame\FV@LeftListFrame@Single%
202 \let\FV@RightListFrame\relax%
203 \let\FV@EndListFrame\LWR@fvendnone}

```

Adds the optional label to the top and bottom edges. Original code is from the fancyvrb package.

```

204 \def\FV@SingleFrameLine#1{%
205 % \hbox to\z@{%
206 % \kern\leftmargin
207 \ifnum#1=\z@\relax
208 \let\FV@Label\FV@LabelBegin
209 \else
210 \let\FV@Label\FV@LabelEnd
211 \fi
212 \ifx\FV@Label\relax
213 % \FancyVerbRuleColor{\vrule \@width\linewidth \@height\FV@FrameRule}%
214 \else
215 \ifnum#1=\z@
216 % \setbox\z@\hbox{\strut\enspace\FV@LabelBegin\enspace\strut}%
217 \ifx\FV@LabelPositionTopLine\relax
218 \else
219 \fi
220 \else
221 % \setbox\z@\hbox{\strut\enspace\FV@LabelEnd\enspace\strut}%
222 \ifx\FV@LabelPositionBottomLine\relax
223 \else
224 \fi
225 \fi
226 \fi
227 % \hss
228 % }
229 }

```

Processes each line, adding optional line numbers. Original code is from the fancyvrb package.

```

230 \def\FV@ListProcessLine#1{%
231 \hbox to \hsize{%
232 % \kern\leftmargin
233 \hbox to \VerbatimHTMLWidth {%
234 \ifcvoid{FV@LeftListNumber}{\kern 2.5em}%
235 \FV@LeftListNumber%
236 % \FV@LeftListFrame
237 \FancyVerbFormatLine{#1}%
238 \hss%
239 % \FV@RightListFrame
240 \FV@RightListNumber%
241 }%
242 \hss% required to avoid underfull hboxes
243 }

```

```

244 }

245 \def\FV@ListProcessLine@i#1{%
246 % \hbox{%
247 \ifvoid\@Labels\else
248 \hbox to \z@\kern\@totalleftmargin\box\@Labels\hss}%
249 \fi
250 \FV@ListProcessLine{#1}%
251 % }%
252 % \let\FV@ProcessLine\FV@ListProcessLine@ii%
253 }

254 \def\FV@ListProcessLastLine{}

```

Env BVerbatim

```

255
256 \xpretocmd{\FV@BeginVBox}
257 {%
258 \LWR@forcenewpage% instead of \preto
259 \LWR@atbeginverbatim{bverbatim}%
260 }
261 {}
262 {\LWR@patcherror{fancyvrb}{FV@BeginVBox}}
263
264 \xapptocmd{\FV@EndVBox}
265 {%
266 \LWR@afterendverbatim%
267 }
268 {}
269 {\LWR@patcherror{fancyvrb}{FV@EndVBox}}

```

End of the modifications to make at the end of the preamble:

```

270 } % \AfterEndPreamble

```

---

File 147 **lwarp-fbox.sty**

§ 253 Package **fbox**

*(Emulates or patches code by HERBERT VOSS.)*

Pkg fbox **fbox** is patched for use by **lwarp**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{fbox}[2020/06/22]

This will be \LWR@formatted when \AtBeginDocument:

```

2 \LetLtxMacro\LWR@HTML@fbox\fbox

```

Instead of using the original, the new version is used with all borders:

```
3 \renewcommand*{\orig@fbox}{\FBox@i[tblr]}
```

```
\WR@fboxpkg@border {<1: top/bottom/left/right>} {<2: padding, or empty>}
```

Accumulates HTML styles for border, and padding if given:

```
4 \newcommand*{\LWR@fboxpkg@border}[2]{%
5 \appto\LWR@tempone{%
6 border-#1: % space
7 \LWR@printlength{\LWR@atleastonept} % space
8 solid \LWR@origpound\LWR@tempcolor ;\LWR@indentHTML
9 }%
10 \ifblank{#2}{}%
11 \appto\LWR@tempone{%
12 padding-#1: \LWR@printlength{#2} ;\LWR@indentHTML
13 }%
14 }%
15 }
```

A hack to reuse the same code for inline and blocks:

```
16 \newbool{\LWR@fboxpkg@ispar}
17 \boolfalse{\LWR@fboxpkg@ispar}
```

Accumulate HTML styles for left and right padding, depending on `\if@fbox@space@left`, `\if@fbox@space@right`:

```
18 \newcommand{\LWR@fboxpkg@lrpadding}[1]{%
19 \csuse{if@fbox@space@#1}%
20 \appto\LWR@tempone{%
21 padding-#1: \LWR@printlength{\fbox@@sep};\LWR@indentHTML
22 }
23 \else%
24 \appto\LWR@tempone{%
25 padding-#1: 0pt;\LWR@indentHTML
26 }
27 \fi%
28 }
```

The HTML version, modified to use HTML styles and either an `\InlineClass` or `BlockClass`:

```
29 \newcommand{\LWR@HTML@FBox@iii}[1]{%
```

Find and set the text color, rule width, margin:

```
30 \LWR@forceminwidth{\fbox@@rule}%
31 \LWR@findcurrenttextcolor%
32 \def\LWR@tempone{%
33 color: \LWR@origpound\LWR@tempcolor ; \LWR@indentHTML
34 margin: 1ex ; \LWR@indentHTML
35 }%
```

Add left/right padding:

```
36 \LWR@fboxpkg@lrpadding{left}%
37 \LWR@fboxpkg@lrpadding{right}%
```

Per the original to decode the borders, in a new way:

```
38 \ifnum\the\@tempcntb>8\relax
39 \advance\@tempcntb by -8
40 \LWR@fboxpkg@border{top}{\fbox@sep}%
41 \fi
42 \ifnum\@tempcntb>3
43 \advance\@tempcntb by -4
44 \LWR@fboxpkg@border{left}{}%
45 \fi
46 \ifnum\@tempcntb>1
47 \LWR@fboxpkg@border{right}{}%
48 \fi
49 \ifodd\@tempcntb
50 \LWR@fboxpkg@border{bottom}{\fbox@sep}%
51 \fi
```

Generate a BlockClass or \InlineClass with the contents:

```
52 \color@begingroup
53 \ifbool{LWR@fboxpkg@ispar}%
54 {%
55 \begin{BlockClass}[\LWR@tempone]{fboxpkg}%
56 #1%
57 \end{BlockClass}%
58 }%
59 {%
60 \InlineClass[\LWR@tempone]{fboxpkg}{%
61 #1%
62 }%
63 }%
64 \color@endgroup
65 \boolfalse{LWR@fboxpkg@ispar}% globally
66 }
67 \LWR@formatted{FBox@iii}
```

For \fparbox, set the use of BlockClass, then reuse the above:

```
68 \long\def\LWR@HTML@FParBox@i[#1]#2{%
69 \booltrue{LWR@fboxpkg@ispar}%
70 \FBox@i[#1]{#2}
71 }
72 \LWR@formatted{FParBox@i}
73
74 \long\def\LWR@HTML@FParBox@ii#1{%
75 \booltrue{LWR@fboxpkg@ispar}%
76 \FBox@i[tblr]{#1}%
77 }
78 \LWR@formatted{FParBox@ii}
```

For MATHJAX, absorb and ignore star and optional arguments:

```
79 \CustomizeMathJax{\let\LWRorigfbox\fbox}
80 \CustomizeMathJax{\newcommand{\LWRfboxpkgtwo}[2][\LWRorigfbox{#2}]}
81 \CustomizeMathJax{\renewcommand{\fbox}{\ifstar\LWRfboxpkgtwo\LWRfboxpkgtwo}}
82 \CustomizeMathJax{\newcommand{\fparbox}{\fbox}}
```

File 148 **lwarp-fewerfloatpages.sty**

§ 254 Package **fewerfloatpages**

Pkg fewerfloatpages fewerfloatpages is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fewerfloatpages}[2020/02/14]

```
2 \newcommand\floatpagekeepfraction{\textfraction}
3 \newcounter{floatpagedeferlimit}
4 \newcounter{floatpagekeeplimit}
```

File 149 **lwarp-figcaps.sty**

§ 255 Package **figcaps**

*(Emulates or patches code by PATRICK W. DALY.)*

Pkg figcaps figcaps is ignored.

**for HTML output:** Discard all options for lwarp-figcaps:

```
1 \LWR@ProvidesPackageDrop{figcaps}[1999/02/23]

2 \newcommand*\figcapson{}
3 \newcommand*\figcapsoff{}
4 \newcommand*\printfigures{}
5 \newcommand*\figmarkon{}
6 \newcommand*\figmarkoff{}
7 \def\figurecapname{Figure Captions}
8 \def\tablepagename{Tables}
9 \def\figurepagename{Figures}
```

File 150 **lwarp-figsize.sty**

§ 256 Package **figsize**

*(Emulates or patches code by ANTHONY A. TANBAKUCHI.)*

Pkg figsize figsize is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{figsize}[2002/03/18]

Emulates a virtual 6×9 inch textsize.

```

2 \newlength{\figwidth}
3 \newlength{\figheight}
4
5 \newcommand{\SetFigLayout}[3][0]{%
6 \setlength{\figheight}{8in}%
7 \setlength{\figheight}{\figheight / #2}%
8 %
9 \setlength{\figwidth}{5.5in}%
10 \setlength{\figwidth}{\figwidth / #3}%
11 }
```

File 151 **lwarp-fitbox.sty**

§ 257 Package **fitbox**

Pkg fitbox **fitbox** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fitbox}[2019/02/20]

```

2 \NewDocumentCommand{\fitbox}{s o m}{%
3 \begin{BlockClass}{fitbox}
4 #3
5 \end{BlockClass}
6 }
7
8 \newcommand*{\fitboxset}[1]{}
9
10 \newdimen\fitboxnatheight
11 \newdimen\fitboxnatwidth
12
13 \newcommand\SetFitboxLayout[3][[]]{}

```

File 152 **lwarp-fix2col.sty**

§ 258 Package **fix2col**

Pkg fix2col **fix2col** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fix2col}[2015/11/13]

File 153 **lwarp-fixmath.sty**

§ 259 Package **fixmath**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg `fixmath` `fixmath` is used as-is for SVG math, and emulated for MATHJAX.

 **limitations** MATHJAX does not have full font support for bold italic Greek.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{fixmath}[2000/04/11]
2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@mathjax@addgreek@u@it*{}{}
6 \LWR@mathjax@addLetter{\BooleanTrue}{up}{}{\delta}{0394}
7 \LWR@mathjax@addLetter{\BooleanTrue}{up}{}{\omega}{03A9}
8 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
9 \end{warpMathJax}
```

File 154 **lwarp-fixme.sty**

§ 260 Package **fixme**

(Emulates or patches code by DIDIER VERNA.)

Pkg `fixme` `fixme` is patched for use by `lwarp`.

 **external layouts** External layouts (`\fxloadlayouts`) are not supported.

User control is provided for setting the HTML styling of the “faces”. The defaults are as follows, and may be changed in the preamble after `fixme` is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{fixme}[2017/03/05]
```

Restore `lwarp`'s version of `\@wrindex`, ignoring the `fixme` package's target option:

```
2 \let\@wrindex\LWR@wrindex
```

Float-related macros required by `lwarp`:

```

3 \newcommand{\ext@fixme}{lox}
4
5 \renewcommand{\l@fixme}[2]{%
6 \hypertocfloat{1}{fixme}{lox}%
7 {\LWR@nameref{\BaseJobname-autopage-\arabic{LWR@nextautopage}} --- #1}
8 {#2}
9 }

```

Other modifications:

```

10 \def\FXFaceInlineHTMLStyle{font-weight:bold}
11
12 \renewcommand*\FXLayoutInline[3]{ %
13 \InlineClass[\FXFaceInlineHTMLStyle]{fixmeinline}%
14 {\@fxttextstd{#1}{#2}{#3}}%
15 }
16
17 \def\FXFaceEnvHTMLStyle{font-weight:bold}
18
19 \renewcommand*\FXEnvLayoutPlainBegin[2]{%
20 \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
21 \ignorespaces#2 \fxnotename{#1}: \ignorespaces}
22
23 \renewcommand*\FXEnvLayoutPlainEnd[2]{\endBlockClass}
24
25 \renewcommand*\FXEnvLayoutSignatureBegin[2]{%
26 \BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
27 \fxnotename{#1}: \ignorespaces}
28
29 \renewcommand*\FXEnvLayoutSignatureEnd[2]{\@fxsignature{#2}\endBlockClass}
30
31 \def\FXFaceSignatureHTMLStyle{font-style:italic}
32
33 \DeclareRobustCommand*\@fxsignature[1]{%
34 \ifthenelse{\equal{#1}{}}%
35 {}%
36 { -- {\InlineClass[\FXFaceSignatureHTMLStyle]{fixmesignature}{#1}}}%
37 }
38
39
40 \def\FXFaceTargetHTMLStyle{font-style:italic}
41
42 \renewcommand\FXTargetLayoutPlain[2]{%
43 \InlineClass[\FXFaceTargetHTMLStyle]{fixmetarget}{#2}%
44 }

```

---

File 155 **lwarp-fixmetodonotes.sty**

§ 261 Package **fixmetodonotes**

*(Emulates or patches code by GIOELE BARABUCCI.)*

Pkg fixmetodonotes **fixmetodonotes** is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{fixmetodonotes}[2013/04/28]
2 \renewcommand{\NOTES@addtolist}[2]{%
3 \refstepcounter{NOTES@note}%
4 % \phantomsection% REMOVED
5 \addcontentsline{notes}{NOTES@note}{%
6 \protect\numberline{\theNOTES@note}{\#1}: {\#2}}%
7 }%
8 }
9
10 \renewcommand{\NOTES@marker}[2]{\fbox{%
11 \textcolor{\#2}{% WAS \color
12 \textbf{\#1}}}%
13 }}
14
15 \renewcommand{\NOTES@colorline}[2]{%
16 \bgroup%
17 \ULon{\LWR@backgroundcolor{\#1}{\#2}}%
18 }

```

---

File 156 **lwarp-flafter.sty**

§ 262 Package **flafter**

Pkg flafter flafter is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{flafter}[2018/01/08]
2 \providecommand\fl@trace[1]{}

```

---

File 157 **lwarp-flippdf.sty**

§ 263 Package **flippdf**

Pkg flippdf flippdf is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{flippdf}[2006/06/30]
2 \newcommand\FlipPDF{}
3 \newcommand\UnFlipPDF{}

```

---

File 158 **lwarp-float.sty**

§ 264 Package **float**

*(Emulates or patches code by ANSELM LINGNAU.)*

Pkg float float is emulated.

Float styles boxed and ruled are emulated by css and a float class according to style.

The HTML `<figure>` class is set to the float type, so css may also be used to format the float and its caption, according to float type. Furthermore, an additional class is set to the float style: `plain`, `plaintop`, `boxed`, or `ruled`, so css may be used to format by float style as well. Default formatting by css is provided for ruled and boxed styles.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{float}[2001/11/08]

\LWR@floatstyle The default float style:

```
2 \newcommand*{\LWR@floatstyle}{plain}
```

\newfloat {<1: type>} {<2: placement>} {<3: ext>} [<4: within>]

Emulates the `\newfloat` command from the `float` package.

“placement” is ignored.

```
3 \NewDocumentCommand{\newfloat}{m m m o}{%
4 \IfValueTF{#4}%
5 {\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}%
6 {\DeclareFloatingEnvironment[fileext=#3]{#1}}%
```

Remember the float style:

```
7 \csdef{\LWR@floatstyle@#1}{\LWR@floatstyle}%
```

`newfloat` package automatically creates the `\listof` command for new floats, but `float` does not, so remove `\listof` here in case it is manually created later.

```
8 \cslet{\listof#1s}\relax%
9 \cslet{\listof#1es}\relax%
```

Like `size`, `newfloat` also creates `\l@<type>`, but `float` does not, so remove it here:

```
10 \cslet{\l@#1}\relax%
11 }
```

\floatname {<type>} {<name>}

Sets the text name of the float, such as “Figure”. Avoids trying to set a recursive name, from `trivfloat`.

```
12 \NewDocumentCommand{\floatname}{m +m}{%
13 \def\LWR@tempone{#2}%
14 \def\LWR@temptwo{\@nameuse{#1name}}%
15 \ifdefequal{\LWR@tempone}{\LWR@temptwo}{}%
16 \SetupFloatingEnvironment{#1}{name=#2}%
17 }%
18 }
```

\floatplacement {<type>} {<placement>}

Float placement is ignored.

```
19 \newcommand*{\floatplacement}[2]{%
```

```
20 \SetupFloatingEnvironment{#1}{placement=#2}%
21 }
```

`\floatstyle`    `{<style>}`

Remember the style for future floats:

```
22 \newcommand{\floatstyle}[1]{%
23 \def\LWR@floatstyle{#1}%
24 }
```

`\restylefloat`    `*{<type>}`

Remember the style for this float:

```
25 \NewDocumentCommand{\restylefloat}{s m}{%
26 \csedef{LWR@floatstyle@#2}{\LWR@floatstyle}%
27 }
```

`\listof`    See section [76.2](#) for the `\listof` command in the `lwarp` core.

File 159    **lwarp-floatflt.sty**

§ 265    Package    **floatflt**

*(Emulates or patches code by MATS DAHLGREN.)*

Pkg floatflt    floatflt is emulated.

for HTML output:    Discard all options for `lwarp-floatflt`:

```
1 \LWR@ProvidesPackageDrop{floatflt}[1997/07/16]
```

Env    [`<>`]    `offset` `{<type>}` `{<width>}` Borrowed from the `lwarp` version of `keyfloat`:

```
2 \NewDocumentEnvironment{KFLTfloatflt@marginfloat}{0{-1.2ex} m m}
3 {%
4 \begin{LWR@setvirtualpage}*%
5 \ifblank{#3}{%
6 \LWR@BlockClassWP{%
7 float:right; %
8 width: 1.5in; % reasonable dummy width for word processor
9 margin:10pt%
10 }}{%
11 {marginblock}%
12 }{%
13 \setlength{\LWR@templengthone}{#3}%
14 \LWR@BlockClassWP{%
15 float:right; %
16 width:\LWR@printlength{\LWR@templengthone}; % extra space
17 margin:10pt%
18 }{%
19 width:\LWR@printlength{\LWR@templengthone}%
```

```

20 }%
21 {marginblock}%
22 }%
23 \renewcommand*\@capttype{#2}%
24 }
25 {%
26 \endLWR@BlockClassWP%
27 \end{LWR@setvirtualpage}%
28 }

```

Env floatingfigure [*<placement>*] [*<width>*]

```

29 \DeclareDocumentEnvironment{floatingfigure}{o m}
30 {\begin{KFLTfloatflt@marginfloat}{figure}{#2}}
31 {\end{KFLTfloatflt@marginfloat}}

```

Env floatingtable [*<placement>*]

```

32 \DeclareDocumentEnvironment{floatingtable}{o}
33 {\begin{KFLTfloatflt@marginfloat}{table}{} }
34 {\end{KFLTfloatflt@marginfloat}}

```

---

File 160 **lwarp-floatpag.sty**

§ 266 Package **floatpag**

(Emulates or patches code by VYTAS STATULEVIČIUS AND SIGITAS TOLUŠIS.)

Pkg floatpag floatpag is ignored.

**for HTML output:** Discard all options for lwarp-floatpag:

```

1 \LWR@ProvidesPackageDrop{floatpag}[2012/05/29]

2 \newcommand*\floatpagestyle[1]{}
3 \newcommand*\rotfloatpagestyle[1]{}
4 \newcommand*\thisfloatpagestyle[1]{}

```

---

File 161 **lwarp-floatrow.sty**

§ 267 Package **floatrow**

(Emulates or patches code by OLGA LAPKO.)

Pkg floatrow floatrow is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{floatrow}[2008/08/02]

 **Misplaced alignment tab character &** Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 8.10.1.

⚠ **subfig package** When combined with the subfig package, while inside a subfloatrow `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

The emulation of floatrow does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

⚠ `\FBwidth, \FBheight`

- Use fixed lengths. `lwarp` will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether `subcaption` was loaded. If not, it is assumed that `subfig` is used instead:

```
2 \newbool{LWR@subcaptionloaded}
3
4 \AtBeginDocument{
5 \ifpackageloaded{subcaption}
6 {\booltrue{LWR@subcaptionloaded}}
7 {\boolfalse{LWR@subcaptionloaded}}
8 }
```

`\floatbox` [`<1 preamble>`] [`<2 captype>`] [`<3 width>`] [`<4 height>`] [`<5 vert pos>`] [`<6 caption>`] [`<7 object>`]

Only parameters for `captype`, `width`, `caption`, and `object` are used.

`LWR@insubfloatrow` is true if inside a `subfloatrow` environment.

There are two actions, depending on the use of `subcaption` or `subfig`.

```
9 \NewDocumentCommand{\floatbox}{o m o o o +m +m}{%
10 \ifbool{LWR@subcaptionloaded}%
11 {% subcaption
```

For `subcaption`:

```
12 \ifbool{LWR@insubfloatrow}%
13 {% subcaption in a subfloatrow
```

`subfigure` and `subtable` environments take `width` as an argument.

```
14 \IfValueTF{#3}%
15 {\@nameuse{sub#2}{#3}}%
16 {\@nameuse{sub#2}{\linewidth}}%
17 }% subcaption in a subfloatrow
18 {% subcaption not in subfloatrow
```

`figure` and `table` environments do not take a `width` argument.

```
19 \@nameuse{#2}%
20 }% subcaption not in subfloatrow
```

```
21 #6
22
23 #7
```

End the environments:

```
24 \ifbool{LWR@insubfloatrow}%
25 {\@nameuse{endsub#2}}%
26 {\@nameuse{end#2}}%
27 }% subcaption
28 {% assume subfig
```

For subfig:

```
29 \ifbool{LWR@insubfloatrow}%
30 {% subfig in a subfloatrow
```

`\subfloat` is a macro, not an environment.

Package `subfig`'s `\subfloat` command takes an optional argument which is the caption, but `\floatbox` argument #6 contains commands to create the caption and label, not the caption itself. Thus, `\caption` is temporarily disabled to return its own argument without braces.

```
31 \begingroup
32 \let\caption\@firstofone
33 \subfloat[#6]{#7}
34 \endgroup
35 }% subfig in a subfloatrow
36 {% subfig package, but not a subfig
```

`figure` and `table` are environments:

```
37 \@nameuse{#2}
38 #6
39
40 #7
41 \@nameuse{end#2}
42 }% subfig package, but not a subfig
43 }% assume subfig
44 }
```

Not used:

```
45 \newcommand*{\nocapbeside}{}
46 \newcommand*{\capbeside}{}
47 \newcommand*{\captop}{}
48 \newlength{\FBwidth}
49 \setlength{\FBwidth}{.3\linewidth}
50 \newlength{\FBheight}
51 \setlength{\FBheight}{2in}
52 \newcommand*{\useFCwidth}{}
53 \newcommand{\floatsetup}[2][{}]{
54 \newcommand{\thisfloatsetup}[1]{
55 \newcommand{\clearfloatsetup}[1]{
56 \newcommand*{\killfloatstyle}{}

```

`\newfloatcommand`     $\langle 1 \text{ command} \rangle$   $\langle 2 \text{ captyp} \rangle$   $[\langle 3 \text{ preamble} \rangle]$   $[\langle 4 \text{ default width} \rangle]$

Preamble and default width are ignored.

```
57 \NewDocumentCommand{\newfloatcommand}{m m o o}{%
58 \@namedef{#1}{
59 \floatbox{#2}
60 }
61 }
```

`\renewfloatcommand` [*⟨1 command⟩*] [*⟨2 captype⟩*] [*⟨3 preamble⟩*] [*⟨4 default width⟩*]

Preamble and default width are ignored.

```
62 \NewDocumentCommand{\renewfloatcommand}{m m o o}{%
63 \@namedef{#1}{%
64 \floatbox{#2}
65 }
66 }
```

`\ffigbox` [*⟨width⟩*] [*⟨height⟩*] [*⟨vposn⟩*] [*⟨caption commands⟩*] [*⟨contents⟩*]

```
67 \newfloatcommand{ffigbox}{figure}[\nocapbeside][[]]
```

`\ttabbox` [*⟨width⟩*] [*⟨height⟩*] [*⟨vposn⟩*] [*⟨caption commands⟩*] [*⟨contents⟩*]

```
68 \newfloatcommand{ttabbox}{table}[\capttop][\FBwidth]
```

`\fcapside` [*⟨width⟩*] [*⟨height⟩*] [*⟨vposn⟩*] [*⟨caption commands⟩*] [*⟨contents⟩*]

```
69 \newfloatcommand{fcapside}{figure}[\capbeside][[]]
```

Env `floatrow` [*⟨numfloats⟩*]

The row of floats is placed into a `<div>` of class `floatrow`.

```
70 \newenvironment*{floatrow}[1][2]
71 {%
72 \begin{LWR@setvirtualpage}*%
73 \BlockClass{floatrow}%
74 }
75 {
76 \endBlockClass%
77 \end{LWR@setvirtualpage}%
78 }
```

Keys for `\DeclareNewFloatType`:

```
79 \newcommand*{\LWR@frowkeyplacement}{}
80 \newcommand*{\LWR@frowkeyname}{}
81 \newcommand*{\LWR@frowkeyfileext}{}
82 \newcommand*{\LWR@frowkeywithin}{}
83 \newcommand*{\LWR@frowkeycapstyle}{}
84
85 \define@key{frowkeys}{placement}{}%
86 \define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}%
87 \define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}%
88 \define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}%
```

```
89 \define@key{frowkeys}{relatedcapstyle}{}%
```

```
\DeclareNewFloatType {<type>} {<options>}
```

Use `\listof{type}{Title}` to print a list of the floats.

```
90 \newcommand*\DeclareNewFloatType[2]{%
```

Reset key values:

```
91 \renewcommand*\LWR@frowkeyplacement}{}%
```

```
92 \renewcommand*\LWR@frowkeyname}{}%
```

```
93 \renewcommand*\LWR@frowkeyfileext}{}%
```

```
94 \renewcommand*\LWR@frowkeywithin}{}%
```

```
95 \renewcommand*\LWR@frowkeycapstyle}{}%
```

Read new key values:

```
96 \LWR@traceinfo{about to setkeys frowkeys}%
```

```
97 \setkeys{frowkeys}{#2}%
```

```
98 \LWR@traceinfo{finished setkeys frowkeys}%
```

Create a new float with optional [within]:

```
99 \ifthenelse{\equal{\LWR@frowkeywithin}{} }{%
```

```
100 {%
```

```
101 \DeclareFloatingEnvironment[
```

```
102 placement=\LWR@frowkeyplacement,
```

```
103 fileext=\LWR@frowkeyfileext
```

```
104]{#1}%
```

```
105 }%
```

```
106 {%
```

```
107 \DeclareFloatingEnvironment[
```

```
108 placement=\LWR@frowkeyplacement,
```

```
109 fileext=\LWR@frowkeyfileext,
```

```
110 within=\LWR@frowkeywithin
```

```
111]{#1}%
```

```
112 % \LWR@traceinfo{finished newfloat #1}%
```

```
113 }%
```

Rename the float if a name was given:

```
114 \ifthenelse{\equal{\LWR@frowkeyname}{} }{%
```

```
115 { }%
```

```
116 { }%
```

```
117 \SetupFloatingEnvironment{#1}{name={\LWR@frowkeyname}}%
```

```
118 }%
```

```
119 }
```

Not used:

```
120 \newcommand{\buildFBBOX}[2]{ }
```

```
121 \newcommand*\CenterFloatBoxes{}
```

```
122 \newcommand*\TopFloatBoxes{}
```

```
123 \newcommand*\BottomFloatBoxes{}
```

```
124 \newcommand*\PlainFloatBoxes{}
```

```
125
```

```
126 \newcommand{\capsubrowsettings}{}
```

```
127
```

```
128 \NewDocumentCommand{\RawFloats}{o o}{}
```

`\RawCaption`     $\langle text \rangle$

To be used inside a minipage or parbox.

```
129 \newcommand{\RawCaption}[1]{#1}
```

`\floatfoot`     $\langle text \rangle$

Places additional text inside a float, inside a CSS `<div>` of class `floatfoot`.

```
130 \NewDocumentCommand{\floatfoot}{s +m}{%
131 \begin{BlockClass}{floatfoot}
132 #2
133 \end{BlockClass}
134 }
```

Used to compute `\linewidth`.

```
135 \newbool{LWR@insubfloatrow}
136 \boolfalse{LWR@insubfloatrow}
```

Env `subfloatrow`     $[\langle num\_floats \rangle]$

```
137 \newenvironment*{subfloatrow}[1][2]
138 {
```

The row of floats is placed into a `<div>` of class `floatrow`:

```
139 \LWR@forcenewpage
140 \BlockClass{floatrow}
```

While inside the `floatrow`, `LWR@insubfloatrow` is set true, which tells `\floatbox` to use `\subfigure` or `\subtable`.

```
141 \begingroup%
142 \booltrue{LWR@insubfloatrow}%
143 }
144 {%
145 \endgroup%
146 \endBlockClass%
147 \boolfalse{LWR@insubfloatrow}%
148 }
```

File 162    **lwarp-fltrace.sty**

§ 268    Package    **fltrace**

Pkg `fltrace`    `fltrace` is ignored.

**for HTML output:**    1 \LWR@ProvidesPackageDrop{fltrace}[2018/01/08]

```
2 \def\tracefloats{}
```

---

```
3 \def\tracefloatsoff{}
4 \def\tracefloatvals{}
```

---

File 163 **lwarp-flushend.sty**

§ 269 Package **flushend**

*(Emulates or patches code by SIGITAS TOLUŠIS.)*

Pkg flushend flushend is ignored.

**for HTML output:** Discard all options for lwarp-flushend:

```
1 \LWR@ProvidesPackageDrop{flushend}[2017/03/27]

2 \newcommand*\flushend{}
3 \newcommand*\raggedend{}
4 \newcommand*\flushcolsend{}
5 \newcommand*\raggedcolsend{}
6 \newcommand*\atColsBreak}[1]{}
7 \newcommand*\atColsEnd}[1]{}
8 \newcommand*\showcolsendrule{}
```

---

File 164 **lwarp-fnbreak.sty**

§ 270 Package **fnbreak**

Pkg fnbreak fnbreak is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fnbreak}[2012/01/01]

```
2 \newcommand*\fnbreakverbose{}
3 \newcommand*\fnbreaknonverbose{}
4 \newcommand*\fnbreaklabel{}
5 \newcommand*\fnbreaknolabel{}
```

---

File 165 **lwarp-fncychap.sty**

§ 271 Package **fncychap**

*(Emulates or patches code by ULF A. LINDGREN.)*

Pkg fncychap fncychap is ignored.

**for HTML output:** Discard all options for lwarp-fncychap:

```
1 \LWR@ProvidesPackageDrop{fncychap}[2007/07/30]
```

---

```

2 \def\mghrulefill#1{}
3 \def\ChNameLowerCase{}
4 \def\ChNameUpperCase{}
5 \def\ChNameAsIs{}
6 \def\ChTitleLowerCase{}
7 \def\ChTitleUpperCase{}
8 \def\ChTitleAsIs{}
9 \newcommand{\ChRuleWidth}[1]{}
10 \newcommand{\ChNameVar}[1]{}
11 \newcommand{\ChNumVar}[1]{}
12 \newcommand{\ChTitleVar}[1]{}
13 \newcommand{\TheAlphaChapter}{}
14 \newcommand{\DOCH}{}
15 \newcommand{\DOTI}[1]{}
16 \newcommand{\DOTIS}[1]{}
17 \newlength{\mylen}
18 \newlength{\myhi}
19 \newlength{\px}
20 \newlength{\py}
21 \newlength{\pyy}
22 \newlength{\pxx}
23 \newlength{\RW}
24 \newcommand{\FmN}[1]{#1}
25 \newcommand{\FmTi}[1]{#1}

```

---

File 166 **lwarp-fnlineno.sty**

§ 272 Package **fnlineno**

Pkg fnlineno fnlineno is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fnlineno}[2011/01/07]

---

File 167 **lwarp-fnpara.sty**

§ 273 Package **fnpara**

Pkg fnpara fnpara is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fnpara}

---

File 168 **lwarp-fnpos.sty**

§ 274 Package **fnpos**

*(Emulates or patches code by HIROSHI NAKASHIMA.)*

Pkg fnpos fnpos is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{fnpos}[1999/07/14]

2 \newcommand*{\makeFNbottom}{}
3 \newcommand*{\makeFNmid}{}
4 \newcommand*{\makeFNbelow}{}
5 \newcommand*{\makeFNabove}{}

```

---

File 169 **lwarp-fontawesome.sty**

§ 275 Package **fontawesome**

*(Emulates or patches code by XAVIER DANAUX.)*

Pkg fontawesome fontawesome is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

 **poppler syntax warning** If using pdfL<sup>A</sup>T<sub>E</sub>X, *poppler* may issue a syntax warning regarding parsing a ligature component. X<sub>H</sub>L<sup>A</sup>T<sub>E</sub>X or LuaL<sup>A</sup>T<sub>E</sub>X may be used to avoid this warning.

In the following, the general strategy is to intercept `\symbol` and embed it inside a `lateximage`. These changes are done inside a local group.

For pdfL<sup>A</sup>T<sub>E</sub>X, the `alt` tag includes the icon (symbol) number. For X<sub>H</sub>L<sup>A</sup>T<sub>E</sub>X and LuaL<sup>A</sup>T<sub>E</sub>X, the `alt` tag is generic.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{fontawesome}[2016/05/15]

2 \LetLtxMacro\LWR@orig@symbol\symbol
3
4 \ifxetexorluatex
5
6 \newfontfamily{\LWR@orig@FA}{FontAwesome}
7
8 \newcommand*{\LWR@fontawesome@xelatex@symbol}[1]{%
9 \LWR@findcurrenttextcolor%
10 \begin{lateximage}*[icon][fontawesomexetex#1SZ\LWR@font@size{}CL\LWR@tempcolor]%
11 \csuse{\LWR@font@size}%
12 \LWR@orig@FA%
13 \LWR@orig@symbol{#1}%
14 \end{lateximage}%
15 }
16
17 \RenewDocumentCommand{\FA}{}{}%
18 \LetLtxMacro\symbol\LWR@fontawesome@xelatex@symbol%
19 }
20
21 \else
22
23 \newcommand*{\LWR@fontawesome@symbolX}[2]{%

```

```

24 \LWR@findcurrenttextcolor%
25 \begin{lateximage}*[icon #1][fontawesome#2#1SZ\LWR@font@size{}CL\LWR@tempcolor]%
26 \csuse{\LWR@font@size}%
27 \fontencoding{U}\fontfamily{fontawesome#2}\selectfont%
28 \LWR@orig@symbol{#1}%
29 \end{lateximage}%
30 }
31
32 \newcommand*\LWR@fontawesome@symbolone}[1]{%
33 \LWR@fontawesome@symbolX{#1}{one}%
34 }
35
36 \newcommand*\LWR@fontawesome@symboltwo}[1]{%
37 \LWR@fontawesome@symbolX{#1}{two}%
38 }
39
40 \newcommand*\LWR@fontawesome@symbolthree}[1]{%
41 \LWR@fontawesome@symbolX{#1}{three}%
42 }
43
44 \renewrobustcmd\FAone{%
45 \LetLtxMacro\symbol\LWR@fontawesome@symbolone%
46 }
47
48 \renewrobustcmd\FAtwo{%
49 \LetLtxMacro\symbol\LWR@fontawesome@symboltwo%
50 }
51
52 \renewrobustcmd\FAthree{%
53 \LetLtxMacro\symbol\LWR@fontawesome@symbolthree%
54 }
55 \fi

```

---

File 170 **lwarp-fontawesome5.sty**

§ 276 Package **fontawesome5**

*(Emulates or patches code by MARCEL KRÜGER.)*

Pkg fontawesome5 fontawesome5 is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

The alt tag has the name of the icon.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{fontawesome5}[2018/07/27]
2 \ExplSyntaxOn
3 \cs_set:Nn\fontawesome_use_icon:nn{
4 \LWR@findcurrenttextcolor
5 \cs_if_exist:cTF{c__fontawesome_slot_#2_tl}{
6 \begin{lateximage}*[#2][fontawesome5#1SZ\LWR@font@size{}CL\LWR@tempcolor]
7 \csuse{\LWR@font@size}

```

---

```

8 \exp_last_unbraced:Nv
9 __fontawesome_icon_at:nnnn
10 {c__fontawesome_slot_#2_tl}
11 {#1}{#2}
12 \end{lateximage}
13 }{
14 \msg_error:nxxx{fontawesome5}{icon-not-found}{#2}{#1}
15 }
16 }
17 \ExplSyntaxOff

```

---

File 171 **lwarp-fontaxes.sty**

§ 277 Package **fontaxes**

*(Emulates or patches code by ANDREAS BÜHMANN, MICHAEL UMMELS.)*

Pkg fontaxes fontaxes is emulated for HTML, and used as-is for print output.

Functionality for small caps is in the `lwarp` core. Swashes and figure styles are ignored for HTML.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{fontaxes}[2014/03/23]

2 \ifdef{\LWR@HTML@swshape}{}{% duplicated by nfssect-cfr
3 \newcommand{\LWR@HTML@swshape}{}
4 \LWR@formatted{swshape}
5
6 \newrobustcmd{\LWR@HTML@textsw}[1]{#1}
7 \LWR@formatted{textsw}
8
9 \FilenameNullify{%
10 \LetLtxMacro\swshape\@empty%
11 \LetLtxMacro\textsw\firstofone%
12 }
13 }

```

---

File 172 **lwarp-fontenc.sty**

§ 278 Package **fontenc**

Pkg fontenc If using pdfL<sup>A</sup>T<sub>E</sub>X, `lwarp` used to require `fontenc` be loaded before `lwarp`, but now `lwarp` itself loads `\fontenc` with T1 encoding, which `lwarp` requires. `fontenc` is now allowed to be loaded with another encoding after `lwarp`.

`lwarp-fontenc` is no longer necessary, but is still provided to overwrite older versions.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{fontenc}[2017/04/05]

```

File 173 **lwarp-footmisc.sty**

§ 279 Package **footmisc**

*(Emulates or patches code by ROBIN FAIRBAIRNS.)*

Pkg footmisc **footmisc** is emulated.

**lwarp** incidentally happens to emulate the stable option.

```
1 \LWR@ProvidesPackageDrop{footmisc}[2011/06/06]
```

Some nullified commands:

```
2 \newcommand{\footnotelayout}{}
3 \newcommand{\setfnsymbol}[1]{}
4 \NewDocumentCommand{\DefineFNSymbols}{s m o m}{}
5
6 \newdimen\footnotemargin
7 \footnotemargin1.8em\relax
8
9 \newcommand*\hangfootparskip{0.5\baselineskip}
10 \newcommand*\hangfootparindent{0em}%
11
12 \let\pagefootnoterule\footnoterule
13 \let\mpfootnoterule\footnoterule
14 \def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}
15
16 \providecommand*\multiplefootnotemarker}{3sp}
17 \providecommand*\multfootsep}{,}
```

Using **cleveref**. `\labelcref` only prints the number of the object, not its type.

```
18 \providecommand*\footref}[1]{\labelcref{#1}}
```

The following work as-is:

```
19 \newcommand\mpfootnotemark{%
20 \@ifnextchar[%
21 \@xmpfootnotemark%
22 {%
23 \stepcounter\@mpfn%
24 \protected@xdef\@thefnmark{\thempfn}%
25 \@footnotemark%
26 }%
27 }
28 \def\@xmpfootnotemark[#1]{%
29 \begingroup%
30 \csname c@\@mpfn\endcsname #1\relax%
31 \unrestored@protected@xdef\@thefnmark{\thempfn}%
```

```

32 \endgroup%
33 \@footnotemark%
34 }

```

---

File 174 **lwarp-footnote.sty**

§ 280 Package **footnote**

*(Emulates or patches code by MARK WOODING.)*

Pkg footnote footnote is used with minor patches.

**for HTML output:** 1 \LWR@ProvidesPackagePass{footnote}[1997/01/28]

Removed print-version formatting:

```

2 \def\fn@startnote{%
3 % \parboxrestore%
4 \protected@edef\@currentlabel{\csname p@\@mpfn\endcsname\@thefnmark}%
5 % \color@begingroup% *** conflicts with lwarp
6 }
7
8 % \let\fn@endnote\color@endgroup% *** conflicts with lwarp
9 \def\fn@endnote{%
10 \LWR@htmltagc{/\LWR@tagregularparagraph}%
11 \LWR@orignewline%
12 }

```

Removed print-version formatting:

```

13 \def\fn@startfntext{%
14 \setbox\z@\vbox\bgroup%
15 \fn@startnote%
16 \ignorespaces%
17 }

```

Removed print-version formatting, added closing paragraph tag:

```

18 \def\fn@endfntext{%
19 \LWR@htmltagc{/\LWR@tagregularparagraph}%
20 \LWR@orignewline%
21 \egroup%
22 \begingroup%
23 \let\@makefntext\@empty%
24 \let\@finalstrut\@gobble%
25 \LetLtxMacro\rule\@gobbletwo% *8* also the optional argument?
26 \@footnotetext{\unvbox\z@}%
27 \endgroup%
28 }

```

These have been redefined, so re-\let them again:

```
29 \let\endfootnote\fn@endfntext
30 \let\endfootnotetext\endfootnote
```

---

File 175 **lwarp-footnotebackref.sty**

§ 281 Package **footnotebackref**

Pkg footnotebackref footnotebackref is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{footnotebackref}[2012/07/01]

---

File 176 **lwarp-footnotehyper.sty**

§ 282 Package **footnotehyper**

Pkg footnotehyper footnotehyper is a hyperref-safe version of footnote. For lwarp, footnotehyper is emulated.

**for HTML output:** Discard all options for lwarp-footnotehyper:

```
1 \RequirePackage{footnote}
2 \LWR@ProvidesPackageDrop{footnotehyper}[2018/01/23]
```

---

File 177 **lwarp-footnoterange.sty**

§ 283 Package **footnoterange**

*(Emulates or patches code by H.-MARTIN MÜNCH.)*

Pkg footnoterange footnoterange is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{footnoterange}[2012/02/17]

```
2 \csletcs{footnoterange}{footnoterange*}
3 \csletcs{endfootnoterange}{endfootnoterange*}
```

---

File 178 **lwarp-footnpag.sty**

§ 284 Package **footnpag**

Pkg footnpag footnpag is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{footnpag}

File 179 **lwarp-foreign.sty**

§ 285 Package **foreign**

*(Emulates or patches code by PHILIP G. RATCLIFFE.)*

Pkg foreign foreign is patched for use by lwarp.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{foreign}[2012/09/25]
2 \renewcommand\foreignabbrfont{\emph}
```

File 180 **lwarp-forest.sty**

§ 286 Package **forest**

*(Emulates or patches code by SAŠO ŽIVANOVIĆ.)*

Pkg forest forest is patched for use by lwarp.

 **\Forest\*** The starred version of the macro `\Forest*` is not supported. `lwarp` encases each `lateximage` in an environment, so the global results of the starred `\Forest*` are lost.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{forest}[2017/07/14]
2 \BeforeBeginEnvironment{forest}{%
3 \begin{lateximage}[-forest-~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{forest}{\end{lateximage}}
7
8 \RenewDocumentCommand{\Forest}{s D(){} m}{%
9 \forest@config{#2}%
10 \IfBooleanTF{#1}{%
11 \PackageError{lwarp-forest}%
12 {\protect\Forest* is not supported}%
13 {Lwarp uses an environment for images,\MessageBreak
14 but \protect\Forest* cannot work in an environment.}%
15 \let\forest@next\forest@env%
16 }{\let\forest@next\forest@group@env}%
17 \begin{lateximage}[-forest-~\PackageDiagramAltText] lwarp
18 \forest@next{#3}%
19 \end{lateximage}%
20 }
```

---

File 181 **lwarp-fouridx.sty**

§ 287 Package **fouridx**

(Emulates or patches code by STEFAN KARRMANN.)

Pkg fouridx fouridx works as-is with SVG math, and is emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{fouridx}[2013/11/21]
2 \begin{warpMathJax}
3 \CustomizeMathJax{%
4 \newcommand{\fourIdx}[5]{%
5 \vphantom{#5}^{\hphantom{#2}#1}_{\hphantom{#1}#2}{#5}^{\#3}_{#4}%
6 }%
7 }
8 \end{warpMathJax}

```

---

File 182 **lwarp-fourier.sty**

§ 288 Package **fourier**

(Emulates or patches code by MICHEL BOVANI.)

Pkg fourier fourier is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except `sloped` and `upright` are honored for Greek characters, but MATHJAX cannot yet honor these for Latin characters.

The dedicated macros for upright and italic Greek letters do work correctly.

SVG math should appear the same as the printed output.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{fourier}[2020/03/03]
2
3 \LWR@infoprocessingmathjax{fourier}

4 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
5
6 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
7
8 \begin{warpMathJax}
9
10 \@ifpackagewith{fourier}{sloped}
11 {
12 \LWR@mathjax@addgreek@l@up{other}{}
13 \LWR@mathjax@addgreek@u@it*{other}{}
14 }% sloped

```

```

15 {% not sloped
16 \@ifpackagewith{fourier}{upright}
17 {% upright option
18 \LWR@mathjax@addgreek@l@up{}{}
19 \LWR@mathjax@addgreek@u@up*{}{}
20 \LWR@mathjax@addgreek@l@it{other}{}
21 \LWR@mathjax@addgreek@u@it*{other}{}
22 }
23 {% neither sloped nor upright
24 \LWR@mathjax@addgreek@l@up{other}{}
25 \LWR@mathjax@addgreek@u@it*{other}{}
26 }
27 }
28
29 \CustomizeMathJax{\newcommand{\othergreek}[1]{#1}}
30 \CustomizeMathJax{\let\varvarrho\varrho}
31 \CustomizeMathJax{\let\varvarpi\varpi}
32 \CustomizeMathJax{\let\othervarvarpi\othervarpi}
33 \CustomizeMathJax{\let\othervarvarrho\othervarrho}
34 \CustomizeMathJax{\let\varpartialdiff\partial}

```

lwarp\_mathjax.txt adds `\left/\right` support for delimiters.

```

35 \CustomizeMathJax{\let\llbracket\lBrack}
36 \CustomizeMathJax{\let\rrbracket\rBrack}
37 \CustomizeMathJax{\let\dblbrackleft\lBrack}
38 \CustomizeMathJax{\let\dblbrackright\rBrack}
39
40 \CustomizeMathJax{\let\VERT|}
41
42 \CustomizeMathJax{\newcommand{\parallelslant}{\mathrel{\unicode{x02AFD}}}}
43 \CustomizeMathJax{\newcommand{\thething}{\mathord{\unicode{x1F60E}}}}
44 \CustomizeMathJax{\newcommand{\nparallelslant}{%
45 \mathrel{\LWROverlaysymbols{-}{\unicode{x02AFD}}}%
46 }}
47 \CustomizeMathJax{\newcommand{\xswordsup}{\mathord{\unicode{x2694}}}}
48 \CustomizeMathJax{\newcommand{\xswordtdown}{\mathord{\unicode{x2694}}}}% up
49 \CustomizeMathJax{\newcommand{\notowns}{\mathrel{\unicode{x220C}}}}
50
51 \CustomizeMathJax{\newcommand{\iintop}{\mathop{\unicode{x222C}}\limits}}
52 \CustomizeMathJax{\newcommand{\iiintop}{\mathop{\unicode{x222D}}\limits}}
53 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
54 \CustomizeMathJax{\let\oiintop\oiint}
55 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x2230}}\limits}}
56 \CustomizeMathJax{\let\oiintop\oiint}
57 \CustomizeMathJax{\newcommand{\slashint}{\mathop{\unicode{x2A0D}}\limits}}
58 \CustomizeMathJax{\let\slashintop\slashint}
59
60 \CustomizeMathJax{\let\overgroup\overparen}
61 \CustomizeMathJax{\let\wideparen\overparen}
62 \CustomizeMathJax{\let\widearc\overparen}
63 \CustomizeMathJax{\let\wideOarc\overrightarrow}
64 \CustomizeMathJax{\newcommand{\widering}[1]{\stackrel{\unicode{x2218}}{\overgroup{#1}}}}
65
66 \end{warpMathJax}

```

File 183 **lwarp-framed.sty**

§ 289 Package **framed**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg framed **framed** is supported and patched by lwarp.

**for HTML output:** Accept all options for lwarp-framed:

```

1 \LWR@ProvidesPackagePass{framed}[2011/10/22]
2 \AtBeginDocument{\RequirePackage{xcolor}}% for \convertcolorspec

3
4 \renewenvironment{framed}{%
5 \LWR@forcenewpage
6 \BlockClass{framed}%
7 }
8 {\endBlockClass}
9
10 \renewenvironment{oframed}{%
11 \LWR@forcenewpage
12 \BlockClass{framed}%
13 }
14 {\endBlockClass}
15
16
17 \renewenvironment{shaded}{%
18 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
19 \LWR@forcenewpage
20 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
21 }
22 {\endBlockClass}
23
24 \renewenvironment{shaded*}{%
25 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
26 \LWR@forcenewpage
27 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
28 }
29 {\endBlockClass}
30
31
32 \renewenvironment{leftbar}{%
33 \LWR@forcenewpage
34 \BlockClass{framedleftbar}
35 \def\FrameCommand{%
36 \MakeFramed {}
37 }%
38 {\endMakeFramed\endBlockClass}
39
40
```

```

41 \renewenvironment{snugshade}{%
42 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
43 \LWR@forcenewpage
44 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
45 }
46 {\endBlockClass}
47
48 \renewenvironment{snugshade*}{%
49 \convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
50 \LWR@forcenewpage
51 \BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
52 }
53 {\endBlockClass}
54
55 \let\oframed\framed
56 \let\endoframed\endframed
57
58
59 \RenewEnviron{titled-frame}[1]{%
60 \CustomFBox{#1}{0pt}{0pt}{0pt}{0pt}{\BODY}
61 }

\CustomFBox {<toptitle>} {<bottitle>} {<thicknesstop>} {<bottom>} {<left>} {<right>}
{<text contents>}

62 \renewcommand{\CustomFBox}[7]{%
63 \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
64 \LWR@forcenewpage
65 \begin{BlockClass}[border: 3px solid \LWR@origpound\LWR@tempcolor]{framed}%
66 \ifthenelse{\isempty{#1}}{0pt}{% not empty
67 \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
68 \textcolor{TFTitleColor}{\textbf{#1}}%
69 \end{BlockClass}
70 }% not empty
71
72 #7
73
74 \ifthenelse{\isempty{#2}}{0pt}{% not empty
75 \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
76 \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
77 \textcolor{TFTitleColor}{\textbf{#2}}%
78 \end{BlockClass}
79 }% not empty
80 \end{BlockClass}
81 }

\TitleBarFrame [<marker>] {<title>} {<contents>}

82 \renewcommand\TitleBarFrame[3][[]
83 \CustomFBox
84 {#2}{%
85 \fboxrule\fboxrule\fboxrule\fboxrule
86 {#3}%
87 }

```

```

88 \renewcommand{\TF@Title}[1]{#1}

MakeFramed {<settings>}

89 \let\MakeFramed\relax
90 \let\endMakeFramed\relax
91
92 \NewEnviron{MakeFramed}[1]{%
93 \FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
94 }

\fb@put@frame {<frame cmd no split>} {<frame cmd split>}

95 \renewcommand*\fb@put@frame[2]{%
96 \relax%
97 \@tempboxa%
98 }

```

---

File 184 **lwarp-ftcap.sty**

§ 290 Package **ftcap**

Pkg ftcap ftcap is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{ftcap}

---

File 185 **lwarp-ftnright.sty**

§ 291 Package **ftnright**

Pkg ftnright ftnright is ignored.

**for HTML output:** Discard all options for lwarp-ftnright:

1 \LWR@ProvidesPackageDrop{ftnright}[2014/10/28]

---

File 186 **lwarp-fullminipage.sty**

§ 292 Package **fullminipage**

Pkg fullminipage fullminipage is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{fullminipage}[2014/07/06]

2 \newenvironment{fullminipage}[1][{}]{}

---

File 187 **lwarp-fullpage.sty**

§ 293 Package **fullpage**

Pkg fullpage fullpage is ignored.

**for HTML output:** Discard all options for lwarp-fullpage:

```
1 \LWR@ProvidesPackageDrop{fullpage}[1994/06/01]
```

---

File 188 **lwarp-fullwidth.sty**

§ 294 Package **fullwidth**

*(Emulates or patches code by MARCO DANIEL.)*

Pkg fullwidth fullwidth is emulated.

A minipage is used, of no HTML width.

**for HTML output:** `1 \LWR@ProvidesPackageDrop{fullwidth}[2011/11/18]`

```
2 \newenvironment*{fullwidth}[1][]{%
3 \minipagefullwidth%
4 \minipage{\linewidth}%
5 }
6 {%
7 \endminipage%
8 }
```

---

File 189 **lwarp-fvextra.sty**

§ 295 Package **fvextra**

*(Emulates or patches code by GEOFFREY M. POORE.)*

Pkg fvextra fvextra is patched for use by lwarp.

**for HTML output:** `1 \LWR@ProvidesPackagePass{fvextra}[2019/02/04]`

Ignored are highlight, showtabs, obeytabs, tab, tabcolor. Also ignored are all options regarding line breaking except breaklines, which is emulated as true.

tabsize is honored.

If line numbers on the right side are used along with breaklines, the line numbers will not be aligned.

```

2
3 \define@booleankey{FV}{obeytabs}%
4 % {\let\FV@ObeyTabsInit\FV@ObeyTabsInit}%
5 {\let\FV@ObeyTabsInit\relax}
6 {\let\FV@ObeyTabsInit\relax}
7
8 \define@key{FV}{tabcolor}%
9 {}
10
11 \define@key{FV}{tab}{=}
12
13 \define@booleankey{FV}{showtabs}%
14 % {\def\FV@TabChar{\FV@TabColor{\FancyVerbTab}}}%
15 {\let\FV@TabChar\relax}
16 {\let\FV@TabChar\relax}
17
18 \newbool{LWR@FV@breaklines}
19
20 \define@booleankey{FV}{breaklines}%
21 {\FV@BreakLinesfalse}
22 \booltrue{LWR@FV@breaklines}
23 \let\FV@ListProcessLine\FV@ListProcessLine@NoBreak}
24 {\FV@BreakLinesfalse}
25 \boolfalse{LWR@FV@breaklines}
26 \let\FV@ListProcessLine\FV@ListProcessLine@NoBreak}
27 % \fvset{breaklines}
28
29 \define@key{FV}{breakanywheresymbolpre}{\def\FancyVerbBreakAnywhereSymbolPre{}}
30 \fvset{breakanywheresymbolpre={}}
31
32 \define@key{FV}{breakanywheresymbolpost}{\def\FancyVerbBreakAnywhereSymbolPost{}}
33 \fvset{breakanywheresymbolpost={}}
34
35 \define@key{FV}{breakbeforesymbolpre}{\def\FancyVerbBreakBeforeSymbolPre{}}
36 \fvset{breakbeforesymbolpre={}}
37
38 \define@key{FV}{breakbeforesymbolpost}{\def\FancyVerbBreakBeforeSymbolPost{}}
39 \fvset{breakbeforesymbolpost={}}
40
41 \define@key{FV}{breakaftersymbolpre}{\def\FancyVerbBreakAfterSymbolPre{}}
42 \fvset{breakaftersymbolpre={}}
43
44 \define@key{FV}{breakaftersymbolpost}{\def\FancyVerbBreakAfterSymbolPost{}}
45 \fvset{breakaftersymbolpost={}}
46
47 \define@key{FV}{breaksymbolleft}{\def\FancyVerbBreakSymbolLeft{}}
48
49 \define@key{FV}{breaksymbol}{\fvset{breaksymbolleft={}}}
50
51 \fvset{breaksymbolleft={}}
52
53 \define@key{FV}{breaksymbolright}{\def\FancyVerbBreakSymbolRight{}}

```

```

54 \fvset{breaksymbolright={}}
55
56 \def\FV@ListProcessLine@NoBreak#1{%
57 % \hbox to \hsize{%
58 % \kern\leftmargin
59 % \hbox to \linewidth{%
60 % \FV@LeftListNumber%
61 % \FV@LeftListFrame%
62 % \FancyVerbFormatLine{%
63 % \FancyVerbHighlightLine{%
64 % \FV@ObeyTabs{\FancyVerbFormatText{#1}}}%\hss
65 % \FV@RightListFrame%
66 % \FV@RightListNumber%
67 % }%
68 % \hss}%
69 \null\par% lwarp
70 }
71
72
73 \newcommand*\LWR@FV@linethensep{%
74 \ifbool{LWR@FV@breakLines}%
75 {\theFancyVerbLine\kern\FV@NumberSep}%
76 {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}%
77 }
78
79 \newcommand*\LWR@FV@sephenline{%
80 \ifbool{LWR@FV@breakLines}%
81 {\kern\FV@NumberSep\theFancyVerbLine}%
82 {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}%
83 }
84
85 \xpatchcmd{\FV@Numbers@left}
86 {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
87 {\LWR@FV@linethensep}
88 {}
89 {\LWR@patcherror{fvextra}{FV@Numbers@left A}}
90
91 \xpatchcmd{\FV@Numbers@left}
92 {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
93 {\LWR@FV@linethensep}
94 {}
95 {\LWR@patcherror{fvextra}{FV@Numbers@left B}}
96
97 \xpatchcmd{\FV@Numbers@left}
98 {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
99 {\LWR@FV@linethensep}
100 {}
101 {\LWR@patcherror{fvextra}{FV@Numbers@left C}}
102
103 \xpatchcmd{\FV@Numbers@right}
104 {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
105 {\LWR@FV@sephenline}
106 {}
107 {\LWR@patcherror{fvextra}{FV@Numbers@right A}}
108

```

```

109 \xpatchcmd{\FV@Numbers@right}
110 {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
111 {\LWR@FV@sephenline}
112 {}
113 {\LWR@patcherror{fvextra}{FV@Numbers@right B}}
114
115 \xpatchcmd{\FV@Numbers@right}
116 {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
117 {\LWR@FV@linethensep}
118 {}
119 {\LWR@patcherror{fvextra}{FV@Numbers@right C}}
120
121 \xpatchcmd{\FV@Numbers@both}
122 {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
123 {\LWR@FV@linethensep}
124 {}
125 {\LWR@patcherror{fvextra}{FV@Numbers@both A}}
126
127 \xpatchcmd{\FV@Numbers@both}
128 {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
129 {\LWR@FV@linethensep}
130 {}
131 {\LWR@patcherror{fvextra}{FV@Numbers@both B}}
132
133 \xpatchcmd{\FV@Numbers@both}
134 {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
135 {\LWR@FV@linethensep}
136 {}
137 {\LWR@patcherror{fvextra}{FV@Numbers@both C}}
138
139 \xpatchcmd{\FV@Numbers@both}
140 {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
141 {\LWR@FV@sephenline}
142 {}
143 {\LWR@patcherror{fvextra}{FV@Numbers@both D}}
144
145 \xpatchcmd{\FV@Numbers@both}
146 {\hbox to\z@{\kern\FV@NumberSep\theFancyVerbLine\hss}}
147 {\LWR@FV@sephenline}
148 {}
149 {\LWR@patcherror{fvextra}{FV@Numbers@both E}}
150
151 \xpatchcmd{\FV@Numbers@both}
152 {\hbox to\z@{\hss\theFancyVerbLine\kern\FV@NumberSep}}
153 {\LWR@FV@linethensep}
154 {}
155 {\LWR@patcherror{fvextra}{FV@Numbers@both F}}

```

---

File 190 **lwarp-fwlw.sty**

§ 296 Package **fwlw**

Pkg fwlw **fwlw** is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{fwlw}

2 \newbox\FirstWordBox \global\setbox\FirstWordBox\hbox{}
3 \newbox\NextWordBox \global\setbox\NextWordBox\hbox{}
4 \newbox\LastWordBox \global\setbox\LastWordBox\hbox{}
5 \def\ps@fwlwhead{}
6 \def\ps@NextWordFoot{}

```

---

File 191 **lwarp-gensymb.sty**

§ 297 Package **gensymb**

*(Emulates or patches code by WALTER SCHMIDT.)*

Pkg gensymb gensymb works as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{gensymb}[2003/07/02]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\degree}{\mathrm{^\circ}}}
4 \CustomizeMathJax{\newcommand{\celsius}{\unicode{x2103}}}
5 \CustomizeMathJax{\newcommand{\perthousand}{\unicode{x2030}}}
6 \CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
7 \CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
8 \end{warpMathJax}

```

---

File 192 **lwarp-gentombow.sty**

§ 298 Package **gentombow**

Pkg gentombow gentombow is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{gentombow}[2018/05/17]

2 \newcommand{\settombowbanner}[1]{}
3 \newcommand{\settombowbannerfont}[1]{}
4 \newcommand{\settombowwidth}[1]{}
5 \newcommand{\settombowbleed}[1]{}
6 \newcommand{\settombowcolor}[1]{}

```

---

File 193 **lwarp-geometry.sty**

§ 299 Package **geometry**

*(Emulates or patches code by HIDEO UMEKI.)*

Pkg geometry geometry is preloaded by lwarp, but must be nullified as seen by the user's source code.

for HTML output: Discard all options for lwarp-geometry:

```
1 \LWR@ProvidesPackageDropA{geometry}{2018/04/16}
```

If geometry is never loaded by the user, it will be loaded by lwarp \AtBeginDocument. If this is the case, the page layout should not be changed but the user macros should still be nullified.

```
2 \ifbool{LWR@allowanothergeometry}{%
```

Assign and set the selected geometry with reset prepended. \AtEndPreamble lwarp will save this, then set its own geometry.

```
3 \edef\LWR@tempone{reset, \optionlist{\@currname.\@current}}%
4 \expandafter\LWR@origgeometry\expandafter{\LWR@tempone}%
5 }{}% LWR@allowanothergeometry
```

The user-level commands are nullified:

```
6 \renewcommand*\geometry[1]{}
7 \renewcommand*\newgeometry[1]{}
8 \renewcommand*\restoregeometry{}
9 \renewcommand*\savegeometry[1]{}
10 \renewcommand*\loadgeometry[1]{}

```

File 194 **lwarp-ghsystem.sty**

§ 300 Package **ghsystem**

(Emulates or patches code by CLEMENS NIEDERBERGER.)

Pkg ghsystem ghsystem is patched for use by lwarp.

△ \ghspic images Images must be provided in svg format, unless jpg is specified. It is recommended to create a local images directory, copy into it the relevant PDF ghsystem images, and then convert them with

```
Enter ⇒ Lwarpmk pdftosvg images/*.pdf
```

for HTML output: 1 \LWR@ProvidesPackagePass{ghsystem}[2020/02/17]

```
2 \ExplSyntaxOn
3
4 \cs_set_protected:Npn \ghsystem_filler:n #1
5 { \emph { \textless #1 \textgreater } }
6
7 \cs_set_protected:Npn \ghsystem_pic:n #1
8 {
9 __ghsystem_includegraphics:xn

```

```

10 {
11 % scale = \fp_to_tl:N \l__ghsystem_picture_scale_fp
12 width = 1.25cm
13 \exp_not:V \l__ghsystem_picture_includegraphics_tl
14 }
15 { ghsystem_ #1 . \l__ghsystem_picture_type_tl }
16 }
17
18 \ExplSyntaxOff

```

---

File 195 **lwarp-gindex.sty**

§ 301 Package **gindex**

*(Emulates or patches code by JAVIER BEZOS.)*

Pkg gindex gindex is patched for use by lwarp.

See section [8.6.15](#).

**for HTML output:** 1 \LWR@ProvidesPackagePass{gindex}[2019/10/07]

Set the index page and range separators. These are set \AtBeginDocument to allow the user to change them. They are then protected so that the lwarp core looks for the tokens instead of their expanded contents, since the \*.ind files will contain \indexpagessep and \indexrangesep instead of their literal contents. Finally, lwarp is told of the gindex macros.

```

2 \AtBeginDocument{
3 \robustify{\indexpagessep}
4 \robustify{\indexrangesep}
5 \renewcommand*\IndexPageSeparator{\indexpagessep}
6 \renewcommand*\IndexRangeSeparator{\indexrangesep}
7 }

```

\hyperindexref is added:

```

8 \def\addindexitem#1#2{%
9 \indexflushitem
10 \gix@getspecial#1\indexspecial\indexspecial\@@\indexitem{\hyperindexref{#2}}
11
12 \def\addindexsubitem#1#2{%
13 \stepcounter{indexsubitems}%
14 \gix@getspecial#1\indexspecial\indexspecial\@@\indexsubitem{\hyperindexref{#2}}
15
16 \def\addindexsubsubitem#1#2{%
17 \gix@getspecial#1\indexspecial\indexspecial\@@\indexsubsubitem{\hyperindexref{#2}}

```

Uses a <div> of class indexheading:

```

18 \renewcommand\indexheading[1]{%
19 \begin{BlockClass}{indexheading}

```

```

20 \MakeUppercase{#1}%
21 \end{BlockClass}
22 }

```

---

File 196 **lwarp-gloss.sty**

§ 302 Package **gloss**

(Emulates or patches code by JOSE LUIS DÍAZ, JAVIER BEZOS.)

Pkg gloss gloss is patched for use by lwarp.

To process the HTML glossary:

```

bibtex <projectname>_html.gls

```

**for HTML output:** 1 \LWR@ProvidesPackagePass{gloss}[2002/07/26]

\BaseJobname is added to the label in case xr or xr-hyper are used.

```

2 \xpatchcmd{\gls@gloss@iii}
3 {\thepage}
4 {\theLWR@previousautopagelabel}
5 {}
6 {\LWR@patcherror{gloss}{gls@gloss@iii}}
7
8 \def\gls@page@i#1#2{%
9 \endgroup%
10 \global\@namedef{gls@p#1}{\nameref{\BaseJobname-autopage-#2}}}%

```

---

File 197 **lwarp-glossaries.sty**

§ 303 Package **glossaries**

(Emulates or patches code by NICOLA L.C. TALBOT.)

Pkg glossaries *lwarp*mk has the commands **lwarp**mk **printglossary** and **lwarp**mk **htmlglossary**, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

Opt GlossaryCmd  
 Default: *makeglossaries*

Opt [*lwarp*mk] **printglossary** The shell command to execute is set by the *lwarp* option **GlossaryCmd**, which defaults to **makeglossaries**. The print or HTML glossary filename is appended to this command.

 **makeglossaries not found** In some situations it may be required to modify the default command, such as to add the **perl** command in front:

```

\usepackage[
 GlossaryCmd={perl makeglossaries},
] {lwarp}

```

*xindy* language To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
 GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and toc options The glossaries may be placed in a numbered or unnumbered section, given a toc entry, and placed inline or on their own HTML page:

**Numbered section, on its own HTML page:**

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
...
\printglossaries
```

**Unnumbered section, inline with the current HTML page:**

```
\usepackage[xindy,toc]{glossaries}
...
\printglossaries
```

**Unnumbered section, on its own HTML page:**

```
\usepackage[xindy,toc]{glossaries}
...
\ForceHTMLPage
\printglossaries
```

△ **glossary style** The default `style=item` option for glossaries conflicts with *lwarp*, so the style is forced to `index` instead.

△ **number list** The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

**for HTML output:**

```
1 \PassOptionsToPackage{xindy}{glossaries}
2
3 \LWR@ProvidesPackagePass{glossaries}[2018/07/23]
4
5 \setupglossaries{nonumberlist}
6 \setglossarystyle{index}
```

Patched to fix toc pointing to the previous page:

```
7 \renewcommand*{\@p@glossarysection}[2]{%
8 \glsclearpage
9 \LWR@phantomsection
10 \ifdefempty\@glossarysecstar
11 {%
12 \csname\@glossarysec\endcsname{#2}%
13 }%
14 {%
```

In the original, the toc entry was made before the section, thus linking to the phantomsection in the printed version, but for HTML, this caused the link to point to the page before the glossaries, which could be a different HTML file. Here, the toc entry is made after the section is created:

```

15 \csname\@glossarysec\endcsname*{#2}%
16 \@gls@toc{#1}{\@glossarysec}% Moved after the previous line.
17 }%
18 \@glossaryseclabel
19 }

```

lwarp's sectioning commands cannot handle robust macros when splitting HTML into named filenames. glossaries uses \translate in sectioning names, and \translate is robust and cannot be expanded. The following pre-expands the translations at this moment, making use of \translatelet.

```

20 \newcommand*\LWR@comp@glossaryname{\translate{Glossary}}
21
22 \ifdefstrequal{\glossaryname}{\LWR@comp@glossaryname}{
23 \translatelet\LWR@translatetemp{Glossary}
24 \edef\glossaryname{\LWR@translatetemp}
25 }{}
26
27 \newcommand*\LWR@comp@acronymname{\translate{Acronym}}
28
29 \ifdefstrequal{\acronymname}{\LWR@comp@acronymname}{
30 \translatelet\LWR@translatetemp{Acronym}
31 \edef\acronymname{\LWR@translatetemp}
32 }{}
33
34 \newcommand*\LWR@comp@glsymbolsgroupname{\translate{Symbols (glossaries)}}
35
36 \ifdefstrequal{\glsymbolsgroupname}{\LWR@comp@glsymbolsgroupname}{
37 \translatelet\LWR@translatetemp{Symbols (glossaries)}
38 \edef\glsymbolsgroupname{\LWR@translatetemp}
39 }{}
40
41 \newcommand*\LWR@comp@glsnumbersgroupname{\translate{Numbers (glossaries)}}
42
43 \ifdefstrequal{\glsnumbersgroupname}{\LWR@comp@glsnumbersgroupname}{
44 \translatelet\LWR@translatetemp{Numbers (glossaries)}
45 \edef\glsnumbersgroupname{\LWR@translatetemp}
46 }{}

```

---

File 198 **lwarp-gmeometric.sty**

§ 304 Package **gmeometric**

Pkg gmeometric gmeometric is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{gmeometric}[2008/11/22]
2 \RequirePackageWithOptions{geometry}

```

File 199 **lwarp-graphics.sty**

§ 305 Package **graphics**

*(Emulates or patches code by D. P. CARLISLE.)*

Pkg graphics graphics is emulated.

**for HTML output:** 1 \LWR@ProvidesPackagePass{graphics}[2020/08/30]

§ 305.1 **Graphics extensions**

\DeclareGraphicsExtensions  $\{\langle list \rangle\}$

\AtBeginDocument allow SVG files instead of PDF:

```
2 \AtBeginDocument{
3 \DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}
4 \DeclareGraphicsRule{.svg}{svg}{.svg}{}
5 \DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
6 }
```

Inside a lateximage, allow PDF instead of SVG:

```
7 \ifpdf
8 \appto\LWR@restoreorigformatting{%
9 \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
10 }
11 \else% \ifpdf
12 \ifXeTeX
13 \appto\LWR@restoreorigformatting{%
14 \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
15 }
16 \else
17 \appto\LWR@restoreorigformatting{%
18 \DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
19 }
20 \fi
21 \fi
```

## § 305.2 Length conversions and graphics options



whitespace

A scaled image in L<sup>A</sup>T<sub>E</sub>X by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

Used to store the user's selected dimensions and HTML class.

The class defaults to “inlineimage” unless changed by a `class=xyx` option.

```

22 \newlength{\LWR@igwidth}
23 \newlength{\LWR@igheight}
24 \newcommand*\LWR@igwidthstyle{}
25 \newcommand*\LWR@igheightstyle{}
26 \newcommand*\LWR@igorigin{}
27 \newcommand*\LWR@igangle{}
28 \newcommand*\LWR@igxscale{1}
29 \newcommand*\LWR@igyyscale{1}
30 \newcommand*\LWR@igclass{inlineimage}

31 \newcommand*\LWR@igalt{\ImageAltText}

```

Set the actions of each of the key/value combinations for `\includegraphics`. Many are ignored.

If an optional width was given, set an HTML style:

```

32 \define@key{igraph}{width}{%
33 \setlength{\LWR@igwidth}{#1}%
34 \ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}%
35 {%

```

Default to use the converted fixed length given:

```

36 \renewcommand*\LWR@igwidthstyle{width:\LWR@printlength{\LWR@igwidth}}%

```

If ex or em dimensions were given, use those instead:

```

37 \IfEndWith{#1}{ex}%
38 {\renewcommand*\LWR@igwidthstyle{width:#1}}% yes ex
39 {}% not ex
40 \IfEndWith{#1}{em}%
41 {\renewcommand*\LWR@igwidthstyle{width:#1}}% yes em
42 {}% not em
43 \IfEndWith{#1}{\}%
44 {\renewcommand*\LWR@igwidthstyle{width:#1}}% yes percent
45 {}% not percent
46 \IfEndWith{#1}{px}%
47 {\renewcommand*\LWR@igwidthstyle{width:#1}}% yes px
48 {}% not px
49 }{}% end of length > 0pt
50 }

```

If an optional height was given, set an HTML style:

```
51 \define@key{igraph}{height}{%
52 \setlength{\LWR@igheight}{#1}%
53 \ifthenelse{\lengthtest{\LWR@igheight > 0pt}}%
54 {%
```

Default to use the converted fixed length given:

```
55 \renewcommand*\LWR@igheightstyle{%
56 height:\LWR@printlength{\LWR@igheight} % extra space
57 }%
```

If ex or em dimensions were given, use those instead:

```
58 \IfEndWith{#1}{ex}%
59 {\renewcommand*\LWR@igheightstyle}{height:#1}}% yes ex
60 {}% not ex
61 \IfEndWith{#1}{em}%
62 {\renewcommand*\LWR@igheightstyle}{height:#1}}% yes em
63 {}% not em
64 \IfEndWith{#1}{\}%
65 {\renewcommand*\LWR@igheightstyle}{height:#1}}% yes percent
66 {}% not percent
67 \IfEndWith{#1}{px}%
68 {\renewcommand*\LWR@igheightstyle}{height:#1}}% yes px
69 {}% not px
70 }{}% end of length > 0pt
71 }
```

Handle origin key:

```
72 \define@key{igraph}{origin}[c]{%
73 \renewcommand*\LWR@igorigin}{#1}%
74 }
```

Handle angle key:

```
75 \define@key{igraph}{angle}{\renewcommand*\LWR@igangle}{#1}}
```

Handle class key:

```
76 \define@key{igraph}{class}{\renewcommand*\LWR@igclass}{#1}}
```

Handle alt key:

```
77 \define@key{igraph}{alt}{\renewcommand*\LWR@igalt}{#1}}
```

It appears that `graphicx` does not have separate keys for `xscale` and `yscale`. `scale` adjusts both at the same time.

```
78 \define@key{igraph}{scale}{%
79 \ifthenelse{equal{#1}{1}}{}{}% must expand #1
80 \PackageWarning{lwarp}{%
```

```

81 It is recommended to use ‘‘[width=xx\protect\linewidth]’’\MessageBreak
82 instead of ‘‘[scale=yy]’’,%
83]%
84 }%
85 \renewcommand*\LWR@igxscale{#1}%
86 \renewcommand*\LWR@igyscale{#1}%
87 }

```

Numerous ignored keys:

```

88 \define@key{igraph}{bb}{}
89 \define@key{igraph}{bblx}{}
90 \define@key{igraph}{bblly}{}
91 \define@key{igraph}{bburx}{}
92 \define@key{igraph}{bbury}{}
93 \define@key{igraph}{natwidth}{}
94 \define@key{igraph}{natheight}{}
95 \define@key{igraph}{hiresbb}[true]{}
96 \define@key{igraph}{viewport}{}
97 \define@key{igraph}{trim}{}
98 \define@key{igraph}{totalheight}{}
99 \define@key{igraph}{keepaspectratio}[true]{}
100 \define@key{igraph}{clip}[true]{}
101 \define@key{igraph}{draft}[true]{}
102 \define@key{igraph}{type}{}
103 \define@key{igraph}{ext}{}
104 \define@key{igraph}{read}{}
105 \define@key{igraph}{command}{}

```

New in v1.1a:

```

106 \define@key{igraph}{quite}{}
107 \define@key{igraph}{page}{}
108 \define@key{igraph}{pagebox}{}
109 \define@key{igraph}{interpolate}[true]{}

```

New in v1.1b:

```

110 \define@key{igraph}{decodearray}{}

```

### § 305.3 **Printing HTML styles**

`\LWR@rotstyle`     $\{\langle prefix \rangle\} \{\langle degrees \rangle\}$

Prints the rotate style with the given prefix.

prefix is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:rotate` style.

```

111 \newcommand*\LWR@rotstyle}[2]{%
112 \edef\LWR@tempone{#2}%
113 \setcounter{LWR@tempcountone}{-1*\real{\LWR@tempone}} % space
114 #1transform:rotate(\arabic{LWR@tempcountone}deg); % space
115 }

```

`\LWR@scalestyle`     $\{\langle prefix \rangle\} \{\langle xscale \rangle\} \{\langle yscale \rangle\}$

Prints the scale style with the given prefix.

prefix is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:scale` style.

```
116 \newcommand*\LWR@scalestyle}[3]{%
117 #1transform:scale(#2,#3);
118 }
```

### § 305.4 **\includegraphics**

`\LWR@opacity` For HTML, used only for `\includegraphics`.

`\LWR@opacity` may be set by the `transparent` package.

```
119 \def\LWR@opacity{1}
```

`\LWR@imagesizebox` Used to determine the actual image size if needed.

```
120 \newsavebox{\LWR@imagesizebox}
```

`\LWR@HTML@Gin@setfile`  $\langle w \rangle$   $\langle h \rangle$   $\langle filename \rangle$  Sets the parsed filename for HTML output.

```
121 \newcommand*\LWR@HTML@Gin@setfile}[3]{%
122 \xdef\LWR@parsedfilename{#3}%
123 }
```

`Key [Gin]` `class` CSS class for the image.

Define the new class `key` for the print-mode version of `\includegraphics`, which is enabled inside a `lateximage`.

```
124 \AtBeginDocument{
125 \define@key{Gin}{class}{}
126 \define@key{Gin}{alt}{}
127 }
```

`\LWR@replaceEPSSVG`

Usually, references to EPS files become SVG files, but if the `epstopdf` package is being used, it automatically converts EPS to PDF, and the following must NOT be done.

```
128 \AtBeginDocument{
129 \@ifpackageloaded{epstopdf}
130 {
131 \newcommand*\LWR@replaceEPSSVG{}
132 }{}
133 \newcommand*\LWR@replaceEPSSVG{%
134 \StrSubstitute{\LWR@tempone}{.eps}{.svg}[\LWR@tempone]%
135 \StrSubstitute{\LWR@tempone}{.EPS}{.SVG}[\LWR@tempone]%
136 }
137 }%
138 }
```

`\LWR@ig@wpimagesizes` \* [ $\langle 2: options \rangle$ ] [ $\langle 3: options \rangle$ ]  $\langle 4: filename \rangle$

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```

139 \newcommand*\LWR@ig@wpimagesizes}[4]{%
140 \ifbool{FormatWP}{%
141 \begingroup%
142 \LWR@restoreorigformatting%
143 \ifpdf%
144 \appto\LWR@restoreorigformatting{%
145 \DeclareGraphicsExtensions{%
146 .pdf, .PDF, .gif, .GIF, .png, .PNG, .jpg, .JPG, .jpeg, .JPEG%
147 }%
148 }%
149 \else% \ifpdf
150 \ifXeTeX%
151 \appto\LWR@restoreorigformatting{%
152 \DeclareGraphicsExtensions{%
153 .pdf, .PDF, .gif, .GIF, .png, .PNG, .jpg, .JPG, .jpeg, .JPEG%
154 }%
155 }%
156 \else%
157 \appto\LWR@restoreorigformatting{%
158 \DeclareGraphicsExtensions{%
159 .eps, .EPS, .gif, .GIF, .png, .PNG, .jpg, .JPG, .jpeg, .JPEG%
160 }%
161 }%
162 \fi%
163 \fi% \ifpdf
164 \define@key{Gin}{angle}{}%
165 \IfBooleanTF{#1}%
166 {% starred
167 \IfValueTF{#3}%
168 {%
169 \global\abox{\LWR@imagesizebox}{%
170 \LWR@originincludegraphics*[#2][#3]{#4}%
171 }%
172 }%
173 {%
174 \IfValueTF{#2}%
175 {%
176 \global\abox{\LWR@imagesizebox}{%
177 \LWR@originincludegraphics*[#2]{#4}%
178 }%
179 }{%
180 \global\abox{\LWR@imagesizebox}{%
181 \LWR@originincludegraphics*{#4}%
182 }%
183 }%
184 }%
185 }% starred
186 {% not starred
187 \IfValueTF{#3}%
188 {%
189 \global\abox{\LWR@imagesizebox}{%
190 \LWR@originincludegraphics[#2][#3]{#4}%
191 }%

```

```

192 }%
193 {%
194 \IfValueTF{#2}%
195 {%
196 \global\abox{\LWR@imagesizebox}{%
197 \LWR@originincludegraphics[#2]{#4}%
198 }%
199 }{%
200 \global\abox{\LWR@imagesizebox}{%
201 \LWR@originincludegraphics{#4}%
202 }%
203 }%
204 }%
205 }% not starred
206 \endgroup%
207 \settowidth{\LWR@igwidth}{\usebox{\LWR@imagesizebox}}%
208 \global\renewcommand*\LWR@igwidthstyle{%
209 width:\LWR@printlength{\LWR@igwidth}%
210 }%
211 \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
212 \global\renewcommand*\LWR@igheightstyle{%
213 height:\LWR@printlength{\LWR@igheight}%
214 }%
215 }{}% FormatWP
216 }

```

`\LWR@ig@htmltag` For the HTML reference, add the graphicspath, filename, extension, alt tag, style, and class.

```

217 \newcommand*\LWR@ig@htmltag{%
218 img\LWR@indentHTML%
219 src="%

220 \detokenize\expandafter{\LWR@parsedfilename}%

221 "\LWR@indentHTML%

```

Only include a style tag if a width, height, angle, or scale was given:

```

222 \ifthenelse{
223 \NOT\equal{\LWR@igwidthstyle}{} \OR
224 \NOT\equal{\LWR@igheightstyle}{} \OR
225 \NOT\equal{\LWR@igorigin}{} \OR
226 \NOT\equal{\LWR@igangle}{} \OR
227 \NOT\equal{\LWR@igxscale}{1} \OR
228 \NOT\equal{\LWR@igyscale}{1}
229 }%
230 {%
231 style="\LWR@indentHTML
232 \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{} }%
233 {\LWR@igwidthstyle;\LWR@indentHTML}{}%
234 \ifthenelse{\NOT\equal{\LWR@igheightstyle}{} }%
235 {\LWR@igheightstyle;\LWR@indentHTML}{}%
236 \ifthenelse{\NOT\equal{\LWR@igorigin}{} }%
237 {%
238 transform-origin: \LWR@originnames{\LWR@igorigin};%

```

```

239 \LWR@indentHTML%
240 }{}%
241 \ifthenelse{\NOT\equal{\LWR@igangle}{}}%
242 {%
243 \LWR@rotstyle{-ms-}{\LWR@igangle}\LWR@indentHTML
244 \LWR@rotstyle{-webkit-}{\LWR@igangle}\LWR@indentHTML
245 \LWR@rotstyle{}{\LWR@igangle }\LWR@indentHTML
246 }{}%
247 \ifthenelse{%
248 \NOT\equal{\LWR@igxscale}{1}\OR%
249 \NOT\equal{\LWR@igyscale}{1}%
250 }%
251 {%
252 \LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale}%
253 \LWR@indentHTML
254 \LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale}%
255 \LWR@indentHTML
256 \LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}%
257 \LWR@indentHTML
258 }{}%
259 %
260 \ifthenelse{\NOT\equal{\LWR@opacity}{1}}%
261 {opacity:\LWR@opacity;\LWR@indentHTML}{}%
262 %
263 "\LWR@indentHTML%
264 }{}%

```

Set the class and alt tag:

```

265 class="\LWR@igclass"\LWR@indentHTML%
266 alt="\AltTextOpen\LWR@igalt\AltTextClose" \LWR@orignewline%
267 }% end of image tags

```

`\LWR@includegraphicsb` \* [*2: options*] [*3: options*] [*4: filename*]  
**graphics** syntax is `\includegraphics` \* [*llx,lly*] [*urx,ury*] [*file*]  
**graphicx** syntax is `\includegraphics` [*key values*] [*file*]

If #3 is empty, only one optional argument was given, thus **graphicx** syntax.

If using `\epsfig` or `\psfig` from the `epsfig` package, #4 will be `\LWR@epsfig@filename`, which will have been set by the file or figure keys. Therefore, #4 must not be used until after the keys have been processed.

```

268 \NewDocumentCommand{\LWR@includegraphicsb}{s o o m}
269 {%

```

Start the image tag on a new line, allow PDF output word wrap:

```

270 \LWR@origtilde \LWR@orignewline%

```

Temporarily compute `\linewidth`, `\textwidth`, `\textheight` arguments with a 6x9 inch size until the next `\endgroup`.

```

271 \begin{LWR@setvirtualpage}%

```

For correct em sizing during the width and height conversions:

```

272 \large%

```

Reset some defaults, possibly will be changed below if options were given:

```

273 \setlength{\LWR@igwidth}{0pt}%
274 \setlength{\LWR@igheight}{0pt}%
275 \renewcommand*\LWR@igwidthstyle{}%
276 \renewcommand*\LWR@igheightstyle{}%
277 \renewcommand*\LWR@igorigin{}%
278 \renewcommand*\LWR@igangle{}%
279 \renewcommand*\LWR@igxscale}{1}%
280 \renewcommand*\LWR@igyyscale}{1}%
281 \renewcommand*\LWR@igclass}{inlineimage}%

282 \ifdefvoid{\LWR@ThisAltText}{%
283 \edef\LWR@igalt{\ImageAltText}%
284 }{%
285 \edef\LWR@igalt{\LWR@ThisAltText}%
286 }%
```

If #3 is empty, only one optional argument was given, thus graphicx syntax:

```

287 \IfValueF{#3}{%
288 \IfValueTF{#2}%
289 {\setkeys{igraph}{#2}}%
290 {\setkeys{igraph}}}%
291 }%
```

Fully expand and detokenize the filename, changing the file extension to .svg if necessary.

```

292 \begingroup%
293 \LetLtxMacro\Gin@setfile\LWR@HTML@Gin@setfile%
294 \edef\LWR@tempone{#4}%
295 \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
296 \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
297 \LWR@replaceEPSSVG%
298 \xdef\LWR@parsedfilename{\LWR@tempone}%
299 \Gininclude@graphics{\detokenize\expandafter{\LWR@tempone}}%
300 \endgroup%
301 \filename@parse{\LWR@parsedfilename}%
```

Remove doubled // in the directory path, from the 2020/10/01 L<sup>A</sup>T<sub>E</sub>X kernel change.

```

302 \StrSubstitute{\LWR@parsedfilename}{//}{/}[\LWR@parsedfilename]%

303 \LWR@traceinfo{\LWR@parsedfilename is \LWR@parsedfilename}%
```

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```

304 \LWR@ig@wpimagesizes{#1}{#2}{#3}{#4}%
```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class:

```

305 \LWR@traceinfo{\LWR@includegraphicsb: about to create href}%
306 \LWR@href{\LWR@parsedfilename}%
307 {% start of href
308 \LWR@traceinfo{\LWR@includegraphicsb: about to LWR@htmltag}%
309 \LWR@htmltag{\LWR@ig@htmltag}%
310 }% end of href
```

Return to original page size and font size:

```
311 \end{LWR@setvirtualpage}%
```

Clear the single-use alt text:

```
312 \gdef\LWR@ThisAltText{%
313 \LWR@traceinfo{LWR@includegraphicsb done}%
314 }
```

`\includegraphics` [*<key=val>*] {*<filename>*}

Handles width and height, converted to fixed width and heights.

The user should always use no file suffix in the document source.

```
315 \AtBeginDocument{
316
317 \LWR@traceinfo{Patching includegraphics.}
318
319 \LetLtxMacro\LWR@originincludegraphics\includegraphics

320 \renewrobustcmd*{\includegraphics}
321 {%
```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```
322 \LWR@traceinfo{includegraphics}%
323 \LWR@ensuredoingapar%
324 \LWR@includegraphicsb%
325 }% includegraphics
326 }% AtBeginDocument
```

### § 305.5 Boxes

`\LWR@rotboxorigin` Holds the origin key letters.

```
327 \newcommand*\LWR@rotboxorigin{}
```

`\LWR@originname` {*<letter>*}

Given one L<sup>A</sup>T<sub>E</sub>X origin key value, translate into an HTML origin word:

```
328 \newcommand*\LWR@originname[1]{%
329 \ifthenelse{\equal{#1}{t}}{top}{}%
330 \ifthenelse{\equal{#1}{b}}{bottom}{}%
331 \ifthenelse{\equal{#1}{c}}{center}{}%
332 \ifthenelse{\equal{#1}{l}}{left}{}%
333 \ifthenelse{\equal{#1}{r}}{right}{}%
334 }
```

`\LWR@originnames` {*<letters>*}

Given one- or two-letter L<sup>A</sup>T<sub>E</sub>X origin key values, translate into HTML origin words:

```

335 \newcommand*{\LWR@originnames}[1]{%
336 \StrChar{#1}{1}[\LWR@strresult]%
337 \LWR@originname{\LWR@strresult}
338 \StrChar{#1}{2}[\LWR@strresult]%
339 \LWR@originname{\LWR@strresult}
340 }

```

Handle the origin key for `\rotatebox`:

```

341 \define@key{krotbox}{origin}{%
342 \renewcommand*{\LWR@rotboxorigin}{#1}%
343 }

```

These keys are ignored:

```

344 \define@key{krotbox}{x}{}
345 \define@key{krotbox}{y}{}
346 \define@key{krotbox}{units}{}

```

`\rotatebox` [*⟨keyval list⟩*] {*⟨angle⟩*} {*⟨text⟩*}

```

347 \AtBeginDocument{

```

The HTML version:

```

348 \NewDocumentCommand{\LWR@HTML@rotatebox}{O{} m +m}{%

```

Reset the origin to “none-given”:

```

349 \renewcommand*{\LWR@rotboxorigin}{}

```

Process the optional keys, which may set `\LWR@rotateboxorigin`:

```

350 \setkeys{krotbox}{#1}%

```

Select inline-block so that HTML will transform this span:

```

351 \LWR@htmltagc{%
352 span\LWR@indentHTML
353 style="\LWR@indentHTML
354 display: inline-block;\LWR@indentHTML

```

If an origin was given, translate and print the origin information:

```

355 \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{} }{
356 {transform-origin: \LWR@originnames{\LWR@rotboxorigin};\LWR@indentHTML}%
357 }{}%

```

Print the rotation information:

```

358 \LWR@rotstyle{-ms-}{#2}\LWR@indentHTML
359 \LWR@rotstyle{-webkit-}{#2}\LWR@indentHTML
360 \LWR@rotstyle{#2}"\LWR@orignewLine%
361 } \LWR@orignewLine%

```

Print the text to be rotated:

```
362 \begin{LWR@nestspan}%
363 #3%
```

Close the span:

```
364 \LWR@htmltagc{/span}%
365 \end{LWR@nestspan}%
366 }
```

The high-level interface:

```
367 \LWR@formatted{rotatebox}
368
369 }% AtBeginDocument
```

`\scalebox`  $\langle h-scale \rangle$  [ $\langle v-scale \rangle$ ]  $\langle text \rangle$

```
370 \AtBeginDocument{
```

The HTML version:

```
371 \NewDocumentCommand{\LWR@HTML@scalebox}{m o m}{%
```

Select inline-block so that HTML will transform this span:

```
372 \LWR@htmltagc{%
373 span\LWR@indentHTML
374 style="\LWR@indentHTML
375 display: inline-block;\LWR@indentHTML
```

Print the scaling information:

```
376 \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
377 \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
378 \LWR@scalestyle{#1}{\IfNoValueTF{#2}{#1}{#2}}
379 "\LWR@orignewLine
380 }\LWR@orignewLine%
```

Print the text to be scaled:

```
381 \begin{LWR@nestspan}%
382 #3%
```

Close the span:

```
383 \LWR@htmltagc{/span}%
384 \end{LWR@nestspan}%
385 }
```

The high-level interface:

```

386 \LWR@formatted{scalebox}
387
388 }% AtBeginDocument

```

`\reflectbox`  $\{\langle text \rangle\}$

```

389 \AtBeginDocument{
390
391 \newcommand{\LWR@HTML@reflectbox}[1]{%
392 \scalebox{-1}[1]{#1}%
393 }% \reflectbox
394
395 \LWR@formatted{reflectbox}
396
397 }% AtBeginDocument

```

`\resizebox`  $\{\langle h-length \rangle\} \{\langle v-length \rangle\} \{\langle text \rangle\}$

Simply prints its text argument.

```

398 \AtBeginDocument{
399
400 \NewDocumentCommand{\LWR@HTML@resizebox}{s m m m}{%
401 #4%
402 }
403
404 \LWR@formatted{resizebox}
405
406 }% AtBeginDocument

```

---

File 200 **lwarp-graphics.sty**

§ 306 Package **graphicx**

Pkg graphicx graphicx is emulated.

graphicx loads graphics, which also loads lwarp-graphics, which remembers the original graphics definitions for use inside a lateximage, and then patches them \AtBeginDocument for HTML output.

lwarp-graphics handles the syntax of either graphics or graphicx.

**for HTML output:** 1 \LWR@ProvidesPackagePass{graphicx}[2020/09/09]

---

File 201 **lwarp-grffile.sty**

§ 307 Package **grffile**

Pkg grffile grffile is supported as-is. File types known to the browser are displayed, and unknown

**matching PDF and SVG**

file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

lwarp-grffile now exists as a placeholder since grffile used to be emulated by lwarp, and thus older versions of lwarp-grffile may exist and should be overwritten by this newer version.

**for HTML output:** `1 \LWR@ProvidesPackagePass{grffile}[2017/06/30]`

File 202 **lwarp-grid.sty**

§ 308 Package **grid**

Pkg grid grid is ignored.

**for HTML output:** `1 \LWR@ProvidesPackageDrop{grid}[2009/06/16]`

`2 \newenvironment*{gridenv}{}{}`

File 203 **lwarp-grid-system.sty**

§ 309 Package **grid-system**

*(Emulates or patches code by MARCUS BITZL.)*

Pkg grid-system grid-system is patched for use by lwarp.

**for HTML output:** `1 \LWR@ProvidesPackagePass{grid-system}[2014/02/16]`

`(\ifdef is in case the older syntax is removed.)`

`2 \AtBeginEnvironment{Row}{\setlength{\linewidth}{6in}}`

`3`

`4 \ifdef{\endrow}{`

`5 \AtBeginEnvironment{row}{\setlength{\linewidth}{6in}}`

`6 }{}`

`7`

`8 \renewcommand{\gridsystem@finishcell}{\hspace{\gridsystem@cellsep}}`

File 204 **lwarp-gridset.sty**

§ 310 Package **gridset**

Pkg gridset gridset is ignored.

**for HTML output:** `1 \LWR@ProvidesPackageDrop{gridset}[2020-02-12]`

```

2 \newcommand*\gridbase{}
3 \newcommand*\gridinterval{}
4 \newcommand*\SavePos}[1]{}
5 \ifLuaTeX
6 \else
7 \let\savepos\SavePos
8 \fi
9 \newcommand*\vskipnextgrid{}
10 \newcommand*\thegridinfo}[1]{(thegridinfo)}
11 \newcommand*\theposinfo}[1]{(theposinfo)}
12 \newcommand*\theypos}[1]{(theypos)}

```

File 205 **lwarp-hang.sty**

§ 311 Package **hang**

*(Emulates or patches code by ANDREAS NOLDA.)*

Pkg hang **hang** is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{hang}[2017/02/18]

2 \newlength{\hangingindent}
3 \setlength{\hangingindent}{1em}
4 \newlength{\hangingleftmargin}
5 \setlength{\hangingleftmargin}{0em}
6
7 \newcommand*\LWR@findhangingleftmargin{%
8 \setlength{\LWR@templengthone}{\hangingleftmargin}%
9 \addtolength{\LWR@templengthone}{\hangingindent}%
10 }
11
12 \newenvironment{hangingpar}
13 {
14 \LWR@findhangingleftmargin%
15 \BlockClass[%
16 \LWR@print@mbx{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
17 \LWR@print@mbx{text-indent:-\LWR@printlength{\hangingindent}}%
18]%
19 {hangingpar}%
20 }
21 {\endBlockClass}
22
23 \newenvironment{hanginglist}
24 {%
25 \renewcommand*\LWR@printcloselist{\LWR@printcloseitemize}%
26 \renewcommand*\LWR@printopenlist{%
27 \LWR@findhangingleftmargin%
28 ul style=""
29 \LWR@print@mbx{list-style-type:none;} % extra space
30 \LWR@print@mbx{%
31 margin-left:\LWR@printlength{\LWR@templengthone}%
32 } ; % extra space

```

```

33 \LWR@print@mbbox{%
34 text-indent:-\LWR@printlength{\hangingindent}%
35 }%
36 "%
37 }%
38 \let\item\LWR@itemizeitem%
39 \list{}{}%
40 }
41 {\endlist}
42
43 \newenvironment{compacthang}
44 {\hanginglist}
45 {\endhanginglist}
46
47 \newlength{\labeledleftmargin}
48 \setlength{\labeledleftmargin}{0em}
49
50 \newenvironment{labeledpar}[2]
51 {%
52 \BlockClass[%
53 \LWR@findhangingleftmargin%
54 \LWR@print@mbbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
55 \LWR@print@mbbox{text-indent:-\LWR@printlength{\hangingindent}}%
56]{labeledpar}#2%
57 }
58 {\endBlockClass}
59
60 \newenvironment{labeledlist}[1]
61 {\hanginglist}
62 {\endhanginglist}
63
64 \newenvironment{compactlabel}[1]
65 {\hanginglist}
66 {\endhanginglist}

```

---

File 206 **lwarp-hanging.sty**

§ 312 Package **hanging**

Pkg hanging **hanging** is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{hanging}[2009/09/02]

```

2 \@ifclassloaded{memoir}{
3 \let\hangpara\relax
4 \let\hangparas\relax
5 \let\endhangparas\relax
6 \let\hangpunct\relax
7 \let\endhangpunct\relax
8 }{}

```

`\hangpara`     $\langle indent \rangle \langle afternum \rangle$

Use `hangparas` instead.

```
9 \newcommand*\hangpara[2]{}
```

Env `hangparas`     $\langle indent \rangle \langle afternum \rangle$

```
10 \newenvironment*{hangparas}[2]
11 {%
12 \BlockClass[%
13 \LWR@print@mbx{margin-left:\LWR@printlength{#1}} ; %
14 \LWR@print@mbx{text-indent:-\LWR@printlength{#1}}}%
15]%
16 {hangingpar}%
17 }
18 {\endBlockClass}
```

Env `hangpunct`

```
19 \newenvironment*{hangpunct}
20 {\BlockClass{hangpunct}}
21 {\endBlockClass}

22 \newcommand{\nhpt}{.}
23 \newcommand{\nhlq}{'}
24 \newcommand{\nhrq}{'}
```

File 207    **lwarp-hepunits.sty**

§ 313    Package    **hepunits**

*(Emulates or patches code by ANDY BUCKLEY.)*

Pkg `hepunits`    `hepunits` is used as-is, and emulated for MATHJAX.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{hepunits}[2020/04/10]

2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{hepunits}
4
5 \ifx\@HEPopt@sicmds\eyes
6 \CustomizeMathJax{\newcommand{\micron}{\micro\metre}}
7 \CustomizeMathJax{\newcommand{\mrad}{\milli\radian}}
8 \fi
9
10 \CustomizeMathJax{\newcommand{\gauss}{\mathrm{G}}}
11
12 \CustomizeMathJax{\newcommand{\invcmsq}{\centi\metre\tothe{-2}}}
13 \CustomizeMathJax{\newcommand{\invcmsqpersecond}{\invcmsq\second\tothe{-1}}}
14 \CustomizeMathJax{\newcommand{\invcmsqpersec}{\invcmsqpersecond}}
15
16 %% (Inverse) cross-sections
```

```
17 \CustomizeMathJax{\newcommand{\invbarn}{\barn\tothe{-1}}}
18
19 \ifx\@HEPopt@noprefixcmds\@empty
20 \CustomizeMathJax{\newcommand{\millibarn}{\milli\barn}}
21 \CustomizeMathJax{\newcommand{\microbarn}{\micro\barn}}
22 \CustomizeMathJax{\newcommand{\nanobarn}{\nano\barn}}
23 \CustomizeMathJax{\newcommand{\picobarn}{\pico\barn}}
24 \CustomizeMathJax{\newcommand{\femtobarn}{\femto\barn}}
25 \CustomizeMathJax{\newcommand{\attobarn}{\atto\barn}}
26 \CustomizeMathJax{\newcommand{\zeptobarn}{\zepto\barn}}
27 \CustomizeMathJax{\newcommand{\yoctobarn}{\yocto\barn}}
28 \CustomizeMathJax{\newcommand{\invnanobarn}{\nano\invbarn}}
29 \CustomizeMathJax{\newcommand{\invpicobarn}{\pico\invbarn}}
30 \CustomizeMathJax{\newcommand{\invfemtobarn}{\femto\invbarn}}
31 \CustomizeMathJax{\newcommand{\invattobarn}{\atto\invbarn}}
32 \CustomizeMathJax{\newcommand{\invzeptobarn}{\zepto\invbarn}}
33 \CustomizeMathJax{\newcommand{\invyoctobarn}{\yocto\invbarn}}
34 \CustomizeMathJax{\newcommand{\invnb}{\invnanobarn}}
35 \CustomizeMathJax{\newcommand{\invpb}{\invpicobarn}}
36 \CustomizeMathJax{\newcommand{\invfb}{\invfemtobarn}}
37 \CustomizeMathJax{\newcommand{\invab}{\invattobarn}}
38 \CustomizeMathJax{\newcommand{\invzb}{\invzeptobarn}}
39 \CustomizeMathJax{\newcommand{\invyb}{\invyoctobarn}}
40 \fi
41
42 \CustomizeMathJax{\newcommand{\electronvoltc}{\electronvolt\per\mathit{c}}}
43 \CustomizeMathJax{\newcommand{\electronvoltcsg}{\electronvolt\per\mathit{c}\squared}}
44 \CustomizeMathJax{\let\evc\electronvoltc}
45 \CustomizeMathJax{\let\evcsg\electronvoltcsg}
46
47 \ifx\@HEPopt@noprefixcmds\@empty
48 \CustomizeMathJax{\newcommand{\meV}{\milli\ev}}
49 \CustomizeMathJax{\newcommand{\keV}{\kilo\ev}}
50 \CustomizeMathJax{\newcommand{\MeV}{\mega\ev}}
51 \CustomizeMathJax{\newcommand{\GeV}{\giga\ev}}
52 \CustomizeMathJax{\newcommand{\TeV}{\tera\ev}}
53 \CustomizeMathJax{\newcommand{\meVc}{\milli\evc}}
54 \CustomizeMathJax{\newcommand{\keVc}{\kilo\evc}}
55 \CustomizeMathJax{\newcommand{\MeVc}{\mega\evc}}
56 \CustomizeMathJax{\newcommand{\GeVc}{\giga\evc}}
57 \CustomizeMathJax{\newcommand{\TeVc}{\tera\evc}}
58 \CustomizeMathJax{\newcommand{\meVcsg}{\milli\evcsg}}
59 \CustomizeMathJax{\newcommand{\keVcsg}{\kilo\evcsg}}
60 \CustomizeMathJax{\newcommand{\MeVcsg}{\mega\evcsg}}
61 \CustomizeMathJax{\newcommand{\GeVcsg}{\giga\evcsg}}
62 \CustomizeMathJax{\newcommand{\TeVcsg}{\tera\evcsg}}
63 \fi
64 \end{warpMathJax}
```

---

File 208 **lwarp-hhline.sty**

§ 314 Package **hhline**

(Emulates or patches code by DAVID CARLISLE.)

Pkg hhline **hhline** is patched for use by **lwarp**.

Only a rudimentary emulation is provided so far. If the argument contains any = characters, the result is a double `\hline`. If none, the result is a single `\hline`.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{hhline}[2014/10/28]

2 \newrobustcmd*{\LWR@HTML@hhline}[1]{%
3 \edef\LWR@tempone{\detokenize\expandafter{#1}}%
4 \IfSubStr[1]{\LWR@tempone}{=}{\hline\hline}{\hline}%
5 }
6 % ^^A or:
7 % ^^A \newrobustcmd*{\LWR@HTML@hhline}[1]{\LWR@getmynexttoken}
8
9 \AtBeginDocument{\LWR@expandableformatted{hhline}}
```

For MATHJAX. A simple `\hline` is used.

```

10 \begin{warpMathJax}
11 \CustomizeMathJax{\newcommand{\hhline}[1]{\hline}}
12 \end{warpMathJax}
```

---

File 209 **lwarp-hhtensor.sty**

§ 315 Package **hhtensor**

(Emulates or patches code by HARALD HARDERS.)

Pkg hhtensor **hhtensor** is used as-is, and emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{hhtensor}[2011/12/29]

2 \begin{warpMathJax}
3 \iftensor@bold
4 \CustomizeMathJax{\newcommand{\vec}[1]{\boldsymbol{#1}}}
5 \CustomizeMathJax{\newcommand{\matr}[1]{\boldsymbol{#1}}}
6 \CustomizeMathJax{\newcommand{\tens}[2]{\boldsymbol{#1}}}
7 \else
8 \iftensor@uline
9 \CustomizeMathJax{\newcommand{\vec}[1]{\ushort{#1}}}
10 \CustomizeMathJax{\newcommand{\matr}[1]{\ushortd{#1}}}
11 \CustomizeMathJax{\newcommand{\tens}[2]{
```

```

12 \underset{
13 \raise{.5ex}{\underset{#2}{\sim}}
14 }{#1}
15 }}
16 \else
17 \CustomizeMathJax{\newcommand{\matr}[1]{\vec{\vec{#1}}}}
18 \CustomizeMathJax{\newcommand{\tens}[2]{
19 \underset{
20 \raise{.5ex}{\underset{#2}{\sim}}
21 }{#1}
22 }}
23 \fi
24 \fi
25 \CustomizeMathJax{\newcommand{\dcdot}{\mathrel{\cdot\mkern 0.0mu \cdot}}}
26 \CustomizeMathJax{\newcommand{\trans}{{}^{\mathrm{T}}}}
27 \end{warpMathJax}

```

---

File 210 **lwarp-hypbmsec.sty**

§ 316 Package **hypbmsec**

Pkg hypbmsec hypbmsec is emulated by the lwarp core.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{hypbmsec}[2016/05/16]

---

File 211 **lwarp-hypcap.sty**

§ 317 Package **hypcap**

Pkg hypcap hypcap is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{hypcap}[2016/05/16]

```

2 \newcommand*{\capstart}{}
3 \newcommand*{\hypcapspace}{}
4 \newcommand*{\hypcapredef}[1]{}
5 \newcommand*{\capstartfalse}{}
6 \newcommand*{\capstarttrue}{}

```

---

File 212 **lwarp-hypdestopt.sty**

§ 318 Package **hypdestopt**

Pkg hypdestopt hypdestopt is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{hypdestopt}[2016/05/21]

---

File 213 **lwarp-hypernat.sty**

§ 319 Package **hypernat**

Pkg hypernat hypernat is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{hypernat}[2001/07/09]

---

File 214 **lwarp-hyperref.sty**

§ 320 Package **hyperref**

*(Emulates or patches code by SEBASTIAN RAHTZ, HEIKO OBERDIEK, THE L<sup>A</sup>T<sub>E</sub>X3 PROJECT.)*

Pkg hyperref hyperref is emulated.

**for HTML output:** 1 % \LWR@ProvidesPackageDrop{hyperref}% not allowed  
 2 % \ProvidesPackage{lwarp-#1-#2}% not allowed  
 3 \PackageInfo{lwarp}{%  
 4 Using the lwarp HTML version of package ‘hyperref’,\MessageBreak  
 5 and discarding options except backref, pagebackref.\MessageBreak  
 6 (Not using \protect\ProvidesPackage, so that other packages\MessageBreak  
 7 do not attempt to patch lwarp’s version of ‘hyperref’.)\MessageBreak}

8 \SetupKeyvalOptions{family=LWR@hyperref,prefix=LWR@hyperref@}  
 9  
 10 \newcommand{\hypersetup}[1]{\setkeys{LWR@hyperref}{#1}}  
 11  
 12 \define@key{LWR@hyperref}{a4paper}[]{}  
 13 \define@key{LWR@hyperref}{a5paper}[]{}  
 14 \define@key{LWR@hyperref}{b5paper}[]{}  
 15 \define@key{LWR@hyperref}{letterpaper}[]{}  
 16 \define@key{LWR@hyperref}{legalpaper}[]{}  
 17 \define@key{LWR@hyperref}{executivepaper}[]{}  
 18 \define@key{LWR@hyperref}{implicit}[]{}  
 19 \define@key{LWR@hyperref}{draft}[]{}  
 20 \define@key{LWR@hyperref}{final}[]{}  
 21 \define@key{LWR@hyperref}{setpagesize}[]{}  
 22 \define@key{LWR@hyperref}{debug}[]{}  
 23 \define@key{LWR@hyperref}{linktocpage}[]{}  
 24 \define@key{LWR@hyperref}{linktoc}[]{}  
 25 \define@key{LWR@hyperref}{extension}[]{}  
 26 \define@key{LWR@hyperref}{verbose}[]{}  
 27 \define@key{LWR@hyperref}{typexml}[]{}  
 28 \define@key{LWR@hyperref}{raiselinks}[]{}  
 29 \define@key{LWR@hyperref}{breaklinks}[]{}  
 30 \define@key{LWR@hyperref}{localanchorname}[]{}  
 31 \define@key{LWR@hyperref}{pageanchor}[]{}

```
32 \define@key{LWR@hyperref}{plainpages}[]{}
33 \define@key{LWR@hyperref}{naturalnames}[]{}
34 \define@key{LWR@hyperref}{hypertextnames}[]{}
35 \define@key{LWR@hyperref}{nesting}[]{}
36 \define@key{LWR@hyperref}{destlabel}[]{}
37 \define@key{LWR@hyperref}{unicode}[]{}
38 \define@key{LWR@hyperref}{pdfencoding}[]{}
39 \define@key{LWR@hyperref}{psdextra}[]{}
40 \define@key{LWR@hyperref}{pdfversion}[]{}
41 \define@key{LWR@hyperref}{dvipdfmx-outline-open}[]{}
42 \define@key{LWR@hyperref}{driverfallback}[]{}
43 \define@key{LWR@hyperref}{customdriver}[]{}
44 \define@key{LWR@hyperref}{hyperfigures}[]{}
45 \define@key{LWR@hyperref}{hyperfootnotes}[]{}
46 \define@key{LWR@hyperref}{hyperindex}[]{}
47 \define@key{LWR@hyperref}{encap}[]{}
48 \define@key{LWR@hyperref}{colorlinks}[]{}
49 \define@key{LWR@hyperref}{ocgcolorlinks}[]{}
50 \define@key{LWR@hyperref}{frenchlinks}[]{}
51 \define@key{LWR@hyperref}{bookmarks}[]{}
52 \define@key{LWR@hyperref}{bookmarksopen}[]{}
53 \define@key{LWR@hyperref}{bookmarksdepth}[]{}
54 \define@key{LWR@hyperref}{bookmarksopenlevel}[]{}
55 \define@key{LWR@hyperref}{bookmarkstype}[]{}
56 \define@key{LWR@hyperref}{bookmarksnumbered}[]{}
57 \define@key{LWR@hyperref}{CJKbookmarks}[]{}
58 \define@key{LWR@hyperref}{link}[]{}
59 \define@key{LWR@hyperref}{anchor}[]{}
60 \define@key{LWR@hyperref}{cite}[]{}
61 \define@key{LWR@hyperref}{file}[]{}
62 \define@key{LWR@hyperref}{url}[]{}
63 \define@key{LWR@hyperref}{menu}[]{}
64 \define@key{LWR@hyperref}{run}[]{}
65 \define@key{LWR@hyperref}{linkbordercolor}[]{}
66 \define@key{LWR@hyperref}{anchorbordercolor}[]{}
67 \define@key{LWR@hyperref}{citebordercolor}[]{}
68 \define@key{LWR@hyperref}{filebordercolor}[]{}
69 \define@key{LWR@hyperref}{urlbordercolor}[]{}
70 \define@key{LWR@hyperref}{menubordercolor}[]{}
71 \define@key{LWR@hyperref}{runbordercolor}[]{}
72 \define@key{LWR@hyperref}{pagecolor}[]{}
73 \define@key{LWR@hyperref}{baseurl}[]{}
74 \define@key{LWR@hyperref}{linkfileprefix}[]{}
75 \define@key{LWR@hyperref}{pdfpagetransition}[]{}
76 \define@key{LWR@hyperref}{pdfpageduration}[]{}
77 \define@key{LWR@hyperref}{pdfpagehidden}[]{}
78 \define@key{LWR@hyperref}{pagebordercolor}[]{}
79 \define@key{LWR@hyperref}{allbordercolors}[]{}
80 \define@key{LWR@hyperref}{pdfhighlight}[]{}
81 \define@key{LWR@hyperref}{pdfborder}[]{}
82 \define@key{LWR@hyperref}{pdfborderstyle}[]{}
83 \define@key{LWR@hyperref}{pdfprintpagerange}[]{}
84 \define@key{LWR@hyperref}{pdfusetitle}[]{}
85 \define@key{LWR@hyperref}{pdftitle}[]{}
86 \define@key{LWR@hyperref}{pdfauthor}[]{}

```

```
87 \define@key{LWR@hyperref}{pdfproducer}[]{}
88 \define@key{LWR@hyperref}{pdfcreator}[]{}
89 \define@key{LWR@hyperref}{addtopdfcreator}[]{}
90 \define@key{LWR@hyperref}{pdfcreationdate}[]{}
91 \define@key{LWR@hyperref}{pdfmoddate}[]{}
92 \define@key{LWR@hyperref}{pdfsubject}[]{}
93 \define@key{LWR@hyperref}{pdfkeywords}[]{}
94 \define@key{LWR@hyperref}{pdftrapped}[]{}
95 \define@key{LWR@hyperref}{pdfinfo}[]{}
96 \define@key{LWR@hyperref}{pdfview}[]{}
97 \define@key{LWR@hyperref}{pdflinkmargin}[]{}
98 \define@key{LWR@hyperref}{pdfstartpage}[]{}
99 \define@key{LWR@hyperref}{pdfstartview}[]{}
100 \define@key{LWR@hyperref}{pdfremotestartview}[]{}
101 \define@key{LWR@hyperref}{pdfpagescrop}[]{}
102 \define@key{LWR@hyperref}{pdftoolbar}[]{}
103 \define@key{LWR@hyperref}{pdfmenubar}[]{}
104 \define@key{LWR@hyperref}{pdfwindowui}[]{}
105 \define@key{LWR@hyperref}{pdffitwindow}[]{}
106 \define@key{LWR@hyperref}{pdfcenterwindow}[]{}
107 \define@key{LWR@hyperref}{pdfdisplaydoctitle}[]{}
108 \define@key{LWR@hyperref}{pdfa}[]{}
109 \define@key{LWR@hyperref}{pdfnewwindow}[]{}
110 \define@key{LWR@hyperref}{pdflang}[]{}
111 \define@key{LWR@hyperref}{pdfpagelabels}[]{}
112 \define@key{LWR@hyperref}{pdfescapeform}[]{}
113 \define@key{LWR@hyperref}{english}[]{}
114 \define@key{LWR@hyperref}{UKenglish}[]{}
115 \define@key{LWR@hyperref}{british}[]{}
116 \define@key{LWR@hyperref}{USenglish}[]{}
117 \define@key{LWR@hyperref}{american}[]{}
118 \define@key{LWR@hyperref}{german}[]{}
119 \define@key{LWR@hyperref}{austrian}[]{}
120 \define@key{LWR@hyperref}{ngerman}[]{}
121 \define@key{LWR@hyperref}{naustrian}[]{}
122 \define@key{LWR@hyperref}{russian}[]{}
123 \define@key{LWR@hyperref}{brazil}[]{}
124 \define@key{LWR@hyperref}{brazilian}[]{}
125 \define@key{LWR@hyperref}{portuguese}[]{}
126 \define@key{LWR@hyperref}{spanish}[]{}
127 \define@key{LWR@hyperref}{catalan}[]{}
128 \define@key{LWR@hyperref}{afrikaans}[]{}
129 \define@key{LWR@hyperref}{french}[]{}
130 \define@key{LWR@hyperref}{frenchb}[]{}
131 \define@key{LWR@hyperref}{français}[]{}
132 \define@key{LWR@hyperref}{acadian}[]{}
133 \define@key{LWR@hyperref}{canadien}[]{}
134 \define@key{LWR@hyperref}{italian}[]{}
135 \define@key{LWR@hyperref}{magyar}[]{}
136 \define@key{LWR@hyperref}{hungarian}[]{}
137 \define@key{LWR@hyperref}{greek}[]{}
138 \define@key{LWR@hyperref}{dutch}[]{}
139 \define@key{LWR@hyperref}{tex4ht}[]{}
140 \define@key{LWR@hyperref}{pdftex}[]{}
141 \define@key{LWR@hyperref}{luatex}[]{}

```

```
142 \define@key{LWR@hyperref}{nativepdf}[]{}
143 \define@key{LWR@hyperref}{dvi pdfm}[]{}
144 \define@key{LWR@hyperref}{dvi pdfmx}[]{}
145 \define@key{LWR@hyperref}{xetex}[]{}
146 \define@key{LWR@hyperref}{pdfmark}[]{}
147 \define@key{LWR@hyperref}{dvips}[]{}
148 \define@key{LWR@hyperref}{hypertex}[]{}
149 \define@key{LWR@hyperref}{vtex}[]{}
150 \define@key{LWR@hyperref}{vtexpdfmark}[]{}
151 \define@key{LWR@hyperref}{dviwindo}[]{}
152 \define@key{LWR@hyperref}{dvipsone}[]{}
153 \define@key{LWR@hyperref}{textures}[]{}
154 \define@key{LWR@hyperref}{latex2html}[]{}
155 \define@key{LWR@hyperref}{ps2pdf}[]{}
156 \define@key{LWR@hyperref}{vietnamese}[]{}
157 \define@key{LWR@hyperref}{vietnam}[]{}
158 \define@key{LWR@hyperref}{arabic}[]{}
159 \define@key{LWR@hyperref}{hidelinks}[]{}
160 \define@key{LWR@hyperref}{draft}[]{}
161 \define@key{LWR@hyperref}{nolinks}[]{}
162 \define@key{LWR@hyperref}{final}[]{}
163 \define@key{LWR@hyperref}{pdfa}[]{}
164 \define@key{LWR@hyperref}{pdfversion}[]{}
165 \define@key{LWR@hyperref}{typexml}[]{}
166 \define@key{LWR@hyperref}{tex4ht}[]{}
167 \define@key{LWR@hyperref}{pdf tex}[]{}
168 \define@key{LWR@hyperref}{nativepdf}[]{}
169 \define@key{LWR@hyperref}{dvi pdfm}[]{}
170 \define@key{LWR@hyperref}{dvi pdfmx}[]{}
171 \define@key{LWR@hyperref}{dvi pdfmx-outline-open}[]{}
172 \define@key{LWR@hyperref}{pdfmark}[]{}
173 \define@key{LWR@hyperref}{dvips}[]{}
174 \define@key{LWR@hyperref}{hypertex}[]{}
175 \define@key{LWR@hyperref}{vtex}[]{}
176 \define@key{LWR@hyperref}{vtexpdfmark}[]{}
177 \define@key{LWR@hyperref}{dviwindo}[]{}
178 \define@key{LWR@hyperref}{dvipsone}[]{}
179 \define@key{LWR@hyperref}{textures}[]{}
180 \define@key{LWR@hyperref}{latex2html}[]{}
181 \define@key{LWR@hyperref}{ps2pdf}[]{}
182 \define@key{LWR@hyperref}{xetex}[]{}
183 \define@key{LWR@hyperref}{driverfallback}[]{}
184 \define@key{LWR@hyperref}{customdriver}[]{}
185 \define@key{LWR@hyperref}{pdfversion}[]{}
186 \define@key{LWR@hyperref}{bookmarks}[]{}
187 \define@key{LWR@hyperref}{ocgcolorlinks}[]{}
188 \define@key{LWR@hyperref}{colorlinks}[]{}
189 \define@key{LWR@hyperref}{frenchlinks}[]{}
190 \define@key{LWR@hyperref}{backref}[]{}
191 \define@key{LWR@hyperref}{pagebackref}[]{}
192 \define@key{LWR@hyperref}{destlabel}[]{}
193 \define@key{LWR@hyperref}{pdfpagescrop}[]{}
194 \define@key{LWR@hyperref}{pdfpagemode}[]{}
195 \define@key{LWR@hyperref}{pdfnonfullscreenpagemode}[]{}
196 \define@key{LWR@hyperref}{pdfdirection}[]{}

```

```

197 \define@key{LWR@hyperref}{pdfviewarea}[]{}
198 \define@key{LWR@hyperref}{pdfviewclip}[]{}
199 \define@key{LWR@hyperref}{pdfprintarea}[]{}
200 \define@key{LWR@hyperref}{pdfprintclip}[]{}
201 \define@key{LWR@hyperref}{pdfprintsclaling}[]{}
202 \define@key{LWR@hyperref}{pdfduplex}[]{}
203 \define@key{LWR@hyperref}{pdfpicktraybypdfsize}[]{}
204 \define@key{LWR@hyperref}{pdfprintpagerange}[]{}
205 \define@key{LWR@hyperref}{pdfnumcopies}[]{}
206 \define@key{LWR@hyperref}{pdfstartview}[]{}
207 \define@key{LWR@hyperref}{pdfstartpage}[]{}
208 \define@key{LWR@hyperref}{pdftoolbar}[]{}
209 \define@key{LWR@hyperref}{pdfmenubar}[]{}
210 \define@key{LWR@hyperref}{pdfwindowui}[]{}
211 \define@key{LWR@hyperref}{pdffitwindow}[]{}
212 \define@key{LWR@hyperref}{pdfcenterwindow}[]{}
213 \define@key{LWR@hyperref}{pdfdisplaydoctitle}[]{}
214 \define@key{LWR@hyperref}{pdfpagelayout}[]{}
215 \define@key{LWR@hyperref}{pdflang}[]{}
216 \define@key{LWR@hyperref}{baseurl}[]{}
217 \define@key{LWR@hyperref}{pdfusetitle}[]{}
218 \define@key{LWR@hyperref}{pdfpageLabels}[]{}
219 \define@key{LWR@hyperref}{hyperfootnotes}[]{}
220 \define@key{LWR@hyperref}{hyperfigures}[]{}
221 \define@key{LWR@hyperref}{hyperindex}[]{}
222 \define@key{LWR@hyperref}{encap}[]{}
223 \define@key{LWR@hyperref}{linkcolor}[]{}
224 \define@key{LWR@hyperref}{anchorcolor}[]{}
225 \define@key{LWR@hyperref}{citecolor}[]{}
226 \define@key{LWR@hyperref}{filecolor}[]{}
227 \define@key{LWR@hyperref}{urllcolor}[]{}
228 \define@key{LWR@hyperref}{menucolor}[]{}
229 \define@key{LWR@hyperref}{runcolor}[]{}
230 \define@key{LWR@hyperref}{allcolors}[]{}
231
232 \DeclareStringOption[false]{backref}[section]
233
234 \DeclareBoolOption{pagebackref}
235
236 \DeclareDefaultOption{}
237
238 \ProcessKeyvalOptions*\relax

```

Maybe load backref:

```

239 \ifdefstring{\LWR@hyperref@backref}{section}
240 {\RequirePackage{backref}}
241 {}
242
243 \ifdefstring{\LWR@hyperref@backref}{slide}
244 {\RequirePackage{backref}}
245 {}
246
247 \ifdefstring{\LWR@hyperref@backref}{page}
248 {\RequirePackage{backref}}

```

```

249 {}
250
251 \ifLWR@hyperref@pagebackref
252 \RequirePackage{backref}
253 \fi

254 \LetLtxMacro\href\LWR@href
255 \LetLtxMacro\nolinkurl\LWR@nolinkurl
256 \LetLtxMacro\url\LWR@url
257 \LetLtxMacro\phantomsection\LWR@phantomsection

258 \newcommand*{\hyperbaseurl}[1]{}

```

`\hyperimage`     $\{\langle URL \rangle\} \{\langle alt \text{ text} \rangle\}$

Insert an image with alt text:

```

259 \NewDocumentCommand{\LWR@hyperimageb}{m +m}{%
260 \LWR@ensuredoingapar%
261 \def\LWR@templink{#1}%
262 \@onelevel@sanitize\LWR@templink%
263 \LWR@htmltag{img src="\LWR@templink" alt="#2" class="hyperimage"%}
264 \LWR@ensuredoingapar%
265 \endgroup%
266 }
267
268 \newrobustcmd*{\hyperimage}{%
269 \begingroup%
270 \LWR@linkcatcodes%
271 \LWR@hyperimageb%
272 }
273

```

`\hyperdef`     $\{\langle 1: category \rangle\} \{\langle 2: name \rangle\} \{\langle 3: text \rangle\}$

Creates an HTML anchor to `category.name` with the given text.

```

274 \NewDocumentCommand{\LWR@hyperdefb}{m m +m}{%
275 \LWR@ensuredoingapar%
276 \LWR@label@createtag{#1.#2}%
277 #3%
278 \endgroup%
279 }
280
281 \newcommand*{\hyperdef}{%
282 \begingroup%
283 \LWR@linkcatcodes%
284 \LWR@hyperdefb%
285 }
286

```

`\LWR@hyperrefb`     $\{\langle 1: URL \rangle\} \{\langle 2: category \rangle\} \{\langle 3: name \rangle\} \{\langle 4: text \rangle\}$

Creates an HTML link to `URL#category.name` with the given text.

To avoid nested links, `\ref` is temporarily redefined to the print version.

```

287 \newcommand{\LWR@hyperreffinish}[1]{%
288 \begingroup%
289 \RenewDocumentCommand{\ref}{s m}{\LWR@print@ref{##2}}%
290 #1%
291 \endgroup%
292 \LWR@htmltag{/a}%
293 }
294
295 \newcommand*\LWR@hyperrefbb}[3]{%
296 \LWR@htmltag{%
297 a href="%
298 \detokenize\expandafter{#1}\LWR@hashmark%
299 \detokenize\expandafter{#2}.\detokenize\expandafter{#3}%
300 "%
301 \LWR@addlinktitle%
302 }%
303 \endgroup%
304 \LWR@hyperreffinish%
305 }
306
307 \newrobustcmd*\LWR@hyperrefb}{%
308 \begingroup%
309 \LWR@linkcatcodes%
310 \LWR@hyperrefbb%
311 }

```

`\LWR@hyperrefc` [*label*] {*text*}

Creates text as an HTML link to the L<sup>A</sup>T<sub>E</sub>X label.

```

312
313 \NewDocumentCommand{\LWR@hyperrefcb}{0{label}}{%
314 \LWR@startref{#1}%
315 \endgroup%
316 \LWR@hyperreffinish%
317 }
318
319 \newcommand*\LWR@hyperrefc}{%
320 \begingroup%
321 \LWR@linkcatcodes%
322 \LWR@hyperrefcb%
323 }

```

`\hyperref` {*1: URL*} {*2: category*} {*3: name*} {*4: text*} — or —  
 [*1: label*] {*2: text*}

```

324 \DeclareRobustCommand*\hyperref}{%
325 \LWR@ensuredoingapar%
326 \@ifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
327 }

```

`\hypertarget` {*name*} {*text*}

Creates an anchor to name with the given text.

```

328 \NewDocumentCommand{\LWR@hypertargetb}{m +m}{%
329 \label{LWR-ht-#1}%
330 #2%
331 \endgroup%
332 }
333
334 \newcommand*{\hypertarget}{%
335 \begingroup%
336 \LWR@linkcatcodes%
337 \LWR@hypertargetb%
338 }

```

`\hyperlink`     $\langle name \rangle$   $\langle text \rangle$

Creates a link to the anchor created by `hypertarget`, with the given link text.

Declared because also defined by `memoir`.

```

339 \DeclareDocumentCommand{\LWR@hyperlinkb}{m}{%
340 \LWR@hyperrefcb[LWR-ht-#1]%
341 }
342
343 \DeclareDocumentCommand{\hyperlink}{l}{%
344 \LWR@ensuredoingapar%
345 \begingroup%
346 \LWR@linkcatcodes%
347 \LWR@hyperlinkb%
348 }

```

`\autoref`    \*  $\langle label \rangle$

For HTML, `\cleveref` is used instead.

```

349 \NewDocumentCommand{\autoref}{s m}{%
350 \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
351 }

```

`\autopageref`     $\langle label \rangle$

For HTML, `\cleveref` is used instead.

```

352 \NewDocumentCommand{\autopageref}{s m}{%
353 \IfBooleanTF{#1}{\cpageref{#2}}{\cref{#2}}%
354 }

```

`\pdfstringdef`     $\langle macroname \rangle$   $\langle TEXstring \rangle$

```

355 \newcommand{\pdfstringdef}[2]{}

```

`\pdfbookmark`    [ $\langle level \rangle$ ]  $\langle text \rangle$   $\langle name \rangle$

```

356 \newcommand{\pdfbookmark}[3][{}]{

```

---

```

\currentpdfbookmark {\langle text \rangle} {\langle name \rangle}
357 \newcommand{\currentpdfbookmark}[2]{}

\subpdfbookmark {\langle text \rangle} {\langle name \rangle}
358 \newcommand{\subpdfbookmark}[2]{}

\belowpdfbookmark {\langle text \rangle} {\langle name \rangle}
359 \newcommand{\belowpdfbookmark}[2]{}

\texorpdfstring {\langle TEXstring \rangle} {\langle PDFstring \rangle}
360 \let\texorpdfstring\relax
361 \newcommand{\texorpdfstring}[2]{#1}

\pdfstringdefDisableCommands
362 \newcommand{\pdfstringdefDisableCommands}[1]{}

\hypercalcbp {\langle dimen \rangle} From hyperref.
363 \def\hypercalcbp#1{%
364 \strip@pt\dimexpr 0.99626401\dimexpr(#1)\relax\relax
365 }%

\Acrobatmenu {\langle menuoption \rangle} {\langle text \rangle}
366 \newcommand{\Acrobatmenu}[2]{}

\TextField [\langle parameters \rangle] {\langle label \rangle}
367 \DeclareRobustCommand{\TextField}[2]{}

\CheckBox [\langle parameters \rangle] {\langle label \rangle}
368 \DeclareRobustCommand{\CheckBox}[2]{}

\ChoiceMenu [\langle parameters \rangle] {\langle label \rangle} {\langle choices \rangle}
369 \DeclareRobustCommand{\ChoiceMenu}[3]{}

\PushButton [\langle parameters \rangle] {\langle label \rangle}
370 \DeclareRobustCommand{\PushButton}[2]{}

\Submit [\langle parameters \rangle] {\langle label \rangle}
371 \DeclareRobustCommand{\Submit}[2]{}

```

---

|                                 |                                                                     |
|---------------------------------|---------------------------------------------------------------------|
| <code>\Reset</code>             | <code>[\langle parameters \rangle] \{\langle label \rangle\}</code> |
|                                 | 372 <code>\DeclareRobustCommand{\Reset}[2]{}{}</code>               |
| <code>\Gauge</code>             | <code>[\langle parameters \rangle] \{\langle label \rangle\}</code> |
|                                 | 373 <code>\DeclareRobustCommand{\Gauge}[2]{}{}</code>               |
| <code>\LayoutTextField</code>   | <code>\{\langle label \rangle\} \{\langle field \rangle\}</code>    |
|                                 | 374 <code>\newcommand*{\LayoutTextField}[2]{}{}</code>              |
| <code>\LayoutChoiceField</code> | <code>\{\langle label \rangle\} \{\langle field \rangle\}</code>    |
|                                 | 375 <code>\newcommand*{\LayoutChoiceField}[2]{}{}</code>            |
| <code>\LayoutCheckField</code>  | <code>\{\langle label \rangle\} \{\langle field \rangle\}</code>    |
|                                 | 376 <code>\newcommand*{\LayoutCheckField}[2]{}{}</code>             |
| <code>\MakeRadioField</code>    | <code>\{\langle width \rangle\} \{\langle height \rangle\}</code>   |
|                                 | 377 <code>\newcommand*{\MakeRadioField}[2]{}{}</code>               |
| <code>\MakeCheckField</code>    | <code>\{\langle width \rangle\} \{\langle height \rangle\}</code>   |
|                                 | 378 <code>\newcommand*{\MakeCheckField}[2]{}{}</code>               |
| <code>\MakeTextField</code>     | <code>\{\langle width \rangle\} \{\langle height \rangle\}</code>   |
|                                 | 379 <code>\newcommand*{\MakeTextField}[2]{}{}</code>                |
| <code>\MakeChoiceField</code>   | <code>\{\langle width \rangle\} \{\langle height \rangle\}</code>   |
|                                 | 380 <code>\newcommand*{\MakeChoiceField}[2]{}{}</code>              |
| <code>\MakeFieldButton</code>   | <code>\{\langle text \rangle\}</code>                               |
|                                 | 381 <code>\newcommand{\MakeFieldButton}[1]{}{}</code>               |

---

File 215 **lwarp-hyperxmp.sty**

§ 321 Package **hyperxmp**

Pkg hyperxmp hyperxmp is ignored.

**for HTML output:** Discard all options for lwarp-hyperxmp:

1 `\LWR@ProvidesPackageDrop{hyperxmp}[2018/11/27]`

---

File 216 **lwarp-hyphenat.sty**

§ 322 Package **hyphenat**

Pkg hyphenat **hyphenat** is emulated during HTML output, while the print-mode version is used inside a `lateximage`.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{hyphenat}[2009/09/02]
2 \LetLtxMacro\LWRHYNAT@origtextnhtt\textnhtt
3 \LetLtxMacro\LWRHYNAT@originhttfamily\nhttfamily
4 \LetLtxMacro\LWRHYNAT@originohyphens\nohyphens
5 \LetLtxMacro\LWRHYNAT@origbshyp\bshyp
6 \LetLtxMacro\LWRHYNAT@origfshyp\fshyp
7 \LetLtxMacro\LWRHYNAT@origdothyp\dothyp
8 \LetLtxMacro\LWRHYNAT@origcolonhyp\colonhyp
9 \LetLtxMacro\LWRHYNAT@orighyp\hyp
10
11 \LetLtxMacro\textnhtt\texttt
12 \LetLtxMacro\nhttfamily\ttfamily
13
14 \renewcommand{\nohyphens}[1]{#1}
15 \renewrobustcmd{\bshyp}{%
16 \ifmmode\backslash\else\textbackslash\fi%
17 }
18 \renewrobustcmd{\fshyp}{/}
19 \renewrobustcmd{\dothyp}{.}
20 \renewrobustcmd{\colonhyp}{:}
21 \renewrobustcmd{\hyp}{-}
22
23 \appto\LWR@restoreorigformatting{%
24 \LetLtxMacro\textnhtt\LWRHYNAT@origtextnhtt%
25 \LetLtxMacro\nhttfamily\LWRHYNAT@originhttfamily%
26 \LetLtxMacro\nohyphens\LWRHYNAT@originohyphens%
27 \LetLtxMacro\bshyp\LWRHYNAT@origbshyp%
28 \LetLtxMacro\fshyp\LWRHYNAT@origfshyp%
29 \LetLtxMacro\dothyp\LWRHYNAT@origdothyp%
30 \LetLtxMacro\colonhyp\LWRHYNAT@origcolonhyp%
31 \LetLtxMacro\hyp\LWRHYNAT@orighyp%
32 }

```

---

File 217 **lwarp-idxlayout.sty**

§ 323 Package **idxlayout**

*(Emulates or patches code by THOMAS TITZ.)*

Pkg idxlayout **idxlayout** is emulated.

**for HTML output:** Discard all options for lwarp-idxlayout:

```
1 \LWR@ProvidesPackageDrop{idxlayout}[2012/03/30]
```

```
2 \newcommand{\LWR@indexprenote}{}
```

\AtBeginDocument to help with package load order.

```
3 \AtBeginDocument{
4 \preto\printindex{
5
6 \LWR@maybe@orignewpage
7 \LWR@startpars
8
9 \LWR@indexprenote
10
11 }
12 }
```

```
13 \newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
```

```
14 \newcommand*{\noindexprenote}{\renewcommand{\LWR@indexprenote}{}}
```

```
15
```

```
16 \newcommand{\idxlayout}[1]{}

```

```
17 \newcommand*{\indexfont}{}

```

```
18 \newcommand*{\indexjustific}{}

```

```
19 \newcommand*{\indexsubsdelim}{}

```

```
20 \newcommand*{\indexstheadcase}{}

```

File 218 **lwarp-ifoddpager.sty**

§ 324 Package **ifoddpager**

*(Emulates or patches code by MARTIN SCHARRER.)*

Pkg ifoddpager ifoddpager is emulated.

**for HTML output:** Discard all options for lwarp-ifoddpager:

```
1 \LWR@ProvidesPackageDrop{ifoddpager}[2016/04/23]
```

```
2 \newif\ifoddpager

```

```
3
```

```
4 \newif\ifoddpageroroneside

```

```
5
```

```
6 \DeclareRobustCommand{\checkoddpager}{\oddpagertrue\oddpageroronesidetrue}

```

```
7
```

```
8 \def\oddpager@page{1}

```

```
9
```

```
10 \def\@ifoddpager{%

```

```
11 \expandafter\@firstoftwo

```

```
12 }

```

```
13
```

```

14 \def\@ifoddpagoroneside{%
15 \expandafter\@firstoftwo
16 }

```

File 219 **lwarp-imakeidx.sty**

§ 325 Package **imakeidx**

(Emulates or patches code by ENRICO GREGORIO.)

Pkg imakeidx imakeidx is patched for use by lwarp.

**letter headings** When using *makeindex*, to match the print and HTML output's display of index letter headings, specify the `lwarp.ist` style:

```
\makeindex[options={-s lwarp.ist}]
```

(For HTML the `lwarp.ist` style is used automatically, which displays letter headings. When using *xindy* the default style also displays letter headings.)

**index setup** See section 8.6.18 for how to setup *lwarpmk* to process the indexes with *imakeidx*, both with and without shell escape.

**for HTML output:** 1 \LWR@ProvidesPackagePass{imakeidx}[2016/10/15]

Use the new HTML suffix:

```

2 \catcode'_ =12%
3 \define@key{imki}{name}{\def\imki@name{#1_html}}
4 \catcode'_ =8%

```

`\printindex` The HTML version of `\printindex`:

```

5 \catcode'_ =12%
6
7 \renewcommand*\printindex[1][\imki@jobname]{%
8 \LWR@maybe@orignewpage%
9 \LWR@startpars%
10 \ifstrequal{#1}{\imki@jobname}{%
11 \@ifundefined{#1@idxfile}{%
12 \imki@error{#1}%
13 }{%
14 \imki@putindex{#1}%
15 }%
16 }{%
17 \@ifundefined{#1_html@idxfile}{\imki@error{#1_html}}{\imki@putindex{#1_html}}%
18 }%
19 }
20
21 \catcode'_ =8%

```

`\@index` The HTML version of `\@index`:

```

22 \catcode'_ =12%
23
24 \def\@index[#1]{%
25 \ifstrequal{#1}{\imki@jobname}%
26 {%
27 \@ifundefined{#1@idxfile}%
28 {%
29 \PackageWarning{lwarp-imakeidx}{Undefined index file '#1'}%
30 \begingroup
31 \@sanitize
32 \imki@nowrindex%
33 }%
34 {%
35 \edef\@idxfile{#1}%
36 \begingroup
37 \@sanitize
38 \@wrindex\@idxfile%
39 }%
40 }%
41 {%
42 \@ifundefined{#1_html@idxfile}%
43 {%
44 \PackageWarning{lwarp-imakeidx}{Undefined index file '#1_html'}%
45 \begingroup
46 \@sanitize
47 \imki@nowrindex%
48 }%
49 {%
50 \edef\@idxfile{#1_html}%
51 \begingroup
52 \@sanitize
53 \@wrindex\@idxfile%
54 }%
55 }%
56 }
57
58 \catcode'_ =8%
```

`\item`

`\subitem`

`\subsubitem` HTML versions of `\item`, etc.:

```

59 \appto\theindex{%
60 \let\item\LWR@indexitem%
61 \let\subitem\LWR@indexsubitem%
62 \let\subsubitem\LWR@indexsubsubitem%
63 }
```

`\imki@wrindexentrysplit`  $\{\langle file \rangle\} \{\langle entry \rangle\} \{\langle page \rangle\}$

`\imki@wrindexentryunique`  $\{\langle file \rangle\} \{\langle entry \rangle\} \{\langle page \rangle\}$

While writing index entries, adds an HTML label, and writes the label's index instead of the page number:

```

64 \renewcommand\imki@wrindexentrysplit[3]{%
65 \addtocounter{LWR@autoindex}{1}%
66 \label{LWRindex-\arabic{LWR@autoindex}}%
67 \expandafter\protected@write\csname#1@idxfile\endcsname{%
68 {\string\indexentry{#2}{\arabic{LWR@autoindex}}}%
69 }
70
71 \renewcommand\imki@wrindexentryunique[3]{%
72 \addtocounter{LWR@autoindex}{1}%
73 \label{LWRindex-\arabic{LWR@autoindex}}%
74 \protected@write\@indexfile{%
75 {\string\indexentry[#1]{#2}{\arabic{LWR@autoindex}}}%
76 }
77
78 \def\imki@wrindexsplit#1#2{%
79 \imki@wrindexentrysplit{#1}{#2}{\thepage}%
80 \endgroup\imki@showindexentry{#1}{#2}%
81 \@esphack%
82 }
83
84 \def\imki@wrindexunique#1#2{%
85 \imki@wrindexentryunique{#1}{#2}{\thepage}%
86 \endgroup\imki@showindexentry{#1}{#2}%
87 \@esphack%
88 }
89

```

`\LWR@imki@setxdydefopts`

Sets the *xindy* HTML options, ignoring the user's settings.

```

90 \newcommand*\LWR@imki@setxdydefopts{%
91 \edef\imki@options{ \space %
92 -M \space \LWR@xindyStyle\space %
93 -L \space \LWR@xindyLanguage\space %
94 -C \space \LWR@xindyCodepage\space %
95 }%
96 }

```

`\LWR@imki@setdefopts`    *{(user options)}*

Sets the HTML options, added to the user's settings, depending on whether *makeindex* or *xindy* are used.

For *makeindex*, the user's choice is ignored, and only the lwarp version is used. (Only one style at a time is possible.)

For *xindy*, multiple modules may be specified, and the lwarp version is appended.

```

97 \newcommand*\LWR@imki@setdefopts[1]{%
98 \ifblank{#1}{%
99 \edef\imki@options{\space -s \space \LWR@makeindexStyle \space}%
100 \ifdefstring{\imki@progdefault}{xindy}{\LWR@imki@setxdydefopts}{%
101 \ifdefstring{\imki@progdefault}{texindy}{\LWR@imki@setxdydefopts}{%
102 \ifdefstring{\imki@progdefault}{truexindy}{\LWR@imki@setxdydefopts}{%

```

```

103 }{%
104 \edef\imki@options{\space #1 \space}%
105 }%
106 }

```

`\imki@makeindex` Use the new HTML options:

```

107 \xpatchcmd{\imki@makeindex}
108 {\let\imki@options\space}
109 {\LWR@imki@setdefopts{}}%
110 {}
111 {\LWR@patcherror{imakeidx}{makeindex}}

```

Use the new HTML options.

```

112 \define@key{imki}{options}{\LWR@imki@setdefopts{#1}}

```

`\imki@resetdefaults` Use the new HTML options:

```

113 \xpatchcmd{\imki@resetdefaults}
114 {\def\imki@options{ }}
115 {\LWR@imki@setdefopts{}}
116 {}
117 {\LWR@patcherror{imakeidx}{resetdefaults}}

```

`theindex` was already defined `\AtBeginDocument` by the `lwarp` core, so it must be redefined here similarly, but patched for `imakeidx`:

Env `theindex`

```

118 \AtBeginDocument{
119 \renewenvironment*{theindex}{%
120 \imki@maybeaddtoc
121 \imki@indexlevel{\indexname}
122 \let\item\LWR@indexitem%
123 \let\subitem\LWR@indexsubitem%
124 \let\subsubitem\LWR@indexsubsubitem%
125 }{}
126 }% \AtBeginDocument

```

Update to the new defaults:

```

127 \imki@resetdefaults

```

Update to the new patches:

`\AtBeginDocument` is because `\@wrindex` is previously defined as `\AtBeginDocument` in the `lwarp` core.

```

128 \ifimki@splitindex
129 \let\imki@startidx\imki@startidxunique
130 \AtBeginDocument{\let\@wrindex\imki@wrindexunique}
131 \let\imki@putindex\imki@putindexunique
132 \let\imki@wrindexentry\imki@wrindexentryunique
133 \let\imki@startidxsplit\@undefined

```

```

134 \let\imki@wrindexsplit\undefined
135 \let\imki@putindexsplit\undefined
136 \else
137 \let\imki@startidx\imki@startidxsplit
138 \AtBeginDocument{\let\@wrindex\imki@wrindexsplit}
139 \let\imki@putindex\imki@putindexsplit
140 \let\imki@wrindexentry\imki@wrindexentrysplit
141 \let\imki@startidxunique\undefined
142 \let\imki@wrindexunique\undefined
143 \let\imki@putindexunique\undefined
144 \fi

```

---

File 220 **lwarp-index.sty**

§ 326 Package **index**

*(Emulates or patches code by DAVID M. JONES.)*

Pkg index **index** is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{index}[2004/01/20]

Use `\theLWR@autoindex` instead of `\thepage`. `\@tempwatrue` is used to force an immediate write to the index file instead of waiting until the end of the page.

```

2 \xpatchcmd{\newindex}
3 {\x@newindex[thepage]}
4 {%
5 \@tempwatrue%
6 \x@newindex[theLWR@autoindex]%
7 }
8 {}
9 {\LWR@patcherror{index}{newindex}}
10
11 \xpatchcmd{\renewindex}
12 {\x@renewindex[thepage]}
13 {%
14 \@tempwatrue%
15 \x@renewindex[theLWR@autoindex]%
16 }
17 {}
18 {\LWR@patcherror{index}{renewindex}}

```

Patched to set a new autoindex:

```

19 \xpatchcmd{\@wrindex}
20 {\begingroup}
21 {%
22 \addtocounter{LWR@autoindex}{1}% lwarp
23 \label{LWRindex-\arabic{LWR@autoindex}}% lwarp
24 \begingroup%
25 }

```

```

26 {}
27 {\LWR@patcherror{index}{@windex}}

```

\AtBeginDocument **lwarp** core \lets \@windex to \LWR@windex. Since the `index` package has been loaded, \let to its version instead:

```

28 \let\LWR@index@windex\@windex
29
30 \AtBeginDocument{
31 \let\@windex\LWR@index@windex
32 }

```

Modified to add \index@prologue:

```

33 \AtBeginDocument{
34 \renewenvironment*{theindex}{%
35 \LWR@indexsection{\indexname}%
36 \ifx\index@prologue\@empty\else
37 \index@prologue
38 \bigskip
39 \fi
40 \let\item\LWR@indexitem%
41 \let\subitem\LWR@indexsubitem%
42 \let\subsubitem\LWR@indexsubsubitem%
43 }{}
44 }% AtBeginDocument

```

Disabled:

```

45 \def\@showidx#1{}
46 \let\@texttop\relax
47 \renewcommand*{\raggedbottom}{}
48 \renewcommand*{\flushbottom}{}
49 \renewcommand*{\markboth}[2]{}
50 \renewcommand*{\markright}[1]{}

```

File 221 **lwarp-inputtrc.sty**

§ 327 Package **inputtrc**

*(Emulates or patches code by Uwe Lück.)*

Pkg inputtrc **inputtrc** is patched for use by **lwarp**.

**for HTML output:** 1 \LWR@ProvidesPackagePass{inputtrc}[2012/10/10]

Patched to remove extraneous spaces, which sometimes showed up in logos inside a `lateximage`.

```

2 \renewcommand*{\IT@prim@input}[1]{%
3 \typeout{\IT@indent\IT@currfile INPUTTING #1}%
4 %% ... TODO: option to write to '.log' only.

```

```

5 \xdef\IT@filestack{{\IT@currfile}\IT@filestack}%
6 \xdef\IT@currfile{#1}%
7 \expandafter \gdef\expandafter \IT@indent\expandafter{%
8 \IT@indent \IT@indent@unit}% lwarp
9 \@input#1% lwarp
10 \expandafter\IT@pop@indent\IT@indent \@nil% lwarp
11 \expandafter\IT@pop@file \IT@filestack\@nil% lwarp
12 \IT@maybe@returnmessage% v0.2 lwarp
13 }

```

---

File 222 **lwarp-intopdf.sty**

§ 328 Package **intopdf**

Pkg intopdf intopdf is emulated.

The filespec, MIME type, and description are ignored for now.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop[intopdf][2019/05/28]

2 \NewDocumentCommand{\attachandlink}{o m o m m}{%
3 \LWR@href{#2}{#5}%
4 }

```

---

File 223 **lwarp-jurabib.sty**

§ 329 Package **jurabib**

*(Emulates or patches code by JENS BERGER.)*

Pkg jurabib jurabib is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass[jurabib][2004/01/25]

2 \renewrobustcmd{\jblangle}{\textless}
3
4 \renewrobustcmd{\jbrangle}{\textgreater}
5
6 \renewcommand*{\jb@biblaw@item}{%
7 \hspace{0.5em}%
8 \triangleright
9 \HTMLUnicode{25B7}% lwarp
10 \hspace{0.5em}%
11 }
12
13 \renewrobustcmd{\jbarchsig}[2]{%
14 \ifjbweareinbib
15 \settowidth{\jb@subarchitemwidth}{\jbsamesubarchindent+#1}%
16 \setlength{\jb@subarchentrywidth}{\textwidth-\jb@subarchitemwidth-4em}%
17 % \begin{tabular}{@{}p{\jb@subarchitemwidth}@{}j{\jb@subarchentrywidth}@{}}%

```

```

18 #1\ifjb@dot\unskip\unskip\unskip.\fi
19 % &
20 \quad% lwarp
21 \ifthenelse{\equal{#2}{}}{\jbarchnameformat{#2}}%
22 % \end{tabular}
23 \fi
24 }%
25
26
27 \xpatchcmd{\jb@do@post@item}
28 {\begin{tabular}{p{\jb@biblaw@item@width}j{\jb@biblaw@entry@width}}}
29 {}
30 {}
31 {\LWR@patcherror{jurabib}{jb@do@post@item 1}}
32
33 \xpatchcmd{\jb@do@post@item}
34 {\multicolumn{2}{p{\columnwidth}}{\jb@name}}
35 {\jb@name}
36 {}
37 {\LWR@patcherror{jurabib}{jb@do@post@item 2}}
38
39 \xpatchcmd{\jb@do@post@item}
40 {\jb@biblaw@item & \jb@fulltitle}
41 {\jb@biblaw@item \quad \jb@fulltitle}
42 {}
43 {\LWR@patcherror{jurabib}{jb@do@post@item 3}}
44
45 \xpatchcmd{\jb@do@post@item}
46 {\end{tabular}}
47 {}
48 {}
49 {\LWR@patcherror{jurabib}{jb@do@post@item 4}}
50
51 \xpatchcmd{\jb@do@post@item}
52 {\begin{minipage}[t]{\bibnumberwidth}}
53 {}
54 {}
55 {\LWR@patcherror{jurabib}{jb@do@post@item 5}}
56
57 \xpatchcmd{\jb@do@post@item}
58 {\end{minipage}}
59 {\quad}
60 {}
61 {\LWR@patcherror{jurabib}{jb@do@post@item 6}}

```

---

File 224 **lwarp-karnaugh-map.sty**

§ 330 Package **karnaugh-map**

*(Emulates or patches code by MATTIAS JACOBSSON.)*

Pkg karnaugh-map karnaugh-map is patched for use by lwarp.



```

51 00 \& |(000000)| \& |(000001)| \& |(000011)| \& |(0000
52 01 \& |(000100)| \& |(000101)| \& |(000111)| \& |(0001
53 11 \& |(001100)| \& |(001101)| \& |(001111)| \& |(0011
54 10 \& |(001000)| \& |(001001)| \& |(001011)| \& |(0010
55 \&
56 \&
57 \&
58 \&
59 \&
60 \&
61 00 \& |(000000)| \& |(000001)| \& |(000011)| \& |(0000
62 01 \& |(000100)| \& |(000101)| \& |(000111)| \& |(0001
63 11 \& |(001100)| \& |(001101)| \& |(001111)| \& |(0011
64 10 \& |(001000)| \& |(001001)| \& |(001011)| \& |(0010
65 \&
66 \&
67 \&
68 \&
69 \&
70 \&
71 00 \& |(000000)| \& |(000001)| \& |(000011)| \& |(0000
72 01 \& |(000100)| \& |(000101)| \& |(000111)| \& |(0001
73 11 \& |(001100)| \& |(001101)| \& |(001111)| \& |(0011
74 10 \& |(001000)| \& |(001001)| \& |(001011)| \& |(0010
75 \&
76 \&
77 \&
78 \&
79 \&
80 \&
81 00 \& |(100000)| \& |(100001)| \& |(100011)| \& |(1000
82 01 \& |(100100)| \& |(100101)| \& |(100111)| \& |(1001
83 11 \& |(101100)| \& |(101101)| \& |(101111)| \& |(1011
84 10 \& |(101000)| \& |(101001)| \& |(101011)| \& |(1010
85 \&
86 \&
87 \&
88 \&
89 \&
90 \&
91 00 \& |(100000)| \& |(100001)| \& |(100011)| \& |(1000
92 01 \& |(100100)| \& |(100101)| \& |(100111)| \& |(1001
93 11 \& |(101100)| \& |(101101)| \& |(101111)| \& |(1011
94 10 \& |(101000)| \& |(101001)| \& |(101011)| \& |(1010
95 \&
96 \&
97 \&
98 \&
99 \&
100 \&
101 \renewcommand{\@karnaughmap@local@maprealignmentx}{2.5}%
102 \renewcommand{\@karnaughmap@local@maprealignmenty}{-2.5}%
103 \fi
104 % [END]}
105 % test if a matrix template is found or not(aka "\@karnaughmap@local@matrixtemplate@" equals to '0')
106 \ifdefstring{\@karnaughmap@local@matrixtemplate@}{0}{% lwarp
107 \ifnum0=\@karnaughmap@local@matrixtemplate@% original
108 % print error if no template could be found
109 \PackageError{lwarp-karnaugh-map}{%
110 Can not find a template fitting your specification (\@karnaughmap@var@mapsizex\space x \@karnaughma
111 }{%
112 Existing templates have the following dimensions: 2x2x1, 2x4x1, 4x2x1, 4x4x1, 4x4x2, and 4x4x4.
113 }%
114 \fi original
115 }{\relax}% lwarp
116 \begin{tikzpicture}
117 % grid
118 % for all dimensions
119 \draw[color=black, ultra thin] (0,0) grid (\@karnaughmap@var@mapsizex,\@karnaughmap@var@mapsizex);
120 % when there are 2 sub maps
121 \ifnum\@karnaughmap@var@mapsizex=2
122 \draw[color=black, ultra thin] (5,0) grid (9,4);
123 \fi

```

```

106 % when there are 4 sub maps
107 \ifnum\@karnaughmap@var@mapsize@=4
108 \draw[color=black, ultra thin] (5,0) grid (9,4);
109 \draw[color=black, ultra thin] (0,-5) grid (4,-1);
110 \draw[color=black, ultra thin] (5,-5) grid (9,-1);
111 \fi
112 % labels
113 % for all dimensions
114 \node[above] at (\@karnaughmap@var@mapsize@*0.5,\@karnaughmap@var@mapsize@+0.9) {\small{#5}};
115 \node[left] at (-0.9,\@karnaughmap@var@mapsize@*0.5) {\small{#6}};
116 % when there are 2 sub maps
117 \ifnum\@karnaughmap@var@mapsize@=2
118 \node[above] at (7,4.9) {\small{#5}};
119 % extra sub maps labels
120 \node[below] at (2,-0.1) {\small{#7$=0$}};
121 \node[below] at (7,-0.1) {\small{#7$=1$}};
122 \fi
123 % when there are 4 sub maps
124 \ifnum\@karnaughmap@var@mapsize@=4
125 \node[above] at (7,4.9) {\small{#5}};
126 \node[left] at (-0.9,-3) {\small{#6}};
127 % extra sub maps labels
128 \node[below] at (2,-0.1) {\small{#7$=00$}};
129 \node[below] at (7,-0.1) {\small{#7$=01$}};
130 \node[below] at (2,-5.1) {\small{#7$=10$}};
131 \node[below] at (7,-5.1) {\small{#7$=11$}};
132 \fi
133 % data
134 \matrix[
135 matrix of nodes,
136 ampersand replacement=\&,
137 column sep={1cm,between origins},
138 row sep={1cm,between origins},
139] at (\@karnaughmap@var@mapsize@*0.5+\@karnaughmap@local@maprealignment@,\@karnaughmap@var@mapsize@*0.5)
140 \@karnaughmap@local@matrixtemplate@
141 };
142 }{
143 \end{tikzpicture}
144 \endgroup
145 }

```

---

File 225 **lwarp-keyfloat.sty**

§ 331 Package **keyfloat**

(Emulates or patches code by BRIAN DUNN.)

Pkg keyfloat **keyfloat** is supported with a considerable amount of hacking. (It's a mashup of **lwarp**, **keyfloat**, and **tocdata**.)

⚠ **keywrap** If placing a `\keyfig[H]` inside a **keywrap**, use an absolute width for `\keyfig`, instead of **lw**-proportional widths. (The `[H]` option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the **lw** option.)

for HTML output:

```

1 \LWR@ProvidesPackagePass[keyfloat][2019/09/23]
2
3 \@ifpackagelater{keyfloat}{2019/09/23}{\relax}{
4 \PackageError{lwarp-keyfloat}
5 {%
6 The keyfloat package is out of date.\MessageBreak
7 Update to keyfloat v2.01 2019/09/23 or later%
8 }
9 {%
10 Please update the keyfloat package. It's worth it!%
11 }
12 }
```

After keyfloat has loaded:

```

13 \AtBeginDocument{

14 \providecommand*\KFLT@LWR@hook@boxouter{}
15 \renewcommand*\KFLT@LWR@hook@boxouter{%
16 \ifbool{KFLT@keywrap}{%
17 }{%
18 \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
19 \setlength{\linewidth}{6in}%
20 \setlength{\textwidth}{6in}%
21 \setlength{\textheight}{9in}%
22 }{}%
23 }%
24 \normalcolor%
25 }

26 \let\ltxMacro\KFLT@LWR@hook@keysubfloats\KFLT@LWR@hook@boxouter
27
28 \let\KFLT@LWR@hook@keyfloatsminipage\relax
29 \let\endKFLT@LWR@hook@keyfloatsminipage\relax
30 \newenvironment{KFLT@LWR@hook@keyfloatsminipage}[1]{}{}

31 \let\ltxMacro\KFLT@LWR@hook@keyfloats\KFLT@LWR@hook@boxouter
32
33 \renewcommand*\KFLT@maybeendfloatrow{%
34 \ifnumless{\value{KFLT@thiscol}}{\value{KFLT@numcols}}%
35 }{% thiscol < numcols
36 }{% >=
37 \defcounter{KFLT@thiscol}{0}%
38 }%
39 }%
40
41 \renewcommand{\KFLT@trackrows}%
42 {%
```

If are nested inside a keyfloats or a subfloat:

```

43 \ifboolexpr{%
44 test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or%
```

```

45 bool{KFLT@inkeysubfloats}%
46 }%
47 {% nested

```

Tracks row start and end:

```

48 \KFLT@maybestartfloatrow%

```

Possibly fill space between columns:

```

49 \ifnumgreater{\value{KFLT@thiscol}}{1}%
50 {%
51 % \hfill%
52 }%
53 }%
54 }% nested
55 }% not nested
56 }

57 \RenewDocumentCommand{\KFLT@onefigureimage}{m}
58 {%
59 \LWR@traceinfo{KFLT@onefigureimage}%
60 % \begin{lrbox}{\KFLT@envbox}%
61 \ifthenelse{\NOT\equal{\KFLT@lw}{}}%
62 {%
63 \KFLT@frame{\includegraphics%
64 [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
65 }%
66 {% not linewidth
67 \ifthenelse{\dimtest{\KFLT@w}{>}{0pt}}%
68 {% width is given
69 \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
70 {% w and h
71 \KFLT@frame{\includegraphics%
72 [scale=\KFLT@s,%
73 width=\KFLT@imagewidth,height=\KFLT@h]{#1}}%
74 }% w and h
75 {% only w
76 \KFLT@frame{\includegraphics%
77 [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
78 }% only w
79 }% width is given
80 {% width is not given
81 \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
82 {%
83 \KFLT@frame{\includegraphics%
84 [scale=\KFLT@s,height=\KFLT@h]{#1}}%
85 }%
86 {%
87 \KFLT@frame{\includegraphics%
88 [scale=\KFLT@s]{#1}}%
89 }%
90 }% width is not given
91 }% not linewidth
92 % \end{lrbox}%

```

```

93 % \unskip%
94 % \KFLT@findenvboxwidth%
95 % \begin{turn}{\KFLT@r}%
96 % \KFLT@frame{\usebox{\KFLT@envbox}}%
97 % \unskip%
98 % \end{turn}%
99 \LWR@traceinfo{KFLT@onefigureimage: done}%
100 }

101 \RenewDocumentEnvironment{KFLT@boxinner}{%
102 {%
103 \LWR@traceinfo{KFLT@boxinner}%
104 \LWR@stoppars%
105 \minipagefullwidth%
106 \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{%
107 \fminipage{\KFLT@imagewidth}%
108 }{%
109 \minipage{\KFLT@imagewidth}%
110 }%
111 }
112 {%
113 \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{%
114 \endfminipage%
115 }{%
116 \endminipage%
117 }%
118 \LWR@startpars%
119 \LWR@traceinfo{KFLT@boxinner: done}%
120 }

121 \newcommand*\LWR@KFLT@settalign}[1]{%
122 \def\LWR@KFLT@textalign{justify}%
123 \ifcsstring{KFLT@#1textalign}{\centering}%
124 {\def\LWR@KFLT@textalign{center}}%
125 }%
126 \ifcsstring{KFLT@#1textalign}{\raggedleft}%
127 {\def\LWR@KFLT@textalign{right}}%
128 }%
129 \ifcsstring{KFLT@#1textalign}{\raggedright}%
130 {\def\LWR@KFLT@textalign{left}}%
131 }%
132 }
133
134 \renewcommand{\KFLT@addtext}[1]
135 {%

Is there text to add?

136 \ifcempty{KFLT@#1t}%
137 }% no text
138 {% text to add
139 }% local

```

Add some space, then create a <div> to contain the text:

```

140 \addvspace{\smallskipamount}%
141 \LWR@KFLT@settextalign{#1}%
142 \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%

```

Set the alignment and some text parameters:

```

143 % \csuse{KFLT@#1textalign}%
144 % \footnotesize%
145 \setlength{\parskip}{1.5ex}%
146 \setlength{\parindent}{0em}%

```

Typeset the actual text:

```

147 \csuse{KFLT@#1t}%

```

Close it all out with a little more space:

```

148 \end{BlockClass}%
149 % \par\addvspace{2ex}%
150 }% local
151 }% text to add
152 }
153
154 \ifpackageloaded{tocdata}
155 {}
156 {% tocdata not loaded
157
158 \newcommand*\LWR@KFLT@setnamealign[1]{%
159 \def\LWR@KFLT@textalign{justify}%
160 \ifstrequal{#1}{\centering}%
161 {\def\LWR@KFLT@textalign{center}}%
162 {}%
163 \ifstrequal{#1}{\raggedleft}%
164 {\def\LWR@KFLT@textalign{right}}%
165 {}%
166 \ifstrequal{#1}{\raggedright}%
167 {\def\LWR@KFLT@textalign{left}}%
168 {}%
169 }
170
171 \renewcommand*\KFLT@addartisttext[3]{%
172

```

Add space and create the name inside a <div>:

```

173 % \addvspace{\medskipamount}%
174 % \begin{minipage}{\linewidth}%
175 \LWR@KFLT@setnamealign{#3}%
176 \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%
177

```

Text alignment is #3, and depends on artist or author:

```

178 % #3%
179

```

#1 is empty or 'subgrp'  
 #2 is empty for artist, 'u' for author:

```

180 \footnotesize\textsc{%
181 \KFLT@optionalname{\csuse{KFLT@#1a#2p}}%
182 \KFLT@optionalname{\csuse{KFLT@#1a#2f}}%
183 \csuse{KFLT@#1a#2L}%
184 \csuse{KFLT@#1a#2s}%
185 }%
186 % \end{minipage}%
187 \end{BlockClass}
188 % \par\advspace{2ex}%
189 }
190
191}% tocd data not loaded

```

Env KFLT@marginfloat [*<offset>*] {*<type>*}

```

192 \DeclareDocumentEnvironment{KFLT@marginfloat}{0{-1.2ex} m}
193 {%
194 \uselengthunit{PT}%
195 \LWR@BlockClassWP%
196 {float:right; width:2in; margin:10pt}%
197 {}%
198 {marginblock}%
199 \renewcommand*{\@capttype}{#2}%
200 \minipage{\LWR@usersmarginparwidth}%
201 \setlength{\marginparwidth}{.95\LWR@usersmarginparwidth}%
202 }
203 {%
204 \endminipage%
205 \endLWR@BlockClassWP%
206 }

207 \DeclareDocumentEnvironment{marginfigure}{o}
208 {\begin{KFLT@marginfloat}{figure}}
209 {\end{KFLT@marginfloat}}
210
211 \DeclareDocumentEnvironment{margintable}{o}
212 {\begin{KFLT@marginfloat}{table}}
213 {\end{KFLT@marginfloat}}

```

Env keywrap {*<width>*} {*<keyfloat>*}

```

214 \DeclareDocumentEnvironment{keywrap}{m +m}
215 {%
216 \begin{LWR@setvirtualpage}*
217 \setlength{\LWR@templengthone}{#1}%
218 \begin{LWR@BlockClassWP}%
219 {%
220 float:right; width:\LWR@printlength{\LWR@templengthone}; % extra space
221 margin:10pt%
222 }%
223 }%

```

```

224 {marginblock}%
225 \setlength{\linewidth}{.95\LWR@templengthone}%
226 \booltrue{KFLT@keywrap}%
227 #2%
228 \end{LWR@BlockClassWP}%
229 \end{LWR@setvirtualpage}%
230 }
231 {}

232 }% AtBeginDocument

```

---

File 226 **lwarp-keystroke.sty**

§ 332 Package **keystroke**

*(Emulates or patches code by WERNER FINK.)*

Pkg keystroke **keystroke** is patched for use by **lwarp**.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{keystroke}[2010/04/23]

2 \newcommand*\LWR@HTML@keystroke}[1]{
3 \InlineClass{keystroke}{#1}
4 }
5 \LWR@formatted{keystroke}
6
7
8 \newcommand*\LWR@HTML@Return}{\keystroke{\HTMLUnicode{021A9}}}
9 \LWR@formatted{Return}
10
11 \newcommand*\LWR@HTML@BSpace}{\keystroke{\HTMLUnicode{027FB}}}
12 \LWR@formatted{BSpace}
13
14 \newcommand*\LWR@HTML@Tab}{\keystroke{| \HTMLUnicode{021C6}|}}
15 \LWR@formatted{Tab}
16
17 \newcommand*\LWR@HTML@UArrow}{\keystroke{\HTMLUnicode{02191}}}
18 \LWR@formatted{UArrow}
19
20 \newcommand*\LWR@HTML@DArrow}{\keystroke{\HTMLUnicode{02193}}}
21 \LWR@formatted{DArrow}
22
23 \newcommand*\LWR@HTML@LArrow}{\keystroke{\HTMLUnicode{02190}}}
24 \LWR@formatted{LArrow}
25
26 \newcommand*\LWR@HTML@RArrow}{\keystroke{\HTMLUnicode{02192}}}
27 \LWR@formatted{RArrow}
28
29 % Preserves the language options:
30 \LetLtxMacro\LWR@HTML@Shift\Shift
31 \xpatchcmd{\LWR@HTML@Shift}
32 {\Uparrow}

```

```

33 {\HTMLUnicode{21D1}}
34 {}
35 {}
36 \LWR@formatted{Shift}
37
38 \LetLtxMacro\LWR@HTML@PgUp\PgUp
39 \xpatchcmd{\LWR@HTML@PgUp}
40 {\$ \uparrow}
41 {\HTMLUnicode{2191}}
42 {}
43 {}
44 \LWR@formatted{PgUp}
45
46 \LetLtxMacro\LWR@HTML@PgDown\PgDown
47 \xpatchcmd{\LWR@HTML@PgDown}
48 {\$ \downarrow}
49 {\HTMLUnicode{2193}}
50 {}
51 {}
52 \LWR@formatted{PgDown}

```

---

File 227 **lwarp-kpfonts.sty**

§ 333 Package **kpfonts**

(Emulates or patches code by CHRISTOPHE CAIGNAERT.)

Pkg kpfonts kpfonts is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation honors the options uprightRoman for \D only, classicReIm, frenchstyle for Greek only, upright for Greek only, uprightgreeks, slantedGreeks, and mathcalasscript.

The dedicated macros for Greek work correctly.

svg math should appear the same as the printed output.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass[kpfonts][2010/08/20]
2
3 \LWR@infoprocessingmathjax{kpfonts}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-newpctxmath}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 \ifkp@ecalasscr
12 \CustomizeMathJax{\let\LWRorigmathscr\mathscr}
13 \CustomizeMathJax{\let\LWRorigmathcal\mathcal}
14 \CustomizeMathJax{\let\mathscr\LWRorigmathcal}
15 \CustomizeMathJax{\let\mathcal\LWRorigmathscr}
16 \fi

```

```

17
18 \ifkp@upgrk % lowercase
19 \LWR@mathjax@addgreek@l@up{}{}
20 \LWR@mathjax@addgreek@l@it{other}{}
21 \else
22 \LWR@mathjax@addgreek@l@up{other}{}
23 \fi
24
25 \ifkp@slGrk
26 \LWR@mathjax@addgreek@u@it*{}{}
27 \LWR@mathjax@addgreek@u@up*{other}{}
28 \LWR@mathjax@addgreek@u@up*{var}{}
29 \else
30 \LWR@mathjax@addgreek@u@it*{other}{}
31 \LWR@mathjax@addgreek@u@it*{var}{}
32 \fi
33
34 \LWR@mathjax@addgreek@u@up*{}{up}
35 \LWR@mathjax@addgreek@l@up{}{up}
36
37 \LWR@mathjax@addgreek@u@it*{}{sl}
38 \LWR@mathjax@addgreek@l@it{}{sl}
39
40 \CustomizeMathJax{\newcommand{\partialsl}{\mathord{\unicode{x1D715}}}}
41 \CustomizeMathJax{\let\partialup\uppartial}% not upright
42
43 \ifkp@oldReIm
44 \else
45 \CustomizeMathJax{\renewcommand{\Re}{\mathfrak{Re}}}
46 \CustomizeMathJax{\renewcommand{\Im}{\mathfrak{Im}}}
47 \fi
48
49 \ifkp@Dcommand
50 \ifkp@upRm%
51 \CustomizeMathJax{
52 \def\D#1{\mathclose{\,}\mathrm{d}}#1}
53 }
54 \else
55 \CustomizeMathJax{
56 \def\D#1{\mathclose{\,}\mathit{d}}#1}
57 }
58 \fi
59 \fi
60
61 \CustomizeMathJax{\let\pounds\mathsterling}
62 \CustomizeMathJax{\let\kppounds\mathsterling}
63
64 \CustomizeMathJax{\newcommand{\mathup}[1]{\mathrm{#1}}}% never sans
65 \CustomizeMathJax{\let\mathupright\mathup}
66
67 \end{warpMathJax}

```

File 228 **lwarp-kpfonts-otf.sty**

§ 334 Package **kpfonts-otf**

(Emulates or patches code by DANIEL FLIPO.)

Pkg kpfonts-otf kpfonts-otf is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation honors the options fancyReIm, mathcal, frenchstyle for Greek only, and mathcalasscript.

Also see the options for unicode-math, which is loaded by kpfonts-otf.

The unicode-math dedicated macros for Greek work correctly.

 **\mathversion** The MATHJAX emulation does not change with the use of \mathversion. Whatever emulation is established at the begin of the document will remain.

SVG math should appear the same as the printed output.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{kpfonts-otf}[2020/06/20]
2
3 \LWR@infoprocessingmathjax{kpfonts-otf}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-nonunicode}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 \ifkp@calasscr
12 \CustomizeMathJax{\let\mathscr\mathcal}
13 \else
14 \CustomizeMathJax{\let\mathcal\mathscr}
15 \fi
16
17 \ifkp@frenchstyle
18 \LWR@mathjax@addgreek@l@up{}{}
19 \LWR@mathjax@addgreek@u@up*{}{}
20 \fi
21
22 \ifkp@oldReIm
23 \CustomizeMathJax{\renewcommand{\Re}{\mathfrak{Re}}}
24 \CustomizeMathJax{\renewcommand{\Im}{\mathfrak{Im}}}
25 \else
26 \fi
27
28 \ifkp@Dcommand
29 \CustomizeMathJax{
30 \def\D#1{\mathclose{\,\,\mathrm{d}}#1}
31 }
32 \fi

```

```

33
34 \CustomizeMathJax{\let\varint\int}
35 \CustomizeMathJax{\let\variint\iint}
36 \CustomizeMathJax{\let\variiint\iiint}
37 \CustomizeMathJax{\let\variiiint\iiiint}
38 \CustomizeMathJax{\let\varidotsint\idotsint}
39
40 \CustomizeMathJax{\newcommand{\varointctrlockwise}{\mathop{\unicode{x2939}\!\!\unicode{x0222E}}}}
41 \CustomizeMathJax{\newcommand{\oiintclockwise}{\mathop{\unicode{x2939}\!\!\unicode{x0222F}}}}
42 \CustomizeMathJax{\newcommand{\oiintctrlockwise}{\mathop{\unicode{x2939}\!\!\unicode{x0222F}}}}
43 \CustomizeMathJax{\newcommand{\varoiintclockwise}{\mathop{\unicode{x0222F}\!\!\unicode{x2938}}}}
44 \CustomizeMathJax{\newcommand{\varoiintctrlockwise}{\mathop{\unicode{x2939}\!\!\unicode{x0222F}}}}
45 \CustomizeMathJax{\newcommand{\oiintclockwise}{\mathop{\unicode{x02230}\!\!\unicode{x2938}}}}
46 \CustomizeMathJax{\newcommand{\oiintctrlockwise}{\mathop{\unicode{x2939}\!\!\unicode{x02230}}}}
47 \CustomizeMathJax{\newcommand{\varoiintclockwise}{\mathop{\unicode{x02230}\!\!\unicode{x2938}}}}
48 \CustomizeMathJax{\newcommand{\varoiintctrlockwise}{\mathop{\unicode{x2939}\!\!\unicode{x02230}}}}
49 \CustomizeMathJax{\newcommand{\sqiint}{\mathop{\unicode{x2A16}\!\!\unicode{x2A16}}}}
50 \CustomizeMathJax{\newcommand{\sqiint}{\mathop{\unicode{x2A16}\!\!\unicode{x2A16}\!\!\unicode{x2A16}}}}
51
52 \CustomizeMathJax{\let\widearc\overparen}
53 \CustomizeMathJax{\let\widearcarrow\overrightarrow}
54 \CustomizeMathJax{\let\overrightarc\overrightarrow}
55
56 \end{warpMathJax}

```

---

File 229 **lwarp-layaureo.sty**

§ 335 Package **layaureo**

Pkg layaureo layaureo is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{layaureo}[2004/09/16]

---

File 230 **lwarp-layout.sty**

§ 336 Package **layout**

Pkg layout layout is ignored.

**for HTML output:** Discard all options for lwarp-layout:

1 \LWR@ProvidesPackageDrop{layout}[2014/10/28]

2 \NewDocumentCommand{\layout}{s}{}

File 231 **lwarp-layouts.sty**

§ 337 Package **layouts**

Pkg layouts layouts is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{layouts}[2009/09/02]

```

2 \newif\ifoddpagelayout
3 \oddpagelayouttrue
4 \newif\iftwocolumnlayout
5 \twocolumnlayoutfalse
6 \newif\ifdrawmarginpars
7 \drawmarginparstrue
8 \newif\ifdrawparameters
9 \drawparameterstrue
10 \newif\iflistaspara
11 \listasparatrue
12 \newif\ifruninhead
13 \runinheadfalse
14 \newif\ifprintparameters
15 \printparameterstrue
16 \newif\ifdrawdimensions
17 \drawdimensionsfalse
18 \newif\ifprintheadings
19 \printheadingstrue
20 \newcommand{\testdrawdimensions}{}
21 \newcommand{\testprintparameters}{}
22 \newcommand{\setlabelfont}[1]{}
23 \newcommand{\setparameterfont}[1]{}
24 \newcommand{\setvaluetextsize}[1]{}
25 \newcommand{\setlayoutscale}[1]{}
26 \newcommand{\setuplayouts}{}
27 \newcommand{\printinunitsof}[1]{}
28 \newcommand{\prntlen}[1]{}
29 \newcommand{\trypaperwidth}[1]{}
30 \newcommand{\trypaperheight}[1]{}
31 \newcommand{\tryhoffset}[1]{}
32 \newcommand{\tryvoffset}[1]{}
33 \newcommand{\trytopmargin}[1]{}
34 \newcommand{\tryheadheight}[1]{}
35 \newcommand{\tryheadsep}[1]{}
36 \newcommand{\trytextheight}[1]{}
37 \newcommand{\tryfootskip}[1]{}
38 \newcommand{\tryoddsidemargin}[1]{}
39 \newcommand{\tryevensidemargin}[1]{}
40 \newcommand{\trytextwidth}[1]{}
41 \newcommand{\trymarginparsep}[1]{}
42 \newcommand{\trymarginparwidth}[1]{}
43 \newcommand{\trymarginparpush}[1]{}
44 \newcommand{\trycolumnsep}[1]{}

```

```
45 \newcommand{\trycolumnseprule}[1]{}
46 \newcommand{\setfootbox}[2]{}
47 \newcommand{\currentpage}{}
48 \newcommand{\drawpage}{(draw page)}
49 \newcommand{\pagediagram}{(page diagram)}
50 \newcommand{\pagedesign}{(page design)}
51 \newcommand{\pagevalues}{(page values)}
52 \newcommand{\trystockwidth}[1]{}
53 \newcommand{\trystockheight}[1]{}
54 \newcommand{\trytrimedge}[1]{}
55 \newcommand{\trytrimtop}[1]{}
56 \newcommand{\tryuppermargin}[1]{}
57 \newcommand{\tryspinemargin}[1]{}
58 \newcommand{\currentstock}{}
59 \newcommand{\drawstock}{(draw stock)}
60 \newcommand{\stockdiagram}{(stock diagram)}
61 \newcommand{\stockdesign}{(stock design)}
62 \newcommand{\stockvalues}{(stock values)}
63 \newcommand{\tryitemindent}[1]{}
64 \newcommand{\trylabelwidth}[1]{}
65 \newcommand{\trylabelsep}[1]{}
66 \newcommand{\tryleftmargin}[1]{}
67 \newcommand{\tryrightmargin}[1]{}
68 \newcommand{\trylistparindent}[1]{}
69 \newcommand{\trytopsep}[1]{}
70 \newcommand{\tryparskip}[1]{}
71 \newcommand{\trypartopsep}[1]{}
72 \newcommand{\tryparsep}[1]{}
73 \newcommand{\tryitemsep}[1]{}
74 \newcommand{\currentlist}{}
75 \newcommand{\drawlist}{(draw list)}
76 \newcommand{\listdiagram}{(list diagram)}
77 \newcommand{\listdesign}{(list design)}
78 \newcommand{\listvalues}{(list values)}
79 \newcommand{\tryfootins}[1]{}
80 \newcommand{\tryfootnotesep}[1]{}
81 \newcommand{\tryfootnotebaseline}[1]{}
82 \newcommand{\tryfootruleheight}[1]{}
83 \newcommand{\tryfootrulefrac}[1]{}
84 \newcommand{\currentfootnote}{}
85 \newcommand{\drawfootnote}{(draw footnote)}
86 \newcommand{\footnotediagram}{(footnote diagram)}
87 \newcommand{\footnotedesign}{(footnote design)}
88 \newcommand{\footnotevalues}{(footnote values)}
89 \newcommand{\tryparindent}[1]{}
90 \newcommand{\tryparlinewidth}[1]{}
91 \newcommand{\tryparbaselineskip}[1]{}
92 \newcommand{\currentparagraph}{}
93 \newcommand{\drawparagraph}{(draw paragraph)}
94 \newcommand{\paragraphdiagram}{(paragraph diagram)}
95 \newcommand{\paragraphdesign}{(paragraph design)}
96 \newcommand{\paragraphvalues}{(paragraph values)}
97 \newcommand{\trybeforeskip}[1]{}
98 \newcommand{\tryafterskip}[1]{}
99 \newcommand{\tryindent}[1]{}

```

```

100 \newcommand{\currentheading}{}
101 \newcommand{\drawheading}[1]{(draw heading)}
102 \newcommand{\headingdiagram}[1]{(heading diagram)}
103 \newcommand{\headingdesign}[1]{(heading design)}
104 \newcommand{\headingvalues}{(heading values)}
105 \newcommand{\trytextfloatsep}[1]{}
106 \newcommand{\tryfloatsep}[1]{}
107 \newcommand{\tryinttextsep}[1]{}
108 \newcommand{\trytopfigrule}[1]{}
109 \newcommand{\trybotfigrule}[1]{}
110 \newcommand{\currentfloat}{}
111 \newcommand{\drawfloat}{(draw float)}
112 \newcommand{\floatdiagram}{(float diagram)}
113 \newcommand{\floatdesign}{(float design)}
114 \newcommand{\floatvalues}{(float values)}
115 \newcommand{\trytotalnumber}[1]{}
116 \newcommand{\trytopnumber}[1]{}
117 \newcommand{\trybottomnumber}[1]{}
118 \newcommand{\trytopfraction}[1]{}
119 \newcommand{\trytextfraction}[1]{}
120 \newcommand{\trybottomfraction}[1]{}
121 \newcommand{\currentfloatpage}{}
122 \newcommand{\drawfloatpage}{(draw floatpage)}
123 \newcommand{\floatpagediagram}{(floatpage diagram)}
124 \newcommand{\floatpagedesign}{(floatpage design)}
125 \newcommand{\floatpagevalues}{(floatpage values)}
126 \newcommand{\trytocindent}[1]{}
127 \newcommand{\trytocnumwidth}[1]{}
128 \newcommand{\trytoclinewidth}[1]{}
129 \newcommand{\trytocrmarg}[1]{}
130 \newcommand{\trytocpnumwidth}[1]{}
131 \newcommand{\trytocdotsep}[1]{}
132 \newcommand{\currenttoc}{}
133 \newcommand{\drawtoc}{(draw toc)}
134 \newcommand{\tocdiagram}{(toc diagram)}
135 \newcommand{\tocdesign}{(toc design)}
136 \newcommand{\tocvalues}{(toc values)}
137 \newcommand{\drawspread}[8][0]{(a spread)}
138 \newcommand{\drawfontframe}[1]{(font frame)}
139 \newcommand{\drawfontframeLabel}[1]{}

```

---

File 232 **lwarp-leading.sty**

§ 338 Package **leading**

Pkg leading leading is ignored.

**for HTML output:** 1 \LWREProvidesPackageDrop{leading}[2008/12/11]

2 \newcommand\leading[1]{}

---

File 233 **lwarp-leftidx.sty**

§ 339 Package **leftidx**

*(Emulates or patches code by HARALD HARDERS.)*

Pkg leftidx leftidx works as-is with SVG math, and is emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{leftidx}[2003/09/24]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\leftidx}[3]{\vphantom{#2}}#1#2#3}}
4 \CustomizeMathJax{\newcommand{\ltrans}[1]{\leftidx{^\mathrm{t}}{\!#1}{}}}
5 \end{warpMathJax}

```

---

File 234 **lwarp-letterspace.sty**

§ 340 Package **letterspace**

*(Emulates or patches code by R SCHLICHT.)*

Pkg letterspace letterspace is a subset of microtype, which is pre-loaded by lwarp. All user options and macros are ignored and disabled.

**for HTML output:** Discard all options for lwarp-letterspace:

```

1 \LWR@ProvidesPackageDrop{letterspace}[2018/01/14]

2 \newcommand*\lsstyle{}
3 \newcommand\textls[2][{}]{
4 \def\textls#1#{}
5 \newcommand*\lslig[1]{#1}

```

---

File 235 **lwarp-lettrine.sty**

§ 341 Package **lettrine**

*(Emulates or patches code by DANIEL FLIPO.)*

Pkg lettrine lettrine is emulated.

**for HTML output:** Discard all options for lwarp-lettrine:

```

1 \LWR@ProvidesPackageDrop{lettrine}[2018-08-28]

```

The initial letter is in a `<span>` of class `lettrine`, and the following text is in a `<span>` of class `lettrinetext`. `\lettrine [<keys>] {<letter>} {<additional text>}`

```

2 \DeclareDocumentCommand{\lettrine}{o m m}{%
3 \InlineClass{lettrine}{#2}\InlineClass{lettrinetext}{#3} % extra space
4 }
5
6 \newcounter{DefaultLines}
7 \setcounter{DefaultLines}{2}
8 \newcounter{DefaultDepth}
9 \newcommand*{\DefaultOptionsFile}{\relax}
10 \newcommand*{\DefaultLoversize}{0}
11 \newcommand*{\DefaultLraise}{0}
12 \newcommand*{\DefaultLhang}{0}
13 \newdimen\DefaultFindent
14 \setlength{\DefaultFindent}{\z@}
15 \newdimen\DefaultNindent
16 \setlength{\DefaultNindent}{0.5em}
17 \newdimen\DefaultSlope
18 \setlength{\DefaultSlope}{\z@}
19 \newdimen\DiscardVskip
20 \setlength{\DiscardVskip}{0.2\p@}
21 \newif\ifLettrineImage
22 \newif\ifLettrineOnGrid
23 \newif\ifLettrineRealHeight
24
25 \newcommand*{\LettrineTextFont}{\scshape}
26 \newcommand*{\LettrineFontHook}{}
27 \newcommand*{\LettrineFont}[1]{\InlineClass{lettrine}{#1}}
28 \newcommand*{\LettrineFontEPS}[1]{\includegraphics[height=1.5ex]{#1}}

```

---

File 236 **lwarp-libertinust1math.sty**

§ 342 Package **libertinust1math**

(Emulates or patches code by MICHAEL SHARPE.)

Pkg `libertinust1math` **libertinust1math** is used as-is for SVG math, and is emulated for MATHJAX.

The MATHJAX emulation honors `frenchmath` for Greek but not Latin characters, and `slantedGreek`, `uprightGreek`, and `ISO` also adjust Greek characters. MATHJAX cannot yet honor options for adjusting Latin characters.

The dedicated macros for upright and italic Greek letters do work correctly. Some of the symbol font macros such as `\mathsfbf` work for Latin but not for Greek letters.

svg math should appear the same as the printed output.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{libertinust1math}[2020/06/10]
2
3 \LWR@infoprocessingmathjax{libertinust1math}

```

```

4 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
5
6 \begin{warpMathJax}
7
8 \iflibus@slantedG
9 \LWR@mathjax@addgreek@u@it*{}{}
10 \else
11 \LWR@mathjax@addgreek@u@up*{}{}
12 \fi
13
14 \LWR@mathjax@addgreek@u@it*{}{it}
15 \LWR@mathjax@addgreek@u@up*{}{up}
16 \LWR@mathjax@addgreek@u@up*{}{up}
17
18 \iflibus@frenchm
19 \LWR@mathjax@addgreek@l@up{}{}
20 \else
21 \LWR@mathjax@addgreek@l@it{}{}
22 \fi
23
24 \LWR@mathjax@addgreek@l@it{}{it}
25 \LWR@mathjax@addgreek@l@up{}{up}
26 \LWR@mathjax@addgreek@l@up{}{up}
27
28 \CustomizeMathJax{\let\upartial\partial}% not upright
29
30 \CustomizeMathJax{\newcommand{\mathsfbf}[1]{%
31 \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}% not greek
32 }}% not sans
33 \CustomizeMathJax{\newcommand{\mathsfbfit}[1]{%
34 \mmlToken{mi}[mathvariant="sans-serif-bold-italic"]{#1}% not greek
35 }}%
36 \CustomizeMathJax{\newcommand{\mathbfit}[1]{\boldsymbol{#1}}}
37 \CustomizeMathJax{\newcommand{\mathsfit}[1]{%
38 \mmlToken{mi}[mathvariant="sans-serif-italic"]{#1}% not greek
39 }}
40 \CustomizeMathJax{\let\vectorsym\mathbfit}
41 \CustomizeMathJax{\let\matrixsym\mathbfit}
42 \CustomizeMathJax{\let\tensorsym\mathsfbfit}
43 \CustomizeMathJax{\let\mathboldsans\mathsfbfit}
44 \CustomizeMathJax{\let\mathbold\mathbfit}

```

lwarp\_mathjax.txt adds \left/\right support for delimiters.

```

45 \CustomizeMathJax{\let\dlb\lBrack}
46 \CustomizeMathJax{\let\drb\rBrack}
47
48 \CustomizeMathJax{\let\sqrtsign\sqrt}
49
50 \CustomizeMathJax{\let\smallintsl\smallint}
51 \CustomizeMathJax{\newcommand{\smallliintsl}{\mathop{\unicode{x222C}}\limits}}
52 \CustomizeMathJax{\newcommand{\smallliiintsl}{\mathop{\unicode{x222D}}\limits}}
53 \CustomizeMathJax{\newcommand{\smallliiiintsl}{\mathop{\unicode{x2A0C}}\limits}}
54 \CustomizeMathJax{\newcommand{\smallointsl}{\mathop{\unicode{x222E}}\limits}}
55 \CustomizeMathJax{\newcommand{\smalloiintsl}{\mathop{\unicode{x222F}}\limits}}

```

```

56
57 \CustomizeMathJax{\let\smallintup\smallint}
58 \CustomizeMathJax{\newcommand{\smallliintup}{\mathop{\unicode{x222C}}\limits}}
59 \CustomizeMathJax{\newcommand{\smallliintup}{\mathop{\unicode{x222D}}\limits}}
60 \CustomizeMathJax{\newcommand{\smallliintup}{\mathop{\unicode{x2A0C}}\limits}}
61 \CustomizeMathJax{\newcommand{\smallointup}{\mathop{\unicode{x222E}}\limits}}
62 \CustomizeMathJax{\newcommand{\smallointup}{\mathop{\unicode{x222F}}\limits}}
63
64 \CustomizeMathJax{\let\intslop\int}
65 \CustomizeMathJax{\newcommand{\iintslop}{\mathop{\unicode{x222C}}\limits}}
66 \CustomizeMathJax{\newcommand{\iintslop}{\mathop{\unicode{x222D}}\limits}}
67 \CustomizeMathJax{\newcommand{\iintslop}{\mathop{\unicode{x2A0C}}\limits}}
68 \CustomizeMathJax{\let\ointslop\oint}
69 \CustomizeMathJax{\newcommand{\oiintslop}{\mathop{\unicode{x222F}}\limits}}
70 \CustomizeMathJax{\newcommand{\oiintslop}{\mathop{\unicode{x2230}}\limits}}
71
72 \CustomizeMathJax{\let\intupop\int}
73 \CustomizeMathJax{\newcommand{\iintupop}{\mathop{\unicode{x222C}}\limits}}
74 \CustomizeMathJax{\newcommand{\iintupop}{\mathop{\unicode{x222D}}\limits}}
75 \CustomizeMathJax{\newcommand{\iintupop}{\mathop{\unicode{x2A0C}}\limits}}
76 \CustomizeMathJax{\let\ointupop\oint}
77 \CustomizeMathJax{\newcommand{\oiintupop}{\mathop{\unicode{x222F}}\limits}}
78 \CustomizeMathJax{\newcommand{\oiintupop}{\mathop{\unicode{x2230}}\limits}}
79
80 \CustomizeMathJax{\newcommand{\smallliint}{\mathop{\unicode{x222C}}\limits}}
81 \CustomizeMathJax{\newcommand{\smallliint}{\mathop{\unicode{x222D}}\limits}}
82 \CustomizeMathJax{\newcommand{\smallliint}{\mathop{\unicode{x2A0C}}\limits}}
83 \CustomizeMathJax{\newcommand{\smalloint}{\mathop{\unicode{x222E}}\limits}}
84 \CustomizeMathJax{\newcommand{\smalloint}{\mathop{\unicode{x222F}}\limits}}
85
86 \CustomizeMathJax{\let\intop\int}
87 \CustomizeMathJax{\newcommand{\iintop}{\mathop{\unicode{x222C}}\limits}}
88 \CustomizeMathJax{\newcommand{\iintop}{\mathop{\unicode{x222D}}\limits}}
89 \CustomizeMathJax{\newcommand{\iintop}{\mathop{\unicode{x2A0C}}\limits}}
90 \CustomizeMathJax{\let\ointop\oint}
91 \CustomizeMathJax{\newcommand{\oiintop}{\mathop{\unicode{x222F}}\limits}}
92 \CustomizeMathJax{\newcommand{\oiintop}{\mathop{\unicode{x2230}}\limits}}
93
94 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
95
96 \CustomizeMathJax{\newcommand{\bigcupdot}{\mathop{\unicode{x2A03}}}}
97 \CustomizeMathJax{\newcommand{\bigsqcap}{\mathop{\unicode{x2A05}}}}
98 \CustomizeMathJax{\newcommand{\xsol}{\mathop{\unicode{x29F8}}}}
99 \CustomizeMathJax{\newcommand{\xbsol}{\mathop{\unicode{x29F9}}}}
100 \CustomizeMathJax{\let\prodop\prod}
101 \CustomizeMathJax{\let\coprodop\coprod}
102 \CustomizeMathJax{\let\sumop\sum}
103 \CustomizeMathJax{\let\bigwedgeop\bigwedge}
104 \CustomizeMathJax{\let\bigveeop\bigvee}
105 \CustomizeMathJax{\let\bigcapop\bigcap}
106 \CustomizeMathJax{\let\bigcupop\bigcup}
107 \CustomizeMathJax{\let\xsolop\xsol}
108 \CustomizeMathJax{\let\xbsolop\xbsol}
109 \CustomizeMathJax{\let\bigodotop\bigodot}
110 \CustomizeMathJax{\let\bigoplusop\bigoplus}

```

```

111 \CustomizeMathJax{\let\bigotimesop\bigotimes}
112 \CustomizeMathJax{\let\bigcupdotop\bigcupdot}
113 \CustomizeMathJax{\let\biguplusop\biguplus}
114 \CustomizeMathJax{\let\bigsqcapop\bigsqcap}
115 \CustomizeMathJax{\let\bigsqcupop\bigsqcup}
116
117 \CustomizeMathJax{\newcommand{\ovhook}[1]{\mathord{#1\unicode{x00309}}}}
118 \CustomizeMathJax{\newcommand{\candra}[1]{\mathord{#1\unicode{x00310}}}}
119 \CustomizeMathJax{\newcommand{\oturnedcomma}[1]{\mathord{#1\unicode{x00312}}}}
120 \CustomizeMathJax{\newcommand{\ocommatopright}[1]{\mathord{#1\unicode{x00315}}}}
121 \CustomizeMathJax{\newcommand{\droang}[1]{\mathord{#1\unicode{x0031A}}}}
122 \CustomizeMathJax{\newcommand{\leftharpoonaccent}[1]{\mathord{#1\unicode{x020D0}}}}
123 \CustomizeMathJax{\newcommand{\rightharpoonaccent}[1]{\mathord{#1\unicode{x020D1}}}}
124 \CustomizeMathJax{\newcommand{\leftarrowaccent}[1]{\mathord{#1\unicode{x020D0}}}}
125 \CustomizeMathJax{\let\rightarrowaccent\vec}
126
127 \CustomizeMathJax{\newcommand{\leftrightharpoonaccent}[1]{\mathord{#1\unicode{x020E1}}}}
128 \CustomizeMathJax{\newcommand{\annuity}[1]{\mathord{#1\unicode{x020E7}}}}
129 \CustomizeMathJax{\newcommand{\widebridgeabove}[1]{\mathord{#1\unicode{x020E9}}}}
130 \CustomizeMathJax{\newcommand{\asteraccent}[1]{\mathord{#1\unicode{x020F0}}}}
131
132 % neutralized:
133 \CustomizeMathJax{\newcommand{\bracedl}{}}
134 \CustomizeMathJax{\newcommand{\bracerd}{}}
135 \CustomizeMathJax{\newcommand{\bracelu}{}}
136 \CustomizeMathJax{\newcommand{\braceru}{}}
137 \CustomizeMathJax{\newcommand{\braceex}{}}
138 \CustomizeMathJax{\newcommand{\bracemu}{}}
139 \CustomizeMathJax{\newcommand{\bracemd}{}}
140 \CustomizeMathJax{\newcommand{\parenld}{}}
141 \CustomizeMathJax{\newcommand{\parenrd}{}}
142 \CustomizeMathJax{\newcommand{\parenlu}{}}
143 \CustomizeMathJax{\newcommand{\parenru}{}}
144 \CustomizeMathJax{\newcommand{\bracketld}{}}
145 \CustomizeMathJax{\newcommand{\bracketrd}{}}
146 \CustomizeMathJax{\newcommand{\bracketlu}{}}
147 \CustomizeMathJax{\newcommand{\bracketru}{}}
148 \CustomizeMathJax{\newcommand{\bracketex}{}}
149 \CustomizeMathJax{\newcommand{\parenex}{}}
150
151 \CustomizeMathJax{\newcommand{\lhook}{~}}
152 \CustomizeMathJax{\newcommand{\rhook}{~}}
153 \CustomizeMathJax{\newcommand{\relbar}{-}}
154 \CustomizeMathJax{\newcommand{\Relbar}{=}}
155
156 \CustomizeMathJax{\newcommand{\mapstochar}{\mathrel{\unicode{x21A6}}}}
157
158 \CustomizeMathJax{\newcommand{\Zbar}{\mathord{\unicode{x0001B5}}}}
159 \CustomizeMathJax{\newcommand{\notchar}{\mathrel{\unicode{x000AC}}}}
160 \CustomizeMathJax{\newcommand{\upbackepsilon}{\mathord{\unicode{x03F6}}}}
161 \CustomizeMathJax{\newcommand{\smbllkcircle}{\mathbin{\unicode{x02022}}}}
162 \CustomizeMathJax{\newcommand{\enleadertwodots}{\mathord{\unicode{x02025}}}}
163 \CustomizeMathJax{\newcommand{\unicodeellipsis}{\mathord{\unicode{x02026}}}}
164 \CustomizeMathJax{\newcommand{\mathellipsis}{\mathinner{\unicode{x02026}}}}
165 \CustomizeMathJax{\newcommand{\dprime}{\mathord{\unicode{x02033}}}}

```

```

166 \CustomizeMathJax{\newcommand{\trprime}{\mathord{\unicode{x02034}}}}
167 \CustomizeMathJax{\newcommand{\backdprime}{\mathord{\unicode{x02036}}}}
168 \CustomizeMathJax{\newcommand{\backtrprime}{\mathord{\unicode{x02037}}}}
169 \CustomizeMathJax{\newcommand{\caretinsert}{\mathord{\unicode{x02038}}}}
170 \CustomizeMathJax{\newcommand{\Exclam}{\mathord{\unicode{x0203C}}}}
171
172 \CustomizeMathJax{\newcommand{\hyphenbullet}{\mathord{\unicode{x02043}}}}
173 \CustomizeMathJax{\newcommand{\fracslash}{\mathbin{\unicode{x02044}}}}
174 \CustomizeMathJax{\newcommand{\Question}{\mathord{\unicode{x02047}}}}
175 \CustomizeMathJax{\newcommand{\closure}{\mathrel{\unicode{x02050}}}}
176 \CustomizeMathJax{\newcommand{\qprime}{\mathord{\unicode{x02057}}}}
177 \CustomizeMathJax{\newcommand{\vertoverlay}{\mathrel{\unicode{x020D2}}}}
178 \CustomizeMathJax{\newcommand{\enclosecircle}{\mathord{\unicode{x020DD}}}}
179 \CustomizeMathJax{\newcommand{\enclosesquare}{\mathord{\unicode{x020DE}}}}
180 \CustomizeMathJax{\newcommand{\enclosetriangle}{\mathord{\unicode{x020E4}}}}
181 \CustomizeMathJax{\newcommand{\Eulerconst}{\mathord{\unicode{x02107}}}}
182 \CustomizeMathJax{\newcommand{\turnediota}{\mathord{\unicode{x02129}}}}
183 \CustomizeMathJax{\newcommand{\Angstrom}{\mathord{\unicode{x0212B}}}}
184
185 \CustomizeMathJax{\newcommand{\sansLturned}{\mathord{\unicode{x02142}}}}
186 \CustomizeMathJax{\newcommand{\sansLmirrored}{\mathord{\unicode{x02143}}}}
187 \CustomizeMathJax{\newcommand{\Yup}{\mathord{\unicode{x02144}}}}
188 \CustomizeMathJax{\newcommand{\upand}{\mathbin{\unicode{x0214B}}}}
189 \CustomizeMathJax{\newcommand{\increment}{\mathord{\unicode{x02206}}}}
190 \CustomizeMathJax{\newcommand{\smallin}{\mathrel{\unicode{x0220A}}}}
191 \CustomizeMathJax{\newcommand{\nni}{\mathrel{\unicode{x0220C}}}}
192
193 \CustomizeMathJax{\newcommand{\smallni}{\mathrel{\unicode{x0220D}}}}
194 \CustomizeMathJax{\newcommand{\QED}{\mathord{\unicode{x0220E}}}}
195 \CustomizeMathJax{\newcommand{\vysmwhtcircle}{\mathbin{\unicode{x02218}}}}
196 \CustomizeMathJax{\newcommand{\vysmbkcircle}{\mathbin{\unicode{x02219}}}}
197 \CustomizeMathJax{\newcommand{\rightangle}{\mathord{\unicode{x0221F}}}}
198
199 \CustomizeMathJax{\newcommand{\Colon}{\mathrel{\unicode{x02237}}}}
200 \CustomizeMathJax{\newcommand{\dotminus}{\mathbin{\unicode{x02238}}}}
201 \CustomizeMathJax{\newcommand{\dashcolon}{\mathrel{\unicode{x02239}}}}
202 \CustomizeMathJax{\newcommand{\dotminusdots}{\mathrel{\unicode{x0223A}}}}
203 \CustomizeMathJax{\newcommand{\kernelcontraction}{\mathrel{\unicode{x0223B}}}}
204 \CustomizeMathJax{\newcommand{\invlazys}{\mathbin{\unicode{x0223E}}}}
205
206 \CustomizeMathJax{\newcommand{\sinewave}{\mathord{\unicode{x0223F}}}}
207 \CustomizeMathJax{\newcommand{\nsime}{\mathrel{\unicode{x02244}}}}
208 \CustomizeMathJax{\newcommand{\simneqq}{\mathrel{\unicode{x02246}}}}
209 \CustomizeMathJax{\newcommand{\napprox}{\mathrel{\unicode{x02249}}}}
210 \CustomizeMathJax{\newcommand{\approxident}{\mathrel{\unicode{x0224B}}}}
211 \CustomizeMathJax{\newcommand{\backcong}{\mathrel{\unicode{x0224C}}}}
212
213 \CustomizeMathJax{\newcommand{\nasymp}{\mathrel{\unicode{x0226D}}}}
214 \CustomizeMathJax{\newcommand{\nlessim}{\mathrel{\unicode{x02274}}}}
215 \CustomizeMathJax{\newcommand{\ngtrsim}{\mathrel{\unicode{x02275}}}}
216 \CustomizeMathJax{\newcommand{\nlessgtr}{\mathrel{\unicode{x02278}}}}
217 \CustomizeMathJax{\newcommand{\ngtrless}{\mathrel{\unicode{x02279}}}}
218
219 \CustomizeMathJax{\newcommand{\nsubset}{\mathrel{\unicode{x02284}}}}
220 \CustomizeMathJax{\newcommand{\nsupset}{\mathrel{\unicode{x02285}}}}

```

```

221
222 \CustomizeMathJax{\newcommand{\cupleftarrow}{\mathbin{\unicode{x0228C}}}}
223 \CustomizeMathJax{\newcommand{\cupdot}{\mathbin{\unicode{x0228D}}}}
224 \CustomizeMathJax{\newcommand{\circlequal}{\mathbin{\unicode{x0229C}}}}
225
226 \CustomizeMathJax{\newcommand{\assert}{\mathrel{\unicode{x022A6}}}}
227 \CustomizeMathJax{\newcommand{\VDash}{\mathrel{\unicode{x022AB}}}}
228 \CustomizeMathJax{\newcommand{\prurel}{\mathrel{\unicode{x022B0}}}}
229
230 \CustomizeMathJax{\newcommand{\origof}{\mathrel{\unicode{x022B6}}}}
231 \CustomizeMathJax{\newcommand{\smallprod}{\mathop{\unicode{x0220F}}}}% not small
232 \CustomizeMathJax{\newcommand{\smallcoprod}{\mathop{\unicode{x02210}}}}% not small
233 \CustomizeMathJax{\newcommand{\smallsum}{\mathop{\unicode{x02211}}}}% not small
234 \CustomizeMathJax{\newcommand{\Hfraktur}{\mathord{\unicode{x1D525}}}}
235 \CustomizeMathJax{\newcommand{\dsol}{\mathbin{\unicode{x029F6}}}}
236 \CustomizeMathJax{\newcommand{\rsolbar}{\mathbin{\unicode{x029F7}}}}
237
238 \CustomizeMathJax{\newcommand{\eqless}{\mathrel{\unicode{x022DC}}}}
239 \CustomizeMathJax{\newcommand{\eqgtr}{\mathrel{\unicode{x022DD}}}}
240 \CustomizeMathJax{\newcommand{\npreccurlyeq}{\mathrel{\unicode{x022E0}}}}
241 \CustomizeMathJax{\newcommand{\nsucccurlyeq}{\mathrel{\unicode{x022E1}}}}
242 \CustomizeMathJax{\newcommand{\nsqsubseteq}{\mathrel{\unicode{x022E2}}}}
243 \CustomizeMathJax{\newcommand{\nsqsupseteq}{\mathrel{\unicode{x022E3}}}}
244 \CustomizeMathJax{\newcommand{\sqsubseteq}{\mathrel{\unicode{x022E4}}}}
245 \CustomizeMathJax{\newcommand{\sqsupseteq}{\mathrel{\unicode{x022E5}}}}
246 \CustomizeMathJax{\newcommand{\nvartriangleleft}{\mathrel{\unicode{x022EA}}}}
247 \CustomizeMathJax{\newcommand{\nvartriangleright}{\mathrel{\unicode{x022EB}}}}
248
249 \CustomizeMathJax{\newcommand{\vdotsmath}{\mathrel{\unicode{x022EE}}}}
250 \CustomizeMathJax{\newcommand{\unicodecdots}{\mathord{\unicode{x022EF}}}}
251 \CustomizeMathJax{\newcommand{\adots}{\mathrel{\unicode{x022F0}}}}
252 \CustomizeMathJax{\newcommand{\succneq}{\mathrel{\unicode{x02AB2}}}}
253 \CustomizeMathJax{\newcommand{\preceq}{\mathrel{\unicode{x02AB3}}}}
254 \CustomizeMathJax{\newcommand{\succeq}{\mathrel{\unicode{x02AB4}}}}
255 \CustomizeMathJax{\newcommand{\precneq}{\mathrel{\unicode{x02AB1}}}}
256
257 \CustomizeMathJax{\newcommand{\mapsfrom}{\mathrel{\unicode{x021A4}}}}
258
259 \CustomizeMathJax{\newcommand{\longmapsfrom}{\mathrel{\unicode{x027FB}}}}
260
261 \CustomizeMathJax{\newcommand{\diameter}{\mathord{\unicode{x02300}}}}
262 \CustomizeMathJax{\newcommand{\coloneq}{\mathrel{\unicode{x02254}}}}
263 \CustomizeMathJax{\newcommand{\eqcolon}{\mathrel{\unicode{x02255}}}}
264 \CustomizeMathJax{\newcommand{\arceq}{\mathrel{\unicode{x02258}}}}
265 \CustomizeMathJax{\newcommand{\wedg}{\mathrel{\unicode{x02259}}}}
266 \CustomizeMathJax{\newcommand{\veeq}{\mathrel{\unicode{x0225A}}}}
267
268 \CustomizeMathJax{\newcommand{\stareq}{\mathrel{\unicode{x0225B}}}}
269 \CustomizeMathJax{\newcommand{\eqdef}{\mathrel{\unicode{x0225D}}}}
270 \CustomizeMathJax{\newcommand{\measeq}{\mathrel{\unicode{x0225E}}}}
271 \CustomizeMathJax{\newcommand{\questeq}{\mathrel{\unicode{x0225F}}}}
272 \CustomizeMathJax{\newcommand{\nequiv}{\mathrel{\unicode{x02262}}}}
273 \CustomizeMathJax{\newcommand{\Equip}{\mathrel{\unicode{x02263}}}}
274
275 \CustomizeMathJax{\newcommand{\house}{\mathord{\unicode{x02302}}}}

```

```

276
277 \CustomizeMathJax{\newcommand{\musicalnote}{\mathord{\unicode{x0266A}}}}
278 \CustomizeMathJax{\newcommand{\degree}{\mathord{\unicode{x000B0}}}}
279 \CustomizeMathJax{\newcommand{\mathsection}{\mathord{\unicode{x000A7}}}}
280 \CustomizeMathJax{\newcommand{\mathparagraph}{\mathord{\unicode{x000B6}}}}
281 \CustomizeMathJax{\newcommand{\checkmarkmath}{\mathord{\unicode{x02713}}}}
282 \CustomizeMathJax{\newcommand{\invnot}{\mathord{\unicode{x02310}}}}
283
284 \CustomizeMathJax{\newcommand{\mathvisiblespace}{\mathord{\unicode{x02423}}}}
285 \CustomizeMathJax{\newcommand{\mdlgblksquare}{\mathord{\unicode{x025A0}}}}
286 \CustomizeMathJax{\newcommand{\mdlgwht square}{\mathord{\unicode{x025A1}}}}
287
288 \CustomizeMathJax{\newcommand{\bigblacktriangleup}{\mathord{\unicode{x025B2}}}}
289 \CustomizeMathJax{\newcommand{\varbigtriangleup}{\mathord{\unicode{x025B3}}}}
290
291 \CustomizeMathJax{\newcommand{\bigblacktriangledown}{\mathord{\unicode{x025BC}}}}
292 \CustomizeMathJax{\newcommand{\varbigtriangledown}{\mathord{\unicode{x025BD}}}}
293 \CustomizeMathJax{\newcommand{\Longmapsfrom}{\mathrel{\unicode{x027FD}}}}
294
295 % bug in print font:
296 \CustomizeMathJax{\newcommand{\mdlgblkdiamond}{\mathord{\unicode{x025C6}}}}
297
298 \CustomizeMathJax{\newcommand{\mdlgwhtdiamond}{\mathord{\unicode{x025C7}}}}
299 \CustomizeMathJax{\newcommand{\Longmapsto}{\mathrel{\unicode{x027FE}}}}
300 \CustomizeMathJax{\newcommand{\fisheye}{\mathord{\unicode{x025C9}}}}
301 \CustomizeMathJax{\newcommand{\mdlgwhtlozenge}{\mathord{\unicode{x025CA}}}}
302 \CustomizeMathJax{\newcommand{\mdlgwht circle}{\mathbin{\unicode{x025CB}}}}
303 \CustomizeMathJax{\newcommand{\bullseye}{\mathord{\unicode{x025CE}}}}
304 \CustomizeMathJax{\newcommand{\mdlgblk circle}{\mathord{\unicode{x025CF}}}}
305
306 \CustomizeMathJax{\newcommand{\Nwarrow}{\mathrel{\unicode{x021D6}}}}
307 \CustomizeMathJax{\newcommand{\Nearrow}{\mathrel{\unicode{x021D7}}}}
308 \CustomizeMathJax{\newcommand{\Searrow}{\mathrel{\unicode{x021D8}}}}
309 \CustomizeMathJax{\newcommand{\Swarrow}{\mathrel{\unicode{x021D9}}}}
310
311 \CustomizeMathJax{\newcommand{\Mapsfrom}{\mathord{\unicode{x02906}}}}
312 \CustomizeMathJax{\newcommand{\smwht circle}{\mathord{\unicode{x025E6}}}}
313 \CustomizeMathJax{\newcommand{\smwhtdiamond}{\mathbin{\unicode{x022C4}}}}
314 \CustomizeMathJax{\newcommand{\Mapsto}{\mathord{\unicode{x02907}}}}
315
316 \CustomizeMathJax{\let\ngets\leftarrow}
317 \CustomizeMathJax{\let\nsimeq\sim}
318 \CustomizeMathJax{\let\nle\leq}
319 \CustomizeMathJax{\let\nge\geq}
320
321 \end{warpMathJax}

```

---

File 237 **lwarp-lineno.sty**

§ 343 Package **lineno**

(Emulates or patches code by STEPHAN I. BÖTTCHER.)

Pkg `lineno` `lineno` is partly emulated, but mostly ignored.

```

for HTML output: 1 \LWR@ProvidesPackageDrop{lineno}[2005/11/02]

2 \newcommand*\resetlinenumber[1][\@ne]{}
3
4 \def\linenumbers{%
5 \@ifnextchar[{\resetlinenumber}%
6 {\@ifstar{\resetlinenumber}{}}%
7 }
8
9 \newcommand*\nolinenumbers{}
10
11 \@namedef{linenumbers*}{\par\linenumbers*}
12 \@namedef{runninglinenumbers*}{\par\runninglinenumbers*}
13
14 \def\endlinenumbers{\par}
15 \let\endrunninglinenumbers\endlinenumbers
16 \let\endpagewiselinenumbers\endlinenumbers
17 \expandafter\let\csname endlinenumbers*\endcsname\endlinenumbers
18 \expandafter\let\csname endrunninglinenumbers*\endcsname\endlinenumbers
19 \let\endnolinenumbers\endlinenumbers
20
21 \def\pagewiselinenumbers{\linenumbers\setpagewiselinenumbers}
22
23 \def\runninglinenumbers{\setrunninglinenumbers\linenumbers}
24
25 \def\setpagewiselinenumbers{}
26
27 \def\setrunninglinenumbers{}
28
29 \def\linenomath{}%
30 \@namedef{linenomath*}{}%
31 \def\endlinenomath{}
32 \expandafter\let\csname endlinenomath*\endcsname\endlinenomath
33
34 \let\lineLabel\label
35
36 \def\switchlinenumbers{\@ifstar{}{}}
37 \def\setmakelinenumbers#1{\@ifstar{}{}}
38
39 \def\leftlinenumbers{\@ifstar{}{}}
40 \def\rightlinenumbers{\@ifstar{}{}}
41
42 \newcounter{linenumber}
43 \newcount\c@pagewiselinenumber
44 \let\c@runninglinenumber\c@linenumber
45
46 \def\runningpagewiselinenumbers{}
47 \def\realpagewiselinenumbers{}
48
49
50 \NewDocumentCommand\modulolinenumbers{s o}{}
51
52 \chardef\c@linenumbermodulo=5

```

```

53 \modulolinenumbers[1]
54
55 \newcommand*{firstlinenumber}[1]{
56
57 \newcommand\internallinenumbers{
58 \let\endinternallinenumbers\endlinenumbers
59 \@namedef{internallinenumbers*}{\internallinenumbers}
60 \expandafter\let\csname endinternallinenumbers*\endcsname\endlinenumbers
61
62 \newcommand*{\linenoplaceholder}[1]{% redefine per language
63 (line number reference for \detokenize\expandafter{#1})
64 }
65
66 \newcommand*{\lineref}[2][\linenoplaceholder{#2}]
67 \newcommand*{\linerefp}[2][\linenoplaceholder{#2}]
68 \newcommand*{\linerefr}[2][\linenoplaceholder{#2}]
69
70 \newcommand\quotelinenumbers
71 {\@ifstar\linenumbers{\@ifnextchar[\linenumbers{\linenumbers*}}}
72
73 \newdimen\linenumbersep
74 \newdimen\linenumberwidth
75 \newdimen\quotelinenumbersep
76
77 \quotelinenumbersep=\linenumbersep
78 \let\quotelinenumberfont\linenumberfont
79
80 \def\linenumberfont{\normalfont\tiny\sffamily}
81
82
83 \linenumberwidth=10pt
84 \linenumbersep=10pt
85
86 \def\thelinenumber{}
87
88 \def\LineNumber{}
89 \def\makeLineNumber{}
90 \def\makeLineNumberLeft{}
91 \def\makeLineNumberRight{}
92 \def\makeLineNumberOdd{}
93 \def\makeLineNumberEven{}
94 \def\makeLineNumberRunning{}
95
96
97 \newenvironment{numquote} {\quote}{\endquote}
98 \newenvironment{numquotation} {\quotation}{\endquotation}
99 \newenvironment{numquote*} {\quote}{\endquote}
100 \newenvironment{numquotation*}{\quotation}{\endquotation}
101
102 \newdimen\bframerule
103 \bframerule=\fbxrule
104
105 \newdimen\bframesep
106 \bframesep=\fbxsep
107

```

```

108 \newenvironment{bframe}
109 {%
110 \LWR@forceminwidth{\bframerule}%
111 \BlockClass[
112 border:\LWR@printlength{\LWR@atleastonept} solid black ; %
113 padding:\LWR@printlength{\bframesep}%
114]{bframe}
115 }
116 {\endBlockClass}

```

---

File 238 **lwarp-lips.sty**

§ 344 Package **lips**

*(Emulates or patches code by MATT SWIFT.)*

Pkg lips lips is emulated.

```

1 % \LWR@ProvidesPackageDrop{lips}
2 \PackageInfo{lwarp}{Using the lwarp version of package 'lips'.}%
3 \ProvidesPackage{lwarp-lips}[2001/08/31]
4
5 \NewDocumentCommand{\Lips}{}{\textellipsis}
6
7 \NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}
8
9 \let\lips\Lips
10 \let\olips\lips
11
12 \DeclareOption*{}
13 \DeclareOption{mla}{
14 \let\lips\BracketedLips
15 }
16 \ProcessOptions\relax
17
18 \newcommand \LPNobreakList {}

```

---

File 239 **lwarp-listings.sty**

§ 345 Package **listings**

*(Emulates or patches code by CARSTEN HEINZ, BROOKS MOSES, JOBST HOFFMANN.)*

Pkg listings listings is supported with some limitations. Text formatting is not yet supported.

```

1 \LWR@ProvidesPackagePass{listings}[2018/09/02]

```

Force flexible columns. Fixed columns inserts spaces in the PDF output.

```

2 \lst@column@flexible

```

Patches to embed listings inside pre tags:

```

3 \let\LWR@origlst@Init\lst@Init
4 \let\LWR@origlst@DeInit\lst@DeInit
5
6 \let\LWR@origlsthkEveryPar\lsthk@EveryPar
7
8 \renewcommand{\l@lstlisting}[2]{\hypertocfloat{1}{\lstlisting}{lol}{#1}{#2}}

```

`\lstset`     $\langle options \rangle$

Use the listings `literate` option to replace HTML entities:

```

9 \def\lstset#1{\endgroup%
10 % \ifx\@empty#1%
11 % \@empty%
12 % \else%
13 \setkeys{lst}{%
14 #1%
15 ,literate=%
16 <{\HTMLentity{lt}}{4}%
17 >{\HTMLentity{gt}}{4}%
18 '{\HTMLentity{apos}}{6}%
19 '{\HTMLentity{grave}}{7}%

```

The ampersand is not treated here, as the result is inconsistent spacing. It is nevertheless converted to `&amp;`; elsewhere. Sanitizing the double quote interferes with listings' conversion of visible spaces inside strings.

```

20 }%
21 % \fi%
22 }

```

`\lst@Init`     $\langle backslash-processing \rangle$     Done at the start of a listing.

```
23 \renewcommand{\lst@Init}[1]{%
```

Perform the listings initialization:

```
24 \LWR@traceinfo{\lst@Init}%
```

`\LWR@forcenewpage` is moved to the start to avoid a spurious bug with paragraph handling and conditionals.

```

25 \lst@ifdisplaystyle%
26 \LWR@forcenewpage%
27 \fi%
28 \renewcommand*\@capttype{\lstlisting}%
29 \let\lst@aboveskip\z@\let\lst@belowskip\z@%
30 \gdef\lst@boxpos{t}%
31 \let\lst@frame\@empty
32 \let\lst@frametshape\@empty
33 \let\lst@framershape\@empty
34 \let\lst@framebshape\@empty
35 \let\lst@framelshape\@empty
36 \lstframe@\lst@frameround ffff\relax%
37 \lst@multicols\@empty%

```

```
38 \LWR@origlst@Init{#1}\relax%
```

Avoids extra horizontal space:

```
39 \def\lst@frame{r{}}%
```

```
40 \LWR@traceinfo{finished origlst@Init}%
```

```
41 \lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the <pre>, then reenable line numbers.

```
42 \LWR@traceinfo{About to create verbatim.}%
```

```
43 \let\lsthk@EveryPar\relax%
```

```
44 \LWR@atbeginverbatim{programlisting}%
```

```
45
```

```
46 \let\lsthk@EveryPar\LWR@origlsthkEveryPar%
```

```
47 \else%
```

Inline, so open a <span>:

```
48 \ifbool{LWR@verbtags}{\LWR@htmltag{span class="inlineprogramlisting"}}{}%
```

```
49 \fi%
```

```
50 \LWR@traceinfo{lst@Init done}%
```

```
51 }
```

```
52
```

`\lst@DeInit` Done at the end of a listing.

```
53 \renewcommand*{\lst@DeInit}{%
```

```
54 \lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```
55 \let\lsthk@EveryPar\relax%
```

```
56 \LWR@afterendverbatim%
```

```
57 \let\lsthk@EveryPar\LWR@origlsthkEveryPar%
```

```
58 \else%
```

Inline, so create the closing </span>:

```
59 \ifbool{LWR@verbtags}{\noindent\LWR@htmltag{/span}}{}%
```

```
60 \fi%
```

Final listings deinit:

```
61 \LWR@origlst@DeInit%
```

```
62 }
```

`\lst@MakeCaption` {<math>t/b</math>}

This is called BOTH at the top and at the bottom of each listing.

Patched for `lwarp`.

```
63
```

```
64 \def\lst@MakeCaption#1{%
```

```
65 \LWR@traceinfo{MAKING CAPTION at #1}%
```

```

66 \lst@ifdisplaystyle
67 \LWR@traceinfo{making a listings display caption}%
68 \ifx #1t%
69 \ifx\lst@caption\@empty\expandafter\lst@HRefStepCounter \else
70 \expandafter\refstepcounter
71 \fi {\lstlisting}%
72 \LWR@traceinfo{About to assign label: !\lst@label!}%
73 % \ifx\lst@label\@empty\else
74 % \label{\lst@label}\fi
75 \LWR@traceinfo{Finished assigning the label.}%
76 \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
77 \global\let\lst@name\lst@arg \global\let\lstname\lst@name
78 \lst@ifnolol\else
79 \ifx\lst@caption\@empty
80 \ifx\lst@caption\@empty
81 \ifx\lst@intname\@empty
82 \else
83 \def\lst@temp{ }%
84 \ifx\lst@intname\lst@temp \else

```

This code places a contents entry for a non-float. This would have to be modified for **lwarp**:

```

85 \LWR@traceinfo{addcontents lst@name: -\lst@name-}%
86 % \addcontentsline{lol}{\lstlisting}{\lst@name}
87 \fi
88 \fi
89 \fi
90 \else

```

This would have to be modified for **lwarp**:

```

91 \LWR@traceinfo{addcontents lst@caption: -\lst@caption-}%
92 \addcontentsline{lol}{\lstlisting}%
93 {\protect\numberline{\the\lstlisting}%
94 {\protect\ignorespaces \LWR@isolate{\lst@caption} \protect\relax}}%
95 \fi
96 \fi
97 \fi
98 \ifx\lst@caption\@empty\else
99 \LWR@traceinfo{\lst@caption not empty-}%
100 \lst@ifSubstring #1\lst@captionpos
101 {\begingroup
102 \LWR@traceinfo{at the selected position}%

```

These space and box commands are not needed for HTML output:

```

103 % \let\@vskip\vskip
104 % \def\vskip{\afterassignment\lst@vskip \@tempskipa}%
105 % \def\lst@vskip{\nobreak\@vskip\@tempskipa\nobreak}%
106 % \par\@parboxrestore\normalsize\normalfont % \noindent (AS)
107 % \ifx #1t\allowbreak \fi
108 \ifx\lst@title\@empty

```

New **lwarp** code to create a caption:

```

109 \LWR@stoppars%
110 \lst@makecaption\fnnum\lstlisting{\ignorespaces \lst@caption}
111 \else

```

New lwarp code to create a title:

```

112 % \lst@maketitle\lst@title % (AS)
113 \LWR@traceinfo{Making title: \lst@title}%
114 \begin{BlockClass}{\lstlistingtitle}% lwarp
115 \lst@maketitle\lst@title% lwarp
116 \end{BlockClass}% lwarp
117 \fi
118 \LWR@traceinfo{About to assign label: !\lst@label!}%
119 \ifx\lst@label\@empty\else
120 \leavevmode% gets rid of bad space factor error
121 \GetTitleStringExpand{\lst@caption}%
122 \edef\LWR@lntemp{\GetTitleStringResult}%
123 \edef\@currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
124 \label{\lst@label}\fi
125 \LWR@traceinfo{Finished assigning the label.}%

```

Not needed for lwarp:

```

126 % \ifx #1b\allowbreak \fi
127 \endgroup}{}%
128 \fi
129 \LWR@traceinfo{end of making a listings display caption}%
130 \else
131 \LWR@traceinfo{INLINE}%
132 \fi
133 \LWR@traceinfo{DONE WITH CAPTION at #1}%
134 }
135
136 \renewcommand{\lst@maketitle}[1]{%
137 \LWR@isolate{#1}%
138 }%
139

```

[line numbers](#) Patched to keep left line numbers outside of the left margin, and place right line numbers in a field `\VerbatimHTMLWidth` wide.

```

140 \lst@Key{numbers}{none}{%
141 \let\lst@PlaceNumber\@empty
142 \lstKV@SwitchCases{#1}%
143 {none:\%
144 left:\def\lst@PlaceNumber{%

```

For now, `lwarp` places left line numbers inline. Ideally the entire line would be moved to the right, but conflicts with list indenting occurs.

```

145 % \LWR@origllap{
146 \LWR@orignormalfont%
147 \lst@numberstyle{\thelstnumber}\kern\lst@numbersep%
148 % }
149 }\%
150 right:\def\lst@PlaceNumber{\LWR@origrlap{\LWR@orignormalfont
151 \kern 6in \kern\lst@numbersep
152 \lst@numberstyle{\thelstnumber}}}%
153 }\PackageError{lwarp-listings}{Numbers #1 unknown}\@ehc}}

```

---

File 240 **lwarp-listliketab.sty**

§ 346 Package **listliketab**

Pkg listliketab listliketab is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{listliketab}[2005/01/09]

```
2 \newcommand*\storestyleof}[1]{}
3 \newcommand*\storeliststyle{}
4 \newenvironment{listliketab}{}{}
```

---

File 241 **lwarp-lltjext.sty**

§ 347 Package **lltjext**

*(Emulates or patches code by THE L<sup>A</sup>T<sub>E</sub>X-JA PROJECT TEAM.)*

Pkg lltjext lltjext is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{lltjext}[2018/10/07]

```
2 \protected\def\yoko{%
3 \directlua{luatexja.direction.set_list_direction(4, 'yoko')}%
4 }
5 \protected\def\tate{\yoko}
6 \protected\def\dtou{\yoko}
7 \protected\def\utod{\yoko}
8
9 \define@key[ltj]{japaram}{direction}{}
10
11 \yoko
12
13 \DeclareExpandableDocumentCommand{\rensujj}{s o m}{#3}
14
15 \DeclareDocumentCommand{\layoutfloat}{d() o m}{}
16
17 \DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}
18
19 \LetLtxMacro\pccaption\caption
20
21 \DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}
22
23 \let\captiondir\relax
24 \RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
25 {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
26 {\endLWR@HTML@sub@minipage}
27
```

```

28 \RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{ } O{t} m +m}
29 {
30 \LWR@traceinfo{parbox of width #4}%
31 \begin{minipage}[#2][#3][#4]{#5}%
32 #6
33 \end{minipage}%
34 }
35
36 \RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
37 \global\booltrue{LWR@minipagefullwidth}%
38 \parbox[#2]{#4}%
39 }

```

File 242 **lwarp-longtable.sty**

§ 348 Package **longtable**

*(Emulates or patches code by DAVID CARLISLE.)*

Pkg longtable longtable is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{longtable}[2014/10/28]

Use one of either `\endhead` or `\endfirsthead` for both print and HTML, and use a `\warpprintonly` macro to disable the other head phrase, and also the `\endfoot` and `\endfirstfoot` phrases. (See section 8.10.4 if using `threeparttablex`.)

```

\begin{longtable}{ [column specifiers] }
[. . .] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[. . .] \endhead % or \endfirsthead
[. . .] \endfoot
[<lastfoot macros>] \endlastfoot
}
. . . table contents . . .
\warppHTMLonly{
[<lastfoot macros>] % HTML last footer, without \endfoot
% or \endlastfoot.
}
\end{longtable}

```

⚠ **Misplaced \noalign** Use the `\warpprintonly` macro instead of the `warpprint` environment. Doing so helps avoid “Misplaced `\noalign`.” when using `\begin{warpprint}`.

⚠ **\kill** `\kill` is ignored, place a `\kill` line inside

```
\begin{warpprint} . . . \end{warpprint}
```

or place it inside `\warpprintonly`.

⚠ **lateximage** longtable is not supported inside a `lateximage`.

See:

<http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable>

Used to detect more than one of `\endhead` and `\endfirsthead` in use for HTML at the same time.

```
2 \newbool{LWR@longtable@havehead}
3 \boolfalse{LWR@longtable@havehead}
```

Env `longtable` \* [*horizontal*] [*colspec*] Emulates the `longtable` environment.

Per the `caption` package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options `[c]`, `[l]`, and `[r]` are ignored.

```
4 \newenvironment{longtable*}[2][]{%
5 \LWR@floatbegin{table}%
6 \ifdef{\setcaptiontype}{% caption package:
7 \setcaptiontype{\LTcaptiontype}%
8 \caption@setoptions{longtable}%
9 \caption@setoptions{@longtable}%
10 \caption@LT@setup%
11 }{% w/o caption package:
12 \renewcommand*{\@captiontype}{\LTcaptiontype}%
13 }%
14 \booltrue{LWR@starredlongtable}%
15 \boolfalse{LWR@longtable@havehead}%
16 \let\captionlistentry\LWR@LTcaptionlistentry%
17 \tabular{#2}%
18 }
19 {\endtabular\LWR@floatend}
20
21 \newenvironment{longtable}[2][]{%
22 \LWR@floatbegin{table}%
23 \ifdef{\setcaptiontype}{% caption package:
24 \setcaptiontype{\LTcaptiontype}%
25 \caption@setoptions{longtable}%
26 \caption@setoptions{@longtable}%
27 \caption@LT@setup%
28 }{% w/o caption package:
29 \renewcommand*{\@captiontype}{\LTcaptiontype}%
30 }%
31 \refstepcounter{\LTcaptiontype}%
32 \boolfalse{LWR@longtable@havehead}%
33 \let\captionlistentry\LWR@LTcaptionlistentry%
34 \tabular{#2}%
35 }
36 {\endtabular\LWR@floatend}
```

Provided for compatibility, but ignored:

```
37 \newcounter{LTchunksize}
```

Error for heads which should have been in `\warpprintonly`:

```

38 \newcommand*{\LWR@longtable@headerror}{%
39 \PackageError{lwarp-longtable}
40 {For longtable:\MessageBreak
41 1: Keep either one of an \protect\endhead\space or
42 \protect\endfirsthead\space\MessageBreak
43 \space phrase as-is, to be used by both print and HTML.\MessageBreak
44 2: Place any other \protect\end... phrases inside a\MessageBreak
45 \space\protect\warpprintonly\space macro,
46 to be ignored by HTML.\MessageBreak
47 3: Add a final footer for HTML at the end of the table\MessageBreak
48 \space inside a \protect\warpprintonly\space macro.
49 This can be\MessageBreak
50 \space a copy of an \protect\endfoot\space or
51 \protect\endfirstfoot\space phrase,\MessageBreak
52 \space but without the actual \protect\endfoot\space
53 or \protect\endfirstfoot\MessageBreak
54 \space macros. If using threeparttablex, add\MessageBreak
55 \space \protect\insertTableNotes\space here,
56 optionally with\MessageBreak
57 \space \protect\UseMinipageWidths\space in front.\MessageBreak
58 See the Lwarp documentation regarding longtables\MessageBreak
59 and threeparttablex}
60 {See the Lwarp documentation regarding longtables and threeparttablex.}
61 }

```

Error if more than one of `\endhead` or `\endfirsthead` is outside of `warpprintonly`.

```

62 \newcommand*{\LWR@longtable@maybeheaderror}{%
63 \ifbool{LWR@longtable@havehead}%
64 {\LWR@longtable@headerror}%
65 {%
66 \booltrue{LWR@longtable@havehead}
67 \LWR@tabularendofline% throws away options //[dim] and //*
68 }%
69 }

```

Error if more than one of these is outside of `warpprint`.

```

70 \def\endhead{\LWR@longtable@maybeheaderror}
71 \def\endfirsthead{\LWR@longtable@maybeheaderror}

```

Error if ANY of these is outside of `warpprint`.

```

72 \def\endfoot{\LWR@longtable@headerror}
73 \def\endlastfoot{\LWR@longtable@headerror}

74 \providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
75 \LWR@formatted{tabularnewline}

76 \newcommand{\setlongtables}{%} Obsolete command, does nothing.
77 \newlength{\LTleft}
78 \newlength{\LTright}

```

```

79 \newlength{\LTpre}
80 \newlength{\LTpost}
81 \newlength{\LTcapwidth}

82 \LetLtxMacro\LWR@origkill\kill
83 \renewcommand*\kill{\LWR@tabularendofline}
84 \appto\LWR@restoreorigformatting{%
85 \LetLtxMacro\kill\LWR@origkill%
86 }

```

---

File 243 **lwarp-lscape.sty**

§ 349 Package **lscape**

*(Emulates or patches code by D. P. CARLISLE.)*

Pkg lscape **lscape** is ignored.

**for HTML output:** Discard all options for lwarp-lscape.

```

1 \LWR@ProvidesPackageDrop{lscape}[2000/10/22]

2 \newenvironment{landscape}{}{}

```

---

File 244 **lwarp-ltablex.sty**

§ 350 Package **ltablex**

*(Emulates or patches code by ANIL K. GOEL.)*

Pkg ltablex **ltablex** is emulated by lwarp.

**for HTML output:** Relies on tabularx.

```

1 \RequirePackage{longtable}
2 \RequirePackage{tabularx}
3
4 \LWR@ProvidesPackageDrop{ltablex}[2014/08/13]
5
6 \DeclareDocumentEnvironment{tabularx}{m o m}
7 {\longtable{#3}}
8 {\endlongtable}
9
10 \DeclareDocumentEnvironment{tabularx*}{m o m}
11 {\longtable{#3}}
12 {\endlongtable}
13
14 \newcommand*\keepXColumns{}
15 \newcommand*\convertXColumns{}

```

---

File 245 **lwarp-ltcaption.sty**

§ 351 Package **ltcaption**

*(Emulates or patches code by AXEL SOMMERFELDT.)*

Pkg ltcaption **ltcaption** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{ltcaption}[2018/08/26]

\LTcaptype is already defined by lwarp.

longtable\* is already defined by lwarp-longtable.

```
2 \newlength{\LTcapskip}
3 \newlength{\LTcapleft}
4 \newlength{\LTcapright}
5 \newcommand*\LTcapmarginfalse{}
```

---

File 246 **lwarp-ltxgrid.sty**

§ 352 Package **ltxgrid**

Pkg ltxgrid **ltxgrid** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{ltxgrid}[2010/07/25]

```
2 \newcommand*\onecolumngrid{}
3 \newcommand*\twocolumngrid{}
4 \newcommand*\removestuff{}
5 \newcommand*\addstuff[2]{}
6 \newcommand*\replacestuff[2]{}

```

---

File 247 **lwarp-ltxtable.sty**

§ 353 Package **ltxtable**

Pkg ltxtable **ltxtable** is emulated.

 **table numbering** The print version does not seem to honor longtable\* from the caption package, while lwarp does.

**for HTML output:** 1 \RequirePackage{tabularx, longtable}  
2 \LWR@ProvidesPackageDrop{ltxtable}[1995/12/11]

```

\LTxtable {\langle width\rangle} {\langle file\rangle}
 3 \newcommand*{\LTxtable}[2]{%
 4 \input{#2}%
 5 }

```

---

File 248 **lwarp-lua-check-hyphen.sty**

§ 354 Package **lua-check-hyphen**

Pkg lua-check-hyphen lua-check-hyphen is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{lua-check-hyphen}[2018/04/19]

2 \newcommand\*{\LuaCheckHyphen}[1]{}

---

File 249 **lwarp-lua-visual-debug.sty**

§ 355 Package **lua-visual-debug**

Pkg lua-visual-debug lua-visual-debug is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{lua-visual-debug}[2016/05/30]

File 250 **lwarp-luacolor.sty**

§ 356 Package **luacolor**

Pkg luacolor luacolor is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{luacolor}[2016/05/16]

2 \newcommand{\luacolorProcessBox}[1]{}

---

File 251 **lwarp-luamplib.sty**

§ 357 Package **luamplib**

*(Emulates or patches code by HANS HAGEN, TACO HOEKWATER, ELIE ROUX, PHILIPP GESANG, KIM DOHYUN.)*

Pkg luamplib luamplib is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{luamplib}[2020/02/24]

```

2 \BeforeBeginEnvironment{mplibcode}{%
3 \begin{lateximage}[-mplibcode~\PackageDiagramAltText]%
4 }
5 \AfterEndEnvironment{mplibcode}{\end{lateximage}}

```

File 252 **lwarp-luatexko.sty**

§ 358 Package **luatexko**

*(Emulates or patches code by DOHYUN KIM, SOOJIN NAM.)*

Pkg luatexko **luatexko** is patched for use by lwarp.

Modern HTML is used for `\dotemph`, `\ruby`, and offset and thickness control for `\uline`, etc.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{luatexko}[2020/03/20]

2 \newcommand{\LWR@HTML@dotemph}[1]{%
3 \uline{#1}%
4 \InlineClass[text-emphasis-style: dot]{dotemph}{#1}%
5 }
6 \LWR@formatted{dotemph}
7
8 \newcommand{\LWR@HTML@ruby}[2]{%
9 \LWR@htmltagc{ruby}%
10 \LWR@htmltagc{rb}#1\LWR@htmltagc{/rb}%
11 \LWR@htmltagc{rp}(\LWR@htmltagc{/rp})%
12 \LWR@htmltagc{rt}#2\LWR@htmltagc{/rt}%
13 \LWR@htmltagc{rp})\LWR@htmltagc{/rp}%
14 \LWR@htmltagc{/ruby}%
15 }
16 \LWR@formatted{ruby}

```

The following is modified from lwarp-ulem:

```

17 \NewDocumentCommand{\LWR@HTML@uline}{+m}{%
18 \InlineClass%
19 (text-decoration:underline; text-decoration-skip: auto)%
20 [%
21 text-underline-offset: \ulinedown ;
22 text-decoration-thickness: \ulinewidth%
23]%
24 {uline}{\LWR@isolate{#1}}%
25 }
26 \LWR@formatted{uline}
27
28 \NewDocumentCommand{\LWR@HTML@uuuline}{+m}{%
29 \InlineClass%
30 (%
31 text-decoration:underline; text-decoration-skip: auto;%
32 text-decoration-style:double%

```

```
33)%
34 [%
35 text-underline-offset: \ulinedown ;
36 text-decoration-thickness: \ulinewidth%
37]%
38 {\uuline}{\LWR@isolate{#1}}%
39 }
40 \LWR@formatted{uuline}
41
42 \NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
43 \InlineClass%
44 (%
45 text-decoration:underline; text-decoration-skip: auto;%
46 text-decoration-style:wavy%
47)%
48 [%
49 text-underline-offset: \ulinedown ;
50 text-decoration-thickness: \ulinewidth%
51]%
52 {\uwave}{\LWR@isolate{#1}}%
53 }
54 \LWR@formatted{uwave}
55
56 \NewDocumentCommand{\LWR@HTML@sout}{+m}{%
57 \InlineClass%
58 (text-decoration:line-through)%
59 [text-decoration-thickness: \ulinewidth]%
60 {\sout}{\LWR@isolate{#1}}%
61 }
62 \LWR@formatted{sout}
63
64 \NewDocumentCommand{\LWR@HTML@xout}{+m}{%
65 \InlineClass%
66 (text-decoration:line-through)%
67 [text-decoration-thickness: \ulinewidth]%
68 {\xout}{\LWR@isolate{#1}}%
69 }
70 \LWR@formatted{xout}
71
72 \NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
73 \InlineClass%
74 (%
75 text-decoration:underline;%
76 text-decoration-skip: auto;%
77 text-decoration-style:dashed%
78)%
79 [%
80 text-underline-offset: \ulinedown ;
81 text-decoration-thickness: \ulinewidth%
82]%
83 {\dashuline}{\LWR@isolate{#1}}%
84 }
85 \LWR@formatted{dashuline}
86
87 \NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
```

```

88 \InlineClass%
89 (%
90 text-decoration:underline;%
91 text-decoration-skip: auto;%
92 text-decoration-style: dotted%
93) %
94 [%
95 text-underline-offset: \ulinedown ;
96 text-decoration-thickness: \linewidth%
97] %
98 {dotuline}{\LWR@isolate{#1}}%
99 }
100 \LWR@formatted{dotuline}

```

---

File 253 **lwarp-luatodonotes.sty**

§ 359 Package **luatodonotes**

*(Emulates or patches code by FABIAN LIPP.)*

Pkg luatodonotes **luatodonotes** is emulated.

The documentation for `todonotes` and `luatodonotes` have an example with a `todo` inside a caption. If this example does not work it will be necessary to move the `todo` outside of the caption.

**for HTML output:** 1 \LWR@ProvidesPackagePass{luatodonotes}[2017/09/30]

Nullify options:

```

2 \@todonotes@additionalMarginEnabledfalse
3 \if@todonotes@disabled
4 \else
5
6 \newcommand{\ext@todo}{tdo}
7
8 \renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}

9 \let\LWR@TODONOTES@orig@todotoc\todotoc
10
11 \renewcommand*{\todotoc}{%
12 \LWR@phantomsection%
13 \LWR@TODONOTES@orig@todotoc%
14 }
15
16
17 \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
18 \fcolorbox
19 {\@todonotes@currentbordercolor}
20 {\@todonotes@currentbackgroundcolor}
21 {\arabic{@todonotes@numberoftodonotes}}

```

```

22 \marginpar{\@todonotes@drawMarginNote}
23 }
24
25 \renewcommand{\@todonotes@drawInlineNote}{%
26 \fcolorboxBlock%
27 {\@todonotes@currentbordercolor}%
28 {\@todonotes@currentbackgroundcolor}%
29 {%
30 \if@todonotes@authorgiven%
31 {\@todonotes@author:\,}%
32 \fi%
33 \@todonotes@text%
34 }%
35 }
36
37 \newcommand{\@todonotes@drawMarginNote}{%
38 \if@todonotes@authorgiven%
39 \@todonotes@author\par%
40 \fi%
41 \arabic{\@todonotes@numberoftodonotes}: %
42 \fcolorbox%
43 {\@todonotes@currentbordercolor}%
44 {\@todonotes@currentbackgroundcolor}%
45 {%
46 \@todonotes@sizecommand%
47 \@todonotes@text %
48 }%
49 }%
50
51 \renewcommand{\missingfigure}[2][{}]{%
52 \setkeys{todonotes}{#1}%
53 \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
54 \fcolorboxBlock%
55 {\@todonotes@currentbordercolor}%
56 {\@todonotes@currentfigcolor}%
57 {%
58 \setlength{\fboxrule}{4pt}%
59 \fcolorbox{red}{white}{Missing figure} \quad #2%
60 }
61 }
62
63 \LetLtxMacro\LRWRTODONOTES@orig@todocommon\@todocommon
64
65 \RenewDocumentCommand{\@todocommon}{m m}{%
66 \begingroup%
67 \renewcommand*\phantomsection{}%
68 \LRWRTODONOTES@orig@todocommon{#1}{#2}%
69 \endgroup%
70 }
71
72 \renewcommand{\@todoarea}[3][{}]{%
73 \@todonotes@areaselectedtrue%
74 \@todocommon{#1}{#2}%
75 \@todonotes@textmark@highlight{#3}%
76 \zref@label{\@todonotes@arabic{\@todonotes@numberoftodonotes}@end}%

```

```

77 }%
78
79
80 \DeclareDocumentCommand{\todonotes@textmark@highlight}{m}{%
81 \InlineClass[background:\LWR@origpound{ }B3FFB3]{highlight}{#1}%
82 }
83
84 \fi% \if@todonotes@disabled

```

File 254 **lwarp-lyluatex.sty**

§ 360 Package **lyluatex**

(Emulates or patches code by FR. JACQUES PERON, URS LISKA, BR. SAMUEL SPRINGUEL.)

Pkg lyluatex lyluatex is patched for use by lwarp.

For the first compile, to set *lwarpmk*'s configuration, use:

```
lualatex --shell-escape <filename>
```

⚠ **images** After compiling the document with **lwarpmk html**, use **lwarpmk images** to convert the Lilypond images for HTML.

The option `insert=systems` results in an image per system. Each music image “system” is placed inside a `<span>` of class `lyluatex`, which defaults to `display: inline-block`.

⚠ **insert=fullpage** The option `insert=fullpage` results in a single image per page of printed output. Each music “fullpage” image is placed inside a `<div>` of class `lyluatex`. To match the number of measures per line with the printed version, use the `geometry` package to select the page geometry, or use the `lyluatex` options for page and staff sizes.

⚠ **options** To use `\linewidth` or `\textwidth` inside the package options for `lyluatex`, use the `kvoptions-patch` package first:

```

\usepackage{kvoptions-patch}
\usepackage[... ,line-width=0.8\linewidth,...]{lyluatex}

```

⚠ **raw-pdf** If using `raw-pdf`, the resulting PDF images must be converted to SVG:

```
Enter ⇒ lwarpmk pdftosvg tmp-ly/*.pdf
```

**for HTML output:**

```

1 \LWR@origRequirePackage{luacode}
2
3 \LWR@ProvidesPackagePass{lyluatex}[2019/05/27]

```

User-redefinable ALT tag:

```
4 \newcommand*{\LyluatexImageAltText}{-lilypond-~\PackageDiagramAltText}
```

```

\ly@compilescore {<Lilypond object>}
5 \LetLtxMacro\LWR@orig@ly@compilescore\ly@compilescore
6
7 \renewcommand*{\ly@compilescore}[1]{%

```

A local group holds a number of changes:

```
8 \begingroup%
```

The user's original geometry and font size are restored to match the print version. This allows for correct spacing in the musical score.

```
9 \LWR@maybe@orignewpage%
10 \LWR@origloadgeometry{\LWR@usergeometry}%
11 \LWR@print@normalsize%
```

A local group holds a redefined `\includegraphics` which is used by *lyluatex.lua* to insert the *Lilypond* score if `insert=systems` is used. This is now placed inside a `lateximage`, which itself is placed inside a `<span>` of class `lyluatex`.

`\LWR@addbaselinemarker` preserves the left margins.

```

12 \renewcommand{\includegraphics}[2][]{%
13 \InlineClass{lyluatex}{%
14 \begin{lateximage}[\LyluatexImageAltText]%
15 \LWR@addbaselinemarker%
16 \LWR@originincludegraphics{##2}%
17 \end{lateximage}%
18 }%
19 }%

```

From the original:

```

20 \ly@setunits%
21 \directlua{
22 ly_opts:set_option('currfiledir', [[\currfiledir]])
23 ly_opts:set_option('twoside', '\ly@istwosided')
24 #1
25 }%
26 \ly@resetunits%
27 \ly@currentfonts%

```

The fullpage version is set inside an HTML `<div>`:

```

28 \directlua{
29 if (ly.score.insert == 'fullpage') then
30 tex.print{[[\string\begin{BlockClass}{lyluatex}]]}
31 end
32 }%

```

Generate the score:

```
33 \directlua{ly.score:process()}%
```

Close the `<div>`:

```

34 \directlua{
35 if (ly.score.insert == 'fullpage') then
36 tex.print{[[\string\end{BlockClass}]]}
37 end

```

```
38 }%
```

Move to a new page and renew the regular page geometry:

```
39 \LWR@maybe@orignewpage%
40 \LWR@origrestoregeometry%
```

End of the local group.

```
41 \endgroup%
42 }
```

In HTML the following generates an error, so is removed:

```
43 \xpatchcmd{\endly@bufferenv}
44 {\hspace{0pt}\}
45 {}
46 {}
47 {\LWR@patcherror{lyluatex}{endly@bufferenv}}
```

File 255 **lwarp-magaz.sty**

§ 361 Package **magaz**

Pkg magaz **magaz** is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{magaz}[2011/11/24]

```
2 \newcommand\FirstLine[1]{%
3 \begingroup%
4 \FirstLineFont{%
5 \LWR@textcurrentcolor{%
6 \LWR@textcurrentfont{%
7 #1%
8 }%
9 }%
10 }%
11 \endgroup%
12 }
13
14 \providecommand\FirstLineFont{\scshape}
```

File 256 **lwarp-makeidx.sty**

§ 362 Package **makeidx**

*(Emulates or patches code by L<sup>A</sup>T<sub>E</sub>X PROJECT TEAM.)*

Pkg makeidx **makeidx** is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{makeidx}[2014/09/29]

`\@wrindex` is redefined `\AtBeginDocument` by the `lwarp` core.

`\printindex`

```
2 \preto\printindex{%
3 \LWR@maybe@orignewpage%
4 \LWR@startpars%
5 }
```

---

File 257 **lwarp-manyfoot.sty**

§ 363 Package **manyfoot**

Pkg manyfoot manyfoot is emulated.

**bigfoot**, **manyfoot** Verbatim footnotes are not yet supported.

 **verbatim**

If using the `bigfoot` package, and possibly also `manyfoot`, problems may occur with counter allocation because `lwarp` uses many counters, and there is a difference in how counters numbered 256 and up are handled in `pdfLATEX`. With `bigfoot` this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining `bigfoot` or `manyfoot` footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use `XYLATEX` or `LuaLATEX` instead of `pdfLATEX`.

`lwarp`'s emulation of `bigfoot` uses `manyfoot`, so some of the `bigfoot` enhancements are included here.

The `bigfoot` “default” footnote is ignored, using the `lwarp` version instead.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{manyfoot}[2005/09/11]

2 \RequirePackage{nccfoots}
3
4 \newcommand{\extrafootnoterule}{}
5
6 \let\defaultfootnoterule\footnoterule
7
8 \newcommand*{\SelectFootnoteRule}[2][0]{}
9
10 \newcommand{\footnoterulepriority}{1}
11
12 \newcommand{\SetFootnoteHook}[1]{}
13 \@onlypreamble\SetFootnoteHook
14
15 \newcommand{\SplitNote}{}
16
17 \newcommand*\ExtraParaSkip[1]{}

```

```

18
19 \newcommand*{\newfootnote}[2][plain]{%
20 \ifstrequal{#2}{default}{}% not "default"
21 \expandafter\newbox\csname LWR@footnote#2box\endcsname%
22 \appto{\LWR@printpendingfootnotes}{%
23 \LWR@@printpendingfootnotes{footnote#2}%
24 }
25 \long\csdef{Footnotetext#2}##1##2{%
26 \NCC@makefnmark{##1}%
27 \LWR@@footnotetext{##2}{LWR@footnote#2box}%
28 }%
29 \long\csdef{Footnotetext#2+}##1##2{%
30 \NCC@makefnmark{##1}%
31 \LWR@@footnotetext{##2}{LWR@footnote#2box}%
32 }%
33 }% not "default"
34 }
35 \@onlypreamble\newfootnote
36
37 \newcommand*{\DeclareNewFootnote}[2][plain]{%
38 \ifnextchar[%
39 {\LWR@manyfoot@declare{#1}{#2}}%
40 {\LWR@manyfoot@declare{#1}{#2}[arabic]}%
41 }
42
43 \def\LWR@manyfoot@declare#1#2[#3]{%
44 \ifstrequal{#2}{default}{}% not "default"
45 \newfootnote[#1]{#2}%
46 \newcounter{footnote#2}%
47 \newcounter{footnote#2Reset}%
48 \setcounter{footnote#2Reset}{0}%
49 \csdef{thefootnote#2}{%
50 \expandafter\noexpand\csname @#3\endcsname%
51 \expandafter\noexpand\csname c@footnote#2\endcsname%
52 }%

```

For **bigfoot**, the footnote commands may be appended with one or two plusses or one or two minuses, which are ignored in HTML.

```

53 \expandafter\NewDocumentCommand\csname footnote#2\endcsname{t{+}t{+}t{-}t{-}}{%
54 \stepcounter{footnote#2}%
55 \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
56 \@footnotemark%
57 \csuse{Footnotetext#2}\@thefnmark}% absorbs the footnote contents
58 }%
59 \csdef{footnotemark#2}{%
60 \stepcounter{footnote#2}%
61 \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
62 \@footnotemark%
63 }%
64 \expandafter\NewDocumentCommand\csname footnotetext#2\endcsname{t{+}t{+}t{-}t{-}}{%
65 \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
66 \csuse{Footnotetext#2}\@thefnmark}% absorbs the footnote contents
67 }%
68 \csdef{Footnotemark#2}{%

```

```

69 \Footnotemark%
70 }%
71 \csdef{Footnote#2}##1{%
72 \Footnotemark{##1}%
73 \csuse{Footnotetext#2}{##1}%
74 }%
75 }% not "default"
76 }
77 \@onlypreamble\DeclareNewFootnote

```

---

File 258 **lwarp-marginal.sty**

§ 364 Package **marginal**

Pkg marginal marginal is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{marginal}

2 \newcommand*{\showlostmarginals}{}
3 \newcommand*{\enlargefreelist}{}
4 \newcommand*{\onesidemarginals}{}

```

---

File 259 **lwarp-marginfit.sty**

§ 365 Package **marginfit**

Pkg marginfit marginfit is ignored.

**for HTML output:** Discard all options for lwarp-marginfit:

```

1 \LWR@ProvidesPackageDrop{marginfit}[2018/06/08]

```

---

File 260 **lwarp-marginfix.sty**

§ 366 Package **marginfix**

*(Emulates or patches code by STEPHEN HICKS.)*

Pkg marginfix marginfix is ignored.

**for HTML output:** Discard all options for lwarp-marginfix:

```

1 \LWR@ProvidesPackageDrop{marginfix}[2013/09/08]

2 \newcommand*{\marginsskip}[1]{}
3 \newcommand*{\clearmargin}{}
4 \newcommand*{\softclearmargin}{}

```

```

5 \newcommand*\extendmargin}[1]{}
6 \newcommand*\mparshift}[1]{}
7 \newdimen\marginheightadjustment
8 \newdimen\marginposadjustment
9 \newcommand*\blockmargin}[1][{}]{
10 \newcommand*\unblockmargin}[1][{}]{
11 \newcommand*\marginphantom}[2][{}]{

```

---

File 261 **lwarp-marginnote.sty**

§ 367 Package **marginnote**

*(Emulates or patches code by MARKUS KOHM.)*

Pkg marginnote marginnote is emulated.

**for HTML output:** Discard all options for lwarp-marginnote:

```

1 \LWR@ProvidesPackageDrop{marginnote}[2018/08/09]

2 \NewDocumentCommand{\marginnote}{+o +m o}{\marginpar{#2}}

3 \newcommand*\marginnoteleftadjust{}
4 \newcommand*\marginnoterightadjust{}
5 \newcommand*\marginnotetextwidth{}
6 \let\marginnotetextwidth\textwidth
7 \newcommand*\marginnotevadjust{}
8 \newcommand*\marginfont{}
9 \newcommand*\raggedleftmarginnote{}
10 \newcommand*\raggedrightmarginnote{}

11 \appto\LWR@restoreorigformatting{%
12 \RenewDocumentCommand{\marginnote}{+o +m o}{
13 }

For MATHJAX:

14 \begin{warpMathJax}
15 \CustomizeMathJax{\newcommand{\LWRmarginnote}[1][{}]}
16 \CustomizeMathJax{\newcommand{\marginnote}[2][{}]{\quad\small\textrm{#2}}\LWRmarginnote}}
17 \end{warpMathJax}

```

---

File 262 **lwarp-marvosym.sty**

§ 368 Package **marvosym**

*(Emulates or patches code by THOMAS HENLICH, MOJCA MIKLAVEC.)*

Pkg marvosym marvosym is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{marvosym}[2011/07/20]
2 \renewcommand{\mvchr}[1]{%
3 \begin{lateximage}*[symbol #1][marvosym #1]%
4 \mvs\char#1%
5 \end{lateximage}%
6 }
7
8 \renewcommand{\textmvs}[1]{%
9 \begin{lateximage}%
10 \mvs #1%
11 \end{lateximage}%
12 }
```

File 263 **lwarp-mathalpha.sty**

§ 369 Package **mathalpha**

*(Emulates or patches code by MICHAEL SHARPE.)*

Pkg mathalpha **mathalpha** is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, and some bold fonts may not be supported by MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{mathalpha}[2019/10/05]
2
3 \begin{warpMathJax}
4 \CustomizeMathJax{\newcommand{\mathbbb}[1]{\boldsymbol{\mathbb{#1}}}}% not bold
5 \CustomizeMathJax{\newcommand{\mathbcal}[1]{\boldsymbol{\mathcal{#1}}}}
6 \CustomizeMathJax{\newcommand{\mathbfrac}[1]{\boldsymbol{\mathfrak{#1}}}}
7 \CustomizeMathJax{\newcommand{\mathbscr}[1]{\boldsymbol{\mathscr{#1}}}}% not bold
8 \end{warpMathJax}
```

File 264 **lwarp-mathastext.sty**

§ 370 Package **mathastext**

*(Emulates or patches code by JEAN-FRANÇOIS BURNOL.)*

Pkg mathastext **mathastext** is used as-is for SVG math, and emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{mathastext}[2019/11/16]
2
3 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
4 \begin{warpMathJax}
```

```

5 \ifmst@itgreek
6 % \LWR@mathjax@addgreek@l@it{}{}
7 \else
8 \ifmst@upgreek
9 \LWR@mathjax@addgreek@l@up{}{}
10 \else
11 \ifmst@frenchmath
12 \LWR@mathjax@addgreek@l@up{}{}
13 \else
14 \ifmst@italic
15 % \LWR@mathjax@addgreek@l@it{}{}
16 \else
17 \LWR@mathjax@addgreek@l@up{}{}
18 \fi
19 \fi
20 \fi
21 \fi
22
23 \ifcase@mst@greek@select
24 \or{\LWR@mathjax@addgreek@u@it*{}{}}
25 % \or{\LWR@mathjax@addgreek@u@up*{}{}}
26 \fi
27
28 \CustomizeMathJax{\newcommand{\mathnormalbold}[1]{\boldsymbol{#1}}}
29 \CustomizeMathJax{\newcommand{\MathEulerBold}[1]{\boldsymbol{#1}}}
30 \CustomizeMathJax{\newcommand{\MathEuler}[1]{#1}}
31 \CustomizeMathJax{\newcommand{\MathPSymbol}[1]{#1}}
32 \CustomizeMathJax{\let\fouriervec\vec}
33 \CustomizeMathJax{\let\pmvec\vec}
34 \CustomizeMathJax{\let\inodot\imath}
35 \CustomizeMathJax{\let\jnodot\jmath}
36 \CustomizeMathJax{\let\shortiff\iff}
37 \CustomizeMathJax{\let\longto\longrightarrow}
38 \CustomizeMathJax{\newcommand{\infitypsy}{\mathord{\unicode{x221E}}}}
39 \CustomizeMathJax{\newcommand{\proptopsy}{\mathrel{\unicode{x221D}}}}
40 \CustomizeMathJax{\let\prodpsy\prod}
41 \CustomizeMathJax{\let\sumpsy\sum}
42 \CustomizeMathJax{\let\MToriginalprod\prod}
43 \CustomizeMathJax{\let\MToriginalsum\sum}
44 \CustomizeMathJax{\newcommand{\DotTriangle}{\mathord{\unicode{x2234}}}}
45 \end{warpMathJax}

```

---

File 265 **lwarp-mathcomp.sty**

§ 371 Package **mathcomp**

(Emulates or patches code by TILMANN BÖB.)

Pkg mathcomp mathcomp is supported as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mathcomp}[2001/01/07]

2 \begin{warpMathJax}

```

3 \CustomizeMathJax{\newcommand{\tcohm}{\mathrm{\Omega}}}
4 \CustomizeMathJax{\newcommand{\tccelsius}{\unicode{x2103}}}
5 \CustomizeMathJax{\newcommand{\tcmu}{\mathrm{\unicode{x00B5}}}}
6 \CustomizeMathJax{\newcommand{\tcpertousand}{\unicode{x2030}}}
7 \CustomizeMathJax{\newcommand{\tcpertenthousand}{\unicode{x2031}}}
8 \CustomizeMathJax{\newcommand{\tcddegree}{\mathrm{^\circ}}}
9 \CustomizeMathJax{\newcommand{\tcdigitoldstyle}[1]{\oldstyle{#1}}}
10 \end{warpMathJax}

```

File 266 **lwarp-mathdesign.sty**

§ 372 Package **mathdesign**

(Emulates or patches code by PAUL PICHAREAU.)

Pkg mathdesign mathdesign is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options except greekuppercase and greeklowercase. The dedicated macros for upright and italic greek letters work correctly, although the user may wish to swap the definitions for epsilon and phi.

SVG math should appear the same as the printed output.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mathdesign}[2013/08/29]

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
5
6 \begin{warpMathJax}
7 \LWR@infoprocessingmathjax{mathdesign}

```

Default greek upright or italicized:

```

8 \if@MD@grupright
9 \LWR@mathjax@addgreek@l@up{}{}
10 \fi
11
12 \if@MD@GRupright
13 \else
14 \LWR@mathjax@addgreek@u@it*{}{}
15 \fi

```

Upright:

```

16 \LWR@mathjax@addgreek@l@up{}{up}
17 \LWR@mathjax@addgreek@u@up*{}{up}

```

Italicized:

```
18 \LWR@mathjax@addgreek@l@it{}{it}
19 \LWR@mathjax@addgreek@u@it*{}{it}
```

Adapt to mathdesign inconsistency:

```
20 \CustomizeMathJax{\let\digammaup\Digammaup}
21 \CustomizeMathJax{\renewcommand{\digammait}{\mathit{\digammaup}}}
```

Extra symbols:

```
22 \CustomizeMathJax{\newcommand{\smallin}{\mathrel{\unicode{x220A}}}}
23 \CustomizeMathJax{\newcommand{\smallowns}{\mathrel{\unicode{x220D}}}}
24 \CustomizeMathJax{\newcommand{\notsmallin}{\mathrel{\LWROverlaysymbols{/}{\unicode{x220A}}}}}
25 \CustomizeMathJax{\newcommand{\notsmallowns}{\mathrel{\LWROverlaysymbols{/}{\unicode{x220D}}}}}
26 \CustomizeMathJax{\newcommand{\rightangle}{\mathord{\unicode{x221F}}}}
```

Integrals:

```
27 \CustomizeMathJax{\newcommand{\intclockwise}{\mathop{\unicode{x2231}}\limits}}
28 \CustomizeMathJax{\newcommand{\ointclockwise}{\mathop{\unicode{x2232}}\limits}}
29 \CustomizeMathJax{\newcommand{\ointctrlockwise}{\mathop{\unicode{x2233}}\limits}}
30 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
31 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x2230}}\limits}}
```

Math and text mode:

```
32 \CustomizeMathJax{\newcommand{\ddag}{\unicode{x2021}}}
33 \CustomizeMathJax{\newcommand{\P}{\unicode{x00B6}}}
34 \CustomizeMathJax{\newcommand{\copyright}{\unicode{x00A9}}}
35 \CustomizeMathJax{\newcommand{\dag}{\unicode{x2020}}}
36 \CustomizeMathJax{\newcommand{\pounds}{\unicode{x00A3}}}
```

Extra symbols:

```
37 \CustomizeMathJax{\newcommand{\iddots}{\mathinner{\unicode{x22F0}}}}
38 \CustomizeMathJax{\newcommand{\utimes}{\mathbin{\overline{\times}}}}
39 \CustomizeMathJax{\newcommand{\dtimes}{\mathbin{\underline{\times}}}}
40 \CustomizeMathJax{\newcommand{\udtimes}{\mathbin{\overline{\underline{\times}}}}}
41 \CustomizeMathJax{\newcommand{\leftwavy}{\left\{}}
42 \CustomizeMathJax{\newcommand{\rightwavy}{\right\}}
43
44 \end{warpMathJax}
```

---

File 267 **lwarp-mathdots.sty**

§ 373 Package **mathdots**

(Emulates or patches code by DAN LUECKING.)

Pkg mathdots mathdots is used as-is for SVG math, and emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{mathdots}[2014/06/11]

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\iddots}{\mathinner{\unicode{x22F0}}}}
4 \CustomizeMathJax{\let\fixedddots\ddots}
5 \CustomizeMathJax{\let\fixedvdots\vdots}
6 \CustomizeMathJax{\let\fixediddots\iddots}
7 \CustomizeMathJax{\let\originalddots\ddots}
8 \CustomizeMathJax{\let\originalvdots\vdots}
9 \CustomizeMathJax{\let\originaliddots\iddots}
10 \CustomizeMathJax{\let\originaldddot\dddot}
11 \CustomizeMathJax{\let\originalddddot\ddddot}
12 \end{warpMathJax}

```

---

File 268 **lwarp-mathfixs.sty**

§ 374 Package **mathfixs**

(Emulates or patches code by NIKLAS BEISERT.)

Pkg mathfixs mathfixs is used as-is for SVG math, and is emulated for MATHJAX.

 Greek letters are unchanged.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mathfixs}[2018/12/30]

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\rfrac}[2]{\tfrac{#1}{#2}}}
4 \CustomizeMathJax{\newcommand{\vfrac}[2]{\mathinner{{}^{\#1}\!/_{\#2}}}}
5 \CustomizeMathJax{\newcommand{\ProvideMathFix}[1]{} }
6 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
7 \CustomizeMathJax{\newcommand{\.}{\,}}
8 \end{warpMathJax}

```

---

File 269 **lwarp-mathpazo.sty**

§ 375 Package **mathpazo**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg mathpazo mathpazo is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options. The dedicated macros for upright greek letters do work correctly.

SVG math should appear the same as the printed output.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mathpazo}[2020/03/25]

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{mathpazo}
6
7 \ifpazo@slGreek
8 \LWR@mathjax@addgreek@u@it*{}{}
9 \fi
10
11 \LWR@mathjax@addgreek@u@up*{}{}
12
13 \CustomizeMathJax{\newcommand{\mathbold}[1]{\boldsymbol{#1}}}
14 \end{warpMathJax}

```

---

File 270 **lwarp-mathptmx.sty**

§ 376 Package **mathptmx**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg mathptmx mathptmx is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options. The dedicated macros for upright greek letters do work correctly.

SVG math should appear the same as the printed output.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mathptmx}[2020/03/25]

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{mathptmx}
6
7 \@ifpackagewith{mathptmx}{slantedGreek}
8 {\LWR@mathjax@addgreek@u@it*{}{}}
9 {}
10
11 \LWR@mathjax@addgreek@u@up*{}{}
12 \end{warpMathJax}

```

---

File 271 **lwarp-mathspec.sty**

§ 377 Package **mathspec**

(Emulates or patches code by ANDREW GILBERT MOSCHOU.)

Pkg mathspec mathspec is used as-is with SVG math, and is emulated for MATHJAX.

 **quotes** Double quotes (`\` and the `"` character) are removed during MATHJAX emulation, but this also includes inside `\text`.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{mathspec}[2016/12/22]

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}

```

Neutralize double quotes (`"` and `\`):

```

5 \booltrue{LWR@MathJax@silentquotes}

```

Sort options for out Greek emulation:

```

6 \AtBeginDocument{
7 \ifcase\eu@GreekUppercase@@value %% If Greek Uppercase Regular
8 \LWR@mathjax@addgreek@u@up*{}{}
9 \or %% If Greek Uppercase Italic
10 \LWR@mathjax@addgreek@u@it*{}{}
11 \or %% If Greek Uppercase Plain
12 \LWR@mathjax@addgreek@u@up*{}{}
13 \fi
14 \ifcase\eu@GreekLowercase@@value %% If Greek Lowercase Regular
15 \LWR@mathjax@addgreek@l@up{}{}
16 \or %% If Greek Lowercase Italic
17 \LWR@mathjax@addgreek@l@it{}{}
18 \or %% If Greek Lowercase Plain
19 \LWR@mathjax@addgreek@l@it{}{}
20 \fi
21 }

```

Swap definitions according the mathspec conditionals:

```

22 \newcommand*{\LWR@mathspec@varforms}{%
23 \eu@ifbooltrue{GreekLowercase}{
24 \eu@ifbooltrue{exchangebetaforms}{
25 \CustomizeMathJax{\let\LWRorigbeta\beta}
26 \CustomizeMathJax{\let\beta\varbeta}
27 \CustomizeMathJax{\let\varbeta\LWRorigbeta}
28 }
29 \eu@ifbooltrue{exchangeepsilonforms}{
30 \CustomizeMathJax{\let\LWRorigepsilon\epsilon}
31 \CustomizeMathJax{\let\epsilon\varepsilon}
32 \CustomizeMathJax{\let\varepsilon\LWRorigepsilon}
33 }
34 \eu@ifbooltrue{exchangethetaforms}{
35 \CustomizeMathJax{\let\LWRorigtheta\theta}
36 \CustomizeMathJax{\let\theta\vartheta}
37 \CustomizeMathJax{\let\vartheta\LWRorigtheta}
38 }
39 \eu@ifbooltrue{exchangekappaforms}{
40 \CustomizeMathJax{\let\LWRorigkappa\kappa}
41 \CustomizeMathJax{\let\kappa\varkappa}

```

```

42 \CustomizeMathJax{\let\varkappa\LWRorigkappa}
43 }
44 \eu@ifbooltrue{exchangepiforms}{
45 \CustomizeMathJax{\let\LWRorigpi\pi}
46 \CustomizeMathJax{\let\pi\varpi}
47 \CustomizeMathJax{\let\varpi\LWRorigpi}
48 }
49 \eu@ifbooltrue{exchangerhoforms}{
50 \CustomizeMathJax{\let\LWRorigrho\rho}
51 \CustomizeMathJax{\let\rho\varrho}
52 \CustomizeMathJax{\let\varrho\LWRorigrho}
53 }
54 \eu@ifbooltrue{exchangephiforms}{
55 \CustomizeMathJax{\let\LWRorigphi\phi}
56 \CustomizeMathJax{\let\phi\varphi}
57 \CustomizeMathJax{\let\varphi\LWRorigphi}
58 }
59 }
60 \eu@ifbooltrue{GreekUppercase}{
61 \eu@ifbooltrue{exchangeThetaforms}{
62 \CustomizeMathJax{\let\LWRorigTheta\Theta}
63 \CustomizeMathJax{\let\Theta\varTheta}
64 \CustomizeMathJax{\let\varTheta\LWRorigTheta}
65 }
66 }
67 }

```

Append new action to mathspec's `\AtBeginDocument` code:

```

68 \xapptocmd{\exchangeforms}
69 {\AtBeginDocument{\LWR@mathspec@varforms}}
70 {}
71 {\LWR@patcherror{mathspec}{exchangeforms}}
72
73 \end{warpMathJax}

```

---

File 272 **lwarp-mathtools.sty**

§ 378 Package **mathtools**

(Emulates or patches code by MORTEN HØGHOLM, LARS MADSEN.)

Pkg `mathtools` `mathtools` is patched for use by `lwarp`. Emulation macros are provided for `MATHJAX`.

 **equation numbering** `showonlyrefs` is disabled, as it conflicts with `cleveref`, which is used by `lwarp`. Equation numbers may not match the print version.

 **italic correction** `mathic` is not emulated for HTML.

 **MATHJAX** If using `MATHJAX`:

- `mathtools disallowspace` does not work for `MATHJAX`. Protect brackets which are not optional arguments, such as:

```
\begin{gathered}{}
[p]=1 . . .
\end{gathered}
```

- `showonlyrefs` does not work in MATHJAX, and will result in a difference in equation numbering compared to the print version.
- Due to MATHJAX limitations, the following do not render well: `\overbracket`, `\underbracket`, `\overbrace`, `\underbrace`, `rcases`, `drcases`, `\Aboxed`, and `\ArrowBetweenLines`.
- For the new cases-like environments, `\text` must be used to set the normal roman font if desired.
- `alignat` in MATHJAX requires math mode, but in L<sup>A</sup>T<sub>E</sub>X it doesn't. It may be required to use `warpHTML` and `warpprint` to isolate a version for each mode.
- `\DeclarePairedDelimiter` and related must be in the preamble before `\begin{document}`.

for HTML output:

```
1 \LWR@ProvidesPackagePass{mathtools}[2018/01/08]
```

```
2 \RequirePackage{graphicx}
```

```
3 \MHInternalSyntaxOn
```

Forces `showonlyrefs` off because `lwarp` uses `cleveref`, which is not compatible with `showonlyrefs`.

```
4 \renewcommand*{\MT_showonlyrefs_true}{%
5 \PackageWarningNoLine{lwarp}
6 {%
7 Mathtools \space showonlyrefs \space conflicts \space
8 with \space cleveref,\MessageBreak
9 which \space is \space used \space by \space lwarp, \space
10 so \space showonlyrefs \space is\MessageBreak
11 forced \space off. \space\space
12 Equation \space numbers \space may \space not \space match%
13 }
14 \MT_showonlyrefs_false:
15 }
16 \mathtoolsset{showonlyrefs=false}
```

Forces math italic correction off. Not patched for `lwarp`.

```
17 \renewcommand*{\MT_mathic_true:}{\MT_mathic_false:}
18 \mathtoolsset{mathic=false}
```

```
19 \MHInternalSyntaxOff
```

For MATHJAX:

```
20 \begin{warpMathJax}
```

```

21 \LWR@infoprocessingmathjax{mathtools}
22
23 \CustomizeMathJax{\newcommand{\mathlLap}[2][\{#1#2\}}
24 \CustomizeMathJax{\newcommand{\mathrLap}[2][\{#1#2\}}
25 \CustomizeMathJax{\newcommand{\mathcLap}[2][\{#1#2\}}
26 \CustomizeMathJax{\newcommand{\mathmbox}[1]{#1}}
27 \CustomizeMathJax{\newcommand{\cLap}[1]{#1}}
28 \CustomizeMathJax{\newcommand{\LWRmathmakebox}[2][\{#2\}}
29 \CustomizeMathJax{\newcommand{\mathmakebox}[1][\{LWRmathmakebox\}}
30 \CustomizeMathJax{\newcommand{\cramped}[2][\{#1#2\}}
31 \CustomizeMathJax{\newcommand{\crampedlLap}[2][\{#1#2\}}
32 \CustomizeMathJax{\newcommand{\crampedrLap}[2][\{#1#2\}}
33 \CustomizeMathJax{\newcommand{\crampedcLap}[2][\{#1#2\}}
34 \CustomizeMathJax{\newenvironment{crampedsubarray}[1]{\{}}
35 \CustomizeMathJax{\newcommand{\crampedsubstack}{}}

36 \CustomizeMathJax{\newcommand{\smashoperator}[2][\{#2\limits}}

37 \CustomizeMathJax{\newcommand{\adjustlimits}{}}

38 \CustomizeMathJax{\newcommand{\SwapAboveDisplaySkip}{}}
39
40 \CustomizeMathJax{\require{extpfeil}}
41 \CustomizeMathJax{\Newextarrow\xLefttrightarrow{10,10}{0x2194}}
42 \CustomizeMathJax{\Newextarrow\xLeftarrow{10,10}{0x21d0}}
43 \CustomizeMathJax{\Newextarrow\xhookrightarrow{10,10}{0x21a9}}
44 \CustomizeMathJax{\Newextarrow\xmapsto{10,10}{0x21a6}}
45 \CustomizeMathJax{\Newextarrow\xrightarrow{10,10}{0x21d2}}
46 \CustomizeMathJax{\Newextarrow\xLefttrightarrow{10,10}{0x21d4}}
47 \CustomizeMathJax{\Newextarrow\xhookrightarrow{10,10}{0x21aa}}
48 \CustomizeMathJax{\Newextarrow\xrightharpoondown{10,10}{0x21c1}}
49 \CustomizeMathJax{\Newextarrow\xleftharpoondown{10,10}{0x21bd}}
50 \CustomizeMathJax{\Newextarrow\xrightleftharpoons{10,10}{0x21cc}}
51 \CustomizeMathJax{\Newextarrow\xrightharpoonup{10,10}{0x21c0}}
52 \CustomizeMathJax{\Newextarrow\xleftharpoonup{10,10}{0x21bc}}
53 \CustomizeMathJax{\Newextarrow\xleftrightharpoons{10,10}{0x21cb}}
54
55 \CustomizeMathJax{\newcommand{\LWRdounderbracket}[3]{%
56 \mathinner{\underset{#3}{\underline{\llcorner{#1}\lrcorner}}}}%
57 }}
58 \CustomizeMathJax{\newcommand{\LWRunderbracket}[2][\{LWRdounderbracket{#2\}}
59 \CustomizeMathJax{\newcommand{\underbracket}[1][\{LWRunderbracket}}
60 \CustomizeMathJax{\newcommand{\LWRdooverbracket}[3]{%
61 \mathinner{\overset{#3}{\overline{\ulcorner{#1}\urcorner}}}}%
62 }}
63 \CustomizeMathJax{\newcommand{\LWRoverbracket}[2][\{LWRdooverbracket{#2\}}
64 \CustomizeMathJax{\newcommand{\overbracket}[1][\{LWRoverbracket}}
65
66 \CustomizeMathJax{\newcommand{\LaTeXunderbrace}[1]{\underbrace{#1}}}
67 \CustomizeMathJax{\newcommand{\LaTeXoverbrace}[1]{\overbrace{#1}}}
68
69 \CustomizeMathJax{\newenvironment{matrix*}[1][\{begin{matrix}\}\end{matrix}}
70 \CustomizeMathJax{\newenvironment{pmatrix*}[1][\{begin{pmatrix}\}\end{pmatrix}}
71 \CustomizeMathJax{\newenvironment{bmatrix*}[1][\{begin{bmatrix}\}\end{bmatrix}}

```

```

72 \CustomizeMathJax{\newenvironment{Bmatrix*}[1][\begin{Bmatrix}\end{Bmatrix}}
73 \CustomizeMathJax{\newenvironment{vmatrix*}[1][\begin{vmatrix}\end{vmatrix}}
74 \CustomizeMathJax{\newenvironment{Vmatrix*}[1][\begin{Vmatrix}\end{Vmatrix}}
75 \CustomizeMathJax{\newenvironment{smallmatrix*}[1][\begin{matrix}\end{matrix}}
76 \CustomizeMathJax{\newenvironment{psmallmatrix*}[1][\begin{pmatrix}\end{pmatrix}}
77 \CustomizeMathJax{\newenvironment{bsmallmatrix*}[1][\begin{bmatrix}\end{bmatrix}}
78 \CustomizeMathJax{\newenvironment{Bsmallmatrix*}[1][\begin{Bmatrix}\end{Bmatrix}}
79 \CustomizeMathJax{\newenvironment{vsmallmatrix*}[1][\begin{vmatrix}\end{vmatrix}}
80 \CustomizeMathJax{\newenvironment{Vsmallmatrix*}[1][\begin{Vmatrix}\end{Vmatrix}}
81 \CustomizeMathJax{\newenvironment{psmallmatrix}[1][\begin{pmatrix}\end{pmatrix}}
82 \CustomizeMathJax{\newenvironment{bsmallmatrix}[1][\begin{bmatrix}\end{bmatrix}}
83 \CustomizeMathJax{\newenvironment{Bsmallmatrix}[1][\begin{Bmatrix}\end{Bmatrix}}
84 \CustomizeMathJax{\newenvironment{vsmallmatrix}[1][\begin{vmatrix}\end{vmatrix}}
85 \CustomizeMathJax{\newenvironment{Vsmallmatrix}[1][\begin{Vmatrix}\end{Vmatrix}}
86
87
88 \CustomizeMathJax{\newcommand{\LWRmultlined}[1][\begin{multline*}}
89 \CustomizeMathJax{\newenvironment{multlined}[1][\LWRmultlined]{\end{multline*}}}
90
91 \CustomizeMathJax{\let\LWRorigshoveleft\shoveleft}
92 \CustomizeMathJax{\renewcommand{\shoveleft}[1][\LWRorigshoveleft}}
93 \CustomizeMathJax{\let\LWRorigshoveright\shoveright}
94 \CustomizeMathJax{\renewcommand{\shoveright}[1][\LWRorigshoveright}}
95
96 \CustomizeMathJax{\newenvironment{dcases}{\begin{cases}\end{cases}}
97 \CustomizeMathJax{\newenvironment{dcases*}{\begin{cases}\end{cases}}
98 \CustomizeMathJax{\newenvironment{rcases}{\begin{cases}\end{cases}}
99 \CustomizeMathJax{\newenvironment{rcases*}{\begin{cases}\end{cases}}
100 \CustomizeMathJax{\newenvironment{drcases}{\begin{cases}\end{cases}}
101 \CustomizeMathJax{\newenvironment{drcases*}{\begin{cases}\end{cases}}
102 \CustomizeMathJax{\newenvironment{cases*}{\begin{cases}\end{cases}}
103
104 \CustomizeMathJax{\newcommand{\MoveEqLeft}[1][{}]}
105
106 \CustomizeMathJax{% special parsing to handle '&' in argument
107 \def\LWRAboxed#1!|!{\fbox{\(#1\)}&\fbox{\(#2\)}}
108 \newcommand{\Aboxed}[1]{\LWRAboxed#1&&!|!}
109 }

110 \CustomizeMathJax{
111 \newcommand{\LWRABLines}[1][\Updownarrow]{#1 \notag \\\}% star/nostar the same
112 \newcommand{\ArrowBetweenLines}{\ifstar\LWRABLines\LWRABLines}
113 }

114 \CustomizeMathJax{\newcommand{\shortintertext}[1]{\text{#1}\notag \\\}}
115
116 \CustomizeMathJax{\newcommand{\vdotswithin}[1]{\hspace{.5em}\vdots}}

117 \CustomizeMathJax{\newcommand{\LWRshortvdotswithinstar}[1]{\vdots \hspace{.5em} & \\\}}
118 \CustomizeMathJax{\newcommand{\LWRshortvdotswithinnostar}[1]{& \hspace{.5em}\vdots \\\}}
119 \CustomizeMathJax{%
120 \newcommand{\shortvdotswithin}%
121 {\ifstar\LWRshortvdotswithinstar\LWRshortvdotswithinnostar}%
122 }

```

```

123
124 \CustomizeMathJax{\newcommand{\MTFlushSpaceAbove}{}}
125 \CustomizeMathJax{\newcommand{\MTFlushSpaceBelow}{\}}
126
127 \LetLtxMacro\LWR@mathtools@orig@DeclarePairedDelimiter\DeclarePairedDelimiter
128 \renewcommand{\DeclarePairedDelimiter}[3]{
129 \LWR@mathtools@orig@DeclarePairedDelimiter{#1}{#2}{#3}
130 % starred:
131 \appto\LWR@customizedMathJax{\LWRbackslash{}}
132 \appto\LWR@customizedMathJax{%
133 \LWRbackslash{}}newcommand{\LWRbackslash\macrotocname{#1}LWRsubstar\}%
134 }%
135 \appto\LWR@customizedMathJax{[2][]}%
136 \appto\LWR@customizedMathJax{\{\}%
137 \LWR@subcustomizedmathjax{##1\left##2##1\right##3}%
138 \appto\LWR@customizedMathJax{\}\}%
139 \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
140 % not starred:
141 \appto\LWR@customizedMathJax{\LWRbackslash{}}
142 \appto\LWR@customizedMathJax{%
143 \LWRbackslash{}}newcommand{\LWRbackslash\macrotocname{#1}LWRsubnostar\}%
144 }%
145 \appto\LWR@customizedMathJax{[2][]}%
146 \appto\LWR@customizedMathJax{\{\}%
147 \LWR@subcustomizedmathjax{##1##2##1##3}%
148 \appto\LWR@customizedMathJax{\}\}%
149 \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
150 % user macro:
151 \appto\LWR@customizedMathJax{\LWRbackslash{}}
152 \appto\LWR@customizedMathJax{%
153 \LWRbackslash{}}newcommand{\LWRbackslash\macrotocname{#1}\}%
154 {\LWRbackslash{}}ifstar%
155 \LWRbackslash\macrotocname{#1}LWRsubstar%
156 \LWRbackslash\macrotocname{#1}LWRsubnostar%
157 \}%
158 }%
159 \appto\LWR@customizedMathJax{\LWRbackslash)\par}%
160 }
161 \@onlypreamble\DeclarePairedDelimiter
162
163 % (DeclarePairedDelimiterX is already defined to use \DeclarePairedDelimiterXPP.)
164
165 \LetLtxMacro\LWR@mathtools@orig@DeclarePairedDelimiterXPP\DeclarePairedDelimiterXPP
166 \DeclareDocumentCommand{\DeclarePairedDelimiterXPP}{m O{1} m m m m m}{
167 \LWR@mathtools@orig@DeclarePairedDelimiterXPP{#1}[#2][#3][#4][#5][#6][#7]
168 % subsubstar, second opt arg
169 \appto\LWR@customizedMathJax{\LWRbackslash{}}%
170 \appto\LWR@customizedMathJax{%
171 \LWRbackslash{}}newcommand{\LWRbackslash\macrotocname{#1}LWRsubsubstar\}%
172 }%
173 \appto\LWR@customizedMathJax{[#2]}%
174 \appto\LWR@customizedMathJax{\{\LWRbackslash{}}left}%
175 \LWR@subcustomizedmathjax{##3##4##7}%
176 \appto\LWR@customizedMathJax{\LWRbackslash{}}right}%
177 \LWR@subcustomizedmathjax{##5##6}%

```

```

178 \appto\LWR@customizedMathJax{\}\}%
179 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
180 % substar, first opt arg
181 \appto\LWR@customizedMathJax{\LWRbackslash}%
182 \appto\LWR@customizedMathJax{%
183 \LWRbackslash{}newcommand{\LWRbackslash\macroto{name}{#1}LWRsubstar\}[1][1]%
184 }%
185 \appto\LWR@customizedMathJax{%
186 \{
187 \LWRbackslash{}def\LWRbackslash{}delimsizel{\#1\}
188 \LWRbackslash\macroto{name}{#1}LWRsubsubstar
189 \}%
190 }%
191 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
192 % subsubnostar, second opt arg
193 \appto\LWR@customizedMathJax{\LWRbackslash}%
194 \appto\LWR@customizedMathJax{%
195 \LWRbackslash{}newcommand{\LWRbackslash\macroto{name}{#1}LWRsubsubnostar\}%
196 }%
197 \appto\LWR@customizedMathJax{[#2]}%
198 \appto\LWR@customizedMathJax{\{\LWRbackslash{}delimsizel}%
199 \LWR@subcustomizedmathjax{#3#4#7}%
200 \appto\LWR@customizedMathJax{\LWRbackslash{}delimsizel}%
201 \LWR@subcustomizedmathjax{#5#6}%
202 \appto\LWR@customizedMathJax{\}\}%
203 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
204 % substar, first opt arg
205 \appto\LWR@customizedMathJax{\LWRbackslash}%
206 \appto\LWR@customizedMathJax{%
207 \LWRbackslash{}newcommand{\LWRbackslash\macroto{name}{#1}LWRsubnostar\}[1][1]%
208 }%
209 \appto\LWR@customizedMathJax{%
210 \{
211 \LWRbackslash{}def\LWRbackslash{}delimsizel{\#1\}
212 \LWRbackslash\macroto{name}{#1}LWRsubsubnostar
213 \}%
214 }%
215 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
216 % user macro:
217 \appto\LWR@customizedMathJax{\LWRbackslash}%
218 \appto\LWR@customizedMathJax{%
219 \LWRbackslash{}newcommand{\%
220 \LWRbackslash{}macroto{name}{#1}%
221 \}%
222 \{\LWRbackslash{}ifstar%
223 \LWRbackslash{}macroto{name}{#1}LWRsubstar%
224 \LWRbackslash{}macroto{name}{#1}LWRsubnostar%
225 \}%
226 }%
227 \appto\LWR@customizedMathJax{\LWRbackslash}\par}%
228 }
229 \@onlypreamble\DeclareParedDelimiterXPP
230 \@onlypreamble\DeclareParedDelimiterX
231
232 \CustomizeMathJax{\newcommand\lparen{}}

```

```

233 \CustomizeMathJax{\newcommand\rparen{}}
234 \CustomizeMathJax{\newcommand{\ordinarycolon}{:}}

235 \CustomizeMathJax{\newcommand{\vcentcolon}{\mathrel{\unicode{x2236}}}}
236
237 \CustomizeMathJax{\newcommand\dblcolon{\mathrel{\unicode{x2237}}}}
238 \CustomizeMathJax{\newcommand\coloneqq{\mathrel{\unicode{x2236}\! =}}}
239 \CustomizeMathJax{\newcommand\Coloneqq{\mathrel{\unicode{x2237}\! =}}}
240 \CustomizeMathJax{\newcommand\coloneq{\mathrel{\unicode{x2236}-}}}
241 \CustomizeMathJax{\newcommand\Coloneq{\mathrel{\unicode{x2237}-}}}
242
243 \CustomizeMathJax{\newcommand\eqqcolon{\mathrel{=!\unicode{x2236}}}}
244 \CustomizeMathJax{\newcommand\Eqqcolon{\mathrel{=!\unicode{x2237}}}}
245 \CustomizeMathJax{\newcommand\eqcolon{\mathrel{-\unicode{x2236}}}}
246 \CustomizeMathJax{\newcommand\Eqcolon{\mathrel{-\unicode{x2237}}}}
247
248 \CustomizeMathJax{\newcommand\colonapprox{\mathrel{\unicode{x2236}\! \approx}}}
249 \CustomizeMathJax{\newcommand\Colonapprox{\mathrel{\unicode{x2237}\! \approx}}}
250 \CustomizeMathJax{\newcommand\colonsim{\mathrel{\unicode{x2236}\! \sim}}}
251 \CustomizeMathJax{\newcommand\Colonsim{\mathrel{\unicode{x2237}\! \sim}}}
252

253 \CustomizeMathJax{\newcommand{\nuparrow}{\mathrel{\cancel{\uparrow}}}}
254 \CustomizeMathJax{\newcommand{\ndownarrow}{\mathrel{\cancel{\downarrow}}}}
255 \CustomizeMathJax{\newcommand{\bigtimes}{\mathop{\Large\times}\limits}}
256
257 \CustomizeMathJax{\newcommand{\prescript}[3]{{}^{\#1}_{\#2}\#3}}
258
259
260 \CustomizeMathJax{\newenvironment{lgathered}{\begin{gathered}}{\end{gathered}}}
261 \CustomizeMathJax{\newenvironment{rgathered}{\begin{gathered}}{\end{gathered}}}
262
263 \LetLtxMacro\LWR@mathtools@orig@newgathered\newgathered
264 \renewcommand{\newgathered}[4]{%
265 \LWR@mathtools@orig@newgathered{\#1}{\#2}{\#3}{\#4}%
266 \appto\LWR@customizedMathJax{\LWRbackslash}%
267 \LWR@subcustomizedmathjax{%
268 \newenvironment{\#1}{\begin{gathered}}{\end{gathered}}%
269 }%
270 \appto\LWR@customizedMathJax{\LWRbackslash}%
271 }
272 \@onlypreamble\newgathered
273
274 \CustomizeMathJax{\newcommand{\splitfrac}[2]{{}^{\#1}_{\#2}}}
275 \CustomizeMathJax{\let\splitfrac\splitfrac}
276 \end{warpMathJax}

```

---

File 273 **lwarp-mcaption.sty**

§ 379 Package **mcaption**

(Emulates or patches code by STEPHAN HENNIG.)

Pkg mcaption mcaption is ignored.

**for HTML output:** Discard all options for lwarp-mcaption:

```
1 \LWR@ProvidesPackageDrop{mcaption}[2009/03/13]
2 \newenvironment{margincap}{}{}
3 \newcommand*{\margincapalign}{}
4 \newlength{\margincapsep}
```

---

File 274 **lwarp-mdframed.sty**

§ 380 Package **mdframed**

*(Emulates or patches code by MARCO DANIEL, ELKE SCHUBERT.)*

Pkg mdframed mdframed is loaded with options forced to framemethod=none.

### § 380.1 Limitations

**support** Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

 **loading** When used, lwarp loads mdframed in HTML with framemethod=none.

**font** For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support `\bfseries` and friends, only one font selection may be made at a time.

**theoremtitlefont** theoremtitlefont is not supported, since the following text is not in braces in the mdframed source.

**ignored options** userdefinedwidth and align are currently ignored.

**css classes** Environments created or encapsulated by mdframed are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class `|mdframedtitle|`. Subtitles are in a `<div>` of class `|mdframedsubtitle|`, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

## § 380.2 Package loading

**for HTML output:**

```

1 \RequirePackage{xcolor}% for \convertcolorspec
2
3 \LWR@ProvidesPackageDrop{mdframed}[2013/07/01]
```

Do not require Tikz or pstricks:

```
4 \LWR@origRequirePackage[framemethod=none]{mdframed}
```

## § 380.3 Patches

Patch to remove PDF formatting and add HTML tags:

```

5 \AtBeginDocument{
6 \def\mdf@trivlist#1{%
7 \edef\mdf@temp{%
8 % \topsep=\the\topsep\relax%
9 % \partopsep=\the\partopsep\relax%
10 % \parsep=\the\parsep\relax%
11 }%
12 % \setlength{\topsep}{#1}%
13 % \topskip\z@%
14 % \partopsep\z@%
15 % \parsep\z@%
16 % \@mbrlistfalse%
17 % \@trivlist%
18 % \labelwidth\z@%
19 % \leftmargin\z@%
20 % \itemindent\z@%
21 \let\itemlabel\@empty%
22 \def\makelabel##1{##1}%
23 % \item\relax\mdf@temp\relax%
24 }
25
26 \renewcommand*{\endmdf@trivlist}{%
27 \LWR@traceinfo{endmdf@trivlist}%
28 % \endtrivlist%
29 \LWR@listend%
30 }
31 }% AtBeginDocument
```

## § 380.4 Initial setup

To handle css and paragraphs, patch code at start and end of environment and contents. `\LWR@print@raggedright` helps avoid hyphenation.

```

32 \mdfsetup{
33 startcode={\LWR@mdframedstart\LWR@print@raggedright},
34 endcode={\LWR@mdframedend},
35 startinnercode={\LWR@startpars\LWR@print@raggedright},
36 endinnercode={\LWR@stoppars},
37 }
```

### § 380.5 **Color and length HTML conversion**

`\LWR@mdfprintcolor`    `{\mdfcolorkey}`  
 Given the `mdframed` key, print the color.

```
38 \newcommand*\LWR@mdfprintcolor[1]{%
39 \convertcolorspec{named}{\@nameuse{mdf@#1}}{HTML}\LWR@tempcolor%
40 \LWR@origpound\LWR@tempcolor
41 }
```

`\LWR@mdfprintlength`    `{\mdflengthkey}`  
 Given the `mdframed` key, print the length.

```
42 \newcommand*\LWR@mdfprintlength[1]{%
43 \LWR@forceminwidth{\@nameuse{mdf@#1@length}}%
44 \LWR@printlength{\LWR@atleastonept}%
45 }
```

### § 380.6 **Environment encapsulation**

`\LWR@mdframedstart`    Actions before an `mdframe` starts.  
 Encapsulate a frame inside a `<div>` of the desired `class`.

```
46 \newcommand*\LWR@mdframedstart{%
47 \LWR@traceinfo{\LWR@mdframedstart start}%
```

Warn if starting a frame inside a `<span>`:

```
48 \LWR@spanwarninvalid{mdframe}%
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
49 \LWR@stoppars%
```

Open a `<div>` and with custom `class` and custom `style`. A `BlockClass` environment is not used because this `<div>` is created by the `mdframed` startcode and encode settings, which do not properly nest the `<div>` inside the `mdframed` environment.

```
50 \LWR@htmltagc{div class="%
51 mdframed%
52 \ifdefstring{\LWR@mdthisenv}{mdframed}}{\LWR@mdthisenv}%
53 " \LWR@orignewline
54 style=" \LWR@orignewline
```

Convert and print the background color:

```
55 background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
56 border: \LWR@mdfprintlength{linewidth} solid
57 \LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
58 border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
59 \ifbool{mdf@shadow}{%
60 box-shadow:
```

```

61 \LWR@mdfprintlength{shadowsize}
62 \LWR@mdfprintlength{shadowsize}
63 \LWR@mdfprintlength{shadowsize}
64 \LWR@mdfprintcolor{shadowcolor} ;
65 }
66 {box-shadow: none ;}
67 \LWR@orignewline

68 "}
69 % \LWR@htmldivclass{\LWR@mdthisenv}

```

mdframed environment may not work with the HTML versions of the following, so restore them to their originals while inside mdframed:

```

70 \LWR@select@print@hspace%
71 \renewcommand*{\rule}{\LWR@print@rule}
72 \LetLtxMacro\makebox\LWR@print@makebox%

73 \LWR@startpars%
74 \LWR@traceinfo{LWR@mdframedstart done}%
75 }

```

\LWR@mdframedend    Actions after an mdframe ends.

After closing the <div>, globally restore to the default environment type:

```

76 \newcommand*{\LWR@mdframedend}{
77 \LWR@traceinfo{LWR@mdframedend start}%

```

Close the custom <div>:

```

78 \LWR@htmldivclassend{\LWR@mdthisenv}

```

Reset future custom class to the default:

```

79 \gdef\LWR@mdthisenv{mdframed}

```

Resume paragraph handling:

```

80 \LWR@startpars%
81 \LWR@traceinfo{LWR@mdframedend done}%
82 }

```

### § 380.7 Mdfamed environment

```

83 \renewenvironment{mdframed}[1][]{%
84 \color@begingroup%
85 \mdfsetup{userdefinedwidth=\linewidth,#1}%
86 \mdf@startcode%
87 \mdf@preenvsetting%
88 \ifdefempty{\mdf@firstframetitle}{}%
89 {\let\mdf@frametitlesave\mdf@frametitle%
90 \let\mdf@frametitle\mdf@firstframetitle%
91 }%
92 \ifvmode\nointerlineskip\fi%
93 \ifdefempty{\mdf@frametitle}{}%
94 {\mdfframedtitleenv{\mdf@frametitle}%
95 \mdf@@frametitle@use%
96 }%
97 \mdf@trivlist{\mdf@skipabove@length}%%

```

```

98 \mdf@settings%
99 % \mdf@lrbox{\mdf@splitbox@one}%
100 % \mdf@startinnercode%
101 }%
102 {%
103 % \mdf@@ignorelastdescenders%
104 \par%
105 % \unskip\ifvmode\nointerlineskip\hrule \@height\z@ \@width\hsize\fi%
106 \ifmdf@footnoteinside%
107 \def\mdf@reserveda{%
108 \mdf@footnoteoutput%
109 % \mdf@endinnercode%
110 % \endmdf@lrbox%
111 % \ifdefempty{\mdf@frametitle}{}%
112 % {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
113 % \detected@mdf@put@frame
114 }%
115 \else%
116 \def\mdf@reserveda{%
117 % \mdf@endinnercode%
118 % \endmdf@lrbox%
119 % \ifdefempty{\mdf@frametitle}{}%
120 % {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
121 % \detected@mdf@put@frame
122 \mdf@footnoteoutput%
123 }%
124 \fi%
125 \mdf@reserveda%
126 \aftergroup\endmdf@trivlist%
127 \color@endgroup%
128 \mdf@endcode%
129 }

```

\mdf@footnoteoutput

```

130 \renewrobustcmd*\mdf@footnoteoutput{%
131 \LWR@printpendingmpfootnotes%
132 }

```

## § 380.8 Titles and subtitles

\mdfframedtitleenv *{<title>}*

Place the title inside a <div> of class mdfframedtitle:

```

133 \newlength{\LWR@titleroundcorner}
134
135 \renewrobustcmd\mdfframedtitleenv[1]{%
136 \LWR@traceinfo{\LWR@mdfframedtitleenv start}%

```

Open a <div> with a custom class and custom style:

```

137 \begin{BlockClass}[%

```

Convert and print the title background color:

```

138 background:
139 \LWR@mdfprintcolor{frametitlebackgroundcolor}

```

```
140 ; \LWR@orignewline
```

Convert and print the title rule:

```
141 \ifbool{mdf@frametitlerule}{%
142 border-bottom:
143 \LWR@mdfprintlength{frametitlerulewidth}
144 solid
145 \LWR@mdfprintcolor{frametitlerulecolor}
146 ; \LWR@orignewline
147 }{ }%
```

Finish the custom style and the opening <div> tag:

```
148]{mdframedtitle}%
```

Print the title inside the <div>:

```
149 \mdf@frametitlefont{\LWR@textcurrentfont{#1}}%
```

Close the <div>:

```
150 \end{BlockClass}%
151 \LWR@traceinfo{\LWR@mdframedtitleenv end}%
152 }
```

```
\LWR@mdfsubtitlecommon {<sub — or — subsub>} [<options>] {<title>}
```

Common code for \LWR@mdfsubtitle and \LWR@mdfsubsubtitle.

Encapsulate the subtitle inside a <div> of class mdframedsubtitle:

```
153 \NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}
154 {% the following empty line is required
155
156 \LWR@traceinfo{\LWR@mdframedsubtitlecommon start}%
```

Open a <div> with a custom class and custom style:

```
157 \begin{BlockClass}[%
```

Convert and print the background color:

```
158 background:
159 \LWR@mdfprintcolor{#1titlebackgroundcolor}
160 ; \LWR@orignewline
```

Convert and print the above line:

```
161 \ifbool{mdf@#1titleaboveline}{%
162 border-top:
163 \LWR@mdfprintlength{#1titleabovelinewidth}
164 solid
165 \LWR@mdfprintcolor{#1titleabovelinecolor}
166 ; \LWR@orignewline
167 }{ }%
```

Convert and print the below line:

```
168 \ifbool{mdf@#1titlebelowline}{%
169 border-bottom:
170 \LWR@mdfprintlength{#1titlebelowlinewidth}
171 solid
```

```

172 \LWR@mdfprintcolor{#1titlebelowlinecolor}
173 ; \LWR@orignewline
174 }{}%

```

Finish the custom style and the opening <div> tag:

```
175]{mdframed#1title}%
```

Perform the original subtitle action:

```

176 \IfNoValueTF{#2}
177 {\@nameuse{LWR@origmdf#1title}\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}%
178 {\@nameuse{LWR@origmdf#1title}[#2]\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}%

```

Close the <div>:

```

179 \end{BlockClass}%
180 \LWR@traceinfo{LWR@mdframedsubtitlecommon end}%
181 }

```

`\LWR@mdfsubtitle` [*<options>*] {*<title>*}

```

182 \newcommand*\LWR@mdfsubtitle{%
183 \LWR@mdfsubtitlecommon{sub}%
184 }
185 \let\mdfsubtitle\LWR@mdfsubtitle

```

`\LWR@mdfsubsubtitle` [*<options>*] {*<title>*}

```

186 \newcommand*\LWR@mdfsubsubtitle{%
187 \LWR@mdfsubtitlecommon{subsub}%
188 }
189 \let\mdfsubsubtitle\LWR@mdfsubsubtitle

```

### § 380.9 **New environments**

`\LWR@mdthisenv` Stores the environment of the frame about to be created:

```
190 \newcommand*\LWR@mdthisenv{mdframed}
```

`\newmdenv` [*<options>*] {*<env-name>*}

Modified from the original to remember the environment.

```

191 \renewrobustcmd*\newmdenv[2][]{%
192 \newenvironment{#2}%
193 {%
194 \mdfsetup{#1}%
195 \renewcommand*\LWR@mdthisenv}{md#2}%
196 \begin{mdframed}%
197 }
198 {\end{mdframed}}%
199 }

```

`\surroundwithmdframed` [*<options>*] {*<environment>*}

Modified from the original to remember the environment.

```
200 \renewrobustcmd*\surroundwithmdframed[2][]{%
```

```

201 \BeforeBeginEnvironment{#2}{%
202 \renewcommand*{\LWR@mdthisenv}{md#2}%
203 \begin{mdframed}[#1]}%
204 \AfterEndEnvironment{#2}{\end{mdframed}}%
205 }

```

`\mdtheorem` [*(<mdframed-options>)*] [*(<envname>)*] [*(<numberedlike>)*] [*(<caption>)*] [*(<within>)*]  
 Modified from the original to remember the environment.

```

206 \DeclareDocumentCommand{\mdtheorem}{ O{ } m o m o }%
207 { \ifcsdef{#2}%
208 { \mdf@PackageWarning{Environment #2 already exists\MessageBreak}}%
209 {%
210 \IfNoValueTF {#3}%
211 {%#3 not given -- number relationship
212 \IfNoValueTF {#5}%
213 {%#3+#5 not given
214 \@definecounter{#2}%
215 \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
216 \newenvironment{#2}[1][{%
217 \refstepcounter{#2}%
218 \ifstrempy{##1}%
219 {\let\@temptitle\relax}%
220 {%
221 \def\@temptitle{\mdf@theoremseparator%
222 \mdf@theoremspace%
223 \mdf@theoremtitlefont%
224 \LWR@textcurrentfont{##1}}% lwarp
225 \mdf@thm@caption{#2}{#4}{\csname the#2\endcsname}{##1}}%
226 }%
227 \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
228 \@temptitle}]]%
229 {\end{mdframed}}%
230 \newenvironment{#2*}[1][{%
231 \ifstrempy{##1}{\let\@temptitle\relax}{\def\@temptitle{: \ ##1}}%
232 \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]]%
233 {\end{mdframed}}%
234 }%
235 {%#5 given -- reset counter
236 \@definecounter{#2}\@newctr{#2}[#5]%
237 \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
238 \expandafter\xdef\csname the#2\endcsname{%
239 \expandafter\noexpand\csname the#5\endcsname \@thmcountersep%
240 \@thmcounter{#2}}%
241 \newenvironment{#2}[1][{%
242 \refstepcounter{#2}%
243 \ifstrempy{##1}%
244 {\let\@temptitle\relax}%
245 {%
246 \def\@temptitle{\mdf@theoremseparator%
247 \mdf@theoremspace%
248 \mdf@theoremtitlefont%
249 \LWR@textcurrentfont{##1}}% lwarp
250 \mdf@thm@caption{#2}{#4}{\csname the#2\endcsname}{##1}}%
251 }

```

```

252 \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
253 \@temptitle}]]%
254 {\end{mdframed}}%
255 \newenvironment{#2*}[1][]{%
256 \ifstrempy{##1}%
257 {\let\@temptitle\relax}%
258 {%
259 \def\@temptitle{\mdf@theoremseparator%
260 \mdf@theoremspace%
261 \mdf@theoremtitlefont%
262 \LWR@textcurrentfont{##1}}% lwarp
263 \mdf@thm@caption{#2}{#4}{\csname the#2\endcsname}{##1}}%
264 }%
265 \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]]%
266 {\end{mdframed}}%
267 }%
268 }%
269 {%#3 given -- number relationship
270 \global\@namedef{the#2}{\@nameuse{the#3}}%
271 \newenvironment{#2}[1][]{%
272 \refstepcounter{#3}%
273 \ifstrempy{##1}%
274 {\let\@temptitle\relax}%
275 {%
276 \def\@temptitle{\mdf@theoremseparator%
277 \mdf@theoremspace%
278 \mdf@theoremtitlefont%
279 \LWR@textcurrentfont{##1}}% lwarp
280 \mdf@thm@caption{#2}{#4}{\csname the#2\endcsname}{##1}}%
281 }
282 \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
283 \@temptitle}]]%
284 {\end{mdframed}}%
285 \newenvironment{#2*}[1][]{%
286 \ifstrempy{##1}{\let\@temptitle\relax}{\def\@temptitle{: \ ##1}}%
287 \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]]%
288 {\end{mdframed}}%
289 }%
290 \BeforeBeginEnvironment{#2}{\renewcommand*\LWR@mdthisenv}{md#2}}% lwarp
291 \BeforeBeginEnvironment{#2*}{\renewcommand*\LWR@mdthisenv}{md#2}}% lwarp
292 }%
293 }

```

`\newmdtheoremenv` [*<1: mdframed-options>*] [*<2: envname>*] [*<3: numberedlike>*] [*<4: caption>*] [*<5: within>*]

Modified from the original to remember the environment.

```

294 \DeclareDocumentCommand\newmdtheoremenv{O{} m o m o }{%
295 \ifbool{expr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }%
296 {\newtheorem{#2}{#4}}%
297 {%
298 \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}%
299 \IfValueT{#5}{\newtheorem{#2}{#4}[#5}}%
300 }%
301 \BeforeBeginEnvironment{#2}{%

```

```

302 \renewcommand*{\LWR@mdthisenv}{md#2}%
303 \begin{mdframed}[#1]}%
304 \AfterEndEnvironment{#2}{%
305 \end{mdframed}}%
306 }

```

File 275 **lwarp-media9.sty**

§ 381 Package **media9**

Pkg media9 **media9** is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addressource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YOUTUBE™ video, use an “embedded” URL with .../embed/... instead of .../v/...

 **& in a URL** Many special characters are converted to regular catcode 12 characters for use inside a URL. & is used in the flash variables fields, which are split with xparse \SplitList, which does not seem to work with a catcode 12 divider token, so & is not converted to

catcode 12, and will not work in a URL with media9. Using & in a URL in a flashvars field may also cause parsing problems with print output, as well.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{media9}[2019/02/21]
2 \LWR@origRequirePackage{lwarp-common-multimedia}
3
4 \RequirePackage{xkeyval}
```

\addmediapath {<path>}

Supported.

```
5 \newcommand*\LWR@medianine@path{}
6
7 \newcommand*\addmediapath}[1]{\appto\LWR@medianine@path{#{1}}}
```

The options and poster text are reused in several places.

```
8 \newcommand*\LWR@medianine@postertext{}
9 \newcommand*\LWR@medianine@options{}
```

Each adresource can generate a multimedia object.

```
10 \define@key{LWR@medianine}{adresource}{%
11 \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]
12 {\LWR@medianine@postertext}
13 {#1}
14 }
```

Each flashvars source can generate a multimedia object.

```
15 \newcommand*\LWR@medianine@flashvarsb}[1]{%
16 \IfBeginWith{#1}{source=}{%
17 \StrGobbleLeft{#1}{7}[\LWR@tempone]%
18 \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
19 {\LWR@medianine@postertext}%
20 {\LWR@tempone}%
21 }{)%
22 \IfBeginWith{#1}{src=}{%
23 \StrGobbleLeft{#1}{4}[\LWR@tempone]%
24 \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
25 {\LWR@medianine@postertext}%
26 {\LWR@tempone}%
27 }{)%
28 }
29
30 \NewDocumentCommand{\LWR@medianine@flashvars}{ >{\SplitList{&}} m }{%
31 \ProcessList {#1}{\LWR@medianine@flashvarsb}%
32 }
33
34 \define@key{LWR@medianine}{flashvars}{%
35 \LWR@medianine@flashvars{#1}%
36 }
```

```

\includemedia [⟨options⟩] {⟨poster text⟩} {⟨file or URL⟩}
37 \newcommand*\LWR@includemediab[3][[]]{%
38 \let\input@path\LWR@medianine@path%
39 \renewcommand*\LWR@medianine@options{#1}%
40 \renewcommand*\LWR@medianine@postertext{#2}%
41 \setkeys*LWR@medianine{#1}%
42 \IfBeginWith{#3}{http}{\LWR@multimedia[#1]{#2}{#3}}{%
43 \IfBeginWith{#3}{HTTP}{\LWR@multimedia[#1]{#2}{#3}}{%
44 \IfBeginWith{#3}{ftp}{\LWR@multimedia[#1]{#2}{#3}}{%
45 \IfBeginWith{#3}{FTP}{\LWR@multimedia[#1]{#2}{#3}}{%
46 }}}}%
47 \endgroup%
48 }
49
50 \newrobustcmd*\includemedia{%
51 \begingroup%
52 \LWR@linkmediacatcodes%
53 \LWR@includemediab%
54 }

```

```

\mediabutton [⟨options⟩] {⟨text⟩}
Ignored.
55 \newcommand*\mediabutton[2][[]]{

```

---

File 276 **lwarp-memhfixc.sty**

§ 382 Package **memhfixc**

Pkg memhfixc memhfixc is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{memhfixc}[2013/05/30]

---

File 277 **lwarp-menukeys.sty**

§ 383 Package **menukeys**

*(Emulates or patches code by TOBIAS WEH.)*

Pkg menukeys menukeys is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{menukeys}[2020/10/31]

Patch to use a `lateximage` whose `alt` text is the contents of this use of the macro. A hash on these contents allows the reuse of the image for each instance of the same contents.

```

2 \xpatchcmd{\tw@define@menu@macro}
3 {\@nameuse{tw@style@#4@pre}}
4 {%
5 \begin{lateximage}*\detokenize{##2}]%
6 \@nameuse{tw@style@#4@pre}%
7 }
8 {}
9 {\LWR@patcherror{menukeys}{tw@define@menu@macro}}
10
11 \xpatchcmd{\tw@define@menu@macro}
12 {\@nameuse{tw@style@#4@post}}
13 {%
14 \@nameuse{tw@style@#4@post}%
15 \end{lateximage}%
16 }
17 {}
18 {\LWR@patcherror{menukeys}{tw@define@menu@macro B}}

```

Patch the existing macros:

```

19 \renewmenumacro{\menu}[>]{menus}
20 \renewmenumacro{\directory}[/]{paths}
21 \renewmenumacro{\keys}[+]{roundedkeys}

```

---

File 278 **lwarp-metalogo.sty**

§ 384 Package **metalogo**

(Emulates or patches code by ANDREW GILBERT MOSCHOU.)

Pkg metalogo metalogo is used in print mode, and emulated in HTML.

**for HTML output:** 1 \LWR@ProvidesPackagePass{metalogo}[2010/05/29]

```

2 \newcommand*\LWR@HTML@setlogokern}[2]{}
3 \newcommand*\LWR@HTML@setlogodrop}[2][XeTeX]{}
4 \newcommand*\LWR@HTML@setLaTeXa}[1]{}
5 \newcommand*\LWR@HTML@setLaTeXee}[1]{}
6 \newcommand*\LWR@HTML@seteverylogo}[1]{}
7 \newcommand*\LWR@HTML@everyLogo}[1]{}
8
9 \LWR@formatted{setlogokern}
10 \LWR@formatted{setlogodrop}
11 \LWR@formatted{setLaTeXa}
12 \LWR@formatted{setLaTeXee}
13 \LWR@formatted{seteverylogo}
14 \LWR@formatted{everyLogo}

```

---

File 279 **lwarp-metalogox.sty**

§ 385 Package **metalogox**

(Emulates or patches code by BRIAN DUNN.)

Pkg metalogox metalogox is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{metalogox}[2019/01/20]

\AtBeginDocument, adjust the logo setting according to the font which is active at that moment.

```
2 \AtBeginDocument{
3 \let\LWR@metalogox@currentformatting\LWR@formatting
4 \renewcommand*\LWR@formatting>{print}%
5 \autoadjustlogos*
6 \let\LWR@formatting\LWR@metalogox@currentformatting
7 }
```

---

File 280 **lwarp-mhchem.sty**

§ 386 Package **mhchem**

(Emulates or patches code by MARTIN HENSEL.)

Pkg mhchem mhchem is patched for use by lwarp.

**without MATHJAX** Without MATHJAX, mhchem expressions are converted to svg math. Inline expressions use hashed filenames to allow reuse, and assume that any mhchem options are global.

**MATHJAX with mhchem extension** For MATHJAX, the mhchem extension is used if the mhchem expression is used inside a math expression:

$$\text{\ce{C6H5-CHO}}$$

To force the use of svg math for an expression which does not work with MATHJAX, place the expression between `\displaymathother` and `\displaymathnormal`:

```
\displaymathother
[\ce{ . . . }] . . . $ \ce { . . . } $
\displaymathnormal
```

not inside math

If *not* used inside a math expression, lwarp converts standalone mhchem expressions into svg math images.

 **nested math**

When producing HTML output without the MATHJAX mhchem extension, lwarp does not support the use of nested dollar signs in mhchem expressions.

For some examples from the mhchem manual, change as follows:

|                                             |       |
|---------------------------------------------|-------|
| $\text{\ce{NaOH(aq, \infty)}}$              | % old |
| $\text{\ce{NaOH(aq, \infty)}}$              | % new |
| $\text{\ce{Fe(CN)_{\frac{6}{2}}}}$          | % old |
| $\text{\ce{Fe(CN)_{\frac{6}{2}}}}$          | % new |
| $\text{\ce{NO_x}}$                          | % old |
| $\text{\ce{NO_x}}$                          | % new |
| $\text{\ce{NO_{x}}}$                        | % old |
| $\text{\ce{NO_{x}}}$                        | % new |
| $\text{\ce{\$cis\{-}[PtCl2(NH3)2]}}$        | % old |
| $\text{\ce{\mathit{cis}\{-}[PtCl2(NH3)2]}}$ | % new |

for HTML output: `1 \LWR@ProvidesPackagePass{mhchem}[2018/06/22]`

The original definition of `\ce`:

```
2 \LetLtxMacro\LWR@mhchem@origce\ce
```

The new definition, called from the new `\ce` after math shift is set. The starred `lateximage` uses a hashed filename for the `svg` image. The `alt` tag is set to the `mhchem` expression.

```
3 \newcommand{\LWR@mhchem@HTML@ce}[1]{%
4 \LWR@findcurrenttextcolor% sets \LWR@tempcolor
5 \ifbool{\LWR@xfakebold}%
6 {\def\LWR@tempone{Y}}%
7 {\def\LWR@tempone{N}}%
8 \begin{lateximage}*\[\textbackslash\}ce{\LWR@HTMLsanitize{#1}\}%
9 [%
10 FM\LWR@f@family%
11 SR\LWR@f@series%
12 SH\LWR@f@shape%
13 SHC\LWR@f@shapecaps%
14 CL\LWR@tempcolor%
15 FB\LWR@tempone% xfakebold
16]%
17 \LWR@setcurrentfont%
18 \LWR@mhchem@origce{#1}%
19 \end{lateximage}%
20 \endgroup%
21 \addtocounter{\LWR@mhchem@cedepth}{-1}%
22 }
```

Only set math shift if outer depth:

```
23 \newcounter{\LWR@mhchem@cedepth}
24 \setcounter{\LWR@mhchem@cedepth}{0}
```

The new `\ce`. Sets math shift then continues.

```

25 \renewcommand{\ce}{%
26 \begingroup%
27 \ifnumequal{\value{LWR@mhchem@cedepth}}{0}{%
28 \catcode'\$=3% math shift
29 }{}%
30 \addtocounter{LWR@mhchem@cedepth}{1}%
31 \LWR@mhchem@HTML@ce%
32 }

```

The original definition of `\cesplit`:

```

33 \LetLtxMacro\LWR@mhchem@origcesplit\cesplit

```

The new definition, called from the new `\cesplit` after math shift is set. The starred `lateximage` uses a hashed filename for the `svg` image. The `alt` tag is set to the `mhchem` expression.

```

34 \newcommand*{\LWR@mhchem@HTML@cesplit}[2]
35 {%
36 \LWR@findcurrenttextcolor% sets \LWR@tempcolor
37 \ifbool{LWR@xfakebold}%
38 {\def\LWR@tempone{Y}}%
39 {\def\LWR@tempone{N}}%
40 \begin{lateximage}*[\textbackslash{}cesplit\{\LWR@HTMLsanitize{#2}\}]*%
41 [%
42 FM\LWR@f@family%
43 SR\LWR@f@series%
44 SH\LWR@f@shape%
45 SHC\LWR@f@shapecaps%
46 CL\LWR@tempcolor%
47 FB\LWR@tempone% xfakebold
48]%
49 \LWR@setcurrentfont%
50 \LWR@mhchem@origcesplit{#1}{#2}%
51 \end{lateximage}%
52 \endgroup%
53 }

```

Only set math shift if outer depth:

```

54 \newcounter{LWR@mhchem@cesplitdepth}
55 \setcounter{LWR@mhchem@cesplitdepth}{0}

```

The new `\cesplit`. Sets math shift then continues.

```

56 \renewcommand{\cesplit}{%
57 \begingroup%
58 \ifnumequal{\value{LWR@mhchem@cesplitdepth}}{0}{%
59 \catcode'\$=3% math shift
60 }{}%
61 \addtocounter{LWR@mhchem@cesplitdepth}{1}%
62 \LWR@mhchem@HTML@cesplit%
63 }

```

Resore originals inside a lateximage:

```
64 \appto\LWR@restoreorigformatting{%
65 \LetLtxMacro\ce\LWR@mhchem@origce%
66 \LetLtxMacro\cesplit\LWR@mhchem@origcesplit%
67 }
68
69 \begin{warpMathJax}
70 \CustomizeMathJax{\require{mhchem}}
71 \end{warpMathJax}
```

---

File 281 **lwarp-microtype.sty**

§ 387 Package **microtype**

*(Emulates or patches code by R SCHLICHT.)*

Pkg microtype microtype is pre-loaded by lwarp. All user options and macros are ignored and disabled.

**for HTML output:** Discard all options for lwarp-microtype:

```
1 \LWR@ProvidesPackageDrop{microtype}[2018/01/14]

2 \DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m}{}
3 \DeclareDocumentCommand{\UseMicrotypeSet}{o m}{}
4 \DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m}{}
5 \DeclareDocumentCommand{\SetProtrusion}{o m m}{}
6 \DeclareDocumentCommand{\SetExpansion}{o m m}{}
7 \DeclareDocumentCommand{\SetTracking}{o m m}{}
8 \DeclareDocumentCommand{\SetExtraKerning}{o m m}{}
9 \DeclareDocumentCommand{\SetExtraSpacing}{o m m}{}
10 \DeclareDocumentCommand{\DisableLigatures}{o m}{}
11 \DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m}{}
12 \DeclareDocumentCommand{\DeclareMicrotypeVariants}{m}{}
13 \DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m}{}
14 \DeclareDocumentCommand{\LoadMicrotypeFile}{m}{}
15 \DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m}{}
16 \DeclareDocumentCommand{\microtypesetup}{m}{}
17 \DeclareDocumentCommand{\microtypecontext}{m}{}
18 \DeclareDocumentCommand{\textmicrotypecontext}{m m}{#2}
19 \ifpackageloaded{letterspace}{\let\MT@textls\relax}{%
20 \DeclareDocumentCommand{\lsstyle}{}{}}
21 \DeclareDocumentCommand{\textls}{o +m}{}
22 \DeclareDocumentCommand{\lslig}{m}{#1}
23 }
24 \def\DeclareMicrotypeSet#1#{\@gobbletwo}
25 \def\DeclareMicrotypeVariants#1#{\@gobble}
26 \@onlypreamble\DeclareMicrotypeSet
27 \@onlypreamble\UseMicrotypeSet
28 \@onlypreamble\DeclareMicrotypeSetDefault
29 \@onlypreamble\DisableLigatures
30 \@onlypreamble\DeclareMicrotypeVariants
```

---

```
31 \@onlypreamble\DeclareMicrotypeBabelHook
```

---

File 282 **lwarp-midfloat.sty**

§ 388 Package **midfloat**

*(Emulates or patches code by SIGITAS TOLUŠIS.)*

Pkg midfloat midfloat is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{midfloat}[2012/05/29]

```
2 \newenvironment{strip}[1][{}]{}
```

```
3 \newskip\stripsep
```

---

File 283 **lwarp-midpage.sty**

§ 389 Package **midpage**

Pkg midpage midpage is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{midpage}[2009/09/03]

```
2 \newenvironment{midpage}
```

```
3 {\begin{BlockClass}[%
```

```
4 \LWR@print@mbbox{margin-top:6ex} ; \LWR@print@mbbox{margin-bottom:6ex}%
```

```
5]{midpage}}
```

```
6 {\end{BlockClass}}
```

---

File 284 **lwarp-minibox.sty**

§ 390 Package **minibox**

*(Emulates or patches code by WILL ROBERTSON.)*

Pkg minibox minibox is patched for use by lwarp.

Due to HTML limitations regarding paragraphs and <div>s, miniboxes inline with other text will appear on their own line.

**for HTML output:** 1 \LWR@ProvidesPackagePass{minibox}[2013/06/21]

```
2 \ExplSyntaxOn
```

```
3 \newcommand\LWR@HTML@minibox[2][{}]{%
```

```
4 \LWR@stoppars%
```

```
5 \group_begin:
```

```

6 \keys_set:nn {minibox} {#1}
7 \bool_if:NTF \l_minibox_frame_bool
8 {
9 \setlength\fbboxrule{\l_minibox_rule_dim}
10 \setlength\fbboxsep{\l_minibox_pad_dim}
11 \fbboxBlock{%
12 \begin{tabular}[\l_minibox_tabular_valign_tl]%
13 {\l_minibox_tabular_preamble_tl}
14 {#2}
15 \end{tabular}
16 }%
17 }
18 {
19 \begin{BlockClass}[display:inline-block]{minibox}
20 \begin{tabular}[\l_minibox_tabular_valign_tl]%
21 {\l_minibox_tabular_preamble_tl}
22 {#2}
23 \end{tabular}
24 \end{BlockClass}
25 }
26 \group_end:
27 \LWR@startpars%
28 }
29 \ExplSyntaxOff
30
31 \LWR@formatted{minibox}

```

---

File 285 **lwarp-minitoc.sty**

§ 391 Package **minitoc**

Pkg minitoc minitoc is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{minitoc}[2018/07/12]

mtcoff disables minitoc.

2 \usepackage{mtcoff}

---

File 286 **lwarp-minted.sty**

§ 392 Package **minted**

(Emulates or patches code by GEOFFREY M. POORE.)

Pkg minted minted is patched for use by lwarp.

 **limitations** mathescape and highlightlines don't work. Line numbers on the right will not be aligned. Due to *pdftotext*, extra spaces may appear in broken lines if other formatting is included.

```

for HTML output: 1 \LWR@ProvidesPackagePass{minted}[2017/07/19]

2 \xpatchcmd{\minted}
3 {\setkeys{minted@opt@cmd}{#1}}
4 {%
5 \setkeys{minted@opt@cmd}{%
6 #1,%
7 mathescape=false,breaklines,texcomments=false,highlightlines={}%
8 }%
9 }
10 {}
11 {\LWR@patcherror{minted}{minted}}
12
13 \xpatchcmd{\mintinline}
14 {\setkeys{minted@opt@cmd}{#1}}
15 {\setkeys{minted@opt@cmd}{%
16 #1,%
17 mathescape=false,breaklines,texcomments=false,highlightlines={}%
18 }%
19 }
20 {}
21 {\LWR@patcherror{minted}{mintinline}}
22
23 \xpatchcmd{\mint}
24 {\setkeys{minted@opt@cmd}{#1}}
25 {%
26 \setkeys{minted@opt@cmd}{%
27 #1,%
28 mathescape=false,breaklines,texcomments=false,highlightlines={}%
29 }%
30 }
31 {}
32 {\LWR@patcherror{minted}{mint}}
33
34 \xpatchcmd{\inputminted}
35 {\setkeys{minted@opt@cmd}{#1}}
36 {\setkeys{minted@opt@cmd}{%
37 #1,%
38 mathescape=false,breaklines,texcomments=false,highlightlines={}%
39 }%
40 }
41 {}
42 {\LWR@patcherror{minted}{inputminted}}

```

---

File 287 **lwarp-mismath.sty**

§ 393 Package **mismath**

(Emulates or patches code by ANTOINE MISSIER.)

Pkg mismath mismath is patched for SVG math, and emulated for MATHJAX.

△ MATHJAX \enumber, \inumber, \jnumber, and \pinumber are ignored for MATHJAX, except that

`\itpi` is made available as a clone of `\pi`.

For MATHJAX, `\boldvect` and `\arrowvect` are honored if in the preamble.

If `\boldvectcommand` is set to `\mathbf` in the preamble, it will be used for MATHJAX, otherwise it will default to `\mathit`. `\boldvectcommand` may also be set with `\CustomizeMathJax` in the preamble. See section 8.7.5. Note that as of this writing there is not a bold italic font across all MATHJAX fonts.

If `\probastyle` is set to `\mathbb` in the preamble, it will be used for MATHJAX, otherwise it will default to `\mathrm`. `\probastyle` may be set with `\CustomizeMathJax` in the preamble.

If `\mathset` is set to `\mathbb` in the preamble, it will be used for MATHJAX, otherwise it will default to `\mathbf`. `\mathset` may be set with `\CustomizeMathJax` in the preamble.

**for HTML output:** `1 \LWR@ProvidesPackagePass{mismath}[2019/12/27]`

For MATHJAX, used in the HTML comment before the environment.

```

2 \ifbool{mathjax}{
3 \RenewEnviron{mathcols}{%
4 \preto\BODY{\begin{aligned}\displaystyle}
5 \appto\BODY{\end{aligned}}
6 \expandafter\(\BODY\)
7 }
8 }% mathjax

```

For svg math. The `lateximage` restores the original definition of the `math` environment.

```

9 {% svg
10 \renewenvironment{mathcols}{
11 \begin{lateximage}
12 \begin{math}
13 \begin{aligned}\displaystyle
14 }{
15 \end{aligned}%
16 \end{math}
17 \end{lateximage}
18 }
19 }% svg
20
21 \renewcommand{\changepcol}{
22 \end{aligned} \quad
23 \begin{aligned}\displaystyle
24 }
25
26 \begin{warpMathJax}
27 \CustomizeMathJax{\newcommand{\mathup}[1]{\mathrm{#1}}}
28 \CustomizeMathJax{\newcommand{\e}{\mathrm{e}}}
29 \CustomizeMathJax{\newcommand{\i}{\mathrm{i}}}
30 \CustomizeMathJax{\newcommand{\j}{\mathrm{j}}}
31
32 \CustomizeMathJax{\newcommand{\boldvect}{}}
33 \CustomizeMathJax{\newcommand{\arrowvect}{}}

```

```
34 \CustomizeMathJax{\newcommand{\pinumber}[1][{}]}
35 \CustomizeMathJax{\newcommand{\hvect}[1]{\vec{\vphantom{h}#1}}}
36 \CustomizeMathJax{\newcommand{\hvec}[1]{\vec{\vphantom{t}#1}}}
37 \CustomizeMathJax{%
38 \newcommand{\norm}[1]{\left\| \left\| \left\| \left\| \right\| \right\| \right\| \right\|}
39 }
40 \CustomizeMathJax{\newcommand{\di}{\mathop{\!}\mathrm{d}}}
41
42 \CustomizeMathJax{\newcommand{\P}{\operatorname{\probastyle{P}}}}
43 \CustomizeMathJax{\newcommand{\E}{\operatorname{\probastyle{E}}}}
44 \CustomizeMathJax{\newcommand{\V}{\operatorname{\probastyle{V}}}}
45 \CustomizeMathJax{\newcommand{\Par}{\unicode{x00B6}}}
46
47 \CustomizeMathJax{\DeclareMathOperator{\adj}{adj}}
48 \CustomizeMathJax{\DeclareMathOperator{\Aut}{Aut}}
49 \CustomizeMathJax{\DeclareMathOperator{\Conv}{Conv}}
50 \CustomizeMathJax{\DeclareMathOperator{\cov}{cov}}
51 \CustomizeMathJax{\DeclareMathOperator{\Cov}{Cov}}
52 \CustomizeMathJax{\newcommand{\curl}{\operatorname{\vect{\mathrm{curl}}}}}
53 \CustomizeMathJax{\DeclareMathOperator{\divg}{div}}
54 \CustomizeMathJax{\DeclareMathOperator{\End}{End}}
55
56 \CustomizeMathJax{\DeclareMathOperator{\erf}{erf}}
57 \CustomizeMathJax{\newcommand{\grad}{\operatorname{\vect{\mathrm{grad}}}}}
58 \CustomizeMathJax{\DeclareMathOperator{\id}{id}}
59 \CustomizeMathJax{\DeclareMathOperator{\Id}{Id}}
60 \CustomizeMathJax{\DeclareMathOperator{\im}{im}}
61 \CustomizeMathJax{\let\oldIm\Im}
62 \CustomizeMathJax{\renewcommand{\Im}{\operatorname{Im}}}
63 \CustomizeMathJax{\DeclareMathOperator{\lb}{lb}}
64 \CustomizeMathJax{\DeclareMathOperator{\lcm}{lcm}}
65
66 \CustomizeMathJax{\DeclareMathOperator{\rank}{rank}}
67 \CustomizeMathJax{\let\oldRe\Re}
68 \CustomizeMathJax{\renewcommand{\Re}{\operatorname{Re}}}
69 \CustomizeMathJax{\newcommand{\rot}{\operatorname{\vect{\mathrm{rot}}}}}
70 \CustomizeMathJax{\DeclareMathOperator{\sgn}{sgn}}
71 \CustomizeMathJax{\DeclareMathOperator{\spa}{span}}
72 \CustomizeMathJax{\DeclareMathOperator{\tr}{tr}}
73 \CustomizeMathJax{\DeclareMathOperator{\Var}{Var}}
74 \CustomizeMathJax{\DeclareMathOperator{\Zu}{Z}}
75
76 \CustomizeMathJax{\DeclareMathOperator{\arccot}{arccot}}
77 \CustomizeMathJax{\DeclareMathOperator{\sech}{sech}}
78 \CustomizeMathJax{\DeclareMathOperator{\csch}{csch}}
79 \CustomizeMathJax{\DeclareMathOperator{\arsinh}{arsinh}}
80 \CustomizeMathJax{\DeclareMathOperator{\arcosh}{arcosh}}
81 \CustomizeMathJax{\DeclareMathOperator{\artanh}{artanh}}
82 \CustomizeMathJax{\DeclareMathOperator{\arcoth}{arcoth}}
83 \CustomizeMathJax{\DeclareMathOperator{\arsech}{arsech}}
84 \CustomizeMathJax{\DeclareMathOperator{\arcsch}{arcsch}}
85
86 \CustomizeMathJax{\DeclareMathOperator{\bigO}{\mathcal{O}}}
87 \CustomizeMathJax{\DeclareMathOperator{\bigo}{O}}
88 \CustomizeMathJax{\DeclareMathOperator{\lito}{o}}
```

```

89
90 \CustomizeMathJax{\newcommand{\R}{\mathset{R}}}
91 \CustomizeMathJax{\newcommand{\C}{\mathset{C}}}
92 \CustomizeMathJax{\newcommand{\N}{\mathset{N}}}
93 \CustomizeMathJax{\newcommand{\Z}{\mathset{Z}}}
94 \CustomizeMathJax{\newcommand{\Q}{\mathset{Q}}}
95 \CustomizeMathJax{\newcommand{\F}{\mathset{F}}}
96 \CustomizeMathJax{\newcommand{\K}{\mathset{K}}}
97
98 \CustomizeMathJax{\newcommand{\ds}{\displaystyle}}
99 \CustomizeMathJax{\newcommand{\dlim}{\lim\limits}}
100 \CustomizeMathJax{\newcommand{\dsum}{\sum\limits}}
101 \CustomizeMathJax{\newcommand{\dprod}{\prod\limits}}
102 \CustomizeMathJax{\newcommand{\dcup}{\bigcup\limits}}
103 \CustomizeMathJax{\newcommand{\dcap}{\bigcap\limits}}
104 \CustomizeMathJax{\newcommand{\lbar}{\overline}}
105 \CustomizeMathJax{\newcommand{\hlbar}[1]{\overline{\vphantom{h}#1}}}
106 \CustomizeMathJax{\newcommand{\eqdef}{\stackrel{\mathrm{def}}{=}}}
107 \CustomizeMathJax{\newcommand{\unbr}{\underbrace}}
108 \CustomizeMathJax{\newcommand{\iif}{if and only if }}
109
110 \CustomizeMathJax{\newcommand{\mul}{\mathord{\times}}}
111 \CustomizeMathJax{\newcommand{\then}{\ \Longrightarrow \ \mbox{ } }}
112 \CustomizeMathJax{\newcommand{\txt}[1]{\quad\text{#1}\quad}}
113 \CustomizeMathJax{\newcommand{\paren}[1]{\mathopen{\left(#1 \right)}}}
114 \CustomizeMathJax{\newcommand{\pow}[2]{\left(#1 \right)^{\!#2}}}
115 \CustomizeMathJax{\newcommand{\abs}[1]{\left| \! \left| #1 \right| \! \right|}}
116 \CustomizeMathJax{\newcommand{\lfrac}[2]{\frac{\!#1\!}{\!#2\!}}}
117
118 \CustomizeMathJax{\newenvironment{system}[1][l]{%
119 {\left\{\begin{array}{@{.15em}#1@{}}
120 {\end{array}\right.}
121 }
122
123 \CustomizeMathJax{\newenvironment{spmatrix}
124 {\left(\begin{smallmatrix}
125 {\end{smallmatrix}\right)}
126 }
127
128 \CustomizeMathJax{%
129 \newenvironment{mathcols}
130 {\begin{aligned}\displaystyle}
131 {\end{aligned}}
132 }
133 \CustomizeMathJax{\newcommand{\changepcol}{\end{aligned}\quad\begin{aligned}}}

```

User-adjustable settings, detected if in the preamble.

```

134 \AtBeginDocument{
135 \ifdef{\itpi}{
136 \CustomizeMathJax{\let\itpi\pi}
137 }{}
138 \ifdefstring{\boldvectcommand}{\mathbf}{
139 \CustomizeMathJax{\newcommand{\boldvectcommand}[1]{\mathbf{#1}}}
140 }{}

```

```

141 \CustomizeMathJax{\newcommand{\boldvectcommand}[1]{\boldsymbol{#1}}}
142 }
143 \ifbool{arrowvect}{
144 \CustomizeMathJax{\newcommand{\vect}[1]{\overrightarrow{#1}}}
145 }{
146 \CustomizeMathJax{\newcommand{\vect}[1]{\boldvectcommand{#1}}}
147 }
148 \ifdefstring{\probastyle}{\mathbb}{
149 \CustomizeMathJax{\newcommand{\mathbb}[1]{\mathbb{#1}}}
150 }{
151 \CustomizeMathJax{\newcommand{\mathbb}[1]{\mathrm{#1}}}
152 }
153 \ifdefstring{\mathset}{\mathbb}{
154 \CustomizeMathJax{\newcommand{\mathset}[1]{\mathbb{#1}}}
155 }{
156 \CustomizeMathJax{\newcommand{\mathset}[1]{\mathbf{#1}}}
157 }
158 }
159 \end{warpMathJax}

```

---

File 288 **lwarp-mleftright.sty**

§ 394 Package **mleftright**

*(Emulates or patches code by HEIKO OBERDIEK.)*

Pkg mleftright mleftright is used as-is, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{mleftright}[2019/12/03]

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\mleft}{\left}}
4 \CustomizeMathJax{\newcommand{\mright}{\right}}
5 \CustomizeMathJax{\newcommand{\mleftright}{}}
6 \CustomizeMathJax{\newcommand{\mleftrightrestore}{}}
7 \end{warpMathJax}

```

---

File 289 **lwarp-morefloats.sty**

§ 395 Package **morefloats**

Pkg morefloats morefloats is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{morefloats}[2015/07/22]

File 290 **lwarp-moreverb.sty**

§ 396 Package **moreverb**

*(Emulates or patches code by ROBIN FAIRBAIRNS.)*

Pkg moreverb **moreverb** is supported with some patches.

```

1 \LWR@ProvidesPackagePass{moreverb}[2008/06/03]

2 \BeforeBeginEnvironment{verbatimtab}{%
3 \LWR@forcenewpage
4 \LWR@atbeginverbatim{Verbatim}%
5 }
6 \AfterEndEnvironment{verbatimtab}{%
7 \LWR@afterendverbatim%
8 }
9
10
11 \LetLtxMacro\LWRMV@orig@verbatimtabinput\@verbatimtabinput
12
13 \renewcommand{\@verbatimtabinput}[2][]{%
14 \LWR@forcenewpage
15 \LWR@atbeginverbatim{Verbatim}%
16 \LWRMV@orig@verbatimtabinput[#1]{#2}%
17 \LWR@afterendverbatim%
18 }
19
20 \BeforeBeginEnvironment{listing}{%
21 \LWR@forcenewpage
22 \LWR@atbeginverbatim{programlisting}%
23 }
24
25 \AfterEndEnvironment{listing}{%
26 \LWR@afterendverbatim%
27 }
28
29 \BeforeBeginEnvironment{listingcont}{%
30 \LWR@forcenewpage
31 \LWR@atbeginverbatim{programlisting}%
32 }
33
34 \AfterEndEnvironment{listingcont}{%
35 \LWR@afterendverbatim%
36 }

37 \LetLtxMacro\LWRMV@listinginput\@listinginput
38
39 \renewcommand{\@listinginput}[3][]{
40 \LWR@forcenewpage
41 \LWR@atbeginverbatim{programlisting}%

```

```

42 \LWRMV@listinginput[#1]{#2}{#3}%
43 \LWR@afterendverbatim%
44 }
45
46
47 \renewenvironment*{boxedverbatim}
48 {
49 \LWR@forcenewpage
50 \LWR@atbeginverbatim{boxedverbatim}%
51 \verbatim%
52 }
53 {
54 \endverbatim%
55 \LWR@afterendverbatim%
56 }

```

---

File 291 **lwarp-movie15.sty**

§ 397 Package **movie15**

Pkg movie15 movie15 is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addressource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

`\hyperlinkmovie`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YOUTUBE™ video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{movie15}[2012/05/16]

2 \LWR@origRequirePackage{lwarp-common-multimedia}
3
4 \RequirePackage{xkeyval}
5
6 \newcommand*\LWR@moviefifteen@text{}
7
8 \define@key{LWR@moviefifteen}{text}{\renewcommand{\LWR@moviefifteen@text}{#1}}
9
10 \newcommand*\LWR@includemovie}[4][[]]{%
11 \renewcommand{\LWR@moviefifteen@text}{(multimedia)}
12 \setkeys*LWR@moviefifteen}{#1}%
13 \LWR@multimediab[#1,width=#2,height=#3]{\LWR@moviefifteen@text}{#4}%
14 }
15
16 \newrobustcmd*\includemovie}{%
17 \begingroup%
18 \LWR@linkmediacatcodes%
19 \LWR@includemovieb%
20 }
21
22
23 \newcommand*\movieref}[3][[]]{}
24
25 \LetLtxMacro\movie\LWR@multimedia
26 % \LetLtxMacro\sound\LWR@multimedia% not in media15
27
28 \newcommand{\hyperlinkmovie}[3][[]]{}

```

---

File 292 **lwarp-mparhack.sty**

§ 398 Package **mparhack**

Pkg mparhack mparhack is ignored.

**for HTML output:** Discard all options for lwarp-mparhack:

```

1 \LWR@ProvidesPackageDrop{mparhack}[2005/04/17]

```

---

File 293 **lwarp-multibib.sty**

§ 399 Package **multibib**

*(Emulates or patches code by THORSTEN HANSEN.)*

Pkg multibib multibib is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{multibib}[2008/12/10]

```
2 \xpatchcmd{\newcites}
3 {{{\@suffix}}}
4 {{{\@suffix_html}}}
5 {}
6 {\LWR@patcherror{multibib}{newcites}}
```

---

File 294 **lwarp-multicap.sty**

§ 400 Package **multicap**

Pkg multicap multicap is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{multicap}[2002/05/04]

```
2 \newcommand*{\mfcaption}{\captionof{figure}}
3 \newcommand*{\mtcaption}{\captionof{table}}
4 \newcounter{mcapsize}
5 \newcounter{mcapskip}
6 \newlength{\abvmcapskip}
7 \newlength{\blwmcapskip}
```

---

File 295 **lwarp-multicol.sty**

§ 401 Package **multicol**

*(Emulates or patches code by FRANK MITTELBACH.)*

Pkg multicol multicol is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{multicol}[2018/12/27]

Multicols are converted into a 1–3 column display, browser-supported.

The optional multicol heading is placed inside a <div> of class multicolshheading.

The content is placed inside a <div> of class multicol.

```
Env multicol * {<numcols>} [<heading>]
2 \NewDocumentEnvironment{multicol}{s m o}
```

HTML <div> class to contain everything:

```
3 {
4 \LWR@forcenewpage
5 \BlockClass{multicol}
```

Optional HTML <div> class for the heading:

```
6 \IfValueT{#3}{\begin{BlockClass}{multicolshheading}#3\end{BlockClass}}%
```

Change \linewidth to compensate for expected size:

```
7 \setlength{\linewidth}{\linewidth/#2}
```

Locally force any minipages to be fullwidth:

```
8 \booltrue{LWR@forceminipagefullwidth}
9 }
```

When done with the environment, close the <div>:

```
10 {\endBlockClass}
```

Emulated null functions which are not used in HTML:

```
11 \newcommand*{\columnbreak}{}
12 \newcommand*{\RLmulticolcolumns}{}
13 \newcommand*{\LRmulticolcolumns}{}
14
15 \newlength{\premulticol}
16 \newlength{\postmulticol}
17 \newlength{\multicolsep}
18 \newlength{\multicolbaselineskip}
19 \newlength{\multicoltolerance}
20 \newlength{\multicolpretolerance}
21 \newcommand*{\columnseprulecolor}{\normalcolor}
22 \newcounter{columnbadness}
23 \newcounter{finalcolumnbadness}
24 \newcounter{collectmore}
25 \newcounter{unbalance}
26 \newlength{\multicolovershoot}
27 \newlength{\multicolundershoot}

28 \NewDocumentCommand{\docolaction}{s o m m m}{%
29 \IfValueTF{#2}{#2}{#3}%
30 }
```

---

File 296 **lwarp-multicolrule.sty**

§ 402 Package **multicolrule**

Pkg multicolrule multicolrule is ignored.

**for HTML output:**

```

1 \RequirePackage{multicol}
2
3 \LWR@ProvidesPackageDrop{multicolrule}[2019/01/01]

4 \newcommand*{\SetMCRule}[1]{}
5 \NewDocumentCommand{\DeclareMCRulePattern}{m m}{}

```

---

File 297 **lwarp-multimedia.sty**

§ 403 Package **multimedia**

Pkg multimedia multimedia is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addressource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

`\hyperlinkmovie`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YOUTUBE™ video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{multimedia}[2012/05/02]
2 \LWR@origRequirePackage{lwarp-common-multimedia}
3
4 \LetLtxMacro\movie\LWR@multimedia
5 \LetLtxMacro\sound\LWR@multimedia
6
7 \newcommand{\hyperlinkmovie}[3][[]]{}
```

---

File 298 **lwarp-multiobjective.sty**

§ 404 Package **multiobjective**

*(Emulates or patches code by LUIS MARTÍ.)*

Pkg multiobjective **multiobjective** is used as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{multiobjective}[2008/08/19]
2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\dom}{\prec}}
4 \CustomizeMathJax{\newcommand{\negdom}{\not\prec}}
5 \CustomizeMathJax{\newcommand{\weakdom}{\preccurlyeq}}
6 \CustomizeMathJax{\newcommand{\negweakdom}{\not\preccurlyeq}}
7 \CustomizeMathJax{\newcommand{\strictdom}{\mathord{\prec}\!\!\!\mathord{\prec}}}
8 \CustomizeMathJax{\newcommand{\negstrictdom}{\mathord{\not\prec}\!\!\!\mathord{\prec}}}
9 \CustomizeMathJax{\newcommand{\multepsilondom}{\preccurlyeq_{\epsilon\cdot}}}
10 \CustomizeMathJax{\newcommand{\addiepsilondom}{\preccurlyeq_{\epsilon +}}}
11 \CustomizeMathJax{\newcommand{better}{\triangleleft}}
12 \CustomizeMathJax{\def\vec#1{%
13 \mathchoice%
14 {{\displaystyle\boldsymbol{#1}}}%
15 {{\textstyle\boldsymbol{#1}}}%
16 {{\scriptstyle\boldsymbol{#1}}}%
17 {{\scriptscriptstyle\boldsymbol{#1}}}%
18 }}
19
20 \CustomizeMathJax{\newcommand{\set}[1]{%
21 \mathchoice%
22 {{\displaystyle\mathcal{#1}}}%
23 {{\textstyle\mathcal{#1}}}%
24 {{\scriptstyle\mathcal{#1}}}%
25 {{\scriptscriptstyle\mathcal{#1}}}%
26 }}
```

```

25 {{\scriptscriptstyle\mathcal{#1}}}%
26 }}
27 \CustomizeMathJax{\def\argmax{\mathop{{\mathrm{arg}}}\, \max}}
28 \CustomizeMathJax{\def\argmin{\mathop{{\mathrm{arg}}}\, \min}
29 }}
30 \end{warpMathJax}

```

File 299 **lwarp-multirow.sty**

§ 405 Package **multirow**

(Emulates or patches code by PIET VAN OOSTRUM, ØYSTEIN BACHE, JERRY LEICHTER.)

Pkg multirow multirow is emulated during HTML output, and used as-is while inside a lateximage.

[vposn](#) • Note that recent versions of multirow include a new optional vposn argument.

[multirow cells](#) • For multirow, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```

... & \multirow{2}{.5in}{text} & ...
... & \mrowcell & ...

```

[colored cells](#) • The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so `\warpprintonly` and `\warpHTMLonly` must be used to make versions for print and HTML.

[with \multicolumn](#) • See section 405.2 for `\multicolumnrow`.

⚠ `\multicolumn & \multirow` lwarp does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

⚠ [skipped cells](#) As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines, `\mcolrowcell` must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

⚠ [empty cells](#)

```

... & \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text} & ...
... & \mcolrowcell & & \mcolrowcell & ...
... & \mcolrowcell & & \mcolrowcell & ...

```

⚠ [MathJax](#) • MATHJAX does not support multirow, so it is emulated to only print its text on the first row. `\multirow` works as expected in text tabulars or svg math.

In a lateximage, `\LWR@restoreorigformatting` restores the original print-mode versions.

See section 73.25 for the print-mode versions.

for HTML output:

Remove the placeholder macro which was used if `multirow` was not loaded:

```
1 \LetLtxMacro\multirow\relax
2 \LWR@ProvidesPackagePass{multirow}[2018/08/03]
```

`\LWR@multirowborder` Set to left or right to create a thick border for the cell, for use by `bigdelim`:

```
3 \newcommand{\LWR@multirowborder}{}
```

### § 405.1 Multirow

`\multirow` [*⟨vpos⟩*] [*⟨numrows⟩*] [*⟨bigstruts⟩*] [*⟨width⟩*] [*⟨fixup⟩*] [*⟨text⟩*]

```
4 \NewDocumentCommand{\LWR@HTML@multirow}{O{c} m o m o +m}%
5 {%
6 \LWR@traceinfo{*** LWR@HTML@multirow #1 #2 #4}%

7 \booltrue{LWR@usedmultirow}%

8 \LWR@maybenewtablerow%
9 \LWR@tabularleftedge%
```

Print the start of a new table data cell:

```
10 \LWR@htmltag{td rowspan="#2" %
```

A class adds the column spec and the rule:

```
11 class="td%
```

Append this column's spec:

```
12 \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
```

If this column has a `cmidrule`, add “rule” to the end of the HTML class tag. Also add the vertical bar class.

```
13 \LWR@addcmidruletrim%
14 \LWR@addleftmostbartag%
15 \LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
16 "%
```

```
17 \LWR@tdstartstyles%
```

The vertical alignment, if given:

```
18 \ifstrequal{#1}{c}{\LWR@tdaddstyle\LWR@print@box{vertical-align:middle}}{}%
19 \ifstrequal{#1}{b}{\LWR@tdaddstyle\LWR@print@box{vertical-align:bottom}}{}%
20 \ifstrequal{#1}{t}{\LWR@tdaddstyle\LWR@print@box{vertical-align:top}}{}%
```

The left/right border, if given:

```
21 \ifdefvoid{\LWR@multirowborder}{}{%
22 \LWR@daddstyle%
23 \LWR@print@mbx{border-\LWR@multirowborder:} 2px dotted black ; %
24 \LWR@print@mbx{padding-\LWR@multirowborder:} 2px%
25 }%
```

Additional style elements:

```
26 \LWR@addcmidrulewidth%
27 \LWR@addcdashline%
28 \LWR@addtabularrulecolors%
29 \LWR@tdendstyles%
30 }%
```

The column's < spec:

```
31 \LWR@getexparray{\LWR@colbeforeSpec}{\arabic{\LWR@tableLaTeXcolindex}}%
```

While printing the text, redefine \\\ to generate a new line

```
32 \begingroup\LetLtxMacro{\\}{\LWR@endofline}#6\endgroup%
33 \LWR@stoppars%
34 \boolfalse{\LWR@intabularmetadata}%
35 \renewcommand{\LWR@multirowborder}{}%
36 \LWR@traceinfo{*** LWR@HTML@multirow done}%
37 }%
38
39 \LWR@formatted{multirow}
```

## § 405.2 Combined multicolumn and multirow

```
\multicolumnrow {<1:cols>} {<2:halign>} [<3:vpos>] {<4:numrows>} [<5:bigstruts>] {<6:width>} [<7:fixup>]
{<8:text>}
```

\@ifpackageloaded{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The HTML version follows.

\AtBeginDocument because the print version had to see if multirow was loaded before determining how to define \LWR@print@multicolumnrow.

```
40 \AtBeginDocument{
41
42 \NewExpandableDocumentCommand{\LWR@HTML@multicolumnrow}{m m O{} m O{} m O{} +m}{%
43 \booltrue{\LWR@usedmultirow}}%
```

Figure out how many extra HTML columns to add for @ and ! columns:

```
44 \LWR@tabularhtmlcolumns{\arabic{\LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn/multirow tag, temporarily redefining the end of line. (Using a group caused problems with a nested tabular.)

```
45 \LetLtxMacro{\}{\LWR@endofline}%
46 \LWR@domulticolumn[#3][#4]{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#8}%
47 \LetLtxMacro{\}{\LWR@tabularendofline}%
```

Move to the next L<sup>A</sup>T<sub>E</sub>X column:

```
48 \defaddtcounter{LWR@tableLaTeXcolindex}{#1}%
49 \defaddtcounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
50 \booltrue{LWR@skipatbang}%
51 }
52
53 \LWR@expandableformatted{multicolumnrow}
54
55 }% \AtBeginDocument
```

For MATHJAX. Only the text is used. All other parameters are ignored.

```
56 \begin{warpMathJax}
57 % \multirow[vpos]{num}[bigstruts]{width}[vmove]{text}
58 \CustomizeMathJax{\newcommand{\LWRsubmultirow}[2][]{#2}}
59 \CustomizeMathJax{\newcommand{\LWRmultirow}[2][]{\LWRsubmultirow}}
60 \CustomizeMathJax{\newcommand{\multirow}[2][]{\LWRmultirow}}
61 %
62 \CustomizeMathJax{\newcommand{\mrowcell}{}{}}
63 \CustomizeMathJax{\newcommand{\mcolrowcell}{}{}}
64 \CustomizeMathJax{\newcommand{\STneed}[1]{}{}}
65 \end{warpMathJax}
```

---

File 300 **lwarp-multitoc.sty**

§ 406 Package **multitoc**

Pkg multitoc multitoc is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{multitoc}[1999/06/08]

```
2 \newcommand{\multicolumntoc}{2}
3 \newcommand{\multicolumnlot}{2}
4 \newcommand{\multicolumnlof}{2}
5 \newcommand*{\immediateaddtocontents}[2]{}{}
```

File 301 **lwarp-musicography.sty**

§ 407 Package **musicography**

(Emulates or patches code by ANDREW A. CASHNER.)

Pkg musicography musicography is patched for use by lwarp.

Images are used for the meter symbols and fingered bass, since the HTML fonts tend not to be the correct size and HTML cannot stack items. The HTML alt tag copies C and 3/2, etc. Hashes are used for the meter images, which are then reused as necessary.



Note that browser support for musical symbols may be buggy. ALT text and copy/paste into a text editor work well.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{musicography}[2019/05/28]
2 \NewDocumentCommand{\LWR@HTML@musSymbol}{ O{\musFont} m m m m }{%
3 \begin{lateximage}%
4 {#1\kern#2\raisebox{#3}{#5}\kern#4}%
5 \end{lateximage}%
6 }
7
8 \LWR@formatted{musSymbol}
9
10 \NewDocumentCommand{\LWR@HTML@musStemmedNote}{ m }{%
11 \begin{lateximage}%
12 \musSymbol{0.05em}{0.5ex}{0.2em}{#1\musStem}%
13 \end{lateximage}%
14 }
15
16 \LWR@formatted{musStemmedNote}
17
18 \NewDocumentCommand{\LWR@HTML@musFlaggedNote}{ m m }{%
19 \begin{lateximage}%
20 \musSymbol{0.05em}{0.5ex}{0pt}{#1\musStem}%
21 \musSymbol{0pt}{0pt}{0.9em}{#2}%
22 \end{lateximage}%
23 }
24
25 \LWR@formatted{musFlaggedNote}
26
27 \NewDocumentCommand{\LWR@HTML@musDottedNote}{ m }{%
28 \begin{lateximage}%
29 #1\musDot%
30 \end{lateximage}%
31 }
32
33 \LWR@formatted{musDottedNote}
34
35 \NewDocumentCommand{\LWR@HTML@musMeter}{ m m }{%

```

```

36 \begin{lateximage}*[#1/#2][#1#2]*%
37 \musStack{#1 #2}\kern0.05em%
38 \end{lateximage}%
39 }
40
41 \LWR@formatted{musMeter}
42
43 \NewDocumentCommand{\LWR@HTML@meterCplus}{ m }{%
44 \begin{lateximage}*[C#1]*%
45 \meterC{\kern-0.7pt#1%
46 \end{lateximage}%
47 }
48
49 \LWR@formatted{meterCplus}
50
51 \NewDocumentCommand{\LWR@HTML@meterC}{}{%
52 \begin{lateximage}*[C]*%
53 \musSymbolMeter{\symbol{83}}%
54 \end{lateximage}%
55 }
56
57 \LWR@formatted{meterC}
58
59 \NewDocumentCommand{\LWR@HTML@meterCutC}{}{%
60 \begin{lateximage}*[C|]*%
61 \musSymbolMeter{\symbol{82}}%
62 \end{lateximage}%
63 }
64
65 \LWR@formatted{meterCutC}
66
67 \NewDocumentCommand{\LWR@HTML@meterCThreeTwo}{}{%
68 \begin{lateximage}*[C3/2]*%
69 \meterCplus{\musStack{3 2}}%
70 \end{lateximage}%
71 }
72
73 \LWR@formatted{meterCThreeTwo}
74
75 \NewDocumentCommand{\LWR@HTML@meterO}{}{\HTMLUnicode{25EF}}
76
77 \LWR@formatted{meterO}
78
79 \newcommand{\LWR@null@noFig}[1][[]]{}%
80
81 \NewDocumentCommand{\LWR@HTML@musFig}{ m }{%
82 \begin{lateximage}*[%
83 \{ % ALT text for copy/paste
84 \LetLtxMacro\noFig\LWR@null@noFig%
85 \LetLtxMacro\musSharp\LWR@HTML@musSharp%
86 \LetLtxMacro\musDoubleSharp\LWR@HTML@musDoubleSharp%
87 \LetLtxMacro\musFlat\LWR@HTML@musFlat%
88 \LetLtxMacro\musDoubleFlat\LWR@HTML@musDoubleFlat%
89 \LetLtxMacro\musNatural\LWR@HTML@musNatural%
90 {#1}% braces here because \noFig uses []

```

```

91 }%
92]*%
93 \musStack[\musFigFont]{#1}%
94 \end{lateximage}%
95 }
96
97 \LWR@formatted{musFig}
98
99 \NewDocumentCommand{\LWR@HTML@musFlat} {}{\HTMLUnicode{266D}}
100 \NewDocumentCommand{\LWR@HTML@musDoubleFlat} {}{\HTMLUnicode{1D12B}}
101 \NewDocumentCommand{\LWR@HTML@musSharp} {}{\HTMLUnicode{266F}}
102 \NewDocumentCommand{\LWR@HTML@musDoubleSharp} {}{\HTMLUnicode{1D12A}}
103 \NewDocumentCommand{\LWR@HTML@musNatural} {}{\HTMLUnicode{266E}}
104
105 \LWR@formatted{musFlat}
106 \LWR@formatted{musDoubleFlat}
107 \LWR@formatted{musSharp}
108 \LWR@formatted{musDoubleSharp}
109 \LWR@formatted{musNatural}
110
111 \NewDocumentCommand{\LWR@HTML@musWhole} {}{\HTMLUnicode{1D15D}}
112 \NewDocumentCommand{\LWR@HTML@musHalf} {}{\HTMLUnicode{1D15E}}
113 \NewDocumentCommand{\LWR@HTML@musQuarter} {}{\HTMLUnicode{1D15F}}
114 \NewDocumentCommand{\LWR@HTML@musEighth} {}{\HTMLUnicode{1D160}}
115 \NewDocumentCommand{\LWR@HTML@musSixteenth} {}{\HTMLUnicode{1D161}}
116 \NewDocumentCommand{\LWR@HTML@musThirtySecond} {}{\HTMLUnicode{1D162}}
117 \NewDocumentCommand{\LWR@HTML@musSixtyFourth} {}{\HTMLUnicode{1D163}}
118
119 \LWR@formatted{musWhole}
120 \LWR@formatted{musHalf}
121 \LWR@formatted{musQuarter}
122 \LWR@formatted{musEighth}
123 \LWR@formatted{musSixteenth}
124 \LWR@formatted{musThirtySecond}
125 \LWR@formatted{musSixtyFourth}
126
127 \NewDocumentCommand{\LWR@HTML@musWholeDotted} {}
128 {\HTMLUnicode{1D15D}\HTMLUnicode{1D16D}}
129 \NewDocumentCommand{\LWR@HTML@musHalfDotted} {}
130 {\HTMLUnicode{1D15E}\HTMLUnicode{1D16D}}
131 \NewDocumentCommand{\LWR@HTML@musQuarterDotted} {}
132 {\HTMLUnicode{1D15F}\HTMLUnicode{1D16D}}
133 \NewDocumentCommand{\LWR@HTML@musEighthDotted} {}
134 {\HTMLUnicode{1D160}\HTMLUnicode{1D16D}}
135 \NewDocumentCommand{\LWR@HTML@musSixteenthDotted} {}
136 {\HTMLUnicode{1D161}\HTMLUnicode{1D16D}}
137 \NewDocumentCommand{\LWR@HTML@musThirtySecondDotted} {}
138 {\HTMLUnicode{1D162}\HTMLUnicode{1D16D}}
139 \NewDocumentCommand{\LWR@HTML@musSixtyFourthDotted} {}
140 {\HTMLUnicode{1D163}\HTMLUnicode{1D16D}}
141
142 \LWR@formatted{musWholeDotted}
143 \LWR@formatted{musHalfDotted}
144 \LWR@formatted{musQuarterDotted}
145 \LWR@formatted{musEighthDotted}

```

```

146 \LWR@formatted{musSixteenthDotted}
147 \LWR@formatted{musThirtySecondDotted}
148 \LWR@formatted{musSixtyFourthDotted}

```

---

File 302 **lwarp-nameauth.sty**

§ 408 Package **nameauth**

(Emulates or patches code by CHARLES P. SCHAUM.)

Pkg nameauth nameauth is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{nameauth}[2017/03/22]

lwarp formatting is inserted in the following.

```

2 \renewcommand*\@nameauth@Hook[1]
3 {%
4 \if@nameauth@Lock
5 \@nameauth@InHooktrue%
6 \protected@edef\test{#1}%
7 \expandafter\@nameauth@TestDot\expandafter{\test}%
8 \if@nameauth@InAKA
9 \if@nameauth@AlwaysFormat
10 \@nameauth@FirstFormattrue%
11 \else
12 \unless\if@nameauth@AKAFormat
13 \@nameauth@FirstFormatfalse\fi
14 \fi
15 \if@nameauth@MainFormat
16 \if@nameauth@FirstFormat
17 \bgroup\NamesFormat{%
18 \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% lwarp
19 }\egroup%
20 \else
21 \bgroup\MainNameHook{%
22 \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% lwarp
23 }\egroup%
24 \fi
25 \else
26 \if@nameauth@FirstFormat
27 \bgroup\FrontNamesFormat{%
28 \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% lwarp
29 }\egroup%
30 \else
31 \bgroup\FrontNameHook{%
32 \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% lwarp
33 }\egroup%
34 \fi
35 \fi
36 \else
37 \if@nameauth@AlwaysFormat

```

```

38 \@nameauth@FirstFormattrue%
39 \fi
40 \if@nameauth@MainFormat
41 \if@nameauth@FirstFormat
42 \bgroup\NamesFormat{%
43 \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% lwarp
44 }\egroup%
45 \else
46 \bgroup\MainNameHook{%
47 \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% lwarp
48 }\egroup%
49 \fi
50 \else
51 \if@nameauth@FirstFormat
52 \bgroup\FrontNamesFormat{%
53 \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% lwarp
54 }\egroup%
55 \else
56 \bgroup\FrontNameHook{%
57 \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}% lwarp
58 }\egroup%
59 \fi
60 \fi
61 \fi
62 \@nameauth@FirstFormatfalse%
63 \@nameauth@InHookfalse%
64 \fi
65 }

```

---

File 303 **lwarp-nameref.sty**

§ 409 Package **nameref**

Pkg nameref nameref is emulated by lwarp.

**for HTML output:** Discard all options for lwarp-nameref:

```

1 \PackageInfo{lwarp}{%
2 Using the lwarp HTML version of package 'nameref',\MessageBreak
3 and discarding options.\MessageBreak
4 (Not using \protect\ProvidesPackage, so that other packages\MessageBreak
5 do not attempt to patch lwarp's version of 'nameref'.)\MessageBreak
6 }
7 \DeclareOption*{}
8 \ProcessOptions\relax

```

---

File 304 **lwarp-natbib.sty**

§ 410 Package **natbib**

*(Emulates or patches code by PATRICK W. DALY.)*

Pkg natbib natbib is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{natbib}[2010/09/13]

Replace math < and > with \textless and \textgreater:

A macro to compare:

```
2 \newcommand{\LWRNB@NAT@open}{<$}
```

To patch \NAT@open and \NAT@close

```
3 \newcommand{\LWRNB@patchnatbibopenclose}{
4 \ifdefstrequal{\NAT@open}{\LWRNB@NAT@open}
5 {
6 \renewcommand{\NAT@open}{\textless}
7 \renewcommand{\NAT@close}{\textgreater}
8 }{ }
9 }
```

Do it now in case angle was selected as an option:

```
10 \LWRNB@patchnatbibopenclose
```

Also patch \setcitestyle to patch after settings are made:

```
11 \let\LWRNB@origsetcitestyle\setcitestyle
12
13 \renewcommand{\setcitestyle}[1]{%
14 \LWRNB@origsetcitestyle{#1}%
15 \LWRNB@patchnatbibopenclose%
16 }
```

File 305 **lwarp-nccfancyhdr.sty**

§ 411 Package **nccfancyhdr**

(Emulates or patches code by ALEXANDER I. ROZHENKO.)

Pkg nccfancyhdr nccfancyhdr is ignored.

for HTML output: 1 \LWR@ProvidesPackageDrop{nccfancyhdr}[2004/12/07]

```
2 \newcommand*{\headrulewidth}{}
3 \newcommand*{\footrulewidth}{}
4 \newcommand{\headstrutheight}{}
5 \newcommand{\footstrutheight}{}
6 \newcommand*{\headrule}{}
7 \newcommand*{\footrule}{}
8
9 \newdimen\headwidth
```

```

10 \newcommand*\extendedheaders{}
11 \newcommand*\normalheaders{}
12
13 \newcommand*\fancyhead[2]{}
14 \newcommand*\fancyfoot[2]{}
15 \newcommand*\fancyhf[2]{}
16 \newcommand*\fancypagestyle[2]{}
17 \newcommand*\lhead[2]{}
18 \newcommand*\chead[2]{}
19 \newcommand*\rhead[2]{}
20 \newcommand*\lfoot[2]{}
21 \newcommand*\cfoot[2]{}
22 \newcommand*\rfoot[2]{}
23
24 \newcommand{\nouppercase}[1]{#1}
25
26 \NewDocumentCommand{\fancycenter}{o o m m}{}
27
28 \NewDocumentCommand{\newpagestyle}{m o m}{}
29
30 \newcommand*\iffloatpage[2]{#2}
31 \newcommand*\ifftopfloat[2]{#2}
32 \newcommand*\iffbotfloat[2]{#2}

```

---

File 306 **lwarp-nccfoots.sty**

§ 412 Package **nccfoots**

*(Emulates or patches code by ALEXANDER I. ROZHENKO.)*

Pkg nccfoots nccfoots is used as-is, and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{nccfoots}[2005/02/03]



For MATHJAX. There is no way to test for an empty argument, so the mark is not automatically duplicated.

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\Footnotemark}[1]{{}^{\mathrm{#1}}}}
4 \CustomizeMathJax{\newcommand{\Footnote}[2]{\Footnotemark{#1}}}
5 \end{warpMathJax}

```

---

File 307 **lwarp-nccmath.sty**

§ 413 Package **nccmath**

*(Emulates or patches code by ALEXANDER I. ROZHENKO.)*

Pkg nccmath nccmath is patched for use by lwarp, and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{nccmath}[2006/01/20]

```

2 \let\LWR@origeqnarray\eqnarray
3 \let\LWR@origendeqnarray\endeqnarray
4
5 \csletcs{LWR@origeqnarraystar}{eqnarray*}
6 \csletcs{LWR@origendeqnarraystar}{endeqnarray*}
7
8 \RenewEnviron{eqnarray}
9 {%
10
11 \LWR@eqnarrayfactor
12
13 }
14
15 \RenewEnviron{eqnarray*}
16 {%
17
18 \begingroup
19 \csletcs{LWR@origeqnarray}{LWR@origeqnarraystar}
20 \csletcs{LWR@origendeqnarray}{LWR@origendeqnarraystar}
21 \boolfalse{LWR@numbereqnarray}
22 \LWR@eqnarrayfactor
23 \endgroup
24
25 }
26
27 \def\eqs{%
28 \ifstar\LWR@nccmath@eqsstar\LWR@nccmath@eqs%
29 }
30 \newcommand*{\LWR@nccmath@eqsstar}[2][[]]{\begin{eqnarray*}#2\end{eqnarray*}}
31 \newcommand*{\LWR@nccmath@eqs}[2][[]]{\begin{eqnarray}#2\end{eqnarray}}
32
33 \begin{warpMathJax}
34 \CustomizeMathJax{\renewcommand{\intertext}[2][[]]{\text{#2}\notag \\\}}
35 \CustomizeMathJax{\newenvironment{fleqn}[1][[]]{}{}}
36 \CustomizeMathJax{\newenvironment{ceqn}{}{}}
37 \CustomizeMathJax{\newenvironment{darray}[2][c]{\begin{array}[#1][#2]{\end{array}}}}
38 \CustomizeMathJax{\newcommand{\dmulticolumn}[3][#3]}

```

As of v0.86, MATHJAX v3 does not offer `\*`, so the unstarred version is used here.

```

39 \CustomizeMathJax{\newcommand{\LWRnrnostar}[1][0.5ex]{\[#1]}}
40 \CustomizeMathJax{\newcommand{\nr}{\ifstar\LWRnrnostar\LWRnrnostar}}
41
42 \CustomizeMathJax{\newcommand{\mrel}[1]{\begin{aligned}#1\end{aligned}}}
43 \CustomizeMathJax{\newcommand{\underrel}[2]{\underset{#2}{#1}}}
44 \CustomizeMathJax{\newcommand{\medmath}[1][#1]}
45 \CustomizeMathJax{\newcommand{\medop}[1][#1]}
46 \CustomizeMathJax{\newcommand{\medint}[1][#1]}
47 \CustomizeMathJax{\newcommand{\medintcorr}[1][#1]}
48 \CustomizeMathJax{\newcommand{\mfrac}[2]{\frac{#1}{#2}}}
49 \CustomizeMathJax{\newcommand{\mbinom}[2]{\binom{#1}{#2}}}
50 \CustomizeMathJax{\newenvironment{mmatrix}{\begin{matrix}}{\end{matrix}}}
51 \CustomizeMathJax{\newcommand{\displaybreak}[1][[]]}

```

$\backslash eq$ ,  $\backslash eqs$ ,  $\backslash eqalign$  are created by L<sup>A</sup>T<sub>E</sub>X, not MATHJAX.

```
52 \end{warpMathJax}
```

---

File 308 **lwarp-needspace.sty**

§ 414 Package **needspace**

(Emulates or patches code by PETER WILSON.)

Pkg needspace needspace is ignored.

**for HTML output:** Discard all options for lwarp-needspace:

```
1 \LWR@ProvidesPackageDrop{needspace}[2010/09/12]
2
3 \DeclareDocumentCommand{\needspace}{m}{}
4 \DeclareDocumentCommand{\Needspace}{s m}{}

```

---

File 309 **lwarp-newpxmath.sty**

§ 415 Package **newpxmath**

(Emulates or patches code by MICHAEL SHARPE.)

Pkg newpxmath newpxmath is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except slantedGreek is honored. The dedicated macros for upright and italic Greek do work correctly.

SVG math should appear the same as the printed output.

**for HTML output:** The MATHJAX code from newtxmath is used:

```
1 \LWR@ProvidesPackagePass{newpxmath}[2020/01/09]
2
3 \LWR@infoprocessingmathjax{newpxmath}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-newpctxmath}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 % * \marg{2: prefix} \marg{3: postfix} \marg{4: i/u: italic/upright}
12 \LWR@mathjax@addgreek@u@up*{}{up}
13 \LWR@mathjax@addgreek@u@up*{}{up}{}
14 \LWR@mathjax@addgreek@l@up{}{up}{}
15 \LWR@mathjax@addgreek@l@up*{}{up}{}
16 \LWR@mathjax@addgreek@u@it*{}{it}
17 \LWR@mathjax@addgreek@l@it*{}{it}

```

Optional slanted Greek:

```

18 \ifpx@slantedG
19 \LWR@mathjax@addgreek@u@it*{}{}
20 \fi
21
22 \end{warpMathJax}

```

File 310 **lwarp-newtxmath.sty**

§ 416 Package **newtxmath**

(Emulates or patches code by MICHAEL SHARPE.)

Pkg newtxmath newtxmath is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except `slantedGreek` is honored, and except that bold italic Latin letters are not defined for MATHJAX if the option is not selected.

The dedicated macros for upright and italic Greek and bold italic Latin letters do work correctly.

SVG math should appear the same as the printed output.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{newtxmath}[2020/08/04]
2
3 \LWR@infoprocessingmathjax{newtxmath}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-newpxtxmath}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 % * \marg{2: prefix} \marg{3: postfix} \marg{4: i/u: italic/upright}
12 \LWR@mathjax@addgreek@u@up*{}{up}
13 \LWR@mathjax@addgreek@u@up*{up}{}
14 \LWR@mathjax@addgreek@l@up{}{up}
15 \LWR@mathjax@addgreek@l@up{}{up}
16 \LWR@mathjax@addgreek@u@it*{}{it}
17 \LWR@mathjax@addgreek@l@it{}{it}
18
19 % only newtxmath, not newpxmath:
20 \LWR@mathjax@addgreek@u@it*{it}{}
21 \LWR@mathjax@addgreek@l@it{it}{}
22
23 % only newtxmath, not newpxmath:
24 \ifdef{\iftx@BI}{
25 \iftx@BI
26 \LWR@mathjax@addlatin@u@bfit{BI}
27 \LWR@mathjax@addlatin@l@bfit{BI}
28 \fi

```

```
29 }{}
```

Optional slanted Greek:

```
30 \iftx@slantedG
31 \LWR@mathjax@addgreek@u@it*{}{}
32 \fi
33
34 \end{warpMathJax}
```

---

File 311 **lwarp-newtxsf.sty**

§ 417 Package **newtxsf**

*(Emulates or patches code by MICHAEL SHARPE.)*

Pkg newtxsf newtxsf is used as-is for SVG math, and is emulated for MATHJAX.

 **limitations** The MATHJAX emulation ignores all package options, except `slantedGreek` is honored. The dedicated macros for upright and italic Greek and bold italic Latin letters do work correctly.

svg math should appear the same as the printed output.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{newtxsf}[2020/05/02]
2
3 \LWR@infoprocessingmathjax{newtxsf}
4
5 \LWR@origRequirePackage{lwarp-common-mathjax-newpxtmath}
6
7 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
8
9 \begin{warpMathJax}
10
11 % * \marg{2: prefix} \marg{3: postfix} \marg{4: i/u: italic/upright}
12 \LWR@mathjax@addgreek@u@up*{}{up}
13 \LWR@mathjax@addgreek@u@up*{}{}
14 \LWR@mathjax@addgreek@l@up{}{}
15 \LWR@mathjax@addgreek@l@up*{}{}
16 \LWR@mathjax@addgreek@u@it*{}{it}
17 \LWR@mathjax@addgreek@l@it*{}{it}
18
19 % only newtxmath, not newpxmath:
20 \LWR@mathjax@addgreek@u@it*{}{}
21 \LWR@mathjax@addgreek@l@it*{}{}
22 %
23 % only newtxmath, not newpxmath:
24 \ifdef{\iftx@BI}{
25 \iftx@BI
26 \LWR@mathjax@addlatin@u@bfit{BI}
27 \LWR@mathjax@addlatin@l@bfit{BI}
28 \fi
29 }{}
```

Optional slanted Greek:

```
30 \iftx@slantedG
31 \LWR@mathjax@addgreek@u@it*{}{}
32 \fi
33
34 \end{warpMathJax}
```

---

File 312 **lwarp-nextpage.sty**

§ 418 Package **nextpage**

*(Emulates or patches code by PETER WILSON.)*

Pkg nextpage nextpage is ignored.

**for HTML output:** Discard all options for lwarp-nextpage.

```
1 \LWR@ProvidesPackageDrop{nextpage}[2009/09/03]

2 \DeclareDocumentCommand{\cleartoevenpage}{o}{}
3 \DeclareDocumentCommand{\movetoevenpage}{o}{}
4 \DeclareDocumentCommand{\cleartooddpage}{o}{}
5 \DeclareDocumentCommand{\movetooddpage}{o}{}

```

---

File 313 **lwarp-nfssext-cfr.sty**

§ 419 Package **nfssext-cfr**

*(Emulates or patches code by CLEA F. REES.)*

Pkg nfssext-cfr nfssext-cfr is emulated in HTML, and used as-is in print output.

Results depend on the browser's font.

**for HTML output:** 1 \LWR@ProvidesPackagePass{nfssext-cfr}[2017/03/28]

Macros which are present in the lwarp core are commented out here.

```
2 \newrobustcmd{\LWR@HTML@lnstyle}{}
3 \newrobustcmd{\LWR@HTML@ostyle}{\LWR@HTML@scshape}
4 \newrobustcmd{\LWR@HTML@instyle}{}
5 \newrobustcmd{\LWR@HTML@sustyle}{}
6 \newrobustcmd{\LWR@HTML@swstyle}{}
7 \newrobustcmd{\LWR@HTML@pstyle}{}
8 \newrobustcmd{\LWR@HTML@tistyle}{}
9 \newrobustcmd{\LWR@HTML@ostyle}{\LWR@HTML@scshape}
10 \newrobustcmd{\LWR@HTML@postyle}{\LWR@HTML@scshape}
11 \newrobustcmd{\LWR@HTML@ltstyle}{}
12 \newrobustcmd{\LWR@HTML@ofstyle}{}

```

```

13 \newrobustcmd{\LWR@HTML@altstyle}{}
14 \newrobustcmd{\LWR@HTML@regstyle}{}
15 \newrobustcmd{\LWR@HTML@embosstyle}{}
16 \newrobustcmd{\LWR@HTML@ornamentalstyle}{}
17 \newrobustcmd{\LWR@HTML@qtstyle}{}
18 \newrobustcmd{\LWR@HTML@shstyle}{}
19 \newrobustcmd{\LWR@HTML@swashstyle}{}
20 \newrobustcmd{\LWR@HTML@tmstyle}{\renewcommand*{\LWR@family}{tt}}
21 \newrobustcmd{\LWR@HTML@tvstyle}{\renewcommand*{\LWR@family}{tt}}
22 \newrobustcmd{\LWR@HTML@tstyle}{}
23 \newrobustcmd{\LWR@HTML@lstyle}{}
24 \newrobustcmd{\LWR@HTML@tlstyle}{}
25 \newrobustcmd{\LWR@HTML@plstyle}{}
26 \newrobustcmd{\LWR@HTML@tostyle}{\LWR@HTML@scshape}
27 % \newrobustcmd{\LWR@HTML@sisshape}{}
28 \newrobustcmd{\LWR@HTML@olshape}{}
29 \newrobustcmd{\LWR@HTML@scolshape}{}
30 \newrobustcmd{\LWR@HTML@ushape}{}
31 \newrobustcmd{\LWR@HTML@scushape}{}
32 \newrobustcmd{\LWR@HTML@uishape}{\LWR@HTML@itshape}
33 \newrobustcmd{\LWR@HTML@rishape}{}
34 \newrobustcmd{\LWR@HTML@regwidth}{}
35 \newrobustcmd{\LWR@HTML@nwwidth}{}
36 \newrobustcmd{\LWR@HTML@cdwidth}{}
37 \newrobustcmd{\LWR@HTML@ecwidth}{}
38 \newrobustcmd{\LWR@HTML@ucwidth}{}
39 \newrobustcmd{\LWR@HTML@etwidth}{}
40 \newrobustcmd{\LWR@HTML@epwidth}{}
41 \newrobustcmd{\LWR@HTML@exwidth}{}
42 \newrobustcmd{\LWR@HTML@uxwidth}{}
43 \newrobustcmd{\LWR@HTML@mbweight}{\renewcommand*{\LWR@family}{md}}
44 \newrobustcmd{\LWR@HTML@dbweight}{\renewcommand*{\LWR@family}{db}}
45 \newrobustcmd{\LWR@HTML@sbweight}{\renewcommand*{\LWR@family}{sb}}
46 % \newrobustcmd{\LWR@HTML@ebweight}{\renewcommand*{\LWR@family}{eb}}
47 \newrobustcmd{\LWR@HTML@ubweight}{\renewcommand*{\LWR@family}{ub}}
48 % \newrobustcmd{\LWR@HTML@lgweight}{\renewcommand*{\LWR@family}{lg}}
49 \newrobustcmd{\LWR@HTML@elweight}{\renewcommand*{\LWR@family}{el}}
50 \newrobustcmd{\LWR@HTML@ulweight}{\renewcommand*{\LWR@family}{ul}}
51 % \newrobustcmd{\LWR@HTML@itshape}{}
52 % \newrobustcmd{\LWR@HTML@scshape}{}
53 % \newrobustcmd{\LWR@HTML@upshape}{}
54 \newrobustcmd{\LWR@HTML@dfshape}{}
55
56 \ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
57 \newrobustcmd{\LWR@HTML@swshape}{}
58 }
59
60 \newrobustcmd{\LWR@HTML@ornament}[1]{}
61
62 \LWR@formatted{lnstyle}
63 \LWR@formatted{osstyle}
64 \LWR@formatted{instyle}
65 \LWR@formatted{sustyle}
66 \LWR@formatted{swstyle}
67 \LWR@formatted{pstyle}

```

```
68 \LWR@formatted{tistyle}
69 \LWR@formatted{ostyle}
70 \LWR@formatted{postyle}
71 \LWR@formatted{ltstyle}
72 \LWR@formatted{ofstyle}
73 \LWR@formatted{altstyle}
74 \LWR@formatted{regstyle}
75 \LWR@formatted{embossstyle}
76 \LWR@formatted{ornamentalstyle}
77 \LWR@formatted{qtstyle}
78 \LWR@formatted{shstyle}
79 \LWR@formatted{swashstyle}
80 \LWR@formatted{tmstyle}
81 \LWR@formatted{tvstyle}
82 \LWR@formatted{tstyle}
83 \LWR@formatted{lstyle}
84 \LWR@formatted{tlstyle}
85 \LWR@formatted{plstyle}
86 \LWR@formatted{tostyle}
87 % \LWR@formatted{sisshape}
88 \LWR@formatted{olshape}
89 \LWR@formatted{scolshape}
90 \LWR@formatted{ushape}
91 \LWR@formatted{scushape}
92 \LWR@formatted{uishape}
93 \LWR@formatted{rishape}
94 \LWR@formatted{regwidth}
95 \LWR@formatted{nwwidth}
96 \LWR@formatted{cdwidth}
97 \LWR@formatted{ecwidth}
98 \LWR@formatted{ucwidth}
99 \LWR@formatted{etwidth}
100 \LWR@formatted{epwidth}
101 \LWR@formatted{exwidth}
102 \LWR@formatted{uxwidth}
103 \LWR@formatted{mbweight}
104 \LWR@formatted{dbweight}
105 \LWR@formatted{sbweight}
106 % \LWR@formatted{ebweight}
107 \LWR@formatted{ubweight}
108 % \LWR@formatted{lgweight}
109 \LWR@formatted{elweight}
110 \LWR@formatted{ulweight}
111 \LWR@formatted{itshape}% adapt to the new print version
112 \LWR@formatted{scshape}% adapt to the new print version
113 \LWR@formatted{upshape}% adapt to the new print version
114 \LWR@formatted{dfshape}
115
116 \ifdef{\LWR@HTML@swshape}{% duplicated by fontaxes
117 \LWR@formatted{swshape}
118 }
119
120 \LWR@formatted{ornament}

121 \FilenameNullify{%
```

122 \LetLtxMacro\lnstyle\@empty%  
123 \LetLtxMacro\osstyle\@empty%  
124 \LetLtxMacro\instyle\@empty%  
125 \LetLtxMacro\sustyle\@empty%  
126 \LetLtxMacro\swstyle\@empty%  
127 \LetLtxMacro\pstyle\@empty%  
128 \LetLtxMacro\tistyle\@empty%  
129 \LetLtxMacro\ostyle\@empty%  
130 \LetLtxMacro\postyle\@empty%  
131 \LetLtxMacro\ltstyle\@empty%  
132 \LetLtxMacro\ofstyle\@empty%  
133 \LetLtxMacro\altstyle\@empty%  
134 \LetLtxMacro\regstyle\@empty%  
135 \LetLtxMacro\embosstyle\@empty%  
136 \LetLtxMacro\ornamentalstyle\@empty%  
137 \LetLtxMacro\qtstyle\@empty%  
138 \LetLtxMacro\shstyle\@empty%  
139 \LetLtxMacro\swashstyle\@empty%  
140 \LetLtxMacro\tmstyle\@empty%  
141 \LetLtxMacro\tvstyle\@empty%  
142 \LetLtxMacro\lstyle\@empty%  
143 \LetLtxMacro\lstyle\@empty%  
144 \LetLtxMacro\lstyle\@empty%  
145 \LetLtxMacro\plstyle\@empty%  
146 \LetLtxMacro\tostyle\@empty%  
147 % \LetLtxMacro\sishape\@empty%  
148 \LetLtxMacro\olshape\@empty%  
149 \LetLtxMacro\scolshape\@empty%  
150 \LetLtxMacro\ushape\@empty%  
151 \LetLtxMacro\scushape\@empty%  
152 \LetLtxMacro\uishape\@empty%  
153 \LetLtxMacro\rishape\@empty%  
154 \LetLtxMacro\regwidth\@empty%  
155 \LetLtxMacro\nwidth\@empty%  
156 \LetLtxMacro\cdwidth\@empty%  
157 \LetLtxMacro\ecwidth\@empty%  
158 \LetLtxMacro\ucwidth\@empty%  
159 \LetLtxMacro\etwidth\@empty%  
160 \LetLtxMacro\epwidth\@empty%  
161 \LetLtxMacro\exwidth\@empty%  
162 \LetLtxMacro\uxwidth\@empty%  
163 \LetLtxMacro\mbweight\@empty%  
164 \LetLtxMacro\dbweight\@empty%  
165 \LetLtxMacro\sweight\@empty%  
166 % \LetLtxMacro\ebweight\@empty%  
167 \LetLtxMacro\ubweight\@empty%  
168 % \LetLtxMacro\lgweight\@empty%  
169 \LetLtxMacro\elweight\@empty%  
170 \LetLtxMacro\ulweight\@empty%  
171 % \LetLtxMacro\itshape\@empty%  
172 % \LetLtxMacro\scshape\@empty%  
173 % \LetLtxMacro\upshape\@empty%  
174 \LetLtxMacro\dfshape\@empty%  
175 \LetLtxMacro\swshape\@empty%  
176 \LetLtxMacro\ornament\@gobble%

```
177 }
178
179 \newrobustcmd{\LWR@HTML@textln}[1]{\InlineClass{textln}{#1}}
180 \newrobustcmd{\LWR@HTML@textos}[1]{\textsc{#1}}
181 \newrobustcmd{\LWR@HTML@textin}[1]{#1}
182 \newrobustcmd{\LWR@HTML@textsu}[1]{#1}
183 % \newrobustcmd{\LWR@HTML@textsi}[1]{#1}
184 \newrobustcmd{\LWR@HTML@textdf}[1]{#1}

185 \ifdef{\LWR@HTML@textsw}{% duplicated by fontaxes
186 \newrobustcmd{\LWR@HTML@textsw}[1]{#1}
187 \LWR@formatted{textsw}
188 }
189
190 \newrobustcmd{\LWR@HTML@textti}[1]{#1}
191 \newrobustcmd{\LWR@HTML@textlt}[1]{#1}
192 \newrobustcmd{\LWR@HTML@textof}[1]{#1}
193 \newrobustcmd{\LWR@HTML@textalt}[1]{#1}
194 \newrobustcmd{\LWR@HTML@textreg}[1]{#1}
195 \newrobustcmd{\LWR@HTML@emboss}[1]{#1}
196 \newrobustcmd{\LWR@HTML@textorn}[1]{#1}
197 \newrobustcmd{\LWR@HTML@textqt}[1]{#1}
198 \newrobustcmd{\LWR@HTML@textsh}[1]{#1}
199 \newrobustcmd{\LWR@HTML@texttm}[1]{\texttt{#1}}
200 \newrobustcmd{\LWR@HTML@texttv}[1]{\texttt{#1}}
201 \newrobustcmd{\LWR@HTML@textl}[1]{\InlineClass{textln}{#1}}
202 \newrobustcmd{\LWR@HTML@texto}[1]{\textsc{#1}}
203 \newrobustcmd{\LWR@HTML@textp}[1]{\InlineClass{textp}{#1}}
204 \newrobustcmd{\LWR@HTML@textt}[1]{\InlineClass{textt}{#1}}
205 \newrobustcmd{\LWR@HTML@textpl}[1]{#1}
206 \newrobustcmd{\LWR@HTML@textpo}[1]{\textsc{#1}}
207 \newrobustcmd{\LWR@HTML@texttl}[1]{\InlineClass{textln}{#1}}
208 \newrobustcmd{\LWR@HTML@textto}[1]{\textsc{#1}}
209 \newrobustcmd{\LWR@HTML@textol}[1]{#1}
210 \newrobustcmd{\LWR@HTML@textswash}[1]{#1}
211 \newrobustcmd{\LWR@HTML@textu}[1]{#1}
212 \newrobustcmd{\LWR@HTML@textscu}[1]{#1}
213 \newrobustcmd{\LWR@HTML@textui}[1]{\LWR@HTML@textit{#1}}
214 \newrobustcmd{\LWR@HTML@textri}[1]{#1}
215 \newrobustcmd{\LWR@HTML@textnw}[1]{#1}
216 \newrobustcmd{\LWR@HTML@textcd}[1]{#1}
217 \newrobustcmd{\LWR@HTML@textec}[1]{#1}
218 \newrobustcmd{\LWR@HTML@textuc}[1]{#1}
219 \newrobustcmd{\LWR@HTML@textet}[1]{#1}
220 \newrobustcmd{\LWR@HTML@textep}[1]{#1}
221 \newrobustcmd{\LWR@HTML@textex}[1]{#1}
222 \newrobustcmd{\LWR@HTML@textux}[1]{#1}
223 \newrobustcmd{\LWR@HTML@textrw}[1]{#1}
224 \newrobustcmd{\LWR@HTML@textmb}[1]{\LWR@HTML@mbweight\InlineClass{textmb}{#1}}
225 \newrobustcmd{\LWR@HTML@textdb}[1]{\LWR@HTML@dbweight\InlineClass{textdb}{#1}}
226 \newrobustcmd{\LWR@HTML@textsb}[1]{\LWR@HTML@sbweight\InlineClass{textsb}{#1}}
227 % \newrobustcmd{\LWR@HTML@texteb}[1]{#1}
228 \newrobustcmd{\LWR@HTML@textub}[1]{\LWR@HTML@ubweight\InlineClass{textub}{#1}}
229 % \newrobustcmd{\LWR@HTML@textlg}[1]{#1}
230 \newrobustcmd{\LWR@HTML@textel}[1]{\LWR@HTML@elweight\InlineClass{textel}{#1}}
```

```
231 \newrobustcmd{\LWR@HTML@textul}[1]{\LWR@HTML@ulweight\InlineClass{textul}{#1}}
232
233 \LWR@formatted{textln}
234 \LWR@formatted{textos}
235 \LWR@formatted{textin}
236 \LWR@formatted{textsu}
237 % \LWR@formatted{textsi}
238 \LWR@formatted{textdf}
239 \LWR@formatted{textti}
240 \LWR@formatted{textlt}
241 \LWR@formatted{textof}
242 \LWR@formatted{textalt}
243 \LWR@formatted{textreg}
244 \LWR@formatted{emboss}
245 \LWR@formatted{textorn}
246 \LWR@formatted{textqt}
247 \LWR@formatted{textsh}
248 \LWR@formatted{texttm}
249 \LWR@formatted{texttv}
250 \LWR@formatted{textl}
251 \LWR@formatted{texto}
252 \LWR@formatted{textp}
253 \LWR@formatted{textt}
254 \LWR@formatted{textpl}
255 \LWR@formatted{textpo}
256 \LWR@formatted{texttl}
257 \LWR@formatted{textto}
258 \LWR@formatted{textol}
259 \LWR@formatted{textswash}
260 \LWR@formatted{textu}
261 \LWR@formatted{textscu}
262 \LWR@formatted{textui}
263 \LWR@formatted{textri}
264 \LWR@formatted{textnw}
265 \LWR@formatted{textcd}
266 \LWR@formatted{textec}
267 \LWR@formatted{textuc}
268 \LWR@formatted{textet}
269 \LWR@formatted{textep}
270 \LWR@formatted{textex}
271 \LWR@formatted{textux}
272 \LWR@formatted{textrw}
273 \LWR@formatted{textmb}
274 \LWR@formatted{textdb}
275 \LWR@formatted{textsb}
276 % \LWR@formatted{texteb}
277 \LWR@formatted{textub}
278 % \LWR@formatted{textlg}
279 \LWR@formatted{textel}
280 \LWR@formatted{textul}
281
282 \FilenameNullify{%
283 \LetLtxMacro\textln\@firstofone%
284 \LetLtxMacro\textos\@firstofone%
```

```
285 \LetLtxMacro\textin\@firstofone%
286 \LetLtxMacro\textsu\@firstofone%
287 % \LetLtxMacro\textsi\@firstofone%
288 \LetLtxMacro\textdf\@firstofone%
289 \LetLtxMacro\textsw\@firstofone%
290 \LetLtxMacro\textti\@firstofone%
291 \LetLtxMacro\textlt\@firstofone%
292 \LetLtxMacro\textof\@firstofone%
293 \LetLtxMacro\textalt\@firstofone%
294 \LetLtxMacro\textreg\@firstofone%
295 \LetLtxMacro\emboss\@firstofone%
296 \LetLtxMacro\textorn\@firstofone%
297 \LetLtxMacro\textqt\@firstofone%
298 \LetLtxMacro\textsh\@firstofone%
299 \LetLtxMacro\texttm\@firstofone%
300 \LetLtxMacro\texttv\@firstofone%
301 \LetLtxMacro\textl\@firstofone%
302 \LetLtxMacro\texto\@firstofone%
303 \LetLtxMacro\textp\@firstofone%
304 \LetLtxMacro\textt\@firstofone%
305 \LetLtxMacro\textpl\@firstofone%
306 \LetLtxMacro\textpo\@firstofone%
307 \LetLtxMacro\texttl\@firstofone%
308 \LetLtxMacro\textto\@firstofone%
309 \LetLtxMacro\textol\@firstofone%
310 \LetLtxMacro\textswash\@firstofone%
311 \LetLtxMacro\textu\@firstofone%
312 \LetLtxMacro\textscu\@firstofone%
313 \LetLtxMacro\textui\@firstofone%
314 \LetLtxMacro\textri\@firstofone%
315 \LetLtxMacro\textnw\@firstofone%
316 \LetLtxMacro\textcd\@firstofone%
317 \LetLtxMacro\textec\@firstofone%
318 \LetLtxMacro\textuc\@firstofone%
319 \LetLtxMacro\textet\@firstofone%
320 \LetLtxMacro\textep\@firstofone%
321 \LetLtxMacro\textex\@firstofone%
322 \LetLtxMacro\textux\@firstofone%
323 \LetLtxMacro\textrw\@firstofone%
324 \LetLtxMacro\textmb\@firstofone%
325 \LetLtxMacro\textdb\@firstofone%
326 \LetLtxMacro\textsb\@firstofone%
327 % \LetLtxMacro\texteb\@firstofone%
328 \LetLtxMacro\textub\@firstofone%
329 % \LetLtxMacro\textlg\@firstofone%
330 \LetLtxMacro\textel\@firstofone%
331 \LetLtxMacro\textul\@firstofone%
332 }
333
334 \providecommand*\zeroslash{}
335 \newrobustcmd*\LWR@HTML@zeroslash{}
336 \LWR@formatted{zeroslash}
```

File 314 **lwarp-nicefrac.sty**

§ 420 Package **nicefrac**

(Emulates or patches code by AXEL REICHERT.)

Pkg nicefrac nicefrac is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{nicefrac}[1998/08/04]

2 \DeclareRobustCommand*\LWR@HTML@UnitsNiceFrac}[3][[]]{%
3 {% localize font selection
4 #1{%
5 \LWR@textcurrentfont{%
6 \InlineClass{numerator}{#2}%
7 /%
8 \InlineClass{denominator}{#3}%
9 }%
10 }%
11 }%
12 }
13
14 \LWR@formatted{@UnitsNiceFrac}
15
16 \DeclareRobustCommand*\LWR@HTML@UnitsUglyFrac}[3][[]]{%
17 {% localize font selection
18 #1{\LWR@textcurrentfont{#2/#3}}%
19 }%
20 }
21
22 \LWR@formatted{@UnitsUglyFrac}

```

For Mathjax:

```

23 \begin{warpMathJax}
24 \CustomizeMathJax{\newcommand{\nicefrac}[3][[]]{\mathinner{{}^{\#2}\!/_{\#3}}}}
25 \end{warpMathJax}

```

File 315 **lwarp-niceframe.sty**

§ 421 Package **niceframe**

Pkg niceframe niceframe is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{niceframe}% the original date is in yyyy/dd/mm format

2 \newcommand{\LWR@niceframe}[3]{%

```

---

```

3 \begin{LWR@setvirtualpage}*%
4 \setlength{\LWR@templengthone}{#1}%
5 \begin{BlockClass}[max-width:\LWR@printlength{\LWR@templengthone}]{#3}%
6 #2
7 \end{BlockClass}%
8 \end{LWR@setvirtualpage}%
9 }
10
11 \newcommand{\niceframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{niceframe}}
12 \newcommand{\curlyframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{curlyframe}}
13 \newcommand{\artdecoframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{artdecoframe}}
14
15 \newcommand{\generalframe}[9]{\LWR@niceframe{\textwidth}{#9}{generalframe}}

```

---

File 316 **lwarp-noitcru1.sty**

§ 422 Package **noitcru1**

*(Emulates or patches code by PAUL EBERMANN.)*

Pkg noitcru1 noitcru1 is used as-is for SVG and emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{noitcru1}[2006/04/11]

```

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\noitUnderline}[1]{\underline{#1}\!}}
4 \end{warpMathJax}

```

---

File 317 **lwarp-nolbreaks.sty**

§ 423 Package **nolbreaks**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg nolbreaks nolbreaks is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{nolbreaks}[2012/05/31]

```

2 \NewDocumentCommand{\nolbreaks}{s m}{\InlineClass{nolbreaks}{#2}}

```

---

File 318 **lwarp-nomencl.sty**

§ 424 Package **nomencl**

*(Emulates or patches code by BORIS VEYTSMAN, BERND SCHANDL, LEE NETHERTON, CV RADHAKRISHNAN.)*

Pkg nomencl nomencl is patched for use by lwarp.

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.list -o <project>_html.nls
```

**for HTML output:** 1 \LWR@ProvidesPackagePass{nomencl}[2005/09/22]

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
2 \def\@@@nomenclature[#1]#2#3{%
3 \def\@tempa{#2}\def\@tempb{#3}%
4 \protected@write\@nomenclaturefile{%
5 {\string\@nomenclatureentry{#1\@nom@verb\@tempa @[\@nom@verb\@tempa]}%
6 \begin@group\@nom@verb\@tempb\protect\@nameqref{\theequation}%
7 |nompageref}{\theLWR@previousautopagelabel}}% lwarp
8 \endgroup
9 \@esphack}
10
11 \renewcommand*\@pagedeclaration[1]{, \nameref{\BaseJobname-autopage-#1}}%
```

File 319 **lwarp-nonfloat.sty**

§ 425 Package **nonfloat**

*(Emulates or patches code by KAI RASCHER.)*

Pkg nonfloat nonfloat is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{nonfloat}[1999/07/05]

```
2 \LetLtxMacro\topcaption\caption
3 \newcommand{\figcaption}{\def\@captype{figure}\caption}
4 \newcommand{\tabcaption}{\def\@captype{table}\topcaption}
5 \newenvironment{narrow}[2]{}{}
```

File 320 **lwarp-nonumonpart.sty**

§ 426 Package **nonumonpart**

Pkg nonumonpart nonumonpart is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{nonumonpart}[2011/04/15]

File 321 **lwarp-nopageno.sty**

§ 427 Package **nopageno**

Pkg nopageno nopageno is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{nopageno}[1989/01/01]

---

File 322 **lwarp-notes.sty**

§ 428 Package **notes**

Pkg notes notes is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{notes}[2002/10/29]

```

2 \newcommand*\LWR@notes@onenote}[2]{%
3 \newenvironment{#1}
4 {
5 \BlockClass{notes#1}
6 \begin{BlockClass}{notesicon}\textcircled{~#2~}\end{BlockClass}
7 \BlockClass{notescontents}
8 }
9 {\endBlockClass\endBlockClass}
10 }
11
12 \LWR@notes@onenote{importantnote}{!}
13
14 \LWR@notes@onenote{warningnote}{--}
15
16 \LWR@notes@onenote{informationnote}{i}

```

---

File 323 **lwarp-notespages.sty**

§ 429 Package **notespages**

Pkg notespages notespages is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{notespages}[2016/08/21]

```

2 \newcommand*\nnotesname{}
3 \newcommand*\nnotestext{}
4 \newcommand*\remainingtextheight{}
5 \newdimen\remainingtextheight
6 \newcommand*\notestitletext{}
7 \newcommand*\notesareatext{}
8 \newcommand*\nnpinfo}[1]{}
9 \newcommand*\tracingnmarks{}
10 \newcommand*\notespage}[1][{}
11 \newcommand*\notespages}[1][{}
12 \newcommand*\notesfill}[1][{}
13 \newcommand*\setnotespages}[1]{}
14 \newcommand*\definotesoption}[2]{}
15 \newcommand*\definotesstyle}[2]{}
16 \newcommand*\definetitlestyle}[2]{}

```

---

```
17 \newcommand{\nppatchchapter}[1]{}
18 \newcommand{\npunpatchchapter}{}
```

---

File 324 **lwarp-nowidow.sty**

§ 430 Package **nowidow**

(Emulates or patches code by RAPHAËL PINSON.)

Pkg nowidow nowidow is ignored.

**for HTML output:** ~~Discard this option for lwarp-nowidow~~ [2011/09/20]

```
\nowidow [⟨lines⟩]
\setnowidow [⟨lines⟩]

2 \newcommand*{\nowidow}[1][{}]{
3 \newcommand*{\setnowidow}[1][{}]{
```

```
\noclub [⟨lines⟩]
\setnoclub [⟨lines⟩]

4 \newcommand*{\noclub}[1][{}]{
5 \newcommand*{\setnoclub}[1][{}]{
```

---

File 325 **lwarp-ntheorem.sty**

§ 431 Package **ntheorem**

(Emulates or patches code by WOLFGANG MAY, ANDREAS SCHEDLER.)

Pkg ntheorem ntheorem is patched for use by lwarp.

---

Table 18: Ntheorem package — css styling of theorems and proofs

**Theorem:** <div> of class theorembody<theoremstyle>

**Theorem Header:** <span> of class theoremheader<style>

where <theoremstyle> is plain, break, etc.

---

### § 431.1 Limitations

- ⚠ **Font control** This conversion is not total. Font control is via CSS, and the custom L<sup>A</sup>T<sub>E</sub>X font settings are ignored.
- ⚠ **cref reference format undefined** If the print version does not use `cleveref`, place all `\theoremstyle` and `\newtheorem` declarations in the preamble inside `\AtBeginDocument`.<sup>19</sup> For some theorems, it may also be required to add inside `\AtBeginDocument` something such as:

```

\AtBeginDocument{ % if not using cleveref package
 \theoremstyle{definition}
 \newtheorem{dtheorem}{Definition}
 . . .
 \usepackage{etoolbox} % for \ifdef
 \ifdef{\cref}{
 \crefname{Proof}{Proof}{Proofs}
 }{
}
}

```

- ⚠ **Equation numbering** `ntheorem` has a bug with equation numbering in  $\mathcal{AMS}$  environments when the option `thref` is used. `lwarp` does not share this bug, so equations with `\split`, etc, are numbered correctly with `lwarp`'s HTML output, but not with the print output. It is recommended to use `cleveref` instead of `ntheorem`'s `thref` option.

### § 431.2 Options

Options `amsthm` or `standard` choose which set of theorems and proofs to initialize.

- ⚠ **Disabled options** The options `thmmarks` and `amsmath` are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option `thref` is disabled because `cleveref` functions are used instead. `\thref` is emulated.

Option `hyperref` is disabled because `lwarp` emulated `hyperref`.

**for HTML output:** Some disabled options:

```

1 \DeclareOption{thref}{
2 \AtEndDocument{
3 \PackageWarningNoLine{lwarp}{%
4 Lwarp uses cleveref, which takes over ntheorem's\MessageBreak
5 referencing, including
6 \protect\label \space and \protect\thref.\MessageBreak
7 Cleveref does not accept ntheorem's optional\MessageBreak
8 argument for \protect\label, so it will appear\MessageBreak
9 in the text. It is recommended to remove the\MessageBreak
10 thref option, \protect\usepackage{cleveref} instead,\MessageBreak
11 and remove any trailing optional arguments for \protect\label%
12 }%
13 }
14 }

```

<sup>19</sup>`lwarp` uses `cleveref` for the HTML conversion, and loads `cleveref` `\AtEndPreamble`, just before `\AtBeginDocument`.

```

15
16
17 \newbool{LWR@theoremmarks}
18 \boolfalse{LWR@theoremmarks}
19
20 \DeclareOption{thmmarks}{
21 \booltrue{LWR@theoremmarks}
22 \newif\ifsetendmark\setendmarktrue
23 }
24
25
26 \newbool{LWR@theoremamsthm}
27 \boolfalse{LWR@theoremamsthm}
28
29 \DeclareOption{amsthm}{\booltrue{LWR@theoremamsthm}}
30
31
32 \DeclareOption{amsmath}{}
33 \DeclareOption{hyperref}{}
34
35 \LWR@ProvidesPackagePass{ntheorem}[2011/08/15]

```

### § 431.3 Remembering the theorem style

Storage for the style being used for new theorems.

```

36 \newcommand{\LWR@newtheoremstyle}{plain}

37 \AtBeginDocument{
38 \ifpackageloaded{cleveref}{
39 \gdef\@thm#1#2#3{%
40 \if@thmmarks
41 \stepcounter{end\InTheoType ctr}%
42 \fi
43 \renewcommand{\InTheoType}{#1}%
44 \if@thmmarks
45 \stepcounter{curr#1ctr}%
46 \setcounter{end#1ctr}{0}%
47 \fi
48 \refstepcounter[#1][#2]% <<< cleveref modification
49 \theorem@prework
50 \LWR@forcenewpage% lwarp
51 \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
52 \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
53 \ifuse@newframeskips % cf. latex.ltx for topsepadd: \@trivlist
54 \ifthm@inframe
55 \thm@topsep\theoremframepreskipamount
56 \thm@topsepadd\theoremframepostskipamount
57 \else
58 \thm@topsep\theoremframepreskipamount
59 \thm@topsepadd\theoremframepostskipamount
60 \fi
61 \else% oldframeskips
62 \thm@topsep\theoremframepreskipamount
63 \thm@topsepadd \theoremframepostskipamount

```

```

64 \ifvmode\advance\thm@topsepadd\partopsep\fi
65 \fi
66 \@topsep\thm@topsep
67 \@topsepadd\thm@topsepadd
68 \advance\linewidth -\theorem@indent
69 \advance\linewidth -\theorem@rightindent
70 \advance\@totalleftmargin \theorem@indent
71 \parshape \@ne \@totalleftmargin \linewidth
72 \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
73 }
74 }{% not @ifpackageloaded{cleveref}
75 \gdef\@thm#1#2#3{%
76 \if@thmmarks
77 \stepcounter{end\InTheoType ctr}%
78 \fi
79 \renewcommand{\InTheoType}{#1}%
80 \if@thmmarks
81 \stepcounter{curr#1ctr}%
82 \setcounter{end#1ctr}{0}%
83 \fi
84 \refstepcounter{#2}%
85 \theorem@prework
86 \LWR@forcenewpage% lwarp
87 \BlockClass{theorembody#1}\LWR@thisthmstyle% lwarp
88 \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
89 \ifuse@newframeskips % cf. latex.ltx for topsepadd: \@trivlist
90 \ifthm@inframe
91 \thm@topsep\theorem@inframepreskipamount
92 \thm@topsepadd\theorem@inframepostskipamount
93 \else
94 \thm@topsep\theorem@preskipamount
95 \thm@topsepadd\theorem@postskipamount
96 \fi
97 \else% oldframeskips
98 \thm@topsep\theorem@preskipamount
99 \thm@topsepadd \theorem@postskipamount
100 \ifvmode\advance\thm@topsepadd\partopsep\fi
101 \fi
102 \@topsep\thm@topsep
103 \@topsepadd\thm@topsepadd
104 \advance\linewidth -\theorem@indent
105 \advance\linewidth -\theorem@rightindent
106 \advance\@totalleftmargin \theorem@indent
107 \parshape \@ne \@totalleftmargin \linewidth
108 \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
109 }
110 }
111 }% AtBeginDocument

```

Patched to remember the style being used for new theorems:

```

112 \gdef\theoremstyle#1{%
113 \@ifundefined{th@#1}{\@warning
114 {Unknown theoremstyle '#1'. Using 'plain'}}%
115 \theorem@style{plain}

```

```

116 \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
117 }%
118 {
119 \theoremstyle{#1}
120 \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
121 }
122 }

```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

123
124 \gdef\xnthm#1#2[#3]{%
125 \ifthm@tempif
126 \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
127 \expandafter\@ifundefined{c@#1}%
128 {\@definecounter{#1}}{%
129 \@newctr{#1}[#3]%
130 \expandafter\xdef\csname the#1\endcsname{%
131 \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
132 {\noexpand\csname\the\theoremnumbering\endcsname{#1}}}%
133 \expandafter\gdef\csname mkheader@#1\endcsname
134 {\csname setparms@#1\endcsname
135 \@thm{#1}{#1}{#2}
136 }%
137 \global\@namedef{end#1}{\@endtheorem}
138 \AtBeginEnvironment{#1}{\edef\LWR@thmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
139 \fi
140 }
141
142 \gdef\@ynthm#1#2{%
143 \ifthm@tempif
144 \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
145 \expandafter\@ifundefined{c@#1}%
146 {\@definecounter{#1}}{%
147 \expandafter\xdef\csname the#1\endcsname
148 {\noexpand\csname\the\theoremnumbering\endcsname{#1}}%
149 \expandafter\gdef\csname mkheader@#1\endcsname
150 {\csname setparms@#1\endcsname
151 \@thm{#1}{#1}{#2}
152 }%
153 \global\@namedef{end#1}{\@endtheorem}
154 \AtBeginEnvironment{#1}{\edef\LWR@thmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
155 \fi
156 }
157
158 \gdef\@othm#1[#2]#3{%
159 \@ifundefined{c@#2}{\@nocounterr{#2}}%
160 {\ifthm@tempif
161 \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
162 \global\@namedef{the#1}{\@nameuse{the#2}}%
163 \expandafter\protected@xdef\csname num@addtheorem#1\endcsname{%
164 \noexpand\@num@addtheorem#1}{#3}}%
165 \expandafter\protected@xdef\csname nonum@addtheorem#1\endcsname{%
166 \noexpand\@nonum@addtheorem#1}{#3}}%

```

```

167 \theoremkeyword{#3}%
168 \expandafter\protected@xdef\csname #1Keyword\endcsname
169 {\the\theoremkeyword}%
170 \expandafter\gdef\csname mkheader@#1\endcsname
171 {\csname setparms@#1\endcsname
172 \@thm{#1}{#2}{#3}
173 }%
174 \global\@namedef{end#1}{\@endtheorem}
175 \AtBeginEnvironment{#1}{\edef\LWR@thmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
176 \fi}
177 }

```

#### § 431.4 HTML cross-referencing

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```

178 \newcommand{\LWR@intheorem}{%
179 \addtocounter{LWR@thisautoid}{1}%
180 \LWR@stoppars%
181 \LWR@htmltag{a id="\LWR@print@mbx{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
182 \LWR@startpars%
183 }

```

#### § 431.5 \newtheoremstyle

The following are patched for css.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a BlockClass environment of class theorembody<style>.

Each header is encased in an \InlineClass of class theoremheader<style>.

```

184 \gdef\newtheoremstyle#1#2#3{%
185 \expandafter\@ifundefined{th#1}%
186 {\expandafter\gdef\csname th@#1\endcsname{%
187 \def\@begintheorem####1####2{%
188 \LWR@intheorem% lwarp
189 #2}%
190 \def\@opargbegintheorem####1####2####3{%
191 \LWR@intheorem% lwarp
192 #3}%
193 }%
194 }%
195 {\PackageError{\basename}{Theorem style #1 already defined}\@eha}
196 }

```

§ 431.6 **Standard styles**

```

197 \renewtheoremstyle{plain}%
198 {\item[
199 \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]]%
200 {\item[
201 \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]]}
202
203 \renewtheoremstyle{break}%
204 {\item[
205 \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
206]}%
207 {\item[
208 \InlineClass{theoremheaderbreak}%
209 {##1\ ##2\ (##3)\theorem@separator}\newline
210]}
211
212 \renewtheoremstyle{change}%
213 {\item[
214 \InlineClass{theoremheaderchange}{##2\ ##1\theorem@separator}]]%
215 {\item[
216 \InlineClass{theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]]}
217
218 \renewtheoremstyle{changebreak}%
219 {\item[
220 \InlineClass{theoremheaderchangebreak}%
221 {##2\ ##1\theorem@separator}\newline
222]}%
223 {\item[
224 \InlineClass{theoremheaderchangebreak}%
225 {##2\ ##1\ (##3)\theorem@separator}\newline
226]}
227
228 \renewtheoremstyle{margin}%
229 {\item[
230 \InlineClass{theoremheadermargin}{##2 \quad ##1\theorem@separator}
231]}%
232 {\item[
233 \InlineClass{theoremheadermargin}{##2 \quad ##1\ (##3)\theorem@separator}
234]}
235
236 \renewtheoremstyle{marginbreak}%
237 {\item[
238 \InlineClass{theoremheadermarginbreak}%
239 {##2 \quad ##1\theorem@separator}\newline
240]}%
241 {\item[
242 \InlineClass{theoremheadermarginbreak}%
243 {##2 \quad ##1\ (##3)\theorem@separator}\newline
244]}
245
246 \renewtheoremstyle{nonumberplain}%
247 {\item[
248 \InlineClass{theoremheaderplain}{##1\theorem@separator}]]%
249 {\item[
250 \InlineClass{theoremheaderplain}{##1\ (##3)\theorem@separator}]]}

```

```

251
252 \renewtheoremstyle{nonumberbreak}%
253 {\item[
254 \InlineClass{theoremheaderbreak}{##1\theoremseparator}\newline
255]}%
256 {\item[
257 \InlineClass{theoremheaderbreak}{##1 (##3)\theoremseparator}\newline
258]}
259
260 \renewtheoremstyle{empty}%
261 {\item[]}%
262 {\item[
263 \InlineClass{theoremheaderplain}{##3}]}
264
265 \renewtheoremstyle{emptybreak}%
266 {\item[]}%
267 {\item[
268 \InlineClass{theoremheaderplain}{##3}] \ \newline}

```

### § 431.7 Additional objects

The following manually adjust the css for the standard configuration objects which are not a purely plain style:

```
269 \ifbool{LWR@theoremamsthm}{}{%
```

Upright text via CSS:

```

270 \newtheoremstyle{plainupright}%
271 {\item[
272 \InlineClass{theoremheaderplain}{##1\ ##2\theoremseparator}]}%
273 {\item[
274 \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theoremseparator}]}

```

Upright text and small caps header via CSS:

```

275 \newtheoremstyle{nonumberplainuprightsc}%
276 {\item[
277 \InlineClass{theoremheadersc}{##1\theoremseparator}]}%
278 {\item[
279 \InlineClass{theoremheadersc}{##1\ (##3)\theoremseparator}]}
280 }% not amsthm

```

### § 431.8 Renewed standard configuration

The following standard configuration is renewed using the new css:

```

281 \ifbool{LWR@theoremamsthm}{}{%

282 \ifx\thm@usestd\undefined
283 \else
284 \theoremnumbering{arabic}
285 \theoremstyle{plain}
286 \RequirePackage{latexsym}

```

```

287 \theoremsymbol{\Box}
288 \theorembodyfont{\itshape}
289 \theoremheaderfont{\normalfont\bfseries}
290 \theoremseparator{}
291 \renewtheorem{Theorem}{Theorem}
292 \renewtheorem{theorem}{Theorem}
293 \renewtheorem{Satz}{Satz}
294 \renewtheorem{satz}{Satz}
295 \renewtheorem{Proposition}{Proposition}
296 \renewtheorem{proposition}{Proposition}
297 \renewtheorem{Lemma}{Lemma}
298 \renewtheorem{lemma}{Lemma}
299 \renewtheorem{Korollar}{Korollar}
300 \renewtheorem{korollar}{Korollar}
301 \renewtheorem{Corollary}{Corollary}
302 \renewtheorem{corollary}{Corollary}
303
304 \theoremstyle{plainupright}
305 \theorembodyfont{\upshape}
306 \theoremsymbol{\HTMLUnicode{25A1}}% UTF-8 white box
307 \renewtheorem{Example}{Example}
308 \renewtheorem{example}{Example}
309 \renewtheorem{Beispiel}{Beispiel}
310 \renewtheorem{beispiel}{Beispiel}
311 \renewtheorem{Bemerkung}{Bemerkung}
312 \renewtheorem{bemerkung}{Bemerkung}
313 \renewtheorem{Anmerkung}{Anmerkung}
314 \renewtheorem{anmerkung}{Anmerkung}
315 \renewtheorem{Remark}{Remark}
316 \renewtheorem{remark}{Remark}
317 \renewtheorem{Definition}{Definition}
318 \renewtheorem{definition}{Definition}
319
320 \theoremstyle{nonumberplainuprightsc}
321 \theoremsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
322 \renewtheorem{Proof}{Proof}
323 \renewtheorem{proof}{Proof}
324 \renewtheorem{Beweis}{Beweis}
325 \renewtheorem{beweis}{Beweis}
326 \qedsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
327
328 \theoremsymbol{}
329 \fi
330}% not amsthm

```

### § 431.9 amsthm option

Only if the amsthm option was given:

```

331 \ifbool{LWR@theoremamsthm}{
332
333 \gdef\th@plain%
334 \def\theorem@headerfont{\normalfont\bfseries}\itshape%
335 \def\@begintheorem##1##2{%
336 \LWR@intheorem% lwarp

```

```

337 \item[
338 \InlineClass{theoremheaderplain}{##1\ ##2.}
339]}%
340 \def\@opargbegintheorem##1##2##3{%
341 \LWR@intheorem% lwarp
342 \item[
343 \InlineClass{theoremheaderplain}{##1\ ##2\ (##3).}
344]}}
345
346 \gdef\th@nonumberplain{%
347 \def\theorem@headerfont{\normalfont\bfseries}\itshape%
348 \def\@begintheorem##1##2{%
349 \LWR@intheorem% lwarp
350 \item[
351 \InlineClass{theoremheaderplain}{##1.}
352]}%
353 \def\@opargbegintheorem##1##2##3{%
354 \LWR@intheorem% lwarp
355 \item[
356 \InlineClass{theoremheaderplain}{##1\ (##3).}
357]}}
358
359 \gdef\th@definition{%
360 \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
361 \def\@begintheorem##1##2{%
362 \LWR@intheorem% lwarp
363 \item[
364 \InlineClass{theoremheaderdefinition}{##1\ ##2.}
365]}%
366 \def\@opargbegintheorem##1##2##3{%
367 \LWR@intheorem% lwarp
368 \item[
369 \InlineClass{theoremheaderdefinition}{##1\ ##2\ (##3).}
370]}}
371
372 \gdef\th@nonumberdefinition{%
373 \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
374 \def\@begintheorem##1##2{%
375 \LWR@intheorem% lwarp
376 \item[
377 \InlineClass{theoremheaderdefinition}{##1.}
378]}%
379 \def\@opargbegintheorem##1##2##3{%
380 \LWR@intheorem% lwarp
381 \item[
382 \InlineClass{theoremheaderdefinition}{##1\ (##3).}
383]}}
384
385 \gdef\th@remark{%
386 \def\theorem@headerfont{\itshape}\normalfont%
387 \def\@begintheorem##1##2{%
388 \LWR@intheorem% lwarp
389 \item[
390 \InlineClass{theoremheaderremark}{##1\ ##2.}
391]}%

```

```

392 \def\@opargbegintheorem##1##2##3{%
393 \LWR@intheorem% lwarp
394 \item[
395 \InlineClass{theoremheaderremark}{##1\ ##2\ (##3).}
396]}}
397
398 \gdef\th@nonumberremark{%
399 \def\theorem@headerfont{\itshape}\normalfont%
400 \def\@begintheorem##1##2{%
401 \LWR@intheorem% lwarp
402 \item[
403 \InlineClass{theoremheaderremark}{##1.}
404]}%
405 \def\@opargbegintheorem##1##2##3{%
406 \LWR@intheorem% lwarp
407 \item[
408 \InlineClass{theoremheaderremark}{##1\ (##3).}
409]}}
410
411 \gdef\th@proof{%
412 \def\theorem@headerfont{\normalfont\bfseries}\itshape%
413 \def\@begintheorem##1##2{%
414 \LWR@intheorem% lwarp
415 \item[
416 \InlineClass{theoremheaderproof}{##1.}
417]}%
418 \def\@opargbegintheorem##1##2##3{%
419 \LWR@intheorem% lwarp
420 \item[
421 \InlineClass{theoremheaderproof}{##1\ (##3).}
422]}}
423
424
425
426 \newcounter{proof}%
427 \if@thmmarks
428 \newcounter{currproofctr}%
429 \newcounter{endproofctr}%
430 \fi
431
432 \gdef\proofSymbol{\openbox}
433
434 \newcommand{\proofname}{Proof}
435
436 \newenvironment{proof}[1][\proofname]{
437 \th@proof
438 \def\theorem@headerfont{\itshape}%
439 \normalfont
440 \theoremsymbol{\HTMLUnicode{220E}}% UTF-8 end-of-proof
441 \@thm{proof}{proof}{#1}
442 }%
443 {\@endtheorem}
444
445 }{}% amsthm option

```

### § 431.10 **Ending a theorem**

Patched for css:

```

446 \let\LWR@origendtheorem\endtheorem
447 \renewcommand{\@endtheorem}{%
448 \ifbool{LWR@theoremmarks}{%
449 \ifsetendmark%
450 \InlineClass{theoremendmark}{\csname\InTheoType Symbol\endcsname}%
451 \setendmarkfalse%
452 \fi%
453 }{}%
454 \LWR@origendtheorem% also does \@endtrivlist
455 \ifbool{LWR@theoremmarks}{\global\setendmarktrue}{}%
456 \endBlockClass%
457 }

```

### § 431.11 **\NoEndMark**

```

458 \gdef\NoEndMark{\global\setendmarkfalse}

```

### § 431.12 **List-of**

Redefined to reuse the float mechanism to add list-of-theorem links:

`\thm@thmline {<1: printed type>} {<2: #>} {<3: optional>} {<4: page>}`

```

459 \renewcommand{\thm@thmline@noname}[4]{%
460 \hypertocfloat{1}{theorem}{thm}{#2 #3}{}%
461 }
462
463 \renewcommand{\thm@thmline@name}[4]{%
464 \hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}%
465 }

```

This was redefined by `ntheorem` when loaded, so it is now redefined for `lwarp`:

```

466 \def\thm@thmline{\thm@thmline@name}

```

Patch for css:

```

467 \def\listtheorems#1{
468 \LWR@htmlElementclass{nav}{lohtm}%
469 \begingroup
470 \c@tocdepth=-2%
471 \def\thm@list{#1}\thm@processlist
472 \endgroup
473 \LWR@htmlElementclassend{nav}{lohtm}%
474 }

```

§ 431.13 **Symbols**

Proof QED symbol:

```

475 \newcommand{\qed}{\quad\the\qedsymbol}
476
477 \AtBeginDocument{
478 \ifundefined{LWR@orig@openbox}{
479 \LetLtxMacro\LWR@orig@openbox\openbox
480 \LetLtxMacro\LWR@orig@blacksquare\blacksquare
481 \LetLtxMacro\LWR@orig@Box\Box
482
483 \def\openbox{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
484 \def\blacksquare{\text{\HTMLUnicode{220E}}}% UTF-8 end-of-proof
485 \def\Box{\text{\HTMLUnicode{25A1}}}% UTF-8 white box
486
487 \appto\LWR@restoreorigformatting{%
488 \LetLtxMacro\openbox\LWR@orig@openbox%
489 \LetLtxMacro\blacksquare\LWR@orig@blacksquare%
490 \LetLtxMacro\Box\LWR@orig@Box%
491 }% appto
492 }{}% @ifundefined
493 }% AtBeginDocument

```

§ 431.14 **Cross-referencing**

`\thref {<label>}`

```

494 \newcommand*\thref}[1]{\cref{#1}}%

```

File 326 **lwarp-octave.sty**§ 432 Package **octave**

*(Emulates or patches code by ANDREW A. CASHNER.)*

Pkg octave octave is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{octave}[2017/10/31]

Remove the leading 1pt kern:

```

2 \RenewDocumentCommand{\@PrintTicks}{ m }{%
3 \kern-1pt% lwarp
4 \@TickNum = #1%
5 \loop
6 \@Tick{}%
7 \advance\@TickNum by -1
8 \ifnum\@TickNum > 0
9 \repeat
10 }

```

Use unicode for the prime character:

```
11 \RenewDocumentCommand{\@Tick}{\HTMLUnicode{2032}}
```

Catch the inline font:

```
12 \RenewDocumentCommand{\pitch}{ m o m }{%
13 \if@OctaveNumber%
14 {%
15 \pitchfont{%
16 \LWR@textcurrentfont{% lwarp
17 \MakeUppercase{#1}%
18 \IfValueTF{#2}{#2}{\textsubscript{#3}%
19 }%
20 }%
21 }%
22 \else%
23 {%
24 \pitchfont{%
25 \LWR@textcurrentfont{% lwarp
26 \@GetOctaveTick{#1}[#2]{#3}%
27 }%
28 }%
29 }%
30 \fi%
31 }
```

The original was hard to adapt to lwarp's handling of &.

```
32 \StartDefiningTabulars
33 \renewcommand{\octavetable}{%
34 \begin{tabular}{ll}
35 \octaveprimes \pitch{C}{0} & \octavenumbers \pitch{C}{0} \\
36 \octaveprimes \pitch{C}{1} & \octavenumbers \pitch{C}{1} \\
37 \octaveprimes \pitch{C}{2} & \octavenumbers \pitch{C}{2} \\
38 \octaveprimes \pitch{C}{3} & \octavenumbers \pitch{C}{3} \\
39 \octaveprimes \pitch{C}{4} & \octavenumbers \pitch{C}{4} \\
40 \octaveprimes \pitch{C}{5} & \octavenumbers \pitch{C}{5} \\
41 \octaveprimes \pitch{C}{6} & \octavenumbers \pitch{C}{6} \\
42 \octaveprimes \pitch{C}{7} & \octavenumbers \pitch{C}{7} \\
43 \end{tabular}
44 }
45 \StopDefiningTabulars
```

---

File 327 **lwarp-overpic.sty**

§ 433 Package **overpic**

(Emulates or patches code by ROLF NIEPRASCHK.)

Pkg overpic **overpic** is patched for use by lwarp.

 **scaling** The macros \overpicfontsize and \overpicfontskip are used during HTML genera-

tion. These are sent to `\fontsize` to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the `overpic` and `Overpic` environments.

See section 86.2 for the print-mode version of `\overpicfontsize` and `\overpicfontskip`.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{overpic}[2017/10/06]

2 \newcommand*{\overpicfontsize}{12}
3 \newcommand*{\overpicfontskip}{14}
4
5 \BeforeBeginEnvironment{overpic}{%
6 \begin{lateximage}%
7 \fontsize{\overpicfontsize}{\overpicfontskip}%
8 \selectfont%
9 }
10
11 \AfterEndEnvironment{overpic}{\end{lateximage}}
12
13 \BeforeBeginEnvironment{Overpic}{%
14 \begin{lateximage}%
15 \fontsize{\overpicfontsize}{\overpicfontskip}%
16 \selectfont%
17 }
18
19 \AfterEndEnvironment{Overpic}{\end{lateximage}}
```

---

File 328 **lwarp-pagegrid.sty**

§ 434 Package **pagegrid**

Pkg pagegrid pagegrid is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{pagegrid}[2016/05/16]

2 \newcommand*{\pagegridsetup}[1]{}
```

---

File 329 **lwarp-pagenote.sty**

§ 435 Package **pagenote**

Pkg pagenote pagenote works as-is, but the page option is disabled.

 **labels** Note that labels in page notes do not appear as expected, even in the print version.

**for HTML output:**

```

1 \DeclareOption{page}{}
2 \LWR@ProvidesPackagePass{pagenote}[2009/09/03]
```

For MATHJAX:

```

3 \begin{warpMathJax}
4 \appto\LWR@syncnotenumbers{\LWR@synconenotenummer{\LWRpagenote}{\thepagenote}}
5 \CustomizeMathJax{\def\LWRpagenote{1}}
6 \CustomizeMathJax{\newcommand{\pagenote}[2][\LWRpagenote]{\mathrm{#1}}}
7 \end{warpMathJax}

```

There is no `\pagenotemark`, so the following are not required:

```

\providecommand{\pagenotename}{pagenote}
\appto\LWR@syncnotenames{\LWR@synconenotename{\LWRpagenote}{\pagenotename}}

```

File 330 **lwarp-pagesel.sty**

§ 436 Package **pagesel**

Pkg pagesel pagesel is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pagesel}[2016/05/16]

File 331 **lwarp-paralist.sty**

§ 437 Package **paralist**

*(Emulates or patches code by BERND SCHANDL.)*

Pkg paralist paralist is supported with minor changes.

**for HTML output:** 1 \LWR@ProvidesPackagePass{paralist}[2017/01/22]

The compact environments are identical to the regular ones:

```

2 \LetLtxMacro\compactitem\itemize
3 \LetLtxMacro\compactenum\enumerate
4 \LetLtxMacro\compactdesc\description
5 \LetLtxMacro\endcompactitem\enditemize
6 \LetLtxMacro\endcompactenum\endenumerate
7 \LetLtxMacro\endcompactdesc\enddescription

```

For the inline environments, revert `\item` to its original print-mode version:

```

8 \AtBeginEnvironment{inparaitem}{\LetLtxMacro\item\LWR@origitem}
9 \AtBeginEnvironment{inparaenum}{\LetLtxMacro\item\LWR@origitem}
10 \AtBeginEnvironment{inparadesc}{\LetLtxMacro\item\LWR@origitem}

```

Manual formatting of the description labels:

```

11 \def\paradescriptionlabel#1{\normalfont\textbf{#1}}

```

File 332 **lwarp-parallel.sty**

§ 438 Package **parallel**

(Emulates or patches code by MATTHIAS ECKERMANN.)

Pkg parallel parallel is emulated.

Package options are ignored. Footnotes are treated as normal lwarp footnotes.

Environment option `c` gives side-by-side `<div>`s of class `minipage`, each of whose width is a percent depending on the given left and right widths, proportional to `\linewidth`.

Inside each environment, `\linewidth` and `\textwidth` are set for the print-output sizes.

for HTML output: Discard all options for lwarp-parallel:

```

1 \LWR@ProvidesPackageDrop{parallel}[2003/04/13]

2 \newcounter{LWR@parallel@Lwidth}
3 \newcounter{LWR@parallel@Rwidth}
4 \newcommand*\LWR@parallel@border}
5
6 \newenvironment*{Parallel}[3][[%
7 {%
8 \LWR@printpendingfootnotes%
9 \setlength{\linewidth}{\LWR@userstextwidth}%
10 \setlength{\textwidth}{\LWR@userstextwidth}%
11 \renewcommand*\LWR@parallel@border}{}%
12 \ifstrequal{#1}{v}%
13 {%
14 \renewcommand*\LWR@parallel@border}{ ; border-left: 2px solid black}%
15 }%
16 }%
17 \ifblank{#2}{%
18 \ifblank{#3}{% {}{}
19 \setcounter{LWR@parallel@Lwidth}{45}%
20 \setcounter{LWR@parallel@Rwidth}{45}%
21 }% {}{}
22 {% {}{x}
23 \setlength{\LWR@templengthone}{\linewidth-#3}%
24 \setcounter{LWR@parallel@Lwidth}{%
25 90*\ratio{\LWR@templengthone}{\linewidth}%
26 }%
27 \setcounter{LWR@parallel@Rwidth}{%
28 90*\ratio{#3}{\linewidth}%
29 }%
30 }% {}{x}
31 }% #2 blank
32 {% #2 non-blank

```

```

33 \ifblank{#3}{% {x}{}}
34 \setcounter{LWR@parallel@Lwidth}{%
35 90*\ratio{#2}{\linewidth}%
36 }%
37 \setlength{LWR@templengthone}{\linewidth-#2}%
38 \setcounter{LWR@parallel@Rwidth}{%
39 90*\ratio{LWR@templengthone}{\linewidth}%
40 }%
41 }% {x}{x}
42 {% {x}{x}
43 \setcounter{LWR@parallel@Lwidth}{%
44 90*\ratio{#2}{\linewidth}%
45 }%
46 \setcounter{LWR@parallel@Rwidth}{%
47 90*\ratio{#3}{\linewidth}%
48 }%
49 }% {x}{x}
50 }% #2 non-blank
51 }
52 {%
53 \ParallelAtEnd%
54 \renewcommand*{\ParallelAtEnd}{%
55 \LWR@printpendingfootnotes%
56 }
57 }
58 \newcommand*{\ParallelLText}[1]{%
59 \begin{BlockClass}[%
60 width:\arabic{LWR@parallel@Lwidth}\% ; % space
61 padding: .5ex 1\% ; % space
62]{minipage}%
63 #1%
64 \end{BlockClass}%
65 }
66
67 \newcommand*{\ParallelRText}[1]{%
68 \begin{BlockClass}[%
69 width:\arabic{LWR@parallel@Rwidth}\% ; % space
70 padding: .5ex 1\% ; % space
71 \LWR@parallel@border%
72]{minipage}%
73 #1%
74 \end{BlockClass}%
75 }
76
77 \newcommand*{\ParallelPar}{\LWR@printpendingfootnotes}
78
79 \newcommand*{\ParallelAtEnd}{}

```

---

File 333 **lwarp-parcolumns.sty**

§ 439 Package **parcolumns**

(Emulates or patches code by JONATHAN SAUER.)

Pkg parcolumns parcolumns is emulated.

rulebetween is honored. The other keys are ignored, including colwidths.

Each column is placed inside a <div> of class minipage, each of whose width is fixed at 85% divided by the number of columns. In most cases, this results in side-by-side minipages adapting to the browser width. Inside each minipage, `\linewidth`, `\textwidth`, and `\textheight` are set for a virtual 6 × 9 inch page, with `\linewidth` divided by the number of columns.

**for HTML output:** Discard all options for `lwarp-parcolumns`:

```

1 \RequirePackage{keyval}%
2
3 \LWR@ProvidesPackageDrop{parcolumns}[2004/11/25]

4 \newcounter{LWR@parcolumns@numcols}
5 \newcounter{LWR@parcolumns@thiscol}
6 \newcounter{LWR@parcolumns@width}
7 \newbool{LWR@parcolumns@started}
8 \newbool{LWR@parcolumns@rule}
9
10 \define@key{LWRparcols}{colwidths}{}
11 \define@key{LWRparcols}{distance}{}
12 \define@key{LWRparcols}{rulebetween}[true]{%
13 \setbool{LWR@parcolumns@rule}{#1}%
14 }
15 \define@key{LWRparcols}{nofirstindent}{}
16 \define@key{LWRparcols}{sloppy}{}
17 \define@key{LWRparcols}{sloppyspaces}{}
18
19 \newenvironment*{parcolumns}[2][
20 {%
21 \begin{LWR@setvirtualpage}*[#2]%
22 \setcounter{LWR@parcolumns@numcols}{#2}%
23 \setcounter{LWR@parcolumns@thiscol}{1}%
24 \boolfalse{LWR@parcolumns@started}%
25 \boolfalse{LWR@parcolumns@rule}%
26 \setcounter{LWR@parcolumns@width}{%
27 85/#2
28 }%
29 \setkeys{LWRparcols}{#1}%
30 }
31 {%

32 \colplacechunks%
33 \end{LWR@setvirtualpage}%
34 }
35
36 \newcommand{\LWR@parcolumns@onecol}[1]{%
37 \ifbool{LWR@parcolumns@started}%
38 {}%
39 {%
40 \LWR@htmldivclass{parcolumns}%
41 \booltrue{LWR@parcolumns@started}%

```

```

42 }%
43 \ifboolexpr{%
44 bool {LWR@parcolumns@rule} and
45 test {%
46 \ifnumgreater
47 {\value{LWR@parcolumns@thiscol}}
48 {1}
49 }%
50 }%
51 {\renewcommand{\LWR@tempone}{ ; border-left: 2px solid black}}%
52 {\renewcommand{\LWR@tempone}{}}%
53 \begin{BlockClass}[%
54 width:\arabic{LWR@parcolumns@width}\% ; % space
55 padding: .5ex 1\% ; % space
56 \LWR@tempone%
57]{minipage}%
58 #1%
59 \end{BlockClass}%
60 \addtocounter{LWR@parcolumns@thiscol}{1}%
61 }
62
63 \newcommand{\colchunk}[2][\value{LWR@parcolumns@thiscol}]{%
64 \whileboolexpr{%
65 test {%
66 \ifnumcomp%
67 {\value{LWR@parcolumns@thiscol}}
68 {<}
69 {#1}%
70 }%
71 }{%
72 \LWR@parcolumns@onecol{}}%
73 }%
74 \LWR@parcolumns@onecol{#2}%
75 }
76
77 \newcommand*{\colplacechunks}{%
78 \ifbool{LWR@parcolumns@started}%
79 {%
80 \LWR@htmldivclassend{div}%
81 \boolfalse{LWR@parcolumns@started}%
82 }%
83 }%
84 \setcounter{LWR@parcolumns@thiscol}{1}%
85 }

```

---

File 334 **lwarp-parnotes.sty**

§ 440 Package **parnotes**

(Emulates or patches code by CHELSEA HUGHES.)

Pkg parnotes parnotes is supported with some patches.

for HTML output:

```

1 \LWR@ProvidesPackagePass{parnotes}[2016/08/15]

2 \Long\def\PN@parnote@real#1#2{%
3 \parnotemark{#1}%
4 % Unless this is the first parnote in \PN@text, add a separator first
5 \unless\ifx\PN@text\@empty\g@addto@macro\PN@text{\parnoteintercmd}\fi
6 % Redefine \@currentlabel to the parnote label, so \label works
7 \g@addto@macro\PN@text{%
8 \phantomsection%
9 \def\@currentlabel{#1}%
10 \def\cref@currentlabel{% lwarp
11 [parnotemark][\arabic{parnotemark}][\theparnotemark%
12]%
13 }%
14 \g@addto@macro\PN@text{%
15 \LWR@textcurrentfont{% lwarp
16 \parnotemark{#1}\nolinebreak\thinspace#2%
17 }%
18 }%
19 }
20
21 \def\PN@parnotes@real{%
22 % We call \par later, so this avoids recursion with \PN@parnotes@auto
23 \PN@inparnotestruer
24 \unless\ifvmode\par\fi
25 % Avoid page breaks between a paragraph and its parnotes
26 \nopagebreak\addvspace{\parnotevskip}%
27 \LWR@forcenewpage% lwarp
28 \begin{BlockClass}{footnotes}% lwarp
29 {\parnotefmt{\PN@text}\par}%
30 \end{BlockClass}% lwarp
31 \global\def\PN@text{}%
32 \addvspace{\parnotevskip}%
33 %
34 % These can be enabled or disabled by package options
35 %
36 \PN@disable@indent
37 \PN@reset@optional
38 \PN@inparnotesfalse
39 }
40
41 \AtBeginDocument{
42 \crefname{parnotemark}{paragraph note}{paragraph notes}
43 \Crefname{parnotemark}{Paragraph note}{Paragraph notes}
44 }

```

For MATHJAX:

```

45 \begin{warpMathJax}
46 \providecommand{\parnotename}{parnote}
47 \appto\LWR@syncnotenumbers{%
48 \addtocounter{parnotemark}{-1}% specific to parnotes
49 \LWR@synconenotenummer{LWRparnote}{\theparnotemark}%
50 \addtocounter{parnotemark}{1}% specific to parnotes
51 }

```

---

```

52 \appto\LWR@syncnotenames{\LWR@synconenotename{LWRparnote}{\parnotename}}
53 \CustomizeMathJax{\def\LWRparnote{1}}
54 \CustomizeMathJax{\newcommand{\parnote}[2][\LWRparnote]{{}^{\mathrm{#1}}}}
55 \CustomizeMathJax{\newcommand{\parnotemark}[1][\LWRparnote]{{}^{\mathrm{#1}}}}
56 \end{warpMathJax}

```

---

File 335 **lwarp-parskip.sty**

§ 441 Package **parskip**

Pkg parskip parskip is ignored.

**for HTML output:** Discard all options for lwarp-parskip.

```
1 \LWR@ProvidesPackageDrop{parskip}[2001/04/09]
```

---

File 336 **lwarp-pbox.sty**

§ 442 Package **pbox**

*(Emulates or patches code by SIMON LAW.)*

Pkg pbox pbox is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pbox}[2011/12/07]

```

2 \NewDocumentCommand{\pbox}{0{t} 0{ } 0{t} m +m}{%
3 \global\booltrue{LWR@minipagefullwidth}%
4 \parbox[#1][#2][#3]{#4}{#5}%
5 }
6
7 \newcommand{\settomwidth}[3][\columnwidth]{%
8 \settowidth{#2}{#3}%
9 }
10
11 \newcommand{\widthofpbox}[1]{%
12 \widthof{#1}%
13 }

```

---

File 337 **lwarp-pdfcol.sty**

§ 443 Package **pdfcol**

Pkg pdfcol pdfcol is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pdfcol}[2018/11/01]  
2

```

3 \ltx@newif\ifpdfcolAvailable
4 \pdfcolAvailablefalse
5
6 \def\pdfcolErrorNoStacks{
7 \PackageInfo{lwarp-pdfcol}{Ignoring pdfcol for HTML output.}
8 }
9
10 \def\pdfcolInitStack#1{%
11
12 \long\def\pdfcolIfStackExists#1#2#3{#3}%
13
14 \def\pdfcolSwitchStack#1{%
15
16 \def\pdfcolSetCurrentColor{%
17
18 \def\pdfcolSetCurrent#1{%

```

---

File 338 **lwarp-pdfcolfoot.sty**

§ 444 Package **pdfcolfoot**

Pkg pdfcolfoot pdfcolfoot is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{pdfcolfoot}[2016/05/16]
2
3 \newcommand*{\pdfcolfoot@switch}{}
4
5 \newcommand*{\pdfcolfoot@current}{}

```

---

File 339 **lwarp-pdfcolmk.sty**

§ 445 Package **pdfcolmk**

Pkg pdfcolmk pdfcolmk is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{pdfcolmk}[2016/05/16]

```

---

File 340 **lwarp-pdfcolparallel.sty**

§ 446 Package **pdfcolparallel**

Pkg pdfcolparallel pdfcolparallel is ignored.

**for HTML output:**

```

1 \RequirePackage{keyval}%
2
3 \LWR@ProvidesPackageDropA{pdfcolparallel}{2016/05/16}

```

Pass options to parallel:

```
4 \DeclareOption*{%
5 \PassoptionsToPackage{\CurrentOption}{parallel}%
6 }
```

Process the options:

```
7 \LWR@ProvidesPackageDropB
```

Require parallel with the given options:

```
8 \RequirePackage{parallel}[2003/04/13]
```

Ignore the new key:

```
9 \define@key{parallel}{rulebetweencolor}{}
```

File 341 **lwarp-pdfcolparcolumns.sty**

§ 447 Package **pdfcolparcolumns**

Pkg pdfcolparcolumns pdfcolparcolumns is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDropA{pdfcolparcolumns}{2016/05/16}

Pass options to parcolumns:

```
2 \DeclareOption*{%
3 \PassoptionsToPackage{\CurrentOption}{parcolumns}%
4 }
```

Process the options:

```
5 \LWR@ProvidesPackageDropB
```

Require parcolumns with the given options:

```
6 \RequirePackage{parcolumns}[2004/11/25]
```

Ignore the new key:

```
7 \define@key{LWRparcols}{rulebetweencolor}{}
```

File 342 **lwarp-pdfcomment.sty**

§ 448 Package **pdfcomment**

Pkg pdfcomment pdfcomment is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pdfcomment}[2016/06/13]

```

2 \newenvironment{pdfsidelinecomment}[2][{}]{ }
3 \newcommand{\pdfcomment}[2][{}]{ }
4 \newcommand{\pdfmargincomment}[2][{}]{ }
5 \newcommand{\pdfmarkupcomment}[3][{}]{#2}
6 \newcommand{\pdfreetextcomment}[2][{}]{ }
7 \newcommand{\pdfsquarecomment}[2][{}]{ }
8 \newcommand{\pdfcirclecomment}[2][{}]{ }
9 \newcommand{\pdflinecomment}[2][{}]{ }
10 \newcommand{\pdftooltip}[3][{}]{#2}
11 \newcommand{\pdfcommentsetup}[2][{}]{ }
12 \newcommand{\listofpdfcomments}[1][{}]{ }
13 \newcommand{\setliststyle}[1][{}]{ }
14 \newcommand{\defineliststyle}[2][{}]{ }
15 \newcommand{\defineavatar}[2][{}]{ }
16 \newcommand{\definestyle}[2][{}]{ }

```

For MATHJAX:

```

17 \begin{warpMathJax}
18 \CustomizeMathJax{\newcommand{\pdfmarkupcomment}[3][{}]{#2}}
19 \CustomizeMathJax{\newcommand{\pdftooltip}[3][{}]{#2}}
20 \end{warpMathJax}

```

---

File 343 **lwarp-pdfcrypt.sty**

§ 449 Package **pdfcrypt**

Pkg pdfcrypt pdfcrypt is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pdfcrypt}[2016/05/16]

```

2 \newcommand*{\pdfcryptsetup}[1][{}]{ }

```

---

File 344 **lwarp-pdflscope.sty**

§ 450 Package **pdflscope**

Pkg pdflscope pdflscope is ignored.

**for HTML output:** Discard all options for lwarp-pdflscope:

```

1 \LWR@ProvidesPackageDrop{pdflscope}[2016/05/14]

```

---

File 345 **lwarp-pdfmarginpar.sty**

§ 451 Package **pdfmarginpar**

Pkg pdfmarginpar pdfmarginpar is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pdfmarginpar}[2011/08/05]

```
2 \newcommand{\pdfmarginpar}[2][{}]{
3 \newcommand{\pdfmarginparset}[1]{}
```

---

File 346 **lwarp-pdfpages.sty**

§ 452 Package **pdfpages**

*(Emulates or patches code by ANDREAS MATTHIAS.)*

Pkg pdfpages pdfpages is patched for use by lwarp.

Option link and linkname work:

---

```
\hyperlink{<filename>.pdf.<pagenumber>}{some text}
\hyperlink{<linkname>.<pagenumber>}{some text}
```

---

Options which make no sense in HTML are disabled.

**for HTML output:** 1 \LWR@ProvidesPackagePass{pdfpages}[2017-10-31]

Disable option which have no meaning for HTML output:

```
2 \define@key{pdfpages}{fitpaper}[false]{}
3 \define@key{pdfpages}{landscape}[false]{}
4 \define@key{pdfpages}{openright}[false]{}
5 \define@key{pdfpages}{signature}{}
6 \define@key{pdfpages}{signature*}{}
7 \define@key{pdfpages}{booklet}[false]{}
8 \define@key{pdfpages}{rotateoversize}[false]{}
9 \define@key{pdfpages}{doublepages}[false]{}
10 \define@key{pdfpages}{doublepageswist}[false]{}
11 \define@key{pdfpages}{doublepageswistodd}[false]{}
12 \define@key{pdfpages}{doublepageswist*}[false]{}
13 \define@key{pdfpages}{doublepageswistodd*}[false]{}
14 \define@key{pdfpages}{duplicatepages}[2]{}
15 \define@key{pdfpages}{thread}[false]{}
16 \define@key{pdfpages}{threadname}{}

```

```

17 \define@key{pdfpages}{linkfit}{}
18 \define@key{pdfpages}{linktodoc}[false]{}
19 \define@key{pdfpages}{linktodocfit}{}
20 \define@key{pdfpages}{linkfilename}{}
21 \define@key{pdfpages}{survey}[false]{}
22 \define@key{pdfpages}{survey-nolink}[false]{}
23 \define@key{pdfpages}{newwindow}[false]{}

```

Use print mode while measuring the page numbers:

```

24 \xpretocmd{\AM@getpagecount}{\LWR@restoreorigformatting}{}{}

```

Emulate a bit of `eso-pic`:

```

25 \newif\ifESO@texcoord
26
27 \newcommand{\ESO@HookIIBG}{}
28
29 \renewcommand{\AM@AddToShipoutPicture}{\g@addto@macro\ESO@HookIIBG}
30
31 \renewcommand{\ClearShipoutPicture}{}

```

`\LWR@esopic@newpage` At each `\newpage`.

```

32 \newcommand*{\LWR@esopic@newpage}{%

```

Is there something to draw?

```

33 \ifdefvoid{\ESO@HookIIBG}%
34 {}%
35 {%

```

If the `link` option was specified, add a hyper target:

```

36 \ifAM@link%
37 \hypertarget{\AM@linkname.\AM@page}{}%
38 \fi%

```

Draw inside a picture environment of the size of a virtual page:

```

39 \begingroup%
40 \setlength{\unitlength}{1in}%
41 \begin{picture}(8,10.5)%
42 \ESO@HookIIBG%
43 \end{picture}%
44 \endgroup%
45 \global\let\ESO@HookIIBG\@empty%
46 }
47 }

```

`\AM@output` Patched to use `\LWR@esopic@newpage`.

```

48 \xpatchcmd{\AM@output}
49 {\newpage}
50 {\LWR@esopic@newpage}
51 {}

```

```

52 {\LWR@patcherror{pdfpages}{AM@output-1}}
53
54 \xpatchcmd{\AM@output}
55 {\newpage}
56 {\LWR@esopic@newpage}
57 {}
58 {\LWR@patcherror{pdfpages}{AM@output-2}}
59
60 \xpatchcmd{\AM@output}
61 {\newpage}
62 {\LWR@esopic@newpage}
63 {}
64 {\LWR@patcherror{pdfpages}{AM@output-3}}

```

`\includepdf` Patched to set the user's paper size.

```

65 \xpretocmd{\includepdf}{%
66 \begingroup%
67 \setlength{\paperwidth}{\LWR@userspaperwidth}%
68 \setlength{\paperheight}{\LWR@userspaperheight}%
69 }{}{}
70
71 \xapptocmd{\includepdf}{%
72 \endgroup%
73 }{}{}

```

`\includepdfmerge` Patched to set the user's paper size.

```

74 \xpretocmd{\includepdfmerge}{%
75 \begingroup%
76 \setlength{\paperwidth}{\LWR@userspaperwidth}%
77 \setlength{\paperheight}{\LWR@userspaperheight}%
78 }{}{}
79
80 \xapptocmd{\includepdfmerge}{%
81 \endgroup%
82 }{}{}

```

`\AM@hyper@begin@i` Hyper links are created by `\LWR@esopic@newpage`, so don't create them here:

```

83 \renewcommand{\AM@hyper@begin@i}{}

```

---

File 347 **lwarp-pdfprivacy.sty**

§ 453 Package **pdfprivacy**

Pkg pdfprivacy pdfprivacy is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pdfprivacy}[2017/12/03]

---

File 348 **lwarp-pdfrender.sty**

§ 454 Package **pdfrender**

Pkg pdfrender pdfrender is allowed during HTML, but it has no effect on HTML text output. pdfrender is enabled for use with xfakebold, and it is enabled during HTML so that it may be in use when an SVG math image is started. I.e. xfakebold's `\setBold` may be used outside of a math expression and still be detected when the math begins.

The lwarp-pdfrender package is present because it used to disable pdfrender, so this newer version is to overwrite older versions.

**for HTML output:** `1 \LWR@ProvidesPackagePass{pdfrender}[2019/12/29]`

---

File 349 **lwarp-pdfsync.sty**

§ 455 Package **pdfsync**

*(Emulates or patches code by J. LAURENS.)*

Pkg pdfsync pdfsync is ignored.

**for HTML output:** Discard all options for lwarp-pdfsync:

```
1 \LWR@ProvidesPackageDrop{pdfsync}[2008/01/26]
2 \newcommand*{\pdfsync}{}
3 \newcommand*{\pdfsyncstart}{}
4 \newcommand*{\pdfsyncstop}{}

```

---

File 350 **lwarp-pdftricks.sty**

§ 456 Package **pdftricks**

*(Emulates or patches code by C. V. RADHAKRISHNAN, C. V. RAJAGOPAL, ANTOINE CHAMBERT-LOIR.)*

Pkg pdftricks pdftricks is patched for use by lwarp.

 **convert image files** The pdftricks image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

```
Enter => lwarpmk pdftosvg <jobname>-fig*.pdf
```

**for HTML output:** `1 \LWR@ProvidesPackagePass{pdftricks}[2003/08/10]`

Reuse the print-mode images:

```
2 \def\PDFTfigname{\BaseJobname-fig\thepsfig}
```

If the .pdf images have not yet been converted to .svg then an error about a missing file will occur. Warn the user to convert the images.

```
3 \PackageWarning{lwarp-pdftricks}{
4 When the pdftricks images change,
5 remember to convert PDF images to SVG using 'lwarpmk pdftosvg *-fig.pdf',
6 }
7
8 \AfterEndDocument{\typeout{***}}
9 \AfterEndDocument{\typeout{*** Note: If pdftricks images are not found, new, or updated,}}
10 \AfterEndDocument{\typeout{*** \space use 'lwarpmk pdftosvg \BaseJobname-fig*.pdf'}}
11 \AfterEndDocument{\typeout{***}}
```

---

File 351 **lwarp-pdfx.sty**

§ 457 Package **pdfx**

Pkg pdfx pdfx is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pdfx}[2017/05/18]

---

File 352 **lwarp-perpage.sty**

§ 458 Package **perpage**

*(Emulates or patches code by DAVID KASTRUP.)*

Pkg perpage **perpage** is mostly ignored, but support is added for footnote counters.

There is no page number in HTML, so most counters are not reset. If the document redefines \the<countername> to include \theperpage, it is necessary to place that redefinition inside a warpprint environment to avoid modifying the HTML definitions.

\AddAbsoluteCounter must not be inside warpprint, as the counter must be added for HTML also, although it is not incremented.

[footnote numbering](#) To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for \alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

```

for HTML output: 1 \LWR@ProvidesPackageDrop{perpage}[2014/10/25]

2 \newcommand\AddAbsoluteCounter[1]
3 {
4 \@ifundefined{c@abs#1}{%
5 \expandafter\newcount\csname c@abs#1\endcsname
6 \global\value{abs#1}\@ne
7 % \global\expandafter\let\csname cl@abs#1\endcsname\@empty
8 \expandafter\xdef\csname theabs#1\endcsname{%
9 % \noexpand\number \csname c@abs#1\endcsname
10 }%
11 % \global\@namedef{c@pabs@#1}{\pp@cl@begin
12 % \stepcounter{abs#1}%
13 % \pp@cl@end}%
14 % \@addtoreset{pabs@#1}{#1}
15 }
16 {}
17 }
18
19 \AddAbsoluteCounter{page}
20 \def\theabspage{1}
21
22 \newcommand*\MakePerPage[2][1]{%
23 \ifltxcounter{#2Reset}{%
24 \setcounter{#2Reset}{#1}%
25 }{
26
27 }%
28 }
29
30 \newcommand*\MakeSorted[1]{%
31
32 \newcommand*\MakeSortedPerPage[2][1]{%
33 \ifltxcounter{#2Reset}{%
34 \setcounter{#2Reset}{#1}%
35 }{
36 }%
37 }
38
39 \newcommand*\theperpage{1}

```

---

File 353 **lwarp-pfnote.sty**

§ 459 Package **pfnote**

Pkg pfnote **pfnote** is ignored.

**pfnote** While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page

 **pfnote numbers**

number to match the printed version, as HTML has no concept of page numbers. `lwarp` therefore uses continuous footnote numbering even for `pfnote`.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pfnote}[1999/07/14]

---

File 354 **lwarp-phfqit.sty**

§ 460 Package **phfqit**

*(Emulates or patches code by PHILIPPE FAIST.)*

Pkg phfqit `phfqit` is patched for use by `lwarp`.

**for HTML output:** 1 \LWR@ProvidesPackagePass{phfqit}[2017/08/16]

```

2 \LetLtxMacro\LWR@origbitstring\bitstring
3
4 \renewcommand\bitstring[1]{%
5 \InlineClass[%
6 text-decoration: overline underline ;
7]{bitstring}{#1}%
8 % \phfqit@bitstring{#1}%
9 }
10
11 \appto\LWR@restoreorigformatting{%
12 \LetLtxMacro\bitstring\LWR@origbitstring%
13 }
```

---

File 355 **lwarp-physics.sty**

§ 461 Package **physics**

*(Emulates or patches code by SERGIO C. DE LA BARRERA.)*

Pkg physics `physics` works as-is for HTML with SVG math.

For MATHJAX, the MATHJAX v3 `physics` extension is used.

**for HTML output:** 1 \LWR@ProvidesPackagePass{physics}% No date is provided by the package.

```

2 \begin{warpMathJax}
3 \PackageWarningNoLine{lwarp, physics}{The MathJax v3 extension will be used}
4 \CustomizeMathJax{\require{physics}}
5 \end{warpMathJax}
```

File 356 **lwarp-physunits.sty**

§ 462 Package **physunits**

(Emulates or patches code by BRIAN W. MULLIGAN.)

Pkg physunits **physunits** is supported as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{physunits}[2020/03/26]

2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{physunits}
4
5 \CustomizeMathJax{\newcommand{\micro}{\mu}}
6 \CustomizeMathJax{\newcommand{\V}[1][]{\, \mathrm{#1V}}}
7 \CustomizeMathJax{\newcommand{\Volt}[1][]{\, \mathrm{#1V}}}
8 \CustomizeMathJax{\newcommand{\Coulomb}[1][]{\, \mathrm{#1C}}}
9 \CustomizeMathJax{\newcommand{\esu}{\, \mathrm{esu}}}
10 \CustomizeMathJax{\newcommand{\Ohm}[1][]{\, \mathrm{#1\Omega}}}
11 \CustomizeMathJax{\newcommand{\Amp}[1][]{\, \mathrm{#1A}}}
12 \CustomizeMathJax{\newcommand{\Farad}[1][]{\, \mathrm{#1F}}}
13 \CustomizeMathJax{\newcommand{\Tesla}[1][]{\, \mathrm{#1T}}}
14 \CustomizeMathJax{\newcommand{\Gauss}[1][]{\, \mathrm{#1G}}}
15 \CustomizeMathJax{\newcommand{\Henry}[1][]{\, \mathrm{#1H}}}
16 \CustomizeMathJax{\newcommand{\eV}[1][]{\, \mathrm{#1eV}}}
17 \CustomizeMathJax{\newcommand{\keV}{\, \mathrm{keV}}}
18 \CustomizeMathJax{\newcommand{\MeV}{\, \mathrm{MeV}}}
19 \CustomizeMathJax{\newcommand{\J}[1][]{\, \mathrm{#1J}}}
20 \CustomizeMathJax{\newcommand{\Joule}[1][]{\, \mathrm{#1J}}}
21 \CustomizeMathJax{\newcommand{\erg}{\, \mathrm{erg}}}
22 \CustomizeMathJax{\newcommand{\kcal}{\, \mathrm{kcal}}}
23 \CustomizeMathJax{\newcommand{\Cal}{\, \mathrm{Cal}}}
24 \CustomizeMathJax{\newcommand{\calorie}[1][]{\, \mathrm{#1cal}}}
25 \CustomizeMathJax{\newcommand{\BTU}{\, \mathrm{BTU}}}
26 \CustomizeMathJax{\newcommand{\tnt}{\, \mathrm{ton\, of\, TNT}}}
27 \CustomizeMathJax{\newcommand{\Watt}[1][]{\, \mathrm{#1W}}}
28 \CustomizeMathJax{\newcommand{\hpi}{\, \mathrm{hp(I)}}}
29 \CustomizeMathJax{\newcommand{\hpm}{\, \mathrm{hp(M)}}}
30 \CustomizeMathJax{\newcommand{\hp}{\, \mathrm{hp}}}
31 \CustomizeMathJax{\newcommand{\meter}[1][]{\, \mathrm{#1m}}}
32 \CustomizeMathJax{\newcommand{\m}[1][]{\, \mathrm{#1m}}}
33 \CustomizeMathJax{\newcommand{\km}{\, \mathrm{km}}}
34 \CustomizeMathJax{\newcommand{\au}{\, \mathrm{au}}}
35 \CustomizeMathJax{\newcommand{\pc}[1][]{\, \mathrm{#1pc}}}
36 \CustomizeMathJax{\newcommand{\ly}[1][]{\, \mathrm{#1ly}}}
37 \CustomizeMathJax{\newcommand{\cm}{\, \mathrm{cm}}}
38 \CustomizeMathJax{\newcommand{\nm}{\, \mathrm{nm}}}
39 \CustomizeMathJax{\newcommand{\ft}{\, \mathrm{ft}}}
40 \CustomizeMathJax{\newcommand{\inch}{\, \mathrm{in}}}
41 \CustomizeMathJax{\newcommand{\mi}{\, \mathrm{mi}}}
42 \CustomizeMathJax{\newcommand{\s}[1][]{\, \mathrm{#1s}}}

```

```

43 \CustomizeMathJax{\newcommand{\Sec}[1][]{\, \mathrm{#1s}}}
44 \CustomizeMathJax{\newcommand{\Min}{\, \mathrm{min}}}
45 \CustomizeMathJax{\newcommand{\h}{\, \mathrm{h}}}
46 \CustomizeMathJax{\newcommand{\y}[1][]{\, \mathrm{#1y}}}
47 \CustomizeMathJax{\newcommand{\Day}{\, \mathrm{d}}}
48
49 \CustomizeMathJax{\newcommand{\gm}[1][]{\, \mathrm{#1g}}}
50 \CustomizeMathJax{\newcommand{\kg}{\, \mathrm{kg}}}
51 \CustomizeMathJax{\newcommand{\lb}{\, \mathrm{lb}}}
52 \CustomizeMathJax{\newcommand{\amu}{\, \mathrm{amu}}}
53 \CustomizeMathJax{\newcommand{\N}[1][]{\, \mathrm{#1N}}}
54 \CustomizeMathJax{\newcommand{\Newton}[1][]{\, \mathrm{#1N}}}
55 \CustomizeMathJax{\newcommand{\dyne}[1][]{\, \mathrm{#1dyn}}}
56 \CustomizeMathJax{\newcommand{\lbf}{\, \mathrm{lbf}}}
57 \CustomizeMathJax{\newcommand{\kmps}{\, \mathrm{km}\, \mathrm{s}^{-1}}}
58 \CustomizeMathJax{\newcommand{\kmph}{\, \mathrm{km}\, \mathrm{h}^{-1}}}
59 \CustomizeMathJax{\newcommand{\mps}[1][]{\, \mathrm{#1m}\, \mathrm{s}^{-1}}}
60 \CustomizeMathJax{\newcommand{\miph}{\, \mathrm{mi}\, \mathrm{h}^{-1}}}
61 \CustomizeMathJax{\newcommand{\kts}{\, \mathrm{kts}}}
62
63 \CustomizeMathJax{\newcommand{\mpss}[1][]{\, \mathrm{#1m}\, \mathrm{s}^{-2}}}
64 \CustomizeMathJax{\newcommand{\gacc}{\, \mathrm{g}}}
65 \CustomizeMathJax{\newcommand{\ftpss}{\, \mathrm{ft}\, \mathrm{s}^{-2}}}
66 \CustomizeMathJax{\newcommand{\K}[1][]{\, \mathrm{#1K}}}
67 \CustomizeMathJax{\newcommand{\Kelvin}[1][]{\, \mathrm{#1K}}}
68 \CustomizeMathJax{\newcommand{\Celsius}{\, ^\circ\mathrm{C}}}
69 \CustomizeMathJax{\newcommand{\Rankine}{\, ^\circ\mathrm{R}}}
70 \CustomizeMathJax{\newcommand{\Fahrenheit}{\, ^\circ\mathrm{F}}}
71
72 \CustomizeMathJax{\newcommand{\rpm}{\, \mathrm{rev}\, \mathrm{Min}^{-1}}}
73
74 \CustomizeMathJax{\newcommand{\Hz}[1][]{\, \mathrm{#1Hz}}}
75 \CustomizeMathJax{\newcommand{\barP}[1][]{\, \mathrm{#1bar}}}
76 \CustomizeMathJax{\newcommand{\atm}{\, \mathrm{atm}}}
77 \CustomizeMathJax{\newcommand{\Pa}[1][]{\, \mathrm{#1Pa}}}
78 \CustomizeMathJax{\newcommand{\mmHg}{\, \mathrm{mmHg}}}
79 \CustomizeMathJax{\newcommand{\inHg}{\, \mathrm{inHg}}}
80 \CustomizeMathJax{\newcommand{\lbsi}{\, \mathrm{psi}}}
81 \CustomizeMathJax{\newcommand{\lbsf}{\, \mathrm{psf}}}
82 \CustomizeMathJax{\newcommand{\Ba}[1][]{\, \mathrm{#1Ba}}}
83 \CustomizeMathJax{\newcommand{\Torr}[1][]{\, \mathrm{#1Torr}}}
84 \CustomizeMathJax{\newcommand{\mol}{\, \mathrm{mol}}}
85 \end{warpMathJax}

```

---

File 357 **lwarp-picinpar.sty**

§ 463 Package **picinpar**

(Emulates or patches code by FRIEDHELM SOWA.)

Pkg picinpar picinpar is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass{picinpar}% No date is assigned.

The window is floated by a BlockClass style.

```

2 \long\def\LWR@HTML@window[#1,#2,#3,#4] {%
3 \if #2r%
4 \begin{BlockClass}[float:right]{marginblock}%
5 \else%
6 \begin{BlockClass}[float:left]{marginblock}%
7 \fi%
8 #3\par%
9 #4%
10 \end{BlockClass}%
11 }
12
13 \def\endLWR@HTML@window{}
14
15 \LWR@formattedenv{window}

```

The framepic and wframepic are placed inside a BlockClass of class framebox.

```

16 \def\LWR@HTML@framepic#1{%
17 \begin{BlockClass}{framebox}
18 \expandafter\box\csname #1box\endcsname%
19 \end{BlockClass}
20 }
21 \LWR@formatted{framepic}

22 \def\LWR@HTML@wframepic#1{%
23 \begin{BlockClass}{framebox}
24 \expandafter\box\csname #1box\endcsname%
25 \end{BlockClass}
26 }
27 \LWR@formatted{wframepic}

```

The caption is placed inside a BlockClass of class figurecaption.

```

28 \long\def\LWR@HTML@@makewincaption#1#2{%
29 \begin{BlockClass}{figurecaption}
30 #1: #2
31 \end{BlockClass}
32 }
33 \LWR@formatted{@makewincaption}

```

With HTML output, figwindow and tabwindow must not pre-decrement their counters.

```

34 \long\def\LWR@HTML@figwindow[#1,#2,#3,#4] {%
35 % \advance\c@figure -1
36 \window[#1,#2,{#3},{\def\capttype{figure}}%
37 \wincaption#4\par] }
38
39 \def\endLWR@HTML@figwindow{\endwindow}
40
41 \LWR@formattedenv{figwindow}

```

For `tabwindow`, to change the catcode of `&`, `\StartDefiningTabulars` is used before absorbing the arguments, and `\EndDefiningTabulars` is used at the end of the environment.

```

42 \long\def\LWR@HTML@subtabwindow[#1,#2,#3,#4] {%
43 % \advance\c@table -1
44 \window[#1,#2,{#3},{\def\@capttype{table}%
45 \wincaption#4\par}] }
46
47 \newcommand*\LWR@HTML@tabwindow{%
48 \StartDefiningTabulars%
49 \LWR@HTML@subtabwindow%
50 }
51
52 \def\endLWR@HTML@tabwindow{%
53 \endwindow%
54 \StopDefiningTabulars%
55 }
56
57 \LWR@formattedenv{tabwindow}

```

---

File 358 **lwarp-pifont.sty**

§ 464 Package **pifont**

(Emulates or patches code by WALTER SCHMIDT.)

Pkg pifont **pifont** is patched for use by **lwarp**.

Hashed inline images are used, as there may not be Unicode support for all icons.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{pifont}[2005/04/12]
2 \renewcommand{\Pisymbol}[2]{%
3 \begin{lateximage}*[Pisymbol][pisymbol#1#2]%
4 {\Pifont{#1}\char#2}%
5 \end{lateximage}%
6 }
7
8 \newcommand*\LWR@HTML@Pifill}[2]{
9 \Pisymbol{#1}{#2} \Pisymbol{#1}{#2} \Pisymbol{#1}{#2}
10 }
11 \LWR@formatted{Pifill}
12
13 \newcommand*\LWR@HTML@Piline}[2]{%
14 \par\noindent\hspace*{0.5in}
15 \Pifill{#1}{#2} \Pifill{#1}{#2} \Pifill{#1}{#2}
16 }
17 \LWR@formatted{Piline}

```

---

File 359 **lwarp-placeins.sty**

§ 465 Package **placeins**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg placeins placeins is ignored.

Discard all options for lwarp-placeins:

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{placeins}[2005/04/18]
2 \newcommand*{\FloatBarrier}{}

```

---

File 360 **lwarp-plarydshln.sty**

§ 466 Package **plarydshln**

Pkg plarydshln plarydshln is emulated by lwarp-arydshln.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{plarydshln}[2018/10/20]
2 \LWR@origRequirePackage{lwarp-arydshln}

```

---

File 361 **lwarp-plext.sty**

§ 467 Package **plext**

Pkg plext plext is preloaded by jrtarticle and related classes.

**for HTML output:**

```
1 \LWR@loadbefore{plext}
2
3 \LWR@ProvidesPackagePass{plext}[2017/07/21]

4 \let\tate\relax
5
6 \DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}
7
8 % \layoutfloat(width,height)[pos]#4
9 \DeclareDocumentCommand{\layoutfloat}{d() o m}{}
10
11 % \DeclareLayoutCaption{type} <dir>(width)[pos1pos2]
12 \DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}
13
14 \LetLtxMacro\pcaption\caption

```

```

15
16 % \layoutcaption<dir>(width)[pos]
17 \DeclareDocumentCommand{\layoutcaption}{d<> d() o{}}
18
19 \let\captiondir\relax

```

Add the optional <t/y> direction:

```

20 \RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{ } O{t} m}
21 {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
22 {\endLWR@HTML@sub@minipage}
23
24 \RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{ } O{t} m +m}
25 {
26 \LWR@traceinfo{parbox of width #4}%
27 \begin{minipage}[#2][#3][#4]{#5}%
28 #6
29 \end{minipage}%
30 }
31
32 % \pbox <t/y> [width] [l/r] {contents}
33 \RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
34 \global\booltrue{LWR@minipagefullwidth}%
35 \parbox{#2}{#4}%
36 }

```

picture, as modified by pext, is encapsulated by the lwarp core.

---

File 362 **lwarp-plextarydshln.sty**

§ 468 Package **plextarydshln**

Pkg plextarydshln plextarydshln is emulated by lwarp-arydshln.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{plextarydshln}[2018/10/20]

2 \LWR@origRequirePackage{lwarp-arydshln}

---

File 363 **lwarp-plextcolortbl.sty**

§ 469 Package **plextcolortbl**

Pkg plextcolortbl plextcolortbl is emulated by lwarp-colortbl.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{plextcolortbl}[2018/09/19]

2 \LWR@origRequirePackage{lwarp-colortbl}

File 364 **lwarp-plimsoll.sty**

§ 470 Package **plimsoll**

*(Emulates or patches code by PALLE JØRGENSEN.)*

Pkg plimsoll plimsoll is used as-is for SVG math, and emulated for MATHJAX.

The circ option is honored. For MATHJAX, \plimsollsans is the same as \plimsollroman.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{plimsoll}[2020/10/09]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\plimsollroman}{\unicode{x029B5}}}
4
5 \CustomizeMathJax{\let\plimsoll\plimsollroman}
6 \CustomizeMathJax{\let\plimsollsans\plimsoll}
7
8 \ifdefstring{\stst}{^{\circ}}
9 {\CustomizeMathJax{\newcommand{\stst}{^{\circ}}}}
10 {\CustomizeMathJax{\newcommand{\stst}{^{\plimsoll}}}}
11 \end{warpMathJax}

```

File 365 **lwarp-prelim2e.sty**

§ 471 Package **prelim2e**

*(Emulates or patches code by MARTIN SCHRÖDER.)*

Pkg prelim2e prelim2e is ignored.

**for HTML output:** Discard all options for lwarp-prelim2e:

```

1 \LWR@ProvidesPackageDrop{prelim2e}[2009/05/29]

2 \newcommand{\PrelimText}{}
3 \newcommand{\PrelimTextStyle}{}
4 \newcommand{\PrelimWords}{}

```

File 366 **lwarp-prettyref.sty**

§ 472 Package **prettyref**

*(Emulates or patches code by KEVIN S. RULAND.)*

Pkg prettyref prettyref is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{prettyref}[1998/07/09]

2 \newreformat{fig}{Figure \ref{#1}}
3 \newreformat{tab}{Table \ref{#1}}
```

---

File 367 **lwarp-preview.sty**

§ 473 Package **preview**

Pkg preview preview is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{preview}[2017/04/24]

2 \newenvironment{preview}{}{}
3 \newenvironment{nopreview}{}{}
4 \NewDocumentCommand{\PreviewMacro}{s o o +m}{}
5 \NewDocumentCommand{\PreviewEnvironment}{s o o +m}{}
6 \newcommand{\PreviewSnarfEnvironment}[2][{}]{
7 \NewDocumentCommand{\PreviewOpen}{s o}{}
8 \NewDocumentCommand{\PreviewClose}{s o}{}
9 \let\ifPreview\iffalse% \fi for syntax highlighting
```

---

File 368 **lwarp-psfrag.sty**

§ 474 Package **psfrag**

*(Emulates or patches code by MICHAEL C. GRANT, DAVID CARLISLE.)*

Pkg psfrag psfrag is patched for use by lwarp.

 **use psfrags** The psfrags environment is modified to use lateximage to encapsulate the image. Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.

 **Tip:** Use a mono-spaced font for the tags in the EPS file.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{psfrag}[1998/04/11]
```

A lateximage captures the modified image from the document.

```

2 \BeforeBeginEnvironment{psfrags}{%
3 \begin{lateximage}[-psfrags-~\PackageDiagramAltText]%
4 }
5
6 \AfterEndEnvironment{psfrags}{\end{lateximage}}
```

File 369 **lwarp-psfragx.sty**

§ 475 Package **psfragx**

*(Emulates or patches code by PASCAL KOCKAERT.)*

Pkg psfragx psfragx is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{psfragx}[2012/05/02]

A lateximage captures the modified image from the document.

```

2 \def\pfx@includegraphicx#1#2{%
3 \begin{lateximage}[-psfragx--\PackageDiagramAltText]%
4 \mbox{\pfx@overpix{#1}{#2}\endpfx@overpix}%
5 \end{lateximage}%
6 }
7
8 \def\@@@overpix[#1]<#2>[#3]#4{%
9 \begin{lateximage}[-psfragx--\PackageDiagramAltText]%
10 \pfx@overpix{#1,ovpfgd={#2},ovbgd={#3}}{#4}%
11 }
12
13 \def\endoverpix{%
14 \endpfx@overpix%
15 \end{lateximage}%
16 }

```

File 370 **lwarp-pst-eps.sty**

§ 476 Package **pst-eps**

*(Emulates or patches code by HERBERT VOSS.)*

Pkg pst-eps pst-eps is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{pst-eps}[2005/05/20]

```

2 \renewenvironment{TeXtoEPS}{}{}
3 \renewcommand{\PSTtoEPS}[3][[]]{}

```

File 371 **lwarp-pstool.sty**

§ 477 Package **pstool**

*(Emulates or patches code by ZEBB PRIME, WILL ROBERTSON.)*

Pkg pstool pstool is patched for use by lwarp.

`\graphicspath` is ignored, and the file directory must be stated.

⚠ **path and filename** The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

**for HTML output:** 1 \LWR@ProvidesPackagePass{pstool}[2018/01/20]

Each image is placed inside a `lateximage` to capture the results of `psfrag`.

```

2 \renewcommand\pstool@alwaysprocess[3][[%
3 \begin{lateximage}[-pstool-~\PackageDiagramAltText]%
4 \includegraphics{#2.pdf}%
5 \end{lateximage}%
6 }
7 \LetLtxMacro\pstool@neverprocess\pstool@alwaysprocess
8 \LetLtxMacro\pstool@maybeprocess\pstool@alwaysprocess
9
10 \renewcommand\pstool@@psfragfig[4]{%
11 \begin{lateximage}[-pstool-~\PackageDiagramAltText]%
12 \includegraphics{#2.pdf}%
13 \end{lateximage}%
14 }
```

---

File 372 **lwarp-pstricks.sty**

§ 478 Package **pstricks**

*(Emulates or patches code by TIMOTHY VAN ZANDT.)*

Pkg pstricks pstricks is patched for use by lwarp.

⚠ **use pspicture** All pstricks content should be contained inside a `pspicture` environment.

**for HTML output:** 1 \LWR@ProvidesPackagePass{pstricks}[2018/01/06]

```

2 \BeforeBeginEnvironment{pspicture}{%
3 \begin{lateximage}[pspicture]%
4 }
5 \AfterEndEnvironment{pspicture}{\end{lateximage}}
6
7 \BeforeBeginEnvironment{pspicture*}{%
8 \begin{lateximage}[pspicture]%
9 }
```

```

9 }
10 \AfterEndEnvironment{pspicture*}{\end{lateximage}}

```

---

File 373 **lwarp-pxatbegshi.sty**

§ 479 Package **pxatbegshi**

Pkg pxatbegshi pxatbegshi is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pxatbegshi}[2017/11/04]  
2 \LWR@origRequirePackage{lwarp-atbegshi}

---

File 374 **lwarp-pxeveryshi.sty**

§ 480 Package **pxeveryshi**

Pkg pxeveryshi pxeveryshi is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pxeveryshi}[2012/05/19]  
2 \LWR@origRequirePackage{lwarp-everyshi}

---

File 375 **lwarp-pxfonts.sty**

§ 481 Package **pxfonts**

*(Emulates or patches code by YOUNG RYU.)*

Pkg pxfonts pxfonts is used as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{pxfonts}[2008/01/22]

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{pxfonts}
6
7 \LWR@mathjax@addgreek@l@up{}{up}
8 \end{warpMathJax}

```

File 376 **lwarp-pxftnright.sty**

§ 482 Package **pxftnright**

Pkg pxftnright pxftnright is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pxftnright}[2017/02/28]

2 \LWR@origRequirePackage{lwarp-ftnright}

File 377 **lwarp-pxjahyper.sty**

§ 483 Package **pxjahyper**

Pkg pxjahyper pxjahyper is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{pxjahyper}[2018/07/15]

File 378 **lwarp-quotchap.sty**

§ 484 Package **quotchap**

*(Emulates or patches code by KARSTEN TINNEFELD, JAN KLEVER.)*

Pkg quotchap quotchap is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{quotchap}[2019/07/09]

```
2 \newcommand{\@quotchap}{}
3 \newlength{\LWR@quotchapwidth}
4
5 \let\@printcites\relax
6
7 \newcommand*{\@iprintcites}{%
```

Place the quotes inside a <div> of class quotchap, of the maximum selected width:

```
8 \begin{BlockClass}[max-width: \LWR@printlength{\LWR@quotchapwidth}]{quotchap}
9 %\begin{minipage}{\LWR@quotchapwidth}
10 \@quotchap
11 %\end{minipage}
12 \end{BlockClass}
```

Deactivate the quote printing:

```
13 \global\let\@printcites\relax
14 }
15
16 \NewEnviron{savequote}[1][\linewidth]{%
```

Remember the width, adjusted for HTML, and make the length assignment global, per:

<https://tex.stackexchange.com/questions/300823/>

[why-is-setlength-ineffective-inside-a-tabular-environment](#)

```
17 \setlength{\LWR@quotchapwidth}{#1*2}%
18 \global\LWR@quotchapwidth=\LWR@quotchapwidth%
```

Remember the body, and activate the quote printing:

```
19 \global\let\@quotchap\BODY
20 \global\let\@printcites\@iprintcites%
21 }
```

The quotation author is placed inside a <div> of class qauthor:

```
22 \newcommand{\qauthor}[1]{%
23 \LWR@stoppars%
24 \begin{BlockClass}{qauthor}%
25 {#1}%
26 \end{BlockClass}%
27 \LWR@startpars%
28 }
```

Fonts are ignored. Use css.

```
29 \newcommand{\qsetcnfont}[1]{}
30 \providecommand*\quotefont{}
31 \providecommand*\qauthorfont{}
```

File 379 **lwarp-quoting.sty**

§ 485 Package **quoting**

*(Emulates or patches code by THOMAS TITZ.)*

Pkg quoting quoting is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{quoting}[2014/01/28]

```
2 \xpatchcmd{\quoting}{\quo@begintext}
3 {\begin{LWR@blocktextcurrentfont}\quo@begintext}
4 {}
5 {\LWR@patcherror{quoting}{quoting}}
6
```

```

7 \xpatchcmd{\endquoting}{\quo@endtext}
8 {\quo@endtext\end{LWR@blocktextcurrentfont}\LWR@stoppars}
9 {}
10 {\LWR@patcherror{quoting}{endquoting}}

```

---

File 380 **lwarp-ragged2e.sty**

§ 486 Package **ragged2e**

*(Emulates or patches code by MARTIN SCHRÖDER.)*

Pkg ragged2e ragged2e is emulated.

Discard all options for lwarp-ragged2e:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{ragged2e}[2009/05/21]

```

2 \LetLtxMacro\Centering\centering
3 \LetLtxMacro\RaggedLeft\raggedleft
4 \LetLtxMacro\RaggedRight\raggedright
5 \newcommand*\justifying{}
6 \newlength{\CenteringLeftskip}
7 \newlength{\RaggedLeftLeftskip}
8 \newlength{\RaggedRightLeftskip}
9 \newlength{\CenteringRightskip}
10 \newlength{\RaggedLeftRightskip}
11 \newlength{\RaggedRightRightskip}
12 \newlength{\CenteringParfillskip}
13 \newlength{\RaggedLeftParfillskip}
14 \newlength{\RaggedRightParfillskip}
15 \newlength{\JustifyingParfillskip}
16 \newlength{\CenteringParindent}
17 \newlength{\RaggedLeftParindent}
18 \newlength{\RaggedRightParindent}
19 \newlength{\JustifyingParindent}
20 \newenvironment*{Center}{\center}{\endcenter}
21 \newenvironment*{FlushLeft}{\flushleft}{\endflushleft}
22 \newenvironment*{FlushRight}{\flushright}{\endflushright}
23 \newenvironment*{justify}{\justifying}{\endjustifying}

```

---

File 381 **lwarp-realscripts.sty**

§ 487 Package **realscripts**

*(Emulates or patches code by WILL ROBERTSON.)*

Pkg realscripts realscripts is emulated. See lwarp.css for the <span> of class supsubscript.

**for HTML output:** 1 \LWR@ProvidesPackagePass{realscripts}[2016/02/13]

The following are copied verbatim from the original, but given new names, since xparse definitions should not be `\let`.

```

2 \ExplSyntaxOn
3
4 \DeclareDocumentCommand \LWR@print@realsubscript {m} {
5 \fontspec_if_fontspec_font:TF {
6 \fontspec_if_opentype:TF
7 { \fontspec_if_feature:nTF {+subs}
8 { {\addfontfeature{VerticalPosition=Inferior}#1} }
9 { \fontspec_if_feature:nTF {+sinf}
10 { {\addfontfeature{VerticalPosition=ScientificInferior}#1} }
11 { \fakesubscript{#1} }
12 }
13 }
14 { \fontspec_if_aat_feature:nnTF {10} {2}
15 { {\addfontfeature{VerticalPosition=Inferior}#1} }
16 { \fakesubscript{#1} }
17 }
18 }
19 { \fakesubscript{#1} }
20 }
21
22 \DeclareDocumentCommand \LWR@HTML@realsubscript {m} {
23 \LWR@HTML@textsubscript{#1}
24 }
25
26 \LWR@formatted{realsubscript}
27
28
29 \DeclareDocumentCommand \LWR@print@realsuperscript {m} {
30 \fontspec_if_fontspec_font:TF
31 {
32 \fontspec_if_opentype:TF
33 { \fontspec_if_feature:nTF {+sups}
34 { {\addfontfeature{VerticalPosition=Superior}#1} }
35 { \fakesuperscript{#1} }
36 }
37 { \fontspec_if_aat_feature:nnTF {10} {1}
38 { {\addfontfeature{VerticalPosition=Superior}#1} }
39 { \fakesuperscript{#1} }
40 }
41 }
42 { \fakesuperscript{#1} }
43 }
44
45 \DeclareDocumentCommand \LWR@HTML@realsuperscript {m} {
46 \LWR@HTML@textsuperscript{#1}
47 }
48
49 \LWR@formatted{realsuperscript}
50
51
52 \DeclareDocumentCommand \LWR@print@textsubsuperscript {s O{l} mm} {
53 \leavevmode

```

```

54 \group_begin:
55 \IfBooleanTF #1
56 {
57 \hbox_set:Nn \l_tmpa_box {\textsubscript*{#3}}
58 \hbox_set:Nn \l_tmpb_box {\textsuperscript*{#4}}
59 }
60 {
61 \hbox_set:Nn \l_tmpa_box {\textsubscript{#3}}
62 \hbox_set:Nn \l_tmpb_box {#4}
63 }
64 \hbox_set:Nn \l_tmpa_box
65 { \box_move_down:nn \subsupersep {\box_use:N \l_tmpa_box} }
66 \hbox_set:Nn \l_tmpb_box
67 { \box_move_up:nn \subsupersep {\box_use:N \l_tmpb_box} }
68 \str_case:nnF {#2}
69 {
70 {l}{\use_i:nnn}
71 {c}{\use_ii:nnn}
72 {r}{\use_iii:nnn}
73 }
74 {
75 \PackageWarning{realscripts}{
76 Unknown~alignment~option~'#2'. \MessageBreak
77 One~ of~ 'l',~ 'c',~ 'r',~ only
78 }
79 \use_i:nnn
80 }
81 {
82 \hbox_overlap_right:n { \box_use:N \l_tmpa_box }
83 \hbox_overlap_right:n { \box_use:N \l_tmpb_box }
84 \skip_horizontal:n {
85 \dim_max:nn {\box_wd:N \l_tmpa_box} {\box_wd:N \l_tmpb_box}
86 }
87 }
88 {
89 \dim_compare:nTF { \box_wd:N \l_tmpa_box > \box_wd:N \l_tmpb_box }
90 {
91 \skip_horizontal:n {
92 0.5\box_wd:N \l_tmpa_box-0.5\box_wd:N \l_tmpb_box
93 }
94 \box_use:N \l_tmpb_box
95 \skip_horizontal:n {
96 -0.5\box_wd:N \l_tmpa_box-0.5\box_wd:N \l_tmpb_box
97 }
98 \box_use:N \l_tmpa_box
99 }
100 {
101 \skip_horizontal:n {
102 0.5\box_wd:N \l_tmpb_box-0.5\box_wd:N \l_tmpa_box
103 }
104 \box_use:N \l_tmpa_box
105 \skip_horizontal:n {
106 -0.5\box_wd:N \l_tmpb_box-0.5\box_wd:N \l_tmpa_box
107 }
108 \box_use:N \l_tmpb_box

```

```

109 }
110 }
111 {
112 \skip_horizontal:n {
113 \dim_max:nn {\box_wd:N \l_tmpa_box} {\box_wd:N \l_tmpb_box}
114 }
115 \hbox_overlap_left:n { \box_use:N \l_tmpa_box }
116 \hbox_overlap_left:n { \box_use:N \l_tmpb_box }
117 }
118 \group_end:
119 }
120
121 \ExplSyntaxOff
122
123
124 \newcommand*\LWR@realscriptsalign{}
125
126 \newcommand*\LWR@setrealscriptsalign[1]{%
127 \renewcommand*\LWR@realscriptsalign{}%
128 \ifthenelse{\equal{#1}{c}}{%
129 \renewcommand*\LWR@realscriptsalign{%
130 \LWR@print@mbbox{text-align:center} ; %
131 }%
132 }{}%
133 \ifthenelse{\equal{#1}{r}}{%
134 \renewcommand*\LWR@realscriptsalign{%
135 \LWR@print@mbbox{text-align:right} ; %
136 }%
137 }{}%
138 }
139
140 \DeclareDocumentCommand \LWR@HTML@textsubsuperscript {s O{l} mm} {%
141 \LWR@setrealscriptsalign{#2}%
142 \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
143 #4\textsubscript{#3}%
144 }%
145 }
146 \LWR@formatted{textsubsuperscript}
147
148 \FilenameNullify{%
149 \RenewDocumentCommand{\textsuperscript}{s m}{}%
150 \RenewDocumentCommand{\textsubscript}{s m}{}%
151 \renewcommand{\fakesubscript}[1]{}%
152 \renewcommand{\fakesuperscript}[1]{}%
153 \renewcommand{\realsubscript}[1]{}%
154 \renewcommand{\realsuperscript}[1]{}%
155 \renewcommand{\textsubsuperscript}[2]{}%
156 \renewcommand{\textsupersubscript}[2]{}%
157 }

```

---

File 382 **lwarp-refcheck.sty**

§ 488 Package **refcheck**

Pkg refcheck refcheck is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{refcheck}[2013/02/14]

```

2 \def\showrefnames{}
3 \def\norefnames{}
4 \def\showcitenames{}
5 \def\nocitenames{}
6 \def\setonmsgs{}
7 \def\setoffmsgs{}
8 \def\checkunlbd{}
9 \def\ignoreunlbd{}
10 \newcommand*\refcheckxrdoc[2][{}]
```

---

File 383 **lwarp-register.sty**

§ 489 Package **register**

*(Emulates or patches code by MATTHEW LOVELL.)*

Pkg register register is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{register}[2019/01/01]

```

2 \xpatchcmd{\register}
3 {\centering}
4 {%
5 \begin{center}%
6 \begin{lateximage}[-register--\PackageDiagramAltText]%
7 }
8 {}
9 {\LWR@patcherror{register}{register}}
10
11 \xpatchcmd{\endregister}
12 {\leftskip}
13 {%
14 \end{lateximage}\end{center}%
15 \leftskip%
16 }%
17 {}
18 {\LWR@patcherror{register}{endregister}}
19
20 \expandafter\xapptocmd\cename register*\endcename
21 {%
```

```

22 \begin{center}%
23 \begin{lateximage}[-register--\PackageDiagramAltText]%
24 }
25 {}
26 {\LWR@patcherror{register}{register*}}
27
28 \expandafter\xpitchcmd\csname endregister*\endcsname
29 {\leftskip}
30 {%
31 \end{lateximage}\end{center}%
32 \leftskip%
33 }%
34 {}
35 {\LWR@patcherror{register}{endregister*}}
36
37 \setlength{\regWidth}{5in}

```

---

File 384 **lwarp-reysize.sty**

§ 490 Package **reysize**

(Emulates or patches code by DONALD ARSENEAU, BERNIE COSELL, MATT SWIFT.)

Pkg reysize reysize is patched for use by lwarp, and emulated for MATHJAX.

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified font-size.

`\reysize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarily restored, and so should work as expected.

 **not small** The HTML browser's setting for minimum font size may limit how small the output will be displayed.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{reysize}[2013/03/29]
2 \let\LWR@origreysize\reysize
3 \LetLtxMacro\LWR@origlarger\larger
4 \LetLtxMacro\LWR@origsmaller\smaller
5 \let\LWR@relscale\relscale
6 \LetLtxMacro\LWR@origtextlarger\textlarger
7 \LetLtxMacro\LWR@origtextsmaller\textsmaller
8 \let\LWR@textscale\textscale
9
10 \appto\LWR@restoreorigformatting{%
11 \let\reysize\LWR@origreysize%
12 \LetLtxMacro\larger\LWR@origlarger%
13 \LetLtxMacro\smaller\LWR@origsmaller%
14 \let\relscale\LWR@relscale%
15 \LetLtxMacro\textlarger\LWR@origtextlarger%
16 \LetLtxMacro\textsmaller\LWR@origtextsmaller%

```

```

17 \let\textscale\LWR@textscale%
18 }
19
20 \newcounter{LWR@relsize}
21
22 \renewcommand*\relsize[1]{%
23 \renewcommand*\larger[1][1]{%
24 \renewcommand*\smaller[1][1]{%
25 \renewcommand*\relscale[1]{%
26
27 \renewcommand*\textlarger[2][1]{%
28 \setcounter{LWR@relsize}{100+(#1*20)}%
29 \InlineClass[font-size:\arabic{LWR@relsize}\%]{textlarger}{#2}%
30 }
31
32 \renewcommand*\textsmaller[2][1]{%
33 \setcounter{LWR@relsize}{100-(#1*20)}%
34 \InlineClass[font-size:\arabic{LWR@relsize}\%]{textsmaller}{#2}%
35 }
36
37 \renewcommand*\textscale[2]{%
38 \setcounter{LWR@relsize}{100*\real{#1}}%
39 \InlineClass[font-size:\arabic{LWR@relsize}\%]{textscale}{#2}%
40 }

```

For MATHJAX:

```

41 \begin{warpMathJax}
42 \CustomizeMathJax{\newcommand{\mathlarger}[1]{#1}}
43 \CustomizeMathJax{\newcommand{\mathsmaller}[1]{#1}}
44 \end{warpMathJax}

```

---

File 385 **lwarp-repeatindex.sty**

§ 491 Package **repeatindex**

Pkg repeatindex repeatindex is emulated for lwarp.

 **style file** lwarp must be used with a special style file:

```
\usepackage[makeindex,makeindexStyle={lwarp_repeatindex}]{lwarp}
```

where lwarp\_repeatindex.ist may be copied from the following modified version of lwarp.ist:

```

| preamble
| "\begin{theindex}
| \providecommand*\lettergroupDefault[1]{%
| \providecommand*\lettergroup[1]{%
| \par\textbf{#1}\par
| \nopagebreak

```

```

 }
 "
 headings_flag 1
 heading_prefix "
 \lettergroup{"
 heading_suffix "}"
 delim_0 "[", \hyperindexref{"
 delim_1 " ", \hyperindexref{"
 delim_2 " ", \hyperindexref{"
 delim_n "}", \hyperindexref{"
 delim_r "} -- \hyperindexref{"
 delim_t "}"
 item_0 "\n \item ["

```

(The modifications are the `delim_0` and `item_0` entries.)

**for HTML output:** 1 \LWR@ProvidesPackageDrop{repeatindex}[2001/10/13]

In the `lwarp` core, `\LWR@indexitem` is modified to accept the optional `\item` argument.

```

2 \RequirePackage{makeidx}
3 \def\entryprefix{\itshape}
4 \def\entrypostfix{\dots}

```

---

File 386 **lwarp-repltext.sty**

§ 492 Package **repltext**

Pkg repltext repltext is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{repltext}[2020/09/25]

```

2 \newcommand{\repltext}[2]{#2}
3 \newcommand*{\prevrepl}{}

```

For MATHJAX:

```

4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\repltext}[2]{#2}}
6 \end{warpMathJax}

```

---

File 387 **lwarp-resizegather.sty**

§ 493 Package **resizegather**

Pkg resizegather resizegather is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{resizgather}[2016/05/16]
2 \newcommand*{\resizgathersetup}[1]{}

```

---

File 388 **lwarp-returntogrid.sty**

§ 494 Package **returntogrid**

Pkg returntogrid returntogrid is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{returntogrid}[2018/08/21]
2 \NewDocumentCommand\returntogrid{ 0 {} }{}
3 \NewDocumentCommand\returntogridsetup { m } {}
4 \NewDocumentCommand\showdebugpagegrid {} {}

```

---

File 389 **lwarp-rmathbr.sty**

§ 495 Package **rmathbr**

*(Emulates or patches code by DENIS RYABOV.)*

Pkg rmathbr rmathbr is used as-is for SVG math, and emulated for MATHJAX.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{rmathbr}[2016/04/10]
2 \begin{warpMathJax}
3 \CustomizeMathJax{\def*{~}}
4 \CustomizeMathJax{\newcommand{\cdott}{\cdot}}
5 \CustomizeMathJax{\newcommand{\nobr}{}}
6 \end{warpMathJax}

```

---

File 390 **lwarp-rmpage.sty**

§ 496 Package **rmpage**

Pkg rmpage rmpage is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{rmpage}[1997/09/29]

```

---

File 391 **lwarp-romanbar.sty**

§ 497 Package **romanbar**

*(Emulates or patches code by H.-MARTIN MÜNCH.)*

Pkg romanbar romanbar is patched for use by lwarp.

An inline class with an overline and underline is used.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{romanbar}[2012/01/01]

2 \DeclareRobustCommand{\Roman@bar}[1]{% #1 is in Roman, i.e. MMXII
3 \InlineClass[%
4 text-decoration: overline underline ;
5]{romanbar}{#1}%
6 }
```

---

File 392 **lwarp-romanbarpagenumber.sty**

§ 498 Package **romanbarpagenumber**

Pkg romanbarpagenumber romanbarpagenumber is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{romanbarpagenumber}[2015/02/06]
```

---

File 393 **lwarp-rotating.sty**

§ 499 Package **rotating**

*(Emulates or patches code by ROBIN FAIRBAIRNS, SEBASTIAN RAHTZ, LEONOR BARROCA.)*

Pkg rotating rotating is emulated.

All rotations are ignored in HTML output.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{rotating}[2016/08/11]
2 \RequirePackage{graphicx}

3 \LetLtxMacro\sidewaystable\table
4 \let\endsidewaystable\endtable
5
6 \LetLtxMacro\sidewaysfigure\figure
7 \let\endsidewaysfigure\endfigure
8
9 \newenvironment*{sideways}{}{}
10 \newenvironment*{turn}[1]{}{}
11 \newenvironment*{rotate}[1]{}{}
12 \NewDocumentCommand{\turnbox}{m +m}{#2}
13 \let\rotcaption\caption
14 \let\@makerotcaption\@makecaption
```

File 394 **lwarp-rotfloat.sty**

§ 500 Package **rotfloat**

(Emulates or patches code by AXEL SOMMERFELDT.)

Pkg rotfloat **rotfloat** is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{rotfloat}[2004/01/04]
2
3 \RequirePackage{float}
4 \RequirePackage{rotating}

```

`\newfloat`  $\langle 1: type \rangle \langle 2: placement \rangle \langle 3: ext \rangle [\langle 4: within \rangle]$

Emulates the `\newfloat` command from the `float` package. Sideways floats are `\let` to the same as regular floats.

“placement” is ignored.

```

5 \RenewDocumentCommand{\newfloat}{m m m o}{%
6 \IfValueTF{#4}%
7 {%
8 \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}%
9 }%
10 {%
11 \DeclareFloatingEnvironment[fileext=#3]{#1}%
12 }%
13 \csletcs{sideways#1}{#1}%
14 \csletcs{endsideways#1}{end#1}%

```

Remember the float style:

```

15 \csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
16 \csedef{LWR@floatstyle@sideways#1}{\LWR@floatstyle}%

```

`newfloat` package automatically creates the `\listof` command for new floats, but `float` does not, so remove `\listof` here in case it is manually created later:

```

17 \cslet{listof#1s}\relax%
18 \cslet{listof#1es}\relax%
19 \cslet{listofsideways#1s}\relax%
20 \cslet{listofsideways#1es}\relax%
21 }

```

---

File 395 **lwarp-rviewport.sty**

§ 501 Package **rviewport**

Pkg rviewport rviewport is honored inside a `lateximage`, and otherwise ignored for HTML output.

If rviewport is important for an image, enclose the image inside a `lateximage` environment.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{rviewport}[2011/08/27]
2 \define@key{igraph}{rviewport}{}

```

---

File 396 **lwarp-savetrees.sty**

§ 502 Package **savetrees**

Pkg savetrees savetrees is ignored.

**for HTML output:** Discard all options for lwarp-savetrees:

```
1 \LWR@ProvidesPackageDrop{savetrees}[2016/04/13]

```

---

File 397 **lwarp-scalefnt.sty**

§ 503 Package **scalefnt**

*(Emulates or patches code by D. CARLISLE.)*

Pkg scalefnt scalefnt is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{scalefnt}
2 \DeclareRobustCommand\scalefont[1]{}

```

---

File 398 **lwarp-scalerel.sty**

§ 504 Package **scalerel**

*(Emulates or patches code by STEVEN B. SEGLETES.)*

Pkg scalerel scalerel is used as-is for SVG math, and is emulated and ignored for MATHJAX.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{scalerel}[2016/12/29]

```

For MATHJAX:

```

2 \begin{warpMathJax}
3 \LWR@infoprocessingmathjax{scalerele}
4
5 \CustomizeMathJax{\newcommand{\scalerele}{\ifstar{\scalereleplain}{\scalereleplus}}}
6 \CustomizeMathJax{\newcommand{\scalereleplain}[3][\#2]}
7 \CustomizeMathJax{\newcommand{\scalereleplus}[3][\#2\#3]}
8 \CustomizeMathJax{\newcommand{\stretchrele}{\ifstar{\stretchreleplain}{\stretchreleplus}}}
9 \CustomizeMathJax{\newcommand{\stretchreleplain}[3][\#2]}
10 \CustomizeMathJax{\newcommand{\stretchreleplus}[3][\#2\#3]}
11 \CustomizeMathJax{\newcommand{\scaleto}[3][\#2]}
12 \CustomizeMathJax{\newcommand{\stretchto}[3][\#2]}
13 \CustomizeMathJax{\newcommand{\scaleleftright}[4][\#2\#3\#4]}
14 \CustomizeMathJax{\newcommand{\stretchleftright}[4][\#2\#3\#4]}
15 \CustomizeMathJax{\newcommand{\hstretch}[2]{\#2}}
16 \CustomizeMathJax{\newcommand{\vstretch}[2]{\#2}}
17 \CustomizeMathJax{\newcommand{\scaleobj}[2]{\#2}}
18 \CustomizeMathJax{\newcommand{\ThisStyle}[1]{\#1}}
19 \CustomizeMathJax{\newcommand{\SavedStyle}{}}
20 \CustomizeMathJax{\def\scriptstyleScaleFactor{.7}}
21 \CustomizeMathJax{\def\scriptscriptstyleScaleFactor{.5}}
22 \CustomizeMathJax{\newcommand{\discernmathstyle}{}}
23 \CustomizeMathJax{\newcommand{\ignoremathstyle}[1][T]}
24 \CustomizeMathJax{\newcommand{\Isnnextbyte}[3][v]}
25 \end{warpMathJax}

```

---

File 399 **lwarp-schemata.sty**

§ 505 Package **schemata**

(Emulates or patches code by CHARLES P. SCHAUM.)

Pkg schemata **schemata** is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{schemata}[2020/11/23]

```

2 \LetLtxMacro\LWR@schemata@origschema\schema
3 \LetLtxMacro\LWR@schemata@origSchema\Schema
4
5 \renewcommand{\schema}[3][open]{%
6 \begin{lateximage}[-schemata~\PackageDiagramAltText]%
7 \LWR@print@normalsize%
8 \LWR@schemata@origschema[\#1]{\#2}{\#3}%
9 \end{lateximage}%
10 }
11
12 \renewcommand{\Schema}[5][open]{%
13 \begin{lateximage}[-schemata~\PackageDiagramAltText]%
14 \LWR@print@normalsize%
15 \LWR@schemata@origSchema[\#1]{\#2}{\#3}{\#4}{\#5}%
16 \end{lateximage}%
17 }

```

File 400 **lwarp-scrextend.sty**

§ 506 Package **scrextend**

Pkg scrextend scrextend is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. `\DeclareDocumentCommand` is used to overwrite the koma-script definitions.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{scrextend}[2020/01/24]

2 \DeclareDocumentCommand{\setkomafont}{m m}{}
3 \DeclareDocumentCommand{\addkomafont}{m m}{}
4 \DeclareDocumentCommand{\usekomafont}{m}{}
5
6 \DeclareDocumentCommand{\usefontofkomafont}{m}{}
7 \DeclareDocumentCommand{\useencodingofkomafont}{m}{}
8 \DeclareDocumentCommand{\usesizeofkomafont}{m}{}
9 \DeclareDocumentCommand{\usefamilyofkomafont}{m}{}
10 \DeclareDocumentCommand{\useseriesofkomafont}{m}{}
11 \DeclareDocumentCommand{\useshapeofkomafont}{m}{}
12
13 \providecommand*\coverpagetopmargin{}
14 \providecommand*\coverpagebottommargin{}
15 \providecommand*\coverpageleftmargin{}
16 \providecommand*\coverpagerightmargin{}
17

```

Title page:

```

18 \AtBeginDocument{
19 \let\LWR@koma@orig@maketitle\maketitle
20 \DeclareDocumentCommand{\maketitle}{o}{\LWR@koma@orig@maketitle}
21 }
22
23 \DeclareDocumentCommand{\@maketitle}{}{%
24 \ifvoid{\@titlehead}{}{%
25 \begin{BlockClass}{titlehead}%
26 \@titlehead%
27 \end{BlockClass}%
28 }%
29 \ifvoid{\@subject}{}{%
30 \begin{BlockClass}{subject}%
31 \@subject%
32 \end{BlockClass}%
33 }%
34 \LWR@stoppars%
35 \LWR@htmltag{\LWR@tagtitle}%
36 \@title%

```

```

37 \LWR@htmltag{\LWR@tagtitleend}%
38 \ifdefvoid{\@subtitle}{}%
39 \begin{BlockClass}{subtitle}%
40 \@subtitle%
41 \end{BlockClass}%
42 }%
43 \LWR@startpars%
44 \begin{BlockClass}{author}%

45 \renewcommand*{\cr}{}%
46 \renewcommand*{\crr}{}%
47 \renewcommand*{\noalign}{}%

48 \renewcommand{\and}{%
49 \end{BlockClass}%
50 \begin{BlockClass}{oneauthor}%
51 }%
52 \begin{BlockClass}{oneauthor}%
53 \@author%
54 \end{BlockClass}%
55 \end{BlockClass}%
56 \begin{BlockClass}{titledate}%
57 \@date%
58 \end{BlockClass}%
59 \ifdefvoid{\@published}{}%
60 \begin{BlockClass}{published}%
61 \@published%
62 \end{BlockClass}%
63 }%
64 }
65
66 \AddSubtitlePublished
67
68 \DeclareDocumentCommand{\extratitle}{m}{}
69 \DeclareDocumentCommand{\frontispiece}{m}{}
70
71 \def\@titlehead{}%
72 \DeclareDocumentCommand{\titlehead}{m}{\gdef\@titlehead{#1}}%
73
74 \def\@subject{}%
75 \DeclareDocumentCommand{\subject}{m}{\gdef\@subject{#1}}%
76
77 % \subtitle and \published are defined by \AddSubtitlePublished
78
79 \DeclareDocumentCommand{\publishers}{m}{\published{#1}}
80
81 \DeclareDocumentCommand{\uppertitleback}{m}{}
82 \DeclareDocumentCommand{\lowertitleback}{m}{}
83 \DeclareDocumentCommand{\dedication}{m}{}
84
85 \DeclareDocumentCommand{\ifthispageodd}{m m}{#1}
86
87 \DeclareDocumentCommand{\cleardoublepageusingstyle}{m}{}
88 \DeclareDocumentCommand{\cleardoubleemptypage}{}{}
89 \DeclareDocumentCommand{\cleardoubleplainpage}{}{}

```

```

90 \DeclareDocumentCommand{\cleardoublestandardpage}{}{}
91 \DeclareDocumentCommand{\cleardoubleoddpge}{}{}
92 \DeclareDocumentCommand{\cleardoubleoddpgeusingstyle}{m}{}
93 \DeclareDocumentCommand{\cleardoubleoddpgeemptypage}{}{}
94 \DeclareDocumentCommand{\cleardoubleoddpgeplainpage}{}{}
95 \DeclareDocumentCommand{\cleardoubleoddpgestandardpage}{}{}
96 \DeclareDocumentCommand{\cleardoubleevenpage}{}{}
97 \DeclareDocumentCommand{\cleardoubleevenpageusingstyle}{m}{}
98 \DeclareDocumentCommand{\cleardoubleevenemptypage}{}{}
99 \DeclareDocumentCommand{\cleardoubleevenplainpage}{}{}
100 \DeclareDocumentCommand{\cleardoubleevenstandardpage}{}{}
101
102 \DeclareDocumentCommand{\multiplefootnoteseparator}{}{%
103 \begingroup\let\thefootnotemark\multfootsep\@makefnmark\endgroup
104 }
105
106 \DeclareDocumentCommand{\multfootsep}{}{, }
107
108 \DeclareDocumentCommand{\footref}{m}{%
109 \begingroup
110 \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
111 \endgroup
112 \@footnotemark
113 }
114
115 \DeclareDocumentCommand{\deffootnote}{o m m}{}
116 \DeclareDocumentCommand{\deffootnotemark}{m}{}
117 \DeclareDocumentCommand{\setfootnoterule}{o m}{}
118 \DeclareDocumentCommand{\raggedfootnote}{}{}

119 \DeclareDocumentCommand{\dictum}{o m}{
120 \begin{LWR@BlockClassWP}{\LWR@print@mbx{text-align:right}}{}{\dictum}
121 #2
122 \IfValueT{#1}
123 {
124 \LWR@stoppars%
125 \ifbool{FormatWP}
126 {\begin{BlockClass}[\LWR@print@mbx{border-top:} 1px solid gray]{dictumauthor}}
127 {\begin{BlockClass}{dictumauthor}}
128 \dictumauthorformat{#1}
129 \end{BlockClass}
130 }
131 \end{LWR@BlockClassWP}
132 }
133
134 \DeclareDocumentCommand{\dictumwidth}{}{}
135 \DeclareDocumentCommand{\dictumauthorformat}{m}{(#1)}
136 \DeclareDocumentCommand{\dictumrule}{}{}
137 \DeclareDocumentCommand{\raggeddictum}{}{}
138 \DeclareDocumentCommand{\raggeddictumtext}{}{}
139 \DeclareDocumentCommand{\raggeddictumauthor}{}{}
140
141 \DeclareDocumentEnvironment{labeling}{o m}
142 {}
143 \def\sc@septext{#1}%

```

```

144 \list{}{}%
145 \let\makeLabel\labelinglabel%
146 }
147 {
148 \endlist
149 }
150
151 \DeclareDocumentCommand{\labelinglabel}{m}{%
152 #1 \quad \sc@septext%
153 }
154
155 \let\addmargin\relax
156 \let\endaddmargin\relax
157 \cslet{addmargin*}{\relax}
158 \cslet{endaddmargin*}{\relax}

159 \NewDocumentEnvironment{addmargin}{s O{} m}
160 {
161 \LWR@stoppars%
162 \setlength{\LWR@templengthtwo}{#3}
163 \ifblank{#2}
164 {
165 \begin{BlockClass}[
166 \LWR@print@mbx{margin-left:\LWR@printlength{\LWR@templengthtwo}} ;
167 \LWR@print@mbx{margin-right:\LWR@printlength{\LWR@templengthtwo}}
168]{addmargin}
169 }
170 {
171 \setlength{\LWR@templengthone}{#2}
172 \begin{BlockClass}[
173 \LWR@print@mbx{margin-left:\LWR@printlength{\LWR@templengthone}} ;
174 \LWR@print@mbx{margin-right:\LWR@printlength{\LWR@templengthtwo}}
175]{addmargin}
176 }
177 }
178 {\end{BlockClass}\LWR@startpars}

```

Ref to create a starred environment:

<https://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment>

```

179
180 \ExplSyntaxOn
181 \cs_new:cpn {addmargin*} {\addmargin*}
182 \cs_new_eq:cN {endaddmargin*} \endaddmargin
183 \ExplSyntaxOff
184
185 \DeclareDocumentCommand{\marginline}{m}{\marginpar{#1}}

```

---

File 401 **lwarp-scrhack.sty**

§ 507 Package **scrhack**

Pkg scrhack scrhack is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{scrhack}[2018/03/30]

---

File 402 **lwarp-scrlayer.sty**

§ 508 Package **scrlayer**

*(Emulates or patches code by MARKUS KOHM.)*

Pkg scrlayer scrlayer is emulated.

 **Not fully tested!** [Please send bug reports!](#)

**for HTML output:** 1 \LWR@ProvidesPackageDrop{scrlayer}[2018/03/30]

```

2 \newcommand*\DeclareSectionNumberDepth[2]{}
3 \newcommand*\DeclareLayer[2]{}
4 \newcommand*\DeclareNewLayer[2]{}
5 \newcommand*\ProvideLayer[2]{}
6 \newcommand*\RedeclareLayer[2]{}
7 \newcommand*\ModifyLayer[2]{}
8 \newcommand*\layerhalign{}
9 \newcommand*\layervalign{}
10 \newcommand*\layerxoffset{}
11 \newcommand*\layeryoffset{}
12 \newcommand*\layerwidth{}
13 \newcommand*\layerheight{}
14 \providecommand*\LenToUnit[1]{\strip@pt\dimexpr#1*\p@/\unitlength}
15 \newcommand*\putUL[1]{}
16 \newcommand*\putUR[1]{}
17 \newcommand*\putLL[1]{}
18 \newcommand*\putLR[1]{}
19 \newcommand*\putC[1]{}
20 \newcommand*\GetLayerContents[1]{}
21 \newcommand*\IfLayerExists[3]{#3}
22 \newcommand*\DestroyLayer[1]{}
23 \newcommand*\layercontentsmeasure{}
24 \newcommand*\currentpagestyle{}
25 \newcommand*\BeforeSelectAnyPageStyle[1]{}
26 \newcommand*\AfterSelectAnyPageStyle[1]{}
27 \newcommand*\DeclarePageStyleAlias[2]{}
28 \newcommand*\DeclareNewPageStyleAlias[2]{}
29 \newcommand*\ProvidePageStyleAlias[2]{}

```

```

30 \newcommand*\RedeclarePageStyleAlias}[2]{}
31 \newcommand*\DestroyPageStyleAlias}[1]{}
32 \newcommand*\GetRealPageStyle}[1]{}
33 \newcommand*\DeclarePageStyleByLayers}[3][[]]{}
34 \newcommand*\DeclareNewPageStyleByLayers}[3][[]]{}
35 \newcommand*\ProvidePageStyleByLayers}[3][[]]{}
36 \newcommand*\RedeclarePageStyleByLayers}[3][[]]{}
37 \NewDocumentCommand{\ForEachLayerOfPageStyle}{s m m}{}
38 \newcommand*\AddLayersToPageStyle}[2]{}
39 \newcommand*\AddLayersAtBeginOfPageStyle}[2]{}
40 \newcommand*\AddLayersAtEndOfPageStyle}[2]{}
41 \newcommand*\RemoveLayersFromPageStyle}[2]{}
42 \newcommand*\AddLayersToPageStyleBeforeLayer}[3]{}
43 \newcommand*\AddLayersToPageStyleAfterLayer}[3]{}
44 \newcommand*\UnifyLayersAtPageStyle}[1]{}
45 \newcommand*\ModifyLayerPageStyleOptions}[2]{}
46 \newcommand*\AddToLayerPageStyleOptions}[2]{}
47 \newcommand{\IfLayerPageStyleExists}[3]{#3}
48 \newcommand{\IfRealLayerPageStyleExists}[3]{#3}
49 \newcommand{\IfLayerAtPageStyle}[4]{#4}
50 \newcommand{\IfSomeLayerAtPageStyle}[4]{#4}
51 \newcommand{\IfLayersAtPageStyle}[4]{#4}
52 \newcommand*\DestroyRealLayerPageStyle}[1]{}
53 \@ifundefined{footheight}{\newlength\footheight}{}
54 \DeclareDocumentCommand{\automark}{s o m}{}
55 \DeclareDocumentCommand{\manualmark}{}{}
56 \DeclareDocumentCommand{\MakeMarkcase}{m}{#1}

57 \newcommand{\partmarkformat}{}
58 \if@chapter
59 \newcommand{\chaptermarkformat}{}
60 \fi
61 \newcommand{\sectionmarkformat}{}
62 \DeclareDocumentCommand{\GenericMarkFormat}{m}{}

63 \newcommand*\@mkleft}[1]{}
64 \newcommand*\@mkright}[1]{}
65 \newcommand*\@mkdouble}[1]{}
66 \newcommand*\@mkboth}[2]{}
67 \newcommand*\sclayerInitInterface}[1][[]]{}
68 \newcommand{\sclayerAddToInterface}[3][[]]{}
69 \newcommand{\sclayerAddCsToInterface}[3][[]]{}
70 \newcommand{\sclayerOnAutoRemoveInterface}[2][[]]{}

```

---

File 403 **lwarp-sclayer-notecolumn.sty**

§ 509 Package **sclayer-notecolumn**

(Emulates or patches code by MARKUS KOHM.)

Pkg sclayer-notecolumn sclayer-notecolumn is emulated.

⚠ **Not fully tested!** [Please send bug reports!](#)

**for HTML output:** 1 \LWR@ProvidesPackageDrop{sclayer-notecolumn}[2018/02/02]

```

2 \newcommand*\DeclareNoteColumn}[2][{}
3 \newcommand*\DeclareNewNoteColumn}[2][{}
4 \newcommand*\ProvideNoteColumn}[2][{}
5 \newcommand*\RedeclareNoteColumn}[2][{}
6 \NewDocumentCommand{\makenote}{s o m}{\marginpar{#3}}
7 \newcommand*\syncwithnotecolumn}[1][{}
8 \newcommand*\syncwithnotecolumns}[1][{}
9 \newcommand*\clearnotecolumn}[1][{}
10 \newcommand*\clearnotecolumns}[1][{}

```

---

File 404 **lwarp-sclayer-scrpage.sty**

§ 510 Package **sclayer-scrpage**

*(Emulates or patches code by MARKUS KOHM.)*

Pkg sclayer-scrpage sclayer-scrpage is ignored.

⚠ **Not fully tested!** [Please send bug reports!](#)

**for HTML output:** 1 \LWR@ProvidesPackageDrop{sclayer-scrpage}[2018/03/30]

```

2 \@ifundefined{footheight}{\newlength\footheight}{}
3 \NewDocumentCommand{\lehead}{s o m}{}
4 \NewDocumentCommand{\cehead}{s o m}{}
5 \NewDocumentCommand{\rehead}{s o m}{}
6 \NewDocumentCommand{\lohead}{s o m}{}
7 \NewDocumentCommand{\cohead}{s o m}{}
8 \NewDocumentCommand{\rohead}{s o m}{}
9 \NewDocumentCommand{\lefoot}{s o m}{}
10 \NewDocumentCommand{\cefoot}{s o m}{}
11 \NewDocumentCommand{\refoot}{s o m}{}
12 \NewDocumentCommand{\lofoot}{s o m}{}
13 \NewDocumentCommand{\cofoot}{s o m}{}
14 \NewDocumentCommand{\rofoot}{s o m}{}
15 \NewDocumentCommand{\ohead}{s o m}{}
16 \NewDocumentCommand{\chead}{s o m}{}
17 \NewDocumentCommand{\ihead}{s o m}{}
18 \NewDocumentCommand{\ofoot}{s o m}{}
19 \NewDocumentCommand{\cfoot}{s o m}{}
20 \NewDocumentCommand{\ifoot}{s o m}{}
21 \DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
22 \newcommand*\defpairofpagestyles}[3][{}
23 \newcommand*\newpairofpagestyles}[3][{}
24 \newcommand*\renewpairofpagestyles}[3][{}
25 \newcommand*\providepairofpagestyles}[3][{}

26 \newcommand*\clearmainofpairofpagestyles}{}

```

```

27 \newcommand*\clearplainofpairofpagestyles{}
28 \newcommand*\clearpairofpagestyles{}
29 \newcommand*\clearscrheadings{}
30 \newcommand*\clearscrheadfoot{}
31 \newcommand*\clearscrplain{}

32 \NewDocumentCommand\deftriplepagestyle{m o o m m m m m m}{}
33 \NewDocumentCommand\newtriplepagestyle{m o o m m m m m m}{}
34 \NewDocumentCommand\renewtriplepagestyle{m o o m m m m m m}{}
35 \NewDocumentCommand\providetriplespagestyle{m o o m m m m m m}{}
36 \newcommand*\defpagestyle[3]{}
37 \newcommand*\newpagestyle[3]{}
38 \newcommand*\providepagestyle[3]{}
39 \newcommand*\renewpagestyle[3]{}

```

---

File 405 **lwarp-scrpage2.sty**

§ 511 Package **scrpage2**

*(Emulates or patches code by MARKUS KOHM.)*

Pkg scrpage2 scrpage2 is ignored.

 **Not fully tested!** [Please send bug reports!](#)

**for HTML output:** 1 \LWR@ProvidesPackageDrop{scrpage2}[2018/03/30]

```

2 \@ifundefined{footheight}{\newlength\footheight}{}
3 \NewDocumentCommand\lehead{o m}{}
4 \NewDocumentCommand\cehead{o m}{}
5 \NewDocumentCommand\rehead{o m}{}
6 \NewDocumentCommand\lohead{o m}{}
7 \NewDocumentCommand\cohead{o m}{}
8 \NewDocumentCommand\rohead{o m}{}
9 \NewDocumentCommand\lefoot{o m}{}
10 \NewDocumentCommand\cefoot{o m}{}
11 \NewDocumentCommand\refoot{o m}{}
12 \NewDocumentCommand\lofoot{o m}{}
13 \NewDocumentCommand\cofoot{o m}{}
14 \NewDocumentCommand\rofoot{o m}{}
15 \NewDocumentCommand\ohead{o m}{}
16 \NewDocumentCommand\chead{o m}{}
17 \NewDocumentCommand\ihead{o m}{}
18 \NewDocumentCommand\ofoot{o m}{}
19 \NewDocumentCommand\cfoot{o m}{}
20 \NewDocumentCommand\ifoot{o m}{}
21 \DeclareDocumentCommand\automark{o m}{}
22 \DeclareDocumentCommand\manualmark{}{}
23 \DeclareDocumentCommand\MakeMarkcase{m}{#1}
24 \NewDocumentCommand\deftripstyle{m o o m m m m m m}{}
25 \NewDocumentCommand\defpagestyle{s m m m}{}
26 \NewDocumentCommand\newpagestyle{s m m m}{}

```

```

27 \NewDocumentCommand{\renewpagestyle}{s m m m}{}
28 \NewDocumentCommand{\providepagestyle}{s m m m}{}
29 \newcommand{\partmarkformat}{}
30 \if@chapter
31 \newcommand{\chaptermarkformat}{}
32 \fi
33 \newcommand{\sectionmarkformat}{}
34 \newcommand{\subsectionmarkformat}{}
35 \newcommand{\subsubsectionmarkformat}{}
36 \newcommand{\paragraphmarkformat}{}
37 \newcommand{\subparagraphmarkformat}{}
38
39 \newcommand*{\clearscrheadings}{}
40 \newcommand*{\clearscrheadfoot}{}
41 \newcommand*{\clearscrplain}{}

```

---

File 406 **lwarp-section.sty**

§ 512 Package **section**

Pkg section section is ignored.

*(Emulates or patches code by OLIVER PRETZEL.)*

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{section}

2 \ifx\chapter\undefined
3 \def\chsize{\Large}\def\hdsiZe{\huge}\else
4 \def\chsize{\huge}\def\hdsiZe{\Huge}
5 \fi
6 \let\ttsiZe\LARGE
7 \let\ausiZe\large
8 \let\dasiZe\large
9 \let\secsiZe\Large
10 \let\subsiZe\large
11 \let\hdpos\raggedright
12 \newcounter{hddepth}
13 \let\fpind\relax
14 \def\ttfnt{}
15 \def\hdfnt{}
16 \def\fefnt{}
17 \def\thfnt{}
18 \def\pgfnt{}
19 \def\hmkfnt{}
20 \let\mkcse\uppercase
21 \def\hddot{}
22 \def\cpdot{:}
23 \def\nmdot{}
24 \ifx\secindent\undefined
25 \newdimen\secindent
26 \newskip\secpreskp
27 \newskip\secpstskp
28 \newdimen\subindent

```

```

29 \newskip\subpreskp
30 \newskip\subpstskp
31 \newskip\parpstskp
32 \newcount\c@hddepth
33 \fi

```

---

File 407 **lwarp-sectionbreak.sty**

§ 513 Package **sectionbreak**

*(Emulates or patches code by MICHAL HOFTICH.)*

Pkg sectionbreak sectionbreak is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{sectionbreak}[2018-01-03]

```

2 \renewcommand\asterism{\HTMLunicode{2042}}
3
4 \renewcommand\pre@sectionbreak{}
5 \renewcommand\post@sectionbreak{}
6
7 \renewcommand\print@sectionbreak[1]{%
8 \begin{center}
9 #1
10 \end{center}
11 }
12

```

---

File 408 **lwarp-sectsty.sty**

§ 514 Package **sectsty**

*(Emulates or patches code by ROWLAND McDONNELL.)*

Pkg sectsty sectsty is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{sectsty}[2002/02/25]

```

2 \newcommand*\partfont [1] {}
3 \newcommand*\partnumberfont [1] {}
4 \newcommand*\parttitlefont [1] {}
5 \newcommand*\chapterfont [1] {}
6 \newcommand*\chapternumberfont [1] {}
7 \newcommand*\chaptertitlefont [1] {}
8 \newcommand*\sectionfont [1] {}
9 \newcommand*\subsectionfont [1] {}
10 \newcommand*\subsubsectionfont [1] {}
11 \newcommand*\paragraphfont [1] {}
12 \newcommand*\subparagraphfont [1] {}
13 \newcommand*\minisecfont [1] {}

```

```

14 \newcommand*{\allsectionsfont}[1] {}
15 \newcommand{\nohang}{}

```

`\sectionrule` is only to be used in `*font` commands, thus it is ignored.

```

16 \newcommand*{\sectionrule}[5]{}
17
18 \def\ulemheading#1#2{}

```

File 409 **lwarp-selectp.sty**

§ 515 Package **selectp**

Pkg selectp selectp is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{selectp}% no date given
2 \newcommand*{\outputonly}[1]{}

```

File 410 **lwarp-semantic-markup.sty**

§ 516 Package **semantic-markup**

*(Emulates or patches code by ANDREW A. CASHNER.)*

Pkg semantic-markup semantic-markup is patched for use by lwarp.

 If using the endnotes option, add `\theendnotes` where desired.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{semantic-markup}[2018/05/21]

```

The endnotes must be printed by the user before the end of the document, since the end is after the HTML footer, etc.

```

2 \ifendnotes
3 \RenewDocumentCommand{\SetupEndnotes}{}{%
4 \let\footnote=\endnote
5 \AtEndDocument{\DoBeforeEndnotes{\EndnoteFont\theendnotes}}%
6 }
7 \fi

```

HTML unicode characters from musicography are used.

```

8 \RequirePackage{musicography}
9
10 \let\fl\musFlat
11 \let\sh\musSharp
12 \let\na\musNatural

```

The `\musfig` is placed inside a hashed image, with a simple alt tag.

```

13 \RequirePackage{amsmath}
14
15 \RenewDocumentCommand{\musfig}{ m m }{%
16 \LWR@subsingledollar*%
17 {#1/#2}% alt tag
18 {musfig}% addl' hashing
19 {% contents
20 \LWR@origensuredmath{%
21 \genfrac{}{}{0pt}{1}{\text{#1}}{\text{#2}}%
22 }%
23 }%
24 }

```

The `\meter` is taken from `musicography`, and becomes a hashed image with a simple alt tag.

```

25 \RenewDocumentCommand{\meter}{ m m }{%
26 \musMeter{#1}{#2}%
27 }

```

---

File 411 **lwarp-seqspl.it.sty**

§ 517 Package **seqsplit**

(Emulates or patches code by BORIS VEYTSMAN.)

Pkg seqsplit seqsplit is patched for use by lwarp.

For HTML output, the results are similar to print mode, and respond to window size.

 **svg math results** For SVG math, the output differs from print mode in that the contents are formatted in a minipage, which is then inline with the surrounding math.

For MATHJAX, the contents are used as-is.

**for HTML output:** 1 \LWR@ProvidesPackagePass{seqsplit}[2006/08/07]

Special handling because `lwarp` uses a box for SVG math, which does not normally allow line breaks, so a print-mode minipage must be used to allow line breaks. The minipage will not be wrapped inline with any surrounding math.

```

2 \begin{warpHTML}
3 \LetLtxMacro\LWR@orig@seqsplit\seqsplit
4
5 \renewcommand*{\seqsplit}[1]{%
6 \ifmode%
7 \begin{LWR@print@minipage}{6in}%
8 \LWR@orig@seqsplit{#1}%
9 \end{LWR@print@minipage}%
10 \else%

```

```

11 \InlineClass[word-wrap:break-word]{seqsplit}{\LWR@orig@seqsplit{#1}}%
12 \fi
13 }

```

Between characters, an empty HTML comment is placed to allow a line wrap in the HTML source, without adding spaces in the output.

```

14 \AtBeginDocument{
15 \newcommand*\LWR@HTML@seqinsert{%
16 \LWR@htmlcomment{ }%
17 }
18 \LWR@formatted{seqinsert}
19 }
20 \end{warpHTML}
21
22 \begin{warpMathJax}
23 \CustomizeMathJax{\newcommand{\seqsplit}[1]{#1}}
24 \end{warpMathJax}

```

---

File 412 **lwarp-setspace.sty**

§ 518 Package **setspace**

*(Emulates or patches code by ROBIN FAIRBAIRNS.)*

Pkg setspace **setspace** is emulated.

Discard all options for lwarp-setspace:

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{setspace}[2011/12/19]
2
3 \newcommand*\setstretch[1]{}
4 \newcommand*\SetSinglespace[1]{}
5 \newcommand*\singlespacing{}
6 \newcommand*\onehalfspacing{}
7 \newcommand*\doublespacing{}
8
9 \newenvironment{singlespace}
10 {
11 \LWR@forcenewpage
12 \BlockClass{singlespace}
13 }
14 {\endBlockClass}
15
16 \newenvironment{singlespace*}
17 {
18 \LWR@forcenewpage
19 \BlockClass{singlespace}
20 }
21 {\endBlockClass}
22
23 \newenvironment{spacing}[1]{
24

```

---

```

25 }{
26
27 }
28
29 \newenvironment*{onehalfspace}
30 {
31 \LWR@forcenewpage
32 \BlockClass{onehalfspace}
33 }
34 {\endBlockClass}
35
36 \newenvironment*{doublespace}
37 {
38 \LWR@forcenewpage
39 \BlockClass{doublespace}
40 }
41 {\endBlockClass}

```

---

File 413 **lwarp-shadethm.sty**

§ 519 Package **shadethm**

*(Emulates or patches code by JIM HEFFERON.)*

Pkg shadethm shadethm is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{shadethm}[1999/11/23]
2 \newenvironment{LWR@HTML@shadebox}
3 {%
4 \convertcolorspec{named}{shadethmcolor}{HTML}\LWR@tempcolor%
5 \convertcolorspec{named}{shaderulecolor}{HTML}\LWR@tempcolortwo%
6 \begin{BlockClass}%
7 background: \LWR@origpound\LWR@tempcolor ;
8 border: 1px solid \LWR@origpound\LWR@tempcolortwo ;
9]{shadebox}
10}%
11 {\end{BlockClass}}
12 \LWR@formattedenv{shadebox}

```

---

File 414 **lwarp-shadow.sty**

§ 520 Package **shadow**

*(Emulates or patches code by MAURO ORLANDINI.)*

Pkg shadow shadow is emulated.

**for HTML output:** Discard all options for lwarp-shadow:

```

1 \LWR@ProvidesPackageDrop{shadow}[2003/02/19]

```

```

2 \newdimen\shboxsep
3 \newdimen\shboxrule
4 \newdimen\shdim
5
6 \newcommand{\shabox}[1]{%
7 \InlineClass{shabox}{#1}%
8 }

```

---

File 415 **lwarp-shapepar.sty**

§ 521 Package **shapepar**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg shapepar shapepar is patched for use by lwarp. Shapes appear in print mode, as well as inside a lateximage, but are ignored for HTML.

**for HTML output:** 1 \LWR@ProvidesPackagePass{shapepar}[2013/03/26]

```

2 \newcommand*{\LWR@HTML@shapepar}[2][{}]{
3 \LWR@formatted{shapepar}
4
5 \NewDocumentCommand{\LWR@HTML@cutout}{m d()}{}
6 \LWR@formatted{cutout}

```

---

File 416 **lwarp-showidx.sty**

§ 522 Package **showidx**

Pkg showidx showidx is ignored.

**for HTML output:** Discard all options for lwarp-showidx:

```
1 \LWR@ProvidesPackageDrop{showidx}[2014/09/29]
```

\@wrindex is redefined \AtBeginDocument by the lwarp core.

---

File 417 **lwarp-showkeys.sty**

§ 523 Package **showkeys**

*(Emulates or patches code by DAVID CARLISLE, MORTEN HØGHOLM.)*

Pkg showkeys showkeys is ignored.

**for HTML output:** Discard all options for lwarp-showkeys:

```
1 \LWR@ProvidesPackageDrop{showkeys}[2014/10/28]
```

---

```
2 \NewDocumentCommand{\showkeys}{s}{}
```

---

File 418 **lwarp-showtags.sty**

§ 524 Package **showtags**

Pkg showtags showtags is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{showtags}% no version is given

```
2 \newcommand{\thecitetag}[1]{}

```

---

File 419 **lwarp-shuffle.sty**

§ 525 Package **shuffle**

*(Emulates or patches code by JULIAN GILBEY AND ANTOINE LEJAY.)*

Pkg shuffle shuffle is emulated for SVG math, and also emulated for MATHJAX.

The font used for shuffle may not render correctly when converted to SVG math, so a picture environment drawing is used instead.

For MATHJAX, the Unicode character is used, and for \cshuffle a \bar is added.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{shuffle}[2008/10/27]  
2 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}

```
3 \newcommand*\LWR@shuffle@start}{%
4 \hspace*{.2em}
5 \begin{picture}(.75,0.65)
6 \setlength{\unitlength}{1em}
7 \put(0,0){\line(1,0){.75}}
8 \put(0,0){\line(0,1){.5}}
9 \put(.375,0){\line(0,1){.5}}
10 \put(.75,0){\line(0,1){.5}}
11 }
12
13 \newcommand*\LWR@shuffle@finish}{%
14 \end{picture}
15 \hspace*{.75em}
16 \hspace*{.2em}
17 }
18
19 \newcommand*\shuffle}{%
20 \LWR@shuffle@start%
21 \LWR@shuffle@finish%
22 }
23
```

```

24 \newcommand*\cshuffle}{%
25 \LWR@shuffle@start%
26 \put(.05,.65){\line(1,0){.65}}%
27 \LWR@shuffle@finish%
28 }

29 \begin{warpMathJax}
30 \CustomizeMathJax{\newcommand{\shuffle}{\mathbin{\unicode{0x29E2}}}}
31 \CustomizeMathJax{\newcommand{\cshuffle}{%
32 \mathbin{\LWRoverlaysymbols{\raise{.6ex}{-}}{\unicode{0x29E2}}}%
33 }}
34 \end{warpMathJax}

```

---

File 420 **lwarp-sidecap.sty**

§ 526 Package **sidecap**

*(Emulates or patches code by ROLF NIEPRASCHK, HUBERT GÄSSLEIN.)*

Pkg sidecap sidecap is emulated.

**for HTML output:** Discard all options for lwarp-sidecap.

```
1 \LWR@ProvidesPackageDrop{sidecap}[2003/06/06]
```

See:

<http://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment> regarding the creation of starred environments with xparse.

```

2 \NewDocumentEnvironment{SCTable}{soo}
3 {\IfValueTF{#3}{\table[#3]}{\table}}
4 {\endtable}
5
6 \ExplSyntaxOn
7 \cs_new:cpn {SCTable*} {\SCTable*}
8 \cs_new_eq:cN {endSCTable*} \endSCTable
9 \ExplSyntaxOff
10
11
12 \NewDocumentEnvironment{SCfigure}{soo}
13 {\IfValueTF{#3}{\figure[#3]}{\figure}}
14 {\endfigure}
15
16 \ExplSyntaxOn
17 \cs_new:cpn {SCfigure*} {\SCfigure*}
18 \cs_new_eq:cN {endSCfigure*} \endSCfigure
19 \ExplSyntaxOff
20
21
22 \newenvironment*{wide}{}{}

```

File 421 **lwarp-sidenotes.sty**

§ 527 Package **sidenotes**

(Emulates or patches code by ANDY THOMAS, OLIVER SCHEBAUM.)

Pkg sidenotes Patched for lwarp.

for HTML output: Load the original package:

```
1 \LWR@ProvidesPackagePass{sidenotes}
```

The following patch sidenotes for use with lwarp:

```
\sidecaption * [⟨entry⟩] [⟨offset⟩] {⟨text⟩}

2 \RenewDocumentCommand \sidecaption {s o o m}
3 {
4 \LWR@stoppars
5 \begingroup
6 \captionsetup{style=sidecaption}%
7 \IfBooleanTF{#1}
8 { % starred
9 \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
10 \caption*{#4}%
11 \end{BlockClass}
12 }
13 { % unstarred
14 \IfNoValueOrEmptyTF{#2}
15 {\def\@sidenotes@sidecaption@tof{#4}}
16 {\def\@sidenotes@sidecaption@tof{#2}}
17 \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
18 \caption[\@sidenotes@sidecaption@tof]{#4}
19 \end{BlockClass}
20 }
21 \endgroup
22 \LWR@startpars
23 }
```

Borrowed from the lwarp version of keyfloat:

```
24 \NewDocumentEnvironment{KFLTsidefloat}{0{-1.2ex} m}
25 {% start
26 \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{marginblock}%
27 \renewcommand*\@capttype{#2}%
28 }
29 {%
30 \endLWR@BlockClassWP%
31 }
32
33 \RenewDocumentEnvironment{marginfigure}{o}
```

```

34 {\begin{KFLTsidenotes@marginfloat}{figure}}
35 {\end{KFLTsidenotes@marginfloat}}
36
37 \RenewDocumentEnvironment{margintable}{o}
38 {\begin{KFLTsidenotes@marginfloat}{table}}
39 {\end{KFLTsidenotes@marginfloat}}

```

The following were changed by `sidenotes`, and now are reset back to their `lwarp`-supported originals:

Restoring the definition from the  $\LaTeX 2_{\epsilon}$  `article.cls` source:

```

40 \renewenvironment{figure*}
41 {\@dblfloat{figure}}
42 {\end@dblfloat}
43
44 \renewenvironment{table*}
45 {\@dblfloat{table}}
46 {\end@dblfloat}

```

For `MATHJAX`:



Note that `sidenotes` does not support `\sidenote` inside math in print mode. Use `\sidenotemark` and `\sidenotetext` instead.

```

47 \begin{warpMathJax}
48 \providecommand{\sidenotename}{sidenote}
49 \appto\LWR@syncnotenumbers{\LWR@synconenotenummer{LWRsidenote}{\thesidenote}}
50 \appto\LWR@syncnotenames{\LWR@synconenotename{LWRsidenote}{\sidenotename}}
51 \CustomizeMathJax{\def\LWRsidenote{1}}
52 \CustomizeMathJax{\newcommand{\sidenotemark}[1][\LWRsidenote]{\mathrm{#1}}}
53 \end{warpMathJax}

```

The following is not defined since is not allowed inside math in print mode, and also would have to be modified to parse the optional offset argument:

```
\CustomizeMathJax{\newcommand{\sidenote}[2][\LWRsidenote]{\mathrm{#1}}}
```

File 422 **lwarp-simplebnf.sty**

§ 528 Package **simplebnf**

*(Emulates or patches code by JAY LEE.)*

Pkg simplebnf simplebnf is patched for use by lwarp.

for HTML output: 1 \LWR@ProvidesPackagePass[simplebnf][2020/09/01]

The entire object is placed inside a `lateximage` whose `alt` text is the  $\LaTeX$  source BNF expression.

```

2 \ExplSyntaxOn
3
4 \RenewDocumentEnvironment { bnfgrammar } { +b }
5 {
6 %% \l__input_seq is a list of term definitions.
7 \regex_split:nnN { ;; } { #1 } \l__input_seq
8 \begin{center}
9 \begin{lateximage}[#1]% lwarp
10 \tl_set:Nn \l__table_tl
11 {
12 \begin{tabular}{lcll}
13 }
14 \bool_set_true:N \l_tmp_first_term % Is this the first term in this grammar?
15 \seq_map_inline:Nn \l__input_seq
16 {
17 %% \l__term_seq - (term, rhses)...
18 %% \l__term_tl - term
19 %% \l__keypairs_tl - rhses
20 \regex_split:nnN { ::= } { ##1 } \l__term_seq
21 \seq_pop_left:NN \l__term_seq \l__term_tl
22 \seq_pop_left:NN \l__term_seq \l__keypairs_tl
23
24 \regex_replace_once:nnN { ^\s+ } {} \l__term_tl
25
26 \bool_if:NTF \l_tmp_first_term
27 {
28 \bool_set_false:N \l_tmp_first_term
29 }
30 {
31 \tl_put_right:Nn \l__table_tl { \ }
32 }
33 \tl_put_right:Nx \l__table_tl
34 {
35 \bnfexpr { \l__term_tl } & \g__simplebnf_defeq_tl &
36 }
37 %% \l__keypairs_seq - (rhs:annot | rhs)...
38 \seq_set_split:NnV \l__keypairs_seq { | } \l__keypairs_tl
39
40 \bool_set_true:N \l__first_rhs
41 \seq_map_function:NN \l__keypairs_seq \simplebnf_typeset_rhs:n
42 }
43
44 \tl_put_right:Nn \l__table_tl { \end{tabular} }
45 \tl_use:N \l__table_tl
46 \end{lateximage}% lwarp
47 \end{center}
48 }
49 { }
50
51 \ExplSyntaxOff

```

File 423 **lwarp-SIunits.sty**

§ 529 Package **Slunits**

(Emulates or patches code by MARCEL HELDOORN.)

Pkg SIunits **Slunits** is patched for use by lwarp.

For SVG math, it is recommended to use `\unit` where possible, which combines the entire expression into a single `lateximage`, and adds the `alt` tag containing the  $\LaTeX$  code, allowing for copy/paste. When units are used outside of the `\unit` macro, each unit macro will have its own `lateximage`, and each will have the `alt` tag set according to `\MathImageAltText`, which defaults to `(math image)`.

For MATHJAX, individual units used in text will appear as SVG images, since `\ensuremath` is used in the original definitions, and `\ensuremath` often has expressions which do not work well in MATHJAX, so it is always forced to an SVG image. If, however, `\unit` is used, the result is expressed with MATHJAX instead of an SVG image.

**for HTML output:** 1 `\LWR@ProvidesPackagePass{SIunits}[2007/12/02]`

Patched for copy/paste with the HTML alt tag:

```

2 \ifbool{mathjax}{
3 \DeclareRobustCommand{\LWR@HTML@unit}[2]{%
4 \LWR@subsingledollar*% lwarp
5 {% alt tag
6 \textbackslash{}unit\{\LWR@HTMLsanitize{#1}\}%
7 \{ \LWR@HTMLsanitize{#2}\}% extra space
8 }%
9 {SIunits}% add'l hashing
10 {%
11 #1\,{#2}%
12 }% contents
13 }
14 }{% not MathJax
15 \DeclareRobustCommand{\LWR@HTML@unit}[2]{%
16 \@inunitcommandtrue% original
17 \LWR@subsingledollar*% lwarp
18 {% alt tag
19 \textbackslash{}unit\{\LWR@HTMLsanitize{#1}\}%
20 \{ \LWR@HTMLsanitize{#2}\}% extra space
21 }%
22 {SIunits}% add'l hashing
23 {%
24 \LWR@origensuredmath{% lwarp modification
25 \SI@fstyle{%
26 {#1}\@qsk\period@active{#2}%
27 }% original
28 }%
29 }% contents

```

```

30 \@inunitcommandfalse% original
31 }
32 }% not MathJax
33 \LWR@formatted{unit}

```

#### For MATHJAX:

```

34 \begin{warpMathJax}
35 \LWR@infoprocessingmathjax{SIunits}
36
37 \CustomizeMathJax{\newcommand{\one}}{}}
38 \CustomizeMathJax{\newcommand{\meter}}{\metre}}
39 \CustomizeMathJax{\newcommand{\deka}}{\deca}}
40 \CustomizeMathJax{\newcommand{\dekad}}{\decad}}
41 \CustomizeMathJax{\newcommand{\per}}{/}}
42 \CustomizeMathJax{\newcommand{\usk}}{\;}}
43 \CustomizeMathJax{\newcommand{\unit}[2]{#1\,{#2}}}
44 \CustomizeMathJax{\newcommand{\power}[2]{#1^{#2}}}
45
46 \AtBeginDocument{%
47 \if@redefsquare
48 \CustomizeMathJax{\renewcommand{\square}[1]{\power{#1}{2}}}
49 \else
50 \if@defsquaren
51 \CustomizeMathJax{\newcommand{\square}[1]{\power{#1}{2}}}
52 \else
53 \CustomizeMathJax{\renewcommand{\square}[1]{\power{#1}{2}}}
54 \fi %\if@defsquaren
55 \fi %\if@redefsquare
56 } %\AtBeginDocument
57
58 \CustomizeMathJax{\newcommand{\squared}}{^2}}
59 \CustomizeMathJax{\newcommand{\cubic}[1]{\power{#1}{3}}}
60 \CustomizeMathJax{\newcommand{\cubed}}{^3}}
61 \CustomizeMathJax{\newcommand{\fourth}[1]{\power{#1}{4}}}
62 \CustomizeMathJax{\newcommand{\reciprocal}[1]{\power{#1}{-1}}}
63 \CustomizeMathJax{\newcommand{\rp}{\reciprocal}}
64 \CustomizeMathJax{\newcommand{\rpsquare}[1]{\power{#1}{-2}}}
65 \CustomizeMathJax{\newcommand{\rpsquared}}{^-2}}
66 \CustomizeMathJax{\newcommand{\rpcubic}[1]{\power{#1}{-3}}}
67 \CustomizeMathJax{\newcommand{\rpcubed}}{^-3}}
68 \CustomizeMathJax{\newcommand{\rpfourth}[1]{\power{#1}{-4}}}
69 \CustomizeMathJax{\newcommand{\yocto}{\mathrm{y}}}
70 \CustomizeMathJax{\newcommand{\zepto}{\mathrm{z}}}
71 \CustomizeMathJax{\newcommand{\atto}{\mathrm{a}}}
72 \CustomizeMathJax{\newcommand{\femto}{\mathrm{f}}}
73 \CustomizeMathJax{\newcommand{\pico}{\mathrm{p}}}
74 \CustomizeMathJax{\newcommand{\nano}{\mathrm{n}}}
75 \CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
76 \CustomizeMathJax{\newcommand{\milli}{\mathrm{m}}}
77 \CustomizeMathJax{\newcommand{\centi}{\mathrm{c}}}
78 \CustomizeMathJax{\newcommand{\deci}{\mathrm{d}}}
79 \CustomizeMathJax{\newcommand{\deca}{\mathrm{da}}}
80 \CustomizeMathJax{\newcommand{\hecto}{\mathrm{h}}}
81 \CustomizeMathJax{\newcommand{\kilo}{\mathrm{k}}}

```

```
82 \CustomizeMathJax{\newcommand{\mega}{\mathrm{M}}}
83 \CustomizeMathJax{\newcommand{\giga}{\mathrm{G}}}
84 \CustomizeMathJax{\newcommand{\tera}{\mathrm{T}}}
85 \CustomizeMathJax{\newcommand{\peta}{\mathrm{P}}}
86 \CustomizeMathJax{\newcommand{\exa}{\mathrm{E}}}
87 \CustomizeMathJax{\newcommand{\zetta}{\mathrm{Z}}}
88 \CustomizeMathJax{\newcommand{\yotta}{\mathrm{Y}}}
89 \CustomizeMathJax{\newcommand{\yoctod}{\power{10}{-24}}}
90 \CustomizeMathJax{\newcommand{\zeptod}{\power{10}{-21}}}
91 \CustomizeMathJax{\newcommand{\atod}{\power{10}{-18}}}
92 \CustomizeMathJax{\newcommand{\femtod}{\power{10}{-15}}}
93 \CustomizeMathJax{\newcommand{\picod}{\power{10}{-12}}}
94 \CustomizeMathJax{\newcommand{\nanod}{\power{10}{-9}}}
95 \CustomizeMathJax{\newcommand{\microd}{\power{10}{-6}}}
96 \CustomizeMathJax{\newcommand{\millid}{\power{10}{-3}}}
97 \CustomizeMathJax{\newcommand{\centid}{\power{10}{-2}}}
98 \CustomizeMathJax{\newcommand{\decid}{\power{10}{-1}}}
99 \CustomizeMathJax{\newcommand{\decad}{\power{10}{1}}}
100 \CustomizeMathJax{\newcommand{\hectod}{\power{10}{2}}}
101 \CustomizeMathJax{\newcommand{\kilod}{\power{10}{3}}}
102 \CustomizeMathJax{\newcommand{\megad}{\power{10}{6}}}
103 \CustomizeMathJax{\newcommand{\gigad}{\power{10}{9}}}
104 \CustomizeMathJax{\newcommand{\terad}{\power{10}{12}}}
105 \CustomizeMathJax{\newcommand{\petad}{\power{10}{15}}}
106 \CustomizeMathJax{\newcommand{\exad}{\power{10}{18}}}
107 \CustomizeMathJax{\newcommand{\zettad}{\power{10}{21}}}
108 \CustomizeMathJax{\newcommand{\yottad}{\power{10}{24}}}
109 \CustomizeMathJax{\newcommand{\gram}{\mathrm{g}}}
110 \CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
111 \CustomizeMathJax{\newcommand{\kilogram}{\kilo\gram}}
112 \CustomizeMathJax{\newcommand{\second}{\mathrm{s}}}
113 \CustomizeMathJax{\newcommand{\ampere}{\mathrm{A}}}
114 \CustomizeMathJax{\newcommand{\kelvin}{\mathrm{K}}}
115 \CustomizeMathJax{\newcommand{\mole}{\mathrm{mol}}}
116 \CustomizeMathJax{\newcommand{\candela}{\mathrm{cd}}}
117 \CustomizeMathJax{\newcommand{\radian}{\mathrm{rad}}}
118 \CustomizeMathJax{\newcommand{\steradian}{\mathrm{sr}}}
119 \CustomizeMathJax{\newcommand{\hertz}{\mathrm{Hz}}}
120 \CustomizeMathJax{\newcommand{\newton}{\mathrm{N}}}
121 \CustomizeMathJax{\newcommand{\pascal}{\mathrm{Pa}}}
122 \CustomizeMathJax{\newcommand{\joule}{\mathrm{J}}}
123 \CustomizeMathJax{\newcommand{\watt}{\mathrm{W}}}
124 \CustomizeMathJax{\newcommand{\coulomb}{\mathrm{C}}}
125 \CustomizeMathJax{\newcommand{\volt}{\mathrm{V}}}
126 \CustomizeMathJax{\newcommand{\farad}{\mathrm{F}}}
127 \CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
128 \CustomizeMathJax{\newcommand{\siemens}{\mathrm{S}}}
129 \CustomizeMathJax{\newcommand{\weber}{\mathrm{Wb}}}
130 \CustomizeMathJax{\newcommand{\tesla}{\mathrm{T}}}
131 \CustomizeMathJax{\newcommand{\henry}{\mathrm{H}}}
132 \CustomizeMathJax{\newcommand{\degreecelsius}{\mathrm{\unicode{x2103}}}}
133 \CustomizeMathJax{\newcommand{\celsius}{\degreecelsius}}
134 \CustomizeMathJax{\newcommand{\lumen}{\mathrm{lm}}}
135 \CustomizeMathJax{\newcommand{\lux}{\mathrm{lx}}}
136 \CustomizeMathJax{\newcommand{\becquerel}{\mathrm{Bq}}}
```

```

137 \CustomizeMathJax{\newcommand{\sievert}{\mathrm{Sv}}}
138 \CustomizeMathJax{\newcommand{\katal}{\mathrm{kat}}}
139
140 \ifdef{\radianbase}{
141 \CustomizeMathJax{\newcommand{\radianbase}%
142 {\metre\usk\reciprocal\metre}}
143 \CustomizeMathJax{\newcommand{\steradianbase}%
144 {\squaremetre\usk\rpsquare\metre}}
145 \CustomizeMathJax{\newcommand{\hertzbase}%
146 {\reciprocal\second}}
147 \CustomizeMathJax{\newcommand{\newtonbase}%
148 {\metre\usk\kilogram\usk\second\rpsquared}}
149 \CustomizeMathJax{\newcommand{\pascalbase}%
150 {\reciprocal\metre\usk\kilogram\usk\second\rpsquared}}
151 \CustomizeMathJax{\newcommand{\joulebase}%
152 {\squaremetre\usk\kilogram\usk\second\rpsquared}}
153 \CustomizeMathJax{\newcommand{\wattbase}%
154 {\squaremetre\usk\kilogram\usk\rpcubic\second}}
155 \CustomizeMathJax{\newcommand{\coulombbase}%
156 {\ampere\usk\second}}
157 \CustomizeMathJax{\newcommand{\voltbase}%
158 {\squaremetre\usk\kilogram\usk\rpcubic\second\usk\reciprocal\ampere}}
159 \CustomizeMathJax{\newcommand{\faradbase}%
160 {\rpsquare\metre\usk\reciprocal\kilogram\usk\fourth\second\usk\ampere\squared}}
161 \CustomizeMathJax{\newcommand{\ohmbase}%
162 {\squaremetre\usk\kilogram\usk\rpcubic\second\usk\rpsquare\ampere}}
163 \CustomizeMathJax{\newcommand{\siemensbase}%
164 {\rpsquare\metre\usk\reciprocal\kilogram\usk\cubic\second\usk\ampere\squared}}
165 \CustomizeMathJax{\newcommand{\weberbase}%
166 {\squaremetre\usk\kilogram\usk\second\rpsquared\usk\reciprocal\ampere}}
167 \CustomizeMathJax{\newcommand{\teslabase}%
168 {\kilogram\usk\second\rpsquared\usk\reciprocal\ampere}}
169 \CustomizeMathJax{\newcommand{\henrybase}%
170 {\squaremetre\usk\kilogram\usk\second\rpsquared\usk\rpsquare\ampere}}
171 \CustomizeMathJax{\newcommand{\celsiusbase}%
172 {\kelvin}}
173 \CustomizeMathJax{\newcommand{\lumenbase}%
174 {\candela\usk\squaremetre\usk\rpsquare\metre}}
175 \CustomizeMathJax{\newcommand{\luxbase}%
176 {\candela\usk\squaremetre\usk\rpfourth\metre}}
177 \CustomizeMathJax{\newcommand{\becquerelbase}%
178 {\hertzbase}}
179 \CustomizeMathJax{\newcommand{\graybase}%
180 {\squaremetre\usk\second\rpsquared}}
181 \CustomizeMathJax{\newcommand{\sievertbase}%
182 {\graybase}}
183 \CustomizeMathJax{\newcommand{\katalbase}%
184 {\rp\second\usk\mole }}
185 }{}
186
187 \ifdef{\derradian}{
188 \CustomizeMathJax{\newcommand{\derradian}%
189 {\metre\usk\reciprocal\metre}}
190 \CustomizeMathJax{\newcommand{\dersteradian}%
191 {\squaremetre\usk\rpsquare\metre}}

```

```

192 \CustomizeMathJax{\newcommand{\derhertz}%
193 {\reciprocal\second}}
194 \CustomizeMathJax{\newcommand{\dernewton}%
195 {\metre\usk\kilogram\usk\second\rpsquared}}
196 \CustomizeMathJax{\newcommand{\derpascal}%
197 {\newton\usk\rpsquare\metre}}
198 \CustomizeMathJax{\newcommand{\derjoule}%
199 {\newton\usk\metre}}
200 \CustomizeMathJax{\newcommand{\derwatt}%
201 {\joule\usk\reciprocal\second}}
202 \CustomizeMathJax{\newcommand{\dercoulomb}%
203 {\ampere\usk\second}}
204 \CustomizeMathJax{\newcommand{\dervolt}%
205 {\watt\usk\reciprocal\ampere}}
206 \CustomizeMathJax{\newcommand{\derfarad}%
207 {\coulomb\usk\reciprocal\volt}}
208 \CustomizeMathJax{\newcommand{\derohm}%
209 {\volt\usk\reciprocal\ampere}}
210 \CustomizeMathJax{\newcommand{\dersiemens}%
211 {\ampere\usk\reciprocal\volt}}
212 \CustomizeMathJax{\newcommand{\derweber}%
213 {\squaremetre\usk\kilogram\usk\second\rpsquared\usk\reciprocal\ampere}}
214 \CustomizeMathJax{\newcommand{\dertesla}%
215 {\weber\usk\rpsquare\metre}}
216 \CustomizeMathJax{\newcommand{\derhenry}%
217 {\weber\usk\reciprocal\ampere}}
218 \CustomizeMathJax{\newcommand{\dercelsius}%
219 {\kelvin}}
220 \CustomizeMathJax{\newcommand{\derlumen}%
221 {\candela\usk\steradian}}
222 \CustomizeMathJax{\newcommand{\derlux}%
223 {\lumen\usk\rpsquare\metre}}
224 \CustomizeMathJax{\newcommand{\derbecquerel}%
225 {\derhertz}}
226 \CustomizeMathJax{\newcommand{\dergray}%
227 {\joule\usk\reciprocal\kilogram}}
228 \CustomizeMathJax{\newcommand{\dersievert}%
229 {\dergray}}
230 \CustomizeMathJax{\newcommand{\derkatal}%
231 {\katalbase}}
232 }{}
233
234 \CustomizeMathJax{\newcommand{\minute}{\mathrm{min}}}
235 \CustomizeMathJax{\newcommand{\hour}{\mathrm{h}}}
236 \CustomizeMathJax{\newcommand{\dday}{\mathrm{d}}}
237 \CustomizeMathJax{\newcommand{\degree}{\mathrm{^\circ}}}
238 \CustomizeMathJax{\newcommand{\pminute}{^\prime}}
239 \CustomizeMathJax{\newcommand{\arcminute}{^\prime}}
240 \CustomizeMathJax{\newcommand{\pasecond}{^\prime\prime}}
241 \CustomizeMathJax{\newcommand{\arcsecond}{^\prime\prime}}
242 \CustomizeMathJax{\newcommand{\ton}{\mathrm{t}}}
243 \CustomizeMathJax{\newcommand{\tonne}{\mathrm{t}}}
244 \CustomizeMathJax{\newcommand{\liter}{\mathrm{L}}}
245 \CustomizeMathJax{\newcommand{\litre}{\mathrm{L}}}
246 \CustomizeMathJax{\newcommand{\neper}{\mathrm{Np}}}

```

```

247 \CustomizeMathJax{\newcommand{\bel}{\mathrm{B}}}
248 \CustomizeMathJax{\newcommand{\curie}{\mathrm{Ci}}}
249 \CustomizeMathJax{\newcommand{\rad}{\mathrm{rad}}}
250 \CustomizeMathJax{\newcommand{\arad}{\mathrm{rd}}}
251 \CustomizeMathJax{\newcommand{\rem}{\mathrm{rem}}}
252 \CustomizeMathJax{\newcommand{\roentgen}{\mathrm{R}}}
253 \CustomizeMathJax{\newcommand{\electronvolt}{\mathrm{\mathrm{eV}}}}
254 \CustomizeMathJax{\newcommand{\atomicmass}{\mathrm{u}}}
255 \CustomizeMathJax{\newcommand{\atomicmassunit}{\mathrm{u}}}
256 \CustomizeMathJax{\newcommand{\dalton}{\mathrm{Da}}}
257 \CustomizeMathJax{\newcommand{\are}{\mathrm{a}}}
258 \CustomizeMathJax{\newcommand{\hectare}{\mathrm{\hecto\are}}}
259 \CustomizeMathJax{\newcommand{\barn}{\mathrm{b}}}
260 \CustomizeMathJax{\newcommand{\bbar}{\mathrm{\bar{b}}}}
261 \CustomizeMathJax{\newcommand{\gal}{\mathrm{Gal}}}
262 \CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\unicode{x212B}}}}
263 \CustomizeMathJax{\newcommand{\rperminute}{\mathrm{r}\per\minute}}
264 \CustomizeMathJax{\newcommand{\rpersecond}{\mathrm{r}\per\second}}
265 \CustomizeMathJax{\newcommand{\squaremetre}{\power{\metre}{2}}}
266 \CustomizeMathJax{\newcommand{\cubicmetre}{\cubic\metre}}
267 \CustomizeMathJax{\newcommand{\graypersecond}{\gray\per\second}}
268 \CustomizeMathJax{\newcommand{\graypersecondnp}{\gray\usk\reciprocal\second}}
269 \CustomizeMathJax{\newcommand{\metrepersquaresecond}{\metre\per\second\squared}}
270 \CustomizeMathJax{\newcommand{\metrepersquaresecondnp}{\metre\usk\second\rpsquared}}
271 \CustomizeMathJax{\newcommand{\joulepermole}{\joule\per\mole}}
272 \CustomizeMathJax{\newcommand{\joulepermolenp}{\joule\usk\reciprocal\mole}}
273 \CustomizeMathJax{\newcommand{\molepercubicmetre}{\mole\per\cubic\metre}}
274 \CustomizeMathJax{\newcommand{\molepercubicmetrenp}{\mole\usk\rpcubic\metre}}
275 \CustomizeMathJax{\newcommand{\radianpersquaresecond}{\radian\per\second\squared}}
276 \CustomizeMathJax{\newcommand{\radianpersquaresecondnp}{\radian\usk\second\rpsquared}}
277 \CustomizeMathJax{\newcommand{\kilogramsquaremetrepersecond}{\kilogram\usk\squaremetre\per\second}}
278 \CustomizeMathJax{\newcommand{\kilogramsquaremetrepersecondnp}{\kilogram\usk\squaremetre\usk\reciproca}}
279 \CustomizeMathJax{\newcommand{\radianpersecond}{\radian\per\second}}
280 \CustomizeMathJax{\newcommand{\radianpersecondnp}{\radian\usk\reciprocal\second}}
281 \CustomizeMathJax{\newcommand{\squaremetrepercubicmetre}{\squaremetre\per\cubic\metre}}
282 \CustomizeMathJax{\newcommand{\squaremetrepercubicmetrenp}{\squaremetre\usk\rpcubic\metre}}
283 \CustomizeMathJax{\newcommand{\katalpercubicmetre}{\katal\per\cubic\metre}}
284 \CustomizeMathJax{\newcommand{\katalpercubicmetrenp}{\katal\usk\rpcubic\metre}}
285 \CustomizeMathJax{\newcommand{\coulombpermol}{\coulomb\per\mole}}
286 \CustomizeMathJax{\newcommand{\coulombpermolnp}{\coulomb\usk\reciprocal\mole}}
287 \CustomizeMathJax{\newcommand{\amperepersquaremetre}{\ampere\per\squaremetre}}
288 \CustomizeMathJax{\newcommand{\amperepersquaremetrenp}{\ampere\usk\rpsquare\metre}}
289 \CustomizeMathJax{\newcommand{\kilogrampercubicmetre}{\kilogram\per\cubic\metre}}
290 \CustomizeMathJax{\newcommand{\kilogrampercubicmetrenp}{\kilogram\usk\rpcubic\metre}}
291 \CustomizeMathJax{\newcommand{\squaremetrepernewtonsecond}{\squaremetre\per\newton\usk\second}}
292 \CustomizeMathJax{\newcommand{\squaremetrepernewtonsecondnp}{\squaremetre\usk\reciprocal\newton\usk\re}}
293 \CustomizeMathJax{\newcommand{\pascalsecond}{\pascal\usk\second}}
294 \CustomizeMathJax{\newcommand{\coulombpercubicmetre}{\coulomb\per\cubic\metre}}
295 \CustomizeMathJax{\newcommand{\coulombpercubicmetrenp}{\coulomb\usk\rpcubic\metre}}
296 \CustomizeMathJax{\newcommand{\ampere metre second}{\ampere\usk\metre\usk\second}}
297 \CustomizeMathJax{\newcommand{\voltpermetre}{\volt\per\metre}}
298 \CustomizeMathJax{\newcommand{\voltpermetrenp}{\volt\usk\reciprocal\metre}}
299 \CustomizeMathJax{\newcommand{\coulombpersquaremetre}{\coulomb\per\squaremetre}}
300 \CustomizeMathJax{\newcommand{\coulombpersquaremetrenp}{\coulomb\usk\rpsquare\metre}}
301 \CustomizeMathJax{\newcommand{\faradpermetre}{\farad\per\metre}}

```

```
302 \CustomizeMathJax{\newcommand{\faradpermetrenp}{\farad\usk\reciprocal\metre}}
303 \CustomizeMathJax{\newcommand{\ohmmetre}{\ohm\usk\metre}}
304 \CustomizeMathJax{\newcommand{\kilowatthour}{\kilo\watt\hour}}
305 \CustomizeMathJax{\newcommand{\wattpersquaremetre}{\watt\per\squaremetre}}
306 \CustomizeMathJax{\newcommand{\wattpersquaremetrenp}{\watt\usk\rpsquare\metre}}
307 \CustomizeMathJax{\newcommand{\joulepersquaremetre}{\joule\per\squaremetre}}
308 \CustomizeMathJax{\newcommand{\joulepersquaremetrenp}{\joule\usk\rpsquare\metre}}
309 \CustomizeMathJax{\newcommand{\newtonpercubicmetre}{\newton\per\cubic\metre}}
310 \CustomizeMathJax{\newcommand{\newtonpercubicmetrenp}{\newton\usk\rpcubic\metre}}
311 \CustomizeMathJax{\newcommand{\newtonperkilogram}{\newton\per\kilogram}}
312 \CustomizeMathJax{\newcommand{\newtonperkilogramnp}{\newton\usk\reciprocal\kilogram}}
313 \CustomizeMathJax{\newcommand{\jouleperkelvin}{\joule\per\kelvin}}
314 \CustomizeMathJax{\newcommand{\jouleperkelvinnp}{\joule\usk\reciprocal\kelvin}}
315 \CustomizeMathJax{\newcommand{\jouleperkilogram}{\joule\per\kilogram}}
316 \CustomizeMathJax{\newcommand{\jouleperkilogramnp}{\joule\usk\reciprocal\kilogram}}
317 \CustomizeMathJax{\newcommand{\coulombperkilogram}{\coulomb\per\kilogram}}
318 \CustomizeMathJax{\newcommand{\coulombperkilogramnp}{\coulomb\usk\reciprocal\kilogram}}
319 \CustomizeMathJax{\newcommand{\squaremetrepersecond}{\squaremetre\per\second}}
320 \CustomizeMathJax{\newcommand{\squaremetrepersecondnp}{\squaremetre\usk\reciprocal\second}}
321 \CustomizeMathJax{\newcommand{\squaremetrepersquaresecond}{\squaremetre\per\second\squared}}
322 \CustomizeMathJax{\newcommand{\squaremetrepersquaresecondnp}{\squaremetre\usk\second\rpsquared}}
323 \CustomizeMathJax{\newcommand{\kilogrammetrepersecond}{\kilogram\usk\metre\per\second}}
324 \CustomizeMathJax{\newcommand{\kilogrammetrepersecondnp}{\kilogram\usk\metre\usk\reciprocal\second}}
325 \CustomizeMathJax{\newcommand{\candelapersquaremetre}{\candela\per\squaremetre}}
326 \CustomizeMathJax{\newcommand{\candelapersquaremetrenp}{\candela\usk\rpsquare\metre}}
327 \CustomizeMathJax{\newcommand{\amperepermetre}{\ampere\per\metre}}
328 \CustomizeMathJax{\newcommand{\amperepermetrenp}{\ampere\usk\reciprocal\metre}}
329 \CustomizeMathJax{\newcommand{\joulepertesla}{\joule\per\tesla}}
330 \CustomizeMathJax{\newcommand{\jouleperteslanp}{\joule\usk\reciprocal\tesla}}
331 \CustomizeMathJax{\newcommand{\henrypermetre}{\henry\per\metre}}
332 \CustomizeMathJax{\newcommand{\henrypermetrenp}{\henry\usk\reciprocal\metre}}
333 \CustomizeMathJax{\newcommand{\kilogrampersecond}{\kilogram\per\second}}
334 \CustomizeMathJax{\newcommand{\kilogrampersecondnp}{\kilogram\usk\reciprocal\second}}
335 \CustomizeMathJax{\newcommand{\kilogrampersquaremetresecond}{\kilogram\per\squaremetre\usk\second}}
336 \CustomizeMathJax{\newcommand{\kilogrampersquaremetresecondnp}{\kilogram\usk\rpsquare\metre\usk\reciprocal\second}}
337 \CustomizeMathJax{\newcommand{\kilogrampersquaremetre}{\kilogram\per\squaremetre}}
338 \CustomizeMathJax{\newcommand{\kilogrampersquaremetrenp}{\kilogram\usk\rpsquare\metre}}
339 \CustomizeMathJax{\newcommand{\kilogrampermetre}{\kilogram\per\metre}}
340 \CustomizeMathJax{\newcommand{\kilogrampermetrenp}{\kilogram\usk\reciprocal\metre}}
341 \CustomizeMathJax{\newcommand{\joulepermolekelvin}{\joule\per\mole\usk\kelvin}}
342 \CustomizeMathJax{\newcommand{\joulepermolekelvinnp}{\joule\usk\reciprocal\mole\usk\reciprocal\kelvin}}
343 \CustomizeMathJax{\newcommand{\kilogramperkilomole}{\kilogram\per\kilo\mole}}
344 \CustomizeMathJax{\newcommand{\kilogramperkilomolenp}{\kilogram\usk\kilo\reciprocal\mole}}
345 \CustomizeMathJax{\newcommand{\kilogramsquaremetre}{\kilogram\usk\squaremetre}}
346 \CustomizeMathJax{\newcommand{\kilogramsquaremetrenp}{\kilogramsquaremetre}}
347 \CustomizeMathJax{\newcommand{\kilogrammetrepersquaresecond}{\kilogram\usk\metre\per\second\squared}}
348 \CustomizeMathJax{\newcommand{\kilogrammetrepersquaresecondnp}{\kilogram\usk\metre\usk\second\rpsquare}}
349 \CustomizeMathJax{\newcommand{\newtonpersquaremetre}{\newton\per\squaremetre}}
350 \CustomizeMathJax{\newcommand{\newtonpersquaremetrenp}{\newton\usk\rpsquare\metre}}
351 \CustomizeMathJax{\newcommand{\persquaremetresecond}{1\per\squaremetre\usk\second}}
352 \CustomizeMathJax{\newcommand{\persquaremetresecondnp}{\rpsquare\metre\usk\reciprocal\second}}
353 \CustomizeMathJax{\newcommand{\wattperkilogram}{\watt\per\kilogram}}
354 \CustomizeMathJax{\newcommand{\wattperkilogramnp}{\watt\usk\reciprocal\kilogram}}
355 \CustomizeMathJax{\newcommand{\wattpercubicmetre}{\watt\per\cubic\metre}}
356 \CustomizeMathJax{\newcommand{\wattpercubicmetrenp}{\watt\usk\rpcubic\metre}}
```

```

357 \CustomizeMathJax{\newcommand{\wattpersquaremetresteradian}{\watt\per\squaremetre\usk\steradian}}
358 \CustomizeMathJax{\newcommand{\wattpersquaremetresteradianp}{\watt\usk\rpsquare\metre\usk\rp\steradia
359 \CustomizeMathJax{\newcommand{\jouleperkilogramkelvin}{\joule\per\kilogram\usk\kelvin}}
360 \CustomizeMathJax{\newcommand{\jouleperkilogramkelvinp}{\joule\usk\reciprocal\kilogram\usk\reciprocal
361 \CustomizeMathJax{\newcommand{\squaremetreperkilogram}{\squaremetre\per\kilogram}}
362 \CustomizeMathJax{\newcommand{\rpsquaremetreperkilogram}{\squaremetre\usk\reciprocal\kilogram}}
363 \CustomizeMathJax{\newcommand{\cubicmetreperkilogram}{\cubic\metre\per\kilogram}}
364 \CustomizeMathJax{\newcommand{\rpcubicmetreperkilogram}{\cubic\metre\usk\reciprocal\kilogram}}
365 \CustomizeMathJax{\newcommand{\newtonpermetre}{\newton\per\metre}}
366 \CustomizeMathJax{\newcommand{\newtonpermetrep}{\newton\usk\reciprocal\metre}}
367 \CustomizeMathJax{\newcommand{\Celsius}{\unicode{x2103}}}
368 \CustomizeMathJax{\newcommand{\wattpermetrekelvin}{\watt\per\metre\usk\kelvin}}
369 \CustomizeMathJax{\newcommand{\wattpermetrekelvinp}{\watt\usk\reciprocal\metre\usk\reciprocal\kelvin}}
370 \CustomizeMathJax{\newcommand{\newtonmetre}{\newton\usk\metre} \CustomizeMathJax{\newcommand{\newtonmetrep}{\newton\usk\reciprocal\metre}}
371 \CustomizeMathJax{\newcommand{\squaremetrepercubicsecond}{\squaremetre\per\cubic\second}}
372 \CustomizeMathJax{\newcommand{\squaremetrepercubicsecondp}{\squaremetre\usk\rpcubic\second}}
373 \CustomizeMathJax{\newcommand{\metrepersecond}{\metre\per\second}}
374 \CustomizeMathJax{\newcommand{\metrepersecondp}{\metre\usk\reciprocal\second}}
375 \CustomizeMathJax{\newcommand{\joulepercubicmetre}{\joule\per\cubicmetre}}
376 \CustomizeMathJax{\newcommand{\joulepercubicmetrep}{\joule\usk\rpcubic\metre}}
377 \CustomizeMathJax{\newcommand{\kilogrampercubicmetrecoulomb}{\kilogram\per\cubic\metre\usk\coulomb}}
378 \CustomizeMathJax{\newcommand{\kilogrampercubicmetrecoulombp}{\kilogram\usk\rpcubic\metre\usk\reciprocal\coulomb}}
379 \CustomizeMathJax{\newcommand{\cubicmetrepersecond}{\cubicmetre\per\second}}
380 \CustomizeMathJax{\newcommand{\rpcubicmetrepersecond}{\cubicmetre\usk\reciprocal\second}}
381 \CustomizeMathJax{\newcommand{\kilogrampersecondcubicmetre}{\kilogram\per\second\usk\cubicmetre}}
382 \CustomizeMathJax{\newcommand{\kilogrampersecondcubicmetrep}{\kilogram\usk\reciprocal\second\usk\rpcubicmetre}}
383 \end{warpMathJax}

```

---

File 424 **lwarp-siunitx.sty**

§ 530 Package **siunitx**

(Emulates or patches code by JOSEPH WRIGHT.)

Pkg siunitx siunitx is patched for use by lwarp.

**fractions** Due to *pdftotext* limitations, fraction output is replaced by symbol output for per-mode and quotient-mode.

 **math mode required** Some units will require that the expression be placed inside math mode.

 **tabular** Tabular S columns are rendered as simple c columns, and tabular s columns are not supported. These may be replaced by c columns with each cell contained in `\num` or `\si`.

For math mode with `svg` display, the original `siunitx` code is used while generating the `svg` image. For text mode, `lwarp` uses an emulation which provides a very effective HTML interpretation of `siunitx`. For math expressions while using `MATHJAX`, a limited emulation is used. Most functions work reasonably well, but many options cannot be emulated. `siunitx` macros with more than one optional value cannot absorb the second optional value, and complicated parsing such as for `\ang` is not supported. The result usually looks fine, and otherwise is enough to get the meaning across.

lwarp's MATHJAX emulation for siunitx is meant to be a stop-gap measure until an extension is included in MATHJAX. As of this writing, the third-party siunitx extension for MATHJAX is not currently hosted at any public CDN, thus siunitx is not usable with this extension unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJax script, but lwarp's emulation would have to be disabled as well.

Document modifications required for MATHJAX:

#### custom units

- Custom units may be added with `\CustomizeMathJax`. See the `lwarp-siunitx` code for examples.

#### ⚠ unit spacing

- Units work better using `~` between units instead of using periods.

#### ⚠ `\square`, `\cubic`

- To square or cube compound units, enclose the following compound units in braces:

```
\cubic{\centi\meter}
```

Single units do not require braces.

Also see [MATHJAX option](#), section 8.7.4.

#### for HTML output:

```
1 \RequirePackage{xcolor}% for \convertcolorspec
2
3 \LWR@ProvidesPackagePass{siunitx}[2018/05/17]
4
5 \AtBeginDocument{% in case textcomp was not loaded
6 \DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
7 \DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
8 \DeclareSIUnit\elementarycharge{\textit{e}}
9 \DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
10 \DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
11 }% AtBeginDocument
```

`\@ensuredmath` is not supported inside an `\hbox`, so it must temporarily be restored to its original. Similar for `\mbox`. SVG math is created explicitly when necessary, using `\LWR@subsingledollar`.

```
12
13 \ExplSyntaxOn
14 %
```

Modified to set set HTML `\textcolor` if not black:

```
15 \cs_undefine:N __siunitx_print_aux:
16 \cs_new_protected:Npn __siunitx_print_aux:
17 {
18 \text
19 {
20 __siunitx_ensure_ltr:n
21 }
```

```

22 \color@begingroup
23 __siunitx_print_color:
24 __siunitx_font_shape:
25 __siunitx_font_weight:
26 \use:c
27 {
28 @_ \l__siunitx_print_type_tl _
29 text \l__siunitx_font_family_tl :
30 }
31 \bool_if:NTF \l__siunitx_font_math_mode_bool
32 { __siunitx_print_math: }
33 {
34 \LWR@findcurrenttextcolor% lwarp
35 \ifdefstring{\LWR@tempcolor}{000000}% lwarp
36 {__siunitx_print_text:}% lwarp
37 {% lwarp
38 \LWR@textcurrentcolor{% lwarp
39 __siunitx_print_text:
40 }% lwarp
41 }% lwarp
42 }
43 \color@endgroup
44 }
45 }
46 }
47
48
49 \cs_undefine:N __siunitx_set_math_fam:n
50 \cs_new_protected:Npn __siunitx_set_math_fam:n #1 {
51 \int_new:c { c__siunitx_math #1 _int }
52 \group_begin:% lwarp
53 \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
54 \LetLtxMacro\mbox\LWR@print@mbox% lwarp
55 \hbox_set:Nn \l__siunitx_tmp_box
56 {
57 \ensuremath
58 {
59 \use:c { math #1 }
60 {
61 \int_gset:cn { c__siunitx_math #1 _int } { \fam }
62 }
63 }
64 }
65 \group_end:% lwarp
66 }
67
68 \cs_undefine:N __siunitx_combined_output:n
69 \cs_new_protected:Npn __siunitx_combined_output:n #1 {
70 \group_begin:% lwarp
71 \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
72 \LetLtxMacro\mbox\LWR@print@mbox% lwarp
73 \bool_if:NTF \l__siunitx_number_parse_bool
74 {
75 \tl_clear:N \l__siunitx_number_out_tl
76 \bool_set_false:N \l__siunitx_number_compound_bool

```

```

77 __siunitx_number_output_parse:n {#1}
78 }
79 {

```

For parse-numbers=false:

```

80 __siunitx_unit_output_pre_print:
81 \begingroup% lwarp
82 \boolfalse{mathjax}% lwarp
83 % __siunitx_print:nn { number } { \ensuremath {#1} }
84 \LWR@subsingledollar{% lwarp
85 \textbackslash(\LWR@HTMLsanitize{#1} \textbackslash)% lwarp
86 }{siunitx}{%
87 __siunitx_print:nn { number } {%
88 \LWR@origensuredmath{#1}%
89 }%
90 }% lwarp
91 \endgroup% lwarp
92 __siunitx_unit_output_print:
93 }
94 \group_end:% lwarp
95 }

```

For parse-numbers=false:

```

96 \cs_set_protected:Npn __siunitx_range_numbers_aux:n #1
97 {
98 \bool_if:NTF \l__siunitx_number_parse_bool
99 {
100 \tl_clear:N \l__siunitx_number_out_tl
101 \tl_clear:N \l__siunitx_number_out_saved_tl
102 \bool_set_false:N \l__siunitx_number_compound_bool
103 __siunitx_number_output_parse:n {#1}
104 \bool_if:NT \l__siunitx_number_compound_bool
105 { \msg_error:nx { siunitx } { multi-part-range } {#1} }
106 }
107 {
108 __siunitx_unit_output_pre_print:
109 \begingroup% lwarp
110 \boolfalse{mathjax}% lwarp
111 % __siunitx_print:nn { number } {#1}
112 \LWR@subsingledollar{% lwarp
113 \textbackslash(\LWR@HTMLsanitize{#1} \textbackslash)% lwarp
114 }{siunitx}{%
115 __siunitx_print:nn { number } {
116 \LWR@origensuredmath{#1}%
117 } % lwarp
118 }% lwarp
119 \endgroup% lwarp
120 __siunitx_unit_output_print:
121 }
122 }

```

For parse-numbers=false:

```

123 \cs_set_protected:Npn __siunitx_angle_print_direct_aux:nn #1#2 {
124 \tl_if_empty:nF {#1}
125 {
126 \tl_set:Nn \l__siunitx_unit_tl {#2}
127 \begingroup% lwarp
128 \boolfalse{mathjax}% lwarp
129 __siunitx_print:nn { number } {#1}
130 \LWR@subsingledollar{% lwarp
131 \textbackslash(\LWR@HTMLSanitize{#1} \textbackslash)% lwarp
132){siunitx}{%
133 __siunitx_print:nn { number } {
134 \LWR@origensuredmath{#1}%
135 } % lwarp
136 }% lwarp
137 \endgroup% lwarp
138 __siunitx_unit_output_print:
139 }
140 }
141 %

```

For quotients, the fraction code is replaced by the symbol code:

```

142 \cs_undefine:N __siunitx_number_output_quotient_fraction:
143 \cs_new_protected:Npn __siunitx_number_output_quotient_fraction: {
144 \bool_set_true:N \l__siunitx_number_compound_bool
145 __siunitx_number_output_quotient_aux_i:
146 \tl_set_eq:NN \l__siunitx_number_out_tl
147 \l__siunitx_number_numerator_tl
148 \tl_put_right:NV \l__siunitx_number_out_tl \l__siunitx_output_quotient_tl
149 \tl_put_right:NV \l__siunitx_number_out_tl
150 \l__siunitx_number_denominator_tl
151 __siunitx_number_output_single_aux:
152 }

```

For units, the fraction code is replaced by the symbol code:

```

153 \cs_undefine:N __siunitx_unit_format_fraction_fraction:
154 \cs_new_protected:Npn __siunitx_unit_format_fraction_fraction: {
155 __siunitx_unit_format_fraction_symbol_aux:
156 \int_compare:nNnT { \l__siunitx_unit_denominator_int } > { 1 }
157 {
158 \bool_if:NT \l__siunitx_unit_denominator_bracket_bool
159 {
160 \tl_put_left:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_open_tl
161 \tl_put_right:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_close_tl
162 }
163 }
164 \tl_set_eq:NN \l__siunitx_unit_tl \l__siunitx_unit_numerator_tl
165 \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_per_symbol_tl
166 \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_unit_denominator_tl
167 }

```

```

168 \cs_undefine:N __siunitx_angle_print_astronomy_aux:
169 \cs_new_protected:Npn __siunitx_angle_print_astronomy_aux: {
170 \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-integer }

```

```

171 \l__siunitx_tmpa_tl
172 { \l__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
173 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
174 {% lateximage
175 \hbox_set:Nn \l__siunitx_angle_marker_box
176 {
177 \l__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
178 }
179 \hbox_set:Nn \l__siunitx_angle_unit_box
180 {
181 \l__siunitx_print:nV { unit } \l__siunitx_unit_tl
182 \skip_horizontal:n { -\scriptspace }
183 }
184 \l__siunitx_angle_print_astronomy_aux:n { marker }
185 \l__siunitx_angle_print_astronomy_aux:n { unit }
186 \hbox_set:Nn \l__siunitx_angle_marker_box
187 {
188 \box_use:N \l__siunitx_angle_marker_box
189 \box_use:N \l__siunitx_angle_unit_box
190 }
191 \dim_compare:nNnTF
192 { \l__siunitx_angle_marker_dim } > { \l__siunitx_angle_unit_dim }
193 { \l__siunitx_angle_print_astronomy_marker: }
194 { \l__siunitx_angle_print_astronomy_unit: }
195 }% lateximage
196 {% not a lateximage
197 \l__siunitx_print:nV { unit } \l__siunitx_unit_tl
198 \l__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
199 }% not a lateximage
200 \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-decimal }
201 \l__siunitx_tmpa_tl
202 { \l__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
203 }

204 \cs_undefine:N \l__siunitx_textsuperscript:n
205 \cs_new_protected:Npn \l__siunitx_textsuperscript:n #1 {#1}

206 \RenewDocumentCommand \num { o m } {
207 \leavevmode
208 \group_begin:% lwarp
209 \LetLtxMacro\ensuredmath\LWR@origensuredmath% lwarp
210 \LetLtxMacro\mbox\LWR@print@mbox% lwarp
211 \bool_set_false:N \l__siunitx_font_set_bool
212 \IfNoValueF {#1}
213 { \keys_set:nn { siunitx } {#1} }
214 \l__siunitx_number_output:n {#2}
215 \group_end:% lwarp
216 }
217
218 \RenewDocumentCommand \numrange { o m m } {
219 \leavevmode
220 \group_begin:% lwarp
221 \LetLtxMacro\ensuredmath\LWR@origensuredmath% lwarp
222 \LetLtxMacro\mbox\LWR@print@mbox% lwarp
223 \bool_set_false:N \l__siunitx_font_set_bool

```

```

224 \IfNoValueF {#1}
225 { \keys_set:nn { siunitx } {#1} }
226 __siunitx_range_numbers:nn {#2} {#3}
227 \group_end:% lwarp
228 }
229
230 \RenewDocumentCommand \ang { o > { \SplitArgument { 2 } { ; } } m } {
231 \group_begin:% lwarp
232 \LetLtxMacro\ensuredmath\LWR@origensuredmath% lwarp
233 \LetLtxMacro\mbox\LWR@print@mbox% lwarp
234 \IfNoValueF {#1}
235 { \keys_set:nn { siunitx } {#1} }
236 __siunitx_angle_output:nnn #2
237 \group_end:% lwarp
238 }
239
240 \RenewDocumentCommand \si { o m } {
241 \leavevmode
242 \group_begin:% lwarp
243 \LetLtxMacro\ensuredmath\LWR@origensuredmath% lwarp
244 \LetLtxMacro\mbox\LWR@print@mbox% lwarp
245 \bool_set_false:N \l__siunitx_font_set_bool
246 \IfNoValueTF {#1}
247 { __siunitx_unit_output:nn {#2} { } }
248 {
249 \keys_set:nn { siunitx } {#1}
250 __siunitx_unit_output:nn {#2} {#1}
251 }
252 \group_end:% lwarp
253 }
254
255
256 \RenewDocumentCommand{\SIRange}{o m m m}
257 {%
258 \leavevmode
259 \group_begin:% lwarp
260 \LetLtxMacro\ensuredmath\LWR@origensuredmath% lwarp
261 \LetLtxMacro\mbox\LWR@print@mbox% lwarp
262 \bool_set_false:N \l__siunitx_font_set_bool
263 \IfNoValueTF {#1}
264 { __siunitx_range_unit:nnnn {#4} { } {#2} {#3} }
265 {
266 \keys_set:nn { siunitx } {#1}
267 __siunitx_range_unit:nnnn {#4} {#1} {#2} {#3}
268 }
269 \group_end:% lwarp
270 }
271
272 \ExplSyntaxOff

```

For MATHJAX. (The following runs much faster as separate `\CusomizeMathJax` calls instead of one single call.)

```

273 \begin{warpMathJax}
274 \LWR@infoprocessingmathjax{siunitx}

```

```
275 \CustomizeMathJax{\newcommand{\tothe}[1]{^{\#1}}}
276 \CustomizeMathJax{\newcommand{\raiseto}[2][{\#2}]{^{\#1}}}
277
278 \CustomizeMathJax{\newcommand{\ang}[2][{}]{\mathrm{\#2}\degree}}
279 \CustomizeMathJax{\newcommand{\num}[2][{}]{\mathrm{\#2}}}
280 \CustomizeMathJax{\newcommand{\si}[2][{}]{\mathrm{\#2}}}
281 %
282 % \SI[opt]{num}[preunit]{unit}
283 \CustomizeMathJax{\newcommand{\LWRSI}[2][{}]{\mathrm{\#1\LWRSInumber\,#2}}}
284 \CustomizeMathJax{\newcommand{\SI}[2][{}]{\def\LWRSInumber{\#2}\LWRSI}}

285 \CustomizeMathJax{\newcommand{\numlist}[2][{}]{\mathrm{\#2}}}
286 \CustomizeMathJax{\newcommand{\numrange}[3][{}]{\mathrm{\#2\, \unicode{x2013}\,#3}}}
287 \CustomizeMathJax{\newcommand{\SIlist}[3][{}]{\mathrm{\#2\,#3}}}
288 \CustomizeMathJax{\newcommand{\SIrange}[4][{}]{\mathrm{\#2\,#4\, \unicode{x2013}\,#3\,#4}}}
289 \CustomizeMathJax{\newcommand{\tablenum}[2][{}]{\mathrm{\#2}}}
290 %
291 \CustomizeMathJax{\newcommand{\ampere}{\mathrm{A}}}
292 \CustomizeMathJax{\newcommand{\candela}{\mathrm{cd}}}
293 \CustomizeMathJax{\newcommand{\kelvin}{\mathrm{K}}}
294 \CustomizeMathJax{\newcommand{\kilogram}{\mathrm{kg}}}
295 \CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
296 \CustomizeMathJax{\newcommand{\mole}{\mathrm{mol}}}
297 \CustomizeMathJax{\newcommand{\second}{\mathrm{s}}}
298 %
299 \CustomizeMathJax{\newcommand{\becquerel}{\mathrm{Bq}}}
300 \CustomizeMathJax{\newcommand{\degreeCelsius}{\unicode{x2103}}}
301 \CustomizeMathJax{\newcommand{\coulomb}{\mathrm{C}}}
302 \CustomizeMathJax{\newcommand{\farad}{\mathrm{F}}}
303 \CustomizeMathJax{\newcommand{\gray}{\mathrm{Gy}}}
304 \CustomizeMathJax{\newcommand{\hertz}{\mathrm{Hz}}}
305 \CustomizeMathJax{\newcommand{\henry}{\mathrm{H}}}
306 \CustomizeMathJax{\newcommand{\joule}{\mathrm{J}}}
307 \CustomizeMathJax{\newcommand{\katal}{\mathrm{kat}}}
308 \CustomizeMathJax{\newcommand{\lumen}{\mathrm{lm}}}
309 \CustomizeMathJax{\newcommand{\lux}{\mathrm{lx}}}
310 \CustomizeMathJax{\newcommand{\newton}{\mathrm{N}}}
311 \CustomizeMathJax{\newcommand{\ohm}{\mathrm{\Omega}}}
312 \CustomizeMathJax{\newcommand{\pascal}{\mathrm{Pa}}}
313 \CustomizeMathJax{\newcommand{\radian}{\mathrm{rad}}}
314 \CustomizeMathJax{\newcommand{\siemens}{\mathrm{S}}}
315 \CustomizeMathJax{\newcommand{\sievert}{\mathrm{Sv}}}
316 \CustomizeMathJax{\newcommand{\steradian}{\mathrm{sr}}}
317 \CustomizeMathJax{\newcommand{\tesla}{\mathrm{T}}}
318 \CustomizeMathJax{\newcommand{\volt}{\mathrm{V}}}
319 \CustomizeMathJax{\newcommand{\watt}{\mathrm{W}}}
320 \CustomizeMathJax{\newcommand{\weber}{\mathrm{Wb}}}
321 \CustomizeMathJax{\newcommand{\day}{\mathrm{d}}}
322 \CustomizeMathJax{\newcommand{\degree}{\mathrm{^{\circ}}}}
323 \CustomizeMathJax{\newcommand{\hectare}{\mathrm{ha}}}
324 \CustomizeMathJax{\newcommand{\hour}{\mathrm{h}}}
325 \CustomizeMathJax{\newcommand{\litre}{\mathrm{l}}}
326 \CustomizeMathJax{\newcommand{\liter}{\mathrm{L}}}
327 \CustomizeMathJax{\newcommand{\arcminute}{\mathrm{^{\prime}}}}
328 \CustomizeMathJax{\newcommand{\minute}{\mathrm{min}}}
```

```

329 \CustomizeMathJax{\newcommand{\arcsecond}^{\prime\prime}}
330 \CustomizeMathJax{\newcommand{\tonne}{\mathrm{t}}}
331 \CustomizeMathJax{\newcommand{\astronomicalunit}{\mathrm{au}}}
332 \CustomizeMathJax{\newcommand{\atomicmassunit}{\mathrm{u}}}
333 \CustomizeMathJax{\newcommand{\bohr}{\mathit{a}_0}}
334 \CustomizeMathJax{\newcommand{\clight}{\mathit{c}_0}}
335 \CustomizeMathJax{\newcommand{\dalton}{\mathrm{D}_\mathrm{a}}}
336 \CustomizeMathJax{\newcommand{\electronmass}{\mathit{m}_\mathrm{e}}}
337 \CustomizeMathJax{\newcommand{\electronvolt}{\mathrm{eV}}}
338 \CustomizeMathJax{\newcommand{\elementarycharge}{\mathit{e}}}
339 \CustomizeMathJax{\newcommand{\hartree}{\mathit{E}_\mathrm{h}}}
340 \CustomizeMathJax{\newcommand{\planckbar}{\mathit{\unicode{x210F}}}}
341 \CustomizeMathJax{\newcommand{\angstrom}{\mathrm{\unicode{x212B}}}}
342 \CustomizeMathJax{\let\LWRorigbar\bar}
343 \CustomizeMathJax{\newcommand{\bar}{\mathrm{bar}}}
344 \CustomizeMathJax{\newcommand{\barn}{\mathrm{b}}}
345 \CustomizeMathJax{\newcommand{\bel}{\mathrm{B}}}
346 \CustomizeMathJax{\newcommand{\decibel}{\mathrm{dB}}}
347 \CustomizeMathJax{\newcommand{\knot}{\mathrm{kn}}}
348 \CustomizeMathJax{\newcommand{\mmHg}{\mathrm{mmHg}}}
349 \CustomizeMathJax{\newcommand{\nauticalmile}{\mathrm{M}}}
350 \CustomizeMathJax{\newcommand{\neper}{\mathrm{Np}}}
351 %
352 \CustomizeMathJax{\newcommand{\yocto}{\mathrm{y}}}
353 \CustomizeMathJax{\newcommand{\zepto}{\mathrm{z}}}
354 \CustomizeMathJax{\newcommand{\atto}{\mathrm{a}}}
355 \CustomizeMathJax{\newcommand{\femto}{\mathrm{f}}}
356 \CustomizeMathJax{\newcommand{\pico}{\mathrm{p}}}
357 \CustomizeMathJax{\newcommand{\nano}{\mathrm{n}}}
358 \CustomizeMathJax{\newcommand{\micro}{\mathrm{\unicode{x00B5}}}}
359 \CustomizeMathJax{\newcommand{\milli}{\mathrm{m}}}
360 \CustomizeMathJax{\newcommand{\centi}{\mathrm{c}}}
361 \CustomizeMathJax{\newcommand{\deci}{\mathrm{d}}}
362 \CustomizeMathJax{\newcommand{\deca}{\mathrm{da}}}
363 \CustomizeMathJax{\newcommand{\hecto}{\mathrm{h}}}
364 \CustomizeMathJax{\newcommand{\kilo}{\mathrm{k}}}
365 \CustomizeMathJax{\newcommand{\mega}{\mathrm{M}}}
366 \CustomizeMathJax{\newcommand{\giga}{\mathrm{G}}}
367 \CustomizeMathJax{\newcommand{\tera}{\mathrm{T}}}
368 \CustomizeMathJax{\newcommand{\peta}{\mathrm{P}}}
369 \CustomizeMathJax{\newcommand{\exa}{\mathrm{E}}}
370 \CustomizeMathJax{\newcommand{\zetta}{\mathrm{Z}}}
371 \CustomizeMathJax{\newcommand{\yotta}{\mathrm{Y}}}
372 %
373 \CustomizeMathJax{\newcommand{\percent}{\mathrm{\%}}}
374 %
375 \CustomizeMathJax{\newcommand{\meter}{\mathrm{m}}}
376 \CustomizeMathJax{\newcommand{\metre}{\mathrm{m}}}
377 %
378 \CustomizeMathJax{\newcommand{\gram}{\mathrm{g}}}
379 \CustomizeMathJax{\newcommand{\kg}{\kilo\gram}}
380 \CustomizeMathJax{\newcommand{\of}[1]_{\mathrm{\#1}}}
381 \CustomizeMathJax{\newcommand{\squared}{^2}}
382 \CustomizeMathJax{\newcommand{\square}[1]{\mathrm{\#1}^2}}
383 \CustomizeMathJax{\newcommand{\cubed}{^3}}

```

```
384 \CustomizeMathJax{\newcommand{\cubic}[1]{\mathrm{#1}^3}}
385 \CustomizeMathJax{\newcommand{\per}{/}}
386 \CustomizeMathJax{\newcommand{\celsius}{\unicode{x2103}}}
387 %
388 \CustomizeMathJax{\newcommand{\fg}{\femto\gram}}
389 \CustomizeMathJax{\newcommand{\pg}{\pico\gram}}
390 \CustomizeMathJax{\newcommand{\ng}{\nano\gram}}
391 \CustomizeMathJax{\newcommand{\ug}{\micro\gram}}
392 \CustomizeMathJax{\newcommand{\mg}{\milli\gram}}
393 \CustomizeMathJax{\newcommand{\g}{\gram}}
394 \CustomizeMathJax{\newcommand{\kg}{\kilo\gram}}
395 %
396 \CustomizeMathJax{\newcommand{\amu}{\mathrm{u}}}
397 %
398 \CustomizeMathJax{\newcommand{\pm}{\pico\metre}}
399 \CustomizeMathJax{\newcommand{\nm}{\nano\metre}}
400 \CustomizeMathJax{\newcommand{\um}{\micro\metre}}
401 \CustomizeMathJax{\newcommand{\mm}{\milli\metre}}
402 \CustomizeMathJax{\newcommand{\cm}{\centi\metre}}
403 \CustomizeMathJax{\newcommand{\dm}{\deci\metre}}
404 \CustomizeMathJax{\newcommand{\m}{\metre}}
405 \CustomizeMathJax{\newcommand{\km}{\kilo\metre}}
406 %
407 \CustomizeMathJax{\newcommand{\as}{\atto\second}}
408 \CustomizeMathJax{\newcommand{\fs}{\femto\second}}
409 \CustomizeMathJax{\newcommand{\ps}{\pico\second}}
410 \CustomizeMathJax{\newcommand{\ns}{\nano\second}}
411 \CustomizeMathJax{\newcommand{\us}{\micro\second}}
412 \CustomizeMathJax{\newcommand{\ms}{\milli\second}}
413 \CustomizeMathJax{\newcommand{\s}{\second}}
414 %
415 \CustomizeMathJax{\newcommand{\fmol}{\femto\mol}}
416 \CustomizeMathJax{\newcommand{\pmol}{\pico\mol}}
417 \CustomizeMathJax{\newcommand{\nmol}{\nano\mol}}
418 \CustomizeMathJax{\newcommand{\umol}{\micro\mol}}
419 \CustomizeMathJax{\newcommand{\mmol}{\milli\mol}}
420 \CustomizeMathJax{\newcommand{\mol}{\mol}}
421 \CustomizeMathJax{\newcommand{\kmol}{\kilo\mol}}
422 %
423 \CustomizeMathJax{\newcommand{\pA}{\pico\ampere}}
424 \CustomizeMathJax{\newcommand{\nA}{\nano\ampere}}
425 \CustomizeMathJax{\newcommand{\uA}{\micro\ampere}}
426 \CustomizeMathJax{\newcommand{\mA}{\milli\ampere}}
427 \CustomizeMathJax{\newcommand{\A}{\ampere}}
428 \CustomizeMathJax{\newcommand{\kA}{\kilo\ampere}}
429 %
430 \CustomizeMathJax{\newcommand{\ul}{\micro\litre}}
431 \CustomizeMathJax{\newcommand{\ml}{\milli\litre}}
432 \CustomizeMathJax{\newcommand{\l}{\litre}}
433 \CustomizeMathJax{\newcommand{\hl}{\hecto\litre}}
434 \CustomizeMathJax{\newcommand{\uL}{\micro\liter}}
435 \CustomizeMathJax{\newcommand{\mL}{\milli\liter}}
436 \CustomizeMathJax{\newcommand{\L}{\liter}}
437 \CustomizeMathJax{\newcommand{\hL}{\hecto\liter}}
438 %
```

```
439 \CustomizeMathJax{\newcommand{\mHz}{\milli\hertz}}
440 \CustomizeMathJax{\newcommand{\Hz}{\hertz}}
441 \CustomizeMathJax{\newcommand{\kHz}{\kilo\hertz}}
442 \CustomizeMathJax{\newcommand{\MHz}{\mega\hertz}}
443 \CustomizeMathJax{\newcommand{\GHz}{\giga\hertz}}
444 \CustomizeMathJax{\newcommand{\THz}{\tera\hertz}}
445 %
446 \CustomizeMathJax{\newcommand{\mN}{\milli\newton}}
447 \CustomizeMathJax{\newcommand{\N}{\newton}}
448 \CustomizeMathJax{\newcommand{\kN}{\kilo\newton}}
449 \CustomizeMathJax{\newcommand{\MN}{\mega\newton}}
450 %
451 \CustomizeMathJax{\newcommand{\Pa}{\pascal}}
452 \CustomizeMathJax{\newcommand{\kPa}{\kilo\pascal}}
453 \CustomizeMathJax{\newcommand{\MPa}{\mega\pascal}}
454 \CustomizeMathJax{\newcommand{\GPa}{\giga\pascal}}
455 %
456 \CustomizeMathJax{\newcommand{\mohm}{\milli\ohm}}
457 \CustomizeMathJax{\newcommand{\kohm}{\kilo\ohm}}
458 \CustomizeMathJax{\newcommand{\Mohm}{\mega\ohm}}
459 %
460 \CustomizeMathJax{\newcommand{\pV}{\pico\volt}}
461 \CustomizeMathJax{\newcommand{\nV}{\nano\volt}}
462 \CustomizeMathJax{\newcommand{\uV}{\micro\volt}}
463 \CustomizeMathJax{\newcommand{\mV}{\milli\volt}}
464 \CustomizeMathJax{\newcommand{\V}{\volt}}
465 \CustomizeMathJax{\newcommand{\kV}{\kilo\volt}}
466 %
467 \CustomizeMathJax{\newcommand{\W}{\watt}}
468 \CustomizeMathJax{\newcommand{\uW}{\micro\watt}}
469 \CustomizeMathJax{\newcommand{\mW}{\milli\watt}}
470 \CustomizeMathJax{\newcommand{\kW}{\kilo\watt}}
471 \CustomizeMathJax{\newcommand{\MW}{\mega\watt}}
472 \CustomizeMathJax{\newcommand{\GW}{\giga\watt}}
473 %
474 \CustomizeMathJax{\newcommand{\J}{\joule}}
475 \CustomizeMathJax{\newcommand{\uJ}{\micro\joule}}
476 \CustomizeMathJax{\newcommand{\mJ}{\milli\joule}}
477 \CustomizeMathJax{\newcommand{\kJ}{\kilo\joule}}
478 %
479 \CustomizeMathJax{\newcommand{\eV}{\electronvolt}}
480 \CustomizeMathJax{\newcommand{\meV}{\milli\electronvolt}}
481 \CustomizeMathJax{\newcommand{\keV}{\kilo\electronvolt}}
482 \CustomizeMathJax{\newcommand{\MeV}{\mega\electronvolt}}
483 \CustomizeMathJax{\newcommand{\GeV}{\giga\electronvolt}}
484 \CustomizeMathJax{\newcommand{\TeV}{\tera\electronvolt}}
485 %
486 \CustomizeMathJax{\newcommand{\kWh}{\kilo\watt\hour}}
487 %
488 \CustomizeMathJax{\newcommand{\F}{\farad}}
489 \CustomizeMathJax{\newcommand{\fF}{\femto\farad}}
490 \CustomizeMathJax{\newcommand{\pF}{\pico\farad}}
491 %
492 \CustomizeMathJax{\newcommand{\K}{\mathrm{K}}}
493 %
```

```

494 \CustomizeMathJax{\newcommand{\dB}{\mathrm{dB}}}
495 %
496 \CustomizeMathJax{\newcommand{\kibi}{\mathrm{Ki}}}
497 \CustomizeMathJax{\newcommand{\mebi}{\mathrm{Mi}}}
498 \CustomizeMathJax{\newcommand{\gibi}{\mathrm{Gi}}}
499 \CustomizeMathJax{\newcommand{\tebi}{\mathrm{Ti}}}
500 \CustomizeMathJax{\newcommand{\pebi}{\mathrm{Pi}}}
501 \CustomizeMathJax{\newcommand{\exbi}{\mathrm{Ei}}}
502 \CustomizeMathJax{\newcommand{\zebi}{\mathrm{Zi}}}
503 \CustomizeMathJax{\newcommand{\yobi}{\mathrm{Yi}}}
504 \end{warpMathJax}

```

---

File 425 **lwarp-slantsc.sty**

§ 531 Package **slantsc**

(Emulates or patches code by HARALD HARDERS.)

Pkg slantsc slantsc is emulated for HTML, and used as-is for print output.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{slantsc}[2012/01/01]

2 \newcommand*{\LWR@HTML@noscsshape}{}
3 \LWR@formatted{noscsshape}
4
5 \FilenameNullify%
6 \LetLtxMacro\noscsshape\@empty%
7 }

```

---

File 426 **lwarp-slashed.sty**

§ 532 Package **slashed**

(Emulates or patches code by DAVID CARLISLE.)

Pkg slashed slashed works as-s for HTML SVG math. For MATHJAX, emulation is provided.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{slashed}[1997/01/16]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\slashed}[1]{\cancel{#1}}}
4 \end{warpMathJax}

```

---

File 427 **lwarp-soul.sty**

§ 533 Package **soul**

(Emulates or patches code by MELCHIOR FRANZ.)

Pkg soul soul is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{soul}[2003/11/17]  
2 \RequirePackage{xcolor}% for \convertcolorspec

Storage for the colors to use:

```
3 \newcommand*\LWR@soululcolor{}
4
5 \newcommand*\LWR@soulstcolor{}
6
7 % \definecolor{LWR@soulhlcolordefault}{HTML}{F8E800}
8 % \newcommand*\LWR@soulhlcolor{LWR@soulhlcolordefault}
9 \newcommand*\LWR@soulhlcolor{}
```

\so {<text>}

Basic markup with css:

```
10 \newcommand{\so}[1]{%
11 \InlineClass(letter-spacing:.2ex){letterspacing}{#1}%
12 }
```

\caps {<text>}

```
13 \newcommand{\caps}[1]{%
14 \InlineClass%
15 (font-variant:small-caps;letter-spacing:.1ex)%
16 {capsspacing}{#1}%
17 }
```

\LWR@soulcolor {<text>}{<color>}{<class>}{<colorstyle>}{<FormatWPstyle>}

Add colors if not empty:

```
18 \newcommand{\LWR@soulcolor}[5]{%
19 \ifcseempty{#2}%
20 {%
21 \InlineClass(#5){#3}{#1}%
22 }%
23 {%
24 \convertcolorspec{named}{\@nameuse{#2}}{HTML}\LWR@tempcolor%
25 \LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}%
26 }%
27 }
```

```
28 \newcommand{\ul}[1]{%
29 \LWR@soulcolor{#1}{LWR@soululcolor}{uline}{text-decoration-color}%
30 {text-decoration:underline; text-decoration-skip: auto;}%
31 }
32
33 \newcommand{\st}[1]{
34 \LWR@soulcolor{#1}{LWR@soulstcolor}{sout}{text-decoration-color}%
35 {text-decoration:line-through}%
36 }
```

```

37
38 \newcommand{\hl}[1]{
39 \LWR@soulcolor{#1}{\LWR@soulhlcolor}{highlight}{background-color}%
40 {background:\LWR@origpound{ }F8E800}
41 }

```

#### Nullified:

```

42 \newcommand*\soulaccent}[1]{}
43 \newcommand*\soulregister}[2]{}
44 \newcommand*\sloppyword}[1]{#1}
45 \newcommand*\sodef}[5]{\DeclareRobustCommand*#1[1]{\so{#1}}}
46 \newcommand*\resetso{}
47 \newcommand*\capsdef}[5]{}
48 \newcommand*\capsreset{}
49 \newcommand*\capssave}[1]{}
50 \newcommand*\capsselect}[1]{}
51 \newcommand*\setul}[2]{}
52 \newcommand*\resetul{}
53 \newcommand*\setuldepth}[1]{}
54 \newcommand*\setuloverlap}[1]{}
55 \newcommand*\<{}{}

```

#### Set colors:

```

56 \newcommand*\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}
57 \newcommand*\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}
58 \newcommand*\sethlcolor}[1]{\renewcommand{\LWR@soulhlcolor}{#1}}

```

#### Long versions of the user-level macros:

```

59 \let\textso\so
60 \let\textul\ul
61 \let\texthl\hl
62 \let\textcaps\caps

```

File 428 **lwarp-soulpos.sty**

§ 534 Package **soulpos**

*(Emulates or patches code by JAVIER BEZOS.)*

Pkg soulpos soulpos is emulated.

**for HTML output:**

```

1 \RequirePackage{soul}
2 \RequirePackage{soulutf8}
3 \LWR@ProvidesPackageDrop{soulpos}[2012/02/25]

4 \NewDocumentCommand{\ulposdef}{m o m}{}
5
6 \newdimen\ulwidth
7

```

```

8 \newcommand\ifulstarttype[1]{%
9 \expandafter\@secondoftwo%
10 }
11
12 \newcommand\ifulendtype[1]{%
13 \expandafter\@secondoftwo%
14 }
15
16 \newcommand{\ulstarttype}{0}
17 \newcommand{\ulendtype}{0}
18 \newcommand\ulpostolerance{0}%

```

---

File 429 **lwarp-soulutf8.sty**

§ 535 Package **soulutf8**

Pkg soulutf8 soulutf8 is emulated.

lwarp's HTML output naturally supports UTF-8 encoding.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{soulutf8}[2016/05/16]
2 \RequirePackage{soul}

```

---

File 430 **lwarp-splitbib.sty**

§ 536 Package **splitbib**

*(Emulates or patches code by NICOLAS MARKEY.)*

Pkg splitbib splitbib is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{splitbib}[2005/12/22]
2 \def\NMSB@stylebox#1#2{%
3 \begin{BlockClass}[text-align:center ; border: 1px solid black]{splitbibbox}
4 \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{#1#2}}
5 \end{BlockClass}
6 }
7
8 \def\NMSB@stylebar#1#2{%
9 \begin{BlockClass}[%
10 text-align:center ;
11 border-top: 1px solid black ;
12 border-bottom: 1px solid black ;
13]{splitbibbar}
14 \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{#1#2}}
15 \end{BlockClass}
16 }
17
18 \def\NMSB@styledash#1#2{%

```

```

19 \begin{BlockClass}[%
20 text-align:center ;
21]{splitbibdash}
22 \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{---~#1#2~---}}
23 \end{BlockClass}
24 }
25
26 \def\NMSB@stylenone#1#2{%
27 \par
28 }
29
30 \def\NMSB@stylesimple#1#2{%
31 \par
32 \csname SB\NMSB@level font\endcsname{\LWR@textcurrentfont{#1#2}}
33 \par
34 }

```

---

File 431 **lwarp-splitidx.sty**

§ 537 Package **splitidx**

(Emulates or patches code by MARKUS KOHM.)

Pkg splitidx **splitidx** is patched for use by **lwarp**.

If the `latexmk` option is selected for **lwarp**, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

 **\thepage** When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to `\thepage` during HTML output, as the concept of a page number is meaningless. Instead, do

```

\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}

```

where the `\index`-like action occurs, and then refer to `\arabic{LWR@autoindex}` instead of `\thepage` where the reference should occur.

See section 653.17 in the `lwarp-patch-memoir` package for the `\@@wrspindexhyp` macro as an example.

**for HTML output:** 1 \LWR@ProvidesPackagePass{splitidx}[2016/02/18]

```

2 \catcode'_ =12%
3 \xpatchcmd{\newindex}
4 {\jobname-#2.idx}
5 {\jobname-#2_html.idx}
6 {}
7 {\LWR@patcherror{splitidx}{@newindex}}
8 \catcode'_ =8%

```

Patched to use lwarp's automatic indexing counter instead of \thepage:

```

9 \renewcommand*{\@wrsindex}[2][\]{%
10 \ifx\relax#1\relax
11 \if@splitidx
12 \@wrsindex[idx]{#2}%
13 \else
14 \def\@tempa{#2}%
15 \if@verbinde\@onelevel@sanitize\@tempa\fi
16 \@wrindex{\@tempa}%
17 \fi
18 \else
19 \def\@tempa{#2}%
20 \csname index@#1@hook\endcsname
21 % \expandafter\ifx\csname @wrsindex\endcsname\relax
22 \addtocounter{LWR@autoindex}{1}% lwarp
23 \label{LWRindex-\arabic{LWR@autoindex}}% lwarp
24 % \@@@wrsindex{#1}{\@tempa}{\thepage}}%
25 \@@@wrsindex{#1}{\@tempa}{\arabic{LWR@autoindex}}%
26 % \else
27 % \def\@tempb{\@wrsindex{#1}}%
28 % \expandafter\@tempb\@tempa||\%
29 % \fi
30 \endgroup
31 \@esphack
32 \fi
33 }

```

lwarp defines sectioning commands with xparse, so the below patches are done as temporary redefinitions instead of being \let.

```

34 \xpatchcmd{\printsubindex}
35 {\let\section\subsection}
36 {\renewcommand*{\section}{\subsection}}
37 {}
38 {\LWR@patcherror{splitidx}{printsubindex-section}}
39
40 \xpatchcmd{\printsubindex}
41 {\let\chapter\section}
42 {\renewcommand*{\chapter}{\section}}
43 {}
44 {\LWR@patcherror{splitidx}{printsubindex-chapter}}
45
46 \xpatchcmd{\printsubindex}
47 {\let\@makechapterhead\section}
48 {\def\@makechapterhead{\section}}
49 {}
50 {\LWR@patcherror{splitidx}{printsubindex-chapter}}

```

File 432 **lwarp-srcltx.sty**

§ 538 Package **srcltx**

Pkg srcltx srcltx is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{srcltx}[2006/11/12]

```

2 \newif\ifSRCOK \SRCOKfalse
3 \newcommand*{srcIncludeHook[1]}{}
4 \newcommand*{srcInputHook[1]}{}
5 \newcommand*{MainFile{}}
6 \def\MainFile{\jobname.tex}
7 \newcommand*{CurrentInput{}}
8 \gdef\CurrentInput{\MainFile}
9 \newcommand{Input{}}
10 \let\Input\input

```

File 433 **lwarp-srctex.sty**

§ 539 Package **srctex**

Pkg srctex srctex is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{srctex}[2006/11/12]  
2 \LWR@origRequirePackage{lwarp-srcltx}

File 434 **lwarp-stabular.sty**

§ 540 Package **stabular**

*(Emulates or patches code by SIGITAS TOLUŠIS.)*

Pkg stabular stabular is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{stabular}[2014/03/20]

Env stabular [*vpos*] {*colspec*}

```

2 \newenvironment{stabular}[2][c]
3 {
4 \begin{tabular}[#1]{#2}
5 \renewcommand{\noalign}[1]{}
6 }
7 {\end{tabular}}

```

Env `stabular`  $\{\langle width \rangle\} [\langle vpos \rangle] \{\langle colspec \rangle\}$

```

8 \NewDocumentEnvironment{stabular*}{m o m}
9 {
10 \begin{tabular}[#2]{#3}
11 \renewcommand{\noalign}[1]{}
12 }
13 \end{tabular}}

```

File 435 **lwarp-stackengine.sty**

§ 541 Package **stackengine**

*(Emulates or patches code by STEVEN B. SEGLETES.)*

Pkg `stackengine` `stackengine` is patched for use by `lwarp`.

**for HTML output:** 1 \LWR@ProvidesPackagePass{stackengine}[2017/02/13]

The original version is necessary for the patched `\@stack` and `\stackanchor`, where nesting `lateximages` does not work:

```

2 \LetLtxMacro\LWR@orig@stackengine\stackengine

3 \renewcommand*{\stackengine}[8]{%
4 \ifstrequal{#4}{0}%
5 {\begin{lateximage}[\ImageAltText]}%
6 {\begin{lateximage}[\ImageAltText][][vertical-align:top]}%
7 \LWR@orig@stackengine{#1}{#2}{#3}{#4}{#5}{#6}{#7}{#8}%
8 \end{lateximage}%
9 }

```

`\@stack` uses a `lateximage` with a vertical alignment:

```

10 \LetLtxMacro\LWR@orig@@stack\@stack
11
12 \xpatchcmd{\LWR@orig@@stack}{\stackengine}{\LWR@orig@stackengine}
13 {}
14 {\LWR@patcherror{stackengine}{\LWR@orig@@stack}}
15
16 \renewcommand*{\@stack}[4]{%
17 \ifstrequal{#3}{0}%
18 {\begin{lateximage}[\ImageAltText]}%
19 {\begin{lateximage}[\ImageAltText][][vertical-align:top]}%
20 \LWR@orig@@stack{#1}{#2}{#3}{#4}%
21 \end{lateximage}%
22 }

```

The lapping macros are disabled for HTML:

```

23 \newcommand*\LWR@HTML@@stacklap[4]{#3}
24 \LWR@formatted{@stacklap}

```

`\stackanchor` is patched for two instances of `\stackengine`. A `lateximage` with vertical alignment is used.

```

25 \xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
26 {}
27 {\LWR@patcherror{stackengine}{stackanchor patch 1}}
28
29 \xpatchcmd{\stackanchor}{\stackengine}{\LWR@orig@stackengine}
30 {}
31 {\LWR@patcherror{stackengine}{stackanchor patch 2}}
32
33 \xpretocmd{\stackanchor}
34 {\begin{lateximage}[\ImageAltText][][vertical-align:middle]}
35 {}
36 {\LWR@patcherror{stackengine}{stackanchor pre}}
37
38 \xapptocmd{\stackanchor}{\end{lateximage}}
39 {}
40 {\LWR@patcherror{stackengine}{stackanchor app}}

```

`\Centerstack` is simply placed inside a `lateximage` with a vertical alignment:

```

41 \xpretocmd{\Centerstack}
42 {\begin{lateximage}[\ImageAltText][][vertical-align:middle]}
43 {}
44 {\LWR@patcherror{stackengine}{Centerstack pre}}
45
46 \xapptocmd{\Centerstack}{\end{lateximage}}
47 {}
48 {\LWR@patcherror{stackengine}{Centerstack app}}

```

`\savestack` reverts to print mode while saving the box, then places it inside a `lateximage` when used:

```

49 \renewcommand*\savestack[2]{%
50 \xdef\sv@name{\stack@macro@name{#1}}%
51 \ifundefined{sv@name content}{%
52 \expandafter\newsavebox\expandafter{\csname\sv@name content\endcsname}%
53 }{}%
54 \begingroup% lwarp
55 \LWR@restoreorigformatting% lwarp
56 \RenewDocumentEnvironment{lateximage}{s o s o o}{}{}% lwarp: inside group
57 \expandafter\LWR@gsavebox\csname\sv@name content\endcsname{#2}%
58 \expandafter\gdef\expandafter#1\expandafter{%
59 \expandafter\begin\expandafter{lateximage\expandafter}% lwarp
60 \expandafter\usebox\expandafter%
61 {\csname\sv@name content\endcsname}%
62 \expandafter\end\expandafter{lateximage\expandafter}% lwarp
63 }%
64 \endgroup% lwarp
65 }

```

File 436 **lwarp-stackrel.sty**

§ 542 Package **stackrel**

(Emulates or patches code by HEIKO OBERDIEK.)

Pkg stackrel stackrel is used as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{stackrel}[2016/05/16]
2 \begin{warpMathJax}
3 \CustomizeMathJax{\renewcommand{\stackrel}[3][[]]{%
4 \mathrel{\mathop{#3}\limits_{#1}^{#2}}}%
5 }}
6
7 \CustomizeMathJax{\newcommand{\stackbin}[3][[]]{%
8 \mathbin{\mathop{#3}\limits_{#1}^{#2}}}%
9 }}
10 \end{warpMathJax}

```

File 437 **lwarp-statex2.sty**

§ 543 Package **statex2**

(Emulates or patches code by RODNEY A SPARAPANI.)

Pkg statex2 statex2 is patched for use by lwarp, and emulated for MATHJAX.

 As of this version, option autobold does not appear to work for PDF output.

 For MATHJAX, the tilde character ~ does not create \sim. Use \sim directly.

 Because MATHJAX has limited conditional processing:

- \wrap only creates square braces, no matter what its optional arguments.
- \P, \pCau, \pN, and \pU do not handle special cases.

 **\and** To have \and work if using \maketitle, place the following after the start of the document:

```

\newcommand*{\and}{%
 \relax\ifmmode%
 \expandafter\;\mb{\mathrm{and}}\;%
 \else%
 \expandafter\STATEXand%
 \fi%
}

```

for HTML output:

```

1 \LWR@ProvidesPackagePass{statex2}[2011/09/14]

2 \newcommand*{\LWR@HTML@Alpha}[1][{}]{%
3 \fcolorbox{black}{ForestGreen}{\textcolor{white}{\textsf{ALPHA}}}%
4 \textbf{\textcolor{ForestGreen}{\textsf{#1}}}%
5 }
6 \LWR@formatted{Alpha}
7
8 \newcommand*{\LWR@HTML@List}[1][{}]{%
9 \textbf{\textcolor{Dandelion}{\textsf{L}\textsubscript{\textit{#1}}}}%
10 }
11 \LWR@formatted{List}
12
13 \newcommand*{\LWR@HTML@Snd}[1][{}]{%
14 \fcolorbox{black}{Dandelion}{\textcolor{white}{\textsf{2nd}}}%
15 \textbf{\textcolor{Dandelion}{\textsf{#1}}}%
16 }
17 \LWR@formatted{Snd}
18
19 \begin{warpMathJax}
20 \LWR@infoprocessingmathjax{statex2}
21
22 \CustomizeMathJax{\newcommand{\cpi}{\boldsymbol{\pi}}}
23 \CustomizeMathJax{\newcommand{\c}[1]{\boldsymbol{\mathrm{#1}}}}
24 \CustomizeMathJax{\newcommand{\sfsl}[1]{\mathsf{#1}}}% not slanted
25
26 \if@manualbold
27 \CustomizeMathJax{\newcommand{\mb}[1]{#1}}
28 \else
29 \CustomizeMathJax{\newcommand{\mb}[1]{\boldsymbol{#1}}}
30 \fi
31
32 \CustomizeMathJax{\newcommand{\diag}{\mb{\mathrm{diag}}}}
33 \CustomizeMathJax{\newcommand{\blockdiag}{\mb{\mathrm{blockdiag}}}}
34 \CustomizeMathJax{\newcommand{\erf}{\mb{\mathrm{erf}}}}
35 \CustomizeMathJax{\newcommand{\logit}{\mb{\mathrm{logit}}}}
36 \CustomizeMathJax{\newcommand{\trace}{\mb{\mathrm{trace}}}}
37
38 \CustomizeMathJax{\newcommand{\chisq}{\mb{\chi^2}}}
39 \CustomizeMathJax{\newcommand{\deriv}[2]{\mb{\frac{d}{d{#1}}}\wrap{\mb{#2}}}}
40 \CustomizeMathJax{\newcommand{\deriv}[2]{\mb{\frac{d}{d{#2}}}\wrap{\mb{#1}}}}
41 \CustomizeMathJax{\newcommand{\e}[1]{\mb{\mathrm{e}^{#1}}}}
42 \CustomizeMathJax{\newcommand{\E}[2][{}]{\mb{\mathrm{E}}_{\mb{#1}} \wrap{\mb{#2}}}}
43 \CustomizeMathJax{\newcommand{\ha}{\mb{\frac{\alpha}{2}}}}
44 \CustomizeMathJax{\newcommand{\I}[2][{}]{%
45 \mb{\mathrm{I}}_{\mb{#1}} \LWRwrapparen{\mb{#2}}%
46 }}
47 \CustomizeMathJax{\newcommand{\IBeta}[2][{}]{%
48 \mb{\frac{\Gamma[#+#2]}{\Gamma[#+1]\Gamma[#+2]}}%
49 }}
50 \CustomizeMathJax{\newcommand{\If}{\; \mb{\mathrm{if}} \; ;}}
51 \CustomizeMathJax{\newcommand{\im}{\mb{\mathrm{i}}}}
52 \CustomizeMathJax{\newcommand{\ol}{\overline{}}}
53 \CustomizeMathJax{\newcommand{\ow}{\; \mb{\mathrm{otherwise}} \; ;}}
54 \CustomizeMathJax{\newcommand{\pderiv}[2][{}]{%

```

```

55 \mb{\frac{\partial}{\partial #1}}\wrap{\mb{#2}}%
56 }}
57 \CustomizeMathJax{\newcommand{\pderivf}[2]{%
58 \mb{\frac{\partial}{\partial #2}}\wrap{\mb{#1}}%
59 }}
60 \CustomizeMathJax{\newcommand{\sd}{\mb{\sigma}}}
61 \CustomizeMathJax{\newcommand{\ul}{\underline}}
62 \CustomizeMathJax{\newcommand{\V}[2][\mb{\mathrm{V}}_{\mb{#1}}}\wrap{\mb{#2}}}}
63 \CustomizeMathJax{\newcommand{\vs}{\; \mb{\mathrm{vs.}} \;}}
64 \CustomizeMathJax{\newcommand{\where}{\; \mb{\mathrm{where}} \;}}
65 \CustomizeMathJax{\newcommand{\wrap}[2][\left[#2 \right]]% only []
66 \CustomizeMathJax{\newcommand{\LWRwrapparen}[1][\left(#1 \right)]}% lwarp
67
68 % \CustomizeMathJax{\renewcommand{\sim}{\mb{\sim}}}% doesn't work,
69 % replace <space>~<space> with <space>\sim<space>
70
71 \CustomizeMathJax{\newcommand{\iid}{\; \stackrel{\mb{\mathrm{iid}}}{\sim}} \;}
72 \CustomizeMathJax{\newcommand{\ind}{\; \stackrel{\mb{\mathrm{ind}}}{\sim}} \;}
73 \CustomizeMathJax{\newcommand{\indpr}{%
74 \; \stackrel{\mb{\mathrm{ind}}}{\stackrel{\mb{\mathrm{prior}}}{\sim}} \;}%
75 }}
76 \CustomizeMathJax{\newcommand{\post}{\; \stackrel{\mb{\mathrm{post}}}{\sim}} \;}
77 \CustomizeMathJax{\newcommand{\prior}{\; \stackrel{\mb{\mathrm{prior}}}{\sim}} \;}
78
79 \CustomizeMathJax{\let\STATEXGamma=\Gamma}
80 \CustomizeMathJax{\renewcommand{\Gamma}[1][\mb{\STATEXGamma}\LWRwrapparen{\mb{#1}}}}
81 %
82 \CustomizeMathJax{\renewcommand{\and}{\; \mb{\mathrm{and}} \;}}
83 %
84 \CustomizeMathJax{\newcommand{\H}{\mb{\mathrm{H}}}}
85 %
86 \CustomizeMathJax{\newcommand{\P}[2][\mb{\mathrm{P}}_{\mb{#1}}}\wrap{\mb{#2}}}}
87 %
88 \CustomizeMathJax{\newcommand{\|}{\mb{\mid}}}
89
90 \CustomizeMathJax{\newcommand{\B}[1][\mb{\mathrm{B}}]\LWRwrapparen{\mb{#1}}}}
91 \CustomizeMathJax{\newcommand{\BB}[1][\mb{\mathrm{BetaBin}}]\LWRwrapparen{\mb{#1}}}}
92 \CustomizeMathJax{\newcommand{\Bin}[2][\mb{\mathrm{Bin}}]\LWRwrapparen{\mb{#1}, \ #2}}}}
93 \CustomizeMathJax{\newcommand{\Dir}[1][\mb{\mathrm{Dirichlet}}]\LWRwrapparen{\mb{#1}}}}
94 \CustomizeMathJax{\newcommand{\HG}[3]{%
95 \mb{\mathrm{Hypergeometric}}\LWRwrapparen{\mb{#1}, \ #2, \ #3}}%
96 }}
97 \CustomizeMathJax{\newcommand{\M}[2]{%
98 \mb{\mathrm{Multinomial}}\LWRwrapparen{\mb{#1}, \ #2}}%
99 }}
100 \CustomizeMathJax{\newcommand{\NB}[2][\mb{\mathrm{NegBin}}]\LWRwrapparen{\mb{#1}, \ #2}}}}
101 \CustomizeMathJax{\newcommand{\Poi}[1][\mb{\mathrm{Poisson}}]\LWRwrapparen{\mb{#1}}}}
102 \CustomizeMathJax{\let\Poisson=\Poi}
103
104 \CustomizeMathJax{\newcommand{\pBB}[4][x]{%
105 \mb{\frac{\Gamma[#+1]\Gamma[#+1]\Gamma[#+4-#1]\Gamma[#+4]}{\Gamma[#+1]\Gamma[#+1]\Gamma[#+3+#+4]\Gamma[#+3]\Gamma[#+4]}}%
106 \I[#+1]{\{0, 1, \dots, #2\}}, \ where \ #3>0, \; \ #4>0 \ and \ n=1, 2, \dots}%
107
108 }}
109 \CustomizeMathJax{\newcommand{\pBin}[3][x]{%

```

```

110 \mb{\binom{#2}{#1}#3^{#1}} \LWRwrapparen{\mb{{1-#3}^{#2-#1}}}%
111 \mb{\I[#1]{\{0,1,\.,#2\}}, \where p \in (0, 1) \and n=1, 2,\.%
112 }}
113 \CustomizeMathJax{\newcommand{\pPoi}[2][x]{%
114 \mb{\frac{1}{#1!}#2^{#1}e^{-#2}\I[#1]{\{0, 1,\.\}}, \where #2>0}%
115 }}
116
117 \CustomizeMathJax{\newcommand{\Cau}[2]{\mb{\mathrm{Cauchy}}\LWRwrapparen{\mb{#1, \ #2}}}}
118 \CustomizeMathJax{\let\Cauchy=\Cau}
119 \CustomizeMathJax{\newcommand{\Chi}[2][x]{%
120 \chisq_{\mb{#1}}\LWRwrapparen{\mb{#2}}}%
121 }}
122 \CustomizeMathJax{\let\Chisq=\Chi}
123 \CustomizeMathJax{\newcommand{\Bet}[2]{\mb{\mathrm{Beta}}\LWRwrapparen{\mb{#1, \ #2}}}}
124 \CustomizeMathJax{\let\Beta=\Bet}
125 \CustomizeMathJax{\newcommand{\Exp}[1]{\mb{\mathrm{Exp}}\LWRwrapparen{\mb{#1}}}}
126 \CustomizeMathJax{\newcommand{\F}[2]{\mb{\mathrm{F}}\LWRwrapparen{\mb{#1, \ #2}}}}
127 \CustomizeMathJax{\newcommand{\Gam}[2]{\mb{\mathrm{Gamma}}\LWRwrapparen{\mb{#1, \ #2}}}}
128 \CustomizeMathJax{\newcommand{\IC}[1]{\mb{\mathrm{\chi^{-2}}}\LWRwrapparen{\mb{#1}}}}
129 \CustomizeMathJax{\newcommand{\IG}[2]{%
130 \mb{\mathrm{Gamma}^{-1}}\LWRwrapparen{\mb{#1, \ #2}}}%
131 }}
132 \CustomizeMathJax{\newcommand{\IW}[2]{%
133 \mb{\mathrm{Wishart}^{-1}}\LWRwrapparen{\mb{#1, \ #2}}}%
134 }}
135 \CustomizeMathJax{\newcommand{\Log}[2]{%
136 \mb{\mathrm{Logistic}}\LWRwrapparen{\mb{#1, \ #2}}}%
137 }}
138 \CustomizeMathJax{\newcommand{\LogN}[2]{%
139 \mb{\mathrm{Log\!-\!N}}\LWRwrapparen{\mb{#1, \ #2}}}%
140 }}
141 \CustomizeMathJax{\newcommand{\N}[3][x]{%
142 \mb{\mathrm{N}}_{\mb{#1}}\LWRwrapparen{\mb{#2, \ #3}}}%
143 }}
144 \CustomizeMathJax{\newcommand{\Par}[2]{\mb{\mathrm{Pareto}}\LWRwrapparen{\mb{#1, \ #2}}}}
145 \CustomizeMathJax{\let\Pareto=\Par}
146 \CustomizeMathJax{\newcommand{\Tsq}[2]{\mb{\mathrm{T}^2}\LWRwrapparen{\mb{#1, \ #2}}}}
147 \CustomizeMathJax{\newcommand{\U}[1]{\mb{\mathrm{U}}\LWRwrapparen{\mb{#1}}}}
148 \CustomizeMathJax{\newcommand{\W}[2]{\mb{\mathrm{Wishart}}\LWRwrapparen{\mb{#1, \ #2}}}}
149
150 \CustomizeMathJax{\renewcommand{\t}[1]{\mb{\mathrm{t}}\LWRwrapparen{\mb{#1}}}}
151
152 \CustomizeMathJax{\newcommand{\pBet}[3][x]{%
153 \IBeta{#2}{#3}%
154 #1^{#2-1}\LWRwrapparen{1-#1}^{#3-1}\I[#1]{0, \ 1}, \where #2>0 \and #3>0%
155 }}
156 \CustomizeMathJax{\newcommand{\pCau}[3][x]{%
157 % \ifthenelse{\equal{#2, #3}{0, 1}}{\frac{1}{\cpi}\LWRwrapparen{1+#1}^2}}%
158 {\frac{1}{#3\cpi}\left\{1+\wrap{\LWRwrapparen{x-#2}/#3}^2\right\}}, \where #3>0}%
159 }}% no special case for 0,1
160 \CustomizeMathJax{\newcommand{\pChi}[2][x]{%
161 \frac{2^{-#2/2}}{\Gamma[#2/2]}#1^{#2/2-1}e^{-#1/2}}%
162 \I[#1]{0, \infty}, \where #2>0%
163 }}
164 \CustomizeMathJax{\newcommand{\pExp}[2][x]{%

```

```

165 \frac{1}{#2}\e^{-#1/#2}\I[#1]{0,\infty},%
166 \where #2>0%
167 }}
168 \CustomizeMathJax{\newcommand{\pGam}[3][x]{%
169 \frac{#3^{#2}}{\Gamma[#2]}#1^{#2-1}\e^{-#3#1}%
170 \I[#1]{0,\infty}, \where #2>0 \and #3>0%
171 }}
172 \CustomizeMathJax{\newcommand{\pN}[3][x]{%
173 % \ifthenelse{equal{#2, #3}{0, 1}}%
174 % {\frac{1}{\sqrt{2\cpi}}\e^{-#1^2/2}}%
175 % {\frac{1}{\sqrt{2\cpi \cdot #3}}\e^{-\LWRwrapparen{#1-#2}^2/2 \cdot #3}}%
176 }}% no test for 0,1, must add \cdot
177 \CustomizeMathJax{\newcommand{\pPar}[3][x]{%
178 \frac{#3}{#2\LWRwrapparen{1+#1/#2}^{#3+1}}\I[#1]{0,\infty},%
179 \where #2>0 \and #3>0%
180 }}
181 \CustomizeMathJax{\newcommand{\pU}[3][x]{%
182 % \ifthenelse{equal{#2, #3}{0, 1}}{\I[#1]{0, \ 1}}%
183 % {\frac{1}{#3-#2}\I[#1]{#2, \ #3}, \where #2<#3}%
184 }}% no special case for 0,1
185
186 \CustomizeMathJax{\newcommand{\=} [1]{\bar{#1}}}
187 \CustomizeMathJax{\let^~\widehat}
188 \CustomizeMathJax{\let~\widetilde}
189 \CustomizeMathJax{\newcommand{\'} [1]{\LWRwrapparen{\mb{#1}}}}
190 \CustomizeMathJax{\newcommand{\b} [1]{\bar{#1}}}
191 \CustomizeMathJax{\newcommand{\c} [1]{\mb{\mathrm{#1}}}}
192 \CustomizeMathJax{\newcommand{\d} [1]{\, \mb{\mathrm{d}}{#1}}}
193 \CustomizeMathJax{\newcommand{\.} {\mb{\ldots}}}
194 \end{warpMathJax}

```

---

File 438 **lwarp-statistics.sty**

§ 544 Package **statistics**

*(Emulates or patches code by JULIEN RIVAUD.)*

Pkg statistics statistics is patched for use by lwarp.

 **\color** The statistics documentation examples include the use of the `\color` macro. Use `\textcolor` instead.

 **math** The statistics package uses math arrays, but the HTML version uses text tabulars to allow text copy/paste. If math is required, use `\ensuremath` or `\( and \)` as needed.

Pre/postline is ignored, and `\hline` is used instead. Each table will have an `\hline` above and below as a frame.

**for HTML output:** 1 \LWR@ProvidesPackagePass{statistics}[2019/09/29]

2 \ExplSyntaxOn

To use text tabular instead of math array. This allows text copy/paste of the results.

In the following, all changes for the Lwarp package are labelled "lwarp".

Redefined using the lwarp version of &:

```

3 \StartDefiningTabulars% lwarp
4 \cs_set_protected_nopar:Nn __statistics_table_make:nn {
5 \int_compare:nT
6 { 0 < \l__statistics_table_maxcols_int
7 = \l__statistics_nbvals_int } {
8 __statistics_table_end:
9 \tl_use:N \l__statistics_table_sep_tl
10 __statistics_table_start:
11 }
12 \int_incr:N \l__statistics_nbvals_int
13 \int_incr:N \l__statistics_currange_int
14 \fp_add:Nn \l__statistics_curtotal_fp { #2 }
15 __statistics_set_if_shown:N \l_tmpa_bool
16 \tl_set:Nx \l_tmpa_tl {
17 \exp_not:n { & \tl_set:Nn \currentcolumn } {
18 \int_use:N \l__statistics_currange_int
19 }
20 }
21 \bool_if:NTF \l_tmpa_bool {
22 \tl_put_right:Nn \l_tmpa_tl
23 { __statistics_table_shown_format:n }
24 }{
25 \tl_put_right:Nn \l_tmpa_tl
26 { __statistics_table_hidden_format:n }
27 }
28 \seq_put_right:Nn \l__statistics_store_values_seq { #1 }
29 \bool_if:NT \l__statistics_table_values_bool {
30 \tl_put_right:Nx \l__statistics_table_values_tl {
31 \exp_not:V \l_tmpa_tl {
32 \exp_not:n {
33 __statistics_table_values_format:n { #1 }
34 }
35 }
36 }
37 }
38 \seq_put_right:Nx \l__statistics_store_counts_seq { \fp_eval:n {#2} }
39 \bool_if:NT \l__statistics_table_counts_bool {
40 \tl_put_right:Nx \l__statistics_table_counts_tl {
41 \exp_not:V \l_tmpa_tl {
42 \exp_not:n {
43 __statistics_table_counts_format:n {
44 { __statistics_table_allcounts_format:n { #2 } }
45 }
46 }
47 }
48 }
49 }
50 \bool_if:NT \l__statistics_table_icc_bool {
51 \tl_put_right:Nx \l__statistics_table_icc_tl {
52 \exp_not:V \l_tmpa_tl {
53 \exp_not:n { __statistics_table_icc_format:n }

```

```

54 {
55 \exp_not:n{ __statistics_table_allcounts_format:n }
56 { \fp_use:N __statistics_curtotal_fp }
57 }
58 }
59 }
60 }
61 \bool_if:NT __statistics_table_dcc_bool {
62 \tl_put_right:Nx __statistics_table_dcc_tl {
63 \exp_not:V \l_tmpa_tl {
64 \exp_not:n { __statistics_table_dcc_format:n }
65 {
66 \exp_not:n{ __statistics_table_allcounts_format:n }
67 {
68 \fp_eval:n {
69 __statistics_total_fp
70 - __statistics_curtotal_fp
71 + #2
72 }
73 }
74 }
75 }
76 }
77 }
78 \fp_set:Nn __statistics_table_curICF_fp {
79 round(__statistics_curtotal_fp
80 / __statistics_total_fp,
81 __statistics_table_round_int)
82 }
83 \bool_if:NT __statistics_table_frequencies_bool {
84 \tl_put_right:Nx __statistics_table_frequencies_tl {
85 \exp_not:V \l_tmpa_tl {
86 \exp_not:n { __statistics_table_frequencies_format:n }
87 {
88 \exp_not:n{ __statistics_table_allfreqs_format:n }
89 {
90 \fp_eval:n {
91 __statistics_table_curICF_fp
92 - __statistics_table_prevICF_fp
93 }
94 }
95 }
96 }
97 }
98 }
99 \bool_if:NT __statistics_table_icf_bool {
100 \tl_put_right:Nx __statistics_table_icf_tl {
101 \exp_not:V \l_tmpa_tl {
102 \exp_not:n { __statistics_table_icf_format:n }
103 {
104 \exp_not:n{ __statistics_table_allfreqs_format:n }
105 { \fp_to_decimal:N __statistics_table_curICF_fp }
106 }
107 }
108 }

```

```

109 }
110 \bool_if:NT \l__statistics_table_dcf_bool {
111 \tl_put_right:Nx \l__statistics_table_dcf_tl {
112 \exp_not:V \l_tmpa_tl {
113 \exp_not:n { __statistics_table_dcf_format:n }
114 {
115 \exp_not:n{ __statistics_table_allfreqs_format:n }
116 {
117 \fp_eval:n {
118 1 - \l__statistics_table_prevICF_fp
119 }
120 }
121 }
122 }
123 }
124 }
125 \fp_set_eq:NN
126 \l__statistics_table_prevICF_fp
127 \l__statistics_table_curICF_fp
128 }
129 \StopDefiningTabulars% lwarp

```

Redefined using `tabular`. Also, preline and postline do not work correctly with `lwarp`, which looks for certain tokens to detect `\hlines`, so `\hline` is used instead.

```

130 \cs_set_protected_nopar:Nn __statistics_table_end: {
131 \tl_set:Nx \l__statistics_table_preamble_tl {
132 % \exp_not:n { \begin{array}[] }
133 \exp_not:n { \begin{tabular}[] }% lwarp
134 \exp_not:V \l__statistics_table_valign_tl
135 \exp_not:n {] }
136 { \exp_not:V \l__statistics_table_headcoltype_tl
137 \prg_replicate:nn { \l__statistics_nbvals_int }
138 { \exp_not:V \l__statistics_table_coltype_tl } }
139 }
140 \seq_clear:N \l__statistics_table_contents_seq
141 \clist_map_inline:nn { values, counts, icc, dcc, frequencies, icf, dcf } {
142 \bool_if:cT { l__statistics_table_##1_bool } {
143 \seq_put_right:Nv
144 \l__statistics_table_contents_seq
145 { l__statistics_table_##1_tl }
146 }
147 }
148 % $
149 \tl_use:N \l__statistics_table_preamble_tl
150 \hline% lwarp
151 % \l__statistics_table_preline_tl
152 \seq_use:Nn
153 \l__statistics_table_contents_seq
154 { \l__statistics_table_newline_tl }
155 \\
156 % \l__statistics_table_postline_tl
157 \hline% lwarp
158 % \end{array}$
159 \end{tabular}% lwarp

```

160 }

With `lwarp`, `\ensuremath` creates an svg image, but its `alt` tag does not contain the text of the contents for copy/paste, since these expressions are usually not simple text. For the `statistics` package, copy/paste is restored by using text instead of math output.

For the leftmost column. Redefined to use text output:

```

161 \cs_set_protected_nopar:Nn __statistics_table_start: {
162 \int_zero:N \l__statistics_nbvals_int
163 \clist_pop:NNT \l__statistics_table_maxcols_clist \l_tmpa_tl {
164 \int_set:Nn \l__statistics_table_maxcols_int { \l_tmpa_tl }
165 }
166 \clist_map_inline:nn { values, counts, frequencies, icc, icf, dcc, dcf } {
167 \tl_set:cx { l__statistics_table_##1_tl } {
168 % \exp_not:N \ensuremath {
169 \exp_not:N \hbox {
170 \exp_not:c { l__statistics_table_##1_name_tl }
171 }
172 % }
173 }
174 }
175 }
```

For the first row. Redefined to use text output:

```

176 \RenewDocumentCommand __statistics_IN:w { m u{;} u{;} m } {
177 % \ensuremath{ \left#1 \num{#2} \mathbin{;} \num{#3} \right#4 }
178 #1 #2 ; #3 #4% lwarp
179 }
180
181 __statistics_setup:nn { table } {
182 % values/format = \ensuremath{#1},
183 values/format = {#1},% lwarp
184 }
```

Added `\ExplSyntaxOn/Off` to avoid errors. (In once instance, a double subscript error appeared.)

```

185 \RenewDocumentCommand \StatsGraph { +0{} +m +0{} } {
186 \group_begin:
187 \int_gincr:N \g__statistics_graph_last_int
188 \tl_set:Nx \l_tmpa_tl {
189 \exp_not:n { g__statistics_graph_xstep_ }
190 \int_use:N \g__statistics_graph_last_int
191 \exp_not:n { _tl }
192 }
193 \tl_if_exist:cTF { \l_tmpa_tl } {
194 \fp_gset:Nn \g__statistics_graph_xstep_fp
195 { \tl_use:c { \l_tmpa_tl } }
196 }{
197 \fp_gset:Nn \g__statistics_graph_xstep_fp { \c_one_int }
198 }
199 __statistics_setup:nn { graph } { #1, #3 }
200 \tl_if_single:nTF { #2 } {
```

```

201 \cs_if_exist:NF #2 { #2 }
202 \tl_set_eq:NN \l__statistics_data_tl #2
203 }{
204 \tl_set:Nn \l__statistics_data_tl { #2 }
205 }
206 \fp_zero:N \l__statistics_graph_maxheight_fp
207 \fp_set:Nn \l__statistics_graph_minvalue_fp {inf}
208 \fp_set:Nn \l__statistics_graph_maxvalue_fp {-inf}
209 \fp_zero:N \l__statistics_total_fp
210 \int_zero:N \l__statistics_nbvals_int
211 \bool_set_true:N \l__statistics_graph_allranges_bool
212 \keyval_parse:NNV
213 __statistics_graph_prepare:n
214 __statistics_graph_prepare:nn
215 \l__statistics_data_tl
216 \tl_clear:N \l__statistics_graph_tikzdata_tl
217 \tl_clear:N \l__statistics_graph_tikzinfo_tl
218 \int_zero:N \l__statistics_currange_int
219 \bool_if:NTF \l__statistics_graph_allranges_bool {
220 \bool_if:NTF \l__statistics_graph_cumulative_bool {
221 \ExplSyntaxOn% lwarp
222 __statistics_graph_dopicture_cumulative:
223 \ExplSyntaxOff% lwarp
224 }{
225 \ExplSyntaxOn% lwarp
226 __statistics_graph_dopicture_hist:
227 \ExplSyntaxOff% lwarp
228 }
229 }{
230 \ExplSyntaxOn% lwarp
231 __statistics_graph_dopicture_comb:
232 \ExplSyntaxOff% lwarp
233 }
234 \iow_now:Nx \@auxout {
235 \exp_not:n {
236 \ExplSyntaxOn
237 \tl_gset:cn
238 }
239 {
240 \exp_not:n {g__statistics_graph_xstep_}
241 \int_use:N \g__statistics_graph_last_int
242 \exp_not:n {_tl}
243 }
244 {
245 \fp_to_decimal:N \g__statistics_graph_xstep_fp
246 }
247 \exp_not:n {
248 \ExplSyntaxOff
249 }
250 }
251 \group_end:
252 }
253
254 \ExplSyntaxOff

```

File 439 **lwarp-statmath.sty**

§ 545 Package **statmath**

(Emulates or patches code by SEBASTIAN ANKARGREN.)

Pkg statmath **statmath** is used as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{statmath}[2018/03/08]

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{statmath}
6
7 \ifdefequal{\abcbf}{\mathbf}
8 {\CustomizeMathJax{\newcommand{\abcbf}[1]{\mathbf{#1}}}}
9 {\CustomizeMathJax{\newcommand{\abcbf}[1]{\boldsymbol{#1}}}}
10
11 \CustomizeMathJax{\newcommand{\greekbf}[1]{\boldsymbol{#1}}}
12
13 \CustomizeMathJax{\newcommand{\bfA}{\abcbf A}}
14 \CustomizeMathJax{\newcommand{\bfB}{\abcbf B}}
15 \CustomizeMathJax{\newcommand{\bfC}{\abcbf C}}
16 \CustomizeMathJax{\newcommand{\bfD}{\abcbf D}}
17 \CustomizeMathJax{\newcommand{\bfE}{\abcbf E}}
18 \CustomizeMathJax{\newcommand{\bfF}{\abcbf F}}
19 \CustomizeMathJax{\newcommand{\bfG}{\abcbf G}}
20 \CustomizeMathJax{\newcommand{\bfH}{\abcbf H}}
21 \CustomizeMathJax{\newcommand{\bfI}{\abcbf I}}
22 \CustomizeMathJax{\newcommand{\bfJ}{\abcbf J}}
23 \CustomizeMathJax{\newcommand{\bfK}{\abcbf K}}
24 \CustomizeMathJax{\newcommand{\bfL}{\abcbf L}}
25 \CustomizeMathJax{\newcommand{\bfM}{\abcbf M}}
26 \CustomizeMathJax{\newcommand{\bfN}{\abcbf N}}
27 \CustomizeMathJax{\newcommand{\bfO}{\abcbf O}}
28 \CustomizeMathJax{\newcommand{\bfP}{\abcbf P}}
29 \CustomizeMathJax{\newcommand{\bfQ}{\abcbf Q}}
30 \CustomizeMathJax{\newcommand{\bfR}{\abcbf R}}
31 \CustomizeMathJax{\newcommand{\bfS}{\abcbf S}}
32 \CustomizeMathJax{\newcommand{\bfT}{\abcbf T}}
33 \CustomizeMathJax{\newcommand{\bfU}{\abcbf U}}
34 \CustomizeMathJax{\newcommand{\bfV}{\abcbf V}}
35 \CustomizeMathJax{\newcommand{\bfW}{\abcbf W}}
36 \CustomizeMathJax{\newcommand{\bfX}{\abcbf X}}
37 \CustomizeMathJax{\newcommand{\bfY}{\abcbf Y}}
38 \CustomizeMathJax{\newcommand{\bfZ}{\abcbf Z}}
39 \CustomizeMathJax{\newcommand{\bfa}{\abcbf a}}
40 \CustomizeMathJax{\newcommand{\bfb}{\abcbf b}}
41 \CustomizeMathJax{\newcommand{\bfc}{\abcbf c}}
42 \CustomizeMathJax{\newcommand{\bfd}{\abcbf d}}
```

```

43 \CustomizeMathJax{\newcommand{\bfe}{\abcbf e}}
44 \CustomizeMathJax{\newcommand{\bff}{\abcbf f}}
45 \CustomizeMathJax{\newcommand{\bfg}{\abcbf g}}
46 \CustomizeMathJax{\newcommand{\bfh}{\abcbf h}}
47 \CustomizeMathJax{\newcommand{\bfi}{\abcbf i}}
48 \CustomizeMathJax{\newcommand{\bfj}{\abcbf j}}
49 \CustomizeMathJax{\newcommand{\bfk}{\abcbf k}}
50 \CustomizeMathJax{\newcommand{\bfl}{\abcbf l}}
51 \CustomizeMathJax{\newcommand{\bfm}{\abcbf m}}
52 \CustomizeMathJax{\newcommand{\bfn}{\abcbf n}}
53 \CustomizeMathJax{\newcommand{\bfo}{\abcbf o}}
54 \CustomizeMathJax{\newcommand{\bfp}{\abcbf p}}
55 \CustomizeMathJax{\newcommand{\bfq}{\abcbf q}}
56 \CustomizeMathJax{\newcommand{\bfr}{\abcbf r}}
57 \CustomizeMathJax{\newcommand{\bfs}{\abcbf s}}
58 \CustomizeMathJax{\newcommand{\bft}{\abcbf t}}
59 \CustomizeMathJax{\newcommand{\bfu}{\abcbf u}}
60 \CustomizeMathJax{\newcommand{\bfv}{\abcbf v}}
61 \CustomizeMathJax{\newcommand{\bfw}{\abcbf w}}
62 \CustomizeMathJax{\newcommand{\bfx}{\abcbf x}}
63 \CustomizeMathJax{\newcommand{\bfy}{\abcbf y}}
64 \CustomizeMathJax{\newcommand{\bfz}{\abcbf z}}
65
66 \LWR@mathjax@addgreek@l@bfit{bf}{}% Greek lowercase bold face italic
67 \LWR@mathjax@addgreek@u@bfup*{bf}{}% Greek uppercase bold face upright, cap macros.
68
69 \CustomizeMathJax{\newcommand{\bfzero}{\greekbf 0}}
70
71 \CustomizeMathJax{\DeclareMathOperator{\cov}{Cov}}
72 \CustomizeMathJax{\DeclareMathOperator{\E}{E}}
73 \CustomizeMathJax{\DeclareMathOperator{\V}{V}}
74 \CustomizeMathJax{\newcommand{\inas}{\overset{a. s.}{\to}}}
75 \CustomizeMathJax{\newcommand{\indist}{\overset{d}{\to}}}
76 \CustomizeMathJax{\newcommand{\inprob}{\overset{p}{\to}}}
77 \CustomizeMathJax{\DeclareMathOperator{\plim}{plim}}
78 \CustomizeMathJax{\DeclareMathOperator{\tr}{tr}}
79 \CustomizeMathJax{\DeclareMathOperator{\vc}{vec}}
80 \CustomizeMathJax{\DeclareMathOperator{\vcs}{vecs}}
81 \CustomizeMathJax{\DeclareMathOperator{\vch}{vech}}
82 \CustomizeMathJax{\DeclareMathOperator{\diag}{diag}}
83 \CustomizeMathJax{\DeclareMathOperator{\argmin}{arg\,min}}
84 \CustomizeMathJax{\DeclareMathOperator{\argmax}{arg\,max}}
85 \end{warpMathJax}

```

---

File 440 **lwarp-steinmetz.sty**

§ 546 Package **steinmetz**

(Emulates or patches code by ENRICO GREGORIO.)

Pkg steinmetz steinmetz is patched for use by lwarp. Emulation is provided for MATHJAX

for HTML output: 1 \LWR@ProvidesPackagePass{steinmetz}[2009/06/14]

```

2 \renewcommand{\phase}[2][]{%
3 \begin{lateximage}*[steinmetz\{\detokenize{#2}\}]
4 \ensuremath{\underline{/#2}}
5 \end{lateximage}
6 }
7
8 \begin{warpMathJax}
9 \CustomizeMathJax{\newcommand{\phase}[2][]{\underline{/#2}}}
10 \end{warpMathJax}

```

---

File 441 **lwarp-stfloats.sty**

§ 547 Package **stfloats**

Pkg stfloats stfloats is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{stfloats}[2017/03/27]

stfloats may have been preloaded by a `ltj*` class.

The following are provided in case they have not yet been defined:

```

2 \providecommand*\fnbelowfloat{}
3 \providecommand*\fnunderfloat{}
4 \providecommand*\setbaselinefloat{}
5 \providecommand*\setbaselinefixed{}

```

Nullified for HTML:

```

6 \renewcommand*\fnbelowfloat{}
7 \renewcommand*\fnunderfloat{}
8 \renewcommand*\setbaselinefloat{}
9 \renewcommand*\setbaselinefixed{}

```

---

File 442 **lwarp-struktex.sty**

§ 548 Package **struktex**

*(Emulates or patches code by JOBST HoffMANN.)*

Pkg struktex struktex is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{struktex}

```

2 \BeforeBeginEnvironment{struktogramm}{%
3 \begin{lateximage}[-struktex-~\PackageDiagramAltText]%
4 }
5 \AfterEndEnvironment{struktogramm}{\end{lateximage}}
6

```

```

7 \newenvironment{LWR@HTML@centernss}{\begin{center}}{\end{center}}
8 \LWR@formattedenv{centernss}
9
10 \newcommand{\LWR@HTML@CenterNssFile}[1]{%
11 \begin{center}
12 \input{#1.nss}
13 \end{center}
14 }
15 \LWR@formatted{CenterNssFile}
16
17 \newcommand{\LWR@HTML@centernssfile}{\LWR@HTML@CenterNssFile}
18 \LWR@formatted{centernssfile}

```

---

File 443 **lwarp-subcaption.sty**

§ 549 Package **subcaption**

*(Emulates or patches code by AXEL SOMMERFELDT.)*

Pkg subcaption subcaption is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{subcaption}[2018/05/01]

Tells `lwarp` to ignore minipage widths inside a subfigure or subtable. In print mode the minipages are used to place the items next to each other. In HTML they are placed side-by-side automatically.

```

2 \xpretocmd{\subcaption@iiminipage}
3 {\minipagefullwidth}
4 {}
5 {\LWR@patcherror{subcaption}{subcaption@iiminipage}}

```

Likewise for a `\subcaptionbox`:

```

6 \xpretocmd{\subcaptionbox}
7 {\minipagefullwidth}
8 {}
9 {\LWR@patcherror{subcaption}{subcaptionbox}}

```

---

File 444 **lwarp-subfig.sty**

§ 550 Package **subfig**

*(Emulates or patches code by STEVEN DOUGLAS COCHRAN.)*

Pkg subfig subfig is supported and patched by lwarp.

 **table numbering** To have correct sub table numbers:

```

\usepackage{caption}
\captionsetup[table]{position=top}

```

⚠ **lof/lotdepth** At present, the package options for lofdepth and lotdepth are not working. These counters must be set separately after the package has been loaded.

⚠ **horizontal spacing** In the document source, use `\hfill` and `\hspace*` between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

**for HTML output:** Accept all options for `lwarp-subfig`:

```
1 \LWR@ProvidesPackagePass{subfig}[2005/06/28]
```

```
\sf@@@subfloat {<1 type>} [<2 LOF entry>] [<3 caption>] {<4 contents>}
```

The outer minipage allows side-by-side subfloats with `\hfill` between.

```
2 \long\def\sf@@@subfloat#1[#2][#3]#4{%
3 \begin{minipage}{\linewidth}% lwarp

4 \IfValueTF{#2}{%
5 \LWR@setlatestname{#2}%
6 }{%
7 \IfValueTF{#3}{%
8 \LWR@setlatestname{#3}%
9 }{%
10 }%
11 \LWR@stoppars% lwarp
12 \ifundefined{FBsc@max}{%
13 {\FB@readaux{\let\FBsuboheight\relax}}%
14 \@tempcnta=\@ne
15 \if@minipage
16 \@tempcnta=\z@
17 \else\ifdim \lastskip=\z@ \else
18 \@tempcnta=\tw@
19 \fi\fi
20 \ifmaincaptiontop
21 \sf@top=\sf@nearskip
22 \sf@bottom=\sf@farskip
23 \else
24 \sf@top=\sf@farskip
25 \sf@bottom=\sf@nearskip
26 \fi
27 \leavevmode

28 % \setbox\@tempboxa \hbox{#4}%
29 % \@tempdima=\wd\@tempboxa
30 % \ifundefined{FBsc@max}{%
31 % {\global\advance\Xhsize-\wd\@tempboxa
32 % \dimen@=\ht\@tempboxa
33 % \advance\dimen@\dp\@tempboxa
34 % \ifdim\dimen@>\FBso@max
35 % \global\FBso@max\dimen@
36 % \fi}%

```

Do not use boxes, which interfere with `lateximages`:

```

37 % \vtop%
38 \bgroup
39 % \vbox%
40 \bgroup
41 \ifcase\@tempcnta
42 \@minipagefalse
43 \or
44 % \vskip\sf@top
45 \or
46 \ifdim \lastskip=\z@ \else
47 % \@tempskipb\sf@top\relax\@xaddvskip
48 \fi
49 \fi
50 \sf@ifpositiontop{%
51 \ifx \@empty#3\relax \else
52 \sf@subcaption{#1}{#2}{#3}%
53 % \vskip\sf@capskip
54 % \vskip\sf@captopadj
55 \fi\egroup
56 % \hrule width0pt height0pt depth0pt
57 \LWR@startpars% lwarp
58 % \box\@tempboxa
59 #4
60 \LWR@stoppars% lwarp
61 }{%
62 \LWR@startpars% lwarp
63 \@ifundefined{FBsc@max}%
64 {
65 % \box\@tempboxa
66 #4
67 }%
68 {\ifx\FBsuboheight\relax
69 % \box\@tempboxa
70 #4
71 \else
72 % \vbox to \FBsuboheight{\FBafil\box\@tempboxa\FBbfil}%
73 #4
74 \fi}%
75 \LWR@stoppars% lwarp
76 \egroup
77 \ifx \@empty#3\relax \else
78 % \vskip\sf@capskip
79 % \hrule width0pt height0pt depth0pt
80 \sf@subcaption{#1}{#2}{#3}%
81 \fi
82 }%
83 % \vskip\sf@bottom
84 \egroup
85 \@ifundefined{FBsc@max}{%
86 {\addtocounter{FRobj}{-1}%
87 \ifnum\c@FRobj=0\else
88 \subfloatrowsep
89 \fi}%
90 \ifmaincaptiontop\else
91 \global\advance\@nameuse{c@\@capytype}\m@ne

```

```

92 \fi
93 \end{minipage}% lwarp
94 \LWR@startpars% lwarp
95 \endgroup\ignorespaces%
96 }%

```

\sf@subcaption    {<1 type>} {<2 LOF entry>} {<3 caption>}

```

97 \long\def\sf@subcaption#1#2#3{%
98 \LWR@stoppars% lwarp
99 \ifx \relax#2\relax \else
100 \bgroup
101 \let\label=@gobble
102 \let\protect=\string
103 \def\@subcaplabel{%
104 \caption@lstfmt{\@nameuse{p@#1}}{\@nameuse{the#1}}}%
105 \sf@updatecaptionlist{#1}{#2}{\the\value{\@captype}}{\the\value{#1}}%
106 \egroup
107 \fi
108 \bgroup
109 \ifx \relax#3\relax
110 \let\captionlabelsep=\relax
111 \fi
112 % \setbox0\vbox{%
113 % \hb@xt@\the\@tempdima{%
114 %
115 % \hss
116 % \parbox[t]{\the\@tempdima}{%
117 % \caption@make
118 % {\@nameuse{sub\@captype name}}%
119 % {\@nameuse{thesub\@captype}}%
120 % {#3}
121 % }%
122 % \hss
123 % }
124 % }%
125 \@ifundefined{FBsc@max}%
126 % {\box0}%
127 % {
128 % \parbox[t]{\the\@tempdima}{%
129 % \LWR@traceinfo{sfsubcap B1}% lwarp
130 % \LWR@figcaption% lwarp
131 % \caption@make
132 % {\@nameuse{sub\@captype name}}%
133 % {\@nameuse{thesub\@captype}}%
134 % {\LWR@isolate{#3}}%
135 % }
136 % \LWR@traceinfo{sfsubcap B2}% lwarp
137 % }%
138 % }%
139 {\dimen@ht0%
140 \advance\dimen@dp0%
141 \ifdim\dimen@>\FBsc@max
142 \global\FBsc@max\dimen@

```

```

143 \fi
144 \FB@readaux{\let\FBsubcheight\relax}%
145 \ifx\FBsubcheight\relax
146 \def\next{
147 % \parbox[t]{\the\@tempdima}
148 }%
149 \else
150 \def\next{
151 % \parbox[t][\FBsubcheight][t]{\the\@tempdima}
152 }%
153 \fi
154 % \vbox{%
155 % \hbext\the\@tempdima{%
156
157 % \hss
158 % \next{%
159 \LWR@traceinfo{sfsubcap C1}% lwarp
160 \caption@make
161 {\@nameuse{sub\@capttype name}}%
162 {\@nameuse{thesub\@capttype}}%
163 {#3}
164 \LWR@traceinfo{sfsubcap C1}% lwarp
165 % }%
166 % \hss
167
168 % }
169 % }
170 % }%
171 \egroup
172 \LWR@startpars% lwarp
173 }

```

`\subfloat@label` Patches for `\sf@sub@label`:

```

174 \def\subfloat@label{%
175 \LWR@ensuredoingapar% lwarp
176 \ifnextchar(% %) match left parenthesis
177 {\sf@sub@label}
178 {\sf@sub@label(Sub\@capttype\space
179 \@ifundefined{thechapter}{\@nameuse{thechapter}\space}%
180 \@nameuse{p@sub\@capttype}%
181 \@nameuse{thesub\@capttype}.)}}

```

Patches for `\subref`.

`\sf@subref`     $\{\langle label \rangle\}$

The unstarred version uses a `\ref` link whose printed text comes from the `sub@<label>`:

```

182 \renewcommand{\sf@subref}[1]{%
183 \LWR@subnewref{#1}{sub#1}%
184 }

```

`\sf@@subref`     $\{\langle label \rangle\}$

The starred version uses the printed `sub@<label>` which is stored as if it were a page number:

```
185 \renewcommand{\sf@@subref}[1]{\LWR@orig@pageref{sub@#1}}
```

Defining new subfloats. The `l@sub<type>` for each is redefined.

```
\@newsubfloat [⟨keys/values⟩] {⟨float name⟩}
186 \LetLtxMacro\LWR@orig@newsubfloat\@newsubfloat
187
188 \def\@newsubfloat[#1]#2{%
189 \LWR@orig@newsubfloat[#1]{#2}%
190 \renewcommand{\l@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
191 }
```

Pre-defined for figures and tables:

```
\l@subfigure {⟨text⟩} {⟨pagenum⟩}
192 \renewcommand{\l@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}

\l@subtable {⟨text⟩} {⟨pagenum⟩}
193 \renewcommand{\l@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
```

File 445 **lwarp-subfigure.sty**

§ 551 Package **subfigure**

Pkg subfigure subfigure is emulated by subfig.

```
for HTML output: 1 \LWR@ProvidesPackageDrop{subfigure}[2002/03/15]
2 \RequirePackage{subfig}

3 \LetLtxMacro\subfigure\subfloat
4 \LetLtxMacro\subtable\subfloat
5 \LetLtxMacro\Subref\subref
6 \@ifundefined{figuretopcaptrue}{\newif\iffiguretopcap}{}
7 \newif\ifsubfiguretopcap
8 \newif\ifsubcaphang
9 \newif\ifsubcapcenter
10 \newif\ifsubcapcenterlast
11 \newif\ifsubcapnooneline
12 \newif\ifsubcapraggedright
13 \newskip\subfigtopskip
14 \newskip\subfigcapskip
15 \newdimen\subfigcaptopadj
16 \newskip\subfigbottomskip
17 \newdimen\subfigcapmargin
18 \newskip\subfiglabelskip
19 \newcommand*{\subcapsize}{}

```

```
20 \newcommand*\subcaplabelfont{}
21 \newcommand*\subcapfont{}
```

File 446 **lwarp-subsubscripts.sty**

§ 552 Package **subsubscripts**

(Emulates or patches code by RICCARDO BRESCIANI.)

Pkg subsubscripts subsubscripts is used as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass[subsubscripts][2009/10/27]

The larger skips are used here.

```
2 \begin{warpMathJax}
3 \CustomizeMathJax{%
4 \newcommand{\fourscriptsC}[7]{%
5 {}^{#2}_{#3}\hspace{#6}#1\hspace{#7}{ }^{#4}_{#5}%
6 }
7 }
8 \CustomizeMathJax{%
9 \newcommand{\lrsubscriptsC}[5]{%
10 \fourscriptsC{#1}{#2}{#3}{#4}{#5}%
11 }
12 }
13 \CustomizeMathJax{%
14 \newcommand{\lrsuperscriptsC}[5]{%
15 \fourscriptsC{#1}{#2}{#3}{#4}{#5}%
16 }
17 }
18 \CustomizeMathJax{%
19 \newcommand{\fourscripts}[5]{%
20 \fourscriptsC{#1}{#2}{#3}{#4}{#5}{0ex}{0ex}%
21 }
22 }
23 \CustomizeMathJax{%
24 \newcommand{\lrsubscripts}[3]{\fourscripts{#1}{#2}{#3}}
25 }
26 \CustomizeMathJax{%
27 \newcommand{\lrsuperscripts}[3]{\fourscripts{#1}{#2}{#3}}
28 }
29 \CustomizeMathJax{%
30 \newcommand{\twoscripts}[4][-.16ex]{ }^{#3}_{#4}\hspace{#1}#2
31 }
32 \CustomizeMathJax{%
33 \newcommand{\tworscripts}[4][-.07ex]{#2\hspace{#1}{ }^{#3}_{#4}}
34 }
35 \CustomizeMathJax{%
36 \newcommand{\subscript}[3][-.16ex]{\twoscripts[#1]{#2}{#3}}
37 }
38 \CustomizeMathJax{%
```

```

39 \newcommand{\lsuperscript}[3][-.16ex]{\twolscripts[#1]{#2}{#3}}
40 }
41 \CustomizeMathJax{%
42 \newcommand{\rsubscript}[3][-.07ex]{\tworscripts[#1]{#2}{#3}}
43 }
44 \CustomizeMathJax{%
45 \newcommand{\rsuperscript}[3][-.07ex]{\tworscripts[#1]{#2}{#3}}
46 }
47 \end{warpMathJax}

```

File 447 **lwarp-supertabular.sty**

§ 553 Package **supertabular**

(Emulates or patches code by JOHANNES BRAAMS, THEO JURRIENS.)

Pkg supertabular supertabular is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{supertabular}[2004/02/20]

 **Misplaced alignment tab character &** For `\tablefirsthead`, etc., enclose them as follows:

```

\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars

```

See section 8.10.1.

 **lateximage** supertabular and xtab are not supported inside a lateximage.

```

2 \newcommand{\LWRST@firsthead}{}
3
4 \newcommand{\tablefirsthead}[1]{%
5 \long\gdef\LWRST@firsthead{#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}
9 \newcommand{\tabletail}[1]{}
10
11 \newcommand{\LWRST@lasttail}{}
12
13 \newcommand{\tablelasttail}[1]{%
14 \long\gdef\LWRST@lasttail{#1}%
15 }

16 \newcommand{\tablecaption}[2][]{%
17 \long\gdef\LWRST@caption{%
18 \ifblank{#1}%
19 {\caption{#2}}%
20 {\caption[#1]{#2}}%
21 }%
22 }

```

```

23
24 \let\topcaption\tablecaption
25 \let\bottomcaption\tablecaption

26 \newcommand*{\LWRST@caption}{ }
27
28 \newcommand*{\shrinkheight}[1]{ }
29
30 \NewDocumentEnvironment{supertabular}{s o m}
31 { %
32 \LWR@traceinfo{supertabular}%
33 \begin{table}%
34 \LWRST@caption%
35 \begin{tabular}{#3}%
36 \TabularMacro\ifdefvoid{\LWRST@firsthead}%
37 {\LWR@getmynexttoken}%
38 {\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
39 }%
40 { %
41 \ifdefvoid{\LWRST@lasttail}%
42 { }%
43 { %
44 \TabularMacro\ResumeTabular%
45 \LWRST@lasttail%
46 }%
47 \end{tabular}%
48 \end{table}%

49 \gdef\LWRST@caption{ }%

50 \LWR@traceinfo{supertabular done}%
51 }
52
53 \NewDocumentEnvironment{mpsupertabular}{s o m}
54 {\minipage{\linewidth}\supertabular{#3}}
55 {\endsupertabular\endminipage}

```

---

File 448 **lwarp-svg.sty**

§ 554 Package **svg**

(Emulates or patches code by PHILIP ILTEN, FALK HANISCH.)

Pkg svg **svg** is patched for use by **lwarp**.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{svg}[2020/10/23]

2 \xpretocmd{\includesvg}%
3 {\begin{lateximage}}%
4 {}%
5 {\LWR@patcherror{svg}{includesvg}}

```

```

6
7 \xapptocmd{\includesvg}%
8 {\end{lateximage}}%
9 {}%
10 {\LWR@patcherror{svg}{includesvg}}
11
12 \xpretocmd{\includeinkscape}%
13 {\begin{lateximage}}%
14 {}%
15 {\LWR@patcherror{svg}{includeinkscape}}
16
17 \xapptocmd{\includeinkscape}%
18 {\end{lateximage}}%
19 {}%
20 {\LWR@patcherror{svg}{includeinkscape}}

```

---

File 449 **lwarp-swfigure.sty**

§ 555 Package **swfigure**

(Emulates or patches code by CLAUDIO BECCARI.)

Pkg swfigure swfigure is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{swfigure}[2020-11-10]

```

2 \NewDocumentEnvironment{DFimage}%
3 {O{SW} m O{#4} m o D(){0.8} D<>{0} D|{|0.25} D!!{}}%
4 {%
5 \begin{figure}
6 \centering
7 \includegraphics{#2}
8 \caption[#{3}]{#4}
9 \IfValueT{#5}{\label{#5}}
10 \end{figure}
11 }%
12 {}%

```

---

File 450 **lwarp-syntonly.sty**

§ 556 Package **syntonly**

(Emulates or patches code by FRANK MITTELBACH, RAINER SCHÖPF.)

Pkg syntonly syntonly is ignored.

**for HTML output:** Discard all options for lwarp-syntonly:

```

1 \LWR@ProvidesPackageDrop{syntonly}[2017/06/30]

```

---

```

2 \newif\ifsyntax@
3 \syntax@false
4
5 \newcommand*\syntaxonly{}
6
7 \@onlypreamble\syntaxonly

8 \def\nopages@{}

```

---

File 451 **lwarp-tabfigures.sty**

§ 557 Package **tabfigures**

Pkg tabfigures tabfigures is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tabfigures}[2012/01/24]

---

File 452 **lwarp-tablefootnote.sty**

§ 558 Package **tablefootnote**

Pkg tablefootnote tablefootnote is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tablefootnote}[2014/01/26]

This works because in HTML tables are no longer floats.

```
2 \LetLtxMacro\tablefootnote\footnote
```

---

File 453 **lwarp-tables.sty**

§ 559 Package **tables**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg tables tables is emulated. \LWR@hline is used to handle the optional argument when tables is loaded.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tables}

```

2 \newdimen\tablineseq
3 \newdimen\arraylineseq
4 \newdimen\extraruleseq

```

---

File 454 **lwarp-tabularx.sty**

§ 560 Package **tabularx**

*(Emulates or patches code by DAVID CARLISLE.)*

Pkg tabularx **tabularx** is emulated by **lwarp**.

**for HTML output:** Discard all options for **lwarp-tabularx**:

```

1 \LWR@ProvidesPackageDrop{tabularx}[2016/02/03]
2 \RequirePackage{array}

3 \DeclareDocumentEnvironment{tabularx}{m o m}
4 {\tabular{#3}}
5 {\endtabular}
6
7 \DeclareDocumentEnvironment{tabularx*}{m o m}
8 {\tabular{#3}}
9 {\endtabular}

```

---

File 455 **lwarp-tabulary.sty**

§ 561 Package **tabulary**

*(Emulates or patches code by DAVID CARLISLE.)*

Pkg tabulary **tabulary** is emulated by **lwarp**.

**for HTML output:** Discard all options for **lwarp-tabulary**.

Column types L, C, R, and J are emulated by **lwarp** core code.

```

1 \LWR@ProvidesPackageDrop{tabulary}[2014/06/11]
2 \RequirePackage{array}

3 \NewDocumentEnvironment{tabulary}{m o m}
4 {\tabular{#3}}
5 {\endtabular}
6
7 \NewDocumentEnvironment{tabulary*}{m o m}
8 {\tabular{#3}}
9 {\endtabular}
10
11 \newdimen\tymin
12 \newdimen\tymax
13 \def\tyformat{}

```

File 456 **lwarp-tagpdf.sty**

§ 562 Package **tagpdf**

Pkg tagpdf tagpdf is mostly ignored, but emulates alt text, for images only. (HTML only has alternate text for images.)

(If left enabled for HTML output, tagpdf errors when producing HTML, somehow due to the HTML page numbers.)

```

for HTML output: 1 \LWR@ProvidesPackageDrop{tagpdf}[2019/07/02]

2 \ExplSyntaxOn
3
4 \tl_new:N \l__uhtag_mc_key_label_tl
5
6 \keys_define:nn { uhtag / mc }
7 {
8 tag .code:n = % the name (H,P,Span etc
9 },
10 raw .code:n =
11 {},
12 ,
13 alttext .code:n = % Alt property
14 {
15 \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
16 },
17 alttext-o .code:n = % Alt property
18 {
19 \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
20 },
21 actualtext .code:n = % ActualText property
22 {},
23 actualtext-o .code:n = % ActualText property
24 {},
25 label .tl_set:N = \l__uhtag_mc_key_label_tl,
26 artifact .code:n = {},
27 artifact .default:n = {notype}
28 }
29
30 \keys_define:nn { uhtag / struct }
31 {
32 label .tl_set:N = \l__uhtag_struct_key_label_tl,
33 stash .bool_set:N = \l__uhtag_struct_elem_stash_bool,
34 tag .code:n = % S property
35 {},
36 title .code:n = % T property
37 {},
38 title-o .code:n = % T property
39 {},
40 alttext .code:n = % Alt property

```

```

41 {
42 \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
43 },
44 alttext-o .code:n = % Alt property
45 {
46 \gdef\LWR@ThisAltText{\detokenize\expandafter{#1}}%
47 },
48 actualtext .code:n = % ActualText property
49 {},
50 actualtext-o .code:n = % ActualText property
51 {},
52 }
53
54 \NewDocumentCommand \tagpdfsetup { m }{}
55
56 \cs_set_eq:NN\tagpdfifluatexTF \sys_if_engine_luatex:TF
57 \cs_set_eq:NN\tagpdfifluatexT \sys_if_engine_luatex:T
58 \cs_set_eq:NN\tagpdfifpdfTeXT \sys_if_engine_pdfTeX:T
59 \cs_new:Npn \tagpdfget #1 {}
60 \cs_new:Npn \uftag_get:n #1 {}
61
62 \NewDocumentCommand \tagmcifinTF { m m }{}
63
64 \NewDocumentCommand \tagmcbegin { m }{\uftag_mc_begin:n {#1}\ignorespaces}
65 \cs_new_protected:Nn \uftag_mc_begin:n {
66 \group_begin:
67 \keys_set:nn { uftag / mc } {#1}
68 \group_end:
69 }
70
71 \NewDocumentCommand \tagmcend {}{\ThisAltText{}}
72
73 \cs_new_protected:Nn \uftag_mc_end: {\ThisAltText{}}
74
75 \NewDocumentCommand \tagmcuse { m }{}
76
77 \cs_new_protected:Nn \uftag_mc_use:n {}
78
79 \NewDocumentCommand \tagstructbegin { m }{
80 \uftag_struct_begin:n {#1}
81 }
82
83 \cs_new_protected:Nn \uftag_struct_begin:n
84 {
85 \group_begin:
86 \keys_set:nn {uftag / struct} { #1 }
87 \group_end:
88 }
89
90 \NewDocumentCommand \tagstructend { }{\ThisAltText{}}
91
92 \cs_new_protected:Nn \uftag_struct_end: {\ThisAltText{}}
93
94 \NewDocumentCommand \tagstructuse { m }{}
95

```

```

96 % \NewDocumentCommand\showtagpdfmcddata { 0 {__uhtag_get_mc_abs_cnt:} }{}
97 % What is the second argument?
98
99 \NewDocumentCommand\showtagpdfattributes { }{}
100
101 \sys_if_engine luatex:T
102 {
103 \NewDocumentCommand\pdffakepace { }
104 {
105 __uhtag_fakepace:
106 }
107 }
108
109 \ExplSyntaxOff

```

---

File 457 **lwarp-tascmac.sty**

§ 563 Package **tascmac**

Pkg tascmac tascmac is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tascmac}[2018/03/09]

```

2 \newenvironment*{boxnote}
3 {
4 \BlockClass[
5 padding: .5ex ;
6 border: 1px solid black ;
7 border-top: 1px dashed black ;
8]{boxnote}
9 }
10 {\endBlockClass}
11
12 \newenvironment*{screen}[1][]
13 {
14 \BlockClass[
15 padding: .5ex ;
16 border: 1px solid gray ;
17 border-radius: 8pt
18]{boxnote}
19 }
20 {\endBlockClass}
21
22 \newenvironment*{itembox}[2][]
23 {
24 \BlockClass[
25 padding: .5ex ;
26 border: 1px solid gray ;
27 border-radius: 8pt
28]{boxnote}
29 \InlineClass{itemboxtitle}{#2}\par
30 }

```

```

31 {\endBlockClass}
32
33 \newenvironment*{shadebox}
34 {
35 \BlockClass[
36 padding: .5ex ;
37 border: 1px solid black ;
38 box-shadow: 3px 3px 3px \#808080 ;
39]{boxnote}
40 }
41 {\endBlockClass}
42
43 \newcommand*{\mask}[2]{%
44 \InlineClass[background: lightgray]{mask}{#1}%
45 }
46
47 \newcommand*{\maskbox}[5]{%
48 \InlineClass[background: lightgray]{mask}{#5}%
49 }
50
51 \newcommand*{\Maskbox}[6]{%
52 \InlineClass[
53 background: lightgray ;
54 border: #5 solid black
55]{mask}{#6}%
56 }
57
58 \newcommand*{\keytop}[2][]{%
59 \InlineClass[%
60 padding: .2ex ;
61 border: 1px solid black ;
62 border-radius: .7ex ;
63]{keytop}{#2}%
64 }
65
66 \def\yen{\HTMLUnicode{00A5}}
67
68 \def\return{\HTMLUnicode{23CE}}
69
70 \def\Return{\HTMLUnicode{23CE}}
71
72 \def\asci{ASCII Corporation}
73
74 \def\Ascii{ASCII Corporation}
75
76 \def\ASCII{ASCII Corporation}

```

---

File 458 **lwarp-tcolorbox.sty**

§ 564 Package **tcolorbox**

(Emulates or patches code by THOMAS E. STURM.)

Pkg tcolorbox tcolorbox is patched for use by lwarp.

See section 8.3.8 for limitations.

for HTML output: 1 \LWR@ProvidesPackagePass{tcolorbox}[2020/04/28]

```
2 \newbool{LWR@havetcblower}
3 \boolfalse{LWR@havetcblower}
```

Colors are supported via HTML styles:

```
4 \newcommand{\LWR@tcolorbox@findcolors}{%
5 \convertcolorspec{named}{tcbcolback}{HTML}\LWR@tcbcolback
6 \convertcolorspec{named}{tcbcolframe}{HTML}\LWR@tcbcolframe
7 \iftcb@titlefilled%
8 \convertcolorspec{named}{tcbcolbacktitle}{HTML}\LWR@tcbcolbacktitle
9 \else
10 \convertcolorspec{named}{tcbcolframe}{HTML}\LWR@tcbcolbacktitle
11 \fi
12 \convertcolorspec{named}{tcbcoltitle}{HTML}\LWR@tcbcoltitle
13 \convertcolorspec{named}{tcbcolupper}{HTML}\LWR@tcbcolupper
14 \convertcolorspec{named}{tcbcollower}{HTML}\LWR@tcbcollower
15 }
16
17 \newcommand*{\LWR@tcolorbox@titlecolorstyles}{%
18 border-top: 1px solid \LWR@origpound\LWR@tcbcolframe ;
19 border-bottom: 1px solid \LWR@origpound\LWR@tcbcolframe ;
20 background: \LWR@origpound\LWR@tcbcolbacktitle ;
21 color: \LWR@origpound\LWR@tcbcoltitle ;
22 }
```

The title is placed inside its own <div> of class tcolorboxtitle.

```
23 \newcommand*{\LWR@showtitle@[1]}{%
24 \begin{BlockClass}[
25 \LWR@tcolorbox@titlecolorstyles
26]{tcolorboxtitle}
27 % \cmdKV@LWR@tcolorbox@title\par
28 \kvtcb@before@title#1\kvtcb@after@title
29 \end{BlockClass}
30 }
```

If no title, a non-breakable space is used to take some vertical space.

```
31 \newcommand*{\LWR@showtitle@[1]}{%
32 \iftcb@titlevisible
33 \LWR@showtitle@{#1}
34 \else
35 \LWR@showtitle@{~}
36 \fi
37 }
38
39 \newcommand*{\LWR@tcolorbox@dophantom}{%
40 % \sbox\tcb@phantombox{\kvtcb@phantom}%
41 % \iftcb@hasPhantom%
```

```

42 % \box\tcb@phantombox%
43 % \tcb@hasPhantomfalse%
44 % \fi%
45 \kvtcb@phantom
46 \let\kvtcb@phantom\@empty%
47 }

```

The tcolorbox is placed inside an external <div> of class #1, which is tcolorbox or tcolorbox inlineminipage. The upper and lower parts are placed into their own internal <div>s of class tcolorboxupper and tcolorboxlower.

```

48 \newcommand*\LWR@tcolorboxstart}[1]{
49 \LWR@tcolorbox@findcolors
50 \begin{BlockClass}[
51 border: 1px solid \LWR@origpound\LWR@tcbcolframe ;
52 background: \LWR@origpound\LWR@tcbcolback ;
53]{#1}
54 \LWR@tcolorbox@dophantom%
55 \ifdefvoid{\kvtcb@title}
56 {}
57 {
58 \LWR@showtitle{\kvtcb@title}
59 }
60 \begin{BlockClass}[
61 color: \LWR@origpound\LWR@tcbcolupper ;
62]{tcolorboxupper}
63 }

```

Floats enclose the tcolorbox.

```

64 \newcommand*\LWR@tcolorbox@dostartfloat}{%
65 \ifx\kvtcb@float\@empty%
66 % \tcb@set@normal@unbroken@beforeafter%
67 \else%
68 % \edef\tcb@before@unbroken{%
69 % \noexpand\tcb@float@env@begin{tcbfloat}[\kvtcb@float]%
70 % \noexpand\kvtcb@everyfloat%
71 % }%
72 % \let\tcb@after@unbroken=\tcb@float@env@end%
73 % \tcb@float@env@begin{tcbfloat}[\kvtcb@float]
74 % \noexpand\kvtcb@everyfloat
75 \fi%
76 }
77
78 \newcommand*\LWR@tcolorbox@doendfloat}{%
79 \ifx\kvtcb@float\@empty%
80 \else%
81 \tcb@float@env@end%
82 \fi%
83 }

```

Footnotes are handled via the main footnote mechanism, and pending notes are printed before and after each tcolorbox. Footnote numbering will not match the print output.

```

84 \renewenvironment{tcolorbox}[1][[]
85 {
86 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
87 {
88 \PackageError{lwarp}
89 {%
90 Lwarp cannot process a tcolorbox inside a lateximage\MessageBreak
91 or SVG math.\MessageBreak
92 Enter 'H' for possible solutions%
93 }
94 {%
95 Use \protect\tcbox, \protect\tcboxmath, or
96 \protect\tcbhighmath\space instead.\MessageBreak%
97 (Inside math, you probably want to use these anyhow.)%
98 }
99 }{\relax}
100 \LWR@printpendingfootnotes
101 \tcb@layer@inc
102 \tcb@apply@box@options{#1}
103 \LWR@tcolorbox@dostartfloat%
104 %
105 \tcbset{title=,#1}
106 \boolfalse{LWR@havetcblower}
107 \LWR@tcolorboxstart{tcolorbox}
108 \tcb@insert@before@upper%
109 }
110 {
111 \ifbool{LWR@havetcblower}{%
112 \tcb@insert@after@lower%
113 }{%
114 \tcb@insert@after@upper%
115 }%
116 \end{BlockClass}
117 \LWR@printpendingfootnotes
118 \tcb@layer@dec
119 \end{BlockClass}
120 \LWR@tcolorbox@doendfloat%
121 }

```

For the lower part, the upper part is finished then the lower is started. \tcblower is only temporarily defined where appropriate, so the HTML version is defined globally via \newcommand instead of \renewcommand.

```

121 \newcommand{\tcblower}{
122 \tcb@insert@after@upper%
123 \end{BlockClass}
124 \begin{BlockClass}[%
125 border-top: 1px dashed \LWR@origpound\LWR@tcbcolframe ;
126 color: \LWR@origpound\LWR@tcbcollower ;
127]{tcolorboxlower}
128 \tcb@insert@before@lower%
129 }

```

Starred and unstarred `\tcbline` are simple `\hrules`.

```

130 \AtBeginDocument{
131 \ifdef{\tcbline}{
132 \newcommand*\LWR@sub@tcbline}{%
133 \begin{BlockClass}{hrule}
134 \end{BlockClass}
135 }
136 \newcommand{\LWR@HTML@tcbline}{\@ifstar\LWR@sub@tcbline\LWR@sub@tcbline}
137 \LWR@formatted{tcbline}
138 }{}
139 }
140
141 \newcommand{\LWR@HTML@tcbox}[2][]{
142 \LWR@printpendingfootnotes
143 \LWR@tcolorbox@dostartfloat%
144 \begingroup
145 \tcb@layer@inc
146 \tcb@apply@box@options{#1}
147 % \tcbset{title=#1}
148 \boolfalse\LWR@havetcblower}
149 \LWR@tcolorboxstart{tcolorbox inlineminipage}
150 \tcb@insert@before@upper%
151 #2
152 \ifbool\LWR@havetcblower}{%
153 \tcb@insert@after@lower%
154 }{%
155 \tcb@insert@after@upper%
156 }%
157 \end{BlockClass}
158 \LWR@printpendingfootnotes
159 \end{BlockClass}
160 \tcb@layer@dec%
161 \endgroup%
162 \LWR@tcolorbox@dostartfloat%
163 \global\booltrue\LWR@minipagethispar}%
164 }
165 \LWR@formatted{tcbox}
166
167 \appto\LWR@restoreMathJaxformatting{%
168 \renewcommand{\tcbox}[2][]{#2}%
169 }

```

Patches for the subtitle, which is placed inside a `<div>` of class `tcolorboxsubtitle`.

```

170 \xpatchcmd{\tcbsubtitle}
171 {\begingroup}
172 {\begingroup\let\kvtcb@title\relax\begin{BlockClass}{tcolorboxsubtitle}}
173 {}
174 {\LWR@patcherror{tcolorbox}{tcbsubtitle}}
175
176 \xpatchcmd{\tcbsubtitle}
177 {\endgroup}
178 {\end{BlockClass}\endgroup}
179 {}

```

```
180 {\LWR@patcherror{tcolorbox}{tcbsubtitleB}}
```

`\tcboxfit` is the same as `\tcbox`.

```
181 \AtBeginDocument{
182 \ifdef{\tcboxfit}{%
183 \let\LWR@HTML@tcboxfit\tcbox%
184 \LWR@formatted{tcboxfit}
185 }{}
186 }
```

`\tcbtitle` is patched to support the text font.

```
187 \LetLtxMacro\LWR@HTML@tcbtitle\tcbtitle
188 \xpatchcmd{\LWR@HTML@tcbtitle}
189 {\kv tcb@before@title\tcbtitletext}
190 {\kv tcb@before@title\LWR@textcurrentfont{\LWR@textcurrentcolor{\tcbtitletext}}}
191 {}
192 {\LWR@patcherror{tcolorbox}{LWR@HTML@tcbtitle}}
193 \LWR@formatted{tcbtitle}
```

List-of:

```
194 \renewcommand*\l@tcolorbox[2]{\hypertocfloat{1}{tcolorbox}{lof}{#1}{#2}}
```

Theorem limitations. An error is printed if the document uses `math`, `ams equation`, etc. `\tcbboxmath` and `\tcbhighmath` are ignored for HTML.

```
195 \AtBeginDocument{
196 \pgfkeysifdefined{/tcb/libload/theorems}{
197
198 \def\LWR@HTML@tcb@hack@amsmath{%
199 \PackageError{lwarp}
200 {%
201 tcolorbox ‘‘math’’, ‘‘ams equation’’, and related\MessageBreak
202 are not supported.\MessageBreak
203 \protect\tcbboxmath\space and
204 \protect\tcbhighmath\space are emulated.\MessageBreak
205 Enter ‘H’ for possible solutions%
206 }
207 {%
208 Remove tcolorbox math-related options, and instead\MessageBreak
209 use the usual math environments inside each tcolorbox.%
210 }
211 }
212 \LWR@formatted{tcb@hack@amsmath}
213
214 % Cause an error if using math:
215 \tcbset{%
216 math upper/.style={before upper*=\tcb@hack@amsmath,after upper*=$},%
217 math lower/.style={before lower*=\tcb@hack@amsmath,after lower*=$},%
218 }
219
220 \appto\LWR@restoreorigformatting{%
221 \tcbset{%
```

```

222 math upper/.style={before upper*=\displaystyle,after upper*=$},%
223 math lower/.style={before lower*=\displaystyle,after lower*=$},%
224 }%
225 }
226
227 \newcommand{\LWR@HTML@tcboxmath}[2][\#2]
228 \LWR@formatted{tcboxmath}
229 \newcommand{\LWR@HTML@tcbhighmath}[2][\#2]
230 \LWR@formatted{tcbhighmath}
231 \appto\LWR@restoreMathJaxformatting{%
232 \renewcommand{\tcboxmath}[2][\#2]%
233 \renewcommand{\tcbhighmath}[2][\#2]%
234 }
235 }{}% theorems loaded
236 }% AtBeginDocument

```

For MATHJAX:

```

237 \CustomizeMathJax{\newcommand{\tcbset}[1]}
238 \CustomizeMathJax{\newcommand{\tcbsetforeverylayer}[1]}
239 \CustomizeMathJax{\newcommand{\tcbox}[2][\boxed{\text{\#2}}}}
240 \CustomizeMathJax{\newcommand{\tcboxfit}[2][\boxed{\#2}}
241 \CustomizeMathJax{\newcommand{\tcblower}{}}
242 \CustomizeMathJax{\newcommand{\tcbline}{}}
243 \CustomizeMathJax{\newcommand{\tcbtitle}{}}
244 \CustomizeMathJax{\newcommand{\tcbsubtitle}[2][\mathrm{\#2}}}}
245 \CustomizeMathJax{\newcommand{\tcboxmath}[2][\boxed{\#2}}
246 \CustomizeMathJax{\newcommand{\tcbhighmath}[2][\boxed{\#2}}

```

---

File 459 **lwarp-termcal.sty**

§ 565 Package **termcal**

(Emulates or patches code by BILL MITCHELL.)

Pkg termcal termcal is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{termcal}% questionable date in the .sty file

Nullify the @ because everything is being done in a token list.

```

2 \xpatchcmd{\endcalendar}
3 {@{}}
4 {}
5 {}
6 {\LWR@patcherror{termcal}{endcalendar}}

```

Remove the hbox:

```

7 \xpatchcmd{\ca@doaday}
8 {\hbox to \size{\calprintdate\hfill\ifclassday\calprintclass\fi}}
9 {}

```

```

10 \calprintdate\hfill\ifclassday\calprintclass\fi%
11 }
12 {}
13 {\LWR@patcherror{termcal}{ca@doaday}}

```

Change each of two ampersands to call the lwarp tabular version:

```

14 \xpatchcmd{\calday}
15 {&}
16 {\LWR@tabularampersand}
17 {}
18 {\LWR@patcherror{termcal}{calday}}
19
20 \xpatchcmd{\calday}
21 {&}
22 {\LWR@tabularampersand}
23 {}
24 {\LWR@patcherror{termcal}{calday B}}

```

---

File 460 **lwarp-textarea.sty**

§ 566 Package **textarea**

*(Emulates or patches code by ALEXANDER I. ROZHENKO.)*

Pkg `textarea` `textarea` is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{textarea}[2005/12/26]

```

2 \newcommand\StartFromTextArea{}
3 \newcommand\StartFromHeaderArea{}
4 \newcommand*\RestoreTextArea{}
5 \newcommand*\ExpandTextArea[1][*]{}
6 \let\NCC@restoretextarea\empty

```

---

File 461 **lwarp-textcomp.sty**

§ 567 Package **textcomp**

*(Emulates or patches code by FRANK MITTELBACH, ROBIN FAIRBAIRNS, WERNER LEMBERG.)*

Pkg `textcomp` `textcomp` is patched for use by lwarp.

### § 567.1 Limitations

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

 **missing symbols** Many textcomp symbols are not supported by many system / browser fonts. In the css try referencing fonts which are more complete, but expect to see gaps in coverage.

### § 567.2 Package loading

**for HTML output:** `1 \LWR@ProvidesPackagePass{textcomp}[2017/04/05]`

### § 567.3 HTML symbols

For HTML, use HTML entities or direct Unicode, depending on the engine.

`\AtBeginDocument` improves support for Lua<sup>A</sup>T<sub>E</sub>X and X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X.

#### § 567.3.1 pdf<sup>A</sup>T<sub>E</sub>X symbols

```

2 \AtBeginDocument{
3 \ifPDFTeX% pdflatex or dvi latex
4 \newcommand*\LWR@HTML@textdegree{\HTMLentity{deg}}
5 \newcommand*\LWR@HTML@textcelsius{\HTMLunicode{2103}}
6 \newcommand*\LWR@HTML@textohm{\HTMLunicode{2126}}
7 \newcommand*\LWR@HTML@textmu{\HTMLunicode{00B5}}
8 \newcommand*\LWR@HTML@textlquill{\HTMLunicode{2045}}
9 \newcommand*\LWR@HTML@textrquill{\HTMLunicode{2046}}
10 \newcommand*\LWR@HTML@textcircledP{\HTMLunicode{2117}}
11 \newcommand*\LWR@HTML@texttwelveudash{\HTMLunicode{2014}}% emdash
12 \newcommand*\LWR@HTML@textthreequartersemdash{\HTMLunicode{2014}}% emdash
13 \newcommand*\LWR@HTML@textmho{\HTMLunicode{2127}}
14 \newcommand*\LWR@HTML@textnaira{\HTMLunicode{20A6}}
15 \newcommand*\LWR@HTML@textpeso{\HTMLunicode{20B1}}
16 \newcommand*\LWR@HTML@textrecipe{\HTMLunicode{211E}}
17 \newcommand*\LWR@HTML@textinterrobang{\HTMLunicode{203D}}
18 \newcommand*\LWR@HTML@textinterrobangdown{\HTMLunicode{2E18}}
19 \newcommand*\LWR@HTML@textperthousand{\HTMLunicode{2030}}
20 \newcommand*\LWR@HTML@textpertenthousand{\HTMLunicode{2031}}
21 \newcommand*\LWR@HTML@textbaht{\HTMLunicode{0E3F}}
22 \newcommand*\LWR@HTML@textdiscount{\%}
23 \newcommand*\LWR@HTML@textservicemark{\HTMLunicode{2120}}
24 \else

```

#### § 567.3.2 X<sub>Y</sub>L<sup>A</sup>T<sub>E</sub>X and Lua<sup>A</sup>T<sub>E</sub>X symbols

NOTE: Some of the following do not print well in the listing. Consult the .dtx or .sty file for the actual characters.

```

25 \newcommand*\LWR@HTML@textdegree{\°}
26 \newcommand*\LWR@HTML@textcelsius{\C}
27 \newcommand*\LWR@HTML@textohm{\Ω}
28 \newcommand*\LWR@HTML@textmu{\μ}

```

```

29 \newcommand*\LWR@HTML@textlquill}{\l}
30 \newcommand*\LWR@HTML@textrquill}{\r}
31 \newcommand*\LWR@HTML@textcircledP}{\textcircled{P}}
32 \newcommand*\LWR@HTML@texttwelveudash}{\texttwelveudash}
33 \newcommand*\LWR@HTML@textthreequartersemdash}{\textthreequartersemdash}
34 \newcommand*\LWR@HTML@textmho}{\textmho}
35 \newcommand*\LWR@HTML@textnaira}{\textnaira}
36 \newcommand*\LWR@HTML@textpeso}{\textpeso}
37 \newcommand*\LWR@HTML@textrecipe}{\textrecipe}
38 \newcommand*\LWR@HTML@textinterrobang}{\textinterrobang}
39 \newcommand*\LWR@HTML@textinterrobangdown}{\textinterrobangdown}
40 \newcommand*\LWR@HTML@textperthousand}{\textperthousand}
41 \newcommand*\LWR@HTML@textpertenthousand}{\textpertenthousand}
42 \newcommand*\LWR@HTML@textbaht}{\textbaht}
43 \newcommand*\LWR@HTML@textdiscount}{\textdiscount}
44 \newcommand*\LWR@HTML@textservicemark}{\textservicemark}
45 \fi
46
47 \LWR@formatted{textdegree}
48 \LWR@formatted{textcelsius}
49 \LWR@formatted{textohm}
50 \LWR@formatted{textmu}
51 \LWR@formatted{textlquill}
52 \LWR@formatted{textrquill}
53 \LWR@formatted{textcircledP}
54 \LWR@formatted{texttwelveudash}
55 \LWR@formatted{textthreequartersemdash}
56 \LWR@formatted{textmho}
57 \LWR@formatted{textnaira}
58 \LWR@formatted{textpeso}
59 \LWR@formatted{textrecipe}
60 \LWR@formatted{textinterrobang}
61 \LWR@formatted{textinterrobangdown}
62 \LWR@formatted{textperthousand}
63 \LWR@formatted{textpertenthousand}
64 \LWR@formatted{textbaht}
65 \LWR@formatted{textdiscount}
66 \LWR@formatted{textservicemark}

```

#### § 567.4 HTML diacritics

For HTML, Unicode diacritical marks are used:

```

67 \newcommand*\LWR@HTML@capitalcedilla}[1]{\HTMLUnicode{0327}}
68 \newcommand*\LWR@HTML@capitalogonek}[1]{\HTMLUnicode{0328}}
69 \newcommand*\LWR@HTML@capitalgrave}[1]{\HTMLUnicode{0300}}
70 \newcommand*\LWR@HTML@capitalacute}[1]{\HTMLUnicode{0301}}
71 \newcommand*\LWR@HTML@capitalcircumflex}[1]{\HTMLUnicode{0302}}
72 \newcommand*\LWR@HTML@capitaltilde}[1]{\HTMLUnicode{0303}}
73 \newcommand*\LWR@HTML@capitaldieresis}[1]{\HTMLUnicode{0308}}
74 \newcommand*\LWR@HTML@capitalhungarumlaut}[1]{\HTMLUnicode{30B}}
75 \newcommand*\LWR@HTML@capitalring}[1]{\HTMLUnicode{30A}}
76 \newcommand*\LWR@HTML@capitalcaron}[1]{\HTMLUnicode{30C}}
77 \newcommand*\LWR@HTML@capitalbreve}[1]{\HTMLUnicode{306}}
78 \newcommand*\LWR@HTML@capitalmacron}[1]{\HTMLUnicode{304}}

```

```
79 \newcommand*\LWR@HTML@capitaldotaccent}[1]{#1\HTMLUnicode{307}}
```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with `xunicode`.

```
80 \providecommand*\LWR@HTML@textcircled}[1]{%
81 \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
82 }
83
84 \LWR@formatted{capitalcedilla}
85 \LWR@formatted{capitalogonek}
86 \LWR@formatted{capitalgrave}
87 \LWR@formatted{capitalacute}
88 \LWR@formatted{capitalcircumflex}
89 \LWR@formatted{capitaltilde}
90 \LWR@formatted{capitaldieresis}
91 \LWR@formatted{capitalhungarumlaut}
92 \LWR@formatted{capitalring}
93 \LWR@formatted{capitalcaron}
94 \LWR@formatted{capitalbreve}
95 \LWR@formatted{capitalmacron}
96 \LWR@formatted{capitaldotaccent}
97
98 \LWR@formatted{textcircled}
```

Nullify `textcomp` macros when generating filenames:

```
99 \FilenameNullify{%
100 \renewcommand*\textdegree}{}%
101 \renewcommand*\textcelsius}{}%
102 \renewcommand*\textohm}{}%
103 \renewcommand*\textmu}{}%
104 \renewcommand*\textlquill}{}%
105 \renewcommand*\textrquill}{}%
106 \renewcommand*\textcircledP}{}%
107 \renewcommand*\texttwelveudash}{}%
108 \renewcommand*\textthreequartersemdash}{}%
109 \renewcommand*\textmho}{}%
110 \renewcommand*\textnaira}{}%
111 \renewcommand*\textpeso}{}%
112 \renewcommand*\textrecipe}{}%
113 \renewcommand*\textinterrobang}{}%
114 \renewcommand*\textinterrobangdown}{}%
115 \renewcommand*\textperthousand}{}%
116 \renewcommand*\textpertenthousand}{}%
117 \renewcommand*\textbaht}{}%
118 \renewcommand*\textdiscount}{}%
119 \renewcommand*\textservicemark}{}%
120 \renewcommand*\textcircled}[1]{#1}%
121 \renewcommand*\capitalcedilla}[1]{#1}%
122 \renewcommand*\capitalogonek}[1]{#1}%
123 \renewcommand*\capitalgrave}[1]{#1}%
124 \renewcommand*\capitalacute}[1]{#1}%
125 \renewcommand*\capitalcircumflex}[1]{#1}%
126 \renewcommand*\capitaltilde}[1]{#1}%
```

```

127 \renewcommand*\capitaldieresis[1]{#1}%
128 \renewcommand*\capitalhungarumlaut[1]{#1}%
129 \renewcommand*\capitalring[1]{#1}%
130 \renewcommand*\capitalcaron[1]{#1}%
131 \renewcommand*\capitalbreve[1]{#1}%
132 \renewcommand*\capitalmacron[1]{#1}%
133 \renewcommand*\capitaldotaccent[1]{#1}%
134 }% FilenameNullify
135
136 }% AtBeginDocument

```

---

File 462 **lwarp-textfit.sty**

§ 568 Package **textfit**

Pkg textfit textfit is emulated.

Text is placed into a <span> of class textfit. Sizes are approximated, and also limited by browser min/max font-size settings.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{textfit}[1994/04/15]

2 \newsavebox{\LWR@textfitbox}
3
4 \newcommand*\LWR@textfitscale[2]{%
5 \setlength{\LWR@templengthone}{#1}%
6 \setlength{\LWR@templengthtwo}{%
7 1em*\ratio{\LWR@templengthone}{\LWR@templengthtwo}%
8 }%
9 \InlineClass[font-size:\LWR@printlength{\LWR@templengthone}]{textfit}{#2}%
10 }
11
12 \newcommand*\scaletowidth[2]{%
13 \sbox{\LWR@textfitbox}{#2}%
14 \settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
15 \LWR@textfitscale{#1}{#2}%
16 }
17
18 \newcommand*\scaletohight[2]{%
19 \sbox{\LWR@textfitbox}{#2}%
20 \settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
21 \LWR@textfitscale{#1}{#2}%
22 }

```

---

File 463 **lwarp-textpos.sty**

§ 569 Package **textpos**

(Emulates or patches code by NORMAN GRAY.)

Pkg `textpos` `textpos` is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{textpos}[2020/09/26]

```

2 \NewDocumentEnvironment{textblock}{m o r()}{}{}
3 \NewDocumentEnvironment{textblock*}{m o r()}{}{}
4 \newcommand*\TPGrid[3]{}
5 \def\TPShowGrid{\@ifstar{\@TPShowGrid}{\@TPShowGrid}}
6 \def\@TPShowGrid#1#2{}
7 \NewDocumentCommand{\TPMargin}{s o}{}
8 \newcommand*\textblockcolour[1]{}
9 \newcommand*\textblockrulecolour[1]{}
10 \newcommand*\textblockcolor[1]{}
11 \newcommand*\textblockrulecolor[1]{}
12 \newcommand*\tekstblokkulur[1]{}
13 \newcommand*\tekstblokrulekulur[1]{}
14 \newlength{\TPHorizModule}
15 \newlength{\TPVertModule}
16 \newlength{\TPboxrulesize}
17 \newcommand{\textblocklabel}[1]{}
18 \newcommand*\showtextsize{}
19 \newcommand{\textblockorigin}[2]{}
20 \newcommand*\TPoptions[1]{}
21 \newcommand*\TPreferencePosition[1]{}

```

---

File 464 **lwarp-theorem.sty**

§ 570 Package **theorem**

*(Emulates or patches code by FRANK MITTELBACH.)*

Pkg `theorem` `theorem` is patched for use by `lwarp`.

---

Table 19: Theorem package — css styling of theorems and proofs

**Theorem:** `<div>` of class `theorembody<theoremstyle>`

**Theorem Header:** `<span>` of class `theoremheader`

where `<theoremstyle>` is `plain`, `break`, etc.

---

**for HTML output:** 1 \LWR@ProvidesPackagePass{theorem}[2014/10/28]

§ 570.1 **Remembering the theorem style**

Storage for the style being used for new theorems:

```
2 \newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
3 \gdef\theoremstyle#1{%
4 \ifundefined{th@#1}{\@warning
5 {Unknown theoremstyle ‘#1’. Using ‘plain’}%
6 \theorem@style{plain}%
7 \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
8 }%
9 {%
10 \theorem@style{#1}%
11 \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
12 }%
13 \begingroup
14 \csname th@the\theorem@style \endcsname
15 \endgroup}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
16 \gdef\xnthm#1#2[#3]{%
17 \expandafter\ifdefinable\csname #1\endcsname
18 {%
19 \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
20 \definecounter{#1}\newctr{#1}[#3]%
21 \expandafter\xdef\csname the#1\endcsname
22 {\expandafter \noexpand \csname the#3\endcsname
23 \@thmcountersep \@thmcounter{#1}}}%
24 \def\@tempa{\global\@namedef{#1}}%
25 \expandafter \@tempa \expandafter{%
26 \csname th@the \theorem@style
27 \expandafter \endcsname \the \theorem@bodyfont
28 \@thm{#1}{#2}}%
29 \global \expandafter \let \csname end#1\endcsname \@endtheorem
30 \AtBeginEnvironment{#1}{\edef\LWR@thmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
31 }}
32
33 \gdef\ynthm#1#2{%
34 \expandafter\ifdefinable\csname #1\endcsname
35 {
36 \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
37 \definecounter{#1}%
38 \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
39 \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
40 \expandafter{\csname th@the \theorem@style \expandafter
41 \endcsname \the\theorem@bodyfont \@thm{#1}{#2}}%
42 \global \expandafter \let \csname end#1\endcsname \@endtheorem
43 \AtBeginEnvironment{#1}{\edef\LWR@thmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
44 }}
45
```

```

46 \gdef\@thm#1[#2]#3{%
47 \expandafter\ifx\csname c@#2\endcsname\relax
48 \@nocounterr{#2}%
49 \else
50 \expandafter\ifdefinable\csname #1\endcsname
51 {
52 \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
53 \expandafter \xdef \csname the#1\endcsname
54 {\expandafter \noexpand \csname the#2\endcsname}%
55 \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
56 \expandafter{\csname th@the \theoremstyle \expandafter
57 \endcsname \the\theorem@bodyfont \@thm{#2}{#3}}%
58 \global \expandafter \let \csname end#1\endcsname \@endtheorem
59 \AtBeginEnvironment{#1}{\edef\LWR@thmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
60 }%
61 \fi}

```

## § 570.2 **css patches**

The following are patched for css.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a BlockClass environment of class theorembody<style>.

Each header is encased in an \InlineClass of class theoremheader.

```

62 \gdef\th@plain{%
63 \def\@begintheorem##1##2{%
64 \item[
65 \InlineClass{theoremheader}{##1\ ##2}
66]
67 }%
68 \def\@opargbegintheorem##1##2##3{%
69 \item[
70 \InlineClass{theoremheader}{##1\ ##2\ (##3)}
71]
72 }
73 }
74
75 \gdef\th@break{%
76 \def\@begintheorem##1##2{%
77 \item[
78 \InlineClass{theoremheader}{##1\ ##2}\newline%
79]
80 }%
81 \def\@opargbegintheorem##1##2##3{%
82 \item[
83 \InlineClass{theoremheader}{##1\ ##2\ (##3)}\newline
84]
85 }
86 }
87
88 \gdef\th@marginbreak{%

```

```

89 \def\@begintheorem##1##2{
90 \item[
91 \InlineClass{theoremheader}{##2 \quad ##1}\newline
92]
93 }%
94 \def\@opargbegintheorem##1##2##3{%
95 \item[
96 \InlineClass{theoremheader}{##2 \quad ##1\ %
97 (##3)}\newline
98]
99 }
100 }
101
102 \gdef\th@changebreak{%
103 \def\@begintheorem##1##2{
104 \item[
105 \InlineClass{theoremheader}{##2\ ##1}\newline
106]
107 }%
108 \def\@opargbegintheorem##1##2##3{%
109 \item[
110 \InlineClass{theoremheader}{ ##2\ ##1\ %
111 (##3)}\newline
112]
113 }
114 }
115
116 \gdef\th@change{%
117 \def\@begintheorem##1##2{
118 \item[
119 \InlineClass{theoremheader}{##2\ ##1}
120]
121 }%
122 \def\@opargbegintheorem##1##2##3{%
123 \item[
124 \InlineClass{theoremheader}{##2\ ##1\ (##3)}
125]
126 }
127 }
128
129 \gdef\th@margin{%
130 \def\@begintheorem##1##2{
131 \item[
132 \InlineClass{theoremheader}{##2 \quad ##1}
133]
134 }%
135 \def\@opargbegintheorem##1##2##3{%
136 \item[
137 \InlineClass{theoremheader}{##2 \quad ##1\ (##3)}
138]
139 }
140 }

```

Patched for css:

```

141 \gdef\@thm#1#2{\refstepcounter{#1}%
142 \LWR@forcenewpage% lwarp
143 \BlockClass{theorembody\LWR@thisthmstyle}% lwarp
144 \trivlist
145 \@topsep \theorempreskipamount % used by first \item
146 \@topsepadd \theorempostskipamount % used by \@endparenv
147 \@ifnextchar [%
148 {\@ythm{#1}{#2}}%
149 {\@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}}
150
151 \gdef\@endtheorem{%
152 \endtrivlist
153 \endBlockClass
154 }

```

---

File 465 **lwarp-thinsp.sty**

§ 571 Package **thinsp**

Pkg thinsp thinsp is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{thinsp}[2016/10/02]

```

2 \AtBeginDocument{
3 \let\thinthinspace\relax% defined by some packages
4 \newcommand*{\thinthinspace}{\thinspace}
5 }
6
7 \newcommand*{\stretchthinspace}{\thinspace}
8 \newcommand*{\stretchthinthinspace}{\thinthinspace}
9 \newcommand*{\stretchnegthinspace}{\negthinspace}

```

---

File 466 **lwarp-thm-listof.sty**

§ 572 Package **thm-listof**

*(Emulates or patches code by ULRICH M. SCHWARZ, YUKAI CHOU.)*

Pkg thm-listof thm-listof is part of thmtools, and is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{thm-listof}[2019/12/22]

For font control, see the generated HTML and use CSS per amsthm or ntheorem.

Other thm-\* package may be loaded by thm-listof.

```

2 \@ifpackagelater{thm-listof}{2020/08/01}{% v0.72
3 \def\thmtlo@newentry{%
4 \csdef{l@thmt@envname}##1##2{\hypertocfloat{1}{figure}{lof}{##1}{##2}}%

```

```

5 }
6 }{% earlier than v0.72
7 \xpatchcmd{\listoftheorems}
8 {%
9 \@xa\protected@edef\csname l@thmt@envname\endcsname{%
10 \@nx\@dottedtocline{1}{1.5em}{\@nx\thmt@listnumwidth}%
11 }%
12 }
13 {%
14 \csdef{l@thmt@envname}##1##2{\hypertocfloat{1}{figure}{lof}{##1}{##2}}%
15 }
16 {}
17 {\LWR@patcherror{thm-listof}{listoftheorems}}
18
19 \xpatchcmd{thmt@mklistcmd}
20 {%
21 \@xa\protected@edef\csname l@thmt@envname\endcsname{%
22 \@nx\@dottedtocline{1}{1.5em}{\@nx\thmt@listnumwidth}%
23 }%
24 }
25 {%
26 \csdef{l@thmt@envname}##1##2{\hypertocfloat{1}{figure}{lof}{##1}{##2}}%
27 }
28 {}
29 {\LWR@patcherror{thm-listof}{thmt@mklistcmd}}
30 }

```

---

File 467 **lwarp-thm-restate.sty**

§ 573 Package **thm-restate**

(Emulates or patches code by ULRICH M. SCHWARZ.)

Pkg thm-restate **thm-restate** is part of thmtools, and is patched for use by lwarp.

**for HTML output:** 1 \LWR@ProvidesPackagePass{thm-restate}[2020/08/01]

```

2 \xpatchcmd{thmt@restatable}
3 {\@ifstar}
4 {\edef\LWR@thisthmstyle{#2}\@ifstar}
5 {}
6 {\LWR@patcherror{thm-restate}{thmt@restatable}}

```

---

File 468 **lwarp-thmbox.sty**

§ 574 Package **thmbox**

(Emulates or patches code by EMMANUEL BEFFARA.)

Pkg thmbox **thmbox** is emulated for use by lwarp.

```

for HTML output: 1 \LWR@ProvidesPackagePass{thmbox}[2005/04/24]

2 \renewenvironment{thmbox}[2][]%
3 {%
4 \begin{BlockClass}{thmbox}
5 \begin{BlockClass}{thmboxtitle}
6 #2
7 \end{BlockClass}
8 }
9 {\end{BlockClass}}
10
11 \renewenvironment{proof}[1][]
12 {%
13 \begin{BlockClass}{thmboxproof}%
14 \InlineClass{thmboxproofname}{\proofname\ #1\unskip\,:}
15 }
16 {%
17 \quad\HTMLUnicode{220E}% end of proof symbol
18 \end{BlockClass}
19 }
20
21 \renewenvironment{example}[1][\examplename]%
22 {%
23 \begin{BlockClass}{thmboxexample}%
24 \InlineClass{thmboxexamplename}{#1\,:}
25 }
26 {\end{BlockClass}}
27
28 \renewenvironment{leftbar}[1][]%
29 {\begin{BlockClass}{thmboxleftbar}}
30 {\end{BlockClass}}

```

---

File 469 **lwarp-thmtools.sty**

§ 575 Package **thmtools**

(Emulates or patches code by ULRICH M. SCHWARZ.)

Pkg thmtools thmtools is patched for use by lwarp.

Also see thm-listof and thm-restate.

```

for HTML output: 1 \LWR@ProvidesPackagePass{thmtools}[2020/08/01]

```

The following patches either thm-amsthm or thm-ntheorem.

```

2 \def\thmt@headstyle@margin{%
3 \InlineClass{amsthmnumbertheorem}{\NUMBER}
4 \
5 \InlineClass{amsthmnametheorem}{\NAME}
6 \InlineClass{amsthmnotetheorem}{\NOTE}
7 }

```

---

```
8
9 \let\thmt@headstyle@swapnumber\thmt@headstyle@margin
```

---

File 470 **lwarp-threadcol.sty**

§ 576 Package **threadcol**

Pkg threadcol threadcol is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{threadcol}[2013/01/06]
2 \newcommand{\setthreadname}[1]{}
```

---

File 471 **lwarp-threeparttable.sty**

§ 577 Package **threeparttable**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg threeparttable threeparttable is emulated.

Table note are contained inside a CSS <div> of class tnotes. If enumitem is used, the note item labels are also individually highlighted with an additional CSS <span> of class tnoteitemheader, otherwise they are plain text.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{threeparttable}[2003/06/13]
```

Env threeparttable [*<alignment>*]

```
2 \newenvironment*{threeparttable}[1][b]
3 {\def\@capttype{table}}
4 {}
```

Env tablenotes [*<options>*]

```
5 \newenvironment*{tablenotes}[1][[]
6 {%
7 \LWR@forcenewpage
8 \BlockClass{tnotes}%
9 \description%
10 }
11 {%
12 \enddescription%
13 \endBlockClass%
14 }
```

\tnote {*<text>*}

```
15 \newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}
```

```

Env measuredfigure [(alignment)]

16 \newenvironment*{measuredfigure}[1][t]
17 {\def\@capttype{figure}}
18 {}

```

File 472 **lwarp-threeparttablex.sty**

§ 578 Package **threeparttablex**

Pkg threeparttablex threeparttablex is patched for use by lwarp.

threeparttablex is used with longtable and booktabs as follows:

```

\begin{longtable}{ [column specifiers] }
[. . .] \endfirsthead % or \endhead, for print and HTML
\warpprintonly{ % not used in HTML
[. . .] \endhead % or \endfirsthead
[. . .] \endfoot
\bottomrule \insertTableNotes \endlastfoot
}
. . . table contents . . .
\warpHTMLonly{ % HTML last footer
\bottomrule
\UseMinipageWidths % optional
\insertTableNotes
\endlastfoot
}
\end{longtable}

```

**table width** The table notes are created using a `\multicolumn`. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, `lwarp` guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use `\UseMinipageWidths` before `\insertTableNotes`. The width is then specified, and in many cases the result is an improvement in overall table layout.

**for HTML output:** 1 \LWR@ProvidesPackagePass{threeparttablex}[2013/07/23]

The width is guessed depending on the number of columns, then limited to a min/max.

```

2 \renewcommand\insertTableNotes{%
3 \setlength{\LWR@templengthone}{.375in*\value{LWR@tabletotalLaTeXcols}}%
4 \setlength{\LWR@templengthone}{\minof{\textwidth}{\LWR@templengthone}}%
5 \setlength{\LWR@templengthone}{\maxof{2.5in}{\LWR@templengthone}}%
6 \multicolumn{\value{LWR@tabletotalLaTeXcols}}{c}{%
7 \parbox{\LWR@templengthone}{%
8 \begin{tablenotes}[\TPTL@optarg]%
9 \TPTL@font%
10 \TPTL@body%

```

---

```

11 \end{tablenotes}%
12 }%
13 }%
14 }
15
16 \renewcommand\TPTL@tnotex[2]{\tnote{\nameref{#2}}}
```

---

File 473 **lwarp-thumb.sty**

§ 579 Package **thumb**

Pkg thumb thumb is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{thumb}[1997/12/24]

```

2 \newcommand*\Overviewpage{}
3 \newlength{\thumbheight}
4 \newlength{\thumbwidth}
```

---

File 474 **lwarp-thumbs.sty**

§ 580 Package **thumbs**

Pkg thumbs thumbs is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{thumbs}[2014/03/09]

```

2 \newcommand{\addthumb}[4]{}
3 \newcommand{\addtitlethumb}[5]{}
4 \newcommand{\stophthumb}{}
5 \newcommand{\continuethumb}{}
6 \newcommand{\thumbsoverview}[1]{}
7 \newcommand{\thumbsoverviewback}[1]{}
8 \newcommand{\thumbsoverviewverso}[1]{}
9 \newcommand{\thumbsoverviewdouble}[1]{}
10 \newcommand{\thumbnewcolumn}{}
11 \newcommand{\addthumbsoverviewtocontents}[2]{}
12 \newcommand{\thumbsnophantom}{}

```

---

File 475 **lwarp-tikz.sty**

§ 581 Package **tikz**

*(Emulates or patches code by TILL TANTAU.)*

Pkg tikz tikz is supported.

- ⚠ **displaymath and matrices** If using display math with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the `tikz` expression must be replaced with `\&`.

Accept all options for `lwarp-tikz`:

```
1 \LWR@ProvidesPackagePass{tikz}[2015/08/07]
```

- catcodes** `lwarp` changes the catcode of `$` for its own use. The `Tikz` `babel` library temporarily changes catcodes back to normal for `Tikz`'s use. `tikz` v3.0.0 introduced the `babel` library which handles catcode changes. For older versions, `lwarp` must change `$`'s catcode itself.

Also see:

<https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded>

```
2 \newbool{LWR@tikzbabel}
3
4 \@ifpackagelater{tikz}{2013/12/20}% Test for Tikz version v3.0.0
5 {\usetikzlibrary{babel}\booltrue{LWR@tikzbabel}}
6 {\boolfalse{LWR@tikzbabel}}
```

- Env `pgfpicture` The `\pgfpicture` environment is enclosed inside a `\lateximage`. Enclose the low-level `\pgfpicture` in a `lateximage`. This is also used by the higher-level `\tikz` and `tikzpicture`.

```
7 \preto\pgfpicture{%
8 \begin{lateximage}[-tikz--\PackageDiagramAltText]%
9 \ifbool{LWR@tikzbabel}% Test for Tikz version v3.0.0
10 {}%
11 {\catcode'\$=3}% dollar sign is math shift
12 }
13
14 \appto\endpgfpicture{\end{lateximage}}
```

`Tikz` is placed inside an `svg` image, so use the original meanings of the following:

```
15 \LetLtxMacro\pgfutil@minipage\LWR@print@minipage
16 \let\pgfutil@endminipage\endLWR@print@minipage
17
18 \let\pgfutil@raggedleft\LWR@print@raggedleft
19 \let\pgfutil@raggedright\LWR@print@raggedright

20 \def\pgfutil@font@tiny{\LWR@print@tiny}
21 \def\pgfutil@font@scriptsize{\LWR@print@scriptsize}
22 \def\pgfutil@font@footnotesize{\LWR@print@footnotesize}
23 \def\pgfutil@font@small{\LWR@print@small}
24 \def\pgfutil@font@normalsize{\LWR@print@normalsize}
```

```

25 \def\pgfutil@font@large{\LWR@print@large}
26 \def\pgfutil@font@Large{\LWR@print@Large}
27 \def\pgfutil@font@huge{\LWR@print@huge}
28 \def\pgfutil@font@Huge{\LWR@print@Huge}
29
30 \def\pgfutil@font@itshape{\LWR@print@itshape}
31 \def\pgfutil@font@bfseries{\LWR@print@bfseries}
32
33 \def\pgfutil@font@normalfont{\LWR@print@normalfont}

```

---

File 476 **lwarp-titles.sty**

§ 582 Package **titles**

*(Emulates or patches code by JAVIER BEZOS.)*

Pkg titles titles is loaded and used by lwarp during HTML output. All user options and macros are ignored and disabled.

Discard all options for lwarp-titles:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{titles}[2016/03/15]

\pagestyle and \thispagestyle are already disabled in the lwarp code.

\newpagestyle {<name> [<style>] [<commands>]  
2 \NewDocumentCommand{\newpagestyle}{m o m}{}

\renewpagestyle {<name> [<style>] [<commands>]  
3 \NewDocumentCommand{\renewpagestyle}{m o m}{}

\sethead [<el>] [<ec>] [<er>] {<ol>} {<oc>} {<or>}  
4 \NewDocumentCommand{\sethead}{o o o m m m}{}

\setfoot [<el>] [<ec>] [<er>] {<ol>} {<oc>} {<or>}  
5 \NewDocumentCommand{\setfoot}{o o o m m m}{}

\settitlemarks \* {<names>}  
6 \NewDocumentCommand{\settitlemarks}{s m}{}

\headrule  
7 \newcommand\*{\headrule}{}

\footrule

---

|                               |    |                                                         |
|-------------------------------|----|---------------------------------------------------------|
|                               | 8  | <code>\newcommand*{\footrule}{}</code>                  |
| <code>\setheadrule</code>     |    | <code>{&lt;length&gt;}</code>                           |
|                               | 9  | <code>\newcommand*{\setheadrule}[1]{}</code>            |
| <code>\setfootrule</code>     |    | <code>{&lt;length&gt;}</code>                           |
|                               | 10 | <code>\newcommand*{\setfootrule}[1]{}</code>            |
| <code>\makeheadrule</code>    |    |                                                         |
|                               | 11 | <code>\newcommand*{\makeheadrule}{}</code>              |
| <code>\makefootrule</code>    |    |                                                         |
|                               | 12 | <code>\newcommand*{\makefootrule}{}</code>              |
| <code>\setmarkboth</code>     |    | <code>{&lt;code&gt;}</code>                             |
|                               | 13 | <code>\newcommand{\setmarkboth}[1]{}</code>             |
| <code>\widenhead</code>       |    |                                                         |
|                               | 14 | <code>\NewDocumentCommand{\widenhead}{s o m m}{}</code> |
| <code>\bottitlemarks</code>   |    |                                                         |
|                               | 15 | <code>\newcommand*{\bottitlemarks}{}</code>             |
| <code>\toptitlemarks</code>   |    |                                                         |
|                               | 16 | <code>\newcommand*{\toptitlemarks}{}</code>             |
| <code>\firsttitlemarks</code> |    |                                                         |
|                               | 17 | <code>\newcommand*{\firsttitlemarks}{}</code>           |
| <code>\nexttitlemarks</code>  |    |                                                         |
|                               | 18 | <code>\newcommand*{\nexttoptitlemarks}{}</code>         |
| <code>\outertitlemarks</code> |    |                                                         |
|                               | 19 | <code>\newcommand*{\outertitlemarks}{}</code>           |
| <code>\innertitlemarks</code> |    |                                                         |
|                               | 20 | <code>\newcommand*{\innertitlemarks}{}</code>           |
| <code>\newtitlemark</code>    |    | <code>* {&lt;name&gt;}</code>                           |

|                               |    |                                                                                                                                                                                     |
|-------------------------------|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                               | 21 | <code>\NewDocumentCommand{\newtitlemark}{s m}{}</code>                                                                                                                              |
| <code>\pretitlemark</code>    | *  | <code>{\langle section \rangle}{\langle text \rangle}</code>                                                                                                                        |
|                               | 22 | <code>\NewDocumentCommand{\pretitlemark}{s m m}{}</code>                                                                                                                            |
| <code>\ifsamemark</code>      |    | <code>{\langle group \rangle}{\langle command \rangle}{\langle true \rangle}{\langle false \rangle}</code>                                                                          |
|                               | 23 | <code>\newcommand{\ifsamemark}[4]{}</code>                                                                                                                                          |
| <code>\setfloathead</code>    | *  | <code>[{\langle . \rangle}][{\langle . \rangle}][{\langle . \rangle}]{\langle . \rangle}{\langle . \rangle}{\langle . \rangle}{\langle extra \rangle}[\langle which \rangle]</code> |
|                               | 24 | <code>\NewDocumentCommand{\setfloathead}{s o o o m m m m}{}</code>                                                                                                                  |
| <code>\setfloatfoot</code>    | *  | <code>[{\langle . \rangle}][{\langle . \rangle}][{\langle . \rangle}]{\langle . \rangle}{\langle . \rangle}{\langle . \rangle}{\langle extra \rangle}[\langle which \rangle]</code> |
|                               | 25 | <code>\NewDocumentCommand{\setfloatfoot}{s o o o m m m m}{}</code>                                                                                                                  |
| <code>\nextfloathead</code>   | *  | <code>[{\langle . \rangle}][{\langle . \rangle}][{\langle . \rangle}]{\langle . \rangle}{\langle . \rangle}{\langle . \rangle}{\langle extra \rangle}[\langle which \rangle]</code> |
|                               | 26 | <code>\NewDocumentCommand{\nextfloathead}{s o o o m m m m}{}</code>                                                                                                                 |
| <code>\nextfloatfoot</code>   | *  | <code>[{\langle . \rangle}][{\langle . \rangle}][{\langle . \rangle}]{\langle . \rangle}{\langle . \rangle}{\langle . \rangle}{\langle extra \rangle}[\langle which \rangle]</code> |
|                               | 27 | <code>\NewDocumentCommand{\nextfloatfoot}{s o o o m m m m}{}</code>                                                                                                                 |
| <code>\newmarkset</code>      |    | <code>{\langle markset \rangle}</code>                                                                                                                                              |
|                               | 28 | <code>\newcommand{\newmarkset}[1]{}</code>                                                                                                                                          |
| <code>\newextramark</code>    | *  | <code>{\langle markset \rangle}{\langle macro-name \rangle}</code>                                                                                                                  |
|                               | 29 | <code>\NewDocumentCommand{\newextramarkset}{s m m}{}</code>                                                                                                                         |
| <code>\botextramarks</code>   |    | <code>{\langle markset \rangle}</code>                                                                                                                                              |
|                               | 30 | <code>\newcommand{\botextramarks}[1]{}</code>                                                                                                                                       |
| <code>\topextramarks</code>   |    | <code>{\langle markset \rangle}</code>                                                                                                                                              |
|                               | 31 | <code>\newcommand{\topextramarks}[1]{}</code>                                                                                                                                       |
| <code>\firstextramarks</code> |    | <code>{\langle markset \rangle}</code>                                                                                                                                              |
|                               | 32 | <code>\newcommand{\firstextramarks}[1]{}</code>                                                                                                                                     |
| <code>\nextextramarks</code>  |    | <code>{\langle markset \rangle}</code>                                                                                                                                              |
|                               | 33 | <code>\newcommand{\nexttopextramarks}[1]{}</code>                                                                                                                                   |
| <code>\outerextramarks</code> |    | <code>{\langle markset \rangle}</code>                                                                                                                                              |

---

```
34 \newcommand{\outerextramarks}[1]{}
```

```
\innerextramarks {<markset>}
```

```
35 \newcommand{\innerextramarks}[1]{}
```

---

File 477 **lwarp-titleref.sty**

§ 583 Package **titleref**

Pkg titleref titleref is emulated.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{titleref}[2001/04/05]
2
3 \LetLtxMacro\titleref\nameref
4
5 \providecounter{LWR@currenttitle}
6
7 \newcommand*{\currenttitle}{%
8 \addtocounter{LWR@currenttitle}{1}%
9 \label{currenttitle\arabic{LWR@currenttitle}}%
10 \nameref{currenttitle\arabic{LWR@currenttitle}}%
11 }
12
13 \newcommand*{\theTitleReference}[2]{}
```

---

File 478 **lwarp-titlesec.sty**

§ 584 Package **titlesec**

*(Emulates or patches code by JAVIER BEZOS.)*

Pkg titlesec titlesec is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titlesec:

**for HTML output:**

```
1 \PackageInfo{lwarp}{Using the lwarp version of package 'titlesec'.}%
2 \ProvidesPackage{lwarp-titlesec}[2016/03/21]
3
4 \newbool{LWR@loadtitleps}
5 \boolfalse{LWR@loadtitleps}
6
7 \DeclareOption{pagestyles}{
8 \booltrue{LWR@loadtitleps}
9 }
10
11 \DeclareOption*{}
12
13 \ProcessOptions\relax
14
```

```

15 \ifbool{LWR@loadtitles}{
16 \RequirePackage{lwarp-titles}
17 }{}

```

`\titlelabel`     $\{\langle label-format \rangle\}$

```

18 \newcommand*\titlelabel[1]{}

```

`\titleformat*`    $\{\langle command \rangle\} \{\langle format \rangle\}$

`\titleformat`     $\{\langle command \rangle\} [\langle shape \rangle] \{\langle format \rangle\} \{\langle label \rangle\} \{\langle sep \rangle\} \{\langle before \rangle\} [\langle after \rangle]$

```

19 \newcommand\titleformat{%
20 \@ifstar{\ttl@format@s}%
21 {\ttl@format@i}}
22 \newcommand{\ttl@format@s}[1]{}
23 \NewDocumentCommand{\ttl@format@i}{m o m m m o}{}

```

`\chaptertitlename`

```

24 \@ifundefined{@chapapp}{\let\@chapapp\chaptername}{}
25 \newcommand\chaptertitlename{\@chapapp}

```

`\titlespacing`    $* \{\langle command \rangle\} \{\langle left \rangle\} \{\langle before \rangle\} \{\langle after \rangle\} [\langle right \rangle]$

```

26 \NewDocumentCommand{\titlespacing}{s m m m m o}{}

```

`\filright`

```

27 \newcommand*\filright{}

```

`\filcenter`

```

28 \newcommand*\filcenter{}

```

`\filleft`

```

29 \newcommand*\filleft{}

```

`\fillast`

```

30 \newcommand*\fillast{}

```

`\filinner`

```

31 \newcommand*\filinner{}

```

`\filouter`

```

32 \newcommand*\filouter{}

```

```

\wordsep
33 \newcommand\wordsep{\fontdimen\tw@\font \@plus
34 \fontdimen\thr@\font \@minus \fontdimen4\font}

\titleline * [⟨align⟩] {⟨material⟩}
35 \NewDocumentCommand{\titleline}{s o m}{}

\titlerule [⟨height⟩]
36 \providecommand*\titlerule{\@ifstar{\ttl@row}{\ttl@rule}}
37 \newcommand*\ttl@rule[1]{}{}
38 \newcommand*\ttl@row[2]{}{}

\iftitlemeasuring {⟨true⟩} {⟨false⟩}
39 \newcommand{\iftitlemeasuring}[2]{#2}

\assignpagestyle {⟨command⟩} {⟨pagestyle⟩}
40 \newcommand{\assignpagestyle}[2]{#2}

\titleclass {⟨name⟩} [⟨startlevel⟩] {⟨class⟩} [⟨cmd⟩]
41 \NewDocumentCommand{\titleclass}{m o m o}{}

```

---

File 479 **lwarp-titletoc.sty**

§ 585 Package **titletoc**

(Emulates or patches code by JAVIER BEZOS.)

Pkg titletoc titletoc is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titletoc:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{titletoc}[2011/12/15]

```

\dottedcontents {⟨section⟩} [⟨left⟩] {⟨above⟩} {⟨label⟩} {⟨leader⟩}
2 \NewDocumentCommand{\dottedcontents}{m o m m m}{}

```

```

\titlecontents * {⟨section⟩} [⟨left⟩] {⟨above⟩} {⟨numbered⟩} {⟨numberless⟩} {⟨filler⟩} [⟨below or
begin⟩] [⟨separator⟩] [⟨end⟩]
3 \newcommand{\titlecontents}{\@ifstar{\ttl@tcstar}{\ttl@tcnostar}}
4 \NewDocumentCommand{\ttl@tcstar}{m o m m m m o o o}{}
5 \NewDocumentCommand{\ttl@tcnostar}{m o m m m m o}{}

```

```

\contentsmargin [⟨correction⟩] {⟨right⟩}

```

6 \newcommand{\contentsmargin}[2][{}]

\thecontentslabel

7 \newcommand\*{\thecontentslabel}{thecontentslabel}

\thecontentspage

8 \newcommand\*{\thecontentspage}{thecontentspage}

\contentslabel [*format*] {*space*}

9 \newcommand{\contentslabel}[2][{\thecontentslabel}]

\contentspage [*format*]

10 \newcommand{\contentspage}[1][{\thecontentspage}]

\contentspush {*text*}

11 \newcommand{\contentspush}[1]{}

\contentsuse {*name*} {*text*}

12 \newcommand{\contentsuse}[2]{}

\startcontents [*name*]

13 \newcommand\*{\startcontents}[1][{}]

\stopcontents [*name*]

14 \newcommand\*{\stopcontents}[1][{}]

\resumecontents [*name*]

15 \newcommand\*{\resumecontents}[1][{}]

\printcontents [*name*] {*prefix*} {*start*} {*code*}

16 \newcommand{\printcontents}[4][{}]

\startlist [*name*] {*list*}

17 \newcommand{\startlist}[2][{}]

\stoplist [*name*] {*list*}

18 \newcommand{\stoplist}[2][{}]

\resumelist [*name*] {*list*}

```
19 \newcommand{\resumelist}[2][{}]
```

```
\printlist [<name>] {<list>} {<prefix>} {<code>}
```

```
20 \newcommand{\printlist}[4][{}]
```

File 480 **lwarp-titling.sty**

§ 586 Package **titling**

*(Emulates or patches code by PETER WILSON.)*

Pkg titling

**package support** lwarp supports the native L<sup>A</sup>T<sub>E</sub>X titling commands, and also supports the packages  
 **load order** authblk and titling. If both are used, authblk should be loaded before titling.

**\published and \subtitle** If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 67.8.

The various titling footnote restyling commands have no effect.

Pass all options to lwarp-titling:

**for HTML output:** 1 \LWR@ProvidesPackagePass{titling}[2009/09/04]

**\@bsmtitleempty** Patch \@bsmtitleempty:

```
2 \let\LWR@orig@bsmtitleempty\@bsmtitleempty
3 \renewcommand*{\@bsmtitleempty}{%
4 \LWR@orig@bsmtitleempty%
5 }
```

**\keepthetitle** Patch \keepthetitle:

```
6 \let\LWR@origkeepthetitle\keepthetitle
7 \renewcommand*{\keepthetitle}{%
8 \LWR@orig@keepthetitle%
9 }
```

**\killtitle** Patch \killtitle:

```
10 \let\LWR@origkilltitle\killtitle
11 \renewcommand*{\killtitle}{%
12 \LWR@orig@killtitle%
13 }
```

Env titlingpage

```
14 \renewenvironment*{titlingpage}
15 {%
```

Start an HTML titlepage div:

```
16 \LWR@printpendingfootnotes
17 \begin{titlepage}
```

Prepare for a custom version of \maketitle inside the titlingpage:

```
18 \LWR@maketitlesetup
19 \let\maketitle\LWR@titlingmaketitle
20 }
21 {
```

At the end of the environment, end the HTML titlepage div:

```
22 \end{titlepage}
23 }
```

Patch the pre/post title/author/date to add HTML tags, then initialize:

```
24 \AtBeginDocument{
25 \pretitle{}
26 \posttitle{}
27
28 \preauthor{}
29 \postauthor{}
30
31 \predate{}
32 \postdate{}
33 }
```

\LWR@maketitlesetup Patches \thanks macros.

```
34 \renewcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
35 \def\@makefnmark{\@thefnmark}%
 \thefootnote ⇒ \nameuse{arabic}{footnote}, or
 \thefootnote ⇒ \nameuse{fnsymbol}{footnote}
```

Redefine the footnote text:

```
36 \long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
37 \makethanksmark~%
 \makethanksmark ⇒ \thanksfootmark ⇒ \tmark ⇒
 \@thefnmark ⇒ \itshape a (or similar)
```

Print the text:

```
38 ##1%
39]% \@makefntext
40 }
```

`\thanksfootmark`

```
41 \renewcommand{\thanksfootmark}{%
42 % \hb@xt@\thanksmarkwidth{\hfil\normalfont%
43 \thanksscript{%
44 \thanksfootpre \tamark \thanksfootpost%
45 }%
46 % }%
47 }
```

`\maketitle` HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
48 \renewcommand*{\maketitle}{%
```

An HTML titlepage `<div>` is used for all classes.

```
49 \begin{titlepage}
```

Select which kind of footnote marks to use:

```
50 \@bsmarkseries
```

Set up special patches:

```
51 \LWR@maketitlesetup
```

Typeset the title, etc:

```
52 \@maketitle
```

Immediately generate any `\thanks` footnotes:

```
53 \LWR@stoppars\@thanks\LWR@startpars
```

Close the HTML titlepage div:

```
54 \end{titlepage}
```

Reset the footnote counter:

```
55 \@bscontmark
56 }
```

`\@maketitle` Typesets the title, etc. Patched for HTML.

```

57 \DeclareDocumentCommand{\@maketitle}{}{%
58 \maketitlehooka
59 {
60 \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
61 \@bspretitle \@title \@bsposttitle%
62 \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
63 }
64 \maketitlehookb
65 {
66 \begin{BlockClass}{author}
67 \renewcommand{\and}{%
68 \end{BlockClass}%
69 \begin{BlockClass}{oneauthor}%
70 }
71 \begin{BlockClass}{oneauthor}%
72 \@bspreauthor \@author \@bspostauthor%
73 \end{BlockClass}%
74 \end{BlockClass}%
75 }
76 \maketitlehookc
77 {
78 \begin{BlockClass}{titledate}%
79 \@bspredate \@date \@bspostdate%
80 \end{BlockClass}%
81 }
82 \maketitlehookd
83 }

```

`\LWR@titlingmaketitle` `\maketitle` for use inside an HTML titlingpage environment.

```
84 \renewcommand*{\LWR@titlingmaketitle}{}%
```

Keep pending footnotes out of the title block:

```
85 \LWR@stoppars\@thanks\LWR@startpars
```

Select which kind of footnote marks to use:

```
86 \@bsmarkseries
```

Set up special patches:

```
87 \LWR@maketitlesetup
```

Typeset the title, etc:

```
88 \@maketitle
```

Immediately generate any `\thanks` footnotes:

```
89 \LWR@stoppars\@thanks\LWR@startpars
```

Reset the footnote counter:

```
90 \@bscontmark
91 }
```

`\thanksmarkseries`  $\{(\textit{series})\}$

Sets the type of footnote marks used by `\thanks`, where type is ‘arabic’, ‘roman’, ‘fn-symbol’, etc.

```
92 \renewcommand{\thanksmarkseries}[1]{%
93 \def\@bsmarkseries{\renewcommand{\thefootnote}{\@nameuse{#1}{footnote}}}%
94 }
```

Set default titlepage thanks footnote marks. See section 67.7.

```
95 \@ifclassloaded{memoir}{
96 \thanksmarkseries{arabic}
97 }{% not memoir
98 \if@titlepage
99 \thanksmarkseries{arabic}
100 \else
101 \thanksmarkseries{fnsymbol}
102 \fi
103 }% not memoir
```

---

File 481 **lwarp-tocbasic.sty**

§ 587 Package **tocbasic**

*(Emulates or patches code by MARKUS KOHM.)*

Pkg `tocbasic` `tocbasic` is nullified for `lwarp`.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. `\DeclareDocumentCommand` is used to overwrite the koma-script definitions.

**for HTML output:** 1 `\LWR@ProvidesPackagePass{tocbasic}[2018/12/30]`

```
2 \DeclareDocumentCommand{\usetocbasicnumberline}{o}{}
3 \DeclareDocumentCommand{\DeclareTOCStyleEntry}{o m m}{}
4 \DeclareDocumentCommand{\DeclareTOCStyleEntries}{o m m}{}
5 \DeclareDocumentCommand{\DeclareTOCEntryStyle}{m o m}{}
6 \DeclareDocumentCommand{\DefineTOCEntryOption}{m o m}{}
7 \DeclareDocumentCommand{\DefineTOCEntryBooleanOption}{m o m m m}{}
8 \DeclareDocumentCommand{\DefineTOCEntryCommandOption}{m o m m m}{}
9 \DeclareDocumentCommand{\DefineTOCEntryIfOption}{m o m m m}{}
10 \DeclareDocumentCommand{\DefineTOCEntryLengthOption}{m o m m m}{}
11 \DeclareDocumentCommand{\DefineTOCEntryNumberOption}{m o m m m}{}
12 \DeclareDocumentCommand{\CloneTOCEntryStyle}{m m}{}

```

```
13 \DeclareDocumentCommand{\TOCEntryStyleInitCode}{m m}{}
14 \DeclareDocumentCommand{\TOCEntryStyleStartInitCode}{m m}{}

```

---

File 482 **lwarp-tocbibind.sty**

§ 588 Package **tocbibind**

*(Emulates or patches code by PETER WILSON.)*

Pkg tocbibind tocbibind is patched for use by lwarp.

[placement and toc options](#) An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual toc entry:**

A commonly-used method to introduce an index in a L<sup>A</sup>T<sub>E</sub>X document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex

```

Pkg makeidx **On its own HTML page, with a manual toc entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex

```

Pkg tocbibind **Inline, with an automatic toc entry:**

The tocbibind package may be used to automatically place an entry in the toc.

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex

```

Pkg tocbibind **On its own HTML page, with an automatic toc entry:**

```
\usepackage[nottoc]{tocbibind}
...
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex

```

Opt [tocbibind] numindex Use the tocbibind numindex option to generate a numbered index. Without this option, [numbered index section](#) the index heading has no number.

Other packages, such as `imakeidx`, may also have options for including the index in the Table of Contents.

for HTML output:

```

1 \let\simplechapterdelim\relax
2
3 \LWR@ProvidesPackagePass{tocbibind}[2010/10/13]

4 \renewenvironment{theindex}%
5 {%
6 \if@bibchapter
7 \if@donumindex
8 \chapter{\indexname}
9 \else
10 \if@dotocind
11 \chapter*{\indexname}
12 \addcontentsline{toc}{chapter}{\LWR@isolate{\indexname}}
13 \else
14 \chapter*{\indexname}
15 \fi
16 \fi
17 \else
18 \if@donumindex
19 \section{\indexname}
20 \else
21 \if@dotocind
22 \section*{\indexname}
23 \addcontentsline{toc}{\@tocextra}{\LWR@isolate{\indexname}}
24 \else
25 \section*{\indexname}
26 \fi
27 \fi
28 \fi
29 \let\item\LWR@indexitem%
30 \let\subitem\LWR@indexsubitem%
31 \let\subsubitem\LWR@indexsubsubitem%
32 }{}

```

The following code is shared by `anonchap`.

```

33 \DeclareDocumentCommand{\simplechapter}{0{\@empty}}{%
34 \def\@chapcntformat##1{%
35 #1~\csname the##1\endcsname\simplechapterdelim\quad%
36 }%
37 }
38
39 \DeclareDocumentCommand{\restorechapter}{}{%
40 \let\@chapcntformat\@secCNTformat%
41 }

```

File 483 **lwarp-tocdata.sty**

§ 589 Package **tocdata**

(Emulates or patches code by BRIAN DUNN.)

Pkg tocdata tocdata is patched for use by lwarp.

```

for HTML output: 1 \LWR@ProvidesPackagePass{tocdata}[2019/07/06]

2 \renewcommand*{\LWR@maybetocdata}{%
3 \ifdefempty{\TD@thistocdata}{}{%
4 \quad \InlineClass{authorartist}{\tocdataformat{\TD@thistocdata}}%
5 \def\TD@thistocdata{}
6 }
7 }

8 \renewrobustcmd{\tocdatapartprint}[4]
9 {%
10 \InlineClass{authorartist}{%
11 \quad --- %
12 \TDoptionalnameprint{#1}\TDoptionalnameprint{#2}#3#4%
13 }%
14 }
15
16 \@ifundefined{chapter}{}{
17 \let\tocdatachapterprint\tocdatapartprint
18 }
19 \let\tocdatasectionprint\tocdatapartprint
20 \let\tocdatasubsectionprint\tocdatapartprint
21
22 \newcommand*{\LWR@TD@settextalign}[1]{%
23 \def\LWR@TD@textalign{justify}%
24 \ifcsstring{TD@#1align}{\centering}%
25 {\def\LWR@TD@textalign{center}}%
26 }%
27 \ifcsstring{TD@#1align}{\raggedleft}%
28 {\def\LWR@TD@textalign{right}}%
29 }%
30 \ifcsstring{TD@#1align}{\raggedright}%
31 {\def\LWR@TD@textalign{left}}%
32 }%
33 }
34
35 \renewcommand{\TDartistauthorprint}[5]{%
36 \LWR@TD@settextalign{#1}%
37 \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
38 \InlineClass{authorartist}{\TDoptionalnameprint{#2}\TDoptionalnameprint{#3}#4#5}%
39 \end{BlockClass}%
40 }

```

```

41
42 \newcommand*\LWR@TD@setnamealign}[1]{%
43 \def\LWR@TD@textalign{justify}%
44 \ifcsstring{TD@#1textalign}{\centering}%
45 {\def\LWR@TD@textalign{center}}%
46 {}%
47 \ifcsstring{TD@#1textalign}{\raggedleft}%
48 {\def\LWR@TD@textalign{right}}%
49 {}%
50 \ifcsstring{TD@#1textalign}{\raggedright}%
51 {\def\LWR@TD@textalign{left}}%
52 {}%
53 }
54
55 \renewcommand{\TDartistauthortextprint}[2]{%
56 \LWR@TD@setnamealign{#1}%
57 \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
58 #2%
59 \end{BlockClass}%
60 }

```

---

File 484 **lwarp-tocenter.sty**

§ 590 Package **tocenter**

Pkg tocenter tocenter is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tocenter}[2004/12/09]

```

2 \NewDocumentCommand{\ToCenter}{s o m m}{ }
3 \NewDocumentCommand{\FromMargins}{s o m m m}{ }

```

---

File 485 **lwarp-tocloft.sty**

§ 591 Package **tocloft**

*(Emulates or patches code by PETER WILSON.)*

Pkg tocloft tocloft is emulated. Most user options and macros are ignored and disabled. \newlistof and \cftchapterprecis are supported.

Pkg tocloft If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its titles option, which tells tocloft to use standard L<sup>A</sup>T<sub>E</sub>X commands to create the titles, allowing other packages to work with it.

 **tocloft & other packages**

Discard all options for lwarp-tocloft:

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tocloft}[2017/08/31]

---

|                                |                                                    |
|--------------------------------|----------------------------------------------------|
| <code>\tocloftpagestyle</code> | <code>{&lt;style&gt;}</code>                       |
|                                | 2 <code>\newcommand{\tocloftpagestyle}[1]{}</code> |
| <code>\cftmarktoc</code>       |                                                    |
|                                | 3 <code>\newcommand*\cftmarktoc{}</code>           |
| <code>\cfttoctitlefont</code>  |                                                    |
|                                | 4 <code>\newcommand*\cfttoctitlefont{}</code>      |
| <code>\cftaftertoctitle</code> |                                                    |
|                                | 5 <code>\newcommand*\cftaftertoctitle{}</code>     |
|                                | 6 <code>\newlength{\cftbeforetoctitleskip}</code>  |
|                                | 7 <code>\newlength{\cftaftertoctitleskip}</code>   |
| <code>\cftmarklof</code>       |                                                    |
|                                | 8 <code>\newcommand*\cftmarklof{}</code>           |
| <code>\cftloftitlefont</code>  |                                                    |
|                                | 9 <code>\newcommand*\cftloftitlefont{}</code>      |
| <code>\cftafterloftitle</code> |                                                    |
|                                | 10 <code>\newcommand*\cftafterloftitle{}</code>    |
|                                | 11 <code>\newlength{\cftbeforeloftitleskip}</code> |
|                                | 12 <code>\newlength{\cftafterloftitleskip}</code>  |
| <code>\cftmarklot</code>       |                                                    |
|                                | 13 <code>\newcommand*\cftmarklot{}</code>          |
| <code>\cftlottitlefont</code>  |                                                    |
|                                | 14 <code>\newcommand*\cftlottitlefont{}</code>     |
| <code>\cftafterlottitle</code> |                                                    |
|                                | 15 <code>\newcommand*\cftafterlottitle{}</code>    |
|                                | 16 <code>\newlength{\cftbeforelottitleskip}</code> |
|                                | 17 <code>\newlength{\cftafterlottitleskip}</code>  |

```

\cftdot
18 \providecommand*\cftdot}{.}

\cftdotsep
19 \providecommand*\cftdotsep}{1}

\cftnodots
20 \providecommand*\cftnodots}{5000}

\cftdotfill {<sep>}
21 \providecommand\cftdotfill}[1]{

\cftsetpnumwidth {<length>}
22 \DeclareDocumentCommand\cftsetpnumwidth}{m}{

\cftsetrmarg {<length>}
23 \DeclareDocumentCommand\cftsetrmarg}{m}{

\cftpnumalign {<alignment>}
24 \DeclareDocumentCommand\cftpnumalign}{m}{

25 \LWR@providelength\cftparskip}

```

The part-related items are also provided by memoir:

```

26 \LWR@providelength\cftbeforepartskip}
27 \LWR@providelength\cftpartindent}
28 \LWR@providelength\cftpartnumwidth}
29 \providecommand*\cftpartfont}{
30 \providecommand*\cftpartpresnum}{
31 \providecommand*\cftpartaftersnum}{
32 \providecommand*\cftpartaftersnumb}{
33 \providecommand*\cftpartleader}{
34 \providecommand*\cftpartdotsep}{1}
35 \providecommand*\cftpartpagefont}{
36 \providecommand*\cftpartafterpnum}{

```

memoir uses the full name “chapter” instead of “chap”:

```

37 \LWR@providelength\cftbeforechapskip}
38 \LWR@providelength\cftchapindent}
39 \LWR@providelength\cftchapnumwidth}
40 \newcommand*\cftchapfont}{
41 \newcommand*\cftchappresnum}{
42 \newcommand*\cftchapaftersnum}{
43 \newcommand*\cftchapaftersnumb}{

```

```

44 \newcommand*\cftchapleader{}
45 \newcommand*\cftchapdotsep{1}
46 \newcommand*\cftchappagefont{}
47 \newcommand*\cftchapafterpnum{}

```

The following do not appear in memoir:

```

48 \LWR@providelength{\cftbeforesecskip}
49 \LWR@providelength{\cftsecindent}
50 \LWR@providelength{\cftsecnumwidth}
51 \newcommand*\cftsecfont{}
52 \newcommand*\cftsecpresnum{}
53 \newcommand*\cftsecaftersnum{}
54 \newcommand*\cftsecaftersnumb{}
55 \newcommand*\cftsecleader{}
56 \newcommand*\cftsecdotsep{1}
57 \newcommand*\cftsecpagefont{}
58 \newcommand*\cftsecafterpnum{}

```

```

59 \LWR@providelength{\cftbeforesubsecskip}
60 \LWR@providelength{\cftsubsecindent}
61 \LWR@providelength{\cftsubsecnumwidth}
62 \newcommand*\cftsubsecfont{}
63 \newcommand*\cftsubsecpresnum{}
64 \newcommand*\cftsubsecaftersnum{}
65 \newcommand*\cftsubsecaftersnumb{}
66 \newcommand*\cftsubsecleader{}
67 \newcommand*\cftsubsecdotsep{1}
68 \newcommand*\cftsubsecpagefont{}
69 \newcommand*\cftsubsecafterpnum{}

```

```

70 \LWR@providelength{\cftbeforesubsubsecskip}
71 \LWR@providelength{\cftsubsubsecindent}
72 \LWR@providelength{\cftsubsubsecnumwidth}
73 \newcommand*\cftsubsubsecfont{}
74 \newcommand*\cftsubsubsecpresnum{}
75 \newcommand*\cftsubsubsecaftersnum{}
76 \newcommand*\cftsubsubsecaftersnumb{}
77 \newcommand*\cftsubsubsecleader{}
78 \newcommand*\cftsubsubsecdotsep{1}
79 \newcommand*\cftsubsubsecpagefont{}
80 \newcommand*\cftsubsubsecafterpnum{}

```

```

81 \LWR@providelength{\cftbeforeparaskip}
82 \LWR@providelength{\cftparaindent}
83 \LWR@providelength{\cftparanumwidth}
84 \newcommand*\cftparafont{}
85 \newcommand*\cftparapresnum{}
86 \newcommand*\cftparaaftersnum{}
87 \newcommand*\cftparaaftersnumb{}
88 \newcommand*\cftparaleader{}
89 \newcommand*\cftparadotsep{1}
90 \newcommand*\cftparapagefont{}
91 \newcommand*\cftparaafterpnum{}

```

```
92 \LWR@providelength{\cftbeforeparaskip}
93 \LWR@providelength{\cftsubparaindent}
94 \LWR@providelength{\cftsubparanumwidth}
95 \newcommand*{\cftsubparafont}{}
96 \newcommand*{\cftsubparapresnum}{}
97 \newcommand*{\cftsubparaaftersnum}{}
98 \newcommand*{\cftsubparaaftersnumb}{}
99 \newcommand*{\cftsubparaleader}{}
100 \newcommand*{\cftsubparadotsep}{1}
101 \newcommand*{\cftsubparapagefont}{}
102 \newcommand*{\cftsubparaafterpnum}{}

103 \LWR@providelength{\cftbeforefigskip}
104 \LWR@providelength{\cftfigindent}
105 \LWR@providelength{\cftfignumwidth}
106 \newcommand*{\cftfigfont}{}
107 \newcommand*{\cftfigpresnum}{}
108 \newcommand*{\cftfigaftersnum}{}
109 \newcommand*{\cftfigaftersnumb}{}
110 \newcommand*{\cftfigleader}{}
111 \newcommand*{\cftfigdotsep}{1}
112 \newcommand*{\cftfigpagefont}{}
113 \newcommand*{\cftfigafterpnum}{}

114 \LWR@providelength{\cftbeforesubfigskip}
115 \LWR@providelength{\cftsubfigindent}
116 \LWR@providelength{\cftsubfignumwidth}
117 \newcommand*{\cftsubfigfont}{}
118 \newcommand*{\cftsubfigpresnum}{}
119 \newcommand*{\cftsubfigaftersnum}{}
120 \newcommand*{\cftsubfigaftersnumb}{}
121 \newcommand*{\cftsubfigleader}{}
122 \newcommand*{\cftsubfigdotsep}{1}
123 \newcommand*{\cftsubfigpagefont}{}
124 \newcommand*{\cftsubfigafterpnum}{}

125 \LWR@providelength{\cftbeforetabskip}
126 \LWR@providelength{\cfttabindent}
127 \LWR@providelength{\cfttabnumwidth}
128 \newcommand*{\cfttabfont}{}
129 \newcommand*{\cfttabpresnum}{}
130 \newcommand*{\cfttabaftersnum}{}
131 \newcommand*{\cfttabaftersnumb}{}
132 \newcommand*{\cfttableader}{}
133 \newcommand*{\cfttabdotsep}{1}
134 \newcommand*{\cfttabpagefont}{}
135 \newcommand*{\cfttabafterpnum}{}

136 \LWR@providelength{\cftbeforesubtabskip}
137 \LWR@providelength{\cftsubtabindent}
138 \LWR@providelength{\cftsubtabnumwidth}
139 \newcommand*{\cftsubtabfont}{}
140 \newcommand*{\cftsubtabpresnum}{}
141 \newcommand*{\cftsubtabaftersnum}{}
142 \newcommand*{\cftsubtabaftersnumb}{}

```

```

143 \newcommand*\cftsubtableader{}
144 \newcommand*\cftsubtabdotsep}{1}
145 \newcommand*\cftsubtabpagefont{}
146 \newcommand*\cftsubtabafterpnum{}

147 \DeclareDocumentCommand{\cftsetindents}{m m m}{}

148 \newcommand{\pagenumbersoff}[1]{}
149 \newcommand{\pagenumberson}[1]{}

```

`\newlistentry` [*<within>*] [*<counter>*] [*<ext>*] [*<level-1>*]

```

150 \DeclareDocumentCommand{\newlistentry}{o m m m}
151 {%
152 \LWR@traceinfo{newlistentry #2 #3 #4}%
153 \IfValueTF{#1}%
154 {%
155 \ifundefined{c@#2}{%
156 \newcounter{#2}[#1]%
157 \expandafter\edef\csname the#2\endcsname%
158 \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}%
159 }%
160 }{%
161 }%
162 {%
163 \ifundefined{c@#2}{%
164 \newcounter{#2}%
165 }{%
166 }%
167 \@namedef{l@#2}##1##2{%
168 \hypertocfloat{1}{#2}{#3}{##1}{##2}%
169 \def\cftwhatismyname{#2}% from memoir
170 }%
171 \expandafter\newlength\csname cftbefore#2skip\endcsname%
172 \expandafter\newlength\csname cft#2indent\endcsname%
173 \expandafter\newlength\csname cft#2numwidth\endcsname%
174 \@namedef{cft#2font}{}%
175 \@namedef{cft#2presnum}{}%
176 \@namedef{cft#2aftersnum}{}%
177 \@namedef{cft#2aftersnumb}{}%
178 \@namedef{cft#2leader}{}%
179 \@namedef{cft#2dotsep}{1}%
180 \@namedef{cft#2pagefont}{}%
181 \@namedef{cft#2afterpnum}{}%
182 \@namedef{toclevel@#2}{#4}%
183 \@namedef{cft#2fillnum}##1{}%
184 \LWR@traceinfo{newlistentry done}%
185 }

```

`\newlistof` [*<within>*] [*<type>*] [*<ext>*] [*<listofname>*]

Emulated through the `\newfloat` mechanism.

```

186 \DeclareDocumentCommand{\newlistof}{o m m m}
187 {%

```

```

188 \IfValueTF{#1}%
189 {\newlistentry[#1]{#2}{#3}{0}}%
190 {\newlistentry{#2}{#3}{0}}%
191 \namedef{ext@#2}{#3}%
192 \@ifundefined{c@#3depth}{\newcounter{#3depth}}{}%
193 \setcounter{#3depth}{1}%
194 \namedef{cftmark#3}{}%
195 \namedef{listof#2}{\listof{#2}{#4}}%
196 \namedef{@cftmake#3title}{}%
197 \expandafter\newlength\csname cftbefore#3titleskip\endcsname%
198 \expandafter\newlength\csname cftafter#3titleskip\endcsname%
199 \namedef{cft#3titlefont}{}%
200 \namedef{cftafter#3title}{}%
201 \namedef{cft#3prehook}{}%
202 \namedef{cft#3posthook}{}%
203 }

```

\cftchapterprecis {<text>}

```

204 \newcommand{\cftchapterprecis}[1]{%
205 \cftchapterprecishere{#1}
206 \cftchapterprecistoc{#1}}
207 \newcommand{\cftchapterprecishere}[1]{%
208 \begin{quote}\textit{#1}\end{quote}}
209 \newcommand{\cftchapterprecistoc}[1]{
210 \addtocontents{toc}{%
211 {
212 \protect\begin{quote}#1\protect\end{quote}}
213 }
214 }

```

---

File 486 **lwarp-tocstyle.sty**

§ 592 Package **tocstyle**

Pkg tocstyle tocstyle is ignored.

 **Not fully tested!** [Please send bug reports!](#)

**for HTML output:** 1 \LWR@ProvidesPackageDrop{tocstyle}[2017/02/23]

```

2 \newcommand*{\usetocstyle}[2][]{ }
3 \newcommand*{\deactivatetocstyle}[1][]{ }
4 \newcommand*{\reactivatetocstyle}[1][]{ }
5 \NewDocumentCommand{\settocfeature}{o o m m}{}
6 \NewDocumentCommand{\settocstylefeature}{o m m}{}
7 \NewDocumentCommand{\newtocstyle}{o o m m}{}
8 \newcommand*{\aliastoc}[2]{}
9 \newcommand*{\showtoc}[2]{}
10 \newcommand{\iftochasdepth}[4]{}

```

File 487 **lwarp-todo.sty**

§ 593 Package **todo**

(Emulates or patches code by FEDERICO GARCIA.)

Pkg todo **todo** is patched for use by **lwarp**.

```

for HTML output: 1 \LWR@ProvidesPackagePass{todo}[2010/03/31]

2 \renewcommand\todoitem[2]{%
3 \refstepcounter{todo}%
4 \item[%
5 \HTMLUnicode{2610} \quad
6 \ref{todopage:\thetodo}
7] : {\todoformat\ifx#1\todotodo\else\textbf{#1} \fi}#2%
8 \label{todolbl:\thetodo}%
9 }%
10
11 \renewcommand\doneitem[2]{%
12 \stepcounter{todo}%
13 \item[%
14 \HTMLUnicode{2611} \quad
15 \ref{todopage:\thetodo}
16] \@nameuse{@done\thetodo}:
17 {\todoformat\ifx#1\todotodo\else\textbf{#1} \fi}#2%
18 }
19
20 \xpatchcmd{\@displaytodo}
21 {\todoformat #1}{\todoformat \textbf{#1}}{}
22 {\PackageWarning{lwarp-todo}{Unable to patch @displaytodo.}}
23
24 \xpatchcmd{\@displayfulltodo}
25 {\todoformat #1}{\todoformat \textbf{#1}}{}
26 {\PackageWarning{lwarp-todo}{Unable to patch @displayfulltodo.}}
27
28 \patchcmd{\todoenv}{\itshape see text.}{\textit{see text.}}{}
29 {\PackageWarning{lwarp-todo}{Unable to patch todoenv.}}
30
31 \patchcmd{\astodos}{\todoformat #1}{\todoformat \textbf{#1}}{}
32 {\PackageWarning{lwarp-todo}{Unable to patch astodos.}}
33
34 \AtBeginDocument{
35 \crefname{todo}{todo}{todos}
36 \Crefname{todo}{Todo}{Todos}
37 }

```

File 488 **lwarp-todonotes.sty**

§ 594 Package **todonotes**

(Emulates or patches code by HENRIK SKOV MIDTIBY.)

Pkg todonotes todonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{todonotes}[2012/07/25]
2 \if@todonotes@disabled
3 \else
4
5 \newcommand{\ext@todo}{tdo}
6
7 \renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}

8 \let\LWRTODONOTES@orig@todotoc\todotoc
9
10 \renewcommand*\@todotoc{%
11 \LWR@phantomsection%
12 \LWRTODONOTES@orig@todotoc%
13 }
14
15 \renewcommand{\@todonotes@drawMarginNoteWithLine}{
16 \fcolorbox
17 {\@todonotes@currentbordercolor}
18 {\@todonotes@currentbackgroundcolor}
19 {\arabic{@todonotes@numberoftodonotes}}
20 \marginpar{\@todonotes@drawMarginNote}
21 }
22
23 \renewcommand{\@todonotes@drawInlineNote}{%
24 \fcolorboxBlock%
25 {\@todonotes@currentbordercolor}%
26 {\@todonotes@currentbackgroundcolor}%
27 {%
28 \if@todonotes@authorgiven%
29 {\@todonotes@author:\,}%
30 \fi%
31 \@todonotes@text%
32 }%
33 }
34
35 \renewcommand{\@todonotes@drawMarginNote}{%
36 \if@todonotes@authorgiven%
```

```

37 \@todonotes@author\par%
38 \fi%
39 \arabic{@todonotes@numberoftodonotes}: %
40 \fcolorbox%
41 {@todonotes@currentbordercolor}%
42 {@todonotes@currentbackgroundcolor}%
43 {%
44 \@todonotes@sizecommand%
45 \@todonotes@text %
46 }%
47 }%
48
49 \renewcommand{\@todonotes@drawLineToRightMargin}{}
50
51 \renewcommand{\@todonotes@drawLineToLeftMargin}{}
52
53 \renewcommand{\missingfigure}[2][[]]{%
54 \setkeys{todonotes}{#1}%
55 \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
56 \fcolorboxBlock%
57 {@todonotes@currentbordercolor}%
58 {@todonotes@currentfigcolor}%
59 {%
60 \setlength{\fboxrule}{4pt}%
61 \fcolorbox{red}{white}{Missing figure} \quad #2%
62 }
63 }
64
65 \LetLtxMacro\LWRTODONOTES@orig@todo\@todo
66
67 \RenewDocumentCommand{\@todo}{o m}{%
68 \begingroup%
69 \renewcommand*\phantomsection}{}%
70 \IfValueTF{#1}{%
71 \LWRTODONOTES@orig@todo[#1]{#2}%
72 }{%
73 \LWRTODONOTES@orig@todo{#2}%
74 }
75 \endgroup%
76 }
77
78 \fi% \if@todonotes@disabled

```

---

File 489 **lwarp-topcapt.sty**

§ 595 Package **topcapt**

Pkg topcapt topcapt is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{topcapt}[2004/12/11]

2 \LetLtxMacro\topcaption\caption

---

File 490 **lwarp-tram.sty**

§ 596 Package **tram**

Pkg tram tram is emulated.

 **block only** The HTML emulation uses a `<div>`, which must not appear inside an HTML `<span>` or an HTML paragraph. For this reason, the tram environment should only be used to contain paragraphs inside a `\parbox` or `minipage`. tram should not be used to mark up inline text.

To disable tram, allowing source compatibility with inline uses:

```
\begin{warpHTML}
\renewenvironment{tram}[1][\]{}{}
\end{warpHTML}
```

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{tram}[2013/04/04]
2 \newenvironment{tram}[1][\]{}{}
3 {\BlockClass[background:lightgray]{tram}}
4 {\endBlockClass}
```

---

File 491 **lwarp-transparent.sty**

§ 597 Package **transparent**

*(Emulates or patches code by HEIKO OBERDIEK.)*

Pkg transparent transparent is emulated. `\texttransparent` works for inline objects. `\transparent` only works for `\includegraphics`.

 **Not X<sub>Ǝ</sub>L<sub>A</sub>T<sub>E</sub>X!** Note that transparent does not work with X<sub>Ǝ</sub>L<sub>A</sub>T<sub>E</sub>X.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{transparent}[2019/11/29]
2 \newcommand*\LWR@HTML@transparent[1]{\edef\LWR@opacity{#1}}
3
4 \LWR@formatted{transparent}
5
6
7 \newcommand*\LWR@HTML@texttransparent[2]{%
8 \begingroup%
9 \transparent{#1}%
10 \InlineClass[opacity: #1]{transparent}{#2}%
11 \endgroup%
12 }
13
14 \LWR@formatted{texttransparent}
```

---

File 492 **lwarp-trimclip.sty**

§ 598 Package **trimclip**

Pkg trimclip trimclip is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{trimclip}[2018/04/08]

The third argument, the text, is not touched. This allows \bgroup / \egroup, and verbatim content.

```

2 \csdef{trimbox}{\@ifstar\@gobble\@gobble}
3 \csletcs{trimbox*}{trimbox}
4 \def\endtrimbox{}
5 \csletcs{endtrimbox*}{endtrimbox}
6
7 \csletcs{clipbox}{trimbox}
8 \csletcs{clipbox*}{trimbox}
9 \csletcs{endclipbox}{endtrimbox}
10 \csletcs{endclipbox*}{endtrimbox}
11
12 \csletcs{marginbox}{trimbox}
13 \csletcs{marginbox*}{trimbox}
14 \csletcs{endmarginbox}{endtrimbox}
15 \csletcs{endmarginbox*}{endtrimbox}

```

---

File 493 **lwarp-trivfloat.sty**

§ 599 Package **trivfloat**

*(Emulates or patches code by JOSEPH WRIGHT.)*

Pkg trivfloat trivfloat is forced to use the built-in lwarp emulation for floats.

To create a new float type and change its name:

---

```

\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}

```

---

Discard all options for lwarp-trivfloat. This tells trivfloat not to use floatrow or memoir.

```

1 \LWR@ProvidesPackageDrop{trivfloat}[2009/04/23]
2 \LWR@origRequirePackage{trivfloat}

```

`\tfl@chapter@fix` Nullified at the beginning of the document. Is used by `trivfloat` to correct float chapter numbers, but is not needed for `lwarp`.

```
3 \AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{}}
```

### § 599.1 **Combining `\newfloat`, `\trivfloat`, and `algorithmicx`**

**For both print and HTML output:**



When using `float`, `trivfloat`, or `algorithmicx` at the same time, be aware of conflicting file usage. `algorithmicx` uses `.loa`. `trivfloat` by default starts with `.loa` and goes up for additional floats, skipping `.lof` and `.lot`.



When using `\newfloat`, be sure to manually assign higher letters to the `\newfloat` files to avoid `.loa` used by `algorithmicx`, and any files used by `trivfloat`. Also avoid using `.lof` and `.lot`.



When using `\trivfloat`, you may force it to avoid conflicting with `algorithmicx` by starting `trivfloat`'s file extensions with `.lob`:

---

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
```

---

#### File 494 **lwarp-truncate.sty**

### § 600 Package **truncate**

Pkg truncate truncate is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{truncate}[2001/08/20]

```
2 \providecommand{\TruncateMarker}{}
3 \newcommand{\truncate}[3][\TruncateMarker]{#3}
```

#### File 495 **lwarp-turnthepage.sty**

### § 601 Package **turnthepage**

Pkg turnthepage turnthepage is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{turnthepage}[2011/03/24]

```
2 \newcommand{\turnthepage}{}

```

---

File 496 **lwarp-twoup.sty**

§ 602 Package **twoup**

Pkg twoup twoup is ignored.

**for HTML output:**

```
1 \LWR@ProvidesPackageDrop{twoup}[2007/02/26]
2 \newcommand{\cleartolastpage}{}

```

---

File 497 **lwarp-txfonts.sty**

§ 603 Package **txfonts**

*(Emulates or patches code by YOUNG RYU.)*

Pkg txfonts txfonts is used as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{txfonts}[2008/01/22]

```

For MATHJAX:

```
2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{txfonts}
6
7 \LWR@mathjax@addgreek@l@up{}{up}
8 \end{warpMathJax}

```

---

File 498 **lwarp-txgreeks.sty**

§ 604 Package **txgreeks**

*(Emulates or patches code by JEAN-FRANÇOIS BURNOL.)*

Pkg txgreeks txgreeks is used as-is for SVG math, and is emulated for MATHJAX.

The MATHJAX emulation honors all package options.

**for HTML output:**

```
1 \LWR@ProvidesPackagePass{txgreeks}[2011/03/16]
2
3 \LWR@infoprocessingmathjax{txgreeks}

```

```

4 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
5
6 \begin{warpMathJax}
7 \iftgs@upLower% upright lowercase Greek
8 \LWR@mathjax@addgreek@l@up{}{}
9 \LWR@mathjax@addgreek@l@it{other}{}
10 \else% italic lowercase Greek
11 \LWR@mathjax@addgreek@l@it{}{}
12 \LWR@mathjax@addgreek@l@up{other}{}
13 \fi
14
15 \iftgs@itupper % italic uppercase Greek
16 \LWR@mathjax@addgreek@u@it*{}{}
17 \LWR@mathjax@addgreek@u@up*{other}{}
18 \LWR@mathjax@addgreek@u@up*{var}{}
19 \else% upright uppercase Greek
20 \LWR@mathjax@addgreek@u@up*{}{}
21 \LWR@mathjax@addgreek@u@it*{other}{}
22 \LWR@mathjax@addgreek@u@it*{var}{}
23 \fi
24 \end{warpMathJax}

```

---

File 499 **lwarp-typearea.sty**

§ 605 Package **typearea**

*(Emulates or patches code by MARKUS KOHM.)*

Pkg typearea **typearea** is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. `\DeclareDocumentCommand` is used to overwrite the koma-script definitions.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{typearea}[2018/03/30]
2 \DeclareDocumentCommand{\typearea}{o m}{}
3 \DeclareDocumentCommand{\reclctypearea}{}{}
4 \@ifundefined{footheight}{\newlength\footheight}{}
5 \DeclareDocumentCommand{\areaset}{o m m}{}
6 \DeclareDocumentCommand{\activateareas}{}{}
7 \DeclareDocumentCommand{\storeareas}{m}{}
8 \DeclareDocumentCommand{\BeforeRestoreareas}{s m}{}
9 \DeclareDocumentCommand{\AfterRestoreareas}{s m}{}
10 \DeclareDocumentCommand{\AfterCalculatingTypearea}{s m}{}
11 \DeclareDocumentCommand{\AfterSettingArea}{s m}{}

```

File 500 **lwarp-typicons.sty**

§ 606 Package **typicons**

*(Emulates or patches code by ARTHUR VIGIL, XAVIER DANAUX.)*

Pkg typicons typicons is patched for use by lwarp.

If `\ticon` is used, the name of the icon is used in the `alt` tag. Otherwise, for each of the individual icon macros, a generic `alt` tag is used.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{typicons}[2015/05/20]

2 \LetLtxMacro\LWR@orig@symbol\symbol
3
4 \let\LWR@orig@typicon@TI\TI
5
6 \newcommand*{\LWR@typicon@symbol}[1]{%
7 \begin{lateximage}*[typicon][typicon#1]%
8 \begingroup%
9 \LWR@orig@typicon@TI%
10 \LWR@orig@symbol{#1}%
11 \endgroup%
12 \end{lateximage}%
13 }
14
15 \renewcommand*{\TI}{%
16 \LetLtxMacro\symbol\LWR@typicon@symbol%
17 }
18
19 \renewcommand*{\ticon}[1]
20 {%
21 \begin{lateximage}*[#1 icon][typicon#1]%
22 \TI\csname ticon@#1\endcsname%
23 \end{lateximage}%
24 }
```

File 501 **lwarp-ulem.sty**

§ 607 Package **ulem**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg ulem Patched for use by lwarp.

**for HTML output:** Use the original package:

```

1 \LWR@ProvidesPackagePass{ulem}[2012/05/18]
```

Basic markup commands, using CSS:

```
2 \NewDocumentCommand{\LWR@HTML@uline}{+m}{%
3 \InlineClass%
4 (text-decoration:underline; text-decoration-skip: auto)%
5 {uline}{\LWR@isolate{#1}}%
6 }
7 \LWR@formatted{uline}
8
9 \NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
10 \InlineClass%
11 (%
12 text-decoration:underline; text-decoration-skip: auto;%
13 text-decoration-style:double%
14)%
15 {uuline}{\LWR@isolate{#1}}%
16 }
17 \LWR@formatted{uuline}
18
19 \NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
20 \InlineClass%
21 (%
22 text-decoration:underline; text-decoration-skip: auto;%
23 text-decoration-style:wavy%
24)%
25 {uwave}{\LWR@isolate{#1}}%
26 }
27 \LWR@formatted{uwave}
28
29 \NewDocumentCommand{\LWR@HTML@sout}{+m}{%
30 \InlineClass%
31 (text-decoration:line-through)%
32 {sout}{\LWR@isolate{#1}}%
33 }
34 \LWR@formatted{sout}
35
36 \NewDocumentCommand{\LWR@HTML@xout}{+m}{%
37 \InlineClass%
38 (text-decoration:line-through)%
39 {xout}{\LWR@isolate{#1}}%
40 }
41 \LWR@formatted{xout}
42
43 \NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
44 \InlineClass%
45 (%
46 text-decoration:underline;%
47 text-decoration-skip: auto;%
48 text-decoration-style:dashed%
49)%
50 {dashuline}{\LWR@isolate{#1}}%
51 }
52 \LWR@formatted{dashuline}
53
54 \NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
```

```

55 \InlineClass%
56 (%)
57 text-decoration:underline;%
58 text-decoration-skip: auto;%
59 text-decoration-style: dotted%
60)%
61 {dotuline}{\LWR@isolate{#1}}%
62 }
63 \LWR@formatted{dotuline}

```

Nullified/emulated macros:

```

64 \NewDocumentCommand{\LWR@HTML@markoverwith}{m}{}
65 \LWR@formatted{markoverwith}
66
67 \NewDocumentCommand{\LWR@HTML@ULon}{+m}{\uline{#1}\egroup}
68 \LWR@formatted{ULon}

```

---

File 502 **lwarp-umoline.sty**

§ 608 Package **umoline**

*(Emulates or patches code by HIROSHI NAKASHIMA.)*

Pkg umoline **umoline** is patched for use by lwarp.

```

for HTML output: 1 \LWR@ProvidesPackagePass{umoline}[2000/07/11]

2 \newcommand*{\LWR@HTML@Underline}[1]{%
3 \InlineClass{uline}{#1}%
4 }
5 \LWR@formatted{Underline}
6
7 \newcommand*{\LWR@HTML@Midline}[1]{%
8 \InlineClass{sout}{#1}%
9 }
10 \LWR@formatted{Midline}
11
12 \newcommand*{\LWR@HTML@Overline}[1]{%
13 \InlineClass{oline}{#1}%
14 }
15 \LWR@formatted{Overline}
16
17 \newcommand*{\LWR@HTML@UMoline}[2]{%
18 \InlineClass{uline}{#2}%
19 }
20 \LWR@formatted{UMoline}
21
22 \NewDocumentCommand{\LWR@HTML@UMospace}{s m o}{\hspace*{#2}}
23 \LWR@formatted{UMospace}
24
25 \NewDocumentCommand{\LWR@HTML@UMOnewline}{s}{\newline}
26 \LWR@formatted{UMOnewline}

```

---

File 503 **lwarp-underscore.sty**

§ 609 Package **underscore**

Pkg underscore underscore is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{underscore}[2006/09/13]

---

File 504 **lwarp-unicode-math.sty**

§ 610 Package **unicode-math**

*(Emulates or patches code by WILL ROBERTSON.)*

Pkg unicode-math unicode-math is supported as-is for HTML with svgnmath.

 **MATHJAX** If the document source includes embedded Unicode characters, these may not be reproduced correctly for *pdftotext*, and thus not display correctly in MATHJAX.

Symbol font commands are emulated, but not all combinations are supported by MathJax, especially with the dedicated Greek macros. Symbol macros such as `\symbfssf` may not be sans or bold. For Greek, use the Unicode equivalent, if necessary.

 **\mathversion** The MATHJAX emulation does not change with the use of `\mathversion`. Whatever emulation is established at the begin of the document will remain.

The option `sans-style` honors upright and italic, but italic will not be sans, in order to support Greek macros.

Greek macros such as `\alpha` respond to the `math-style` option. Latin symbols does not, per MATHJAX limitations, unless placed inside `\symbit` or similar.

Macros from the categories `\mathopen`, `\mathclose`, and `\mathfence` are emulated. Due to current MATHJAX limitations, not all stretch to the correct height.

Also emulated are macros from the categories `\mathpunct`, `\mathover`, `\mathunder`, `\mathaccent`, `\mathbotaccent`, and `\mathop`.

The individual `unicode-math` macros of categories `\mathbin`, `\mathord`, and `\mathrel` are not emulated for MATHJAX, as there are more than two thousand of them, but they may be added as needed. Place the following in the document preamble after loading `unicode-math`, including a definition for each macro which is used in the document but undefined in MATHJAX:

```
\begin{warpMathJax}
\CustomizeMathJax{\newcommand{\uplus}{\mathbin{\unicode{x0228E}}}}
...
\end{warpMathJax}
```

Use `\mathrel`, `\mathbin`, etc. depending on the category of each macro. For a list of macro names and symbols, see **texdoc unimath-symbols**.

for HTML output:

```

1 \LWR@ProvidesPackagePass{unicode-math}[2019/09/26]
2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{unicode-math}
6
7 % Not all are possible in MathJax.
8 \CustomizeMathJax{\let\symnormal\mathit}
9 \CustomizeMathJax{\let\symliteral\mathrm}
10 \CustomizeMathJax{\let\sybbb\mathbb}
11 \CustomizeMathJax{\let\sybbb\mathbb}% not italic
12 \CustomizeMathJax{\let\symcal\mathcal}
13 \CustomizeMathJax{\let\symscr\mathscr}
14 \CustomizeMathJax{\let\symfrac\mathfrak}
15
16 \CustomizeMathJax{\let\symsfup\mathsf}
17
18 \CustomizeMathJax{\let\symsfit\mathit}% not sans
19 % \CustomizeMathJax{\newcommand{\symsfit}[1]{%
20 % \mmlToken{mi}[mathvariant="sans-serif-italic"]{#1}}% not greek
21 % }
22
23 \CustomizeMathJax{\let\sybfsf\mathbf}% not sans
24 % \CustomizeMathJax{\newcommand{\sybfsf}[1]{%
25 % \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}}% not greek
26 % }
27
28 \CustomizeMathJax{\let\sybfup\mathbf}
29 \CustomizeMathJax{\newcommand{\sybfit}[1]{\boldsymbol{#1}}}
30 \CustomizeMathJax{\let\sybfcal\mathcal}% not bold
31
32 \CustomizeMathJax{\let\sybfscr\mathscr}% not bold
33 % \CustomizeMathJax{\newcommand{\sybfscr}[1]{
34 % \mmlToken{mi}[mathvariant="math-bold-script"]{#1}}% not greek
35 % }
36
37 \CustomizeMathJax{\let\sybffrak\mathfrak}% not bold
38 % \CustomizeMathJax{\newcommand{\sybffrak}[1]{%
39 % \mmlToken{mi}[mathvariant="math-bold-fraktur"]{#1}}% not greek
40 % }
41
42 \CustomizeMathJax{\let\sybfsfup\mathbf}% not sans
43 % \CustomizeMathJax{\newcommand{\sybfsfup}[1]{%
44 % \mmlToken{mi}[mathvariant="bold-sans-serif"]{#1}}% not greek
45 % }
46
47 \CustomizeMathJax{\newcommand{\sybfsfit}[1]{\boldsymbol{#1}}}% not sans
48 % \CustomizeMathJax{\newcommand{\sybfsfit}[1]{%
49 % \mmlToken{mi}[mathvariant="sans-serif-bold-italic"]{#1}}% not greek
50 % }
51

```

```

52 % Duplicates below are commented out.
53 \CustomizeMathJax{\let\symup\mathrm}
54 \CustomizeMathJax{\let\sympf\mathbf}% \sympfup defined above
55 \CustomizeMathJax{\let\symit\mathit}
56 % \CustomizeMathJax{\let\sympfit\mathit}% not bold

57 \ExplSyntaxOn
58 \AtBeginDocument{
59 \bool_if:NTF \g__um_sfliteral_bool
60 {\CustomizeMathJax{\let\symsf\symsfup}}
61 {
62 \bool_if:NTF \g__um_upsans_bool
63 {\CustomizeMathJax{\let\symsf\symsfup}}
64 {\CustomizeMathJax{\let\symsf\symsfit}}
65 }
66 }
67 \ExplSyntaxOff

68 % \CustomizeMathJax{\let\sympfsfup\mathbf}% not sans
69 % \CustomizeMathJax{\let\symsfit\mathit}% not sans
70 % \CustomizeMathJax{\let\sympfsfit\mathit}% not bold nor sans
71 \CustomizeMathJax{\let\symtt\mathtt}
72 % \CustomizeMathJax{\let\sympb\mathbb}
73 % \CustomizeMathJax{\let\sympbbit\mathbb}% not italic
74 % \CustomizeMathJax{\let\symscr\mathscr}
75 % \CustomizeMathJax{\let\sympfscr\mathscr}% not bold
76 % \CustomizeMathJax{\let\symfrac\mathfrak}
77 \CustomizeMathJax{\let\sympffrac\mathbffrac}

```

Some symbol categories defined by `unicode-math`, in case they are used inside custom macros:

```

78 \CustomizeMathJax{\newcommand{\mathfence}[1]{\mathord{#1}}}
79 \CustomizeMathJax{\newcommand{\mathover}[1]{#1}}
80 \CustomizeMathJax{\newcommand{\mathunder}[1]{#1}}
81 \CustomizeMathJax{\newcommand{\mathaccent}[1]{#1}}
82 \CustomizeMathJax{\newcommand{\mathbotaccent}[1]{#1}}
83 \CustomizeMathJax{\newcommand{\mathalpha}[1]{\mathord{#1}}}

```

`math-style` is one of: `ISO`, `TeX`, `french`, `upright`, or `literal`, which set `\g__um_upGreek_bool` and `\g__um_upgreek_bool`.

```

84 \ExplSyntaxOn
85
86 \AtBeginDocument{
87 \bool_if:NTF \g__um_upGreek_bool
88 {\LWR@mathjax@addgreek@u@up*{}}
89 {\LWR@mathjax@addgreek@u@it*{}}
90
91 \bool_if:NTF \g__um_upgreek_bool
92 {\LWR@mathjax@addgreek@l@up{}}
93 {\LWR@mathjax@addgreek@l@it{}}
94 }
95

```

```

96 \LWR@mathjax@addgreek@u@up*{up}{ }
97 \LWR@mathjax@addgreek@u@it*{it}{ }
98 \LWR@mathjax@addgreek@l@up{up}{ }
99 \LWR@mathjax@addgreek@l@it{it}{ }
100
101 \ExplSyntaxOff
102
103 \CustomizeMathJax{\let\lparen()}
104 \CustomizeMathJax{\let\rparen)}
105 \CustomizeMathJax{\newcommand{\cuberoot}[1]{\,{ }^3\!\!\sqrt{#1}}\,}
106 \CustomizeMathJax{\newcommand{\fourthroot}[1]{\,{ }^4\!\!\sqrt{#1}}\,}

```

Many `\mathopen/\mathclose` delimiters are defined in `lwarp_mathjax.txt`, where `\left/\right` support is added.

```

107 \CustomizeMathJax{\newcommand{\longdivision}[1]{\mathord{\unicode{x027CC}#1}}}
108
109 \CustomizeMathJax{\newcommand{\mathcomma}{,}}
110 \CustomizeMathJax{\newcommand{\mathcolon}{:}}
111 \CustomizeMathJax{\newcommand{\mathsemicolon}{;}}
112
113 \CustomizeMathJax{\newcommand{\overbracket}[1]{\mathinner{\overline{\ulcorner#1\urcorner}}}}
114 \CustomizeMathJax{\newcommand{\underbracket}[1]{\mathinner{\underline{\llcorner#1\lrcorner}}}}
115
116 \CustomizeMathJax{\newcommand{\overbar}[1]{\mathord{#1\unicode{x00305}}}}
117 \CustomizeMathJax{\newcommand{\ovhook}[1]{\mathord{#1\unicode{x00309}}}}
118 \CustomizeMathJax{\newcommand{\ocirc}[1]{\mathord{#1\unicode{x0030A}}}}
119 \CustomizeMathJax{\newcommand{\candra}[1]{\mathord{#1\unicode{x00310}}}}
120 \CustomizeMathJax{\newcommand{\oturnedcomma}[1]{\mathord{#1\unicode{x00312}}}}
121 \CustomizeMathJax{\newcommand{\ocommatopright}[1]{\mathord{#1\unicode{x00315}}}}
122 \CustomizeMathJax{\newcommand{\droang}[1]{\mathord{#1\unicode{x0031A}}}}
123 \CustomizeMathJax{\newcommand{\leftharpoonaccent}[1]{\mathord{#1\unicode{x020D0}}}}
124 \CustomizeMathJax{\newcommand{\rightharpoonaccent}[1]{\mathord{#1\unicode{x020D1}}}}
125 \CustomizeMathJax{\newcommand{\vertoverlay}[1]{\mathord{#1\unicode{x020D2}}}}
126 \CustomizeMathJax{\newcommand{\leftarrowaccent}[1]{\mathord{#1\unicode{x020D0}}}}
127 \CustomizeMathJax{\newcommand{\annuity}[1]{\mathord{#1\unicode{x020E7}}}}
128 \CustomizeMathJax{\newcommand{\widebridgeabove}[1]{\mathord{#1\unicode{x020E9}}}}
129 \CustomizeMathJax{\newcommand{\asteraccent}[1]{\mathord{#1\unicode{x020F0}}}}
130 \CustomizeMathJax{\newcommand{\threunderdot}[1]{\mathord{#1\unicode{x020E8}}}}
131
132 \CustomizeMathJax{\newcommand{\Bbbsum}{\mathop{\unicode{x2140}}\limits}}
133 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
134 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x2230}}\limits}}
135 \CustomizeMathJax{\newcommand{\intclockwise}{\mathop{\unicode{x2231}}\limits}}
136 \CustomizeMathJax{\newcommand{\ointclockwise}{\mathop{\unicode{x2232}}\limits}}
137 \CustomizeMathJax{\newcommand{\ointctrlockwise}{\mathop{\unicode{x2233}}\limits}}
138 \CustomizeMathJax{\newcommand{\varointclockwise}{\mathop{\unicode{x2232}}\limits}}
139 \CustomizeMathJax{\newcommand{\leftouterjoin}{\mathop{\unicode{x27D5}}\limits}}
140 \CustomizeMathJax{\newcommand{\rightouterjoin}{\mathop{\unicode{x27D6}}\limits}}
141 \CustomizeMathJax{\newcommand{\fullouterjoin}{\mathop{\unicode{x27D7}}\limits}}
142 \CustomizeMathJax{\newcommand{\bigbot}{\mathop{\unicode{x27D8}}\limits}}
143 \CustomizeMathJax{\newcommand{\bigtop}{\mathop{\unicode{x27D9}}\limits}}
144 \CustomizeMathJax{\newcommand{\xsol}{\mathop{\unicode{x29F8}}\limits}}
145 \CustomizeMathJax{\newcommand{\xbsol}{\mathop{\unicode{x29F9}}\limits}}
146 \CustomizeMathJax{\newcommand{\bigcupdot}{\mathop{\unicode{x2A03}}\limits}}

```

```

147 \CustomizeMathJax{\newcommand{\bigsqcap}{\mathop{\unicode{x2A05}}\limits}}
148 \CustomizeMathJax{\newcommand{\conjquant}{\mathop{\unicode{x2A07}}\limits}}
149 \CustomizeMathJax{\newcommand{\disjquant}{\mathop{\unicode{x2A08}}\limits}}
150 \CustomizeMathJax{\newcommand{\bigtimes}{\mathop{\unicode{x2A09}}\limits}}
151 \CustomizeMathJax{\newcommand{\modtwosum}{\mathop{\unicode{x2A0A}}\limits}}
152 \CustomizeMathJax{\newcommand{\sumint}{\mathop{\unicode{x2A0B}}\limits}}
153 \CustomizeMathJax{\newcommand{\intbar}{\mathop{\unicode{x2A0D}}\limits}}
154 \CustomizeMathJax{\newcommand{\intBar}{\mathop{\unicode{x2A0E}}\limits}}
155 \CustomizeMathJax{\newcommand{\fint}{\mathop{\unicode{x2A0F}}\limits}}
156 \CustomizeMathJax{\newcommand{\cirfnint}{\mathop{\unicode{x2A10}}\limits}}
157 \CustomizeMathJax{\newcommand{\awint}{\mathop{\unicode{x2A11}}\limits}}
158 \CustomizeMathJax{\newcommand{\rppolint}{\mathop{\unicode{x2A12}}\limits}}
159 \CustomizeMathJax{\newcommand{\scpolint}{\mathop{\unicode{x2A13}}\limits}}
160 \CustomizeMathJax{\newcommand{\npolint}{\mathop{\unicode{x2A14}}\limits}}
161 \CustomizeMathJax{\newcommand{\pointint}{\mathop{\unicode{x2A15}}\limits}}
162 \CustomizeMathJax{\newcommand{\sqint}{\mathop{\unicode{x2A16}}\limits}}
163 \CustomizeMathJax{\newcommand{\intlarhk}{\mathop{\unicode{x2A17}}\limits}}
164 \CustomizeMathJax{\newcommand{\intx}{\mathop{\unicode{x2A18}}\limits}}
165 \CustomizeMathJax{\newcommand{\intcap}{\mathop{\unicode{x2A19}}\limits}}
166 \CustomizeMathJax{\newcommand{\intcup}{\mathop{\unicode{x2A1A}}\limits}}
167 \CustomizeMathJax{\newcommand{\upint}{\mathop{\unicode{x2A1B}}\limits}}
168 \CustomizeMathJax{\newcommand{\lowint}{\mathop{\unicode{x2A1C}}\limits}}
169 \CustomizeMathJax{\newcommand{\bigtriangleleft}{\mathop{\unicode{x2A1E}}\limits}}
170 \CustomizeMathJax{\newcommand{\zcmp}{\mathop{\unicode{x2A1F}}\limits}}
171 \CustomizeMathJax{\newcommand{\zpipe}{\mathop{\unicode{x2A20}}\limits}}
172 \CustomizeMathJax{\newcommand{\zproject}{\mathop{\unicode{x2A21}}\limits}}
173 \CustomizeMathJax{\newcommand{\biginterleave}{\mathop{\unicode{x2AFC}}\limits}}
174 \CustomizeMathJax{\newcommand{\bigtalloblong}{\mathop{\unicode{x2AFF}}\limits}}
175 \CustomizeMathJax{\newcommand{\arabicmaj}{\mathop{\unicode{x1EEF0}}\limits}}
176 \CustomizeMathJax{\newcommand{\arabichad}{\mathop{\unicode{x1EEF1}}\limits}}
177
178 \end{warpMathJax}

```

---

## File 505 **lwarp-units.sty**

### § 611 Package **units**

*(Emulates or patches code by AXEL REICHERT.)*

Pkg units units is patched for use by lwarp.

Values are not styled by css, and take the style of the surrounding HTML text.

Units are styled according to the print version, so they will be forced to upright roman in HTML if the print version does so. It may be necessary to adjust the document's body css to match the print version.

**for HTML output:** 1 \LWR@ProvidesPackagePass{units}[1998/08/04]

```

2 \DeclareRobustCommand*{\LWR@HTML@unit}[2][]{%
3 \ifblank{#1}%
4 {\LWR@textcurrentfont{#2}}%
5 {%

```

```

6 #1%
7 \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,%
8 \LWR@textcurrentfont{#2}%
9 }%
10 }
11 \LWR@formatted{unit}

12 \DeclareRobustCommand*\LWR@HTML@unitfrac}[3][[]]{%
13 \ifblank{#1}%
14 {%
15 \nicefrac{#2}{#3}%
16 }%
17 {%
18 #1%
19 \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,%
20 \nicefrac{#2}{#3}%
21 }%
22 }
23
24 \LWR@formatted{unitfrac}

```

For Mathjax:

```

25 \begin{warpMathJax}
26 \CustomizeMathJax{\newcommand{\unit}[2][[]]{#1 \mathinner{#2}}}
27 \CustomizeMathJax{\newcommand{\unitfrac}[3][[]]{#1 \mathinner{{}^{\#2}\!/_{\#3}}}}
28 \end{warpMathJax}

```

---

File 506 **lwarp-unitsdef.sty**

§ 612 Package **unitsdef**

(Emulates or patches code by PATRICK HAPPEL.)

Pkg unitsdef unitsdef is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{unitsdef}[2005/01/04]

2 \renewcommand{\unitvaluesep}{\,%
3
4 \renewcommand{\unitittimes}{\@@setunitsepfalse\HTMLUnicode{22c5}}% \cdot
5
6 \renewunit{\arcmin}{%
7 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
8 {\ensuremath{{}^{\prime}}}%
9 {\HTMLUnicode{2032}}% prime
10 }
11
12 \renewunit{\arcsec}{%
13 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
14 {\ensuremath{{}^{\prime}\prime}}%
15 {\HTMLUnicode{2033}}% dbl prime

```

---

```

16 }
17
18 \renewrobustcmd{\SI}[2]{%
19 \begingroup%
20 \let\unit@@xspace\relax%
21 \unitSIdef\selectfont%
22 \LWR@textcurrentfont{#1#2}% lwarp
23 \endgroup%
24 }

```

---

File 507 **lwarp-upgreek.sty**

§ 613 Package **upgreek**

*(Emulates or patches code by WALTER SCHMIDT.)*

Pkg upgreek upgreek is used as-is for SVG math, and is emulated for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{upgreek}[2003/02/12]

For MATHJAX:

```

2 \LWR@origRequirePackage{lwarp-common-mathjax-letters}
3
4 \begin{warpMathJax}
5 \LWR@infoprocessingmathjax{upgreek}
6
7 \LWR@mathjax@addgreek@l@up{up}{}
8 \LWR@mathjax@addgreek@u@up{Up}{}
9
10 \end{warpMathJax}

```

---

File 508 **lwarp-upref.sty**

§ 614 Package **upref**

Pkg upref upref is ignored.

**for HTML output:** Discard all options for lwarp-upref:

```

1 \LWR@ProvidesPackageDrop{upref}[2007/03/14]

```

---

File 509 **lwarp-url.sty**

§ 615 Package **url**

*(Emulates or patches code by DONALD ARSENEAU.)*

Pkg url **url** is patched for use by **lwarp**.

**for HTML output:**

```

1 \LetLtxMacro\LWR@url@orig@url\LWR@url
2
3 \LWR@ProvidesPackagePass{url}[2013/09/16]

4 \newcommand*\LWR@HTML@Url@FormatString{%
5 \expandafter\LWR@url@orig@url\expandafter{\Url@String}%
6 }
7 \LWR@formatted{Url@FormatString}
```

---

File 510 **lwarp-ushort.sty**

§ 616 Package **ushort**

*(Emulates or patches code by MARTIN VÄTH.)*

Pkg ushort **ushort** is used as-is, and emulated for **MATHJAX**.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{ushort}[2001/06/13]

2 \begin{warpMathJax}
3 \CustomizeMathJax{\newcommand{\ushortdline}[1]{%
4 \kern{.1em}\underline{\underline{#1}}\kern{.1em}%
5 }}
6 \CustomizeMathJax{\newcommand{\ushort}[1]{\kern{.1em}\underline{#1}\kern{.1em}}}
7 \CustomizeMathJax{\newcommand{\ushortd}[1]{\ushortdline{#1}}}
8 \CustomizeMathJax{\newcommand{\ushortw}[1]{\kern{.1em}\underline{#1}\kern{.1em}}}
9 \CustomizeMathJax{\newcommand{\ushortdw}[1]{\ushortdline{#1}}}
10 \end{warpMathJax}
```

---

File 511 **lwarp-ospace.sty**

§ 617 Package **ospace**

Pkg ospace **ospace** is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{ospace}[2016/11/06]
```

---

File 512 **lwarp-varioref.sty**

§ 618 Package **varioref**

*(Emulates or patches code by FRANK MITTELBACH.)*

Pkg varioref **varioref** is patched for use by **lwarp**.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{varioref}[2020/01/23]
```

Page-related output is not used for HTML output.

```
2 \def\reftextfaceafter {\unskip}%
3 \def\reftextfacebefore{\unskip}%
4 \def\reftextafter {\unskip}%
5 \def\reftextbefore {\unskip}%
6 \def\reftextcurrent {\unskip}%
7 \def\reftextfaraway#1{\unskip}%
8 \def\reftextpagerange#1#2{\unskip}%
```

---

File 513 **lwarp-verse.sty**

§ 619 Package **verse**

(Emulates or patches code by PETER WILSON.)

Pkg verse **verse** is supported and patched by **lwarp**.

**for HTML output:** Pass all options for **lwarp-verse**:

```
1 \LWR@ProvidesPackagePass{verse}[2009/09/04]
```

When using **verse** or **memoir**, always place a `\\` after each line.

`\attrib` The documentation for the **verse** and **memoir** packages suggest defining an `\attrib` command, which may already exist in current documents, but it will only work for print output. **lwarp** provides `\attribution`, which works for both print and HTML output. To combine the two so that `\attrib` is used for print and `\attribution` is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len `\vleftskip` These lengths are used by **verse** and **memoir** to control the left margin, and they may already be set by the user for print output. New lengths `\HTMLvleftskip` and `\HTMLleftmargini` are provided to control the margins in HTML output. These new lengths may be set by the user before any **verse** environment, and persist until they are manually changed again. One reason to change `\HTMLleftmargini` is if there is a wide `\flagverse` in use, such as the word “Chorus”, in which case the value of `\HTMLleftmargini` should be set to a wide enough length to contain “Chorus”. The default is wide enough for a stanza number.

⚠ spacing Horizontal spacing relies on *pdftotext*’s ability to discern the layout (`-layout` option) of the text in the HTML-tagged PDF output. For some settings of `\HTMLleftmargini` or `\HTMLvleftskip` the horizontal alignment may not work out exactly, in which case a

⚠ **verse margin** label may be shifted by one space. During translation to HTML, the stanza numbers are kept out of the left margin, which would have caused *pdftotext* to shift everything over.

Env verse The verse environment will be placed inside a HTML <pre>.

```
2 \AfterEndPreamble{
3 \LWR@traceinfo{Patching verse.}
```

At the beginning of the verse environment:

```
4 \AtBeginEnvironment{verse}
5 {%
```

Use the original list environment inside a <pre> to attempt to preserve formatting.

```
6 \LWR@restoreoriglists%
```

Pkg verse The verse or memoir packages can place stanza numbers to the left with their  
Cls memoir \flagverse command. The following does not allow them to go into the left mar-  
\flagverse gin, which would cause *pdfcrop* to crop the entire page further to the left.

```
Len \vleftskip 7 \ifdef{\vleftskip}{%
8 \setlength{\vleftskip}{\HTMLvleftskip}
9 \setlength{\leftmargini}{\HTMLleftmargini}
10 }{}
11 \LWR@forcenewpage
12 \LWR@atbeginverbatim{verse}%
13 }
```

After the end of the verse environment, which places the <pre> tag at the regular left margin:

```
14 \AtEndEnvironment{verse}{%
15 \leavevmode%
16 \LWR@afterendverbatim%
17 }
```

Patch to place poemtitle inside an HTML <span> of class poemtitle:

```
18 \ifdef{\poemtitle}{
19 \DeclareDocumentCommand{\@vstypeptitle}{m}{%
20 \vspace{\beforepoemtitleskip}%
21 {\InlineClass{poemtitle}{\poemtitlefont #1}\par}%
22 \vspace{\afterpoemtitleskip}%
23 }
24 }{}
25
26 \LWR@traceinfo{Finished patching verse.}
27 }% AfterEndPreamble
```

---

File 514 **lwarp-versednotes.sty**

§ 620 Package **versednotes**

(Emulates or patches code by NORMAN GRAY.)

Pkg versonotes **versonotes** is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{versonotes}[2019/07/06]

2 \newcommand{\versonote}[1]{\marginpar{#1}}
3 \newdimen\versotextwidth
4 \newdimen\versoleftmargin
5 \newcommand*\versolayout{}
```

In case the user changed the page number before loading versonotes:

```
6 \setcounter{page}{1}
```

File 515 **lwarp-vertbars.sty**

§ 621 Package **vertbars**

*(Emulates or patches code by PETER WILSON.)*

Pkg vertbars **vertbars** is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{vertbars}[2010/11/27]

2 \newlength{\barwidth}
3 \setlength{\barwidth}{0.4pt}
4 \newlength{\barspace}
5 \setlength{\barspace}{1em}
6
7 \newenvironment{vertbar}{
8 \LWR@forcenewpage
9 \LWR@forceminwidth{\barwidth}
10 \begin{BlockClass}%
11 border-left: \LWR@printlength{\LWR@atleastonept} solid black ; %
12 padding-left: \LWR@printlength{\barspace}%
13]{vertbar}
14 }{
15 \end{BlockClass}
16 }
```

File 516 **lwarp-vmargin.sty**

§ 622 Package **vmargin**

Pkg vmargin **vmargin** is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{vmargin}[2004/07/15]

2 \newcommand*\LWRVM@customsize}[2]{}
3 \newcommand*\setpapersize}[2][\ifstrequal{#2}{custom}{\LWRVM@customsize}{}]
```

---

```

4 \newcommand*\setmargins[8]{}
5 \newcommand*\setmarginsrb[8]{}
6 \newcommand*\setmargnohf[4]{}
7 \newcommand*\setmargnohfrb[4]{}
8 \newcommand*\setmarg[4]{}
9 \newcommand*\setmargrb[4]{}
10 \newlength\PaperWidth
11 \setlength\PaperWidth{8.5in}
12 \newlength\PaperHeight
13 \setlength\PaperHeight{11in}
14 \newif\ifLandscape

```

---

File 517 **lwarp-vowel.sty**

§ 623 Package **vowel**

*(Emulates or patches code by FUKUI REI.)*

Pkg vowel **vowel** is patched for use by **lwarp**.

This package has been tested with *pdf<sub>l</sub>atex* and the Type 1 TIPA fonts using the following package load sequence:

```

\usepackage[T3,T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[noenc]{tipa}
\usepackage{vowel}

```

**for HTML output:** 1 \LWR@ProvidesPackagePass{vowel}[2002/08/08]

```

2 \renewenvironment{vowel}[1]{}
3 {%
4 \begin{lateximage}[-vowel-~\PackageDiagramAltText]%
5 \@vowel[#1]%
6 }
7 {%
8 \@@vowel%
9 \end{lateximage}%
10 }

```

---

File 518 **lwarp-vpe.sty**

§ 624 Package **vpe**

Pkg vpe **vpe** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{vpe}[2012/04/18]

File 519 **lwarp-vwcol.sty**

§ 625 Package **vwcol**

(Emulates or patches code by WILL ROBERTSON.)

Pkg vwcol vwcol is patched for use with lwarp.

The width option is ignored. All vwcol environments adjust to 1–3 equal-width columns, depending on the width of the browser window.

The remaining options are supported, except for lines and maxrecursion.

**for HTML output:** 1 \LWR@ProvidesPackagePass{vwcol}[2015/02/10]

Factored from \vwcol. Each is given a style tag to append to the final style.

```
\LWR@vwcol@addrule {<style tag>}
2 \newcommand*{\LWR@vwcol@addrule}[1]{%
3 \appto{\LWR@vwcolstyle}{%
4 #1: %
5 \LWR@printlength{\vwcol@rule} solid \LWR@origpound\LWR@vwcol@rulecolor ; %
6 }%
7 }
```

```
\LWR@vwcol@addrule {<style tag>}
8 \newcommand*{\LWR@vwcol@addgap}[1]{%
9 \appto{\LWR@vwcolstyle}{%
10 #1: %
11 \LWR@printlength{\vwcol@sep} ; %
12 }%
13 }
```

Env vwcol {<key/values>}

Redefine the environment to add a HTML style. The style is built depending on the required options.

```
14 \renewenvironment*{vwcol}[1][1]{%
```

New paragraph, and process the options:

```
15 \LWR@stoppars%
16 \vwcolsetup{#1}%
```

Begin with no style:

```
17 \newcommand*{\LWR@vwcolstyle}{}
```

presep and postsep are created with HTML margins:

```

18 \if@vwcol@presep
19 \appto{\LWR@vwcolstyle}{margin-left: 1em ; padding-left: .5em ; }
20 \fi
21 \if@vwcol@postsep
22 \appto{\LWR@vwcolstyle}{margin-right: 1em ; padding-right: .5em ; }
23 \fi

```

sep becomes column-gap:

```

24 \ifdimgreater{\vwcol@sep}{1sp}{
25 \LWR@vwcol@addgap{column-gap}
26 \LWR@vwcol@addgap{-moz-column-gap}
27 \LWR@vwcol@addgap{-webkit-column-gap}
28 }{}

```

rule become column-rule, while prerule and postrule become HTML borders:

```

29 \convertcolorspec{named}{\vwcol@rulecol}{HTML}\LWR@vwcol@rulecolor%
30 \ifdimgreater{\vwcol@rule}{0pt}{
31 \ifdimless{\vwcol@rule}{1pt}{
32 \setlength{\vwcol@rule}{1pt}
33 }{}
34 \LWR@vwcol@addrule{column-rule}
35 \LWR@vwcol@addrule{-moz-column-rule}
36 \LWR@vwcol@addrule{-webkit-column-rule}
37 \if@vwcol@prerule\LWR@vwcol@addrule{border-left}\fi
38 \if@vwcol@postrule\LWR@vwcol@addrule{border-right}\fi
39 }{}

```

Each of the justify options becomes a text-align. Indentation is added where appropriate.

```

40 \ifdefequal{\vwcol@justify}{\RaggedRight}{
41 \appto{\LWR@vwcolstyle}{text-align: left ; }
42 \ifdimgreater{\vwcol@parindent}{0pt}{
43 \appto{\LWR@vwcolstyle}{%
44 text-indent: \LWR@printlength{\vwcol@parindent} ; %
45 }
46 }{}
47 }{}

48 \ifdefequal{\vwcol@justify}{\RaggedLeft}{
49 \appto{\LWR@vwcolstyle}{text-align: right ; }
50 }{}

51 \ifdefequal{\vwcol@justify}{\Centering}{
52 \appto{\LWR@vwcolstyle}{text-align: center ; }
53 }{}

54 \ifdefequal{\vwcol@justify}{\justifying}{
55 \appto{\LWR@vwcolstyle}{text-align: justify ; }
56 \ifdimgreater{\vwcol@parindent}{0pt}{
57 \appto{\LWR@vwcolstyle}{%
58 text-indent: \LWR@printlength{\vwcol@parindent} ; %
59 }
60 }{}
61 }{}

```

Create the <div> with the assembled style:

```
62 \BlockClass[\LWR@vwcolstyle]{multicols}
63 }
```

When the environment ends:

```
64 {
65 \endBlockClass
66 \LWR@startpars
67 }
```

File 520 **lwarp-wallpaper.sty**

§ 626 Package **wallpaper**

*(Emulates or patches code by MICHAEL H.F. WILKINSON.)*

Pkg wallpaper **wallpaper** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{wallpaper}[2005/01/18]

```
2 \newcommand*\CenterWallPaper}[2]{}
3 \newcommand*\ThisCenterWallPaper}[2]{}
4 \newcommand*\TileWallPaper}[3]{}
5 \newcommand*\ThisTileWallPaper}[3]{}
6 \newcommand*\TileSquareWallPaper}[2]{}
7 \newcommand*\ThisTileSquareWallPaper}[2]{}
8 \newcommand*\ULCornerWallPaper}[2]{}
9 \newcommand*\ThisULCornerWallPaper}[2]{}
10 \newcommand*\LLCornerWallPaper}[2]{}
11 \newcommand*\ThisLLCornerWallPaper}[2]{}
12 \newcommand*\URCornerWallPaper}[2]{}
13 \newcommand*\ThisURCornerWallPaper}[2]{}
14 \newcommand*\LRCornerWallPaper}[2]{}
15 \newcommand*\ThisLRCornerWallPaper}[2]{}
16 \newcommand*\ClearWallPaper[1]{}
17 \newlength\wpXoffset
18 \newlength\wpYoffset
```

File 521 **lwarp-watermark.sty**

§ 627 Package **watermark**

*(Emulates or patches code by ALEXANDER I. ROZHENKO.)*

Pkg watermark **watermark** is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{watermark}[2004/12/09]

```
2 \newcommand\watermark[1]{}
3 \newcommand\leftwatermark[1]{}
4 \newcommand\rightwatermark[1]{}

```

---

```
5 \newcommand{\thiswatermark}[1]{ }
6 \newcommand{\thispageheading}[1]{ }
```

---

File 522 **lwarp-widetable.sty**

§ 628 Package **widetable**

(Emulates or patches code by CLAUDIO BECCARI.)

Pkg widetable widetable is emulated.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{widetable}[2019-06-25]

```
2 \newenvironment{widetable}{\begin{tabular*}}{\end{tabular*}}
```

---

File 523 **lwarp-widows-and-orphans.sty**

§ 629 Package **widows-and-orphans**

Pkg widows-and-orphans widows-and-orphans is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{widows-and-orphans}[2018/09/01]

```
2 \NewDocumentCommand\Wa0setup{m}{ }
3 \NewDocumentCommand\Wa0parameters{ }{ }
4 \NewDocumentCommand\Wa0ignorenext{ }{ }
```

---

File 524 **lwarp-witharrows.sty**

§ 630 Package **witharrows**

(Emulates or patches code by F. PANTIGNY.)

Pkg witharrows witharrows is patched for use by lwarp. Emulation is provided for MATHJAX.

**for HTML output:** 1 \LWR@ProvidesPackagePass{witharrows}[2019/12/27]

```
2 \ifbool{mathjax}{
3 % For the hidden print version in the HTML:
4 \newcommand{\Arrow}[2][]{ }
5 \newcommand{\unicode}[1]{ }
6 \NewDocumentEnvironment { DispWithArrows } { ! d < > ! 0 { } +b }
7 {
8 \IfValueTF{#1}{
9 \begin{displaymath}
10 #1 \left\lbracket
```

```

11 \begin{align}
12 #3
13 \end{align}
14 \right .
15 \end{displaymath}
16 }{
17 \begin{displaymath}
18 \begin{align}
19 #3
20 \end{align}
21 \end{displaymath}
22 }
23 }
24 {}
25 \NewDocumentEnvironment { DispWithArrows* } { ! d < > ! 0 { } +b}
26 {
27 \IfValueTF{#1}{
28 \begin{displaymath}
29 #1 \left\lbracket
30 \begin{align*}
31 #3
32 \end{align*}
33 \right .
34 \end{displaymath}
35 }{
36 \begin{displaymath}
37 \begin{align*}
38 #3
39 \end{align*}
40 \end{displaymath}
41 }
42 }
43 {}
44 }{
45 % If not MathJax, use SVG images.
46 \BeforeBeginEnvironment{WithArrows}{\global\booltrue{LWR@unknownmathsize}}
47 \BeforeBeginEnvironment{DispWithArrows}{%
48 \begin{BlockClass}{displaymathnumbered}%
49 \begin{lateximage}%
50 }
51 \AfterEndEnvironment{DispWithArrows}{\end{lateximage}\end{BlockClass}}
52 \BeforeBeginEnvironment{DispWithArrows*}{%
53 \begin{BlockClass}{displaymath}%
54 \begin{lateximage}%
55 }
56 \AfterEndEnvironment{DispWithArrows*}{\end{lateximage}\end{BlockClass}}
57 }
58
59 \begin{warpMathJax}
60 \CustomizeMathJax{\newenvironment{WithArrows}[1][\begin{aligned}]{\end{aligned}}}
61 % Unable to make a sized box.
62 \CustomizeMathJax{\newcommand{\Arrow}[2][\&{\Large\unicode{x2938}}~\textit{#2}}}
63 \end{warpMathJax}

```

File 525 **lwarp-wrapfig.sty**

§ 631 Package **wrapfig**

(Emulates or patches code by DONALD ARSENEAU.)

Pkg wrapfig **wrapfig** is emulated.

```

for HTML output: 1 \LWR@ProvidesPackageDrop{wrapfig}[2003/01/31]

2 \newcommand*\LWR@wrapposition{}
3
4 \newcommand*\LWR@subwrapfigure}[2]{%
5 \renewcommand*\LWR@wrapposition{}%
6 \ifthenelse{%
7 \equal{#1}{r}\OR\equal{#1}{R}\OR%
8 \equal{#1}{o}\OR\equal{#1}{O}%
9 }%
10 {\renewcommand*\LWR@wrapposition}{float:right}}%
11 {\renewcommand*\LWR@wrapposition}{float:left}}%
12 \setlength{\LWR@templengthone}{#2}%
13 \LWR@BlockClassWP{%
14 width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
15 margin:10pt%
16 }%
17 {%
18 width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
19 }%
20 {marginblock}%

21 \setlength{\linewidth}{\LWR@templengthone}%
22 }
23
24
25 \NewDocumentEnvironment{wrapfigure}{o m o m}
26 {%
27 \begin{LWR@setvirtualpage}*%
28 \LWR@subwrapfigure{#2}{#4}%
29 \renewcommand*\@capttype{figure}%
30 }
31 {%
32 \endLWR@BlockClassWP%
33 \end{LWR@setvirtualpage}%
34 }
35
36
37 \NewDocumentEnvironment{wraptable}{o m o m}
38 {%
39 \begin{LWR@setvirtualpage}*%
40 \LWR@subwrapfigure{#2}{#4}%

```

```

41 \renewcommand*\@capttype{table}%
42 }
43 {%
44 \endLWR@BlockClassWP%
45 \end{LWR@setvirtualpage}%
46 }
47
48
49 \NewDocumentEnvironment{wrapfloat}{m o m o m}
50 {%
51 \begin{LWR@setvirtualpage}*%
52 \LWR@subwrapfigure{#3}{#5}%
53 \renewcommand*\@capttype{#1}%
54 }
55 {%
56 \endLWR@BlockClassWP%
57 \end{LWR@setvirtualpage}%
58 }
59
60 \newlength{\wrapoverhang}

```

---

File 526 **lwarp-xbmk.s sty**

§ 632 Package **xbmks**

Pkg xbmks xbmks is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{xbmks}[2018/07/04]

```

2 \newcommand{\xbmksetup}[1]{}
3 \NewDocumentCommand{\pdfbookmarkx}{o m o m}{}
4 \NewDocumentCommand{\currentpdfbookmarkx}{m o m}{}
5 \NewDocumentCommand{\subpdfbookmarkx}{m o m}{}
6 \NewDocumentCommand{\belowpdfbookmarkx}{m o m}{}

```

---

File 527 **lwarp-xcolor.s sty**

§ 633 Package **xcolor**

*(Emulates or patches code by DR. UWE KERN.)*

Pkg xcolor xcolor is supported by lwarp.

### § 633.1 **Limitations**

|                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\colorboxBlock</code> and <code>\fcolorboxBlock</code> | <code>\colorboxBlock</code> and <code>\fcolorboxBlock</code> are provided for increased HTML compatibility, and they are identical to <code>\colorbox</code> and <code>\fcolorbox</code> in print mode. In HTML mode they place their contents into a <code>&lt;div&gt;</code> instead of a <code>&lt;span&gt;</code> . These <code>&lt;div&gt;</code> s are set to <code>display: inline-block</code> so adjacent <code>\colorboxBlock</code> s appear side-by-side in HTML, although text is placed before or after each. |
|                                                              | Print-mode definitions for <code>\colorboxBlock</code> and <code>\fcolorboxBlock</code> are created by <code>lwarp</code> 's core if <code>xcolor</code> is loaded.                                                                                                                                                                                                                                                                                                                                                         |
| <code>background: none</code>                                | <code>\colorbox</code> and <code>\fcolorboxBlock</code> allow a background color of <code>none</code> , in which case only the frame is drawn, which can be useful for HTML.                                                                                                                                                                                                                                                                                                                                                |
| <code>color support</code>                                   | Color definitions, models, and mixing are fully supported without any changes required.                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <code>colored tables</code>                                  | <code>\rowcolors</code> is supported, except that the optional argument is ignored so far.                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <code>colored text and boxes</code>                          | <code>\textcolor</code> , <code>\colorbox</code> , and <code>\fcolorbox</code> are supported.                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <code>\color</code> and <code>\pagecolor</code>              | <code>\color</code> and <code>\pagecolor</code> are ignored. Use <code>css</code> or <code>\textcolor</code> where possible.                                                                                                                                                                                                                                                                                                                                                                                                |

### § 633.2 **xcolor definitions: location and timing**

The `lwarp` core and its `lwarp-xcolor` package are tightly integrated to allow comparable results for print, HTML, and print inside an HTML `lateximage`. This requires a number of definitions and redefinitions depending on whether each of `xcolor` and `lateximage` is being used, and whether print or HTML is being generated. Some of these actions are one-time when `xcolor` is loaded, and others are temporary as `lateximage` is used.

**When `xcolor` is loaded in print mode:** No special actions are taken at the time that `xcolor` is loaded in print mode, but see `\AtBeginDocument` below.

**When `lwarp-xcolor` is loaded in HTML mode:** `xcolor`'s original definitions are saved for later restoration. `\LWR@restoreorigformatting` is appended to restore these definitions for use inside a `lateximage`. New HTML-mode definitions are created for `\textcolor`, `\pagecolor`, `\nopagecolor`, `\colorbox`, `\colorboxBlock`, `\fcolorbox`, `\fcolorboxBlock`, and `fcolorminipage`.

**`\AtBeginDocument` in print or HTML mode:** See Section 87. If `xcolor` has been loaded, the print-mode `\fcolorbox` is modified to accept a background color of `none`, and additional definitions are created for `lwarp`'s new macros print-mode macros `\colorboxBlock`, `\fcolorboxBlock`, and `fcolorminipage`. The HTML versions of these macros will already have been created by `lwarp-xcolor` if it has been loaded.

For use inside an HTML `lateximage`, `\LWR@restoreorigformatting` is appended to temporarily set these functions to their print-mode versions.

**In a `lateximage` in HTML mode:** `\LWR@restoreorigformatting` temporarily restores the print-mode definitions of `xcolor`'s functions. See `\LWR@restoreorigformatting` on page 542.

**`\color`:**

**Print:** Used as-is.  
**HTML:** Ignored by *pdftotext*, and will not appear.  
**HTML lateximage:** Colors will appear in a lateximage.

**\textcolor:**

**Print:** Used as-is.  
**HTML:** Redefined by *lwarp-xcolor*, page 1206.  
**HTML lateximage:** Remembers and reuses the print version.

**\pagecolor:**

**Print:** Used as-is.  
**HTML:** Ignored.  
**HTML lateximage:** Colors will be picked up in a lateximage.

**\nopagecolor:**

**Print:** Used as-is.  
**HTML:** Ignored.  
**HTML lateximage:** Colors will be picked up in a lateximage.

**\colorbox:**

**Print:** Used as-is.  
**HTML:** Redefined by *lwarp-xcolor*, page 1207.  
**HTML lateximage:** Remembers and reuses the print version.

**\colorboxBlock:**

**Print:** Becomes `\colorbox`.  
**HTML:** Newly defined by *lwarp-xcolor* to use a `<div>`, page 1207.  
**HTML lateximage:** Remembers and reuses the print version `\colorbox`.

**\fcolorbox:**

**Print:** Modified to allow a background of none.  
`\LWR@print@fcolorbox` at section 87  
**HTML:** Redefined by *lwarp-xcolor*, page 1207.  
**HTML lateximage:** Remembers and reuses the print version.

**\fcolorboxBlock:**

**Print:** Becomes `\fcolorbox`. Section 87  
**HTML:** Newly defined by *lwarp-xcolor* to use a `<div>`, page 1208.  
**HTML lateximage:** Remembers and reuses the print version `\fcolorbox`.

**fcolorminipage:**

**Print:** Newly defined in the *lwarp* core.  
`\LWR@print@fcolorminipage` at section 87

**HTML:** Newly defined by `lwarp-xcolor`, page 1209.

**HTML lateximage:** Uses the print version.

**\boxframe:**

**Print:** Used as-is.

**HTML:** Redefined by `lwarp-xcolor`, page 1210.

**HTML lateximage:** Remembers and reuses the print version.

### § 633.3 Package loading

**for HTML output:** `1 \LWR@ProvidesPackagePass{xcolor}[2016/05/11]`

### § 633.4 Remembering and restoring original definitions

Remember the following print-mode actions to be restored when inside a `lateximage` environment:

```
2 \LetLtxMacro\LWR@print@pagecolor\pagecolor
3 \LetLtxMacro\LWR@print@npagecolor\npagecolor
```

`\LWR@restoreorigformatting` Inside a `lateximage` the following gets restored to their print-mode actions:

```
4 \appto\LWR@restoreorigformatting{%
5 \LetLtxMacro\pagecolor\LWR@print@pagecolor%
6 \LetLtxMacro\npagecolor\LWR@print@npagecolor%
7 }
```

### § 633.5 \normalcolor

`\normalcolor`

```
8 \DeclareRobustCommand{\LWR@HTML@normalcolor}{\color{black}}%
9
10 \LWR@formatted{normalcolor}
```

### § 633.6 HTML color style

`\LWR@findcurrenttextcolor` Sets `\LWR@tempcolor` to the current color.

```
11 \renewcommand*{\LWR@findcurrenttextcolor}{%
12 \protect\colorlet{\LWR@current@color}{.}%
13 \protect\convertcolorspec{named}{\LWR@current@color}{HTML}\LWR@tempcolor%
14 }
```

Prints a color style for the current color.

`\LWR@currenttextcolorstyle`

```
15 \newcommand*{\LWR@currenttextcolorstyle}{%
16 \LWR@findcurrenttextcolor%
17 \ifdefstring{\LWR@tempcolor}{000000}%
18 {}%
19 {color: \LWR@origpound\LWR@tempcolor ; }%
20 }
```

`\LWR@textcurrentcolor`  $\{\langle text \rangle\}$  Like `\textcolor` but uses the current `\color` instead.

```

21 \DeclareDocumentCommand{\LWR@textcurrentcolor}{m}{%
22 \begingroup%
23 \LWR@FBcancel%
24 \LWR@findcurrenttextcolor%
25 \InlineClass[color:\LWR@origpound\LWR@tempcolor]{textcolor}{%
26 \renewcommand*\LWR@currenttextcolor{\LWR@origpound\LWR@tempcolor}%
27 #1%
28 }%
29 \endgroup%
30 }
```

`\LWR@colorstyle`  $\{\langle 1: model \rangle\} \{\langle 2: color \rangle\}$

For a color style, prints the color converted to HTML colors.

```

31 \NewDocumentCommand{\LWR@colorstyle}{m m}{%
32 \begingroup%
33 \LWR@FBcancel%
```

Use the `xcolor` package to convert to an HTML color space:

```

34 \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```

35 \LWR@origpound\LWR@tempcolor%
36 \endgroup%
37 }
```

`\LWR@backgroundcolor`  $[\langle model \rangle] \{\langle color \rangle\} \{\langle text \rangle\}$

Similar to `\textcolor`, but prints black text against a color background.

Converted into an HTML hex color span.

```

38 \NewDocumentCommand{\LWR@backgroundcolor}{O{named} m m}{%
39 \begingroup%
40 \LWR@FBcancel%
41 \InlineClass[background:\LWR@colorstyle{#1}{#2}]{backgroundcolor}{%
42 #3%
43 }%
44 \endgroup%
45 }
```

§ 633.7 **HTML border**

`\LWR@borderpadding`  $\{\langle colorstyle \rangle\} \{\langle color \rangle\}$  Prints the HTML attributes for a black border and padding. `\LWR@forceminwidth` must be used first in order to set the border width.

```
46 \newcommand*\LWR@borderpadding[2]{%
47 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
48 padding:\LWR@printlength{\fboxsep}%
49 }
```

§ 633.8 **High-level macros**

`\color`  $[\langle model \rangle] \{\langle color \rangle\}$



The current `\color` is used by HTML rules and frames, but does not affect the current HTML text output, due to the lack of HTML states and scoping limitations. Use `\textcolor` if possible.

```
50 \NewDocumentCommand{\LWR@HTML@color}{o m}{%
51 \IfValueTF{#1}{%
52 \LWR@print@color[#1]{#2}%
53 \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
54 }{%
55 \LWR@print@color{#2}%
56 \convertcolorspec{named}{#2}{HTML}\LWR@tempcolor%
57 }%
58 \edef\LWR@currenttextcolor{\LWR@origpound\LWR@tempcolor}%
59 }
60
61 \LWR@formatted{color}
```

`\textcolor`  $[\langle model \rangle] \{\langle color \rangle\} \{\langle text \rangle\}$

Converted into an HTML hex color span.

```
62 \NewDocumentCommand{\LWR@HTML@textcolor}{o m m}{%
63 \begingroup%
64 \LWR@FBCancel%
65 \IfValueTF{#1}{%
66 \color[#1]{#2}%
67 }{%
68 \color{#2}%
69 }%
70 \InlineClass[color:\LWR@currenttextcolor]{textcolor}{#3}%
71 \endgroup%
72 }%
73
74 \LWR@formatted{textcolor}
```

`\pagecolor`  $[\langle model \rangle] \{\langle color \rangle\}$

Ignored. Use CSS instead.

```
75 \renewcommand*\pagecolor[2][named]{}
```

`\nopagecolor` Ignored.

```
76 \renewcommand*{\nopagecolor}{}
```

`\colorbox` [*model*] {*color*} {*text*}

Converted into an HTML hex background color `<span>`.

```
77 \NewDocumentCommand{\LWR@HTML@colorbox}{O{named} m +m}{%
78 \begingroup%
79 \LWR@FBcancel%
80 \InlineClass[%
81 background:\LWR@colorstyle{#1}{#2} ; %
82 padding:\LWR@printlength{\fboxsep}%
83]{colorbox}{#3}%
84 \endgroup%
85 }
86
87 \AtBeginDocument{
88 \LWR@formatted{colorbox}
89 }
```

`\colorboxBlock` [*model*] {*color*} {*text*}

Converted into an HTML hex background color `<div>`.

```
90 \NewDocumentCommand{\LWR@HTML@colorboxBlock}{O{named} m +m}{%
91 \begingroup%
92 \LWR@FBcancel%
93 \LWR@stoppars%
94 \begin{BlockClass}[%
95 background:\LWR@colorstyle{#1}{#2} ; %
96 padding:\LWR@printlength{\fboxsep}%
97]{colorboxBlock}
98 #3
99 \end{BlockClass}%
100 \endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
101 \global\booltrue{LWR@minipagethispar}%
102 }
103
104 \AtBeginDocument{
105 \LWR@formatted{colorboxBlock}
106 }
```

`\fcolorbox` [*framemodel*] {*framecolor*} [*boxmodel*] {*boxcolor*} {*text*}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

107 \NewDocumentCommand{\LWR@HTML@fcolorbox}{O{named} m O{#1} m +m}{%
108 \LWR@traceinfo{HTML fcolorbox #2 #4}%
109 \begingroup%
110 \LWR@FBcancel%
111 \LWR@forceminwidth{\fboxrule}%
112 \ifthenelse{\equal{#4}{none}}{%
113 {% no background color
114 \InlineClass[%
115 \LWR@borderpadding{#1}{#2}%
116]{fcolorbox}{#5}%
117 }%
118 {% yes background color
119 \InlineClass[%
120 \LWR@borderpadding{#1}{#2} ; %
121 background:\LWR@colorstyle{#3}{#4}%
122]{fcolorbox}{#5}%
123 }%
124 \endgroup%
125 }
126
127 \AtBeginDocument{
128 \LWR@formatted{fcolorbox}
129 }

```

`\fcolorboxBlock` [*framemodel*] {*framecolor*} [*boxmodel*] {*boxcolor*} {*text*}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```

130 \NewDocumentCommand{\LWR@HTML@fcolorboxBlock}{O{named} m O{#1} m +m}{%
131 \LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
132 \begingroup%
133 \LWR@FBcancel%
134 \LWR@forceminwidth{\fboxrule}%

135 \LWR@stoppars%

136 \ifthenelse{\equal{#4}{none}}{%
137 {% no background color
138 \begin{BlockClass}[%
139 \LWR@borderpadding{#1}{#2}%
140]{fcolorboxBlock}
141 #5
142 \end{BlockClass}%
143 }%
144 {% yes background color

```

```

145 \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
146 \begin{BlockClass}[%
147 background:\LWR@origpound\LWR@tempcolortwo\ ; %
148 \LWR@borderpadding{#1}{#2}%
149]{fcolorboxBlock}
150 #5
151 \end{BlockClass}%
152 }%
153 \endgroup%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

154 \global\booltrue{LWR@minipagethispar}%
155 \LWR@traceinfo{HTML fcolorboxBlock done}%
156 }
157
158 \AtBeginDocument{
159 \LWR@formatted{fcolorboxBlock}
160 }

```

Creates a framed HTML <div> around its contents.

A print-output version is defined in the lwarp core: section 87

```

\LWR@subfcolorminipage {<framemodel>} {<framecolor>} {<background tag>} {<height>}
161 \NewDocumentCommand{\LWR@subfcolorminipage}{m m m m}{%
162 \LWR@stoppars%
163 \begin{BlockClass}[%
164 #3%
165 \LWR@borderpadding{#1}{#2} ; %
166 \IfValueT{#4}{height:\LWR@printlength{\LWR@tempheight} ; }%
167 width:\LWR@printlength{\LWR@tempwidth}%
168]{fcolorminipage}%
169 }

```

```

Env fcolorminipage [<1:framemodel>] { <2:framecolor> } [<3:boxmodel>] { <4:boxcolor> } [<5:align>] [<6:height>]
[<7:inner-align>] { <8:width> }

```

```

170 \NewDocumentEnvironment{LWR@HTML@fcolorminipage}{O{named} m O{#1} m O{c} o o m}
171 {%
172 \LWR@FBcancel%
173 \setlength{\LWR@tempwidth}{#8}%
174 \IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
175 \LWR@forceminwidth{\fboxrule}%
176 \convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
177 \ifthenelse{\equal{#4}{none}}%
178 {\LWR@subfcolorminipage{#1}{#2}{#6}}%
179 {%
180 \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%

```

```

181 \LWR@subfcolorminipage{#1}{#2}%
182 {background:\LWR@origpound\LWR@tempcolortwo\ ; }%
183 {#6}%
184 }%
185 }%
186 {%
187 \end{BlockClass}%

```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```

188 \global\booltrue{LWR@minipagethispar}%
189 }
190
191 \AtBeginDocument{
192 \LWR@formattedenv{fcolorminipage}
193 }

```

`\boxframe`  $\langle width \rangle$   $\langle height \rangle$   $\langle depth \rangle$

The depth is added to the height, but the box is not decended below by the depth. `\textcolor` is honored.

```

194 \newcommand*{\LWR@HTML@boxframe}[3]{%
195 {%
196 \setlength{\LWR@tempwidth}{#1}%
197 \setlength{\LWR@tempheight}{#2}%
198 \addtolength{\LWR@tempheight}{#3}%
199 \LWR@forceminwidth{\fboxrule}%
200 \LWR@findcurrenttextcolor%
201 \InlineClass[%
202 display:inline-block ; %
203 border:\LWR@printlength{\LWR@atleastonept} solid \LWR@currenttextcolor{} ; %
204 width:\LWR@printlength{\LWR@tempwidth} ; %
205 height:\LWR@printlength{\LWR@tempheight}%
206]{boxframe}{}%
207 }%
208 }
209
210 \LWR@formatted{boxframe}

```

### § 633.9 Row colors

`\rowcol@l@rs` [ $\langle cmds \rangle$ ]  $\langle startrow \rangle$   $\langle odd color \rangle$   $\langle even color \rangle$

```

211 \newcommand*{\LWR@xcolortempcolor}{}
212
213 \def\rowcol@l@rs[#1]#2#3#4%
214 {
215 \rownum=1%
216 \@rowcolorstrue%
217 \@ifxempty{#3}%
218 {\def\@oddrowcolor{\@norowcolor}}%

```

```

219 {%
220 \convertcolorspec{named}{#3}{HTML}\LWR@xcolortempcolor%
221 \edef\@oddrowcolor{%
222 \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
223 }%
224 }%
225 \@ifxempty{#4}%
226 {\def\@evenrowcolor{\@norowcolor}}%
227 {%
228 \convertcolorspec{named}{#4}{HTML}\LWR@xcolortempcolor%
229 \edef\@evenrowcolor{%
230 \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
231 }%
232 }%
233 \if@rowcmd
234 \def\@rowcolors
235 {%
236 % #1%
237 \if@rowcolors
238 % \noalign{%
239 % \relax\ifnum\rownum<#2\@norowcolor\else
240 % \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi\fi%
241 % }%
242 \fi%
243 }%
244 \else
245 \def\@rowcolors
246 {%
247 \if@rowcolors
248 % \ifnum\rownum<#2%
249 % \noalign{%
250 % \@norowcolor
251 % }
252 % \else
253 % #1%
254 % \noalign{%
255 % \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi%
256 % }%
257 % \fi
258 % \fi%
259 }%
260 \fi
261 \ignorespaces%
262 }

```

`\@norowcolor` Turns off color for this row.

```

263 \def\@norowcolor{%
264 \renewcommand{\LWR@xcolorrowHTMLcolor}{}%
265 }

```

`\@rowc@lors` Executed at the end of each row.

```

266 \def\@rowc@lors{%
267 % \noalign{%

```

```

268 \advance\rownum\@ne%
269 % }%
270 \@rowcolors%
271 }

```

---

File 528 **lwarp-xexchangebar.sty**

§ 634 Package **xexchangebar**

Pkg xexchangebar xexchangebar is ignored

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{xexchangebar}[2017/08/03]
2 \LWR@origRequirePackage{lwarp-changebar}

```

---

File 529 **lwarp-xellipsis.sty**

§ 635 Package **xellipsis**

*(Emulates or patches code by DONALD P. GOODMAN III.)*

Pkg xellipsis xellipsis is patched for use by lwarp.

When non-zero, each of the spaces is converted to an HTML thin unbreakable space.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{xellipsis}[2015/11/01]
2 \newcommand*{\LWR@xellipsespace}[1]{%
3 \ifdim#1=0pt\else%
4 \ifdim#1<\fontdimen2\font%
5 \,%
6 \else%
7 ~%
8 \fi%
9 \fi%
10 }
11
12 \def\xelip{%
13 \mbox{%
14 \LWR@xellipsespace{\xelipprebef}%
15 \xelipprechar%
16 \LWR@xellipsespace{\xelippreaft}%
17 \LWR@xellipsespace{\xelipbef}%
18 \xelipchar%
19 \xel@loopi = 1%
20 \loop\ifnum\xelipnum>\xel@loopi%
21 \advance\xel@loopi by1%
22 \LWR@xellipsespace{\xelipgap}%
23 \xelipchar%
24 \repeat%
25 \LWR@xellipsespace{\xelipaft}%

```

```

26 \LWR@xellipsespace{\xelippostbef}%
27 \xelippostchar%
28 \LWR@xellipsespace{\xelippostaft}%
29 }%
30 }%

```

---

File 530 **lwarp-xetexko-vertical.sty**

§ 636 Package **xetexko-vertical**

*(Emulates or patches code by DOHYUN KIM.)*

Pkg xetexko-vertical xetexko-vertical is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@loadbefore{xetexko-vertical}
2
3 \LWR@ProvidesPackagePass{xetexko-vertical}[2018/04/06]

4 \renewcommand{\verticaltypesetting}{}
5 \renewenvironment{vertical}[1]{\BlockClass{verticalrl}}{\endBlockClass}
6 \renewenvironment{horizontal}[1]{\BlockClass{horizontaltb}}{\endBlockClass}
7 \renewcommand{\vertlatin}[1]{#1}

```

---

File 531 **lwarp-xfakebold.sty**

§ 637 Package **xfakebold**

*(Emulates or patches code by HERBERT VOSS.)*

Pkg xfakebold xfakebold is patched for use by lwarp, and additional underlying support is found in the lwarp core.

 **text mode** xfakebold is only used in svg math and lateximages. Text mode is not set bold, but `\setBold` in text will be applied to any following svg math.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{xfakebold}[2020/06/24]

2 \newcommand*\LWR@HTML@setBold{\booltrue{LWR@xfakebold}}
3 \LWR@formatted{setBold}
4
5 \newcommand*\LWR@HTML@unsetBold{\boolfalse{LWR@xfakebold}}
6 \LWR@formatted{unsetBold}
7
8 \renewcommand*\LWR@applyxfakebold{%
9 \ifbool{LWR@xfakebold}{\LWR@print@setBold}{\LWR@print@unsetBold}%
10 }

```

For MATHJAX, xfakebold is ignored.

```

11 \begin{warpMathJax}
12 \CustomizeMathJax{\newcommand{\setBold}[1][{}]}
13 \CustomizeMathJax{\newcommand{\unsetBold}{}]}
14 \end{warpMathJax}

```

File 532 **lwarp-xfrac.sty**

§ 638 Package **xfrac**

(Emulates or patches code by THE L<sup>A</sup>T<sub>E</sub>X3 PROJECT.)

Pkg xfrac Supported by adding xfrac instances, and emulated for MATHJAX.

for HTML output: 1 \LWR@ProvidesPackagePass{xfrac}[2018-08-23]

⚠ font size

In the user's document preamble, `lwarp` should be loaded after font-related setup. During HTML conversion, this font is used by `lwarp` to generate its initial PDF output containing HTML tags, later to be converted by `pdftotext` to a plain text file. While the text may be in any font which `pdftotext` can read, the math is directly converted into SVG images using this same user-selected font. `xfrac` below is set for the Latin Modern (`lmr`) font. If another font is used, it may be desirable to redefine `\xfracHTMLfontsize` with a different em size.

`\sfrac` [*instance*] {*num*} [*sep*] {*denom*}

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in HTML tags. `\scalebox` is made null inside the numerator and denominator, since the HTML tags should not be scaled, and we do not want to introduce additional HTML tags for scaling.

In math mode, which will appear inside a `lateximage`, no adjustments are necessary.

`\xfracHTMLfontsize` User-redefinable macro which controls the font size of the fraction.

```
2 \newcommand*{\xfracHTMLfontsize}{.6em}
```

instances Instances of `xfrac` for various font choices:

Produce CSS for a small raised numerator and a small denominator.

Scaling is turned off so that `pdftotext` correctly reads the result.

```

3 \DeclareInstance{xfrac}{default}{text}{
4 numerator-format = {%
5 \begingroup%
6 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
7 \InlineClass{numerator}{#1}\,%
8 \endgroup%
9 },
10 denominator-format = {%
11 \begingroup%

```

```

12 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
13 \InlineClass{denominator}{#1}%
14 \endgroup%
15 },

```

For *pdftotext*, do not scale the text:

```

16 scaling = false
17 }
18
19 \DeclareInstance{xfrac}{lmr}{text}{
20 numerator-format = {%
21 \begingroup%
22 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
23 \InlineClass{numerator}{#1}\,%
24 \endgroup%
25 },
26 denominator-format = {%
27 \begingroup%
28 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
29 \InlineClass{denominator}{#1}%
30 \endgroup%
31 },

```

For *pdftotext*, do not scale the text:

```

32 scaling = false
33 }
34
35 \DeclareInstance{xfrac}{lmss}{text}{
36 numerator-format = {%
37 \begingroup%
38 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
39 \InlineClass{numerator}{#1}\,%
40 \endgroup%
41 },
42 denominator-format = {%
43 \begingroup%
44 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
45 \InlineClass{denominator}{#1}%
46 \endgroup%
47 },

```

For *pdftotext*, do not scale the text:

```

48 scaling = false
49 }
50
51 \DeclareInstance{xfrac}{lmtt}{text}{
52 numerator-format = {%
53 \begingroup%
54 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
55 \InlineClass{numerator}{#1}\,%
56 \endgroup%
57 },

```

```

58 denominator-format = {%
59 \begingroup%
60 \RenewDocumentCommand{\scalebox}{m o m}{##3}%
61 \InlineClass{denominator}{#1}%
62 \endgroup%
63 },

```

For *pdftotext*, do not scale the text:

```

64 scaling = false
65 }

```

For MATHJAX:

```

66 \begin{warpMathJax}
67 \CustomizeMathJax{\newcommand{\LWRsfrac}[2][/]{\{{}^\wedge\LWRsfracnumerator\!#1}_{#2}}}
68 \CustomizeMathJax{\newcommand{\sfrac}[2][]{\def\LWRsfracnumerator{#2}\LWRsfrac}}
69 \end{warpMathJax}

```

---

File 533 **lwarp-xltabular.sty**

§ 639 Package **xltabular**

(Emulates or patches code by ROLF NIEPRASCHK, HERBERT VOSS.)

Pkg xltabular xltabular is emulated by lwarp.

for HTML output: Relies on tabularx.

 **table numbering** At present, an xltabular without a caption or with only a \caption\* may be misnumbered in HTML, so it may be necessary to place at the end of the table:

```
\warpHTMLonly{\addtocounter{table}{-1}}
```

```

1 \RequirePackage{tabularx}
2 \RequirePackage{ltablex}
3
4 \LWR@ProvidesPackageDrop{xltabular}[2018/05/23]
5
6 \DeclareDocumentEnvironment{xltabular}{o m m}
7 {\longtable{#3}}
8 {\endlongtable}

```

---

File 534 **lwarp-xltextra.sty**

§ 640 Package **xltextra**

(Emulates or patches code by WILL ROBERTSON, JONATHAN KEW.)

Pkg xltextra xltextra is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{xltextra}[2016/01/21]

2 \RequirePackage{realscripts}
3 \RequirePackage{metalogo}
4 \newcommand*\TeX@Logo@spacing[6]{}
5
6 \newcommand*\vfrac[2]{%
7 #1/\textsubscript{#2}%
8 }
9
10 \newcommand\namedglyph[1]{%
11 \@tempcnta=\XeTeXglyphindex " #1 "\relax
12 \ifnum\@tempcnta>0
13 \XeTeXglyph\@tempcnta
14 \else
15 \xxt@namedglyph@fallback{#1}%
16 \fi}
17
18 \newcommand\xxt@namedglyph@fallback[1][[#1]]
19
20 \DeclareDocumentCommand{\showhyphens}{m}{}

```

File 535 **lwarp-xmpincl.sty**

§ 641 Package **xmpincl**

*(Emulates or patches code by MAARTEN SNEEP.)*

Pkg xmpincl xmpincl is ignored.

**for HTML output:** Discard all options for lwarp-xmpincl:

```

1 \LWR@ProvidesPackageDrop{xmpincl}[2008/05/10]

2 \newcommand*\includemp[1]{}

```

File 536 **lwarp-xpiano.sty**

§ 642 Package **xpiano**

*(Emulates or patches code by ENRICO GREGORIO.)*

Pkg xpiano xpiano is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{xpiano}

2 \ExplSyntaxOn
3 \NewDocumentCommand{\LWR@print@keyboard}{ O {m }
4 {

```

```

5 \xpiano_keyboard:nn { #1 } { #2 }
6 }
7
8 \NewDocumentCommand{\LWR@HTML@keyboard}{ O{}m }
9 {
10 \begin{lateximage}*
11 [%
12 -xpiano--\PackageDiagramAltText{}: \detokenize\expandafter{#2}%
13]
14 [\detokenize\expandafter{#1}]
15 \xpiano_keyboard:nn { #1 } { #2 }
16 \end{lateximage}
17 }
18 \ExplSyntaxOff
19
20 \LWR@formatted{keyboard}

```

---

File 537 **lwarp-xpinyin.sty**

§ 643 Package **xpinyin**

*(Emulates or patches code by SOBEN LEE.)*

Pkg xpinyin xpinyin is supported.

Pinyin is disabled for file names, the sideroc, and regular footnotes, but is left enabled for minipage footnotes, as per the print mode.

**for HTML output:** 1 \LWR@ProvidesPackagePass{xpinyin}[2019-04-07]

The original's boxes are not used, instead the contents are used with `<ruby>`, `<rb>`, and `<rt>` tags per modern HTML. Color is detected. `ratio` is ignored for *pdfotext* to work correctly. Extra spaces are placed inside the tags to allow line breaks in the HTML text.

```

2 \ExplSyntaxOn
3 \cs_new_protected_nopar:Npn \LWR@HTML@__xpinyin_make_pinyin_box:nnn #1#2#3
4 {
5 \color_group_begin: \color_ensure_current:
6 \l__xpinyin_pinyin_box_hook_tl
7 \renewcommand*{\l__xpinyin_ratio_tl}{1}% for pdfotext
8 __xpinyin_select_font:
9 \clist_if_exist:cTF { c__xpinyin_multiple_ #1 _clist }
10 { \l__xpinyin_multiple_tl \l__xpinyin_format_tl }
11 { \l__xpinyin_format_tl }
12 \ifdefempty{\l__xpinyin_format_tl}
13 {#3}
14 {\LWR@textcurrentcolor{#3}}
15 \color_group_end:
16 }
17 \LWR@formatted{__xpinyin_make_pinyin_box:nnn}
18

```

```

19 \cs_new_protected_nopar:Npn \LWR@HTML@__xpinyin_CJKsymbol:nn #1#2
20 {
21 __xpinyin_leavevmode:
22 \LWR@htmltagc{ruby}
23 \LWR@htmltagc{rb}
24 __xpinyin_save_CJKsymbol:n {#2}\null% \null removes extra space
25 \LWR@htmltagc{/rb\space}
26 \LWR@htmltagc{rp}\LWR@htmltagc{/rp\space}
27 \LWR@htmltagc{rt}
28 __xpinyin_make_pinyin_box:nnn {#1} {#2} { \use:c { c__xpinyin_ #1 _tl } }
29 \LWR@htmltagc{/rt\space}
30 \LWR@htmltagc{rp}\LWR@htmltagc{/rp\space}
31 \LWR@htmltagc{/ruby\space}\null
32 }
33 \LWR@formatted{__xpinyin_CJKsymbol:nn}
34
35 \cs_new_protected_nopar:Npn \LWR@HTML@__xpinyin_single_CJKsymbol:nn #1#2
36 {
37 __xpinyin_leavevmode:
38 \LWR@htmltagc{ruby}
39 \LWR@htmltagc{rb}
40 __xpinyin_save_CJKsymbol:n {#1}\null% \null removes extra space
41 \LWR@htmltagc{/rb\space}
42 \LWR@htmltagc{rp}\LWR@htmltagc{/rp\space}
43 \LWR@htmltagc{rt}
44 __xpinyin_make_pinyin_box:xnn
45 { __xpinyin_to_unicode:n {#1} } {#1} { __xpinyin_pinyin:n {#2} }
46 \LWR@htmltagc{/rt\space}
47 \LWR@htmltagc{rp}\LWR@htmltagc{/rp\space}
48 \LWR@htmltagc{/ruby\space}\null
49 }
50 \LWR@formatted{__xpinyin_single_CJKsymbol:nn}
51
52 \ExplSyntaxOff

```

The `lwarp` core uses the following to disable CJK xpinyin for filenames, sideroc, and footnotes.

```

53 \renewcommand*{\LWR@disablepinyin}{\disablepinyin}
54
55 \FilenameNullify{\LWR@disablepinyin}

```

---

File 538 **lwarp-xr.sty**

§ 644 Package **X<sub>r</sub>**

*(Emulates or patches code by JEAN-PIERRE DRUCBERT, DAVID CARLISLE.)*

Pkg `xr` `xr` is patched for use by `lwarp`. The `*_html.aux` file is used. `\externaldocument` is modified to also accept the optional arguments for `xr-hyper`, which currently uses `xr` for HTML output.

See section 5.17.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{xr}[2019/07/22]%
2 \LetLtxMacro\LWR@orig@externaldocument\externaldocument
3
4 \RenewDocumentCommand{\externaldocument}{O{} O{} m O{}}{%
5 \ifblank{#1}{%
6 \LWR@orig@externaldocument{#3_html}%
7 }{%
8 \LWR@orig@externaldocument[#1]{#3_html}%
9 }%
10 }
```

---

File 539 **lwarp-xr-hyper.sty**

§ 645 Package **xr-hyper**

*(Emulates or patches code by DAVID CARLISLE.)*

Pkg xr-hyper xr-hyper is replaced by xr, which is modified to accept the optional arguments for \externaldocument. So far, no hyperlinks are provided for citations.

See section 5.17.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{xr-hyper}[2019/10/03]%
2
3 \LWR@origRequirePackage{lwarp-xr}
```

---

File 540 **lwarp-xtab.sty**

§ 646 Package **xtab**

*(Emulates or patches code by PETER WILSON.)*

Pkg xtab xtab is emulated.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{xtab}[2011/07/31]
```

⚠ Misplaced alignment tab character &

For \tablefirsthead, etc., enclose them as follows:

```

\StartDefiningTabulars
\tablefirsthead
...
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a lateximage.

```

2 \newcommand{\LWRXT@firsthead}{ }
3
```

```

4 \newcommand{\tablefirsthead}[1]{%
5 \long\gdef\LWRXT@firsthead{#1}%
6 }
7
8 \newcommand{\tablehead}[1]{}
9
10 \newcommand{\tablelasthead}[1]{}
11
12 \newcommand{\notablelasthead}{}
13
14 \newcommand{\tabletail}[1]{}
15
16 \newcommand{\LWRXT@lasttail}{}
17
18 \newcommand{\tablelasttail}[1]{%
19 \long\gdef\LWRXT@lasttail{#1}%
20 }

21 \newcommand{\tablecaption}[2][]{%
22 \long\gdef\LWRXT@caption{%
23 \ifblank{#1}%
24 {\caption{#2}}%
25 {\caption[#1]{#2}}%
26 }%
27 }
28
29 \let\topcaption\tablecaption
30 \let\bottomcaption\tablecaption

31 \newcommand*{\LWRXT@caption}{}
32
33 \newcommand*{\shrinkheight}[1]{}
34
35 \newcommand*{\xentrystretch}[1]{}
36
37 \NewDocumentEnvironment{xtabular}{s o m}
38 {%
39 \LWR@traceinfo{xtabular}%
40 \table%
41 \LWRXT@caption%
42 \begin{tabular}{#3}%
43 \TabularMacro\ifdefvoid{\LWRXT@firsthead}%
44 {\LWR@getmynexttoken}%
45 {\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
46 }%
47 {%
48 \ifdefvoid{\LWRXT@lasttail}%
49 {}%
50 {%
51 \TabularMacro\ResumeTabular%
52 \LWRXT@lasttail%
53 }%
54 \end{tabular}%
55 \endtable%

```

```

56 \gdef\LWRXT@caption{%
57 \LWR@traceinfo{xtabular done}%
58 }
59
60 \NewDocumentEnvironment{mpxtabular}{s o m}
61 {\minipage{\linewidth}\xtabular{#3}}
62 {\endxtabular\endminipage}

```

---

File 541 **lwarp-xunicode.sty**

§ 647 Package **xunicode**

Pkg xunicode Error if xunicode is loaded after lwarp.

Patch lwarp-xunicode, but also verify that it was loaded before lwarp:

for HTML output:

```

1 \LWR@loadbefore{xunicode}%
2
3 \LWR@ProvidesPackagePass{xunicode}[2011/09/09]

```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with `textcomp`.

```

4 \providecommand*\LWR@HTML@textcircled[1]{%
5 \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
6 }
7
8 \LWR@formatted{textcircled}

```

Nullify xunicode macros when generating filenames:

```

9 \FilenameNullify{%
10 \renewcommand*\textdegree{}%
11 \renewcommand*\textcelsius{}%
12 \renewcommand*\textohm{}%
13 \renewcommand*\textmu{}%
14 \renewcommand*\textlquill{}%
15 \renewcommand*\textrquill{}%
16 \renewcommand*\textcircledP{}%
17 \renewcommand*\texttwelveudash{}%
18 \renewcommand*\textthreequartersemdash{}%
19 \renewcommand*\textmho{}%
20 \renewcommand*\textnaira{}%
21 \renewcommand*\textpeso{}%
22 \renewcommand*\textrecipe{}%
23 \renewcommand*\textinterrobang{}%
24 \renewcommand*\textinterrobangdown{}%
25 \renewcommand*\textperthousand{}%
26 \renewcommand*\textpertenthousand{}%
27 \renewcommand*\textbaht{}%
28 \renewcommand*\textdiscount{}%

```

---

```

29 \renewcommand*\textservicemark{}%
30 \renewcommand*\textcircled}[1]{#1}%
31 \renewcommand*\capitalcedilla}[1]{#1}%
32 \renewcommand*\capitalogonek}[1]{#1}%
33 \renewcommand*\capitalgrave}[1]{#1}%
34 \renewcommand*\capitalacute}[1]{#1}%
35 \renewcommand*\capitalcircumflex}[1]{#1}%
36 \renewcommand*\capitaltilde}[1]{#1}%
37 \renewcommand*\capitaldieresis}[1]{#1}%
38 \renewcommand*\capitalhungarumlaut}[1]{#1}%
39 \renewcommand*\capitalring}[1]{#1}%
40 \renewcommand*\capitalcaron}[1]{#1}%
41 \renewcommand*\capitalbreve}[1]{#1}%
42 \renewcommand*\capitalmacron}[1]{#1}%
43 \renewcommand*\capitaldotaccent}[1]{#1}%
44 }% FilenameNullify

```

---

File 542 **lwarp-xurl.sty**

§ 648 Package **xurl**

Pkg xurl xurl is ignored.

**for HTML output:**

```

1 \LWR@ProvidesPackageDrop{xurl}[2020/01/14]
2
3 \def\useOriginalUrlSetting{}

```

---

File 543 **lwarp-xy.sty**

§ 649 Package **xy**

*(Emulates or patches code by KRISTOFFER H. ROSE, ROSS MOORE.)*

Pkg xy xy is patched for use by lwarp.

**for HTML output:**

```

1 \LWR@ProvidesPackagePass{xy}[2013/10/06]

```

After xy modules have been loaded:

```

2 \AtBeginDocument{

```

The original definitions without a lateximage:

```

3 \LetLtxMacro\LWR@orig@xy\xy
4 \LetLtxMacro\LWR@orig@endxy\endxy

```

The outer-most xy environment is placed in a lateximage, but not more than one level deep, which would conflict with xy:

```

5 \renewcommand*\xy}{%
6 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
7 {\addtocounter{LWR@lateximagedepth}{1}}%
8 {\begin{lateximage}[-xy-~\PackageDiagramAltText]}%
9 \LWR@orig@xy%
10 }
11
12 \renewcommand*\endxy}{%
13 \LWR@orig@endxy%
14 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
15 {\addtocounter{LWR@lateximagedepth}{-1}}%
16 {\end{lateximage}}%
17 }

```

The `\xybox` must use the original definitions of `\xy`, `\endxy`:

```

18 \def\xybox#1{%
19 \LWR@orig@xy#1\LWR@orig@endxy%
20 \Edge@c={\rectangleEdge}\computeLeftUpness@%
21 }

```

If `\xygraph` is used, it is placed inside a `lateximage`:

```

22 \@ifundefined{xygraph}{}{
23
24 \LetLtxMacro\LWR@origxygraph\xygraph
25
26 \renewcommand*\xygraph}[1]{%
27 \begin{lateximage}[-xy- xygraph \PackageDiagramAltText]
28 \LWR@origxygraph{#1}
29 \end{lateximage}
30 }
31
32 }% xygraph defined
33
34 }% AtBeginDocument

```

---

File 544 **lwarp-zhlineskip.sty**

§ 650 Package **zhlineskip**

Pkg zhlineskip zhlineskip is ignored.

**for HTML output:** 1 \LWR@ProvidesPackageDrop{zhlineskip}[2019/05/15]

```

2 \newcommand*\SetTextEnvironmentSinglespace[1]{}
3 \newcommand*\RestoreTextEnvironmentLeading[1]{}
4 \newcommand*\SetMathEnvironmentSinglespace[1]{}
5 \newcommand*\RestoreMathEnvironmentLeading[1]{}

```

File 545 **lwarp-zwpageLayout.sty**

§ 651 Package **zwpageLayout**

*(Emulates or patches code by ZDENĚK WAGNER.)*

Pkg zwpageLayout **zwpageLayout** is ignored.

```

for HTML output: 1 \LWR@ProvidesPackageDrop{zwpageLayout}[2013/01/13]

2 \def\noBboxes{}
3 \@onlypreamble\noBboxes
4
5 \expandafter\ifx\csname definecolor\endcsname\relax \else
6 \definecolor{cmykblack}{cmyk}{0,0,0,1}
7 \definecolor{grblack}{gray}{0}
8 % \ifzwpl@redefineblack
9 % \definecolor{black}{cmyk}{0,0,0,1}\color{black}
10 % \fi
11 \definecolor{cmykred}{cmyk}{0,1,1,0}
12 \definecolor{cmykgreen}{cmyk}{1,0,1,0}
13 \definecolor{cmykblue}{cmyk}{1,1,0,0}
14 \definecolor{rgbred}{rgb}{1,0,0}
15 \definecolor{rgbgreen}{rgb}{0,1,0}
16 \definecolor{rgbblue}{rgb}{0,0,1}
17 % \ifzwpl@redefinetcmyk
18 % \definecolor{red}{cmyk}{0,1,1,0}
19 % \definecolor{green}{cmyk}{1,0,1,0}
20 % \definecolor{blue}{cmyk}{1,1,0,0}
21 % \fi
22 \fi
23
24 \let\OverprintXeTeXExtGState\relax
25
26 \DeclareRobustCommand\SetOverprint{\ignorespaces}
27 \DeclareRobustCommand\SetKnockout{\ignorespaces}
28 \DeclareRobustCommand\textoverprint[1]{\SetOverprint#1}
29 \DeclareRobustCommand\textknockout[1]{\SetKnockout#1}
30
31 \def\SetPDFminorversion#1{}
32 \@onlypreamble\SetPDFminorversion
33
34 \newcommand*\Vcorr{}
35
36 \DeclareRobustCommand\vb[1][1]{}
37 \NewDocumentCommand\NewOddPage{* o}{}
38 \NewDocumentCommand\NewEvenPage{* o}{}
39 \def\SetOddPageMessage#\gdef\ZW@oddwarning}
40 \def\SetEvenPageMessage#\gdef\ZW@evenwarning}
41 \def\ZW@oddwarning{Empty page inserted}\let\ZW@evenwarning\ZW@oddwarning
42

```

```

43 \def\clap#1{#1}
44
45 \def\CropFlap{2in}
46 \def\CropSpine{1in}
47 \def\CropXSpine{1in}
48 \def\CropXtrim{.25in}
49 \def\CropYtrim{.25in}
50 \def\UserWidth{5in}
51 \def\UserLeftMargin{1in}
52 \def\UserRightMargin{1in}
53 \def\UserTopMargin{1in}
54 \def\UserBotMargin{1in}
55 \def\thePageNumber{\LWR@origpound\,\arabic{page}}
56 \ifXeTeX
57 \def\ifcaseZWdriver{\ifcase2}
58 \else
59 \def\ifcaseZWdriver{\ifcase1}
60 \fi
61 \DeclareRobustCommand\ZWifdriver[2]{}

```

---

File 546 **lwarp-patch-komascript.sty**

§ 652 Package **patch-komascript**

Pkg lwarp-patch-komascript Patches for komascript classes.

lwarp loads this package when scrbook, scartcl, or screprt classes are detected.

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

\captionformat, \figureformat, and \tableformat are not yet emulated.

 **Not fully tested!** [Please send bug reports!](#)

Some features have not yet been tested. Please contact the author with any bug reports.

**for HTML output:** 1 \ProvidesPackage{lwarp-patch-komascript}

typearea is emulated.

2 \RequirePackage{lwarp-typearea}

tocbasic is emulated.

3 \RequirePackage{lwarp-tocbasic}

scrextend patches most of the new macros.

4 \RequirePackage{lwarp-scrextend}

Indexing macros, simplified for lwarp:

```

5 \AtBeginDocument{
6
7 \renewcommand*{\idx@heading}{%
8 \idx@@heading{\indexname}%
9 }
10
11 \renewenvironment{theindex}{%
12 \idx@heading%
13 \index@preamble\par\nobreak
14 \let\item\LWR@indexitem%
15 \let\subitem\LWR@indexsubitem%
16 \let\subsubitem\LWR@indexsubsubitem%
17 }
18 {}
19
20 \renewcommand*\indexspace{}
21
22 }% AtBeginDocument

```

The `\minisec` is placed inside a `<div>` of class `minisec`.

```

23 \renewcommand*\minisec}[1]{
24 \begin{BlockClass}{minisec}
25 #1
26 \end{BlockClass}
27 }

```

The part and chapter preambles are placed as plain text just after each heading.

```

28 \@ifundefined{setpartpreamble}{}{
29 \RenewDocumentCommand{\setpartpreamble}{o o +m}{%
30 \renewcommand{\part@preamble}{#3}%
31 }
32 }
33
34 \@ifundefined{setchapterpreamble}{}{
35 \RenewDocumentCommand{\setchapterpreamble}{o o +m}{%
36 \renewcommand{\chapter@preamble}{#3}%
37 }
38 }

```

Do not use `\chaptername`:

```

39 \renewcommand*\LWR@printchaptername{}

```

Simple captions are used in all cases.

```

40 \AtBeginDocument{
41 \AtBeginDocument{
42 \LetLtxMacro\captionbelow\caption
43 \LetLtxMacro\captionabove\caption
44
45 \LetLtxMacro\captionofbelow\captionof

```

```

46 \LetLtxMacro\captionofabove\captionof
47 }
48 }
49
50 \RenewDocumentEnvironment{captionbeside}{o m o o s}
51 {}
52 {%
53 \IfValueTF{#1}%
54 {\caption[#1]{#2}}%
55 {\caption{#2}}%
56 }
57
58 \RenewDocumentEnvironment{captionofbeside}{m o m o o s}
59 {}
60 {%
61 \IfValueTF{#2}%
62 {\captionof{#1}[#2]{#3}}%
63 {\captionof{#1}{#3}}%
64 }
65
66 \RenewDocumentCommand{\setcapindent}{s m}{}
67 \renewcommand*\setcaphanging{}
68 \renewcommand*\setcapwidth[2][{}]{ }
69 \renewcommand*\setcapdynwidth[2][{}]{ }
70 \RenewDocumentCommand{\setcapmargin}{s o m}{}

```

---

File 547 **lwarp-patch-memoir.sty**

§ 653 Package **patch-memoir**

(Emulates or patches code by PETER WILSON.)

Pkg lwarp-patch-memoir Patches for memoir class.

 **Not fully tested!** [Please send bug reports!](#)

lwarp loads this package when the memoir class is detected.

 **captions** lwarp uses caption, which causes a warning from memoir. This is normal. Adjust captions via caption, instead of memoir.

 **options clash** While emulating memoir, lwarp pre-loads a number of packages (section 653.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```

\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}

```

-  **version numbers** memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since `lwarp` is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.
- `\label{bookmark}{tag}` `\label` accepts an optional (bookmark) argument, but this is ignored in HTML.
-  **comment** The `comment` environment is from the `comment` package, and thus requires that the `\begin` and `\end` each be on its own line:
- ```
\begin{comment}
This is a comment.
\end{comment}
```
- `\newcomment` Comments defined with `\newcomment` use memoir's definitions, and behave as expected, where the `\begin` and `\end` do have to each be on its own line.
-  **verbatim footnotes** `\verbfootnote` is not supported.
-  **\newfootnoteseries** `\newfootnoteseries`, etc. are not supported.
-  **page notes** `lwarp` loads `pagenote` to perform memoir's `pagenote` functions, but there are minor differences in `\pagenotesubhead` and related macros.
- page notes with cleveref** To add support for pagenotes with `cleveref`, add:
- ```
\crefname{pagenote}{page note}{page notes}
\Crefname{pagenote}{Page note}{Page notes}
```
- page note \nameref** Note that for print mode, `\nameref` print the section name where the page notes are declared in the text, but for HTML it prints the name where the page notes are printed.
-  **poems** Poem numbering is not supported.
-  **verbatim** The `verbatim` environment does not yet support the memoir enhancements. It is currently recommended to load and use `fancyvrb` instead.
-  **glossaries** The memoir glossary system is not yet supported by `lwarpmk`. The `glossaries` package may be used instead, but does require the glossary entries be changed from the memoir syntax to the `glossaries` syntax.
- for HTML output:** `1 \ProvidesPackage{lwarp-patch-memoir}`

## § 653.1 Packages

These are pre-loaded to provide emulation for many of memoir's functions. memoir pretends that `abstract`, etc. are already loaded, via its "emulated" package mechanism, but `lwarp` is directly loading the "lwarp-" version of each, which happens to avoid memoir's emulation system.

```
2 \RequirePackage{lwarp-abstract}% req'd
3 % \RequirePackage{lwarp-array}% no longer req'd
4 \RequirePackage{lwarp-booktabs}% req'd
5 % \RequirePackage{lwarp-ccaption}% emulated below
6 \RequirePackage{lwarp-changepage}% req'd
```

```

7 \RequirePackage{lwarp-crop}
8 % \RequirePackage{lwarp-dcolumn}% no longer req'd
9 \RequirePackage{lwarp-enumerate}% req'd
10 \RequirePackage{lwarp-epigraph}% req'd
11 \RequirePackage{lwarp-fancyvrb}% req'd
12 \RequirePackage{lwarp-footmisc}% req'd

13 \let\framed\relax \let\endframed\relax
14 \let\shaded\relax \let\endshaded\relax
15 \let\leftbar\relax \let\endleftbar\relax
16 \let\snugshade\relax \let\endsnugshade\relax
17 \RequirePackage{lwarp-framed}% req'd
18
19 \RequirePackage{lwarp-hanging}% req'd
20 \RequirePackage{lwarp-makeidx}% req'd
21 \DisemulatePackage{moreverb}
22 \RequirePackage{lwarp-moreverb}
23 \RequirePackage{lwarp-mparhack}
24 \RequirePackage{lwarp-needspace}% req'd
25 \RequirePackage{lwarp-nextpage}% req'd
26 \RequirePackage{lwarp-pagenote}% req'd
27 \RequirePackage{lwarp-parskip}
28 \RequirePackage{lwarp-setspace}% req'd
29 \RequirePackage{lwarp-showidx}

30 \makeindex

31 % \RequirePackage{lwarp-tabularx}% no longer req'd
32 \RequirePackage{lwarp-titling}% req'd
33 % \RequirePackage{lwarp-tocbibind}% not emulated by memoir
34 \RequirePackage{lwarp-tocloft}% req'd
35 \RequirePackage{lwarp-verse}% req'd

```

## § 653.2 Label handling

Insert the lwarp label mechanism into the memoir package mechanism:

- `\@mem@old@label` is the L<sup>A</sup>T<sub>E</sub>X definition of `\label`.
- `\LWR@orig@label` adds the memoir definition.
- lwarp's `\LWR@new@label` uses `\LWR@orig@label`.
- Want memoir's `\label` to use lwarp's `\label`, which then would use L<sup>A</sup>T<sub>E</sub>X's `\label`.
- So:
  - `\@mem@old@label` becomes `\LWR@new@label`.
  - `\LWR@orig@label` becomes `\@mem@old@label`.
- `cleveref` then encapsulates all the above.
- For a subcaption, `cleveref` modifies memoir's `\sf@memsub@label`.

```

36 \let\LWR@orig@label\@mem@old@label
37 \let\@mem@old@label\LWR@new@label

```

Patches for subfloats to support additional lwarp labels:

```

38 \AtBeginDocument{
39 \renewcommand*\sf@memsub@label}[1]{%
40 \@bsphack
41 \sf@memsub@label@hook{#1}%
42 \@memoldlabel{#1}%
43 \LWR@label@createtag{sub@#1}%
44 \protected@write\@auxout{}%
45 \string\newlabel{sub@#1}%
46 {\@nameuse{@thesub\@caption}}%
47 {\thepage}}%
48 \LWR@write@lwarpLabel{sub@#1}%
49 \@esphack
50 }
51 }

```

### § 653.3 Page layout

memoir already set the page size to a default, so it must be forced large for lwarp's use, to avoid tag overflows off the page.

```

52 \setstocksize{190in}{20in}
53 \setlrmarginsandblock{2in}{2in}{*}
54 \setulmarginsandblock{1in}{1in}{*}

55 \renewcommand*\stockavi{}
56 \renewcommand*\stockav{}
57 \renewcommand*\stockaiv{}
58 \renewcommand*\stockaiii{}
59 \renewcommand*\stockavii{}
60 \renewcommand*\stockbvi{}
61 \renewcommand*\stockbv{}
62 \renewcommand*\stockbiv{}
63 \renewcommand*\stockbiii{}
64 \renewcommand*\stockbvii{}
65 % \renewcommand*\stockmetriccrownvo{}% in docs but not in the package
66 \renewcommand*\stockmlargecrownvo{}
67 \renewcommand*\stockmdemyvo{}
68 \renewcommand*\stockmsmallroyalvo{}
69 \renewcommand*\pageavi{}
70 \renewcommand*\pageavii{}
71 \renewcommand*\pageav{}
72 \renewcommand*\pageaiv{}
73 \renewcommand*\pageaiii{}
74 \renewcommand*\pagebvii{}
75 \renewcommand*\pagebvii{}
76 \renewcommand*\pagebv{}
77 \renewcommand*\pagebiv{}
78 \renewcommand*\pagebiii{}
79 % \renewcommand*\pagemetriccrownvo{}% in docs but not in the package

```

```
80 \renewcommand*{\pagelargecrownvo}{}
81 \renewcommand*{\pagedemyvo}{}
82 \renewcommand*{\pagesmallroyalvo}{}
83
84 \renewcommand*{\stockdbill}{}
85 \renewcommand*{\stockstatement}{}
86 \renewcommand*{\stockexecutive}{}
87 \renewcommand*{\stockletter}{}
88 \renewcommand*{\stockold}{}
89 \renewcommand*{\stocklegal}{}
90 \renewcommand*{\stockledger}{}
91 \renewcommand*{\stockbroadsheet}{}
92 \renewcommand*{\pagedbill}{}
93 \renewcommand*{\pagestatement}{}
94 \renewcommand*{\pageexecutive}{}
95 \renewcommand*{\pageletter}{}
96 \renewcommand*{\pageold}{}
97 \renewcommand*{\pagelegal}{}
98 \renewcommand*{\pageledger}{}
99 \renewcommand*{\pagebroadsheet}{}
100
101 \renewcommand*{\stockpottvo}{}
102 \renewcommand*{\stockfoolscapvo}{}
103 \renewcommand*{\stockcrownvo}{}
104 \renewcommand*{\stockpostvo}{}
105 \renewcommand*{\stocklargecrownvo}{}
106 \renewcommand*{\stocklargepostvo}{}
107 \renewcommand*{\stocksmalldemyvo}{}
108 \renewcommand*{\stockdemyvo}{}
109 \renewcommand*{\stockmediumvo}{}
110 \renewcommand*{\stocksmallroyalvo}{}
111 \renewcommand*{\stockroyalvo}{}
112 \renewcommand*{\stocksuperroyalvo}{}
113 \renewcommand*{\stockimperialvo}{}
114 \renewcommand*{\pagepottvo}{}
115 \renewcommand*{\pagefoolscapvo}{}
116 \renewcommand*{\pagecrownvo}{}
117 \renewcommand*{\pagepostvo}{}
118 \renewcommand*{\pagelargecrownvo}{}
119 \renewcommand*{\pagelargepostvo}{}
120 \renewcommand*{\pagesmalldemyvo}{}
121 \renewcommand*{\pagedemyvo}{}
122 \renewcommand*{\pagemediumvo}{}
123 \renewcommand*{\pagesmallroyalvo}{}
124 \renewcommand*{\pageroyalvo}{}
125 \renewcommand*{\pagesuperroyalvo}{}
126 \renewcommand*{\pageimperialvo}{}
127
128 \renewcommand*{\memfontfamily}{}
129 \renewcommand*{\memfontenc}{}
130 \renewcommand*{\memfontpack}{}
131
132 \renewcommand*{\anyptfilebase}{}
133 \renewcommand*{\anyptsize}{10}
134
```

```
135 \renewcommand*\setstocksize}[2]{}
136 \renewcommand*\settrimmedsize}[3]{}
137 \renewcommand*\settrims}[2]{}
138
139 % \newlength{\lxvchars}
140 % \setlength{\lxvchars}{305pt}
141 % \newlength{\xlvchars}
142 % \setlength{\xlvchars}{190pt}
143 \renewcommand*\setxlvchars}[1]{}
144 \renewcommand*\setlxvchars}[1]{}
145
146 \renewcommand*\settypeblocksize}[3]{}
147 \renewcommand*\setlrmargins}[3]{}
148 \renewcommand*\setlrmarginsandblock}[3]{}
149 \renewcommand*\setbinding}[1]{}
150 \renewcommand*\setulmargins}[3]{}
151 \renewcommand*\setulmarginsandblock}[3]{}
152 \renewcommand*\setcolsepandrule}[2]{}
153
154 \renewcommand*\setheadfoot}[2]{}
155 \renewcommand*\setheaderspaces}[3]{}
156 \renewcommand*\setmarginnotes}[3]{}
157 \renewcommand*\setfootins}[2]{}
158 \renewcommand*\checkandfixthelayout}[1][1]{}
159 \renewcommand*\checkthelayout}[1]{}
160 \renewcommand*\fixthelayout}{}
161 %
162 % \newlength{\stockheight}
163 % \newlength{\trimtop}
164 % \newlength{\trimedge}
165 % \newlength{\stockwidth}
166 % \newlength{\spinemargin}
167 % \newlength{\foremargin}
168 % \newlength{\uppermargin}
169 % \newlength{\headmargin}
170 %
171 \renewcommand*\typeoutlayout}{}
172 \renewcommand*\typeoutstandardlayout}{}
173 \renewcommand*\settypeoutlayoutunit}[1]{}
174 \renewcommand*\fixpdflayout}{}
175 \renewcommand*\fixdvipslayout}{}
176
177 \renewcommand*\medievalpage}[1][1]{}
178 \renewcommand*\isopage}[1][1]{}
179 \renewcommand*\semiisopage}[1][1]{}
180
181 \renewcommand{\setpagebl}[3]{}
182 \renewcommand{\setpageml}[3]{}
183 \renewcommand{\setpagetl}[3]{}
184 \renewcommand{\setpagetm}[3]{}
185 \renewcommand{\setpagetr}[3]{}
186 \renewcommand{\setpagemr}[3]{}
187 \renewcommand{\setpagebr}[3]{}
188 \renewcommand{\setpagebm}[3]{}
189 \renewcommand{\setpagecc}[3]{}

```

§ 653.4 **Text and fonts**

```

190 \let\miniscule\tiny
191 \let\HUGE\Huge
192
193 \renewcommand*\abnormalparskip}[1]{}
194 \renewcommand*\nonzeroparskip){}
195 \renewcommand*\traditionalparskip){}
196
197 \let\onelineskip\baselineskip
198
199 \let\OnehalfSpacing\onehalfspacing
200 \let\DoubleSpacing\doublespacing
201 \renewcommand*\setPagenoteSpacing}[1]{}
202 \renewcommand*\setFloatSpacing}[1]{}

203 \renewcommand{\SingleSpacing}{\ifstar\singlespacing\singlespacing}

204 \let\setSingleSpace\SetSingleSpace
205 \let\SingleSpace\singleSpace
206 \let\endSingleSpace\endSingleSpace
207 \let\Spacing\spacing
208 \let\endSpacing\endSpacing
209 \let\OnehalfSpace\onehalfSpace
210 \let\endOnehalfSpace\endonehalfSpace
211 \csletcs{OnehalfSpace*}{onehalfSpace}
212 \csletcs{endOnehalfSpace*}{endonehalfSpace}
213 \let\DoubleSpace\doublespace
214 \let\endDoubleSpace\enddoublespace
215 \csletcs{DoubleSpace*}{doublespace}
216 \csletcs{endDoubleSpace*}{enddoublespace}
217 \renewcommand*\setDisplayskipStretch}[1]{}
218 \renewcommand*\memdskipstretch){}
219 \renewcommand*\noDisplayskipStretch){}
220 \renewcommand*\memdskips){}
221
222 \renewcommand*\midslippy){}
223 \renewenvironment*{midslippy}{\relax}{}{}
224
225 \renewcommand*\slippybottom){}

```

§ 653.5 **Titles**

```

226 \csletcs{titlingpage*}{titlingpage}
227 \csletcs{endtitlingpage*}{endtitlingpage}
228 \let\titlingpageend\relax
229 \newcommand{\titlingpageend}[2]{}
230 \let\andnext\and
231 \renewcommand*\thanksmarkstyle}[1]{}
232
233 \renewcommand{\thanksfootmark}{%
234 \thanksscript{\tmark}%
235 }
236
237 % \newlength{\thanksmarksep}% already provided by memoir

```

```
238 \renewcommand\titlingpageend[2]{}

```

### § 653.6 Abstracts

```
239 % \newlength{\absindent}
240 % \newlength{\absparsep}
241 \renewcommand*\abstractcol{}
242 \renewcommand*\abstractintoc{}
243 \renewcommand*\abstractnum{}
244 \renewcommand*\abstractrunin{}

```

### § 653.7 Document divisions

```
\book * (<2:PDF name>) [<3:TOC name>] [<4:PDF name>] (<5:PDF name>) {\<6:name>}

```

```
245 \DeclareDocumentCommand\book{s d() o o d() m}{%
246 \LWR@section{#1}{#3}{#6}{book}%
247 }

```

```
248 \def\@apppage{%
249 \part*\appendixpagename}
250 }
251 \renewcommand\mempreaddappagetotochook{}
252 \renewcommand\mempostaddappagetotochook{}
253
254 \def\@sapppage{%
255 \part*\appendixpagename}
256 }

```

```
257 \DeclareDocumentCommand\mainmatter{s}{%
258 \booltrue{LWR@mainmatter}%
259 }
260
261 \DeclareDocumentCommand\frontmatter{s}{%
262 \boolfalse{LWR@mainmatter}%
263 }

```

```
264 \renewcommand*\raggedbottomsection{}
265 \renewcommand*\normalbottomsection{}
266 \renewcommand*\bottomsectionskip{}
267 \renewcommand*\bottomsectionpenalty{}
268 \csletcs{appendixpage*}{appendixpage}
269 \renewcommand*\namedsubappendices{}
270 \renewcommand*\unnamedsubappendices{}
271 \renewcommand*\beforebookskip{}
272 \renewcommand*\afterbookskip{}
273 \renewcommand*\beforepartskip{}
274 \renewcommand*\afterpartskip{}
275 \renewcommand*\midbookskip{}
276 \renewcommand*\midpartskip{}
277 \renewcommand*\printbookname{}
278 \renewcommand*\booknamefont{}
279 \renewcommand*\booknamenum{}
280 \renewcommand*\printbooknum{}

```

```
281 \renewcommand*\booknumfont{}
282 \renewcommand*\printpartname{}
283 \renewcommand*\partnamefont{}
284 \renewcommand*\partnamenum{}
285 \renewcommand*\printpartnum{}
286 \renewcommand*\partnumfont{}
287 \renewcommand*\printbooktitle[1]{}
288 \renewcommand*\booktitlefont{}
289 \renewcommand*\printparttitle[1]{}
290 \renewcommand*\parttitlefont{}
291 \renewcommand*\bookpageend{}
292 \renewcommand*\bookblankpage{}
293 \renewcommand*\nobookblankpage{}
294 \renewcommand*\partpageend{}
295 \renewcommand*\partblankpage{}
296 \renewcommand*\nopartblankpage{}
297 \RenewDocumentCommand{\newleadpage}{s o m m}{}% todo
298 \RenewDocumentCommand{\renewleadpage}{s o m m}{}% todo
299 \renewcommand*\leadpagetoclevel{chapter}
300
301 \renewcommand*\openright{}
302 \renewcommand*\openleft{}
303 \renewcommand*\openany{}
304 \renewcommand*\clearforchapter{}
305 \renewcommand*\memendofchapterhook{}
306 \renewcommand*\chapterheadstart{}
307 % \newlength{\beforechapskip}
308 \renewcommand*\afterchapternum{}
309 % \newlength{\midchapskip}
310 \renewcommand*\afterchaptertitle{}
311 % \newlength{\afterchapskip}
312 \renewcommand*\printchaptername{}
313 \renewcommand*\chapnamefont{}
314 \renewcommand*\chapternamenum{}
315 \renewcommand*\printchapternum{}
316 \renewcommand*\chapnumfont{}
317 \renewcommand*\printchaptertitle[1]{}
318 \renewcommand*\chaptitlefont{}
319 \renewcommand*\printchapternonum{}
320 \renewcommand*\indentafterchapter{}
321 \renewcommand*\noindentafterchapter{}
322 \renewcommand*\insertchapterspace{}
323
324 \renewcommand*\chapterstyle[1]{}
325 \renewcommand*\makechapterstyle[2]{}
326 \renewcommand*\chapindent{}
327 \let\chapterprecis\cftchapterprecis
328 \let\chapterprecishere\cftchapterprecishere
329 \let\chapterprecistoc\cftchapterprecistoc
330 \renewcommand*\precisfont{}
331 \renewcommand*\prechapterprecis{}
332 \renewcommand*\postchapterprecis{}
333 \renewcommand*\precistoc[1]{}
334 \renewcommand*\precistocfont{}
335 \renewcommand*\precistocformat{}

```

```
336 % \newlength{\prechapterprecisshift}
337
338 \renewcommand*{\setbeforesecskip}[1]{ }
339 \renewcommand*{\setaftersecskip}[1]{ }
340 \renewcommand*{\setsecindent}[1]{ }
341 \renewcommand*{\setsecheadstyle}[1]{ }
342 \renewcommand*{\setbeforesubsecskip}[1]{ }
343 \renewcommand*{\setaftersubsecskip}[1]{ }
344 \renewcommand*{\setsubsecindent}[1]{ }
345 \renewcommand*{\setsubsecheadstyle}[1]{ }
346 \renewcommand*{\setbeforesubsubsecskip}[1]{ }
347 \renewcommand*{\setaftersubsubsecskip}[1]{ }
348 \renewcommand*{\setsubsubsecindent}[1]{ }
349 \renewcommand*{\setsubsubsecheadstyle}[1]{ }
350 \renewcommand*{\setbeforeparaskip}[1]{ }
351 \renewcommand*{\setafterparaskip}[1]{ }
352 \renewcommand*{\setparaindent}[1]{ }
353 \renewcommand*{\setparaheadstyle}[1]{ }
354 \renewcommand*{\setbeforesubparaskip}[1]{ }
355 \renewcommand*{\setaftersubparaskip}[1]{ }
356 \renewcommand*{\setsubparaindent}[1]{ }
357 \renewcommand*{\setsubparaheadstyle}[1]{ }
358 \renewcommand{\@hangfrom}[1]{#1}
359 \renewcommand{\sethangfrom}[1]{ }
360 \renewcommand{\setsecnumformat}[1]{ }
361
362 \renewcommand*{\hangsecnum}{ }
363 \renewcommand*{\defaultsecnum}{ }
364
365 \renewcommand*{\sechook}{ }
366 \renewcommand{\setsechook}[1]{ }
367 \renewcommand*{\subsechook}{ }
368 \renewcommand{\setsubsechook}[1]{ }
369 \renewcommand*{\subsubsechook}{ }
370 \renewcommand{\setsubsubsechook}[1]{ }
371 \renewcommand*{\parahook}{ }
372 \renewcommand{\setparahook}[1]{ }
373 \renewcommand*{\subparahook}{ }
374 \renewcommand{\setsubparahook}[1]{ }
375
376 \RenewDocumentCommand{\plainbreak}{s m}{\begin{center}~\end{center}}
377
378 \RenewDocumentCommand{\fancybreak}{s +m}{%
379 \begin{center}#2\end{center}%
380 }
381
382 \RenewDocumentCommand{\plainfancybreak}{s m m +m}{%
383 \begin{center}#4\end{center}%
384 }
385
386 \RenewDocumentCommand{\pfbreak}{s}{%
387 \begin{center}
388 \pfbreakdisplay
389 \end{center}
390 }
```

```

391
392 % \newlength{\pfbreakskip}
393 \renewcommand{\pfbreakdisplay}{*\quad*\quad*}
394
395 \renewcommand{\makeheadstyles}[2]{}
396 \renewcommand*\headstyles[1]{}

```

## § 653.8 **Pagination and headers**

```

397 \renewcommand*\savepagenumber{}
398 \renewcommand*\restorepagenumber{}
399 \renewcommand*\uppercaseheads{}
400 \renewcommand*\nouppercaseheads{}
401
402 \renewcommand*\bookpagemark[1]{}
403 \renewcommand*\partmark[1]{}
404 \renewcommand*\bibmark{}
405 \renewcommand*\indexmark{}
406 \renewcommand*\glossarymark{}
407
408 \LWR@origpagestyle{empty}
409 \renewcommand*\ps@empty{}
410 \renewcommand*\makepagestyle[1]{}
411 \renewcommand*\emptyshook{}%
412 % \renewcommand*\empty@oddhead{}
413 % \renewcommand*\empty@oddfoot{}
414 % \renewcommand*\empty@evenhead{}
415 % \renewcommand*\empty@evenfoot{}
416 \renewcommand*\@oddhead{}
417 \renewcommand*\@oddfoot{}
418 \renewcommand*\@evenhead{}
419 \renewcommand*\@evenfoot{}
420 \renewcommand*\aliaspagestyle[2]{}
421 \renewcommand*\copypagestyle[2]{}
422
423 \renewcommand*\makeevenhead[4]{}
424 \renewcommand*\makeoddhead[4]{}
425 \renewcommand*\makeevenfoot[4]{}
426 \renewcommand*\makeoddfoot[4]{}
427 \renewcommand*\makerunningwidth[3]{}
428 % \newlength{\headwidth}
429 \renewcommand*\makeheadrule[3]{}
430 \renewcommand*\makefootrule[3]{}
431 \renewcommand*\makeheadfootruleprefix[3]{}
432 % \newlength{\normalrulethickness}
433 % \setlength{\normalrulethickness}{.4pt}
434 % \newlength{\footruleheight}
435 % \newlength{\footruleskip}
436 \renewcommand*\makeheadposition[5]{}
437 \renewcommand{\makepsmarks}[2]{}
438 \renewcommand*\makeheadfootstrut[3]{}

439 \renewcommand{\createmark}[5]{\csdef{#1mark}[1]{} }
440 \renewcommand{\createplainmark}[3]{\csdef{#1mark}{} }

```

```

441 \renewcommand{\memUchead}[1]{}
442 \renewcommand*\clearplainmark}[1]{}
443 \renewcommand*\clearmark}[1]{}
444 \renewcommand{\addtopsmarks}[3]{}
445 \renewcommand{\ifonlyfloats}[2]{#2}
446 \renewcommand*\mergepagefloatstyle}[3]{}
447
448 \renewcommand*\framepichead{}
449 \renewcommand*\framepictfoot{}
450 \renewcommand*\framepichook{}
451 \renewcommand*\showheadfootlocoff{}
452 \renewcommand*\showtextblocklocoff{}

```

### § 653.9 Paragraphs and lists

```

453 \renewcommand{\hangfrom}[1]{#1}
454 \let\centerfloat\centering
455 \renewcommand*\raggedyright}[1][{}
456 % \newlength{\ragrparindent}
457 \renewcommand{\sourceatright}[2][{\attribution{#2}}
458 \let\memorigdbs\LWR@endofline
459 \let\memorigpar\par
460 \let\atcentercr\LWR@endofline
461
462 \renewcommand*\linenottooshort}[1][{}
463 \renewcommand*\russianpar{}
464 \renewcommand*\lastlinerulefill{}
465 \renewcommand*\lastlineparrule{}
466 \renewcommand*\justlastraggedleft{}
467 \renewcommand*\raggedrightthenleft{}
468 \renewcommand*\leftcenterright{}
469
470 \renewcommand{\leftspringright}[4]{%
471 \begin{minipage}{#1\linewidth}#3\end{minipage}\qqquad%
472 \begin{minipage}{#2\linewidth}\begin{flushright}#4\end{flushright}\end{minipage}%
473 }
474
475 \renewenvironment*{blockdescription}
476 {\LWR@descriptionstart\LWR@origdescription}
477 {\enddescription}
478
479 \renewcommand*\blockdescriptionlabel}[1]{\textbf{#1}}
480 \renewenvironment*{labelled}[1]{\begin{description}}{\end{description}}
481 \renewenvironment*{flexlabelled}[6]{\begin{description}}{\end{description}}
482 \renewcommand*\tightlists{}
483 \renewcommand*\defaultlists{}
484 \RenewDocumentCommand{\firmlists}{s}{}
485 \renewcommand*\firmlist{}
486 \renewcommand*\tightlist{}
487 \renewcommand*\zerotrivseps{}
488 \renewcommand*\savetrivseps{}
489 \renewcommand*\restoretrivseps{}

```

### § 653.10 Contents lists

```

490 \csletcs{tableofcontents*}{tableofcontents}
491 \csletcs{listoffigures*}{listoffigures}
492 \csletcs{listoftables*}{listoftables}
493 \renewenvironment{KeepFromToc}{}{}
494 \renewcommand*\onocoltocetc{}
495 \renewcommand*\twocoltocetc{}
496 \renewcommand*\ensureonecol{}
497 \renewcommand*\restorefromonecol{}
498 \renewcommand*\doccoltocetc{}
499
500 \renewcommand{\toheadstart}{}
501 \renewcommand{\printtoctitle}[1]{}
502 \renewcommand{\tocmark}{}
503 \renewcommand{\aftertoctitle}{}
504 \renewcommand{\lofheadstart}{}
505 \renewcommand{\printloftitle}[1]{}
506 \renewcommand{\lofmark}{}
507 \renewcommand{\afterloftitle}{}
508 \renewcommand{\lotheadstart}{}
509 \renewcommand{\printlottitle}[1]{}
510 \renewcommand{\lotmark}{}
511 \renewcommand{\afterlottitle}{}
512
513 \renewcommand*\setpnumwidth[1]{}
514 \renewcommand*\setrmarg[1]{}
515 \renewcommand*\cftbookbreak{}
516 \renewcommand*\cftpartbreak{}
517 \renewcommand*\cftchapterbreak{}

518 % \newlength{\cftbeforebookskip}
519 % \newlength{\cftbookindent}
520 % \newlength{\cftbooknumwidth}
521 \renewcommand*\cftbookfont{}
522 \renewcommand*\cftbookname{}
523 \renewcommand*\cftbookpresnum{}
524 \renewcommand*\cftbookaftersnum{}
525 \renewcommand*\cftbookaftersnumb{}
526 \renewcommand*\cftbookleader{}
527 \renewcommand*\cftbookdotsep}{1}
528 \renewcommand*\cftbookpagefont{}
529 \renewcommand*\cftbookafterpnum{}
530 \renewcommand*\cftbookformatpnum}[1]{}
531 \renewcommand*\cftbookformatpnumhook}[1]{}

```

Part is already defined by tocloft.

```

532 % \newlength{\cftbeforechapterskip}
533 % \newlength{\cftchapterindent}
534 % \newlength{\cftchapternumwidth}
535 \renewcommand*\cftchapterfont{}
536 \renewcommand*\cftchaptername{}
537 \renewcommand*\cftchapterpresnum{}
538 \renewcommand*\cftchapteraftersnum{}
539 \renewcommand*\cftchapteraftersnumb{}
540 \renewcommand*\cftchapterleader{}
541 \renewcommand*\cftchapterdotsep}{1}

```

```
542 \renewcommand*{\cftchapterpagefont}{}
543 \renewcommand*{\cftchapterafterpnum}{}
544 \renewcommand*{\cftchapterformatpnum}[1]{}
545 \renewcommand*{\cftchapterformatpnumhook}[1]{}

546 % \newlength{\cftbeforesectionskip}
547 % \newlength{\cftsectionindent}
548 % \newlength{\cftsectionnumwidth}
549 \renewcommand*{\cftsectionfont}{}
550 \renewcommand*{\cftsectionname}{}
551 \renewcommand*{\cftsectionpresnum}{}
552 \renewcommand*{\cftsectionaftersnum}{}
553 \renewcommand*{\cftsectionaftersnumb}{}
554 \renewcommand*{\cftsectionleader}{}
555 \renewcommand*{\cftsectiondotsep}{1}
556 \renewcommand*{\cftsectionpagefont}{}
557 \renewcommand*{\cftsectionafterpnum}{}
558 \renewcommand*{\cftsectionformatpnum}[1]{}
559 \renewcommand*{\cftsectionformatpnumhook}[1]{}

560 % \newlength{\cftbeforesubsections skip}
561 % \newlength{\cftsubsectionindent}
562 % \newlength{\cftsubsectionnumwidth}
563 \renewcommand*{\cftsubsectionfont}{}
564 \renewcommand*{\cftsubsectionname}{}
565 \renewcommand*{\cftsubsectionpresnum}{}
566 \renewcommand*{\cftsubsectionaftersnum}{}
567 \renewcommand*{\cftsubsectionaftersnumb}{}
568 \renewcommand*{\cftsubsectionleader}{}
569 \renewcommand*{\cftsubsectiondotsep}{1}
570 \renewcommand*{\cftsubsectionpagefont}{}
571 \renewcommand*{\cftsubsectionafterpnum}{}
572 \renewcommand*{\cftsubsectionformatpnum}[1]{}
573 \renewcommand*{\cftsubsectionformatpnumhook}[1]{}

574 % \newlength{\cftbeforesubsubsections skip}
575 % \newlength{\cftsubsubsectionindent}
576 % \newlength{\cftsubsubsectionnumwidth}
577 \renewcommand*{\cftsubsubsectionfont}{}
578 \renewcommand*{\cftsubsubsectionname}{}
579 \renewcommand*{\cftsubsubsectionpresnum}{}
580 \renewcommand*{\cftsubsubsectionaftersnum}{}
581 \renewcommand*{\cftsubsubsectionaftersnumb}{}
582 \renewcommand*{\cftsubsubsectionleader}{}
583 \renewcommand*{\cftsubsubsectiondotsep}{1}
584 \renewcommand*{\cftsubsubsectionpagefont}{}
585 \renewcommand*{\cftsubsubsectionafterpnum}{}
586 \renewcommand*{\cftsubsubsectionformatpnum}[1]{}
587 \renewcommand*{\cftsubsubsectionformatpnumhook}[1]{}

588 % \newlength{\cftbeforeparagraphskip}
589 % \newlength{\cftparagraphindent}
590 % \newlength{\cftparagraphnumwidth}
591 \renewcommand*{\cftparagraphfont}{}
592 \renewcommand*{\cftparagraphname}{}
593 \renewcommand*{\cftparagraphpresnum}{}

```

```
594 \renewcommand*{\cftparagraphaftersnum}{}
595 \renewcommand*{\cftparagraphaftersnumb}{}
596 \renewcommand*{\cftparagraphleader}{}
597 \renewcommand*{\cftparagraphdotsep}{1}
598 \renewcommand*{\cftparagraphpagefont}{}
599 \renewcommand*{\cftparagraphafterpnum}{}
600 \renewcommand*{\cftparagraphformatpnum}[1]{}
601 \renewcommand*{\cftparagraphformatpnumhook}[1]{}

602 % \newlength{\cftbeforesubparagraphskip}
603 % \newlength{\cftsubparagraphindent}
604 % \newlength{\cftsubparagraphnumwidth}
605 \renewcommand*{\cftsubparagraphfont}{}
606 \renewcommand*{\cftsubparagraphname}{}
607 \renewcommand*{\cftsubparagraphpresnum}{}
608 \renewcommand*{\cftsubparagraphaftersnum}{}
609 \renewcommand*{\cftsubparagraphaftersnumb}{}
610 \renewcommand*{\cftsubparagraphleader}{}
611 \renewcommand*{\cftsubparagraphdotsep}{1}
612 \renewcommand*{\cftsubparagraphpagefont}{}
613 \renewcommand*{\cftsubparagraphafterpnum}{}
614 \renewcommand*{\cftsubparagraphformatpnum}[1]{}
615 \renewcommand*{\cftsubparagraphformatpnumhook}[1]{}

616 % \newlength{\cftbeforefigureskip}
617 % \newlength{\cftfigureindent}
618 % \newlength{\cftfigurenumwidth}
619 \renewcommand*{\cftfigurefont}{}
620 \renewcommand*{\cftfigurename}{}
621 \renewcommand*{\cftfigurepresnum}{}
622 \renewcommand*{\cftfigureaftersnum}{}
623 \renewcommand*{\cftfigureaftersnumb}{}
624 \renewcommand*{\cftfigureleader}{}
625 \renewcommand*{\cftfiguredotsep}{1}
626 \renewcommand*{\cftfigurepagefont}{}
627 \renewcommand*{\cftfigureafterpnum}{}
628 \renewcommand*{\cftfigureformatpnum}[1]{}
629 \renewcommand*{\cftfigureformatpnumhook}[1]{}

630 % \newlength{\cftbeforesubfigureskip}
631 % \newlength{\cftsubfigureindent}
632 % \newlength{\cftsubfigurenumwidth}
633 \newcommand*{\cftsubfigurefont}{}
634 \newcommand*{\cftsubfigurename}{}
635 \newcommand*{\cftsubfigurepresnum}{}
636 \newcommand*{\cftsubfigureaftersnum}{}
637 \newcommand*{\cftsubfigureaftersnumb}{}
638 \newcommand*{\cftsubfigureleader}{}
639 \newcommand*{\cftsubfiguredotsep}{1}
640 \newcommand*{\cftsubfigurepagefont}{}
641 \newcommand*{\cftsubfigureafterpnum}{}
642 \newcommand*{\cftsubfigureformatpnum}[1]{}
643 \newcommand*{\cftsubfigureformatpnumhook}[1]{}

644 % \newlength{\cftbeforetablesip}
645 % \newlength{\cfttableindent}
```

```

646 % \newlength{\cfttablenumwidth}
647 \renewcommand*{\cfttablefont}{}
648 \renewcommand*{\cfttablename}{}
649 \renewcommand*{\cfttablepresnum}{}
650 \renewcommand*{\cfttableaftersnum}{}
651 \renewcommand*{\cfttableaftersnumb}{}
652 \renewcommand*{\cfttableleader}{}
653 \renewcommand*{\cfttabledotsep}{1}
654 \renewcommand*{\cfttablepagefont}{}
655 \renewcommand*{\cfttableafterpnum}{}
656 \renewcommand*{\cfttableformatpnum}[1]{}
657 \renewcommand*{\cfttableformatpnumhook}[1]{}

658 % \newlength{\cftbeforesubtablesip}
659 % \newlength{\cftsubtableindent}
660 % \newlength{\cftsubtablenumwidth}
661 \newcommand*{\cftsubtablefont}{}
662 \newcommand*{\cftsubtablename}{}
663 \newcommand*{\cftsubtablepresnum}{}
664 \newcommand*{\cftsubtableaftersnum}{}
665 \newcommand*{\cftsubtableaftersnumb}{}
666 \newcommand*{\cftsubtableleader}{}
667 \newcommand*{\cftsubtabledotsep}{1}
668 \newcommand*{\cftsubtablepagefont}{}
669 \newcommand*{\cftsubtableafterpnum}{}
670 \newcommand*{\cftsubtableformatpnum}[1]{}
671 \newcommand*{\cftsubtableformatpnumhook}[1]{}

672 \renewcommand*{\booknumberline}[1]{}
673 \renewcommand*{\partnumberline}[1]{}
674 \renewcommand*{\chapternumberline}[1]{}
675 \renewcommand*{\numberlinehook}[1]{}
676 % \renewcommand*{\cftwhatismyname}{}%
677 \renewcommand*{\booknumberlinehook}[1]{}
678 \renewcommand*{\partnumberlinehook}[1]{}
679 \renewcommand*{\chapternumberlinehook}[1]{}
680 \renewcommand{\numberlinebox}[2]{}
681 \renewcommand{\booknumberlinebox}[2]{}
682 \renewcommand{\partnumberlinebox}[2]{}
683 \renewcommand{\chapternumberlinebox}[2]{}
684 %
685 % \newlength{\cftparfillskip}
686 \renewcommand*{\cftpagenumbersoff}[1]{}
687 \renewcommand*{\cftpagenumberon}[1]{}
688 \renewcommand*{\cftlocalchange}[3]{}
689 \renewcommand*{\cftaddtitleline}[4]{}
690 \renewcommand*{\cftaddnumtitleline}[4]{}
691 \renewcommand{\cftinsertcode}[2]{}
692 \renewcommand{\cftinserthook}[2]{}
693 \renewcommand{\settocpreprocessor}[2]{}
694 \DeclareRobustCommand{\cftpagenumbersoff}[1]{}
695 \DeclareRobustCommand{\cftpagenumberon}[1]{}

```

## § 653.11 Floats and captions

`\@xfloat`

`\xdblfloat` Reestablish lwarp's takeover the float handing, which memoir tried to grab:

```

696 \AtBeginDocument{
697 \def\xfloat #1[#2]{%
698 \LWR@floatbegin{#1}[#2]
699 \normalsize
700 \@nameuse{#1adjustment}%
701 \LWR@futurenonspacel\LWR@mynexttoken\LWR@floatalignment%
702 }
703 \def\xdblfloat #1[#2]{%
704 \LWR@floatbegin{#1}[#2]
705 \normalsize
706 \@nameuse{#1adjustment}%
707 \LWR@futurenonspacel\LWR@mynexttoken\LWR@floatalignment%
708 }
709 }

```

`\newfloat` [*<1: within>*] [*<2: type>*] [*<3: ext>*] [*<4: capname>*]

```

710 \RenewDocumentCommand{\newfloat}{o m m m}{%
711 \def\LWR@tempone{#4}%
712 \def\LWR@temptwo{\@nameuse{#2name}}%
713 \ifdefequal{\LWR@tempone}{\LWR@temptwo}{% recursive name, already defined
714 \IfValueTF{#1}%
715 {\DeclareFloatingEnvironment[fileext=#3,within=#1]{#2}}%
716 {\DeclareFloatingEnvironment[fileext=#3]{#2}}%
717 }{% not recursive name
718 \IfValueTF{#1}%
719 {\DeclareFloatingEnvironment[fileext=#3,within=#1,name={#4}]{#2}}%
720 {\DeclareFloatingEnvironment[fileext=#3,name={#4}]{#2}}%
721 }%

```

`newfloat` package automatically creates the `\listof` command for new floats, but `float` does not, so remove `\listof` here in case it is manually created later.

```

722 \cslet{listof#2s}\relax%
723 \cslet{listof#2es}\relax%
724 }

```

`\newlistof` [*<within>*] [*<type>*] [*<ext>*] [*<listofname>*]

Emulated through the `\newfloat` mechanism. Note that memoir uses a different syntax than `tocloft` for the name.

```

725 \RenewDocumentCommand{\newlistof}{o m m m}
726 {%
727 \IfValueTF{#1}%
728 {\newlistentry[#1]{#2}{#3}{0}}%
729 {\newlistentry{#2}{#3}{0}}%
730 \@namedef{ext@#2}{#3}%
731 \@ifundefined{c@#3depth}{\newcounter{#3depth}}{%
732 \setcounter{#3depth}{1}%
733 \@namedef{#3mark}{}%
734 \@namedef{#2}{\listof{#2}{#4}}%
735 \@namedef{cftmake#3title}{}%
736 \@ifundefined{cftbefore#3titleskip}{%
737 \expandafter\newlength\csname cftbefore#3titleskip\endcsname%

```

```

738 \expandafter\newlength\csname cftafter#3titleskip\endcsname%
739 }{}%
740 \@namedef{cft#3titlefont}{}%
741 \@namedef{cftafter#3title}{}%
742 \@namedef{cft#3prehook}{}%
743 \@namedef{cft#3posthook}{}%
744 }

```

```
745 \renewcommand{\setfloatadjustment}[2]{}

```

Borrowed from the lwarp version of keyfloat:

```

746 \NewDocumentEnvironment{KFLTmemoir@marginfloat}{0{-1.2ex} m}
747 {% start
748 \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
749 \renewcommand*\@capttype{#2}%
750 }
751 {%
752 \endLWR@BlockClassWP%
753 }
754
755 \DeclareDocumentEnvironment{marginfigure}{o}
756 {\begin{KFLTmemoir@marginfloat}{figure}}
757 {\end{KFLTmemoir@marginfloat}}
758
759 \DeclareDocumentEnvironment{margintable}{o}
760 {\begin{KFLTmemoir@marginfloat}{table}}
761 {\end{KFLTmemoir@marginfloat}}

762 \renewcommand{\setmarginfloatcaptionadjustment}[2]{}
763 \renewcommand{\setmpjustification}[2]{}
764 \renewcommand*\@mpjustification{}
765 \renewcommand*\setfloatlocations}[2]{}
766 \DeclareDocumentCommand\suppressfloats{o}{}
767 \renewcommand*\FloatBlock{}
768 \renewcommand*\FloatBlockAllowAbove{}
769 \renewcommand*\FloatBlockAllowBelow{}
770 \renewcommand*\setFloatBlockFor{}
771
772 \renewcommand{\captiontitlefinal}[1]{}

```

`\flegtable`, `\flegfigure`, `\flegtocfigure` are defined by memoir using `\newfloat`. These are defined with an @ in ccaption.

```

773 \renewcommand{\flegtable}{\tablename}
774 \renewcommand{\flegfigure}{\figurename}
775 \renewcommand{\flegtocfigure}{}
776 \renewcommand{\flegtocfigure}{}

777 \renewcommand{\@makesubfloatcaption}[2]{%
778 \minipagefullwidth
779 \begin{minipage}{\linewidth}%
780 #1 \ignorespaces #2 \unskip%

```

```

781 \end{minipage}
782 }
783
784 \renewcommand*\tightsubcaptions{}
785 \renewcommand*\loosesubcaptions{}
786
787 \renewcommand*\subcaptionsize[1]{}
788 \renewcommand*\subcaptionlabelfont[1]{}
789 \renewcommand*\subcaptionfont[1]{}
790 \renewcommand*\subcaptionstyle[1]{}
791
792 \renewcommand*\hangsubcaption{}
793 \renewcommand*\shortsubcaption{}
794 \renewcommand*\normalsubcaption{}
795
796 \RenewDocumentEnvironment{sidecaption}{o m o}
797 {}
798 {%
799 \IfValueTF{#1}{\caption[#1]{#2}}{\caption{#2}}%
800 \IfValueT{#3}{\label{#3}}%
801 }
802
803 % \newlength{\sidecapwidth}
804 % \newlength{\sidecapsep}
805 \renewcommand*\setsidecaps[2]{}
806 \renewcommand*\sidecapmargin[1]{}
807 % \newif\ifscapmargleft
808 \scapmargleftfalse
809 \renewcommand*\setsidecappos[1]{}

```

Env sidecontcaption

```

810 \RenewDocumentEnvironment{sidecontcaption}{m o}
811 {}
812 {%
813 \ifdef{\ContinuedFloat}%
814 {\ContinuedFloat}%
815 {\addtocounter{\@capttype}{-1}}%
816 \caption{#1}%

```

Without \@capttype, the section is referred to instead.

```

817 \IfValueT{#2}{\label[\@capttype]{#2}}%
818 }

```

\sidenamedlegend does not appear to use the toc argument.

```

819 \renewenvironment{sidenamedlegend}[2][]{
820 \begin{center}
821 \@nameuse{\@capttype name}\CaptionSeparator#2
822 \end{center}
823 }
824 {}
825
826 \renewenvironment{sidelegend}[1]
827 {\begin{center}

```

```

828 #1
829
830 }
831 {\end{center}}
832
833 \renewcommand*\sidecapstyle{}
834 \renewcommand*\overridescapmargin}[1]{}
835 % \newlength{\sidecapraise}
836 \renewcommand*\sidecapfloatwidth{\linewidth}
837
838 \LetLtxMacro\ctabular\ctabular
839 \LetLtxMacro\endctabular\endctabular
840
841 \renewcommand{\autorows}[5][1]{%
842 #5%
843 }
844
845 \renewcommand{\autocol}[5][1]{%
846 #5%
847 }

```

## § 653.12 Footnotes and page notes

```

848 \renewcommand*\feetabovelfloat{}
849 \renewcommand*\feetbelowfloat{}
850 \renewcommand*\feetatbottom{}
851
852 \renewcommand*\verbfootnote}[2][1]{%
853 \PackageError{lwarp, memoir}%
854 {Verbatim footnotes are not yet supported by lwarp}%
855 {This may be improved some day.}%
856 }
857
858 \renewcommand*\plainfootnotes{}
859 \renewcommand*\twocolumnfootnotes{}
860 \renewcommand*\threecolumnfootnotes{}
861 \renewcommand*\paragraphfootnotes{}
862 \renewcommand*\footfudgefiddle{}
863
864 \renewcommand*\newfootnoteseries}[1]{%
865 \PackageError{lwarp, memoir}%
866 {Memoir footnote series are not yet supported by lwarp}%
867 {This may be improved some day.}%
868 }
869
870 \renewcommand*\plainfootstyle}[1]{}
871 \renewcommand*\twocolumnfootstyle}[1]{}
872 \renewcommand*\threecolumnfootstyle}[1]{}
873 \renewcommand*\paragraphfootstyle}[1]{}
874
875 \renewcommand*\footfootmark{}
876 \renewcommand*\footmarkstyle}[1]{}
877
878 % \newlength{\footmarkwidth}
879 % \newlength{\footmarksep}

```

```
880 % \newlength{\footparindent}
881
882 \renewcommand*{\foottextfont}{}
883
884 \renewcommand*{\marginparmargin}[1]{}
885 \renewcommand*{\sideparmargin}[1]{}
886
887 \LetLtxMacro\sidepar\marginpar
888 \renewcommand*{\sideparfont}{}
889 \renewcommand*{\sideparform}{}
890 \LWR@provideLength{\sideparvshift}
891
892 \renewcommand*{\parnopar}{}
893
894 \renewcommand{\sidebar}[1]{\begin{quote}#1\end{quote}}
895 \renewcommand*{\sidebarmargin}[1]{}
896 \renewcommand*{\sidebarfont}{}
897 \renewcommand*{\sidebarform}{}
898 % \newlength{\sidebarhsep}
899 % \newlength{\sidebarvsep}
900 % \newlength{\sidebarwidth}
901 % \newlength{\sidebartopsep}
902 \renewcommand{\setsidebarheight}[1]{}
903 \renewcommand*{\setsidebars}[6]{}
904 \renewcommand*{\footnotesatfoot}{}
905 \renewcommand*{\footnotesinmargin}{}
906
907 \LetLtxMacro\sidefootnote\footnote
908 \LetLtxMacro\sidefootnotemark\footnotemark
909 \LetLtxMacro\sidefootnotetext\footnotetext
910
911 \renewcommand*{\sidefootmargin}[1]{}
912 % \newlength{\sidefootsep}
913 % \newlength{\sidefootvsep}
914 % \newlength{\sidefootwidth}
915 % \newlength{\sidefootadjust}
916 % \newlength{\sidefootheight}
917 \renewcommand*{\setsidefootheight}[1]{}
918 % \renewcommand*{\sidefootfont}{}% in docs but not in the package
919 \renewcommand*{\setsidefeet}[6]{}
920 \renewcommand*{\sidefootmarkstyle}[1]{}
921 \renewcommand*{\sidefoottextfont}{}
922 \renewcommand*{\sidefootform}{}

923 \renewcommand*{\continuousnotenums}{\pncontopttrue}% from pagenote
924 \renewcommand*{\notepageref}{}
925 \renewcommand*{\prenotetext}{}
926 \renewcommand*{\postnotetext}{}
927 \LetLtxMacro\printpageinnoteshyperref\printpageinnotes
928 \renewcommand*{\foottopagenote}{}
929 \renewcommand*{\pagetofootnote}{}

```

`\m@m@wrpnote`

`\startnoteentrystart` To have `cleveref` work with page note labels, the following patch writes `\thepagenote` and also adds `\arabic{pagenote}` to the first argument written to the `.ent` file:

```
\startnoteentry{\thepagenote}{\arabic{pagenote}} . . .
```

The arabic value is required for `cleveref`. `\thepagenote` becomes `\@firstoftwo#1` and the arabic value becomes `\@secondoftwo#1`.

 `\nameref` Note that for print mode, `\nameref` print the section name where the page notes are declared in the text, but for HTML it prints the name where the page notes are printed.

```
930 \xpatchcmd{\m@m@wrpnote}
931 {\string\startnoteentry{\thepagenote}}
932 {\string\startnoteentry{\thepagenote}{\arabic{pagenote}}}}
933 {}
934 {\LWR@patcherror{memoir}{m@m@wrpnote}}
935
936 \renewcommand\startnoteentrystart[4]{%
937 \prenoteinnotes%
938 \noteidinnotes{\@firstoftwo#1}{#2}%
939 \ifmtarg{#2}{%
940 \phantomsection\def\@currentlabel{#1}% original
941 \def\@currentlabel{\@firstoftwo#1}% lwarp
942 \def\cref@currentlabel{% lwarp
943 [pagenote][\@secondoftwo#1][\@firstoftwo#1% lwarp
944]}% lwarp
945 }{}%
946 \pagenoteanchor{#4}%
947 \pageinnotes{#3}%
948 \prenotetext%
949 }
```

### § 653.13 Decorative text

```
950 \renewcommand*\epigraphposition[1]{}
951 \renewcommand*\epigraphtextposition[1]{}
952 \renewcommand*\epigraphsourceposition[1]{}
953 \renewcommand*\epigraphfontsize[1]{}
954 \renewcommand*\epigraphforheader[2]{}
955 \renewcommand*\epigraphpicture{}
```

### § 653.14 Poetry

```
956 \renewcommand*\vinphantom{}
957 \renewcommand*\vleftofline[1]{#1}
958 % \let\linenumberfrequency\poemlines
959 % \renewcommand*\linenumberfont[1]{}
960
961 \DeclareDocumentCommand{\PoemTitle}{s o m}{%
962 \IfValueTF{#2}%
963 {\poemtitle[#2]{#4}}%
964 {\poemtitle{#4}}%
965 }
966
967 \renewcommand*\NumberPoemTitle{}
```

```

968 \renewcommand*\PlainPoemTitle{}
969 \renewcommand*\poemtitlestyle{}
970 \renewcommand*\poemtitlestar[1]{}
971 \renewcommand*\poemtitlestarstyle{}
972 \renewcommand*\PoemTitleheadstart{}
973 \renewcommand*\printPoemTitlenonum{}
974 \renewcommand*\printPoemTitlenum{}
975 \renewcommand*\afterPoemTitlenum{}
976 \renewcommand*\printPoemTitletitle[1]{}
977 \renewcommand*\afterPoemTitle{}
978 \newlength{\midpoemtitleskip}
979 \renewcommand*\PoemTitlenumfont{}
980 \renewcommand*\PoemTitlefont{}

```

### § 653.15 Boxes, verbatims and files

```

981 \renewenvironment{qframe}{\framed}\endframed}
982 \renewenvironment{qshade}{\shaded}\endshaded}

983 \renewcommand*\setverbatimfont[1]{}
984 \renewcommand*\tabson[1]{}
985 \renewcommand*\tabsoff{}
986 \renewcommand*\wrappingon{}
987 \renewcommand*\wrappingoff{}
988 \renewcommand*\verbatimindent{}
989 \renewcommand*\verbatimbreakchar[1]{}

990 \DefineVerbatimEnvironment{fboxverbatim}{Verbatim}{frame=single}

```

`boxedverbatim` is already defined by `moreverb`. `boxedverbatim*` does not appear to work at all, even in a minimal print memoir document.

```

991 \renewcommand*\bvbox{}
992 \renewcommand*\bvtopandtail{}
993 \renewcommand*\bvtopandtail{}
994 \renewcommand*\nobvbox{}
995 % \newlength\bvboxsep
996 \renewcommand*\bvtoprulehook{}
997 \renewcommand*\bvtopmidhook{}
998 \renewcommand*\bvendrulehook{}
999 \renewcommand*\bvleftsidehook{}
1000 \renewcommand*\bvrightsidehook{}
1001 \renewcommand*\bvperpagetrue{}
1002 \renewcommand*\bvperpagefalse{}
1003 \renewcommand*\bvtopofpage[1]{}
1004 \renewcommand*\bvendofpage[1]{}
1005 \renewcommand*\linenumberfrequency[1]{}
1006 \renewcommand*\resetbvlینumber{}
1007 \renewcommand*\setbvlینums[2]{}
1008 \renewcommand*\linenumberfont[1]{}
1009 \renewcommand*\bvnumbersinside{}
1010 \renewcommand*\bvnumbersoutside{}

```

### § 653.16 Cross referencing

```

1011 \renewcommand*\fref}[1]{\cref{#1}}
1012 \renewcommand*\tref}[1]{\cref{#1}}
1013 \renewcommand*\pref}[1]{\cpageref{#1}}
1014 \renewcommand*\Aref}[1]{\cref{#1}}
1015 \renewcommand*\Bref}[1]{\cref{#1}}
1016 \renewcommand*\Pref}[1]{\cref{#1}}
1017 \renewcommand*\Sref}[1]{\cref{#1}}
1018 \renewcommand*\figurerefname}{Figure}
1019 \renewcommand*\tablerefname}{Table}
1020 \renewcommand*\pagerefname}{page}
1021 \renewcommand*\bookrefname}{Book~}
1022 \renewcommand*\partrefname}{Part~}
1023 \renewcommand*\chapterrefname}{Chapter~}
1024 \renewcommand*\sectionrefname}{\S}
1025 \renewcommand*\appendixrefname}{Appendix~}
1026 \LetLtxMacro\titleref\nameref
1027 \renewcommand*\headnameref{}{}
1028 \renewcommand*\tocnameref{}{}
1029
1030 \providecounter{LWR@currenttitle}
1031
1032 \renewcommand*\currenttitle}{%
1033 \addtocounter{LWR@currenttitle}{1}%
1034 \label{currenttitle\arabic{LWR@currenttitle}}%
1035 \nameref{currenttitle\arabic{LWR@currenttitle}}%
1036 }
1037
1038 \renewcommand*\theTitleReference}[2]{}
1039 \renewcommand*\namerefon{}{}
1040 \renewcommand*\namerefoff{}{}

```

### § 653.17 **Back matter**

`\@@wrindexhyp` Redefined to write the `LWR@autoindex` counter instead of page. Note that memoir has two versions, depending on the use of `hyperref`.

```

1041 \AtBeginDocument{
1042
1043 \def\@@wrindexhyp#1||\{\%
1044 \addtocounter{LWR@autoindex}{1}%
1045 \label{LWRindex-\arabic{LWR@autoindex}}%
1046 % \ifshowindexmark\@showidx{#1}\fi
1047 \protected@write\@auxout{}%
1048 % {\string\@@wrindexm@m{\idxfile}{#1}{\thepage}}%
1049 {\string\@@wrindexm@m{\idxfile}{#1}{\arabic{LWR@autoindex}}}%
1050 \endgroup
1051 \@esphack}%

```

`\@@wrspindexhyp` `\specialindex` behaves like a regular `\index`, pointing to where `\specialindex` is used. If `\specialindex` is used inside a figure or table after the `\caption`, then the hyperlink will be given the name of that particular figure or table.

```

1052 \def\@@wrspindexhyp#1||\{\%
1053 \addtocounter{LWR@autoindex}{1}%
1054 \label{LWRindex-\arabic{LWR@autoindex}}%

```

```

1055 % \ifshowindexmark\@showidx{#1}\fi
1056 \protected@write\@auxout{%
1057 % {\string\@wrindexm@m{\@idxfile}{#1}{\@nameuse{the\@sptheid}}}%
1058 % {\string\@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}}%
1059 \endgroup
1060 \@esphack}%
1061
1062 }% \AtBeginDocument

```

`\@spindex` Patched to append `_html` to the file:

```

1063 \renewcommand{\@spindex}[2]{%
1064 \ifundefined{#1@idxfile}%
1065 {\ifreportnoidxfile
1066 \@memwarn{Undefined index file #1}%
1067 \fi
1068 \begingroup
1069 \@sanitize
1070 \@nowrindex}%
1071 {\def\@idxfile{#1_html}%
1072 \def\@sptheid{#2}%
1073 \begingroup
1074 \@sanitize
1075 \@wrspindex}}

```

`\makeindex` Patched to use `_html` filename and `\BaseJobname`:

```

1076 \catcode'_ =12%
1077 \renewcommand*\makeindex[1][\BaseJobname]{%
1078 \if@filesw
1079 \def\gindex{\@bsphack%
1080 \@ifnextchar [{\@index}{\@index[\BaseJobname]}}
1081 \def\specialindex{\@bsphack\@spindex}%
1082 \makememindexhook
1083 \expandafter\newwrite\csname #1@idxfile\endcsname
1084 \expandafter\immediate\openout \csname #1@idxfile\endcsname #1_html.idx\relax
1085 \typeout{Writing index file #1_html.idx }%
1086 \fi}
1087 \catcode'_ =8%

```

`\printindex` Patched to use `_html` filename and `\BaseJobname`. This will later be patched by the **lwarp** core.

```

1088 \catcode'_ =12%
1089 \renewcommand{\printindex}[1][\BaseJobname]{\input{#1_html.ind}}
1090 \catcode'_ =8%

1091 \DeclareDocumentCommand{\newblock}{}{}
1092 %
1093 \renewcommand*\showindexmarks{}
1094 \renewcommand*\hideindexmarks{}
1095
1096 \renewcommand*\xindyindex{}

```

§ 653.18 **Miscellaneous**

```

1097 \renewcommand*\changemarks{}
1098 \renewcommand*\nochangemarks{}
1099 \renewcommand*\added[1]{}
1100 \renewcommand*\deleted[1]{}
1101 \renewcommand*\changed[1]{}
1102
1103 \renewcommand*\showtrimsoff{}
1104 \renewcommand*\showtrimson{}
1105 \renewcommand*\trimXmarks{}
1106 \renewcommand*\trimLmarks{}
1107 \renewcommand*\trimFrame{}
1108 \renewcommand*\trimNone{}
1109 \renewcommand*\trimmarkscolor{}
1110 \renewcommand*\trimmarks{}
1111 \renewcommand*\tmarktl{}
1112 \renewcommand*\tmarktr{}
1113 \renewcommand*\tmarkbr{}
1114 \renewcommand*\tmarkbl{}
1115 \renewcommand*\tmarktm{}
1116 \renewcommand*\tmarkmr{}
1117 \renewcommand*\tmarkbm{}
1118 \renewcommand*\tmarkml{}
1119 \renewcommand*\trimmark{}
1120 \renewcommand*\quarkmarks{}
1121 \renewcommand*\registrationColour[1]{}
1122
1123 \renewcommand*\leavespergathering[1]{}
1124
1125 \renewcommand*\noprelistbreak{}
1126
1127 \renewcommand*\cleartorecto{}
1128 \renewcommand*\cleartoverso{}
1129
1130 \renewenvironment{vplace}[1][1]{}{}

```

§ 653.19 **caption emulation**

```

1131 \renewcommand*\captiondelim[1]{\renewcommand*\CaptionSeparator}{#1}}
1132 \renewcommand*\captionnamefont[1]{}
1133 \renewcommand*\captiontitlefont[1]{}
1134 \renewcommand*\flushleftright{}
1135 \renewcommand*\centerlastline{}
1136 \renewcommand*\captionstyle[2][1]{}
1137 \DeclareDocumentCommand\captionwidth{m}{}
1138 \renewcommand*\changecaptionwidth{}
1139 \renewcommand*\normalcaptionwidth{}
1140 \renewcommand*\hangcaption{}
1141 \renewcommand*\indentcaption[1]{}
1142 \renewcommand*\normalcaption{}
1143 \renewcommand\precaption[1]{}
1144 \renewcommand\postcaption[1]{}
1145 \renewcommand\midbication[1]{}
1146 \renewcommand\contcaption[1]{%
1147 % \ContinuedFloat%

```

```

1148 % \caption{#1}%
1149 \begin{LWR@figcaption}% later becomes \caption*
1150 \LWR@isolate{\@nameuse{\@capttype name}}~%
1151 \thechapter.\the\value{\@capttype}\CaptionSeparator\LWR@isolate{#1}%
1152 \end{LWR@figcaption}%
1153 }

1154 \newlength{\abovelegendskip}
1155 \setlength{\abovelegendskip}{0.5\baselineskip}
1156 \newlength{\belowlegendskip}
1157 \setlength{\belowlegendskip}{\abovelegendskip}

```

The extra `\\` here forces a `<br>` in HTML when `\legend` is used in a `\marginpar`.

```

1158 \renewcommand{\legend}[1]{\begin{center}#1\\end{center}}
1159
1160 \renewcommand{\namedlegend}[2][]{%
1161 \begin{center}
1162 \@nameuse{fleg\@capttype}\CaptionSeparator#2\\
1163 \end{center}
1164 \@nameuse{flegtoc\@capttype}{#1}
1165 }

```

`\flegtable`, `\flegfigure`, `\flegtocable`, `\flegtocfigure` are defined by memoir using `\newfloat`. These are defined with an `@` in `ccaption`.

```

1166 \renewcommand{\newfixedcaption}[3][\caption]{%
1167 \renewcommand{#2}{\def\@capttype{#3}#1}}
1168 \renewcommand{\renfixedcaption}[3][\caption]{%
1169 \renewcommand{#2}{\def\@capttype{#3}#1}}
1170 \renewcommand{\providfixedcaption}[3][\caption]{%
1171 \providecommand{#2}{\def\@capttype{#3}#1}}
1172
1173 \renewcommand{\bitwonumcaption}[6][]{%
1174 \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
1175 \addtocounter{\@capttype}{-1}%
1176 \begingroup%
1177 \csdef{\@capttype name}{#4}%
1178 \ifblank{#5}{\caption{#6}}{\caption[#5]{#6}}%
1179 \endgroup%
1180 \ifblank{#1}{\label{#1}}%
1181 }
1182
1183 \LetLtxMacro\bionenumcaption\bitwonumcaption% todo
1184
1185 \renewcommand{\bicaption}[5][]{%
1186 \ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
1187 \begin{LWR@figcaption}% later becomes \caption*
1188 \LWR@isolate{#4} % space
1189 \thechapter.\the\value{\@capttype}\CaptionSeparator\LWR@isolate{#5}%
1190 \end{LWR@figcaption}%
1191 \ifblank{#1}{\label{#1}}%
1192 }
1193
1194 \renewcommand{\bicontcaption}[3]{%
1195 \contcaption{#1}%

```

```

1196 \begingroup%
1197 \csdef{\@capttype name}{#2}%
1198 \contcaption{#3}%
1199 \endgroup%
1200 }

```

Only in ccaption, not in memoir:

```

1201 % \LetLtxMacro\longbitwonumcaption\bitwonumcaption%
1202 % \LetLtxMacro\longbionenumcaption\bitwonumcaption%
1203 % \LetLtxMacro\longbicaption\bicaption%

```

Patches for subfloats to support additional lwarp labels:

```

1204 \renewcommand{\@memsubbody}{%
1205 \bgroup
1206 \let\label=\memsub@label
1207 \ifdonemaincaption\else
1208 \advance\csname c@\@capttype\endcsname\@ne
1209 \fi
1210 % \refstepcounter{sub\@capttype}\@contkeep%
1211 % \leavevmode\lwarp
1212 \ifnextchar [%
1213 {\@memsubfig}%
1214 {\@memsubfig[\@empty]}}
1215
1216 \renewcommand{\@memcontsubbody}{%
1217 \bgroup
1218 \let\label=\memsub@label
1219 \@contset
1220 % \refstepcounter{sub\@capttype}\@contkeep%
1221 % \leavevmode\lwarp
1222 \ifnextchar [%
1223 {\@memsubfig}%
1224 {\@memsubfig[\@empty]}}
1225
1226
1227 \long\def\@memsubfloat#1[#2][#3]#4{%
1228 % \@tempcnta=\@ne
1229 % \if@tightsubcap
1230 % \if@minipage
1231 % \@tempcnta=\z@
1232 % \else
1233 % \ifdim\lastskip=\z@
1234 % \@tempcnta=\@ne
1235 % \else
1236 % \@tempcnta=\tw@
1237 % \fi
1238 % \fi
1239 % \fi
1240 % \if@contbotsub
1241 % \def\subfig@top{\subfloattopskip}%
1242 % \def\subfig@bottom{\subfloatbottomskip}%
1243 % \else
1244 % \def\subfig@top{\subfloatbottomskip}%

```

```

1245 % \def\subfig@bottom{\subfloattopskip}%
1246 % \fi
1247 % \setbox\@tempboxa \hbox{#4}%
1248 % \@tempdima=\wd\@tempboxa
1249 % \vbox
1250 \bgroup%
1251 \mem@step@subcounter%
1252 % \vbox
1253 \LWR@stoppars%
1254 \minipagefullwidth% lwarp
1255 \begin{minipage}{\linewidth}% lwarp
1256 \bgroup
1257 % \ifcase\@tempcnta
1258 % \@minipagefalse
1259 % \or
1260 % \vspace{\subfig@top}
1261 % \or
1262 % \ifdim \lastskip=\z@ \else
1263 % \@tempskipb\subfig@top\@xaddvskip
1264 % \fi
1265 % \fi
1266 \if@contbotsub
1267 #4% \box\@tempboxa
1268 \egroup
1269 \ifx \@empty#3\relax \else
1270 % \vskip\subfloatcapskip
1271 % \@memsubcaption{#1}{#2}{#3}%
1272 % \fi
1273 \else
1274 \ifx \@empty#3\relax \else
1275 % \@memsubcaption{#1}{#2}{#3}%
1276 % \vskip\subfloatcapskip
1277 % \vskip\subfloatcaptopadj
1278 \fi\egroup
1279 #4% \box\@tempboxa
1280 \fi
1281 % \vspace{\subfig@bottom}
1282 \end{minipage}% lwarp
1283 \LWR@startpars% lwarp
1284 \egroup
1285 \egroup
1286 }

```

### § 653.20 Final patchwork

```

1287 \newlistof{tableofcontents}{toc}{\contentsname}
1288 \newlistof{listoffigures}{lof}{\listfigurename}
1289 \newlistof{listoftables}{lot}{\listtablename}

```

File 548 **lwarp-common-multimedia.sty**

§ 654 Package **common-multimedia**

Pkg lwarp-common-multimedia Common code for multimedia, movie15, and media9.

The packages `multimedia`, `movie15`, and `media9` are supported.

HTML5 `<audio>` and `<video>` objects are created for `.mp3` and `.mp4` files.

HTML5 `<embed>` objects are created for `http` and `ftp` links.

`\href` links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For `media9`, a multimedia object is inserted for each `addressource=`, as well as each `flashvars source=` and `src=`. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside `\warpprintonly` or the `warpprint` environment.

Each HTML multimedia object includes the poster text, except for `<embed>` objects. For `movie15`, the `text` option is supported to specify the poster text.

The `width`, `height`, and `totalheight` options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

`media9 \addmediapath` is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each `<audio>` and `<video>` object.

`media9` slideshows are not supported.

`\hyperlinkmovie`, `\movieref`, and `\mediabutton` are not supported.

3D objects are not supported.

If using a YOUTUBE™ video, use an “embedded” URL with `.../embed/...` instead of `.../v/...`

**for HTML output:**

```
1 \ProvidesPackage{lwarp-common-multimedia}[2019/04/22]
2 \RequirePackage{xkeyval}
3
4 \define@key{LWR@multimedia}{width}{\setlength{\LWR@multimedia@width}{#1}}
5 \define@key{LWR@multimedia}{height}{\setlength{\LWR@multimedia@height}{#1}}
6 \define@key{LWR@multimedia}{totalheight}{\setlength{\LWR@multimedia@height}{#1}}
```

```

7 \newlength{\LWR@multimedia@width}
8 \newlength{\LWR@multimedia@height}
9 \newlength{\LWR@multimedia@maxdimension}

```

`\LWR@multimedia@printsiz` Proportional to `\linewidth` and the viewport's smaller dimension. This scales each object such that it will always fit on the screen, even if a tall or wide object inside a tall or wide viewport.

```

10 \newcommand*\LWR@multimedia@printsiz{%
11 \setlength{\LWR@multimedia@maxdimension}{%
12 \maxof%
13 {\linewidth}%
14 {\maxof{\LWR@multimedia@width}{\LWR@multimedia@height}}%
15 }%
16 \setlength{\LWR@multimedia@maxdimension}{1.1\LWR@multimedia@maxdimension}%
17 \ifdimgreater{\LWR@multimedia@width}{0pt}{%
18 width:%
19 \LWR@printpercentlength%
20 {\LWR@multimedia@width}%
21 {\LWR@multimedia@maxdimension}vmin ; % space
22 }{}%
23 \ifdimgreater{\LWR@multimedia@height}{0pt}{%
24 height:%
25 \LWR@printpercentlength%
26 {\LWR@multimedia@height}%
27 {\LWR@multimedia@maxdimension}vmin ; % space
28 }{}%
29 }

```

`\LWR@multimedia@fileAV` `{\langle poster text \rangle}{\langle filename \rangle}{\langle audio/video \rangle}{\langle mimetype \rangle}`

Creates a video or audio from a file. The 2019/10 update of the L<sup>A</sup>T<sub>E</sub>X kernel may cause extra quotes to be added in the filenames. They are removed here.

```

30 \newcommand*\LWR@multimedia@fileAV[4]{%
31 \IfFileExists{#2}{% also sets \@filef@und
32 \StrSubstitute[100]{\@filef@und}{"}{[\LWR@parsedfilename]}%

```

The container `<div>` is sized as desired.

```

33 \ifstrequal{#3}{audio}{%
34 \begin{BlockClass}{AVviewport}
35 }{%
36 \begin{BlockClass}[\LWR@multimedia@printsiz\ margin:auto]{AVviewport}
37 }

```

Paragraph tags are unnecessary for the A/V tags.

```

38 \LWR@stoppars

```

The A/V element is 100% of the container.

```

39 \LWR@htmltag{%
40 #3\ % space
41 \ifstrequal{#3}{audio}{}{}%
42 width=\textquotedbl{}100%\textquotedbl\ % space
43 height=\textquotedbl{}100%\textquotedbl\ % space

```

```

44 }%
45 controls%
46 } \LWR@orignewline

```

The file source and type:

```

47 \LWR@htmltag{%
48 source % space
49 src=\textquotedbl%
50 \LWR@parsedfilename\unskip\textquotedbl\ % space
51 type=\textquotedbl{#4\textquotedbl}

```

The poster text inside paragraph tags, along with a reference to the file.

```

52 \LWR@startpars
53 \LWR@href{\LWR@parsedfilename}{#1}
54 \LWR@stoppars

```

Finish.

```

55 \LWR@htmltag{/#3}\LWR@orignewline
56 \end{BlockClass}
57 }{%
58 \PackageError{lwarp-common-multimedia}
59 {File '#2' not found}
60 {Perhaps an incorrect path?}
61 }%
62 }

```

```
\LWR@multimedia@httpAV {<poster text>} {<filename>} {<audio/video>} {<mimetype>}
```

Creates a video or audio from a URL link.

```
63 \newcommand*\LWR@multimedia@httpAV}[4]{%
```

The container <div> is sized as desired.

```

64 \ifstrequal{#3}{audio}{%
65 \begin{BlockClass}{AVviewport}
66 }{%
67 \begin{BlockClass}[\LWR@multimedia@printsizel margin:auto]{AVviewport}
68 }

```

Paragraph tags are unnecessary for the A/v tags.

```
69 \LWR@stoppars
```

The A/v element is 100% of the container.

```

70 \LWR@htmltag{%
71 #3\ % space
72 \ifstrequal{#3}{audio}{}%
73 width=\textquotedbl{100\%\textquotedbl\ % space
74 height=\textquotedbl{100\%\textquotedbl\ controls%
75 }%
76 } \LWR@orignewline

```

The file source and type:

```

77 \LWR@htmltag{%
78 source % space
79 src=\textquotedbl#2\textquotedbl\ % space

```

```
80 type=\textquotedbl#4\textquotedbl}
```

The poster text inside paragraph tags, along with a reference to the URL.

```
81 \LWR@startpars
82 \LWR@href{#2}{#1}
83 \LWR@stoppars
```

Finish.

```
84 \LWR@htmltag{/#3}\LWR@orignewline
85 \end{BlockClass}
86 }
```

```
\LWR@multimedia@AV {<poster text>} {<filename>} {<audio/video>} {<mimetype>}
```

Creates an audio or video from a file or a URL.

```
87 \newcommand*\LWR@multimedia@AV[4]{%
88 \IfBeginWith{#2}{http}%
89 {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
90 {%
91 \IfBeginWith{#2}{HTTP}%
92 {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
93 {\LWR@multimedia@fileAV{#1}{#2}{#3}{#4}}%
94 }%
95 }
```

```
\LWR@multimedia@embed {<poster text>} {<URL or filename>} {<mime type>}
```

Embeds multimedia of an arbitrary type. The poster text is not used, as it would appear along with the video if the <embed> element is supported.

```
96 \newcommand*\LWR@multimedia@embed[3]{%
97 \begin{BlockClass}[width:100\%]{AVviewport}%
98 \LWR@stoppars
99 \LWR@htmltag{%
100 embed % space
101 \ifblank{#3}{\type=\textquotedbl#3\textquotedbl\ }%
102 style=\textquotedbl\LWR@multimedia@printsize\ margin:auto\textquotedbl\ % space
103 src=\textquotedbl#2\textquotedbl\ % space
104 }%
105 \LWR@startpars
106 \end{BlockClass}
107 }
```

Error message if the comment character is used among the arguments of \LWR@multimedia@b.

```
\LWR@multimedia@percenterror
```

```
108 \newcommand*\LWR@multimedia@percenterror{%
109 \PackageError{lwarp-media9}
110 {%
111 Do not use a percent comment between\MessageBreak
112 \protect\includemedia\space arguments%
113 }
114 {%
115 Percent is changed to a regular character\MessageBreak
116 to allow its use inside a URL.%
117 }
```

118 }

`\LWR@multimediab` [*<options>*] [*<poster text>*] [*<filename>*]

Creates multimedia. Examines the file extension to determine the type. If not a supported type, creates an embedded object if it has a URL. If neither, create a link to the unsupported object.

119 `\newcommand*{\LWR@multimediab}[3][[]]{%`

Error if the percent character appears among the arguments. This could happen since the comment character has been temporarily disabled, for use in a URL.

```
120 \if#1\@percentchar\LWR@multimedia@percenterror\fi%
121 \if#2\@percentchar\LWR@multimedia@percenterror\fi%
122 \if#3\@percentchar\LWR@multimedia@percenterror\fi%
```

Paragraph handling:

123 `\LWR@stoppars%`

Record the desired size.

```
124 \setlength{\LWR@multimedia@width}{0pt}%
125 \setlength{\LWR@multimedia@height}{0pt}%
126 \setkeys*{\LWR@multimedia}{#1}%
```

If a known A / v type, create an HTML5 `<video>` or `<audio>`.

```
127 \IfEndWith{#3}{.mp4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
128 \IfEndWith{#3}{.MP4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
129 \IfEndWith{#3}{.mp3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
130 \IfEndWith{#3}{.MP3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
```

If an arbitrary URL, embed it.

```
131 \IfBeginWith{#3}{http}{\LWR@multimedia@embed{#2}{#3}}{%
132 \IfBeginWith{#3}{HTTP}{\LWR@multimedia@embed{#2}{#3}}{%
133 \IfBeginWith{#3}{ftp}{\LWR@multimedia@embed{#2}{#3}}{%
134 \IfBeginWith{#3}{FTP}{\LWR@multimedia@embed{#2}{#3}}{%
```

If unknown, create a link to it.

```
135 \LWR@href{#3}{#2}% unknown format
136 }}}}}}}}%
```

Paragraph handling:

```
137 \LWR@startpars%
138 \endgroup%
139 }
```

Catcodes which may appear in a URL.

```
140 \newrobustcmd*{\LWR@multimedia}{%
141 \begingroup%
142 \LWR@linkmediacatcodes%
143 \LWR@multimediab%
144 }
```

File 549 **lwarp-common-mathjax-letters.sty**

§ 655 Package **common-mathjax-letters**

Pkg Common code used by a number of packages to generate Greek math characters for  
 lwarp-common-mathjax-letters MATHJAX.

**for HTML output:** 1 \ProvidesPackage{lwarp-common-mathjax-letters}[2020/08/10]

\LWR@mathjax@addLetter \* {<2: capitalize name?>} {<3: prefix>} {<4: postfix>} {<5: name>} {<6: unicode>}

Star to italicize the result, used when the unicode character does not exist.

```

2 \begin{warpMathJax}
3
4 \NewDocumentCommand{\LWR@mathjax@addLetter}{s m m m m m}{
5 \IfBooleanTF{#2}%
6 {\edef\LWR@tempone{\LWRtexttitlecase{#5}}}%
7 {\edef\LWR@tempone{#5}}%
8 \xdef\LWR@customizedMathJax{%
9 \LWR@customizedMathJax%
10 \LWRbackslash%
11 \LWRbackslash def\LWRbackslash%
12 #3% prefix
13 \LWR@tempone%name
14 #4% postfix
15 \LWRleftbrace%
16 }%
17 \IfBooleanTF{#1}{%
18 \xdef\LWR@customizedMathJax{%
19 \LWR@customizedMathJax%
20 \LWRbackslash mathit\LWRleftbrace%
21 \LWRbackslash unicode\LWRleftbrace x#6\LWRrightbrace%
22 \LWRrightbrace%
23 }%
24 }{%
25 \xdef\LWR@customizedMathJax{%
26 \LWR@customizedMathJax%
27 \LWRbackslash unicode\LWRleftbrace x#6\LWRrightbrace%
28 }%
29 }%
30 \xdef\LWR@customizedMathJax{%
31 \LWR@customizedMathJax%
32 \LWRrightbrace\LWRbackslash)\par%
33 }%
34 }

```

\* {<2: prefix>} {<3: postfix>}

\LWR@mathjax@addgreek@l@up Star to capitalize the macro names.

Adds `\CustomizeMathjax` expressions to define a set of macros for Greek letters, lowercase upright.

```

35 \NewDocumentCommand{\LWR@mathjax@addgreek@l@up}{s m m}{
36 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{03B1}
37 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{03B2}
38 \LWR@mathjax@addLetter{#1}{#2}{#3}{varbeta}{03D0}
39 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{03B3}
40 \LWR@mathjax@addLetter{#1}{#2}{#3}{digamma}{03DD}
41 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{03B4}
42 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{03F5}
43 \LWR@mathjax@addLetter{#1}{#2}{#3}{varepsilon}{03B5}
44 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{03B6}
45 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{03B7}
46 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{03B8}
47 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{03D1}
48 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{03B9}
49 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{03BA}
50 \LWR@mathjax@addLetter{#1}{#2}{#3}{varkappa}{03F0}
51 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{03BB}
52 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{03BC}
53 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{03BD}
54 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{03BE}
55 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{03BF}
56 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{03C0}
57 \LWR@mathjax@addLetter{#1}{#2}{#3}{varpi}{03D6}
58 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{03C1}
59 \LWR@mathjax@addLetter{#1}{#2}{#3}{varrho}{03F1}
60 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{03C3}
61 \LWR@mathjax@addLetter{#1}{#2}{#3}{varsigma}{03C2}
62 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{03C4}
63 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{03C5}
64 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{03D5}
65 \LWR@mathjax@addLetter{#1}{#2}{#3}{varphi}{03C6}
66 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{03C7}
67 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{03C8}
68 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{03C9}
69 }

```

\*  $\langle 2: prefix \rangle \langle 3: postfix \rangle$

`\LWR@mathjax@addgreek@u@up`

Star to capitalize the macro names.

Adds `\CustomizeMathjax` expressions to define a set of macros for Greek letters, uppercase upright.

```

70 \NewDocumentCommand{\LWR@mathjax@addgreek@u@up}{s m m}{
71 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{0391}
72 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{0392}
73 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{0393}
74 \LWR@mathjax@addLetter{#1}{#2}{#3}{digamma}{03DC}
75 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{0394}
76 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{0395}
77 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{0396}
78 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{0397}
79 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{0398}
80 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{03F4}

```

```

81 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{0399}
82 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{039A}
83 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{039B}
84 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{039C}
85 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{039D}
86 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{039E}
87 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{039F}
88 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{03A0}
89 \LWR@mathjax@addLetter{#1}{#2}{#3}{varpi}{03D6}
90 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{03A1}
91 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{03A3}
92 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{03A4}
93 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{03A5}
94 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{03A6}
95 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{03A7}
96 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{03A8}
97 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{03A9}
98 }

```

\*  $\langle 2: prefix \rangle \langle 3: postfix \rangle$

\LWR@mathjax@addgreek@l@it

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, lowercase italic.

```

99 \NewDocumentCommand{\LWR@mathjax@addgreek@l@it}{s m m}{
100 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{1D6FC}
101 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{1D6FD}
102 \LWR@mathjax@addLetter{#1}{#2}{#3}{varbeta}{03D0}
103 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{1D6FE}
104 \LWR@mathjax@addLetter*{#1}{#2}{#3}{digamma}{03DD}
105 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{1D6FF}
106 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{1D716}
107 \LWR@mathjax@addLetter{#1}{#2}{#3}{varepsilon}{1D700}
108 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{1D701}
109 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{1D702}
110 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{1D703}
111 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{1D717}
112 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{1D704}
113 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{1D705}
114 \LWR@mathjax@addLetter{#1}{#2}{#3}{varkappa}{1D718}
115 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{1D706}
116 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{1D707}
117 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{1D708}
118 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{1D709}
119 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{1D70A}
120 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{1D70B}
121 \LWR@mathjax@addLetter{#1}{#2}{#3}{varpi}{1D71B}
122 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{1D70C}
123 \LWR@mathjax@addLetter{#1}{#2}{#3}{varrho}{1D71A}
124 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{1D70E}
125 \LWR@mathjax@addLetter{#1}{#2}{#3}{varsigma}{1D70D}
126 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{1D70F}
127 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{1D710}
128 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{1D719}

```

```

129 \LWR@mathjax@addletter{#1}{#2}{#3}{varphi}{1D711}
130 \LWR@mathjax@addletter{#1}{#2}{#3}{chi}{1D712}
131 \LWR@mathjax@addletter{#1}{#2}{#3}{psi}{1D713}
132 \LWR@mathjax@addletter{#1}{#2}{#3}{omega}{1D714}
133 }

```

\*  $\langle 2: prefix \rangle \langle 3: postfix \rangle$

\LWR@mathjax@addgreek@u@it

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, uppercase italic.

```

134 \NewDocumentCommand{\LWR@mathjax@addgreek@u@it}{s m m}{
135 \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{1D6E2}
136 \LWR@mathjax@addletter{#1}{#2}{#3}{beta}{1D6E3}
137 \LWR@mathjax@addletter{#1}{#2}{#3}{gamma}{1D6E4}
138 \LWR@mathjax@addletter*{#1}{#2}{#3}{digamma}{03DC}
139 \LWR@mathjax@addletter{#1}{#2}{#3}{delta}{1D6E5}
140 \LWR@mathjax@addletter{#1}{#2}{#3}{epsilon}{1D6E6}
141 \LWR@mathjax@addletter{#1}{#2}{#3}{zeta}{1D6E7}
142 \LWR@mathjax@addletter{#1}{#2}{#3}{eta}{1D6E8}
143 \LWR@mathjax@addletter{#1}{#2}{#3}{theta}{1D6E9}
144 \LWR@mathjax@addletter{#1}{#2}{#3}{vartheta}{1D6F3}
145 \LWR@mathjax@addletter{#1}{#2}{#3}{iota}{1D6EA}
146 \LWR@mathjax@addletter{#1}{#2}{#3}{kappa}{1D6EB}
147 \LWR@mathjax@addletter{#1}{#2}{#3}{lambda}{1D6EC}
148 \LWR@mathjax@addletter{#1}{#2}{#3}{mu}{1D6ED}
149 \LWR@mathjax@addletter{#1}{#2}{#3}{nu}{1D6EE}
150 \LWR@mathjax@addletter{#1}{#2}{#3}{xi}{1D6EF}
151 \LWR@mathjax@addletter{#1}{#2}{#3}{omicron}{1D6F0}
152 \LWR@mathjax@addletter{#1}{#2}{#3}{pi}{1D6F1}
153 \LWR@mathjax@addletter{#1}{#2}{#3}{rho}{1D6F2}
154 \LWR@mathjax@addletter{#1}{#2}{#3}{sigma}{1D6F4}
155 \LWR@mathjax@addletter{#1}{#2}{#3}{tau}{1D6F5}
156 \LWR@mathjax@addletter{#1}{#2}{#3}{upsilon}{1D6F6}
157 \LWR@mathjax@addletter{#1}{#2}{#3}{phi}{1D6F7}
158 \LWR@mathjax@addletter{#1}{#2}{#3}{chi}{1D6F8}
159 \LWR@mathjax@addletter{#1}{#2}{#3}{psi}{1D6F9}
160 \LWR@mathjax@addletter{#1}{#2}{#3}{omega}{1D6FA}
161 }

```

\*  $\langle 2: prefix \rangle \langle 3: postfix \rangle$

\LWR@mathjax@addgreek@l@bfit

Star to capitalize the macro names.

Adds \CustomizeMathjax expressions to define a set of macros for Greek letters, lowercase boldface italic.

```

162 \NewDocumentCommand{\LWR@mathjax@addgreek@l@bfit}{s m m}{
163 \LWR@mathjax@addletter{#1}{#2}{#3}{alpha}{1D736}
164 \LWR@mathjax@addletter{#1}{#2}{#3}{beta}{1D737}
165 \LWR@mathjax@addletter{#1}{#2}{#3}{varbeta}{03D0}
166 \LWR@mathjax@addletter{#1}{#2}{#3}{gamma}{1D738}
167 \LWR@mathjax@addletter*{#1}{#2}{#3}{digamma}{03DD}
168 \LWR@mathjax@addletter{#1}{#2}{#3}{delta}{1D739}
169 \LWR@mathjax@addletter{#1}{#2}{#3}{epsilon}{1D750}

```

```

170 \LWR@mathjax@addLetter{#1}{#2}{#3}{varepsilon}{1D73A}
171 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{1D73B}
172 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{1D73C}
173 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{1D73D}
174 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{1D751}
175 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{1D73E}
176 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{1D73F}
177 \LWR@mathjax@addLetter{#1}{#2}{#3}{varkappa}{1D752}
178 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{1D740}
179 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{1D741}
180 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{1D742}
181 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{1D743}
182 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{1D744}
183 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{1D745}
184 \LWR@mathjax@addLetter{#1}{#2}{#3}{varpi}{1D755}
185 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{1D746}
186 \LWR@mathjax@addLetter{#1}{#2}{#3}{varrho}{1D754}
187 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{1D748}
188 \LWR@mathjax@addLetter{#1}{#2}{#3}{varsigma}{1D747}
189 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{1D749}
190 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{1D74A}
191 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{1D753}
192 \LWR@mathjax@addLetter{#1}{#2}{#3}{varphi}{1D74B}
193 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{1D74C}
194 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{1D74D}
195 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{1D74E}
196 }

```

\*  $\langle 2: prefix \rangle \langle 3: postfix \rangle$

`\LWR@mathjax@addgreek@u@bfit`

Star to capitalize the macro names.

Adds `\CustomizeMathjax` expressions to define a set of macros for Greek letters, uppercase boldface italic.

```

197 \NewDocumentCommand{\LWR@mathjax@addgreek@u@bfit}{s m m}{
198 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{1D71C}
199 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{1D71D}
200 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{1D71E}
201 \LWR@mathjax@addLetter*{#1}{#2}{#3}{digamma}{03DC}
202 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{1D71F}
203 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{1D720}
204 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{1D721}
205 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{1D722}
206 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{1D723}
207 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{1D72D}
208 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{1D724}
209 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{1D725}
210 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{1D726}
211 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{1D727}
212 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{1D728}
213 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{1D729}
214 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{1D72A}
215 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{1D72B}
216 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{1D72C}
217 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{1D72E}

```

```

218 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{1D72F}
219 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{1D730}
220 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{1D731}
221 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{1D732}
222 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{1D733}
223 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{1D734}
224 }

```

`\LWR@mathjax@addgreek@u@bfup` is not needed.

*\* {<2: prefix>} {<3: postfix>}*

`\LWR@mathjax@addgreek@u@bfup`

Star to capitalize the macro names.

Adds `\CustomizeMathjax` expressions to define a set of macros for Greek letters, uppercase boldface upright.

```

225 \NewDocumentCommand{\LWR@mathjax@addgreek@u@bfup}{s m m}{
226 \LWR@mathjax@addLetter{#1}{#2}{#3}{alpha}{1D6A8}
227 \LWR@mathjax@addLetter{#1}{#2}{#3}{beta}{1D6A9}
228 \LWR@mathjax@addLetter{#1}{#2}{#3}{gamma}{1D6AA}
229 \LWR@mathjax@addLetter*{#1}{#2}{#3}{digamma}{03DC}
230 \LWR@mathjax@addLetter{#1}{#2}{#3}{delta}{1D6AB}
231 \LWR@mathjax@addLetter{#1}{#2}{#3}{epsilon}{1D6AC}
232 \LWR@mathjax@addLetter{#1}{#2}{#3}{zeta}{1D6AD}
233 \LWR@mathjax@addLetter{#1}{#2}{#3}{eta}{1D6AE}
234 \LWR@mathjax@addLetter{#1}{#2}{#3}{theta}{1D6AF}
235 \LWR@mathjax@addLetter{#1}{#2}{#3}{vartheta}{1D6B9}
236 \LWR@mathjax@addLetter{#1}{#2}{#3}{iota}{1D6B0}
237 \LWR@mathjax@addLetter{#1}{#2}{#3}{kappa}{1D6B1}
238 \LWR@mathjax@addLetter{#1}{#2}{#3}{lambda}{1D6B2}
239 \LWR@mathjax@addLetter{#1}{#2}{#3}{mu}{1D6B3}
240 \LWR@mathjax@addLetter{#1}{#2}{#3}{nu}{1D6B4}
241 \LWR@mathjax@addLetter{#1}{#2}{#3}{xi}{1D6B5}
242 \LWR@mathjax@addLetter{#1}{#2}{#3}{omicron}{1D6B6}
243 \LWR@mathjax@addLetter{#1}{#2}{#3}{pi}{1D6B7}
244 \LWR@mathjax@addLetter{#1}{#2}{#3}{rho}{1D6B8}
245 \LWR@mathjax@addLetter{#1}{#2}{#3}{sigma}{1D6BA}
246 \LWR@mathjax@addLetter{#1}{#2}{#3}{tau}{1D6BB}
247 \LWR@mathjax@addLetter{#1}{#2}{#3}{upsilon}{1D6BC}
248 \LWR@mathjax@addLetter{#1}{#2}{#3}{phi}{1D6BD}
249 \LWR@mathjax@addLetter{#1}{#2}{#3}{chi}{1D6BE}
250 \LWR@mathjax@addLetter{#1}{#2}{#3}{psi}{1D6BF}
251 \LWR@mathjax@addLetter{#1}{#2}{#3}{omega}{1D6C0}
252 }

```

*{<prefix>}*

`\LWR@mathjax@addlatin@u@bfif`

Adds `\CustomizeMathjax` expressions to define a set of macros for bold-face italic Latin letters, uppercase and lowercase.

```

253 \NewDocumentCommand{\LWR@mathjax@addlatin@u@bfif}{m}{
254 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{A}{1D468}
255 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{B}{1D469}
256 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{C}{1D46A}
257 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{D}{1D46B}
258 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{E}{1D46C}

```

```

259 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{F}{1D46D}
260 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{G}{1D46E}
261 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{H}{1D46F}
262 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{I}{1D470}
263 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{J}{1D471}
264 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{K}{1D472}
265 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{L}{1D473}
266 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{M}{1D474}
267 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{N}{1D475}
268 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{O}{1D476}
269 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{P}{1D477}
270 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{Q}{1D478}
271 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{R}{1D479}
272 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{S}{1D47A}
273 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{T}{1D47B}
274 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{U}{1D47C}
275 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{V}{1D47D}
276 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{W}{1D47E}
277 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{X}{1D47F}
278 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{Y}{1D480}
279 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{Z}{1D481}
280 }

```

$\langle prefix \rangle$

`\LWR@mathjax@addLatin@l@bfit`

Adds `\CustomizeMathjax` expressions to define a set of macros for bold-face italic Latin letters, uppercase and lowercase.

```

281 \NewDocumentCommand{\LWR@mathjax@addLatin@l@bfit}{m}{
282 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{a}{1D482}
283 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{b}{1D483}
284 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{c}{1D484}
285 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{d}{1D485}
286 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{e}{1D486}
287 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{f}{1D487}
288 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{g}{1D488}
289 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{h}{1D489}
290 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{i}{1D48A}
291 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{j}{1D48B}
292 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{k}{1D48C}
293 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{l}{1D48D}
294 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{m}{1D48E}
295 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{n}{1D48F}
296 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{o}{1D490}
297 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{p}{1D491}
298 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{q}{1D492}
299 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{r}{1D493}
300 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{s}{1D494}
301 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{t}{1D495}
302 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{u}{1D496}
303 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{v}{1D497}
304 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{w}{1D498}
305 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{x}{1D499}
306 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{y}{1D49A}
307 \LWR@mathjax@addLetter{\BooleanFalse}{#1}{z}{1D49B}
308 }

```

```
309 \end{warpMathJax}
```

---

File 550 **lwarp-common-mathjax-newpctxmath.sty**

§ 656 Package **common-mathjax-newpctxmath**

(Emulates or patches code by MICHAEL SHARPE.)

Pkg Common code used by newpctxmath, newtxmath, and newtxsf for MATHJAX.

lwarp-common-mathjax-newpctxmath

**for HTML output:** 1 \ProvidesPackage{lwarp-common-mathjax-newpctxmath}[2020/09/20]

For MATHJAX:

```
2 \LWR@origRequirePackage{lwarp-common-mathjax-nonunicode}
3 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
4
5 \begin{warpMathJax}
6 \CustomizeMathJax{\newcommand{\fAlt}{f}}
7 \CustomizeMathJax{\newcommand{\rhoAlt}{\rho}}
8
9 \CustomizeMathJax{\newcommand{\imathscr}{\mathord{\mathscr{i}}}}
10 \CustomizeMathJax{\newcommand{\jmathscr}{\mathord{\mathscr{j}}}}
```

lwarp\_mathjax.txt adds \left/\right support for delimiters.

```
11 \CustomizeMathJax{\let\llbracket\lBrack}
12 \CustomizeMathJax{\let\rrbracket\rBrack}
13
14 \CustomizeMathJax{\let\smllbrace\{ }
15 \CustomizeMathJax{\let\smrbrace\} }
16 \CustomizeMathJax{\newcommand{\Perp}{\mathrel{\unicode{x02AEB}}}}
17 \CustomizeMathJax{\newcommand{\nPerp}{\mathrel{\not{\! \unicode{x02AEB}}}}}
18 \CustomizeMathJax{\newcommand{\Zbar}{\mathord{\unicode{x01B5}}}}
19 \CustomizeMathJax{\newcommand{\Angstrom}{\mathord{\unicode{x212B}}}}
20 \CustomizeMathJax{\newcommand{\Euler}{\mathord{\unicode{x2107}}}}
21 \CustomizeMathJax{\newcommand{\transp}{\mathord{\unicode{xFF34}}}}
22 \CustomizeMathJax{\newcommand{\hermtransp}{\mathord{\unicode{xFF28}}}}
23 \CustomizeMathJax{\let\htransp=\hermtransp}
24 \CustomizeMathJax{\newcommand{\circledplus}{\mathbin{\unicode{x2295}}}}
25 \CustomizeMathJax{\newcommand{\circledminus}{\mathbin{\unicode{x2296}}}}
26 \CustomizeMathJax{\newcommand{\circledtimes}{\mathbin{\unicode{x2297}}}}
27 \CustomizeMathJax{\newcommand{\circledslash}{\mathbin{\unicode{x2298}}}}
28 %
29 \CustomizeMathJax{\newcommand{\circleddot}{\mathbin{\unicode{x2299}}}}
30 \CustomizeMathJax{\let\overgroup\overparen}
31 \CustomizeMathJax{\let\overgroupra\overrightarrow}
32 \CustomizeMathJax{\let\undergroup\underparen}
33 \CustomizeMathJax{\let\undergroupla\underleftarrow}
34 \CustomizeMathJax{\newcommand{\widering}[1]{\stackrel{\unicode{x2218}}{\overgroup{#1}}}}
35 \CustomizeMathJax{\let\widearc\overparen}
```

```

36 \CustomizeMathJax{\let\wideOarc\overrightarrow}
37 \CustomizeMathJax{\newcommand{\LWRvvstar}[2]{\overrightarrow{#1}_{#2}}}
38 \CustomizeMathJax{\newcommand{\vv}{\ifstar\LWRvvstar\overrightarrow}}
39 %
40 \CustomizeMathJax{\let\smallintsl\smallint}
41 \CustomizeMathJax{\newcommand{\smalliintsl}{\mathop{\unicode{x222C}}\limits}}
42 \CustomizeMathJax{\newcommand{\smalliiintsl}{\mathop{\unicode{x222D}}\limits}}
43 \CustomizeMathJax{\newcommand{\smalliiiintsl}{\mathop{\unicode{x2A0C}}\limits}}
44 \CustomizeMathJax{\newcommand{\smalllointsl}{\mathop{\unicode{x222E}}\limits}}
45 \CustomizeMathJax{\newcommand{\smalllooiintsl}{\mathop{\unicode{x222F}}\limits}}
46 \CustomizeMathJax{\newcommand{\smalllooiintsl}{\mathop{\unicode{x2230}}\limits}}
47 \CustomizeMathJax{\newcommand{\smallvarointclockwisel}{\mathop{\unicode{x2232}}\limits}}
48 \CustomizeMathJax{\newcommand{\smalllointctrlockwisel}{\mathop{\unicode{x2233}}\limits}}
49 \CustomizeMathJax{\newcommand{\smallsumintsl}{\mathop{\unicode{x2A0B}}\limits}}
50 \CustomizeMathJax{\newcommand{\smallfintsl}{\mathop{\unicode{x2A0F}}\limits}}
51 \CustomizeMathJax{\newcommand{\smallsqintsl}{\mathop{\unicode{x2A16}}\limits}}
52 %
53 \CustomizeMathJax{\let\smallintup\smallint}
54 \CustomizeMathJax{\newcommand{\smalliintup}{\mathop{\unicode{x222C}}\limits}}
55 \CustomizeMathJax{\newcommand{\smalliiintup}{\mathop{\unicode{x222D}}\limits}}
56 \CustomizeMathJax{\newcommand{\smalliiiintup}{\mathop{\unicode{x2A0C}}\limits}}
57 \CustomizeMathJax{\newcommand{\smalllointup}{\mathop{\unicode{x222E}}\limits}}
58 \CustomizeMathJax{\newcommand{\smalllooiintup}{\mathop{\unicode{x222F}}\limits}}
59 \CustomizeMathJax{\newcommand{\smalllooiintup}{\mathop{\unicode{x2230}}\limits}}
60 \CustomizeMathJax{\newcommand{\smallvarointclockwiseup}{\mathop{\unicode{x2232}}\limits}}
61 \CustomizeMathJax{\newcommand{\smalllointctrlockwiseup}{\mathop{\unicode{x2233}}\limits}}
62 \CustomizeMathJax{\newcommand{\smallsumintup}{\mathop{\unicode{x2A0B}}\limits}}
63 \CustomizeMathJax{\newcommand{\smallfintup}{\mathop{\unicode{x2A0F}}\limits}}
64 \CustomizeMathJax{\newcommand{\smallsqintup}{\mathop{\unicode{x2A16}}\limits}}
65 %
66 \CustomizeMathJax{\newcommand{\iint}{\mathop{\unicode{x222C}}\limits}}
67 \CustomizeMathJax{\newcommand{\iiint}{\mathop{\unicode{x222D}}\limits}}
68 \CustomizeMathJax{\newcommand{\iiiint}{\mathop{\unicode{x2A0C}}\limits}}
69 \CustomizeMathJax{\newcommand{\oiint}{\mathop{\unicode{x222F}}\limits}}
70 \CustomizeMathJax{\newcommand{\ooiint}{\mathop{\unicode{x2230}}\limits}}
71 \CustomizeMathJax{\newcommand{\varointclockwise}{\mathop{\unicode{x2232}}\limits}}
72 \CustomizeMathJax{\newcommand{\ointctrlockwise}{\mathop{\unicode{x2233}}\limits}}
73 \CustomizeMathJax{\newcommand{\sumint}{\mathop{\unicode{x2A0B}}\limits}}
74 \CustomizeMathJax{\newcommand{\fint}{\mathop{\unicode{x2A0F}}\limits}}
75 \CustomizeMathJax{\newcommand{\sqint}{\mathop{\unicode{x2A16}}\limits}}
76 %
77 \CustomizeMathJax{\let\intsl\int}
78 \CustomizeMathJax{\newcommand{\iintsl}{\mathop{\unicode{x222C}}\limits}}
79 \CustomizeMathJax{\newcommand{\iiintsl}{\mathop{\unicode{x222D}}\limits}}
80 \CustomizeMathJax{\newcommand{\iiiintsl}{\mathop{\unicode{x2A0C}}\limits}}
81 \CustomizeMathJax{\let\oiintsl\oiint}
82 \CustomizeMathJax{\newcommand{\oiintsl}{\mathop{\unicode{x222F}}\limits}}
83 \CustomizeMathJax{\newcommand{\ooiintsl}{\mathop{\unicode{x2230}}\limits}}
84 \CustomizeMathJax{\newcommand{\varointclockwisel}{\mathop{\unicode{x2232}}\limits}}
85 \CustomizeMathJax{\newcommand{\ointctrlockwisel}{\mathop{\unicode{x2233}}\limits}}
86 \CustomizeMathJax{\newcommand{\sumintsl}{\mathop{\unicode{x2A0B}}\limits}}
87 \CustomizeMathJax{\newcommand{\fintsl}{\mathop{\unicode{x2A0F}}\limits}}
88 \CustomizeMathJax{\newcommand{\sqintsl}{\mathop{\unicode{x2A16}}\limits}}
89 %
90 \CustomizeMathJax{\let\intup\int}

```

```

91 \CustomizeMathJax{\newcommand{\iintup}{\mathop{\unicode{x222C}}\limits}}
92 \CustomizeMathJax{\newcommand{\iiintup}{\mathop{\unicode{x222D}}\limits}}
93 \CustomizeMathJax{\newcommand{\iiintup}{\mathop{\unicode{x2A0C}}\limits}}
94 \CustomizeMathJax{\let\ointup\oint}
95 \CustomizeMathJax{\newcommand{\oiintup}{\mathop{\unicode{x222F}}\limits}}
96 \CustomizeMathJax{\newcommand{\oiintup}{\mathop{\unicode{x2230}}\limits}}
97 \CustomizeMathJax{\newcommand{\varointclockwiseup}{\mathop{\unicode{x2232}}\limits}}
98 \CustomizeMathJax{\newcommand{\ointctrclockwiseup}{\mathop{\unicode{x2233}}\limits}}
99 \CustomizeMathJax{\newcommand{\sumintup}{\mathop{\unicode{x2A0B}}\limits}}
100 \CustomizeMathJax{\newcommand{\fintup}{\mathop{\unicode{x2A0F}}\limits}}
101 \CustomizeMathJax{\newcommand{\sqintup}{\mathop{\unicode{x2A16}}\limits}}
102 %
103 \CustomizeMathJax{\newcommand{\bigcupdot}{\mathop{\unicode{x2A03}}}}
104 \CustomizeMathJax{\newcommand{\bigcupplus}{\mathop{\unicode{x2A04}}}}
105 \CustomizeMathJax{\newcommand{\bigsqcap}{\mathop{\unicode{x2A05}}}}
106 %

107 %
108 \CustomizeMathJax{\newcommand{\bigtimes}{\mathop{\unicode{x2A09}}}}
109 \CustomizeMathJax{\let\varprod\bigtimes}
110 %

111 \CustomizeMathJax{\newcommand{\mappedfrom}{\mathrel{\unicode{x021A4}}}}
112 \CustomizeMathJax{\let\mappedfromchar\mappedfrom}
113 \CustomizeMathJax{\newcommand{\mapsfrom}{\mathrel{\unicode{x021A4}}}}
114 \CustomizeMathJax{\newcommand{\longmappedfrom}{\mathrel{\unicode{x027FB}}}}
115 %
116 \CustomizeMathJax{\newcommand{\Mapsto}{\mathrel{\unicode{x02907}}}}
117 \CustomizeMathJax{\let\Mapstochar\Mapsto}
118 \CustomizeMathJax{\newcommand{\Longmapsto}{\mathrel{\unicode{x027FE}}}}
119 \CustomizeMathJax{\newcommand{\Mappedfrom}{\mathrel{\unicode{x02906}}}}
120 \CustomizeMathJax{\let\Mappedfromchar\Mappedfrom}
121 \CustomizeMathJax{\newcommand{\Mapsfrom}{\mathrel{\unicode{x02906}}}}
122 \CustomizeMathJax{\newcommand{\Longmappedfrom}{\mathrel{\unicode{x27FD}}}}
123 %

124 \CustomizeMathJax{\newcommand{\medcirc}{\mathbin{\unicode{x025CB}}}}
125 \CustomizeMathJax{\newcommand{\medbullet}{\mathbin{\unicode{x025CF}}}}
126 \CustomizeMathJax{\newcommand{\varparallel}{\mathrel{\unicode{x02AFD}}}}
127 \CustomizeMathJax{\newcommand{\varparallelinv}{\mathrel{\unicode{x244A}}}}
128 \CustomizeMathJax{\newcommand{\nvarparallel}{\mathrel{\LWROverlaysymbols{-}\unicode{x02AFD}}}}
129 \CustomizeMathJax{\newcommand{\nvarparallelinv}{\mathrel{\LWROverlaysymbols{-}\unicode{x244A}}}}
130 %

131 \CustomizeMathJax{\newcommand{\coloneq}{\mathrel{\unicode{x02254}}}}
132 \CustomizeMathJax{\newcommand{\eqcolon}{\mathrel{\unicode{x02255}}}}
133 %
134 \CustomizeMathJax{\newcommand{\VDash}{\mathrel{\unicode{x22AB}}}}

135 %
136 \CustomizeMathJax{\newcommand{\preceqq}{\mathrel{\unicode{x02AB3}}}}
137 \CustomizeMathJax{\newcommand{\succeqq}{\mathrel{\unicode{x02AB4}}}}

```

```

138 %
139
140 \CustomizeMathJax{\newcommand{\nprecsm}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0227E}}}}}
141 \CustomizeMathJax{\newcommand{\nsuccsm}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0227F}}}}}
142 \CustomizeMathJax{\newcommand{\nlessim}{\mathrel{\unicode{x02274}}}}
143 \CustomizeMathJax{\newcommand{\ngtrsim}{\mathrel{\unicode{x02275}}}}
144 %

145 \CustomizeMathJax{\newcommand{\nsubset}{\mathrel{\unicode{x02284}}}}
146 \CustomizeMathJax{\newcommand{\nsupset}{\mathrel{\unicode{x02285}}}}
147 \CustomizeMathJax{\newcommand{\notni}{\mathrel{\unicode{x220C}}}}
148 \CustomizeMathJax{\let\notowns\notni}
149 %

150 \CustomizeMathJax{\newcommand{\nlessapprox}{\mathrel{\LWOverlaysymbols{/}{\unicode{x02A85}}}}}
151 \CustomizeMathJax{\newcommand{\ngtrapprox}{\mathrel{\LWOverlaysymbols{/}{\unicode{x02A86}}}}}
152 %

153 \CustomizeMathJax{\newcommand{\npreccurlyeq}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0227C}}}}}
154 \CustomizeMathJax{\newcommand{\nsucccurlyeq}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0227D}}}}}
155 \CustomizeMathJax{\newcommand{\ngtrless}{\mathrel{\unicode{x02279}}}}
156 \CustomizeMathJax{\newcommand{\nlessgtr}{\mathrel{\unicode{x2278}}}}
157 \CustomizeMathJax{\newcommand{\nbumpeq}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0224F}}}}}
158 \CustomizeMathJax{\newcommand{\nBumpeq}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0224E}}}}}
159 %

160 \CustomizeMathJax{\newcommand{\nbacksim}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0223D}}}}}
161 \CustomizeMathJax{\newcommand{\nbacksimeq}{\mathrel{\LWOverlaysymbols{/}{\unicode{x022CD}}}}}
162 \CustomizeMathJax{\newcommand{\nasymp}{\mathrel{\unicode{x226D}}}}
163 \CustomizeMathJax{\newcommand{\nequiv}{\mathrel{\unicode{x2262}}}}
164 \CustomizeMathJax{\newcommand{\napprox}{\mathrel{\unicode{x2249}}}}
165 %

166 \CustomizeMathJax{\newcommand{\nll}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0226A}}}}}
167 \CustomizeMathJax{\newcommand{\ngg}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0226B}}}}}
168 \CustomizeMathJax{\newcommand{\nthickapprox}{%
169 \mathrel{\LWOverlaysymbols{/}{\mathbf{\unicode{x02248}}}}}
170 }}
171 \CustomizeMathJax{\newcommand{\napproxeq}{\mathrel{\LWOverlaysymbols{/}{\unicode{x0224A}}}}}
172 \CustomizeMathJax{\newcommand{\nprecapprox}{\mathrel{\LWOverlaysymbols{/}{\unicode{x02AB7}}}}}
173 \CustomizeMathJax{\newcommand{\nsuccapprox}{\mathrel{\LWOverlaysymbols{/}{\unicode{x02AB8}}}}}
174 \CustomizeMathJax{\newcommand{\npreceqq}{\mathrel{\LWOverlaysymbols{/}{\unicode{x02AB3}}}}}
175 \CustomizeMathJax{\newcommand{\nsucceqq}{\mathrel{\LWOverlaysymbols{/}{\unicode{x02AB4}}}}}
176 \CustomizeMathJax{\newcommand{\nsimeq}{\mathrel{\unicode{x02244}}}}
177 %

178 \CustomizeMathJax{\newcommand{\nSubset}{\mathrel{\LWOverlaysymbols{/}{\unicode{x022D0}}}}}
179 \CustomizeMathJax{\newcommand{\nSupset}{\mathrel{\LWOverlaysymbols{/}{\unicode{x022D1}}}}}
180 \CustomizeMathJax{\newcommand{\nsqsubseteq}{\mathrel{\unicode{x022E2}}}}
181 \CustomizeMathJax{\newcommand{\nsqsupseteq}{\mathrel{\unicode{x022E3}}}}
182 %

183 \CustomizeMathJax{\newcommand{\coloneqq}{\mathrel{\unicode{x02254}}}}
184 \CustomizeMathJax{\newcommand{\eqqcolon}{\mathrel{\unicode{x02255}}}}
185 \CustomizeMathJax{\newcommand{\Coloneqq}{\mathrel{\unicode{x02A74}}}}
186 \CustomizeMathJax{\newcommand{\Coloneq}{\mathrel{\unicode{x2237}-}}}
187 \CustomizeMathJax{\newcommand{\Eqcolon}{\mathrel{-\unicode{x2237}}}}
188 %

189 \CustomizeMathJax{\newcommand{\lvec}[1]{\mathord{\overset{\unicode{x02190}}{\#1}}}}
190 \CustomizeMathJax{\newcommand{\lrvec}[1]{\mathord{\overset{\unicode{x2194}}{\#1}}}}
191 \CustomizeMathJax{\newcommand{\harpoonacc}[1]{\mathord{\overset{\unicode{x021C0}}{\#1}}}}

```

```

192 \CustomizeMathJax{\newcommand{\lharpoonacc}[1]{\mathord{\overset{\unicode{x021BC}}{#1}}}}
193 \CustomizeMathJax{\newcommand{\lrharpoonacc}[1]{\mathord{\overset{\unicode{x0294E}}{#1}}}}
194 \CustomizeMathJax{\newcommand{\barbar}[1]{\mathord{\overset{=}{#1}}}}
195 \CustomizeMathJax{\newcommand{\bartilde}[1]{\mathord{\overset{\simeq}{#1}}}}
196 \CustomizeMathJax{\newcommand{\barhat}[1]{\mathord{\hat{\bar{#1}}}}}
197 \CustomizeMathJax{\newcommand{\tildebar}[1]{\mathord{\overset{\eqsim}{#1}}}}
198 \CustomizeMathJax{\newcommand{\tildetilde}[1]{\mathord{\overset{\approx}{#1}}}}
199 \CustomizeMathJax{\newcommand{\tildehat}[1]{\mathord{\hat{\tilde{#1}}}}}
200 \CustomizeMathJax{\newcommand{\hatbar}[1]{\mathord{\bar{\hat{#1}}}}}
201 \CustomizeMathJax{\newcommand{\hattilde}[1]{\mathord{\tilde{\hat{#1}}}}}
202 \CustomizeMathJax{\newcommand{\hathat}[1]{\mathord{\hat{\hat{#1}}}}}
203
204 \CustomizeMathJax{\newcommand{\cdotB}{\mathord{\boldsymbol{\cdot}}}}
205 \CustomizeMathJax{\newcommand{\cdotBB}{\mathord{\unicode{x2022}}}}
206 \CustomizeMathJax{\newcommand{\circS}{\boldsymbol{\circ}}}
207 \CustomizeMathJax{\newcommand{\bulletSSS}{\bullet}}
208 \CustomizeMathJax{\newcommand{\bulletSS}{\mathord{\unicode{x025CF}}}}
209 \CustomizeMathJax{\newcommand{\bulletS}{\mathord{\unicode{x02B24}}}}
210 \CustomizeMathJax{\newcommand{\primeS}{\prime}}
211
212 \CustomizeMathJax{\newcommand{\invamp}{\mathbin{\unicode{x0214B}}}}

```

lwarp\_mathjax.txt adds \left/\right support for delimiters.

```

213 \CustomizeMathJax{\newcommand{\Lbag}{\mathopen{\Large\unicode{x027C5}}}}
214 \CustomizeMathJax{\newcommand{\Rbag}{\mathclose{\Large\unicode{x027C6}}}}
215 \CustomizeMathJax{\newcommand{\circledless}{\mathrel{\unicode{x029C0}}}}
216 \CustomizeMathJax{\newcommand{\circledgtr}{\mathrel{\unicode{x029C1}}}}
217 \CustomizeMathJax{\newcommand{\circledbslash}{\mathbin{\unicode{x029B8}}}}

218 \CustomizeMathJax{\newcommand{\lJoin}{\mathrel{\unicode{x22C9}}}}
219 \CustomizeMathJax{\newcommand{\rJoin}{\mathrel{\unicode{x22CA}}}}
220 \CustomizeMathJax{\newcommand{\lrJoin}{\mathrel{\unicode{x2A1D}}}}
221
222 \CustomizeMathJax{\newcommand{\lRtimes}{\mathrel{\unicode{x2A1D}}}}
223 \CustomizeMathJax{\newcommand{\Diamondblack}{\mathord{\unicode{x025C6}}}}
224 \CustomizeMathJax{\newcommand{\nplus}{\mathrel{\LWROverlaysymbols{+}{\unicode{x02229}}}}}
225 \CustomizeMathJax{\newcommand{\nsqsubset}{\mathrel{\LWROverlaysymbols{/}{\unicode{x0228F}}}}}
226 \CustomizeMathJax{\newcommand{\nsqsupset}{\mathrel{\LWROverlaysymbols{/}{\unicode{x02290}}}}}
227 \CustomizeMathJax{\newcommand{\dasharrow}{\mathrel{\unicode{x021E2}}}}
228 \CustomizeMathJax{\newcommand{\leftsquigarrow}{\mathrel{\unicode{x021DC}}}}
229 \CustomizeMathJax{\newcommand{\twoheadrightarrow}{\mathrel{\unicode{x02900}}}}
230 \CustomizeMathJax{\newcommand{\twoheadleftarrow}{\mathrel{\unicode{x02B34}}}}
231 \CustomizeMathJax{\newcommand{\boxast}{\mathbin{\unicode{x029C6}}}}
232 \CustomizeMathJax{\newcommand{\boxbslash}{\mathbin{\unicode{x29C5}}}}
233 \CustomizeMathJax{\newcommand{\boxbar}{\mathbin{\unicode{x025EB}}}}
234 \CustomizeMathJax{\newcommand{\boxslash}{\mathbin{\unicode{x029C4}}}}
235
236 \CustomizeMathJax{\newcommand{\varclubsuit}{\mathord{\unicode{x02667}}}}
237 \CustomizeMathJax{\newcommand{\vardiamondsuit}{\mathord{\unicode{x02666}}}}
238 \CustomizeMathJax{\newcommand{\varheartsuit}{\mathord{\unicode{x02665}}}}
239 \CustomizeMathJax{\newcommand{\varspadesuit}{\mathord{\unicode{x02664}}}}
240
241 \CustomizeMathJax{\newcommand{\Nearrow}{\mathrel{\unicode{x021D7}}}}
242 \CustomizeMathJax{\newcommand{\Searrow}{\mathrel{\unicode{x021D8}}}}

```

```

243 \CustomizeMathJax{\newcommand{\Nwarrow}{\mathrel{\unicode{x021D6}}}}
244 \CustomizeMathJax{\newcommand{\Swarrow}{\mathrel{\unicode{x021D9}}}}
245 \CustomizeMathJax{\newcommand{\Top}{\mathord{\unicode{x02AEA}}}}
246 \CustomizeMathJax{\newcommand{\Bot}{\mathord{\unicode{x02AEB}}}}
247
248 \CustomizeMathJax{\newcommand{\leadstoext}{\mathrel{\unicode{xFF5E}}}}
249
250 \CustomizeMathJax{\newcommand{\sqcupplus}{\mathbin{\LWOverlaysymbols{+}{\unicode{x02294}}}}}
251 \CustomizeMathJax{\newcommand{\sqcapplus}{\mathbin{\LWOverlaysymbols{+}{\unicode{x02293}}}}}
252
253 \CustomizeMathJax{\newcommand{\dlb}{\mathopen{\unicode{x027E6}}}}
254 \CustomizeMathJax{\newcommand{\drb}{\mathopen{\unicode{x027E7}}}}
255
256 \CustomizeMathJax{\newcommand{\varg}{g}}
257 \CustomizeMathJax{\newcommand{\vary}{y}}
258 \CustomizeMathJax{\newcommand{\varv}{v}}
259 \CustomizeMathJax{\newcommand{\varw}{w}}
260
261 \CustomizeMathJax{\newcommand{\nexistsAlt}{\mathord{\unicode{x02204}}}}
262 \CustomizeMathJax{\newcommand{\existsAlt}{\mathord{\unicode{x02203}}}}
263 \CustomizeMathJax{\newcommand{\forallAlt}{\mathord{\unicode{x02200}}}}
264 \CustomizeMathJax{\newcommand{\emptysetAlt}{\mathord{\unicode{x02205}}}}
265
266 \CustomizeMathJax{\newcommand{\upartial}{\mathord{\unicode{x02202}}}}% not upright
267
268 \CustomizeMathJax{\let\varmathbb\mathbb}
269 \CustomizeMathJax{\let\vmathbb\mathbb}
270 \CustomizeMathJax{\let\vvmathbb\mathbb}
271
272 \CustomizeMathJax{\let\smallprod\prod}
273 \CustomizeMathJax{\let\smallsum\sum}
274 \CustomizeMathJax{\let\smallcoprod\coprod}
275
276 \CustomizeMathJax{\newcommand{\openbox}{\mathord{\unicode{x25FD}}}}
277 \CustomizeMathJax{\let\textsquare\openbox}

278 \CustomizeMathJax{\let\vareemptyset\emptyset}
279 %
280 % for newpxmath:
281 \CustomizeMathJax{\newcommand{\mathsterling}{\mathord{\unicode{x000A3}}}}
282 \CustomizeMathJax{\newcommand{\mathcent}{\mathord{\unicode{x000A2}}}}
283
284 \end{warpMathJax}

```

---

File 551 **lwarp-common-mathjax-nonunicode.sty**

§ 657 Package **common-mathjax-nonunicode**

(Emulates or patches code by DANIEL FLIPO, MICHAEL SHARPE.)

pkg Common code used by newpxmath, newtxmath, newtxsf, kpfonts-otf for MATHJAX.

lwarp-common-mathjax-nonunicode These are symbols not found in UNICODE.

Factored from lwarp-common-mathjax-newpctxmath.

for HTML output:

```
1 \ProvidesPackage{lwarp-common-mathjax-nonunicode}[2020/09/20]
```

For MATHJAX:

```
2 \LWR@origRequirePackage{lwarp-common-mathjax-overlaysymbols}
3
4 \begin{warpMathJax}
5 \CustomizeMathJax{\newcommand{\mmapsto}{\mathrel{\unicode{x021A6}}}}
6 \CustomizeMathJax{\let\mmapstochar\mmapsto}
7 \CustomizeMathJax{\newcommand{\longmmapsto}{\mathrel{\unicode{x021A6}}}}
8 \CustomizeMathJax{\newcommand{\mmappedfrom}{\mathrel{\unicode{x021A4}}}}
9 \CustomizeMathJax{\let\mmappedfromchar\mmappedfrom}
10 \CustomizeMathJax{\newcommand{\longmmappedfrom}{\mathrel{\unicode{x021A4}}}}
11 \CustomizeMathJax{\let\mmapsfrom\mmappedfrom}% from kpfonts-otf
12 \CustomizeMathJax{\let\longmmapsfrom\longmmappedfrom}% from kpfonts-otf
13
14 \CustomizeMathJax{\newcommand{\Mmapsto}{\mathrel{\unicode{x02907}}}}
15 \CustomizeMathJax{\let\Mmapstochar\Mmapsto}
16 \CustomizeMathJax{\newcommand{\Longmmapsto}{\mathrel{\unicode{x027FE}}}}
17 \CustomizeMathJax{\newcommand{\Mmappedfrom}{\mathrel{\unicode{x02906}}}}
18 \CustomizeMathJax{\let\Mmappedfromchar\Mmappedfrom}
19 \CustomizeMathJax{\newcommand{\Longmmappedfrom}{\mathrel{\unicode{x027FD}}}}
20 \CustomizeMathJax{\let\Mmapsfrom\Mmappedfrom}% from kpfonts-otf
21 \CustomizeMathJax{\let\Longmmapsfrom\Longmmappedfrom}% from kpfonts-otf
22 %
23 \CustomizeMathJax{\newcommand{\boxright}{\mathrel{\unicode{x025A1}\!\unicode{x02192}}}}
24 \CustomizeMathJax{\newcommand{\boxleft}{\mathrel{\unicode{x02190}\!\unicode{x025A1}}}}
25 \CustomizeMathJax{\newcommand{\boxdotright}{\mathrel{\unicode{x022A1}\!\unicode{x02192}}}}
26 \CustomizeMathJax{\newcommand{\boxdotleft}{\mathrel{\unicode{x02190}\!\unicode{x022A1}}}}
27
28 \CustomizeMathJax{\newcommand{\Diamondright}{\mathrel{\unicode{x025C7}\!\unicode{x02192}}}}
29 \CustomizeMathJax{\newcommand{\Diamondleft}{\mathrel{\unicode{x02190}\!\unicode{x025C7}}}}
30 \CustomizeMathJax{\newcommand{\Diamonddotright}{\mathrel{\unicode{x027D0}\!\unicode{x02192}}}}
31 \CustomizeMathJax{\newcommand{\Diamonddotleft}{\mathrel{\unicode{x02190}\!\unicode{x027D0}}}}
32
33 \CustomizeMathJax{\newcommand{\boxRight}{\mathrel{\unicode{x025A1}\!\unicode{x021D2}}}}
34 \CustomizeMathJax{\newcommand{\boxLeft}{\mathrel{\unicode{x021D0}\!\unicode{x025A1}}}}
35 \CustomizeMathJax{\newcommand{\boxdotRight}{\mathrel{\unicode{x022A1}\!\unicode{x021D2}}}}
36 \CustomizeMathJax{\newcommand{\boxdotLeft}{\mathrel{\unicode{x021D0}\!\unicode{x022A1}}}}
37
38 \CustomizeMathJax{\newcommand{\DiamondRight}{\mathrel{\unicode{x025C7}\!\unicode{x021D2}}}}
39 \CustomizeMathJax{\newcommand{\DiamondLeft}{\mathrel{\unicode{x021D0}\!\unicode{x025C7}}}}
40 \CustomizeMathJax{\newcommand{\DiamonddotRight}{\mathrel{\unicode{x027D0}\!\unicode{x021D2}}}}
41 \CustomizeMathJax{\newcommand{\DiamonddotLeft}{\mathrel{\unicode{x021D0}\!\unicode{x027D0}}}}
42 \CustomizeMathJax{\newcommand{\Diamonddot}{\mathrel{\unicode{x027D0}}}}
43
44 \CustomizeMathJax{\newcommand{\circleright}{\mathrel{\unicode{x025CB}\!\unicode{x02192}}}}
45 \CustomizeMathJax{\newcommand{\circleleft}{\mathrel{\unicode{x02190}\!\unicode{x025CB}}}}
46 \CustomizeMathJax{\newcommand{\circledotright}{\mathrel{\unicode{x02299}\!\unicode{x02192}}}}
47 \CustomizeMathJax{\newcommand{\circledotleft}{\mathrel{\unicode{x02190}\!\unicode{x02299}}}}
48 \CustomizeMathJax{\let\circleddotright\circledotright}
49 \CustomizeMathJax{\let\circleddotleft\circledotleft}
50
```

```

51 \CustomizeMathJax{\newcommand{\multimapinv}{\mathrel{\unicode{x027DC}}}}
52 \CustomizeMathJax{\newcommand{\multimapboth}{\mathrel{\unicode{x029DF}}}}
53 \CustomizeMathJax{\newcommand{\multimapdot}{\mathrel{-!\bullet}}}
54 \CustomizeMathJax{\newcommand{\multimapdotinv}{\mathrel{\bullet!-}}}
55 \CustomizeMathJax{\newcommand{\multimapdotboth}{\mathrel{\bullet!!\bullet}}}
56 \CustomizeMathJax{\newcommand{\multimapdotbothA}{\mathrel{\unicode{x022B6}}}}
57 \CustomizeMathJax{\newcommand{\multimapdotbothB}{\mathrel{\unicode{x22B7}}}}
58
59 \CustomizeMathJax{\newcommand{\multimapbothvert}{%
60 \mathrel{\overset{\unicode{x025CB}}{\underset{\unicode{x025CB}}{|}}}}%
61 }}
62 \CustomizeMathJax{\newcommand{\multimapdotbothvert}{%
63 \mathrel{\overset{\unicode{x025CF}}{\underset{\unicode{x025CF}}{|}}}}%
64 }}
65 \CustomizeMathJax{\newcommand{\multimapdotbothBvert}{% bug in kpfonts-otf
66 \mathrel{\overset{\unicode{x025CF}}{\underset{\unicode{x025CB}}{|}}}}%
67 }}
68 \CustomizeMathJax{\newcommand{\multimapdotbothAvert}{% bug in kpfonts-otf
69 \mathrel{\overset{\unicode{x025CB}}{\underset{\unicode{x025CF}}{|}}}}%
70 }}
71
72 \CustomizeMathJax{\newcommand{\bignplus}{%
73 \mathop{\LWROverLaysymbols{\unicode{xFF0B}}{\unicode{x22C2}}}}%
74 }}
75 \CustomizeMathJax{\let\bigcapplus\bignplus}
76 \CustomizeMathJax{\let\capplus\bignplus}% from kpfonts-otf
77
78 \CustomizeMathJax{\newcommand{\bigsqcapplus}{%
79 \mathop{\LWROverLaysymbols{\unicode{xFF0B}}{\unicode{x2A05}}}}
80 }}
81 \CustomizeMathJax{\let\sqcapplus\bigsqcapplus}% from kpfonts-otf
82
83 \CustomizeMathJax{\newcommand{\bigscupplus}{%
84 \mathop{\LWROverLaysymbols{\unicode{xFF0B}}{\unicode{x2A06}}}}
85 }}
86 \CustomizeMathJax{\let\scupplus\bigscupplus}% from kpfonts-otf
87
88 \CustomizeMathJax{\newcommand{\parallelslant}{\mathrel{\unicode{x02AFD}}}}
89 \CustomizeMathJax{\newcommand{\parallelbackslant}{%
90 \mathrel{\unicode{x0005C}\!\!\unicode{x0005C}}}%
91 }}
92
93 \CustomizeMathJax{\newcommand{\Eqqcolon}{\mathrel{=\!\unicode{x2237}}}}
94 \CustomizeMathJax{\let\eqqColon\Eqqcolon}% for kpfonts-otf
95 \CustomizeMathJax{\newcommand{\dashColon}{\mathrel{-\unicode{x2237}}}}
96 \CustomizeMathJax{\newcommand{\Colondash}{\mathrel{\unicode{x2237}-}}}
97
98 \CustomizeMathJax{\newcommand{\colonapprox}{\mathrel{: \approx}}}
99 \CustomizeMathJax{\newcommand{\colonsim}{\mathrel{: \sim}}}
100 \CustomizeMathJax{\newcommand{\Colonapprox}{\mathrel{\unicode{x2237}\!\approx}}}
101 \CustomizeMathJax{\newcommand{\Colonsim}{\mathrel{\unicode{x2237}\!\sim}}}
102
103 \CustomizeMathJax{\newcommand{\strictif}{\mathrel{\unicode{x0297D}}}}% right fish tail
104 \CustomizeMathJax{\newcommand{\strictfi}{\mathrel{\unicode{x0297C}}}}% left fish tail
105 \CustomizeMathJax{\newcommand{\strictiff}{%

```

```

106 \mathrel{\unicode{x0297C}\!\!\unicode{x0297D}}%
107 }}% left/right fish tails
108
109 \CustomizeMathJax{\newcommand{\circledwedge}{%
110 \mathbin{\LWROverlaysymbols{\unicode{x025EF}}{\unicode{x02227}}}%
111 }}
112 \CustomizeMathJax{\newcommand{\circledvee}{%
113 \mathbin{\LWROverlaysymbols{\unicode{x025EF}}{\unicode{0x02228}}}%
114 }}
115 \CustomizeMathJax{\newcommand{\circledbar}{\mathbin{\unicode{x029B6}}}}
116
117 \CustomizeMathJax{\newcommand{\openJoin}{\mathrel{\unicode{x2AA4}}}}% overlapping ><
118 \CustomizeMathJax{\newcommand{\opentimes}{\mathrel{\unicode{x2AA4}}}}% overlapping ><
119
120 \CustomizeMathJax{\newcommand{\VvDash}{\mathrel{\unicode{x22AA}}}}
121
122 \CustomizeMathJax{\newcommand{\lambdabar}{%
123 \mathord{\LWROverlaysymbols{\raise{.5ex}{-}}{\lambda}}}%
124 }}
125
126 \CustomizeMathJax{\newcommand{\lambdaslash}{\mathord{\unicode{x019B}}}}
127
128 \CustomizeMathJax{\newcommand{\Wr}{\mathbin{\unicode{x02240}\!\unicode{x02240}}}}
129
130 \CustomizeMathJax{\newcommand{\dashleftrightharrow}{%
131 \mathrel{\unicode{x021E0}\!\unicode{x021E2}}}%
132 }}
133 \CustomizeMathJax{\let\leftrightdasharrow\dashleftrightharrow}% for kpfonts-otf
134
135 \end{warpMathJax}

```

---

File 552 **lwarp-common-mathjax-overlaysymbols.sty**

§ 658 Package **common-mathjax-overlaysymbols**

Pkg Common code used by a number of packages to overlay two symbols for MATHJAX.

lwarp-common-mathjax-overlaysymbols

**for HTML output:** 1 \ProvidesPackage{lwarp-common-mathjax-overlaysymbols}[2020/08/17]

\LWROverlaysymbols {<symbol>} {<symbol>}

Overlays one symbol over another.

```

2 \begin{warpMathJax}
3
4 \CustomizeMathJax{\newcommand{\LWROverlaysymbols}[2]{%
5 \mathord{%
6 \smash{%
7 \mathop{#2\strut}%
8 \limits^{\smash{\lower3ex{#1}}}}%
9 }%
10 \strut%
11 }%

```

```
12 }}
13
14 \end{warpMathJax}
```

# Change History

## § 659 Chg Hist

For the most recent changes, see page 1316.

|       |                                                                |                                                                                    |
|-------|----------------------------------------------------------------|------------------------------------------------------------------------------------|
| v0.10 | General: 2016/03/08 Initial version . . . 1                    | Test Suite: Assigned cleveref name for Test Float. . . . . 1                       |
| v0.11 | General: 2016/03/11 . . . . . 1                                | Test Suite: Floatrow . . . . . 1                                                   |
|       | Added section: Operating-System portability. . . . . 228       |                                                                                    |
|       | Added section: Selecting the operating system. . . . . 118     |                                                                                    |
|       | Test Suite: MS-WINDOWS in README.txt . . . . . 1               |                                                                                    |
|       | Test Suite: limages and index in README.txt . . . . . 1        |                                                                                    |
| v0.12 | \LWR@newhtmlfile: Bugfix: toc with numbered files. . . . . 392 |                                                                                    |
|       | General: 2016/03/14 . . . . . 1                                |                                                                                    |
|       | Global: Uses \p@(type) in float captions. . . . . 1            |                                                                                    |
|       | Test Suite: Sub-figures . . . . . 1                            |                                                                                    |
| v0.13 | \CaptionSeparator: Fix for newer babel package. . . . . 519    |                                                                                    |
|       | \LWR@LwarpStart: \up and \fup . . . 412                        |                                                                                    |
|       | General: 2016/03/24 . . . . . 1                                |                                                                                    |
|       | Fix dollar-redefined bug for newer package. . . . . 1149       |                                                                                    |
|       | Removed package: subfig . . . . . 1                            |                                                                                    |
|       | Test Suite: Ordinals, Subcaption . . . 1                       |                                                                                    |
| v0.14 | \LWR@htmlsectionfilename: Fix: Links to home page. . . . . 345 |                                                                                    |
|       | General: 2016/03/31 . . . . . 1                                |                                                                                    |
|       | floatrow: Added. . . . . 804                                   |                                                                                    |
|       | Docs: Commands for a successful HTML conversion. . . . . 123   |                                                                                    |
|       | Docs: Commands into a warpprint environment. . . . . 120       |                                                                                    |
|       | Docs: Newclude limitations. . . . 176                          |                                                                                    |
|       | Docs: Table: Cross-referencing data structures. . . . . 503    |                                                                                    |
|       | Docs: Table: Float data structures. 515                        |                                                                                    |
|       | Docs: Trademarks section. . . . . 202                          |                                                                                    |
|       | Docs: Troubleshooting cross-references. . . . . 197            |                                                                                    |
|       |                                                                | v0.15                                                                              |
|       |                                                                | General: 2016/04/06 . . . . . 1                                                    |
|       |                                                                | Added. . . . . 809                                                                 |
|       |                                                                | Ampersand (&): Fixed handling when passed as an argument. . . 449                  |
|       |                                                                | Docs: Added warning icons for items needing special attention. 205                 |
|       |                                                                | Docs: Clarify print/HTML output. 119                                               |
|       |                                                                | Docs: Moved the supported features table to the introduction. 66                   |
|       |                                                                | Files: lwarp_formal.css added. . . . 1                                             |
|       |                                                                | Fix: steps counter . . . . . 809                                                   |
|       |                                                                | Fixed & handling. . . . . 807                                                      |
|       |                                                                | Test Suite: test_suite_formal.css file added. . . . . 1                            |
|       |                                                                | v0.16                                                                              |
|       |                                                                | General: 2016/04/11 . . . . . 1                                                    |
|       |                                                                | \titlingpage: Improved print-output spacing. . . . . 420                           |
|       |                                                                | xfrac: Adjusted for the use of any font: . . . . . 1214                            |
|       |                                                                | Added XeLaTeX, LuaLaTeX support. . . . . 206                                       |
|       |                                                                | Docs: Font and UTF-8 support. . . 101                                              |
|       |                                                                | Docs: Moved location of \usepackage{lwarp}. . . . . 104                            |
|       |                                                                | Docs: Text not converting. . . . . 197                                             |
|       |                                                                | Lwarp no longer selects fonts. 101, 239                                            |
|       |                                                                | Removed package: suffix . . . . . 1                                                |
|       |                                                                | Test Suite: Improved titlingpage. 420                                              |
|       |                                                                | Test Suite: Lwarp no longer selects fonts. . . . . 1                               |
|       |                                                                | Test Suite: Supports XeLaTeX, LuaLaTeX. . . . . 1                                  |
|       |                                                                | v0.17                                                                              |
|       |                                                                | \LWR@htmlsectionfilename: Fix: Links when entire doc is one HTML page. . . . . 345 |
|       |                                                                | General: 2016/04/14 . . . . . 1                                                    |
|       |                                                                | mdframed: Added. . . . . 937                                                       |
|       |                                                                | Test Suite: Fix: Print-version front-matter page numbers. . . . 1                  |

|                                                                       |      |                                                                          |          |
|-----------------------------------------------------------------------|------|--------------------------------------------------------------------------|----------|
| Test Suite: Mdfamed                                                   | 1    | \LWR@minipagestartpars: Suppresses paragraph tags between minipages.     | 618      |
| v0.18                                                                 |      | \LWR@subsingledollar: MATHJAX support.                                   | 556      |
| \LWR@myshorttoc: Reorganize \HomeHTMLfilename logic.                  | 524  | \LateximageFontSizeName: Add: User-adjustable math/lateximage font size. | 574      |
| \LWR@newhtmlfile: sideroc after title, improving responsive design.   | 391  | \hspace: Fix: \hspace length computations.                               | 619      |
| \LWR@requesttoc: Reorganize \HomeHTMLfilename logic.                  | 414  | \minipagefullwidth: Added: No width tag for the next minipage in HTML.   | 596      |
| \LWR@subhyperref: Improved HTML output linebreaks.                    | 512  | \warpHTMLonly: Added.                                                    | 237      |
| \LWR@subhyperrefclass: Improved HTML output linebreaks.               | 512  | \warpprintonly: Replaces \rowprintedonly.                                | 237      |
| \LWR@subinlineimage: Suppress extra space.                            | 514  | \xfracHTMLfontsize: Added.                                               | 1214     |
| \hspace: \hspace supported.                                           | 619  | General: 2016/06/08                                                      | 1        |
| General: 2016/05/19                                                   | 1    | css for table note item.                                                 | 1146     |
| graphics: Add: svgz file extension.                                   | 841  | MATHJAX support added.                                                   | 561, 569 |
| graphics: Fix: \linewidth, \textwidth, \textheight inside a minipage. | 841  | multirow: Added optional args.                                           | 969      |
| graphics: Improved HTML output linebreaks.                            | 841  | xcolor: Supports colored \rule.                                          | 1205     |
| graphics: em, ex, %, px dimensions preserved.                         | 841  | Adapts to tikz version.                                                  | 1149     |
| File: lwarp.css: Improved toc outline display.                        | 1    | Avoids MATHJAX.                                                          | 549      |
| Files: lwarp.css and lwarp_formal.css: Improved responsive design.    | 1    | cleveref: Loaded \AtEndPreamble.                                         | 593      |
| Microtype disabled during HTML generation                             | 239  | Docs: Math options.                                                      | 104      |
| PDF Unicode input characters.                                         | 222  | Docs: Table: Cross-referencing data structures, updated.                 | 503      |
| Test Suite: Verse package                                             | 1    | File: lwarp.css: tnoteitemheader added.                                  | 1        |
| lateximage: pdfcrop: --hires added.                                   | 577  | File: lwarp_mathjax.txt added.                                           | 1        |
| Reorganize \HomeHTMLfilename logic.                                   | 577  | Introduction: MATHJAX support mentioned.                                 | 63       |
| Suppress extra space.                                                 | 577  | Options: mathsvg and mathjax                                             | 231      |
| verse: Supports verse, memoir packages.                               | 1191 | titles: null \pagestyle and \thispagestyle for HTML.                     | 1150     |
| minipage: Fix: \linewidth, \textwidth, \textheight inside a minipage. | 597  | v0.20                                                                    |          |
| v0.19                                                                 |      | \BlockClassSingle: Renamed from "LWR@htmldivclassline".                  | 360      |
| \HTMLfilename: Docs: Escape filename underscores.                     | 344  | \HTMLDescription: Added \NewHTMLdescription. (Renamed in v0.30.)         | 372      |
| \HomeHTMLfilename: Docs: Escape filename underscores.                 | 344  | \HTMLfilename: No longer escape underscores.                             | 344      |
| \LWR@LwarpStart: Enabled \ equal to \newline.                         | 411  | \HomeHTMLfilename: No longer escape underscores.                         | 344      |
| \LWR@doequation: MATHJAX support.                                     | 564  | \InlineClass: Renamed from "inlineclass".                                | 361      |
| \LWR@doubledollar: MATHJAX support.                                   | 557  | \LWR@closeparagraph: \unskip extra spaces.                               | 365      |
| \LWR@filestart: lwarp_mathjax.txt loaded.                             | 407  | No break tags in the start/end of a tabular.                             | 365      |
|                                                                       |      | \LWR@endofline: Fix: \                                                   | 617      |
|                                                                       |      | \LWR@filestart: Adds meta description.                                   | 407      |

|                                                                                                                  |     |                                                                                           |      |
|------------------------------------------------------------------------------------------------------------------|-----|-------------------------------------------------------------------------------------------|------|
| <code>\LWR@htmldivclass</code> : Added optional style. . . . .                                                   | 359 | <code>lrcaption</code> : Added. . . . .                                                   | 910  |
| <code>\LWR@htmlclass</code> : Added optional style. . . . .                                                      | 359 | <code>lwarp-newproject</code> : Added. . . . .                                            | 266  |
| <code>\LWR@htmlsectionfilename</code> : HTMLFilename: removed additional trailing '-', and may be empty. . . . . | 345 | <code>microtype</code> : User-interface emulated. . . . .                                 | 953  |
| Sections called "Index" or "index" have an underscore prepended to their filenames if no prefix. . . . .         | 345 | <code>needspace</code> : Added. . . . .                                                   | 980  |
| <code>\LWR@hyperindexrefsubtwo</code> : Print mode provided in case hyperref not used. . . . .                   | 539 | <code>nowidow</code> : Added. . . . .                                                     | 994  |
| <code>\LWR@longtabledatacaptiontag</code> : Fix: Pars in captions. . . . .                                       | 486 | <code>placeins</code> : Added. . . . .                                                    | 1030 |
| <code>\LWR@section</code> : Combined higher-level sections together into files. . . . .                          | 399 | <code>ragged2e</code> : Added. . . . .                                                    | 1039 |
| <code>\LWR@setOSWindows</code> : Auto-detects operating system. . . . .                                          | 229 | <code>setspace</code> : Improved support. . . . .                                         | 1064 |
| <code>\LWR@subhtmlclass</code> : Factored code. . . . .                                                          | 358 | <code>textpos</code> : Added. . . . .                                                     | 1138 |
| <code>\SetHTMLFileNumber</code> : Add: Control file numbers. . . . .                                             | 344 | <code>titles</code> : Added. . . . .                                                      | 1150 |
| <code>\cpgereffor</code> : User-redefinable word for page references. . . . .                                    | 739 | <code>titlesec</code> : Added. . . . .                                                    | 1153 |
| <code>\dotfill</code> : Inserts an ellipsis. . . . .                                                             | 617 | <code>titletoc</code> : Added. . . . .                                                    | 1155 |
| <code>\hfill</code> : Inserts a \quad. . . . .                                                                   | 617 | <code>titling</code> : Improved compatibility. . . . .                                    | 1157 |
| <code>\hrulefill</code> : Inserts a short rule. . . . .                                                          | 617 | <code>tocloft</code> : Added. . . . .                                                     | 1165 |
| <code>\hspace</code> : Add: Supports HTML thin breakable space. . . . .                                          | 619 | <code>wallpaper</code> : Added. . . . .                                                   | 1197 |
| <code>\pageref</code> : Added. . . . .                                                                           | 510 | <code>wrapfig</code> : Added. . . . .                                                     | 1200 |
| <code>\tracinglwarp</code> : Added. . . . .                                                                      | 253 | <code>xetexko-vertical</code> : Added. . . . .                                            | 1213 |
| General: 2017/02/09 . . . . .                                                                                    | 1   | Added @, <, > columns. . . . .                                                            | 442  |
| <code>afterpage</code> : Added. . . . .                                                                          | 647 | Added single-expansion data arrays. . . . .                                               | 341  |
| <code>alltt</code> : Added. . . . .                                                                              | 652 | Code factored into independent <code>lwarp_html</code> files. . . . .                     | 635  |
| <code>bookmark</code> : Added. . . . .                                                                           | 690 | Docs: Examples for generating HTML file names. . . . .                                    | 116  |
| <code>caption</code> and <code>subcaption</code> supported. . . . .                                              | 1   | Docs: Improved index. . . . .                                                             | 1    |
| <code>cleveref</code> and referencing patches: Applied <code>\AfterEndPreamble</code> . . . . .                  | 738 | Enhanced titling support. . . . .                                                         | 419  |
| <code>draftwatermark</code> : Added. . . . .                                                                     | 755 | File: <code>lwarp.css</code> : Minor fixes for validation. . . . .                        | 1    |
| <code>eso-pic</code> : Added. . . . .                                                                            | 775 | File: <code>lwarpmk</code> used to compile print, HTML, indexes, and lateximages. . . . . | 1    |
| <code>everypage</code> : Added. . . . .                                                                          | 779 | Fix: <code>\linewidth</code> in a floatrow. . . . .                                       | 807  |
| <code>extramarks</code> : Added. . . . .                                                                         | 780 | Moved sidebar and example code to test suite. . . . .                                     | 1    |
| <code>fancyhdr</code> : Added. . . . .                                                                           | 786 | Page geometry set to 6in wide with large margins. . . . .                                 | 240  |
| <code>float</code> : Improved float caption type handling. . . . .                                               | 802 | Parallel versions of aux files for print/HTML. . . . .                                    | 1    |
| <code>graphics</code> : Fix: Expands filename. . . . .                                                           | 841 | Removed reliance on <code>make</code> , <code>grep</code> , <code>gawk</code> . . . . .   | 1    |
| <code>graphics</code> : Fix: <code>\linewidth</code> in a floatrow. . . . .                                      | 841 | <code>Tabular</code> : <code>\unskip</code> extra spaces. . . . .                         | 442  |
| <code>hyperref</code> : Additional user macros. . . . .                                                          | 854 | Test Suite: HTML meta descriptions. . . . .                                               | 1    |
| <code>keyfloat</code> : Added. . . . .                                                                           | 876 | <code>verbatim</code> : Added. . . . .                                                    | 431  |
| <code>letterspace</code> : User-interface emulated. . . . .                                                      | 890 | <code>BlockClass</code> : Added optional style. . . . .                                   | 360  |
| <code>listings</code> : Added. . . . .                                                                           | 900 | Renamed from "blockclass". . . . .                                                        | 360  |
|                                                                                                                  |     | <code>LWR@nestspan</code> : Fix: Minipages inside a span. . . . .                         | 355  |
|                                                                                                                  |     | v0.21                                                                                     |      |
|                                                                                                                  |     | <code>\LWR@LwarpStart</code> : Changed lateximages to a .txt file. . . . .                | 411  |
|                                                                                                                  |     | <code>\LWR@filestart</code> : Skip title if not given. . . . .                            | 407  |
|                                                                                                                  |     | <code>\LWR@newhtmlfile</code> : Skip title if not given. . . . .                          | 391  |

|                                                                                                                                                              |      |                                                                                                                                                                                  |        |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <code>\marginpar</code> : Fixed source listing. . .                                                                                                          | 378  | <code>\hspace</code> : Add: <code>\hspace \fill</code><br>converts to 2em . . . . .                                                                                              | 619    |
| <code>\marginparBlock</code> : Fixed source<br>listing. . . . .                                                                                              | 379  | <code>\hypertocfloat</code> : List of floats<br>responds to <code>lofdepth</code> , <code>lotdepth</code> . 530                                                                  |        |
| General: 2017/02/23 . . . . .                                                                                                                                | 1    | General: 2017/03/15 . . . . .                                                                                                                                                    | 1      |
| <code>fontenc</code> : Added. . . . .                                                                                                                        | 814  | <code>floatrow</code> : Support for <code>subfig</code> . . . . .                                                                                                                | 804    |
| <code>lwarpmk</code> : Fix: <code>lwarpmk</code> again for<br>WINDOWS. . . . .                                                                               | 320  | <code>subfig</code> : Added. . . . .                                                                                                                                             | 1112   |
| <code>lwarpmk</code> : Fix: <code>lwarpmk</code> <code>limages</code> for<br>WINDOWS. . . . .                                                                | 320  | <code>tikz</code> : For <code>tikz v3.0.0</code> or later,<br>auto-loads <code>tikz babel</code> library if<br>necessary. . . . .                                                | 1149   |
| <code>lwarpmk</code> : Fix: <code>lwarpmk</code> uses<br><code>lateximages</code> text file instead of<br>shell script. . . . .                              | 320  | Docs: Filename underscore. 104, 126                                                                                                                                              |        |
| Add: Errors for misplaced<br>packages. . . . .                                                                                                               | 206  | Fix for inline images. . . . .                                                                                                                                                   | 1149   |
| Docs: Added internet class. . . . .                                                                                                                          | 73   | No longer preloads <code>subcaption</code> ;<br>conflicted with <code>subfig</code> . . . . .                                                                                    | 244    |
| Docs: Added TeX2page, GladTeX. . . . .                                                                                                                       | 73   | <code>picture</code> : Fix for inline images. . . . .                                                                                                                            | 594    |
| Docs: Installing on WINDOWS. . . . .                                                                                                                         | 79   |                                                                                                                                                                                  |        |
| File: <code>lwrap_tutorial.txt</code> added. . . . .                                                                                                         | 83   |                                                                                                                                                                                  |        |
| v0.22                                                                                                                                                        |      | v0.25                                                                                                                                                                            |        |
| <code>\LWR@parseDcolumn</code> : Added <code>tabular D</code><br><code>column</code> . . . . .                                                               | 458  | <code>\LWR@loadnever</code> : Added the ability to<br>prevent conflicting packages. . . . .                                                                                      | 208    |
| <code>\LWR@parsebangcolumn</code> : Added<br><code>tabular ! column</code> . . . . .                                                                         | 453  | <code>\addcontentsline</code> : Handles<br><code>theorems</code> . . . . .                                                                                                       | 523    |
| <code>\LWR@parsetablecols</code> : Unknown<br><code>table column</code> types become <code>l</code> .<br>Added <code>tabular D, !, X</code> columns. . . . . | 460  | General: 2016/03/22 . . . . .                                                                                                                                                    | 1      |
| <code>\LWR@printmcoldata</code> : Added <code>tabular</code><br><code>D, !, and X</code> columns. . . . .                                                    | 480  | <code>amsthm</code> : Added. . . . .                                                                                                                                             | 656    |
| General: 2017/03/02 . . . . .                                                                                                                                | 1    | <code>ellipsis</code> : Added. . . . .                                                                                                                                           | 761    |
| <code>abstract</code> : Added. . . . .                                                                                                                       | 637  | <code>emptypage</code> : Added. . . . .                                                                                                                                          | 762    |
| <code>change page</code> : Added. . . . .                                                                                                                    | 705  | <code>framed</code> : Added. . . . .                                                                                                                                             | 821    |
| <code>dcolumn</code> : Added. . . . .                                                                                                                        | 750  | <code>lips</code> : Added. . . . .                                                                                                                                               | 900    |
| <code>ftnright</code> : Added. . . . .                                                                                                                       | 823  | <code>mdframed</code> : Help avoid<br><code>hyphenation</code> . . . . .                                                                                                         | 938    |
| <code>geometry</code> : Nullified commands. . . . .                                                                                                          | 829  | <code>ntheorem</code> : Added. . . . .                                                                                                                                           | 994    |
| <code>layout</code> : Added. . . . .                                                                                                                         | 886  | <code>showidx</code> : Added. . . . .                                                                                                                                            | 1066   |
| <code>lscape</code> : Added. . . . .                                                                                                                         | 909  | <code>theorem</code> : Added. . . . .                                                                                                                                            | 1139   |
| <code>mcaption</code> : Added. . . . .                                                                                                                       | 937  | Basic L <sup>A</sup> T <sub>E</sub> X theorems: improved<br><code>css</code> . . . . .                                                                                           | 432    |
| <code>nameref</code> : Added. . . . .                                                                                                                        | 976  | Docs: Adds credits for patched<br><code>code</code> . . . . .                                                                                                                    | 1      |
| <code>nextpage</code> : Added. . . . .                                                                                                                       | 983  | Docs: Testing <code>lwrap</code> . . . . .                                                                                                                                       | 193    |
| <code>parskip</code> : Added. . . . .                                                                                                                        | 1015 | Fix: Allows XE <sup>L</sup> A <sub>T</sub> E <sub>X</sub> and Lua <sup>L</sup> A <sub>T</sub> E <sub>X</sub><br>to preload <code>graphics</code> and <code>graphicx</code> . 210 |        |
| <code>showkeys</code> : Added. . . . .                                                                                                                       | 1066 | v0.26                                                                                                                                                                            |        |
| <code>sidecap</code> : Added. . . . .                                                                                                                        | 1068 | General: 2017/03/31 . . . . .                                                                                                                                                    | 1      |
| <code>tabularx</code> : Added. . . . .                                                                                                                       | 1123 | <code>lwrap.css</code> : Improved responsive<br><code>marginpar</code> and <code>marginblock</code> . . . . .                                                                    | 273    |
| <code>varioref</code> : Supported. . . . .                                                                                                                   | 132  | <code>cutwin</code> : Added. . . . .                                                                                                                                             | 749    |
| <code>verse</code> : Added. . . . .                                                                                                                          | 1191 | <code>endnotes</code> : Added. . . . .                                                                                                                                           | 764    |
| v0.23                                                                                                                                                        |      | <code>floatflt</code> : Added. . . . .                                                                                                                                           | 803    |
| <code>\LWR@parsetablecols</code> : Fix for <code>vert bar</code><br><code>column type</code> . . . . .                                                       | 460  | <code>footmisc</code> : Added. . . . .                                                                                                                                           | 815    |
| <code>\LWR@printmcoldata</code> : Fix for <code>vert bar</code><br><code>column type</code> . . . . .                                                        | 480  | <code>footnotehyper</code> : Added. . . . .                                                                                                                                      | 817    |
| General: 2017/03/02 . . . . .                                                                                                                                | 1    | <code>footnote</code> : Added. . . . .                                                                                                                                           | 816    |
| v0.24                                                                                                                                                        |      | <code>marginfix</code> : Added. . . . .                                                                                                                                          | 921    |
| <code>\LWR@htmlfileref</code> : Fix: Index links<br>while <code>\tracinglwrap</code> . . . . .                                                               | 505  | <code>marginnote</code> : Added. . . . .                                                                                                                                         | 922    |
|                                                                                                                                                              |      | <code>mparhack</code> : Added. . . . .                                                                                                                                           | 963    |
|                                                                                                                                                              |      | <code>pagenote</code> : Supported as-is. . . . .                                                                                                                                 | 1008   |
|                                                                                                                                                              |      | <code>sidenotes</code> : Added. . . . .                                                                                                                                          | 1069   |
|                                                                                                                                                              |      | Docs: Improved M <sup>I</sup> K <sup>T</sup> E <sub>X</sub> install<br>instructions. . . . .                                                                                     | 78, 80 |



|                                                                                                                                    |     |                                                                                        |          |
|------------------------------------------------------------------------------------------------------------------------------------|-----|----------------------------------------------------------------------------------------|----------|
| <i>lwarpmk</i> : language now used for both index and glossary generation. . . . .                                                 | 320 | <i>cleveref</i> : Fix: Loaded<br>\AtEndPreamble. . . . .                               | 593      |
| File: <i>lwarp_html</i> . <i>xdy</i> renamed to <i>lwarp</i> . <i>xdy</i> . . . . .                                                | 315 | Fix: Incorrectly-inline math environments. . . . .                                     | 569      |
| Fix: *. <i>css</i> files only written in print mode. . . . .                                                                       | 273 | New handling of & to localize catcode changes. . . . .                                 | 442      |
| Fix: <i>lwarp</i> . <i>xdy</i> only written in print mode. . . . .                                                                 | 315 | v0.34                                                                                  |          |
| Fix: <i>lwarp_mathjax</i> . <i>txt</i> : Only written in print mode. . . . .                                                       | 316 | \@fnsymbol: Text symbols instead of math. . . . .                                      | 422      |
| Option <i>lwarpmklang</i> changed to <i>IndexLanguage</i> . . . . .                                                                | 232 | \InlineClass: Moved optional argument in front of mandatory. . . . .                   | 361      |
| Option <i>OSWindows</i> replaces macro <i>\warpOSWindows</i> . . . . .                                                             | 232 | \LWR@htmldivclass: Moved optional argument in front of mandatory. . . . .              | 359      |
| Option <i>xdyFilename</i> added. . . . .                                                                                           | 232 | \LWR@htmlclass: Moved optional argument in front of mandatory. . . . .                 | 359      |
| Option <i>latexmk</i> replaces macro <i>\UseLatexmk</i> . . . . .                                                                  | 234 | \LWR@htmlclassline: Moved optional argument in front of mandatory. . . . .             | 359      |
| Options <i>HomeHTMLFilename</i> and <i>HTMLFilename</i> replace macros <i>\HomeHTMLFilename</i> and <i>\HTMLFilename</i> . . . . . | 233 | \LWR@htmlspanclass: Moved optional argument in front of mandatory. . . . .             | 356      |
| v0.31                                                                                                                              |     | \LWR@nullfont: Improved font control. . . . .                                          | 543      |
| General: 2017/05/15 . . . . .                                                                                                      | 1   | \LWR@restoreorigformatting: <i>booktabs</i> : Works inside <i>lateximage</i> . . . . . | 542      |
| <i>keyfloat</i> : Improved compatibility. . . . .                                                                                  | 876 | Improved font control. . . . .                                                         | 542      |
| v0.32                                                                                                                              |     | \LWR@subhtmlclass: Moved optional argument in front of mandatory. . . . .              | 358      |
| <i>\RequirePackage</i> : Fix: Ignores blanks in package list. . . . .                                                              | 248 | \LWR@tabledatacolumn: <i>booktabs</i> : Works inside <i>lateximage</i> . . . . .       | 492      |
| General: 2016/06/09 . . . . .                                                                                                      | 1   | \fboxBlock: Added. . . . .                                                             | 603      |
| <i>glossaries</i> : Prevent error with <i>\glo@name</i> not defined. . . . .                                                       | 540 | \makebox: Fix: Handles paren arg. . . . .                                              | 601      |
| <i>lwarpmk</i> : Fix: <i>io.lines()</i> changed to <i>file:lines()</i> due to <i>luatex</i> changes. . . . .                       | 320 | General: 2017/08/08 . . . . .                                                          | 1        |
| v0.33                                                                                                                              |     | <i>babel-french</i> : Adds fixed-width HTML spaces to punctuation. . . . .             | 353      |
| <i>\HTMLAuthor</i> : Fix: Provides empty default author if none given. . . . .                                                     | 371 | <i>balance</i> : Added. . . . .                                                        | 677      |
| <i>\LWR@loadbefore</i> : Fix: No <i>\PackageError</i> if already loaded. . . . .                                                   | 208 | <i>booktabs</i> : Works inside <i>lateximage</i> . . . . .                             | 496, 691 |
| <i>\LWR@parseatcolumn</i> : Fix: Column alignment with leftmost @. . . . .                                                         | 453 | <i>boxedminipage2e</i> : Added. . . . .                                                | 693      |
| <i>\LWR@tabledatasinglecolumn</i> : Fix: Macros in tabular could cause extra data cell. . . . .                                    | 468 | <i>crop</i> : Added. . . . .                                                           | 746      |
| <i>\LWR@vspace</i> : Add: <i>\vspace</i> nullified. . . . .                                                                        | 621 | <i>enumerate</i> : Added. . . . .                                                      | 769      |
| <i>\StartDefiningTabulars</i> : Add: Avoids error: Misplaced alignment tab character &. . . . .                                    | 341 | <i>enumitem</i> : Added, no longer required. . . . .                                   | 769      |
| General: 2017/07/10 . . . . .                                                                                                      | 1   | <i>everyshi</i> : Added. . . . .                                                       | 780      |
| <i>amsmath</i> : Removed <i>fleqn</i> option. . . . .                                                                              | 653 | <i>fancybox</i> : Added. . . . .                                                       | 782      |
| <i>fancyhdr</i> : Fix: Optional args for <i>\thead</i> , etc. . . . .                                                              | 786 | <i>fancyvrb</i> : Added, no longer required. . . . .                                   | 788      |
| Add: Tabular at and bang columns now have their own HTML columns. . . . .                                                          | 442 | <i>figcaps</i> : Added. . . . .                                                        | 797      |
|                                                                                                                                    |     | <i>filecontents</i> : Required. Patched for <i>morewrites</i> . . . . .                | 243      |
|                                                                                                                                    |     | <i>floatpag</i> : Added. . . . .                                                       | 804      |
|                                                                                                                                    |     | <i>flushend</i> : Added. . . . .                                                       | 810      |
|                                                                                                                                    |     | <i>fullpage</i> : Added. . . . .                                                       | 824      |

|                                     |      |                                                         |      |
|-------------------------------------|------|---------------------------------------------------------|------|
| hyperxmp: Added. . . . .            | 863  | \LWR@currenttextcolor: Fix for                          |      |
| idxlayout: Added. . . . .           | 864  | \rule when xcolor not loaded. . .                       | 615  |
| marginfit: Added. . . . .           | 921  | \LWR@nullfonts: Fix: Filenames while                    |      |
| mdframed: Improved mdtheorem        |      | using MATHJAX. . . . .                                  | 543  |
| patch. . . . .                      | 944  | \LWR@restoreorigformatting:                             |      |
| moreverb: Added. . . . .            | 961  | siunitx: Improved                                       |      |
| paralist: Added. . . . .            | 1009 | super/subscripts in a                                   |      |
| pdfscape: Added. . . . .            | 1018 | lateximage. . . . .                                     | 542  |
| pdfsync: Added. . . . .             | 1022 | \LWR@section: Improved spacing. .                       | 399  |
| prelim2e: Added. . . . .            | 1032 | \LWR@stoppars: Extra HTML source                        |      |
| rotfloat: Added. . . . .            | 1049 | space after paragraphs. . . . .                         | 367  |
| savetrees: Added. . . . .           | 1050 | \LWR@subHTMLsanitize: Fix for                           |      |
| shadow: Added. . . . .              | 1065 | babel-french. . . . .                                   | 386  |
| syntonly: Added. . . . .            | 1121 | \fbox: Fix: Uses \fboxrule and                          |      |
| titles: No longer required. . . .   | 1150 | \fboxsep. . . . .                                       | 602  |
| titleref: Prevented. . . . .        | 1153 | \framebox: Fix: Handles width and                       |      |
| xcolor: Added                       |      | horiz position. . . . .                                 | 602  |
| \LWR@subcolorminipage. . . .        | 1209 | \makebox: Fix: Handles width and                        |      |
| xmpincl: Added. . . . .             | 1217 | horiz position. . . . .                                 | 601  |
| Docs: Horizontal space limitations. | 1    | General: 2017/08/17 . . . . .                           | 1    |
| Docs: Misplaced alignment           |      | babel-french: Adjustements for                          |      |
| character. . . . .                  | 197  | French variants, load order,                            |      |
| File: lwarp_mathjax.txt: Version    |      | footnotes, ellipses. . . . .                            | 353  |
| change. . . . .                     | 316  | footnote: Extra HTML source space                       |      |
| File: README.txt: updated. . . . .  | 1    | after paragraphs. . . . .                               | 816  |
| Fix: Added the eqnarray             |      | siunitx: Fix for babel-french. . . .                    | 587  |
| environments. . . . .               | 569  | siunitx: Improved symbol                                |      |
| Improved font control. . . . .      | 606  | support. . . . .                                        | 1080 |
| Lists refactored to remove          |      | transparent: Added. . . . .                             | 1175 |
| enumitem requirement. . . . .       | 433  | upref: Added. . . . .                                   | 1189 |
| Verbatim refactored to remove       |      | xcolor: Added \fcolorboxBlock,                          |      |
| fancyvrb requirement. . . . .       | 428  | \colorboxBlock. . . . .                                 | 1201 |
| tabular: booktabs: Works inside     |      | xcolor: Fix: Background none in                         |      |
| lateximage. . . . .                 | 497  | print mode. . . . .                                     | 1201 |
| lateximage: Fix: lateximage with    |      | xcolor: Refactored                                      |      |
| minipage, \parbox, \makebox,        |      | \LWR@colorstyle. . . . .                                | 1205 |
| \fbox, \framebox, \raisebox,        |      | xcolor: Uses \fboxrule and                              |      |
| \scalebox, \reflectbox. . . . .     | 577  | \fboxsep. . . . .                                       | 1201 |
| BlockClass: Moved optional          |      | xcolor: \fcolorbox etc. now work                        |      |
| argument in front of mandatory.     | 360  | inside lateximage. . . . .                              | 1201 |
| fminipage: Added. . . . .           | 603  | Docs: Reorganized: Special cases                        |      |
| \LWR@nestspan: Fix: Minipages,      |      | and limitations. . . . .                                | 123  |
| BlocksClass, and lists inside a     |      | Source: Improved formatting. . . . .                    | 1    |
| span. . . . .                       | 355  | tabular: Fix for babel-french. . . . .                  | 497  |
| v0.35                               |      | lateximage: Footnotes appear in                         |      |
| General: 2017/08/08 . . . . .       | 1    | regular text instead of the                             |      |
| Fix: \textbf and related. . . . .   | 606  | lateximage minipage. . . . .                            | 577  |
| v0.36                               |      | v0.37                                                   |      |
| \LWR@footnotetext: Extra HTML       |      | \@include: Maintains independent                        |      |
| source space after paragraphs. .    | 375  | aux files for HTML. . . . .                             | 252  |
| Force HTML superscripts. . . . .    | 375  | General: 2017/08/19 . . . . .                           | 1    |
| \LWR@HTMLsanitizeexpand: Fix for    |      | L <sup>A</sup> T <sub>E</sub> X accents: Added. . . . . | 264  |
| babel-french. . . . .               | 387  | babel-french: Adjustment for load                       |      |
| \LWR@closeparagraph: Extra HTML     |      | order. . . . .                                          | 353  |
| source space after paragraphs. .    | 365  | color: Prevented. . . . .                               | 743  |

|                                                                             |           |                                                                                                              |          |
|-----------------------------------------------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------|----------|
| siunitx: Improved symbol support. . . . .                                   | 1080      | \LWR@domulticolumn: Add: Optional vpos and # rows. . . . .                                                   | 483      |
| textcomp: Improved support. . . . .                                         | 1135      | \LWR@restoreorigformatting: Appended with \appto instead of calling various macros. . . . .                  | 542      |
| <i>lwarpmk</i> : Removes additional HTML aux files. . . . .                 | 320       | \LWR@tabledatacolumnntag: Don't start a data cell if see \TabularMacro. . . . .                              | 492      |
| File handles reorganized. . . . .                                           | 251       | \ResumeTabular: Added. . . . .                                                                               | 492      |
| v0.38                                                                       |           | \TabularMacro: Added. . . . .                                                                                | 491      |
| \@secntformat: Added for appendix. . . . .                                  | 398       | \multicolumnrow: Added. . . . .                                                                              | 490, 970 |
| \ForceHTMLPage: Added. . . . .                                              | 396       | \printauthor: Removed minipages. Supports authblk with <div>s of class oneauthor instead of tabular. . . . . | 420      |
| \ForceHTMLTOC: Added. . . . .                                               | 396       | \thanksmarkseries: Removed minipage footnotes. . . . .                                                       | 1161     |
| \LWR@section: \part* starts a new HTML page, for appendix. . . . .          | 399       | General: 2017/09/05 . . . . .                                                                                | 1        |
| Modified spacing, uses \numberline. . . . .                                 | 399       | a4wide: Added. . . . .                                                                                       | 637      |
| \numberline: Added trailing \quad. . . . .                                  | 529       | a4: Added. . . . .                                                                                           | 636      |
| \part: Fix with article class. . . . .                                      | 405       | a5comb: Added. . . . .                                                                                       | 637      |
| General: 2017/08/27 . . . . .                                               | 1         | addlines: Added. . . . .                                                                                     | 647      |
| appendix: Added. . . . .                                                    | 662       | anysize: Added. . . . .                                                                                      | 661      |
| arabicfront: Added. . . . .                                                 | 664       | authblk: Added. . . . .                                                                                      | 671      |
| chappg: Added. . . . .                                                      | 708       | bigdelim: Added. . . . .                                                                                     | 687      |
| color: Forces xcolor as well. . . . .                                       | 743       | bigstrut: Added. . . . .                                                                                     | 688      |
| fix2col: Added. . . . .                                                     | 798       | ebook: Added. . . . .                                                                                        | 757      |
| fncychap: Added. . . . .                                                    | 810       | fullwidth: Added. . . . .                                                                                    | 824      |
| grffile: Added. . . . .                                                     | 847       | midpage: Added. . . . .                                                                                      | 954      |
| metalogo: Added. . . . .                                                    | 949       | multirow: Add: New optional vpos argument. . . . .                                                           | 969      |
| nonumonpart: Added. . . . .                                                 | 992       | multirow: Add: Supports left/right border for bigdelim. . . . .                                              | 969      |
| nopageno: Added. . . . .                                                    | 992       | multirow: Fix: Long text argument. . . . .                                                                   | 969      |
| pagenote: Option page disabled. . . . .                                     | 1008      | supertabular: Added. . . . .                                                                                 | 1119     |
| realscripts: Added. . . . .                                                 | 1039      | textarea: Added. . . . .                                                                                     | 1134     |
| reysize: Added. . . . .                                                     | 1044      | titling: Improved compatibility. . . . .                                                                     | 1157     |
| romanbarpagenumber: Added. . . . .                                          | 1048      | titling: Removed extraneous center environments. . . . .                                                     | 1158     |
| romanbar: Added. . . . .                                                    | 1048      | typearea: Added. . . . .                                                                                     | 1179     |
| scaleftnt: Added. . . . .                                                   | 1050      | xtabular: Added. . . . .                                                                                     | 1220     |
| siunitx: Removed from lwarp core. . . . .                                   | 1080      | zwpagelayout: Added. . . . .                                                                                 | 1225     |
| textcomp: Removed from lwarp core. . . . .                                  | 1135      | Docs: Reorganized tabular discussion. . . . .                                                                | 166      |
| tocbibind: Added. . . . .                                                   | 1163      | Titlepage \published and \subtitle removed. \AddSubtitlePublished restores. . . . .                          | 424      |
| xltxtra: Added. . . . .                                                     | 1216      | titlepage: Clear pending footnotes. . . . .                                                                  | 419      |
| <i>lwarpmk</i> : Added <b>print1</b> and <b>html1</b> actions. . . . .      | 320       | Removed minipages. . . . .                                                                                   | 419      |
| Added \markboth, \sloppy, etc. . . . .                                      | 351       | titlingpage: Clear pending footnotes. . . . .                                                                | 1157     |
| Docs: Enhanced <i>Supported Features</i> table. . . . .                     | 66        | v0.40                                                                                                        |          |
| Docs: Index, tocbibind. . . . .                                             | 139       | \@chapcntformat: Added for tocbibind, anonchap. . . . .                                                      | 398      |
| Docs: Starred sections. . . . .                                             | 135       | \LWR@HTMLhline: Added. . . . .                                                                               | 496      |
| v0.39                                                                       |           |                                                                                                              |          |
| \@maketitle: titling version. . . . .                                       | 1160      |                                                                                                              |          |
| Native L <sup>A</sup> T <sub>E</sub> X version. . . . .                     | 423       |                                                                                                              |          |
| Removed minipages. . . . .                                                  | 423, 1160 |                                                                                                              |          |
| Supports authblk with <div>s of class oneauthor instead of tabular. . . . . | 423, 1160 |                                                                                                              |          |
| \AddSubtitlePublished: Added. . . . .                                       | 424       |                                                                                                              |          |

|                                                                                                                                                   |      |       |                                                                                                                             |     |
|---------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|-----------------------------------------------------------------------------------------------------------------------------|-----|
| <code>\LWR@nullfonts</code> : Fix: Long arguments for expandable command. . . . .                                                                 | 543  | v0.41 | <code>\LWR@addcmidruletrim</code> : Add: <code>\cmidrule</code> trims. . . . .                                              | 473 |
| <code>\LWR@restoreorigformatting</code> : Improved L <sup>A</sup> T <sub>E</sub> X logos inside a <code>lateximage</code> . . . . .               | 542  |       | <code>\LWR@clearmidrules</code> : Add: <code>\cmidrule</code> trims. . . . .                                                | 471 |
| Improved symbols inside a <code>lateximage</code> . . . . .                                                                                       | 542  |       | <code>\LWR@closetabledatacell</code> : Add: Mute > for <code>\bottomrule</code> . . . . .                                   | 447 |
| Nullified <code>\InlineClass</code> , etc. inside a <code>lateximage</code> . . . . .                                                             | 542  |       | Fix: At/bang column with <code>\multirow</code> . . . . .                                                                   | 447 |
| <code>\LWR@tabledatacolumntag</code> : Fix for <code>bigdelim</code> : <code>\ldelim</code> , <code>\rdelim</code> . . . . .                      | 492  |       | Fix: Cancel < for <code>\multicolumn</code> . . . . .                                                                       | 448 |
| <code>\chapter</code> : Added support for <code>quotchap</code> . . . . .                                                                         | 405  |       | <code>\LWR@domulticolumn</code> : Add: <code>\cmidrule</code> trims. . . . .                                                | 483 |
| <code>\multicolumnrow</code> : Fix: Adapts to older <code>multirow</code> and <code>xparse</code> . . . . .                                       | 490  |       | Added vertical rules. . . . .                                                                                               | 484 |
| <code>\simplechapterdelim</code> : Added for <code>tocbibind</code> , <code>anonchap</code> . . . . .                                             | 398  |       | <code>\LWR@nullifyNoAutoSpacing</code> : <code>babel-french</code> : Fix: <code>\NoAutoSpacing</code> in a tabular. . . . . | 497 |
| <code>\underline</code> : Added. . . . .                                                                                                          | 614  |       | <code>\LWR@parsebarcolumn</code> : Added vertical rules. . . . .                                                            | 455 |
| General: 2017/09/25 . . . . .                                                                                                                     | 1    |       | <code>\LWR@printatbang</code> : Add: <code>\cmidrule</code> trims. . . . .                                                  | 467 |
| <code>adjmulticol</code> : Added. . . . .                                                                                                         | 646  |       | Add: Mute at and bang columns for <code>\bottomrule</code> . . . . .                                                        | 467 |
| <code>anonchap</code> : Added. . . . .                                                                                                            | 661  |       | <code>\LWR@printbartag</code> : Added vertical rules. . . . .                                                               | 466 |
| <code>bigdelim</code> : Improved documentation. . . . .                                                                                           | 687  |       | <code>\LWR@subaddcmidruletrim</code> : Added. . . . .                                                                       | 473 |
| <code>cuted</code> : Added. . . . .                                                                                                               | 749  |       | <code>\LWR@subcmidrule</code> : Add: <code>\cmidrule</code> trims. . . . .                                                  | 471 |
| <code>dblfnote</code> : Added. . . . .                                                                                                            | 750  |       | <code>\LWR@tabledatasinglecolumntag</code> : Add: <code>\cmidrule</code> trims. . . . .                                     | 468 |
| <code>fnpos</code> : Added. . . . .                                                                                                               | 812  |       | Add: Mute < for <code>\bottomrule</code> . . . . .                                                                          | 468 |
| <code>graphics</code> : Add: Full <code>\graphicspath</code> support. . . . .                                                                     | 841  |       | <code>\LWR@tabularfinishrow</code> : Unfinished tabular rows automatically filled. . . . .                                  | 450 |
| <code>graphics</code> : Moved out of the <code>lwarp</code> core. . . . .                                                                         | 834  |       | <code>\mcolrowcell</code> : Added for <code>\multicolumrow</code> cells. . . . .                                            | 495 |
| <code>graphics</code> : Restores <code>\includegraphics</code> and <code>\DeclareGraphicsExtensions</code> in a <code>lateximage</code> . . . . . | 834  |       | General: 2017/10/07 . . . . .                                                                                               | 1   |
| <code>graphicx</code> : Moved out of the <code>lwarp</code> core. . . . .                                                                         | 846  |       | <code>booktabs</code> : Improved rules. . . . .                                                                             | 691 |
| <code>grffile</code> : Directly supported. . . . .                                                                                                | 847  |       | <code>multirow</code> : Add: <code>\cmidrule</code> trims. . . . .                                                          | 969 |
| <code>midfloat</code> : Added. . . . .                                                                                                            | 954  |       | Added vertical rules. . . . .                                                                                               | 969 |
| <code>multirow</code> : Improved <code>bigdelim</code> borders. . . . .                                                                           | 969  |       | Fix: < spec. . . . .                                                                                                        | 970 |
| <code>pfnote</code> : Added. . . . .                                                                                                              | 1025 |       | <code>tabular</code> : Fix: <code>\NoAutoSpacing</code> in a tabular with <code>babel-french</code> . . . . .               | 498 |
| <code>quotchap</code> : Added. . . . .                                                                                                            | 1037 | v0.42 |                                                                                                                             |     |
| <code>sectsty</code> : Added. . . . .                                                                                                             | 1061 |       | <code>\@ensuredmath</code> : Improved <code>\ensuremath</code> . . . . .                                                    | 559 |
| <code>stabular</code> : Added. . . . .                                                                                                            | 1096 |       | <code>\@textsubscript</code> : Added. . . . .                                                                               | 614 |
| <code>tabs</code> : Added. . . . .                                                                                                                | 1122 |       | <code>\@textsuperscript</code> : Added. . . . .                                                                             | 614 |
| <code>textcomp</code> : Additional symbols, improved XeLaTeX and LuaLaTeX support. . . . .                                                        | 1135 |       | <code>\LWR@HTMLhline</code> : If FormatWP force explicit border. . . . .                                                    | 496 |
| <code>tocbibind</code> : Improved for <code>\simplechapter</code> . . . . .                                                                       | 1163 |       | <code>\LWR@addformatwpalignment</code> : If FormatWP add explicit style for cell alignment. . . . .                         | 475 |
| <code>xfrac</code> : No longer preloaded. . . . .                                                                                                 | 244  |       | <code>\LWR@addrulewidth</code> : If FormatWP force explicit border. . . . .                                                 | 473 |
| <code>xltxtra</code> : Fix for <code>\showhyphens</code> with XeLaTeX. . . . .                                                                    | 1216 |       |                                                                                                                             |     |

|                                                                                                            |     |                                                                                      |      |
|------------------------------------------------------------------------------------------------------------|-----|--------------------------------------------------------------------------------------|------|
| <code>\LWR@amsmathbody</code> : Fix: Numbering and naming AMS math environments. . . . .                   | 575 | <code>epigraph</code> : If FormatWP add HTML styles. . . . .                         | 770  |
| <code>\LWR@amsmathbodynumbered</code> : Fix: Numbering and naming AMS math environments. . . . .           | 575 | <code>fancybox</code> : If FormatWP add HTML styles. . . . .                         | 782  |
| <code>\LWR@doequation</code> : If FormatWP print LaTeX expression. . . . .                                 | 564 | <code>floatflt</code> : Added width. . . . .                                         | 803  |
| <code>\LWR@domulticolumn</code> : If FormatWP add cell alignment. . . . .                                  | 485 | <code>graphics</code> : Fix: Class key. . . . .                                      | 838  |
| <code>\LWR@doubledollar</code> : If FormatWP print LaTeX expression. . . . .                               | 557 | <code>graphics</code> : Fix: Filename expansion. . . . .                             | 841  |
| Improved <code>\ensuremath</code> . . . . .                                                                | 557 | <code>graphics</code> : If FormatWP, use explicit size. . . . .                      | 839  |
| Improved line spacing with <code>mathjax</code> . . . . .                                                  | 558 | <code>keyfloat</code> : If FormatWP add explicit HTML style. . . . .                 | 881  |
| <code>\LWR@floatbegin</code> : If FormatWP add a text frame. . . . .                                       | 516 | <code>moreverb</code> : Simplified formatting of listings. . . . .                   | 961  |
| <code>\LWR@floatend</code> : If FormatWP add a text frame. . . . .                                         | 517 | <code>multirow</code> : If FormatWP add cell alignment. . . . .                      | 969  |
| <code>\LWR@remembertag</code> : Fix: Numbering and naming AMS math environments. . . . .                   | 575 | <code>overpic</code> : Added. . . . .                                                | 1007 |
| <code>\LWR@restoreorigformatting</code> : Improved <code>\ensuremath</code> . . . . .                      | 543 | <code>realscripts</code> : Fix for subscripts in a <code>lateximage</code> . . . . . | 1039 |
| <code>\LWR@subaddcmidruletrim</code> : Opt if no rule given. . . . .                                       | 473 | <code>sidenotes</code> : If FormatWP add explicit HTML style. . . . .                | 1069 |
| <code>\LWR@subsingledollar</code> : If FormatWP print LaTeX expression. . . . .                            | 556 | <code>siunitx</code> : Improved <code>\ensuremath</code> . . . . .                   | 1080 |
| <code>\LWR@tabledatasinglecolumn</code> : If FormatWP add cell alignment. . . . .                          | 469 | <code>soul</code> : If FormatWP, add explicit styles. . . . .                        | 1091 |
| <code>\LaTeX</code> : If FormatWP use explicit style. . . . .                                              | 625 | <code>textcomp</code> : Improved <code>\interrobangdown</code> . . . . .             | 1135 |
| <code>\TeX</code> : If FormatWP use explicit style. . . . .                                                | 625 | <code>wrapfig</code> : If FormatWP add explicit HTML style. . . . .                  | 1200 |
| <code>\hspace</code> : If FormatWP add <code>\quads</code> . . . . .                                       | 620 | Added boolean <code>WPMarkLOFT</code> . . . . .                                      | 260  |
| <code>\listoffigures</code> : Added boolean <code>WPMarkLOFT</code> . . . . .                              | 526 | Added boolean <code>WPMarkMath</code> . . . . .                                      | 260  |
| <code>\listoftables</code> : Added boolean <code>WPMarkLOFT</code> . . . . .                               | 526 | Added boolean <code>WPMarkMinipages</code> . . . . .                                 | 260  |
| <code>\marginpar</code> : If FormatWP emulate a <code>wrapfig</code> . . . . .                             | 378 | Added boolean <code>WPMarkTOC</code> . . . . .                                       | 260  |
| <code>\marginparBlock</code> : If FormatWP emulate a <code>wrapfig</code> . . . . .                        | 379 | Added boolean <code>WPTitleHeading</code> . . . . .                                  | 261  |
| <code>\rule</code> : If FormatWP add <code>\quads</code> . . . . .                                         | 623 | Docs: Added support page. . . . .                                                    | 2    |
| <code>\tableofcontents</code> : Added boolean <code>WPMarkTOC</code> . . . . .                             | 526 | Docs: Improper <code>\prevdepth</code> . . . . .                                     | 197  |
| <code>\underline</code> : If FormatWP, use explicit styles for <code>\underline</code> , etc. . . . .      | 614 | Docs: Reorganized math limitations . . . . .                                         | 154  |
| General: 2017/10/30 . . . . .                                                                              | 1   | File: <code>lwarp_mathjax.txt</code> : Updated <code>siunitx</code> script. . . . .  | 316  |
| <code>\textbf</code> and related: If FormatWP, use explicit styles for <code>\textsc</code> , etc. . . . . | 606 | Fix: Numbering and naming AMS math environments. . . . .                             | 574  |
| <code>algorithmicx</code> : If FormatWP add <code>\quads</code> . . . . .                                  | 651 | If FormatWP, shift section headings. . . . .                                         | 261  |
| <code>booktabs</code> : If FormatWP force explicit border. . . . .                                         | 691 | <code>tabbing</code> : Added. . . . .                                                | 431  |
|                                                                                                            |     | <code>lateximage</code> : Fix: Numbering and naming AMS math environments. . . . .   | 577  |
|                                                                                                            |     | <code>center</code> : If FormatWP use explicit <code>text-align</code> . . . . .     | 582  |
|                                                                                                            |     | <code>minipage</code> : Added boolean <code>WPMarkMinipages</code> . . . . .         | 599  |
|                                                                                                            |     | If FormatWP add a text frame. . . . .                                                | 597  |
|                                                                                                            |     | <code>eqnarray</code> : Fix: Numbering and naming AMS math environments. . . . .     | 571  |
|                                                                                                            |     | If FormatWP print LaTeX expression. . . . .                                          | 570  |
|                                                                                                            |     | <code>LWR@BlockClassWP</code> : Added to factor code. . . . .                        | 361  |

|                                                                                    |               |                                                                     |      |
|------------------------------------------------------------------------------------|---------------|---------------------------------------------------------------------|------|
| LWR@figcaption: If FormatWP forces italic captions. . . . .                        | 521           | \LWR@textcurrentcolor: xcolor: Added \LWR@textcurrentcolor. . . . . | 1205 |
| v0.43                                                                              |               | \addcontentsline: Automatic \LWR@newfloatanchor. . . . .            | 523  |
| \LWR@domulticolumn: Fix for vertical rules. . . . .                                | 484           | \chapter: Add preamble for koma-script. . . . .                     | 405  |
| Fix: Multicolumn trim. . . . .                                                     | 483, 484      | \marginparBlock: Added. . . . .                                     | 379  |
| \LWR@href: Made robust. . . . .                                                    | 513           | \nopagecolor: xcolor: Fix for \nopagecolor. . . . .                 | 1207 |
| \LWR@maybeprintpendingfootnotes: Added FootnoteDepth. . . . .                      | 378           | \part: Add preamble for koma-script. . . . .                        | 405  |
| \LWR@nolinkurl: Made robust. . . . .                                               | 513           | \title: Added \thetitle. . . . .                                    | 371  |
| \LWR@nullfonts: Fix: Nullify dollar inside filenames. . . . .                      | 543           | General: 2017/11/22 . . . . .                                       | 1    |
| \LWR@parsetablecols: Ignore spaces in col spec. . . . .                            | 460           | algorithmicx: Improved comment symbol. . . . .                      | 651  |
| \LWR@printmccoltype: Added vertical rules. . . . .                                 | 479           | atbegshi: Added. . . . .                                            | 667  |
| \LWR@section: Fix: Expansion in comparison. . . . .                                | 399           | cancel: Added. . . . .                                              | 697  |
| Fix: Math in section name. . . . .                                                 | 401, 403      | change page: Additional options. . . . .                            | 706  |
| Fix: Nullify fonts inside HTML comment. . . . .                                    | 400           | easy-todo: Added. . . . .                                           | 756  |
| \LWR@url: Made robust. . . . .                                                     | 513           | fancyref: Added. . . . .                                            | 787  |
| \TabularMacro: \newcommand instead of \relax to fix supertabular and xtab. . . . . | 491           | fixmetodonotes: Added. . . . .                                      | 800  |
| \nameref: Made robust. . . . .                                                     | 511           | fixme: Added. . . . .                                               | 799  |
| General: 2017/11/08 . . . . .                                                      | 1             | fontenc: Allowed after lwarp. . . . .                               | 814  |
| LWR@currentautosec: Added. . . . .                                                 | 399           | hang: Added. . . . .                                                | 848  |
| breakurl: Added. . . . .                                                           | 694           | ifoddpage: Added. . . . .                                           | 865  |
| hyperref: Made robust. . . . .                                                     | 859, 860, 862 | ltxtable: Added. . . . .                                            | 910  |
| hyperref: \Gauge added. . . . .                                                    | 863           | luatodonotes: Improved. . . . .                                     | 914  |
| luatodonotes: Added. . . . .                                                       | 914           | lwarp-patch-komascript: Added. . . . .                              | 1226 |
| todonotes: Added. . . . .                                                          | 1173          | overpic: Fix: Groups for lateximages. . . . .                       | 1007 |
| Added FootnoteDepth. . . . .                                                       | 374           | pdfsync: Fixes. . . . .                                             | 1022 |
| Docs: HTML settings table. . . . .                                                 | 110           | preview: Added. . . . .                                             | 1033 |
| Docs: Reorganized HTML customization. . . . .                                      | 110           | scrxend: Added. . . . .                                             | 1052 |
| v0.44                                                                              |               | scrhack: Added. . . . .                                             | 1056 |
| \@currentlabelname: Adjustment for koma-script. . . . .                            | 503           | scrlayer-notecolumn: Added. . . . .                                 | 1058 |
| \HTMLTitle: Added. . . . .                                                         | 371           | scrlayer-scrpage: Added. . . . .                                    | 1058 |
| \LWR@addformatwppalignment: Fix for multicolumn alignment if FormatWP. . . . .     | 475           | scrlayer: Added. . . . .                                            | 1056 |
| \LWR@backgroundcolor: xcolor: Added \LWR@backgroundcolor. . . . .                  | 1205          | section: Added. . . . .                                             | 1060 |
| \LWR@filestart: Add \HTMLTitle. . . . .                                            | 409           | soulpos: Added. . . . .                                             | 1092 |
| Fix \HTMLAuthor. . . . .                                                           | 408           | soulutf8: Added. . . . .                                            | 1093 |
| \LWR@listitem: Added list and trivlist. . . . .                                    | 436           | supertabular: Fix for caption. . . . .                              | 1120 |
| \LWR@patchlists: Added list and trivlist. . . . .                                  | 438           | tikz: Fix: Groups for lateximages. . . . .                          | 1149 |
| \LWR@strresult: Fix: \providecommand. . . . .                                      | 445           | tocbasic: Added. . . . .                                            | 1161 |
|                                                                                    |               | tocloft: Added \newlistentry. . . . .                               | 1170 |
|                                                                                    |               | tocloft: Improved \newlistof. . . . .                               | 1170 |
|                                                                                    |               | tocstyle: Added. . . . .                                            | 1171 |
|                                                                                    |               | todonotes: Improved. . . . .                                        | 1173 |
|                                                                                    |               | todo: Added. . . . .                                                | 1172 |
|                                                                                    |               | typearea: Added expert commands. . . . .                            | 1179 |
|                                                                                    |               | watermark: Added. . . . .                                           | 1197 |
|                                                                                    |               | xcolor: Added \LWR@currenttextcolorstyle. . . . .                   | 1204 |
|                                                                                    |               | xcolor: Added \LWR@findcurrenttextcolor. . . . .                    | 1204 |
|                                                                                    |               | xtab: Fix for caption. . . . .                                      | 1221 |

|                                                                               |     |                                                                      |          |
|-------------------------------------------------------------------------------|-----|----------------------------------------------------------------------|----------|
| Adjustment for koma-script. . . . .                                           | 219 | continue: Added. . . . .                                             | 745      |
| AMS environments: Fix: Groups for<br>lateximages. . . . .                     | 653 | endfloat: Added. . . . .                                             | 762      |
| If pdfLaTeX, require T1 and UTF-8<br>encoding. . . . .                        | 221 | fancyvrb: Improvements. . . . .                                      | 788, 789 |
| picture: overpic: Fix: Groups for<br>lateximages. . . . .                     | 594 | flafter: Added. . . . .                                              | 801      |
| list: Added list and trivlist. . . . .                                        | 436 | fltrace: Added. . . . .                                              | 809      |
| LWR@nestspan: Added list and<br>trivlist. . . . .                             | 355 | footnpag: Added. . . . .                                             | 817      |
| v0.45                                                                         |     | fwlw: Added. . . . .                                                 | 827      |
| \@currentHref: Added. . . . .                                                 | 511 | graphics: Improved URLs with<br>underscores. . . . .                 | 841      |
| \@donoparitem: Modified for HTML. . . . .                                     | 434 | hanging: Added. . . . .                                              | 849      |
| \@item: Modified for HTML. . . . .                                            | 434 | hyperref: Fix: Underscore in URL. . . . .                            | 859      |
| \@mklab: Modified for HTML. . . . .                                           | 433 | lwrap-patch-memoir: Added. . . . .                                   | 1229     |
| \CSSFilename: Improved filenames<br>with underscores. . . . .                 | 370 | memhfix: Added. . . . .                                              | 948      |
| \LWR@lwrapStart: Fix: Lateximages<br>on incorrect pages with Mathjax. . . . . | 412 | memoir: Added. . . . .                                               | 629      |
| \LWR@label@createtag: Fix: Labels<br>with underscores. . . . .                | 507 | natbib: Added. . . . .                                               | 977      |
| \LWR@newautoidanchor: Fix: No<br>anchor if frozen autoid. . . . .             | 518 | pagesel: Added. . . . .                                              | 1009     |
| \LWR@nolinkurl: Fix: Underscore in<br>URL. . . . .                            | 513 | prettyref: Added. . . . .                                            | 1032     |
| \LWR@notmemoirloadafter: Added. . . . .                                       | 207 | subfigure: Added. . . . .                                            | 1117     |
| \LWR@printpendingmpfootnotes:<br>Added. . . . .                               | 378 | subfig: Fix for subcaption end tag. . . . .                          | 1115     |
| \LWR@startref: Fix: Labels with<br>underscores. . . . .                       | 509 | subfig: Fix: Math in subcaptions. . . . .                            | 1113     |
| \LWR@subhyperref: Improved URLs<br>with underscores. . . . .                  | 512 | textfit: Added. . . . .                                              | 1138     |
| \LWR@subhyperrefclass: Improved<br>URLs with underscores. . . . .             | 512 | titleref: Added. . . . .                                             | 1153     |
| \LWR@tabledatacolumntag: Fix:<br>Empty line between rows. . . . .             | 495 | turnthepage: Added. . . . .                                          | 1177     |
| \LWR@url: Improved URLs with<br>underscores. . . . .                          | 513 | Allows memoir's preloaded<br>packages. . . . .                       | 210      |
| \chapter: Add optional heading title<br>for memoir. . . . .                   | 405 | Docs: xparse warnings. . . . .                                       | 178      |
| \newpage: Added. . . . .                                                      | 617 | Docs: Fix for double hyphens. . . . .                                | 81       |
| \normalmarginpar: Added. . . . .                                              | 379 | Docs: Improved install instructions. . . . .                         | 82       |
| \reversemarginpar: Added. . . . .                                             | 379 | Docs: Improved MiKTeX install<br>instructions. . . . .               | 78       |
| \section: Add optional heading title<br>for memoir. . . . .                   | 406 | Docs: Moved table so doesn't<br>interfere with install docs. . . . . | 77       |
| \tableofcontents: Fix: Empty<br>sitetoc. . . . .                              | 525 | File: lwrap_mathjax.txt: Allow<br>MATHJAX inside tabbing. . . . .    | 316      |
| Fix: Patch \AtBeginDocument. . . . .                                          | 525 | File: lwrap_mathjax.txt: Allow<br>MATHJAX inside verse. . . . .      | 316      |
| General: 2018/01/14 . . . . .                                                 | 1   | Fix: Empty sidetoc. . . . .                                          | 525      |
| array: Added. . . . .                                                         | 664 | Improved: Robust \,, \ , and<br>\textellipsis commands. . . . .      | 616      |
| babel-french: Robust commands. . . . .                                        | 353 | Separate LWR@thisautoidWP for<br>word processor <div>s. . . . .      | 518      |
| backref: Added. . . . .                                                       | 676 | thebibliography: Patched to<br>emphasize titles. . . . .             | 541      |
| breakurl: Fix: Underscore in URL. . . . .                                     | 694 | minipage: Fix: Improper \prevdepth. . . . .                          | 599      |
| changebar: Added. . . . .                                                     | 704 | v0.46                                                                |          |
| cite: Added. . . . .                                                          | 736 | \LWR@closeparagraph: Fix: Tabular<br>empty lines. . . . .            | 366      |
|                                                                               |     | \LWR@closeprevious: Fix: Stack<br>unnesting. . . . .                 | 351      |
|                                                                               |     | \LWR@forcenewpage: Fix: Improper<br>\prevdepth. . . . .              | 351      |
|                                                                               |     | \LWR@lookforpackagename: Fix:<br>Spaces in \usepackage. . . . .      | 248      |
|                                                                               |     | \LWR@popclose: Fix: Stack unnesting. . . . .                         | 340      |
|                                                                               |     | \LWR@providelength: Added. . . . .                                   | 223      |

|                                                                                                              |            |                                                                                            |          |
|--------------------------------------------------------------------------------------------------------------|------------|--------------------------------------------------------------------------------------------|----------|
| <code>\LWR@pushclose</code> : Fix: Stack unnesting. . . . .                                                  | 339        | <code>adjmulticol</code> : Fix: Line wrap at HTML hyphen. . . . .                          | 646      |
| <code>\LWR@PrintStack</code> : Name changed from <code>\PrintStack</code> . . . . .                          | 350        | <code>blowup</code> : Added. . . . .                                                       | 689      |
| General: 2018/01/23 . . . . .                                                                                | 1          | <code>caption</code> : Added. . . . .                                                      | 699      |
| <code>LWR@tabularpardepth</code> added. . . . .                                                              | 445        | <code>changeage</code> : Fix for pagecheck macros. . . . .                                 | 706      |
| <code>amsthm</code> : Adapted to trivlist changes. . . . .                                                   | 659        | <code>endheads</code> : Added. . . . .                                                     | 763      |
| <code>mdframed</code> : Fixes for SVG math or <code>lateximage</code> in title. . . . .                      | 940        | <code>epigraph</code> : Fix: Line wrap at HTML hyphen. . . . .                             | 770      |
| <code>mdframed</code> : Fixes for footnotes. . . . .                                                         | 941        | <code>hanging</code> : Fix: Line wrap at HTML hyphen. . . . .                              | 850      |
| <code>ntheorem</code> : Adapted to trivlist changes. . . . .                                                 | 994        | <code>hang</code> : Fix: Line wrap at HTML hyphen. . . . .                                 | 848      |
| <code>theorem</code> : Adapt to trivlist changes. . . . .                                                    | 1141, 1142 | <code>keyfloat</code> : Fix for SVG math in captions. . . . .                              | 878      |
| <code>tabular</code> : Fix: Tabular empty lines. . . . .                                                     | 500, 501   | <code>midpage</code> : Fix: Line wrap at HTML hyphen. . . . .                              | 954      |
| <code>list</code> : Fix: Stack unnesting. . . . .                                                            | 436        | <code>multirow</code> : Fix: Line wrap at HTML hyphen. . . . .                             | 969      |
| v0.47                                                                                                        |            | <code>multitoc</code> : Added. . . . .                                                     | 971      |
| <code>\LWR@HTML@caption@begin</code> : Fix: Argument passed to <code>\LWR@origcaption@begin</code> . . . . . | 521        | <code>ntheorem</code> : Fix: Line wrap at HTML hyphen. . . . .                             | 999      |
| <code>\LWR@LwarpStart</code> : Fix for SVG math in <code>\nameref</code> . . . . .                           | 413        | <code>realscripts</code> : Fix: Line wrap at HTML hyphen. . . . .                          | 1039     |
| <code>\LWR@WPcell</code> : Fix: Line wrap at HTML hyphen. . . . .                                            | 475        | <code>scrextend</code> : Fix: Line wrap at HTML hyphen. . . . .                            | 1052     |
| <code>\LWR@createautosec</code> : Fix: Line wrap at HTML hyphen. . . . .                                     | 397        | <code>sectionbreak</code> : Added. . . . .                                                 | 1061     |
| <code>\LWR@domulticolumn</code> : Fix: Line wrap at HTML hyphen. . . . .                                     | 485        | <code>sidenotes</code> : Fix for SVG math in captions. . . . .                             | 1069     |
| <code>\LWR@floatbegin</code> : Fix: Line wrap at HTML hyphen. . . . .                                        | 516        | <code>subfig</code> : Fix for SVG math in captions. . . . .                                | 1113     |
| <code>\LWR@htmlclosecomment</code> : Add <code>\mbox</code> to prevent line breaks. . . . .                  | 357        | <code>subfig</code> : Fix: Support <code>\nameref</code> . . . . .                         | 1113     |
| <code>\LWR@label@createtag</code> : Fix: Line wrap at HTML hyphen. . . . .                                   | 507        | <code>xurl</code> : Added. . . . .                                                         | 1223     |
| <code>\LWR@newautoidanchor</code> : Fix: Line wrap at HTML hyphen. . . . .                                   | 518        | <i>lwarpmk</i> : <i>pdfcrop</i> : Removed hires option for improved crop accuracy. . . . . | 320      |
| <code>\LWR@printopenlist</code> : Fix: Line wrap at HTML hyphen. . . . .                                     | 433        | <code>lateximage</code> : Added CSS style option. . . . .                                  | 577      |
| <code>\LWR@startref</code> : Fix: Line wrap at HTML hyphen. . . . .                                          | 508        | Fix: Line wrap at HTML hyphen. . . . .                                                     | 581      |
| <code>\LWR@subsingledollar</code> : Added SVG math image baseline adjust and em sizing. . . . .              | 556        | <code>center</code> : Fix: Line wrap at HTML hyphen. . . . .                               | 582      |
| <code>\LWR@subsingledollarsvg</code> : Fix: Line wrap at HTML hyphen. . . . .                                | 553        | <code>minipage</code> : Fix: Line wrap at HTML hyphen. . . . .                             | 597, 598 |
| <code>\captionlistentry</code> : Fix: Line wrap at HTML hyphen. . . . .                                      | 522        | <code>flushleft</code> : Fix: Line wrap at HTML hyphen. . . . .                            | 583      |
| <code>\hypertoc</code> : Fix: Line wrap at HTML hyphen. . . . .                                              | 529        | <code>flushright</code> : Fix: Line wrap at HTML hyphen. . . . .                           | 582      |
| <code>\hypertocfloat</code> : Fix: Line wrap at HTML hyphen. . . . .                                         | 531        | <code>enumerate</code> : Fix: Line wrap at HTML hyphen. . . . .                            | 437      |
| General: 2018/01/30 . . . . .                                                                                | 1          | <code>itemize</code> : Fix: Line wrap at HTML hyphen. . . . .                              | 437      |
|                                                                                                              |            | <code>LWR@BlockClassWP</code> : Fix: Line wrap at HTML hyphen. . . . .                     | 361      |
|                                                                                                              |            | v0.48                                                                                      |          |
|                                                                                                              |            | <code>\@@@setcpageref</code> : Fix for new v0.21 of <code>cleveref</code> . . . . .        | 739      |

|                                                                                                                           |               |                                                                                                                       |          |
|---------------------------------------------------------------------------------------------------------------------------|---------------|-----------------------------------------------------------------------------------------------------------------------|----------|
| <code>\@@@setcref</code> : Fix for new v0.21 of <code>cleveref</code> . . . . .                                           | 738           | <code>graphics</code> : Fix: Virtual page size limited to a group. . . . .                                            | 841, 843 |
| <code>\@@@setcrefrange</code> : Fix for new v0.21 of <code>cleveref</code> . . . . .                                      | 739           | <code>hyccap</code> : Added. . . . .                                                                                  | 853      |
| <code>\@biblabel</code> : Improved bibliography label. . . . .                                                            | 541           | <code>hypernat</code> : Added. . . . .                                                                                | 854      |
| <code>\@item</code> : Honors <code>\makelabel</code> . . . . .                                                            | 434           | <code>hyperref</code> : <code>\texorpdfstring</code> now uses the TeX string. . . . .                                 | 862      |
| <code>\@maketitle</code> : Fix: Errors with IEEEtran class. . . . .                                                       | 423           | <code>luatodonotes</code> : Improved <code>\todotoc</code> . . . . .                                                  | 914      |
| <code>\LWR@LwarpStart</code> : Adjusted space around captions. . . . .                                                    | 412           | <code>siunitx</code> : Changes fraction to symbol. . . . .                                                            | 1083     |
| <code>\LWR@ProvidesPackageDropB</code> : Fix: Options with braces. . . . .                                                | 250           | <code>siunitx</code> : Improved svg math. 1080, 1082                                                                  |          |
| <code>\LWR@addtabularhrulecolor</code> : <code>colortbl</code> : Added. . . . .                                           | 476           | <code>siunitx</code> : Improved color output. 1080                                                                    |          |
| <code>\LWR@addtabularrulecolors</code> : <code>colortbl</code> : Added. . . . .                                           | 477           | <code>stfloats</code> : Added. . . . .                                                                                | 1111     |
| <code>\LWR@closetabledatcell</code> : <code>colortbl</code> : Added. . . . .                                              | 448           | <code>todonotes</code> : Improved <code>\todotoc</code> . . . . .                                                     | 1173     |
| <code>\LWR@lookforpackagename</code> : Fix: Parsing similar package names. . . . .                                        | 247           | <code>vmargin</code> : Added. . . . .                                                                                 | 1193     |
| <code>\LWR@newautopagelabel</code> : Fix: TOC, LOF, LOT links. . . . .                                                    | 385           | <code>xfrac</code> : Fix: Added groups around super/subscripts to localize <code>LWR@nestspan</code> changes. . . . . | 1214     |
| <code>\LWR@newhtmlfile</code> : Fix: TOC, LOF, LOT links. . . . .                                                         | 394           | Docs: Converting an existing document. . . . .                                                                        | 98       |
| <code>\LWR@nullfont</code> : Fix: <code>\newline</code> in title. . . . .                                                 | 543           | Improved font control. . . . .                                                                                        | 610      |
| <code>\LWR@parsedrequirepackagenames</code> : Fix: Parsing similar package names. . . . .                                 | 245           | <code>tabular</code> : <code>colortbl</code> : Added. . . . .                                                         | 499      |
| <code>\LWR@parsetablecols</code> : Fix: Ignore optional tabular column arguments. . . . .                                 | 463           | <code>lateximage</code> : Print mode boxed to natural width. . . . .                                                  | 582      |
| <code>\LWR@restoreorigformatting</code> : Fix: Spacing in svg math, <code>lateximage</code> , <code>Tikz</code> . . . . . | 542           | <code>abstract</code> : Allow optional name. . . . .                                                                  | 425      |
| <code>\LWR@section</code> : Fix: TOC, LOF, LOT links. . . . .                                                             | 403           | v0.49                                                                                                                 |          |
| <code>\LWR@tabledatasingletag</code> : <code>colortbl</code> : Added. . . . .                                             | 469           | <code>\LWR@addtabularcellcolor</code> : <code>xcolor</code> : Added tabular row colors. . . . .                       | 478      |
| <code>\LWR@textcurrentfont</code> : Added. Improves font control. . . . .                                                 | 610           | <code>\LWR@domulticolumn</code> : <code>xcolor</code> : Added tabular row colors. . . . .                             | 485      |
| <code>\centerline</code> : Added. . . . .                                                                                 | 584           | <code>\LWR@href</code> : Fix: Adapt to classes. . . . .                                                               | 513      |
| <code>\l@part</code> : Adapts to classes without <code>\part</code> . . . . .                                             | 531           | <code>\LWR@printlength</code> : Fix: Group <code>printlen</code> changes. . . . .                                     | 244      |
| <code>\leftline</code> : Added. . . . .                                                                                   | 584           | <code>\LWR@url</code> : Fix: Adapt to classes. . . . .                                                                | 513      |
| <code>\mbox</code> : Nullified for HTML. . . . .                                                                          | 600           | <code>\affiliation</code> : Fix: Adapts to classes which already provide. . . . .                                     | 418      |
| <code>\rightline</code> : Added. . . . .                                                                                  | 584           | <code>\noalign</code> : Fix: <code>\noalign</code> inside <code>tabular</code> . . . . .                              | 496      |
| <code>\thempfootnote</code> : Removed <code>\itshape</code> . . . . .                                                     | 377           | General: 2018/02/19 . . . . .                                                                                         | 1        |
| General: 2018/02/14 . . . . .                                                                                             | 1             | <code>amsmath</code> : Fix: Patches for <code>\eqref</code> . . . . .                                                 | 653      |
| <code>acronym</code> : Added. . . . .                                                                                     | 645           | <code>eso-pic</code> : Fix for <code>\AddToShipoutPicture</code> . . . . .                                            | 776      |
| <code>acro</code> : Added. . . . .                                                                                        | 642           | <code>figsize</code> : Added. . . . .                                                                                 | 797      |
| <code>chapterbib</code> : Added. . . . .                                                                                  | 709           | <code>fnlineno</code> : Added. . . . .                                                                                | 811      |
| <code>colortbl</code> : Added. . . . .                                                                                    | 464, 475, 743 | <code>hypdestopt</code> : Added. . . . .                                                                              | 853      |
| <code>fancyref</code> : Now directly supported. . . . .                                                                   | 787           | <code>hyphenat</code> : Added. . . . .                                                                                | 864      |
|                                                                                                                           |               | <code>lineno</code> : Added. . . . .                                                                                  | 898      |
|                                                                                                                           |               | <code>luacolor</code> : Added. . . . .                                                                                | 911      |
|                                                                                                                           |               | <code>pagegrid</code> : Added. . . . .                                                                                | 1008     |
|                                                                                                                           |               | <code>pdfrender</code> : Added. . . . .                                                                               | 1022     |
|                                                                                                                           |               | <code>resizegather</code> : Added. . . . .                                                                            | 1046     |
|                                                                                                                           |               | <code>vertbars</code> : Added. . . . .                                                                                | 1193     |
|                                                                                                                           |               | <code>vwcol</code> : Added. . . . .                                                                                   | 1195     |

|                                                                                              |                 |  |  |
|----------------------------------------------------------------------------------------------|-----------------|--|--|
| xcolor: Added tabular row colors. . . . .                                                    | 464, 1210       |  |  |
| Fix: Adapt to classes. . . . .                                                               | 616             |  |  |
| v0.50                                                                                        |                 |  |  |
| \@ensuredmath: Fix: Use lateximage even if MathJax. . . . .                                  | 559             |  |  |
| Improved svg math alt tags. . . . .                                                          | 559             |  |  |
| \LWR@footnotetext: Robustify macros. . . . .                                                 | 375             |  |  |
| \LWR@atbeginverbatim: Improved column alignment. . . . .                                     | 430             |  |  |
| \LWR@doequation: Improved svg math display. . . . .                                          | 565             |  |  |
| \LWR@doubledollar: Improved svg math alt tags. . . . .                                       | 558             |  |  |
| Improved svg math display. . . . .                                                           | 558             |  |  |
| \LWR@htmlrefsectionfilename: Fix: SVG math in a section name. . . . .                        | 347             |  |  |
| \LWR@newhtmlfile: Fix: SVG math in a section name. . . . .                                   | 393             |  |  |
| \LWR@nullfonts: Fix: \underline in sectioning file name. . . . .                             | 546             |  |  |
| \LWR@overline: Added. . . . .                                                                | 614             |  |  |
| \LWR@subsingledollar: Fix: Use lateximage even if MathJax. . . . .                           | 556             |  |  |
| Improved svg math alt tags. . . . .                                                          | 556             |  |  |
| \LWR@subsingledollarsvg: MD5 hash avoids duplicate svg math. . . . .                         | 554             |  |  |
| \LWR@vspace: Robustify macros. . . . .                                                       | 621             |  |  |
| \newline: Robustify macros. . . . .                                                          | 617             |  |  |
| \textsubscript: Robustify macros. . . . .                                                    | 614             |  |  |
| \textsuperscript: Robustify macros. . . . .                                                  | 614             |  |  |
| General: 2018/03/03 . . . . .                                                                | 1               |  |  |
| lwarp.css: Improved svg display math centering. . . . .                                      | 273             |  |  |
| lwarp_one_limage.txt: Added. . . . .                                                         | 315             |  |  |
| amsmath: Fix: Upright tags for svgmath. . . . .                                              | 653             |  |  |
| axodraw2: Added. . . . .                                                                     | 676             |  |  |
| bytefield: Added. . . . .                                                                    | 697             |  |  |
| dblfloatfix: Added. . . . .                                                                  | 750             |  |  |
| diagbox: Added. . . . .                                                                      | 751             |  |  |
| epstopdf: Added. . . . .                                                                     | 771             |  |  |
| listings: Force flexible columns. . . . .                                                    | 900             |  |  |
| morefloats: Added. . . . .                                                                   | 960             |  |  |
| nonfloat: Added. . . . .                                                                     | 992             |  |  |
| ntheorem: Fix: Not standard nor amsthm selected. . . . .                                     | 1001            |  |  |
| pbox: Added. . . . .                                                                         | 1015            |  |  |
| phfqit: Added. . . . .                                                                       | 1025            |  |  |
| schemata: Added. . . . .                                                                     | 1051            |  |  |
| siunitx: Fix: Loads xcolor. . . . .                                                          | 1080            |  |  |
| siunitx: Improved svg math alt tags. . . . .                                                 | 1082            |  |  |
| siunitx: Improved units. . . . .                                                             | 587, 1080, 1083 |  |  |
| xy: Added. . . . .                                                                           | 1223            |  |  |
| lwarpmk: Error if lateximages.txt does not exist. . . . .                                    | 320             |  |  |
| lwarpmk: Error if lwarpmk.conf points to lwarp. . . . .                                      | 320             |  |  |
| lwarpmk: Improved error messages. . . . .                                                    | 320             |  |  |
| lwarpmk: MD5 hash avoids duplicate svg math. . . . .                                         | 320             |  |  |
| lwarpmk: Multiprocess support making lateximages. . . . .                                    | 320             |  |  |
| AMS environments: Improved svg math display. . . . .                                         | 653             |  |  |
| Fix: Load fontspec if necessary. . . . .                                                     | 239             |  |  |
| Robustify macros. . . . .                                                                    | 610             |  |  |
| lateximage: Fix: SVG math in a section name. . . . .                                         | 580             |  |  |
| MD5 hash avoids duplicate svg math. . . . .                                                  | 578, 581        |  |  |
| eqnarray: Improved svg math display. . . . .                                                 | 571             |  |  |
| v0.51                                                                                        |                 |  |  |
| \@ensuredmath: Hashes \ensuremath. . . . .                                                   | 559             |  |  |
| \@item: Restored list label space. . . . .                                                   | 435             |  |  |
| \LWR@HTMLsanitizeexpand: Fix: Escapes double quotes. . . . .                                 | 387             |  |  |
| \LWR@LwarpStart: MathJax: Nullifies \ensuremath. . . . .                                     | 413             |  |  |
| \LWR@addbaselinemarker: Improved svg math baseline. . . . .                                  | 549             |  |  |
| \LWR@atbeginverbatim: Adds vertical offset. . . . .                                          | 429             |  |  |
| \LWR@doequation: Fix: \addcontentsline inside svg math. Provides an autoid anchor. . . . .   | 565             |  |  |
| \LWR@doubledollar: Fix: \addcontentsline inside svg math. Provides an autoid anchor. . . . . | 558             |  |  |
| \LWR@findcurrenttextcolor: Added \LWR@findcurrenttextcolor when no xcolor. . . . .           | 615             |  |  |
| \LWR@newautoidanchor: Fix: No autoid is inside a lateximage. . . . .                         | 518             |  |  |
| \LWR@singledollarmeasure: Fix: lateximage inside $\text{. . . . .}$                          | 551             |  |  |
| Fix: Honors text font around svg math. . . . .                                               | 551             |  |  |
| Improved svg math baseline. . . . .                                                          | 552             |  |  |
| Typeset svg math only once during measurement. . . . .                                       | 551             |  |  |
| \LWR@subHTMLsanitize: Fix: Escapes double quotes. . . . .                                    | 386             |  |  |
| \LWR@subsingledollar: Fix: \ensuredmath inside svg image. . . . .                            | 556             |  |  |

|                                                                                                                                          |      |                                                                                                                                                           |     |
|------------------------------------------------------------------------------------------------------------------------------------------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| <code>\LWR@subsingledollarsvg</code> : Fix: SVG math with enclosed <code>lateximage</code> . . . . .                                     | 553  | Fix: <code>lateximage</code> inside $\mathcal{AMS}$ <code>\text</code> . . . . .                                                                          | 577 |
| SVG math baseline improved with invisible rule at corner. . . . .                                                                        | 555  | Processing for complicated display math. . . . .                                                                                                          | 580 |
| <code>\LWR@textcurrentcolor</code> : <code>xcolor</code> : <code>\LWR@textcurrentcolor</code> if <code>xcolor</code> not loaded. . . . . | 615  | <code>alignat</code> : <code>amsmath</code> : Fix: Added. . . . .                                                                                         | 656 |
| <code>\addcontentsline</code> : Add missing support for float mechanism if necessary. . . . .                                            | 523  | <code>eqnarray</code> : Fix: <code>\addcontentsline</code> inside svg math. Provides an autoid anchor. . . . .                                            | 571 |
| No anchor ID if inside svg image. . . . .                                                                                                | 523  | <code>LWR@displaymathother</code> : Processing for complicated display math. . . . .                                                                      | 560 |
| <code>\displaymathnormal</code> : Processing for complicated display math. . . . .                                                       | 568  | <code>LWR@equationother</code> : Processing for complicated display math. . . . .                                                                         | 561 |
| <code>\displaymathother</code> : Processing for complicated display math. . . . .                                                        | 568  | v0.52                                                                                                                                                     |     |
| General: 2018/03/24 . . . . .                                                                                                            | 1    | <code>\@ensuredmath</code> : Improved hashing expansion. . . . .                                                                                          | 559 |
| <code>MATHJAX</code> : Nullifies <code>\ensuremath</code> . . . . .                                                                      | 389  | <code>\@mpfootnotetext</code> : Fix: Paragraph handling. . . . .                                                                                          | 377 |
| <code>lwarp_one_limage.txt</code> : <i>pdftocairo</i> -noshrink added. . . . .                                                           | 315  | <code>\CustomizeMathJax</code> : Added. . . . .                                                                                                           | 388 |
| <code>afterpackage</code> : No longer required. . . . .                                                                                  | 242  | <code>\LWR@@footnotetext</code> : Fix: Paragraph handling. . . . .                                                                                        | 376 |
| <code>chemfig</code> : Added. . . . .                                                                                                    | 709  | <code>\LWR@addbaselinemarker</code> : Warnings if <code>lwarp_baseLine_marker.png</code> is not present or if <code>graphicx/s</code> not loaded. . . . . | 549 |
| <code>chemformula</code> : Added. . . . .                                                                                                | 711  | <code>\LWR@customizedMathJax</code> : Added. . . . .                                                                                                      | 388 |
| <code>chemgreek</code> : Added. . . . .                                                                                                  | 717  | <code>\LWR@doequation</code> : Fix: <code>equation*</code> now based on equation instead of <code>displaymath</code> . . . . .                            | 565 |
| <code>chemmacros</code> : Added. . . . .                                                                                                 | 717  | Fix: <code>equation*</code> with <code>split</code> . . . . .                                                                                             | 564 |
| <code>chemnum</code> : Added. . . . .                                                                                                    | 735  | <code>\LWR@filenamenoblanks</code> : Fix: <code>\FileDepth</code> with non-utf8 encoding. . . . .                                                         | 384 |
| <code>epstopdf-base</code> : Added. . . . .                                                                                              | 772  | <code>\LWR@href</code> : Fix: <code>#, %, &amp;, ~, _</code> in URL. . . . .                                                                              | 513 |
| <code>fancybox</code> : Fix: Optional tag for <code>\item</code> in a span. . . . .                                                      | 785  | <code>\LWR@nolinkurl</code> : Fix: <code>#, %, &amp;, ~, _</code> in URL. . . . .                                                                         | 513 |
| <code>grid</code> : Added. . . . .                                                                                                       | 847  | <code>\LWR@nullfonts</code> : Fix: <code>\texorpdfstring</code> in section names. . . . .                                                                 | 546 |
| <code>listings</code> : Forces cleared options. . . . .                                                                                  | 901  | <code>\LWR@section</code> : Fix: Footnote numbering: Limited HTML comment if starred. . . . .                                                             | 400 |
| <code>ltxgrid</code> : Added. . . . .                                                                                                    | 910  | Fix: Footnote numbering: Use short roc entry for <code>HTMLDebug</code> comments. . . . .                                                                 | 400 |
| <code>mhchem</code> : Added. . . . .                                                                                                     | 951  | <code>\LWR@singledollarmeasure</code> : Added user-adjustable svg math font scaling. . . . .                                                              | 552 |
| <code>tikz</code> : Fix for <code>\tikz</code> macro. . . . .                                                                            | 1149 | <code>\LWR@url</code> : Fix: <code>#, %, &amp;, ~, _</code> in URL. . . . .                                                                               | 513 |
| <code>tikz</code> : Fix for <code>tikz</code> with optional argument. . . . .                                                            | 1149 | <code>\LateximageFontScale</code> : Added user-adjustable svg math font scaling. . . . .                                                                  | 574 |
| <code>titling</code> : Fix for <code>\thanks</code> mark. . . . .                                                                        | 1159 | <code>\theHTMLTitleSeparator</code> : Fix: <code>\FileDepth</code> with non-utf8 encoding. . . . .                                                        | 407 |
| <i>lwarpmk</i> : <i>pdfcrop</i> : Restored hires option. . . . .                                                                         | 320  | General: 2018/04/01 . . . . .                                                                                                                             | 1   |
| <i>lwarpmk</i> : <i>pdftocairo</i> -noshrink added. . . . .                                                                              | 320  |                                                                                                                                                           |     |
| AMS environments: Fix: <code>\addcontentsline</code> inside svg math. Provides an autoid anchor. . . . .                                 | 653  |                                                                                                                                                           |     |
| Docs: <code>tikz</code> limitations. . . . .                                                                                             | 163  |                                                                                                                                                           |     |
| Docs: Multiple authors and affiliations. . . . .                                                                                         | 135  |                                                                                                                                                           |     |
| Docs: Things to avoid. . . . .                                                                                                           | 123  |                                                                                                                                                           |     |
| Docs: Updated Converting an existing document. . . . .                                                                                   | 98   |                                                                                                                                                           |     |
| Fix: Remember original <code>\#</code> in case is redefined. . . . .                                                                     | 262  |                                                                                                                                                           |     |
| Named HTML entity used for text dollar. . . . .                                                                                          | 549  |                                                                                                                                                           |     |
| <code>lateximage</code> : Added additional hashing option. . . . .                                                                       | 577  |                                                                                                                                                           |     |

|                                              |          |                                               |          |
|----------------------------------------------|----------|-----------------------------------------------|----------|
| breakurl: Fix: #, %, &, ~, _ in URL. . . . . | 694      | General: 2018/04/22 . . . . .                 | 1        |
| endfloat: Updated for v2.6. . . . .          | 762      | *.lwarpmkconf: Option                         |          |
| fancyvrb: Initial support for                |          | IndexLanguage changed to                      |          |
| \VerbatimFootnotes. . . . .                  | 782, 788 | xindyLanguage. . . . .                        | 273      |
| graphics: Added defaults. . . . .            | 836, 837 | *.lwarpmkconf: Option                         |          |
| graphics: Updated for v1.1a. . . . .         | 837      | pdftotextEnc added. . . . .                   | 273      |
| graphics: Updated for v1.1b. . . . .         | 837      | *.lwarpmkconf: Option                         |          |
| hyperref: Fix: #, %, &, ~, _ in              |          | xdyFilename changed to                        |          |
| URL. . . . .                                 | 859, 861 | xindyStyle. . . . .                           | 273      |
| nicefrac: Added. . . . .                     | 990      | *.lwarpmkconf: Option                         |          |
| url: Added. . . . .                          | 1190     | xindyCodepage added. . . . .                  | 273      |
| <i>lwarpmk</i> : Fix: Memory overflow        |          | lwarpmk.css: Fix:                             |          |
| when spawning tasks. . . . .                 | 320      | Text-decoration-skip: auto. . . . .           | 273      |
| <i>lwarpmk</i> : Fix: Skip image             |          | lwarpmk.conf: Option                          |          |
| generation if from page 0. . . . .           | 320      | IndexLanguage changed to                      |          |
| Changed FootnoteDepth default to             |          | xindyLanguage. . . . .                        | 273      |
| \subsubsection. . . . .                      | 374      | lwarpmk.conf: Option                          |          |
| Docs: Improved install instructions. . . . . | 79       | pdftotextEnc added. . . . .                   | 273      |
| Fix: MathJax script line wraps.              |          | lwarpmk.conf: Option                          |          |
| Reduced right margin. . . . .                | 240      | xdyFilename changed to                        |          |
| If pdfLaTeX, allow other input               |          | xindyStyle. . . . .                           | 273      |
| encoding. . . . .                            | 221      | lwarpmk.conf: Option                          |          |
| Restore \kill in a lateximage. . . . .       | 909      | xindyCodepage added. . . . .                  | 273      |
| tabbing: Fix to allow inside                 |          | bibunits: Added. . . . .                      | 686      |
| lateximage. . . . .                          | 431      | chnpage: Added. . . . .                       | 736      |
| lateximage: Fix for hash expansion. . . . .  | 578      | forest: Added. . . . .                        | 818      |
| v0.53                                        |          | glossaries: Fix when not using                |          |
| General: 2018/04/01 . . . . .                | 1        | babel or polyglossia. . . . .                 | 833      |
| <i>lwarpmk</i> : Added                       |          | gridset: Added. . . . .                       | 847      |
| <i>lwarpmk cleanimages</i> . . . . .         | 320      | hyperref: Fix: \hyperref and                  |          |
| <i>lwarpmk</i> : Added warning for           |          | \hyperlink with special chars in              |          |
| corrupted images. . . . .                    | 320      | text. . . . .                                 | 860, 861 |
| Docs: <i>lwarpmk cleanimages</i> . . . . .   | 95       | hyperref: Fix: \ref in \hyperref              |          |
| Docs: <i>lwarpmk pdftohtml</i> . . . . .     | 95       | and \hyperlink caused nested                  |          |
| v0.54                                        |          | link. . . . .                                 | 860, 861 |
| \@xdlbfloat: Honor \centering, etc.          |          | lwarpmk: Update for                           |          |
| in floats. . . . .                           | 517      | v3.7g. . . . .                                | 1234     |
| \LWR@afterendverbatim: Added                 |          | magaz: Added. . . . .                         | 918      |
| vspace argument. . . . .                     | 430      | ragged2e: Fix: \centering, etc. . . . .       | 1039     |
| \LWR@atbeginverbatim: Improved               |          | textcomp: Fix for                             |          |
| column alignment. . . . .                    | 430      | \textperthousand. . . . .                     | 1135     |
| \LWR@earlyloadnever: Added. . . . .          | 209      | tikz: Fixes for \pgfpicture,                  |          |
| \LWR@endfloatalignment: Honor                |          | minipages, fit, align, font. . . . .          | 1149     |
| \centering, etc. in floats. . . . .          | 519      | <i>lwarpmk</i> : Added pdftotextenc. . . . .  | 320      |
| \LWR@floatalignment: Honor                   |          | <i>lwarpmk</i> : Added xindycodepage. . . . . | 320      |
| \centering, etc. in floats. . . . .          | 519      | <i>lwarpmk</i> : Changed language to          |          |
| \LWR@floatend: Honor \centering,             |          | xindyLanguage. . . . .                        | 320      |
| etc. in floats. . . . .                      | 517      | <i>lwarpmk</i> : Changed xdyfile to           |          |
| \LateximageFontSizeName: Defaults            |          | xindystyle. . . . .                           | 320      |
| to normalsize. . . . .                       | 574      | <i>lwarpmk</i> : Improved error if            |          |
| \centering: Added debug comment. . . . .     | 583      | configuration file does not exist. . . . .    | 320      |
| \raggedleft: Added debug                     |          | <i>lwarpmk</i> : Increased prominence for     |          |
| comment. . . . .                             | 583      | error for an unknown command. . . . .         | 320      |
| \raggedright: Added debug                    |          | <i>lwarpmk</i> : Verifies HTML version        |          |
| comment. . . . .                             | 583      | exists before lwarpmk limages. . . . .        | 320      |

|                                                                                                                            |           |
|----------------------------------------------------------------------------------------------------------------------------|-----------|
| <i>lwarpmk</i> : Verifies image references                                                                                 |           |
| before <code>lwarpmk</code> <code>limages</code> . . . . .                                                                 | 320       |
| Add: <code>pdftotextEnc</code> . . . . .                                                                                   | 232       |
| Add: <code>xindyCodepage</code> . . . . .                                                                                  | 232       |
| Added early check for disallowed packages. . . . .                                                                         | 209       |
| Docs: BibTeX. . . . .                                                                                                      | 137       |
| Docs: Macros in sectioning names. . . . .                                                                                  | 123       |
| Never load <code>aecompl</code> . . . . .                                                                                  | 209       |
| Option <code>IndexLanguage</code> changed to <code>xindyLanguage</code> . . . . .                                          | 232       |
| Option <code>xdyFilename</code> changed to <code>xindyStyle</code> . . . . .                                               | 232       |
| verse: Fix: Line spacing. . . . .                                                                                          | 428       |
| v0.55                                                                                                                      |           |
| <code>\@xdlbfloat</code> : Fix: Float optional args. . . . .                                                               | 517       |
| <code>\LWR@LwarpStart</code> : Fix: Overfull boxes in <code>lateximages</code> . . . . .                                   | 411       |
| <code>\LWR@nullfonts</code> : Removed extraneous space which appeared in file links. . . . .                               | 546       |
| <code>\LWR@phantomsection</code> : Fix: <code>\ForceHTMLTOC</code> with <code>\phantomsection</code> . . . . .             | 624       |
| General: 2018/04/26 . . . . .                                                                                              | 1         |
| <code>clrdblpg</code> : Added. . . . .                                                                                     | 741       |
| Fix: <code>\centering</code> , etc. for <code>koma-script</code> . . . . .                                                 | 516       |
| Fix: QED symbols in <code>lateximage</code> . . . . .                                                                      | 660, 1006 |
| v0.56                                                                                                                      |           |
| <code>\LWR@addcdashline</code> : <code>arydshln</code> : Added. . . . .                                                    | 474       |
| <code>\LWR@addmulticolvertulecolor</code> : Adds support for dashed vertical rules. . . . .                                | 482       |
| Adds support for double vertical rules. . . . .                                                                            | 482       |
| <code>\LWR@addtabularhrulecolor</code> : Adds support for <code>arydshln</code> dashed rules. . . . .                      | 476       |
| Adds support for double <code>\hlines</code> and <code>\midrules</code> . . . . .                                          | 476       |
| <code>\LWR@addtabularrulecolors</code> : Adds support for dashed vertical rules. . . . .                                   | 477       |
| Adds support for double vertical rules. . . . .                                                                            | 477       |
| <code>\LWR@closeparagraph</code> : Added support for <code>parnotes</code> . . . . .                                       | 366       |
| <code>\LWR@domulticolumn</code> : Adds support for dashed vertical rules. . . . .                                          | 484       |
| Adds support for double vertical rules. . . . .                                                                            | 484       |
| <code>\LWR@floatbegin</code> : Adds a <code>&lt;class&gt;</code> per float package style. . . . .                          | 516       |
| <code>\LWR@multicolparttext</code> : Fix: <code>\multicolumn</code> parameters. . . . .                                    | 480       |
| <code>\LWR@openparagraph</code> : Added support for <code>parnotes</code> . . . . .                                        | 364       |
| <code>\LWR@parsebarcolumn</code> : Adds support for double vertical rules. . . . .                                         | 455       |
| <code>\LWR@parsecoloncolumn</code> : <code>arydshln</code> : Added. . . . .                                                | 456       |
| <code>\LWR@parsesemicoloncolumn</code> : <code>arydshln</code> : Added. . . . .                                            | 456       |
| <code>\LWR@parsetablecols</code> : Added array <code>W</code> column. . . . .                                              | 463       |
| <code>\LWR@printmccoldata</code> : Added array <code>W</code> column. . . . .                                              | 481       |
| Fix: <code>\multicolumn</code> parameters. . . . .                                                                         | 481       |
| <code>\LWR@printmccoltype</code> : Added array <code>W</code> column. . . . .                                              | 479       |
| Adds support for dashed vertical rules. . . . .                                                                            | 479       |
| Adds support for double vertical rules. . . . .                                                                            | 479       |
| <code>\LWR@tabledatacolumnntag</code> : Fix: <code>\morecmidrules</code> . . . . .                                         | 494       |
| <code>\LWR@textcurrentfont</code> : Added <code>span.textbf</code> , etc. . . . .                                          | 610       |
| General: 2018/05/12 . . . . .                                                                                              | 1         |
| <code>*.lwarpmkconf</code> : Records                                                                                       |           |
| <code>--shell-escape</code> . . . . .                                                                                      | 273       |
| <code>lwarp.css</code> : Added <code>div.textbf</code> , etc. . . . .                                                      | 273       |
| <code>lwarp.css</code> : Added <code>span.textbf</code> , etc. . . . .                                                     | 273       |
| <code>lwarpmk.conf</code> : Records                                                                                        |           |
| <code>--shell-escape</code> . . . . .                                                                                      | 273       |
| <code>arydshln</code> : Added. . . . .                                                                                     | 442, 665  |
| <code>lua-check-hyphen</code> : Added. . . . .                                                                             | 911       |
| <code>paralist</code> : Fixes for <code>compactenum</code> , <code>compactitem</code> , <code>compactdesc</code> . . . . . | 1009      |
| <code>parnotes</code> : Added. . . . .                                                                                     | 1013      |
| <code>quoting</code> : Added. . . . .                                                                                      | 1038      |
| <code>tocenter</code> : Added. . . . .                                                                                     | 1165      |
| <code>underscore</code> : Added. . . . .                                                                                   | 1183      |
| <i>lwarpmk</i> : Added                                                                                                     |           |
| <code>lwarpmk pdftosvg</code> . . . . .                                                                                    | 320       |
| <i>lwarpmk</i> : Supports                                                                                                  |           |
| <code>--shell-escape</code> . . . . .                                                                                      | 320       |
| Added <code>\thinspace</code> . . . . .                                                                                    | 616       |
| Docs: <b>lwarpmk pdftosvg</b> . . . . .                                                                                    | 95        |
| <code>LWR@blocktextcurrentfont</code> : Added <code>div.textbf</code> , etc. . . . .                                       | 610       |
| v0.57                                                                                                                      |           |
| <code>\BlockClassSingle</code> : Improved <code>print/HTML</code> output selection. . . . .                                | 360       |
| <code>\InlineClass</code> : Improved <code>print/HTML</code> output selection. . . . .                                     | 361       |

|                                                                                                            |      |                                                                                                  |          |
|------------------------------------------------------------------------------------------------------------|------|--------------------------------------------------------------------------------------------------|----------|
| <code>\LWR@href</code> : Fix: Text catcodes. . . . .                                                       | 513  | <code>\rotatebox</code> : Improved print/HTML<br>output selection. . . . .                       | 844      |
| <code>\LWR@singledollarmeasure</code> : Fix:<br>Dynamic inline math expressions. . . . .                   | 551  | <code>\rule</code> : Fix: Colored rules. . . . .                                                 | 622      |
| <code>\LWR@subhyperref</code> : Fix: Text<br>catcodes. . . . .                                             | 512  | <code>\scalebox</code> : Improved print/HTML<br>output selection. . . . .                        | 845      |
| <code>\LWR@subhyperref</code> text: Fix: Text<br>catcodes. . . . .                                         | 512  | <code>\textcolor</code> : xcolor: New system for<br>switching print and HTML<br>outputs. . . . . | 1206     |
| <code>\LWR@subsingledollar</code> : Fix: Dynamic<br>inline math expressions. . . . .                       | 556  | General: 2018/06/06 . . . . .                                                                    | 1        |
| <code>\LWR@subsingledollarsvg</code> : Fix:<br>Dynamic inline math expressions. . . . .                    | 554  | <code>MATHJAX</code> : Supports <code>\footnote</code> ,<br><code>\footnotemark</code> . . . . . | 389      |
| <code>\LWR@vspace</code> : Improved print/HTML<br>output selection. . . . .                                | 621  | <code>lwarp.css</code> : Added ruled, boxed,<br>boxruled floats. . . . .                         | 273      |
| <code>\MathImageAltText</code> : Added. . . . .                                                            | 547  | <code>lwarp.css</code> : Increased float vertical<br>margins. . . . .                            | 273      |
| <code>\PackageDiagramAltText</code> : Added. . . . .                                                       | 547  | <code>algorithm2e</code> : Added. . . . .                                                        | 647      |
| <code>\StartDefiningMath</code> : Added. . . . .                                                           | 342  | <code>bigdelim</code> : Improved print/HTML<br>output selection. . . . .                         | 687      |
| <code>\boxframe</code> : xcolor: Fix: Colored<br><code>\boxframe</code> . . . . .                          | 1210 | <code>breakurl</code> : Fix: Text catcodes. . . . .                                              | 694      |
| <code>\colorbox</code> : xcolor: New system for<br>switching print and HTML<br>outputs. . . . .            | 1207 | <code>colortbl</code> : New system for switching<br>print and HTML outputs. . . . .              | 743, 744 |
| <code>\colorboxBlock</code> : xcolor: New system<br>for switching print and HTML<br>outputs. . . . .       | 1207 | <code>ellipsis</code> : Added <code>\midwordellipsis</code> . . . . .                            | 761      |
| <code>\fboxBlock</code> : Improved print/HTML<br>output selection. . . . .                                 | 603  | errata: Added. . . . .                                                                           | 774      |
| <code>\fcolorbox</code> : xcolor: New system for<br>switching print and HTML<br>outputs. . . . .           | 1208 | float: Added float styles. . . . .                                                               | 802      |
| <code>\framebox</code> : Improved print/HTML<br>output selection. . . . .                                  | 602  | float: Fix: Do not pre-define<br><code>\l@name</code> . . . . .                                  | 802      |
| <code>\inlinemathother</code> : Added. . . . .                                                             | 343  | <code>ltablex</code> : Added. . . . .                                                            | 909      |
| <code>\listof</code> : Fix: Provide <code>\l@name</code> if not<br>defined. . . . .                        | 527  | <code>marginnote</code> : Fix: Long optional<br>argument. . . . .                                | 922      |
| <code>\makebox</code> : Improved print/HTML<br>output selection. . . . .                                   | 601  | <code>multirow</code> : Improved print/HTML<br>output selection. . . . .                         | 969      |
| <code>\mbox</code> : Improved print/HTML output<br>selection. . . . .                                      | 600  | <code>register</code> : Added. . . . .                                                           | 1043     |
| <code>\multicolumnrow</code> : <code>multirow</code> :<br>Improved print/HTML output<br>selection. . . . . | 970  | <code>subcaption</code> : Fix: <code>\subref</code> . . . . .                                    | 859      |
| Improved print/HTML output<br>selection. . . . .                                                           | 490  | <code>trimclip</code> : Added. . . . .                                                           | 1176     |
| <code>\newfloat</code> : <code>rotfloat</code> : Added float<br>styles. . . . .                            | 1049 | <code>vowel</code> : Added. . . . .                                                              | 1194     |
| <code>rotfloat</code> : Fix for listof sideways<br>floats. . . . .                                         | 1049 | <code>xellipsis</code> : Added. . . . .                                                          | 1212     |
| <code>\parbox</code> : Improved print/HTML<br>output selection. . . . .                                    | 600  | <code>xfrac</code> : Improved print/HTML<br><code>\scalebox</code> control. . . . .              | 1214     |
| <code>\raisebox</code> : Improved print/HTML<br>output selection. . . . .                                  | 605  | <code>xltabular</code> : Added. . . . .                                                          | 1216     |
| <code>\reflectbox</code> : Improved print/HTML<br>output selection. . . . .                                | 846  | <code>xpiano</code> : Added. . . . .                                                             | 1217     |
| <code>\resizebox</code> : Improved print/HTML<br>output selection. . . . .                                 | 846  | <i>lwarpmk</i> : Improved code factoring. . . . .                                                | 320      |
|                                                                                                            |      | <i>lwarpmk</i> : Improved error handling. . . . .                                                | 320      |
|                                                                                                            |      | Docs: Recompiling <i>lwarpmk</i> or css<br>files. . . . .                                        | 193      |
|                                                                                                            |      | Docs: Recreating the index for<br><i>lwarp</i> source. . . . .                                   | 191      |
|                                                                                                            |      | New system for switching print and<br>HTML outputs. . . . .                                      | 257      |
|                                                                                                            |      | <code>minipage</code> : Improved print/HTML<br>output selection. . . . .                         | 597      |
|                                                                                                            |      | <code>BlockClass</code> : Improved print/HTML<br>output selection. . . . .                       | 360      |
|                                                                                                            |      | <code>fminipage</code> : Improved print/HTML<br>output selection. . . . .                        | 603      |

|                                                                                            |      |                                                                                                                     |      |
|--------------------------------------------------------------------------------------------|------|---------------------------------------------------------------------------------------------------------------------|------|
| LWR@BlockClassWP: Improved print/HTML output selection. . .                                | 361  | lwrap-patch-memoir: Fix for \specialindex. . . . .                                                                  | 1251 |
| v0.58                                                                                      |      | lwrap-patch-memoir: Fix for multiple indexes. . . . .                                                               | 1252 |
| \LWR@HTML@caption@begin: Improved print/HTML output selection. . .                         | 521  | makeidx: Added. Moved from lwrap core. . . . .                                                                      | 918  |
| \LWR@HTML@caption@end: Improved print/HTML output selection. . .                           | 521  | memoir: Fix for \firsthlline, \lasthline. . . . .                                                                   | 491  |
| \LWR@HTML@ref: Improved print/HTML output selection. . . . .                               | 510  | memoir: Fix for booktabs. . . . .                                                                                   | 496  |
| \LWR@doindexentrysubsub: Adds support for \see, \seealso, \emph, \textbf, etc. . . . .     | 537  | pdfpages: Added. . . . .                                                                                            | 1019 |
| \LWR@hyperindexrefnullified: Adds support for \see, \seealso, \emph, \textbf, etc. . . . . | 538  | pdfx: Added. . . . .                                                                                                | 1023 |
| \LWR@hyperindexrefsubtwo: Adds support for \see, \seealso, \emph, \textbf, etc. . . . .    | 539  | repeatindex: Added. . . . .                                                                                         | 1046 |
| \LWR@indexitem: Accepts optional arg for repeatindex. . . . .                              | 533  | splitidx: Added. . . . .                                                                                            | 1094 |
| \dotfill: Improved print/HTML output selection. . . . .                                    | 617  | textcomp: Improved print/HTML output selection. . . . .                                                             | 1135 |
| \hfill: Improved print/HTML output selection. . . . .                                      | 617  | lwrapmk: Added makeindex and xindy options. . . . .                                                                 | 320  |
| \hrulefill: Improved print/HTML output selection. . . . .                                  | 617  | lwrapmk: Added -p option for project name. . . . .                                                                  | 320  |
| \printindex: Fix: Extra \newpage to flush pending \index writes. . .                       | 919  | lwrapmk: Added optional list of names for lwrapmk printindex and /cmdslwrapmk htmindex. .                           | 320  |
| General: 2018/07/07 . . . . .                                                              | 1    | lwrapmk: Glossary generation now uses makeglossaries. . . . .                                                       | 320  |
| *.lwrapmkconf: Added option makeindexstyle. . . . .                                        | 273  | lwrapmk: lwrapmk clean removes all *.ind and *.idx files. . . . .                                                   | 320  |
| *.lwrapmkconf: Added options makeindex and xindy. . . . .                                  | 273  | Added makeindex option. . . . .                                                                                     | 233  |
| *.lwrapmkconf: Generated \AtBeginDocument. . . . .                                         | 273  | Added xindy option. . . . .                                                                                         | 233  |
| lwrap.xdy: Requires makeindex.xdy. . . . .                                                 | 315  | Added option makeindexStyle. .                                                                                      | 232  |
| lwrap.xdy: Supports bold, italic. .                                                        | 315  | Docs: Index, <i>makeindex</i> , imakeidx. .                                                                         | 139  |
| lwrap_html.ist: Added. . . . .                                                             | 314  | Docs: Misplaced \omit. . . . .                                                                                      | 197  |
| lwrapmk.conf: Added option makeindexstyle. . . . .                                         | 273  | Fix: memoir and ccaption. . . . .                                                                                   | 210  |
| lwrapmk.conf: Added options makeindex and xindy. . . . .                                   | 273  | Improved print/HTML output selection. . . . .                                                                       | 616  |
| lwrapmk.conf: Generated \AtBeginDocument. . . . .                                          | 273  | Replaced each \csuse with \@nameuse to force error if undefined. . . . .                                            | 1    |
| array: Improved print/HTML output selection. . . . .                                       | 664  | tabbing: Improved print/HTML output selection. . . . .                                                              | 431  |
| attachfile2: Added. . . . .                                                                | 669  | v0.59                                                                                                               |      |
| attachfile: Added. . . . .                                                                 | 668  | \LWR@addbaselinemarker: Uses .eps if DVI <i>latex</i> . . . . .                                                     | 549  |
| cases: Added. . . . .                                                                      | 703  | \LWR@latexmkcmd: Fix: --shell-escape with <i>latexmk</i> . . .                                                      | 268  |
| imakeidx: Added. . . . .                                                                   | 866  | \LWR@writeconf: Compilation commands now preassigned by lwrap instead of being computed by <i>lwrapmk</i> . . . . . | 272  |
| index: Added. . . . .                                                                      | 870  | \[: Fix with \displaymathnormal. .                                                                                  | 559  |
| intopdf: Added. . . . .                                                                    | 872  | General: 2018/09/07 . . . . .                                                                                       | 1    |
| lwrap-patch-komascript: Modified indexing. . . . .                                         | 1227 | Slunits: Added. . . . .                                                                                             | 1072 |
|                                                                                            |      | accsupp: Added. . . . .                                                                                             | 642  |
|                                                                                            |      | amsmath: Moved from the lwrap core. . . . .                                                                         | 653  |
|                                                                                            |      | asymptote: Added. . . . .                                                                                           | 667  |

|                                                                                                                 |          |
|-----------------------------------------------------------------------------------------------------------------|----------|
| axessibility: Added. . . . .                                                                                    | 675      |
| breqn: Added. . . . .                                                                                           | 695      |
| bxpapersize: Added. . . . .                                                                                     | 697      |
| canoniclayout: Added. . . . .                                                                                   | 698      |
| chemformula: Fix for \NMR. . . . .                                                                              | 732      |
| draftcopy: Added. . . . .                                                                                       | 755      |
| epstopdf-base: Improved. . . . .                                                                                | 772      |
| epstopdf: Improved. . . . .                                                                                     | 771      |
| fnbreak: Added. . . . .                                                                                         | 810      |
| graphics: Fix: Expand filename. . . . .                                                                         | 842      |
| graphics: Now works with .pdf and<br>.eps filename extensions. . . . .                                          | 841      |
| nccfancyhdr: Added. . . . .                                                                                     | 977      |
| pdftricks: Added. . . . .                                                                                       | 1022     |
| pst-eps: Added. . . . .                                                                                         | 1034     |
| pstricks: Added. . . . .                                                                                        | 1035     |
| units: Added support for MathJax. . . . .                                                                       | 1187     |
| xunicode: Added. . . . .                                                                                        | 1222     |
| <i>lwarpmk</i> : Added                                                                                          |          |
| <i>lwarpmk</i> epstopdf. . . . .                                                                                | 320      |
| <i>lwarpmk</i> : Consolidated compiling<br>options into printlatexcmd and<br>HTMLlatexcmd. . . . .              | 320      |
| <i>lwarpmk</i> : Double instead of<br>single-dashed --shell-escape<br>option. . . . .                           | 320      |
| <i>lwarpmk</i> : Error if lwarpmk.conf<br>format changed. . . . .                                               | 320      |
| <i>lwarpmk</i> : Warning if operating<br>system changed. . . . .                                                | 320      |
| Added option dvipdfmx. . . . .                                                                                  | 234      |
| Added option dvipdfm. . . . .                                                                                   | 234      |
| Added option dvips. . . . .                                                                                     | 234      |
| Docs: <i>lwarpmk</i> epstopdf. . . . .                                                                          | 95       |
| File: lwarpmathjax.txt: Fix:<br>Removed chapter number from<br>tagged non-numeric MATHJAX<br>equations. . . . . | 316      |
| File: lwarpmathjax.txt: Updated<br>to MATHJAX v2.7.4. . . . .                                                   | 316      |
| picture: Added an alt tag. . . . .                                                                              | 594      |
| v0.60                                                                                                           |          |
| \LWR@clearmidrules: tabular: Fix for<br>midrules. . . . .                                                       | 471      |
| \LWR@parsenormalcolumn: tabular:<br>Improved memory management:<br>Not using xstring. . . . .                   | 457      |
| \LWR@tabledatasinglecolumn: tag:<br>tabular: Improved memory<br>management: Not using<br>xstring. . . . .       | 468, 469 |
| \LWR@tabularendofline: Fix:<br>Slowdown for long tables. . . . .                                                | 452      |
| General: 2018/09/19 . . . . .                                                                                   | 1        |
| tabular: Improved memory<br>management: Global boolean. . . . .                                                 | 443      |
| tabular: Improved memory<br>management: Not using<br>xstring. . . . .                                           | 445, 969 |
| 2up: Added. . . . .                                                                                             | 636      |
| booklet: Added. . . . .                                                                                         | 690      |
| bophook: Added. . . . .                                                                                         | 692      |
| diagbox: Fix for par tags. . . . .                                                                              | 752      |
| draftfigure: Added. . . . .                                                                                     | 755      |
| fancytabs: Added. . . . .                                                                                       | 787      |
| fullminipage: Added. . . . .                                                                                    | 823      |
| grid-system: Added. . . . .                                                                                     | 847      |
| layaureo: Added. . . . .                                                                                        | 886      |
| leading: Added. . . . .                                                                                         | 889      |
| listings: Fix for HTML entities. . . . .                                                                        | 901      |
| listings: Fix if inside a list. . . . .                                                                         | 902, 904 |
| thumbs: Added. . . . .                                                                                          | 1148     |
| thumb: Added. . . . .                                                                                           | 1148     |
| widows-and-orphans: Added. . . . .                                                                              | 1198     |
| v0.61                                                                                                           |          |
| \DeclareGraphicsExtensions: Fix:<br>EPS for DVI L <sup>A</sup> T <sub>E</sub> X. . . . .                        | 834      |
| \LWR@HTMLLatexCmd: Added<br>HTMLLatexCmd option. . . . .                                                        | 272      |
| Added PrintLatexCmd option. . . . .                                                                             | 272      |
| \LWR@addcompilecmd: Removed<br>spaces. . . . .                                                                  | 267      |
| \LWR@closetabledatacell: Fix: Par<br>tags in tabular. . . . .                                                   | 447      |
| \LWR@hyperindexrefnullified:<br>Made robust, . . . . .                                                          | 538      |
| \LWR@opseq: Added spaces. . . . .                                                                               | 229      |
| \RequirePackage: Support up to 20<br>packages. . . . .                                                          | 248      |
| \inlinemathnormal: Changed name<br>from \StopDynamicMath to<br>\inlinemathnormal. . . . .                       | 343      |
| \inlinemathother: Changed name<br>from \StartDynamicMath to<br>\inlinemathother. . . . .                        | 343      |
| \listof: Fix: newfloat lists. . . . .                                                                           | 527      |
| \lwarpmksetup: Added. . . . .                                                                                   | 230      |
| General: 2018/10/13 . . . . .                                                                                   | 1        |
| lwarpmk.css: Footnotes text align<br>left. . . . .                                                              | 273      |
| lwarpmk.css: Minipage table and<br>footnotes: tighter margin. . . . .                                           | 273      |
| chkfloat: Added. . . . .                                                                                        | 736      |
| cmdtrack: Added. . . . .                                                                                        | 742      |
| copyrightbox: Added. . . . .                                                                                    | 745      |
| dprogressbar: Added. . . . .                                                                                    | 754      |
| epsfig: Added. . . . .                                                                                          | 771      |
| graphics: Fix: EPS for DVI L <sup>A</sup> T <sub>E</sub> X. . . . .                                             | 839      |

|                                                                                          |            |                                                                     |      |
|------------------------------------------------------------------------------------------|------------|---------------------------------------------------------------------|------|
| graphics: Set keys before using filename, for epsfig. . . . . .                          | 842        | \l@chapter: Don't define if no \chapter. Fix for algorithm2e. . .   | 531  |
| lua-visual-debug: Added. . . . .                                                         | 911        | \slshape: Added. . . . .                                            | 613  |
| pdfprivacy: Added. . . . .                                                               | 1021       | \textup: Fixed WP span class. . . .                                 | 608  |
| psfragx: Added. . . . .                                                                  | 1034       | \theHTMLSection: Added. . . . .                                     | 407  |
| psfrag: Added. . . . .                                                                   | 1033       | \theHTMLTitleSection: Added. . . .                                  | 407  |
| pstool: Added. . . . .                                                                   | 1035       | \theHTMLTitleSeparator:<br>Refactored. . . . .                      | 407  |
| refcheck: Added. . . . .                                                                 | 1043       | General: 2018/11/19 . . . . .                                       | 1    |
| srcltx: Added. . . . .                                                                   | 1096       | \textbf and related: Improved font detection. . . . .               | 606  |
| srctex: Added. . . . .                                                                   | 1096       | lwrap.css: Added css for xfrac, nicefrac. . . . .                   | 273  |
| supertabular: Fix for caption w/o opt arg. . . . .                                       | 1119       | lwrap.css: Fixed css for \textup. . .                               | 273  |
| thinsp: Added. . . . .                                                                   | 1143       | lwrap.css: Reduced margins in titlepage. . . . .                    | 273  |
| threadcol: Added. . . . .                                                                | 1146       | lwrap_formal.css: Fix: Font for verse. . . . .                      | 310  |
| uspace: Added. . . . .                                                                   | 1190       | 2in1: Added. . . . .                                                | 636  |
| vpe: Added. . . . .                                                                      | 1194       | CJKutF8: Prevented unless xeCJK. . .                                | 737  |
| xbmks: Added. . . . .                                                                    | 1201       | CJK: Prevented unless xeCJK. . . .                                  | 737  |
| xtab: Fix for caption w/o opt arg. . .                                                   | 1221       | asymptote: Improved alt tags. . . .                                 | 667  |
| Added HTMLLatexCmd option. . . . .                                                       | 233        | bitpattern: Added. . . . .                                          | 688  |
| Added PrintLatexCmd option. . . . .                                                      | 233        | calc: Fix: Required for print version. . . . .                      | 242  |
| Docs: \tracinglwrap . . . . .                                                            | 253        | chngepage: Fix: Loads lwrap-chngepage. . . . .                      | 736  |
| Docs: HTML entities. . . . .                                                             | 124        | ctexpatch: Added patch. . . . .                                     | 631  |
| Docs: Compiling using custom shell commands. . . . .                                     | 179        | flippdf: Added. . . . .                                             | 801  |
| Docs: Fonts. . . . .                                                                     | 101        | graphics: Fix: Filename expansion. . .                              | 840  |
| Docs: HTMLDebugComments . . . . .                                                        | 110, 253   | graphics: Fix: FormatWP. . . . .                                    | 839  |
| Docs: Multiple indexes. . . . .                                                          | 202        | musicography: Added. . . . .                                        | 972  |
| Don't write configuration files if processing pstool image. . . . .                      | 266        | nicefrac: Improved font control and css, honors nice, ugly. . . . . | 990  |
| Spaces redefined \AtBeginDocument. . . . .                                               | 616        | notespages: Added. . . . .                                          | 993  |
| v0.62                                                                                    |            | octave: Added. . . . .                                              | 1006 |
| \@partcntformat: Added for ctex. . .                                                     | 398        | pdfcomment: Added. . . . .                                          | 1017 |
| \@partnameformat: Added for ctex. . .                                                    | 398        | pdfmarginpar: Added. . . . .                                        | 1019 |
| \InlineClass: Added optional word-processing style. Replaces \LWR@HTMLtextstyle. . . . . | 361        | register: Updated to v1.8. . . . .                                  | 1043 |
| \LWR@PreLoadedPackage: Added. . . . .                                                    | 584        | rviewport: Added. . . . .                                           | 1050 |
| \LWR@ProvidesPackagePass: Fix: Unknown option error. . . . .                             | 250        | semantic-markup: Added. . . . .                                     | 1062 |
| \LWR@endofline: Extra space if optional arg. . . . .                                     | 618        | textcomp: Fix conflict with xunicode. . . . .                       | 1137 |
| \LWR@filestart: Refactored. . . . .                                                      | 409        | tram: Added. . . . .                                                | 1175 |
| \LWR@isolate: Added. . . . .                                                             | 224        | twoup: Added. . . . .                                               | 1178 |
| \LWR@textcurrentfont: Added print version. . . . .                                       | 615        | ulem: Improved compatibility with CJKulem. . . . .                  | 1180 |
| Tracks depth to avoid nesting repeated font changes. . . . .                             | 610        | ulem: Now works in a lateximage. . . . .                            | 1180 |
| \colorboxBlock: xcolor: Fix: Horiz white space. . . . .                                  | 1207       | unitsdef: Added. . . . .                                            | 1188 |
| \fcolorbox: Fix: No longer requires xifthen. . . . .                                     | 590        | units: Improved font control and css, honors loose, tight. . . . .  | 1187 |
| \fcolorboxBlock: xcolor: Fix: Horiz white space. . . . .                                 | 1208, 1209 | xcolor: Fix: Horiz white space. . . .                               | 1209 |
|                                                                                          |            | xexchangebar: Added. . . . .                                        | 1212 |
|                                                                                          |            | xfrac: Improved css. . . . .                                        | 1214 |

|                                                                             |          |                                                                                      |          |
|-----------------------------------------------------------------------------|----------|--------------------------------------------------------------------------------------|----------|
| xunicode: Fix conflict with textcomp. . . . .                               | 1222     | lwrap.css: Improved css for mdframed. . . . .                                        | 273      |
| Added early checks for CJK, CJKutf8. . . . .                                | 209      | amsthm, mdframed: Fix for enforced load order. . . . .                               | 656      |
| Docs: asymptote. . . . .                                                    | 165      | emumitem: v3.6: Nullify \DrawEnumitemLabel. . . . .                                  | 769      |
| Docs: miktex-poppler-bin-* . . . . .                                        | 82       | everyhook: Fix for bxjs* classes. . . . .                                            | 242      |
| Docs: <i>MiKTeX Console</i> . . . . .                                       | 78       | geometry: Fix for bxjs* classes. . . . .                                             | 241      |
| Docs: Improved MiKTeX install instructions. . . . .                         | 78       | mdframed: Avoid thin rules. . . . .                                                  | 939      |
| Docs: UTF-8 locale. . . . .                                                 | 182      | mdframed: Improved font control. . . . .                                             | 942–944  |
| File: lwrap_mathjax.txt: Removed inoperable siunitx extension. . . . .      | 316      | stfloats: Adapted to ltj* classes. . . . .                                           | 1111     |
| Logos: CSS instead of <sub>, <sub>. . . . .                                 | 624      | xpinyin: Added. . . . .                                                              | 1218     |
| Logos: Fix for Xe <sub>La</sub> TeX logo if graphics is not loaded. . . . . | 624      | zhlineskip: Added. . . . .                                                           | 1224     |
| Logos: Improved CSS. . . . .                                                | 624      | Added pTeXsupport. . . . .                                                           | 206      |
| Logos: Made robust. . . . .                                                 | 624      | Docs: \Linkhomename. . . . .                                                         | 110      |
| fcolorminipage: xcolor: Fix: Horiz white space. . . . .                     | 1210     | Docs: \sidetocname. . . . .                                                          | 112      |
| Fix: No longer requires xifthen. . . . .                                    | 592      | Fix: Default \LWR@mdfive. . . . .                                                    | 221      |
| fminipage: Fix: Horiz white space. . . . .                                  | 604, 605 | Improved titles. . . . .                                                             | 941, 942 |
| LWR@blocktextcurrentfont: Added print version. . . . .                      | 615      | pTeX: Encoding. . . . .                                                              | 221      |
|                                                                             |          | pTeX: Load upquote. . . . .                                                          | 223      |
|                                                                             |          | pTeX: No newunicodechar. . . . .                                                     | 222      |
|                                                                             |          | LWR@BlockClassWP: Fix for xeCJK. . . . .                                             | 361      |
|                                                                             |          |                                                                                      |          |
| v0.63                                                                       |          | v0.64                                                                                |          |
| \LWR@HTMLLatexCmd: uarticle and related: Compile options. . . . .           | 272      | \LWR@HTMLLatexCmd: utarticle and related: Added. . . . .                             | 272      |
| \LWR@LwrapStart: Fixes for xeCJK. . . . .                                   | 411      | \LWR@checkloadfilename: Prevented bitfield, doublespace, newthm, rplain, si. . . . . | 246      |
| \LWR@atbeginverbatim: Fix for xeCJK. . . . .                                | 429      | \LWR@section: Support for uarticle and related. . . . .                              | 402      |
| \LWR@checkloadbefore: Added. . . . .                                        | 208      | \enskip: Made robust. . . . .                                                        | 619      |
| \LWR@checkloadfilename: Added to reduce number of lwrap-* files. . . . .    | 246      | \qqad: Made robust. . . . .                                                          | 618      |
| \LWR@checkloadnever: Added. . . . .                                         | 209      | \quad: Made robust. . . . .                                                          | 618      |
| \LWR@compileuplatex: Added. . . . .                                         | 268      | \theHTMLTitleSeparator: Added utarticle and related. . . . .                         | 407      |
| \LWR@createautosec: Fix for xeCJK. . . . .                                  | 397      | General: 2018/12/08 . . . . .                                                        | 1        |
| \LWR@earlyclassloadnever: Added. . . . .                                    | 209      | addlines: Updated to v0.3. . . . .                                                   | 647      |
| \LWR@filestart: Fix: Break ligature for luatexko. . . . .                   | 409      | biblatex: Added patch for CTeX. . . . .                                              | 682      |
| \LWR@firstoffour: Added. . . . .                                            | 225      | bsheaders: Added. . . . .                                                            | 696      |
| \LWR@htmlclosecomment: Fix: Break ligature for luatexko. . . . .            | 357      | gmeometric: Added. . . . .                                                           | 833      |
| \LWR@isolate: Fix for xeCJK. . . . .                                        | 224      | marginal: Added. . . . .                                                             | 921      |
| \LWR@notltjloadafter: Added more classes. . . . .                           | 207      | rmpage: Added. . . . .                                                               | 1047     |
| Added. . . . .                                                              | 207      | scrlayer-scrpage: Fixes. . . . .                                                     | 1058     |
| \LWR@subhtmllementclass: Fix for xeCJK. . . . .                             | 358      | scrlayer: Fixes. . . . .                                                             | 1057     |
| \LinkHome: Fix: Print version. . . . .                                      | 347      | scrpage2: Added. . . . .                                                             | 1059     |
| \Linkhomename: Added. . . . .                                               | 347      | uarticle and related: Improved \today. . . . .                                       | 629      |
| General: 2018/12/03 . . . . .                                               | 1        | Added utarticle and related. . . . .                                                 | 629      |
| lwrap.css: Added css for vertical writing. . . . .                          | 273      |                                                                                      |          |
|                                                                             |          | v0.65                                                                                |          |
|                                                                             |          | \LWR@LwrapEnd: Improved css for page layout. . . . .                                 | 414      |
|                                                                             |          | \LWR@LwrapStart: Improved css for page layout. . . . .                               | 412      |

|                                          |                                          |     |
|------------------------------------------|------------------------------------------|-----|
| \LWR@PreLoadedPackage:                   | Fix: tabular*. . . . .                   | 497 |
| \AtBeginDocument to avoid                | Fix: Rule color. . . . .                 | 499 |
| option clashes. . . . .                  | minipage: Refactored to later allow      |     |
| . . . . . 584                            | Japanese <t/y> argument. . . . .         | 597 |
| \LWR@hyperindexrefnullified:             | LWR@figcaption: Uses                     |     |
| Added \textsi. . . . .                   | <figurecaption> instead of               |     |
| . . . . . 538                            | <figcaption>. . . . .                    | 521 |
| \LWR@newhtmlfile: Error if duplicate     | v0.66                                    |     |
| file name. . . . .                       | \@mpfootnotetext: Improved HTML          |     |
| . . . . . 392                            | formatting. . . . .                      | 376 |
| Improved css for page layout. 392, 394   | \IgnoreMinipageWidths: Added, ..         | 596 |
| \LWR@nullfonts: Added \textsi. . . . .   | \LWR@footnotetext: Improved HTML         |     |
| . . . . . 543                            | formatting. . . . .                      | 375 |
| \LWR@restoreorigformatting: Fix:         | \LWR@LwarpStart: Fix: TOC, LOF, LOT      |     |
| tabular*. . . . .                        | links. . . . .                           | 413 |
| . . . . . 542                            | \LWR@checkloadfilename: Prevented        |     |
| \enskip: Changed to Unicode EN           | colortab, epsf, hyper, picinpar,         |     |
| SPACE. . . . .                           | picins, sistyle, ucs. . . . .            | 246 |
| . . . . . 619                            | \LWR@closeparagraph: Fix: Combined       |     |
| \quad: Changed to Unicode EM             | span, tabular, and lateximage. 366       |     |
| SPACE. . . . .                           | Improved HTML formatting. . . . .        | 365 |
| . . . . . 618                            | \LWR@closeparagraph@br: Factored. 364    |     |
| \sishape: Added \sishape. . . . .        | \LWR@fboxstyle: Use current text         |     |
| . . . . . 612                            | color. . . . .                           | 602 |
| \textsi: Added. . . . .                  | \LWR@filenamenoblanks: Fix: Section      |     |
| . . . . . 608                            | names detokenized. . . . .               | 382 |
| General: 2018/12/22 . . . . .            | Fix: Section names with macros. 383      |     |
| . . . . . 1                              | Fix: Section names with percent. 383     |     |
| lwarp.css: Added \sishape,               | Improved file name generation. . 382     |     |
| \textsi. . . . .                         | Limits filename length. . . . .          | 385 |
| . . . . . 273                            | \LWR@findcurrenttextcolor: Fix:          |     |
| lwarp.css: Improved css for page         | Color if xcolor not loaded. . . . .      | 615 |
| layout. . . . .                          | \LWR@htmlfileref: No longer use          |     |
| . . . . . 273                            | zref. . . . .                            | 505 |
| lwarp.css: Improved css for              | \LWR@htmlsectionfilename: Sanitize       |     |
| quotations. . . . .                      | underscores. . . . .                     | 345 |
| . . . . . 273                            | \LWR@hyperindexrefsubtwo: Fix:           |     |
| lwarp.css: Siderocto left for            | Long index entries. . . . .              | 539 |
| improved \marginpars. . . . .            | \LWR@indentHTML: Added. . . . .          | 354 |
| . . . . . 273                            | \LWR@lateximagedepthref: No longer       |     |
| lwarp_formal.css: Siderocto left         | use zref. . . . .                        | 505 |
| for improved \marginpars. . . . .        | \LWR@lateximagenumberref: No             |     |
| . . . . . 310                            | longer use zref. . . . .                 | 505 |
| lwarp_sagebrush.css: Siderocto           | \LWR@nameref: No longer use zref. . 505  |     |
| left for improved \marginpars. . 305     | \LWR@nullfonts: Logos. . . . .           | 546 |
| . . . . . 305                            | \LWR@openparagraph: Improved HTML        |     |
| bounddvi: Added. . . . .                 | formatting. . . . .                      | 364 |
| . . . . . 693                            | \LWR@section: Fix: TOC, LOF, LOT         |     |
| embrac: Added. . . . .                   | links. . . . .                           | 403 |
| . . . . . 761                            | Improved HTML formatting. . . . .        | 403 |
| footnoterange: Added. . . . .            | \LWR@setexparray: Fix with \par. . 341   |     |
| . . . . . 817                            | \LWR@setref: No longer use zref. . . 505 |     |
| gentombow: Added. . . . .                | \LWR@simplifname: Added. . . . .         | 381 |
| . . . . . 828                            | \LWR@startref: No longer use zref. 508   |     |
| geometry: Fix for bxjs* classes. . . 241 |                                          |     |
| graphics: Added \includegraphics         |                                          |     |
| alt key. 589, 835, 836, 838, 841, 842    |                                          |     |
| . . . . . 905                            |                                          |     |
| lltjext: Added. . . . .                  |                                          |     |
| . . . . . 905                            |                                          |     |
| multicolrule: Added. . . . .             |                                          |     |
| . . . . . 966                            |                                          |     |
| multicol: Added \docolaction. . . 965    |                                          |     |
| . . . . . 965                            |                                          |     |
| plarydshln: Added. . . . .               |                                          |     |
| . . . . . 1030                           |                                          |     |
| plextarydshln: Added. . . . .            |                                          |     |
| . . . . . 1031                           |                                          |     |
| plextcolortbl: Added. . . . .            |                                          |     |
| . . . . . 1031                           |                                          |     |
| plext: Added. . . . .                    |                                          |     |
| . . . . . 1030                           |                                          |     |
| pxatbegshi: Added. . . . .               |                                          |     |
| . . . . . 1036                           |                                          |     |
| pxeveryshi: Added. . . . .               |                                          |     |
| . . . . . 1036                           |                                          |     |
| pxftnright: Added. . . . .               |                                          |     |
| . . . . . 1037                           |                                          |     |
| pxjahyper: Added. . . . .                |                                          |     |
| . . . . . 1037                           |                                          |     |
| tascmac: Added. . . . .                  |                                          |     |
| . . . . . 1126                           |                                          |     |
| versonotes: Added. . . . .               |                                          |     |
| . . . . . 1193                           |                                          |     |
| Added early checks for jarticle,         |                                          |     |
| tarticle, and related. . . . .           |                                          |     |
| . . . . . 209                            |                                          |     |
| Fix for \rensuji. . . . .                |                                          |     |
| . . . . . 629                            |                                          |     |
| Fix space between class and id. . 361    |                                          |     |
| . . . . . 361                            |                                          |     |
| tabular: Added support for plect. . 497  |                                          |     |
| . . . . . 497                            |                                          |     |

|                                                                                           |      |                                                                                       |          |
|-------------------------------------------------------------------------------------------|------|---------------------------------------------------------------------------------------|----------|
| \LWR@stoppars: Improved HTML formatting. . . . .                                          | 368  | zref: No longer used. . . . .                                                         | 244      |
| \LWR@subhtmlclass: Improved HTML formatting. . . . .                                      | 358  | <i>lwarpmk</i> : Added ImagesDirectory and ImagesName. . . . .                        | 320      |
| \LWR@subhyperrefclass: Improved HTML formatting. . . . .                                  | 512  | <i>lwarpmk</i> : Fix for <b>cleanimages</b> . . . . .                                 | 320      |
| \LWR@subinlineimage: Improved HTML formatting. . . . .                                    | 514  | Added early checks for colortab, epsf, hyper, picinpar, picins, sistyle, ucs. . . . . | 209      |
| \LWR@write@lwarplabel: No longer use zref. . . . .                                        | 505  | Added option ImagesDirectory. . . . .                                                 | 231      |
| \LWR@writeconf: Added ImagesDirectory and ImagesName. . . . .                             | 272  | Added option ImagesName. . . . .                                                      | 231      |
| \LinkHome: Fix: Document cross-references. . . . .                                        | 347  | Added support for indentfirst. . . . .                                                | 369      |
| \UseMinipageWidths: Added, . . . . .                                                      | 596  | Docs: Updated Converting an existing document. . . . .                                | 98       |
| \fbox: Fix: Removed extra space. . . . .                                                  | 602  | Fix: Minipages inside multicol. . . . .                                               | 965      |
| \minipagefullwidth: Made \global. . . . .                                                 | 596  | Improved HTML formatting. . . . .                                                     | 789      |
| \rotatebox: Improved HTML formatting. . . . .                                             | 844  | Package dates added where possible. . . . .                                           | 636      |
| \rule: Improved HTML formatting. . . . .                                                  | 622  | Sanitize filenames. . . . .                                                           | 235      |
| \scalebox: Improved HTML formatting. . . . .                                              | 845  | tabular: Fix: Minipages inside tabular. . . . .                                       | 500      |
| \textgreater: Made robust. . . . .                                                        | 344  | lateximage: Added \BaseJobname for multiple projects. . . . .                         | 577      |
| \textless: Made robust. . . . .                                                           | 344  | Improved HTML formatting. . . . .                                                     | 578      |
| General: 2019/02/08 . . . . .                                                             | 1    | minipage: Honor \LWR@forceminipagefullwidth. . . . .                                  | 598      |
| LWR@currentautosec: Fix for L <sup>o</sup> F, L <sup>o</sup> Ffloat in home page. . . . . | 399  | v0.67                                                                                 |          |
| lwarp.css: Added niceframe. . . . .                                                       | 273  | \FilenameNullify: Added. . . . .                                                      | 546, 615 |
| lwarp.css: Improved css for definition lists. . . . .                                     | 273  | \FilenameSimplify: Added. . . . .                                                     | 381, 391 |
| lwarp_formal.css: Improved css for table notes. . . . .                                   | 310  | \LWR@doequation: xfakebold: Added support. . . . .                                    | 565      |
| lwarp_one_limage.txt: Image directory and prefix. . . . .                                 | 315  | \LWR@doubledollar: xfakebold: Added support. . . . .                                  | 558      |
| acronym: Fix for acronym in caption. . . . .                                              | 645  | \LWR@filenamenoblanks: Improved file name generation. . . . .                         | 382      |
| acronym: No longer uses zref. . . . .                                                     | 645  | \LWR@lookforpackagename: <b>easyReview</b> : Supported. . . . .                       | 247      |
| ar: Added. . . . .                                                                        | 662  | \LWR@nullfonts: Add'l symbols. . . . .                                                | 544      |
| ed: Added. . . . .                                                                        | 760  | \LWR@simplifycustom: Added. . . . .                                                   | 381      |
| extramarks: Updated to v3.10. . . . .                                                     | 780  | \LWR@subsingledollar: xfakebold: Added support. . . . .                               | 556      |
| fancyhdr: Updated to v3.10. . . . .                                                       | 786  | \LWR@subsingledollarsvg: xfakebold: Added support. . . . .                            | 554, 555 |
| fancyvrb: Improved HTML formatting. . . . .                                               | 783  | General: 2019/02/23 . . . . .                                                         | 1        |
| graphics: Improved HTML formatting. . . . .                                               | 841  | academicons: Added. . . . .                                                           | 639      |
| kotexutf: Patch for references. . . . .                                                   | 631  | bbding: Added. . . . .                                                                | 677      |
| memoir: Docs re: version numbers. . . . .                                                 | 174  | changes: Added. . . . .                                                               | 706      |
| multicolrule: Updated for v1.2. . . . .                                                   | 966  | color: Fix for version number. . . . .                                                | 743      |
| nameauth: Added. . . . .                                                                  | 975  | dingbat: Added. . . . .                                                               | 753      |
| register: Verified for v1.9. . . . .                                                      | 1043 | eurosym: Added. . . . .                                                               | 779      |
| subcaption: Added. . . . .                                                                | 1112 | fitbox: Added. . . . .                                                                | 798      |
| tocbasic: Updated to v3.26a. . . . .                                                      | 1161 | fontawesome5: Added. . . . .                                                          | 813      |
| truncate: Added. . . . .                                                                  | 1177 | fontawesome: Added. . . . .                                                           | 812      |
|                                                                                           |      | foreign: Added. . . . .                                                               | 818      |
|                                                                                           |      | gloss: Added. . . . .                                                                 | 831      |
|                                                                                           |      | karnaugh-map: Added. . . . .                                                          | 873      |
|                                                                                           |      | marvosym: Added. . . . .                                                              | 923      |

|                                          |      |                                            |               |
|------------------------------------------|------|--------------------------------------------|---------------|
| multicap: Added. . . . .                 | 964  | \makebox: Fix: Handle paren arg. . .       | 601           |
| nomencl: Added. . . . .                  | 992  | \multicolumnrow: multirow: Error if        |               |
| notes: Added. . . . .                    | 993  | \multirow without \mrowcell. . .           | 970           |
| pifont: Added. . . . .                   | 1029 | General: 2019/03/21 . . . . .              | 1             |
| struktex: Added. . . . .                 | 1111 | array: Fix for                             |               |
| textcomp: Nullify in filenames. . .      | 1137 | \tabularnewline. . . . .                   | 664, 908      |
| typicons: Added. . . . .                 | 1180 | ctable: Added. . . . .                     | 746           |
| umoline: Added. . . . .                  | 1182 | eqlist: Added. . . . .                     | 773           |
| xfakebold: Added support. . . . .        | 548  | eqparbox: Added. . . . .                   | 773           |
| xfakebold: Added. . . . .                | 1213 | ftcap: Added. . . . .                      | 823           |
| xunicode: Nullify in filenames. . .      | 1222 | graphics: Warning if using scale           |               |
| AMS environments: Added                  |      | option. . . . .                            | 836           |
| xfakebold support. . . . .               | 653  | keyfloat: Updated for v2.00. . . .         | 876           |
| eqnarray: xfakebold: Added support.      | 571  | listliketab: Added. . . . .                | 905           |
| v0.68                                    |      | minitoc: Added. . . . .                    | 955           |
| \LWR@footnotetext: Factored for          |      | multirow: Error if \multirow               |               |
| multiple foot boxes. . . . .             | 375  | without \mrowcell. . . . .                 | 969           |
| \LWR@checkloadfilename: Prevented        |      | rotfloat: Requires graphicx. . . .         | 1048          |
| alg, algorithmic, fncylab,               |      | supertabular: Fix: Clear caption           |               |
| pdfcpot. . . . .                         | 246  | after use. . . . .                         | 1120          |
| \LWR@printpendingfootnotes:              |      | tabularx: Require array. . . . .           | 1123          |
| Factored for multiple footnote           |      | tabulary: Require array. . . . .           | 1123          |
| boxes. . . . .                           | 378  | tocdata: Added. . . . .                    | 1164          |
| \LWR@tabular@warpprintonly:              |      | topcapt: Added. . . . .                    | 1174          |
| Added. . . . .                           | 497  | xtab: Fix: Clear caption after use.        | 1222          |
| General: 2019/03/05 . . . . .            | 1    | tabular: Error if \multirow without        |               |
| bigfoot: Added. . . . .                  | 687  | \mrowcell. . . . .                         | 498, 500, 502 |
| fnpara: Added. . . . .                   | 811  | lateximage: Fix for <i>pdfotext</i> errors |               |
| footnotebackref: Added. . . . .          | 817  | from font size change. . . . .             | 581           |
| layouts: Added. . . . .                  | 887  | fminipage: Honors                          |               |
| listings: Fix for listings v1.7. . . .   | 904  | \minipagefullwidth. . . . .                | 604           |
| longtable: Improved error                |      | v0.70                                      |               |
| handling. . . . .                        | 908  | \LWR@closeparagraph: Reduced               |               |
| manyfoot: Added. . . . .                 | 919  | underfull \hbox warnings. . . . .          | 365           |
| niceframe: Added. . . . .                | 990  | \LWR@lookforpackagename: changes:          |               |
| perpage: Added. . . . .                  | 1024 | Updated to v3.1.2. . . . .                 | 247           |
| showtags: Added. . . . .                 | 1067 | \LWR@mathjaxfilename: Added. . . .         | 370           |
| tablefootnote: Added. . . . .            | 1122 | \LWR@restoreorigformatting: Fix:           |               |
| threeparttable: Added. . . . .           | 1147 | \& in a lateximage. . . . .                | 542           |
| threeparttable: Fix for caption          |      | \MathJaxFilename: Added. . . . .           | 371           |
| type. . . . .                            | 1146 | \enddocument: If labels changed,           |               |
| <i>lwarpmk</i> : Improved error handling |      | require recompile before making            |               |
| if incomplete compile. . . . .           | 320  | limages. . . . .                           | 415           |
| Prevented alg, algorithmic, fncylab,     |      | \framebox: Fix: Accept long arg. . .       | 602           |
| pdfcpot. . . . .                         | 209  | \makebox: Fix: Accept long arg. . . .      | 601           |
| tabular: Fix: \warpprintonly inside      |      | Fix: Ignore width of Opt. . . . .          | 601           |
| tabular. . . . .                         | 499  | Fix: No width given. . . . .               | 601           |
| v0.69                                    |      | General: 2019/04/03 . . . . .              | 1             |
| \LWR@maybetocdata: Added support         |      | autonum: Added. . . . .                    | 673           |
| for tocdata. . . . .                     | 529  | changelayout: Added. . . . .               | 705           |
| \framebox: Fix: Handle paren arg. . .    | 602  | changes: Updated to v3.1.2. . . .          | 706           |
| \hypertoc: Added support for             |      | inputtrc: Added. . . . .                   | 871           |
| tocdata. . . . .                         | 530  | mathtools: Added. . . . .                  | 931           |
| \hypertocfloat: Added support for        |      | metalogo: Added. . . . .                   | 950           |
| tocdata. . . . .                         | 531  | metalogo: Used in print mode. . . .        | 949           |

|                                             |          |                                            |          |
|---------------------------------------------|----------|--------------------------------------------|----------|
| textcomp: Fix for                           |          | \hypertoc: Fix: References for xr,         |          |
| \textinterrobang. . . . .                   | 1135     | xr-hyper. . . . .                          | 529      |
| textpos: Added optional arg to              |          | \hypertocfloat: Fix: References for        |          |
| textblock. . . . .                          | 1138     | xr, xr-hyper. . . . .                      | 531      |
| xunicode: Fix for                           |          | \lgweight: nfssect-cfr: Added. . . . .     | 611      |
| \textinterrobang. . . . .                   | 1222     | \paragraph: Added support for              |          |
| AMS environments: Refactored. . . . .       | 653      | hypbmsec. . . . .                          | 406      |
| Ensure vector font. . . . .                 | 222      | \part: Added support for hypbmsec. . . . . | 405      |
| File: lwarp_mathjax.txt: Loads              |          | \section: Added support for                |          |
| autoload-all.js extension. . . . .          | 316      | hypbmsec. . . . .                          | 406      |
| File: lwarp_mathjax.txt: Updated            |          | \subparagraph: Added support for           |          |
| to MATHJAX v2.7.5. . . . .                  | 316      | hypbmsec. . . . .                          | 406      |
| Logs: Improved for metalogox,               |          | \subsection: Added support for             |          |
| lateximages. . . . .                        | 624      | hypbmsec. . . . .                          | 406      |
| LWR@nestspan: Improved minipage,            |          | \subsubsection: Added support for          |          |
| \parbox inside a span. . . . .              | 355      | hypbmsec. . . . .                          | 406      |
| v0.71                                       |          | \texteb: nfssect-cfr: Added. . . . .       | 606      |
| \@mpfootnotetext: Improved HTML             |          | \textlg: nfssect-cfr: Added. . . . .       | 607      |
| formatting. . . . .                         | 377      | \textulc: fontaxes: Added. . . . .         | 608      |
| Reduced underfull \hbox warnings. . . . .   | 377      | \ulcshape: fontaxes: Added. . . . .        | 612      |
| \LWR@closeparagraph: Flush left             |          | General: 2019/06/08 . . . . .              | 1        |
| captions. . . . .                           | 365      | lwarp.css: Added backnaur. . . . .         | 273      |
| \LWR@closetabledatcell: Fix:                |          | lwarp.css: Removed unneeded                |          |
| Tabular par tags. . . . .                   | 447, 448 | support for \sishape, \textsi. . . . .     | 273      |
| \LWR@stoppars: Reduced underfull            |          | backnaur: Added. . . . .                   | 676      |
| \hbox warnings. . . . .                     | 368      | boxedminipage2e: Added support             |          |
| \expandcolspec: Added support for           |          | for lateximages. . . . .                   | 693      |
| tabular '*' column. . . . .                 | 459      | changes: Fix references for xr,            |          |
| General: 2019/04/29 . . . . .               | 1        | xr-hyper. . . . .                          | 706      |
| caption: Reduced underfull \hbox            |          | fontaxes: Added. . . . .                   | 610, 814 |
| warnings. . . . .                           | 700      | gloss: Fix references for xr,              |          |
| chemfig: Updated to v1.4. . . . .           | 709      | xr-hyper. . . . .                          | 831      |
| endfloat: Updated for v2.7. . . . .         | 762      | hypbmsec: Added. . . . .                   | 853      |
| lwarp-common-multimedia:                    |          | minibox: Added. . . . .                    | 954      |
| Added. . . . .                              | 1257     | nfssect-cfr: Added. . . . .                | 983      |
| media9: Added. . . . .                      | 947      | nomencl: Fix references for xr,            |          |
| movie15: Added. . . . .                     | 963      | xr-hyper. . . . .                          | 992      |
| multimedia: Added. . . . .                  | 967      | pdfcrypt: Added. . . . .                   | 1018     |
| textpos: Updated for v1.9.1. . . . .        | 1138     | shapepar: Added. . . . .                   | 1066     |
| lwarpmk: If wrong lwarpmk.conf              |          | slantsc: Added. . . . .                    | 1090     |
| version, or wrong OS, displays the          |          | soulutf8: Fix: Loads soul. . . . .         | 1093     |
| print command to recompile. . . . .         | 320      | tabfigures: Added. . . . .                 | 1122     |
| Docs: Error testing. . . . .                | 195      | xr-hyper: Added. . . . .                   | 1220     |
| quotation: Fix: blockquotation tag. . . . . | 427      | xr: Added. . . . .                         | 1219     |
| v0.72                                       |          | zhlineskip: Updated to v1.0e. . . . .      | 1224     |
| \LWR@newautopagelabel: Fix:                 |          | Use \LWR@formatted for                     |          |
| References for xr, xr-hyper. . . . .        | 385      | \bfseries, etc. . . . .                    | 262, 610 |
| \LWR@printmccoldata: Fix:                   |          | v0.73                                      |          |
| \multicolumn parameters. . . . .            | 481      | \@include: Fix: \newpage instead of        |          |
| \LWR@restoreorigformatting: Use             |          | \clearpage. . . . .                        | 252      |
| \LWR@formatted for \bfseries,               |          | \HTMLtitle: Added default title if         |          |
| etc. . . . .                                | 542      | none specified. . . . .                    | 371      |
| \chapter: Added support for                 |          | \LWR@LwarpStart: Fix: Empty                |          |
| hypbmsec. . . . .                           | 405      | header/footer. . . . .                     | 412      |
| \ebweight: nfssect-cfr: Added. . . . .      | 611      |                                            |          |

|                                                                                          |           |                                                                                                                   |            |
|------------------------------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------|------------|
| <code>\LWR@addbaselinemarker</code> : Improved warning messages. . . . .                 | 549       | <code>intopdf</code> : Updated to v0.2.1. . . . .                                                                 | 872        |
| <code>\LWR@createfooter</code> : Fix: Empty header/footer. . . . .                       | 391       | <code>listings</code> : Fix: Paragraph tags. . . . .                                                              | 903        |
| <code>\LWR@descitem</code> : Fix: HTML tags. . . . .                                     | 438       | <code>lwarp-common-multimedia</code> : Fix: No size for audio file. . . . .                                       | 1258, 1259 |
| <code>\LWR@forceemptyline</code> : Added. . . . .                                        | 225       | <code>lwarp-common-multimedia</code> : Fix: Paragraph tags. . . . .                                               | 1261       |
| <code>\LWR@gsavebox</code> : Added global save boxes. . . . .                            | 226       | <code>lwarp-patch-komascript</code> : Fix for captions. . . . .                                                   | 1227       |
| <code>\LWR@htmlElementclass</code> : Vertical space. . . . .                             | 359       | <code>lwarp-patch-memoir</code> : Added <code>\book</code> . . . . .                                              | 1235       |
| <code>\LWR@htmlElementclassline</code> : Vertical space. . . . .                         | 359       | <code>lwarp-patch-memoir</code> : Fix for <code>\frontmatter*</code> and <code>\mainmatter*</code> . . . . .      | 1235       |
| <code>\LWR@indentHTMLtwo</code> : Added. . . . .                                         | 354       | <code>lyluatex</code> : Added. . . . .                                                                            | 916        |
| <code>\LWR@indexitem</code> : Fix: Avoid empty <code>&lt;span&gt;</code> . . . . .       | 533       | <code>musicography</code> : Updated to 2019/05/28. Now supports <code>lateximages</code> . . . . .                | 972        |
| <code>\LWR@indexsubitem</code> : Fix: Avoid empty <code>&lt;span&gt;</code> . . . . .    | 533       | <code>quotchap</code> : Fix: Paragraph tags. . . . .                                                              | 1038       |
| <code>\LWR@indexsubsubitem</code> : Fix: Avoid empty <code>&lt;span&gt;</code> . . . . . | 533       | <code>quotchap</code> : Updated to v1.2. . . . .                                                                  | 1037       |
| <code>\LWR@newhtmlfile</code> : Fix: Empty header/footer. . . . .                        | 394       | <code>quoting</code> : Fix: Paragraph tags. . . . .                                                               | 1038       |
| <code>\LWR@nullfonts</code> : Fix: <code>\hspace</code> in sectioning file name. . . . . | 546       | <code>scrxextend</code> : Fix: Paragraph tags. . . . .                                                            | 1054, 1055 |
| <code>\LWR@titlingmaketitle</code> : titling: Fix: Paragraph tags. . . . .               | 424, 1160 | <code>stackengine</code> : Added. . . . .                                                                         | 1097       |
| Fix: Paragraph tags. . . . .                                                             | 424       | <code>threeparttable</code> : Added <code>measuredfigure</code> . . . . .                                         | 1147       |
| <code>\attribution</code> : Fix: Paragraph tags. . . . .                                 | 426       | <code>tocdata</code> : Honors <code>\tocdataformat</code> . . . . .                                               | 1164       |
| <code>\color</code> : <code>xcolor</code> : Added HTML support. . . . .                  | 1206      | <code>tocdata</code> : Improved formatting. . . . .                                                               | 1164       |
| <code>\fboxBlock</code> : Fix: Paragraph tags. . . . .                                   | 603       | <code>tocdata</code> : Updated to v2.03. . . . .                                                                  | 1164       |
| <code>\hspace</code> : Fix: Avoid empty <code>&lt;span&gt;</code> . . . . .              | 620       | <code>versonotes</code> : Updated to v0.4. . . . .                                                                | 1193       |
| <code>\l@book</code> : Added <code>\book</code> for memoir. . . . .                      | 531       | <code>vwcol</code> : Fix: Paragraph tags. . . . .                                                                 | 1195       |
| <code>\maketitle</code> : titling: Fix: Paragraph tags. . . . .                          | 1159      | <code>xy</code> : Fix for <code>\xybox</code> . . . . .                                                           | 1223       |
| Fix: Paragraph tags. . . . .                                                             | 423       | <code>xy</code> : Improved <code>xy</code> , reverted <code>\xymatrix</code> , for <code>qcicuit</code> . . . . . | 1223       |
| <code>\marginparBlock</code> : Fix: Paragraph tags. . . . .                              | 379       | Added <code>\book</code> for memoir. . . . .                                                                      | 338, 352   |
| <code>\postbookname</code> : Added <code>\book</code> for memoir. . . . .                | 404       | AMS environments: Fix: <code>alt</code> tags. . . . .                                                             | 653        |
| <code>\printthanks</code> : Fix: Paragraph tags. . . . .                                 | 419       | AMS environments: Fix: Paragraph tags. . . . .                                                                    | 653, 654   |
| <code>\rule</code> : Fix: Avoid empty <code>&lt;span&gt;</code> . . . . .                | 623       | Numbered HTML entity used for text dollar. . . . .                                                                | 549        |
| General: 2019/07/11 . . . . .                                                            | 1         | <code>tabular</code> : Fix and warning for tabular inside a <code>&lt;span&gt;</code> . . . . .                   | 497        |
| <code>lwarp.css</code> : Added <code>\book</code> for memoir. . . . .                    | 273       | <code>LWR@blocktextcurrentfont</code> : Fix: Paragraph tags. . . . .                                              | 610        |
| <code>lwarp.css</code> : Improved <code>pkgtoctdata</code> formatting. . . . .           | 273       | <code>LWR@nestspan</code> : Fix: quote, quotation inside a span. . . . .                                          | 355        |
| <code>lwarp_formal.css</code> : Added <code>\book</code> for memoir. . . . .             | 305, 310  | v0.74                                                                                                             |            |
| <code>boxedminipage2e</code> : Fix: Paragraph tags. . . . .                              | 693       | <code>\@ensuredmath</code> : Add <code>\ThisAltText</code> . . . . .                                              | 560        |
| <code>epigraph</code> : Fix: Paragraph tags. . . . .                                     | 770       | <code>\AltTextClose</code> : Added. . . . .                                                                       | 547        |
| <code>fancyvrb</code> : Fix: Nested <code>&lt;div&gt;/&lt;pre&gt;</code> . . . . .       | 790, 793  | <code>\AltTextOpen</code> : Added. . . . .                                                                        | 547        |
| <code>fancyvrb</code> : <code>Btrivlist</code> : Fixed paragraph tags. . . . .           | 784       | <code>\ImageAltText</code> : Added. . . . .                                                                       | 547        |
|                                                                                          |           | <code>\LWR@ThisAltText</code> : Add <code>\ThisAltText</code> . . . . .                                           | 547        |
|                                                                                          |           | <code>\LWR@addlinktitle</code> : Added. . . . .                                                                   | 508        |
|                                                                                          |           | <code>\LWR@doequation</code> : Add <code>\ThisAltText</code> . . . . .                                            | 566        |

|                                                                                                                      |               |
|----------------------------------------------------------------------------------------------------------------------|---------------|
| <code>\LWR@doubledollar</code> : Add                                                                                 |               |
| <code>\ThisAltText</code> . . . . .                                                                                  | 558           |
| <code>\LWR@lateximage@oneimage</code> : Factored from lateximage. . . . .                                            | 576           |
| <code>\LWR@lateximage@oneimageb</code> : Factored from lateximage. . . . .                                           | 576           |
| <code>\LWR@setcurrentfont</code> : Factored. . . . .                                                                 | 548           |
| <code>\LWR@singledollar</code> : Add                                                                                 |               |
| <code>\ThisAltText</code> . . . . .                                                                                  | 559           |
| <code>\LWR@singledollarmeasure</code> : Fix: Font control. . . . .                                                   | 551           |
| <code>\LWR@subinlineimage</code> : Add                                                                               |               |
| <code>\ThisAltText</code> . . . . .                                                                                  | 514           |
| <code>\LWR@subsingledollar</code> : Add                                                                              |               |
| <code>\ThisAltText</code> . . . . .                                                                                  | 557           |
| <code>\LWR@subsingledollarsvg</code> : Adds star argument for lateximage. . . . .                                    | 554           |
| <code>\LateximageFontScale</code> : Adjusted svg math font scaling default to 1. . . . .                             | 574           |
| <code>\MathImageAltText</code> : Renamed from <code>\mathimage</code> . . . . .                                      | 547           |
| <code>\PackageDiagramAltText</code> : Renamed from <code>\packagediagramname</code> . . . . .                        | 547           |
| <code>\ThisAltText</code> : Add <code>\ThisAltText</code> . . . . .                                                  | 547           |
| <code>\hspace</code> : Ignore negative space. . . . .                                                                | 619           |
| General: 2019/09/02 . . . . .                                                                                        | 1             |
| <code>lwrap.css</code> : Added <code>lyluatex</code> . . . . .                                                       | 273           |
| <code>amsmath</code> : Add <code>\ThisAltText</code> . . . . .                                                       | 655           |
| <code>forest</code> : alt text. . . . .                                                                              | 818           |
| <code>geometry</code> : Remembers user's geometry. . . . .                                                           | 829           |
| <code>graphics</code> : Add                                                                                          |               |
| <code>\ThisAltText</code> . . . . .                                                                                  | 836, 842, 843 |
| <code>lyluatex</code> : Adapts to user's geometry. . . . .                                                           | 917           |
| <code>lyluatex</code> : Preserves left margin. . . . .                                                               | 917           |
| <code>lyluatex</code> : Rename                                                                                       |               |
| <code>\lyluateximaname</code> . . . . .                                                                              | 916           |
| <code>lyluatex</code> : Split system images, assign class. . . . .                                                   | 917           |
| <code>mhchem</code> : Modified for new lateximage. . . . .                                                           | 951           |
| <code>pdfpages</code> : Adjust to user's paper size. . . . .                                                         | 1021          |
| <code>stackengine</code> : alt tags. . . . .                                                                         | 1097          |
| <code>struktex</code> : alt text. . . . .                                                                            | 1111          |
| <code>tikz</code> : Added alt text. . . . .                                                                          | 1149          |
| <code>lwrapmk</code> : <code>lwrapmk clean</code> removes add'l files. . . . .                                       | 320           |
| <code>lwrapmk</code> : <code>lwrapmk epstopdf</code> and <code>pdfsvgs</code> honor directories. . . . .             | 320           |
| Remembers user's geometry. . . . .                                                                                   | 240           |
| <code>lateximage</code> : Add <code>\ThisAltText</code> . . . . .                                                    | 582           |
| Added second starred argument. . . . .                                                                               | 577, 582      |
| Improved alt text. . . . .                                                                                           | 578           |
| New syntax for                                                                                                       |               |
| <code>\LWR@subinlineimage</code> . . . . .                                                                           | 581           |
| <code>eqnarray</code> : Add <code>\ThisAltText</code> . . . . .                                                      | 571           |
| <code>LWR@displaymathother</code> : Uses                                                                             |               |
| <code>\MathImageAltText</code> . . . . .                                                                             | 560           |
| <code>LWR@equationother</code> : Uses                                                                                |               |
| <code>\MathImageAltText</code> . . . . .                                                                             | 561           |
| v0.75                                                                                                                |               |
| <code>\normalcolor</code> : <code>xcolor</code> : Added for HTML. . . . .                                            | 1204          |
| General: 2019/09/23 . . . . .                                                                                        | 1             |
| <code>lwrap.css</code> : Improved                                                                                    |               |
| <code>marginblock</code> . . . . .                                                                                   | 273           |
| <code>keyfloat</code> : Fix: <code>\normalcolor</code> . . . . .                                                     | 877           |
| <code>wrapfig</code> : Fix for <code>\linewidth</code> . . . . .                                                     | 1200          |
| <code>wrapfig</code> : Fix for width. . . . .                                                                        | 1200          |
| <code>minipage</code> : Fix: <code>\linewidth</code> . . . . .                                                       | 598           |
| v0.76                                                                                                                |               |
| General: 2019/10/08 . . . . .                                                                                        | 1             |
| <code>lwrap.css</code> : Fix for small caps. . . . .                                                                 | 273           |
| <code>acro</code> : Updated for v2.10. . . . .                                                                       | 643           |
| <code>xr-hyper</code> : Updated for v6.1. . . . .                                                                    | 1220          |
| <code>xr</code> : Updated for v5.05 and <code>xr-hyper</code> v6.1. . . . .                                          | 1219          |
| Docs expanded: Multiple projects. . . . .                                                                            | 95            |
| File: <code>lwrap_mathjax.txt</code> : Updated to MATHJAX v2.7.6. . . . .                                            | 316           |
| v0.77                                                                                                                |               |
| General: 2019/10/15 . . . . .                                                                                        | 1             |
| <code>booktabs</code> : Updated to v1.6180339. . . . .                                                               | 691           |
| <code>chemformula</code> : Updated to v4.15. . . . .                                                                 | 712           |
| v0.78                                                                                                                |               |
| <code>\LWR@linkcatcodes</code> : <code>babel-french</code> :                                                         |               |
| Fix: Hyperlinks. . . . .                                                                                             | 511           |
| Factored. . . . .                                                                                                    | 511           |
| <code>\LWR@linkmediacatcodes</code> :                                                                                |               |
| <code>babel-french</code> : Fix: Hyperlinks. . . . .                                                                 | 512           |
| Factored. . . . .                                                                                                    | 512           |
| <code>\LWR@nullifyNoAutoSpacing</code> :                                                                             |               |
| <code>babel-french</code> : Fix: Hyperlinks. . . . .                                                                 | 497           |
| <code>\LWR@subhyperrefclass</code> : Remove extra space. . . . .                                                     | 512           |
| <code>\normalfont</code> : Uses <code>\LWR@formatted</code> . . . . .                                                | 613           |
| General: 2019/11/07 . . . . .                                                                                        | 1             |
| <code>accessibility</code> : Added. . . . .                                                                          | 641           |
| <code>babel-french</code> : Fix: Hyperlinks. . . . .                                                                 | 353           |
| <code>caption</code> : Added warning regarding passing options. . . . .                                              | 699           |
| <code>filecontents</code> : Fix to overwrite existing files using new <code>filecontents</code> environment. . . . . | 243           |
| <code>geometry</code> : Cleaner option handling. . . . .                                                             | 829           |
| <code>graphics</code> : Fix: alt tag expansion. . . . .                                                              | 842           |

|                                                                                  |            |                                                            |          |
|----------------------------------------------------------------------------------|------------|------------------------------------------------------------|----------|
| lwarp-common-multimedia: Fix<br>links with new LaTeX<br>kernel. . . . .          | 1258, 1259 | ar: Added MATHJAX emulation. . .                           | 663      |
| titlesec: Fix for \titleclass. . .                                               | 1155       | awesomebox: Added. . . . .                                 | 674      |
| v0.79                                                                            |            | babel and polyglossia: Added info<br>messages. . . . .     | 632      |
| \CustomizeMathJax: Fix: Sanitize for<br>HTML. . . . .                            | 388        | bigdelim: Added MATHJAX<br>emulation. . . . .              | 687      |
| \LWR@ProvidesPackagePass: Fix:<br>catoptions. . . . .                            | 249        | bigstrut: Added MATHJAX<br>emulation. . . . .              | 688      |
| \LWR@checkloadfilename: Prevented<br>bxcjkatype, hangul. . . . .                 | 246        | bm: Added. . . . .                                         | 689      |
| \LWR@closetabledatcell: Fix:<br>Nested tabulars. . . . .                         | 448        | booktabs: Added MATHJAX<br>emulation. . . . .              | 692      |
| \LWR@customizeMathJax: MathJax:<br>Hide definitions. . . . .                     | 390        | booktabs: Fix for memoir with<br>lateximage. . . . .       | 496, 691 |
| \LWR@earlyloadnever: Factored. . .                                               | 209        | braket: Added. . . . .                                     | 694      |
| \LWR@forcenewautoidanchor:<br>Factored. . . . .                                  | 518        | floatflt: Improved width control.                          | 803      |
| \LWR@mathjaxwarn: Warn if using<br>packages not supported by<br>MATHJAX. . . . . | 633        | fontawesome5: Supports font size,<br>color. . . . .        | 813      |
| \LWR@parseaftercolumn: Remove<br>outermost braces. . . . .                       | 455        | fontawesome: Refactored with fix<br>for \FAtthree. . . . . | 812      |
| \LWR@parseatcolumn: Remove<br>outermost braces. . . . .                          | 453        | fontawesome: Supports font size,<br>color. . . . .         | 812      |
| \LWR@parsebangcolumn: Remove<br>outermost braces. . . . .                        | 454        | geometry: Also save \textwidth,<br>\textheight. . . . .    | 241      |
| \LWR@parsebeforecolumn: Remove<br>outermost braces. . . . .                      | 454        | graphics: Factored from<br>\LWR@includegraphicsb. . .      | 839, 840 |
| \LWR@setexparray: Fix: Nested<br>tabulars. . . . .                               | 341        | graphics: Fix for negative angles.                         | 837      |
| \LWR@singledollarmeasure:<br>Factored. . . . .                                   | 551        | ifpdf, ifptex: Provided by iftex. . .                      | 206      |
| \LWR@subHTMLsanitize: Fix: \&.<br>Factored. . . . .                              | 386        | ltablex: Fix: Require longtable. . .                       | 909      |
| \LWR@subsingledollarsvg: Adjust for<br>unknown size. . . . .                     | 554        | ltxtable: Fix: Required packages. . .                      | 910      |
| Factored. . . . .                                                                | 552        | luatex85: Removed. . . . .                                 | 206      |
| \LWR@tabularendofline: Fix: Nested<br>tabulars. . . . .                          | 452        | mathtools: Added MATHJAX<br>emulation. . . . .             | 931      |
| \captionlistentry: Fix: Duplicate<br>auto-id. . . . .                            | 522        | multirow: Add: MATHJAX<br>emulation. . . . .               | 971      |
| \macrotoctname: Added. . . . .                                                   | 227        | multirow: Fix: Centered vertical<br>alignment. . . . .     | 969      |
| \makebox: Fix: Adjust for virtual page<br>size. . . . .                          | 601        | niceframe: Fix: Adjust for virtual<br>page size. . . . .   | 990      |
| \multicolumnrow: multirow: Fix:<br>Nested tabulars. . . . .                      | 971        | parallel: Added. . . . .                                   | 1010     |
| \noalign: Fix: Nested tabulars. . .                                              | 496        | parcolumns: Added. . . . .                                 | 1012     |
| General: 2020/02/01 . . . . .                                                    | 1          | pdfcolfoot: Added. . . . .                                 | 1016     |
| MATHJAX: Additional macros. . .                                                  | 389        | pdfcolmk: Added. . . . .                                   | 1016     |
| lwarp.css: Fix: Nested tabulars.                                                 | 273        | pdfcolparallel: Added. . . . .                             | 1016     |
| amsmath: Added MATHJAX<br>emulation. . . . .                                     | 656        | pdfcolparcolumns: Added. . . . .                           | 1017     |
| arydshln: Added MATHJAX<br>emulation. . . . .                                    | 666        | pdfcol: Added. . . . .                                     | 1015     |
|                                                                                  |            | physics: Added. . . . .                                    | 1025     |
|                                                                                  |            | siunitx: Fix: \square, \cubed. . .                         | 1084     |
|                                                                                  |            | siunitx: Improved MATHJAX. . .                             | 1082     |
|                                                                                  |            | slashed: Added. . . . .                                    | 1090     |
|                                                                                  |            | steinmetz: Added. . . . .                                  | 1110     |
|                                                                                  |            | svg: Added. . . . .                                        | 1120     |
|                                                                                  |            | transparent: Supports<br>lateximages. . . . .              | 1175     |
|                                                                                  |            | unicode-math: Added. . . . .                               | 1184     |
|                                                                                  |            | widetable: Added. . . . .                                  | 1198     |

|                                         |               |                                     |            |
|-----------------------------------------|---------------|-------------------------------------|------------|
| witharrows: Added. . . . .              | 1198          | mathcomp: Added. . . . .            | 924        |
| xcolor: Fix: Nested                     |               | mathdots: Added. . . . .            | 926        |
| tabulars. . . . .                       | 1210, 1211    | mathfixs: Added. . . . .            | 927        |
| xltabular: Fix: Require ltablex. . .    | 1216          | mismath: Added. . . . .             | 957        |
| xurl: Updated to v0.08. . . . .         | 1223          | nccmath: Added. . . . .             | 978        |
| AMS environments: Fix: Nested. . .      | 654           | noitcrul: Added. . . . .            | 991        |
| Factored to                             |               | pdfcomment: Added MATHJAX           |            |
| \LWR@setvirtualpage. . . . .            | 807, 841, 881 | emulation. . . . .                  | 1018       |
| Fix: Use newfloat instead of float. .   | 808           | resize: Added MATHJAX               |            |
| Fix: Use full \linewidth. . . . .       | 807           | emulation. . . . .                  | 1045       |
| Remember HTML font size. . . . .        | 616           | rmathbr: Added. . . . .             | 1047       |
| tabular: colortbl: Fix: Nested          |               | subsupscripts: Added. . . . .       | 1118       |
| tabulars. . . . .                       | 499           | tagpdf: Added. . . . .              | 1124       |
| Fix: Nested tabulars. . . . .           | 501           | unicode-math: Improved              |            |
| warpMathJax: Added. . . . .             | 238           | MATHJAX. . . . .                    | 1184, 1185 |
| lateximage: Improved \linewidth. . .    | 579           | url: Creates hyperlinks. . . . .    | 1190       |
| minipage: Fix: \linewidth frame         |               | xfrac: Added MATHJAX emulation. . . | 1216       |
| padding. . . . .                        | 598           | AMS environments: Fix: Centering    |            |
| Fix: Adjust for virtual page size. .    | 597           | starred envs. . . . .               | 654        |
| fminipage: Fix: Adjust for virtual page |               | Improved math, displaymath. . .     | 560        |
| size. . . . .                           | 604           | Prevented formula, shadethm,        |            |
| LWR@setvirtualpage: Factored. . . .     | 596           | slashbox. . . . .                   | 209        |
| v0.80                                   |               | lateximage: Fix: Rule color in      |            |
| \CustomizeMathJax: Fix: Made            |               | lateximage. . . . .                 | 580        |
| \@onlypreamble. . . . .                 | 388           | fcolorminipage: Made robust. . . .  | 592        |
| Warn of slow compile. . . . .           | 388           | eqnarray: Fix: eqnarray*. . . . .   | 571        |
| \LWR@checkloadfilename: Prevented       |               | v0.81                               |            |
| formula, shadethm, slashbox. . .        | 246           | \LWR@addbaselinemarker: Improved    |            |
| \LWR@infoprocessingmathjax: Add:        |               | warning messages. . . . .           | 549        |
| Info message. . . . .                   | 389           | \LWR@checkloadfilename: Prevented   |            |
| \LWR@restoreorigformatting:             |               | statex. . . . .                     | 246        |
| Improved math, displaymath. . .         | 543           | \LWR@replacestrings: Added. . . .   | 385        |
| \fcolorbox: Made robust. . . . .        | 591           | \LWR@subHTMLsanitize: Faster. . .   | 386        |
| \fcolorboxBlock: Made robust. . .       | 591           | \textcolor: xcolor: \textcolor:     |            |
| \includegraphics: Made robust. . .      | 843           | Spurious space. . . . .             | 1206       |
| General: 2020/02/19 . . . . .           | 1             | General: 2020/03/04 . . . . .       | 1          |
| \textbf and related: Use HTML           |               | lwarp.css: Added nolbreaks. . .     | 273        |
| series, etc. . . . .                    | 606           | DotArrow: Added. . . . .            | 754        |
| accessibility: Added MATHJAX            |               | Slunits: Improved \unit. Fixed in   |            |
| emulation. . . . .                      | 641           | math mode. Added MATHJAX            |            |
| accsupp: Added MATHJAX                  |               | emulation. . . . .                  | 1072       |
| emulation. . . . .                      | 642           | axessibility: Added MATHJAX         |            |
| autobreak: Added. . . . .               | 672           | emulation. . . . .                  | 675        |
| biblatex: Creates hyperlinks. . . .     | 682           | axessibility: Updated to 2020/01/08 |            |
| centernot: Added. . . . .               | 704           | version. . . . .                    | 675        |
| chemmacros: Updated to                  |               | colonequals: Added. . . . .         | 742        |
| v5.10. . . . .                          | 723, 731      | decimal: Added. . . . .             | 751        |
| extarrows: Added. . . . .               | 780           | dotlessi: Added. . . . .            | 754        |
| fewerfloatpages: Added. . . . .         | 797           | econometrics: Added. . . . .        | 758        |
| fouridx: Added. . . . .                 | 819           | engtlc: Added. . . . .              | 765        |
| gensymb: Added. . . . .                 | 828           | gridset: Updated to v0.3. . . . .   | 847        |
| ghsystem: Added. . . . .                | 829           | hyperref: Added                     |            |
| gmeometric: Requires geometry. . .      | 833           | \pdfstringdefDisableCommands. .     | 862        |
| hhline: Added. . . . .                  | 852           | luamplib: Added. . . . .            | 911        |
| leftidx: Added. . . . .                 | 890           | multiobjective: Added. . . . .      | 967        |

|                                                                                 |            |                                                                                                                                      |            |
|---------------------------------------------------------------------------------|------------|--------------------------------------------------------------------------------------------------------------------------------------|------------|
| nolbreaks: Added. . . . .                                                       | 991        | lwrap-patch-memoir: Updated for<br>new sizes. . . . .                                                                                | 1231       |
| physunits: Added. . . . .                                                       | 1026       | lwrap-patch-memoir:<br>Updated. . . . .                                                                                              | 1234, 1235 |
| returntograd: Added. . . . .                                                    | 1047       | physunits: Updated to v1.0.4. . .                                                                                                    | 1026       |
| stackrel: Added. . . . .                                                        | 1099       |                                                                                                                                      |            |
| statex2: Added. . . . .                                                         | 1100       |                                                                                                                                      |            |
| statmath: Added. . . . .                                                        | 1109       |                                                                                                                                      |            |
| <i>lwrapmk</i> : Improved error if in <i>lwrap</i><br>source directory. . . . . | 320        |                                                                                                                                      |            |
| Prevented <i>statex</i> . . . . .                                               | 209        |                                                                                                                                      |            |
| v0.82                                                                           |            |                                                                                                                                      |            |
| \LWR@disablepinyin: Added. . . . .                                              | 225        |                                                                                                                                      |            |
| \LWR@doequation: MATHJAX:<br>Improved footnotes. . . . .                        | 566        |                                                                                                                                      |            |
| \LWR@syncmathjax: Removed <par><br>tags. . . . .                                | 562        |                                                                                                                                      |            |
| General: 2020/03/25 . . . . .                                                   | 1          |                                                                                                                                      |            |
| MATHJAX: Improved footnotes. 389, 566                                           |            |                                                                                                                                      |            |
| amsmath: Fixed: \intertext for<br>MATHJAX. . . . .                              | 656        |                                                                                                                                      |            |
| chemfig: Updated to v1.5. . . . .                                               | 709        |                                                                                                                                      |            |
| draftwatermark: Updated to v2.0. . . . .                                        | 755        |                                                                                                                                      |            |
| endnotes: Added MATHJAX<br>emulation. . . . .                                   | 764        |                                                                                                                                      |            |
| endnotes: Fix: Mark in print mode. . . . .                                      | 764        |                                                                                                                                      |            |
| etoc: Added. . . . .                                                            | 777        |                                                                                                                                      |            |
| luatexko: Added. . . . .                                                        | 912        |                                                                                                                                      |            |
| lwrap-patch-memoir: Supports<br>tocvsec2. . . . .                               | 1235, 1239 |                                                                                                                                      |            |
| marginnote: Added MATHJAX<br>emulation. . . . .                                 | 922        |                                                                                                                                      |            |
| marginnote: Fix: Neutralize in print<br>mode. . . . .                           | 922        |                                                                                                                                      |            |
| nccfoots: Added MATHJAX<br>emulation. . . . .                                   | 978        |                                                                                                                                      |            |
| pagenote: Added MATHJAX<br>emulation. . . . .                                   | 1009       |                                                                                                                                      |            |
| parnotes: Added MATHJAX<br>emulation. . . . .                                   | 1014       |                                                                                                                                      |            |
| sidenotes: Added MATHJAX<br>emulation. . . . .                                  | 1070       |                                                                                                                                      |            |
| soul: Fixed: \<. . . . .                                                        | 1091       |                                                                                                                                      |            |
| syntonly: Added \nopages@. . . . .                                              | 1122       |                                                                                                                                      |            |
| syntonly: Added to<br>\LWR@loadafter. . . . .                                   | 210        |                                                                                                                                      |            |
| ulem: Fixed: \dashuline. . . . .                                                | 1180       |                                                                                                                                      |            |
| xpinyin: Added full pinyin<br>support. . . . .                                  | 1218       |                                                                                                                                      |            |
| v0.83                                                                           |            |                                                                                                                                      |            |
| General: 2020/03/27 . . . . .                                                   | 1          |                                                                                                                                      |            |
| lwrap-patch-memoir: Fixed<br>framed. . . . .                                    | 1230       |                                                                                                                                      |            |
| lwrap-patch-memoir: Fixed:<br>\specialindex. . . . .                            | 1252       |                                                                                                                                      |            |
| lwrap-patch-memoir: No longer<br>requires subfigure. . . . .                    | 1230       |                                                                                                                                      |            |
|                                                                                 |            | \@currentHref: backref: Fixed from<br>lwrap v0.72 changes. . . . .                                                                   | 511        |
|                                                                                 |            | \@currentlabelname: Default name<br>for previous/next links. . . . .                                                                 | 503        |
|                                                                                 |            | \@fnsymbol: \LWR@formatted, fixed<br>double bar. . . . .                                                                             | 422        |
|                                                                                 |            | \@makecaption: caption now<br>optional. . . . .                                                                                      | 519        |
|                                                                                 |            | Warn inside a <span>. . . . .                                                                                                        | 519        |
|                                                                                 |            | \@textsubscript: Use<br>\LWR@formatted. No longer<br>\AtBeginDocument. . . . .                                                       | 614        |
|                                                                                 |            | \@textsuperscript: Use<br>\LWR@formatted. . . . .                                                                                    | 614        |
|                                                                                 |            | \@xdlbfloat: caption now optional. . . . .                                                                                           | 517        |
|                                                                                 |            | \AddSubTitlePublished: Added<br>\subtitle, \published for<br>koma*. . . . .                                                          | 425        |
|                                                                                 |            | Fixed \subtitle, \prints subtitle<br>if no titling. . . . .                                                                          | 425        |
|                                                                                 |            | \HTMLFirstPageBottom: Added<br>\FirstPageBottom. . . . .                                                                             | 369        |
|                                                                                 |            | \LWR@LwrapEnd: Added prev/next<br>links. . . . .                                                                                     | 414        |
|                                                                                 |            | Fix: No footer for EPUB . . . . .                                                                                                    | 414        |
|                                                                                 |            | \LWR@LwrapStart: Added prev/next<br>links. . . . .                                                                                   | 412        |
|                                                                                 |            | \LWR@createfooter: Added<br>\FirstPageBottom. . . . .                                                                                | 391        |
|                                                                                 |            | \LWR@domulticolumn: Fix:<br>Multicolumn style. . . . .                                                                               | 484        |
|                                                                                 |            | \LWR@excludecomment: Independent<br>cut files. . . . .                                                                               | 237        |
|                                                                                 |            | \LWR@filenamenoblanks: Fix: Dashes<br>in filename. . . . .                                                                           | 384        |
|                                                                                 |            | \LWR@filestart: Improved HTML<br>title. . . . .                                                                                      | 408        |
|                                                                                 |            | \LWR@floatbegin: Warn inside a<br><span>. . . . .                                                                                    | 515        |
|                                                                                 |            | \LWR@forcenewautoidanchor: <par><br>handling. . . . .                                                                                | 518        |
|                                                                                 |            | \LWR@htmlsectionfilename: Fix:<br>Sections called "Index" or "index"<br>have -0 appended to their<br>filenames if no prefix. . . . . | 345        |
|                                                                                 |            | \LWR@new@label: Removed optional<br>args. . . . .                                                                                    | 507        |
|                                                                                 |            | \LWR@newhtmlfile: Added prev/next<br>links. . . . .                                                                                  | 392, 394   |

|                                                                        |     |                                                                           |          |
|------------------------------------------------------------------------|-----|---------------------------------------------------------------------------|----------|
| <code>\LWR@nullfonts</code> : Add'l symbols. . . . .                   | 544 | <code>epigraph</code> : Added print mode. . . . .                         | 770      |
| Factored out redefinitions. . . . .                                    | 543 | <code>fixme</code> : Added section name. . . . .                          | 799      |
| Fix: Accents. . . . .                                                  | 543 | <code>float</code> : Fix: Recursive name. . . . .                         | 802      |
| Revised <code>\texorpdfstring</code> . . . . .                         | 546 | <code>fontaxes</code> : Moved <code>sscshape</code> to core.              |          |
| <code>\LWR@section</code> : Added prev/next links. . . . .             | 403 | <code>\FilenameNullify</code> . . . . .                                   | 814      |
| Warn inside a <code>&lt;span&gt;</code> . . . . .                      | 399 | <code>lwrap-patch-memoir</code> : Creates mark                            |          |
| <code>\LWR@startpars</code> : Ignore if in                             |     | macros. . . . .                                                           | 1238     |
| <code>lateximage</code> . . . . .                                      | 366 | <code>lwrap-patch-memoir</code> : Fix:                                    |          |
| <code>\LWR@stoppars</code> : Ignore if in                              |     | <code>\label</code> . . . . .                                             | 1231     |
| <code>lateximage</code> . . . . .                                      | 367 | <code>lwrap-patch-memoir</code> : Fixed                                   |          |
| <code>\LinkNext</code> : Added prev/next links. . . . .                | 349 | <code>pagenotes</code> . . . . .                                          | 1248     |
| <code>\LinkPrevious</code> : Added prev/next                           |     | <code>lwrap-patch-memoir</code> : Improved                                |          |
| links. . . . .                                                         | 349 | <code>cleveref</code> support. . . . .                                    | 1249     |
| <code>\attribution</code> : Added print mode. . . . .                  | 426 | <code>lwrap-patch-memoir</code> : No longer                               |          |
| <code>\caption@end</code> : <code>caption</code> now optional. . . . . | 522 | requires <code>subcaption</code> . . . . .                                | 1230     |
| <code>\captionlistentry</code> : <code>caption</code> now              |     | <code>lwrap-patch-memoir</code> : No longer                               |          |
| optional. . . . .                                                      | 522 | uses <code>subcaption</code> . . . . .                                    | 1245     |
| <code>\captionof</code> : <code>caption</code> now optional. . . . .   | 523 | <code>lwrap-patch-memoir</code> : Use $\LaTeX$                            |          |
| <code>\end@dlbfloat</code> : <code>caption</code> now                  |     | captions. . . . .                                                         | 1244     |
| optional. . . . .                                                      | 517 | <code>lwrap-patch-memoir</code> : Uses                                    |          |
| <code>\linknextname</code> : Added prev/next                           |     | memoir's <code>\newcomment</code> ,                                       |          |
| links. . . . .                                                         | 348 | <code>\commentsoff</code> , <code>\commentson</code> . . . . .            | 1250     |
| <code>\linkpreviousname</code> : Added prev/next                       |     | <code>lwrap-patch-memoir</code> : <code>\contsubtop</code> ,              |          |
| links. . . . .                                                         | 348 | etc. now as-is. . . . .                                                   | 1256     |
| <code>\printthanks</code> : Fix: <code>\printthanks</code> in          |     | <code>lwrap-patch-memoir</code> : <code>caption</code> now                |          |
| print mode. . . . .                                                    | 419 | optional, removed dup caption. . . . .                                    | 1246     |
| <code>\sscshape</code> : Moved to core. . . . .                        | 613 | <code>mdframed</code> : Warn inside a <code>&lt;span&gt;</code> . . . . . | 939      |
| <code>\textssc</code> : Moved to core. . . . .                         | 609 | <code>memoir</code> : Preloads <code>xcolor</code> . . . . .              | 629      |
| <code>\textsubscript</code> : Use                                      |     | <code>nfssect-cfr</code> : Improved. . . . .                              | 983      |
| <code>\LWR@formatted</code> . No longer                                |     | <code>nfssect-cfr</code> :                                                |          |
| <code>\AtBeginDocument</code> . . . . .                                | 614 | <code>\FilenameNullify</code> . . . . .                                   | 985, 988 |
| <code>\textsuperscript</code> : Use                                    |     | <code>ntheorem</code> : Warning if <code>thref</code> . . . . .           | 995      |
| <code>\LWR@formatted</code> . . . . .                                  | 614 | <code>parcolumns</code> : Fixed: Missing                                  |          |
| <code>\theHTMLTitleSeparator</code> : Improved                         |     | <code>\colplacechunks</code> . . . . .                                    | 1012     |
| spacing for <code>xeCJK</code> . . . . .                               | 407 | <code>realscripts</code> : Added print mode. . . . .                      | 1039     |
| <code>\verbatiminput</code> : Added print mode. . . . .                | 430 | <code>realscripts</code> : Fixed starred                                  |          |
| General: 2020/04/24 . . . . .                                          | 1   | <code>\textsuperscript</code> ,                                           |          |
| $\LaTeX$ accents: Add'l symbols. . . . .                               | 264 | <code>\textsubscript</code> . . . . .                                     | 1039     |
| <code>lwrap.css</code> : Added <code>koma-*</code> subject. . . . .    | 273 | <code>realscripts</code> : Improved supersub                              |          |
| <code>lwrap.css</code> : Fix: <code>Minipage</code> tex align. . . . . | 273 | scripts. . . . .                                                          | 1039     |
| <code>lwrap.css</code> : Fix: Top nav if narrow                        |     | <code>rotfloat</code> : Fix: Requires rotating. . . . .                   | 1049     |
| window. . . . .                                                        | 273 | <code>scrextend</code> : Added <code>\titlehead</code> ,                  |          |
| <code>lwrap.css</code> : Improved <code>nfssect-cfr</code> . . . . .   | 273 | <code>\subject</code> , <code>\subtitle</code> ,                          |          |
| <code>lwrap.css</code> : Improved <code>realscripts</code> . . . . .   | 273 | <code>\published</code> . . . . .                                         | 1052     |
| abstract: Updated for memoir. . . . .                                  | 638 | <code>scrextend</code> : Updated to v3.29. . . . .                        | 1052     |
| alltt: Added print mode. . . . .                                       | 652 | <code>sidenotes</code> : <code>\sidecaption</code> not long               |          |
| amsthm: Fix for <code>\nameref</code> . . . . .                        | 658 | arg. . . . .                                                              | 1069     |
| backref: Fixed from <code>lwrap</code> v0.72                           |     | <code>slantsc</code> : <code>\FilenameNullify</code> . . . . .            | 1090     |
| changes. . . . .                                                       | 676 | <code>titling</code> : <code>\AtBeginDocument</code> . . . . .            | 1158     |
| biblatex: Fixed: Requires <code>hyperref</code> . . . . .              | 682 | <code>xpinyin</code> : Disables pinyin when null                          |          |
| boxedminipage: Renamed from                                            |     | fonts. . . . .                                                            | 1219     |
| boxedminipage2e per author. . . . .                                    | 693 | <code>lwrapmk</code> : clean also removes                                 |          |
| caption: Improved integration. . . . .                                 | 700 | <code>comment_*.cut</code> . . . . .                                      | 320      |
| caption: Non-width <code>\parboxes</code> . . . . .                    | 699 | Added <code>\FirstPageBottom</code> . . . . .                             | 369      |
| caption: Simplified. . . . .                                           | 699 | Added prev/next links. . . . .                                            | 345      |

|                                          |          |                                        |      |
|------------------------------------------|----------|----------------------------------------|------|
| Docs: JETBRAIN MONO font. . . . .        | 102      | \LWR@url: hyperref: Adjusted           |      |
| Docs: \linkpreviousname. . . . .         | 110      | emulation. . . . .                     | 513  |
| Fix: Multirow style. . . . .             | 969, 970 | \textcolor: xcolor: \textcolor:        |      |
| Fixed: textcomp now in kernel. . .       | 628      | Fixed for babel-french. . . . .        | 1206 |
| Logos: Only warn about graphics if       |          | General: 2020/05/12 . . . . .          | 1    |
| actually use \Xe. . . . .                | 624      | LWR@insidemathcomment: Added. .        | 548  |
| tabbing: Restore spacing. . . . .        | 431      | amsmath: Added support for             |      |
| center: Added print mode. . . . .        | 582      | MATHJAX. . . . .                       | 656  |
| verbatim: Added print mode. . . . .      | 431      | hyperref: Adjusted emulation. . .      | 859  |
| verse: Added print mode. . . . .         | 428      | mathtools: Added                       |      |
| flushleft: Added print mode. . . .       | 583      | \ArrowBetweenLines*. . . . .           | 933  |
| flushright: Added print mode. . . .      | 582      | mathtools: Added                       |      |
| longtable: caption now optional. . .     | 907      | \shortvdotswithin*. . . . .            | 933  |
| quotation: Added print mode. . . . .     | 427      | mathtools: Added starred delimited     |      |
| quote: Added print mode. . . . .         | 426      | macros. . . . .                        | 933  |
| LWR@nestspan: Issue warnings inside      |          | nccmath: Added \displaybreak. . .      | 979  |
| a span. . . . .                          | 355      | nccmath: Fixed \nr, added starred. .   | 979  |
| Nullified minipage, \parbox inside       |          | File: lwrap_mathjax.txt: Added         |      |
| a span. . . . .                          | 355      | support for starred macros. . . . .    | 316  |
| v0.85                                    |          | File: lwrap_mathjax.txt:               |      |
| \LWR@atbeginverbatim: Fix: Added         |          | Improved equation numbering. . .       | 316  |
| print macros for fontspec. . . . .       | 430      | File: lwrap_mathjax.txt: Updated       |      |
| \LWR@htmlclosecomment: Fix: Added        |          | to MATHJAX v3 current. . . . .         | 316  |
| print macros for fontspec. . . . .       | 357      | v0.87                                  |      |
| \LWR@htmlcomment: Fix: Added print       |          | \LWR@checkloadfilename: Prevented      |      |
| macros for fontspec. . . . .             | 357      | csvtools. . . . .                      | 246  |
| \LWR@htmltag: Fix: Added print           |          | \bibliography: Reverted to original. . | 540  |
| macros for fontspec. . . . .             | 354      | \scshape: Added FixSmallCaps to        |      |
| General: 2020/05/01 . . . . .            | 1        | remove \LWR@print@scshape for          |      |
| idxlayout: Fixed:                        |          | erewhon, et. al. . . . .               | 612  |
| \AtBeginDocument for load order. . .     | 865      | \sishape: Added FixSmallCaps to        |      |
| mathtools: Fixed:                        |          | remove \LWR@print@scshape for          |      |
| \shortintertext. . . . .                 | 933      | erewhon, et. al. . . . .               | 612  |
| titlesec: pagestyles option. . . . .     | 1153     | General: 2020/06/03 . . . . .          | 1    |
| url: Fixed print mode. . . . .           | 1190     | cancel: Now uses MATHJAX v3            |      |
| Fix: Added print macros for              |          | extension. . . . .                     | 697  |
| fontspec. . . . .                        | 610      | citeref: Added. . . . .                | 737  |
| v0.86                                    |          | drftcite: Added. . . . .               | 756  |
| \LWR@filenamoblanks: Fix: *, (, ), .     |          | embrac: Neutralized kerning. . . . .   | 761  |
| in filename. . . . .                     | 383      | ifpdf, ifptex: Restored to work on     |      |
| \LWR@filestart: Error if missing file. . | 410      | TL2019 and earlier. . . . .            | 206  |
| \LWR@href: hyperref: Adjusted            |          | jurabib: Added. . . . .                | 872  |
| emulation. . . . .                       | 513      | mathtools: Improved                    |      |
| \LWR@label@createtag: Fix: Labels in     |          | \underbracket, \overbracket. . . .     | 931  |
| eqnarray. . . . .                        | 507      | mathtools: Updated starred             |      |
| \LWR@label@inmathcomment: Fix:           |          | macros. . . . .                        | 931  |
| Labels in eqnarray. . . . .              | 506      | mhchem: Now uses MATHJAX v3            |      |
| \LWR@nolinkurl: hyperref: Adjusted       |          | extension. . . . .                     | 951  |
| emulation. . . . .                       | 513      | multibib: Added. . . . .               | 964  |
| \LWR@phantomsection: hyperref:           |          | nccmath: Updated starred,              |      |
| Adjusted emulation. . . . .              | 624      | improved \underref. . . . .            | 979  |
| \LWR@startref: Fixed: \label inside      |          | physics: Now uses MATHJAX v3           |      |
| lateximage. . . . .                      | 509      | extension. . . . .                     | 1025 |
| \LWR@syncmathjax: Improved               |          | splitbib: Added. . . . .               | 1093 |
| MATHJAX equation numbers. . . . .        | 562      | statex2: \pBin exponent. . . . .       | 1100 |



|                                                                                                                |          |                                                                                                                |                        |
|----------------------------------------------------------------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------|------------------------|
| <code>\LWR@subsingledollar</code> : TT font for<br>MATHJAX. . . . .                                            | 556      | Foreground/background hooks:<br>Adapt to L <sup>A</sup> T <sub>E</sub> X core changes. . . . .                 | 416                    |
| <code>\enddocument</code> : Adapt to L <sup>A</sup> T <sub>E</sub> X core<br>changes. . . . .                  | 415      | MATHJAX: Added <code>\protect</code> , and<br><code>\mathcode</code> and related. . . . .                      | 390                    |
| General: 2020/09/03 . . . . .                                                                                  | 1        | Removed <code>\let</code> of <code>\[, \]</code> . . . . .                                                     | 560                    |
| accents: Added. . . . .                                                                                        | 640      | <code>eqnarray</code> : <code>\textendash</code> for number<br>range. . . . .                                  | 571                    |
| <code>atbegshi</code> : Adapt to L <sup>A</sup> T <sub>E</sub> Xkernel<br>changes. . . . .                     | 667      | v0.891                                                                                                         |                        |
| <code>caption3</code> : Split from <code>lwrap-caption</code> . . . . .                                        | 701      | <code>\LWR@atbeginverbatim</code> : Fix for<br><code>verbatim</code> , <code>alltt</code> with lists . . . . . | 429                    |
| <code>caption</code> : Adapt to v3.5. . . . .                                                                  | 699      | <code>\LWR@checkloadfilename</code> : Prevented<br><code>libgreek</code> . . . . .                             | 246                    |
| <code>centernot</code> : Improved. . . . .                                                                     | 704      | <code>\LWR@excludacomment</code> : Error if nested<br><code>comment</code> . . . . .                           | 237                    |
| <code>econometrics</code> : Uses<br><code>lwrap-common-mathjax-letters</code> . . . . .                        | 758      | <code>\LWR@subHTMLsanitize</code> : Neutralized<br>single quotes. . . . .                                      | 386                    |
| <code>everyshi</code> : Adapt to L <sup>A</sup> T <sub>E</sub> Xkernel<br>changes. . . . .                     | 780      | <code>\verb</code> : <code>\verb</code> as <code>\texttt</code> . . . . .                                      | 429                    |
| <code>everyshi</code> : Included in L <sup>A</sup> T <sub>E</sub> X core. . . . .                              | 628      | General: 2020/09/22 . . . . .                                                                                  | 1                      |
| <code>hepunits</code> : Added. . . . .                                                                         | 850      | <code>biblatex</code> : Fixed: Back page<br>references. . . . .                                                | 683                    |
| <code>lwrap-common-mathjax-letters</code> :<br>Added. . . . .                                                  | 1262     | <code>bussproofs</code> : Added. . . . .                                                                       | 696                    |
| <code>lwrap-common-mathjax-newpctxmath</code> :<br>Added. . . . .                                              | 1269     | <code>caption</code> : Improved integration. . . . .                                                           | 700                    |
| <code>lwrap-common-mathjax-overlaysymbols</code> :<br>Added. . . . .                                           | 1277     | <code>cmbright</code> : Added. . . . .                                                                         | 741                    |
| <code>mathalpha</code> : Added. . . . .                                                                        | 923      | <code>colonequals</code> : Uses Unicode and<br><code>\mathrel</code> . . . . .                                 | 742                    |
| <code>mathdesign</code> : Added. . . . .                                                                       | 925      | <code>fancyvrb</code> : Fix: B <code>Verbatim</code> with<br>labels. . . . .                                   | 790                    |
| <code>mathpazo</code> : Added. . . . .                                                                         | 927      | <code>fourier</code> : Added. . . . .                                                                          | 819                    |
| <code>mathptmx</code> : Added. . . . .                                                                         | 928      | <code>hyperref</code> : Added <code>backref</code> ,<br><code>pagebackref</code> . . . . .                     | 854                    |
| <code>mathtools</code> : Added <code>\adjustlimits</code> . . . . .                                            | 932      | <code>hyperref</code> : Fixed <code>\texorpdfstring</code><br>with <code>babel-french</code> . . . . .         | 862                    |
| <code>mathtools</code> : Minor<br>improvements. . . . .                                                        | 932, 936 | <code>kpfonts-otf</code> : Added. . . . .                                                                      | 885                    |
| <code>mismatch</code> : Improved math<br>operators. . . . .                                                    | 957      | <code>kpfonts</code> : Added. . . . .                                                                          | 883                    |
| <code>newpctxmath</code> : Added. . . . .                                                                      | 980      | <code>libertinustlmath</code> : Added. . . . .                                                                 | 891                    |
| <code>newtxmath</code> : Added. . . . .                                                                        | 981      | <code>listings</code> : Fix for MATHJAX: Moved<br><code>\LWR@forcenewpage</code> to start. . . . .             | 901, 902               |
| <code>newtxsf</code> : Added. . . . .                                                                          | 982      | <code>listings</code> : Improved HTML sanitizing. . . . .                                                      | 901                    |
| <code>pxfonts</code> : Added. . . . .                                                                          | 1036     | <code>listings</code> : Improved spacing around<br><code>ampersand</code> . . . . .                            | 901                    |
| <code>shuffle</code> : Added. . . . .                                                                          | 1067     | <code>lwrap-common-mathjax-newpctxmath</code> :<br>Expanded for<br><code>kpfonts</code> . . . . .              | 1269, 1271, 1272, 1274 |
| <code>siunitx</code> : Fix: MATHJAX for <code>\tothe</code> ,<br><code>\raiseto</code> . . . . .               | 1086     | <code>lwrap-common-mathjax-newpctxmath</code> :<br>Factored non-UNICODE. . . . .                               | 1271, 1273             |
| <code>siunitx</code> : Unicode for <code>endash</code> . . . . .                                               | 1086     | <code>lwrap-common-mathjax-newpctxmath</code> :<br>Reverse factored out Greek,<br>non-UNICODE. . . . .         | 1269                   |
| <code>statmath</code> : Fixed <code>abcbm</code> , uses<br><code>lwrap-common-mathjax-letters</code> . . . . . | 1109     | <code>lwrap-common-mathjax-nonunicode</code> :<br>Added. . . . .                                               | 1275                   |
| <code>thm-listof</code> : Updated to v0.72. . . . .                                                            | 1143     | <code>mathdesign</code> : Added <code>\mathinner</code> ,<br><code>\mathbin</code> . . . . .                   | 926                    |
| <code>thm-restate</code> : Updated to v0.72, no<br>changes needed. . . . .                                     | 1144     | <code>mathdesign</code> : Added <code>\mathop</code> . . . . .                                                 | 926                    |
| <code>thmtools</code> : Added. . . . .                                                                         | 1145     | <code>mathdesign</code> : Added <code>\mathrel</code> ,<br><code>\mathord</code> . . . . .                     | 926                    |
| <code>txfonts</code> : Added. . . . .                                                                          | 1178     |                                                                                                                |                        |
| <code>upgreek</code> : Added. . . . .                                                                          | 1189     |                                                                                                                |                        |
| <code>lwrapmk</code> : <code>clean</code> also removes<br><code>*.bbl</code> . . . . .                         | 320      |                                                                                                                |                        |
| Allow preload of <code>amsmath</code> ,<br><code>amsthm</code> , <code>centernot</code> . . . . .              | 210, 628 |                                                                                                                |                        |
| AMS environments: Fix: <code>&lt;ALT&gt;</code> text<br><code>env name</code> . . . . .                        | 654      |                                                                                                                |                        |

|                                            |          |                                                     |            |
|--------------------------------------------|----------|-----------------------------------------------------|------------|
| mathdesign: Honors                         |          | lwrap-common-mathjax-newpctxmath:                   |            |
| greekuppercase,                            |          | Added $\left/\right.$ support in                    |            |
| greeklowercase. . . . .                    | 925      | lwrap_mathjax.txt. . . . .                          | 1269, 1273 |
| mathdots: Added more macros,               |          | minted: Added. . . . .                              | 955        |
| $\mathinner$ . . . . .                     | 926      | unicode-math: Adeed MATHJAX                         |            |
| mathfixs: Added $\mathinner$ . . . . .     | 927      | support for $\left/\right.$ . . . . .               | 1186       |
| mathpazo: Honors slantedGreek. . . . .     | 927      | File: lwrap_mathjax.txt: Added                      |            |
| mathptmx: Honors slantedGreek. . . . .     | 928      | $\left/\right.$ delimiters. . . . .                 | 316        |
| mathtools: Improved                        |          | fcolorminipage: xcolor: Fixed second                |            |
| $\underbracket$ , $\overbracket$ . . . . . | 931      | optional arg. . . . .                               | 1209       |
| mathtools: Uses Unicode and                |          | v0.893                                              |            |
| $\mathrel$ . . . . .                       | 936      | $\LWR@checkloadfilename$ : Allowed                  |            |
| multiobjective: Improved. . . . .          | 967      | picinpar. . . . .                                   | 246        |
| newpxmath: Honors uprightGreek,            |          | $\LWR@expandableformatted$ :                        |            |
| slantedGreek. . . . .                      | 980, 982 | Improved error handling. . . . .                    | 258        |
| newtxmath: Honors uprightGreek,            |          | $\LWR@expandableformattedenv$ :                     |            |
| slantedGreek. . . . .                      | 981      | Improved error handling. . . . .                    | 259        |
| nicefrac: Added $\mathinner$ ,             |          | $\LWR@formatted$ : Improved error                   |            |
| improved fraction. . . . .                 | 990      | handling. . . . .                                   | 257        |
| scalere! : Added. . . . .                  | 1050     | $\LWR@formatted@checkendname$ :                     |            |
| shuffle: Added $\mathbin$ , improved       |          | Added. . . . .                                      | 257        |
| bar. . . . .                               | 1068     | $\LWR@formatted@checkname$ : Added. . . . .         | 257        |
| txgreek: Added. . . . .                    | 1178     | $\LWR@formattedenv$ : Improved error                |            |
| unicode-math: Added                        |          | handling. . . . .                                   | 258        |
| sans-style. . . . .                        | 1185     | $\LWR@htmlcomment$ : Disabled in math               |            |
| units: Added $\mathinner$ , improved       |          | mode. . . . .                                       | 357        |
| fraction. . . . .                          | 1188     | $\LWR@subHTMLsanitize$ : Optionally                 |            |
| File: lwrap_mathjax.txt: Renamed           |          | neutralized single quotes. . . . .                  | 386        |
| tagformat extension. . . . .               | 316      | General: 2020/11/26 . . . . .                       | 1          |
| Prevented libgreek. . . . .                | 209      | MATHJAX: Added $\mathnormal$ . . . . .              | 389        |
| BVerbatim: fancyvrb: Fix: BVerbatim        |          | lwrap.css: Added keystroke. . . . .                 | 273        |
| with labels. . . . .                       | 794      | braket: Now uses MATHJAX                            |            |
| v0.892                                     |          | extension. . . . .                                  | 694        |
| $\LWR@subhtmlclass$ : Ignore               |          | caption3: Updated date to v2.2e. . . . .            | 701        |
| empty class. . . . .                       | 358      | caption: Updated date to v3.5g. . . . .             | 699        |
| $\fcolorbox$ : xcolor: Fixed second        |          | epstopdf-base: Updated date to                      |            |
| optional arg. . . . .                      | 1208     | v2.11. . . . .                                      | 772        |
| $\fcolorboxBlock$ : xcolor: Fixed          |          | epstopdf: Updated date to v2.11. . . . .            | 771        |
| second optional arg. . . . .               | 1208     | esvect: Added. . . . .                              | 776        |
| General: 2020/10/07 . . . . .              | 1        | fixmath: Added. . . . .                             | 799        |
| fancyvrb: Adapted to fvextra. . . . .      | 794      | graphics: Updated date to v1.4c. . . . .            | 834        |
| fancyvrb: Provided                         |          | graphicx: Updated date to v1.2b. . . . .            | 846        |
| $\FV@FrameFillLine$ . . . . .              | 792      | keystroke: Added. . . . .                           | 882        |
| fourier: Added $\left/\right.$             |          | lwrap-common-mathjax-letters:                       |            |
| support in lwrap_mathjax.txt. . . . .      | 820      | Added $\varbeta$ . . . . .                          | 1262       |
| fvextra: Added. . . . .                    | 824      | mathastext: Added. . . . .                          | 923        |
| graphics: Fix path from kernel             |          | mathspec: Added. . . . .                            | 929        |
| change. . . . .                            | 842      | menukeys: Added. . . . .                            | 948        |
| libertinustlmath: Added $\left/\right.$    |          | picinpar: Added. . . . .                            | 1027       |
| support in                                 |          | plimsoll: Added. . . . .                            | 1032       |
| lwrap_mathjax.txt. . . . .                 | 892      | pstricks: Fixed pspicture*. . . . .                 | 1035       |
| lineno: Fix for                            |          | repltext: Added. . . . .                            | 1046       |
| internallinenumbers*. . . . .              | 898      | schemata: Added $\langle alt \rangle$ text. . . . . | 1051       |
|                                            |          | selectp: Added. . . . .                             | 1062       |
|                                            |          | seqsplit: Added. . . . .                            | 1063       |

|                                         |      |                                  |      |
|-----------------------------------------|------|----------------------------------|------|
| simplebnf: Added. . . . .               | 1070 | swfigure: Added. . . . .         | 1121 |
| statistics: Added. . . . .              | 1103 | tikz: Fixed font macros. . . . . | 1149 |
| struktex: Removed package date. . . . . | 1111 | Allowed picinpar. . . . .        | 209  |
| svg: Updated date to v2.02j. . . . .    | 1120 |                                  |      |

## Index of Objects

This is an index of macros, environments, booleans, counters, lengths, packages, classes, options, keys, files, and various other programming objects. Each is listed by itself, and also by category. In some cases, they are further subdivided by [class].

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

| <b>Symbols</b>          |                                                   |
|-------------------------|---------------------------------------------------|
| \\$                     | <i>549</i>                                        |
| \&                      | <i>344</i> , <i>8375</i>                          |
| \(                      | <i>11371</i>                                      |
| *-images.txt (file)     | <i>577</i>                                        |
| *_html.aux (file)       | <i>385</i> , <i>502</i> , <i>503</i> , <i>577</i> |
| *_html.lof (file)       | <i>520</i>                                        |
| *_html.lot (file)       | <i>520</i>                                        |
| *_html.tex (file)       | <i>266</i>                                        |
| \,                      | <i>124</i>                                        |
| --shell-escape (option) | <i>101</i>                                        |
| \@@@setcpageref         | <i>39</i>                                         |
| \@@@setcref             | <i>2</i>                                          |
| \@@@setcrefrange        | <i>17</i>                                         |
| \@author                | <i>417</i>                                        |
| \@begintheorem          | <i>8006</i>                                       |
| \@biblabel              | <i>10830</i>                                      |
| \@caption               | <i>10253</i>                                      |
| \@capttype              | <i>10230</i>                                      |
| \@chapcntformat         | <i>7103</i>                                       |
| \@currentHref           | <i>10040</i>                                      |
| \@currentlabelname      | <i>9854</i>                                       |
| \@date                  | <i>417</i>                                        |
| \@donoparitem           | <i>8034</i>                                       |
| \@endtheorem            | <i>8020</i>                                       |
| \@ensuredmath           | <i>11381</i>                                      |
| \@fnsymbol              | <i>7743</i>                                       |
| \@footnotetext          | <i>6479</i>                                       |
| \@include               | <i>1499</i>                                       |
| \@item                  | <i>8047</i>                                       |
| \@makecaption           | <i>10253</i>                                      |
| \@makefnmark            | <i>6445</i>                                       |
| \@makefntext            | <i>6444</i>                                       |
| \@maketitle             | <i>57</i> , <i>7775</i>                           |
| \@mklab                 | <i>8028</i>                                       |
| \@mpfootnotetext        | <i>6481</i>                                       |
| \@nbitem                | <i>8114</i>                                       |
| \@opargbegintheorem     | <i>8012</i>                                       |
| \@partcntformat         | <i>7104</i>                                       |
| \@partnameformat        | <i>7105</i>                                       |
| \@rowc@lors             | <i>8746</i>                                       |
| \@rowcolors             | <i>8745</i>                                       |
| \@secCNTformat          | <i>7101</i>                                       |
| \@starttoc              | <i>10396</i>                                      |
| \@textsubscript         | <i>12805</i>                                      |
| \@textsuperscript       | <i>12801</i>                                      |
| \@title                 | <i>417</i>                                        |
| \@wrglossary            | <i>10649</i>                                      |
| \@wrindex               | <i>10621</i>                                      |
| \@xdlbfloat             | <i>10178</i>                                      |
| \@xfloat                | <i>10178</i>                                      |
| \[                      | <i>11371</i>                                      |
| \                       | <i>617</i>                                        |
| \$                      | <i>557</i>                                        |
| \$\$                    | <i>557</i>                                        |
| 2in1 (package)          | <i>636</i>                                        |
| 2up (package)           | <i>636</i>                                        |
| <b>A</b>                |                                                   |
| a4 (package)            | <i>636</i>                                        |
| a4wide (package)        | <i>637</i>                                        |
| a5comb (package)        | <i>637</i>                                        |
| abstract (environment)  | <i>7842</i>                                       |
| abstract (package)      | <i>136</i> , <i>637</i>                           |
| \abstractname           | <i>113</i> , <i>7841</i>                          |
| academicons (package)   | <i>639</i>                                        |
| accents (package)       | <i>640</i>                                        |
| accessibility (package) | <i>641</i>                                        |
| accsupp (package)       | <i>642</i>                                        |
| acro (package)          | <i>642</i>                                        |
| acronym (package)       | <i>645</i>                                        |
| \addcontentsline        | <i>10344</i>                                      |
| addlines (package)      | <i>647</i>                                        |
| \AddSubTitlePublished   | <i>7805</i>                                       |
| adjmulticol (package)   | <i>646</i>                                        |
| Adobe (program)         | <i>74</i>                                         |
| \affiliation            | <i>7643</i>                                       |
| afterpage (package)     | <i>647</i>                                        |
| algorithm2e (package)   | <i>647</i>                                        |
| algorithmicx (package)  | <i>172</i> , <i>651</i>                           |
| align (environment)     | <i>85</i>                                         |
| align* (environment)    | <i>88</i>                                         |
| alignat (environment)   | <i>97</i>                                         |
| alignat* (environment)  | <i>100</i>                                        |
| alltt (package)         | <i>652</i>                                        |
| \AltTextClose           | <i>115</i> , <i>11046</i>                         |

|                                                |                |                                              |               |
|------------------------------------------------|----------------|----------------------------------------------|---------------|
| <code>\AltTextOpen</code> .....                | 115, 11045     | <code>booktabs</code> (package) .....        | 690           |
| <code>\AmS</code> .....                        | 13163          | boolean:                                     |               |
| <code>amsmath</code> (package) .....           | 653            | <code>CombineHigherDepths</code> .....       | 112, 380      |
| <code>amsthm</code> (package) .....            | 656            | <code>FileSectionNames</code> .....          | 112, 345      |
| <code>\and</code> .....                        | 417            | <code>FixSmallCaps</code> .....              | 113, 124, 606 |
| <code>anonchp</code> (package) .....           | 661            | <code>FormatEpub</code> .....                | 183, 259      |
| <code>anysize</code> (package) .....           | 661            | <code>FormatWP</code> .....                  | 185, 259      |
| <code>appendix</code> (package) .....          | 136, 661       | <code>HTMLDebugComments</code> .....         | 113, 254      |
| <code>ar</code> (package) .....                | 662            | <code>LWR@allowanothergeometry</code> .....  | 241           |
| <code>arabicfront</code> (package) .....       | 664            | <code>LWR@amsmultline</code> .....           | 569           |
| <code>array</code> (package) .....             | 664            | <code>LWR@copiedsidetoc</code> .....         | 525           |
| <code>\arrayrulecolor</code> .....             | 8753           | <code>LWR@doingapar</code> .....             | 363           |
| <code>\arrayrulecolornexttoken</code> .....    | 8753           | <code>LWR@doingcmidrule</code> .....         | 443           |
| <code>arydshln</code> (package) .....          | 665            | <code>LWR@doingstartpars</code> .....        | 363           |
| <code>AsciiDoc</code> (program) .....          | 74             | <code>LWR@doingtbrule</code> .....           | 443           |
| <code>AsciiDoctor</code> (program) .....       | 74             | <code>LWR@dynamicmath</code> .....           | 343           |
| <code>Asciidoctor-LaTeX</code> (program) ..... | 74             | <code>LWR@emptyatbang</code> .....           | 444           |
| <code>asymptote</code> (package) .....         | 165, 667       | <code>LWR@exitingtabular</code> .....        | 444           |
| <code>atbegshi</code> (package) .....          | 667            | <code>LWR@forceminipagefullwidth</code> .... | 596           |
| <code>attachfile</code> (package) .....        | 668            | <code>LWR@foundmrowcell</code> .....         | 444           |
| <code>attachfile2</code> (package) .....       | 669            | <code>LWR@freezethisautoid</code> .....      | 518           |
| <code>\attrib</code> .....                     | 176, 427, 1191 | <code>LWR@indisplaymathimage</code> .....    | 548           |
| <code>\attribution</code> .....                | 7852           | <code>LWR@insidemathcomment</code> .....     | 548           |
| <code>authblk</code> (package) .....           | 136, 671       | <code>LWR@intabularmetadata</code> .....     | 444           |
| <code>\author</code> .....                     | 121, 417       | <code>LWR@isstartingequation</code> .....    | 574           |
| <code>autobreak</code> (package) .....         | 672            | <code>LWR@MathJax@silentquotes</code> .....  | 386           |
| <code>autonum</code> (package) .....           | 673            | <code>LWR@mathmacro</code> .....             | 342           |
| <code>autosec</code> .....                     | 397            | <code>LWR@minipagefullwidth</code> .....     | 596           |
| <code>awesomebox</code> (package) .....        | 674            | <code>LWR@minipagethispar</code> .....       | 597           |
| <code>axessibility</code> (package) .....      | 675            | <code>LWR@opttablecol</code> .....           | 444           |
| <code>axodraw2</code> (package) .....          | 676            | <code>LWR@origmathjax</code> .....           | 230           |
|                                                |                | <code>LWR@setseqfilelabel</code> .....       | 345           |
|                                                |                | <code>LWR@skipatbang</code> .....            | 444           |
|                                                |                | <code>LWR@skippingmcolrowcell</code> .....   | 444           |
|                                                |                | <code>LWR@skippingmrowcell</code> .....      | 443           |
|                                                |                | <code>LWR@starredlongtable</code> .....      | 446           |
|                                                |                | <code>LWR@startedrow</code> .....            | 443           |
|                                                |                | <code>LWR@tableparcell</code> .....          | 443           |
|                                                |                | <code>LWR@tabularcelladded</code> .....      | 443           |
|                                                |                | <code>LWR@tabularmutemods</code> .....       | 444           |
|                                                |                | <code>LWR@tracinglwrap</code> .....          | 253           |
|                                                |                | <code>LWR@unknownmathsize</code> .....       | 550           |
|                                                |                | <code>LWR@usedmultirow</code> .....          | 444           |
|                                                |                | <code>LWR@validtablecol</code> .....         | 444           |
|                                                |                | <code>LWR@verbtags</code> .....              | 429           |
|                                                |                | <code>LWR@warnbaselinemarker</code> .....    | 550           |
|                                                |                | <code>LWR@warnedcustomizemathjax</code> .... | 388           |
|                                                |                | <code>LWR@xfakebold</code> .....             | 548           |
|                                                |                | <code>mathjax</code> .....                   | 230           |
|                                                |                | <code>usingOSWindows</code> .....            | 229           |
|                                                |                | <code>warpingHTML</code> .....               | 230           |
|                                                |                | <code>warpingprint</code> .....              | 230           |
|                                                |                | <code>WPMarkFloats</code> .....              | 186, 259      |
|                                                |                | <code>WPMarkLOFT</code> .....                | 187, 260      |
|                                                |                | <code>WPMarkMath</code> .....                | 187, 260      |
|                                                |                |                                              |               |
| <b>B</b>                                       |                |                                              |               |
| <code>babel</code> (package) .....             | 176            |                                              |               |
| <code>\backmatter</code> .....                 | 7079           |                                              |               |
| <code>backnaur</code> (package) .....          | 676            |                                              |               |
| <code>backref</code> (package) .....           | 676            |                                              |               |
| <code>balance</code> (package) .....           | 677            |                                              |               |
| <code>\BaseJobname</code> .....                | 5664           |                                              |               |
| <code>BaseJobname</code> (option) .....        | 109, 231       |                                              |               |
| <code>bbding</code> (package) .....            | 677            |                                              |               |
| <code>\bfseries</code> .....                   | 12705          |                                              |               |
| <code>biblatex</code> (package) .....          | 682            |                                              |               |
| <code>\bibliography</code> .....               | 10830          |                                              |               |
| <code>\BibTeX</code> .....                     | 13156          |                                              |               |
| <code>bibunits</code> (package) .....          | 686            |                                              |               |
| <code>bigdelim</code> (package) .....          | 171, 686       |                                              |               |
| <code>bigfoot</code> (package) .....           | 687            |                                              |               |
| <code>bigstrut</code> (package) .....          | 688            |                                              |               |
| <code>bitpattern</code> (package) .....        | 688            |                                              |               |
| <code>BlockClass</code> (environment) .....    | 118, 6133      |                                              |               |
| <code>\BlockClassSingle</code> .....           | 6146           |                                              |               |
| <code>blowup</code> (package) .....            | 689            |                                              |               |
| <code>bm</code> (package) .....                | 689            |                                              |               |
| <code>booklet</code> (package) .....           | 690            |                                              |               |
| <code>bookmark</code> (package) .....          | 690            |                                              |               |

|                           |               |                               |                |
|---------------------------|---------------|-------------------------------|----------------|
| WPMarkMinipages           | 187, 260      | memoir                        | 174, 176, 1192 |
| WPMarkTOC                 | 187, 260      | \cleardoublepage              | 12985          |
| WPTitleHeading            | 188, 261      | \clearpage                    | 12985          |
| bophook (package)         | 692           | cleveref (package)            | 132, 738       |
| bounddvi (package)        | 693           | clrdblpg (package)            | 741            |
| boxedminipage (package)   | 693           | cm-super (package)            | 101            |
| boxedminipage2e (package) | 693           | cmap (package)                | 102            |
| \boxframe                 | 194           | cmbright (package)            | 741            |
| braket (package)          | 694           | cmdtrack (package)            | 742            |
| breakurl (package)        | 694           | colonequals (package)         | 742            |
| breqn (package)           | 695           | \color                        | 50             |
| bsheaders (package)       | 696           | color (package)               | 163, 743       |
| bussproofs (package)      | 696           | \colorbox                     | 77             |
| BVerbatim (environment)   | 255           | \colorboxBlock                | 90, 12086      |
| bxpapersize (package)     | 697           | colortbl (package)            | 171, 743       |
| bytefield (package)       | 697           | CombineHigherDepths (boolean) | 112, 380       |
| <b>C</b>                  |               |                               |                |
| calc (package)            | 242           | comment (package)             | 237            |
| cancel (package)          | 697           | \ConTeXt                      | 13151          |
| canoniclayout (package)   | 698           | continue (package)            | 745            |
| capt-of (package)         | 523           | copyrightbox (package)        | 745            |
| caption (package)         | 172, 523, 699 | counter:                      |                |
| caption3 (package)        | 701           | FileDepth                     | 112, 380       |
| \caption@begin            | 10312         | FootnoteDepth                 | 112, 374       |
| \caption@end              | 10312         | footnoteReset                 | 374            |
| \captionlistentry         | 10319         | lofdepth                      | 530            |
| \captionof                | 10360         | lotdepth                      | 530            |
| \CaptionSeparator         | 10252         | LWR@cellcolordepth            | 446            |
| cases (package)           | 703           | LWR@currentautosec            | 399            |
| center (environment)      | 11957         | LWR@externalfilecnt           | 548            |
| \centering                | 11987         | LWR@dashedlines               | 443            |
| \centerline               | 12006         | LWR@hlines                    | 443            |
| centernot (package)       | 704           | LWR@htmlfilenumber            | 345            |
| changebar (package)       | 704           | LWR@htmlseqfilenumber         | 345            |
| changelayout (package)    | 705           | LWR@latestautopage            | 520            |
| changepage (package)      | 705           | LWR@lateximagedepth           | 573            |
| changes (package)         | 706           | LWR@lateximagenumber          | 573            |
| chappg (package)          | 708           | LWR@Lipage                    | 573            |
| \chapter                  | 7317          | LWR@midrulecounter            | 447            |
| chapterbib (package)      | 709           | LWR@nextautoid                | 520            |
| chemfig (package)         | 709           | LWR@nextautopage              | 520            |
| chemformula (package)     | 711           | LWR@nextequation              | 561            |
| chemgreek (package)       | 716           | LWR@prevFileDepth             | 398            |
| chemmacros (package)      | 717           | LWR@previousautopagelabel     | 385            |
| chemnum (package)         | 735           | LWR@spandepth                 | 363            |
| chkfloat (package)        | 736           | LWR@splitstarcopies           | 458            |
| chngpape (package)        | 736           | LWR@splitstarindex            | 458            |
| cite (package)            | 736           | LWR@starcount                 | 458            |
| citeref (package)         | 737           | LWR@startingequation          | 574            |
| CJK (package)             | 737           | LWR@tablecolspecindex         | 445            |
| CJKutf8 (package)         | 737           | LWR@tablecolspecwidth         | 445            |
| class (key) [Gin]         | 838           | LWR@tableLaTeXcolindex        | 445            |
| class:                    |               | LWR@tabletotalLaTeXcols       | 446            |
| internet                  | 73            | LWR@tabletotalLaTeXcolsnext   | 446            |
| komascript                | 173           | LWR@tabularDepth              | 445            |
|                           |               | LWR@tabularpardepth           | 445            |



|                         |            |                              |                    |
|-------------------------|------------|------------------------------|--------------------|
| LWRcreatelwarpmk        | 1152       | fcolorminipage (environment) | 170, 12126         |
| math                    | 11418      | fewerfloatpages (package)    | 797                |
| minipage                | 12233      | figcaps (package)            | 797                |
| multline                | 72         | figsize (package)            | 797                |
| multline*               | 75         | file:                        |                    |
| picture                 | 12198      | *-images.txt                 | 577                |
| quotation               | 7879       | *_html.aux                   | 385, 502, 503, 577 |
| quote                   | 7871       | *_html.lof                   | 520                |
| tabbing                 | 7984       | *_html.lot                   | 520                |
| tabular                 | 9698       | *_html.tex                   | 266                |
| thebibliography         | 10831      | glyphtounicode.tex           | 102                |
| theindex                | 10572      | lwrap.css                    | 117, 273           |
| titlepage               | 7660       | lwrap.ist                    | 150, 314           |
| titlingpage             | 14         | lwrap.xdy                    | 151, 314           |
| verbatim                | 7966       | lwrap_baseline_marker.eps    | 549                |
| verse                   | 2, 7889    | lwrap_baseline_marker.png    | 549                |
| warpall                 | 1136       | lwrap_formal.css             | 309                |
| warpHTML                | 1137       | lwrap_mathjax.txt            | 316                |
| warpMathJax             | 1143       | lwrap_one_limage.cmd         | 315                |
| warpprint               | 1140       | lwrap_sagebrush.css          | 305                |
| epigraph (package)      | 770        | lwrap_tutorial.txt           | 83                 |
| epsfig (package)        | 771        | lwrapmk.conf                 | 273                |
| epstopdf (package)      | 164, 771   | lwrapmk.lua                  | 194                |
| epstopdf (program)      | 162, 588   | project.css                  | 117                |
| epstopdf-base (package) | 772        | project.lwrapmkconf          | 273                |
| eqlist (package)        | 773        | sample_project.css           | 117, 313           |
| eqnarray (environment)  | 11672      | tutorial.tex                 | 83                 |
| eqparbox (package)      | 773        | filecontents (package)       | 243                |
| equation (environment)  | 11603      | FileDepth (counter)          | 112, 380           |
| equation* (environment) | 11611      | \FilenameLimit               | 112, 6591          |
| errata (package)        | 774        | \FilenameNullify             | 131, 11040, 12833  |
| eso-pic (package)       | 775        | \FilenameSimplify            | 131, 6612, 6934    |
| esvect (package)        | 776        | FileSectionNames (boolean)   | 112, 345           |
| \etalchar               | 137        | fitbox (package)             | 798                |
| etoc (package)          | 776        | fix2col (package)            | 798                |
| etoolbox (package)      | 206        | fixmath (package)            | 799                |
| eurosym (package)       | 779        | fixme (package)              | 177, 799           |
| everyhook (package)     | 242        | fixmetodonotes (package)     | 800                |
| everypage (package)     | 779        | FixSmallCaps (boolean)       | 113, 124, 606      |
| everyshi (package)      | 780        | flafter (package)            | 801                |
| \expandcolspec          | 8631       | \flagverse                   | 1192               |
| expl3 (package)         | 242        | flalign (environment)        | 91                 |
| extrarrows (package)    | 780        | flalign* (environment)       | 94                 |
| extramarks (package)    | 780        | Flare (program)              | 74                 |
| <b>F</b>                |            |                              |                    |
| fancybox (package)      | 129, 781   | flippdf (package)            | 801                |
| fancyhdr (package)      | 786        | float (package)              | 172, 801           |
| fancyref (package)      | 787        | floatflt (package)           | 803                |
| fancytabs (package)     | 787        | floatpag (package)           | 804                |
| fancyvrb (package)      | 788        | floatrow (package)           | 173, 804           |
| \fbox                   | 128, 12418 | fltrace (package)            | 809                |
| fbox (package)          | 794        | \flushbottom                 | 5860               |
| \fboxBlock              | 128, 12427 | flushend (package)           | 810                |
| \fcolorbox              | 107, 12088 | flushleft (environment)      | 11977              |
| \fcolorboxBlock         | 130, 12124 | flushright (environment)     | 11967              |
|                         |            | fminipage (environment)      | 128, 12447         |



|                                      |                                                                                         |
|--------------------------------------|-----------------------------------------------------------------------------------------|
| <b>I</b>                             |                                                                                         |
| idxlayout (package) . . . . .        | <a href="#">864</a>                                                                     |
| \if@titlepage . . . . .              | <a href="#">7638</a>                                                                    |
| \ifnextchar . . . . .                | <a href="#">157</a>                                                                     |
| ifoddpaper (package) . . . . .       | <a href="#">865</a>                                                                     |
| ifplatform (package) . . . . .       | <a href="#">206</a>                                                                     |
| \ifstar . . . . .                    | <a href="#">157</a>                                                                     |
| \IgnoreMinipageWidths . . . . .      | <a href="#">127</a> , <a href="#">595</a> , <a href="#">12223</a>                       |
| \ImageAltText . . . . .              | <a href="#">114</a> , <a href="#">11047</a>                                             |
| ImagesDirectory (option) . . . . .   | <a href="#">104</a> , <a href="#">231</a>                                               |
| ImagesName (option) . . . . .        | <a href="#">104</a> , <a href="#">231</a>                                               |
| imakeidx (package) . . . . .         | <a href="#">866</a>                                                                     |
| imakeidx (program) . . . . .         | <a href="#">144</a>                                                                     |
| \includegraphics . . . . .           | <a href="#">315</a>                                                                     |
| indentfirst (package) . . . . .      | <a href="#">369</a>                                                                     |
| InDesign (program) . . . . .         | <a href="#">74</a>                                                                      |
| index (package) . . . . .            | <a href="#">870</a>                                                                     |
| index (program) . . . . .            | <a href="#">141</a>                                                                     |
| \IndexPageSeparator . . . . .        | <a href="#">113</a> , <a href="#">10570</a>                                             |
| \IndexRangeSeparator . . . . .       | <a href="#">113</a> , <a href="#">10570</a>                                             |
| IndexRef (option) . . . . .          | <a href="#">108</a> , <a href="#">234</a>                                               |
| \InlineClass . . . . .               | <a href="#">118</a> , <a href="#">6156</a>                                              |
| \inlinemathnormal . . . . .          | <a href="#">158</a> , <a href="#">5641</a>                                              |
| \inlinemathother . . . . .           | <a href="#">158</a> , <a href="#">5637</a>                                              |
| inputenc (package) . . . . .         | <a href="#">102</a>                                                                     |
| inputenx (package) . . . . .         | <a href="#">102</a>                                                                     |
| inputtrc (package) . . . . .         | <a href="#">871</a>                                                                     |
| internet (class) . . . . .           | <a href="#">73</a>                                                                      |
| intopdf (package) . . . . .          | <a href="#">872</a>                                                                     |
| itemize (environment) . . . . .      | <a href="#">8164</a>                                                                    |
| \itshape . . . . .                   | <a href="#">12740</a>                                                                   |
| <b>J</b>                             |                                                                                         |
| jurabib (package) . . . . .          | <a href="#">872</a>                                                                     |
| <b>K</b>                             |                                                                                         |
| karnaugh-map (package) . . . . .     | <a href="#">873</a>                                                                     |
| \kern . . . . .                      | <a href="#">124</a>                                                                     |
| key:                                 |                                                                                         |
| [Gin]:                               |                                                                                         |
| class . . . . .                      | <a href="#">838</a>                                                                     |
| keyfloat (package) . . . . .         | <a href="#">173</a> , <a href="#">876</a>                                               |
| keystroke (package) . . . . .        | <a href="#">882</a>                                                                     |
| komascript (class) . . . . .         | <a href="#">173</a>                                                                     |
| kotex (package) . . . . .            | <a href="#">178</a>                                                                     |
| kpfonts (package) . . . . .          | <a href="#">883</a>                                                                     |
| kpfonts-otf (package) . . . . .      | <a href="#">885</a>                                                                     |
| kvoptions (package) . . . . .        | <a href="#">230</a>                                                                     |
| <b>L</b>                             |                                                                                         |
| \l@book . . . . .                    | <a href="#">10548</a>                                                                   |
| \l@chapter . . . . .                 | <a href="#">10550</a>                                                                   |
| \l@figure . . . . .                  | <a href="#">10561</a>                                                                   |
| \l@paragraph . . . . .               | <a href="#">10559</a>                                                                   |
| \l@part . . . . .                    | <a href="#">10549</a>                                                                   |
| \l@section . . . . .                 | <a href="#">10556</a>                                                                   |
| \l@subparagraph . . . . .            | <a href="#">10560</a>                                                                   |
| \l@subsection . . . . .              | <a href="#">10557</a>                                                                   |
| \l@subsubsection . . . . .           | <a href="#">10558</a>                                                                   |
| \l@table . . . . .                   | <a href="#">10562</a>                                                                   |
| \LaTeX . . . . .                     | <a href="#">13105</a>                                                                   |
| LaTeX2HTML (program) . . . . .       | <a href="#">73</a>                                                                      |
| \LaTeXe . . . . .                    | <a href="#">13105</a>                                                                   |
| lateximage (environment) . . . . .   | <a href="#">572</a> , <a href="#">11815</a> , <a href="#">11952</a>                     |
| \LateximageFontSize . . . . .        | <a href="#">11745</a>                                                                   |
| \LateximageFontSizeName . . . . .    | <a href="#">11744</a>                                                                   |
| latexmk (option) . . . . .           | <a href="#">104</a> , <a href="#">234</a>                                               |
| latexmk (program) . . . . .          | <a href="#">180</a>                                                                     |
| LatexmkIndexCmd (option) . . . . .   | <a href="#">107</a> , <a href="#">233</a>                                               |
| LaTeXML (program) . . . . .          | <a href="#">73</a>                                                                      |
| layaureo (package) . . . . .         | <a href="#">886</a>                                                                     |
| layout (package) . . . . .           | <a href="#">886</a>                                                                     |
| layouts (package) . . . . .          | <a href="#">887</a>                                                                     |
| leading (package) . . . . .          | <a href="#">889</a>                                                                     |
| leftidx (package) . . . . .          | <a href="#">890</a>                                                                     |
| \leftline . . . . .                  | <a href="#">12005</a>                                                                   |
| length:                              |                                                                                         |
| \HTMLleftmargini . . . . .           | <a href="#">176</a> , <a href="#">427</a> , <a href="#">428</a> , <a href="#">1191</a>  |
| \HTMLvleftskip . . . . .             | <a href="#">176</a> , <a href="#">427</a> , <a href="#">428</a> , <a href="#">1191</a>  |
| \LWR@cmidrulewidth . . . . .         | <a href="#">470</a>                                                                     |
| \LWR@heavyrulewidth . . . . .        | <a href="#">470</a>                                                                     |
| \LWR@lightrulewidth . . . . .        | <a href="#">470</a>                                                                     |
| \LWR@minipageheight . . . . .        | <a href="#">595</a>                                                                     |
| \LWR@minipagewidth . . . . .         | <a href="#">595</a>                                                                     |
| \LWR@tempheight . . . . .            | <a href="#">619</a>                                                                     |
| \LWR@tempraise . . . . .             | <a href="#">619</a>                                                                     |
| \LWR@tempwidth . . . . .             | <a href="#">619</a>                                                                     |
| \LWR@thiscmidrulewidth . . . . .     | <a href="#">470</a>                                                                     |
| \VerbatimHTMLwidth . . . . .         | <a href="#">428</a>                                                                     |
| \vleftmargini . . . . .              | <a href="#">176</a> , <a href="#">427</a> , <a href="#">1191</a>                        |
| \vleftskip . . . . .                 | <a href="#">176</a> , <a href="#">427</a> , <a href="#">1191</a> , <a href="#">1192</a> |
| letltxmacro (package) . . . . .      | <a href="#">206</a>                                                                     |
| letterspace (package) . . . . .      | <a href="#">890</a>                                                                     |
| lettrine (package) . . . . .         | <a href="#">890</a>                                                                     |
| lgweight . . . . .                   | <a href="#">12715</a>                                                                   |
| libertinust1math (package) . . . . . | <a href="#">891</a>                                                                     |
| LibreOffice (program) . . . . .      | <a href="#">74</a>                                                                      |
| \linebreak . . . . .                 | <a href="#">12978</a>                                                                   |
| lineno (package) . . . . .           | <a href="#">898</a>                                                                     |
| \LinkHome . . . . .                  | <a href="#">114</a> , <a href="#">5735</a> , <a href="#">5740</a>                       |
| \linkhomename . . . . .              | <a href="#">110</a> , <a href="#">5732</a>                                              |
| \LinkNext . . . . .                  | <a href="#">114</a> , <a href="#">5768</a> , <a href="#">5781</a>                       |
| \linknextname . . . . .              | <a href="#">110</a> , <a href="#">5764</a>                                              |
| \LinkPrevious . . . . .              | <a href="#">114</a> , <a href="#">5767</a> , <a href="#">5771</a>                       |
| \linkpreviousname . . . . .          | <a href="#">110</a> , <a href="#">5763</a>                                              |
| Linux (program) . . . . .            | <a href="#">118</a> , <a href="#">228</a>                                               |
| lips (package) . . . . .             | <a href="#">900</a>                                                                     |
| list (environment) . . . . .         | <a href="#">8134</a>                                                                    |
| listings (package) . . . . .         | <a href="#">900</a>                                                                     |
| listliketab (package) . . . . .      | <a href="#">905</a>                                                                     |
| \listof . . . . .                    | <a href="#">10452</a>                                                                   |

|                                                            |               |                                                     |              |
|------------------------------------------------------------|---------------|-----------------------------------------------------|--------------|
| <code>\listoffigures</code>                                | 10426         | <code>\LWR@makebox@align</code>                     | 12352        |
| <code>\listoftables</code>                                 | 10439         | <code>\LWR@makebox@paren</code>                     | 12337        |
| <code>lltjext</code> (package)                             | 905           | <code>\LWR@printpendingfootnotes</code>             | 6515         |
| <code>lmodern</code> (package)                             | 101, 102      | <code>\LWR@absorbstar</code>                        | 877          |
| <code>lofdepth</code> (counter)                            | 530           | <code>\LWR@addbaselinemarker</code>                 | 11082        |
| <code>longtable</code> (environment)                       | 4             | <code>\LWR@addcdashline</code>                      | 9021         |
| <code>longtable</code> (package)                           | 169, 906      | <code>\LWR@addcmidruletrim</code>                   | 8987         |
| <code>lotdepth</code> (counter)                            | 530           | <code>\LWR@addcmidrulewidth</code>                  | 9018         |
| <code>lscapex</code> (package)                             | 909           | <code>\LWR@addcompilecmd</code>                     | 1910         |
| <code>ltablex</code> (package)                             | 909           | <code>\LWR@addformatwppalignment</code>             | 9037         |
| <code>lrcaption</code> (package)                           | 910           | <code>\LWR@addleftmostbartag</code>                 | 8825         |
| <code>ltxgrid</code> (package)                             | 910           | <code>\LWR@addlinktitle</code>                      | 9968         |
| <code>ltxtable</code> (package)                            | 910           | <code>\LWR@addmathjax</code>                        | 11515        |
| <code>lua-check-hyphen</code> (package)                    | 911           | <code>\LWR@addmulticolverturulecolor</code>         | 9289         |
| <code>lua-visual-debug</code> (package)                    | 911           | <code>\LWR@addrulewidth</code>                      | 8992         |
| <code>luacolor</code> (package)                            | 911           | <code>\LWR@addtabularcellcolor</code>               | 9164         |
| <code>\LuaLaTeX</code>                                     | 13134         | <code>\LWR@addtabularhrulecolor</code>              | 9065         |
| <code>LuaLaTeX</code> (program) [requirement]              | 77            | <code>\LWR@addtabulararrowcolor</code>              | 9050         |
| <code>luamplib</code> (package)                            | 911           | <code>\LWR@addtabularrulecolors</code>              | 9111         |
| <code>\LuaTeX</code>                                       | 13134         | <code>\LWR@afterendverbatim</code>                  | 7950         |
| <code>luatexko</code> (package)                            | 912           | <code>LWR@allowanothergeometry</code> (boolean)     | 241          |
| <code>luatodonotes</code> (package)                        | 177, 914      | <code>\LWR@amsmathbody</code>                       | 11778        |
| <code>lwrap</code> (package)                               | 104           | <code>\LWR@amsmathbodynumbered</code>               | 11784        |
| <code>lwrap-common-mathjax-letters</code> (package)        | 1262          | <code>LWR@amsmultline</code> (boolean)              | 569          |
| <code>lwrap-common-mathjax-newpctxmath</code> (package)    | 1269          | <code>\LWR@applyxfakebold</code>                    | 11064        |
| <code>lwrap-common-mathjax-nonunicode</code> (package)     | 1274          | <code>\LWR@atbeginverbatim</code>                   | 7930         |
| <code>lwrap-common-mathjax-overlaysymbols</code> (package) | 1277          | <code>\LWR@avoiddupfilenames</code>                 | 6623         |
| <code>lwrap-common-multimedia</code> (package)             | 1257          | <code>\LWR@backgroundcolor</code>                   | 38           |
| <code>lwrap-patch-komascript</code> (package)              | 1226          | <code>\LWR@beginhideamsmath</code>                  | 11655        |
| <code>lwrap-patch-memoir</code> (package)                  | 1228          | <code>LWR@BlockClassWP</code> (environment)         | 6172         |
| <code>lwrap.css</code> (file)                              | 117, 273      | <code>LWR@blocktextcurrentfont</code> (environment) | 12691, 12832 |
| <code>lwrap.ist</code> (file)                              | 150, 314      | <code>\LWR@botnavigation</code>                     | 5758         |
| <code>lwrap.xdy</code> (file)                              | 151, 314      | <code>LWR@cdashlines</code>                         | 470          |
| <code>lwrap_baseline_marker.eps</code> (file)              | 549           | <code>LWR@cellcolordepth</code> (counter)           | 446          |
| <code>lwrap_baseline_marker.png</code> (file)              | 549           | <code>\LWR@cellHTMLcolor</code>                     | 8750         |
| <code>lwrap_formal.css</code> (file)                       | 309           | <code>\LWR@checkloadbefore</code>                   | 67           |
| <code>lwrap_mathjax.txt</code> (file)                      | 316           | <code>\LWR@checkloadfilename</code>                 | 1317         |
| <code>lwrap_one_limage.cmd</code> (file)                   | 315           | <code>\LWR@checkloadnever</code>                    | 88           |
| <code>lwrap_sagebrush.css</code> (file)                    | 305           | <code>\LWR@clearmidrules</code>                     | 8906         |
| <code>lwrap_tutorial.txt</code> (file)                     | 83            | <code>\LWR@closeparagraph</code>                    | 6272         |
| [ <code>lwrapmk</code> ]:                                  |               | <code>\LWR@closeparagraph@br</code>                 | 6262         |
| <code>htmlglossary</code> (option)                         | 138, 831      | <code>\LWR@closeprevious</code>                     | 5823         |
| <code>printglossary</code> (option)                        | 138, 831      | <code>\LWR@closetabledatcell</code>                 | 8328         |
| <code>lwrapmk</code> (option)                              | 108, 232, 319 | <code>\LWR@cmidrulewidth</code> (length)            | 470          |
| <code>lwrapmk</code> (program)                             | 194, 319      | <code>LWR@colafterspec</code>                       | 446          |
| <code>lwrapmk epstopdf</code> (program)                    | 162, 588      | <code>LWR@colatspec</code>                          | 446          |
| <code>lwrapmk pdftosvg</code> (program)                    | 162, 588      | <code>LWR@colbangspec</code>                        | 446          |
| <code>lwrapmk.conf</code> (file)                           | 273           | <code>LWR@colbarspec</code>                         | 446          |
| <code>lwrapmk.lua</code> (file)                            | 194           | <code>LWR@colbeforespec</code>                      | 446          |
| <code>\LWR@footnotetext</code>                             | 6448          | <code>\LWR@columnHTMLcolor</code>                   | 8748         |
|                                                            |               | <code>\LWR@columnspeclookahead</code>               | 8459         |
|                                                            |               | <code>\LWR@compilecmd</code>                        | 1907         |
|                                                            |               | <code>\LWR@compileuplatex</code>                    | 1942         |
|                                                            |               | <code>\LWR@convertto</code>                         | 792          |

|                                                 |       |                                                 |       |
|-------------------------------------------------|-------|-------------------------------------------------|-------|
| LWR@copiedsidetoc (boolean) . . . . .           | 525   | \LWR@footnotetext . . . . .                     | 6478  |
| \LWR@copyfile . . . . .                         | 1534  | \LWR@forceemptyline . . . . .                   | 819   |
| \LWR@createautosec . . . . .                    | 7085  | LWR@forceminipagefullwidth (boolean) <b>596</b> |       |
| \LWR@createfooter . . . . .                     | 6937  | \LWR@forceminwidth . . . . .                    | 12401 |
| LWR@currentautosec (counter) . . . . .          | 399   | \LWR@forcenewautoidanchor . . . . .             | 10211 |
| \LWR@currentcss . . . . .                       | 6386  | \LWR@forcenewpage . . . . .                     | 5843  |
| \LWR@currenttextcolor . . . . .                 | 12819 | \LWR@formatted . . . . .                        | 1599  |
| \LWR@customizedMathJax . . . . .                | 6832  | \LWR@formatted@checkendname . . . . .           | 1590  |
| \LWR@customizeMathJax . . . . .                 | 6914  | \LWR@formatted@checkname . . . . .              | 1581  |
| \LWR@descitem . . . . .                         | 8176  | \LWR@formattedenv . . . . .                     | 1631  |
| \LWR@disablepinyin . . . . .                    | 818   | \LWR@formatting . . . . .                       | 1580  |
| LWR@displaymathnormal (environment)             |       | LWR@foundmrowcell (boolean) . . . . .           | 444   |
| . . . . .                                       | 11419 | \LWR@fourthoffour . . . . .                     | 823   |
| LWR@displaymathother (environment) <b>11422</b> |       | LWR@freezethisautoid (boolean) . . . . .        | 518   |
| \LWR@docdashline . . . . .                      | 8955  | \LWR@futurenonspacelct . . . . .                | 8254  |
| \LWR@docmidrule . . . . .                       | 8939  | \LWR@FVstyle . . . . .                          | 54    |
| \LWR@doequation . . . . .                       | 11533 | \LWR@getexparray . . . . .                      | 5610  |
| \LWR@doindexentry . . . . .                     | 10758 | \LWR@getmynexttoken . . . . .                   | 8264  |
| \LWR@doindexentrysub . . . . .                  | 10756 | LWR@glrbox (environment) . . . . .              | 850   |
| \LWR@doindexentrysubsub . . . . .               | 10745 | \LWR@gsavebox . . . . .                         | 836   |
| LWR@doingapar (boolean) . . . . .               | 363   | LWR@hdashedlines (counter) . . . . .            | 443   |
| LWR@doingcmidrule (boolean) . . . . .           | 443   | \LWR@heavyrulewidth (length) . . . . .          | 470   |
| LWR@doingstartpars (boolean) . . . . .          | 363   | \LWR@hidelatexequation . . . . .                | 11499 |
| LWR@doingtbrule (boolean) . . . . .             | 443   | LWR@hlines (counter) . . . . .                  | 443   |
| \LWR@domulticolumn . . . . .                    | 9327  | \LWR@href . . . . .                             | 10084 |
| \LWR@doubledollar . . . . .                     | 11322 | \LWR@HTML@caption@begin . . . . .               | 10292 |
| LWR@dynamicmath (boolean) . . . . .             | 343   | \LWR@HTML@caption@end . . . . .                 | 10303 |
| \LWR@earlyclassloadnever . . . . .              | 99    | \LWR@HTML@ref . . . . .                         | 10011 |
| \LWR@earlyloadnever . . . . .                   | 94    | \LWR@htmlblockcomment . . . . .                 | 6070  |
| LWR@emptyatbang (boolean) . . . . .             | 444   | \LWR@htmlblocktag . . . . .                     | 6072  |
| \LWR@endfloatalignment . . . . .                | 10246 | \LWR@HTMLcline . . . . .                        | 9679  |
| \LWR@endhideamsmath . . . . .                   | 11664 | \LWR@htmlclosecomment . . . . .                 | 6037  |
| \LWR@endofline . . . . .                        | 12910 | \LWR@htmlcomment . . . . .                      | 6058  |
| \LWR@ensuredoingapar . . . . .                  | 6238  | \LWR@htmldivclass . . . . .                     | 6109  |
| LWR@equationother (environment) . . . . .       | 11436 | \LWR@htmldivclassend . . . . .                  | 6112  |
| \LWR@equationtag . . . . .                      | 11764 | \LWR@html element . . . . .                     | 6123  |
| \LWR@excludacomment . . . . .                   | 1096  | \LWR@html elementclass . . . . .                | 6095  |
| LWR@exitingtabular (boolean) . . . . .          | 444   | \LWR@html elementclassend . . . . .             | 6101  |
| \LWR@expandableformatted . . . . .              | 1615  | \LWR@html elementclassline . . . . .            | 6115  |
| \LWR@expandableformattedenv . . . . .           | 1647  | \LWR@html elementend . . . . .                  | 6126  |
| \LWR@expcolspec . . . . .                       | 8627  | LWR@htmlfilenumber (counter) . . . . .          | 345   |
| LWR@externalfilecnt (counter) . . . . .         | 548   | \LWR@htmlfileref . . . . .                      | 9873  |
| \LWR@fboxstyle . . . . .                        | 12412 | \LWR@HTMLhline . . . . .                        | 9660  |
| LWR@figcaption (environment) . . . . .          | 10282 | \LWR@HTMLLatexCmd . . . . .                     | 1952  |
| \LWR@filenamoblanks . . . . .                   | 6636  | \LWR@htmlmulticolumn . . . . .                  | 9393  |
| \LWR@filestart . . . . .                        | 7382  | \LWR@htmlopencomment . . . . .                  | 6037  |
| \LWR@findcurrenttextcolor . . . . .             | 12822 | \LWR@htmlrefsectionfilename . . . . .           | 5722  |
| \LWR@findword . . . . .                         | 1314  | \LWR@HTMLsanitize . . . . .                     | 6802  |
| \LWR@firstoffour . . . . .                      | 823   | \LWR@HTMLsanitizeexpand . . . . .               | 6810  |
| \LWR@floatalignment . . . . .                   | 10232 | \LWR@htmlsectionfilename . . . . .              | 5682  |
| \LWR@floatalignmentname . . . . .               | 10231 | LWR@htmlseqfilenumber (counter) . . . . .       | 345   |
| \LWR@floatbegin . . . . .                       | 10143 | \LWR@htmlspan . . . . .                         | 6014  |
| \LWR@floatend . . . . .                         | 10188 | \LWR@htmlspanclass . . . . .                    | 6022  |
| \LWR@floatstyle . . . . .                       | 2     | \LWR@htmltag . . . . .                          | 6032  |
| \LWR@footnotebox . . . . .                      | 6443  | \LWR@htmltagc . . . . .                         | 5944  |

|                                                      |                    |                                                      |              |
|------------------------------------------------------|--------------------|------------------------------------------------------|--------------|
| <code>\LWR@hyperindexref@comma</code> . . . . .      | <u>10788</u>       | <code>LWR@MathJax@silentquotes</code> (boolean) .    | <u>386</u>   |
| <code>\LWR@hyperindexref@comma</code> . . . . .      | <u>10781</u>       | <code>\LWR@mathjaxfilename</code> . . . . .          | <u>6397</u>  |
| <code>\LWR@hyperindexref@range</code> . . . . .      | <u>10793</u>       | <code>\LWR@mathjaxwarn</code> . . . . .              | <u>13347</u> |
| <code>\LWR@hyperindexrefnullified</code> . . . . .   | <u>10762</u>       | <code>LWR@mathmacro</code> (boolean) . . . . .       | <u>342</u>   |
| <code>\LWR@hyperindexrefsub</code> . . . . .         | <u>10796</u>       | <code>\LWR@maybeorignewpage</code> . . . . .         | <u>829</u>   |
| <code>\LWR@hyperindexrefsubtwo</code> . . . . .      | <u>10803</u>       | <code>\LWR@maybenewtablerow</code> . . . . .         | <u>8757</u>  |
| <code>\LWR@includedcomment</code> . . . . .          | <u>1096</u>        | <code>\LWR@maybeprintpendingfootnotes</code> .       | <u>6534</u>  |
| <code>\LWR@indentHTML</code> . . . . .               | <u>5938</u>        | <code>\LWR@maybetocdata</code> . . . . .             | <u>10504</u> |
| <code>\LWR@indentHTMLtwo</code> . . . . .            | <u>5941</u>        | <code>LWR@midrulecounter</code> (counter) . . . . .  | <u>447</u>   |
| <code>\LWR@indextem</code> . . . . .                 | <u>10587</u>       | <code>LWR@midrules</code> . . . . .                  | <u>470</u>   |
| <code>\LWR@indexnameref</code> . . . . .             | <u>10716</u>       | <code>LWR@minipagefullwidth</code> (boolean) . . .   | <u>596</u>   |
| <code>\LWR@indexnameref@anonref</code> . . . . .     | <u>10657</u>       | <code>\LWR@minipageheight</code> (length) . . . . .  | <u>595</u>   |
| <code>\LWR@indexnameref@ceref</code> . . . . .       | <u>10683</u>       | <code>\LWR@minipagestartpars</code> . . . . .        | <u>12917</u> |
| <code>\LWR@indexnameref@crefnameref</code> . . .     | <u>10700</u>       | <code>\LWR@minipagestoppars</code> . . . . .         | <u>12920</u> |
| <code>\LWR@indexnameref@ref</code> . . . . .         | <u>10662</u>       | <code>LWR@minipagethispar</code> (boolean) . . . . . | <u>597</u>   |
| <code>\LWR@indexnameref@refnameref</code> . . .      | <u>10671</u>       | <code>\LWR@minipagewidth</code> (length) . . . . .   | <u>595</u>   |
| <code>\LWR@indexsubitem</code> . . . . .             | <u>10591</u>       | <code>\LWR@multicolother</code> . . . . .            | <u>9229</u>  |
| <code>\LWR@indexsubsubitem</code> . . . . .          | <u>10595</u>       | <code>\LWR@multicolpartext</code> . . . . .          | <u>9223</u>  |
| <code>LWR@indisplaymathimage</code> (boolean) . .    | <u>548</u>         | <code>\LWR@multicolskip</code> . . . . .             | <u>9235</u>  |
| <code>\LWR@infoprocessingmathjax</code> . . . . .    | <u>6867</u>        | <code>\LWR@multirowborder</code> . . . . .           | <u>3</u>     |
| <code>LWR@insidemathcomment</code> (boolean) . . .   | <u>548</u>         | <code>\LWR@mynexttoken</code> . . . . .              | <u>8253</u>  |
| <code>\LWR@instertatbangcols</code> . . . . .        | <u>8320</u>        | <code>\LWR@myshorttoc</code> . . . . .               | <u>10372</u> |
| <code>LWR@intabularmetadata</code> (boolean) . . .   | <u>444</u>         | <code>\LWR@nameref</code> . . . . .                  | <u>9870</u>  |
| <code>\LWR@isolate</code> . . . . .                  | <u>809</u>         | <code>LWR@nestspan</code> (environment) . . . . .    | <u>5970</u>  |
| <code>LWR@isstartingequation</code> (boolean) . .    | <u>574</u>         | <code>\LWR@new@label</code> . . . . .                | <u>9948</u>  |
| <code>\LWR@itemizeitem</code> . . . . .              | <u>8157</u>        | <code>\LWR@newautoidanchor</code> . . . . .          | <u>10225</u> |
| <code>\LWR@label@createtag</code> . . . . .          | <u>9919</u>        | <code>\LWR@newautopagelabel</code> . . . . .         | <u>6753</u>  |
| <code>\LWR@label@inmathcomment</code> . . . . .      | <u>9905</u>        | <code>\LWR@newhtmlfile</code> . . . . .              | <u>6956</u>  |
| <code>\LWR@label@subcreatetag</code> . . . . .       | <u>9901</u>        | <code>LWR@nextautoid</code> (counter) . . . . .      | <u>520</u>   |
| <code>LWR@latestautopage</code> (counter) . . . . .  | <u>520</u>         | <code>LWR@nextautopage</code> (counter) . . . . .    | <u>520</u>   |
| <code>\LWR@lateximage@oneimage</code> . . . . .      | <u>11800</u>       | <code>LWR@nextequation</code> (counter) . . . . .    | <u>561</u>   |
| <code>\LWR@lateximage@oneimageb</code> . . . . .     | <u>11791</u>       | <code>\LWR@nolinkurl</code> . . . . .                | <u>10096</u> |
| <code>LWR@lateximagedepth</code> (counter) . . . . . | <u>573</u>         | <code>\LWR@notljloadafter</code> . . . . .           | <u>42</u>    |
| <code>\LWR@lateximagedepthref</code> . . . . .       | <u>9876</u>        | <code>\LWR@notmemoirloadafter</code> . . . . .       | <u>39</u>    |
| <code>LWR@lateximagenumber</code> (counter) . . . .  | <u>573</u>         | <code>\LWR@nullfonts</code> . . . . .                | <u>10907</u> |
| <code>\LWR@lateximagenumberref</code> . . . . .      | <u>9879</u>        | <code>\LWR@nullifycomment</code> . . . . .           | <u>1308</u>  |
| <code>\LWR@lateximagesfile</code> . . . . .          | <u>1496</u>        | <code>\LWR@nullifyNoAutoSpacing</code> . . . . .     | <u>9685</u>  |
| <code>\LWR@latexmkcmd</code> . . . . .               | <u>1928</u>        | <code>\LWR@nulllistfills</code> . . . . .            | <u>8126</u>  |
| <code>\LWR@latexmkdvipdfm</code> . . . . .           | <u>1933</u>        | <code>\LWR@openparagraph</code> . . . . .            | <u>6244</u>  |
| <code>\LWR@latexmkvar</code> . . . . .               | <u>1922</u>        | <code>LWR@opttablecol</code> (boolean) . . . . .     | <u>444</u>   |
| <code>\LWR@letLtxMacros</code> . . . . .             | <u>873</u>         | <code>\LWR@orig@setBold</code> . . . . .             | <u>11062</u> |
| <code>\LWR@lightrulewidth</code> (length) . . . . .  | <u>470</u>         | <code>\LWR@orig@unsetBold</code> . . . . .           | <u>11063</u> |
| <code>\LWR@linkcatcodes</code> . . . . .             | <u>10043</u>       | <code>\LWR@origcolspec</code> . . . . .              | <u>8303</u>  |
| <code>\LWR@linkmediacatcodes</code> . . . . .        | <u>10051</u>       | <code>LWR@origmathjax</code> (boolean) . . . . .     | <u>230</u>   |
| <code>LWR@LIpage</code> (counter) . . . . .          | <u>573</u>         | <code>\LWR@overline</code> . . . . .                 | <u>12814</u> |
| <code>\LWR@listitem</code> . . . . .                 | <u>8119</u>        | <code>\LWR@parseaftercolumn</code> . . . . .         | <u>8536</u>  |
| <code>\LWR@loadafter</code> . . . . .                | <u>20</u>          | <code>\LWR@parseatcolumn</code> . . . . .            | <u>8469</u>  |
| <code>\LWR@loadbefore</code> . . . . .               | <u>55</u>          | <code>\LWR@parsebangcolumn</code> . . . . .          | <u>8498</u>  |
| <code>\LWR@loadnever</code> . . . . .                | <u>73</u>          | <code>\LWR@parsebarcolumn</code> . . . . .           | <u>8548</u>  |
| <code>\LWR@longtabledatacaptiontag</code> . . . .    | <u>9402</u>        | <code>\LWR@parsebeforecolumn</code> . . . . .        | <u>8524</u>  |
| <code>\LWR@lookforpackagename</code> . . . . .       | <u>1367</u>        | <code>\LWR@parsecoloncolumn</code> . . . . .         | <u>8573</u>  |
| <code>\LWR@lwarpcnfversion</code> . . . . .          | <u>1901</u>        | <code>\LWR@parseDcolumn</code> . . . . .             | <u>8622</u>  |
| <code>\LWR@LwarpEnd</code> . . . . .                 | <u>7559, 13182</u> | <code>\LWR@parsedrequirepackagenames</code> . .      | <u>1307</u>  |
| <code>\LWR@LwarpStart</code> . . . . .               | <u>7480, 13182</u> | <code>\LWR@parsenormalcolumn</code> . . . . .        | <u>8598</u>  |
| <code>\LWR@maketitlesetup</code> . . . . .           | <u>34, 7735</u>    | <code>\LWR@parsepcolumn</code> . . . . .             | <u>8610</u>  |

|                                                  |       |                                                |       |
|--------------------------------------------------|-------|------------------------------------------------|-------|
| <code>\LWR@parsesemicoloncolumn</code>           | 8594  | <code>\LWR@setref</code>                       | 9864  |
| <code>\LWR@parsestarcolumn</code>                | 8619  | <code>LWR@setseqfilelabel (boolean)</code>     | 345   |
| <code>\LWR@parsetablecols</code>                 | 8659  | <code>LWR@setvirtualpage (environment)</code>  | 12207 |
| <code>\LWR@parsewcolumn</code>                   | 8614  | <code>\LWR@shellescapecmd</code>               | 1902  |
| <code>\LWR@patcherror</code>                     | 800   | <code>\LWR@sidetoc</code>                      | 10478 |
| <code>\LWR@patchlists</code>                     | 8201  | <code>\LWR@simplifycustom</code>               | 6611  |
| <code>\LWR@pdfencoding</code>                    | 718   | <code>\LWR@simplifyname</code>                 | 6600  |
| <code>\LWR@phantomsection</code>                 | 13044 | <code>\LWR@singledollar</code>                 | 11349 |
| <code>\LWR@popclose</code>                       | 5574  | <code>\LWR@singledollarmeasure</code>          | 11137 |
| <code>\LWR@PreloadedPackage</code>               | 12010 | <code>LWR@skipatbang (boolean)</code>          | 444   |
| <code>LWR@prevFileDepth (counter)</code>         | 398   | <code>LWR@skippingmcolrowcell (boolean)</code> | 444   |
| <code>LWR@previousautopagelabel (counter)</code> | 385   | <code>LWR@skippingmrowcell (boolean)</code>    | 443   |
| <code>\LWR@printatbang</code>                    | 8800  | <code>LWR@spandepth (counter)</code>           | 363   |
| <code>\LWR@printbartag</code>                    | 8790  | <code>\LWR@spanwarnformat</code>               | 5954  |
| <code>\LWR@printchaptername</code>               | 7106  | <code>\LWR@spanwarninvalid</code>              | 5962  |
| <code>\LWR@printcloselist</code>                 | 8026  | <code>\LWR@splitstarcontents</code>            | 8630  |
| <code>\LWR@PrintLatexCmd</code>                  | 1952  | <code>LWR@splitstarcopies (counter)</code>     | 458   |
| <code>\LWR@printlength</code>                    | 1288  | <code>LWR@splitstarindex (counter)</code>      | 458   |
| <code>\LWR@printmccoldata</code>                 | 9238  | <code>LWR@starcount (counter)</code>           | 458   |
| <code>\LWR@printmccoltype</code>                 | 9181  | <code>LWR@starredlongtable (boolean)</code>    | 446   |
| <code>\LWR@printopenlist</code>                  | 8027  | <code>LWR@startedrow (boolean)</code>          | 443   |
| <code>\LWR@printpendingfootnotes</code>          | 6531  | <code>LWR@startingequation (counter)</code>    | 574   |
| <code>\LWR@printpendingmpfootnotes</code>        | 6543  | <code>\LWR@startingequationtag</code>          | 11763 |
| <code>\LWR@printpercentlength</code>             | 793   | <code>\LWR@startnewdepth</code>                | 7095  |
| <code>\LWR@printthetitle</code>                  | 7687  | <code>\LWR@startpars</code>                    | 6314  |
| <code>\LWR@providelength</code>                  | 789   | <code>\LWR@startref</code>                     | 9974  |
| <code>\LWR@ProvidesPackageDrop</code>            | 1486  | <code>\LWR@stoppars</code>                     | 6335  |
| <code>\LWR@ProvidesPackageDropA</code>           | 1471  | <code>\LWR@stripperiod</code>                  | 9855  |
| <code>\LWR@ProvidesPackageDropB</code>           | 1480  | <code>\LWR@strresult</code>                    | 8301  |
| <code>\LWR@ProvidesPackagePass</code>            | 1440  | <code>\LWR@subaddcmidruletrim</code>           | 8974  |
| <code>\LWR@pushclose</code>                      | 5547  | <code>\LWR@subaddtabularcellcolor</code>       | 9158  |
| <code>\LWR@pushoneclose</code>                   | 7091  | <code>\LWR@subcdashline</code>                 | 8942  |
| <code>\LWR@quickfile</code>                      | 1493  | <code>\LWR@subcmidrule</code>                  | 8924  |
| <code>\LWR@remembertag</code>                    | 11768 | <code>\LWR@subcustomizedmathjax</code>         | 6835  |
| <code>\LWR@replacestrings</code>                 | 6761  | <code>\LWR@subhtml-elementclass</code>         | 6077  |
| <code>\LWR@requesttoc</code>                     | 7552  | <code>\LWR@subHTMLsanitize</code>              | 6782  |
| <code>\LWR@requirepackagenames</code>            | 1306  | <code>\LWR@subhyperref</code>                  | 10059 |
| <code>\LWR@restoreMathJaxformatting</code>       | 10855 | <code>\LWR@subhyperrefclass</code>             | 10073 |
| <code>\LWR@restoreorigaccents</code>             | 1850  | <code>\LWR@subhyperref-text</code>             | 10068 |
| <code>\LWR@restoreorigformatting</code>          | 10856 | <code>\LWR@subinlineimage</code>               | 10122 |
| <code>\LWR@restoreoriglists</code>               | 8229  | <code>\LWR@subnewref</code>                    | 10005 |
| <code>\LWR@rowHTMLcolor</code>                   | 8749  | <code>\LWR@subsingledollar</code>              | 11262 |
| <code>\LWR@ruleHTMLcolor</code>                  | 8751  | <code>\LWR@subsingledollarsvg</code>           | 11183 |
| <code>\LWR@sanitize</code>                       | 998   | <code>\LWR@subtableofcontents</code>           | 10386 |
| <code>\LWR@sanitized</code>                      | 997   | <code>\LWR@subtabularhtmlcolumns</code>        | 9473  |
| <code>\LWR@secondoffour</code>                   | 823   | <code>\LWR@syncmathjax</code>                  | 11487 |
| <code>\LWR@section</code>                        | 7111  | <code>\LWR@syncnotenames</code>                | 11596 |
| <code>\LWR@sectionnumber</code>                  | 7082  | <code>\LWR@syncnotenumbers</code>              | 11590 |
| <code>\LWR@select@html@hspace</code>             | 12937 | <code>\LWR@syncnotenotename</code>             | 11591 |
| <code>\LWR@select@html@nohspace</code>           | 12968 | <code>\LWR@syncnotenotenummer</code>           | 11585 |
| <code>\LWR@select@print@hspace</code>            | 12971 | <code>LWR@tablecolspec</code>                  | 445   |
| <code>\LWR@setcurrentfont</code>                 | 11065 | <code>LWR@tablecolspecindex (counter)</code>   | 445   |
| <code>\LWR@setexparray</code>                    | 5601  | <code>LWR@tablecolspecwidth (counter)</code>   | 445   |
| <code>\LWR@setlatestname</code>                  | 9856  | <code>\LWR@tabledatacolumn-tag</code>          | 9562  |
| <code>\LWR@setOSWindows</code>                   | 912   | <code>\LWR@tabledata-singlecolumn-tag</code>   | 8839  |





mathjax ..... 104, 231  
 mathsvg ..... 104, 231  
 OSWindows ..... 108, 118, 228, 232  
 pdftotextEnc ..... 108, 232  
 PrintIndexCmd ..... 106, 233  
 PrintLatexCmd ..... 106, 179, 233  
 warpHTML ..... 108, 231  
 warpprint ..... 108, 230  
 xindex ..... 106, 234  
 xindexConfig ..... 106, 152, 232  
 xindy ..... 106, 233  
 xindyCodepage ..... 106, 232  
 xindyLanguage ..... 106, 232  
 xindyStyle ..... 106, 152, 232  
 \OSPathSymbol ..... 911  
 OSWindows (option) ..... 108, 118, 228, 232  
 overpic (package) ..... 165, 1007

**P**

package:  
   2in1 ..... 636  
   2up ..... 636  
   a4 ..... 636  
   a4wide ..... 637  
   a5comb ..... 637  
   abstract ..... 136, 637  
   academicons ..... 639  
   accents ..... 640  
   accessibility ..... 641  
   accsupp ..... 642  
   acro ..... 642  
   acronym ..... 645  
   addlines ..... 647  
   adjmulticol ..... 646  
   afterpage ..... 647  
   algorithm2e ..... 647  
   algorithmicx ..... 172, 651  
   alltt ..... 652  
   amsmath ..... 653  
   amsthm ..... 656  
   anonchap ..... 661  
   ansize ..... 661  
   appendix ..... 136, 661  
   ar ..... 662  
   arabicfront ..... 664  
   array ..... 664  
   arydshln ..... 665  
   asymptote ..... 165, 667  
   atbegshi ..... 667  
   attachfile ..... 668  
   attachfile2 ..... 669  
   authblk ..... 136, 671  
   autobreak ..... 672  
   autonum ..... 673  
   awesomebox ..... 674  
   axessibility ..... 675

axodraw2 ..... 676  
 babel ..... 176  
 backnaur ..... 676  
 backref ..... 676  
 balance ..... 677  
 bbding ..... 677  
 biblatex ..... 682  
 bibunits ..... 686  
 bigdelim ..... 171, 686  
 bigfoot ..... 687  
 bigstrut ..... 688  
 bitpattern ..... 688  
 blowup ..... 689  
 bm ..... 689  
 booklet ..... 690  
 bookmark ..... 690  
 booktabs ..... 690  
 bophook ..... 692  
 bounddvi ..... 693  
 boxedminipage ..... 693  
 boxedminipage2e ..... 693  
 braket ..... 694  
 breakurl ..... 694  
 breqn ..... 695  
 bsheaders ..... 696  
 bussproofs ..... 696  
 bxpapersize ..... 697  
 bytefield ..... 697  
 calc ..... 242  
 cancel ..... 697  
 canoniclayout ..... 698  
 capt-of ..... 523  
 caption ..... 172, 523, 699  
 caption3 ..... 701  
 cases ..... 703  
 centernot ..... 704  
 changebar ..... 704  
 changelayout ..... 705  
 changepage ..... 705  
 changes ..... 706  
 chappg ..... 708  
 chapterbib ..... 709  
 chemfig ..... 709  
 chemformula ..... 711  
 chemgreek ..... 716  
 chemmacros ..... 717  
 chemnum ..... 735  
 chkfloat ..... 736  
 chngpage ..... 736  
 cite ..... 736  
 citeref ..... 737  
 CJK ..... 737  
 CJKutf8 ..... 737  
 cleveref ..... 132, 738  
 clrdblpg ..... 741

|                |          |                 |          |
|----------------|----------|-----------------|----------|
| cm-super       | 101      | everyhook       | 242      |
| cmap           | 102      | everypage       | 779      |
| cmbright       | 741      | everyshi        | 780      |
| cmdtrack       | 742      | expl3           | 242      |
| colonequals    | 742      | extrarrows      | 780      |
| color          | 163, 743 | extramarks      | 780      |
| colortbl       | 171, 743 | fancybox        | 129, 781 |
| comment        | 237      | fancyhdr        | 786      |
| continue       | 745      | fancyref        | 787      |
| copyrightbox   | 745      | fancytabs       | 787      |
| crop           | 746      | fancyvrb        | 788      |
| ctable         | 746      | fbox            | 794      |
| cuted          | 749      | fewerfloatpages | 797      |
| cutwin         | 749      | figcaps         | 797      |
| dblfloatfix    | 750      | figsize         | 797      |
| dblfnote       | 750      | filecontents    | 243      |
| dcolumn        | 750      | fitbox          | 798      |
| decimal        | 751      | fix2col         | 798      |
| dejavu         | 101      | fixmath         | 799      |
| diagbox        | 751      | fixme           | 177, 799 |
| dingbat        | 753      | fixmetodonotes  | 800      |
| ditaa          | 182      | flafter         | 801      |
| DotArrow       | 754      | flippdf         | 801      |
| dotlessi       | 754      | float           | 172, 801 |
| dprogress      | 754      | floatflt        | 803      |
| draftcopy      | 755      | floatpag        | 804      |
| draftfigure    | 755      | floatrow        | 173, 804 |
| draftwatermark | 756      | fltrace         | 809      |
| drftcite       | 756      | flushend        | 810      |
| easy-todo      | 756      | fnbreak         | 810      |
| ebook          | 757      | fncychap        | 810      |
| econometrics   | 758      | fnlineno        | 811      |
| ed             | 760      | fnpara          | 811      |
| ellipsis       | 761      | fnpos           | 812      |
| embrac         | 761      | fontawesome     | 812      |
| emptypage      | 762      | fontawesome5    | 813      |
| endfloat       | 762      | fontaxes        | 814      |
| endheads       | 763      | fontenc         | 102, 814 |
| endnotes       | 137, 764 | fontspec        | 102, 239 |
| engtlc         | 765      | footmisc        | 815      |
| enumerate      | 769      | footnote        | 816      |
| enumitem       | 769      | footnotebackref | 817      |
| environ        | 244      | footnotehyper   | 817      |
| epigraph       | 770      | footnoterange   | 817      |
| epsfig         | 771      | footnpag        | 817      |
| epstopdf       | 164, 771 | foreign         | 818      |
| epstopdf-base  | 772      | forest          | 818      |
| eqlist         | 773      | fouridx         | 819      |
| eqparbox       | 773      | fourier         | 819      |
| errata         | 774      | framed          | 821      |
| eso-pic        | 775      | ftcap           | 823      |
| esvect         | 776      | ftnright        | 823      |
| etoc           | 776      | fullminipage    | 823      |
| etoolbox       | 206      | fullpage        | 824      |
| eurosym        | 779      | fullwidth       | 824      |

|                 |               |                                     |                |
|-----------------|---------------|-------------------------------------|----------------|
| fvextra         | 824           | libertinustlmath                    | 891            |
| fwlw            | 827           | lineno                              | 898            |
| gensymb         | 828           | lips                                | 900            |
| gentombow       | 828           | listings                            | 900            |
| geometry        | 240, 829      | listliketab                         | 905            |
| getttitlestring | 242           | lltjext                             | 905            |
| ghsystem        | 829           | lmodern                             | 101, 102       |
| gindex          | 141, 830      | longtable                           | 169, 906       |
| gloss           | 137, 831      | lscap                               | 909            |
| glossaries      | 138, 831      | ltablex                             | 909            |
| gmeometric      | 833           | ltxcaption                          | 910            |
| graphics        | 161, 834      | ltxgrid                             | 910            |
| graphicx        | 161, 846      | ltxtable                            | 910            |
| grffile         | 163, 846      | lua-check-hyphen                    | 911            |
| grid            | 847           | lua-visual-debug                    | 911            |
| grid-system     | 847           | luacolor                            | 911            |
| gridset         | 847           | luamplib                            | 911            |
| hang            | 848           | luatexko                            | 912            |
| hanging         | 849           | luatodonotes                        | 177, 914       |
| hepunits        | 850           | lwarp                               | 104            |
| hhline          | 852           | lwarp-common-mathjax-letters        | 1262           |
| hhtensor        | 852           | lwarp-common-mathjax-newpctxmath    | 1269           |
| hybmssec        | 853           | lwarp-common-mathjax-nonunicode     | 1274           |
| hypcap          | 853           | lwarp-common-mathjax-overlaysymbols | 1277           |
| hypdestopt      | 853           | lwarp-common-multimedia             | 1257           |
| hypernat        | 854           | lwarp-patch-komascript              | 1226           |
| hyperref        | 133, 511, 854 | lwarp-patch-memoir                  | 1228           |
| hyperxmp        | 863           | lyluatex                            | 916            |
| hyphenat        | 864           | magaz                               | 918            |
| idxlayout       | 864           | makeidx                             | 153, 918, 1162 |
| ifoddpaper      | 865           | manyfoot                            | 919            |
| ifplatform      | 206           | marginal                            | 921            |
| imakeidx        | 866           | marginfit                           | 921            |
| indentfirst     | 369           | marginfix                           | 921            |
| index           | 870           | marginnote                          | 922            |
| inputenc        | 102           | marvosym                            | 922            |
| inputenx        | 102           | mathalpha                           | 923            |
| inputtrc        | 871           | mathastext                          | 923            |
| intopdf         | 872           | mathcomp                            | 924            |
| jurabib         | 872           | mathdesign                          | 925            |
| karnaugh-map    | 873           | mathdots                            | 926            |
| keyfloat        | 173, 876      | mathfixs                            | 927            |
| keystroke       | 882           | mathpazo                            | 927            |
| kotex           | 178           | mathptmx                            | 928            |
| kpfonts         | 883           | mathspec                            | 928            |
| kpfonts-otf     | 885           | mathtools                           | 160, 930       |
| kvoptions       | 230           | mcaption                            | 937            |
| layaureo        | 886           | mdframed                            | 130, 937       |
| layout          | 886           | media9                              | 165, 946       |
| layouts         | 887           | memhfixc                            | 948            |
| leading         | 889           | menukeys                            | 948            |
| leftidx         | 890           | metalogo                            | 949            |
| letltxmacro     | 206           | metalogox                           | 950            |
| letterspace     | 890           |                                     |                |
| lettrine        | 890           |                                     |                |

|                |           |                  |           |
|----------------|-----------|------------------|-----------|
| mhchem         | 950       | paralist         | 1009      |
| microtype      | 239, 953  | parallel         | 1010      |
| midfloat       | 954       | parcolumns       | 1012      |
| midpage        | 954       | parnotes         | 1013      |
| minibox        | 954       | parskip          | 1015      |
| minitoc        | 955       | pbox             | 1015      |
| minted         | 955       | pdfcol           | 1015      |
| mismatch       | 956       | pdfcolfoot       | 1016      |
| mleftright     | 960       | pdfcolmk         | 1016      |
| mmap           | 102       | pdfcolparallel   | 1016      |
| morefloats     | 960       | pdfcolparcolumns | 1017      |
| moreverb       | 961       | pdfcomment       | 1017      |
| movie15        | 165, 962  | pdfcrypt         | 1018      |
| mparhack       | 963       | pdfscape         | 1018      |
| multibib       | 964       | pdfmarginpar     | 1019      |
| multicap       | 964       | pdfpages         | 1019      |
| multicol       | 964       | pdfprivacy       | 1021      |
| multicolrule   | 966       | pdfrender        | 1022      |
| multimedia     | 165, 966  | pdfsync          | 1022      |
| multiobjective | 967       | pdftricks        | 164, 1022 |
| multirow       | 968       | pdfx             | 1023      |
| multitoc       | 971       | perltex          | 181       |
| musicography   | 972       | perpage          | 1023      |
| nameauth       | 975       | pfnote           | 1024      |
| nameref        | 976       | phfqit           | 1025      |
| natbib         | 977       | physics          | 161, 1025 |
| nccfancyhdr    | 977       | physunits        | 1026      |
| nccfoots       | 978       | picinpar         | 1027      |
| nccmath        | 978       | pifont           | 1029      |
| needspace      | 980       | placeins         | 1030      |
| newclude       | 176       | plarydshln       | 1030      |
| newfloat       | 244       | plext            | 1030      |
| newpxmath      | 980       | plextarydshln    | 1031      |
| newtxmath      | 981       | plextcolortbl    | 1031      |
| newtxsf        | 982       | plimsoll         | 1032      |
| newunicodechar | 102       | polyglossia      | 177       |
| nextpage       | 983       | prelim2e         | 1032      |
| nfssect-cfr    | 983       | prettyref        | 1032      |
| nicefrac       | 161, 990  | preview          | 1033      |
| niceframe      | 990       | printlen         | 244       |
| noitcrul       | 991       | psfrag           | 164, 1033 |
| nolbreaks      | 991       | psfragx          | 1034      |
| nomencl        | 139, 991  | pst-eps          | 1034      |
| nonfloat       | 992       | pstool           | 164, 1035 |
| nonumonpart    | 992       | pstricks         | 164, 1035 |
| nopageno       | 992       | pxatbegshi       | 1036      |
| notes          | 993       | pxeveryshi       | 1036      |
| notespages     | 993       | pxfonts          | 1036      |
| nowidow        | 994       | pxftnright       | 1037      |
| ntheorem       | 159, 994  | pxjahyper        | 1037      |
| octave         | 1006      | pythontex        | 181       |
| overpic        | 165, 1007 | quotchap         | 1037      |
| pagegrid       | 1008      | quoting          | 1038      |
| pagenote       | 136, 1008 | ragged2e         | 1039      |
| pagesel        | 1009      | realscripts      | 1039      |

|                     |                |                |                     |
|---------------------|----------------|----------------|---------------------|
| refcheck            | 1043           | stabular       | 1096                |
| refcount            | 244            | stackengine    | 1097                |
| register            | 1043           | stackrel       | 1099                |
| resize              | 126, 1044      | statex2        | 1099                |
| repeatindex         | 1045           | statistics     | 1103                |
| repltext            | 1046           | statmath       | 1109                |
| resizegather        | 1046           | steinmetz      | 1110                |
| returntogrid        | 1047           | stfloats       | 1111                |
| rmathbr             | 1047           | struktex       | 1111                |
| rmpage              | 1047           | subcaption     | 172, 1112           |
| romanbar            | 1048           | subfig         | 173, 1112           |
| romanbarpagenumber  | 1048           | subfigure      | 1117                |
| rotating            | 1048           | subsupscripts  | 1118                |
| rotfloat            | 1049           | supertabular   | 171, 1119           |
| rterface            | 181            | svg            | 1120                |
| rviewport           | 1050           | swfigure       | 1121                |
| sagetex             | 181            | sympytex       | 181                 |
| savetrees           | 1050           | syntonly       | 1121                |
| scalegnt            | 1050           | tabfigures     | 1122                |
| scalereel           | 1050           | tablefootnote  | 1122                |
| schemata            | 1051           | tabls          | 1122                |
| scrextend           | 1052           | tabularx       | 1123                |
| scrhack             | 1056           | tabulary       | 1123                |
| scrlayer            | 1056           | tagpdf         | 1124                |
| scrlayer-notecolumn | 1057           | tascmac        | 1126                |
| scrlayer-scrpage    | 1058           | tcolorbox      | 130, 1128           |
| scrpage2            | 1059           | termcal        | 1133                |
| section             | 1060           | textarea       | 1134                |
| sectionbreak        | 1061           | textcomp       | 102, 125, 1134      |
| sectsty             | 1061           | textfit        | 1138                |
| selectp             | 1062           | textpos        | 1139                |
| semantic-markup     | 1062           | theorem        | 1139                |
| seqsplit            | 1063           | thinsp         | 1143                |
| setspace            | 1064           | thm-listof     | 1143                |
| shadethm            | 1065           | thm-restate    | 1144                |
| shadow              | 1065           | thmbox         | 1144                |
| shapepar            | 1066           | thmtools       | 1145                |
| showidx             | 1066           | threadcol      | 1146                |
| showkeys            | 1066           | threparttable  | 1146                |
| showtags            | 1067           | threparttablex | 170, 1147           |
| shuffle             | 1067           | thumb          | 1148                |
| sidecap             | 1068           | thumbs         | 1148                |
| sidenotes           | 1069           | tikz           | 163, 1148           |
| simplebnf           | 1070           | titleps        | 1150                |
| SIunits             | 1072           | titleref       | 1153                |
| siunitx             | 160, 586, 1079 | titlesec       | 1153                |
| slantsc             | 1090           | titletoc       | 1155                |
| slashed             | 1090           | titling        | 136, 1157           |
| soul                | 1091           | tochasic       | 1161                |
| soulpos             | 1092           | tocbibind      | 153, 154, 1162      |
| soulutf8            | 1093           | tocdata        | 1164                |
| splitbib            | 1093           | tocenter       | 1165                |
| splitidx            | 1094           | tocloft        | 136, 154, 661, 1165 |
| srcltx              | 1096           | tocstyle       | 1171                |
| srctex              | 1096           | todo           | 1172                |

|                    |                 |                                     |            |
|--------------------|-----------------|-------------------------------------|------------|
| todonotes          | 177, 1173       | xr                                  | 1219       |
| topcapt            | 1174            | xr-hyper                            | 1220       |
| tram               | 1175            | xstring                             | 244        |
| transparent        | 1175            | xtab                                | 171, 1220  |
| trimclip           | 1176            | xunicode                            | 1222       |
| trivfloat          | 172, 1176       | xurl                                | 1223       |
| truncate           | 1177            | xy                                  | 1223       |
| turnthepage        | 1177            | zhlineskip                          | 1224       |
| twoup              | 1178            | zwpagelayout                        | 1225       |
| txfonts            | 1178            | \PackageDiagramAltText              | 115, 11053 |
| txgreek            | 1178            | \pagebreak                          | 12980      |
| typearea           | 1179            | \pagecolor                          | 75         |
| typicons           | 1180            | pagegrid (package)                  | 1008       |
| ulem               | 1180            | pagenote (package)                  | 136, 1008  |
| umoline            | 1182            | \pagenumbering                      | 5863       |
| underscore         | 1183            | \pageref                            | 10023      |
| unicode-math       | 1183            | \pagerefPageFor                     | 10022      |
| units              | 161, 1187       | pagesel (package)                   | 1009       |
| unitsdef           | 1188            | \pagestyle                          | 5855       |
| upgreek            | 1189            | Pandoc (program)                    | 74         |
| upref              | 1189            | \paragraph                          | 7342       |
| url                | 133, 1190       | paralist (package)                  | 1009       |
| ushort             | 1190            | parallel (package)                  | 1010       |
| uspace             | 1190            | \parbox                             | 12325      |
| varioref           | 132, 1190       | parcolumns (package)                | 1012       |
| varwidth           | 245             | parnotes (package)                  | 1013       |
| verbatim           | 244             | \parsemulticolumnalignment          | 9274       |
| verse              | 176, 1191, 1192 | parskip (package)                   | 1015       |
| versonotes         | 1193            | \part                               | 7309       |
| vertbars           | 1193            | pbox (package)                      | 1015       |
| vmargin            | 1193            | pdfcol (package)                    | 1015       |
| vowel              | 1194            | pdfcolfoot (package)                | 1016       |
| vpe                | 1194            | pdfcolmk (package)                  | 1016       |
| vwcol              | 1195            | pdfcolparallel (package)            | 1016       |
| wallpaper          | 1197            | pdfcolparcolumns (package)          | 1017       |
| watermark          | 1197            | pdfcomment (package)                | 1017       |
| widetable          | 1198            | pdfcrop (program) [requirement]     | 77         |
| widows-and-orphans | 1198            | pdfcrypt (package)                  | 1018       |
| witharrows         | 1198            | pdfLaTeX (program) [requirement]    | 77         |
| wrapfig            | 1200            | pdfscape (package)                  | 1018       |
| xbmks              | 1201            | pdfmarginpar (package)              | 1019       |
| xcolor             | 163, 589, 1201  | pdfpages (package)                  | 1019       |
| xexchangebar       | 1212            | pdfprivacy (package)                | 1021       |
| xellipsis          | 1212            | pdfrender (package)                 | 1022       |
| xetexko-vertical   | 1213            | pdfseparate (program) [requirement] | 77, 82     |
| xfakebold          | 1213            | pdfsync (package)                   | 1022       |
| xfrac              | 1214            | pdftocairo (program)                | 162, 588   |
| xifthen            | 244             | pdftocairo (program) [requirement]  | 77, 82     |
| xltabular          | 1216            | pdftotext (program) [requirement]   | 77, 82     |
| xltxtra            | 1216            | pdftotextEnc (option)               | 108, 232   |
| xmpincl            | 1217            | pdftricks (package)                 | 164, 1022  |
| xparse             | 178, 242        | pdfx (package)                      | 1023       |
| xpatch             | 206             | perl (program) [requirement]        | 82         |
| xpiano             | 1217            | perltex (package)                   | 181        |
| xpinyin            | 1218            | perpage (package)                   | 1023       |



| <b>R</b>                                |                |
|-----------------------------------------|----------------|
| ragged2e (package) . . . . .            | 1039           |
| \raggedbottom . . . . .                 | 5859           |
| \raggedleft . . . . .                   | 11993          |
| \raggedright . . . . .                  | 11999          |
| \raisebox . . . . .                     | 12510          |
| realscripts (package) . . . . .         | 1039           |
| \ref . . . . .                          | 10011          |
| refcheck (package) . . . . .            | 1043           |
| refcount (package) . . . . .            | 244            |
| \reflectbox . . . . .                   | 389            |
| register (package) . . . . .            | 1043           |
| resize (package) . . . . .              | 126, 1044      |
| repeatindex (package) . . . . .         | 1045           |
| repltext (package) . . . . .            | 1046           |
| [requirement]:                          |                |
| LuaLaTeX (program) . . . . .            | 77             |
| MathJax (program) . . . . .             | 77             |
| pdfcrop (program) . . . . .             | 77             |
| pdfLaTeX (program) . . . . .            | 77             |
| pdfseparate (program) . . . . .         | 77, 82         |
| pdftocairo (program) . . . . .          | 77, 82         |
| pdftotext (program) . . . . .           | 77, 82         |
| perl (program) . . . . .                | 82             |
| XeLaTeX (program) . . . . .             | 77             |
| \RequirePackage . . . . .               | 1400           |
| \resizebox . . . . .                    | 398            |
| resizegather (package) . . . . .        | 1046           |
| \ResumeTabular . . . . .                | 9551           |
| returntogrid (package) . . . . .        | 1047           |
| \reversemarginpar . . . . .             | 6580           |
| \rightline . . . . .                    | 12007          |
| rmathbr (package) . . . . .             | 1047           |
| \rmfamily . . . . .                     | 12720          |
| rmpage (package) . . . . .              | 1047           |
| romanbar (package) . . . . .            | 1048           |
| romanbarpagenumber (package) . . . . .  | 1048           |
| \rotatebox . . . . .                    | 347            |
| rotating (package) . . . . .            | 1048           |
| rotfloat (package) . . . . .            | 1049           |
| \rowcolor . . . . .                     | 8752           |
| \rownum . . . . .                       | 8744           |
| rterface (package) . . . . .            | 181            |
| \rule . . . . .                         | 124, 12987     |
| rviewport (package) . . . . .           | 1050           |
| <b>S</b>                                |                |
| sagetex (package) . . . . .             | 181            |
| sample_project.css (file) . . . . .     | 117, 313       |
| savetrees (package) . . . . .           | 1050           |
| \sb . . . . .                           | 12798          |
| \scalebox . . . . .                     | 370            |
| scalefnt (package) . . . . .            | 1050           |
| scalereel (package) . . . . .           | 1050           |
| schemata (package) . . . . .            | 1051           |
| scrextend (package) . . . . .           | 1052           |
| scrhack (package) . . . . .             | 1056           |
| scrlayer (package) . . . . .            | 1056           |
| scrlayer-notecolumn (package) . . . . . | 1057           |
| scrlayer-scrpage (package) . . . . .    | 1058           |
| scrpge2 (package) . . . . .             | 1059           |
| \scshape . . . . .                      | 12745          |
| \section . . . . .                      | 7333           |
| section (package) . . . . .             | 1060           |
| sectionbreak (package) . . . . .        | 1061           |
| sectsty (package) . . . . .             | 1061           |
| selectp (package) . . . . .             | 1062           |
| semantic-markup (package) . . . . .     | 1062           |
| seqsplit (package) . . . . .            | 1063           |
| \SetHTMLFileNumber . . . . .            | 5667           |
| setspace (package) . . . . .            | 1064           |
| \sffamily . . . . .                     | 12725          |
| \sfrac . . . . .                        | 1214           |
| shadethm (package) . . . . .            | 1065           |
| shadow (package) . . . . .              | 1065           |
| shapepar (package) . . . . .            | 1066           |
| showidx (package) . . . . .             | 1066           |
| showkeys (package) . . . . .            | 1066           |
| showtags (package) . . . . .            | 1067           |
| shuffle (package) . . . . .             | 1067           |
| sidecap (package) . . . . .             | 1068           |
| sidenotes (package) . . . . .           | 1069           |
| SideTOCDepth (counter) . . . . .        | 110, 527       |
| \sitetocname . . . . .                  | 112, 10475     |
| simplebnf (package) . . . . .           | 1070           |
| \simplechapterdelim . . . . .           | 7102           |
| \sishape . . . . .                      | 12760          |
| SIunits (package) . . . . .             | 1072           |
| siunitx (package) . . . . .             | 160, 586, 1079 |
| slantsc (package) . . . . .             | 1090           |
| slashed (package) . . . . .             | 1090           |
| \sloppy . . . . .                       | 5861           |
| \slshape . . . . .                      | 12771          |
| soul (package) . . . . .                | 1091           |
| soulpos (package) . . . . .             | 1092           |
| soulutf8 (package) . . . . .            | 1093           |
| \sp . . . . .                           | 12797          |
| splitbib (package) . . . . .            | 1093           |
| splitidx (package) . . . . .            | 1094           |
| splitidx (program) . . . . .            | 142            |
| srcltx (package) . . . . .              | 1096           |
| srctex (package) . . . . .              | 1096           |
| \sscshape . . . . .                     | 12776          |
| stabular (package) . . . . .            | 1096           |
| stackengine (package) . . . . .         | 1097           |
| stackrel (package) . . . . .            | 1099           |
| \StartDefiningMath . . . . .            | 5625           |
| \StartDefiningTabulars . . . . .        | 5615           |
| statex2 (package) . . . . .             | 1099           |
| statistics (package) . . . . .          | 1103           |
| statmath (package) . . . . .            | 1109           |

|                                   |                |                                         |                     |
|-----------------------------------|----------------|-----------------------------------------|---------------------|
| steinmetz (package) . . . . .     | 1110           | \textsuperscript . . . . .              | 12799               |
| stfloats (package) . . . . .      | 1111           | \texttt . . . . .                       | 12577               |
| \StopDefiningMath . . . . .       | 5629           | \textulc . . . . .                      | 12609               |
| \StopDefiningTabulars . . . . .   | 5619           | \textup . . . . .                       | 12585               |
| struktex (package) . . . . .      | 1111           | \tfl@chapter@fix . . . . .              | 1177                |
| subcaption (package) . . . . .    | 172, 1112      | \thanks . . . . .                       | 121                 |
| subfig (package) . . . . .        | 173, 1112      | \thanksmarkseries . . . . .             | 92                  |
| subfigure (package) . . . . .     | 1117           | \theauthor . . . . .                    | 417                 |
| \subparagraph . . . . .           | 7345           | thebibliography (environment) . . . . . | 10831               |
| \subsection . . . . .             | 7336           | \thedata . . . . .                      | 417                 |
| \subsubsection . . . . .          | 7339           | \theHTMLSection . . . . .               | 7379                |
| subsupscripts (package) . . . . . | 1118           | \theHTMLTitleSection . . . . .          | 7378                |
| supertabular (package) . . . . .  | 171, 1119      | \theHTMLTitleSeparator . . . . .        | 7355                |
| svg (package) . . . . .           | 1120           | theindex (environment) . . . . .        | 10572               |
| swfigure (package) . . . . .      | 1121           | \thempfootnote . . . . .                | 6512                |
| sympytex (package) . . . . .      | 181            | theorem (package) . . . . .             | 1139                |
| syntonly (package) . . . . .      | 1121           | \thetitle . . . . .                     | 417                 |
| <b>T</b>                          |                |                                         |                     |
| tabbing (environment) . . . . .   | 7984           | thinsp (package) . . . . .              | 1143                |
| tabfigures (package) . . . . .    | 1122           | \ThisAltText . . . . .                  | 115, 11050          |
| tablefootnote (package) . . . . . | 1122           | \thispagestyle . . . . .                | 5856                |
| \tableofcontents . . . . .        | 114, 10405     | thm-listof (package) . . . . .          | 1143                |
| tabls (package) . . . . .         | 1122           | thm-restate (package) . . . . .         | 1144                |
| tabular (environment) . . . . .   | 9698           | thmbox (package) . . . . .              | 1144                |
| \TabularMacro . . . . .           | 9549           | thmtools (package) . . . . .            | 1145                |
| tabularx (package) . . . . .      | 1123           | threadcol (package) . . . . .           | 1146                |
| tabulary (package) . . . . .      | 1123           | threeparttable (package) . . . . .      | 1146                |
| tagpdf (package) . . . . .        | 1124           | threeparttablex (package) . . . . .     | 170, 1147           |
| tascmac (package) . . . . .       | 1126           | thumb (package) . . . . .               | 1148                |
| tcolorbox (package) . . . . .     | 130, 1128      | thumbs (package) . . . . .              | 1148                |
| termcal (package) . . . . .       | 1133           | tikz (package) . . . . .                | 163, 1148           |
| \TeX . . . . .                    | 13092          | \title . . . . .                        | 121, 6408           |
| TeX2page (program) . . . . .      | 73             | titlepage (environment) . . . . .       | 121, 7660           |
| TeX4ht (program) . . . . .        | 73             | titleps (package) . . . . .             | 1150                |
| TeXMaths (program) . . . . .      | 187            | titleref (package) . . . . .            | 1153                |
| textarea (package) . . . . .      | 1134           | titles (option) [tocloft] . . . . .     | 136                 |
| \textbf . . . . .                 | 12537          | titlesec (package) . . . . .            | 1153                |
| \textcolor . . . . .              | 62             | titletoc (package) . . . . .            | 1155                |
| textcomp (package) . . . . .      | 102, 125, 1134 | titling (package) . . . . .             | 136, 1157           |
| \texteb . . . . .                 | 12545          | titlingpage (environment) . . . . .     | 14, 121             |
| textfit (package) . . . . .       | 1138           | tocbasic (package) . . . . .            | 1161                |
| \textgreater . . . . .            | 5660           | [tocbibind]:                            |                     |
| \textit . . . . .                 | 12593          | numindex (option) . . . . .             | 154, 1162           |
| \textless . . . . .               | 5658           | tocbibind (package) . . . . .           | 153, 154, 1162      |
| \textlg . . . . .                 | 12553          | tocdata (package) . . . . .             | 1164                |
| \textmd . . . . .                 | 12529          | tocdepth (counter) . . . . .            | 110                 |
| \textnormal . . . . .             | 12644          | tocenter (package) . . . . .            | 1165                |
| textpos (package) . . . . .       | 1139           | [tocloft]:                              |                     |
| \textrm . . . . .                 | 12561          | titles (option) . . . . .               | 136                 |
| \textsc . . . . .                 | 12601          | tocloft (package) . . . . .             | 136, 154, 661, 1165 |
| \textsf . . . . .                 | 12569          | tocstyle (package) . . . . .            | 1171                |
| \textsi . . . . .                 | 12617          | todo (package) . . . . .                | 1172                |
| \textsl . . . . .                 | 12634          | todonotes (package) . . . . .           | 177, 1173           |
| \textssc . . . . .                | 12642          | topcapt (package) . . . . .             | 1174                |
| \textsubscript . . . . .          | 12803          | \tracinglwrap . . . . .                 | 201, 1561           |
|                                   |                | tram (package) . . . . .                | 1175                |

|                                           |                      |  |          |
|-------------------------------------------|----------------------|--|----------|
| transparent (package) . . . . .           | 1175                 |  |          |
| trimclip (package) . . . . .              | 1176                 |  |          |
| trivfloat (package) . . . . .             | 172, 1176            |  |          |
| truncate (package) . . . . .              | 1177                 |  |          |
| \ttfamily . . . . .                       | 12730                |  |          |
| TtH (program) . . . . .                   | 73                   |  |          |
| turnthepage (package) . . . . .           | 1177                 |  |          |
| tutorial.tex (file) . . . . .             | 83                   |  |          |
| twoup (package) . . . . .                 | 1178                 |  |          |
| txfonts (package) . . . . .               | 1178                 |  |          |
| txgreek (package) . . . . .               | 1178                 |  |          |
| typearea (package) . . . . .              | 1179                 |  |          |
| typicons (package) . . . . .              | 1180                 |  |          |
|                                           |                      |  |          |
|                                           |                      |  | <b>U</b> |
| \ulcshape . . . . .                       | 12752                |  |          |
| ulem (package) . . . . .                  | 1180                 |  |          |
| umoline (package) . . . . .               | 1182                 |  |          |
| \underline . . . . .                      | 12809                |  |          |
| underscore (package) . . . . .            | 1183                 |  |          |
| unicode-math (package) . . . . .          | 1183                 |  |          |
| units (package) . . . . .                 | 161, 1187            |  |          |
| unitsdef (package) . . . . .              | 1188                 |  |          |
| Unix (program) . . . . .                  | 118, 228             |  |          |
| \up . . . . .                             | 12807                |  |          |
| upgreek (package) . . . . .               | 1189                 |  |          |
| upref (package) . . . . .                 | 1189                 |  |          |
| \upshape . . . . .                        | 12735                |  |          |
| url (package) . . . . .                   | 133, 1190            |  |          |
| \UseMinipageWidths . . . . .              | 127, 595, 12222      |  |          |
| ushort (package) . . . . .                | 1190                 |  |          |
| usingOSWindows (boolean) . . . . .        | 229                  |  |          |
| uspace (package) . . . . .                | 1190                 |  |          |
|                                           |                      |  |          |
|                                           |                      |  | <b>V</b> |
| varioref (package) . . . . .              | 132, 1190            |  |          |
| varwidth (package) . . . . .              | 245                  |  |          |
| \verb . . . . .                           | 7914                 |  |          |
| verbatim (environment) . . . . .          | 7966                 |  |          |
| verbatim (package) . . . . .              | 244                  |  |          |
| \VerbatimHTMLWidth (length) . . . . .     | 428                  |  |          |
| \verbatiminput . . . . .                  | 7958                 |  |          |
| verse (environment) . . . . .             | 2, 7889              |  |          |
| verse (package) . . . . .                 | 176, 1191, 1192      |  |          |
| versionotes (package) . . . . .           | 1193                 |  |          |
| vertbars (package) . . . . .              | 1193                 |  |          |
| \vleftmargini (length) . . . . .          | 176, 427, 1191       |  |          |
| \vleftskip (length) . . . . .             | 176, 427, 1191, 1192 |  |          |
| vmargin (package) . . . . .               | 1193                 |  |          |
| vowel (package) . . . . .                 | 1194                 |  |          |
| vpe (package) . . . . .                   | 1194                 |  |          |
| \vrule . . . . .                          | 125                  |  |          |
| \vspace . . . . .                         | 124                  |  |          |
| wcol (package) . . . . .                  | 1195                 |  |          |
|                                           |                      |  |          |
|                                           |                      |  | <b>W</b> |
| wallpaper (package) . . . . .             | 1197                 |  |          |
| warpall (environment) . . . . .           | 119, 1136            |  |          |
| warpHTML (environment) . . . . .          | 116, 119, 1137       |  |          |
| warpHTML (option) . . . . .               | 108, 231             |  |          |
| \warpHTMLonly . . . . .                   | 116, 120, 1094       |  |          |
| warpingHTML (boolean) . . . . .           | 230                  |  |          |
| warpingprint (boolean) . . . . .          | 230                  |  |          |
| warpMathJax (environment) . . . . .       | 120, 1143            |  |          |
| warpprint (environment) . . . . .         | 115, 119, 1140       |  |          |
| warpprint (option) . . . . .              | 108, 230             |  |          |
| \warpprintonly . . . . .                  | 116, 120, 1093       |  |          |
| watermark (package) . . . . .             | 1197                 |  |          |
| widetable (package) . . . . .             | 1198                 |  |          |
| widows-and-orphans (package) . . . . .    | 1198                 |  |          |
| Windows (program) . . . . .               | 118, 228             |  |          |
| witharrows (package) . . . . .            | 1198                 |  |          |
| Word (program) . . . . .                  | 74                   |  |          |
| WPMarkFloats (boolean) . . . . .          | 186, 259             |  |          |
| WPMarkLOFT (boolean) . . . . .            | 187, 260             |  |          |
| WPMarkMath (boolean) . . . . .            | 187, 260             |  |          |
| WPMarkMinipages (boolean) . . . . .       | 187, 260             |  |          |
| WPMarkTOC (boolean) . . . . .             | 187, 260             |  |          |
| WPTitleHeading (boolean) . . . . .        | 188, 261             |  |          |
| wrapfig (package) . . . . .               | 1200                 |  |          |
|                                           |                      |  |          |
|                                           |                      |  | <b>X</b> |
| xbmks (package) . . . . .                 | 1201                 |  |          |
| xcolor (package) . . . . .                | 163, 589, 1201       |  |          |
| xexchangebar (package) . . . . .          | 1212                 |  |          |
| \XeLaTeX . . . . .                        | 13139                |  |          |
| XeLaTeX (program) [requirement] . . . . . | 77                   |  |          |
| xellipsis (package) . . . . .             | 1212                 |  |          |
| \XeTeX . . . . .                          | 13139                |  |          |
| xetexko-vertical (package) . . . . .      | 1213                 |  |          |
| xfakebold (package) . . . . .             | 1213                 |  |          |
| xfrac (package) . . . . .                 | 1214                 |  |          |
| \xfracHTMLfontsize . . . . .              | 2                    |  |          |
| xifthen (package) . . . . .               | 244                  |  |          |
| xindex (option) . . . . .                 | 106, 234             |  |          |
| xindex (program) . . . . .                | 140, 152             |  |          |
| xindexConfig (option) . . . . .           | 106, 152, 232        |  |          |
| xindy (option) . . . . .                  | 106, 233             |  |          |
| xindy (program) . . . . .                 | 140, 151             |  |          |
| xindyCodepage (option) . . . . .          | 106, 232             |  |          |
| xindyLanguage (option) . . . . .          | 106, 232             |  |          |
| xindyStyle (option) . . . . .             | 106, 152, 232        |  |          |
| xltable (package) . . . . .               | 1216                 |  |          |
| xltxtra (package) . . . . .               | 1216                 |  |          |
| xmpinl (package) . . . . .                | 1217                 |  |          |
| xparse (package) . . . . .                | 178, 242             |  |          |
| xpatch (package) . . . . .                | 206                  |  |          |
| xpiano (package) . . . . .                | 1217                 |  |          |
| xpinyin (package) . . . . .               | 1218                 |  |          |
| xr (package) . . . . .                    | 1219                 |  |          |
| xr-hyper (package) . . . . .              | 1220                 |  |          |

|                          |           |                              |      |
|--------------------------|-----------|------------------------------|------|
| xstring (package) .....  | 244       | xy (package) .....           | 1223 |
| xtab (package) .....     | 171, 1220 |                              |      |
| xunicode (package) ..... | 1222      |                              |      |
| xurl (package) .....     | 1223      |                              |      |
|                          |           | <b>Z</b>                     |      |
|                          |           | zhlineskip (package) .....   | 1224 |
|                          |           | zwpagelayout (package) ..... | 1225 |

# General Index

This is an index of instructions and concepts. Look here when wondering how to do something, and check the Troubleshooting Index when something goes wrong.

|                                              |          |
|----------------------------------------------|----------|
| <b>Symbols</b>                               |          |
| <code>\@ifnextchar</code> with MATHJAX ..... | 157      |
| <code>\@ifstar</code> with MATHJAX .....     | 157      |
| <code>\,</code> .....                        | 124      |
| <code>~</code> .....                         | 124      |
| <b>A</b>                                     |          |
| accents                                      |          |
| in section & file names .....                | 395      |
| accessibility .....                          | 99       |
| adapting                                     |          |
| class .....                                  | 193      |
| document .....                               | 98       |
| package .....                                | 192      |
| affiliation                                  |          |
| multiple authors .....                       | 135      |
| algorithmicx                                 |          |
| with newfloat, trivfloat .....               | 1177     |
| alt text .....                               | 99       |
| array                                        |          |
| mhchem .....                                 | 950      |
| audio .....                                  | 165      |
| author                                       |          |
| HTML meta tag .....                          | 122, 371 |
| multiple .....                               | 135      |
| <b>B</b>                                     |          |
| baseline                                     |          |
| tabular .....                                | 460      |
| bibliography                                 |          |
| HTML page and TOC .....                      | 135      |
| bitmapped fonts .....                        | 101      |
| bugs .....                                   | 195      |
| <b>C</b>                                     |          |
| <i>Calibre</i> .....                         | 183      |
| chemistry                                    |          |
| Greek symbols .....                          | 716      |
| class                                        |          |
| modifying for lwrap .....                    | 193      |
| code listings .....                          | 124      |
| compiling                                    |          |
| custom .....                                 | 179      |
| Computer Modern .....                        | 101      |
| converting                                   |          |
| class .....                                  | 193      |
| document .....                               | 98       |
| package .....                                | 192      |
| CSS                                          |          |
| class .....                                  | 118      |
| file selection .....                         | 117      |
| lwrap.css .....                              | 117      |
| per HTML page .....                          | 117      |
| project-specific changes .....               | 117      |
| span .....                                   | 118      |
| ctable .....                                 | 171      |
| <b>D</b>                                     |          |
| danger icon .....                            | 205      |
| debugging .....                              | 195      |
| HTML debug comments .....                    | 253      |
| tracing log .....                            | 253      |
| Deja Vu .....                                | 101      |
| description                                  |          |
| HTML meta tag .....                          | 121, 372 |
| display math                                 |          |
| complicated objects .....                    | 159      |
| document                                     |          |
| convert existing .....                       | 98       |
| documentation                                |          |
| compile .....                                | 191      |
| DVI L <sup>A</sup> T <sub>E</sub> X .....    | 93, 101  |
| dynamic math .....                           | 158, 159 |
| dynamic math expressions .....               | 342      |
| <b>E</b>                                     |          |
| endnotes                                     |          |
| HTML page and TOC .....                      | 135      |
| EPS image                                    |          |
| converting .....                             | 95       |
| using .....                                  | 161, 587 |
| EPUB                                         |          |
| conversion software .....                    | 183      |
| HTML conversion settings .....               | 183, 259 |
| equation numbering                           |          |
| MATHJAX .....                                | 156      |
| error messages .....                         | 195      |
| export                                       |          |
| to word processor .....                      | 185      |
| <b>F</b>                                     |          |
| FAQ .....                                    | 195      |
| filename                                     |          |
| accent in .....                              | 395      |

|                                  |                    |
|----------------------------------|--------------------|
| hashed                           | 555, 576           |
| international languages          | 175                |
| length                           | 112                |
| simplify                         | 131                |
| underscore in                    | 104, 126           |
| unique                           | 112                |
| font                             |                    |
| Computer Modern                  | 101                |
| Deja Vu                          | 101                |
| ligatures                        | 102                |
| packages                         | 102                |
| selection                        | 101                |
| size                             |                    |
| lateximage                       | 155, 573           |
| math, SVG                        | 155, 573           |
| xfrac                            | 1214               |
| type 1 vector                    | 101                |
| type 3 bitmapped                 | 101                |
| footnotes                        | 372                |
| MATHJAX                          | 133                |
| numbering                        | 133                |
| foreign                          |                    |
| section names                    | 175                |
| framed objects                   | 128                |
| Frequently Asked Questions       | 195                |
| <b>G</b>                         |                    |
| generator                        |                    |
| HTML meta tag                    | 409                |
| GIF images                       | 162, 588           |
| gindex                           | 141                |
| gloss                            | 137                |
| glossaries                       |                    |
| HTML page and TOC                | 135                |
| language                         | 138                |
| options                          | 138                |
| processing                       | 94                 |
| graphics                         |                    |
| file formats                     | 161, 587           |
| Greek                            |                    |
| chemistry symbols                | 716                |
| <b>H</b>                         |                    |
| hash                             |                    |
| SVG image filename               | 555, 576           |
| heading, word processor          | 188                |
| horizontal and vertical space    | 124                |
| horizontal rule                  | 125                |
| horizontal space                 |                    |
| between minipages                | 618                |
| \hrule                           | 125                |
| HTML                             |                    |
| alt text                         | 99                 |
| class                            | 118                |
| conversion settings              | 110                |
| debug comments                   | 253                |
| Epub                             | 183, 259           |
| word processor                   | 185, 259, 260      |
| conversion suggestions           | 123                |
| <div>                            | 118                |
| entities, conversion             | 124                |
| filename generation              | 116                |
| headings                         | 204                |
| meta tag                         |                    |
| author                           | 122, 371           |
| description                      | 121, 372           |
| generator                        | 409                |
| title                            | 113, 114, 122, 371 |
| viewport                         | 409                |
| selecting print/HTML definitions | 254                |
| <span>                           | 118                |
| style                            | 118                |
| tabular column conversion        | 461                |
| verbatim, in                     | 124                |
| hyperref                         |                    |
| and <i>xindy</i>                 | 139                |
| title text                       | 99                 |
| <b>I</b>                         |                    |
| icon                             |                    |
| warning                          | 205                |
| \@ifnextchar with MATHJAX        | 157                |
| \@ifnextstar with MATHJAX        | 157                |
| image                            |                    |
| alt text                         | 99                 |
| file formats                     | 161, 587           |
| GIF                              | 162, 588           |
| graphicx package                 | 587                |
| hashed filename                  | 555, 576           |
| PDF or EPS                       |                    |
| converting                       | 95, 162, 588       |
| using                            | 161, 587           |
| PNG and JPG                      | 162, 588           |
| processing                       | 319                |
| \includegraphics                 |                    |
| using                            | 161, 587           |
| index                            |                    |
| custom display styles            | 153                |
| formatting                       | 538                |
| gindex                           |                    |
| setup                            | 141                |
| HTML page and TOC                | 135                |
| <i>imakeidx</i>                  |                    |
| setup                            | 144                |
| <i>index</i>                     |                    |
| setup                            | 141                |
| letter headings                  | 866                |
| <i>makeindex</i>                 |                    |
| custom style file                | 150                |
| setup                            | 139                |
| memoir                           |                    |
| setup                            | 147                |

|                                  |               |
|----------------------------------|---------------|
| placement                        | 153           |
| placement and roc options        | 153, 1162     |
| processing                       | 87, 88, 139   |
| see, seealso, ranges             | 139           |
| source code                      | 139           |
| <i>splitidx</i>                  |               |
| setup                            | 142           |
| table of contents                | 153, 1162     |
| tocbibind                        | 153           |
| UTF-8                            | 103           |
| <i>xindex</i>                    |               |
| custom configuration file        | 152           |
| setup                            | 140           |
| <i>xindy</i>                     |               |
| custom style file                | 151           |
| and hyperref                     | 139           |
| setup                            | 140           |
| inline math                      |               |
| complicated objects              | 158           |
| international                    |               |
| section names                    | 175           |
| item                             |               |
| empty                            | 433           |
| <b>J</b>                         |               |
| JAVASCRIPT                       |               |
| MATHJAX                          | 154           |
| JPG images                       | 162, 588      |
| <b>L</b>                         |               |
| language                         |               |
| glossaries                       | 138           |
| localization                     | 99            |
| language HTML metadata           | 406           |
| lateximage                       |               |
| font size                        | 155, 573      |
| processing                       | 319           |
| Latin Modern font                | 101           |
| LIBREOffice                      |               |
| conversion recommendations       | 188           |
| import into                      | 185           |
| section headings                 | 188           |
| ligatures                        | 102, 239      |
| line numbers                     | 205           |
| link                             |               |
| home / previous / next page      | 114           |
| title text                       | 99            |
| list                             |               |
| empty item                       | 433           |
| filename                         | 126           |
| listings, program code           | 124           |
| locale                           | 182           |
| localization                     | 99            |
| Lua $\LaTeX$                     |               |
| detection                        | 206           |
| file & section names             | 395           |
| lwarp                            |               |
| compiling documentation          | 191           |
| loading                          | 104           |
| options                          | 104           |
| lwarp.ist                        |               |
| customizing                      | 150           |
| lwarp.xdy                        |               |
| customizing                      | 151           |
| <i>lwarpmk</i>                   |               |
| customizing                      | 194           |
| <b>M</b>                         |               |
| make utility                     | 182           |
| <i>makeindex</i>                 | 139           |
| customizing                      | 150           |
| margin                           |               |
| numbers                          | 205           |
| tags                             | 205           |
| markup languages                 | 74            |
| math                             |               |
| alt text                         | 99            |
| display with complicated objects | 159           |
| dynamic                          | 158, 159, 342 |
| MATHJAX                          | 156           |
| font size — SVG                  | 155, 573      |
| inline with complicated objects  | 158           |
| MATHJAX custom functions         | 156           |
| MATHJAX summary                  | 155           |
| mathjax option                   | 231           |
| mathsvg option                   | 231           |
| mhchem                           | 950           |
| SVG summary                      | 155           |
| word processor conversion        | 187           |
| MATHJAX                          |               |
| \@ifnextchar macros              | 157           |
| \@ifstar macros                  | 157           |
| accessibility                    | 99            |
| custom functions                 | 156           |
| custom script                    | 316           |
| equation numbering               | 156           |
| mathjax option                   | 231           |
| starred macros                   | 157           |
| summary                          | 155           |
| \mcolrowcell                     | 169           |
| MD5 hash                         |               |
| SVG image filename               | 555, 576      |
| memoir                           |               |
| framewithtitle, titledframe      | 175           |
| meta tag, HTML                   |               |
| author                           | 122, 371      |
| description                      | 121, 372      |
| generator                        | 409           |
| title                            | 122, 371      |
| viewport                         | 409           |
| minipage                         |               |
| framed                           | 128           |



|                        |          |                            |               |
|------------------------|----------|----------------------------|---------------|
| type 3 bitmapped fonts | 101      | viewport                   |               |
|                        |          | HTML meta tag              | 409           |
| <b>U</b>               |          |                            |               |
| underscore             |          | <b>W</b>                   |               |
| filename               | 104, 126 | warning icon               | 205           |
| Unicode                |          | word processor             |               |
| enhanced coverage      | 101      | conversion recommendations | 188           |
| file & section names   | 395      | HTML conversion settings   | 185, 259, 260 |
| input characters       | 222      | section headings           | 188           |
| selection              | 101      | <b>X</b>                   |               |
| UTF-8                  |          | xcite                      | 95            |
| enhanced coverage      | 101      | Xe $\LaTeX$                |               |
| file & section names   | 395      | detection                  | 206           |
| index                  | 103      | file & section names       | 395           |
| locale                 | 182      | <i>xindex</i>              | 140           |
| selection              | 101      | customizing                | 152           |
| utility                |          | <i>xindy</i>               | 140           |
| programs               | 76       | and hyperref               | 139           |
| <b>V</b>               |          |                            |               |
| vector fonts           | 101      | customizing                | 151           |
| verbatim               |          | xparse                     |               |
| code and HTML tags     | 124      | warnings                   | 178           |
| vertical space         | 124      | xr                         | 95            |
| video                  | 165      | xr-hyper                   | 95            |

# Troubleshooting Index

This index is a sorted reference of problems and solutions. In order to make it easier to locate a solution, the same issue may be addressed by more than one entry.

Entries with higher page numbers are often duplicates of entries with lower page numbers, as the same warning may occur within the user manual and again within the source code for a given package.

| A                       |                     | breqn                              |           |
|-------------------------|---------------------|------------------------------------|-----------|
| abstract                |                     | darray                             | 695       |
| missing TOC             | 136, 637            | bussproofs                         | 696       |
| accents                 |                     |                                    |           |
| file names              | 395                 |                                    |           |
| acro                    | 178                 |                                    |           |
| acronym                 |                     |                                    |           |
| multiply-defined labels | 645                 |                                    |           |
| \AddSubtitlePublished   | 424                 |                                    |           |
| affiliation             | 417                 |                                    |           |
| alt tags                | 159, 199            |                                    |           |
| AMSMath                 |                     |                                    |           |
| ntheorem                |                     |                                    |           |
| numbering               | 159, 995            |                                    |           |
| appendix                |                     |                                    |           |
| incorrect TOC link      | 136, 662            |                                    |           |
| array                   |                     |                                    |           |
| chemformula             | 178                 |                                    |           |
| MATHJAX                 | 157                 |                                    |           |
| arydshln                | 665                 |                                    |           |
| audio                   | 165                 |                                    |           |
| authblk                 |                     |                                    |           |
| \theauthor              | 416, 417            |                                    |           |
| titling                 | 136, 416, 671, 1157 |                                    |           |
| author                  |                     |                                    |           |
| affiliation             | 417                 |                                    |           |
| formatting              | 121                 |                                    |           |
| autonom                 | 673                 |                                    |           |
|                         |                     |                                    |           |
| B                       |                     | C                                  |           |
| babel                   |                     | <i>Calibre</i>                     |           |
| French                  | 176                 | Epub conversion                    | 183       |
| backref                 | 676                 | caption                            |           |
| backref                 | 133                 | numbering                          | 172       |
| bibliography            |                     | options                            | 123       |
| HTML page and TOC       | 135                 | chemfig                            | 178       |
| bibtex                  |                     | chemformula                        |           |
| \etaLchar               | 137                 | MATHJAX                            | 178, 711  |
| Improper \prevdepth     | 137                 | chemgreek                          |           |
| bigdelim                | 171, 686            | fontspec mapping                   | 716       |
| bigfoot                 | 135, 919            | text-mode symbols                  | 716       |
| booktabs                | 690                 | chemmacros                         |           |
| boxes                   | 126                 | \makepolymerdelims                 | 717       |
|                         |                     | redox reactions                    | 717       |
|                         |                     | Chinese                            |           |
|                         |                     | font                               | 124       |
|                         |                     | CJK                                |           |
|                         |                     | font                               | 124       |
|                         |                     | cleveref                           |           |
|                         |                     | cref reference format              | 159, 995  |
|                         |                     | cmbright                           | 741       |
|                         |                     | colortbl                           | 171, 743  |
|                         |                     | Command \textquoteright invalid in |           |
|                         |                     | math mode                          | 199       |
|                         |                     | comment                            | 174, 1229 |
|                         |                     | compiling                          |           |
|                         |                     | slow MATHJAX                       | 156       |
|                         |                     | cref reference format              | 159, 995  |
|                         |                     | cross reference                    |           |
|                         |                     | incorrect link                     | 200       |
|                         |                     | MATHJAX                            | 157       |
|                         |                     | missing                            | 199       |
|                         |                     | CSS                                | 201       |
|                         |                     | ctable                             | 171       |
|                         |                     |                                    |           |
|                         |                     | D                                  |           |
|                         |                     | ditaa                              | 182       |

|                                                                             |               |  |
|-----------------------------------------------------------------------------|---------------|--|
| documentation                                                               |               |  |
| index cross-references                                                      | 191           |  |
| dotless j                                                                   | 102           |  |
| dotlessj                                                                    | 197           |  |
| duplciate filename                                                          | 132           |  |
| <b>E</b>                                                                    |               |  |
| \endhead, etc.                                                              | 169           |  |
| endnotes                                                                    |               |  |
| HTML page and toc                                                           | 135           |  |
| numbering                                                                   | 137           |  |
| \ensuremath                                                                 | 198           |  |
| epstopdf                                                                    | 164, 772      |  |
| EPUB                                                                        |               |  |
| encoding                                                                    | 183           |  |
| page order                                                                  | 183           |  |
| search order                                                                | 183           |  |
| section breaks                                                              | 184           |  |
| equation numbering                                                          |               |  |
| MATHJAX                                                                     | 156           |  |
| error messages                                                              | 195           |  |
| \etalchar                                                                   | 137           |  |
| <b>F</b>                                                                    |               |  |
| fancybox                                                                    |               |  |
| \VerbatimFootnotes                                                          | 134, 782, 788 |  |
| fancyvrb                                                                    |               |  |
| \VerbatimFootnotes                                                          | 134, 782, 788 |  |
| figure                                                                      |               |  |
| macro in name                                                               | 198           |  |
| file                                                                        |               |  |
| inaccessible                                                                | 112           |  |
| multiple projects in directory                                              | 95            |  |
| File ended while scanning use of \next                                      | 197           |  |
| filename                                                                    |               |  |
| accents                                                                     | 395           |  |
| corrupted                                                                   | 131, 175      |  |
| duplicate                                                                   | 132           |  |
| international, UTF-8                                                        | 175           |  |
| Korean                                                                      | 178           |  |
| macro in name                                                               | 131           |  |
| math in                                                                     | 98, 132, 154  |  |
| Missing \$ inserted                                                         | 198           |  |
| fixme                                                                       | 177, 799      |  |
| float                                                                       |               |  |
| alignment                                                                   | 125, 172      |  |
| numbering                                                                   | 172           |  |
| out of sequence                                                             | 200           |  |
| floatrow                                                                    |               |  |
| \FBwidth and \FBheight                                                      | 173, 805      |  |
| with subfig                                                                 | 173, 805      |  |
| floatrow                                                                    |               |  |
| \ttboxed                                                                    | 166, 440      |  |
| font                                                                        |               |  |
| CJK                                                                         | 124           |  |
| JETBRAIN MONO                                                               | 102           |  |
| ligatures                                                                   | 102           |  |
| missing symbols                                                             | 125, 1135     |  |
| monospace                                                                   | 102           |  |
| package conflicts                                                           | 101           |  |
| selection                                                                   | 101           |  |
| small caps                                                                  | 124           |  |
| UTF-8                                                                       | 101           |  |
| fontspec                                                                    |               |  |
| with monospaced fonts                                                       | 102           |  |
| with Xe <sub>L</sub> AT <sub>E</sub> X, Lua <sub>L</sub> AT <sub>E</sub> X. | 101           |  |
| footmisc                                                                    | 134, 373      |  |
| footnote                                                                    |               |  |
| displaymath                                                                 | 134, 782, 788 |  |
| in math                                                                     | 134           |  |
| in sectioning command                                                       | 133           |  |
| MATHJAX                                                                     | 133           |  |
| memoir                                                                      | 134, 373      |  |
| numbering                                                                   | 133           |  |
| paragraph tags                                                              | 134, 782, 788 |  |
| sectioning, footmisc                                                        | 134, 373      |  |
| sectioning, verbatim                                                        | 134, 782, 788 |  |
| title                                                                       | 417           |  |
| verbatim                                                                    | 134           |  |
| \VerbatimFootnotes                                                          | 134, 782, 788 |  |
| forest                                                                      | 818           |  |
| formatting                                                                  |               |  |
| \bfseries etc.                                                              | 124, 605      |  |
| fourier                                                                     | 819           |  |
| frames                                                                      | 128           |  |
| framewithtitle                                                              | 175           |  |
| <b>G</b>                                                                    |               |  |
| gloss                                                                       | 137           |  |
| glossaries                                                                  |               |  |
| HTML page and toc                                                           | 135           |  |
| <i>makeglossaries</i> not found                                             | 138, 831      |  |
| page numbers                                                                | 138, 832      |  |
| style                                                                       | 138, 832      |  |
| graphics                                                                    |               |  |
| \rotatebox, \scalebox, \reflectbox                                          | 163, 589      |  |
| image format priorities                                                     | 162, 588      |  |
| images out of order                                                         | 89, 200       |  |
| multimedia                                                                  | 165           |  |
| optional arguments                                                          | 162, 588      |  |
| scale option                                                                | 98, 161, 587  |  |
| scaled                                                                      | 835           |  |
| viewport                                                                    | 162, 588      |  |
| Greek packages                                                              | 716           |  |
| grffile                                                                     | 163, 847      |  |
| <b>H</b>                                                                    |               |  |
| \hrule                                                                      | 125           |  |
| HTML                                                                        |               |  |
| &, <, >                                                                     | 124, 605      |  |
| alt tags                                                                    | 159           |  |

|                                        |                         |          |  |
|----------------------------------------|-------------------------|----------|--|
| author                                 | 372                     |          |  |
| corrupted                              | 102, 121, 126, 197, 201 |          |  |
| entities                               | 124, 605                |          |  |
| image appear as HTML code              | 89, 200                 |          |  |
| inaccessible pages                     | 112, 114                |          |  |
| starred section                        | 136                     |          |  |
| invalid                                | 124                     |          |  |
| missing pages                          |                         |          |  |
| filename not unique                    | 112                     |          |  |
| recompile                              | 201                     |          |  |
| SideTOCDepth and FileDepth             | 112                     |          |  |
| SideTOCDepth and tocdepth              | 112                     |          |  |
| page did not update                    | 112, 201                |          |  |
| settings                               |                         |          |  |
| changed                                | 110                     |          |  |
| undefined                              | 197                     |          |  |
| validation                             | 124                     |          |  |
| \HTMLAuthor                            | 372                     |          |  |
| HTMLIndexCmd                           |                         |          |  |
| filenames                              | 107                     |          |  |
| hyperref                               |                         |          |  |
| backref                                | 133                     |          |  |
| comments between arguments             | 133                     |          |  |
| incorrect link                         | 200                     |          |  |
| Token not allowed in a PDF string      | 199                     |          |  |
|                                        |                         | <b>I</b> |  |
| image                                  |                         |          |  |
| appears as HTML code                   | 89, 200                 |          |  |
| format priorities                      | 162, 588                |          |  |
| incorrect                              | 89, 200                 |          |  |
| svg math size and baseline             | 155                     |          |  |
| viewport                               | 162, 588                |          |  |
| Improper \prevdepth                    |                         |          |  |
| bibtex                                 | 137                     |          |  |
| boxes                                  | 198                     |          |  |
| \includegraphics                       |                         |          |  |
| optional arguments                     | 162, 588                |          |  |
| scale                                  | 98, 161, 587            |          |  |
| index                                  |                         |          |  |
| ?? and non-functional link             | 108                     |          |  |
| documentation references               | 191                     |          |  |
| empty                                  | 153                     |          |  |
| empty link                             | 132, 199                |          |  |
| formatting                             | 108, 538                |          |  |
| HTML page and toc                      | 135                     |          |  |
| missing entries                        | 139                     |          |  |
| numbers, not links                     | 244                     |          |  |
| reference ranges                       | 152                     |          |  |
| see and seealso                        | 152                     |          |  |
| styling references                     | 152                     |          |  |
| <i>xindy</i>                           |                         |          |  |
| and hyperref                           | 152                     |          |  |
| xstring bug                            | 244                     |          |  |
|                                        |                         | <b>J</b> |  |
| \j                                     | 102                     |          |  |
| Japanese                               |                         |          |  |
| font                                   | 124                     |          |  |
| JETBRAIN MONO                          | 102                     |          |  |
|                                        |                         | <b>K</b> |  |
| keyfloat                               | 173, 876                |          |  |
| Korean                                 |                         |          |  |
| font                                   | 124                     |          |  |
| kpfonts                                | 883                     |          |  |
| kpfonts-otf                            | 885                     |          |  |
|                                        |                         | <b>L</b> |  |
| label                                  |                         |          |  |
| \nameref empty                         | 132, 199                |          |  |
| characters                             | 132, 199                |          |  |
| Label(s) may have changed              | 198                     |          |  |
| LaTeX was unable to guess the total... | 198                     |          |  |
| \LateximageFontSizeName                | 574                     |          |  |
| Leaders not followed by proper glue    | 198                     |          |  |
| <i>LibreOffice</i>                     |                         |          |  |
| import                                 | 185                     |          |  |
| ligatures                              | 102                     |          |  |
| LINUX                                  | 118, 228                |          |  |
| list                                   |                         |          |  |
| empty item                             | 125, 433                |          |  |
| listings                               | 200                     |          |  |
| lists                                  |                         |          |  |
| label formatting                       | 433                     |          |  |
| locale                                 | 182                     |          |  |
| longtable                              |                         |          |  |
| \endhead, etc.                         | 169                     |          |  |
| Lrbox                                  | 126                     |          |  |
| ltxtable                               |                         |          |  |
| numbering                              | 910                     |          |  |
| luaL <sup>A</sup> T <sub>E</sub> X     | 101                     |          |  |
| \LWRbackslash                          | 179                     |          |  |
| \LWRdollar                             | 179                     |          |  |
| \LWRhash                               | 179                     |          |  |
| \LWRopquote                            | 179                     |          |  |
| \LWRopseq                              | 179                     |          |  |
| \LWRpercent                            | 179                     |          |  |
|                                        |                         | <b>M</b> |  |
| MAC OS                                 | 118, 228                |          |  |
| <i>makeglossaries</i>                  |                         |          |  |
| not found                              | 138, 831                |          |  |
| \makeLabel                             | 433                     |          |  |
| manyfoot                               | 135, 919                |          |  |
| \marginpar                             | 126, 378                |          |  |
| math                                   |                         |          |  |
| \ifnextchar macros and MATHJAX         | 157                     |          |  |
| \ifstar macros and MATHJAX             | 157                     |          |  |
| alt tags                               | 199                     |          |  |
| appears as HTML code                   | 89, 200                 |          |  |

|                                                      |                 |
|------------------------------------------------------|-----------------|
| baseline incorrect                                   | 155             |
| chemformula                                          | 178             |
| Command <code>\textquoteright</code> invalid         |                 |
| in math mode                                         | 199             |
| custom macros                                        | 198             |
| dynamic                                              | 342             |
| equation numbering                                   |                 |
| MATHJAX                                              | 156             |
| ntheorem                                             | 159, 995        |
| file name                                            | 98, 132, 154    |
| footnote                                             | 134             |
| MATHJAX                                              | 133             |
| in $\TeX$ boxes                                      | 155             |
| incorrect                                            | 89, 200, 342    |
| non-math contents                                    | 199             |
| section name                                         | 98, 132, 154    |
| size incorrect                                       | 155             |
| slow or failed compile                               | 199             |
| MATHJAX                                              | 157             |
| tabbing                                              | 166, 431        |
| Tikz                                                 | 159             |
| mathalpha                                            | 923             |
| mathdesign                                           | 925             |
| MATHJAX                                              |                 |
| <code>\ifnextchar</code> macros                      | 157             |
| <code>\ifstar</code> macros                          | 157             |
| arydshn                                              | 665             |
| booktabs                                             | 690             |
| chemformula                                          | 178, 711        |
| custom script                                        | 316             |
| equation numbering                                   | 156             |
| errors                                               | 159, 199, 342   |
| footnotes                                            | 133             |
| mathtools                                            | 160, 930        |
| mhchem                                               | 950             |
| <code>\multicolumn</code>                            | 157             |
| <code>\multirow</code>                               | 157, 169, 968   |
| physics                                              | 161             |
| references                                           | 157             |
| siunitx                                              | 160, 586, 1079  |
| slow compilation                                     | 156             |
| starred macros                                       | 157             |
| unicode-math                                         | 1183            |
| unsupported packages                                 | 158, 199        |
| mathpazo                                             | 927             |
| mathptmx                                             | 928             |
| mathspec                                             | 929             |
| mathtools                                            | 160, 930        |
| <code>\mcolrowcell</code>                            | 169             |
| media9                                               | 165             |
| memoir                                               |                 |
| framewithtitle, titledframe                          | 175             |
| captions                                             | 174, 1228       |
| comment                                              | 174, 1229       |
| footmisc                                             | 134, 373        |
| options clash                                        | 174, 1228       |
| page notes                                           | 174, 1229       |
| verse                                                |                 |
| margin                                               | 176, 427, 1191  |
| version clash                                        | 174, 1229       |
| mhchem                                               |                 |
| MATHJAX                                              | 950             |
| nested dollar signs                                  | 950             |
| minipage                                             |                 |
| alignment                                            | 127, 595        |
| horizontal space between                             | 618             |
| in a span                                            | 127, 594        |
| inline                                               | 126, 594        |
| multicols, width in                                  | 127, 595        |
| size                                                 | 127, 594        |
| tabular, width in                                    | 127, 595        |
| minted                                               | 955             |
| Misplaced <code>\noalign</code>                      | 170, 906        |
| tabular                                              |                 |
| rules                                                | 168, 441        |
| Misplaced <code>\omit</code>                         |                 |
| tabular                                              | 256             |
| Misplaced alignment tab character &                  |                 |
| ctable                                               | 171, 746        |
| floatrow                                             | 173, 804        |
| frames                                               | 128             |
| supertabular                                         | 171, 1119, 1220 |
| tabular                                              |                 |
| macros                                               | 166, 341, 440   |
| Missing \$ inserted                                  |                 |
| filename or URL                                      | 198             |
| Missing <code>\begin{document}</code>                |                 |
| package options                                      | 123             |
| morewrites                                           | 153, 198        |
| movie15                                              | 165             |
| <code>\mrowcell</code>                               | 169             |
| MS-WINDOWS                                           | 118, 228        |
| multicol                                             |                 |
| <code>\linewidth</code>                              | 127, 595        |
| <code>\multicolumn</code>                            |                 |
| MATHJAX                                              | 157             |
| multimedia                                           | 165             |
| multiple projects in a directory                     | 95              |
| multiply-defined labels                              |                 |
| acronym                                              | 645             |
| <code>\multirow</code> and <code>\multicolumn</code> | 169, 968        |
| multirow                                             |                 |
| MATHJAX                                              | 157, 169, 968   |
| <code>\mrowcell</code> and <code>\mcolrowcell</code> | 169             |
| <b>N</b>                                             |                 |
| newclude                                             | 176             |
| newpxmath                                            | 980             |
| newtxmath                                            | 981             |
| newtxsf                                              | 982             |
| nicefrac                                             | 161             |





## Index of Indexes

|                |          |      |                       |          |      |
|----------------|----------|------|-----------------------|----------|------|
|                | <b>C</b> |      |                       | <b>I</b> |      |
| Change History | .....    | 1279 | Index of Objects      | .....    | 1317 |
|                | <b>G</b> |      |                       | <b>T</b> |      |
| General Index  | .....    | 1341 | Troubleshooting Index | .....    | 1346 |